

Buddy Garcia, *Chairman*
Larry R. Soward, *Commissioner*
Bryan W. Shaw, Ph.D., *Commissioner*
Glenn Shankle, *Executive Director*



TEXAS COMMISSION ON ENVIRONMENTAL QUALITY

Protecting Texas by Reducing and Preventing Pollution

March 28, 2008

Mr. Michael J. Zetlmeisl
Baker Petrolite
12645 West Airport Blvd.
Sugar Land TX 77478

Re: Alternative Diesel Fuel Formulation Approval Notification

Dear Mr. Zetlmeisl:

The Texas Commission on Environmental Quality (TCEQ) has approved the alternative diesel fuel formulation for Texas low emission diesel fuel (TxLED) consisting of diesel fuel as defined in the TCEQ regulations under Title 30 Texas Administrative Code (30 TAC) §114.6 treated with 9.5 milliliters (ml) of the Baker Petrolite NOxitrol® 1000 Additive per gallon of diesel fuel in accordance with the TCEQ regulations specified under 30 TAC §114.315(c). This approval is based upon the following findings:

- The emissions testing performed by the Southwest Research Institute (SwRI) in San Antonio, Texas, was conducted in accordance with the procedures specified in the TCEQ regulations under 30 TAC §114.315(c).
- The emissions of nitrogen oxides (NO_x) and particulate matter (PM) from the 21 eligible candidate fuel emissions tests were less than the NO_x and PM emissions from the 21 TxLED reference fuel emissions tests as determined in accordance with the emissions comparison calculations specified in the TCEQ regulations under 30 TAC §114.315(c)(5). In addition, the average emissions of total hydrocarbons (THC) and non-methane hydrocarbons (NMHC) recorded during the candidate fuel testing did not exceed the test engine's applicable emission standards.
- The comparative analysis of the emission test data from the testing of the Baker Petrolite's formulation indicate it has met the conditions specified in the TCEQ regulations under 30 TAC §114.315(c)(5) to be approved by the TCEQ as an alternative diesel formulation for TxLED.

This approval only applies to the alternative diesel fuel formulation consisting of diesel fuel as defined in the TCEQ regulations under 30 TAC §114.6 treated with 9.5 ml of the Baker Petrolite NOxitrol® 1000 Additive per gallon of diesel fuel and as described in the TCEQ's Approval Notification issued under the following notice number:

- TCEQ assigned identification number: TXLED-A-00015.

As a TCEQ approved alternative diesel fuel formulation, diesel fuel producers may use diesel fuel as defined in the TCEQ regulations under 30 TAC §114.6 treated with 9.5 ml of the Baker Petrolite NOxitrol® 1000 Additive per gallon of diesel fuel for compliance with the TxLED fuel content

Mr. Michael J. Zetlmeisl
Page 2
March 28, 2008

requirements as provided in the TCEQ regulations under 30 TAC §114.312(f). Producers using this product will be required to comply with the registration requirements specified in the TCEQ regulations under 30 TAC §114.314 and the appropriate monitoring, recordkeeping, and reporting requirements specified in the TCEQ regulations under 30 TAC §114.316.

This approval is subject to the actual emissions performance of diesel-powered engines using diesel fuel as defined in the TCEQ regulations under 30 TAC §114.6 treated with 9.5 ml of the Baker Petrolite NOxitol® 1000 Additive per gallon of diesel fuel. Evidence that diesel fuel as defined in the TCEQ regulations under 30 TAC §114.6 treated with 9.5 ml of the Baker Petrolite NOxitol® 1000 Additive per gallon of diesel fuel does not result in emissions that are equivalent to or better than diesel fuel meeting the cetane number and aromatic hydrocarbons content requirements of TxLED may result in the revocation of this approval or other appropriate enforcement action. This approval is also subject to proper treatment and storage of diesel fuel as defined in the TCEQ regulations under 30 TAC §114.6 treated with 9.5 ml of the Baker Petrolite NOxitol® 1000 Additive per gallon of diesel fuel.

Baker Petrolite is required to provide detailed written instructions regarding the specific storage requirements, blending methods, and treatment rate to any producer using this approved alternative diesel fuel formulation for compliance with the TxLED requirements that are necessary to ensure proper emissions performance of the diesel fuel as defined in the TCEQ regulations under 30 TAC §114.6 treated with 9.5 ml of the Baker Petrolite NOxitol® 1000 Additive per gallon of diesel fuel. Improper storage, blending, and/or treatment rate of diesel fuel as defined in the TCEQ regulations under 30 TAC §114.6 treated with 9.5 ml of the Baker Petrolite NOxitol® 1000 Additive per gallon of diesel fuel may result in enforcement action.

Enclosed with this letter is the Approval Notification documenting TCEQ's approval of the formulation consisting of diesel fuel as defined in the TCEQ regulations under 30 TAC §114.6 treated with 9.5 ml of the Baker Petrolite NOxitol® 1000 Additive per gallon of diesel fuel.

This letter and the Approval Notification document will be posted to the TCEQ website for public notice at the following link: <http://www.tceq.state.tx.us/implementation/air/sip/cleandiesel.html>.

If you have any additional questions or need further assistance in regards to this process, please contact Mr. Morris Brown in the TCEQ's Air Quality Planning Section at (512) 239-1438 or mbrown@tceq.state.tx.us.

Sincerely,



David C. Schanbacher, P.E.
Chief Engineer
Texas Commission on Environmental Quality

DS/MB/sy