

## 40 CFR Part 60, Subpart H - Requirements Reference Tables

### Subpart H Standards

- [§60.82\(a\)](#) No excess of 2 kg per metric ton of acid produced shall be discharged to atmosphere
- [§60.83\(a\)\(1\)](#) Acid mist, H<sub>2</sub>SO<sub>4</sub>, in excess of 0.075 kg/metric ton produced shall not be emitted
- [§60.83\(a\)\(2\)](#) Affected facilities shall not exhibit 10% opacity or greater

These relationship entry screens and flowcharts are for use by sources subject to the Texas Federal Operating Permits Program only and are subject to revision.

Last Modified: October 22, 1997



Document: Below is a Relationship Entry Screen Table describing 40 CFR Part 60, Subpart H. It will likely not be accessible using a screen reader. For the text of the statute/rule, please go to [40 CFR Part 60, Subpart H](#)

Standard	Monitoring/Testing	Recordkeeping	Reporting
§60.82(a)	[R]§60.84(a) [D]§60.84(b) [D]§60.84(c) [D]§60.84(d) [R]§60.84(e) [T][R]§60.85(a) [R]§60.85(b)(1) [R]§60.85(b)(2) [R]§60.85(b)(3) [GD]§60.85(c)	[D]§60.84(c)	[R]§60.84(e)
§60.83(a)(1)	[T][R]§60.85(a) [R]§60.85(b)(1) [R]§60.85(b)(2) [R]§60.85(b)(3) [GD]§60.85(c)		
§60.83(a)(2)	[T][R]§60.85(a) [R]§60.85(b)(4)		