

40 CFR Part 60, Subpart PP - Requirements Reference Tables

Subpart PP Standards

- [§60.422](#) Ammonium sulfate dryers must emit less than or equal to 0.15kg per Mg (0.30 lbs per ton) of particulate.
- [§60.422](#) Ammonium sulfate dryers must have an opacity of less than or equal to 15%

These relationship entry screens and flowcharts are for use by sources subject to the Texas Federal Operating Permits Program only and are subject to revision.

Last Modified: December 22, 2004



Document: Below is a Relationship Entry Screen Table describing 40 CFR Part 60, Subpart PP. It will likely not be accessible using a screen reader. For the text of the statute/rule, please go to [40 CFR Part 60, Subpart PP](#)

Standard	Monitoring/Testing	Recordkeeping	Reporting
§60.422 PM Limit	[R]§60.423(a) [R]§60.423(b) [T][R]§60.424(a) [T][R]§60.424(b) [T][R]§60.424(b)(1) [T][R]§60.424(b)(2) [T][R]§60.424(b)(3) [T][D]§60.424(b)(3)(i) [T][D]§60.424(b)(3)(ii)	[R]§60.423(b)	
§60.422 PM (Opacity) Limit	[R]§60.423(a) [R]§60.423(b) [T][R]§60.424(a) [T][R]§60.424(b) [T][R]§60.424(b)(4)	[R]§60.423(b)	