

FEDERAL OPERATING PERMIT

A FEDERAL OPERATING PERMIT IS HEREBY ISSUED TO

Valero Refining - Texas, L.P.

AUTHORIZING THE OPERATION OF

Houston Refinery
Petroleum Refining

LOCATED AT

Harris County, Texas

Latitude 29° 43' 24" Longitude 95° 15' 11"

Regulated Entity Number: RN100219310

This permit is issued in accordance with and subject to the Texas Clean Air Act (TCAA), Chapter 382 of the Texas Health and Safety Code and Title 30 Texas Administrative Code Chapter 122 (30 TAC Chapter 122), Federal Operating Permits. Under 30 TAC Chapter 122, this permit constitutes the permit holder's authority to operate the site and emission units listed in this permit. Operations of the site and emission units listed in this permit are subject to all additional rules or amended rules and orders of the Commission pursuant to the TCAA.

This permit does not relieve the permit holder from the responsibility of obtaining New Source Review authorization for new, modified, or existing facilities in accordance with 30 TAC Chapter 116, Control of Air Pollution by Permits for New Construction or Modification.

The site and emission units authorized by this permit shall be operated in accordance with 30 TAC Chapter 122, the general terms and conditions, special terms and conditions, and attachments contained herein.

This permit shall expire five years from the date of issuance. The renewal requirements specified in 30 TAC § 122.241 must be satisfied in order to renew the authorization to operate the site and emission units.

Permit No: O1381 Issuance Date: October 13, 2011

For the Commission

Table of Contents

Section	Page
General Terms and Conditions	1
Special Terms and Conditions	1
Emission Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting	1
Additional Monitoring Requirements	15
New Source Review Authorization Requirements	16
Compliance Requirements.....	17
Risk Management Plan	19
Protection of Stratospheric Ozone.....	19
Permit Location.....	19
Permit Shield (30 TAC § 122.148)	20
Attachments	21
Applicable Requirements Summary	22
Additional Monitoring Requirements	250
Permit Shield.....	269
New Source Review Authorization References.....	289
Appendix A	316
Acronym List	317
Appendix B	318
New Source Review Permits 19637 and PSDTX767M2	319

General Terms and Conditions

The permit holder shall comply with all terms and conditions contained in 30 TAC § 122.143 (General Terms and Conditions), 30 TAC § 122.144 (Recordkeeping Terms and Conditions), 30 TAC § 122.145 (Reporting Terms and Conditions), and 30 TAC § 122.146 (Compliance Certification Terms and Conditions).

In accordance with 30 TAC § 122.144(1), records of required monitoring data and support information required by this permit, or any applicable requirement codified in this permit, are required to be maintained for a period of five years from the date of the monitoring report, sample, or application unless a longer data retention period is specified in an applicable requirement. The five year record retention period supersedes any less stringent retention requirement that may be specified in a condition of a permit identified in the New Source Review Authorization attachment.

If the permit holder chooses to demonstrate that this permit is no longer required, a written request to void this permit shall be submitted to the Texas Commission on Environmental Quality (TCEQ) by the Responsible Official in accordance with 30 TAC § 122.161(e). The permit holder shall comply with the permit's requirements, including compliance certification and deviation reporting, until notified by the TCEQ that this permit is voided.

The permit holder shall comply with 30 TAC Chapter 116 by obtaining a New Source Review authorization prior to new construction or modification of emission units located in the area covered by this permit.

All reports required by this permit must include in the submittal a cover letter which identifies the following information: company name, TCEQ regulated entity number, air account number (if assigned), site name, area name (if applicable), and Air Permits Division permit number(s).

Special Terms and Conditions: Emission Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting

1. Permit holder shall comply with the following requirements:
 - A. Emission units (including groups and processes) in the Applicable Requirements Summary attachment shall meet the limitations, standards, equipment specifications, monitoring, recordkeeping, reporting, testing, and other requirements listed in the Applicable Requirements Summary attachment to assure compliance with the permit.
 - B. The textual description in the column titled "Textual Description" in the Applicable Requirements Summary attachment is not enforceable and is not deemed as a substitute for the actual regulatory language. The Textual Description is provided for information purposes only.

- C. A citation listed on the Applicable Requirements Summary attachment, which has a notation [G] listed before it, shall include the referenced section and subsection for all commission rules, or paragraphs for all federal and state regulations and all subordinate paragraphs, subparagraphs and clauses, subclauses, and items contained within the referenced citation as applicable requirements.
- D. When a grouped citation, notated with a [G] in the Applicable Requirements Summary, contains multiple compliance options, the permit holder must keep records of when each compliance option was used.
- E. Emission units subject to 40 CFR Part 63, Subparts Y, CC, UUU, ZZZZ, DDDDD, and GGGGG as identified in the attached Applicable Requirements Summary table are subject to 30 TAC Chapter 113, Subchapter C, § 113.300, § 113.340, § 113.780, § 113.1090, § 113.1130 and § 113.1160 respectively, which incorporate the 40 CFR Part 63 Subparts by reference.
- F. For the purpose of generating emission reduction credits through 30 TAC Chapter 101, Subchapter H, Division 1 (Emission Credit Banking and Trading), the permit holder shall comply with the following requirements:
 - (i) Title 30 TAC § 101.302 (relating to General Provisions)
 - (ii) Title 30 TAC § 101.303 (relating to Emission Reduction Credit Generation Certification)
 - (iii) Title 30 TAC § 101.304 (relating to Mobile Emission Reduction Credit Generation and Certification)
 - (iv) Title 30 TAC § 101.305 (relating to Emission Reductions Achieved Outside the United States)
 - (v) Title 30 TAC § 101.309 (relating to Emission Credit Banking and Trading)
 - (vi) The terms and conditions by which the emission limits are established to generate the reduction credit are applicable requirements of this permit
- G. The permit holder shall comply with the following 30 TAC Chapter 101, Subchapter H, Division 3 (Mass Emission Cap and Trade Program) Requirements:
 - (i) Title 30 TAC § 101.352 (relating to General Provisions)

- (ii) Title 30 TAC § 101.353 (relating to Allocation of Allowances)
 - (iii) Title 30 TAC § 101.354 (relating to Allowance Deductions)
 - (iv) Title 30 TAC § 101.356 (relating to Allowance Banking and Trading)
 - (v) Title 30 TAC § 101.358 (relating to Emission Monitoring and Compliance Demonstration)
 - (vi) Title 30 TAC § 101.359 (relating to Reporting)
 - (vii) Title 30 TAC § 101.360 (relating to Level of Activity Certification)
 - (viii) The terms and conditions by which the emission limits are established to meet or exceed the cap are applicable requirements of this permit
- H. For the purpose of generating discrete emission reduction credits through 30 TAC Chapter 101, Subchapter H, Division 4 (Discrete Emission Credit Banking and Trading), the permit holder shall comply with the following requirements:
- (i) Title 30 TAC § 101.372 (relating to General Provisions)
 - (ii) Title 30 TAC § 101.373 (relating to Discrete Emission Reduction Credit Generation and Certification)
 - (iii) Title 30 TAC § 101.374 (relating to Mobile Discrete Emission Reduction Credit Generation and Certification)
 - (iv) Title 30 TAC § 101.375 (relating to Emission Reductions Achieved Outside the United States)
 - (v) Title 30 TAC § 101.378 (relating to Discrete Emission Credit Banking and Trading)
 - (vi) The terms and conditions by which the emission limits are established to generate the discrete reduction credit are applicable requirements of this permit
- I. The permit holder shall comply with the following 30 TAC Chapter 101, Subchapter H, Division 6 (Highly Reactive Volatile Organic Compound Emissions Cap and Trade Program) requirements:
- (i) Title 30 TAC § 101.393 (relating to General Provisions)
 - (ii) Title 30 TAC § 101.394 (relating to Allocation of Allowances)
 - (iii) Title 30 TAC § 101.396 (relating to Allowance Deductions)

- (iv) Title 30 TAC § 101.399 (relating to Allowance Banking and Trading)
 - (v) Title 30 TAC § 101.400 (relating to Reporting)
 - (vi) The terms and conditions by which the emission limits are established to meet or exceed the cap are applicable requirements of this permit
- 2. The permit holder shall comply with the following sections of 30 TAC Chapter 101 (General Air Quality Rules):
 - A. Title 30 TAC § 101.1 (relating to Definitions), insofar as the terms defined in this section are used to define the terms used in other applicable requirements
 - B. Title 30 TAC § 101.3 (relating to Circumvention)
 - C. Title 30 TAC § 101.8 (relating to Sampling), if such action has been requested by the TCEQ
 - D. Title 30 TAC § 101.9 (relating to Sampling Ports), if such action has been requested by the TCEQ
 - E. Title 30 TAC § 101.10 (relating to Emissions Inventory Requirements)
 - F. Title 30 TAC § 101.201 (relating to Emission Event Reporting and Recordkeeping Requirements)
 - G. Title 30 TAC § 101.211 (relating to Scheduled Maintenance, Start-up, and Shutdown Reporting and Recordkeeping Requirements)
 - H. Title 30 TAC § 101.221 (relating to Operational Requirements)
 - I. Title 30 TAC § 101.222 (relating to Demonstrations)
 - J. Title 30 TAC § 101.223 (relating to Actions to Reduce Excessive Emissions)
- 3. Permit holder shall comply with the following requirements of 30 TAC Chapter 111:
 - A. For visible emissions from a building, enclosed facility, or other structure; the permit holder shall comply with the following requirements:
 - (i) Title 30 TAC § 111.111(a)(7)(A) (relating to Requirements for Specified Sources)
 - (ii) Title 30 TAC § 111.111(a)(7)(B)(i) or (ii)

- (iii) For a building containing an air emission source, enclosed facility, or other structure containing or associated with an air emission source subject to 30 TAC § 111.111(a)(7)(A), complying with 30 TAC § 111.111(a)(7)(B)(i) or (ii), and capable of producing visible emissions from, but not limited to, particulate matter, acid gases and NO_x, the permit holder shall also comply with the following periodic monitoring requirements for the purpose of annual compliance certification under 30 TAC § 122.146:
- (1) An observation of visible emissions from a building containing an air emission source, enclosed facility, or other structure containing or associated with an air emission source which is required to comply with 30 TAC § 111.111(a)(7)(A) shall be conducted at least once during each calendar quarter unless the air emission source or enclosed facility is not operating for the entire quarter.
 - (2) Records of all observations shall be maintained.
 - (3) Visible emissions observations of air emission sources or enclosed facilities operated during daylight hours shall be conducted no earlier than one hour after sunrise and no later than one hour before sunset. Visible emissions observations of air emission sources or enclosed facilities operated only at night must be made with additional lighting and the temporary installation of contrasting backgrounds. Visible emissions shall be determined with each emissions outlet in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 mile, away from each emissions outlet during the observation. For outdoor locations, the observer shall select a position where the sun is not directly in the observer's eyes. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. A certified opacity reader is not required for visible emissions observations.
 - (4) Compliance Certification:
 - (a) If visible emissions are not present during the observation, the RO may certify that the source is in compliance with the applicable opacity requirement in 30 TAC § 111.111(a)(7) and (a)(7)(A)

(b) However, if visible emissions are present during the observation, the permit holder shall either list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(7)(B) to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.

B. For visible emissions from all other sources not specified in 30 TAC § 111.111(a)(1), (4), or (7); the permit holder shall comply with the following requirements:

- (i) Title 30 TAC § 111.111(a)(8)(A) (relating to Requirements for Specified Sources)
- (ii) Title 30 TAC § 111.111(a)(8)(B)(i) or (ii)
- (iii) For a source subject to 30 TAC § 111.111(a)(8)(A), complying with 30 TAC § 111.111(a)(8)(B)(i) or (ii), and capable of producing visible emissions from, but not limited to, particulate matter, acid gases and NO_x, the permit holder shall also comply with the following periodic monitoring requirements for the purpose of annual compliance certification under 30 TAC § 122.146:
 - (1) An observation of visible emissions from a source which is required to comply with 30 TAC § 111.111(a)(8)(A) shall be conducted at least once during each calendar quarter unless the source is not operating for the entire quarter.
 - (2) Records of all observations shall be maintained.

(3) Visible emissions observations of sources operated during daylight hours shall be conducted no earlier than one hour after sunrise and no later than one hour before sunset. Visible emissions observations of sources operated only at night must be made with additional lighting and the temporary installation of contrasting backgrounds. Visible emissions shall be determined with each source in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 mile, away from each source during the observation. For outdoor locations, the observer shall select a position where the sun is not directly in the observer's eyes. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. A certified opacity reader is not required for visible emissions observations.

(4) Compliance Certification:

(a) If visible emissions are not present during the observation, the RO may certify that the source is in compliance with the applicable opacity requirement in 30 TAC § 111.111(a)(8) and (a)(8)(A)

(b) However, if visible emissions are present during the observation, the permit holder shall either list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(8)(B) to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.

- C. Certification of opacity readers determining opacities under Method 9 (as outlined in 40 CFR Part 60, Appendix A) to comply with opacity monitoring requirements shall be accomplished by completing the Visible Emissions Evaluators Course, or approved agency equivalent, no more than 180 days before the opacity reading.
- D. For emission units with contributions from uncombined water, the permit holder shall comply with the requirements of 30 TAC § 111.111(b).
- E. Emission limits on nonagricultural processes, except for the steam generators specified in 30 TAC § 111.153, shall comply with the following requirements:
 - (i) Emissions of PM from any source may not exceed the allowable rates as required in 30 TAC § 111.151(a) (relating to Allowable Emissions Limits)
 - (ii) Sources with an effective stack height (h_e) less than the standard effective stack height (H_e), must reduce the allowable emission level by multiplying it by $[h_e/H_e]^2$ as required in 30 TAC § 111.151(b)
 - (iii) Effective stack height shall be calculated by the equation specified in 30 TAC § 111.151(c)
- 4. For storage vessels maintaining working pressure as specified in 30 TAC Chapter 115, Subchapter B, Division 1: Storage of Volatile Organic Compounds, the permit holder shall comply with the requirements of 30 TAC § 115.112(e)(1).
- 5. For industrial wastewater specified in 30 TAC Chapter 115, Subchapter B, the permit holder shall comply with the following requirements for wastewater drains, junction boxes, lift stations and weirs:
 - A. Title 30 TAC § 115.142 (relating to Control Requirements)
 - B. Title 30 TAC § 115.142(1)(A) - (D) (relating to Control Requirements)
 - C. Title 30 TAC § 115.142(1)(E) and (F) (relating to Control Requirements)
 - D. Title 30 TAC § 115.145 (relating to Approved Test Methods)
 - E. Title 30 TAC § 115.146 (relating to Recordkeeping Requirements)
 - F. Title 30 TAC § 115.147(2) (relating to Exemptions), for streams with an annual VOC loading of 10 megagrams (11.03 tons) or less
 - G. Title 30 TAC § 115.147(7), (7)(A) and (B) (relating to Exemptions)
 - H. Title 30 TAC § 115.148 (relating to Determination of Wastewater Characteristics)

6. Permit holder shall comply with the following 30 TAC Chapter 115, Subchapter C requirements:
 - A. For filling of motor vehicle fuel tanks (Stage II) at motor vehicle fuel dispensing facilities specified in 30 TAC Chapter 115, Subchapter C, the permit holder shall comply with the following requirements:
 - (i) Title 30 TAC § 115.241 (relating to Emission Specifications)
 - (ii) Title 30 TAC § 115.242 (relating to Control Requirements)
 - (iii) Title 30 TAC § 115.243 (relating to Alternate Control Requirements)
 - (iv) Title 30 TAC § 115.244 (relating to Inspection Requirements)
 - (v) Title 30 TAC § 115.245 (relating to Testing Requirements)
 - (vi) Title 30 TAC § 115.246 (relating to Recordkeeping Requirements)
7. Permit holder shall comply with the following 30 TAC Chapter 115, Subchapter D requirements:
 - A. Title 30 TAC § 115.312(a)(1) (relating to Control Requirements), for emissions during Process Unit Shutdown or Turnaround
 - B. Title 30 TAC § 115.316(a)(2) (relating to Recordkeeping Requirements), for Process Unit Shutdown or Turnaround
8. The permit holder shall comply with the following requirements of 30 TAC Chapter 115, Subchapter F, Division 3, Degassing of Storage Tanks, Transport Vessels and Marine Vessels:
 - A. For degassing of stationary VOC storage tanks, the permit holder shall comply with the following requirements:
 - (i) Title 30 TAC § 115.541(a) - (c) (relating to Emission Specifications)
 - (ii) Title 30 TAC § 115.541(f) (relating to Emission Specifications), for floating roof storage tanks
 - (iii) Title 30 TAC § 115.542(a) and (a)(1), (a)(2), (a)(3) or (a)(4) (relating to Control Requirements). Where the requirements of 30 TAC Chapter 115, Subchapter F contain multiple compliance options, the permit holder shall keep records of when each compliance option was used.
 - (iv) Title 30 TAC § 115.542(b) - (d), (relating to Control Requirements)
 - (v) Title 30 TAC § 115.543 (relating to Alternate Control Requirements)

- (vi) Title 30 TAC § 115.544(a)(1) and (a)(2) (relating to Inspection, Monitoring, and Testing Requirements), for inspections
- (vii) Title 30 TAC § 115.544(b) (relating to Inspection, Monitoring, and Testing Requirements), for monitoring
- (viii) Title 30 TAC § 115.544(b)(1) and (b)(2) (relating to Inspection, Monitoring, and Testing Requirements), for monitoring of control devices
- (ix) Title 30 TAC § 115.544(b)(2)(A) - (J) (relating to Inspection, Monitoring, and Testing Requirements), for monitoring (as appropriate to the control device)
- (x) Title 30 TAC § 115.544(b)(3), (b)(4) and (b)(6) (relating to Inspection, Monitoring, and Testing Requirements), for VOC concentration or lower explosive limit threshold monitoring
- (xi) Title 30 TAC § 115.544(c), and (c)(1) - (c)(3) (relating to Inspection, Monitoring, and Testing Requirements), for testing of control devices used to comply with 30 TAC § 115.542(a)(1)
- (xii) Title 30 TAC § 115.545(1) - (7), (9) - (11) and (13) (relating to Approved Test Methods)
- (xiii) Title 30 TAC § 115.546(a), (a)(1) and (a)(3) (relating to Recordkeeping and Notification Requirements), for recordkeeping
- (xiv) Title 30 TAC § 115.546(a)(2) and (a)(2)(A) - (J) (relating to Recordkeeping and Notification Requirements), for recordkeeping (as appropriate to the control device)
- (xv) Title 30 TAC § 115.546(a)(4) (relating to Recordkeeping and Notification Requirements), for recordkeeping of testing of control devices used to comply with 30 TAC § 115.542(a)(1)
- (xvi) Title 30 TAC § 115.546(b) (relating to Recordkeeping and Notification Requirements), for notification
- (xvii) Title 30 TAC § 115.547(4) (relating to Exemptions)

9. The permit holder shall comply with the following requirements of 30 TAC Chapter 115, Subchapter H, Division 1 for pressure relief devices not controlled by a flare:

- A. Title 30 TAC § 115.725(c)
- B. Title 30 TAC § 115.725(c)(1), (c)(1)(A) - (C)

- C. Title 30 TAC § 115.725(c)(2)
 - D. Title 30 TAC § 115.725(c)(3), (c)(3)(A) - (E)
 - E. Title 30 TAC § 115.725(c)(4)
 - F. Title 30 TAC § 115.725(l)
 - G. Title 30 TAC § 115.726(c), (c)(1) - (4)
10. The permit holder shall comply with the requirements of 30 TAC § 115.726(e)(3)(A) for vent streams having no potential to emit HRVOC.
11. The permit holder shall comply with the requirements of 30 TAC § 115.726(e)(3)(A) for vent streams from sources exempt under 30 TAC § 115.727(c)(3).
12. The permit holder shall comply with the following requirements for units subject to any subpart of 40 CFR Part 60, unless otherwise stated in the applicable subpart:
- A. Title 40 CFR § 60.7 (relating to Notification and Recordkeeping)
 - B. Title 40 CFR § 60.8 (relating to Performance Tests)
 - C. Title 40 CFR § 60.11 (relating to Compliance with Standards and Maintenance Requirements)
 - D. Title 40 CFR § 60.12 (relating to Circumvention)
 - E. Title 40 CFR § 60.13 (relating to Monitoring Requirements)
 - F. Title 40 CFR § 60.14 (relating to Modification)
 - G. Title 40 CFR § 60.15 (relating to Reconstruction)
 - H. Title 40 CFR § 60.19 (relating to General Notification and Reporting Requirements)
13. For petroleum refinery facilities subject to 40 CFR Part 60, Subpart QQQ, the permit holder shall comply with the following requirements:
- A. Title 40 CFR § 60.692-1(a) - (c) (relating to Standards: General)
 - B. Title 40 CFR § 60.692-2(a) - (c), (e) (relating to Standards: Individual Drain Systems)
 - C. Title 40 CFR § 60.692-2(d) (relating to Standards: Individual Drain Systems)

- D. Title 40 CFR § 60.692-6(a) - (b) (relating to Standards: Delay of Repair)
 - E. Title 40 CFR § 60.692-7(a) - (b) (relating to Standards: Delay of Compliance)
 - F. Title 40 CFR § 60.693-1(a) - (d), (e)(1) - (3) (relating to Alternative Standards for Individual Drain Systems)
 - G. Title 40 CFR § 60.697(a), (b)(1) - (3) (relating to Recordkeeping Requirements), as applicable to Individual Drain Systems
 - H. Title 40 CFR § 60.697(f)(1) - (2), (g) (relating to Recordkeeping Requirements), as applicable to Individual Drain Systems
 - I. Title 40 CFR § 60.697(h) (relating to Recordkeeping Requirements), as applicable to excluded Stormwater Sewer Systems
 - J. Title 40 CFR § 60.697(i) (relating to Recordkeeping Requirements), as applicable to excluded Ancillary Equipment
 - K. Title 40 CFR § 60.698(a), and (b)(1) (relating to Reporting Requirements), as applicable to Individual Drain Systems
 - L. Title 40 CFR § 60.698(c) (relating to Reporting Requirements), for water seal breaches in Drain Systems
 - M. Title 40 CFR § 60.698(e) (relating to Reporting Requirements), as applicable to Individual Drain Systems
14. The permit holder shall comply with the following requirements for units subject to any subpart of 40 CFR Part 61, unless otherwise stated in the applicable subpart:
- A. Title 40 CFR § 61.05 (relating to Prohibited Activities)
 - B. Title 40 CFR § 61.07 (relating to Application for Approval of Construction or Modification)
 - C. Title 40 CFR § 61.09 (relating to Notification of Start-up)
 - D. Title 40 CFR § 61.10 (relating to Source Reporting and Request Waiver)
 - E. Title 40 CFR § 61.12 (relating to Compliance with Standards and Maintenance Requirements)
 - F. Title 40 CFR § 61.13 (relating to Emissions Tests and Waiver of Emission Tests)
 - G. Title 40 CFR § 61.14 (relating to Monitoring Requirements)

- H. Title 40 CFR § 61.15 (relating to Modification)
 - I. Title 40 CFR § 61.19 (relating to Circumvention)
15. For facilities where total annual benzene quantity from waste is greater than or equal to 10 megagrams per year and subject to emission standards in 40 CFR Part 61, Subpart FF, the permit holder shall comply with the following requirements:
- A. Title 40 CFR § 61.342(c)(1)(i) - (iii) (relating to Standards: General)
 - B. Title 40 CFR § 61.342(e)(1) (relating to Standards: General)
 - C. Title 40 CFR § 61.342(e)(2)(i) - (ii) (relating to Standards: General)
 - D. Title 40 CFR § 61.342(f)(1), and (2) (relating to Standards: General)
 - E. Title 40 CFR § 61.342(g) (relating to Standards: General)
 - F. Title 40 CFR § 61.350(a) and (b) (relating to Standards: Delay of Repair)
 - G. Title 40 CFR § 61.355(a)(1)(iii), (a)(2), (a)(6), (b), and (c)(1) - (3) (relating to Test Methods, Procedures, and Compliance Provisions)
 - H. Title 40 CFR § 61.355(k)(1) - (6), and (7)(i) - (iv) (relating to Test Methods, Procedures, and Compliance Provisions), for calculation procedures
 - I. Title 40 CFR § 61.356(a) (relating to Recordkeeping Requirements)
 - J. Title 40 CFR § 61.356(b), and (b)(1) (relating to Recordkeeping Requirements)
 - K. Title 40 CFR § 61.356(b)(4) (relating to Recordkeeping Requirements)
 - L. Title 40 CFR § 61.356(b)(5) (relating to Recordkeeping Requirements)
 - M. Title 40 CFR § 61.356(c) (relating to Recordkeeping Requirements)
 - N. Title 40 CFR § 61.357(a), (d)(1), (d)(2) (d)(6) and (d)(8) (relating to Reporting Requirements)
 - O. Title 40 CFR § 61.357(d)(5) (relating to Reporting Requirements)
 - P. Waste generated by remediation activities at these facilities are subject to the requirements identified under 40 CFR § 61.342 for treatment and management of waste

16. For facilities with containers subject to emission standards in 40 CFR Part 61, Subpart FF, the permit holder shall comply with the following requirements:
 - A. Title 40 CFR § 61.353(a) - (c) (relating to Alternative Means of Emission Limitation)
17. For facilities with individual drain systems subject to emission standards in 40 CFR Part 61, Subpart FF, the permit holder shall comply with the following requirements:
 - A. Title 40 CFR § 61.353(a) - (c) (relating to Alternative Means of Emission Limitation)
18. The permit holder shall comply with the requirements of 30 TAC Chapter 113, Subchapter C, § 113.100 for units subject to any subpart of 40 CFR Part 63, unless otherwise stated in the applicable subpart.
19. For sources subject to emission standards in 40 CFR Part 63, Subpart CC, the permit holder shall comply with the following requirements (Title 30 TAC Chapter 113, Subchapter C, § 113.340 incorporated by reference):
 - A. Title 40 CFR § 63.640(l)(3) - (4) (relating to Applicability and Designation of Affected Source), for units and equipment added to an existing source
 - B. Title 40 CFR § 63.640(m)(1) - (2) (relating to Applicability and Designation of Affected Source), for units and emission points changing from Group 2 to Group 1 status
 - C. Title 40 CFR § 63.642(c) (relating to General Standards), for applicability of the General Provisions of Subpart A
 - D. Title 40 CFR § 63.642(e) (relating to General Standards), for recordkeeping
 - E. Title 40 CFR § 63.642(f) (relating to General Standards), for reporting
20. The permit holder shall comply with the requirement to prepare and implement an Operations and Maintenance plan in accordance with 40 CFR Part 63, Subpart UUU, § 63.1574(f) (Title 30 TAC Chapter 113, Subchapter C, § 113.780 incorporated by reference).

21. The permit holder shall comply with certified registrations submitted to the TCEQ for purposes of establishing federally enforceable emission limits. A copy of the certified registration shall be maintained with the permit. Records sufficient to demonstrate compliance with the established limits shall be maintained. The certified registration and records demonstrating compliance shall be provided, on request, to representatives of the appropriate TCEQ regional office and any local air pollution control agency having jurisdiction over the site. The permit holder shall submit updated certified registrations when changes at the site require establishment of new emission limits. If changes result in emissions that do not remain below major source thresholds, the permit holder shall submit a revision application to codify the appropriate requirements in the permit.

Additional Monitoring Requirements

22. Unless otherwise specified, the permit holder shall comply with the compliance assurance monitoring requirements as specified in the attached “CAM Summary” upon issuance of the permit. In addition, the permit holder shall comply with the following:
 - A. The permit holder shall comply with the terms and conditions contained in 30 TAC § 122.147 (General Terms and Conditions for Compliance Assurance Monitoring).
 - B. The permit holder shall report, consistent with the averaging time identified in the “CAM Summary,” deviations as defined by the deviation limit in the “CAM Summary.” Any monitoring data below a minimum limit or above a maximum limit, that is collected in accordance with the requirements specified in 40 CFR § 64.7(c), shall be reported as a deviation. Deviations shall be reported according to 30 TAC § 122.145 (Reporting Terms and Conditions).
 - C. The permit holder may elect to collect monitoring data on a more frequent basis and average the data, consistent with the averaging time specified in the “CAM Summary,” for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis. In no event shall data be collected and used in particular instances in order to avoid reporting deviations. All monitoring data shall be collected in accordance with the requirements specified in 40 CFR § 64.7(c).
 - D. The permit holder shall operate the monitoring, identified in the attached “CAM Summary,” in accordance with the provisions of 40 CFR § 64.7.
 - E. The permit holder shall comply with the requirements of 40 CFR § 70.6(a)(3)(ii)(A) and 30 TAC § 122.144(1)(A)-(F) for documentation of all required inspections.

23. The permit holder shall comply with the periodic monitoring requirements as specified in the attached “Periodic Monitoring Summary” upon issuance of the permit. Except for, as applicable, monitoring malfunctions, associated repairs, and required quality assurance or control activities (including, as applicable, calibration checks and required zero and span adjustments), the permit holder shall conduct all monitoring in continuous operation (or shall collect data at all required intervals) at all times that the pollutant-specific emissions unit is operating. The permit holder may elect to collect monitoring data on a more frequent basis and average the data, consistent with the averaging time specified in the “Periodic Monitoring Summary,” for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis. In no event shall data be collected and used in particular instances to avoid reporting deviations. Deviations shall be reported according to 30 TAC § 122.145 (Reporting Terms and Conditions).

New Source Review Authorization Requirements

24. Permit holder shall comply with the requirements of New Source Review authorizations issued or claimed by the permit holder for the permitted area, including permits, permits by rule, standard permits, flexible permits, special permits, permits for existing facilities including Voluntary Emissions Reduction Permits and Electric Generating Facility Permits issued under 30 TAC Chapter 116, Subchapter I, or special exemptions referenced in the New Source Review Authorization References attachment. These requirements:
 - A. Are incorporated by reference into this permit as applicable requirements
 - B. Shall be located with this operating permit
 - C. Are not eligible for a permit shield
25. The permit holder shall comply with the general requirements of 30 TAC Chapter 106, Subchapter A or the general requirements, if any, in effect at the time of the claim of any PBR.
26. The permit holder shall maintain records to demonstrate compliance with any emission limitation or standard that is specified in a permit by rule (PBR) or Standard Permit listed in the New Source Review Authorizations attachment. The records shall yield reliable data from the relevant time period that are representative of the emission unit’s compliance with the PBR or Standard Permit. These records may include, but are not limited to, production capacity and throughput, hours of operation, material safety data sheets (MSDS), chemical composition of raw materials, speciation of air contaminant data, engineering calculations, maintenance records, fugitive data, performance tests, capture/control device efficiencies, direct pollutant monitoring (CEMS, COMS, or PEMS), or control device parametric monitoring. These records shall be made readily accessible and available as required by 30 TAC § 122.144.

- A. If applicable, monitoring of control device performance or general work practice standards shall be made in accordance with the TCEQ Periodic Monitoring Guidance document.
 - B. Any monitoring or recordkeeping data indicating noncompliance with the PBR or Standard Permit shall be considered and reported as a deviation according to 30 TAC § 122.145 (Reporting Terms and Conditions).
27. The permit holder shall comply with the following requirements for Air Quality Standard Permits:
- A. Registration requirements listed in 30 TAC § 116.611, unless otherwise provided for in an Air Quality Standard Permit
 - B. General Conditions listed in 30 TAC § 116.615, unless otherwise provided for in an Air Quality Standard Permit
 - C. Applicable requirements of 30 TAC § 116.617 for Pollution Control Projects based on the information contained in the registration application.
 - D. Requirements of the non-rule Air Quality Standard Permit for Pollution Control Projects

Compliance Requirements

28. The permit holder shall certify compliance in accordance with 30 TAC § 122.146. The permit holder shall comply with 30 TAC § 122.146 using at a minimum, but not limited to, the continuous or intermittent compliance method data from monitoring, recordkeeping, reporting, or testing required by the permit and any other credible evidence or information. The certification period may not exceed 12 months and the certification must be submitted within 30 days after the end of the period being certified.
29. Permit holder shall comply with the following 30 TAC Chapter 117 requirements:
- A. The permit holder shall comply with the compliance schedules and submit written notification to the TCEQ Executive Director as required in 30 TAC Chapter 117, Subchapter H, Division 1:
 - (i) For sources in the Houston-Galveston-Brazoria Nonattainment area, 30 TAC § 117.9020:
 - (1) Title 30 TAC § 117.9020(2)(A), (C), and (D)
 - B. The permit holder shall comply with the Initial Control Plan unit listing requirement in 30 TAC § 117.350(c) and (c)(1).

- C. The permit holder shall comply with the requirements of 30 TAC § 117.354 for Final Control Plan Procedures for Attainment Demonstration Emission Specifications and 30 TAC § 117.356 for Revision of Final Control Plan.
30. Use of Emission Credits to comply with applicable requirements:
- A. Unless otherwise prohibited, the permit holder may use emission credits to comply with the following applicable requirements listed elsewhere in this permit:
 - (i) Title 30 TAC Chapter 115
 - (ii) Title 30 TAC Chapter 117
 - (iii) Offsets for Title 30 TAC Chapter 116
 - B. The permit holder shall comply with the following requirements in order to use the emission credits to comply with the applicable requirements:
 - (i) The permit holder must notify the TCEQ according to 30 TAC § 101.306(c)(2)
 - (ii) The emission credits to be used must meet all the geographic, timeliness, applicable pollutant type, and availability requirements listed in 30 TAC Chapter 101, Subchapter H, Division 1
 - (iii) The executive director has approved the use of the credit according to 30 TAC § 101.306(c)(2)
 - (iv) The permit holder keeps records of the use of credits towards compliance with the applicable requirements in accordance with 30 TAC § 101.302(g) and 30 TAC Chapter 122
31. Use of Discrete Emission Credits to comply with the applicable requirements:
- A. Unless otherwise prohibited, the permit holder may use discrete emission credits to comply with the following applicable requirements listed elsewhere in this permit:
 - (i) Title 30 TAC Chapter 115
 - (ii) Title 30 TAC Chapter 117
 - (iii) If applicable, offsets for Title 30 TAC Chapter 116
 - (iv) Temporarily exceed state NSR permit allowables

- B. The permit holder shall comply with the following requirements in order to use the credit to comply with the applicable requirements:
- (i) The permit holder must notify the TCEQ according to 30 TAC § 101.376(d)
 - (ii) The discrete emission credits to be used must meet all the geographic, timeliness, applicable pollutant type, and availability requirements listed in 30 TAC Chapter 101, Subchapter H, Division 4
 - (iii) The executive director has approved the use of the discrete emission credits according to 30 TAC § 101.376(d)(1)(A)
 - (iv) The permit holder keeps records of the use of credits towards compliance with the applicable requirements in accordance with 30 TAC § 101.372(h) and 30 TAC Chapter 122

Risk Management Plan

32. For processes subject to 40 CFR Part 68 and specified in 40 CFR § 68.10, the permit holder shall comply with the requirements of the Accidental Release Prevention Provisions in 40 CFR Part 68. The permit holder shall submit to the appropriate agency either a compliance schedule for meeting the requirements of 40 CFR Part 68 by the date provided in 40 CFR § 68.10(a), or as part of the compliance certification submitted under this permit, a certification statement that the source is in compliance with all requirements of 40 CFR Part 68, including the registration and submission of a risk management plan.

Protection of Stratospheric Ozone

33. Permit holders at a site subject to Title VI of the FCAA Amendments shall meet the following requirements for protection of stratospheric ozone.
- A. Any on site servicing, maintenance, and repair on refrigeration and nonmotor vehicle air-conditioning appliances using ozone-depleting refrigerants or non-exempt substitutes shall be conducted in accordance with 40 CFR Part 82, Subpart F. Permit holders shall ensure that repairs on or refrigerant removal from refrigeration and nonmotor vehicle air-conditioning appliances using ozone-depleting refrigerants are performed only by properly certified technicians using certified equipment. Records shall be maintained as required by 40 CFR Part 82, Subpart F.

Permit Location

34. The permit holder shall maintain a copy of this permit and records related to requirements listed in this permit on site.

Permit Shield (30 TAC § 122.148)

35. A permit shield is granted for the emission units, groups, or processes specified in the attached “Permit Shield.” Compliance with the conditions of the permit shall be deemed compliance with the specified potentially applicable requirements or specified potentially applicable state-only requirements listed in the attachment “Permit Shield.” Permit shield provisions shall not be modified by the executive director until notification is provided to the permit holder. No later than 90 days after notification of a change in a determination made by the executive director, the permit holder shall apply for the appropriate permit revision to reflect the new determination. Provisional terms are not eligible for this permit shield. Any term or condition, under a permit shield, shall not be protected by the permit shield if it is replaced by a provisional term or condition or the basis of the term and condition changes.

Attachments

Applicable Requirements Summary

Additional Monitoring Requirements

Permit Shield

New Source Review Authorization References

Applicable Requirements Summary

Unit Summary 23

Applicable Requirements Summary 62

Note: A “none” entry may be noted for some emission sources in this permit’s “Applicable Requirements Summary” under the heading of “Monitoring and Testing Requirements” and/or “Recordkeeping Requirements” and/or “Reporting Requirements.” Such a notation indicates that there are no requirements for the indicated emission source as identified under the respective column heading(s) for the stated portion of the regulation when the emission source is operating under the conditions of the specified SOP Index Number. However, other relevant requirements pursuant to 30 TAC Chapter 122 including Recordkeeping Terms and Conditions (30 TAC § 122.144), Reporting Terms and Conditions (30 TAC § 122.145), and Compliance Certification Terms and Conditions (30 TAC § 122.146) continue to apply.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
44BA3002	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	60Dc-1	40 CFR Part 60, Subpart Dc	No changing attributes.
50BF02	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	R7300-6	30 TAC Chapter 117, Subchapter B	No changing attributes.
50BF02	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	60Db-1	40 CFR Part 60, Subpart Db	No changing attributes.
50BF02	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	63DDDDD -1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
50BF03	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	R7300-6	30 TAC Chapter 117, Subchapter B	No changing attributes.
50BF03	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	60Db-1	40 CFR Part 60, Subpart Db	No changing attributes.
50BF03	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	63DDDDD -1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
81BF01	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	R7300-6	30 TAC Chapter 117, Subchapter B	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
81BF01	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	60Db-1	40 CFR Part 60, Subpart Db	No changing attributes.
81BF01	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	63DDDDD -1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
5GCVS	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	63GGGGG- 1	40 CFR Part 63, Subpart GGGGG	No changing attributes.
81SKD5602	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	63GGGGG- 1	40 CFR Part 63, Subpart GGGGG	No changing attributes.
81SKD5603	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	63GGGGG- 1	40 CFR Part 63, Subpart GGGGG	No changing attributes.
91CB915	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	63GGGGG- 1	40 CFR Part 63, Subpart GGGGG	No changing attributes.
22AVENT	EMISSION POINTS/ STATIONARY VENTS/ PROCESS VENTS	N/A	R1111-3	30 TAC Chapter 111, Visible Emissions	No changing attributes.
22AVENT	EMISSION POINTS/ STATIONARY VENTS/ PROCESS VENTS	N/A	R5127-1	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
22EG400	EMISSION POINTS/ STATIONARY VENTS/ PROCESS VENTS	N/A	R1111-3	30 TAC Chapter 111, Visible Emissions	No changing attributes.
22EG400	EMISSION POINTS/ STATIONARY VENTS/ PROCESS VENTS	N/A	R5127-1	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
22FA225	EMISSION POINTS/ STATIONARY VENTS/ PROCESS VENTS	N/A	R1111-3	30 TAC Chapter 111, Visible Emissions	No changing attributes.
22FA225	EMISSION POINTS/ STATIONARY VENTS/ PROCESS VENTS	N/A	R5127-1	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
42CB2201	EMISSION POINTS/ STATIONARY VENTS/ PROCESS VENTS	N/A	R1111-2	30 TAC Chapter 111, Visible Emissions	No changing attributes.
GRP-DISTILL	EMISSION POINTS/ STATIONARY VENTS/ PROCESS VENTS	40DA1101, 40DA1102, 40DA1103, 40DA1201, 40DA1202, 40DA1203, 40DA1204, 40DA1205, 40DA1206, 40DA1207	R5127-1	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
GRP-HEAT1	EMISSION POINTS/ STATIONARY VENTS/ PROCESS VENTS	27BA1000, 28BA1200, 29BA1300, 41BA101, 41BA102, 81BA25	R1111-0	30 TAC Chapter 111, Visible Emissions	No changing attributes.
GRP-HEATER	EMISSION POINTS/ STATIONARY VENTS/ PROCESS VENTS	40BA1001, 40BA1002, 40BA1101	R1111-1	30 TAC Chapter 111, Visible Emissions	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
GRP-HEATER	EMISSION POINTS/ STATIONARY VENTS/ PROCESS VENTS	40BA1001, 40BA1002, 40BA1101	R5725-001	30 TAC Chapter 115, HRVOC Vent Gas	No changing attributes.
GRP-LABVENT	EMISSION POINTS/ STATIONARY VENTS/ PROCESS VENTS	92EF1A, 92EF1B, 92EF1C, 92EF2, 92EF3, 92EF4, 92EF5	R1111-3	30 TAC Chapter 111, Visible Emissions	No changing attributes.
GRP-LABVENT	EMISSION POINTS/ STATIONARY VENTS/ PROCESS VENTS	92EF1A, 92EF1B, 92EF1C, 92EF2, 92EF3, 92EF4, 92EF5	R5127-1	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
GRP-PRV	EMISSION POINTS/ STATIONARY VENTS/ PROCESS VENTS	90FB831, 90FB832, 90FB833, 90FB834, 90FB835, 90FB844, 90FB845, 90FB847	R1111-3	30 TAC Chapter 111, Visible Emissions	No changing attributes.
GRP-PRV	EMISSION POINTS/ STATIONARY VENTS/ PROCESS VENTS	90FB831, 90FB832, 90FB833, 90FB834, 90FB835, 90FB844, 90FB845, 90FB847	R5127-1	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
GRP-REG1VENT	EMISSION POINTS/ STATIONARY VENTS/ PROCESS VENTS	23BA302, 27ENG1, 27ENG2, 30GG1822, 30PU2991, 30PU2992, 30PU2993, 39CB2001, 42ENG1, 42GG1730, 42GG1848, 42GG1849, 44BA3001, 44BA3002, 44BA3005, 46CB6301, 47GG1523, 50BF02, 50BF03, 51HTR, 81BF01, 81ENG1, 81GEN001, 81SKD5602, 81SKD5603, 90CB5601, 90GG2245, 91CB915, 97GE2999	R1111-1	30 TAC Chapter 111, Visible Emissions	No changing attributes.
GRP-VENTLUBE	EMISSION POINTS/ STATIONARY VENTS/ PROCESS VENTS	22VENT, 45AVENT, 45VENT, 46VENT	R1111-3	30 TAC Chapter 111, Visible Emissions	No changing attributes.
GRP-VENTLUBE	EMISSION POINTS/ STATIONARY VENTS/ PROCESS VENTS	22VENT, 45AVENT, 45VENT, 46VENT	R5127-1	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
PROCVENT	EMISSION POINTS/ STATIONARY VENTS/ PROCESS VENTS	N/A	R1111-3	30 TAC Chapter 111, Visible Emissions	No changing attributes.
PROCVENT	EMISSION POINTS/ STATIONARY VENTS/ PROCESS VENTS	N/A	R5127-1	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
23BA302	FCCU CAT REGEN/ FUEL GAS COMBUSTION/ CLAUS SRU	N/A	60J-2	40 CFR Part 60, Subpart J	No changing attributes.
30FL1	FCCU CAT REGEN/ FUEL GAS COMBUSTION/ CLAUS SRU	N/A	60Ja-1	40 CFR Part 60, Subpart Ja	No changing attributes.
30FL6	FCCU CAT REGEN/ FUEL GAS COMBUSTION/ CLAUS SRU	N/A	60Ja-1	40 CFR Part 60, Subpart Ja	No changing attributes.
39CB2001	FCCU CAT REGEN/ FUEL GAS COMBUSTION/ CLAUS SRU	N/A	60JTGI-1	40 CFR Part 60, Subpart J	No changing attributes.
39CB2001	FCCU CAT REGEN/ FUEL GAS COMBUSTION/ CLAUS SRU	N/A	63UUU-1	40 CFR Part 63, Subpart UUU	No changing attributes.
39FA1006	FCCU CAT REGEN/ FUEL GAS COMBUSTION/ CLAUS SRU	N/A	60JSP-1B	40 CFR Part 60, Subpart J	No changing attributes.
39FA1006	FCCU CAT REGEN/ FUEL GAS COMBUSTION/ CLAUS SRU	N/A	60JSP-1C	40 CFR Part 60, Subpart J	No changing attributes.
39FA1006	FCCU CAT REGEN/ FUEL GAS COMBUSTION/ CLAUS SRU	N/A	63UUU-1	40 CFR Part 63, Subpart UUU	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
39FB1001	FCCU CAT REGEN/ FUEL GAS COMBUSTION/ CLAUS SRU	N/A	60JSP-1B	40 CFR Part 60, Subpart J	No changing attributes.
39FB1001	FCCU CAT REGEN/ FUEL GAS COMBUSTION/ CLAUS SRU	N/A	60JSP-1C	40 CFR Part 60, Subpart J	No changing attributes.
39FB1001	FCCU CAT REGEN/ FUEL GAS COMBUSTION/ CLAUS SRU	N/A	63UUU-1	40 CFR Part 63, Subpart UUU	No changing attributes.
39LO1001	FCCU CAT REGEN/ FUEL GAS COMBUSTION/ CLAUS SRU	N/A	60JSP-1B	40 CFR Part 60, Subpart J	No changing attributes.
39LO1001	FCCU CAT REGEN/ FUEL GAS COMBUSTION/ CLAUS SRU	N/A	60JSP-1C	40 CFR Part 60, Subpart J	No changing attributes.
39LO1001	FCCU CAT REGEN/ FUEL GAS COMBUSTION/ CLAUS SRU	N/A	63UUU-1	40 CFR Part 63, Subpart UUU	No changing attributes.
39RX2001	FCCU CAT REGEN/ FUEL GAS COMBUSTION/ CLAUS SRU	N/A	60JSRU-1B	40 CFR Part 60, Subpart J	CONTROL DEVICE ID NO. = 46CB6301
39RX2001	FCCU CAT REGEN/ FUEL GAS COMBUSTION/ CLAUS SRU	N/A	60JSRU-1C	40 CFR Part 60, Subpart J	CONTROL DEVICE ID NO. = 39CB2001

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
39RX2001	FCCU CAT REGEN/ FUEL GAS COMBUSTION/ CLAUS SRU	N/A	63UUU-1	40 CFR Part 63, Subpart UUU	No changing attributes.
42CB2201	FCCU CAT REGEN/ FUEL GAS COMBUSTION/ CLAUS SRU	N/A	60J-3	40 CFR Part 60, Subpart J	No changing attributes.
42CB2201	FCCU CAT REGEN/ FUEL GAS COMBUSTION/ CLAUS SRU	N/A	63UUU-3	40 CFR Part 63, Subpart UUU	No changing attributes.
44BA3001	FCCU CAT REGEN/ FUEL GAS COMBUSTION/ CLAUS SRU	N/A	60J-2	40 CFR Part 60, Subpart J	No changing attributes.
44BA3002	FCCU CAT REGEN/ FUEL GAS COMBUSTION/ CLAUS SRU	N/A	60J-2	40 CFR Part 60, Subpart J	No changing attributes.
44BA3005	FCCU CAT REGEN/ FUEL GAS COMBUSTION/ CLAUS SRU	N/A	60J-2	40 CFR Part 60, Subpart J	No changing attributes.
46AD6202	FCCU CAT REGEN/ FUEL GAS COMBUSTION/ CLAUS SRU	N/A	60JSP-1B	40 CFR Part 60, Subpart J	No changing attributes.
46AD6202	FCCU CAT REGEN/ FUEL GAS COMBUSTION/ CLAUS SRU	N/A	60JSP-1C	40 CFR Part 60, Subpart J	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
46AD6202	FCCU CAT REGEN/ FUEL GAS COMBUSTION/ CLAUS SRU	N/A	63UUU-1	40 CFR Part 63, Subpart UUU	No changing attributes.
46BC6302	FCCU CAT REGEN/ FUEL GAS COMBUSTION/ CLAUS SRU	N/A	60J-2	40 CFR Part 60, Subpart J	No changing attributes.
46CB6301	FCCU CAT REGEN/ FUEL GAS COMBUSTION/ CLAUS SRU	N/A	60JTGI-1	40 CFR Part 60, Subpart J	No changing attributes.
46CB6301	FCCU CAT REGEN/ FUEL GAS COMBUSTION/ CLAUS SRU	N/A	63UUU-1	40 CFR Part 63, Subpart UUU	No changing attributes.
46LO6201	FCCU CAT REGEN/ FUEL GAS COMBUSTION/ CLAUS SRU	N/A	60JSP-1B	40 CFR Part 60, Subpart J	No changing attributes.
46LO6201	FCCU CAT REGEN/ FUEL GAS COMBUSTION/ CLAUS SRU	N/A	60JSP-1C	40 CFR Part 60, Subpart J	No changing attributes.
46LO6201	FCCU CAT REGEN/ FUEL GAS COMBUSTION/ CLAUS SRU	N/A	63UUU-1	40 CFR Part 63, Subpart UUU	No changing attributes.
46RX6206	FCCU CAT REGEN/ FUEL GAS COMBUSTION/ CLAUS SRU	N/A	60JSRU-1B	40 CFR Part 60, Subpart J	CONTROL DEVICE ID NO. = 46CB6301

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
46RX6206	FCCU CAT REGEN/ FUEL GAS COMBUSTION/ CLAUS SRU	N/A	60JSRU-1C	40 CFR Part 60, Subpart J	CONTROL DEVICE ID NO. = 39CB2001
46RX6206	FCCU CAT REGEN/ FUEL GAS COMBUSTION/ CLAUS SRU	N/A	63UUU-1	40 CFR Part 63, Subpart UUU	No changing attributes.
50BF02	FCCU CAT REGEN/ FUEL GAS COMBUSTION/ CLAUS SRU	N/A	60J-2	40 CFR Part 60, Subpart J	No changing attributes.
50BF03	FCCU CAT REGEN/ FUEL GAS COMBUSTION/ CLAUS SRU	N/A	60J-2	40 CFR Part 60, Subpart J	No changing attributes.
51HTR	FCCU CAT REGEN/ FUEL GAS COMBUSTION/ CLAUS SRU	N/A	60Ja-3	40 CFR Part 60, Subpart Ja	No changing attributes.
81BF01	FCCU CAT REGEN/ FUEL GAS COMBUSTION/ CLAUS SRU	N/A	60J-2	40 CFR Part 60, Subpart J	No changing attributes.
81SKD5602	FCCU CAT REGEN/ FUEL GAS COMBUSTION/ CLAUS SRU	N/A	60Ja-2	40 CFR Part 60, Subpart Ja	No changing attributes.
81SKD5603	FCCU CAT REGEN/ FUEL GAS COMBUSTION/ CLAUS SRU	N/A	60Ja-2	40 CFR Part 60, Subpart Ja	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
91CB915	FCCU CAT REGEN/ FUEL GAS COMBUSTION/ CLAUS SRU	N/A	60J-4	40 CFR Part 60, Subpart J	No changing attributes.
GRP-HEATER	FCCU CAT REGEN/ FUEL GAS COMBUSTION/ CLAUS SRU	40BA1001, 40BA1002, 40BA1101	60J-2	40 CFR Part 60, Subpart J	No changing attributes.
30FL1	FLARES	N/A	R1111-1	30 TAC Chapter 111, Visible Emissions	No changing attributes.
30FL1	FLARES	N/A	R5720-1	30 TAC Chapter 115, HRVOC Vent Gas	No changing attributes.
30FL1	FLARES	N/A	60A-1	40 CFR Part 60, Subpart A	No changing attributes.
30FL1	FLARES	N/A	63A-0	40 CFR Part 63, Subpart A	No changing attributes.
30FL6	FLARES	N/A	R1111-1	30 TAC Chapter 111, Visible Emissions	No changing attributes.
30FL6	FLARES	N/A	R5720-1	30 TAC Chapter 115, HRVOC Vent Gas	No changing attributes.
30FL6	FLARES	N/A	60A-1	40 CFR Part 60, Subpart A	No changing attributes.
30FL6	FLARES	N/A	63A-0	40 CFR Part 63, Subpart A	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
22FUG	FUGITIVE EMISSION UNITS	N/A	R5352- FUG	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	No changing attributes.
22FUG	FUGITIVE EMISSION UNITS	N/A	60GGG- FUG	40 CFR Part 60, Subpart GGG	No changing attributes.
22FUG	FUGITIVE EMISSION UNITS	N/A	63CC-FUG	40 CFR Part 63, Subpart CC	No changing attributes.
40FUG	FUGITIVE EMISSION UNITS	N/A	R5352-ALL	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	No changing attributes.
40FUG	FUGITIVE EMISSION UNITS	N/A	60GGG- ALL	40 CFR Part 60, Subpart GGG	No changing attributes.
40FUG	FUGITIVE EMISSION UNITS	N/A	63CCVV- ALL	40 CFR Part 63, Subpart CC	No changing attributes.
44FUG	FUGITIVE EMISSION UNITS	N/A	R5352- FUG	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	No changing attributes.
44FUG	FUGITIVE EMISSION UNITS	N/A	60GGG- FUG	40 CFR Part 60, Subpart GGG	No changing attributes.
5GFUG	FUGITIVE EMISSION UNITS	N/A	63GGGGG- 1	40 CFR Part 63, Subpart GGGGG	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
GRP-FUG	FUGITIVE EMISSION UNITS	21FUG, 22AFUG, 22BFUG, 23FUG, 27AFUG, 27FUG, 28FUG, 29FUG, 30FUG, 39FUG, 41FUG, 42AFUG, 42BFUG, 42CFUG, 42FUG, 43AFUG, 43FUG, 44AFUG, 45AFUG, 45FUG, 46FUG, 47FUG, 50FUG, 51FUG, 81FUG, 90AFUG, 90BFUG, 90CFUG, 90FUG, 91BFUG, 91FUG, 96FUG	R5352- FUG	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
GRP-FUG	FUGITIVE EMISSION UNITS	21FUG, 22AFUG, 22BFUG, 23FUG, 27AFUG, 27FUG, 28FUG, 29FUG, 30FUG, 39FUG, 41FUG, 42AFUG, 42BFUG, 42CFUG, 42FUG, 43AFUG, 43FUG, 44AFUG, 45AFUG, 45FUG, 46FUG, 47FUG, 50FUG, 51FUG, 81FUG, 90AFUG, 90BFUG, 90CFUG, 90FUG, 91BFUG, 91FUG, 96FUG	60GGG- FUG	40 CFR Part 60, Subpart GGG	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
GRP-FUG	FUGITIVE EMISSION UNITS	21FUG, 22AFUG, 22BFUG, 23FUG, 27AFUG, 27FUG, 28FUG, 29FUG, 30FUG, 39FUG, 41FUG, 42AFUG, 42BFUG, 42CFUG, 42FUG, 43AFUG, 43FUG, 44AFUG, 45AFUG, 45FUG, 46FUG, 47FUG, 50FUG, 51FUG, 81FUG, 90AFUG, 90BFUG, 90CFUG, 90FUG, 91BFUG, 91FUG, 96FUG	63CC-FUG	40 CFR Part 63, Subpart CC	No changing attributes.
39RX2001	GAS SWEETENING/ SULFUR RECOVERY UNITS	N/A	R2SRU-1B	30 TAC Chapter 112, Sulfur Compounds	CONTROL DEVICE ID NO. = 46CB6301
39RX2001	GAS SWEETENING/ SULFUR RECOVERY UNITS	N/A	R2SRU-1C	30 TAC Chapter 112, Sulfur Compounds	CONTROL DEVICE ID NO. = 39CB2001
46RX6206	GAS SWEETENING/ SULFUR RECOVERY UNITS	N/A	R2SRU-1B	30 TAC Chapter 112, Sulfur Compounds	CONTROL DEVICE ID NO. = 46CB6301
46RX6206	GAS SWEETENING/ SULFUR RECOVERY UNITS	N/A	R2SRU-1C	30 TAC Chapter 112, Sulfur Compounds	CONTROL DEVICE ID NO. = 39CB2001

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
GRP-CWT	INDUSTRIAL PROCESS COOLING TOWERS	22CWT3, 23CWT7, 27CWT2, 42CWT10, 44CWT9	R5760-1	30 TAC Chapter 115, HRVOC Cooling Towers	No changing attributes.
9058LOAD	LOADING/ UNLOADING OPERATIONS	N/A	R5217-1	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.
9059LOAD	LOADING/ UNLOADING OPERATIONS	N/A	R5217-1	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
90DOCK1	LOADING/ UNLOADING OPERATIONS	N/A	REGV- LOAD1	30 TAC Chapter 115, Loading and Unloading of VOC	PRODUCT TRANSFERRED = Gasoline, TRUE VAPOR PRESSURE = True vapor pressure greater than or equal to 0.5 psia., DAILY THROUGHPUT = Daily throughput not determined since 30 TAC § 115.217(a)(2)(B), (b)(3)(B), (a)(2)(A), and (b)(3)(A) exemptions do not apply to marine terminals or gasoline terminals., CHPTR 115 CNTRL DEV TYPE = Vapor control system with a vapor combustor., CONTROL OPTIONS = Vapor control system that maintains a control efficiency of at least 90%., VAPOR TIGHT = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected., MARINE TERMINAL EXEMPTION = The marine terminal is not claiming one or more of the exemptions in 30 TAC § 115.217(a)(5)(B).

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
90DOCK1	LOADING/ UNLOADING OPERATIONS	N/A	REGV- LOAD2	30 TAC Chapter 115, Loading and Unloading of VOC	PRODUCT TRANSFERRED = Volatile organic compounds other than liquefied petroleum gas and gasoline., TRUE VAPOR PRESSURE = True vapor pressure greater than or equal to 0.5 psia., DAILY THROUGHPUT = Daily throughput not determined since 30 TAC § 115.217(a)(2)(B), (b)(3)(B), (a)(2)(A), and (b)(3)(A) exemptions do not apply to marine terminals or gasoline terminals., CHPTR 115 CNTRL DEV TYPE = Vapor control system with a vapor combustor., CONTROL OPTIONS = Vapor control system that maintains a control efficiency of at least 90%., VAPOR TIGHT = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected., MARINE TERMINAL EXEMPTION = The marine terminal is not claiming one or more of the exemptions in 30 TAC § 115.217(a)(5)(B).
90DOCK1	LOADING/ UNLOADING OPERATIONS	N/A	REGV- LOAD3	30 TAC Chapter 115, Loading and Unloading of VOC	PRODUCT TRANSFERRED = Volatile organic compounds other than liquefied petroleum gas and gasoline., TRUE VAPOR PRESSURE = True vapor pressure less than 0.5 psia.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
90DOCK1	LOADING/ UNLOADING OPERATIONS	N/A	REGV- LOAD4	30 TAC Chapter 115, Loading and Unloading of VOC	PRODUCT TRANSFERRED = Liquefied petroleum gas (LPG)
90DOCK1	LOADING/ UNLOADING OPERATIONS	N/A	MACTCC- LOAD1	40 CFR Part 63, Subpart CC	No changing attributes.
90DOCK1	LOADING/ UNLOADING OPERATIONS	N/A	MACTY- LOAD1	40 CFR Part 63, Subpart Y	MATERIAL LOADED = Gasoline. THROUGHPUT = Source with throughput less than 10 M barrels and 200 M barrels.
90DOCK1	LOADING/ UNLOADING OPERATIONS	N/A	MACTY- LOAD2	40 CFR Part 63, Subpart Y	MATERIAL LOADED = Material other than crude oil or gasoline.
90DOCK2	LOADING/ UNLOADING OPERATIONS	N/A	REGV- LOAD3	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.
9155LOAD	LOADING/ UNLOADING OPERATIONS	N/A	R5217-1	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.
9157LOAD	LOADING/ UNLOADING OPERATIONS	N/A	R5217-1	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
9160LOAD	LOADING/ UNLOADING OPERATIONS	N/A	R5217-1	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.
GRP-MARINE	LOADING/ UNLOADING OPERATIONS	9040LOAD, 9130LOAD	R5211-1	30 TAC Chapter 115, Loading and Unloading of VOC	PRODUCT TRANSFERRED = Volatile organic compounds other than liquefied petroleum gas and gasoline., TRUE VAPOR PRESSURE = True vapor pressure greater than or equal to 0.5 psia., DAILY THROUGHPUT = Daily throughput not determined since 30 TAC § 115.217(a)(2)(B), (b)(3)(B), (a)(2)(A), and (b)(3)(A) exemptions do not apply to marine terminals or gasoline terminals., CHPTR 115 CNTRL DEV TYPE = Vapor control system with a vapor combustor., UNCTRL'D VOC EMISSIONS = Uncontrolled VOC emissions are less than 100 tpy., VOC FLASH POINT = Flash point less than 150° F., CONTROL OPTIONS = Vapor control system that maintains a control efficiency of at least 90%., VAPOR TIGHT = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected., MARINE TERMINAL EXEMPTION = The marine terminal is claiming one or more of the exemptions in 30 TAC § 115.217(a)(5)(B).

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
GRP-MARINE	LOADING/ UNLOADING OPERATIONS	9040LOAD, 9130LOAD	R5211-2	30 TAC Chapter 115, Loading and Unloading of VOC	PRODUCT TRANSFERRED = Volatile organic compounds other than liquefied petroleum gas and gasoline., TRUE VAPOR PRESSURE = True vapor pressure less than 0.5 psia., CHPTR 115 CNTRL DEV TYPE = Vapor control system with a vapor combustor., UNCTRL'D VOC EMISSIONS = Uncontrolled VOC emissions are less than 100 tpy., VOC FLASH POINT = Flash point less than 150° F., VAPOR TIGHT = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected., VAPOR SPACE HOLDING TANK = the gasoline terminal does not have a variable vapor space holding tank design that can process vapors independent of transport vessel loading or chooses compliance with 30 TAC 115.212(a)(4)(C)., MARINE TERMINAL EXEMPTION = The marine terminal is claiming one or more of the exemptions in 30 TAC § 115.217(a)(5)(B).

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
GRP-MARINE	LOADING/ UNLOADING OPERATIONS	9040LOAD, 9130LOAD	R5211-3	30 TAC Chapter 115, Loading and Unloading of VOC	PRODUCT TRANSFERRED = Liquefied petroleum gas (LPG), TRUE VAPOR PRESSURE = True vapor pressure greater than or equal to 0.5 psia., DAILY THROUGHPUT = Daily throughput not determined since 30 TAC § 115.217(a)(2)(B), (b)(3)(B), (a)(2)(A), and (b)(3)(A) exemptions do not apply to marine terminals or gasoline terminals., CONTROL OPTIONS = Pressurized loading system.
GRP-MARINE	LOADING/ UNLOADING OPERATIONS	9040LOAD, 9130LOAD	63CC-1	40 CFR Part 63, Subpart CC	No changing attributes.
GRP-MARINE	LOADING/ UNLOADING OPERATIONS	9040LOAD, 9130LOAD	63Y-1	40 CFR Part 63, Subpart Y	No changing attributes.
23BA301	PROCESS HEATERS/ FURNACES	N/A	R7300-3	30 TAC Chapter 117, Subchapter B	No changing attributes.
23BA302	PROCESS HEATERS/ FURNACES	N/A	R7300-2	30 TAC Chapter 117, Subchapter B	No changing attributes.
23BA302	PROCESS HEATERS/ FURNACES	N/A	63DDDDD -1	40 CFR Part 63, Subpart DDDDD	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
23BC201	PROCESS HEATERS/ FURNACES	N/A	R7300-5	30 TAC Chapter 117, Subchapter B	No changing attributes.
29BA1300	PROCESS HEATERS/ FURNACES	N/A	R7300-2	30 TAC Chapter 117, Subchapter B	No changing attributes.
42BC2001	PROCESS HEATERS/ FURNACES	N/A	63DDDDD -2	40 CFR Part 63, Subpart DDDDD	No changing attributes.
44BA3001	PROCESS HEATERS/ FURNACES	N/A	R7300-2	30 TAC Chapter 117, Subchapter B	No changing attributes.
44BA3001	PROCESS HEATERS/ FURNACES	N/A	63DDDDD -1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
44BA3002	PROCESS HEATERS/ FURNACES	N/A	R7300-3	30 TAC Chapter 117, Subchapter B	No changing attributes.
44BA3002	PROCESS HEATERS/ FURNACES	N/A	63DDDDD -1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
44BA3005	PROCESS HEATERS/ FURNACES	N/A	R7300-2	30 TAC Chapter 117, Subchapter B	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
44BA3005	PROCESS HEATERS/ FURNACES	N/A	63DDDDD -1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
51HTR	PROCESS HEATERS/ FURNACES	N/A	R7300-7	30 TAC Chapter 117, Subchapter B	No changing attributes.
GRP-HEAT1	PROCESS HEATERS/ FURNACES	27BA1000, 28BA1200, 41BA101, 41BA102, 81BA25	R7300-2	30 TAC Chapter 117, Subchapter B	No changing attributes.
GRP-HEAT1	PROCESS HEATERS/ FURNACES	27BA1000, 28BA1200, 41BA101, 41BA102, 81BA25	60DDDDD -1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
GRP-HEATER	PROCESS HEATERS/ FURNACES	40BA1001, 40BA1002, 40BA1101	R2112-001	30 TAC Chapter 112, Sulfur Compounds	No changing attributes.
GRP-HEATER	PROCESS HEATERS/ FURNACES	40BA1001, 40BA1002, 40BA1101	R7300- 2NG	30 TAC Chapter 117, Subchapter B	No changing attributes.
GRP-HEATER	PROCESS HEATERS/ FURNACES	40BA1001, 40BA1002, 40BA1101	63DDDDD -1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
DG-AGIT	SOLVENT DEGREASING MACHINES	N/A	R5412-1	30 TAC Chapter 115, Degreasing Processes	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
DG-AGIT2	SOLVENT DEGREASING MACHINES	N/A	R5412-1	30 TAC Chapter 115, Degreasing Processes	No changing attributes.
27ENG1	SRIC ENGINES	N/A	R7300-1	30 TAC Chapter 117, Subchapter B	No changing attributes.
27ENG1	SRIC ENGINES	N/A	60III-1	40 CFR Part 60, Subpart III	No changing attributes.
27ENG1	SRIC ENGINES	N/A	63ZZZZ-0	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
27ENG2	SRIC ENGINES	N/A	R7300-1	30 TAC Chapter 117, Subchapter B	No changing attributes.
27ENG2	SRIC ENGINES	N/A	60III-1	40 CFR Part 60, Subpart III	No changing attributes.
27ENG2	SRIC ENGINES	N/A	63ZZZZ-0	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
30GG1822	SRIC ENGINES	N/A	R7300-0	30 TAC Chapter 117, Subchapter B	No changing attributes.
30GG1822	SRIC ENGINES	N/A	63ZZZZ-0	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
42GG1730	SRIC ENGINES	N/A	R7300-0	30 TAC Chapter 117, Subchapter B	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
42GG1730	SRIC ENGINES	N/A	63ZZZZ-0	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
47GG1523	SRIC ENGINES	N/A	R7300-1	30 TAC Chapter 117, Subchapter B	No changing attributes.
47GG1523	SRIC ENGINES	N/A	63ZZZZ-0	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
81ENG1	SRIC ENGINES	N/A	R7300-1	30 TAC Chapter 117, Subchapter B	No changing attributes.
81ENG1	SRIC ENGINES	N/A	60IIII-1	40 CFR Part 60, Subpart IIII	No changing attributes.
81ENG1	SRIC ENGINES	N/A	63ZZZZ-0	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
81GEN001	SRIC ENGINES	N/A	R7300-0	30 TAC Chapter 117, Subchapter B	No changing attributes.
81GEN001	SRIC ENGINES	N/A	60IIII-1	40 CFR Part 60, Subpart IIII	No changing attributes.
81GEN001	SRIC ENGINES	N/A	63ZZZZ-1	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
90GG2245	SRIC ENGINES	N/A	R7300-0	30 TAC Chapter 117, Subchapter B	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
90GG2245	SRIC ENGINES	N/A	63ZZZZ-0	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
GRP-ENG	SRIC ENGINES	42GG1848, 42GG1849	R7300-0	30 TAC Chapter 117, Subchapter B	No changing attributes.
GRP-ENG	SRIC ENGINES	42GG1848, 42GG1849	63ZZZZ-0	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
GRP- ENGEMERG	SRIC ENGINES	30PU2991, 30PU2992, 30PU2993, 97GE2999	R7300-0	30 TAC Chapter 117, Subchapter B	No changing attributes.
GRP- ENGEMERG	SRIC ENGINES	30PU2991, 30PU2992, 30PU2993, 97GE2999	60IIII-1	40 CFR Part 60, Subpart IIII	No changing attributes.
GRP- ENGEMERG	SRIC ENGINES	30PU2991, 30PU2992, 30PU2993, 97GE2999	63ZZZZ-1	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
22FB748	STORAGE TANKS/VESSELS	N/A	R5112-2	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
22FB749	STORAGE TANKS/VESSELS	N/A	R5112-2	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
42FB2802	STORAGE TANKS/VESSELS	N/A	R5117-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
42FB2802	STORAGE TANKS/VESSELS	N/A	63CC-1	40 CFR Part 63, Subpart CC	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
45FB6001	STORAGE TANKS/VESSELS	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
45FB6002	STORAGE TANKS/VESSELS	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
45FB6360	STORAGE TANKS/VESSELS	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
45FB7401	STORAGE TANKS/VESSELS	N/A	R5112-3	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
45FB7401	STORAGE TANKS/VESSELS	N/A	60K-3	40 CFR Part 60, Subpart K	No changing attributes.
45FB7402	STORAGE TANKS/VESSELS	N/A	R5112-3	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
45FB7402	STORAGE TANKS/VESSELS	N/A	60Kb-3	40 CFR Part 60, Subpart Kb	No changing attributes.
45FB7403	STORAGE TANKS/VESSELS	N/A	R5112-3	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
45FB7403	STORAGE TANKS/VESSELS	N/A	60Kb-3	40 CFR Part 60, Subpart Kb	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
46FB6301	STORAGE TANKS/VESSELS	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
47FA2	STORAGE TANKS/VESSELS	N/A	R5117-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
47FB321	STORAGE TANKS/VESSELS	N/A	R5112-8	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
47FB321	STORAGE TANKS/VESSELS	N/A	60Kb-9	40 CFR Part 60, Subpart Kb	No changing attributes.
47FB321	STORAGE TANKS/VESSELS	N/A	60QQQ-1	40 CFR Part 60, Subpart QQQ	No changing attributes.
47FB323	STORAGE TANKS/VESSELS	N/A	R5112-8	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
47FB323	STORAGE TANKS/VESSELS	N/A	60Kb-9	40 CFR Part 60, Subpart Kb	No changing attributes.
47FB323	STORAGE TANKS/VESSELS	N/A	60QQQ-1	40 CFR Part 60, Subpart QQQ	No changing attributes.
47FB503	STORAGE TANKS/VESSELS	N/A	R5112-2	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
47FB503	STORAGE TANKS/VESSELS	N/A	60Kb-1	40 CFR Part 60, Subpart Kb	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
47FB504	STORAGE TANKS/VESSELS	N/A	R5112-2	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
47FB504	STORAGE TANKS/VESSELS	N/A	60Kb-1	40 CFR Part 60, Subpart Kb	No changing attributes.
47FB509	STORAGE TANKS/VESSELS	N/A	R5112-2	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
90FB001	STORAGE TANKS/VESSELS	N/A	R5112-5	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
90FB001	STORAGE TANKS/VESSELS	N/A	60Kb-6	40 CFR Part 60, Subpart Kb	No changing attributes.
90FB001	STORAGE TANKS/VESSELS	N/A	63CC-2	40 CFR Part 63, Subpart CC	No changing attributes.
90FB002	STORAGE TANKS/VESSELS	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
90FB002	STORAGE TANKS/VESSELS	N/A	60Kb-4	40 CFR Part 60, Subpart Kb	No changing attributes.
90FB002	STORAGE TANKS/VESSELS	N/A	63CC-1	40 CFR Part 63, Subpart CC	No changing attributes.
90FB004	STORAGE TANKS/VESSELS	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
90FB004	STORAGE TANKS/VESSELS	N/A	60Kb-4	40 CFR Part 60, Subpart Kb	No changing attributes.
90FB004	STORAGE TANKS/VESSELS	N/A	63CC-1	40 CFR Part 63, Subpart CC	No changing attributes.
90FB005	STORAGE TANKS/VESSELS	N/A	R5112-2	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
90FB005	STORAGE TANKS/VESSELS	N/A	63CC-1	40 CFR Part 63, Subpart CC	No changing attributes.
90FB205	STORAGE TANKS/VESSELS	N/A	R5112-6	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
90FB205	STORAGE TANKS/VESSELS	N/A	60Kb-7	40 CFR Part 60, Subpart Kb	No changing attributes.
90FB205	STORAGE TANKS/VESSELS	N/A	63CC-3	40 CFR Part 63, Subpart CC	No changing attributes.
90FB210	STORAGE TANKS/VESSELS	N/A	R5112-002	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
90FB210	STORAGE TANKS/VESSELS	N/A	60Kb-002	40 CFR Part 60, Subpart Kb	No changing attributes.
90FB210	STORAGE TANKS/VESSELS	N/A	63CC-001	40 CFR Part 63, Subpart CC	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
90FB223	STORAGE TANKS/VESSELS	N/A	R5112-2	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
90FB223	STORAGE TANKS/VESSELS	N/A	63CC-5	40 CFR Part 63, Subpart CC	No changing attributes.
90FB229	STORAGE TANKS/VESSELS	N/A	R5112-2	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
90FB229	STORAGE TANKS/VESSELS	N/A	63CC-5	40 CFR Part 63, Subpart CC	No changing attributes.
90FB230	STORAGE TANKS/VESSELS	N/A	R5112-2	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
90FB230	STORAGE TANKS/VESSELS	N/A	60Kb-1	40 CFR Part 60, Subpart Kb	No changing attributes.
90FB230	STORAGE TANKS/VESSELS	N/A	63CC-1	40 CFR Part 63, Subpart CC	No changing attributes.
90FB231	STORAGE TANKS/VESSELS	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
90FB231	STORAGE TANKS/VESSELS	N/A	63CC-2	40 CFR Part 63, Subpart CC	No changing attributes.
90FB234	STORAGE TANKS/VESSELS	N/A	R5115-001	30 TAC Chapter 115, Storage of VOCs	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
90FB234	STORAGE TANKS/VESSELS	N/A	60KB-001	40 CFR Part 60, Subpart Kb	No changing attributes.
90FB234	STORAGE TANKS/VESSELS	N/A	63CC-002	40 CFR Part 63, Subpart CC	No changing attributes.
90FB511	STORAGE TANKS/VESSELS	N/A	R5115-002	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
90FB511	STORAGE TANKS/VESSELS	N/A	60KB-002	40 CFR Part 60, Subpart Kb	No changing attributes.
90FB511	STORAGE TANKS/VESSELS	N/A	63CC-001	40 CFR Part 63, Subpart CC	No changing attributes.
90FB735	STORAGE TANKS/VESSELS	N/A	R5112-2	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
90FB735	STORAGE TANKS/VESSELS	N/A	60Kb-1	40 CFR Part 60, Subpart Kb	No changing attributes.
90FB807	STORAGE TANKS/VESSELS	N/A	R5112-2	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
91FB901	STORAGE TANKS/VESSELS	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
91FB901	STORAGE TANKS/VESSELS	N/A	60Kb-4	40 CFR Part 60, Subpart Kb	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
91FB901	STORAGE TANKS/VESSELS	N/A	63CC-1	40 CFR Part 63, Subpart CC	No changing attributes.
91FB907	STORAGE TANKS/VESSELS	N/A	R5117-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
91FB907	STORAGE TANKS/VESSELS	N/A	63CC-2	40 CFR Part 63, Subpart CC	No changing attributes.
91FB912	STORAGE TANKS/VESSELS	N/A	R5112-7	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
91FB912	STORAGE TANKS/VESSELS	N/A	60Kb-8	40 CFR Part 60, Subpart Kb	No changing attributes.
91FB912	STORAGE TANKS/VESSELS	N/A	63CC-4	40 CFR Part 63, Subpart CC	No changing attributes.
91FB913	STORAGE TANKS/VESSELS	N/A	R5112-7	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
91FB913	STORAGE TANKS/VESSELS	N/A	60Kb-8	40 CFR Part 60, Subpart Kb	No changing attributes.
91FB913	STORAGE TANKS/VESSELS	N/A	63CC-4	40 CFR Part 63, Subpart CC	No changing attributes.
91FB917	STORAGE TANKS/VESSELS	N/A	R5112-2	30 TAC Chapter 115, Storage of VOCs	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
91FB917	STORAGE TANKS/VESSELS	N/A	60Kb-1	40 CFR Part 60, Subpart Kb	No changing attributes.
91FB917	STORAGE TANKS/VESSELS	N/A	63CC-1	40 CFR Part 63, Subpart CC	No changing attributes.
91FB918	STORAGE TANKS/VESSELS	N/A	R5112-2	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
91FB918	STORAGE TANKS/VESSELS	N/A	60Kb-1	40 CFR Part 60, Subpart Kb	No changing attributes.
91FB918	STORAGE TANKS/VESSELS	N/A	63CC-1	40 CFR Part 63, Subpart CC	No changing attributes.
91FB920	STORAGE TANKS/VESSELS	N/A	R5112-2	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
91FB920	STORAGE TANKS/VESSELS	N/A	60Kb-1	40 CFR Part 60, Subpart Kb	No changing attributes.
91FB920	STORAGE TANKS/VESSELS	N/A	63CC-1	40 CFR Part 63, Subpart CC	No changing attributes.
91FB921	STORAGE TANKS/VESSELS	N/A	R5112-2	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
91FB921	STORAGE TANKS/VESSELS	N/A	60Kb-1	40 CFR Part 60, Subpart Kb	No changing attributes.
91FB921	STORAGE TANKS/VESSELS	N/A	63CC-1	40 CFR Part 63, Subpart CC	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
91FB922	STORAGE TANKS/VESSELS	N/A	R5112-2	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
91FB922	STORAGE TANKS/VESSELS	N/A	60Kb-1	40 CFR Part 60, Subpart Kb	No changing attributes.
91FB922	STORAGE TANKS/VESSELS	N/A	63CC-1	40 CFR Part 63, Subpart CC	No changing attributes.
91FB924	STORAGE TANKS/VESSELS	N/A	R5112-2	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
91FB924	STORAGE TANKS/VESSELS	N/A	60Kb-1	40 CFR Part 60, Subpart Kb	No changing attributes.
91FB924	STORAGE TANKS/VESSELS	N/A	63CC-1	40 CFR Part 63, Subpart CC	No changing attributes.
91FB927	STORAGE TANKS/VESSELS	N/A	R5117-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
91FB927	STORAGE TANKS/VESSELS	N/A	63CC-1	40 CFR Part 63, Subpart CC	No changing attributes.
91FB931	STORAGE TANKS/VESSELS	N/A	R5112-2	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
91FB931	STORAGE TANKS/VESSELS	N/A	60Kb-1	40 CFR Part 60, Subpart Kb	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
91FB931	STORAGE TANKS/VESSELS	N/A	63CC-1	40 CFR Part 63, Subpart CC	No changing attributes.
92FA4001	STORAGE TANKS/VESSELS	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
92FA4002	STORAGE TANKS/VESSELS	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
GRP-TK1	STORAGE TANKS/VESSELS	90FB722, 90FB723	R5112-2	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
GRP-TK1	STORAGE TANKS/VESSELS	90FB722, 90FB723	60Kb-1	40 CFR Part 60, Subpart Kb	No changing attributes.
GRP-TK10	STORAGE TANKS/VESSELS	91FB370, 91FB371	R5112-2	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
GRP-TK10	STORAGE TANKS/VESSELS	91FB370, 91FB371	63CC-1	40 CFR Part 63, Subpart CC	No changing attributes.
GRP-TK12	STORAGE TANKS/VESSELS	90FB213, 90FB215, 90FB216, 90FB224, 91FB411, 91FB413, 91FB909, 91FB916	R5117-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
GRP-TK12	STORAGE TANKS/VESSELS	90FB213, 90FB215, 90FB216, 90FB224, 91FB411, 91FB413, 91FB909, 91FB916	63CC-1	40 CFR Part 63, Subpart CC	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
GRP-TK2	STORAGE TANKS/VESSELS	90FB006, 90FB232, 90FB233	R5117-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
GRP-TK2	STORAGE TANKS/VESSELS	90FB006, 90FB232, 90FB233	63CC-5	40 CFR Part 63, Subpart CC	No changing attributes.
GRP-TK6	STORAGE TANKS/VESSELS	23FB4501V, 23FB4503V, 42FB2097V, 42FB2099V, 42FB2499, 42FB2699	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
GRP-TK7	STORAGE TANKS/VESSELS	90FB228, 90FB505, 90FB506, 90FB507	R5112-2	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
GRP-TK7	STORAGE TANKS/VESSELS	90FB228, 90FB505, 90FB506, 90FB507	63CC-1	40 CFR Part 63, Subpart CC	No changing attributes.
GRP-TK8	STORAGE TANKS/VESSELS	90FB003, 90FB225, 90FB226, 91FB911	R5112-2	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
GRP-TK8	STORAGE TANKS/VESSELS	90FB003, 90FB225, 90FB226, 91FB911	63CC-1	40 CFR Part 63, Subpart CC	No changing attributes.
5GTRANSFER	TRANSFER SYSTEM	N/A	63GGGGG- 1	40 CFR Part 63, Subpart GGGGG	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
EJECTORS	VACUUM PRODUCING SYSTEMS	23EA301, 23FA206, EJECTOR_AU, EJECTOR_BU, EJECTOR_CU, EJECTOR_DU	R5311	30 TAC Chapter 115, Unit Turn & Vac System- Pet Ref	No changing attributes.
47FB503	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	R5132-1	30 TAC Chapter 115, Water Separation	No changing attributes.
47FB504	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	R5132-1	30 TAC Chapter 115, Water Separation	No changing attributes.
47FB509	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	R5132-1	30 TAC Chapter 115, Water Separation	No changing attributes.
47GF5401	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	R5132-1	30 TAC Chapter 115, Water Separation	No changing attributes.
47GF5401	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	60QQQ-1	40 CFR Part 60, Subpart QQQ	No changing attributes.
5G-C001OWS	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	63GGGGG- 1	40 CFR Part 63, Subpart GGGGG	No changing attributes.

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
44BA3002	EU	60Dc-1	SO ₂	40 CFR Part 60, Subpart Dc	§ 60.40c(a)	This subpart applies to each steam generating unit constructed, reconstructed, or modified after 6/9/89 and that has a maximum design heat input capacity of 2.9-29 megawatts (MW).	None	§ 60.48c(g)(1) § 60.48c(g)(2) § 60.48c(g)(3) § 60.48c(i)	[G]§ 60.48c(a) § 60.48c(j)
44BA3002	EU	60Dc-1	PM	40 CFR Part 60, Subpart Dc	§ 60.40c(a)	This subpart applies to each steam generating unit constructed, reconstructed, or modified after 6/9/89 and that has a maximum design heat input capacity of 2.9-29 megawatts (MW).	None	§ 60.48c(g)(1) § 60.48c(g)(2) § 60.48c(g)(3) § 60.48c(i)	[G]§ 60.48c(a) § 60.48c(j)
44BA3002	EU	60Dc-1	PM (OPACITY)	40 CFR Part 60, Subpart Dc	§ 60.40c(a)	This subpart applies to each steam generating unit constructed, reconstructed, or modified after 6/9/89 and that has a maximum design heat input capacity of 2.9-29 megawatts (MW).	None	§ 60.48c(g)(1) § 60.48c(g)(2) § 60.48c(g)(3) § 60.48c(i)	[G]§ 60.48c(a) § 60.48c(j)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
50BFo2	EU	R7300-6	NO _x	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(1)(A) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO _x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(1) § 117.335(g) § 117.340(a) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) [G]§ 117.340(c)(3) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
50BFo2	EU	R7300-6	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1) § 117.8120	CO emissions must not exceed 400 ppmv at 3.0% O ₂ , dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a) § 117.340(b)(1) § 117.340(b)(3) § 117.340(e) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120(1) § 117.8120(1)(A)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
50BF02	EU	R7300-6	NH ₃	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(2) § 117.310(c)(2)(A)	For boilers that inject urea or ammonia into the exhaust stream for NO _x control, ammonia emissions must not exceed 10 ppmv at 3.0% O ₂ , dry.	§ 117.335(a)(2) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(d) § 117.8000(b) § 117.8000(c) § 117.8000(c)(3) § 117.8000(c)(4) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8130 § 117.8130(3)	§ 117.345(a) § 117.345(f) § 117.345(f)(11) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
50BF02	EU	60Db-1	SO ₂	40 CFR Part 60, Subpart Db	§ 60.104(a)(1) § 60.104	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide in excess of 230 mg/dscm (0.10 gr/dscf). The combustion in a flare of process upset gases or fuel gas that is released to the flare as a result of relief valve leakage or other emergency malfunctions is exempt from this paragraph.	§ 60.105(a) § 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.105(e) § 60.105(e)(3)(ii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4)	§ 60.105(e) § 60.105(e)(3)(ii) § 60.107(e) § 60.107(f)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
50BF02	EU	60Db-1	PM	40 CFR Part 60, Subpart Db	§ 60.40b(a)	This subpart applies to each steam generating unit constructed, modified, or reconstructed after 6/19/84, and that has a heat input capacity from fuels combusted in the unit > 29 MW (100 MMBtu/hr).	None	[G]§ 60.49b(d) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3)
50BF02	EU	60Db-1	PM (OPACITY)	40 CFR Part 60, Subpart Db	§ 60.40b(a)	This subpart applies to each steam generating unit constructed, modified, or reconstructed after 6/19/84, and that has a heat input capacity from fuels combusted in the unit > 29 MW (100 MMBtu/hr).	None	[G]§ 60.49b(d) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3)
50BF02	EU	60Db-1	NO _x	40 CFR Part 60, Subpart Db	§ 60.44b(l)(1) § 60.44b(h) § 60.44b(i) § 60.46b(a)	Affected facilities combusting coal, oil, or natural gas, or a mixture of these fuels, or any other fuels: a limit of 86 ng/JI (0.20 lb/million Btu) heat input unless the affected facility meets the specified requirements.	§ 60.46b(c) § 60.46b(e) § 60.46b(e)(1) § 60.46b(e)(3) [G]§ 60.48b(b) § 60.48b(c) § 60.48b(d) § 60.48b(e) [G]§ 60.48b(e)(2) § 60.48b(e)(3) § 60.48b(f)	[G]§ 60.48b(b) § 60.48b(c) [G]§ 60.49b(d) [G]§ 60.49b(g) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3) § 60.49b(b) § 60.49b(i) § 60.49b(v) § 60.49b(w)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
50BF02	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
50BF03	EU	R7300-6	NO _x	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(1)(A) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO _x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(1) § 117.335(g) § 117.340(a) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) [G]§ 117.340(c)(3) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
50BF03	EU	R7300-6	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1) § 117.8120	CO emissions must not exceed 400 ppmv at 3.0% O ₂ , dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a) § 117.340(b)(1) § 117.340(b)(3) § 117.340(e) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120(1) § 117.8120(1)(A)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
50BF03	EU	R7300-6	NH ₃	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(2) § 117.310(c)(2)(A)	For boilers that inject urea or ammonia into the exhaust stream for NO _x control, ammonia emissions must not exceed 10 ppmv at 3.0% O ₂ , dry.	§ 117.335(a)(2) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(d) § 117.8000(b) § 117.8000(c) § 117.8000(c)(3) § 117.8000(c)(4) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8130 § 117.8130(3)	§ 117.345(a) § 117.345(f) § 117.345(f)(11) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
50BF03	EU	60Db-1	SO ₂	40 CFR Part 60, Subpart Db	§ 60.104(a)(1) § 60.104	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide in excess of 230 mg/dscm (0.10 gr/dscf). The combustion in a flare of process upset gases or fuel gas that is released to the flare as a result of relief valve leakage or other emergency malfunctions is exempt from this paragraph.	§ 60.105(a) § 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.105(e) § 60.105(e)(3)(ii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4)	§ 60.105(e) § 60.105(e)(3)(ii) § 60.107(e) § 60.107(f)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
50BF03	EU	60Db-1	PM	40 CFR Part 60, Subpart Db	§ 60.40b(a)	This subpart applies to each steam generating unit constructed, modified, or reconstructed after 6/19/84, and that has a heat input capacity from fuels combusted in the unit > 29 MW (100 MMBtu/hr).	None	[G]§ 60.49b(d) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3)
50BF03	EU	60Db-1	PM (OPACITY)	40 CFR Part 60, Subpart Db	§ 60.40b(a)	This subpart applies to each steam generating unit constructed, modified, or reconstructed after 6/19/84, and that has a heat input capacity from fuels combusted in the unit > 29 MW (100 MMBtu/hr).	None	[G]§ 60.49b(d) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3)
50BF03	EU	60Db-1	NO _x	40 CFR Part 60, Subpart Db	§ 60.44b(l)(1) § 60.44b(h) § 60.44b(i) § 60.46b(a)	Affected facilities combusting coal, oil, or natural gas, or a mixture of these fuels, or any other fuels: a limit of 86 ng/JI (0.20 lb/million Btu) heat input unless the affected facility meets the specified requirements.	§ 60.46b(c) § 60.46b(e) § 60.46b(e)(1) § 60.46b(e)(3) [G]§ 60.48b(b) § 60.48b(c) § 60.48b(d) § 60.48b(e) [G]§ 60.48b(e)(2) § 60.48b(e)(3) § 60.48b(f)	[G]§ 60.48b(b) § 60.48b(c) [G]§ 60.49b(d) [G]§ 60.49b(g) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3) § 60.49b(b) § 60.49b(i) § 60.49b(v) § 60.49b(w)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
50BF03	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
81BFo1	EU	R7300-6	NO _x	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(1)(A) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO _x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(1) § 117.335(g) § 117.340(a) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) [G]§ 117.340(c)(3) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
81BF01	EU	R7300-6	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1) § 117.8120	CO emissions must not exceed 400 ppmv at 3.0% O ₂ , dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a) § 117.340(b)(1) § 117.340(b)(3) § 117.340(e) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120(1) § 117.8120(1)(A)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
81BFo1	EU	R7300-6	NH ₃	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(2) § 117.310(c)(2)(A)	For boilers that inject urea or ammonia into the exhaust stream for NO _x control, ammonia emissions must not exceed 10 ppmv at 3.0% O ₂ , dry.	§ 117.335(a)(2) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(d) § 117.8000(b) § 117.8000(c) § 117.8000(c)(3) § 117.8000(c)(4) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8130 § 117.8130(3)	§ 117.345(a) § 117.345(f) § 117.345(f)(11) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
81BFo1	EU	60Db-1	SO ₂	40 CFR Part 60, Subpart Db	§ 60.104(a)(1) § 60.104	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide in excess of 230 mg/dscm (0.10 gr/dscf). The combustion in a flare of process upset gases or fuel gas that is released to the flare as a result of relief valve leakage or other emergency malfunctions is exempt from this paragraph.	§ 60.105(a) § 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.105(e) § 60.105(e)(3)(ii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4)	§ 60.105(e) § 60.105(e)(3)(ii) § 60.107(e) § 60.107(f)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
81BF01	EU	60Db-1	PM	40 CFR Part 60, Subpart Db	§ 60.40b(a)	This subpart applies to each steam generating unit constructed, modified, or reconstructed after 6/19/84, and that has a heat input capacity from fuels combusted in the unit > 29 MW (100 MMBtu/hr).	None	[G]§ 60.49b(d) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3)
81BF01	EU	60Db-1	PM (OPACITY)	40 CFR Part 60, Subpart Db	§ 60.40b(a)	This subpart applies to each steam generating unit constructed, modified, or reconstructed after 6/19/84, and that has a heat input capacity from fuels combusted in the unit > 29 MW (100 MMBtu/hr).	None	[G]§ 60.49b(d) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3)
81BF01	EU	60Db-1	NO _x	40 CFR Part 60, Subpart Db	§ 60.44b(l)(1) § 60.44b(h) § 60.44b(i) § 60.46b(a)	Affected facilities combusting coal, oil, or natural gas, or a mixture of these fuels, or any other fuels: a limit of 86 ng/JI (0.20 lb/million Btu) heat input unless the affected facility meets the specified requirements.	§ 60.46b(c) § 60.46b(e) § 60.46b(e)(1) § 60.46b(e)(3) [G]§ 60.48b(b) § 60.48b(c) § 60.48b(d) § 60.48b(e) [G]§ 60.48b(e)(2) § 60.48b(e)(3) § 60.48b(f)	[G]§ 60.48b(b) § 60.48b(c) [G]§ 60.49b(d) [G]§ 60.49b(g) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3) § 60.49b(b) § 60.49b(h) § 60.49b(i) § 60.49b(v) § 60.49b(w)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
81BF01	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
5GCVS	EU	63GGGGG-1	112(B) HAPS	40 CFR Part 63, Subpart GGGGG	§ 63.7886(b)(1)(ii) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart GGGGG	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart GGGGG	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart GGGGG	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart GGGGG	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart GGGGG
81SKD5602	EU	63GGGGG-1	112(B) HAPS	40 CFR Part 63, Subpart GGGGG	§ 63.7886(b)(1)(ii) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart GGGGG	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart GGGGG	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart GGGGG	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart GGGGG	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart GGGGG

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
81SKD5603	EU	63GGGGG-1	112(B) HAPS	40 CFR Part 63, Subpart GGGGG	§ 63.7886(b)(1)(ii) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart GGGGG	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart GGGGG	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart GGGGG	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart GGGGG	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart GGGGG
91CB915	EU	63GGGGG-1	112(B) HAPS	40 CFR Part 63, Subpart GGGGG	§ 63.7886(b)(1)(ii) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart GGGGG	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart GGGGG	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart GGGGG	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart GGGGG	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart GGGGG

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
22AVENT	EP	R1111-3	OPACITY	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(B)	Visible emissions from any stationary vent shall not exceed an opacity of 20% averaged over a six-minute period for any source on which construction was begun after January 31, 1972. The emissions from this vent originate from colorless VOCs, non-fuming liquids, or other sources that are not capable of obstructing the transmission of light. These vents are not capable of exceeding the opacity standards of 30 TAC Chapter 111 and therefore no monitoring is required to demonstrate compliance.	None	None	None
22AVENT	EP	R5127-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
22EG400	EP	R1111-3	OPACITY	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(B)	Visible emissions from any stationary vent shall not exceed an opacity of 20% averaged over a six-minute period for any source on which construction was begun after January 31, 1972. The emissions from this vent originate from colorless VOCs, non-fuming liquids, or other sources that are not capable of obstructing the transmission of light. These vents are not capable of exceeding the opacity standards of 30 TAC Chapter 111 and therefore no monitoring is required to demonstrate compliance.	None	None	None
22EG400	EP	R5127-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
22FA225	EP	R1111-3	OPACITY	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(B)	Visible emissions from any stationary vent shall not exceed an opacity of 20% averaged over a six-minute period for any source on which construction was begun after January 31, 1972. The emissions from this vent originate from colorless VOCs, non-fuming liquids, or other sources that are not capable of obstructing the transmission of light. These vents are not capable of exceeding the opacity standards of 30 TAC Chapter 111 and therefore no monitoring is required to demonstrate compliance.	None	None	None
22FA225	EP	R5127-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
42CB2201	EP	R1111-2	OPACITY	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(B) § 111.111(a)(1)(E) § 111.111(a)(3)	Visible emissions from any stationary vent shall not exceed an opacity of 20% averaged over a six minute period for any source on which construction was begun after January 31, 1972.	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None
GRP-DISTILL	EP	R5127-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
GRP-DISTILL	EP	R5127-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(B) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream specified in § 115.121(a)(1) of this title with a concentration of VOC < 612 ppmv is exempt from § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
GRP-HEAT1	EP	R1111-0	OPACITY	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(A) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall not exceed an opacity of 30% averaged over a six minute period.	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-HEATER	EP	R1111-1	OPACITY	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(B) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall not exceed an opacity of 20% averaged over a six minute period for any source on which construction was begun after January 31, 1972.	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None
GRP-HEATER	EP	R5725-001	HIGHLY REACTIVE VOC	30 TAC Chapter 115, HRVOC Vent Gas	§ 115.722(c)(1) § 115.722(c)(3) § 115.725(a)(2)(A) § 115.725(a)(2)(B) § 115.725(a)(2)(C) § 115.725(a)(2)(D) § 115.725(a)(3) [G]§ 115.725(a)(4) [G]§ 115.725(l) [G]§ 115.726(a)(2)	HRVOC emissions at each site located in Harris County that is subject to this division or Division 2 of this subchapter must not exceed 1,200 pounds of HRVOC per one-hour block period from any flare, vent, pressure relief valve, cooling tower, or any combination.	§ 115.725(a) § 115.725(a)(2)(A) § 115.725(a)(2)(B) § 115.725(a)(2)(C) § 115.725(a)(2)(D) § 115.725(a)(3) § 115.725(a)(3)(A) [G]§ 115.725(a)(4) § 115.725(a)(5) [G]§ 115.725(l) § 115.725(n)	§ 115.726(b)(1) § 115.726(b)(2) § 115.726(b)(3) [G]§ 115.726(g) [G]§ 115.726(h) § 115.726(i) § 115.726(j)(1) § 115.726(j)(2)	[G]§ 115.725(a)(4) § 115.725(a)(5) § 115.725(n) [G]§ 115.726(a)(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-LABVENT	EP	R1111-3	OPACITY	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(B)	Visible emissions from any stationary vent shall not exceed an opacity of 20% averaged over a six-minute period for any source on which construction was begun after January 31, 1972. The emissions from this vent originate from colorless VOCs, non-fuming liquids, or other sources that are not capable of obstructing the transmission of light. These vents are not capable of exceeding the opacity standards of 30 TAC Chapter 111 and therefore no monitoring is required to demonstrate compliance.	None	None	None
GRP-LABVENT	EP	R5127-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-PRV	EP	R1111-3	OPACITY	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(B)	Visible emissions from any stationary vent shall not exceed an opacity of 20% averaged over a six-minute period for any source on which construction was begun after January 31, 1972. The emissions from this vent originate from colorless VOCs, non-fuming liquids, or other sources that are not capable of obstructing the transmission of light. These vents are not capable of exceeding the opacity standards of 30 TAC Chapter 111 and therefore no monitoring is required to demonstrate compliance.	None	None	None
GRP-PRV	EP	R5127-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-REGiVENT	EP	R1111-1	OPACITY	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(B) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall not exceed an opacity of 20% averaged over a six minute period for any source on which construction was begun after January 31, 1972.	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None
GRP-VENTLUBE	EP	R1111-3	OPACITY	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(B)	Visible emissions from any stationary vent shall not exceed an opacity of 20% averaged over a six-minute period for any source on which construction was begun after January 31, 1972. The emissions from this vent originate from colorless VOCs, non-fuming liquids, or other sources that are not capable of obstructing the transmission of light. These vents are not capable of exceeding the opacity standards of 30 TAC Chapter 111 and therefore no monitoring is required to demonstrate compliance.	None	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-VENTLUBE	EP	R5127-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
PROCVENT	EP	R1111-3	OPACITY	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(B)	Visible emissions from any stationary vent shall not exceed an opacity of 20% averaged over a six-minute period for any source on which construction was begun after January 31, 1972. The emissions from this vent originate from colorless VOCs, non-fuming liquids, or other sources that are not capable of obstructing the transmission of light. These vents are not capable of exceeding the opacity standards of 30 TAC Chapter 111 and therefore no monitoring is required to demonstrate compliance.	None	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
PROCVENT	EP	R5127-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
23BA302	EU	60J-2	HYDROGEN SULFIDE	40 CFR Part 60, Subpart J	§ 60.104(a)(1) § 60.104 § 60.104(a)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide in excess of 230 mg/dscm (0.10 gr/dscf). The combustion in a flare of process upset gases or fuel gas that is released to the flare as a result of relief valve leakage or other emergency malfunctions is exempt from this paragraph.	§ 60.105(a) [G]§ 60.105(a)(4)(iv) [G]§ 60.105(b) § 60.105(e) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a) [G]§ 60.105(a)(4)(iv) § 60.107(e)	[G]§ 60.105(b) § 60.105(e) § 60.107(f) § 60.107(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
30FL1	EU	60Ja-1	HYDROGEN SULFIDE	40 CFR Part 60, Subpart Ja	§ 60.102a(g)(1)(ii) § 60.102a(a) § 60.102a(g) § 60.102a(g)(1) § 60.102a(g)(3) § 60.102a(h) § 60.102a(i) [G]§ 60.103a(a) § 60.103a(b)	For each fuel gas combustion device the owner or operator shall not burn in any fuel gas combustion device any fuel gas that contains H ₂ S in excess of 162 ppmv determined hourly on a 3-hour rolling average basis and H ₂ S in excess of 60 ppmv determined daily on a 365 successive calendar day rolling average basis.	[G]§ 60.103a(a) § 60.104a(a) § 60.104a(c) § 60.104a(i) § 60.104a(i)(1) § 60.104a(i)(2) § 60.104a(i)(3) [G]§ 60.104a(i)(4) [G]§ 60.104a(j) § 60.107a(a) [G]§ 60.107a(a)(2) [G]§ 60.107a(d) [G]§ 60.107a(e) § 60.107a(f) § 60.107a(f)(2) § 60.107a(f)(4)	§ 60.108a(a) § 60.108a(c) § 60.108a(c)(1) [G]§ 60.108a(c)(6) [G]§ 60.108a(d)	§ 60.108a(a) § 60.108a(b) [G]§ 60.108a(d)
30FL6	EU	60Ja-1	HYDROGEN SULFIDE	40 CFR Part 60, Subpart Ja	§ 60.102a(g)(1)(ii) § 60.102a(a) § 60.102a(g) § 60.102a(g)(1) § 60.102a(g)(3) § 60.102a(h) § 60.102a(i) [G]§ 60.103a(a) § 60.103a(b)	For each fuel gas combustion device the owner or operator shall not burn in any fuel gas combustion device any fuel gas that contains H ₂ S in excess of 162 ppmv determined hourly on a 3-hour rolling average basis and H ₂ S in excess of 60 ppmv determined daily on a 365 successive calendar day rolling average basis.	[G]§ 60.103a(a) § 60.104a(a) § 60.104a(c) § 60.104a(i) § 60.104a(i)(1) § 60.104a(i)(2) § 60.104a(i)(3) [G]§ 60.104a(i)(4) [G]§ 60.104a(j) § 60.107a(a) [G]§ 60.107a(a)(2) [G]§ 60.107a(d) [G]§ 60.107a(e) § 60.107a(f) § 60.107a(f)(2) § 60.107a(f)(4)	§ 60.108a(a) § 60.108a(c) § 60.108a(c)(1) [G]§ 60.108a(c)(6) [G]§ 60.108a(d)	§ 60.108a(a) § 60.108a(b) [G]§ 60.108a(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
39CB2001	EU	60JTGI-1	SO ₂	40 CFR Part 60, Subpart J	§ 60.104(a)(2)(i) § 60.104 § 60.104(a) § 60.104(a)(2)	No owner or operator subject to the provisions of this subpart shall discharge or cause the discharge from any Claus sulfur recovery plant with an oxidation control system or a reduction control system followed by incineration any gases containing in excess of 250 ppm by volume (dry basis) of sulfur dioxide at zero percent excess air into the atmosphere.	§ 60.105(a) [G]§ 60.105(a)(5) § 60.105(e) § 60.105(e)(4)(i) § 60.106(a) [G]§ 60.106(f)	§ 60.105(a) [G]§ 60.105(a)(5)	§ 60.105(e) § 60.105(e)(4)(i) § 60.107(f) § 60.107(g)
39CB2001	EU	63UUU-1	SO ₂	40 CFR Part 63, Subpart UUU	§ 63.1568(a)(1)-Table29.1.a § 63.1568(a)(1) § 63.1568(a)(2) § 63.1568(a)(2)-Table30.1 § 63.1568(a)(3) § 63.1568(b)(3) § 63.1568(b)(4) § 63.1568(b)(5) § 63.1568(b)(5)-Table33.1.a § 63.1568(c)(1) § 63.1568(c)(1)-Table35.1 § 63.1568(c)(2) § 63.1570(a) § 63.1570(c) § 63.1570(d) § 63.1570(g)	For each new or existing Claus SRU part of a sulfur recovery plant of 20 long tons per day or more and subject to NSPS for sulfur oxides in 40 CFR §60.104(a)(2), you must meet the emission limit for each process vent of 250ppmv (dry basis) of sulfur dioxide (SO ₂) at zero percent excess air if you use an oxidation or reduction control system followed by incineration.	§ 63.1568(b)(1) § 63.1568(b)(1)-Table31.1.a § 63.1568(c)(1)-Table34.1.a § 63.1572(a)(1)-Table40.4 § 63.1572(a)(1)-Table40.8 § 63.1572(a)(2) § 63.1572(a)(3) § 63.1572(a)(4) [G]§ 63.1572(d)	§ 63.1568(b)(1)-Table31.1.a § 63.1568(c)(1)-Table34.1.a § 63.1570(c) [G]§ 63.1576(a) [G]§ 63.1576(b) § 63.1576(d) § 63.1576(e) § 63.1576(f) § 63.1576(g) § 63.1576(h) § 63.1576(i)	§ 63.1568(b)(6) § 63.1568(b)(7) § 63.1570(f) § 63.1571(a) [G]§ 63.1574(a) § 63.1574(d) § 63.1574(d)-Table42.1 § 63.1574(d)-Table42.2 § 63.1574(d)-Table42.3 § 63.1575(a) § 63.1575(a)-Table43.1 [G]§ 63.1575(b) [G]§ 63.1575(c) [G]§ 63.1575(e) [G]§ 63.1575(f) § 63.1575(g) [G]§ 63.1575(h)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
39FA1006	EU	60JSP-1B	SO ₂	40 CFR Part 60, Subpart J	§ 60.104(a)(2)(i) § 60.104 § 60.104(a) § 60.104(a)(2)	No owner or operator subject to the provisions of this subpart shall discharge or cause the discharge from any Claus sulfur recovery plant with an oxidation control system or a reduction control system followed by incineration any gases containing in excess of 250 ppm by volume (dry basis) of sulfur dioxide at zero percent excess air into the atmosphere.	§ 60.105(a) [G]§ 60.105(a)(5) § 60.105(e) § 60.105(e)(4)(i) § 60.106(a) [G]§ 60.106(f)	§ 60.105(a) [G]§ 60.105(a)(5)	§ 60.105(e) § 60.105(e)(4)(i) § 60.107(f) § 60.107(g)
39FA1006	EU	60JSP-1C	SO ₂	40 CFR Part 60, Subpart J	§ 60.104(a)(2)(i) § 60.104 § 60.104(a) § 60.104(a)(2)	No owner or operator subject to the provisions of this subpart shall discharge or cause the discharge from any Claus sulfur recovery plant with an oxidation control system or a reduction control system followed by incineration any gases containing in excess of 250 ppm by volume (dry basis) of sulfur dioxide at zero percent excess air into the atmosphere.	§ 60.105(a) [G]§ 60.105(a)(5) § 60.105(e) § 60.105(e)(4)(i) § 60.106(a) [G]§ 60.106(f)	§ 60.105(a) [G]§ 60.105(a)(5)	§ 60.105(e) § 60.105(e)(4)(i) § 60.107(f) § 60.107(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
39FA1006	EU	63UUU-1	SO ₂	40 CFR Part 63, Subpart UUU	§ 63.1568(a)(1)-Table29.1.a § 63.1568(a)(1) § 63.1568(a)(2) § 63.1568(a)(2)-Table30.1 § 63.1568(a)(3) § 63.1568(b)(3) § 63.1568(b)(4) § 63.1568(b)(5) § 63.1568(b)(5)-Table33.1.a § 63.1568(c)(1) § 63.1568(c)(1)-Table35.1 § 63.1568(c)(2) § 63.1570(a) § 63.1570(c) § 63.1570(d) § 63.1570(g)	For each new or existing Claus SRU part of a sulfur recovery plant of 20 long tons per day or more and subject to NSPS for sulfur oxides in 40 CFR §60.104(a)(2), you must meet the emission limit for each process vent of 250ppmv (dry basis) of sulfur dioxide (SO ₂) at zero percent excess air if you use an oxidation or reduction control system followed by incineration.	§ 63.1568(b)(1) § 63.1568(b)(1)-Table31.1.a § 63.1568(c)(1)-Table34.1.a § 63.1572(a)(1)-Table40.4 § 63.1572(a)(1)-Table40.8 § 63.1572(a)(2) § 63.1572(a)(3) § 63.1572(a)(4) [G]§ 63.1572(d)	§ 63.1568(b)(1)-Table31.1.a § 63.1568(c)(1)-Table34.1.a § 63.1570(c) [G]§ 63.1576(a) [G]§ 63.1576(b) § 63.1576(d) § 63.1576(e) § 63.1576(f) § 63.1576(g) § 63.1576(h) § 63.1576(i)	§ 63.1568(b)(6) § 63.1568(b)(7) § 63.1570(f) § 63.1571(a) [G]§ 63.1574(a) § 63.1574(d) § 63.1574(d)-Table42.1 § 63.1574(d)-Table42.2 § 63.1574(d)-Table42.3 § 63.1575(a) § 63.1575(a)-Table43.1 [G]§ 63.1575(b) [G]§ 63.1575(c) [G]§ 63.1575(e) [G]§ 63.1575(f) § 63.1575(g) [G]§ 63.1575(h)
39FB1001	EU	60JSP-1B	SO ₂	40 CFR Part 60, Subpart J	§ 60.104(a)(2)(i) § 60.104 § 60.104(a) § 60.104(a)(2)	No owner or operator subject to the provisions of this subpart shall discharge or cause the discharge from any Claus sulfur recovery plant with an oxidation control system or a reduction control system followed by incineration any gases containing in excess of 250 ppm by volume (dry basis) of sulfur dioxide at zero percent excess air into the atmosphere.	§ 60.105(a) [G]§ 60.105(a)(5) § 60.105(e) § 60.105(e)(4)(i) § 60.106(a) [G]§ 60.106(f)	§ 60.105(a) [G]§ 60.105(a)(5)	§ 60.105(e) § 60.105(e)(4)(i) § 60.107(f) § 60.107(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
39FB1001	EU	60JSP-1C	SO ₂	40 CFR Part 60, Subpart J	§ 60.104(a)(2)(i) § 60.104 § 60.104(a) § 60.104(a)(2)	No owner or operator subject to the provisions of this subpart shall discharge or cause the discharge from any Claus sulfur recovery plant with an oxidation control system or a reduction control system followed by incineration any gases containing in excess of 250 ppm by volume (dry basis) of sulfur dioxide at zero percent excess air into the atmosphere.	§ 60.105(a) [G]§ 60.105(a)(5) § 60.105(e) § 60.105(e)(4)(i) § 60.106(a) [G]§ 60.106(f)	§ 60.105(a) [G]§ 60.105(a)(5)	§ 60.105(e) § 60.105(e)(4)(i) § 60.107(f) § 60.107(g)
39FB1001	EU	63UUU-1	SO ₂	40 CFR Part 63, Subpart UUU	§ 63.1568(a)(1)-Table29.1.a § 63.1568(a)(1) § 63.1568(a)(2) § 63.1568(a)(2)-Table30.1 § 63.1568(a)(3) § 63.1568(b)(3) § 63.1568(b)(4) § 63.1568(b)(5) § 63.1568(b)(5)-Table33.1.a § 63.1568(c)(1) § 63.1568(c)(1)-Table35.1 § 63.1568(c)(2) § 63.1570(a) § 63.1570(c) § 63.1570(d) § 63.1570(g)	For each new or existing Claus SRU part of a sulfur recovery plant of 20 long tons per day or more and subject to NSPS for sulfur oxides in 40 CFR §60.104(a)(2), you must meet the emission limit for each process vent of 250ppmv (dry basis) of sulfur dioxide (SO ₂) at zero percent excess air if you use an oxidation or reduction control system followed by incineration.	§ 63.1568(b)(1) § 63.1568(b)(1)-Table31.1.a § 63.1568(c)(1)-Table34.1.a § 63.1572(a)(1)-Table40.4 § 63.1572(a)(1)-Table40.8 § 63.1572(a)(2) § 63.1572(a)(3) § 63.1572(a)(4) [G]§ 63.1572(d)	§ 63.1568(b)(1)-Table31.1.a § 63.1568(c)(1)-Table34.1.a § 63.1570(c) [G]§ 63.1576(a) [G]§ 63.1576(b) § 63.1576(d) § 63.1576(e) § 63.1576(f) § 63.1576(g) § 63.1576(h) § 63.1576(i)	§ 63.1568(b)(6) § 63.1568(b)(7) § 63.1570(f) § 63.1571(a) [G]§ 63.1574(a) § 63.1574(d) § 63.1574(d)-Table42.1 § 63.1574(d)-Table42.2 § 63.1574(d)-Table42.3 § 63.1575(a) § 63.1575(a)-Table43.1 [G]§ 63.1575(b) [G]§ 63.1575(c) [G]§ 63.1575(e) [G]§ 63.1575(f) § 63.1575(g) [G]§ 63.1575(h)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
39LO1001	EU	60JSP-1B	SO ₂	40 CFR Part 60, Subpart J	§ 60.104(a)(2)(i) § 60.104 § 60.104(a) § 60.104(a)(2)	No owner or operator subject to the provisions of this subpart shall discharge or cause the discharge from any Claus sulfur recovery plant with an oxidation control system or a reduction control system followed by incineration any gases containing in excess of 250 ppm by volume (dry basis) of sulfur dioxide at zero percent excess air into the atmosphere.	§ 60.105(a) [G]§ 60.105(a)(5) § 60.105(e) § 60.105(e)(4)(i) § 60.106(a) [G]§ 60.106(f)	§ 60.105(a) [G]§ 60.105(a)(5)	§ 60.105(e) § 60.105(e)(4)(i) § 60.107(f) § 60.107(g)
39LO1001	EU	60JSP-1C	SO ₂	40 CFR Part 60, Subpart J	§ 60.104(a)(2)(i) § 60.104 § 60.104(a) § 60.104(a)(2)	No owner or operator subject to the provisions of this subpart shall discharge or cause the discharge from any Claus sulfur recovery plant with an oxidation control system or a reduction control system followed by incineration any gases containing in excess of 250 ppm by volume (dry basis) of sulfur dioxide at zero percent excess air into the atmosphere.	§ 60.105(a) [G]§ 60.105(a)(5) § 60.105(e) § 60.105(e)(4)(i) § 60.106(a) [G]§ 60.106(f)	§ 60.105(a) [G]§ 60.105(a)(5)	§ 60.105(e) § 60.105(e)(4)(i) § 60.107(f) § 60.107(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
39LO1001	EU	63UUU-1	SO ₂	40 CFR Part 63, Subpart UUU	§ 63.1568(a)(1)-Table29.1.a § 63.1568(a)(1) § 63.1568(a)(2) § 63.1568(a)(2)-Table30.1 § 63.1568(a)(3) § 63.1568(b)(3) § 63.1568(b)(4) § 63.1568(b)(5) § 63.1568(b)(5)-Table33.1.a § 63.1568(c)(1) § 63.1568(c)(1)-Table35.1 § 63.1568(c)(2) § 63.1570(a) § 63.1570(c) § 63.1570(d) § 63.1570(g)	For each new or existing Claus SRU part of a sulfur recovery plant of 20 long tons per day or more and subject to NSPS for sulfur oxides in 40 CFR §60.104(a)(2), you must meet the emission limit for each process vent of 250ppmv (dry basis) of sulfur dioxide (SO ₂) at zero percent excess air if you use an oxidation or reduction control system followed by incineration.	§ 63.1568(b)(1) § 63.1568(b)(1)-Table31.1.a § 63.1568(c)(1)-Table34.1.a § 63.1572(a)(1)-Table40.4 § 63.1572(a)(1)-Table40.8 § 63.1572(a)(2) § 63.1572(a)(3) § 63.1572(a)(4) [G]§ 63.1572(d)	§ 63.1568(b)(1)-Table31.1.a § 63.1568(c)(1)-Table34.1.a § 63.1570(c) [G]§ 63.1576(a) [G]§ 63.1576(b) § 63.1576(d) § 63.1576(e) § 63.1576(f) § 63.1576(g) § 63.1576(h) § 63.1576(i)	§ 63.1568(b)(6) § 63.1568(b)(7) § 63.1570(f) § 63.1571(a) [G]§ 63.1574(a) § 63.1574(d) § 63.1574(d)-Table42.1 § 63.1574(d)-Table42.2 § 63.1574(d)-Table42.3 § 63.1575(a) § 63.1575(a)-Table43.1 [G]§ 63.1575(b) [G]§ 63.1575(c) [G]§ 63.1575(e) [G]§ 63.1575(f) § 63.1575(g) [G]§ 63.1575(h)
39RX2001	EU	60JSRU-1B	SO ₂	40 CFR Part 60, Subpart J	§ 60.104(a)(2)(i) § 60.104 § 60.104(a) § 60.104(a)(2)	No owner or operator subject to the provisions of this subpart shall discharge or cause the discharge from any Claus sulfur recovery plant with an oxidation control system or a reduction control system followed by incineration any gases containing in excess of 250 ppm by volume (dry basis) of sulfur dioxide at zero percent excess air into the atmosphere.	§ 60.105(a) [G]§ 60.105(a)(5) § 60.105(e) § 60.105(e)(4)(i) § 60.106(a) [G]§ 60.106(f)	§ 60.105(a) [G]§ 60.105(a)(5)	§ 60.105(e) § 60.105(e)(4)(i) § 60.107(f) § 60.107(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
39RX2001	EU	60JSRU-1C	SO ₂	40 CFR Part 60, Subpart J	§ 60.104(a)(2)(i) § 60.104 § 60.104(a) § 60.104(a)(2)	No owner or operator subject to the provisions of this subpart shall discharge or cause the discharge from any Claus sulfur recovery plant with an oxidation control system or a reduction control system followed by incineration any gases containing in excess of 250 ppm by volume (dry basis) of sulfur dioxide at zero percent excess air into the atmosphere.	§ 60.105(a) [G]§ 60.105(a)(5) § 60.105(e) § 60.105(e)(4)(i) § 60.106(a) [G]§ 60.106(f)	§ 60.105(a) [G]§ 60.105(a)(5)	§ 60.105(e) § 60.105(e)(4)(i) § 60.107(f) § 60.107(g)
39RX2001	EU	63UUU-1	SO ₂	40 CFR Part 63, Subpart UUU	§ 63.1568(a)(1)-Table29.1.a § 63.1568(a)(1) § 63.1568(a)(2) § 63.1568(a)(2)-Table30.1 § 63.1568(a)(3) § 63.1568(b)(3) § 63.1568(b)(4) § 63.1568(b)(5) § 63.1568(b)(5)-Table33.1.a § 63.1568(c)(1) § 63.1568(c)(1)-Table35.1 § 63.1568(c)(2) § 63.1570(a) § 63.1570(c) § 63.1570(d) § 63.1570(g)	For each new or existing Claus SRU part of a sulfur recovery plant of 20 long tons per day or more and subject to NSPS for sulfur oxides in 40 CFR §60.104(a)(2), you must meet the emission limit for each process vent of 250ppmv (dry basis) of sulfur dioxide (SO ₂) at zero percent excess air if you use an oxidation or reduction control system followed by incineration.	§ 63.1568(b)(1) § 63.1568(b)(1)-Table31.1.a § 63.1568(c)(1)-Table34.1.a § 63.1572(a)(1)-Table40.4 § 63.1572(a)(1)-Table40.8 § 63.1572(a)(2) § 63.1572(a)(3) § 63.1572(a)(4) [G]§ 63.1572(d)	§ 63.1568(b)(1)-Table31.1.a § 63.1568(c)(1)-Table34.1.a § 63.1570(c) [G]§ 63.1576(a) [G]§ 63.1576(b) § 63.1576(d) § 63.1576(e) § 63.1576(f) § 63.1576(g) § 63.1576(h) § 63.1576(i)	§ 63.1568(b)(6) § 63.1568(b)(7) § 63.1570(f) § 63.1571(a) [G]§ 63.1574(a) § 63.1574(d) § 63.1574(d)-Table42.1 § 63.1574(d)-Table42.2 § 63.1574(d)-Table42.3 § 63.1575(a) § 63.1575(a)-Table43.1 [G]§ 63.1575(b) [G]§ 63.1575(c) [G]§ 63.1575(e) [G]§ 63.1575(f) § 63.1575(g) [G]§ 63.1575(h)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
42CB2201	EU	60J-3	SO ₂	40 CFR Part 60, Subpart J	§ 60.104(b)(1) § 60.104 § 60.104(b) § 60.104(c) § 60.104(d)	For each affected fluid catalytic cracking unit catalyst regenerator with an add-on control device, reduce sulfur dioxide emissions to the atmosphere by 90 percent or maintain sulfur dioxide emissions to the atmosphere less than or equal to 50 ppm by volume, whichever is less stringent.	§ 60.105(a) § 60.105(a)(10) § 60.105(a)(11) [G]§ 60.105(a)(12) [G]§ 60.105(a)(13) [G]§ 60.105(a)(9) § 60.106(a) § 60.106(g) [G]§ 60.106(h) [G]§ 60.106(k) § 60.108(a) § 60.108(c) § 60.108(d) § 60.108(e)	§ 60.105(a) § 60.105(a)(10) § 60.105(a)(11) [G]§ 60.105(a)(13) [G]§ 60.105(a)(9) § 60.107(b) [G]§ 60.107(b)(1) § 60.107(b)(4)	§ 60.107(a) § 60.107(c) [G]§ 60.107(c)(1) § 60.107(c)(2) [G]§ 60.107(c)(3) [G]§ 60.107(c)(4) § 60.107(d) § 60.107(e) § 60.107(f) § 60.107(g)
42CB2201	EU	60J-3	CO	40 CFR Part 60, Subpart J	§ 60.103(a) § 60.103	No owner or operator shall discharge or cause the discharge into the atmosphere from any fluid catalytic cracking unit catalyst regenerator any gases that contain carbon monoxide (CO) in excess of 500 ppm by volume (dry basis).	§ 60.105(a) [G]§ 60.105(a)(2) § 60.105(c) § 60.105(e) § 60.105(e)(2) § 60.106(a) § 60.106(d)	§ 60.105(a) [G]§ 60.105(a)(2) § 60.105(c)	§ 60.105(e) § 60.105(e)(2) § 60.107(f) § 60.107(g)
42CB2201	EU	60J-3	PM	40 CFR Part 60, Subpart J	§ 60.102(a)(1) § 60.102 § 60.102(a)	No owner or operator subject to the provisions of this subpart shall discharge or cause the discharge into the atmosphere from any fluid catalytic cracking unit catalyst regenerator particulate matter in excess of 1.0 kg/Mg (2.0 lb/ton) of coke burn-off in the catalyst regenerator.	§ 60.105(c) § 60.106(a) [G]§ 60.106(b)	§ 60.105(c)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
42CB2201	EU	60J-3	PM (OPACITY)	40 CFR Part 60, Subpart J	§ 60.102(a)(2) § 60.102 § 60.102(a)	No owner or operator subject to the provisions of this subpart shall discharge or cause the discharge into the atmosphere from any fluid catalytic cracking unit catalyst regenerator gases exhibiting greater than 30 percent opacity, except for one six-minute average opacity reading in any one hour period.	§ 60.105(a) § 60.105(a)(1) § 60.105(c) § 60.105(e) § 60.105(e)(1) § 60.106(a) [G]§ 60.106(b)	§ 60.105(a) § 60.105(a)(1) § 60.105(c)	§ 60.105(e) § 60.105(e)(1) § 60.107(f) § 60.107(g)
42CB2201	EU	63UUU-3	112(B) HAPS	40 CFR Part 63, Subpart UUU	§ 63.1563 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart UUU	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart UUU	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart UUU	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart UUU	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart UUU

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
44BA3001	EU	60J-2	HYDROGEN SULFIDE	40 CFR Part 60, Subpart J	§ 60.104(a)(1) § 60.104 § 60.104(a)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide in excess of 230 mg/dscm (0.10 gr/dscf). The combustion in a flare of process upset gases or fuel gas that is released to the flare as a result of relief valve leakage or other emergency malfunctions is exempt from this paragraph.	§ 60.105(a) [G]§ 60.105(a)(4)(iv) [G]§ 60.105(b) § 60.105(e) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a) [G]§ 60.105(a)(4)(iv) § 60.107(e)	[G]§ 60.105(b) § 60.105(e) § 60.107(f) § 60.107(g)
44BA3002	EU	60J-2	HYDROGEN SULFIDE	40 CFR Part 60, Subpart J	§ 60.104(a)(1) § 60.104 § 60.104(a)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide in excess of 230 mg/dscm (0.10 gr/dscf). The combustion in a flare of process upset gases or fuel gas that is released to the flare as a result of relief valve leakage or other emergency malfunctions is exempt from this paragraph.	§ 60.105(a) [G]§ 60.105(a)(4)(iv) [G]§ 60.105(b) § 60.105(e) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a) [G]§ 60.105(a)(4)(iv) § 60.107(e)	[G]§ 60.105(b) § 60.105(e) § 60.107(f) § 60.107(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
44BA3005	EU	60J-2	HYDROGEN SULFIDE	40 CFR Part 60, Subpart J	§ 60.104(a)(1) § 60.104 § 60.104(a)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide in excess of 230 mg/dscm (0.10 gr/dscf). The combustion in a flare of process upset gases or fuel gas that is released to the flare as a result of relief valve leakage or other emergency malfunctions is exempt from this paragraph.	§ 60.105(a) [G]§ 60.105(a)(4)(iv) [G]§ 60.105(b) § 60.105(e) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a) [G]§ 60.105(a)(4)(iv) § 60.107(e)	[G]§ 60.105(b) § 60.105(e) § 60.107(f) § 60.107(g)
46AD6202	EU	60JSP-1B	SO ₂	40 CFR Part 60, Subpart J	§ 60.104(a)(2)(i) § 60.104 § 60.104(a) § 60.104(a)(2)	No owner or operator subject to the provisions of this subpart shall discharge or cause the discharge from any Claus sulfur recovery plant with an oxidation control system or a reduction control system followed by incineration any gases containing in excess of 250 ppm by volume (dry basis) of sulfur dioxide at zero percent excess air into the atmosphere.	§ 60.105(a) [G]§ 60.105(a)(5) § 60.105(e) § 60.105(e)(4)(i) § 60.106(a) [G]§ 60.106(f)	§ 60.105(a) [G]§ 60.105(a)(5)	§ 60.105(e) § 60.105(e)(4)(i) § 60.107(f) § 60.107(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
46AD6202	EU	60JSP-1C	SO ₂	40 CFR Part 60, Subpart J	§ 60.104(a)(2)(i) § 60.104 § 60.104(a) § 60.104(a)(2)	No owner or operator subject to the provisions of this subpart shall discharge or cause the discharge from any Claus sulfur recovery plant with an oxidation control system or a reduction control system followed by incineration any gases containing in excess of 250 ppm by volume (dry basis) of sulfur dioxide at zero percent excess air into the atmosphere.	§ 60.105(a) [G]§ 60.105(a)(5) § 60.105(e) § 60.105(e)(4)(i) § 60.106(a) [G]§ 60.106(f)	§ 60.105(a) [G]§ 60.105(a)(5)	§ 60.105(e) § 60.105(e)(4)(i) § 60.107(f) § 60.107(g)
46AD6202	EU	63UUU-1	112(B) HAPS	40 CFR Part 63, Subpart UUU	§ 63.1569(a)(1)(iv)-Table36.4 § 63.1569(a)(1) § 63.1569(a)(3) § 63.1569(b)(2) § 63.1569(b)(2)-Table38.1.d § 63.1569(c)(1) § 63.1570(a) § 63.1570(c) § 63.1570(d) § 63.1570(g)	If you elect to vent to a control device (Option 4), you must vent the bypass line to a control device that meets the appropriate requirements in this subpart.	§ 63.1569(c)(1)-Table39.4	§ 63.1569(c)(1)-Table39.4 § 63.1569(c)(1)-Table39.5 § 63.1570(c) [G]§ 63.1576(a) § 63.1576(d) § 63.1576(e) § 63.1576(f) § 63.1576(g) § 63.1576(h) § 63.1576(i)	§ 63.1569(b)(3) § 63.1569(b)(4) § 63.1569(c)(1)-Table39.5 § 63.1570(f) [G]§ 63.1574(a) § 63.1574(d) § 63.1574(d)-Table42.1 § 63.1574(d)-Table42.2 § 63.1574(d)-Table42.3 § 63.1575(a) § 63.1575(a)-Table43.1 [G]§ 63.1575(b) [G]§ 63.1575(c) [G]§ 63.1575(d) [G]§ 63.1575(f) § 63.1575(g) [G]§ 63.1575(h)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
46AD6202	EU	63UUU-1	SO ₂	40 CFR Part 63, Subpart UUU	§ 63.1568(a)(1)-Table29.1.a § 63.1568(a)(1) § 63.1568(a)(2) § 63.1568(a)(2)-Table30.1 § 63.1568(a)(3) § 63.1568(b)(3) § 63.1568(b)(4) § 63.1568(b)(5) § 63.1568(b)(5)-Table33.1.a § 63.1568(c)(1) § 63.1568(c)(1)-Table35.1 § 63.1568(c)(2) § 63.1570(a) § 63.1570(c) § 63.1570(d) § 63.1570(g)	For each new or existing Claus SRU part of a sulfur recovery plant of 20 long tons per day or more and subject to NSPS for sulfur oxides in 40 CFR §60.104(a)(2), you must meet the emission limit for each process vent of 250ppmv (dry basis) of sulfur dioxide (SO ₂) at zero percent excess air if you use an oxidation or reduction control system followed by incineration.	§ 63.1568(b)(1) § 63.1568(b)(1)-Table31.1.a § 63.1568(c)(1)-Table34.1.a § 63.1572(a)(1)-Table40.4 § 63.1572(a)(1)-Table40.8 § 63.1572(a)(2) § 63.1572(a)(3) § 63.1572(a)(4) [G]§ 63.1572(d)	§ 63.1568(b)(1)-Table31.1.a § 63.1568(c)(1)-Table34.1.a § 63.1570(c) [G]§ 63.1576(a) [G]§ 63.1576(b) § 63.1576(d) § 63.1576(e) § 63.1576(f) § 63.1576(g) § 63.1576(h) § 63.1576(i)	§ 63.1568(b)(6) § 63.1568(b)(7) § 63.1570(f) § 63.1571(a) [G]§ 63.1574(a) § 63.1574(d) § 63.1574(d)-Table42.1 § 63.1574(d)-Table42.2 § 63.1574(d)-Table42.3 § 63.1575(a) § 63.1575(a)-Table43.1 [G]§ 63.1575(b) [G]§ 63.1575(c) [G]§ 63.1575(e) [G]§ 63.1575(f) § 63.1575(g) [G]§ 63.1575(h)
46BC6302	EU	60J-2	HYDROGEN SULFIDE	40 CFR Part 60, Subpart J	§ 60.104(a)(1) § 60.104 § 60.104(a)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide in excess of 230 mg/dscm (0.10 gr/dscf). The combustion in a flare of process upset gases or fuel gas that is released to the flare as a result of relief valve leakage or other emergency malfunctions is exempt from this paragraph.	§ 60.105(a) [G]§ 60.105(a)(4)(iv) [G]§ 60.105(b) § 60.105(e) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a) [G]§ 60.105(a)(4)(iv) § 60.107(e)	[G]§ 60.105(b) § 60.105(e) § 60.107(f) § 60.107(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
46CB6301	EU	60JTGI-1	SO ₂	40 CFR Part 60, Subpart J	§ 60.104(a)(2)(i) § 60.104 § 60.104(a) § 60.104(a)(2)	No owner or operator subject to the provisions of this subpart shall discharge or cause the discharge from any Claus sulfur recovery plant with an oxidation control system or a reduction control system followed by incineration any gases containing in excess of 250 ppm by volume (dry basis) of sulfur dioxide at zero percent excess air into the atmosphere.	§ 60.105(a) [G]§ 60.105(a)(5) § 60.105(e) § 60.105(e)(4)(i) § 60.106(a) [G]§ 60.106(f)	§ 60.105(a) [G]§ 60.105(a)(5)	§ 60.105(e) § 60.105(e)(4)(i) § 60.107(f) § 60.107(g)
46CB6301	EU	63UUU-1	SO ₂	40 CFR Part 63, Subpart UUU	§ 63.1568(a)(1)-Table29.1.a § 63.1568(a)(1) § 63.1568(a)(2) § 63.1568(a)(2)-Table30.1 § 63.1568(a)(3) § 63.1568(b)(3) § 63.1568(b)(4) § 63.1568(b)(5) § 63.1568(b)(5)-Table33.1.a § 63.1568(c)(1) § 63.1568(c)(1)-Table35.1 § 63.1568(c)(2) § 63.1570(a) § 63.1570(c) § 63.1570(d) § 63.1570(g)	For each new or existing Claus SRU part of a sulfur recovery plant of 20 long tons per day or more and subject to NSPS for sulfur oxides in 40 CFR §60.104(a)(2), you must meet the emission limit for each process vent of 250ppmv (dry basis) of sulfur dioxide (SO ₂) at zero percent excess air if you use an oxidation or reduction control system followed by incineration.	§ 63.1568(b)(1) § 63.1568(b)(1)-Table31.1.a § 63.1568(c)(1)-Table34.1.a § 63.1572(a)(1)-Table40.4 § 63.1572(a)(1)-Table40.8 § 63.1572(a)(2) § 63.1572(a)(3) § 63.1572(a)(4) [G]§ 63.1572(d)	§ 63.1568(b)(1)-Table31.1.a § 63.1568(c)(1)-Table34.1.a § 63.1570(c) [G]§ 63.1576(a) [G]§ 63.1576(b) § 63.1576(d) § 63.1576(e) § 63.1576(f) § 63.1576(g) § 63.1576(h) § 63.1576(i)	§ 63.1568(b)(6) § 63.1568(b)(7) § 63.1570(f) § 63.1571(a) [G]§ 63.1574(a) § 63.1574(d) § 63.1574(d)-Table42.1 § 63.1574(d)-Table42.2 § 63.1574(d)-Table42.3 § 63.1575(a) § 63.1575(a)-Table43.1 [G]§ 63.1575(b) [G]§ 63.1575(c) [G]§ 63.1575(e) [G]§ 63.1575(f) § 63.1575(g) [G]§ 63.1575(h)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
46LO6201	EU	60JSP-1B	SO ₂	40 CFR Part 60, Subpart J	§ 60.104(a)(2)(i) § 60.104 § 60.104(a) § 60.104(a)(2)	No owner or operator subject to the provisions of this subpart shall discharge or cause the discharge from any Claus sulfur recovery plant with an oxidation control system or a reduction control system followed by incineration any gases containing in excess of 250 ppm by volume (dry basis) of sulfur dioxide at zero percent excess air into the atmosphere.	§ 60.105(a) [G]§ 60.105(a)(5) § 60.105(e) § 60.105(e)(4)(i) § 60.106(a) [G]§ 60.106(f)	§ 60.105(a) [G]§ 60.105(a)(5)	§ 60.105(e) § 60.105(e)(4)(i) § 60.107(f) § 60.107(g)
46LO6201	EU	60JSP-1C	SO ₂	40 CFR Part 60, Subpart J	§ 60.104(a)(2)(i) § 60.104 § 60.104(a) § 60.104(a)(2)	No owner or operator subject to the provisions of this subpart shall discharge or cause the discharge from any Claus sulfur recovery plant with an oxidation control system or a reduction control system followed by incineration any gases containing in excess of 250 ppm by volume (dry basis) of sulfur dioxide at zero percent excess air into the atmosphere.	§ 60.105(a) [G]§ 60.105(a)(5) § 60.105(e) § 60.105(e)(4)(i) § 60.106(a) [G]§ 60.106(f)	§ 60.105(a) [G]§ 60.105(a)(5)	§ 60.105(e) § 60.105(e)(4)(i) § 60.107(f) § 60.107(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
46LO6201	EU	63UUU-1	112(B) HAPS	40 CFR Part 63, Subpart UUU	<p>§ 63.1569(a)(1)(iv)-Table36.4</p> <p>§ 63.1569(a)(1)</p> <p>§ 63.1569(a)(3)</p> <p>§ 63.1569(b)(2)</p> <p>§ 63.1569(b)(2)-Table38.1.d</p> <p>§ 63.1569(c)(1)</p> <p>§ 63.1570(a)</p> <p>§ 63.1570(c)</p> <p>§ 63.1570(d)</p> <p>§ 63.1570(g)</p>	If you elect to vent to a control device (Option 4), you must vent the bypass line to a control device that meets the appropriate requirements in this subpart.	<p>§ 63.1569(c)(1)-Table39.4</p>	<p>§ 63.1569(c)(1)-Table39.4</p> <p>§ 63.1569(c)(1)-Table39.5</p> <p>§ 63.1570(c)</p> <p>[G]§ 63.1576(a)</p> <p>§ 63.1576(d)</p> <p>§ 63.1576(e)</p> <p>§ 63.1576(f)</p> <p>§ 63.1576(g)</p> <p>§ 63.1576(h)</p> <p>§ 63.1576(i)</p>	<p>§ 63.1569(b)(3)</p> <p>§ 63.1569(b)(4)</p> <p>§ 63.1569(c)(1)-Table39.5</p> <p>§ 63.1570(f)</p> <p>[G]§ 63.1574(a)</p> <p>§ 63.1574(d)</p> <p>§ 63.1574(d)-Table42.1</p> <p>§ 63.1574(d)-Table42.2</p> <p>§ 63.1574(d)-Table42.3</p> <p>§ 63.1575(a)</p> <p>§ 63.1575(a)-Table43.1</p> <p>[G]§ 63.1575(b)</p> <p>[G]§ 63.1575(c)</p> <p>[G]§ 63.1575(d)</p> <p>[G]§ 63.1575(f)</p> <p>§ 63.1575(g)</p> <p>[G]§ 63.1575(h)</p>
46LO6201	EU	63UUU-1	SO ₂	40 CFR Part 63, Subpart UUU	<p>§ 63.1568(a)(1)-Table29.1.a</p> <p>§ 63.1568(a)(1)</p> <p>§ 63.1568(a)(2)</p> <p>§ 63.1568(a)(2)-Table30.1</p> <p>§ 63.1568(a)(3)</p> <p>§ 63.1568(b)(3)</p> <p>§ 63.1568(b)(4)</p> <p>§ 63.1568(b)(5)</p> <p>§ 63.1568(b)(5)-Table33.1.a</p> <p>§ 63.1568(c)(1)</p> <p>§ 63.1568(c)(1)-Table35.1</p> <p>§ 63.1568(c)(2)</p> <p>§ 63.1570(a)</p> <p>§ 63.1570(c)</p> <p>§ 63.1570(d)</p> <p>§ 63.1570(g)</p>	For each new or existing Claus SRU part of a sulfur recovery plant of 20 long tons per day or more and subject to NSPS for sulfur oxides in 40 CFR §60.104(a)(2), you must meet the emission limit for each process vent of 25ppmv (dry basis) of sulfur dioxide (SO ₂) at zero percent excess air if you use an oxidation or reduction control system followed by incineration.	<p>§ 63.1568(b)(1)</p> <p>§ 63.1568(b)(1)-Table31.1.a</p> <p>§ 63.1568(c)(1)-Table34.1.a</p> <p>§ 63.1572(a)(1)-Table40.4</p> <p>§ 63.1572(a)(1)-Table40.8</p> <p>§ 63.1572(a)(2)</p> <p>§ 63.1572(a)(3)</p> <p>§ 63.1572(a)(4)</p> <p>[G]§ 63.1572(d)</p>	<p>§ 63.1568(b)(1)-Table31.1.a</p> <p>§ 63.1568(c)(1)-Table34.1.a</p> <p>§ 63.1570(c)</p> <p>[G]§ 63.1576(a)</p> <p>[G]§ 63.1576(b)</p> <p>§ 63.1576(d)</p> <p>§ 63.1576(e)</p> <p>§ 63.1576(f)</p> <p>§ 63.1576(g)</p> <p>§ 63.1576(h)</p> <p>§ 63.1576(i)</p>	<p>§ 63.1568(b)(6)</p> <p>§ 63.1568(b)(7)</p> <p>§ 63.1570(f)</p> <p>§ 63.1571(a)</p> <p>[G]§ 63.1574(a)</p> <p>§ 63.1574(d)</p> <p>§ 63.1574(d)-Table42.1</p> <p>§ 63.1574(d)-Table42.2</p> <p>§ 63.1574(d)-Table42.3</p> <p>§ 63.1575(a)</p> <p>§ 63.1575(a)-Table43.1</p> <p>[G]§ 63.1575(b)</p> <p>[G]§ 63.1575(c)</p> <p>[G]§ 63.1575(e)</p> <p>[G]§ 63.1575(f)</p> <p>§ 63.1575(g)</p> <p>[G]§ 63.1575(h)</p>

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
46RX6206	EU	60JSRU-1B	SO ₂	40 CFR Part 60, Subpart J	§ 60.104(a)(2)(i) § 60.104 § 60.104(a) § 60.104(a)(2)	No owner or operator subject to the provisions of this subpart shall discharge or cause the discharge from any Claus sulfur recovery plant with an oxidation control system or a reduction control system followed by incineration any gases containing in excess of 250 ppm by volume (dry basis) of sulfur dioxide at zero percent excess air into the atmosphere.	§ 60.105(a) [G]§ 60.105(a)(5) § 60.105(e) § 60.105(e)(4)(i) § 60.106(a) [G]§ 60.106(f)	§ 60.105(a) [G]§ 60.105(a)(5)	§ 60.105(e) § 60.105(e)(4)(i) § 60.107(f) § 60.107(g)
46RX6206	EU	60JSRU-1C	SO ₂	40 CFR Part 60, Subpart J	§ 60.104(a)(2)(i) § 60.104 § 60.104(a) § 60.104(a)(2)	No owner or operator subject to the provisions of this subpart shall discharge or cause the discharge from any Claus sulfur recovery plant with an oxidation control system or a reduction control system followed by incineration any gases containing in excess of 250 ppm by volume (dry basis) of sulfur dioxide at zero percent excess air into the atmosphere.	§ 60.105(a) [G]§ 60.105(a)(5) § 60.105(e) § 60.105(e)(4)(i) § 60.106(a) [G]§ 60.106(f)	§ 60.105(a) [G]§ 60.105(a)(5)	§ 60.105(e) § 60.105(e)(4)(i) § 60.107(f) § 60.107(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
46RX6206	EU	63UUU-1	112(B) HAPS	40 CFR Part 63, Subpart UUU	<p>§ 63.1569(a)(1)(iv)-Table36.4</p> <p>§ 63.1569(a)(1)</p> <p>§ 63.1569(a)(3)</p> <p>§ 63.1569(b)(2)</p> <p>§ 63.1569(b)(2)-Table38.1.d</p> <p>§ 63.1569(c)(1)</p> <p>§ 63.1570(a)</p> <p>§ 63.1570(c)</p> <p>§ 63.1570(d)</p> <p>§ 63.1570(g)</p>	If you elect to vent to a control device (Option 4), you must vent the bypass line to a control device that meets the appropriate requirements in this subpart.	<p>§ 63.1569(c)(1)-Table39.4</p>	<p>§ 63.1569(c)(1)-Table39.4</p> <p>§ 63.1569(c)(1)-Table39.5</p> <p>§ 63.1570(c)</p> <p>[G]§ 63.1576(a)</p> <p>§ 63.1576(d)</p> <p>§ 63.1576(e)</p> <p>§ 63.1576(f)</p> <p>§ 63.1576(g)</p> <p>§ 63.1576(h)</p> <p>§ 63.1576(i)</p>	<p>§ 63.1569(b)(3)</p> <p>§ 63.1569(b)(4)</p> <p>§ 63.1569(c)(1)-Table39.5</p> <p>§ 63.1570(f)</p> <p>[G]§ 63.1574(a)</p> <p>§ 63.1574(d)</p> <p>§ 63.1574(d)-Table42.1</p> <p>§ 63.1574(d)-Table42.2</p> <p>§ 63.1574(d)-Table42.3</p> <p>§ 63.1575(a)</p> <p>§ 63.1575(a)-Table43.1</p> <p>[G]§ 63.1575(b)</p> <p>[G]§ 63.1575(c)</p> <p>[G]§ 63.1575(d)</p> <p>[G]§ 63.1575(f)</p> <p>§ 63.1575(g)</p> <p>[G]§ 63.1575(h)</p>
46RX6206	EU	63UUU-1	SO ₂	40 CFR Part 63, Subpart UUU	<p>§ 63.1568(a)(1)-Table29.1.a</p> <p>§ 63.1568(a)(1)</p> <p>§ 63.1568(a)(2)</p> <p>§ 63.1568(a)(2)-Table30.1</p> <p>§ 63.1568(a)(3)</p> <p>§ 63.1568(b)(3)</p> <p>§ 63.1568(b)(4)</p> <p>§ 63.1568(b)(5)</p> <p>§ 63.1568(b)(5)-Table33.1.a</p> <p>§ 63.1568(c)(1)-Table35.1</p> <p>§ 63.1568(c)(2)</p> <p>§ 63.1570(a)</p> <p>§ 63.1570(c)</p> <p>§ 63.1570(d)</p> <p>§ 63.1570(g)</p>	For each new or existing Claus SRU part of a sulfur recovery plant of 20 long tons per day or more and subject to NSPS for sulfur oxides in 40 CFR §60.104(a)(2), you must meet the emission limit for each process vent of 25ppmv (dry basis) of sulfur dioxide (SO ₂) at zero percent excess air if you use an oxidation or reduction control system followed by incineration.	<p>§ 63.1568(b)(1)</p> <p>§ 63.1568(b)(1)-Table31.1.a</p> <p>§ 63.1568(c)(1)-Table34.1.a</p> <p>§ 63.1572(a)(1)-Table40.4</p> <p>§ 63.1572(a)(1)-Table40.8</p> <p>§ 63.1572(a)(2)</p> <p>§ 63.1572(a)(3)</p> <p>§ 63.1572(a)(4)</p> <p>[G]§ 63.1572(d)</p>	<p>§ 63.1568(b)(1)-Table31.1.a</p> <p>§ 63.1568(c)(1)-Table34.1.a</p> <p>§ 63.1570(c)</p> <p>[G]§ 63.1576(a)</p> <p>[G]§ 63.1576(b)</p> <p>§ 63.1576(d)</p> <p>§ 63.1576(e)</p> <p>§ 63.1576(f)</p> <p>§ 63.1576(g)</p> <p>§ 63.1576(h)</p> <p>§ 63.1576(i)</p>	<p>§ 63.1568(b)(6)</p> <p>§ 63.1568(b)(7)</p> <p>§ 63.1570(f)</p> <p>§ 63.1571(a)</p> <p>[G]§ 63.1574(a)</p> <p>§ 63.1574(d)</p> <p>§ 63.1574(d)-Table42.1</p> <p>§ 63.1574(d)-Table42.2</p> <p>§ 63.1574(d)-Table42.3</p> <p>§ 63.1575(a)</p> <p>§ 63.1575(a)-Table43.1</p> <p>[G]§ 63.1575(b)</p> <p>[G]§ 63.1575(c)</p> <p>[G]§ 63.1575(e)</p> <p>[G]§ 63.1575(f)</p> <p>§ 63.1575(g)</p> <p>[G]§ 63.1575(h)</p>

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
50BF02	EU	60J-2	HYDROGEN SULFIDE	40 CFR Part 60, Subpart J	§ 60.104(a)(1) § 60.104 § 60.104(a)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide in excess of 230 mg/dscm (0.10 gr/dscf). The combustion in a flare of process upset gases or fuel gas that is released to the flare as a result of relief valve leakage or other emergency malfunctions is exempt from this paragraph.	§ 60.105(a) [G]§ 60.105(a)(4)(iv) [G]§ 60.105(b) § 60.105(e) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a) [G]§ 60.105(a)(4)(iv) § 60.107(e)	[G]§ 60.105(b) § 60.105(e) § 60.107(f) § 60.107(g)
50BF03	EU	60J-2	HYDROGEN SULFIDE	40 CFR Part 60, Subpart J	§ 60.104(a)(1) § 60.104 § 60.104(a)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide in excess of 230 mg/dscm (0.10 gr/dscf). The combustion in a flare of process upset gases or fuel gas that is released to the flare as a result of relief valve leakage or other emergency malfunctions is exempt from this paragraph.	§ 60.105(a) [G]§ 60.105(a)(4)(iv) [G]§ 60.105(b) § 60.105(e) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a) [G]§ 60.105(a)(4)(iv) § 60.107(e)	[G]§ 60.105(b) § 60.105(e) § 60.107(f) § 60.107(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
51HTR	EU	60Ja-3	NO _x	40 CFR Part 60, Subpart Ja	§ 60.102a(g)(2) § 60.102a(a) § 60.102a(g)	For each process heater with a rated capacity of greater than 40 million British thermal units per hour (MMBtu/hr), the owner or operator shall not discharge to the atmosphere any emissions of NO _x in excess of 40 ppmv (dry basis, corrected to 0 percent excess air) on a 24-hour rolling average basis.	§ 60.104a(a) § 60.104a(c) § 60.104a(i) § 60.104a(i)(1) § 60.104a(i)(2) § 60.104a(i)(3) § 60.104a(i)(5) § 60.107a(c) § 60.107a(c)(1) § 60.107a(c)(2) § 60.107a(c)(3) § 60.107a(c)(4) § 60.107a(c)(5) § 60.107a(f) § 60.107a(f)(3)	§ 60.108a(a) [G]§ 60.108a(d)	§ 60.108a(a) § 60.108a(b) [G]§ 60.108a(d)
51HTR	EU	60Ja-3	HYDROGEN SULFIDE	40 CFR Part 60, Subpart Ja	§ 60.102a(g)(1)(ii) § 60.102a(a) § 60.102a(g) § 60.102a(g)(1) § 60.103a(b)	For each fuel gas combustion device the owner or operator shall not burn in any fuel gas combustion device any fuel gas that contains H ₂ S in excess of 162 ppmv determined hourly on a 3-hour rolling average basis and H ₂ S in excess of 60 ppmv determined daily on a 365 successive calendar day rolling average basis.	§ 60.104a(a) § 60.104a(c) § 60.104a(i) § 60.104a(i)(1) § 60.104a(i)(2) § 60.104a(i)(3) [G]§ 60.104a(i)(4) [G]§ 60.104a(j) § 60.107a(a) [G]§ 60.107a(a)(2) § 60.107a(f) § 60.107a(f)(2)	§ 60.108a(a) § 60.108a(c) [G]§ 60.108a(c)(6) [G]§ 60.108a(d)	§ 60.108a(a) § 60.108a(b) [G]§ 60.108a(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
81BF01	EU	60J-2	HYDROGEN SULFIDE	40 CFR Part 60, Subpart J	§ 60.104(a)(1) § 60.104 § 60.104(a)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide in excess of 230 mg/dscm (0.10 gr/dscf). The combustion in a flare of process upset gases or fuel gas that is released to the flare as a result of relief valve leakage or other emergency malfunctions is exempt from this paragraph.	§ 60.105(a) [G]§ 60.105(a)(4)(iv) [G]§ 60.105(b) § 60.105(e) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a) [G]§ 60.105(a)(4)(iv) § 60.107(e)	[G]§ 60.105(b) § 60.105(e) § 60.107(f) § 60.107(g)
81SKD5602	EU	60Ja-2	HYDROGEN SULFIDE	40 CFR Part 60, Subpart Ja	§ 60.102a(g)(1)(ii) § 60.102a(a) § 60.102a(g) § 60.102a(g)(1) § 60.103a(b) [G]§ 60.107a(a)(3) [G]§ 60.107a(b)	For each fuel gas combustion device the owner or operator shall not burn in any fuel gas combustion device any fuel gas that contains H ₂ S in excess of 162 ppmv determined hourly on a 3-hour rolling average basis and H ₂ S in excess of 60 ppmv determined daily on a 365 successive calendar day rolling average basis.	§ 60.104a(a) § 60.104a(c) § 60.104a(i) § 60.104a(i)(1) § 60.104a(i)(2) § 60.104a(i)(3) [G]§ 60.104a(i)(4) [G]§ 60.104a(j) § 60.107a(a)(4)	§ 60.108a(a) § 60.108a(c) § 60.108a(c)(5) [G]§ 60.108a(c)(6) [G]§ 60.108a(d)	§ 60.108a(a) § 60.108a(b) [G]§ 60.108a(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
81SKD5603	EU	60Ja-2	HYDROGEN SULFIDE	40 CFR Part 60, Subpart Ja	§ 60.102a(g)(1)(ii) § 60.102a(a) § 60.102a(g) § 60.102a(g)(1) § 60.103a(b) [G]§ 60.107a(a)(3) [G]§ 60.107a(b)	For each fuel gas combustion device the owner or operator shall not burn in any fuel gas combustion device any fuel gas that contains H ₂ S in excess of 162 ppmv determined hourly on a 3-hour rolling average basis and H ₂ S in excess of 60 ppmv determined daily on a 365 successive calendar day rolling average basis.	§ 60.104a(a) § 60.104a(c) § 60.104a(i) § 60.104a(i)(1) § 60.104a(i)(2) § 60.104a(i)(3) [G]§ 60.104a(i)(4) [G]§ 60.104a(j) § 60.107a(a)(4)	§ 60.108a(a) § 60.108a(c) § 60.108a(c)(5) [G]§ 60.108a(c)(6) [G]§ 60.108a(d)	§ 60.108a(a) § 60.108a(b) [G]§ 60.108a(d)
91CB915	EU	60J-4	HYDROGEN SULFIDE	40 CFR Part 60, Subpart J	§ 60.104(a)(1) § 60.104 § 60.104(a)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide in excess of 230 mg/dscm (0.10 gr/dscf). The combustion in a flare of process upset gases or fuel gas that is released to the flare as a result of relief valve leakage or other emergency malfunctions is exempt from this paragraph.	§ 60.105(a) [G]§ 60.105(a)(4)(iv) [G]§ 60.105(b) § 60.105(e) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a) [G]§ 60.105(a)(4)(iv) § 60.107(e)	[G]§ 60.105(b) § 60.105(e) § 60.107(f) § 60.107(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-HEATER	EU	60J-2	HYDROGEN SULFIDE	40 CFR Part 60, Subpart J	§ 60.104(a)(1) § 60.104 § 60.104(a)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide in excess of 230 mg/dscm (0.10 gr/dscf). The combustion in a flare of process upset gases or fuel gas that is released to the flare as a result of relief valve leakage or other emergency malfunctions is exempt from this paragraph.	§ 60.105(a) [G]§ 60.105(a)(4)(iv) [G]§ 60.105(b) § 60.105(e) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a) [G]§ 60.105(a)(4)(iv) § 60.107(e)	[G]§ 60.105(b) § 60.105(e) § 60.107(f) § 60.107(g)
30FL1	EU	R1111-1	OPACITY	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(4)(A)	Visible emissions from a process gas flare shall not be permitted for more than five minutes in any two-hour period, except for emission event emissions as provided in §101.222(b).	§ 111.111(a)(4)(A)(i) § 111.111(a)(4)(A)(ii)	§ 111.111(a)(4)(A)(ii)	None
30FL1	EP	R5720-1	HIGHLY REACTIVE VOC	30 TAC Chapter 115, HRVOC Vent Gas	§ 115.722(d) § 115.722(d)(1) § 115.722(d)(2) [G]§ 115.725(d)(1) § 115.725(f)(1) § 115.725(f)(2) § 115.725(f)(3) § 115.725(f)(4) § 115.725(f)(5) § 115.725(f)(6) [G]§ 115.725(l)	All flares must continuously meet the requirements of 40 CFR § 60.18(c)(2)-(6) and (d) as amended through October 17, 2000 (65 FR 61744) when vent gas containing HRVOC is being routed to the flare.	[G]§ 115.725(d)(1) § 115.725(f)(1) § 115.725(f)(2) § 115.725(f)(3) § 115.725(f)(4) § 115.725(f)(4)(A) § 115.725(f)(5) § 115.725(f)(6) [G]§ 115.725(l) § 115.725(n)	§ 115.726(d)(1) § 115.726(d)(2) § 115.726(d)(3) § 115.726(d)(4) [G]§ 115.726(d)(6) § 115.726(i) § 115.726(j)(1) § 115.726(j)(2)	§ 115.725(n)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
30FL1	CD	60A-1	OPACITY	40 CFR Part 60, Subpart A	§ 60.18(b) § 60.18(c)(1) § 60.18(c)(2) § 60.18(c)(3)(ii) § 60.18(c)(4)(i) § 60.18(c)(6) § 60.18(e)	Flares shall comply with paragraphs (c)-(f) of § 60.18.	§ 60.18(d) § 60.18(f)(1) § 60.18(f)(2) § 60.18(f)(3) § 60.18(f)(4)	None	None
30FL1	CD	63A-0	OPACITY	40 CFR Part 63, Subpart A	§ 63.11(b)(4) § 63.11(b)(1) § 63.11(b)(2) § 63.11(b)(3) § 63.11(b)(5) § 63.11(b)(6)(ii) § 63.11(b)(7)(i)	Flares shall be designed and operated with no visible emissions, except for periods of a total of 5 minutes or less during any 2 consecutive hrs. Test Method 22 in App. A of part 60 of this chapter shall be used.	§ 63.11(b)(4) § 63.11(b)(5) § 63.11(b)(7)(i)	None	None
30FL6	EU	R1111-1	OPACITY	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(4)(A)	Visible emissions from a process gas flare shall not be permitted for more than five minutes in any two-hour period, except for emission event emissions as provided in §101.222(b).	§ 111.111(a)(4)(A)(i) § 111.111(a)(4)(A)(ii)	§ 111.111(a)(4)(A)(ii)	None
30FL6	EP	R5720-1	HIGHLY REACTIVE VOC	30 TAC Chapter 115, HRVOC Vent Gas	§ 115.722(d) § 115.722(d)(1) § 115.722(d)(2) [G]§ 115.725(d)(1) § 115.725(f)(1) § 115.725(f)(2) § 115.725(f)(3) § 115.725(f)(4) § 115.725(f)(5) § 115.725(f)(6) [G]§ 115.725(l)	All flares must continuously meet the requirements of 40 CFR § 60.18(c)(2)-(6) and (d) as amended through October 17, 2000 (65 FR 61744) when vent gas containing HRVOC is being routed to the flare.	[G]§ 115.725(d)(1) § 115.725(f)(1) § 115.725(f)(2) § 115.725(f)(3) § 115.725(f)(4) § 115.725(f)(4)(A) § 115.725(f)(5) § 115.725(f)(6) [G]§ 115.725(l) § 115.725(n)	§ 115.726(d)(1) § 115.726(d)(2) § 115.726(d)(3) § 115.726(d)(4) [G]§ 115.726(d)(6) § 115.726(i) § 115.726(j)(1) § 115.726(j)(2)	§ 115.725(n)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
30FL6	CD	60A-1	OPACITY	40 CFR Part 60, Subpart A	§ 60.18(b) § 60.18(c)(1) § 60.18(c)(2) § 60.18(c)(3)(ii) § 60.18(c)(4)(i) § 60.18(c)(6) § 60.18(e)	Flares shall comply with paragraphs (c)-(f) of § 60.18.	§ 60.18(d) § 60.18(f)(1) § 60.18(f)(2) § 60.18(f)(3) § 60.18(f)(4)	None	None
30FL6	CD	63A-0	OPACITY	40 CFR Part 63, Subpart A	§ 63.11(b)(4) § 63.11(b)(1) § 63.11(b)(2) § 63.11(b)(3) § 63.11(b)(5) § 63.11(b)(6)(ii) § 63.11(b)(7)(i)	Flares shall be designed and operated with no visible emissions, except for periods of a total of 5 minutes or less during any 2 consecutive hrs. Test Method 22 in App. A of part 60 of this chapter shall be used.	§ 63.11(b)(4) § 63.11(b)(5) § 63.11(b)(7)(i)	None	None
22FUG	EU	R5352-FUG	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(2) § 115.352(9)	Each pressure relief valve equipped with a rupture disk must comply with §115.352(9) and §115.356(3)(C).	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
22FUG	EU	R5352-FUG	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7) § 115.357(1)	No process drains shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dropping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
22FUG	EU	R5352-FUG	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7)	No process drains shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dropping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(5)	None
22FUG	EU	R5352-FUG	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(8) § 115.357(1) § 115.357(12) § 115.357(8)	No flanges or other connectors shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dropping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
22FUG	EU	R5352-FUG	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(8) § 115.357(12) § 115.357(8)	No flanges or other connectors shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dropping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
22FUG	EU	R5352-FUG	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	No compressor seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dropping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
22FUG	EU	R5352-FUG	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	No pump seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dropping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
22FUG	EU	60GGG-FUG	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(d)	Comply with the requirements as stated in §60.482-1(d) for equipment in vacuum service.	None	§ 60.486(e) § 60.486(e)(1) § 60.486(e)(5)	None
22FUG	EU	60GGG-FUG	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-2 [G]§ 60.482-9	Comply with the requirements as stated in §60.482-2 for pumps in light-liquid service.	[G]§ 60.482-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d) § 60.593(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
22FUG	EU	60GGG-FUG	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-3 [G]§ 60.482-9	Comply with the requirements as stated in §60.482-3 for compressors.	[G]§ 60.482-3 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
22FUG	EU	60GGG-FUG	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-4 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-4 for pressure relief devices in gas/vapor service.	[G]§ 60.482-4 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(3) [G]§ 60.486(e)(4) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
22FUG	EU	60GGG-FUG	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-5 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-5 for sampling connection systems.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
22FUG	EU	60GGG-FUG	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-6 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-6 for open-ended valves and lines.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
22FUG	EU	60GGG-FUG	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-7 [G]§ 60.482-9 [G]§ 60.483-1 [G]§ 60.483-2 § 60.592(b)	Comply with the requirements in as stated in §60.482-7 for valves in gas/vapor or light-liquid service.	[G]§ 60.482-7 [G]§ 60.483-1 [G]§ 60.483-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d) § 60.593(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) [G]§ 60.486(g) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(d) § 60.487(e) § 60.592(e)
22FUG	EU	60GGG-FUG	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for pumps in heavy-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
22FUG	EU	60GGG-FUG	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.18 § 60.482-1(a) § 60.482-1(b) § 60.482-10(d) § 60.482-10(e) § 60.482-10(m)	Comply with the requirements in as stated in §60.482-10 for flares.	§ 60.485(a) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) [G]§ 60.485(g) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
22FUG	EU	60GGG-FUG	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) § 60.482-10(e) [G]§ 60.482-10(g) § 60.482-10(h) § 60.482-10(m)	Comply with the requirements in as stated in §60.482-10 for closed-vent systems.	[G]§ 60.482-10(f) § 60.482-10(i) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.482-10(j) [G]§ 60.482-10(k) [G]§ 60.482-10(l) [G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
22FUG	EU	60GGG-FUG	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for valves in heavy-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
22FUG	EU	60GGG-FUG	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for flanges or other connectors.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
22FUG	EU	60GGG-FUG	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for pressure relief devices in light-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
22FUG	EU	63CC-FUG	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(c)(1) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.163 [G]§ 63.171 [G]§ 63.176 § 63.648(f) § 63.655(d)(2)	Comply with the specified Subpart H requirements for pumps in light liquid service, instrument readings that define a leak are specified in Subpart CC, table 2.	[G]§ 63.163 [G]§ 63.176 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(3) § 63.648(c)(4) § 63.648(c)(6) § 63.648(c)(7) § 63.648(c)(8)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(3) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(8) § 63.181(h)(9) § 63.648(h) § 63.655(d)(1)(i) § 63.655(d)(6) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(v)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
22FUG	EU	63CC-FUG	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for non-reciprocating pumps in heavy liquid service.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(6)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
22FUG	EU	63CC-FUG	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.164 [G]§ 63.171 § 63.648(i) § 63.655(d)(2)	Comply with the specified Subpart H requirements for compressors which are not in hydrogen service.	[G]§ 63.164 [G]§ 63.180(b) [G]§ 63.180(c) [G]§ 63.180(d) [G]§ 63.648(b)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(f) § 63.648(h) § 63.655(d)(1)(i) § 63.655(d)(6) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
22FUG	EU	63CC-FUG	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.165 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for pressure relief devices in gas/vapor service.	[G]§ 63.165 [G]§ 63.180(b) [G]§ 63.180(c) [G]§ 63.180(d) [G]§ 63.648(b)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(f) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
22FUG	EU	63CC-FUG	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for pressure relief device in liquid service.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(6)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
22FUG	EU	63CC-FUG	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.166 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for sampling connection systems.	[G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(i) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
22FUG	EU	63CC-FUG	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.167 [G]§ 63.171 [G]§ 63.175 § 63.655(d)(2)	Comply with the specified Subpart H requirements for open-ended valves and lines.	[G]§ 63.175 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(9) [G]§ 63.181(i) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
22FUG	EU	63CC-FUG	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(c)(1) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.168 [G]§ 63.171 [G]§ 63.175 § 63.648(c)(2)(ii) § 63.648(c)(9) § 63.655(d)(2)	Comply with the specified Subpart H requirements for valves in gas/vapor and light liquid service, instrument readings defining a leak are specified in Subpart CC, table 2.	[G]§ 63.168 [G]§ 63.175 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(3) § 63.648(c)(4) § 63.648(c)(8)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(9) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(v)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
22FUG	EU	63CC-FUG	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for valves in heavy liquid service.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(6)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
22FUG	EU	63CC-FUG	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(c)(5) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.649(a) § 63.655(d)(2)	Connectors in gas/vapor or light liquid are subject to the requirements in heavy liquid service in §63.169. The leak definition for specified systems subject to §63.169 is 1,000 parts per million.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(4)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(v)
22FUG	EU	63CC-FUG	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(c)(2)(ii) § 63.649(e)	If an owner or operator elects to monitor connectors according to §63.649(b), (c), or (d), then the owner or operator shall monitor valves at the frequencies specified in table 9 of this subpart.	[G]§ 63.649(c)	§ 63.649(g)	§ 63.655(f) § 63.655(f)(1)(v)
22FUG	EU	63CC-FUG	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for connectors in heavy liquid service.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(6)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
22FUG	EU	63CC-FUG	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for instrumentation systems.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(6)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
22FUG	EU	63CC-FUG	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.172(a) [G]§ 63.172(h) § 63.172(i) § 63.172(j)(1) § 63.172(j)(2) § 63.172(m) § 63.655(d)(2)	Comply with the specified Subpart H requirements for closed vent systems.	[G]§ 63.172(f)(1) [G]§ 63.172(f)(2) § 63.172(g) [G]§ 63.172(h) § 63.172(j)(1) § 63.172(j)(2) [G]§ 63.172(k) [G]§ 63.172(l) [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b)	§ 63.118(a)(3) § 63.172(j)(1) [G]§ 63.172(k) [G]§ 63.172(l) § 63.181(a) § 63.181(c) [G]§ 63.181(d) § 63.181(g) § 63.181(g)(1)(i) § 63.181(g)(1)(ii) [G]§ 63.181(g)(2) [G]§ 63.181(g)(3) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e) [G]§ 63.655(f)(1)(i)(C) [G]§ 63.655(f)(1)(i)(D)
22FUG	EU	63CC-FUG	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.172(b) § 63.172(e) [G]§ 63.172(h) § 63.172(m) § 63.655(d)(2)	Comply with the specified Subpart H requirements for vapor recovery systems.	§ 63.172(e) [G]§ 63.172(h) [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(g) § 63.181(g)(1)(i) § 63.181(g)(1)(ii) § 63.181(g)(1)(iv) [G]§ 63.181(g)(2) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
22FUG	EU	63CC-FUG	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.11(b) § 63.172(d) § 63.172(e) [G]§ 63.172(h) § 63.172(m) § 63.655(d)(2)	Comply with the specified Subpart H requirements for flares.	§ 63.172(e) [G]§ 63.172(h) [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.180(e)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(g) § 63.181(g)(1)(i) § 63.181(g)(1)(ii) § 63.181(g)(1)(iii) § 63.181(g)(1)(iv) [G]§ 63.181(g)(2) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e) [G]§ 63.655(f)(1)(i)(D)
40FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7) § 115.357(1)	No process drains, contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
40FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7)	No process drains, contacting a process fluid with a TVP >0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
40FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.352(9) § 115.357(1) § 115.357(12)	No pressure relief valves (gaseous service), contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, longer than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
40FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.352(9) § 115.357(12) § 115.357(8)	No pressure relief valves (gaseous service), contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, longer than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
40FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No open-ended valves or lines, in an emergency shutdown system or containing materials that would autocatalytically polymerize or would present an explosion, serious overpressure, or other safety hazard if capped or equipped with a double block and bleed system, and contacting a process fluid with a TVP < 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
40FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No open-ended valves or lines, in an emergency shutdown system or containing materials that would autocatalytically polymerize or would present an explosion, serious overpressure, or other safety hazard if capped or equipped with a double block and bleed system, and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
40FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No open-ended valves or lines, rated > 10,000 psig and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
40FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No open-ended valves or lines, rated 10,000 psig or greater and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
40FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No open-ended valves or lines, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
40FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No open-ended valves or lines, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
40FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No valves, rated 10,000 psig or greater and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
40FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No valves, rated 10,000 psig or greater and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
40FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No valves, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
40FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No valves, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
40FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1) § 115.357(12)	No flanges, contacting a process fluid with a TVP of 0.044 psia or less, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
40FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	No flanges, contacting a process fluid with a TVP >0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
40FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1)	No compressor seal, contacting a process fluid with a TVP of 0.044 psia or less, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
40FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7)	No compressor seal, in hydrogen service or equipped with a shaft seal system, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
40FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(8)	No compressor seals, contacting a process fluid with a TVP >0.044 psia, not in hydrogen service or not equipped with a shaft seal, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
40FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1)	No pump seals, contacting a process fluid with a TVP of 0.044 psia or less, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
40FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7)	No pump seal, equipped with a shaft seal system, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
40FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(8)	No pump seals, contacting a process fluid with a TVP >0.044 psia and not equipped with a shaft seal system, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
40FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(6)	Components at a petroleum refinery or synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process, that contact a process fluid that contains less than 10% VOC by weight and components at a natural gas/gasoline processing operation that contact a process fluid that contains less than 1.0% VOC by weight are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
40FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(5)	Reciprocating compressors and positive displacement pumps used in natural gas/gasoline processing operations are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
40FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(2) § 115.352(9)	Each pressure relief valve equipped with a rupture disk must comply with §115.352(9) and §115.356(3)(C).	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
40FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(10)	Instrumentation systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet 40 CFR §63.169 (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
40FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(11)	Sampling connection systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet the requirements of 40 CFR §63.166(a) and (b) (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
40FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(13)	Components/systems that contact a process fluid containing VOC having a true vapor pressure equal to or less than 0.002 psia at 68 degrees Fahrenheit are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
40FUG	EU	60GGG-ALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(d)	Comply with the requirements as stated in §60.482-1(d) for equipment in vacuum service.	None	§ 60.486(e) § 60.486(e)(1) § 60.486(e)(5)	None
40FUG	EU	60GGG-ALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-2 [G]§ 60.482-9	Comply with the requirements as stated in §60.482-2 for pumps in light-liquid service.	[G]§ 60.482-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d) § 60.593(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
40FUG	EU	60GGG-ALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) § 60.482-3(f) § 60.482-3(g)(1) § 60.482-3(g)(2) [G]§ 60.482-3(i) § 60.482-3(j) [G]§ 60.482-9 § 60.593(c)	Comply with the requirements as stated in §60.482-3 for reciprocating compressors that become subject under §60.14 and §60.15.	§ 60.482-3(f) § 60.482-3(g)(1) § 60.482-3(g)(2) [G]§ 60.482-3(i) § 60.482-3(j) § 60.485(a) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
40FUG	EU	60GGG-ALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-3 [G]§ 60.482-9	Comply with the requirements as stated in §60.482-3 for compressors.	[G]§ 60.482-3 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
40FUG	EU	60GGG-ALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-4 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-4 for pressure relief devices in gas/vapor service.	[G]§ 60.482-4 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(3) [G]§ 60.486(e)(4) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
40FUG	EU	60GGG-ALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-5 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-5 for sampling connection systems.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
40FUG	EU	60GGG-ALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-6 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-6 for open-ended valves and lines.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
40FUG	EU	60GGG-ALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-7 [G]§ 60.482-9 [G]§ 60.483-1 [G]§ 60.483-2 § 60.592(b)	Comply with the requirements in as stated in §60.482-7 for valves in gas/vapor or light-liquid service.	[G]§ 60.482-7 [G]§ 60.483-1 [G]§ 60.483-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d) § 60.593(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) [G]§ 60.486(g) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(d) § 60.487(e) § 60.592(e)
40FUG	EU	60GGG-ALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for pumps in heavy-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
40FUG	EU	60GGG-ALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for valves in heavy-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
40FUG	EU	60GGG-ALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for pressure relief devices in light-liquid service.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
40FUG	EU	60GGG-ALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for flanges or other connectors.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
40FUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	[G]§ 63.648(g)	Compressors in hydrogen service are exempt from the requirements of §63.648(a) and (c), if an owner or operator demonstrates that a compressor is in hydrogen service. §63.648(g)(1)-(2).	[G]§ 63.648(g)	§ 63.648(h) § 63.654(d)(3)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
40FUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(d)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for equipment in vacuum service.	None	§ 60.486(e) § 60.486(e)(1) § 60.486(e)(5)	None
40FUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-2 [G]§ 60.482-9 § 63.648(a)(2) § 63.648(f) § 63.654(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pumps in light liquid service complying with §60.482-2.	[G]§ 60.482-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 63.648(h) § 63.654(d)(1)(i) § 63.654(d)(6)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
40FUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-3 [G]§ 60.482-9 § 63.648(a)(2) § 63.648(i) § 63.654(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for compressors complying with §60.482-3.	[G]§ 60.482-3 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 63.648(h) § 63.654(d)(1)(i) § 63.654(d)(6)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
40FUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) § 60.482-4(a) § 60.482-4(b)(1) [G]§ 60.482-9 § 63.648(a)(2) § 63.654(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pressure relief devices in gas/vapor service.	§ 60.482-4(b)(2) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(3) [G]§ 60.486(e)(4) § 63.648(h) § 63.654(d)(1)(i)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
40FUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-5 [G]§ 60.482-9 § 63.648(a)(2) § 63.654(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for sampling connection systems complying with §60.482-5.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 63.648(h) § 63.654(d)(1)(i)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
40FUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-6 [G]§ 60.482-9 § 63.648(a)(2) § 63.654(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for open-ended valves or lines complying with §60.482-6.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 63.648(h) § 63.654(d)(1)(i)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
40FUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-7 [G]§ 60.482-9 [G]§ 60.483-1 [G]§ 60.483-2 § 63.648(a)(2) § 63.654(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for valves in gas/vapor service or in light liquid service complying with §60.482-7.	[G]§ 60.482-7 [G]§ 60.483-1 [G]§ 60.483-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) [G]§ 60.486(g) § 63.648(h) § 63.654(d)(1)(i)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(d) § 60.487(e)
40FUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.654(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pumps in heavy liquid service complying with §60.482-8.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 63.648(h) § 63.654(d)(1)(i)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
40FUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.654(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for valves in heavy liquid service complying with §60.482-8.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 63.648(h) § 63.654(d)(1)(i)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
40FUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.654(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pressure relief devices in light liquid service complying with §60.482-8.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 63.648(h) § 63.654(d)(1)(i)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
40FUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.654(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pressure relief devices in light liquid service complying with §60.482-8.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 63.648(h) § 63.654(d)(1)(i)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
40FUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.654(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for flanges or other connectors complying with §60.482-8.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 63.648(h) § 63.654(d)(1)(i)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
44FUG	EU	R5352-FUG	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(2) § 115.352(9)	Each pressure relief valve equipped with a rupture disk must comply with §115.352(9) and §115.356(3)(C).	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
44FUG	EU	R5352-FUG	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7) § 115.357(1)	No process drains shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dropping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
44FUG	EU	R5352-FUG	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7)	No process drains shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dropping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
44FUG	EU	R5352-FUG	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(8) § 115.357(1) § 115.357(12) § 115.357(8)	No flanges or other connectors shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dropping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
44FUG	EU	R5352-FUG	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(8) § 115.357(12) § 115.357(8)	No flanges or other connectors shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dropping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
44FUG	EU	R5352-FUG	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	No compressor seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dropping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
44FUG	EU	R5352-FUG	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	No pump seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dropping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
44FUG	EU	60GGG-FUG	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(d)	Comply with the requirements as stated in §60.482-1(d) for equipment in vacuum service.	None	§ 60.486(e) § 60.486(e)(1) § 60.486(e)(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
44FUG	EU	60GGG-FUG	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-2 [G]§ 60.482-9	Comply with the requirements as stated in §60.482-2 for pumps in light-liquid service.	[G]§ 60.482-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d) § 60.593(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
44FUG	EU	60GGG-FUG	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-3 [G]§ 60.482-9	Comply with the requirements as stated in §60.482-3 for compressors.	[G]§ 60.482-3 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
44FUG	EU	60GGG-FUG	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-4 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-4 for pressure relief devices in gas/vapor service.	[G]§ 60.482-4 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(3) [G]§ 60.486(e)(4) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
44FUG	EU	60GGG-FUG	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-5 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-5 for sampling connection systems.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
44FUG	EU	60GGG-FUG	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-6 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-6 for open-ended valves and lines.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
44FUG	EU	60GGG-FUG	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-7 [G]§ 60.482-9 [G]§ 60.483-1 [G]§ 60.483-2 § 60.592(b)	Comply with the requirements in as stated in §60.482-7 for valves in gas/vapor or light-liquid service.	[G]§ 60.482-7 [G]§ 60.483-1 [G]§ 60.483-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d) § 60.593(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) [G]§ 60.486(g) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(d) § 60.487(e) § 60.592(e)
44FUG	EU	60GGG-FUG	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for pumps in heavy-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
44FUG	EU	60GGG-FUG	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.18 § 60.482-1(a) § 60.482-1(b) § 60.482-10(d) § 60.482-10(e) § 60.482-10(m)	Comply with the requirements in as stated in §60.482-10 for flares.	§ 60.485(a) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) [G]§ 60.485(g) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
44FUG	EU	6oGGG-FUG	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) § 60.482-10(e) [G]§ 60.482-10(g) § 60.482-10(h) § 60.482-10(m)	Comply with the requirements in as stated in §60.482-10 for closed-vent systems.	[G]§ 60.482-10(f) § 60.482-10(i) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.482-10(j) [G]§ 60.482-10(k) [G]§ 60.482-10(l) [G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
44FUG	EU	6oGGG-FUG	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for valves in heavy-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
44FUG	EU	6oGGG-FUG	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for flanges or other connectors.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
44FUG	EU	6oGGG-FUG	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for pressure relief devices in light-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
5GFUG	EU	63GGGGG-1	112(B) HAPS	40 CFR Part 63, Subpart GGGGG	§ 63.7887 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart GGGGG	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart GGGGG	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart GGGGG	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart GGGGG	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart GGGGG
GRP-FUG	EU	R5352-FUG	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(6)	Components at a petroleum refinery or synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process, that contact a process fluid that contains less than 10% VOC by weight and components at a natural gas/gasoline processing operation that contact a process fluid that contains less than 1.0% VOC by weight are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-FUG	EU	R5352-FUG	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(10)	Instrumentation systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet 40 CFR §63.169 (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
GRP-FUG	EU	R5352-FUG	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(11)	Sampling connection systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet the requirements of 40 CFR §63.166(a) and (b) (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
GRP-FUG	EU	R5352-FUG	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(13)	Components/systems that contact a process fluid containing VOC having a true vapor pressure equal to or less than 0.002 psia at 68 degrees Fahrenheit are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-FUG	EU	R5352-FUG	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7) § 115.357(1)	No process drains shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dropping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
GRP-FUG	EU	R5352-FUG	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7)	No process drains shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dropping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-FUG	EU	R5352-FUG	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(8) § 115.357(1) § 115.357(12) § 115.357(8)	No flanges or other connectors shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dropping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
GRP-FUG	EU	R5352-FUG	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(8) § 115.357(12) § 115.357(8)	No flanges or other connectors shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dropping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-FUG	EU	R5352-FUG	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	No compressor seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dropping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
GRP-FUG	EU	R5352-FUG	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1) § 115.357(8)	No pump seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dropping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-FUG	EU	R5352-FUG	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	No pump seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dropping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
GRP-FUG	EU	60GGG-FUG	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-2 [G]§ 60.482-9	Comply with the requirements as stated in §60.482-2 for pumps in light-liquid service.	[G]§ 60.482-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d) § 60.593(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-FUG	EU	60GGG-FUG	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-3 [G]§ 60.482-9	Comply with the requirements as stated in §60.482-3 for compressors.	[G]§ 60.482-3 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-FUG	EU	60GGG-FUG	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-4 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-4 for pressure relief devices in gas/vapor service.	[G]§ 60.482-4 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(3) [G]§ 60.486(e)(4) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-FUG	EU	60GGG-FUG	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-5 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-5 for sampling connection systems.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-FUG	EU	60GGG-FUG	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-7 [G]§ 60.482-9 [G]§ 60.483-1 [G]§ 60.483-2 § 60.592(b)	Comply with the requirements in as stated in §60.482-7 for valves in gas/vapor or light-liquid service.	[G]§ 60.482-7 [G]§ 60.483-1 [G]§ 60.483-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d) § 60.593(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) [G]§ 60.486(g) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(d) § 60.487(e) § 60.592(e)
GRP-FUG	EU	60GGG-FUG	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for pumps in heavy-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-FUG	EU	6oGGG-FUG	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) § 60.482-10(e) [G]§ 60.482-10(g) § 60.482-10(h) § 60.482-10(m)	Comply with the requirements in as stated in §60.482-10 for closed-vent systems.	[G]§ 60.482-10(f) § 60.482-10(i) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.482-10(j) [G]§ 60.482-10(k) [G]§ 60.482-10(l) [G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-FUG	EU	6oGGG-FUG	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for valves in heavy-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-FUG	EU	6oGGG-FUG	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for flanges or other connectors.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-FUG	EU	6oGGG-FUG	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for pressure relief devices in light-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-FUG	EU	63CC-FUG	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-2 [G]§ 60.482-9 § 63.648(a)(2) § 63.648(f) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pumps in light liquid service complying with §60.482-2.	[G]§ 60.482-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(d)(6) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
GRP-FUG	EU	63CC-FUG	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-3 [G]§ 60.482-9 § 63.648(a)(2) § 63.648(i) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for compressors complying with §60.482-3.	[G]§ 60.482-3 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(d)(6) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
GRP-FUG	EU	63CC-FUG	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) § 60.482-4(a) § 60.482-4(b)(1) [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pressure relief devices in gas/vapor service.	§ 60.482-4(b)(2) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(3) [G]§ 60.486(e)(4) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-FUG	EU	63CC-FUG	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-5 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for sampling connection systems complying with §60.482-5.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
GRP-FUG	EU	63CC-FUG	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-7 [G]§ 60.482-9 [G]§ 60.483-1 [G]§ 60.483-2 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for valves in gas/vapor service or in light liquid service complying with §60.482-7.	[G]§ 60.482-7 [G]§ 60.483-1 [G]§ 60.483-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) [G]§ 60.486(g) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(d) § 60.487(e)
GRP-FUG	EU	63CC-FUG	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for valves in heavy liquid service complying with §60.482-8.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-FUG	EU	63CC-FUG	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pumps in heavy liquid service complying with §60.482-8.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
GRP-FUG	EU	63CC-FUG	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for flanges or other connectors complying with §60.482-8.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
GRP-FUG	EU	63CC-FUG	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pressure relief devices in light liquid service complying with §60.482-8.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
GRP-FUG	EU	63CC-FUG	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pressure relief devices in heavy liquid service complying with §60.482-8.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-FUG	EU	63CC-FUG	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) § 60.482-10(e) [G]§ 60.482-10(g) § 60.482-10(h) § 60.482-10(m) § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for closed vent (or vapor collection) systems complying with §60.482-10.	[G]§ 60.482-10(f) § 60.482-10(i) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.482-10(j) [G]§ 60.482-10(k) [G]§ 60.482-10(l) [G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) [G]§ 63.655(f)(1)(i)(C) [G]§ 63.655(f)(1)(i)(D)
39RX2001	EU	R2SRU-1B	SO ₂	30 TAC Chapter 112, Sulfur Compounds	§ 112.7(a) § 112.7(b)	No person may cause, suffer, allow, or permit emissions of SO ₂ to exceed the emission limits specified for stack effluent flow rates < 4,000 scfm as determined by the specified equation.	§ 112.2(a) ** See CAM Summary	§ 112.2(c)	§ 112.2(b)
39RX2001	EU	R2SRU-1C	SO ₂	30 TAC Chapter 112, Sulfur Compounds	§ 112.7(a) § 112.7(b)	No person may cause, suffer, allow, or permit emissions of SO ₂ to exceed the emission limits specified for stack effluent flow rates < 4,000 scfm as determined by the specified equation.	§ 112.2(a) ** See CAM Summary	§ 112.2(c)	§ 112.2(b)
46RX6206	EU	R2SRU-1B	SO ₂	30 TAC Chapter 112, Sulfur Compounds	§ 112.7(a) § 112.7(b)	No person may cause, suffer, allow, or permit emissions of SO ₂ to exceed the emission limits specified for stack effluent flow rates < 4,000 scfm as determined by the specified equation.	§ 112.2(a) ** See CAM Summary	§ 112.2(c)	§ 112.2(b)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
46RX6206	EU	R2SRU-1C	SO ₂	30 TAC Chapter 112, Sulfur Compounds	§ 112.7(a) § 112.7(b)	No person may cause, suffer, allow, or permit emissions of SO ₂ to exceed the emission limits specified for stack effluent flow rates < 4,000 scfm as determined by the specified equation.	§ 112.2(a) ** See CAM Summary	§ 112.2(c)	§ 112.2(b)
GRP-CWT	EU	R5760-1	HIGHLY REACTIVE VOC	30 TAC Chapter 115, HRVOC Cooling Towers	§ 115.761(c)(1) § 115.761(c)(3) § 115.764(a)(1) § 115.766(i)	HRVOC emissions at each site located in Harris County that is subject to this division or Division 1 of this subchapter must not exceed 1,200 pounds of HRVOCs per one-hour block period from any flare, vent, pressure relief valve, cooling tower, or any combination.	§ 115.764(a)(1) § 115.764(a)(3) [G]§ 115.764(a)(6) § 115.764(c)	§ 115.766(a)(1) § 115.766(a)(2) § 115.766(a)(3) § 115.766(a)(5) § 115.766(a)(6) § 115.766(c) [G]§ 115.766(g) [G]§ 115.766(h) § 115.766(i)(1)	§ 115.766(i)(2)
9058LOAD	EU	R5217-1	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(a)(1) § 115.214(a)(1)(B) § 115.214(a)(1)(D) § 115.214(a)(1)(D)(i)	Vapor pressure (at land-based operations). All land-based loading and unloading of VOC with a true vapor pressure less than 0.5 psia is exempt from the requirements of this division, except as specified.	§ 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.215 § 115.215(4)	§ 115.216 § 115.216(2) § 115.216(3)(B)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
9059LOAD	EU	R5217-1	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(a)(3) § 115.212(a)(2) § 115.214(a)(1)(B) § 115.214(a)(1)(D) § 115.214(a)(1)(D)(i)	Liquefied petroleum gas. All loading and unloading of liquefied petroleum gas is exempt from the requirements of this division, except for the specified requirements.	§ 115.214(a)(1)(A) § 115.214(a)(1)(A)(i)	§ 115.216 § 115.216(3)(A) § 115.216(3)(A)(i) § 115.216(3)(A)(ii) § 115.216(3)(A)(iii) § 115.216(3)(B)	None
90DOCK1	EU	REGV-LOAD1	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.212(a)(6)(A) § 115.212(a)(6)(B) [G]§ 115.212(a)(6)(C) § 115.212(a)(6)(D) [G]§ 115.214(a)(3)(A) § 115.214(a)(3)(C) § 115.214(a)(3)(D) § 115.214(a)(3)(E)	Emissions shall not exceed 0.09lb/1,000gal loaded, or the vapor control system shall maintain a control efficiency of at least 90%, or a vapor balance system or pressurized loading may be used.	[G]§ 115.214(a)(3)(A) § 115.214(a)(3)(B) § 115.214(a)(3)(B)(i) § 115.214(a)(3)(B)(ii) § 115.214(a)(3)(B)(iii) § 115.214(a)(3)(D) § 115.215 § 115.215(1) § 115.215(10) [G]§ 115.215(2) § 115.215(4) § 115.215(5) § 115.215(7) § 115.215(8) § 115.215(9) § 115.216(1) § 115.216(1)(A) § 115.216(1)(A)(iv)	[G]§ 115.214(a)(3)(A) § 115.214(a)(3)(D) § 115.216 § 115.216(1) § 115.216(1)(A) § 115.216(1)(A)(iv) § 115.216(2) [G]§ 115.216(4)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
90DOCK1	EU	REGV-LOAD2	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.212(a)(6)(A) § 115.212(a)(6)(B) [G]§ 115.212(a)(6)(C) § 115.212(a)(6)(D) [G]§ 115.214(a)(3)(A) § 115.214(a)(3)(C) § 115.214(a)(3)(D) § 115.214(a)(3)(E)	Emissions shall not exceed 0.09lb/1,000gal loaded, or the vapor control system shall maintain a control efficiency of at least 90%, or a vapor balance system or pressurized loading may be used.	[G]§ 115.214(a)(3)(A) § 115.214(a)(3)(B) § 115.214(a)(3)(B)(i) § 115.214(a)(3)(B)(ii) § 115.214(a)(3)(B)(iii) § 115.214(a)(3)(D) § 115.215 § 115.215(1) § 115.215(10) [G]§ 115.215(2) § 115.215(4) § 115.215(5) § 115.215(7) § 115.215(8) § 115.215(9) § 115.216(1) § 115.216(1)(A) § 115.216(1)(A)(iv)	[G]§ 115.214(a)(3)(A) § 115.214(a)(3)(D) § 115.216 § 115.216(1) § 115.216(1)(A) § 115.216(1)(A)(iv) § 115.216(2) [G]§ 115.216(4)	None
90DOCK1	EU	REGV-LOAD3	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(a)(5)(B) § 115.212(a)(6)(D) § 115.214(a)(3)(C) § 115.214(a)(3)(G) § 115.214(a)(3)(G)(i) § 115.217(a)(5)(B)(iii)	The marine vessel transfer operations specified in § 115.217(a)(5)(B)(i)-(iv) are exempt from the requirements of §§ 115.212(a), 115.214(a), and 115.216 of this title, except as noted.	§ 115.214(a)(3)(B) § 115.214(a)(3)(B)(i) § 115.215 § 115.215(4)	§ 115.216 § 115.216(2)	None
90DOCK1	EU	REGV-LOAD3	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(a)(5)(B) § 115.214(a)(3)(C) § 115.214(a)(3)(G) § 115.214(a)(3)(G)(i) § 115.217(a)(5)(B)(i)	The marine vessel transfer operations specified in § 115.217(a)(5)(B)(i)-(iv) are exempt from the requirements of §§ 115.212(a), 115.214(a), and 115.216 of this title, except as noted.	§ 115.214(a)(3)(B) § 115.214(a)(3)(B)(i)	§ 115.216 § 115.216(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
90DOCK1	EU	REGV-LOAD4	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(a)(3) § 115.214(a)(1)(B) § 115.214(a)(1)(D) § 115.214(a)(1)(D)(i)	Liquefied petroleum gas. All loading and unloading of liquefied petroleum gas is exempt from the requirements of this division, except for the specified requirements.	§ 115.214(a)(1)(A) § 115.214(a)(1)(A)(i)	§ 115.216 § 115.216(3)(A) § 115.216(3)(A)(i) § 115.216(3)(A)(ii) § 115.216(3)(A)(iii) § 115.216(3)(B)	None
90DOCK1	EU	REGV-LOAD4	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(a)(5)(B) § 115.214(a)(3)(C) § 115.214(a)(3)(G) § 115.214(a)(3)(G)(i) § 115.217(a)(5)(B)(i)	The marine vessel transfer operations specified in § 115.217(a)(5)(B)(i)-(iv) are exempt from the requirements of §§ 115.212(a), 115.214(a), and 115.216 of this title, except as noted.	§ 115.214(a)(3)(B) § 115.214(a)(3)(B)(i)	§ 115.216 § 115.216(2)	None
90DOCK1	EU	MACTCC-LOAD1	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.651(a)	Except as provided in §63.651(b)-(d), each owner or operator of a marine tank vessel loading operation located at a petroleum refinery shall comply with the requirements of §63.560 through §63.567.	§ 63.642(d)(1) § 63.642(d)(3) § 63.642(d)(4)	§ 63.642(e) § 63.655(c) § 63.655(i)(5)	§ 63.642(d)(2) § 63.642(f) § 63.655(c)
90DOCK1	EU	MACTY-LOAD1	EXEMPT	40 CFR Part 63, Subpart Y	§ 63.560(a)(2) § 153.282 § 63.560(a)(4)	Existing sources with emissions less than 10 and 25 tons must meet the submerged fill standards of 46 CFR 153.282. This submerged fill requirement does not apply to petroleum refineries.	§ 63.565(l)	§ 63.567(j)(4)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
90DOCK1	EU	MACTY-LOAD2	EXEMPT	40 CFR Part 63, Subpart Y	§ 63.560(a)(2) § 153.282 § 63.560(a)(4)	Existing sources with emissions less than 10 and 25 tons must meet the submerged fill standards of 46 CFR 153.282. This submerged fill requirement does not apply to petroleum refineries.	§ 63.565(l)	§ 63.567(j)(4)	None
90DOCK2	EU	REGV-LOAD3	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(a)(5)(B) § 115.212(a)(6)(D) [G]§ 115.212(a)(7) § 115.214(a)(3)(C) § 115.214(a)(3)(G) § 115.214(a)(3)(G)(i) § 115.217(a)(5)(B)(iii)	The marine vessel transfer operations specified in § 115.217(a)(5)(B)(i)-(iv) are exempt from the requirements of §§ 115.212(a), 115.214(a), and 115.216 of this title, except as noted.	§ 115.214(a)(3)(B) § 115.214(a)(3)(B)(i) § 115.215 § 115.215(4)	§ 115.216 § 115.216(2)	None
90DOCK2	EU	REGV-LOAD3	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(a)(5)(B) [G]§ 115.212(a)(7) § 115.214(a)(3)(C) § 115.214(a)(3)(G) § 115.214(a)(3)(G)(i) § 115.217(a)(5)(B)(i)	The marine vessel transfer operations specified in § 115.217(a)(5)(B)(i)-(iv) are exempt from the requirements of §§ 115.212(a), 115.214(a), and 115.216 of this title, except as noted.	§ 115.214(a)(3)(B) § 115.214(a)(3)(B)(i)	§ 115.216 § 115.216(2)	None
9155LOAD	EU	R5217-1	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(a)(1) § 115.212(a)(2) § 115.214(a)(1)(B) § 115.214(a)(1)(D) § 115.214(a)(1)(D)(i)	Vapor pressure (at land-based operations). All land-based loading and unloading of VOC with a true vapor pressure less than 0.5 psia is exempt from the requirements of this division, except as specified.	§ 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.215 § 115.215(4)	§ 115.216 § 115.216(2) § 115.216(3)(B)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
9157LOAD	EU	R5217-1	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(a)(1) § 115.212(a)(2) § 115.214(a)(1)(B) § 115.214(a)(1)(D) § 115.214(a)(1)(D)(i)	Vapor pressure (at land-based operations). All land-based loading and unloading of VOC with a true vapor pressure less than 0.5 psia is exempt from the requirements of this division, except as specified.	§ 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.215 § 115.215(4)	§ 115.216 § 115.216(2) § 115.216(3)(B)	None
9160LOAD	EU	R5217-1	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(a)(1) § 115.212(a)(2) § 115.214(a)(1)(B) § 115.214(a)(1)(D) § 115.214(a)(1)(D)(i)	Vapor pressure (at land-based operations). All land-based loading and unloading of VOC with a true vapor pressure less than 0.5 psia is exempt from the requirements of this division, except as specified.	§ 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.215 § 115.215(4)	§ 115.216 § 115.216(2) § 115.216(3)(B)	None
GRP-MARINE	EU	R5211-1	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.212(a)(6)(A) § 115.212(a)(6)(B) [G]§ 115.212(a)(6)(C) § 115.212(a)(6)(D) [G]§ 115.214(a)(3)(A) § 115.214(a)(3)(C) § 115.214(a)(3)(D) § 115.214(a)(3)(E)	Emissions shall not exceed 0.09lb/1,000gal loaded, or the vapor control system shall maintain a control efficiency of at least 90%, or a vapor balance system or pressurized loading may be used.	[G]§ 115.214(a)(3)(A) § 115.214(a)(3)(B) § 115.214(a)(3)(B)(i) § 115.214(a)(3)(B)(ii) § 115.214(a)(3)(B)(iii) § 115.214(a)(3)(D) § 115.215 § 115.215(1) § 115.215(10) [G]§ 115.215(2) § 115.215(4) § 115.215(5) § 115.215(7) § 115.215(8) § 115.215(9) § 115.216(1) § 115.216(1)(A) § 115.216(1)(A)(iv)	[G]§ 115.214(a)(3)(A) § 115.214(a)(3)(D) § 115.216 § 115.216(1) § 115.216(1)(A) § 115.216(1)(A)(iv) § 115.216(2) [G]§ 115.216(4)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-MARINE	EU	R5211-1	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(a)(5)(B) § 115.214(a)(3)(C) § 115.214(a)(3)(G) § 115.214(a)(3)(G)(i) § 115.217(a)(5)(B)(ii)	The marine vessel transfer operations specified in § 115.217(a)(5)(B)(i)-(iv) are exempt from the requirements of §§ 115.212(a), 115.214(a), and 115.216 of this title, except as noted.	§ 115.214(a)(3)(B) § 115.214(a)(3)(B)(i) § 115.215 § 115.215(1) [G]§ 115.215(2)	§ 115.216 § 115.216(2)	None
GRP-MARINE	EU	R5211-1	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(a)(5)(B) § 115.214(a)(3)(C) § 115.214(a)(3)(G) § 115.214(a)(3)(G)(i) § 115.217(a)(5)(B)(i)	The marine vessel transfer operations specified in § 115.217(a)(5)(B)(i)-(iv) are exempt from the requirements of §§ 115.212(a), 115.214(a), and 115.216 of this title, except as noted.	§ 115.214(a)(3)(B) § 115.214(a)(3)(B)(i)	§ 115.216 § 115.216(2)	None
GRP-MARINE	EU	R5211-2	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(a)(5)(B) § 115.212(a)(6)(D) § 115.214(a)(3)(C) § 115.214(a)(3)(G) § 115.214(a)(3)(G)(i) § 115.217(a)(5)(B)(iii)	The marine vessel transfer operations specified in § 115.217(a)(5)(B)(i)-(iv) are exempt from the requirements of §§ 115.212(a), 115.214(a), and 115.216 of this title, except as noted.	§ 115.214(a)(3)(B) § 115.214(a)(3)(B)(i) § 115.215 § 115.215(4)	§ 115.216 § 115.216(2)	None
GRP-MARINE	EU	R5211-2	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(a)(5)(B) § 115.214(a)(3)(C) § 115.214(a)(3)(G) § 115.214(a)(3)(G)(i) § 115.217(a)(5)(B)(ii)	The marine vessel transfer operations specified in § 115.217(a)(5)(B)(i)-(iv) are exempt from the requirements of §§ 115.212(a), 115.214(a), and 115.216 of this title, except as noted.	§ 115.214(a)(3)(B) § 115.214(a)(3)(B)(i) § 115.215 § 115.215(1) [G]§ 115.215(2)	§ 115.216 § 115.216(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-MARINE	EU	R5211-2	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(a)(5)(B) § 115.214(a)(3)(C) § 115.214(a)(3)(G) § 115.214(a)(3)(G)(i) § 115.217(a)(5)(B)(i)	The marine vessel transfer operations specified in § 115.217(a)(5)(B)(i)-(iv) are exempt from the requirements of §§ 115.212(a), 115.214(a), and 115.216 of this title, except as noted.	§ 115.214(a)(3)(B) § 115.214(a)(3)(B)(i)	§ 115.216 § 115.216(2)	None
GRP-MARINE	EU	R5211-3	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.212(a)(6)(A) § 115.212(a)(6)(B) [G]§ 115.212(a)(6)(C) § 115.212(a)(6)(D) [G]§ 115.214(a)(3)(A) § 115.214(a)(3)(C) § 115.214(a)(3)(D) § 115.214(a)(3)(E)	Emissions shall not exceed 0.09lb/1,000gal loaded, or the vapor control system shall maintain a control efficiency of at least 90%, or a vapor balance system or pressurized loading may be used.	[G]§ 115.214(a)(3)(A) § 115.214(a)(3)(B) § 115.214(a)(3)(B)(i) § 115.214(a)(3)(B)(ii) § 115.214(a)(3)(B)(iii) § 115.214(a)(3)(D) § 115.215 § 115.215(1) § 115.215(10) [G]§ 115.215(2) § 115.215(4) § 115.215(5) § 115.215(7) § 115.215(8) § 115.215(9)	[G]§ 115.214(a)(3)(A) § 115.214(a)(3)(D) § 115.216 § 115.216(2) [G]§ 115.216(4)	None
GRP-MARINE	EU	R5211-3	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(a)(3) § 115.214(a)(1)(B) § 115.214(a)(1)(D) § 115.214(a)(1)(D)(i)	Liquefied petroleum gas. All loading and unloading of liquefied petroleum gas is exempt from the requirements of this division, except for the specified requirements.	§ 115.214(a)(1)(A) § 115.214(a)(1)(A)(i)	§ 115.216 § 115.216(3)(A) § 115.216(3)(A)(i) § 115.216(3)(A)(ii) § 115.216(3)(A)(iii) § 115.216(3)(B)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-MARINE	EU	R5211-3	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(a)(5)(B) § 115.214(a)(3)(C) § 115.214(a)(3)(G) § 115.214(a)(3)(G)(i) § 115.217(a)(5)(B)(i)	The marine vessel transfer operations specified in § 115.217(a)(5)(B)(i)-(iv) are exempt from the requirements of §§ 115.212(a), 115.214(a), and 115.216 of this title, except as noted.	§ 115.214(a)(3)(B) § 115.214(a)(3)(B)(i)	§ 115.216 § 115.216(2)	None
GRP-MARINE	EU	63CC-1	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.651(a)	Except as provided in §63.651(b)-(d), each owner or operator of a marine tank vessel loading operation located at a petroleum refinery shall comply with the requirements of §63.560 through §63.567.	§ 63.642(d)(1) § 63.642(d)(3) § 63.642(d)(4)	§ 63.642(e) § 63.655(c) § 63.655(i)(5)	§ 63.642(d)(2) § 63.642(f) § 63.655(c)
GRP-MARINE	EU	63Y-1	EXEMPT	40 CFR Part 63, Subpart Y	§ 63.560(a)(2) § 153.282 § 63.560(a)(4)	Existing sources with emissions less than 10 and 25 tons must meet the submerged fill standards of 46 CFR 153.282. This submerged fill requirement does not apply to petroleum refineries.	§ 63.565(l)	§ 63.567(j)(4)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
23BA301	EU	R7300-3	NO _x	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO _x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c)
23BA301	EU	R7300-3	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B) § 117.310(c)(3)	CO emissions must not exceed 400 ppmv at 3.0% O ₂ , dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g)	§ 117.345(a) § 117.345(f) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
23BA302	EU	R7300-2	NO _x	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(ii) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO _x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C) § 117.8000(b) § 117.8000(c) § 117.8000(c)(1) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
23BA302	EU	R7300-2	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B) § 117.310(c)(3)	CO emissions must not exceed 400 ppmv at 3.0% O ₂ , dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.8000(b) § 117.8000(c) § 117.8000(c)(2) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8120 § 117.8120(2) [G]§ 117.8120(2)(A) § 117.8120(2)(B)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
23BA302	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
23BC201	EU	R7300-5	NO _x	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO _x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(2) § 117.335(g) § 117.340(a) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) [G]§ 117.340(c)(3) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(8) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3)
23BC201	EU	R7300-5	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O ₂ , dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(e) [G]§ 117.340(f)(2)	§ 117.345(a) § 117.345(f) [G]§ 117.345(f)(2) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
29BA1300	EU	R7300-2	NO _x	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(ii) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO _x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c)
29BA1300	EU	R7300-2	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B) § 117.310(c)(3)	CO emissions must not exceed 400 ppmv at 3.0% O ₂ , dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g)	§ 117.345(a) § 117.345(f) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c)
42BC2001	EU	63DDDDDD-2	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
44BA3001	EU	R7300-2	NO _x	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(ii) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO _x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C) § 117.8000(b) § 117.8000(c) § 117.8000(c)(1) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
44BA3001	EU	R7300-2	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B) § 117.310(c)(3)	CO emissions must not exceed 400 ppmv at 3.0% O ₂ , dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.8000(b) § 117.8000(c) § 117.8000(c)(2) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8120 § 117.8120(2) [G]§ 117.8120(2)(A) § 117.8120(2)(B)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
44BA3001	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
44BA3002	EU	R7300-3	NO _x	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO _x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C) § 117.8000(b) § 117.8000(c) § 117.8000(c)(1) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
44BA3002	EU	R7300-3	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B) § 117.310(c)(3)	CO emissions must not exceed 400 ppmv at 3.0% O ₂ , dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.8000(b) § 117.8000(c) § 117.8000(c)(2) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8120 § 117.8120(2) [G]§ 117.8120(2)(A) § 117.8120(2)(B)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
44BA3002	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
44BA3005	EU	R7300-2	NO _x	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(ii) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO _x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C) § 117.8000(b) § 117.8000(c) § 117.8000(c)(1) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
44BA3005	EU	R7300-2	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B) § 117.310(c)(3)	CO emissions must not exceed 400 ppmv at 3.0% O ₂ , dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.8000(b) § 117.8000(c) § 117.8000(c)(2) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8120 § 117.8120(2) [G]§ 117.8120(2)(A) § 117.8120(2)(B)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
44BA3005	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
51HTR	EU	R7300-7	NO _x	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO _x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(2) § 117.335(g) § 117.340(a) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) [G]§ 117.340(c)(3) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
51HTR	EU	R7300-7	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O ₂ , dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a) § 117.340(b)(1) § 117.340(b)(3) § 117.340(e) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
51HTR	EU	R7300-7	NH ₃	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(2) § 117.310(c)(2)(A)	For process heaters that inject urea or ammonia into the exhaust stream for NO _x control, ammonia emissions must not exceed 10 ppmv at 3.0% O ₂ , dry.	§ 117.335(a)(2) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(d) § 117.8000(b) § 117.8000(c) § 117.8000(c)(3) § 117.8000(c)(4) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) [G]§ 117.8130	§ 117.345(a) § 117.345(f) § 117.345(f)(11) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
GRP-HEAT1	EU	R7300-2	NO _x	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(ii) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO _x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C) § 117.8000(b) § 117.8000(c) § 117.8000(c)(1) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-HEAT1	EU	R7300-2	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B) § 117.310(c)(3)	CO emissions must not exceed 400 ppmv at 3.0% O ₂ , dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.8000(b) § 117.8000(c) § 117.8000(c)(2) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8120 § 117.8120(2) [G]§ 117.8120(2)(A) § 117.8120(2)(B)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
GRP-HEAT1	EU	60DDDD D-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
GRP-HEATER	EU	R2112-001	SO ₂	30 TAC Chapter 112, Sulfur Compounds	§ 112.9(c) § 112.9(b)	No person shall use liquid fuel with a sulfur content greater than 0.3% by weight, or allow emissions of SO ₂ to exceed 150 ppmv, based on 20% excess air, averaged over a 3-hour period.	§ 112.2(a)	§ 112.2(c)	§ 112.2(b)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-HEATER	EU	R7300-2NG	NO _x	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(ii) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO _x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C) § 117.8000(b) § 117.8000(c) § 117.8000(c)(1) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-HEATER	EU	R7300-2NG	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B) § 117.310(c)(3)	CO emissions must not exceed 400 ppmv at 3.0% O ₂ , dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.8000(b) § 117.8000(c) § 117.8000(c)(2) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8120 § 117.8120(2) [G]§ 117.8120(2)(A) § 117.8120(2)(B)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
GRP-HEATER	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
DG-AGIT	EU	R5412-1	VOC	30 TAC Chapter 115, Degreasing Processes	§ 115.412(1) [G]§ 115.412(1)(A) § 115.412(1)(C) § 115.412(1)(D) [G]§ 115.412(1)(F) § 115.417(1)	Cold solvent cleaning. No person shall own or operate a system utilizing a VOC for the cold solvent cleaning of objects without the controls listed in §115.412(1)(A)-(F).	[G]§ 115.415(1) § 115.415(3) ** See Periodic Monitoring Summary	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
DG-AGIT2	EU	R5412-1	VOC	30 TAC Chapter 115, Degreasing Processes	§ 115.412(1) [G]§ 115.412(1)(A) § 115.412(1)(C) § 115.412(1)(D) [G]§ 115.412(1)(F) § 115.417(1)	Cold solvent cleaning. No person shall own or operate a system utilizing a VOC for the cold solvent cleaning of objects without the controls listed in §115.412(1)(A)-(F).	[G]§ 115.415(1) § 115.415(3) ** See Periodic Monitoring Summary	None	None
27ENG1	EU	R7300-1	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B)	CO emissions must not exceed 3.0 g/hp-hr for stationary internal combustion engines.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(h)	§ 117.345(a) § 117.345(f) [G]§ 117.345(f)(10) [G]§ 117.345(f)(3) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c)
27ENG1	EU	60III-1	112(B) HAPS	40 CFR Part 60, Subpart III	§ 60.4200(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 60, Subpart III	The permit holder shall comply with the applicable requirements of 40 CFR Part 60, Subpart III	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 60, Subpart III	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 60, Subpart III	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 60, Subpart III

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
27ENG1	EU	63ZZZZ-0	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(c)	A new/reconstructed stationary RICE located at an area source, or located at a major source of HAP emissions and is a spark ignition (SI) 2SLB < 500 HP, SI 4 SLB < 250 HP, or 4SRB, compression ignition (CI), emergency or limited use, or which combusts landfill or digester gas at > 10% of the gross heat input < 500 HP must meet the requirements of this part by meeting the requirements of 40 CFR Part 60, Subpart IIII, for CI engines or 40 CFR Part 60, Subpart JJJJ, for SI engines.	None	None	None
27ENG2	EU	R7300-1	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B)	CO emissions must not exceed 3.0 g/hp-hr for stationary internal combustion engines.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(h)	§ 117.345(a) § 117.345(f) [G]§ 117.345(f)(10) [G]§ 117.345(f)(3) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
27ENG2	EU	60III-1	112(B) HAPS	40 CFR Part 60, Subpart IIII	§ 60.4200(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 60, Subpart IIII	The permit holder shall comply with the applicable requirements of 40 CFR Part 60, Subpart IIII	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 60, Subpart IIII	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 60, Subpart IIII	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 60, Subpart IIII
27ENG2	EU	63ZZZZ-0	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(c)	A new/reconstructed stationary RICE located at an area source, or located at a major source of HAP emissions and is a spark ignition (SI) 2SLB < 500 HP, SI 4 SLB < 250 HP, or 4SRB, compression ignition (CI), emergency or limited use, or which combusts landfill or digester gas at > 10% of the gross heat input < 500 HP must meet the requirements of this part by meeting the requirements of 40 CFR Part 60, Subpart IIII, for CI engines or 40 CFR Part 60, Subpart JJJJ, for SI engines.	None	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
30GG1822	EU	R7300-0	EXEMPT	30 TAC Chapter 117, Subchapter B	§ 117.303(a)(6)(D) [G]§ 117.310(f)	Units exempted from the provisions of this division, except as specified in §§117.310(f), 117.340(j), 117.345(f)(6) and (10), 117.350(c)(1), and 117.354(a)(5), include stationary gas turbines and stationary internal combustion engines that are used exclusively in emergency situations, except that operation for testing or maintenance purposes is allowed for up to 52 hours per year, based on a rolling 12-month average.	None	§ 117.340(j) [G]§ 117.345(f)(10) [G]§ 117.345(f)(6)	None
30GG1822	EU	63ZZZZ-0	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6602-Table2c.1 § 63.6595(a)(1) § 63.6605(a) § 63.6605(b) § 63.6625(e) § 63.6625(h) § 63.6625(i) § 63.6640(b) [G]§ 63.6640(f)(1)	For each existing emergency stationary CI RICE and black start stationary CI RICE, located at a major source, you must comply with the requirements as specified in Table 2c.1.a-c.	§ 63.6625(f) § 63.6625(i) § 63.6640(a) § 63.6640(a)-Table6.9.a.i § 63.6640(a)-Table6.9.a.ii § 63.6640(b)	§ 63.6625(i) § 63.6655(a) § 63.6655(a)(1) § 63.6655(a)(2) § 63.6655(a)(4) § 63.6655(a)(5) § 63.6655(d) § 63.6655(e) § 63.6655(f) § 63.6660(a) § 63.6660(b) § 63.6660(c)	§ 63.6640(b) § 63.6640(e) § 63.6650(f)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
42GG1730	EU	R7300-0	EXEMPT	30 TAC Chapter 117, Subchapter B	§ 117.303(a)(6)(D) [G]§ 117.310(f)	Units exempted from the provisions of this division, except as specified in §§117.310(f), 117.340(j), 117.345(f)(6) and (10), 117.350(c)(1), and 117.354(a)(5), include stationary gas turbines and stationary internal combustion engines that are used exclusively in emergency situations, except that operation for testing or maintenance purposes is allowed for up to 52 hours per year, based on a rolling 12-month average.	None	§ 117.340(j) [G]§ 117.345(f)(10) [G]§ 117.345(f)(6)	None
42GG1730	EU	63ZZZZ-0	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6602-Table2c.1 § 63.6595(a)(1) § 63.6605(a) § 63.6605(b) § 63.6625(e) § 63.6625(h) § 63.6625(i) § 63.6640(b) [G]§ 63.6640(f)(1)	For each existing emergency stationary CI RICE and black start stationary CI RICE, located at a major source, you must comply with the requirements as specified in Table 2c.1.a-c.	§ 63.6625(f) § 63.6625(i) § 63.6640(a) § 63.6640(a)-Table6.9.a.i § 63.6640(a)-Table6.9.a.ii § 63.6640(b)	§ 63.6625(i) § 63.6655(a) § 63.6655(a)(1) § 63.6655(a)(2) § 63.6655(a)(4) § 63.6655(a)(5) § 63.6655(d) § 63.6655(e) § 63.6655(f) § 63.6660(a) § 63.6660(b) § 63.6660(c)	§ 63.6640(b) § 63.6640(e) § 63.6650(f)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
47GG1523	EU	R7300-1	NO _x	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(9)(D) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) [G]§ 117.310(f) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO _x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a)(2)(C) § 117.340(h) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C)	§ 117.345(a) § 117.345(f) [G]§ 117.345(f)(10) [G]§ 117.345(f)(3) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c)
47GG1523	EU	63ZZZZ-0	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6602-Table2c.1 § 63.6595(a)(1) § 63.6605(a) § 63.6605(b) § 63.6625(e) § 63.6625(h) § 63.6625(i) § 63.6640(b) [G]§ 63.6640(f)(1)	For each existing emergency stationary CI RICE and black start stationary CI RICE, located at a major source, you must comply with the requirements as specified in Table 2c.1.a-c.	§ 63.6625(f) § 63.6625(i) § 63.6640(a) § 63.6640(a)-Table6.9.a.i § 63.6640(a)-Table6.9.a.ii § 63.6640(b)	§ 63.6625(i) § 63.6655(a) § 63.6655(a)(1) § 63.6655(a)(2) § 63.6655(a)(4) § 63.6655(a)(5) § 63.6655(d) § 63.6655(e) § 63.6655(f) § 63.6660(a) § 63.6660(b) § 63.6660(c)	§ 63.6640(b) § 63.6640(e) § 63.6650(f)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
81ENG1	EU	R7300-1	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B)	CO emissions must not exceed 3.0 g/hp-hr for stationary internal combustion engines.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(h)	§ 117.345(a) § 117.345(f) [G]§ 117.345(f)(10) [G]§ 117.345(f)(3) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c)
81ENG1	EU	60III-1	112(B) HAPS	40 CFR Part 60, Subpart III	§ 60.4200(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 60, Subpart III	The permit holder shall comply with the applicable requirements of 40 CFR Part 60, Subpart III	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 60, Subpart III	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 60, Subpart III	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 60, Subpart III

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
81ENG1	EU	63ZZZZ-o	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(c)	A new/reconstructed stationary RICE located at an area source, or located at a major source of HAP emissions and is a spark ignition (SI) 2SLB < 500 HP, SI 4 SLB < 250 HP, or 4SRB, compression ignition (CI), emergency or limited use, or which combusts landfill or digester gas at > 10% of the gross heat input < 500 HP must meet the requirements of this part by meeting the requirements of 40 CFR Part 60, Subpart IIII, for CI engines or 40 CFR Part 60, Subpart JJJJ, for SI engines.	None	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
81GEN001	EU	R7300-0	EXEMPT	30 TAC Chapter 117, Subchapter B	[G]§ 117.303(a)(11) [G]§ 117.310(f)	Units exempted from the provisions of this division except as specified in §§117.310(f), 117.340(j), 117.345(f)(6) and (10), 117.350(c)(1) and 117.354(a)(5) include new, modified, reconstructed, or relocated stationary diesel engine placed into service on or after October 1, 2001, that operates less than 100 hours per year, based on a rolling 12-month average, in other than emergency situations; and meets the requirements for non-road engines as specified. §117.303(a)(11)(A)-(B)	None	§ 117.340(j) [G]§ 117.345(f)(10) [G]§ 117.345(f)(6)	None
81GEN001	EU	60III-1	112(B) HAPS	40 CFR Part 60, Subpart III	§ 60.4200(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 60, Subpart III	The permit holder shall comply with the applicable requirements of 40 CFR Part 60, Subpart III	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 60, Subpart III	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 60, Subpart III	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 60, Subpart III

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
81GEN001	EU	63ZZZZ-1	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(c)	A new/reconstructed stationary RICE located at an area source, or located at a major source of HAP emissions and is a spark ignition (SI) 2SLB < 500 HP, SI 4 SLB < 250 HP, or 4SRB, compression ignition (CI), emergency or limited use, or which combusts landfill or digester gas at > 10% of the gross heat input < 500 HP must meet the requirements of this part by meeting the requirements of 40 CFR Part 60, Subpart IIII, for CI engines or 40 CFR Part 60, Subpart JJJJ, for SI engines.	None	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
90GG2245	EU	R7300-0	EXEMPT	30 TAC Chapter 117, Subchapter B	§ 117.303(a)(6)(D) [G]§ 117.310(f)	Units exempted from the provisions of this division, except as specified in §§117.310(f), 117.340(j), 117.345(f)(6) and (10), 117.350(c)(1), and 117.354(a)(5), include stationary gas turbines and stationary internal combustion engines that are used exclusively in emergency situations, except that operation for testing or maintenance purposes is allowed for up to 52 hours per year, based on a rolling 12-month average.	None	§ 117.340(j) [G]§ 117.345(f)(10) [G]§ 117.345(f)(6)	None
90GG2245	EU	63ZZZZ-0	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6602-Table2c.1 § 63.6595(a)(1) § 63.6605(a) § 63.6605(b) § 63.6625(e) § 63.6625(h) § 63.6625(i) § 63.6640(b) [G]§ 63.6640(f)(1)	For each existing emergency stationary CI RICE and black start stationary CI RICE, located at a major source, you must comply with the requirements as specified in Table 2c.1.a-c.	§ 63.6625(f) § 63.6625(i) § 63.6640(a) § 63.6640(a)-Table6.9.a.i § 63.6640(a)-Table6.9.a.ii § 63.6640(b)	§ 63.6625(i) § 63.6655(a) § 63.6655(a)(1) § 63.6655(a)(2) § 63.6655(a)(4) § 63.6655(a)(5) § 63.6655(d) § 63.6655(e) § 63.6655(f) § 63.6660(a) § 63.6660(b) § 63.6660(c)	§ 63.6640(b) § 63.6640(e) § 63.6650(f)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-ENG	EU	R7300-0	EXEMPT	30 TAC Chapter 117, Subchapter B	§ 117.303(a)(6)(D) [G]§ 117.310(f)	Units exempted from the provisions of this division, except as specified in §§117.310(f), 117.340(j), 117.345(f)(6) and (10), 117.350(c)(1), and 117.354(a)(5), include stationary gas turbines and stationary internal combustion engines that are used exclusively in emergency situations, except that operation for testing or maintenance purposes is allowed for up to 52 hours per year, based on a rolling 12-month average.	None	§ 117.340(j) [G]§ 117.345(f)(10) [G]§ 117.345(f)(6)	None
GRP-ENG	EU	63ZZZZ-0	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6602-Table2c.1 § 63.6595(a)(1) § 63.6605(a) § 63.6605(b) § 63.6625(e) § 63.6625(h) § 63.6625(i) § 63.6640(b) [G]§ 63.6640(f)(1)	For each existing emergency stationary CI RICE and black start stationary CI RICE, located at a major source, you must comply with the requirements as specified in Table 2c.1.a-c.	§ 63.6625(f) § 63.6625(i) § 63.6640(a) § 63.6640(a)-Table6.9.a.i § 63.6640(a)-Table6.9.a.ii § 63.6640(b)	§ 63.6625(i) § 63.6655(a) § 63.6655(a)(1) § 63.6655(a)(2) § 63.6655(a)(4) § 63.6655(a)(5) § 63.6655(d) § 63.6655(e) § 63.6655(f) § 63.6660(a) § 63.6660(b) § 63.6660(c)	§ 63.6640(b) § 63.6640(e) § 63.6650(f)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-ENGEMERG	EU	R7300-0	EXEMPT	30 TAC Chapter 117, Subchapter B	[G]§ 117.303(a)(11) [G]§ 117.310(f)	Units exempted from the provisions of this division except as specified in §§117.310(f), 117.340(j), 117.345(f)(6) and (10), 117.350(c)(1) and 117.354(a)(5) include new, modified, reconstructed, or relocated stationary diesel engine placed into service on or after October 1, 2001, that operates less than 100 hours per year, based on a rolling 12-month average, in other than emergency situations; and meets the requirements for non-road engines as specified. §117.303(a)(11)(A)-(B)	None	§ 117.340(j) [G]§ 117.345(f)(10) [G]§ 117.345(f)(6)	None
GRP-ENGEMERG	EU	60III-1	112(B) HAPS	40 CFR Part 60, Subpart III	§ 60.4200(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 60, Subpart III	The permit holder shall comply with the applicable requirements of 40 CFR Part 60, Subpart III	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 60, Subpart III	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 60, Subpart III	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 60, Subpart III

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-ENGEMERG	EU	63ZZZZ-1	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(c)	A new/reconstructed stationary RICE located at an area source, or located at a major source of HAP emissions and is a spark ignition (SI) 2SLB < 500 HP, SI 4 SLB < 250 HP, or 4SRB, compression ignition (CI), emergency or limited use, or which combusts landfill or digester gas at > 10% of the gross heat input < 500 HP must meet the requirements of this part by meeting the requirements of 40 CFR Part 60, Subpart IIII, for CI engines or 40 CFR Part 60, Subpart JJJJ, for SI engines.	None	None	None
22FB748	EU	R5112-2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
22FB749	EU	R5112-2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
42FB2802	EU	R5117-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
42FB2802	EU	63CC-1	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
45FB6001	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
45FB6002	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
45FB6360	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
45FB7401	EU	R5112-3	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(3) § 115.112(e)(3)(A) § 115.112(e)(3)(A)(i)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.115(a) § 115.115(a)(1) § 115.116(a)(1) [G]§ 115.117	§ 115.118(a)(4) § 115.118(a)(4)(A) § 115.118(a)(5) § 115.118(a)(7)	None
45FB7401	EU	60K-3	VOC	40 CFR Part 60, Subpart K	§ 60.112(a)(1)	Storage vessels holding petroleum liquids with a true vapor pressure of 78 mm Hg (1.5 psia) or greater but not greater than 570 mm Hg (11.1 psia) shall have a floating roof, a vapor recovery system, or their equivalents.	§ 60.113(a) § 60.113(b) ** See Periodic Monitoring Summary	§ 60.113(a)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
45FB7402	EU	R5112-3	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(3) § 115.112(e)(3)(A) § 115.112(e)(3)(A)(i)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.115(a) § 115.115(a)(1) § 115.116(a)(1) [G]§ 115.117	§ 115.118(a)(4) § 115.118(a)(4)(A) § 115.118(a)(5) § 115.118(a)(7)	None
45FB7402	EU	60Kb-3	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(3)	Storage vessels specified in §60.112b(a) and equipped with a closed vent system/control device are to meet the specifications of §60.112b(a)(3)(i)-(ii).	[G]§ 60.113b(c)(1) § 60.113b(c)(2) § 60.116b(a) § 60.116b(b) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3) [G]§ 60.485(b) ** See Periodic Monitoring Summary	§ 60.115b [G]§ 60.115b(c) § 60.116b(a) § 60.116b(b)	[G]§ 60.113b(c)(1) § 60.115b

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
45FB7403	EU	R5112-3	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(3) § 115.112(e)(3)(A) § 115.112(e)(3)(A)(i)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.115(a) § 115.115(a)(1) § 115.116(a)(1) [G]§ 115.117	§ 115.118(a)(4) § 115.118(a)(4)(A) § 115.118(a)(5) § 115.118(a)(7)	None
45FB7403	EU	60Kb-3	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(3)	Storage vessels specified in §60.112b(a) and equipped with a closed vent system/control device are to meet the specifications of §60.112b(a)(3)(i)-(ii).	[G]§ 60.113b(c)(1) § 60.113b(c)(2) § 60.116b(a) § 60.116b(b) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3) [G]§ 60.485(b) ** See Periodic Monitoring Summary	§ 60.115b [G]§ 60.115b(c) § 60.116b(a) § 60.116b(b)	[G]§ 60.113b(c)(1) § 60.115b
46FB6301	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
47FA2	EU	R5117-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
47FB321	EU	R5112-8	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	[G]§ 115.117 ** See Periodic Monitoring Summary	§ 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
47FB321	EU	60Kb-9	VOC	40 CFR Part 60, Subpart Kb	§ 60.110b(a)	Except for §60.110b(b), this subpart applies to vessels with a capacity greater than or equal to 75 cubic meters (19,800 gal) used to store VOLs for which construction/reconstruction/modification began after 7/23/84.	§ 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(d) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.116b(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
47FB321	EU	60QQQ-1	VOC	40 CFR Part 60, Subpart QQQ	§ 60.692-3(a) § 60.692-1(a) § 60.692-3(a)(1) § 60.692-3(a)(2) § 60.692-3(a)(3) § 60.692-3(a)(5) § 60.692-3(e) § 60.692-3(f) § 60.692-6(a) § 60.692-6(b) § 60.692-7(b)	Except as noted, each oil-water separator tank, slop oil tank, storage vessel, or other auxiliary equipment shall be equipped with fixed roof, meeting following specifications:	§ 60.692-3(a)(4) § 60.696(a)	§ 60.697(a) § 60.697(c) [G]§ 60.697(e) § 60.697(f)(1) [G]§ 60.697(f)(2)	§ 60.698(b)(1) § 60.698(e)
47FB323	EU	R5112-8	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	[G]§ 115.117 ** See Periodic Monitoring Summary	§ 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
47FB323	EU	60Kb-9	VOC	40 CFR Part 60, Subpart Kb	§ 60.110b(a)	Except for §60.110b(b), this subpart applies to vessels with a capacity greater than or equal to 75 cubic meters (19,800 gal) used to store VOLs for which construction/reconstruction/modification began after 7/23/84.	§ 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(d) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.116b(d)
47FB323	EU	60QQQ-1	VOC	40 CFR Part 60, Subpart QQQ	§ 60.692-3(a) § 60.692-1(a) § 60.692-3(a)(1) § 60.692-3(a)(2) § 60.692-3(a)(3) § 60.692-3(a)(5) § 60.692-3(e) § 60.692-3(f) § 60.692-6(a) § 60.692-6(b) § 60.692-7(b)	Except as noted, each oil-water separator tank, slop oil tank, storage vessel, or other auxiliary equipment shall be equipped with fixed roof, meeting following specifications:	§ 60.692-3(a)(4) § 60.696(a)	§ 60.697(a) § 60.697(c) [G]§ 60.697(e) § 60.697(f)(1) [G]§ 60.697(f)(2)	§ 60.698(b)(1) § 60.698(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
47FB503	EU	R5112-2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)
47FB503	EU	60Kb-1	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
47FB504	EU	R5112-2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)
47FB504	EU	60Kb-1	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
47FB509	EU	R5112-2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)
90FB001	EU	R5112-5	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(d)(1) § 115.112(d)(2) § 115.112(d)(2)(A) § 115.112(d)(2)(B) § 115.112(d)(2)(C) § 115.112(d)(2)(D) § 115.112(d)(2)(E)	No person shall place, store, or hold in any stationary tank, reservoir, or other container any VOC unless such container is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere, or is equipped with at least the control device specified in either Table I(a) of subsection (a)(1) of this section for VOC other than crude oil and condensate, or Table II(a) of subsection (a)(1) of this section for crude oil and condensate.	§ 115.114(a)(1) [G]§ 115.115(a) § 115.116(a)(4) § 115.116(a)(5)	§ 115.116(a)(2) § 115.116(a)(4) § 115.116(a)(5)	§ 115.114(a)(1)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
90FB001	EU	60Kb-6	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)
90FB001	EU	63CC-2	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) § 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) § 63.640(n)(8)(ii)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
90FB002	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(d)(1) § 115.112(d)(2) § 115.112(d)(2)(A) § 115.112(d)(2)(B) § 115.112(d)(2)(C) § 115.112(d)(2)(D) § 115.112(d)(2)(E) § 115.112(d)(2)(F) [G]§ 115.112(d)(2)(G) [G]§ 115.112(d)(2)(H)	No person shall place, store, or hold in any stationary tank, reservoir, or other container any VOC unless such container is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere, or is equipped with at least the control device specified in either Table I(a) of subsection (a)(1) of this section for VOC other than crude oil and condensate, or Table II(a) of subsection (a)(1) of this section for crude oil and condensate.	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) [G]§ 115.115(a) § 115.116(a)(2) § 115.116(a)(2)(A) § 115.116(a)(2)(B) § 115.116(a)(2)(C) § 115.116(a)(2)(D) § 115.116(a)(2)(E) § 115.116(a)(2)(F) § 115.116(a)(2)(G) § 115.116(a)(2)(H) § 115.116(a)(2)(I) § 115.116(a)(2)(J) § 115.116(a)(4) § 115.116(a)(5)	§ 115.116(a)(2) § 115.116(a)(4) § 115.116(a)(5)	§ 115.114(a)(2) § 115.114(a)(4) § 115.116(a)(2) § 115.116(a)(2)(C) § 115.116(a)(2)(D) § 115.116(a)(2)(F) § 115.116(a)(2)(G) § 115.116(a)(2)(J)
90FB002	EU	60Kb-4	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(f)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
90FB002	EU	63CC-1	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) [G]§ 60.112b(a)(2) § 63.640(n)(8)(i) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) [G]§ 63.120(b)(7) § 63.640(n)(8)(ii)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 63.640(n)(8)(vi)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)
90FB004	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(d)(1) § 115.112(d)(2) § 115.112(d)(2)(A) § 115.112(d)(2)(B) § 115.112(d)(2)(C) § 115.112(d)(2)(D) § 115.112(d)(2)(E) § 115.112(d)(2)(F) [G]§ 115.112(d)(2)(G) [G]§ 115.112(d)(2)(H)	No person shall place, store, or hold in any stationary tank, reservoir, or other container any VOC unless such container is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere, or is equipped with at least the control device specified in either Table I(a) of subsection (a)(1) of this section for VOC other than crude oil and condensate, or Table II(a) of subsection (a)(1) of this section for crude oil and condensate.	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) [G]§ 115.115(a) § 115.116(a)(2) § 115.116(a)(2)(A) § 115.116(a)(2)(B) § 115.116(a)(2)(C) § 115.116(a)(2)(D) § 115.116(a)(2)(E) § 115.116(a)(2)(F) § 115.116(a)(2)(G) § 115.116(a)(2)(H) § 115.116(a)(2)(I) § 115.116(a)(2)(J) § 115.116(a)(4) § 115.116(a)(5)	§ 115.116(a)(2) § 115.116(a)(4) § 115.116(a)(5)	§ 115.114(a)(2) § 115.114(a)(4) § 115.116(a)(2) § 115.116(a)(2)(C) § 115.116(a)(2)(D) § 115.116(a)(2)(F) § 115.116(a)(2)(G) § 115.116(a)(2)(J)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
90FB004	EU	60Kb-4	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)
90FB004	EU	63CC-1	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) [G]§ 60.112b(a)(2) § 63.640(n)(8)(i) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) [G]§ 63.120(b)(7) § 63.640(n)(8)(ii)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 63.640(n)(8)(vi)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
90FB005	EU	R5112-2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(2) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)
90FB005	EU	63CC-1	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.119(a)(1) § 63.119(c)(1) § 63.119(c)(1)(i) § 63.119(c)(1)(ii) § 63.119(c)(1)(iii) [G]§ 63.119(c)(3) § 63.119(c)(4) § 63.120(b)(10)(i) § 63.120(b)(5)(i) § 63.120(b)(5)(ii) § 63.120(b)(6)(i) § 63.120(b)(6)(ii) [G]§ 63.120(b)(7) § 63.120(b)(8) [G]§ 63.646(f) § 63.646(g)	Each owner or operator of a Group 1 storage vessel subject to this subpart shall comply with the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.120(b)(1)(i) § 63.120(b)(1)(iii) § 63.120(b)(1)(iv) § 63.120(b)(10) § 63.120(b)(2)(i) § 63.120(b)(2)(ii) § 63.120(b)(2)(iii) § 63.120(b)(3) § 63.120(b)(4) § 63.646(b)(1) § 63.646(e)	[G]§ 63.120(b)(7) § 63.120(b)(8) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1) § 63.655(i)(5)	§ 63.120(b)(10)(ii) § 63.120(b)(10)(iii) § 63.120(b)(9) § 63.642(f) § 63.655(f) [G]§ 63.655(f)(1)(i)(B) § 63.655(f)(6) § 63.655(g) [G]§ 63.655(g)(3) § 63.655(h) § 63.655(h)(1) § 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(B) § 63.655(h)(2)(i)(C) § 63.655(h)(2)(ii) [G]§ 63.655(h)(6)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
90FB205	EU	R5112-6	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(d)(1) § 115.112(d)(2) § 115.112(d)(2)(A) § 115.112(d)(2)(B) § 115.112(d)(2)(C) § 115.112(d)(2)(D) § 115.112(d)(2)(E) [G]§ 115.112(d)(2)(H)	No person shall place, store, or hold in any stationary tank, reservoir, or other container any VOC unless such container is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere, or is equipped with at least the control device specified in either Table I(a) of subsection (a)(1) of this section for VOC other than crude oil and condensate, or Table II(a) of subsection (a)(1) of this section for crude oil and condensate.	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) [G]§ 115.115(a) § 115.116(a)(2) § 115.116(a)(2)(A) § 115.116(a)(2)(B) § 115.116(a)(2)(C) § 115.116(a)(2)(D) § 115.116(a)(2)(E) § 115.116(a)(2)(F) § 115.116(a)(2)(G) § 115.116(a)(2)(H) § 115.116(a)(2)(I) § 115.116(a)(2)(J) § 115.116(a)(4) § 115.116(a)(5)	§ 115.116(a)(2) § 115.116(a)(4) § 115.116(a)(5)	§ 115.114(a)(2) § 115.114(a)(4) § 115.116(a)(2) § 115.116(a)(2)(C) § 115.116(a)(2)(D) § 115.116(a)(2)(F) § 115.116(a)(2)(G) § 115.116(a)(2)(J)
90FB205	EU	60Kb-7	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(f)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
90FB205	EU	63CC-3	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) [G]§ 60.112b(a)(2) § 63.640(n)(8)(i) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) [G]§ 63.120(b)(7) § 63.640(n)(8)(ii)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 63.640(n)(8)(vi)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)
90FB210	EU	R5112-002	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(d)(1) § 115.112(d)(2) § 115.112(d)(2)(A) § 115.112(d)(2)(B) § 115.112(d)(2)(C) § 115.112(d)(2)(D) § 115.112(d)(2)(E) [G]§ 115.112(d)(2)(H)	No person shall place, store, or hold in any stationary tank, reservoir, or other container any VOC unless such container is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere, or is equipped with at least the control device specified in either Table I(a) of subsection (a)(1) of this section for VOC other than crude oil and condensate, or Table II(a) of subsection (a)(1) of this section for crude oil and condensate.	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) [G]§ 115.115(a) § 115.116(a)(2) § 115.116(a)(2)(A) § 115.116(a)(2)(B) § 115.116(a)(2)(C) § 115.116(a)(2)(D) § 115.116(a)(2)(E) § 115.116(a)(2)(F) § 115.116(a)(2)(G) § 115.116(a)(2)(H) § 115.116(a)(2)(I) § 115.116(a)(2)(J) § 115.116(a)(4) § 115.116(a)(5)	§ 115.116(a)(2) § 115.116(a)(4) § 115.116(a)(5)	§ 115.114(a)(2) § 115.114(a)(4) § 115.116(a)(2) § 115.116(a)(2)(C) § 115.116(a)(2)(D) § 115.116(a)(2)(F) § 115.116(a)(2)(G) § 115.116(a)(2)(J)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
90FB210	EU	60Kb-002	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)
90FB210	EU	63CC-001	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) [G]§ 60.112b(a)(2) § 63.640(n)(8)(i) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) [G]§ 63.120(b)(7) § 63.640(n)(8)(ii)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 63.640(n)(8)(vi)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
90FB223	EU	R5112-2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
90FB223	EU	63CC-5	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
90FB229	EU	R5112-2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
90FB229	EU	63CC-5	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
90FB230	EU	R5112-2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)
90FB230	EU	60Kb-1	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
90FB230	EU	63CC-1	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) [G]§ 60.112b(a)(2) § 63.640(n)(8)(i) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) [G]§ 63.120(b)(7) § 63.640(n)(8)(ii)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 63.640(n)(8)(vi)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)
90FB231	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
90FB231	EU	63CC-2	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
90FB234	EU	R5115-001	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.117(a)(1)	Except as provided in §115.116 of this title (relating to Monitoring and Recordkeeping Requirements), any volatile organic compound (VOC) with a true vapor pressure less than 1.5 pounds per square inch absolute (psia) (10.3 kPa) at storage conditions is exempt from the requirements of this division (relating to the Storage of Volatile Organic Compounds).	§ 115.116(a)(5)	§ 115.116(a)(5) § 115.116(c)(1)	None
90FB234	EU	60KB-001	VOC	40 CFR Part 60, Subpart Kb	§ 60.110b(a)	Except for §60.110b(b), this subpart applies to vessels with a capacity greater than or equal to 75 cubic meters (19,800 gal) used to store VOLs for which construction/reconstruction/modification began after 7/23/84.	§ 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(d) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.116b(d)
90FB234	EU	63CC-002	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.654(g)(7)(ii) § 63.654(i)(1)(iv) § 63.654(i)(4)	§ 63.654(f) § 63.654(f)(1)(i)(A) § 63.654(g) § 63.654(g)(7) § 63.654(g)(7)(i) § 63.654(h) § 63.654(h)(6) § 63.654(h)(6)(ii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
90FB511	EU	R5115-002	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(d)(1) § 115.112(d)(2) § 115.112(d)(2)(A) § 115.112(d)(2)(B) § 115.112(d)(2)(C) § 115.112(d)(2)(D) § 115.112(d)(2)(E) [G]§ 115.112(d)(2)(H)	No person shall place, store, or hold in any stationary tank, reservoir, or other container any VOC unless such container is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere, or is equipped with at least the control device specified in either Table I(a) of subsection (a)(1) of this section for VOC other than crude oil and condensate, or Table II(a) of subsection (a)(1) of this section for crude oil and condensate.	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) [G]§ 115.115(a) § 115.116(a)(2) § 115.116(a)(2)(A) § 115.116(a)(2)(B) § 115.116(a)(2)(C) § 115.116(a)(2)(D) § 115.116(a)(2)(E) § 115.116(a)(2)(F) § 115.116(a)(2)(G) § 115.116(a)(2)(H) § 115.116(a)(2)(I) § 115.116(a)(2)(J) § 115.116(a)(4) § 115.116(a)(5)	§ 115.116(a)(2) § 115.116(a)(4) § 115.116(a)(5)	§ 115.114(a)(2) § 115.114(a)(4) § 115.116(a)(2) § 115.116(a)(2)(C) § 115.116(a)(2)(D) § 115.116(a)(2)(F) § 115.116(a)(2)(G) § 115.116(a)(2)(J)
90FB511	EU	60KB-002	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(f)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
90FB511	EU	63CC-001	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) [G]§ 60.112b(a)(2) § 63.640(n)(8)(i) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) [G]§ 63.120(b)(7) § 63.640(n)(8)(ii)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 63.640(n)(8)(vi)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)
90FB735	EU	R5112-2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(D) § 115.112(e)(2)(F) [G]§ 115.112(e)(2)(I) § 115.114(a)(1)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(1)(B) § 115.118(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
90FB735	EU	60Kb-1	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)
90FB807	EU	R5112-2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.117(a)(1)	Except as provided in §115.116 of this title (relating to Monitoring and Recordkeeping Requirements), any volatile organic compound (VOC) with a true vapor pressure less than 1.5 pounds per square inch absolute (psia) (10.3 kPa) at storage conditions is exempt from the requirements of this division (relating to the Storage of Volatile Organic Compounds).	§ 115.116(a)(5)	§ 115.116(a)(5) § 115.116(c)(1)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
91FB901	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(d)(1) § 115.112(d)(2) § 115.112(d)(2)(A) § 115.112(d)(2)(B) § 115.112(d)(2)(C) § 115.112(d)(2)(D) § 115.112(d)(2)(E) § 115.112(d)(2)(F) [G]§ 115.112(d)(2)(G) [G]§ 115.112(d)(2)(H)	No person shall place, store, or hold in any stationary tank, reservoir, or other container any VOC unless such container is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere, or is equipped with at least the control device specified in either Table I(a) of subsection (a)(1) of this section for VOC other than crude oil and condensate, or Table II(a) of subsection (a)(1) of this section for crude oil and condensate.	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) [G]§ 115.115(a) § 115.116(a)(2) § 115.116(a)(2)(A) § 115.116(a)(2)(B) § 115.116(a)(2)(C) § 115.116(a)(2)(D) § 115.116(a)(2)(E) § 115.116(a)(2)(F) § 115.116(a)(2)(G) § 115.116(a)(2)(H) § 115.116(a)(2)(I) § 115.116(a)(2)(J) § 115.116(a)(4) § 115.116(a)(5)	§ 115.116(a)(2) § 115.116(a)(4) § 115.116(a)(5)	§ 115.114(a)(2) § 115.114(a)(4) § 115.116(a)(2) § 115.116(a)(2)(C) § 115.116(a)(2)(D) § 115.116(a)(2)(F) § 115.116(a)(2)(G) § 115.116(a)(2)(J)
91FB901	EU	60Kb-4	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(f)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
91FB901	EU	63CC-1	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) [G]§ 60.112b(a)(2) § 63.640(n)(8)(i) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) [G]§ 63.120(b)(7) § 63.640(n)(8)(ii)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 63.640(n)(8)(vi)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)
91FB907	EU	R5117-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
91FB907	EU	63CC-2	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
91FB912	EU	R5112-7	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.117(a)(1)	Except as provided in §115.116 of this title (relating to Monitoring and Recordkeeping Requirements), any volatile organic compound (VOC) with a true vapor pressure less than 1.5 pounds per square inch absolute (psia) (10.3 kPa) at storage conditions is exempt from the requirements of this division (relating to the Storage of Volatile Organic Compounds).	§ 115.116(a)(5)	§ 115.116(a)(5) § 115.116(c)(1)	None
91FB912	EU	60Kb-8	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
91FB912	EU	63CC-4	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) § 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) § 63.640(n)(8)(ii)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)
91FB913	EU	R5112-7	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.117(a)(1)	Except as provided in §115.116 of this title (relating to Monitoring and Recordkeeping Requirements), any volatile organic compound (VOC) with a true vapor pressure less than 1.5 pounds per square inch absolute (psia) (10.3 kPa) at storage conditions is exempt from the requirements of this division (relating to the Storage of Volatile Organic Compounds).	§ 115.116(a)(5)	§ 115.116(a)(5) § 115.116(c)(1)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
91FB913	EU	60Kb-8	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(d) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)
91FB913	EU	63CC-4	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) § 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) § 63.640(n)(8)(ii)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
91FB917	EU	R5112-2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(D) § 115.112(e)(2)(F) [G]§ 115.112(e)(2)(I) § 115.114(a)(1)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(1)(B) § 115.118(a)(3)
91FB917	EU	60Kb-1	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
91FB917	EU	63CC-1	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) § 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) § 63.640(n)(8)(ii)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)
91FB918	EU	R5112-2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(D) § 115.112(e)(2)(F) [G]§ 115.112(e)(2)(I) § 115.114(a)(1)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(1)(B) § 115.118(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
91FB918	EU	60Kb-1	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(B) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) [G]§ 60.113b(a)(3) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(4)
91FB918	EU	63CC-1	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) § 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(B) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii) § 63.640(n)(8)(ii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	§ 60.113b(a)(1) [G]§ 60.113b(a)(3) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(c) § 60.116b(e)(1) [G]§ 60.116b(e)(3) § 63.640(n)(8)(ii)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
91FB920	EU	R5112-2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(D) § 115.112(e)(2)(F) [G]§ 115.112(e)(2)(I) § 115.114(a)(1)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(1)(B) § 115.118(a)(3)
91FB920	EU	60Kb-1	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(B) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) [G]§ 60.113b(a)(3) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
91FB920	EU	63CC-1	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) § 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(B) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii) § 63.640(n)(8)(ii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	§ 60.113b(a)(1) [G]§ 60.113b(a)(3) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) [G]§ 60.116b(e)(3) § 63.640(n)(8)(ii)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(4)
91FB921	EU	R5112-2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(D) § 115.112(e)(2)(F) [G]§ 115.112(e)(2)(I) § 115.114(a)(1)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(1)(B) § 115.118(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
91FB921	EU	60Kb-1	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(B) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) [G]§ 60.113b(a)(3) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(4)
91FB921	EU	63CC-1	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) § 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(B) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii) § 63.640(n)(8)(ii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	§ 60.113b(a)(1) [G]§ 60.113b(a)(3) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(c) § 60.116b(e)(1) [G]§ 60.116b(e)(3) § 63.640(n)(8)(ii)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
91FB922	EU	R5112-2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(D) § 115.112(e)(2)(F) [G]§ 115.112(e)(2)(I) § 115.114(a)(1)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(1)(B) § 115.118(a)(3)
91FB922	EU	60Kb-1	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(B) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) [G]§ 60.113b(a)(3) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
91FB922	EU	63CC-1	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) § 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(B) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii) § 63.640(n)(8)(ii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	§ 60.113b(a)(1) [G]§ 60.113b(a)(3) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) § 63.640(n)(8)(ii)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(4)
91FB924	EU	R5112-2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(D) § 115.112(e)(2)(F) [G]§ 115.112(e)(2)(I) § 115.114(a)(1)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(1)(B) § 115.118(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
91FB924	EU	60Kb-1	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)
91FB924	EU	63CC-1	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) § 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) § 63.640(n)(8)(ii)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)
91FB927	EU	R5117-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
91FB927	EU	63CC-1	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
91FB931	EU	R5112-2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
91FB931	EU	60Kb-1	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)
91FB931	EU	63CC-1	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) [G]§ 60.112b(a)(2) § 63.640(n)(8)(i) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) [G]§ 60.116b(e)(3) [G]§ 63.120(b)(7) § 63.640(n)(8)(ii)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 63.640(n)(8)(vi)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
92FA4001	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
92FA4002	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	[G]§ 115.117 ** See Periodic Monitoring Summary	§ 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-TK1	EU	R5112-2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(D) § 115.112(e)(2)(F) [G]§ 115.112(e)(2)(I) § 115.114(a)(1)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(1)(B) § 115.118(a)(3)
GRP-TK1	EU	60Kb-1	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-TK10	EU	R5112-2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(D) § 115.112(e)(2)(F) [G]§ 115.112(e)(2)(I) § 115.114(a)(1)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(1)(B) § 115.118(a)(3)
GRP-TK10	EU	63CC-1	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.119(a)(1) [G]§ 63.119(b)(1) § 63.119(b)(2) § 63.119(b)(3)(ii) § 63.119(b)(4) § 63.120(a)(4) § 63.120(a)(7) [G]§ 63.646(f) § 63.646(g)	Each owner or operator of a Group 1 storage vessel subject to this subpart shall comply with the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.120(a)(2)(i) § 63.120(a)(2)(ii) § 63.646(b)(1) § 63.646(e)	§ 63.120(a)(4) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1) § 63.655(i)(5)	§ 63.120(a)(5) § 63.120(a)(6) § 63.642(f) § 63.655(f) [G]§ 63.655(f)(1)(i)(B) § 63.655(f)(6) § 63.655(g) § 63.655(g)(2) [G]§ 63.655(g)(2)(i) [G]§ 63.655(g)(2)(ii) § 63.655(h) § 63.655(h)(1) § 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(B) § 63.655(h)(2)(i)(C) [G]§ 63.655(h)(6)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-TK12	EU	R5117-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
GRP-TK12	EU	63CC-1	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
GRP-TK2	EU	R5117-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
GRP-TK2	EU	63CC-5	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-TK6	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
GRP-TK7	EU	R5112-2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-TK7	EU	63CC-1	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.119(a)(1) § 63.119(c)(1) § 63.119(c)(1)(i) § 63.119(c)(1)(ii) § 63.119(c)(1)(iii) [G]§ 63.119(c)(3) § 63.119(c)(4) § 63.120(b)(10)(i) § 63.120(b)(5)(i) § 63.120(b)(5)(ii) § 63.120(b)(6)(i) § 63.120(b)(6)(ii) [G]§ 63.120(b)(7) § 63.120(b)(8) [G]§ 63.646(f) § 63.646(g)	Each owner or operator of a Group 1 storage vessel subject to this subpart shall comply with the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.120(b)(1)(i) § 63.120(b)(1)(iii) § 63.120(b)(1)(iv) § 63.120(b)(10) § 63.120(b)(2)(i) § 63.120(b)(2)(ii) § 63.120(b)(2)(iii) § 63.120(b)(3) § 63.120(b)(4) § 63.646(b)(1) § 63.646(e)	[G]§ 63.120(b)(7) § 63.120(b)(8) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1) § 63.655(i)(5)	§ 63.120(b)(10)(ii) § 63.120(b)(10)(iii) § 63.120(b)(9) § 63.642(f) § 63.655(f) [G]§ 63.655(f)(1)(i)(B) § 63.655(f)(6) § 63.655(g) [G]§ 63.655(g)(3) § 63.655(h) § 63.655(h)(1) § 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(B) § 63.655(h)(2)(i)(C) § 63.655(h)(2)(ii) [G]§ 63.655(h)(6)
GRP-TK8	EU	R5112-2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-TK8	EU	63CC-1	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.119(a)(1) § 63.119(c)(1) § 63.119(c)(1)(i) § 63.119(c)(1)(ii) § 63.119(c)(1)(iii) [G]§ 63.119(c)(3) § 63.119(c)(4) § 63.120(b)(10)(i) § 63.120(b)(5)(i) § 63.120(b)(5)(ii) § 63.120(b)(6)(i) § 63.120(b)(6)(ii) [G]§ 63.120(b)(7) § 63.120(b)(8) [G]§ 63.646(f) § 63.646(g)	Each owner or operator of a Group 1 storage vessel subject to this subpart shall comply with the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.120(b)(1)(i) § 63.120(b)(1)(iii) § 63.120(b)(1)(iv) § 63.120(b)(10) § 63.120(b)(2)(i) § 63.120(b)(2)(ii) § 63.120(b)(2)(iii) § 63.120(b)(3) § 63.120(b)(4) § 63.646(b)(1) § 63.646(e)	[G]§ 63.120(b)(7) § 63.120(b)(8) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1) § 63.655(i)(5)	§ 63.120(b)(10)(ii) § 63.120(b)(10)(iii) § 63.120(b)(9) § 63.642(f) § 63.655(f) [G]§ 63.655(f)(1)(i)(B) § 63.655(f)(6) § 63.655(g) [G]§ 63.655(g)(3) § 63.655(h) § 63.655(h)(1) § 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(B) § 63.655(h)(2)(i)(C) § 63.655(h)(2)(ii) [G]§ 63.655(h)(6)
5GTRANSFER	EU	63GGGGG-1	112(B) HAPS	40 CFR Part 63, Subpart GGGGG	§ 63.7886(b)(1)(v) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart GGGGG	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart GGGGG	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart GGGGG	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart GGGGG	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart GGGGG
EJECTORS	EU	R5311	VOC	30 TAC Chapter 115, Unit Turn & Vac System-Pet Ref	§ 115.311(a)(1) § 115.312(a)(2) § 115.312(a)(2)(B)	No emission of VOC from steam ejector or mechanical vacuum pump in a petroleum refinery unless vent stream is burned in accordance with §115.312(a) of this title.	[G]§ 115.315(a) ** See Periodic Monitoring Summary	§ 115.316(a)(3) § 115.316(a)(4)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
47FB503	EU	R5132-1	VOC	30 TAC Chapter 115, Water Separation	§ 115.132(a)(2)	VOC water separator compartments must have a floating roof or internal-floating cover resting on the surface with closure seals. Gauging and sampling devices shall be vapor-tight except during use.	[G]§ 115.135(a) § 115.136(a)(3) § 115.136(a)(4) ** See Periodic Monitoring Summary	§ 115.136(a)(3) § 115.136(a)(4)	None
47FB504	EU	R5132-1	VOC	30 TAC Chapter 115, Water Separation	§ 115.132(a)(2)	VOC water separator compartments must have a floating roof or internal-floating cover resting on the surface with closure seals. Gauging and sampling devices shall be vapor-tight except during use.	[G]§ 115.135(a) § 115.136(a)(3) § 115.136(a)(4) ** See Periodic Monitoring Summary	§ 115.136(a)(3) § 115.136(a)(4)	None
47FB509	EU	R5132-1	VOC	30 TAC Chapter 115, Water Separation	§ 115.132(a)(2)	VOC water separator compartments must have a floating roof or internal-floating cover resting on the surface with closure seals. Gauging and sampling devices shall be vapor-tight except during use.	[G]§ 115.135(a) § 115.136(a)(3) § 115.136(a)(4) ** See Periodic Monitoring Summary	§ 115.136(a)(3) § 115.136(a)(4)	None
47GF5401	EU	R5132-1	VOC	30 TAC Chapter 115, Water Separation	§ 115.132(a)(2)	VOC water separator compartments must have a floating roof or internal-floating cover resting on the surface with closure seals. Gauging and sampling devices shall be vapor-tight except during use.	[G]§ 115.135(a) § 115.136(a)(3) § 115.136(a)(4) ** See Periodic Monitoring Summary	§ 115.136(a)(3) § 115.136(a)(4)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
47GF5401	EU	60QQQ-1	VOC	40 CFR Part 60, Subpart QQQ	§ 60.693-2(a) § 60.692-1(a) § 60.692-6(a) § 60.692-6(b) § 60.692-7(b) § 60.693-2(a)(1) § 60.693-2(a)(1)(i) § 60.693-2(a)(1)(i)(B) § 60.693-2(a)(1)(i)(C) [G]§ 60.693-2(a)(1)(ii) § 60.693-2(a)(1)(iii) § 60.693-2(a)(1)(iv) § 60.693-2(a)(2) § 60.693-2(a)(3) § 60.693-2(a)(4) § 60.693-2(a)(5)(ii) § 60.693-2(c)	May elect to install a floating roof on an oil-water separator tank, slop oil tank or other auxiliary equipment subject to this subpart which meets the following specifications:	§ 60.693-2(a)(1)(iii)(A) § 60.693-2(a)(1)(iii)(B) § 60.693-2(a)(5)(i) § 60.696(a) [G]§ 60.696(d)	§ 60.697(a) § 60.697(c) [G]§ 60.697(e) § 60.697(f)(1) [G]§ 60.697(f)(2) [G]§ 60.697(k)	§ 60.693-2(b) § 60.698(a) § 60.698(b)(1) § 60.698(e)
5G-Coo1OWS	EU	63GGGGG-1	112(B) HAPS	40 CFR Part 63, Subpart GGGGG	§ 63.7886(b)(1)(iv) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart GGGGG	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart GGGGG	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart GGGGG	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart GGGGG	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart GGGGG

Additional Monitoring Requirements

Compliance Assurance Monitoring Summary251

Periodic Monitoring Summary..... 257

CAM Summary

Unit/Group/Process Information	
ID No.: 39RX2001	
Control Device ID Nos.: 46CB6301, 39CB2001	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 112, Sulfur Compounds	SOP Index Nos.: R2SRU-1B, R2SRU-1C
Pollutant: SO ₂	Main Standard: § 112.7(a)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: four times per hour	
Averaging Period: one hour	
Deviation Limit: The minimum combustion temperature is 1,200 degrees F (649 degrees C).	
<p>CAM Text: The monitoring device should be installed in the combustion chamber or immediately downstream of the combustion chamber. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following:</p> <ul style="list-style-type: none"> ± 2% of reading; or ± 2.5 degrees Celsius. 	

CAM Summary

Unit/Group/Process Information	
ID No.: 39RX2001	
Control Device ID No.: 46CB6301	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 112, Sulfur Compounds	SOP Index No.: R2SRU-1B
Pollutant: SO ₂	Main Standard: § 112.7(a)
Monitoring Information	
Indicator: SO ₂ Mass Emissions in Pounds per Hour	
Minimum Frequency: four times per hour	
Averaging Period: one hour	
Deviation Limit: The maximum SO ₂ mass emission rate is 852 lb/hr, as calculated per equation in §112.7(a).	
CAM Text: Use a continuous emission monitoring system (CEMS) to measure and record the mass emissions rate of sulfur dioxide expressed in pounds per hour in the exhaust stream of the control device. The CEMS shall be operated in accordance with the monitoring requirements of 40 CFR § 60.13 and the Performance Specifications of 40 CFR Part 60, Appendix B.	

CAM Summary

Unit/Group/Process Information	
ID No.: 39RX2001	
Control Device ID No.: 39CB2001	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 112, Sulfur Compounds	SOP Index No.: R2SRU-1C
Pollutant: SO ₂	Main Standard: § 112.7(a)
Monitoring Information	
Indicator: SO ₂ Mass Emissions in Pounds per Hour	
Minimum Frequency: four times per hour	
Averaging Period: one hour	
Deviation Limit: The maximum SO ₂ mass emission rate is 677 lb/hr, as calculated per equation in §112.7(a).	
CAM Text: Use a continuous emission monitoring system (CEMS) to measure and record the mass emissions rate of sulfur dioxide expressed in pounds per hour in the exhaust stream of the control device. The CEMS shall be operated in accordance with the monitoring requirements of 40 CFR § 60.13 and the Performance Specifications of 40 CFR Part 60, Appendix B.	

CAM Summary

Unit/Group/Process Information	
ID No.: 46RX6206	
Control Device ID Nos.: 46CB6301, 39CB2001	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 112, Sulfur Compounds	SOP Index Nos.: R2SRU-1B, R2SRU-1C
Pollutant: SO ₂	Main Standard: § 112.7(a)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: four times per hour	
Averaging Period: one hour	
Deviation Limit: The minimum combustion temperature is 1,200 degrees F (649 degrees C).	
<p>CAM Text: The monitoring device should be installed in the combustion chamber or immediately downstream of the combustion chamber. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following:</p> <ul style="list-style-type: none"> ± 2% of reading; or ± 2.5 degrees Celsius. 	

CAM Summary

Unit/Group/Process Information	
ID No.: 46RX6206	
Control Device ID No.: 46CB6301	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 112, Sulfur Compounds	SOP Index No.: R2SRU-1B
Pollutant: SO ₂	Main Standard: § 112.7(a)
Monitoring Information	
Indicator: SO ₂ Mass Emissions in Pounds per Hour	
Minimum Frequency: four times per hour	
Averaging Period: one hour	
Deviation Limit: The maximum SO ₂ mass emission rate is 852 lb/hr, as calculated per equation in §112.7(a).	
CAM Text: Use a continuous emission monitoring system (CEMS) to measure and record the mass emissions rate of sulfur dioxide expressed in pounds per hour in the exhaust stream of the control device. The CEMS shall be operated in accordance with the monitoring requirements of 40 CFR § 60.13 and the Performance Specifications of 40 CFR Part 60, Appendix B.	

CAM Summary

Unit/Group/Process Information	
ID No.: 46RX6206	
Control Device ID No.: 39CB2001	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 112, Sulfur Compounds	SOP Index No.: R2SRU-1C
Pollutant: SO ₂	Main Standard: § 112.7(a)
Monitoring Information	
Indicator: SO ₂ Mass Emissions in Pounds per Hour	
Minimum Frequency: four times per hour	
Averaging Period: one hour	
Deviation Limit: The maximum SO ₂ mass emission rate is 677 lb/hr, as calculated per equation in §112.7(a).	
CAM Text: Use a continuous emission monitoring system (CEMS) to measure and record the mass emissions rate of sulfur dioxide expressed in pounds per hour in the exhaust stream of the control device. The CEMS shall be operated in accordance with the monitoring requirements of 40 CFR § 60.13 and the Performance Specifications of 40 CFR Part 60, Appendix B.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: 42CB2201	
Control Device ID No.: 42CB2201	Control Device Type: Wet Scrubber
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-2
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(B)
Monitoring Information	
Indicator: Pressure Drop	
Minimum Frequency: once per week	
Averaging Period: n/a*	
Deviation Limit: 14.7 in H ₂ O	
<p>Periodic Monitoring Text: Measure and record the pressure drop. The monitoring instrumentation shall be calibrated, maintained and operated in accordance with manufacturer's specifications or other written procedures. Any monitoring data below the minimum limit shall be considered and reported as a deviation.</p>	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: 42CB2201	
Control Device ID No.: 42CB2201	Control Device Type: Wet Scrubber
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-2
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(B)
Monitoring Information	
Indicator: Liquid Supply Pressure	
Minimum Frequency: once per week	
Averaging Period: n/a*	
Deviation Limit: 53.2 psi (quench/spray tower) and 96.6 psi (filtering modules)	
<p>Periodic Monitoring Text: Measure and record the liquid supply pressure. The monitoring instrumentation shall be calibrated, maintained and operated in accordance with manufacturer's specifications or other written procedures. Any monitoring data below the minimum limit shall be considered and reported as a deviation.</p>	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: 45FB7401	
Control Device ID No.: 46CB6301	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart K	SOP Index No.: 60K-3
Pollutant: VOC	Main Standard: § 60.112(a)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: n/a*	
Deviation Limit: Any temperature less than 1070 F	
<p>Periodic Monitoring Text: Measure and record the combustion temperature in the combustion chamber or immediately downstream of the combustion chamber. The monitoring instrumentation shall be maintained, calibrated and operated in accordance with manufacturer's specifications or other written procedures. Any monitoring data below the minimum limit shall be considered and reported as a deviation.</p>	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: 45FB7402	
Control Device ID No.: 46CB6301	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart Kb	SOP Index No.: 60Kb-3
Pollutant: VOC	Main Standard: [G]§ 60.112b(a)(3)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: n/a*	
Deviation Limit: Any temperature less than 1070 F	
<p>Periodic Monitoring Text: Measure and record the combustion temperature in the combustion chamber or immediately downstream of the combustion chamber. The monitoring instrumentation shall be maintained, calibrated and operated in accordance with manufacturer's specifications or other written procedures. Any monitoring data below the minimum limit shall be considered and reported as a deviation.</p>	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: 45FB7403	
Control Device ID No.: 39CB2001	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart Kb	SOP Index No.: 60Kb-3
Pollutant: VOC	Main Standard: [G]§ 60.112b(a)(3)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: n/a*	
Deviation Limit: Any temperature less than 1070 F	
<p>Periodic Monitoring Text: Measure and record the combustion temperature in the combustion chamber or immediately downstream of the combustion chamber. The monitoring instrumentation shall be maintained, calibrated and operated in accordance with manufacturer's specifications or other written procedures. Any monitoring data below the minimum limit shall be considered and reported as a deviation.</p>	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Periodic Monitoring Summary

Unit/Group/Process Information	
ID Nos.: 47FB321, 47FB323, 92FA4002	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-8
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Structural Integrity of the Pipe	
Minimum Frequency: Emptied and degassed	
Averaging Period: n/a	
Deviation Limit: Non-repair of fill pipe which shows questionable structural integrity prior to refilling.	
<p>Periodic Monitoring Text: Inspect to determine the structural integrity of the fill pipe and record each time the storage vessel is emptied and degassed to ensure that it continues to meet the specifications in the above requirement. If the structural integrity of the fill pipe is in question, repairs shall be made before the storage vessel is refilled. It shall be considered and reported as a deviation if the repairs are not completed prior to refilling the storage vessel.</p>	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID Nos.: 47FB321, 47FB323, 92FA4002	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-8
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Record of Tank Construction Specifications	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: No record of tank construction specifications that show a fill pipe.	
<p>Periodic Monitoring Text: Keep a record of tank construction specifications (e.g. engineering drawings) that show a fill pipe that extends from the top of a tank to have a maximum clearance of six inches (15.2 centimeters) from the bottom or, when the tank is loaded from the side, a discharge opening entirely submerged when the pipe used to withdraw liquid from the tank can no longer withdraw liquid in normal operation.</p>	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID Nos.: 47FB503, 47FB504, 47FB509, 47GF5401	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Water Separation	SOP Index No.: R5132-1
Pollutant: VOC	Main Standard: § 115.132(a)(2)
Monitoring Information	
Indicator: External Floating Roof	
Minimum Frequency: annually	
Averaging Period: N/A	
Deviation Limit: Roof not floating on surface of VOC, liquid accumulation on roof, detached seals, or holes/tears in seals	
<p>Periodic Monitoring Text: Visually inspect and record the inspection of the external floating roof to ensure: the roof is floating on the surface of the VOC and not on the leg supports, liquid has not accumulated on the external floating roof, the seals are not detached, and there are no holes or tears in the seal fabric.</p> <p>If there is any monitoring data in which the roof is not floating on the surface of the VOC, if liquid has accumulated on the external floating roof, the seals are detached, or if there are holes or tears in the seal fabric, the owner or operator shall repair the items or remove the equipment from service within 45 days. If the equipment cannot be removed from service within 45 days, a 30-day extension may be requested from the Executive Director. Failure to repair the items or to remove the equipment from service within the specified time period shall be considered and reported as a deviation.</p>	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID Nos.: DG-AGIT, DG-AGIT2	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Degreasing Processes	SOP Index No.: R5412-1
Pollutant: VOC	Main Standard: § 115.412(1)
Monitoring Information	
Indicator: Visual Inspection	
Minimum Frequency: Monthly	
Averaging Period: n/a	
Deviation Limit: Monitoring results that indicate noncompliance with § 115.412(1)(A)-(F)	
<p>Periodic Monitoring Text: Inspect equipment and record data monthly to ensure compliance with any applicable requirements in § 115.412(1)(A)-(F). Any monitoring data which indicates that the cold cleaner is not in compliance with the applicable requirements of § 115.412(1)(A)-(F) shall be considered and reported as a deviation.</p>	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: EJECTORS	
Control Device ID Nos.: 30FL1, 30FL2, 30FL5	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Unit Turn & Vac System-Pet Ref	SOP Index No.: R5311
Pollutant: VOC	Main Standard: § 115.311(a)(1)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Once per hour	
Averaging Period: n/a	
Deviation Limit: Monitoring data that indicates the lack of a pilot flame	
<p>Periodic Monitoring Text: Measure and record the presence of the pilot flame or maintain records of alarm events and duration of alarm events. The presence of a flare pilot flame shall be monitored using a thermocouple or any other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. The monitoring instrumentation shall be maintained, calibrated and operated in accordance with manufacturer's specifications or other written procedures. Any monitoring data which indicates the lack of a pilot flame shall be considered and reported as a deviation.</p>	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: GRP-HEAT1	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-0
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(A)
Monitoring Information	
Indicator: Visible Emissions	
Minimum Frequency: once per calendar quarter	
Averaging Period: n/a	
Deviation Limit: 30% Opacity	
<p>Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor.</p> <p>If visible emissions are observed, the permit holder shall report a deviation. As an alternative, the permit holder may determine the opacity consistent with Test Method 9, as soon as practicable, but no later than 24 hours after observing visible emissions. If the result of the Test Method 9 is opacity above the opacity limit in the applicable requirement, the permit holder shall report a deviation.</p>	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID Nos.: GRP-HEATER, GRP-REG1VENT	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-1
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(B)
Monitoring Information	
Indicator: Visible Emissions	
Minimum Frequency: once per calendar quarter	
Averaging Period: n/a	
Deviation Limit: 20% Opacity	
<p>Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor.</p> <p>If visible emissions are observed, the permit holder shall report a deviation. As an alternative, the permit holder may determine the opacity consistent with Test Method 9, as soon as practicable, but no later than 24 hours after observing visible emissions. If the result of the Test Method 9 is opacity above the opacity limit in the applicable requirement, the permit holder shall report a deviation.</p>	

Permit Shield

Permit Shield 270

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
22AVENT	N/A	40 CFR Part 63, Subpart CC	Process vents do not contain greater than 20 ppmv organic HAP.
22CO517	N/A	40 CFR Part 60, Subpart GGG	The Alky Unit Kellogg Compressor was originally constructed prior to January 4, 1983. It is an affected facility constructed prior to the applicability date of NSPS GGG.
22CO517	N/A	40 CFR Part 63, Subpart CC	Does not meet the definition of a miscellaneous process vent because it is not periodically discharged during normal operation.
22FA225	N/A	40 CFR Part 63, Subpart CC	Process vents do not contain greater than 20 ppmv organic HAP.
22FB748	N/A	40 CFR Part 60, Subpart Kb	Vessel stores a VOL with a maximum true vapor pressure less than 0.5 psia.
22FB748	N/A	40 CFR Part 63, Subpart CC	NSPS Kb supercedes MACT CC for Group 1 and Group 2 tanks at existing units.
22FB749	N/A	30 TAC Chapter 115, Storage of VOCs	Tank does not store VOC.

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
22FB749	N/A	40 CFR Part 60, Subpart Kb	Tank does not store VOL.
22SKD4202	N/A	30 TAC Chapter 117, Subchapter B	Equipment is a thermal oxidizer (incinerator) rated at less than 40 MMBtu/hr.
23BA301	N/A	40 CFR Part 60, Subpart J	pre 6/11/73
23BC201	N/A	40 CFR Part 60, Subpart D	pre 8/17/71
23BC201	N/A	40 CFR Part 60, Subpart Db	Constructed prior to 6/19/84. The convection section of this furnace produces steam
23BC201	N/A	40 CFR Part 60, Subpart Dc	pre 6/9/89
23BC201	N/A	40 CFR Part 60, Subpart J	pre 6/11/73
30FL6	N/A	40 CFR Part 63, Subpart A	The flare is not required under 40 CFR 63, Subpart A.
30GG1822	N/A	40 CFR Part 60, Subpart J	Source does not burn fuel gas

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
30LOAD	N/A	30 TAC Chapter 115, Loading and Unloading of VOC	Refueling equipment is a motor vehicle dispensing facility as defined at 101.1(58).
30LOAD	N/A	40 CFR Part 60, Subpart XX	Refueling equipment does not deliver liquid product into gasoline tank trucks as defined by 60.501
30LOAD	N/A	40 CFR Part 61, Subpart BB	Refueling equipment does not load benzene.
30LOAD	N/A	40 CFR Part 63, Subpart CC	Refueling equipment is not a gasoline loading rack by definition.
30LOAD	N/A	40 CFR Part 63, Subpart F	Refueling equipment is not a “loading rack” associated with a chemical manufacturing process.
30LOAD	N/A	40 CFR Part 63, Subpart G	Subpart G is not applicable because Subpart F is not applicable.
30LOAD	N/A	40 CFR Part 63, Subpart R	Refueling equipment is not a gasoline distribution facility.
30LOAD	N/A	40 CFR Part 63, Subpart Y	Refueling equipment is not a marine tank vessel loading operation.
39FB1001	N/A	30 TAC Chapter 115, Storage of VOCs	Tank does not store VOC.

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
39FB1001	N/A	40 CFR Part 60, Subpart Kb	Tank does not store VOL.
40CWT11	N/A	40 CFR Part 63, Subpart Q	Chromium compounds are not used in the cooling tower.
42EG7901	N/A	30 TAC Chapter 115, Vent Gas Controls	The vent stream does not contain any VOC
42FA2099V	N/A	40 CFR Part 60, Subpart Kb	capacity < 10,600 gallons
42FA2099V	N/A	40 CFR Part 63, Subpart CC	Does not meet the definition of a storage vessel since the capacity is less than 40 cubic meters.
42FB2801	N/A	30 TAC Chapter 115, Storage of VOCs	Tank does not store VOC.
42FB2801	N/A	40 CFR Part 60, Subpart Kb	Tank does not store VOL.
42FB2802	N/A	40 CFR Part 60, Subpart K	capacity < 40,000 gallons
44BA3002	N/A	40 CFR Part 60, Subpart D	Unit is < 250MMBtu/hr.

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
44BA3002	N/A	40 CFR Part 60, Subpart Db	Not subject to NSPS Db since it was built prior to 6/19/84.
44CO1418	N/A	40 CFR Part 60, Subpart GGG	The ROSE Solvent Compressor was originally constructed in 1975 and was not modified as part of the ROSE Unit modification. Therefore, the compressor is not subject to NSPS GGG.
44FA3007	N/A	40 CFR Part 63, Subpart CC	Does not meet the definition of a miscellaneous process vent because the gas stream does not contain greater than 20 PPM organic HAPs by volume.
44FB3001	N/A	30 TAC Chapter 115, Storage of VOCs	Tank does not store VOC.
44FB3001	N/A	40 CFR Part 60, Subpart Kb	Tank does not store VOL.
44FUG	N/A	40 CFR Part 63, Subpart CC	Does not meet the definition of an equipment leak in organic HAP service because it does not contain greater than 5% total HAP by weight.
45FB6001	N/A	40 CFR Part 60, Subpart Kb	Tank capacity is less than 75 cubic meters (19,813 gallons).

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
45FB6002	N/A	40 CFR Part 60, Subpart Kb	Tank capacity is less than 75 cubic meters (19,813 gallons).
45FB6360	N/A	40 CFR Part 60, Subpart Kb	Tank capacity is less than 75 cubic meters (19,813 gallons).
45FB7401	N/A	40 CFR Part 60, Subpart QQQ	Tank is subject to 60.112 of NSPS K.
45FB7401	N/A	40 CFR Part 63, Subpart CC	Group 2 wastewater streams are not required to comply with the requirements of 61.340 through 61.355 from the definition of Group 2 wastewater stream in 63.641.
45FB7402	N/A	40 CFR Part 60, Subpart QQQ	Tank is subject to 60.112b of NSPS Kb.
45FB7402	N/A	40 CFR Part 63, Subpart CC	Group 2 wastewater streams are not required to comply with the requirements of 61.340 through 61.355 from the definition of Group 2 wastewater stream in 63.641.
46BC6325	N/A	30 TAC Chapter 117, Commercial	Excluded as a burner for an SRU.
46BC6325	N/A	40 CFR Part 60, Subpart J	Not a fuel gas combustion device.

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
46FB6301	N/A	40 CFR Part 60, Subpart Kb	Tank capacity is less than 75 cubic meters (19,813 gallons).
47AD5409	N/A	30 TAC Chapter 115, Water Separation	Does not meet the definition of a VOC water separator.
47FA2	N/A	40 CFR Part 60, Subpart Kb	Vessel stores a VOL with a maximum true vapor pressure less than 0.5 psia.
47FA2	N/A	40 CFR Part 60, Subpart QQQ	Storage vessels subject to any requirements under NSPS subpart K series are exempt from the requirements under NSPS subpart QQQ.
47FA2	N/A	40 CFR Part 63, Subpart CC	Group 2 wastewater streams are not required to comply with the requirements of 61.340 through 61.355 from the definition of Group 2 wastewater stream in 63.641.
47FB321	N/A	40 CFR Part 60, Subpart Ka	capacity < 40,000 gallons
47FB323	N/A	40 CFR Part 60, Subpart Kb	Tank capacity is less than 20,000 gallons.

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
47FB503	N/A	40 CFR Part 60, Subpart QQQ	Storage vessels subject to any requirements under NSPS subpart K series are exempt from the requirements under NSPS subpart QQQ.
47FB503	N/A	40 CFR Part 63, Subpart CC	Group 2 wastewater streams are not required to comply with the requirements of 61.340 through 61.355 from the definition of Group 2 wastewater stream in 63.641.
47FB504	N/A	40 CFR Part 60, Subpart QQQ	Storage vessels subject to any requirements under NSPS Subpart K series are exempt from the requirements under NSPS QQQ.
47FB504	N/A	40 CFR Part 63, Subpart CC	Group 2 wastewater streams are not required to comply with the requirements of 61.340 through 61.355 from the definition of Group 2 wastewater stream in 63.641.
47FB509	N/A	40 CFR Part 60, Subpart Ka	Does not store petroleum liquids. Stores wastewater.
47FB509	N/A	40 CFR Part 60, Subpart QQQ	There has been no construction, modification, or reconstruction after May 4, 1987.

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
47FB509	N/A	40 CFR Part 63, Subpart CC	Group 2 wastewater streams are not required to comply with the requirements of 61.340 through 61.355 from the definition of Group 2 wastewater stream in 63.641.
47GF5401	N/A	40 CFR Part 63, Subpart CC	Group 2 wastewater streams are not required to comply with the requirements of 61.340 through 61.355 from the definition of Group 2 wastewater stream in 63.641.
47GF5401	N/A	40 CFR Part 63, Subpart G	The API Separator does not receive wastewater from sources subject to MACT Subpart F.
47GG1523	N/A	40 CFR Part 60, Subpart J	Source does not burn fuel gas.
9058LOAD	N/A	40 CFR Part 63, Subpart CC	Not subject to the provisions of this subpart because the equipment does not contact one or more HAP in Table 1.
9059LOAD	N/A	40 CFR Part 63, Subpart CC	Not subject to the provisions of this subpart because the equipment does not contact one or more HAP in Table 1.

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
90FB004	N/A	40 CFR Part 60, Subpart K	Capacity > 65,000 gallons and constructed prior to 6/11/73.
90FB005	N/A	40 CFR Part 60, Subpart K	MACT CC supersedes NSPS K for Group 1 tanks.
90FB231	N/A	40 CFR Part 60, Subpart Kb	Vessel stores a VOL with a maximum true vapor pressure less than 0.5 psia.
90FB735	N/A	40 CFR Part 60, Subpart QQQ	Storage vessels subject to any requirements under NSPS subpart K series are exempt from the requirements under NSPS subpart QQQ.
90FB807	N/A	40 CFR Part 60, Subpart Kb	Tank capacity is less than 75 cubic meters (19,813 gallons).
9155LOAD	N/A	40 CFR Part 63, Subpart CC	Not subject to the provisions of this subpart because the equipment does not contact one or more HAP in Table 1.
9157LOAD	N/A	40 CFR Part 63, Subpart CC	Not subject to the provisions of this subpart because the equipment does not contact one or more HAP in Table 1.

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
9160LOAD	N/A	40 CFR Part 63, Subpart CC	Not subject to the provisions of this subpart because the equipment does not contact one or more HAP in Table 1.
91FB922	N/A	40 CFR Part 60, Subpart QQQ	Storage vessels subject to any requirements under NSPS subpart K series are exempt from the requirements under NSPS subpart QQQ.
91FB924	N/A	40 CFR Part 60, Subpart QQQ	Storage vessels subject to any requirements under NSPS subpart K series are exempt from the requirements under NSPS subpart QQQ.
92FA4001	N/A	40 CFR Part 60, Subpart Kb	capacity < 10,600 gallons
92FA4001	N/A	40 CFR Part 63, Subpart CC	Group 2 wastewater streams are not required to comply with the requirements of 61.340 through 61.355 from the definition of Group 2 wastewater stream in 63.641.
92FA4002	N/A	40 CFR Part 60, Subpart Kb	capacity < 10,600 gallons

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
92FA4002	N/A	40 CFR Part 63, Subpart CC	Does not meet the definition of a storage vessel since the capacity is less than 40 cubic meters.
96FB500	N/A	30 TAC Chapter 115, Storage of VOCs	Located in BPA, DFW, El Paso, or HGA and in a motor vehicle fuel dispensing service and has a nominal capacity < 25,000 gallons.
96FB500	N/A	40 CFR Part 60, Subpart Kb	capacity < 10,600 gallons
96FB500	N/A	40 CFR Part 63, Subpart CC	Does not meet the definition of a storage vessel since the capacity is less than 40 cubic meters.
DG-AGIT	N/A	40 CFR Part 63, Subpart T	Is not a solvent cleaning machine that uses any solvent containing methylene chloride, perchloroethylene, trichloroethylene, 1,1,1-trichloroethane, carbon tetrachloride, or chloroform, or any combination >5% weight as a cleaning and/or drying agent.

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
DG-AGIT2	N/A	40 CFR Part 63, Subpart T	Is not a solvent cleaning machine that uses any solvent containing methylene chloride, perchloroethylene, trichloroethylene, 1,1,1-trichloroethane, carbon tetrachloride, or chloroform, or any combination >5% weight as a cleaning and/or drying agent.
DG-ALKY	N/A	30 TAC Chapter 115, Degreasing Processes	Remote reservoir cold cleaner with TVP <= 0.6 psia @ 100F with a drain area < 16 sq. inches and waste solvent is disposed of in enclosed containers.
DG-ALKY	N/A	40 CFR Part 63, Subpart T	Is not a solvent cleaning machine that uses any solvent containing methylene chloride, perchloroethylene, trichloroethylene, 1,1,1-trichloroethane, carbon tetrachloride, or chloroform, or any combination >5% weight as a cleaning and/or drying agent.
DG-SHOP	N/A	30 TAC Chapter 115, Degreasing Processes	Remote reservoir cold cleaner with TVP <= 0.6 psia @ 100F with a drain area < 16 sq. inches and waste solvent is disposed of in enclosed containers.

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
DG-SHOP	N/A	40 CFR Part 63, Subpart T	Is not a solvent cleaning machine that uses any solvent containing methylene chloride, perchloroethylene, trichloroethylene, 1,1,1-trichloroethane, carbon tetrachloride, or chloroform, or any combination >5% weight as a cleaning and/or drying agent.
DG-UNIF	N/A	30 TAC Chapter 115, Degreasing Processes	Remote reservoir cold cleaner with TVP <= 0.6 psia @ 100F with a drain area < 16 sq. inches and waste solvent is disposed of in enclosed containers.
DG-UNIF	N/A	40 CFR Part 63, Subpart T	Is not a solvent cleaning machine that uses any solvent containing methylene chloride, perchloroethylene, trichloroethylene, 1,1,1-trichloroethane, carbon tetrachloride, or chloroform, or any combination >5% weight as a cleaning and/or drying agent.
GRP-CWT	22CWT3, 23CWT7, 27CWT2, 42CWT10, 44CWT9	40 CFR Part 63, Subpart Q	Cooling tower has not used chromium-based water treatment chemicals after 9/8/94.
GRP-ENG	42GG1848, 42GG1849	40 CFR Part 60, Subpart J	Source does not burn fuel gas.

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
GRP-HEAT1	27BA1000, 28BA1200, 41BA101, 41BA102, 81BA25	40 CFR Part 60, Subpart J	pre 6/11/73
GRP-HEATER	40BA1001, 40BA1002	40 CFR Part 63, Subpart CC	Process vents do not contain greater than 20 ppmv organic HAP; hence, they are not MACT CC miscellaneous process vents.
GRP-LABVENT	92EF1A, 92EF1B, 92EF1C, 92EF2, 92EF3, 92EF4, 92EF5	30 TAC Chapter 115, HRVOC Vent Gas	Equipment is a laboratory vent hood.
GRP-MARINE	9040LOAD, 9130LOAD	40 CFR Part 60, Subpart XX	Marine terminal not subject to NSPS Subpart XX since it is not a bulk gasoline terminal which delivers liquid products into gasoline tank trucks.
GRP-MARINE	9040LOAD, 9130LOAD	40 CFR Part 61, Subpart BB	Marine terminal does not load benzene.
GRP-SEP4	90CPI2001, 90CPI8301, 91CPI0301, 91CPI0401, 91CPI901	30 TAC Chapter 115, Water Separation	Any single or multiple compartment VOC water separator which is designed solely to capture stormwater, spills, or exterior surface cleanup waters is exempt from this undesignated head.
GRP-SEP4	90CPI2001, 90CPI8301, 91CPI0301, 91CPI0401, 91CPI901	40 CFR Part 60, Subpart QQQ	Manages storm water

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
GRP-SEP4	90CPI2001, 90CPI8301, 91CPI0301, 91CPI0401, 91CPI901	40 CFR Part 63, Subpart CC	Affected sources subject to this subpart does not include stormwater from segregated stormwater sewers.
GRP-TK1	90FB722, 90FB723	40 CFR Part 60, Subpart QQQ	Storage vessels subject to any requirements under NSPS subpart K series are exempt from the requirements under NSPS subpart QQQ.
GRP-TK1	90FB722, 90FB723	40 CFR Part 63, Subpart CC	Group 2 wastewater streams are not required to comply with the requirements of 61.340 through 61.355 from the definition of Group 2 wastewater stream in 63.641.
GRP-TK10	91FB370, 91FB371	40 CFR Part 60, Subpart K	Capacity > 65,000 gallons and constructed prior to 6/11/73.
GRP-TK12	90FB213, 90FB215, 90FB216, 90FB224, 91FB411, 91FB413, 91FB909, 91FB916	40 CFR Part 60, Subpart K	Capacity > 65,000 gallons and constructed prior to 6/11/73.
GRP-TK2	90FB006, 90FB232, 90FB233	40 CFR Part 60, Subpart Kb	Vessel stores a VOL with a maximum true vapor pressure less than 0.5 psia.
GRP-TK4	27TANK2, 41TANK1, 42TANK1, 42TANK2, 42TANK3, 42TANK4, 42TANK5, 44FA3095, 44FA3099, 44FB3097, 44FB3098, 45FB7499V, 45TANK1, 46FA6299V, 47FA5412, 47FA5493, 47FA5494, 91FA9001, 91FA9002, 91FA9003	30 TAC Chapter 115, Storage of VOCs	Tank less than 1,000 gallons

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
GRP-TK4	27TANK2, 41TANK1, 42TANK1, 42TANK2, 42TANK3, 42TANK4, 42TANK5, 44FA3095, 44FA3099, 44FB3097, 44FB3098, 45FB7499V, 45TANK1, 46FA6299V, 47FA5412, 47FA5493, 47FA5494, 91FA9001, 91FA9002, 91FA9003	40 CFR Part 60, Subpart Kb	capacity < 10,600 gallons
GRP-TK4	27TANK2, 41TANK1, 42TANK1, 42TANK2, 42TANK3, 42TANK4, 42TANK5, 44FA3095, 44FA3099, 44FB3097, 44FB3098, 45FB7499V, 45TANK1, 46FA6299V, 47FA5412, 47FA5493, 47FA5494, 91FA9001, 91FA9002, 91FA9003	40 CFR Part 63, Subpart CC	Does not meet the definition of a storage vessel since the capacity is less than 40 cubic meters.
GRP-TK6	23FB4501V, 23FB4503V, 42FB2097V, 42FB2099V, 42FB2499, 42FB2699	40 CFR Part 60, Subpart Kb	capacity < 10,600 gallons
GRP-TK6	23FB4501V, 23FB4503V, 42FB2097V, 42FB2099V, 42FB2499, 42FB2699	40 CFR Part 63, Subpart CC	Does not meet the definition of a storage vessel since the capacity is less than 40 cubic meters.
GRP-TK7	90FB228, 90FB505, 90FB506, 90FB507	40 CFR Part 60, Subpart K	MACT CC supersedes NSPS K for Group 1 tanks.
GRP-TK8	90FB003, 90FB225, 90FB226, 91FB911	40 CFR Part 60, Subpart K	Capacity > 65,000 gallons and constructed prior to 6/11/73.
GRP-VENTLUBE	22VENT, 45AVENT, 45VENT, 46VENT	40 CFR Part 63, Subpart CC	Process vents do not contain greater than 20 ppmv organic HAP.

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
GRP-VNT2	21FA103, 21FA18, 22CO2039, 22DA301, 22DA558, 22DA559, 22EA200A, 22EA200B, 22EA200C, 22EA202, 22EA4605, 22EA4606, 22FA201, 22FA202, 22FA223, 22FA300, 22FA301, 22FA302, 22FA4601, 22FA4602, 22PU1116, 22PU1526, 22PU1724, 22PU1725, 22PU1728, 22PU1729, 22PU2040, 22PU2041, 22PU2042, 22PU2044, 22PU2045, 22PU2046, 22PU2048, 22PU2099, 22PU2099A, 22PU2113, 22PU2114, 22PU2115, 22PU2116, 22PU2117, 22PU2118, 22PU2119, 22PU500, 22PU501, 22PU803, 22PU862, 22RX225, 22RX226, 23CO2028, 23DA101, 23DA102, 23DA201, 23DA405, 23EA310, 23EC205A-J, 23FA101, 23FA102, 23FA201, 23FA405, 23FA406, 23FA650, 23FA652, 23FA653, 23FA655, 23FA656, 23FA658, 24EA2402A, 27DA1101, 27DA1102, 27FA001, 27FA002, 27FA003, 27FA004, 27FA1000, 27FA1001, 27FA1101, 27FA1102, 28DA1200, 28FA1202, 29DA1300, 29FA1300, 41DA102, 41FA104, 42DA2001, 42DA2403, 42DA2404, 42DA2405, 42EA2401B, 42EA2410A, 42EA2410C, 42EA2411A, 42EA2411B, 42EA2412B, 42EA2413A, 42EA2413B, 42FA2001, 42FA2401, 42FA2402, 42FA2403, 42FA2452AX, 42FA2452BX, 42RX2101, 43DA4501, 43DA4502, 43EA4503A, 43EA4503B, 43EA4503C, 43EA4503D, 43EA4504A, 43EA4504B, 44DA3001, 44DA3002, 44DA3003, 44DA3004, 44DA3010, 44DA3011, 44FA3001, 44FA3002, 44FA3004A, 44FA3004B, 44FA3005, 45DA3002, 45DA7401, 45FA6001, 45FA6003, 45FA6004, 45FA6006, 45FA6008, 45FA7403, 46FA6201, 46FA6202	40 CFR Part 63, Subpart CC	Does not meet the definition of a miscellaneous process vent because it is not periodically discharged during normal operation.

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
GRP-VNT6	21DA1104, 22DA107, 22DA1802	30 TAC Chapter 115, Vent Gas Controls	Does not meet the definition of vent as defined in 115.10
GRP-VNT6	21DA1104, 22DA107, 22DA1802	40 CFR Part 63, Subpart CC	Does not meet the definition of a miscellaneous process vent because it is not periodically discharged during normal operation.

New Source Review Authorization References

New Source Review Authorization References 290

New Source Review Authorization References by Emission Unit..... 293

New Source Review Authorization References

The New Source Review authorizations listed in the table below are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Prevention of Significant Deterioration (PSD) Permits	
PSD Permit No.: PSDTX767M2	Issuance Date: 07/12/1995
Title 30 TAC Chapter 116 Permits, Special Permits, and Other Authorizations (Other Than Permits By Rule, PSD Permits, or NA Permits) for the Application Area.	
Authorization No.: 19294	Issuance Date: 03/01/2010
Authorization No.: 19637	Issuance Date: 03/01/2010
Authorization No.: 2498A	Issuance Date: 10/12/2005
Authorization No.: 2501A	Issuance Date: 02/08/2012
Authorization No.: 2507A	Issuance Date: 08/10/2007
Authorization No.: 48982	Issuance Date: 03/31/2010
Authorization No.: 50232	Issuance Date: 03/05/2004
Authorization No.: 71281	Issuance Date: 03/19/2010
Authorization No.: 80493	Issuance Date: 06/25/2012
Authorization No.: 83749	Issuance Date: 02/24/2009
Authorization No.: 86142	Issuance Date: 10/09/2008
Authorization No.: 88508	Issuance Date: 06/02/2009
Authorization No.: 94434	Issuance Date: 01/26/2011
Authorization No.: 101541	Issuance Date: 04/12/2012
Authorization No.: 106909	Issuance Date: 06/12/2013
Permits By Rule (30 TAC Chapter 106) for the Application Area	
Number: 106.122	Version No./Date: 09/04/2000
Number: 106.211	Version No./Date: 11/01/2003
Number: 106.261	Version No./Date: 12/24/1998
Number: 106.261	Version No./Date: 09/01/1999
Number: 106.261	Version No./Date: 09/04/2000
Number: 106.261	Version No./Date: 11/01/2003
Number: 106.262	Version No./Date: 12/24/1998
Number: 106.262	Version No./Date: 11/01/2003

New Source Review Authorization References

The New Source Review authorizations listed in the table below are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Number: 106.263	Version No./Date: 11/01/2001
Number: 106.264	Version No./Date: 03/14/1997
Number: 106.264	Version No./Date: 09/01/1999
Number: 106.264	Version No./Date: 09/04/2000
Number: 106.412	Version No./Date: 03/14/1997
Number: 106.433	Version No./Date: 09/04/2000
Number: 106.454	Version No./Date: 03/14/1997
Number: 106.454	Version No./Date: 06/18/1997
Number: 106.454	Version No./Date: 07/08/1998
Number: 106.454	Version No./Date: 09/09/1998
Number: 106.454	Version No./Date: 09/01/1999
Number: 106.472	Version No./Date: 03/14/1997
Number: 106.472	Version No./Date: 09/01/1999
Number: 106.472	Version No./Date: 09/04/2000
Number: 106.473	Version No./Date: 03/14/1997
Number: 106.478	Version No./Date: 03/14/1997
Number: 106.478	Version No./Date: 11/26/1997
Number: 106.478	Version No./Date: 09/01/1999
Number: 106.478	Version No./Date: 09/04/2000
Number: 106.492	Version No./Date: 09/04/2000
Number: 106.511	Version No./Date: 09/04/2000
Number: 106.512	Version No./Date: 09/04/2000
Number: 106.533	Version No./Date: 07/04/2004
Number: 5	Version No./Date: 09/12/1989
Number: 5	Version No./Date: 07/20/1992
Number: 6	Version No./Date: 05/12/1981
Number: 6	Version No./Date: 09/12/1989
Number: 51	Version No./Date: 07/20/1992

New Source Review Authorization References

The New Source Review authorizations listed in the table below are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Number: 51	Version No./Date: 04/05/1995
Number: 51	Version No./Date: 06/07/1996
Number: 53	Version No./Date: 10/04/1995
Number: 79	Version No./Date: 05/12/1981
Number: 86	Version No./Date: 08/30/1988
Number: 86	Version No./Date: 09/12/1989
Number: 86	Version No./Date: 05/04/1994
Number: 86	Version No./Date: 04/05/1995
Number: 86	Version No./Date: 06/07/1996
Number: 102	Version No./Date: 01/08/1980
Number: 111	Version No./Date: 09/12/1989
Number: 111	Version No./Date: 06/07/1996
Number: 118	Version No./Date: 09/12/1989
Number: 118	Version No./Date: 09/13/1993

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
21DA1104	DEPENTANIZER	2501A
21FA103	41FA103 - COMPRESSOR KNOCKOUT DRUM	2501A
21FA18	FLARE KNOCKOUT DRUM	2501A
21FUG	ISOOCTENE UNIT FUGITIVES	2501A, 106.261/11/01/2003
22AFUG	BHT FUGITIVES	2501A, 106.261/11/01/2003
22AVENT	BHT CATALYST REGENERATION	2501A
22BFUG	O2 GAS PLANT FUGITIVES	48982, 106.261/11/01/2003
22CO2039	REFRIGERATION COMPRESSOR	2501A
22CO517	ALKY UNIT KELLOGG COMPRESSOR	2501A
22CWT3	#3 COOLING TOWER	106.261/11/01/2003
22DA107	DEISOBUTANIZER	2501A
22DA1802	DEBUTANIZER	2501A
22DA301	VACUUM TOWER	2501A
22DA558	BAUXITE TOWER, WEST	2501A
22DA559	BAUXITE TOWER, EAST	2501A
22EA200A	REFRIGERANT CONDENSER	2501A
22EA200B	REFRIGERANT CONDENSER	2501A
22EA200C	REFRIGERANT ACCUMULATOR	2501A

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
22EA202	DEISOBUTANIZER REBOILER	2501A
22EA4605	HYDROTREATER EFFLUENT COOLER	2501A
22EA4606	HYDROTREATER RUN DOWN COOLER	2501A
22EG400	BARGE LOADING SCRUBBER	101541
22FA201	COMPRESSOR DRY DRUM	2501A
22FA202	COMPRESSOR CONDENSATE DRUM	2501A
22FA223	ACID CATCH DRUM	2501A
22FA225	ALKY UNIT BAUXITE TOWER WASHING	2501A
22FA300	ACID SETTLER	2501A
22FA301	STRATCO COMPRESSOR KNOCKOUT DRUM	2501A
22FA302	REFRIGERANT ACCUMULATOR	2501A
22FA4601	HIGH PRESSURE FLASH DRUM	2501A
22FA4602	LP FLASH DRUM	2501A
22FB748	STORAGE TANK 22FB748	2501A
22FB749	FRESH ACID TANK	2501A
22FUG	ALKYLATION UNIT	2501A, 106.261/11/01/2003
22PU1116	REACTOR EFFLUENT PUMP	2501A
22PU1526	REACTOR EFFLUENT PUMP	2501A

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
22PU1724	BHT CHARGE PUMP	2501A
22PU1725	BHT CHARGE PUMP	2501A
22PU1728	BHT RUNDOWN PUMP	2501A
22PU1729	BHT RUNDOWN PUMP	2501A
22PU2040	PROPANE PURGE PUMP	2501A
22PU2041	EFFLUENT PUMP	2501A
22PU2042	REFRIG. RECYCLE PUMP	2501A
22PU2044	ACID CIRC. PUMP	2501A
22PU2045	ISOBUTANE MAKEUP PUMP	2501A
22PU2046	ALKY FEED PUMP	2501A
22PU2048	ISOBUTANE RECYCLE BOOSTER PUMP	2501A
22PU2099A	PROPANE PURGE PUMP	2501A
22PU2099	PROPANE PURGE PUMP	2501A
22PU2113	PROPANE PURGE PUMP	2501A
22PU2114	EFFLUENT PUMP	2501A
22PU2115	REFRIG. RECYCLE PUMP	2501A
22PU2116	ACID CIRC. PUMP	2501A
22PU2117	ACID CIRC. PUMP	2501A

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
22PU2118	ALKY FEED PUMP	2501A
22PU2119	ISOBUTANE RECYCLE BOOSTER PUMP	2501A
22PU500	DEBUTANIZER REFLUX PUMPS	2501A
22PU501	DEBUTANIZER REFLUX PUMPS	2501A
22PU803	DEBUTANIZER OH PUMP	2501A
22PU862	DEBUTANIZER OH PUMP	2501A
22RX225	STRATCO REACTOR	2501A
22RX226	STRATCO REACTOR	2501A
22SKD4201	ACID VAPOR SCRUBBER	88508
22SKD4202	THERMAL OXIDIZER	88508
22VENT	ALKY UNIT LUBE OIL MIST SYSTEM VENTS	106.261/11/01/2003
23BA301	VACUUM TOWER FURNACE (WEST)	19294
23BA302	VACUUM TOWER HTR. (EAST)	19294
23BC201	ATMOS. TOWER FURNACE	48982
23CO2028	SAT. COMBO OFF GAS COMPRESSOR	111/09/12/1989
23CWT7	#7 COOLING TOWER	48982
23DA101	STABILIZER TOWER	2501A
23DA102	DEBUTANIZER	2501A

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
23DA201	ATMOSPHERIC TOWER	2501A
23DA405	COMBO SOUR WATER STRIPPER	2501A
23EA301	#3 VACUUM JET CONDENSER	2501A
23EA310	#3 VACUUM JET CONDENSER	2501A
23EC205A-J	FRACTIONATOR OH CONDENSER	2501A
23FA101	STABILIZER OVERHEAD RECEIVER	2501A
23FA102	DEBUTANIZER OVERHEAD ACCUMULATOR	2501A
23FA201	ATMOSPHERIC TOWER OVERHEAD RECEIVER	2501A
23FA206	VACUUM SEAL DRUM	2501A
23FA405	COMBO SWS OVERHEAD ACCUMULATOR	2501A
23FA406	COMBO SWS OIL/WATER ACCUMULATOR	2501A
23FA650	SGC 1ST STAGE SUCTION DRUM	2501A
23FA652	SAT. GAS COMPRESSOR 1ST STAGE DISCHARGE BOTTLE	2501A
23FA653	SGC 2ND STAGE SUCTION	2501A
23FA655	SAT. GAS COMPRESSOR 2ND STAGE DISCHARGE BOTTLE	2501A
23FA656	SGC 3RD STAGE SUCTION	2501A
23FA658	SAT. GAS COMPRESSOR 3RD STAGE DISCHARGE BOTTLE	2501A
23FB4501V	DM 9942	106.472/03/14/1997

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
23FB4503V	EMBREAK 2W151	106.472/03/14/1997
23FUG	CRUDE UNIT FUGITIVES	48982, 106.261/11/01/2003
24EA2402A	HP RECEIVER TRIM COOLER	2501A
27AFUG	"C" UNIFIER FUGITIVES	48982, 106.261/11/01/2003
27BA1000	C UNIFINER RX. FURNACE	48982
27CWT2	#2 COOLING TOWER	48982
27DA1101	STABILIZER	2501A
27DA1102	RERUN TOWER	2501A
27ENG1	PLATFORMER AIR COMPRESSOR ENGINE NO. 1	006/09/12/1989, 106.511/09/04/2000
27ENG2	PLATFORMER AIR COMPRESSOR ENGINE NO. 2	006/09/12/1989, 106.511/09/04/2000
27FA001	#1 COMPRESSOR KNOCKOUT POT	2501A
27FA002	#2 COMPRESSOR KNOCKOUT POT	2501A
27FA003	#3 COMPRESSOR KNOCKOUT POT	2501A
27FA004	#4 COMPRESSOR KNOCKOUT POT	2501A
27FA1000	HP PRODUCT SEPARATOR	2501A
27FA1001	LP PRODUCT SEPARATOR	2501A
27FA1101	PRODUCT SEPARATOR	2501A
27FA1102	STABILIZER RECEIVER	2501A

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
27FUG	PLATFORMER FUGITIVES	48982, 106.261/11/01/2003
27TANK2	NO. 2 OIL	106.472/03/14/1997
28BA1200	A UNIFINER RX. FURNACE	48982
28DA1200	A UNIFINER STRIPPER TOWER	2501A
28FA1202	A UNIFINER STRIPPER ACCUMULATOR	2501A
28FUG	"A" UNIFIER FUGITIVES	48982, 106.261/11/01/2003
29BA1300	B UNIFINER RX. FURNACE	48982
29DA1300	B UNIFINER STRIPPER TOWER	2501A
29FA1300	B UNIFINER STRIPPER RECEIVER	2501A
29FUG	"B" UNIFIER FUGITIVES	83749, 106.261/11/01/2003
30FL1	MAIN REFINERY FLARE	83749
30FL6	ULSD FLARE	71281
30FUG	REFINERY FLARE AND FL GAS RECOVERY UNIT FUG	83749, 106.261/11/01/2003
30GG1822	CFU EMERGENCY GENERATOR	106.511/09/04/2000, 005/09/12/1989
30LOAD	PLANT GASOLINE REFUELING	106.473/03/14/1997
30PU2991	DIESEL FIRE WATER PUMP ENGINE 1	106.511/09/04/2000
30PU2992	DIESEL FIRE WATER PUMP ENGINE 2	106.511/09/04/2000
30PU2993	DIESEL FIRE WATER PUMP ENGINE 3	106.511/09/04/2000

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
39CB2001	TAIL GAS INCINERATOR UNIT 39 SRU	2507A
39FA1006	SRU C SULFUR COLLECTION HEADER	2507A
39FB1001	SULFUR TANK 39FB1001	2507A
39FUG	UNIT 39 SRU FUGITIVES	2507A, 106.261/11/01/2003
39LO1001	SRU C SULFUR LOADING	2507A
39RX2001	C TRAIN SRU	2507A
40BA1001	LCO COMBINED FEED HEATER	71281
40BA1002	DIESEL COMBINED FEED HEATER	71281
40BA1101	PRODUCT FRACTIONATOR REBOILER HEATER	71281
40CWT11	#11 COOLING TOWER	71281
40DA1101	H ₂ S STRIPPER	71281
40DA1102	PRODUCT FRACTIONATOR	71281
40DA1103	HEAVY NAPHTHA STRIPPER	71281
40DA1201	DEETHANIZER	71281
40DA1202	SPONGE OIL ABSORBER	71281
40DA1203	DEBUTANIZER	71281
40DA1204	DEPROPANIZER	71281
40DA1205	DEISOBUTANIZER	71281

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
40DA1206	FUEL GAS AMINE ABSORBER	71281
40DA1207	LIQUID AMINE ABSORBER	71281
40FUG	ULSD UNIT FUGITIVES	71281, 106.261/11/01/2003
41BA101	D UNIFINER RX. FURNACE	48982
41BA102	D UNIFINER REBOILER	48982
41DA102	RERUN TOWER	2501A
41FA104	41FA104 - COMPRESSOR KNOCKOUT DRUM	2501A
41FUG	"D" UNIFIER FUGITIVES	48982, 106.261/11/01/2003
41TANK1	SS-99	106.472/03/14/1997
42AFUG	FCC UNIT FUGITIVES	2501A, 106.261/11/01/2003
42BC2001	PEABODY AIR HEATER	2501A
42BFUG	FCC CAT CON UNIT FUGITIVES	2501A, 106.261/11/01/2003
42CB2201	FCC REGENERATOR	50232
42CFUG	FCC DEPENTANIZER UNIT FUGITIVES	2501A, 106.261/11/01/2003
42CWT10	#10 COOLING TOWER	2501A
42DA2001	MAIN COLUMN	2501A
42DA2403	GASOLINE STRIPPER	2501A
42DA2404	DEBUTANIZER	2501A

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
42DA2405	DEPENTANIZER	2501A
42EA2401B	INTERSTAGE COOLER	2501A
42EA2410A	DEBUTANIZER OH CONDENSER	2501A
42EA2410C	DEBUTANIZER OH CONDENSER	2501A
42EA2411A	DEBUTANIZER REBOILER	2501A
42EA2411B	DEBUTANIZER REBOILER	2501A
42EA2412B	GAS PRODUCTS TRIM COOLER	2501A
42EA2413A	S INTERSTAGE COOLER	2501A
42EA2413B	S INTERSTAGE COOLER	2501A
42EG7901	DEAERATOR	2501A
42ENG1	FCCU BACK-UP AIR COMPRESSOR 1 VENT	106.511/09/04/2000
42FA2001	MAIN COLUMN OVERHEAD ACCUMULATOR	2501A
42FA2099V	DEGREASER STORAGE	106.472/03/14/1997
42FA2401	WGC 1ST STAGE SUCTION DRUM	2501A
42FA2402	WGC INTERSTAGE DRUM	2501A
42FA2403	WGC HIGH STAGE DRUM	2501A
42FA2452AX	SEAL OIL TRAP	2501A
42FA2452BX	SEAL OIL TRAP	2501A

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
42FB2097V	STABILIZER STORAGE	051/07/20/1992
42FB2099V	NICKEL PASSIVATOR STORAGE	051/07/20/1992
42FB2499	COMPRESSOR INHIBITOR	051/07/20/1992
42FB2699	DEMULSIFIER STORAGE	051/07/20/1992
42FB2801	FRESH CAUSTIC TANK	2501A
42FB2802	CORROSION INHIBITOR	2501A
42FUG	FCC CAT GAS UNIT FUGITIVES	2501A, 106.261/11/01/2003
42GG1730	FCC EMERGENCY ENGINE	106.511/09/04/2000
42GG1848	CIWA FIREWATER PUMP ENGINE NO. 1	106.511/09/04/2000, 005/09/12/1989
42GG1849	CIWA FIREWATER PUMP ENGINE NO. 2	106.511/09/04/2000, 005/09/12/1989
42RX2101	FCC REACTOR	2501A
42TANK1	DEGREASER STORAGE	106.472/03/14/1997
42TANK2	DEGREASER STORAGE	106.472/03/14/1997
42TANK3	DEGREASER STORAGE	106.472/03/14/1997
42TANK4	DEGREASER STORAGE	106.472/03/14/1997
42TANK5	DEGREASER STORAGE	106.472/03/14/1997
43AFUG	FCC PROPYLENE UNIT FUGITIVES	2501A, 106.261/11/01/2003
43DA4501	PROPYLENE SPLITTER	2501A

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
43DA4502	DEPROPANIZER	2501A
43EA4503A	PROPYLENE SPLITTER OH CONDENSER	2501A
43EA4503B	PROPYLENE SPLITTER OH CONDENSER	2501A
43EA4503C	PROPYLENE SPLITTER OH CONDENSER	2501A
43EA4503D	PROPYLENE SPLITTER OH CONDENSER	2501A
43EA4504A	DEPROPANIZER OH CONDENSER	2501A
43EA4504B	DEPROPANIZER OH CONDENSER	2501A
43FUG	FCC MEROX UNIT FUGITIVES	2501A, 106.261/11/01/2003
44AFUG	SATS GAS FUGITIVES	48982, 106.261/11/01/2003
44BA3001	ROSE DAO FURNACE	2498A
44BA3002	ROSE HOT OIL HTR.	2498A
44BA3005	ROSE ASPHALT FURNACE	2498A
44CO1418	ROSE UNIT SOLVENT COMPRESSOR	2498A
44CWT9	#9 COOLING TOWER	48982
44DA3001	ASPHALTENE SEPARATOR	2501A
44DA3002	DAO STRIPPER	2501A
44DA3003	ASPHALT STRIPPER	2501A
44DA3004	LOW PRESSURE FLASH DRUM	2501A

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
44DA3010	DAO STRIPPER	2501A
44DA3011	HOT OIL DRUM	2501A
44FA3001	ASPHALT MIX FLASH DRUM	2501A
44FA3002	SOLVENT ACCUMULATOR	2501A
44FA3004A	COMPRESSOR KNOCKOUT DRUM	2501A
44FA3004B	COMPRESSOR KNOCKOUT DRUM	2501A
44FA3005	HIGH PRESSURE FLASH DRUM	2501A
44FA3007	FEED SURGE DRUM	2501A
44FA3095	DEGREASER STORAGE	106.473/03/14/1997
44FA3099	DEGREASER STORAGE	106.472/03/14/1997
44FB3001	TEMPERED WATER TANK	2498A
44FB3097	DEGREASER STORAGE	106.472/03/14/1997
44FB3098	DEGREASER STORAGE	106.472/03/14/1997
44FUG	ROSE FUGITIVES	2498A, 106.261/11/01/2003
45AFUG	SWS UNIT FUGITIVES	2507A, 106.261/11/01/2003
45AVENT	AMINE UNIT LUBE OIL MIST SYSTEM VENTS	106.261/11/01/2003
45DA3002	MEA REGENERATOR	2501A
45DA7401	SOUR WATER STRIPPER	2501A

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
45FA6001	SOUR GAS KNOCKOUT DRUM	2501A
45FA6003	AMINE REGENERATOR OH ACCUMULATOR	2501A
45FA6004	MEA RECLAIMER	2501A
45FA6006	MOBIL COMPRESSOR DISCHARGE DRUM	2501A
45FA6008	MOBIL COMPRESSOR SUCTION DRUM	2501A
45FA7403	SOUR WATER STRIPPER OVERHEAD ACCUMULATOR	2501A
45FB6001	FRESH MEA TANK	2507A
45FB6002	ORGANIC TANK	2507A
45FB6360	MDEA STORAGE TANK	2507A
45FB7401	SOUR WATER STORAGE	2507A
45FB7402	SOUR WATER STORAGE	2507A
45FB7403	SOUR WATER TANK	2507A
45FB7499V	CHEMICAL INHIBITION STORAGE	106.472/03/14/1997
45FUG	AMINE UNIT FUGITIVES	2507A, 106.261/11/01/2003
45TANK1	DEGREASER STORAGE	106.472/03/14/1997
45VENT	SWS UNIT LUBE OIL MIST SYSTEM VENTS	106.261/11/01/2003
46AD6202	SRU B SULFUR PIT	2507A
46BC6302	TAIL GAS INCINERATOR BURNER	2507A

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
46BC6325	REDUCING GAS GENERATOR	2507A
46CB6301	TAIL GAS INCINERATOR	2507A
46FA6201	MEA GAS KNOCKOUT DRUM	2507A
46FA6202	SOUR WATER STRIPPER KNOCKOUT DRUM	2507A
46FA6299V	DEGREASER STORAGE	106.472/03/14/1997
46FB6301	SOLVENT STORAGE TANK	2507A
46FUG	UNIT 46 SRU FUGITIVES	2507A, 106.261/11/01/2003
46LO6201	SRU B SULFUR LOADING	2507A
46RX6206	B TRAIN SRU	2507A
46VENT	UNIT 46 SRU LUBE OIL MIST SYSTEM VENTS	106.261/11/01/2003
47AD5409	DAF UNIT	48982
47FA2	DAF FLOAT TANK	106.264/09/01/1999
47FA5412	DIESEL STORAGE TANK	106.472/03/14/1997
47FA5493	DIESEL STORAGE TANK	106.472/03/14/1997
47FA5494	DEGREASER STORAGE	106.472/03/14/1997
47FB321	API SEPARATOR RECOVERED OIL TANK	079/05/12/1981
47FB323	API SEPARATOR RECOVERED OIL TANK	106.264/09/01/1999
47FB503	TANK 47FB503	086/04/05/1995

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
47FB504	TANK 47FB504	086/06/07/1996, 086/09/12/1989, 118/09/12/1989
47FB509	TANK 47FB509	102/01/08/1980, 106.478/03/14/1997
47FUG	WASTEWATER TREATER FUGITIVES	48982, 106.261/11/01/2003
47GF5401	API SEPARATOR	48982
47GG1523	PUMP ENGINE AT WWT	106.511/09/04/2000, 005/09/12/1989
50BF02	#2 BOILER	19637
50BF03	#3 BOILER	19637
50FUG	BOILERS NO. 2 AND NO. 3 FUGITIVES	19637, 106.261/11/01/2003
51FUG	CRUDE UNIT 51 FUGITIVE COMPONENTS	106909
51HTR	PROCESS HEATER	106909
5G-C001OWS	MACT 5G OWS	106.533/07/04/2004
5GCVS	GW RECOVERY CVS	106.533/07/04/2004
5GFUG	GW RECOVERY FUGITIVES	106.533/07/04/2004
5GTRANSFER	MACT 5G TRANSFER SYSTEMS	106.533/07/04/2004
81BA25	BOILER HOUSE HOT OIL HTR.	48982
81BF01	#1 BOILER	19637
81ENG1	BOILER HOUSE BACK-UP AIR COMPRESSOR 1	106.511/09/04/2000

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
81FUG	BOILERHOUSE UNIT FUGITIVES	19637, 48982, 106.261/11/01/2003
81GEN001	BOILER HOUSE DIESEL EMERGENCY GENERATOR	106.511/09/04/2000
81SKD5602	GROUNDWATER RECOVERY THERMAL OXIDIZER (PHASE II)	106.533/07/04/2004
81SKD5603	GROUNDWATER RECOVERY THERMAL OXIDIZER (PHASE II)	106.533/07/04/2004
9040LOAD	NO.4 DOCK	48982
9058LOAD	A PUMP TRUCK RACK	051/04/05/1995
9059LOAD	A PUMP RAIL RACK	48982
90AFUG	CRUDE TANK FARM FUGITIVES	48982, 106.261/11/01/2003
90BFUG	16-ACRE TANK FARM FUGITIVES	48982, 106.211/11/01/2003
90CB5601	MARINE LOADING DOCK NO. 1 THERMAL OXIDIZER	106.492/09/04/2000
90CFUG	REFRIGERATED STORAGE FUGITIVES	48982, 106.261/11/01/2003
90CPI2001	OUTFALL 007 CPI	48982
90CPI8301	OUTFALL 003 CPI	48982
90DOCK1	MARINE LOADING DOCK NO. 1	106.261/11/01/2003, 106.262/11/01/2003, 106.492/09/04/2000
90DOCK2	SIMS BAYOU DOCK #2	106.261/09/01/1999
90FB001	TANK 90FB001	86142, 106.261/11/01/2003
90FB002	STORAGE TANK 90FB002	106.263/11/01/2001, 106.478/09/04/2000

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
90FB003	TANK 90FB003	106.261/09/01/1999
90FB004	TANK 90FB004	106.261/09/04/2000, 106.478/09/04/2000
90FB005	TANK 90FB005	2501A
90FB006	TANK 90FB006	2501A
90FB205	TANK 90FB205	2501A, 106.478/09/04/2000
90FB210	TANK 90FB210	71281
90FB213	TANK 90FB213	2501A
90FB215	TANK 90FB215	2501A
90FB216	TANK 90FB216	2501A
90FB223	STORAGE TANK 90FB223	106909
90FB224	TANK 90FB224	2501A
90FB225	TANK 90FB225	102/01/08/1980, 106.478/03/14/1997
90FB226	TANK 90FB226	2501A
90FB228	TANK 90FB228	2501A
90FB229	STORAGE TANK 90FB229	106909
90FB230	TANK 90FB230	2501A
90FB231	TANK 90FB231	106.472/09/04/2000
90FB232	TANK 90FB232	2501A

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
90FB233	TANK 90FB233	2501A
90FB234	DIESEL STORAGE TANK	71281
90FB505	TANK 90FB505	2501A
90FB506	TANK 90FB506	2501A
90FB507	TANK 90FB507	2501A
90FB511	GASOLINE STORAGE TANK	71281
90FB722	TANK 90FB722	106.472/03/14/1997
90FB723	TANK 90FB723	106.472/03/14/1997
90FB735	TANK 90FB735	106.472/09/04/2000
90FB807	PROCESS AMINE STORAGE	2507A
90FB831	PRESSURIZED TANK 90FB831	2501A
90FB832	PRESSURIZED TANK 90FB832	2501A
90FB833	PRESSURIZED TANK 90FB833	2501A
90FB834	PRESSURIZED TANK 90FB834	2501A
90FB835	PRESSURIZED TANK 90FB835	2501A
90FB844	PRESSURIZED TANK 90FB844	2501A
90FB845	PRESSURIZED TANK 90FB845	2501A
90FB847	PRESSURIZED TANK 90FB847	2501A

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
90FUG	"A" TANK FARM FUGITIVES	48982, 71281, 106.261/11/01/2003, 106.492/09/04/2000
90GG2245	SIMS BAYOU FIREWATER PUMP ENGINE	106.511/09/04/2000
9130LOAD	NO. 3 DOCK	111/06/07/1996
9155LOAD	CHEMICAL TRUCK RACK	106.472/09/01/1999
9157LOAD	B PUMP RAIL RACK	48982
9160LOAD	B PUMP TRUCK RACK	48982
91BFUG	900-GROUP TANK FARM FUGITIVES	48982, 106.261/11/01/2003
91CB915	GROUNDWATER RECOVERY THERMAL OXIDIZER (PHASE I)	106.533/07/04/2004
91CPI0301	300 TANK FARM CPI	48982
91CPI0401	400 TANK FARM CPI	48982
91CPI901	900 TANK FARM CPI	48982
91FA9001	CONTRACTOR REFUELING - DIESEL	106.412/03/14/1997
91FA9002	CONTRACTOR REFUELING - GASOLINE	106.412/03/14/1997
91FA9003	CONTRACTOR REFUELING - DIESEL	106.412/03/14/1997
91FB370	TANK 91FB370	106.478/11/26/1997
91FB371	TANK 91FB371	106.478/11/26/1997
91FB411	TANK 91FB411	106.472/09/01/1999

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
91FB413	TANK 91FB413	106.472/09/01/1999
91FB901	TANK 91FB901	106.263/11/01/2001, 106.264/09/04/2000
91FB907	TANK 91FB907	106.264/09/01/1999
91FB909	TANK 91FB909	48982
91FB911	TANK 91FB911	106.261/09/01/1999
91FB912	STORAGE TANK 91FB912	48982, 94434, 106.478/09/04/2000
91FB913	STORAGE TANK 91FB913	48982, 94434, 106.478/09/04/2000
91FB916	TANK 91FB916	2501A
91FB917	TANK 91FB917	2501A
91FB918	TANK 91FB918	2501A, 106.261/11/01/2003
91FB920	TANK 91FB920	2501A, 106.261/09/04/2000, 106.478/09/04/2000
91FB921	TANK 91FB921	2501A, 106.478/09/04/2000
91FB922	TANK 91FB922	86/08/11/1989
91FB924	TANK 91FB924	86/06/07/1996
91FB927	TANK 91FB927	106.264/09/04/2000, 106.478/03/14/1997
91FB931	TANK 91FB931	106.478/09/01/1999
91FUG	300-GROUP TANK FARM FUGITIVES	48982, 106.261/11/01/2003

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
92EF1A	LABORATORY VENT	80493, 106.122/09/04/2000
92EF1B	LABORATORY VENT	80493, 106.122/09/04/2000
92EF1C	LABORATORY VENT	80493, 106.122/09/04/2000
92EF2	LABORATORY VENT	80493, 106.122/09/04/2000
92EF3	LABORATORY VENT	80493, 106.122/09/04/2000
92EF4	LABORATORY VENT	80493, 106.122/09/04/2000
92EF5	LABORATORY VENT	80493, 106.122/09/04/2000
92FA4001	RECOVERED OIL	051/06/07/1996
92FA4002	OILY WATER	53/10/04/1995
96FB500	PLANT GASOLINE REFUELING TANK	106.264/03/14/1997
96FUG	RECOVERY WELL SYSTEM FUGITIVES	106.533/07/04/2004
97GE2999	DIESEL GENERATOR (IS BACKUP)	106.511/09/04/2000
DG-AGIT2	MAINTENANCE SHOP PARTS WASHER, WEST	106.454/09/01/1999
DG-AGIT	SHOP AGITATED DEGREASER	106.454/09/09/1998
DG-ALKY	ALKY DEGREASER	106.454/06/18/1997
DG-SHOP	SHOP DEGREASER	106.454/06/18/1997
DG-UNIF	UNIFINER DEGREASER	106.454/06/18/1997
EJECTOR_AU	PULLING VACUUM ON REACTOR	48982

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
EJECTOR_BU	PULLING VACUUM ON REACTOR	48982
EJECTOR_CU	PULLING VACUUM ON REACTOR	48982
EJECTOR_DU	PULLING VACUUM ON REACTOR	48982
PROCVENT	PROCESS ANALYZER VENTS	106.261/11/01/2003

Appendix A

Acronym List317

Acronym List

The following abbreviations or acronyms may be used in this permit:

ACFM	actual cubic feet per minute
AMOC	alternate means of control
ARP	Acid Rain Program
ASTM	American Society of Testing and Materials
B/PA	Beaumont/Port Arthur (nonattainment area)
CAM	Compliance Assurance Monitoring
CD	control device
COMS	continuous opacity monitoring system
CVS	closed-vent system
D/FW	Dallas/Fort Worth (nonattainment area)
DR	Designated Representative
ELP	El Paso (nonattainment area)
EP	emission point
EPA	U.S. Environmental Protection Agency
EU	emission unit
FCAA Amendments	Federal Clean Air Act Amendments
FOP	federal operating permit
GF	grandfathered
gr/100 scf	grains per 100 standard cubic feet
HAP	hazardous air pollutant
H/G/B	Houston/Galveston/Brazoria (nonattainment area)
H ₂ S	hydrogen sulfide
ID No.	identification number
lb/hr	pound(s) per hour
MMBtu/hr	Million British thermal units per hour
MRRT	monitoring, recordkeeping, reporting, and testing
NA	nonattainment
N/A	not applicable
NADB	National Allowance Data Base
NO _x	nitrogen oxides
NSPS	New Source Performance Standard (40 CFR Part 60)
NSR	New Source Review
ORIS	Office of Regulatory Information Systems
Pb	lead
PBR	Permit By Rule
PM	particulate matter
ppmv	parts per million by volume
PSD	prevention of significant deterioration
RO	Responsible Official
SO ₂	sulfur dioxide
TCEQ	Texas Commission on Environmental Quality
TSP	total suspended particulate
TVP	true vapor pressure
U.S.C.	United States Code
VOC	volatile organic compound

Appendix B

New Source Review Permits 19637 and PSDTX767M2319

Bryan W. Shaw, Ph.D., *Chairman*
Buddy Garcia, *Commissioner*
Carlos Rubinstein, *Commissioner*
Mark R. Vickery, P.G., *Executive Director*



TEXAS COMMISSION ON ENVIRONMENTAL QUALITY
Protecting Texas by Reducing and Preventing Pollution

March 1, 2010

MR CHRISTOPHER ABSHIRE
MANAGER ENVIRONMENTAL ENGINEERING
VALERO REFINING TEXAS LP
PO BOX 5038
HOUSTON TX 77262-5038

Re: Permit Alteration
Permit Numbers: 19637 and PSDTX767M2
Valero Refining Houston Refinery
Houston, Harris County
Regulated Entity Number: RN100219310
Customer Reference Number: CN600127468
Account Number: HG-0130-C

Dear Mr. Abshire:

This is in response to your letter received December 18, 2009, requesting alteration of the conditions of the above-referenced permit. We understand you propose to add language pursuant to U.S. Environmental Protection Agency Consent Decree SA-05-CA-0569 limiting nitrogen oxides emissions from Emission Point Nos. 81BF5601, 81BF5602, and 81BF5603.

As indicated in Title 30 Texas Administrative Code § 116.116(c) [30 TAC § 116.116(c)], and based on our review, Permit Numbers 19637 and PSDTX767M2 are altered. Enclosed are the altered permit conditions to replace those currently attached to your permit. Please attach these to your permit.

No planned maintenance, startup, and shutdown emissions have been reviewed or represented in this application and none are authorized by this permit.

As of July 1, 2008, all analytical data generated by a mobile or stationary laboratory in support of compliance with air permits must be obtained from a NELAC (National Environmental Laboratory Accreditation Conference) accredited laboratory under the Texas Laboratory Accreditation Program or meet one of several exemptions. Specific information concerning which laboratories must be accredited and which are exempt may be found in 30 TAC § 25.4 and § 25.6.

Mr. Christopher Abshire
Page 2
March 1, 2010

Re: Permit Numbers 19637 and PSDTX767M2

For additional information regarding the laboratory accreditation program and a list of accredited laboratories and their fields of accreditation, please see the following Web site:


http://www.tceq.state.tx.us/compliance/compliance_support/qa/env_lab_accreditation.html

For questions regarding the accreditation program, you may contact the Texas Laboratory Accreditation Program at (512) 239-3754 or by e-mail at labprgms@tceq.state.tx.us.

Your cooperation in this matter is appreciated. If you need further information or have any questions, please contact Mr. David Havens at (512) 239-1275 or write to the Texas Commission on Environmental Quality, Office of Permitting and Registration, Air Permits Division, MC-163, P.O. Box 13087, Austin, Texas 78711-3087.

This action is taken under authority delegated by the Executive Director of the Texas Commission on Environmental Quality.

Sincerely,



Steve Hagle, P.E., Director
Air Permits Division
Office of Permitting and Registration
Texas Commission on Environmental Quality

SH/DH/kp

Enclosure

cc: Bureau Chief of Air Quality Control, Health and Human Services Department, City of Houston, Houston
Director, Environmental Public Health Division, Harris County Public Health and Environmental Services, Pasadena
Air Section Manager, Region 12 - Houston
Air Permits Section Chief, U.S. Environmental Protection Agency, Region 6, Dallas

Project Number: 153488

TEXAS COMMISSION ON ENVIRONMENTAL QUALITY
AIR QUALITY PERMIT



A PERMIT IS HEREBY ISSUED TO
Valero Refining-Texas, L.P.
AUTHORIZING THE CONTINUED OPERATION OF
Houston Refinery-Package Boilers
LOCATED AT
Houston, Harris County, Texas
LATITUDE 29° 43' 24" LONGITUDE 095° 15' 11"

1. **Facilities** covered by this permit shall be constructed and operated as specified in the application for the permit. All representations regarding construction plans and operation procedures contained in the permit application shall be conditions upon which the permit is issued. Variations from these representations shall be unlawful unless the permit holder first makes application to the Texas Commission on Environmental Quality (commission) Executive Director to amend this permit in that regard and such amendment is approved. [Title 30 Texas Administrative Code § 116.116 (30 TAC § 116.116)]
2. **Voiding of Permit.** A permit or permit amendment is automatically void if the holder fails to begin construction within 18 months of date of issuance, discontinues construction for more than 18 consecutive months prior to completion, or fails to complete construction within a reasonable time. Upon request, the executive director may grant a onetime 18-month extension of the date to begin construction. [30 TAC § 116.120(a)]
3. **Construction Progress.** Start of construction, construction interruptions exceeding 45 days, and completion of construction shall be reported to the appropriate regional office of the commission not later than 15 working days after occurrence of the event. [30 TAC § 116.115(b)(2)(A)]
4. **Start-up Notification.** The appropriate air program regional office shall be notified prior to the commencement of operations of the facilities authorized by the permit in such a manner that a representative of the commission may be present. The permit holder shall provide a separate notification for the commencement of operations for each unit of phased construction, which may involve a series of units commencing operations at different times. Prior to operation of the facilities authorized by the permit, the permit holder shall identify to the Office of Permitting, Remediation, and Registration the source or sources of allowances to be utilized for compliance with Chapter 101, Subchapter H, Division 3 of this title (relating to Mass Emissions Cap and Trade Program). [30 TAC § 116.115(b)(2)(B)]
5. **Sampling Requirements.** If sampling is required, the permit holder shall contact the commission's Office of Compliance and Enforcement prior to sampling to obtain the proper data forms and procedures. All sampling and testing procedures must be approved by the executive director and coordinated with the regional representatives of the commission. The permit holder is also responsible for providing sampling facilities and conducting the sampling operations or contracting with an independent sampling consultant. [30 TAC § 116.115(b)(2)(C)]
6. **Equivalency of Methods.** The permit holder must demonstrate or otherwise justify the equivalency of emission control methods, sampling or other emission testing methods, and monitoring methods proposed as alternatives to methods indicated in the conditions of the permit. Alternative methods shall be applied for in writing and must be reviewed and approved by the executive director prior to their use in fulfilling any requirements of the permit. [30 TAC § 116.115(b)(2)(D)]
7. **Recordkeeping.** The permit holder shall maintain a copy of the permit along with records containing the information and data sufficient to demonstrate compliance with the permit, including production records and operating hours; keep all required records in a file at the plant site. If, however, the facility normally operates unattended, records shall be maintained at the nearest staffed location within Texas specified in the application; make the records available at the request of personnel from the commission or any air pollution control program having jurisdiction; comply with any additional recordkeeping requirements specified in special conditions attached to the permit; and retain information in the file for at least two years following the date that the information or data is obtained. [30 TAC § 116.115(b)(2)(E)]
8. **Maximum Allowable Emission Rates.** The total emissions of air contaminants from any of the sources of emissions must not exceed the values stated on the table attached to the permit entitled "Emission Sources--Maximum Allowable Emission Rates." [30 TAC § 116.115(b)(2)(F)]
9. **Maintenance of Emission Control.** The permitted facilities shall not be operated unless all air pollution emission capture and abatement equipment is maintained in good working order and operating properly during normal facility operations. The permit holder shall provide notification for upsets and maintenance in accordance with § §101.201, 101.211, and 101.221 of this title (relating to Emissions Event Reporting and Recordkeeping Requirements; Scheduled Maintenance, Startup and Shutdown Reporting and Recordkeeping Requirements; and Operational Requirements). [30 TAC § 116.115(b)(2)(G)]
10. **Compliance with Rules.** Acceptance of a permit by an applicant constitutes an acknowledgment and agreement that the permit holder will comply with all rules, regulations, and orders of the commission issued in conformity with the TCAA and the conditions precedent to the granting of the permit. If more than one state or federal rule or regulation or permit condition are applicable, the most stringent limit or condition shall govern and be the standard by which compliance shall be demonstrated. Acceptance includes consent to the entrance of commission employees and agents into the permitted premises at reasonable times to investigate conditions relating to the emission or concentration of air contaminants, including compliance with the permit. [30 TAC § 116.115(b)(2)(H)]
11. This permit may be appealed pursuant to 30 TAC § 50.139.
12. This permit may not be transferred, assigned, or conveyed by the holder except as provided by rule. [30 TAC § 116.110(e)]
13. There may be additional special conditions attached to a permit upon issuance or modification of the permit. Such conditions in a permit may be more restrictive than the requirements of Title 30 of the Texas Administrative Code. [30 TAC § 116.115(c)]
14. **Emissions** from this facility must not cause or contribute to a condition of "air pollution" as defined in TCAA § 382.003(3) or violate TCAA § 382.085, as codified in the Texas Health and Safety Code. If the executive director determines that such a condition or violation occurs, the holder shall implement additional abatement measures as necessary to control or prevent the condition or violation.

PERMIT 19637 and PSD-TX-767M2

Date: November 29, 2004

A handwritten signature in black ink, appearing to read "Glenn Shankle".

Glenn Shankle
Executive Director
Texas Commission on Environmental Quality

SPECIAL CONDITIONS

Permit Numbers 19637 and PSDTX767M2

1. This permit covers only those sources of emissions listed in the attached table entitled ■Emission Sources - Maximum Allowable Emission Rates,• and those sources are limited to the emission limits and other conditions specified in that attached table. Compliance with the annual emission limits shall be based on a rolling 12-month year.

FEDERAL APPLICABILITY

2. Facilities covered by this permit shall comply with all applicable requirements of the U.S. Environmental Protection Agency (EPA) regulations on Standards of Performance for Industrial-Commercial-Institutional Steam Generating Units, Petroleum Refineries, and Stationary Gas Turbines in Title 40 Code of Federal Regulations (40 CFR) Part 60, Subparts A, Db, J, and GG. If any condition of this permit is more stringent than the regulations so incorporated, then for the purposes of complying with this permit, the permit shall govern and be the standard by which compliance shall be demonstrated.

EMISSION STANDARDS AND FUEL SPECIFICATIONS (TURBINE AND DUCT BURNERS)

3. Emission concentrations of nitrogen oxides (NO_x) and carbon monoxide (CO) in the stack gases from the cogeneration trains shall not exceed the following limits:

A. <u>Firing Case</u>	<u>Pollutant</u>	<u>Emission Rate</u>
Turbine Only Firing	NO _x	25 parts per million by volume, dry (ppmvd)
	CO	26 ppmvd
Turbine and Duct Burner Firing	NO _x	26 ppmvd
	CO	43 ppmvd
Duct Burners Only With Fresh Air Firing	NO _x	44 ppmvd
	CO	41 ppmvd

The NO_x emission limits are expressed on a dry basis at 15 percent oxygen (O₂). The CO emission limits are expressed on a dry basis not corrected to 15 percent O₂. Measured concentrations at the exhaust stacks shall be expressed accordingly.

SPECIAL CONDITIONS

Permit Numbers 19637 and PSDTX767M2

Page 2

B. In addition, emissions shall not exceed the following limits:

<u>Emission Unit</u>	<u>Pollutant</u>	<u>Emission Rate</u>
Duct Burners	NO _x (turbine exhaust)	0.10 lb/MMBtu
CG-1 and CG-2 lb/MMBtu	NO _x (fresh air)	0.15
Duct Burners	CO (turbine exhaust)	0.08 lb/MMBtu
CG-1 and CG-2	CO (fresh air)	0.10 lb/MMBtu

Emission limits are based on fuel high heating value.

- Fuel fired in the gas turbines is limited to pipeline-quality natural gas. Fuel fired in the duct burners is limited to a mixture of refinery produced gas and natural gas (refinery gas). The refinery gas shall contain no more than 10 grains hydrogen sulfide (H₂S) per 100 dry standard cubic feet (dscf) in any rolling 12-hour period. Use of any other fuel will require modification to this permit.
- Emissions from the turbines and duct burners shall not exceed 5 percent opacity as determined by EPA Reference Method 9.

EMISSION STANDARDS AND FUEL SPECIFICATIONS (PACKAGE BOILERS AND SELECTIVE CATALYTIC REDUCTION [SCR])

- Emissions for the Package Boilers 1, 2, and 3 (Emission Point Nos. [EPNs] 81BF5601, 81BF5602, and 81BF5603) shall not exceed the following limits: **(3/10)**
 - NO_x: 0.01 lb/MMBtu
 - CO: 0.035 lb/MMBtu.
 - Ammonia (NH₃): 10 ppmvd, corrected to 3 percent excess O₂.

The NO_x heat input-based limit is based upon the higher heating value of the fuel. Compliance with the lb/MMBtu limitations will be demonstrated on a 30-day rolling average corrected as specified in 40 CFR Part 60, Subpart Db. Compliance with the above requirements will also

SPECIAL CONDITIONS

Permit Numbers 19637 and PSDTX767M2

Page 3

serve to satisfy the requirements of Paragraph No. 27(a) of Consent Decree (CD), Civil Action No. SA-05-CA-0569, related to the system wide 365-day rolling NO_x average from covered heaters and boilers. The CD requires a 365-day rolling average to demonstrate NO_x limitations compliance, which can be calculated from using 30-day rolling averages of the previous 12 months. The permit holder shall demonstrate during the initial compliance stack sampling that best available control technology has been applied by demonstrating compliance with the above performance specifications on a one-hour basis. The hourly emission limits in the maximum allowable emission rates table (MAERT) shall apply at all times.

Emissions from the NH₃ tank shall be minimized by use of a vapor-balance system to route vapors displaced from the tanks back to the truck during filling operations.

7. Audio, olfactory, and visual checks for NH₃ shall be made once per shift within the NH₃ storage area. No later than one hour following detection of a leak, plant personnel shall take the following actions:
 - A. Locate and isolate the leak.
 - B. Commence repair or replacement of the leaking component as appropriate.
 - C. Use a leak collection/containment system to control the leak until repair or replacement can be made. **(5/04)**
8. Fuel for the Package Boilers Nos. 1, 2, and 3 (EPNs 81BF5601, 81BF5602, and 81BF5603) authorized by this permit shall be refinery fuel gas. The refinery fuel gas shall contain no more than 10 grains H₂S per 100 dscf on a 12-hour rolling average. Use of any other fuel will require authorization from the permitting authority. **(5/04)**
9. Opacity of emissions from the package boilers shall not exceed 5 percent average over a six-minute period. **(5/04)**

INITIAL DETERMINATION OF COMPLIANCE (TURBINE AND DUCT BURNERS)

10. The holder of this permit shall perform stack sampling and other testing, as required, to initially establish the actual pattern and quantities of air contaminants being emitted into the atmosphere from each turbine and duct burner. Sampling must be conducted in accordance with appropriate procedures of the Texas Commission on Environmental Quality (TCEQ) Sampling Procedures Manual and in accordance with EPA Reference Methods 201A and 202

SPECIAL CONDITIONS

Permit Numbers 19637 and PSDTX767M2

Page 4

or Reference Method 5, modified to include back-half condensibles, for the concentration of particulate matter (PM) with the allowance for ambient particulates (i.e., subtracting out particulates entering the turbine), EPA Reference Method 8 for sulfur dioxide (SO₂), Reference Method 9 for opacity (consisting of 30 six-minute readings as provided in 40 CFR • 60.11[b]), Reference Method 10 for the concentration of CO, Reference Method 20 for the concentrations of NO_x and O₂ and Reference Method 25 for volatile organic compounds (VOC). Fuel sampling using the methods and procedures of 40 CFR • 60.335(d) may be conducted in lieu of stack sampling for SO₂. Compliance with the maximum allowable emission rates of Special Condition No. 1 shall be based on 100 percent conversion of the sulfur in the fuel to SO₂. The holder of this permit is responsible for providing sampling and testing facilities and conducting the sampling and testing operation at his expense.

- A. The TCEQ Houston Regional Office shall be contacted as soon as testing is scheduled but not less than 45 days prior to sampling to schedule a pretest meeting.

The notice shall include:

- (1) Date for pretest meeting.
- (2) Date sampling will occur.
- (3) Name of firm conducting sampling.
- (4) Type of sampling equipment to be used.
- (5) Method or procedure to be used in sampling.

The purpose of the pretest meeting is to review and formalize the necessary sampling and testing procedures, to provide the proper data forms for recording pertinent data, to identify each operating parameter which is significant to maintaining emission compliance, and to review the format procedures for submitting the test reports.

A written proposed description of any deviation from sampling procedures specified in these permit conditions or any TCEQ or the EPA sampling procedures shall be made available to the TCEQ at or prior to the pretest meeting. The TCEQ Regional Director and the EPA Region 6 in Dallas shall approve or disapprove of any deviation from specified sampling procedures. Requests to waive testing for any pollutant specified in paragraphs B and D of this condition shall be submitted to the TCEQ Office of Permitting and Registration, Air Permits Division. Test waivers and alternate/equivalent procedure proposals for New Source Performance Standards (NSPS) testing which must

SPECIAL CONDITIONS

Permit Numbers 19637 and PSDTX767M2

Page 5

have the EPA approval shall be submitted to the TCEQ Regional Director. Any equivalent test procedures or any test waivers must be approved by both the TCEQ and the EPA prior to the date required in paragraph E of this condition for conducting the tests.

- B. Air emissions from the gas turbines to be tested for at a full load while the duct burners are fired at a full load include (but are not limited to) the following: NO_x, O₂, CO, VOC, PM, SO₂, and opacity. This testing will be used to demonstrate initial compliance with Special Condition Nos. 1 and 3.
- C. The NO_x, O₂, and CO from the turbines alone shall be sampled concurrently at four turbine loads, including the minimum point in the normal operating range and the peak load for the atmospheric conditions occurring during the test. The NO_x and CO concentrations shall be corrected and reported according to Special Condition No. 3. This testing will be used to demonstrate initial compliance with Special Condition Nos. 1 and 3.
- D. Air emissions from the duct burners to be tested for at a full load while the turbines are not operating include (but are not limited to) the following: PM, NO_x, O₂, CO, and opacity. This testing will be used to demonstrate initial compliance with Special Condition Nos. 1, 2, and 3.
- E. Sampling shall occur within 60 days after achieving the maximum production rate at which the turbines will be operated but no later than 180 days after initial start-up of the turbines. Sampling as described in this condition will also be performed within 60 days of the date this permit is amended. Additional sampling shall occur as may be required by the TCEQ or the EPA.
- F. Within 60 days after the completion of the testing and sampling required herein, three copies of the sampling report shall be distributed as follows:

One copy to the TCEQ Houston Regional Office.

One copy to the TCEQ Office of Permitting and Registration, Air Permits
Division, Austin.

One copy to the EPA Region 6 in Dallas.

SPECIAL CONDITIONS

Permit Numbers 19637 and PSDTX767M2

Page 6

INITIAL DETERMINATION OF COMPLIANCE (BOILERS AND SCR)

11. The holder of this permit shall perform stack sampling and other testing as required to establish the actual pattern and quantities of air contaminants being emitted into the atmosphere by the Package Boilers 1, 2, and 3 (EPNs 81BF5601, 81BF5602, and 81BF5603). The testing required by this special condition for NO_x and CO shall be used to determine initial compliance with the limits specified in the MAERT. Initial compliance with the permit opacity limit of Special Condition No. 9 shall be demonstrated on the basis of compliance with 40 CFR • 60.11(b). Sampling must be conducted in accordance with appropriate procedures of the TCEQ Sampling Procedures Manual and in accordance with the EPA Reference Method 9 for opacity, Reference Method 10 for CO, Reference Method 7E for NO_x, and Reference Method 3 for O₂ or equivalent methods.

The holder of this permit is responsible for providing sampling and testing facilities and conducting the sampling and testing operation at his expense.

- A. The TCEQ Houston Regional Office shall be contacted as soon as testing is scheduled but not less than 45 days prior to sampling to schedule a pretest meeting. The notice shall include:
 - (1) Date for pretest meeting.
 - (2) Date sampling will occur.
 - (3) Name of firm conducting sampling.
 - (4) Type of sampling equipment to be used.
 - (5) Method or procedure to be used in sampling.
 - (6) Proposed method of demonstrating compliance with 40 CFR • 60.48b.

The purpose of the pretest meeting is to review the necessary sampling and testing procedures, to provide the proper data forms for recording pertinent data, and to review the format procedures for submitting the test reports.

A written proposed description of any deviation from sampling procedures specified in permit conditions or the TCEQ or the EPA sampling procedures shall be made available to the TCEQ prior to the pretest meeting. The TCEQ Regional Director shall approve or disapprove of any deviation from specified sampling procedures.

SPECIAL CONDITIONS

Permit Numbers 19637 and PSDTX767M2

Page 7

Requests to waive testing for any pollutant specified in Special Condition No. 11B shall be submitted to the TCEQ Office of Permitting and Registration, Air Permits Division. Test waivers and alternate/equivalent procedure proposals for NSPS testing which must have the EPA approval shall be submitted to the TCEQ Regional Director.

- B. The air contaminants emitted from the boilers to be tested for include (but are not limited to) NO_x, CO, NH₃, O₂, VOC, and opacity. If the boilers are unable to reach the maximum firing rate during testing, then future firing may be limited to the highest firing rate achieved during testing. Furthermore, if the boilers are unable to comply with the emission limits of this permit for any or all of the pollutants of this permit while operating at maximum firing during the test, then future firing will be limited to the maximum emissions-complying firing tested. Additional stack testing may be required for higher firing outside the emissions-complying maximum achieved during the test to be authorized. During the initial stack test, the permit holder may be allowed to fire the boilers at levels up to 15 percent above the firing rate limits represented in the permit amendment application received July 22, 2004. **(11/04)**
- C. Sampling shall occur within 60 days after the facilities achieve maximum production but not later than 180 days after initial start-up of the facilities and at such other times as may be required by the Executive Director of the TCEQ. Requests for additional time to perform stack sampling shall be submitted to the TCEQ Regional Office.

Additional time to comply with the applicable requirements of 40 CFR Part 60 require the EPA approval, and requests shall be submitted to the TCEQ Regional Director.

- D. Two copies of the final sampling report shall be forwarded to the appropriate agencies within 60 days after sampling is completed. Sampling reports shall comply with the attached provisions of Chapter 14 of the TCEQ Sampling Procedures Manual. The reports shall be distributed as follows:

One copy to the TCEQ Houston Regional Office.

One copy to the appropriate local programs **(5/04)**

CONTINUOUS DEMONSTRATION OF COMPLIANCE (TURBINE AND DUCT BURNERS)

12. The holder of this permit shall install, calibrate, maintain, and operate a continuous emission monitoring system (CEMS) to:

SPECIAL CONDITIONS

Permit Numbers 19637 and PSDTX767M2

Page 8

- A. Measure and record the concentrations of NO_x and O₂ at the exhaust stack; and
- B. Measure and record the concentration of CO in the exhaust stack.

The NO_x and CO concentrations shall be corrected and reported according to Special Condition No. 3A.

- C. The CEMS required in Special Condition No. 12A and B shall comply with the following requirements:
 - (1) The CEMS shall meet the design and performance specifications, pass the field tests, and meet the installation requirements and data analysis and reporting requirements specified in the applicable performance specifications in 40 CFR Part 60, Appendix B. The performance specification tests shall be conducted during the sampling required by Special Condition No. 11, and written copies of the results shall be submitted within 60 days of completion of the tests to the TCEQ Houston Regional Office, the TCEQ Office of Permitting and Registration, Air Permits Division in Austin, and the EPA Region 6 in Dallas.
 - (2) The system shall be zeroed and spanned daily and corrective action taken when the 24-hour span drift exceeds two times the amounts specified in 40 CFR Part 60, Appendix B. Each gaseous monitor shall be quality-assured at least quarterly using cylinder gas audits (CGA). The CGA method to be used is contained in 40 CFR Part 60, Appendix F, Procedure 1, •5.1.2. An equivalent method approved by the EPA and TCEQ may be used.
 - (3) The gaseous monitoring data shall be reduced to hourly average concentrations at least once everyday, using a minimum of four equally-spaced data points from each one-hour period. At least 23 hourly averages shall be generated per day.
 - (4) All CGA exceedances greater than ∇ 15 percent accuracy and any unscheduled CEMS downtime shall be reported to the TCEQ Houston Regional Office and the EPA Region 6 in Dallas, and necessary corrective action shall be taken. Unscheduled CEMS downtime is any CEMS downtime not required for daily zero and span checks, quarterly CGAs, and annual relative accuracy test audits. Supplemental stack concentration measurements may be required at the discretion of the TCEQ Regional Director or the EPA.

SPECIAL CONDITIONS

Permit Numbers 19637 and PSDTX767M2

Page 9

- D. The holder of this permit shall install, calibrate, maintain, and operate a continuous steam-to-fuel ratio monitoring system to monitor and record the ratio of injection steam-to-fuel fired in each turbine. The system shall be accurate to ± 5.0 percent and its design shall be approved by the Executive Director of the TCEQ prior to the initial compliance demonstration required under Special Condition No. 10. The system shall be calibrated by means of the initial compliance demonstration required by Special Condition No. 13.
13. The holder of this permit shall monitor sulfur content of the refinery fuel gas fired in the duct burners in accordance with NSPS, Subpart J.
14. After the demonstration of initial compliance required in Special Condition No. 10, the CEMS and steam-to-fuel ratio monitoring required in Special Condition No. 12 shall constitute the methods for demonstrating continuous compliance with the standards. The CEMS and steam-to-fuel ratio monitoring data will be used to evaluate compliance with the emission limitations of Special Condition Nos. 1, 2, and 3.

CONTINUOUS DETERMINATION OF COMPLIANCE (BOILERS AND SCR)

15. The holder of this permit shall install, calibrate, maintain, and operate a CEMS to measure and record the concentrations of NO_x , CO, and diluent gases (O_2 or carbon dioxide [CO_2]), from the Package Boilers 1, 2, and 3 (EPNs 81BF5601, 81BF5602, and 81BF5603).
 - A. The CEMS shall meet the design and performance specifications, pass the field tests, and meet the installation requirements and the data analysis and reporting requirements specified in the applicable Performance Specification Nos. 1, 2, and 6 through 12, 40 CFR Part 60, Appendix B, or an acceptable alternative. A cylinder gas audit or relative accuracy audit may be performed in lieu of the annual relative accuracy test audit required in Appendix F, • 5.1.1. If there are no applicable performance specifications in 40 CFR Part 60, Appendix B, contact the TCEQ Office of Permitting and Registration, Air Permits Division in Austin for requirements to be met. The CEMS shall comply with the following requirements:

The holder of this permit shall assure that the CEMS meets the applicable quality-assurance requirements specified in 40 CFR Part 60, Appendix F, Procedure 1, or an acceptable alternative. Relative accuracy exceedances, as specified in 40 CFR Part 60, Appendix F, • 5.2.3, and any CEMS downtime and all cylinder gas audit exceedances of ± 15 percent accuracy shall be reported semiannually to the appropriate TCEQ Regional Director and the appropriate local air program with jurisdiction, and

SPECIAL CONDITIONS

Permit Numbers 19637 and PSDTX767M2

Page 10

necessary corrective action shall be taken. The CEMS downtime does not include downtime required for daily zero span checks, quarterly CGAs and annual relative accuracy test audits. Supplemental stack concentration measurements may be required at the discretion of the appropriate TCEQ Regional Director.

- B. The monitoring data shall be reduced to hourly average values at least once everyday, using a minimum of four equally-spaced data points from each one-hour period. At least two valid data points shall be generated during the hourly period in which zero and span is performed.
 - C. All monitoring data and quality-assurance data shall be maintained by the source for a period of five years and shall be made available to the TCEQ Executive Director or a designated representative upon request. The hourly average data from the CEMS may be used to determine compliance with the conditions of this permit. Hourly average concentrations from the boilers shall be summed to ton per year each month and used to determine compliance with the emission limits of this permit on a rolling 12-months. **(5/04)**
 - D. The appropriate TCEQ Regional Office shall be notified at least 21 days prior to any required relative accuracy test audit in order to provide them the opportunity to observe the testing. **(11/04)**
16. The holder of this permit shall additionally install, calibrate, maintain, and operate continuous monitoring systems to monitor and record the average hourly refinery fuel gas consumption of the boilers. The systems shall be accurate to ± 5.0 percent of the units maximum flow. **(5/04)**
17. The NH_3 concentration in each boiler exhaust stack shall be tested or calculated according to one of the methods listed below and shall be tested or calculated according to frequency listed below. Testing for NH_3 slip is only required on days when the SCR unit is in operation.
- A. The holder of this permit may install, calibrate, maintain, and operate a CEMS to measure and record the concentrations of NH_3 . The NH_3 concentrations shall be corrected and reported in accordance with Special Condition No. 6.
 - B. As an approved alternative, the NH_3 slip may be measured using a sorbent or stain tube device specific for NH_3 measurement in the 5 to 10 parts per million (ppm) range. The frequency of sorbent/stain tube testing shall be daily for the first 60 days of operation, after which the frequency may be reduced to weekly testing if operating procedures have been developed to prevent excess amounts of NH_3 from being introduced in the SCR unit and when operation of the SCR unit has been proven successful with regard to controlling NH_3 slip. Daily sorbent or stain tube testing shall resume when the catalyst is

SPECIAL CONDITIONS

Permit Numbers 19637 and PSDTX767M2

Page 11

within 30 days of its useful life expectancy. These results shall be recorded and used to determine compliance with Special Condition No. 6.

- C. As an approved alternative to sorbent or stain tube testing or an NH₃ CEMS, the permit holder may install and operate a second NO_x CEMS probe located between the firebox and the SCR, upstream of the stack NO_x CEMS, which may be used in association with the SCR efficiency and NH₃ injection rate to estimate NH₃ slip. This condition shall not be construed to set a minimum NO_x reduction efficiency on the SCR unit. These results shall be recorded and used to determine compliance with Special Condition No. 6.
- D. If the sorbent or stain tube testing indicates an NH₃ slip concentration which exceeds 5 ppm at any time, the permit holder shall begin NH₃ testing by either the Phenol-Nitroprusside Method, the Indophenol Method, or the EPA Conditional Test Method (CTM) 27 on a quarterly basis, in addition to the weekly sorbent or stain tube testing. The quarterly testing shall continue until such time as the SCR unit catalyst is replaced; or if the quarterly testing indicates NH₃ slip is 4 ppm or less, the Phenol-Nitroprusside/Indophenol/CTM 27 tests may be suspended until sorbent or stain tube testing again indicate 5 ppm NH₃ slip or greater. These results shall be recorded and used to determine compliance with Special Condition No. 6.
- E. As an approved alternative to sorbent or stain tube testing, NH₃ CEMS, or a second NO_x CEMS, the permit holder may install and operate a dual stream system of NO_x CEMS at the exit of the SCR. One of the exhaust streams would be routed, in an unconverted state, to one NO_x CEMS and the other exhaust stream would be routed through a NH₃ converter to convert NH₃ to NO_x and then to a second NO_x CEMS. The NH₃ slip concentration shall be calculated from the delta between the two NO_x CEMS readings (converted and unconverted). These results shall be recorded and used to determine compliance with Special Condition No. 6.
- F. Any other method used for measuring NH₃ slip shall require prior approval from the TCEQ Regional Director. **(5/04)**

RECORDKEEPING REQUIREMENTS (TURBINE AND DUCT BURNERS)

- 18. While the turbines are firing, duct burner firing rates are limited to 183 MMBtu/hr. Duct burner firing in a stand-alone mode (without turbine firing) is limited to 375 MMBtu/hr per unit. Records of firing rates (in MMBtu/hr) shall be made and maintained to verify compliance with this condition.

SPECIAL CONDITIONS

Permit Numbers 19637 and PSDTX767M2

Page 12

19. The following information shall be made and maintained by the holder of this permit for a period of two years and shall be made available on request to representatives of the TCEQ, EPA, or any local air pollution control program having jurisdiction:
 - A. Average hourly NO_x, CO, and O₂ concentrations which are monitored pursuant to Special Condition No. 12.
 - B. The results of all fuel sampling conducted pursuant to Special Condition No. 13.
 - C. The results of all stack tests conducted pursuant to Special Condition No. 10.
 - D. All hourly periods during which any fuel other than natural gas is fired in the turbines or refinery gas is fired in the duct burners.
 - E. All hourly periods during which turbine exhaust is vented through a turbine bypass stack.
 - F. All records required to be maintained pursuant to Special Condition Nos. 18 and 27.
 - G. Average hourly steam-to-fuel ratio records which are monitored pursuant to Special Condition No. 12D.

RECORDKEEPING REQUIREMENTS (BOILERS AND SCR)

20. The following records shall be kept at the plant for the life of the permit. All records required in this permit shall be made available at the request of personnel from the TCEQ or any air pollution control agency with jurisdiction.
 - A. A copy of this permit.
 - B. Permit application dated November 2003, and subsequent representations submitted to the TCEQ.
 - C. A complete copy of the testing reports and records of the initial performance testing completed pursuant to Special Condition No. 11 to demonstrate initial compliance.
 - D. Stack sampling results or other air emissions testing (other than CEMS data and NH₃ test data required by Special Condition No. 17) that may be conducted on units authorized under this permit after the date of issuance of this permit. **(5/04)**

SPECIAL CONDITIONS

Permit Numbers 19637 and PSDTX767M2

Page 13

21. The following information shall be maintained by the holder of this permit in a form suitable for inspection for a period of five years after collection, and shall be made immediately available upon request to representatives of the TCEQ or any air pollution control agency with jurisdiction:
 - A. The NO_x, CO, and diluent gases, O₂ or CO₂, CEMS emissions data to demonstrate compliance with the emission rates listed in the MAERT.
 - B. Raw data files of all CEMS data including calibration checks and adjustments and maintenance performed on these systems.
 - C. Records of NH₃ emissions sampling and calculations pursuant to Special Condition No. 20.
 - D. Records of the hours of operation and average daily quantity of refinery fuel gas fired in the boilers. **(5/04)**
 - E. Records of the hours each of the boilers is operated without SCR during May and June 2007. **(5/07)**

REPORTING (TURBINE AND DUCT BURNERS)

22. The holder of this permit shall submit to the TCEQ Houston Regional Office and the EPA Region 6 in Dallas quarterly reports as described in 40 CFR • 60.7. Such reports are required for each emission unit which is required to be continuously monitored pursuant to Special Condition No. 15. In addition to the information specified in 40 CFR • 60.7(c), each report shall contain the hours of operation of the facility and a report summary of the periods of noncomplying emissions and CEMS downtimes by cause.
23. For the purposes of reporting pursuant to Special Condition No. 22, noncomplying emissions are defined as follows:
 - A. Noncomplying emissions of NO_x are each one-hour period of operation, except during start-up or shutdown (defined as turbine operation at less than 30 percent of base load, not to exceed four hours), during which the average emissions of NO_x, as measured and recorded by the CEMS, exceed the emission limitations of Special Condition No. 3A.

SPECIAL CONDITIONS

Permit Numbers 19637 and PSDTX767M2

Page 14

Such emissions will be violations of the NO_x emission limitations of Special Condition Nos. 1 and 3A.

- B. Noncomplying emissions of CO are defined as each one-hour period of operation, except during start-up or shutdown, during which the average emissions of CO exceed the emission limitations of Special Condition No. 3A. Noncomplying emissions of CO are also any period of gas turbine operation, except during start-up or shutdown, during which exhaust emissions are vented through a bypass stack. Such emissions will be violations of the CO emission limitations of Special Condition Nos. 1 and 3A.
- C. During periods when the NO_x CEMS are inoperative, continuous compliance shall be demonstrated by the steam-to-fuel ratio required by Special Condition No.12D. Compliance shall be demonstrated by maintaining the steam-to-fuel ratio validated in the initial compliance test required in Special Condition No. 10.

REPORTING

- 24. The holder of this permit shall submit to the TCEQ Houston Regional Office, the local air program with jurisdiction, and the Air Enforcement Branch of EPA in Dallas semiannual reports as described in 40 CFR •60.7. Such reports are required for each emission unit which is required to be continuously monitored pursuant to this permit.

CONTEMPORANEOUS REDUCTION

- 25. Within six months of the start-up of the cogeneration facilities of this permit, the grandfathered Low Pressure Boilers identified as Unit Nos. BS-1, BS-2, BS-3, BS-5, BS-6, and BS-11 shall be shut down and rendered permanently inoperable. Grandfathered Low Pressure Boilers identified as Unit Nos. BS-4 and BS-7 shall be operated as standby units and records kept to demonstrate that these units are only operated when there is an equivalent reduction of steam from another unit at the complex. Records of hours of operation and steam generation shall be maintained to document that the operation of these boilers does not result in an increase in steam at the complex. When Boilers BS-4 and BS-7 are operated in conjunction with these cogeneration units no more than 480,000 pounds per hour of steam shall be produced.

SPECIAL CONDITIONS

Permit Numbers 19637 and PSDTX767M2

Page 15

SHUTDOWN OF EQUIPMENT

26. A reasonable shakedown period, not to exceed 180 days will be allowed for the new Package Boilers 1, 2, and 3 (EPNs 81BF5601, 81BF5602, and 81BF5603) and SCR. Upon a successful start of operation for the new package boilers and SCR, the two existing cogeneration turbines and associated duct burners (EPNs CG-1 and CG-2) will shut down. **(5/04)**

OPERATIONAL LIMITATIONS

27. Package Boilers 1, 2, and 3 (EPNs 81BF5601, 81BF5602, and 81BF5603) are authorized to operate without SCR for a period not to exceed 336 hours during May and June 2007. Only one boiler may be operated without SCR at any time. **(5/07)**

Dated March 1, 2010

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

Permit Numbers 19637 and PSD-TX-767M2

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

AIR CONTAMINANTS DATA

Emission Point No. (EPN) (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr (4)	TPY (5)
-				
Case I: Turbine and Duct Burner Firing Simultaneously				
CG-1	18 MW (ISO) Westinghouse Model 191 Gas Turbine with 183 MMBtu/hr Fired Duct Burner	NO _x	41.4	181
		CO	38.0	166
		VOC	3.7	16
		PM	7.5	24
		SO ₂	4.6	20
CG-2	18 MW (ISO) Westinghouse Model 191 Gas Turbine with 183 MMBtu/hr Fired Duct Burner	NO _x	41.4	181
		CO	38.0	166
		VOC	3.7	16
		PM	7.5	24
		SO ₂	4.6	20
CG-3	Fugitive VOC (6)	VOC	0.4	2

* Emission rates are based on and the facilities are limited by a maximum operating schedule of 8,760 hours per year.

Case II: Duct Burner Firing Only

CG-1	375 MMBtu/hr (HHV) Duct Burner	NO _x	56.2	38
		CO	37.5	26
		VOC	6.0	4
		PM	12.5	6
		SO ₂	8.8	6
CG-2	375 MMBtu/hr (HHV) Duct Burner	NO _x	56.2	38
		CO	37.5	26
		VOC	6.0	4
		PM	12.5	6
		SO ₂	8.8	6

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

AIR CONTAMINANTS DATA

EPN (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr (4)	TPY (5)

Total emissions from the combined operation of both Duct Burners (EPNs CG-1 and CG-2) in stand alone mode are as follows:

	Two 375 MMBtu/hr (HHV) Duct Burners	NO _x		38
		CO		26
		VOC		4
		PM		6
		SO ₂		6
CG-3	Fugitive VOC (6)	VOC	0.4	<1

Case III: Turbine Only Firing

CG-1	18 MW (ISO) Westinghouse Model 191 Gas Turbine	NO _x	23.1	101
		CO	23.4	102
		VOC	0.8	4
		PM	1.5	7
		SO ₂	0.2	<1
CG-2	18 MW (ISO) Westinghouse Model 191 Gas Turbine	NO _x	23.1	101
		CO	23.4	102
		VOC	0.8	4
		PM	1.5	7
		SO ₂	0.2	<1
CG-3	Fugitive VOC (6)	VOC	0.4	2

* Emission rates are based on, and limited by, the turbines in stand alone mode and a maximum operating schedule of 8,760 hours per year.

Compliance with the annual emission limits and operating schedules is based on a rolling 12-month year rather than the calendar year.

Boilers - Firing Refinery Fuel Gas:

81BF5601	No. 1 Package Boiler (366 MMBtu/hr)	NO _x (9)	3.95
		CO	13.63
		VOC	1.83
		PM	3.66
		SO _x	9.10

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

AIR CONTAMINANTS DATA

EPN (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr (4)	TPY (5)
		NH ₃ (9)	1.83	
81BF5602	No. 2 Package Boiler (366 MMBtu/hr)	NO _x (9)	3.95	
		CO	13.63	
		VOC	1.83	
		PM	3.66	
		SO _x	9.10	
		NH ₃ (9)	1.83	
81BF5603	No. 3 Package Boiler (366 MMBtu/hr)	NO _x (9)	3.95	
		CO	13.63	
		VOC	1.83	
		PM	3.66	
		SO _x	9.10	
		NH ₃ (9)	1.83	
81BF5601, 81BF5602, and 81BF5603	Package Boilers (Nos. 1, 2, and 3)	NO _x		35.5
		CO		131.5
		VOC		20.4
		PM		26.0
		SO _x		43.9
		NH ₃		16.0
81 FUG	81FUG	NH ₃	0.01	0.04
		VOC	1.0	4.0

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

- (1) Emission point identification - emission point number from plot plan.
- (2) Specific point source name.
 - ISO - Rated electric output at International Standards Organization standard day conditions of 59°F, 1 atmosphere, and 60 percent relative humidity.
 - HHV - high heating value
- (3) VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1
 - NO_x - total oxides of nitrogen
 - SO₂ - sulfur dioxide
 - PM - particulate matter suspended in the atmosphere, including PM₁₀.
 - PM₁₀ - particulate matter equal to or less than 10 microns in diameter. Where PM is not listed, it shall be assumed that no PM greater than 10 microns is emitted.
 - CO - carbon monoxide
 - NH₃ - Ammonia
- (4) Turbine maximum hourly emissions based on minimum ambient temperature.
- (5) Turbine annual emissions based on base load at average annual ambient temperature of 68°F.
- (6) Fugitive emissions are an estimate only and should not be considered as a maximum allowable emission rate.
- (7) Hourly rates are based on maximum firing rate and a maximum operating schedule of 8,760 hours.
- (8) Compliance with annual emission limits is based on a rolling 12-month period.
- (9) During May and June 2007 these package boilers may be operated without SCR, only one at a time, for no more than a total of 336 hours. Allowable emissions for each boiler when operated without SCR are 13.18 lb/hr for NO_x, zero for NH₃, and same as above for CO, VOC, PM, and SO_x.

Dated May 18, 2007