

# Statement of Basis of the Federal Operating Permit

Akzo Nobel Surface Chemistry LLC

Site/Area Name: Akzo Nobel Surface Chemistry Houston Plant

Physical location: 15200 Almeda Road

Nearest City: Houston

County: Fort Bend

Permit Number: O1328

Project Type: Minor Revision

Standard Industrial Classification (SIC) Code: 2843

SIC Name: Surface Active Agents

This Statement of Basis sets forth the legal and factual basis for the draft changes to the permit conditions resulting from the minor revision project in accordance with 30 TAC §122.201(a)(4). The applicant has submitted an application for a minor permit revision per §§ 122.215-217. This document may include the following information:

- A description of the facility/area process description;
- A description of the revision project;
- A basis for applying permit shields;
- A list of the federal regulatory applicability determinations;
- A table listing the determination of applicable requirements;
- A list of the New Source Review Requirements;
- The rationale for periodic monitoring methods selected;
- The rationale for compliance assurance methods selected;
- A compliance status; and
- A list of available unit attribute forms.

Prepared on: March 12, 2014

## Operating Permit Basis of Determination

### Description of Revisions

Akzo Nobel Surface Chemistry LLC, Houston Plant is a surface active agents facility which was issued a Federal Operating Permit (FOP) in accordance with 30 TAC Chapter 122 on March 21, 2011. A minor revision application was received by TCEQ on January 7, 2014 for the addition of 40 CFR 63, Subpart ZZZZ requirements for four emergency reciprocating internal combustion engines; for updating the preconstruction authorization for unit K-201, and to incorporate by reference an amendment to NSR permit 9600.

### Permit Area Process Description

The AkzoNobel Houston Plant consists of several process units. In the A-100, A-200, and A-300 processes, elemental sulfur is reacted with oxygen to produce SO<sub>2</sub> in the sulfur burner. In the presence of a catalyst, SO<sub>2</sub> is converted to SO<sub>3</sub> by reacting SO<sub>2</sub> with O<sub>2</sub>. SO<sub>3</sub> is then used to sulfonate docecyl benzene or other organic compounds to produce sulfonic acid.

The K-100 process manufactures polymerized polyols and amides. The K-200 process produces phenol formaldehyde resins in a heated reactor. The K-201 Reactor process makes amides, amide ester, ester amine, diamide, imidazoline and formaldehyde resins in a batch process. The K-300 and K-301 processes manufacture calcium sulfonates. The K-400 process makes phosphate esters. The K-500 process manufactures phosphate esters and amides. The K-600 process produces phosphate esters, carboxylated nonionic surfactant, quarternary ammonium compounds, acid salts, and polymerization polyols.

There are 7 oxylation reactor systems designated as R100, R200, R300, R400, R500 (V500), R600 (V600), and R700 (V700). The end products are surfactants, which are typically used in oil field, household and industrial cleaning, and agricultural applications.

The LUWA unit is an evaporation process for the blending and removal of solvents from calcium sulfonate.

Two Plant Boilers supply the plant with steam. Boiler B-4, rated at 39.6 MM/Btu, normally burns gas, but No. 2 fuel oil can also be used. Boiler B-5, rated at 39.7 MM/Btu, uses natural gas as fuel.

### FOPs at Site

The “application area” consists of the emission units and that portion of the site included in the application and this permit. Multiple FOPs may be issued to a site in accordance with 30 TAC § 122.201(e). When there is only one area for the site, then the application information and permit will include all units at the site. Additional FOPs that exist at the site, if any, are listed below.

Additional FOPs: None

### Major Source Pollutants

The table below specifies the pollutants for which the site is a major source:

Major Pollutants	VOC
------------------	-----

### Reading State of Texas’s Federal Operating Permit

The Title V Federal Operating Permit (FOP) lists all state and federal air emission regulations and New Source Review (NSR) authorizations (collectively known as “applicable requirements”) that apply at a particular site or permit area (in the event a site has multiple FOPs). **The FOP does not authorize new emissions or new construction activities.** The FOP begins with an introductory page which is common to all Title V permits. This page gives the details of the company, states the authority of the issuing agency, requires the company to

operate in accordance with this permit and 30 Texas Administrative Code (TAC) Chapter 122, requires adherence with NSR requirements of 30 TAC Chapter 116, and finally indicates the permit number and the issuance date.

This is followed by the table of contents, which is generally composed of the following elements. Not all permits will have all of the elements.

- General Terms and Conditions
- Special Terms and Conditions
  - Emissions Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting
  - Additional Monitoring Requirements
  - New Source Review Authorization Requirements
  - Compliance Requirements
  - Protection of Stratosphere Ozone
  - Permit Location
  - Permit Shield (30 TAC § 122.148)
- Attachments
  - Applicable Requirements Summary
    - Unit Summary
    - Applicable Requirements Summary
  - Additional Monitoring Requirements
  - Permit Shield
  - New Source Review Authorization References
  - Compliance Plan
  - Alternative Requirements
- Appendix A
  - Acronym list

## General Terms and Conditions

The General Terms and Conditions are the same and appear in all permits. The first paragraph lists the specific citations for 30 TAC Chapter 122 requirements that apply to all Title V permit holders. The second paragraph describes the requirements for record retention. The third paragraph provides details for voiding the permit, if applicable. The fourth paragraph states that the permit holder shall comply with the requirements of 30 TAC Chapter 116 by obtaining a New Source Review authorization prior to new construction or modification of emission units located in the area covered by this permit. The fifth paragraph provides details on submission of reports required by the permit.

## Special Terms and Conditions

Emissions Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting. The TCEQ has designated certain applicable requirements as site-wide requirements. A site-wide requirement is a requirement that applies uniformly to all the units or activities at the site. Units with only site-wide requirements are addressed on Form OP-REQ1 and are not required to be listed separately on a OP-UA Form or Form OP-SUM. Form OP-SUM must list all units addressed in the application and provide identifying information, applicable OP-UA Forms, and preconstruction authorizations. The various OP-UA Forms provide the characteristics of each unit from which applicable requirements are established. Some exceptions exist as a few units may have both site-wide requirements and unit specific requirements.

Other conditions. The other entries under special terms and conditions are in general terms referring to compliance with the more detailed data listed in the attachments.

## Attachments

**Applicable Requirements Summary.** The first attachment, the Applicable Requirements Summary, has two tables, addressing unit specific requirements. The first table, the Unit Summary, includes a list of units with applicable requirements, the unit type, the applicable regulation, and the requirement driver. The intent of the requirement driver is to inform the reader that a given unit may have several different operating scenarios and the differences between those operating scenarios.

The applicable requirements summary table provides the detailed citations of the rules that apply to the various units. For each unit and operating scenario, there is an added modifier called the “index number,” detailed citations specifying monitoring and testing requirements, recordkeeping requirements, and reporting requirements. The data for this table are based on data supplied by the applicant on the OP-SUM and various OP-UA forms.

**Additional Monitoring Requirement.** The next attachment includes additional monitoring the applicant must perform to ensure compliance with the applicable standard. Compliance assurance monitoring (CAM) is often required to provide a reasonable assurance of compliance with applicable emission limitations/standards for large emission units that use control devices to achieve compliance with applicant requirements. When necessary, periodic monitoring (PM) requirements are specified for certain parameters (i.e. feed rates, flow rates, temperature, fuel type and consumption, etc.) to determine if a term and condition or emission unit is operating within specified limits to control emissions. These additional monitoring approaches may be required for two reasons. First, the applicable rules do not adequately specify monitoring requirements (exception- Maximum Achievable Control Technology Standards (MACTs) generally have sufficient monitoring), and second, monitoring may be required to fill gaps in the monitoring requirements of certain applicable requirements. In situations where the NSR permit is the applicable requirement requiring extra monitoring for a specific emission unit, the preferred solution is to have the monitoring requirements in the NSR permit updated so that all NSR requirements are consolidated in the NSR permit.

**Permit Shield.** A permit may or may not have a permit shield, depending on whether an applicant has applied for, and justified the granting of, a permit shield. A permit shield is a special condition included in the permit document stating that compliance with the conditions of the permit shall be deemed compliance with the specified potentially applicable requirement(s) or specified applicable state-only requirement(s).

**New Source Review Authorization References.** All activities which are related to emissions in the state of Texas must have a NSR authorization prior to beginning construction. This section lists all units in the permit and the NSR authorization that allowed the unit to be constructed or modified. Units that do not have unit specific applicable requirements other than the NSR authorization do not need to be listed in this attachment. While NSR permits are not physically a part of the Title V permit, they are legally incorporated into the Title V permit by reference. Those NSR permits whose emissions exceed certain PSD/NA thresholds must also undergo a Federal review of federally regulated pollutants in addition to review for state regulated pollutants.

**Compliance Plan.** A permit may have a compliance schedule attachment for listing corrective actions plans for any emission unit that is out of compliance with an applicable requirement.

**Alternative Requirements.** This attachment will list any alternative monitoring plans or alternative means of compliance for applicable requirements that have been approved by the EPA Administrator and/or the TCEQ Executive Director.

## Appendix A

**Acronym list.** This attachment lists the common acronyms used when discussing the FOPs.

### **Stationary vents subject to 30 TAC Chapter 111, Subchapter A, § 111.111(a)(1)(B) addressed in the Special Terms and Conditions**

The site contains stationary vents with a flowrate less than 100,000 actual cubic feet per minute (acfm) and constructed after January 31, 1972 which are limited, over a six-minute average, to 20% opacity as required by 30 TAC § 111.111(a)(1)(B). As a site may have a large number of stationary vents that fall into this category, they are not required to be listed individually in the permit's Applicable Requirement Summary. This is consistent with EPA's White Paper for Streamlined Development of Part 70 Permit Applications, July 10, 1995, that states that requirements that apply identically to emission units at a site can be treated on a generic basis such as source-wide opacity limits.

Periodic monitoring is specified in Special Term and Condition 3 for stationary vents subject to 30 TAC § 111.111(a)(1)(B) to verify compliance with the 20% opacity limit. These vents are not expected to produce visible emissions during normal operation. The TCEQ evaluated the probability of these sources violating the opacity standards and determined that there is a very low potential that an opacity standard would be exceeded. It was determined that continuous monitoring for these sources is not warranted as there would be very limited environmental benefit in continuously monitoring sources that have a low potential to produce visible emissions. Therefore, the TCEQ set the visible observation monitoring frequency for these sources to once per calendar quarter.

The TCEQ has exempted vents that are not capable of producing visible emissions from periodic monitoring requirements. These vents include sources of colorless VOCs, non-fuming liquids, and other materials that cannot produce emissions that obstruct the transmission of light. Passive ventilation vents, such as plumbing vents, are also included in this category. Since this category of vents are not capable of producing opacity due to the physical or chemical characteristics of the emission source, periodic monitoring is not required as it would not yield any additional data to assure compliance with the 20% opacity standard of 30 TAC § 111.111(a)(1)(B).

In the event that visible emissions are detected, either through the quarterly observation or other credible evidence, such as observations from company personnel, the permit holder shall either report a deviation or perform a Test Method 9 observation to determine the opacity consistent with the 6-minute averaging time specified in 30 TAC § 111.111(a)(1)(B). An additional provision is included to monitor combustion sources more frequently than quarterly if alternate fuels are burned for periods greater than 24 consecutive hours. This will address possible emissions that may arise when switching fuel types.

### **Stationary Vents subject to 30 TAC Chapter 111 not addressed in the Special Terms and Conditions**

All other stationary vents subject to 30 TAC Chapter 111 not covered in the Special Terms and Conditions are listed in the permit's Applicable Requirement Summary. The basis for the applicability determinations for these vents are listed in the Determination of Applicable Requirements table.

## Federal Regulatory Applicability Determinations

The following chart summarizes the applicability of the principal air pollution regulatory programs to the permit area:

<b>Regulatory Program</b>	<b>Applicability (Yes/No)</b>
Prevention of Significant Deterioration (PSD)	No
Nonattainment New Source Review (NNSR)	No
Minor NSR	Yes
40 CFR Part 60 - New Source Performance Standards	Yes
40 CFR Part 61 - National Emission Standards for Hazardous Air Pollutants (NESHAPs)	No
40 CFR Part 63 - NESHAPs for Source Categories	Yes
Title IV (Acid Rain) of the Clean Air Act (CAA)	No
Title V (Federal Operating Permits) of the CAA	Yes
Title VI (Stratospheric Ozone Protection) of the CAA	Yes
CAIR (Clean Air Interstate Rule)	No

### Basis for Applying Permit Shields

An operating permit applicant has the opportunity to specifically request a permit shield to document that specific applicable requirements do not apply to emission units in the permit. A permit shield is a special condition stating that compliance with the conditions of the permit shall be deemed compliance with the specified potentially applicable requirements or specified potentially applicable state-only requirements. A permit shield has been requested in the application for specific emission units. For the permit shield requests that have been approved, the basis of determination for regulations that the owner/operator need not comply with are located in the "Permit Shield" attachment of the permit.

### Insignificant Activities

In general, units not meeting the criteria for inclusion on either Form OP-SUM or Form OP-REQ1 are not required to be addressed in the operating permit application. Examples of these types of units include, but are not limited to, the following:

1. Office activities such as photocopying, blueprint copying, and photographic processes.
2. Sanitary sewage collection and treatment facilities other than those used to incinerate wastewater treatment plant sludge. Stacks or vents for sanitary sewer plumbing traps are also included.
3. Food preparation facilities including, but not limited to, restaurants and cafeterias used for preparing food or beverages primarily for consumption on the premises.
4. Outdoor barbecue pits, campfires, and fireplaces.
5. Laundry dryers, extractors, and tumblers processing bedding, clothing, or other fabric items generated primarily at the premises. This does not include emissions from dry cleaning systems using perchloroethylene or petroleum solvents.

6. Facilities storing only dry, sweet natural gas, including natural gas pressure regulator vents.
7. Any air separation or other industrial gas production, storage, or packaging facility. Industrial gases, for purposes of this list, include only oxygen, nitrogen, helium, neon, argon, krypton, and xenon.
8. Storage and handling of sealed portable containers, cylinders, or sealed drums.
9. Vehicle exhaust from maintenance or repair shops.
10. Storage and use of non-VOC products or equipment for maintaining motor vehicles operated at the site (including but not limited to, antifreeze and fuel additives).
11. Air contaminant detectors and recorders, combustion controllers and shut-off devices, product analyzers, laboratory analyzers, continuous emissions monitors, other analyzers and monitors, and emissions associated with sampling activities. Exception to this category includes sampling activities that are deemed fugitive emissions and under a regulatory leak detection and repair program.
12. Bench scale laboratory equipment and laboratory equipment used exclusively for chemical and physical analysis, including but not limited to, assorted vacuum producing devices and laboratory fume hoods.
13. Steam vents, steam leaks, and steam safety relief valves, provided the steam (or boiler feedwater) has not contacted other materials or fluids containing regulated air pollutants other than boiler water treatment chemicals.
14. Storage of water that has not contacted other materials or fluids containing regulated air pollutants other than boiler water treatment chemicals.
15. Well cellars.
16. Fire or emergency response equipment and training, including but not limited to, use of fire control equipment including equipment testing and training, and open burning of materials or fuels associated with firefighting training.
17. Crucible or pot furnaces with a brim full capacity of less than 450 cubic inches of any molten metal.
18. Equipment used exclusively for the melting or application of wax.
19. All closed tumblers used for the cleaning or deburring of metal products without abrasive blasting, and all open tumblers with a batch capacity of 1,000 lbs. or less.
20. Shell core and shell mold manufacturing machines.
21. Sand or investment molds with a capacity of 100 lbs. or less used for the casting of metals;
22. Equipment used for inspection of metal products.
23. Equipment used exclusively for rolling, forging, pressing, drawing, spinning, or extruding either hot or cold metals by some mechanical means.
24. Instrument systems utilizing air, natural gas, nitrogen, oxygen, carbon dioxide, helium, neon, argon, krypton, and xenon.
25. Battery recharging areas.
26. Brazing, soldering, or welding equipment.

## **Determination of Applicable Requirements**

The tables below include the applicability determinations for the emission units, the index number(s) where applicable, and all relevant unit attribute information used to form the basis of the applicability determination. The unit attribute information is a description of the physical properties of an emission unit which is used to determine the requirements to which the permit holder must comply. For more information about the descriptions of the unit attributes specific Unit Attribute Forms may be viewed at [www.tceq.texas.gov/permitting/air/nav/air\\_all\\_ua\\_forms.html](http://www.tceq.texas.gov/permitting/air/nav/air_all_ua_forms.html).

A list of unit attribute forms is included at the end of this document. Some examples of unit attributes include construction date; product stored in a tank; boiler fuel type; etc.. Generally, multiple attributes are needed to determine the requirements for a given emission unit and index number. The table below lists these attributes in the column entitled "Basis of Determination." Attributes that demonstrate that an applicable requirement applies will be the factual basis for the specific citations in an applicable requirement that apply to a unit for that index number. The TCEQ Air Permits Division has developed flowcharts for determining applicability of state and federal regulations based on the unit attribute information in a Decision Support System (DSS).

These flowcharts can be accessed via the internet at [www.tceq.texas.gov/permitting/air/nav/air\\_supportsys.html](http://www.tceq.texas.gov/permitting/air/nav/air_supportsys.html). The Air Permits Division staff may also be contacted for assistance at (512) 239-1250.

The attributes for each unit and corresponding index number provide the basis for determining the specific legal citations in an applicable requirement that apply, including emission limitations or standards, monitoring, recordkeeping, and reporting. The rules were found to apply or not apply by using the unit attributes as answers to decision questions found in the flowcharts of the DSS. Some additional attributes indicate which legal citations of a rule apply. The legal citations that apply to each emission unit may be found in the Applicable Requirements Summary table of the draft permit. There may be some entries or rows of units and rules not found in the permit, or if the permit contains a permit shield, repeated in the permit shield area. These are sets of attributes that describe negative applicability, or; in other words, the reason why a potentially applicable requirement does not apply.

If applicability determinations have been made which differ from the available flowcharts, an explanation of the decisions involved in the applicability determination is specified in the column "Changes and Exceptions to RRT." If there were no exceptions to the DSS, then this column has been removed.

The draft permit includes all emission limitations or standards, monitoring, recordkeeping and reporting required by each applicable requirement. If an applicable requirement does not require monitoring, recordkeeping, or reporting, the word "None" will appear in the Applicable Requirements Summary table. If additional periodic monitoring is required for an applicable requirement, it will be explained in detail in the portion of this document entitled "Rationale for Compliance Assurance Monitoring (CAM)/ Periodic Monitoring Methods Selected."

When attributes demonstrate that a unit is not subject to an applicable requirement, the applicant may request a permit shield for those items. The portion of this document entitled "Basis for Applying Permit Shields" specifies which units, if any, have a permit shield.

#### Operational Flexibility

When an emission unit has multiple operating scenarios, it will have a different index number associated with each operating condition. This means that units are permitted to operate under multiple operating conditions. The applicable requirements for each operating condition are determined by a unique set of unit attributes. For example, a tank may store two different products at different points in time. The tank may, therefore, need to comply with two distinct sets of requirements, depending on the product that is stored. Both sets of requirements are included in the permit, so that the permit holder may store either product in the tank.

## Determination of Applicable Requirements

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
ENG-1	40 CFR Part 63, Subpart ZZZZ	63ZZZZ	Brake HP = Stationary RICE with a brake hp less than 100 hp. Construction/Reconstruction Date = Commenced construction or reconstruction before December 19, 2002. Nonindustrial Emergency Engine = Stationary RICE is not defined as a residential emergency RICE, a commercial emergency RICE, or an institutional emergency RICE. Service Type = Emergency use. Stationary RICE Type = Compression ignition engine	The applicable main standard, related standards, monitoring and testing, recordkeeping, and reporting requirements were determined from an analysis of the rule text and the basis of determination.
ENG-2	40 CFR Part 63, Subpart ZZZZ	63ZZZZ	Brake HP = Stationary RICE with a brake hp greater than or equal to 100 and less than 250 hp. Construction/Reconstruction Date = Commenced construction or reconstruction before December 19, 2002. Nonindustrial Emergency Engine = Stationary RICE is not defined as a residential emergency RICE, a commercial emergency RICE, or an institutional emergency RICE. Service Type = Emergency use. Stationary RICE Type = Compression ignition engine	The applicable main standard, related standards, monitoring and testing, recordkeeping, and reporting requirements were determined from an analysis of the rule text and the basis of determination.
ENG-3	40 CFR Part 63, Subpart ZZZZ	63ZZZZ	Brake HP = Stationary RICE with a brake hp greater than or equal to 100 and less than 250 hp. Construction/Reconstruction Date = Commenced construction or reconstruction before December 19, 2002. Nonindustrial Emergency Engine = Stationary RICE is not defined as a residential emergency RICE, a commercial emergency RICE, or an institutional emergency RICE. Service Type = Emergency use. Stationary RICE Type = Compression ignition engine	The applicable main standard, related standards, monitoring and testing, recordkeeping, and reporting requirements were determined from an analysis of the rule text and the basis of determination.
ENG-4	40 CFR Part 63, Subpart ZZZZ	63ZZZZ	Brake HP = Stationary RICE with a brake hp greater than or equal to 100 and less than 250 hp. Construction/Reconstruction Date = Commenced construction or reconstruction before December 19, 2002. Nonindustrial Emergency Engine = Stationary RICE is not defined as a residential emergency RICE, a commercial emergency RICE, or an institutional emergency RICE. Service Type = Emergency use. Stationary RICE Type = Compression ignition engine	The applicable main standard, related standards, monitoring and testing, recordkeeping, and reporting requirements were determined from an analysis of the rule text and the basis of determination.
D101	30 TAC Chapter 115, Storage of VOCs	R5112	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons	
D102	30 TAC Chapter 115, Storage of VOCs	R5112	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons	
DB-100	30 TAC Chapter 115, Storage of VOCs	R5112-10	Tank Description = Tank using a submerged fill pipe True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
DB-200	30 TAC Chapter 115, Storage of VOCs	R5112-15	Tank Description = Tank using a submerged fill pipe True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
DB-50	30 TAC Chapter 115, Storage of VOCs	R5112-16	Tank Description = Tank using a submerged fill pipe True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
ISOTRAILERS	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
ISOTRAILERS	40 CFR Part 60, Subpart Kb	60KB-39	Product Stored = Volatile organic liquid Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)	
T0001	30 TAC Chapter 115, Storage of VOCs	R5112-1	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
T0001	40 CFR Part 60, Subpart K	60K-4	Construction/Modification Date = On or before June 11, 1973	
T0002	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
T0002	40 CFR Part 60, Subpart K	60K-5	Construction/Modification Date = On or before June 11, 1973	
T0003	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
T0003	40 CFR Part 60, Subpart K	60K-6	Construction/Modification Date = On or before June 11, 1973	
T0004	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
T0004	40 CFR Part 60, Subpart K	60K-7	Construction/Modification Date = On or before June 11, 1973	
T0005	30 TAC Chapter 115, Storage of VOCs	R5112-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
T0005	40 CFR Part 60, Subpart K	60K-8	Construction/Modification Date = On or before June 11, 1973	
T0006	30 TAC Chapter 115, Storage of VOCs	R5112-10	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a submerged fill pipe True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
T0006	40 CFR Part 60,	60K-9	Construction/Modification Date = On or before June 11, 1973	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	Subpart K			
T0007	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
T0007	40 CFR Part 60, Subpart K	60K-10	Construction/Modification Date = On or before June 11, 1973	
T0008	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
T0008	40 CFR Part 60, Subpart K	60K-11	Construction/Modification Date = On or before June 11, 1973	
T0009	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
T0009	40 CFR Part 60, Subpart K	60K-12	Construction/Modification Date = On or before June 11, 1973	
T0010	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
T0010	40 CFR Part 60, Subpart K	60K-13	Construction/Modification Date = On or before June 11, 1973	

<b>Unit ID</b>	<b>Regulation</b>	<b>Index Number</b>	<b>Basis of Determination*</b>	<b>Changes and Exceptions to DSS**</b>
To011	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
To011	40 CFR Part 60, Subpart K	60K-14	Construction/Modification Date = On or before June 11, 1973	
To012	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
To013	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
To013	40 CFR Part 60, Subpart K	60K-15	Construction/Modification Date = On or before June 11, 1973	
To017	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
To017	40 CFR Part 60, Subpart Kb	60KB-60	<p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)</p>	
To018	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To018	40 CFR Part 60, Subpart Kb	60KB-61	Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)	
To020	30 TAC Chapter 115, Storage of VOCs	R5112-46	Tank Description = Tank using a submerged fill pipe True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons	
To020	40 CFR Part 60, Subpart Kb	60KB-10	Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 19,800 gallons (75,000 liters) but less than 39,900 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia	
To022	30 TAC Chapter 115, Storage of VOCs	R5112-47	Tank Description = Tank using a submerged fill pipe True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons	
To022	40 CFR Part 60, Subpart Kb	60KB-11	Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 19,800 gallons (75,000 liters) but less than 39,900 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia	
To023	30 TAC Chapter 115, Storage of VOCs	R5112-48	Tank Description = Tank using a submerged fill pipe True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons	
To023	40 CFR Part 60, Subpart Kb	60KB-12	Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 19,800 gallons (75,000 liters) but less than 39,900 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia	
To024	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To024	40 CFR Part 60, Subpart Kb	60KB-13	Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)	
To049	30 TAC Chapter 115, Storage of VOCs	R5112-50	Tank Description = Tank using a submerged fill pipe True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons	
To049	40 CFR Part 60, Subpart Kb	60KB-14	Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 19,800 gallons (75,000 liters) but less than 39,900 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia	
To050	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To050	40 CFR Part 60, Subpart Kb	60KB-15	Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 19,800 gallons (75,000 liters) but less than 39,900 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia	
To098	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To098	40 CFR Part 60, Subpart K	60K-16	Construction/Modification Date = On or before June 11, 1973	
To099	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To099	40 CFR Part 60, Subpart K	60K-17	Construction/Modification Date = On or before June 11, 1973	
To100	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To100	40 CFR Part 60, Subpart K	60K-18	Construction/Modification Date = On or before June 11, 1973	
To101	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To101	40 CFR Part 60, Subpart K	60K-23	Construction/Modification Date = On or before June 11, 1973	
To102	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To102	40 CFR Part 60, Subpart K	60K-24	Construction/Modification Date = On or before June 11, 1973	
To103	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To103	40 CFR Part 60, Subpart K	60K-25	Construction/Modification Date = On or before June 11, 1973	
To104	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To104	40 CFR Part 60, Subpart K	60K-26	Construction/Modification Date = On or before June 11, 1973	
To105	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To105	40 CFR Part 60, Subpart K	60K-27	Construction/Modification Date = On or before June 11, 1973	
To106	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To106	40 CFR Part 60, Subpart K	60K-28	Construction/Modification Date = On or before June 11, 1973	
To107	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	

<b>Unit ID</b>	<b>Regulation</b>	<b>Index Number</b>	<b>Basis of Determination*</b>	<b>Changes and Exceptions to DSS**</b>
To107	40 CFR Part 60, Subpart K	60K-29	Construction/Modification Date = On or before June 11, 1973	
To108	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
To108	40 CFR Part 60, Subpart K	60K-30	Construction/Modification Date = On or before June 11, 1973	
To109	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
To109	40 CFR Part 60, Subpart K	60K-31	Construction/Modification Date = On or before June 11, 1973	
To110	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
To110	40 CFR Part 60, Subpart K	60K-32	Construction/Modification Date = On or before June 11, 1973	
To111	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
To111	40 CFR Part 60,	60K-33	Construction/Modification Date = On or before June 11, 1973	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	Subpart K			
To112	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
To112	40 CFR Part 60, Subpart K	60K-34	Construction/Modification Date = On or before June 11, 1973	
To113	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
To113	40 CFR Part 60, Subpart K	60K-35	Construction/Modification Date = On or before June 11, 1973	
To114	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
To114	40 CFR Part 60, Subpart K	60K-36	Construction/Modification Date = On or before June 11, 1973	
To115	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
To115	40 CFR Part 60, Subpart K	60K-37	Construction/Modification Date = On or before June 11, 1973	

<b>Unit ID</b>	<b>Regulation</b>	<b>Index Number</b>	<b>Basis of Determination*</b>	<b>Changes and Exceptions to DSS**</b>
To116	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To116	40 CFR Part 60, Subpart K	60K-38	Construction/Modification Date = On or before June 11, 1973	
To117	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To117	40 CFR Part 60, Subpart K	60K-39	Construction/Modification Date = On or before June 11, 1973	
To118	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To118	40 CFR Part 60, Subpart K	60K-40	Construction/Modification Date = On or before June 11, 1973	
To119	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To119	40 CFR Part 60, Subpart K	60K-41	Construction/Modification Date = On or before June 11, 1973	
To120	30 TAC Chapter 115, Storage of VOCs	R5112-11	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Tank Description = Tank using a submerged fill pipe True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To120	40 CFR Part 60, Subpart K	60K-42	Construction/Modification Date = On or before June 11, 1973	
To121	30 TAC Chapter 115, Storage of VOCs	R5112-12	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a submerged fill pipe True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To121	40 CFR Part 60, Subpart K	60K-43	Construction/Modification Date = On or before June 11, 1973	
To122	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To122	40 CFR Part 60, Subpart K	60K-44	Construction/Modification Date = On or before June 11, 1973	
To123	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To123	40 CFR Part 60, Subpart K	60K-45	Construction/Modification Date = On or before June 11, 1973	
To124	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To124	40 CFR Part 60, Subpart K	60K-46	Construction/Modification Date = On or before June 11, 1973	
To125	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To125	40 CFR Part 60, Subpart K	60K-47	Construction/Modification Date = On or before June 11, 1973	
To126	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To126	40 CFR Part 60, Subpart K	60K-48	Construction/Modification Date = On or before June 11, 1973	
To127	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To127	40 CFR Part 60, Subpart K	60K-49	Construction/Modification Date = On or before June 11, 1973	
To128	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To128	40 CFR Part 60, Subpart K	60K-50	Construction/Modification Date = On or before June 11, 1973	
To129	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To129	40 CFR Part 60, Subpart K	60K-51	Construction/Modification Date = On or before June 11, 1973	
To130	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To130	40 CFR Part 60, Subpart K	60K-52	Construction/Modification Date = On or before June 11, 1973	
To131	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To131	40 CFR Part 60, Subpart K	60K-53	Construction/Modification Date = On or before June 11, 1973	
To132	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To132	40 CFR Part 60, Subpart K	60K-54	Construction/Modification Date = On or before June 11, 1973	
To133	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To133	40 CFR Part 60, Subpart K	60K-55	Construction/Modification Date = On or before June 11, 1973	
To134	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To134	40 CFR Part 60, Subpart K	60K-56	Construction/Modification Date = On or before June 11, 1973	
To135	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To135	40 CFR Part 60, Subpart K	60K-57	Construction/Modification Date = On or before June 11, 1973	
To136	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	

<b>Unit ID</b>	<b>Regulation</b>	<b>Index Number</b>	<b>Basis of Determination*</b>	<b>Changes and Exceptions to DSS**</b>
To136	40 CFR Part 60, Subpart K	60K-58	Construction/Modification Date = On or before June 11, 1973	
To137	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To137	40 CFR Part 60, Subpart K	60K-59	Construction/Modification Date = On or before June 11, 1973	
To138	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To138	40 CFR Part 60, Subpart K	60K-60	Construction/Modification Date = On or before June 11, 1973	
To139	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To139	40 CFR Part 60, Subpart K	60K-61	Construction/Modification Date = On or before June 11, 1973	
To140	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To140	40 CFR Part 60,	60K-62	Construction/Modification Date = On or before June 11, 1973	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	Subpart K			
To141	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
To141	40 CFR Part 60, Subpart K	60K-63	Construction/Modification Date = On or before June 11, 1973	
To142	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
To142	40 CFR Part 60, Subpart K	60K-64	Construction/Modification Date = On or before June 11, 1973	
To143	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
To143	40 CFR Part 60, Subpart K	60K-65	Construction/Modification Date = On or before June 11, 1973	
To144	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
To144	40 CFR Part 60, Subpart K	60K-66	Construction/Modification Date = On or before June 11, 1973	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
T0145	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
T0145	40 CFR Part 60, Subpart K	60K-67	Construction/Modification Date = On or before June 11, 1973	
T0146	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
T0146	40 CFR Part 60, Subpart K	60K-68	Construction/Modification Date = On or before June 11, 1973	
T0146	40 CFR Part 60, Subpart Ka	60KA-6	Product Stored = Stored product other than a petroleum liquid	
T0147	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
T0147	40 CFR Part 60, Subpart K	60K-69	Construction/Modification Date = On or before June 11, 1973	
T0147	40 CFR Part 60, Subpart Ka	60KA-7	Product Stored = Stored product other than a petroleum liquid	
T0148	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To148	40 CFR Part 60, Subpart K	60K-70	Construction/Modification Date = On or before June 11, 1973	
To148	40 CFR Part 60, Subpart Ka	60KA-8	Product Stored = Stored product other than a petroleum liquid	
To149	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To149	40 CFR Part 60, Subpart K	60K-71	Construction/Modification Date = On or before June 11, 1973	
To149	40 CFR Part 60, Subpart Ka	60KA-9	Product Stored = Stored product other than a petroleum liquid	
To150	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To150	40 CFR Part 60, Subpart K	60K-72	Construction/Modification Date = On or before June 11, 1973	
To151	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To151	40 CFR Part 60, Subpart K	60K-73	Construction/Modification Date = On or before June 11, 1973	
To152	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
T0152	40 CFR Part 60, Subpart K	60K-74	Construction/Modification Date = On or before June 11, 1973	
T0153	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
T0153	40 CFR Part 60, Subpart K	60K-75	Construction/Modification Date = On or before June 11, 1973	
T0154	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
T0154	40 CFR Part 60, Subpart K	60K-76	Construction/Modification Date = On or before June 11, 1973	
T0155	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
T0155	40 CFR Part 60, Subpart K	60K-77	Construction/Modification Date = On or before June 11, 1973	
T0156	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To156	40 CFR Part 60, Subpart K	60K-78	Construction/Modification Date = On or before June 11, 1973	
To157	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To157	40 CFR Part 60, Subpart K	60K-79	Construction/Modification Date = On or before June 11, 1973	
To158	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To158	40 CFR Part 60, Subpart K	60K-80	Construction/Modification Date = On or before June 11, 1973	
To159	30 TAC Chapter 115, Storage of VOCs	R5112-117	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a submerged fill pipe True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To159	40 CFR Part 60, Subpart K	60K-81	Construction/Modification Date = After March 8, 1974 and on or before May 19, 1978 Storage Capacity = Capacity is 40,000 gallons (151,416 liters) or less	
To160	30 TAC Chapter 115, Storage of VOCs	R5112-118	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a submerged fill pipe True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To160	40 CFR Part 60, Subpart K	60K-82	Construction/Modification Date = After March 8, 1974 and on or before May 19, 1978 Storage Capacity = Capacity is 40,000 gallons (151,416 liters) or less	
To161	30 TAC Chapter 115, Storage of VOCs	R5112-119	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a submerged fill pipe	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To161	40 CFR Part 60, Subpart K	60K-83	Construction/Modification Date = After March 8, 1974 and on or before May 19, 1978 Storage Capacity = Capacity is 40,000 gallons (151,416 liters) or less	
To162	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To162	40 CFR Part 60, Subpart K	60K-84	Construction/Modification Date = On or before June 11, 1973	
To163	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To163	40 CFR Part 60, Subpart K	60K-85	Construction/Modification Date = On or before June 11, 1973	
To164	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To164	40 CFR Part 60, Subpart Kb	60KB-46	Product Stored = Volatile organic liquid Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)	
To165	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To165	40 CFR Part 60, Subpart Kb	60KB-16	Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)	
To166	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To166	40 CFR Part 60, Subpart Kb	60KB-17	Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)	
To167	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To167	40 CFR Part 60, Subpart K	60K-165	Construction/Modification Date = After March 8, 1974 and on or before May 19, 1978 Storage Capacity = Capacity is 40,000 gallons (151,416 liters) or less	
To167	40 CFR Part 60, Subpart Kb	60KB-	Product Stored = Volatile organic liquid Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)	
To168	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To168	40 CFR Part 60, Subpart K	60K-166	Construction/Modification Date = After March 8, 1974 and on or before May 19, 1978 Storage Capacity = Capacity is 40,000 gallons (151,416 liters) or less	
To168	40 CFR Part 60, Subpart Kb	60KB-	Product Stored = Volatile organic liquid Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)	

<b>Unit ID</b>	<b>Regulation</b>	<b>Index Number</b>	<b>Basis of Determination*</b>	<b>Changes and Exceptions to DSS**</b>
To169	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
To169	40 CFR Part 60, Subpart Kb	60KB-18	<p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)</p>	
To170	30 TAC Chapter 115, Storage of VOCs	R5117	<p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
To171	30 TAC Chapter 115, Storage of VOCs	R5117	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
To200	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
To200	40 CFR Part 60, Subpart K	60K-86	Construction/Modification Date = On or before June 11, 1973	
To201	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
To201	40 CFR Part 60, Subpart K	60K-87	Construction/Modification Date = On or before June 11, 1973	

<b>Unit ID</b>	<b>Regulation</b>	<b>Index Number</b>	<b>Basis of Determination*</b>	<b>Changes and Exceptions to DSS**</b>
To202	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
To202	40 CFR Part 60, Subpart K	60K-88	Construction/Modification Date = On or before June 11, 1973	
To203	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
To203	40 CFR Part 60, Subpart K	60K-89	Construction/Modification Date = On or before June 11, 1973	
To204	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
To204	40 CFR Part 60, Subpart K	60K-90	Construction/Modification Date = On or before June 11, 1973	
To205	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
To205	40 CFR Part 60, Subpart K	60K-91	Construction/Modification Date = On or before June 11, 1973	
To206	30 TAC Chapter	R5111-1	Today's Date = Today's date is March 1, 2013 or later.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To206	40 CFR Part 60, Subpart K	60K-92	Construction/Modification Date = On or before June 11, 1973	
To207	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To207	40 CFR Part 60, Subpart K	60K-93	Construction/Modification Date = On or before June 11, 1973	
To208	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To208	40 CFR Part 60, Subpart K	60K-94	Construction/Modification Date = On or before June 11, 1973	
To209	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To209	40 CFR Part 60, Subpart K	60K-95	Construction/Modification Date = On or before June 11, 1973	
To210	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To210	40 CFR Part 60, Subpart K	60K-96	Construction/Modification Date = On or before June 11, 1973	
To211	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To211	40 CFR Part 60, Subpart K	60K-97	Construction/Modification Date = On or before June 11, 1973	
To212	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To212	40 CFR Part 60, Subpart K	60K-98	Construction/Modification Date = On or before June 11, 1973	
To213	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To213	40 CFR Part 60, Subpart K	60K-99	Construction/Modification Date = On or before June 11, 1973	
To215	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls	

<b>Unit ID</b>	<b>Regulation</b>	<b>Index Number</b>	<b>Basis of Determination*</b>	<b>Changes and Exceptions to DSS**</b>
			True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To215	40 CFR Part 60, Subpart K	60K-101	Construction/Modification Date = On or before June 11, 1973	
To216	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To216	40 CFR Part 60, Subpart K	60K-102	Construction/Modification Date = On or before June 11, 1973	
To217	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To217	40 CFR Part 60, Subpart K	60K-103	Construction/Modification Date = On or before June 11, 1973	
To218	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To218	40 CFR Part 60, Subpart K	60K-104	Construction/Modification Date = On or before June 11, 1973	
To219	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To219	40 CFR Part 60, Subpart K	60K-105	Construction/Modification Date = On or before June 11, 1973	
To220	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To220	40 CFR Part 60, Subpart K	60K-106	Construction/Modification Date = On or before June 11, 1973	
To221	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To221	40 CFR Part 60, Subpart K	60K-107	Construction/Modification Date = On or before June 11, 1973	
To222	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To222	40 CFR Part 60, Subpart K	60K-108	Construction/Modification Date = On or before June 11, 1973	
To223	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To223	40 CFR Part 60, Subpart K	60K-109	Construction/Modification Date = On or before June 11, 1973	
To224	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To224	40 CFR Part 60, Subpart K	60K-110	Construction/Modification Date = On or before June 11, 1973	
To225	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To225	40 CFR Part 60, Subpart K	60K-111	Construction/Modification Date = On or before June 11, 1973	
To226	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To226	40 CFR Part 60, Subpart K	60K-112	Construction/Modification Date = On or before June 11, 1973	
To227	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	

<b>Unit ID</b>	<b>Regulation</b>	<b>Index Number</b>	<b>Basis of Determination*</b>	<b>Changes and Exceptions to DSS**</b>
To227	40 CFR Part 60, Subpart K	60K-113	Construction/Modification Date = On or before June 11, 1973	
To228	30 TAC Chapter 115, Storage of VOCs	R5112-1	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To228	40 CFR Part 60, Subpart K	60K-114	Construction/Modification Date = On or before June 11, 1973	
To229	30 TAC Chapter 115, Storage of VOCs	R5112-159	Tank Description = Tank using a vapor recovery system (VRS) True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons Control Device Type = Other vapor recovery unit	
To229	40 CFR Part 60, Subpart K	60K-115	Construction/Modification Date = On or before June 11, 1973	
To230	30 TAC Chapter 115, Storage of VOCs	R5112-160	Tank Description = Tank using a vapor recovery system (VRS) True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons Control Device Type = Other vapor recovery unit	
To230	40 CFR Part 60, Subpart K	60K-116	Construction/Modification Date = On or before June 11, 1973	
To233	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To233	40 CFR Part 60, Subpart K	60K-118	Construction/Modification Date = On or before June 11, 1973	
To234	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To234	40 CFR Part 60, Subpart K	60K-119	Construction/Modification Date = On or before June 11, 1973	
To235	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To235	40 CFR Part 60, Subpart K	60K-120	Construction/Modification Date = On or before June 11, 1973	
To251	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To251	40 CFR Part 60, Subpart K	60K-121	Construction/Modification Date = On or before June 11, 1973	
To252	30 TAC Chapter 115, Storage of VOCs	R5111-1	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To252	40 CFR Part 60, Subpart K	60K-122	Construction/Modification Date = On or before June 11, 1973	
To253	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To253	40 CFR Part 60, Subpart K	60K-123	Construction/Modification Date = On or before June 11, 1973	
To254	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To254	40 CFR Part 60, Subpart K	60K-124	Construction/Modification Date = On or before June 11, 1973	
To255	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To255	40 CFR Part 60, Subpart K	60K-125	Construction/Modification Date = On or before June 11, 1973	
To256	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To256	40 CFR Part 60, Subpart K	60K-126	Construction/Modification Date = On or before June 11, 1973	
To258	30 TAC Chapter 115, Storage of VOCs	R5112-1	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	

<b>Unit ID</b>	<b>Regulation</b>	<b>Index Number</b>	<b>Basis of Determination*</b>	<b>Changes and Exceptions to DSS**</b>
To258	40 CFR Part 60, Subpart K	60K-128	Construction/Modification Date = On or before June 11, 1973	
To259	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
To259	40 CFR Part 60, Subpart K	60K-129	Construction/Modification Date = On or before June 11, 1973	
To260	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
To260	40 CFR Part 60, Subpart K	60K-130	Construction/Modification Date = On or before June 11, 1973	
To261	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
To261	40 CFR Part 60, Subpart K	60K-131	Construction/Modification Date = On or before June 11, 1973	
To262	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
To262	40 CFR Part 60,	60K-132	Construction/Modification Date = On or before June 11, 1973	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	Subpart K			
To263	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
To263	40 CFR Part 60, Subpart K	60K-133	Construction/Modification Date = On or before June 11, 1973	
To264	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
To264	40 CFR Part 60, Subpart K	60K-134	Construction/Modification Date = On or before June 11, 1973	
To265	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
To265	40 CFR Part 60, Subpart K	60K-135	Construction/Modification Date = On or before June 11, 1973	
To267	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
To267	40 CFR Part 60, Subpart K	60K-137	Construction/Modification Date = On or before June 11, 1973	

<b>Unit ID</b>	<b>Regulation</b>	<b>Index Number</b>	<b>Basis of Determination*</b>	<b>Changes and Exceptions to DSS**</b>
To268	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To268	40 CFR Part 60, Subpart K	60K-138	Construction/Modification Date = On or before June 11, 1973	
To269	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To269	40 CFR Part 60, Subpart K	60K-139	Construction/Modification Date = On or before June 11, 1973	
To269	40 CFR Part 60, Subpart Kb	60KB-60	Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)	
To270	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To270	40 CFR Part 60, Subpart K	60K-140	Construction/Modification Date = On or before June 11, 1973	
To270	40 CFR Part 60, Subpart Kb	60KB-61	Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)	
To271	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To271	40 CFR Part 60, Subpart K	60K-141	Construction/Modification Date = On or before June 11, 1973	
To271	40 CFR Part 60, Subpart Kb	60KB-62	Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)	
To272	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To272	40 CFR Part 60, Subpart K	60K-142	Construction/Modification Date = After March 8, 1974 and on or before May 19, 1978 Storage Capacity = Capacity is 40,000 gallons (151,416 liters) or less	
To273	30 TAC Chapter 115, Storage of VOCs	R5112-188	Tank Description = Tank using a submerged fill pipe True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons	
To273	40 CFR Part 60, Subpart Ka	60KA-1	Product Stored = Stored product other than a petroleum liquid	
To274	30 TAC Chapter 115, Storage of VOCs	R5112-189	Tank Description = Tank using a submerged fill pipe True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons	
To274	40 CFR Part 60, Subpart Ka	60KA-2	Product Stored = Stored product other than a petroleum liquid	
To275	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	

<b>Unit ID</b>	<b>Regulation</b>	<b>Index Number</b>	<b>Basis of Determination*</b>	<b>Changes and Exceptions to DSS**</b>
To275	40 CFR Part 60, Subpart K	60K-143	Construction/Modification Date = After March 8, 1974 and on or before May 19, 1978 Storage Capacity = Capacity is 40,000 gallons (151,416 liters) or less	
To276	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To276	40 CFR Part 60, Subpart K	60K-144	Construction/Modification Date = After March 8, 1974 and on or before May 19, 1978 Storage Capacity = Capacity is 40,000 gallons (151,416 liters) or less	
To277	30 TAC Chapter 115, Storage of VOCs	R5112-1	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To277	40 CFR Part 60, Subpart Kb	60KB-50	Product Stored = Volatile organic liquid Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)	
To278	30 TAC Chapter 115, Storage of VOCs	R5112-193	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a submerged fill pipe True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons	
To278	40 CFR Part 60, Subpart Ka	60KA-3	Product Stored = Stored product other than a petroleum liquid	
To280	30 TAC Chapter 115, Storage of VOCs	R5111-1	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To280	40 CFR Part 60, Subpart Kb	60KB-19	Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			(75,000 liters)	
To281	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
To281	40 CFR Part 60, Subpart Kb	60KB-20	<p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is greater than or equal to 19,800 gallons (75,000 liters) but less than 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia</p>	
To301	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
To301	40 CFR Part 60, Subpart K	60K-145	Construction/Modification Date = On or before June 11, 1973	
To302	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
To302	40 CFR Part 60, Subpart K	60K-146	Construction/Modification Date = On or before June 11, 1973	
To303	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	

<b>Unit ID</b>	<b>Regulation</b>	<b>Index Number</b>	<b>Basis of Determination*</b>	<b>Changes and Exceptions to DSS**</b>
To303	40 CFR Part 60, Subpart K	60K-147	Construction/Modification Date = On or before June 11, 1973	
To304	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To304	40 CFR Part 60, Subpart K	60K-148	Construction/Modification Date = On or before June 11, 1973	
To305	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To305	40 CFR Part 60, Subpart K	60K-149	Construction/Modification Date = On or before June 11, 1973	
To306	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To306	40 CFR Part 60, Subpart K	60K-150	Construction/Modification Date = On or before June 11, 1973	
To307	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To307	40 CFR Part 60,	60K-151	Construction/Modification Date = On or before June 11, 1973	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	Subpart K			
To308	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
To308	40 CFR Part 60, Subpart K	60K-152	Construction/Modification Date = On or before June 11, 1973	
To309	30 TAC Chapter 115, Storage of VOCs	R5112-205	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons</p>	
To309	40 CFR Part 60, Subpart K	60K-153	Construction/Modification Date = On or before June 11, 1973	
To310	30 TAC Chapter 115, Storage of VOCs	R5112-206	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons</p>	
To310	40 CFR Part 60, Subpart K	60K-154	Construction/Modification Date = On or before June 11, 1973	
To313	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
To314	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
To314	40 CFR Part 60, Subpart Kb	60KB-63	<p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)</p>	
To401	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
To401	40 CFR Part 60, Subpart K	60K-155	Construction/Modification Date = On or before June 11, 1973	
To402	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
To402	40 CFR Part 60, Subpart K	60K-156	Construction/Modification Date = On or before June 11, 1973	
To403	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
To403	40 CFR Part 60, Subpart Kb	60KB-51	<p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)</p>	
To404	30 TAC Chapter 115, Storage of	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	VOCs		<p>compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
To404	40 CFR Part 60, Subpart K	60K-157	<p>Construction/Modification Date = After March 8, 1974 and on or before May 19, 1978</p> <p>Storage Capacity = Capacity is 40,000 gallons (151,416 liters) or less</p>	
To405	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
To405	40 CFR Part 60, Subpart Kb	60KB-52	<p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)</p>	
To407	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
To407	40 CFR Part 60, Subpart K	60K-158	<p>Construction/Modification Date = On or before June 11, 1973</p>	
To407	40 CFR Part 60, Subpart Kb	60KB-64	<p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)</p>	
To408	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
To408	40 CFR Part 60, Subpart K	60K-159	<p>Construction/Modification Date = After March 8, 1974 and on or before May 19, 1978</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Storage Capacity = Capacity is 40,000 gallons (151,416 liters) or less	
To409	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
To409	40 CFR Part 60, Subpart K	60K-160	<p>Construction/Modification Date = After March 8, 1974 and on or before May 19, 1978</p> <p>Storage Capacity = Capacity is 40,000 gallons (151,416 liters) or less</p>	
To410	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
To410	40 CFR Part 60, Subpart K	60K-161	<p>Construction/Modification Date = After March 8, 1974 and on or before May 19, 1978</p> <p>Storage Capacity = Capacity is 40,000 gallons (151,416 liters) or less</p>	
To411	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
To411	40 CFR Part 60, Subpart Kb	60KB-21	<p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)</p>	
To412	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	

<b>Unit ID</b>	<b>Regulation</b>	<b>Index Number</b>	<b>Basis of Determination*</b>	<b>Changes and Exceptions to DSS**</b>
To412	40 CFR Part 60, Subpart Kb	60KB-22	Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)	
To413	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To413	40 CFR Part 60, Subpart K	60K-162	Construction/Modification Date = After March 8, 1974 and on or before May 19, 1978 Storage Capacity = Capacity is 40,000 gallons (151,416 liters) or less	
To414	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To414	40 CFR Part 60, Subpart K	60K-165	Construction/Modification Date = After March 8, 1974 and on or before May 19, 1978 Storage Capacity = Capacity is 40,000 gallons (151,416 liters) or less	
To414	40 CFR Part 60, Subpart Kb	60KB-23	Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)	
To415	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a submerged fill pipe True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons	
To415	40 CFR Part 60, Subpart Ka	60KA-5	Product Stored = Stored product other than a petroleum liquid	
To416	30 TAC Chapter 115, Storage of VOCs	R5112-221	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a submerged fill pipe True Vapor Pressure = True vapor pressure is less than 1.0 psia	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons	
To416	40 CFR Part 60, Subpart Ka	60KA-6	Product Stored = Stored product other than a petroleum liquid	
To417	30 TAC Chapter 115, Storage of VOCs	R5112-222	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a submerged fill pipe True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons	
To417	40 CFR Part 60, Subpart Ka	60KA-7	Product Stored = Stored product other than a petroleum liquid	
To418	30 TAC Chapter 115, Storage of VOCs	R5112-223	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a submerged fill pipe True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons	
To418	40 CFR Part 60, Subpart Ka	60KA-8	Product Stored = Stored product other than a petroleum liquid	
To419	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To419	40 CFR Part 60, Subpart Ka	60KA-9	Product Stored = Stored product other than a petroleum liquid	
To420	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a submerged fill pipe True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To420	40 CFR Part 60,	60KA-10	Product Stored = Stored product other than a petroleum liquid	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	Subpart Ka			
To421	30 TAC Chapter 115, Storage of VOCs	R5112-226	Tank Description = Tank using a submerged fill pipe True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons	
To421	40 CFR Part 60, Subpart Ka	60KA-11	Product Stored = Stored product other than a petroleum liquid	
To422	30 TAC Chapter 115, Storage of VOCs	R5112-227	Tank Description = Tank using a submerged fill pipe True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons	
To422	40 CFR Part 60, Subpart Ka	60KA-12	Product Stored = Stored product other than a petroleum liquid	
To423	30 TAC Chapter 115, Storage of VOCs	R5112-228	Tank Description = Tank using a submerged fill pipe True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons	
To423	40 CFR Part 60, Subpart Ka	60KA-13	Product Stored = Stored product other than a petroleum liquid	
To424	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To424	40 CFR Part 60, Subpart K	60K-163	Construction/Modification Date = On or before June 11, 1973	
To425	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To425	40 CFR Part 60, Subpart K	60K-166	Construction/Modification Date = On or before June 11, 1973	

<b>Unit ID</b>	<b>Regulation</b>	<b>Index Number</b>	<b>Basis of Determination*</b>	<b>Changes and Exceptions to DSS**</b>
To425	40 CFR Part 60, Subpart Kb	60KB-53	Product Stored = Volatile organic liquid Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)	
To426	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To426	40 CFR Part 60, Subpart Kb	60KB-54	Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)	
To427	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To427	40 CFR Part 60, Subpart Kb	60KB-24	Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)	
To432	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To432	40 CFR Part 60, Subpart Kb	60KB-25	Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)	
To434	30 TAC Chapter 115, Storage of VOCs	R5112-1	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To434	40 CFR Part 60, Subpart Kb	60KB-26	Product Stored = Volatile organic liquid Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)	
To501	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To501	40 CFR Part 60, Subpart Kb	60KB-55	Product Stored = Volatile organic liquid Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)	
To505	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To505	40 CFR Part 60, Subpart Ka	60KA-14	Product Stored = Stored product other than a petroleum liquid	
To506	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To506	40 CFR Part 60, Subpart Ka	60KA-15	Product Stored = Stored product other than a petroleum liquid	
To591	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To591	40 CFR Part 60, Subpart Kb	60KB-26	Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 19,800 gallons (75,000 liters) but less than 39,900 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia	
To603	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To603	40 CFR Part 60, Subpart Kb	60KB-27	Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)	
To604	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To604	40 CFR Part 60, Subpart Kb	60KB-28	Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)	
To605	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To605	40 CFR Part 60, Subpart Kb	60KB-29	Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)	
To606	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
To606	40 CFR Part 60, Subpart K	60K-167	<p>Construction/Modification Date = After June 11, 1973 And on or before March 8, 1974</p> <p>Storage Capacity = Capacity is 40,000 gallons (151,416 liters) or less</p>	
To606	40 CFR Part 60, Subpart Kb	60KB-30	<p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)</p>	
To607	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
To607	40 CFR Part 60, Subpart K	60K-168	<p>Construction/Modification Date = After June 11, 1973 And on or before March 8, 1974</p> <p>Storage Capacity = Capacity is 40,000 gallons (151,416 liters) or less</p>	
To701	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
To701	40 CFR Part 60, Subpart Kb	60KB-32	<p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)</p>	
To809	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
To809	40 CFR Part 60, Subpart Kb	60KB-7	<p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			(75,000 liters)	
To810	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
To810	40 CFR Part 60, Subpart Kb	60KB-8	<p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)</p>	
To811	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
To811	40 CFR Part 60, Subpart Kb	60KB-40	<p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)</p>	
To812	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>	
To812	40 CFR Part 60, Subpart Kb	60KB-9	<p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)</p>	
To813	30 TAC Chapter 115, Storage of VOCs	R5111-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To813	40 CFR Part 60, Subpart Kb	60KB-41	Product Stored = Volatile organic liquid Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)	
To814	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To814	40 CFR Part 60, Subpart Kb	60KB-42	Product Stored = Volatile organic liquid Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)	
To815	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To815	40 CFR Part 60, Subpart Kb	60KB-43	Product Stored = Volatile organic liquid Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)	
To819	30 TAC Chapter 115, Storage of VOCs	R5112-246	Tank Description = Tank using a submerged fill pipe True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons	
To860	30 TAC Chapter 115, Storage of VOCs	R5112-260	Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To860	40 CFR Part 60, Subpart Kb	60KB-65	Product Stored = Volatile organic liquid Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)	
To861	30 TAC Chapter 115, Storage of VOCs	R5112-261	Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	

<b>Unit ID</b>	<b>Regulation</b>	<b>Index Number</b>	<b>Basis of Determination*</b>	<b>Changes and Exceptions to DSS**</b>
To861	40 CFR Part 60, Subpart Kb	60KB-66	Product Stored = Volatile organic liquid Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)	
To862	30 TAC Chapter 115, Storage of VOCs	R5112-262	Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To862	40 CFR Part 60, Subpart Kb	60KB-67	Product Stored = Volatile organic liquid Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)	
To863	30 TAC Chapter 115, Storage of VOCs	R5112-263	Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To863	40 CFR Part 60, Subpart Kb	60KB-68	Product Stored = Volatile organic liquid Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)	
To864	30 TAC Chapter 115, Storage of VOCs	R5112-264	Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To864	40 CFR Part 60, Subpart Kb	60KB-69	Product Stored = Volatile organic liquid Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)	
To865	30 TAC Chapter 115, Storage of VOCs	R5112-265	Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To865	40 CFR Part 60, Subpart Kb	60KB-70	Product Stored = Volatile organic liquid Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)	
To866	30 TAC Chapter 115, Storage of VOCs	R5112-266	Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To866	40 CFR Part 60, Subpart Kb	60KB-71	Product Stored = Volatile organic liquid Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)	
To867	30 TAC Chapter 115, Storage of	R5112-267	Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	VOCs		Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To867	40 CFR Part 60, Subpart Kb	60KB-72	Product Stored = Volatile organic liquid Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)	
To868	30 TAC Chapter 115, Storage of VOCs	R5112-268	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To868	40 CFR Part 60, Subpart Kb	60KB-73	Product Stored = Volatile organic liquid Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)	
To869	30 TAC Chapter 115, Storage of VOCs	R5112-269	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To869	40 CFR Part 60, Subpart Kb	60KB-74	Product Stored = Volatile organic liquid Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)	
To870	30 TAC Chapter 115, Storage of VOCs	R5112-270	Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To870	40 CFR Part 60, Subpart Kb	60KB-75	Product Stored = Volatile organic liquid Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)	
To871	30 TAC Chapter 115, Storage of VOCs	R5112-271	Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
To871	40 CFR Part 60, Subpart Kb	60KB-76	Product Stored = Volatile organic liquid Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)	
T1001	30 TAC Chapter	R5112	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	115, Storage of VOCs		compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a submerged fill pipe True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons	
T1002	30 TAC Chapter 115, Storage of VOCs	R5112	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
T1005	30 TAC Chapter 115, Storage of VOCs	R5112	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a submerged fill pipe True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons	
T1006	30 TAC Chapter 115, Storage of VOCs	R5112	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a submerged fill pipe True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons	
T4304	30 TAC Chapter 115, Storage of VOCs	R5112	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a vapor recovery system (VRS) True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons Control Device Type = Other vapor recovery unit	
T4304	40 CFR Part 60, Subpart Ka	60KA-16	Product Stored = Stored product other than a petroleum liquid	
T4304	40 CFR Part 60, Subpart Kb	60Kb	Product Stored = Volatile organic liquid Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)	
T4602	30 TAC Chapter 115, Storage of VOCs	R5115-251	Tank Description = Tank using a submerged fill pipe True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
T5102	30 TAC Chapter 115, Storage of VOCs	R5112-1	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
T5102	40 CFR Part 60, Subpart Kb	60-KB	Product Stored = Volatile organic liquid Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)	
T5200	30 TAC Chapter 115, Storage of VOCs	R5112-1	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
T5200	40 CFR Part 60, Subpart Kb	60-KB	Product Stored = Volatile organic liquid Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)	
T5702	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
T5702	40 CFR Part 60, Subpart Kb	60KB-33	Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)	
T6110	30 TAC Chapter 115, Storage of VOCs	R5112-6	Tank Description = Tank using a submerged fill pipe True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
T6110	40 CFR Part 60, Subpart K	60K-169	Construction/Modification Date = After March 8, 1974 and on or before May 19, 1978 Storage Capacity = Capacity is 40,000 gallons (151,416 liters) or less	
T6120	30 TAC Chapter 115, Storage of VOCs	R5112-7	Tank Description = Tank using a submerged fill pipe True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Product Stored = VOC other than crude oil or condensate	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
T6130	30 TAC Chapter 115, Storage of VOCs	R5112-8	Tank Description = Tank using a submerged fill pipe True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
T6140	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
T6150	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
T6150	40 CFR Part 60, Subpart Kb	60KB-3	Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)	
T6160	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
T6160	40 CFR Part 60, Subpart Kb	60KB-1	Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)	
T6170	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
T6170	40 CFR Part 60, Subpart Kb	60KB-2	Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)	
T6200	30 TAC Chapter 115, Storage of VOCs	R5111-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
T6200	40 CFR Part 60, Subpart K	60K-164	Construction/Modification Date = On or before June 11, 1973 Storage Capacity = Capacity is 40,000 gallons (151,416 liters) or less Product Stored = Stored product other than petroleum liquid (as defined in 40 CFR Part 60, Subpart K)	
#1 RACK	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-1	30 TAC CHAPTER 115 (REG V) FACILITY TYPE = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal. ALTERNATE CONTROL REQUIREMENT (ACR) [REG V] = No alternate control requirements are being utilized. PRODUCT TRANSFERRED = Volatile organic compounds other than liquefied petroleum gas and gasoline. TRANSFER TYPE = Loading and unloading. TRUE VAPOR PRESSURE [REG V] = True vapor pressure less than 0.5 psia.	
#2 RACK	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-2	30 TAC CHAPTER 115 (REG V) FACILITY TYPE = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal. ALTERNATE CONTROL REQUIREMENT (ACR) [REG V] = No alternate control requirements are being utilized. PRODUCT TRANSFERRED = Volatile organic compounds other than liquefied petroleum gas and gasoline. TRANSFER TYPE = Loading and unloading. TRUE VAPOR PRESSURE [REG V] = True vapor pressure less than 0.5 psia.	
A-100 RACK	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-8	30 TAC CHAPTER 115 (REG V) FACILITY TYPE = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal. ALTERNATE CONTROL REQUIREMENT (ACR) [REG V] = No alternate control requirements are being utilized. PRODUCT TRANSFERRED = Volatile organic compounds other than liquefied petroleum gas and gasoline. TRANSFER TYPE = Loading and unloading. TRUE VAPOR PRESSURE [REG V] = True vapor pressure less than 0.5 psia.	
A-200 AOS RACK	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-10	30 TAC CHAPTER 115 (REG V) FACILITY TYPE = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal. ALTERNATE CONTROL REQUIREMENT (ACR) [REG V] = No alternate control requirements are being utilized. PRODUCT TRANSFERRED = Volatile organic compounds other than liquefied petroleum gas and gasoline.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>TRANSFER TYPE = Loading and unloading.</p> <p>TRUE VAPOR PRESSURE [REG V] = True vapor pressure less than 0.5 psia.</p>	
A-200 RACK	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-9	<p>30 TAC CHAPTER 115 (REG V) FACILITY TYPE = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>ALTERNATE CONTROL REQUIREMENT (ACR) [REG V] = No alternate control requirements are being utilized.</p> <p>PRODUCT TRANSFERRED = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>TRANSFER TYPE = Loading and unloading.</p> <p>TRUE VAPOR PRESSURE [REG V] = True vapor pressure greater than or equal to 0.5 psia.</p> <p>DAILY THROUGHPUT [REG V] = Loading less than 20,000 gallons per day.</p>	
AOS L/O RACK	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-14	<p>30 TAC CHAPTER 115 (REG V) FACILITY TYPE = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>ALTERNATE CONTROL REQUIREMENT (ACR) [REG V] = No alternate control requirements are being utilized.</p> <p>PRODUCT TRANSFERRED = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>TRANSFER TYPE = Loading and unloading.</p> <p>TRUE VAPOR PRESSURE [REG V] = True vapor pressure less than 0.5 psia.</p>	
DB-100 L/O	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-6	<p>30 TAC CHAPTER 115 (REG V) FACILITY TYPE = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>ALTERNATE CONTROL REQUIREMENT (ACR) [REG V] = No alternate control requirements are being utilized.</p> <p>PRODUCT TRANSFERRED = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>TRANSFER TYPE = Loading and unloading.</p> <p>TRUE VAPOR PRESSURE [REG V] = True vapor pressure less than 0.5 psia.</p>	
EFL1	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-35	<p>30 TAC CHAPTER 115 (REG V) FACILITY TYPE = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>ALTERNATE CONTROL REQUIREMENT (ACR) [REG V] = No alternate control requirements are being utilized.</p> <p>PRODUCT TRANSFERRED = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>TRANSFER TYPE = Loading and unloading.</p> <p>TRUE VAPOR PRESSURE [REG V] = True vapor pressure less than 0.5 psia.</p>	
EFL2	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-42	<p>30 TAC CHAPTER 115 (REG V) FACILITY TYPE = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>ALTERNATE CONTROL REQUIREMENT (ACR) [REG V] = No alternate control requirements are being utilized.</p> <p>PRODUCT TRANSFERRED = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>TRANSFER TYPE = Loading and unloading.</p> <p>TRUE VAPOR PRESSURE [REG V] = True vapor pressure less than 0.5 psia.</p>	
EFL3	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-43	<p>30 TAC CHAPTER 115 (REG V) FACILITY TYPE = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>ALTERNATE CONTROL REQUIREMENT (ACR) [REG V] = No alternate control requirements are being utilized.</p> <p>PRODUCT TRANSFERRED = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			TRANSFER TYPE = Loading and unloading. TRUE VAPOR PRESSURE [REG V] = True vapor pressure less than 0.5 psia.	
EFL4	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-44	30 TAC CHAPTER 115 (REG V) FACILITY TYPE = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal. ALTERNATE CONTROL REQUIREMENT (ACR) [REG V] = No alternate control requirements are being utilized. PRODUCT TRANSFERRED = Volatile organic compounds other than liquefied petroleum gas and gasoline. TRANSFER TYPE = Loading and unloading. TRUE VAPOR PRESSURE [REG V] = True vapor pressure less than 0.5 psia.	
EL1	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-37	30 TAC CHAPTER 115 (REG V) FACILITY TYPE = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal. ALTERNATE CONTROL REQUIREMENT (ACR) [REG V] = No alternate control requirements are being utilized. PRODUCT TRANSFERRED = Volatile organic compounds other than liquefied petroleum gas and gasoline. TRANSFER TYPE = Only loading. TRUE VAPOR PRESSURE [REG V] = True vapor pressure greater than or equal to 0.5 psia. DAILY THROUGHPUT [REG V] = Loading less than 20,000 gallons per day.	
EV3	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-36	30 TAC CHAPTER 115 (REG V) FACILITY TYPE = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal. ALTERNATE CONTROL REQUIREMENT (ACR) [REG V] = No alternate control requirements are being utilized. PRODUCT TRANSFERRED = Volatile organic compounds other than liquefied petroleum gas and gasoline. TRANSFER TYPE = Only loading. TRUE VAPOR PRESSURE [REG V] = True vapor pressure greater than or equal to 0.5 psia. DAILY THROUGHPUT [REG V] = Loading less than 20,000 gallons per day.	
K-4/5 DRUMOFF	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-22	30 TAC CHAPTER 115 (REG V) FACILITY TYPE = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal. ALTERNATE CONTROL REQUIREMENT (ACR) [REG V] = No alternate control requirements are being utilized. PRODUCT TRANSFERRED = Volatile organic compounds other than liquefied petroleum gas and gasoline. TRANSFER TYPE = Loading and unloading. TRUE VAPOR PRESSURE [REG V] = True vapor pressure less than 0.5 psia.	
K-400 RACK	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-16	30 TAC CHAPTER 115 (REG V) FACILITY TYPE = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal. ALTERNATE CONTROL REQUIREMENT (ACR) [REG V] = No alternate control requirements are being utilized. PRODUCT TRANSFERRED = Volatile organic compounds other than liquefied petroleum gas and gasoline. TRANSFER TYPE = Loading and unloading. TRUE VAPOR PRESSURE [REG V] = True vapor pressure less than 0.5 psia.	
LOAD620-2	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-5	30 TAC CHAPTER 115 (REG V) FACILITY TYPE = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal. ALTERNATE CONTROL REQUIREMENT (ACR) [REG V] = No alternate control requirements are being utilized.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>PRODUCT TRANSFERRED = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>TRANSFER TYPE = Loading and unloading.</p> <p>TRUE VAPOR PRESSURE [REG V] = True vapor pressure less than 0.5 psia.</p>	
R-100 DRUMOFF	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-18	<p>30 TAC CHAPTER 115 (REG V) FACILITY TYPE = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>ALTERNATE CONTROL REQUIREMENT (ACR) [REG V] = No alternate control requirements are being utilized.</p> <p>PRODUCT TRANSFERRED = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>TRANSFER TYPE = Only loading.</p> <p>TRUE VAPOR PRESSURE [REG V] = True vapor pressure greater than or equal to 0.5 psia.</p> <p>DAILY THROUGHPUT [REG V] = Loading less than 20,000 gallons per day.</p>	
R-200 DRUMOFF	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-19	<p>30 TAC CHAPTER 115 (REG V) FACILITY TYPE = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>ALTERNATE CONTROL REQUIREMENT (ACR) [REG V] = No alternate control requirements are being utilized.</p> <p>PRODUCT TRANSFERRED = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>TRANSFER TYPE = Only loading.</p> <p>TRUE VAPOR PRESSURE [REG V] = True vapor pressure less than 0.5 psia.</p>	
R-200 RACK	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-3	<p>30 TAC CHAPTER 115 (REG V) FACILITY TYPE = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>ALTERNATE CONTROL REQUIREMENT (ACR) [REG V] = No alternate control requirements are being utilized.</p> <p>PRODUCT TRANSFERRED = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>TRANSFER TYPE = Loading and unloading.</p> <p>TRUE VAPOR PRESSURE [REG V] = True vapor pressure less than 0.5 psia.</p>	
R-3/4 L/O RACK	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-15	<p>30 TAC CHAPTER 115 (REG V) FACILITY TYPE = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>ALTERNATE CONTROL REQUIREMENT (ACR) [REG V] = No alternate control requirements are being utilized.</p> <p>PRODUCT TRANSFERRED = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>TRANSFER TYPE = Loading and unloading.</p> <p>TRUE VAPOR PRESSURE [REG V] = True vapor pressure less than 0.5 psia.</p>	
R-300 DRUMOFF	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-20	<p>30 TAC CHAPTER 115 (REG V) FACILITY TYPE = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>ALTERNATE CONTROL REQUIREMENT (ACR) [REG V] = No alternate control requirements are being utilized.</p> <p>PRODUCT TRANSFERRED = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>TRANSFER TYPE = Only loading.</p> <p>TRUE VAPOR PRESSURE [REG V] = True vapor pressure less than 0.5 psia.</p>	
R-400 DRUMOFF	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-21	<p>30 TAC CHAPTER 115 (REG V) FACILITY TYPE = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>ALTERNATE CONTROL REQUIREMENT (ACR) [REG V] = No alternate control requirements are being utilized.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>PRODUCT TRANSFERRED = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>TRANSFER TYPE = Only loading.</p> <p>TRUE VAPOR PRESSURE [REG V] = True vapor pressure less than 0.5 psia.</p>	
SPONTO DRUMOFF	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-23	<p>30 TAC CHAPTER 115 (REG V) FACILITY TYPE = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>ALTERNATE CONTROL REQUIREMENT (ACR) [REG V] = No alternate control requirements are being utilized.</p> <p>PRODUCT TRANSFERRED = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>TRANSFER TYPE = Only loading.</p> <p>TRUE VAPOR PRESSURE [REG V] = True vapor pressure greater than or equal to 0.5 psia.</p> <p>DAILY THROUGHPUT [REG V] = Loading less than 20,000 gallons per day.</p>	
SPONTO RACK	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-4	<p>30 TAC CHAPTER 115 (REG V) FACILITY TYPE = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>ALTERNATE CONTROL REQUIREMENT (ACR) [REG V] = No alternate control requirements are being utilized.</p> <p>PRODUCT TRANSFERRED = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>TRANSFER TYPE = Loading and unloading.</p> <p>TRUE VAPOR PRESSURE [REG V] = True vapor pressure greater than or equal to 0.5 psia.</p> <p>DAILY THROUGHPUT [REG V] = Loading less than 20,000 gallons per day.</p>	
SPOT 13A,B,C	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-33	<p>30 TAC CHAPTER 115 (REG V) FACILITY TYPE = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>ALTERNATE CONTROL REQUIREMENT (ACR) [REG V] = No alternate control requirements are being utilized.</p> <p>PRODUCT TRANSFERRED = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>TRANSFER TYPE = Loading and unloading.</p> <p>TRUE VAPOR PRESSURE [REG V] = True vapor pressure less than 0.5 psia.</p>	
SPOT 7A	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-26	<p>30 TAC CHAPTER 115 (REG V) FACILITY TYPE = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>ALTERNATE CONTROL REQUIREMENT (ACR) [REG V] = No alternate control requirements are being utilized.</p> <p>PRODUCT TRANSFERRED = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>TRANSFER TYPE = Loading and unloading.</p> <p>TRUE VAPOR PRESSURE [REG V] = True vapor pressure less than 0.5 psia.</p>	
SPOT 7B	30 TAC Chapter 115, Loading and Unloading of VOC	R5211 -27	<p>30 TAC CHAPTER 115 (REG V) FACILITY TYPE = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>ALTERNATE CONTROL REQUIREMENT (ACR) [REG V] = No alternate control requirements are being utilized.</p> <p>PRODUCT TRANSFERRED = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>TRANSFER TYPE = Loading and unloading.</p> <p>TRUE VAPOR PRESSURE [REG V] = True vapor pressure less than 0.5 psia.</p>	
SPOT 8	30 TAC Chapter 115, Loading and	R5211-28	<p>30 TAC CHAPTER 115 (REG V) FACILITY TYPE = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	Unloading of VOC		ALTERNATE CONTROL REQUIREMENT (ACR) [REG V] = No alternate control requirements are being utilized. PRODUCT TRANSFERRED = Volatile organic compounds other than liquefied petroleum gas and gasoline. TRANSFER TYPE = Only loading. TRUE VAPOR PRESSURE [REG V] = True vapor pressure greater than or equal to 0.5 psia. DAILY THROUGHPUT [REG V] = Loading less than 20,000 gallons per day.	
SPOT 9	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-29	30 TAC CHAPTER 115 (REG V) FACILITY TYPE = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal. ALTERNATE CONTROL REQUIREMENT (ACR) [REG V] = No alternate control requirements are being utilized. PRODUCT TRANSFERRED = Volatile organic compounds other than liquefied petroleum gas and gasoline. TRANSFER TYPE = Loading and unloading. TRUE VAPOR PRESSURE [REG V] = True vapor pressure greater than or equal to 0.5 psia. DAILY THROUGHPUT [REG V] = Loading less than 20,000 gallons per day.	
STUB LINE	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-7	30 TAC CHAPTER 115 (REG V) FACILITY TYPE = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal. ALTERNATE CONTROL REQUIREMENT (ACR) [REG V] = No alternate control requirements are being utilized. PRODUCT TRANSFERRED = Volatile organic compounds other than liquefied petroleum gas and gasoline. TRANSFER TYPE = Loading and unloading. TRUE VAPOR PRESSURE [REG V] = True vapor pressure greater than or equal to 0.5 psia. DAILY THROUGHPUT [REG V] = Loading less than 20,000 gallons per day.	
B-4	40 CFR Part 60, Subpart D	60D	CONSTRUCTION/MODIFICATION DATE = After September 18, 1978. COVERED UNDER SUBPART DA = The steam generating unit is not covered under 40 CFR Part 60, Subpart Da. 40 CFR 60 (NSPS) D CHANGES TO EXISTING AFFECTED FACILITY [NSPS D] = No change has been made to the existing fossil fuel-fired steam generating unit. 40 CFR 60 (NSPS) SUBPART D HEAT INPUT RATE = Heat input rate is less than or equal to 250 MMBtu/hr (73 MW).	
B-4	40 CFR Part 60, Subpart Dc	60Dc	CONSTRUCTION/MODIFICATION DATE = On or before June 9, 1989. MAXIMUM DESIGN HEAT INPUT CAPACITY = Maximum design heat input capacity is greater than or equal to 10 MMBtu/hr (2.9 MW) but less than or equal to 100 MMBtu (29 MW).	
B-5	40 CFR Part 60, Subpart D	60D	CONSTRUCTION/MODIFICATION DATE = After September 18, 1978. COVERED UNDER SUBPART DA = The steam generating unit is not covered under 40 CFR Part 60, Subpart Da. 40 CFR 60 (NSPS) D CHANGES TO EXISTING AFFECTED FACILITY [NSPS D] = No change has been made to the existing fossil fuel-fired steam generating unit. 40 CFR 60 (NSPS) SUBPART D HEAT INPUT RATE = Heat input rate is less than or equal to 250 MMBtu/hr (73 MW).	
EFOO1A	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	R9600-1	Title 30 TAC § 115.352 Applicable = Site is not a petroleum refinery, synthetic organic chemical, polymer resin or methyl tert-butyl ether (MTBE) manufacturing process nor a natural gas/gasoline processing operation as defined in 30 TAC 115.10.	
EFOO1A	40 CFR Part 60,	60VV-1	PRODUCES CHEMICALS LISTED IN 40 CFR 60.489 = PRODUCES AS INTERMEDIATE OR FINAL PRODUCT	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	Subpart VV		ONE OR MORE CHEMICALS LISTED IN 40 CFR 60.489 AFFECTED FACILITY AS DEFINED IN 40 CFR 60.480(A)(2) = FACILITY IS AN AFFECTED FACILITY AS DEFINED IN 40 CFR 60.480(A)(2) 40 CFR 60 (NSPS) SUBPART VV CONSTRUCTION/MODIFICATION (RECONSTRUCTION) DATE = AFTER JANUARY 5, 1981 40 CFR 60 SUBPART VV DESIGN CAPACITY = SITE WITH DESIGN CAPACITY LESS THAN 1,000 MEGAGRAMS PER YEAR	
EF001A	40 CFR Part 60, Subpart VV	R9600-1	PRODUCES CHEMICALS LISTED IN 40 CFR 60.489 = DOES NOT PRODUCE ANY CHEMICAL LISTED IN 40 CFR 60.489 AS INTERMEDIATE OR FINAL PRODUCT	
FUGA100	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	R5352-6	Title 30 TAC § 115.352 Applicable = Site is not a petroleum refinery, synthetic organic chemical, polymer resin or methyl tert-butyl ether (MTBE) manufacturing process nor a natural gas/gasoline processing operation as defined in 30 TAC 115.10.	
FUGA100	40 CFR Part 60, Subpart VV	60VV-1	PRODUCES CHEMICALS LISTED IN 40 CFR 60.489 = PRODUCES AS INTERMEDIATE OR FINAL PRODUCT ONE OR MORE CHEMICALS LISTED IN 40 CFR 60.489 AFFECTED FACILITY AS DEFINED IN 40 CFR 60.480(A)(2) = FACILITY IS AN AFFECTED FACILITY AS DEFINED IN 40 CFR 60.480(A)(2) 40 CFR 60 (NSPS) SUBPART VV CONSTRUCTION/MODIFICATION (RECONSTRUCTION) DATE = AFTER JANUARY 5, 1981 40 CFR 60 SUBPART VV DESIGN CAPACITY = SITE WITH DESIGN CAPACITY LESS THAN 1,000 MEGAGRAMS PER YEAR	
FUGA100	40 CFR Part 60, Subpart VV	60VV-6	PRODUCES CHEMICALS LISTED IN 40 CFR 60.489 = DOES NOT PRODUCE ANY CHEMICAL LISTED IN 40 CFR 60.489 AS INTERMEDIATE OR FINAL PRODUCT	
FUGA100B	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	R5352-7	Title 30 TAC § 115.352 Applicable = Site is not a petroleum refinery, synthetic organic chemical, polymer resin or methyl tert-butyl ether (MTBE) manufacturing process nor a natural gas/gasoline processing operation as defined in 30 TAC 115.10.	
FUGA100B	40 CFR Part 60, Subpart VV	60VV-1	PRODUCES CHEMICALS LISTED IN 40 CFR 60.489 = PRODUCES AS INTERMEDIATE OR FINAL PRODUCT ONE OR MORE CHEMICALS LISTED IN 40 CFR 60.489 AFFECTED FACILITY AS DEFINED IN 40 CFR 60.480(A)(2) = FACILITY IS AN AFFECTED FACILITY AS DEFINED IN 40 CFR 60.480(A)(2) 40 CFR 60 (NSPS) SUBPART VV CONSTRUCTION/MODIFICATION (RECONSTRUCTION) DATE = AFTER JANUARY 5, 1981 40 CFR 60 SUBPART VV DESIGN CAPACITY = SITE WITH DESIGN CAPACITY LESS THAN 1,000 MEGAGRAMS PER YEAR	
FUGA100B	40 CFR Part 60, Subpart VV	60VV-7	PRODUCES CHEMICALS LISTED IN 40 CFR 60.489 = DOES NOT PRODUCE ANY CHEMICAL LISTED IN 40 CFR 60.489 AS INTERMEDIATE OR FINAL PRODUCT	
FUGA2,300B	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	R5352-8	Title 30 TAC § 115.352 Applicable = Site is not a petroleum refinery, synthetic organic chemical, polymer resin or methyl tert-butyl ether (MTBE) manufacturing process nor a natural gas/gasoline processing operation as defined in 30 TAC 115.10.	
FUGA2,300B	40 CFR Part 60, Subpart VV	60VV-1	PRODUCES CHEMICALS LISTED IN 40 CFR 60.489 = PRODUCES AS INTERMEDIATE OR FINAL PRODUCT ONE OR MORE CHEMICALS LISTED IN 40 CFR 60.489 AFFECTED FACILITY AS DEFINED IN 40 CFR 60.480(A)(2) = FACILITY IS AN AFFECTED FACILITY AS DEFINED IN 40 CFR 60.480(A)(2)	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			40 CFR 60 (NSPS) SUBPART VV CONSTRUCTION/MODIFICATION (RECONSTRUCTION) DATE = AFTER JANUARY 5, 1981 40 CFR 60 SUBPART VV DESIGN CAPACITY = SITE WITH DESIGN CAPACITY LESS THAN 1,000 MEGAGRAMS PER YEAR	
FUGK600	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	R5352-11	Title 30 TAC § 115.352 Applicable = Site is not a petroleum refinery, synthetic organic chemical, polymer resin or methyl tert-butyl ether (MTBE) manufacturing process nor a natural gas/gasoline processing operation as defined in 30 TAC 115.10.	
FUGK600	40 CFR Part 60, Subpart VV	60VV-1	PRODUCES CHEMICALS LISTED IN 40 CFR 60.489 = PRODUCES AS INTERMEDIATE OR FINAL PRODUCT ONE OR MORE CHEMICALS LISTED IN 40 CFR 60.489 AFFECTED FACILITY AS DEFINED IN 40 CFR 60.480(A)(2) = FACILITY IS AN AFFECTED FACILITY AS DEFINED IN 40 CFR 60.480(A)(2) 40 CFR 60 (NSPS) SUBPART VV CONSTRUCTION/MODIFICATION (RECONSTRUCTION) DATE = AFTER JANUARY 5, 1981 40 CFR 60 SUBPART VV DESIGN CAPACITY = SITE WITH DESIGN CAPACITY LESS THAN 1,000 MEGAGRAMS PER YEAR	
FUGK600	40 CFR Part 60, Subpart VV	60VV-11	PRODUCES CHEMICALS LISTED IN 40 CFR 60.489 = DOES NOT PRODUCE ANY CHEMICAL LISTED IN 40 CFR 60.489 AS INTERMEDIATE OR FINAL PRODUCT	
FUGK600B	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	R5352-12	Title 30 TAC § 115.352 Applicable = Site is not a petroleum refinery, synthetic organic chemical, polymer resin or methyl tert-butyl ether (MTBE) manufacturing process nor a natural gas/gasoline processing operation as defined in 30 TAC 115.10.	
FUGK600B	40 CFR Part 60, Subpart VV	60VV-1	PRODUCES CHEMICALS LISTED IN 40 CFR 60.489 = PRODUCES AS INTERMEDIATE OR FINAL PRODUCT ONE OR MORE CHEMICALS LISTED IN 40 CFR 60.489 AFFECTED FACILITY AS DEFINED IN 40 CFR 60.480(A)(2) = FACILITY IS AN AFFECTED FACILITY AS DEFINED IN 40 CFR 60.480(A)(2) 40 CFR 60 (NSPS) SUBPART VV CONSTRUCTION/MODIFICATION (RECONSTRUCTION) DATE = AFTER JANUARY 5, 1981 40 CFR 60 SUBPART VV DESIGN CAPACITY = SITE WITH DESIGN CAPACITY LESS THAN 1,000 MEGAGRAMS PER YEAR	
FUGK600B	40 CFR Part 60, Subpart VV	60VV-12	PRODUCES CHEMICALS LISTED IN 40 CFR 60.489 = DOES NOT PRODUCE ANY CHEMICAL LISTED IN 40 CFR 60.489 AS INTERMEDIATE OR FINAL PRODUCT	
FUGR1,200	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	R5352-13	Title 30 TAC § 115.352 Applicable = Site is not a petroleum refinery, synthetic organic chemical, polymer resin or methyl tert-butyl ether (MTBE) manufacturing process nor a natural gas/gasoline processing operation as defined in 30 TAC 115.10.	
FUGR1,200	40 CFR Part 60, Subpart VV	60VV-1	PRODUCES CHEMICALS LISTED IN 40 CFR 60.489 = PRODUCES AS INTERMEDIATE OR FINAL PRODUCT ONE OR MORE CHEMICALS LISTED IN 40 CFR 60.489 AFFECTED FACILITY AS DEFINED IN 40 CFR 60.480(A)(2) = FACILITY IS AN AFFECTED FACILITY AS DEFINED IN 40 CFR 60.480(A)(2) 40 CFR 60 (NSPS) SUBPART VV CONSTRUCTION/MODIFICATION (RECONSTRUCTION) DATE = AFTER JANUARY 5, 1981 40 CFR 60 SUBPART VV DESIGN CAPACITY = SITE WITH DESIGN CAPACITY LESS THAN 1,000 MEGAGRAMS PER YEAR	
FUGR1,200	40 CFR Part 60,	60VV-13	PRODUCES CHEMICALS LISTED IN 40 CFR 60.489 = DOES NOT PRODUCE ANY CHEMICAL LISTED IN 40 CFR	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	Subpart VV		60.489 AS INTERMEDIATE OR FINAL PRODUCT	
FUGR1,200B	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	R5352-14	Title 30 TAC § 115.352 Applicable = Site is not a petroleum refinery, synthetic organic chemical, polymer resin or methyl tert-butyl ether (MTBE) manufacturing process nor a natural gas/gasoline processing operation as defined in 30 TAC 115.10.	
FUGR1,200B	40 CFR Part 60, Subpart VV	60VV-1	PRODUCES CHEMICALS LISTED IN 40 CFR 60.489 = PRODUCES AS INTERMEDIATE OR FINAL PRODUCT ONE OR MORE CHEMICALS LISTED IN 40 CFR 60.489 AFFECTED FACILITY AS DEFINED IN 40 CFR 60.480(A)(2) = FACILITY IS AN AFFECTED FACILITY AS DEFINED IN 40 CFR 60.480(A)(2) 40 CFR 60 (NSPS) SUBPART VV CONSTRUCTION/MODIFICATION (RECONSTRUCTION) DATE = AFTER JANUARY 5, 1981 40 CFR 60 SUBPART VV DESIGN CAPACITY = SITE WITH DESIGN CAPACITY LESS THAN 1,000 MEGAGRAMS PER YEAR	
FUGR1,200B	40 CFR Part 60, Subpart VV	60VV-14	PRODUCES CHEMICALS LISTED IN 40 CFR 60.489 = DOES NOT PRODUCE ANY CHEMICAL LISTED IN 40 CFR 60.489 AS INTERMEDIATE OR FINAL PRODUCT	
FUGR3,400	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	R5352-15	Title 30 TAC § 115.352 Applicable = Site is not a petroleum refinery, synthetic organic chemical, polymer resin or methyl tert-butyl ether (MTBE) manufacturing process nor a natural gas/gasoline processing operation as defined in 30 TAC 115.10.	
FUGR3,400	40 CFR Part 60, Subpart VV	60VV-1	PRODUCES CHEMICALS LISTED IN 40 CFR 60.489 = PRODUCES AS INTERMEDIATE OR FINAL PRODUCT ONE OR MORE CHEMICALS LISTED IN 40 CFR 60.489 AFFECTED FACILITY AS DEFINED IN 40 CFR 60.480(A)(2) = FACILITY IS AN AFFECTED FACILITY AS DEFINED IN 40 CFR 60.480(A)(2) 40 CFR 60 (NSPS) SUBPART VV CONSTRUCTION/MODIFICATION (RECONSTRUCTION) DATE = AFTER JANUARY 5, 1981 40 CFR 60 SUBPART VV DESIGN CAPACITY = SITE WITH DESIGN CAPACITY LESS THAN 1,000 MEGAGRAMS PER YEAR	
FUGR3,400	40 CFR Part 60, Subpart VV	60VV-15	PRODUCES CHEMICALS LISTED IN 40 CFR 60.489 = DOES NOT PRODUCE ANY CHEMICAL LISTED IN 40 CFR 60.489 AS INTERMEDIATE OR FINAL PRODUCT	
FUGR3,400B	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	R5352-16	Title 30 TAC § 115.352 Applicable = Site is not a petroleum refinery, synthetic organic chemical, polymer resin or methyl tert-butyl ether (MTBE) manufacturing process nor a natural gas/gasoline processing operation as defined in 30 TAC 115.10.	
FUGR3,400B	40 CFR Part 60, Subpart VV	60VV-1	PRODUCES CHEMICALS LISTED IN 40 CFR 60.489 = PRODUCES AS INTERMEDIATE OR FINAL PRODUCT ONE OR MORE CHEMICALS LISTED IN 40 CFR 60.489 AFFECTED FACILITY AS DEFINED IN 40 CFR 60.480(A)(2) = FACILITY IS AN AFFECTED FACILITY AS DEFINED IN 40 CFR 60.480(A)(2) 40 CFR 60 (NSPS) SUBPART VV CONSTRUCTION/MODIFICATION (RECONSTRUCTION) DATE = AFTER JANUARY 5, 1981 40 CFR 60 SUBPART VV DESIGN CAPACITY = SITE WITH DESIGN CAPACITY LESS THAN 1,000 MEGAGRAMS PER YEAR	
FUGR3,400B	40 CFR Part 60, Subpart VV	60VV-16	PRODUCES CHEMICALS LISTED IN 40 CFR 60.489 = DOES NOT PRODUCE ANY CHEMICAL LISTED IN 40 CFR 60.489 AS INTERMEDIATE OR FINAL PRODUCT	
PA-12	30 TAC Chapter 115, Pet. Refinery	R5352-19	Title 30 TAC § 115.352 Applicable = Site is not a petroleum refinery, synthetic organic chemical, polymer resin or methyl tert-butyl ether (MTBE) manufacturing process nor a natural gas/gasoline processing operation as defined in	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	& Petrochemicals		30 TAC 115.10.	
PA-12	40 CFR Part 60, Subpart VV	60VV-1	<p>PRODUCES CHEMICALS LISTED IN 40 CFR 60.489 = PRODUCES AS INTERMEDIATE OR FINAL PRODUCT ONE OR MORE CHEMICALS LISTED IN 40 CFR 60.489</p> <p>AFFECTED FACILITY AS DEFINED IN 40 CFR 60.480(A)(2) = FACILITY IS AN AFFECTED FACILITY AS DEFINED IN 40 CFR 60.480(A)(2)</p> <p>40 CFR 60 (NSPS) SUBPART VV CONSTRUCTION/MODIFICATION (RECONSTRUCTION) DATE = AFTER JANUARY 5, 1981</p> <p>40 CFR 60 SUBPART VV DESIGN CAPACITY = SITE WITH DESIGN CAPACITY LESS THAN 1,000 MEGAGRAMS PER YEAR</p>	
PA-12	40 CFR Part 60, Subpart VV	60VV-19	PRODUCES CHEMICALS LISTED IN 40 CFR 60.489 = DOES NOT PRODUCE ANY CHEMICAL LISTED IN 40 CFR 60.489 AS INTERMEDIATE OR FINAL PRODUCT	
PA-14	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	R5352-20	Title 30 TAC § 115.352 Applicable = Site is not a petroleum refinery, synthetic organic chemical, polymer resin or methyl tert-butyl ether (MTBE) manufacturing process nor a natural gas/gasoline processing operation as defined in 30 TAC 115.10.	
PA-14	40 CFR Part 60, Subpart VV	60VV-1	<p>PRODUCES CHEMICALS LISTED IN 40 CFR 60.489 = PRODUCES AS INTERMEDIATE OR FINAL PRODUCT ONE OR MORE CHEMICALS LISTED IN 40 CFR 60.489</p> <p>AFFECTED FACILITY AS DEFINED IN 40 CFR 60.480(A)(2) = FACILITY IS AN AFFECTED FACILITY AS DEFINED IN 40 CFR 60.480(A)(2)</p> <p>40 CFR 60 (NSPS) SUBPART VV CONSTRUCTION/MODIFICATION (RECONSTRUCTION) DATE = AFTER JANUARY 5, 1981</p> <p>40 CFR 60 SUBPART VV DESIGN CAPACITY = SITE WITH DESIGN CAPACITY LESS THAN 1,000 MEGAGRAMS PER YEAR</p>	
PA-14	40 CFR Part 60, Subpart VV	60VV-20	PRODUCES CHEMICALS LISTED IN 40 CFR 60.489 = DOES NOT PRODUCE ANY CHEMICAL LISTED IN 40 CFR 60.489 AS INTERMEDIATE OR FINAL PRODUCT	
PA-15	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	R5352-21	Title 30 TAC § 115.352 Applicable = Site is not a petroleum refinery, synthetic organic chemical, polymer resin or methyl tert-butyl ether (MTBE) manufacturing process nor a natural gas/gasoline processing operation as defined in 30 TAC 115.10.	
PA-15	40 CFR Part 60, Subpart VV	60VV-1	<p>PRODUCES CHEMICALS LISTED IN 40 CFR 60.489 = PRODUCES AS INTERMEDIATE OR FINAL PRODUCT ONE OR MORE CHEMICALS LISTED IN 40 CFR 60.489</p> <p>AFFECTED FACILITY AS DEFINED IN 40 CFR 60.480(A)(2) = FACILITY IS AN AFFECTED FACILITY AS DEFINED IN 40 CFR 60.480(A)(2)</p> <p>40 CFR 60 (NSPS) SUBPART VV CONSTRUCTION/MODIFICATION (RECONSTRUCTION) DATE = AFTER JANUARY 5, 1981</p> <p>40 CFR 60 SUBPART VV DESIGN CAPACITY = SITE WITH DESIGN CAPACITY LESS THAN 1,000 MEGAGRAMS PER YEAR</p>	
PA-15	40 CFR Part 60, Subpart VV	60VV-21	PRODUCES CHEMICALS LISTED IN 40 CFR 60.489 = DOES NOT PRODUCE ANY CHEMICAL LISTED IN 40 CFR 60.489 AS INTERMEDIATE OR FINAL PRODUCT	
R-400FUG	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	R9600-11	Title 30 TAC § 115.352 Applicable = Site is not a petroleum refinery, synthetic organic chemical, polymer resin or methyl tert-butyl ether (MTBE) manufacturing process nor a natural gas/gasoline processing operation as defined in 30 TAC 115.10.	
R-400FUG	40 CFR Part 60, Subpart VV	60VV-1	PRODUCES CHEMICALS LISTED IN 40 CFR 60.489 = PRODUCES AS INTERMEDIATE OR FINAL PRODUCT ONE OR MORE CHEMICALS LISTED IN 40 CFR 60.489	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>AFFECTED FACILITY AS DEFINED IN 40 CFR 60.480(A)(2) = FACILITY IS AN AFFECTED FACILITY AS DEFINED IN 40 CFR 60.480(A)(2)</p> <p>40 CFR 60 (NSPS) SUBPART VV CONSTRUCTION/MODIFICATION (RECONSTRUCTION) DATE = AFTER JANUARY 5, 1981</p> <p>40 CFR 60 SUBPART VV DESIGN CAPACITY = SITE WITH DESIGN CAPACITY LESS THAN 1,000 MEGAGRAMS PER YEAR</p>	
R-400FUG	40 CFR Part 60, Subpart VV	R9600-11	PRODUCES CHEMICALS LISTED IN 40 CFR 60.489 = DOES NOT PRODUCE ANY CHEMICAL LISTED IN 40 CFR 60.489 AS INTERMEDIATE OR FINAL PRODUCT	
T1002	30 TAC Chapter 115, Water Separation	R5131-02	<p>ALTERNATE CONTROL REQUIREMENT (ACR) [REG V] = The executive director (or the EPA Administrator) has not approved an ACR or exemption criteria in accordance with 30 TAC § 115.910.</p> <p>EXEMPTION FROM CONTROL REQUIREMENTS OF 115.132 [REG V] = Any single or multiple compartment VOC water separator which separates materials having a true vapor pressure less than 0.5 psia (3.4 kPa) obtained from any equipment.</p>	
A100D	30 TAC Chapter 111, Visible Emissions	R111-1	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = The executive director and Administrator have determined that 30 TAC § 111.111(a)(1)(F) may be used to comply with the appropriate opacity standard since the gas stream contains condensed water vapor which could interfere with proper CEMS operation.</p> <p>Construction Date = On or before January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.</p>	
A100D	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is less than 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
A-200C	30 TAC Chapter 115, Vent Gas Controls	R5121-2	<p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is less than 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
A-300	30 TAC Chapter 115, Vent Gas Controls	R5121-3	<p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is less than 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
EP-600-1	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
EP-600-1	30 TAC Chapter 115, Vent Gas Controls	R5121-2	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Vapor recovery system, as defined in 30 TAC § 115.10, other than an afterburner, blast furnace combustion device, boiler, catalytic or direct flame incinerator, carbon adsorption system, chiller, flare or vapor combustor.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p>	
EV1	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
EV2	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
EV4	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Vapor recovery system, as defined in 30 TAC § 115.10, other than an afterburner, blast furnace combustion device, boiler, catalytic or direct flame incinerator, carbon adsorption system, chiller, flare or vapor combustor.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p>	
EV5	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
EV6	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
K-201A	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
K-300A	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Vapor recovery system, as defined in 30 TAC § 115.10, other than an afterburner, blast furnace combustion device, boiler, catalytic or direct flame incinerator, carbon adsorption system, chiller, flare or vapor combustor.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p>	
K-301	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Vapor recovery system, as defined in 30 TAC § 115.10, other than an afterburner, blast furnace combustion device, boiler, catalytic or direct flame incinerator, carbon adsorption system, chiller, flare or vapor combustor.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p>	
K-400B	30 TAC Chapter 115, Vent Gas Controls	R5121-14	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Vapor recovery system, as defined in 30 TAC § 115.10, other than an afterburner, blast furnace combustion device, boiler, catalytic or direct flame incinerator, carbon adsorption system, chiller, flare or vapor combustor.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
K-500	30 TAC Chapter 115, Vent Gas Controls	R5121-15	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>B, Division 2.</p> <p>Control Device Type = Vapor recovery system, as defined in 30 TAC § 115.10, other than an afterburner, blast furnace combustion device, boiler, catalytic or direct flame incinerator, carbon adsorption system, chiller, flare or vapor combustor.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
LUWA	30 TAC Chapter 115, Vent Gas Controls	R5121-17	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p>	
R-100D	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Vapor recovery system, as defined in 30 TAC § 115.10, other than an afterburner, blast furnace combustion device, boiler, catalytic or direct flame incinerator, carbon adsorption system, chiller, flare or vapor combustor.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p>	
R-3DEHYD	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			requirements of 30 TAC § 115.126(4) are being selected.	
R-400	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Vapor recovery system, as defined in 30 TAC § 115.10, other than an afterburner, blast furnace combustion device, boiler, catalytic or direct flame incinerator, carbon adsorption system, chiller, flare or vapor combustor.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p>	
R-400A	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Vapor recovery system, as defined in 30 TAC § 115.10, other than an afterburner, blast furnace combustion device, boiler, catalytic or direct flame incinerator, carbon adsorption system, chiller, flare or vapor combustor.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p>	

\* - The "unit attributes" or operating conditions that determine what requirements apply

\*\* - Notes changes made to the automated results from the DSS, and a brief explanation why

## NSR Versus Title V FOP

The state of Texas has two Air permitting programs, New Source Review (NSR) and Title V Federal Operating Permits. The two programs are substantially different both in intent and permit content.

NSR is a preconstruction permitting program authorized by the Texas Clean Air Act and Title I of the Federal Clean Air Act (FCAA). The processing of these permits is governed by 30 Texas Administrative Code (TAC) Chapter 116.111. The Title V Federal Operating Program is a federal program authorized under Title V of the FCAA that has been delegated to the state of Texas to administer and is governed by 30 TAC Chapter 122. The major differences between the two permitting programs are listed in the table below:

NSR Permit	Federal Operating Permit(FOP)
Issued Prior to new Construction or modification of an existing facility	For initial permit with application shield, can be issued after operation commences; significant revisions require approval prior to operation.
Authorizes air emissions	Codifies existing applicable requirements, does not authorize new emissions
Ensures issued permits are protective of the environment and human health by conducting a health effects review and that requirement for best available control technology (BACT) is implemented.	Applicable requirements listed in permit are used by the inspectors to ensure proper operation of the site as authorized. Ensures that adequate monitoring is in place to allow compliance determination with the FOP.
Up to two Public notices may be required. Opportunity for public comment and contested case hearings for some authorizations.	One public notice required. Opportunity for public comments. No contested case hearings.
Applies to all point source emissions in the state.	Applies to all major sources and some non-major sources identified by the EPA.
Applies to facilities: a portion of site or individual emission sources	One or multiple FOPs cover the entire site (consists of multiple facilities)
Permits include terms and conditions under which the applicant must construct and operate its various equipment and processes on a facility basis.	Permits include terms and conditions that specify the general operational requirements of the site; and also include codification of all applicable requirements for emission units at the site.
Opportunity for EPA review for Federal Prevention of Significant Deterioration (PSD) and Nonattainment (NA) permits for major sources.	Opportunity for EPA review, Affected states review, and a Public petition period for every FOP.
Permits have a table listing maximum emission limits for pollutants	Permit has an applicable requirements table and Periodic Monitoring (PM) / Compliance Assurance Monitoring (CAM) tables which document applicable monitoring requirements.
Permits can be altered or amended upon application by company. Permits must be issued before construction or modification of facilities can begin.	Permits can be revised through several revision processes, which provide for different levels of public notice and opportunity to comment. Changes that would be significant revisions require that a revised permit be issued before those changes can be operated.
NSR permits are issued independent of FOP requirements.	FOP are independent of NSR permits, but contain a list of all NSR permits incorporated by reference

## New Source Review Requirements

Below is a list of the New Source Review (NSR) permits for the permitted area. These NSR permits are incorporated by reference into the operating permit and are enforceable under it. These permits can be found in the main TCEQ file room, located on the first floor of Building E, 12100 Park 35 Circle, Austin, Texas. The Public Education Program may be contacted at 1-800-687-4040 or the Air Permits Division (APD) may be contacted at 1-512-239-1250 for help with any question.

Additionally, the site contains emission units that are permitted by rule under the requirements of 30 TAC Chapter 106, Permits by Rule. The following table specifies the permits by rule that apply to the site. All current permits by rule are contained in Chapter 106. Outdated 30 TAC Chapter 106 permits by rule may be viewed at the following Web site:

[www.tceq.texas.gov/permitting/air/permitbyrule/historical\\_rules/old106list/index106.html](http://www.tceq.texas.gov/permitting/air/permitbyrule/historical_rules/old106list/index106.html)

Outdated Standard Exemption lists may be viewed at the following Web site:

[www.tceq.texas.gov/permitting/air/permitbyrule/historical\\_rules/oldselist/se\\_index.html](http://www.tceq.texas.gov/permitting/air/permitbyrule/historical_rules/oldselist/se_index.html)

<b>Title 30 TAC Chapter 116 Permits, Special Permits, and Other Authorizations (Other Than Permits By Rule, PSD Permits, or NA Permits) for the Application Area.</b>
Authorization No.: 19449
Authorization No.: 19803
Authorization No.: 3847
Authorization No.: 524
Authorization No.: 562
Authorization No.: 563
Authorization No.: 56693
Authorization No.: 56694
Authorization No.: 56695
Authorization No.: 56696
Authorization No.: 56697
Authorization No.: 56698
Authorization No.: 56699
Authorization No.: 6449
Authorization No.: 6450
Authorization No.: 8207
Authorization No.: 9001
Authorization No.: 9536
Authorization No.: 9600

<b>Permits By Rule (30 TAC Chapter 106) for the Application Area</b>	
Number: 106.124	Version No./Date: 03/14/1997
Number: 106.144	Version No./Date: 09/04/2000
Number: 106.183	Version No./Date: 06/18/1997
Number: 106.183	Version No./Date: 09/04/2000
Number: 106.261	Version No./Date: 12/24/1998
Number: 106.261	Version No./Date: 11/01/2003
Number: 106.262	Version No./Date: 03/14/1997
Number: 106.262	Version No./Date: 12/24/1998
Number: 106.262	Version No./Date: 09/04/2000
Number: 106.262	Version No./Date: 11/01/2003
Number: 106.472	Version No./Date: 03/14/1997
Number: 106.472	Version No./Date: 09/04/2000
Number: 106.473	Version No./Date: 03/14/1997
Number: 106.473	Version No./Date: 09/04/2000
Number: 106.511	Version No./Date: 09/04/2000
Number: 106.532	Version No./Date: 03/14/1997
Number: 15	Version No./Date: 01/08/1980
Number: 51	Version No./Date: 09/12/1989
Number: 99	Version No./Date: 09/23/1982
Number: 102	Version No./Date: 05/12/1981
Number: 106	Version No./Date: 05/04/1994
Number: 124	Version No./Date: 09/23/1982

### **Emission Units and Emission Points**

In air permitting terminology, any source capable of generating emissions (for example, an engine or a sandblasting area) is called an Emission Unit. For purposes of Title V, emission units are specifically listed in the operating permit when they have applicable requirements other than New Source Review (NSR), or when they are listed in the permit shield table.

The actual physical location where the emissions enter the atmosphere (for example, an engine stack or a sandblasting yard) is called an emission point. For New Source Review preconstruction permitting purposes, every emission unit has an associated emission point. Emission limits are listed in an NSR permit, associated with an emission point. This list of emission points and emission limits per pollutant is commonly referred to as the “Maximum Allowable Emission Rate Table”, or “MAERT” for short. Specifically, the MAERT lists the Emission Point Number (EPN) that identifies the emission point, followed immediately by the Source Name, identifying the emission unit that is the source of those emissions on this table.

Thus, by reference, an emission unit in a Title V operating permit is linked by reference number to an NSR authorization, and its related emission point.

### **Monitoring Sufficiency**

Federal and state rules, 40 CFR § 70.6(a)(3)(i)(B) and 30 TAC § 122.142(c) respectively, require that each federal operating permit include additional monitoring for applicable requirements that lack periodic or instrumental monitoring (which may include recordkeeping that serves as monitoring) that yields reliable data from a relevant time period that are representative of the emission unit's compliance with the applicable emission limitation or standard. Furthermore, the federal operating permit must include compliance assurance monitoring (CAM) requirements for emission sources that meet the applicability criteria of 40 CFR Part 64 in accordance with 40 CFR § 70.6(a)(3)(i)(A) and 30 TAC § 122.604(b).

With the exception of any emission units listed in the Periodic Monitoring or CAM Summaries in the FOP, the TCEQ Executive Director has determined that the permit contains sufficient monitoring, testing, recordkeeping, and reporting requirements that assure compliance with the applicable requirements. If applicable, each emission unit that requires additional monitoring in the form of periodic monitoring or CAM is described in further detail under the Rationale for CAM/PM Methods Selected section following this paragraph.

## Rationale for Compliance Assurance Monitoring (CAM)/ Periodic Monitoring Methods Selected

### Periodic Monitoring:

The Federal Clean Air Act requires that each federal operating permit include monitoring sufficient to assure compliance with the terms and conditions of the permit. Most of the emission limits and standards applicable to emission units at Title V sources include adequate monitoring to show that the units meet the limits and standards. For those requirements that do not include monitoring, or where the monitoring is not sufficient to assure compliance, the federal operating permit must include such monitoring for the emission units affected. The following emission units are subject to periodic monitoring requirements because the emission units are subject to an emission limitation or standard for an air pollutant (or surrogate thereof) in an applicable requirement that does not already require monitoring, or the monitoring for the applicable requirement is not sufficient to assure compliance:

<b>Unit/Group/Process Information</b>	
ID No.: A100D	
Control Device ID No.: N/A	Control Device Type: N/A
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R111-1
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(A)
<b>Monitoring Information</b>	
Indicator: Opacity	
Minimum Frequency: Once per month	
Averaging Period: Six-minutes	
Deviation Limit: Opacity shall not exceed 30% averaged over a six-minute period.	
<p>Basis of monitoring:                      The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p>	

<b>Unit/Group/Process Information</b>	
ID No.: R-400	
Control Device ID No.: Z5400	Control Device Type: Absorber (Caustic Absorber)
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-1
Pollutant: VOC	Main Standard: § 115.121(a)(1)
<b>Monitoring Information</b>	
Indicator: Liquid Flow Rate	
Minimum Frequency: once per week	
Averaging Period: n/a*	
Deviation Limit: Minimum liquid flow rate = 28 gpm	
Basis of monitoring: The option to monitor the liquid flow rate, liquid supply pressure, or the liquid flow rate and gas flow rate are provided as monitoring options because monitoring these parameters can indicate malfunctions in the liquid pumping equipment, blockage of pipes or spray nozzles.	

\*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

<b>Unit/Group/Process Information</b>	
ID No.: R-400	
Control Device ID No.: Z5400	Control Device Type: Absorber (Caustic Absorber)
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-1
Pollutant: VOC	Main Standard: § 115.121(a)(1)
<b>Monitoring Information</b>	
Indicator: pH	
Minimum Frequency: once per week	
Averaging Period: n/a*	
Deviation Limit: Minimum pH = 13 (measured as 5% caustic)	
Basis of monitoring: The option to monitor pH or caustic concentration is appropriate for caustic absorption to indicate absorbing liquid saturation and can indicate if the proper caustic concentration is being utilized to absorb the VOC. Additionally, monitoring indicators to measure absorbing liquid saturation is commonly required in federal rules including: 40 CFR Part 60, Subparts III, NNN, and RRR and 40 CFR Part 63, Subpart G.	

\*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

<b>Unit/Group/Process Information</b>	
ID No.: R-400A	
Control Device ID No.: Z5400	Control Device Type: Absorber (Caustic Absorber)
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-1
Pollutant: VOC	Main Standard: § 115.121(a)(1)
<b>Monitoring Information</b>	
Indicator: Liquid Flow Rate	
Minimum Frequency: once per week	
Averaging Period: n/a*	
Deviation Limit: Minimum liquid flow rate = 28 gpm	
Basis of monitoring: The option to monitor the liquid flow rate, liquid supply pressure, or the liquid flow rate and gas flow rate are provided as monitoring options because monitoring these parameters can indicate malfunctions in the liquid pumping equipment, blockage of pipes or spray nozzles.	

\*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

<b>Unit/Group/Process Information</b>	
ID No.: R-400A	
Control Device ID No.: Z5400	Control Device Type: Absorber (Caustic Absorber)
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-1
Pollutant: VOC	Main Standard: § 115.121(a)(1)
<b>Monitoring Information</b>	
Indicator: pH	
Minimum Frequency: once per week	
Averaging Period: n/a*	
Deviation Limit: Minimum pH = 13 (measured as 5% caustic)	
Basis of monitoring: The option to monitor pH or caustic concentration is appropriate for caustic absorption to indicate absorbing liquid saturation and can indicate if the proper caustic concentration is being utilized to absorb the VOC. Additionally, monitoring indicators to measure absorbing liquid saturation is commonly required in federal rules including: 40 CFR Part 60, Subparts III, NNN, and RRR and 40 CFR Part 63, Subpart G.	

\*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

**Compliance Assurance Monitoring (CAM):**

Compliance Assurance Monitoring (CAM) is a federal monitoring program established under Title 40 Code of Federal Regulations Part 64 (40 CFR Part 64).

Emission units are subject to CAM requirements if they meet the following criteria:

1. the emission unit is subject to an emission limitation or standard for an air pollutant (or surrogate thereof) in an applicable requirement;
2. the emission unit uses a control device to achieve compliance with the emission limitation or standard specified in the applicable requirement; and
3. the emission unit has the pre-control device potential to emit greater than or equal to the amount in tons per year for a site to be classified as a major source.

The following table(s) identify the emission unit(s) that are subject to CAM:

<b>Unit/Group/Process Information</b>	
ID No.: EP-600-1	
Control Device ID No.: Z4606	Control Device Type: Absorber (Direct Absorption)
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-2
Pollutant: VOC	Main Standard: § 115.121(a)(1)
<b>Monitoring Information</b>	
Indicator: Outlet Gas Temperature	
Minimum Frequency: once per day	
Averaging Period: n/a*	
Deviation Limit: Maximum outlet gas temperature = 125 degrees Fahrenheit	
Basis of CAM: The option to monitor outlet gas temperature can indicate the amount of VOC from the gas stream that can be absorbed by the scrubbing liquid. As the temperature increases, the vapor pressure and energy level of the gas stream increases, raising the energy level of the absorbed molecules. At higher energy levels the absorbed molecules may have sufficient energy to overcome the attraction of the absorbing liquid. Therefore, absorbing liquids capture more air contaminants at low temperatures. Temperature is a good indicator of proper operation of the absorber.	

\*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

<b>Unit/Group/Process Information</b>	
ID No.: EP-600-1	
Control Device ID No.: Z4606	Control Device Type: Absorber (Direct Absorption)
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-2
Pollutant: VOC	Main Standard: § 115.121(a)(1)
<b>Monitoring Information</b>	
Indicator: Liquid Flow Rate	
Minimum Frequency: once per day	
Averaging Period: n/a*	
Deviation Limit: Minimum liquid flow rate = 10 gpm	
Basis of CAM: The option to monitor the liquid flow rate, liquid supply pressure, and the liquid flow rate and gas flow rate are provided as monitoring options because monitoring these parameters can indicate malfunctions in the liquid pumping equipment, blockage of pipes or spray nozzles.	

\*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

<b>Unit/Group/Process Information</b>	
ID No.: EV4	
Control Device ID No.: V004	Control Device Type: Absorber (Direct Absorption)
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-1
Pollutant: VOC	Main Standard: § 115.121(a)(1)
<b>Monitoring Information</b>	
Indicator: Outlet Gas Temperature	
Minimum Frequency: once per day	
Averaging Period: n/a*	
Deviation Limit: Maximum outlet gas temperature = 100 degrees Fahrenheit	
Basis of CAM: The option to monitor outlet gas temperature can indicate the amount of VOC from the gas stream that can be absorbed by the scrubbing liquid. As the temperature increases, the vapor pressure and energy level of the gas stream increases, raising the energy level of the absorbed molecules. At higher energy levels the absorbed molecules may have sufficient energy to overcome the attraction of the absorbing liquid. Therefore, absorbing liquids capture more air contaminants at low temperatures. Temperature is a good indicator of proper operation of the absorber.	

\*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

<b>Unit/Group/Process Information</b>	
ID No.: EV4	
Control Device ID No.: V004	Control Device Type: Absorber (Direct Absorption)
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-1
Pollutant: VOC	Main Standard: § 115.121(a)(1)
<b>Monitoring Information</b>	
Indicator: Liquid Flow Rate	
Minimum Frequency: once per day	
Averaging Period: n/a*	
Deviation Limit: Minimum liquid flow rate = 185 gpm	
Basis of CAM: The option to monitor the liquid flow rate, liquid supply pressure, and the liquid flow rate and gas flow rate are provided as monitoring options because monitoring these parameters can indicate malfunctions in the liquid pumping equipment, blockage of pipes or spray nozzles.	

\*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

<b>Unit/Group/Process Information</b>	
ID No.: K-300A	
Control Device ID No.: Z4000	Control Device Type: Absorber (Direct Absorption)
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-1
Pollutant: VOC	Main Standard: § 115.121(a)(1)
<b>Monitoring Information</b>	
Indicator: Outlet Gas Temperature	
Minimum Frequency: once per day	
Averaging Period: n/a*	
Deviation Limit: Maximum outlet gas temperature = 114.7 degrees Fahrenheit	
Basis of CAM: The option to monitor outlet gas temperature can indicate the amount of VOC from the gas stream that can be absorbed by the scrubbing liquid. As the temperature increases, the vapor pressure and energy level of the gas stream increases, raising the energy level of the absorbed molecules. At higher energy levels the absorbed molecules may have sufficient energy to overcome the attraction of the absorbing liquid. Therefore, absorbing liquids capture more air contaminants at low temperatures. Temperature is a good indicator of proper operation of the absorber.	

\*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

<b>Unit/Group/Process Information</b>	
ID No.: K-300A	
Control Device ID No.: Z4000	Control Device Type: Absorber (Direct Absorption)
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-1
Pollutant: VOC	Main Standard: § 115.121(a)(1)
<b>Monitoring Information</b>	
Indicator: Liquid Flow Rate	
Minimum Frequency: once per day	
Averaging Period: n/a*	
Deviation Limit: Minimum liquid flow rate = 4 gpm	
Basis of CAM: The option to monitor the liquid flow rate, liquid supply pressure, and the liquid flow rate and gas flow rate are provided as monitoring options because monitoring these parameters can indicate malfunctions in the liquid pumping equipment, blockage of pipes or spray nozzles.	

\*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

<b>Unit/Group/Process Information</b>	
ID No.: K-301	
Control Device ID No.: Z4000	Control Device Type: Absorber (Direct Absorption)
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-1
Pollutant: VOC	Main Standard: § 115.121(a)(1)
<b>Monitoring Information</b>	
Indicator: Outlet Gas Temperature	
Minimum Frequency: once per day	
Averaging Period: n/a*	
Deviation Limit: Maximum outlet gas temperature = 114.7 degrees Fahrenheit	
Basis of CAM: The option to monitor outlet gas temperature can indicate the amount of VOC from the gas stream that can be absorbed by the scrubbing liquid. As the temperature increases, the vapor pressure and energy level of the gas stream increases, raising the energy level of the absorbed molecules. At higher energy levels the absorbed molecules may have sufficient energy to overcome the attraction of the absorbing liquid. Therefore, absorbing liquids capture more air contaminants at low temperatures. Temperature is a good indicator of proper operation of the absorber.	

\*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

<b>Unit/Group/Process Information</b>	
ID No.: K-301	
Control Device ID No.: Z4000	Control Device Type: Absorber (Direct Absorption)
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-1
Pollutant: VOC	Main Standard: § 115.121(a)(1)
<b>Monitoring Information</b>	
Indicator: Liquid Flow Rate	
Minimum Frequency: once per day	
Averaging Period: n/a*	
Deviation Limit: Minimum liquid flow rate = 4 gpm	
Basis of CAM: The option to monitor the liquid flow rate, liquid supply pressure, and the liquid flow rate and gas flow rate are provided as monitoring options because monitoring these parameters can indicate malfunctions in the liquid pumping equipment, blockage of pipes or spray nozzles.	

\*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

<b>Unit/Group/Process Information</b>	
ID No.: R-100D	
Control Device ID No.: Z5000	Control Device Type: Absorber (Direct Absorption)
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-1
Pollutant: VOC	Main Standard: § 115.121(a)(1)
<b>Monitoring Information</b>	
Indicator: Outlet Gas Temperature	
Minimum Frequency: once per day	
Averaging Period: n/a*	
Deviation Limit: Maximum outlet gas temperature = 120 degrees Fahrenheit	
Basis of CAM: The option to monitor outlet gas temperature can indicate the amount of VOC from the gas stream that can be absorbed by the scrubbing liquid. As the temperature increases, the vapor pressure and energy level of the gas stream increases, raising the energy level of the absorbed molecules. At higher energy levels the absorbed molecules may have sufficient energy to overcome the attraction of the absorbing liquid. Therefore, absorbing liquids capture more air contaminants at low temperatures. Temperature is a good indicator of proper operation of the absorber.	

\*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

<b>Unit/Group/Process Information</b>	
ID No.: R-100D	
Control Device ID No.: Z5000	Control Device Type: Absorber (Direct Absorption)
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-1
Pollutant: VOC	Main Standard: § 115.121(a)(1)
<b>Monitoring Information</b>	
Indicator: Liquid Flow Rate	
Minimum Frequency: once per day	
Averaging Period: n/a*	
Deviation Limit: Minimum liquid flow rate = 4 gpm	
Basis of CAM: The option to monitor the liquid flow rate, liquid supply pressure, and the liquid flow rate and gas flow rate are provided as monitoring options because monitoring these parameters can indicate malfunctions in the liquid pumping equipment, blockage of pipes or spray nozzles.	

\*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

## Available Unit Attribute Forms

OP-UA1 - Miscellaneous and Generic Unit Attributes  
OP-UA2 - Stationary Reciprocating Internal Combustion Engine Attributes  
OP-UA3 - Storage Tank/Vessel Attributes  
OP-UA4 - Loading/Unloading Operations Attributes  
OP-UA5 - Process Heater/Furnace Attributes  
OP-UA6 - Boiler/Steam Generator/Steam Generating Unit Attributes  
OP-UA7 - Flare Attributes  
OP-UA8 - Coal Preparation Plant Attributes  
OP-UA9 - Nonmetallic Mineral Process Plant Attributes  
OP-UA10 - Gas Sweetening/Sulfur Recovery Unit Attributes  
OP-UA11 - Stationary Turbine Attributes  
OP-UA12 - Fugitive Emission Unit Attributes  
OP-UA13 - Industrial Process Cooling Tower Attributes  
OP-UA14 - Water Separator Attributes  
OP-UA15 - Emission Point/Stationary Vent/Distillation Operation/Process Vent Attributes  
OP-UA16 - Solvent Degreasing Machine Attributes  
OP-UA17 - Distillation Unit Attributes  
OP-UA18 - Surface Coating Operations Attributes  
OP-UA19 - Wastewater Unit Attributes  
OP-UA20 - Asphalt Operations Attributes  
OP-UA21 - Grain Elevator Attributes  
OP-UA22 - Printing Attributes  
OP-UA24 - Wool Fiberglass Insulation Manufacturing Plant Attributes  
OP-UA25 - Synthetic Fiber Production Attributes  
OP-UA26 - Electroplating and Anodizing Unit Attributes  
OP-UA27 - Nitric Acid Manufacturing Attributes  
OP-UA28 - Polymer Manufacturing Attributes  
OP-UA29 - Glass Manufacturing Unit Attributes  
OP-UA30 - Kraft, Soda, Sulfite, and Stand-Alone Semicheical Pulp Mill Attributes  
OP-UA31 - Lead Smelting Attributes  
OP-UA32 - Copper and Zinc Smelting/Brass and Bronze Production Attributes  
OP-UA33 - Metallic Mineral Processing Plant Attributes  
OP-UA34 - Pharmaceutical Manufacturing  
OP-UA35 - Incinerator Attributes  
OP-UA36 - Steel Plant Unit Attributes  
OP-UA37 - Basic Oxygen Process Furnace Unit Attributes  
OP-UA38 - Lead-Acid Battery Manufacturing Plant Attributes  
OP-UA39 - Sterilization Source Attributes  
OP-UA40 - Ferroalloy Production Facility Attributes  
OP-UA41 - Dry Cleaning Facility Attributes  
OP-UA42 - Phosphate Fertilizer Manufacturing Attributes  
OP-UA43 - Sulfuric Acid Production Attributes  
OP-UA44 - Municipal Solid Waste Landfill/Waste Disposal Site Attributes  
OP-UA45 - Surface Impoundment Attributes  
OP-UA46 - Epoxy Resins and Non-Nylon Polyamides Production Attributes  
OP-UA47 - Ship Building and Ship Repair Unit Attributes  
OP-UA48 - Air Oxidation Unit Process Attributes  
OP-UA49 - Vacuum-Producing System Attributes  
OP-UA50 - Fluid Catalytic Cracking Unit Catalyst Regenerator/Fuel Gas Combustion Device/Claus Sulfur Recovery Plant Attributes

OP-UA51 - Dryer/Kiln/Oven Attributes  
OP-UA52 - Closed Vent Systems and Control Devices  
OP-UA53 - Beryllium Processing Attributes  
OP-UA54 - Mercury Chlor-Alkali Cell Attributes  
OP-UA55 - Transfer System Attributes  
OP-UA56 - Vinyl Chloride Process Attributes  
OP-UA57 - Cleaning/Depainting Operation Attributes  
OP-UA58 - Treatment Process Attributes  
OP-UA59 - Coke By-Product Recovery Plant Attributes  
OP-UA60 - Chemical Manufacturing Process Unit Attributes  
OP-UA61 - Pulp, Paper, or Paperboard Producing Process Attributes  
OP-UA62 - Glycol Dehydration Unit Attributes  
OP-UA63 - Vegetable Oil Production Attributes