FEDERAL OPERATING PERMIT

A FEDERAL OPERATING PERMIT IS HEREBY ISSUED TO

Valero Refining-Texas, L.P.

AUTHORIZING THE OPERATION OF

Valero Corpus Christi Refinery West Plant
Petroleum Refining

LOCATED AT

Nueces County, Texas

Latitude 27° 48' 54" Longitude 097° 29' 20"

Regulated Entity Number: RN100214386

This permit is issued in accordance with and subject to the Texas Clean Air Act (TCAA), Chapter 382 of the Texas Health and Safety Code and Title 30 Texas Administrative Code Chapter 122 (30 TAC Chapter 122), Federal Operating Permits. Under 30 TAC Chapter 122, this permit constitutes the permit holder's authority to operate the site and emission units listed in this permit. Operations of the site and emission units listed in this permit are subject to all additional rules or amended rules and orders of the Commission pursuant to the TCAA.

This permit does not relieve the permit holder from the responsibility of obtaining New Source Review authorization for new, modified, or existing facilities in accordance with 30 TAC Chapter 116, Control of Air Pollution by Permits for New Construction or Modification.

The site and emission units authorized by this permit shall be operated in accordance with 30 TAC Chapter 122, the general terms and conditions, special terms and conditions, and attachments contained herein.

This permit shall expire five years from the date of issuance. The renewal requirements specified in 30 TAC § 122.241 must be satisfied in order to renew the authorization to operate the site and emission units.

Permit No: O1458 Issuance Date: April 29, 2013

For the Commission

Table of Contents

Section **Page**

General Terms and Conditions 1

Special Terms and Conditions..... 1
Emission Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting 1
Additional Monitoring Requirements 15
New Source Review Authorization Requirements 16
Compliance Requirements.....17
Risk Management Plan 18
Protection of Stratospheric Ozone 18
Alternative Requirements 19
Permit Location..... 19
Permit Shield (30 TAC § 122.148)..... 19

Attachments 21
Applicable Requirements Summary 22
Additional Monitoring Requirements 312
Permit Shield.....349
New Source Review Authorization References.....362
Schedules.....378
Alternative Requirement.....397

Appendix A 408
Acronym List 409

Appendix B 410
Major NSR Summary Table 411
Permit Numbers 38754 and PSDTX324M13..... 427

General Terms and Conditions

The permit holder shall comply with all terms and conditions contained in 30 TAC § 122.143 (General Terms and Conditions), 30 TAC § 122.144 (Recordkeeping Terms and Conditions), 30 TAC § 122.145 (Reporting Terms and Conditions), and 30 TAC § 122.146 (Compliance Certification Terms and Conditions).

In accordance with 30 TAC § 122.144(1), records of required monitoring data and support information required by this permit, or any applicable requirement codified in this permit, are required to be maintained for a period of five years from the date of the monitoring report, sample, or application unless a longer data retention period is specified in an applicable requirement. The five year record retention period supersedes any less stringent retention requirement that may be specified in a condition of a permit identified in the New Source Review Authorization attachment.

If the permit holder chooses to demonstrate that this permit is no longer required, a written request to void this permit shall be submitted to the Texas Commission on Environmental Quality (TCEQ) by the Responsible Official in accordance with 30 TAC § 122.161(e). The permit holder shall comply with the permit's requirements, including compliance certification and deviation reporting, until notified by the TCEQ that this permit is voided.

The permit holder shall comply with 30 TAC Chapter 116 by obtaining a New Source Review authorization prior to new construction or modification of emission units located in the area covered by this permit.

All reports required by this permit must include in the submittal a cover letter which identifies the following information: company name, TCEQ regulated entity number, air account number (if assigned), site name, area name (if applicable), and Air Permits Division permit number(s).

Special Terms and Conditions:
Emission Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting

1. Permit holder shall comply with the following requirements:

    A. Emission units (including groups and processes) in the Applicable Requirements Summary attachment shall meet the limitations, standards, equipment specifications, monitoring, recordkeeping, reporting, testing, and other requirements listed in the Applicable Requirements Summary attachment to assure compliance with the permit.

    B. The textual description in the column titled "Textual Description" in the Applicable Requirements Summary attachment is not enforceable and is not deemed as a substitute for the actual regulatory language. The Textual Description is provided for information purposes only.

C. A citation listed on the Applicable Requirements Summary attachment, which has a notation [G] listed before it, shall include the referenced section and subsection for all commission rules, or paragraphs for all federal and state regulations and all subordinate paragraphs, subparagraphs and clauses, subclauses, and items contained within the referenced citation as applicable requirements.

D. When a grouped citation, notated with a [G] in the Applicable Requirements Summary, contains multiple compliance options, the permit holder must keep records of when each compliance option was used.

E. Emission units subject to 40 CFR Part 63, Subparts A, Y, CC, UUU, ZZZZ, DDDDD, or GGGGG as identified in the attached Applicable Requirements Summary table are subject to 30 TAC Chapter 113, Subchapter C, § 113.100, 113.300, 113.340, 113.780, 113.1090, 113.1130, or 113.1160, respectively, which incorporates the 40 CFR Part 63 Subpart by reference.

2. The permit holder shall comply with the following sections of 30 TAC Chapter 101 (General Air Quality Rules):

A. Title 30 TAC § 101.1 (relating to Definitions), insofar as the terms defined in this section are used to define the terms used in other applicable requirements

B. Title 30 TAC § 101.3 (relating to Circumvention)

C. Title 30 TAC § 101.8 (relating to Sampling), if such action has been requested by the TCEQ

D. Title 30 TAC § 101.9 (relating to Sampling Ports), if such action has been requested by the TCEQ

E. Title 30 TAC § 101.10 (relating to Emissions Inventory Requirements)

F. Title 30 TAC § 101.201 (relating to Emission Event Reporting and Recordkeeping Requirements)

G. Title 30 TAC § 101.211 (relating to Scheduled Maintenance, Start-up, and Shutdown Reporting and Recordkeeping Requirements)

H. Title 30 TAC § 101.221 (relating to Operational Requirements)

I. Title 30 TAC § 101.222 (relating to Demonstrations)

J. Title 30 TAC § 101.223 (relating to Actions to Reduce Excessive Emissions)

3. Permit holder shall comply with the following requirements of 30 TAC Chapter 111:

A. Visible emissions from stationary vents with a flow rate of less than 100,000 actual cubic feet per minute and constructed after January 31, 1972 that are not listed in the Applicable Requirements Summary attachment for 30 TAC Chapter 111, Subchapter A, Division 1 , shall not exceed 20% opacity averaged over a six-minute period. The permit holder shall comply with the following requirements for stationary vents at the site subject to this standard:

(i) Title 30 TAC § 111.111(a)(1)(B) (relating to Requirements for Specified Sources)

(ii) Title 30 TAC § 111.111(a)(1)(E)

(iii) Title 30 TAC § 111.111(a)(1)(F)(i), (ii), (iii), or (iv)

(iv) For emission units with vent emissions subject to 30 TAC § 111.111(a)(1)(B), complying with 30 TAC § 111.111(a)(1)(F)(ii), (iii), or (iv), and capable of producing visible emissions from, but not limited to, particulate matter, acid gases and NO_x, the permit holder shall also comply with the following periodic monitoring requirements for the purpose of annual compliance certification under 30 TAC § 122.146. These periodic monitoring requirements do not apply to vents that are not capable of producing visible emissions such as vents that emit only colorless VOCs; vents from non-fuming liquids; vents that provide passive ventilation, such as plumbing vents; or vent emissions from any other source that does not obstruct the transmission of light. Vents, as specified in the "Applicable Requirements Summary" attachment, that are subject to the emission limitation of 30 TAC § 111.111(a)(1)(B) are not subject to the following periodic monitoring requirements:

(1) An observation of stationary vents from emission units in operation shall be conducted at least once during each calendar quarter unless the emission unit is not operating for the entire quarter.

(2) For stationary vents from a combustion source, if an alternative to the normally fired fuel is fired for a period greater than or equal to 24 consecutive hours, the permit holder shall conduct an observation of the stationary vent for each such period to determine if visible emissions are present. If such period is greater than 3 months, observations shall be conducted once during each quarter. Supplementing the normally fired fuel with natural gas or fuel gas to increase the net heating value to the minimum required value does not constitute creation of an alternative fuel.

(3) Records of all observations shall be maintained.

(4) Visible emissions observations of emission units operated during daylight hours shall be conducted no earlier than one hour after sunrise and no later than one hour before sunset. Visible emissions observations of emission units operated only at night must be made with additional lighting and the temporary installation of contrasting backgrounds. Visible emissions observations shall be made during times when the activities described in 30 TAC § 111.111(a)(1)(E) are not taking place. Visible emissions shall be determined with each stationary vent in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 mile, away from each stationary vent during the observation. For outdoor locations, the observer shall select a position where the sun is not directly in the observer's eyes. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. A certified opacity reader is not required for visible emissions observations.

(5) Compliance Certification:

(a) If visible emissions are not present during the observation, the RO may certify that the source is in compliance with the applicable opacity requirement in 30 TAC § 111.111(a)(1) and (a)(1)(B).

(b) However, if visible emissions are present during the observation, the permit holder shall either list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(1)(F) to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required

under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.

(c) Some vents may be subject to multiple visible emission or monitoring requirements. All credible data must be considered when certifying compliance with this requirement even if the observation or monitoring was performed to demonstrate compliance with a different requirement.

B. For visible emissions from a building, enclosed facility, or other structure; the permit holder shall comply with the following requirements:

(i) Title 30 TAC § 111.111(a)(7)(A) (relating to Requirements for Specified Sources)

(ii) Title 30 TAC § 111.111(a)(7)(B)(i) or (ii)

(iii) For a building containing an air emission source, enclosed facility, or other structure containing or associated with an air emission source subject to 30 TAC § 111.111(a)(7)(A), complying with 30 TAC § 111.111(a)(7)(B)(i) or (ii), and capable of producing visible emissions from, but not limited to, particulate matter, acid gases and NO_x, the permit holder shall also comply with the following periodic monitoring requirements for the purpose of annual compliance certification under 30 TAC § 122.146:

(1) An observation of visible emissions from a building containing an air emission source, enclosed facility, or other structure containing or associated with an air emission source which is required to comply with 30 TAC § 111.111(a)(7)(A) shall be conducted at least once during each calendar quarter unless the air emission source or enclosed facility is not operating for the entire quarter.

(2) Records of all observations shall be maintained.

(3) Visible emissions observations of air emission sources or enclosed facilities operated during daylight hours shall be conducted no earlier than one hour after sunrise and no later than one hour before sunset. Visible emissions observations of air emission sources or enclosed facilities operated only at night must be made with additional lighting and the temporary installation of contrasting backgrounds. Visible emissions shall be determined with each emissions outlet in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 mile, away from each emissions outlet during the observation. For outdoor locations, the

observer shall select a position where the sun is not directly in the observer's eyes. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. A certified opacity reader is not required for visible emissions observations.

(4) Compliance Certification:

(a) If visible emissions are not present during the observation, the RO may certify that the source is in compliance with the applicable opacity requirement in 30 TAC § 111.111(a)(7) and (a)(7)(A)

(b) However, if visible emissions are present during the observation, the permit holder shall either list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(7)(B) to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.

C. For visible emissions from all other sources not specified in 30 TAC § 111.111(a)(1), (4), or (7); the permit holder shall comply with the following requirements:

(i) Title 30 TAC § 111.111(a)(8)(A) (relating to Requirements for Specified Sources)

(ii) Title 30 TAC § 111.111(a)(8)(B)(i) or (ii)

(iii) For a source subject to 30 TAC § 111.111(a)(8)(A), complying with 30 TAC § 111.111(a)(8)(B)(i) or (ii), and capable of producing visible emissions from, but not limited to, particulate matter, acid gases and NO_x, the permit holder shall also comply with the following

periodic monitoring requirements for the purpose of annual compliance certification under 30 TAC § 122.146:

(1) An observation of visible emissions from a source which is required to comply with 30 TAC § 111.111(a)(8)(A) shall be conducted at least once during each calendar quarter unless the source is not operating for the entire quarter.

(2) Records of all observations shall be maintained.

(3) Visible emissions observations of sources operated during daylight hours shall be conducted no earlier than one hour after sunrise and no later than one hour before sunset. Visible emissions observations of sources operated only at night must be made with additional lighting and the temporary installation of contrasting backgrounds. Visible emissions shall be determined with each source in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 mile, away from each source during the observation. For outdoor locations, the observer shall select a position where the sun is not directly in the observer's eyes. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. A certified opacity reader is not required for visible emissions observations.

(4) Compliance Certification:

(a) If visible emissions are not present during the observation, the RO may certify that the source is in compliance with the applicable opacity requirement in 30 TAC § 111.111(a)(8) and (a)(8)(A)

(b) However, if visible emissions are present during the observation, the permit holder shall either list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(8)(B) to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity

requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.

D. Certification of opacity readers determining opacities under Method 9 (as outlined in 40 CFR Part 60, Appendix A) to comply with opacity monitoring requirements shall be accomplished by completing the Visible Emissions Evaluators Course, or approved agency equivalent, no more than 180 days before the opacity reading.

E. For emission units with contributions from uncombined water, the permit holder shall comply with the requirements of 30 TAC § 111.111(b).

F. Emission limits on nonagricultural processes, except for the steam generators specified in 30 TAC § 111.153, shall comply with the following requirements:

(i) Emissions of PM from any source may not exceed the allowable rates as required in 30 TAC § 111.151(a) (relating to Allowable Emissions Limits)

(ii) Sources with an effective stack height (h_e) less than the standard effective stack height (H_e), must reduce the allowable emission level by multiplying it by $[h_e/H_e]^2$ as required in 30 TAC § 111.151(b)

(iii) Effective stack height shall be calculated by the equation specified in 30 TAC § 111.151(c)

4. For storage vessels maintaining working pressure as specified in 30 TAC Chapter 115, Subchapter B, Division 1: "Storage of Volatile Organic Compounds," the permit holder shall comply with the requirements of 30 TAC § 115.112(b)(1).

5. Permit holder shall comply with the following 30 TAC Chapter 115, Subchapter C requirements:

A. When filling gasoline storage vessels with a nominal capacity greater than 1,000 gallons (Stage I) at motor vehicle fuel dispensing facilities, which have dispensed less than 125,000 gallons of gasoline in any calendar month after January 1, 1999, the permit holder shall comply with the following requirements specified in 30 TAC Chapter 115, Subchapter C:

(i) Title 30 TAC § 115.222(7) (relating to Control Requirements)

(ii) Title 30 TAC § 115.222(3), as it applies to liquid gasoline leaks

(iii) Title 30 TAC § 115.224(1) (relating to Inspection Requirements), as it applies to liquid gasoline leaks

(iv) Title 30 TAC § 115.226(2)(C) (relating to Recordkeeping Requirements)

B. When filling stationary gasoline storage containers with a nominal capacity less than or equal to 1,000 gallons at a Stage I motor vehicle fuel dispensing facility, the permit holder shall comply with the following requirements specified in 30 TAC Chapter 115, Subchapter C:

(i) Title 30 TAC § 115.222(7) (relating to Control Requirements)

(ii) Title 30 TAC § 115.222(3), as it applies to liquid gasoline leaks

(iii) Title 30 TAC § 115.224(1) (relating to Inspection Requirements), as it applies to liquid gasoline leaks

6. Permit holder shall comply with the following 30 TAC Chapter 115, Subchapter D requirements:

A. Title 30 TAC § 115.312(b)(1) (relating to Control Requirements), for emissions during Process Unit Shutdown or Turnaround

7. The permit holder shall comply with the following 30 TAC Chapter 115, Subchapter F requirements (relating to Cutback Asphalt Requirements):

A. Title 30 TAC § 115.512(3) (relating to Control Requirements)

8. The permit holder shall comply with the following requirements for units subject to any subpart of 40 CFR Part 60, unless otherwise stated in the applicable subpart:

A. Title 40 CFR § 60.7 (relating to Notification and Recordkeeping)

B. Title 40 CFR § 60.8 (relating to Performance Tests)

C. Title 40 CFR § 60.11 (relating to Compliance with Standards and Maintenance Requirements)

D. Title 40 CFR § 60.12 (relating to Circumvention)

E. Title 40 CFR § 60.13 (relating to Monitoring Requirements)

F. Title 40 CFR § 60.14 (relating to Modification)

G. Title 40 CFR § 60.15 (relating to Reconstruction)

H. Title 40 CFR § 60.19 (relating to General Notification and Reporting Requirements)

9. For petroleum refinery facilities subject to 40 CFR Part 60, Subpart QQQ, the permit holder shall comply with the following requirements:

A. Title 40 CFR § 60.692-1(a) - (c) (relating to Standards: General)

B. Title 40 CFR § 60.692-2(a) - (c), (e) (relating to Standards: Individual Drain Systems)

C. Title 40 CFR § 60.692-6(a) - (b) (relating to Standards: Delay of Repair)

D. Title 40 CFR § 60.692-7(a) - (b) (relating to Standards: Delay of Compliance)

E. Title 40 CFR § 60.693-1(a) - (d), (e)(1) - (3) (relating to Alternative Standards for Individual Drain Systems)

F. Title 40 CFR § 60.697(a), (b)(1) - (3) (relating to Recordkeeping Requirements), as applicable to Individual Drain Systems

G. Title 40 CFR § 60.697(f)(1) - (2), (g) (relating to Recordkeeping Requirements), as applicable to Individual Drain Systems

H. Title 40 CFR § 60.697(h) (relating to Recordkeeping Requirements), as applicable to excluded Stormwater Sewer Systems

I. Title 40 CFR § 60.697(i) (relating to Recordkeeping Requirements), as applicable to excluded Ancillary Equipment

J. Title 40 CFR § 60.697(j) (relating to Recordkeeping Requirements), as applicable to excluded Non-contact Cooling Water Systems

K. Title 40 CFR § 60.698(a), and (b)(1) (relating to Reporting Requirements), as applicable to Individual Drain Systems

L. Title 40 CFR § 60.698(c) (relating to Reporting Requirements), for water seal breaches in Drain Systems

M. Title 40 CFR § 60.698(e) (relating to Reporting Requirements), as applicable to Individual Drain Systems

10. The permit holder shall comply with the following requirements for units subject to any subpart of 40 CFR Part 61, unless otherwise stated in the applicable subpart:

A. Title 40 CFR § 61.05 (relating to Prohibited Activities)

B. Title 40 CFR § 61.07 (relating to Application for Approval of Construction or Modification)

C. Title 40 CFR § 61.09 (relating to Notification of Start-up)

D. Title 40 CFR § 61.10 (relating to Source Reporting and Request Waiver)

E. Title 40 CFR § 61.12 (relating to Compliance with Standards and Maintenance Requirements)

F. Title 40 CFR § 61.13 (relating to Emissions Tests and Waiver of Emission Tests)

G. Title 40 CFR § 61.14 (relating to Monitoring Requirements)

H. Title 40 CFR § 61.15 (relating to Modification)

I. Title 40 CFR § 61.19 (relating to Circumvention)

11. For facilities where total annual benzene quantity from waste is greater than or equal to 10 megagrams per year and subject to emission standards in 40 CFR Part 61, Subpart FF, the permit holder shall comply with the following requirements:

A. Title 40 CFR § 61.342(c)(1)(i) - (iii) (relating to Standards: General)

B. Title 40 CFR § 61.342(e)(1) (relating to Standards: General)

C. Title 40 CFR § 61.342(e)(2)(i) - (ii) (relating to Standards: General)

D. Title 40 CFR § 61.342(f)(1), and (2) (relating to Standards: General)

E. Title 40 CFR § 61.342(g) (relating to Standards: General)

F. Title 40 CFR § 61.350(a) and (b) (relating to Standards: Delay of Repair)

G. Title 40 CFR § 61.355(a)(1)(iii), (a)(2), (a)(6), (b), and (c)(1) - (3) (relating to Test Methods, Procedures, and Compliance Provisions)

H. Title 40 CFR § 61.355(k)(1) - (6), and (7)(i) - (iv) (relating to Test Methods, Procedures, and Compliance Provisions), for calculation procedures

I. Title 40 CFR § 61.356(a) (relating to Recordkeeping Requirements)

J. Title 40 CFR § 61.356(b), and (b)(1) (relating to Recordkeeping Requirements)

K. Title 40 CFR § 61.356(b)(4) (relating to Recordkeeping Requirements)

L. Title 40 CFR § 61.356(b)(5) (relating to Recordkeeping Requirements)

M. Title 40 CFR § 61.356(c) (relating to Recordkeeping Requirements)

N. Title 40 CFR § 61.357(a), (d)(1), (d)(2) (d)(6) and (d)(8) (relating to Reporting Requirements)

O. Title 40 CFR § 61.357(d)(5) (relating to Reporting Requirements)

P. Waste generated by remediation activities at these facilities are subject to the requirements identified under 40 CFR § 61.342 for treatment and management of waste

12. For facilities with containers subject to emission standards in 40 CFR Part 61, Subpart FF, the permit holder shall comply with the following requirements:

A. Title 40 CFR § 61.345(a)(1) - (3), (b), and (c) (relating to Standards: Containers)

B. Title 40 CFR § 61.355(h) (relating to Test Methods, Procedures and Compliance Provisions)

C. Title 40 CFR § 61.356(g) (relating to Recordkeeping Requirements)

D. Title 40 CFR § 61.356(h) (relating to Recordkeeping Requirements)

13. For facilities with individual drain systems subject to emission standards in 40 CFR Part 61, Subpart FF, the permit holder shall comply with the following requirements:

A. Title 40 CFR § 61.346(b)(1), (2), (2)(i), (3), (4)(i) - (iv), and (5) (relating to Standards: Individual Drain Systems)

B. Title 40 CFR § 61.346(b)(2)(ii)(B) (relating to Standards: Individual Drain Systems), for junction boxes

14. The permit holder shall comply with the requirements of 30 TAC Chapter 113, Subchapter C, § 113.100 for units subject to any subpart of 40 CFR Part 63, unless otherwise stated in the applicable subpart.

15. For the bulk gasoline terminals specified in 40 CFR Part 63, Subpart R, the permit holder shall comply with the following requirements (Title 30 TAC Chapter 113, Subchapter C, § 113.230 incorporated by reference):

A. Title 40 CFR § 63.420(h), for applicability of the General Provisions of Subpart A

B. Title 40 CFR § 63.422(c), (c)(1) - (2) (relating to Standards: Loading Racks)

C. Title 40 CFR § 63.424(f) (relating to Standards: Equipment Leaks)

D. Title 40 CFR § 63.424(g) (relating to Standards: Equipment Leaks)

E. Title 40 CFR § 63.425(e) - (h) (relating to Test Methods and Procedures)

F. Title 40 CFR § 63.428(a) - (b), (g)(1), and (h)(2) - (3) (relating to Reporting and Recordkeeping)

G. Title 40 CFR § 63.428(f)(1) - (2) (relating to Reporting and Recordkeeping)

16. For the operations pertaining to the loading and unloading of marine tank vessels specified in 40 CFR Part 63, Subpart Y, the permit holder shall comply with the following requirements (Title 30 TAC Chapter 113, Subchapter C, § 113.300 incorporated by reference):

A. Title 40 CFR § 63.560(c) (relating to Designation of Affected Source), for applicability of the General Provisions of Subpart A

B. Title 40 CFR § 63.563(a)(4) (relating to Compliance and Performance Testing), for vapor tightness requirements of the marine vessels

C. Title 40 CFR § 63.564(a)(1) and (d) (relating to Monitoring Requirements)

D. Title 40 CFR § 63.565(a) (relating to Test Methods and Procedures), for performance testing requirements

E. Title 40 CFR § 63.565(c) (relating to Test Methods and Procedures), for vapor tightness requirements of the marine vessels

F. Title 40 CFR § 63.566 (relating to Construction and Reconstruction)

G. Title 40 CFR § 63.567(a) - (b) and (h) - (i) (relating to Reporting and Recordkeeping Requirements)

17. The permit holder shall comply with the requirement to prepare and implement an Operations and Maintenance plan in accordance with 40 CFR Part 63, Subpart UUU, § 63.1574(f) (Title 30 TAC Chapter 113, Subchapter C, § 113.780 incorporated by reference).

18. For site remediation projects subject to 40 CFR Part 63, Subpart GGGGG that will remove remediation material containing less than 1 megagram per year of the HAP listed in Table 1 to Subpart GGGGG, the permit holder shall comply with 40 CFR § 63.7881(c)(1) - (3) (Title 30 TAC Chapter 113, Subchapter C, § 113.1160 incorporated by reference).

19. For containers managing remediation materials subject to 40 CFR Part 63, Subpart GGGGG, the permit holder shall comply with the following requirements (Title 30 TAC Chapter 113, Subchapter C, § 113.1160 incorporated by reference):

A. Title 40 CFR § 63.922(b)(1) - (3), (c), (d)(1) - (5), (e), and (f)(1) - (4) (relating to Standards - Container Level 1 Controls)

B. Title 40 CFR § 63.923(b)(1) - (3), (c), (d)(1) - (5), (e), and (f)(1) - (4) (relating to Standards - Container Level 2 Controls)

C. Title 40 CFR § 63.924(b)(1) - (2), (c)(1), and (d) (relating to Standards - Container Level 3 Controls)

D. Title 40 CFR § 63.925(a)(1) - (8), and (b)(1) - (3) (relating to Test Methods and Procedures)

E. Title 40 CFR § 63.926(a)(1) - (3) (relating to Inspection and Monitoring Requirements)

F. Title 40 CFR § 63.7901(b) and (b)(1), for initial demonstration of compliance

G. Title 40 CFR § 63.7901(b)(2), for initial demonstration of compliance

H. Title 40 CFR § 63.7901(c), (c)(1), and (c)(2), for initial demonstration of compliance

I. Title 40 CFR § 63.7901(d), and (d)(1) - (4), for initial demonstration of compliance

J. Title 40 CFR § 63.7901(e), (e)(1), and (e)(2), for initial demonstration of compliance

K. Title 40 CFR § 63.7902(b), (b)(1), and (b)(2), for inspection and monitoring

L. Title 40 CFR § 63.7903(b) and (b)(1), for continuous demonstration of compliance

M. Title 40 CFR § 63.7903(b)(2), (b)(2)(i), (b)(2)(ii), for continuous demonstration of compliance

N. Title 40 CFR § 63.7903(c)(4), (c)(4)(i), and (c)(4)(ii), for continuous demonstration of compliance

O. Title 40 CFR § 63.7903(d)(5), (d)(5)(i), and (d)(5)(ii), for continuous demonstration of compliance

P. Title 40 CFR § 63.7903(e)(1) - (3), for continuous demonstration of compliance

Q. Title 40 CFR § 63.7952(c), for recordkeeping

Additional Monitoring Requirements

20. Unless otherwise specified, the permit holder shall comply with the compliance assurance monitoring requirements as specified in the attached "CAM Summary" upon issuance of the permit. In addition, the permit holder shall comply with the following:

    A. The permit holder shall comply with the terms and conditions contained in 30 TAC § 122.147 (General Terms and Conditions for Compliance Assurance Monitoring).

    B. The permit holder shall report, consistent with the averaging time identified in the "CAM Summary," deviations as defined by the deviation limit in the "CAM Summary." Any monitoring data below a minimum limit or above a maximum limit, that is collected in accordance with the requirements specified in 40 CFR § 64.7(c), shall be reported as a deviation. Deviations shall be reported according to 30 TAC § 122.145 (Reporting Terms and Conditions).

    C. The permit holder may elect to collect monitoring data on a more frequent basis and average the data, consistent with the averaging time specified in the "CAM Summary," for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis. In no event shall data be collected and used in particular instances in order to avoid reporting deviations. All monitoring data shall be collected in accordance with the requirements specified in 40 CFR § 64.7(c).

    D. The permit holder shall operate the monitoring, identified in the attached "CAM Summary," in accordance with the provisions of 40 CFR § 64.7.

    E. The permit holder shall comply with the requirements of 40 CFR § 70.6(a)(3)(ii)(A) and 30 TAC § 122.144(1)(A)-(F) for documentation of all required inspections.

21. The permit holder shall comply with the periodic monitoring requirements as specified in the attached "Periodic Monitoring Summary" upon issuance of the permit. Except for, as applicable, monitoring malfunctions, associated repairs, and required quality assurance or control activities (including, as applicable, calibration checks and required zero and span adjustments), the permit holder shall conduct all monitoring in continuous operation (or shall collect data at all required intervals) at all times that the pollutant-specific emissions unit is operating. The permit holder may elect to collect monitoring data on a more

frequent basis and average the data, consistent with the averaging time specified in the "Periodic Monitoring Summary," for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis. In no event shall data be collected and used in particular instances to avoid reporting deviations. Deviations shall be reported according to 30 TAC § 122.145 (Reporting Terms and Conditions).

New Source Review Authorization Requirements

22. Permit holder shall comply with the requirements of New Source Review authorizations issued or claimed by the permit holder for the permitted area, including permits, permits by rule, standard permits, flexible permits, special permits, permits for existing facilities including Voluntary Emissions Reduction Permits and Electric Generating Facility Permits issued under 30 TAC Chapter 116, Subchapter I, or special exemptions referenced in the New Source Review Authorization References attachment. These requirements:

    A. Are incorporated by reference into this permit as applicable requirements

    B. Shall be located with this operating permit

    C. Are not eligible for a permit shield

23. The permit holder shall comply with the general requirements of 30 TAC Chapter 106, Subchapter A or the general requirements, if any, in effect at the time of the claim of any PBR.

24. The permit holder shall maintain records to demonstrate compliance with any emission limitation or standard that is specified in a permit by rule (PBR) or Standard Permit listed in the New Source Review Authorizations attachment. The records shall yield reliable data from the relevant time period that are representative of the emission unit's compliance with the PBR or Standard Permit. These records may include, but are not limited to, production capacity and throughput, hours of operation, material safety data sheets (MSDS), chemical composition of raw materials, speciation of air contaminant data, engineering calculations, maintenance records, fugitive data, performance tests, capture/control device efficiencies, direct pollutant monitoring (CEMS, COMS, or PEMS), or control device parametric monitoring. These records shall be made readily accessible and available as required by 30 TAC § 122.144. Any monitoring or recordkeeping data indicating noncompliance with the PBR or Standard Permit shall be considered and reported as a deviation according to 30 TAC § 122.145 (Reporting Terms and Conditions).

25. The permit holder shall comply with the following requirements for Air Quality Standard Permits:

    A. Registration requirements listed in 30 TAC § 116.611, unless otherwise provided for in an Air Quality Standard Permit

B. General Conditions listed in 30 TAC § 116.615, unless otherwise provided for in an Air Quality Standard Permit

C. Applicable requirements of 30 TAC § 116.617 for Pollution Control Projects based on the information contained in the registration application.

D. Boiler Standard Permit

Compliance Requirements

26. The permit holder shall certify compliance in accordance with 30 TAC § 122.146. The permit holder shall comply with 30 TAC § 122.146 using at a minimum, but not limited to, the continuous or intermittent compliance method data from monitoring, recordkeeping, reporting, or testing required by the permit and any other credible evidence or information. The certification period may not exceed 12 months and the certification must be submitted within 30 days after the end of the period being certified.

27. The permit holder shall adhere to the provisions in the Compliance Schedule attachment of this permit and submit certified progress reports consistent with the schedule established under 30 TAC § 122.132(e)(4)(C) and including the information specified in 30 TAC § 122.142(e)(2). Those emission units listed in the Compliance Schedule attachment shall adhere with the requirements in the Compliance Schedule attachment until operating fully in compliance with the applicable requirements.

28. Use of Discrete Emission Credits to comply with the applicable requirements:

A. Unless otherwise prohibited, the permit holder may use discrete emission credits to comply with the following applicable requirements listed elsewhere in this permit:

(i) Title 30 TAC Chapter 115

(ii) Title 30 TAC Chapter 117

(iii) If applicable, offsets for Title 30 TAC Chapter 116

(iv) Temporarily exceed state NSR permit allowables

B. The permit holder shall comply with the following requirements in order to use the credit to comply with the applicable requirements:

(i) The permit holder must notify the TCEQ according to 30 TAC § 101.376(d)

(ii) The discrete emission credits to be used must meet all the geographic, timeliness, applicable pollutant type, and availability

requirements listed in 30 TAC Chapter 101, Subchapter H, Division 4

(iii) The executive director has approved the use of the discrete emission credits according to 30 TAC § 101.376(d)(1)(A)

(iv) The permit holder keeps records of the use of credits towards compliance with the applicable requirements in accordance with 30 TAC § 101.372(h) and 30 TAC Chapter 122

Risk Management Plan

29. For processes subject to 40 CFR Part 68 and specified in 40 CFR § 68.10, the permit holder shall comply with the requirements of the Accidental Release Prevention Provisions in 40 CFR Part 68. The permit holder shall submit to the appropriate agency either a compliance schedule for meeting the requirements of 40 CFR Part 68 by the date provided in 40 CFR § 68.10(a), or as part of the compliance certification submitted under this permit, a certification statement that the source is in compliance with all requirements of 40 CFR Part 68, including the registration and submission of a risk management plan.

Protection of Stratospheric Ozone

30. Permit holders at a site subject to Title VI of the FCAA Amendments shall meet the following requirements for protection of stratospheric ozone.

A. Any on site servicing, maintenance, and repair on refrigeration and nonmotor vehicle air-conditioning appliances using ozone-depleting refrigerants or non-exempt substitutes shall be conducted in accordance with 40 CFR Part 82, Subpart F. Permit holders shall ensure that repairs on or refrigerant removal from refrigeration and nonmotor vehicle air-conditioning appliances using ozone-depleting refrigerants are performed only by properly certified technicians using certified equipment. Records shall be maintained as required by 40 CFR Part 82, Subpart F.

B. The permit holder shall comply with the following 40 CFR Part 82, Subpart E requirements for labeling products using ozone-depleting substances:

(i) Title 40 CFR § 82.100 (relating to Purpose)

(ii) Title 40 CFR § 82.102(a)(1) - (3), (b), (c) (relating to Applicability);

(iii) Title 40 CFR § 82.104 (relating to Definitions)

(iv) Title 40 CFR § 82.106 - 112 (relating to Warning Statements and Labels)

(v) Title 40 CFR § 82.114 (relating to Labeling Containers of Controlled [ozone - depleting] Substances)

(vi) Title 40 CFR § 82.116 (relating to Incorporation of Products Manufactured with Controlled [ozone-depleting] Substances)

(vii) Title 40 CFR § 82.120 (relating to Petitions)

(viii) Title 40 CFR § 82.122 (relating Certification, Recordkeeping, and Notice requirements)

(ix) Title 40 CFR § 82.124 (relating to Prohibitions)

C. The permit holder shall comply with 40 CFR Part 82, Subpart H related to Halon Emissions Reduction requirements as specified in 40 CFR § 82.250 - § 82.270 and the applicable Part 82 Appendices.

Alternative Requirements

31. The permit holder shall comply with the approved alternative means of control (AMOC); alternative monitoring, recordkeeping, or reporting requirements; or requirements determined to be equivalent to an otherwise applicable requirement contained in the Alternative Requirements attachment of this permit. Units complying with an approved alternative requirement have reference to the approval in the Applicable Requirements summary listing for the unit. The permit holder shall maintain the original documentation, from (the EPA Administrator and/or TCEQ Executive Director), demonstrating the method or limitation utilized. Documentation shall be maintained and made available in accordance with 30 TAC § 122.144.

Permit Location

32. The permit holder shall maintain a copy of this permit and records related to requirements listed in this permit on site.

Permit Shield (30 TAC § 122.148)

33. A permit shield is granted for the emission units, groups, or processes specified in the attached "Permit Shield." Compliance with the conditions of the permit shall be deemed compliance with the specified potentially applicable requirements or specified potentially applicable state-only requirements listed in the attachment "Permit Shield." Permit shield provisions shall not be modified by the executive director until notification is provided to the permit holder. No later than 90 days after notification of a change in a determination made by the executive director, the permit holder shall apply for the appropriate permit revision to reflect the new determination. Provisional terms are not eligible for this permit shield. Any term or condition, under a permit shield, shall not be protected by the permit

shield if it is replaced by a provisional term or condition or the basis of the term and condition changes.

Attachments

Applicable Requirements Summary

Additional Monitoring Requirements

Permit Shield

New Source Review Authorization References

Schedules

Alternative Requirement

Applicable Requirements Summary

Unit Summary 23

Applicable Requirements Summary 72

Note: A "none" entry may be noted for some emission sources in this permit's "Applicable Requirements Summary" under the heading of "Monitoring and Testing Requirements" and/or "Recordkeeping Requirements" and/or "Reporting Requirements." Such a notation indicates that there are no requirements for the indicated emission source as identified under the respective column heading(s) for the stated portion of the regulation when the emission source is operating under the conditions of the specified SOP Index Number. However, other relevant requirements pursuant to 30 TAC Chapter 122 including Recordkeeping Terms and Conditions (30 TAC § 122.144), Reporting Terms and Conditions (30 TAC § 122.145), and Compliance Certification Terms and Conditions (30 TAC § 122.146) continue to apply.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
30-B-02	Boilers/Steam Generators/ Steam Generating Units	N/A	60Db	40 CFR Part 60, Subpart Db	No changing attributes.
30-B-03	Boilers/Steam Generators/ Steam Generating Units	N/A	60Db	40 CFR Part 60, Subpart Db	No changing attributes.
30-B-04	Boilers/Steam Generators/ Steam Generating Units	N/A	60Db	40 CFR Part 60, Subpart Db	No changing attributes.
30-B-04	Boilers/Steam Generators/ Steam Generating Units	N/A	63DDDDD	40 CFR Part 63, Subpart DDDDD	No changing attributes.
WWTP-FUG	Closed Vent System And Control Device	N/A	61FF-DRAINS	40 CFR Part 61, Subpart FF	No changing attributes.
GRP-NNN	Distillation Operations	20-V-03, 36-T-02, 36-V-06, 37-V-03, 37-V-05, 49-V-01, 54-V-42	60NNNa	40 CFR Part 60, Subpart NNN	No changing attributes.
GRP-NNN	Distillation Operations	20-V-03, 36-T-02, 36-V-06, 37-V-03, 37-V-05, 49-V-01, 54-V-42	60NNNb	40 CFR Part 60, Subpart NNN	No changing attributes.
02-V-12	Emission Points/Stationary Vents/Process Vents	N/A	R5121	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
02-V-12	Emission Points/Stationary Vents/Process Vents	N/A	63CC	40 CFR Part 63, Subpart CC	No changing attributes.
38-V-54	Emission Points/Stationary Vents/Process Vents	N/A	R5121	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
38-V-54	Emission Points/Stationary Vents/Process Vents	N/A	63CC	40 CFR Part 63, Subpart CC	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
38-V-55	Emission Points/Stationary Vents/Process Vents	N/A	R5121	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
38-V-55	Emission Points/Stationary Vents/Process Vents	N/A	63CC	40 CFR Part 63, Subpart CC	No changing attributes.
44-V-01	Emission Points/Stationary Vents/Process Vents	N/A	R5121	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
44-V-01	Emission Points/Stationary Vents/Process Vents	N/A	63CCa	40 CFR Part 63, Subpart CC	No changing attributes.
47-V-02	Emission Points/Stationary Vents/Process Vents	N/A	R5121	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
47-V-02	Emission Points/Stationary Vents/Process Vents	N/A	63CC	40 CFR Part 63, Subpart CC	No changing attributes.
48-V-01	Emission Points/Stationary Vents/Process Vents	N/A	R5121	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
48-V-01	Emission Points/Stationary Vents/Process Vents	N/A	63CC	40 CFR Part 63, Subpart CC	No changing attributes.
49-V-01	Emission Points/Stationary Vents/Process Vents	N/A	R5121	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
49-V-01	Emission Points/Stationary Vents/Process Vents	N/A	63CC	40 CFR Part 63, Subpart CC	No changing attributes.
GRP-EPN118	Emission Points/Stationary Vents/Process Vents	13T01, SMR-CO2-VT	R5121	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
GRP-EPN118	Emission Points/Stationary Vents/Process Vents	13T01, SMR-CO2-VT	R5121a	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
GRP-EPN121	Emission Points/Stationary	2202-L, 2203-L, 24-	R1151	30 TAC Chapter 111,	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	Vents/Process Vents	ST-02		Nonagricultural Processes	
GRP-EPN121	Emission Points/Stationary Vents/Process Vents	2202-L, 2203-L, 24-ST-02	R1111	30 TAC Chapter 111, Visible Emissions	No changing attributes.
GRP-EPN126A	Emission Points/Stationary Vents/Process Vents	31V05, 47L01PSA	R5121	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
GRP-EPN126A	Emission Points/Stationary Vents/Process Vents	31V05, 47L01PSA	63CC	40 CFR Part 63, Subpart CC	No changing attributes.
GRP-EPN126B	Emission Points/Stationary Vents/Process Vents	49V06, 49V07	R5121	30 TAC Chapter 115, Vent Gas Controls	Control Device Type = Smokeless flare
GRP-EPN126B	Emission Points/Stationary Vents/Process Vents	49V06, 49V07	R5121a	30 TAC Chapter 115, Vent Gas Controls	Control Device Type = Vapor recovery system, as defined in 30 TAC § 115.10, other than an afterburner, blast furnace combustion device, boiler, catalytic or direct flame incinerator, carbon adsorption system, chiller, flare or vapor combustor.
GRP-EPN126B	Emission Points/Stationary Vents/Process Vents	49V06, 49V07	63CCa	40 CFR Part 63, Subpart CC	Control Device = Flare
GRP-EPN126B	Emission Points/Stationary Vents/Process Vents	49V06, 49V07	63CCb	40 CFR Part 63, Subpart CC	Control Device = Boiler or process heater with a design heat input capacity of greater or equal to than 44 MW or a boiler or process heater in which all vent streams are introduced into the flame zone.
GRP-EPN135	Emission Points/Stationary	01V01, 01V13,	R5121	30 TAC Chapter 115, Vent	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	Vents/Process Vents	01V16, 24V36		Gas Controls	
GRP-EPN135	Emission Points/Stationary Vents/Process Vents	01V01, 01V13, 01V16, 24V36	63CCa	40 CFR Part 63, Subpart CC	No changing attributes.
13-H-01A	FCCU Cat Regen/Fuel Gas Combustion/Claus SRU	N/A	60J	40 CFR Part 60, Subpart J	No changing attributes.
13-H-01A	FCCU Cat Regen/Fuel Gas Combustion/Claus SRU	N/A	60J-low	40 CFR Part 60, Subpart J	No changing attributes.
13-H-01B	FCCU Cat Regen/Fuel Gas Combustion/Claus SRU	N/A	60J	40 CFR Part 60, Subpart J	No changing attributes.
13-H-01B	FCCU Cat Regen/Fuel Gas Combustion/Claus SRU	N/A	60J-low	40 CFR Part 60, Subpart J	No changing attributes.
13-H-01C	FCCU Cat Regen/Fuel Gas Combustion/Claus SRU	N/A	60J	40 CFR Part 60, Subpart J	No changing attributes.
13-H-01C	FCCU Cat Regen/Fuel Gas Combustion/Claus SRU	N/A	60J-low	40 CFR Part 60, Subpart J	No changing attributes.
24-ST-01	FCCU Cat Regen/Fuel Gas Combustion/Claus SRU	N/A	60J	40 CFR Part 60, Subpart J	No changing attributes.
24-ST-01	FCCU Cat Regen/Fuel Gas Combustion/Claus SRU	N/A	63UUU	40 CFR Part 63, Subpart UUU	No changing attributes.
38-H-01	FCCU Cat Regen/Fuel Gas Combustion/Claus SRU	N/A	60J	40 CFR Part 60, Subpart J	No changing attributes.
38-H-01	FCCU Cat Regen/Fuel Gas Combustion/Claus SRU	N/A	60J-low	40 CFR Part 60, Subpart J	No changing attributes.
38-H-02	FCCU Cat Regen/Fuel Gas Combustion/Claus SRU	N/A	60J	40 CFR Part 60, Subpart J	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
38-H-02	FCCU Cat Regen/Fuel Gas Combustion/Claus SRU	N/A	60J-low	40 CFR Part 60, Subpart J	No changing attributes.
41-H-07	FCCU Cat Regen/Fuel Gas Combustion/Claus SRU	N/A	60J	40 CFR Part 60, Subpart J	No changing attributes.
46-H-01	FCCU Cat Regen/Fuel Gas Combustion/Claus SRU	N/A	60J	40 CFR Part 60, Subpart J	No changing attributes.
48-H-01	FCCU Cat Regen/Fuel Gas Combustion/Claus SRU	N/A	60J	40 CFR Part 60, Subpart J	Monitoring Device = An instrument is in place for continuously monitoring and recording the concentration (dry basis) of hydrogen sulfide in fuel gases before being burned in any fuel gas combustion device.
48-H-01	FCCU Cat Regen/Fuel Gas Combustion/Claus SRU	N/A	60J-AMP	40 CFR Part 60, Subpart J	Monitoring Device = An instrument is in place for continuously monitoring and recording the concentration (dry basis, zero percent excess air) of SO2 emissions into the atmosphere.
49CRU	FCCU Cat Regen/Fuel Gas Combustion/Claus SRU	N/A	63UUU	40 CFR Part 63, Subpart UUU	No changing attributes.
49-H-91	FCCU Cat Regen/Fuel Gas Combustion/Claus SRU	N/A	60J	40 CFR Part 60, Subpart J	No changing attributes.
52-H-01	FCCU Cat Regen/Fuel Gas Combustion/Claus SRU	N/A	60J	40 CFR Part 60, Subpart J	No changing attributes.
GF-1	FCCU Cat Regen/Fuel Gas	N/A	60J	40 CFR Part 60, Subpart J	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	Combustion/Claus SRU				
GRP-49HTR	FCCU Cat Regen/Fuel Gas Combustion/Claus SRU	49-H-01, 49-H-02, 49-H-03, 49-H-04	60J	40 CFR Part 60, Subpart J	No changing attributes.
GRP-49HTR	FCCU Cat Regen/Fuel Gas Combustion/Claus SRU	49-H-01, 49-H-02, 49-H-03, 49-H-04	60J-low	40 CFR Part 60, Subpart J	No changing attributes.
GRP-BLR-DB	FCCU Cat Regen/Fuel Gas Combustion/Claus SRU	30-B-02, 30-B-03	60J	40 CFR Part 60, Subpart J	No changing attributes.
GRP-HTR	FCCU Cat Regen/Fuel Gas Combustion/Claus SRU	01-H-01, 01-H-02, 01-H-03, 02-H-01, 02-H-02, 11-H-01, 12-H01A, 12-H01B, 12-H02, 31-H-01, 36-H-01, 38-H-03, 47-H-05, 49-H-02NEW, 49-H-71, 49-H-90, 49-HDIC6	60J	40 CFR Part 60, Subpart J	No changing attributes.
GRP-HTRJ	FCCU Cat Regen/Fuel Gas Combustion/Claus SRU	47-H-01, 47-H-02, 47-H-03, 47-H-04	60J	40 CFR Part 60, Subpart J	Monitoring Device = An instrument is in place for continuously monitoring and recording the concentration (dry basis) of hydrogen sulfide in fuel gases before being burned in any fuel gas combustion device.
GRP-HTRJ	FCCU Cat Regen/Fuel Gas Combustion/Claus SRU	47-H-01, 47-H-02, 47-H-03, 47-H-04	60J-AMP	40 CFR Part 60, Subpart J	Monitoring Device = An instrument is in place for continuously monitoring and recording the concentration (dry basis, zero percent excess

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					air) of SO2 emissions into the atmosphere.
MFL-1	FCCU Cat Regen/Fuel Gas Combustion/Claus SRU	N/A	60J	40 CFR Part 60, Subpart J	No changing attributes.
MTBE FL-2	FCCU Cat Regen/Fuel Gas Combustion/Claus SRU	N/A	60J	40 CFR Part 60, Subpart J	No changing attributes.
SRU	FCCU Cat Regen/Fuel Gas Combustion/Claus SRU	N/A	60J	40 CFR Part 60, Subpart J	No changing attributes.
SRU	FCCU Cat Regen/Fuel Gas Combustion/Claus SRU	N/A	63UUU	40 CFR Part 63, Subpart UUU	No changing attributes.
SRU3	FCCU Cat Regen/Fuel Gas Combustion/Claus SRU	N/A	60J	40 CFR Part 60, Subpart J	No changing attributes.
SRU3	FCCU Cat Regen/Fuel Gas Combustion/Claus SRU	N/A	63UUU	40 CFR Part 63, Subpart UUU	No changing attributes.
TRUCKCOMB	FCCU Cat Regen/Fuel Gas Combustion/Claus SRU	N/A	60J	40 CFR Part 60, Subpart J	No changing attributes.
GF-1	Flares	N/A	R1111	30 TAC Chapter 111, Visible Emissions	No changing attributes.
GF-1	Flares	N/A	60A	40 CFR Part 60, Subpart A	No changing attributes.
GF-1	Flares	N/A	63A	40 CFR Part 63, Subpart A	No changing attributes.
MFL-1	Flares	N/A	R1111	30 TAC Chapter 111, Visible Emissions	No changing attributes.
MFL-1	Flares	N/A	60A	40 CFR Part 60, Subpart A	No changing attributes.
MFL-1	Flares	N/A	63A	40 CFR Part 63, Subpart A	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
MFL-1B	Flares	N/A	R1111	30 TAC Chapter 111, Visible Emissions	No changing attributes.
MFL-1B	Flares	N/A	63A	40 CFR Part 63, Subpart A	No changing attributes.
MTBE FL-2	Flares	N/A	R1111	30 TAC Chapter 111, Visible Emissions	No changing attributes.
MTBE FL-2	Flares	N/A	60A	40 CFR Part 60, Subpart A	No changing attributes.
MTBE FL-2	Flares	N/A	63A	40 CFR Part 63, Subpart A	No changing attributes.
30B04F	Fugitive Emission Units	N/A	R5322ALL	30 TAC Chapter 115, Fugitives Pet Ref B Counties	No changing attributes.
54F-MTBE	Fugitive Emission Units	N/A	R5322ALL	30 TAC Chapter 115, Fugitives Pet Ref B Counties	No changing attributes.
54F-MTBE	Fugitive Emission Units	N/A	60GGGALL	40 CFR Part 60, Subpart GGG	No changing attributes.
54F-MTBE	Fugitive Emission Units	N/A	63CCH-ALL	40 CFR Part 63, Subpart CC	No changing attributes.
54F-TAME	Fugitive Emission Units	N/A	R5322ALL	30 TAC Chapter 115, Fugitives Pet Ref B Counties	No changing attributes.
54F-TAME	Fugitive Emission Units	N/A	60GGGALL	40 CFR Part 60, Subpart GGG	No changing attributes.
54F-TAME	Fugitive Emission Units	N/A	63CCVVALL	40 CFR Part 63, Subpart CC	No changing attributes.
BUTAMER	Fugitive Emission Units	N/A	60GGGALL	40 CFR Part 60, Subpart GGG	No changing attributes.
CD-LOADING	LOADING/UNLOADING OPERATIONS	N/A	63CC	40 CFR Part 63, Subpart CC	No changing attributes.
CD-PIPING	FUGITIVE EMISSION	N/A	R5322ALL	30 TAC Chapter 115,	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	UNITS			Fugitives Pet Ref B Counties	
CD-PIPING	FUGITIVE EMISSION UNITS	N/A	63CCVVALL	40 CFR Part 63, Subpart CC	No changing attributes.
FUELDRM	Fugitive Emission Units	N/A	R5322ALL	30 TAC Chapter 115, Fugitives Pet Ref B Counties	No changing attributes.
GDFUG	Fugitive Emission Units	N/A	R5322ALL	30 TAC Chapter 115, Fugitives Pet Ref B Counties	No changing attributes.
GDFUG	Fugitive Emission Units	N/A	60GGGALL	40 CFR Part 60, Subpart GGG	No changing attributes.
GDFUG	Fugitive Emission Units	N/A	63CCHALL	40 CFR Part 63, Subpart CC	No changing attributes.
GRP-5GCCVV	Fugitive Emission Units	11F-HOC, 49-RSU, 49-XFU, 4F, CRUDE UNIT, CRU-FUG, HCU-FUG, HOC-FUG, HRLEU-FUG, LRU, NHT-FUG	R5322ALL	30 TAC Chapter 115, Fugitives Pet Ref B Counties	No changing attributes.
GRP-5GCCVV	Fugitive Emission Units	11F-HOC, 49-RSU, 49-XFU, 4F, CRUDE UNIT, CRU-FUG, HCU-FUG, HOC-FUG, HRLEU-FUG, LRU, NHT-FUG	60GGGALL	40 CFR Part 60, Subpart GGG	No changing attributes.
GRP-5GCCVV	Fugitive Emission Units	11F-HOC, 49-RSU, 49-XFU, 4F, CRUDE UNIT, CRU-FUG, HCU-FUG, HOC-FUG, HRLEU-FUG, LRU, NHT-FUG	63CCVVALL	40 CFR Part 63, Subpart CC	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
GRP-R5-1	Fugitive Emission Units	41F, AMINE-FUG, SMR-FUG, SWS-FUG	R5322ALL	30 TAC Chapter 115, Fugitives Pet Ref B Counties	No changing attributes.
GRP-R5-2	Fugitive Emission Units	30B01F, 30B02F, 30B03F	R5322ALL	30 TAC Chapter 115, Fugitives Pet Ref B Counties	No changing attributes.
GRP-R5CC	Fugitive Emission Units	11F-HDS, ALKY-FUG, HDS FUG	R5322ALL	30 TAC Chapter 115, Fugitives Pet Ref B Counties	No changing attributes.
GRP-R5CC	Fugitive Emission Units	11F-HDS, ALKY-FUG, HDS FUG	63CCHALL	40 CFR Part 63, Subpart CC	No changing attributes.
GRP-R5CC2	Fugitive Emission Units	DOCKS-F, GAS BLEND, PIPING FUG, TERMIN 2/2A, TERMINAL 1, TERMINAL 3	R5322ALL	30 TAC Chapter 115, Fugitives Pet Ref B Counties	No changing attributes.
GRP-R5CC2	Fugitive Emission Units	DOCKS-F, GAS BLEND, PIPING FUG, TERMIN 2/2A, TERMINAL 1, TERMINAL 3	63CCHALL	40 CFR Part 63, Subpart CC	No changing attributes.
GRP-R5G	Fugitive Emission Units	46F/24F, 47PSA, VACUUMUNIT	R5322ALL	30 TAC Chapter 115, Fugitives Pet Ref B Counties	No changing attributes.
GRP-R5G	Fugitive Emission Units	46F/24F, 47PSA, VACUUMUNIT	60GGGALL	40 CFR Part 60, Subpart GGG	No changing attributes.
GRP-SRU3	Fugitive Emission Units	ATU3FUG, SCOTFUG, SRU3FUG	R5322ALL	30 TAC Chapter 115, Fugitives Pet Ref B Counties	No changing attributes.
GRP-SRU3	Fugitive Emission Units	ATU3FUG,	60GGGALL	40 CFR Part 60, Subpart	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
		SCOTFUG, SRU3FUG		GGG	
LPG STORAG	Fugitive Emission Units	N/A	R5322ALL	30 TAC Chapter 115, Fugitives Pet Ref B Counties	No changing attributes.
MTBE-FUG	Fugitive Emission Units	N/A	R5322ALL	30 TAC Chapter 115, Fugitives Pet Ref B Counties	No changing attributes.
MTBE-FUG	Fugitive Emission Units	N/A	60GGGALL	40 CFR Part 60, Subpart GGG	No changing attributes.
MVRUF	Fugitive Emission Units	N/A	R5322ALL	30 TAC Chapter 115, Fugitives Pet Ref B Counties	No changing attributes.
MVRUF	Fugitive Emission Units	N/A	63CCVVALL	40 CFR Part 63, Subpart CC	No changing attributes.
OLEFLEX-FU	Fugitive Emission Units	N/A	60VVALL	40 CFR Part 60, Subpart VV	No changing attributes.
RAIL-FUG	Fugitive Emission Units	N/A	R5322ALL	30 TAC Chapter 115, Fugitives Pet Ref B Counties	No changing attributes.
RAIL-FUG	Fugitive Emission Units	N/A	63CCALL	40 CFR Part 63, Subpart CC	No changing attributes.
WWTP-FUG	Fugitive Emission Units	N/A	R5322ALL	30 TAC Chapter 115, Fugitives Pet Ref B Counties	No changing attributes.
SRU	Gas Sweetening/Sulfur Recovery Units	N/A	REG2	30 TAC Chapter 112, Sulfur Compounds	No changing attributes.
SRU3	Gas Sweetening/Sulfur Recovery Units	N/A	REG2	30 TAC Chapter 112, Sulfur Compounds	No changing attributes.
BARGEDOCKS	Loading/Unloading Operations	N/A	61BB	40 CFR Part 61, Subpart BB	No changing attributes.
BARGEDOCKS	Loading/Unloading Operations	N/A	63CC	40 CFR Part 63, Subpart CC	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
BARGEDOCKS	Loading/Unloading Operations	N/A	63Ya	40 CFR Part 63, Subpart Y	MATERIAL LOADED = Material other than crude oil or gasoline., SOURCE EMISSIONS = Source with emissions less than 10 and 25 tons.
BARGEDOCKS	Loading/Unloading Operations	N/A	63Yb	40 CFR Part 63, Subpart Y	MATERIAL LOADED = Gasoline., SOURCE EMISSIONS = Source with emissions of 10 or 25 tons., THROUGHPUT = Source with throughput of 10 M barrels or 200 M barrels., VAPOR BALANCING SYSTEM = Emissions are not reduced by a vapor balancing system., CEMS = Continuous emissions monitoring system (CEMS) is not being used., DOCUMENT VAPOR TIGHTNESS = Electing to comply with the emissions reporting requirements in 40 CFR § 63.567(b)(5)(i)., SUBPART Y CTRL DEV TYPE = Carbon adsorber with vacuum regeneration., PERFORMANCE TEST = Baseline temperature from manufacturer., ALTERNATE MONITORING = Complying with the control device specific monitoring procedures in 40 CFR § 63.564., ALTERNATE TEST

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					PROCEDURE = Complying with the test procedures in 40 CFR § 63.565., BYPASS FLOW INDICATOR = Visual inspection of seal or closure mechanism., VENT STREAM BY-PASS = There are valves that could route displaced vapors to the atmosphere.
RAILRACK1	Loading/Unloading Operations	N/A	R5211	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.
SHIPDOCKS	Loading/Unloading Operations	N/A	61BB	40 CFR Part 61, Subpart BB	No changing attributes.
SHIPDOCKS	Loading/Unloading Operations	N/A	63CC	40 CFR Part 63, Subpart CC	No changing attributes.
SHIPDOCKS	Loading/Unloading Operations	N/A	63Ya	40 CFR Part 63, Subpart Y	MATERIAL LOADED = Material other than crude oil or gasoline., SOURCE EMISSIONS = Source with emissions less than 10 and 25 tons.
SHIPDOCKS	Loading/Unloading Operations	N/A	63Yb	40 CFR Part 63, Subpart Y	MATERIAL LOADED = Gasoline., SOURCE EMISSIONS = Source with emissions of 10 or 25 tons., THROUGHPUT = Source with throughput of 10 M barrels or 200 M barrels., VAPOR BALANCING SYSTEM = Emissions are not reduced by a vapor balancing system., CEMS

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					= Continuous emissions monitoring system (CEMS) is not being used., DOCUMENT VAPOR TIGHTNESS = Electing to comply with the emissions reporting requirements in 40 CFR § 63.567(b)(5)(i)., SUBPART Y CTRL DEV TYPE = Carbon adsorber with vacuum regeneration., PERFORMANCE TEST = Baseline temperature from manufacturer., ALTERNATE MONITORING = Complying with the control device specific monitoring procedures in 40 CFR § 63.564., ALTERNATE TEST PROCEDURE = Complying with the test procedures in 40 CFR § 63.565., BYPASS FLOW INDICATOR = Visual inspection of seal or closure mechanism., VENT STREAM BY-PASS = There are valves that could route displaced vapors to the atmosphere.
T-RACK	Loading/Unloading Operations	N/A	R5211a	30 TAC Chapter 115, Loading and Unloading of VOC	CHAPTER 115 FACILITY TYPE = Gasoline terminal, PRODUCT TRANSFERRED = Gasoline, TRUE VAPOR PRESSURE = True vapor pressure is greater than or equal to 1.5 psia., DAILY

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					THROUGHPUT = Daily throughput not determined since 30 TAC § 115.217(a)(2)(B), (b)(3)(B), (a)(2)(A), and (b)(3)(A) exemptions do not apply to marine terminals or gasoline terminals., CHPTR 115 CNTRL DEV TYPE = Vapor control system with a vapor combustor., TRANSFER TYPE = Only loading., VAPOR TIGHT = All liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected., VAPOR SPACE HOLDING TANK = the gasoline terminal does not have a variable vapor space holding tank design that can process vapors independent of transport vessel loading or chooses compliance with 30 TAC 115.212(a)(4)(C).
T-RACK	Loading/Unloading Operations	N/A	R5211b	30 TAC Chapter 115, Loading and Unloading of VOC	CHAPTER 115 FACILITY TYPE = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal., PRODUCT TRANSFERRED = Volatile organic compounds other than

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					liquefied petroleum gas, crude oil, condensate and gasoline., TRUE VAPOR PRESSURE = True vapor pressure is less than 1.5 psia., TRANSFER TYPE = Loading and unloading.
T-RACK	Loading/Unloading Operations	N/A	R5211c	30 TAC Chapter 115, Loading and Unloading of VOC	CHAPTER 115 FACILITY TYPE = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal., PRODUCT TRANSFERRED = Liquefied petroleum gas (LPG), crude oil, or condensate., TRANSFER TYPE = Loading and unloading.
T-RACK	Loading/Unloading Operations	N/A	63CC	40 CFR Part 63, Subpart CC	No changing attributes.
GRP-RRR	Reactor	38-V-23, 38-V-32	60RRRa	40 CFR Part 60, Subpart RRR	No changing attributes.
GRP-RRR	Reactor	38-V-23, 38-V-32	60RRRb	40 CFR Part 60, Subpart RRR	No changing attributes.
GRP-RRR	Reactor	38-V-23, 38-V-32	60RRRc	40 CFR Part 60, Subpart RRR	No changing attributes.
DEGREASE-F	Solvent Degreasing Machines	N/A	R5412	30 TAC Chapter 115, Degreasing Processes	No changing attributes.
16-P-11-EN	SRIC Engines	N/A	63-ZZZZ	40 CFR Part 63, Subpart ZZZZ	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
16-P-12-EN	SRIC Engines	N/A	63-ZZZZ	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
16-P-13-EN	SRIC Engines	N/A	63-ZZZZ	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
16-P-14-EN	SRIC Engines	N/A	63-ZZZZ	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
16-P-4-EN	SRIC Engines	N/A	63-ZZZZ	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
16-P-7-EN	SRIC Engines	N/A	63-ZZZZ	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
83P136A-EN	SRIC Engines	N/A	60-IIII	40 CFR Part 60, Subpart IIII	No changing attributes.
83P136A-EN	SRIC Engines	N/A	60-IIII	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
83P136B-EN	SRIC Engines	N/A	60-IIII	40 CFR Part 60, Subpart IIII	No changing attributes.
83P136B-EN	SRIC Engines	N/A	60-IIII	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
03-TK-156	Storage Tanks/Vessels	N/A	R5112-a	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is less than 1.0 psia, PRODUCT STORED = VOC other than crude oil or condensate
03-TK-156	Storage Tanks/Vessels	N/A	R5112-b	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					PRESSURE = True vapor pressure is greater than or equal to 1.5 psia, PRODUCT STORED = VOC other than crude oil or condensate
03-TK-156	Storage Tanks/Vessels	N/A	R5112-c	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is greater than or equal to 1.5 psia, PRODUCT STORED = Crude oil and/or condensate
03-TK-156	Storage Tanks/Vessels	N/A	60KB-b	40 CFR Part 60, Subpart Kb	PRODUCT STORED = Petroleum liquid (other than petroleum or condensate)
03-TK-156	Storage Tanks/Vessels	N/A	60KB-c	40 CFR Part 60, Subpart Kb	PRODUCT STORED = Volatile organic liquid
03-TK-156	Storage Tanks/Vessels	N/A	60KB-d	40 CFR Part 60, Subpart Kb	PRODUCT STORED = Crude oil stored, processed, and/or treated after custody transfer, REID VAPOR PRESSURE = Reid vapor pressure is greater than or equal to 2.0 psia
03-TK-156	Storage Tanks/Vessels	N/A	63CC	40 CFR Part 63, Subpart CC	PRODUCT STORED = Refined petroleum products
03-TK-156	Storage Tanks/Vessels	N/A	63CC-b	40 CFR Part 63, Subpart CC	REID VAPOR PRESSURE = Reid vapor pressure is greater than or equal to 2.0 psia, PRODUCT STORED = Crude oil

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
03-TK-161	Storage Tanks/Vessels	N/A	R5112-a	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is less than 1.0 psia, PRODUCT STORED = VOC other than crude oil or condensate
03-TK-161	Storage Tanks/Vessels	N/A	R5112-b	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is greater than or equal to 1.5 psia, PRODUCT STORED = VOC other than crude oil or condensate
03-TK-161	Storage Tanks/Vessels	N/A	R5112-c	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is greater than or equal to 1.5 psia, PRODUCT STORED = Crude oil and/or condensate
03-TK-161	Storage Tanks/Vessels	N/A	60KB-b	40 CFR Part 60, Subpart Kb	No changing attributes.
03-TK-161	Storage Tanks/Vessels	N/A	60KB-c	40 CFR Part 60, Subpart Kb	No changing attributes.
03-TK-161	Storage Tanks/Vessels	N/A	60KB-d	40 CFR Part 60, Subpart Kb	No changing attributes.
03-TK-161	Storage Tanks/Vessels	N/A	63CC	40 CFR Part 63, Subpart CC	PRODUCT STORED = Refined petroleum products

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
03-TK-161	Storage Tanks/Vessels	N/A	63CC-b	40 CFR Part 63, Subpart CC	REID VAPOR PRESSURE = Reid vapor pressure is greater than or equal to 2.0 psia, PRODUCT STORED = Crude oil
43-TK-04	Storage Tanks/Vessels	N/A	R5112-a	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
50-TK-60	Storage Tanks/Vessels	N/A	R5112-a	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is less than 1.0 psia, PRODUCT STORED = VOC other than crude oil or condensate
50-TK-60	Storage Tanks/Vessels	N/A	R5112-b	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is greater than or equal to 1.5 psia, PRODUCT STORED = VOC other than crude oil or condensate
50-TK-60	Storage Tanks/Vessels	N/A	R5112-c	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is greater than or equal to 1.5 psia, PRODUCT STORED = Crude oil and/or condensate
50-TK-60	Storage Tanks/Vessels	N/A	60KA-b	40 CFR Part 60, Subpart Ka	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
50-TK-60	Storage Tanks/Vessels	N/A	60KA-c	40 CFR Part 60, Subpart Ka	No changing attributes.
50-TK-60	Storage Tanks/Vessels	N/A	60KA-d	40 CFR Part 60, Subpart Ka	No changing attributes.
50-TK-60	Storage Tanks/Vessels	N/A	63CC	40 CFR Part 63, Subpart CC	No changing attributes.
50-TK-61	Storage Tanks/Vessels	N/A	R5112-a	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is less than 1.0 psia, PRODUCT STORED = VOC other than crude oil or condensate
50-TK-61	Storage Tanks/Vessels	N/A	R5112-b	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is greater than or equal to 1.5 psia, PRODUCT STORED = VOC other than crude oil or condensate
50-TK-61	Storage Tanks/Vessels	N/A	R5112-c	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is greater than or equal to 1.5 psia, PRODUCT STORED = Crude oil and/or condensate
50-TK-61	Storage Tanks/Vessels	N/A	60KA-b	40 CFR Part 60, Subpart Ka	No changing attributes.
50-TK-61	Storage Tanks/Vessels	N/A	60KA-c	40 CFR Part 60, Subpart Ka	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
50-TK-61	Storage Tanks/Vessels	N/A	60KA-d	40 CFR Part 60, Subpart Ka	No changing attributes.
50-TK-61	Storage Tanks/Vessels	N/A	63CC	40 CFR Part 63, Subpart CC	No changing attributes.
70-TK-109	Storage Tanks/Vessels	N/A	R5112-a	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is less than 1.0 psia, PRODUCT STORED = VOC other than crude oil or condensate
70-TK-109	Storage Tanks/Vessels	N/A	R5112-b	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is greater than or equal to 1.5 psia, PRODUCT STORED = VOC other than crude oil or condensate
70-TK-109	Storage Tanks/Vessels	N/A	R5112-c	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is greater than or equal to 1.5 psia, PRODUCT STORED = Crude oil and/or condensate
70-TK-109	Storage Tanks/Vessels	N/A	60K-b	40 CFR Part 60, Subpart K	No changing attributes.
70-TK-109	Storage Tanks/Vessels	N/A	60K-c	40 CFR Part 60, Subpart K	No changing attributes.
70-TK-109	Storage Tanks/Vessels	N/A	60K-d	40 CFR Part 60, Subpart K	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
70-TK-109	Storage Tanks/Vessels	N/A	63CC	40 CFR Part 63, Subpart CC	No changing attributes.
70-TK-110	Storage Tanks/Vessels	N/A	R5112-a	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is less than 1.0 psia, PRODUCT STORED = VOC other than crude oil or condensate
70-TK-110	Storage Tanks/Vessels	N/A	R5112-b	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is greater than or equal to 1.5 psia, PRODUCT STORED = VOC other than crude oil or condensate
70-TK-110	Storage Tanks/Vessels	N/A	R5112-c	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is greater than or equal to 1.5 psia, PRODUCT STORED = Crude oil and/or condensate
70-TK-110	Storage Tanks/Vessels	N/A	60KB-b	40 CFR Part 60, Subpart Kb	No changing attributes.
70-TK-110	Storage Tanks/Vessels	N/A	60KB-c	40 CFR Part 60, Subpart Kb	No changing attributes.
70-TK-110	Storage Tanks/Vessels	N/A	60KB-d	40 CFR Part 60, Subpart Kb	No changing attributes.
70-TK-110	Storage Tanks/Vessels	N/A	63CC-a	40 CFR Part 63, Subpart CC	PRODUCT STORED = Refined

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					petroleum products
70-TK-110	Storage Tanks/Vessels	N/A	63CC-b	40 CFR Part 63, Subpart CC	REID VAPOR PRESSURE = Reid vapor pressure is greater than or equal to 2.0 psia, PRODUCT STORED = Crude oil
70-TK-138	Storage Tanks/Vessels	N/A	R5112-a	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
70-TK-138	Storage Tanks/Vessels	N/A	60K-b	40 CFR Part 60, Subpart K	No changing attributes.
70-TK-140	Storage Tanks/Vessels	N/A	R5112	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
70-TK-140	Storage Tanks/Vessels	N/A	63GGGGG-1	40 CFR Part 63, Subpart GGGGG	No changing attributes.
70-TK-95	Storage Tanks/Vessels	N/A	R5112-a	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
70-TK-95	Storage Tanks/Vessels	N/A	60K-b	40 CFR Part 60, Subpart K	No changing attributes.
73-TK-166	STORAGE TANKS/VESSELS	N/A	R5112	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
73-TK-166	STORAGE TANKS/VESSELS	N/A	60KB	40 CFR Part 60, Subpart Kb	No changing attributes.
73-TK-166	STORAGE TANKS/VESSELS	N/A	63CC	40 CFR Part 63, Subpart CC	No changing attributes.
73-TK-167	STORAGE TANKS/VESSELS	N/A	R5112	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
73-TK-167	STORAGE TANKS/VESSELS	N/A	60KB	40 CFR Part 60, Subpart Kb	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
73-TK-167	STORAGE TANKS/VESSELS	N/A	63CC	40 CFR Part 63, Subpart CC	No changing attributes.
83-TK-155	Storage Tanks/Vessels	N/A	R5112-a	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is less than 1.0 psia, PRODUCT STORED = VOC other than crude oil or condensate
83-TK-155	Storage Tanks/Vessels	N/A	R5112-b	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is greater than or equal to 1.5 psia, PRODUCT STORED = VOC other than crude oil or condensate
83-TK-155	Storage Tanks/Vessels	N/A	R5112-c	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is greater than or equal to 1.5 psia, PRODUCT STORED = Crude oil and/or condensate
83-TK-155	Storage Tanks/Vessels	N/A	60KB-b	40 CFR Part 60, Subpart Kb	No changing attributes.
83-TK-155	Storage Tanks/Vessels	N/A	60KB-c	40 CFR Part 60, Subpart Kb	No changing attributes.
83-TK-155	Storage Tanks/Vessels	N/A	60KB-d	40 CFR Part 60, Subpart Kb	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
83-TK-155	Storage Tanks/Vessels	N/A	60QQQ	40 CFR Part 60, Subpart QQQ	No changing attributes.
83-TK-155	Storage Tanks/Vessels	N/A	61FF	40 CFR Part 61, Subpart FF	No changing attributes.
83-TK-162	Storage Tanks/Vessels	N/A	R5112-a	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is less than 1.0 psia, PRODUCT STORED = VOC other than crude oil or condensate
83-TK-162	Storage Tanks/Vessels	N/A	R5112-b	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is greater than or equal to 1.5 psia, PRODUCT STORED = VOC other than crude oil or condensate
83-TK-162	Storage Tanks/Vessels	N/A	R5112-c	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is greater than or equal to 1.5 psia, PRODUCT STORED = Crude oil and/or condensate
83-TK-162	Storage Tanks/Vessels	N/A	60KB-b	40 CFR Part 60, Subpart Kb	No changing attributes.
83-TK-162	Storage Tanks/Vessels	N/A	60KB-c	40 CFR Part 60, Subpart Kb	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
83-TK-162	Storage Tanks/Vessels	N/A	60KB-d	40 CFR Part 60, Subpart Kb	No changing attributes.
83-TK-162	Storage Tanks/Vessels	N/A	60QQQ	40 CFR Part 60, Subpart QQQ	No changing attributes.
83-TK-162	Storage Tanks/Vessels	N/A	61FF	40 CFR Part 61, Subpart FF	No changing attributes.
83-TK-23	Storage Tanks/Vessels	N/A	R5112-a	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is less than 1.0 psia, PRODUCT STORED = VOC other than crude oil or condensate
83-TK-23	Storage Tanks/Vessels	N/A	R5112-b	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is greater than or equal to 1.5 psia, PRODUCT STORED = VOC other than crude oil or condensate
83-TK-23	Storage Tanks/Vessels	N/A	R5112-c	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is greater than or equal to 1.5 psia, PRODUCT STORED = Crude oil and/or condensate
83-TK-23	Storage Tanks/Vessels	N/A	60KA-b	40 CFR Part 60, Subpart Ka	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
83-TK-23	Storage Tanks/Vessels	N/A	60KA-c	40 CFR Part 60, Subpart Ka	No changing attributes.
83-TK-23	Storage Tanks/Vessels	N/A	60KA-d	40 CFR Part 60, Subpart Ka	No changing attributes.
83-TK-23	Storage Tanks/Vessels	N/A	60QQQ	40 CFR Part 60, Subpart QQQ	No changing attributes.
83-TK-25	Storage Tanks/Vessels	N/A	R5112-a	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
83-TK-25	Storage Tanks/Vessels	N/A	60KA-b	40 CFR Part 60, Subpart Ka	No changing attributes.
83-TK-25	Storage Tanks/Vessels	N/A	61FF	40 CFR Part 61, Subpart FF	No changing attributes.
83-TK-26	Storage Tanks/Vessels	N/A	R5112-a	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is less than 1.0 psia, PRODUCT STORED = VOC other than crude oil or condensate
83-TK-26	Storage Tanks/Vessels	N/A	R5112-b	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is greater than or equal to 1.5 psia, PRODUCT STORED = VOC other than crude oil or condensate
83-TK-26	Storage Tanks/Vessels	N/A	R5112-c	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					pressure is greater than or equal to 1.5 psia, PRODUCT STORED = Crude oil and/or condensate
83-TK-26	Storage Tanks/Vessels	N/A	60KB-b	40 CFR Part 60, Subpart Kb	No changing attributes.
83-TK-26	Storage Tanks/Vessels	N/A	60KB-c	40 CFR Part 60, Subpart Kb	No changing attributes.
83-TK-26	Storage Tanks/Vessels	N/A	60KB-d	40 CFR Part 60, Subpart Kb	No changing attributes.
83-TK-26	Storage Tanks/Vessels	N/A	60QQQ	40 CFR Part 60, Subpart QQQ	No changing attributes.
83-TK-26	Storage Tanks/Vessels	N/A	63CC	40 CFR Part 63, Subpart CC	PRODUCT STORED = Refined petroleum products
83-TK-26	Storage Tanks/Vessels	N/A	63CC-b	40 CFR Part 63, Subpart CC	REID VAPOR PRESSURE = Reid vapor pressure is greater than or equal to 2.0 psia, PRODUCT STORED = Crude oil
83-TK-28	Storage Tanks/Vessels	N/A	R5112-a	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
83-V-97	Storage Tanks/Vessels	N/A	R5112-a	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is less than 1.0 psia, PRODUCT STORED = VOC other than crude oil or condensate
83-V-97	Storage Tanks/Vessels	N/A	R5112-b	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					PRESSURE = True vapor pressure is greater than or equal to 1.5 psia, PRODUCT STORED = VOC other than crude oil or condensate
83-V-97	Storage Tanks/Vessels	N/A	R5112-c	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is greater than or equal to 1.5 psia, PRODUCT STORED = Crude oil and/or condensate
83-V-97	Storage Tanks/Vessels	N/A	60KB-b	40 CFR Part 60, Subpart Kb	No changing attributes.
83-V-97	Storage Tanks/Vessels	N/A	60KB-c	40 CFR Part 60, Subpart Kb	No changing attributes.
83-V-97	Storage Tanks/Vessels	N/A	60KB-d	40 CFR Part 60, Subpart Kb	No changing attributes.
83-V-97	Storage Tanks/Vessels	N/A	60QQQ	40 CFR Part 60, Subpart QQQ	No changing attributes.
83-V-97	Storage Tanks/Vessels	N/A	61FF	40 CFR Part 61, Subpart FF	No changing attributes.
83-V-98	Storage Tanks/Vessels	N/A	R5112-a	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is less than 1.0 psia, PRODUCT STORED = VOC other than crude oil or condensate
83-V-98	Storage Tanks/Vessels	N/A	R5112-b	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					gallons, TRUE VAPOR PRESSURE = True vapor pressure is greater than or equal to 1.5 psia, PRODUCT STORED = VOC other than crude oil or condensate
83-V-98	Storage Tanks/Vessels	N/A	R5112-c	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is greater than or equal to 1.5 psia, PRODUCT STORED = Crude oil and/or condensate
83-V-98	Storage Tanks/Vessels	N/A	60KB-b	40 CFR Part 60, Subpart Kb	No changing attributes.
83-V-98	Storage Tanks/Vessels	N/A	60KB-c	40 CFR Part 60, Subpart Kb	No changing attributes.
83-V-98	Storage Tanks/Vessels	N/A	60KB-d	40 CFR Part 60, Subpart Kb	No changing attributes.
83-V-98	Storage Tanks/Vessels	N/A	61FF	40 CFR Part 61, Subpart FF	No changing attributes.
83-V-98	Storage Tanks/Vessels	N/A	63CC	40 CFR Part 63, Subpart CC	No changing attributes.
GRP-EFRA1	Storage Tanks/Vessels	50-TK-57, 50-TK-59, 72-TK-14, 72-TK-15	R5112-a	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is less than 1.0 psia, PRODUCT STORED = VOC other than crude oil or condensate
GRP-EFRA1	Storage Tanks/Vessels	50-TK-57, 50-TK-59, 72-TK-14, 72-TK-15	R5112-b	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					gallons, TRUE VAPOR PRESSURE = True vapor pressure is greater than or equal to 1.5 psia, PRODUCT STORED = VOC other than crude oil or condensate
GRP-EFRA1	Storage Tanks/Vessels	50-TK-57, 50-TK-59, 72-TK-14, 72-TK-15	R5112-c	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is greater than or equal to 1.5 psia, PRODUCT STORED = Crude oil and/or condensate
GRP-EFRA1	Storage Tanks/Vessels	50-TK-57, 50-TK-59, 72-TK-14, 72-TK-15	60KA-b	40 CFR Part 60, Subpart Ka	No changing attributes.
GRP-EFRA1	Storage Tanks/Vessels	50-TK-57, 50-TK-59, 72-TK-14, 72-TK-15	60KA-c	40 CFR Part 60, Subpart Ka	No changing attributes.
GRP-EFRA1	Storage Tanks/Vessels	50-TK-57, 50-TK-59, 72-TK-14, 72-TK-15	60KA-d	40 CFR Part 60, Subpart Ka	No changing attributes.
GRP-EFRA1	Storage Tanks/Vessels	50-TK-57, 50-TK-59, 72-TK-14, 72-TK-15	63CC	40 CFR Part 63, Subpart CC	No changing attributes.
GRP-ERLQA	Storage Tanks/Vessels	83-V-58, 83-V-59	R5112-a	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is less than 1.0 psia, PRODUCT STORED = VOC other than crude oil or condensate

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
GRP-ERLQA	Storage Tanks/Vessels	83-V-58, 83-V-59	R5112-b	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is greater than or equal to 1.5 psia, PRODUCT STORED = VOC other than crude oil or condensate
GRP-ERLQA	Storage Tanks/Vessels	83-V-58, 83-V-59	R5112-c	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is greater than or equal to 1.5 psia, PRODUCT STORED = Crude oil and/or condensate
GRP-ERLQA	Storage Tanks/Vessels	83-V-58, 83-V-59	60KB-b	40 CFR Part 60, Subpart Kb	No changing attributes.
GRP-ERLQA	Storage Tanks/Vessels	83-V-58, 83-V-59	60KB-c	40 CFR Part 60, Subpart Kb	No changing attributes.
GRP-ERLQA	Storage Tanks/Vessels	83-V-58, 83-V-59	60KB-d	40 CFR Part 60, Subpart Kb	No changing attributes.
GRP-ERLQA	Storage Tanks/Vessels	83-V-58, 83-V-59	60QQQ	40 CFR Part 60, Subpart QQQ	No changing attributes.
GRP-ERLQA	Storage Tanks/Vessels	83-V-58, 83-V-59	61FF	40 CFR Part 61, Subpart FF	No changing attributes.
GRP-ERLQA	Storage Tanks/Vessels	83-V-58, 83-V-59	63CC	40 CFR Part 63, Subpart CC	No changing attributes.
GRP-FIXA2	Storage Tanks/Vessels	70-TK-105, 70-TK-98, 73-TK-9	R5112-a	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
GRP-FIXA2	Storage Tanks/Vessels	70-TK-105, 70-TK-98, 73-TK-9	60KA-b	40 CFR Part 60, Subpart Ka	No changing attributes.
GRP-FIXA2	Storage Tanks/Vessels	70-TK-105, 70-TK-	63CC	40 CFR Part 63, Subpart CC	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
		98, 73-TK-9			
GRP-FIXAN	Storage Tanks/Vessels	70-TK-149, 70-TK-150, 72-TK-18, 72-TK-19, 72-TK-20	R5112-a	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
GRP-FIXAN	Storage Tanks/Vessels	70-TK-149, 70-TK-150, 72-TK-18, 72-TK-19, 72-TK-20	60KA-b	40 CFR Part 60, Subpart Ka	No changing attributes.
GRP-FIXAS	Storage Tanks/Vessels	43-TK-08, 43-V-10	R5112-a	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
GRP-FIXK2	Storage Tanks/Vessels	70-TK-96, 70-TK-97	R5112-a	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
GRP-FIXK2	Storage Tanks/Vessels	70-TK-96, 70-TK-97	60K-b	40 CFR Part 60, Subpart K	No changing attributes.
GRP-FIXK2	Storage Tanks/Vessels	70-TK-96, 70-TK-97	63CC	40 CFR Part 63, Subpart CC	No changing attributes.
GRP-GDTKS	Storage Tanks/Vessels	70-TK-66, 70-TK-67, 70-TK-68	R5112-a	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is less than 1.0 psia, PRODUCT STORED = VOC other than crude oil or condensate
GRP-GDTKS	Storage Tanks/Vessels	70-TK-66, 70-TK-67, 70-TK-68	R5112-b	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is greater than or equal to 1.5 psia, PRODUCT STORED = VOC other than crude oil or

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					condensate
GRP-GDTKS	Storage Tanks/Vessels	70-TK-66, 70-TK-67, 70-TK-68	R5112-c	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is greater than or equal to 1.5 psia, PRODUCT STORED = Crude oil and/or condensate
GRP-GDTKS	Storage Tanks/Vessels	70-TK-66, 70-TK-67, 70-TK-68	60KB-b	40 CFR Part 60, Subpart Kb	No changing attributes.
GRP-GDTKS	Storage Tanks/Vessels	70-TK-66, 70-TK-67, 70-TK-68	60KB-c	40 CFR Part 60, Subpart Kb	No changing attributes.
GRP-GDTKS	Storage Tanks/Vessels	70-TK-66, 70-TK-67, 70-TK-68	60KB-d	40 CFR Part 60, Subpart Kb	No changing attributes.
GRP-GDTKS	Storage Tanks/Vessels	70-TK-66, 70-TK-67, 70-TK-68	63CC	40 CFR Part 63, Subpart CC	PRODUCT STORED = Refined petroleum products
GRP-GDTKS	Storage Tanks/Vessels	70-TK-66, 70-TK-67, 70-TK-68	63CC-b	40 CFR Part 63, Subpart CC	REID VAPOR PRESSURE = Reid vapor pressure is greater than or equal to 2.0 psia, PRODUCT STORED = Crude oil
GRP-IRLQAG	Storage Tanks/Vessels	72-TK-77, 72-TK-78	R5112-a	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is less than 1.0 psia, PRODUCT STORED = VOC other than crude oil or condensate

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
GRP-IRLQAG	Storage Tanks/Vessels	72-TK-77, 72-TK-78	R5112-b	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is greater than or equal to 1.5 psia, PRODUCT STORED = VOC other than crude oil or condensate
GRP-IRLQAG	Storage Tanks/Vessels	72-TK-77, 72-TK-78	R5112-c	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is greater than or equal to 1.5 psia, PRODUCT STORED = Crude oil and/or condensate
GRP-IRLQAG	Storage Tanks/Vessels	72-TK-77, 72-TK-78	60KA-b	40 CFR Part 60, Subpart Ka	No changing attributes.
GRP-IRLQAG	Storage Tanks/Vessels	72-TK-77, 72-TK-78	60KA-c	40 CFR Part 60, Subpart Ka	No changing attributes.
GRP-IRLQAG	Storage Tanks/Vessels	72-TK-77, 72-TK-78	60KA-d	40 CFR Part 60, Subpart Ka	No changing attributes.
GRP-IRLQAG	Storage Tanks/Vessels	72-TK-77, 72-TK-78	63CC	40 CFR Part 63, Subpart CC	No changing attributes.
GRP-IRLQB1	Storage Tanks/Vessels	50-TK-62, 50-TK-63, 72-TK-111	R5112-a	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is less than 1.0 psia, PRODUCT STORED = VOC other than crude oil or condensate
GRP-IRLQB1	Storage Tanks/Vessels	50-TK-62, 50-TK-	R5112-b	30 TAC Chapter 115, Storage	STORAGE CAPACITY =

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
		63, 72-TK-111		of VOCs	Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is greater than or equal to 1.5 psia, PRODUCT STORED = VOC other than crude oil or condensate
GRP-IRLQB1	Storage Tanks/Vessels	50-TK-62, 50-TK-63, 72-TK-111	R5112-c	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is greater than or equal to 1.5 psia, PRODUCT STORED = Crude oil and/or condensate
GRP-IRLQB1	Storage Tanks/Vessels	50-TK-62, 50-TK-63, 72-TK-111	60KB-b	40 CFR Part 60, Subpart Kb	No changing attributes.
GRP-IRLQB1	Storage Tanks/Vessels	50-TK-62, 50-TK-63, 72-TK-111	60KB-c	40 CFR Part 60, Subpart Kb	No changing attributes.
GRP-IRLQB1	Storage Tanks/Vessels	50-TK-62, 50-TK-63, 72-TK-111	60KB-d	40 CFR Part 60, Subpart Kb	No changing attributes.
GRP-IRLQB1	Storage Tanks/Vessels	50-TK-62, 50-TK-63, 72-TK-111	63CC	40 CFR Part 63, Subpart CC	PRODUCT STORED = Refined petroleum products
GRP-IRLQB1	Storage Tanks/Vessels	50-TK-62, 50-TK-63, 72-TK-111	63CC-b	40 CFR Part 63, Subpart CC	REID VAPOR PRESSURE = Reid vapor pressure is greater than or equal to 2.0 psia, PRODUCT STORED = Crude oil
GRP-IRLQBG	Storage Tanks/Vessels	50-TK-64, 50-TK-65	R5112-a	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					gallons, TRUE VAPOR PRESSURE = True vapor pressure is less than 1.0 psia, PRODUCT STORED = VOC other than crude oil or condensate
GRP-IRLQBG	Storage Tanks/Vessels	50-TK-64, 50-TK-65	R5112-b	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is greater than or equal to 1.5 psia, PRODUCT STORED = VOC other than crude oil or condensate
GRP-IRLQBG	Storage Tanks/Vessels	50-TK-64, 50-TK-65	R5112-c	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is greater than or equal to 1.5 psia, PRODUCT STORED = Crude oil and/or condensate
GRP-IRLQBG	Storage Tanks/Vessels	50-TK-64, 50-TK-65	60KB-b	40 CFR Part 60, Subpart Kb	No changing attributes.
GRP-IRLQBG	Storage Tanks/Vessels	50-TK-64, 50-TK-65	60KB-c	40 CFR Part 60, Subpart Kb	No changing attributes.
GRP-IRLQBG	Storage Tanks/Vessels	50-TK-64, 50-TK-65	60KB-d	40 CFR Part 60, Subpart Kb	No changing attributes.
GRP-IRLQBG	Storage Tanks/Vessels	50-TK-64, 50-TK-65	63CC	40 CFR Part 63, Subpart CC	PRODUCT STORED = Refined petroleum products
GRP-IRLQBG	Storage Tanks/Vessels	50-TK-64, 50-TK-65	63CC-b	40 CFR Part 63, Subpart CC	REID VAPOR PRESSURE = Reid vapor pressure is greater

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					than or equal to 2.0 psia, PRODUCT STORED = Crude oil
GRP-IRLQK1	Storage Tanks/Vessels	70-TK-101, 70-TK-102, 70-TK-103, 70-TK-108, 70-TK-137, 70-TK-94	R5112-a	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is less than 1.0 psia, PRODUCT STORED = VOC other than crude oil or condensate
GRP-IRLQK1	Storage Tanks/Vessels	70-TK-101, 70-TK-102, 70-TK-103, 70-TK-108, 70-TK-137, 70-TK-94	R5112-b	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is greater than or equal to 1.5 psia, PRODUCT STORED = VOC other than crude oil or condensate
GRP-IRLQK1	Storage Tanks/Vessels	70-TK-101, 70-TK-102, 70-TK-103, 70-TK-108, 70-TK-137, 70-TK-94	R5112-c	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is greater than or equal to 1.5 psia, PRODUCT STORED = Crude oil and/or condensate
GRP-IRLQK1	Storage Tanks/Vessels	70-TK-101, 70-TK-102, 70-TK-103, 70-TK-108, 70-TK-137, 70-TK-94	60K-b	40 CFR Part 60, Subpart K	No changing attributes.
GRP-IRLQK1	Storage Tanks/Vessels	70-TK-101, 70-TK-	60K-c	40 CFR Part 60, Subpart K	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
		102, 70-TK-103, 70-TK-108, 70-TK-137, 70-TK-94			
GRP-IRLQK1	Storage Tanks/Vessels	70-TK-101, 70-TK-102, 70-TK-103, 70-TK-108, 70-TK-137, 70-TK-94	60K-d	40 CFR Part 60, Subpart K	No changing attributes.
GRP-IRLQK1	Storage Tanks/Vessels	70-TK-101, 70-TK-102, 70-TK-103, 70-TK-108, 70-TK-137, 70-TK-94	63CC	40 CFR Part 63, Subpart CC	No changing attributes.
GRP-IRMTA1	Storage Tanks/Vessels	50-TK-58, 70-TK-93	R5112-a	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is less than 1.0 psia, PRODUCT STORED = VOC other than crude oil or condensate
GRP-IRMTA1	Storage Tanks/Vessels	50-TK-58, 70-TK-93	R5112-b	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is greater than or equal to 1.5 psia, PRODUCT STORED = VOC other than crude oil or condensate
GRP-IRMTA1	Storage Tanks/Vessels	50-TK-58, 70-TK-93	R5112-c	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					PRESSURE = True vapor pressure is greater than or equal to 1.5 psia, PRODUCT STORED = Crude oil and/or condensate
GRP-IRMTA1	Storage Tanks/Vessels	50-TK-58, 70-TK-93	60KA-b	40 CFR Part 60, Subpart Ka	No changing attributes.
GRP-IRMTA1	Storage Tanks/Vessels	50-TK-58, 70-TK-93	60KA-c	40 CFR Part 60, Subpart Ka	No changing attributes.
GRP-IRMTA1	Storage Tanks/Vessels	50-TK-58, 70-TK-93	60KA-d	40 CFR Part 60, Subpart Ka	No changing attributes.
GRP-IRMTA1	Storage Tanks/Vessels	50-TK-58, 70-TK-93	63CC	40 CFR Part 63, Subpart CC	No changing attributes.
GRP-IRMTAG	Storage Tanks/Vessels	72-TK-16, 72-TK-17	R5112-a	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is less than 1.0 psia, PRODUCT STORED = VOC other than crude oil or condensate
GRP-IRMTAG	Storage Tanks/Vessels	72-TK-16, 72-TK-17	R5112-b	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is greater than or equal to 1.5 psia, PRODUCT STORED = VOC other than crude oil or condensate
GRP-IRMTAG	Storage Tanks/Vessels	72-TK-16, 72-TK-17	R5112-c	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					pressure is greater than or equal to 1.5 psia, PRODUCT STORED = Crude oil and/or condensate
GRP-IRMTAG	Storage Tanks/Vessels	72-TK-16, 72-TK-17	60KA-b	40 CFR Part 60, Subpart Ka	No changing attributes.
GRP-IRMTAG	Storage Tanks/Vessels	72-TK-16, 72-TK-17	60KA-c	40 CFR Part 60, Subpart Ka	No changing attributes.
GRP-IRMTAG	Storage Tanks/Vessels	72-TK-16, 72-TK-17	60KA-d	40 CFR Part 60, Subpart Ka	No changing attributes.
GRP-IRMTAG	Storage Tanks/Vessels	72-TK-16, 72-TK-17	63CC	40 CFR Part 63, Subpart CC	No changing attributes.
GRP-IRMTB1	Storage Tanks/Vessels	70-TK-115, 70-TK-116, 72-TK-112, TK-114	R5112-a	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is less than 1.0 psia, PRODUCT STORED = VOC other than crude oil or condensate
GRP-IRMTB1	Storage Tanks/Vessels	70-TK-115, 70-TK-116, 72-TK-112, TK-114	R5112-b	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is greater than or equal to 1.5 psia, PRODUCT STORED = VOC other than crude oil or condensate
GRP-IRMTB1	Storage Tanks/Vessels	70-TK-115, 70-TK-116, 72-TK-112, TK-114	R5112-c	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is greater than or equal

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					to 1.5 psia, PRODUCT STORED = Crude oil and/or condensate
GRP-IRMTB1	Storage Tanks/Vessels	70-TK-115, 70-TK-116, 72-TK-112, TK-114	60KB-b	40 CFR Part 60, Subpart Kb	No changing attributes.
GRP-IRMTB1	Storage Tanks/Vessels	70-TK-115, 70-TK-116, 72-TK-112, TK-114	60KB-c	40 CFR Part 60, Subpart Kb	No changing attributes.
GRP-IRMTB1	Storage Tanks/Vessels	70-TK-115, 70-TK-116, 72-TK-112, TK-114	60KB-d	40 CFR Part 60, Subpart Kb	No changing attributes.
GRP-IRMTB1	Storage Tanks/Vessels	70-TK-115, 70-TK-116, 72-TK-112, TK-114	63CC	40 CFR Part 63, Subpart CC	PRODUCT STORED = Refined petroleum products
GRP-IRMTB1	Storage Tanks/Vessels	70-TK-115, 70-TK-116, 72-TK-112, TK-114	63CC-b	40 CFR Part 63, Subpart CC	REID VAPOR PRESSURE = Reid vapor pressure is greater than or equal to 2.0 psia, PRODUCT STORED = Crude oil
GRP-IRMTBG	Storage Tanks/Vessels	72-TK-75, TK76	R5112-a	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is less than 1.0 psia, PRODUCT STORED = VOC other than crude oil or condensate
GRP-IRMTBG	Storage Tanks/Vessels	72-TK-75, TK76	R5112-b	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					gallons, TRUE VAPOR PRESSURE = True vapor pressure is greater than or equal to 1.5 psia, PRODUCT STORED = VOC other than crude oil or condensate
GRP-IRMTBG	Storage Tanks/Vessels	72-TK-75, TK76	R5112-c	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is greater than or equal to 1.5 psia, PRODUCT STORED = Crude oil and/or condensate
GRP-IRMTBG	Storage Tanks/Vessels	72-TK-75, TK76	60KB-b	40 CFR Part 60, Subpart Kb	No changing attributes.
GRP-IRMTBG	Storage Tanks/Vessels	72-TK-75, TK76	60KB-c	40 CFR Part 60, Subpart Kb	No changing attributes.
GRP-IRMTBG	Storage Tanks/Vessels	72-TK-75, TK76	60KB-d	40 CFR Part 60, Subpart Kb	No changing attributes.
GRP-IRMTBG	Storage Tanks/Vessels	72-TK-75, TK76	63CC	40 CFR Part 63, Subpart CC	PRODUCT STORED = Refined petroleum products
GRP-IRMTBG	Storage Tanks/Vessels	72-TK-75, TK76	63CC-b	40 CFR Part 63, Subpart CC	REID VAPOR PRESSURE = Reid vapor pressure is greater than or equal to 2.0 psia, PRODUCT STORED = Crude oil
GRP-IRMTBQ	Storage Tanks/Vessels	83-TK-159, 83-TK-160	R5112-a	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is less than 1.0 psia, PRODUCT STORED = VOC

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					other than crude oil or condensate
GRP-IRMTBQ	Storage Tanks/Vessels	83-TK-159, 83-TK-160	R5112-b	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is greater than or equal to 1.5 psia, PRODUCT STORED = VOC other than crude oil or condensate
GRP-IRMTBQ	Storage Tanks/Vessels	83-TK-159, 83-TK-160	R5112-c	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is greater than or equal to 1.5 psia, PRODUCT STORED = Crude oil and/or condensate
GRP-IRMTBQ	Storage Tanks/Vessels	83-TK-159, 83-TK-160	60KB-b	40 CFR Part 60, Subpart Kb	No changing attributes.
GRP-IRMTBQ	Storage Tanks/Vessels	83-TK-159, 83-TK-160	60KB-c	40 CFR Part 60, Subpart Kb	No changing attributes.
GRP-IRMTBQ	Storage Tanks/Vessels	83-TK-159, 83-TK-160	60KB-d	40 CFR Part 60, Subpart Kb	No changing attributes.
GRP-IRMTBQ	Storage Tanks/Vessels	83-TK-159, 83-TK-160	60QQQ	40 CFR Part 60, Subpart QQQ	No changing attributes.
GRP-IRMTBQ	Storage Tanks/Vessels	83-TK-159, 83-TK-160	61FF	40 CFR Part 61, Subpart FF	No changing attributes.
GRP-IRMTBQ	Storage Tanks/Vessels	83-TK-159, 83-TK-	63CC	40 CFR Part 63, Subpart CC	PRODUCT STORED = Refined

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
		160			petroleum products
GRP-IRMTBQ	Storage Tanks/Vessels	83-TK-159, 83-TK-160	63CC-b	40 CFR Part 63, Subpart CC	REID VAPOR PRESSURE = Reid vapor pressure is greater than or equal to 2.0 psia, PRODUCT STORED = Crude oil
GRP-IRMTK1	Storage Tanks/Vessels	70-TK-100, 70-TK-104, 70-TK-139, 70-TK-99	R5112-a	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is less than 1.0 psia, PRODUCT STORED = VOC other than crude oil or condensate
GRP-IRMTK1	Storage Tanks/Vessels	70-TK-100, 70-TK-104, 70-TK-139, 70-TK-99	R5112-b	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is greater than or equal to 1.5 psia, PRODUCT STORED = VOC other than crude oil or condensate
GRP-IRMTK1	Storage Tanks/Vessels	70-TK-100, 70-TK-104, 70-TK-139, 70-TK-99	R5112-c	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is greater than or equal to 1.5 psia, PRODUCT STORED = Crude oil and/or condensate
GRP-IRMTK1	Storage Tanks/Vessels	70-TK-100, 70-TK-104, 70-TK-139, 70-	60K-b	40 CFR Part 60, Subpart K	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
		TK-99			
GRP-IRMTK1	Storage Tanks/Vessels	70-TK-100, 70-TK-104, 70-TK-139, 70-TK-99	60K-c	40 CFR Part 60, Subpart K	No changing attributes.
GRP-IRMTK1	Storage Tanks/Vessels	70-TK-100, 70-TK-104, 70-TK-139, 70-TK-99	60K-d	40 CFR Part 60, Subpart K	No changing attributes.
GRP-IRMTK1	Storage Tanks/Vessels	70-TK-100, 70-TK-104, 70-TK-139, 70-TK-99	63CC	40 CFR Part 63, Subpart CC	No changing attributes.
TK-51	Storage Tanks/Vessels	N/A	R5112-a	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is less than 1.0 psia, PRODUCT STORED = VOC other than crude oil or condensate
TK-51	Storage Tanks/Vessels	N/A	R5112-b	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR PRESSURE = True vapor pressure is greater than or equal to 1.5 psia, PRODUCT STORED = VOC other than crude oil or condensate
TK-51	Storage Tanks/Vessels	N/A	R5112-c	30 TAC Chapter 115, Storage of VOCs	STORAGE CAPACITY = Capacity is greater than 40,000 gallons, TRUE VAPOR

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					PRESSURE = True vapor pressure is greater than or equal to 1.5 psia, PRODUCT STORED = Crude oil and/or condensate
TK-51	Storage Tanks/Vessels	N/A	60KB-b	40 CFR Part 60, Subpart Kb	No changing attributes.
TK-51	Storage Tanks/Vessels	N/A	60KB-c	40 CFR Part 60, Subpart Kb	No changing attributes.
TK-51	Storage Tanks/Vessels	N/A	60KB-d	40 CFR Part 60, Subpart Kb	No changing attributes.
TK-51	Storage Tanks/Vessels	N/A	63CC	40 CFR Part 63, Subpart CC	PRODUCT STORED = Refined petroleum products
TK-51	Storage Tanks/Vessels	N/A	63CC-b	40 CFR Part 63, Subpart CC	REID VAPOR PRESSURE = Reid vapor pressure is greater than or equal to 2.0 psia, PRODUCT STORED = Crude oil
GRPTURNJET	Vacuum Producing Systems	36J01, 38J01, 47J01, 49J01, SP-1271	R5311a	30 TAC Chapter 115, Unit Turn & Vac System-Pet Ref	No changing attributes.
GRP-VACJET	Vacuum Producing Systems	02J01, 02J02, 02J03, 02J04, 02J05, 02J06	R5311a	30 TAC Chapter 115, Unit Turn & Vac System-Pet Ref	CONTROL DEVICE = Any other vapor recovery system
GRP-VACJET	Vacuum Producing Systems	02J01, 02J02, 02J03, 02J04, 02J05, 02J06	R5311b	30 TAC Chapter 115, Unit Turn & Vac System-Pet Ref	CONTROL DEVICE = Smokeless flare
APISEP	Volatile Organic Compound Water Separators	N/A	R5131	30 TAC Chapter 115, Water Separation	No changing attributes.
APISEP	Volatile Organic Compound Water Separators	N/A	60QQQ	40 CFR Part 60, Subpart QQQ	No changing attributes.
APISEP	Volatile Organic Compound	N/A	60FF-a	40 CFR Part 61, Subpart FF	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	Water Separators				

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
30-B-02	EU	60Db	SO_2	40 CFR Part 60, Subpart Db	§ 60.104(a)(1) § 60.104	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide in excess of 230 mg/dscm (0.10 gr/dscf). The combustion in a flare of process upset gases or fuel gas that is released to the flare as a result of relief valve leakage or other emergency malfunctions is exempt from this paragraph.	§ 60.105(a) § 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.105(e) § 60.105(e)(3)(ii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4)	§ 60.105(e) § 60.105(e)(3)(ii) § 60.107(e) § 60.107(f)
30-B-02	EU	60Db	PM	40 CFR Part 60, Subpart Db	§ 60.40b(a)	This subpart applies to each steam generating unit constructed, modified, or reconstructed after 6/19/84, and that has a heat input capacity from fuels combusted in the unit > 29 MW (100 MMBtu/hr).	None	[G]§ 60.49b(d) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3)
30-B-02	EU	60Db	PM (OPACITY)	40 CFR Part 60, Subpart Db	§ 60.40b(a)	This subpart applies to each steam generating unit constructed, modified, or reconstructed after 6/19/84, and that has a heat input capacity from fuels combusted in the unit > 29 MW (100 MMBtu/hr).	None	[G]§ 60.49b(d) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3)
30-B-02	EU	60Db	NO_X	40 CFR Part 60, Subpart Db	§ 60.40b(a)	This subpart applies to each steam generating	None	[G]§ 60.49b(d) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						unit constructed, modified, or reconstructed after 6/19/84, and that has a heat input capacity from fuels combusted in the unit > 29 MW (100 MMBtu/hr).			§ 60.49b(a)(3)
30-B-03	EU	60Db	SO_2	40 CFR Part 60, Subpart Db	§ 60.104(a)(1) § 60.104	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide in excess of 230 mg/dscm (0.10 gr/dscf). The combustion in a flare of process upset gases or fuel gas that is released to the flare as a result of relief valve leakage or other emergency malfunctions is exempt from this paragraph.	§ 60.105(a) § 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.105(e) § 60.105(e)(3)(ii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4)	§ 60.105(e) § 60.105(e)(3)(ii) § 60.107(e) § 60.107(f)
30-B-03	EU	60Db	PM	40 CFR Part 60, Subpart Db	§ 60.40b(a)	This subpart applies to each steam generating unit constructed, modified, or reconstructed after 6/19/84, and that has a heat input capacity from fuels combusted in the unit > 29 MW (100 MMBtu/hr).	None	[G]§ 60.49b(d) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3)
30-B-03	EU	60Db	PM (OPACITY)	40 CFR Part 60, Subpart Db	§ 60.40b(a)	This subpart applies to each steam generating unit constructed, modified, or	None	[G]§ 60.49b(d) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						reconstructed after 6/19/84, and that has a heat input capacity from fuels combusted in the unit > 29 MW (100 MMBtu/hr).			
30-B-03	EU	60Db	NO_X	40 CFR Part 60, Subpart Db	§ 60.40b(a)	This subpart applies to each steam generating unit constructed, modified, or reconstructed after 6/19/84, and that has a heat input capacity from fuels combusted in the unit > 29 MW (100 MMBtu/hr).	None	[G]§ 60.49b(d) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3)
30-B-04	EU	60Db	SO_2	40 CFR Part 60, Subpart Db	§ 60.104(a)(1) § 60.104	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide in excess of 230 mg/dscm (0.10 gr/dscf). The combustion in a flare of process upset gases or fuel gas that is released to the flare as a result of relief valve leakage or other emergency malfunctions is exempt from this paragraph.	§ 60.105(a) § 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.105(e) § 60.105(e)(3)(ii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4)	§ 60.105(e) § 60.105(e)(3)(ii) § 60.107(e) § 60.107(f)
30-B-04	EU	60Db	PM	40 CFR Part 60, Subpart Db	§ 60.40b(a)	This subpart applies to each steam generating unit constructed, modified, or reconstructed after 6/19/84, and that has a	None	[G]§ 60.49b(d) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						heat input capacity from fuels combusted in the unit > 29 MW (100 MMBtu/hr).			
30-B-04	EU	60Db	PM (OPACITY)	40 CFR Part 60, Subpart Db	§ 60.40b(a)	This subpart applies to each steam generating unit constructed, modified, or reconstructed after 6/19/84, and that has a heat input capacity from fuels combusted in the unit > 29 MW (100 MMBtu/hr).	None	[G]§ 60.49b(d) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3)
30-B-04	EU	60Db	NO_X	40 CFR Part 60, Subpart Db	§ 60.44b(l)(1) § 60.44b(h) § 60.44b(i) § 60.46b(a)	Affected facilities combusting coal, oil, or natural gas, or a mixture of these fuels, or any other fuels: a limit of 86 ng/JI (0.20 lb/million Btu) heat input unless the affected facility meets the specified requirements.	§ 60.46b(c) § 60.46b(e) § 60.46b(e)(1) § 60.46b(e)(3) [G]§ 60.48b(b) § 60.48b(c) § 60.48b(d) § 60.48b(e) [G]§ 60.48b(e)(2) § 60.48b(e)(3) § 60.48b(f)	[G]§ 60.48b(b) § 60.48b(c) [G]§ 60.49b(d) [G]§ 60.49b(g) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3) § 60.49b(b) § 60.49b(h) § 60.49b(i) § 60.49b(v) § 60.49b(w)
30-B-04	EU	63DDDDD	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
WWTP-FUG	CD	61FF-DRAINS	BENZENE	40 CFR Part 61, Subpart FF	§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(iii)	For each closed-vent system and control device used to comply	§ 61.349(a)(1)(i) § 61.349(e) § 61.349(f)	§ 61.355(i)(1) § 61.355(i)(3)(ii)(A) § 61.356(f)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 61.354(d) [G]§ 61.355(h) § 61.355(i)(1) § 61.355(i)(2) § 61.355(i)(3)(i) § 61.355(i)(3)(ii) § 61.355(i)(3)(ii)(A) § 61.355(i)(3)(ii)(B) § 61.355(i)(3)(ii)(C) § 61.355(i)(3)(iii) § 61.355(i)(3)(iv) § 61.355(i)(4)	§ 61.356(f)(1) § 61.356(f)(2)(i)(G) [G]§ 61.356(f)(3) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3)	
GRP-NNN	EP	60NNNa	VOC/TOC	40 CFR Part 60, Subpart NNN	§ 60.662(a)	Affected facilities shall reduce TOC emissions by 98 weight-percent or to a concentration of 20ppmv, whichever is less stringent. Introduce the stream into the flame zone of a boiler/process heater.	§ 60.663(f) § 60.664(a)	§ 60.665(b) § 60.665(p)	§ 60.663(f) § 60.665(a) § 60.665(b) § 60.665(k) § 60.665(l) § 60.665(p)
GRP-NNN	EP	60NNNb	VOC/TOC	40 CFR Part 60, Subpart NNN	§ 60.662(b) § 60.18	Each affected facility shall combust the emissions in a flare that meets the requirements of § 60.18.	§ 60.663(b) § 60.663(b)(1) § 60.663(b)(2) § 60.664(a) § 60.664(d) [G]§ 60.664(e)	§ 60.663(b)(2) § 60.665(b) § 60.665(b)(3) § 60.665(d) § 60.665(f)	§ 60.665(a) § 60.665(b) § 60.665(b)(3) § 60.665(k) § 60.665(l) § 60.665(l)(2) § 60.665(l)(4)
02-V-12	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(b) § 115.122(b) § 115.122(b)(2)	In Nueces and Victoria Counties, any process vent containing one or more VOC or classes of VOC specified in §115.121 (b)(1)-(3), shall be controlled properly in accordance with §115.122(b).	[G]§ 115.125 § 115.126(2) ** See Periodic Monitoring Summary	§ 115.126 § 115.126(2)	None
02-V-12	EP	63CC	112(B)	40 CFR Part 63,	§ 63.643(a)	The owner or operator	§ 63.116(a)(2)	§ 63.642(e)	§ 63.642(f)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
			HAPS	Subpart CC	§ 63.11(b) § 63.643(a)(1)	of a Group 1 miscellaneous process vent as defined in §63.641 shall comply with the requirements of either §63.643(a)(1)-(2).	§ 63.116(a)(3) § 63.644(a) § 63.644(a)(2) § 63.644(e) § 63.645(a) § 63.645(i)	§ 63.655(h)(1) § 63.655(i)(5)	[G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(ii) [G]§ 63.655(f)(1)(iv) [G]§ 63.655(f)(2) § 63.655(f)(4) § 63.655(g) § 63.655(g)(6) § 63.655(h) § 63.655(h)(1)
38-V-54	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(b) § 115.122(b) § 115.122(b)(3)	In Nueces and Victoria Counties, any process vent containing one or more VOC or classes of VOC specified in §115.121 (b)(1)-(3), shall be controlled properly in accordance with §115.122(b).	[G]§ 115.125 § 115.126(2) ** See Periodic Monitoring Summary	§ 115.126 § 115.126(2)	None
38-V-54	EP	63CC	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.643(a) § 63.116(b) § 63.643(a)(2) § 63.643(b)	The owner or operator of a Group 1 miscellaneous process vent as defined in §63.641 shall comply with the requirements of either §63.643(a)(1)-(2).	§ 63.644(a) § 63.644(a)(3) § 63.644(d) § 63.644(e) § 63.645(a)	§ 63.642(e) § 63.655(h)(1) § 63.655(i)(5)	§ 63.642(f) § 63.644(d) [G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(ii) [G]§ 63.655(f)(2) [G]§ 63.655(f)(3) § 63.655(f)(4) § 63.655(h) § 63.655(h)(1)
38-V-55	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(b) § 115.122(b) § 115.122(b)(3)	In Nueces and Victoria Counties, any process vent containing one or more VOC or classes of VOC specified in §115.121 (b)(1)-(3), shall be controlled properly in accordance with §115.122(b).	[G]§ 115.125 § 115.126(2) ** See Periodic Monitoring Summary	§ 115.126 § 115.126(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
38-V-55	EP	63CC	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.643(a) § 63.116(b) § 63.643(a)(2) § 63.643(b)	The owner or operator of a Group 1 miscellaneous process vent as defined in §63.641 shall comply with the requirements of either §63.643(a)(1)-(2).	§ 63.644(a) § 63.644(a)(3) § 63.644(d) § 63.644(e) § 63.645(a)	§ 63.642(e) § 63.655(h)(1) § 63.655(i)(5)	§ 63.642(f) § 63.644(d) [G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(ii) [G]§ 63.655(f)(2) [G]§ 63.655(f)(3) § 63.655(f)(4) § 63.655(h) § 63.655(h)(1)
44-V-01	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(b) § 115.122(b) § 115.122(b)(2)	In Nueces and Victoria Counties, any process vent containing one or more VOC or classes of VOC specified in §115.121 (b)(1)-(3), shall be controlled properly in accordance with §115.122(b).	[G]§ 115.125 § 115.126(2) ** See Periodic Monitoring Summary	§ 115.126 § 115.126(2)	None
44-V-01	EP	63CCa	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.643(a) § 63.11(b) § 63.643(a)(1)	The owner or operator of a Group 1 miscellaneous process vent as defined in §63.641 shall comply with the requirements of either §63.643(a)(1)-(2).	§ 63.116(a)(2) § 63.116(a)(3) § 63.644(a) § 63.644(a)(2) § 63.644(e) § 63.645(a) § 63.645(i)	§ 63.642(e) § 63.655(h)(1) § 63.655(i)(5)	§ 63.642(f) [G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(ii) [G]§ 63.655(f)(1)(iv) [G]§ 63.655(f)(2) § 63.655(f)(4) § 63.655(g) § 63.655(g)(6) § 63.655(h) § 63.655(h)(1)
47-V-02	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(b) § 115.122(b) § 115.122(b)(3)	In Nueces and Victoria Counties, any process vent containing one or more VOC or classes of VOC specified in §115.121 (b)(1)-(3), shall be controlled properly in accordance with §115.122(b).	[G]§ 115.125 § 115.126(2) ** See Periodic Monitoring Summary	§ 115.126 § 115.126(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
47-V-02	EP	63CC	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.643(a) § 63.116(b) § 63.643(a)(2) § 63.643(b)	The owner or operator of a Group 1 miscellaneous process vent as defined in §63.641 shall comply with the requirements of either §63.643(a)(1)-(2).	§ 63.644(a) § 63.644(a)(3) § 63.644(d) § 63.644(e) § 63.645(a)	§ 63.642(e) § 63.655(h)(1) § 63.655(i)(5)	§ 63.642(f) § 63.644(d) [G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(ii) [G]§ 63.655(f)(2) [G]§ 63.655(f)(3) § 63.655(f)(4) § 63.655(h) § 63.655(h)(1)
48-V-01	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(b) § 115.122(b) § 115.122(b)(3)	In Nueces and Victoria Counties, any process vent containing one or more VOC or classes of VOC specified in §115.121 (b)(1)-(3), shall be controlled properly in accordance with §115.122(b).	[G]§ 115.125 § 115.126(2) ** See Periodic Monitoring Summary	§ 115.126 § 115.126(2)	None
48-V-01	EP	63CC	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.643(a) § 63.116(b) § 63.643(a)(2) § 63.643(b)	The owner or operator of a Group 1 miscellaneous process vent as defined in §63.641 shall comply with the requirements of either §63.643(a)(1)-(2).	§ 63.644(a) § 63.644(a)(3) § 63.644(d) § 63.644(e) § 63.645(a)	§ 63.642(e) § 63.655(h)(1) § 63.655(i)(5)	§ 63.642(f) § 63.644(d) [G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(ii) [G]§ 63.655(f)(2) [G]§ 63.655(f)(3) § 63.655(f)(4) § 63.655(h) § 63.655(h)(1)
49-V-01	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(b) § 115.122(b) § 115.122(b)(2)	In Nueces and Victoria Counties, any process vent containing one or more VOC or classes of VOC specified in §115.121 (b)(1)-(3), shall be controlled properly in accordance with §115.122(b).	[G]§ 115.125 § 115.126(2) ** See Periodic Monitoring Summary	§ 115.126 § 115.126(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
49-V-01	EP	63CC	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.643(a) § 63.11(b) § 63.643(a)(1)	The owner or operator of a Group 1 miscellaneous process vent as defined in §63.641 shall comply with the requirements of either §63.643(a)(1)-(2).	§ 63.116(a)(2) § 63.116(a)(3) § 63.644(a) § 63.644(a)(2) § 63.644(e) § 63.645(a) § 63.645(i)	§ 63.642(e) § 63.655(h)(1) § 63.655(i)(5)	§ 63.642(f) [G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(ii) [G]§ 63.655(f)(1)(iv) [G]§ 63.655(f)(2) § 63.655(f)(4) § 63.655(g) § 63.655(g)(6) § 63.655(h) § 63.655(h)(1)
GRP-EPN118	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(b) § 115.122(b) § 115.122(b)(3)	In Nueces and Victoria Counties, any process vent containing one or more VOC or classes of VOC specified in §115.121 (b)(1)-(3), shall be controlled properly in accordance with §115.122(b).	[G]§ 115.125 § 115.126(2) ** See Periodic Monitoring Summary	§ 115.126 § 115.126(2)	None
GRP-EPN118	EP	R5121a	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(b) § 115.122(b) § 115.122(b)(3)	In Nueces and Victoria Counties, any process vent containing one or more VOC or classes of VOC specified in §115.121 (b)(1)-(3), shall be controlled properly in accordance with §115.122(b).	[G]§ 115.125 § 115.126(2) ** See Periodic Monitoring Summary	§ 115.126 § 115.126(2)	None
GRP-EPN121	EU	R1151	PM	30 TAC Chapter 111, Nonagricultural Processes	§ 111.151(a) § 111.151(c)	No person may cause, suffer, allow, or permit emissions of particulate matter from any source to exceed the allowable rates specified in §111.151, except as provided by §111.153. [§111.151(a)-(c)]	** See CAM Summary	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-EPN121	EP	R1111	OPACITY	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(B) § 111.111(a)(1)(E) § 111.111(a)(3)	Visible emissions from any stationary vent shall not exceed an opacity of 20% averaged over a six minute period for any source on which construction was begun after January 31, 1972.	[G]§ 111.111(a)(1)(F) ** See CAM Summary	None	None
GRP-EPN126A	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(b) § 115.122(b) § 115.122(b)(2)	In Nueces and Victoria Counties, any process vent containing one or more VOC or classes of VOC specified in §115.121 (b)(1)-(3), shall be controlled properly in accordance with §115.122(b).	[G]§ 115.125 § 115.126(2) ** See Periodic Monitoring Summary	§ 115.126 § 115.126(2)	None
GRP-EPN126A	EP	63CC	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.643(a) § 63.11(b) § 63.643(a)(1)	The owner or operator of a Group 1 miscellaneous process vent as defined in §63.641 shall comply with the requirements of either §63.643(a)(1)-(2).	§ 63.116(a)(2) § 63.116(a)(3) § 63.644(a) § 63.644(a)(2) § 63.644(e) § 63.645(a) § 63.645(i)	§ 63.642(e) § 63.655(h)(1) § 63.655(i)(5)	§ 63.642(f) [G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(ii) [G]§ 63.655(f)(1)(iv) [G]§ 63.655(f)(2) § 63.655(f)(4) § 63.655(g) § 63.655(g)(6) § 63.655(h) § 63.655(h)(1)
GRP-EPN126B	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(b) § 115.122(b) § 115.122(b)(2)	In Nueces and Victoria Counties, any process vent containing one or more VOC or classes of VOC specified in §115.121 (b)(1)-(3), shall be controlled properly in accordance with §115.122(b).	[G]§ 115.125 § 115.126(2) ** See Periodic Monitoring Summary	§ 115.126 § 115.126(2)	None
GRP-EPN126B	EP	R5121a	VOC	30 TAC Chapter	§ 115.121(b)	In Nueces and Victoria	[G]§ 115.125	§ 115.126	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				115, Vent Gas Controls	§ 115.122(b) § 115.122(b)(3)	Counties, any process vent containing one or more VOC or classes of VOC specified in §115.121 (b)(1)-(3), shall be controlled properly in accordance with §115.122(b).	§ 115.126(2) ** See Periodic Monitoring Summary	§ 115.126(2)	
GRP-EPN126B	EP	63CCa	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.643(a) § 63.11(b) § 63.643(a)(1)	The owner or operator of a Group 1 miscellaneous process vent as defined in §63.641 shall comply with the requirements of either §63.643(a)(1)-(2).	§ 63.116(a)(2) § 63.116(a)(3) § 63.644(a) § 63.644(a)(2) § 63.644(e) § 63.645(a) § 63.645(i)	§ 63.642(e) § 63.655(h)(1) § 63.655(i)(5)	§ 63.642(f) [G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(ii) [G]§ 63.655(f)(1)(iv) [G]§ 63.655(f)(2) § 63.655(f)(4) § 63.655(g) § 63.655(g)(6) § 63.655(h) § 63.655(h)(1)
GRP-EPN126B	EP	63CCb	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.643(a) § 63.116(b) § 63.643(a)(2) § 63.643(b)	The owner or operator of a Group 1 miscellaneous process vent as defined in §63.641 shall comply with the requirements of either §63.643(a)(1)-(2).	§ 63.644(a) § 63.644(a)(3) § 63.644(d) § 63.644(e) § 63.645(a)	§ 63.642(e) § 63.655(h)(1) § 63.655(i)(5)	§ 63.642(f) § 63.644(d) [G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(ii) [G]§ 63.655(f)(2) [G]§ 63.655(f)(3) § 63.655(f)(4) § 63.655(h) § 63.655(h)(1)
GRP-EPN135	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(b) § 115.122(b) § 115.122(b)(2)	In Nueces and Victoria Counties, any process vent containing one or more VOC or classes of VOC specified in §115.121 (b)(1)-(3), shall be controlled properly in accordance with §115.122(b).	[G]§ 115.125 § 115.126(2) ** See Periodic Monitoring Summary	§ 115.126 § 115.126(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-EPN135	EP	63CCa	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.643(a) § 63.11(b) § 63.643(a)(1)	The owner or operator of a Group 1 miscellaneous process vent as defined in §63.641 shall comply with the requirements of either §63.643(a)(1)-(2).	§ 63.116(a)(2) § 63.116(a)(3) § 63.644(a) § 63.644(a)(2) § 63.644(e) § 63.645(a) § 63.645(i)	§ 63.642(e) § 63.655(h)(1) § 63.655(i)(5)	§ 63.642(f) [G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(ii) [G]§ 63.655(f)(1)(iv) [G]§ 63.655(f)(2) § 63.655(f)(4) § 63.655(g) § 63.655(g)(6) § 63.655(h) § 63.655(h)(1)
13-H-01A	EU	60J	HYDROGEN SULFIDE	40 CFR Part 60, Subpart J	§ 60.104(a)(1) § 60.104 § 60.104(a)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide in excess of 230 mg/dscm (0.10 gr/dscf). The combustion in a flare of process upset gases or fuel gas that is released to the flare as a result of relief valve leakage or other emergency malfunctions is exempt from this paragraph.	§ 60.105(a) § 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.105(e) § 60.105(e)(3)(ii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a) § 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii)	§ 60.105(e) § 60.105(e)(3)(ii) § 60.107(f) § 60.107(g)
13-H-01A	EU	60J-low	HYDROGEN SULFIDE	40 CFR Part 60, Subpart J	§ 60.104(a)(1) § 60.104 § 60.104(a)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide in excess of 230 mg/dscm (0.10 gr/dscf). The combustion in a flare of process upset gases or	§ 60.105(a) [G]§ 60.105(a)(4)(iv) [G]§ 60.105(b) § 60.105(e) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a) [G]§ 60.105(a)(4)(iv) § 60.107(e)	[G]§ 60.105(b) § 60.105(e) § 60.107(f) § 60.107(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						fuel gas that is released to the flare as a result of relief valve leakage or other emergency malfunctions is exempt from this paragraph.			
13-H-01B	EU	60J	HYDROGEN SULFIDE	40 CFR Part 60, Subpart J	§ 60.104(a)(1) § 60.104 § 60.104(a)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide in excess of 230 mg/dscm (0.10 gr/dscf). The combustion in a flare of process upset gases or fuel gas that is released to the flare as a result of relief valve leakage or other emergency malfunctions is exempt from this paragraph.	§ 60.105(a) § 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.105(e) § 60.105(e)(3)(ii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a) § 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii)	§ 60.105(e) § 60.105(e)(3)(ii) § 60.107(f) § 60.107(g)
13-H-01B	EU	60J-low	HYDROGEN SULFIDE	40 CFR Part 60, Subpart J	§ 60.104(a)(1) § 60.104 § 60.104(a)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide in excess of 230 mg/dscm (0.10 gr/dscf). The combustion in a flare of process upset gases or fuel gas that is released to the flare as a result of relief valve leakage or other emergency malfunctions is exempt	§ 60.105(a) [G]§ 60.105(a)(4)(iv) [G]§ 60.105(b) § 60.105(e) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a) [G]§ 60.105(a)(4)(iv) § 60.107(e)	[G]§ 60.105(b) § 60.105(e) § 60.107(f) § 60.107(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						from this paragraph.			
13-H-01C	EU	60J	HYDROGEN SULFIDE	40 CFR Part 60, Subpart J	§ 60.104(a)(1) § 60.104 § 60.104(a)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide in excess of 230 mg/dscm (0.10 gr/dscf). The combustion in a flare of process upset gases or fuel gas that is released to the flare as a result of relief valve leakage or other emergency malfunctions is exempt from this paragraph.	§ 60.105(a) § 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.105(e) § 60.105(e)(3)(ii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a) § 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii)	§ 60.105(e) § 60.105(e)(3)(ii) § 60.107(f) § 60.107(g)
13-H-01C	EU	60J-low	HYDROGEN SULFIDE	40 CFR Part 60, Subpart J	§ 60.104(a)(1) § 60.104 § 60.104(a)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide in excess of 230 mg/dscm (0.10 gr/dscf). The combustion in a flare of process upset gases or fuel gas that is released to the flare as a result of relief valve leakage or other emergency malfunctions is exempt from this paragraph.	§ 60.105(a) [G]§ 60.105(a)(4)(iv) [G]§ 60.105(b) § 60.105(e) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a) [G]§ 60.105(a)(4)(iv) § 60.107(e)	[G]§ 60.105(b) § 60.105(e) § 60.107(f) § 60.107(g)
24-ST-01	EU	60J	SO2	40 CFR Part 60, Subpart J	§ 60.104(b)(1) § 60.104 § 60.104(b) § 60.104(c)	For each affected fluid catalytic cracking unit catalyst regenerator with an add-on control	§ 60.105(a) § 60.105(a)(10) § 60.105(a)(11) [G]§ 60.105(a)(12)	§ 60.105(a) § 60.105(a)(10) § 60.105(a)(11) [G]§ 60.105(a)(13)	§ 60.107(a) § 60.107(c) [G]§ 60.107(c)(1) § 60.107(c)(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.104(d)	device, reduce sulfur dioxide emissions to the atmosphere by 90 percent or maintain sulfur dioxide emissions to the atmosphere less than or equal to 50 ppm by volume, whichever is less stringent.	[G]§ 60.105(a)(13) [G]§ 60.105(a)(9) § 60.106(a) § 60.106(g) [G]§ 60.106(h) [G]§ 60.106(k) § 60.108(a) § 60.108(c) § 60.108(d) § 60.108(e)	[G]§ 60.105(a)(9) § 60.107(b) [G]§ 60.107(b)(1) § 60.107(b)(4)	[G]§ 60.107(c)(3) [G]§ 60.107(c)(4) § 60.107(d) § 60.107(e) § 60.107(f) § 60.107(g)
24-ST-01	EU	60J	CO	40 CFR Part 60, Subpart J	§ 60.103(a) § 60.103	No owner or operator shall discharge or cause the discharge into the atmosphere from any fluid catalytic cracking unit catalyst regenerator any gases that contain carbon monoxide (CO) in excess of 500 ppm by volume (dry basis).	§ 60.105(a) [G]§ 60.105(a)(2) § 60.105(c) § 60.105(e) § 60.105(e)(2) § 60.106(a) § 60.106(d)	§ 60.105(a) [G]§ 60.105(a)(2) § 60.105(c)	§ 60.105(e) § 60.105(e)(2) § 60.107(f) § 60.107(g)
24-ST-01	EU	60J	PM	40 CFR Part 60, Subpart J	§ 60.102(a)(1) § 60.102 § 60.102(a)	No owner or operator subject to the provisions of this subpart shall discharge or cause the discharge into the atmosphere from any fluid catalytic cracking unit catalyst regenerator particulate matter in excess of 1.0 kg/Mg (2.0 lb/ton) of coke burn-off in the catalyst regenerator.	§ 60.105(c) § 60.106(a) [G]§ 60.106(b) ** See CAM Summary	§ 60.105(c)	None
24-ST-01	EU	60J	PM (OPACITY)	40 CFR Part 60, Subpart J	§ 60.102(a)(2) § 60.102 § 60.102(a)	No owner or operator subject to the provisions of this subpart shall discharge or cause the discharge into the atmosphere from any	§ 60.105(a) § 60.105(a)(1) § 60.105(c) § 60.105(e) § 60.105(e)(1) § 60.106(a)	§ 60.105(a) § 60.105(a)(1) § 60.105(c)	§ 60.105(e) § 60.105(e)(1) § 60.107(f) § 60.107(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						fluid catalytic cracking unit catalyst regenerator gases exhibiting greater than 30 percent opacity, except for one six-minute average opacity reading in any one hour period.	[G]§ 60.106(b) ** See CAM Summary *See Alternative Requirement		
24-ST-01	EU	63UUU	CO	40 CFR Part 63, Subpart UUU	§ 63.1565(a)(1)-Table8.1 § 63.1565(a)(1) § 63.1565(a)(2) § 63.1565(a)(2)-Table9.1 § 63.1565(a)(3) § 63.1565(a)(4) § 63.1565(b)(3) § 63.1565(b)(4) § 63.1565(b)(4)-Table12.1 § 63.1565(c)(1) § 63.1565(c)(2) § 63.1570(a) § 63.1570(c) § 63.1570(d) § 63.1570(g) [G]§ 63.1571(e)	For each new and existing CCU subject to the NSPS for CO in 40 CFR §60.103 or electing to comply with the NSPS requirements (Option 1), CO emissions from the catalyst regenerator vent or CO boiler serving the CCU must not exceed 500 parts per million volume (ppmv) (dry basis).	§ 63.1565(b)(1) § 63.1565(b)(1)-Table10.1 § 63.1565(c)(1)-Table13.1 § 63.1565(c)(1)-Table14.1 [G]§ 63.1571(b) § 63.1572(a) § 63.1572(a)(1) § 63.1572(a)(1)-Table40.2 § 63.1572(a)(2) § 63.1572(a)(3) § 63.1572(a)(4) [G]§ 63.1572(d) [G]§ 63.1573(a)(2)	§ 63.1565(b)(1)-Table10.1 § 63.1570(c) [G]§ 63.1576(a) [G]§ 63.1576(b) § 63.1576(d) § 63.1576(e) § 63.1576(f) § 63.1576(g) § 63.1576(h) § 63.1576(i)	§ 63.1565(b)(5) § 63.1565(b)(6) § 63.1570(f) § 63.1571(a) [G]§ 63.1574(a) § 63.1574(d) § 63.1574(d)-Table42.1 § 63.1574(d)-Table42.2 § 63.1574(d)-Table42.3 § 63.1575(a) § 63.1575(a)-Table43.1 [G]§ 63.1575(b) [G]§ 63.1575(c) [G]§ 63.1575(e) [G]§ 63.1575(f) § 63.1575(g) [G]§ 63.1575(h) [G]§ 63.1575(i)
24-ST-01	EU	63UUU	PM	40 CFR Part 63, Subpart UUU	§ 63.1564(a)(1)-Table1.1 § 63.1564(a)(1) § 63.1564(a)(3) § 63.1564(a)(4) § 63.1564(b)(5) § 63.1564(b)(5)-Table5.1 § 63.1570(a) § 63.1570(c) § 63.1570(d) § 63.1570(g)	For each new or existing CCU subject to NSPS for PM in 40 CFR §60.102, PM emissions must not exceed 1.0 kg/1,000 kg (1.0 lb/1,000 lbs) of coke burn-off in the catalyst regenerator and, if applicable, the incremental rate of PM emissions must not exceed 43.0 g/GJ (0.10	§ 63.1564(c)(1)-Table6.1.a.i [G]§ 63.1572(d)	§ 63.1564(c)(2) § 63.1570(c) [G]§ 63.1576(a) § 63.1576(d) § 63.1576(e) § 63.1576(f) § 63.1576(g) § 63.1576(h) § 63.1576(i)	§ 63.1564(b)(6) § 63.1564(b)(7) § 63.1570(f) § 63.1573(f)(3) [G]§ 63.1574(a) § 63.1574(d) § 63.1574(d)-Table42.1 § 63.1574(d)-Table42.2 § 63.1574(d)-Table42.3 § 63.1575(a) § 63.1575(a)-Table43.1 [G]§ 63.1575(b)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 63.1573(f)(1) § 63.1573(f)(2)	lb/MMBtu) of heat input attributable to auxiliary or supplemental fired liquid or solid fossil fuel.			[G]§ 63.1575(c) [G]§ 63.1575(d) [G]§ 63.1575(f) § 63.1575(g) [G]§ 63.1575(h) [G]§ 63.1575(i)
24-ST-01	EU	63UUU	PM (OPACITY)	40 CFR Part 63, Subpart UUU	§ 63.1564(a)(1)-Table1.1 § 63.1564(a)(1) § 63.1564(a)(1) § 63.1564(a)(3) § 63.1564(a)(4) § 63.1564(b)(5) § 63.1564(b)(5)-Table5.1 § 63.1570(b) § 63.1570(c) § 63.1570(d) § 63.1570(g) [G]§ 63.1573(f)(1) § 63.1573(f)(2)	For each new or existing CCU subject to NSPS for PM in 40 CFR §60.102, opacity of emissions must not exceed 30%, except for one 6-minute average opacity reading in any 1-hour period.	§ 63.1564(c)(1)-Table6.1.a.i [G]§ 63.1572(d)	§ 63.1564(c)(2) § 63.1570(c) [G]§ 63.1576(a) [G]§ 63.1576(b) § 63.1576(d) § 63.1576(e) § 63.1576(f) § 63.1576(g) § 63.1576(h) § 63.1576(i)	§ 63.1564(b)(6) § 63.1564(b)(7) § 63.1570(f) § 63.1573(f)(3) [G]§ 63.1574(a) § 63.1574(d) § 63.1574(d)-Table42.1 § 63.1574(d)-Table42.2 § 63.1574(d)-Table42.3 § 63.1575(a) § 63.1575(a)-Table43.1 [G]§ 63.1575(b) [G]§ 63.1575(c) [G]§ 63.1575(d) [G]§ 63.1575(f) § 63.1575(g) [G]§ 63.1575(h) [G]§ 63.1575(i)
38-H-01	EU	60J	HYDROGEN SULFIDE	40 CFR Part 60, Subpart J	§ 60.104(a)(1) § 60.104 § 60.104(a)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide in excess of 230 mg/dscm (0.10 gr/dscf). The combustion in a flare of process upset gases or fuel gas that is released to the flare as a result of relief valve leakage or other emergency	§ 60.105(a) § 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.105(e) § 60.105(e)(3)(ii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a) § 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii)	§ 60.105(e) § 60.105(e)(3)(ii) § 60.107(f) § 60.107(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						malfunctions is exempt from this paragraph.			
38-H-01	EU	60J-low	HYDROGEN SULFIDE	40 CFR Part 60, Subpart J	§ 60.104(a)(1) § 60.104 § 60.104(a)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide in excess of 230 mg/dscm (0.10 gr/dscf). The combustion in a flare of process upset gases or fuel gas that is released to the flare as a result of relief valve leakage or other emergency malfunctions is exempt from this paragraph.	§ 60.105(a) [G]§ 60.105(a)(4)(iv) [G]§ 60.105(b) § 60.105(e) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a) [G]§ 60.105(a)(4)(iv) § 60.107(e)	[G]§ 60.105(b) § 60.105(e) § 60.107(f) § 60.107(g)
38-H-02	EU	60J	HYDROGEN SULFIDE	40 CFR Part 60, Subpart J	§ 60.104(a)(1) § 60.104 § 60.104(a)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide in excess of 230 mg/dscm (0.10 gr/dscf). The combustion in a flare of process upset gases or fuel gas that is released to the flare as a result of relief valve leakage or other emergency malfunctions is exempt from this paragraph.	§ 60.105(a) § 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.105(e) § 60.105(e)(3)(ii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a) § 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii)	§ 60.105(e) § 60.105(e)(3)(ii) § 60.107(f) § 60.107(g)
38-H-02	EU	60J-low	HYDROGEN SULFIDE	40 CFR Part 60, Subpart J	§ 60.104(a)(1) § 60.104 § 60.104(a)	No owner or operator subject to the provisions of this subpart shall	§ 60.105(a) [G]§ 60.105(a)(4)(iv) [G]§ 60.105(b)	§ 60.105(a) [G]§ 60.105(a)(4)(iv) § 60.107(e)	[G]§ 60.105(b) § 60.105(e) § 60.107(f)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide in excess of 230 mg/dscm (0.10 gr/dscf). The combustion in a flare of process upset gases or fuel gas that is released to the flare as a result of relief valve leakage or other emergency malfunctions is exempt from this paragraph.	§ 60.105(e) § 60.106(a) [G]§ 60.106(e)(1)		§ 60.107(g)
41-H-07	EU	60J	HYDROGEN SULFIDE	40 CFR Part 60, Subpart J	§ 60.104(a)(1) § 60.104 § 60.104(a)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide in excess of 230 mg/dscm (0.10 gr/dscf). The combustion in a flare of process upset gases or fuel gas that is released to the flare as a result of relief valve leakage or other emergency malfunctions is exempt from this paragraph.	§ 60.105(a) § 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.105(e) § 60.105(e)(3)(ii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a) § 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii)	§ 60.105(e) § 60.105(e)(3)(ii) § 60.107(f) § 60.107(g)
46-H-01	EU	60J	HYDROGEN SULFIDE	40 CFR Part 60, Subpart J	§ 60.104(a)(1) § 60.104 § 60.104(a)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide in excess of 230 mg/dscm	§ 60.105(a) § 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.105(e) § 60.105(e)(3)(ii) § 60.106(a)	§ 60.105(a) § 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii)	§ 60.105(e) § 60.105(e)(3)(ii) § 60.107(f) § 60.107(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						(0.10 gr/dscf). The combustion in a flare of process upset gases or fuel gas that is released to the flare as a result of relief valve leakage or other emergency malfunctions is exempt from this paragraph.	[G]§ 60.106(e)(1)		
48-H-01	EU	60J	HYDROGEN SULFIDE	40 CFR Part 60, Subpart J	§ 60.104(a)(1) § 60.104 § 60.104(a)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide in excess of 230 mg/dscm (0.10 gr/dscf). The combustion in a flare of process upset gases or fuel gas that is released to the flare as a result of relief valve leakage or other emergency malfunctions is exempt from this paragraph.	§ 60.105(a) § 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.105(e) § 60.105(e)(3)(ii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a) § 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii)	§ 60.105(e) § 60.105(e)(3)(ii) § 60.107(f) § 60.107(g)
48-H-01	EU	60J-AMP	HYDROGEN SULFIDE	40 CFR Part 60, Subpart J	§ 60.104(a)(1) § 60.104 § 60.104(a)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide in excess of 230 mg/dscm (0.10 gr/dscf). The combustion in a flare of process upset gases or fuel gas that is released to the flare as a result of	§ 60.105(a) [G]§ 60.105(a)(3) § 60.105(e) § 60.105(e)(3)(i) § 60.106(a) [G]§ 60.106(e)(1) § 60.106(e)(2) *See Alternative Requirement	§ 60.105(a) [G]§ 60.105(a)(3)	§ 60.105(e) § 60.105(e)(3)(i) § 60.107(f) § 60.107(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						relief valve leakage or other emergency malfunctions is exempt from this paragraph.			
49CRU	EU	63UUU	112(B) HAPS	40 CFR Part 63, Subpart UUU	§ 63.1569(a)(1)(i)-Table36.1 § 63.1569(a)(1) § 63.1569(a)(3) § 63.1569(b)(2) § 63.1569(b)(2)-Table38.1.a § 63.1569(c)(1) § 63.1570(a) § 63.1570(c) § 63.1570(d) § 63.1570(g)	If you elect to install an automated system (Option 1), you must install and operate a device (including a flow indicator, level recorder, or electronic valve position monitor) to demonstrate, either continuously or at least every hour, whether flow is present in the bypass line. Install the device at or near as practical to the entrance to any bypass line that could divert the vent stream away from the control device to the atmosphere.	§ 63.1569(b)(1) § 63.1569(b)(1)-Table37.1 § 63.1569(c)(1)-Table39.1 § 63.1571(a) § 63.1571(a)(1) [G]§ 63.1571(b)	§ 63.1569(b)(1)-Table37.1 § 63.1569(c)(1)-Table39.1 § 63.1569(c)(1)-Table39.5 § 63.1570(c) [G]§ 63.1576(a) § 63.1576(d) § 63.1576(e) § 63.1576(f) § 63.1576(g) § 63.1576(h) § 63.1576(i)	§ 63.1569(b)(3) § 63.1569(b)(4) § 63.1569(c)(1)-Table39.5 § 63.1570(f) § 63.1571(a) [G]§ 63.1574(a) § 63.1574(d) § 63.1574(d)-Table42.1 § 63.1574(d)-Table42.2 § 63.1574(d)-Table42.3 § 63.1575(a) § 63.1575(a)-Table43.1 [G]§ 63.1575(b) [G]§ 63.1575(c) [G]§ 63.1575(d) [G]§ 63.1575(f) § 63.1575(g) [G]§ 63.1575(h)
49CRU	EU	63UUU	HYDROGEN CHLORIDE	40 CFR Part 63, Subpart UUU	§ 63.1567(a)(1)-Table22.2 § 63.1567(a)(1) § 63.1567(a)(1)(i) § 63.1567(a)(1)(ii) § 63.1567(a)(2) § 63.1567(a)(2)-Table23.1 § 63.1567(a)(3) § 63.1567(b)(3) § 63.1567(b)(4) § 63.1567(b)(4)(i) § 63.1567(b)(5) § 63.1567(b)(5)-Table26.2	For each existing cyclic or continuous CRU, you must reduce uncontrolled emissions of HCl by 97 percent by weight or to a concentration of 10 ppmv (dry basis), corrected to 3% oxygen.	§ 63.1567(b)(1) § 63.1567(b)(1)-Table24.1 § 63.1567(b)(2) § 63.1567(b)(2)-Table25.1.a.(1) § 63.1567(b)(2)-Table25.1.a.(2) § 63.1567(b)(2)-Table25.1.b § 63.1567(b)(2)-Table25.1.c § 63.1567(b)(2)-Table25.1.d § 63.1567(b)(2)-	§ 63.1567(b)(1)-Table24.1 § 63.1567(b)(2)-Table25.2.a.i § 63.1567(b)(2)-Table25.2.b.i § 63.1567(c)(1)-Table28.1.a § 63.1567(c)(1)-Table28.1.b § 63.1567(c)(2) § 63.1570(c) § 63.1572(c)(4) § 63.1572(c)(5) § 63.1573(b)(1)	§ 63.1567(b)(6) § 63.1567(b)(7) § 63.1570(f) § 63.1571(a) § 63.1571(d)(4) § 63.1571(d)(4) [G]§ 63.1574(a) § 63.1574(d) § 63.1574(d)-Table42.1 § 63.1574(d)-Table42.2 § 63.1574(d)-Table42.3 § 63.1575(a) § 63.1575(a)-Table43.1 [G]§ 63.1575(b) [G]§ 63.1575(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.1567(c)(1) § 63.1570(a) § 63.1570(c) § 63.1570(d) § 63.1570(g) § 63.1571(d)(4) [G]§ 63.1571(e)		Table25.1.e.(1) § 63.1567(b)(2)-Table25.1.e.(2) § 63.1567(b)(2)-Table25.1.e.(3) § 63.1567(b)(2)-Table25.1.e.(4) § 63.1567(b)(2)-Table25.2.a.i § 63.1567(b)(2)-Table25.2.a.ii § 63.1567(b)(2)-Table25.2.b.i § 63.1567(b)(2)-Table25.2.b.ii § 63.1567(c)(1)-Table27.2 § 63.1567(c)(1)-Table28.1.a § 63.1567(c)(1)-Table28.1.b § 63.1571(a) § 63.1571(a)(1) [G]§ 63.1571(b) § 63.1572(c) § 63.1572(c)(1) § 63.1572(c)(1)-Table41.1 § 63.1572(c)(2) § 63.1572(c)(3) § 63.1572(c)(4) [G]§ 63.1572(d) [G]§ 63.1573(a)(1) § 63.1573(b)(1)	[G]§ 63.1576(a) § 63.1576(d) § 63.1576(e) § 63.1576(f) § 63.1576(g) § 63.1576(h) § 63.1576(i)	[G]§ 63.1575(d) [G]§ 63.1575(f) § 63.1575(g) [G]§ 63.1575(h)
49-H-91	EU	60J	HYDROGEN SULFIDE	40 CFR Part 60, Subpart J	§ 60.104(a)(1) § 60.104 § 60.104(a)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains	§ 60.105(a) § 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.105(e)	§ 60.105(a) § 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii)	§ 60.105(e) § 60.105(e)(3)(ii) § 60.107(f) § 60.107(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						hydrogen sulfide in excess of 230 mg/dscm (0.10 gr/dscf). The combustion in a flare of process upset gases or fuel gas that is released to the flare as a result of relief valve leakage or other emergency malfunctions is exempt from this paragraph.	§ 60.105(e)(3)(ii) § 60.106(a) [G]§ 60.106(e)(1)		
52-H-01	EU	60J	HYDROGEN SULFIDE	40 CFR Part 60, Subpart J	§ 60.104(a)(1) § 60.104 § 60.104(a)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide in excess of 230 mg/dscm (0.10 gr/dscf). The combustion in a flare of process upset gases or fuel gas that is released to the flare as a result of relief valve leakage or other emergency malfunctions is exempt from this paragraph.	§ 60.105(a) § 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.105(e) § 60.105(e)(3)(ii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a) § 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii)	§ 60.105(e) § 60.105(e)(3)(ii) § 60.107(f) § 60.107(g)
GF-1	EU	60J	HYDROGEN SULFIDE	40 CFR Part 60, Subpart J	§ 60.104(a)(1) § 60.104 § 60.104(a)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide in excess of 230 mg/dscm (0.10 gr/dscf). The combustion in a flare of process upset gases or	§ 60.105(a) § 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) [G]§ 60.105(a)(4)(iv) [G]§ 60.105(b) § 60.105(e) § 60.105(e)(3)(ii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a) § 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) [G]§ 60.105(a)(4)(iv) § 60.107(e)	[G]§ 60.105(b) § 60.105(e) § 60.105(e)(3)(ii) § 60.107(f) § 60.107(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						fuel gas that is released to the flare as a result of relief valve leakage or other emergency malfunctions is exempt from this paragraph.			
GRP-49HTR	EU	60J	HYDROGEN SULFIDE	40 CFR Part 60, Subpart J	§ 60.104(a)(1) § 60.104 § 60.104(a)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide in excess of 230 mg/dscm (0.10 gr/dscf). The combustion in a flare of process upset gases or fuel gas that is released to the flare as a result of relief valve leakage or other emergency malfunctions is exempt from this paragraph.	§ 60.105(a) § 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.105(e) § 60.105(e)(3)(ii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a) § 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii)	§ 60.105(e) § 60.105(e)(3)(ii) § 60.107(f) § 60.107(g)
GRP-49HTR	EU	60J-low	HYDROGEN SULFIDE	40 CFR Part 60, Subpart J	§ 60.104(a)(1) § 60.104 § 60.104(a)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide in excess of 230 mg/dscm (0.10 gr/dscf). The combustion in a flare of process upset gases or fuel gas that is released to the flare as a result of relief valve leakage or other emergency malfunctions is exempt	§ 60.105(a) [G]§ 60.105(a)(4)(iv) [G]§ 60.105(b) § 60.105(e) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a) [G]§ 60.105(a)(4)(iv) § 60.107(e)	[G]§ 60.105(b) § 60.105(e) § 60.107(f) § 60.107(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						from this paragraph.			
GRP-BLR-DB	EU	60J	HYDROGEN SULFIDE	40 CFR Part 60, Subpart J	§ 60.104(a)(1) § 60.104 § 60.104(a)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide in excess of 230 mg/dscm (0.10 gr/dscf). The combustion in a flare of process upset gases or fuel gas that is released to the flare as a result of relief valve leakage or other emergency malfunctions is exempt from this paragraph.	§ 60.105(a) § 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.105(e) § 60.105(e)(3)(ii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a) § 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii)	§ 60.105(e) § 60.105(e)(3)(ii) § 60.107(f) § 60.107(g)
GRP-HTR	EU	60J	HYDROGEN SULFIDE	40 CFR Part 60, Subpart J	§ 60.104(a)(1) § 60.104 § 60.104(a)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide in excess of 230 mg/dscm (0.10 gr/dscf). The combustion in a flare of process upset gases or fuel gas that is released to the flare as a result of relief valve leakage or other emergency malfunctions is exempt from this paragraph.	§ 60.105(a) § 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.105(e) § 60.105(e)(3)(ii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a) § 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii)	§ 60.105(e) § 60.105(e)(3)(ii) § 60.107(f) § 60.107(g)
GRP-HTRJ	EU	60J	HYDROGEN SULFIDE	40 CFR Part 60, Subpart J	§ 60.104(a)(1) § 60.104 § 60.104(a)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas	§ 60.105(a) § 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii)	§ 60.105(a) § 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii)	§ 60.105(e) § 60.105(e)(3)(ii) § 60.107(f) § 60.107(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						combustion device any fuel gas that contains hydrogen sulfide in excess of 230 mg/dscm (0.10 gr/dscf). The combustion in a flare of process upset gases or fuel gas that is released to the flare as a result of relief valve leakage or other emergency malfunctions is exempt from this paragraph.	§ 60.105(a)(4)(iii) § 60.105(e) § 60.105(e)(3)(ii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4)(iii)	
GRP-HTRJ	EU	60J-AMP	HYDROGEN SULFIDE	40 CFR Part 60, Subpart J	§ 60.104(a)(1) § 60.104 § 60.104(a)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide in excess of 230 mg/dscm (0.10 gr/dscf). The combustion in a flare of process upset gases or fuel gas that is released to the flare as a result of relief valve leakage or other emergency malfunctions is exempt from this paragraph.	§ 60.105(a) [G]§ 60.105(a)(3) § 60.105(e) § 60.105(e)(3)(i) § 60.106(a) [G]§ 60.106(e)(1) § 60.106(e)(2) *See Alternative Requirement	§ 60.105(a) [G]§ 60.105(a)(3)	§ 60.105(e) § 60.105(e)(3)(i) § 60.107(f) § 60.107(g)
MFL-1	EU	60J	HYDROGEN SULFIDE	40 CFR Part 60, Subpart J	§ 60.104(a)(1) § 60.104 § 60.104(a)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide in excess of 230 mg/dscm (0.10 gr/dscf). The	§ 60.105(a) § 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) [G]§ 60.105(a)(4)(iv) [G]§ 60.105(b) § 60.105(e) § 60.105(e)(3)(ii)	§ 60.105(a) § 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) [G]§ 60.105(a)(4)(iv) § 60.107(e)	[G]§ 60.105(b) § 60.105(e) § 60.105(e)(3)(ii) § 60.107(f) § 60.107(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						combustion in a flare of process upset gases or fuel gas that is released to the flare as a result of relief valve leakage or other emergency malfunctions is exempt from this paragraph.	§ 60.106(a) [G]§ 60.106(e)(1)		
MTBE FL-2	EU	60J	HYDROGEN SULFIDE	40 CFR Part 60, Subpart J	§ 60.104(a)(1) § 60.104 § 60.104(a)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide in excess of 230 mg/dscm (0.10 gr/dscf). The combustion in a flare of process upset gases or fuel gas that is released to the flare as a result of relief valve leakage or other emergency malfunctions is exempt from this paragraph.	§ 60.105(a) § 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) [G]§ 60.105(a)(4)(iv) [G]§ 60.105(b) § 60.105(e) § 60.105(e)(3)(ii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a) § 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) [G]§ 60.105(a)(4)(iv) § 60.107(e)	[G]§ 60.105(b) § 60.105(e) § 60.105(e)(3)(ii) § 60.107(f) § 60.107(g)
SRU	PRO	60J	SO2	40 CFR Part 60, Subpart J	§ 60.104(a)(2)(i) § 60.104 § 60.104(a) § 60.104(a)(2)	No owner or operator subject to the provisions of this subpart shall discharge or cause the discharge from any Claus sulfur recovery plant with an oxidation control system or a reduction control system followed by incineration any gases containing in excess of 250 ppm by volume (dry basis) of sulfur dioxide	§ 60.105(a) [G]§ 60.105(a)(5) § 60.105(e) § 60.105(e)(4)(i) § 60.106(a) [G]§ 60.106(f) ** See CAM Summary *See Alternative Requirement	§ 60.105(a) [G]§ 60.105(a)(5)	§ 60.105(e) § 60.105(e)(4)(i) § 60.107(f) § 60.107(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						at zero percent excess air into the atmosphere.			
SRU	EU	63UUU	112(B) HAPS	40 CFR Part 63, Subpart UUU	§ 63.1569(a)(1)(i)-Table36.1 § 63.1569(a)(1) § 63.1569(a)(3) § 63.1569(b)(2) § 63.1569(b)(2)-Table38.1.a § 63.1569(c)(1) § 63.1570(a) § 63.1570(c) § 63.1570(d) § 63.1570(g)	If you elect to install an automated system (Option 1), you must install and operate a device (including a flow indicator, level recorder, or electronic valve position monitor) to demonstrate, either continuously or at least every hour, whether flow is present in the bypass line. Install the device at or near as practical to the entrance to any bypass line that could divert the vent stream away from the control device to the atmosphere.	§ 63.1569(b)(1) § 63.1569(b)(1)-Table37.1 § 63.1569(c)(1)-Table39.1 § 63.1571(a) § 63.1571(a)(1) [G]§ 63.1571(b)	§ 63.1569(b)(1)-Table37.1 § 63.1569(c)(1)-Table39.1 § 63.1569(c)(1)-Table39.5 § 63.1570(c) [G]§ 63.1576(a) § 63.1576(d) § 63.1576(e) § 63.1576(f) § 63.1576(g) § 63.1576(h) § 63.1576(i)	§ 63.1569(b)(3) § 63.1569(b)(4) § 63.1569(c)(1)-Table39.5 § 63.1570(f) § 63.1571(a) [G]§ 63.1574(a) § 63.1574(d) § 63.1574(d)-Table42.1 § 63.1574(d)-Table42.2 § 63.1574(d)-Table42.3 § 63.1575(a) § 63.1575(a)-Table43.1 [G]§ 63.1575(b) [G]§ 63.1575(c) [G]§ 63.1575(d) [G]§ 63.1575(f) § 63.1575(g) [G]§ 63.1575(h)
SRU	EU	63UUU	SO_2	40 CFR Part 63, Subpart UUU	§ 63.1568(a)(1)-Table29.1.a § 63.1568(a)(1) § 63.1568(a)(2) § 63.1568(a)(2)-Table30.1 § 63.1568(a)(3) § 63.1568(b)(3) § 63.1568(b)(4) § 63.1568(b)(5) § 63.1568(b)(5)-Table33.1.a § 63.1568(c)(1) § 63.1568(c)(1)-Table35.1 § 63.1568(c)(2) § 63.1570(a)	For each new or existing Claus SRU part of a sulfur recovery plant of 20 long tons per day or more and subject to NSPS for sulfur oxides in 40 CFR §60.104(a)(2), you must meet the emission limit for each process vent of 250ppmv (dry basis) of sulfur dioxide (SO2) at zero percent excess air if you use an oxidation or reduction control system followed by incineration.	§ 63.1568(b)(1) § 63.1568(b)(1)-Table31.1.a § 63.1568(c)(1)-Table34.1.a § 63.1572(a)(1)-Table40.4 § 63.1572(a)(1)-Table40.8 § 63.1572(a)(2) § 63.1572(a)(3) § 63.1572(a)(4) [G]§ 63.1572(d)	§ 63.1568(b)(1)-Table31.1.a § 63.1568(c)(1)-Table34.1.a § 63.1570(c) [G]§ 63.1576(a) [G]§ 63.1576(b) § 63.1576(d) § 63.1576(e) § 63.1576(f) § 63.1576(g) § 63.1576(h) § 63.1576(i)	§ 63.1568(b)(6) § 63.1568(b)(7) § 63.1570(f) § 63.1571(a) [G]§ 63.1574(a) § 63.1574(d) § 63.1574(d)-Table42.1 § 63.1574(d)-Table42.2 § 63.1574(d)-Table42.3 § 63.1575(a) § 63.1575(a)-Table43.1 [G]§ 63.1575(b) [G]§ 63.1575(c) [G]§ 63.1575(e) [G]§ 63.1575(f) § 63.1575(g) [G]§ 63.1575(h)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.1570(c) § 63.1570(d) § 63.1570(g)				
SRU3	PRO	60J	SO2	40 CFR Part 60, Subpart J	§ 60.104(a)(2)(i) § 60.104 § 60.104(a) § 60.104(a)(2)	No owner or operator subject to the provisions of this subpart shall discharge or cause the discharge from any Claus sulfur recovery plant with an oxidation control system or a reduction control system followed by incineration any gases containing in excess of 250 ppm by volume (dry basis) of sulfur dioxide at zero percent excess air into the atmosphere.	§ 60.105(a) [G]§ 60.105(a)(5) § 60.105(e) § 60.105(e)(4)(i) § 60.106(a) [G]§ 60.106(f) ** See CAM Summary *See Alternative Requirement	§ 60.105(a) [G]§ 60.105(a)(5)	§ 60.105(e) § 60.105(e)(4)(i) § 60.107(f) § 60.107(g)
SRU3	EU	63UUU	112(B) HAPS	40 CFR Part 63, Subpart UUU	§ 63.1569(a)(1)(i)-Table36.1 § 63.1569(a)(1) § 63.1569(a)(3) § 63.1569(b)(2) § 63.1569(b)(2)-Table38.1.a § 63.1569(c)(1) § 63.1570(a) § 63.1570(c) § 63.1570(d) § 63.1570(g)	If you elect to install an automated system (Option 1), you must install and operate a device (including a flow indicator, level recorder, or electronic valve position monitor) to demonstrate, either continuously or at least every hour, whether flow is present in the bypass line. Install the device at or near as practical to the entrance to any bypass line that could divert the vent stream away from the control device to the atmosphere.	§ 63.1569(b)(1) § 63.1569(b)(1)-Table37.1 § 63.1569(c)(1)-Table39.1 § 63.1571(a) § 63.1571(a)(1) [G]§ 63.1571(b)	§ 63.1569(b)(1)-Table37.1 § 63.1569(c)(1)-Table39.1 § 63.1569(c)(1)-Table39.5 § 63.1570(c) [G]§ 63.1576(a) § 63.1576(d) § 63.1576(e) § 63.1576(f) § 63.1576(g) § 63.1576(h) § 63.1576(i)	§ 63.1569(b)(3) § 63.1569(b)(4) § 63.1569(c)(1)-Table39.5 § 63.1570(f) § 63.1571(a) [G]§ 63.1574(a) § 63.1574(d) § 63.1574(d)-Table42.1 § 63.1574(d)-Table42.2 § 63.1574(d)-Table42.3 § 63.1575(a) § 63.1575(a)-Table43.1 [G]§ 63.1575(b) [G]§ 63.1575(c) [G]§ 63.1575(d) [G]§ 63.1575(f) § 63.1575(g) [G]§ 63.1575(h)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
SRU3	EU	63UUU	SO_2	40 CFR Part 63, Subpart UUU	§ 63.1568(a)(1)-Table29.1.a § 63.1568(a)(1) § 63.1568(a)(2) § 63.1568(a)(2)-Table30.1 § 63.1568(a)(3) § 63.1568(b)(3) § 63.1568(b)(4) § 63.1568(b)(5) § 63.1568(b)(5)-Table33.1.a § 63.1568(c)(1) § 63.1568(c)(1)-Table35.1 § 63.1568(c)(2) § 63.1570(a) § 63.1570(c) § 63.1570(d) § 63.1570(g)	For each new or existing Claus SRU part of a sulfur recovery plant of 20 long tons per day or more and subject to NSPS for sulfur oxides in 40 CFR §60.104(a)(2), you must meet the emission limit for each process vent of 250ppmv (dry basis) of sulfur dioxide (SO2) at zero percent excess air if you use an oxidation or reduction control system followed by incineration.	§ 63.1568(b)(1) § 63.1568(b)(1)-Table31.1.a § 63.1568(c)(1)-Table34.1.a § 63.1572(a)(1)-Table40.4 § 63.1572(a)(1)-Table40.8 § 63.1572(a)(2) § 63.1572(a)(3) § 63.1572(a)(4) [G]§ 63.1572(d)	§ 63.1568(b)(1)-Table31.1.a § 63.1568(c)(1)-Table34.1.a § 63.1570(c) [G]§ 63.1576(a) [G]§ 63.1576(b) § 63.1576(d) § 63.1576(e) § 63.1576(f) § 63.1576(g) § 63.1576(h) § 63.1576(i)	§ 63.1568(b)(6) § 63.1568(b)(7) § 63.1570(f) § 63.1571(a) [G]§ 63.1574(a) § 63.1574(d) § 63.1574(d)-Table42.1 § 63.1574(d)-Table42.2 § 63.1574(d)-Table42.3 § 63.1575(a) § 63.1575(a)-Table43.1 [G]§ 63.1575(b) [G]§ 63.1575(c) [G]§ 63.1575(e) [G]§ 63.1575(f) § 63.1575(g) [G]§ 63.1575(h)
TRUCKCOMB	EU	60J	HYDROGEN SULFIDE	40 CFR Part 60, Subpart J	§ 60.104(a)(1) § 60.104 § 60.104(a)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide in excess of 230 mg/dscm (0.10 gr/dscf). The combustion in a flare of process upset gases or fuel gas that is released to the flare as a result of relief valve leakage or other emergency malfunctions is exempt from this paragraph.	§ 60.105(a) [G]§ 60.105(a)(4)(iv) [G]§ 60.105(b) § 60.105(e) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a) [G]§ 60.105(a)(4)(iv) § 60.107(e)	[G]§ 60.105(b) § 60.105(e) § 60.107(f) § 60.107(g)
GF-1	EU	R1111	OPACITY	30 TAC Chapter 111, Visible	§ 111.111(a)(4)(A)	Visible emissions from a process gas flare shall	§ 111.111(a)(4)(A)(i) § 111.111(a)(4)(A)(ii)	§ 111.111(a)(4)(A)(ii)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Emissions		not be permitted for more than five minutes in any two-hour period, except for emission event emissions as provided in §101.222(b).			
GF-1	CD	60A	OPACITY	40 CFR Part 60, Subpart A	§ 60.18(b) § 60.18(c)(1) § 60.18(c)(2) § 60.18(c)(3)(ii) § 60.18(c)(4)(iii) § 60.18(c)(6) § 60.18(e)	Flares shall comply with paragraphs (c)-(f) of § 60.18.	§ 60.18(d) § 60.18(f)(1) § 60.18(f)(2) § 60.18(f)(3) § 60.18(f)(4) § 60.18(f)(5)	None	None
GF-1	CD	63A	OPACITY	40 CFR Part 63, Subpart A	§ 63.11(b)(4) § 63.11(b)(1) § 63.11(b)(2) § 63.11(b)(3) § 63.11(b)(5) § 63.11(b)(6)(ii) § 63.11(b)(7)(iii)	Flares shall be designed and operated with no visible emissions, except for periods of a total of 5 minutes or less during any 2 consecutive hrs. Test Method 22 in App. A of part 60 of this chapter shall be used.	§ 63.11(b)(4) § 63.11(b)(5) § 63.11(b)(7)(i)	None	None
MFL-1	EU	R1111	OPACITY	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(4)(A)	Visible emissions from a process gas flare shall not be permitted for more than five minutes in any two-hour period, except for emission event emissions as provided in §101.222(b).	§ 111.111(a)(4)(A)(i) § 111.111(a)(4)(A)(ii)	§ 111.111(a)(4)(A)(ii)	None
MFL-1	CD	60A	OPACITY	40 CFR Part 60, Subpart A	§ 60.18(b) § 60.18(c)(1) § 60.18(c)(2) § 60.18(c)(3)(ii) § 60.18(c)(4)(iii) § 60.18(c)(6) § 60.18(e)	Flares shall comply with paragraphs (c)-(f) of § 60.18.	§ 60.18(d) § 60.18(f)(1) § 60.18(f)(2) § 60.18(f)(3) § 60.18(f)(4) § 60.18(f)(5)	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
MFL-1	CD	63A	OPACITY	40 CFR Part 63, Subpart A	§ 63.11(b)(4) § 63.11(b)(1) § 63.11(b)(2) § 63.11(b)(3) § 63.11(b)(5) § 63.11(b)(6)(ii) § 63.11(b)(7)(iii)	Flares shall be designed and operated with no visible emissions, except for periods of a total of 5 minutes or less during any 2 consecutive hrs. Test Method 22 in App. A of part 60 of this chapter shall be used.	§ 63.11(b)(4) § 63.11(b)(5) § 63.11(b)(7)(i)	None	None
MFL-1B	EP	R1111	OPACITY	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(B) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall not exceed an opacity of 20% averaged over a six minute period for any source on which construction was begun after January 31, 1972.	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None
MFL-1B	CD	63A	OPACITY	40 CFR Part 63, Subpart A	§ 63.11(b)(4) § 63.11(b)(1) § 63.11(b)(2) § 63.11(b)(3) § 63.11(b)(5) § 63.11(b)(6)(i)(A) § 63.11(b)(6)(i)(B) § 63.11(b)(7)(i)	Flares shall be designed and operated with no visible emissions, except for periods of a total of 5 minutes or less during any 2 consecutive hrs. Test Method 22 in App. A of part 60 of this chapter shall be used.	§ 63.11(b)(4) § 63.11(b)(5) § 63.11(b)(7)(i)	None	None
MTBE FL-2	EU	R1111	OPACITY	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(4)(A)	Visible emissions from a process gas flare shall not be permitted for more than five minutes in any two-hour period, except for emission event emissions as provided in §101.222(b).	§ 111.111(a)(4)(A)(i) § 111.111(a)(4)(A)(ii)	§ 111.111(a)(4)(A)(ii)	None
MTBE FL-2	CD	60A	OPACITY	40 CFR Part 60, Subpart A	§ 60.18(b) § 60.18(c)(1) § 60.18(c)(2) § 60.18(c)(3)(ii)	Flares shall comply with paragraphs (c)-(f) of § 60.18.	§ 60.18(d) § 60.18(f)(1) § 60.18(f)(2) § 60.18(f)(3)	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.18(c)(4)(ii) § 60.18(c)(6) § 60.18(e)		§ 60.18(f)(4)		
MTBE FL-2	CD	63A	OPACITY	40 CFR Part 63, Subpart A	§ 63.11(b)(4) § 63.11(b)(1) § 63.11(b)(2) § 63.11(b)(3) § 63.11(b)(5) § 63.11(b)(6)(ii) § 63.11(b)(7)(iii)	Flares shall be designed and operated with no visible emissions, except for periods of a total of 5 minutes or less during any 2 consecutive hrs. Test Method 22 in App. A of part 60 of this chapter shall be used.	§ 63.11(b)(4) § 63.11(b)(5) § 63.11(b)(7)(i)	None	None
30B04F	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.322(5)	No valve (gaseous service) may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.324(2) § 115.324(4) § 115.324(5) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	§ 115.326(1) [G]§ 115.326(2) § 115.326(3) § 115.326(4)	§ 115.326(1) § 115.327(4)
30B04F	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.327(1)	Valves of nominal size of 2" (5 cm) or less are exempt, provided allowable emissions from sources affected by this division after controls are applied with exemptions will not exceed by more than 5.0% such allowable emissions with no exemptions.	None	None	§ 115.327(1)(A) § 115.327(1)(B) § 115.327(1)(C)
30B04F	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No pump seal, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						days after the leak is found, except as provided in §115.322(2).			
30B04F	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No pump seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(A) § 115.324(3) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
30B04F	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(5)	No valve (gaseous service), as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
30B04F	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.322(5)	No valve (gaseous service) may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
30B04F	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No valve in liquid service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
30B04F	EU	R5322ALL	VOC	30 TAC Chapter	§ 115.322(1)	No valve in liquid	§ 115.324	[G]§ 115.326(1)	[G]§ 115.324(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				115, Fugitives Pet Ref B Counties	§ 115.322(2) § 115.322(3) § 115.322(4)	service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324(1) § 115.324(1)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
30B04F	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No process drain, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
30B04F	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No process drain may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(C) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
30B04F	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3) § 115.327(6)	No compressor seal, as described in § 115.327(3), (5) or (6), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
30B04F	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No compressor seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as	§ 115.324 § 115.324(2) § 115.324(2)(A) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						provided in §115.322(2).			
30B04F	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No elevated valve, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
30B04F	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No elevated valve may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(D) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
30B04F	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(5)	No pressure relief valve in gaseous service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
30B04F	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(5)	No pressure relief valve in gaseous service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(C) § 115.324(4) § 115.324(5) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
30B04F	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives	§ 115.322(1) § 115.322(2)	No connector, as described in § 115.327(3)	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Pet Ref B Counties	§ 115.322(3) § 115.327(3)	or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).			
54F-MTBE	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.322(5)	No valve (gaseous service) may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.324(2) § 115.324(4) § 115.324(5) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	§ 115.326(1) [G]§ 115.326(2) § 115.326(3) § 115.326(4)	§ 115.326(1) § 115.327(4)
54F-MTBE	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.327(1)	Valves of nominal size of 2" (5 cm) or less are exempt, provided allowable emissions from sources affected by this division after controls are applied with exemptions will not exceed by more than 5.0% such allowable emissions with no exemptions.	None	None	§ 115.327(1)(A) § 115.327(1)(B) § 115.327(1)(C)
54F-MTBE	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No pump seal, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
54F-MTBE	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives	§ 115.322(1) § 115.322(2)	No pump seal may be allowed to have a VOC	§ 115.324 § 115.324(1)	[G]§ 115.326(1) [G]§ 115.326(2)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Pet Ref B Counties	§ 115.322(3)	leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324(1)(A) § 115.324(3) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(3) § 115.326(5)	
54F-MTBE	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(5)	No valve (gaseous service), as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
54F-MTBE	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.322(5)	No valve (gaseous service) may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
54F-MTBE	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No valve in liquid service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
54F-MTBE	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No valve in liquid service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as	§ 115.324 § 115.324(1) § 115.324(1)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						provided in §115.322(2).			
54F-MTBE	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No process drain, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
54F-MTBE	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No process drain may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(C) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
54F-MTBE	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3) § 115.327(6)	No compressor seal, as described in § 115.327(3), (5) or (6), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
54F-MTBE	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No compressor seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(A) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
54F-MTBE	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No elevated valve, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.327(3) § 115.327(5)	defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).			
54F-MTBE	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No elevated valve may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(D) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
54F-MTBE	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(5)	No pressure relief valve in gaseous service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
54F-MTBE	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(5)	No pressure relief valve in gaseous service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(C) § 115.324(4) § 115.324(5) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
54F-MTBE	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No connector, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						provided in §115.322(2).			
54F-MTBE	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(d)	Comply with the requirements as stated in §60.482-1(d) for equipment in vacuum service.	None	§ 60.486(e) § 60.486(e)(1) § 60.486(e)(5)	None
54F-MTBE	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-2 [G]§ 60.482-9	Comply with the requirements as stated in §60.482-2 for pumps in light-liquid service.	[G]§ 60.482-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d) § 60.593(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
54F-MTBE	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) § 60.482-3(f) § 60.482-3(g)(1) § 60.482-3(g)(2) [G]§ 60.482-3(i) § 60.482-3(j) [G]§ 60.482-9 § 60.593(c)	Comply with the requirements as stated in §60.482-3 for reciprocating compressors that become subject under §60.14 and §60.15.	§ 60.482-3(f) § 60.482-3(g)(1) § 60.482-3(g)(2) [G]§ 60.482-3(i) § 60.482-3(j) § 60.485(a) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
54F-MTBE	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-3 [G]§ 60.482-9	Comply with the requirements as stated in §60.482-3 for compressors.	[G]§ 60.482-3 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
54F-MTBE	EU	60GGGALL	VOC	40 CFR Part 60,	§ 60.592(a)	Comply with the	[G]§ 60.482-4	[G]§ 60.486(a)	§ 60.487(a)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Subpart GGG	§ 60.482-1(a) § 60.482-1(b) [G]§ 60.482-4 [G]§ 60.482-9	requirements in as stated in §60.482-4 for pressure relief devices in gas/vapor service.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	§ 60.486(e) § 60.486(e)(1) § 60.486(e)(3) [G]§ 60.486(e)(4) § 60.486(j) § 60.592(e)	[G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
54F-MTBE	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-5 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-5 for sampling connection systems.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
54F-MTBE	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-6 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-6 for open-ended valves and lines.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
54F-MTBE	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-7 [G]§ 60.482-9 [G]§ 60.483-1 [G]§ 60.483-2 § 60.592(b)	Comply with the requirements in as stated in §60.482-7 for valves in gas/vapor or light-liquid service.	[G]§ 60.482-7 [G]§ 60.483-1 [G]§ 60.483-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d) § 60.593(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) [G]§ 60.486(g) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(d) § 60.487(e) § 60.592(e)
54F-MTBE	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for pumps in heavy-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
54F-MTBE	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.18 § 60.482-1(a)	Comply with the requirements in as stated in §60.482-10 for	§ 60.485(a) [G]§ 60.485(c) [G]§ 60.485(d)	[G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.482-1(b) § 60.482-10(d) § 60.482-10(e) § 60.482-10(m)	flares.	§ 60.485(f) [G]§ 60.485(g) § 60.592(d)	§ 60.486(e)(1) § 60.592(e)	§ 60.487(e) § 60.592(e)
54F-MTBE	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) § 60.482-10(e) [G]§ 60.482-10(g) § 60.482-10(h) § 60.482-10(m)	Comply with the requirements in as stated in §60.482-10 for closed-vent systems.	[G]§ 60.482-10(f) § 60.482-10(i) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.482-10(j) [G]§ 60.482-10(k) [G]§ 60.482-10(l) [G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
54F-MTBE	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for valves in heavy-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
54F-MTBE	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for flanges or other connectors.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
54F-MTBE	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for pressure relief devices in light-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
54F-MTBE	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(c)(1) § 63.162(a) § 63.162(c) [G]§ 63.162(f)	Comply with the specified Subpart H requirements for pumps in light liquid service,	[G]§ 63.163 [G]§ 63.176 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 63.162(g) § 63.162(h) [G]§ 63.163 [G]§ 63.171 [G]§ 63.176 § 63.648(f) § 63.655(d)(2)	instrument readings that define a leak are specified in Subpart CC, table 2.	[G]§ 63.648(b) § 63.648(c)(3) § 63.648(c)(4) § 63.648(c)(6) § 63.648(c)(7) § 63.648(c)(8)	§ 63.181(h) [G]§ 63.181(h)(3) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(8) § 63.181(h)(9) § 63.648(h) § 63.655(d)(1)(i) § 63.655(d)(6) § 63.655(i)(5)	[G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(v)
54F-MTBE	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for non-reciprocating pumps in heavy liquid service.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(6)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
54F-MTBE	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.164 [G]§ 63.171 § 63.648(i) § 63.655(d)(2)	Comply with the specified Subpart H requirements for compressors which are not in hydrogen service.	[G]§ 63.164 [G]§ 63.180(b) [G]§ 63.180(c) [G]§ 63.180(d) [G]§ 63.648(b)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(f) § 63.648(h) § 63.655(d)(1)(i) § 63.655(d)(6) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
54F-MTBE	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.165 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for pressure relief devices in gas/vapor service.	[G]§ 63.165 [G]§ 63.180(b) [G]§ 63.180(c) [G]§ 63.180(d) [G]§ 63.648(b)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(f) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
54F-MTBE	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for pressure relief device in liquid service.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(6)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
54F-MTBE	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.166 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for sampling connection systems.	[G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(i) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
54F-MTBE	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.167 [G]§ 63.171 [G]§ 63.175 § 63.655(d)(2)	Comply with the specified Subpart H requirements for open-ended valves and lines.	[G]§ 63.175 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(9) [G]§ 63.181(i) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
54F-MTBE	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(c)(1) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.168	Comply with the specified Subpart H requirements for valves in gas/vapor and light liquid service, instrument readings defining a leak are	[G]§ 63.168 [G]§ 63.175 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(3)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(v)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 63.171 [G]§ 63.175 § 63.648(c)(9) § 63.655(d)(2)	specified in Subpart CC, table 2.	§ 63.648(c)(4) § 63.648(c)(8)	§ 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(9) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	
54F-MTBE	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for valves in heavy liquid service.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(6)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
54F-MTBE	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(c)(5) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.649(a) § 63.655(d)(2)	Connectors in gas/vapor or light liquid are subject to the requirements in heavy liquid service in §63.169. The leak definition for specified systems subject to §63.169 is 1,000 parts per million.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(4)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(v)
54F-MTBE	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for connectors in heavy liquid service.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(6)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
54F-MTBE	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a)	Comply with the specified Subpart H	[G]§ 63.169 [G]§ 63.180(b)	§ 63.181(a) [G]§ 63.181(b)	[G]§ 63.182(a) § 63.182(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.655(d)(2)	requirements for instrumentation systems.	[G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(6)	§ 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
54F-MTBE	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.11(b) § 63.172(d) § 63.172(e) [G]§ 63.172(h) § 63.172(m) § 63.655(d)(2)	Comply with the specified Subpart H requirements for flares.	§ 63.172(e) [G]§ 63.172(h) [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.180(e)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(g) § 63.181(g)(1)(i) § 63.181(g)(1)(ii) § 63.181(g)(1)(iii) § 63.181(g)(1)(iv) [G]§ 63.181(g)(2) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e) [G]§ 63.655(f)(1)(i)(D)
54F-MTBE	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	[G]§ 63.648(g)	Compressors in hydrogen service are exempt from the requirements of §63.648(a) and (c), if an owner or operator demonstrates that a compressor is in hydrogen service. §63.648(g)(1)-(2).	[G]§ 63.648(g)	§ 63.648(h) § 63.655(d)(3)	None
54F-TAME	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.322(5)	No valve (gaseous service) may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.324(2) § 115.324(4) § 115.324(5) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	§ 115.326(1) [G]§ 115.326(2) § 115.326(3) § 115.326(4)	§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
54F-TAME	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.327(1)	Valves of nominal size of 2" (5 cm) or less are exempt, provided allowable emissions from sources affected by this division after controls are applied with exemptions will not exceed by more than 5.0% such allowable emissions with no exemptions.	None	None	§ 115.327(1)(A) § 115.327(1)(B) § 115.327(1)(C)
54F-TAME	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No pump seal, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
54F-TAME	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No pump seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(A) § 115.324(3) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
54F-TAME	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(5)	No valve (gaseous service), as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
54F-TAME	EU	R5322ALL	VOC	30 TAC Chapter	§ 115.322(1)	No valve (gaseous	§ 115.324	[G]§ 115.326(1)	[G]§ 115.324(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				115, Fugitives Pet Ref B Counties	§ 115.322(2) § 115.322(3) § 115.322(4) § 115.322(5)	service) may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324(2) § 115.324(2)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
54F-TAME	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No valve in liquid service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
54F-TAME	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No valve in liquid service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
54F-TAME	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No process drain, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
54F-TAME	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No process drain may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the	§ 115.324 § 115.324(1) § 115.324(1)(C) § 115.324(4) § 115.324(6)	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						leak is found, except as provided in §115.322(2).	[G]§ 115.325		
54F-TAME	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3) § 115.327(6)	No compressor seal, as described in § 115.327(3), (5) or (6), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
54F-TAME	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No compressor seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(A) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
54F-TAME	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No elevated valve, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
54F-TAME	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No elevated valve may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(D) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
54F-TAME	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B	§ 115.322(1) § 115.322(2) § 115.322(3)	No pressure relief valve in gaseous service, as described in § 115.327(3)	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Counties	§ 115.327(5)	or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).			
54F-TAME	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(5)	No pressure relief valve in gaseous service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(C) § 115.324(4) § 115.324(5) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
54F-TAME	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No connector, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
54F-TAME	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(d)	Comply with the requirements as stated in §60.482-1(d) for equipment in vacuum service.	None	§ 60.486(e) § 60.486(e)(1) § 60.486(e)(5)	None
54F-TAME	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-2 [G]§ 60.482-9	Comply with the requirements as stated in §60.482-2 for pumps in light-liquid service.	[G]§ 60.482-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d) § 60.593(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
								§ 60.592(e)	
54F-TAME	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) § 60.482-3(f) § 60.482-3(g)(1) § 60.482-3(g)(2) [G]§ 60.482-3(i) § 60.482-3(j) [G]§ 60.482-9 § 60.593(c)	Comply with the requirements as stated in §60.482-3 for reciprocating compressors that become subject under §60.14 and §60.15.	§ 60.482-3(f) § 60.482-3(g)(1) § 60.482-3(g)(2) [G]§ 60.482-3(i) § 60.482-3(j) § 60.485(a) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
54F-TAME	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-3 [G]§ 60.482-9	Comply with the requirements as stated in §60.482-3 for compressors.	[G]§ 60.482-3 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
54F-TAME	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-4 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-4 for pressure relief devices in gas/vapor service.	[G]§ 60.482-4 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(3) [G]§ 60.486(e)(4) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
54F-TAME	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-5 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-5 for sampling connection systems.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
54F-TAME	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-6	Comply with the requirements in as stated in §60.482-6 for open-ended valves and	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 60.482-9	lines.	§ 60.592(d)	§ 60.592(e)	§ 60.592(e)
54F-TAME	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-7 [G]§ 60.482-9 [G]§ 60.483-1 [G]§ 60.483-2 § 60.592(b)	Comply with the requirements in as stated in §60.482-7 for valves in gas/vapor or light-liquid service.	[G]§ 60.482-7 [G]§ 60.483-1 [G]§ 60.483-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d) § 60.593(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) [G]§ 60.486(g) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(d) § 60.487(e) § 60.592(e)
54F-TAME	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for pumps in heavy-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
54F-TAME	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.18 § 60.482-1(a) § 60.482-1(b) § 60.482-10(d) § 60.482-10(e) § 60.482-10(m)	Comply with the requirements in as stated in §60.482-10 for flares.	§ 60.485(a) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) [G]§ 60.485(g) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
54F-TAME	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) § 60.482-10(e) [G]§ 60.482-10(g) § 60.482-10(h) § 60.482-10(m)	Comply with the requirements in as stated in §60.482-10 for closed-vent systems.	[G]§ 60.482-10(f) § 60.482-10(i) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.482-10(j) [G]§ 60.482-10(k) [G]§ 60.482-10(l) [G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
54F-TAME	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b)	Comply with the requirements in as stated in §60.482-8 for	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 60.482-8 [G]§ 60.482-9	valves in heavy-liquid service.	[G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	§ 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(e) § 60.592(e)
54F-TAME	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for flanges or other connectors.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
54F-TAME	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for pressure relief devices in light-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
54F-TAME	EU	63CCVVALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(d)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for equipment in vacuum service.	None	§ 60.486(e) § 60.486(e)(1) § 60.486(e)(5)	None
54F-TAME	EU	63CCVVALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-2 [G]§ 60.482-9 § 63.648(a)(2) § 63.648(f) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pumps in light liquid service complying with §60.482-2.	[G]§ 60.482-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(d)(6) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
54F-TAME	EU	63CCVVALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-3 [G]§ 60.482-9 § 63.648(a)(2) § 63.648(i) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for compressors complying with §60.482-3.	[G]§ 60.482-3 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(d)(6) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
54F-TAME	EU	63CCVVALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) § 60.482-4(a) § 60.482-4(b)(1) [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pressure relief devices in gas/vapor service.	§ 60.482-4(b)(2) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(3) [G]§ 60.486(e)(4) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
54F-TAME	EU	63CCVVALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-5 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for sampling connection systems complying with §60.482-5.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
54F-TAME	EU	63CCVVALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-6 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for open-ended valves or lines complying with §60.482-6.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
54F-TAME	EU	63CCVVALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a)	Comply with the specified 40 CFR Part	[G]§ 60.482-7 [G]§ 60.483-1	[G]§ 60.486(a) [G]§ 60.486(b)	§ 60.487(a) [G]§ 60.487(b)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.482-1(b) [G]§ 60.482-7 [G]§ 60.482-9 [G]§ 60.483-1 [G]§ 60.483-2 § 63.648(a)(2) § 63.655(d)(2)	60, Subpart VV requirements for valves in gas/vapor service or in light liquid service complying with §60.482-7.	[G]§ 60.483-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) [G]§ 60.486(g) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 60.487(c) § 60.487(d) § 60.487(e)
54F-TAME	EU	63CCVVALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for valves in heavy liquid service complying with §60.482-8.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
54F-TAME	EU	63CCVVALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pumps in heavy liquid service complying with §60.482-8.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
54F-TAME	EU	63CCVVALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for flanges or other connectors complying with §60.482-8.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
54F-TAME	EU	63CCVVALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pressure relief devices in light liquid service complying with §60.482-8.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
54F-TAME	EU	63CCVVALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pressure relief devices in heavy liquid service complying with §60.482-8.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
54F-TAME	EU	63CCVVALL	112(B) HAPS	40 CFR Part 63, Subpart CC	[G]§ 63.648(g)	Compressors in hydrogen service are exempt from the requirements of §63.648(a) and (c), if an owner or operator demonstrates that a compressor is in hydrogen service. §63.648(g)(1)-(2).	[G]§ 63.648(g)	§ 63.648(h) § 63.655(d)(3) § 63.655(i)(5)	None
BUTAMER	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(d)	Comply with the requirements as stated in §60.482-1(d) for equipment in vacuum service.	None	§ 60.486(e) § 60.486(e)(1) § 60.486(e)(5)	None
BUTAMER	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-2 [G]§ 60.482-9	Comply with the requirements as stated in §60.482-2 for pumps in light-liquid service.	[G]§ 60.482-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							[G]§ 60.485(e) § 60.485(f) § 60.592(d) § 60.593(d)	[G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	
BUTAMER	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) § 60.482-3(f) § 60.482-3(g)(1) § 60.482-3(g)(2) [G]§ 60.482-3(i) § 60.482-3(j) [G]§ 60.482-9 § 60.593(c)	Comply with the requirements as stated in §60.482-3 for reciprocating compressors that become subject under §60.14 and §60.15.	§ 60.482-3(f) § 60.482-3(g)(1) § 60.482-3(g)(2) [G]§ 60.482-3(i) § 60.482-3(j) § 60.485(a) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
BUTAMER	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-3 [G]§ 60.482-9	Comply with the requirements as stated in §60.482-3 for compressors.	[G]§ 60.482-3 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
BUTAMER	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-4 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-4 for pressure relief devices in gas/vapor service.	[G]§ 60.482-4 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(3) [G]§ 60.486(e)(4) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
BUTAMER	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-5 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-5 for sampling connection systems.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
BUTAMER	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-6 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-6 for open-ended valves and lines.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
BUTAMER	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-7 [G]§ 60.482-9 [G]§ 60.483-1 [G]§ 60.483-2 § 60.592(b)	Comply with the requirements in as stated in §60.482-7 for valves in gas/vapor or light-liquid service.	[G]§ 60.482-7 [G]§ 60.483-1 [G]§ 60.483-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d) § 60.593(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) [G]§ 60.486(g) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(d) § 60.487(e) § 60.592(e)
BUTAMER	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for pumps in heavy-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
BUTAMER	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.18 § 60.482-1(a) § 60.482-1(b) § 60.482-10(d) § 60.482-10(e) § 60.482-10(m)	Comply with the requirements in as stated in §60.482-10 for flares.	§ 60.485(a) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) [G]§ 60.485(g) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
BUTAMER	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) § 60.482-10(e) [G]§ 60.482-10(g) § 60.482-10(h) § 60.482-10(m)	Comply with the requirements in as stated in §60.482-10 for closed-vent systems.	[G]§ 60.482-10(f) § 60.482-10(i) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.482-10(j) [G]§ 60.482-10(k) [G]§ 60.482-10(l) [G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
BUTAMER	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for valves in heavy-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
BUTAMER	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for flanges or other connectors.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
BUTAMER	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for pressure relief devices in light-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
CD-LOADING	EU	63CC	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.651(a)	Except as provided in §63.651(b)-(d), each owner or operator of a marine tank vessel loading operation located at a petroleum refinery shall comply with the requirements of §63.560 through §63.567.	§ 63.642(d)(1) § 63.642(d)(3) § 63.642(d)(4)	§ 63.642(e) § 63.655(c) § 63.655(i)(5)	§ 63.642(d)(2) § 63.642(f) § 63.655(c)
CD-PIPING	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.327(1)	Valves of nominal size of 2" (5 cm) or less are exempt, provided allowable emissions from sources affected by this division after controls are applied with	None	None	§ 115.327(1)(A) § 115.327(1)(B) § 115.327(1)(C)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						exemptions will not exceed by more than 5.0% such allowable emissions with no exemptions.			
CD-PIPING	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No pump seal, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
CD-PIPING	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No pump seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(A) § 115.324(3) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
CD-PIPING	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(5)	No valve (gaseous service), as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
CD-PIPING	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.322(5)	No valve (gaseous service) may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
CD-PIPING	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No valve in liquid service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
CD-PIPING	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No valve in liquid service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
CD-PIPING	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No process drain, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
CD-PIPING	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No process drain may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(C) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
CD-PIPING	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3) § 115.327(6)	No compressor seal, as described in § 115.327(3), (5) or (6), may be allowed to have a VOC leak as defined in	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						§101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).			
CD-PIPING	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No compressor seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(A) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
CD-PIPING	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No elevated valve, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
CD-PIPING	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No elevated valve may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(D) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
CD-PIPING	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(5)	No pressure relief valve in gaseous service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
CD-PIPING	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(5)	No pressure relief valve in gaseous service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(C) § 115.324(4) § 115.324(5) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
CD-PIPING	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No connector, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
CD-PIPING	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No connector may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
CD-PIPING	EU	63CCVVALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(d)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for equipment in vacuum service.	None	§ 60.486(e) § 60.486(e)(1) § 60.486(e)(5)	None
CD-PIPING	EU	63CCVVALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-2 [G]§ 60.482-9 § 63.648(a)(2) § 63.648(f) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pumps in light liquid service complying with §60.482-2.	[G]§ 60.482-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
								§ 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(d)(6) § 63.655(i)(5)	
CD-PIPING	EU	63CCVVALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-3 [G]§ 60.482-9 § 63.648(a)(2) § 63.648(i) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for compressors complying with §60.482-3.	[G]§ 60.482-3 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(d)(6) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
CD-PIPING	EU	63CCVVALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) § 60.482-4(a) § 60.482-4(b)(1) [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pressure relief devices in gas/vapor service.	§ 60.482-4(b)(2) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(3) [G]§ 60.486(e)(4) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
CD-PIPING	EU	63CCVVALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-5 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for sampling connection systems complying with §60.482-5.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
CD-PIPING	EU	63CCVVALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-6	Comply with the specified 40 CFR Part 60, Subpart VV requirements for open-	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	ended valves or lines complying with §60.482-6.	[G]§ 63.648(b)	§ 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	
CD-PIPING	EU	63CCVVALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-7 [G]§ 60.482-9 [G]§ 60.483-1 [G]§ 60.483-2 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for valves in gas/vapor service or in light liquid service complying with §60.482-7.	[G]§ 60.482-7 [G]§ 60.483-1 [G]§ 60.483-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) [G]§ 60.486(g) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(d) § 60.487(e)
CD-PIPING	EU	63CCVVALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for valves in heavy liquid service complying with §60.482-8.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
CD-PIPING	EU	63CCVVALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pumps in heavy liquid service complying with §60.482-8.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
CD-PIPING	EU	63CCVVALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8	Comply with the specified 40 CFR Part 60, Subpart VV requirements for flanges	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	or other connectors complying with §60.482-8.	§ 60.485(f) [G]§ 63.648(b)	§ 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	
CD-PIPING	EU	63CCVVALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pressure relief devices in light liquid service complying with §60.482-8.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
CD-PIPING	EU	63CCVVALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pressure relief devices in heavy liquid service complying with §60.482-8.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
CD-PIPING	EU	63CCVVALL	112(B) HAPS	40 CFR Part 63, Subpart CC	[G]§ 63.648(g)	Compressors in hydrogen service are exempt from the requirements of §63.648(a) and (c), if an owner or operator demonstrates that a compressor is in hydrogen service. §63.648(g)(1)-(2).	[G]§ 63.648(g)	§ 63.648(h) § 63.655(d)(3) § 63.655(i)(5)	None
FUELDRM	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.322(5)	No valve (gaseous service) may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar	[G]§ 115.324(2) § 115.324(4) § 115.324(5) § 115.324(6) [G]§ 115.324(7)	§ 115.326(1) [G]§ 115.326(2) § 115.326(3) § 115.326(4)	§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325		
FUELDRM	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.327(1)	Valves of nominal size of 2" (5 cm) or less are exempt, provided allowable emissions from sources affected by this division after controls are applied with exemptions will not exceed by more than 5.0% such allowable emissions with no exemptions.	None	None	§ 115.327(1)(A) § 115.327(1)(B) § 115.327(1)(C)
FUELDRM	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No pump seal, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
FUELDRM	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No pump seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(A) § 115.324(3) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
FUELDRM	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(5)	No valve (gaseous service), as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						leak is found, except as provided in §115.322(2).			
FUELDRM	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.322(5)	No valve (gaseous service) may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
FUELDRM	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No valve in liquid service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
FUELDRM	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No valve in liquid service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
FUELDRM	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No process drain, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
FUELDRM	EU	R5322ALL	VOC	30 TAC Chapter	§ 115.322(1)	No process drain may be	§ 115.324	[G]§ 115.326(1)	[G]§ 115.326(1)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				115, Fugitives Pet Ref B Counties	§ 115.322(2) § 115.322(3)	allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324(1) § 115.324(1)(C) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	§ 115.327(4)
FUELDRM	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3) § 115.327(6)	No compressor seal, as described in § 115.327(3), (5) or (6), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
FUELDRM	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No compressor seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(A) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
FUELDRM	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No elevated valve, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
FUELDRM	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No elevated valve may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(D) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
FUELDRM	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(5)	No pressure relief valve in gaseous service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
FUELDRM	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(5)	No pressure relief valve in gaseous service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(C) § 115.324(4) § 115.324(5) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
FUELDRM	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No connector, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GDFUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.322(5)	No valve (gaseous service) may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.324(2) § 115.324(4) § 115.324(5) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	§ 115.326(1) [G]§ 115.326(2) § 115.326(3) § 115.326(4)	§ 115.326(1) § 115.327(4)
GDFUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B	§ 115.327(1)	Valves of nominal size of 2" (5 cm) or less are exempt, provided	None	None	§ 115.327(1)(A) § 115.327(1)(B) § 115.327(1)(C)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Counties		allowable emissions from sources affected by this division after controls are applied with exemptions will not exceed by more than 5.0% such allowable emissions with no exemptions.			
GDFUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No pump seal, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GDFUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No pump seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(A) § 115.324(3) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GDFUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(5)	No valve (gaseous service), as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GDFUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No valve (gaseous service) may be allowed to have a VOC leak as defined in §101.1 for	§ 115.324 § 115.324(2) § 115.324(2)(B) § 115.324(4)	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.322(5)	more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324(6) [G]§ 115.324(7) [G]§ 115.325		
GDFUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No valve in liquid service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GDFUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No valve in liquid service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
GDFUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No process drain, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GDFUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No process drain may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(C) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GDFUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3) § 115.327(6)	No compressor seal, as described in § 115.327(3), (5) or (6), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GDFUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No compressor seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(A) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GDFUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No elevated valve, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GDFUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No elevated valve may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(D) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
GDFUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(5)	No pressure relief valve in gaseous service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						more than 15 calendar days after the leak is found, except as provided in §115.322(2).			
GDFUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(5)	No pressure relief valve in gaseous service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(C) § 115.324(4) § 115.324(5) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
GDFUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No connector, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GDFUG	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(d)	Comply with the requirements as stated in §60.482-1(d) for equipment in vacuum service.	None	§ 60.486(e) § 60.486(e)(1) § 60.486(e)(5)	None
GDFUG	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-2 [G]§ 60.482-9	Comply with the requirements as stated in §60.482-2 for pumps in light-liquid service.	[G]§ 60.482-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d) § 60.593(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GDFUG	EU	60GGGALL	VOC	40 CFR Part 60,	§ 60.592(a)	Comply with the	§ 60.482-3(f)	[G]§ 60.486(a)	§ 60.487(a)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Subpart GGG	§ 60.482-1(a) § 60.482-1(b) § 60.482-3(f) § 60.482-3(g)(1) § 60.482-3(g)(2) [G]§ 60.482-3(i) § 60.482-3(j) [G]§ 60.482-9 § 60.593(c)	requirements as stated in §60.482-3 for reciprocating compressors that become subject under §60.14 and §60.15.	§ 60.482-3(g)(1) § 60.482-3(g)(2) [G]§ 60.482-3(i) § 60.482-3(j) § 60.485(a) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	[G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GDFUG	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-3 [G]§ 60.482-9	Comply with the requirements as stated in §60.482-3 for compressors.	[G]§ 60.482-3 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GDFUG	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-4 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-4 for pressure relief devices in gas/vapor service.	[G]§ 60.482-4 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(3) [G]§ 60.486(e)(4) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GDFUG	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-5 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-5 for sampling connection systems.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GDFUG	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-6 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-6 for open-ended valves and lines.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GDFUG	EU	60GGGALL	VOC	40 CFR Part 60,	§ 60.592(a)	Comply with the	[G]§ 60.482-7	[G]§ 60.486(a)	§ 60.487(a)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Subpart GGG	§ 60.482-1(a) § 60.482-1(b) [G]§ 60.482-7 [G]§ 60.482-9 [G]§ 60.483-1 [G]§ 60.483-2 § 60.592(b)	requirements in as stated in §60.482-7 for valves in gas/vapor or light-liquid service.	[G]§ 60.483-1 [G]§ 60.483-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d) § 60.593(d)	[G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) [G]§ 60.486(g) § 60.486(j) § 60.592(e)	[G]§ 60.487(b) [G]§ 60.487(c) § 60.487(d) § 60.487(e) § 60.592(e)
GDFUG	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for pumps in heavy-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GDFUG	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.18 § 60.482-1(a) § 60.482-1(b) § 60.482-10(d) § 60.482-10(e) § 60.482-10(m)	Comply with the requirements in as stated in §60.482-10 for flares.	§ 60.485(a) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) [G]§ 60.485(g) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GDFUG	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) § 60.482-10(e) [G]§ 60.482-10(g) § 60.482-10(h) § 60.482-10(m)	Comply with the requirements in as stated in §60.482-10 for closed-vent systems.	[G]§ 60.482-10(f) § 60.482-10(i) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.482-10(j) [G]§ 60.482-10(k) [G]§ 60.482-10(l) [G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GDFUG	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for valves in heavy-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 60.592(d)	§ 60.592(e)	
GDFUG	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for flanges or other connectors.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GDFUG	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for pressure relief devices in light-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GDFUG	EU	63CCHALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) § 63.162(e) [G]§ 63.162(g) § 63.162(h)	Comply with the specified Subpart H requirements for equipment operated in organic HAP service < 300 hours per year.	[G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(i) § 63.181(j) § 63.648(h) § 63.654(d)(1)(i) § 63.654(d)(5) [G]§ 63.654(e) § 63.654(i)(4)	[G]§ 63.182(a) [G]§ 63.654(e)
GDFUG	EU	63CCHALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(c)(1) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.163 [G]§ 63.171 [G]§ 63.176 § 63.648(f) § 63.655(d)(2)	Comply with the specified Subpart H requirements for pumps in light liquid service, instrument readings that define a leak are specified in Subpart CC, table 2.	[G]§ 63.163 [G]§ 63.176 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(3) § 63.648(c)(4) § 63.648(c)(6) § 63.648(c)(7) § 63.648(c)(8)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(3) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(8) § 63.181(h)(9) § 63.648(h)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(v)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
								§ 63.655(d)(1)(i) § 63.655(d)(6) § 63.655(i)(5)	
GDFUG	EU	63CCHALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for non-reciprocating pumps in heavy liquid service.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(6)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
GDFUG	EU	63CCHALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.164 [G]§ 63.171 § 63.648(i) § 63.655(d)(2)	Comply with the specified Subpart H requirements for compressors which are not in hydrogen service.	[G]§ 63.164 [G]§ 63.180(b) [G]§ 63.180(c) [G]§ 63.180(d) [G]§ 63.648(b)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(f) § 63.648(h) § 63.655(d)(1)(i) § 63.655(d)(6) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
GDFUG	EU	63CCHALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.165 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for pressure relief devices in gas/vapor service.	[G]§ 63.165 [G]§ 63.180(b) [G]§ 63.180(c) [G]§ 63.180(d) [G]§ 63.648(b)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(f) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
GDFUG	EU	63CCHALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171	Comply with the specified Subpart H requirements for pressure relief device in liquid service.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(6)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.655(d)(2)				
GDFUG	EU	63CCHALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.166 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for sampling connection systems.	[G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(i) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
GDFUG	EU	63CCHALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.167 [G]§ 63.171 [G]§ 63.175 § 63.655(d)(2)	Comply with the specified Subpart H requirements for open-ended valves and lines.	[G]§ 63.175 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(9) [G]§ 63.181(i) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
GDFUG	EU	63CCHALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(c)(1) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.168 [G]§ 63.171 [G]§ 63.175 § 63.648(c)(9) § 63.655(d)(2)	Comply with the specified Subpart H requirements for valves in gas/vapor and light liquid service, instrument readings defining a leak are specified in Subpart CC, table 2.	[G]§ 63.168 [G]§ 63.175 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(3) § 63.648(c)(4) § 63.648(c)(8)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(9) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(v)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GDFUG	EU	63CCHALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for valves in heavy liquid service.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(6)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
GDFUG	EU	63CCHALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(c)(5) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.649(a) § 63.655(d)(2)	Connectors in gas/vapor or light liquid are subject to the requirements in heavy liquid service in §63.169. The leak definition for specified systems subject to §63.169 is 1,000 parts per million.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(4)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(v)
GDFUG	EU	63CCHALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for connectors in heavy liquid service.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(6)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
GDFUG	EU	63CCHALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for instrumentation systems.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(6)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
GDFUG	EU	63CCHALL	112(B)	40 CFR Part 63,	§ 63.648(a)	Comply with the	[G]§ 63.172(f)(1)	[G]§ 63.172(k)	[G]§ 63.182(a)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
			HAPS	Subpart CC	§ 63.172(a) [G]§ 63.172(h) § 63.172(i) § 63.172(m) § 63.655(d)(2)	specified Subpart H requirements for closed vent systems.	[G]§ 63.172(f)(2) § 63.172(g) [G]§ 63.172(h) [G]§ 63.172(k) [G]§ 63.172(l) [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b)	[G]§ 63.172(l) § 63.181(a) § 63.181(c) [G]§ 63.181(d) § 63.181(g) § 63.181(g)(1)(i) § 63.181(g)(1)(ii) [G]§ 63.181(g)(2) [G]§ 63.181(g)(3) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e) [G]§ 63.655(f)(1)(i)(C) [G]§ 63.655(f)(1)(i)(D)
GDFUG	EU	63CCHALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.11(b) § 63.172(d) § 63.172(e) [G]§ 63.172(h) § 63.172(m) § 63.655(d)(2)	Comply with the specified Subpart H requirements for flares.	§ 63.172(e) [G]§ 63.172(h) [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.180(e)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(g) § 63.181(g)(1)(i) § 63.181(g)(1)(ii) § 63.181(g)(1)(iii) § 63.181(g)(1)(iv) [G]§ 63.181(g)(2) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e) [G]§ 63.655(f)(1)(i)(D)
GDFUG	EU	63CCHALL	112(B) HAPS	40 CFR Part 63, Subpart CC	[G]§ 63.648(g)	Compressors in hydrogen service are exempt from the requirements of §63.648(a) and (c), if an owner or operator demonstrates that a compressor is in hydrogen service. §63.648(g)(1)-(2).	[G]§ 63.648(g)	§ 63.648(h) § 63.655(d)(3)	None
GRP-5GCCVV	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No valve (gaseous service) may be allowed to have a VOC leak as defined in §101.1 for	[G]§ 115.324(2) § 115.324(4) § 115.324(5) § 115.324(6)	§ 115.326(1) [G]§ 115.326(2) § 115.326(3) § 115.326(4)	§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.322(5)	more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.324(7) [G]§ 115.325		
GRP-5GCCVV	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.327(1)	Valves of nominal size of 2" (5 cm) or less are exempt, provided allowable emissions from sources affected by this division after controls are applied with exemptions will not exceed by more than 5.0% such allowable emissions with no exemptions.	None	None	§ 115.327(1)(A) § 115.327(1)(B) § 115.327(1)(C)
GRP-5GCCVV	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No pump seal, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-5GCCVV	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No pump seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(A) § 115.324(3) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-5GCCVV	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(5)	No valve (gaseous service), as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						calendar days after the leak is found, except as provided in §115.322(2).			
GRP-5GCCVV	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.322(5)	No valve (gaseous service) may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
GRP-5GCCVV	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No valve in liquid service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-5GCCVV	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No valve in liquid service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
GRP-5GCCVV	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No process drain, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-5GCCVV	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No process drain may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(C) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-5GCCVV	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3) § 115.327(6)	No compressor seal, as described in § 115.327(3), (5) or (6), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-5GCCVV	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No compressor seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(A) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-5GCCVV	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No elevated valve, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-5GCCVV	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No elevated valve may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as	§ 115.324 § 115.324(1) § 115.324(1)(D) § 115.324(4) § 115.324(6) [G]§ 115.324(7)	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						provided in §115.322(2).	[G]§ 115.325		
GRP-5GCCVV	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(5)	No pressure relief valve in gaseous service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-5GCCVV	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(5)	No pressure relief valve in gaseous service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(C) § 115.324(4) § 115.324(5) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
GRP-5GCCVV	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No connector, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-5GCCVV	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(d)	Comply with the requirements as stated in §60.482-1(d) for equipment in vacuum service.	None	§ 60.486(e) § 60.486(e)(1) § 60.486(e)(5)	None
GRP-5GCCVV	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-2	Comply with the requirements as stated in §60.482-2 for pumps in light-liquid service.	[G]§ 60.482-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 60.482-9		[G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d) § 60.593(d)	§ 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.592(e)
GRP-5GCCVV	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) § 60.482-3(f) § 60.482-3(g)(1) § 60.482-3(g)(2) [G]§ 60.482-3(i) § 60.482-3(j) [G]§ 60.482-9 § 60.593(c)	Comply with the requirements as stated in §60.482-3 for reciprocating compressors that become subject under §60.14 and §60.15.	§ 60.482-3(f) § 60.482-3(g)(1) § 60.482-3(g)(2) [G]§ 60.482-3(i) § 60.482-3(j) § 60.485(a) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-5GCCVV	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-3 [G]§ 60.482-9	Comply with the requirements as stated in §60.482-3 for compressors.	[G]§ 60.482-3 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-5GCCVV	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-4 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-4 for pressure relief devices in gas/vapor service.	[G]§ 60.482-4 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(3) [G]§ 60.486(e)(4) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-5GCCVV	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-5 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-5 for sampling connection systems.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-5GCCVV	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-6 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-6 for open-ended valves and lines.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-5GCCVV	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-7 [G]§ 60.482-9 [G]§ 60.483-1 [G]§ 60.483-2 § 60.592(b)	Comply with the requirements in as stated in §60.482-7 for valves in gas/vapor or light-liquid service.	[G]§ 60.482-7 [G]§ 60.483-1 [G]§ 60.483-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d) § 60.593(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) [G]§ 60.486(g) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(d) § 60.487(e) § 60.592(e)
GRP-5GCCVV	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for pumps in heavy-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-5GCCVV	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.18 § 60.482-1(a) § 60.482-1(b) § 60.482-10(d) § 60.482-10(e) § 60.482-10(m)	Comply with the requirements in as stated in §60.482-10 for flares.	§ 60.485(a) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) [G]§ 60.485(g) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1) § 60.592(e)	§ 60.487(a) § 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-5GCCVV	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) § 60.482-10(e) [G]§ 60.482-10(g) § 60.482-10(h) § 60.482-10(m)	Comply with the requirements in as stated in §60.482-10 for closed-vent systems.	[G]§ 60.482-10(f) § 60.482-10(i) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.482-10(j) [G]§ 60.482-10(k) [G]§ 60.482-10(l) [G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-5GCCVV	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for valves in heavy-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-5GCCVV	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for flanges or other connectors.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-5GCCVV	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for pressure relief devices in light-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-5GCCVV	EU	63CCVVALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(d)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for equipment in vacuum service.	None	§ 60.486(e) § 60.486(e)(1) § 60.486(e)(5)	None
GRP-5GCCVV	EU	63CCVVALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-2 [G]§ 60.482-9 § 63.648(a)(2) § 63.648(f) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pumps in light liquid service complying with §60.482-2.	[G]§ 60.482-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
								§ 63.655(d)(6) § 63.655(i)(5)	
GRP-5GCCVV	EU	63CCVVALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-3 [G]§ 60.482-9 § 63.648(a)(2) § 63.648(i) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for compressors complying with §60.482-3.	[G]§ 60.482-3 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(d)(6) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
GRP-5GCCVV	EU	63CCVVALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) § 60.482-4(a) § 60.482-4(b)(1) [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pressure relief devices in gas/vapor service.	§ 60.482-4(b)(2) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(3) [G]§ 60.486(e)(4) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
GRP-5GCCVV	EU	63CCVVALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-5 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for sampling connection systems complying with §60.482-5.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
GRP-5GCCVV	EU	63CCVVALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-6 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for open-ended valves or lines complying with §60.482-6.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-5GCCVV	EU	63CCVVALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-7 [G]§ 60.482-9 [G]§ 60.483-1 [G]§ 60.483-2 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for valves in gas/vapor service or in light liquid service complying with §60.482-7.	[G]§ 60.482-7 [G]§ 60.483-1 [G]§ 60.483-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) [G]§ 60.486(g) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(d) § 60.487(e)
GRP-5GCCVV	EU	63CCVVALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for valves in heavy liquid service complying with §60.482-8.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
GRP-5GCCVV	EU	63CCVVALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pumps in heavy liquid service complying with §60.482-8.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
GRP-5GCCVV	EU	63CCVVALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for flanges or other connectors complying with §60.482-8.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
								§ 63.655(i)(5)	
GRP-5GCCVV	EU	63CCVVALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pressure relief devices in light liquid service complying with §60.482-8.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
GRP-5GCCVV	EU	63CCVVALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pressure relief devices in heavy liquid service complying with §60.482-8.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
GRP-5GCCVV	EU	63CCVVALL	112(B) HAPS	40 CFR Part 63, Subpart CC	[G]§ 63.648(g)	Compressors in hydrogen service are exempt from the requirements of §63.648(a) and (c), if an owner or operator demonstrates that a compressor is in hydrogen service. §63.648(g)(1)-(2).	[G]§ 63.648(g)	§ 63.648(h) § 63.655(d)(3) § 63.655(i)(5)	None
GRP-R5-1	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.322(5)	No valve (gaseous service) may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.324(2) § 115.324(4) § 115.324(5) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	§ 115.326(1) [G]§ 115.326(2) § 115.326(3) § 115.326(4)	§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-R5-1	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.327(1)	Valves of nominal size of 2" (5 cm) or less are exempt, provided allowable emissions from sources affected by this division after controls are applied with exemptions will not exceed by more than 5.0% such allowable emissions with no exemptions.	None	None	§ 115.327(1)(A) § 115.327(1)(B) § 115.327(1)(C)
GRP-R5-1	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No pump seal, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5-1	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No pump seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(A) § 115.324(3) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5-1	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(5)	No valve (gaseous service), as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5-1	EU	R5322ALL	VOC	30 TAC Chapter	§ 115.322(1)	No valve (gaseous	§ 115.324	[G]§ 115.326(1)	[G]§ 115.324(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				115, Fugitives Pet Ref B Counties	§ 115.322(2) § 115.322(3) § 115.322(4) § 115.322(5)	service) may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324(2) § 115.324(2)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5-1	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No valve in liquid service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5-1	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No valve in liquid service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
GRP-R5-1	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No process drain, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5-1	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No process drain may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the	§ 115.324 § 115.324(1) § 115.324(1)(C) § 115.324(4) § 115.324(6)	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						leak is found, except as provided in §115.322(2).	[G]§ 115.325		
GRP-R5-1	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3) § 115.327(6)	No compressor seal, as described in § 115.327(3), (5) or (6), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5-1	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No compressor seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(A) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5-1	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No elevated valve, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5-1	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No elevated valve may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(D) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
GRP-R5-1	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B	§ 115.322(1) § 115.322(2) § 115.322(3)	No pressure relief valve in gaseous service, as described in § 115.327(3)	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Counties	§ 115.327(5)	or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).			
GRP-R5-1	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(5)	No pressure relief valve in gaseous service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(C) § 115.324(4) § 115.324(5) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
GRP-R5-1	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No connector, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5-2	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.322(5)	No valve (gaseous service) may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.324(2) § 115.324(4) § 115.324(5) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	§ 115.326(1) [G]§ 115.326(2) § 115.326(3) § 115.326(4)	§ 115.326(1) § 115.327(4)
GRP-R5-2	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.327(1)	Valves of nominal size of 2" (5 cm) or less are exempt, provided allowable emissions from sources affected by this division after	None	None	§ 115.327(1)(A) § 115.327(1)(B) § 115.327(1)(C)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						controls are applied with exemptions will not exceed by more than 5.0% such allowable emissions with no exemptions.			
GRP-R5-2	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No pump seal, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5-2	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No pump seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(A) § 115.324(3) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5-2	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(5)	No valve (gaseous service), as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5-2	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.322(5)	No valve (gaseous service) may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as	§ 115.324 § 115.324(2) § 115.324(2)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						provided in §115.322(2).			
GRP-R5-2	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No valve in liquid service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5-2	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No valve in liquid service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
GRP-R5-2	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No process drain, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5-2	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No process drain may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(C) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5-2	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B	§ 115.322(1) § 115.322(2) § 115.322(3)	No compressor seal, as described in § 115.327(3), (5) or (6),	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Counties	§ 115.327(3) § 115.327(6)	may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).			
GRP-R5-2	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No compressor seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(A) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5-2	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No elevated valve, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5-2	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No elevated valve may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(D) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
GRP-R5-2	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(5)	No pressure relief valve in gaseous service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						provided in §115.322(2).			
GRP-R5-2	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(5)	No pressure relief valve in gaseous service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(C) § 115.324(4) § 115.324(5) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
GRP-R5-2	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No connector, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5CC	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.322(5)	No valve (gaseous service) may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.324(2) § 115.324(4) § 115.324(5) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	§ 115.326(1) [G]§ 115.326(2) § 115.326(3) § 115.326(4)	§ 115.326(1) § 115.327(4)
GRP-R5CC	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.327(1)	Valves of nominal size of 2” (5 cm) or less are exempt, provided allowable emissions from sources affected by this division after controls are applied with exemptions will not exceed by more than 5.0% such allowable emissions with no exemptions.	None	None	§ 115.327(1)(A) § 115.327(1)(B) § 115.327(1)(C)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-R5CC	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No pump seal, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5CC	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No pump seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(A) § 115.324(3) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5CC	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(5)	No valve (gaseous service), as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5CC	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.322(5)	No valve (gaseous service) may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
GRP-R5CC	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3)	No valve in liquid service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.327(5)	for more than 15 calendar days after the leak is found, except as provided in §115.322(2).			
GRP-R5CC	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No valve in liquid service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
GRP-R5CC	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No process drain, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5CC	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No process drain may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(C) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5CC	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3) § 115.327(6)	No compressor seal, as described in § 115.327(3), (5) or (6), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-R5CC	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No compressor seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(A) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5CC	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No elevated valve, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5CC	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No elevated valve may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(D) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
GRP-R5CC	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(5)	No pressure relief valve in gaseous service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5CC	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(5)	No pressure relief valve in gaseous service may be allowed to have a VOC leak as defined in §101.1 for more than 15	§ 115.324 § 115.324(2) § 115.324(2)(C) § 115.324(4) § 115.324(5)	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324(6) [G]§ 115.324(7) [G]§ 115.325		
GRP-R5CC	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No connector, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5CC	EU	63CCHALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) § 63.162(e) [G]§ 63.162(g) § 63.162(h)	Comply with the specified Subpart H requirements for equipment operated in organic HAP service < 300 hours per year.	[G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(i) § 63.181(j) § 63.648(h) § 63.654(d)(1)(i) § 63.654(d)(5) [G]§ 63.654(e) § 63.654(i)(4)	[G]§ 63.182(a) [G]§ 63.654(e)
GRP-R5CC	EU	63CCHALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(c)(1) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.163 [G]§ 63.171 [G]§ 63.176 § 63.648(f) § 63.655(d)(2)	Comply with the specified Subpart H requirements for pumps in light liquid service, instrument readings that define a leak are specified in Subpart CC, table 2.	[G]§ 63.163 [G]§ 63.176 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(3) § 63.648(c)(4) § 63.648(c)(6) § 63.648(c)(7) § 63.648(c)(8)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(3) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(8) § 63.181(h)(9) § 63.648(h) § 63.655(d)(1)(i) § 63.655(d)(6) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(v)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-R5CC	EU	63CCHALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for non-reciprocating pumps in heavy liquid service.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(6)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
GRP-R5CC	EU	63CCHALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.164 [G]§ 63.171 § 63.648(i) § 63.655(d)(2)	Comply with the specified Subpart H requirements for compressors which are not in hydrogen service.	[G]§ 63.164 [G]§ 63.180(b) [G]§ 63.180(c) [G]§ 63.180(d) [G]§ 63.648(b)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(f) § 63.648(h) § 63.655(d)(1)(i) § 63.655(d)(6) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
GRP-R5CC	EU	63CCHALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.165 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for pressure relief devices in gas/vapor service.	[G]§ 63.165 [G]§ 63.180(b) [G]§ 63.180(c) [G]§ 63.180(d) [G]§ 63.648(b)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(f) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
GRP-R5CC	EU	63CCHALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for pressure relief device in liquid service.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(6)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
GRP-R5CC	EU	63CCHALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a)	Comply with the specified Subpart H	[G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b)	[G]§ 63.182(a) § 63.182(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.166 [G]§ 63.171 § 63.655(d)(2)	requirements for sampling connection systems.	[G]§ 63.648(b)	§ 63.181(c) [G]§ 63.181(i) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
GRP-R5CC	EU	63CCHALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.167 [G]§ 63.171 [G]§ 63.175 § 63.655(d)(2)	Comply with the specified Subpart H requirements for open-ended valves and lines.	[G]§ 63.175 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(9) [G]§ 63.181(i) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
GRP-R5CC	EU	63CCHALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(c)(1) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.168 [G]§ 63.171 [G]§ 63.175 § 63.648(c)(9) § 63.655(d)(2)	Comply with the specified Subpart H requirements for valves in gas/vapor and light liquid service, instrument readings defining a leak are specified in Subpart CC, table 2.	[G]§ 63.168 [G]§ 63.175 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(3) § 63.648(c)(4) § 63.648(c)(8)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(9) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(v)
GRP-R5CC	EU	63CCHALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c)	Comply with the specified Subpart H requirements for valves	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.655(d)(2)	in heavy liquid service.	[G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(6)	[G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(d) [G]§ 63.655(e)
GRP-R5CC	EU	63CCHALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(c)(5) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.649(a) § 63.655(d)(2)	Connectors in gas/vapor or light liquid are subject to the requirements in heavy liquid service in §63.169. The leak definition for specified systems subject to §63.169 is 1,000 parts per million.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(4)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(v)
GRP-R5CC	EU	63CCHALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for connectors in heavy liquid service.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(6)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
GRP-R5CC	EU	63CCHALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for instrumentation systems.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(6)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
GRP-R5CC	EU	63CCHALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.172(a) [G]§ 63.172(h) § 63.172(i)	Comply with the specified Subpart H requirements for closed vent systems.	[G]§ 63.172(f)(1) [G]§ 63.172(f)(2) § 63.172(g) [G]§ 63.172(h)	[G]§ 63.172(k) [G]§ 63.172(l) § 63.181(a) § 63.181(c)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.172(m) § 63.655(d)(2)		[G]§ 63.172(k) [G]§ 63.172(l) [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b)	[G]§ 63.181(d) § 63.181(g) § 63.181(g)(1)(i) § 63.181(g)(1)(ii) [G]§ 63.181(g)(2) [G]§ 63.181(g)(3) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.655(e) [G]§ 63.655(f)(1)(i)(C) [G]§ 63.655(f)(1)(i)(D)
GRP-R5CC	EU	63CCHALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.11(b) § 63.172(d) § 63.172(e) [G]§ 63.172(h) § 63.172(m) § 63.655(d)(2)	Comply with the specified Subpart H requirements for flares.	§ 63.172(e) [G]§ 63.172(h) [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.180(e)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(g) § 63.181(g)(1)(i) § 63.181(g)(1)(ii) § 63.181(g)(1)(iii) § 63.181(g)(1)(iv) [G]§ 63.181(g)(2) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e) [G]§ 63.655(f)(1)(i)(D)
GRP-R5CC	EU	63CCHALL	112(B) HAPS	40 CFR Part 63, Subpart CC	[G]§ 63.648(g)	Compressors in hydrogen service are exempt from the requirements of §63.648(a) and (c), if an owner or operator demonstrates that a compressor is in hydrogen service. §63.648(g)(1)-(2).	[G]§ 63.648(g)	§ 63.648(h) § 63.655(d)(3)	None
GRP-R5CC2	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.322(5)	No valve (gaseous service) may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as	[G]§ 115.324(2) § 115.324(4) § 115.324(5) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	§ 115.326(1) [G]§ 115.326(2) § 115.326(3) § 115.326(4)	§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						provided in §115.322(2).			
GRP-R5CC2	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.327(1)	Valves of nominal size of 2" (5 cm) or less are exempt, provided allowable emissions from sources affected by this division after controls are applied with exemptions will not exceed by more than 5.0% such allowable emissions with no exemptions.	None	None	§ 115.327(1)(A) § 115.327(1)(B) § 115.327(1)(C)
GRP-R5CC2	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No pump seal, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5CC2	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No pump seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(A) § 115.324(3) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5CC2	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(5)	No valve (gaseous service), as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-R5CC2	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.322(5)	No valve (gaseous service) may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
GRP-R5CC2	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No valve in liquid service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5CC2	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No valve in liquid service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
GRP-R5CC2	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No process drain, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5CC2	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No process drain may be allowed to have a VOC leak as defined in §101.1 for more than 15	§ 115.324 § 115.324(1) § 115.324(1)(C) § 115.324(4)	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324(6) [G]§ 115.325		
GRP-R5CC2	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3) § 115.327(6)	No compressor seal, as described in § 115.327(3), (5) or (6), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5CC2	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No compressor seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(A) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5CC2	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No elevated valve, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5CC2	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No elevated valve may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(D) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
GRP-R5CC2	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives	§ 115.322(1) § 115.322(2)	No pressure relief valve in gaseous service, as	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Pet Ref B Counties	§ 115.322(3) § 115.327(5)	described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).			
GRP-R5CC2	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(5)	No pressure relief valve in gaseous service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(C) § 115.324(4) § 115.324(5) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
GRP-R5CC2	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No connector, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5CC2	EU	63CCHALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) § 63.162(e) [G]§ 63.162(g) § 63.162(h)	Comply with the specified Subpart H requirements for equipment operated in organic HAP service < 300 hours per year.	[G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(i) § 63.181(j) § 63.648(h) § 63.654(d)(1)(i) § 63.654(d)(5) [G]§ 63.654(e) § 63.654(i)(4)	[G]§ 63.182(a) [G]§ 63.654(e)
GRP-R5CC2	EU	63CCHALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(c)(1) § 63.162(a) § 63.162(c)	Comply with the specified Subpart H requirements for pumps	[G]§ 63.163 [G]§ 63.176 [G]§ 63.180(b)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.163 [G]§ 63.171 [G]§ 63.176 § 63.648(f) § 63.655(d)(2)	in light liquid service, instrument readings that define a leak are specified in Subpart CC, table 2.	[G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(3) § 63.648(c)(4) § 63.648(c)(6) § 63.648(c)(7) § 63.648(c)(8)	[G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(3) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(8) § 63.181(h)(9) § 63.648(h) § 63.655(d)(1)(i) § 63.655(d)(6) § 63.655(i)(5)	[G]§ 63.182(d) [G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(v)
GRP-R5CC2	EU	63CCHALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for non-reciprocating pumps in heavy liquid service.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(6)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
GRP-R5CC2	EU	63CCHALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.164 [G]§ 63.171 § 63.648(i) § 63.655(d)(2)	Comply with the specified Subpart H requirements for compressors which are not in hydrogen service.	[G]§ 63.164 [G]§ 63.180(b) [G]§ 63.180(c) [G]§ 63.180(d) [G]§ 63.648(b)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(f) § 63.648(h) § 63.655(d)(1)(i) § 63.655(d)(6) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
GRP-R5CC2	EU	63CCHALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.165 [G]§ 63.171	Comply with the specified Subpart H requirements for pressure relief devices in gas/vapor service.	[G]§ 63.165 [G]§ 63.180(b) [G]§ 63.180(c) [G]§ 63.180(d) [G]§ 63.648(b)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(f) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.655(d)(2)				
GRP-R5CC2	EU	63CCHALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for pressure relief device in liquid service.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(6)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
GRP-R5CC2	EU	63CCHALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.166 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for sampling connection systems.	[G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(i) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
GRP-R5CC2	EU	63CCHALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.167 [G]§ 63.171 [G]§ 63.175 § 63.655(d)(2)	Comply with the specified Subpart H requirements for open-ended valves and lines.	[G]§ 63.175 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(9) [G]§ 63.181(i) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
GRP-R5CC2	EU	63CCHALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(c)(1) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g)	Comply with the specified Subpart H requirements for valves in gas/vapor and light liquid service,	[G]§ 63.168 [G]§ 63.175 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.162(h) [G]§ 63.168 [G]§ 63.171 [G]§ 63.175 § 63.648(c)(9) § 63.655(d)(2)	instrument readings defining a leak are specified in Subpart CC, table 2.	§ 63.648(c)(2)(i) § 63.648(c)(3) § 63.648(c)(4) § 63.648(c)(8)	[G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(9) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(v)
GRP-R5CC2	EU	63CCHALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for valves in heavy liquid service.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(6)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
GRP-R5CC2	EU	63CCHALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(c)(5) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.649(a) § 63.655(d)(2)	Connectors in gas/vapor or light liquid are subject to the requirements in heavy liquid service in §63.169. The leak definition for specified systems subject to §63.169 is 1,000 parts per million.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(4)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(v)
GRP-R5CC2	EU	63CCHALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for connectors in heavy liquid service.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(6)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-R5CC2	EU	63CCHALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for instrumentation systems.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(6)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
GRP-R5CC2	EU	63CCHALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.172(a) [G]§ 63.172(h) § 63.172(i) § 63.172(m) § 63.655(d)(2)	Comply with the specified Subpart H requirements for closed vent systems.	[G]§ 63.172(f)(1) [G]§ 63.172(f)(2) § 63.172(g) [G]§ 63.172(h) [G]§ 63.172(k) [G]§ 63.172(l) [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b)	[G]§ 63.172(k) [G]§ 63.172(l) § 63.181(a) § 63.181(c) [G]§ 63.181(d) § 63.181(g) § 63.181(g)(1)(i) § 63.181(g)(1)(ii) [G]§ 63.181(g)(2) [G]§ 63.181(g)(3) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e) [G]§ 63.655(f)(1)(i)(C) [G]§ 63.655(f)(1)(i)(D)
GRP-R5CC2	EU	63CCHALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.11(b) § 63.172(d) § 63.172(e) [G]§ 63.172(h) § 63.172(m) § 63.655(d)(2)	Comply with the specified Subpart H requirements for flares.	§ 63.172(e) [G]§ 63.172(h) [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.180(e)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(g) § 63.181(g)(1)(i) § 63.181(g)(1)(ii) § 63.181(g)(1)(iii) § 63.181(g)(1)(iv) [G]§ 63.181(g)(2) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e) [G]§ 63.655(f)(1)(i)(D)
GRP-R5CC2	EU	63CCHALL	112(B) HAPS	40 CFR Part 63, Subpart CC	[G]§ 63.648(g)	Compressors in hydrogen service are exempt from the requirements of	[G]§ 63.648(g)	§ 63.648(h) § 63.655(d)(3)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						§63.648(a) and (c), if an owner or operator demonstrates that a compressor is in hydrogen service. §63.648(g)(1)-(2).			
GRP-R5G	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.322(5)	No valve (gaseous service) may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.324(2) § 115.324(4) § 115.324(5) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	§ 115.326(1) [G]§ 115.326(2) § 115.326(3) § 115.326(4)	§ 115.326(1) § 115.327(4)
GRP-R5G	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.327(1)	Valves of nominal size of 2" (5 cm) or less are exempt, provided allowable emissions from sources affected by this division after controls are applied with exemptions will not exceed by more than 5.0% such allowable emissions with no exemptions.	None	None	§ 115.327(1)(A) § 115.327(1)(B) § 115.327(1)(C)
GRP-R5G	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No pump seal, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5G	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B	§ 115.322(1) § 115.322(2) § 115.322(3)	No pump seal may be allowed to have a VOC leak as defined in §101.1	§ 115.324 § 115.324(1) § 115.324(1)(A)	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Counties		for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324(3) § 115.324(4) § 115.324(6) [G]§ 115.325	§ 115.326(5)	
GRP-R5G	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(5)	No valve (gaseous service), as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5G	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.322(5)	No valve (gaseous service) may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
GRP-R5G	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No valve in liquid service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5G	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No valve in liquid service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-R5G	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No process drain, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5G	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No process drain may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(C) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5G	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3) § 115.327(6)	No compressor seal, as described in § 115.327(3), (5) or (6), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5G	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No compressor seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(A) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5G	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No elevated valve, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						days after the leak is found, except as provided in §115.322(2).			
GRP-R5G	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No elevated valve may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(D) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
GRP-R5G	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(5)	No pressure relief valve in gaseous service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5G	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(5)	No pressure relief valve in gaseous service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(C) § 115.324(4) § 115.324(5) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
GRP-R5G	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No connector, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-R5G	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(d)	Comply with the requirements as stated in §60.482-1(d) for equipment in vacuum service.	None	§ 60.486(e) § 60.486(e)(1) § 60.486(e)(5)	None
GRP-R5G	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-2 [G]§ 60.482-9	Comply with the requirements as stated in §60.482-2 for pumps in light-liquid service.	[G]§ 60.482-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d) § 60.593(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-R5G	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) § 60.482-3(f) § 60.482-3(g)(1) § 60.482-3(g)(2) [G]§ 60.482-3(i) § 60.482-3(j) [G]§ 60.482-9 § 60.593(c)	Comply with the requirements as stated in §60.482-3 for reciprocating compressors that become subject under §60.14 and §60.15.	§ 60.482-3(f) § 60.482-3(g)(1) § 60.482-3(g)(2) [G]§ 60.482-3(i) § 60.482-3(j) § 60.485(a) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-R5G	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-3 [G]§ 60.482-9	Comply with the requirements as stated in §60.482-3 for compressors.	[G]§ 60.482-3 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-R5G	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b)	Comply with the requirements in as stated in §60.482-4 for	[G]§ 60.482-4 § 60.485(a) [G]§ 60.485(b)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 60.482-4 [G]§ 60.482-9	pressure relief devices in gas/vapor service.	[G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	§ 60.486(e)(3) [G]§ 60.486(e)(4) § 60.486(j) § 60.592(e)	§ 60.487(e) § 60.592(e)
GRP-R5G	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-5 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-5 for sampling connection systems.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-R5G	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-6 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-6 for open-ended valves and lines.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-R5G	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-7 [G]§ 60.482-9 [G]§ 60.483-1 [G]§ 60.483-2 § 60.592(b)	Comply with the requirements in as stated in §60.482-7 for valves in gas/vapor or light-liquid service.	[G]§ 60.482-7 [G]§ 60.483-1 [G]§ 60.483-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d) § 60.593(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) [G]§ 60.486(g) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(d) § 60.487(e) § 60.592(e)
GRP-R5G	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for pumps in heavy-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-R5G	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.18 § 60.482-1(a) § 60.482-1(b)	Comply with the requirements in as stated in §60.482-10 for flares.	§ 60.485(a) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.482-10(d) § 60.482-10(e) § 60.482-10(m)		[G]§ 60.485(g) § 60.592(d)	§ 60.592(e)	§ 60.592(e)
GRP-R5G	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) § 60.482-10(e) [G]§ 60.482-10(g) § 60.482-10(h) § 60.482-10(m)	Comply with the requirements in as stated in §60.482-10 for closed-vent systems.	[G]§ 60.482-10(f) § 60.482-10(i) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.482-10(j) [G]§ 60.482-10(k) [G]§ 60.482-10(l) [G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-R5G	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for valves in heavy-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-R5G	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for flanges or other connectors.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-R5G	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for pressure relief devices in light-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-SRU3	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.322(5)	No valve (gaseous service) may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar	[G]§ 115.324(2) § 115.324(4) § 115.324(5) § 115.324(6) [G]§ 115.324(7)	§ 115.326(1) [G]§ 115.326(2) § 115.326(3) § 115.326(4)	§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325		
GRP-SRU3	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.327(1)	Valves of nominal size of 2" (5 cm) or less are exempt, provided allowable emissions from sources affected by this division after controls are applied with exemptions will not exceed by more than 5.0% such allowable emissions with no exemptions.	None	None	§ 115.327(1)(A) § 115.327(1)(B) § 115.327(1)(C)
GRP-SRU3	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No pump seal, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-SRU3	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No pump seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(A) § 115.324(3) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-SRU3	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(5)	No valve (gaseous service), as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						leak is found, except as provided in §115.322(2).			
GRP-SRU3	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.322(5)	No valve (gaseous service) may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
GRP-SRU3	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No valve in liquid service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-SRU3	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No valve in liquid service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
GRP-SRU3	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No process drain, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-SRU3	EU	R5322ALL	VOC	30 TAC Chapter	§ 115.322(1)	No process drain may be	§ 115.324	[G]§ 115.326(1)	[G]§ 115.326(1)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				115, Fugitives Pet Ref B Counties	§ 115.322(2) § 115.322(3)	allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324(1) § 115.324(1)(C) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	§ 115.327(4)
GRP-SRU3	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3) § 115.327(6)	No compressor seal, as described in § 115.327(3), (5) or (6), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-SRU3	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No compressor seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(A) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-SRU3	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No elevated valve, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-SRU3	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No elevated valve may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(D) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-SRU3	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(5)	No pressure relief valve in gaseous service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-SRU3	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(5)	No pressure relief valve in gaseous service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(C) § 115.324(4) § 115.324(5) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
GRP-SRU3	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No connector, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-SRU3	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(d)	Comply with the requirements as stated in §60.482-1(d) for equipment in vacuum service.	None	§ 60.486(e) § 60.486(e)(1) § 60.486(e)(5)	None
GRP-SRU3	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-2 [G]§ 60.482-9	Comply with the requirements as stated in §60.482-2 for pumps in light-liquid service.	[G]§ 60.482-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 60.485(f) § 60.592(d) § 60.593(d)	[G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	
GRP-SRU3	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) § 60.482-3(f) § 60.482-3(g)(1) § 60.482-3(g)(2) [G]§ 60.482-3(i) § 60.482-3(j) [G]§ 60.482-9 § 60.593(c)	Comply with the requirements as stated in §60.482-3 for reciprocating compressors that become subject under §60.14 and §60.15.	§ 60.482-3(f) § 60.482-3(g)(1) § 60.482-3(g)(2) [G]§ 60.482-3(i) § 60.482-3(j) § 60.485(a) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-SRU3	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-3 [G]§ 60.482-9	Comply with the requirements as stated in §60.482-3 for compressors.	[G]§ 60.482-3 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-SRU3	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-4 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-4 for pressure relief devices in gas/vapor service.	[G]§ 60.482-4 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(3) [G]§ 60.486(e)(4) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-SRU3	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-5 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-5 for sampling connection systems.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-SRU3	EU	60GGGALL	VOC	40 CFR Part 60,	§ 60.592(a)	Comply with the	§ 60.485(a)	[G]§ 60.486(a)	§ 60.487(a)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Subpart GGG	§ 60.482-1(a) § 60.482-1(b) [G]§ 60.482-6 [G]§ 60.482-9	requirements in as stated in §60.482-6 for open-ended valves and lines.	[G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	§ 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	[G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-SRU3	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-7 [G]§ 60.482-9 [G]§ 60.483-1 [G]§ 60.483-2 § 60.592(b)	Comply with the requirements in as stated in §60.482-7 for valves in gas/vapor or light-liquid service.	[G]§ 60.482-7 [G]§ 60.483-1 [G]§ 60.483-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d) § 60.593(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) [G]§ 60.486(g) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(d) § 60.487(e) § 60.592(e)
GRP-SRU3	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for pumps in heavy-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-SRU3	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.18 § 60.482-1(a) § 60.482-1(b) § 60.482-10(d) § 60.482-10(e) § 60.482-10(m)	Comply with the requirements in as stated in §60.482-10 for flares.	§ 60.485(a) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) [G]§ 60.485(g) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-SRU3	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) § 60.482-10(e) [G]§ 60.482-10(g) § 60.482-10(h) § 60.482-10(m)	Comply with the requirements in as stated in §60.482-10 for closed-vent systems.	[G]§ 60.482-10(f) § 60.482-10(i) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.482-10(j) [G]§ 60.482-10(k) [G]§ 60.482-10(l) [G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-SRU3	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for valves in heavy-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-SRU3	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for flanges or other connectors.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-SRU3	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for pressure relief devices in light-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
LPG STORAG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.322(5)	No valve (gaseous service) may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.324(2) § 115.324(4) § 115.324(5) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	§ 115.326(1) [G]§ 115.326(2) § 115.326(3) § 115.326(4)	§ 115.326(1) § 115.327(4)
LPG STORAG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.327(1)	Valves of nominal size of 2" (5 cm) or less are exempt, provided allowable emissions from sources affected by this division after controls are applied with exemptions will not exceed by more than	None	None	§ 115.327(1)(A) § 115.327(1)(B) § 115.327(1)(C)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						5.0% such allowable emissions with no exemptions.			
LPG STORAG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No pump seal, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
LPG STORAG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No pump seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(A) § 115.324(3) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
LPG STORAG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(5)	No valve (gaseous service), as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
LPG STORAG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.322(5)	No valve (gaseous service) may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
LPG STORAG	EU	R5322ALL	VOC	30 TAC Chapter	§ 115.322(1)	No valve in liquid	[G]§ 115.325	[G]§ 115.326(1)	[G]§ 115.326(1)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				115, Fugitives Pet Ref B Counties	§ 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).		§ 115.326(5)	§ 115.327(4)
LPG STORAG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No valve in liquid service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
LPG STORAG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No process drain, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
LPG STORAG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No process drain may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(C) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
LPG STORAG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3) § 115.327(6)	No compressor seal, as described in § 115.327(3), (5) or (6), may be allowed to have a VOC leak as defined in §101.1 for more than 15	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						calendar days after the leak is found, except as provided in §115.322(2).			
LPG STORAG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No compressor seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(A) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
LPG STORAG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No elevated valve, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
LPG STORAG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No elevated valve may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(D) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
LPG STORAG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(5)	No pressure relief valve in gaseous service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
LPG STORAG	EU	R5322ALL	VOC	30 TAC Chapter	§ 115.322(1)	No pressure relief valve	§ 115.324	[G]§ 115.326(1)	[G]§ 115.324(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				115, Fugitives Pet Ref B Counties	§ 115.322(2) § 115.322(3) § 115.322(5)	in gaseous service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324(2) § 115.324(2)(C) § 115.324(4) § 115.324(5) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
LPG STORAG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No connector, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
MTBE-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.322(5)	No valve (gaseous service) may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.324(2) § 115.324(4) § 115.324(5) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	§ 115.326(1) [G]§ 115.326(2) § 115.326(3) § 115.326(4)	§ 115.326(1) § 115.327(4)
MTBE-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.327(1)	Valves of nominal size of 2" (5 cm) or less are exempt, provided allowable emissions from sources affected by this division after controls are applied with exemptions will not exceed by more than 5.0% such allowable emissions with no exemptions.	None	None	§ 115.327(1)(A) § 115.327(1)(B) § 115.327(1)(C)
MTBE-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives	§ 115.322(1) § 115.322(2)	No pump seal, as described in § 115.327(3)	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Pet Ref B Counties	§ 115.322(3) § 115.327(3)	or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).			
MTBE-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No pump seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(A) § 115.324(3) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
MTBE-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(5)	No valve (gaseous service), as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
MTBE-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.322(5)	No valve (gaseous service) may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
MTBE-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No valve in liquid service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						leak is found, except as provided in §115.322(2).			
MTBE-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No valve in liquid service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
MTBE-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No process drain, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
MTBE-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No process drain may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(C) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
MTBE-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3) § 115.327(6)	No compressor seal, as described in § 115.327(3), (5) or (6), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
MTBE-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives	§ 115.322(1) § 115.322(2)	No compressor seal may be allowed to have a	§ 115.324 § 115.324(2)	[G]§ 115.326(1) [G]§ 115.326(2)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Pet Ref B Counties	§ 115.322(3)	VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324(2)(A) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(3) § 115.326(5)	
MTBE-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No elevated valve, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
MTBE-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No elevated valve may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(D) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
MTBE-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(5)	No pressure relief valve in gaseous service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
MTBE-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(5)	No pressure relief valve in gaseous service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as	§ 115.324 § 115.324(2) § 115.324(2)(C) § 115.324(4) § 115.324(5) § 115.324(6) [G]§ 115.324(7)	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						provided in §115.322(2).	[G]§ 115.325		
MTBE-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No connector, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
MTBE-FUG	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(d)	Comply with the requirements as stated in §60.482-1(d) for equipment in vacuum service.	None	§ 60.486(e) § 60.486(e)(1) § 60.486(e)(5)	None
MTBE-FUG	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-2 [G]§ 60.482-9	Comply with the requirements as stated in §60.482-2 for pumps in light-liquid service.	[G]§ 60.482-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d) § 60.593(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
MTBE-FUG	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) § 60.482-3(f) § 60.482-3(g)(1) § 60.482-3(g)(2) [G]§ 60.482-3(i) § 60.482-3(j) [G]§ 60.482-9 § 60.593(c)	Comply with the requirements as stated in §60.482-3 for reciprocating compressors that become subject under §60.14 and §60.15.	§ 60.482-3(f) § 60.482-3(g)(1) § 60.482-3(g)(2) [G]§ 60.482-3(i) § 60.482-3(j) § 60.485(a) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
MTBE-FUG	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a)	Comply with the requirements as stated	[G]§ 60.482-3 § 60.485(a)	[G]§ 60.486(a) [G]§ 60.486(b)	§ 60.487(a) [G]§ 60.487(b)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.482-1(b) [G]§ 60.482-3 [G]§ 60.482-9	in §60.482-3 for compressors.	[G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	[G]§ 60.487(c) § 60.487(e) § 60.592(e)
MTBE-FUG	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-4 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-4 for pressure relief devices in gas/vapor service.	[G]§ 60.482-4 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(3) [G]§ 60.486(e)(4) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
MTBE-FUG	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-5 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-5 for sampling connection systems.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
MTBE-FUG	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-6 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-6 for open-ended valves and lines.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
MTBE-FUG	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-7 [G]§ 60.482-9 [G]§ 60.483-1 [G]§ 60.483-2 § 60.592(b)	Comply with the requirements in as stated in §60.482-7 for valves in gas/vapor or light-liquid service.	[G]§ 60.482-7 [G]§ 60.483-1 [G]§ 60.483-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d) § 60.593(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) [G]§ 60.486(g) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(d) § 60.487(e) § 60.592(e)
MTBE-FUG	EU	60GGGALL	VOC	40 CFR Part 60,	§ 60.592(a)	Comply with the	[G]§ 60.482-8	[G]§ 60.486(a)	§ 60.487(a)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Subpart GGG	§ 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	requirements in as stated in §60.482-8 for pumps in heavy-liquid service.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	[G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
MTBE-FUG	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.18 § 60.482-1(a) § 60.482-1(b) § 60.482-10(d) § 60.482-10(e) § 60.482-10(m)	Comply with the requirements in as stated in §60.482-10 for flares.	§ 60.485(a) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) [G]§ 60.485(g) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
MTBE-FUG	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) § 60.482-10(e) [G]§ 60.482-10(g) § 60.482-10(h) § 60.482-10(m)	Comply with the requirements in as stated in §60.482-10 for closed-vent systems.	[G]§ 60.482-10(f) § 60.482-10(i) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.482-10(j) [G]§ 60.482-10(k) [G]§ 60.482-10(l) [G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
MTBE-FUG	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for valves in heavy-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
MTBE-FUG	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for flanges or other connectors.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
MTBE-FUG	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a)	Comply with the requirements in as	[G]§ 60.482-8 § 60.485(a)	[G]§ 60.486(a) [G]§ 60.486(b)	§ 60.487(a) [G]§ 60.487(b)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	stated in §60.482-8 for pressure relief devices in light-liquid service.	[G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	[G]§ 60.487(c) § 60.487(e) § 60.592(e)
MVRUF	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.322(5)	No valve (gaseous service) may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.324(2) § 115.324(4) § 115.324(5) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	§ 115.326(1) [G]§ 115.326(2) § 115.326(3) § 115.326(4)	§ 115.326(1) § 115.327(4)
MVRUF	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.327(1)	Valves of nominal size of 2" (5 cm) or less are exempt, provided allowable emissions from sources affected by this division after controls are applied with exemptions will not exceed by more than 5.0% such allowable emissions with no exemptions.	None	None	§ 115.327(1)(A) § 115.327(1)(B) § 115.327(1)(C)
MVRUF	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No pump seal, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
MVRUF	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No pump seal may be allowed to have a VOC leak as defined in §101.1 for more than 15	§ 115.324 § 115.324(1) § 115.324(1)(A) § 115.324(3)	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324(4) § 115.324(6) [G]§ 115.325		
MVRUF	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(5)	No valve (gaseous service), as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
MVRUF	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.322(5)	No valve (gaseous service) may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
MVRUF	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No valve in liquid service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
MVRUF	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No valve in liquid service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
MVRUF	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No process drain, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
MVRUF	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No process drain may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(C) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
MVRUF	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3) § 115.327(6)	No compressor seal, as described in § 115.327(3), (5) or (6), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
MVRUF	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No compressor seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(A) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
MVRUF	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No elevated valve, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						days after the leak is found, except as provided in §115.322(2).			
MVRUF	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No elevated valve may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(D) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
MVRUF	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(5)	No pressure relief valve in gaseous service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
MVRUF	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(5)	No pressure relief valve in gaseous service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(C) § 115.324(4) § 115.324(5) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
MVRUF	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No connector, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
MVRUF	EU	63CCVVALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(d)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for equipment in vacuum service.	None	§ 60.486(e) § 60.486(e)(1) § 60.486(e)(5)	None
MVRUF	EU	63CCVVALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-2 [G]§ 60.482-9 § 63.648(a)(2) § 63.648(f) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pumps in light liquid service complying with §60.482-2.	[G]§ 60.482-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(d)(6) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
MVRUF	EU	63CCVVALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-3 [G]§ 60.482-9 § 63.648(a)(2) § 63.648(i) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for compressors complying with §60.482-3.	[G]§ 60.482-3 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(d)(6) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
MVRUF	EU	63CCVVALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) § 60.482-4(a) § 60.482-4(b)(1) [G]§ 60.482-9 § 63.648(a)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pressure relief devices in gas/vapor service.	§ 60.482-4(b)(2) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(3) [G]§ 60.486(e)(4) § 60.486(j) § 63.648(h)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.655(d)(2)			§ 63.655(d)(1)(i) § 63.655(i)(5)	
MVRUF	EU	63CCVVALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-5 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for sampling connection systems complying with §60.482-5.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
MVRUF	EU	63CCVVALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-6 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for open-ended valves or lines complying with §60.482-6.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
MVRUF	EU	63CCVVALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-7 [G]§ 60.482-9 [G]§ 60.483-1 [G]§ 60.483-2 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for valves in gas/vapor service or in light liquid service complying with §60.482-7.	[G]§ 60.482-7 [G]§ 60.483-1 [G]§ 60.483-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) [G]§ 60.486(g) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(d) § 60.487(e)
MVRUF	EU	63CCVVALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for valves in heavy liquid service complying with §60.482-8.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
MVRUF	EU	63CCVVALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pumps in heavy liquid service complying with §60.482-8.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
MVRUF	EU	63CCVVALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for flanges or other connectors complying with §60.482-8.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
MVRUF	EU	63CCVVALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pressure relief devices in light liquid service complying with §60.482-8.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
MVRUF	EU	63CCVVALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pressure relief devices in heavy liquid service complying with §60.482-8.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
MVRUF	EU	63CCVVALL	112(B) HAPS	40 CFR Part 63, Subpart CC	[G]§ 63.648(g)	Compressors in hydrogen service are	[G]§ 63.648(g)	§ 63.648(h) § 63.655(d)(3)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						exempt from the requirements of §63.648(a) and (c), if an owner or operator demonstrates that a compressor is in hydrogen service. §63.648(g)(1)-(2).		§ 63.655(i)(5)	
OLEFLEX-FU	EU	60VVALL	VOC	40 CFR Part 60, Subpart VV	§ 60.482-1(d)	Equipment that is in vacuum service is excluded from the requirements of §60.482-2 to §60.482-10, if it is identified as required in §60.486(e)(5).	None	§ 60.486(e) § 60.486(e)(1) § 60.486(e)(5)	None
OLEFLEX-FU	EU	60VVALL	VOC	40 CFR Part 60, Subpart VV	[G]§ 60.482-2 § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-9	Pumps in light liquid service shall comply with the requirements outlined in § 60.482-2(a)-(f).	[G]§ 60.482-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
OLEFLEX-FU	EU	60VVALL	VOC	40 CFR Part 60, Subpart VV	[G]§ 60.482-10(g) § 60.482-1(a) § 60.482-1(b) § 60.482-10(e) § 60.482-10(h) § 60.482-10(m)	Leaks, as indicated by the specified instrument or by visual inspections, shall be repaired as soon as practicable except as provided in § 60.482-10(h). § 60.482-10(g)(1)-(2)	[G]§ 60.482-10(f) § 60.482-10(i) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.482-10(j) [G]§ 60.482-10(k) [G]§ 60.482-10(l) [G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
OLEFLEX-FU	EU	60VVALL	VOC	40 CFR Part 60, Subpart VV	§ 60.482-10(d) § 60.18 § 60.482-1(a) § 60.482-1(b) § 60.482-10(e)	Flares used to comply with this subpart shall comply with the requirements of §60.18.	§ 60.485(a) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) [G]§ 60.485(g)	[G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.482-10(m)				
OLEFLEX-FU	EU	60VVALL	VOC	40 CFR Part 60, Subpart VV	[G]§ 60.482-3 § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-9	Compressors shall comply with the requirements outlined in § 60.482-3(a)-(j).	[G]§ 60.482-3 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
OLEFLEX-FU	EU	60VVALL	VOC	40 CFR Part 60, Subpart VV	[G]§ 60.482-6 § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-9	Open-ended valves or lines shall comply with the requirements outlined in § 60.482-6(a)-(c).	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
OLEFLEX-FU	EU	60VVALL	VOC	40 CFR Part 60, Subpart VV	[G]§ 60.482-7 § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-9 [G]§ 60.483-1 [G]§ 60.483-2	Valves in gas/vapor service and in light liquid service shall comply with the requirements outlined in § 60.482-7(a)-(h).	[G]§ 60.482-7 [G]§ 60.483-1 [G]§ 60.483-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) [G]§ 60.486(g) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(d) § 60.487(e)
OLEFLEX-FU	EU	60VVALL	VOC	40 CFR Part 60, Subpart VV	§ 60.482-4(a) § 60.482-1(a) § 60.482-1(b) § 60.482-4(b)(1) § 60.482-4(b)(2) § 60.482-4(d)(1) § 60.482-4(d)(2) [G]§ 60.482-9	Except during pressure releases, each pressure relief device in gas/vapor service shall be operated with no detectable emissions, as indicated by an instrument reading of less than 500 ppm above background.	§ 60.482-4(b)(1) § 60.482-4(b)(2) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(3) [G]§ 60.486(e)(4) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
OLEFLEX-FU	EU	60VVALL	VOC	40 CFR Part 60, Subpart VV	[G]§ 60.482-8 § 60.482-1(a)	Pumps in heavy liquid service shall comply	[G]§ 60.482-8 § 60.485(a)	[G]§ 60.486(a) [G]§ 60.486(b)	§ 60.487(a) [G]§ 60.487(b)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.482-1(b) [G]§ 60.482-9	with the requirements of §60.482-8(a)-(d).	[G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j)	[G]§ 60.487(c) § 60.487(e)
OLEFLEX-FU	EU	60VVALL	VOC	40 CFR Part 60, Subpart VV	[G]§ 60.482-8 § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-9	Pressure relief devices in light-liquid service shall comply with the requirements of §60.482-8(a)-(d).	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
OLEFLEX-FU	EU	60VVALL	VOC	40 CFR Part 60, Subpart VV	[G]§ 60.482-8 § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-9	Pressure relief devices in heavy liquid service shall comply with the requirements of §60.482-8(a)-(d).	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
OLEFLEX-FU	EU	60VVALL	VOC	40 CFR Part 60, Subpart VV	[G]§ 60.482-8 § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-9	Flanges and other connectors shall comply with the requirements of §60.482-8(a)-(d).	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
OLEFLEX-FU	EU	60VVALL	VOC	40 CFR Part 60, Subpart VV	[G]§ 60.482-8 § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-9	Valves in heavy liquid service shall comply with the requirements of §60.482-8(a)-(d).	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
OLEFLEX-FU	EU	60VVALL	VOC	40 CFR Part 60, Subpart VV	[G]§ 60.482-5 § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-9	Sampling connection systems shall be in compliance with the requirements outlined in § 60.482-5(a)-(c).	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
RAIL-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B	§ 115.322(1) § 115.322(2) § 115.322(3)	No valve (gaseous service) may be allowed to have a VOC leak as	[G]§ 115.324(2) § 115.324(4) § 115.324(5)	§ 115.326(1) [G]§ 115.326(2) § 115.326(3)	§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Counties	§ 115.322(4) § 115.322(5)	defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324(6) [G]§ 115.324(7) [G]§ 115.325	§ 115.326(4)	
RAIL-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.327(1)	Valves of nominal size of 2" (5 cm) or less are exempt, provided allowable emissions from sources affected by this division after controls are applied with exemptions will not exceed by more than 5.0% such allowable emissions with no exemptions.	None	None	§ 115.327(1)(A) § 115.327(1)(B) § 115.327(1)(C)
RAIL-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No pump seal, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
RAIL-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No pump seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(A) § 115.324(3) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
RAIL-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(5)	No valve (gaseous service), as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						§101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).			
RAIL-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.322(5)	No valve (gaseous service) may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
RAIL-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No valve in liquid service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
RAIL-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No valve in liquid service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
RAIL-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No process drain, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
RAIL-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No process drain may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(C) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
RAIL-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3) § 115.327(6)	No compressor seal, as described in § 115.327(3), (5) or (6), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
RAIL-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No compressor seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(A) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
RAIL-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No elevated valve, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
RAIL-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No elevated valve may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as	§ 115.324 § 115.324(1) § 115.324(1)(D) § 115.324(4) § 115.324(6) [G]§ 115.324(7)	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						provided in §115.322(2).	[G]§ 115.325		
RAIL-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(5)	No pressure relief valve in gaseous service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
RAIL-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(5)	No pressure relief valve in gaseous service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(C) § 115.324(4) § 115.324(5) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
RAIL-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No connector, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
RAIL-FUG	EU	63CCALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(c)(1) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.163 [G]§ 63.171 [G]§ 63.176 § 63.648(f)	Comply with the specified Subpart H requirements for pumps in light liquid service, instrument readings that define a leak are specified in Subpart CC, table 2.	[G]§ 63.163 [G]§ 63.176 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(3) § 63.648(c)(4) § 63.648(c)(6) § 63.648(c)(7) § 63.648(c)(8)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(3) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(v)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.655(d)(2)			§ 63.181(h)(8) § 63.181(h)(9) § 63.648(h) § 63.655(d)(1)(i) § 63.655(d)(6) § 63.655(i)(5)	
RAIL-FUG	EU	63CCALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for non-reciprocating pumps in heavy liquid service.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(6)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
RAIL-FUG	EU	63CCALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.164 [G]§ 63.171 § 63.648(i) § 63.655(d)(2)	Comply with the specified Subpart H requirements for compressors which are not in hydrogen service.	[G]§ 63.164 [G]§ 63.180(b) [G]§ 63.180(c) [G]§ 63.180(d) [G]§ 63.648(b)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(f) § 63.648(h) § 63.655(d)(1)(i) § 63.655(d)(6) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
RAIL-FUG	EU	63CCALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.165 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for pressure relief devices in gas/vapor service.	[G]§ 63.165 [G]§ 63.180(b) [G]§ 63.180(c) [G]§ 63.180(d) [G]§ 63.648(b)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(f) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
RAIL-FUG	EU	63CCALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g)	Comply with the specified Subpart H requirements for pressure relief device in liquid service.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.655(d)(2)		§ 63.648(c)(6)	§ 63.655(d)(1)(i) § 63.655(i)(5)	
RAIL-FUG	EU	63CCALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.166 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for sampling connection systems.	[G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(i) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
RAIL-FUG	EU	63CCALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.167 [G]§ 63.171 [G]§ 63.175 § 63.655(d)(2)	Comply with the specified Subpart H requirements for open-ended valves and lines.	[G]§ 63.175 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(9) [G]§ 63.181(i) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
RAIL-FUG	EU	63CCALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(c)(1) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.168 [G]§ 63.171 [G]§ 63.175 § 63.648(c)(9) § 63.655(d)(2)	Comply with the specified Subpart H requirements for valves in gas/vapor and light liquid service, instrument readings defining a leak are specified in Subpart CC, table 2.	[G]§ 63.168 [G]§ 63.175 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(3) § 63.648(c)(4) § 63.648(c)(8)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(9)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(v)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
								§ 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	
RAIL-FUG	EU	63CCALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for valves in heavy liquid service.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(6)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
RAIL-FUG	EU	63CCALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(c)(5) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.649(a) § 63.655(d)(2)	Connectors in gas/vapor or light liquid are subject to the requirements in heavy liquid service in §63.169. The leak definition for specified systems subject to §63.169 is 1,000 parts per million.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(4)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(v)
RAIL-FUG	EU	63CCALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for connectors in heavy liquid service.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(6)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
RAIL-FUG	EU	63CCALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169	Comply with the specified Subpart H requirements for instrumentation systems.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(6)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 63.171 § 63.655(d)(2)				
RAIL-FUG	EU	63CCALL	112(B) HAPS	40 CFR Part 63, Subpart CC	[G]§ 63.648(g)	Compressors in hydrogen service are exempt from the requirements of §63.648(a) and (c), if an owner or operator demonstrates that a compressor is in hydrogen service. §63.648(g)(1)-(2).	[G]§ 63.648(g)	§ 63.648(h) § 63.655(d)(3)	None
WWTP-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.322(5)	No valve (gaseous service) may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.324(2) § 115.324(4) § 115.324(5) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	§ 115.326(1) [G]§ 115.326(2) § 115.326(3) § 115.326(4)	§ 115.326(1) § 115.327(4)
WWTP-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.327(1)	Valves of nominal size of 2" (5 cm) or less are exempt, provided allowable emissions from sources affected by this division after controls are applied with exemptions will not exceed by more than 5.0% such allowable emissions with no exemptions.	None	None	§ 115.327(1)(A) § 115.327(1)(B) § 115.327(1)(C)
WWTP-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No pump seal, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						days after the leak is found, except as provided in §115.322(2).			
WWTP-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No pump seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(A) § 115.324(3) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
WWTP-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(5)	No valve (gaseous service), as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
WWTP-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.322(5)	No valve (gaseous service) may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
WWTP-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No valve in liquid service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
WWTP-FUG	EU	R5322ALL	VOC	30 TAC Chapter	§ 115.322(1)	No valve in liquid	§ 115.324	[G]§ 115.326(1)	[G]§ 115.324(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				115, Fugitives Pet Ref B Counties	§ 115.322(2) § 115.322(3) § 115.322(4)	service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324(1) § 115.324(1)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
WWTP-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No process drain, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
WWTP-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No process drain may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(C) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
WWTP-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3) § 115.327(6)	No compressor seal, as described in § 115.327(3), (5) or (6), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
WWTP-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No compressor seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as	§ 115.324 § 115.324(2) § 115.324(2)(A) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						provided in §115.322(2).			
WWTP-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No elevated valve, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
WWTP-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No elevated valve may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(D) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
WWTP-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(5)	No pressure relief valve in gaseous service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
WWTP-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(5)	No pressure relief valve in gaseous service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(C) § 115.324(4) § 115.324(5) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
WWTP-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives	§ 115.322(1) § 115.322(2)	No connector, as described in § 115.327(3)	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Pet Ref B Counties	§ 115.322(3) § 115.327(3)	or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).			
SRU	EU	REG2	SO2	30 TAC Chapter 112, Sulfur Compounds	§ 112.7(a) § 112.7(b)	No person may cause, suffer, allow, or permit emissions of SO2 to exceed the emission limits specified for stack effluent flow rates < 4,000 scfm as determined by the specified equation.	§ 112.2(a) ** See CAM Summary	§ 112.2(c)	§ 112.2(b)
SRU3	EU	REG2	SO2	30 TAC Chapter 112, Sulfur Compounds	§ 112.7(a) § 112.7(b)	No person may cause, suffer, allow, or permit emissions of SO2 to exceed the emission limits specified for stack effluent flow rates < 4,000 scfm as determined by the specified equation.	§ 112.2(a) ** See CAM Summary	§ 112.2(c)	§ 112.2(b)
BARGEDOCKS	EU	61BB	BENZENE	40 CFR Part 61, Subpart BB	§ 61.300(b)	Any affected facility as per § 61.300(a), loading only liquid containing < 70 weight-percent benzene is exempt from this subpart, except for the recordkeeping and reporting in § 61.305(i).	None	[G]§ 61.305(i)	[G]§ 61.305(i)
BARGEDOCKS	EU	63CC	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.651(a)	Except as provided in §63.651(b)-(d), each owner or operator of a marine tank vessel loading operation	§ 63.642(d)(1) § 63.642(d)(3) § 63.642(d)(4)	§ 63.642(e) § 63.655(c) § 63.655(i)(5)	§ 63.642(d)(2) § 63.642(f) § 63.655(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						located at a petroleum refinery shall comply with the requirements of §63.560 through §63.567.			
BARGEDOCKS	EU	63Ya	EXEMPT	40 CFR Part 63, Subpart Y	§ 63.560(a)(2) § 153.282 § 63.560(a)(4)	Existing sources with emissions less than 10 and 25 tons must meet the submerged fill standards of 46 CFR 153.282. This submerged fill requirement does not apply to petroleum refineries.	§ 63.565(l)	§ 63.567(j)(4)	None
BARGEDOCKS	EU	63Yb	112(B) HAPS	40 CFR Part 63, Subpart Y	§ 63.562(b) [G]§ 63.562(b)(1) § 63.562(b)(2) § 63.562(b)(5) [G]§ 63.562(b)(6) § 63.562(e) § 63.562(e)(1) [G]§ 63.562(e)(2) [G]§ 63.562(e)(3) § 63.562(e)(4) § 63.562(e)(5) § 63.562(e)(6) § 63.562(e)(7) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) [G]§ 63.563(a)(1) § 63.563(a)(2) § 63.563(a)(3)	Marine tank vessel loading operations shall apply MACT standards, except for the VMT source.	[G]§ 63.562(b)(6) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) § 63.563(b)(10) § 63.563(b)(3) § 63.563(b)(6) § 63.563(b)(6)(i) § 63.563(b)(6)(iii) [G]§ 63.563(c) § 63.564(a)(2) § 63.564(a)(3) § 63.564(a)(4) § 63.564(b)(3) § 63.564(c) [G]§ 63.565(b) § 63.565(l)	[G]§ 63.562(b)(6) § 63.562(e)(5) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) § 63.564(b)(3) § 63.567(f) [G]§ 63.567(g) § 63.567(j)(1) § 63.567(j)(2) [G]§ 63.567(k)	[G]§ 63.562(b)(6) § 63.562(e)(7)(ii) § 63.567(b)(5) § 63.567(c) § 63.567(e)(1) [G]§ 63.567(e)(2) § 63.567(e)(3) § 63.567(e)(4) § 63.567(e)(5) § 63.567(e)(6) § 63.567(f) § 63.567(j)(3) § 63.567(m) § 63.567(m) § 63.567(n)(1) § 63.567(n)(2)
BARGEDOCKS	EU	63Yb	VOC	40 CFR Part 63, Subpart Y	§ 63.562(c) [G]§ 63.562(c)(2) § 63.562(c)(3) § 63.562(c)(4) [G]§ 63.562(c)(6) § 63.562(e)	RACT standards, except the VMT source.	[G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) § 63.563(b)(3) § 63.563(b)(6) § 63.563(b)(6)(i) § 63.563(b)(6)(iii)	§ 63.562(e)(5) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) § 63.564(b)(3) § 63.567(f) [G]§ 63.567(g)	§ 63.562(c)(1) § 63.562(e)(7)(ii) [G]§ 63.567(b)(2) § 63.567(b)(3) [G]§ 63.567(b)(4) § 63.567(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.562(e)(1) [G]§ 63.562(e)(2) [G]§ 63.562(e)(3) § 63.562(e)(4) § 63.562(e)(5) § 63.562(e)(6) § 63.562(e)(7) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) [G]§ 63.563(a)(1) § 63.563(a)(2) § 63.563(a)(3)		[G]§ 63.563(c) § 63.564(a)(2) § 63.564(a)(3) § 63.564(a)(4) § 63.564(b)(3) § 63.564(c) [G]§ 63.565(b) § 63.565(l)	§ 63.567(j)(1) [G]§ 63.567(k)	§ 63.567(e)(1) [G]§ 63.567(e)(2) § 63.567(e)(3) § 63.567(e)(4) § 63.567(e)(5) § 63.567(e)(6) § 63.567(f) § 63.567(m) § 63.567(n)(1) § 63.567(n)(2)
RAILRACK1	EU	R5211	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(b)(3)(A) § 115.212(b)(2) § 115.214(b)(1)(B) § 115.214(b)(1)(D) § 115.214(b)(1)(D)(i)	Plants, excluding gasoline bulk plants, which load <20,000 gallons of VOC into transport vessels per day with a true vapor pressure of 1.5 psia or greater are exempt from this division, except for the specified requirements.	§ 115.214(b)(1)(A) § 115.214(b)(1)(A)(i) § 115.215 § 115.215(4)	§ 115.216 § 115.216(2) § 115.216(3)(B) § 115.216(3)(D)	None
SHIPDOCKS	EU	61BB	BENZENE	40 CFR Part 61, Subpart BB	§ 61.300(b)	Any affected facility as per § 61.300(a), loading only liquid containing < 70 weight-percent benzene is exempt from this subpart, except for the recordkeeping and reporting in § 61.305(i).	None	[G]§ 61.305(i)	[G]§ 61.305(i)
SHIPDOCKS	EU	63CC	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.651(a)	Except as provided in §63.651(b)-(d), each owner or operator of a marine tank vessel loading operation located at a petroleum refinery shall comply with the requirements of	§ 63.642(d)(1) § 63.642(d)(3) § 63.642(d)(4)	§ 63.642(e) § 63.655(c) § 63.655(i)(5)	§ 63.642(d)(2) § 63.642(f) § 63.655(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						§63.560 through §63.567.			
SHIPDOCKS	EU	63Ya	EXEMPT	40 CFR Part 63, Subpart Y	§ 63.560(a)(2) § 153.282 § 63.560(a)(4)	Existing sources with emissions less than 10 and 25 tons must meet the submerged fill standards of 46 CFR 153.282. This submerged fill requirement does not apply to petroleum refineries.	§ 63.565(l)	§ 63.567(j)(4)	None
SHIPDOCKS	EU	63Yb	112(B) HAPS	40 CFR Part 63, Subpart Y	§ 63.562(b) [G]§ 63.562(b)(1) § 63.562(b)(2) § 63.562(b)(5) [G]§ 63.562(b)(6) § 63.562(e) § 63.562(e)(1) [G]§ 63.562(e)(2) [G]§ 63.562(e)(3) § 63.562(e)(4) § 63.562(e)(5) § 63.562(e)(6) § 63.562(e)(7) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) [G]§ 63.563(a)(1) § 63.563(a)(2) § 63.563(a)(3)	Marine tank vessel loading operations shall apply MACT standards, except for the VMT source.	[G]§ 63.562(b)(6) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) § 63.563(b)(10) § 63.563(b)(3) § 63.563(b)(6) § 63.563(b)(6)(i) § 63.563(b)(6)(iii) [G]§ 63.563(c) § 63.564(a)(2) § 63.564(a)(3) § 63.564(a)(4) § 63.564(b)(3) § 63.564(c) [G]§ 63.565(b) § 63.565(l)	[G]§ 63.562(b)(6) § 63.562(e)(5) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) § 63.564(b)(3) § 63.567(f) [G]§ 63.567(g) § 63.567(j)(1) § 63.567(j)(2) [G]§ 63.567(k)	[G]§ 63.562(b)(6) § 63.562(e)(7)(ii) § 63.567(b)(5) § 63.567(c) § 63.567(e)(1) [G]§ 63.567(e)(2) § 63.567(e)(3) § 63.567(e)(4) § 63.567(e)(5) § 63.567(e)(6) § 63.567(f) § 63.567(j)(3) § 63.567(m) § 63.567(n)(1) § 63.567(n)(2)
SHIPDOCKS	EU	63Yb	VOC	40 CFR Part 63, Subpart Y	§ 63.562(c) [G]§ 63.562(c)(2) § 63.562(c)(3) § 63.562(c)(4) [G]§ 63.562(c)(6) § 63.562(e) § 63.562(e)(1) [G]§ 63.562(e)(2) [G]§ 63.562(e)(3)	RACT standards, except the VMT source.	[G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) § 63.563(b)(3) § 63.563(b)(6) § 63.563(b)(6)(i) § 63.563(b)(6)(iii) [G]§ 63.563(c) § 63.564(a)(2) § 63.564(a)(3)	§ 63.562(e)(5) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) § 63.564(b)(3) § 63.567(f) [G]§ 63.567(g) § 63.567(j)(1) [G]§ 63.567(k)	§ 63.562(c)(1) § 63.562(e)(7)(ii) [G]§ 63.567(b)(2) § 63.567(b)(3) [G]§ 63.567(b)(4) § 63.567(c) § 63.567(e)(1) [G]§ 63.567(e)(2) § 63.567(e)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.562(e)(4) § 63.562(e)(5) § 63.562(e)(6) § 63.562(e)(7) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) [G]§ 63.563(a)(1) § 63.563(a)(2) § 63.563(a)(3)		§ 63.564(a)(4) § 63.564(b)(3) § 63.564(c) [G]§ 63.565(b) § 63.565(l)		§ 63.567(e)(4) § 63.567(e)(5) § 63.567(e)(6) § 63.567(f) § 63.567(m) § 63.567(n)(1) § 63.567(n)(2)
T-RACK	EU	R5211a	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.211(2) § 115.212(b)(3)(A) § 115.212(b)(3)(A)(i) § 115.212(b)(3)(B) [G]§ 115.212(b)(3)(C) § 115.212(b)(3)(E) § 115.212(b)(4)(A) § 115.212(b)(4)(B) § 115.212(b)(4)(C) § 115.214(b)(1)(B) § 115.214(b)(1)(C)	Gasoline terminals, in the covered attainment counties, shall ensure that VOC emissions do not exceed 0.17lb/1,000gal, and until 4/30/00 in Gregg, Nueces, and Victoria Counties 0.67lb/1,000gal.	§ 115.212(b)(3)(B) § 115.212(b)(4)(C) § 115.214(b)(1)(A) § 115.214(b)(1)(A)(i) § 115.214(b)(1)(A)(ii) § 115.214(b)(1)(A)(iii) § 115.214(b)(2) § 115.215 § 115.215(1) § 115.215(10) [G]§ 115.215(2) § 115.215(4) § 115.215(5) § 115.215(6) § 115.215(9) § 115.216(1) § 115.216(1)(A) § 115.216(1)(A)(iv) ** See CAM Summary	§ 115.216 § 115.216(1) § 115.216(1)(A) § 115.216(1)(A)(iv) § 115.216(2) § 115.216(3)(A) § 115.216(3)(A)(i) § 115.216(3)(A)(ii) § 115.216(3)(A)(iii) § 115.216(3)(B) [G]§ 115.216(3)(E)	None
T-RACK	EU	R5211b	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(b)(2) § 115.212(b)(2) § 115.214(b)(1)(B) § 115.214(b)(1)(D) § 115.214(b)(1)(D)(i)	Vapor pressure (at land-based operations). All land-based loading and unloading of VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division except as specified.	§ 115.214(b)(1)(A) § 115.214(b)(1)(A)(i) § 115.215 § 115.215(4)	§ 115.216 § 115.216(2) § 115.216(3)(B)	None
T-RACK	EU	R5211c	VOC	30 TAC Chapter 115, Loading	§ 115.217(b)(4) § 115.212(b)(2)	Crude oil, condensate, and liquefied petroleum	§ 115.214(b)(1)(A) § 115.214(b)(1)(A)(i)	§ 115.216 § 115.216(3)(A)(ii)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				and Unloading of VOC	§ 115.214(b)(1)(B) § 115.214(b)(1)(D) § 115.214(b)(1)(D)(i)	gas. All loading and unloading of crude oil, condensate, and liquefied petroleum gas is exempt from division, except for the specified requirements.		§ 115.216(3)(B)	
T-RACK	EU	63CC	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.650(a) § 60.502(a) § 60.502(d) § 60.502(g) § 60.502(h) § 60.502(i) § 63.422(a) § 63.422(b) § 63.427(b)	A gasoline loading rack classified under SIC 2911 located within a contiguous area and under common control with a petroleum refinery shall comply with specified sections.	§ 60.503(a) § 60.503(b) § 60.503(d) § 60.503(d)(1) § 60.503(d)(2) § 63.425(a) § 63.425(b) § 63.425(b)(1) § 63.425(b)(2) § 63.425(b)(3) § 63.427(a) § 63.427(a)(3) § 63.427(b) § 63.642(d)(1) § 63.642(d)(3) § 63.642(d)(4)	§ 60.503(d)(2) § 63.425(b)(1) § 63.425(c) § 63.428(c)(1) § 63.428(c)(2) § 63.428(c)(2)(i) § 63.642(e) § 63.655(b) § 63.655(i)(5)	§ 63.428(c)(2) § 63.428(c)(2)(i) § 63.428(h)(1) § 63.642(d)(2) § 63.642(f) § 63.655(b)
GRP-RRR	EP	60RRRa	VOC/TOC	40 CFR Part 60, Subpart RRR	§ 60.702(a) [G]§ 60.704(b)(5)	For each vent stream, reduce TOC by 98%w or to a TOC concentration of 20 ppmv, on a dry basis corrected to 3% oxygen, whichever is less stringent. If a boiler or process heater is used, introduce vent stream as specified.	§ 60.703(c) § 60.704(a) § 60.704(b) § 60.704(b)(1) § 60.704(b)(2) § 60.704(b)(3) [G]§ 60.704(b)(4)	§ 60.705(b) § 60.705(b)(2)(i) § 60.705(c) § 60.705(c)(4) § 60.705(s)	§ 60.705(a) § 60.705(b) § 60.705(b)(2)(i) § 60.705(c) § 60.705(c)(4) § 60.705(k) § 60.705(l) § 60.705(l)(1) § 60.705(s)
GRP-RRR	EP	60RRRb	VOC/TOC	40 CFR Part 60, Subpart RRR	§ 60.702(a) [G]§ 60.704(b)(5)	For each vent stream, reduce TOC by 98%w or to a TOC concentration of 20 ppmv, on a dry basis corrected to 3% oxygen, whichever is	§ 60.703(c) § 60.704(a) § 60.704(b) § 60.704(b)(1) § 60.704(b)(2) § 60.704(b)(3)	§ 60.705(b) § 60.705(b)(2)(i) § 60.705(c) § 60.705(c)(4) § 60.705(s)	§ 60.705(a) § 60.705(b) § 60.705(b)(2)(i) § 60.705(c) § 60.705(c)(4) § 60.705(k)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						less stringent. If a boiler or process heater is used, introduce vent stream as specified.	[G]§ 60.704(b)(4)		§ 60.705(l) § 60.705(l)(1) § 60.705(s)
GRP-RRR	EP	60RRRc	VOC/TOC	40 CFR Part 60, Subpart RRR	§ 60.702(b) § 60.18	For each vent stream, combust the emissions in a flare that meets the requirements of §60.18.	§ 60.703(b) § 60.703(b)(1) § 60.704(a) § 60.704(c) [G]§ 60.704(d)	§ 60.705(b) § 60.705(b)(3) § 60.705(e) § 60.705(s)	§ 60.705(a) § 60.705(b) § 60.705(b)(3) § 60.705(k) § 60.705(l) § 60.705(l)(3) § 60.705(s)
DEGREASE-F	EU	R5412	VOC	30 TAC Chapter 115, Degreasing Processes	§ 115.417(5)	In Gregg, Nueces, and Victoria Counties, operations which can emit, when uncontrolled, a combined weight of VOC < 550 pounds in any consecutive 24-hour period are exempt from § 115.412.	None	§ 115.416 § 115.416(3)	None
16-P-11-EN	EU	63-ZZZZ	EXEMPT	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(b)(1) § 63.6595(c) § 63.6605(b) [G]§ 63.6640(f)(1)	An affected source which meets either of the criteria in paragraph (b)(1)(i) through (ii) of this section does not have to meet the requirements of this subpart and of subpart A of this part except for the initial notification requirements of 63.6645(d).	None	None	§ 63.6645(c) § 63.6645(f)
16-P-12-EN	EU	63-ZZZZ	EXEMPT	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(b)(1) § 63.6595(c) § 63.6605(b) [G]§ 63.6640(f)(1)	An affected source which meets either of the criteria in paragraph (b)(1)(i) through (ii) of this section does not	None	None	§ 63.6645(c) § 63.6645(f)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						have to meet the requirements of this subpart and of subpart A of this part except for the initial notification requirements of 63.6645(d).			
16-P-13-EN	EU	63-ZZZZ	EXEMPT	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(b)(1) § 63.6595(c) § 63.6605(b) [G]§ 63.6640(f)(1)	An affected source which meets either of the criteria in paragraph (b)(1)(i) through (ii) of this section does not have to meet the requirements of this subpart and of subpart A of this part except for the initial notification requirements of 63.6645(d).	None	None	§ 63.6645(c) § 63.6645(f)
16-P-14-EN	EU	63-ZZZZ	EXEMPT	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(b)(1) § 63.6595(c) § 63.6605(b) [G]§ 63.6640(f)(1)	An affected source which meets either of the criteria in paragraph (b)(1)(i) through (ii) of this section does not have to meet the requirements of this subpart and of subpart A of this part except for the initial notification requirements of 63.6645(d).	None	None	§ 63.6645(c) § 63.6645(f)
16-P-4-EN	EU	63-ZZZZ	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6602-Table2c.1 § 63.6595(a)(1) § 63.6605(a) § 63.6605(b) § 63.6625(e) § 63.6625(h) § 63.6625(i) § 63.6640(b)	For each existing emergency stationary CI RICE and black start stationary CI RICE, located at a major source, you must comply with the requirements as specified in Table 2c.1.a-	§ 63.6625(f) § 63.6625(i) § 63.6640(a) § 63.6640(a)-Table6.9.a.i § 63.6640(a)-Table6.9.a.ii § 63.6640(b)	§ 63.6625(i) § 63.6655(a) § 63.6655(a)(1) § 63.6655(a)(2) § 63.6655(a)(4) § 63.6655(a)(5) § 63.6655(d) § 63.6655(e)	§ 63.6640(b) § 63.6640(e) § 63.6650(f)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 63.6640(f)(1)	c.		§ 63.6655(f) § 63.6660(a) § 63.6660(b) § 63.6660(c)	
16-P-7-EN	EU	63-ZZZZ	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6602-Table2c.1 § 63.6595(a)(1) § 63.6605(a) § 63.6605(b) § 63.6625(e) § 63.6625(h) § 63.6625(i) § 63.6640(b) [G]§ 63.6640(f)(1)	For each existing emergency stationary CI RICE and black start stationary CI RICE, located at a major source, you must comply with the requirements as specified in Table 2c.1.a-c.	§ 63.6625(f) § 63.6625(i) § 63.6640(a) § 63.6640(a)-Table6.9.a.i § 63.6640(a)-Table6.9.a.ii § 63.6640(b)	§ 63.6625(i) § 63.6655(a) § 63.6655(a)(1) § 63.6655(a)(2) § 63.6655(a)(4) § 63.6655(a)(5) § 63.6655(d) § 63.6655(e) § 63.6655(f) § 63.6660(a) § 63.6660(b) § 63.6660(c)	§ 63.6640(b) § 63.6640(e) § 63.6650(f)
83P136A-EN	EU	60-IIII	CO, PM, NOx+NMHC	40 CFR Part 60, Subpart IIII	§ 60.4200(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 60, Subpart IIII	The permit holder shall comply with the applicable requirements of 40 CFR Part 60, Subpart IIII	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 60, Subpart IIII	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 60, Subpart IIII	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 60, Subpart IIII
83P136A-EN	EU	60-IIII	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(c)	A new/reconstructed stationary RICE located at an area source, or located at a major source of HAP emissions and is a spark ignition (SI) 2SLB < 500 HP, SI 4 SLB < 250 HP, or 4SRB, compression ignition (CI), emergency or limited use, or which combusts landfill or digester gas at > 10% of	None	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						the gross heat input < 500 HP must meet the requirements of this part by meeting the requirements of 40 CFR Part 60, Subpart IIII, for CI engines or 40 CFR Part 60, Subpart JJJJ, for SI engines.			
83P136B-EN	EU	60-IIII	CO, PM, NOx+NMHC	40 CFR Part 60, Subpart IIII	§ 60.4200(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 60, Subpart IIII	The permit holder shall comply with the applicable requirements of 40 CFR Part 60, Subpart IIII	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 60, Subpart IIII	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 60, Subpart IIII	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 60, Subpart IIII
83P136B-EN	EU	60-IIII	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(c)	A new/reconstructed stationary RICE located at an area source, or located at a major source of HAP emissions and is a spark ignition (SI) 2SLB < 500 HP, SI 4 SLB < 250 HP, or 4SRB, compression ignition (CI), emergency or limited use, or which combusts landfill or digester gas at > 10% of the gross heat input < 500 HP must meet the requirements of this part by meeting the requirements of 40 CFR Part 60, Subpart IIII, for CI engines or 40 CFR	None	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						Part 60, Subpart JJJJ, for SI engines.			
03-TK-156	EU	R5112-a	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
03-TK-156	EU	R5112-b	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
03-TK-156	EU	R5112-c	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
03-TK-156	EU	60KB-b	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)		
03-TK-156	EU	60KB-c	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)
03-TK-156	EU	60KB-d	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)
03-TK-156	EU	63CC	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) § 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) § 63.640(n)(8)(ii)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)
03-TK-156	EU	63CC-b	112(B)	40 CFR Part 63,	§ 63.640(n)(8)	Vessels described by §	§ 60.113b(a)(1)	§ 60.115b	§ 60.113b(a)(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
			HAPS	Subpart CC	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	§ 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) § 63.640(n)(8)(ii)	§ 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)
03-TK-161	EU	R5112-a	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
03-TK-161	EU	R5112-b	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
03-TK-161	EU	R5112-c	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					requirements of 30 TAC Chapter 115, Storage of VOCs				
03-TK-161	EU	60KB-b	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)
03-TK-161	EU	60KB-c	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)
03-TK-161	EU	60KB-d	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)
03-TK-161	EU	63CC	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) § 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	for in §63.640(n)(8)(i)-(vi).	§ 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) § 63.640(n)(8)(ii)		§ 63.640(n)(8)(iv) § 63.640(n)(8)(v)
03-TK-161	EU	63CC-b	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) § 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) § 63.640(n)(8)(ii)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)
43-TK-04	EU	R5112-a	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
50-TK-60	EU	R5112-a	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					TAC Chapter 115, Storage of VOCs				
50-TK-60	EU	R5112-b	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
50-TK-60	EU	R5112-c	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
50-TK-60	EU	60KA-b	VOC	40 CFR Part 60, Subpart Ka	§ 60.110a(a)	The affected facility is each storage vessel for petroleum liquids that has a storage capacity > 151,416 L (40,000 gal) and for which construction commenced after 5/18/78 and prior to 7/23/84.	§ 60.115a(a) § 60.115a(b)	§ 60.115a(a)	None
50-TK-60	EU	60KA-c	VOC	40 CFR Part 60, Subpart Ka	§ 60.112a(a)(2)	Vessels storing petroleum liquids with a TVP > 10.3 kPa (1.5 psia) but < 76.6 kPa (11.1 psia) shall have a fixed roof and an internal	§ 60.115a(a) § 60.115a(b)	§ 60.115a(a)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						floating cover with the specified closure device and vents.			
50-TK-60	EU	60KA-d	VOC	40 CFR Part 60, Subpart Ka	§ 60.112a(a)(2)	Vessels storing petroleum liquids with a TVP > 10.3 kPa (1.5 psia) but < 76.6 kPa (11.1 psia) shall have a fixed roof and an internal floating cover with the specified closure device and vents.	§ 60.115a(a) § 60.115a(b)	§ 60.115a(a)	None
50-TK-60	EU	63CC	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.119(a)(1) [G]§ 63.119(b)(1) § 63.119(b)(2) § 63.119(b)(3)(i) § 63.119(b)(4) § 63.120(a)(4) § 63.120(a)(7) [G]§ 63.646(f) § 63.646(g)	Each owner or operator of a Group 1 storage vessel subject to this subpart shall comply with the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.120(a)(2)(i) § 63.120(a)(2)(ii) § 63.646(b)(1) § 63.646(e)	§ 63.120(a)(4) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1) § 63.655(i)(5)	§ 63.120(a)(5) § 63.120(a)(6) § 63.642(f) § 63.655(f) [G]§ 63.655(f)(1)(i)(B) § 63.655(f)(6) § 63.655(g) § 63.655(g)(2) [G]§ 63.655(g)(2)(i) [G]§ 63.655(g)(2)(ii) § 63.655(h) § 63.655(h)(1) § 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(B) § 63.655(h)(2)(i)(C) [G]§ 63.655(h)(6)
50-TK-61	EU	R5112-a	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
50-TK-61	EU	R5112-b	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
50-TK-61	EU	R5112-c	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
50-TK-61	EU	60KA-b	VOC	40 CFR Part 60, Subpart Ka	§ 60.110a(a)	The affected facility is each storage vessel for petroleum liquids that has a storage capacity > 151,416 L (40,000 gal) and for which construction commenced after 5/18/78 and prior to 7/23/84.	§ 60.115a(a) § 60.115a(b)	§ 60.115a(a)	None
50-TK-61	EU	60KA-c	VOC	40 CFR Part 60, Subpart Ka	§ 60.112a(a)(1) § 60.112a(a)(1)(i) § 60.112a(a)(1)(i)(A) § 60.112a(a)(1)(i)(C) § 60.112a(a)(1)(i)(D) § 60.112a(a)(1)(ii)(A) § 60.112a(a)(1)(ii)(B) § 60.112a(a)(1)(ii)(C) § 60.112a(a)(1)(ii)(D)	Vessels storing petroleum liquids with a TVP > 10.3 kPa (1.5 psia) but < 76.6 kPa (11.1 psia) shall be equipped with an external floating roof and closure device as specified.	§ 60.113a(a)(1) § 60.113a(a)(1)(i) § 60.113a(a)(1)(i)(A) § 60.113a(a)(1)(i)(B) § 60.113a(a)(1)(i)(C) § 60.113a(a)(1)(i)(D) § 60.113a(a)(1)(i)(E) § 60.113a(a)(1)(ii)(A) § 60.113a(a)(1)(ii)(B)	§ 60.113a(a)(1)(i)(D) § 60.115a(a)	§ 60.113a(a)(1)(i)(E) § 60.113a(a)(1)(iv)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.112a(a)(1)(iii) § 60.112a(a)(1)(iv)		§ 60.113a(a)(1)(ii)(C) § 60.113a(a)(1)(iii) § 60.113a(a)(1)(iv) § 60.115a(a) § 60.115a(b)		
50-TK-61	EU	60KA-d	VOC	40 CFR Part 60, Subpart Ka	§ 60.112a(a)(1) § 60.112a(a)(1)(i) § 60.112a(a)(1)(i)(A) § 60.112a(a)(1)(i)(C) § 60.112a(a)(1)(i)(D) § 60.112a(a)(1)(ii)(A) § 60.112a(a)(1)(ii)(B) § 60.112a(a)(1)(ii)(C) § 60.112a(a)(1)(ii)(D) § 60.112a(a)(1)(iii) § 60.112a(a)(1)(iv)	Vessels storing petroleum liquids with a TVP > 10.3 kPa (1.5 psia) but < 76.6 kPa (11.1 psia) shall be equipped with an external floating roof and closure device as specified.	§ 60.113a(a)(1) § 60.113a(a)(1)(i) § 60.113a(a)(1)(i)(A) § 60.113a(a)(1)(i)(B) § 60.113a(a)(1)(i)(C) § 60.113a(a)(1)(i)(D) § 60.113a(a)(1)(i)(E) § 60.113a(a)(1)(ii)(A) § 60.113a(a)(1)(ii)(B) § 60.113a(a)(1)(ii)(C) § 60.113a(a)(1)(iii) § 60.113a(a)(1)(iv) § 60.115a(a) § 60.115a(b)	§ 60.113a(a)(1)(i)(D) § 60.115a(a)	§ 60.113a(a)(1)(i)(E) § 60.113a(a)(1)(iv)
50-TK-61	EU	63CC	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.119(a)(1) § 63.119(c)(1) § 63.119(c)(1)(i) § 63.119(c)(1)(ii) § 63.119(c)(1)(iii) [G]§ 63.119(c)(3) § 63.119(c)(4) § 63.120(b)(10)(i) § 63.120(b)(5)(i) § 63.120(b)(5)(ii) § 63.120(b)(6)(i) § 63.120(b)(6)(ii) [G]§ 63.120(b)(7) § 63.120(b)(8) [G]§ 63.646(f) § 63.646(g)	Each owner or operator of a Group 1 storage vessel subject to this subpart shall comply with the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.120(b)(1)(i) § 63.120(b)(1)(iii) § 63.120(b)(1)(iv) § 63.120(b)(10) § 63.120(b)(2)(i) § 63.120(b)(2)(ii) § 63.120(b)(2)(iii) § 63.120(b)(3) § 63.120(b)(4) § 63.646(b)(1) § 63.646(e)	[G]§ 63.120(b)(7) § 63.120(b)(8) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1) § 63.655(i)(5)	§ 63.120(b)(10)(ii) § 63.120(b)(10)(iii) § 63.120(b)(9) § 63.642(f) § 63.655(f) [G]§ 63.655(f)(1)(i)(B) § 63.655(f)(6) § 63.655(g) [G]§ 63.655(g)(3) § 63.655(h) § 63.655(h)(1) § 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(B) § 63.655(h)(2)(i)(C) § 63.655(h)(2)(ii) [G]§ 63.655(h)(6)
70-TK-109	EU	R5112-a	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the	The permit holder shall comply with the applicable requirements	The permit holder shall comply with the applicable monitoring	The permit holder shall comply with the applicable	The permit holder shall comply with the applicable reporting

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	of 30 TAC Chapter 115, Storage of VOCs	and testing requirements of 30 TAC Chapter 115, Storage of VOCs	recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	requirements of 30 TAC Chapter 115, Storage of VOCs
70-TK-109	EU	R5112-b	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
70-TK-109	EU	R5112-c	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
70-TK-109	EU	60K-b	VOC	40 CFR Part 60, Subpart K	§ 60.110(c) § 60.110(c)(2)	Facilities under §60.110(a) of this section with a capacity, construction or modification date as given in §60.110(c)(1) or §60.110(c)(2) are subject to the requirements of this section.	§ 60.113(a) § 60.113(b)	§ 60.113(a)	None
70-TK-109	EU	60K-c	VOC	40 CFR Part 60, Subpart K	§ 60.112(a)(1)	Storage vessels holding petroleum liquids with a	§ 60.113(a) § 60.113(b)	§ 60.113(a)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						true vapor pressure of 78 mm Hg (1.5 psia) or greater but not greater than 570 mm Hg (11.1 psia) shall have a floating roof, a vapor recovery system, or their equivalents.	** See Periodic Monitoring Summary		
70-TK-109	EU	60K-d	VOC	40 CFR Part 60, Subpart K	§ 60.112(a)(1)	Storage vessels holding petroleum liquids with a true vapor pressure of 78 mm Hg (1.5 psia) or greater but not greater than 570 mm Hg (11.1 psia) shall have a floating roof, a vapor recovery system, or their equivalents.	§ 60.113(a) § 60.113(b) ** See Periodic Monitoring Summary	§ 60.113(a)	None
70-TK-109	EU	63CC	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.119(a)(1) [G]§ 63.119(b)(1) § 63.119(b)(2) § 63.119(b)(3)(i) § 63.119(b)(4) § 63.120(a)(4) § 63.120(a)(7) [G]§ 63.646(f) § 63.646(g)	Each owner or operator of a Group 1 storage vessel subject to this subpart shall comply with the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.120(a)(2)(i) § 63.120(a)(2)(ii) § 63.646(b)(1) § 63.646(e)	§ 63.120(a)(4) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1) § 63.655(i)(5)	§ 63.120(a)(5) § 63.120(a)(6) § 63.642(f) § 63.655(f) [G]§ 63.655(f)(1)(i)(B) § 63.655(f)(6) § 63.655(g) § 63.655(g)(2) [G]§ 63.655(g)(2)(i) [G]§ 63.655(g)(2)(ii) § 63.655(h) § 63.655(h)(1) § 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(B) § 63.655(h)(2)(i)(C) [G]§ 63.655(h)(6)
70-TK-110	EU	R5112-a	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation,	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115,	The permit holder shall comply with the applicable monitoring and testing	The permit holder shall comply with the applicable recordkeeping	The permit holder shall comply with the applicable reporting requirements of 30 TAC

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	Storage of VOCs	requirements of 30 TAC Chapter 115, Storage of VOCs	requirements of 30 TAC Chapter 115, Storage of VOCs	Chapter 115, Storage of VOCs
70-TK-110	EU	R5112-b	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
70-TK-110	EU	R5112-c	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
70-TK-110	EU	60KB-b	VOC	40 CFR Part 60, Subpart Kb	§ 60.110b(a)	Except for §60.110b(b), this subpart applies to vessels with a capacity greater than or equal to 75 cubic meters (19,800 gal) used to store VOLs for which construction/reconstruction/modification began after 7/23/84.	§ 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(d) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.116b(d)
70-TK-110	EU	60KB-c	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i)	Storage vessels specified in §60.112b(a) and	§ 60.113b(a)(1) § 60.113b(a)(2)	§ 60.115b § 60.115b(a)(2)	§ 60.113b(a)(2) § 60.113b(a)(5)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.115b § 60.115b(a)(1) § 60.115b(a)(3)
70-TK-110	EU	60KB-d	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)
70-TK-110	EU	63CC-a	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) § 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) § 63.640(n)(8)(ii)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)
70-TK-110	EU	63CC-b	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) § 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)		§ 60.116b(e)(2)(i) § 63.640(n)(8)(ii)		
70-TK-138	EU	R5112-a	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
70-TK-138	EU	60K-b	VOC	40 CFR Part 60, Subpart K	§ 60.110(c) § 60.110(c)(2)	Facilities under §60.110(a) of this section with a capacity, construction or modification date as given in §60.110(c)(1) or §60.110(c)(2) are subject to the requirements of this section.	§ 60.113(a) § 60.113(b)	§ 60.113(a)	None
70-TK-140	EU	R5112	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
70-TK-140	EU	63GGGGG-1	112(B) HAPS	40 CFR Part 63, Subpart GGGGG	§ 63.7886(b)(1)(i) The permit holder shall comply with the applicable limitation,	The permit holder shall comply with the applicable requirements of 40 CFR Part 63,	The permit holder shall comply with the applicable monitoring and testing	The permit holder shall comply with the applicable recordkeeping	The permit holder shall comply with the applicable reporting requirements of 40 CFR

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					standard and/or equipment specification requirements of 40 CFR Part 63, Subpart GGGGG	Subpart GGGGG	requirements of 40 CFR Part 63, Subpart GGGGG	requirements of 40 CFR Part 63, Subpart GGGGG	Part 63, Subpart GGGGG
70-TK-95	EU	R5112-a	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
70-TK-95	EU	60K-b	VOC	40 CFR Part 60, Subpart K	§ 60.110(c) § 60.110(c)(2)	Facilities under §60.110(a) of this section with a capacity, construction or modification date as given in §60.110(c)(1) or §60.110(c)(2) are subject to the requirements of this section.	§ 60.113(a) § 60.113(b)	§ 60.113(a)	None
73-TK-166	EU	R5112	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(b)(1) § 115.112(b)(2) § 115.112(b)(2)(A) § 115.112(b)(2)(B) § 115.112(b)(2)(C) § 115.112(b)(2)(D) § 115.112(b)(2)(E) § 115.112(b)(2)(F) § 115.114(b)(2)(A) § 115.114(b)(4)(A)	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	§ 115.114(b)(2) § 115.114(b)(3) § 115.114(b)(4) § 115.114(b)(4)(A) [G]§ 115.117	§ 115.118(b)(2) § 115.118(b)(4) § 115.118(b)(5)	§ 115.114(b)(2)(B) § 115.114(b)(4)(B)
73-TK-166	EU	60KB	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	§ 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.116b(b) § 60.116b(c)	§ 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)
73-TK-166	EU	63CC	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.119(a)(1) § 63.119(c)(1) § 63.119(c)(1)(i) § 63.119(c)(1)(ii) § 63.119(c)(1)(iii) § 63.119(c)(2) [G]§ 63.119(c)(3) § 63.119(c)(4) § 63.120(b)(10)(i) § 63.120(b)(5)(i) § 63.120(b)(5)(ii) § 63.120(b)(6)(i) § 63.120(b)(6)(ii) [G]§ 63.120(b)(7) § 63.120(b)(8) § 63.646(g)	Each owner or operator of a Group 1 storage vessel subject to this subpart shall comply with the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.120(b)(1)(i) § 63.120(b)(1)(iii) § 63.120(b)(1)(iv) § 63.120(b)(10) § 63.120(b)(2)(i) § 63.120(b)(2)(ii) § 63.120(b)(2)(iii) § 63.120(b)(3) § 63.120(b)(4) § 63.646(b)(1)	[G]§ 63.120(b)(7) § 63.120(b)(8) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1) § 63.655(i)(5)	§ 63.120(b)(10)(ii) § 63.120(b)(10)(iii) § 63.120(b)(9) § 63.642(f) § 63.655(f) [G]§ 63.655(f)(1)(i)(B) § 63.655(f)(6) § 63.655(g) [G]§ 63.655(g)(3) § 63.655(h) § 63.655(h)(1) § 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(B) § 63.655(h)(2)(i)(C) § 63.655(h)(2)(ii) [G]§ 63.655(h)(6)
73-TK-167	EU	R5112	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(b)(1) § 115.112(b)(2) § 115.112(b)(2)(A) § 115.112(b)(2)(B) § 115.112(b)(2)(C) § 115.112(b)(2)(D) § 115.112(b)(2)(E) § 115.112(b)(2)(F)	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	§ 115.114(b)(2) § 115.114(b)(3) § 115.114(b)(4) § 115.114(b)(4)(A) [G]§ 115.117	§ 115.118(b)(2) § 115.118(b)(4) § 115.118(b)(5)	§ 115.114(b)(2)(B) § 115.114(b)(4)(B)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.114(b)(2)(A) § 115.114(b)(4)(A)				
73-TK-167	EU	60KB	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)
73-TK-167	EU	63CC	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.119(a)(1) § 63.119(c)(1) § 63.119(c)(1)(i) § 63.119(c)(1)(ii) § 63.119(c)(1)(iii) § 63.119(c)(2) [G]§ 63.119(c)(3) § 63.119(c)(4) § 63.120(b)(10)(i) § 63.120(b)(5)(i) § 63.120(b)(5)(ii) § 63.120(b)(6)(i) § 63.120(b)(6)(ii) [G]§ 63.120(b)(7) § 63.120(b)(8) § 63.646(g)	Each owner or operator of a Group 1 storage vessel subject to this subpart shall comply with the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.120(b)(1)(i) § 63.120(b)(1)(iii) § 63.120(b)(1)(iv) § 63.120(b)(10) § 63.120(b)(2)(i) § 63.120(b)(2)(ii) § 63.120(b)(2)(iii) § 63.120(b)(3) § 63.120(b)(4) § 63.646(b)(1)	[G]§ 63.120(b)(7) § 63.120(b)(8) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1) § 63.655(i)(5)	§ 63.120(b)(10)(ii) § 63.120(b)(10)(iii) § 63.120(b)(9) § 63.642(f) § 63.655(f) [G]§ 63.655(f)(1)(i)(B) § 63.655(f)(6) § 63.655(g) [G]§ 63.655(g)(3) § 63.655(h) § 63.655(h)(1) § 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(B) § 63.655(h)(2)(i)(C) § 63.655(h)(2)(ii) [G]§ 63.655(h)(6)
83-TK-155	EU	R5112-a	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the	The permit holder shall comply with the applicable requirements	The permit holder shall comply with the applicable monitoring	The permit holder shall comply with the applicable	The permit holder shall comply with the applicable reporting

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	of 30 TAC Chapter 115, Storage of VOCs	and testing requirements of 30 TAC Chapter 115, Storage of VOCs	recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	requirements of 30 TAC Chapter 115, Storage of VOCs
83-TK-155	EU	R5112-b	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
83-TK-155	EU	R5112-c	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
83-TK-155	EU	60KB-b	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)		
83-TK-155	EU	60KB-c	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)
83-TK-155	EU	60KB-d	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
83-TK-155	EU	60QQQ	VOC	40 CFR Part 60, Subpart QQQ	§ 60.692-3(d) § 60.692-1(a) § 60.692-6(a) § 60.692-6(b) § 60.692-7(b)	Storage vessels, including slop oil tanks and other auxiliary tanks that are subject to the requirements of 40 CFR subparts K, Ka, or Kb, are not subject to the requirements of this section.	§ 60.692-3(a)(4) § 60.696(a)	§ 60.697(a) § 60.697(c) [G]§ 60.697(e) § 60.697(f)(1) [G]§ 60.697(f)(2)	§ 60.698(b)(1) § 60.698(e)
83-TK-155	EU	61FF	BENZENE	40 CFR Part 61, Subpart FF	§ 61.351(a) [G]§ 60.112b(a)(2) § 61.351(a)(2) § 61.351(b)	As an alternative to the standards for tanks specified in § 61.343, an owner or operator may elect to comply with one of the following §61.351(a)(1)-(3):	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6)	§ 60.115b [G]§ 60.115b(b)(3) § 61.356(k)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 61.357(e) § 61.357(f)
83-TK-162	EU	R5112-a	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
83-TK-162	EU	R5112-b	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115,	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					Storage of VOCs				
83-TK-162	EU	R5112-c	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
83-TK-162	EU	60KB-b	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)
83-TK-162	EU	60KB-c	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)		
83-TK-162	EU	60KB-d	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)
83-TK-162	EU	60QQQ	VOC	40 CFR Part 60, Subpart QQQ	§ 60.692-3(d) § 60.692-1(a) § 60.692-6(a) § 60.692-6(b) § 60.692-7(b)	Storage vessels, including slop oil tanks and other auxiliary tanks that are subject to the requirements of 40 CFR subparts K, Ka, or Kb, are not subject to the requirements of this section.	§ 60.692-3(a)(4) § 60.696(a)	§ 60.697(a) § 60.697(c) [G]§ 60.697(e) § 60.697(f)(1) [G]§ 60.697(f)(2)	§ 60.698(b)(1) § 60.698(e)
83-TK-162	EU	61FF	BENZENE	40 CFR Part 61, Subpart FF	§ 61.351(a) [G]§ 60.112b(a)(2) § 61.351(a)(2) § 61.351(b)	As an alternative to the standards for tanks specified in § 61.343, an owner or operator may elect to comply with one of the following §61.351(a)(1)-(3):	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B)	§ 60.115b [G]§ 60.115b(b)(3) § 61.356(k)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							[G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6)		§ 61.357(e) § 61.357(f)
83-TK-23	EU	R5112-a	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
83-TK-23	EU	R5112-b	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
83-TK-23	EU	R5112-c	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
83-TK-23	EU	60KA-b	VOC	40 CFR Part 60, Subpart Ka	§ 60.110a(a)	The affected facility is each storage vessel for petroleum liquids that has a storage capacity >	§ 60.115a(a) § 60.115a(b)	§ 60.115a(a)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						151,416 L (40,000 gal) and for which construction commenced after 5/18/78 and prior to 7/23/84.			
83-TK-23	EU	60KA-c	VOC	40 CFR Part 60, Subpart Ka	§ 60.112a(a)(1) § 60.112a(a)(1)(i) § 60.112a(a)(1)(i)(A) § 60.112a(a)(1)(i)(C) § 60.112a(a)(1)(i)(D) § 60.112a(a)(1)(ii)(A) § 60.112a(a)(1)(ii)(B) § 60.112a(a)(1)(ii)(C) § 60.112a(a)(1)(ii)(D) § 60.112a(a)(1)(iii) § 60.112a(a)(1)(iv)	Vessels storing petroleum liquids with a TVP > 10.3 kPa (1.5 psia) but < 76.6 kPa (11.1 psia) shall be equipped with an external floating roof and closure device as specified.	§ 60.113a(a)(1) § 60.113a(a)(1)(i) § 60.113a(a)(1)(i)(A) § 60.113a(a)(1)(i)(B) § 60.113a(a)(1)(i)(C) § 60.113a(a)(1)(i)(D) § 60.113a(a)(1)(i)(E) § 60.113a(a)(1)(ii)(A) § 60.113a(a)(1)(ii)(B) § 60.113a(a)(1)(ii)(C) § 60.113a(a)(1)(iii) § 60.113a(a)(1)(iv) § 60.115a(a) § 60.115a(b)	§ 60.113a(a)(1)(i)(D) § 60.115a(a)	§ 60.113a(a)(1)(i)(E) § 60.113a(a)(1)(iv)
83-TK-23	EU	60KA-d	VOC	40 CFR Part 60, Subpart Ka	§ 60.112a(a)(1) § 60.112a(a)(1)(i) § 60.112a(a)(1)(i)(A) § 60.112a(a)(1)(i)(C) § 60.112a(a)(1)(i)(D) § 60.112a(a)(1)(ii)(A) § 60.112a(a)(1)(ii)(B) § 60.112a(a)(1)(ii)(C) § 60.112a(a)(1)(ii)(D) § 60.112a(a)(1)(iii) § 60.112a(a)(1)(iv)	Vessels storing petroleum liquids with a TVP > 10.3 kPa (1.5 psia) but < 76.6 kPa (11.1 psia) shall be equipped with an external floating roof and closure device as specified.	§ 60.113a(a)(1) § 60.113a(a)(1)(i) § 60.113a(a)(1)(i)(A) § 60.113a(a)(1)(i)(B) § 60.113a(a)(1)(i)(C) § 60.113a(a)(1)(i)(D) § 60.113a(a)(1)(i)(E) § 60.113a(a)(1)(ii)(A) § 60.113a(a)(1)(ii)(B) § 60.113a(a)(1)(ii)(C) § 60.113a(a)(1)(iii) § 60.113a(a)(1)(iv) § 60.115a(a) § 60.115a(b)	§ 60.113a(a)(1)(i)(D) § 60.115a(a)	§ 60.113a(a)(1)(i)(E) § 60.113a(a)(1)(iv)
83-TK-23	EU	60QQQ	VOC	40 CFR Part 60, Subpart QQQ	§ 60.692-3(d) § 60.692-1(a) § 60.692-6(a) § 60.692-6(b) § 60.692-7(b)	Storage vessels, including slop oil tanks and other auxiliary tanks that are subject to the requirements of 40	§ 60.692-3(a)(4) § 60.696(a)	§ 60.697(a) § 60.697(c) [G]§ 60.697(e) § 60.697(f)(1) [G]§ 60.697(f)(2)	§ 60.698(b)(1) § 60.698(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						CFR subparts K, Ka, or Kb, are not subject to the requirements of this section.			
83-TK-25	EU	R5112-a	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
83-TK-25	EU	60KA-b	VOC	40 CFR Part 60, Subpart Ka	§ 60.110a(a)	The affected facility is each storage vessel for petroleum liquids that has a storage capacity > 151,416 L (40,000 gal) and for which construction commenced after 5/18/78 and prior to 7/23/84.	§ 60.115a(a) § 60.115a(b)	§ 60.115a(a)	None
83-TK-25	EU	61FF	BENZENE	40 CFR Part 61, Subpart FF	§ 61.351(a) [G]§ 60.112b(a)(2) § 61.351(a)(2) § 61.351(b)	As an alternative to the standards for tanks specified in § 61.343, an owner or operator may elect to comply with one of the following §61.351(a)(1)-(3):	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6)	§ 60.115b [G]§ 60.115b(b)(3) § 61.356(k)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 61.357(e) § 61.357(f)
83-TK-26	EU	R5112-a	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the	The permit holder shall comply with the applicable requirements	The permit holder shall comply with the applicable monitoring	The permit holder shall comply with the applicable	The permit holder shall comply with the applicable reporting

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	of 30 TAC Chapter 115, Storage of VOCs	and testing requirements of 30 TAC Chapter 115, Storage of VOCs	recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	requirements of 30 TAC Chapter 115, Storage of VOCs
83-TK-26	EU	R5112-b	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
83-TK-26	EU	R5112-c	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
83-TK-26	EU	60KB-b	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)		
83-TK-26	EU	60KB-c	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)
83-TK-26	EU	60KB-d	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
83-TK-26	EU	60QQQ	VOC	40 CFR Part 60, Subpart QQQ	§ 60.692-3(d) § 60.692-1(a) § 60.692-6(a) § 60.692-6(b) § 60.692-7(b)	Storage vessels, including slop oil tanks and other auxiliary tanks that are subject to the requirements of 40 CFR subparts K, Ka, or Kb, are not subject to the requirements of this section.	§ 60.692-3(a)(4) § 60.696(a)	§ 60.697(a) § 60.697(c) [G]§ 60.697(e) § 60.697(f)(1) [G]§ 60.697(f)(2)	§ 60.698(b)(1) § 60.698(e)
83-TK-26	EU	63CC	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) [G]§ 60.112b(a)(2) § 63.640(n)(8)(i) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) [G]§ 63.120(b)(7) § 63.640(n)(8)(ii)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 63.640(n)(8)(vi)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)
83-TK-26	EU	63CC-b	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) [G]§ 60.112b(a)(2) § 63.640(n)(8)(i) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 63.640(n)(8)(vi)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) [G]§ 63.120(b)(7) § 63.640(n)(8)(ii)		
83-TK-28	EU	R5112-a	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
83-V-97	EU	R5112-a	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
83-V-97	EU	R5112-b	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
83-V-97	EU	R5112-c	VOC	30 TAC Chapter 115, Storage of	§ 115.112 The permit holder	The permit holder shall comply with the	The permit holder shall comply with the	The permit holder shall comply with the	The permit holder shall comply with the

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				VOCs	shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	applicable requirements of 30 TAC Chapter 115, Storage of VOCs	applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
83-V-97	EU	60KB-b	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)
83-V-97	EU	60KB-c	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)		
83-V-97	EU	60KB-d	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)
83-V-97	EU	60QQQ	VOC	40 CFR Part 60, Subpart QQQ	§ 60.692-3(d) § 60.692-1(a) § 60.692-6(a) § 60.692-6(b) § 60.692-7(b)	Storage vessels, including slop oil tanks and other auxiliary tanks that are subject to the requirements of 40 CFR subparts K, Ka, or Kb, are not subject to the requirements of this section.	§ 60.692-3(a)(4) § 60.696(a)	§ 60.697(a) § 60.697(c) [G]§ 60.697(e) § 60.697(f)(1) [G]§ 60.697(f)(2)	§ 60.698(b)(1) § 60.698(e)
83-V-97	EU	61FF	BENZENE	40 CFR Part 61, Subpart FF	§ 61.351(a) [G]§ 60.112b(a)(2) § 61.351(a)(2) § 61.351(b)	As an alternative to the standards for tanks specified in § 61.343, an owner or operator may elect to comply with one of the following §61.351(a)(1)-(3):	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5)	§ 60.115b [G]§ 60.115b(b)(3) § 61.356(k)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 61.357(e) § 61.357(f)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							[G]§ 60.113b(b)(6)		
83-V-98	EU	R5112-a	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
83-V-98	EU	R5112-b	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
83-V-98	EU	R5112-c	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
83-V-98	EU	60KB-b	VOC	40 CFR Part 60, Subpart Kb	§ 60.110b(a)	Except for §60.110b(b), this subpart applies to vessels with a capacity greater than or equal to 75 cubic meters (19,800 gal) used to store VOLs for which	§ 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(d) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.116b(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						construction/reconstruction/modification began after 7/23/84.			
83-V-98	EU	60KB-c	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(B) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) [G]§ 60.113b(a)(3) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(4)
83-V-98	EU	60KB-d	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(B) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) [G]§ 60.113b(a)(3) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(4)
83-V-98	EU	61FF	BENZENE	40 CFR Part 61, Subpart FF	§ 61.351(a) § 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(B) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii) § 61.351(a)(1) § 61.351(b)	As an alternative to the standards for tanks specified in § 61.343, an owner or operator may elect to comply with one of the following §61.351(a)(1)-(3):	§ 60.113b(a)(1) [G]§ 60.113b(a)(3) § 60.113b(a)(4) § 60.113b(a)(5)	§ 60.115b § 60.115b(a)(2) § 61.356(k)	§ 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(4) § 61.357(e) § 61.357(f)
83-V-98	EU	63CC	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) § 60.112b(a)(1)	Vessels described by § 63.640(n)(1) and (n)(3)	§ 60.113b(a)(1) [G]§ 60.113b(a)(3)	§ 60.115b § 60.115b(a)(2)	§ 60.113b(a)(5) § 60.115b

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(B) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii) § 63.640(n)(8)(ii)	are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	§ 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) [G]§ 60.116b(e)(3) § 63.640(n)(8)(ii)	§ 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.115b(a)(1) § 60.115b(a)(4)
GRP-EFRA1	EU	R5112-a	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
GRP-EFRA1	EU	R5112-b	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
GRP-EFRA1	EU	R5112-c	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115,	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					Storage of VOCs				
GRP-EFRA1	EU	60KA-b	VOC	40 CFR Part 60, Subpart Ka	§ 60.110a(a)	The affected facility is each storage vessel for petroleum liquids that has a storage capacity > 151,416 L (40,000 gal) and for which construction commenced after 5/18/78 and prior to 7/23/84.	§ 60.115a(a) § 60.115a(b)	§ 60.115a(a)	None
GRP-EFRA1	EU	60KA-c	VOC	40 CFR Part 60, Subpart Ka	§ 60.112a(a)(1) § 60.112a(a)(1)(i) § 60.112a(a)(1)(i)(A) § 60.112a(a)(1)(i)(C) § 60.112a(a)(1)(i)(D) § 60.112a(a)(1)(ii)(A) § 60.112a(a)(1)(ii)(B) § 60.112a(a)(1)(ii)(C) § 60.112a(a)(1)(ii)(D) § 60.112a(a)(1)(iii) § 60.112a(a)(1)(iv)	Vessels storing petroleum liquids with a TVP > 10.3 kPa (1.5 psia) but < 76.6 kPa (11.1 psia) shall be equipped with an external floating roof and closure device as specified.	§ 60.113a(a)(1) § 60.113a(a)(1)(i) § 60.113a(a)(1)(i)(A) § 60.113a(a)(1)(i)(B) § 60.113a(a)(1)(i)(C) § 60.113a(a)(1)(i)(D) § 60.113a(a)(1)(i)(E) § 60.113a(a)(1)(ii)(A) § 60.113a(a)(1)(ii)(B) § 60.113a(a)(1)(ii)(C) § 60.113a(a)(1)(iii) § 60.113a(a)(1)(iv) § 60.115a(a) § 60.115a(b)	§ 60.113a(a)(1)(i)(D) § 60.115a(a)	§ 60.113a(a)(1)(i)(E) § 60.113a(a)(1)(iv)
GRP-EFRA1	EU	60KA-d	VOC	40 CFR Part 60, Subpart Ka	§ 60.112a(a)(1) § 60.112a(a)(1)(i) § 60.112a(a)(1)(i)(A) § 60.112a(a)(1)(i)(C) § 60.112a(a)(1)(i)(D) § 60.112a(a)(1)(ii)(A) § 60.112a(a)(1)(ii)(B) § 60.112a(a)(1)(ii)(C) § 60.112a(a)(1)(ii)(D) § 60.112a(a)(1)(iii) § 60.112a(a)(1)(iv)	Vessels storing petroleum liquids with a TVP > 10.3 kPa (1.5 psia) but < 76.6 kPa (11.1 psia) shall be equipped with an external floating roof and closure device as specified.	§ 60.113a(a)(1) § 60.113a(a)(1)(i) § 60.113a(a)(1)(i)(A) § 60.113a(a)(1)(i)(B) § 60.113a(a)(1)(i)(C) § 60.113a(a)(1)(i)(D) § 60.113a(a)(1)(i)(E) § 60.113a(a)(1)(ii)(A) § 60.113a(a)(1)(ii)(B) § 60.113a(a)(1)(ii)(C) § 60.113a(a)(1)(iii) § 60.113a(a)(1)(iv) § 60.115a(a) § 60.115a(b)	§ 60.113a(a)(1)(i)(D) § 60.115a(a)	§ 60.113a(a)(1)(i)(E) § 60.113a(a)(1)(iv)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-EFRA1	EU	63CC	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.119(a)(1) § 63.119(c)(1) § 63.119(c)(1)(i) § 63.119(c)(1)(ii) § 63.119(c)(1)(iii) [G]§ 63.119(c)(3) § 63.119(c)(4) § 63.120(b)(10)(i) § 63.120(b)(5)(i) § 63.120(b)(5)(ii) § 63.120(b)(6)(i) § 63.120(b)(6)(ii) [G]§ 63.120(b)(7) § 63.120(b)(8) [G]§ 63.646(f) § 63.646(g)	Each owner or operator of a Group 1 storage vessel subject to this subpart shall comply with the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.120(b)(1)(i) § 63.120(b)(1)(iii) § 63.120(b)(1)(iv) § 63.120(b)(10) § 63.120(b)(2)(i) § 63.120(b)(2)(ii) § 63.120(b)(2)(iii) § 63.120(b)(3) § 63.120(b)(4) § 63.646(b)(1) § 63.646(e)	[G]§ 63.120(b)(7) § 63.120(b)(8) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1) § 63.655(i)(5)	§ 63.120(b)(10)(ii) § 63.120(b)(10)(iii) § 63.120(b)(9) § 63.642(f) § 63.655(f) [G]§ 63.655(f)(1)(i)(B) § 63.655(f)(6) § 63.655(g) [G]§ 63.655(g)(3) § 63.655(h) § 63.655(h)(1) § 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(B) § 63.655(h)(2)(i)(C) § 63.655(h)(2)(ii) [G]§ 63.655(h)(6)
GRP-ERLQA	EU	R5112-a	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
GRP-ERLQA	EU	R5112-b	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
GRP-ERLQA	EU	R5112-c	VOC	30 TAC Chapter 115, Storage of	§ 115.112 The permit holder	The permit holder shall comply with the	The permit holder shall comply with the	The permit holder shall comply with the	The permit holder shall comply with the

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				VOCs	shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	applicable requirements of 30 TAC Chapter 115, Storage of VOCs	applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
GRP-ERLQA	EU	60KB-b	VOC	40 CFR Part 60, Subpart Kb	§ 60.110b(a)	Except for §60.110b(b), this subpart applies to vessels with a capacity greater than or equal to 75 cubic meters (19,800 gal) used to store VOLs for which construction/reconstruction/modification began after 7/23/84.	§ 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(d) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.116b(d)
GRP-ERLQA	EU	60KB-c	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)
GRP-ERLQA	EU	60KB-d	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						(pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	§ 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.116b(c)	§ 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)
GRP-ERLQA	EU	60QQQ	VOC	40 CFR Part 60, Subpart QQQ	§ 60.692-3(d) § 60.692-1(a) § 60.692-6(a) § 60.692-6(b) § 60.692-7(b)	Storage vessels, including slop oil tanks and other auxiliary tanks that are subject to the requirements of 40 CFR subparts K, Ka, or Kb, are not subject to the requirements of this section.	§ 60.692-3(a)(4) § 60.696(a)	§ 60.697(a) § 60.697(c) [G]§ 60.697(e) § 60.697(f)(1) [G]§ 60.697(f)(2)	§ 60.698(b)(1) § 60.698(e)
GRP-ERLQA	EU	61FF	BENZENE	40 CFR Part 61, Subpart FF	§ 61.351(a) [G]§ 60.112b(a)(2) § 61.351(a)(2) § 61.351(b)	As an alternative to the standards for tanks specified in § 61.343, an owner or operator may elect to comply with one of the following §61.351(a)(1)-(3):	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6)	§ 60.115b [G]§ 60.115b(b)(3) § 61.356(k)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 61.357(e) § 61.357(f)
GRP-ERLQA	EU	63CC	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) [G]§ 60.112b(a)(2) § 63.640(n)(8)(i) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 63.640(n)(8)(vi)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						(vi).	§ 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) [G]§ 60.116b(e)(3) [G]§ 63.120(b)(7) § 63.640(n)(8)(ii)		§ 60.115b(b)(4) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)
GRP-FIXA2	EU	R5112-a	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
GRP-FIXA2	EU	60KA-b	VOC	40 CFR Part 60, Subpart Ka	§ 60.110a(a)	The affected facility is each storage vessel for petroleum liquids that has a storage capacity > 151,416 L (40,000 gal) and for which construction commenced after 5/18/78 and prior to 7/23/84.	§ 60.115a(a) § 60.115a(b)	§ 60.115a(a)	None
GRP-FIXA2	EU	63CC	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						source.			§ 63.655(h)(6)(ii)
GRP-FIXAN	EU	R5112-a	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
GRP-FIXAN	EU	60KA-b	VOC	40 CFR Part 60, Subpart Ka	§ 60.110a(a)	The affected facility is each storage vessel for petroleum liquids that has a storage capacity > 151,416 L (40,000 gal) and for which construction commenced after 5/18/78 and prior to 7/23/84.	§ 60.115a(a) § 60.115a(b)	§ 60.115a(a)	None
GRP-FIXAS	EU	R5112-a	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
GRP-FIXK2	EU	R5112-a	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					requirements of 30 TAC Chapter 115, Storage of VOCs				
GRP-FIXK2	EU	60K-b	VOC	40 CFR Part 60, Subpart K	§ 60.110(c) § 60.110(c)(2)	Facilities under §60.110(a) of this section with a capacity, construction or modification date as given in §60.110(c)(1) or §60.110(c)(2) are subject to the requirements of this section.	§ 60.113(a) § 60.113(b)	§ 60.113(a)	None
GRP-FIXK2	EU	63CC	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
GRP-GDTKS	EU	R5112-a	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
GRP-GDTKS	EU	R5112-b	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					TAC Chapter 115, Storage of VOCs				
GRP-GDTKS	EU	R5112-c	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
GRP-GDTKS	EU	60KB-b	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)
GRP-GDTKS	EU	60KB-c	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)
GRP-GDTKS	EU	60KB-d	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)		
GRP-GDTKS	EU	63CC	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) § 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) § 63.640(n)(8)(ii)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)
GRP-GDTKS	EU	63CC-b	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) § 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) § 63.640(n)(8)(ii)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)
GRP-IRLQAG	EU	R5112-a	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115,	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					Storage of VOCs				
GRP-IRLQAG	EU	R5112-b	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
GRP-IRLQAG	EU	R5112-c	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
GRP-IRLQAG	EU	60KA-b	VOC	40 CFR Part 60, Subpart Ka	§ 60.110a(a)	The affected facility is each storage vessel for petroleum liquids that has a storage capacity > 151,416 L (40,000 gal) and for which construction commenced after 5/18/78 and prior to 7/23/84.	§ 60.115a(a) § 60.115a(b)	§ 60.115a(a)	None
GRP-IRLQAG	EU	60KA-c	VOC	40 CFR Part 60, Subpart Ka	§ 60.112a(a)(2)	Vessels storing petroleum liquids with a TVP > 10.3 kPa (1.5 psia) but < 76.6 kPa (11.1 psia) shall have a fixed roof and an internal floating cover with the	§ 60.115a(a) § 60.115a(b)	§ 60.115a(a)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						specified closure device and vents.			
GRP-IRLQAG	EU	60KA-d	VOC	40 CFR Part 60, Subpart Ka	§ 60.112a(a)(2)	Vessels storing petroleum liquids with a TVP > 10.3 kPa (1.5 psia) but < 76.6 kPa (11.1 psia) shall have a fixed roof and an internal floating cover with the specified closure device and vents.	§ 60.115a(a) § 60.115a(b)	§ 60.115a(a)	None
GRP-IRLQAG	EU	63CC	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.119(a)(1) [G]§ 63.119(b)(1) § 63.119(b)(2) § 63.119(b)(3)(i) § 63.119(b)(4) § 63.120(a)(4) § 63.120(a)(7) [G]§ 63.646(f) § 63.646(g)	Each owner or operator of a Group 1 storage vessel subject to this subpart shall comply with the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.120(a)(2)(i) § 63.120(a)(2)(ii) § 63.646(b)(1) § 63.646(e)	§ 63.120(a)(4) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1) § 63.655(i)(5)	§ 63.120(a)(5) § 63.120(a)(6) § 63.642(f) § 63.655(f) [G]§ 63.655(f)(1)(i)(B) § 63.655(f)(6) § 63.655(g) § 63.655(g)(2) [G]§ 63.655(g)(2)(i) [G]§ 63.655(g)(2)(ii) § 63.655(h) § 63.655(h)(1) § 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(B) § 63.655(h)(2)(i)(C) [G]§ 63.655(h)(6)
GRP-IRLQB1	EU	R5112-a	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-IRLQB1	EU	R5112-b	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
GRP-IRLQB1	EU	R5112-c	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
GRP-IRLQB1	EU	60KB-b	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(A) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)
GRP-IRLQB1	EU	60KB-c	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(A) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.112b(a)(1)(viii)		[G]§ 60.116b(e)(3)		
GRP-IRLQB1	EU	60KB-d	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(A) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)
GRP-IRLQB1	EU	63CC	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) § 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(A) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) § 63.640(n)(8)(ii)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3) § 63.640(n)(8)(v)
GRP-IRLQB1	EU	63CC-b	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) § 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(A) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) § 63.640(n)(8)(ii)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3) § 63.640(n)(8)(v)
GRP-IRLQBG	EU	R5112-a	VOC	30 TAC Chapter	§ 115.112	The permit holder shall	The permit holder	The permit holder shall	The permit holder shall

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				115, Storage of VOCs	The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
GRP-IRLQBG	EU	R5112-b	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
GRP-IRLQBG	EU	R5112-c	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
GRP-IRLQBG	EU	60KB-b	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(A) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-IRLQBG	EU	60KB-c	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(A) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)
GRP-IRLQBG	EU	60KB-d	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(A) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)
GRP-IRLQBG	EU	63CC	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) § 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(A) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) § 63.640(n)(8)(ii)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3) § 63.640(n)(8)(v)
GRP-IRLQBG	EU	63CC-b	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) § 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(A) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3) § 63.640(n)(8)(v)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	(vi).	§ 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) § 63.640(n)(8)(ii)		
GRP-IRLQK1	EU	R5112-a	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
GRP-IRLQK1	EU	R5112-b	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
GRP-IRLQK1	EU	R5112-c	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
GRP-IRLQK1	EU	60K-b	VOC	40 CFR Part 60,	§ 60.110(c)	Facilities under	§ 60.113(a)	§ 60.113(a)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Subpart K	§ 60.110(c)(2)	§60.110(a) of this section with a capacity, construction or modification date as given in §60.110(c)(1) or §60.110(c)(2) are subject to the requirements of this section.	§ 60.113(b)		
GRP-IRLQK1	EU	60K-c	VOC	40 CFR Part 60, Subpart K	§ 60.112(a)(1)	Storage vessels holding petroleum liquids with a true vapor pressure of 78 mm Hg (1.5 psia) or greater but not greater than 570 mm Hg (11.1 psia) shall have a floating roof, a vapor recovery system, or their equivalents.	§ 60.113(a) § 60.113(b) ** See Periodic Monitoring Summary	§ 60.113(a)	None
GRP-IRLQK1	EU	60K-d	VOC	40 CFR Part 60, Subpart K	§ 60.112(a)(1)	Storage vessels holding petroleum liquids with a true vapor pressure of 78 mm Hg (1.5 psia) or greater but not greater than 570 mm Hg (11.1 psia) shall have a floating roof, a vapor recovery system, or their equivalents.	§ 60.113(a) § 60.113(b) ** See Periodic Monitoring Summary	§ 60.113(a)	None
GRP-IRLQK1	EU	63CC	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.119(a)(1) [G]§ 63.119(b)(1) § 63.119(b)(2) § 63.119(b)(3)(i) § 63.119(b)(4) § 63.120(a)(4) § 63.120(a)(7) [G]§ 63.646(f) § 63.646(g)	Each owner or operator of a Group 1 storage vessel subject to this subpart shall comply with the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.120(a)(2)(i) § 63.120(a)(2)(ii) § 63.646(b)(1) § 63.646(e)	§ 63.120(a)(4) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1) § 63.655(i)(5)	§ 63.120(a)(5) § 63.120(a)(6) § 63.642(f) § 63.655(f) [G]§ 63.655(f)(1)(i)(B) § 63.655(f)(6) § 63.655(g) § 63.655(g)(2) [G]§ 63.655(g)(2)(i) [G]§ 63.655(g)(2)(ii) § 63.655(h)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
									§ 63.655(h)(1) § 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(B) § 63.655(h)(2)(i)(C) [G]§ 63.655(h)(6)
GRP-IRMTA1	EU	R5112-a	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
GRP-IRMTA1	EU	R5112-b	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
GRP-IRMTA1	EU	R5112-c	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
GRP-IRMTA1	EU	60KA-b	VOC	40 CFR Part 60, Subpart Ka	§ 60.110a(a)	The affected facility is each storage vessel for	§ 60.115a(a) § 60.115a(b)	§ 60.115a(a)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						petroleum liquids that has a storage capacity > 151,416 L (40,000 gal) and for which construction commenced after 5/18/78 and prior to 7/23/84.			
GRP-IRMTA1	EU	60KA-c	VOC	40 CFR Part 60, Subpart Ka	§ 60.112a(a)(2)	Vessels storing petroleum liquids with a TVP > 10.3 kPa (1.5 psia) but < 76.6 kPa (11.1 psia) shall have a fixed roof and an internal floating cover with the specified closure device and vents.	§ 60.115a(a) § 60.115a(b)	§ 60.115a(a)	None
GRP-IRMTA1	EU	60KA-d	VOC	40 CFR Part 60, Subpart Ka	§ 60.112a(a)(2)	Vessels storing petroleum liquids with a TVP > 10.3 kPa (1.5 psia) but < 76.6 kPa (11.1 psia) shall have a fixed roof and an internal floating cover with the specified closure device and vents.	§ 60.115a(a) § 60.115a(b)	§ 60.115a(a)	None
GRP-IRMTA1	EU	63CC	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.119(a)(1) [G]§ 63.119(b)(1) § 63.119(b)(2) § 63.119(b)(3)(ii) § 63.119(b)(4) § 63.120(a)(4) § 63.120(a)(7) [G]§ 63.646(f) § 63.646(g)	Each owner or operator of a Group 1 storage vessel subject to this subpart shall comply with the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.120(a)(2)(i) § 63.120(a)(2)(ii) § 63.646(b)(1) § 63.646(e)	§ 63.120(a)(4) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1) § 63.655(i)(5)	§ 63.120(a)(5) § 63.120(a)(6) § 63.642(f) § 63.655(f) [G]§ 63.655(f)(1)(i)(B) § 63.655(f)(6) § 63.655(g) § 63.655(g)(2) [G]§ 63.655(g)(2)(i) [G]§ 63.655(g)(2)(ii) § 63.655(h) § 63.655(h)(1) § 63.655(h)(2)(i)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
									§ 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(B) § 63.655(h)(2)(i)(C) [G]§ 63.655(h)(6)
GRP-IRMTAG	EU	R5112-a	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
GRP-IRMTAG	EU	R5112-b	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
GRP-IRMTAG	EU	R5112-c	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
GRP-IRMTAG	EU	60KA-b	VOC	40 CFR Part 60, Subpart Ka	§ 60.110a(a)	The affected facility is each storage vessel for petroleum liquids that has a storage capacity >	§ 60.115a(a) § 60.115a(b)	§ 60.115a(a)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						151,416 L (40,000 gal) and for which construction commenced after 5/18/78 and prior to 7/23/84.			
GRP-IRMTAG	EU	60KA-c	VOC	40 CFR Part 60, Subpart Ka	§ 60.112a(a)(2)	Vessels storing petroleum liquids with a TVP > 10.3 kPa (1.5 psia) but < 76.6 kPa (11.1 psia) shall have a fixed roof and an internal floating cover with the specified closure device and vents.	§ 60.115a(a) § 60.115a(b)	§ 60.115a(a)	None
GRP-IRMTAG	EU	60KA-d	VOC	40 CFR Part 60, Subpart Ka	§ 60.112a(a)(2)	Vessels storing petroleum liquids with a TVP > 10.3 kPa (1.5 psia) but < 76.6 kPa (11.1 psia) shall have a fixed roof and an internal floating cover with the specified closure device and vents.	§ 60.115a(a) § 60.115a(b)	§ 60.115a(a)	None
GRP-IRMTAG	EU	63CC	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.119(a)(1) [G]§ 63.119(b)(1) § 63.119(b)(2) § 63.119(b)(3)(i) § 63.119(b)(4) § 63.120(a)(4) § 63.120(a)(7) [G]§ 63.646(f) § 63.646(g)	Each owner or operator of a Group 1 storage vessel subject to this subpart shall comply with the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.120(a)(2)(i) § 63.120(a)(2)(ii) § 63.646(b)(1) § 63.646(e)	§ 63.120(a)(4) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1) § 63.655(i)(5)	§ 63.120(a)(5) § 63.120(a)(6) § 63.642(f) § 63.655(f) [G]§ 63.655(f)(1)(i)(B) § 63.655(f)(6) § 63.655(g) § 63.655(g)(2) [G]§ 63.655(g)(2)(i) [G]§ 63.655(g)(2)(ii) § 63.655(h) § 63.655(h)(1) § 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(B)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
									§ 63.655(h)(2)(i)(C) [G]§ 63.655(h)(6)
GRP-IRMTB1	EU	R5112-a	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
GRP-IRMTB1	EU	R5112-b	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
GRP-IRMTB1	EU	R5112-c	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
GRP-IRMTB1	EU	60KB-b	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)		
GRP-IRMTB1	EU	60KB-c	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)
GRP-IRMTB1	EU	60KB-d	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)
GRP-IRMTB1	EU	63CC	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) § 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) § 63.640(n)(8)(ii)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)
GRP-IRMTB1	EU	63CC-b	112(B)	40 CFR Part 63,	§ 63.640(n)(8)	Vessels described by §	§ 60.113b(a)(1)	§ 60.115b	§ 60.113b(a)(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
			HAPS	Subpart CC	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	§ 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) § 63.640(n)(8)(ii)	§ 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)
GRP-IRMTBG	EU	R5112-a	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
GRP-IRMTBG	EU	R5112-b	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
GRP-IRMTBG	EU	R5112-c	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					requirements of 30 TAC Chapter 115, Storage of VOCs				
GRP-IRMTBG	EU	60KB-b	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)
GRP-IRMTBG	EU	60KB-c	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)
GRP-IRMTBG	EU	60KB-d	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)
GRP-IRMTBG	EU	63CC	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) § 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	for in §63.640(n)(8)(i)-(vi).	§ 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) § 63.640(n)(8)(ii)		§ 63.640(n)(8)(iv) § 63.640(n)(8)(v)
GRP-IRMTBG	EU	63CC-b	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) § 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) § 63.640(n)(8)(ii)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)
GRP-IRMTBQ	EU	R5112-a	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
GRP-IRMTBQ	EU	R5112-b	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					TAC Chapter 115, Storage of VOCs				
GRP-IRMTBQ	EU	R5112-c	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
GRP-IRMTBQ	EU	60KB-b	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)
GRP-IRMTBQ	EU	60KB-c	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)
GRP-IRMTBQ	EU	60KB-d	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)		
GRP-IRMTBQ	EU	60QQQ	VOC	40 CFR Part 60, Subpart QQQ	§ 60.692-3(d) § 60.692-1(a) § 60.692-6(a) § 60.692-6(b) § 60.692-7(b)	Storage vessels, including slop oil tanks and other auxiliary tanks that are subject to the requirements of 40 CFR subparts K, Ka, or Kb, are not subject to the requirements of this section.	§ 60.692-3(a)(4) § 60.696(a)	§ 60.697(a) § 60.697(c) [G]§ 60.697(e) § 60.697(f)(1) [G]§ 60.697(f)(2)	§ 60.698(b)(1) § 60.698(e)
GRP-IRMTBQ	EU	61FF	BENZENE	40 CFR Part 61, Subpart FF	§ 61.351(a) § 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(A) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii) § 61.351(a)(1) § 61.351(b)	As an alternative to the standards for tanks specified in § 61.343, an owner or operator may elect to comply with one of the following §61.351(a)(1)-(3):	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5)	§ 60.115b § 60.115b(a)(2) § 61.356(k)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3) § 61.357(e) § 61.357(f)
GRP-IRMTBQ	EU	63CC	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) § 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) § 63.640(n)(8)(ii)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-IRMTBQ	EU	63CC-b	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) § 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) § 63.640(n)(8)(ii)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)
GRP-IRMTK1	EU	R5112-a	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
GRP-IRMTK1	EU	R5112-b	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
GRP-IRMTK1	EU	R5112-c	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115,	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					specification requirements of 30 TAC Chapter 115, Storage of VOCs		Storage of VOCs	VOCs	
GRP-IRMTK1	EU	60K-b	VOC	40 CFR Part 60, Subpart K	§ 60.110(c) § 60.110(c)(2)	Facilities under §60.110(a) of this section with a capacity, construction or modification date as given in §60.110(c)(1) or §60.110(c)(2) are subject to the requirements of this section.	§ 60.113(a) § 60.113(b)	§ 60.113(a)	None
GRP-IRMTK1	EU	60K-c	VOC	40 CFR Part 60, Subpart K	§ 60.112(a)(1)	Storage vessels holding petroleum liquids with a true vapor pressure of 78 mm Hg (1.5 psia) or greater but not greater than 570 mm Hg (11.1 psia) shall have a floating roof, a vapor recovery system, or their equivalents.	§ 60.113(a) § 60.113(b) ** See Periodic Monitoring Summary	§ 60.113(a)	None
GRP-IRMTK1	EU	60K-d	VOC	40 CFR Part 60, Subpart K	§ 60.112(a)(1)	Storage vessels holding petroleum liquids with a true vapor pressure of 78 mm Hg (1.5 psia) or greater but not greater than 570 mm Hg (11.1 psia) shall have a floating roof, a vapor recovery system, or their equivalents.	§ 60.113(a) § 60.113(b) ** See Periodic Monitoring Summary	§ 60.113(a)	None
GRP-IRMTK1	EU	63CC	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.119(a)(1) [G]§ 63.119(b)(1) § 63.119(b)(2) § 63.119(b)(2)	Each owner or operator of a Group 1 storage vessel subject to this subpart shall comply with the requirements of	§ 63.120(a)(2)(i) § 63.120(a)(2)(ii) § 63.646(b)(1) § 63.646(e)	§ 63.120(a)(4) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1)	§ 63.120(a)(5) § 63.120(a)(6) § 63.642(f) § 63.655(f) [G]§ 63.655(f)(1)(i)(B)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.119(b)(3)(ii) § 63.119(b)(4) § 63.120(a)(4) § 63.120(a)(7) [G]§ 63.646(f) § 63.646(g)	§63.119 - §63.121 except as provided in §63.646(b)-(l).		§ 63.655(i)(5)	§ 63.655(f)(6) § 63.655(g) § 63.655(g)(2) [G]§ 63.655(g)(2)(i) [G]§ 63.655(g)(2)(ii) § 63.655(h) § 63.655(h)(1) § 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(B) § 63.655(h)(2)(i)(C) [G]§ 63.655(h)(6)
TK-51	EU	R5112-a	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
TK-51	EU	R5112-b	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs
TK-51	EU	R5112-c	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112 The permit holder shall comply with the applicable limitation, standard and/or equipment specification	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 115, Storage of VOCs	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 115, Storage of VOCs

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					requirements of 30 TAC Chapter 115, Storage of VOCs				
TK-51	EU	60KB-b	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(A) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)
TK-51	EU	60KB-c	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(A) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)
TK-51	EU	60KB-d	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(A) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)
TK-51	EU	63CC	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) § 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(A) § 60.112b(a)(1)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	for in §63.640(n)(8)(i)-(vi).	§ 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) § 63.640(n)(8)(ii)		§ 63.640(n)(8)(v)
TK-51	EU	63CC-b	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) § 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(A) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) § 63.640(n)(8)(ii)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3) § 63.640(n)(8)(v)
GRPTURNJET	EU	R5311a	VOC	30 TAC Chapter 115, Unit Turn & Vac System-Pet Ref	§ 115.317	In Gregg, Nueces and Victoria Counties, a vacuum-producing system emitting a combined weight of VOCs less than or equal to 100 lbs. in any consecutive 24-hour period is exempt from the requirements of §115.311(b).	None	None	None
GRP-VACJET	EU	R5311a	VOC	30 TAC Chapter 115, Unit Turn & Vac System-Pet Ref	§ 115.311(b)(1) § 115.312(b)(2) § 115.312(b)(2)(C)	No person may be allowed to emit VOC from a steam ejector or mechanical vacuum pump in a petroleum refinery, unless vent stream is burned	[G]§ 115.315(b) ** See Periodic Monitoring Summary	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						properly in accordance with §115.312(b)(2) of this title.			
GRP-VACJET	EU	R5311b	VOC	30 TAC Chapter 115, Unit Turn & Vac System-Pet Ref	§ 115.311(b)(1) § 115.312(b)(2) § 115.312(b)(2)(B)	No person may be allowed to emit VOC from a steam ejector or mechanical vacuum pump in a petroleum refinery, unless vent stream is burned properly in accordance with §115.312(b)(2) of this title.	[G]§ 115.315(b) ** See Periodic Monitoring Summary	None	None
APISEP	EU	R5131	VOC	30 TAC Chapter 115, Water Separation	§ 115.132(b)(3) § 115.131(b)	VOC water separator compartments must be equipped with a vapor recovery system which satisfies the provisions of §115.131(b) of this title.	[G]§ 115.135(b) § 115.136(b)(3) § 115.136(b)(4) ** See Periodic Monitoring Summary	§ 115.136(b)(3) § 115.136(b)(4)	None
APISEP	EU	60QQQ	VOC	40 CFR Part 60, Subpart QQQ	§ 60.692-3(a) § 60.692-1(a) § 60.692-3(a)(1) § 60.692-3(a)(2) § 60.692-3(a)(3) § 60.692-3(a)(5) § 60.692-3(b) § 60.692-3(e) § 60.692-5(a) § 60.692-5(d) [G]§ 60.692-5(e) § 60.692-6(a) § 60.692-6(b) § 60.692-7(b)	Except as noted, each oil-water separator tank, slop oil tank, storage vessel, or other auxiliary equipment shall be equipped with fixed roof, meeting following specifications:	§ 60.692-3(a)(4) § 60.695(a) § 60.695(a)(1) § 60.696(a)	§ 60.695(a)(1) § 60.697(a) § 60.697(c) § 60.697(d) [G]§ 60.697(e) § 60.697(f)(1) [G]§ 60.697(f)(2) § 60.697(f)(3) § 60.697(f)(3)(i) § 60.697(f)(3)(iii) § 60.697(f)(3)(iv) § 60.697(f)(3)(v) § 60.697(f)(3)(vi) § 60.697(f)(3)(vii) § 60.697(f)(3)(viii)	§ 60.698(b)(1) § 60.698(d) § 60.698(d)(1) § 60.698(e)
APISEP	EU	60FF-a	BENZENE	40 CFR Part 61, Subpart FF	§ 61.347(a)(1) § 61.347(a)(1)(i)(A) § 61.347(a)(1)(i)(B)	Install, operate, and maintain a fixed-roof and closed-vent system	§ 61.347(a)(1)(i)(A) § 61.347(b) § 61.349(a)(1)(i)	§ 61.354(c) § 61.354(c)(1) § 61.356(d)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(A)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 61.347(b) § 61.347(c) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(i)(C) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	that routes all organic vapors vented from the oil-water separator to a control device.	§ 61.349(e) § 61.349(f) § 61.354(c) § 61.354(c)(1) [G]§ 61.355(h)	§ 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(A) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(4)	

Additional Monitoring Requirements

Compliance Assurance Monitoring Summary 313

Periodic Monitoring Summary..... 326

CAM Summary

Unit/Group/Process Information	
ID No.: 24-ST-01	
Control Device ID No.: 24-ST-02	Control Device Type: Wet Scrubber
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart J	SOP Index No.: 60J
Pollutant: PM	Main Standard: § 60.102(a)(1)
Monitoring Information	
Indicator: Pressure Drop	
Minimum Frequency: four times per hour	
Averaging Period: one hour	
Deviation Limit: Min. flue gas pressure drop across the filtering modules & cyclolabs is 80% of the avg. value recorded from the most recent performance test. The TCEQ will be notified of changes to the deviation limit from the most recent stack test within 60 days.	
CAM Text: Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following: ± 1 inch water gauge pressure (± 250 pascals); or ± 2% of span.	

CAM Summary

Unit/Group/Process Information	
ID No.: 24-ST-01	
Control Device ID No.: 24-ST-02	Control Device Type: Wet Scrubber
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart J	SOP Index No.: 60J
Pollutant: PM	Main Standard: § 60.102(a)(1)
Monitoring Information	
Indicator: Liquid Supply Pressure	
Minimum Frequency: four times per hour	
Averaging Period: one hour	
Deviation Limit: Minimum water pressure to filtering modules is 80% of the average value recorded from the most recent performance test. The TCEQ will be notified of changes to the deviation limit from the most recent stack test within 60 days after the stack sample	
CAM Text: Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following: ± 5% of span; or ± 5% of design liquid supply pressure.	

CAM Summary

Unit/Group/Process Information	
ID No.: 24-ST-01	
Control Device ID No.: 24-ST-02	Control Device Type: Wet Scrubber
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart J	SOP Index No.: 60J
Pollutant: PM (OPACITY)	Main Standard: § 60.102(a)(2)
Monitoring Information	
Indicator: Pressure Drop	
Minimum Frequency: four times per hour	
Averaging Period: one hour	
Deviation Limit: Min. flue gas pressure drop across the filtering modules & cyclolabs is 80% of the avg. value recorded from the most recent performance test. The TCEQ will be notified of changes to the deviation limit from the most recent stack test within 60 days.	
CAM Text: Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following: ± 1 inch water gauge pressure (± 250 pascals); or ± 2% of span.	

CAM Summary

Unit/Group/Process Information	
ID No.: 24-ST-01	
Control Device ID No.: 24-ST-02	Control Device Type: Wet Scrubber
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart J	SOP Index No.: 60J
Pollutant: PM (OPACITY)	Main Standard: § 60.102(a)(2)
Monitoring Information	
Indicator: Liquid Supply Pressure	
Minimum Frequency: four times per hour	
Averaging Period: one hour	
Deviation Limit: Minimum water pressure to filtering modules is 80% of the average value recorded from the most recent performance test. The TCEQ will be notified of changes to the deviation limit from the most recent stack test within 60 days after the stack sample	
CAM Text: Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following: ± 5% of span; or ± 5% of design liquid supply pressure.	

CAM Summary

Unit/Group/Process Information	
ID No.: GRP-EPN121	
Control Device ID No.: 24-ST-02	Control Device Type: Wet Scrubber
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(B)
Monitoring Information	
Indicator: Pressure Drop	
Minimum Frequency: four times per hour	
Averaging Period: one hour	
Deviation Limit: Min. flue gas pressure drop across the filtering modules & cyclolabs is 80% of the avg. value recorded from the most recent performance test. The TCEQ will be notified of changes to the deviation limit from the most recent stack test within 60 days.	
CAM Text: Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following: ± 1 inch water gauge pressure (± 250 pascals); or ± 2% of span.	

CAM Summary

Unit/Group/Process Information	
ID No.: GRP-EPN121	
Control Device ID No.: 24-ST-02	Control Device Type: Wet Scrubber
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(B)
Monitoring Information	
Indicator: Liquid Supply Pressure	
Minimum Frequency: four times per hour	
Averaging Period: one hour	
Deviation Limit: Minimum water pressure to filtering modules is 80% of the average value recorded from the most recent performance test. The TCEQ will be notified of changes to the deviation limit from the most recent stack test within 60 days after the stack sample	
CAM Text: Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following: ± 5% of span; or ± 5% of design liquid supply pressure.	

CAM Summary

Unit/Group/Process Information	
ID No.: GRP-EPN121	
Control Device ID No.: 24-ST-02	Control Device Type: Wet Scrubber
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Nonagricultural Processes	SOP Index No.: R1151
Pollutant: PM	Main Standard: § 111.151(a)
Monitoring Information	
Indicator: Pressure Drop	
Minimum Frequency: four times per hour	
Averaging Period: one hour	
Deviation Limit: Min. flue gas pressure drop across the filtering modules & cyclolabs is 80% of the avg. value recorded from the most recent performance test. The TCEQ will be notified of changes to the deviation limit from the most recent stack test within 60 days.	
CAM Text: Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following: ± 1 inch water gauge pressure (± 250 pascals); or ± 2% of span.	

CAM Summary

Unit/Group/Process Information	
ID No.: GRP-EPN121	
Control Device ID No.: 24-ST-02	Control Device Type: Wet Scrubber
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Nonagricultural Processes	SOP Index No.: R1151
Pollutant: PM	Main Standard: § 111.151(a)
Monitoring Information	
Indicator: Liquid Supply Pressure	
Minimum Frequency: four times per hour	
Averaging Period: one hour	
Deviation Limit: Minimum water pressure to filtering modules is 80% of the average value recorded from the most recent performance test. The TCEQ will be notified of changes to the deviation limit from the most recent stack test within 60 days after the stack sample	
CAM Text: Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following: ± 5% of span; or ± 5% of design liquid supply pressure.	

CAM Summary

Unit/Group/Process Information	
ID No.: SRU	
Control Device ID No.: 24-ST-02	Control Device Type: Sulfur recovery unit with incinerator
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 112, Sulfur Compounds	SOP Index No.: REG2
Pollutant: SO2	Main Standard: § 112.7(a)
Monitoring Information	
Indicator: Sulfur Dioxide Concentration	
Minimum Frequency: four times per hour	
Averaging Period: one hour	
Deviation Limit: 2493.1 lbs/hr SO2	
CAM Text: Use a continuous emission monitoring system (CEMS) to measure and record sulfur dioxide emissions in the exhaust stream of the control device. The CEMS shall be operated in accordance with the monitoring requirements of 40 CFR § 60.13 and the performance specifications of 40 CFR Part 60, Appendix B. In addition, monitor oxygen or carbon dioxide with a CEMS operated in accordance with above CEMS procedures.	

CAM Summary

Unit/Group/Process Information	
ID No.: SRU	
Control Device ID No.: 24-ST-02	Control Device Type: Sulfur recovery unit with incinerator
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart J	SOP Index No.: 60J
Pollutant: SO2	Main Standard: § 60.104(a)(2)(i)
Monitoring Information	
Indicator: Sulfur Dioxide Concentration	
Minimum Frequency: four times per hour	
Averaging Period: one hour	
Deviation Limit: 250 ppmv (dry basis) SO2 @ 0% excess air	
CAM Text: Use a continuous emission monitoring system (CEMS) to measure and record sulfur dioxide emissions in the exhaust stream of the control device. The CEMS shall be operated in accordance with the monitoring requirements of 40 CFR § 60.13 and the performance specifications of 40 CFR Part 60, Appendix B. In addition, monitor oxygen or carbon dioxide with a CEMS operated in accordance with above CEMS procedures.	

CAM Summary

Unit/Group/Process Information	
ID No.: SRU3	
Control Device ID No.: 24-ST-02	Control Device Type: Sulfur recovery unit with incinerator
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 112, Sulfur Compounds	SOP Index No.: REG2
Pollutant: SO2	Main Standard: § 112.7(a)
Monitoring Information	
Indicator: Sulfur Dioxide Concentration	
Minimum Frequency: four times per hour	
Averaging Period: one hour	
Deviation Limit: 2667.5 lbs/hr SO2	
CAM Text: Use a continuous emission monitoring system (CEMS) to measure and record sulfur dioxide emissions in the exhaust stream of the control device. The CEMS shall be operated in accordance with the monitoring requirements of 40 CFR § 60.13 and the performance specifications of 40 CFR Part 60, Appendix B. In addition, monitor oxygen or carbon dioxide with a CEMS operated in accordance with above CEMS procedures.	

CAM Summary

Unit/Group/Process Information	
ID No.: SRU3	
Control Device ID No.: 24-ST-02	Control Device Type: Sulfur recovery unit with incinerator
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart J	SOP Index No.: 60J
Pollutant: SO2	Main Standard: § 60.104(a)(2)(i)
Monitoring Information	
Indicator: Sulfur Dioxide Concentration	
Minimum Frequency: four times per hour	
Averaging Period: one hour	
Deviation Limit: 250 ppmv (dry basis) SO2 @ 0% excess air	
CAM Text: Use a continuous emission monitoring system (CEMS) to measure and record sulfur dioxide emissions in the exhaust stream of the control device. The CEMS shall be operated in accordance with the monitoring requirements of 40 CFR § 60.13 and the performance specifications of 40 CFR Part 60, Appendix B. In addition, monitor oxygen or carbon dioxide with a CEMS operated in accordance with above CEMS procedures.	

CAM Summary

Unit/Group/Process Information	
ID No.: T-RACK	
Control Device ID No.: TRUCKCOMB	Control Device Type: Vapor Combustor
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Loading and Unloading of VOC	SOP Index No.: R5211a
Pollutant: VOC	Main Standard: § 115.211(2)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: four times per hour	
Averaging Period: one hour	
Deviation Limit: Minimum combustion temperature is the average value recorded from the most recent performance test. The TCEQ will be notified of the changes to the deviation limit from the most recent stack test within 60 days after the stack sampling is completed	
CAM Text: The monitoring device should be installed in the combustion chamber or immediately downstream of the combustion chamber. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following: ± 2% of reading; or ± 2.5 degrees Celsius.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: 02-V-12	
Control Device ID No.: MFL-1	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121
Pollutant: VOC	Main Standard: § 115.121(b)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Once per hour	
Averaging Period: n/a	
Deviation Limit: Any monitoring which indicates the lack of a pilot flames shall be considered and reported as a deviation when vent is routed to the flare, MFL-1, for vapor control.	
Periodic Monitoring Text: Measure and record the presence of the pilot flame or maintain records of alarm events and duration of alarm events. The presence of a flare pilot flame shall be monitored using a thermocouple or any other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. The monitoring instrumentation shall be maintained, calibrated and operated in accordance with manufacturer's specifications or other written procedures. Any monitoring data which indicates the lack of a pilot flame shall be considered and reported as a deviation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: 38-V-54	
Control Device ID No.: 38-H-01	Control Device Type: Steam Generating Unit (Boiler)/Process Heater (Design heat input is greater than or equal to 44MW)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121
Pollutant: VOC	Main Standard: § 115.121(b)
Monitoring Information	
Indicator: Period of Operation	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: All periods of operation that are not recorded are to be considered and reported as a deviation when vent is routed to the Oleflex Charge Heater, 38-H-01, for vapor control.	
Periodic Monitoring Text: Monitor and record the periods of operation of the steam generating units or process heater. All periods that are not recorded shall be considered and reported as a deviation. The records must be readily available for inspection.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: 38-V-55	
Control Device ID No.: 38-H-02	Control Device Type: Steam Generating Unit (Boiler)/Process Heater (Design heat input is greater than or equal to 44MW)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121
Pollutant: VOC	Main Standard: § 115.121(b)
Monitoring Information	
Indicator: Period of Operation	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: All periods of operation that are not recorded are to be considered and reported as a deviation when vent is routed to the Oleflex Interheater, 38-H-02, for vapor control.	
Periodic Monitoring Text: Monitor and record the periods of operation of the steam generating units or process heater. All periods that are not recorded shall be considered and reported as a deviation. The records must be readily available for inspection.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: 44-V-01	
Control Device ID No.: GF-1	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121
Pollutant: VOC	Main Standard: § 115.121(b)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Once per hour	
Averaging Period: n/a	
Deviation Limit: Any monitoring which indicates the lack of a pilot flames shall be considered and reported as a deviation when vent is routed to the flare, GF-1, for vapor control.	
Periodic Monitoring Text: Measure and record the presence of the pilot flame or maintain records of alarm events and duration of alarm events. The presence of a flare pilot flame shall be monitored using a thermocouple or any other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. The monitoring instrumentation shall be maintained, calibrated and operated in accordance with manufacturer's specifications or other written procedures. Any monitoring data which indicates the lack of a pilot flame shall be considered and reported as a deviation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: 47-V-02	
Control Device ID No.: 47-H-01	Control Device Type: Steam Generating Unit (Boiler)/Process Heater (Design heat input is greater than or equal to 44MW)
Control Device ID No.: 47-H-02	Control Device Type: Steam Generating Unit (Boiler)/Process Heater (Design heat input is greater than or equal to 44MW)
Control Device ID No.: 47-H-03	Control Device Type: Steam Generating Unit (Boiler)/Process Heater (Design heat input is greater than or equal to 44MW)
Control Device ID No.: 47-H-04	Control Device Type: Steam Generating Unit (Boiler)/Process Heater (Design heat input is greater than or equal to 44MW)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121
Pollutant: VOC	Main Standard: § 115.121(b)
Monitoring Information	
Indicator: Period of Operation	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: All periods of operation that are not recorded are to be considered and reported as a deviation when vent is routed to the Hydrocracker heaters, 47-H-01, 47-H-02, 47-H-03, & 47-H-04, for vapor control.	
Periodic Monitoring Text: Monitor and record the periods of operation of the steam generating units or process heater. All periods that are not recorded shall be considered and reported as a deviation. The records must be readily available for inspection.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: 48-V-01	
Control Device ID No.: 48-H-01	Control Device Type: Steam Generating Unit (Boiler)/Process Heater (Design heat input is greater than or equal to 44MW)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121
Pollutant: VOC	Main Standard: § 115.121(b)
Monitoring Information	
Indicator: Period of Operation	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: All periods of operation that are not recorded are to be considered and reported as a deviation when vent is routed to the NHT heater, 48-H-01, for vapor control.	
Periodic Monitoring Text: Monitor and record the periods of operation of the steam generating units or process heater. All periods that are not recorded shall be considered and reported as a deviation. The records must be readily available for inspection.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: 49-V-01	
Control Device ID No.: GF-1	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121
Pollutant: VOC	Main Standard: § 115.121(b)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Once per hour	
Averaging Period: n/a	
Deviation Limit: Any monitoring which indicates the lack of a pilot flames shall be considered and reported as a deviation when vent is routed to the flare, GF-1, for vapor control.	
Periodic Monitoring Text: Measure and record the presence of the pilot flame or maintain records of alarm events and duration of alarm events. The presence of a flare pilot flame shall be monitored using a thermocouple or any other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. The monitoring instrumentation shall be maintained, calibrated and operated in accordance with manufacturer's specifications or other written procedures. Any monitoring data which indicates the lack of a pilot flame shall be considered and reported as a deviation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: 70-TK-109	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart K	SOP Index No.: 60K-c
Pollutant: VOC	Main Standard: § 60.112(a)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Any monitoring data in which the roof is not floating on the surface of the VOC, if liquid has accumulated on the IFR, the seals are detached, or if there are holes or tears in the seal fabric shall be considered a deviation.	
Periodic Monitoring Text: Visually inspect and record the inspection of the internal floating roof to ensure: the roof is floating on the surface of the VOC and, liquid has not accumulated on the internal floating roof, the seals are not detached, and there are no holes or tears in the seal fabric. Any monitoring data in which the roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: 70-TK-109	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart K	SOP Index No.: 60K-d
Pollutant: VOC	Main Standard: § 60.112(a)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Any monitoring data in which the roof is not floating on the surface of the VOC, if liquid has accumulated on the IFR, the seals are detached, or if there are holes or tears in the seal fabric shall be considered a deviation.	
Periodic Monitoring Text: Visually inspect and record the inspection of the internal floating roof to ensure: the roof is floating on the surface of the VOC and, liquid has not accumulated on the internal floating roof, the seals are not detached, and there are no holes or tears in the seal fabric. Any monitoring data in which the roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: APISEP	
Control Device ID No.: 124	Control Device Type: Vapor Combustor
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Water Separation	SOP Index No.: R5131
Pollutant: VOC	Main Standard: § 115.132(b)(3)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: n/a*	
Deviation Limit: Minimum combustor temperature of 1645 F.	
Periodic Monitoring Text: Measure and record the combustion temperature in the combustion chamber or immediately downstream of the combustion chamber. The monitoring instrumentation shall be maintained, calibrated and operated in accordance with manufacturer's specifications or other written procedures. Any monitoring data below the minimum limit shall be considered and reported as a deviation.	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: GRP-EPN118	
Control Device ID No.: GRP-EPN118	Control Device Type: Other Control Device Type
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121
Pollutant: VOC	Main Standard: § 115.121(b)
Monitoring Information	
Indicator: Exhaust Gas Temperature	
Minimum Frequency: once per week	
Averaging Period: n/a*	
Deviation Limit: Maximum exhaust gas temperature = 121 degrees F	
Periodic Monitoring Text: Measure and record the exhaust gas temperature at the outlet of the condenser system. The monitoring instrumentation shall be maintained, calibrated and operated in accordance with manufacturer's specifications or other written procedures. Any monitoring data above the maximum limit shall be considered and reported as a deviation.	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: GRP-EPN118	
Control Device ID No.: 13-H-01A	Control Device Type: Steam Generating Unit (Boiler)/Process Heater (Design heat input is greater than or equal to 44MW)
Control Device ID No.: 13-H-01B	Control Device Type: Steam Generating Unit (Boiler)/Process Heater (Design heat input is greater than or equal to 44MW)
Control Device ID No.: 13-H-01C	Control Device Type: Steam Generating Unit (Boiler)/Process Heater (Design heat input is greater than or equal to 44MW)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121a
Pollutant: VOC	Main Standard: § 115.121(b)
Monitoring Information	
Indicator: Period of Operation	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: All periods of operation that are not recorded are to be considered and reported as a deviation when vent is routed to hydrogen reformer heater, 13-H-01A, 13-H-01B, 13-H-01C for vapor control.	
Periodic Monitoring Text: Monitor and record the periods of operation of the steam generating units or process heater. All periods that are not recorded shall be considered and reported as a deviation. The records must be readily available for inspection.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: GRP-EPN126A	
Control Device ID No.: MFL-1	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121
Pollutant: VOC	Main Standard: § 115.121(b)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Once per hour	
Averaging Period: n/a	
Deviation Limit: Any monitoring which indicates the lack of a pilot flames shall be considered and reported as a deviation when vent is routed to the flare, MFL-1, for vapor control.	
Periodic Monitoring Text: Measure and record the presence of the pilot flame or maintain records of alarm events and duration of alarm events. The presence of a flare pilot flame shall be monitored using a thermocouple or any other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. The monitoring instrumentation shall be maintained, calibrated and operated in accordance with manufacturer's specifications or other written procedures. Any monitoring data which indicates the lack of a pilot flame shall be considered and reported as a deviation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: GRP-EPN126B	
Control Device ID No.: MFL-1	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121
Pollutant: VOC	Main Standard: § 115.121(b)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Once per hour	
Averaging Period: n/a	
Deviation Limit: Any monitoring which indicates the lack of a pilot flames shall be considered and reported as a deviation when vent is routed to the flare, MFL-1, for vapor control.	
Periodic Monitoring Text: Measure and record the presence of the pilot flame or maintain records of alarm events and duration of alarm events. The presence of a flare pilot flame shall be monitored using a thermocouple or any other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. The monitoring instrumentation shall be maintained, calibrated and operated in accordance with manufacturer's specifications or other written procedures. Any monitoring data which indicates the lack of a pilot flame shall be considered and reported as a deviation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: GRP-EPN126B	
Control Device ID No.: GRP-49HTR	Control Device Type: Steam Generating Unit (Boiler)/Process Heater (Design heat input is greater than or equal to 44MW)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121a
Pollutant: VOC	Main Standard: § 115.121(b)
Monitoring Information	
Indicator: Period of Operation	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: All periods of operation that are not recorded are to be considered and reported as a deviation when vent is routed to the reformer heater, GRP-49HTR, for vapor control.	
Periodic Monitoring Text: Monitor and record the periods of operation of the steam generating units or process heater. All periods that are not recorded shall be considered and reported as a deviation. The records must be readily available for inspection.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: GRP-EPN135	
Control Device ID No.: MFL-1	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121
Pollutant: VOC	Main Standard: § 115.121(b)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Once per hour	
Averaging Period: n/a	
Deviation Limit: Any monitoring which indicates the lack of a pilot flames shall be considered and reported as a deviation when vent is routed to the flare, MFL-1, for vapor control.	
Periodic Monitoring Text: Measure and record the presence of the pilot flame or maintain records of alarm events and duration of alarm events. The presence of a flare pilot flame shall be monitored using a thermocouple or any other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. The monitoring instrumentation shall be maintained, calibrated and operated in accordance with manufacturer's specifications or other written procedures. Any monitoring data which indicates the lack of a pilot flame shall be considered and reported as a deviation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: GRP-IRLQK1	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart K	SOP Index No.: 60K-c
Pollutant: VOC	Main Standard: § 60.112(a)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Any monitoring data in which the roof is not floating on the surface of the VOC, if liquid has accumulated on the IFR, the seals are detached, or if there are holes or tears in the seal fabric shall be considered a deviation.	
Periodic Monitoring Text: Visually inspect and record the inspection of the internal floating roof to ensure: the roof is floating on the surface of the VOC and, liquid has not accumulated on the internal floating roof, the seals are not detached, and there are no holes or tears in the seal fabric. Any monitoring data in which the roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: GRP-IRLQK1	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart K	SOP Index No.: 60K-d
Pollutant: VOC	Main Standard: § 60.112(a)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Any monitoring data in which the roof is not floating on the surface of the VOC, if liquid has accumulated on the IFR, the seals are detached, or if there are holes or tears in the seal fabric shall be considered a deviation.	
Periodic Monitoring Text: Visually inspect and record the inspection of the internal floating roof to ensure: the roof is floating on the surface of the VOC and, liquid has not accumulated on the internal floating roof, the seals are not detached, and there are no holes or tears in the seal fabric. Any monitoring data in which the roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: GRP-IRMTK1	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart K	SOP Index No.: 60K-c
Pollutant: VOC	Main Standard: § 60.112(a)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Any monitoring data in which the roof is not floating on the surface of the VOC, if liquid has accumulated on the IFR, the seals are detached, or if there are holes or tears in the seal fabric shall be considered a deviation.	
Periodic Monitoring Text: Visually inspect and record the inspection of the internal floating roof to ensure: the roof is floating on the surface of the VOC and, liquid has not accumulated on the internal floating roof, the seals are not detached, and there are no holes or tears in the seal fabric. Any monitoring data in which the roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: GRP-IRMTK1	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart K	SOP Index No.: 60K-d
Pollutant: VOC	Main Standard: § 60.112(a)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Any monitoring data in which the roof is not floating on the surface of the VOC, if liquid has accumulated on the IFR, the seals are detached, or if there are holes or tears in the seal fabric shall be considered a deviation.	
Periodic Monitoring Text: Visually inspect and record the inspection of the internal floating roof to ensure: the roof is floating on the surface of the VOC and, liquid has not accumulated on the internal floating roof, the seals are not detached, and there are no holes or tears in the seal fabric. Any monitoring data in which the roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: GRP-VACJET	
Control Device ID No.: 02-H-01	Control Device Type: Other Control Device Type
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Unit Turn & Vac System-Pet Ref	SOP Index No.: R5311a
Pollutant: VOC	Main Standard: § 115.311(b)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: n/a*	
Deviation Limit: Minimum Temperature = 1200 F	
Periodic Monitoring Text: Measure and record the combustion temperature in the combustion chamber or immediately downstream of the combustion chamber into which the volatile organic compound is introduced. Any monitoring data below the minimum limit shall be considered and reported as a deviation.	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: GRP-VACJET	
Control Device ID No.: MFL-1	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Unit Turn & Vac System-Pet Ref	SOP Index No.: R5311b
Pollutant: VOC	Main Standard: § 115.311(b)(1)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Once per hour	
Averaging Period: n/a	
Deviation Limit: Lack of a pilot flame shall be considered and reported as a deviation.	
Periodic Monitoring Text: Measure and record the presence of the pilot flame or maintain records of alarm events and duration of alarm events. The presence of a flare pilot flame shall be monitored using a thermocouple or any other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. The monitoring instrumentation shall be maintained, calibrated and operated in accordance with manufacturer's specifications or other written procedures. Any monitoring data which indicates the lack of a pilot flame shall be considered and reported as a deviation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: MFL-1B	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(B)
Monitoring Information	
Indicator: Visible Emissions	
Minimum Frequency: Once per week	
Averaging Period: n/a	
Deviation Limit: Any visible emissions observed on a weekly basis or a Test Method 9 can be performed as soon as practicable within 24 hours of observation with the opacity limit not to exceed 20% averaged over a 6 minute period.	
Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. If visible emissions are observed, the permit holder shall report a deviation. As an alternative, the permit holder may determine the opacity consistent with Test Method 9, as soon as practicable, but no later than 24 hours after observing visible emissions. If the result of the Test Method 9 is an opacity above the corresponding opacity limit, the permit holder shall report a deviation.	

Permit Shield

Permit Shield **350**

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
13-H-01C	N/A	30 TAC Chapter 112, Sulfur Compounds	Boiler does not burn solid nor liquid fuel.
13-H-01C	N/A	40 CFR Part 60, Subpart D	Boiler does not have a heat input of greater than 250 MMBtu/hr.
13-H-01C	N/A	40 CFR Part 60, Subpart Da	Boiler does not have a heat input of greater than 250 MMBtu/hr and is not an electric utility steam generating units.
13-H-01C	N/A	40 CFR Part 60, Subpart Db	Boiler construction began before June 19, 1984.
13-H-01C	N/A	40 CFR Part 60, Subpart Dc	Boiler construction began before June 9, 1989.
30-B-02	N/A	30 TAC Chapter 112, Sulfur Compounds	Boiler does not burn solid nor liquid fuel.
30-B-02	N/A	40 CFR Part 60, Subpart D	Boilers do not have a heat input of greater than 250 MMBtu/hr.
30-B-02	N/A	40 CFR Part 60, Subpart Da	Boilers do not have a heat input of greater than 250 MMBtu/hr, and boilers are not electric utility steam generating units.
30-B-02	N/A	40 CFR Part 60, Subpart Dc	Boilers have a heat input of greater than 100 MMBtu/hr.
30-B-03	N/A	30 TAC Chapter 112, Sulfur Compounds	Boiler does not burn solid nor liquid fuel.

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
30-B-03	N/A	40 CFR Part 60, Subpart D	Boilers do not have a heat input of greater than 250 MMBtu/hr.
30-B-03	N/A	40 CFR Part 60, Subpart Da	Boilers do not have a heat input of greater than 250 MMBtu/hr, and boilers are not electric utility steam generating units.
30-B-03	N/A	40 CFR Part 60, Subpart Dc	Boilers have a heat input of greater than 100 MMBtu/hr.
46-H-01	N/A	30 TAC Chapter 112, Sulfur Compounds	Hot oil heater does not burn solid nor liquid fuel.
46-H-01	N/A	40 CFR Part 60, Subpart D	Hot oil heater does not have a heat input of greater than 250 MMBtu/hr.
46-H-01	N/A	40 CFR Part 60, Subpart Da	Hot oil heater does not have a heat input of greater than 250 MMBtu/hr and is not an electric utility steam generating unit.
46-H-01	N/A	40 CFR Part 60, Subpart Db	Hot oil heater has a heat input of less than 100 MMBtu/hr.
46-H-01	N/A	40 CFR Part 60, Subpart Dc	Hot oil heater construction began before June 9, 1989.
GRP-EPN118	13T01, SMR-CO2-VT	40 CFR Part 63, Subpart CC	By definition, CO2 vents from hydrogen production plants are not subject to vent rules.
GRP-EPN118	13T01, SMR-CO2-VT	40 CFR Part 63, Subpart G	Not subject to HON - unit does not produce a listed

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
			chemical.
GRP-EPN121	2202-L, 2203-L, 24-ST-02	30 TAC Chapter 115, Vent Gas Controls	Vent downstream of combustion device.
GRP-EPN121	2202-L, 2203-L, 24-ST-02	40 CFR Part 63, Subpart CC	Vents from Cracking Units and Sulfur Recovery Units are except from MACT CC
GRP-EPN121	2202-L, 2203-L, 24-ST-02	40 CFR Part 63, Subpart G	Process vent is not part of a SOCMI process
GRP-EPN135	01V01, 01V13, 01V16, 24V36	40 CFR Part 63, Subpart G	Does not meet the definition of subject process vents.
GRP-EPN155	49-SCRUB	30 TAC Chapter 115, Vent Gas Controls	Vent downstream of combustion device.
GRP-EPN155	49-SCRUB	40 CFR Part 63, Subpart CC	Vents from catalytic reformer catalyst regeneration are except from MACT CC.
GRP-EPN155	49-SCRUB	40 CFR Part 63, Subpart G	Does not meet the definition of subject process vents.
GRP-EPN168	38-SCRUB	30 TAC Chapter 115, Vent Gas Controls	Vent downstream of combustion device.
GRP-EPN168	38-SCRUB	40 CFR Part 63, Subpart CC	Not part of a petroleum refining process unit.
GRP-EPN168	38-SCRUB	40 CFR Part 63, Subpart G	Does not meet the definition of subject process vents.
MFL-1B	N/A	40 CFR Part 60, Subpart A	Flare not used as control device for a source subject to part 60.
54F-MTBE	N/A	40 CFR Part 60, Subpart VV	Does not produce listed chemical

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
54F-MTBE	N/A	40 CFR Part 63, Subpart H	Not subject to HON - unit does not produce a listed chemical.
BUTAMER	N/A	30 TAC Chapter 115, Fugitives Pet Ref B Counties	Not a petroleum unit.
FUELDRM	N/A	40 CFR Part 60, Subpart GGG	Not a process unit.
FUELDRM	N/A	40 CFR Part 60, Subpart VV	Does not produce listed chemical.
GRP-5GCCVV	11F-HOC, 49-RSU, 49-XFU, 4F, CRUDE UNIT, CRU-FUG, HCU-FUG, HOC-FUG, HRLEU-FUG, LRU, NHT-FUG	40 CFR Part 61, Subpart J	MACT CC overrides
GRP-R5-1	41F, AMINE-FUG, SMR-FUG, SWS-FUG	40 CFR Part 60, Subpart GGG	Construction before applicability date
GRP-R5-1	41F, AMINE-FUG, SMR-FUG, SWS-FUG	40 CFR Part 60, Subpart VV	Does not produce listed chemical
GRP-R5-1	41F, AMINE-FUG, SMR-FUG, SWS-FUG	40 CFR Part 63, Subpart CC	No HAPS
GRP-R5-2	30B01F, 30B02F, 30B03F	40 CFR Part 60, Subpart GGG	Not a process unit
GRP-R5-2	30B01F, 30B02F, 30B03F	40 CFR Part 60, Subpart VV	Does not produce listed chemical
GRP-R5-2	30B01F, 30B02F, 30B03F	40 CFR Part 63, Subpart CC	No HAPS
GRP-R5CC	11F-HDS, ALKY-FUG, HDS FUG	40 CFR Part 60, Subpart GGG	Construction before applicability date

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
GRP-R5CC	11F-HDS, ALKY-FUG, HDS FUG	40 CFR Part 60, Subpart VV	Does not produce listed chemical
GRP-R5CC2	DOCKS-F, GAS BLEND, PIPING FUG, TERMIN 2/2A, TERMINAL 1, TERMINAL 3	40 CFR Part 60, Subpart GGG	Not a process unit
GRP-R5CC2	DOCKS-F, GAS BLEND, PIPING FUG, TERMIN 2/2A, TERMINAL 1, TERMINAL 3	40 CFR Part 60, Subpart VV	Does not produce listed chemical.
GRP-R5G	46F/24F, 47PSA, VACUUMUNIT	40 CFR Part 60, Subpart VV	Does not produce listed chemical
GRP-R5G	46F/24F, 47PSA, VACUUMUNIT	40 CFR Part 63, Subpart CC	No HAPS
LPG STORAG	N/A	40 CFR Part 60, Subpart GGG	Not a process unit
LPG STORAG	N/A	40 CFR Part 60, Subpart VV	Does not produce listed chemical
LPG STORAG	N/A	40 CFR Part 63, Subpart CC	No HAPS
MTBE-FUG	N/A	40 CFR Part 60, Subpart VV	Does not produce listed chemical
MTBE-FUG	N/A	40 CFR Part 63, Subpart H	Not subject to HON - unit does not produce a listed chemical.
MVRUF	N/A	40 CFR Part 60, Subpart GGG	Not a process unit.
MVRUF	N/A	40 CFR Part 60, Subpart VV	Does not produce listed chemical.
OLEFLEX-FU	N/A	30 TAC Chapter 115, Fugitives Pet Ref B Counties	Not a petroleum unit

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
OLEFLEX-FU	N/A	40 CFR Part 60, Subpart GGG	(SOP 60GGGEXVV) Facilities subject to Subpart VV are excluded from Subpart GGG.
OLEFLEX-FU	N/A	40 CFR Part 63, Subpart CC	Not a petroleum refining process unit.
SRU	N/A	40 CFR Part 60, Subpart LLL	Not onshore natural gas processing plant.
SRU3	N/A	40 CFR Part 60, Subpart LLL	Not onshore natural gas processing plant.
GRP-CT	ALKY-CT, BUP-CT, CRUDE-CT, HOC-CT	40 CFR Part 63, Subpart Q	Cooling towers do not use chromium-based water treatment chemicals.
BARGEDOCKS	N/A	30 TAC Chapter 115, Loading and Unloading of VOC	Marine loading not subject to requirements.
BARGEDOCKS	N/A	40 CFR Part 60, Subpart XX	Does not load tank trucks.
BARGEDOCKS	N/A	40 CFR Part 63, Subpart G	Not a transfer rack by MACT F definition.
BARGEDOCKS	N/A	40 CFR Part 63, Subpart R	Does not load tank trucks
SHIPDOCKS	N/A	30 TAC Chapter 115, Loading and Unloading of VOC	Marine loading not subject to requirements.
SHIPDOCKS	N/A	40 CFR Part 60, Subpart XX	Does not load tank trucks.
SHIPDOCKS	N/A	40 CFR Part 63, Subpart G	Not a transfer rack by MACT F definition.
SHIPDOCKS	N/A	40 CFR Part 63, Subpart R	Does not load tank trucks
T-RACK	N/A	40 CFR Part 61, Subpart BB	Truck rack does not load benzene.

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
T-RACK	N/A	40 CFR Part 63, Subpart G	Not a transfer rack by MACT F definition.
T-RACK	N/A	40 CFR Part 63, Subpart R	Subject to MACT CC - overrides MACT R
T-RACK	N/A	40 CFR Part 63, Subpart Y	Not marine loading
VRU	N/A	30 TAC Chapter 115, Loading and Unloading of VOC	Marine loading not subject to requirements.
VRU	N/A	40 CFR Part 60, Subpart XX	Does not load tank trucks.
VRU	N/A	40 CFR Part 63, Subpart F	Not a transfer rack by MACT F definition.
VRU	N/A	40 CFR Part 63, Subpart R	Does not load tank trucks
GRP-SULJET	43J01, 43J02	30 TAC Chapter 115, Unit Turn & Vac System-Pet Ref	No VOCs in the vent stream.
13-H-01A	N/A	30 TAC Chapter 112, Sulfur Compounds	Heater does not burn liquid fuel or solid fuel.
13-H-01B	N/A	30 TAC Chapter 112, Sulfur Compounds	Heater does not burn liquid or solid fuel.
38-H-01	N/A	30 TAC Chapter 112, Sulfur Compounds	Heater does not burn liquid or solid fuel.
38-H-02	N/A	30 TAC Chapter 112, Sulfur Compounds	Heater does not burn liquid or solid fuel.
49-H-91	N/A	30 TAC Chapter 112, Sulfur	Heaters do not burn liquid or solid fuel.

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
		Compounds	
52-H-01	N/A	30 TAC Chapter 112, Sulfur Compounds	Heater does not burn liquid or solid fuel.
GRP-49HTR	49-H-01, 49-H-02, 49-H-03, 49-H-04	30 TAC Chapter 112, Sulfur Compounds	Heaters do not burn liquid or solid fuel.
GRP-HTR	01-H-01, 01-H-02, 01-H-03, 02-H-01, 02-H-02, 11-H-01, 12-H01A, 12-H01B, 12-H02, 31-H-01, 36-H-01, 38-H-03, 47-H-05, 49-H-02NEW, 49-H-71, 49-H-90, 49-HDIC6	30 TAC Chapter 112, Sulfur Compounds	Heaters do not burn liquid or solid fuel.
GRP-HTRJ	47-H-01, 47-H-02, 47-H-03, 47-H-04, 48-H-01	30 TAC Chapter 112, Sulfur Compounds	Heaters do not burn liquid or solid fuel.
03-TK-156	N/A	40 CFR Part 63, Subpart G	Not subject to HON - unit does not produce a listed chemical and thus tanks no longer store a listed chemical.
03-TK-161	N/A	40 CFR Part 63, Subpart G	Not subject to HON - unit does not produce a listed chemical and thus tanks no longer store a listed chemical.
43-TK-04	N/A	40 CFR Part 63, Subpart CC	Tank does not store HAPs listed in Table 1 of 63 Subpart CC
43-TK-04	N/A	40 CFR Part 63, Subpart G	Not subject because not associated with SOCMI unit

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
49-V-14	N/A	30 TAC Chapter 115, Storage of VOCs	When not storing VOC, tank is not subject to regulation. When storing any VOC, a storage tank with storage capacity less than 1,000 gallons is exempt.
49-V-14	N/A	40 CFR Part 60, Subpart Kb	Tank capacity less than 40,000 gallons.
49-V-14	N/A	40 CFR Part 63, Subpart CC	Tank does not store HAPs listed in Table 1 of 63 Subpart CC
49-V-14	N/A	40 CFR Part 63, Subpart G	Not subject because not associated with SOCMI unit.
50-TK-60	N/A	40 CFR Part 63, Subpart G	Not subject because not associated with SOCMI unit.
70-TK-109	N/A	40 CFR Part 63, Subpart G	Not subject because not associated with SOCMI unit.
70-TK-110	N/A	40 CFR Part 63, Subpart G	Not subject because not associated with SOCMI unit.
70-TK-138	N/A	40 CFR Part 63, Subpart G	Not subject because not associated with SOCMI unit.
70-TK-140	N/A	40 CFR Part 60, Subpart Kb	Not subject to Subpart Kb - tank stores a VOL with a maximum true vapor pressure less than 2.2 psia.
83-TK-155	N/A	40 CFR Part 63, Subpart CC	Does not process MACT CC Group 1 wastewater streams.
83-TK-155	N/A	40 CFR Part 63, Subpart DD	The facility doesn't process wastes, materials are considered off-spec products to be recycled. The facility does process both in-plant generated and employee household "do-it-yourself" used motor oil

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
			that doesn't meet the definition of used oil.
83-TK-155	N/A	40 CFR Part 63, Subpart G	Not subject because not associated with SOCMI unit.
83-TK-23	N/A	40 CFR Part 63, Subpart CC	Does not process MACT CC Group 1 wastewater streams.
83-TK-23	N/A	40 CFR Part 63, Subpart DD	The facility doesn't process wastes, materials are considered off-spec products to be recycled. The facility does process both in-plant generated and employee household "do-it-yourself" used motor oil that doesn't meet the definition of used oil.
83-TK-23	N/A	40 CFR Part 63, Subpart G	Not subject because not associated with SOCMI unit.
83-TK-25	N/A	40 CFR Part 63, Subpart CC	Tank does not store HAPs listed in Table 1 of 63 Subpart CC
83-TK-25	N/A	40 CFR Part 63, Subpart G	Not subject because not associated with SOCMI unit
83-TK-26	N/A	40 CFR Part 63, Subpart G	Not subject because not associated with SOCMI unit.
83-TK-28	N/A	40 CFR Part 63, Subpart CC	Tank does not store HAPs listed in Table 1 of 63 Subpart CC.
83-TK-28	N/A	40 CFR Part 63, Subpart G	Not subject because not associated with SOCMI unit.
83-V-97	N/A	40 CFR Part 63, Subpart CC	Does not process MACT CC Group 1 wastewater streams.
83-V-97	N/A	40 CFR Part 63, Subpart G	Not subject because not associated with SOCMI unit.

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
GRP-EFRA1	50-TK-57, 50-TK-59, 72-TK-14, 72-TK-15	40 CFR Part 63, Subpart G	Not subject because not associated with SOCMI unit.
GRP-ERLQA	83-V-58, 83-V-59	40 CFR Part 63, Subpart G	Not subject because not associated with SOCMI unit.
GRP-FIXA2	70-TK-105, 70-TK-98, 73-TK-9	40 CFR Part 63, Subpart G	Not subject because not associated with SOCMI unit.
GRP-FIXAN	70-TK-149, 70-TK-150, 72-TK-18, 72-TK-19, 72-TK-20	40 CFR Part 63, Subpart CC	Tank does not store HAPs listed in Table 1 of 63 Subpart CC
GRP-FIXAN	70-TK-149, 70-TK-150, 72-TK-18, 72-TK-19, 72-TK-20	40 CFR Part 63, Subpart G	Not subject because not associated with SOCMI unit
GRP-FIXAS	43-TK-08, 43-V-10	40 CFR Part 60, Subpart Ka	Tank capacity less than 40,000 gallons.
GRP-FIXAS	43-TK-08, 43-V-10	40 CFR Part 63, Subpart CC	Tank does not store HAPs listed in Table 1 of 63 Subpart CC
GRP-FIXAS	43-TK-08, 43-V-10	40 CFR Part 63, Subpart G	Not subject because not associated with SOCMI unit
GRP-FIXK2	70-TK-96, 70-TK-97	40 CFR Part 63, Subpart G	Not subject because not associated with SOCMI unit.
GRP-IRLQB1	50-TK-62, 50-TK-63, 72-TK-111	40 CFR Part 63, Subpart G	Not subject because not associated with SOCMI unit.
GRP-IRLQBG	50-TK-64, 50-TK-65	40 CFR Part 63, Subpart G	Not subject to HON - unit does not produce a listed chemical and thus tanks no longer store a listed chemical.
GRP-IRLQK1	70-TK-101, 70-TK-102, 70-TK-103, 70-TK-108, 70-TK-137, 70-TK-94	40 CFR Part 63, Subpart G	Not subject because not associated with SOCMI unit.

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
GRP-IRMTA1	50-TK-58, 70-TK-93	40 CFR Part 63, Subpart G	Not subject because not associated with SOCMI unit.
GRP-IRMTB1	70-TK-115, 70-TK-116, 72-TK-112, TK-114	40 CFR Part 63, Subpart G	Not subject because not associated with SOCMI unit.
GRP-IRMTBQ	83-TK-159, 83-TK-160	40 CFR Part 63, Subpart G	Not subject because not associated with SOCMI unit.
GRP-IRMTK1	70-TK-100, 70-TK-104, 70-TK-139, 70-TK-99	40 CFR Part 63, Subpart G	Not subject because not associated with SOCMI unit.
TK-51	N/A	40 CFR Part 63, Subpart G	Not subject because not associated with SOCMI unit.
APISEP	N/A	40 CFR Part 63, Subpart CC	Does not process MACT CC Group 1 wastewater streams.
APISEP	N/A	40 CFR Part 63, Subpart DD	Facility does not process off-site waste. Used oil at crude refineries is exempt under 279.10(g)(3).
APISEP	N/A	40 CFR Part 63, Subpart VV	Facility is not subject to 40 CFR Part 60, 61, 63 subparts which reference this subpart

New Source Review Authorization References

New Source Review Authorization References 363

New Source Review Authorization References by Emission Unit..... 365

New Source Review Authorization References

The New Source Review authorizations listed in the table below are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Prevention of Significant Deterioration (PSD) Permits	
PSD Permit No.: PSDTX324M13	
Title 30 TAC Chapter 116 Permits, Special Permits, and Other Authorizations (Other Than Permits By Rule, PSD Permits, or NA Permits) for the Application Area.	
Authorization No.: 106965	
Authorization No.: 109543	
Authorization No.: 20740	
Authorization No.: 20992	
Authorization No.: 38754	
Authorization No.: 55294	
Authorization No.: 55362	
Authorization No.: 55688	
Authorization No.: 86443	
Authorization No.: 92722	
Authorization No.: 93732	
Authorization No.: 95652	
Permits By Rule (30 TAC Chapter 106) for the Application Area	
Number: 69	Version No./Date: 05/05/1976
Number: 69	Version No./Date: 09/23/1982
Number: 71	Version No./Date: 05/05/1976
Number: 86	Version No./Date: 08/30/1988
Number: 86	Version No./Date: 09/12/1989
Number: 86	Version No./Date: 09/13/1993
Number: 102	Version No./Date: 05/12/1981
Number: 102	Version No./Date: 09/23/1982
Number: 118	Version No./Date: 09/12/1989
Number: 125	Version No./Date: 09/23/1982
Number: 106.261	Version No./Date: 09/04/2000
Number: 106.261	Version No./Date: 11/01/2003

New Source Review Authorization References

The New Source Review authorizations listed in the table below are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Number: 106.262	Version No./Date: 11/01/2003
Number: 106.371	Version No./Date: 09/04/2000
Number: 106.472	Version No./Date: 09/04/2000
Number: 106.478	Version No./Date: 03/14/1997
Number: 106.478	Version No./Date: 09/04/2000
Number: 106.511	Version No./Date: 09/04/2000
Number: 106.532	Version No./Date: 03/14/1997

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
01-H-01	CRUDE HEATER	38754, PSDTX324M13
01-H-02	CRD PREFLASH HTR	38754, PSDTX324M13
01-H-03	CRD STAB HEATER	38754, PSDTX324M13
01V01	CRUDE TOWER OVERHEAD ACCUMULATOR	38754, PSDTX324M13
01V13	PREFLASH OVERHEAD ACCUMULATOR	38754, PSDTX324M13
01V16	STABILIZER OVERHEAD ACCUMULATOR	38754, PSDTX324M13
02-H-01	VACUUM HEATER	38754, PSDTX324M13
02-H-02	VACUUM PF HEATER	38754, PSDTX324M13
02J01	VACUUM TOWER JET	38754, PSDTX324M13
02J02	VACUUM TOWER JET	38754, PSDTX324M13
02J03	VACUUM TOWER JET	38754, PSDTX324M13
02J04	VACUUM TOWER JET	38754, PSDTX324M13
02J05	VACUUM TOWER JET	38754, PSDTX324M13
02J06	VACUUM TOWER JET	38754, PSDTX324M13
02-V-12	VACUUM UNIT COOLANT OIL HOLDUP TANK	106.261/11/01/2003
03-TK-156	TANK NO. 156	38754, PSDTX324M13
03-TK-161	TANK NO. 161	38754, PSDTX324M13
11F-HDS	HDS DESALTER UNIT	38754, PSDTX324M13, 106.261/11/01/2003
11F-HOC	HOC DESALTER UNIT	38754, PSDTX324M13

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
11-H-01	DESALTER HEATER	38754, PSDTX324M13
12-H01A	HDS HTR. A	38754, PSDTX324M13
12-H01B	HDS HTR. B	38754, PSDTX324M13
12-H02	HDS PREHEATER	38754, PSDTX324M13
13-H-01A	H2 REFORMER HTR	38754, PSDTX324M13
13-H-01B	H2 REFORMER HTR	38754, PSDTX324M13
13-H-01C	H2 REFORMER HEATER	38754, PSDTX324M13
13T01	CONDENSATE STRIPPER	38754, 86443, PSDTX324M13
16-P-11-EN	DIESEL ENGINE DRIVER FOR PUMP	106.511/09/04/2000
16-P-12-EN	DIESEL ENGINE DRIVER FOR PUMP	106.511/09/04/2000
16-P-13-EN	DIESEL ENGINE DRIVER FOR PUMP	106.511/09/04/2000
16-P-14-EN	DIESEL ENGINE DRIVER FOR PUMP	106.511/09/04/2000
16-P-4-EN	DIESEL ENGINE DRIVER FOR PUMP	38754, PSDTX324M13
16-P-7-EN	DIESEL ENGINE DRIVER FOR PUMP	38754, PSDTX324M13
20-V-03	LRU STABILIZER O/H VENT	38754, PSDTX324M13
2202-L	LPG OXIDIZER VENT	38754, PSDTX324M13
2203-L	LPG OXIDIZER VENT	38754, PSDTX324M13
24-ST-01	FCCU	38754, PSDTX324M13
24-ST-02	CAUSTIC SCRUBBER/SULFTEN INCINERATOR/SCOT INCINERATOR	38754, PSDTX324M13

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
24V36	WATER DEGASSING DRUM	38754, PSDTX324M13
30B01F	30-B-01 FUGITIVES	38754, PSDTX324M13
30-B-02	30-B-02 BOILER	38754, PSDTX324M13
30B02F	30-B-02 FUGITIVES	38754, PSDTX324M13
30-B-03	30-B-03 BOILER	20740
30B03F	30-B-03 FUGITIVES	20740, 38754, PSDTX324M13
30-B-04	30-B-04 BOILER	95652
30B04F	BOILER 30-B-04 FUGITIVES	95652
31-H-01	ALKY REBOILER	38754, PSDTX324M13
31V05	DEPROPANIZER OVHD	38754, PSDTX324M13
36-H-01	BUTAMER HEATER	38754, PSDTX324M13
36J01	BUTAMER TURNAROUND VACUUM JET	118/09/12/1989
36-T-02	BUTAMER STABILIZER VENT 36-T-02	38754, PSDTX324M13
36-V-06	BUTAMER DEISOBUT OVERHEAD ACCUMULATOR 36-V-06	38754, PSDTX324M13
37-V-03	MTBE BUTENE COLUMN OVERHEAD DRUM 37-V-03	38754, PSDTX324M13
37-V-05	MTBE DEPROPANIZER OVERHEAD DRUM 37-V-05	38754, PSDTX324M13
38-H-01	OLEFLEX CHARGE HEATER	38754, PSDTX324M13
38-H-02	OLEFLEX INTERHEATER	38754, PSDTX324M13
38-H-03	OLEFLEX INTERHEATER	38754, PSDTX324M13

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
38J01	OLEFLEX TURNAROUND VACUUM JET	118/09/12/1989
38-SCRUB	OLEFLEX SCRUBBER	38754, PSDTX324M13
38-V-23	OLEFLEX PSA FEED COMPRESSOR 38-V-23	38754, PSDTX324M13
38-V-32	OLEFLEX PSA TAIL GAS COMP. SEC. OIL SEP. 38-V-32	38754, PSDTX324M13
38-V-54	OLEFLEX LOCK HOPPER #1	106.261/11/01/2003
38-V-55	OLEFLEX LOCK HOPPER #2	106.261/11/01/2003
41F	SRU FUGITIVES	38754, PSDTX324M13
41-H-07	SRU INCINERATOR	38754, PSDTX324M13
43J01	SULFUR LOADING VACUUM JET	118/09/12/1989
43J02	SULFUR PIT VACUUM JET	118/09/12/1989
43-TK-04	MDEA TANK	102/05/12/1981
43-TK-08	AMINE STORAGE TANK 43TK08	102/05/12/1981
43-V-10	AMINE SLOP TANK 43V10	86/09/12/1989
44-V-01	MAIN FUEL GAS DRUM	38754, PSDTX324M13
46F/24F	SULFTEN/SEU FUGITIVES	38754, PSDTX324M13
46-H-01	SULFTEN HEATER	38754, PSDTX324M13
47-H-01	HCU RX-01 47-H-01	38754, PSDTX324M13
47-H-02	HCU RX-02 47-H-02	38754, PSDTX324M13
47-H-03	DEBUTAN. REBOILER 47-H-03	38754, PSDTX324M13

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
47-H-04	FRACTIONATOR REBOILER 47-H-04	38754, PSDTX324M13
47-H-05	HCU HEATER	38754, PSDTX324M13
47J01	HCU TURNAROUND VACUUM JET	118/09/12/1989
47L01PSA	PSA OFF-GAS	38754, PSDTX324M13
47PSA	PSA	38754, PSDTX324M13
47-V-02	HCU FEED SURGE DRUM	106.261/11/01/2003
48-H-01	NHT HEATER	38754, PSDTX324M13
48-V-01	NHT FEED SURGE DRUM	106.261/11/01/2003
49CRU	UNIT 49 CRU	38754, PSDTX324M13, 106.261/11/01/2003
49-H-01	CRU CHARGE HEATER 49-H-01A	38754, PSDTX324M13
49-H-02	CRU CHARGE HEATER 49-H-01B	38754, PSDTX324M13
49-H-02NEW	NO. 1 INTERHEATER	38754, PSDTX324M13
49-H-03	CRU NO.2 INTERHEATER 49-H-03	38754, PSDTX324M13
49-H-04	CRU NO.3 INTERHEATER 49-H-04	38754, PSDTX324M13
49-H-71	RSU HEATER	38754, PSDTX324M13
49-H-90	C7 SPLITTER REB.	38754, PSDTX324M13
49-H-91	C8 SPLITTER REB.	20992
49-HDIC6	CRU DEISOHEXANIZER REBOILER	38754, PSDTX324M13
49J01	CRU TURNAROUND VACUUM JET	118/09/12/1989

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
49-RSU	49-RSU	38754, PSDTX324M13, 106.261/11/01/2003
49-SCRUB	CRU SCRUBBER	38754, PSDTX324M13
49-V-01	NET GAS SEPARATOR DRUM	38754, PSDTX324M13
49V06	FUEL GAS DRUM NO. 1	38754, PSDTX324M13, 106.261/11/01/2003
49V07	FUEL GAS DRUM NO. 2	38754, PSDTX324M13, 106.261/11/01/2003
49-V-14	PERCHLOROETHYLENE DRUM 49V14	38754, PSDTX324M13
49-XFU	49-XFU	38754, PSDTX324M13, 106.261/11/01/2003
4F	LEU	38754, PSDTX324M13, 106.261/11/01/2003
50-TK-57	TANK NO. 57	38754, PSDTX324M13
50-TK-58	TANK NO. 58	38754, PSDTX324M13
50-TK-59	TANK NO. 59	38754, PSDTX324M13
50-TK-60	TANK NO. 60	38754, PSDTX324M13
50-TK-61	TANK NO. 61	38754, PSDTX324M13
50-TK-62	TANK NO. 62	38754, PSDTX324M13
50-TK-63	TANK NO. 63	38754, PSDTX324M13
50-TK-64	TANK NO. 64	38754, PSDTX324M13
50-TK-65	TANK NO. 65	38754, PSDTX324M13
52-H-01	GD CHARGE HEATER	38754, PSDTX324M13
54F-MTBE	MTBE/TAME FUGITIVES	38754, PSDTX324M13

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
54F-TAME	TAMU UNIT	38754, PSDTX324M13
54-V-42	HOC MTBE DME STRIPPER OVERHEAD DRUM 54-V-42	38754, PSDTX324M13
70-TK-100	TANK NO. 100	38754, PSDTX324M13
70-TK-101	TANK NO. 101	38754, PSDTX324M13
70-TK-102	TANK NO. 102	38754, PSDTX324M13
70-TK-103	TANK NO. 103	38754, PSDTX324M13
70-TK-104	TANK NO. 104	38754, PSDTX324M13
70-TK-105	TANK NO. 105	38754, PSDTX324M13
70-TK-108	TANK NO. 108	38754, PSDTX324M13
70-TK-109	TANK NO. 109	38754, PSDTX324M13
70-TK-110	TANK NO. 110	38754, PSDTX324M13
70-TK-115	TANK NO. 115	38754, PSDTX324M13
70-TK-116	TANK NO. 116	38754, PSDTX324M13
70-TK-137	TANK NO. 137	38754, PSDTX324M13
70-TK-138	TANK NO. 138	71/05/05/1976
70-TK-139	TANK NO. 139	38754, PSDTX324M13
70-TK-140	TANK NO. 140	106.532/03/14/1997
70-TK-149	TANK NO. 149	38754, PSDTX324M13
70-TK-150	TANK NO. 150	38754, PSDTX324M13

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
70-TK-66	TANK NO. 66	106.478/09/04/2000
70-TK-67	TANK NO. 67	106.478/09/04/2000
70-TK-68	TANK NO. 68	106.478/09/04/2000
70-TK-93	TANK NO. 93	38754, PSDTX324M13
70-TK-94	TANK NO. 94	38754, PSDTX324M13
70-TK-95	TANK NO. 95	38754, PSDTX324M13
70-TK-96	TANK NO. 96	38754, PSDTX324M13
70-TK-97	TANK NO. 97	38754, PSDTX324M13
70-TK-98	TANK NO. 98	38754, PSDTX324M13
70-TK-99	TANK NO. 99	38754, PSDTX324M13
72-TK-111	TANK NO.111	38754, PSDTX324M13
72-TK-112	TANK NO. 112	38754, PSDTX324M13
72-TK-14	TANK NO. 14	38754, PSDTX324M13
72-TK-15	TANK NO. 15	38754, PSDTX324M13
72-TK-16	TANK NO. 16	38754, PSDTX324M13
72-TK-17	TANK NO. 17	38754, PSDTX324M13
72-TK-18	TANK NO. 18	38754, PSDTX324M13
72-TK-19	TANK NO. 19	38754, PSDTX324M13, 106.261/11/01/2003
72-TK-20	TANK NO. 20	38754, PSDTX324M13

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
72-TK-75	TANK NO. 75	38754, PSDTX324M13
72-TK-77	TANK NO. 77	38754, PSDTX324M13
72-TK-78	TANK NO. 78	38754, PSDTX324M13
73-TK-166	TANK 166	109543
73-TK-167	TANK 167	109543
73-TK-9	TANK NO. 9	38754, PSDTX324M13
83P136A-EN	DIESEL ENGINE DRIVER FOR PUMP	106.511/09/04/2000
83P136B-EN	DIESEL ENGINE DRIVER FOR PUMP	106.511/09/04/2000
83-TK-155	TANK NO. 155	106.532/03/14/1997
83-TK-159	TANK NO. 159	86/08/30/1988
83-TK-160	TANK NO. 160	86/08/30/1988
83-TK-162	TANK NO. 162	106.532/03/14/1997
83-TK-23	TANK NO. 23	102/09/23/1982
83-TK-25	TANK NO. 25	106.532/03/14/1997
83-TK-26	TANK NO. 26	86/09/12/1989
83-TK-28	CATALYST STORAGE TANK 83TK28	106.478/03/14/1997
83-V-58	83-V-58-OIL ONLY	86/08/30/1988
83-V-59	83-V-59	86/08/30/1988
83-V-97	83-V-97	106.478/03/14/1997

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
83-V-98	83-V-98	106.478/03/14/1997
ALKY-CT	ALKY COOLING TOWER	38754, PSDTX324M13
ALKY-FUG	ALKY UNIT	38754, PSDTX324M13
AMINE-FUG	AMINE UNIT	38754, PSDTX324M13
APISEP	API SEPARATOR	38754, PSDTX324M13
ATU3FUG	AMINE TREATER NO. 3 FUGITIVES	38754, PSDTX324M13
BARGEDOCKS	BARGEDOCKS	38754, PSDTX324M13
BUP-CT	BUP COOLING TOWER	38754, PSDTX324M13
BUTAMER	BUTAMER UNIT	38754, PSDTX324M13, 106.261/11/01/2003
CD-LOADING	THERMAL OXIDIZER AREA	109543
CD-PIPING	PIPING FUGITIVES	109543
CRUDE UNIT	CU FUGITIVES	38754, PSDTX324M13, 106.261/11/01/2003
CRUDE-CT	CRUDE COOLING TOWER	38754, PSDTX324M13
CRU-FUG	CRU	38754, PSDTX324M13
DEGREASE-F	DEGREASING	125/09/23/1982
DOCKS-F	DOCKS	38754, PSDTX324M13, 106.261/11/01/2003
FUELDRM	FUEL GAS DRUM	38754, PSDTX324M13
GAS BLEND	GAS BLENDING	38754, PSDTX324M13
GDFUG	GD FUGITIVES	38754, PSDTX324M13, 106.261/11/01/2003

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
GF-1	GROUND FLARE	38754, PSDTX324M13
HCU-FUG	HCU	38754, PSDTX324M13, 106.261/11/01/2003
HDS FUG	HDS UNIT	38754, PSDTX324M13, 106.261/11/01/2003
HOC-CT	HOC COOLING TOWER	38754, PSDTX324M13
HOC-FUG	HOC UNIT	38754, PSDTX324M13, 106.261/11/01/2003
HRLEU-FUG	HRLEU UNIT	38754, PSDTX324M13, 106.261/11/01/2003
LPG STORAG	LPG STORAGE	38754, PSDTX324M13, 106.261/11/01/2003
LRU	LRU	38754, PSDTX324M13
MFL-1B	ACID GAS FLARE	38754, PSDTX324M13
MFL-1	MAIN FLARE	38754, PSDTX324M13
MTBE FL-2	MTBE FLARE	38754, PSDTX324M13
MTBE-FUG	MTBE / ISO-OCTENE	38754, PSDTX324M13, 106.261/11/01/2003
MVRUF	VRU FUGITIVES	38754, PSDTX324M13
NHT-FUG	NHT	38754, PSDTX324M13, 106.261/11/01/2003
OLEFLEX-FU	OLEFLEX	38754, PSDTX324M13
PIPING FUG	TRUCK RACK	38754, PSDTX324M13, 106.261/11/01/2003
RAIL-FUG	RAILCAR RACK FUGITIVES	38754, PSDTX324M13
RAILRACK1	RAILCAR RACK	38754, PSDTX324M13
SCOTFUG	SCOT UNIT FUGITIVES	38754, PSDTX324M13

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
SHIPDOCKS	SHIPDOCKS	38754, PSDTX324M13
SMR-CO2-VT	CO2 STRIPPER VENT	38754, 86443, PSDTX324M13
SMR-FUG	SMR	38754, PSDTX324M13, 106.261/11/01/2003
SP-1271	HDS TURNAROUND VACUUM JET	118/09/12/1989
SRU3FUG	SULFUR TRAIN NO. 3 FUGITIVES	38754, PSDTX324M13
SRU3	SULFUR RECOVERY UNIT #3	38754, PSDTX324M13
SRU	SULFUR RECOVERY UNIT	38754, PSDTX324M13
SWS-FUG	SWS	38754, PSDTX324M13, 106.261/11/01/2003
TERMIN 2/2A	TERMINAL 2/2A FUGITIVES	38754, PSDTX324M13, 106.261/11/01/2003
TERMINAL 1	TERMINAL 1 FUGITIVES	38754, PSDTX324M13, 106.261/11/01/2003
TERMINAL 3	TERMINAL 3 FUGITIVES	38754, PSDTX324M13
TK-114	TANK NO. 114	38754, PSDTX324M13
TK-51	TANK NO. 51	38754, PSDTX324M13
TK76	TANK NO. 76	38754, PSDTX324M13
T-RACK	TRUCK RACK	38754, PSDTX324M13
TRUCKCOMB	TRUCK LOADING COMBUSTOR	38754, PSDTX324M13
VACUUMUNIT	VACUUM UNIT	38754, PSDTX324M13
VRU	VAPOR RECOVERY UNIT	38754, PSDTX324M13

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
WWTP-FUG	WWTP FUGITIVES	69/09/23/1982

Schedules

Compliance Schedule 379

Compliance Schedule

A. Compliance Schedule				
1. Specific Non-Compliance Situation				
Unit/Group/ Process ID. No(s).	**SOP Index No.**	**Pollutant**	**Applicable Requirement**	
			Citation	**Text Description**
30-B-02		NOX	116.116(b)(1)(B) & (C)	Do not vary from any representation without obtaining a permit amendment for a change in the character of the emissions or an increase in the emissions rate.

2. Compliance Status Assessment Method and Records Location		
Compliance Status Assessment Method		**Location of Records/Documentation**
Citation	**Text Description**	
116.116(b)(1)(B) & (C)	Do not vary from any representation without obtaining a permit amendment for a change in the character of the emissions or an increase in the emissions rate.	Environmental Offices

3. Non-compliance Situation Description
The NOx emission limits (lbs/hour and tons/yr) for boiler, 30-B-02, were incorrectly incorporated into the NSR 30 TAC 116 Subchapter B Permit in December 2010.
4. Corrective Action Plan Description
Obtain proper authorization of the NOx emissions (lbs/hour and tons/yr) through an amendment application to the NSR permit.

5. List of Activities/Milestones to Implement the Corrective Action Plan	
1	Submit an application to the TCEQ for authorization of the NOx emissions (lbs/hour and tons/yr) for the boiler, 30-B-02, though a permit amendment, or permit renewal to the NSR permit in the first quarter of 2012.
2	Submit a revision to the FOP if necessary once NSR authorization is approved for changes to applicable requirements identified in the FOP. Submit such a revision within the timeline specified in 30 TAC Chapter 122.
3	Until compliance is achieved with NSR authorization, continue to submit deviation reports pursuant to 30 TAC Chapter 122.

6. Previously Submitted Compliance Plan(s)	**Type of Action**	**Date Submitted**
	N/A	
7. Progress Report Submission Schedule	Semi-annually beginning at permit renewal issuance.	

Compliance Schedule

A. Compliance Schedule				
1. Specific Non-Compliance Situation				
Unit/Group/ Process ID. No(s).	**SOP Index No.**	**Pollutant**	**Applicable Requirement**	
			Citation	**Text Description**
30-B-02		NOX	116.116(b)(1)(B) & (C)	Do not vary from any representation without obtaining a permit amendment for a change in the character of the emissions or an increase in the emissions rate.

2. Compliance Status Assessment Method and Records Location		
Compliance Status Assessment Method		**Location of Records/Documentation**
Citation	**Text Description**	
116.116(b)(1)(B) & (C)	Do not vary from any representation without obtaining a permit amendment for a change in the character of the emissions or an increase in the emissions rate.	Environmental Offices

3. Non-compliance Situation Description
The NOx emissions limit (lbs NOx/MMBtu) for boiler, 30-B-02, was incorrectly incorporated into the NSR Air Permit limit in June 2010 as 0.08 where it should be 0.10 lbs NOx/MMBtu.
4. Corrective Action Plan Description
Obtain proper authorization of the NOx emissions (lbs NOx/MMBtu) through an amendment to the NSR permit.

5. List of Activities/Milestones to Implement the Corrective Action Plan	
1	Submit an application to the TCEQ for authorization of the NOx emissions (lbs NOx/MMBtu) for the boiler, 30-B-02, though a permit amendment, or permit renewal to the NSR permit in the first quarter of 2012.
2	Submit a revision to the FOP if necessary once NSR authorization is approved for changes to applicable requirements identified in the FOP. Submit such a revision within the timeline specified in 30 TAC Chapter 122.
3	Until compliance is achieved with NSR authorization, continue to submit deviation reports pursuant to 30 TAC Chapter 122.

6. Previously Submitted Compliance Plan(s)	**Type of Action**	**Date Submitted**
	N/A	
7. Progress Report Submission Schedule	Semi-annually beginning at permit renewal issuance.	

Compliance Schedule

A. Compliance Schedule				
1. Specific Non-Compliance Situation				
Unit/Group/ Process ID. No(s).	**SOP Index No.**	**Pollutant**	**Applicable Requirement**	
			Citation	**Text Description**
47-H-01, 47-H-02, 47-H-03, 47-H-04		NOX	116.116(b)(1)(B) & (C)	Do not vary from any representation without obtaining a permit amendment for a change in the character of the emissions or an increase in the emissions rate.

2. Compliance Status Assessment Method and Records Location		
Compliance Status Assessment Method		**Location of Records/Documentation**
Citation	**Text Description**	
116.116(b)(1)(B) & (C)	Do not vary from any representation without obtaining a permit amendment for a change in the character of the emissions or an increase in the emissions rate.	Environmental Offices

3. Non-compliance Situation Description
The NOx emissions limits (lbs/hour and tons/yr) for heaters, 47-H-01, 47-H-02, 47-H-03, 47-H-04, were incorrectly incorporated into the NSR 30 TAC 116 Subchapter B Permit in December 2010.
4. Corrective Action Plan Description
Obtain proper authorization of the NOx emissions (lbs/hour and tons/yr) through an amendment application to the NSR permit.

5. List of Activities/Milestones to Implement the Corrective Action Plan	
1	Submit an application to the TCEQ for authorization of the NOx emissions (lbs/hour and tons/yr) for the heaters, 47-H-01, 47-H-02, 47-H-03, 47-H-04, though a permit amendment, or permit renewal to the NSR permit in the first quarter of 2012.
2	Submit a revision to the FOP if necessary once NSR authorization is approved for changes to applicable requirements identified in the FOP. Submit such a revision within the timeline specified in 30 TAC Chapter 122.
3	Until compliance is achieved with NSR authorization, continue to submit deviation reports pursuant to 30 TAC Chapter 122.

6. Previously Submitted Compliance Plan(s)	**Type of Action**	**Date Submitted**
	N/A	
7. Progress Report Submission Schedule	Semi-annually beginning at permit renewal issuance.	

Compliance Schedule

A. Compliance Schedule				
1. Specific Non-Compliance Situation				
Unit/Group/ Process ID. No(s).	**SOP Index No.**	**Pollutant**	**Applicable Requirement**	
			Citation	**Text Description**
47-H-01, 47-H-02, 47-H-03, 47-H-04		NOX	116.116(b)(1)(B) & (C)	Do not vary from any representation without obtaining a permit amendment for a change in the character of the emissions or an increase in the emissions rate.

2. Compliance Status Assessment Method and Records Location		
Compliance Status Assessment Method		**Location of Records/Documentation**
Citation	**Text Description**	
116.116(b)(1)(B) & (C)	Do not vary from any representation without obtaining a permit amendment for a change in the character of the emissions or an increase in the emissions rate.	Environmental Offices

3. Non-compliance Situation Description
The NOx emissions limits (lbs NOx/MMBtu) for heaters, 47-H-01, 47-H-02, 47-H-03, 47-H-04, were incorrectly incorporated into the NSR Air Permit limit in June 2010 as 0.06 where it should be 0.10 lbs NOx/MMBtu.
4. Corrective Action Plan Description
Obtain proper authorization of the NOx emissions (lbs NOx/MMBtu) through an amendment application to the NSR permit.

5. List of Activities/Milestones to Implement the Corrective Action Plan	
1	Submit an application to the TCEQ for authorization of the NOx emissions (lbs NOx/MMBtu) for the heaters, 47-H-01, 47-H-02, 47-H-03, 47-H-04, though a permit amendment, or permit renewal to the NSR permit in the first quarter of 2012.
2	Submit a revision to the FOP if necessary once NSR authorization is approved for changes to applicable requirements identified in the FOP. Submit such a revision within the timeline specified in 30 TAC Chapter 122.
3	Until compliance is achieved with NSR authorization, continue to submit deviation reports pursuant to 30 TAC Chapter 122.

6. Previously Submitted Compliance Plan(s)	**Type of Action**	**Date Submitted**
	N/A	
7. Progress Report Submission Schedule	Semi-annually beginning at permit renewal issuance.	

Compliance Schedule

A. Compliance Schedule				
1. Specific Non-Compliance Situation				
Unit/Group/ Process ID. No(s).	**SOP Index No.**	**Pollutant**	**Applicable Requirement**	
			Citation	**Text Description**
		VOC	60.692-2(a)(1), (b)(1), (b)(2)	Drains shall be equipped with water seal controls. Junction boxes shall be equipped with cover & may have an open vent pipe at least 90 cm in length & not exceed 10.2 cm in diameter. Junction box covers shall have a tight seal around edge all times.

2. Compliance Status Assessment Method and Records Location		
Compliance Status Assessment Method		**Location of Records/Documentation**
Citation	**Text Description**	
60.692-2(a)(1), (b)(1), (b)(2)	Drains shall be equipped with water seal controls. Junction boxes shall be equipped with cover & may have an open vent pipe at least 90 cm in length & not exceed 10.2 cm in diameter. Junction box covers shall have a tight seal around edge all times.	Environmental Offices

3. Non-compliance Situation Description
A new oily water junction box (neutralization sump) at the Alkylation Unit that connects to the oily water sewer system was not covered and the pump drains connected to the junction box did not have water seals as required.
4. Corrective Action Plan Description
Cover the junction box and install water seals on the 26 pump drains at the Alkylation Unit as required per 40 CFR 60 Subpart QQQ.

5. List of Activities/Milestones to Implement the Corrective Action Plan	
1	Cover the junction box and install water seals on the 26 pump drains at the Alkylation Unit as required by the fourth quarter of 2013.
2	Continue to submit deviation reports pursuant to 30 TAC Chapter 122 until junction box and pump drain water seals are in compliance.

6. Previously Submitted Compliance Plan(s)	**Type of Action**	**Date Submitted**
	N/A	
7. Progress Report Submission Schedule	Semi-annually beginning at permit renewal issuance.	

Compliance Schedule

A. Compliance Schedule				
1. Specific Non-Compliance Situation				
Unit/Group/ Process ID. No(s).	**SOP Index No.**	**Pollutant**	**Applicable Requirement**	
			Citation	**Text Description**
APISEP		NOX	116.116(b)(1)(B) & (C)	Do not vary from any representation without obtaining a permit amendment for a change in the character of the emissions or an increase in the emissions rate.

2. Compliance Status Assessment Method and Records Location		
Compliance Status Assessment Method		**Location of Records/Documentation**
Citation	**Text Description**	
116.116(b)(1)(B) & (C)	Do not vary from any representation without obtaining a permit amendment for a change in the character of the emissions or an increase in the emissions rate.	Environmental Offices

3. Non-compliance Situation Description
The NOx emissions limits (lbs/hour and tons/yr) for the API Vapor Combustor, APISEP, were incorrectly incorporated into the NSR 30 TAC 116 Subchapter B Permit.
4. Corrective Action Plan Description
Obtain proper authorization of the NOx emissions (lbs/hour and tons/yr) through an amendment application to the NSR permit.

5. List of Activities/Milestones to Implement the Corrective Action Plan	
1	Submit an application to the TCEQ for authorization of the NOx emissions (lbs/hour and tons/yr) for the API Vapor Combustor, APISEP, through a permit amendment, or permit renewal to the NSR permit in the first quarter of 2012.
2	Submit a revision to the FOP if necessary once NSR authorization is approved for changes to applicable requirements identified in the FOP. Submit such a revision within the timeline specified in 30 TAC Chapter 122.
3	Until compliance is achieved with NSR authorization, continue to submit deviation reports pursuant to 30 TAC Chapter 122.

6. Previously Submitted Compliance Plan(s)	Type of Action	Date Submitted
	N/A	
7. Progress Report Submission Schedule	Semi-annually beginning at permit renewal issuance.	

Compliance Schedule

A. Compliance Schedule				
1. Specific Non-Compliance Situation				
Unit/Group/ Process ID. No(s).	**SOP Index No.**	**Pollutant**	**Applicable Requirement**	
			Citation	**Text Description**
		VOC	116.116(b)(1)(B) & (C)	Do not vary from any representation without obtaining a permit amendment for a change in the character of the emissions or an increase in the emissions rate.

2. Compliance Status Assessment Method and Records Location		
Compliance Status Assessment Method		**Location of Records/Documentation**
Citation	**Text Description**	
116.116(b)(1)(B) & (C)	Do not vary from any representation without obtaining a permit amendment for a change in the character of the emissions or an increase in the emissions rate.	Environmental Offices

3. Non-compliance Situation Description
VOC emissions (lbs/hour and tons/yr) from carbon adsorption canisters installed on the Oily Water Separator (OWS) junction boxes, and one liquid scrubber installed on the Crude Unit OWS, were not previously identified in the NSR 30 TAC 116 Subchapter B Permit #38754 and thus need to be incorporated into the NSR permit.

4. Corrective Action Plan Description
Obtain proper authorization of the emissions (lbs/hour and tons/yr) from carbon adsorption canisters installed on the Oily Water Separator (OWS) junction boxes, and one liquid scrubber installed on the Crude Unit OWS through an amendment application to the NSR permit.

5. List of Activities/Milestones to Implement the Corrective Action Plan	
1	Submit an application to the TCEQ for authorization of emissions (lbs/hour and tons/yr) from carbon adsorption canisters installed on the Oily Water Separator (OWS) junction boxes, and one liquid scrubber installed on the Crude Unit OWS through a permit amendment, or permit renewal to the NSR permit in the first quarter of 2012.
2	Submit a revision to the FOP if necessary once NSR authorization is approved for changes to applicable requirements identified in the FOP. Submit such a revision within the timeline specified in 30 TAC Chapter 122.
3	Until compliance is achieved with NSR authorization, continue to submit deviation reports pursuant to 30 TAC Chapter 122.

6. Previously Submitted Compliance Plan(s)	Type of Action	Date Submitted
	N/A	

7. Progress Report Submission Schedule	Semi-annually beginning at permit renewal issuance.

Compliance Schedule

A. Compliance Schedule				
1. Specific Non-Compliance Situation				
Unit/Group/ Process ID. No(s).	**SOP Index No.**	**Pollutant**	**Applicable Requirement**	
			Citation	**Text Description**
11F-HDS, 11F-HOC, 30B01F, 30B02F, 30B03F, 41F, 46F/24F, 4F, 54F, ALKY-FUG, AMINE-FUG, ATU3FUG, BUTAMER, CRUDE UNIT, CRU-FUG, HCU-FUG, HDS FUG, HOC-FUG, HRLEU-FUG, LPG STORAG, LRU, MTBE-FUG, MVRUF, NHT-FUG, OLEFLEX-FU, PIPING FUG, DEGREASE-F, DOCKS-F, GAS BLEND, GDFUG, SCOTFUG, SMR-FUG, SRU3FUG, SWS-FUG, TERMIN 2/2A, TERMINAL 1, TERMINAL 3, VACUUMUNIT, WWTP-FUG		H2S, VOC	116.116(b)(1)(B) & (C)	Do not vary from any representation without obtaining a permit amendment for a change in the character of the emissions or an increase in the emissions rate.

2. Compliance Status Assessment Method and Records Location		
Compliance Status Assessment Method		**Location of Records/Documentation**
Citation	**Text Description**	
116.116(b)(1)(B) & (C)	Do not vary from any representation without obtaining a permit amendment for a change in the character of the emissions or an increase in the emissions rate.	Environmental Offices

3. Non-compliance Situation Description

The updated component counts for all aforementioned Unit ID Numbers listed caused increases in the VOC emissions limits (lbs/hour and tons/yr) greater than the Prevention of Significant Deterioration (PSD) thresholds and thus need to be incorporated into the NSR 30 TAC 116 Subchapter B Permit #38754. Also the fugitive sources with Unit ID. Numbers listed (EPNs in the NSR Permit) do not include H2S as an emission (lbs/hour and tons/yr) in the NSR 30 TAC 116 Subchapter B Permit #38754 and thus need to be incorporated into the NSR permit.
4. Corrective Action Plan Description
Obtain proper authorization of the H2S & VOC fugitive emissions (lbs/hour and tons/yr) through an amendment application to the NSR permit. Also obtain proper authorization of the VOC emissions (lbs/hour and tons/yr) due to the component count increases through an amendment application to the NSR permit. Finally, three new fugitive EPNs are also being added: 42F (Sour Water Stripper), 54F (Selective Hydrogenation Unit - this replaces both 54F-MTBE & 54F-TAME), and 201 (Railcar Unloading) not previously identified in the NSR permit need to be incorporated into the NSR permit.

5. List of Activities/Milestones to Implement the Corrective Action Plan	
1	Submit an application to the TCEQ for authorization of the VOC emissions (lbs/hour and tons/yr) due to the component count increases at the West Plant through a permit amendment, or permit renewal to the NSR permit in the first quarter of 2012.
2	Submit a revision to the FOP if necessary once NSR authorization is approved for changes to applicable requirements identified in the FOP. Submit such a revision within the timeline specified in 30 TAC Chapter 122.
3	Until compliance is achieved with NSR authorization, continue to submit deviation reports pursuant to 30 TAC Chapter 122

6. Previously Submitted Compliance Plan(s)	**Type of Action**	**Date Submitted**
	N/A	

7. Progress Report Submission Schedule	Semi-annually beginning at permit renewal issuance.

Compliance Schedule

A. Compliance Schedule				
1. Specific Non-Compliance Situation				
Unit/Group/ Process ID. No(s).	**SOP Index No.**	**Pollutant**	**Applicable Requirement**	
			Citation	**Text Description**
ALKY-CT, BUP-CT, CRUDE-CT, HOC-CT, GRP-CT		PM	116.116(b)(1)(B) & (C)	Do not vary from any representation without obtaining a permit amendment for a change in the character of the emissions or an increase in the emissions rate.

2. Compliance Status Assessment Method and Records Location		
Compliance Status Assessment Method		**Location of Records/Documentation**
Citation	**Text Description**	
116.116(b)(1)(B) & (C)	Do not vary from any representation without obtaining a permit amendment for a change in the character of the emissions or an increase in the emissions rate.	Environmental Offices

3. Non-compliance Situation Description
All cooling tower existing particulate matter (PM) emissions (lbs/hour and tons/yr) were not previously identified in the NSR 30 TAC 116 Subchapter B Permit #38754 and thus need to have NSR authorization.
4. Corrective Action Plan Description
Obtain proper NSR authorization of the cooling tower existing PM emissions (lbs/hour and tons/yr.

5. List of Activities/Milestones to Implement the Corrective Action Plan	
1	Submit an application to the TCEQ for NSR authorization of the cooling tower existing PM emissions (lbs/hour and tons/yr) in the first quarter of 2012.
2	Submit a revision to the FOP if necessary once NSR authorization is approved for changes to applicable requirements identified in the FOP. Submit such a revision within the timeline specified in 30 TAC Chapter 122.
3	Until compliance is achieved with NSR authorization, continue to submit deviation reports pursuant to 30 TAC Chapter 122.

6. Previously Submitted Compliance Plan(s)	**Type of Action**	**Date Submitted**
	N/A	
7. Progress Report Submission Schedule	Semi-annually beginning at permit renewal issuance.	

Compliance Schedule

A. Compliance Schedule				
1. Specific Non-Compliance Situation				
Unit/Group/ Process ID. No(s).	**SOP Index No.**	**Pollutant**	**Applicable Requirement**	
			Citation	**Text Description**
83P136A-EN, 83P136B-EN		VOC, NOX, CO	60.4205(b) & 60.4202(a)(2)	Owners & operators of 2007 model year & later emergency stationary CI ICE with a displacement of less than 30 liters per cylinder that are not fire pump engines must comply with the emission standards for new nonroad CI engine in §60.4202, for all pollutants, for the same model year & maximum engine power for their 2007 model year & later emergency stationary CI ICE. Stationary CI ICE manufacturers must certify their 2007 model year & later emergency stationary CI ICE with a maximum engine power less than or equal to 2,237 KW (3,000 HP) & a displacement of less than 10 liters per cylinder that are not fire pump engines to the emission standards specified in paragraphs (a)(1) through (2) of this section. (2) For engines with a maximum engine power greater than or equal to 37 KW (50 HP), the certification emission standards for new nonroad CI engines for the same model year & maximum engine power in 40 CFR 89.112 and 40 CFR 89.113 for all pollutants beginning in model year 2007.

2. Compliance Status Assessment Method and Records Location		
Compliance Status Assessment Method		**Location of Records/Documentation**
Citation	**Text Description**	

60.4205(b) & 60.4202(a)(2)	Owners & operators of 2007 model year & later emergency stationary CI ICE with a displacement of less than 30 liters per cylinder that are not fire pump engines must comply with the emission standards for new nonroad CI engine in §60.4202, for all pollutants, for the same model year & maximum engine power for their 2007 model year & later emergency stationary CI ICE. Stationary CI ICE manufacturers must certify their 2007 model year & later emergency stationary CI ICE with a maximum engine power less than or equal to 2,237 KW (3,000 HP) & a displacement of less than 10 liters per cylinder that are not fire pump engines to the emission standards specified in paragraphs (a)(1) through (2) of this section. (2) For engines with a maximum engine power greater than or equal to 37 KW (50 HP), the certification emission standards for new nonroad CI engines for the same model year & maximum engine power in 40 CFR 89.112 and 40 CFR 89.113 for all pollutants beginning in model year 2007.	Environmental Offices

3. Non-compliance Situation Description

Two diesel engines used as drivers for two emergency storm water pumps were manufactured as fire water pumps and do not meet the requirements of NSPS IIII.

4. Corrective Action Plan Description

Resolve 40 CFR 60 Subpart IIII compliance issues with two diesel engine drivers for two emergency storm water pumps.

5. List of Activities/Milestones to Implement the Corrective Action Plan

1	Resolve 40 CFR 60 Subpart IIII compliance issues with two diesel engine drivers for two emergency storm water pumps by the fourth quarter of 2015.
2	Continue to submit deviation reports pursuant to 30 TAC Chapter 122 until compliance issues are resolved.

6. Previously Submitted Compliance Plan(s)	**Type of Action**	**Date Submitted**
	N/A	

7. Progress Report Submission Schedule	Semi-annually beginning at permit renewal issuance.

Compliance Schedule

A. Compliance Schedule				
1. Specific Non-Compliance Situation				
Unit/Group/ Process ID. No(s).	**SOP Index No.**	**Pollutant**	**Applicable Requirement**	
			Citation	**Text Description**
GF-1, MFL-1, MTBE FL-2		VOC, PM, SO2, CO, NOX	116.116(b)(1)(B) & (C)	Do not vary from any representation without obtaining a permit amendment for a change in the character of the emissions or an increase in the emissions rate.

2. Compliance Status Assessment Method and Records Location		
Compliance Status Assessment Method		**Location of Records/Documentation**
Citation	**Text Description**	
116.116(b)(1)(B) & (C)	Do not vary from any representation without obtaining a permit amendment for a change in the character of the emissions or an increase in the emissions rate.	Environmental Offices

3. Non-compliance Situation Description
The additional process flare emissions (lbs/hour and tons/yr) were not previously identified in the NSR 30 TAC 116 Subchapter B Permit #38754 and thus need to be incorporated into the NSR permit.
4. Corrective Action Plan Description
Obtain proper authorization of the additional process flare emissions (lbs/hour and tons/yr) through an amendment application to the NSR permit.

5. List of Activities/Milestones to Implement the Corrective Action Plan	
1	Submit an application to the TCEQ for authorization of the additional flare emissions (lbs/hour and tons/yr) through a permit amendment, or permit renewal to the NSR permit in the first quarter of 2014.
2	Submit a revision to the FOP if necessary once NSR authorization is approved for changes to applicable requirements identified in the FOP. Submit such a revision within the timeline specified in 30 TAC Chapter 122.
3	Until compliance is achieved with NSR authorization, continue to submit deviation reports pursuant to 30 TAC Chapter 122.

6. Previously Submitted Compliance Plan(s)	**Type of Action**	**Date Submitted**
	N/A	
7. Progress Report Submission Schedule	Semi-annually beginning at permit renewal issuance.	

Compliance Schedule

A. Compliance Schedule				
1. Specific Non-Compliance Situation				
Unit/Group/ Process ID. No(s).	**SOP Index No.**	**Pollutant**	**Applicable Requirement**	
			Citation	**Text Description**
01-H-01, 01-H-02, 01-H-03, 02-H-01, 02-H-02, 11-H-01, 12-H01A, 12-H01B, 12-H02, 13-H-01A, 13-H-01B, 13-H-01C, 31-H-01, 38-H-01, 38-H-02, 38-H-03, 47-H-01, 47-H-02, 47-H-03, 47-H-04, 48-H-01, 49-H-01, 49-H-02, 49-H-03, 49-H-04, 49-H-71, 49-H-90, 49-H-91, 52-H-01, 30-B-02, 30-B-03, 30-B-04		NH3	116.116(b)(1)(B) & (C)	Do not vary from any representation without obtaining a permit amendment for a change in the character of the emissions or an increase in the emissions rate

2. Compliance Status Assessment Method and Records Location		
Compliance Status Assessment Method		**Location of Records/Documentation**
Citation	**Text Description**	
116.116(b)(1)(B) & (C)	Do not vary from any representation without obtaining a permit amendment for a change in the character of the emissions or an increase in the emissions rate	Environmental Offices

3. Non-compliance Situation Description
All heater and boiler existing ammonia (NH3) emissions (lbs/hour and tons/yr) were not previously identified in the NSR 30 TAC 116 Subchapter B Permit #38754 and thus need to be incorporated into the NSR permit.

4. Corrective Action Plan Description
Obtain proper authorization of the heater and boiler existing ammonia (NH3) emissions (lbs/hour and tons/yr) through an amendment application to the NSR permit.

5. List of Activities/Milestones to Implement the Corrective Action Plan	
1	Submit an application to the TCEQ for authorization of the heater and boiler existing ammonia (NH3) emissions (lbs/hour and tons/yr) through a permit amendment, or permit renewal to the NSR permit in the first quarter of 2012.

2	Submit a revision to the FOP if necessary once NSR authorization is approved for changes to applicable requirements identified in the FOP. Submit such a revision within the timeline specified in 30 TAC Chapter 122.		
3	Until compliance is achieved with NSR authorization, continue to submit deviation reports pursuant to 30 TAC Chapter 122.		
6. Previously Submitted Compliance Plan(s)		**Type of Action**	**Date Submitted**
		N/A	
7. Progress Report Submission Schedule		Semi-annually beginning at permit renewal issuance	

Compliance Schedule

A. Compliance Schedule				
1. Specific Non-Compliance Situation				
Unit/Group/ Process ID. No(s).	**SOP Index No.**	**Pollutant**	**Applicable Requirement**	
			Citation	**Text Description**
2202-L & 2203-L, SRU3, SRU		HAPS VOC PM SO2 CO NOX	116.116(b)(1) (B) & (C)	Do not vary from any representation without obtaining a permit amendment for a change in the character of the emissions or an increase in the emissions rate.

2. Compliance Status Assessment Method and Records Location		
Compliance Status Assessment Method		**Location of Records/Documentation**
Citation	**Text Description**	
116.116(b)(1)(B) & (C)	Do not vary from any representation without obtaining a permit amendment for a change in the character of the emissions or an increase in the emissions rate.	Environmental Offices

3. Non-compliance Situation Description
Additional emissions from the SCOT (SRU3) incinerator (lbs/hour and tons/yr) and backup Sulften incinerator (SRU) due to routing a vent stream from the HOC LPG Oxidizer (2202-L & 2203-L) were not previously identified in the NSR 30 TAC 116 Subchapter B Permit #38754 and thus need to be incorporated into the NSR permit.

4. Corrective Action Plan Description
Obtain proper authorization of additional emissions from the SCOT (SRU3) incinerator (lbs/hour and tons/yr) and backup Sulften incinerator (SRU) through an amendment application to the NSR permit.

5. List of Activities/Milestones to Implement the Corrective Action Plan	
1	Submit an application to the TCEQ for authorization of additional emissions from the SCOT (SRU3) incinerator (lbs/hour and tons/yr) and backup Sulften incinerator (SRU) through an amendment application, or permit renewal to the NSR permit in the first quarter of 2012.
2	Submit a revision to the FOP if necessary once NSR authorization is approved for changes to applicable requirements identified in the FOP. Submit such a revision within the timeline specified in 30 TAC Chapter 122.
3	Until compliance is achieved with NSR authorization, continue to submit deviation reports pursuant to 30 TAC Chapter 122.

6. Previously Submitted Compliance Plan(s)	Type of Action	Date Submitted
	N/A	

7. Progress Report Submission Schedule	Semi-annually beginning at permit renewal issuance.

Compliance Schedule

A. Compliance Schedule				
1. Specific Non-Compliance Situation				
Unit/Group/ Process ID. No(s).	**SOP Index No.**	**Pollutant**	**Applicable Requirement**	
			Citation	**Text Description**
		VOC	60.692-2(b)(1) & (2)	Junction boxes shall be equipped with a cover & may have an open vent pipe at least 90 cm in length & not exceed 10.2 cm in diameter. Junction box covers shall have a tight seal around the edge be kept in place at all times.

2. Compliance Status Assessment Method and Records Location		
Compliance Status Assessment Method		**Location of Records/Documentation**
Citation	**Text Description**	
60.692-2(b)(1) & (2)	Junction boxes shall be equipped with a cover & may have an open vent pipe at least 90 cm in length & not exceed 10.2 cm in diameter. Junction box covers shall have a tight seal around the edge be kept in place at all times.	Environmental Offices

3. Non-compliance Situation Description
An oily water junction box (overflow sump) near the West Plant Truck Rack that is connected to the oily water sewer system was not covered as required.
4. Corrective Action Plan Description
Eliminate uncontrolled junction box (overflow sump) near the West Plant Truck Rack as required per 40 CFR 60 Subpart QQQ.

5. List of Activities/Milestones to Implement the Corrective Action Plan	
1	Eliminate uncontrolled junction box (overflow sump) near the West Plant Truck Rack as required by the fourth quarter of 2013.
2	Continue to submit deviation reports pursuant to 30 TAC Chapter 122 until compliance is achieved with the elimination of the uncontrolled junction box.

6. Previously Submitted Compliance Plan(s)	**Type of Action**	**Date Submitted**
	N/A	
7. Progress Report Submission Schedule	Semi-annually beginning at permit renewal issuance.	

Compliance Schedule

A. Compliance Schedule				
1. Specific Non-Compliance Situation				
Unit/Group/ Process ID. No(s).	**SOP Index No.**	**Pollutant**	**Applicable Requirement**	
			Citation	**Text Description**
T-RACK			116.116(b)(1)(B) & (C)	Do not vary from any representation without obtaining a permit amendment for a change in the character of the emissions or an increase in the emissions rate.

2. Compliance Status Assessment Method and Records Location		
Compliance Status Assessment Method		**Location of Records/Documentation**
Citation	**Text Description**	
116.116(b)(1)(B) & (C)	Do not vary from any representation without obtaining a permit amendment for a change in the character of the emissions or an increase in the emissions rate.	Environmental Offices

3. Non-compliance Situation Description
A throughput increase at the truck loading rack (T-RACK) was not previously identified in the NSR 30 TAC 116 Subchapter B Permit #38754 and thus needs to be incorporated into the NSR permit special conditions.

4. Corrective Action Plan Description
Obtain proper authorization for a throughput increase at the truck loading rack (T-RACK) through an amendment application to the NSR permit.

5. List of Activities/Milestones to Implement the Corrective Action Plan	
1	Submit an application to the TCEQ for authorization for a throughput increase at the truck loading rack (T-RACK) through a permit amendment, or permit renewal to the NSR permit in the first quarter of 2012.
2	Until compliance is achieved with NSR authorization, continue to submit deviation reports pursuant to 30 TAC Chapter 122.

6. Previously Submitted Compliance Plan(s)	Type of Action	Date Submitted
	N/A	
7. Progress Report Submission Schedule	Semi-annually beginning at permit renewal issuance.	

Alternative Requirement

Alternative Requirement 398

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
REGION 6
1445 ROSS AVENUE, SUITE 1200
DALLAS, TX 75202-2733

RECEIVED
AUG 25 1999

AUG 19 1999

Mr. Kirk A. Saffell
Manager, Environmental Engineering
Valero Refining Company - Texas
P.O. Box 9370
Corpus Christi, TX 78469-9370

Re: Approval of Alternative Monitoring for NSPS Subpart J
Valero Refining Company - Texas
Corpus Christi Refinery
TNRCC Account No. NE-0112-G

Dear Mr. Saffell:

By letter dated February 5, 1999, Valero Refining Company - Texas (Valero) requested approval of alternative monitoring to a continuous opacity monitoring system (COMS), which is required by a New Source Performance Standard (NSPS) under Title 40, Code of Federal Regulations (CFR) Part 60, at its petroleum refinery in Corpus Christi, Texas. Valero's petroleum refinery contains a fluid catalytic cracking unit (FCCU) which is subject to NSPS Subpart J - *Standards of Performance for Petroleum Refineries*. A COMS on the FCCU (EPN 121) is required by § 60.105(a)(1) of NSPS Subpart J. The FCCU is equipped with a high efficiency Belco Technologies Corporation (Belco) flue gas scrubber. Moisture in the exhaust of the Belco scrubber would interfere with the operation of a COMS. Therefore, Valero requested that the following alternate monitoring program be approved as recommended to Valero by Belco.

1. Monitor the pressure of the water to the filtering modules and maintain a pressure of a least 45 psig at all times.

2. Monitor the flue gas pressure drop across the filtering modules/cyclolabs and maintain a drop of at least 5" H_2O.

In a letter dated November 12, 1993, by which Valero submitted additional information and comments on draft provisions to Permit No. 8373 and PSD-TX-324M-6 to the Texas Natural Resource Conservation Commission (TNRCC), Valero proposed alternative monitoring to the COMS required by NSPS Subpart J. The TNRCC included the following approval of the alternative monitoring as Special Provision 15 when it revised Permit No. 8373 and PSD-TX-324M-6 on December 13, 1993.

Recycled/Recyclable • Printed with Vegetable Oil Based Inks on 100% Recycled Paper (40% Postconsumer)

In order to control opacity from the stack of EPN 121, the permittee shall maintain the liquid to the filtering modules at a pressure greater than 45 pounds per square inch and the flue gas pressure drop across the filtering modules and the cyclolabs at no less than five inches of water. Liquid pressure and pressure drop shall be continuously recorded and maintained at the plant site for a period of two years. These records shall be made available for inspection by the Executive Director of the TNRCC or his designated representative.

Special Provision 15 of Permit No. 8373 and PSD-TX-324M-6 became Special Condition 31 of Permit No. 8373 and PSD-TX-324M7, which was issued on May 29, 1997, and remained Special Condition 31 of Permit No. 8373 and PSD-TX-324M8, which was issued on January 27, 1998. Valero has not received approval of this alternative monitoring program from EPA. The authority to approve alternative monitoring under 40 CFR 60.13(i) has been delegated to the EPA Region 6, but has not been delegated to the TNRCC.

Pursuant to 40 CFR 60.13(i), we are approving the following alternative monitoring to the COMS which is required under § 60.105(a)(1) of NSPS Subpart J for the HOC FCCU (EPN 121) at Valero's petroleum refinery in Corpus Christi, Texas.

1. Valero shall continuously monitor and record the pressure of the water to the filtering modules of the Belco scrubber and the flue gas pressure drop across the filtering modules/cyclolabs of the Belco scrubber.

2. Valero shall maintain records of the water pressure and flue gas pressure drop at the plant site for at least two years.

3. Valero shall monitor and record the pressure of the water to the filtering modules of the Belco scrubber and the flue gas pressure drop across the filtering modules/cyclolabs of the Belco scrubber during all performance tests for particulate matter of the Belco scrubber. The arithmetic averages of the three runs shall be used as the baseline average values for the purposes of defining excess emissions. The arithmetic averages of the water pressure and flue gas pressure drop which were determined during a performance test for particulate matter which was conducted prior to the date of approval of this alternative monitoring may be used as the baseline average values for the purposes of defining excess emissions.

4. Valero shall submit reports of excess emissions semiannually to the Texas Natural Resource Conservation Commission. All reports shall be postmarked by the 30th day following the end of each calendar half. Excess emissions are defined as follows.

    a. Any 6-minute period when the average pressure of the water to the filtering modules of the Belco scrubber is less than 80 percent of the average value recorded during the most recent performance test that demonstrated compliance with the particulate matter standard in § 60.102(a)(1) of NSPS Subpart J.

b. Any 6-minute period when the flue gas pressure drop across the filtering modules/cyclolabs of the Belco scrubber is less than 80 percent of the average value recorded during the most recent performance test that demonstrated compliance with the particulate matter standard in § 60.102(a)(1) of NSPS Subpart J.

By letter dated July 13, 1999, we notified the TNRCC of our intention to approve this alternative monitoring. The TNRCC did not have any objections to our approving this alternative monitoring, nor any proposed conditions to this alternative monitoring. In our letter to the TNRCC, we proposed that excess emissions be defined as any 6-minute period when the parameter in provision 4.a or 4.b is less than 90 percent of the average value recorded during the most recent performance test for particulate matter. We sent Valero a copy of our letter of July 13, 1999, to the TNRCC. Valero requested that the 90 percent level specified in provisions 4.a and 4.b be changed to 80 percent. Eighty percent will allow Valero sufficient operating flexibility while still ensuring compliance with the standards for opacity and particulate matter in NSPS Subpart J. A limit of 80 percent is more restrictive than the alternative monitoring requirements for NSPS Subpart LL - *Standards of Performance for Metallic Mineral Processing Plants*, NSPS Subpart OOO - *Standards of Performance for Nonmetallic Mineral Processing Plants*, and NSPS Subpart PPP - *Standards of Performance for Wool fiberglass Insulation Manufacturing Plants*. In all of these subparts, excess emissions are defined as periods when the alternative monitoring parameters for a wet gas scrubber are less than 70 percent of the value recorded during the performance test. Valero submitted information from a recent stack test that was conducted on the Belco scrubber on April 13, 1999, by letter dated May 12, 1999, and a fax on May 25, 1999. The average emission rate of particulate matter was 25 percent of the standard of 1.0 lb/1000 lb of coke burnoff in § 60.102(a)(1) of NSPS Subpart J. The testing information is summarized in the following table.

	Run #1	*Run #2*	*Run #3*	*Average*
Particulate Matter (lb/1000 lb coke burnoff)	0.33	0.22	0.19	0.25
Average Filter Differential Pressure (in. of H_2O)	9.87	9.63	9.85	9.78
Average Discharge Pressure (psig)	80.8	81.3	81.4	81.2
Minimum 6-min Average Filter Differential Pressure (in. of H_2O)	9.80	9.47	9.80	
Minimum 6-min Average Discharge Pressure (psig)	80.7	81.1	81.1	

Eighty percent of the arithmetic averages of the three runs of the water pressure and flue gas pressure drop are more stringent requirements than the minimum pressures for these parameters

of 45 pounds per square inch and five inches of water, respectively, established by the TNRCC in the air permit.

If you have any questions concerning this matter, please contact Mr. George V. Marusak, of my staff, at (214) 665-8366.

Sincerely yours,

John R. Hepola

John R. Hepola
Chief
Air/Toxics and Inspection
Coordination Branch

cc: Jeffrey P. Greif, TNRCC
David Bower, TNRCC
Jim Bowman, TNRCC Region 14 - Corpus Christi

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
REGION 6
1445 ROSS AVENUE, SUITE 1200
DALLAS TX 75202-2733

RECEIVED
DEC 2010
HS&E DEPT.
Valero Refining Company
Corpus Christi, TX

DEC 0 3 2010

CERTIFIED MAIL RETURN REQUEST 7007 1490 0004 0582 0430

Sam D. Sanders
Senior Environmental Engineer
VALERO REFINING-TEXAS, L.P.
Corpus Christi Manufacturing Facility
P.O. Box 9370
Corpus Christi, Texas 78469-9370

Re: Alternative Monitoring Plans (AMPs) – Valero Refining – Texas, L.P. (Valero) West Plant, Corpus Christi, Nueces County, Account Number: NE-0112-G, Regulated Entity Number: RN100214386; Monitoring plan for West Plant NHT Feed Surge Drum, 48-V-01, vent stream to the fuel gas line that is combusted at the NHT Charge Heater, 48-H-01, dated November 20, 2007

Dear Mr. Sanders:

This letter is in response to your AMP request, dated November 20, 2007, as referenced above for your Corpus Christi West Plant. Your request involves control of a vent stream from the NHT Feed Surge Drum, 48-V-01 that is combusted at the NHT Charge Heater, 48-H-01. Based on the description of your process vent stream, the particular design of the vent gas controls, and H2S monitoring data, the Environmental Protection Agency is approving your AMP.

According to the diagrams provided in your AMP, there are no crossover points or points where sour gas can be introduced into the fuel gas to the NHT Charge Heater, 48-H-01. The sample point for the vent stream from the NHT Feed Surge Drum (48-V-01) is located in the fuel gas line from the Feed Surge Drum (48-V-01) to the NHT Charge Heater (48-H-01). H2S testing of spent air is conducted using colorimetric tubes. Test results from a 14 day monitoring period indicate an average H2S concentration of 9.536 ppmv.

Valero has proposed to use concentrations of Total Sulfur in the Combined Feed and the temperature of the contents in the Feed Surge Drum (48-V-01) as a means of monitoring the vent stream that is combusted in the NHT Charge Heater, 48-H-01. Total Sulfur and the temperature of the Feed Surge Drum would be sampled and analyzed in conjunction with the Vent from 48-V-01 Feed Surge Drum H2S monitoring schedule. Process parameter limits should not exceed 213 ppm maximum of Total Sulfur in the Combined Feed and a temperature in the Feed Surge Drum (48-V-01) of 165 degrees F.

Internal Address (URL) • http://www.epa.gov/region6
Recycled/Recyclable • Printed with Vegetable Oil Based Inks on 100% Recycled Paper, Process Chlorine Free

Valero would follow the seven step process outlined in Appendix D (Alternative Monitoring Plan for NSPS Subpart J Refinery Fuel Gas) of the Valero consent decree (Civil Action No. SA-05-CA-0569) relative to monitoring the NHT Feed Surge Drum, 48-V-01, vent stream.

If you have any questions or concerns regarding this AMP approval, please do not hesitate to contact either Ms. Cynthia Kaleri of my staff at (214) 665-6772, or Mr. Garry Mokry of my staff at (214) 665-7429.

Sincerely yours,

for David F. Garcia
Associate Director
Air/Toxics & Inspection
Coordination Branch

Cc: Robert Lucas (OAQPS)
Maria Malave (OECA)
David Turner (TCEQ, Corpus Christi)
John Sadler (TCEQ, Austin)
Karen Kornell (Office of the Attorney General of the State of Texas)

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
REGION 6
1445 ROSS AVENUE, SUITE 1200
DALLAS TX 75202-2733

NOV 30 2010

RECEIVED
DEC 2010
HSE&E DEPT.

CERTIFIED MAIL RETURN REQUEST 7007 1490 0004 0582 0263

Sam D. Sanders,
Senior Environmental Engineer
VALERO REFINING-TEXAS, L.P.
Corpus Christi Manufacturing Facility
P.O. Box 9370
Corpus Christi, Texas 78469-9370

Re: Alternative Monitoring Plans (AMPs) – Valero Refining – Texas , L.P. (Valero) West Plant, Corpus Christi, Nueces County, Account Number: NE-0112-G, Regulated Entity Number: RN100214386; Monitoring plan for West Plant, Hydrocracker Feed Surge Drum, 47-V-02, vent stream to the fuel gas line that is Combusted at the Hydrocracker Heaters: 47-H-01, 47-H-02, 47-H-03, and 47-H-04, dated November 20, 2007.

Dear Mr. Sanders:

This letter is in response to your AMP request, dated November 20, 2007, as referenced above for your Corpus Christi West Plant. Your request involves control of a vent stream from the Hydrocracker Feed Surge Drum, 47-V-02 that is combusted at the Hydrocracker Heaters: 47-H-01, 47-H-02, 47-H-03, and 47-H-04. Based on the description of your process vent stream, the particular design of the vent gas controls, and H2S monitoring data, the Environmental Protection Agency is approving your AMP.

According to the diagrams provided in your AMP, there are no crossover points or points where sour gas can be introduced into the fuel gas to the Hydrocracker Heaters 47-H-01, 47-H-02, 47-H-03, and 47-H-04. The sample point for the vent stream from the Hydrocracker Feed Surge Drum (47-V-02) is located at the fuel gas line from the Feed Surge Drum (47-V-02) to the fuel gas line to the Hydrocracker Heaters . H2S testing of the vent stream was conducted using colorimetric tubes, and results from a 14 day monitoring period indicate an average H2S concentration of 7.71 ppmv.

Valero has proposed to use concentrations of Total Sulfur in the Combined Feed and the temperature of the contents in the Feed Surge Drum (47-V-02) as a means of monitoring the vent stream that is combusted in the Hydrocracker Heaters. Total Sulfur and the temperature of the Feed Surge Drum would be sampled and analyzed in conjunction with the Vent from 47-V-02 Feed Surge Drum H2S monitoring schedule. Process parameter limits should not exceed 1.50 wt % maximum of Total Sulfur in the Combined Feed and a temperature in the Feed Surge Drum (47-V-02) not to exceed 190 degrees F.

Internet Address (URL) • http://www.epa.gov/region6
Recycled/Recyclable • Printed with Vegetable Oil Based Inks on 100% Recycled Paper, Process Chlorine Free

Valero would follow the seven step process outlined in Appendix D (Alternative Monitoring Plan for NSPS Subpart J Refinery Fuel Gas) of the Valero consent decree (Civil Action No. SA-05-CA-0569) relative to monitoring the Hydrocracker Feed Surge Drum, 48-V-01, vent stream.

If you have any questions or concerns regarding this AMP approval, please do not hesitate to contact either Ms. Cynthia Kaleri of my staff at (214) 665-6772, or Mr. Garry Mokry of my staff at (214) 665-7429.

Sincerely yours,

David F. Garcia
Associate Director
Air/Toxics & Inspection
Coordination Branch

Cc: Robert Lucas (OAQPS)
Maria Malave (OECA)
David Turner (TCEQ, Corpus Christi)
John Sadler (TCEQ, Austin)
Karen Kornell (Office of the Attorney General of the State of Texas)

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
REGION 6
1445 ROSS AVENUE, SUITE 1200
DALLAS, TX 75202-2733

OCT 0 4 2011

RECEIVED
OCT 2011
HS&E DEPT.
Valero Refining Company
Corpus Christi, TX

Mr. Sam Sanders
Senior Environmental Engineer
Valero Refining – Texas L.P.
Corpus Christi East Plant
Post Office Box 9370
Corpus Christi, Texas 78469-9370

RE: New Source Performance Standards (NSPS) 40 CFR 60 Subpart J
Alternative Monitoring Plan (AMP)
Sulfur Loading and Storage Vent Streams
Routed to Tail Gas Incinerator (TGI)
CD No SA-05-CA-0569

Dear Mr. Sanders:

This letter is in response to your AMP dated November 20, 2007, with additional information from April 30, 2011, and August 24, 2011, concerning sulfur vapor vents from the following:

1. East Plant Sulfur Truck (Unit 141 and SULF-TLDG) and Railcar loading (Unit 141 and SULF-RCLD);
2. East Plant Sulfur Storage Tank (195-TK-038), routed to SRU No. 2 TGI (Unit 195);
3. East Plant Sulfur Drain Header (195-V-037), routed to SRU No. 1 TGI (Unit 195);
4. East Plant Sulfur Drain Header (141-V-021), routed to SRU No. 1 TGI (Unit 141);
5. West Plant Sulfur Truck Loading vent gas stream (Unit 41 and Vent Stream WPSULF-TLD) routed to the Claus Tail Gas Burner (41H07) TGI or alternately to the Claus Tail Gas Burner (41H34) TGI.

In addition to the review of all material submitted by Valero, EPA also evaluated saturated steam tables and partial vapor pressure of sulfur at various temperatures. From the available materials it has been determined that saturated steam at 50 pounds per square inch gauge (psig) pressure, which keeps the sulfur molten for storage and transfer operations at approximately 139°C, does not generate sufficient partial vapor pressure to exceed 250 ppm by volume of sulfur dioxide at 0% oxygen after vapor incineration. Under consideration of this information, EPA approves the alternative monitoring plan as stipulated above such that the temperature of the molten sulfur (139°C) shall not generate sufficient vapors to exceed 250 ppmv of sulfur dioxide at 0% oxygen in the combusted gas.

Recycled/Recyclable • Printed with Vegetable Oil Based Inks on 100% Recycled Paper (40% Postconsumer)

If you have any questions, please contact Mr. Charles Handrich at (214) 665-6553.

Sincerely,

David F. Garcia
Associate Director
Air/Toxics & Inspection
Coordination Branch

cc: Michael De La Cruz (Texas Commission on Environmental Quality)

Appendix A

Acronym List 409

Acronym List

The following abbreviations or acronyms may be used in this permit:

ACFM ..... actual cubic feet per minute
AMOC ..... alternate means of control
ARP ..... Acid Rain Program
ASTM ..... American Society of Testing and Materials
B/PA ..... Beaumont/Port Arthur (nonattainment area)
CAM ..... Compliance Assurance Monitoring
CD ..... control device
COMS ..... continuous opacity monitoring system
CVS ..... closed-vent system
D/FW ..... Dallas/Fort Worth (nonattainment area)
DR ..... Designated Representative
ElP ..... El Paso (nonattainment area)
EP ..... emission point
EPA ..... U.S. Environmental Protection Agency
EU ..... emission unit
FCAA Amendments ..... Federal Clean Air Act Amendments
FOP ..... federal operating permit
GF ..... grandfathered
gr/100 scf ..... grains per 100 standard cubic feet
HAP ..... hazardous air pollutant
H/G/B ..... Houston/Galveston/Brazoria (nonattainment area)
H_2S ..... hydrogen sulfide
ID No. ..... identification number
lb/hr ..... pound(s) per hour
MMBtu/hr ..... Million British thermal units per hour
MRRT ..... monitoring, recordkeeping, reporting, and testing
NA ..... nonattainment
N/A ..... not applicable
NADB ..... National Allowance Data Base
NO_x ..... nitrogen oxides
NSPS ..... New Source Performance Standard (40 CFR Part 60)
NSR ..... New Source Review
ORIS ..... Office of Regulatory Information Systems
Pb ..... lead
PBR ..... Permit By Rule
PM ..... particulate matter
ppmv ..... parts per million by volume
PSD ..... prevention of significant deterioration
RO ..... Responsible Official
SO_2 ..... sulfur dioxide
TCEQ ..... Texas Commission on Environmental Quality
TSP ..... total suspended particulate
TVP ..... true vapor pressure
U.S.C. ..... United States Code
VOC ..... volatile organic compound

Appendix B

Major NSR Summary Table 411

Permit Numbers 38754 and PSDTX324M13 427

Major NSR Summary Table

Permit Number: 38754 and PSDTX324M13 (Version Date: 6/18/2012)							
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirement	Recordkeeping Requirement	Reporting Requirements
			Limit	Units (lb/hr, TPY, etc.)	Spec. Cond.	Spec. Cond.	Spec. Cond.
31F	Alky Unit Fugitives	HF	0.55 0.13	tpy lb/hr	SC35, SC37, SC38, SC45, SC47	SC35, SC38, SC43	SC47
168	Oleflex CCR	Sulfuric Acid	0.01 0.01	tpy lb/hr	SC27	SC43	
		HCl	0.28 0.06	tpy lb/hr			
		Chlorine	0.04 0.01	tpy lb/hr			
121	HOC Scrubber	Sulfuric Acid	214.6 49	tpy lb/hr	SC22, SC26, SC39, SC40, SC42	SC22, SC26, SC40, SC42, SC43	SC39, SC40
155	CRU CCR	HCl	0.29 0.1	tpy lb/hr	SC27, SC28	SC28, SC43	
LEU, FUG-DOCKS, ATU3FUG, RU3FUG, SCOTFUG, GD-FUG, LPGSTGF (listed in attachment 1 for MAERT, but not in MAERT)	Refinery Fugitives VOC Subcaps	H_2S (total plant wide limit)	12.79 2.92	tpy lb/hr	SC38, SC56, SC65	SC38, SC56, SC65	
REFFUG - includes: 1F, 2F, 4F, 11F, 12F, 13F, 18F, 20F, 21/22F, 30B02F, 30B03F, 31F, 36F, 37F, 38F, 41/46/24F, 47F, 47PSA, 48F, 49F, 175, 52F, 133F, DOCKS, FUEL DRUM, GBF, LPG STGF, MVRUF, T1F, T2/2AF, T3F, TRKRACKFUG, 201	Refinery Fugitives VOC Subcaps	VOC	205.8 46.99	tpy lb/hr	SC32, SC33, SC34, SC35, SC36, SC37, SC56, SC65	SC32, SC33, SC35, SC36, SC34, SC43, SC56, SC65	
		H_2S (total plant wide limit)	12.79 2.92	tpy lb/hr	SC38, SC56, SC65	SC38, SC56, SC65	
1	Heater - Crude Heater (01-H-01)	NO_x	19.24 5.09	tpy lb/hr	SC39, SC40(CEMS),	SC40, SC43, SC63	

Permit Number: 38754 and PSDTX324M13 (Version Date: 6/18/2012)							
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirement	Recordkeeping Requirement	Reporting Requirements
			Limit	Units (lb/hr, TPY, etc.)	Spec. Cond.	Spec. Cond.	Spec. Cond.
		VOC	2.9 0.68	tpy lb/hr	SC63		
		SO_2	6.43 2.2	tpy lb/hr			
		CO	20.13 6.33	tpy lb/hr			
		PM/PM_{10}	4 0.94	tpy lb/hr			
131	Heater - Crude Preflash (01-H-02)	NO_x	6.291.51	tpylb/hr	SC63	SC43, SC63	
		VOC	0.35 0.08	tpy lb/hr			
		SO_2	0.64 0.25	tpy lb/hr			
		CO	2.71 0.62	tpy lb/hr			
		PM/PM_{10}	0.49 0.11	tpy lb/hr			
132	Heater - Crude Stabilizer (01-H-03)	NO_x	2.06 0.48	tpy lb/hr	SC63	SC43, SC63	
		VOC	0.11 0.03	tpy lb/hr			
		SO_2	0.25 0.08	tpy lb/hr			
		CO	0.72 0.17	tpy lb/hr			
		PM/PM_{10}	0.15 0.04	tpy lb/hr			
74	Vacuum Heater	NO_x	18.83 5.62	tpy lb/hr	SC39, SC63	SC43, SC63	

Permit Number: 38754 and PSDTX324M13 (Version Date: 6/18/2012)							
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirement	Recordkeeping Requirement	Reporting Requirements
			Limit	Units (lb/hr, TPY, etc.)	Spec. Cond.	Spec. Cond.	Spec. Cond.
		VOC	1.69 0.5	tpy lb/hr			
		SO_2	3.34 1.44	tpy lb/hr			
		CO	15.69 4.68	tpy lb/hr			
		PM/PM_{10}	2.34 0.7	tpy lb/hr			
114	Heater - Desalter Heater (11-H-01)	NO_x	20.71 6.69	tpy lb/hr	SC39, SC63	SC43, SC63	
		VOC	1.86 0.6	tpy lb/hr			
		SO_2	4.13 1.93	tpy lb/hr			
		CO	17.26 5.58	tpy lb/hr			
		PM/PM_{10}	2.57 0.83	tpy lb/hr			
115A/B	HDS Heaters	NO_x	42.86 10.72	tpy lb/hr	SC39, SC63	SC43, SC63	
		VOC	3.85 0.96	tpy lb/hr			
		SO_2	8.54 3.1	tpy lb/hr			
		CO	32.91 8.93	tpy lb/hr			
		PM/PM_{10}	5.32 1.33	tpy lb/hr			
116	Heater - HDS Pre-Heater (12-H-02)	NO_x	8.28 2.14	tpy lb/hr	SC39, SC63	SC43, SC63	

Permit Number: 38754 and PSDTX324M13 (Version Date: 6/18/2012)							
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirement	Recordkeeping Requirement	Reporting Requirements
			Limit	Units (lb/hr, TPY, etc.)	Spec. Cond.	Spec. Cond.	Spec. Cond.
		VOC	0.37 0.1	tpy lb/hr			
		SO_2	0.83 0.31	tpy lb/hr			
		CO	1.1 0.29	tpy lb/hr			
		PM/PM_{10}	0.51 0.13	tpy lb/hr			
118	Hydrogen Reformer Heater	NO_x	284.4 60.19	tpy lb/hr	SC39, SC40(CEMS), SC63	SC40, SC43, SC63	
		VOC	41.85 9.05	tpy lb/hr			
		SO_2	122.64 43.55	tpy lb/hr			
		CO	220.73 50.16	tpy lb/hr			
		PM/PM_{10}	35.8 7.47	tpy lb/hr			
153	Heater - HR Boiler (30-B-02)	NO_x	82.34 22.56	tpy lb/hr	SC39, SC40(CEMS), SC63	SC40, SC43, SC63	
		VOC	3.99 1.52	tpy lb/hr			
		SO_2	10.66 4.89	tpy lb/hr			
		PM/PM_{10}	5.51 2.1	tpy lb/hr			
117	Heater - Alky Frac. Reb. (31-H-01)	NO_x	19.86 5.12	tpy lb/hr	SC39, SC40(CEMS), SC63	SC40, SC43, SC63	
		VOC	2.97 0.77	tpy lb/hr			

Permit Number: 38754 and PSDTX324M13 (Version Date: 6/18/2012)							
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirement	Recordkeeping Requirement	Reporting Requirements
			Limit	Units (lb/hr, TPY, etc.)	Spec. Cond.	Spec. Cond.	Spec. Cond.
		SO_2	6.6 2.47	tpy lb/hr			
		CO	8.83 2.28	tpy lb/hr			
		PM/PM_{10}	4.11 1.06	tpy lb/hr			
120	Heater - Butamer Heater (36-H-01)	NO_x	4.3 2	tpy lb/hr	SC63	SC43, SC63	
		VOC	0.19 0.09	tpy lb/hr			
		SO_2	0.41 0.29	tpy lb/hr			
		CO	0.98 0.27	tpy lb/hr			
		PM/PM_{10}	0.26 0.12	tpy lb/hr			
162	Oleflex Heater	NO_x	65.75 17.72	tpy lb/hr	SC39, SC40(CEMS), SC63	SC40, SC43, SC63	
		VOC	8.41 2.1	tpy lb/hr			
		SO_2	18.66 6.75	tpy lb/hr			
		CO	69.49 19.45	tpy lb/hr			
		PM/PM_{10}	11.62 2.9	tpy lb/hr			
119	Heater - Sulften Heater (46-H-01)	NO_x	5.21 1.71	tpy lb/hr	SC63	SC43, SC63	
		VOC	0.24 0.08	tpy lb/hr			

Permit Number: 38754 and PSDTX324M13 (Version Date: 6/18/2012)							
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirement	Recordkeeping Requirement	Reporting Requirements
			Limit	Units (lb/hr, TPY, etc.)	Spec. Cond.	Spec. Cond.	Spec. Cond.
		SO_2	0.63 0.24	tpy lb/hr			
		CO	1.49 0.35	tpy lb/hr			
		PM/PM_{10}	0.32 0.11	tpy lb/hr			
150	HCU Heater	NO_x	48.76 12.19	tpy lb/hr	SC39, SC63	SC43, SC63	
		VOC	4.38 1.1	tpy lb/hr			
		SO_2	9.72 3.52	tpy lb/hr			
		CO	24.38 6.1	tpy lb/hr			
		PM/PM_{10}	6.06 1.51	tpy lb/hr			
151	Heater - NHU Heater (48-H-01)	PM/PM_{10}	0.95 0.26	tpy lb/hr	SC39, SC63	SC43, SC63	
		VOC	0.69 0.19	tpy lb/hr			
		SO_2	1.52 0.61	tpy lb/hr			
		NO_x	12.72 3.52	tpy lb/hr			
		CO	3.82 1.06	tpy lb/hr			
152	CRU Heater	NO_x	133.06 36.9	tpy lb/hr	SC39, SC40(CEMS), SC63	SC40, SC43, SC63	
		VOC	10.25 3.03	tpy lb/hr			

Permit Number: 38754 and PSDTX324M13 (Version Date: 6/18/2012)							
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirement	Recordkeeping Requirement	Reporting Requirements
			Limit	Units (lb/hr, TPY, etc.)	Spec. Cond.	Spec. Cond.	Spec. Cond.
		SO_2	25.69 11.1	tpy lb/hr			
		CO	57.02 16.85	tpy lb/hr			
		PM/PM_{10}	14.16 4.18	tpy lb/hr			
172	Heater - RSU Heater (49-H-71)	NO_x	15.26 3.96	tpy lb/hr	SC39, SC63	SC43, SC63	
		VOC	1.37 0.36	tpy lb/hr			
		SO_2	3.04 1.14	tpy lb/hr			
		CO	12.72 3.3	tpy lb/hr			
		PM/PM_{10}	1.9 0.49	tpy lb/hr			
49-H-90	Heater - C7 Splitter Reb. (49-H-90)	NO_x	15.46 3.99	tpy lb/hr	SC39, SC40(CEMS), SC63	SC40, SC43, SC63	
		VOC	2.18 0.57	tpy lb/hr			
		SO_2	4.83 1.84	tpy lb/hr			
		CO	16.82 5.32	tpy lb/hr			
		PM/PM_{10}	3.01 0.79	tpy lb/hr			
195	Heater - GDU Charge Heater (52-H-01)	NO_x	14.69 3.35	tpy lb/hr	SC39, SC40(CEMS), SC63	SC40, SC43, SC63	
		VOC	3.34 0.89	tpy lb/hr			

Permit Number: 38754 and PSDTX324M13 (Version Date: 6/18/2012)							
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirement	Recordkeeping Requirement	Reporting Requirements
			Limit	Units (lb/hr, TPY, etc.)	Spec. Cond.	Spec. Cond.	Spec. Cond.
		SO_2	7.4 2.87	tpy lb/hr			
		CO	34.29 13.15	tpy lb/hr			
		PM/PM_{10}	4.61 1.23	tpy lb/hr			
124	API Separator	NO_x	0.84 0.19	tpy lb/hr	SC16, SC39	SC16, SC43	SC39
		VOC	2.08 0.43	tpy lb/hr			
		SO_2	0.13 0.03	tpy lb/hr			
		CO	7.22 1.65	tpy lb/hr			
168	Oleflex CCR	SO_2	0.19 0.04	tpy lb/hr	SC27	SC43	
V-201	Unloading Vent	VOC	0.16 0.04	tpy lb/hr	SC7	SC43	
122	Cooling Tower - HOC	VOC	26.67 6.09	tpy lb/hr	SC31	SC31, SC43	
123	Cooling Tower - Alky	VOC	5.52 1.26	tpy lb/hr	SC31	SC31, SC43	
167-CT	Cooling Tower - BUP	VOC	7.91 1.81	tpy lb/hr	SC31	SC31, SC43	
1CT	Cooling Tower - Crude	VOC	0.92 0.21	tpy lb/hr	SC31	SC31, SC43	
73-P-3	Engine - 73-P-3	NO_x	15.35 11.63	tpy lb/hr		SC43	
		VOC	1.59 1.21	tpy lb/hr			

Permit Number: 38754 and PSDTX324M13 (Version Date: 6/18/2012)							
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirement	Recordkeeping Requirement	Reporting Requirements
			Limit	Units (lb/hr, TPY, etc.)	Spec. Cond.	Spec. Cond.	Spec. Cond.
		SO_2	1.3 0.98	tpy lb/hr			
		CO	4.23 3.21	tpy lb/hr			
		PM/PM_{10}	1.39 1.06	tpy lb/hr			
73-P-4	Engine - 73-P-4	NO_x	18.09 10.42	tpy lb/hr		SC43	
		VOC	1.88 1.08	tpy lb/hr			
		SO_2	1.53 0.88	tpy lb/hr			
		CO	4.99 2.87	tpy lb/hr			
		PM/PM_{10}	1.64 0.95	tpy lb/hr			
73-P-5	Engine - 73-P-5	NO_x	29.12 11.63	tpy lb/hr		SC43	
		VOC	3.02 1.21	tpy lb/hr			
		SO_2	2.46 0.98	tpy lb/hr			
		CO	8.03 3.21	tpy lb/hr			
		PM/PM_{10}	2.64 1.06	tpy lb/hr			
72-P-6	Engine - 72-P-6	NO_x	11.64 11.63	tpy lb/hr		SC43	
		VOC	1.21 1.21	tpy lb/hr			

Permit Number: 38754 and PSDTX324M13 (Version Date: 6/18/2012)							
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirement	Recordkeeping Requirement	Reporting Requirements
			Limit	Units (lb/hr, TPY, etc.)	Spec. Cond.	Spec. Cond.	Spec. Cond.
		SO_2	0.98 0.98	tpy lb/hr			
		CO	3.21 3.21	tpy lb/hr			
		PM/PM_{10}	1.06 1.06	tpy lb/hr			
72-P-7	Engine - 72-P-7	NO_x	2.25 11.63	tpy lb/hr		SC43	
		VOC	0.23 1.21	tpy lb/hr			
		SO_2	0.19 0.98	tpy lb/hr			
		CO	0.62 3.21	tpy lb/hr			
		PM/PM_{10}	0.2 1.06	tpy lb/hr			
72-P-8	Engine - 72-P-8	NO_x	2.79 11.63	tpy lb/hr		SC43	
		VOC	0.29 1.21	tpy lb/hr			
		SO_2	0.24 0.98	tpy lb/hr			
		CO	0.77 3.21	tpy lb/hr			
		PM/PM_{10}	0.25 1.06	tpy lb/hr			
72-P-9	Engine - 72-P-9	NO_x	17.32 11.63	tpy lb/hr		SC43	
		VOC	1.8 1.21	tpy lb/hr			

Permit Number: 38754 and PSDTX324M13 (Version Date: 6/18/2012)							
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirement	Recordkeeping Requirement	Reporting Requirements
			Limit	Units (lb/hr, TPY, etc.)	Spec. Cond.	Spec. Cond.	Spec. Cond.
		SO_2	1.47 0.98	tpy lb/hr			
		CO	4.77 3.21	tpy lb/hr			
		PM/PM_{10}	1.57 1.06	tpy lb/hr			
72-P-10	Engine - 72-P-10	NO_x	26.31 8.36	tpy lb/hr		SC43	
		VOC	2.73 0.87	tpy lb/hr			
		SO_2	2.23 0.71	tpy lb/hr			
		CO	7.25 2.3	tpy lb/hr			
		PM/PM_{10}	2.39 0.76	tpy lb/hr			
72-P-11	Engine - 72-P-11	NO_x	23.34 11.75	tpy lb/hr		SC43	
		VOC	2.42 1.22	tpy lb/hr			
		SO_2	1.97 0.99	tpy lb/hr			
		CO	6.43 3.24	tpy lb/hr			
		PM/PM_{10}	2.12 1.07	tpy lb/hr			
72-P-14A	Engine - 72-P-14A	NO_x	14.17 11.63	tpy lb/hr		SC43	
		VOC	1.47 1.21	tpy lb/hr			

Permit Number: 38754 and PSDTX324M13 (Version Date: 6/18/2012)							
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirement	Recordkeeping Requirement	Reporting Requirements
			Limit	Units (lb/hr, TPY, etc.)	Spec. Cond.	Spec. Cond.	Spec. Cond.
		SO_2	1.2 0.98	tpy lb/hr			
		CO	3.91 3.21	tpy lb/hr			
		PM/PM_{10}	1.29 1.06	tpy lb/hr			
72-P-14B	Engine - 72-P-14B	NO_x	17.2 10.32	tpy lb/hr		SC43	
		VOC	1.78 1.07	tpy lb/hr			
		SO_2	1.45 0.87	tpy lb/hr			
		CO	4.74 2.85	tpy lb/hr			
		PM/PM_{10}	1.56 0.94	tpy lb/hr			
50-P-16	Engine - 50-P-16	NO_x	4.74 10.9	tpy lb/hr		SC43	
		VOC	0.49 1.13	tpy lb/hr			
		SO_2	0.4 0.92	tpy lb/hr			
		CO	1.31 3.01	tpy lb/hr			
		PM/PM_{10}	0.43 0.99	tpy lb/hr			
50-P-20	Engine - 50-P-20	NO_x	9.61 10.9	tpy lb/hr		SC43	
		VOC	1 1.13	tpy lb/hr			

Permit Number: 38754 and PSDTX324M13 (Version Date: 6/18/2012)							
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirement	Recordkeeping Requirement	Reporting Requirements
			Limit	Units (lb/hr, TPY, etc.)	Spec. Cond.	Spec. Cond.	Spec. Cond.
		SO_2	0.81 0.92	tpy lb/hr			
		CO	2.65 3.01	tpy lb/hr			
		PM/PM_{10}	0.87 0.99	tpy lb/hr			
16-P-04	Engine - 16-P-04	NO_x	0.21 8	tpy lb/hr		SC43	
		VOC	0.02 0.83	tpy lb/hr			
		SO_2	0.02 0.68	tpy lb/hr			
		CO	0.06 2.2	tpy lb/hr			
		PM/PM_{10}	0.02 0.73	tpy lb/hr			
16-P-07	Engine - 16-P-07	NO_x	0.15 9.69	tpy lb/hr		SC43	
		VOC	0.02 1.01	tpy lb/hr			
		SO_2	0.01 0.82	tpy lb/hr			
		CO	0.04 2.67	tpy lb/hr			
		PM/PM_{10}	0.01 0.88	tpy lb/hr			
126, 158, 127, 135	Main Flare, Ground Flare, BUP Flare, Acid Gas Flare Subcaps	NO_x	11.48 62.17	tpy lb/hr	SC15, SC51	SC43, SC51	SC51
		VOC	136.78 220.25	tpy lb/hr			

Permit Number: 38754 and PSDTX324M13 (Version Date: 6/18/2012)							
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirement	Recordkeeping Requirement	Reporting Requirements
			Limit	Units (lb/hr, TPY, etc.)	Spec. Cond.	Spec. Cond.	Spec. Cond.
		SO_2	4.7 18.82	tpy lb/hr			
		CO	76.87 450.94	tpy lb/hr			
31	Loading - Heavy Oil	VOC	4.72 16.45	tpy lb/hr		SC43	
SHIP FUG	Loading - Ships Fugitives	VOC	91.74 186.57	tpy lb/hr	SC13	SC43	
VRU	Loading - MVRU	VOC	23.13 33.74	tpy lb/hr	SC14, SC39, SC40, SC42	SC40, SC42, SC43	SC39, SC40
TRUCKFUG	Loading - Truck Fugitives	VOC	10.87 11.88	tpy lb/hr	SC9	SC43	
TRUCKCOMB	Loading - Truck Combustor	NO_x	7.41 6.98	tpy lb/hr	SC8, SC39	SC8, SC43	SC39
		VOC	9.41 8.19	tpy lb/hr			
		SO_2	0.01 0.01	tpy lb/hr			
		CO	11.44 13.96	tpy lb/hr			
AE-49601A/B	AE-49601A/B Analyzer Vent	VOC	0.01 0.01	tpy lb/hr		SC43	
AE-49900A/B	AE-49900A/B Analyzer Vent	VOC	0.01 0.01	tpy lb/hr		SC43	
AE-49901A/B	AE-49901A/B Analyzer Vent	VOC	0.01 0.01	tpy lb/hr		SC43	
121	HOC Belco Scrubber	NO_x	845.44 356.2	tpy lb/hr	SC22, SC26, SC39, SC40, SC42	SC22, SC26, SC40, SC42, SC43	SC39, SC40
		VOC	115.53 28.02	tpy lb/hr			

Permit Number: 38754 and PSDTX324M13 (Version Date: 6/18/2012)							
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirement	Recordkeeping Requirement	Reporting Requirements
			Limit	Units (lb/hr, TPY, etc.)	Spec. Cond.	Spec. Cond.	Spec. Cond.
		SO_2	420.09 205.53	tpy lb/hr			
		CO	1470.33 889.96	tpy lb/hr			
		PM/PM_{10}	527 120.32	tpy lb/hr			
	SRU Incinerators	NO_x	142.8 54.64	tpy lb/hr	SC25, SC39, SC40, SC42	SC40, SC42, SC43, SC63	SC39, SC40
		VOC	3.13 0.96	tpy lb/hr			
		SO_2	674.9 191.3	tpy lb/hr			
		CO	392.1 177.4	tpy lb/hr			
		PM/PM_{10}	4.39 1.34	tpy lb/hr			
Tanks - include: 5, 6, 7, 8, 9, 10, 11, 12, 13, 15, 16, 17, 34, 35, 36, 37, 46, 48, TK-51, 60, 61, 63, 64, 69, 70, 71, 72, 88, 89, 90, 91, 92, 93, 94, 95, 96, TK-112, TK-114, 129, 140, 142, 156, 157, 164, 165, 166, 169, 173, 174, 196, 197, 198	Tanks subcap	VOC	289.6 232.7	tpy lb/hr	SC29	SC2, SC3, SC4, SC29, SC43, SC53, SC57	
MSS Caps	MSS	CO	54.35 3005	tpy lb/hr	SC54, SC55, SC56, SC57, SC58, SC59, SC60, SC63, SC64, SC65, SC71	SC43, SC53, SC54, SC56, SC57, SC59, SC60, SC67, SC69, SC71	
		NO_x	11.24 560.3	tpy lb/hr			
		VOC	59.96 1838	tpy lb/hr			
		SO_2	37.24 1019	tpy lb/hr			
		H_2S	0.22 6.59	tpy lb/hr			

Permit Number: 38754 and PSDTX324M13 (Version Date: 6/18/2012)							
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirement	Recordkeeping Requirement	Reporting Requirements
			Limit	Units (lb/hr, TPY, etc.)	Spec. Cond.	Spec. Cond.	Spec. Cond.
		PM/PM_{10}	1.28 80.53	tpy lb/hr			
		Ammonia	0.17 4.41	tpy lb/hr			
		Exempt Solvents	0.60 1.76	tpy lb/hr			

Permit Numbers 38754 and PSDTX324M13

SPECIAL CONDITIONS

Permit Numbers 38754 and PSDTX324M13

1. This permit authorizes emissions only from those points listed in the attached table entitled "Emission Sources Emission Caps and Individual Emissions Limitations," and the facilities covered by this permit are authorized to emit subject to the emission rate limits on that table and other operating requirements specified in the special conditions. **(PSD)(6/08)**

Throughput Limitations

2. The total transfer rate of resid, bunker, atmospheric tower bottoms, vacuum tower bottoms, slurry, hydrodesulfurization (HDS) feed, heavy oil cracking (HOC) feed, vacuum feed, and gas oil to and from tanks at this and the adjacent Valero Logistics Operations, L.P., (RN104276696) site shall not exceed 91,000 barrels per hour (bbl/hr). The total transfer rate of gas oil to and from tanks at this and the adjacent Valero Logistics Operations, L.P., (RN104276696) site shall not exceed 26,000 bbl/hr. **(1/04)**

3. A maximum of eight tanks on the site may be in naphtha service at any time. The total sitewide naphtha transfer rate shall not exceed 10,000 bbl/hr for any tank or a total of 13,150 bbl/hr for all tanks in naphtha service.

   A maximum of 11 tanks at this and the adjacent Valero Logistics Operations, L.P., (RN104276696) site may be in crude oil service at any time. The total sitewide crude oil transfer rate for both sites shall not exceed a total of 81,000 bbl/hr for all tanks in crude oil service. **(1/04)**

4. A maximum of six tanks on this and the adjacent Valero Logistics Operations, L.P., (RN104276696) site may be in diesel service at any time. The total diesel transfer rate for both sites shall not exceed 12,500 bbl/hr for any tank or a total of 17,000 bbl/hr for all tanks in diesel service. **(1/04)**

5. Tank truck loading operations are limited to the following liquids and maximum loading rates:

Chemical	Hourly Rate (gal/hr)
Kerosene	30,000
Diesel	30,000
Gasoline	60,000

6. The Marine loading shall comply with the following:

A. Marine loading with emissions that are controlled with the marine vapor recovery unit (VRU) shall be limited to a maximum of 35,000 bbl/hr. The liquids that are loaded at this rate and controlled with the VRU at this facility are limited to methyl tert butyl ether, gasoline, natural gasoline, naphtha, cat gasoline, alkylate, and reformate.

The BT concentrate, mixed xylenes, heartcut, and toluene concentrate may also be loaded into marine vessels with emissions controlled by the VRU, at a rate not to exceed 5,000 bbl/hr. Only one of these products may be loaded at a time.

B. Marine loading with uncontrolled vapor emissions shall be limited to the following services at the indicated rates:

Liquid	Barge bbl/hr	Ship bbl/hr
Diesel*	8,500	12,500
Kerosene*	5,000	12,500
Gas Oil	6,000	20,000
ATB	6,000	20,000
VTB	6,000	20,000
Slurry	6,000	0
Bunker	6,000	20,000

* Diesel and kerosene shall not be loaded onto ships and barges concurrently. **(6/08)**

Loading Controls

7. Operation without visible liquid leaks or spills shall be maintained at all loading or unloading facilities regardless of vapor pressure. This does not apply to momentary dripping associated with the initial connection or disconnection of fittings. Sustained dripping from fittings during loading or unloading operations is not permitted. Any liquid spill that occurs during loading or unloading activities shall be cleaned up immediately to minimize air emissions.

8. Emissions resulting from the tank truck loading of gasoline shall be routed to the Vapor Combustor (Emission Point No. [EPN] TRUCKCOMB) for final abatement. The volatile organic compounds (VOC) emissions from EPN TRUCKCOMB shall not exceed 10 milligrams per liter of gasoline loaded. The vapor combustor combustion temperature shall be maintained at or above 1400˚F (based on a five-minute averaging period) when loading vapors are routed to it. This temperature shall be recorded during loading operations and the records maintained on-site. The vapor combustor operating temperature may be lowered if it has been tested at the lower temperature in accordance

with Special Condition No. 39 to demonstrate compliance with this emission limit. Recordkeeping associated with this permit condition shall commence on April 1, 1999.

9. All tank trucks loading gasoline at this facility shall be leak-tight tested a minimum of once a year using the method described in the U.S. Environmental Protection Agency (EPA) regulations in Title 40 Code of Federal Regulations Part 60 (40 CFR Part 60), Subparts A and XX on Standards of Performance for New Stationary Sources promulgated for Bulk Gasoline Terminals.

10. All tank truck loading of kerosene and diesel shall be conducted using submerged loading procedures.

11. The marine VRU shall limit VOC emissions from EPN VRU to 5 mg/l of liquid loaded.

12. All marine loading emissions of liquids with vapor pressures greater than 0.5 pound per square inch, absolute (psia) must be vented to the VRU. **(9/04)**

13. A vacuum of at least one-inch water column shall be established downstream of the dock pressure control valve prior to commencing marine loading. A vacuum shall also be established on the barge or ship being loaded if possible. The vacuum shall be maintained during loading and monitored continually or an alarm activated if the vacuum is not maintained. **(9/04)**

14. The VRU VOC concentration as measured by the continuous emission monitor specified in Special Condition No. 40 shall not exceed 7,621 parts per million (ppm) over any one-hour period while the marine loading emissions are being vented. If the reading exceeds this limit, marine loading shall be secured, the Texas Commission on Environmental Quality (TCEQ) Corpus Christi Regional Office notified, and the cause determined and corrected before loading resumes. **(9/04)**.

<u>Combustion Controls</u>

15. Flares shall be designed and operated in accordance with 40 CFR § 60.18 including specifications of minimum heating value of the waste gas, maximum tip velocity, and pilot flame monitoring. If necessary to insure adequate combustion, sufficient fuel gas shall be added to make the gases combustible. An infrared monitor is considered equivalent to a thermocouple for flame monitoring purposes.

    The Acid Gas Flare (EPN 135) is not subject to the requirements of 40 CFR § 60.18. It shall be used only in case of upsets. **(PSD) (6/08)**

16. The American Petroleum Institute (API) Separator Combustor shall achieve at least 98 percent destruction efficiency. The vapor combustor combustion temperature shall be maintained at or above 1600˚F (based on a five-minute averaging period) when the separator is in service. This temperature shall be recorded and the records maintained on-site. The vapor combustor operating temperature may be lowered if it has been tested at the lower temperature in accordance with Special Condition No. 39 to demonstrate compliance with this emission limit. Records associated with this permit condition shall be kept for five years. **(PSD) (6/08)**

17. No visible emissions are allowed from the heaters. **(PSD)**

18. The permittee shall operate a continuous hydrogen sulfide (H_2S) monitoring instrument in the fuel feed line header for all fired units with a firing rate greater than 40 MMBtu/hr to continuously monitor a representative sample of fuel gas for H2S content. The instrument shall be installed according to the specifications set out in 40 CFR § 60.105 and follow the quality-assurance or quality-control procedure stated in the attached table entitled "Quality Assurance/Quality Control Procedure." These gases shall have a maximum H_2S concentration of 0.054 grain per dry standard cubic foot (dscf) on an hourly average. The Vacuum Unit Heater (EPN 74) may also be fired with vacuum off-gas having a maximum H2S concentration of 0.10 grain/dscf on an hourly average. **(PSD)**

19. Heater and reboiler emissions shall meet the following specifications:

EPN	Facility	NO_X lb/MMBtu	CO lb/MMBtu	NO_X Compliance Method[1]
162	Oleflex Charge Heater Oleflex Interheater 1 Oleflex Interheater 2	0.06	0.05	CEMS
1	Crude Heater	0.06	0.05	CEMS
74	Vacuum Unit Heater	0.06	0.05	stack test
150	HCU RX-01 Fractionater Reboiler	0.06	0.03	stack test
152	CRU Charge Heaters CRU No. 2 Interheater CRU No. 3 Interheater	0.07	0.03	CEMS
153	Boiler 30-B-02[2]	0.08		CEMS
172	RSU Heater	0.06	0.05	stack test
49H90	C7 Splitter Reboiler	0.04	0.05	CEMS
114	Desalter Heater	0.06	0.05	stack test
115	HDS Heater A HDS Heater B	0.06	0.05	stack test
116	HDS Heavy Oil Preheater	0.12	0.016	

EPN	Facility	NO_X lb/MMBtu	CO lb/MMBtu	NO_X Compliance Method[1]
117	Alky Fract Reboiler	0.036	0.016	CEMS
118	Hydrogen Reformer Heater	0.06	0.05	CEMS
119	Sulften Heater	0.12	0.016	
120	Butamer Heater	0.12	0.016	
195	GD Charge Heater	0.035	100 ppmv	CEMS

Footnote 1:
Compliance method specified in this condition per US EPA Consent Decree SA-05-CA-0569 for the NO_X standard (lb/MMBtu) specified in the table. The Consent Decree standards for units with CEMS are stated in terms of a 365 day rolling average and in terms of a three hour averaging period for those subject only to a stack test. For the purpose of this permit, all standards (NO_X and CO), except for those for Boiler 30-B-02, must be met on an hourly averaging period.

Footnote 2:
The requirements for this boiler were added to this condition from US EPA Consent Decree SA-05-CA-0569. **(PSD) (6/10)**

20. Upon request by the Executive Director of the TCEQ, the EPA, or any local air pollution control program having jurisdiction, the holder of this permit shall provide a sample and/or an analysis of the fuel(s) utilized in these facilities or shall allow air pollution control agency representatives to obtain a sample for analysis. **(PSD)**

Sulfur Recovery Units (SRUs) and HOC Scrubber

21. The coke burn-off non-sulfate particulate matter (PM) emissions may not exceed 0.57 pound per 1,000 pounds of coke burn-off. The HOC scrubber sulfuric acid mist (a subset of total PM) emissions shall not exceed 0.35 pound per 1,000 pounds of coke burn-off. **(PSD) (9/04)**

22. The pH of the HOC scrubber circulating caustic solution shall be continually monitored and be maintained at a level between 6.0 and 9.0 by the addition of fresh caustic solution as required. The pH shall be recorded at least hourly, and the records maintained at the plant site for a period of five years. These records shall be made available for inspection by the Executive Director of the TCEQ or his designated representative. **(PSD) (6/08)**

23. The minimum sulfur recovery efficiency for the SRU/Sulften and SRU/Scot shall be 99.8 percent. The sulfur recovery efficiency shall be determined by calculation as follows:

Efficiency = (S recovered)*(100) / (S acid gas)

Where:	Efficiency	=	sulfur recovery efficiency, percent
	S recovered	=	(S acid gas - S stack), pounds per hour (lb/hr)
	S acid gas	=	sulfur in acid gas stream, lb/hr
	S stack	=	sulfur in incinerator stack, lb/hr **(PSD) (11/01)**

24. Acid gas must be routed to a properly operating SRU train. All SRU trains shall normally be operated when acid gas is being produced to maintain the maximum redundant sulfur capacity. The TCEQ Regional Office shall be notified within 72 hours if any SRU train is not fully operational. The notification shall include a description of the problem, the estimated loss of capacity, actions required to correct the problem, and when the line is expected to be fully operational.

In the event that the Sulften/Scot unit is not operating properly, immediate steps shall be taken to correct the improper operation and shift the acid gas feeds to another fully operational SRU. **(PSD) (11/01)**

25. The Scot tail gas incinerator shall be operated with no less than 3.0 percent oxygen (O_2) in the incinerator stack and at no less than 1500˚F incinerator firebox exit temperature. The incinerator shall achieve a minimum H_2S destruction efficiency of 99.9 percent or 5 parts per million by volume (ppmv) (corrected to 3 percent excess O_2) reduced sulfur compound exit concentration. If stack testing indicates that a higher temperature or O_2 concentration is necessary to obtain a minimum H_2S destruction efficiency of 99.9 percent or 5 ppmv (corrected to 3 percent excess O_2) reduced sulfur compound exit concentration, then the temperature and O_2 maintained during the stack test will become the new minimum operating limits. The O_2 and temperature requirements do not apply when performing stack tested on the incinerator in accordance with Special Condition No. 39. The permit holder may request that the operating limits be relaxed with a permit alteration request should stack testing indicate the required emissions control is obtained at the proposed limits. **(PSD) (11/01)**

26. In order to control opacity from the stack of EPN 121, the permittee shall maintain the liquid to the filtering modules at a pressure greater than 45 pounds per square inch (psi) and the flue gas pressure drop across the filtering modules and the cyclolabs at no less than 5 inches of water. Liquid pressure and pressure drop shall be continuously recorded and maintained at the plant site for a period of five years. These records shall be made available for inspection by the Executive Director of the TCEQ or his designated representative.

The opacity of emissions from the Caustic Scrubber Stack (EPN 121) shall not exceed 20 percent averaged over a six-minute period as determined by a trained observer. **(PSD) (6/08)**

Control Requirements

27. The Oleflex and Naphtha Continuous Catalyst Regenerator (CCR) scrubber liquids shall be sampled at least twice daily (once per shift) for caustic inventory. The caustic concentration of the Oleflex CCR shall be maintained greater than that represented in the confidential portion of the permit amendment application dated July 15, 1994. The caustic concentration of the Naphtha Reformer CCR shall be maintained greater than 0.41 weight percent sodium hydroxide as represented in Table 14 of the Standard Permit Application Permit Number 50947 dated April 8, 2002. **(6/02)**

28. The caustic absorber circulation rate for the Naphtha CCR shall be a minimum of 368 gpm. The circulation rate shall be recorded at least hourly, and the records maintained at the plant site for a period of five years. These records shall be made available for inspection by the Executive Director of the TCEQ or his designated representative. **(6/08)**

29. Storage tanks are subject to the following requirements. The control requirements specified in paragraphs A D of this condition shall not apply (1) where the VOC has an aggregate partial pressure of less than 0.50 psia at the maximum feed temperature or 95˚F, whichever is greater, or (2) to storage tanks smaller than 25,000 gallons.

    A. An internal floating deck or roof or equivalent control shall be installed in all tanks. The floating roof shall be equipped with one of the following closure devices between the wall of the storage vessel and the edge of the internal floating roof: (1) a liquid-mounted seal, (2) two continuous seals mounted one above the other, or (3) a mechanical shoe seal.

    B. An open-top tank containing a floating roof (external floating roof tank) which uses double seal or secondary seal technology shall be an approved control alternative to an internal floating roof tank provided the primary seal consists of either a mechanical shoe seal or a liquid-mounted seal and the secondary seal is rim-mounted. A weathershield is not approvable as a secondary seal unless specifically reviewed and determined to be vapor-tight.

    C. For any tank equipped with a floating roof, the permit holder shall perform the visual inspections and seal gap measurements as specified in 40 CFR § 60.113b, Testing and Procedures (as amended at 54 FR 32973, Aug. 11, 1989), to verify fitting and seal integrity. Records shall be maintained of the dates seals were inspected and seal gap measurements made, results of inspections and

measurements made (including raw data), and actions taken to correct any deficiencies noted.

D. The floating roof design shall incorporate sufficient flotation to conform to the requirements of API Code 650 dated November 1, 1998, except that an internal floating cover need not be designed to meet rainfall support requirements and the materials of construction may be steel or other materials.

E. Uninsulated tank exterior surfaces exposed to the sun shall be white or aluminum. Storage tanks must be equipped with permanent submerged fill pipes.

F. The permit holder shall maintain an emissions record which includes calculated emissions of VOC from all storage tanks during the previous calendar month and the past consecutive 12-month period. The record shall include tank identification number, control method used, tank capacity in barrels, name of the material stored, VOC molecular weight, VOC monthly average temperature in degrees Fahrenheit, VOC vapor pressure at the monthly average material temperature in psia, VOC throughput for the previous month and year-to-date. Records of VOC monthly average temperature are not required to be kept for unheated tanks which receive liquids that are at or below ambient temperatures.

Emissions for tanks shall be calculated using the TCEQ publication titled "Technical Guidance Package for Chemical Sources - Storage Tanks."

G. Floating roof tanks 23, 26, and 164 shall be equipped with a Pole Sleeve System or equivalent by April 13, 2010 as required by the Storage Tank Emission Reduction Partnership Program (STERPP) Agreement with U.S. EPA, dated May 23, 2001, as listed in Appendix I and Annex A of that agreement. Storage Tank 164 was owned by the Valero Bill Greehey Refinery – West Plant at the time of STERPP Agreement execution and is currently owned by NuStar Energy LP (a non-affiliated company). **(6/10)**

30. Non-fugitive emissions from relief valves, safety valves, or rupture discs of gases containing VOC at a concentration of greater than 1 percent are not authorized by this permit unless authorized on the maximum allowable rates table. Any releases directly to atmosphere from relief valves, safety valves, or rupture discs of gases containing VOC at a concentration greater than 1 weight percent are not consistent with good practice for minimizing emissions. **(11/01)**

31. The VOC associated with cooling tower water shall be monitored monthly with an approved air stripping system or equivalent. The appropriate equipment shall be maintained so as to minimize fugitive VOC emissions from the cooling tower. Faulty equipment shall be repaired at the earliest opportunity, but no later than the next scheduled shutdown of the process unit in which the leak occurs. The results of the

monitoring and maintenance efforts shall be recorded, and such records shall be maintained for a period of five years. The records shall be made available to the TCEQ Executive Director upon request. **(6/08)**

Fugitive Emissions Control

32. Piping, Valves, Flanges, Pumps, and Compressors in VOC Service - Intensive Directed Maintenance - 28 VHP

Except as may be provided for in the special conditions of this permit, the following requirements apply to the above-referenced equipment.

A. These conditions shall not apply (1) where the VOC has an aggregate partial pressure or vapor pressure of less than 0.044 psia at 68˚F or, (2) operating pressure is at least 5 kilopascals (0.725 psi) below ambient pressure, (3) to Fugitive Areas 4F, 20F, 36F, 54F, 133F, and FUG-DOCKS if monitored under Special Condition Nos. 33 or 34, or (4) to fugitive areas monitored under Special Condition 35. Equipment excluded from this condition shall be identified in a list to be made available upon request.

B. Construction of new and reworked piping, valves, pump systems, and compressor systems shall conform to applicable American National Standards Institute (ANSI), API, American Society of Mechanical Engineers (ASME), or equivalent codes.

C. New and reworked underground process pipelines shall contain no buried valves such that fugitive emission monitoring is rendered impractical.

D. To the extent that good engineering practice will permit, new and reworked valves and piping connections shall be so located to be reasonably accessible for leak-checking during plant operation. Non-accessible valves, as defined by 30 TAC Chapter 115, shall be identified in a list to be made available upon request.

E. New and reworked piping connections shall be welded or flanged. Screwed connections are permissible only on piping smaller than two-inch diameter. No later than the next scheduled quarterly monitoring after initial installation or replacement, all new or reworked connections shall be gas-tested or hydraulically-tested at no less than normal operating pressure and adjustments made as necessary to obtain leak-free performance. Connectors shall be inspected by visual, audible, and/or olfactory means at least weekly by operating personnel walk-through.

Each open-ended valve or line shall be equipped with a cap, blind flange, plug, or a second valve. Except during sampling, the second valve shall be closed.

F. Accessible valves shall be monitored by leak-checking for fugitive emissions at least quarterly using an approved gas analyzer. Sealless/leakless valves (including, but not limited to, welded bonnet bellows and diaphragm valves) and relief valves equipped with a rupture disc upstream or venting to a control device are not required to be monitored. For valves equipped with rupture discs, a pressure-sensing device shall be installed between the relief valve and rupture disc to monitor disc integrity. All leaking discs shall be replaced at the earliest opportunity but no later than the next process shutdown.

An approved gas analyzer shall conform to requirements listed in 40 CFR § 60.485(a) (b).

Replaced components shall be re-monitored within 15 days of being placed back into VOC service.

G. Except as may be provided for in the special conditions of this permit, all pump and compressor seals shall be monitored with an approved gas analyzer at least quarterly or be equipped with a shaft sealing system that prevents or detects emissions of VOC from the seal. Seal systems designed and operated to prevent emissions or seals equipped with an automatic seal failure detection and alarm system need not be monitored. These seal systems may include (but are not limited to) dual pump seals with barrier fluid at higher pressure than process pressure, seals degassing to vent control systems kept in good working order, or seals equipped with an automatic seal failure detection and alarm system. Submerged pumps or sealless pumps (including, but not limited to, diaphragm, canned, or magnetic-driven pumps) may be used to satisfy the requirements of this condition and need not be monitored.

H. Damaged or leaking valves or connectors found to be emitting VOC in excess of 500 ppmv or found by visual inspection to be leaking (e.g., dripping process fluids) shall be tagged and replaced or repaired. Damaged or leaking pump and compressor seals found to be emitting VOC in excess of 2,000 ppmv or found by visual inspection to be leaking (e.g., dripping process fluids) shall be tagged and replaced or repaired.

I. Every reasonable effort shall be made to repair a leaking component, as specified in this paragraph, within 15 days after the leak is found. If the repair of a component would require a unit shutdown, the repair may be delayed until the next scheduled shutdown. All leaking components which cannot be repaired until a scheduled shutdown shall be identified for such repair by tagging. At the discretion of the TCEQ Executive Director or his designated representative, early

unit shutdown or other appropriate action may be required based on the number and severity of tagged leaks awaiting shutdown.

J. The results of the required fugitive instrument monitoring and maintenance program shall be made available to the TCEQ Executive Director or his designated representative upon request. Records shall indicate appropriate dates, test methods, instrument readings, repair results, justification for delay of repairs, and corrective actions taken for all components. Records of physical inspections are not required unless a leak is detected.

K. Alternative monitoring frequency schedules of 30 TAC §§ 115.352 through 115.359 or National Emission Standards for Organic Hazardous Air Pollutants, 40 CFR Part 63, Subpart H, may be used in lieu of Items F through G of this condition.

Compliance with the requirements of this condition does not assure compliance with requirements of 30 TAC Chapter 115, an applicable New Source Performance Standards (NSPS), or an applicable National Emission Standard for Hazardous Air Pollutants (NESHAPS) and does not constitute approval of alternative standards for these regulations. (6/10)

33. <u>Piping, Valves, Flanges, Pumps, and Compressors in VOC Service - Directed Maintenance 28 MD</u>

A. These conditions shall not apply (1) where the VOC has an aggregate partial pressure or vapor pressure of less than 0.5 psia at 100˚F or at maximum process operating temperature if less than 100°F, (2) where the operating pressure is at least 5 kilopascals (0.725 psi) below ambient pressure, or (3) to fugitive areas covered by Special Condition Nos. 32 or 35, or EPNs 31F, 133F, and FUG-DOCKS.

B. Construction of new and reworked piping, valves, pump systems, and compressor systems shall conform to applicable ANSI, API, ASME, or equivalent codes.

C. New and reworked underground process pipelines shall contain no buried valves such that fugitive emission monitoring is rendered impractical.

D. To the extent that good engineering practice will permit, new and reworked valves and piping connections shall be so located to be reasonably accessible for leak-checking during plant operation. Non-accessible valves shall be identified in a list to be made available upon request.

E. New and reworked piping connections shall be welded or flanged. Screwed connections are permissible only on piping smaller than two-inch diameter. No

later than the next scheduled monthly monitoring period after initial installation or replacement, all new or reworked connections shall be gas-tested or hydraulically-tested at no less than normal operating pressure and adjustments made as necessary to obtain leak-free performance. Flanges shall be inspected by visual, audible, and/or olfactory means at least weekly by operating personnel walk-through.

Each open-ended valve or line shall be equipped with a cap, blind flange, plug, or a second valve.

F. Accessible valves shall be monitored by leak checking for fugitive emissions at least monthly using an approved gas analyzer and a directed maintenance program. Sealless/leakless valves (including, but not limited to, bellows and diaphragm valves) and relief valves equipped with a rupture disc upstream or venting to a control device are not required to be monitored. For valves equipped with rupture discs, a pressure gauge shall be installed between the relief valve and rupture disc to monitor disc integrity. All leaking discs shall be replaced at the earliest opportunity but no later than the next process shutdown.

A directed maintenance program shall consist of the repair and maintenance of components assisted simultaneously by the use of an approved gas analyzer such that a minimum concentration of leaking VOC is obtained for each component being maintained.

G. Except as may be provided for in the special conditions of this permit, all pump and compressor seals shall be monitored with an approved gas analyzer and a directed maintenance program at least monthly or be equipped with a shaft sealing system that prevents or detects emissions of VOC from the seal. Seal systems designed and operated to prevent emissions or seals equipped with an automatic seal failure detection and alarm system need not be monitored. Seal systems that prevent emissions may include (but are not limited to) dual pump seals with barrier fluid at higher pressure than process pressure or seals degassing to vent control systems kept in good working order.

Submerged pumps or sealless pumps (including, but not limited to, diaphragm, canned, or magnetic-driven pumps) may be used to satisfy the requirements of this condition and need not be monitored.

H. Damaged or leaking valves, flanges, compressor seals, and pump seals found to be emitting VOC in excess of 10,000 ppmv or found by visual inspection to be leaking (e.g., dripping process fluids) shall be tagged and replaced or repaired. Every reasonable effort shall be made to repair a leaking component as specified in this paragraph within 15 days after the leak is found. If the repair of a component would require a unit shutdown, the repair may be delayed until the

next scheduled shutdown. All leaking components which cannot be repaired until a scheduled shutdown shall be identified for such repair by tagging. The TCEQ Executive Director, at his discretion, may require early unit shutdown or other appropriate action based on the number and severity of tagged leaks awaiting shutdown.

I. The results of the required fugitive monitoring and maintenance program shall be made available to the TCEQ Executive Director or his designated representative upon request. Records shall indicate appropriate dates, test methods, instrument readings, repair results, and corrective actions taken. Records of flange inspections are not required unless a leak is detected.

J. Compliance with the requirements of this condition does not assure compliance with requirements of 30 TAC Chapter 115, an applicable NSPS, or an applicable NESHAPS and does not constitute approval of alternative standards for these regulations. **(6/10)**

34. Piping, Valves, Flanges, Pumps, and Compressors in VOC Service - 28M

A. These conditions shall not apply (1) where the VOC has an aggregate partial pressure or vapor pressure of less than 0.5 psia at 100˚F or at maximum process operating temperature if less than 100˚F, (2) where the operating pressure is at least 5 kilopascals (0.725 psi) below ambient pressure, or (3) to fugitive areas covered by Special Condition Nos. 32, 33, or 35. Equipment excluded from this condition shall be identified in a list to be made available upon request.

B. Construction of new and reworked piping, valves, pump systems, and compressor systems shall conform to applicable ANSI, API, ASME, or equivalent codes.

C. New and reworked underground process pipelines shall contain no buried valves such that fugitive emission monitoring is rendered impractical.

D. To the extent that good engineering practice will permit, new and reworked valves and piping connections shall be so located to be reasonably accessible for leak-checking during plant operation. Non-accessible valves, as defined in 30 TAC Chapter 115, shall be identified in a list to be made available upon request.

E. New and reworked piping connections shall be welded or flanged. Screwed connections are permissible only on piping smaller than two-inch diameter. No later than the next scheduled quarterly monitoring period after initial installation or replacement, all new or reworked connections shall be gas-tested or hydraulically-tested at no less than normal operating pressure and adjustments made as necessary to obtain leak-free performance. Connectors shall be inspected

by visual, audible, and/or olfactory means at least weekly by operating personnel walk-through.

Each open-ended valve or line shall be equipped with a cap, blind flange, plug, or a second valve. Except during sampling, the second valve shall be closed.

F. Accessible valves shall be monitored by leak checking for fugitive emissions at least quarterly using an approved gas analyzer. Sealless/leakless valves (including, but not limited to, welded bonnet bellows and diaphragm valves) and relief valves equipped with a rupture disc upstream or venting to a control device are not required to be monitored.

For valves equipped with rupture discs, a pressure-sensing device shall be installed between the relief valve and rupture disc to monitor disc integrity. All leaking discs shall be replaced at the earliest opportunity but no later than the next process shutdown.

An approved gas analyzer shall conform to requirements listed in 40 CFR § 60.485(a) (b).

G. Except as may be provided for in the special conditions of this permit, all pump and compressor seals shall be monitored with an approved gas analyzer at least quarterly or be equipped with a shaft sealing system that prevents or detects emissions of VOC from the seal. Seal systems designed and operated to prevent emissions or seals equipped with an automatic seal failure detection and alarm system need not be monitored. Seal systems that prevent emissions may include (but are not limited to) dual pump seals with barrier fluid at higher pressure than process pressure or seals degassing to vent control systems kept in good working order.

Submerged pumps or sealless pumps (including, but not limited to, diaphragm, canned, or magnetic-driven pumps) may be used to satisfy the requirements of this condition and need not be monitored.

H. Damaged or leaking valves, connectors, compressor seals, and pump seals found to be emitting VOC in excess of 10,000 ppmv or found by visual inspection to be leaking (e.g., dripping process fluids) shall be tagged and replaced or repaired.

Every reasonable effort shall be made to repair a leaking component, as specified in this paragraph, within 15 days after the leak is found. If the repair of a component would require a unit shutdown, the repair may be delayed until the next scheduled shutdown. All leaking components which cannot be repaired until a scheduled shutdown shall be identified for such repair by tagging. At the discretion of the TCEQ Executive Director or his designated representative, early

unit shutdown or other appropriate action may be required based on the number and severity of tagged leaks awaiting shutdown.

I. The results of the required fugitive instrument monitoring and maintenance program shall be made available to the TCEQ Executive Director or his designated representative upon request. Records shall indicate appropriate dates, test methods, instrument readings, repair results, justification for delay of repairs, and corrective actions taken for all components. Records of physical inspections are not required unless a leak is detected. **(6/10)**

35. Piping, Valves, Connectors, Pumps, Agitators, and Compressors for the HF Alkylation Unit and Rapid Acid Transfer Drum, Terminal 1, Rail Car Unloading, and 49-RSU/XFU Fugitive Areas (EPNs 31F, T1F, 201 and 175) - 28VHP

Except as may be provided for in the special conditions of this permit, the following requirements apply to the above-referenced equipment:

A. These conditions shall not apply (1) where the VOC has an aggregate partial pressure or vapor pressure of less than 0.044 psia at 68˚F, (2) operating pressure is at least 5 kilopascals (0.725 psi) below ambient pressure. Equipment excluded from this condition shall be identified in a list to be made available upon request.

The exempted components may be identified by one or more of the following methods:

(1) piping and instrumentation diagram (PID); or

(2) a written or electronic database.

B. Construction of new and reworked piping, valves, pump systems, and compressor systems shall conform to applicable ANSI, API, ASME, or equivalent codes.

C. New and reworked underground process pipelines shall contain no buried valves such that fugitive emission monitoring is rendered impractical. New and reworked buried connectors shall be welded.

D. To the extent that good engineering practice will permit, new and reworked valves and piping connections shall be so located to be reasonably accessible for leak-checking during plant operation. Difficult-to-monitor and unsafe-to-monitor valves, as defined by 30 TAC Chapter 115, shall be identified in a list to be made readily available upon request. The difficult-to-monitor and unsafe-to-monitor valves may be identified by one or more of the methods described in subparagraph A above. If an unsafe-to-monitor component is not considered safe to monitor within a calendar year, then it shall be monitored as soon as possible during safe

to monitor times. A difficult-to-monitor component for which quarterly monitoring is specified may instead be monitored annually.

E. New and reworked piping connections shall be welded or flanged. Screwed connections are permissible only on piping smaller than two-inch diameter. Gas or hydraulic testing of the new and reworked piping connections at no less than operating pressure shall be performed prior to returning the components to service or they shall be monitored for leaks using an approved gas analyzer within 8 hours of the components being returned to service. Adjustments shall be made as necessary to obtain leak-free performance. Connectors shall be inspected by visual, audible, and/or olfactory means at least weekly by operating personnel walk-through.

Each open-ended valve or line shall be equipped with a cap, blind flange, plug, or a second valve to seal the line so that no leakage occurs. Except during sampling, both valves shall be closed. If the removal of a component for repair or replacement results in an open-ended line or valve, it is exempt from the requirement to install a cap, blind flange, plug, or second valve for 24 hours. If the repair or replacement is not completed within 24 hours, the line or valve must have a cap, blind flange, plug, or second valve installed.

F. Accessible valves shall be monitored by leak-checking for fugitive emissions at least quarterly using an approved gas analyzer. Sealless/leakless valves (including, but not limited to, welded bonnet bellows and diaphragm valves) and relief valves equipped with a rupture disc upstream or venting to a control device are not required to be monitored. For valves equipped with rupture discs, a pressure-sensing device shall be installed between the relief valve and rupture disc to monitor disc integrity. All leaking discs shall be replaced at the earliest opportunity but no later than the next process shutdown.

A check of the reading of the pressure-sensing device to verify disc integrity shall be performed weekly and recorded in the unit log.

The gas analyzer shall conform to requirements listed in Method 21 of 40 CFR Part 60, Appendix A. The gas analyzer shall be calibrated with methane. In addition, the response factor of the instrument for a specific VOC of interest shall be determined and meet the requirements of Section 8 of Method 21. If a mixture of VOCs is being monitored, the response factor shall be calculated for the average composition of the process fluid. If a response factor less than 10 cannot be achieved using methane, then the instrument may be calibrated with one of the VOC to be measured or any other VOC so long as the instrument has a response factor of less than 10 for each of the VOC to be measured.

Replacements for leaking components shall be re-monitored within 15 days of being placed back into VOC service.

G. Except as may be provided for in the special conditions of this permit, all pump, compressor, and agitator seals shall be monitored with an approved gas analyzer at least quarterly or be equipped with a shaft sealing system that prevents or detects emissions of VOC from the seal. Seal systems designed and operated to prevent emissions or seals equipped with an automatic seal failure detection and alarm system need not be monitored. These seal systems may include (but are not limited to) dual pump seals with barrier fluid at higher pressure than process pressure, seals degassing to vent control systems kept in good working order, or seals equipped with an automatic seal failure detection and alarm system. Submerged pumps or sealless pumps (including, but not limited to, diaphragm, canned, or magnetic-driven pumps) may be used to satisfy the requirements of this condition and need not be monitored.

H. Damaged or leaking valves or connectors found to be emitting VOC in excess of 500 ppmv or found by visual inspection to be leaking (e.g., dripping process fluids) shall be tagged and replaced or repaired. Damaged or leaking pump, compressor, and agitator seals found to be emitting VOC in excess of 2,000 ppmv or found by visual inspection to be leaking (e.g., dripping process fluids) shall be tagged and replaced or repaired. A first attempt to repair the leak must be made within five days. Records of the first attempt to repair shall be maintained.

I. Every reasonable effort shall be made to repair a leaking component, as specified in this paragraph, within 15 days after the leak is found. If the repair of a component would require a unit shutdown that would create more emissions than the repair would eliminate, the repair may be delayed until the next scheduled shutdown. All leaking components which cannot be repaired until a scheduled shutdown shall be identified for such repair by tagging within 15 days of the detection of the leak. A listing of all components that qualify for delay of repair shall be maintained on a delay of repair list. The cumulative daily emissions from all components on the delay of repair list shall be estimated by multiplying by 24 the mass emission rate for each component calculated in accordance with the instructions in 30 TAC § 115.782(c)(1)(B)(i)(II). The calculations of the cumulative daily emissions from all components on the delay of repair list shall be updated within ten days of when the latest leaking component is added to the delay of repair list. When the cumulative daily emission rate of all components on the delay of repair list times the number of days until the next scheduled unit shutdown is equal to or exceeds the total emissions from a unit shutdown as calculated in accordance with 30 TAC § 115.782(c)(1)(B)(i)(I), the TCEQ Regional Manager and any local programs shall be notified and may require early unit shutdown or other appropriate action based on the number and severity of

tagged leaks awaiting shutdown. This notification shall be made within 15 days of making this determination.

J. Records of repairs shall include date of repairs, repair results, justification for delay of repairs, and corrective actions taken for all components. Records of instrument monitoring shall indicate dates and times, test methods, and instrument readings. Records of physical inspections shall be noted in the operator's log or equivalent.

K. Alternative monitoring frequency schedules of 30 TAC §§ 115.352 - 115.359 or National Emission Standards for Organic Hazardous Air Pollutants, 40 CFR Part 63, Subpart H, may be used in lieu of Items F through G of this condition.

L. Compliance with the requirements of this condition does not assure compliance with requirements of 30 TAC Chapter 115, an applicable NSPS, or an applicable NESHAPS and does not constitute approval of alternative standards for these regulations. **(6/10)**

36. Pump and compressor seals shall be monitored for fugitive leakage monthly rather than quarterly as specified by Special Condition Nos. 32 and 34. The leak definitions, recordkeeping, and corrective actions of those conditions still apply to these components.

37. In addition to the weekly physical inspection required by Item E of Special Condition Nos. 32, 33, 34, and 35, all accessible valve connectors in gas or vapor and light liquid service shall be monitored quarterly with an approved gas analyzer in accordance with Items F through J of Special Condition Nos. 32, 33, 34, and 35.

In lieu of the monitoring frequency specified in the above paragraph, connectors may be monitored on a semiannual basis if the percent of connectors leaking for two consecutive quarterly monitoring periods is less than 0.5 percent.

Connectors may be monitored on an annual basis if the percent of connectors leaking for two consecutive semiannual monitoring periods is less than 0.5 percent.

If the percent of connectors leaking for any semiannual or annual monitoring period is 0.5 percent or greater, the facility shall revert to quarterly monitoring until the facility again qualifies for the alternative monitoring schedules previously outlined in the paragraph.

The percent of connectors leaking used in paragraph B shall be determined using the following formula:

$$(Cl + Cs) \times 100/Ct = Cp$$

Where:

Cl = the number of connectors found leaking by the end of the monitoring period, either by Method 21 or sight, sound, and smell.

Cs = the number of connectors for which repair has been delayed and are listed on the facility shutdown log.

Ct = the total number of connectors in the facility subject to the monitoring requirements, as of the last day of the monitoring period, not including nonaccessible and unsafe-to-monitor connectors.

Cp = the percentage of leaking connectors for the monitoring period.

38. Process Piping, Valves, Pumps, and Compressors in H_2S and Hydrogen Fluoride (HF) Service

This condition shall apply to all process streams with greater than 2 weight percent H_2S and all process streams with greater than 0.5 weight percent HF.

A. Audio, olfactory, and visual checks for H_2S leaks within the operating area shall be made once a shift.

B. Immediately, but no later than one hour upon detection of a leak, plant personnel shall take the following actions:

(1) Isolate the leak.

(2) Commence repair or replacement of the leaking component.

(3) If immediate repair is not possible, a leak collection or containment system will be used to prevent or minimize the leak or the facility shall be shutdown in an orderly manner until repair or replacement can be made. Containment can include adjustment of bolts, fittings, packing glands, and pump or compressor seals to contain the leak.

Records shall be maintained of all inspections, leaks noted, repairs, and replacements made. These records shall be maintained at the plant site for a period of five years and shall be made immediately available at the request of TCEQ personnel. **(6/08)**

Compliance Testing

39. The holder of this permit shall perform stack sampling and other testing as required to establish the actual pattern and quantities of air contaminants being emitted into the atmosphere from all heaters and boilers with firing rates greater than 40 MMBtu/hr, Scot Tail Gas Incinerator (EPN 121 or 121a), Sulften Tail Gas Incinerator (EPN 121 or 121a), Caustic Scrubber (EPN 121), Marine Loading VRU (EPN VRU), and Vapor Combustors (EPNs TRUCKCOMB and 124). Sampling shall be performed upstream and downstream of the SMR condensate stripper vent condenser to demonstrate compliance with Special Condition No. 48. The holder of this permit is responsible for providing sampling and testing facilities and conducting the sampling and testing operations at their expense. **(05/06)**

A. The appropriate TCEQ Regional Office in the region where the source is located shall be contacted as soon as testing is scheduled but not less than 45 days prior to sampling to schedule a pretest meeting.

The notice shall include:

(1) Date for pretest meeting.

(2) Date sampling will occur.

(3) Name of firm conducting sampling.

(4) Type of sampling equipment to be used.

(5) Method or procedure to be used in sampling.

The purpose of the pretest meeting is to review the necessary sampling and testing procedures, to provide the proper data forms for recording pertinent data, and to review the format procedures for submitting the test reports.

A written proposed description of any deviation from sampling procedures specified in permit conditions or the TCEQ or EPA sampling procedures shall be made available to the TCEQ prior to the pretest meeting. The TCEQ Regional Director or the TCEQ Austin Compliance Support Division shall approve or disapprove of any deviation from specified sampling procedures.

Requests to waive testing for any pollutant specified in B of this condition shall be submitted to the TCEQ Office of Permitting, Remediation, and Registration, Air Permits Division. Test waivers and alternate or equivalent procedure proposals for NSPS testing which must have the EPA approval shall be submitted to the TCEQ Austin Compliance Support Division.

B. Air contaminants emitted from the heaters and boilers to be tested for include (but are not limited to) nitrogen oxide (NO_X) and carbon monoxide (CO).

Air contaminants emitted from the caustic scrubber to be tested for include (but are not limited to) sulfur dioxide (SO_2), NOx, PM (both front and back-half of the sampling train), sulfuric acid, and CO. Stack testing of the Belco Scrubber (EPN 121) shall be accomplished by temporarily routing the Sulften and Scot Tail gas to EPN 121a. The sulfuric acid mist stack sample shall be performed using both TCEQ Method 24 and EPA Method 8. The lower of the two sampling results may be used to demonstrate compliance.

Air contaminants emitted from the Sulften and Scot tail gas incinerators to be tested for include (but are not limited to) SO_2, NO_X, CO, PM (both front and back half of the sampling train), and total reduced sulfur.

Air contaminants emitted from the vapor combustors to be tested for include (but are not limited to) VOC, NO_X, and CO.

Air contaminants to be tested for the SMR condensate stripper vent condenser include methanol. **(05/06)**

C. Sampling of air contaminants not monitored by continuous emission monitoring system (CEMS) or predictive emission monitoring system (PEMS) under Special Condition No. 40 shall occur as follows:

(1) Within 180 days of the issuance of this permit unless the emission point had been sampled within the last 5 years.

(2) Each emission point shall be sampled within 60 days of achieving maximum operation, not to exceed 180 days after initial operation, if new burners have been installed or if an operational change has been made allowing emissions to increase more than 10 percent greater than determined by the last stack sample.

(3) Each emission point shall be sampled at least every five years.

(4) Each emission point shall be sampled as may be required by the Executive Director of the TCEQ. **(6/08)**

(5) The Belco Scrubber (EPN 121) shall be sampled on an annual basis for PM (both front and back-half of the sampling train) and sulfuric acid. This sampling frequency may be reduced to once every five years after three years of consistent sampling results. Consistent sampling results shall be

defined as three years of annual tests that demonstrate emission rates less than the planned emission rates represented in the application for the July 2004 permit amendment. The planned emission rate used for this evaluation may be reestablished according to the methodologies utilized in the July 2004 permit amendment if the coke burn rate for the heavy oil cracker exceeds the levels represented in that application. The sampling results must be obtained without the need for retests. This sampling shall commence prior to March 15, 2005.

Air contaminants monitored with a CEMS or PEMS as specified under Special Condition No. 40 shall be sampled to support CEMS or PEMS operation as required by that condition.

Requests for additional time to perform sampling shall be submitted to the TCEQ Corpus Christi Regional Office. Additional time to comply with the applicable requirements of 40 CFR Part 60 and 40 CFR Part 61 requires the EPA approval, and requests shall be submitted to the TCEQ Austin Compliance Support Division.

D. The facility shall operate at maximum production rates during stack emission testing. Primary operating parameters that enable determination of production rates shall be monitored and recorded during the stack test. These parameters are to be determined at the pretest meeting. If the plant is unable to operate at maximum rates during testing, then future production rates may be limited to the rates established during testing. Additional stack testing may be required when higher production rates are achieved.

E. One copy of the final sampling report shall be forwarded to the TCEQ within 60 days after sampling is completed. Sampling reports shall comply with the attached conditions of Chapter 14 of the TCEQ Sampling Procedures Manual. The reports shall be distributed as follows:

One copy to the TCEQ Corpus Christi Regional Office. **(PSD) (6/08)**

<u>Continuous Determination of Compliance</u>

40. The holder of this permit shall install, calibrate, and maintain a CEMS to measure and record the in-stack concentration of VOC from the marine VRU; CO, NO_X, and O_2 from the heaters and boilers with firing rates greater than 100 MMBtu/hr; SO_2 and O_2 from the SRU/Sulften Tail Gas Incinerator (exhausts to EPN 121 or 121a); SO_2 and O_2 from the SRU/Scot Tail Gas Incinerator (exhausts to EPN 121 or 121a), the in-stack (EPN 121 or 121a) concentration of NO_X from the caustic scrubber and sulfur recovery system; and CO, O_2, and SO_2 from the Caustic Scrubber (exhausts to EPN 121). The monitoring

system shall meet either the following section of Requirements for CEMS or the section Requirements for PEMS, as applicable.

Requirements for CEMS

A. The CEMS shall meet the design and performance specifications, pass the field tests, and meet the installation requirements and the data analysis and reporting requirements specified in the applicable Performance Specification Nos. 1 through 7, 40 CFR Part 60, Appendix B. If there are no applicable performance specifications in 40 CFR Part 60, Appendix B, contact the TCEQ Austin Compliance Support Division for requirements to be met.

B. The system shall be zeroed and spanned daily and corrective action taken when the 24 hour span drift exceeds two times the amounts specified in 40 CFR Part 60, Appendix B or as specified by the TCEQ if not specified in Appendix B.

Zero and span is not required on weekends and plant holidays if instrument technicians are not normally scheduled on those days, unless the monitor is required by a subpart of NSPS or NESHAPS, in which case zero and span shall be done daily without exception.

Each monitor shall be quality-assured at least quarterly in accordance with 40 CFR Part 60, Appendix F, Procedure 1, § 5.1.2. Cylinder gas audit conducted in all four calendar quarters may be used in lieu of relative accuracy test audits (RATA) for non NSPS sources and for NSPS sources not subject to 40 CFR Part 60, Appendix F.

C. The monitoring data shall be reduced to hourly average concentrations at least once weekly, using a minimum of four equally-spaced data points from each one-hour period. The individual average concentrations shall be reduced to units of the permit allowable emission rate in pounds/hr at least once every week and cumulative tons per year (TPY) on a 12-month rolling average at least once every month.

D. All monitoring data and quality-assurance data shall be maintained by the source for a period of five years and shall be made available to the TCEQ Executive Director or his designated representative upon request. The data from the CEMS may, at the discretion of the TCEQ, be used to determine compliance with the conditions of this permit. **(6/08)**

E. All cylinder gas audit exceedances of ±15 percent accuracy and any CEMS downtime associated with emissions from EPNs 121 and 121a shall be reported to the appropriate TCEQ Regional Director within three days of any downtime, and necessary corrective action shall be taken. If the CEMS downtime for a specific

emission point occurs when emissions are not being routed to that stack, that time period shall not be considered reportable CEMS downtime for the purposes of this special condition. Exceedances at other emission points shall be reported in Semiannual Excess Emission Reports. Supplemental stack concentration measurements may be required at the discretion of the appropriate TCEQ Regional Director.

F. For NSPS sources subject to Appendix F, the appropriate TCEQ Regional Office shall be notified at least 30 days prior to each annual RATA in order to provide them the opportunity to observe the testing.

Requirements for PEMS

A. A PEMS may be used for demonstrating continuous compliance if it can be proven to have the same or better accuracy, precision, reliability, accessibility, and timeliness as that provided by a hardware CEMS. All PEMS shall be subject to the approval of the TCEQ Executive Director. Owners or operators must petition the TCEQ Executive Director for approval to use PEMS. The petition must include results of tests conducted beforehand to demonstrate equivalent accuracy and precision of PEMS to that of hardware CEMS. Demonstrating equivalency of PEMS to CEMS shall be met by instantaneously comparing data collected by PEMS with that collected by a certified hardware CEMS or an EPA reference method. For a PEMS replacing a CEMS, both systems shall remain in place for at least an operating quarter collecting valid information before the CEMS is removed.

B. For any unit at which the PEMS is installed, PEMS initial certification by the TCEQ shall occur while the unit is firing its primary fuel. The owner or operator shall:

(1) Conduct relative accuracy testing for NO_X, O_2, or carbon dioxide (CO_2) and CO per 40 CFR Part 60, Appendix B, Performance Specifications 2, 3, and 4, respectively, at low, medium, and high levels of the most significant operating parameter affecting NO_X emissions.

(2) Conduct statistical test analysis at low, medium, and high levels of the most significant operating parameter affecting NO_X emissions. A minimum of 30 successive paired data points which are either 15-minute averages, 20 minute averages, or hourly averages must be collected at each tested level before a reliable statistical test can be performed.

Data collection must be continuous at all times except when calibration of the reference method must be conducted for the purpose of collecting data for RATA.

The following three tests must be conducted to demonstrate precision:

(a) A T-test for bias per Appendix A, 40 CFR Part 75, § 7.6. The test shall be conducted using all paired data points collected at all three tested levels.

(b) An F-test per 40 CFR § 75.41(c)(1). The F-test must be conducted separately at the three tested levels.

(c) A correlation analysis per 40 CFR § 75.41(c)(2). Calculation of the correlation coefficient (Equation 27) shall be performed using all paired data points collected at all three tested levels.

(3) For either NO_X or CO and for the purpose of conducting an F-test, if the standard deviation (SD) of the reference method is less than either 3 percent of the span or 5 ppm, use a reference method SD of the greater of 5 ppm or 3 percent of span.

(4) For diluent CO_2 or O_2 and for the purpose of conducting an F-test, if the SD of the reference method is less than 3 percent of span, use a reference method SD of 3 percent of span.

(5) For either NO_X or CO and at any one tested level, if the mean value of the reference method is less than either 10 ppm or 5 percent of the standard, all statistical tests are waived for that emission parameter at that specific tested level.

(6) For either O_2 or CO_2 and at any one tested level, if the mean value of the reference method is less than 3 percent of span, all the statistical tests are waived for that diluent parameter at that specific tested level.

C. The monitoring data shall be reduced to hourly average concentrations at least once every day, using a minimum of four equally-spaced data points from each one hour period. The individual average concentrations shall be reduced to units of the permit allowable emission rate in lbs/hr at least once every day and cumulative TPY on a 12 month rolling average at least once every month.

D. All monitoring data and quality-assurance data shall be maintained by the permit holder for a period of five years and shall be made available to the TCEQ Executive Director or designated representative upon request. **(6/08)**

E. Any PEMS downtime shall be reported to the appropriate TCEQ Regional Director within three days of any downtime, and necessary corrective action shall be taken. Owners or operators shall demonstrate that all missing data can be

accounted for in accordance with the applicable missing data procedures of 40 CFR Part 75, Subpart D. Supplemental stack concentration measurements may be required at the discretion of the appropriate TCEQ Regional Director.

F. The appropriate TCEQ Regional Office shall be notified at least 30 days prior to each annual RATA in order to provide them the opportunity to observe the testing.

G. The owner or operator shall perform daily sensor validation. The owner or operator shall develop and implement plans that will ensure proper functioning of the monitoring systems, ensure proper accuracy and calibration of all operational parameters that affect emissions and serve as input to the predictive monitoring system, and ensure continuous operation within the certified operating range.

H. In accordance with the procedure of § 2.3.1, Appendix B of 40 CFR Part 60, a RATA must be performed every six months for each unit while firing its primary fuel. A RATA may be performed annually if the relative accuracy of the previous audit is 7.5 percent or less.

I. For each of the three successive quarters following the quarter in which initial certification was conducted, RATA and statistical testing must be conducted for at least one unit in a category of units in accordance with the procedures outlined for initial certification under Section B.

J. Any RATA exceeding 20 percent or statistical test exceeding the applicable standard shall be reported to the appropriate TCEQ Regional Director, and necessary corrective action shall be taken.

K. When an alternative fuel is fired in a unit, PEMS must be re-certified in accordance with the certification procedures outlined for initial certification under Section B. Owners or operators may justify to the satisfaction of the TCEQ Executive Director that slight changes in fuel composition do not constitute an alternative fuel. No additional recertification procedures are required if the unit meets the current monitoring requirements when switching back to the normal fuel from an alternate fuel.

L. The system is required to provide valid emission predictions for at least 95 percent of the time that the unit being monitored is operated. The following rules for tuning without recertification shall be followed:

(1) The model did not change fundamentally.
(2) The model continues to operate within the initially certified operating ranges.

Otherwise, the system must be recertified. Any tuning must be documented, and the records must be made available during any future inspection.

M. All owners or operators shall develop a quality-assurance plan or manual that insures continuous and reliable performance of the PEMS. As part of the plan, owners or operators shall recommend a frequency for calibrating each sensor whose readout serves as an input to the model. All sensors, at a minimum, shall be calibrated as often as recommended by the manufacturer. **(PSD) (9/04)**

41. Pollutant concentrations at the outlet from the Caustic Scrubber (exhausts to EPN 121) shall not exceed the following values at dry conditions, 0 percent O_2:

Pollutant	Maximum Allowable	Averaging Period
SO_2	50 ppm	1.0 hour
SO_2	25 ppm	Annual
CO	500 ppm	1.0 hour
NO_X	150 ppm	1.0 hour

Pollutant concentrations at the outlet from the SCOT Stack (EPN 121a) shall not exceed the following values at dry conditions, 0 percent O2:

Pollutant	Maximum Allowable	Averaging Period
SO_2	250 ppm	1.0 hour
CO	332 ppm	1.0 hour
NO_X	50 ppm	1.0 hour **(PSD) (11/05)**

42. The continuous monitoring data will be used to determine violations of the limitations in this permit. For purposes of enforcement, the following averaging periods shall be utilized unless otherwise specified in this permit with respect to a specific emission point and pollutant:

Pollutant	Averaging Period
SO_2	1.0 hour
CO	1.0 hour
H_2S	1.0 hour
Opacity	6.0 minutes
NO_X	1.0 hour **(PSD) (11/05)**

<u>Emission Cap Compliance Recordkeeping</u>

43. Recordkeeping programs for those facilities authorized by the permit shall be established and maintained such that the ability to demonstrate compliance with all authorized

emission caps and individual emission rate limits (short-term and annual) is ensured. Records of all compliance testing, CEMS/PEMS results, and process parameters necessary to demonstrate compliance with the emission rate caps shall be maintained on-site for a period of five years. **(6/08)**

Emissions calculations for verifying compliance with the emission caps shall be performed at least once every month to demonstrate compliance with the annual rolling average requirement. The holder of this permit shall maintain all records necessary to demonstrate compliance with the short-term (lb/hr) and annual TPY emissions cap and provide such demonstration of compliance to the TCEQ Corpus Christi Regional Office upon request. The short-term and annual benzene and VOC emission limits that are reduced from one year to the next year become effective in December of the year when the reduced pound an hour and TPY emission limits are identified to demonstrate compliance with 30 TAC § 116.115(b)(2)(G).

The emissions shall be determined using the following techniques:

Fugitive	Component counts using the emission factors and method specified in the permit application.
Cooling Towers	Measured strippable VOC concentration as specified in Special Condition No. 31 and the cooling tower circulation rate.
Tanks	As specified in Special Condition No. 29.
Heaters/Boilers	If a CEMS or PEMS is installed, as specified in Special Condition No. 40. If stack tested per Special Condition No. 39, using the most recent stack test result and recorded firing rate for the period. If no sampling is required, using the emission factor in the flexible permit application and the recorded firing rate for the period.
Loading	Fugitive emissions from loading operations shall be calculated using: (a) AP 42 loading equation listed in Chapter 5.2 and (b) the TCEQ publication titled "Technical Guidance for Chemical Sources Loading Operations." Emissions from control devices shall be determined using the emission factor (in mg/l) determined through testing and the volume loaded. The manufacturer's guaranteed emission factor may be used if the most recent stack testing has verified that factor. **(11/05)**
SRU/HOC	If a CEMS or PEMS is installed, as specified in Special Condition No. 40.
Scrubber	If stack tested per Special Condition No. 39, using the most recent stack test result and recorded operating rate for the period. If no

	sampling is required, using the emission factor in the flexible permit application and the average value of the appropriate operating parameter for the period.
Diesel Engines	Emissions calculated based on hours of operation and emission factors listed on Table D-1 in the confidential section of the permit amendment application dated November 16, 2004.

These and all other records required by any previous condition of this permit shall be made available to the TCEQ Executive Director or his representative upon request. **(PSD) (11/05)**

Permit References

44. The permit holder shall maintain a copy of the effective permit at the site together with complete copies of all confidential documents that are referenced in the above permit conditions as attachments. The permit and attachments shall be made available to TCEQ personnel at the site upon request. **(PSD)**

HF Control Measures

45. The HF detection paint shall be used on all potential fugitive sources and possible leak sites. Locations with HF detection paint shall be inspected every shift during the audio, visual, and olfactory checks required by Special Condition No. 39. If leaks are detected, corrective action shall be taken immediately as described in Special Condition No. 39. If there is a problem with HF sensitive paint availability, the holder of this permit shall notify the TCEQ Corpus Christi Regional Office and request additional time for painting or request alternate leak detection methods pending availability of the HF sensitive paint. **(12/10)**

46. In the event of an HF release which may have the potential for off-site impacts, the holder of this permit shall implement the procedures outlined in the emergency response plans.

47. There shall be no overhead work in the HF process unit where equipment is being lifted over unprotected vessels or lines without first completing a safe work checklist in accordance with Occupational Safety and Health Administration Process Safety Management rules. The safe work checklist shall be used to ensure that every effort is made to minimize the potential for an accident that would result in loss of integrity of HF-containing equipment.

The holder of this permit is required to notify the TCEQ Corpus Christi Regional Office no less than eight hours prior to conducting work over unprotected vessels or lines containing more than 5 percent by weight HF.

Miscellaneous

48. The SMR stripper vent condenser shall collect 98 percent of the methanol in the stripper vent on an hourly averaging period. The stripper exhaust gas temperature shall be maintained below that maintained during the most recent stack sample following the initial stack test.

    The condenser exhaust gas temperature shall be continuously monitored and recorded when the stripper is operating. The temperature measurement device shall reduce the temperature readings to an averaging period of six minutes or less and record it at that frequency. The temperature measurement device shall be installed, calibrated, and maintained according to accepted practice and the manufacturer's specifications. The device shall have an accuracy of the greater of ±0.75 percent of the temperature being measured expressed in degrees Celsius or ±2.5˚C. **(05/06)**

49. The permit holder shall submit an alteration request upon shutdown of the East Plant HF Alkylation Unit and completion of hydrogen fluoride transfer and expansion for the West Plant HF Alkylation Unit. The purpose of this alteration request shall be to remove the East HF Alkylation Unit, any associated allowable emissions and special conditions, and update the emissions cap as necessary for this unit which is authorized under Permit Number 2937. The permit holder shall submit an alteration to modify Permit Number 38754 after the transfer of HF is completed to delete the initial HF emissions rates for EPN 31F from the permit. **(12/10)**

50. Per US EPA Consent Decree SA-05-CA-0569, after December 31, 2008 the maximum allowable emission limit of NO_X from the West Plant Heavy Oil Cracker (HOC)(EPN 121) shall not exceed 37 ppmv (dry, 0 percent oxygen basis) on a 365-day rolling average and shall not exceed 74 ppmv (dry, 0 percent oxygen basis) on a 7-day rolling average. **(03/12)**

51. Flares: BUP Flare, Main Flare and Ground Flare shall be operated in accordance with the New Source Performance Standards for Petroleum Refineries, 40 CFR Part 60 Subpart J as specified in their Consent Decree SA-05-CA-0569 with the EPA. **(6/12)**

Maintenance, Startup, and Shutdown (MSS)

52. Planned startup and shutdown emissions due to the activities identified in Special Condition No. 53 are authorized from facilities and emission points identified in

Attachment 1 and Boiler 30-B-01 (EPN: 133) in Permit 1507A, Boiler 30-B-03 (EPN: 163) in Permit 20740, and the Xylene Splitter Reboiler Heater 49-H-91 (EPN: 49-H-91) in Permit 20992 provided the facility and emissions are compliant with the routine emission caps and Special Condition No. 63 of this permit. **(3/10)**

53. This permit authorizes the emissions for the planned MSS activities summarized in the MSS Activity Summary (Attachment 4) attached to this permit. This permit also authorizes emissions from the following temporary facilities used to support planned MSS activities at permanent site facilities: frac tanks, containers, vacuum trucks, facilities used for painting or abrasive blasting, portable control devices identified in Special Condition 64, and controlled recovery systems. Emissions from temporary facilities are authorized provided the temporary facility (a) does not remain on the plant site for more than 12 consecutive months, (b) is used solely to support planned MSS activities at the permanent site facilities listed in Attachment 1, and (c) does not operate as a replacement for an existing authorized facility.

Attachment 2 identifies the inherently low emitting MSS activities that may be performed at the refinery. Emissions from activities identified in Attachment 2 shall be considered to be equal to the potential to emit represented in the permit application. The estimated emissions from the activities listed in Attachment 2 must be revalidated annually. This revalidation shall consist of the estimated emissions for each type of activity and the basis for that emission estimate.

Routine maintenance activities, as identified in Attachment 3 may be tracked through the work orders or equivalent. Emissions from activities identified in Attachment 3 shall be calculated using the number of work orders or equivalent that month and the emissions associated with that activity identified in the permit application.

The performance of each planned MSS activity not identified in Attachments 2 or 3 and the emissions associated with it shall be recorded and include at least the following information:

A. the process unit at which emissions from the MSS activity occurred, including the emission point number and common name of the process unit;

B. the type of planned MSS activity and the reason for the planned activity;

C. the common name or the facility identification number, if applicable, of the facilities at which the MSS activity and emissions occurred;

D. the date on which the MSS activity occurred;

E. the estimated quantity of each air contaminant, or mixture of air contaminants, emitted with the data and methods used to determine it. The emissions shall be

estimated using the methods identified in the permit application, consistent with good engineering practice.

All MSS emissions shall be summed monthly and the rolling 12-month emissions shall be updated on a monthly basis. **(3/10)**

54. Process units and facilities, with the exception of those identified in Special Condition Nos. 57 (related to Floating Roof Tanks), 58(related to Fixed Roof Tanks), 60 (related to frac or temporary tanks), and activities listed in Attachment 2, shall operate in accordance with the following requirements during MSS.

A. The process equipment shall be depressurized to a control device or a controlled recovery system prior to venting to atmosphere, degassing, or draining liquid. Equipment that only contains material that is liquid with VOC true vapor pressure (TVP) less than 0.50 psi at the normal process temperature and 95°F may be opened to atmosphere and drained in accordance with paragraph C of this special condition without depressuring or degassing to a control device. The vapor pressure at 95°F may be used if the actual temperature of the liquid is verified to be less than 95°F and the temperature is recorded.

B. If mixed phase materials must be removed from process equipment, the cleared material shall be routed to a knockout drum or equivalent to allow for managed initial phase separation. If the VOC TVP is greater than 0.50 psi at either the normal process temperature or 95°F, any vents in the system must be routed to a control device or a controlled recovery system. The vapor pressure at 95°F may be used if the actual temperature of the liquid is verified to be less than 95°F and the temperature is recorded. Control must remain in place until degassing has been completed or the system is no longer vented to atmosphere.

C. All liquids from process equipment shall be removed to the maximum extent practical prior to opening equipment to commence degassing and/or maintenance. Liquids with a VOC partial pressure greater than or equal to 0.044 psia at 68°F shall be drained into a closed vessel unless prevented by the physical configuration of the equipment. If it is necessary to drain liquid into an open pan or sump, the liquid shall be covered or transferred to a covered vessel within one hour of being drained. After draining is complete, empty open pans may remain in use for housekeeping reasons to collect incidental drips.

D. If the VOC TVP is greater than 0.50 psi at the normal process temperature or 95°F, facilities shall be degassed using good engineering practice to ensure air contaminants are removed from the system through the control device or controlled recovery system to the extent allowed by process equipment or storage vessel design. The vapor pressure at 95°F may be used if the actual temperature of the liquid is verified to be less than 95°F and the temperature is recorded.

The following requirements do not apply to fugitive components, pumps, compressors.

(1) For MSS activities identified in Attachment 3, the following option may be used in lieu of (2) below. The facilities being prepared for maintenance shall not be vented directly to atmosphere, except as necessary to verify an acceptable VOC concentration and establish isolation of the work area, until the VOC concentration has been verified to be less than 10 percent of the lower explosive limit (LEL) per the site safety procedures.

(2) The locations and/or identifiers where the purge gas or steam enters the process equipment or storage vessel and the exit points for the exhaust gases shall be recorded (PFD's, P&ID's, or Turnaround and Inspection [T&I] plans may be used to demonstrate compliance with the requirement). Documented refinery procedures used to deinventory equipment to a control device for safety purposes (i.e., hot work or vessel entry procedures) that achieve at least the same level of purging may be used in lieu of the above. If the process equipment is purged with a gas, purge gas must have passed through the control device or controlled recovery system for a sufficient period of time in accordance with the applicable site operating procedures before the vent stream may be sampled to verify acceptable VOC concentration prior to uncontrolled venting. The VOC sampling and analysis shall be performed using an instrument meeting the requirements of Special Condition 55. The sampling point shall be upstream of the inlet to the control device or controlled recovery system. The sample ports and the collection system must be designed and operated such that there is no air leakage into the sample probe or the collection system downstream of the process equipment or vessel being purged. The facilities shall be degassed to a control device or controlled recovery system until the VOC concentration is less than or equal to 10,000 ppmv or 10 percent of the LEL.

(3) Alternatively, the process equipment may filled with a liquid with a VOC vapor pressure less than 0.147 psi while venting to control. If it can be verified that the liquid filled the entire process equipment or vessel, no sampling is necessary. If not, the VOC concentration shall be verified to be less than 10,000 ppmv or 10 percent of the LEL using an instrument meeting the requirements of Special Condition 55 while purging to control immediately after draining the liquid from the system. The locations and/or identifiers where the liquid enters the process equipment or storage vessel and the exit points for the exhaust gases shall be recorded (PFDs, P&IDs, or T&I plans may be used to demonstrate compliance with the requirement).

E. Equipment containing materials with VOC TVP greater than 0.50 psi may be vented directly to atmosphere if all the following criteria are met:

(1) It is not technically practicable to depressurize or degas, as applicable, into the process.

(2) There is not an available connection to a plant control system (flare).

(3) There is no more than 50 lb of air contaminants to be vented to atmosphere during a each shutdown or startup of a piece of equipment, as applicable.

All instances of venting directly to atmosphere per Special Condition 54.D must be documented when occurring as part of any MSS activity. The emissions associated with venting without control must be included in the work order, shift logs, or equivalent for those planned MSS activities identified in Attachment 3. **(3/10)**

55. Air contaminant concentration shall be measured using an instrument/detector meeting one set of requirements specified below.

A. The VOC concentration shall be measured using an instrument meeting all the requirements specified in EPA Method 21 (40 CFR Part 60, Appendix A) with the following exceptions:

(1) The instrument shall be calibrated within 24 hours of use with a calibration gas. The calibration gas used and its concentration, and the vapor to be sampled and its approximate response factor (RF), shall be recorded. If the RF of the VOC (or mixture of VOCs) to be monitored is greater than 2.0, the VOC concentration shall be determined as follows:

VOC Concentration = Concentration as read from the instrument*RF

(2) Sampling shall be performed as directed by this permit in lieu of section 8.3 of Method 21. During sampling, data recording shall not begin until after two times the instrument response time. The date and time shall be recorded, and VOC concentration shall be monitored for at least 5 minutes and the greatest VOC concentration recorded. This VOC concentration shall not exceed the specified VOC concentration limit prior to uncontrolled venting.

(3) If a TVA-1000 series FID analyzer calibrated with methane is used to determine the VOC concentration, a measured concentration of 34,000 ppmv may be considered equivalent to 10,000 ppmv as VOC.

B. Colorimetric gas detector tubes may be used to determine air contaminant concentrations if they are used in accordance with the following requirements.

(1) The air contaminant concentration measured is less than 80 percent of the range of the tube. If the maximum range of the tube is greater than the release concentration defined in (3), the concentration measured is at least 20 percent of the maximum range of the tube.

(2) The tube is used in accordance with the manufacturer's guidelines.

(3) At least 2 samples taken at least 5 minutes apart must satisfy the following prior to uncontrolled venting:

measured contaminant concentration (ppmv) < release concentration.

Where the release concentration is:

10,000*mole fraction of the total air contaminants present that can be detected by the tube.

The mole fraction may be estimated based on process knowledge. The release concentration and basis for its determination shall be recorded.

Records shall be maintained of the tube type, range, measured concentrations, and time the samples were taken.

C. Lower explosive limit measured with a lower explosive limit detector.

(1) The detector shall be calibrated monthly with a certified pentane gas standard at 25 percent of the lower explosive limit (LEL) for pentane. Records of the calibration date/time and calibration result (pass/fail) shall be maintained.

(2) A daily functionality test shall be performed on each detector using the same certified gas standard used for calibration. The LEL monitor shall read no lower than 90 percent of the calibration gas certified value. Records, including the date/time and test results, shall be maintained.

(3) A certified methane gas standard equivalent to 25 percent of the LEL for pentane may be used for calibration and functionality tests provided that the LEL response is within 95 percent of that for pentane.

D. For measuring benzene breakthrough on Carbon Adsorption Systems in Special Condition 64.A.(4), a portable gas chromatograph using a flame ionization detector or photo ionization detector may be used. Alternatively a photo-ionization detector equipped with a benzene separation tube consistent with manufacturer requirements may be used. The monitor shall have the sensitivity and specificity to quantify low level benzene concentrations. The monitor device shall be calibrated within 24 hours of use with a certified calibration gas containing ~5 ppm benzene. Records of the calibration date/time and calibration result shall be maintained. **(3/10)**

56. If the removal of a component for repair or replacement results in an open ended line or valve, the open ended line is exempt from any New Source Review (NSR) permit condition requirement to install a cap, blind flange, plug, or second valve for 72 hours. If the repair or replacement is not completed within 72 hours, the permit holder must complete either of the following actions within that time period;

A. a cap, blind flange, plug, or second valve must be installed on the line or valve, or demonstrate that the line, valve, component, etc, has been double blocked from the process; or

B. the permit holder shall verify that there is no leakage from the open-ended line or valve. The open-ended line or valve shall be monitored on a weekly basis in accordance with the applicable NSR permit condition for fugitive emission monitoring except that a leak is defined as any VOC reading greater than background. Leaks must be repaired within 24 hours or a cap, blind flange, plug, or second valve must be installed on the line or valve. The results of this weekly check and any corrective actions taken shall be recorded. **(3/10)**

57. This permit authorizes emissions from the storage tanks identified in Attachment 1 during planned floating roof landings. Tank floating roofs may only be landed for changes of tank service or tank inspection/maintenance as identified in the permit application, except when the VOC vapors below the floating roof are routed to a control device or a controlled recovery system while the roof is landed. Tank change of service includes landings to accommodate seasonal RVP spec changes and landings to correct off-spec material that cannot be blended into finished product tanks. Tank roof landings include all operations when the tank floating roof is on its supporting legs. These emissions are subject to the maximum allowable emission rates indicated on the MAERT. The following requirements apply to tank roof landings. **(3/10)**

A. The tank liquid level shall be continuously lowered after the tank floating roof initially lands on its supporting legs until the tank has been drained to the maximum extent practicable without entering the tank. Liquid level may be maintained steady for a period of up to two hours if necessary to allow for valve lineups and pump changes necessary to drain the tank. This requirement does not apply where the vapor under a floating roof is routed to control during this process.

B. If the VOC TVP of the liquid previously stored in the tank is greater than 0.50 psi at 95°F tank refilling or degassing of the vapor space under the landed floating roof must begin within 24 hours after the tank has been drained. Floating roof tanks with liquid capacities less than 100,000 gallons may be degassed without control if the VOC TVP of the standing liquid in the tank has been reduced to less than 0.02 psia prior to ventilating the tank. Controlled degassing of the vapor space under landed roofs shall be completed as follows:

(1) Any gas or vapor removed from the vapor space under the floating roof must be routed to a control device or a controlled recovery system and controlled degassing must be maintained until the VOC concentration is less than 10,000 ppmv or 10 percent of the LEL. The locations and identifiers of vents other than permanent roof fittings and seals, control device or controlled recovery system, and controlled exhaust stream shall be recorded. There shall be no other gas/vapor flow out of the vapor space under the floating roof when degassing to the control device or controlled recovery system.

(2) The vapor space under the floating roof shall be vented using good engineering practice to ensure air contaminants are flushed out of the tank through the control device or controlled recovery system to the extent allowed by the storage tank design.

(3) A volume equivalent to twice the volume of the vapor space under the floating roof must have passed through the control device or into a controlled recovery system, before the vent stream may be sampled to verify acceptable VOC concentration. The volume measurement shall not include any make-up air introduced into the control device or recovery system. The VOC sampling and analysis shall be performed as specified in Special Condition 55.

(4) The sampling point shall be upstream of the inlet to the control device or controlled recovery system. The sample ports and the collection system must be designed and operated such that there is no air leakage into the sample probe or the collection system downstream of the process equipment or vessel being purged.

(5) If ventilation is to be maintained with emission control, the VOC concentration shall be recorded once an hour.

(6) Degassing must be performed every 24 hours unless there is no standing liquid in the tank or the VOC TVP of the remaining liquid in the tank is less than 0.15 psia.

C. The tank shall not be opened except as necessary to set up for degassing and cleaning, or ventilated without control, until either all standing liquid has been removed from the tank or the liquid in the tank has a VOC TVP less than 0.02 psia. These criteria may be demonstrated in any one of the following ways.

(1) Low VOC TVP liquid that is soluble with the liquid previously stored may be added to the tank to lower the VOC TVP of the liquid mixture remaining in the tank to less than 0.02 psia. This liquid shall be added during tank degassing if practicable. The estimated volume of liquid remaining in the drained tank and the volume and type of liquid added shall be recorded. The liquid VOC TVP may be estimated based on this information and engineering calculations.

(2) If water is added or sprayed into the tank to remove standing VOC, one of the following must be demonstrated:

(a) Take a representative sample of the liquid remaining in the tank and verify no visible sheen using the static sheen test from 40 CFR Part 435 Subpart A Appendix 1.

(b) Take a representative sample of the liquid remaining in the tank and verify hexane soluble VOC concentration is less than 1000 ppmw using EPA method 1664 (may also use 8260B or 5030 with 8015 from SW-846).

(c) Stop ventilation and close the tank for at least 24 hours. When the tank manway is opened after this period, verify VOC concentration is less than 1000 ppmv through the procedure in MSS Special Condition 55.

(3) No standing liquid verified through visual inspection.

The permit holder shall maintain records to document the method used to release the tank.

D. Tanks shall be refilled as rapidly as practicable until the roof is off its legs unless the vapor space is routed to control during refilling except as required by Special Condition 72.

E. The occurrence of each roof landing and the associated emissions shall be recorded and the rolling 12-month tank roof landing emissions shall be updated on a monthly basis. These records shall include at least the following information:

(1) the identification of the tank and emission point number, and any control devices or recovery systems used to reduce emissions;

(2) the reason for the tank roof landing;

(3) for the purpose of estimating emissions, the date and time of each of the following events:

(a) the roof was initially landed,

(b) all liquid was pumped from the tank to the extent practical,

(c) start and completion of controlled degassing, and total volumetric flow,

(d) all standing liquid was removed from the tank or any transfers of low VOC TVP liquid to or from the tank including volumes and vapor pressures to reduce tank liquid VOC TVP to <0.02 psi,

(e) if there is liquid in the tank, VOC TVP of liquid, start and completion of uncontrolled degassing, and total volumetric flow,

(f) refilling commenced, liquid filling the tank, and the volume necessary to float the roof; and

(g) tank roof off supporting legs, floating on liquid;

(4) the estimated quantity of each air contaminant, or mixture of air contaminants, emitted between events (c) and (g) with the data and methods used to determine it. The emissions associated with roof landing activities shall be calculated using the methods described in Section 7.1.3.2 of AP-42 “Compilation of Air Pollution Emission Factors, Chapter 7 - Storage of Organic Liquids” dated November 2006 and the permit application. **(3/10)**

58. Fixed-roof storage tanks shall not be ventilated without control, until either all standing liquid has been removed from the tank or the liquid in the tank has a VOC TVP less than 0.02 psia. This shall be verified and documented through one of the criteria identified in MSS Special Condition 57.C. Storage tanks manways may be opened without emission controls when there is standing liquid with a VOC TVP greater than 0.02 psia as necessary to set up for degassing and cleaning. One manway may be opened to provide access to the tank when necessary to allow access to remove or de-volatilize the remaining liquid. The emission control system shall meet the requirements of Special Condition 57.B.(1) through 57.B.(5) and records maintained per Special Condition 57.E.(3)c through 57.E.(3)e, and 57.E.(4). Low vapor pressure liquid may be added to and removed from the tank as necessary to lower the vapor pressure of the liquid mixture remaining in the tank to less than 0.02 psia. **(3/10)**

59. The following requirements apply to vacuum and air mover truck operations at this site:

A. Vacuum pumps and blowers shall not be operated on trucks containing or vacuuming liquids with VOC TVP greater than 0.50 psi at 95F unless the vacuum/blower exhaust is routed to a control device or a controlled recovery system.

B. Equip fill line intake with a “duckbill” or equivalent attachment if the hose end cannot be submerged in the liquid being collected.

C. A daily record containing the information identified below is required for each vacuum truck in operation at the site each day.

(1) Prior to initial use, identify any liquid in the truck. Record the liquid level and document that the VOC TVP is less than 0.50 psi if the vacuum exhaust is not routed to a control device or a controlled recovery system. After each liquid transfer, identify the liquid transferred and document that the VOC TVP is less than 0.50 psi if the vacuum exhaust is not routed to a control device or a controlled recovery system.

(2) For each liquid transfer made with the vacuum operating, record the duration of any periods when air may have been entrained with the liquid transfer. The reason for operating in this manner and whether a “duckbill” or equivalent was used shall be recorded. Short, incidental periods, such as those necessary to walk from the truck to the fill line intake, do not need to be documented.

(3) If the vacuum truck exhaust is controlled with a control device other than an engine or oxidizer, VOC exhaust concentration upon commencing each transfer, at the end of each transfer, and as required by Special Condition

65, measured using an instrument meeting the requirements of MSS Special Condition 55.

(4) The volume in the vacuum truck at the end of the day, or the volume unloaded, as applicable.

D. The permit holder shall determine the vacuum truck emissions each month using the daily vacuum truck records and the calculation methods utilized in the permit application. If records of the volume of liquid transferred for each pick-up are not maintained, the emissions shall be determined using the physical properties of the liquid vacuumed with the greatest potential emissions. Rolling 12 month vacuum truck emissions shall also be determined on a monthly basis.

E. If the VOC TVP of all the liquids vacuumed into the truck is less than 0.10 psi, this shall be recorded when the truck is unloaded or leaves the plant site and the emissions may be estimated as the maximum potential to emit for a truck in that service as documented in the permit application. The recordkeeping requirements in Special Condition 59.A through 59.D do not apply. **(3/10)**

60. The following requirements apply to frac, or temporary, tanks and vessels used in support of MSS activities.

A. Except for labels, logos, etc. not to exceed 15 percent of the tank/vessel total surface area, the exterior surfaces of these tanks/vessels that are exposed to the sun shall be white or aluminum effective May 1, 2013. This requirement does not apply to tanks/vessels that only vent to atmosphere when being filled.

B. These tanks/vessels must be covered and equipped with fill pipes that discharge within 6 inches of the tank/vessel bottom.

C. These requirements do not apply to vessels storing less than 25 barrels of liquid that are closed such that the vessel does not vent to atmosphere.

D. The permit holder shall maintain an emissions record which includes calculated emissions of VOC from all frac tanks during the previous calendar month and the past consecutive 12 month period. The record shall include tank identification number, dates put into and removed from service, control method used, tank capacity and volume of liquid stored in gallons, name of the material stored, VOC molecular weight, and VOC TVP at the estimated monthly average material temperature in psia. Filling emissions for tanks shall be calculated using the TCEQ publication titled “Technical Guidance Package for Chemical Sources - Loading Operations” and standing emissions determined using: the TCEQ publication titled “Technical Guidance Package for Chemical Sources Storage Tanks.”

E. If the tank/vessel is used to store liquid with VOC TVP less than 0.10 psi at 95F, records may be limited to the days the tank is in service and the liquid stored. Emissions may be estimated based upon the potential to emit as identified in the permit application. **(3/10)**

61. The term "true vapor pressure (TVP)" is used in lieu of the term "partial pressure" in this permit. **(3/10)**

62. The MSS activities represented in the permit application may be authorized under permit by rule only if the procedures, emission controls, monitoring, and recordkeeping are the same as those required by this permit. **(3/10)**

63. All permanent facilities must comply with all operating requirements, limits, and representations in the permits identified in Attachment 1 during planned startup and shutdown unless alternate requirements and limits are identified in this permit. Alternate requirements for emissions from routine emission points are identified below:

A. Heaters, boilers, and furnaces are exempt from NO_X and CO operating requirements identified in other special conditions this permit during planned startup and shutdown if the following criteria are satisfied.

(1) The routine maximum allowable emission caps are not exceeded.

(2) The startup period does not exceed 8 hours in duration and the firing rate does not exceed 75 percent of the design firing rate. The time it takes to complete the shutdown does not exceed 4 hours.

(3) Control devices are started and operating properly when venting a waste gas stream.

B. The limits identified below apply to the operations of the specified facilities during startup and shutdown. All other routine operating limitations apply during planned startup and shutdown.

(1) The HOC startup period shall not exceed 50 hours and the hourly average CO concentration during this period shall not exceed 1200 ppmvd corrected to 0 percent oxygen. All HOC emissions during startup are in the MSS emission caps.

(2) The sulfur recovery requirements and SRU tail gas incinerator sulfur dioxide concentration limits in Special Conditions 23 and 41 do not apply during SRU startup. Operation in the hot standby mode shall be minimized. The SRU tailgas incinerator shall be operated in accordance

with Special Condition 25 during this period. A SRU incinerator shall not operate in this mode for more than 72 hours in any rolling 12 month period.

C. A record shall be maintained indicating that the start and end times for each of the activities identified above occur and documentation that the requirements for each have been satisfied. **(3/10)**

64. Control devices required by this permit for emissions from planned MSS activities are limited to those types identified in this condition. Control devices shall be operated with no visible emissions except periods not to exceed a total of five minutes during any two consecutive hours. Each device used must meet all the requirements identified for that type of control device.

Controlled recovery systems identified in this permit shall be directed to an operating refinery process or to a collection system that is vented through a control device meeting the requirements of this permit condition.

A. Carbon Adsorption System (CAS).

(1) The CAS shall consist of 2 carbon canisters in series with adequate carbon supply for the emission control operation.

(2) The CAS shall be sampled downstream on the first can and the concentration recorded at least once every hour of CAS run time to determine breakthrough of the VOC. The sampling frequency may be extended using either of the following methods:

(a) The CAS systems equipped with an upstream liquid scrubber may be sampled once every 12 hours of CAS run time to determine breakthrough.

(b) Sampling frequency may be extended to up to 30 percent of the minimum potential saturation time for a new can of carbon. The permit holder shall maintain records including the calculations performed to determine the minimum saturation time.

(c) The carbon sampling frequency may be extended to longer periods based on previous experience with carbon control of a MSS waste gas stream. The past experience must be with the same VOC, type of facility, and MSS activity. The basis for the sampling frequency shall be recorded. If breakthrough is monitored on the initial sample of the upstream can when the polishing can is put in place, a permit deviation shall be recorded.

(3) The method of VOC sampling and analysis shall be by detector meeting the requirements of Special Condition 55.

(4) Breakthrough is defined as the highest measured VOC or benzene concentration at or exceeding 100 ppmv or 5 ppmv, respectively, above background. When the condition of breakthrough of VOC from the initial saturation canister occurs, the waste gas flow shall be switched to the second canister and a fresh canister shall be placed as the new final polishing canister within twenty-four hours. In lieu of replacing canisters, the flow of waste gas may be discontinued until the canisters are switched. Sufficient new activated carbon canisters shall be available to replace spent carbon canisters such that replacements can be done in the above specified time frame.

(5) Records of CAS monitoring shall include the following:

(a) Sample time and date.
(b) Monitoring results (ppmv).
(c) Canister replacement log.

(6) Single canister systems are allowed if the time the carbon canister is in service is limited to no more than 30 percent of the minimum potential saturation time. The permit holder shall maintain records for these systems, including the calculations performed to determine the saturation time. The time limit on carbon canister service shall be recorded and the expiration date attached to the carbon can.

(7) Liquid scrubbers may be used upstream of carbon canisters to enhance VOC capture provided such systems are closed systems and the spent absorbing solution is discharged into a closed container, vessel, or system.

B. Thermal Oxidizer.

(1) The thermal oxidizer six minute average firebox exit temperature shall be maintained at not less than 1400°F and waste gas flows shall be limited to assure at least a 0.5 second residence time in the fire box while waste gas is being fed into the oxidizer.

(2) The thermal oxidizer exhaust temperature shall be continuously monitored and recorded when waste gas is directed to the oxidizer. The temperature measurements shall be made at intervals of six minutes or less and recorded at that frequency. Temperature measurements recorded in

continuous strip charts may be used to meet the requirements of this section.

The temperature measurement device shall be installed, calibrated, and maintained according to accepted practice and the manufacturer's specifications. The device shall have an accuracy of the greater of ±0.75 percent of the temperature being measured expressed in degrees Celsius or ±2.5ºC.

(3) As an alternative to Special Condition 64.B.(1), the thermal oxidizer may be tested to confirm a minimum 99 wt percent destruction efficiency. The results of the test will be used to determine the minimum operating temperature and residence time. Stack Test must have been performed within the last 12 months. Stack VOC concentrations and flow rates shall be measured in accordance with applicable United States Environmental Protection Agency (EPA) Reference Methods. A copy of the test report shall be maintained with the thermal oxidizer and a summary of the testing results shall be included with the emission calculations.

(4) As an alternative to Special Condition 64.B.(1)-(2), the thermal oxidizer may be equipped with continuous VOC monitors (inlet and outlet). The VOC monitors shall be calibrated and maintained according to Special Condition No. 55, except 55.C. In order to demonstrate compliance with this requirement, inlet VOC and outlet VOC concentrations and flows shall be measured at least every 15 minutes and this information used to determine inlet and outlet VOC mass rates on an hourly basis to confirm a minimum 99 percent destruction efficiency or an exhaust concentration not greater than 20 ppmv.

C. Internal Combustion Engine.

(1) The internal combustion engine shall have a VOC destruction efficiency of at least 99 percent.

(2) The engine must have been stack tested with butane to confirm the required destruction efficiency within the past 12 months. VOC shall be measured in accordance with the applicable United States Environmental Protection Agency (EPA) Reference Method during the stack test and the exhaust flow rate may be determined from measured fuel flow rate and measured oxygen concentration. A copy of the stack test report shall be maintained with the engine. There shall also be documentation of acceptable VOC emissions following each occurrence of engine maintenance which may reasonably be expected to increase emissions including oxygen sensor replacement and catalyst cleaning or replacement. Stain tube indicators specifically designed to measure VOC

concentration shall be acceptable for this documentation, provided a hot air probe or equivalent device is used to prevent error due to high stack temperature, and three sets of concentration measurements are made and averaged. Portable VOC analyzers meeting the requirements of Special Condition 55 are also acceptable for this documentation.

(3) The engine shall be operated with an oxygen sensor-based air-to-fuel ratio (AFR) controller. Documentation for each AFR controller that the, manufacturer's, or supplier's recommended maintenance has been performed, including replacement of the oxygen sensor as necessary for oxygen sensor-based controllers shall be maintained with the engine. The oxygen sensor shall be replaced at least quarterly in the absence of a specific written recommendation.

D. The plant flare system

(1) The heating value and velocity requirements in 40 CFR 60.18 shall be satisfied during operations authorized by this permit.

(2) The flare shall be operated with a flame present at all times and/or have a constant pilot flame. The pilot flame shall be continuously monitored by a thermal couple or an infrared monitor. The time, date, and duration of any loss of pilot flame shall be recorded. Each monitoring device shall be accurate to, and shall be calibrated at a frequency in accordance with, the manufacturer's specifications.

(3) Each flare shall be equipped with one of the following by December 31, 2011:

(a) Operation and maintenance of a flare gas recovery system.

(b) A continuous flow monitor and composition analyzer that provides a record of the flare gas flow and composition of either the total VOC or heating value of the flare gas.

The flow monitor and analyzer sample point shall be installed as near as possible to the flare inlet such that the total vent stream to the flare is measured and analyzed. Readings shall be taken at least once every 15 minutes and the average hourly values of the flow and composition shall be recorded each hour. The flow monitors shall be calibrated on an annual basis to meet the following accuracy specifications: the flow monitor must be calibrated to manufacturer's specifications; the temperature monitor must be

calibrated to within ± 2.0 percent at absolute temperature; the pressure monitor must be calibrated to within ± 5.0 mmHg.

(i) If VOC monitoring is chosen: Calibration of the analyzer shall follow the procedures and requirements of Section 10.0 of 40 CFR Part 60, Appendix B, Performance Specification 9, as amended through October 17, 2000, (65 FR 61744), except that the multi-point calibration procedure in Section 10.1 of Performance Specification 9 shall be performed at least once every calendar quarter instead of once every month, and the mid-level calibration check procedure in Section 10.2 of Performance Specification 9 shall be performed at least once every calendar week instead of once every 24 hours. The on-line analyzer system must be capable of measuring constituents sufficient to determine the net heating value of the gas combusted in the flare to within 5.0%, or be calibrated with certified standards of the top tow constituents affecting net heating value, whichever is more stringent and the ranges of calibration standards may be based on the typical concentrations observed rather than the full potential range of concentrations. The calibration gases used for calibration procedures shall be in accordance with Section 7.1 of Performance Specification 9. Net heating value of the gas combusted in the flare shall be calculated according to the equation given in 40 CFR § 60.18(f)(3) as amended through October 17, 2000, (65 FR 61744). (10/11).

(ii) If heating value is chosen: The calorimeter shall be calibrated, installed, operated, and maintained, in accordance with manufacturer recommendations, to continuously measure and record the net heating value of the gas sent to the flare, in British thermal units/standard cubic foot of the gas.

E. Single Carbon Adsorption or Scrubber System

A single liquid scrubbing or single carbon canister adsorption system may be used as a sole control device if the requirements below are satisfied.

(1) The exhaust to atmosphere shall be continuously monitored with a CEM. The VOC concentration shall be recorded at least once every 15 minutes when waste gas is directed to the CAS or scrubber.

(2) The method of VOC sampling and analysis shall be by detector meeting the requirements of Special Condition 55 except 55.C.

(3) An alarm shall be installed such that an operator is alerted when outlet VOC concentration exceeds 100 ppmv above background. The MSS activity shall be stopped as soon as possible when the VOC concentration exceeds 100 ppmv above background for more than one minute. The date and time of all alarms and the actions taken shall be recorded.

F. A closed loop refrigerated vapor recovery system

(1) The vapor recovery system shall be installed on the facility to be degassed using good engineering practice to ensure air contaminants are flushed from the facility through the refrigerated vapor condensers and back to the facility being degassed. The vapor recovery system and facility being degassed shall be enclosed except as necessary to insure structural integrity (such as roof vents on a floating roof tank).

(2) VOC concentration in vapor being circulated by the system shall be sampled and recorded at least once every 4 hours at the inlet of the condenser unit with an instrument meeting the requirements of Special Condition 55.

(3) The quantity of liquid recovered from the tank vapors and the tank pressure shall be monitored and recorded each hour. The liquid recovered must increase with each reading and the tank pressure shall not exceed one inch water pressure while the system is operating.

G. Other control devices approved by the TCEQ through a permit amendment application or a pollution control permit application. **(3/10)**

65. The following requirements apply to capture systems for the plant flare system.

A. Either conduct a once a month visual, audible, and/or olfactory inspection of the capture system to verify there are no leaking components in the capture system; or verify the capture system is leak-free by inspecting in accordance with 40 CFR Part 60, Appendix A, Test Method 21 once a year. Leaks shall be indicated by an instrument reading greater than or equal to 500 ppmv above background.

B. The control device shall not have a bypass.

or

If there is a bypass for the control device, comply with either of the following requirements:

(1) Install a flow indicator that records and verifies zero flow at least once every fifteen minutes immediately downstream of each valve that if opened would allow a vent stream to bypass the control device and be emitted, either directly or indirectly, to the atmosphere; or

(2) Once a month, inspect the valves, verifying the position of the valves and the condition of the car seals that prevent flow out the bypass.

These requirements do not apply to high point vent and low point drain valves. A deviation shall be reported if the monitoring or inspections indicate bypass of the control device when required to be in service per this permit.

C. If any of the above inspections is not satisfactory, the permit holder shall promptly take necessary corrective action. Records shall be maintained documenting the performance and results of the inspections required above. **(3/10)**

66. If spray guns are used to apply paint, they shall be airless, high volume low pressure (HVLP), or have the same or higher transfer efficiency as airless or HVLP spray guns. **(3/10)**

67. Emissions from all painting activities, except for minor painting identified in Attachment 2 to this permit, at this site must satisfy the criteria below. New compounds may also be added through the use of the procedure below.

A. Short-term (pounds per hour [lb/hr]) and annual (TPY) emissions shall be determined for each chemical in the paint as documented in the permit application. The calculated emission rate shall not exceed the maximum allowable emissions rate at any emission point.

B. The Effect Screening Level (ESL) for the material shall be obtained from the current TCEQ ESL list or by written request to the TCEQ Toxicology Section.

C. The total painting emissions of any compound must satisfy one of the following conditions:

(1) The total emission rate is less than 0.1 lb/hr and the ESL greater than or equal to 2 ug/m3; or

(2) The emission rate of the compound in pounds per hour is less than the ESL for the compound divided by 171.5 (ER<ESL/171.5).

D. The permit holder shall maintain records of the information below and the demonstrations in steps A though C above. The following documentation is required for each compound:

(1) Chemical name(s), composition, and chemical abstract registry number if available.

(2) Material Safety Data Sheet.

(3) Maximum concentration of the chemical in weight percent

(4) Paint usage and the associated emissions shall be recorded each month and the rolling 12 month total emissions updated. **(3/10)**

68. No visible emissions shall leave the property due to painting or abrasive blasting. **(3/10)**

69. Black Beauty and Garnet Sand may be used for abrasive blasting. The permit holder may also use blast media that meet the criteria below:

A. The media shall not contain asbestos or greater than 1.0 weight percent crystalline silica.

B. The weight fraction of any metal in the blast media with a short term effects screening level (ESL) less than 50 micrograms per cubic meter as identified in the most recently published TCEQ ESL list shall not exceed the ESLmetal/1000.

C. The MSDS for each media used shall be maintained on site.

D. Blasting media usage and the associated emissions shall be recorded each month and the rolling 12 month total emissions updated. **(3/10)**

70. Planned maintenance activities must be conducted in a manner consistent with good practice for minimizing emissions, including the use of air pollution control equipment, practices and processes. All reasonable and practical efforts to comply with Special Conditions 52 through 69, 71, and 72 must be used when conducting the planned maintenance activity, until the commission determines that the efforts are unreasonable or impractical, or that the activity is an unplanned maintenance activity. **(3/10)**

71. Slab cleaning activities are limited to water washing small pieces of process equipment, empty vacuum trucks, and empty portable frac containers. Records shall be maintained of the number of items cleaned each day and the emissions determined each month based

on the number of items cleaned as estimated in the permit amendment application, PI-1 dated December 21, 2006. The permit holder may assume that all vacuum trucks and frac tanks used on the site as recorded in Special Conditions 59 and 60 are cleaned in lieu of maintaining cleaning records for those items. **(3/10)**

72. The following requirements ensure satisfactory impacts off-site during MSS.

    A. A maximum of 3 frac or temporary storage tanks or vessels may be filled with naphtha during any one hour period.

    B. Emissions from refilling tanks with a landed roofs with a liquid with a vapor pressure greater than 0.50 psia shall be routed to a control device meeting the requirements of Special Condition 64 unless the tank has been cleaned and degassed.

    C. While filling a tank with a landed roof with a liquid with vapor pressure greater than 0.50 psia without emission control, no other tanks with landed roofs may be degassed or filled with that type of liquid.

    D. If a cleaned and degassed tank with a landed roof has been refilled with a liquid with vapor pressure greater than 0.50 psia without emission control in the past 12 months, emissions from refilling the tank with a landed roof shall be routed to a control device meeting the requirements of Special Condition 64 if the liquid has a vapor pressure greater than 0.50 psia. **(3/10)**

73. Records shall be maintained in accordance with Special Condition 53 for planned MSS on the Air Liquide Large Industries SMR (Permit 34245, RN103120929). Total waste gas directed to the Valero flares during these operations shall not exceed the total identified in the permit amendment application, PI-1 dated December 21, 2006. **(3/10)**

74. The following steps shall take place before the catalyst is removed from the HDS unit for transfer to the catalyst pad. The reactor shall be cooled prior to opening and the catalyst shall be flushed with gas oil followed by hydrogen recycle gas circulation. The catalyst shall then be neutralized with a demineralized water and soda ash solution. **(3/10)**

75. With the exception of the MSS emission caps in the attached table entitled, “Emission Sources - Emission Caps and Individual Emissions Limitations,” these permit conditions become effective 180 days after the approval of the amendment application, PI 1 dated December 21, 2006. During this period, monitoring and recordkeeping shall satisfy the requirements of Special Condition 53.A through 53.D. Emissions shall be estimated using good engineering practice and methods to provide reasonably accurate representations for emissions. The basis used for determining the quantity of air contaminants to be emitted shall be recorded. The permit holder may maintain abbreviated records of emissions from Attachments 2 and 3 activities as allowed in

Special Condition 53 rather than documenting all the information required by Special Condition 53 parts A through D. **(3/10)**

MSAT Project

76. Tanks 114, 115, 116, 156, and 161 (EPNs TK-114, 173, 174, 129, and 140) shall be equipped with internal floating roofs with mechanical shoe primary seals and rim mounted secondary seals prior to storing benzene concentrate for the MSAT project. **(6/10)**

Dated: June 18, 2012

ATTACHMENT 2

Permit Numbers 38754 and PSDTX324M13

INHERENTLY LOW EMITTING ACTIVITIES

	Emissions				
Activity	VOC	NOx	CO	PM	H_2S/SO_2
Catalyst activation/deactivation	x				
Management of sludge from pits, ponds, sumps, and water conveyances	x				
Aerosol Cans	x				
Calibration of analytical equipment and process instrumentation	x	x	x		x
Carbon canister replacement	x				
Catalyst charging/handling				x	
Instrumentation/analyzer maintenance	x				
Meter proving	x				
Replacement of analyzer filters and screens	x				
Maintenance on water treatment systems (cooling, boiler, potable)	x				
Soap and other aqueous based cleaners	x				
Cleaning sight glasses	x				
Aerosol and miscellaneous chemical usage	x				

Dated: December 10, 2010

ATTACHMENT 3

Permit Numbers 38754 and PSDTX324M13

ROUTINE MAINTENANCE ACTIVITIES

Pump repair/replacement
Fugitive component (valve, pipe, flange) repair/replacement
Compressor repair/replacement
Heat exchanger repair/replacement
Vessel repair/replacement

Dated: December 10, 2010

ATTACHMENT 4

Permit Numbers 38754 and PSDTX324M13

MSS ACTIVITY SUMMARY

Facilities	Description	Emissions Activity	EPN
all process units and tanks	shutdown/depressurize/ drain/startup (includes SRU shutdowns, FCCU startups and Air Liquide MSS activities)	Vent to control	MSS-TA MSS-MA
all process units and tanks	process unit purgegas/drain/startup (except FCCU and SRU)	Vent to atmosphere	MSS-TA UNCONTROLLED MSS-MA UNCONTROLLED
Vacuum Trucks	removal and transfer of process and/or waste liquids	Vent to atmosphere	MSS-TA UNCONTROLLED MSS-MA UNCONTROLLED
Process units and tanks	Painting	Vent to atmosphere	MSS-TA UNCONTROLLED MSS-MA UNCONTROLLED
Process units and tanks	Miscellaneous chemical usage	Vent to atmosphere	MSS-TA UNCONTROLLED MSS-MA UNCONTROLLED
FRAC tanks	Temporary storage of process liquids and/or waste liquids	Vent to atmosphere	MSS-TA UNCONTROLLED MSS-MA UNCONTROLLED
Cleaning Slab	Washing of portable or mobile MSS or process equipment	vent to atmosphere	MSS-TA UNCONTROLLED MSS-MA UNCONTROLLED
Process units and tanks	Abrasive blasting	Vent to atmosphere	MSS-TA UNCONTROLLED
HDS	Remove spent catalyst, store on pad prior to transfer	Vent to atmosphere	MSS-TA UNCONTROLLED

Dated: December 10, 2010

EMISSION SOURCES - EMISSIONS CAPS AND INDIVIDUAL EMISSION LIMITATIONS

Permit Numbers 38754 and PSDTX324M13

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

AIR CONTAMINANTS DATA

Pollutant (1)	Emission Rates * lb/hr	TPY**
Emission Caps		
SO_2	465.9	1,854
VOC	929.5	1,079
NO_x	1,047	2,226
CO	1,246	5,154
PM_{10}	248.6	759.5
H_2SO_4	49.00	214.6
H_2S	2.92	12.79
Benzene	16.33	13.49
Maintenance, Startup, and Shutdown (MSS) Caps (5)		
CO	3,005	54.35
NO_x	560.3	11.24
VOC	1,838	59.96
SO_2	1,019	37.24
H_2S	6.59	0.22
PM	80.53	1.28
Ammonia	4.41	0.17
Exempt Solvents	1.76	0.60

EMISSION SOURCES - EMISSIONS CAPS AND INDIVIDUAL EMISSION LIMITATIONS

AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates * lb/hr	TPY**
Emissions not in permit emission caps:				
31F	Alky Unit Fugitives (4)	HF	0.13	0.55
168	Oleflex CCR	Sulfuric Acid	0.01	0.01
		HCl	0.06	0.28
		Chlorine	0.01	0.04
121	HOC Scrubber	Sulfuric Acid	49.00	214.6
155	CRU CCR	HCl	0.10	0.29
Emissions in permit emission caps:				
REFFUG - includes: 1F, 2F, 4F, 11F, 12F, 13F, 18F, 20F, 21/22F, 30B02F, 30B03F, 31F, 36F, 37F, 38F, 41/46/24F, 47F, 47PSA, 48F, 49F, 175, 52F, 133F, DOCKS, FUEL DRUM, GBF, LPG STGF, MVRUF, T1F, T2/2AF, T3F, TRKRACKFUG, 201	Refinery Fugitives VOC Subcaps (4)	VOC	46.99	205.8
37, 9, 10, 11, 12, 13, 15, 16, 17, 142, 112, TK-114, 173, 174, 46, 48, 60, 63, 61, 64, 129, 70, 140, 71, 72, 93, 94, TK-51, 88, 89, 90, 91, 92, 156, 157, 164, 165, 196, 197, 198, 169, 166, 95, 96, 69, 5, 6, 7, 8, 34, 35, 36	Tanks Subcaps	VOC	232.7	289.6

EMISSION SOURCES - EMISSIONS CAPS AND INDIVIDUAL EMISSION LIMITATIONS

AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates * lb/hr	TPY**
1	Heater - Crude Heater (01-H-01)	NO_x	5.09	19.24
		VOC	0.68	2.90
		SO_2	2.20	6.43
		CO	6.33	20.13
		PM/PM_{10}	0.94	4.00
131	Heater - Crude Preflash (01-H-02)	NO_x	1.51	6.29
		VOC	0.08	0.35
		SO_2	0.25	0.64
		CO	0.62	2.71
		PM/PM_{10}	0.11	0.49
132	Heater - Crude Stabilizer (01-H-03)	NO_x	0.48	2.06
		VOC	0.03	0.11
		SO_2	0.08	0.25
		CO	0.17	0.72
		PM/PM_{10}	0.04	0.15
74	Vacuum Heater	NO_x	5.62	18.83
		VOC	0.50	1.69
		SO_2	1.44	3.34
		CO	4.68	15.69
		PM/PM_{10}	0.70	2.34
114	Heater - Desalter Heater (11-H-01)	NO_x	6.69	20.71
		VOC	0.60	1.86
		SO_2	1.93	4.13
		CO	5.58	17.26
		PM/PM_{10}	0.83	2.57
115A/B	HDS Heaters	NO_x	10.72	42.86
		VOC	0.96	3.85
		SO_2	3.10	8.54
		CO	8.93	32.91
		PM/PM_{10}	1.33	5.32

EMISSION SOURCES - EMISSIONS CAPS AND INDIVIDUAL EMISSION LIMITATIONS

AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates * lb/hr	TPY**
116	Heater - HDS Pre-Heater (12-H-02)	NO_x	2.14	8.28
		VOC	0.10	0.37
		SO_2	0.31	0.83
		CO	0.29	1.10
		PM/PM_{10}	0.13	0.51
118	Hydrogen Reformer Heater	NO_x	60.19	284.40
		VOC	9.05	41.85
		SO_2	43.55	122.64
		CO	50.16	220.73
		PM/PM_{10}	7.47	35.80
153	Heater - HR Boiler (30-B-02)	NO_x	22.56	82.34
		VOC	1.52	3.99
		SO_2	4.89	10.66
		CO	8.46	28.94
		PM/PM_{10}	2.10	5.51
117	Heater - Alky Frac. Reb. (31-H-01)	NO_x	5.12	19.86
		VOC	0.77	2.97
		SO_2	2.47	6.60
		CO	2.28	8.83
		PM/PM_{10}	1.06	4.11
120	Heater - Butamer Heater (36-H-01)	NO_x	2.00	4.30
		VOC	0.09	0.19
		SO_2	0.29	0.41
		CO	0.27	0.98
		PM/PM_{10}	0.12	0.26
162	Oleflex Heater	NO_x	17.72	65.75
		VOC	2.10	8.41
		SO_2	6.75	18.66
		CO	19.45	69.49
		PM/PM_{10}	2.90	11.62

EMISSION SOURCES - EMISSIONS CAPS AND INDIVIDUAL EMISSION LIMITATIONS

AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates * lb/hr	TPY**
119	Heater - Sulften Heater (46-H-01)	NO_x	1.71	5.21
		VOC	0.08	0.24
		SO_2	0.24	0.63
		CO	0.35	1.49
		PM/PM_{10}	0.11	0.32
150	HCU Heater	NO_x	12.19	48.76
		VOC	1.10	4.38
		SO_2	3.52	9.72
		CO	6.10	24.38
		PM/PM_{10}	1.51	6.06
151	Heater - NHU Heater (48-H-01)	NO_x	3.52	12.72
		VOC	0.19	0.69
		SO_2	0.61	1.52
		CO	1.06	3.82
		PM/PM_{10}	0.26	0.95
152	CRU Heater	NO_x	36.90	133.06
		VOC	3.03	10.25
		SO_2	11.10	25.69
		CO	16.85	57.02
		PM/PM_{10}	4.18	14.16
172	Heater - RSU Heater (49-H-71)	NO_x	3.96	15.26
		VOC	0.36	1.37
		SO_2	1.14	3.04
		CO	3.30	12.72
		PM/PM_{10}	0.49	1.90
49-H-90	Heater - C7 Splitter Reb. (49-H-90)	NO_x	3.99	15.46
		VOC	0.57	2.18
		SO_2	1.84	4.83
		CO	5.32	16.82
		PM/PM_{10}	0.79	3.01

EMISSION SOURCES - EMISSIONS CAPS AND INDIVIDUAL EMISSION LIMITATIONS

AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates * lb/hr	TPY**
195	Heater - GDU Charge Heater (52-H-01)	NO_x	3.35	14.69
		VOC	0.89	3.34
		SO_2	2.87	7.40
		CO	13.15	34.29
		PM/PM_{10}	1.23	4.61
124	API Separator	NO_x	0.19	0.84
		VOC	0.43	2.08
		SO_2	0.03	0.13
		CO	1.65	7.22
168	Oleflex CCR	SO_2	0.04	0.19
V-201	Unloading Vent	VOC	0.04	0.16
122	Cooling Tower - HOC	VOC	6.09	26.67
123	Cooling Tower - Alky	VOC	1.26	5.52
167-CT	Cooling Tower - BUP	VOC	1.81	7.91
1CT	Cooling Tower - Crude	VOC	0.21	0.92
73-P-3	Engine - 73-P-3	NO_x	11.63	15.35
		VOC	1.21	1.59
		SO_2	0.98	1.30
		CO	3.21	4.23
		PM/PM_{10}	1.06	1.39
73-P-4	Engine - 73-P-4	NO_x	10.42	18.09
		VOC	1.08	1.88
		SO_2	0.88	1.53
		CO	2.87	4.99
		PM/PM_{10}	0.95	1.64

EMISSION SOURCES - EMISSIONS CAPS AND INDIVIDUAL EMISSION LIMITATIONS

AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates * lb/hr	TPY**
73-P-5	Engine - 73-P-5	NO_x	11.63	29.12
		VOC	1.21	3.02
		SO_2	0.98	2.46
		CO	3.21	8.03
		PM/PM_{10}	1.06	2.64
72-P-6	Engine - 72-P-6	NO_x	11.63	11.64
		VOC	1.21	1.21
		SO_2	0.98	0.98
		CO	3.21	3.21
		PM/PM_{10}	1.06	1.06
72-P-7	Engine - 72-P-7	NO_x	11.63	2.25
		VOC	1.21	0.23
		SO_2	0.98	0.19
		CO	3.21	0.62
		PM/PM_{10}	1.06	0.20
72-P-8	Engine - 72-P-8	NO_x	11.63	2.79
		VOC	1.21	0.29
		SO_2	0.98	0.24
		CO	3.21	0.77
		PM/PM_{10}	1.06	0.25
72-P-9	Engine - 72-P-9	NO_x	11.63	17.32
		VOC	1.21	1.80
		SO_2	0.98	1.47
		CO	3.21	4.77
		PM/PM_{10}	1.06	1.57
72-P-10	Engine - 72-P-10	NO_x	8.36	26.31
		VOC	0.87	2.73
		SO_2	0.71	2.23
		CO	2.30	7.25
		PM/PM_{10}	0.76	2.39

EMISSION SOURCES - EMISSIONS CAPS AND INDIVIDUAL EMISSION LIMITATIONS

AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates * lb/hr	TPY**
72-P-11	Engine - 72-P-11	NO_x	11.75	23.34
		VOC	1.22	2.42
		SO_2	0.99	1.97
		CO	3.24	6.43
		PM/PM_{10}	1.07	2.12
72-P-14A	Engine - 72-P-14A	NO_x	11.63	14.17
		VOC	1.21	1.47
		SO_2	0.98	1.20
		CO	3.21	3.91
		PM/PM_{10}	1.06	1.29
72-P-14B	Engine - 72-P-14B	NO_x	10.32	17.20
		VOC	1.07	1.78
		SO_2	0.87	1.45
		CO	2.85	4.74
		PM/PM_{10}	0.94	1.56
50-P-16	Engine - 50-P-16	NO_x	10.90	4.74
		VOC	1.13	0.49
		SO_2	0.92	0.40
		CO	3.01	1.31
		PM/PM_{10}	0.99	0.43
50-P-20	Engine - 50-P-20	NO_x	10.90	9.61
		VOC	1.13	1.00
		SO_2	0.92	0.81
		CO	3.01	2.65
		PM/PM_{10}	0.99	0.87
16-P-04	Engine - 16-P-04	NO_x	8.00	0.21
		VOC	0.83	0.02
		SO_2	0.68	0.02
		CO	2.20	0.06
		PM/PM_{10}	0.73	0.02

EMISSION SOURCES - EMISSIONS CAPS AND INDIVIDUAL EMISSION LIMITATIONS

AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates * lb/hr	TPY**
16-P-07	Engine - 16-P-07	NO_x	9.69	0.15
		VOC	1.01	0.02
		SO_2	0.82	0.01
		CO	2.67	0.04
		PM/PM_{10}	0.88	0.01
126, 158, 127	Main Flare, Ground Flare, BUP Flare Subcaps	NO_x	62.17	11.48
		VOC	220.25	136.78
		SO_2	18.82	4.70
		CO	450.94	76.87
31	Loading - Heavy Oil	VOC	16.45	4.72
SHIP FUG	Loading - Ships Fugitives (4)	VOC	186.57	91.74
VRU	Loading - MVRU	VOC	33.74	23.13
TRUCKFUG	Loading - Truck Fugitives (4)	VOC	11.88	10.87
TRUCKCOMB	Loading - Truck Combustor	NO_x	6.98	7.41
		VOC	8.19	9.41
		SO_2	0.01	0.01
		CO	13.96	11.44
AE-49601A/B	AE-49601A/B Analyzer Vent	VOC	0.01	0.01
AE-49900A/B	AE-49900A/B Analyzer Vent	VOC	0.01	0.01
AE-49901A/B	AE-49901A/B Analyzer Vent	VOC	0.01	0.01
121	HOC Belco Scrubber	NO_x	356.20	473.81
		VOC	28.02	115.53
		SO_2	203.53	420.09
		CO	889.96	1470.33
		PM/PM_{10}	120.32	527.00

EMISSION SOURCES - EMISSIONS CAPS AND INDIVIDUAL EMISSION LIMITATIONS

AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates * lb/hr	TPY**
121	SRU Incinerators	NO_x	54.64	142.8
		VOC	0.96	3.13
		SO_2	191.3	674.9
		CO	177.4	392.1
		PM/PM_{10}	1.34	4.39

(1) Emission point identification - either specific equipment designation or emission point number from plot plan per Attachment 1.
(2) Specific point source name. For fugitive sources use area name or fugitive source name.
(3) VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1
Exempt Solvents - carbon compounds that have been excluded from the definition of volatile organic compound
NO_x - total oxides of nitrogen
SO_2 - sulfur dioxide
CO - carbon monoxide
PM - particulate matter, suspended in the atmosphere, including PM_{10}
PM_{10} - particulate matter equal to or less than 10 microns in diameter. Where PM is not listed, it shall be assumed that no PM greater than 10 microns is emitted.
HF - hydrogen flouride
H_2S - hydrogen sulfide
H_2SO_4 - sulfuric acid
HCl - hydrochloric acid
Cl_2 - chlorine
NH_3 - ammonia
(4) Emission rate is an estimate and is enforceable through compliance with the applicable special condition(s) and permit application representations.
(5) The annual limits tons per year apply to calendar year 2010 and for each rolling 12-month period starting January 2011. The MSS emission caps are independent of the routine operating emission caps. Authorized emissions of a pollutant from facilities in this permit is the sum of the emission cap and the MSS emission cap.

Dated: March 5, 2012

ATTACHMENT 1

Permit Numbers 38754 and PSDTX324M13

Permit Emission Points by Type

Category: Fired Units	EPN	Description
	1	Crude Heater
	74	Vacuum Unit Heater
	114	Desalter Heater
	115	HDS Charge Heaters
	116	HDS Heavy Oil Preheater
	117	Alky Fract Reboiler
	118	Hydrogen Reformer Heater
	119	Sulften Heater
	120	Butamer Heater
	121	HOC (incinerator and scrubber stack)
	124	API Separator Combustor
	131	Crude Preflash Heater
	132	Crude Stabilizer Heater
	150	HCU Heater
	151	NHT Heater
	152	CRU Heaters
	153	Boiler 30-B-02
	162	Oleflex Heaters
	172	RSU Heater
	49H90	C7 Splitter Reboiler
	TRUCKCOMB	Truck Loading Combustor
	195	GD Charge Heater
	73-P-3	Diesel Pump
	73-P-4	Diesel Pump
	73-P-5	Diesel Pump
	72-P-6	Diesel Pump
	72-P-7	Diesel Pump
	72-P-8	Diesel Pump
	72-P-9	Diesel Pump
	72-P-10	Diesel Pump
	72-P-11	Diesel Pump
	72-P-14A	Diesel Pump
	72-P-14B	Diesel Pump
	50-P-16	Diesel Pump
	50-P-20	Diesel Pump
	16-P-04	Diesel Pump
	16-P-07	Diesel Pump

Category: Flares	EPN	Description
	126	Main Flare
	127	MTBE Flare
	128	Halo Flare (Pilots Only)
	135	Acid Gas Flare (Pilots Only)
	158	Ground Flare

Category: Tanks	EPN	Description
	5	Tank No. 93
	6	Tank No. 94
	7	Tank No. 95
	8	Tank No. 96
	9	Tank No. 101
	10	Tank No. 102
	11	Tank No. 103
	12	Tank No. 104
	13	Tank No. 105
	15	Tank No. 108
	16	Tank No. 109
	17	Tank No. 110
	34	Tank No. 97
	35	Tank No. 98
	36	Tank No. 99
	37	Tank No. 100
	46	Tank No. 137
	48	Tank No. 139
	TK-51	Tank No. 51
	60	Tank No. 14
	61	Tank No. 15
	63	Tank No. 149
	64	Tank No. 150
	69	Tank No. 9
	70	Tank No. 16
	71	Tank No. 17
	72	Tank No. 18
	88	Tank No. 57
	89	Tank No. 58
	90	Tank No. 59
	91	Tank No. 60
	92	Tank No. 61

Category: Tanks (cont'd.)	EPN	Description
	93	Tank No. 19
	94	Tank No. 20
	95	Tank No. 77
	96	Tank No. 78
	TK-112	Tank No. 112
	TK-114	Tank No. 114
	129	Tank No. 156
	140	Tank No. 161
	142	Tank No. 111
	156	Tank No. 62
	157	Tank No. 63
	164	Tank No. 64
	165	Tank No. 65
	166	Tank No. 76
	169	Tank No. 75
	173	Tank No. 115
	174	Tank No. 116
	196	Tank No. 70-TK-66
	197	Tank No. 70-TK-67
	198	Tank No. 70-TK-68

Category: Fugitive	EPN	Description
	1F	Crude Unit
	2F	Vacuum Unit
	4F	LEU
	11F	Desalter Unit
	12F	HDS Unit
	13F	SMR
	18F	HRLEU Unit
	20F	LRU
	21/22F	HOC Unit
	30B02F	30-B-02
	30B03F	30-B-03
	31F	HF Alkylation Unit
	36F	Butamer Unit
	37F	MTBE
	38F	Oleflex

Category: Fugitive (cont'd.)	EPN	Description
	41/46/24F	SULF/SEU/SRU
	47F	HCU
	47PSAF	PSA
	48F	NHT
	49F	CRU
	54F	MTBE/TAME Unit
	133F	Powerhouse
	175	49-RSU/XFU
	FUG-DOCKS	Docks
	FUELDRM	Fuel Gas Drum
	GBF	Gas Blending
	LPGSTGF	LPG Storage
	MVRUF	MVRU
	T1F	Terminal 1
	T2/2AF	Terminal 2/2A
	T3F	Terminal 3
	TRKRACKFUG	Truck Rack
	ATU3FUG	Amine
	SRU3FUG	SRU
	SCOTFUG	SCOT
	GD-FUG	Gasoline Desulfurization
	LPGSTGF	Propane Pump Fugitives
	201	Railcar Unloading

Category: Loading	EPN	Description
	VRU	Marine loading VRU
	31	Barge Loading (Heavy Oil)
	SHIP FUG	Ship Dock Fugitives
	TRUCKFUG	Truck Loading
	Loading-East	Loading East

Category: Other	EPN	Description
	1CT	CU/VRU Cooling Tower
	122	HOC Cooling Tower
	123	ALKY Cooling Tower
	167-CT	BUP Cooling Tower

Category: Other (cont'd.)	EPN	Description
	AE-49601A/B	Analyzer Vent AE-49601A/B
	AE-49900A/B	Analyzer Vent AE-49900A/B
	AE-49901A/B	Analyzer Vent AE-49901A/B
	V-201	Unloading Vent (MSS only)

Dated: December 10, 2010

Bryan W. Shaw, Ph.D., *Chairman*
Carlos Rubinstein, *Commissioner*
Toby Baker, *Commissioner*
Zak Covar, *Executive Director*

TEXAS COMMISSION ON ENVIRONMENTAL QUALITY

Protecting Texas by Reducing and Preventing Pollution

June 18, 2012

MR MICHAEL COX
STAFF ENVIRONMENTAL ENGINEER
VALERO REFINING-TEXAS LP
PO BOX 9370
CORPUS CHRISTI TX 78469-9370

Re: Permit Alteration
Permit Number: 38754
Valero Corpus Christi Refinery West Plant
Corpus Christi, Nueces County
Regulated Entity Number: RN100214386
Customer Reference Number: CN600127468
Account Number: NE-0112-G

Dear Mr. Cox:

This is in response to your letter received March 9, 2012, requesting alteration of the conditions of the above-referenced permit. We understand that an alteration was requested of Permit No. 38754 to comply with an EPA Consent Decree to incorporate federally enforceable NSPS Subpart J applicability for the BUP Flare, Main Flare and Ground Flare. Special Condition No. 51 was revised to include Subpart J as required or stipulated in Consent Decree paragraph 292.

As indicated in Title 30 Texas Administrative Code § 116.116(c) [30 TAC § 116.116(c)], and based on our review, Permit Number 38754 is altered. Enclosed are the altered permit conditions to replace those currently attached to your permit. Please attach these to your permit.

Planned maintenance, startup, and shutdown emissions have been previously reviewed, authorized, and included in the MAERT. Any other maintenance activities are not authorized by this permit and will need to obtain a separate authorization.

Your cooperation in this matter is appreciated. If you need further information or have any questions, please contact Mr. Joel Ford at (512) 239-1339 or write to the Texas Commission on Environmental Quality, Office of Air, Air Permits Division, MC-163, P.O. Box 13087, Austin, Texas 78711-3087.

Re: Permit Number: 38754

This action is taken under authority delegated by the Executive Director of the Texas Commission on Environmental Quality.

Sincerely,

Michael Wilson, P.E., Director
Air Permits Division
Office of Air
Texas Commission on Environmental Quality

MPW/jf

Enclosure

cc: Air Section Manager, Region 14 - Corpus Christi

Project Number: 175327