

FEDERAL OPERATING PERMIT

A FEDERAL OPERATING PERMIT IS HEREBY ISSUED TO
ExxonMobil Oil Corporation

AUTHORIZING THE OPERATION OF
Beaumont Polyethylene Plant
Mobil Beaumont Polyethylene Plant - Low Pressure Unit
Plastics Materials

LOCATED AT
Jefferson County, Texas
Latitude 30° 4' 1" Longitude 94° 13' 47"
Regulated Entity Number: RN100211903

This permit is issued in accordance with and subject to the Texas Clean Air Act (TCAA), Chapter 382 of the Texas Health and Safety Code and Title 30 Texas Administrative Code Chapter 122 (30 TAC Chapter 122), Federal Operating Permits. Under 30 TAC Chapter 122, this permit constitutes the permit holder's authority to operate the site and emission units listed in this permit. Operations of the site and emission units listed in this permit are subject to all additional rules or amended rules and orders of the Commission pursuant to the TCAA.

This permit does not relieve the permit holder from the responsibility of obtaining New Source Review authorization for new, modified, or existing facilities in accordance with 30 TAC Chapter 116, Control of Air Pollution by Permits for New Construction or Modification.

The site and emission units authorized by this permit shall be operated in accordance with 30 TAC Chapter 122, the general terms and conditions, special terms and conditions, and attachments contained herein.

This permit shall expire five years from the date of issuance. The renewal requirements specified in 30 TAC § 122.241 must be satisfied in order to renew the authorization to operate the site and emission units.

Permit No: 02277 Issuance Date: _____

For the Commission

Table of Contents

Section	Page
General Terms and Conditions	1
Special Terms and Conditions	1
Emission Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting.....	1
Additional Monitoring Requirements	9
New Source Review Authorization Requirements.....	11
Compliance Requirements	11
Risk Management Plan	13
Protection of Stratospheric Ozone	13
Permit Location.....	13
Permit Shield (30 TAC § 122.148)	13
Attachments.....	14
Applicable Requirements Summary.....	15
Additional Monitoring Requirements	58
Permit Shield	63
New Source Review Authorization References	68
Appendix A	79
Acronym List	80

General Terms and Conditions

The permit holder shall comply with all terms and conditions contained in 30 TAC § 122.143 (General Terms and Conditions), 30 TAC § 122.144 (Recordkeeping Terms and Conditions), 30 TAC § 122.145 (Reporting Terms and Conditions), and 30 TAC § 122.146 (Compliance Certification Terms and Conditions).

In accordance with 30 TAC § 122.144(1), records of required monitoring data and support information required by this permit, or any applicable requirement codified in this permit, are required to be maintained for a period of five years from the date of the monitoring report, sample, or application unless a longer data retention period is specified in an applicable requirement. The five year record retention period supersedes any less stringent retention requirement that may be specified in a condition of a permit identified in the New Source Review Authorization attachment.

If the permit holder chooses to demonstrate that this permit is no longer required, a written request to void this permit shall be submitted to the Texas Commission on Environmental Quality (TCEQ) by the Responsible Official in accordance with 30 TAC § 122.161(e). The permit holder shall comply with the permit's requirements, including compliance certification and deviation reporting, until notified by the TCEQ that this permit is voided.

The permit holder shall comply with 30 TAC Chapter 116 by obtaining a New Source Review authorization prior to new construction or modification of emission units located in the area covered by this permit.

All reports required by this permit must include in the submittal a cover letter which identifies the following information: company name, TCEQ regulated entity number, air account number (if assigned), site name, area name (if applicable), and Air Permits Division permit number(s).

Special Terms and Conditions:

Emission Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting

1. Permit holder shall comply with the following requirements:
 - A. Emission units (including groups and processes) in the Applicable Requirements Summary attachment shall meet the limitations, standards, equipment specifications, monitoring, recordkeeping, reporting, testing, and other requirements listed in the Applicable Requirements Summary attachment to assure compliance with the permit.
 - B. The textual description in the column titled "Textual Description" in the Applicable Requirements Summary attachment is not enforceable and is not deemed as a substitute for the actual regulatory language. The Textual Description is provided for information purposes only.
 - C. A citation listed on the Applicable Requirements Summary attachment, which has a notation [G] listed before it, shall include the referenced section and subsection for all commission rules, or paragraphs for all federal and state regulations and all subordinate paragraphs, subparagraphs and clauses, subclauses, and items contained within the referenced citation as applicable requirements.

- D. When a grouped citation, notated with a [G] in the Applicable Requirements Summary, contains multiple compliance options, the permit holder must keep records of when each compliance option was used.
 - E. Emission units subject to 40 CFR Part 63, Subpart FFFF as identified in the attached Applicable Requirements Summary table are subject to 30 TAC Chapter 113, Subchapter C, § 113.890 which incorporates the 40 CFR Part 63 Subpart by reference.
 - F. Emission units subject to 40 CFR Part 63, Subpart ZZZZ as identified in the attached Applicable Requirements Summary table are subject to 30 TAC Chapter 113, Subchapter C, §113.1090 which incorporates the 40 CFR Part 63 Subpart by reference.
 - G. Emission units subject to 40 CFR Part 63, Subpart A as identified in the attached Applicable Requirements Summary table are subject to 30 TAC Chapter 113, Subchapter C, §113.100 which incorporates the 40 CFR Part 63 Subpart by reference.
 - H. Emission units subject to 40 CFR Part 63, Subpart DDDDD as identified in the attached Applicable Requirements Summary table are subject to 30 TAC Chapter 113, Subchapter C, §113.1130 which incorporates the 40 CFR Part 63 Subpart by reference.
2. The permit holder shall comply with the following sections of 30 TAC Chapter 101 (General Air Quality Rules):
- A. Title 30 TAC § 101.1 (relating to Definitions), insofar as the terms defined in this section are used to define the terms used in other applicable requirements
 - B. Title 30 TAC § 101.3 (relating to Circumvention)
 - C. Title 30 TAC § 101.8 (relating to Sampling), if such action has been requested by the TCEQ
 - D. Title 30 TAC § 101.9 (relating to Sampling Ports), if such action has been requested by the TCEQ
 - E. Title 30 TAC § 101.10 (relating to Emissions Inventory Requirements)
 - F. Title 30 TAC § 101.201 (relating to Emission Event Reporting and Recordkeeping Requirements)
 - G. Title 30 TAC § 101.211 (relating to Scheduled Maintenance, Start-up, and Shutdown Reporting and Recordkeeping Requirements)
 - H. Title 30 TAC § 101.221 (relating to Operational Requirements)
 - I. Title 30 TAC § 101.222 (relating to Demonstrations)
 - J. Title 30 TAC § 101.223 (relating to Actions to Reduce Excessive Emissions)
3. Permit holder shall comply with the following requirements of 30 TAC Chapter 111:

- A. Visible emissions from stationary vents with a flow rate of less than 100,000 actual cubic feet per minute and constructed after January 31, 1972 that are not listed in the Applicable Requirements Summary attachment for 30 TAC Chapter 111, Subchapter A, Division 1, shall not exceed 20% opacity averaged over a six-minute period. The permit holder shall comply with the following requirements for stationary vents at the site subject to this standard:
- (i) Title 30 TAC § 111.111(a)(1)(B) (relating to Requirements for Specified Sources)
 - (ii) Title 30 TAC § 111.111(a)(1)(E)
 - (iii) Title 30 TAC § 111.111(a)(1)(F)(i), (ii), (iii), or (iv)
 - (iv) For emission units with vent emissions subject to 30 TAC § 111.111(a)(1)(B), complying with 30 TAC § 111.111(a)(1)(F)(ii), (iii), or (iv), and capable of producing visible emissions from, but not limited to, particulate matter, acid gases and NO_x, the permit holder shall also comply with the following periodic monitoring requirements for the purpose of annual compliance certification under 30 TAC § 122.146. These periodic monitoring requirements do not apply to vents that are not capable of producing visible emissions such as vents that emit only colorless VOCs; vents from non-fuming liquids; vents that provide passive ventilation, such as plumbing vents; or vent emissions from any other source that does not obstruct the transmission of light. Vents, as specified in the “Applicable Requirements Summary” attachment, that are subject to the emission limitation of 30 TAC § 111.111(a)(1)(B) are not subject to the following periodic monitoring requirements:
 - (1) An observation of stationary vents from emission units in operation shall be conducted at least once during each calendar quarter unless the emission unit is not operating for the entire quarter.
 - (2) For stationary vents from a combustion source, if an alternative to the normally fired fuel is fired for a period greater than or equal to 24 consecutive hours, the permit holder shall conduct an observation of the stationary vent for each such period to determine if visible emissions are present. If such period is greater than 3 months, observations shall be conducted once during each quarter. Supplementing the normally fired fuel with natural gas or fuel gas to increase the net heating value to the minimum required value does not constitute creation of an alternative fuel.
 - (3) Records of all observations shall be maintained.
 - (4) Visible emissions observations of emission units operated during daylight hours shall be conducted no earlier than one hour after sunrise and no later than one hour before sunset. Visible emissions observations of emission units operated only at night must be made with additional lighting and the temporary installation of contrasting backgrounds. Visible emissions observations shall be made during times when the activities

described in 30 TAC § 111.111(a)(1)(E) are not taking place. Visible emissions shall be determined with each stationary vent in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 mile, away from each stationary vent during the observation. For outdoor locations, the observer shall select a position where the sun is not directly in the observer's eyes. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. A certified opacity reader is not required for visible emissions observations.

(5) Compliance Certification:

- (a) If visible emissions are not present during the observation, the RO may certify that the source is in compliance with the applicable opacity requirement in 30 TAC § 111.111(a)(1) and (a)(1)(B).
- (b) However, if visible emissions are present during the observation, the permit holder shall either list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(1)(F) as soon as practicable, but no later than 24 hours after observing visible emissions to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.
- (c) Some vents may be subject to multiple visible emission or monitoring requirements. All credible data must be considered when certifying compliance with this requirement even if the observation or monitoring was performed to demonstrate compliance with a different requirement.

B. For visible emissions from a building, enclosed facility, or other structure; the permit holder shall comply with the following requirements:

- (i) Title 30 TAC § 111.111(a)(7)(A) (relating to Requirements for Specified Sources)
- (ii) Title 30 TAC § 111.111(a)(7)(B)(i) or (ii)

- (iii) For a building containing an air emission source, enclosed facility, or other structure containing or associated with an air emission source subject to 30 TAC § 111.111(a)(7)(A), complying with 30 TAC § 111.111(a)(7)(B)(i) or (ii), and capable of producing visible emissions from, but not limited to, particulate matter, acid gases and NO_x, the permit holder shall also comply with the following periodic monitoring requirements for the purpose of annual compliance certification under 30 TAC § 122.146:
- (1) An observation of visible emissions from a building containing an air emission source, enclosed facility, or other structure containing or associated with an air emission source which is required to comply with 30 TAC § 111.111(a)(7)(A) shall be conducted at least once during each calendar quarter unless the air emission source or enclosed facility is not operating for the entire quarter.
 - (2) Records of all observations shall be maintained.
 - (3) Visible emissions observations of air emission sources or enclosed facilities operated during daylight hours shall be conducted no earlier than one hour after sunrise and no later than one hour before sunset. Visible emissions observations of air emission sources or enclosed facilities operated only at night must be made with additional lighting and the temporary installation of contrasting backgrounds. Visible emissions shall be determined with each emissions outlet in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 mile, away from each emissions outlet during the observation. For outdoor locations, the observer shall select a position where the sun is not directly in the observer's eyes. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. A certified opacity reader is not required for visible emissions observations.
 - (4) Compliance Certification:
 - (a) If visible emissions are not present during the observation, the RO may certify that the source is in compliance with the applicable opacity requirement in 30 TAC § 111.111(a)(7) and (a)(7)(A)
 - (b) However, if visible emissions are present during the observation, the permit holder shall either list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(7)(B) as soon as practicable, but no later than 24 hours after observing visible emissions to

determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader

- C. For visible emissions from all other sources not specified in 30 TAC § 111.111(a)(1), (4), or (7); the permit holder shall comply with the following requirements:
- (i) Title 30 TAC § 111.111(a)(8)(A) (relating to Requirements for Specified Sources)
 - (ii) Title 30 TAC § 111.111(a)(8)(B)(i) or (ii)
 - (iii) For a source subject to 30 TAC § 111.111(a)(8)(A), complying with 30 TAC § 111.111(a)(8)(B)(i) or (ii), and capable of producing visible emissions from, but not limited to, particulate matter, acid gases and NO_x, the permit holder shall also comply with the following periodic monitoring requirements for the purpose of annual compliance certification under 30 TAC § 122.146:
 - (1) An observation of visible emissions from a source which is required to comply with 30 TAC § 111.111(a)(8)(A) shall be conducted at least once during each calendar quarter unless the source is not operating for the entire quarter.
 - (2) Records of all observations shall be maintained.
 - (3) Visible emissions observations of sources operated during daylight hours shall be conducted no earlier than one hour after sunrise and no later than one hour before sunset. Visible emissions observations of sources operated only at night must be made with additional lighting and the temporary installation of contrasting backgrounds. Visible emissions shall be determined with each source in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 mile, away from each source during the observation. For outdoor locations, the observer shall select a position where the sun is not directly in the observer's eyes. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. A certified opacity reader is not required for visible emissions observations.
 - (4) Compliance Certification:

- (a) If visible emissions are not present during the observation, the RO may certify that the source is in compliance with the applicable opacity requirement in 30 TAC § 111.111(a)(8) and (a)(8)(A)
 - (b) However, if visible emissions are present during the observation, the permit holder shall either list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(8)(B) as soon as practicable, but no later than 24 hours after observing visible emissions to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.
- D. For emission units with contributions from uncombined water, the permit holder shall comply with the requirements of 30 TAC § 111.111(b).
- E. Emission limits on nonagricultural processes, except for the steam generators specified in 30 TAC § 111.153, shall comply with the following requirements:
 - (i) Emissions of PM from any source may not exceed the allowable rates as required in 30 TAC § 111.151(a) (relating to Allowable Emissions Limits)
 - (ii) Sources with an effective stack height (h_e) less than the standard effective stack height (H_e), must reduce the allowable emission level by multiplying it by $[h_e/H_e]^2$ as required in 30 TAC § 111.151(b)
 - (iii) Effective stack height shall be calculated by the equation specified in 30 TAC § 111.151(c)
- F. Outdoor burning, as stated in 30 TAC § 111.201, shall not be authorized unless the following requirements are satisfied:
 - (i) Title 30 TAC § 111.205 (relating to Exception for Fire Training)
 - (ii) Title 30 TAC § 111.207 (relating to Exception for Recreation, Ceremony, Cooking, and Warmth)
 - (iii) Title 30 TAC § 111.219 (relating to General Requirements for Allowable Outdoor Burning)
 - (iv) Title 30 TAC § 111.221 (relating to Responsibility for Consequences of Outdoor Burning)

4. For storage vessels maintaining working pressure as specified in 30 TAC Chapter 115, Subchapter B, Division 1: "Storage of Volatile Organic Compounds," the permit holder shall comply with the requirements of 30 TAC § 115.112(a)(1).
5. For industrial wastewater specified in 30 TAC Chapter 115, Subchapter B, the permit holder shall comply with the following requirements:
 - A. Title 30 TAC § 115.145 (relating to Approved Test Methods)
 - B. Title 30 TAC § 115.146 (relating to Recordkeeping Requirements)
 - C. Title 30 TAC § 115.147(1) (relating to Exemptions)
 - D. Title 30 TAC § 115.148 (relating to Determination of Wastewater Characteristics)
6. The permit holder shall comply with the following requirements for units subject to any subpart of 40 CFR Part 60, unless otherwise stated in the applicable subpart:
 - A. Title 40 CFR § 60.7 (relating to Notification and Recordkeeping)
 - B. Title 40 CFR § 60.8 (relating to Performance Tests)
 - C. Title 40 CFR § 60.11 (relating to Compliance with Standards and Maintenance Requirements)
 - D. Title 40 CFR § 60.12 (relating to Circumvention)
 - E. Title 40 CFR § 60.13 (relating to Monitoring Requirements)
 - F. Title 40 CFR § 60.14 (relating to Modification)
 - G. Title 40 CFR § 60.15 (relating to Reconstruction)
 - H. Title 40 CFR § 60.19 (relating to General Notification and Reporting Requirements)
7. The permit holder shall comply with the following requirements for units subject to any subpart of 40 CFR Part 61, unless otherwise stated in the applicable subpart:
 - A. Title 40 CFR § 61.05 (relating to Prohibited Activities)
 - B. Title 40 CFR § 61.07 (relating to Application for Approval of Construction or Modification)
 - C. Title 40 CFR § 61.09 (relating to Notification of Start-up)
 - D. Title 40 CFR § 61.10 (relating to Source Reporting and Request Waiver)
 - E. Title 40 CFR § 61.12 (relating to Compliance with Standards and Maintenance Requirements)
 - F. Title 40 CFR § 61.13 (relating to Emissions Tests and Waiver of Emission Tests)
 - G. Title 40 CFR § 61.14 (relating to Monitoring Requirements)

- H. Title 40 CFR § 61.15 (relating to Modification)
 - I. Title 40 CFR § 61.19 (relating to Circumvention)
8. For facilities where total annual benzene quantity from waste is less than 1 megagram per year and subject to emission standards in 40 CFR Part 61, Subpart FF, the permit holder shall comply with the following requirements:
- A. Title 40 CFR § 61.355(a)(1)(iii), (a)(2), (a)(5)(i) - (ii), (a)(6), (b), and (c)(1) - (3) (relating to Test Methods, Procedures, and Compliance Provisions), for calculation procedures
 - B. Title 40 CFR § 61.356(a) (relating to Recordkeeping Requirements)
 - C. Title 40 CFR § 61.356(b), and (b)(1) (relating to Recordkeeping Requirements)
 - D. Title 40 CFR § 61.357(a), and (b) (relating to Reporting Requirements)
9. The permit holder shall comply with the requirements of 30 TAC Chapter 113, Subchapter C, § 113.100 for units subject to any subpart of 40 CFR Part 63, unless otherwise stated in the applicable subpart.
10. For miscellaneous chemical process facilities subject to maintenance wastewater requirements as specified in 40 CFR § 63.2485, Table 7, the permit holder shall comply with the requirements of 40 CFR § 63.105 (relating to Maintenance Wastewater Requirements) (Title 30 TAC Chapter 113, Subchapter C, § 113.890 incorporated by reference).

Additional Monitoring Requirements

11. Unless otherwise specified, the permit holder shall comply with the compliance assurance monitoring requirements as specified in the attached "CAM Summary" upon issuance of the permit. In addition, the permit holder shall comply with the following:
- A. The permit holder shall comply with the terms and conditions contained in 30 TAC § 122.147 (General Terms and Conditions for Compliance Assurance Monitoring).
 - B. The permit holder shall report, consistent with the averaging time identified in the "CAM Summary," deviations as defined by the deviation limit in the "CAM Summary." Any monitoring data below a minimum limit or above a maximum limit, that is collected in accordance with the requirements specified in 40 CFR § 64.7(c), shall be reported as a deviation. Deviations shall be reported according to 30 TAC § 122.145 (Reporting Terms and Conditions).
 - C. The permit holder may elect to collect monitoring data on a more frequent basis and average the data, consistent with the averaging time specified in the "CAM Summary," for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis. In no event shall data be collected and used in particular instances in order to avoid reporting deviations. All monitoring data shall be collected in accordance with the requirements specified in 40 CFR § 64.7(c).

- D. The permit holder shall operate the monitoring, identified in the attached “CAM Summary,” in accordance with the provisions of 40 CFR § 64.7.
 - E. The permit holder shall comply with either of the following requirements for any capture system associated with the VOC control device subject to CAM. If the results of the following inspections indicate that the capture system is not working properly, the permit holder shall promptly take necessary corrective actions:
 - (i) Once a year the permit holder shall inspect the capture system in compliance of CAM for leaks in accordance with 40 CFR Part 60, Appendix A, Test Method 21. Leaks shall be indicated by an instrument reading greater than or equal to 500 ppm above background or as defined by the underlying applicable requirement; or
 - (ii) Once a month, the permit holder shall conduct a visual, audible, and/or olfactory inspection of the capture system in compliance of CAM to detect leaking components.
 - F. The permit holder shall comply with either of the following requirements for any bypass of the control device subject to CAM. If the results of the following inspections or monitoring indicate bypass of the control device, the permit holder shall promptly take necessary corrective actions and report a deviation:
 - (i) Install a flow indicator that is capable of recording flow, at least once every fifteen minutes, immediately downstream of each valve that if opened would allow a vent stream to bypass the control device and be emitted, either directly or indirectly, to the atmosphere; or
 - (ii) Once a month, the permit holder shall inspect the valves checking the position of the valves and the condition of the car seals. Identify all times when the car seal has been broken and the valve position has been changed to allow a vent stream to bypass the control device and be emitted, either directly or indirectly, to the atmosphere.
 - G. The permit holder shall comply with the requirements of 40 CFR § 70.6(a)(3)(ii)(A) and 30 TAC § 122.144(1)(A)-(F) for documentation of all required inspections.
12. The permit holder shall comply with the periodic monitoring requirements as specified in the attached “Periodic Monitoring Summary” upon issuance of the permit. Except for, as applicable, monitoring malfunctions, associated repairs, and required quality assurance or control activities (including, as applicable, calibration checks and required zero and span adjustments), the permit holder shall conduct all monitoring in continuous operation (or shall collect data at all required intervals) at all times that the pollutant-specific emissions unit is operating. The permit holder may elect to collect monitoring data on a more frequent basis and average the data, consistent with the averaging time specified in the “Periodic Monitoring Summary,” for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis. In no event shall data be collected and used in particular instances to avoid reporting deviations. Deviations shall be reported according to 30 TAC § 122.145 (Reporting Terms and Conditions).

New Source Review Authorization Requirements

13. Permit holder shall comply with the requirements of New Source Review authorizations issued or claimed by the permit holder for the permitted area, including permits, permits by rule, standard permits, flexible permits, special permits, permits for existing facilities including Voluntary Emissions Reduction Permits and Electric Generating Facility Permits issued under 30 TAC Chapter 116, Subchapter I, or special exemptions referenced in the New Source Review Authorization References attachment. These requirements:
 - A. Are incorporated by reference into this permit as applicable requirements
 - B. Shall be located with this operating permit
 - C. Are not eligible for a permit shield
14. The permit holder shall comply with the general requirements of 30 TAC Chapter 106, Subchapter A or the general requirements, if any, in effect at the time of the claim of any PBR.
15. The permit holder shall maintain records to demonstrate compliance with any emission limitation or standard that is specified in a permit by rule (PBR) or Standard Permit listed in the New Source Review Authorizations attachment. The records shall yield reliable data from the relevant time period that are representative of the emission unit's compliance with the PBR or Standard Permit. These records may include, but are not limited to, production capacity and throughput, hours of operation, safety data sheets (SDS), chemical composition of raw materials, speciation of air contaminant data, engineering calculations, maintenance records, fugitive data, performance tests, capture/control device efficiencies, direct pollutant monitoring (CEMS, COMS, or PEMS), or control device parametric monitoring. These records shall be made readily accessible and available as required by 30 TAC § 122.144. Any monitoring or recordkeeping data indicating noncompliance with the PBR or Standard Permit shall be considered and reported as a deviation according to 30 TAC § 122.145 (Reporting Terms and Conditions).

Compliance Requirements

16. The permit holder shall certify compliance in accordance with 30 TAC § 122.146. The permit holder shall comply with 30 TAC § 122.146 using at a minimum, but not limited to, the continuous or intermittent compliance method data from monitoring, recordkeeping, reporting, or testing required by the permit and any other credible evidence or information. The certification period may not exceed 12 months and the certification must be submitted within 30 days after the end of the period being certified.
17. Permit holder shall comply with the following 30 TAC Chapter 117 requirements:
 - A. The permit holder shall comply with the compliance schedules and submit written notification to the TCEQ Executive Director as required in 30 TAC Chapter 117, Subchapter H, Division 1:
 - (i) For sources in the Beaumont-Port Arthur Nonattainment area, 30 TAC § 117.9000

- B. The permit holder shall comply with the Initial Control Plan unit listing requirement in 30 TAC § 117.150(c) and (c)(1).
18. Use of Emission Credits to comply with applicable requirements:
- A. Unless otherwise prohibited, the permit holder may use emission credits to comply with the following applicable requirements listed elsewhere in this permit:
 - (i) Title 30 TAC Chapter 115
 - (ii) Title 30 TAC Chapter 117
 - (iii) Offsets for Title 30 TAC Chapter 116
 - B. The permit holder shall comply with the following requirements in order to use the emission credits to comply with the applicable requirements:
 - (i) The permit holder must notify the TCEQ according to 30 TAC § 101.306(c)(2)
 - (ii) The emission credits to be used must meet all the geographic, timeliness, applicable pollutant type, and availability requirements listed in 30 TAC Chapter 101, Subchapter H, Division 1
 - (iii) The executive director has approved the use of the credit according to 30 TAC § 101.306(c)(2)
 - (iv) The permit holder keeps records of the use of credits towards compliance with the applicable requirements in accordance with 30 TAC § 101.302(g) and 30 TAC Chapter 122
19. Use of Discrete Emission Credits to comply with the applicable requirements:
- A. Unless otherwise prohibited, the permit holder may use discrete emission credits to comply with the following applicable requirements listed elsewhere in this permit:
 - (i) Title 30 TAC Chapter 115
 - (ii) Title 30 TAC Chapter 117
 - (iii) If applicable, offsets for Title 30 TAC Chapter 116
 - (iv) Temporarily exceed state NSR permit allowables
 - B. The permit holder shall comply with the following requirements in order to use the credit to comply with the applicable requirements:
 - (i) The permit holder must notify the TCEQ according to 30 TAC § 101.376(d)

- (ii) The discrete emission credits to be used must meet all the geographic, timeliness, applicable pollutant type, and availability requirements listed in 30 TAC Chapter 101, Subchapter H, Division 4
- (iii) The executive director has approved the use of the discrete emission credits according to 30 TAC § 101.376(d)(1)(A)
- (iv) The permit holder keeps records of the use of credits towards compliance with the applicable requirements in accordance with 30 TAC § 101.372(h) and 30 TAC Chapter 122

Risk Management Plan

20. For processes subject to 40 CFR Part 68 and specified in 40 CFR § 68.10, the permit holder shall comply with the requirements of the Accidental Release Prevention Provisions in 40 CFR Part 68. The permit holder shall submit to the appropriate agency either a compliance schedule for meeting the requirements of 40 CFR Part 68 by the date provided in 40 CFR § 68.10(a), or as part of the compliance certification submitted under this permit, a certification statement that the source is in compliance with all requirements of 40 CFR Part 68, including the registration and submission of a risk management plan.

Protection of Stratospheric Ozone

21. Permit holders at a site subject to Title VI of the FCAA Amendments shall meet the following requirements for protection of stratospheric ozone:
- A. Any on site servicing, maintenance, and repair on refrigeration and nonmotor vehicle air-conditioning appliances using ozone-depleting refrigerants or non-exempt substitutes shall be conducted in accordance with 40 CFR Part 82, Subpart F. Permit holders shall ensure that repairs on or refrigerant removal from refrigeration and nonmotor vehicle air-conditioning appliances using ozone-depleting refrigerants are performed only by properly certified technicians using certified equipment. Records shall be maintained as required by 40 CFR Part 82, Subpart F.

Permit Location

22. The permit holder shall maintain a copy of this permit and records related to requirements listed in this permit on site.

Permit Shield (30 TAC § 122.148)

23. A permit shield is granted for the emission units, groups, or processes specified in the attached "Permit Shield." Compliance with the conditions of the permit shall be deemed compliance with the specified potentially applicable requirements or specified potentially applicable state-only requirements listed in the attachment "Permit Shield." Permit shield provisions shall not be modified by the executive director until notification is provided to the permit holder. No later than 90 days after notification of a change in a determination made by the executive director, the permit holder shall apply for the appropriate permit revision to reflect the new determination. Provisional terms are not eligible for this permit shield. Any term or condition, under a permit shield, shall not be protected by the permit shield if it is replaced by a provisional term or condition or the basis of the term and condition changes.

Attachments

Applicable Requirements Summary

Additional Monitoring Requirements

Permit Shield

New Source Review Authorization References

Applicable Requirements Summary

Unit Summary 16

Applicable Requirements Summary 26

Note: A “none” entry may be noted for some emission sources in this permit’s “Applicable Requirements Summary” under the heading of “Monitoring and Testing Requirements” and/or “Recordkeeping Requirements” and/or “Reporting Requirements.” Such a notation indicates that there are no requirements for the indicated emission source as identified under the respective column heading(s) for the stated portion of the regulation when the emission source is operating under the conditions of the specified SOP Index Number. However, other relevant requirements pursuant to 30 TAC Chapter 122 including Recordkeeping Terms and Conditions (30 TAC § 122.144), Reporting Terms and Conditions (30 TAC § 122.145), and Compliance Certification Terms and Conditions (30 TAC § 122.146) continue to apply.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
612-D4718	STORAGE TANKS/VESSELS	N/A	R5112-0097	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
612-D4723	STORAGE TANKS/VESSELS	N/A	R5112-0097	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
612-D4725	STORAGE TANKS/VESSELS	N/A	R5112-0097	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
612-D4749	STORAGE TANKS/VESSELS	N/A	R5112-0132	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
612-D4749	STORAGE TANKS/VESSELS	N/A	60Kb-0081	40 CFR Part 60, Subpart Kb	No changing attributes.
612-D4752	STORAGE TANKS/VESSELS	N/A	R5112-0097	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
612-D4754	STORAGE TANKS/VESSELS	N/A	R5112-0097	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
612-D4758	STORAGE TANKS/VESSELS	N/A	R5112-0132	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
612-D4758	STORAGE TANKS/VESSELS	N/A	60Kb-0081	40 CFR Part 60, Subpart Kb	No changing attributes.
612-F5959	STORAGE TANKS/VESSELS	N/A	R5112-0006	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
721	FLARES	N/A	R1111-001	30 TAC Chapter 111, Visible Emissions	No changing attributes.
721	FLARES	N/A	60A-001	40 CFR Part 60, Subpart A	No changing attributes.
721	FLARES	N/A	63A-001	40 CFR Part 63, Subpart A	No changing attributes.
721	FLARES	N/A	63FFFF-1	40 CFR Part 63, Subpart	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
				FFFF	
721V	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121-8	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
858	FLARES	N/A	R1111-001	30 TAC Chapter 111, Visible Emissions	No changing attributes.
858	FLARES	N/A	63A-002	40 CFR Part 63, Subpart A	No changing attributes.
858	FLARES	N/A	63FFFF-1	40 CFR Part 63, Subpart FFFF	No changing attributes.
858V	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121-8	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
863	STORAGE TANKS/VESSELS	N/A	R5112-0019	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
863	STORAGE TANKS/VESSELS	N/A	60Kb-0068	40 CFR Part 60, Subpart Kb	No changing attributes.
B-4901	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
B-4902	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	63DDDDD-2	40 CFR Part 63, Subpart DDDDD	No changing attributes.
B-4903	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	63DDDDD-3	40 CFR Part 63, Subpart DDDDD	No changing attributes.
GRPLPTANK1	STORAGE TANKS/VESSELS	612-F4706, 612- F6640A, 612-	R5112-0006	30 TAC Chapter 115, Storage of VOCs	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
		F6640B			
GRPLPVENT4	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	401, 423, 424, 429A, 429B, 429C, 429D, 429E, 429F	R5121-4	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
GRPLPVENT6	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	641A, 642A, 642B, 642C, 642D, 642E, 642G, 642H, 643, 645, 650, 651, 652, 653, 654AB, 655AB, 656, 657, 662, 663, 664, 665, 666, 667, 668, 669, 670, 671, 672, 673, 674, 675, 676, 677, 678, 679, 680, 681, 682, 683, 684, 686, 687, 688, 689, 690, 691, 692, 695, 696, 697, 698, 699	R5121-4	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
GRPLPVENT8	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	817, 819A, 819B, 819C, 819D, 819E, 821, 845, 850, 851, 854, 855, 861, 862, 866, 867, 868, 869, 870, 871, 872, 873, 878, 879, 884, 886, 889, 891	R5121-4	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
GRPLPVENT9	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	900, 910, 911, 924, 925, 926, 927, 928, 929, 930, 931, 944, 945, 946, 947, 948,	R5121-4	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
		949, 953, 954, 955, 956, 957, 958, 959, 960, 961, 962, 963, 973, 991, 992, 993A			
LINE 45	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	63FFFF-G1CPV	40 CFR Part 63, Subpart FFFF	No changing attributes.
LINE 60	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	63FFFF-G1CPV	40 CFR Part 63, Subpart FFFF	No changing attributes.
LINE44	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	63FFFF-G1CPV	40 CFR Part 63, Subpart FFFF	No changing attributes.
LPFUG	FUGITIVE EMISSION UNITS	N/A	R5352-1	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	No changing attributes.
LPFUG	FUGITIVE EMISSION UNITS	N/A	60DDD-ALL	40 CFR Part 60, Subpart DDD	No changing attributes.
LPFUG	FUGITIVE EMISSION UNITS	N/A	LPFFFF-1	40 CFR Part 63, Subpart FFFF	No changing attributes.
M-4799	SRIC ENGINES	N/A	60III-1	40 CFR Part 60, Subpart III	No changing attributes.
M-4799	SRIC ENGINES	N/A	63ZZZZ-1	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
PROLPMR	POLYMER MANUFACTURING PROCESSES	N/A	60DDD-CVCF	40 CFR Part 60, Subpart DDD	Process Emissions = Individual vent gas streams emit continuous emissions., Uncontrolled Annual Emissions =

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					<p>Uncontrolled annual emissions are 1.6 Mg/yr (1.76 tpy) or greater., Weight Percent TOC = Weight percent of total organic compounds is 0.10% or greater., Control of Continuous Emissions = All continuous emissions are controlled in an existing control device (as defined in 40 CFR § 60.561)., Continuous Control Device = Flare., Annual Emissions Entering the Control Device = Annual emissions entering the control device are greater than or equal to the calculated threshold emissions levels calculated in Table 3., Table 3 Control Requirements = Calculations from Table 3 require controls., Emission Reduction from Control Device = Existing control device (as defined in 40 CFR § 60.561) reduces emissions by 98 percent or greater, or exit concentration is 20 ppmv or less.</p>
PROLPMR	POLYMER MANUFACTURING PROCESSES	N/A	60DDD-IVCF	40 CFR Part 60, Subpart DDD	<p>Process Emissions = Individual vent gas streams emit intermittent emissions., Emergency Vent = Emissions are not an emergency vent stream from a new, modified, or reconstructed facility., Existing</p>

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					Control Device = The vent stream is controlled in an existing control device (as defined in 40 CFR '60.561) which has not been reconstructed, replaced, or its operating conditions modified as a result of state or local regulations.
PROLPPF4AB	POLYMER MANUFACTURING PROCESSES	N/A	60DDD-CVCF	40 CFR Part 60, Subpart DDD	Uncontrolled Annual Emissions = Uncontrolled annual emissions are 1.6 Mg/yr (1.76 tpy) or greater., Control of Continuous Emissions = All continuous emissions are controlled in an existing control device (as defined in 40 CFR § 60.561)., Continuous Control Device = Flare., Annual Emissions Entering the Control Device = Annual emissions entering the control device are greater than or equal to the calculated threshold emissions levels calculated in Table 3., Table 3 Control Requirements = Calculations from Table 3 require controls., Emission Reduction from Control Device = Existing control device (as defined in 40 CFR § 60.561) reduces emissions by 98 percent or greater, or exit concentration is 20 ppmv or less.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
PROLPPF4AB	POLYMER MANUFACTURING PROCESSES	N/A	60DDD-CVU1	40 CFR Part 60, Subpart DDD	Polyolefin Production = Only one polyolefin is produced or no polyolefin is produced. Uncontrolled Annual Emissions = Uncontrolled annual emissions are less than 1.6 Mg/yr (1.76 tpy)., Control of Continuous Emissions = Vent gas stream emissions are not controlled with an existing control device (as defined in 40 CFR § 60.561).
PROLPPF4AB	POLYMER MANUFACTURING PROCESSES	N/A	60DDD-CVU2	40 CFR Part 60, Subpart DDD	Polyolefin Production = Only one polyolefin is produced or no polyolefin is produced., Uncontrolled Annual Emissions = Uncontrolled annual emissions are 1.6 Mg/yr (1.76 tpy) or greater., Control of Continuous Emissions = Vent gas stream emissions are not controlled with an existing control device (as defined in 40 CFR § 60.561)., Continuous Control Device = Flare., Table 3 Control Requirements = Calculations from Table 3 do not require controls.
PROLPRMP	POLYMER MANUFACTURING PROCESSES	N/A	60DDD-CVCF	40 CFR Part 60, Subpart DDD	Table 2 Threshold Emission Rates = The uncontrolled emission rate is greater than the uncontrolled threshold emission rates in Table 2 of 40 CFR § 60.560., Process Emissions =

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					<p>Individual vent gas streams emit continuous emissions., Uncontrolled Annual Emissions = Uncontrolled annual emissions are 1.6 Mg/yr (1.76 tpy) or greater., Weight Percent TOC = Weight percent of total organic compounds is 0.10% or greater., Control of Continuous Emissions = All continuous emissions are controlled in an existing control device (as defined in 40 CFR § 60.561)., Continuous Control Device = Flare., Annual Emissions Entering the Control Device = Annual emissions entering the control device are greater than or equal to the calculated threshold emissions levels calculated in Table 3., Table 3 Control Requirements = Calculations from Table 3 require controls., Emission Reduction from Control Device = Existing control device (as defined in 40 CFR § 60.561) reduces emissions by 98 percent or greater, or exit concentration is 20 ppmv or less.</p>
PROLPRMP	POLYMER MANUFACTURING PROCESSES	N/A	60DDD-IVCF	40 CFR Part 60, Subpart DDD	Table 2 Threshold Emission Rates = The uncontrolled emission rate is greater than the uncontrolled threshold emission

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					<p>rates in Table 2 of 40 CFR § 60.560., Process Emissions = Individual vent gas streams emit intermittent emissions., Emergency Vent = Emissions are not an emergency vent stream from a new, modified, or reconstructed facility., Existing Control Device = The vent stream is controlled in an existing control device (as defined in 40 CFR ' 60.561) which has not been reconstructed, replaced, or its operating conditions modified as a result of state or local regulations., Intermittent Control Device = Flare.</p>
PROLPRMP	POLYMER MANUFACTURING PROCESSES	N/A	60DDD-IVU	40 CFR Part 60, Subpart DDD	<p>Table 2 Threshold Emission Rates = The uncontrolled emission rate is less than or equal to the uncontrolled threshold emission rates in Table 2 of 40 CFR § 60.560., Process Emissions = Individual vent gas streams emit continuous emissions., Uncontrolled Annual Emissions = Uncontrolled annual emissions are 1.6 Mg/yr (1.76 tpy) or greater., Weight Percent TOC = Weight percent of total organic compounds is 0.10% or greater.</p>

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
PROLPRX60	POLYMER MANUFACTURING PROCESSES	N/A	60DDD-EV	40 CFR Part 60, Subpart DDD	Table 2 Threshold Emission Rates = The uncontrolled emission rate is less than or equal to the uncontrolled threshold emission rates in Table 2 of 40 CFR § 60.560., Emergency Vent = Emissions are an emergency vent stream from a new, modified, or reconstructed facility.
PROLPRX60	POLYMER MANUFACTURING PROCESSES	N/A	60DDD-IVCF	40 CFR Part 60, Subpart DDD	Table 2 Threshold Emission Rates = The uncontrolled emission rate is greater than the uncontrolled threshold emission rates in Table 2 of 40 CFR § 60.560., Emergency Vent = Emissions are not an emergency vent stream from a new, modified, or reconstructed facility., Existing Control Device = The vent stream is controlled in an existing control device (as defined in 40 CFR ' 60.561) which has not been reconstructed, replaced, or its operating conditions modified as a result of state or local regulations., Intermittent Control Device = Flare.

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
612-D4718	EU	R5112-0097	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(a)(1) § 115.112(a)(3) § 60.18	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	§ 115.115(a) § 115.115(a)(6) § 115.116(a)(2) [G]§ 115.117	§ 115.118(a)(4) § 115.118(a)(4)(F) § 115.118(a)(5) § 115.118(a)(7)	None
612-D4723	EU	R5112-0097	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(a)(1) § 115.112(a)(3) § 60.18	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	§ 115.115(a) § 115.115(a)(6) § 115.116(a)(2) [G]§ 115.117	§ 115.118(a)(4) § 115.118(a)(4)(F) § 115.118(a)(5) § 115.118(a)(7)	None
612-D4725	EU	R5112-0097	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(a)(1) § 115.112(a)(3) § 60.18	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	§ 115.115(a) § 115.115(a)(6) § 115.116(a)(2) [G]§ 115.117	§ 115.118(a)(4) § 115.118(a)(4)(F) § 115.118(a)(5) § 115.118(a)(7)	None
612-D4749	EU	R5112-0132	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(a)(1) § 115.112(a)(3) § 60.18	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	§ 115.115(a) § 115.115(a)(6) § 115.116(a)(2) [G]§ 115.117	§ 115.118(a)(4) § 115.118(a)(4)(F) § 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
612-D4749	EU	60Kb-0081	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(b)(1) § 60.18	Storage vessels specified in §60.112b(b) and equipped with a closed vent system and control device are to meet the specifications in §60.112b(a)(3).	§ 60.113b(d) § 60.116b(a) § 60.116b(b) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3) [G]§ 60.485(b) ** See Periodic Monitoring Summary	§ 60.115b § 60.115b(d)(2) § 60.116b(a) § 60.116b(b)	§ 60.115b § 60.115b(d)(1) § 60.115b(d)(3)
612-D4752	EU	R5112-0097	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(a)(1) § 115.112(a)(3) § 60.18	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	§ 115.115(a) § 115.115(a)(6) § 115.116(a)(2) [G]§ 115.117	§ 115.118(a)(4) § 115.118(a)(4)(F) § 115.118(a)(5) § 115.118(a)(7)	None
612-D4754	EU	R5112-0097	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(a)(1) § 115.112(a)(3) § 60.18	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	§ 115.115(a) § 115.115(a)(6) § 115.116(a)(2) [G]§ 115.117	§ 115.118(a)(4) § 115.118(a)(4)(F) § 115.118(a)(5) § 115.118(a)(7)	None
612-D4758	EU	R5112-0132	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(a)(1) § 115.112(a)(3) § 60.18	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table	§ 115.115(a) § 115.115(a)(6) § 115.116(a)(2) [G]§ 115.117	§ 115.118(a)(4) § 115.118(a)(4)(F) § 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						II(a).			
612-D4758	EU	60Kb-0081	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(b)(1) § 60.18	Storage vessels specified in §60.112b(b) and equipped with a closed vent system and control device are to meet the specifications in §60.112b(a)(3).	§ 60.113b(d) § 60.116b(a) § 60.116b(b) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3) [G]§ 60.485(b) ** See Periodic Monitoring Summary	§ 60.115b § 60.115b(d)(2) § 60.116b(a) § 60.116b(b)	§ 60.115b § 60.115b(d)(1) § 60.115b(d)(3)
612-F5959	EU	R5112-0006	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
721	EU	R1111-001	PM (OPACITY)	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(4)(A)	Visible emissions from a process gas flare shall not be permitted for more than five minutes in any two-hour period, except for upset emissions as provided in §101.11(a).	§ 111.111(a)(4)(A)(i) § 111.111(a)(4)(A)(ii)	§ 111.111(a)(4)(A)(ii)	None
721	CD	60A-001	OPACITY	40 CFR Part 60, Subpart A	§ 60.18(b) § 60.18(c)(1) § 60.18(c)(2) § 60.18(c)(3)(ii) § 60.18(c)(5) § 60.18(c)(6) § 60.18(e)	Flares shall comply with paragraphs (c)-(f) of § 60.18.	§ 60.18(d) § 60.18(f)(1) § 60.18(f)(2) § 60.18(f)(3) § 60.18(f)(6)	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
721	CD	63A-001	112(B) HAPS	40 CFR Part 63, Subpart A	§ 63.11(b)(4) § 63.11(b)(1) § 63.11(b)(2) § 63.11(b)(3) § 63.11(b)(5) § 63.11(b)(6)(ii) § 63.11(b)(8)	Flares shall be designed and operated with no visible emissions, except for periods of a total of 5 minutes or less during any 2 consecutive hrs. Test Method 22 in App. A of part 60 of this chapter shall be used.	§ 63.11(b)(4) § 63.11(b)(5)	None	None
721	CD	63FFFF-1	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2450(e)(2) § 63.2450(k)(2) § 63.2470(d) § 63.982(b) § 63.987(a) § 63.996(a) § 63.996(a)(2)	Except when complying with §63.2485, if you reduce organic HAP emissions by venting emissions through a closed vent system to a flare, you must meet the requirements of §63.982(b) from 40 CFR 63, Subpart SS and the requirements referenced therein.	§ 63.2450(f) § 63.2450(k) § 63.2450(l) § 63.987(b) § 63.987(b)(3) § 63.987(b)(3)(i) § 63.987(b)(3)(ii) § 63.987(b)(3)(iii) § 63.987(b)(3)(iv) § 63.987(c) § 63.997(a) [G]§ 63.997(b) § 63.997(c) § 63.997(c)(1) § 63.997(c)(1)(iii) § 63.997(c)(1)(v) § 63.997(c)(2) § 63.997(c)(3) § 63.997(c)(3)(i)	[G]§ 63.2450(f)(2) § 63.987(b) § 63.987(b)(1) § 63.998(a) [G]§ 63.998(a)(1) § 63.998(b) [G]§ 63.998(b)(1) [G]§ 63.998(b)(2) [G]§ 63.998(b)(3) § 63.998(b)(6)(i) § 63.998(b)(6)(i)(A) [G]§ 63.998(d)(2)	§ 63.2450(f)(2)(ii) § 63.987(b)(1) § 63.999(a) [G]§ 63.999(a)(1) § 63.999(a)(2) § 63.999(a)(2)(i) § 63.999(a)(2)(ii) § 63.999(a)(2)(iii) § 63.999(a)(2)(iii)(A) § 63.999(b)(5) § 63.999(c)(1) § 63.999(c)(3)
721V	EP	R5121-8	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(a)(1) § 115.121(a)(1) § 115.122(a)(1)(B) § 60.18	Vent gas affected by §115.121(a)(1) must be controlled properly with a control efficiency > 90% or to a VOC concentration of no more than 20	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2) ** See CAM Summary	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						ppmv (dry, corrected to 3% O2 for combustion devices).			
858	EU	R1111-001	PM (OPACITY)	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(4)(A)	Visible emissions from a process gas flare shall not be permitted for more than five minutes in any two-hour period, except for upset emissions as provided in §101.11(a).	§ 111.111(a)(4)(A)(i) § 111.111(a)(4)(A)(ii)	§ 111.111(a)(4)(A)(ii)	None
858	CD	63A-002	112(B) HAPS	40 CFR Part 63, Subpart A	§ 63.11(b)(4) § 63.11(b)(1) § 63.11(b)(2) § 63.11(b)(3) § 63.11(b)(5) § 63.11(b)(6)(ii) § 63.11(b)(7)(i)	Flares shall be designed and operated with no visible emissions, except for periods of a total of 5 minutes or less during any 2 consecutive hrs. Test Method 22 in App. A of part 60 of this chapter shall be used.	§ 63.11(b)(4) § 63.11(b)(5) § 63.11(b)(7)(i)	None	None
858	CD	63FFFF-1	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2450(e)(2) § 63.2450(k)(2) § 63.2470(d) § 63.982(b) § 63.987(a) § 63.996(a) § 63.996(a)(2)	Except when complying with §63.2485, if you reduce organic HAP emissions by venting emissions through a closed vent system to a flare, you must meet the requirements of §63.982(b) from 40 CFR 63, Subpart SS and the requirements referenced therein.	§ 63.2450(f) § 63.2450(k) § 63.2450(l) § 63.987(b) § 63.998(a) § 63.987(b)(3) § 63.987(b)(3)(i) § 63.987(b)(3)(ii) § 63.987(b)(3)(iii) § 63.987(b)(3)(iv) § 63.987(c) § 63.997(a) [G]§ 63.997(b) § 63.997(c)	[G]§ 63.2450(f)(2) § 63.987(b) § 63.987(b)(1) § 63.998(a) [G]§ 63.998(a)(1) § 63.998(b) [G]§ 63.998(b)(1) [G]§ 63.998(b)(2) [G]§ 63.998(b)(3) § 63.998(b)(6)(i) § 63.998(b)(6)(i)(A) [G]§ 63.998(d)(2)	§ 63.2450(f)(2)(ii) § 63.987(b) § 63.987(b)(1) § 63.999(a) [G]§ 63.999(a)(1) § 63.999(a)(2) § 63.999(a)(2)(i) § 63.999(a)(2)(ii) § 63.999(a)(2)(iii) § 63.999(a)(2)(iii)(A) § 63.999(b)(5) § 63.999(c)(1) § 63.999(c)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 63.997(c)(1) § 63.997(c)(1)(iii) § 63.997(c)(1)(v) § 63.997(c)(2) § 63.997(c)(3) § 63.997(c)(3)(i)		
858V	EP	R5121-8	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(a)(1) § 115.121(a)(1) § 115.122(a)(1)(B) § 60.18	Vent gas affected by §115.121(a)(1) must be controlled properly with a control efficiency > 90% or to a VOC concentration of no more than 20 ppmv (dry, corrected to 3% O2 for combustion devices).	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2) ** See CAM Summary	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None
863	EU	R5112-0019	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(a)(1) § 115.112(a)(2) § 115.112(a)(2)(A) § 115.112(a)(2)(B) § 115.112(a)(2)(C) § 115.112(a)(2)(D) § 115.112(a)(2)(E) § 115.114(a)(1)(A)	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(7)	§ 115.114(a)(1)(B) § 115.118(a)(3)
863	EU	60Kb-0068	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(B) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) [G]§ 60.113b(a)(3) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
B-4901	EU	63DDDD D-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7500(a)(1)-Table 3.1 § 63.7495(b) § 63.7495(h) § 63.7499(l) § 63.7500(a) § 63.7500(a)(3) § 63.7500(e) § 63.7505(a) § 63.7510(e) § 63.7515(d) § 63.7540(a) § 63.7540(a)(12) § 63.7540(a)(13) § 63.7565	A new or existing boiler or process heater with a continuous oxygen trim system that maintains an optimum air to fuel ratio, or a heat input capacity of less than or equal to 5 million Btu per hour in any of the following subcategories: unit designed to burn gas 1; unit designed to burn gas 2 (other); or unit designed to burn light liquid, or a limited use boiler or process heater. You must Conduct a tune-up of the boiler or process heater every 5 years as specified in §63.7540.	§ 63.7521(f) § 63.7521(f)(1) § 63.7521(f)(2) § 63.7521(g) § 63.7521(g)(1) § 63.7521(g)(2) § 63.7521(g)(2)(i) § 63.7521(g)(2)(ii) § 63.7521(g)(2)(iii) § 63.7521(g)(2)(iv) § 63.7521(g)(2)(v) § 63.7521(h) § 63.7521(i) § 63.7530(g) § 63.7540(a)(10)(i) § 63.7540(a)(10)(ii) § 63.7540(a)(10)(iii) § 63.7540(a)(10)(iv) § 63.7540(a)(10)(v) § 63.7540(c) § 63.7540(c)(4)	§ 63.7530(g) [G]§ 63.7540(a)(10)(vi) § 63.7555(a) § 63.7555(a)(1) [G]§ 63.7560	§ 63.7495(d) § 63.7530(e) [G]§ 63.7540(a)(10)(vi) § 63.7545(a) § 63.7545(b) § 63.7545(e) § 63.7545(e)(1) § 63.7545(e)(8) § 63.7545(e)(8)(i) § 63.7545(e)(8)(ii) § 63.7550(a) [G]§ 63.7550(b) § 63.7550(c) § 63.7550(c)(1) § 63.7550(c)(5)(i) § 63.7550(c)(5)(ii) § 63.7550(c)(5)(iii) § 63.7550(c)(5)(iv) § 63.7550(c)(5)(xiv) § 63.7550(c)(5)(xvii) § 63.7550(h) § 63.7550(h)(3)
B-4902	EU	63DDDD D-2	VOC	40 CFR Part 63, Subpart DDDDD	§ 63.7500(a)(1)-Table 3.1 § 63.7495(b) § 63.7495(h) § 63.7499(l) § 63.7500(a) § 63.7500(a)(3) § 63.7500(e) § 63.7505(a) § 63.7510(e) § 63.7515(d) § 63.7540(a) § 63.7540(a)(12)	A new or existing boiler or process heater with a continuous oxygen trim system that maintains an optimum air to fuel ratio, or a heat input capacity of less than or equal to 5 million Btu per hour in any of the following subcategories: unit designed to burn gas	§ 63.7521(f) § 63.7521(f)(1) § 63.7521(f)(2) § 63.7521(g) § 63.7521(g)(1) § 63.7521(g)(2) § 63.7521(g)(2)(i) § 63.7521(g)(2)(ii) § 63.7521(g)(2)(iii) § 63.7521(g)(2)(iv) § 63.7521(g)(2)(v) § 63.7521(h) § 63.7521(i)	§ 63.7530(g) [G]§ 63.7540(a)(10)(vi) § 63.7555(a) § 63.7555(a)(1) [G]§ 63.7560	§ 63.7495(d) § 63.7530(e) [G]§ 63.7540(a)(10)(vi) § 63.7545(a) § 63.7545(b) § 63.7545(e) § 63.7545(e)(1) § 63.7545(e)(8) § 63.7545(e)(8)(i) § 63.7545(e)(8)(ii) § 63.7550(a) [G]§ 63.7550(b) § 63.7550(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.7540(a)(13) § 63.7565	1; unit designed to burn gas 2 (other); or unit designed to burn light liquid, or a limited use boiler or process heater. You must Conduct a tune-up of the boiler or process heater every 5 years as specified in §63.7540.	§ 63.7530(g) § 63.7540(a)(10)(i) § 63.7540(a)(10)(ii) § 63.7540(a)(10)(iii) § 63.7540(a)(10)(iv) § 63.7540(a)(10)(v) § 63.7540(c) § 63.7540(c)(4)		§ 63.7550(c)(1) § 63.7550(c)(5)(i) § 63.7550(c)(5)(ii) § 63.7550(c)(5)(iii) § 63.7550(c)(5)(iv) § 63.7550(c)(5)(xiv) § 63.7550(c)(5)(xvii) § 63.7550(h) § 63.7550(h)(3)
B-4903	EU	63DDDD D-3	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7500(a)(1)- Table 3.1 § 63.7495(b) § 63.7495(h) § 63.7499(l) § 63.7500(a) § 63.7500(a)(3) § 63.7500(e) § 63.7505(a) § 63.7510(e) § 63.7515(d) § 63.7540(a) § 63.7540(a)(12) § 63.7540(a)(13) § 63.7565	A new or existing boiler or process heater with a continuous oxygen trim system that maintains an optimum air to fuel ratio, or a heat input capacity of less than or equal to 5 million Btu per hour in any of the following subcategories: unit designed to burn gas 1; unit designed to burn gas 2 (other); or unit designed to burn light liquid, or a limited use boiler or process heater. You must Conduct a tune-up of the boiler or process heater every 5 years as specified in §63.7540.	§ 63.7521(f) § 63.7521(f)(1) § 63.7521(f)(2) § 63.7521(g) § 63.7521(g)(1) § 63.7521(g)(2) § 63.7521(g)(2)(i) § 63.7521(g)(2)(ii) § 63.7521(g)(2)(iii) § 63.7521(g)(2)(iv) § 63.7521(g)(2)(v) § 63.7521(h) § 63.7521(i) § 63.7530(g) § 63.7540(a)(10)(i) § 63.7540(a)(10)(ii) § 63.7540(a)(10)(iii) § 63.7540(a)(10)(iv) § 63.7540(a)(10)(v) § 63.7540(c) § 63.7540(c)(4)	§ 63.7530(g) [G]§ 63.7540(a)(10)(vi) § 63.7555(a) § 63.7555(a)(1) [G]§ 63.7560	§ 63.7495(d) § 63.7530(e) [G]§ 63.7540(a)(10)(vi) § 63.7545(a) § 63.7545(b) § 63.7545(e) § 63.7545(e)(1) § 63.7545(e)(8) § 63.7545(e)(8)(i) § 63.7545(e)(8)(ii) § 63.7550(a) [G]§ 63.7550(b) § 63.7550(c) § 63.7550(c)(1) § 63.7550(c)(5)(i) § 63.7550(c)(5)(ii) § 63.7550(c)(5)(iii) § 63.7550(c)(5)(iv) § 63.7550(c)(5)(xiv) § 63.7550(c)(5)(xvii) § 63.7550(h) § 63.7550(h)(3)
GRPLPTAN K1	EU	R5112- 0006	VOC	30 TAC Chapter 115, Storage of	§ 115.111(a)(1)	Except as provided in § 115.118, a storage	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				VOCs		tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.		§ 115.118(a)(7)	
GRPLPVENT 4	EP	R5121-4	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	§ 115.125(1) [G]§ 115.125(2) § 115.125(4) § 115.125(5) § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
GRPLPVENT 6	EP	R5121-4	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	§ 115.125(1) [G]§ 115.125(2) § 115.125(4) § 115.125(5) § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
GRPLPVENT 8	EP	R5121-4	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	§ 115.125(1) [G]§ 115.125(2) § 115.125(4) § 115.125(5) § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRPLPVENT 9	EP	R5121-4	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	§ 115.125(1) [G]§ 115.125(2) § 115.125(4) § 115.125(5) § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
LINE 45	EP	63FFFF-G1CPV	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2455(a)-Table 1.1.a.ii § 63.2450(e)(2) § 63.2455(a) § 63.2455(b) § 63.2455(b)(1) § 63.2470(c)(2) § 63.982(b) § 63.983(a)(1) § 63.983(a)(2) § 63.983(a)(3) § 63.983(a)(3)(ii) § 63.983(d)(1) § 63.983(d)(1)(i) [G]§ 63.983(d)(2) § 63.983(d)(3)	For each Group I continuous process vent, the owner or operator must reduce emissions of total organic HAP by venting emissions through a closed vent system to a flare.	§ 63.983(a)(3) § 63.983(a)(3)(ii) § 63.983(b) § 63.983(b)(1) [G]§ 63.983(b)(1)(i) [G]§ 63.983(b)(2) [G]§ 63.983(b)(3) § 63.983(b)(4) § 63.983(b)(4)(ii) [G]§ 63.983(c)(1) § 63.983(c)(2) § 63.983(c)(3) § 63.983(d)(1) § 63.983(d)(1)(ii)	§ 63.983(a)(3)(ii) § 63.983(b) [G]§ 63.983(d)(2) § 63.998(a)(1)(ii) § 63.998(d)(1) § 63.998(d)(1)(i) § 63.998(d)(1)(ii) § 63.998(d)(1)(ii)(B) [G]§ 63.998(d)(1)(iii) § 63.998(d)(1)(iv) [G]§ 63.998(d)(2) § 63.998(d)(3)(i) § 63.998(d)(3)(ii)	§ 63.997(c)(3) § 63.999(c) § 63.999(c)(1) § 63.999(c)(2)(i) § 63.999(c)(2)(iii) § 63.999(c)(3)
LINE 60	EP	63FFFF-G1CPV	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2455(a)-Table 1.1.a.ii § 63.2450(e)(2) § 63.2455(a) § 63.2455(b) § 63.2455(b)(1) § 63.2470(c)(2) § 63.982(b) § 63.983(a)(1) § 63.983(a)(2) § 63.983(a)(3)	For each Group I continuous process vent, the owner or operator must reduce emissions of total organic HAP by venting emissions through a closed vent system to a flare.	§ 63.983(a)(3) § 63.983(a)(3)(ii) § 63.983(b) § 63.983(b)(1) [G]§ 63.983(b)(1)(i) [G]§ 63.983(b)(2) [G]§ 63.983(b)(3) § 63.983(b)(4) § 63.983(b)(4)(ii) [G]§ 63.983(c)(1) § 63.983(c)(2)	§ 63.983(a)(3)(ii) § 63.983(b) [G]§ 63.983(d)(2) § 63.998(a)(1)(ii) § 63.998(d)(1) § 63.998(d)(1)(i) § 63.998(d)(1)(ii) § 63.998(d)(1)(ii)(B) [G]§ 63.998(d)(1)(iii) § 63.998(d)(1)(iv) [G]§ 63.998(d)(2)	§ 63.997(c)(3) § 63.999(c) § 63.999(c)(1) § 63.999(c)(2)(i) § 63.999(c)(2)(iii) § 63.999(c)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.983(a)(3)(ii) § 63.983(d)(1) § 63.983(d)(1)(i) [G]§ 63.983(d)(2) § 63.983(d)(3)		§ 63.983(c)(3) § 63.983(d)(1) § 63.983(d)(1)(ii)	§ 63.998(d)(3)(i) § 63.998(d)(3)(ii)	
LINE44	EP	63FFFF-G1CPV	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2455(a)-Table 1.1.a.ii § 63.2450(e)(2) § 63.2455(a) § 63.2455(b) § 63.2455(b)(1) § 63.2470(c)(2) § 63.982(b) § 63.983(a)(1) § 63.983(a)(2) § 63.983(a)(3) § 63.983(a)(3)(ii) § 63.983(d)(1) § 63.983(d)(1)(i) [G]§ 63.983(d)(2) § 63.983(d)(3)	For each Group I continuous process vent, the owner or operator must reduce emissions of total organic HAP by venting emissions through a closed vent system to a flare.	§ 63.983(a)(3) § 63.983(a)(3)(ii) § 63.983(b) § 63.983(b)(1) [G]§ 63.983(b)(1)(i) [G]§ 63.983(b)(2) [G]§ 63.983(b)(3) § 63.983(b)(4) § 63.983(b)(4)(ii) [G]§ 63.983(c)(1) § 63.983(c)(2) § 63.983(c)(3) § 63.983(d)(1) § 63.983(d)(1)(ii)	§ 63.983(a)(3)(ii) § 63.983(b) [G]§ 63.983(d)(2) § 63.998(a)(1)(ii) § 63.998(d)(1) § 63.998(d)(1)(i) § 63.998(d)(1)(ii) § 63.998(d)(1)(ii)(B) [G]§ 63.998(d)(1)(iii) § 63.998(d)(1)(iv) [G]§ 63.998(d)(2) § 63.998(d)(3)(i) § 63.998(d)(3)(ii)	§ 63.997(c)(3) § 63.999(c) § 63.999(c)(1) § 63.999(c)(2)(i) § 63.999(c)(2)(iii) § 63.999(c)(3)
LPFUG	EU	R5352-1	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(6)	Components at a petroleum refinery or synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process, that contact a process fluid that contains less than 10% VOC by weight and components at a natural gas/gasoline processing operation that contact a process fluid that contains	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						less than 1.0% VOC by weight are exempt from the requirements of this division except §115.356(3)(C) of this title.			
LPFUG	EU	R5352-1	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(10)	Instrumentation systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet 40 CFR §63.169 (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
LPFUG	EU	R5352-1	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(11)	Sampling connection systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet the requirements of 40 CFR §63.166(a) and (b) (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
LPFUG	EU	R5352-1	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(13)	Components/systems that contact a process fluid containing VOC having a true vapor pressure equal to or less than 0.002 psia at	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						68 degrees Fahrenheit are exempt from the requirements of this division except §115.356(3)(C) of this title.			
LPFUG	EU	R5352-1	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(2) § 115.352(9)	Each pressure relief valve equipped with a rupture disk must comply with §115.352(9) and §115.356(3)(C).	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
LPFUG	EU	R5352-1	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7) § 115.357(1)	No process drains contacting an affected VOC wastewater stream with a VOC TVP less than or equal to 0.044 psia shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(1)(A) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) § 115.356(2) § 115.356(2)(A) § 115.356(2)(B) [G]§ 115.356(2)(E) § 115.356(2)(F) [G]§ 115.356(2) [G]§ 115.356(3) § 115.356(5)	None
LPFUG	EU	R5352-1	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3)	No process drains contacting an affected VOC wastewater stream with a VOC TVP greater than	[G]§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(7)	0.044 psia shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	[G]§ 115.355	§ 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(5)	
LPFUG	EU	R5352-1	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(9) § 115.357(1) § 115.357(8) § 115.357(9)	No pressure relief valves contacting a process fluid less than or equal to 0.044 psia shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) § 115.356(2) § 115.356(2)(A) § 115.356(2)(B) § 115.356(2)(C) [G]§ 115.356(2)(E) § 115.356(2)(F) [G]§ 115.356(3) § 115.356(5)	None
LPFUG	EU	R5352-1	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3)	No pressure relief valves contacting a process fluid greater than 0.044 psia shall be allowed to have a VOC leak, for more	§ 115.354(1) § 115.354(1)(B) § 115.354(1)(C) § 115.354(10) § 115.354(2) § 115.354(2)(D)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) [G]§ 115.356(3)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(5) § 115.352(7) § 115.352(9) § 115.357(12) § 115.357(8) § 115.357(9)	than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(4) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.356(5)	
LPFUG	EU	R5352-1	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(8) § 115.357(9)	No open-ended valves or lines contacting a process fluid less than or equal to 0.044 psia shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(1)(A) § 115.354(1)(B) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) § 115.356(2) § 115.356(2)(A) § 115.356(2)(B) § 115.356(2)(C) [G]§ 115.356(2)(E) § 115.356(2)(F) [G]§ 115.356(3) § 115.356(5)	None
LPFUG	EU	R5352-1	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6)	No open-ended valves or lines contacting a process fluid greater than 0.044 psia shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening	§ 115.354(1) § 115.354(1)(A) § 115.354(1)(B) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) [G]§ 115.356(3) § 115.356(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(7) § 115.357(12) § 115.357(8) § 115.357(9)	concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.			
LPFUG	EU	R5352-1	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(8) § 115.357(9)	No valves contacting a process fluid less than or equal to 0.044 psia shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(1)(B) § 115.354(1)(C) § 115.354(2) § 115.354(2)(C) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) [G]§ 115.356(3) § 115.356(5)	None
LPFUG	EU	R5352-1	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8) § 115.357(9)	No valves contacting a process fluid greater than 0.044 psia shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the	§ 115.354(1) § 115.354(1)(B) § 115.354(1)(C) § 115.354(10) § 115.354(2) § 115.354(2)(C) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) [G]§ 115.356(3) § 115.356(5)	[G]§ 115.354(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						dripping or exuding of process fluid based on sight, smell, or sound.			
LPFUG	EU	R5352-1	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(8) § 115.357(1) § 115.357(12) § 115.357(8)	No flanges or other connectors contacting a process fluid less than or equal to 0.044 psia shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(1)(B) § 115.354(1)(C) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) [G]§ 115.356(3) § 115.356(5)	None
LPFUG	EU	R5352-1	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(8) § 115.357(12) § 115.357(8)	No flanges or other connectors contacting a process fluid greater than 0.044 psia shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(1)(B) § 115.354(1)(C) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) [G]§ 115.356(3) § 115.356(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
LPFUG	EU	R5352-1	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(7) § 115.357(12) § 115.357(8)	No agitators contacting a process fluid greater than 0.044 psia shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) [G]§ 115.356(3) § 115.356(5)	None
LPFUG	EU	R5352-1	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(4) § 115.357(8)	No compressor seals contacting a process fluid greater than 0.044 psia shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) § 115.356(2) § 115.356(2)(A) § 115.356(2)(B) [G]§ 115.356(3) § 115.356(5)	None
LPFUG	EU	R5352-1	VOC	30 TAC Chapter 115, Pet. Refinery &	§ 115.352(1)(B) § 115.352(1) § 115.352(2)	No compressor seals contacting a process fluid greater than	§ 115.354(1) § 115.354(1)(B) § 115.354(1)(C)	§ 115.352(7) § 115.354(10) § 115.356	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Petrochemicals	§ 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	0.044 psia shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(10) § 115.354(2) § 115.354(2)(A) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	[G]§ 115.356(1) [G]§ 115.356(2) [G]§ 115.356(3) § 115.356(5)	
LPFUG	EU	R5352-1	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(4) § 115.357(8)	No pump seals equipped with a shaft sealing system shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) § 115.356(2) § 115.356(2)(A) § 115.356(2)(B) [G]§ 115.356(2)(E) § 115.356(2)(F) [G]§ 115.356(3) § 115.356(5)	None
LPFUG	EU	R5352-1	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i)	No pump seals contacting a process fluid less than or equal to 0.044 psia shall be allowed to have a VOC leak, for more than 15 days	§ 115.354(1) § 115.354(1)(B) § 115.354(1)(C) § 115.354(2) § 115.354(2)(B) § 115.354(5) § 115.354(6)	§ 115.352(7) § 115.356 [G]§ 115.356(1) § 115.356(2) § 115.356(2)(A) § 115.356(2)(B) [G]§ 115.356(2)(E)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1) § 115.357(8)	after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.356(2)(F) [G]§ 115.356(3) § 115.356(5)	
LPFUG	EU	R5352-1	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	No pump seals contacting a process fluid greater than 0.044 psia shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(1)(B) § 115.354(1)(C) § 115.354(10) § 115.354(2) § 115.354(2)(B) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) [G]§ 115.356(3) § 115.356(5)	None
LPFUG	EU	60DDD-ALL	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-2(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-2 [G]§ 60.482-9 § 60.562-2(d) § 60.562-2(e)	Comply with the requirements as stated in §60.482-2 for pumps in light-liquid service.	[G]§ 60.482-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.565(l)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
LPFUG	EU	60DDD-ALL	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-2(a) § 60.482-1(a) § 60.482-1(b) § 60.482-10(e) [G]§ 60.482-10(g) § 60.482-10(h) § 60.482-10(m) § 60.562-2(d) § 60.562-2(e)	Comply with the requirements in as stated in §60.482-10 for closed-vent systems.	[G]§ 60.482-10(f) § 60.482-10(i) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.482-10(j) [G]§ 60.482-10(k) [G]§ 60.482-10(l) [G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.565(l)
LPFUG	EU	60DDD-ALL	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-2(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-3 [G]§ 60.482-9 § 60.562-2(d) § 60.562-2(e)	Comply with the requirements as stated in §60.482-3 for compressors.	[G]§ 60.482-3 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.565(l)
LPFUG	EU	60DDD-ALL	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-2(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-4 [G]§ 60.482-9 § 60.562-2(d) § 60.562-2(e)	Comply with the requirements in as stated in §60.482-4 for pressure relief devices in gas/vapor service.	[G]§ 60.482-4 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(3) [G]§ 60.486(e)(4) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.565(l)
LPFUG	EU	60DDD-ALL	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-2(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-5 [G]§ 60.482-9 § 60.562-2(d) § 60.562-2(e)	Comply with the requirements in as stated in §60.482-5 for sampling connection systems.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.565(l)
LPFUG	EU	60DDD-ALL	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-2(a) § 60.482-1(a) § 60.482-1(b)	Comply with the requirements in as stated in §60.482-6	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 60.482-6 [G]§ 60.482-9 § 60.562-2(d) § 60.562-2(e)	for open-ended valves and lines.	§ 60.485(f)	§ 60.486(j)	§ 60.487(e) § 60.565(l)
LPFUG	EU	60DDD-ALL	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-2(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-7 [G]§ 60.482-9 [G]§ 60.483-1 [G]§ 60.483-2 § 60.562-2(b) § 60.562-2(d) § 60.562-2(e)	Comply with the requirements in as stated in §60.482-7 for valves in gas/vapor or light-liquid service.	[G]§ 60.482-7 [G]§ 60.483-1 [G]§ 60.483-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) [G]§ 60.486(g) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(d) § 60.487(e) § 60.565(l)
LPFUG	EU	60DDD-ALL	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-2(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 60.562-2(d) § 60.562-2(e)	Comply with the requirements in as stated in §60.482-8 for pumps in heavy-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.565(l)
LPFUG	EU	60DDD-ALL	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-2(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 60.562-2(d) § 60.562-2(e)	Comply with the requirements in as stated in §60.482-8 for valves in heavy-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.565(l)
LPFUG	EU	60DDD-ALL	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-2(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 60.562-2(d) § 60.562-2(e)	Comply with the requirements in as stated in §60.482-8 for pressure relief devices in light-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.565(l)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
LPFUG	EU	60DDD-ALL	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-2(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 60.562-2(d) § 60.562-2(e)	Comply with the requirements in as stated in §60.482-8 for flanges or other connectors.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.565(l)
LPFUG	EU	60DDD-ALL	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-2(a) § 60.482-1(d) § 60.562-2(e)	Comply with the requirements as stated in §60.482-1(d) for equipment in vacuum service.	None	§ 60.486(e) § 60.486(e)(1) § 60.486(e)(5)	§ 60.562-2(e)
LPFUG	EU	60DDD-ALL	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-2(a) § 60.18 § 60.482-1(a) § 60.482-1(b) § 60.482-10(d) § 60.482-10(e) § 60.482-10(m) § 60.562-2(d) § 60.562-2(e)	Comply with the requirements in as stated in §60.482-10 for flares.	§ 60.485(a) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) [G]§ 60.485(g)	[G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.565(l)
LPFUG	EU	LPFFFF-1	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2480(a) - Table 6.1.a § 63.1022(b)(1) § 63.1022(c) § 63.1022(c)(1) § 63.1022(d)(1) § 63.1024(e)	Comply with the requirements of Subpart UU of this Part 63 except as specified in §63.2480(b) and (d): §63.1027, connectors in gas and vapor service and in light liquid service standards (except connectors at existing sources electing to comply with §63.1029).	§ 63.1022(c)(4)(i) § 63.1023(a)(1)(iii) § 63.1024(c)(1) [G]§ 63.1024(c)(3) § 63.1025(b)(3)(i) [G]§ 63.1025(d) § 63.1027(a) § 63.1027(b) § 63.1027(b)(1) § 63.1027(b)(2) § 63.1027(b)(3) § 63.1027(b)(3)(i) § 63.1027(b)(3)(iv) § 63.1027(c) § 63.1027(d)	§ 63.1022(c)(3) § 63.1022(c)(4) § 63.1022(d)(2) § 63.1027(b)(3)(v) § 63.1027(e)(1) § 63.1038(c)(3)	§ 63.1039(b)(1) § 63.1039(b)(1)(iii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						§63.1027(a)-(e)	[G]§ 63.1027(e)		
LPFUG	EU	LPFFFF-1	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2480(a) - Table 6.1.a § 63.1022(c) § 63.1022(c)(1) § 63.1022(c)(2) [G]§ 63.1022(c)(2)(i) § 63.1024(d) [G]§ 63.1024(d)(3) § 63.1024(d)(5) § 63.1025(a) § 63.1025(a)(1) [G]§ 63.1025(c)	Comply with the requirements of Subpart UU of this Part 63 except as specified in §63.2480(b) and (d): §63.1025, Valves in gas and vapor service and in light liquid service standards. §63.1025(a)-(e)	§ 63.1022(c)(4) § 63.1022(c)(4)(i) § 63.1022(c)(4)(ii) § 63.1023(a)(1) § 63.1025(a)(2) § 63.1025(b) § 63.1025(b)(1) § 63.1025(b)(2) § 63.1025(b)(3) § 63.1025(b)(3)(i) § 63.1025(b)(3)(ii) [G]§ 63.1025(d) § 63.1025(e) § 63.1025(e)(1) § 63.1025(e)(2)	§ 63.1022(c)(3) § 63.1022(c)(4) § 63.1022(c)(4)(i) § 63.1022(c)(4)(ii) § 63.1025(b)(3)(vi) § 63.1025(e) § 63.1025(e)(1) § 63.1025(e)(2) § 63.1038(c) § 63.1038(c)(1) § 63.1038(c)(1)(i)	§ 63.1039(a) [G]§ 63.1039(a)(1) § 63.1039(b)(1) § 63.1039(b)(1)(i) § 63.1039(b)(5)
LPFUG	EU	LPFFFF-1	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ § 63.2480(a)-Table 6.1.a § 63.1033(a) [G]§ 63.1033(b) § 63.1033(c) § 63.1033(d)	Comply with the requirements of Subpart UU of this Part 63 except as specified in §63.2480(b) and (d): §63.1033, Open-ended valves or lines standards. §63.1033(a)-(d)	None	None	None
LPFUG	EU	LPFFFF-1	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2480(a)-Table 6.1.a § 63.1032(a) § 63.1032(b) § 63.1032(b)(2) § 63.1032(c) § 63.1034(b) § 63.1034(b)(2)(iii)	Comply with the requirements of Subpart UU of this Part 63 except as specified in §63.2480(b) and (d): §63.1032(b), each sampling connection system shall be equipped with a	§ 63.1024(c)(2)	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						closed-purge, closed-loop, or closed vent system, except as provided in §§63.1021(b), 63.1036, 63.1037, or §63.1032(d). Gases displaced during filling of the sample container are not required to be collected or captured			
LPFUG	EU	LPFFFF-1	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2480(a)-Table 6.1.a [G]§ 63.1024 (d)(4) § 63.1026(e)(5)	Comply with the requirements of Subpart UU of this Part 63 except as specified in §63.2480(b) and (d): §63.1026, Pumps in light liquid service standards. §63.1026(a)-(e)	§ 63.1023(a)(1)(ii) § 63.1023(a)(2) § 63.1023(a)(2)(i) § 63.1024(c)(2) § 63.1026(a) § 63.1026(b) § 63.1026(b)(1) § 63.1026(b)(2) § 63.1026(b)(2)(i) § 63.1026(b)(2)(iii) § 63.1026(b)(3) [G]§ 63.1026(b)(4) [G]§ 63.1026(c) § 63.1026(d) § 63.1026(e) [G]§ 63.1026(e)(1) [G]§ 63.1035	[G]§ 63.1035 § 63.1038 (c)(2) [G]§ 63.1038(c)(7)	§ 63.1039 (b)(1) § 63.1039(b)(1)(ii) § 63.1039(b)(6)
LPFUG	EU	LPFFFF-1	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2480(a)-Table 6.1.a	Comply with the requirements of Subpart UU of this Part 63 except as specified in §63.2480(b) and (d): §63.1028, agitators in gas and vapor service	§ 63.1023(a)(1)(iv) § 63.1023(a)(2) § 63.1023(a)(2)(iii) § 63.1024(c)(2) § 63.1024(d) [G]§ 63.1024(d)(3) [G]§ 63.1028(a) [G]§ 63.1028(c)	§ 63.1038 (c)(4) § 63.1038(c)(4)(i)	§ 63.1039(b)(1) § 63.1039(b)(1)(iv)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						and in light liquid service standards. §63.1028(a)-(e)	§ 63.1028(d)		
LPFUG	EU	LPFFFF-1	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2480(a)- Table 6.1.a § 63.1030(a) § 63.1030(d) § 63.1030(e)	Comply with the requirements of Subpart UU of this Part 63 except as specified in §63.2480(b) and (d): §63.1030, pressure relief devices in gas and vapor service standards. §63.1030(a)-(e)	None	None	None
M-4799	EU	60III-1	CO	40 CFR Part 60, Subpart III	§ 60.4205(b) § 60.4202(a)(2) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) § 60.4211(f) § 60.4211(f)(1) § 60.4211(f)(2) § 60.4211(f)(2)(i) § 60.4211(f)(3) § 60.4218 § 89.112(a)	Owners and operators of emergency stationary CI ICE, that are not fire pump engines, with a maximum engine power greater than or equal to 130 KW and less than or equal to 2237 KW and a displacement of less than 10 liters per cylinder and is a 2007 model year and later must comply with a CO emission limit of 3.5 g/KW-hr, as stated in 40 CFR 60.4202(a)(2) and 40 CFR 89.112(a).	None	§ 60.4211(f)(1)	None
M-4799	EU	60III-1	NMHC and NO _x	40 CFR Part 60, Subpart III	§ 60.4205(b) § 60.4202(a)(2)	Owners and operators of emergency	None	§ 60.4211(f)(1)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) § 60.4211(f) § 60.4211(f)(1) § 60.4211(f)(2) § 60.4211(f)(2)(i) § 60.4211(f)(3) § 60.4218 § 89.112(a)	stationary CI ICE, that are not fire pump engines, with a maximum engine power greater than or equal to 75 KW and less than or equal to 560 KW and a displacement of less than 10 liters per cylinder and is a 2007 model year and later must comply with an NMHC+NOx emission limit of 4.0 g/KW-hr, as stated in 40 CFR 60.4202(a)(2) and 40 CFR 89.112(a).			
M-4799	EU	60III-1	PM (OPACITY)	40 CFR Part 60, Subpart III	§ 60.4205(b) § 60.4202(a)(2) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) § 60.4211(f) § 60.4211(f)(1) § 60.4211(f)(2) § 60.4211(f)(2)(i) § 60.4211(f)(3) § 60.4218 § 89.113(a)(1) § 89.113(a)(2) § 89.113(a)(3)	Emergency stationary CI ICE, that are not fire pump engines, with displacement < 10 lpc and not constant-speed engines, with max engine power < 2237 KW and a 2007 model year and later or max engine power > 2237 KW and a 2011 model year and later, must comply with following opacity emission limits: 20% during acceleration, 15% during lugging, 50% during peaks in either	None	§ 60.4211(f)(1)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						acceleration or lugging modes as stated in §60.4202(a)(1)-(2), (b)(2) and §89.113(a)(1)-(3) and §1039.105(b)(1)-(3).			
M-4799	EU	60III-1	PM	40 CFR Part 60, Subpart III	§ 60.4205(b) § 60.4202(a)(2) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) § 60.4211(f) § 60.4211(f)(1) § 60.4211(f)(2) § 60.4211(f)(2)(i) § 60.4211(f)(3) § 60.4218 § 89.112(a)	Owners and operators of emergency stationary CI ICE, that are not fire pump engines, with a maximum engine power greater than or equal to 130 KW and less than or equal to 2237 KW and a displacement of less than 10 liters per cylinder and is a 2007 model year and later must comply with a PM emission limit of 0.20 g/KW-hr, as stated in 40 CFR 60.4202(a)(2) and 40 CFR 89.112(a).	None	§ 60.4211(f)(1)	None
M-4799	EU	63ZZZZ-1	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(c) § 63.6590(c)(7)	Stationary RICE subject to Regulations under 40 CFR Part 60. An affected source that meets any of the criteria in paragraphs (c)(1) through (7) of this section must meet the requirements of this part by	None	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						meeting the requirements of 40 CFR part 60 subpart III, for compression ignition engines or 40 CFR part 60 subpart JJJJ, for spark ignition engines as applicable. No further requirements apply for such engines under this part.			
PROLPMR	PRO	60DDD-CVCF	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-1(a)(1) § 60.18 § 60.562-1(a)(1)(i) § 60.562-1(a)(1)(i)(C) § 60.562-1(a)(1)(iii) § 60.562-1(a)(1)(iii)(A) § 60.562-1(d) § 60.562-1(e)	For each vent stream that emits continuous emissions from affected facility, use procedures in paragraphs (a)(1)(ii)-(iii) for determining which continuous emissions to control as specified.	[G]§ 60.563(a) § 60.563(b) § 60.563(b)(2)(i) § 60.563(c) § 60.563(d)(1) § 60.563(d)(2) § 60.564(a) § 60.564(a)(1) § 60.564(a)(3) [G]§ 60.564(d) [G]§ 60.564(e) [G]§ 60.564(f) [G]§ 60.564(g)	[G]§ 60.563(a) § 60.563(d)(1) § 60.565(a) [G]§ 60.565(a)(3) [G]§ 60.565(b)(2) [G]§ 60.565(e) [G]§ 60.565(g) § 60.565(j)	§ 60.565(a) [G]§ 60.565(a)(3) § 60.565(b)(1) § 60.565(i) § 60.565(j) § 60.565(k) § 60.565(k)(2) § 60.565(k)(4) § 60.565(l)
PROLPMR	EU	60DDD-IVCF	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-1(a)(2)	Each vent stream that emits intermittent emissions as defined in §60.560-1(a)(1) shall be controlled as specified; prior to control modification/reconstruction/replacement, the vent stream is exempted.	None	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
PROLPPF4A B	PRO	60DDD-CVCF	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-1(a)(1) § 60.18 § 60.562-1(a)(1)(i) § 60.562-1(a)(1)(i)(C) § 60.562-1(a)(1)(iii) § 60.562-1(a)(1)(iii)(A) § 60.562-1(d) § 60.562-1(e)	For each vent stream that emits continuous emissions from affected facility, use procedures in paragraphs (a)(1)(ii)-(iii) for determining which continuous emissions to control as specified.	[G]§ 60.563(a) § 60.563(b) § 60.563(b)(2)(i) § 60.563(c) § 60.563(d)(1) § 60.563(d)(2) § 60.564(a) § 60.564(a)(1) § 60.564(a)(3) [G]§ 60.564(d) [G]§ 60.564(e) [G]§ 60.564(f) [G]§ 60.564(g)	[G]§ 60.563(a) § 60.563(d)(1) § 60.565(a) [G]§ 60.565(a)(3) [G]§ 60.565(b)(2) [G]§ 60.565(e) [G]§ 60.565(g) § 60.565(j)	§ 60.565(a) [G]§ 60.565(a)(3) § 60.565(b)(1) § 60.565(i) § 60.565(j) § 60.565(k) § 60.565(k)(2) § 60.565(k)(4) § 60.565(l)
PROLPPF4A B	PRO	60DDD-CVU1	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.560(g)	Vent streams emitting continuous emissions with uncontrolled annual emissions of < 1.6 Mg/yr (1.76 Tons/yr) or with weight % TOC of < 0.10 % from facilities as specified, exempted from §60.562-1(a)(1).	[G]§ 60.564(d)	§ 60.565(a) § 60.565(a)(10) § 60.565(h)	§ 60.565(a) § 60.565(a)(10) § 60.565(k) § 60.565(k)(6) § 60.565(k)(7)
PROLPPF4A B	PRO	60DDD-CVU2	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-1(a)(1) § 60.562-1(a)(1)(ii) § 60.562-1(d) § 60.562-1(e)	For each vent stream that emits continuous emissions from affected facility, use procedures in paragraphs (a)(1)(ii)-(iii) for determining which continuous emissions to control as specified.	[G]§ 60.563(a) § 60.563(d)(1) § 60.563(d)(2) § 60.564(a) § 60.564(a)(1) § 60.564(a)(3) [G]§ 60.564(d)	[G]§ 60.563(a) § 60.563(d)(1) § 60.565(a) [G]§ 60.565(b)(2) [G]§ 60.565(g) § 60.565(j)	§ 60.565(a) § 60.565(b)(1) § 60.565(i) § 60.565(j) § 60.565(k) § 60.565(k)(2) § 60.565(l)
PROLPRMP	PRO	60DDD-CVCF	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-1(a)(1) § 60.18 § 60.562-1(a)(1)(i)	For each vent stream that emits continuous emissions from	[G]§ 60.563(a) § 60.563(b) § 60.563(b)(2)(i)	[G]§ 60.563(a) § 60.563(d)(1) § 60.565(a)	§ 60.565(a) [G]§ 60.565(a)(3) § 60.565(b)(1)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.562-1(a)(1)(i)(C) § 60.562-1(a)(1)(iii) § 60.562-1(a)(1)(iii)(A) § 60.562-1(d) § 60.562-1(e)	affected facility, use procedures in paragraphs (a)(1)(ii)-(iii) for determining which continuous emissions to control as specified.	§ 60.563(c) § 60.563(d)(1) § 60.563(d)(2) § 60.564(a) § 60.564(a)(1) § 60.564(a)(3) [G]§ 60.564(d) [G]§ 60.564(e) [G]§ 60.564(f) [G]§ 60.564(g)	[G]§ 60.565(a)(3) [G]§ 60.565(b)(2) [G]§ 60.565(e) [G]§ 60.565(g) § 60.565(j)	§ 60.565(i) § 60.565(j) § 60.565(k) § 60.565(k)(2) § 60.565(k)(4) § 60.565(l)
PROLPRMP	EU	60DDD-IVCF	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-1(a)(2) [G]§ 60.562-1(a)(2)(i) § 60.562-1(d) § 60.562-1(e)	Each vent stream that emits intermittent emissions as defined in §60.560-1(a)(1) shall be controlled as specified; prior to control modification/reconstruction/replacement, the vent stream is exempted.	[G]§ 60.563(a) § 60.563(b) § 60.563(b)(2)(ii) § 60.563(c) § 60.563(d)(1) § 60.563(d)(2) § 60.564(a) § 60.564(a)(1) § 60.564(a)(3) [G]§ 60.564(e)	[G]§ 60.563(a) § 60.563(d)(1) § 60.565(a) [G]§ 60.565(a)(5) [G]§ 60.565(b)(2) [G]§ 60.565(e) [G]§ 60.565(g) § 60.565(j)	§ 60.565(1) § 60.565(a) [G]§ 60.565(a)(5) § 60.565(b)(1) § 60.565(i) § 60.565(j) § 60.565(k) § 60.565(k)(2) § 60.565(k)(4)
PROLPRMP	PRO	60DDD-IVU	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.560(d)	§60.562-1 does not apply to any polypropylene or polyethylene affected facility with an 09/30/87 applicability date and an uncontrolled emission rate that is the rates of Table 2.	[G]§ 60.564(h)	§ 60.565(a) § 60.565(a)(10) § 60.565(h)	§ 60.565(a) § 60.565(a)(10) § 60.565(k) § 60.565(k)(6) § 60.565(k)(7) § 60.565(l)
PROLPRX60	PRO	60DDD-EV	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.560(d)	§60.562-1 does not apply to any polypropylene or polyethylene affected facility with an	[G]§ 60.564(h)	§ 60.565(a) § 60.565(a)(10) § 60.565(h)	§ 60.565(a) § 60.565(a)(10) § 60.565(k) § 60.565(k)(6) § 60.565(k)(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						09/30/87 applicability date and an uncontrolled emission rate that is the rates of Table 2.			§ 60.565(l)
PROLPRX60	EU	60DDD-IVCF	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-1(a)(2) [G]§ 60.562-1(a)(2)(i) § 60.562-1(d) § 60.562-1(e)	Each vent stream that emits intermittent emissions as defined in §60.560-1(a)(1) shall be controlled as specified; prior to control modification/reconstruction/replacement, the vent stream is exempted.	[G]§ 60.563(a) § 60.563(b) § 60.563(b)(2)(ii) § 60.563(c) § 60.563(d)(1) § 60.563(d)(2) § 60.564(a) § 60.564(a)(1) § 60.564(a)(3) [G]§ 60.564(e)	[G]§ 60.563(a) § 60.563(d)(1) § 60.565(a) [G]§ 60.565(a)(5) [G]§ 60.565(b)(2) [G]§ 60.565(e) [G]§ 60.565(g) § 60.565(j)	§ 60.565(a) [G]§ 60.565(a)(5) § 60.565(b)(1) § 60.565(i) § 60.565(j) § 60.565(k) § 60.565(k)(2) § 60.565(k)(4) § 60.565(l)

Additional Monitoring Requirements

Compliance Assurance Monitoring Summary 59

Periodic Monitoring Summary 61

CAM Summary

Unit/Group/Process Information	
ID No.: 721V	
Control Device ID No.: 721	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-8
Pollutant: VOC	Main Standard: § 115.122(a)(1)
Monitoring Information	
Indicator: Pilot flame	
Minimum Frequency: Continuous	
Averaging Period: N/A	
Deviation Limit: Loss of all pilots on flare	
<p>CAM Text: Measure and record the presence of the pilot flame. The presence of a pilot flame shall be monitored using a thermocouple or any other equivalent device to detect the presence of a flame. The monitoring instrumentation shall be maintained, calibrated, and operated in accordance with manufacturer's specifications or other written procedures. In the event the thermocouple or equivalent monitoring device is experiencing a system malfunction, a visual verification of the pilot flame may be performed to detect the presence of a flame. Lack of all flare pilot flames, as evidenced by all available monitoring data and/or visual observation shall be considered and reported as a deviation.</p>	

CAM Summary

Unit/Group/Process Information	
ID No.: 858V	
Control Device ID No.: 858	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-8
Pollutant: VOC	Main Standard: § 115.122(a)(1)
Monitoring Information	
Indicator: Pilot flame	
Minimum Frequency: Continuous	
Averaging Period: N/A	
Deviation Limit: Loss of all pilots on flare	
<p>CAM Text: Measure and record the presence of the pilot flame. The presence of a pilot flame shall be monitored using a thermocouple or any other equivalent device to detect the presence of a flame. The monitoring instrumentation shall be maintained, calibrated, and operated in accordance with manufacturer's specifications or other written procedures. In the event the thermocouple or equivalent monitoring device is experiencing a system malfunction, a visual verification of the pilot flame may be performed to detect the presence of a flame. Lack of all flare pilot flames, as evidenced by all available monitoring data and/or visual observation shall be considered and reported as a deviation.</p>	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: 612-D4749	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart Kb	SOP Index No.: 60Kb-0081
Pollutant: VOC	Main Standard: § 60.112b(b)(1)
Monitoring Information	
Indicator: Indication of a leak in CVS components	
Minimum Frequency: Annually	
Averaging Period: N/A	
Deviation Limit: Failure to repair leaks as required	
<p>Periodic Monitoring Text: Perform an inspection of the closed vent system utilizing visual, audible, or olfactory (AVO) methods. If a leak is found by AVO methods, a first attempt at repair shall be performed within 5 days after discovery of the leak. The leak shall be repaired within 15 days after discovery of the leak, unless the repair is technically infeasible without a process unit shutdown or if the immediate repair would cause more emissions than the fugitive emissions likely to result from the delay of repair. If the repair is delayed, repairs must be performed during the next process unit shutdown. If delay of repair is not justified, it shall be considered a deviation if, upon discovery of a leak, the first attempt at repair is not attempted within 5 days or if repairs are not complete within 15 days after discovery of a leak. If delay of repair is justified, it shall be considered a deviation if the repairs are not completed during the next process unit shutdown.</p>	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: 612-D4758	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart Kb	SOP Index No.: 60Kb-0081
Pollutant: VOC	Main Standard: § 60.112b(b)(1)
Monitoring Information	
Indicator: Indication of a leak in CVS components	
Minimum Frequency: Annually	
Averaging Period: N/A	
Deviation Limit: Failure to repair leaks as required	
<p>Periodic Monitoring Text: Perform an inspection of the closed vent system utilizing visual, audible, or olfactory (AVO) methods. If a leak is found by AVO methods, a first attempt at repair shall be performed within 5 days after discovery of the leak. The leak shall be repaired within 15 days after discovery of the leak, unless the repair is technically infeasible without a process unit shutdown or if the immediate repair would cause more emissions than the fugitive emissions likely to result from the delay of repair. If the repair is delayed, repairs must be performed during the next process unit shutdown. If delay of repair is not justified, it shall be considered a deviation if, upon discovery of a leak, the first attempt at repair is not attempted within 5 days or if repairs are not complete within 15 days after discovery of a leak. If delay of repair is justified, it shall be considered a deviation if the repairs are not completed during the next process unit shutdown.</p>	

Permit Shield

Permit Shield 64

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
612-D4718	N/A	40 CFR Part 60, Subpart Ka	Tank does not store petroleum liquid and the storage capacity is less than 151,412 liters (40,000 gallons)
612-D4723	N/A	40 CFR Part 60, Subpart Ka	Tank does not store petroleum liquid and the storage capacity is less than 151,412 liters (40,000 gallons)
612-D4725	N/A	40 CFR Part 60, Subpart Kb	Tank capacity is less than 75 cubic meters (19,812 gallons)
612-D4752	N/A	40 CFR Part 60, Subpart Kb	Tank capacity is less than 75 cubic meters (19,812 gallons)
612-D4754	N/A	40 CFR Part 60, Subpart Kb	Tank capacity is less than 75 cubic meters (19,812 gallons)
612-F5959	N/A	40 CFR Part 60, Subpart Kb	Tank capacity is less than 75 cubic meters (19,812 gallons)
723	N/A	30 TAC Chapter 115, Vent Gas Controls	Unit which is not being used as a control device for any vent gas stream subject to this undesignated head and which originates from a non-combustion source
723A	N/A	30 TAC Chapter 115, Vent Gas Controls	Unit which is not being used as a control device for any vent gas stream subject to this undesignated head and which originates from a non-combustion source
976	N/A	30 TAC Chapter 115, Vent Gas Controls	Unit which is not being used as a control device for any vent gas stream subject to

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
			this undesignated head and which originates from a non-combustion source
B-4901	N/A	30 TAC Chapter 112, Sulfur Compounds	Does not burn solid fuel
B-4901	N/A	40 CFR Part 60, Subpart D	Heat input rate for fossil fuel fired steam generating unit is less than or equal to 250 MMBTU/hr (73 MW)
B-4901	N/A	40 CFR Part 60, Subpart Db	Heat input rate for the steam generating unit is less than or equal to 100 MMBTU/hr
B-4901	N/A	40 CFR Part 60, Subpart Dc	Heat input rate for the steam generating unit is less than 10 MMBTU/hr
B-4902	N/A	30 TAC Chapter 112, Sulfur Compounds	Does not burn solid fuel
B-4902	N/A	40 CFR Part 60, Subpart D	Heat input rate for fossil fuel fired steam generating unit is less than or equal to 250 MMBTU/hr (73 MW)
B-4902	N/A	40 CFR Part 60, Subpart Db	Heat input rate for the steam generating unit is less than or equal to 100 MMBTU/hr
B-4902	N/A	40 CFR Part 60, Subpart Dc	Unit was constructed, modified, or reconstructed before 06/09/1989
B-4903	N/A	30 TAC Chapter 112, Sulfur Compounds	Does not burn solid fuel
B-4903	N/A	40 CFR Part 60, Subpart D	Heat input rate for fossil fuel fired steam generating unit is less than or equal to

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
			250 MMBTU/hr (73 MW)
B-4903	N/A	40 CFR Part 60, Subpart Db	Heat input rate for the steam generating unit is less than or equal to 100 MMBTU/hr
B-4903	N/A	40 CFR Part 60, Subpart Dc	Heat input rate for the steam generating unit is less than 10 MMBTU/hr
F701	N/A	40 CFR Part 63, Subpart Q	Not operated with chromium-based water treatment chemicals on or after 09/08/1994
GRPLPTANK1	612-F4706, 612-F6640A, 612-F6640B	40 CFR Part 60, Subpart Kb	Tank capacity is less than 75 cubic meters (19,812 gallons)
LPFUG	N/A	40 CFR Part 60, Subpart VV	Facility does not make a chemical that meets the definition of a SOCM I plant
LPFUG	N/A	40 CFR Part 61, Subpart J	This unit does not have equipment intended for operation in benzene service
LPFUG	N/A	40 CFR Part 61, Subpart V	This unit does not have equipment intended for operation in VHAP service
M-4799	N/A	30 TAC Chapter 117, Subchapter B	Stationary diesel engines are exempt from the provision of Chapter 117 Subchapter B, Division 1 relating to Beaumont-Port Arthur Ozone Nonattainment Area major sources
PROLPPF5	N/A	40 CFR Part 60, Subpart DDD	Affected facility was constructed, modified, or reconstructed before

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
			09/30/1987
PROLPPF6	N/A	40 CFR Part 60, Subpart DDD	Affected facility was constructed, modified, or reconstructed before 09/30/1987
PROLPPS4AB	N/A	40 CFR Part 60, Subpart DDD	Affected facility was constructed, modified, or reconstructed before 09/30/1987
PROLPPS5	N/A	40 CFR Part 60, Subpart DDD	Affected facility was constructed, modified, or reconstructed before 09/30/1987
PROLPPS6	N/A	40 CFR Part 60, Subpart DDD	Affected facility was constructed, modified, or reconstructed before 09/30/1987
PROLPRX44	N/A	40 CFR Part 60, Subpart DDD	Affected facility was constructed, modified, or reconstructed before 09/30/1987
PROLPRX45	N/A	40 CFR Part 60, Subpart DDD	Affected facility was constructed, modified, or reconstructed before 09/30/1987

New Source Review Authorization References

New Source Review Authorization References..... 69
New Source Review Authorization References by Emission Unit 70

New Source Review Authorization References

The New Source Review authorizations listed in the table below are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Title 30 TAC Chapter 116 Permits, Special Permits, and Other Authorizations (Other Than Permits By Rule, PSD Permits, or NA Permits) for the Application Area.	
Authorization No.: 8758	Issuance Date: 09/25/2015
Permits By Rule (30 TAC Chapter 106) for the Application Area	
Number: 106.261	Version No./Date: 11/01/2003
Number: 106.262	Version No./Date: 11/01/2003
Number: 106.263	Version No./Date: 11/01/2001
Number: 106.433	Version No./Date: 09/04/2000
Number: 106.452	Version No./Date: 09/04/2000
Number: 83	Version No./Date: 03/15/1985

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
401	CATALYST SUPPORT DEHYDRTR	8758
423	PRODUCT CONVEYING SYSTEM (REACTOR 44)	8758
424	PRODUCT CONVEYING SYSTEM (REACTOR 45)	8758
429A	ANALYZER VENT	8758
429B	ANALYZER VENT	8758
429C	ANALYZER VENT	8758
429D	ANALYZER VENT	8758
429E	ANALYZER VENT	8758
429F	ANALYZER VENT	8758
612-D4718	TEAL TANK	83/03/15/1985
612-D4723	THF TANK	83/03/15/1985
612-D4725	TMA/HEXANE TANK	83/03/15/1985
612-D4749	BUTENE STORAGE	8758
612-D4752	TEAL TANK	83/03/15/1985
612-D4754	TMA/ISOPENTANE TANK	83/03/15/1985
612-D4758	ISOPENTANE TANK	83/03/15/1985
612-F4706	DIESEL TANK	8758
612-F5959	TNPP TANK	8758
612-F6640A	OMS/PEROXIDE STORAGE TANK	8758

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
612-F6640B	OMS/PEROXIDE STORAGE TANK	8758
641A	ANALYZER VENT	8758
642A	ANALYZER VENT	8758
642B	ANALYZER VENT	8758
642C	ANALYZER VENT	8758
642D	ANALYZER VENT	8758
642E	ANALYZER VENT	8758
642G	ANALYZER VENT	8758
642H	ANALYZER VENT	8758
643	ANALYZER VENT	8758
645	SURGE SILO L4AB	8758
650	SPIN DRYER L4A	8758
651	SPIN DRYER L4B	8758
652	BLENDING SILO L4A	8758
653	BLENDING SILO L4B	8758
654AB	LOADING ELUTRIATORS L4A	8758
655AB	LOADING SCALPERATORS L4B	8758
656	HOPPER CAR LOADING L4A	8758
657	HOPPER CAR LOADING L4B	8758

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
662	SURGE SILO L4AB	8758
663	SURGE SILO L4AB	8758
664	SURGE SILO L4AB	8758
665	LOADOUT SURGE VESSEL L5	8758
666	LOADOUT SURGE VESSEL L5	8758
667	PREFILL BIN L5	8758
668	PREFILL BIN L5	8758
669	PREFILL BIN L5	8758
670	PREFILL BIN L5	8758
671	PREFILL BIN L5	8758
672	PREFILL BIN L5	8758
673	PREFILL BIN L5	8758
674	PREFILL BIN L5	8758
675	LOADOUT SURGE VESSEL L6	8758
676	LOADOUT SURGE VESSEL L6	8758
677	PREFILL BIN L6	8758
678	PREFILL BIN L6	8758
679	PREFILL BIN L6	8758
680	PREFILL BIN L6	8758

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
681	PREFILL BIN L6	8758
682	PREFILL BIN L6	8758
683	PREFILL BIN L6	8758
684	PREFILL BIN L6	8758
686	COMPOUNDING SEED SILO L4AB, L5, L6	8758
687	MIXER FEED HOPPER VENT L5	8758
688	MIXER FEED HOPPER VENT L6	8758
689	PELLET BLEND SILO L5	8758
690	PELLET BLEND SILO L6	8758
691	PELLET BLEND SILO L5	8758
692	PELLET BLEND SILO L6	8758
695	COMPOSITE PELLET SAMPLE POT L4B	8758
696	COMPOSITE PELLET SAMPLE POT L4A	8758
697	COMPOSITE PELLET SAMPLE POT L5	8758
698	COMPOSITE PELLET SAMPLE POT L6	8758
699	COMPOSITE PELLET SAMPLE POT L5	8758
721	LPPE FLARE-AIR ASSIST	8758
721V	PROCESS VENT STREAM TO LPPE FLARE	8758
723A	STEAM GENERATOR STACK	8758

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
723	STEAM GENERATOR STACK	8758
817	RX60 VENT	8758
819A	ANALYZER VENT	8758
819B	ANALYZER VENT	8758
819C	ANALYZER VENT	8758
819D	ANALYZER VENT	8758
819E	ANALYZER VENT	8758
821	PROD CONVEY SYSTEM VENT, REACTOR 60	8758
845	SURGE SILO L4AB	8758
850	SPIN DRYER L5	8758
851	SPIN DRYER L6	8758
854	ELUTRIATOR L5	8758
855	ELUTRIATOR L6	8758
858	LPPE FLARE-LRGO	8758
858V	PROCESS VENT STREAM TO LRGO FLARE	8758
861	RX44 VENT	8758
862	RX45 VENT	8758
863	F-6705 HEXENE TANK	8758
866	SURGE SILO L6	8758

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
867	SURGE SILO L6	8758
868	SURGE SILO L6	8758
869	SURGE SILO L6	8758
870	SURGE SILO L6	8758
871	BOOSTER BLOWER L4AB	8758
872	BOOSTER BLOWER L5	8758
873	BOOSTER BLOWER L6	8758
878	PELLET BLEND SILO L5	8758
879	PELLET BLEND SILO L6	8758
884	PRIME FEED SILO L5	8758
886	W/S FEED SILO L5	8758
889	PRIME FEED SILO L6	8758
891	W/S FEED SILO L6	8758
900	SEED BOOSTER BLOWER L4AB, L5, L6	8758
910	PRIME PE FEEDER L4B	8758
911	W/S FEEDER SILO L4B	8758
924	GRANULAR HOLDUP BIN L4B	8758
925	PRODUCT SILO L4B	8758
926	PRODUCT SILO L4B	8758

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
927	GRANULAR FILLER RECEIVER L4B	8758
928	SCALPERATOR L4A	8758
929	PRODUCT SILO VENT L4B	8758
930	PRIME FEED SILO L4A	8758
931	W/S FEED SILO VENT L4A	8758
944	GRANULAR HOLDUP BIN L4A	8758
945	PRODUCT SILO L4A	8758
946	PRODUCT SILO L4A	8758
947	PRODUCT SILO L4A	8758
948	SCALPERATOR L4B	8758
949	GRANULAR FILTER RECEIVER L4A	8758
953	COMPOUND SAMPLER L5	8758
954	SAMPLER	8758
955	PELLET HOLDUP BIN L4A	8758
956	PELLET HOLDUP BIN L4B	8758
957	PELLET HOLDUP BIN L5	8758
958	PELLET HOLDUP BIN L6	8758
959	PELLET SAMPLE HOPPER L4B	8758
960	PELLET SAMPLE HOPPER L4A	8758

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
961	PELLET SAMPLE HOPPER L5	8758
962	PELLET SAMPLE HOPPER L6	8758
963	PELLET RECLAIM SAMPLE BIN L4AB, L5, L6	8758
973	SURGE SILO FILTER L5	8758
976	STEAM GENERATOR STACK	8758
991	FEED PURIFICATION	8758
992	FEED PURIFICATION	8758
993A	CHARGE POT	8758
B-4901	STEAM GENERATOR	8758
B-4902	STEAM GENERATOR	8758
B-4903	STEAM GENERATOR	8758
F701	COOLING TOWER #2	8758
LINE 45	LINE 45 MATERIAL RECOVERY PURGE	8758
LINE 60	LINE 60 PURGE SYSTEM	8758
LINE44	LINE 44 MATERIAL RECOVERY PURGE	8758
LPFUG	LOW PRESSURE FUGITIVES	8758
M-4799	EMERGENCY GENERATOR (EPN: 980)	8758
PROLPMR	LP MATERIAL RECOVERY (PROCESS)	8758
PROLPPF4AB	LP PRODUCT FINISHING L4A, L4B (PROCESS)	8758

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
PROLPPF5	LP PRODUCT FINISHING L5 (PROCESS)	8758
PROLPPF6	LP PRODUCT FINISHING L6 (PROCESS)	8758
PROLPPS4AB	LP PRODUCT STORAGE L4AB (PROCESS)	8758
PROLPPS5	LP PRODUCT STORAGE L5 (PROCESS)	8758
PROLPPS6	LP PRODUCT STORAGE L6 (PROCESS)	8758
PROLPRMP	LP RAW MATERIAL PREPARATION (PROCESS)	8758
PROLPRX44	LP POLYMERIZATION REACTION REACTOR 44 (PROCESS)	8758
PROLPRX45	LP POLYMERIZATION REACTION REACTOR 45 (PROCESS)	8758
PROLPRX60	LP POLYMERIZATION REACTION REACTOR 60 (PROCESS)	8758

Appendix A

Acronym List 80

Acronym List

The following abbreviations or acronyms may be used in this permit:

ACFM	actual cubic feet per minute
AMOC	alternate means of control
ARP	Acid Rain Program
ASTM	American Society of Testing and Materials
B/PA	Beaumont/Port Arthur (nonattainment area)
CAM	Compliance Assurance Monitoring
CD	control device
COMS	continuous opacity monitoring system
CVS	closed-vent system
D/FW	Dallas/Fort Worth (nonattainment area)
DR	Designated Representative
EIP	El Paso (nonattainment area)
EP	emission point
EPA	U.S. Environmental Protection Agency
EU	emission unit
FCAA Amendments	Federal Clean Air Act Amendments
FOP	federal operating permit
GF	grandfathered
gr/100 scf	grains per 100 standard cubic feet
HAP	hazardous air pollutant
H/G/B	Houston/Galveston/Brazoria (nonattainment area)
H ₂ S	hydrogen sulfide
ID No.	identification number
lb/hr	pound(s) per hour
MMBtu/hr	Million British thermal units per hour
MRRT	monitoring, recordkeeping, reporting, and testing
NA	nonattainment
N/A	not applicable
NADB	National Allowance Data Base
NO _x	nitrogen oxides
NSPS	New Source Performance Standard (40 CFR Part 60)
NSR	New Source Review
ORIS	Office of Regulatory Information Systems
Pb	lead
PBR	Permit By Rule
PM	particulate matter
ppmv	parts per million by volume
PSD	prevention of significant deterioration
RO	Responsible Official
SO ₂	sulfur dioxide
TCEQ	Texas Commission on Environmental Quality
TSP	total suspended particulate
TVP	true vapor pressure
U.S.C.	United States Code
VOC	volatile organic compound