

FEDERAL OPERATING PERMIT

A FEDERAL OPERATING PERMIT IS HEREBY ISSUED TO
Kaneka North America LLC

AUTHORIZING THE OPERATION OF
Kaneka Pasadena Site
Plastics Materials

LOCATED AT
Harris County, Texas
Latitude 29° 37' 16" Longitude 95° 5' 32"
Regulated Entity Number: RN100218841

This permit is issued in accordance with and subject to the Texas Clean Air Act (TCAA), Chapter 382 of the Texas Health and Safety Code and Title 30 Texas Administrative Code Chapter 122 (30 TAC Chapter 122), Federal Operating Permits. Under 30 TAC Chapter 122, this permit constitutes the permit holder's authority to operate the site and emission units listed in this permit. Operations of the site and emission units listed in this permit are subject to all additional rules or amended rules and orders of the Commission pursuant to the TCAA.

This permit does not relieve the permit holder from the responsibility of obtaining New Source Review authorization for new, modified, or existing facilities in accordance with 30 TAC Chapter 116, Control of Air Pollution by Permits for New Construction or Modification.

The site and emission units authorized by this permit shall be operated in accordance with 30 TAC Chapter 122, the general terms and conditions, special terms and conditions, and attachments contained herein.

This permit shall expire five years from the date of issuance. The renewal requirements specified in 30 TAC § 122.241 must be satisfied in order to renew the authorization to operate the site and emission units.

Permit No: O3528 Issuance Date: March 21, 2013

For the Commission

Table of Contents

Section	Page
General Terms and Conditions	1
Special Terms and Conditions	1
Emission Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting	1
Additional Monitoring Requirements	8
New Source Review Authorization Requirements	10
Compliance Requirements	11
Risk Management Plan	13
Protection of Stratospheric Ozone	13
Permit Location	13
Permit Shield (30 TAC § 122.148)	13
Attachments	14
Applicable Requirements Summary	15
Additional Monitoring Requirements	156
Permit Shield	207
New Source Review Authorization References	214
Appendix A	226
Acronym List	227

General Terms and Conditions

The permit holder shall comply with all terms and conditions contained in 30 TAC § 122.143 (General Terms and Conditions), 30 TAC § 122.144 (Recordkeeping Terms and Conditions), 30 TAC § 122.145 (Reporting Terms and Conditions), and 30 TAC § 122.146 (Compliance Certification Terms and Conditions).

In accordance with 30 TAC § 122.144(1), records of required monitoring data and support information required by this permit, or any applicable requirement codified in this permit, are required to be maintained for a period of five years from the date of the monitoring report, sample, or application unless a longer data retention period is specified in an applicable requirement. The five year record retention period supersedes any less stringent retention requirement that may be specified in a condition of a permit identified in the New Source Review Authorization attachment.

If the permit holder chooses to demonstrate that this permit is no longer required, a written request to void this permit shall be submitted to the Texas Commission on Environmental Quality (TCEQ) by the Responsible Official in accordance with 30 TAC § 122.161(e). The permit holder shall comply with the permit's requirements, including compliance certification and deviation reporting, until notified by the TCEQ that this permit is voided.

The permit holder shall comply with 30 TAC Chapter 116 by obtaining a New Source Review authorization prior to new construction or modification of emission units located in the area covered by this permit.

All reports required by this permit must include in the submittal a cover letter which identifies the following information: company name, TCEQ regulated entity number, air account number (if assigned), site name, area name (if applicable), and Air Permits Division permit number(s).

Special Terms and Conditions: Emission Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting

1. Permit holder shall comply with the following requirements:
 - A. Emission units (including groups and processes) in the Applicable Requirements Summary attachment shall meet the limitations, standards, equipment specifications, monitoring, recordkeeping, reporting, testing, and other requirements listed in the Applicable Requirements Summary attachment to assure compliance with the permit.
 - B. The textual description in the column titled "Textual Description" in the Applicable Requirements Summary attachment is not enforceable and is not deemed as a substitute for the actual regulatory language. The Textual Description is provided for information purposes only.

- C. A citation listed on the Applicable Requirements Summary attachment, which has a notation [G] listed before it, shall include the referenced section and subsection for all commission rules, or paragraphs for all federal and state regulations and all subordinate paragraphs, subparagraphs and clauses, subclauses, and items contained within the referenced citation as applicable requirements.
- D. When a grouped citation, notated with a [G] in the Applicable Requirements Summary, contains multiple compliance options, the permit holder must keep records of when each compliance option was used.
- E. Emission units subject to 40 CFR Part 63, Subparts EEEE, FFFF, JJJ and ZZZZ as identified in the attached Applicable Requirements Summary table are subject to 30 TAC Chapter 113, Subchapter C, § 113.880, 113.890, 113.670 and 113.1090 respectively, which incorporates the respective 40 CFR Part 63 Subpart by reference.
- F. The permit holder shall comply with the following 30 TAC Chapter 101, Subchapter H, Division 3 (Mass Emission Cap and Trade Program) Requirements:
 - (i) Title 30 TAC § 101.352 (relating to General Provisions)
 - (ii) Title 30 TAC § 101.353 (relating to Allocation of Allowances)
 - (iii) Title 30 TAC § 101.354 (relating to Allowance Deductions)
 - (iv) Title 30 TAC § 101.356 (relating to Allowance Banking and Trading)
 - (v) Title 30 TAC § 101.358 (relating to Emission Monitoring and Compliance Demonstration)
 - (vi) Title 30 TAC § 101.359 (relating to Reporting)
 - (vii) Title 30 TAC § 101.360 (relating to Level of Activity Certification)
 - (viii) The terms and conditions by which the emission limits are established to meet or exceed the cap are applicable requirements of this permit
- G. The permit holder shall comply with the following 30 TAC Chapter 101, Subchapter H, Division 6 (Highly Reactive Volatile Organic Compound Emissions Cap and Trade Program) requirements:
 - (i) Title 30 TAC § 101.393 (relating to General Provisions)
 - (ii) Title 30 TAC § 101.394 (relating to Allocation of Allowances)

- (iii) Title 30 TAC § 101.396 (relating to Allowance Deductions)
 - (iv) Title 30 TAC § 101.399 (relating to Allowance Banking and Trading)
 - (v) Title 30 TAC § 101.400 (relating to Reporting)
 - (vi) The terms and conditions by which the emission limits are established to meet or exceed the cap are applicable requirements of this permit
2. The permit holder shall comply with the following sections of 30 TAC Chapter 101 (General Air Quality Rules):
- A. Title 30 TAC § 101.1 (relating to Definitions), insofar as the terms defined in this section are used to define the terms used in other applicable requirements
 - B. Title 30 TAC § 101.3 (relating to Circumvention)
 - C. Title 30 TAC § 101.8 (relating to Sampling), if such action has been requested by the TCEQ
 - D. Title 30 TAC § 101.9 (relating to Sampling Ports), if such action has been requested by the TCEQ
 - E. Title 30 TAC § 101.10 (relating to Emissions Inventory Requirements)
 - F. Title 30 TAC § 101.201 (relating to Emission Event Reporting and Recordkeeping Requirements)
 - G. Title 30 TAC § 101.211 (relating to Scheduled Maintenance, Start-up, and Shutdown Reporting and Recordkeeping Requirements)
 - H. Title 30 TAC § 101.221 (relating to Operational Requirements)
 - I. Title 30 TAC § 101.222 (relating to Demonstrations)
 - J. Title 30 TAC § 101.223 (relating to Actions to Reduce Excessive Emissions)
3. Permit holder shall comply with the following requirements of 30 TAC Chapter 111:
- A. Visible emissions from stationary vents with a flow rate of less than 100,000 actual cubic feet per minute and constructed after January 31, 1972 that are not listed in the Applicable Requirements Summary attachment for 30 TAC Chapter 111, Subchapter A, Division 1, shall not exceed 20% opacity averaged over a six-minute period. The permit holder

shall comply with the following requirements for stationary vents at the site subject to this standard:

- (i) Title 30 TAC § 111.111(a)(1)(B) (relating to Requirements for Specified Sources)
- (ii) Title 30 TAC § 111.111(a)(1)(E)
- (iii) Title 30 TAC § 111.111(a)(1)(F)(i), (ii), (iii), or (iv)
- (iv) For emission units with vent emissions subject to 30 TAC § 111.111(a)(1)(B), complying with 30 TAC § 111.111(a)(1)(F)(ii), (iii), or (iv), and capable of producing visible emissions from, but not limited to, particulate matter, acid gases and NO_x, the permit holder shall also comply with the following periodic monitoring requirements for the purpose of annual compliance certification under 30 TAC § 122.146. These periodic monitoring requirements do not apply to vents that are not capable of producing visible emissions such as vents that emit only colorless VOCs; vents from non-fuming liquids; vents that provide passive ventilation, such as plumbing vents; or vent emissions from any other source that does not obstruct the transmission of light. Vents, as specified in the “Applicable Requirements Summary” attachment, that are subject to the emission limitation of 30 TAC § 111.111(a)(1)(B) are not subject to the following periodic monitoring requirements:
 - (1) An observation of stationary vents from emission units in operation shall be conducted at least once during each calendar quarter unless the emission unit is not operating for the entire quarter.
 - (2) For stationary vents from a combustion source, if an alternative to the normally fired fuel is fired for a period greater than or equal to 24 consecutive hours, the permit holder shall conduct an observation of the stationary vent for each such period to determine if visible emissions are present. If such period is greater than 3 months, observations shall be conducted once during each quarter. Supplementing the normally fired fuel with natural gas or fuel gas to increase the net heating value to the minimum required value does not constitute creation of an alternative fuel.
 - (3) Records of all observations shall be maintained.
 - (4) Visible emissions observations of emission units operated during daylight hours shall be conducted no earlier than one hour after sunrise and no later than one hour before sunset.

Visible emissions observations of emission units operated only at night must be made with additional lighting and the temporary installation of contrasting backgrounds. Visible emissions observations shall be made during times when the activities described in 30 TAC § 111.111(a)(1)(E) are not taking place. Visible emissions shall be determined with each stationary vent in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 mile, away from each stationary vent during the observation. For outdoor locations, the observer shall select a position where the sun is not directly in the observer's eyes. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. A certified opacity reader is not required for visible emissions observations.

- (5) Compliance Certification:
- (a) If visible emissions are not present during the observation, the RO may certify that the source is in compliance with the applicable opacity requirement in 30 TAC § 111.111(a)(1) and (a)(1)(B).
 - (b) However, if visible emissions are present during the observation, the permit holder shall either list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(1)(F) as soon as practicable, but no later than 24 hours after observing visible emissions to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.

- (c) Some vents may be subject to multiple visible emission or monitoring requirements. All credible data must be considered when certifying compliance with this requirement even if the observation or monitoring was performed to demonstrate compliance with a different requirement.
 - B. Certification of opacity readers determining opacities under Method 9 (as outlined in 40 CFR Part 60, Appendix A) to comply with opacity monitoring requirements shall be accomplished by completing the Visible Emissions Evaluators Course, or approved agency equivalent, no more than 180 days before the opacity reading.
 - C. For emission units with contributions from uncombined water, the permit holder shall comply with the requirements of 30 TAC § 111.111(b).
 - D. Outdoor burning, as stated in 30 TAC § 111.201, shall not be authorized unless the following requirements are satisfied:
 - (i) Title 30 TAC § 111.205 (relating to Exception for Fire Training)
 - (ii) Title 30 TAC § 111.207 (relating to Exception for Recreation, Ceremony, Cooking, and Warmth)
 - (iii) Title 30 TAC § 111.219 (relating to General Requirements for Allowable Outdoor Burning)
 - (iv) Title 30 TAC § 111.221 (relating to Responsibility for Consequences of Outdoor Burning)
- 4. For storage vessels maintaining working pressure as specified in 30 TAC Chapter 115, Subchapter B, Division 1: Storage of Volatile Organic Compounds, the permit holder shall comply with the requirements of 30 TAC § 115.112(e)(1).
- 5. The permit holder shall comply with the following requirements of 30 TAC Chapter 115, Subchapter H, Division 1 for pressure relief devices not controlled by a flare:
 - A. Title 30 TAC § 115.725(c)
 - B. Title 30 TAC § 115.725(c)(1), (c)(1)(A) - (C)
 - C. Title 30 TAC § 115.725(c)(2)
 - D. Title 30 TAC § 115.725(c)(3), (c)(3)(A) - (E)
 - E. Title 30 TAC § 115.725(c)(4)
 - F. Title 30 TAC § 115.725(l)

- G. Title 30 TAC § 115.726(c), (c)(1) - (4)
- 6. The permit holder shall comply with the requirements of 30 TAC § 115.726(e)(3)(A) for vent streams having no potential to emit HRVOC.
- 7. The permit holder shall comply with the following requirements for units subject to any subpart of 40 CFR Part 60, unless otherwise stated in the applicable subpart:
 - A. Title 40 CFR § 60.7 (relating to Notification and Recordkeeping)
 - B. Title 40 CFR § 60.8 (relating to Performance Tests)
 - C. Title 40 CFR § 60.11 (relating to Compliance with Standards and Maintenance Requirements)
 - D. Title 40 CFR § 60.12 (relating to Circumvention)
 - E. Title 40 CFR § 60.13 (relating to Monitoring Requirements)
 - F. Title 40 CFR § 60.14 (relating to Modification)
 - G. Title 40 CFR § 60.15 (relating to Reconstruction)
 - H. Title 40 CFR § 60.19 (relating to General Notification and Reporting Requirements)
- 8. The permit holder shall comply with the requirements of 30 TAC Chapter 113, Subchapter C, § 113.100 for units subject to any subpart of 40 CFR Part 63, unless otherwise stated in the applicable subpart.
- 9. For thermoplastic product process facilities subject to maintenance wastewater requirements as specified in 40 CFR § 63.1330(c), the permit holder shall comply with the requirements of 40 CFR § 63.105(b) - (e) (relating to Maintenance Wastewater Requirements)(Title 30 TAC Chapter 113, Subchapter C, § 113.670 incorporated by reference).
- 10. For miscellaneous chemical process facilities subject to maintenance wastewater requirements as specified in 40 CFR § 63.2485, Table 7, the permit holder shall comply with the requirements of 40 CFR § 63.105 (relating to Maintenance Wastewater Requirements) (Title 30 TAC Chapter 113, Subchapter C, § 113.890 incorporated by reference).
- 11. For miscellaneous chemical process facilities with Group 2 wastewater streams subject to wastewater operations requirements in 40 CFR Part 63, Subpart FFFF, the permit holder shall comply with the requirements of 40 CFR § 63.132(a), (a)(1), (a)(1)(i), and (a)(3) as specified in § 63.2485(a) (Title 30 TAC Chapter 113, Subchapter C, § 113.890 incorporated by reference).

Additional Monitoring Requirements

12. Unless otherwise specified, the permit holder shall comply with the compliance assurance monitoring requirements as specified in the attached “CAM Summary” upon issuance of the permit. In addition, the permit holder shall comply with the following:
 - A. The permit holder shall comply with the terms and conditions contained in 30 TAC § 122.147 (General Terms and Conditions for Compliance Assurance Monitoring).
 - B. The permit holder shall report, consistent with the averaging time identified in the “CAM Summary,” deviations as defined by the deviation limit in the “CAM Summary.” Any monitoring data below a minimum limit or above a maximum limit, that is collected in accordance with the requirements specified in 40 CFR § 64.7(c), shall be reported as a deviation. Deviations shall be reported according to 30 TAC § 122.145 (Reporting Terms and Conditions).
 - C. The permit holder may elect to collect monitoring data on a more frequent basis and average the data, consistent with the averaging time specified in the “CAM Summary,” for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis. In no event shall data be collected and used in particular instances in order to avoid reporting deviations. All monitoring data shall be collected in accordance with the requirements specified in 40 CFR § 64.7(c).
 - D. The permit holder shall operate the monitoring, identified in the attached “CAM Summary,” in accordance with the provisions of 40 CFR § 64.7.
 - E. The permit holder shall comply with either of the following requirements for any particulate matter capture system associated with the control device subject to CAM. If the results of the following inspections indicate that the capture system is not working properly, the permit holder shall promptly take necessary corrective action:
 - (i) Once per year the permit holder shall inspect any fan for proper operation and inspect the capture system used in compliance of CAM for cracks, holes, tears, and other defects; or
 - (ii) Once per year, the permit holder shall inspect for fugitive emissions escaping from the capture system in compliance of CAM by performing a visible emissions observation for a period of at least six minutes in accordance with 40 CFR Part 60, Appendix A, Test Method 22.

- F. The permit holder shall comply with either of the following requirements for any capture system associated with the VOC control device subject to CAM. If the results of the following inspections indicate that the capture system is not working properly, the permit holder shall promptly take necessary corrective actions:
- (i) Once a year the permit holder shall inspect the capture system in compliance of CAM for leaks in accordance with 40 CFR Part 60, Appendix A, Test Method 21. Leaks shall be indicated by an instrument reading greater than or equal to 500 ppm above background or as defined by the underlying applicable requirement; or
 - (ii) Once a month, the permit holder shall conduct a visual, audible, and/or olfactory inspection of the capture system in compliance of CAM to detect leaking components.
- G. The permit holder shall comply with either of the following requirements for any bypass of the control device subject to CAM. If the results of the following inspections or monitoring indicate bypass of the control device, the permit holder shall promptly take necessary corrective actions and report a deviation:
- (i) Install a flow indicator that is capable of recording flow, at least once every fifteen minutes, immediately downstream of each valve that if opened would allow a vent stream to bypass the control device and be emitted, either directly or indirectly, to the atmosphere; or
 - (ii) Once a month, the permit holder shall inspect the valves checking the position of the valves and the condition of the car seals. Identify all times when the car seal has been broken and the valve position has been changed to allow a vent stream to bypass the control device and be emitted, either directly or indirectly, to the atmosphere.
- H. The permit holder shall comply with the requirements of 40 CFR § 70.6(a)(3)(ii)(A) and 30 TAC § 122.144(1)(A)-(F) for documentation of all required inspections.
13. The permit holder shall comply with the periodic monitoring requirements as specified in the attached “Periodic Monitoring Summary” upon issuance of the permit. Except for, as applicable, monitoring malfunctions, associated repairs, and required quality assurance or control activities (including, as applicable, calibration checks and required zero and span adjustments), the permit holder shall conduct all monitoring in continuous operation (or shall collect data at all required intervals) at all times that the pollutant-specific emissions unit is operating. The permit holder may elect to collect monitoring data on a more

frequent basis and average the data, consistent with the averaging time specified in the “Periodic Monitoring Summary,” for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis. In no event shall data be collected and used in particular instances to avoid reporting deviations. Deviations shall be reported according to 30 TAC § 122.145 (Reporting Terms and Conditions).

New Source Review Authorization Requirements

14. Permit holder shall comply with the requirements of New Source Review authorizations issued or claimed by the permit holder for the permitted area, including permits, permits by rule, standard permits, flexible permits, special permits, permits for existing facilities including Voluntary Emissions Reduction Permits and Electric Generating Facility Permits issued under 30 TAC Chapter 116, Subchapter I, or special exemptions referenced in the New Source Review Authorization References attachment. These requirements:
 - A. Are incorporated by reference into this permit as applicable requirements
 - B. Shall be located with this operating permit
 - C. Are not eligible for a permit shield
15. The permit holder shall comply with the general requirements of 30 TAC Chapter 106, Subchapter A or the general requirements, if any, in effect at the time of the claim of any PBR.
16. The permit holder shall maintain records to demonstrate compliance with any emission limitation or standard that is specified in a permit by rule (PBR) or Standard Permit listed in the New Source Review Authorizations attachment. The records shall yield reliable data from the relevant time period that are representative of the emission unit’s compliance with the PBR or Standard Permit. These records may include, but are not limited to, production capacity and throughput, hours of operation, safety data sheets (SDS), chemical composition of raw materials, speciation of air contaminant data, engineering calculations, maintenance records, fugitive data, performance tests, capture/control device efficiencies, direct pollutant monitoring (CEMS, COMS, or PEMS), or control device parametric monitoring. These records shall be made readily accessible and available as required by 30 TAC § 122.144. Any monitoring or recordkeeping data indicating noncompliance with the PBR or Standard Permit shall be considered and reported as a deviation according to 30 TAC § 122.145 (Reporting Terms and Conditions).
17. The permit holder shall comply with the following requirements for Air Quality Standard Permits:
 - A. Registration requirements listed in 30 TAC § 116.611, unless otherwise provided for in an Air Quality Standard Permit

- B. General Conditions listed in 30 TAC § 116.615, unless otherwise provided for in an Air Quality Standard Permit
- C. Applicable requirements of 30 TAC § 116.617 for Pollution Control Projects based on the information contained in the registration application.

Compliance Requirements

- 18. The permit holder shall certify compliance in accordance with 30 TAC § 122.146. The permit holder shall comply with 30 TAC § 122.146 using at a minimum, but not limited to, the continuous or intermittent compliance method data from monitoring, recordkeeping, reporting, or testing required by the permit and any other credible evidence or information. The certification period may not exceed 12 months and the certification must be submitted within 30 days after the end of the period being certified.
- 19. Permit holder shall comply with the following 30 TAC Chapter 117 requirements:
 - A. The permit holder shall comply with the compliance schedules and submit written notification to the TCEQ Executive Director as required in 30 TAC Chapter 117, Subchapter H, Division 1:
 - (i) For sources in the Houston-Galveston-Brazoria Nonattainment area, 30 TAC § 117.9020:
 - (1) Title 30 TAC § 117.9020(2)(A), (C), and (D)
 - B. The permit holder shall comply with the requirements of 30 TAC § 117.354 for Final Control Plan Procedures for Attainment Demonstration Emission Specifications and 30 TAC § 117.356 for Revision of Final Control Plan.
- 20. Use of Emission Credits to comply with applicable requirements:
 - A. Unless otherwise prohibited, the permit holder may use emission credits to comply with the following applicable requirements listed elsewhere in this permit:
 - (i) Title 30 TAC Chapter 115
 - (ii) Title 30 TAC Chapter 117
 - (iii) Offsets for Title 30 TAC Chapter 116
 - B. The permit holder shall comply with the following requirements in order to use the emission credits to comply with the applicable requirements:
 - (i) The permit holder must notify the TCEQ according to 30 TAC § 101.306(c)(2)

- (ii) The emission credits to be used must meet all the geographic, timeliness, applicable pollutant type, and availability requirements listed in 30 TAC Chapter 101, Subchapter H, Division 1
- (iii) The executive director has approved the use of the credit according to 30 TAC § 101.306(c)(2)
- (iv) The permit holder keeps records of the use of credits towards compliance with the applicable requirements in accordance with 30 TAC § 101.302(g) and 30 TAC Chapter 122
- (v) Title 30 TAC § 101.305 (relating to Emission Reductions Achieved Outside the United States)

21. Use of Discrete Emission Credits to comply with the applicable requirements:

A. Unless otherwise prohibited, the permit holder may use discrete emission credits to comply with the following applicable requirements listed elsewhere in this permit:

- (i) Title 30 TAC Chapter 115
- (ii) Title 30 TAC Chapter 117
- (iii) If applicable, offsets for Title 30 TAC Chapter 116
- (iv) Temporarily exceed state NSR permit allowables

B. The permit holder shall comply with the following requirements in order to use the credit to comply with the applicable requirements:

- (i) The permit holder must notify the TCEQ according to 30 TAC § 101.376(d)
- (ii) The discrete emission credits to be used must meet all the geographic, timeliness, applicable pollutant type, and availability requirements listed in 30 TAC Chapter 101, Subchapter H, Division 4
- (iii) The executive director has approved the use of the discrete emission credits according to 30 TAC § 101.376(d)(1)(A)
- (iv) The permit holder keeps records of the use of credits towards compliance with the applicable requirements in accordance with 30 TAC § 101.372(h) and 30 TAC Chapter 122
- (v) Title 30 TAC § 101.375 (relating to Emission Reductions Achieved Outside the United States)

Risk Management Plan

22. For processes subject to 40 CFR Part 68 and specified in 40 CFR § 68.10, the permit holder shall comply with the requirements of the Accidental Release Prevention Provisions in 40 CFR Part 68. The permit holder shall submit to the appropriate agency either a compliance schedule for meeting the requirements of 40 CFR Part 68 by the date provided in 40 CFR § 68.10(a), or as part of the compliance certification submitted under this permit, a certification statement that the source is in compliance with all requirements of 40 CFR Part 68, including the registration and submission of a risk management plan.

Protection of Stratospheric Ozone

23. Permit holders at a site subject to Title VI of the FCAA Amendments shall meet the following requirements for protection of stratospheric ozone:
 - A. Any on site servicing, maintenance, and repair on refrigeration and nonmotor vehicle air-conditioning appliances using ozone-depleting refrigerants or non-exempt substitutes shall be conducted in accordance with 40 CFR Part 82, Subpart F. Permit holders shall ensure that repairs on or refrigerant removal from refrigeration and nonmotor vehicle air-conditioning appliances using ozone-depleting refrigerants are performed only by properly certified technicians using certified equipment. Records shall be maintained as required by 40 CFR Part 82, Subpart F.

Permit Location

24. The permit holder shall maintain a copy of this permit and records related to requirements listed in this permit on site.

Permit Shield (30 TAC § 122.148)

25. A permit shield is granted for the emission units, groups, or processes specified in the attached "Permit Shield." Compliance with the conditions of the permit shall be deemed compliance with the specified potentially applicable requirements or specified potentially applicable state-only requirements listed in the attachment "Permit Shield." Permit shield provisions shall not be modified by the executive director until notification is provided to the permit holder. No later than 90 days after notification of a change in a determination made by the executive director, the permit holder shall apply for the appropriate permit revision to reflect the new determination. Provisional terms are not eligible for this permit shield. Any term or condition, under a permit shield, shall not be protected by the permit shield if it is replaced by a provisional term or condition or the basis of the term and condition changes.

Attachments

Applicable Requirements Summary

Additional Monitoring Requirements

Permit Shield

New Source Review Authorization References

Applicable Requirements Summary

Unit Summary 16

Applicable Requirements Summary 47

Note: A “none” entry may be noted for some emission sources in this permit’s “Applicable Requirements Summary” under the heading of “Monitoring and Testing Requirements” and/or “Recordkeeping Requirements” and/or “Reporting Requirements.” Such a notation indicates that there are no requirements for the indicated emission source as identified under the respective column heading(s) for the stated portion of the regulation when the emission source is operating under the conditions of the specified SOP Index Number. However, other relevant requirements pursuant to 30 TAC Chapter 122 including Recordkeeping Terms and Conditions (30 TAC § 122.144), Reporting Terms and Conditions (30 TAC § 122.145), and Compliance Certification Terms and Conditions (30 TAC § 122.146) continue to apply.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
APIB-7502	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
APIST-7519B	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
APIV-7101	STORAGE TANKS/VESSELS	N/A	R-5112	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
APIV-7101LD	LOADING/UNLOADING OPERATIONS	N/A	R-5211	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.
APIV-7102	STORAGE TANKS/VESSELS	N/A	R-5112	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
APIV-7102LD	LOADING/UNLOADING OPERATIONS	N/A	R5211	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.
APIZ-7402	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
APIZ-7402VNT	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
APIZ-7601	EMISSION	N/A	R5121	30 TAC Chapter 115, Vent	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	POINTS/STATIONARY VENTS/PROCESS VENTS			Gas Controls	
APIZ-7602	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
APIZ-7810	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
CPVC-C2710	CHEMICAL MANUFACTURING PROCESS	N/A	R5160	30 TAC Chapter 115, Batch Processes	No changing attributes.
CPVC-C2710	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	115120-19	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
CPVC-C2710	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	63FFFF	40 CFR Part 63, Subpart FFFF	No changing attributes.
CPVC-C710	CHEMICAL MANUFACTURING PROCESS	N/A	R5160	30 TAC Chapter 115, Batch Processes	No changing attributes.
CPVC-C710	EMISSION POINTS/STATIONARY	N/A	115120-19	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	VENTS/PROCESS VENTS				
CPVC-C710	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	63FFFF	40 CFR Part 63, Subpart FFFF	No changing attributes.
CPVF-C101A	CHEMICAL MANUFACTURING PROCESS	N/A	R5160	30 TAC Chapter 115, Batch Processes	No changing attributes.
CPVF-C101A	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	115120-1	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
CPVF-C102B	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
CPVF-C110	CHEMICAL MANUFACTURING PROCESS	N/A	R5160	30 TAC Chapter 115, Batch Processes	No changing attributes.
CPVF-C110	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	115120-9	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
CPVF-C110	CHEMICAL MANUFACTURING PROCESS	N/A	63FFFF	40 CFR Part 63, Subpart FFFF	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
CPVF-C2101A	CHEMICAL MANUFACTURING PROCESS	N/A	R5160	30 TAC Chapter 115, Batch Processes	No changing attributes.
CPVF-C2101A	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	115120-14	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
CPVF-C2102C	CHEMICAL MANUFACTURING PROCESS	N/A	R5160	30 TAC Chapter 115, Batch Processes	No changing attributes.
CPVF-C2102C	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	115120-15	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
CPVF-C2110	CHEMICAL MANUFACTURING PROCESS	N/A	R5160	30 TAC Chapter 115, Batch Processes	No changing attributes.
CPVF-C2110	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	115120-16	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
CPVF-C2110	CHEMICAL MANUFACTURING PROCESS	N/A	63FFFF	40 CFR Part 63, Subpart FFFF	No changing attributes.
CPVF-C2110	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	63FFFF	40 CFR Part 63, Subpart FFFF	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	VENTS				
CPVF-C2601	CHEMICAL MANUFACTURING PROCESS	N/A	R5160	30 TAC Chapter 115, Batch Processes	No changing attributes.
CPVF-C2601	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	115120-17	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
CPVF-C2603	CHEMICAL MANUFACTURING PROCESS	N/A	R5160	30 TAC Chapter 115, Batch Processes	No changing attributes.
CPVF-C2603	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	115120-18	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
CPVF-C601	CHEMICAL MANUFACTURING PROCESS	N/A	R5160	30 TAC Chapter 115, Batch Processes	No changing attributes.
CPVF-C601	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	115120-10	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
CPVF-C603A	CHEMICAL MANUFACTURING PROCESS	N/A	R5160	30 TAC Chapter 115, Batch Processes	No changing attributes.
CPVF-C603A	EMISSION POINTS/STATIONARY	N/A	115120-11	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	VENTS/PROCESS VENTS				
CPVF-C603B	CHEMICAL MANUFACTURING PROCESS	N/A	R5160	30 TAC Chapter 115, Batch Processes	No changing attributes.
CPVF-C603B	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	115120-12	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
CPVF-C606A	CHEMICAL MANUFACTURING PROCESS	N/A	R5160	30 TAC Chapter 115, Batch Processes	No changing attributes.
CPVF-C606A	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	115120-6	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
CPVF-C606B	CHEMICAL MANUFACTURING PROCESS	N/A	R5160	30 TAC Chapter 115, Batch Processes	No changing attributes.
CPVF-C606B	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	115120-7	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
CPVN-C508	CHEMICAL MANUFACTURING PROCESS	N/A	R5160	30 TAC Chapter 115, Batch Processes	No changing attributes.
CPVN-C508	EMISSION	N/A	115120-8	30 TAC Chapter 115, Vent	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	POINTS/STATIONARY VENTS/PROCESS VENTS			Gas Controls	
CPVSBG2-812	SRIC ENGINES	N/A	R7300	30 TAC Chapter 117, Subchapter B	No changing attributes.
CPVSBG2-812	SRIC ENGINES	N/A	60III	40 CFR Part 60, Subpart III	No changing attributes.
CPVSBG2-812	SRIC ENGINES	N/A	63ZZZZ	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
CPVSBG-812	SRIC ENGINES	N/A	R7300	30 TAC Chapter 117, Subchapter B	No changing attributes.
CPVSBG-812	SRIC ENGINES	N/A	63ZZZZ	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
CPVT-C102A	CHEMICAL MANUFACTURING PROCESS	N/A	R5160	30 TAC Chapter 115, Batch Processes	No changing attributes.
CPVT-C102A	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	115120-2	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
CPVT-C706	CHEMICAL MANUFACTURING PROCESS	N/A	R5160	30 TAC Chapter 115, Batch Processes	No changing attributes.
CPVT-C706	EMISSION POINTS/STATIONARY VENTS/PROCESS	N/A	115120-13	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	VENTS				
CPVT-C706	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	63FFFF	40 CFR Part 63, Subpart FFFF	No changing attributes.
CPVV-C2703	CHEMICAL MANUFACTURING PROCESS	N/A	R5160	30 TAC Chapter 115, Batch Processes	No changing attributes.
CPVV-C2703	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	115120-20	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
CPVV-C2703	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	63FFFF	40 CFR Part 63, Subpart FFFF	No changing attributes.
CPVV-C703A	CHEMICAL MANUFACTURING PROCESS	N/A	R5160	30 TAC Chapter 115, Batch Processes	No changing attributes.
CPVV-C703A	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	115120-4	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
CPVV-C703A	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	63FFFF	40 CFR Part 63, Subpart FFFF	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
CPVV-C703B	CHEMICAL MANUFACTURING PROCESS	N/A	R5160	30 TAC Chapter 115, Batch Processes	No changing attributes.
CPVV-C703B	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	115120-5	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
GRP-UNLOAD	LOADING/UNLOADING OPERATIONS	NUT1T-4207LD, NUT1T-5058LD, NUT1T-5117LD, NUT1T-5321LD	R115UNL-001	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.
MODF-1	FUGITIVE EMISSION UNITS	N/A	63JJJ-001	40 CFR Part 63, Subpart JJJ	No changing attributes.
MODF-2B	FUGITIVE EMISSION UNITS	N/A	63FFFF	40 CFR Part 63, Subpart FFFF	No changing attributes.
MODF-3A	FUGITIVE EMISSION UNITS	N/A	63FFFF	40 CFR Part 63, Subpart FFFF	No changing attributes.
MODF-3A	FUGITIVE EMISSION UNITS	N/A	63JJJ-002	40 CFR Part 63, Subpart JJJ	No changing attributes.
MODF-3B	FUGITIVE EMISSION UNITS	N/A	63FFFF	40 CFR Part 63, Subpart FFFF	No changing attributes.
MODF-3B	FUGITIVE EMISSION UNITS	N/A	63JJJ-003	40 CFR Part 63, Subpart JJJ	No changing attributes.
MODF-3C	FUGITIVE EMISSION UNITS	N/A	63FFFF	40 CFR Part 63, Subpart FFFF	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
MODF-3C	FUGITIVE EMISSION UNITS	N/A	63JJJ-004	40 CFR Part 63, Subpart JJJ	No changing attributes.
MODF-4	FUGITIVE EMISSION UNITS	N/A	63FFFF	40 CFR Part 63, Subpart FFFF	No changing attributes.
MODF-4	FUGITIVE EMISSION UNITS	N/A	63JJJ-005	40 CFR Part 63, Subpart JJJ	No changing attributes.
MODF-5	FUGITIVE EMISSION UNITS	N/A	63FFFF	40 CFR Part 63, Subpart FFFF	No changing attributes.
MODF-5	FUGITIVE EMISSION UNITS	N/A	63JJJ-006	40 CFR Part 63, Subpart JJJ	No changing attributes.
MODP-79901-B	SRIC ENGINES	N/A	R7ICI	30 TAC Chapter 117, Subchapter B	No changing attributes.
MODP-79901-B	SRIC ENGINES	N/A	63ZZZZ-01	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
MODP-79901-C	SRIC ENGINES	N/A	R7ICI	30 TAC Chapter 117, Subchapter B	No changing attributes.
MODP-79901-C	SRIC ENGINES	N/A	63ZZZZ-02	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
MODSBG-001	SRIC ENGINES	N/A	R7ICI	30 TAC Chapter 117, Subchapter B	No changing attributes.
MODSBG-002	SRIC ENGINES	N/A	R7300	30 TAC Chapter 117, Subchapter B	No changing attributes.
MODSBG-002	SRIC ENGINES	N/A	60III	40 CFR Part 60, Subpart III	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
MODSBG-002	SRIC ENGINES	N/A	63ZZZZ	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
MODSBG-003	SRIC ENGINES	N/A	R7ICI	30 TAC Chapter 117, Subchapter B	No changing attributes.
MODSBG-003	SRIC ENGINES	N/A	63ZZZZ-01	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
MODT-121	STORAGE TANKS/VESSELS	N/A	R5112	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
MODT-121LD	LOADING/UNLOADING OPERATIONS	N/A	R5211	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.
MODT-130	STORAGE TANKS/VESSELS	N/A	R5112	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
MODT-130	STORAGE TANKS/VESSELS	N/A	63FFFF-1	40 CFR Part 63, Subpart FFFF	HAL Device Type = No halogen scrubber or other halogen reduction device is used., Prior Test = The data from a prior performance test is not used., Test Waiver = The Administrator has not granted a waiver of the performance test or no waiver has been requested., Bypass Line = No bypass lines., Designated HAL = The emission stream is not designated as halogenated., Determined HAL = The emission stream is determined not to be halogenated., Emission Standard

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					= HAP vapor pressure is < 76.6 and a non-flare CD is being used to meet 95% reduction per § 63.2470(a)-Table 4.1.b.ii, SS Device Type = Combustion device other than a boiler, process heater, or incinerator., Alt 63SS Mon Parameters = Alternate monitoring parameters or requirements have not been approved by the Administrator or have not been requested., Negative Pressure = The closed vent system is operated and maintained at or above atmospheric pressure., CEMS = A continuous parameter monitoring system is used., Formaldehyde = The stream does not contain formaldehyde.
MODT-130	STORAGE TANKS/VESSELS	N/A	63FFFF-2	40 CFR Part 63, Subpart FFFF	Emission Standard = Vapor balance alternative as provided in 40 CFR § 63.2470(e)., Offsite = Railcars or tank trucks are reloaded or cleaned at an offsite facility., Barge = The storage tank is not filled from a barge., Other Part 63 = Not complying with another part 63 subpart as specified in 40 CFR § 63.2535(a)(2).

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
MODT-130	STORAGE TANKS/VESSELS	N/A	63JJJ	40 CFR Part 63, Subpart JJJ	No changing attributes.
MODT-130LD	LOADING/UNLOADING OPERATIONS	N/A	R5211	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.
MODT-140	STORAGE TANKS/VESSELS	N/A	R5112	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
MODT-140	STORAGE TANKS/VESSELS	N/A	60KB	40 CFR Part 60, Subpart Kb	No changing attributes.
MODT-140	STORAGE TANKS/VESSELS	N/A	63FFFF-1	40 CFR Part 63, Subpart FFFF	HAL Device Type = No halogen scrubber or other halogen reduction device is used., Prior Test = The data from a prior performance test is not used., Test Waiver = The Administrator has not granted a waiver of the performance test or no waiver has been requested., Bypass Line = No bypass lines., Designated HAL = The emission stream is not designated as halogenated., Determined HAL = The emission stream is determined not to be halogenated., Emission Standard = HAP vapor pressure is < 76.6 and a non-flare CD is being used to meet 95% reduction per § 63.2470(a)-Table 4.1.b.ii, SS Device Type = Combustion

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					device other than a boiler, process heater, or incinerator., Alt 63SS Mon Parameters = Alternate monitoring parameters or requirements have not been approved by the Administrator or have not been requested., Negative Pressure = The closed vent system is operated and maintained at or above atmospheric pressure., CEMS = A continuous parameter monitoring system is used., Formaldehyde = The stream does not contain formaldehyde.
MODT-140	STORAGE TANKS/VESSELS	N/A	63FFFF-2	40 CFR Part 63, Subpart FFFF	Emission Standard = Vapor balance alternative as provided in 40 CFR § 63.2470(e)., Offsite = Railcars or tank trucks are reloaded or cleaned at an offsite facility., Barge = The storage tank is not filled from a barge., Other Part 63 = Not complying with another part 63 subpart as specified in 40 CFR § 63.2535(a)(2).
MODT-140	STORAGE TANKS/VESSELS	N/A	63JJJ	40 CFR Part 63, Subpart JJJ	No changing attributes.
MODT-140LD	LOADING/UNLOADING OPERATIONS	N/A	R5211	30 TAC Chapter 115, Loading and Unloading of	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
				VOC	
MODT-150	STORAGE TANKS/VESSELS	N/A	R5112	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
MODT-150LD	LOADING/UNLOADING OPERATIONS	N/A	R5211	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.
MODT-2121	STORAGE TANKS/VESSELS	N/A	R5112	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
MODT-2121LD	LOADING/UNLOADING OPERATIONS	N/A	R5211	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.
MODT-2130	STORAGE TANKS/VESSELS	N/A	R5112	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
MODT-2130LD	LOADING/UNLOADING OPERATIONS	N/A	R5211	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.
MODT-3107	STORAGE TANKS/VESSELS	N/A	R5112	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
MODT-3336LD	LOADING/UNLOADING OPERATIONS	N/A	R5211	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.
MODV-2321	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
MODV-3336	LOADING/UNLOADING OPERATIONS	N/A	R5211	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.
MODV-402	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
MODWG-1VNT	CHEMICAL MANUFACTURING PROCESS	N/A	R5160-1	30 TAC Chapter 115, Batch Processes	No changing attributes.
MODWG-1VNT	CHEMICAL MANUFACTURING PROCESS	N/A	R5160-2	30 TAC Chapter 115, Batch Processes	No changing attributes.
MODWG-1VNT	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121-1	30 TAC Chapter 115, Vent Gas Controls	Alternate Control Requirement = not used, Control Device Type = not used
MODWG-1VNT	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121-2	30 TAC Chapter 115, Vent Gas Controls	Alternate Control Requirement = Alternate control is not used., Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).
MODWG-1VNT	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121-3	30 TAC Chapter 115, Vent Gas Controls	Alternate Control Requirement = Alternate control is not used., Control Device Type = Direct flame incinerator in which the

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					vent gas stream is burned at a temperature or at least 1300° F (704 C).
MODZ-1607S	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5720	30 TAC Chapter 115, HRVOC Vent Gas	No changing attributes.
MODZ-1607S	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
MODZ-1607S	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	63JJJ	40 CFR Part 63, Subpart JJJ	No changing attributes.
MODZ- 1607SVNT	CHEMICAL MANUFACTURING PROCESS	N/A	R5160	30 TAC Chapter 115, Batch Processes	No changing attributes.
MODZ- 1607SVNT	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5720	30 TAC Chapter 115, HRVOC Vent Gas	No changing attributes.
MODZ- 1607SVNT	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121-1	30 TAC Chapter 115, Vent Gas Controls	Alternate Control Requirement = not used, Control Device Type = not used
MODZ-	EMISSION	N/A	R5121-2	30 TAC Chapter 115, Vent	Alternate Control Requirement =

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
1607SVNT	POINTS/STATIONARY VENTS/PROCESS VENTS			Gas Controls	Alternate control is not used., Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).
MODZ- 1607SVNT	CHEMICAL MANUFACTURING PROCESS	N/A	63FFFF	40 CFR Part 63, Subpart FFFF	No changing attributes.
MODZ- 1607SVNT	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	63JJJ	40 CFR Part 63, Subpart JJJ	No changing attributes.
MODZ-1608	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5720	30 TAC Chapter 115, HRVOC Vent Gas	No changing attributes.
MODZ-1608	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
MODZ-1608	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	63JJJ	40 CFR Part 63, Subpart JJJ	No changing attributes.
MODZ-1608VNT	CHEMICAL MANUFACTURING PROCESS	N/A	R5160	30 TAC Chapter 115, Batch Processes	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
MODZ-1608VNT	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5720	30 TAC Chapter 115, HRVOC Vent Gas	No changing attributes.
MODZ-1608VNT	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
MODZ-1608VNT	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	63JJJ	40 CFR Part 63, Subpart JJJ	No changing attributes.
MODZ-1781	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	R117-001	30 TAC Chapter 117, Subchapter B	No changing attributes.
MODZ-1781	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	60DC	40 CFR Part 60, Subpart Dc	No changing attributes.
MODZ-2625	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	63JJJ	40 CFR Part 63, Subpart JJJ	No changing attributes.
MODZ-2652	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5720	30 TAC Chapter 115, HRVOC Vent Gas	No changing attributes.
MODZ-2652	EMISSION	N/A	R5121	30 TAC Chapter 115, Vent	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	POINTS/STATIONARY VENTS/PROCESS VENTS			Gas Controls	
MODZ-2652	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	63JJJ	40 CFR Part 63, Subpart JJJ	No changing attributes.
MODZ-2655	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5720	30 TAC Chapter 115, HRVOC Vent Gas	No changing attributes.
MODZ-2655	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
MODZ-2655	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	63JJJ	40 CFR Part 63, Subpart JJJ	No changing attributes.
MODZ-2656	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
MODZ-2753	INDUSTRIAL PROCESS COOLING TOWERS	N/A	R5760	30 TAC Chapter 115, HRVOC Cooling Towers	No changing attributes.
MODZ-2753	INDUSTRIAL PROCESS COOLING TOWERS	N/A	63JJJ	40 CFR Part 63, Subpart JJJ	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
MODZ-2781	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	R117-001	30 TAC Chapter 117, Subchapter B	No changing attributes.
MODZ-2781	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	60DC	40 CFR Part 60, Subpart Dc	No changing attributes.
MODZ-3654	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
MODZ-3655	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
MODZ-3656	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
MODZ-3753	INDUSTRIAL PROCESS COOLING TOWERS	N/A	63FFFF	40 CFR Part 63, Subpart FFFF	No changing attributes.
MODZ-3780	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	R117-001	30 TAC Chapter 117, Subchapter B	No changing attributes.
MODZ-3780	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	60DC	40 CFR Part 60, Subpart Dc	No changing attributes.
MODZ-3781	BOILERS/STEAM	N/A	R117-001	30 TAC Chapter 117,	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	GENERATORS/STEAM GENERATING UNITS			Subchapter B	
MODZ-3781	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	60DC	40 CFR Part 60, Subpart Dc	No changing attributes.
MODZ-652	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5720	30 TAC Chapter 115, HRVOC Vent Gas	No changing attributes.
MODZ-652	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
MODZ-652	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	63JJJ	40 CFR Part 63, Subpart JJJ	No changing attributes.
MODZ-655	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5720	30 TAC Chapter 115, HRVOC Vent Gas	No changing attributes.
MODZ-655	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
MODZ-655	EMISSION POINTS/STATIONARY	N/A	63JJJ	40 CFR Part 63, Subpart JJJ	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	VENTS/PROCESS VENTS				
MODZ-656	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
MODZ-753	INDUSTRIAL PROCESS COOLING TOWERS	N/A	R5760	30 TAC Chapter 115, HRVOC Cooling Towers	No changing attributes.
MODZ-753	INDUSTRIAL PROCESS COOLING TOWERS	N/A	63JJJ	40 CFR Part 63, Subpart JJJ	No changing attributes.
MODZ-780S	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	R117-001	30 TAC Chapter 117, Subchapter B	No changing attributes.
MODZ-780S	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	60Db	40 CFR Part 60, Subpart Db	No changing attributes.
MSAP-S623C	SRIC ENGINES	N/A	R7300	30 TAC Chapter 117, Subchapter B	No changing attributes.
MSAP-S623C	SRIC ENGINES	N/A	60III	40 CFR Part 60, Subpart III	No changing attributes.
MSAP-S623C	SRIC ENGINES	N/A	63ZZZZ	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
MSAT-S106	STORAGE TANKS/VESSELS	N/A	R5112	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
MSAT-S107	STORAGE	N/A	R5112	30 TAC Chapter 115,	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	TANKS/VESSELS			Storage of VOCs	
MSAT-S415	STORAGE TANKS/VESSELS	N/A	R5112	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
MSAT-S503	STORAGE TANKS/VESSELS	N/A	R5112	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
MSAT-S713	STORAGE TANKS/VESSELS	N/A	R5112	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
MSAT-S718	STORAGE TANKS/VESSELS	N/A	R5112	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
MSAT-S719	STORAGE TANKS/VESSELS	N/A	R5112	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
MSAY-S601	INDUSTRIAL PROCESS COOLING TOWERS	N/A	63FFFF	40 CFR Part 63, Subpart FFFF	No changing attributes.
MSAZ-S419	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R1111	30 TAC Chapter 111, Visible Emissions	No changing attributes.
MSAZ-S419	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
MSAZ-S421	FLARES	N/A	R1111	30 TAC Chapter 111, Visible Emissions	No changing attributes.
MSAZ-S421	FLARES	N/A	63A	40 CFR Part 63, Subpart A	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
MSAZ-S421VNT	CHEMICAL MANUFACTURING PROCESS	N/A	R5160	30 TAC Chapter 115, Batch Processes	No changing attributes.
MSAZ-S421VNT	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
MSAZ-S421VNT	CHEMICAL MANUFACTURING PROCESS	N/A	63FFFF	40 CFR Part 63, Subpart FFFF	No changing attributes.
NUT1P-9013	SRIC ENGINES	N/A	R117-1	30 TAC Chapter 117, Subchapter B	No changing attributes.
NUT1P-9013	SRIC ENGINES	N/A	63ZZZZ-01	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
NUT1T-4201	STORAGE TANKS/VESSELS	N/A	R115TNK-001	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
NUT1T-4201	STORAGE TANKS/VESSELS	N/A	60KB-001	40 CFR Part 60, Subpart Kb	No changing attributes.
NUT1T-4207	STORAGE TANKS/VESSELS	N/A	R115TNK-002	30 TAC Chapter 115, Storage of VOCs	Tank Description = Tank using a vapor recovery system (VRS), Control Device Type = Flare
NUT1T-4207	STORAGE TANKS/VESSELS	N/A	R5112-2	30 TAC Chapter 115, Storage of VOCs	Tank Description = Tank using a submerged fill pipe
NUT1T-4211	STORAGE TANKS/VESSELS	N/A	R115TNK-015	30 TAC Chapter 115, Storage of VOCs	Tank Description = Tank using a submerged fill pipe and vapor recovery system, Control Device

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					Type = Flare
NUT1T-4211	STORAGE TANKS/VESSELS	N/A	R5112-2	30 TAC Chapter 115, Storage of VOCs	Tank Description = Tank using a submerged fill pipe
NUT1T-5058	STORAGE TANKS/VESSELS	N/A	R115TNK-003	30 TAC Chapter 115, Storage of VOCs	Tank Description = Tank using a vapor recovery system (VRS), Control Device Type = Flare
NUT1T-5058	STORAGE TANKS/VESSELS	N/A	R5112-2	30 TAC Chapter 115, Storage of VOCs	Tank Description = Tank using a submerged fill pipe
NUT1T-5103	STORAGE TANKS/VESSELS	N/A	R115TNK-016	30 TAC Chapter 115, Storage of VOCs	Tank Description = Tank using a vapor recovery system (VRS), Control Device Type = Flare
NUT1T-5103	STORAGE TANKS/VESSELS	N/A	R5112-2	30 TAC Chapter 115, Storage of VOCs	Tank Description = Tank using a submerged fill pipe
NUT1T-5104	STORAGE TANKS/VESSELS	N/A	R115TNK-004	30 TAC Chapter 115, Storage of VOCs	Tank Description = Tank using a vapor recovery system (VRS), Control Device Type = Flare
NUT1T-5104	STORAGE TANKS/VESSELS	N/A	R5112-2	30 TAC Chapter 115, Storage of VOCs	Tank Description = Tank using a submerged fill pipe
NUT1T-5104	STORAGE TANKS/VESSELS	N/A	63EEEEETNK- 001	40 CFR Part 63, Subpart EEEE	No changing attributes.
NUT1T-5110	STORAGE TANKS/VESSELS	N/A	R115TNK-005	30 TAC Chapter 115, Storage of VOCs	Tank Description = Tank using a vapor recovery system (VRS), Control Device Type = Flare
NUT1T-5110	STORAGE TANKS/VESSELS	N/A	R5112-2	30 TAC Chapter 115, Storage of VOCs	Tank Description = Tank using a submerged fill pipe

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
NUT1T-5110	STORAGE TANKS/VESSELS	N/A	63EEEEETNK- 001	40 CFR Part 63, Subpart EEEE	No changing attributes.
NUT1T-5113	STORAGE TANKS/VESSELS	N/A	R115TNK-006	30 TAC Chapter 115, Storage of VOCs	Tank Description = Tank using a vapor recovery system (VRS), Control Device Type = Flare
NUT1T-5113	STORAGE TANKS/VESSELS	N/A	R5112-2	30 TAC Chapter 115, Storage of VOCs	Tank Description = Tank using a submerged fill pipe
NUT1T-5117	STORAGE TANKS/VESSELS	N/A	R115TNK-007	30 TAC Chapter 115, Storage of VOCs	Tank Description = Tank using a vapor recovery system (VRS), Control Device Type = Flare
NUT1T-5117	STORAGE TANKS/VESSELS	N/A	R5112-2	30 TAC Chapter 115, Storage of VOCs	Tank Description = Tank using a submerged fill pipe
NUT1T-5117	STORAGE TANKS/VESSELS	N/A	63EEEEETNK- 001	40 CFR Part 63, Subpart EEEE	No changing attributes.
NUT1T-5200	STORAGE TANKS/VESSELS	N/A	R115TNK-014	30 TAC Chapter 115, Storage of VOCs	Tank Description = Tank using a vapor recovery system (VRS), Control Device Type = Flare
NUT1T-5200	STORAGE TANKS/VESSELS	N/A	R5112-2	30 TAC Chapter 115, Storage of VOCs	Tank Description = Tank using a submerged fill pipe
NUT1T-5200	STORAGE TANKS/VESSELS	N/A	63EEEEETNK- 001	40 CFR Part 63, Subpart EEEE	No changing attributes.
NUT1T-5200LD	LOADING/UNLOADING OPERATIONS	N/A	R115UNL-002	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.
NUT1T-5205	STORAGE	N/A	R115TNK-008	30 TAC Chapter 115,	Tank Description = Tank using a

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	TANKS/VESSELS			Storage of VOCs	vapor recovery system (VRS), Control Device Type = Flare
NUT1T-5205	STORAGE TANKS/VESSELS	N/A	R5112-2	30 TAC Chapter 115, Storage of VOCs	Tank Description = Tank using a submerged fill pipe
NUT1T-5210	STORAGE TANKS/VESSELS	N/A	R115TNK-009	30 TAC Chapter 115, Storage of VOCs	Tank Description = Tank using a vapor recovery system (VRS), Control Device Type = Flare
NUT1T-5210	STORAGE TANKS/VESSELS	N/A	R5112-2	30 TAC Chapter 115, Storage of VOCs	Tank Description = Tank using a submerged fill pipe
NUT1T-5308	STORAGE TANKS/VESSELS	N/A	R115TNK-010	30 TAC Chapter 115, Storage of VOCs	Tank Description = Tank using a vapor recovery system (VRS), Control Device Type = Flare
NUT1T-5308	STORAGE TANKS/VESSELS	N/A	R5112-2	30 TAC Chapter 115, Storage of VOCs	Tank Description = Tank using a submerged fill pipe
NUT1T-5311	STORAGE TANKS/VESSELS	N/A	R115TNK-011	30 TAC Chapter 115, Storage of VOCs	Tank Description = Tank using a vapor recovery system (VRS), Control Device Type = Flare
NUT1T-5311	STORAGE TANKS/VESSELS	N/A	R5112-2	30 TAC Chapter 115, Storage of VOCs	Tank Description = Tank using a submerged fill pipe
NUT1T-5313	STORAGE TANKS/VESSELS	N/A	R115TNK-012	30 TAC Chapter 115, Storage of VOCs	Tank Description = Tank using a vapor recovery system (VRS), Control Device Type = Flare
NUT1T-5313	STORAGE TANKS/VESSELS	N/A	R5112-2	30 TAC Chapter 115, Storage of VOCs	Tank Description = Tank using a submerged fill pipe
NUT1T-5321	STORAGE	N/A	R115TNK-013	30 TAC Chapter 115,	Tank Description = Tank using a

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	TANKS/VESSELS			Storage of VOCs	vapor recovery system (VRS), Control Device Type = Flare
NUT1T-5321	STORAGE TANKS/VESSELS	N/A	R5112-2	30 TAC Chapter 115, Storage of VOCs	Tank Description = Tank using a submerged fill pipe
NUTB-Q2425	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R115VENT-003	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
NUTB-Q3805	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R115VENT-009	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
NUTB-Q3810	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R115VENT-006	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
NUTB-Q3813	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R115VENT-007	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
NUTB-Q3814	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R115VENT-008	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
NUTLABGEN	SRIC ENGINES	N/A	R117-2	30 TAC Chapter 117, Subchapter B	No changing attributes.
NUTLABGEN	SRIC ENGINES	N/A	63ZZZZ-02	40 CFR Part 63, Subpart	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
				<i>ZZZZ</i>	
NUTY-Q7215	FLARES	N/A	R111-1	30 TAC Chapter 111, Visible Emissions	No changing attributes.
NUTY-Q7215	FLARES	N/A	60A-1	40 CFR Part 60, Subpart A	No changing attributes.
PRO-CPV	CHEMICAL MANUFACTURING PROCESS	N/A	R5160	30 TAC Chapter 115, Batch Processes	No changing attributes.
PRO-CPV	CHEMICAL MANUFACTURING PROCESS	N/A	63FFFF	40 CFR Part 63, Subpart FFFF	No changing attributes.
PRO- MODLINE1&2	CHEMICAL MANUFACTURING PROCESS	N/A	R5160	30 TAC Chapter 115, Batch Processes	No changing attributes.
PRO- MODLINE1&2	CHEMICAL MANUFACTURING PROCESS	N/A	63JJJ	40 CFR Part 63, Subpart JJJ	No changing attributes.
PRO-MODLINE3	CHEMICAL MANUFACTURING PROCESS	N/A	R5160	30 TAC Chapter 115, Batch Processes	No changing attributes.
PRO-MODLINE3	CHEMICAL MANUFACTURING PROCESS	N/A	63FFFF	40 CFR Part 63, Subpart FFFF	No changing attributes.
PRO-MSA	CHEMICAL MANUFACTURING PROCESS	N/A	63FFFF	40 CFR Part 63, Subpart FFFF	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
REGVLOAD	LOADING/UNLOADING OPERATIONS	N/A	R5211	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
APIB-7502	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
APIB-7502	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(B) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream specified in § 115.121(a)(1) of this title with a concentration of VOC < 612 ppmv is exempt from § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
APIST-7519B	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
APIST-7519B	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(B) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream specified in § 115.121(a)(1) of this title with a concentration of VOC < 612 ppmv is exempt from § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
APIV-7101	EU	R-5112	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
APIV-7101LD	EU	R-5211	VOC	30 TAC Chapter 115, Loading and	§ 115.217(a)(1) § 115.212(a)(2)	Vapor pressure (at land-based operations). All land-	§ 115.214(a)(1)(A) § 115.214(a)(1)(A)(i)	§ 115.216 § 115.216(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Unloading of VOC	§ 115.214(a)(1)(B) § 115.214(a)(1)(D) § 115.214(a)(1)(D)(i)	based loading and unloading of VOC with a true vapor pressure less than 0.5 psia is exempt from the requirements of this division, except as specified.	§ 115.215 § 115.215(4)	§ 115.216(3)(B)	
APIV-7102	EU	R-5112	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
APIV-7102LD	EU	R5211	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(a)(1) § 115.212(a)(2) § 115.214(a)(1)(B) § 115.214(a)(1)(D) § 115.214(a)(1)(D)(i)	Vapor pressure (at land-based operations). All land-based loading and unloading of VOC with a true vapor pressure less than 0.5 psia is exempt from the requirements of this division, except as specified.	§ 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.215 § 115.215(4)	§ 115.216 § 115.216(2) § 115.216(3)(B)	None
APIZ-7402	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(a)(1) § 115.121(a)(1) § 115.122(a)(1)(A)	Vent gas affected by §115.121(a)(1) must be controlled properly with a control efficiency > 90% or to a VOC concentration of no more than 20 ppmv (dry, corrected to 3% O ₂ for combustion devices).	[G]§ 115.125 § 115.126(1) § 115.126(1)(A) § 115.126(1)(A)(i) § 115.126(2) ** See CAM Summary	§ 115.126 § 115.126(1) § 115.126(1)(A) § 115.126(1)(A)(i) § 115.126(2)	None
APIZ-7402VNT	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(a)(1) § 115.121(a)(1) § 115.122(a)(1)(A)	Vent gas affected by §115.121(a)(1) must be controlled properly with a control efficiency > 90% or to a VOC concentration of	[G]§ 115.125 § 115.126(1) § 115.126(1)(A) § 115.126(1)(A)(i) § 115.126(2)	§ 115.126 § 115.126(1) § 115.126(1)(A) § 115.126(1)(A)(i) § 115.126(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						no more than 20 ppmv (dry, corrected to 3% O ₂ for combustion devices).	** See CAM Summary		
APIZ-7601	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
APIZ-7601	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(B) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream specified in § 115.121(a)(1) of this title with a concentration of VOC < 612 ppmv is exempt from § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
APIZ-7602	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
APIZ-7602	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(B) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream specified in § 115.121(a)(1) of this title with a concentration of VOC < 612 ppmv is exempt from § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
APIZ-7810	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						requirements of § 115.121(a)(1).			
APIZ-7810	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(B) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream specified in § 115.121(a)(1) of this title with a concentration of VOC < 612 ppmv is exempt from § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
CPVC-C2710	PRO	R5160	VOC	30 TAC Chapter 115, Batch Processes	§ 115.167(2) § 115.162(3)	Combined vents from a batch process train or single unit operations that meet the criteria in § 115.162(2)(A) or (B), respectively, are exempt from the requirements of this division, except for §§115.161(b) and (C), 115.164, and 115.166(2).	§ 115.164(1) § 115.164(2) § 115.166 [G]§ 115.166(2)	§ 115.166 [G]§ 115.166(2)	None
CPVC-C2710	EP	115120-19	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
CPVC-C2710	EP	115120-19	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(B) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream specified in § 115.121(a)(1) of this title with a concentration of VOC < 612 ppmv is exempt from § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
CPVC-C2710	EP	63FFFF	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2455(b) § 63.2455(b)(1) § 63.2455(b)(2) § 63.2455(b)(3)	For each continuous process vent, you must either designate the vent as a Group 1 continuous process vent or determine the total	§ 63.115(d) [G]§ 63.115(d)(1) § 63.115(d)(2) § 63.115(d)(2)(i) [G]§ 63.115(d)(2)(ii)	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						resource effectiveness (TRE) index value as specified in §63.115(d), except as specified in paragraphs (b)(1)-(3) of this section.	§ 63.115(d)(2)(iii) § 63.115(d)(2)(iv) § 63.115(d)(3)(i) § 63.115(d)(3)(ii)		
CPVC-C710	PRO	R5160	VOC	30 TAC Chapter 115, Batch Processes	§ 115.167(2) § 115.162(3)	Combined vents from a batch process train or single unit operations that meet the criteria in § 115.162(2)(A) or (B), respectively, are exempt from the requirements of this division, except for §§115.161(b) and (C), 115.164, and 115.166(2).	§ 115.164(1) § 115.164(2) § 115.166 [G]§ 115.166(2)	§ 115.166 [G]§ 115.166(2)	None
CPVC-C710	EP	115120-19	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
CPVC-C710	EP	115120-19	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(B) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream specified in § 115.121(a)(1) of this title with a concentration of VOC < 612 ppmv is exempt from § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
CPVC-C710	EP	63FFFF	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2455(b) § 63.2455(b)(1) § 63.2455(b)(2) § 63.2455(b)(3)	For each continuous process vent, you must either designate the vent as a Group 1 continuous process vent or determine the total resource effectiveness (TRE) index value as	§ 63.115(d) [G]§ 63.115(d)(1) § 63.115(d)(2) § 63.115(d)(2)(i) [G]§ 63.115(d)(2)(ii) § 63.115(d)(2)(iii) § 63.115(d)(2)(iv)	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						specified in §63.115(d), except as specified in paragraphs (b)(1)-(3) of this section.	§ 63.115(d)(3)(i) § 63.115(d)(3)(ii)		
CPVF-C101A	PRO	R5160	VOC	30 TAC Chapter 115, Batch Processes	§ 115.167(2) § 115.162(3)	Combined vents from a batch process train or single unit operations that meet the criteria in § 115.162(2)(A) or (B), respectively, are exempt from the requirements of this division, except for §§115.161(b) and (C), 115.164, and 115.166(2).	§ 115.164(1) § 115.164(2) § 115.166 [G]§ 115.166(2)	§ 115.166 [G]§ 115.166(2)	None
CPVF-C101A	EP	115120-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
CPVF-C101A	EP	115120-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(B) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream specified in § 115.121(a)(1) of this title with a concentration of VOC < 612 ppmv is exempt from § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
CPVF-C102B	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
CPVF-C102B	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(B) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream specified in § 115.121(a)(1) of this title with a concentration of VOC < 612 ppmv is exempt from § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
CPVF-C110	PRO	R5160	VOC	30 TAC Chapter 115, Batch Processes	§ 115.167(2) § 115.162(3)	Combined vents from a batch process train or single unit operations that meet the criteria in § 115.162(2)(A) or (B), respectively, are exempt from the requirements of this division, except for §§115.161(b) and (C), 115.164, and 115.166(2).	§ 115.164(1) § 115.164(2) § 115.166 [G]§ 115.166(2)	§ 115.166 [G]§ 115.166(2)	None
CPVF-C110	EP	115120-9	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
CPVF-C110	EP	115120-9	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(B) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream specified in § 115.121(a)(1) of this title with a concentration of VOC < 612 ppmv is exempt from § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
CPVF-C110	EP	63FFFF	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2460(a) § 63.2450(b) § 63.2460(b)	You must meet each emission limit in Table 2 to this subpart that applies to you, and you must meet each applicable requirement specified in §63.2460(b) and (c).	[G]§ 63.1257(d)(2)(i) [G]§ 63.1257(d)(2)(ii) § 63.2460(b)(1) § 63.2460(b)(2) § 63.2460(b)(3) [G]§ 63.2460(b)(4)	§ 63.2460(b)(6)(i) § 63.2460(b)(7)	§ 63.2460(b)(6) § 63.2460(b)(6)(i) § 63.2460(b)(6)(ii) § 63.2460(b)(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 63.2460(b)(7)		
CPVF-C2101A	PRO	R5160	VOC	30 TAC Chapter 115, Batch Processes	§ 115.167(2) § 115.162(3)	Combined vents from a batch process train or single unit operations that meet the criteria in § 115.162(2)(A) or (B), respectively, are exempt from the requirements of this division, except for §§115.161(b) and (C), 115.164, and 115.166(2).	§ 115.164(1) § 115.164(2) § 115.166 [G]§ 115.166(2)	§ 115.166 [G]§ 115.166(2)	None
CPVF-C2101A	EP	115120-14	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
CPVF-C2101A	EP	115120-14	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(B) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream specified in § 115.121(a)(1) of this title with a concentration of VOC < 612 ppmv is exempt from § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
CPVF-C2102C	PRO	R5160	VOC	30 TAC Chapter 115, Batch Processes	§ 115.167(2) § 115.162(3)	Combined vents from a batch process train or single unit operations that meet the criteria in § 115.162(2)(A) or (B), respectively, are exempt from the requirements of this division, except for §§115.161(b) and (C), 115.164, and 115.166(2).	§ 115.164(1) § 115.164(2) § 115.166 [G]§ 115.166(2)	§ 115.166 [G]§ 115.166(2)	None
CPVF-	EP	115120-15	VOC	30 TAC Chapter	§ 115.127(a)(2)(A)	A vent gas stream having a	[G]§ 115.125	§ 115.126	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
C2102C				115, Vent Gas Controls	[G]§ 115.122(a)(4) § 115.127(a)(2)	combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	§ 115.126(2)	§ 115.126(2) § 115.126(4)	
CPVF-C2102C	EP	115120-15	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(B) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream specified in § 115.121(a)(1) of this title with a concentration of VOC < 612 ppmv is exempt from § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
CPVF-C2110	PRO	R5160	VOC	30 TAC Chapter 115, Batch Processes	§ 115.167(2) § 115.162(3)	Combined vents from a batch process train or single unit operations that meet the criteria in § 115.162(2)(A) or (B), respectively, are exempt from the requirements of this division, except for §§115.161(b) and (C), 115.164, and 115.166(2).	§ 115.164(1) § 115.164(2) § 115.166 [G]§ 115.166(2)	§ 115.166 [G]§ 115.166(2)	None
CPVF-C2110	EP	115120-16	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
CPVF-C2110	EP	115120-16	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(B) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream specified in § 115.121(a)(1) of this title with a concentration of VOC < 612 ppmv is exempt from § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
CPVF-C2110	EP	63FFFF	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2460(a) § 63.2450(b) § 63.2460(b)	You must meet each emission limit in Table 2 to this subpart that applies to you, and you must meet each applicable requirement specified in §63.2460(b) and (c).	[G]§ 63.1257(d)(2)(i) [G]§ 63.1257(d)(2)(ii) § 63.2460(b)(1) § 63.2460(b)(2) § 63.2460(b)(3) [G]§ 63.2460(b)(4) § 63.2460(b)(7)	§ 63.2460(b)(6)(i) § 63.2460(b)(7)	§ 63.2460(b)(6) § 63.2460(b)(6)(i) § 63.2460(b)(6)(ii) § 63.2460(b)(7)
CPVF-C2110	EP	63FFFF	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2455(b) § 63.2455(b)(1) § 63.2455(b)(2) § 63.2455(b)(3)	For each continuous process vent, you must either designate the vent as a Group 1 continuous process vent or determine the total resource effectiveness (TRE) index value as specified in §63.115(d), except as specified in paragraphs (b)(1)-(3) of this section.	§ 63.115(d) [G]§ 63.115(d)(1) § 63.115(d)(2) § 63.115(d)(2)(i) [G]§ 63.115(d)(2)(ii) § 63.115(d)(2)(iii) § 63.115(d)(2)(iv) § 63.115(d)(3)(i) § 63.115(d)(3)(ii)	None	None
CPVF-C2601	PRO	R5160	VOC	30 TAC Chapter 115, Batch Processes	§ 115.167(2) § 115.162(3)	Combined vents from a batch process train or single unit operations that meet the criteria in § 115.162(2)(A) or (B), respectively, are exempt from the requirements of this division, except for §§115.161(b) and (C), 115.164, and 115.166(2).	§ 115.164(1) § 115.164(2) § 115.166 [G]§ 115.166(2)	§ 115.166 [G]§ 115.166(2)	None
CPVF-C2601	EP	115120-17	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of §	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						115.121(a)(1).			
CPVF-C2601	EP	115120-17	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(B) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream specified in § 115.121(a)(1) of this title with a concentration of VOC < 612 ppmv is exempt from § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
CPVF-C2603	PRO	R5160	VOC	30 TAC Chapter 115, Batch Processes	§ 115.167(2) § 115.162(3)	Combined vents from a batch process train or single unit operations that meet the criteria in § 115.162(2)(A) or (B), respectively, are exempt from the requirements of this division, except for §§115.161(b) and (C), 115.164, and 115.166(2).	§ 115.164(1) § 115.164(2) § 115.166 [G]§ 115.166(2)	§ 115.166 [G]§ 115.166(2)	None
CPVF-C2603	EP	115120-18	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
CPVF-C2603	EP	115120-18	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(B) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream specified in § 115.121(a)(1) of this title with a concentration of VOC < 612 ppmv is exempt from § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
CPVF-C601	PRO	R5160	VOC	30 TAC Chapter 115, Batch Processes	§ 115.167(2) § 115.162(3)	Combined vents from a batch process train or single unit operations that meet the criteria in § 115.162(2)(A) or (B), respectively, are exempt	§ 115.164(1) § 115.164(2) § 115.166 [G]§ 115.166(2)	§ 115.166 [G]§ 115.166(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						from the requirements of this division, except for §§115.161(b) and (C), 115.164, and 115.166(2).			
CPVF-C601	EP	115120-10	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
CPVF-C601	EP	115120-10	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(B) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream specified in § 115.121(a)(1) of this title with a concentration of VOC < 612 ppmv is exempt from § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
CPVF-C603A	PRO	R5160	VOC	30 TAC Chapter 115, Batch Processes	§ 115.167(2) § 115.162(3)	Combined vents from a batch process train or single unit operations that meet the criteria in § 115.162(2)(A) or (B), respectively, are exempt from the requirements of this division, except for §§115.161(b) and (C), 115.164, and 115.166(2).	§ 115.164(1) § 115.164(2) § 115.166 [G]§ 115.166(2)	§ 115.166 [G]§ 115.166(2)	None
CPVF-C603A	EP	115120-11	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
CPVF-C603A	EP	115120-11	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(B) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream specified in § 115.121(a)(1) of this title with a concentration of VOC < 612 ppmv is exempt from § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
CPVF-C603B	PRO	R5160	VOC	30 TAC Chapter 115, Batch Processes	§ 115.167(2) § 115.162(3)	Combined vents from a batch process train or single unit operations that meet the criteria in § 115.162(2)(A) or (B), respectively, are exempt from the requirements of this division, except for §§115.161(b) and (C), 115.164, and 115.166(2).	§ 115.164(1) § 115.164(2) § 115.166 [G]§ 115.166(2)	§ 115.166 [G]§ 115.166(2)	None
CPVF-C603B	EP	115120-12	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
CPVF-C603B	EP	115120-12	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(B) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream specified in § 115.121(a)(1) of this title with a concentration of VOC < 612 ppmv is exempt from § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
CPVF-C606A	PRO	R5160	VOC	30 TAC Chapter 115, Batch Processes	§ 115.167(2) § 115.162(3)	Combined vents from a batch process train or single unit operations that meet the criteria in § 115.162(2)(A) or (B), respectively, are exempt from the requirements of this division, except for	§ 115.164(1) § 115.164(2) § 115.166 [G]§ 115.166(2)	§ 115.166 [G]§ 115.166(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						§§115.161(b) and (C), 115.164, and 115.166(2).			
CPVF-C606A	EP	115120-6	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
CPVF-C606A	EP	115120-6	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(B) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream specified in § 115.121(a)(1) of this title with a concentration of VOC < 612 ppmv is exempt from § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
CPVF-C606B	PRO	R5160	VOC	30 TAC Chapter 115, Batch Processes	§ 115.167(2) § 115.162(3)	Combined vents from a batch process train or single unit operations that meet the criteria in § 115.162(2)(A) or (B), respectively, are exempt from the requirements of this division, except for §§115.161(b) and (C), 115.164, and 115.166(2).	§ 115.164(1) § 115.164(2) § 115.166 [G]§ 115.166(2)	§ 115.166 [G]§ 115.166(2)	None
CPVF-C606B	EP	115120-7	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
CPVF-C606B	EP	115120-7	VOC	30 TAC Chapter 115, Vent Gas	§ 115.127(a)(2)(B) [G]§ 115.122(a)(4)	A vent gas stream specified in § 115.121(a)(1) of this title	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Controls	§ 115.127(a)(2)	with a concentration of VOC < 612 ppmv is exempt from § 115.121(a)(1).		§ 115.126(4)	
CPVN-C508	PRO	R5160	VOC	30 TAC Chapter 115, Batch Processes	§ 115.167(2) § 115.162(3)	Combined vents from a batch process train or single unit operations that meet the criteria in § 115.162(2)(A) or (B), respectively, are exempt from the requirements of this division, except for §§115.161(b) and (C), 115.164, and 115.166(2).	§ 115.164(1) § 115.164(2) § 115.166 [G]§ 115.166(2)	§ 115.166 [G]§ 115.166(2)	None
CPVN-C508	EP	115120-8	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
CPVN-C508	EP	115120-8	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(B) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream specified in § 115.121(a)(1) of this title with a concentration of VOC < 612 ppmv is exempt from § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
CPVSBG2-812	EU	R7300	EXEMPT	30 TAC Chapter 117, Subchapter B	[G]§ 117.303(a)(11) [G]§ 117.310(f)	Units exempted from the provisions of this division except as specified in §§117.310(f), 117.340(j), 117.345(f)(6) and (10), 117.350(c)(1) and 117.354(a)(5) include new, modified, reconstructed, or relocated stationary diesel engine placed into service	None	§ 117.340(j) [G]§ 117.345(f)(10) [G]§ 117.345(f)(6)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						on or after October 1, 2001, that operates less than 100 hours per year, based on a rolling 12-month average, in other than emergency situations; and meets the requirements for non-road engines as specified. §117.303(a)(11)(A)-(B)			
CPVSBG2-812	EU	6oIII	CO	40 CFR Part 60, Subpart III	§ 60.4205(b) § 60.4202(a)(2) § 60.4206 [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218 § 89.112(a)	Owners and operators of emergency stationary CI ICE, that are not fire pump engines, with a maximum engine power greater than or equal to 130 KW and less than or equal to 2237 KW and a displacement of less than 10 liters per cylinder and is a 2007 model year and later must comply with a CO emission limit of 3.5 g/KW-hr, as stated in 40 CFR 60.4202(a)(2) and 40 CFR 89.112(a).	§ 60.4209(a)	§ 60.4214(b)	[G]§ 60.4214(d)
CPVSBG2-812	EU	6oIII	NMHC and NO _x	40 CFR Part 60, Subpart III	§ 60.4205(b) § 60.4202(a)(2) § 60.4206 [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218 § 89.112(a)	Owners and operators of emergency stationary CI ICE, that are not fire pump engines, with a maximum engine power greater than or equal to 75 KW and less than or equal to 560 KW and a displacement of less than 10 liters per cylinder and is a 2007 model year and later must comply with an NMHC+NO _x emission limit of 4.0 g/KW-hr, as stated in 40 CFR	§ 60.4209(a)	§ 60.4214(b)	[G]§ 60.4214(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						60.4202(a)(2) and 40 CFR 89.112(a).			
CPVSBG2-812	EU	6oIII	PM (OPACITY)	40 CFR Part 60, Subpart III	§ 60.4205(b) § 60.4202(a)(2) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218 § 89.113(a)(1) § 89.113(a)(2) § 89.113(a)(3)	Emergency stationary CI ICE, that are not fire pump engines, with displacement < 10 lpc and not constant-speed engines, with max engine power < 2237 KW and a 2007 model year and later or max engine power > 2237 KW and a 2011 model year and later, must comply with following opacity emission limits: 20% during acceleration, 15% during lugging, 50% during peaks in either acceleration or lugging modes as stated in §60.4202(a)(1)-(2), (b)(2) and §89.113(a)(1)-(3) and §1039.105(b)(1)-(3).	§ 60.4209(a)	§ 60.4214(b)	[G]§ 60.4214(d)
CPVSBG2-812	EU	6oIII	PM	40 CFR Part 60, Subpart III	§ 60.4205(b) § 60.4202(a)(2) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218 § 89.112(a)	Owners and operators of emergency stationary CI ICE, that are not fire pump engines, with a maximum engine power greater than or equal to 130 KW and less than or equal to 2237 KW and a displacement of less than 10 liters per cylinder and is a 2007 model year and later must comply with a PM emission limit of 0.20 g/KW-hr, as stated in 40 CFR 60.4202(a)(2) and 40 CFR 89.112(a).	§ 60.4209(a)	§ 60.4214(b)	[G]§ 60.4214(d)
CPVSBG2-	EU	63ZZZZ	112(B)	40 CFR Part 63,	§ 63.6590(c)	Stationary RICE subject to	None	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
812			HAPS	Subpart ZZZZ		Regulations under 40 CFR Part 60. An affected source that meets any of the criteria in paragraphs (c)(1) through (7) of this section must meet the requirements of this part by meeting the requirements of 40 CFR part 60 subpart IIII, for compression ignition engines or 40 CFR part 60 subpart JJJJ, for spark ignition engines as applicable. No further requirements apply for such engines under this part.			
CPVSBG-812	EU	R7300	EXEMPT	30 TAC Chapter 117, Subchapter B	[G]§ 117.303(a)(11) [G]§ 117.310(f)	Units exempted from the provisions of this division except as specified in §§117.310(f), 117.340(j), 117.345(f)(6) and (10), 117.350(c)(1) and 117.354(a)(5) include new, modified, reconstructed, or relocated stationary diesel engine placed into service on or after October 1, 2001, that operates less than 100 hours per year, based on a rolling 12-month average, in other than emergency situations; and meets the requirements for non-road engines as specified. §117.303(a)(11)(A)-(B)	None	§ 117.340(j) [G]§ 117.345(f)(10) [G]§ 117.345(f)(6)	None
CPVSBG-812	EU	63ZZZZ	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(c)	Stationary RICE subject to Regulations under 40 CFR Part 60. An affected source	None	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						that meets any of the criteria in paragraphs (c)(1) through (7) of this section must meet the requirements of this part by meeting the requirements of 40 CFR part 60 subpart IIII, for compression ignition engines or 40 CFR part 60 subpart JJJJ, for spark ignition engines as applicable. No further requirements apply for such engines under this part.			
CPVT-C102A	PRO	R5160	VOC	30 TAC Chapter 115, Batch Processes	§ 115.167(2) § 115.162(3)	Combined vents from a batch process train or single unit operations that meet the criteria in § 115.162(2)(A) or (B), respectively, are exempt from the requirements of this division, except for §§115.161(b) and (C), 115.164, and 115.166(2).	§ 115.164(1) § 115.164(2) § 115.166 [G]§ 115.166(2)	§ 115.166 [G]§ 115.166(2)	None
CPVT-C102A	EP	115120-2	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
CPVT-C102A	EP	115120-2	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(B) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream specified in § 115.121(a)(1) of this title with a concentration of VOC < 612 ppmv is exempt from § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
CPVT-C706	PRO	R5160	VOC	30 TAC Chapter 115, Batch Processes	§ 115.167(2) § 115.162(3)	Combined vents from a batch process train or single unit operations that meet the criteria in § 115.162(2)(A) or (B), respectively, are exempt from the requirements of this division, except for §§115.161(b) and (C), 115.164, and 115.166(2).	§ 115.164(1) § 115.164(2) § 115.166 [G]§ 115.166(2)	§ 115.166 [G]§ 115.166(2)	None
CPVT-C706	EP	115120-13	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
CPVT-C706	EP	115120-13	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(B) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream specified in § 115.121(a)(1) of this title with a concentration of VOC < 612 ppmv is exempt from § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
CPVT-C706	EP	63FFFF	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2455(b) § 63.2455(b)(1) § 63.2455(b)(2) § 63.2455(b)(3)	For each continuous process vent, you must either designate the vent as a Group 1 continuous process vent or determine the total resource effectiveness (TRE) index value as specified in §63.115(d), except as specified in paragraphs (b)(1)-(3) of this section.	§ 63.115(d) [G]§ 63.115(d)(1) § 63.115(d)(2) § 63.115(d)(2)(i) [G]§ 63.115(d)(2)(ii) § 63.115(d)(2)(iii) § 63.115(d)(2)(iv) § 63.115(d)(3)(i) § 63.115(d)(3)(ii)	None	None
CPVV-C2703	PRO	R5160	VOC	30 TAC Chapter 115, Batch	§ 115.167(2) § 115.162(3)	Combined vents from a batch process train or single	§ 115.164(1) § 115.164(2)	§ 115.166 [G]§ 115.166(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Processes		unit operations that meet the criteria in § 115.162(2)(A) or (B), respectively, are exempt from the requirements of this division, except for §§115.161(b) and (C), 115.164, and 115.166(2).	§ 115.166 [G]§ 115.166(2)		
CPVV-C2703	EP	115120-20	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
CPVV-C2703	EP	115120-20	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(B) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream specified in § 115.121(a)(1) of this title with a concentration of VOC < 612 ppmv is exempt from § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
CPVV-C2703	EP	63FFFF	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2455(b) § 63.2455(b)(1) § 63.2455(b)(2) § 63.2455(b)(3)	For each continuous process vent, you must either designate the vent as a Group 1 continuous process vent or determine the total resource effectiveness (TRE) index value as specified in §63.115(d), except as specified in paragraphs (b)(1)-(3) of this section.	§ 63.115(d) [G]§ 63.115(d)(1) § 63.115(d)(2) § 63.115(d)(2)(i) [G]§ 63.115(d)(2)(ii) § 63.115(d)(2)(iii) § 63.115(d)(2)(iv) § 63.115(d)(3)(i) § 63.115(d)(3)(ii)	None	None
CPVV-C703A	PRO	R5160	VOC	30 TAC Chapter 115, Batch Processes	§ 115.167(2) § 115.162(3)	Combined vents from a batch process train or single unit operations that meet the criteria in §	§ 115.164(1) § 115.164(2) § 115.166 [G]§ 115.166(2)	§ 115.166 [G]§ 115.166(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						115.162(2)(A) or (B), respectively, are exempt from the requirements of this division, except for §§115.161(b) and (C), 115.164, and 115.166(2).			
CPVV-C703A	EP	115120-4	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
CPVV-C703A	EP	115120-4	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(B) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream specified in § 115.121(a)(1) of this title with a concentration of VOC < 612 ppmv is exempt from § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
CPVV-C703A	EP	63FFFF	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2455(b) § 63.2455(b)(1) § 63.2455(b)(2) § 63.2455(b)(3)	For each continuous process vent, you must either designate the vent as a Group 1 continuous process vent or determine the total resource effectiveness (TRE) index value as specified in §63.115(d), except as specified in paragraphs (b)(1)-(3) of this section.	§ 63.115(d) [G]§ 63.115(d)(1) § 63.115(d)(2) § 63.115(d)(2)(i) [G]§ 63.115(d)(2)(ii) § 63.115(d)(2)(iii) § 63.115(d)(2)(iv) § 63.115(d)(3)(i) § 63.115(d)(3)(ii)	None	None
CPVV-C703B	PRO	R5160	VOC	30 TAC Chapter 115, Batch Processes	§ 115.167(2) § 115.162(3)	Combined vents from a batch process train or single unit operations that meet the criteria in § 115.162(2)(A) or (B), respectively, are exempt	§ 115.164(1) § 115.164(2) § 115.166 [G]§ 115.166(2)	§ 115.166 [G]§ 115.166(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						from the requirements of this division, except for §§115.161(b) and (C), 115.164, and 115.166(2).			
CPVV-C703B	EP	115120-5	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
CPVV-C703B	EP	115120-5	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(B) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream specified in § 115.121(a)(1) of this title with a concentration of VOC < 612 ppmv is exempt from § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
GRP-UNLOAD	EU	R115UNL-001	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.212(a)(3) § 115.212(a)(2) § 115.212(a)(3)(A) § 115.212(a)(3)(A)(ii) § 115.212(a)(3)(B) [G]§ 115.212(a)(3)(C) § 115.212(a)(3)(D) § 115.214(a)(1)(B) § 115.214(a)(1)(C)	All land-based VOC transfer to or from transport vessels shall be conducted in the manner specified for leak-free operations.	§ 115.212(a)(3)(B) § 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.214(a)(1)(A)(ii) § 115.214(a)(1)(A)(iii)	§ 115.216 § 115.216(3)(A) § 115.216(3)(A)(i) § 115.216(3)(A)(iii)	None
MODF-1	EU	63JJJ-001	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1331(a) [G]§ 63.1311(o) § 63.1331(a)(1) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h)	The owner or operator of each affected source, shall comply with the requirements of subpart H for pumps in light liquid service, with exceptions noted in paragraphs (a)(1) - (a)(13) of § 63.1331.	§ 63.1331(a)(8) [G]§ 63.163 [G]§ 63.176 [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(3) § 63.181(h)(4) [G]§ 63.181(h)(5)	§ 63.1331(a)(4) § 63.1331(a)(5) § 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 63.163 [G]§ 63.171 [G]§ 63.176			§ 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(8) § 63.181(h)(9)	[G]§ 63.182(d)
MODF-1	EU	63JJJ-001	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1331(a) [G]§ 63.1311(o) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.165 [G]§ 63.171	The owner or operator of each affected source, shall comply with the requirements of subpart H for pressure relief devices in gas/vapor service, with exceptions noted in paragraphs (a)(1) - (a)(13) of § 63.1331.	§ 63.1331(a)(8) [G]§ 63.165 [G]§ 63.180(b) [G]§ 63.180(c) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(f)	§ 63.1331(a)(4) § 63.1331(a)(5) § 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
MODF-1	EU	63JJJ-001	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1331(a) [G]§ 63.1311(o) § 63.1331(a)(7) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.166 [G]§ 63.171	The owner or operator of each affected source, shall comply with the requirements of subpart H for sampling connection systems, with exceptions noted in paragraphs (a)(1) - (a)(13) of § 63.1331.	§ 63.1331(a)(8) [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c)	§ 63.1331(a)(4) § 63.1331(a)(5) § 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
MODF-1	EU	63JJJ-001	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1331(a) [G]§ 63.1311(o) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.168 [G]§ 63.171 [G]§ 63.175	The owner or operator of each affected source, shall comply with the requirements of subpart H for valves in light liquid or gas/vapor service, with exceptions noted in paragraphs (a)(1) - (a)(13) of § 63.1331.	§ 63.1331(a)(8) [G]§ 63.168 [G]§ 63.175 [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(9)	§ 63.1331(a)(4) § 63.1331(a)(5) § 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
MODF-1	EU	63JJJ-001	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1331(a) [G]§ 63.1311(o)	The owner or operator of each affected source, shall	§ 63.1331(a)(8) [G]§ 63.173	§ 63.181(a) [G]§ 63.181(b)	§ 63.1331(a)(4) § 63.1331(a)(5)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.1331(a)(1) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.173	comply with the requirements of subpart H for agitators in gas/vapor or light liquid service, with exceptions noted in paragraphs (a)(1) - (a)(13) of § 63.1331.	[G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4)	§ 63.181(c) [G]§ 63.181(d)	§ 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
MODF-1	EU	63JJJ-001	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1331(a) [G]§ 63.1311(o) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.174	The owner or operator of each affected source, shall comply with the requirements of subpart H for connectors in gas/vapor or light liquid service, with exceptions noted in paragraphs (a)(1) - (a)(13) of § 63.1331.	§ 63.1331(a)(8) [G]§ 63.174 [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	§ 63.1331(a)(4) § 63.1331(a)(5) § 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
MODF-1	EU	63JJJ-001	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1331(a) [G]§ 63.1311(o) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171	The owner or operator of each affected source, shall comply with the requirements of subpart H for instrumentation systems, with exceptions noted in paragraphs (a)(1) - (a)(13) of § 63.1331.	§ 63.1331(a)(8) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	§ 63.1331(a)(4) § 63.1331(a)(5) § 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
MODF-1	EU	63JJJ-001	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1331(a) [G]§ 63.1311(o) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171	The owner or operator of each affected source, shall comply with the requirements of subpart H for pressure relief devices in liquid service, with exceptions noted in paragraphs (a)(1) - (a)(13) of § 63.1331.	§ 63.1331(a)(8) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	§ 63.1331(a)(4) § 63.1331(a)(5) § 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
MODF-1	EU	63JJJ-001	112(B)	40 CFR Part 63,	§ 63.1331(a)	The owner or operator of	§ 63.1331(a)(8)	§ 63.118(a)(3)	§ 63.1331(a)(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
			HAPS	Subpart JJJ	[G]§ 63.1311(o) § 63.172(a) [G]§ 63.172(h) § 63.172(i) § 63.172(j)(1) § 63.172(j)(2) § 63.172(m)	each affected source, shall comply with the requirements of subpart H for closed vent systems, with exceptions noted in paragraphs (a)(1) - (a)(13) of § 63.1331.	[G]§ 63.172(f)(1) [G]§ 63.172(f)(2) § 63.172(g) [G]§ 63.172(h) § 63.172(j)(1) § 63.172(j)(2) [G]§ 63.172(k) [G]§ 63.172(l) [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4)	§ 63.172(j)(1) [G]§ 63.172(k) [G]§ 63.172(l) § 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(g) § 63.181(g)(1)(i) § 63.181(g)(1)(ii) [G]§ 63.181(g)(2) [G]§ 63.181(g)(3)	§ 63.1331(a)(5) § 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
MODF-2B	EU	63FFFF	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2480(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart FFFF	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart FFFF	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart FFFF	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart FFFF	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart FFFF
MODF-3A	EU	63FFFF	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2480(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart FFFF	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart FFFF	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart FFFF	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart FFFF	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart FFFF
MODF-3A	EU	63JJJ-002	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1331(a) [G]§ 63.1311(o) § 63.1331(a)(1) § 63.162(a)	The owner or operator of each affected source, shall comply with the requirements of subpart H	§ 63.1331(a)(8) [G]§ 63.163 [G]§ 63.176 [G]§ 63.180(b)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	§ 63.1331(a)(4) § 63.1331(a)(5) § 63.182(a)(2) § 63.182(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.163 [G]§ 63.171 [G]§ 63.176	for pumps in light liquid service, with exceptions noted in paragraphs (a)(1) - (a)(13) of § 63.1331.	§ 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4)	§ 63.181(h) [G]§ 63.181(h)(3) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(8) § 63.181(h)(9)	[G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
MODF-3A	EU	63JJJ-002	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1331(a) [G]§ 63.1311(o) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.165 [G]§ 63.171	The owner or operator of each affected source, shall comply with the requirements of subpart H for pressure relief devices in gas/vapor service, with exceptions noted in paragraphs (a)(1) - (a)(13) of § 63.1331.	§ 63.1331(a)(8) [G]§ 63.165 [G]§ 63.180(b) [G]§ 63.180(c) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(f)	§ 63.1331(a)(4) § 63.1331(a)(5) § 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
MODF-3A	EU	63JJJ-002	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1331(a) [G]§ 63.1311(o) § 63.1331(a)(7) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.166 [G]§ 63.171	The owner or operator of each affected source, shall comply with the requirements of subpart H for sampling connection systems, with exceptions noted in paragraphs (a)(1) - (a)(13) of § 63.1331.	§ 63.1331(a)(8) [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c)	§ 63.1331(a)(4) § 63.1331(a)(5) § 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
MODF-3A	EU	63JJJ-002	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1331(a) [G]§ 63.1311(o) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.168 [G]§ 63.171 [G]§ 63.175	The owner or operator of each affected source, shall comply with the requirements of subpart H for valves in light liquid or gas/vapor service, with exceptions noted in paragraphs (a)(1) - (a)(13) of § 63.1331.	§ 63.1331(a)(8) [G]§ 63.168 [G]§ 63.175 [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7)	§ 63.1331(a)(4) § 63.1331(a)(5) § 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
								§ 63.181(h)(9)	
MODF-3A	EU	63JJJ-002	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1331(a) [G]§ 63.1311(o) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.174	The owner or operator of each affected source, shall comply with the requirements of subpart H for connectors in gas/vapor or light liquid service, with exceptions noted in paragraphs (a)(1) - (a)(13) of § 63.1331.	§ 63.1331(a)(8) [G]§ 63.174 [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	§ 63.1331(a)(4) § 63.1331(a)(5) § 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
MODF-3A	EU	63JJJ-002	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1331(a) [G]§ 63.1311(o) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171	The owner or operator of each affected source, shall comply with the requirements of subpart H for instrumentation systems, with exceptions noted in paragraphs (a)(1) - (a)(13) of § 63.1331.	§ 63.1331(a)(8) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	§ 63.1331(a)(4) § 63.1331(a)(5) § 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
MODF-3A	EU	63JJJ-002	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1331(a) [G]§ 63.1311(o) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171	The owner or operator of each affected source, shall comply with the requirements of subpart H for pressure relief devices in liquid service, with exceptions noted in paragraphs (a)(1) - (a)(13) of § 63.1331.	§ 63.1331(a)(8) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	§ 63.1331(a)(4) § 63.1331(a)(5) § 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
MODF-3A	EU	63JJJ-002	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1331(a) [G]§ 63.1311(o) § 63.172(a) [G]§ 63.172(h) § 63.172(i) § 63.172(j)(1) § 63.172(j)(2) § 63.172(m)	The owner or operator of each affected source, shall comply with the requirements of subpart H for closed vent systems, with exceptions noted in paragraphs (a)(1) - (a)(13) of § 63.1331.	§ 63.1331(a)(8) [G]§ 63.172(f)(1) [G]§ 63.172(f)(2) § 63.172(g) [G]§ 63.172(h) § 63.172(j)(1) § 63.172(j)(2) [G]§ 63.172(k)	§ 63.118(a)(3) § 63.172(j)(1) [G]§ 63.172(k) [G]§ 63.172(l) § 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	§ 63.1331(a)(4) § 63.1331(a)(5) § 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							[G]§ 63.172(l) [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4)	§ 63.181(g) § 63.181(g)(1)(i) § 63.181(g)(1)(ii) [G]§ 63.181(g)(2) [G]§ 63.181(g)(3)	[G]§ 63.182(d)
MODF-3B	EU	63FFFF	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2480(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart FFFF	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart FFFF	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart FFFF	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart FFFF	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart FFFF
MODF-3B	EU	63JJJ-003	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1331(a) [G]§ 63.1311(o) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.164 [G]§ 63.171	The owner or operator of each affected source, shall comply with the requirements of subpart H for compressors, with exceptions noted in paragraphs (a)(1) - (a)(13) of § 63.1331.	§ 63.1331(a)(8) [G]§ 63.164 [G]§ 63.180(b) [G]§ 63.180(c) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(f)	§ 63.1331(a)(4) § 63.1331(a)(5) § 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
MODF-3B	EU	63JJJ-003	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1331(a) [G]§ 63.1311(o) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.165 [G]§ 63.171	The owner or operator of each affected source, shall comply with the requirements of subpart H for pressure relief devices in gas/vapor service, with exceptions noted in paragraphs (a)(1) - (a)(13) of § 63.1331.	§ 63.1331(a)(8) [G]§ 63.165 [G]§ 63.180(b) [G]§ 63.180(c) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(f)	§ 63.1331(a)(4) § 63.1331(a)(5) § 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
MODF-3B	EU	63JJJ-003	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1331(a) [G]§ 63.1311(o)	The owner or operator of each affected source, shall	§ 63.1331(a)(8) [G]§ 63.180(b)	§ 63.181(a) [G]§ 63.181(b)	§ 63.1331(a)(4) § 63.1331(a)(5)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.1331(a)(7) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.166 [G]§ 63.171	comply with the requirements of subpart H for sampling connection systems, with exceptions noted in paragraphs (a)(1) - (a)(13) of § 63.1331.	§ 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4)	§ 63.181(c)	§ 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
MODF-3B	EU	63JJJ-003	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1331(a) [G]§ 63.1311(o) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.168 [G]§ 63.171 [G]§ 63.175	The owner or operator of each affected source, shall comply with the requirements of subpart H for valves in light liquid or gas/vapor service, with exceptions noted in paragraphs (a)(1) - (a)(13) of § 63.1331.	§ 63.1331(a)(8) [G]§ 63.168 [G]§ 63.175 [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(9)	§ 63.1331(a)(4) § 63.1331(a)(5) § 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
MODF-3B	EU	63JJJ-003	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1331(a) [G]§ 63.1311(o) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.174	The owner or operator of each affected source, shall comply with the requirements of subpart H for connectors in gas/vapor or light liquid service, with exceptions noted in paragraphs (a)(1) - (a)(13) of § 63.1331.	§ 63.1331(a)(8) [G]§ 63.174 [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	§ 63.1331(a)(4) § 63.1331(a)(5) § 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
MODF-3B	EU	63JJJ-003	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1331(a) [G]§ 63.1311(o) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171	The owner or operator of each affected source, shall comply with the requirements of subpart H for instrumentation systems, with exceptions noted in paragraphs (a)(1) - (a)(13) of § 63.1331.	§ 63.1331(a)(8) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	§ 63.1331(a)(4) § 63.1331(a)(5) § 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
MODF-3B	EU	63JJJ-003	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1331(a) [G]§ 63.1311(o) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171	The owner or operator of each affected source, shall comply with the requirements of subpart H for pressure relief devices in liquid service, with exceptions noted in paragraphs (a)(1) - (a)(13) of § 63.1331.	§ 63.1331(a)(8) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	§ 63.1331(a)(4) § 63.1331(a)(5) § 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
MODF-3B	EU	63JJJ-003	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1331(a) [G]§ 63.1311(o) § 63.172(a) [G]§ 63.172(h) § 63.172(i) § 63.172(j)(1) § 63.172(j)(2) § 63.172(m)	The owner or operator of each affected source, shall comply with the requirements of subpart H for closed vent systems, with exceptions noted in paragraphs (a)(1) - (a)(13) of § 63.1331.	§ 63.1331(a)(8) [G]§ 63.172(f)(1) [G]§ 63.172(f)(2) § 63.172(g) [G]§ 63.172(h) § 63.172(j)(1) § 63.172(j)(2) [G]§ 63.172(k) [G]§ 63.172(l) [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4)	§ 63.118(a)(3) § 63.172(j)(1) [G]§ 63.172(k) [G]§ 63.172(l) § 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(g) § 63.181(g)(1)(i) § 63.181(g)(1)(ii) [G]§ 63.181(g)(2) [G]§ 63.181(g)(3)	§ 63.1331(a)(4) § 63.1331(a)(5) § 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
MODF-3C	EU	63FFFF	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2480(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart FFFF	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart FFFF	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart FFFF	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart FFFF	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart FFFF
MODF-3C	EU	63JJJ-004	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1331(a) [G]§ 63.1311(o) § 63.1331(a)(1) § 63.162(a)	The owner or operator of each affected source, shall comply with the requirements of subpart H	§ 63.1331(a)(8) [G]§ 63.163 [G]§ 63.176 [G]§ 63.180(b)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	§ 63.1331(a)(4) § 63.1331(a)(5) § 63.182(a)(2) § 63.182(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.163 [G]§ 63.171 [G]§ 63.176	for pumps in light liquid service, with exceptions noted in paragraphs (a)(1) - (a)(13) of § 63.1331.	§ 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4)	§ 63.181(h) [G]§ 63.181(h)(3) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(8) § 63.181(h)(9)	[G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
MODF-3C	EU	63JJJ-004	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1331(a) [G]§ 63.1311(o) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.165 [G]§ 63.171	The owner or operator of each affected source, shall comply with the requirements of subpart H for pressure relief devices in gas/vapor service, with exceptions noted in paragraphs (a)(1) - (a)(13) of § 63.1331.	§ 63.1331(a)(8) [G]§ 63.165 [G]§ 63.180(b) [G]§ 63.180(c) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(f)	§ 63.1331(a)(4) § 63.1331(a)(5) § 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
MODF-3C	EU	63JJJ-004	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1331(a) [G]§ 63.1311(o) § 63.1331(a)(7) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.166 [G]§ 63.171	The owner or operator of each affected source, shall comply with the requirements of subpart H for sampling connection systems, with exceptions noted in paragraphs (a)(1) - (a)(13) of § 63.1331.	§ 63.1331(a)(8) [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c)	§ 63.1331(a)(4) § 63.1331(a)(5) § 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
MODF-3C	EU	63JJJ-004	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1331(a) [G]§ 63.1311(o) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.168 [G]§ 63.171 [G]§ 63.175	The owner or operator of each affected source, shall comply with the requirements of subpart H for valves in light liquid or gas/vapor service, with exceptions noted in paragraphs (a)(1) - (a)(13) of § 63.1331.	§ 63.1331(a)(8) [G]§ 63.168 [G]§ 63.175 [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7)	§ 63.1331(a)(4) § 63.1331(a)(5) § 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
								§ 63.181(h)(9)	
MODF-3C	EU	63JJJ-004	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1331(a) [G]§ 63.1311(o) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.174	The owner or operator of each affected source, shall comply with the requirements of subpart H for connectors in gas/vapor or light liquid service, with exceptions noted in paragraphs (a)(1) - (a)(13) of § 63.1331.	§ 63.1331(a)(8) [G]§ 63.174 [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	§ 63.1331(a)(4) § 63.1331(a)(5) § 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
MODF-3C	EU	63JJJ-004	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1331(a) [G]§ 63.1311(o) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171	The owner or operator of each affected source, shall comply with the requirements of subpart H for instrumentation systems, with exceptions noted in paragraphs (a)(1) - (a)(13) of § 63.1331.	§ 63.1331(a)(8) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	§ 63.1331(a)(4) § 63.1331(a)(5) § 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
MODF-3C	EU	63JJJ-004	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1331(a) [G]§ 63.1311(o) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171	The owner or operator of each affected source, shall comply with the requirements of subpart H for pressure relief devices in liquid service, with exceptions noted in paragraphs (a)(1) - (a)(13) of § 63.1331.	§ 63.1331(a)(8) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	§ 63.1331(a)(4) § 63.1331(a)(5) § 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
MODF-3C	EU	63JJJ-004	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1331(a) [G]§ 63.1311(o) § 63.172(a) [G]§ 63.172(h) § 63.172(i) § 63.172(j)(1) § 63.172(j)(2) § 63.172(m)	The owner or operator of each affected source, shall comply with the requirements of subpart H for closed vent systems, with exceptions noted in paragraphs (a)(1) - (a)(13) of § 63.1331.	§ 63.1331(a)(8) [G]§ 63.172(f)(1) [G]§ 63.172(f)(2) § 63.172(g) [G]§ 63.172(h) § 63.172(j)(1) § 63.172(j)(2) [G]§ 63.172(k)	§ 63.118(a)(3) § 63.172(j)(1) [G]§ 63.172(k) [G]§ 63.172(l) § 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	§ 63.1331(a)(4) § 63.1331(a)(5) § 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							[G]§ 63.172(l) [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4)	§ 63.181(g) § 63.181(g)(1)(i) § 63.181(g)(1)(ii) [G]§ 63.181(g)(2) [G]§ 63.181(g)(3)	[G]§ 63.182(d)
MODF-4	EU	63FFFF	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2480(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart FFFF	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart FFFF	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart FFFF	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart FFFF	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart FFFF
MODF-4	EU	63JJJ-005	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1331(a) [G]§ 63.1311(o) § 63.1331(a)(1) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.163 [G]§ 63.171 [G]§ 63.176	The owner or operator of each affected source, shall comply with the requirements of subpart H for pumps in light liquid service, with exceptions noted in paragraphs (a)(1) - (a)(13) of § 63.1331.	§ 63.1331(a)(8) [G]§ 63.163 [G]§ 63.176 [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(3) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(8) § 63.181(h)(9)	§ 63.1331(a)(4) § 63.1331(a)(5) § 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
MODF-4	EU	63JJJ-005	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1331(a) [G]§ 63.1311(o) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.165 [G]§ 63.171	The owner or operator of each affected source, shall comply with the requirements of subpart H for pressure relief devices in gas/vapor service, with exceptions noted in paragraphs (a)(1) - (a)(13) of § 63.1331.	§ 63.1331(a)(8) [G]§ 63.165 [G]§ 63.180(b) [G]§ 63.180(c) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(f)	§ 63.1331(a)(4) § 63.1331(a)(5) § 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
MODF-4	EU	63JJJ-005	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1331(a) [G]§ 63.1311(o) § 63.1331(a)(7) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.166 [G]§ 63.171	The owner or operator of each affected source, shall comply with the requirements of subpart H for sampling connection systems, with exceptions noted in paragraphs (a)(1) - (a)(13) of § 63.1331.	§ 63.1331(a)(8) [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c)	§ 63.1331(a)(4) § 63.1331(a)(5) § 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
MODF-4	EU	63JJJ-005	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1331(a) [G]§ 63.1311(o) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.168 [G]§ 63.171 [G]§ 63.175	The owner or operator of each affected source, shall comply with the requirements of subpart H for valves in light liquid or gas/vapor service, with exceptions noted in paragraphs (a)(1) - (a)(13) of § 63.1331.	§ 63.1331(a)(8) [G]§ 63.168 [G]§ 63.175 [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(9)	§ 63.1331(a)(4) § 63.1331(a)(5) § 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
MODF-4	EU	63JJJ-005	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1331(a) [G]§ 63.1311(o) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.174	The owner or operator of each affected source, shall comply with the requirements of subpart H for connectors in gas/vapor or light liquid service, with exceptions noted in paragraphs (a)(1) - (a)(13) of § 63.1331.	§ 63.1331(a)(8) [G]§ 63.174 [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	§ 63.1331(a)(4) § 63.1331(a)(5) § 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
MODF-4	EU	63JJJ-005	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1331(a) [G]§ 63.1311(o) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h)	The owner or operator of each affected source, shall comply with the requirements of subpart H for instrumentation systems, with exceptions noted in paragraphs (a)(1) -	§ 63.1331(a)(8) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	§ 63.1331(a)(4) § 63.1331(a)(5) § 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 63.169 [G]§ 63.171	(a)(13) of § 63.1331.			§ 63.182(c)(4) [G]§ 63.182(d)
MODF-4	EU	63JJJ-005	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1331(a) [G]§ 63.1311(o) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171	The owner or operator of each affected source, shall comply with the requirements of subpart H for pressure relief devices in liquid service, with exceptions noted in paragraphs (a)(1) - (a)(13) of § 63.1331.	§ 63.1331(a)(8) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	§ 63.1331(a)(4) § 63.1331(a)(5) § 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
MODF-4	EU	63JJJ-005	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1331(a) [G]§ 63.1311(o) § 63.172(a) [G]§ 63.172(h) § 63.172(i) § 63.172(j)(1) § 63.172(j)(2) § 63.172(m)	The owner or operator of each affected source, shall comply with the requirements of subpart H for closed vent systems, with exceptions noted in paragraphs (a)(1) - (a)(13) of § 63.1331.	§ 63.1331(a)(8) [G]§ 63.172(f)(1) [G]§ 63.172(f)(2) § 63.172(g) [G]§ 63.172(h) § 63.172(j)(1) § 63.172(j)(2) [G]§ 63.172(k) [G]§ 63.172(l) [G]§ 63.172(l) [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4)	§ 63.118(a)(3) § 63.172(j)(1) [G]§ 63.172(k) [G]§ 63.172(l) § 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(g) § 63.181(g)(1)(i) § 63.181(g)(1)(ii) [G]§ 63.181(g)(2) [G]§ 63.181(g)(3)	§ 63.1331(a)(4) § 63.1331(a)(5) § 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
MODF-4	EU	63JJJ-005	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1331(a) [G]§ 63.1311(o) § 63.1334(a)(1) § 63.172(c) § 63.172(e) [G]§ 63.172(h) § 63.172(m)	The owner or operator of each affected source, shall comply with the requirements of subpart H for enclosed combustion devices, with exceptions noted in paragraphs (a)(1) - (a)(13) of § 63.1331.	§ 63.1331(a)(8) § 63.1334(a) § 63.1334(b)(2) § 63.1334(d) § 63.1335(d)(1) § 63.1335(d)(3) § 63.1335(d)(3)(i) § 63.172(c) § 63.172(e) [G]§ 63.172(h) [G]§ 63.180(b) § 63.180(d)(1)	§ 63.1335(d) § 63.1335(d)(2) § 63.1335(d)(6) [G]§ 63.1335(d)(7) § 63.1335(d)(8) § 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(g) § 63.181(g)(1)(i) § 63.181(g)(1)(ii)	§ 63.1331(a)(4) § 63.1331(a)(5) § 63.1334(a) § 63.1334(a)(2) § 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							[G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4)	§ 63.181(g)(1)(iv) [G]§ 63.181(g)(2)	
MODF-5	EU	63FFFF	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2480(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart FFFF	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart FFFF	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart FFFF	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart FFFF	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart FFFF
MODF-5	EU	63JJJ-006	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1331(a) [G]§ 63.1311(o) § 63.1331(a)(1) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.163 [G]§ 63.171 [G]§ 63.176	The owner or operator of each affected source, shall comply with the requirements of subpart H for pumps in light liquid service, with exceptions noted in paragraphs (a)(1) - (a)(13) of § 63.1331.	§ 63.1331(a)(8) [G]§ 63.163 [G]§ 63.176 [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(3) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(8) § 63.181(h)(9)	§ 63.1331(a)(4) § 63.1331(a)(5) § 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
MODF-5	EU	63JJJ-006	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1331(a) [G]§ 63.1311(o) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.165 [G]§ 63.171	The owner or operator of each affected source, shall comply with the requirements of subpart H for pressure relief devices in gas/vapor service, with exceptions noted in paragraphs (a)(1) - (a)(13) of § 63.1331.	§ 63.1331(a)(8) [G]§ 63.165 [G]§ 63.180(b) [G]§ 63.180(c) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(f)	§ 63.1331(a)(4) § 63.1331(a)(5) § 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
MODF-5	EU	63JJJ-006	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1331(a) [G]§ 63.1311(o)	The owner or operator of each affected source, shall	§ 63.1331(a)(8) [G]§ 63.180(b)	§ 63.181(a) [G]§ 63.181(b)	§ 63.1331(a)(4) § 63.1331(a)(5)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.1331(a)(7) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.166 [G]§ 63.171	comply with the requirements of subpart H for sampling connection systems, with exceptions noted in paragraphs (a)(1) - (a)(13) of § 63.1331.	§ 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4)	§ 63.181(c)	§ 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
MODF-5	EU	63JJJ-006	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1331(a) [G]§ 63.1311(o) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.168 [G]§ 63.171 [G]§ 63.175	The owner or operator of each affected source, shall comply with the requirements of subpart H for valves in light liquid or gas/vapor service, with exceptions noted in paragraphs (a)(1) - (a)(13) of § 63.1331.	§ 63.1331(a)(8) [G]§ 63.168 [G]§ 63.175 [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(9)	§ 63.1331(a)(4) § 63.1331(a)(5) § 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
MODF-5	EU	63JJJ-006	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1331(a) [G]§ 63.1311(o) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.174	The owner or operator of each affected source, shall comply with the requirements of subpart H for connectors in gas/vapor or light liquid service, with exceptions noted in paragraphs (a)(1) - (a)(13) of § 63.1331.	§ 63.1331(a)(8) [G]§ 63.174 [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	§ 63.1331(a)(4) § 63.1331(a)(5) § 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
MODF-5	EU	63JJJ-006	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1331(a) [G]§ 63.1311(o) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171	The owner or operator of each affected source, shall comply with the requirements of subpart H for instrumentation systems, with exceptions noted in paragraphs (a)(1) - (a)(13) of § 63.1331.	§ 63.1331(a)(8) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	§ 63.1331(a)(4) § 63.1331(a)(5) § 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
MODF-5	EU	63JJJ-006	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1331(a) [G]§ 63.1311(o) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171	The owner or operator of each affected source, shall comply with the requirements of subpart H for pressure relief devices in liquid service, with exceptions noted in paragraphs (a)(1) - (a)(13) of § 63.1331.	§ 63.1331(a)(8) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	§ 63.1331(a)(4) § 63.1331(a)(5) § 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
MODF-5	EU	63JJJ-006	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1331(a) [G]§ 63.1311(o) § 63.172(a) [G]§ 63.172(h) § 63.172(i) § 63.172(j)(1) § 63.172(j)(2) § 63.172(m)	The owner or operator of each affected source, shall comply with the requirements of subpart H for closed vent systems, with exceptions noted in paragraphs (a)(1) - (a)(13) of § 63.1331.	§ 63.1331(a)(8) [G]§ 63.172(f)(1) [G]§ 63.172(f)(2) § 63.172(g) [G]§ 63.172(h) § 63.172(j)(1) § 63.172(j)(2) [G]§ 63.172(k) [G]§ 63.172(l) [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4)	§ 63.118(a)(3) § 63.172(j)(1) [G]§ 63.172(k) [G]§ 63.172(l) § 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(g) § 63.181(g)(1)(i) § 63.181(g)(1)(ii) [G]§ 63.181(g)(2) [G]§ 63.181(g)(3)	§ 63.1331(a)(4) § 63.1331(a)(5) § 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
MODF-5	EU	63JJJ-006	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1331(a) [G]§ 63.1311(o) § 63.1334(a)(1) § 63.172(c) § 63.172(e) [G]§ 63.172(h) § 63.172(m)	The owner or operator of each affected source, shall comply with the requirements of subpart H for enclosed combustion devices, with exceptions noted in paragraphs (a)(1) - (a)(13) of § 63.1331.	§ 63.1331(a)(8) § 63.1334(a) § 63.1334(b)(2) § 63.1334(d) § 63.1335(d)(1) § 63.1335(d)(3) § 63.1335(d)(3)(i) § 63.172(c) § 63.172(e) [G]§ 63.172(h) [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4)	§ 63.1335(d) § 63.1335(d)(2) § 63.1335(d)(6) [G]§ 63.1335(d)(7) § 63.1335(d)(8) § 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(g) § 63.181(g)(1)(i) § 63.181(g)(1)(ii) § 63.181(g)(1)(iv) [G]§ 63.181(g)(2)	§ 63.1331(a)(4) § 63.1331(a)(5) § 63.1334(a) § 63.1334(a)(2) § 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
MODP-79901-B	EU	R7ICI	EXEMPT	30 TAC Chapter 117, Subchapter B	[G]§ 117.303(a)(11) [G]§ 117.310(f)	Units exempted from the provisions of this division except as specified in §§117.310(f), 117.340(j), 117.345(f)(6) and (10), 117.350(c)(1) and 117.354(a)(5) include new, modified, reconstructed, or relocated stationary diesel engine placed into service on or after October 1, 2001, that operates less than 100 hours per year, based on a rolling 12-month average, in other than emergency situations; and meets the requirements for non-road engines as specified. §117.303(a)(11)(A)-(B)	None	§ 117.340(j) [G]§ 117.345(f)(10) [G]§ 117.345(f)(6)	None
MODP-79901-B	EU	63ZZZZ-01	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6602-Table2c.1 § 63.6595(a)(1) § 63.6605(a) § 63.6605(b) § 63.6625(e) § 63.6625(h) § 63.6625(i) § 63.6640(b) § 63.6640(f)(1) [G]§ 63.6640(f)(2) § 63.6640(f)(3)	For each existing emergency stationary CI RICE and black start stationary CI RICE, located at a major source, you must comply with the requirements as specified in Table 2c.1.a-c.	§ 63.6625(f) § 63.6625(i) § 63.6640(a) § 63.6640(a)-Table6.9.a.i § 63.6640(a)-Table6.9.a.ii § 63.6640(b)	§ 63.6625(i) § 63.6655(a) § 63.6655(a)(1) § 63.6655(d) § 63.6655(e) § 63.6655(f) § 63.6660(a) § 63.6660(b) § 63.6660(c)	§ 63.6640(b) § 63.6640(e) § 63.6650(f)
MODP-79901-C	EU	R7ICI	EXEMPT	30 TAC Chapter 117, Subchapter B	[G]§ 117.303(a)(11) [G]§ 117.310(f)	Units exempted from the provisions of this division except as specified in §§117.310(f), 117.340(j), 117.345(f)(6) and (10), 117.350(c)(1) and 117.354(a)(5) include new,	None	§ 117.340(j) [G]§ 117.345(f)(10) [G]§ 117.345(f)(6)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						modified, reconstructed, or relocated stationary diesel engine placed into service on or after October 1, 2001, that operates less than 100 hours per year, based on a rolling 12-month average, in other than emergency situations; and meets the requirements for non-road engines as specified. §117.303(a)(11)(A)-(B)			
MODP-79901-C	EU	63ZZZZ-02	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6602-Table2c.1 § 63.6595(a)(1) § 63.6605(a) § 63.6605(b) § 63.6625(e) § 63.6625(h) § 63.6625(i) § 63.6640(b) § 63.6640(f)(1) [G]§ 63.6640(f)(2) § 63.6640(f)(3)	For each existing emergency stationary CI RICE and black start stationary CI RICE, located at a major source, you must comply with the requirements as specified in Table 2c.1.a-c.	§ 63.6625(f) § 63.6625(i) § 63.6640(a) § 63.6640(a)-Table6.9.a.i § 63.6640(a)-Table6.9.a.ii § 63.6640(b)	§ 63.6625(i) § 63.6655(a) § 63.6655(a)(1) § 63.6655(d) § 63.6655(e) § 63.6655(f) § 63.6660(a) § 63.6660(b) § 63.6660(c)	§ 63.6640(b) § 63.6640(e) § 63.6650(f)
MODSBG-001	EU	R7ICI	EXEMPT	30 TAC Chapter 117, Subchapter B	§ 117.303(a)(6)(D) [G]§ 117.310(f)	Units exempted from the provisions of this division, except as specified in §§117.310(f), 117.340(j), 117.345(f)(6) and (10), 117.350(c)(1), and 117.354(a)(5), include stationary gas turbines and stationary internal combustion engines that are used exclusively in emergency situations, except that operation for testing or maintenance	None	§ 117.340(j) [G]§ 117.345(f)(10) [G]§ 117.345(f)(6)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						purposes is allowed for up to 52 hours per year, based on a rolling 12-month average.			
MODSBG-002	EU	R7300	EXEMPT	30 TAC Chapter 117, Subchapter B	[G]§ 117.303(a)(11) [G]§ 117.310(f)	Units exempted from the provisions of this division except as specified in §§117.310(f), 117.340(j), 117.345(f)(6) and (10), 117.350(c)(1) and 117.354(a)(5) include new, modified, reconstructed, or relocated stationary diesel engine placed into service on or after October 1, 2001, that operates less than 100 hours per year, based on a rolling 12-month average, in other than emergency situations; and meets the requirements for non-road engines as specified. §117.303(a)(11)(A)-(B)	None	§ 117.340(j) [G]§ 117.345(f)(10) [G]§ 117.345(f)(6)	None
MODSBG-002	EU	6oIII	NO _x	40 CFR Part 60, Subpart III	[G]§ 60.4205(d)(2) § 60.4206 § 60.4207(d) § 60.4211(d) [G]§ 60.4211(f) § 60.4218	Owners and operators of emergency stationary CI ICE with a displacement of greater than or equal to 30 liters per cylinder and was installed on or after 01/01/2012 must comply with the following NO _x emission limits: 14.4 g/KW-hr when maximum engine speed is less than 130 rpm, 44.0 x N-0.23 when maximum engine speed is at least 130 but less than 2000 rpm, and 7.7 g/KW-hr when	§ 60.4211(d)(1) § 60.4213(a) § 60.4213(b) § 60.4213(c) § 60.4213(e)	[G]§ 60.4211(d)(2)	[G]§ 60.4211(d)(2) [G]§ 60.4214(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						maximum engine speed is 2000 rpm or more.			
MODSBG-002	EU	60III	PM	40 CFR Part 60, Subpart III	§ 60.4205(d)(3) § 60.4206 § 60.4207(d) § 60.4211(d) [G]§ 60.4211(f) § 60.4218	Owners and operators of emergency stationary CI ICE with a displacement of greater than or equal to 30 liters per cylinder must comply with a PM emission limit of 0.40 g/KW-hr.	§ 60.4211(d)(1) § 60.4213(a) § 60.4213(b) § 60.4213(c) § 60.4213(f)	[G]§ 60.4211(d)(2)	[G]§ 60.4211(d)(2) [G]§ 60.4214(d)
MODSBG-002	EU	63ZZZZ	EXEMPT	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(b)(1) § 63.6595(c) § 63.6640(f)(1) [G]§ 63.6640(f)(2) § 63.6640(f)(3)	An affected source which meets either of the criteria in paragraphs §63.6590(b)(1)(i)-(ii) of this section does not have to meet the requirements of this subpart and of subpart A of this part except for the initial notification requirements of §63.6645(f).	None	None	§ 63.6645(c) § 63.6645(f)
MODSBG-003	EU	R7ICI	EXEMPT	30 TAC Chapter 117, Subchapter B	[G]§ 117.303(a)(11) [G]§ 117.310(f)	Units exempted from the provisions of this division except as specified in §§117.310(f), 117.340(j), 117.345(f)(6) and (10), 117.350(c)(1) and 117.354(a)(5) include new, modified, reconstructed, or relocated stationary diesel engine placed into service on or after October 1, 2001, that operates less than 100 hours per year, based on a rolling 12-month average, in other than emergency situations; and meets the requirements for non-road	None	§ 117.340(j) [G]§ 117.345(f)(10) [G]§ 117.345(f)(6)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						engines as specified. §117.303(a)(11)(A)-(B)			
MODSBG-003	EU	63ZZZZ-01	EXEMPT	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(b)(1) § 63.6595(c) § 63.6640(f)(1) [G]§ 63.6640(f)(2) § 63.6640(f)(3)	An affected source which meets either of the criteria in paragraphs §63.6590(b)(1)(i)-(ii) of this section does not have to meet the requirements of this subpart and of subpart A of this part except for the initial notification requirements of §63.6645(f).	None	None	§ 63.6645(c) § 63.6645(f)
MODT-121	EU	R5112	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
MODT-121LD	EU	R5211	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.212(a)(3) § 115.212(a)(2) § 115.212(a)(3)(A) § 115.212(a)(3)(A)(ii) § 115.212(a)(3)(B) [G]§ 115.212(a)(3)(C) § 115.212(a)(3)(D) § 115.214(a)(1)(B) § 115.214(a)(1)(C)	All land-based VOC transfer to or from transport vessels shall be conducted in the manner specified for leak-free operations.	§ 115.212(a)(3)(B) § 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.214(a)(1)(A)(ii) § 115.214(a)(1)(A)(iii)	§ 115.216 § 115.216(3)(A) § 115.216(3)(A)(i) § 115.216(3)(A)(iii)	None
MODT-130	EU	R5112	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient	[G]§ 115.117 ** See Periodic Monitoring Summary	§ 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.			
MODT-130	EU	63FFFF-1	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2470(a)-Table4.1.b.ii § 63.2450(b) § 63.2470(a) § 63.2470(d) § 63.982(c) § 63.982(c)(2) § 63.983(a)(1) § 63.983(a)(2) § 63.983(d)(1) § 63.983(d)(1)(i) [G]§ 63.983(d)(2) § 63.983(d)(3) § 63.995(a)(1) § 63.995(a)(2) § 63.996(c)(1) § 63.996(c)(2) § 63.996(c)(2)(i) § 63.996(c)(3) § 63.996(c)(4) § 63.996(c)(5) § 63.996(c)(6) [G]§ 63.997(c)(1) [G]§ 63.997(d)	For each Group 1 storage tank for which the maximum true vapor pressure of total HAP at the storage temperature is < 76.6 kilopascals, you may reduce total HAP emissions by > 95 percent by weight by venting emissions through a closed vent system to any combination of control devices (excluding a flare).	[G]§ 63.115(d)(2)(v) § 63.115(d)(3)(iii) § 63.2450(g) § 63.2450(g)(1) § 63.2450(g)(2) [G]§ 63.2450(g)(3) § 63.2450(g)(4) § 63.2450(k)(6) § 63.2470(c)(1) § 63.983(b) [G]§ 63.983(b)(1) [G]§ 63.983(b)(2) [G]§ 63.983(b)(3) [G]§ 63.983(c)(1) § 63.983(c)(2) § 63.983(c)(3) § 63.983(d)(1) § 63.983(d)(1)(ii) § 63.995(b) § 63.995(c) § 63.996(b)(1) § 63.996(b)(1)(i) § 63.996(b)(2) § 63.997(a) [G]§ 63.997(c)(1) [G]§ 63.997(d) § 63.997(e) § 63.997(e)(1)(i)	§ 63.2450(k)(6) § 63.2470(c)(1) § 63.2525(g) § 63.2525(h) § 63.983(b) [G]§ 63.983(d)(2) § 63.995(b) § 63.995(c) § 63.996(c)(2)(ii) § 63.998(a)(2)(i) § 63.998(a)(2)(ii)(A) [G]§ 63.998(b)(1) [G]§ 63.998(b)(2) [G]§ 63.998(b)(3) [G]§ 63.998(b)(5) [G]§ 63.998(c)(1) § 63.998(c)(2)(iii) § 63.998(c)(3)(iii) [G]§ 63.998(d)(1) § 63.998(d)(3)(i) § 63.998(d)(3)(ii) § 63.998(d)(5)	§ 63.2450(q) § 63.2470(d) § 63.995(b) § 63.995(c) § 63.996(b)(2) § 63.996(c)(6) § 63.998(a)(2)(ii)(A) [G]§ 63.998(b)(3) [G]§ 63.999(a)(1) [G]§ 63.999(a)(2) [G]§ 63.999(b)(3) § 63.999(b)(5) § 63.999(c)(1) § 63.999(c)(2)(i) § 63.999(c)(6) [G]§ 63.999(c)(6)(i) § 63.999(c)(6)(iv)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							[G]§ 63.997(e)(1)(iv) [G]§ 63.997(e)(1)(v) § 63.997(e)(2) § 63.997(e)(2)(i) [G]§ 63.997(e)(2)(i)(A) § 63.997(e)(2)(ii) § 63.997(e)(2)(iv) § 63.997(e)(2)(iv)(A) [G]§ 63.997(e)(2)(iv)(B) § 63.997(e)(2)(iv)(C) § 63.997(e)(2)(iv)(D) § 63.997(e)(2)(iv)(F) § 63.997(e)(2)(iv)(G) [G]§ 63.997(e)(2)(iv)(H)		
MODT-130	EU	63FFFF-2	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2470(e) § 63.1253(f)(1) § 63.1253(f)(3) § 63.1253(f)(4) § 63.1253(f)(5) § 63.1253(f)(5)(ii) § 63.1253(f)(5)(iii) [G]§ 63.1253(f)(6) § 63.2470(e)(1)	Vapor balancing alternative. As an alternative to the emission limits specified in Table 4 to this subpart, you may elect to implement vapor balancing in accordance with §63.1253(f), except as specified in §63.2470(e)(1)-(3).	§ 63.1253(f)(5)(i) § 63.2470(e)(2) § 63.2470(e)(3)	§ 63.1253(f)(2) § 63.1253(f)(5) § 63.1253(f)(5)(iii) [G]§ 63.1253(f)(7)(iii) § 63.2470(e)(2)	§ 63.1253(f)(7)(i) § 63.2470(e)(2) § 63.2470(e)(2)(i)
MODT-130	EU	63JJJ	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1314(a) § 63.119(a)(3) [G]§ 63.1311(o)	Except as specified in § 63.1314(b) or (c), the owner or operator of an affected source shall comply with the requirements of § 63.119	None	§ 63.123(a)	§ 63.1310(g)(6) § 63.1335(e)(5)(vi) § 63.1335(e)(6)(vii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						through § 63.123 and § 63.148 for each storage vessel that is assigned to an affected source.			
MODT-130LD	EU	R5211	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.212(a)(3) § 115.212(a)(2) § 115.212(a)(3)(A) § 115.212(a)(3)(A)(ii) § 115.212(a)(3)(B) [G]§ 115.212(a)(3)(C) § 115.212(a)(3)(D) § 115.214(a)(1)(B) § 115.214(a)(1)(C)	All land-based VOC transfer to or from transport vessels shall be conducted in the manner specified for leak-free operations.	§ 115.212(a)(3)(B) § 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.214(a)(1)(A)(ii) § 115.214(a)(1)(A)(iii)	§ 115.216 § 115.216(3)(A) § 115.216(3)(A)(i) § 115.216(3)(A)(iii)	None
MODT-140	EU	R5112	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
MODT-140	EU	60KB	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(3)	Storage vessels specified in §60.112b(a) and equipped with a closed vent system/control device are to meet the specifications of §60.112b(a)(3)(i)-(ii).	[G]§ 60.113b(c)(1) § 60.113b(c)(2) § 60.116b(a) § 60.116b(b) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3) [G]§ 60.485(b) ** See Periodic Monitoring Summary	§ 60.115b [G]§ 60.115b(c) § 60.116b(a) § 60.116b(b)	[G]§ 60.113b(c)(1) § 60.115b
MODT-140	EU	63FFFF-1	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2470(a)-Table4.1.b.ii § 63.2450(b)	For each Group 1 storage tank for which the maximum true vapor	[G]§ 63.115(d)(2)(v) § 63.115(d)(3)(iii) § 63.2450(g)	§ 63.2450(k)(6) § 63.2470(c)(1) § 63.2525(g)	§ 63.2450(q) § 63.2470(d) § 63.995(b)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.2470(a) § 63.2470(d) § 63.982(c) § 63.982(c)(2) § 63.983(a)(1) § 63.983(a)(2) § 63.983(d)(1) § 63.983(d)(1)(i) [G]§ 63.983(d)(2) § 63.983(d)(3) § 63.995(a)(1) § 63.995(a)(2) § 63.996(c)(1) § 63.996(c)(2) § 63.996(c)(2)(i) § 63.996(c)(3) § 63.996(c)(4) § 63.996(c)(5) § 63.996(c)(6) [G]§ 63.997(c)(1) [G]§ 63.997(d)	pressure of total HAP at the storage temperature is < 76.6 kilopascals, you may reduce total HAP emissions by > 95 percent by weight by venting emissions through a closed vent system to any combination of control devices (excluding a flare).	§ 63.2450(g)(1) § 63.2450(g)(2) [G]§ 63.2450(g)(3) § 63.2450(g)(4) § 63.2450(k)(6) § 63.2470(c)(1) § 63.983(b) [G]§ 63.983(b)(1) [G]§ 63.983(b)(2) [G]§ 63.983(b)(3) [G]§ 63.983(c)(1) § 63.983(c)(2) § 63.983(c)(3) § 63.983(d)(1) § 63.983(d)(1)(ii) § 63.995(b) § 63.995(c) § 63.996(b)(1) § 63.996(b)(1)(i) § 63.996(b)(2) § 63.997(a) [G]§ 63.997(c)(1) [G]§ 63.997(d) § 63.997(e) § 63.997(e)(1)(i) [G]§ 63.997(e)(1)(iv) [G]§ 63.997(e)(1)(v) § 63.997(e)(2) § 63.997(e)(2)(i) [G]§ 63.997(e)(2)(i)(A) § 63.997(e)(2)(ii) § 63.997(e)(2)(iv) § 63.997(e)(2)(iv)(A) [G]§ 63.997(e)(2)(iv)(B) §	§ 63.2525(h) § 63.983(b) [G]§ 63.983(d)(2) § 63.995(b) § 63.995(c) § 63.996(c)(2)(ii) § 63.998(a)(2)(i) § 63.998(a)(2)(ii)(A) [G]§ 63.998(b)(1) [G]§ 63.998(b)(2) [G]§ 63.998(b)(3) [G]§ 63.998(b)(5) [G]§ 63.998(c)(1) § 63.998(c)(2)(iii) § 63.998(c)(3)(iii) [G]§ 63.998(d)(1) § 63.998(d)(3)(i) § 63.998(d)(3)(ii) § 63.998(d)(5)	§ 63.995(c) § 63.996(b)(2) § 63.996(c)(6) § 63.998(a)(2)(ii)(A) [G]§ 63.998(b)(3) [G]§ 63.999(a)(1) [G]§ 63.999(a)(2) [G]§ 63.999(b)(3) § 63.999(b)(5) § 63.999(c)(1) § 63.999(c)(2)(i) § 63.999(c)(6) [G]§ 63.999(c)(6)(i) § 63.999(c)(6)(iv)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							63.997(e)(2)(iv)(C) § 63.997(e)(2)(iv)(D) § 63.997(e)(2)(iv)(F) § 63.997(e)(2)(iv)(G) [G]§ 63.997(e)(2)(iv)(H)		
MODT-140	EU	63FFFF-2	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2470(e) § 63.1253(f)(1) § 63.1253(f)(3) § 63.1253(f)(4) § 63.1253(f)(5) § 63.1253(f)(5)(ii) § 63.1253(f)(5)(iii) [G]§ 63.1253(f)(6) § 63.2470(e)(1)	Vapor balancing alternative. As an alternative to the emission limits specified in Table 4 to this subpart, you may elect to implement vapor balancing in accordance with §63.1253(f), except as specified in §63.2470(e)(1)-(3).	§ 63.1253(f)(5)(i) § 63.2470(e)(2) § 63.2470(e)(3)	§ 63.1253(f)(2) § 63.1253(f)(5) § 63.1253(f)(5)(iii) [G]§ 63.1253(f)(7)(iii) § 63.2470(e)(2)	§ 63.1253(f)(7)(i) § 63.2470(e)(2) § 63.2470(e)(2)(i)
MODT-140	EU	63JJJ	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1314(a) § 63.119(a)(3) [G]§ 63.1311(o)	Except as specified in § 63.1314(b) or (c), the owner or operator of an affected source shall comply with the requirements of § 63.119 through § 63.123 and § 63.148 for each storage vessel that is assigned to an affected source.	None	§ 63.123(a)	§ 63.1310(g)(6) § 63.1335(e)(5)(vi) § 63.1335(e)(6)(vii)
MODT-140LD	EU	R5211	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.212(a)(3) § 115.212(a)(2) § 115.212(a)(3)(A) § 115.212(a)(3)(A)(ii) § 115.212(a)(3)(B) [G]§ 115.212(a)(3)(C) § 115.212(a)(3)(D)	All land-based VOC transfer to or from transport vessels shall be conducted in the manner specified for leak-free operations.	§ 115.212(a)(3)(B) § 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.214(a)(1)(A)(ii) § 115.214(a)(1)(A)(iii)	§ 115.216 § 115.216(3)(A) § 115.216(3)(A)(i) § 115.216(3)(A)(iii)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.214(a)(1)(B) § 115.214(a)(1)(C)				
MODT-150	EU	R5112	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
MODT-150LD	EU	R5211	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.212(a)(3) § 115.212(a)(2) § 115.212(a)(3)(A) § 115.212(a)(3)(A)(ii) § 115.212(a)(3)(B) [G]§ 115.212(a)(3)(C) § 115.212(a)(3)(D) § 115.214(a)(1)(B) § 115.214(a)(1)(C)	All land-based VOC transfer to or from transport vessels shall be conducted in the manner specified for leak-free operations.	§ 115.212(a)(3)(B) § 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.214(a)(1)(A)(ii) § 115.214(a)(1)(A)(iii)	§ 115.216 § 115.216(3)(A) § 115.216(3)(A)(i) § 115.216(3)(A)(iii)	None
MODT-2121	EU	R5112	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
MODT-2121LD	EU	R5211	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.212(a)(3) § 115.212(a)(2) § 115.212(a)(3)(A) § 115.212(a)(3)(A)(ii) § 115.212(a)(3)(B) [G]§ 115.212(a)(3)(C) § 115.212(a)(3)(D)	All land-based VOC transfer to or from transport vessels shall be conducted in the manner specified for leak-free operations.	§ 115.212(a)(3)(B) § 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.214(a)(1)(A)(ii) § 115.214(a)(1)(A)(iii)	§ 115.216 § 115.216(3)(A) § 115.216(3)(A)(i) § 115.216(3)(A)(iii)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.214(a)(1)(B) § 115.214(a)(1)(C)				
MODT-2130	EU	R5112	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
MODT-2130LD	EU	R5211	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.212(a)(3) § 115.212(a)(2) § 115.212(a)(3)(A) § 115.212(a)(3)(A)(ii) § 115.212(a)(3)(B) [G]§ 115.212(a)(3)(C) § 115.212(a)(3)(D) § 115.214(a)(1)(B) § 115.214(a)(1)(C)	All land-based VOC transfer to or from transport vessels shall be conducted in the manner specified for leak-free operations.	§ 115.212(a)(3)(B) § 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.214(a)(1)(A)(ii) § 115.214(a)(1)(A)(iii)	§ 115.216 § 115.216(3)(A) § 115.216(3)(A)(i) § 115.216(3)(A)(iii)	None
MODT-3107	EU	R5112	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
MODT-3336LD	EU	R5211	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.212(a)(3) § 115.212(a)(2) § 115.212(a)(3)(A) § 115.212(a)(3)(A)(ii) § 115.212(a)(3)(B) [G]§ 115.212(a)(3)(C) § 115.212(a)(3)(D)	All land-based VOC transfer to or from transport vessels shall be conducted in the manner specified for leak-free operations.	§ 115.212(a)(3)(B) § 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.214(a)(1)(A)(ii) § 115.214(a)(1)(A)(iii)	§ 115.216 § 115.216(3)(A) § 115.216(3)(A)(i) § 115.216(3)(A)(iii)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.214(a)(1)(B) § 115.214(a)(1)(C)				
MODV-2321	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
MODV-2321	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(B) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream specified in § 115.121(a)(1) of this title with a concentration of VOC < 612 ppmv is exempt from § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
MODV-3336	EU	R5211	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.212(a)(3) § 115.212(a)(2) § 115.212(a)(3)(A) § 115.212(a)(3)(A)(ii) § 115.212(a)(3)(B) [G]§ 115.212(a)(3)(C) § 115.212(a)(3)(D) § 115.214(a)(1)(B) § 115.214(a)(1)(C)	All land-based VOC transfer to or from transport vessels shall be conducted in the manner specified for leak-free operations.	§ 115.212(a)(3)(B) § 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.214(a)(1)(A)(ii) § 115.214(a)(1)(A)(iii)	§ 115.216 § 115.216(3)(A) § 115.216(3)(A)(i) § 115.216(3)(A)(iii)	None
MODV-402	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
MODV-402	EP	R5121	VOC	30 TAC Chapter	§ 115.127(a)(2)(B)	A vent gas stream specified	[G]§ 115.125	§ 115.126	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				115, Vent Gas Controls	[G]§ 115.122(a)(4) § 115.127(a)(2)	in § 115.121(a)(1) of this title with a concentration of VOC < 612 ppmv is exempt from § 115.121(a)(1).	§ 115.126(2)	§ 115.126(2) § 115.126(4)	
MODWG-1VNT	PRO	R5160-1	VOC	30 TAC Chapter 115, Batch Processes	§ 115.162(1) § 115.162(1)(A) § 115.162(1)(B) § 115.162(1)(C) § 115.162(2) § 115.162(2)(B) § 115.162(2)(D) § 115.162(2)(E)	The mass emission rate from individual process vents or for process vent streams in aggregate within a batch process shall be reduced by 90% if the actual average flow rate value is below the flow rate value calculated using the applicable RACT equation.	§ 115.164(1) § 115.164(2) § 115.165(1) § 115.165(2) [G]§ 115.165(2)(A) [G]§ 115.165(2)(B) § 115.166 § 115.166(1) § 115.166(1)(C) [G]§ 115.166(2)	§ 115.166 § 115.166(1) § 115.166(1)(C) [G]§ 115.166(2)	None
MODWG-1VNT	PRO	R5160-2	VOC	30 TAC Chapter 115, Batch Processes	§ 115.162(1) § 115.162(1)(A) § 115.162(1)(B) § 115.162(1)(C) § 115.162(2) § 115.162(2)(B) § 115.162(2)(D) § 115.162(2)(E)	The mass emission rate from individual process vents or for process vent streams in aggregate within a batch process shall be reduced by 90% if the actual average flow rate value is below the flow rate value calculated using the applicable RACT equation.	§ 115.164(1) § 115.164(2) § 115.165(1) § 115.165(2) [G]§ 115.165(2)(A) [G]§ 115.165(2)(B) § 115.166 § 115.166(1) § 115.166(1)(C) [G]§ 115.166(2)	§ 115.166 § 115.166(1) § 115.166(1)(C) [G]§ 115.166(2)	None
MODWG-1VNT	EP	R5121-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
MODWG-1VNT	EP	R5121-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(B) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream specified in § 115.121(a)(1) of this title with a concentration of VOC < 612 ppmv is exempt from	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						§ 115.121(a)(1).			
MODWG-1VNT	EP	R5121-2	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
MODWG-1VNT	EP	R5121-2	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(B) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream specified in § 115.121(a)(1) of this title with a concentration of VOC < 612 ppmv is exempt from § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
MODWG-1VNT	EP	R5121-3	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
MODWG-1VNT	EP	R5121-3	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(B) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream specified in § 115.121(a)(1) of this title with a concentration of VOC < 612 ppmv is exempt from § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
MODZ-1607S	EP	R5720	HIGHLY REACTIVE VOC	30 TAC Chapter 115, HRVOC Vent Gas	§ 115.727(c)(2)	A vent gas stream that has the potential to emit HRVOCs, but has a concentration less than 100 ppmv at all times or has a maximum potential flow rate equal to or less than 100 dry standard cubic feet	None	§ 115.726(e)(3)(A) § 115.726(j)(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						per hour is exempt from this division with the exception of § 115.726(e)(3)(A) of this title. The maximum potential HRVOC emissions for the sum of all vent gas streams claimed under this exemption, must be less for the account specified in § 115.722(a) or (b) of this title than 0.5 tpy.			
MODZ-1607S	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(a)(1) § 115.121(a)(1) § 115.122(a)(1)(A)	Vent gas affected by §115.121(a)(1) must be controlled properly with a control efficiency > 90% or to a VOC concentration of no more than 20 ppmv (dry, corrected to 3% O2 for combustion devices).	[G]§ 115.125 § 115.126(1) § 115.126(1)(A) § 115.126(1)(A)(i) § 115.126(2) ** See CAM Summary	§ 115.126 § 115.126(1) § 115.126(1)(A) § 115.126(1)(A)(i) § 115.126(2)	None
MODZ-1607S	EP	63JJJ	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1321(c) [G]§ 63.1311(o) § 63.1322(b) § 63.1322(b)(2) § 63.1324(a)(2) § 63.1324(f)(1) § 63.1334(a)(1)	Aggregate batch vent streams. Aggregate batch vent streams, as defined in § 63.1312, are subject to the control requirements specified in § 63.1322(b), as well as the monitoring, testing, recordkeeping, and reporting requirements specified in §§ 63.1324 through 63.1327 for aggregate batch vent streams.	[G]§ 63.1323(h) § 63.1324(a) § 63.1324(a)(1) § 63.1324(c) § 63.1324(c)(1) § 63.1324(c)(1)(i) § 63.1324(e)(1) § 63.1334(a) § 63.1334(b)(2) § 63.1334(b)(4) § 63.1334(d) § 63.1335(d)(1) § 63.1335(d)(3) § 63.1335(d)(3)(i)	§ 63.1324(c)(1) § 63.1324(e)(1) § 63.1326(b) § 63.1326(b)(1) § 63.1326(b)(2) § 63.1326(b)(5) § 63.1326(c) § 63.1326(e)(3) § 63.1326(f) § 63.1326(f)(1) § 63.1326(f)(2) § 63.1335(d) § 63.1335(d)(2) § 63.1335(d)(6) [G]§ 63.1335(d)(7) § 63.1335(d)(8)	§ 63.1327(a) § 63.1327(a)(1) § 63.1327(g)(1) § 63.1334(a) § 63.1334(a)(2)
MODZ-	PRO	R5160	VOC	30 TAC Chapter	§ 115.162(1)	The mass emission rate	§ 115.164(1)	§ 115.166	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
1607SVNT				115, Batch Processes	§ 115.162(1)(A) § 115.162(1)(B) § 115.162(1)(C) § 115.162(2) § 115.162(2)(B) § 115.162(2)(D) § 115.162(2)(E)	from individual process vents or for process vent streams in aggregate within a batch process shall be reduced by 90% if the actual average flow rate value is below the flow rate value calculated using the applicable RACT equation.	§ 115.164(2) § 115.165(1) § 115.165(2) [G]§ 115.165(2)(A) [G]§ 115.165(2)(B) § 115.166 § 115.166(1) § 115.166(1)(A) § 115.166(1)(A)(i) [G]§ 115.166(2) § 115.166(3) § 115.166(3)(A)	§ 115.166(1) § 115.166(1)(A) § 115.166(1)(A)(i) [G]§ 115.166(2) § 115.166(3) § 115.166(3)(A)	
MODZ-1607SVNT	EP	R5720	HIGHLY REACTIVE VOC	30 TAC Chapter 115, HRVOC Vent Gas	§ 115.727(c)(2)	A vent gas stream that has the potential to emit HRVOCs, but has a concentration less than 100 ppmv at all times or has a maximum potential flow rate equal to or less than 100 dry standard cubic feet per hour is exempt from this division with the exception of § 115.726(e)(3)(A) of this title. The maximum potential HRVOC emissions for the sum of all vent gas streams claimed under this exemption, must be less for the account specified in § 115.722(a) or (b) of this title than 0.5 tpy.	None	§ 115.726(e)(3)(A) § 115.726(j)(2)	None
MODZ-1607SVNT	EP	R5121-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						requirements of § 115.121(a)(1).			
MODZ-1607SVNT	EP	R5121-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(B) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream specified in § 115.121(a)(1) of this title with a concentration of VOC < 612 ppmv is exempt from § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
MODZ-1607SVNT	EP	R5121-2	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
MODZ-1607SVNT	EP	R5121-2	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(B) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream specified in § 115.121(a)(1) of this title with a concentration of VOC < 612 ppmv is exempt from § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
MODZ-1607SVNT	EP	63FFFF	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2460(a) § 63.2450(b) § 63.2460(a)-Table 2.1.c § 63.2460(b) § 63.2460(c)(7) § 63.982(c) § 63.982(c)(2) § 63.983(a)(1) § 63.983(a)(2) § 63.983(d)(1) § 63.983(d)(1)(i) [G]§ 63.983(d)(2) § 63.983(d)(3) § 63.988(a)(1) § 63.988(a)(2)	You must meet each emission limit in Table 2 to this subpart that applies to you, and you must meet each applicable requirement specified in §63.2460(b) and (c).	[G]§ 63.115(d)(2)(v) § 63.115(d)(3)(iii) § 63.2450(g) § 63.2450(g)(1) § 63.2450(g)(2) [G]§ 63.2450(g)(3) § 63.2450(g)(4) § 63.2450(k)(6) § 63.2460(c)(2)(i) § 63.2460(c)(2)(ii) § 63.2460(c)(2)(vi) § 63.2460(c)(3) § 63.2460(c)(3)(i) § 63.2460(c)(4) § 63.2460(c)(6) § 63.983(b)	§ 63.2450(k)(6) § 63.2460(c)(3)(ii) § 63.2460(c)(6) § 63.2525(g) § 63.983(b) [G]§ 63.983(d)(2) § 63.988(b)(1) § 63.996(c)(2)(ii) § 63.998(a)(2)(ii)(B)(1) § 63.998(a)(2)(ii)(B)(4) [G]§ 63.998(b)(1) [G]§ 63.998(b)(2) [G]§ 63.998(b)(3) [G]§ 63.998(b)(5) [G]§ 63.998(c)(1) § 63.998(c)(2)(iii)	§ 63.2450(q) § 63.2460(c)(3)(i) § 63.988(b)(1) § 63.996(b)(2) § 63.996(c)(6) § 63.997(b)(1) § 63.997(c)(3) [G]§ 63.998(b)(3) [G]§ 63.999(a)(1) [G]§ 63.999(b)(3) § 63.999(b)(5) § 63.999(c)(1) § 63.999(c)(2)(i) § 63.999(c)(6) [G]§ 63.999(c)(6)(i) § 63.999(c)(6)(iv)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.996(c)(1) § 63.996(c)(2) § 63.996(c)(2)(i) § 63.996(c)(3) § 63.996(c)(4) § 63.996(c)(5) § 63.996(c)(6) § 63.997(b)(1) § 63.997(c)(3)		[G]§ 63.983(b)(1) [G]§ 63.983(b)(2) [G]§ 63.983(b)(3) [G]§ 63.983(c)(1) § 63.983(c)(2) § 63.983(c)(3) § 63.983(d)(1) § 63.983(d)(1)(ii) § 63.988(b)(1) § 63.988(c)(1) § 63.996(b)(1) § 63.996(b)(1)(i) § 63.996(b)(2) § 63.997(b) § 63.997(b)(1) § 63.997(c)(2) § 63.997(c)(3) § 63.997(c)(3)(iii)	§ 63.998(c)(3)(iii) [G]§ 63.998(d)(1) § 63.998(d)(3)(i) § 63.998(d)(3)(ii) § 63.998(d)(5)	
MODZ-1607SVNT	EP	63JJJ	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1321(c) [G]§ 63.1311(o) § 63.1322(b) § 63.1322(b)(2) § 63.1324(a)(2) § 63.1324(f)(1) § 63.1334(a)(1)	Aggregate batch vent streams. Aggregate batch vent streams, as defined in § 63.1312, are subject to the control requirements specified in § 63.1322(b), as well as the monitoring, testing, recordkeeping, and reporting requirements specified in §§ 63.1324 through 63.1327 for aggregate batch vent streams.	[G]§ 63.1323(h) § 63.1324(a) § 63.1324(a)(1) § 63.1324(c) § 63.1324(c)(1) § 63.1324(c)(1)(i) § 63.1324(e)(1) § 63.1334(a) § 63.1334(b)(2) § 63.1334(b)(4) § 63.1334(d) § 63.1335(d)(1) § 63.1335(d)(3) § 63.1335(d)(3)(i)	§ 63.1324(c)(1) § 63.1324(e)(1) § 63.1326(b) § 63.1326(b)(1) § 63.1326(b)(2) § 63.1326(b)(5) § 63.1326(c) § 63.1326(e)(3) § 63.1326(f) § 63.1326(f)(1) § 63.1326(f)(2) § 63.1335(d) § 63.1335(d)(2) § 63.1335(d)(6) [G]§ 63.1335(d)(7) § 63.1335(d)(8)	§ 63.1327(a) § 63.1327(a)(1) § 63.1327(g)(1) § 63.1334(a) § 63.1334(a)(2)
MODZ-1608	EP	R5720	HIGHLY REACTIVE VOC	30 TAC Chapter 115, HRVOC Vent Gas	§ 115.727(c)(2)	A vent gas stream that has the potential to emit HRVOCs, but has a concentration less than 100	None	§ 115.726(e)(3)(A) § 115.726(j)(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						ppmv at all times or has a maximum potential flow rate equal to or less than 100 dry standard cubic feet per hour is exempt from this division with the exception of § 115.726(e)(3)(A) of this title. The maximum potential HRVOC emissions for the sum of all vent gas streams claimed under this exemption, must be less for the account specified in § 115.722(a) or (b) of this title than 0.5 tpy.			
MODZ-1608	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(a)(1) § 115.121(a)(1) § 115.122(a)(1)(A)	Vent gas affected by §115.121(a)(1) must be controlled properly with a control efficiency > 90% or to a VOC concentration of no more than 20 ppmv (dry, corrected to 3% O2 for combustion devices).	[G]§ 115.125 § 115.126(1) § 115.126(1)(A) § 115.126(1)(A)(i) § 115.126(2) ** See CAM Summary	§ 115.126 § 115.126(1) § 115.126(1)(A) § 115.126(1)(A)(i) § 115.126(2)	None
MODZ-1608	EP	63JJJ	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1321(c) [G]§ 63.1311(o) § 63.1322(b) § 63.1322(b)(2) § 63.1324(a)(2) § 63.1324(f)(1) § 63.1334(a)(1)	Aggregate batch vent streams. Aggregate batch vent streams, as defined in § 63.1312, are subject to the control requirements specified in § 63.1322(b), as well as the monitoring, testing, recordkeeping, and reporting requirements specified in §§ 63.1324 through 63.1327 for aggregate batch vent streams.	[G]§ 63.1323(h) § 63.1324(a) § 63.1324(a)(1) § 63.1324(c) § 63.1324(c)(1) § 63.1324(c)(1)(i) § 63.1324(e)(1) § 63.1334(a) § 63.1334(b)(2) § 63.1334(b)(4) § 63.1334(d) § 63.1335(d)(1) § 63.1335(d)(3) § 63.1335(d)(3)(i)	§ 63.1324(c)(1) § 63.1324(e)(1) § 63.1326(b) § 63.1326(b)(1) § 63.1326(b)(2) § 63.1326(b)(5) § 63.1326(c) § 63.1326(e)(3) § 63.1326(f) § 63.1326(f)(1) § 63.1326(f)(2) § 63.1335(d) § 63.1335(d)(2) § 63.1335(d)(6)	§ 63.1327(a) § 63.1327(a)(1) § 63.1327(g)(1) § 63.1334(a) § 63.1334(a)(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
								[G]§ 63.1335(d)(7) § 63.1335(d)(8)	
MODZ-1608VNT	PRO	R5160	VOC	30 TAC Chapter 115, Batch Processes	§ 115.162(1) § 115.162(1)(A) § 115.162(1)(B) § 115.162(1)(C) § 115.162(2) § 115.162(2)(B) § 115.162(2)(D) § 115.162(2)(E)	The mass emission rate from individual process vents or for process vent streams in aggregate within a batch process shall be reduced by 90% if the actual average flow rate value is below the flow rate value calculated using the applicable RACT equation.	§ 115.164(1) § 115.164(2) § 115.165(1) § 115.165(2) [G]§ 115.165(2)(A) [G]§ 115.165(2)(B) § 115.166 § 115.166(1) § 115.166(1)(A) § 115.166(1)(A)(i) [G]§ 115.166(2) § 115.166(3) § 115.166(3)(A)	§ 115.166 § 115.166(1) § 115.166(1)(A) § 115.166(1)(A)(i) [G]§ 115.166(2) § 115.166(3) § 115.166(3)(A)	None
MODZ-1608VNT	EP	R5720	HIGHLY REACTIVE VOC	30 TAC Chapter 115, HRVOC Vent Gas	§ 115.727(c)(2)	A vent gas stream that has the potential to emit HRVOCs, but has a concentration less than 100 ppmv at all times or has a maximum potential flow rate equal to or less than 100 dry standard cubic feet per hour is exempt from this division with the exception of § 115.726(e)(3)(A) of this title. The maximum potential HRVOC emissions for the sum of all vent gas streams claimed under this exemption, must be less for the account specified in § 115.722(a) or (b) of this title than 0.5 tpy.	None	§ 115.726(e)(3)(A) § 115.726(j)(2)	None
MODZ-1608VNT	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas	§ 115.122(a)(1) § 115.121(a)(1)	Vent gas affected by §115.121(a)(1) must be	[G]§ 115.125 § 115.126(1)	§ 115.126 § 115.126(1)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Controls	§ 115.122(a)(1)(A)	controlled properly with a control efficiency > 90% or to a VOC concentration of no more than 20 ppmv (dry, corrected to 3% O ₂ for combustion devices).	§ 115.126(1)(A) § 115.126(1)(A)(i) § 115.126(2) ** See CAM Summary	§ 115.126(1)(A) § 115.126(1)(A)(i) § 115.126(2)	
MODZ-1608VNT	EP	63JJJ	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1321(c) [G]§ 63.1311(o) § 63.1322(b) § 63.1322(b)(2) § 63.1324(a)(2) § 63.1324(f)(1) § 63.1334(a)(1)	Aggregate batch vent streams. Aggregate batch vent streams, as defined in § 63.1312, are subject to the control requirements specified in § 63.1322(b), as well as the monitoring, testing, recordkeeping, and reporting requirements specified in §§ 63.1324 through 63.1327 for aggregate batch vent streams.	[G]§ 63.1323(h) § 63.1324(a) § 63.1324(a)(1) § 63.1324(c) § 63.1324(c)(1) § 63.1324(c)(1)(i) § 63.1324(e)(1) § 63.1334(a) § 63.1334(b)(2) § 63.1334(b)(4) § 63.1334(d) § 63.1335(d)(1) § 63.1335(d)(3) § 63.1335(d)(3)(i)	§ 63.1324(c)(1) § 63.1324(e)(1) § 63.1326(b) § 63.1326(b)(1) § 63.1326(b)(2) § 63.1326(b)(5) § 63.1326(c) § 63.1326(e)(3) § 63.1326(f) § 63.1326(f)(1) § 63.1326(f)(2) § 63.1335(d) § 63.1335(d)(2) § 63.1335(d)(6) [G]§ 63.1335(d)(7) § 63.1335(d)(8)	§ 63.1327(a) § 63.1327(a)(1) § 63.1327(g)(1) § 63.1334(a) § 63.1334(a)(2)
MODZ-1781	EU	R117-001	NO _x	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(1)(B) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO _x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C) § 117.8000(b) § 117.8000(c) § 117.8000(c)(1)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	§ 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d)		[G]§ 117.8010(7) [G]§ 117.8010(8)
MODZ-1781	EU	R117-001	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B) § 117.310(c)(3) § 117.8120	CO emissions must not exceed 400 ppmv at 3.0% O ₂ , dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.8000(b) § 117.8000(c) § 117.8000(c)(2) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8120(2) [G]§ 117.8120(2)(A) § 117.8120(2)(B)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
MODZ-1781	EU	60DC	SO ₂	40 CFR Part 60, Subpart Dc	§ 60.40c(a)	This subpart applies to each steam generating unit constructed, reconstructed, or modified after 6/9/89 and that has a maximum design heat input capacity of 2.9-29 megawatts (MW).	None	§ 60.48c(g)(1) § 60.48c(g)(2) § 60.48c(g)(3) § 60.48c(i)	[G]§ 60.48c(a) § 60.48c(j)
MODZ-1781	EU	60DC	PM	40 CFR Part 60, Subpart Dc	§ 60.40c(a)	This subpart applies to each steam generating unit constructed, reconstructed, or modified after 6/9/89 and that has a maximum design heat input capacity of 2.9-29 megawatts (MW).	None	§ 60.48c(g)(1) § 60.48c(g)(2) § 60.48c(g)(3) § 60.48c(i)	[G]§ 60.48c(a) § 60.48c(j)
MODZ-1781	EU	60DC	PM	40 CFR Part 60,	§ 60.40c(a)	This subpart applies to each	None	§ 60.48c(g)(1)	[G]§ 60.48c(a)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
			(OPACITY)	Subpart Dc		steam generating unit constructed, reconstructed, or modified after 6/9/89 and that has a maximum design heat input capacity of 2.9-29 megawatts (MW).		§ 60.48c(g)(2) § 60.48c(g)(3) § 60.48c(i)	§ 60.48c(j)
MODZ-2625	EP	63JJJ	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1315(b)(2) [G]§ 63.1311(o)	Not allow organic HAP emissions from the collection of continuous process vents at the affected source to be greater than 0.000590 kg organic HAP/Mg of product. Compliance with this paragraph (b)(2) shall be determined using the procedures specified in 63.1333(b).	[G]§ 63.116(c)(4) § 63.1318(b)(1)(ii) [G]§ 63.1333(b)	None	None
MODZ-2652	EP	R5720	HIGHLY REACTIVE VOC	30 TAC Chapter 115, HRVOC Vent Gas	§ 115.727(c)(2)	A vent gas stream that has the potential to emit HRVOCs, but has a concentration less than 100 ppmv at all times or has a maximum potential flow rate equal to or less than 100 dry standard cubic feet per hour is exempt from this division with the exception of § 115.726(e)(3)(A) of this title. The maximum potential HRVOC emissions for the sum of all vent gas streams claimed under this exemption, must be less for the account specified in § 115.722(a) or (b) of this title than 0.5 tpy.	None	§ 115.726(e)(3)(A) § 115.726(j)(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
MODZ-2652	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
MODZ-2652	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(B) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream specified in § 115.121(a)(1) of this title with a concentration of VOC < 612 ppmv is exempt from § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
MODZ-2652	EP	63JJJ	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1315(b)(2) [G]§ 63.1311(o)	Not allow organic HAP emissions from the collection of continuous process vents at the affected source to be greater than 0.000590 kg organic HAP/Mg of product. Compliance with this paragraph (b)(2) shall be determined using the procedures specified in 63.1333(b).	[G]§ 63.116(c)(4) § 63.1318(b)(1)(ii) [G]§ 63.1333(b)	None	None
MODZ-2655	EP	R5720	HIGHLY REACTIVE VOC	30 TAC Chapter 115, HRVOC Vent Gas	§ 115.727(c)(2)	A vent gas stream that has the potential to emit HRVOCs, but has a concentration less than 100 ppmv at all times or has a maximum potential flow rate equal to or less than 100 dry standard cubic feet per hour is exempt from this division with the exception of § 115.726(e)(3)(A) of this title.	None	§ 115.726(e)(3)(A) § 115.726(j)(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						The maximum potential HRVOC emissions for the sum of all vent gas streams claimed under this exemption, must be less for the account specified in § 115.722(a) or (b) of this title than 0.5 tpy.			
MODZ-2655	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
MODZ-2655	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(B) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream specified in § 115.121(a)(1) of this title with a concentration of VOC < 612 ppmv is exempt from § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
MODZ-2655	EP	63JJJ	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1321(a) [G]§ 63.1311(o) § 63.1322(a) § 63.1322(h) § 63.1323(i)(2) § 63.1323(i)(3)(i) § 63.1323(i)(3)(ii)	Except as specified, new/existing batch process vents (BPV) shall comply with §§63.1322-27. The BPV group status shall be determined by §63.1323. BPV classified as Grp. 1 shall comply with the reference control technology (RCT) in §63.1322, the monitoring in §63.1324, the performance test methods and procedures in §63.1325, the R/K in §63.1326, and the reporting in §63.1327. Grp.	§ 63.1323(a) § 63.1323(a)(1)(i) § 63.1323(a)(1)(ii) § 63.1323(a)(2) § 63.1323(b) § 63.1323(b)(1) § 63.1323(b)(2) § 63.1323(b)(3) [G]§ 63.1323(b)(4) [G]§ 63.1323(b)(5) § 63.1323(b)(6) § 63.1323(b)(6)(i) [G]§ 63.1323(b)(6)(i)(A) § 63.1323(b)(6)(i)(B)	§ 63.1323(b)(6) § 63.1326(a) § 63.1326(a)(1) [G]§ 63.1326(a)(2) [G]§ 63.1326(a)(3) [G]§ 63.1326(a)(9)	§ 63.1323(b)(6)(i)(C) § 63.1323(b)(6)(iii)(A) § 63.1323(b)(6)(iii)(B) § 63.1327(a) § 63.1327(a)(1) § 63.1327(a)(4) § 63.1327(a)(5) § 63.1327(a)(6) § 63.1327(b) § 63.1335(e)(3)(vi)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						2 BPV shall comply with the applicable RCT in §63.1322, the R/K in §63.1326, and the reporting in §63.1327.	[G]§ 63.1323(b)(6)(ii) § 63.1323(b)(7) § 63.1323(b)(8) [G]§ 63.1323(b)(9)		
MODZ-2656	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
MODZ-2656	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(B) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream specified in § 115.121(a)(1) of this title with a concentration of VOC < 612 ppmv is exempt from § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
MODZ-2753	EU	R5760	HIGHLY REACTIVE VOC	30 TAC Chapter 115, HRVOC Cooling Towers	§ 115.761(c)(1) § 115.761(c)(3) § 115.766(i)	HRVOC emissions at each site located in Harris County that is subject to this division or Division 1 of this subchapter must not exceed 1,200 pounds of HRVOCs per one-hour block period from any flare, vent, pressure relief valve, cooling tower, or any combination.	§ 115.764(b)(2) § 115.764(b)(4) § 115.764(b)(5) § 115.764(c) § 115.764(e)(1)	§ 115.766(a)(1) § 115.766(a)(2) § 115.766(a)(3) § 115.766(a)(4) § 115.766(a)(5) § 115.766(a)(6) § 115.766(c) [G]§ 115.766(e) [G]§ 115.766(g) [G]§ 115.766(h) § 115.766(i)(1)	§ 115.766(i)(2)
MODZ-2753	EU	63JJJ	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1328(a) [G]§ 63.104(a) [G]§ 63.104(d) § 63.104(e) § 63.104(e)(1) [G]§ 63.104(e)(2) [G]§ 63.1311(o)	Each owner or operator of an affected source shall comply with 63.104 for heat exchange systems.	[G]§ 63.104(b)	[G]§ 63.104(e)(2) [G]§ 63.104(f)(1)	[G]§ 63.104(f)(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.1328(e)				
MODZ-2781	EU	R117-001	NO _x	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(1)(B) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO _x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C) § 117.8000(b) § 117.8000(c) § 117.8000(c)(1) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
MODZ-2781	EU	R117-001	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B) § 117.310(c)(3) § 117.8120	CO emissions must not exceed 400 ppmv at 3.0% O ₂ , dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.8000(b) § 117.8000(c) § 117.8000(c)(2) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8120(2) [G]§ 117.8120(2)(A) § 117.8120(2)(B)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
MODZ-2781	EU	60DC	SO ₂	40 CFR Part 60, Subpart Dc	§ 60.40c(a)	This subpart applies to each steam generating unit constructed, reconstructed, or modified after 6/9/89 and that has a maximum design heat input capacity of 2.9-29 megawatts (MW).	None	§ 60.48c(g)(1) § 60.48c(g)(2) § 60.48c(g)(3) § 60.48c(i)	[G]§ 60.48c(a) § 60.48c(j)
MODZ-2781	EU	60DC	PM	40 CFR Part 60, Subpart Dc	§ 60.40c(a)	This subpart applies to each steam generating unit constructed, reconstructed, or modified after 6/9/89 and that has a maximum design heat input capacity of 2.9-29 megawatts (MW).	None	§ 60.48c(g)(1) § 60.48c(g)(2) § 60.48c(g)(3) § 60.48c(i)	[G]§ 60.48c(a) § 60.48c(j)
MODZ-2781	EU	60DC	PM (OPACITY)	40 CFR Part 60, Subpart Dc	§ 60.40c(a)	This subpart applies to each steam generating unit constructed, reconstructed, or modified after 6/9/89 and that has a maximum design heat input capacity of 2.9-29 megawatts (MW).	None	§ 60.48c(g)(1) § 60.48c(g)(2) § 60.48c(g)(3) § 60.48c(i)	[G]§ 60.48c(a) § 60.48c(j)
MODZ-3654	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
MODZ-3654	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(B) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream specified in § 115.121(a)(1) of this title with a concentration of VOC < 612 ppmv is exempt from § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
MODZ-3655	EP	R5121	VOC	30 TAC Chapter	§ 115.127(a)(2)(A)	A vent gas stream having a	[G]§ 115.125	§ 115.126	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				115, Vent Gas Controls	[G]§ 115.122(a)(4) § 115.127(a)(2)	combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	§ 115.126(2)	§ 115.126(2) § 115.126(4)	
MODZ-3655	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(B) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream specified in § 115.121(a)(1) of this title with a concentration of VOC < 612 ppmv is exempt from § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
MODZ-3656	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
MODZ-3656	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(B) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream specified in § 115.121(a)(1) of this title with a concentration of VOC < 612 ppmv is exempt from § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
MODZ-3753	EU	63FFFF	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2490(a)-Table10 § 63.104(a) [G]§ 63.104(d) § 63.104(e) § 63.104(e)(1) [G]§ 63.104(e)(2) § 63.2490(a) § 63.2490(b) § 63.2490(c)	For each heat exchange system, as defined in §63.101, comply with the requirements of §63.104 and the requirements referenced therein except as specified in §63.2490.	[G]§ 63.104(b)	[G]§ 63.104(e)(2) [G]§ 63.104(f)(1)	[G]§ 63.104(f)(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
MODZ-3780	EU	R117-001	NO _x	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(1)(B) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO _x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C) § 117.8000(b) § 117.8000(c) § 117.8000(c)(1) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
MODZ-3780	EU	R117-001	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B) § 117.310(c)(3) § 117.8120	CO emissions must not exceed 400 ppmv at 3.0% O ₂ , dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.8000(b) § 117.8000(c) § 117.8000(c)(2) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8120(2) [G]§ 117.8120(2)(A) § 117.8120(2)(B)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
MODZ-3780	EU	60DC	SO ₂	40 CFR Part 60,	§ 60.40c(a)	This subpart applies to each	None	§ 60.48c(g)(1)	[G]§ 60.48c(a)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Subpart Dc		steam generating unit constructed, reconstructed, or modified after 6/9/89 and that has a maximum design heat input capacity of 2.9-29 megawatts (MW).		§ 60.48c(g)(2) § 60.48c(g)(3) § 60.48c(i)	§ 60.48c(j)
MODZ-3780	EU	60DC	PM	40 CFR Part 60, Subpart Dc	§ 60.40c(a)	This subpart applies to each steam generating unit constructed, reconstructed, or modified after 6/9/89 and that has a maximum design heat input capacity of 2.9-29 megawatts (MW).	None	§ 60.48c(g)(1) § 60.48c(g)(2) § 60.48c(g)(3) § 60.48c(i)	[G]§ 60.48c(a) § 60.48c(j)
MODZ-3780	EU	60DC	PM (OPACITY)	40 CFR Part 60, Subpart Dc	§ 60.40c(a)	This subpart applies to each steam generating unit constructed, reconstructed, or modified after 6/9/89 and that has a maximum design heat input capacity of 2.9-29 megawatts (MW).	None	§ 60.48c(g)(1) § 60.48c(g)(2) § 60.48c(g)(3) § 60.48c(i)	[G]§ 60.48c(a) § 60.48c(j)
MODZ-3781	EU	R117-001	NO _x	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(1)(B) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO _x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C) § 117.8000(b) § 117.8000(c) § 117.8000(c)(1) § 117.8000(c)(3)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						alternative methods specified in § 117.9800 to comply with § 117.320.	§ 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d)		[G]§ 117.8010(8)
MODZ-3781	EU	R117-001	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B) § 117.310(c)(3) § 117.8120	CO emissions must not exceed 400 ppmv at 3.0% O ₂ , dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.8000(b) § 117.8000(c) § 117.8000(c)(2) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8120(2) [G]§ 117.8120(2)(A) § 117.8120(2)(B)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
MODZ-3781	EU	60DC	SO ₂	40 CFR Part 60, Subpart Dc	§ 60.40c(a)	This subpart applies to each steam generating unit constructed, reconstructed, or modified after 6/9/89 and that has a maximum design heat input capacity of 2.9-29 megawatts (MW).	None	§ 60.48c(g)(1) § 60.48c(g)(2) § 60.48c(g)(3) § 60.48c(i)	[G]§ 60.48c(a) § 60.48c(j)
MODZ-3781	EU	60DC	PM	40 CFR Part 60, Subpart Dc	§ 60.40c(a)	This subpart applies to each steam generating unit constructed, reconstructed, or modified after 6/9/89 and that has a maximum design heat input capacity of 2.9-29 megawatts (MW).	None	§ 60.48c(g)(1) § 60.48c(g)(2) § 60.48c(g)(3) § 60.48c(i)	[G]§ 60.48c(a) § 60.48c(j)
MODZ-3781	EU	60DC	PM (OPACITY)	40 CFR Part 60, Subpart Dc	§ 60.40c(a)	This subpart applies to each steam generating unit	None	§ 60.48c(g)(1) § 60.48c(g)(2)	[G]§ 60.48c(a) § 60.48c(j)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						constructed, reconstructed, or modified after 6/9/89 and that has a maximum design heat input capacity of 2.9-29 megawatts (MW).		§ 60.48c(g)(3) § 60.48c(i)	
MODZ-652	EP	R5720	HIGHLY REACTIVE VOC	30 TAC Chapter 115, HRVOC Vent Gas	§ 115.727(c)(2)	A vent gas stream that has the potential to emit HRVOCs, but has a concentration less than 100 ppmv at all times or has a maximum potential flow rate equal to or less than 100 dry standard cubic feet per hour is exempt from this division with the exception of § 115.726(e)(3)(A) of this title. The maximum potential HRVOC emissions for the sum of all vent gas streams claimed under this exemption, must be less for the account specified in § 115.722(a) or (b) of this title than 0.5 tpy.	None	§ 115.726(e)(3)(A) § 115.726(j)(2)	None
MODZ-652	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
MODZ-652	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(B) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream specified in § 115.121(a)(1) of this title with a concentration of VOC < 612 ppmv is exempt from	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						§ 115.121(a)(1).			
MODZ-652	EP	63JJJ	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1321(a) [G]§ 63.1311(o) § 63.1322(a) § 63.1322(h) § 63.1323(i)(2) § 63.1323(i)(3)(i) § 63.1323(i)(3)(ii)	Except as specified, new/existing batch process vents (BPV) shall comply with §§63.1322-27. The BPV group status shall be determined by §63.1323. BPV classified as Grp. 1 shall comply with the reference control technology (RCT) in §63.1322, the monitoring in §63.1324, the performance test methods and procedures in §63.1325, the R/K in §63.1326, and the reporting in §63.1327. Grp. 2 BPV shall comply with the applicable RCT in §63.1322, the R/K in §63.1326, and the reporting in §63.1327.	§ 63.1323(a) § 63.1323(a)(1)(i) § 63.1323(a)(1)(ii) § 63.1323(a)(2) § 63.1323(b) § 63.1323(b)(1) § 63.1323(b)(2) § 63.1323(b)(3) [G]§ 63.1323(b)(4) [G]§ 63.1323(b)(5) § 63.1323(b)(6) § 63.1323(b)(6)(i) [G]§ 63.1323(b)(6)(i)(A) § 63.1323(b)(6)(i)(B) [G]§ 63.1323(b)(6)(ii) § 63.1323(b)(7) § 63.1323(b)(8) [G]§ 63.1323(b)(9)	§ 63.1323(b)(6) § 63.1326(a) § 63.1326(a)(1) [G]§ 63.1326(a)(2) [G]§ 63.1326(a)(3) [G]§ 63.1326(a)(9)	§ 63.1323(b)(6)(i)(C) § 63.1323(b)(6)(iii)(A) § 63.1323(b)(6)(iii)(B) § 63.1327(a) § 63.1327(a)(1) § 63.1327(a)(4) § 63.1327(a)(5) § 63.1327(a)(6) § 63.1327(b) § 63.1335(e)(3)(vi)
MODZ-655	EP	R5720	HIGHLY REACTIVE VOC	30 TAC Chapter 115, HRVOC Vent Gas	§ 115.727(c)(2)	A vent gas stream that has the potential to emit HRVOCs, but has a concentration less than 100 ppmv at all times or has a maximum potential flow rate equal to or less than 100 dry standard cubic feet per hour is exempt from this division with the exception of § 115.726(e)(3)(A) of this title. The maximum potential HRVOC emissions for the sum of all vent gas streams claimed under this	None	§ 115.726(e)(3)(A) § 115.726(j)(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						exemption, must be less for the account specified in § 115.722(a) or (b) of this title than 0.5 tpy.			
MODZ-655	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
MODZ-655	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(B) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream specified in § 115.121(a)(1) of this title with a concentration of VOC < 612 ppmv is exempt from § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
MODZ-655	EP	63JJJ	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1321(a) [G]§ 63.1311(o) § 63.1322(a) § 63.1322(h) § 63.1323(i)(2) § 63.1323(i)(3)(i) § 63.1323(i)(3)(ii)	Except as specified, new/existing batch process vents (BPV) shall comply with §§63.1322-27. The BPV group status shall be determined by §63.1323. BPV classified as Grp. 1 shall comply with the reference control technology (RCT) in §63.1322, the monitoring in §63.1324, the performance test methods and procedures in §63.1325, the R/K in §63.1326, and the reporting in §63.1327. Grp. 2 BPV shall comply with the applicable RCT in §63.1322, the R/K in §63.1326, and the reporting in §63.1327.	§ 63.1323(a) § 63.1323(a)(1)(i) § 63.1323(a)(1)(ii) § 63.1323(a)(2) § 63.1323(b) § 63.1323(b)(1) § 63.1323(b)(2) § 63.1323(b)(3) [G]§ 63.1323(b)(4) [G]§ 63.1323(b)(5) § 63.1323(b)(6) § 63.1323(b)(6)(i) [G]§ 63.1323(b)(6)(i)(A) § 63.1323(b)(6)(i)(B) [G]§ 63.1323(b)(6)(ii) § 63.1323(b)(7) § 63.1323(b)(8)	§ 63.1323(b)(6) § 63.1326(a) § 63.1326(a)(1) [G]§ 63.1326(a)(2) [G]§ 63.1326(a)(3) [G]§ 63.1326(a)(9)	§ 63.1323(b)(6)(i)(C) § 63.1323(b)(6)(iii)(A) § 63.1323(b)(6)(iii)(B) § 63.1327(a) § 63.1327(a)(1) § 63.1327(a)(4) § 63.1327(a)(5) § 63.1327(a)(6) § 63.1327(b) § 63.1335(e)(3)(vi)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							[G]§ 63.1323(b)(9)		
MODZ-656	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
MODZ-656	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(B) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream specified in § 115.121(a)(1) of this title with a concentration of VOC < 612 ppmv is exempt from § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
MODZ-753	EU	R5760	HIGHLY REACTIVE VOC	30 TAC Chapter 115, HRVOC Cooling Towers	§ 115.761(c)(1) § 115.761(c)(3) § 115.766(i)	HRVOC emissions at each site located in Harris County that is subject to this division or Division 1 of this subchapter must not exceed 1,200 pounds of HRVOCs per one-hour block period from any flare, vent, pressure relief valve, cooling tower, or any combination.	§ 115.764(b)(2) § 115.764(b)(4) § 115.764(b)(5) § 115.764(c) § 115.764(e)(1)	§ 115.766(a)(1) § 115.766(a)(2) § 115.766(a)(3) § 115.766(a)(4) § 115.766(a)(5) § 115.766(a)(6) § 115.766(c) [G]§ 115.766(e) [G]§ 115.766(g) [G]§ 115.766(h) § 115.766(i)(1)	§ 115.766(i)(2)
MODZ-753	EU	63JJJ	112(B) HAPS	40 CFR Part 63, Subpart JJJ	§ 63.1328(a) [G]§ 63.104(a) [G]§ 63.104(d) § 63.104(e) § 63.104(e)(1) [G]§ 63.104(e)(2) [G]§ 63.1311(o) § 63.1328(e)	Each owner or operator of an affected source shall comply with 63.104 for heat exchange systems.	[G]§ 63.104(b)	[G]§ 63.104(e)(2) [G]§ 63.104(f)(1)	[G]§ 63.104(f)(2)
MODZ-78oS	EU	R117-001	NO _x	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a)	An owner or operator may not use the alternative	[G]§ 117.335(a)(1) § 117.335(a)(4)	§ 117.345(a) § 117.345(f)	§ 117.335(b) § 117.335(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 117.310(a)(1)(A) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO _x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	§ 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(g) § 117.340(a) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) [G]§ 117.340(c)(3) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)	§ 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	[G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
MODZ-78oS	EU	R117-001	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O ₂ , dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 117.8120		§ 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a) § 117.340(b)(1) § 117.340(b)(3) § 117.340(e) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii)) § 117.8100(a)(1)(B)(iii)) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120(1) § 117.8120(1)(A)	§ 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
MODZ-78oS	EU	60Db	PM	40 CFR Part 60, Subpart Db	§ 60.40b(a)	This subpart applies to each steam generating unit constructed, modified, or reconstructed after 6/19/84, and that has a heat input capacity from fuels	None	[G]§ 60.49b(d) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						combusted in the unit > 29 MW (100 MMBtu/hr).			
MODZ-78oS	EU	6oDb	PM (OPACITY)	40 CFR Part 60, Subpart Db	§ 60.40b(a)	This subpart applies to each steam generating unit constructed, modified, or reconstructed after 6/19/84, and that has a heat input capacity from fuels combusted in the unit > 29 MW (100 MMBtu/hr).	None	[G]§ 60.49b(d) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3)
MODZ-78oS	EU	6oDb	NO _x	40 CFR Part 60, Subpart Db	§ 60.44b(l)(1) § 60.44b(h) § 60.44b(i) § 60.46b(a)	Affected facilities combusting coal, oil, or natural gas, or a mixture of these fuels, or any other fuels: a limit of 86 ng/JI (0.20 lb/million Btu) heat input unless the affected facility meets the specified requirements.	§ 60.46b(c) § 60.46b(e) § 60.46b(e)(1) § 60.46b(e)(4) [G]§ 60.48b(b) § 60.48b(c) § 60.48b(d) § 60.48b(e) [G]§ 60.48b(e)(2) § 60.48b(e)(3) § 60.48b(f) § 60.48b(g)(1)	[G]§ 60.48b(b) § 60.48b(c) [G]§ 60.49b(d) [G]§ 60.49b(g) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3) § 60.49b(b) § 60.49b(h) § 60.49b(h)(4) § 60.49b(i) § 60.49b(v) § 60.49b(w)
MSAP-S623C	EU	R7300	EXEMPT	30 TAC Chapter 117, Subchapter B	[G]§ 117.303(a)(11) [G]§ 117.310(f)	Units exempted from the provisions of this division except as specified in §§117.310(f), 117.340(j), 117.345(f)(6) and (10), 117.350(c)(1) and 117.354(a)(5) include new, modified, reconstructed, or relocated stationary diesel engine placed into service on or after October 1, 2001, that operates less than 100 hours per year, based on a rolling 12-month average, in other than emergency	None	§ 117.340(j) [G]§ 117.345(f)(10) [G]§ 117.345(f)(6)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						situations; and meets the requirements for non-road engines as specified. §117.303(a)(11)(A)-(B)			
MSAP-S623C	EU	6oIII	CO	40 CFR Part 60, Subpart III	§ 60.4205(b) § 60.4202(e)(1) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218 § 94.8(a)(2)	Owners and operators of emergency stationary CI ICE, that are not fire pump engines, with a displacement of greater than or equal to 10 liters per cylinder and less than 30 liters per cylinder and is a 2007 model year and later must comply with a CO emission limit of 5.0 g/KW-hr, as stated in 40 CFR 60.4202(e)-(f) and 40 CFR 94.8(a)(2) and 40 CFR 1042.101.	None	None	[G]§ 60.4214(d)
MSAP-S623C	EU	6oIII	Total Hydrocarbons/NO	40 CFR Part 60, Subpart III	§ 60.4205(b) § 60.4202(e)(1) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218 § 94.8(a)(2)	Owners and operators of emergency stationary CI ICE, that are not fire pump engines, with a displacement of greater than or equal to 10 liters per cylinder and less than 15 liters per cylinder and is a 2007 - 2012 model year must comply with a THC+NOx emission limit of 7.8 g/KW-hr, as stated in 40 CFR 60.4202(e)(1) and 40 CFR 94.8(a)(2).	None	None	[G]§ 60.4214(d)
MSAP-S623C	EU	6oIII	PM	40 CFR Part 60, Subpart III	§ 60.4205(b) § 60.4202(e)(1) § 60.4206 § 60.4207(b)	Owners and operators of emergency stationary CI ICE, that are not fire pump engines, with a	None	None	[G]§ 60.4214(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218 § 94.8(a)(2)	displacement of greater than or equal to 10 liters per cylinder and less than 15 liters per cylinder and is a 2007 - 2012 model year must comply with a PM emission limit of 0.27 g/KW-hr, as stated in 40 CFR 60.4202(e)(1) and 40 CFR 94.8(a)(2).			
MSAP-S623C	EU	63ZZZZ	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(c)	Stationary RICE subject to Regulations under 40 CFR Part 60. An affected source that meets any of the criteria in paragraphs (c)(1) through (7) of this section must meet the requirements of this part by meeting the requirements of 40 CFR part 60 subpart IIII, for compression ignition engines or 40 CFR part 60 subpart JJJJ, for spark ignition engines as applicable. No further requirements apply for such engines under this part.	None	None	None
MSAT-S106	EU	R5112	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for	[G]§ 115.117 ** See Periodic Monitoring Summary	§ 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.			
MSAT-S107	EU	R5112	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	[G]§ 115.117 ** See Periodic Monitoring Summary	§ 115.118(a)(5) § 115.118(a)(7)	None
MSAT-S415	EU	R5112	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
MSAT-S503	EU	R5112	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control	[G]§ 115.117 ** See Periodic Monitoring Summary	§ 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.			
MSAT-S713	EU	R5112	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	[G]§ 115.117 ** See Periodic Monitoring Summary	§ 115.118(a)(5) § 115.118(a)(7)	None
MSAT-S718	EU	R5112	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
MSAT-S719	EU	R5112	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
MSAY-S601	EU	63FFFF	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2490(a)- Table10 § 63.104(a) [G]§ 63.104(d) § 63.104(e) § 63.104(e)(1) [G]§ 63.104(e)(2) § 63.2490(a) § 63.2490(b) § 63.2490(c)	For each heat exchange system, as defined in §63.101, comply with the requirements of §63.104 and the requirements referenced therein except as specified in §63.2490.	[G]§ 63.104(b)	[G]§ 63.104(e)(2) [G]§ 63.104(f)(1)	[G]§ 63.104(f)(2)
MSAZ-S419	EP	R1111	PM (OPACITY)	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(A) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall not exceed an opacity of 30% averaged over a six minute period.	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None
MSAZ-S419	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
MSAZ-S419	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(B) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream specified in § 115.121(a)(1) of this title with a concentration of VOC < 612 ppmv is exempt from § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
MSAZ-S421	EU	R1111	PM (OPACITY)	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(4)(A)	Visible emissions from a process gas flare shall not be permitted for more than five minutes in any two-hour period, except for upset emissions as provided in §101.11(a).	§ 111.111(a)(4)(A)(i) § 111.111(a)(4)(A)(ii) ** See CAM Summary	§ 111.111(a)(4)(A)(ii)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
MSAZ-S421	CD	63A	112(B) HAPS	40 CFR Part 63, Subpart A	§ 63.11(b)(4) § 63.11(b)(1) § 63.11(b)(2) § 63.11(b)(3) § 63.11(b)(5) § 63.11(b)(6)(ii) § 63.11(b)(8)	Flares shall be designed and operated with no visible emissions, except for periods of a total of 5 minutes or less during any 2 consecutive hrs. Test Method 22 in App. A of part 60 of this chapter shall be used.	§ 63.11(b)(4) § 63.11(b)(5)	None	None
MSAZ-S421VNT	PRO	R5160	VOC	30 TAC Chapter 115, Batch Processes	§ 115.167(2) § 115.162(3)	Combined vents from a batch process train or single unit operations that meet the criteria in § 115.162(2)(A) or (B), respectively, are exempt from the requirements of this division, except for §§115.161(b) and (C), 115.164, and 115.166(2).	§ 115.164(1) § 115.164(2) § 115.166 [G]§ 115.166(2)	§ 115.166 [G]§ 115.166(2)	None
MSAZ-S421VNT	PRO	R5160	VOC	30 TAC Chapter 115, Batch Processes	§ 115.162(1) § 115.162(1)(A) § 115.162(1)(B) § 115.162(1)(C) § 115.162(2) § 115.162(2)(B) § 115.162(2)(D) § 115.162(2)(E) § 60.18(b)	The mass emission rate from individual process vents or for process vent streams in aggregate within a batch process shall be reduced by 90% if the actual average flow rate value is below the flow rate value calculated using the applicable RACT equation.	§ 115.164(1) § 115.164(2) § 115.165(2)(C)(i) § 115.165(2)(C)(iii) § 115.165(2)(D) § 115.165(2)(E) § 115.166 § 115.166(1) § 115.166(1)(B) [G]§ 115.166(2) § 115.166(3) § 115.166(3)(B)	§ 115.166 § 115.166(1) § 115.166(1)(B) [G]§ 115.166(2) § 115.166(3) § 115.166(3)(B)	None
MSAZ-S421VNT	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(a)(1) § 115.121(a)(1) § 115.122(a)(1)(B) § 60.18	Vent gas affected by §115.121(a)(1) must be controlled properly with a control efficiency > 90% or to a VOC concentration of no more than 20 ppmv (dry,	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2) ** See CAM Summary	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						corrected to 3% O2 for combustion devices).			
MSAZ-S421VNT	EP	63FFFF	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2460(a) § 63.11(b) § 63.2450(b) § 63.2460(a)-Table 2.1.b § 63.2460(a)-Table 2.1.c § 63.2460(b) § 63.2460(c)(7) § 63.2460(c)(9)(i) § 63.982(b) § 63.983(a)(1) § 63.983(a)(2) § 63.983(a)(3) § 63.983(a)(3)(ii) § 63.983(d)(1) § 63.983(d)(1)(f) [G]§ 63.983(d)(2) § 63.983(d)(3) § 63.987(a) § 63.997(b)(1) § 63.997(c)(3)	You must meet each emission limit in Table 2 to this subpart that applies to you, and you must meet each applicable requirement specified in §63.2460(b) and (c).	[G]§ 63.115(d)(2)(v) § 63.115(d)(3)(iii) § 63.2460(c)(2)(i) § 63.2460(c)(2)(ii) § 63.2460(c)(2)(vi) § 63.2460(c)(3) § 63.2460(c)(3)(i) § 63.2460(c)(4) § 63.2460(c)(6) § 63.2460(c)(9)(ii) § 63.2460(c)(9)(ii)(C) § 63.2460(c)(9)(iii) § 63.2460(c)(9)(iv) § 63.983(a)(3) § 63.983(a)(3)(ii) § 63.983(b) [G]§ 63.983(b)(1) [G]§ 63.983(b)(2) [G]§ 63.983(b)(3) [G]§ 63.983(b)(4) [G]§ 63.983(c)(1) § 63.983(c)(2) § 63.983(c)(3) § 63.983(d)(1) § 63.983(d)(1)(ii) § 63.987(c) § 63.997(b) § 63.997(b)(1) § 63.997(c)(2) § 63.997(c)(3) § 63.997(c)(3)(i) § 63.997(c)(3)(ii)	§ 63.2450(f)(2) § 63.2450(f)(2)(i) § 63.2450(f)(2)(ii) § 63.2460(c)(3)(ii) § 63.2460(c)(6) § 63.2460(c)(9)(ii)(A) § 63.2460(c)(9)(ii)(B) § 63.2460(c)(9)(iii) [G]§ 63.2525(d) § 63.2525(g) § 63.983(a)(3)(ii) § 63.983(b) [G]§ 63.983(d)(2) § 63.987(c) § 63.998(a)(1)(ii) § 63.998(a)(1)(iii)(A) § 63.998(a)(1)(iii)(B) [G]§ 63.998(b)(1) [G]§ 63.998(b)(2) [G]§ 63.998(b)(3) [G]§ 63.998(b)(5) [G]§ 63.998(c)(1) [G]§ 63.998(d)(1) § 63.998(d)(3)(i) § 63.998(d)(3)(ii) § 63.998(d)(5)	§ 63.2450(f)(2)(ii) § 63.2450(q) § 63.2460(c)(3)(i) § 63.2460(c)(9)(ii)(A) § 63.2460(c)(9)(ii)(C) § 63.2460(c)(9)(ii)(D) § 63.997(b)(1) § 63.997(c)(3) § 63.998(a)(1)(iii)(A) [G]§ 63.998(b)(3) [G]§ 63.999(a)(1) § 63.999(b)(5) § 63.999(c)(1) § 63.999(c)(2)(i) § 63.999(c)(2)(iii) § 63.999(c)(3) § 63.999(c)(6) [G]§ 63.999(c)(6)(i) § 63.999(c)(6)(iv) [G]§ 63.999(d)(1) [G]§ 63.999(d)(2)
NUT1P-9013	EU	R117-1	EXEMPT	30 TAC Chapter 117, Subchapter B	[G]§ 117.303(a)(11) [G]§ 117.310(f)	Units exempted from the provisions of this division except as specified in	None	§ 117.340(j) [G]§ 117.345(f)(10) [G]§ 117.345(f)(6)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						§§117.310(f), 117.340(j), 117.345(f)(6) and (10), 117.350(c)(1) and 117.354(a)(5) include new, modified, reconstructed, or relocated stationary diesel engine placed into service on or after October 1, 2001, that operates less than 100 hours per year, based on a rolling 12-month average, in other than emergency situations; and meets the requirements for non-road engines as specified. §117.303(a)(11)(A)-(B)			
NUT1P-9013	EU	63ZZZZ-01	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6602-Table2c.1 § 63.6595(a)(1) § 63.6605(a) § 63.6605(b) § 63.6625(e) § 63.6625(h) § 63.6625(i) § 63.6640(b) § 63.6640(f)(1) [G]§ 63.6640(f)(2) § 63.6640(f)(3)	For each existing emergency stationary CI RICE and black start stationary CI RICE, located at a major source, you must comply with the requirements as specified in Table 2c.1.a-c.	§ 63.6625(f) § 63.6625(i) § 63.6640(a) § 63.6640(a)-Table6.9.a.i § 63.6640(a)-Table6.9.a.ii § 63.6640(b)	§ 63.6625(i) § 63.6655(a) § 63.6655(a)(1) § 63.6655(d) § 63.6655(e) § 63.6655(f) § 63.6660(a) § 63.6660(b) § 63.6660(c)	§ 63.6640(b) § 63.6640(e) § 63.6650(f)
NUT1T-4201	EU	R115TNK-001	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(3) § 115.112(e)(3)(C) § 60.18	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in	§ 115.115(a) § 115.115(a)(6) § 115.116(a)(2) [G]§ 115.117	§ 115.118(a)(4) § 115.118(a)(4)(F) § 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.			
NUT1T-4201	EU	60KB-001	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(3)	Storage vessels specified in §60.112b(a) and equipped with a closed vent system/control device are to meet the specifications of §60.112b(a)(3)(i)-(ii).	[G]§ 60.113b(c)(1) § 60.113b(c)(2) § 60.116b(a) § 60.116b(b) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3) [G]§ 60.485(b) ** See Periodic Monitoring Summary	§ 60.115b [G]§ 60.115b(c) § 60.116b(a) § 60.116b(b)	[G]§ 60.113b(c)(1) § 60.115b
NUT1T-4207	EU	R115TNK-002	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(3) § 115.112(e)(3)(C) § 60.18	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.115(a) § 115.115(a)(6) § 115.116(a)(2) [G]§ 115.117	§ 115.118(a)(4) § 115.118(a)(4)(F) § 115.118(a)(5) § 115.118(a)(7)	None
NUT1T-4207	EU	R5112-2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining	[G]§ 115.117 ** See Periodic Monitoring Summary	§ 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.			
NUT1T-4211	EU	R115TNK-015	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(3) § 115.112(e)(3)(C) § 60.18	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.115(a) § 115.115(a)(6) § 115.116(a)(2) [G]§ 115.117	§ 115.118(a)(4) § 115.118(a)(4)(F) § 115.118(a)(5) § 115.118(a)(7)	None
NUT1T-4211	EU	R5112-2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in	[G]§ 115.117 ** See Periodic Monitoring Summary	§ 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.			
NUT1T-5058	EU	R115TNK-003	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(3) § 115.112(e)(3)(C) § 60.18	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.115(a) § 115.115(a)(6) § 115.116(a)(2) [G]§ 115.117	§ 115.118(a)(4) § 115.118(a)(4)(F) § 115.118(a)(5) § 115.118(a)(7)	None
NUT1T-5058	EU	R5112-2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	[G]§ 115.117 ** See Periodic Monitoring Summary	§ 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
NUT1T-5103	EU	R115TNK-016	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(3) § 115.112(e)(3)(C) § 60.18	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.115(a) § 115.115(a)(6) § 115.116(a)(2) [G]§ 115.117	§ 115.118(a)(4) § 115.118(a)(4)(F) § 115.118(a)(5) § 115.118(a)(7)	None
NUT1T-5103	EU	R5112-2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	[G]§ 115.117 ** See Periodic Monitoring Summary	§ 115.118(a)(5) § 115.118(a)(7)	None
NUT1T-5104	EU	R115TNK-004	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(3) § 115.112(e)(3)(C) § 60.18	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any	§ 115.115(a) § 115.115(a)(6) § 115.116(a)(2) [G]§ 115.117	§ 115.118(a)(4) § 115.118(a)(4)(F) § 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.			
NUT1T-5104	EU	R5112-2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	[G]§ 115.117 ** See Periodic Monitoring Summary	§ 115.118(a)(5) § 115.118(a)(7)	None
NUT1T-5104	EU	63EEEEET NK-001	112(B) HAPS	40 CFR Part 63, Subpart EEEE	§ 63.2338(b) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart EEEE
NUT1T-5110	EU	R115TNK-	VOC	30 TAC Chapter	§ 115.112(e)(1)	No person shall place, store,	§ 115.115(a)	§ 115.118(a)(4)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		005		115, Storage of VOCs	§ 115.112(e)(3) § 115.112(e)(3)(C) § 60.18	or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.115(a)(6) § 115.116(a)(2) [G]§ 115.117	§ 115.118(a)(4)(F) § 115.118(a)(5) § 115.118(a)(7)	
NUT1T-5110	EU	R5112-2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	[G]§ 115.117 ** See Periodic Monitoring Summary	§ 115.118(a)(5) § 115.118(a)(7)	None
NUT1T-5110	EU	63EEEEET NK-001	112(B) HAPS	40 CFR Part 63, Subpart EEEE	§ 63.2338(b) The permit holder shall comply with the applicable limitation, standard and/or equipment specification	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63,	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart EEEE

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					requirements of 40 CFR Part 63, Subpart EEEE		Subpart EEEE		
NUT1T-5113	EU	R115TNK-006	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(3) § 115.112(e)(3)(C) § 60.18	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.115(a) § 115.115(a)(6) § 115.116(a)(2) [G]§ 115.117	§ 115.118(a)(4) § 115.118(a)(4)(F) § 115.118(a)(5) § 115.118(a)(7)	None
NUT1T-5113	EU	R5112-2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	[G]§ 115.117 ** See Periodic Monitoring Summary	§ 115.118(a)(5) § 115.118(a)(7)	None
NUT1T-5117	EU	R115TNK-007	VOC	30 TAC Chapter 115, Storage of	§ 115.112(e)(1) § 115.112(e)(3)	No person shall place, store, or hold VOC in any storage	§ 115.115(a) § 115.115(a)(6)	§ 115.118(a)(4) § 115.118(a)(4)(F)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				VOCs	§ 115.112(e)(3)(C) § 60.18	tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.116(a)(2) [G]§ 115.117	§ 115.118(a)(5) § 115.118(a)(7)	
NUT1T-5117	EU	R5112-2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	[G]§ 115.117 ** See Periodic Monitoring Summary	§ 115.118(a)(5) § 115.118(a)(7)	None
NUT1T-5117	EU	63EEEEET NK-001	112(B) HAPS	40 CFR Part 63, Subpart EEEE	§ 63.2338(b) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart EEEE

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					CFR Part 63, Subpart EEEE				
NUT1T-5200	EU	R115TNK-014	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(3) § 115.112(e)(3)(C) § 60.18	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.115(a) § 115.115(a)(6) § 115.116(a)(2) [G]§ 115.117	§ 115.118(a)(4) § 115.118(a)(4)(F) § 115.118(a)(5) § 115.118(a)(7)	None
NUT1T-5200	EU	R5112-2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	[G]§ 115.117 ** See Periodic Monitoring Summary	§ 115.118(a)(5) § 115.118(a)(7)	None
NUT1T-5200	EU	63EEEEET NK-001	112(B) HAPS	40 CFR Part 63, Subpart EEEE	§ 63.2338(b) The permit holder shall comply with	The permit holder shall comply with the applicable requirements of 40 CFR	The permit holder shall comply with the applicable	The permit holder shall comply with the applicable	The permit holder shall comply with the applicable reporting

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart EEEE	Part 63, Subpart EEEE	monitoring and testing requirements of 40 CFR Part 63, Subpart EEEE	recordkeeping requirements of 40 CFR Part 63, Subpart EEEE	requirements of 40 CFR Part 63, Subpart EEEE
NUT1T-5200LD	EU	R115UNL-002	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(a)(2)(A) [G]§ 115.212(a)(7) § 115.214(a)(1)(B) § 115.214(a)(1)(D) § 115.214(a)(1)(D)(i)	Any plant, excluding gasoline bulk plants, which loads less than 20,000 gpd of VOC with a true vapor pressure of 0.5 psia or greater is exempt from the requirements of this division, except for the specified requirements.	§ 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.215 § 115.215(4)	§ 115.216 § 115.216(2) § 115.216(3)(B) § 115.216(3)(D)	None
NUT1T-5205	EU	R115TNK-008	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(3) § 115.112(e)(3)(C) § 60.18	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.115(a) § 115.115(a)(6) § 115.116(a)(2) [G]§ 115.117	§ 115.118(a)(4) § 115.118(a)(4)(F) § 115.118(a)(5) § 115.118(a)(7)	None
NUT1T-5205	EU	R5112-2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient	[G]§ 115.117 ** See Periodic Monitoring Summary	§ 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.			
NUT1T-5210	EU	R115TNK-009	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(3) § 115.112(e)(3)(C) § 60.18	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.115(a) § 115.115(a)(6) § 115.116(a)(2) [G]§ 115.117	§ 115.118(a)(4) § 115.118(a)(4)(F) § 115.118(a)(5) § 115.118(a)(7)	None
NUT1T-5210	EU	R5112-2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for	[G]§ 115.117 ** See Periodic Monitoring Summary	§ 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.			
NUT1T-5308	EU	R115TNK-010	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(3) § 115.112(e)(3)(C) § 60.18	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.115(a) § 115.115(a)(6) § 115.116(a)(2) [G]§ 115.117	§ 115.118(a)(4) § 115.118(a)(4)(F) § 115.118(a)(5) § 115.118(a)(7)	None
NUT1T-5308	EU	R5112-2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	[G]§ 115.117 ** See Periodic Monitoring Summary	§ 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
NUT1T-5311	EU	R115TNK-011	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(3) § 115.112(e)(3)(C) § 60.18	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.115(a) § 115.115(a)(6) § 115.116(a)(2) [G]§ 115.117	§ 115.118(a)(4) § 115.118(a)(4)(F) § 115.118(a)(5) § 115.118(a)(7)	None
NUT1T-5311	EU	R5112-2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	[G]§ 115.117 ** See Periodic Monitoring Summary	§ 115.118(a)(5) § 115.118(a)(7)	None
NUT1T-5313	EU	R115TNK-012	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(3) § 115.112(e)(3)(C) § 60.18	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any	§ 115.115(a) § 115.115(a)(6) § 115.116(a)(2) [G]§ 115.117	§ 115.118(a)(4) § 115.118(a)(4)(F) § 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.			
NUT1T-5313	EU	R5112-2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	[G]§ 115.117 ** See Periodic Monitoring Summary	§ 115.118(a)(5) § 115.118(a)(7)	None
NUT1T-5321	EU	R115TNK-013	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(3) § 115.112(e)(3)(C) § 60.18	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil	§ 115.115(a) § 115.115(a)(6) § 115.116(a)(2) [G]§ 115.117	§ 115.118(a)(4) § 115.118(a)(4)(F) § 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.			
NUT1T-5321	EU	R5112-2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	[G]§ 115.117 ** See Periodic Monitoring Summary	§ 115.118(a)(5) § 115.118(a)(7)	None
NUTB-Q2425	EP	R115VENT-003	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
NUTB-Q2425	EP	R115VENT-003	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(B) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream specified in § 115.121(a)(1) of this title with a concentration of VOC < 612 ppmv is exempt from § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
NUTB-Q3805	EP	R115VENT-009	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC)	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						< 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).			
NUTB-Q3805	EP	R115VENT-009	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(B) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream specified in § 115.121(a)(1) of this title with a concentration of VOC < 612 ppmv is exempt from § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
NUTB-Q3810	EP	R115VENT-006	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
NUTB-Q3810	EP	R115VENT-006	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(B) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream specified in § 115.121(a)(1) of this title with a concentration of VOC < 612 ppmv is exempt from § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
NUTB-Q3813	EP	R115VENT-007	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
NUTB-Q3813	EP	R115VENT-007	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(B) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream specified in § 115.121(a)(1) of this title with a concentration of VOC < 612 ppmv is exempt from	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						§ 115.121(a)(1).			
NUTB-Q3814	EP	R115VENT-008	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
NUTB-Q3814	EP	R115VENT-008	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(B) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream specified in § 115.121(a)(1) of this title with a concentration of VOC < 612 ppmv is exempt from § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
NUTLABGEN	EU	R117-2	EXEMPT	30 TAC Chapter 117, Subchapter B	§ 117.303(a)(6)(D)	Units exempted from the provisions of this division, except as specified in §§117.310(f), 117.340(j), 117.345(f)(6) and (10), 117.350(c)(1), and 117.354(a)(5), include stationary gas turbines and stationary internal combustion engines that are used exclusively in emergency situations, except that operation for testing or maintenance purposes is allowed for up to 52 hours per year, based on a rolling 12-month average.	None	§ 117.340(j) [G]§ 117.345(f)(6)	None
NUTLABGEN	EU	63ZZZZ-02	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6602-Table2c.1 § 63.6595(a)(1) § 63.6605(a)	For each existing emergency stationary CI RICE and black start stationary CI RICE, located at a major	§ 63.6625(f) § 63.6625(i) § 63.6640(a) § 63.6640(a)-	§ 63.6625(i) § 63.6655(a) § 63.6655(a)(1) § 63.6655(d)	§ 63.6640(b) § 63.6640(e) § 63.6650(f)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.6605(b) § 63.6625(e) § 63.6625(h) § 63.6625(i) § 63.6640(b) § 63.6640(f)(1) [G]§ 63.6640(f)(2) § 63.6640(f)(3)	source, you must comply with the requirements as specified in Table 2c.1.a-c.	Table 6.9.a.i § 63.6640(a)- Table 6.9.a.ii § 63.6640(b)	§ 63.6655(e) § 63.6655(f) § 63.6660(a) § 63.6660(b) § 63.6660(c)	
NUTY-Q7215	EU	R111-1	PM (OPACITY)	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(4)(A)	Visible emissions from a process gas flare shall not be permitted for more than five minutes in any two-hour period, except for upset emissions as provided in §101.11(a).	§ 111.111(a)(4)(A)(i) § 111.111(a)(4)(A)(ii)	§ 111.111(a)(4)(A)(ii)	None
NUTY-Q7215	CD	60A-1	OPACITY	40 CFR Part 60, Subpart A	§ 60.18(b) § 60.18(c)(1) § 60.18(c)(2) § 60.18(c)(3)(ii) § 60.18(c)(4)(i) § 60.18(c)(6) § 60.18(e)	Flares shall comply with paragraphs (c)-(f) of § 60.18.	§ 60.18(d) § 60.18(f)(1) § 60.18(f)(2) § 60.18(f)(3) § 60.18(f)(4)	None	None
PRO-CPV	PRO	R5160	VOC	30 TAC Chapter 115, Batch Processes	§ 115.167(2) § 115.162(3)	Combined vents from a batch process train or single unit operations that meet the criteria in § 115.162(2)(A) or (B), respectively, are exempt from the requirements of this division, except for §§115.161(b) and (C), 115.164, and 115.166(2).	§ 115.164(1) § 115.164(2) § 115.166 [G]§ 115.166(2)	§ 115.166 [G]§ 115.166(2)	None
PRO-CPV	PRO	63FFFF	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2440(a) § 63.2450(a) § 63.2450(l) § 63.2460(c)(1)	This subpart applies to each miscellaneous organic chemical manufacturing affected source.	§ 63.2445(d) § 63.2445(e) § 63.2445(f) § 63.2450(g)	§ 63.2445(f) § 63.2525 § 63.2525(a) [G]§ 63.2525(b)	§ 63.2435(d) § 63.2445(c) § 63.2450(g)(5) § 63.2450(m)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.2465(a) § 63.2465(a)-Table 3.1.a § 63.2465(b) § 63.2465(c) § 63.2465(c)(2) § 63.2465(c)(3)		§ 63.2450(g)(1) § 63.2450(g)(2) [G]§ 63.2450(g)(3) § 63.2450(g)(4) § 63.2460(c)(2)(v) § 63.2465(c)(1)	§ 63.2525(c) § 63.2525(f) § 63.2525(j)	§ 63.2450(m)(1) § 63.2450(m)(2) § 63.2450(q) § 63.2460(c)(1) § 63.2515(a) § 63.2515(b)(2) § 63.2515(c) § 63.2520(a) [G]§ 63.2520(b) [G]§ 63.2520(c) [G]§ 63.2520(d) § 63.2520(e) § 63.2520(e)(1) [G]§ 63.2520(e)(10) § 63.2520(e)(2) § 63.2520(e)(3) § 63.2520(e)(4) § 63.2520(e)(5) § 63.2520(e)(5)(i) [G]§ 63.2520(e)(5)(ii) [G]§ 63.2520(e)(5)(iii) § 63.2520(e)(6) § 63.2520(e)(7) § 63.2520(e)(9)
PRO-MODLINE1 &2	PRO	R5160	VOC	30 TAC Chapter 115, Batch Processes	§ 115.162(1) § 115.162(1)(A) § 115.162(1)(B) § 115.162(1)(C) § 115.162(2) § 115.162(2)(B) § 115.162(2)(D) § 115.162(2)(E)	The mass emission rate from individual process vents or for process vent streams in aggregate within a batch process shall be reduced by 90% if the actual average flow rate value is below the flow rate value calculated using the applicable RACT equation.	§ 115.164(1) § 115.164(2) § 115.165(1) § 115.165(2) [G]§ 115.165(2)(A) [G]§ 115.165(2)(B) § 115.166 § 115.166(1) § 115.166(1)(A) § 115.166(1)(A)(i) [G]§ 115.166(2) § 115.166(3) § 115.166(3)(A)	§ 115.166 § 115.166(1) § 115.166(1)(A) § 115.166(1)(A)(i) [G]§ 115.166(2) § 115.166(3) § 115.166(3)(A)	None
PRO-	PRO	63JJJ	112(B)	40 CFR Part 63,	§ 63.1310(b)	A TPPU that is part of an	None	§ 63.1310(b)(1)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
MODLINE1 &2			HAPS	Subpart JJJ	§ 63.1310(b)(2)	affected source, but does not use or manufacture any organic HAP shall comply with the requirements of either 63.1310(b)(1) or (b)(2).		§ 63.1335(a) § 63.1335(a)(1)	
PRO-MODLINE3	PRO	R5160	VOC	30 TAC Chapter 115, Batch Processes	§ 115.162(1) § 115.162(1)(A) § 115.162(1)(B) § 115.162(1)(C) § 115.162(2) § 115.162(2)(B) § 115.162(2)(D) § 115.162(2)(E)	The mass emission rate from individual process vents or for process vent streams in aggregate within a batch process shall be reduced by 90% if the actual average flow rate value is below the flow rate value calculated using the applicable RACT equation.	§ 115.164(1) § 115.164(2) § 115.165(1) § 115.165(2) [G]§ 115.165(2)(A) [G]§ 115.165(2)(B) § 115.166 § 115.166(1) § 115.166(1)(A) § 115.166(1)(A)(i) [G]§ 115.166(2) § 115.166(3) § 115.166(3)(A)	§ 115.166 § 115.166(1) § 115.166(1)(A) § 115.166(1)(A)(i) [G]§ 115.166(2) § 115.166(3) § 115.166(3)(A)	None
PRO-MODLINE3	PRO	63FFFF	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2440(a) § 63.2450(a) § 63.2450(l) § 63.2460(c)(1) § 63.2465(a) § 63.2465(a)-Table 3.1.a § 63.2465(b) § 63.2465(c) § 63.2465(c)(2) § 63.2465(c)(3)	This subpart applies to each miscellaneous organic chemical manufacturing affected source.	§ 63.2445(d) § 63.2445(e) § 63.2445(f) § 63.2450(g) § 63.2450(g)(1) § 63.2450(g)(2) [G]§ 63.2450(g)(3) § 63.2450(g)(4) § 63.2460(c)(2)(v) § 63.2465(c)(1)	§ 63.2445(f) § 63.2525 § 63.2525(a) [G]§ 63.2525(b) § 63.2525(c) § 63.2525(f) § 63.2525(j)	§ 63.2435(d) § 63.2445(c) § 63.2450(g)(5) § 63.2450(m) § 63.2450(m)(1) § 63.2450(m)(2) § 63.2450(q) § 63.2460(c)(1) § 63.2515(a) § 63.2515(b)(1) § 63.2515(c) § 63.2520(a) [G]§ 63.2520(b) [G]§ 63.2520(c) [G]§ 63.2520(d) § 63.2520(e) § 63.2520(e)(1) [G]§ 63.2520(e)(10) § 63.2520(e)(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
									§ 63.2520(e)(3) § 63.2520(e)(4) § 63.2520(e)(5) § 63.2520(e)(5)(i) [G]§ 63.2520(e)(5)(ii) [G]§ 63.2520(e)(5)(iii) § 63.2520(e)(6) § 63.2520(e)(7) § 63.2520(e)(9)
PRO-MSA	PRO	63FFFF	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2440(a) § 63.2450(a) § 63.2450(l) § 63.2460(c)(1) § 63.2465(a) § 63.2465(a)-Table 3.1.a § 63.2465(b) § 63.2465(c) § 63.2465(c)(2) § 63.2465(c)(3)	This subpart applies to each miscellaneous organic chemical manufacturing affected source.	§ 63.2445(d) § 63.2445(e) § 63.2445(f) § 63.2450(g) § 63.2450(g)(1) § 63.2450(g)(2) [G]§ 63.2450(g)(3) § 63.2450(g)(4) § 63.2460(c)(2)(v) § 63.2465(c)(1)	§ 63.2445(f) § 63.2525 § 63.2525(a) [G]§ 63.2525(b) § 63.2525(c) § 63.2525(f) § 63.2525(j)	§ 63.2435(d) § 63.2445(c) § 63.2450(g)(5) § 63.2450(m) § 63.2450(m)(1) § 63.2450(m)(2) § 63.2450(q) § 63.2460(c)(1) § 63.2515(a) § 63.2515(b)(2) § 63.2515(c) § 63.2520(a) [G]§ 63.2520(b) [G]§ 63.2520(c) [G]§ 63.2520(d) § 63.2520(e) § 63.2520(e)(1) [G]§ 63.2520(e)(10) § 63.2520(e)(2) § 63.2520(e)(3) § 63.2520(e)(4) § 63.2520(e)(5) § 63.2520(e)(5)(i) [G]§ 63.2520(e)(5)(ii) [G]§ 63.2520(e)(5)(iii) § 63.2520(e)(6) § 63.2520(e)(7) § 63.2520(e)(9)
REGVLOAD	EU	R5211	VOC	30 TAC Chapter	§ 115.217(a)(1)	Vapor pressure (at land-	§ 115.214(a)(1)(A)	§ 115.216	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				115, Loading and Unloading of VOC	§ 115.212(a)(2) § 115.214(a)(1)(B) § 115.214(a)(1)(D) § 115.214(a)(1)(D)(i)	based operations). All land-based loading and unloading of VOC with a true vapor pressure less than 0.5 psia is exempt from the requirements of this division, except as specified.	§ 115.214(a)(1)(A)(i) § 115.215 § 115.215(4)	§ 115.216(2) § 115.216(3)(B)	

Additional Monitoring Requirements

Compliance Assurance Monitoring Summary 157

Periodic Monitoring Summary.....163

CAM Summary

Unit/Group/Process Information	
ID No.: APIZ-7402	
Control Device ID No.: APIZ-7402	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121
Pollutant: VOC	Main Standard: § 115.122(a)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: once per day	
Averaging Period: n/a*	
Deviation Limit: A combustion temperature of less than 1300 degrees Fahrenheit shall be considered and reported as a deviation.	
<p>CAM Text: The monitoring device should be installed in the combustion chamber or immediately downstream of the combustion chamber. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following:</p> <ul style="list-style-type: none"> ± 0.75% of the temperature being measured expressed in degrees Celsius; or ± 2.5 degrees Celsius. 	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

CAM Summary

Unit/Group/Process Information	
ID No.: APIZ-7402VNT	
Control Device ID No.: APIZ-7402VNT	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121
Pollutant: VOC	Main Standard: § 115.122(a)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: once per day	
Averaging Period: n/a*	
Deviation Limit: A combustion temperature of less than 1300 degrees Fahrenheit shall be considered and reported as a deviation.	
<p>CAM Text: The monitoring device should be installed in the combustion chamber or immediately downstream of the combustion chamber. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following:</p> <ul style="list-style-type: none"> ± 0.75% of the temperature being measured expressed in degrees Celsius; or ± 2.5 degrees Celsius. 	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

CAM Summary

Unit/Group/Process Information	
ID No.: MODZ-1607S	
Control Device ID No.: MODZ-1607S	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121
Pollutant: VOC	Main Standard: § 115.122(a)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: once per day	
Averaging Period: n/a*	
Deviation Limit: A combustion temperature of less than 1300 degrees Fahrenheit shall be considered and reported as a deviation.	
<p>CAM Text: The monitoring device should be installed in the combustion chamber or immediately downstream of the combustion chamber. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following:</p> <ul style="list-style-type: none"> ± 0.75% of the temperature being measured expressed in degrees Celsius; or ± 2.5 degrees Celsius. 	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

CAM Summary

Unit/Group/Process Information	
ID No.: MODZ-1608	
Control Device ID No.: MODZ-1608	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121
Pollutant: VOC	Main Standard: § 115.122(a)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: once per day	
Averaging Period: n/a*	
Deviation Limit: A combustion temperature of less than 1300 degrees Fahrenheit shall be considered and reported as a deviation.	
<p>CAM Text: The monitoring device should be installed in the combustion chamber or immediately downstream of the combustion chamber. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following:</p> <ul style="list-style-type: none"> ± 0.75% of the temperature being measured expressed in degrees Celsius; or ± 2.5 degrees Celsius. 	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

CAM Summary

Unit/Group/Process Information	
ID No.: MODZ-1608VNT	
Control Device ID No.: MODZ-1608	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121
Pollutant: VOC	Main Standard: § 115.122(a)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: once per day	
Averaging Period: n/a*	
Deviation Limit: When waste gas is being combusted, a combustion temperature of less than 1400 degrees Fahrenheit shall be considered and reported as a deviation.	
<p>CAM Text: The monitoring device should be installed in the combustion chamber or immediately downstream of the combustion chamber. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following:</p> <ul style="list-style-type: none"> ± 0.75% of the temperature being measured expressed in degrees Celsius; or ± 2.5 degrees Celsius. 	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

CAM Summary

Unit/Group/Process Information	
ID No.: MSAZ-S421VNT	
Control Device ID No.: MSAZ-S421	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121
Pollutant: VOC	Main Standard: § 115.122(a)(1)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: n/a	
Deviation Limit: A combustion temperature of less than 1400 degrees Fahrenheit shall be considered and reported as a deviation.	
<p>CAM Text: Monitor the presence of a flare pilot flame using a thermocouple or other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. Maintain records of alarm events and duration of alarm events. Each monitoring device shall be accurate to within manufacturer's recommendations. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications or other written procedures that provide an adequate assurance that the device is calibrated accurately.</p>	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: MODT-130	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Structural Integrity of the Pipe	
Minimum Frequency: Emptied and degassed	
Averaging Period: n/a	
Deviation Limit: It shall be considered and reported as a deviation if the repairs are not completed prior to refilling the storage vessel.	
Periodic Monitoring Text: Inspect to determine the structural integrity of the fill pipe and record each time the storage vessel is emptied and degassed to ensure that it continues to meet the specifications in the above requirement. If the structural integrity of the fill pipe is in question, repairs shall be made before the storage vessel is refilled. It shall be considered and reported as a deviation if the repairs are not completed prior to refilling the storage vessel.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: MODT-130	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Record of Tank Construction Specifications	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: It shall be considered and reported as a deviation any time the liquid level falls below the fill pipe level.	
Periodic Monitoring Text: Keep a record of tank construction specifications (e.g. engineering drawings) that show a fill pipe that extends from the top of a tank to have a maximum clearance of six inches (15.2 centimeters) from the bottom or, when the tank is loaded from the side, a discharge opening entirely submerged when the pipe used to withdraw liquid from the tank can no longer withdraw liquid in normal operation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: MODT-140	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart Kb	SOP Index No.: 60KB
Pollutant: VOC	Main Standard: [G]§ 60.112b(a)(3)
Monitoring Information	
Indicator: VOC Concentration	
Minimum Frequency: Annually	
Averaging Period: n/a*	
Deviation Limit: If VOC concentration is greater than or equal to 500 ppmv it shall be considered and reported as a deviation.	
<p>Periodic Monitoring Text: Measure and record the VOC concentration using a portable analyzer to monitor VOC concentration around the immediate area of the compartment in accordance with 40 CFR Part 60, Appendix A, Method 21. Each potential leak interface (i.e., a location where organic vapor leakage could occur) on the cover and associated closure devices shall be checked. Potential leak interfaces that are associated with covers and closure devices include, but are not limited to: the interface of the cover and its foundation mounting; the periphery of any opening on the cover and its associated closure device; and the sealing seat interface on a spring-loaded pressure relief valve. The owner or operator may choose to adjust the detection instrument readings for the background organic concentration level.</p> <p>The monitoring instrumentation shall be maintained and operated in accordance with manufacturer's specifications or other written procedures.</p> <p>Any monitoring data greater than the maximum VOC limit indicated in the Deviation Limit above shall be considered and reported as a deviation as required by § 122.145(2).</p>	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: MODT-140	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart Kb	SOP Index No.: 60KB
Pollutant: VOC	Main Standard: [G]§ 60.112b(a)(3)
Monitoring Information	
Indicator: Visual Inspection	
Minimum Frequency: Monthly	
Averaging Period: n/a	
Deviation Limit: Presence of cracks, holes, gaps, loose connections, or broken or missing covers or other closure devices that could result in air emissions shall be considered and reported as a deviation.	
<p>Periodic Monitoring Text: The oil-water separator and its closure devices shall be visually inspected by the owner operator to check for defects that could result in air emissions. Defects include, but are not limited to, visible cracks, holes, or gaps in the roof sections or between the roof and the separator wall; broken, cracked, or otherwise damaged seals or gaskets on closure devices; and broken or missing hatches, access covers, caps, or other closure devices.</p> <p>Any monitoring data that indicates a gap or crack in a sealed opening shall be considered and reported as a deviation as required by § 122.145(2).</p>	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: MSAT-S106	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Structural Integrity of the Pipe	
Minimum Frequency: Emptied and degassed	
Averaging Period: n/a	
Deviation Limit: It shall be considered and reported as a deviation if the repairs are not completed prior to refilling the storage vessel.	
Periodic Monitoring Text: Inspect to determine the structural integrity of the fill pipe and record each time the storage vessel is emptied and degassed to ensure that it continues to meet the specifications in the above requirement. If the structural integrity of the fill pipe is in question, repairs shall be made before the storage vessel is refilled. It shall be considered and reported as a deviation if the repairs are not completed prior to refilling the storage vessel.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: MSAT-S106	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Record of Tank Construction Specifications	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: It shall be considered and reported as a deviation any time the liquid level falls below the fill pipe level.	
Periodic Monitoring Text: Keep a record of tank construction specifications (e.g. engineering drawings) that show a fill pipe that extends from the top of a tank to have a maximum clearance of six inches (15.2 centimeters) from the bottom or, when the tank is loaded from the side, a discharge opening entirely submerged when the pipe used to withdraw liquid from the tank can no longer withdraw liquid in normal operation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: MSAT-S107	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Structural Integrity of the Pipe	
Minimum Frequency: Emptied and degassed	
Averaging Period: n/a	
Deviation Limit: It shall be considered and reported as a deviation if the repairs are not completed prior to refilling the storage vessel.	
Periodic Monitoring Text: Inspect to determine the structural integrity of the fill pipe and record each time the storage vessel is emptied and degassed to ensure that it continues to meet the specifications in the above requirement. If the structural integrity of the fill pipe is in question, repairs shall be made before the storage vessel is refilled. It shall be considered and reported as a deviation if the repairs are not completed prior to refilling the storage vessel.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: MSAT-S107	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Record of Tank Construction Specifications	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: It shall be considered and reported as a deviation any time the liquid level falls below the fill pipe level.	
<p>Periodic Monitoring Text: Keep a record of tank construction specifications (e.g. engineering drawings) that show a fill pipe that extends from the top of a tank to have a maximum clearance of six inches (15.2 centimeters) from the bottom or, when the tank is loaded from the side, a discharge opening entirely submerged when the pipe used to withdraw liquid from the tank can no longer withdraw liquid in normal operation.</p>	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: MSAT-S503	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Structural Integrity of the Pipe	
Minimum Frequency: Emptied and degassed	
Averaging Period: n/a	
Deviation Limit: It shall be considered and reported as a deviation if the repairs are not completed prior to refilling the storage vessel.	
Periodic Monitoring Text: Inspect to determine the structural integrity of the fill pipe and record each time the storage vessel is emptied and degassed to ensure that it continues to meet the specifications in the above requirement. If the structural integrity of the fill pipe is in question, repairs shall be made before the storage vessel is refilled. It shall be considered and reported as a deviation if the repairs are not completed prior to refilling the storage vessel.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: MSAT-S503	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Record of Tank Construction Specifications	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: It shall be considered and reported as a deviation any time the liquid level falls below the fill pipe level.	
Periodic Monitoring Text: Keep a record of tank construction specifications (e.g. engineering drawings) that show a fill pipe that extends from the top of a tank to have a maximum clearance of six inches (15.2 centimeters) from the bottom or, when the tank is loaded from the side, a discharge opening entirely submerged when the pipe used to withdraw liquid from the tank can no longer withdraw liquid in normal operation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: MSAT-S713	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Structural Integrity of the Pipe	
Minimum Frequency: Emptied and degassed	
Averaging Period: n/a	
Deviation Limit: It shall be considered and reported as a deviation if the repairs are not completed prior to refilling the storage vessel.	
Periodic Monitoring Text: Inspect to determine the structural integrity of the fill pipe and record each time the storage vessel is emptied and degassed to ensure that it continues to meet the specifications in the above requirement. If the structural integrity of the fill pipe is in question, repairs shall be made before the storage vessel is refilled. It shall be considered and reported as a deviation if the repairs are not completed prior to refilling the storage vessel.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: MSAT-S713	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Record of Tank Construction Specifications	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: It shall be considered and reported as a deviation any time the liquid level falls below the fill pipe level.	
Periodic Monitoring Text: Keep a record of tank construction specifications (e.g. engineering drawings) that show a fill pipe that extends from the top of a tank to have a maximum clearance of six inches (15.2 centimeters) from the bottom or, when the tank is loaded from the side, a discharge opening entirely submerged when the pipe used to withdraw liquid from the tank can no longer withdraw liquid in normal operation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: MSAZ-S419	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111
Pollutant: PM (OPACITY)	Main Standard: § 111.111(a)(1)(A)
Monitoring Information	
Indicator: Visible Emissions	
Minimum Frequency: Once per week	
Averaging Period: n/a	
Deviation Limit: An opacity reading above 30% shall be considered and reported as a deviation.	
<p>Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor.</p> <p>If visible emissions are observed, the permit holder shall report a deviation. As an alternative, the permit holder may determine the opacity consistent with Test Method 9, as soon as practicable, but no later than 24 hours after observing visible emissions.</p> <p>If the result of the Test Method 9 is an opacity above the corresponding opacity limit, the permit holder shall report a deviation.</p>	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: NUT1T-4201	
Control Device ID No.: Y-Q7215	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart Kb	SOP Index No.: 60KB-001
Pollutant: VOC	Main Standard: [G]§ 60.112b(a)(3)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Once per hour	
Averaging Period: n/a	
Deviation Limit: An absence of a pilot flame shall be considered and reported as a deviation.	
<p>Periodic Monitoring Text: Measure and record the presence of the pilot flame or maintain records of alarm events and duration of alarm events. The presence of a flare pilot flame shall be monitored using a thermocouple or any other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. The monitoring instrumentation shall be maintained, calibrated and operated in accordance with manufacturer's specifications or other written procedures. Any monitoring data which indicates the lack of a pilot flame shall be considered and reported as a deviation.</p>	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: NUT1T-4207	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-2
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Structural Integrity of the Pipe	
Minimum Frequency: Emptied and degassed	
Averaging Period: n/a	
Deviation Limit: It shall be considered and reported as a deviation if the repairs are not completed prior to refilling the storage vessel.	
Periodic Monitoring Text: Inspect to determine the structural integrity of the fill pipe and record each time the storage vessel is emptied and degassed to ensure that it continues to meet the specifications in the above requirement. If the structural integrity of the fill pipe is in question, repairs shall be made before the storage vessel is refilled. It shall be considered and reported as a deviation if the repairs are not completed prior to refilling the storage vessel.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: NUT1T-4207	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-2
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Record of Tank Construction Specifications	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: It shall be considered and reported as a deviation any time the liquid level falls below the fill pipe level.	
Periodic Monitoring Text: Keep a record of tank construction specifications (e.g. engineering drawings) that show a fill pipe that extends from the top of a tank to have a maximum clearance of six inches (15.2 centimeters) from the bottom or, when the tank is loaded from the side, a discharge opening entirely submerged when the pipe used to withdraw liquid from the tank can no longer withdraw liquid in normal operation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: NUT1T-4211	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-2
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Structural Integrity of the Pipe	
Minimum Frequency: Emptied and degassed	
Averaging Period: n/a	
Deviation Limit: It shall be considered and reported as a deviation if the repairs are not completed prior to refilling the storage vessel.	
Periodic Monitoring Text: Inspect to determine the structural integrity of the fill pipe and record each time the storage vessel is emptied and degassed to ensure that it continues to meet the specifications in the above requirement. If the structural integrity of the fill pipe is in question, repairs shall be made before the storage vessel is refilled. It shall be considered and reported as a deviation if the repairs are not completed prior to refilling the storage vessel.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: NUT1T-4211	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-2
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Record of Tank Construction Specifications	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: It shall be considered and reported as a deviation any time the liquid level falls below the fill pipe level.	
Periodic Monitoring Text: Keep a record of tank construction specifications (e.g. engineering drawings) that show a fill pipe that extends from the top of a tank to have a maximum clearance of six inches (15.2 centimeters) from the bottom or, when the tank is loaded from the side, a discharge opening entirely submerged when the pipe used to withdraw liquid from the tank can no longer withdraw liquid in normal operation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: NUT1T-5058	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-2
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Structural Integrity of the Pipe	
Minimum Frequency: Emptied and degassed	
Averaging Period: n/a	
Deviation Limit: It shall be considered and reported as a deviation if the repairs are not completed prior to refilling the storage vessel.	
Periodic Monitoring Text: Inspect to determine the structural integrity of the fill pipe and record each time the storage vessel is emptied and degassed to ensure that it continues to meet the specifications in the above requirement. If the structural integrity of the fill pipe is in question, repairs shall be made before the storage vessel is refilled. It shall be considered and reported as a deviation if the repairs are not completed prior to refilling the storage vessel.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: NUT1T-5058	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-2
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Record of Tank Construction Specifications	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: It shall be considered and reported as a deviation any time the liquid level falls below the fill pipe level.	
Periodic Monitoring Text: Keep a record of tank construction specifications (e.g. engineering drawings) that show a fill pipe that extends from the top of a tank to have a maximum clearance of six inches (15.2 centimeters) from the bottom or, when the tank is loaded from the side, a discharge opening entirely submerged when the pipe used to withdraw liquid from the tank can no longer withdraw liquid in normal operation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: NUT1T-5103	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-2
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Structural Integrity of the Pipe	
Minimum Frequency: Emptied and degassed	
Averaging Period: n/a	
Deviation Limit: It shall be considered and reported as a deviation if the repairs are not completed prior to refilling the storage vessel.	
Periodic Monitoring Text: Inspect to determine the structural integrity of the fill pipe and record each time the storage vessel is emptied and degassed to ensure that it continues to meet the specifications in the above requirement. If the structural integrity of the fill pipe is in question, repairs shall be made before the storage vessel is refilled. It shall be considered and reported as a deviation if the repairs are not completed prior to refilling the storage vessel.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: NUT1T-5103	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-2
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Record of Tank Construction Specifications	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: It shall be considered and reported as a deviation any time the liquid level falls below the fill pipe level.	
Periodic Monitoring Text: Keep a record of tank construction specifications (e.g. engineering drawings) that show a fill pipe that extends from the top of a tank to have a maximum clearance of six inches (15.2 centimeters) from the bottom or, when the tank is loaded from the side, a discharge opening entirely submerged when the pipe used to withdraw liquid from the tank can no longer withdraw liquid in normal operation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: NUT1T-5104	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-2
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Structural Integrity of the Pipe	
Minimum Frequency: Emptied and degassed	
Averaging Period: n/a	
Deviation Limit: It shall be considered and reported as a deviation if the repairs are not completed prior to refilling the storage vessel.	
Periodic Monitoring Text: Inspect to determine the structural integrity of the fill pipe and record each time the storage vessel is emptied and degassed to ensure that it continues to meet the specifications in the above requirement. If the structural integrity of the fill pipe is in question, repairs shall be made before the storage vessel is refilled. It shall be considered and reported as a deviation if the repairs are not completed prior to refilling the storage vessel.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: NUT1T-5104	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-2
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Record of Tank Construction Specifications	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: It shall be considered and reported as a deviation any time the liquid level falls below the fill pipe level.	
Periodic Monitoring Text: Keep a record of tank construction specifications (e.g. engineering drawings) that show a fill pipe that extends from the top of a tank to have a maximum clearance of six inches (15.2 centimeters) from the bottom or, when the tank is loaded from the side, a discharge opening entirely submerged when the pipe used to withdraw liquid from the tank can no longer withdraw liquid in normal operation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: NUT1T-5110	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-2
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Structural Integrity of the Pipe	
Minimum Frequency: Emptied and degassed	
Averaging Period: n/a	
Deviation Limit: It shall be considered and reported as a deviation if the repairs are not completed prior to refilling the storage vessel.	
Periodic Monitoring Text: Inspect to determine the structural integrity of the fill pipe and record each time the storage vessel is emptied and degassed to ensure that it continues to meet the specifications in the above requirement. If the structural integrity of the fill pipe is in question, repairs shall be made before the storage vessel is refilled. It shall be considered and reported as a deviation if the repairs are not completed prior to refilling the storage vessel.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: NUT1T-5110	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-2
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Record of Tank Construction Specifications	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: It shall be considered and reported as a deviation any time the liquid level falls below the fill pipe level.	
Periodic Monitoring Text: Keep a record of tank construction specifications (e.g. engineering drawings) that show a fill pipe that extends from the top of a tank to have a maximum clearance of six inches (15.2 centimeters) from the bottom or, when the tank is loaded from the side, a discharge opening entirely submerged when the pipe used to withdraw liquid from the tank can no longer withdraw liquid in normal operation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: NUT1T-5113	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-2
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Structural Integrity of the Pipe	
Minimum Frequency: Emptied and degassed	
Averaging Period: n/a	
Deviation Limit: It shall be considered and reported as a deviation if the repairs are not completed prior to refilling the storage vessel.	
Periodic Monitoring Text: Inspect to determine the structural integrity of the fill pipe and record each time the storage vessel is emptied and degassed to ensure that it continues to meet the specifications in the above requirement. If the structural integrity of the fill pipe is in question, repairs shall be made before the storage vessel is refilled. It shall be considered and reported as a deviation if the repairs are not completed prior to refilling the storage vessel.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: NUT1T-5113	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-2
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Record of Tank Construction Specifications	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: It shall be considered and reported as a deviation any time the liquid level falls below the fill pipe level.	
Periodic Monitoring Text: Keep a record of tank construction specifications (e.g. engineering drawings) that show a fill pipe that extends from the top of a tank to have a maximum clearance of six inches (15.2 centimeters) from the bottom or, when the tank is loaded from the side, a discharge opening entirely submerged when the pipe used to withdraw liquid from the tank can no longer withdraw liquid in normal operation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: NUT1T-5117	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-2
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Structural Integrity of the Pipe	
Minimum Frequency: Emptied and degassed	
Averaging Period: n/a	
Deviation Limit: It shall be considered and reported as a deviation if the repairs are not completed prior to refilling the storage vessel.	
Periodic Monitoring Text: Inspect to determine the structural integrity of the fill pipe and record each time the storage vessel is emptied and degassed to ensure that it continues to meet the specifications in the above requirement. If the structural integrity of the fill pipe is in question, repairs shall be made before the storage vessel is refilled. It shall be considered and reported as a deviation if the repairs are not completed prior to refilling the storage vessel.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: NUT1T-5117	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-2
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Record of Tank Construction Specifications	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: It shall be considered and reported as a deviation any time the liquid level falls below the fill pipe level.	
Periodic Monitoring Text: Keep a record of tank construction specifications (e.g. engineering drawings) that show a fill pipe that extends from the top of a tank to have a maximum clearance of six inches (15.2 centimeters) from the bottom or, when the tank is loaded from the side, a discharge opening entirely submerged when the pipe used to withdraw liquid from the tank can no longer withdraw liquid in normal operation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: NUT1T-5200	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-2
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Structural Integrity of the Pipe	
Minimum Frequency: Emptied and degassed	
Averaging Period: n/a	
Deviation Limit: It shall be considered and reported as a deviation if the repairs are not completed prior to refilling the storage vessel.	
Periodic Monitoring Text: Inspect to determine the structural integrity of the fill pipe and record each time the storage vessel is emptied and degassed to ensure that it continues to meet the specifications in the above requirement. If the structural integrity of the fill pipe is in question, repairs shall be made before the storage vessel is refilled. It shall be considered and reported as a deviation if the repairs are not completed prior to refilling the storage vessel.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: NUT1T-5200	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-2
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Record of Tank Construction Specifications	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: It shall be considered and reported as a deviation any time the liquid level falls below the fill pipe level.	
Periodic Monitoring Text: Keep a record of tank construction specifications (e.g. engineering drawings) that show a fill pipe that extends from the top of a tank to have a maximum clearance of six inches (15.2 centimeters) from the bottom or, when the tank is loaded from the side, a discharge opening entirely submerged when the pipe used to withdraw liquid from the tank can no longer withdraw liquid in normal operation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: NUT1T-5205	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-2
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Structural Integrity of the Pipe	
Minimum Frequency: Emptied and degassed	
Averaging Period: n/a	
Deviation Limit: It shall be considered and reported as a deviation if the repairs are not completed prior to refilling the storage vessel.	
Periodic Monitoring Text: Inspect to determine the structural integrity of the fill pipe and record each time the storage vessel is emptied and degassed to ensure that it continues to meet the specifications in the above requirement. If the structural integrity of the fill pipe is in question, repairs shall be made before the storage vessel is refilled. It shall be considered and reported as a deviation if the repairs are not completed prior to refilling the storage vessel.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: NUT1T-5205	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-2
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Record of Tank Construction Specifications	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: It shall be considered and reported as a deviation any time the liquid level falls below the fill pipe level.	
Periodic Monitoring Text: Keep a record of tank construction specifications (e.g. engineering drawings) that show a fill pipe that extends from the top of a tank to have a maximum clearance of six inches (15.2 centimeters) from the bottom or, when the tank is loaded from the side, a discharge opening entirely submerged when the pipe used to withdraw liquid from the tank can no longer withdraw liquid in normal operation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: NUT1T-5210	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-2
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Structural Integrity of the Pipe	
Minimum Frequency: Emptied and degassed	
Averaging Period: n/a	
Deviation Limit: It shall be considered and reported as a deviation if the repairs are not completed prior to refilling the storage vessel.	
Periodic Monitoring Text: Inspect to determine the structural integrity of the fill pipe and record each time the storage vessel is emptied and degassed to ensure that it continues to meet the specifications in the above requirement. If the structural integrity of the fill pipe is in question, repairs shall be made before the storage vessel is refilled. It shall be considered and reported as a deviation if the repairs are not completed prior to refilling the storage vessel.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: NUT1T-5210	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-2
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Record of Tank Construction Specifications	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: It shall be considered and reported as a deviation any time the liquid level falls below the fill pipe level.	
Periodic Monitoring Text: Keep a record of tank construction specifications (e.g. engineering drawings) that show a fill pipe that extends from the top of a tank to have a maximum clearance of six inches (15.2 centimeters) from the bottom or, when the tank is loaded from the side, a discharge opening entirely submerged when the pipe used to withdraw liquid from the tank can no longer withdraw liquid in normal operation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: NUT1T-5308	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-2
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Structural Integrity of the Pipe	
Minimum Frequency: Emptied and degassed	
Averaging Period: n/a	
Deviation Limit: It shall be considered and reported as a deviation if the repairs are not completed prior to refilling the storage vessel.	
Periodic Monitoring Text: Inspect to determine the structural integrity of the fill pipe and record each time the storage vessel is emptied and degassed to ensure that it continues to meet the specifications in the above requirement. If the structural integrity of the fill pipe is in question, repairs shall be made before the storage vessel is refilled. It shall be considered and reported as a deviation if the repairs are not completed prior to refilling the storage vessel.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: NUT1T-5308	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-2
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Record of Tank Construction Specifications	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: It shall be considered and reported as a deviation any time the liquid level falls below the fill pipe level.	
Periodic Monitoring Text: Keep a record of tank construction specifications (e.g. engineering drawings) that show a fill pipe that extends from the top of a tank to have a maximum clearance of six inches (15.2 centimeters) from the bottom or, when the tank is loaded from the side, a discharge opening entirely submerged when the pipe used to withdraw liquid from the tank can no longer withdraw liquid in normal operation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: NUT1T-5311	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-2
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Structural Integrity of the Pipe	
Minimum Frequency: Emptied and degassed	
Averaging Period: n/a	
Deviation Limit: It shall be considered and reported as a deviation if the repairs are not completed prior to refilling the storage vessel.	
Periodic Monitoring Text: Inspect to determine the structural integrity of the fill pipe and record each time the storage vessel is emptied and degassed to ensure that it continues to meet the specifications in the above requirement. If the structural integrity of the fill pipe is in question, repairs shall be made before the storage vessel is refilled. It shall be considered and reported as a deviation if the repairs are not completed prior to refilling the storage vessel.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: NUT1T-5311	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-2
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Record of Tank Construction Specifications	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: It shall be considered and reported as a deviation any time the liquid level falls below the fill pipe level.	
Periodic Monitoring Text: Keep a record of tank construction specifications (e.g. engineering drawings) that show a fill pipe that extends from the top of a tank to have a maximum clearance of six inches (15.2 centimeters) from the bottom or, when the tank is loaded from the side, a discharge opening entirely submerged when the pipe used to withdraw liquid from the tank can no longer withdraw liquid in normal operation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: NUT1T-5313	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-2
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Structural Integrity of the Pipe	
Minimum Frequency: Emptied and degassed	
Averaging Period: n/a	
Deviation Limit: It shall be considered and reported as a deviation if the repairs are not completed prior to refilling the storage vessel.	
Periodic Monitoring Text: Inspect to determine the structural integrity of the fill pipe and record each time the storage vessel is emptied and degassed to ensure that it continues to meet the specifications in the above requirement. If the structural integrity of the fill pipe is in question, repairs shall be made before the storage vessel is refilled. It shall be considered and reported as a deviation if the repairs are not completed prior to refilling the storage vessel.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: NUT1T-5313	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-2
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Record of Tank Construction Specifications	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: It shall be considered and reported as a deviation any time the liquid level falls below the fill pipe level.	
Periodic Monitoring Text: Keep a record of tank construction specifications (e.g. engineering drawings) that show a fill pipe that extends from the top of a tank to have a maximum clearance of six inches (15.2 centimeters) from the bottom or, when the tank is loaded from the side, a discharge opening entirely submerged when the pipe used to withdraw liquid from the tank can no longer withdraw liquid in normal operation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: NUT1T-5321	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-2
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Structural Integrity of the Pipe	
Minimum Frequency: Emptied and degassed	
Averaging Period: n/a	
Deviation Limit: It shall be considered and reported as a deviation if the repairs are not completed prior to refilling the storage vessel.	
Periodic Monitoring Text: Inspect to determine the structural integrity of the fill pipe and record each time the storage vessel is emptied and degassed to ensure that it continues to meet the specifications in the above requirement. If the structural integrity of the fill pipe is in question, repairs shall be made before the storage vessel is refilled. It shall be considered and reported as a deviation if the repairs are not completed prior to refilling the storage vessel.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: NUT1T-5321	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-2
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Record of Tank Construction Specifications	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: It shall be considered and reported as a deviation any time the liquid level falls below the fill pipe level.	
Periodic Monitoring Text: Keep a record of tank construction specifications (e.g. engineering drawings) that show a fill pipe that extends from the top of a tank to have a maximum clearance of six inches (15.2 centimeters) from the bottom or, when the tank is loaded from the side, a discharge opening entirely submerged when the pipe used to withdraw liquid from the tank can no longer withdraw liquid in normal operation.	

Permit Shield

Permit Shield208

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
APIV-7101	N/A	40 CFR Part 60, Subpart Kb	Capacity of storage tank unit is less than 75 cubic meters (m3).
APIV-7102	N/A	40 CFR Part 60, Subpart Kb	Capacity of storage tank unit is less than 75 cubic meters (m3).
B-Q9300	N/A	30 TAC Chapter 115, Vent Gas Controls	Vent stream does not contain VOC.
MODSBG-001	N/A	40 CFR Part 63, Subpart ZZZZ	Engine is an existing emergency stationary RICE with a rating above 500 brake HP.
MODT-121	N/A	40 CFR Part 60, Subpart Kb	Capacity of storage tank is greater than or equal to 75 m3 but less than 151 m3 storing a liquid with a maximum true vapor pressure less than 15.0 kPa.
MODT-121	N/A	40 CFR Part 63, Subpart FFFF	Predominant use of the storage vessel is for process unit other than MCPU.
MODT-125	N/A	30 TAC Chapter 115, Storage of VOCs	Vessel capacity is <= 1,000 gals.
MODT-125	N/A	40 CFR Part 60, Subpart Kb	vessel has capacity<= 40m3
MODT-130	N/A	40 CFR Part 60, Subpart Kb	Capacity of storage tank unit is less than 75 cubic meters (m3).
MODT-150	N/A	40 CFR Part 60, Subpart Kb	Capacity of storage tank is greater than or equal to 75 m3 but less than 151 m3 storing a liquid with a maximum true vapor pressure less than 15.0 kPa.

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
MODT-150	N/A	40 CFR Part 63, Subpart FFFF	Storage tank is not an affected source since it is not a tank or other vessel that is used to store liquids that contain organic HAP and/or hydrogen halide and halogen HAP and that has been assigned to an MCPU.
MODT-2121	N/A	40 CFR Part 60, Subpart Kb	Capacity of storage tank is greater than or equal to 75 m ³ but less than 151 m ³ storing a liquid with a maximum true vapor pressure less than 15.0 kPa.
MODT-2121	N/A	40 CFR Part 63, Subpart FFFF	Predominant use of the storage vessel is for process unit other than MCPU.
MODT-2130	N/A	40 CFR Part 60, Subpart Kb	Capacity of storage tank is greater than or equal to 75 m ³ but less than 151 m ³ storing a liquid with a maximum true vapor pressure less than 15.0 kPa.
MODT-2130	N/A	40 CFR Part 63, Subpart FFFF	Storage tank is not an affected source since it is not a tank or other vessel that is used to store liquids that contain organic HAP and/or hydrogen halide and halogen HAP and that has been assigned to an MCPU.
MODT-3107	N/A	40 CFR Part 60, Subpart Kb	Vessel capacity is < 40m ³ .

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
MODV-335	N/A	40 CFR Part 60, Subpart Kb	Vessel has capacity <= 40m ³
MODV-362	N/A	30 TAC Chapter 115, Storage of VOCs	Vessel capacity is < 1,000 gallons.
MODV-362	N/A	40 CFR Part 60, Subpart Kb	Vessel capacity is < 40m ³ .
MODZ-2753	N/A	40 CFR Part 63, Subpart Q	Cooling tower does not operate with chromium-based water treatment chemicals.
MODZ-753	N/A	40 CFR Part 63, Subpart Q	Cooling tower does not operate with chromium-based water treatment chemicals.
MSAT-S106	N/A	40 CFR Part 60, Subpart Kb	Capacity of storage tank unit is less than 75 cubic meters (m ³).
MSAT-S107	N/A	40 CFR Part 60, Subpart Kb	Capacity of storage tank unit is less than 75 cubic meters (m ³).
MSAT-S415	N/A	40 CFR Part 60, Subpart Kb	Capacity of storage tank unit is less than 75 cubic meters (m ³).
MSAT-S503	N/A	40 CFR Part 60, Subpart Kb	Capacity of storage tank unit is less than 75 cubic meters (m ³).
MSAT-S713	N/A	40 CFR Part 60, Subpart Kb	Capacity of storage tank unit is less than 75 cubic meters (m ³).
MSAT-S718	N/A	40 CFR Part 60, Subpart Kb	Capacity of storage tank unit is less than 75 cubic meters (m ³).

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
MSAT-S719	N/A	40 CFR Part 60, Subpart Kb	Capacity of storage tank unit is less than 75 cubic meters (m3).
NUT1T-4207	N/A	40 CFR Part 60, Subpart Kb	Capacity of storage tank unit is less than 75 cubic meters (m3).
NUT1T-4211	N/A	40 CFR Part 60, Subpart Kb	Capacity of storage tank unit is less than 75 cubic meters (m3).
NUT1T-5058	N/A	40 CFR Part 60, Subpart Kb	Capacity of storage tank unit is less than 75 cubic meters (m3).
NUT1T-5103	N/A	40 CFR Part 60, Subpart Kb	Capacity of storage tank unit is less than 75 cubic meters (m3).
NUT1T-5104	N/A	40 CFR Part 60, Subpart Kb	Capacity of storage tank unit is less than 75 cubic meters (m3).
NUT1T-5110	N/A	40 CFR Part 60, Subpart Kb	Capacity of storage tank unit is less than 75 cubic meters (m3).
NUT1T-5113	N/A	40 CFR Part 60, Subpart Kb	Capacity of storage tank unit is less than 75 cubic meters (m3).
NUT1T-5117	N/A	40 CFR Part 60, Subpart Kb	Capacity of storage tank unit is less than 75 cubic meters (m3).
NUT1T-5200	N/A	40 CFR Part 60, Subpart Kb	Capacity of storage tank unit is less than 75 cubic meters (m3).
NUT1T-5205	N/A	40 CFR Part 60, Subpart Kb	Capacity of storage tank unit is less than

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
			75 cubic meters (m3).
NUT1T-5210	N/A	40 CFR Part 60, Subpart Kb	Capacity of storage tank unit is less than 75 cubic meters (m3).
NUT1T-5308	N/A	40 CFR Part 60, Subpart Kb	Capacity of storage tank unit is less than 75 cubic meters (m3).
NUT1T-5311	N/A	40 CFR Part 60, Subpart Kb	Capacity of storage tank unit is less than 75 cubic meters (m3).
NUT1T-5313	N/A	40 CFR Part 60, Subpart Kb	Capacity of storage tank unit is less than 75 cubic meters (m3).
NUT1T-5321	N/A	40 CFR Part 60, Subpart Kb	Capacity of storage tank unit is less than 75 cubic meters (m3).
NUTB-Q2406	N/A	30 TAC Chapter 115, Vent Gas Controls	Vent stream does not contain VOC.
NUTB-Q3307	N/A	30 TAC Chapter 115, Vent Gas Controls	Vent stream does not contain VOC.
NUTB-Q3517	N/A	30 TAC Chapter 115, Vent Gas Controls	Vent stream does not contain VOC.
NUTB-Q3518	N/A	30 TAC Chapter 115, Vent Gas Controls	Vent stream does not contain VOC.
NUTB-Q9300	N/A	30 TAC Chapter 115, Vent Gas Controls	Vent stream does not contain VOC.
NUTF-Q2228	N/A	30 TAC Chapter 115, Vent Gas Controls	Vent stream does not contain VOC.
NUTF-Q4410	N/A	30 TAC Chapter 115, Vent Gas Controls	Vent stream does not contain VOC.
NUTIWW	N/A	30 TAC Chapter 115, Industrial Wastewater	Facility does not meet the requirements of

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
			an affected source as defined in 115.140. The plant is a food supplements facility that is classified under SIC 2023.

New Source Review Authorization References

New Source Review Authorization References215

New Source Review Authorization References by Emission Unit.....217

New Source Review Authorization References

The New Source Review authorizations listed in the table below are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Title 30 TAC Chapter 116 Permits, Special Permits, and Other Authorizations (Other Than Permits By Rule, PSD Permits, or NA Permits) for the Application Area.	
Authorization No.: 38180	Issuance Date: 09/18/2013
Authorization No.: 71768	Issuance Date: 12/05/2014
Authorization No.: 77886	Issuance Date: 05/21/2014
Authorization No.: 80931	Issuance Date: 10/24/2014
Authorization No.: 9092	Issuance Date: 02/10/2015
Permits By Rule (30 TAC Chapter 106) for the Application Area	
Number: 106.124	Version No./Date: 09/04/2000
Number: 106.261	Version No./Date: 03/14/1997
Number: 106.261	Version No./Date: 12/24/1998
Number: 106.261	Version No./Date: 09/04/2000
Number: 106.261	Version No./Date: 11/01/2003
Number: 106.262	Version No./Date: 03/14/1997
Number: 106.262	Version No./Date: 12/24/1998
Number: 106.262	Version No./Date: 09/04/2000
Number: 106.262	Version No./Date: 11/01/2003
Number: 106.263	Version No./Date: 11/01/2001
Number: 106.371	Version No./Date: 09/04/2000
Number: 106.373	Version No./Date: 09/04/2000
Number: 106.393	Version No./Date: 09/04/2000
Number: 106.432	Version No./Date: 03/14/1997
Number: 106.432	Version No./Date: 09/04/2000
Number: 106.433	Version No./Date: 03/14/1997
Number: 106.433	Version No./Date: 09/04/2000
Number: 106.472	Version No./Date: 09/04/2000
Number: 106.473	Version No./Date: 09/04/2000
Number: 106.476	Version No./Date: 09/04/2000

New Source Review Authorization References

The New Source Review authorizations listed in the table below are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Number: 106.478	Version No./Date: 09/04/2000
Number: 106.492	Version No./Date: 09/04/2000
Number: 106.511	Version No./Date: 03/14/1997
Number: 106.511	Version No./Date: 09/04/2000
Number: 106.532	Version No./Date: 09/04/2000
Number: 5	Version No./Date: 09/12/1989
Number: 106	Version No./Date: 09/12/1989
Number: 118	Version No./Date: 09/12/1989

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
APIB-7502	KHM AFTERTREATMENT STACK	106/09/12/1989, 118/09/12/1989
APIST-7519B	PLASMA TREATER DISCHARGE STACK	106.261/12/24/1998, 106.262/11/01/2003
APIV-7101	DD VESSEL	106.478/09/04/2000
APIV-7101LD	DD VESSEL LOADING	106.478/09/04/2000
APIV-7102	AA VESSEL	106.478/09/04/2000
APIV-7102LD	AA VESSEL LOADING	106.478/09/04/2000
APIZ-7402	KHM THERMAL OXIDIZER	38180
APIZ-7402VNT	PROCESS VENT	38180
APIZ-7601	KHM WASTE GAS SCRUBBER STACK	106/09/12/1989, 118/09/12/1989
APIZ-7602	KHM WASTE GAS/DUST STACK	106/09/12/1989, 118/09/12/1989
APIZ-7810	KHM FILM COATING SYSTEM STACK	106.433/03/14/1997
B-Q9300	RM WAREHOUSE BLOWER (W-44037)	106.261/11/01/2003, 106.262/11/01/2003
CPVC-C2710	FLUID BED DRYER SCRUBBER	77886
CPVC-C710	FLUID BED DRYER AND SCRUBBER	77886
CPVC-C710	FLUID BED DRYER AND SCRUBBER	77886
CPVF-C101A	RAW MATERIAL TRANSFER BAG FILTER	77886
CPVF-C102B	RAW MATERIAL TRANSFER BAG FILTER	106.393/09/04/2000
CPVF-C110	SLURRY TANK	77886

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
CPVF-C2101A	RAW MATERIAL TRANSFER BAG FILTER	77886
CPVF-C2102C	STORAGE TANK BAG FILTER	77886
CPVF-C2110	SLURRY TANK FILTER	77886
CPVF-C2601	PRODUCT TRANSFER BAG FILTER	77886
CPVF-C2603	PRODUCT DUST COLLECTOR	77886
CPVF-C601	PRODUCT TRANSFER BAG FILTER	77886
CPVF-C603A	PRODUCT DUST COLLECTOR	77886
CPVF-C603B	PRODUCT DUST COLLECTOR	77886
CPVF-C606A	PRODUCT TRANSFER BAG FILTER	77886
CPVF-C606B	PRODUCT TRANSFER BAG FILTER	77886
CPVN-C508	PRODUCT DUST COLLECTOR	77886
CPVSBG2-812	EMERGENCY GENERATOR	106.511/09/04/2000
CPVSBG-812	EMERGENCY GENERATOR	77886
CPVT-C102A	RAW MATERIAL TRANSFER BAG FILTER	77886
CPVT-C706	GAS ABSORPTION COLLECTOR	77886
CPVV-C2703	CHLORINE SCRUBBER	77886
CPVV-C703A	GAS ABSORPTION COLLECTOR	77886
CPVV-C703B	BACKUP GAS ABSORPTION COLLECTOR	77886

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
MODF-1	LINE NOS. 1 & 2 FUGITIVES	9092
MODF-2B	FUGITIVE EMISSION UNIT	9092
MODF-3A	AREA A TANK FARM FUGITIVES	9092
MODF-3B	AREA B TANK FARM FUGITIVES	9092
MODF-3C	AREA C TANK FARM FUGITIVES	9092
MODF-4	BOILER AREA FUGITIVES	9092
MODF-5	TO & RTO AREA FUGITIVES	9092
MODP-79901-B	FIREWATER PUMP	005/09/12/1989
MODP-79901-C	FIREWATER PUMP	106.511/09/04/2000
MODSBG-001	EMERGENCY GENERATOR	106.511/09/04/2000
MODSBG-002	EMERGENCY GENERATOR	106.511/09/04/2000
MODSBG-003	EMERGENCY GENERATOR	106.511/09/04/2000
MODT-121LD	ST TANK LOADING	9092
MODT-121	ST TANK	9092
MODT-125	M-3 STORAGE TANK	9092
MODT-130	AMS TANK	9092
MODT-130LD	AMS TANK LOADING	9092
MODT-140LD	MMA TANK LOADING	9092

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
MODT-140	MMA TANK	9092
MODT-150LD	MX TANK LOADING	9092
MODT-150	MX TANK	9092
MODT-2121LD	ST TANK LOADING	9092
MODT-2121	ST TANK	9092
MODT-2130	AMS TANK	9092
MODT-2130LD	AMS TANK LOADING	9092
MODT-3107	EM-7 FEED VESSEL	9092
MODT-3336LD	LOADING	9092
MODV-2321	RL RECIEVER	9092
MODV-3336	M-7 FEED VESSEL	9092
MODV-335	M-6 FEED VESSEL	9092
MODV-362	M-4 STORAGE VESSEL	9092
MODV-402	FILTER LATEX RECIEVER	9092
MODWG-1VNT	WASTE GAS FROM REACTORS TO BOILERS FOR USE AS FUEL	9092
MODZ-1607S	REGENERATIVE THERMAL OXIDIZER	9092
MODZ-1607SVNT	PROCESS VENT	9092
MODZ-1608	THERMAL OXIDIZER	9092

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
MODZ-1608VNT	PROCESS VENT	9092
MODZ-1781	#3 BOILER	9092
MODZ-2625	CONTINUOUS VENT	9092
MODZ-2652	MODIFIER LINE 2 AFTER TREATMENT STACK	9092
MODZ-2655	LINE NO. 2 DRYER	9092
MODZ-2656	MODIFIER LINE 2 BAGGING VENT	9092, 106.393/09/04/2000
MODZ-2753	LINE 2 COOLING WATER TOWER	106.371/09/04/2000
MODZ-2781	#1 BOILER	9092
MODZ-3654	MODIFIER LINE 3 DRYER STACK	9092
MODZ-3655	LINE 3 FLUID BED DRYER	9092
MODZ-3656	MODIFIER LINE 3 BAGGING VENT	9092
MODZ-3753	COOLING TOWER	106.371/09/04/2000
MODZ-3780	#4 BOILER	9092
MODZ-3781	#4 BOILER STACK	9092
MODZ-652	LINE NO. 1 AFTER TREATMENT STACK	9092
MODZ-655	MODIFIER LINE 1 DRYER STACK	9092
MODZ-656	MODIFIER LINE 1 BAGGING VENT	9092, 106.393/09/04/2000
MODZ-753	LINE 1 COOLING WATER TOWER	106.371/09/04/2000

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
MODZ-78oS	BOILER NO. 5	9092
MSAP-S623C	FIREWATER PUMP	106.511/09/04/2000
MSAT-S106	RAW MATERIAL STORAGE	80931
MSAT-S107	RAW MATERIAL STORAGE	80931
MSAT-S415	STABILIZER STORAGE	80931
MSAT-S503	RAW MATERIAL STORAGE	80931
MSAT-S713	RAW MATERIAL STORAGE	80931
MSAT-S718	RAW MATERIAL STORAGE	80931
MSAT-S719	RAW MATERIAL STORAGE	80931
MSAY-S601	COOLING TOWER	80931
MSAZ-S419	CHIMNEY	80931
MSAZ-S421	FLARE	80931
MSAZ-S421VNT	PROCESS REACTOR	80931
MSAZ-S421VNT	PROCESS VENT	80931
NUT1P-9013	FIREWATER PUMP	106.511/03/14/1997
NUT1T-4201	STORAGE TANK	106.476/09/04/2000
NUT1T-4207LD	STORAGE TANK LOADING	106.476/09/04/2000
NUT1T-4207	STORAGE TANK	106.476/09/04/2000

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
NUT1T-4211	NW ADDITION TANK	106.476/09/04/2000
NUT1T-5058LD	STORAGE TANK LOADING	106.476/09/04/2000
NUT1T-5058	STORAGE TANK	106.476/09/04/2000
NUT1T-5103	STORAGE TANK	106.476/09/04/2000
NUT1T-5104	STORAGE TANK	106.476/09/04/2000
NUT1T-5110	STORAGE TANK	106.476/09/04/2000
NUT1T-5113	STORAGE TANK	106.476/09/04/2000
NUT1T-5117LD	STORAGE TANK LOADING	106.476/09/04/2000
NUT1T-5117	STORAGE TANK	106.476/09/04/2000
NUT1T-5200	HAZARDOUS WASTE TANK	106.476/09/04/2000
NUT1T-5200LD	HAZARDOUS WASTE TANK LOADING	106.476/09/04/2000
NUT1T-5205	STORAGE TANK	106.476/09/04/2000
NUT1T-5210	SURGE TANK	106.476/09/04/2000
NUT1T-5308	SURGE TANK	106.476/09/04/2000
NUT1T-5311	CHECK TANK A	106.476/09/04/2000
NUT1T-5313	CHECK TANK B	106.476/09/04/2000
NUT1T-5321LD	STORAGE TANK LOADING	106.476/09/04/2000
NUT1T-5321	STORAGE TANK	106.476/09/04/2000

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
NUTB-Q2406	B-2406 FA BLOWER EXHAUST	106.261/11/01/2003, 106.262/11/01/2003
NUTB-Q2425	B-2425 FA VAC BLOWER (F-2407)	106.261/11/01/2003, 106.262/11/01/2003
NUTB-Q3307	B-3307 AA DUST COLLECTOR	106.261/11/01/2003, 106.262/11/01/2003
NUTB-Q3517	FABRIC FILTER PRODUCT LOADING	71768
NUTB-Q3518	FABRIC FILTER PRODUCT LOADING	71768
NUTB-Q3805	PIN MILL VAC. BLOWER EXHAUST	106.261/11/01/2003, 106.262/11/01/2003
NUTB-Q3810	DRYER TRANSFER SYSTEM TO IBC'S	106.261/11/01/2003, 106.262/11/01/2003
NUTB-Q3813	QH DUST COLL. BLOWER EXHAUST (1B3813)	106.261/11/01/2003, 106.262/11/01/2003
NUTB-Q3814	QH VAC. COLL. BLOWER EXHAUST (1B3814)	106.261/11/01/2003, 106.262/11/01/2003
NUTB-Q9300	RM WAREHOUSE BLOWER (W-44037)	106.261/11/01/2003, 106.262/11/01/2003
NUTF-Q2228	FABRIC FILTER	71768
NUTF-Q4410	FABRIC FILTER	71768
NUTIIWW	WASTE WATER	106.532/09/04/2000
NUTLABGEN	LAB BACK-UP GENERATOR	106.511/03/14/1997
NUTY-Q7215	FLARE	106.492/09/04/2000
PRO-CPV	CPV PROCESS	77886
PRO-MODLINE1&2	LINE 1&2 RTO	9092
PRO-MODLINE3	LINE 3 RTO	9092

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
PRO-MSA	MS POLYMERS PLANT	80931
REGVLOAD	LOADING	106.472/09/04/2000, 106.473/09/04/2000

Appendix A

Acronym List 227

Acronym List

The following abbreviations or acronyms may be used in this permit:

ACFM	actual cubic feet per minute
AMOC	alternate means of control
ARP	Acid Rain Program
ASTM	American Society of Testing and Materials
B/PA	Beaumont/Port Arthur (nonattainment area)
CAM	Compliance Assurance Monitoring
CD	control device
COMS	continuous opacity monitoring system
CVS	closed-vent system
D/FW	Dallas/Fort Worth (nonattainment area)
DR	Designated Representative
ELP	El Paso (nonattainment area)
EP	emission point
EPA	U.S. Environmental Protection Agency
EU	emission unit
FCAA Amendments	Federal Clean Air Act Amendments
FOP	federal operating permit
GF	grandfathered
gr/100 scf	grains per 100 standard cubic feet
HAP	hazardous air pollutant
H/G/B	Houston/Galveston/Brazoria (nonattainment area)
H ₂ S	hydrogen sulfide
ID No.	identification number
lb/hr	pound(s) per hour
MMBtu/hr	Million British thermal units per hour
MRRT	monitoring, recordkeeping, reporting, and testing
NA	nonattainment
N/A	not applicable
NADB	National Allowance Data Base
NO _x	nitrogen oxides
NSPS	New Source Performance Standard (40 CFR Part 60)
NSR	New Source Review
ORIS	Office of Regulatory Information Systems
Pb	lead
PBR	Permit By Rule
PM	particulate matter
ppmv	parts per million by volume
PSD	prevention of significant deterioration
RO	Responsible Official
SO ₂	sulfur dioxide
TCEQ	Texas Commission on Environmental Quality
TSP	total suspended particulate
TVP	true vapor pressure
U.S.C.	United States Code
VOC	volatile organic compound