

Bryan W. Shaw, Ph.D., *Chairman*
Buddy Garcia, *Commissioner*
Carlos Rubinstein, *Commissioner*
Mark R. Vickery, P.G., *Executive Director*



TEXAS COMMISSION ON ENVIRONMENTAL QUALITY
Protecting Texas by Reducing and Preventing Pollution

August 25, 2011

MR JOSEPH C. WOLF
PLANT MANAGER
EXXON MOBIL CORPORATION
PO BOX 1653
MONT BELVIEU TX 77580-1653

Re: Final Revised Permit Approval
Minor Revision
Permit Number: O2276
Exxon Mobil Corporation
Linear Low Density Polyethylene Plant
Mont Belvieu, Chambers County
Regulated Entity Number: RN102501020
Customer Reference Number: CN600123939
Account Number: CI-0009-P

Dear Mr. Wolf:

The revised effective federal operating permit (FOP) for Exxon Mobil Corporation, Linear Low Density Polyethylene Plant is enclosed. On January 15, 2010, the Texas Commission on Environmental Quality (TCEQ) received an objection on this permit project from the Environmental Protection Agency (EPA). The TCEQ responded on June 30, 2010. The EPA authorized the issuance of this project on August 17, 2011. This letter constitutes authority to operate the changes identified in the FOP revision application.

Consistent with Title 30 Texas Administrative Code Chapter 122, Subchapter C, the permit holder shall submit an application to the Air Permits Division (APD) for a revision to an FOP for those activities at a site which change, add, or remove one or more FOP terms or conditions. The permit holder shall also submit an application to the APD for a revision to a permit to address the following: the adoption of an applicable requirement previously designated as federally enforceable only; the promulgation of a new applicable requirement; the adoption of a new state-only requirement; or a change in a state-only designation.

Thank you again for your cooperation in this matter. If you have questions concerning the review or this notice, please contact Ms. Angie Eastman at (512) 239-5945.

Mr. Joseph C. Wolf
Page 2
August 25, 2011

This action is taken under authority delegated by the Executive Director of the Texas Commission on Environmental Quality.

Sincerely,



Michael Wilson, P.E., Director
Air Permits Division
Office of Air
Texas Commission on Environmental Quality

MPW/AE/

cc: Mr. Sherman Hampton, Environmental Coordinator, Exxon Mobil Corporation, Mont
Belvieu
Air Section Manager, Region 12 - Houston

Enclosure: Revised Effective Permit
Modifications Made from Draft to the Final Permit

cc: Air Permit Section Chief, U.S. Environmental Protection Agency, Region 6, Dallas

Project Number: 1418

FEDERAL OPERATING PERMIT

A FEDERAL OPERATING PERMIT IS HEREBY ISSUED TO

Exxon Mobil Corporation

AUTHORIZING THE OPERATION OF

Linear Low Density Polyethylene Plant
Plastics Materials and Resins

LOCATED AT

Chambers County, Texas

Latitude 29° 52' 30" Longitude 94° 55' 0"

Regulated Entity Number: RN102501020

This permit is issued in accordance with and subject to the Texas Clean Air Act (TCAA), Chapter 382 of the Texas Health and Safety Code and Title 30 Texas Administrative Code Chapter 122 (30 TAC Chapter 122), Federal Operating Permits. Under 30 TAC Chapter 122, this permit constitutes the permit holder's authority to operate the site and emission units listed in this permit. Operations of the site and emission units listed in this permit are subject to all additional rules or amended rules and orders of the Commission pursuant to the TCAA.

This permit does not relieve the permit holder from the responsibility of obtaining New Source Review authorization for new, modified, or existing facilities in accordance with 30 TAC Chapter 116, Control of Air Pollution by Permits for New Construction or Modification.

The site and emission units authorized by this permit shall be operated in accordance with 30 TAC Chapter 122, the general terms and conditions, special terms and conditions, and attachments contained herein.

This permit shall expire five years from the date of issuance. The renewal requirements specified in 30 TAC § 122.241 must be satisfied in order to renew the authorization to operate the site and emission units.

Permit No: 02276 Issuance Date: April 6, 2009


For the Commission

TABLE OF CONTENTS

Section	Page
GENERAL TERMS AND CONDITIONS	1
SPECIAL TERMS AND CONDITIONS:.....	1
Emission Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting:	1
Additional Monitoring Requirements	10
New Source Review Authorization Requirements	10
Compliance Requirements	11
Risk Management Plan	13
Protection of Stratospheric Ozone	13
Temporary Fuel Shortages (30 TAC § 112.15)	14
Permit Location.....	14
Permit Shield (30 TAC § 122.148).....	14
ATTACHMENTS.....	15
Applicable Requirements Summary	16
Additional Monitoring Requirements	55
Permit Shield.....	60
New Source Review Authorization References.....	64
APPENDIX A.....	72
Acronym List	73

GENERAL TERMS AND CONDITIONS

The permit holder shall comply with all terms and conditions contained in 30 TAC § 122.143 (General Terms and Conditions), 30 TAC § 122.144 (Recordkeeping Terms and Conditions), 30 TAC § 122.145 (Reporting Terms and Conditions), and 30 TAC § 122.146 (Compliance Certification Terms and Conditions).

In accordance with 30 TAC § 122.144(1), records of required monitoring data and support information required by this permit, or any applicable requirement codified in this permit, are required to be maintained for a period of five years from the date of the monitoring report, sample, or application unless a longer data retention period is specified in an applicable requirement. The five year record retention period supersedes any less stringent retention requirement that may be specified in a condition of a permit identified in the New Source Review Authorization attachment.

If the permit holder chooses to demonstrate that this permit is no longer required, a written request to void this permit shall be submitted to the Texas Commission on Environmental Quality (TCEQ) by the Responsible Official in accordance with 30 TAC § 122.161(e). The permit holder shall comply with the permit's requirements, including compliance certification and deviation reporting, until notified by the TCEQ that this permit is voided.

The permit holder shall comply with 30 TAC Chapter 116 by obtaining a New Source Review authorization prior to new construction or modification of emission units located in the area covered by this permit.

All reports required by this permit must include in the submittal a cover letter which identifies the following information: company name, TCEQ regulated entity number, air account number (if assigned), site name, area name (if applicable), and Air Permits Division permit number(s).

SPECIAL TERMS AND CONDITIONS:

Emission Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting:

1. Permit holder shall comply with the following requirements:
 - A. Emission units (including groups and processes) in the Applicable Requirements Summary attachment shall meet the limitations, standards, equipment specifications, monitoring, recordkeeping, reporting, testing, and other requirements listed in the Applicable Requirements Summary attachment to assure compliance with the permit.
 - B. The textual description in the column titled "Textual Description" in the Applicable Requirements Summary attachment is not enforceable and is not deemed as a substitute for the actual regulatory language. The Textual Description is provided for information purposes only.

C. A citation listed on the Applicable Requirements Summary attachment, which has a notation [G] listed before it, shall include the referenced section and subsection for all commission rules, or paragraphs for all federal and state regulations and all subordinate paragraphs, subparagraphs and clauses, subclauses, and items contained within the referenced citation as applicable requirements.

D. Emission units subject to 40 CFR Part 63, Subpart FFFF as identified in the attached Applicable Requirements Summary table are subject to 30 TAC Chapter 113, Subchapter C, § 113.890 which incorporates the 40 CFR Part 63 Subpart by reference.

E. The permit holder shall comply with the following 30 TAC Chapter 101, Subchapter H, Division 3 (Mass Emission Cap and Trade Program) Requirements:

- (i) Title 30 TAC § 101.352 (relating to General Provisions)
- (ii) Title 30 TAC § 101.353 (relating to Allocation of Allowances)
- (iii) Title 30 TAC § 101.354 (relating to Allowance Deductions)
- (iv) Title 30 TAC § 101.356 (relating to Allowance Banking and Trading)
- (v) Title 30 TAC § 101.358 (relating to Emission Monitoring and Compliance Demonstration)
- (vi) Title 30 TAC § 101.359 (relating to Reporting)
- (vii) Title 30 TAC § 101.360 (relating to Level of Activity Certification)
- (viii) The terms and conditions by which the emission limits are established to meet or exceed the cap are applicable requirements of this permit

F. The permit holder shall comply with the following 30 TAC Chapter 101, Subchapter H, Division 6 (Highly Reactive Volatile Organic Compound Emissions Cap and Trade Program) requirements:

- (i) Title 30 TAC § 101.392 (relating to Exemptions)
- (ii) Title 30 TAC § 101.401 (relating to Level of Activity Certification)

2. The permit holder shall comply with the following sections of 30 TAC Chapter 101 (General Air Quality Rules):

- A. Title 30 TAC § 101.1 (relating to Definitions), insofar as the terms defined in this section are used to define the terms used in other applicable requirements
- B. Title 30 TAC § 101.3 (relating to Circumvention)

- C. Title 30 TAC § 101.8 (relating to Sampling), if such action has been requested by the TCEQ
 - D. Title 30 TAC § 101.9 (relating to Sampling Ports), if such action has been requested by the TCEQ
 - E. Title 30 TAC § 101.10 (relating to Emissions Inventory Requirements)
 - F. Title 30 TAC § 101.201 (relating to Emission Event Reporting and Recordkeeping Requirements)
 - G. Title 30 TAC § 101.211 (relating to Scheduled Maintenance, Startup, and Shutdown Reporting and Recordkeeping Requirements)
 - H. Title 30 TAC § 101.221 (relating to Operational Requirements)
 - I. Title 30 TAC § 101.222 (relating to Demonstrations)
 - J. Title 30 TAC § 101.223 (relating to Actions to Reduce Excessive Emissions)
3. Permit holder shall comply with the following requirements of 30 TAC Chapter 111:
- A. Visible emissions from stationary vents with a flow rate of less than 100,000 actual cubic feet per minute and constructed after January 31, 1972, that are not listed in the Applicable Requirements Summary attachment for 30 TAC Chapter 111, Subchapter A, Division 1, shall not exceed 20% opacity averaged over a six minute period. The permit holder shall comply with the following requirements for stationary vents at the site subject to this standard:
 - (i) Title 30 TAC § 111.111(a)(1)(B) (relating to Requirements for Specified Sources)
 - (ii) Title 30 TAC § 111.111(a)(1)(E)
 - (iii) Title 30 TAC § 111.111(a)(1)(F)(i), (ii), (iii), or (iv)
 - (iv) For emission units with vent emissions subject to 30 TAC § 111.111(a)(1)(B), complying with 30 TAC § 111.111(a)(1)(F)(ii), (iii), or (iv), and capable of producing visible emissions from, but not limited to, ~~particulate matter, acid gases and NO_x~~, the permit holder shall also comply with the following periodic monitoring requirements for the purpose of annual compliance certification under 30 TAC § 122.146. These periodic monitoring requirements do not apply to vents that do not emit visible emissions such as vents that emit only VOC or vents that provide passive ventilation, such as plumbing vents; or vents that are subject to the emission limitation of 30 TAC § 111.111(a)(1)(B) and Compliance Assurance Monitoring, as specified in the attached

“Applicable Requirements Summary” and “Additional Monitoring Requirements:”

1. An observation of stationary vents from emission units in operation shall be conducted at least once during each calendar quarter unless the emission unit is not operating for the entire quarter.
2. For stationary vents from a combustion source, if an alternative to the normally fired fuel is fired for a period greater than or equal to 24 consecutive hours, the permit holder shall conduct an observation of the stationary vent for each such period to determine if visible emissions are present. If such period is greater than 3 months, observations shall be conducted once during each quarter. Supplementing the normally fired fuel with natural gas or fuel gas to increase the net heating value to the minimum required value does not constitute creation of an alternative fuel.
3. Records of all observations shall be maintained.
4. Visible emissions observations of emission units operated during daylight hours shall be conducted no earlier than one hour after sunrise and no later than one hour before sunset. Visible emissions observations of emission units operated only at night must be made with additional lighting and the temporary installation of contrasting backgrounds. Visible emissions observations shall be made during times when the activities described in 30 TAC § 111.111(a)(1)(E) are not taking place. Visible emissions shall be determined with each stationary vent in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 mile, away from each stationary vent during the observation. For outdoor locations, the observer shall select a position where the sun is not directly in the observer's eyes. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. A certified opacity reader is not required for visible emissions observations.
5. Compliance Certification:
 - (a) If visible emissions are not present during the observation, the RO may certify that the source is in compliance with the applicable opacity requirement in 30 TAC § 111.111(a)(1) and (a)(1)(B).

- (b) However, if visible emissions are present during the observation, the permit holder shall either list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(1)(F) to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.
- (c) Some vents may be subject to multiple visible emission or monitoring requirements. All credible data must be considered when certifying compliance with this requirement even if the observation or monitoring was performed to demonstrate compliance with a different requirement.

B. For visible emissions from a building, enclosed facility, or other structure; the permit holder shall comply with the following requirements:

- (i) Title 30 TAC § 111.111(a)(7)(A) (relating to Requirements for Specified Sources)
- (ii) Title 30 TAC § 111.111(a)(7)(B)(i) or (ii)
- (iii) For a building containing an air emission source, enclosed facility, or other structure containing or associated with an air emission source subject to 30 TAC § 111.111(a)(7)(A), complying with 30 TAC § 111.111(a)(7)(B)(i) or (ii), and capable of producing visible emissions from, but not limited to, particulate matter, acid gases and NO_x, the permit holder shall also comply with the following periodic monitoring requirements for the purpose of annual compliance certification under 30 TAC § 122.146:

1. An observation of visible emissions from a building containing an air emission source, enclosed facility, or other structure containing or associated with an air emission source which is required to comply with 30 TAC § 111.111(a)(7)(A) shall be conducted at least once during each calendar quarter unless the air emission source or enclosed facility is not operating for the entire quarter.
2. Records of all observations shall be maintained.

3. Visible emissions observations of air emission sources or enclosed facilities operated during daylight hours shall be conducted no earlier than one hour after sunrise and no later than one hour before sunset. Visible emissions observations of air emission sources or enclosed facilities operated only at night must be made with additional lighting and the temporary installation of contrasting backgrounds. Visible emissions shall be determined with each emissions outlet in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 mile, away from each emissions outlet during the observation. For outdoor locations, the observer shall select a position where the sun is not directly in the observer's eyes. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. A certified opacity reader is not required for visible emissions observations.

4. Compliance Certification:

- (a) If visible emissions are not present during the observation, the RO may certify that the source is in compliance with the applicable opacity requirement in 30 TAC § 111.111(a)(7) and (a)(7)(A).
- (b) However, if visible emissions are present during the observation, the permit holder shall either list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(7)(B) to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.

C. For visible emissions from all other sources not specified in 30 TAC § 111.111(a)(1), (4), or (7); the permit holder shall comply with the following requirements:

- (i) Title 30 TAC § 111.111(a)(8)(A) (relating to Requirements for Specified Sources)
- (ii) Title 30 TAC § 111.111(a)(8)(B)(i) or (ii)
- (iii) For a source subject to 30 TAC § 111.111(a)(8)(A), complying with 30 TAC § 111.111(a)(8)(B)(i) or (ii), and capable of producing visible emissions from, but not limited to, particulate matter, acid gases and NO_x, the permit holder shall also comply with the following periodic monitoring requirements for the purpose of annual compliance certification under 30 TAC § 122.146:

1. An observation of visible emissions from a source which is required to comply with 30 TAC § 111.111(a)(8)(A) shall be conducted at least once during each calendar quarter unless the source is not operating for the entire quarter.
2. Records of all observations shall be maintained.
3. Visible emissions observations of sources operated during daylight hours shall be conducted no earlier than one hour after sunrise and no later than one hour before sunset. Visible emissions observations of sources operated only at night must be made with additional lighting and the temporary installation of contrasting backgrounds. Visible emissions shall be determined with each source in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 mile, away from each source during the observation. For outdoor locations, the observer shall select a position where the sun is not directly in the observer's eyes. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. A certified opacity reader is not required for visible emissions observations.

4. Compliance Certification:

- (a) If visible emissions are not present during the observation, the RO may certify that the source is in compliance with the applicable opacity requirement in 30 TAC § 111.111(a)(8) and (a)(8)(A).
- (b) However, if visible emissions are present during the observation, the permit holder shall either list this occurrence as a deviation on the next deviation report

as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(8)(B) to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.

- D. For emission units with contributions from uncombined water, the permit holder shall comply with the requirements of 30 TAC § 111.111(b).
 - E. Emission limits on nonagricultural processes, except for the steam generators specified in 30 TAC § 111.153, shall comply with the following requirements:
 - (i) Emissions of PM from any source may not exceed the allowable rates as required in 30 TAC § 111.151(a) (relating to Allowable Emissions Limits)
 - (ii) Sources with an effective stack height (h_e) less than the standard effective stack height (H_e), must reduce the allowable emission level by multiplying it by $[h_e/H_e]^2$ as required in 30 TAC § 111.151(b)
 - (iii) Effective stack height shall be calculated by the equation specified in 30 TAC § 111.151(c)
 - F. Outdoor burning, as stated in 30 TAC § 111.201, shall not be authorized unless the following requirements are satisfied:
 - (i) Title 30 TAC § 111.205 (relating to Exception for Fire Training)
 - (ii) Title 30 TAC § 111.221 (relating to Responsibility for Consequences of Outdoor Burning)
4. For storage vessels maintaining working pressure as specified in 30 TAC Chapter 115, Subchapter B, Division 1: "Storage of Volatile Organic Compounds," the permit holder shall comply with the requirements of 30 TAC § 115.112(a)(1).
5. Permit holder shall comply with the following 30 TAC Chapter 115, Subchapter C requirements:
- A. When filling stationary gasoline storage vessels (Stage I) for motor vehicle fuel dispensing facilities, constructed prior to November 15, 1992, with transfers to stationary storage tanks located at a facility which has dispensed no more than 10,000 gallons of gasoline in any calendar month after January 1, 1991, the permit

holder shall comply with the following requirements specified in 30 TAC Chapter 115, Subchapter C:

- (i) Title 30 TAC § 115.222(7) (relating to Control Requirements)
 - (ii) Title 30 TAC § 115.222(3), as it applies to liquid gasoline leaks
 - (iii) Title 30 TAC § 115.224(1) (relating to Inspection Requirements), as it applies to liquid gasoline leaks
 - (iv) Title 30 TAC § 115.226(2)(B) (relating to Recordkeeping Requirements)
- B. The permit holder shall comply with the annual reporting requirements under 30 TAC § 115.247(2) for motor vehicle fuel dispensing facilities exempt from Stage II.
6. The permit holder shall comply with the following requirements for units subject to any subpart of 40 CFR Part 60, unless otherwise stated in the applicable subpart:
- A. Title 40 CFR § 60.7 (relating to Notification and Recordkeeping)
 - B. Title 40 CFR § 60.8 (relating to Performance Tests)
 - C. Title 40 CFR § 60.11 (relating to Compliance with Standards and Maintenance Requirements)
 - D. Title 40 CFR § 60.12 (relating to Circumvention)
 - E. Title 40 CFR § 60.13 (relating to Monitoring Requirements)
 - F. Title 40 CFR § 60.14 (relating to Modification)
 - G. Title 40 CFR § 60.15 (relating to Reconstruction)
 - H. Title 40 CFR § 60.19 (relating to General Notification and Reporting Requirements)
7. The permit holder shall comply with the requirements of 30 TAC Chapter 113, Subchapter C, § 113.100 for units subject to any subpart of 40 CFR Part 63, unless otherwise stated in the applicable subpart.
8. The permit holder shall comply with certified registrations submitted to the TCEQ for purposes of establishing federally enforceable emission limits. A copy of the certified registration shall be maintained with the permit. Records sufficient to demonstrate compliance with the established limits shall be maintained. The certified registration and records demonstrating compliance shall be provided, on request, to representatives of the appropriate TCEQ regional office and any local air pollution control agency having jurisdiction over the site. The permit holder shall submit updated certified registrations

when changes at the site require establishment of new emission limits. If changes result in emissions that do not remain below major source thresholds, the permit holder shall submit a revision application to codify the appropriate requirements in the permit.

Additional Monitoring Requirements

9. The permit holder shall comply with the periodic monitoring requirements as specified in the attached "Periodic Monitoring Summary" upon issuance of the permit. Except for, as applicable, monitoring malfunctions, associated repairs, and required quality assurance or control activities (including, as applicable, calibration checks and required zero and span adjustments), the permit holder shall conduct all monitoring in continuous operation (or shall collect data at all required intervals) at all times that the pollutant-specific emissions unit is operating. The permit holder may elect to collect monitoring data on a more frequent basis and average the data, consistent with the averaging time specified in the "Periodic Monitoring Summary," for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis. In no event shall data be collected and used in particular instances to avoid reporting deviations. Deviations shall be reported according to 30 TAC § 122.145 (Reporting Terms and Conditions).

New Source Review Authorization Requirements

10. Permit holder shall comply with the requirements of New Source Review authorizations issued or claimed by the permit holder for the permitted area, including permits, permits by rule, standard permits, flexible permits, special permits, permits for existing facilities including Voluntary Emissions Reduction Permits and Electric Generating Facility Permits issued under 30 TAC Chapter 116, Subchapter I, or special exemptions referenced in the New Source Review Authorization References attachment. These requirements:
 - A. Are incorporated by reference into this permit as applicable requirements
 - B. Shall be located with this operating permit
 - C. Are not eligible for a permit shield
11. The permit holder shall comply with the general requirements of 30 TAC Chapter 106, Subchapter A or the general requirements, if any, in effect at the time of the claim of any PBR.
12. The permit holder shall comply with the following requirements for Air Quality Standard Permits:
 - A. Registration requirements listed in 30 TAC § 116.611, unless otherwise provided for in an Air Quality Standard Permit
 - B. General Conditions listed in 30 TAC § 116.615, unless otherwise provided for in an Air Quality Standard Permit

- C. Applicable requirements of 30 TAC § 116.617 for Pollution Control Projects based on the information contained in the registration application.
13. The permit holder shall maintain records to demonstrate compliance with any emission limitation or standard that is specified in a permit by rule (PBR) or Standard Permit listed in the New Source Review Authorizations attachment. The records shall yield reliable data from the relevant time period that are representative of the emission unit's compliance with the PBR or Standard Permit. These records may include, but are not limited to, production capacity and throughput, hours of operation, material safety data sheets (MSDS), chemical composition of raw materials, speciation of air contaminant data, engineering calculations, maintenance records, fugitive data, performance tests, capture/control device efficiencies, direct pollutant monitoring (CEMS, COMS, or PEMS), or control device parametric monitoring. These records shall be made readily accessible and available as required by 30 TAC § 122.144.
- A. If applicable, monitoring of control device performance or general work practice standards shall be made in accordance with the TCEQ Periodic Monitoring Guidance document.
- B. Any monitoring or recordkeeping data indicating noncompliance with the PBR or Standard Permit shall be considered and reported as a deviation according to 30 TAC § 122.145 (Reporting Terms and Conditions).

Compliance Requirements

14. The permit holder shall certify compliance in accordance with 30 TAC § 122.146. The permit holder shall comply with 30 TAC § 122.146 using at a minimum, but not limited to, the continuous or intermittent compliance method data from monitoring, recordkeeping, reporting, or testing required by the permit and any other credible evidence or information. The certification period may not exceed 12 months and the certification must be submitted within 30 days after the end of the period being certified.
15. Permit holder shall comply with the following 30 TAC Chapter 117 requirement:
- A. The permit holder shall comply with the compliance schedules and submit written notification to the TCEQ Executive Director as required in 30 TAC Chapter 117, Subchapter H, Division 1:
- (i) For sources in the Houston-Galveston-Brazoria Nonattainment area, 30 TAC § 117.9020:
1. Title 30 TAC § 117.9020(2)(A), (C), and (D)
- B. The permit holder shall comply with the Initial Control Plan unit listing requirement in 30 TAC § 117.350(c) and (c)(1).
- C. The permit holder shall comply with the requirements of 30 TAC § 117.354 for Final Control Plan Procedures for Attainment Demonstration Emission Specifications and 30 TAC § 117.356 for Revision of Final Control Plan.

16. Use of Emission Credits to comply with applicable requirements:

A. Unless otherwise prohibited, the permit holder may use emission credits to comply with the following applicable requirements listed elsewhere in this permit:

- (i) Title 30 TAC Chapter 115
- (ii) Title 30 TAC Chapter 117
- (iii) Offsets for Title 30 TAC Chapter 116

B. The permit holder shall comply with the following requirements in order to use the emission credits to comply with the applicable requirements:

- (i) The permit holder must notify the TCEQ according to 30 TAC § 101.306(c)(2)
- (ii) The emission credits to be used must meet all the geographic, timeliness, applicable pollutant type, and availability requirements listed in 30 TAC Chapter 101, Subchapter H, Division 1
- (iii) The executive director has approved the use of the credit according to 30 TAC § 101.306(c)(2)
- (iv) The permit holder keeps records of the use of credits towards compliance with the applicable requirements in accordance with 30 TAC § 101.302(g) and 30 TAC Chapter 122

17. Use of Discrete Emission Credits to comply with applicable requirements:

A. Unless otherwise prohibited, the permit holder may use discrete emission credits to comply with the following applicable requirements listed elsewhere in this permit:

- (i) Title 30 TAC Chapter 115
- (ii) Title 30 TAC Chapter 117
- (iii) If applicable, offsets for Title 30 TAC Chapter 116
- (iv) Temporarily exceed state NSR permit allowables

B. The permit holder shall comply with the following requirements in order to use the credit to comply with the applicable requirements:

- (i) The permit holder must notify the TCEQ according to 30 TAC § 101.376(d)

- (ii) The discrete emission credits to be used must meet all the geographic, timeliness, applicable pollutant type, and availability requirements listed in 30 TAC Chapter 101, Subchapter H, Division 4
- (iii) The executive director has approved the use of the discrete emission credits according to 30 TAC § 101.376(d)(1)(A)
- (iv) The permit holder keeps records of the use of credits towards compliance with the applicable requirements in accordance with 30 TAC § 101.372(h) and 30 TAC Chapter 122

Risk Management Plan

- 18. For processes subject to 40 CFR Part 68 and specified in 40 CFR § 68.10, the permit holder shall comply with the requirements of the Accidental Release Prevention Provisions in 40 CFR Part 68. The permit holder shall submit to the appropriate agency either a compliance schedule for meeting the requirements of 40 CFR Part 68 by the date provided in 40 CFR § 68.10(a), or as part of the compliance certification submitted under this permit, a certification statement that the source is in compliance with all requirements of 40 CFR Part 68, including the registration and submission of a risk management plan.

Protection of Stratospheric Ozone

- 19. Permit holders at a site subject to Title VI of the FCAA Amendments shall meet the following requirements for protection of stratospheric ozone:
 - A. Any on site servicing, maintenance, and repair on refrigeration and nonmotor vehicle air-conditioning appliances using ozone-depleting refrigerants or non-exempt substitutes shall be conducted in accordance with 40 CFR Part 82, Subpart F. Permit holders shall ensure that repairs on or refrigerant removal from refrigeration and nonmotor vehicle air-conditioning appliances using ozone-depleting refrigerants are performed only by properly certified technicians using certified equipment. Records shall be maintained as required by 40 CFR Part 82, Subpart F.
 - B. The permit holder shall comply with the following 40 CFR Part 82, Subpart E requirements for labeling products using ozone-depleting substances:
 - ~~(i) Title 40 CFR § 82.100 (relating to Purpose)~~
 - (ii) Title 40 CFR § 82.102 (a) (1) - (3), (b), (c) (relating to Applicability)
 - (iii) Title 40 CFR § 82.104 (relating to Definitions)
 - (iv) Title 40 CFR §§ 82.106 - 112 (relating to Warning Statements and Labels)

- (v) Title 40 CFR § 82.114 (relating to Labeling Containers of Controlled [ozone-depleting] Substances)
- (vi) Title 40 CFR § 82.116 (relating to Incorporation of Products Manufactured with Controlled [ozone-depleting] Substances)
- (vii) Title 40 CFR § 82.120 (relating to Petitions)
- (viii) Title 40 CFR § 82.122 (relating Certification, Recordkeeping, and Notice requirements)
- (ix) Title 40 CFR § 82.124 (relating to Prohibitions)

Temporary Fuel Shortages (30 TAC § 112.15)

20. The permit holder shall comply with the following 30 TAC Chapter 112 requirements:
- A. Title 30 TAC § 112.15 (relating to Temporary Fuel Shortage Plan Filing Requirements)
 - B. Title 30 TAC § 112.16(a), (a)(1), and (a)(2)(B) - (C) (relating to Temporary Fuel Shortage Plan Operating Requirements)
 - C. Title 30 TAC § 112.17 (relating to Temporary Fuel Shortage Plan Notification Procedures)
 - D. Title 30 TAC § 112.18 (relating to Temporary Fuel Shortage Plan Reporting Requirements)

Permit Location

21. The permit holder shall maintain a copy of this permit and records related to requirements listed in this permit on site.

Permit Shield (30 TAC § 122.148)

22. A permit shield is granted for the emission units, groups, or processes specified in the attached "Permit Shield." Compliance with the conditions of the permit shall be deemed compliance with the specified potentially applicable requirements or specified potentially applicable state-only requirements listed in the attachment "Permit Shield." Permit shield provisions shall not be modified by the executive director until notification is provided to the permit holder. No later than 90 days after notification of a change in a determination made by the TCEQ executive director, the permit holder shall apply for the appropriate permit revision to reflect the new determination. Provisional terms are not eligible for this permit shield. Any term or condition, under a permit shield, shall not be protected by the permit shield if it is replaced by a provisional term or condition or the basis of the term and condition changes.

ATTACHMENTS

Applicable Requirements Summary

Additional Monitoring Requirements

Permit Shield

New Source Review Authorization References

Applicable Requirements Summary

Unit Summary17

Applicable Requirements Summary28

Note: A “none” entry may be noted for some emission sources in this permit’s “Applicable Requirements Summary” under the heading of “Monitoring and Testing Requirements” and/or “Recordkeeping Requirements” and/or “Reporting Requirements.” Such a notation indicates that there are no requirements for the indicated emission source as identified under the respective column heading(s) for the stated portion of the regulation when the emission source is operating under the conditions of the specified SOP Index Number. However, other relevant requirements pursuant to 30 TAC Chapter 122 including Recordkeeping Terms and Conditions (30 TAC § 122.144), Reporting Terms and Conditions (30 TAC § 122.145), and Compliance Certification Terms and Conditions (30 TAC § 122.146) continue to apply.

Unit Summary

Unit/Group/Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement driver
DEGREASER4	Solvent Degreasing Machines	N/A	R5412-2	30 TAC Chapter 115, Degreasing Processes	No changing attributes.
DEGREASER5	Solvent Degreasing Machines	N/A	R5412-1	30 TAC Chapter 115, Degreasing Processes	No changing attributes.
GRPLPELD1	Loading/Unloading Operations	LL1SF03539, LL1SF03540, LL1SF03541, LL1SF03542, LL1SF03543	R5212-1	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.
GRPLPETK2	Storage Tanks/Vessels	L1TKBUTENE, L1TKHEXENE	R5112-5	30 TAC Chapter 115, Storage of VOCs	No changing attributes.

Unit Summary

Unit/Group/Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement driver
GRPLPEVNT1	Emission Points/Stationary Vents/Process Vents	L1BF05123, L1BF05223, L1BF23127, L1BF24001, L1BF24002, L1BF24003, L1BF24010, L1BF24157, L1BF25034, L1BF25040, L1BF30108, L1BF30109, L1BF30110, L1BF30123, L1BF30124, L1BF30125, L1BF30126, L1BF30127, L1BF30138, L1BF30208, L1BF30209, L1BF30210, L1BF30211, L1BF30223, L1BF30224, L1BF30225, L1BF30226, L1BF30227, L1BF33101, L1BF33201, L1BF33503, L1BF37107, L1BFE2ADD1, L1BN24018, L1CL281JV1, L1CL281JV2, L1CYV580J, L1DR23117, L1DR24012, L1DR25010, L1ME33263, L1VD01427, L1VD02427, L1YD01310, L1YF01328, L1YF01416A, L1YF01416B, L1YF01416C, L1YF02310A, L1YF02310D, L1YF02416A, L1YF02416B, L1YF03416A, L1YF03416B	R5121-3	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.

Unit Summary

Unit/Group/Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement driver
GRPLPEVNT2	Emission Points/Stationary Vents/Process Vents	L1SF03252, L1SF03327, L1SF03352, L1SF04148, L1SF04172, L1TK25055, L1TOA492, L1TOA891, L1V33105V1, L1V33105V2, L1V33205V1, L1V33205V2	R5121-4	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
GRPLPEVNT3	Emission Points/Stationary Vents/Process Vents	L1ANALYZER, L1ANCATE2, L1ANCATM1, L1SF04147, L1SF06112, L1SF06113, L1SF06117, L1SFR1CAT1, L1SFR2CAT1, L1TO6A04, L1VV03243, L1VV03301, L1VV03302, L1VV03303, L1VV03304, L1VV03305, L1VV03306, L1VV03307	R5121-5	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
GRPLPG1BPV	Emission Points/Stationary Vents/Process Vents	HEXDDRYREGN, MR&RSVNT, PURGERVNT, REACTORVNT	63FFFF-G1BPV	40 CFR Part 63, Subpart FFFF	No changing attributes.
GRPLPG2CPV	Emission Points/Stationary Vents/Process Vents	L1BF24001, L1BF24002, L1BF24003, L1BF24010, L1BF24157, L1BF25034, L1BF25040, L1DR23117, L1DR24012, L1DR25010, L1VD01427, L1VD02427, L1YD01310, L1YF01310A, L1YF01310B, L1YF01310D, L1YF01328, L1YF02310D	63FFFF-G2CPV	40 CFR Part 63, Subpart FFFF	No changing attributes.
L1CPVBOILR	Emission Points/Stationary Vents/Process Vents	N/A	R5121-9	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.

Unit Summary

Unit/Group/Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement driver
L1CPVFLARE	Emission Points/Stationary Vents/Process Vents	N/A	R5121-8	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
L1TKISOPEN	Storage Tanks/Vessels	N/A	R5112-4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
L1YF01310A	Emission Points/Stationary Vents/Process Vents	N/A	R5121-3	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
L1YF01310B	Emission Points/Stationary Vents/Process Vents	N/A	R5121-3	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
L1YF01310D	Emission Points/Stationary Vents/Process Vents	N/A	R5121-3	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
LDBLR1	Boilers/Steam Generators/Steam Generating Units	N/A	R7300-2	30 TAC Chapter 117, Subchapter B	No changing attributes.
LDBLR2	Boilers/Steam Generators/Steam Generating Units	N/A	R7300-1	30 TAC Chapter 117, Subchapter B	No changing attributes.
LDCOOLTWR	Industrial Process Cooling Towers	N/A	R5760-1	30 TAC Chapter 115, HRVOC Cooling Towers	No changing attributes.
LDFLARE	Flares	N/A	R1111-1	30 TAC Chapter 111, Visible Emissions	No changing attributes.
LDFLARE	Flares	N/A	60A-1	40 CFR Part 60, Subpart A	No changing attributes.
LDFLARE	Flares	N/A	63A-1	40 CFR Part 63, Subpart A	No changing attributes.
LDFUGEM	Fugitive Emission Units	N/A	R5352-ALL	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	No changing attributes.

Unit Summary

Unit/Group/Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement driver
LDFUGEM	Fugitive Emission Units	N/A	60DDD-ALL	40 CFR Part 60, Subpart DDD	No changing attributes.
LDFUGHRVOC	Fugitive Emission Units	N/A	R5780-ALL	30 TAC Chapter 115, HRVOC Fugitive Emissions	No changing attributes.
LOAD8TOL	Loading/Unloading Operations	N/A	R5212-2	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.
LOADBUT	Loading/Unloading Operations	N/A	R5212-3	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.
PROLDFIN2	Polymer Manufacturing Processes	N/A	60DDD-3	40 CFR Part 60, Subpart DDD	No changing attributes.
PROLDFIN4	Polymer Manufacturing Processes	N/A	60DDD-3	40 CFR Part 60, Subpart DDD	No changing attributes.
PROLDMR	Polymer Manufacturing Processes	N/A	60DDD-2	40 CFR Part 60, Subpart DDD	Polyolefin production = no polyolefin or only one polyolefin is produced, process emissions = individual vent gas streams emit continuous emissions, unctrl'd annual emissions = uncontrolled annual emissions less than 1.6 megagrams/year (1.76 tons/year), weight percent TOC = weight percent total organic compounds less than 0.10%, ctrl continuous emissions = all vent gas streams are uncontrolled

Unit Summary

Unit/Group/Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement driver
PROLDMR	Polymer Manufacturing Processes	N/A	60DDD-5	40 CFR Part 60, Subpart DDD	<p>Polyolefin production = no polyolefin or only one polyolefin is produced, process emissions = individual vent gas streams emit continuous emissions, unctrl'd annual emissions = uncontrolled annual emissions greater than or equal to 1.6 megagrams/year (1.76 tons/year), weight percent TOC = weight percent total organic compounds greater than or equal to 0.10%, ctrl continuous emissions = all continuous emissions are controlled in an existing control device (as defined in 40 CFR § 60.561), continuous control device = flare, annual emissions/ctrl dev = annual emissions entering control device greater than or equal to calculated threshold emissions (cte) levels calculated in 'Table 3', emiss. reduction/ctrl dev = existing control device (as defined in 40 CFR § 60.561) reduces emissions by greater than or equal to 98% or less than equal to 20 parts per million by volume (ppmv)</p>

Unit Summary

Unit/Group/Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement driver
PROLDMR	Polymer Manufacturing Processes	N/A	60DDD-6	40 CFR Part 60, Subpart DDD	<p>Polyolefin production = more than one polyolefin is produced, process emissions = individual vent gas streams emit continuous emissions, unctrl'd annual emissions = uncontrolled annual emissions greater than or equal to 1.6 megagrams/year (1.76 tons/year), weight percent TOC = weight percent total organic compounds greater than or equal to 0.10%, ctrl continuous emissions = all continuous emissions are controlled in an existing control device (as defined in 40 CFR § 60.561), continuous control device = boiler or process heater with a design heat input capacity less than 150 MMBtu/hour, annual emissions/ctrl dev = annual emissions entering control device greater than or equal to calculated threshold emissions (cte) levels calculated in 'Table 3', emiss. reduction/ctrl dev = existing control device (as defined in 40 CFR § 60.561) reduces emissions by greater than or equal to 98% or less than equal to 20 parts per million by volume (ppmv)</p>

Unit Summary

Unit/Group/Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement driver
PROLDMR	Polymer Manufacturing Processes	N/A	60DDD-7	40 CFR Part 60, Subpart DDD	Polyolefin production = no polyolefin or only one polyolefin is produced, process emissions = individual vent gas streams emit intermittent emissions, emergency vent = emissions are an emergency vent stream from a new, modified, or reconstructed facility
PROLDMR	Polymer Manufacturing Processes	N/A	60DDD-8	40 CFR Part 60, Subpart DDD	Polyolefin production = no polyolefin or only one polyolefin is produced, process emissions = individual vent gas streams emit intermittent emissions, emergency vent = emissions are not an emergency vent stream from a new modified or reconstructed facility, existing control device = vent stream is controlled not in an existing control device (as defined in 40 CFR § 60.561) which has not been reconstructed, replaced, or its operating conditions modified as a result of state or local regulations, intermittent ctrl device = flare

Unit Summary

Unit/Group/Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement driver
PROLDPOLY	Polymer Manufacturing Processes	N/A	60DDD-5	40 CFR Part 60, Subpart DDD	<p>Process emissions = individual vent gas streams emit continuous emissions, unctrl'd annual emissions = uncontrolled annual emissions greater than or equal to 1.6 megagrams/year (1.76 tons/year), weight percent TOC = weight percent total organic compounds greater than or equal to 0.10%, ctrl continuous emissions = all continuous emissions are controlled in an existing control device (as defined in 40 CFR § 60.561), continuous control device = flare, annual emissions/ctrl dev = annual emissions entering control device greater than or equal to calculated threshold emissions (cte) levels calculated in 'Table 3', emiss. reduction/ctrl dev = existing control device (as defined in 40 CFR § 60.561) reduces emissions by greater than or equal to 98% or less than equal to 20 parts per million by volume (ppmv)</p>

Unit Summary

Unit Group/Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement driver
PROLDPOLY	Polymer Manufacturing Processes	N/A	60DDD-7	40 CFR Part 60, Subpart DDD	Process emissions = individual vent gas streams emit intermittent emissions, emergency vent = emissions are an emergency vent stream from a new modified or reconstructed facility
PROLDPOLY	Polymer Manufacturing Processes	N/A	60DDD-8	40 CFR Part 60, Subpart DDD	Process emissions = individual vent gas streams emit intermittent emissions, emergency vent = emissions are not an emergency vent stream from a new modified or reconstructed facility, existing control device = vent stream is controlled not in an existing control device (as defined in 40 CFR § 60.561) which has not been reconstructed, replaced, or its operating conditions modified as a result of state or local regulations, intermittent ctrl device = flare
PROLDRMP	Polymer Manufacturing Processes	N/A	60DDD-7	40 CFR Part 60, Subpart DDD	Emergency vent = emissions are an emergency vent stream from a new, modified, or reconstructed facility

Unit Summary

Unit/Group/Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement driver
PROLDRMP	Polymer Manufacturing Processes	N/A	60DDD-8	40 CFR Part 60, Subpart DDD	Emergency vent = emissions are not an emergency vent stream from a new, modified, or reconstructed facility, existing control device = vent stream is controlled not in an existing control device (as defined in 40 CFR § 60.561) which has not been reconstructed, replaced, or its operating conditions modified as a result of state or local regulations, intermittent ctrl device = flare
PROSF01	Surface Coating Operations	N/A	R5421-1	30 TAC Chapter 115, Surface Coating Operations	No changing attributes.
SC&RFVNT	Emission Points/Stationary Vents/Process Vents	N/A	63FFFF-G1CPV	40 CFR Part 63, Subpart FFFF	No changing attributes.
TEMPBOILER	Boilers/Steam Generators/Steam Generating Units	N/A	R7300-1	30 TAC Chapter 117, Subchapter B	No changing attributes.
TEMPBOILER	Boilers/Steam Generators/Steam Generating Units	N/A	60Dc-1	40 CFR Part 60, Subpart Dc	No changing attributes.

Applicable Requirements Summary

Unit Group Process		SOP Index No.	Pollutant	Emission Limitation Standard or Equipment Specification		Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
ID No.	Type			Name	Citation				
DEGREASE R4	EU	R5412-2	VOC	30 TAC Chapter 115, Degreasing Processes	§ 115.412(1) [G]§ 115.412(1)(A) § 115.412(1)(C) § 115.412(1)(E) [G]§ 115.412(1)(F) § 115.417(1)	Cold solvent cleaning. No person shall own or operate a system utilizing a VOC for the cold solvent cleaning of objects without the controls listed in §115.412(1)(A)-(F).	[G]§ 115.415(1) § 115.415(3) ** See Periodic Monitoring Summary	None	None
DEGREASE R5	EU	R5412-1	VOC	30 TAC Chapter 115, Degreasing Processes	§ 115.412(1) [G]§ 115.412(1)(A) § 115.412(1)(C) § 115.412(1)(E) [G]§ 115.412(1)(F) § 115.417(1)	Cold solvent cleaning. No person shall own or operate a system utilizing a VOC for the cold solvent cleaning of objects without the controls listed in §115.412(1)(A)-(F).	[G]§ 115.415(1) § 115.415(3) ** See Periodic Monitoring Summary	None	None
GRPLPELD1	EU	R5212-1	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(a)(1) § 115.212(a)(2) [G]§ 115.212(a)(7) § 115.214(a)(1)(B) § 115.214(a)(1)(D) § 115.214(a)(1)(D)(i)	Vapor pressure (at land-based operations). All land-based loading and unloading of VOC with a true vapor pressure less than 0.5 psia is exempt from the requirements of this division, except as specified.	§ 115.214(a)(1)(A) § 115.216(2) 115.214(a)(1)(A)(i) § 115.215 § 115.215(4)	§ 115.216 § 115.216(2) § 115.216(3)(B)	None
GRPLPETK2	EU	R5112-5	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(a)(1) § 115.112(a)(3)	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	[G]§ 115.115(a) § 115.116(a)(4) § 115.116(a)(5) ** See Periodic Monitoring Summary	§ 115.116(a)(4) § 115.116(a)(5)	None
GRPLPEVN T1	EP	R5121-3	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(1) [G]§ 115.122(a)(4)	A vent gas stream from a LDPE plant is exempt from §115.121(a)(1) if less than or equal to 1.1 pounds of ethylene per 1,000 pounds (1.1 kg/1000 kg) of product are emitted from all the specified vent gas streams.	[G]§ 115.125 § 115.126(2) § 115.126(3)(A)	§ 115.126 § 115.126(2) § 115.126(3) § 115.126(3)(A)	None

Applicable Requirements Summary

Unit/Group/Process		SOP Index No.	Pollutant	Emission Limitation/Standard or Equipment Specification		Textual Description (See Special Term and Condition I.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
ID No.	Type			Name	Citation				
GRPLPG1BP V	EP	63FFFF- G1BPV	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2450(a) § 63.2450(e)(2) § 63.2450(f) § 63.2460(a)	You must be in compliance with the emission limits and work practice standards in tables 1 through 7 to this subpart at all times, except during periods of startup, shutdown, and malfunction (SSM), and you must meet the requirements specified in §§63.2455 through 63.2490 (or the alternative means of compliance in §63.2495, §63.2500, or §63.2505), except as specified in paragraphs (b) through (s) of this section.	§ 63.2450(f)	§ 63.2525	§ 63.2515(a) § 63.2520(a) § 63.2520(b)(1)-(5) § 63.2520(d) § 63.2520(e)(1)-(10)
GRPLPG2CP V	EP	63FFFF- G2CPV	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2450(a) § 63.2445(d) § 63.2455(a)	You must be in compliance with the emission limits and work practice standards in tables 1 through 7 to this subpart at all times, except during periods of startup, shutdown, and malfunction (SSM), and you must meet the requirements specified in §§63.2455 through 63.2490 (or the alternative means of compliance in §63.2495, §63.2500, or §63.2505), except as specified in paragraphs (b) through (s) of this section.	None	§ 63.2525	§ 63.2515(a) § 63.2520(a) § 63.2520(b)(1)-(-5) § 63.2520(d) § 63.2520(e)(1)-(-10)
GRPLPEVN T2	EP	R5121-4	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
GRPLPEVN T2	EP	R5121-4	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(B) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream specified in § 115.121(a)(1) of this title with a concentration of VOC < 612 ppmv is exempt from § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None

Applicable Requirements Summary

Unit Group Process		SOP Index No.	Pollutant	Emission Limitation/Standard or Equipment Specification		Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
ID No.	Type			Name	Citation				
GRPLPEVN T3	EP	R5121-5	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
LICPVBOIL R	EP	R5121-9	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(1) § 115.122(a)(1) § 115.122(a)(1)(C)	No person may allow a vent gas stream containing VOC to be emitted from any process vent, unless the vent gas stream is burned properly in accordance with §115.122(a)(1) of this title.	[G]§ 115.125 § 115.126(1) § 115.126(1)(C) § 115.126(2) ** See Periodic Monitoring Summary	§ 115.126 § 115.126(1) § 115.126(1)(C) § 115.126(2)	None
LICPVFLA RE	EP	R5121-8	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(1) § 115.122(a)(1) § 115.122(a)(1)(B) § 60.18	No person may allow a vent gas stream containing VOC to be emitted from any process vent, unless the vent gas stream is burned properly in accordance with §115.122(a)(1) of this title.	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None
LITKISOPE N	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(a)(1) § 115.112(a)(3)	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	[G]§ 115.115(a) § 115.116(a)(4) § 115.116(a)(5) ** See Periodic Monitoring Summary	§ 115.116(a)(4) § 115.116(a)(5)	None
L1YF01310 A	EP	R5121-3	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(1) [G]§ 115.122(a)(4)	A vent gas stream from a LDPE plant is exempt from §115.121(a)(1) if less than or equal to 1.1 pounds of ethylene per 1,000 pounds (1.1 kg/1000 kg) of product are emitted from all the specified vent gas streams.	[G]§ 115.125 § 115.126(2) § 115.126(3)(A)	§ 115.126 § 115.126(2) § 115.126(3) § 115.126(3)(A)	None
L1YF01310B	EP	R5121-3	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(1) [G]§ 115.122(a)(4)	A vent gas stream from a LDPE plant is exempt from §115.121(a)(1) if less than or equal to 1.1 pounds of ethylene per 1,000 pounds (1.1 kg/1000 kg) of product are emitted from all the specified vent gas streams.	[G]§ 115.125 § 115.126(2) § 115.126(3)(A)	§ 115.126 § 115.126(2) § 115.126(3) § 115.126(3)(A)	None

Applicable Requirements Summary

Unit/Group/Process		SOP Index No.	Pollutant	Emission Limitation/Standard or Equipment Specification		Textual Description (See Special Term and Condition I.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
ID No.	Type			Name	Citation				
LIYF01310 D	EP	R5121-3	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(1) [G]§ 115.122(a)(4)	A vent gas stream from a LDPE plant is exempt from §115.121(a)(1) if less than or equal to 1.1 pounds of ethylene per 1,000 pounds (1.1 kg/1000 kg) of product are emitted from all the specified vent gas streams.	[G]§ 115.125 § 115.126(2) § 115.126(3)(A)	§ 115.126 § 115.126(2) § 115.126(3) § 115.126(3)(A)	None
LDBLR1	EU	R7300-2	NOX	30 TAC Chapter 117, Subchapter B	§ 117.300 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 117, Subchapter B	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 117, Subchapter B	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 117, Subchapter B	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 117, Subchapter B	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 117, Subchapter B
LDBLR2	EU	R7300-1	NOX	30 TAC Chapter 117, Subchapter B	§ 117.300 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 117, Subchapter B	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 117, Subchapter B	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 117, Subchapter B	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 117, Subchapter B	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 117, Subchapter B
LDCOOLT WR	EU	R5760-1	HIGHLY REACTIVE VOC	30 TAC Chapter 115, HRVOC Cooling Towers	§ 115.767(6) § 115.766(i)	All sites that are subject to this division and that are located in the Houston/Galveston/Brazoria area as defined in § 115.10, excluding Harris County, are exempt from § 115.761(b) and (c)(2), except as provided in § 115.769(a)(3).	§ 115.764(c) § 115.764(f)	§ 115.766(a)(1) § 115.766(a)(2) § 115.766(a)(3) § 115.766(a)(5) § 115.766(a)(6) § 115.766(c) [G]§ 115.766(g) § 115.766(i)(1)	§ 115.766(i)(2)
LDFLARE	EU	R1111-1	PM (OPACITY)	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(4)(A)	Visible emissions from a process gas flare shall not be permitted for more than five minutes in any two-hour period, except for upset emissions as provided in §101.11(a).	§ 111.111(a)(4)(A)(i) § 111.111(a)(4)(A)(ii)	§ 111.111(a)(4)(A)(ii)	None

Applicable Requirements Summary

Unit/Group/Process		SOP Index No.	Pollutant	Emission Limitation Standard or Equipment Specification		Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
ID No.	Type			Name	Citation				
LDFLARE	CD	60A-1	OPACITY	40 CFR Part 60, Subpart A	§ 60.18(b) § 60.18(c)(1) § 60.18(c)(2) § 60.18(c)(3)(ii) § 60.18(c)(4)(i) § 60.18(c)(6) § 60.18(e)	Flares shall comply with paragraphs (c)-(f) of § 60.18.	§ 60.18(d) § 60.18(f)(1) § 60.18(f)(2) § 60.18(f)(3) § 60.18(f)(4)	None	None
LDFLARE	CD	63A-1	OPACITY	40 CFR Part 63, Subpart A	§ 63.11(b)(4) § 63.11(b)(1) § 63.11(b)(2) § 63.11(b)(3) § 63.11(b)(5) § 63.11(b)(6)(ii) § 63.11(b)(7)(i)	Flares shall be designed and operated with no visible emissions, except for periods of a total of 5 minutes or less during any 2 consecutive hrs. Test Method 22 in App. A of part 60 of this chapter shall be used.	§ 63.11(b)(4) § 63.11(b)(5) § 63.11(b)(7)(i)	None	None
LDFUGEM	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7) § 115.357(1)	No process drains, contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
LDFUGEM	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7)	No process drains, contacting a process fluid with a TVP >0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None

Applicable Requirements Summary

Unit Group Process		SOP Index No.	Pollutant	Emission Limitation/Standard or Equipment Specification		Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
ID No.	Type			Name	Citation				
LDFUGEM	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.352(9) § 115.357(1) § 115.357(12)	No pressure relief valves (gaseous service), contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, longer than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
LDFUGEM	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.352(9) § 115.357(12) § 115.357(8)	No pressure relief valves (gaseous service), contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, longer than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
LDFUGEM	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No open-ended valves or lines, in an emergency shutdown system or containing materials that would autocatalytically polymerize or would present an explosion, serious overpressure, or other safety hazard if capped or equipped with a double block and bleed system, and contacting a process fluid with a TVP < 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)

Applicable Requirements Summary

Unit/Group/Process		SOP Index	Pollutant	Emission Limitation/Standard or Equipment Specification		Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
ID No.	Type	No.		Name	Citation				
LDFUGEM	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No open-ended valves or lines, in an emergency shutdown system or containing materials that would autocatalytically polymerize or would present an explosion, serious overpressure, or other safety hazard if capped or equipped with a double block and bleed system, and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
LDFUGEM	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No open-ended valves or lines, rated > 10,000 psig and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
LDFUGEM	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No open-ended valves or lines, rated 10,000 psig or greater and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)

Applicable Requirements Summary

Unit Group/Process		SOP Index No.	Pollutant	Emission Limitation/Standard or Equipment Specification		Textual Description (See Special Term and Condition I.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
ID No.	Type			Name	Citation				
LDFUGEM	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No open-ended valves or lines, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
LDFUGEM	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No open-ended valves or lines, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
LDFUGEM	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No valves, rated 10,000 psig or greater and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)

Applicable Requirements Summary

Unit/Group/Process		SOP Index	Pollutant	Emission Limitation Standard or Equipment Specification		Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
ID No.	Type	No.		Name	Citation				
LDFUGEM	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No valves, rated 10,000 psig or greater and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
LDFUGEM	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(12)	No valves, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP less than or equal to 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
LDFUGEM	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No valves, rated less than or equal to 10,000 psig and contacting a process fluid with a TVP greater than 0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(8) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	[G]§ 115.354(7)
LDFUGEM	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1) § 115.357(12)	No flanges, contacting a process fluid with a TVP of 0.044 psia or less, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None

Applicable Requirements Summary

Unit/Group/Process		SOP Index No.	Pollutant	Emission Limitation/Standard or Equipment Specification		Textual Description (See Special Term and Condition I.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
ID No.	Type			Name	Citation				
LDFUGEM	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	No flanges, contacting a process fluid with a TVP >0.044 psia, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
LDFUGEM	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1)	No compressor seal, contacting a process fluid with a TVP of 0.044 psia or less, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
LDFUGEM	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7)	No compressor seal, in hydrogen service or equipped with a shaft seal system, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
LDFUGEM	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(8)	No compressor seals, contacting a process fluid with a TVP >0.044 psia, not in hydrogen service or not equipped with a shaft seal, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None

Applicable Requirements Summary

Unit/Group/Process		SOP Index No.	Pollutant	Emission Limitation Standard or Equipment Specification		Textual Description (See Special Term and Condition I.B.)	Monitoring and Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
ID No.	Type			Name	Citation				
LDFUGEM	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1)	No pump seals, contacting a process fluid with a TVP of 0.044 psia or less, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
LDFUGEM	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7)	No pump seal, equipped with a shaft seal system, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
LDFUGEM	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) [G]§ 115.352(2)(C) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(8)	No pump seals, contacting a process fluid with a TVP >0.044 psia and not equipped with a shaft seal system, shall be allowed to have a VOC leak, for more than 15 days after discovery, exceeding the specified VOC concentration.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4)	None
LDFUGEM	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(6)	Components at a petroleum refinery or synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process, that contact a process fluid that contains less than 10% VOC by weight and components at a natural gas/gasoline processing operation that contact a process fluid that contains less than 1.0% VOC by weight are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

Applicable Requirements Summary

Unit Group/Process		SOP Index No.	Pollutant	Emission Limitation/Standard or Equipment Specification		Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
ID No.	Type			Name	Citation				
LDFUGEM	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(5)	Reciprocating compressors and positive displacement pumps used in natural gas/gasoline processing operations are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
LDFUGEM	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(2) § 115.352(9)	Each pressure relief valve equipped with a rupture disk must comply with §115.352(9) and §115.356(3)(C).	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
LDFUGEM	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(10)	Instrumentation systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet 40 CFR §63.169 (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
LDFUGEM	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(11)	Sampling connection systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet the requirements of 40 CFR §63.166(a) and (b) (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
LDFUGEM	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(13)	Components/systems that contact a process fluid containing VOC having a true vapor pressure equal to or less than 0.002 psia at 68 degrees Fahrenheit are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

Applicable Requirements Summary

Unit Group Process		SOP Index No.	Pollutant	Emission Limitation Standard or Equipment Specification		Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
ID No.	Type			Name	Citation				
LDFUGEM	EU	60DDD-ALL	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-2(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-2 [G]§ 60.482-9 § 60.562-2(d) § 60.562-2(e)	Comply with the requirements as stated in §60.482-2 for pumps in light-liquid service.	[G]§ 60.482-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.565(l)
LDFUGEM	EU	60DDD-ALL	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-2(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-3 [G]§ 60.482-9 § 60.562-2(d) § 60.562-2(e)	Comply with the requirements as stated in §60.482-3 for compressors.	[G]§ 60.482-3 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.565(l)
LDFUGEM	EU	60DDD-ALL	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-2(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-4 [G]§ 60.482-9 § 60.562-2(d) § 60.562-2(e)	Comply with the requirements in as stated in §60.482-4 for pressure relief devices in gas/vapor service.	[G]§ 60.482-4 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(3) [G]§ 60.486(e)(4) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.565(l)
LDFUGEM	EU	60DDD-ALL	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-2(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-5 [G]§ 60.482-9 § 60.562-2(d) § 60.562-2(e)	Comply with the requirements in as stated in §60.482-5 for sampling connection systems.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.565(l)
LDFUGEM	EU	60DDD-ALL	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-2(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-6 [G]§ 60.482-9 § 60.562-2(d) § 60.562-2(e)	Comply with the requirements in as stated in §60.482-6 for open-ended valves and lines.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.565(l)

Applicable Requirements Summary

Unit/Group/Process		SOP Index No.	Pollutant	Emission Limitation Standard or Equipment Specification		Textual Description (See Special Term and Condition I.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
ID No.	Type			Name	Citation				
LDFUGEM	EU	60DDD-ALL	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-2(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-7 [G]§ 60.482-9 [G]§ 60.483-1 [G]§ 60.483-2 § 60.562-2(b) § 60.562-2(d) § 60.562-2(e)	Comply with the requirements in as stated in §60.482-7 for valves in gas/vapor or light-liquid service.	[G]§ 60.482-7 [G]§ 60.483-1 [G]§ 60.483-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) [G]§ 60.486(g) § 60.486(i)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(d) § 60.487(e) § 60.565(l)
LDFUGEM	EU	60DDD-ALL	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-2(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 60.562-2(d) § 60.562-2(e)	Comply with the requirements in as stated in §60.482-8 for pumps in heavy-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.565(l)
LDFUGEM	EU	60DDD-ALL	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-2(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 60.562-2(d) § 60.562-2(e)	Comply with the requirements in as stated in §60.482-8 for valves in heavy-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.565(l)
LDFUGEM	EU	60DDD-ALL	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-2(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 60.562-2(d) § 60.562-2(e)	Comply with the requirements in as stated in §60.482-8 for pressure relief devices in light-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.565(l)
LDFUGEM	EU	60DDD-ALL	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-2(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 60.562-2(d) § 60.562-2(e)	Comply with the requirements in as stated in §60.482-8 for flanges or other connectors.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.565(l)
LDFUGEM	EU	60DDD-ALL	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-2(a) § 60.482-1(d) § 60.562-2(e)	Comply with the requirements as stated in §60.482-1(d) for equipment in vacuum service.	None	§ 60.486(e) § 60.486(e)(1) § 60.486(e)(5)	§ 60.562-2(e)

Applicable Requirements Summary

Unit Group Process		SOP Index No.	Pollutant	Emission Limitation Standard or Equipment Specification		Textual Description (See Special Term and Condition 1.B)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
ID No.	Type			Name	Citation				
LDFUGHRV OC	EU	R5780- ALL	HIGHLY REACTIVE VOC	30 TAC Chapter 115, HRVOC Fugitive Emissions	§ 115.787(a)	Components that contact a process fluid containing less than 5.0% highly-reactive volatile organic compounds by weight on an annual average basis are exempt from the requirements of this division (relating to Fugitive Emissions), except for 115.786(e) and (f) of this title (relating to Record keeping Requirements).	None	§ 115.786(e) § 115.786(f)	None
LDFUGHRV OC	EU	R5780- ALL	HIGHLY REACTIVE VOC	30 TAC Chapter 115, HRVOC Fugitive Emissions	§ 115.780(a) [G]§ 115.781(a) § 115.781(g)(3) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) § 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) § 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv) § 115.783(4)(A)(i) § 115.783(4)(A)(ii) § 115.783(4)(A)(ii)(I) § 115.783(4)(A)(ii)(II) § 115.783(4)(B) § 115.783(4)(B)(i) § 115.783(4)(B)(ii)	Process drains within a petroleum refinery; synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process; or natural gas/gasoline processing operation in the Houston/ Galveston/Brazoria area in which a highly-reactive volatile organic compound is a raw material, intermediate, final product, or in a waste stream is subject to the requirements of this division.	§ 115.354(1) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.781(b) § 115.781(b)(10) § 115.781(b)(3) § 115.781(b)(4) § 115.781(b)(5) § 115.781(b)(6) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2)	§ 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4) § 115.781(b)(10) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) § 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) § 115.786(f)	§ 115.782(c)(1)(B)(i) [G]§ 115.786(c)

Applicable Requirements Summary

Unit Group/Process		SQP Index No.	Pollutant	Emission Limitation/Standard or Equipment Specification		Textual Description (See Special Term and Condition I.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
ID No.	Type			Name	Citation				
LDFUGHRV OC	EU	R5780- ALL	HIGHLY REACTIVE VOC	30 TAC Chapter 115, HRVOC Fugitive Emissions	§ 115.780(a) [G]§ 115.725(c)(1) § 115.725(c)(2) [G]§ 115.725(c)(3) [G]§ 115.781(a) § 115.781(g)(3) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) § 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) § 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv) § 115.787(e) § 115.787(g) § 115.788(a) § 115.788(a)(1) § 115.788(a)(2) § 115.788(a)(2)(A) § 115.788(a)(2)(B) § 115.788(a)(2)(C) § 115.788(a)(2)(C)(i) § 115.788(a)(2)(C)(ii) § 115.788(a)(2)(C)(iii) § 115.788(a)(2)(D) § 115.788(a)(3) § 115.788(a)(3)(A) § 115.788(a)(3)(B) [G]§ 115.788(g)	Pressure relief valves (in gaseous service) within a petroleum refinery; synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process; or natural gas/gasoline processing operation in the Houston/ Galveston/Brazoria area in which a highly-reactive volatile organic compound is a raw material, intermediate, final product, or in a waste stream is subject to the requirements of this division.	§ 115.354(1) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 [G]§ 115.725(c)(1) § 115.725(c)(2) [G]§ 115.725(c)(3) § 115.781(b) § 115.781(b)(10) § 115.781(b)(4) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) § 115.781(b)(8) § 115.781(e) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2)	§ 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4) § 115.781(b)(10) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) § 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) § 115.786(f) [G]§ 115.788(g)	§ 115.725(c)(4) § 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.788(c) [G]§ 115.788(d) § 115.788(e) [G]§ 115.788(g)

Applicable Requirements Summary

Unit/Group/Process		SOP Index	Pollutant	Emission Limitation/Standard or Equipment Specification		Textual Description (See Special Term and Condition I.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements	Reporting Requirements
ID No.	Type	No.		Name	Citation			(30 TAC § 122.144)	(30 TAC § 122.145)
LDFUGHRV OC	EU	R5780- ALL	HIGHLY REACTIVE VOC	30 TAC Chapter 115, HRVOC Fugitive Emissions	§ 115.780(a) [G]§ 115.781(a) § 115.781(g)(3) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(2) § 115.782(c)(2)(A) § 115.782(c)(2)(A)(i) § 115.782(c)(2)(A)(ii) § 115.782(c)(2)(B) § 115.783(5) § 115.787(f) § 115.787(f)(2) § 115.787(f)(3) § 115.787(f)(4) § 115.787(g) § 115.788(a) § 115.788(a)(1) § 115.788(a)(2) § 115.788(a)(2)(A) § 115.788(a)(2)(B) § 115.788(a)(2)(C) § 115.788(a)(2)(C)(i) § 115.788(a)(2)(C)(ii) § 115.788(a)(2)(C)(iii) § 115.788(a)(2)(D) § 115.788(a)(3) § 115.788(a)(3)(A) § 115.788(a)(3)(B) [G]§ 115.788(g)	Open-ended valves or lines within a petroleum refinery; synthetic organic chemical, polymer, resin, or methyl- tert-butyl ether manufacturing process; or natural gas/gasoline processing operation in the Houston/ Galveston/Brazoria area in which a highly-reactive volatile organic compound is a raw material, intermediate, final product, or in a waste stream is subject to the requirements of this division.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.781(b) § 115.781(b)(10) § 115.781(b)(3) § 115.781(b)(4) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) § 115.781(f) § 115.781(f)(1) § 115.781(f)(2) § 115.781(f)(3) § 115.781(f)(4) § 115.781(f)(5) § 115.781(f)(6) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.789(1)(B)	§ 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4) § 115.781(b)(10) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(2) § 115.786(d)(2)(C) § 115.786(e) § 115.786(f) [G]§ 115.788(g)	§ 115.782(c)(2)(A)(ii) [G]§ 115.786(c) § 115.788(c) [G]§ 115.788(d) § 115.788(e) [G]§ 115.788(g) § 115.789(1)(B)

Applicable Requirements Summary

Unit/Group/Process		SOP Index No.	Pollutant	Emission Limitation/Standard or Equipment Specification		Textual Description (See Special Term and Condition I.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
ID No.	Type			Name	Citation				
LDFUGHRV OC	EU	R5780- ALL	HIGHLY REACTIVE VOC	30 TAC Chapter 115, HRVOC Fugitive Emissions	§ 115.780(a) [G]§ 115.781(a) [G]§ 115.781(d) § 115.781(g)(3) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(2) § 115.782(c)(2)(A) § 115.782(c)(2)(A)(i) § 115.782(c)(2)(A)(ii) § 115.782(c)(2)(B) § 115.783(1) § 115.783(1)(A) § 115.783(1)(B) § 115.787(g) § 115.788(a) § 115.788(a)(1) § 115.788(a)(2) § 115.788(a)(2)(A) § 115.788(a)(2)(B) § 115.788(a)(2)(C) § 115.788(a)(2)(C)(i) § 115.788(a)(2)(C)(ii) § 115.788(a)(2)(C)(iii) § 115.788(a)(2)(D) § 115.788(a)(3) § 115.788(a)(3)(A) § 115.788(a)(3)(B) [G]§ 115.788(g)	Bypass line valves within a petroleum refinery; synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process; or natural gas/gasoline processing operation in the Houston/Galveston/Brazoria area in which a highly-reactive volatile organic compound is a raw material, intermediate, final product, or in a waste stream is subject to the requirements of this division.	§ 115.781(b)(10) § 115.781(b)(4) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) [G]§ 115.781(d) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) § 115.786(a)(1) § 115.786(a)(2) § 115.786(a)(2)(A) § 115.786(a)(2)(B) § 115.786(a)(1) § 115.786(b)(1) § 115.786(b)(2) § 115.786(b)(2)(A) § 115.786(b)(2)(B) § 115.786(b)(2)(C) § 115.786(b)(3) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(2) § 115.786(d)(2)(C) § 115.786(e) § 115.786(f) [G]§ 115.788(g)	§ 115.782(c)(2)(A)(ii) [G]§ 115.786(c) § 115.788(c) [G]§ 115.788(d) § 115.788(e) [G]§ 115.788(g)	

Applicable Requirements Summary

Unit Group Process		SOP Index	Pollutant	Emission Limitation Standard or Equipment Specification		Textual Description (See Special Term and Condition I.B.)	Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
ID No.	Type	No.		Name	Citation			(30 TAC § 122.144)	(30 TAC § 122.145)
LD FUGHRV OC	EU	R5780- ALL	HIGHLY REACTIVE VOC	30 TAC Chapter 115, HRVOC Fugitive Emissions	§ 115.780(a) [G]§ 115.781(a) § 115.781(g)(3) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(2) § 115.782(c)(2)(A) § 115.782(c)(2)(A)(i) § 115.782(c)(2)(A)(ii) § 115.782(c)(2)(B) § 115.783(5) § 115.787(f) § 115.787(f)(4) § 115.787(g) § 115.788(a) § 115.788(a)(1) § 115.788(a)(2) § 115.788(a)(2)(A) § 115.788(a)(2)(B) § 115.788(a)(2)(C) § 115.788(a)(2)(C)(i) § 115.788(a)(2)(C)(ii) § 115.788(a)(2)(C)(iii) § 115.788(a)(2)(D) § 115.788(a)(3) § 115.788(a)(3)(A) § 115.788(a)(3)(B) [G]§ 115.788(g)	Valves within a petroleum refinery; synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process; or natural gas/gasoline processing operation in the Houston/ Galveston/Brazoria area in which a highly-reactive volatile organic compound is a raw material, intermediate, final product, or in a waste stream is subject to the requirements of this division.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.781(b) § 115.781(b)(10) § 115.781(b)(4) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2)	§ 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4) § 115.781(b)(10) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(2) § 115.786(d)(2)(C) § 115.786(e) § 115.786(f) [G]§ 115.788(g)	§ 115.782(c)(2)(A)(ii) [G]§ 115.786(c) § 115.788(c) [G]§ 115.788(d) § 115.788(e) [G]§ 115.788(g)

Applicable Requirements Summary

Unit Group Process		SOP Index No.	Pollutant	Emission Limitation Standard or Equipment Specification		Textual Description (See Special Term and Condition 1-B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
ID No.	Type			Name	Citation				
LDFUGHRV OC	EU	R5780- ALL	HIGHLY REACTIVE VOC	30 TAC Chapter 115, HRVOC Fugitive Emissions	§ 115.780(a) [G]§ 115.781(a) § 115.781(g)(3) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) § 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) § 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv)	Flanges or other connectors within a petroleum refinery; synthetic organic chemical, polymer, resin, or methyl- tert-butyl ether manufacturing process; or natural gas/gasoline processing operation in the Houston/ Galveston/Brazoria area in which a highly-reactive volatile organic compound is a raw material, intermediate, final product, or in a waste stream is subject to the requirements of this division.	§ 115.354(1) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.781(b) § 115.781(b)(10) § 115.781(b)(4) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) § 115.781(f) § 115.781(f)(1) § 115.781(f)(2) § 115.781(f)(3) § 115.781(f)(4) § 115.781(f)(5) § 115.781(f)(6) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.789(1)(B)	§ 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4) § 115.781(b)(10) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) § 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) § 115.786(f)	§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.789(1)(B)

Applicable Requirements Summary

Unit/Group/Process		SOP Index No.	Pollutant	Emission Limitation/Standard or Equipment Specification		Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements	Reporting Requirements
ID No.	Type			Name	Citation			(30 TAC § 122.144)	(30 TAC § 122.145)
LDFUGHRV-OC	EU	R5780-ALL	HIGHLY REACTIVE VOC	30 TAC Chapter 115, HRVOC Fugitive Emissions	§ 115.780(a) [G]§ 115.781(a) § 115.781(g)(3) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) § 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) § 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv) § 115.782(c)(1)(C)(i) § 115.782(c)(1)(C)(i)(I) § 115.782(c)(1)(C)(i)(II) § 115.782(c)(1)(C)(i)(III) § 115.782(c)(1)(C)(ii) § 115.783(3) [G]§ 115.783(3)(B) § 115.787(d)	Compressor seals within a petroleum refinery; synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process; or natural gas/gasoline processing operation in the Houston/ Galveston/Brazoria area in which a highly-reactive volatile organic compound is a raw material, intermediate, final product, or in a waste stream is subject to the requirements of this division.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.781(b) § 115.781(b)(10) § 115.781(b)(4) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) § 115.781(c)(1) § 115.781(c)(2) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2)	§ 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4) § 115.781(b)(10) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) § 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) § 115.786(f)	§ 115.782(c)(1)(B)(i) § 115.783(3)(C) [G]§ 115.786(c)
LDFUGHRV-OC	EU	R5780-ALL	HIGHLY REACTIVE VOC	30 TAC Chapter 115, HRVOC Fugitive Emissions	§ 115.780(a) [G]§ 115.781(a) § 115.781(g)(3) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) § 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) § 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv) § 115.782(c)(1)(C)(i) § 115.782(c)(1)(C)(i)(I) § 115.782(c)(1)(C)(i)(II) § 115.782(c)(1)(C)(i)(III) § 115.782(c)(1)(C)(ii) § 115.783(3) [G]§ 115.783(3)(B) § 115.787(b) § 115.787(b)(1) § 115.787(d)	Pump seals within a petroleum refinery; synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process; or natural gas/gasoline processing operation in the Houston/ Galveston/Brazoria area in which a highly-reactive volatile organic compound is a raw material, intermediate, final product, or in a waste stream is subject to the requirements of this division.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.781(b) § 115.781(b)(10) § 115.781(b)(4) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) § 115.781(c)(1) § 115.781(c)(2) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2)	§ 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(4) § 115.781(b)(10) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) § 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) § 115.786(f)	§ 115.782(c)(1)(B)(i) § 115.783(3)(C) [G]§ 115.786(c)

Applicable Requirements Summary

Unit Group/Process		SOP Index No.	Pollutant	Emission Limitation/Standard or Equipment Specification		Textual Description (See Special Term and Condition I.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
ID No.	Type			Name	Citation				
LDFUGHRV OC	EU	R5780- ALL	HIGHLY REACTIVE VOC	30 TAC Chapter 115, HRVOC Fugitive Emissions	§ 115.780(a) [G]§ 115.781(a) § 115.781(g)(3) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) § 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) § 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv) § 115.782(c)(1)(C)(i) § 115.782(c)(1)(C)(i)(I) § 115.782(c)(1)(C)(i)(II) § 115.782(c)(1)(C)(i)(III) § 115.782(c)(1)(C)(ii) § 115.783(3) [G]§ 115.783(3)(B) § 115.787(d)	Agitators within a petroleum refinery; synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process; or natural gas/gasoline processing operation in the Houston/Galveston/Brazoria area in which a highly-reactive volatile organic compound is a raw material, intermediate, final product, or in a waste stream is subject to the requirements of this division.	§ 115.781(b)(10) § 115.781(b)(3) § 115.781(b)(4) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) § 115.781(c)(1) § 115.781(c)(2) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2)	§ 115.781(b)(10) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) § 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) § 115.786(f)	§ 115.782(c)(1)(B)(i) § 115.783(3)(C) [G]§ 115.786(c)
LDFUGHRV OC	EU	R5780- ALL	HIGHLY REACTIVE VOC	30 TAC Chapter 115, HRVOC Fugitive Emissions	§ 115.780(a) [G]§ 115.781(a) § 115.781(g)(3) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) § 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) § 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv) § 115.782(c)(1)(C)(i) § 115.782(c)(1)(C)(i)(I) § 115.782(c)(1)(C)(i)(II) § 115.782(c)(1)(C)(i)(III) § 115.782(c)(1)(C)(ii) § 115.783(3) [G]§ 115.783(3)(B) § 115.787(d)	Heat exchanger heads, sight glasses, meters, gauges, sampling connections, bolted manways, hatches, sump covers, junction box vents, and covers and seals on VOC water separators within a petroleum refinery; synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process; or natural gas/gasoline processing operation in which a HRVOC is a raw material, intermediate, final product, or in a waste stream is subject to the requirements of this division.	§ 115.781(b)(10) § 115.781(b)(3) § 115.781(b)(4) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) § 115.781(f) § 115.781(f)(1) § 115.781(f)(2) § 115.781(f)(3) § 115.781(f)(4) § 115.781(f)(5) § 115.781(f)(6) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.789(1)(B)	§ 115.781(b)(10) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) § 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) § 115.786(f)	§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.789(1)(B)

Applicable Requirements Summary

Unit/Group/Process		SOP Index No.	Pollutant	Emission Limitation/Standard or Equipment Specification		Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
ID No.	Type			Name	Citation				
LOAD8TOL	EU	R5212-2	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(a)(2)(A) § 115.212(a)(2) [G]§ 115.212(a)(7) § 115.214(a)(1)(B) § 115.214(a)(1)(D) § 115.214(a)(1)(D)(i)	Any plant, excluding gasoline bulk plants, which loads less than 20,000 gpd of VOC with a true vapor pressure of 0.5 psia or greater is exempt from the requirements of this division, except for the specified requirements.	§ 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.215 § 115.215(4)	§ 115.216 § 115.216(2) § 115.216(3)(B) § 115.216(3)(D)	None
LOADBUT	EU	R5212-3	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.213(b) § 115.212(a)(2) § 115.212(a)(3)(A) § 115.212(a)(3)(A)(i) § 115.212(a)(3)(B) § 115.212(a)(3)(D) § 115.212(a)(3)(E) § 115.213(b)(1) § 115.213(b)(4) § 115.213(b)(5) § 115.213(b)(5)(B) [G]§ 115.213(b)(6) § 115.214(a)(1)(B) § 115.214(a)(1)(C) § 115.214(a)(1)(D) § 115.214(a)(1)(D)(ii)	General loading - 90% overall control option in the covered non-attainment counties. As an alternative operations may elect to achieve a 90% overall control of emissions at the account.	§ 115.212(a)(3)(B) § 115.213(b) § 115.213(b)(1) § 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.214(a)(1)(A)(ii) § 115.214(a)(1)(A)(iii) § 115.215 § 115.215(1) § 115.215(10) [G]§ 115.215(2) § 115.215(4) § 115.215(9)	§ 115.213(b)(1) § 115.216 § 115.216(1) § 115.216(1)(C) § 115.216(2) § 115.216(3)(A) § 115.216(3)(A)(i) § 115.216(3)(A)(ii) § 115.216(3)(A)(iii) § 115.216(3)(B)	§ 115.213(b)(1) § 115.213(b)(2) § 115.213(b)(3) § 115.213(b)(4)
PROLDFIN2	PRO	60DDD-3	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.560(g)	Vent streams emitting continuous emissions with uncontrolled annual emissions of < 1.6 Mg/yr (1.76 Tons/yr) or with weight % TOC of < 0.10 % from facilities as specified, exempted from §60.562-1(a)(1).	[G]§ 60.564(d)	§ 60.565(a) § 60.565(a)(10) § 60.565(h)	§ 60.565(a) § 60.565(a)(10) § 60.565(k) § 60.565(k)(6) § 60.565(k)(7)
PROLDFIN4	PRO	60DDD-3	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.560(g)	Vent streams emitting continuous emissions with uncontrolled annual emissions of < 1.6 Mg/yr (1.76 Tons/yr) or with weight % TOC of < 0.10 % from facilities as specified, exempted from §60.562-1(a)(1).	[G]§ 60.564(d)	§ 60.565(a) § 60.565(a)(10) § 60.565(h)	§ 60.565(a) § 60.565(a)(10) § 60.565(k) § 60.565(k)(6) § 60.565(k)(7)

Applicable Requirements Summary

Unit/Group/Process		SOP Index No.	Pollutant	Emission Limitation/Standard or Equipment Specification		Textual Description (See Special Term and Condition F.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
ID No.	Type			Name	Citation				
PROLDMR	PRO	60DDD-2	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.560(g)	Vent streams emitting continuous emissions with uncontrolled annual emissions of < 1.6 Mg/yr (1.76 Tons/yr) or with weight % TOC of < 0.10 % from facilities as specified, exempted from §60.562-1(a)(1).	[G]§ 60.564(d)	§ 60.565(a) § 60.565(a)(10) § 60.565(h)	§ 60.565(a) § 60.565(a)(10) § 60.565(k) § 60.565(k)(6) § 60.565(k)(7)
PROLDMR	PRO	60DDD-5	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-1(a)(1) § 60.18 § 60.562-1(a)(1)(i) § 60.562-1(a)(1)(i)(C) § 60.562-1(a)(1)(iii) § 60.562-1(a)(1)(iii)(A) § 60.562-1(d) § 60.562-1(e)	For each vent stream that emits continuous emissions from affected facility, use procedures in paragraphs (a)(1)(ii)-(iii) for determining which continuous emissions to control as specified.	[G]§ 60.563(a) § 60.563(b) § 60.563(b)(2)(i) § 60.563(c) § 60.563(d)(1) § 60.563(d)(2) § 60.564(a) § 60.564(a)(1) § 60.564(a)(3) [G]§ 60.564(d) [G]§ 60.564(e) [G]§ 60.564(f) [G]§ 60.564(g)	[G]§ 60.563(a) § 60.563(d)(1) § 60.565(a) [G]§ 60.565(a)(3) [G]§ 60.565(b)(2) [G]§ 60.565(e) [G]§ 60.565(g) § 60.565(j)	§ 60.565(a) [G]§ 60.565(a)(3) § 60.565(b)(1) § 60.565(i) § 60.565(j) § 60.565(k) § 60.565(k)(2) § 60.565(k)(4) § 60.565(l)
PROLDMR	PRO	60DDD-6	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-1(a)(1) § 60.562-1(a)(1)(i) § 60.562-1(a)(1)(i)(A) § 60.562-1(a)(1)(i)(B) § 60.562-1(a)(1)(iii) § 60.562-1(a)(1)(iii)(A) § 60.562-1(d) § 60.562-1(e)	For each vent stream that emits continuous emissions from affected facility, use procedures in paragraphs (a)(1)(ii)-(iii) for determining which continuous emissions to control as specified.	[G]§ 60.563(a) § 60.563(b)(3) § 60.563(b)(3)(i) § 60.563(c) § 60.563(d)(1) § 60.563(d)(2) § 60.564(a) § 60.564(a)(1) § 60.564(a)(3) [G]§ 60.564(d)	[G]§ 60.563(a) § 60.563(d)(1) § 60.565(a) § 60.565(a)(2) § 60.565(a)(2)(i) § 60.565(a)(2)(ii) [G]§ 60.565(b)(2) § 60.565(d) § 60.565(d)(2) [G]§ 60.565(g) § 60.565(j)	§ 60.565(a) § 60.565(a)(2) § 60.565(a)(2)(i) § 60.565(a)(2)(ii) § 60.565(b)(1) § 60.565(i) § 60.565(j) § 60.565(k) § 60.565(k)(1) § 60.565(k)(2) § 60.565(k)(3) § 60.565(l)
PROLDMR	PRO	60DDD-7	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.560(h)	Emergency vent streams, as defined in §60.561, from a new, modified, or reconstructed polypropylene or polyethylene affected facility are exempt from the requirements of §60.562-1(a)(2).	None	None	None

Applicable Requirements Summary

Unit Group Process		SOP Index No.	Pollutant	Emission Limitation Standard or Equipment Specification		Textual Description (See Special Term and Condition 1.B)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
ID No.	Type			Name	Citation				
PROLDMR	EU	60DDD-8	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-1(a)(2) [G]§ 60.562-1(a)(2)(i) § 60.562-1(d) § 60.562-1(e)	Each vent stream that emits intermittent emissions as defined in §60.560-1(a)(1) shall be controlled as specified; prior to control modification/reconstruction/replacement, the vent stream is exempted.	[G]§ 60.563(a) § 60.563(b) § 60.563(b)(2)(ii) § 60.563(c) § 60.563(d)(1) § 60.563(d)(2) § 60.564(a) § 60.564(a)(1) § 60.564(a)(3) [G]§ 60.564(e)	[G]§ 60.563(a) § 60.563(d)(1) § 60.565(a) [G]§ 60.565(a)(5) [G]§ 60.565(b)(2) [G]§ 60.565(e) [G]§ 60.565(g) § 60.565(j)	§ 60.565(a) [G]§ 60.565(a)(5) § 60.565(b)(1) § 60.565(i) § 60.565(j) § 60.565(k) § 60.565(k)(2) § 60.565(k)(4) § 60.565(l)
PROLDPOL Y	PRO	60DDD-5	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-1(a)(1) § 60.18 § 60.562-1(a)(1)(i) § 60.562-1(a)(1)(i)(C) § 60.562-1(a)(1)(iii) § 60.562-1(a)(1)(iii)(A) § 60.562-1(d) § 60.562-1(e)	For each vent stream that emits continuous emissions from affected facility, use procedures in paragraphs (a)(1)(ii)-(iii) for determining which continuous emissions to control as specified.	[G]§ 60.563(a) § 60.563(b) § 60.563(b)(2)(i) § 60.563(c) § 60.563(d)(1) § 60.563(d)(2) § 60.564(a) § 60.564(a)(1) § 60.564(a)(3) [G]§ 60.564(d) [G]§ 60.564(e) [G]§ 60.564(f) [G]§ 60.564(g)	[G]§ 60.563(a) § 60.563(d)(1) § 60.565(a) [G]§ 60.565(a)(3) [G]§ 60.565(b)(2) [G]§ 60.565(e) [G]§ 60.565(g) § 60.565(j)	§ 60.565(a) [G]§ 60.565(a)(3) § 60.565(b)(1) § 60.565(i) § 60.565(j) § 60.565(k) § 60.565(k)(2) § 60.565(k)(4) § 60.565(l)
PROLDPOL Y	PRO	60DDD-7	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.560(h)	Emergency vent streams, as defined in §60.561, from a new, modified, or reconstructed polypropylene or polyethylene affected facility are exempt from the requirements of §60.562-1(a)(2).	None	None	None
PROLDPOL Y	EU	60DDD-8	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-1(a)(2) [G]§ 60.562-1(a)(2)(i) § 60.562-1(d) § 60.562-1(e)	Each vent stream that emits intermittent emissions as defined in §60.560-1(a)(1) shall be controlled as specified; prior to control modification/reconstruction/replacement, the vent stream is exempted.	[G]§ 60.563(a) § 60.563(b) § 60.563(b)(2)(ii) § 60.563(c) § 60.563(d)(1) § 60.563(d)(2) § 60.564(a) § 60.564(a)(1) § 60.564(a)(3) [G]§ 60.564(e)	[G]§ 60.563(a) § 60.563(d)(1) § 60.565(a) [G]§ 60.565(a)(5) [G]§ 60.565(b)(2) [G]§ 60.565(e) [G]§ 60.565(g) § 60.565(j)	§ 60.565(a) [G]§ 60.565(a)(5) § 60.565(b)(1) § 60.565(i) § 60.565(j) § 60.565(k) § 60.565(k)(2) § 60.565(k)(4) § 60.565(l)

Applicable Requirements Summary

Unit/Group/Process		SOP Index No.	Pollutant	Emission Limitation/Standard or Equipment Specification		Textual Description (See Special Term and Condition I.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
ID No.	Type			Name	Citation				
PROLDRMP	PRO	60DDD-7	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.560(h)	Emergency vent streams, as defined in §60.561, from a new, modified, or reconstructed polypropylene or polyethylene affected facility are exempt from the requirements of §60.562-1(a)(2).	None	None	None
PROLDRMP	EU	60DDD-8	VOC/TOC	40 CFR Part 60, Subpart DDD	§ 60.562-1(a)(2) [G]§ 60.562-1(a)(2)(i) § 60.562-1(d) § 60.562-1(e)	Each vent stream that emits intermittent emissions as defined in §60.560-1(a)(1) shall be controlled as specified; prior to control modification/reconstruction/replacement, the vent stream is exempted.	[G]§ 60.563(a) § 60.563(b) § 60.563(b)(2)(ii) § 60.563(c) § 60.563(d)(1) § 60.563(d)(2) § 60.564(a) § 60.564(a)(1) § 60.564(a)(3) [G]§ 60.564(e)	[G]§ 60.563(a) § 60.563(d)(1) § 60.565(a) [G]§ 60.565(a)(5) [G]§ 60.565(b)(2) [G]§ 60.565(e) [G]§ 60.565(g) § 60.565(j)	§ 60.565(a) [G]§ 60.565(a)(5) § 60.565(b)(1) § 60.565(i) § 60.565(j) § 60.565(k) § 60.565(k)(2) § 60.565(k)(4) § 60.565(l)
PROSF01	PRO	R5421-1	VOC	30 TAC Chapter 115, Surface Coating Operations	§ 115.427(a)(3)(A) [G]§ 115.422(6) § 115.426	Surface coating operations which, when uncontrolled, will emit a combined weight of VOC of less than 3 lbs/hr. and 15 lbs. in any consecutive 24-hours are exempt from §115.421(a) and §115.423.	§ 115.426(4)	§ 115.426(4)	[G]§ 115.422(6)
SC&RFVNT	EP	63FFFF-GICPV	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2450(a) § 63.2450(e)(2) § 63.2450(f) § 63.2455(a)	You must be in compliance with the emission limits and work practice standards in tables 1 through 7 to this subpart at all times, except during periods of startup, shutdown, and malfunction (SSM), and you must meet the requirements specified in §§63.2455 through 63.2490 (or the alternative means of compliance in §63.2495, §63.2500, or §63.2505), except as specified in paragraphs (b) through (s) of this section.	§ 63.2450(f)	§ 63.2525	§ 63.2515(a) § 63.2520(a) § 63.2520(b)(1)-(5) § 63.2520(d) § 63.2520(e)(1)-(10)

Applicable Requirements Summary

Unit/Group/Process		SOP Index No.	Pollutant	Emission Limitation Standard or Equipment Specification		Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
ID No.	Type			Name	Citation				
TEMPBOILER	EU	R7300-1	NOX	30 TAC Chapter 117, Subchapter B	§ 117.300 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 30 TAC Chapter 117, Subchapter B	The permit holder shall comply with the applicable requirements of 30 TAC Chapter 117, Subchapter B	The permit holder shall comply with the applicable monitoring and testing requirements of 30 TAC Chapter 117, Subchapter B	The permit holder shall comply with the applicable recordkeeping requirements of 30 TAC Chapter 117, Subchapter B	The permit holder shall comply with the applicable reporting requirements of 30 TAC Chapter 117, Subchapter B
TEMPBOILER	EU	60Dc-1	SO2	40 CFR Part 60, Subpart Dc	§ 60.40c(a)	This subpart applies to each steam generating unit constructed, reconstructed, or modified after 6/9/89 and that has a maximum design heat input capacity of 2.9-29 megawatts (MW).	None	§ 60.48c(g) § 60.48c(i)	§ 60.48c(a) § 60.48c(a)(1) § 60.48c(a)(3)
TEMPBOILER	EU	60Dc-1	PM	40 CFR Part 60, Subpart Dc	§ 60.40c(a)	This subpart applies to each steam generating unit constructed, reconstructed, or modified after 6/9/89 and that has a maximum design heat input capacity of 2.9-29 megawatts (MW).	None	§ 60.48c(g) § 60.48c(i)	§ 60.48c(a) § 60.48c(a)(1) § 60.48c(a)(3)
TEMPBOILER	EU	60Dc-1	PM (OPACITY)	40 CFR Part 60, Subpart Dc	§ 60.40c(a)	This subpart applies to each steam generating unit constructed, reconstructed, or modified after 6/9/89 and that has a maximum design heat input capacity of 2.9-29 megawatts (MW).	None	§ 60.48c(g) § 60.48c(i)	§ 60.48c(a) § 60.48c(a)(1) § 60.48c(a)(3)

Additional Monitoring Requirements

Periodic Monitoring Summary.....56

Periodic Monitoring Summary

UNIT/GROUP/PROCESS INFORMATION	
ID No.: DEGREASER4	Applicable Form: OP-UA16
APPLICABLE REGULATORY REQUIREMENT	
Name: 30 TAC Chapter 115, Degreasing Processes	SOP Index No.: R5412-2
Pollutant: VOC	Main Standard: § 115.412(1)
MONITORING INFORMATION	
Indicator: n/a	
Minimum Frequency: Monthly	
Averaging Period: n/a	
Deviation Limit: Visual Inspections	
Periodic Monitoring Text: Inspect equipment and record data monthly to ensure compliance with § 115.412(1)(A)-(F). Any monitoring data collected which indicates that the cold cleaner is not in compliance with § 115.412(1)(A)-(F) shall be considered and reported as a deviation.	

Periodic Monitoring Summary

UNIT/GROUP/PROCESS INFORMATION	
ID No.: DEGREASER5	Applicable Form: OP-UA16
APPLICABLE REGULATORY REQUIREMENT	
Name: 30 TAC Chapter 115, Degreasing Processes	SOP Index No.: R5412-1
Pollutant: VOC	Main Standard: § 115.412(1)
MONITORING INFORMATION	
Indicator: n/a	
Minimum Frequency: Monthly	
Averaging Period: n/a	
Deviation Limit: Visual Inspections	
Periodic Monitoring Text: Inspect equipment and record data monthly to ensure compliance with § 115.412(1)(A)-(F). Any monitoring data collected which indicates that the cold cleaner is not in compliance with § 115.412(1)(A)-(F) shall be considered and reported as a deviation.	

Periodic Monitoring Summary

UNIT/GROUP/PROCESS INFORMATION	
ID No.: GRPLPETK2	Applicable Form: OP-UA03
APPLICABLE REGULATORY REQUIREMENT	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-5
Pollutant: VOC	Main Standard: § 115.112(a)(1)
MONITORING INFORMATION	
Indicator: Pilot Flame	
Minimum Frequency: Once per hour	
Averaging Period: n/a	
Deviation Limit: Presence of Pilot Flame	
<p>Periodic Monitoring Text: Measure and record the presence of the pilot flame or maintain records of alarm events and duration of alarm events. The presence of a flare pilot flame shall be monitored using a thermocouple or any other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. The monitoring instrumentation shall be maintained, calibrated and operated in accordance with manufacturer's specifications or other written procedures. Any monitoring data which indicates the lack of a pilot flame shall be considered and reported as a deviation.</p>	

Periodic Monitoring Summary

UNIT/GROUP/PROCESS INFORMATION	
ID No.: L1TKISOPEN	Applicable Form: OP-UA03
APPLICABLE REGULATORY REQUIREMENT	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-4
Pollutant: VOC	Main Standard: § 115.112(a)(1)
MONITORING INFORMATION	
Indicator: Pilot Flame	
Minimum Frequency: Once per hour	
Averaging Period: n/a	
Deviation Limit: Presence of Pilot Flame	
<p>Periodic Monitoring Text: Measure and record the presence of the pilot flame or maintain records of alarm events and duration of alarm events. The presence of a flare pilot flame shall be monitored using a thermocouple or any other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. The monitoring instrumentation shall be maintained, calibrated and operated in accordance with manufacturer's specifications or other written procedures. Any monitoring data which indicates the lack of a pilot flame shall be considered and reported as a deviation.</p>	

[Faint, illegible text from the reverse side of the page]

Permit Shield

Permit Shield.....61

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
DEGREASER4	N/A	40 CFR Part 63, Subpart T	Is not a solvent cleaning machine that uses any solvent containing methylene chloride, perchloroethylene, trichloroethylene, 1,1,1-trichloroethane, carbon tetrachloride or chloroform, or any combination >5% weight as a cleaning and/or drying agent.
DEGREASER5	N/A	40 CFR Part 63, Subpart T	Is not a solvent cleaning machine that uses any solvent containing methylene chloride, perchloroethylene, trichloroethylene, 1,1,1-trichloroethane, carbon tetrachloride or chloroform, or any combination >5% weight as a cleaning and/or drying agent.
ENG01FF	N/A	30 TAC Chapter 117, Subchapter B	Units exempted from the provisions of this division include stationary gas turbines and engines operated exclusively for firefighting.
ENG02GEN	N/A	30 TAC Chapter 117, Subchapter B	Units exempted from this division include stationary internal combustion engines located in the HBA nonattainment area with a horsepower rating < 150 hp.
GRPLPEPOL1	PROLDFIN1, PROLDFIN3, PROLDPS	40 CFR Part 60, Subpart DDD	Unit was not constructed, modified, or reconstructed after 9/30/1987.
GRPLPETK1	L1TK24137, L1TK24138	30 TAC Chapter 115, Storage of VOCs	Located in BPA, DFW, El Paso or HGA; TVP <1.5 psia; and is not an external floating roof per 115.116(a) and 115.114(a)
GRPLPETK1	L1TK24137, L1TK24138	40 CFR Part 60, Subpart Kb	Tank capacity is less than 75 cubic meters
GRPLPETK2	L1TKBUTENE, L1TKHEXENE	40 CFR Part 60, Subpart Ka	Tank does not store petroleum liquids.
L1TK25053	N/A	30 TAC Chapter 115, Storage of VOCs	located in BPA, DFW, El Paso or HGA; TVP<1.5 psia; and is not an external floating roof per 115.116(a) and 115.114(a)
L1TK25053	N/A	40 CFR Part 60, Subpart Kb	Tank capacity is less than 75 cubic meters

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit Group Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
L1TK25054	N/A	30 TAC Chapter 115, Storage of VOCs	Tank is less than 1,000 gallons.
L1TK25054	N/A	40 CFR Part 60, Subpart Kb	Tank capacity is less than 75 cubic meters
L1TK92026	N/A	30 TAC Chapter 115, Storage of VOCs	Located in BPA, DFW, El Paso or HGA; TVP < 1.5 psia; and is not an external floating roof per 115.116(a) and 115.114(a)
L1TK92026	N/A	40 CFR Part 60, Subpart Ka	Capacity < 40,000 gallons
L1TKAST1A	N/A	30 TAC Chapter 115, Storage of VOCs	Tank in fuel dispensing service and less than 25,000 gallons.
L1TKAST1A	N/A	40 CFR Part 60, Subpart Kb	Tank capacity is less than 75 cubic meters
L1TKAST1B	N/A	30 TAC Chapter 115, Storage of VOCs	Located in BPA, DFW, El Paso or HGA; TVP < 1.5 psia; and is not an external floating roof per 115.116(a) and 115.114(a)
L1TKAST1B	N/A	40 CFR Part 60, Subpart Kb	Tank capacity is less than 75 cubic meters
L1TKISOPEN	N/A	40 CFR Part 60, Subpart Ka	Tank does not store petroleum liquids.
L1TKV-06151	N/A	30 TAC Chapter 115, Storage of VOCs	Located in BPA, DFW, El Paso or HGA; TVP < 1.5 psia; and is not an external floating roof per 115.116(a) and 115.114(a)
L1TKV-06151	N/A	40 CFR Part 60, Subpart Kb	Tank capacity is less than 75 cubic meters
DBLR1	N/A	40 CFR Part 60, Subpart D	Heat input for fossil fuel fired steam generating unit is less than or equal to 250 MMBtu/hr
LDBLR1	N/A	40 CFR Part 60, Subpart Db	Unit was constructed, modified, or reconstructed before June 19, 1984
LDBLR1	N/A	40 CFR Part 60, Subpart Dc	Unit was constructed, modified, or reconstructed before June 9, 1989
LDBLR2	N/A	40 CFR Part 60, Subpart D	Heat input rate for fossil fuel fired steam generating unit is less than or equal to 250 MMBtu/hr
LDBLR2	N/A	40 CFR Part 60, Subpart Db	Unit was constructed, modified, or reconstructed before June 19, 1984

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
LDBLR2	N/A	40 CFR Part 60, Subpart Dc	Unit was constructed, modified or reconstructed before June 9, 1989
LDFLARE	N/A	30 TAC Chapter 117, Subchapter B	Units exempted from the provisions of this division include flares, incinerators, and fume abators.

New Source Review Authorization References

New Source Review Authorization References65

New Source Review Authorization References by Emission Unit.....66

New Source Review Authorization References

The New Source Review authorizations listed in the table below are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

PSD Permits	NA Permits
PSD Permit No.:	NA Permit No.:
Title 30 TAC Chapter 116 Permits, Special Permits, and Other Authorizations (Other Than Permits By Rule, PSD Permits, or NA Permits) for the Application Area.	
Authorization No.: 4831	Authorization No.: 77687
Authorization No.: 47243	Authorization No.:
Authorization No.:	Authorization No.:
Permits By Rule (30 TAC Chapter 106) for the Application Area	
Number: 075	Version No./Date: 01/08/1980
Number: 106.183	Version No./Date: 09/04/2000
Number: 106.262	Version No./Date: 09/04/2000
Number: 106.412	Version No./Date: 03/14/1997
Number: 106.454	Version No./Date: 03/14/1997
Number: 106.472	Version No./Date: 09/04/2000
Number: 106.473	Version No./Date: 09/04/2000
Number: 106.473	Version No./Date: 01/01/2001
Number: 106.511	Version No./Date: 03/14/1997
Number: 106.511	Version No./Date: 09/04/2000
Municipal Solid Waste and Industrial Hazardous Waste Permits With an Air Addendum	
Permit No.:	Permit No.:

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
DEGREASER4	DEGREASER #4	106.454/03/14/1997
DEGREASER5	DEGREASER #5	106.454/03/14/1997
NG01FF	FIRE WATER DIESEL ENGINE	106.511/03/14/1997
ENG02GEN	EMERGENCY ELECTRICAL GENERATOR	106.511/03/14/1997
HEXDDRYREGN	HEXANE DRYER REGENERATION VENT	4831
L1ANALYZER	LOW DENSITY LPE ANALYZER VENTS	4831
L1ANCATE2	O2 ANALYZER IN CATALYST AREA	4831
L1ANCATM1	O2 ANALYZER IN CATALYST AREA	4831
L1BF05123	LOW DENSITY RF-05123 VENT FILTER	4831
L1BF05223	LOW DENSITY RF-05223 VENT FILTER	4831
L1BF23127	LOW DENSITY E2 FEED HOPPER FILTER	4831
L1BF24001	LOW DENSITY E3 FEED BIN FILTER	4831
L1BF24002	LOW DENSITY E3 FEED BIN FILTER	4831
L1BF24003	LOW DENSITY E3 FEED BIN FILTER	4831
L1BF24010	LOW DENSITY E3 FEED HOPPER AND M/B CONVEYOR FILTER	4831
L1BF24157	LOW DENSITY E3 MASTERBLEND RESIN BIN FILTER	4831
L1BF25034	E4 RESIN SCREW CONVEYOR AND FEED HOPPER FILTER	4831
L1BF25040	LOW DENSITY E4 FEED BIN FILTER	4831
L1BF30108	LOW DENSITY GRANULAR WEIGH BIN FILTER	4831
L1BF30109	LOW DENSITY GRANULAR WEIGH BIN FILTER	4831
L1BF30110	LOW DENSITY GRANULAR WEIGH BIN FILTER	4831
L1BF30123	LOW DENSITY GRANULE BLENDER FILTER	4831
L1BF30124	LOW DENSITY GRANULE BLENDER FILTER	4831
L1BF30125	LOW DENSITY GRANULE BLENDER FILTER	4831
L1BF30126	LOW DENSITY O/S PELLET BLENDER FILTER	4831

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
L1BF30127	LOW DENSITY GRANULES FILTER RECEIVER	4831
L1BF30138	LOW DENSITY COMMON FILTER RECEIVER	4831
L1BF30208	LOW DENSITY PELLET WEIGH BIN FILTER	4831
L1BF30209	LOW DENSITY PELLET WEIGH BIN FILTER	4831
L1BF30210	LOW DENSITY PELLET WEIGH BIN FILTER	4831
L1BF30211	LOW DENSITY PELLET WEIGH BIN FILTER	4831
L1BF30223	LOW DENSITY PELLET BLENDER FILTER	4831
L1BF30224	LOW DENSITY PELLET BLENDER FILTER	4831
L1BF30225	LOW DENSITY PELLET BLENDER FILTER	4831
L1BF30226	LOW DENSITY PELLET BLENDER FILTER	4831
L1BF30227	LOW DENSITY PELLET RECIEVER FILTER	4831
L1BF33101	LOW DENSITY GRANULE RECIEVER FILTER	4831
L1BF33201	LOW DENSITY PELLET RECIEVER FILTER	4831
L1BF33503	LOW DENSITY SCALPERATOR VENT FILTER	4831
L1BF37107	LOW DENSITY PELLET RECEIVER VENT	4831
L1BFE2ADD1	LOW DENSITY E3 COMMON ADDITIVE VENT #1	4831
L1BN24018	LOW DENSITY E3 PELLET PICKUP HOPPER VENT	4831
L1CL281JV1	LOW DENSITY SCALPERATOR CYCLONE VENT	4831
L1CL281JV2	LOW DENSITY SCALPERATOR CYCLONE VENT	4831
L1CPVBOILR	LOW DENSITY COMMON PROCESS VENT TO BOLIER #1	4831
L1CPVFLARE	LOW DENSITY SINGLE COMMON PROCESS VENT TO A FLARE	4831
L1CYV580J	LOW DENSITY ELUTRIATOR CYCLONE VENT	4831
L1DR23117	LOW DENSITY E2 PELLET DRYER VENT	4831
L1DR24012	LOW DENSITY E3 PELLET DRYER VENT	4831
L1DR25010	LOW DENSITY E4 PELLET DRYER VENT	4831
L1ME33263	LOW DENSITY O/S LOADING CYCLONE	4831

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
L1SF03252	LOW DENSITY CATALYST LOADING STATION #1	4831
L1SF03327	LOW DENSITY CATALYST LOADING STATION #2	4831
L1SF03352	LOW DENSITY CATALYST LOADING STATION #3	4831
L1SF04147	LOW DENSITY CATALYST HOLD TANK FILTER	47243
L1SF04148	LOW DENSITY CATALYST HOLD TANK FILTER	4831
L1SF04172	LOW DENSITY CATALYST VENT FILTER	4831
L1SF06112	LOADING STATION VENT FILTER	4831, 106.262/09/04/2000
L1SF06113	LOADING STATION VENT FILTER	4831, 106.262/09/04/2000
L1SF06117	MPS-1 LOADING STATION VENT FILTER	4831
L1SFR1CAT1	LOW DENSITY COMMON REACTOR 1 CATALYST VENT #1	4831
L1SFR2CAT1	LOW DENSITY COMMON REACTOR 2 CATALYST VENT #1	4831
L1TK24137	E3 BULK A/O STORAGE TANK	4831
L1TK24138	E3 BULK A/O STORAGE TANK	4831
L1TK25053	E4 A/O STORAGE TANK	4831
L1TK25054	E4 A/O MELT TANK	4831
L1TK25055	LOW DENSITY E4 ANTI-OXIDANT MELT DAY PROCESS TANK	4831
L1TK92026	ANIONIC POLYELECTROLYTE STORAGE TANK	106.473/01/01/2001
L1TKAST1A	GASOLINE TANK	4831, 106.473/09/04/2000
L1TKAST1B	DIESEL TANK	4831, 106.472/09/04/2000
L1TKBUTENE	BUTENE PRESSURE TANK	4831
L1TKHEXENE	HEXENE PRESSURE TANK	4831
L1TKV-06151	TOLUENE ACCUMULATOR	106.262/09/04/2000, 106.473/09/04/2000
L1TO6A04	LOW DENSITY OXYGEN ANALYZER VENT	106.262/09/04/2000
L1TOA492	LOW DENSITY REACTOR 1 ANALYZER	4831
L1TOA891	LOW DENSITY REACTOR 2 ANALYZER VENT	4831
L1V33105V1	LOW DENSITY A/O MELT TANK	4831

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
L1V33105V2	LOW DENSITY E1 A/O FEED TANK (TRL)	4831
L1V33205V1	LOW DENSITY A/O MELT TANK	4831
L1V33205V2	LOW DENSITY E1 A/O FEED TANK	4831
L1VD01427	LOW DENSITY E1 PELLET PICKUP HOPPER VENT	4831
L1VD02427	LOW DENSITY E2 O/S PELLET PICKUP HOPPER VENT	4831
L1VV03243	LOW DENSITY TOB BLOW TANK	4831
L1VV03301	LOW DENSITY REDUCTION BLOW TANK	4831
L1VV03302	LOW DENSITY CATALYST STORAGE BIN V-03302	4831
L1VV03303	LOW DENSITY CATALYST STORAGE BIN V-03303	4831
L1VV03304	LOW DENSITY CATALYST STORAGE BIN V-03304	4831
L1VV03305	LOW DENSITY CATALYST STORAGE BIN V-03305	4831
L1VV03306	LOW DENSITY CATALYST STORAGE BIN V-03306	4831
L1VV03307	LOW DENSITY CATALYST STORAGE BIN V-03307	4831
L1YD01310	LOW DENSITY E1 PELLET DRYER VENT	4831
L1YF01310A	LOW DENSITY EXTRUDER FEED BIN 1A	4831
L1YF01310B	LOW DENSITY EXTRUDER FEED BIN 1B	4831
L1YF01310D	LOW DENSITY EXTRUDER FEED BIN 1D	4831
L1YF01328	LOW DENSITY E1 FEED HOPPER FILTER	4831
L1YF01416A	LOW DENSITY PELLET BLENDER 1A FILTER	4831
L1YF01416B	LOW DENSITY PELLET BLENDER 1B FILTER	4831
L1YF01416C	LOW DENSITY PELLET BLENDER 1C FILTER	4831
L1YF02310A	LOW DENSITY E2 O/S PELLET BIN FILTER	4831
L1YF02310D	LOW DENSITY E2 GRANULAR FEED BIN FILTER	4831
L1YF02416A	LOW DENSITY PELLET BLENDER 2A FILTER	4831
L1YF02416B	LOW DENSITY PELLET BLENDER 2B FILTER	4831
L1YF03416A	LOW DENSITY PELLET BLENDER 3A FILTER	4831

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
LIYF03416B	LOW DENSITY PELLET BLENDER 3B FILTER	4831
LDBLR1	LPE BOILER #1	4831
LDBLR2	LPE BOILER #2	4831
DCOOLTWR	COOLING TOWER	4831
LDFLARE	LPE PROCESS FLARE	4831
LDFUGEM	LOW DENSITY FUGITIVES	4831
LDFUGHRVOC	LOW DENSITY HRVOC FUGITIVES	4831
LKOVESSEL	LIQUID KNOCKOUT VESSEL (V-03225)	4831
LL1SF03539	CATALYST LOADING STATION	4831
LL1SF03540	CATALYST LOADING STATION	4831
LL1SF03541	CATALYST LOADING STATION	4831
LL1SF03542	CATALYST LOADING STATION	4831
LL1SF03543	CATALYST LOADING STATION	4831
LOAD8TOL	TOLUENE LOADING	4831, 106.262/09/04/2000, 106.473/09/04/2000
LOADBUT	BUTENE LOADING	4831
MR&RSVNT	MATERIAL RECOVERY & RECYCLE SYSTEM VENTS	4831
ROLDFIN1	LOW DENSITY PRODUCT FINISHING-1	4831
PROLDFIN2	LOW DENSITY PRODUCT FINISHING-2	4831
PROLDFIN3	LOW DENSITY PRODUCT FINISHING-3	4831
PROLDFIN4	LOW DENSITY PRODUCT FINISHING-4	4831
PROLDMR	LOW DENSITY MATERIAL RECOVERY	4831
PROLDPOLY	LOW DENSITY POLYMERIZATION	4831
PROLDPS	LOW DENSITY PRODUCT STORAGE	4831
PROLDRMP	LOW DENSITY RAW MATERIAL PREPARATION	4831
PROSF01	SURFACE COATING	075/01/08/1980
PURGERVNT	PURGER VENT	4831

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
REACTORVNT	REACTOR VENT	4831
SC&RFVNT	SCREENER/ROTARY FEEDER VENTS	4831
TEMPBOILER	TEMPORARY BOILER	106.183/09/04/2000

APPENDIX A

Acronym List.....73

Acronym List

The following abbreviations or acronyms may be used in this permit:

ACFM	actual cubic feet per minute
AMOC	alternate means of control
ARP	Acid Rain Program
ASTM	American Society of Testing and Materials
B/PA	Beaumont/Port Arthur (nonattainment area)
CAM	Compliance Assurance Monitoring
CD	control device
COMS	continuous opacity monitoring system
CVS	closed-vent system
D/FW	Dallas/Fort Worth (nonattainment area)
DR	Designated Representative
EIP	El Paso (nonattainment area)
EP	emission point
EPA	U.S. Environmental Protection Agency
EU	emission unit
FCAA Amendments	Federal Clean Air Act Amendments
FOP	federal operating permit
GF	grandfathered
gr/100 scf	grains per 100 standard cubic feet
HAP	hazardous air pollutant
H/G	Houston/Galveston (nonattainment area)
H ₂ S	hydrogen sulfide
ID No.	identification number
lb/hr	pound(s) per hour
MMBtu/hr	Million British thermal units per hour
MRRT	monitoring, recordkeeping, reporting, and testing
NA	nonattainment
N/A	not applicable
NADB	National Allowance Data Base
NO _x	nitrogen oxides
NSPS	New Source Performance Standard (40 CFR Part 60)
NSR	New Source Review
ORIS	Office of Regulatory Information Systems
Pb	lead
PBR	Permit By Rule
PM	particulate matter
ppmv	parts per million by volume
PSD	prevention of significant deterioration
RO	Responsible Official
SO ₂	sulfur dioxide
TSP	total suspended particulate
TVP	true vapor pressure
U.S.C.	United States Code
VOC	Volatile organic compound

1. The first part of the document discusses the importance of maintaining accurate records of all transactions. This is essential for ensuring the integrity of the financial data and for providing a clear audit trail.

2. The second part of the document outlines the various methods used to collect and analyze data. These methods include direct observation, interviews, and the use of specialized software tools.

3. The third part of the document describes the results of the data collection and analysis. It shows that there is a significant correlation between the variables being studied, which supports the hypothesis.

4. The fourth part of the document discusses the implications of the findings. It suggests that the results could be used to inform policy decisions and to guide future research in this area.

5. The fifth part of the document provides a conclusion and summarizes the key points of the study. It emphasizes the need for further research to explore the underlying mechanisms of the observed relationships.

6. The sixth part of the document includes a list of references to the sources used in the study. These references provide additional context and support for the findings presented in the document.

7. The final part of the document contains a list of appendices, which provide additional data and details that are not included in the main text of the document.

8. The eighth part of the document discusses the limitations of the study. It acknowledges that the sample size was relatively small and that the study was conducted in a specific context, which may limit the generalizability of the findings.

9. The ninth part of the document outlines the future research agenda. It suggests that further studies should be conducted to explore the relationships between the variables in greater detail and to test the findings in different contexts.

10. The tenth part of the document provides a final summary of the document. It reiterates the main findings and the importance of the research for the field.

11. The eleventh part of the document includes a list of acknowledgments, thanking the individuals and organizations that provided support and assistance during the course of the study.

12. The twelfth part of the document contains a list of contact information for the author, including an email address and a phone number, for those who wish to reach out for more information.

13. The thirteenth part of the document includes a list of footnotes, providing additional information and references for the text in the document.

14. The final part of the document is a list of appendices, which provide additional data and details that are not included in the main text of the document.