

Texas Commission on Environmental Quality
Table 11 Instructions

A. Emission Point Number (EPN) and Emission Point Name:

- Identify the EPN and name for the location that air contaminants enter the atmosphere. The EPNs must be consistent with the emission point identification used on the plot plan, any previous permits, and the “Emissions Inventory Questionnaire.”

B. Manufacturer and Model Number:

- Enter the company brand name and model number. Include manufacturer’s specifications or brochure, if available.

C. Name of Source(s) or Equipment Being Controlled:

- Enter the name of the source(s) or equipment being controlled. Associate the EPN to the appropriate facility(ies) with facility identification number(s) (FIN), or a description of the process or equipment being controlled. If using FINs, these numbers can be alphanumeric and maximum of 10 characters. Please note that no two distinct facilities may share the same FIN. The FINs must match those on your permit.

D. Type of Particulate Controlled:

- List each component or air contaminant name. Examples of component names are; lead, sand, clay, iron dust, and cement dust.

E. Gas Stream Characteristics

- Include the design maximum flow rate in units of actual cubic feet per minute (acfm), the average flow rate expected in acfm;
- Enter the temperature of the exhaust gas stream from the baghouse;
- Enter the amount of particulate matter in the inlet and outlet gas stream. The inlet and outlet particulate grain loading in grains per dry standard cubic foot (scf).
- Enter the pressure drop across the baghouse measured in inches of water column.
- Enter the water vapor content of the exhaust stream measured in pounds of water per pound of dry air.
- Enter the fan motor requirements in horsepower and the fan capacity in acfm.

F. Particulate Distribution (By Weight)

- Enter the particle size distribution as determined through laboratory analysis in units of microns (micrometers).

G. Filter Characteristics

- Filtering velocity in units of acfm of air stream flow divided by the total surface area of the filtering media in square feet (ft²). The filtering velocity can also be expressed in units of feet per minute (fpm).
- Enter the bag diameter expressed in units of inches.
- Enter the length of the filter bags in units of feet.
- Enter the quantity of bags used in the filtering of the air stream.

H. Bag Rows

- Enter the pattern or arrangement of the baghouse bag filter rows. Indicate the arrangement of the baghouse bag filter rows. Select staggered or straight.

I. Walkways

- Enter "YES" if there will be space available between the rows of bag filters to provide access for inspection and maintenance. Otherwise, enter "NO."

J. Material

- Identify the filtering media and include any additional coating or treatment of the baghouse material.

K. Cleaning

- Explain the method of bag filter cleaning. Typically, there are mechanical shakers or reverse pulse air jets.

L. Cost

- Identify the capital cost of installation of the baghouse. This includes all engineering design costs and construction costs associated with the establishment of the control device.
- Estimate the annual operating expenses for the baghouse, including utility expense and replacement bag costs.

Note: The Texas Commission on Environmental Quality standard conditions are 68° F and 14.7 PSIA (Title 30 Texas Administrative Code § 101.1).

**Texas Commission on Environmental Quality
Table 11
Fabric Filters**

Tables, checklists, and guidance documents pertaining to air quality permits are available from the Texas Commission on Environmental Quality (TCEQ) Air Permits Division (APD) website at www.tceq.texas.gov/permitting/air.

A. Emission Point Number (EPN) and Emission Point Name				
EPN:		Emission Point Name:		
B. Manufacturer and Model Numbers (No.)				
Manufacturer No.:		Model No.:		
C Name of Source(s) or Equipment Being Controlled				
Name	EPN	FIN		
D. Type of Particulate Controlled				
E. Gas Stream Characteristics				
Design Maximum	Average Expected Flow Rate (acfm)	Gas Stream Temperature (°F)	Particulate Grain Loading (grain/scf)	
			Inlet:	Outlet:
Pressure Drop (inches of H ₂ O)	Water Vapor Content of Effluent Stream (lb water/lb dry air)		Fan Requirements	
			hp:	ft ³ /min.:
F. Particulate Distribution (By Weight)				
Micron Range	Inlet %	Outlet %		
0.0-0.5				
0.5-1.0				
1.0-5.0				
5-10				
10-20				
over 20				
G. Filter Characteristics				
Filtering Velocity (acfm/ft ² of Cloth)	Bag Diameter (inches)	Bag Length (feet)	Total Number of Bags	

Texas Commission on Environmental Quality
Table 11
Fabric Filters

H. Bag Rows	
Indicate the arrangement of the baghouse bag filter rows.	<input type="checkbox"/> Staggered <input type="checkbox"/> Straight
I. Walkways	
Will walkways be provided between banks of bags?	<input type="checkbox"/> YES <input type="checkbox"/> NO
J. Filtering Material	
Identify the filtering media:	
Any additional coating or treatment of the baghouse material:	
K. Cleaning of the Filter(s)	
Describe Bag Cleaning Method and Cycle:	
L. Cost	
Capital Installed Cost:	
Annual Operating Cost:	

Note: Attach the details regarding the principle of operation and an assembly drawing (front and top view) of the abatement device drawn to scale clearly showing the design, size and shape.
If the device has bypasses, safety valves, etc., include in the drawing and specify when such bypasses are to be used and under what conditions.