

40 CFR Part 60, Subpart F - Requirements Reference Tables

Subpart F Standards

- [§60.62\(a\)\(1\)\(i\)](#) Particulate matter limits for kilns constructed, reconstructed, or modified after August 17, 1971 but on or before June 16, 2008.
- [§60.62\(a\)\(1\)\(ii\)](#) Particulate matter limits for kilns constructed, reconstructed, or modified after June 16, 2008.
- [§60.62\(a\)\(2\)|1](#) Opacity limits for kilns constructed, reconstructed, or modified after August 17, 1971 but on or before June 16, 2008 that do not use a PM continuous emissions monitoring system (CEMS).
- [§60.62\(a\)\(2\)|2](#) Opacity limits for kilns in which the kiln and clinker cooler exhaust are combined for energy efficiency purposes and sent to a single control device that do not use a PM continuous emissions monitoring system (CEMS).
- [§60.62\(a\)\(3\)](#) NO_x limits for kilns constructed, reconstructed, or modified after June 16, 2008.
- [§60.62\(b\)\(3\)](#) Particulate matter limits for the kiln and clinker combined cooler exhaust for energy efficiency purposes.
- [§60.62\(a\)\(4\)|1](#) SO₂ limits for kilns constructed, reconstructed, or modified after June 16, 2008 that are complying with the limit of pounds of SO₂ per ton of clinker on a 30-operating day rolling average.
- [§60.62\(a\)\(4\)|2](#) SO₂ limits for kilns constructed, reconstructed, or modified after June 16, 2008 that are complying with the limit of greater than the 90 percent SO₂ emissions reduction measured across the SO₂ control device.
- [§60.62\(b\)\(1\)\(i\)](#) Particulate matter limits for clinker coolers constructed, reconstructed, or modified after August 17, 1971 but on or before June 16, 2008.
- [§60.62\(b\)\(1\)\(ii\)](#) Particulate matter limits for clinker coolers constructed, reconstructed, or modified after June 16, 2008.
- [§60.62\(b\)\(2\)](#) Opacity limits for clinker coolers constructed, reconstructed, or modified after August 17, 1971 but on or before June 16, 2008 that do not use a PM continuous emissions monitoring system (CEMS).
- [§60.62\(b\)\(3\)](#) Alternative particulate matter limits for kilns in which the kiln and clinker cooler exhaust are combined for energy efficiency purposes and sent to a single control device.
- [§60.62\(c\)](#) Opacity limits for raw mill system, finish mill system, raw mill dryer, raw material storage, clinker storage, finished product storage, conveyor transfer points, bagging and bulk loading and unloading systems.
- [§60.62\(d\)|1](#) An affected source subject to this subpart with a different emission limit or requirement for particulate matter under another regulation in title 40 of this chapter must comply with the most stringent emission limit or requirement and are not subject to the less stringent requirement.
- [§60.62\(d\)|2](#) An affected source subject to this subpart with a different emission limit or requirement for Opacity under another regulation in title 40 of this chapter must comply with the most stringent emission limit or requirement and are not subject to the less stringent requirement.
- [§60.62\(d\)|3](#) An affected source subject to this subpart with a different emission

limit or requirement for NO_x under another regulation in title 40 of this chapter, must comply with the most stringent emission limit or requirement and are not subject to the less stringent requirement.

- [§60.62\(d\)|4](#) An affected source subject to this subpart with a different emission limit or requirement for SO₂ under another regulation in title 40 of this chapter must comply with the most stringent emission limit or requirement and are not subject to the less stringent requirement
-

These relationship entry screens and flowcharts are for use by sources subject to the Texas Federal Operating Permits Program only and are subject to revision.

Last Modified: September 25, 2012