

## **40 CFR Part 60, Subpart Na - Requirements Reference Tables**

### **Subpart Na Standards**

- [§60.142a\(a\)\(1\)](#) Facilities shall not exhibit 10% or greater, except as stated in §60.142a(a)(1)
- [§60.142a\(a\)\(2\)](#) Emission limitation for top or bottom blown BOPF control device is 23mg/dscm

These relationship entry screens and flowcharts are for use by sources subject to the Texas Federal Operating Permits Program only and are subject to revision.

Last Modified: September 1, 1999



Document: Below is a Relationship Entry Screen Table describing 40 CFR Part 60, Subpart Na. It will likely not be accessible using a screen reader. For the text of the statute/rule, please go to [40 CFR Part 60, Subpart Na](#)

Standard	Monitoring/Testing	Recordkeeping	Reporting
§60.142a(a)(1) <i>[D]</i> §60.142a(a)(3) {§60.142a(b)} {§60.142a(c)} <i>[D]</i> §60.145a(a) <i>[R]</i> §60.145a(b) <i>[R]</i> §60.145a(c) <i>[R]</i> §60.145a(d) <i>[R]</i> §60.145a(e) <i>[D]</i> §60.145a(g)	<i>[R]</i> §60.143a(a) <i>[R]</i> §60.143a(b) <i>[R]</i> §60.143a(c) <i>[R]</i> §60.143a(d) <i>[D]</i> §60.143a(e) <i>[R]</i> §60.144a(a) <i>[R]</i> §60.144a(b)(1) <i>[GR]</i> §60.144a(b)(3) <i>[GR]</i> §60.144a(c) <i>[R]</i> §60.144a(d)	<i>[R]</i> §60.143a(a) <i>[R]</i> §60.144a(b)(1) <i>[GR]</i> §60.144a(b)(3)	<i>[R]</i> §60.143a(d) <i>[D]</i> §60.143a(e)
§60.142a(a)(2) {§60.142a(b)} {§60.142a(c)} <i>[R]</i> §60.145a(a) <i>[R]</i> §60.145a(b) <i>[R]</i> §60.145a(c) <i>[R]</i> §60.145a(f)	<i>[R]</i> §60.143a(a) <i>[R]</i> §60.143a(b) <i>[R]</i> §60.143a(c) <i>[R]</i> §60.143a(d) <i>[R]</i> §60.144a(a) <i>[R]</i> §60.144a(b)(1) <i>[R]</i> §60.144a(b)(2) <i>[GR]</i> §60.144a(c) <i>[R]</i> §60.144a(d)	<i>[R]</i> §60.143a(a) <i>[R]</i> §60.144a(b)(1)	<i>[R]</i> §60.143a(d)