

## 40 CFR Part 60, Subpart OOOOa - Requirements Reference Tables

### Subpart OOOOa Standards

- [§60.5375a\(a\)](#) Well completion operation with hydraulic fracturing at a non-low pressure, non-delineation, or non-wildcat well
- [§60.5375a\(f\)](#) Well completion operation with hydraulic fracturing at a wildcat well, delineation well, non-wildcat low pressure well, or non-delineation low pressure well
- [§60.5375a\(g\)](#) Well affected facility with less than 300 scf of gas per stock tank barrel of oil produced
- [§60.5380a\(a\)\(1\)](#) Centrifugal compressor
- [§60.5385a\(a\)\(1\)](#) Reciprocating compressor where rod packing is replaced on or before the compressor has operated for 26,000 hours
- [§60.5385a\(a\)\(2\)](#) Reciprocating compressor where rod packing is replaced prior to 36 months from the date of the most recent rod packing replacement or 36 months from the date of initial startup
- [§60.5385a\(a\)\(3\)](#) Reciprocating compressor where emissions are collected and routed to a process through a closed vent system
- [§60.5390a\(a\)](#) Exemption for pneumatic controller
- [§60.5390a\(b\)\(1\)](#) Pneumatic controller at a natural gas processing plant
- [§60.5390a\(c\)\(1\)](#) Pneumatic controller at a location other than a natural gas processing plant
- [§60.5393a\(b\)](#) Pneumatic pump located at a well site where emissions are routed to a process or control device achieving 95 percent reduction
- [§60.5393a\(b\)\(3\)](#) Pneumatic pump located at a well site with no control device
- [§60.5393a\(b\)\(4\)](#) Pneumatic pump located at a well site with control device unable to achieve 95 percent reduction
- [§60.5393a\(b\)\(5\)](#) Pneumatic pump located at a well site where routing emissions to a control device or process is technically infeasible
- [§60.5395a\(a\)\(2\)](#) Storage vessel where VOC emissions are reduced by 95% percent
- [§60.5395a\(a\)\(3\)](#) Storage vessel where uncontrolled actual VOC emissions are maintained at less than 4 tpy
- [§60.5397a|1](#) Collection of fugitive emission components at a well site
- [§60.5397a|2](#) Collection of fugitive emission components at a compressor station
- [§60.5398a\(a\)](#) Alternative standard for well affected facilities, reciprocating compressors, or collection of fugitive emission components at a well site or compressor station
- [§60.5399a\(l\)](#) Alternative standard for collection of fugitive emission components at a well site
- [§60.5399a\(m\)](#) Alternative standard for collection of fugitive emission components at a compressor station
- [§60.5400a\(a\)|3](#) Equipment in vacuum service located at an onshore natural gas processing plant
- [§60.5400a\(a\)|4](#) Pumps in light liquid service located at an onshore natural gas processing plant
- [§60.5400a\(a\)|5](#) Pressure relief devices in gas/vapor service located at an onshore natural gas processing plant
- [§60.5400a\(a\)|7](#) Open-ended valves or lines located at an onshore natural gas processing plant
- [§60.5400a\(a\)|8](#) Valves in gas/vapor service or light liquid service located at an onshore

- natural gas processing plant
- [§60.5400a\(a\)9](#) Pumps in heavy liquid service located at an onshore natural gas processing plant
- [§60.5400a\(a\)10](#) Valves in heavy liquid service located at an onshore natural gas processing plant
- [§60.5400a\(a\)11](#) Connectors in heavy liquid service located at an onshore natural gas processing plant
- [§60.5400a\(a\)12](#) Pressure relief devices in light liquid or heavy liquid service located at an onshore natural gas processing plant
- [§60.5400a\(a\)13](#) Vapor recovery systems located at an onshore natural gas processing plant
- [§60.5400a\(a\)14](#) Enclosed combustion devices located at an onshore natural gas processing plant
- [§60.5400a\(a\)15](#) Flares located at an onshore natural gas processing plant
- [§60.5400a\(a\)16](#) Closed vent systems located at an onshore natural gas processing plant
- [§60.5400a\(a\)17](#) Connectors in gas and vapor and light liquid service located at an onshore natural gas processing plant
- [§60.5400a\(b\)](#) Alternative standard for valves located at an onshore natural gas processing plant
- [§60.5400a\(c\)](#) Alternative standard for fugitive components located at an onshore natural gas processing plant
- [§60.5405a\(b\)-Table 2](#) Sweetening unit located at an onshore natural gas processing plant
- [§60.5365a\(g\)\(3\)](#) Exemption for sweetening unit

These relationship entry screens and flowcharts are for use by sources subject to the Texas Federal Operating Permits Program only and are subject to revision.

Last modified: June 15, 2021