

40 CFR Part 63, Subpart HH - Requirements Reference Tables

Subpart HH Standards

- [§63.760\(g\)\(2\)](#) Standards for ancillary equipment and compressors subject to 40 CFR part 61, subpart V.
- [§63.760\(g\)\(3\)](#) Standards for ancillary equipment and compressors subject to 40 CFR part 63, subpart H.
- [§63.764\(d\)\(2\)\(ii\)](#) TEG dehydration unit located at an area source that is not located within an UA plus offset and UC boundary.
- [§63.764\(e\)\(1\)\(i\)](#) Exempt as determined by the procedures specified in §63.772(b)(1).
- [§63.764\(e\)\(1\)\(ii\)](#) Exempt as determined by the procedures specified in §63.772(b)(2).
- [§63.764\(e\)\(2\)\(i\)](#) Exempt as determined by the procedures specified in §63.772(a).
- [§63.764\(e\)\(2\)\(ii\)](#) Exemption if operated in VHAP service less than 300 hours per calendar year.
- [§63.765\(b\)\(1\)\(i\)](#) Standard for glycol dehydration unit process vent connected to a control device or a combination of control devices through a closed-vent system.
- [§63.765\(b\)\(1\)\(ii\)](#) Standard for glycol dehydration unit process vent connected to a control device or a combination of control devices through a closed-vent system and benzene emissions reduced to a level less than 0.90 megagrams per year.
- [§63.765\(b\)\(1\)\(iii\)|1](#) Standard for glycol dehydration unit process vent limiting BTEX emissions to the limit determined in Equation 1 of §63.765.
- [§63.765\(b\)\(1\)\(iii\)|2](#) Standard for glycol dehydration unit process vent limiting BTEX emissions to the limit determined in Equation 2 of §63.765.
- [§63.765\(c\)\(1\)](#) Alternate standard for glycol dehydration unit process vents.
- [§63.765\(c\)\(2\)](#) Alternate standard glycol dehydration unit process vent reducing HAP emissions by 95.0 percent through process modifications, or a combination of process modifications and one or more control devices.
- [§63.766\(b\)\(1\)](#) Standard for a storage vessel with a cover that is connected, through a closed vent system.
- [§63.766\(b\)\(2\)](#) Standard for a storage vessel operated as a closed system operated with no detectable emissions.
- [§63.766\(b\)\(3\)](#) Standard for a storage vessel connecting the cover, through a closed-vent system to a process natural gas line.
- [§63.766\(d\)|1](#) Storage vessel complying with 40 CFR Part 60, subpart OOOO.
- [§63.769\(b\)](#) Ancillary equipment and compressors complying with 40 CFR Part 60, subpart OOOO.
- [§63.769\(c\)|1](#) Exclusion per [§61.242-1\(e\)](#): Equipment in vacuum service.
- [§63.769\(c\)|18](#) Standards per [§61.242-2](#): Pumps located at a nonfractionating plant with a design capacity <283,000 scm/day per §63.769(c)(5).
- [§63.769\(c\)|3](#) Standards per [§61.242-2](#): Pumps complying with all requirements of §61.242-2.
- [§63.769\(c\)|4](#) Standards per [§61.242-3](#): Compressors.

- [§63.769\(c\)|5](#) Standards per [§61.242-4](#): Pressure relief device located in a nonfractionating facility that is monitored only by non-facility personnel.
- [§63.769\(c\)|6](#) Standards per [§61.242-4](#): Pressure relief device located at a non-fractionating plant with a design capacity <283,000 scm/day.
- [§63.769\(c\)|7](#) Standards per [§61.242-4](#): Pressure relief device complying with all requirements in §61.242-4.
- [§63.769\(c\)|8](#) Standards per [§61.242-6](#): Open-ended valves or lines.
- [§63.769\(c\)|9](#) Standards per [§61.242-7](#): Valves in gas/vapor or light liquid service located at a nonfractionating plant with a design capacity <283,000scm/day.
- [§63.769\(c\)|19](#) Standards per [§61.242-7](#): Valves complying with all requirements in §61.242-7.
- [§63.769\(c\)|11](#) Standards per [§61.242-8](#): Pressure relief devices in liquid service.
- [§63.769\(c\)|12](#) Standards per [§61.242-8](#): Flanges and other connectors.
- [§63.769\(c\)|13](#) Standards per [§61.242-9](#): Product accumulator vessels.
- [§63.769\(c\)|14](#) Standards per [§61.242-11\(b\)](#): Closed-vent systems and vapor recovery systems.
- [§63.769\(c\)|15](#) Standards per [§61.242-11\(c\)](#): Closed-vent systems and enclosed combustion devices.
- [§63.769\(c\)|16](#) Standards per [§61.242-11\(d\)](#): Closed-vent systems and flares.
- [§63.769\(c\)|17](#) Standards per [§61.242-11\(f\)\(1\)](#): Closed-vent systems.
- [§63.769\(c\)|20](#) Alternative means of emission limitation in accordance with §61.242-1(c).
- [§63.777\(a\)](#) Alternative means of emission limitation.

These relationship entry screens and flowcharts are for use by sources subject to the Texas Federal Operating Permits Program only and are subject to revision.

Last modified: June 9, 2015