

## 40 CFR Part 63, Subpart JJ - Requirements Reference Tables

### Subpart JJ Standards

- [§63.800\(b\)\(1\)](#) Exemption for area sources that use no more than 250 gallons per month of the materials specified in §63.800(b)(1)
- [§63.800\(b\)\(2\)](#) Exemption for area sources that use no more than 3000 gallons per rolling 12-month period of the materials specified in §63.800(b)(2)
- [§63.800\(b\)\(3\)](#) Exemption for area sources meeting the criteria specified in §63.800(b)(3)
- [§63.802\(a\)\(1\)](#) VHAP emissions limit for existing sources carrying out finishing operations
- [§63.802\(a\)\(2\)\(i\)](#) VHAP emissions limit for existing sources with foam adhesive operations which meet flammability requirements
- [§63.802\(a\)\(2\)\(ii\)](#) VHAP emissions limit for existing sources all contact adhesive operations
- [§63.802\(a\)\(3\)](#) Emissions limit for existing sources using strippable spray booth coatings
- [§63.802\(a\)\(4\)\(i\)](#) Emissions limit for existing sources using coatings and contact adhesives
- [§63.802\(a\)\(4\)\(ii\)](#) Limit for low-formaldehyde coatings and adhesives, in any existing wood furniture manufacturing operations
- [§63.802\(b\)\(1\)](#) VHAP emissions limit for new sources carrying out finishing operations
- [§63.802\(b\)\(2\)](#) VHAP emissions limit for new sources carrying out adhesive operations
- [§63.802\(b\)\(3\)](#) VHAP emissions limit for new sources using strippable spray booth coatings
- [§63.802\(b\)\(4\)\(i\)](#) Emissions limit for new sources using coatings and contact adhesives
- [§63.802\(b\)\(4\)\(ii\)](#) Limit for low-formaldehyde coatings and adhesives, in any new wood furniture manufacturing operations

These relationship entry screens and flowcharts are for use by sources subject to the Texas Federal Operating Permits Program only and are subject to revision.

Last Modified: February 08, 2013