

30 TAC 111 - Requirements Reference Tables

30 TAC 111 Standards

- [§111.111\(a\)\(4\)\(A\)\(2\)](#) Opacity Limitation < 30% for acid gas flares
- [§111.111\(a\)\(1\)\(A\)1](#) Opacity Limitation < 30%. The emissions from this vent originate from colorless VOCs, non-fuming liquids, or other sources that are not capable of obstructing the transmission of light and therefore no monitoring is required to demonstrate compliance with this standard.
- [§111.111\(a\)\(4\)\(A\)3](#) Opacity Limitation < 20% for acid gas flares for which construction was begun after January 31, 1972
- [§111.111\(a\)\(1\)\(B\)1](#) Opacity Limitation < 20%. The emissions from this vent originate from colorless VOCs, non-fuming liquids, or other sources that are not capable of obstructing the transmission of light and therefore no monitoring is required to demonstrate compliance with this standard.
- [§111.111\(a\)\(1\)\(C\)](#) Opacity Limitation < 15%
- [§111.111\(a\)\(4\)\(A\)1](#) Visible Emissions Requirement for Process Gas Flares
- [§111.113](#) Alternate Opacity Limitations

These relationship entry screens and flowcharts are for use by sources subject to the Texas Federal Operating Permits Program only and are subject to revision.

Last Modified: November 23, 2015