

Statement of Basis of the Federal Operating Permit

Phillips 66 Company

Site Name: Borger Refinery

Physical Location: The facility is located northeast of Borger in Hutchinson County, Texas on Spur 119 (Phillips Rd) one mile from intersection of Spur 245 and Spur 119

Nearest City: Borger

County: Hutchinson

Permit Number: O1440

Project Type: Renewal

Standard Industrial Classification (SIC) Code: 2911

SIC Name: Petroleum Refining

This Statement of Basis sets forth the legal and factual basis for the draft permit conditions in accordance with 30 TAC §122.201(a)(4). Per 30 TAC §§ 122.241 and 243, the permit holder has submitted an application under § 122.134 for permit renewal. This document may include the following information:

- A description of the facility/area process description;
- A basis for applying permit shields;
- A list of the federal regulatory applicability determinations;
- A table listing the determination of applicable requirements;
- A list of the New Source Review Requirements;
- The rationale for periodic monitoring methods selected;
- The rationale for compliance assurance methods selected;
- A compliance status; and
- A list of available unit attribute forms.

Revised on: September 11, 2015

Operating Permit Basis of Determination

Permit Area Process Description

The Borger Refinery process begins when crude oil and recycle streams are desalted. The treated crude is then separated into components using atmospheric distillation. The lighter materials go to another unit for further fractionation in the Natural Gas Liquid (NGL) side. The remaining liquid undergoes further processing. In the desulfurization process, hydrogen reacts over catalyst with sulfur bound in organic molecules to produce H₂S. H₂S containing streams from other refinery and NGL processes are treated at the individual units or in the amine treater, with the purified H₂S going to a unit for sulfur recovery. The HDS units treat refinery streams with hydrogen from the reformer to remove sulfur. Products from this process are used as NGL feed, fractionated at another unit, or blended into final products (furnace oil, jet fuels, stove oil, kerosene, dual purpose fuel oil, etc.)

Heavier streams from the crude units and desulfurization units go to the catalytic cracking units, where long chain hydrocarbons are “cracked” into smaller molecules, which are subsequently fractionated and sent to appropriate further processing or product storage.

NGL products are fuel gas for complex use, petrochemicals, solvents and blend stocks for liquid fuels. Front end fractionation splits the various feed streams by molecular weight. The products of this fractionation process go to the pentane fractionation/isom processes, to a HDS unit, or to the refinery. The pentane processes are designed to maximize the yield of isopentane, which is used mostly as a high-octane blend stock.

FOPs at Site

The “application area” consists of the emission units and that portion of the site included in the application and this permit. Multiple FOPs may be issued to a site in accordance with 30 TAC § 122.201(e). When there is only one area for the site, then the application information and permit will include all units at the site. Additional FOPs that exist at the site, if any, are listed below.

Additional FOPs: O2166

Major Source Pollutants

The table below specifies the pollutants for which the site is a major source:

Major Pollutants	VOC, SO ₂ , PM, NOX, HAPS, CO, GHG
------------------	-----------------------------------------------

Reading State of Texas’s Federal Operating Permit

The Title V Federal Operating Permit (FOP) lists all state and federal air emission regulations and New Source Review (NSR) authorizations (collectively known as “applicable requirements”) that apply at a particular site or permit area (in the event a site has multiple FOPs). **The FOP does not authorize new emissions or new construction activities.** The FOP begins with an introductory page which is common to all Title V permits. This page gives the details of the company, states the authority of the issuing agency, requires the company to operate in accordance with this permit and 30 Texas Administrative Code (TAC) Chapter 122, requires adherence with NSR requirements of 30 TAC Chapter 116, and finally indicates the permit number and the issuance date.

This is followed by the table of contents, which is generally composed of the following elements. Not all permits will have all of the elements.

- General Terms and Conditions
- Special Terms and Conditions

- Emissions Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting
- Additional Monitoring Requirements
- New Source Review Authorization Requirements
- Compliance Requirements
- Protection of Stratosphere Ozone
- Permit Location
- Permit Shield (30 TAC § 122.148)
- Attachments
 - Applicable Requirements Summary
 - Unit Summary
 - Applicable Requirements Summary
 - Additional Monitoring Requirements
 - Permit Shield
 - New Source Review Authorization References
 - Compliance Plan
 - Alternative Requirements
- Appendix A
 - Acronym list
- Appendix B
 - Copies of major NSR authorizations

General Terms and Conditions

The General Terms and Conditions are the same and appear in all permits. The first paragraph lists the specific citations for 30 TAC Chapter 122 requirements that apply to all Title V permit holders. The second paragraph describes the requirements for record retention. The third paragraph provides details for voiding the permit, if applicable. The fourth paragraph states that the permit holder shall comply with the requirements of 30 TAC Chapter 116 by obtaining a New Source Review authorization prior to new construction or modification of emission units located in the area covered by this permit. The fifth paragraph provides details on submission of reports required by the permit.

Special Terms and Conditions

Emissions Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting. The TCEQ has designated certain applicable requirements as site-wide requirements. A site-wide requirement is a requirement that applies uniformly to all the units or activities at the site. Units with only site-wide requirements are addressed on Form OP-REQ₁ and are not required to be listed separately on a OP-UA Form or Form OP-SUM. Form OP-SUM must list all units addressed in the application and provide identifying information, applicable OP-UA Forms, and preconstruction authorizations. The various OP-UA Forms provide the characteristics of each unit from which applicable requirements are established. Some exceptions exist as a few units may have both site-wide requirements and unit specific requirements.

Other conditions. The other entries under special terms and conditions are in general terms referring to compliance with the more detailed data listed in the attachments.

Attachments

Applicable Requirements Summary. The first attachment, the Applicable Requirements Summary, has two tables, addressing unit specific requirements. The first table, the Unit Summary, includes a list of units with applicable requirements, the unit type, the applicable regulation, and the requirement driver. The intent of the

requirement driver is to inform the reader that a given unit may have several different operating scenarios and the differences between those operating scenarios.

The applicable requirements summary table provides the detailed citations of the rules that apply to the various units. For each unit and operating scenario, there is an added modifier called the “index number,” detailed citations specifying monitoring and testing requirements, recordkeeping requirements, and reporting requirements. The data for this table are based on data supplied by the applicant on the OP-SUM and various OP-UA forms.

Additional Monitoring Requirement. The next attachment includes additional monitoring the applicant must perform to ensure compliance with the applicable standard. Compliance assurance monitoring (CAM) is often required to provide a reasonable assurance of compliance with applicable emission limitations/standards for large emission units that use control devices to achieve compliance with applicant requirements. When necessary, periodic monitoring (PM) requirements are specified for certain parameters (i.e. feed rates, flow rates, temperature, fuel type and consumption, etc.) to determine if a term and condition or emission unit is operating within specified limits to control emissions. These additional monitoring approaches may be required for two reasons. First, the applicable rules do not adequately specify monitoring requirements (exception- Maximum Achievable Control Technology Standards (MACTs) generally have sufficient monitoring), and second, monitoring may be required to fill gaps in the monitoring requirements of certain applicable requirements. In situations where the NSR permit is the applicable requirement requiring extra monitoring for a specific emission unit, the preferred solution is to have the monitoring requirements in the NSR permit updated so that all NSR requirements are consolidated in the NSR permit.

Permit Shield. A permit may or may not have a permit shield, depending on whether an applicant has applied for, and justified the granting of, a permit shield. A permit shield is a special condition included in the permit document stating that compliance with the conditions of the permit shall be deemed compliance with the specified potentially applicable requirement(s) or specified applicable state-only requirement(s).

New Source Review Authorization References. All activities which are related to emissions in the state of Texas must have a NSR authorization prior to beginning construction. This section lists all units in the permit and the NSR authorization that allowed the unit to be constructed or modified. Units that do not have unit specific applicable requirements other than the NSR authorization do not need to be listed in this attachment. While NSR permits are not physically a part of the Title V permit, they are legally incorporated into the Title V permit by reference. Those NSR permits whose emissions exceed certain PSD/NA thresholds must also undergo a Federal review of federally regulated pollutants in addition to review for state regulated pollutants.

Compliance Plan. A permit may have a compliance schedule attachment for listing corrective actions plans for any emission unit that is out of compliance with an applicable requirement.

Alternative Requirements. This attachment will list any alternative monitoring plans or alternative means of compliance for applicable requirements that have been approved by the EPA Administrator and/or the TCEQ Executive Director.

Appendix A

Acronym list. This attachment lists the common acronyms used when discussing the FOPs.

Appendix B

Copies of major NSR authorizations applicable to the units covered by this permit have been included in this Appendix, to ensure that all interested persons can access those authorizations.

Stationary vents subject to 30 TAC Chapter 111, Subchapter A, § 111.111(a)(1)(B) addressed in the Special Terms and Conditions

The site contains stationary vents with a flowrate less than 100,000 actual cubic feet per minute (acfm) and constructed after January 31, 1972 which are limited, over a six-minute average, to 20% opacity as required by 30 TAC § 111.111(a)(1)(B). As a site may have a large number of stationary vents that fall into this category, they are not required to be listed individually in the permit's Applicable Requirement Summary. This is consistent with EPA's White Paper for Streamlined Development of Part 70 Permit Applications, July 10, 1995, that states that requirements that apply identically to emission units at a site can be treated on a generic basis such as source-wide opacity limits.

Periodic monitoring is specified in Special Term and Condition 3.A.(iv) for stationary vents subject to 30 TAC § 111.111(a)(1)(B) to verify compliance with the 20% opacity limit. These vents are not expected to produce visible emissions during normal operation. The TCEQ evaluated the probability of these sources violating the opacity standards and determined that there is a very low potential that an opacity standard would be exceeded. It was determined that continuous monitoring for these sources is not warranted as there would be very limited environmental benefit in continuously monitoring sources that have a low potential to produce visible emissions. Therefore, the TCEQ set the visible observation monitoring frequency for these sources to once per calendar quarter.

The TCEQ has exempted vents that are not capable of producing visible emissions from periodic monitoring requirements. These vents include sources of colorless VOCs, non-fuming liquids, and other materials that cannot produce emissions that obstruct the transmission of light. Passive ventilation vents, such as plumbing vents, are also included in this category. Since this category of vents are not capable of producing opacity due to the physical or chemical characteristics of the emission source, periodic monitoring is not required as it would not yield any additional data to assure compliance with the 20% opacity standard of 30 TAC § 111.111(a)(1)(B).

In the event that visible emissions are detected, either through the quarterly observation or other credible evidence, such as observations from company personnel, the permit holder shall either report a deviation or perform a Test Method 9 observation to determine the opacity consistent with the 6-minute averaging time specified in 30 TAC § 111.111(a)(1)(B). An additional provision is included to monitor combustion sources more frequently than quarterly if alternate fuels are burned for periods greater than 24 consecutive hours. This will address possible emissions that may arise when switching fuel types.

Stationary Vents subject to 30 TAC Chapter 111 not addressed in the Special Terms and Conditions

All other stationary vents subject to 30 TAC Chapter 111 not covered in the Special Terms and Conditions are listed in the permit's Applicable Requirement Summary. The basis for the applicability determinations for these vents are listed in the Determination of Applicable Requirements table.

Federal Regulatory Applicability Determinations

The following chart summarizes the applicability of the principal air pollution regulatory programs to the permit area:

Regulatory Program	Applicability (Yes/No)
Prevention of Significant Deterioration (PSD)	Yes
Nonattainment New Source Review (NNSR)	No
Minor NSR	Yes
40 CFR Part 60 - New Source Performance Standards	Yes
40 CFR Part 61 - National Emission Standards for Hazardous Air Pollutants (NESHAPs)	Yes
40 CFR Part 63 - NESHAPs for Source Categories	Yes
Title IV (Acid Rain) of the Clean Air Act (CAA)	No
Title V (Federal Operating Permits) of the CAA	Yes
Title VI (Stratospheric Ozone Protection) of the CAA	Yes
CAIR (Clean Air Interstate Rule)	No

Basis for Applying Permit Shields

An operating permit applicant has the opportunity to specifically request a permit shield to document that specific applicable requirements do not apply to emission units in the permit. A permit shield is a special condition stating that compliance with the conditions of the permit shall be deemed compliance with the specified potentially applicable requirements or specified potentially applicable state-only requirements. A permit shield has been requested in the application for specific emission units. For the permit shield requests that have been approved, the basis of determination for regulations that the owner/operator need not comply with are located in the "Permit Shield" attachment of the permit.

Insignificant Activities

In general, units not meeting the criteria for inclusion on either Form OP-SUM or Form OP-REQ1 are not required to be addressed in the operating permit application. Examples of these types of units include, but are not limited to, the following:

1. Office activities such as photocopying, blueprint copying, and photographic processes.
2. Sanitary sewage collection and treatment facilities other than those used to incinerate wastewater treatment plant sludge. Stacks or vents for sanitary sewer plumbing traps are also included.
3. Food preparation facilities including, but not limited to, restaurants and cafeterias used for preparing food or beverages primarily for consumption on the premises.
4. Outdoor barbecue pits, campfires, and fireplaces.
5. Laundry dryers, extractors, and tumblers processing bedding, clothing, or other fabric items generated primarily at the premises. This does not include emissions from dry cleaning systems using perchloroethylene or petroleum solvents.
6. Facilities storing only dry, sweet natural gas, including natural gas pressure regulator vents.
7. Any air separation or other industrial gas production, storage, or packaging facility. Industrial gases, for purposes of this list, include only oxygen, nitrogen, helium, neon, argon, krypton, and xenon.
8. Storage and handling of sealed portable containers, cylinders, or sealed drums.
9. Vehicle exhaust from maintenance or repair shops.

10. Storage and use of non-VOC products or equipment for maintaining motor vehicles operated at the site (including but not limited to, antifreeze and fuel additives).
11. Air contaminant detectors and recorders, combustion controllers and shut-off devices, product analyzers, laboratory analyzers, continuous emissions monitors, other analyzers and monitors, and emissions associated with sampling activities. Exception to this category includes sampling activities that are deemed fugitive emissions and under a regulatory leak detection and repair program.
12. Bench scale laboratory equipment and laboratory equipment used exclusively for chemical and physical analysis, including but not limited to, assorted vacuum producing devices and laboratory fume hoods.
13. Steam vents, steam leaks, and steam safety relief valves, provided the steam (or boiler feedwater) has not contacted other materials or fluids containing regulated air pollutants other than boiler water treatment chemicals.
14. Storage of water that has not contacted other materials or fluids containing regulated air pollutants other than boiler water treatment chemicals.
15. Well cellars.
16. Fire or emergency response equipment and training, including but not limited to, use of fire control equipment including equipment testing and training, and open burning of materials or fuels associated with firefighting training.
17. Crucible or pot furnaces with a brim full capacity of less than 450 cubic inches of any molten metal.
18. Equipment used exclusively for the melting or application of wax.
19. All closed tumblers used for the cleaning or deburring of metal products without abrasive blasting, and all open tumblers with a batch capacity of 1,000 lbs. or less.
20. Shell core and shell mold manufacturing machines.
21. Sand or investment molds with a capacity of 100 lbs. or less used for the casting of metals;
22. Equipment used for inspection of metal products.
23. Equipment used exclusively for rolling, forging, pressing, drawing, spinning, or extruding either hot or cold metals by some mechanical means.
24. Instrument systems utilizing air, natural gas, nitrogen, oxygen, carbon dioxide, helium, neon, argon, krypton, and xenon.
25. Battery recharging areas.
26. Brazing, soldering, or welding equipment.

Determination of Applicable Requirements

The tables below include the applicability determinations for the emission units, the index number(s) where applicable, and all relevant unit attribute information used to form the basis of the applicability determination. The unit attribute information is a description of the physical properties of an emission unit which is used to determine the requirements to which the permit holder must comply. For more information about the descriptions of the unit attributes specific Unit Attribute Forms may be viewed at www.tceq.texas.gov/permitting/air/nav/air_all_ua_forms.html.

A list of unit attribute forms is included at the end of this document. Some examples of unit attributes include construction date; product stored in a tank; boiler fuel type; etc.. Generally, multiple attributes are needed to determine the requirements for a given emission unit and index number. The table below lists these attributes in the column entitled "Basis of Determination." Attributes that demonstrate that an applicable requirement applies will be the factual basis for the specific citations in an applicable requirement that apply to a unit for that index number. The TCEQ Air Permits Division has developed flowcharts for determining applicability of state and federal regulations based on the unit attribute information in a Decision Support System (DSS). These flowcharts can be accessed via the internet at www.tceq.texas.gov/permitting/air/nav/air_supportsys.html. The Air Permits Division staff may also be contacted for assistance at (512) 239-1250.

The attributes for each unit and corresponding index number provide the basis for determining the specific legal citations in an applicable requirement that apply, including emission limitations or standards,

monitoring, recordkeeping, and reporting. The rules were found to apply or not apply by using the unit attributes as answers to decision questions found in the flowcharts of the DSS. Some additional attributes indicate which legal citations of a rule apply. The legal citations that apply to each emission unit may be found in the Applicable Requirements Summary table of the draft permit. There may be some entries or rows of units and rules not found in the permit, or if the permit contains a permit shield, repeated in the permit shield area. These are sets of attributes that describe negative applicability, or; in other words, the reason why a potentially applicable requirement does not apply.

If applicability determinations have been made which differ from the available flowcharts, an explanation of the decisions involved in the applicability determination is specified in the column “Changes and Exceptions to RRT.” If there were no exceptions to the DSS, then this column has been removed.

The draft permit includes all emission limitations or standards, monitoring, recordkeeping and reporting required by each applicable requirement. If an applicable requirement does not require monitoring, recordkeeping, or reporting, the word “None” will appear in the Applicable Requirements Summary table. If additional periodic monitoring is required for an applicable requirement, it will be explained in detail in the portion of this document entitled “Rationale for Compliance Assurance Monitoring (CAM)/ Periodic Monitoring Methods Selected.”

When attributes demonstrate that a unit is not subject to an applicable requirement, the applicant may request a permit shield for those items. The portion of this document entitled “Basis for Applying Permit Shields” specifies which units, if any, have a permit shield.

Operational Flexibility

When an emission unit has multiple operating scenarios, it will have a different index number associated with each operating condition. This means that units are permitted to operate under multiple operating conditions. The applicable requirements for each operating condition are determined by a unique set of unit attributes. For example, a tank may store two different products at different points in time. The tank may, therefore, need to comply with two distinct sets of requirements, depending on the product that is stored. Both sets of requirements are included in the permit, so that the permit holder may store either product in the tank.

Determination of Applicable Requirements

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
12E1	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-6	<p>HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2.</p> <p>Brake HP = Stationary RICE with a brake hp greater than 500.</p> <p>Performance Test = A performance test has been previously conducted that meets the conditions in 40 CFR § 63.6610(d)(1)-(5).</p> <p>Construction/Reconstruction Date = Commenced construction or reconstruction before December 19, 2002.</p> <p>Control Technique = Control technique other than non-selective catalytic reduction</p> <p>Different Schedule = Schedule specified in Subpart ZZZZ for submission of reports applies.</p> <p>Emission Limitation = Reducing formaldehyde emission by 76% or greater</p> <p>Nonindustrial Emergency Engine = Stationary RICE is not defined in 40 CFR §63.6675 as a residential emergency RICE, a commercial emergency RICE, or an institutional emergency RICE.</p> <p>Operating Limits = Using the control techniques approved in Subpart ZZZZ</p> <p>Monitoring System = Monitoring system other than a CPMS or CEMS</p> <p>Service Type = Normal use.</p> <p>Stationary RICE Type = 4 stroke spark ignited rich burn engine</p>	
12E2	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-6	<p>HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2.</p> <p>Brake HP = Stationary RICE with a brake hp greater than 500.</p> <p>Performance Test = A performance test has been previously conducted that meets the conditions in 40 CFR § 63.6610(d)(1)-(5).</p> <p>Construction/Reconstruction Date = Commenced construction or reconstruction before December 19, 2002.</p> <p>Control Technique = Control technique other than non-selective catalytic reduction</p> <p>Different Schedule = Schedule specified in Subpart ZZZZ for submission of reports applies.</p> <p>Emission Limitation = Reducing formaldehyde emission by 76% or greater</p> <p>Nonindustrial Emergency Engine = Stationary RICE is not defined in 40 CFR §63.6675 as a residential emergency RICE, a commercial emergency RICE, or an institutional emergency RICE.</p> <p>Operating Limits = Using the control techniques approved in Subpart ZZZZ</p> <p>Monitoring System = Monitoring system other than a CPMS or CEMS</p> <p>Service Type = Normal use.</p> <p>Stationary RICE Type = 4 stroke spark ignited rich burn engine</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
12E3	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-6	<p>HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2.</p> <p>Brake HP = Stationary RICE with a brake hp greater than 500.</p> <p>Performance Test = A performance test has been previously conducted that meets the conditions in 40 CFR § 63.6610(d)(1)-(5).</p> <p>Construction/Reconstruction Date = Commenced construction or reconstruction before December 19, 2002.</p> <p>Control Technique = Control technique other than non-selective catalytic reduction</p> <p>Different Schedule = Schedule specified in Subpart ZZZZ for submission of reports applies.</p> <p>Emission Limitation = Reducing formaldehyde emission by 76% or greater</p> <p>Nonindustrial Emergency Engine = Stationary RICE is not defined in 40 CFR §63.6675 as a residential emergency RICE, a commercial emergency RICE, or an institutional emergency RICE.</p> <p>Operating Limits = Using the control techniques approved in Subpart ZZZZ</p> <p>Monitoring System = Monitoring system other than a CPMS or CEMS</p> <p>Service Type = Normal use.</p> <p>Stationary RICE Type = 4 stroke spark ignited rich burn engine</p>	
12E4	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-6	<p>HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2.</p> <p>Brake HP = Stationary RICE with a brake hp greater than 500.</p> <p>Performance Test = A performance test has been previously conducted that meets the conditions in 40 CFR § 63.6610(d)(1)-(5).</p> <p>Construction/Reconstruction Date = Commenced construction or reconstruction before December 19, 2002.</p> <p>Control Technique = Control technique other than non-selective catalytic reduction</p> <p>Different Schedule = Schedule specified in Subpart ZZZZ for submission of reports applies.</p> <p>Emission Limitation = Reducing formaldehyde emission by 76% or greater</p> <p>Nonindustrial Emergency Engine = Stationary RICE is not defined in 40 CFR §63.6675 as a residential emergency RICE, a commercial emergency RICE, or an institutional emergency RICE.</p> <p>Operating Limits = Using the control techniques approved in Subpart ZZZZ</p> <p>Monitoring System = Monitoring system other than a CPMS or CEMS</p> <p>Service Type = Normal use.</p> <p>Stationary RICE Type = 4 stroke spark ignited rich burn engine</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
12E5	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-6	<p>HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2.</p> <p>Brake HP = Stationary RICE with a brake hp greater than 500.</p> <p>Performance Test = A performance test has been previously conducted that meets the conditions in 40 CFR § 63.6610(d)(1)-(5).</p> <p>Construction/Reconstruction Date = Commenced construction or reconstruction before December 19, 2002.</p> <p>Control Technique = Control technique other than non-selective catalytic reduction</p> <p>Different Schedule = Schedule specified in Subpart ZZZZ for submission of reports applies.</p> <p>Emission Limitation = Reducing formaldehyde emission by 76% or greater</p> <p>Nonindustrial Emergency Engine = Stationary RICE is not defined in 40 CFR §63.6675 as a residential emergency RICE, a commercial emergency RICE, or an institutional emergency RICE.</p> <p>Operating Limits = Using the control techniques approved in Subpart ZZZZ</p> <p>Monitoring System = Monitoring system other than a CPMS or CEMS</p> <p>Service Type = Normal use.</p> <p>Stationary RICE Type = 4 stroke spark ignited rich burn engine</p>	
12E6	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-3	<p>HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2.</p> <p>Brake HP = Stationary RICE with a brake hp greater than or equal to 300 hp and less than or equal to 500 hp.</p> <p>Performance Test = A performance test has been previously conducted that meets the conditions in 40 CFR § 63.6610(d)(1)-(5).</p> <p>Construction/Reconstruction Date = Commenced construction or reconstruction before December 19, 2002.</p> <p>Control Technique = Control technique other than non-selective catalytic reduction</p> <p>Different Schedule = Schedule specified in Subpart ZZZZ for submission of reports applies.</p> <p>Emission Limitation = Reducing formaldehyde emission by 76% or greater</p> <p>Nonindustrial Emergency Engine = Stationary RICE is not defined in 40 CFR §63.6675 as a residential emergency RICE, a commercial emergency RICE, or an institutional emergency RICE.</p> <p>Operating Limits = Using the control techniques approved in Subpart ZZZZ</p> <p>Monitoring System = Monitoring system other than a CPMS or CEMS</p> <p>Service Type = Normal use.</p> <p>Stationary RICE Type = 4 stroke spark ignited rich burn engine</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
12E7	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-3	<p>HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2.</p> <p>Brake HP = Stationary RICE with a brake hp greater than or equal to 300 hp and less than or equal to 500 hp.</p> <p>Performance Test = A performance test has been previously conducted that meets the conditions in 40 CFR § 63.6610(d)(1)-(5).</p> <p>Construction/Reconstruction Date = Commenced construction or reconstruction before December 19, 2002.</p> <p>Control Technique = Control technique other than non-selective catalytic reduction</p> <p>Different Schedule = Schedule specified in Subpart ZZZZ for submission of reports applies.</p> <p>Emission Limitation = Reducing formaldehyde emission by 76% or greater</p> <p>Nonindustrial Emergency Engine = Stationary RICE is not defined in 40 CFR §63.6675 as a residential emergency RICE, a commercial emergency RICE, or an institutional emergency RICE.</p> <p>Operating Limits = Using the control techniques approved in Subpart ZZZZ</p> <p>Monitoring System = Monitoring system other than a CPMS or CEMS</p> <p>Service Type = Normal use.</p> <p>Stationary RICE Type = 4 stroke spark ignited rich burn engine</p>	
7E1	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-1	<p>HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2.</p> <p>Brake HP = Stationary RICE with a brake hp greater than or equal to 100 and less than 250 hp.</p> <p>Performance Test = A performance test has been previously conducted that meets the conditions in 40 CFR § 63.6610(d)(1)-(5).</p> <p>Construction/Reconstruction Date = Commenced construction or reconstruction before December 19, 2002.</p> <p>Control Technique = Control technique other than an oxidation catalyst</p> <p>Different Schedule = Schedule specified in Subpart ZZZZ for submission of reports applies.</p> <p>Emission Limitation = Limiting the concentration of carbon monoxide in the stationary RICE exhaust.</p> <p>Nonindustrial Emergency Engine = Stationary RICE is not defined in 40 CFR §63.6675 as a residential emergency RICE, a commercial emergency RICE, or an institutional emergency RICE.</p> <p>Operating Limits = Using the control techniques approved in Subpart ZZZZ</p> <p>Monitoring System = Monitoring system other than a CPMS or CEMS</p> <p>Service Type = Normal use.</p> <p>Stationary RICE Type = 2 stroke spark ignited lean burn engine</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
7E2	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-1	<p>HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2.</p> <p>Brake HP = Stationary RICE with a brake hp greater than or equal to 100 and less than 250 hp.</p> <p>Performance Test = A performance test has been previously conducted that meets the conditions in 40 CFR § 63.6610(d)(1)-(5).</p> <p>Construction/Reconstruction Date = Commenced construction or reconstruction before December 19, 2002.</p> <p>Control Technique = Control technique other than an oxidation catalyst</p> <p>Different Schedule = Schedule specified in Subpart ZZZZ for submission of reports applies.</p> <p>Emission Limitation = Limiting the concentration of carbon monoxide in the stationary RICE exhaust.</p> <p>Nonindustrial Emergency Engine = Stationary RICE is not defined in 40 CFR §63.6675 as a residential emergency RICE, a commercial emergency RICE, or an institutional emergency RICE.</p> <p>Operating Limits = Using the control techniques approved in Subpart ZZZZ</p> <p>Monitoring System = Monitoring system other than a CPMS or CEMS</p> <p>Service Type = Normal use.</p> <p>Stationary RICE Type = 2 stroke spark ignited lean burn engine</p>	
7E3	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-1	<p>HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2.</p> <p>Brake HP = Stationary RICE with a brake hp greater than or equal to 100 and less than 250 hp.</p> <p>Performance Test = A performance test has been previously conducted that meets the conditions in 40 CFR § 63.6610(d)(1)-(5).</p> <p>Construction/Reconstruction Date = Commenced construction or reconstruction before December 19, 2002.</p> <p>Control Technique = Control technique other than an oxidation catalyst</p> <p>Different Schedule = Schedule specified in Subpart ZZZZ for submission of reports applies.</p> <p>Emission Limitation = Limiting the concentration of carbon monoxide in the stationary RICE exhaust.</p> <p>Nonindustrial Emergency Engine = Stationary RICE is not defined in 40 CFR §63.6675 as a residential emergency RICE, a commercial emergency RICE, or an institutional emergency RICE.</p> <p>Operating Limits = Using the control techniques approved in Subpart ZZZZ</p> <p>Monitoring System = Monitoring system other than a CPMS or CEMS</p> <p>Service Type = Normal use.</p> <p>Stationary RICE Type = 2 stroke spark ignited lean burn engine</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
7E4	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-1	<p>HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2.</p> <p>Brake HP = Stationary RICE with a brake hp greater than or equal to 100 and less than 250 hp.</p> <p>Performance Test = A performance test has been previously conducted that meets the conditions in 40 CFR § 63.6610(d)(1)-(5).</p> <p>Construction/Reconstruction Date = Commenced construction or reconstruction before December 19, 2002.</p> <p>Control Technique = Control technique other than an oxidation catalyst</p> <p>Different Schedule = Schedule specified in Subpart ZZZZ for submission of reports applies.</p> <p>Emission Limitation = Limiting the concentration of carbon monoxide in the stationary RICE exhaust.</p> <p>Nonindustrial Emergency Engine = Stationary RICE is not defined in 40 CFR §63.6675 as a residential emergency RICE, a commercial emergency RICE, or an institutional emergency RICE.</p> <p>Operating Limits = Using the control techniques approved in Subpart ZZZZ</p> <p>Monitoring System = Monitoring system other than a CPMS or CEMS</p> <p>Service Type = Normal use.</p> <p>Stationary RICE Type = 2 stroke spark ignited lean burn engine</p>	
7E5	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-1	<p>HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2.</p> <p>Brake HP = Stationary RICE with a brake hp greater than or equal to 100 and less than 250 hp.</p> <p>Performance Test = A performance test has been previously conducted that meets the conditions in 40 CFR § 63.6610(d)(1)-(5).</p> <p>Construction/Reconstruction Date = Commenced construction or reconstruction before December 19, 2002.</p> <p>Control Technique = Control technique other than an oxidation catalyst</p> <p>Different Schedule = Schedule specified in Subpart ZZZZ for submission of reports applies.</p> <p>Emission Limitation = Limiting the concentration of carbon monoxide in the stationary RICE exhaust.</p> <p>Nonindustrial Emergency Engine = Stationary RICE is not defined in 40 CFR §63.6675 as a residential emergency RICE, a commercial emergency RICE, or an institutional emergency RICE.</p> <p>Operating Limits = Using the control techniques approved in Subpart ZZZZ</p> <p>Monitoring System = Monitoring system other than a CPMS or CEMS</p> <p>Service Type = Normal use.</p> <p>Stationary RICE Type = 2 stroke spark ignited lean burn engine</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
7E6	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-1	<p>HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2.</p> <p>Brake HP = Stationary RICE with a brake hp greater than or equal to 100 and less than 250 hp.</p> <p>Performance Test = A performance test has been previously conducted that meets the conditions in 40 CFR § 63.6610(d)(1)-(5).</p> <p>Construction/Reconstruction Date = Commenced construction or reconstruction before December 19, 2002.</p> <p>Control Technique = Control technique other than an oxidation catalyst</p> <p>Different Schedule = Schedule specified in Subpart ZZZZ for submission of reports applies.</p> <p>Emission Limitation = Limiting the concentration of carbon monoxide in the stationary RICE exhaust.</p> <p>Nonindustrial Emergency Engine = Stationary RICE is not defined in 40 CFR §63.6675 as a residential emergency RICE, a commercial emergency RICE, or an institutional emergency RICE.</p> <p>Operating Limits = Using the control techniques approved in Subpart ZZZZ</p> <p>Monitoring System = Monitoring system other than a CPMS or CEMS</p> <p>Service Type = Normal use.</p> <p>Stationary RICE Type = 2 stroke spark ignited lean burn engine</p>	
93E1	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-4	<p>HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2.</p> <p>Brake HP = Stationary RICE with a brake hp greater than 500.</p> <p>Construction/Reconstruction Date = Commenced construction or reconstruction before December 19, 2002.</p> <p>Nonindustrial Emergency Engine = Stationary RICE is not defined in 40 CFR §63.6675 as a residential emergency RICE, a commercial emergency RICE, or an institutional emergency RICE.</p> <p>Service Type = Normal use.</p> <p>Stationary RICE Type = 2 stroke spark ignited lean burn engine</p>	
93E2	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-4	<p>HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2.</p> <p>Brake HP = Stationary RICE with a brake hp greater than 500.</p> <p>Construction/Reconstruction Date = Commenced construction or reconstruction before December 19, 2002.</p> <p>Nonindustrial Emergency Engine = Stationary RICE is not defined in 40 CFR §63.6675 as a residential emergency RICE, a commercial emergency RICE, or an institutional emergency RICE.</p> <p>Service Type = Normal use.</p> <p>Stationary RICE Type = 2 stroke spark ignited lean burn engine</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
ENG-SC-1	40 CFR Part 60, Subpart IIII	60IIII-3	<p>Applicability Date = Stationary CI ICE commenced construction, reconstruction, or modification after July 11, 2005.</p> <p>Diesel = Diesel fuel is used.</p> <p>Kilowatts = Power rating is greater than or equal to 75 KW and less than or equal to 368 KW.</p> <p>Exemptions = The CI ICE is not exempt due to national security, testing at an engine test cell/stand or as a temporary replacement.</p> <p>Filter = The CI ICE is not equipped with a diesel particulate filter.</p> <p>Displacement = Displacement is greater than or equal to 10 and less than 15 liters per cylinder.</p> <p>Service = CI ICE is a non-emergency engine.</p> <p>Commencing = CI ICE that is commencing new construction.</p> <p>Compliance Option = The CI ICE and control device is installed, configured, operated, and maintained according to the manufacturer's emission-related written instructions.</p> <p>Manufacture Date = Date of manufacture is after 04/01/2006.</p> <p>Model Year = CI ICE was manufactured in model year 2009.</p>	
ENG-SC-1	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-5	<p>HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2.</p> <p>Brake HP = Stationary RICE with a brake hp greater than or equal to 300 hp and less than or equal to 500 hp.</p> <p>Construction/Reconstruction Date = Commenced construction or reconstruction on or after June 12, 2006.</p> <p>Nonindustrial Emergency Engine = Stationary RICE is not defined in 40 CFR §63.6675 as a residential emergency RICE, a commercial emergency RICE, or an institutional emergency RICE.</p> <p>Service Type = Normal use.</p> <p>Stationary RICE Type = Compression ignition engine</p>	
ENG-SD1	40 CFR Part 60, Subpart IIII	60IIII-1	<p>Applicability Date = Stationary CI ICE commenced construction, reconstruction, or modification after July 11, 2005.</p> <p>Diesel = Diesel fuel is used.</p> <p>Kilowatts = Power rating greater than or equal to 130 KW and less than or equal to 368 KW.</p> <p>Exemptions = The CI ICE is not exempt due to national security, testing at an engine test cell/stand or as a temporary replacement.</p> <p>Filter = The CI ICE is not equipped with a diesel particulate filter.</p> <p>Displacement = Displacement is less than 10 liters per cylinder.</p> <p>Service = CI ICE is a non-emergency engine.</p> <p>Commencing = CI ICE that is commencing new construction.</p> <p>Compliance Option = The CI ICE and control device is installed, configured, operated, and maintained according to the manufacturer's emission-related written instructions.</p> <p>Generator Set = The CI ICE is not a generator set engine.</p> <p>Manufacture Date = Date of manufacture is after 04/01/2006.</p> <p>Model Year = CI ICE was manufactured in model year 2007.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
ENG-SD1	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-5	<p>HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2.</p> <p>Brake HP = Stationary RICE with a brake hp greater than or equal to 100 and less than 250 hp.</p> <p>Construction/Reconstruction Date = Commenced construction or reconstruction on or after June 12, 2006.</p> <p>Nonindustrial Emergency Engine = Stationary RICE is not defined in 40 CFR §63.6675 as a residential emergency RICE, a commercial emergency RICE, or an institutional emergency RICE.</p> <p>Service Type = Normal use.</p> <p>Stationary RICE Type = Compression ignition engine</p>	
ENG-SD2	40 CFR Part 60, Subpart IIII	60IIII-1	<p>Applicability Date = Stationary CI ICE commenced construction, reconstruction, or modification after July 11, 2005.</p> <p>Diesel = Diesel fuel is used.</p> <p>Kilowatts = Power rating greater than or equal to 130 KW and less than or equal to 368 KW.</p> <p>Exemptions = The CI ICE is not exempt due to national security, testing at an engine test cell/stand or as a temporary replacement.</p> <p>Filter = The CI ICE is not equipped with a diesel particulate filter.</p> <p>Displacement = Displacement is less than 10 liters per cylinder.</p> <p>Service = CI ICE is a non-emergency engine.</p> <p>Commencing = CI ICE that is commencing new construction.</p> <p>Compliance Option = The CI ICE and control device is installed, configured, operated, and maintained according to the manufacturer's emission-related written instructions.</p> <p>Generator Set = The CI ICE is not a generator set engine.</p> <p>Manufacture Date = Date of manufacture is after 04/01/2006.</p> <p>Model Year = CI ICE was manufactured in model year 2010.</p>	
ENG-SD2	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-5	<p>HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2.</p> <p>Brake HP = Stationary RICE with a brake hp greater than or equal to 100 and less than 250 hp.</p> <p>Construction/Reconstruction Date = Commenced construction or reconstruction on or after June 12, 2006.</p> <p>Nonindustrial Emergency Engine = Stationary RICE is not defined in 40 CFR §63.6675 as a residential emergency RICE, a commercial emergency RICE, or an institutional emergency RICE.</p> <p>Service Type = Normal use.</p> <p>Stationary RICE Type = Compression ignition engine</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
ENG-SD3	40 CFR Part 60, Subpart IIII	60IIII-1	<p>Applicability Date = Stationary CI ICE commenced construction, reconstruction, or modification after July 11, 2005.</p> <p>Diesel = Diesel fuel is used.</p> <p>Kilowatts = Power rating greater than or equal to 130 KW and less than or equal to 368 KW.</p> <p>Exemptions = The CI ICE is not exempt due to national security, testing at an engine test cell/stand or as a temporary replacement.</p> <p>Filter = The CI ICE is not equipped with a diesel particulate filter.</p> <p>Displacement = Displacement is less than 10 liters per cylinder.</p> <p>Service = CI ICE is a non-emergency engine.</p> <p>Commencing = CI ICE that is commencing new construction.</p> <p>Compliance Option = The CI ICE and control device is installed, configured, operated, and maintained according to the manufacturer's emission-related written instructions.</p> <p>Generator Set = The CI ICE is not a generator set engine.</p> <p>Manufacture Date = Date of manufacture is after 04/01/2006.</p> <p>Model Year = CI ICE was manufactured in model year 2007.</p>	
ENG-SD3	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-5	<p>HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2.</p> <p>Brake HP = Stationary RICE with a brake hp greater than or equal to 100 and less than 250 hp.</p> <p>Construction/Reconstruction Date = Commenced construction or reconstruction on or after June 12, 2006.</p> <p>Nonindustrial Emergency Engine = Stationary RICE is not defined in 40 CFR §63.6675 as a residential emergency RICE, a commercial emergency RICE, or an institutional emergency RICE.</p> <p>Service Type = Normal use.</p> <p>Stationary RICE Type = Compression ignition engine</p>	
ENG-SD4	40 CFR Part 60, Subpart IIII	60IIII-1	<p>Applicability Date = Stationary CI ICE commenced construction, reconstruction, or modification after July 11, 2005.</p> <p>Diesel = Diesel fuel is used.</p> <p>Kilowatts = Power rating greater than or equal to 130 KW and less than or equal to 368 KW.</p> <p>Exemptions = The CI ICE is not exempt due to national security, testing at an engine test cell/stand or as a temporary replacement.</p> <p>Filter = The CI ICE is not equipped with a diesel particulate filter.</p> <p>Displacement = Displacement is less than 10 liters per cylinder.</p> <p>Service = CI ICE is a non-emergency engine.</p> <p>Commencing = CI ICE that is commencing new construction.</p> <p>Compliance Option = The CI ICE and control device is installed, configured, operated, and maintained according to the manufacturer's emission-related written instructions.</p> <p>Generator Set = The CI ICE is not a generator set engine.</p> <p>Manufacture Date = Date of manufacture is after 04/01/2006.</p> <p>Model Year = CI ICE was manufactured in model year 2013.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
ENG-SD4	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-5	<p>HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2.</p> <p>Brake HP = Stationary RICE with a brake hp greater than or equal to 100 and less than 250 hp.</p> <p>Construction/Reconstruction Date = Commenced construction or reconstruction on or after June 12, 2006.</p> <p>Nonindustrial Emergency Engine = Stationary RICE is not defined in 40 CFR §63.6675 as a residential emergency RICE, a commercial emergency RICE, or an institutional emergency RICE.</p> <p>Service Type = Normal use.</p> <p>Stationary RICE Type = Compression ignition engine</p>	
ENG-SD5	40 CFR Part 60, Subpart IIII	60IIII-2	<p>Applicability Date = Stationary CI ICE commenced construction, reconstruction, or modification after July 11, 2005.</p> <p>Diesel = Diesel fuel is used.</p> <p>Kilowatts = Power rating is greater than or equal to 19 KW and less than 37 KW.</p> <p>Exemptions = The CI ICE is not exempt due to national security, testing at an engine test cell/stand or as a temporary replacement.</p> <p>Filter = The CI ICE is not equipped with a diesel particulate filter.</p> <p>Displacement = Displacement is less than 10 liters per cylinder.</p> <p>Service = CI ICE is a non-emergency engine.</p> <p>Commencing = CI ICE that is commencing new construction.</p> <p>Compliance Option = The CI ICE and control device is installed, configured, operated, and maintained according to the manufacturer's emission-related written instructions.</p> <p>Generator Set = The CI ICE is not a generator set engine.</p> <p>Manufacture Date = Date of manufacture is after 04/01/2006.</p> <p>Model Year = CI ICE was manufactured in model year 2011.</p>	
ENG-SD5	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-5	<p>HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2.</p> <p>Brake HP = Stationary RICE with a brake hp less than 100 hp.</p> <p>Construction/Reconstruction Date = Commenced construction or reconstruction on or after June 12, 2006.</p> <p>Nonindustrial Emergency Engine = Stationary RICE is not defined in 40 CFR §63.6675 as a residential emergency RICE, a commercial emergency RICE, or an institutional emergency RICE.</p> <p>Service Type = Normal use.</p> <p>Stationary RICE Type = Compression ignition engine</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
FWP1	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-2	<p>HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2.</p> <p>Brake HP = Stationary RICE with a brake hp greater than or equal to 250 hp and less than 300 hp.</p> <p>Construction/Reconstruction Date = Commenced construction or reconstruction before December 19, 2002.</p> <p>Nonindustrial Emergency Engine = Stationary RICE is not defined in 40 CFR §63.6675 as a residential emergency RICE, a commercial emergency RICE, or an institutional emergency RICE.</p> <p>Service Type = Emergency use where the RICE does not operate or is not contractually obligated to be available for more than 15 hours per calendar year as specified in 40 CFR §63.6640(f)(2)(ii)-(iii) or does not operate as specified in 40 CFR §63.6640(f)(4)(ii).</p> <p>Stationary RICE Type = Compression ignition engine</p>	
FWP2	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-2	<p>HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2.</p> <p>Brake HP = Stationary RICE with a brake hp greater than or equal to 250 hp and less than 300 hp.</p> <p>Construction/Reconstruction Date = Commenced construction or reconstruction before December 19, 2002.</p> <p>Nonindustrial Emergency Engine = Stationary RICE is not defined in 40 CFR §63.6675 as a residential emergency RICE, a commercial emergency RICE, or an institutional emergency RICE.</p> <p>Service Type = Emergency use where the RICE does not operate or is not contractually obligated to be available for more than 15 hours per calendar year as specified in 40 CFR §63.6640(f)(2)(ii)-(iii) or does not operate as specified in 40 CFR §63.6640(f)(4)(ii).</p> <p>Stationary RICE Type = Compression ignition engine</p>	
FWP3	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-2	<p>HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2.</p> <p>Brake HP = Stationary RICE with a brake hp greater than or equal to 250 hp and less than 300 hp.</p> <p>Construction/Reconstruction Date = Commenced construction or reconstruction before December 19, 2002.</p> <p>Nonindustrial Emergency Engine = Stationary RICE is not defined in 40 CFR §63.6675 as a residential emergency RICE, a commercial emergency RICE, or an institutional emergency RICE.</p> <p>Service Type = Emergency use where the RICE does not operate or is not contractually obligated to be available for more than 15 hours per calendar year as specified in 40 CFR §63.6640(f)(2)(ii)-(iii) or does not operate as specified in 40 CFR §63.6640(f)(4)(ii).</p> <p>Stationary RICE Type = Compression ignition engine</p>	
FWP4	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-2	<p>HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2.</p> <p>Brake HP = Stationary RICE with a brake hp greater than or equal to 250 hp and less than 300 hp.</p> <p>Construction/Reconstruction Date = Commenced construction or reconstruction before December 19, 2002.</p> <p>Nonindustrial Emergency Engine = Stationary RICE is not defined in 40 CFR §63.6675 as a residential emergency RICE, a commercial emergency RICE, or an institutional emergency RICE.</p> <p>Service Type = Emergency use where the RICE does not operate or is not contractually obligated to be available for more than 15 hours per calendar year as specified in 40 CFR §63.6640(f)(2)(ii)-(iii) or does not operate as specified in 40 CFR §63.6640(f)(4)(ii).</p> <p>Stationary RICE Type = Compression ignition engine</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
FWP5	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-2	<p>HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2.</p> <p>Brake HP = Stationary RICE with a brake hp greater than or equal to 250 hp and less than 300 hp.</p> <p>Construction/Reconstruction Date = Commenced construction or reconstruction before December 19, 2002.</p> <p>Nonindustrial Emergency Engine = Stationary RICE is not defined in 40 CFR §63.6675 as a residential emergency RICE, a commercial emergency RICE, or an institutional emergency RICE.</p> <p>Service Type = Emergency use where the RICE does not operate or is not contractually obligated to be available for more than 15 hours per calendar year as specified in 40 CFR §63.6640(f)(2)(ii)-(iii) or does not operate as specified in 40 CFR §63.6640(f)(4)(ii).</p> <p>Stationary RICE Type = Compression ignition engine</p>	
GRP-EBCENG	40 CFR Part 60, Subpart IIII	60IIII-3	<p>Applicability Date = Stationary CI ICE commenced construction, reconstruction, or modification after July 11, 2005.</p> <p>Diesel = Diesel fuel is used.</p> <p>Kilowatts = Power rating is greater than or equal to 75 KW and less than or equal to 368 KW.</p> <p>Exemptions = The CI ICE is not exempt due to national security, testing at an engine test cell/stand or as a temporary replacement.</p> <p>Filter = The CI ICE is not equipped with a diesel particulate filter.</p> <p>Displacement = Displacement is greater than or equal to 10 and less than 15 liters per cylinder.</p> <p>Service = CI ICE is a non-emergency engine.</p> <p>Commencing = CI ICE that is commencing new construction.</p> <p>Compliance Option = The CI ICE and control device is installed, configured, operated, and maintained according to the manufacturer's emission-related written instructions.</p> <p>Manufacture Date = Date of manufacture is after 04/01/2006.</p> <p>Model Year = CI ICE was manufactured in model year 2009.</p>	
GRP-EBCENG	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-5	<p>HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2.</p> <p>Brake HP = Stationary RICE with a brake hp greater than or equal to 300 hp and less than or equal to 500 hp.</p> <p>Construction/Reconstruction Date = Commenced construction or reconstruction on or after June 12, 2006.</p> <p>Nonindustrial Emergency Engine = Stationary RICE is not defined in 40 CFR §63.6675 as a residential emergency RICE, a commercial emergency RICE, or an institutional emergency RICE.</p> <p>Service Type = Normal use.</p> <p>Stationary RICE Type = Compression ignition engine</p>	
0111	40 CFR Part 60, Subpart Ka	60Ka	<p>Product Stored = Petroleum liquid (other than petroleum or condensate)</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons (151,416 liters)</p> <p>True Vapor Pressure = TVP is less than 1.5 psia</p> <p>Storage Vessel Description = Fixed roof with an internal floating-type cover</p> <p>Reid Vapor Pressure = RVP not determined since 40 CFR § 60.115a(d)(1) exemption is not utilized</p> <p>Maximum True Vapor Pressure = Maximum true vapor pressure is greater than 1.0 psia</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
0111	40 CFR Part 63, Subpart CC	63CC	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is subject to the control requirements of 40 CFR Part 60, Subpart Ka</p> <p>Storage Vessel Description = Storage vessel does not have an external floating roof.</p>	
0111	40 CFR Part 63, Subpart OO	63OO	<p>Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.</p>	
0202	40 CFR Part 60, Subpart Ka	60Ka	<p>Product Stored = Petroleum liquid (other than petroleum or condensate)</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons (151,416 liters)</p> <p>True Vapor Pressure = TVP is less than 1.5 psia</p> <p>Storage Vessel Description = Fixed roof with an internal floating-type cover</p> <p>Reid Vapor Pressure = RVP not determined since 40 CFR § 60.115a(d)(1) exemption is not utilized</p> <p>Maximum True Vapor Pressure = Maximum true vapor pressure is greater than 1.0 psia</p>	
0202	40 CFR Part 61, Subpart FF	61FF	<p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is complying with the alternative standards in 40 CFR § 61.351.</p> <p>Kb Tank Type = Using a fixed roof and internal floating roof, that meets the requirements of 40 CFR § 60.112b(a)(1)</p> <p>Seal Type = Mechanical shoe seal</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
0202	40 CFR Part 63, Subpart CC	63CC	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is subject to the control requirements of 40 CFR Part 60, Subpart Ka</p> <p>Storage Vessel Description = Storage vessel does not have an external floating roof.</p>	
0202	40 CFR Part 63, Subpart OO	63OO	<p>Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
0401	40 CFR Part 60, Subpart Kb	60Kb	Product Stored = Petroleum liquid (other than petroleum or condensate) Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia Storage Vessel Description = Fixed roof with an internal floating roof using a mechanical shoe seal	
0401	40 CFR Part 63, Subpart OO	63OO	Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.	
0562	40 CFR Part 60, Subpart Kb	60KB	Product Stored = Petroleum liquid (other than petroleum or condensate) Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia Storage Vessel Description = Pontoon-type or double-deck-type external floating roof with mechanical shoe primary seal	
0562	40 CFR Part 63, Subpart CC	63CC	Product Stored = Refined petroleum products Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6). Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,416 liters) Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I. Existing Kb Source = The storage vessel is part of an existing source and is also subject to the provisions of 40 CFR Part 60, Subpart Kb. Maximum TVP = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia Storage Vessel Description = Pontoon-type or double-deck-type external floating roof a with mechanical shoe primary seal Applicability = The storage vessel is subject to the control requirements of 40 CFR Part 60, Subpart Kb	
0562	40 CFR Part 63, Subpart OO	63OO	Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.	
1001	40 CFR Part 60, Subpart Kb	60KB	Product Stored = Petroleum (other than crude oil) or condensate stored, processed, and/or treated after custody transfer Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia Storage Vessel Description = Pontoon-type or double-deck-type external floating roof with mechanical shoe primary seal	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
1001	40 CFR Part 63, Subpart CC	63CC	<p>Product Stored = Refined petroleum products</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,416 liters)</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is part of an existing source and is also subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Maximum TVP = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof a with mechanical shoe primary seal</p>	
1001	40 CFR Part 63, Subpart OO	63OO	Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.	
1002	40 CFR Part 60, Subpart Kb	60KB	<p>Product Stored = Petroleum (other than crude oil) or condensate stored, processed, and/or treated after custody transfer</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof with mechanical shoe primary seal</p>	
1002	40 CFR Part 63, Subpart CC	63CC	<p>Product Stored = Refined petroleum products</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,416 liters)</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is part of an existing source and is also subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Maximum TVP = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof a with mechanical shoe primary seal</p>	
1002	40 CFR Part 63, Subpart OO	63OO	Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
1025	40 CFR Part 63, Subpart CC	63CC	<p>Closed Vent System = Closed vent system is subject to § 63.172 of Subpart H</p> <p>Existing Source = The storage vessel is at an existing source.</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>By-pass Lines = Closed vent system has no by-pass lines.</p> <p>Emission Control Type = Closed vent system and control device</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Control Device Type = Flare</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641)</p>	
1064	40 CFR Part 60, Subpart Kb	60KB	<p>Product Stored = Petroleum (other than crude oil) or condensate stored, processed, and/or treated after custody transfer</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof with mechanical shoe primary seal</p>	
1064	40 CFR Part 63, Subpart CC	63CC	<p>Product Stored = Refined petroleum products</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,416 liters)</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is part of an existing source and is also subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Maximum TVP = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof a with mechanical shoe primary seal</p>	
1064	40 CFR Part 63, Subpart OO	63OO	<p>Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.</p>	
1163	40 CFR Part 60, Subpart Kb	60KB	<p>Product Stored = Petroleum (other than crude oil) or condensate stored, processed, and/or treated after custody transfer</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof with mechanical shoe primary seal</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
1163	40 CFR Part 63, Subpart CC	63CC	<p>Product Stored = Refined petroleum products</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,416 liters)</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is part of an existing source and is also subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Maximum TVP = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof a with mechanical shoe primary seal</p>	
1163	40 CFR Part 63, Subpart OO	63OO	Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.	
1165	40 CFR Part 60, Subpart Kb	60KB	<p>Product Stored = Petroleum liquid (other than petroleum or condensate)</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof with mechanical shoe primary seal</p>	
1165	40 CFR Part 63, Subpart CC	63CC	<p>Product Stored = Volatile organic liquid other than crude oil, refined petroleum products or waste of variable or indeterminate composition</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,416 liters)</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is part of an existing source and is also subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Maximum TVP = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof a with mechanical shoe primary seal</p> <p>Applicability = The storage vessel is subject to the control requirements of 40 CFR Part 60, Subpart Kb</p>	
1165	40 CFR Part 63, Subpart OO	63OO	Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.	
2072	40 CFR Part 60, Subpart Kb	60KB	<p>Product Stored = Petroleum liquid (other than petroleum or condensate)</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Fixed roof with an internal floating roof using a mechanical shoe seal</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
2072	40 CFR Part 63, Subpart CC	63CC	<p>Product Stored = Refined petroleum products</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,416 liters)</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is part of an existing source and is also subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Maximum TVP = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Fixed roof with an internal floating roof using a mechanical shoe seal</p>	
2072	40 CFR Part 63, Subpart OO	63OO	Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.	
2510	40 CFR Part 60, Subpart K	60K	Construction/Modification Date = On or before June 11, 1973	
2510	40 CFR Part 63, Subpart CC	63CC-1	<p>Existing Source = The storage vessel is at an existing source.</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = External floating roof</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641)</p> <p>Seal Type = Two seals, one above the other, the primary seal being a metallic shoe seal</p>	
2510	40 CFR Part 63, Subpart OO	63OO	Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.	
2576	40 CFR Part 60, Subpart Kb	60KB	<p>Product Stored = Petroleum (other than crude oil) or condensate stored, processed, and/or treated after custody transfer</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof with mechanical shoe primary seal</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
2576	40 CFR Part 63, Subpart CC	63CC	<p>Product Stored = Refined petroleum products</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,416 liters)</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is part of an existing source and is also subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Maximum TVP = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof a with mechanical shoe primary seal</p>	
2576	40 CFR Part 63, Subpart OO	63OO	<p>Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.</p>	
2577	40 CFR Part 60, Subpart Kb	60KB	<p>Product Stored = Petroleum liquid (other than petroleum or condensate)</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Fixed roof with an internal floating roof using a mechanical shoe seal</p>	
2577	40 CFR Part 63, Subpart CC	63CC	<p>Product Stored = Refined petroleum products</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,416 liters)</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is part of an existing source and is also subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Maximum TVP = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Fixed roof with an internal floating roof using a mechanical shoe seal</p>	
2577	40 CFR Part 63, Subpart OO	63OO	<p>Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.</p>	
2579	40 CFR Part 60, Subpart Kb	60KB	<p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Fixed roof with an internal floating roof using a mechanical shoe seal</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
2579	40 CFR Part 63, Subpart CC	63CC	<p>Product Stored = Volatile organic liquid other than crude oil, refined petroleum products or waste of variable or indeterminate composition</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,416 liters)</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is part of an existing source and is also subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Maximum TVP = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Fixed roof with an internal floating roof using a mechanical shoe seal</p>	
2579	40 CFR Part 63, Subpart OO	63OO	<p>Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.</p>	
2580	40 CFR Part 60, Subpart Kb	60KB	<p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia</p>	
2580	40 CFR Part 63, Subpart CC	63CC	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	
2673	40 CFR Part 60, Subpart Kb	60KB	<p>Product Stored = Petroleum liquid (other than petroleum or condensate)</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof with mechanical shoe primary seal</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
2673	40 CFR Part 63, Subpart CC	63CC	<p>Product Stored = Volatile organic liquid other than crude oil, refined petroleum products or waste of variable or indeterminate composition</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,416 liters)</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is part of an existing source and is also subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Maximum TVP = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof a with mechanical shoe primary seal</p> <p>Applicability = The storage vessel is subject to the control requirements of 40 CFR Part 60, Subpart Kb</p>	
2673	40 CFR Part 63, Subpart OO	63OO	Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.	
3001	40 CFR Part 60, Subpart K	60K	Construction/Modification Date = On or before June 11, 1973	
3001	40 CFR Part 63, Subpart CC	63CC	<p>Product Stored = Refined petroleum products</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,416 liters)</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is part of an existing source and is also subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Maximum TVP = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof a with mechanical shoe primary seal</p>	
3001	40 CFR Part 63, Subpart OO	63OO	Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.	
3002	40 CFR Part 60, Subpart K	60K	Construction/Modification Date = On or before June 11, 1973	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
3002	40 CFR Part 63, Subpart CC	63CC	<p>Product Stored = Refined petroleum products</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,416 liters)</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is part of an existing source and is also subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Maximum TVP = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof a with mechanical shoe primary seal</p>	
3002	40 CFR Part 63, Subpart OO	63OO	<p>Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.</p>	
3003	40 CFR Part 60, Subpart Kb	60Kb	<p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof with mechanical shoe primary seal</p>	
3003	40 CFR Part 61, Subpart FF	61FF-STORE	<p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is complying with the alternative standards in 40 CFR § 61.351.</p> <p>Closed Vent System and Control Device = No closed vent system and control device is used.</p> <p>Kb Tank Type = Using an external floating roof that meets the requirements of 40 CFR § 60.112b(a)(2)</p> <p>Seal Type = Mechanical shoe primary seal</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
4030	40 CFR Part 60, Subpart Kb	60KB	<p>Product Stored = Petroleum liquid (other than petroleum or condensate)</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof with mechanical shoe primary seal</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
4030	40 CFR Part 63, Subpart CC	63CC	<p>Product Stored = Refined petroleum products</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,416 liters)</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is part of an existing source and is also subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Maximum TVP = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof a with mechanical shoe primary seal</p> <p>Applicability = The storage vessel is subject to the control requirements of 40 CFR Part 60, Subpart Kb</p>	
4030	40 CFR Part 63, Subpart OO	63OO	<p>Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.</p>	
5505	40 CFR Part 60, Subpart Kb	60KB	<p>Product Stored = Petroleum (other than crude oil) or condensate stored, processed, and/or treated after custody transfer</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof with mechanical shoe primary seal</p>	
5505	40 CFR Part 63, Subpart CC	63CC	<p>Product Stored = Refined petroleum products</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,416 liters)</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is part of an existing source and is also subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Maximum TVP = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof a with mechanical shoe primary seal</p>	
5505	40 CFR Part 63, Subpart OO	63OO	<p>Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.</p>	
5520	40 CFR Part 60, Subpart Kb	60KB	<p>Product Stored = Petroleum liquid (other than petroleum or condensate)</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Fixed roof with an internal floating roof using a mechanical shoe seal</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
5520	40 CFR Part 63, Subpart CC	63CC	<p>Product Stored = Refined petroleum products</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,416 liters)</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is part of an existing source and is also subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Maximum TVP = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Fixed roof with an internal floating roof using a mechanical shoe seal</p>	
5520	40 CFR Part 63, Subpart OO	63OO	Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.	
5521	40 CFR Part 60, Subpart Kb	60KB	<p>Product Stored = Petroleum liquid (other than petroleum or condensate)</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof with mechanical shoe primary seal</p>	
5521	40 CFR Part 63, Subpart CC	63CC	<p>Product Stored = Refined petroleum products</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,416 liters)</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is part of an existing source and is also subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Maximum TVP = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof with mechanical shoe primary seal</p> <p>Applicability = The storage vessel is subject to the control requirements of 40 CFR Part 60, Subpart Kb</p>	
5521	40 CFR Part 63, Subpart OO	63OO	Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.	
5531	40 CFR Part 60, Subpart Kb	60KB	<p>Product Stored = Petroleum liquid (other than petroleum or condensate)</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
5531	40 CFR Part 63, Subpart CC	63CC	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	
5531	40 CFR Part 63, Subpart OO	63OO	Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.	
5532	40 CFR Part 60, Subpart Kb	60KB	<p>Product Stored = Petroleum liquid (other than petroleum or condensate)</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof with mechanical shoe primary seal</p>	
5532	40 CFR Part 63, Subpart CC	63CC	<p>Product Stored = Refined petroleum products</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,416 liters)</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is part of an existing source and is also subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Maximum TVP = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof a with mechanical shoe primary seal</p> <p>Applicability = The storage vessel is subject to the control requirements of 40 CFR Part 60, Subpart Kb</p>	
5532	40 CFR Part 63, Subpart OO	63OO	Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.	
5551	40 CFR Part 60, Subpart Kb	60KB	<p>Product Stored = Petroleum liquid (other than petroleum or condensate)</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof with mechanical shoe primary seal</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
5551	40 CFR Part 63, Subpart CC	63CC	<p>Product Stored = Refined petroleum products</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,416 liters)</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is part of an existing source and is also subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Maximum TVP = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof a with mechanical shoe primary seal</p> <p>Applicability = The storage vessel is subject to the control requirements of 40 CFR Part 60, Subpart Kb</p>	
5551	40 CFR Part 63, Subpart OO	63OO	<p>Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.</p>	
5553	40 CFR Part 60, Subpart Kb	60KB	<p>Product Stored = Petroleum liquid (other than petroleum or condensate)</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof with mechanical shoe primary seal</p>	
5553	40 CFR Part 63, Subpart CC	63CC	<p>Product Stored = Refined petroleum products</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,416 liters)</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is part of an existing source and is also subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Maximum TVP = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof a with mechanical shoe primary seal</p> <p>Applicability = The storage vessel is subject to the control requirements of 40 CFR Part 60, Subpart Kb</p>	
5553	40 CFR Part 63, Subpart OO	63OO	<p>Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.</p>	
5554	40 CFR Part 60, Subpart Kb	60KB	<p>Product Stored = Petroleum liquid (other than petroleum or condensate)</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof with mechanical shoe primary seal</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
5554	40 CFR Part 63, Subpart CC	63CC	<p>Product Stored = Refined petroleum products</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,416 liters)</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is part of an existing source and is also subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Maximum TVP = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof a with mechanical shoe primary seal</p> <p>Applicability = The storage vessel is subject to the control requirements of 40 CFR Part 60, Subpart Kb</p>	
5554	40 CFR Part 63, Subpart OO	63OO	<p>Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.</p>	
5555	40 CFR Part 60, Subpart Kb	60KB	<p>Product Stored = Petroleum liquid (other than petroleum or condensate)</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof with mechanical shoe primary seal</p>	
5555	40 CFR Part 63, Subpart CC	63CC	<p>Product Stored = Refined petroleum products</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,416 liters)</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is part of an existing source and is also subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Maximum TVP = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof a with mechanical shoe primary seal</p> <p>Applicability = The storage vessel is subject to the control requirements of 40 CFR Part 60, Subpart Kb</p>	
5555	40 CFR Part 63, Subpart OO	63OO	<p>Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.</p>	
5556	40 CFR Part 60, Subpart K	60K	<p>Construction/Modification Date = On or before June 11, 1973</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
5556	40 CFR Part 63, Subpart CC	63CC-1	<p>Existing Source = The storage vessel is at an existing source.</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Fixed roof and an internal floating roof</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641)</p> <p>Seal Type = Metallic shoe seal (as defined in 40 CFR § 63.111)</p>	
5556	40 CFR Part 63, Subpart OO	63OO	Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.	
5557	40 CFR Part 60, Subpart Kb	60KB	<p>Product Stored = Petroleum liquid (other than petroleum or condensate)</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof with mechanical shoe primary seal</p>	
5557	40 CFR Part 63, Subpart CC	63CC	<p>Product Stored = Refined petroleum products</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,416 liters)</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is part of an existing source and is also subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Maximum TVP = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof with mechanical shoe primary seal</p> <p>Applicability = The storage vessel is subject to the control requirements of 40 CFR Part 60, Subpart Kb</p>	
5557	40 CFR Part 63, Subpart OO	63OO	Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.	
5558	40 CFR Part 60, Subpart Kb	60KB	<p>Product Stored = Petroleum (other than crude oil) or condensate stored, processed, and/or treated after custody transfer</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof with mechanical shoe primary seal</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
5558	40 CFR Part 63, Subpart CC	63CC	<p>Product Stored = Refined petroleum products</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,416 liters)</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is part of an existing source and is also subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Maximum TVP = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof a with mechanical shoe primary seal</p>	
5558	40 CFR Part 63, Subpart OO	63OO	<p>Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.</p>	
5578	40 CFR Part 60, Subpart Kb	60KB	<p>Product Stored = Petroleum (other than crude oil) or condensate stored, processed, and/or treated after custody transfer</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof with mechanical shoe primary seal</p>	
5578	40 CFR Part 63, Subpart CC	63CC	<p>Product Stored = Refined petroleum products</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,416 liters)</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is part of an existing source and is also subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Maximum TVP = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof a with mechanical shoe primary seal</p>	
5578	40 CFR Part 63, Subpart OO	63OO	<p>Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.</p>	
5580	40 CFR Part 60, Subpart Kb	60KB	<p>Product Stored = Petroleum (other than crude oil) or condensate stored, processed, and/or treated after custody transfer</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof with mechanical shoe primary seal</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
5580	40 CFR Part 63, Subpart CC	63CC	<p>Product Stored = Refined petroleum products</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,416 liters)</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is part of an existing source and is also subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Maximum TVP = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof a with mechanical shoe primary seal</p>	
5580	40 CFR Part 63, Subpart OO	63OO	<p>Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.</p>	
5583	40 CFR Part 60, Subpart Kb	60KB	<p>Product Stored = Petroleum liquid (other than petroleum or condensate)</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof with mechanical shoe primary seal</p>	
5583	40 CFR Part 63, Subpart CC	63CC	<p>Product Stored = Refined petroleum products</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,416 liters)</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is part of an existing source and is also subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Maximum TVP = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof a with mechanical shoe primary seal</p> <p>Applicability = The storage vessel is subject to the control requirements of 40 CFR Part 60, Subpart Kb</p>	
5583	40 CFR Part 63, Subpart OO	63OO	<p>Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.</p>	
5584	40 CFR Part 60, Subpart Kb	60KB	<p>Product Stored = Petroleum liquid (other than petroleum or condensate)</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof with mechanical shoe primary seal</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
5584	40 CFR Part 63, Subpart CC	63CC	<p>Product Stored = Refined petroleum products</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,416 liters)</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is part of an existing source and is also subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Maximum TVP = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof a with mechanical shoe primary seal</p> <p>Applicability = The storage vessel is subject to the control requirements of 40 CFR Part 60, Subpart Kb</p>	
5584	40 CFR Part 63, Subpart OO	63OO	<p>Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.</p>	
5591	40 CFR Part 60, Subpart Kb	60KB	<p>Product Stored = Petroleum liquid (other than petroleum or condensate)</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.5 psia but less than 0.75 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof with mechanical shoe primary seal</p>	
5591	40 CFR Part 63, Subpart CC	63CC	<p>Product Stored = Refined petroleum products</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,416 liters)</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is part of an existing source and is also subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Maximum TVP = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof a with mechanical shoe primary seal</p> <p>Applicability = The storage vessel is subject to the control requirements of 40 CFR Part 60, Subpart Kb</p>	
5591	40 CFR Part 63, Subpart OO	63OO	<p>Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.</p>	
5592	40 CFR Part 60, Subpart Kb	60KB	<p>Product Stored = Petroleum liquid (other than petroleum or condensate)</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof with mechanical shoe primary seal</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
5592	40 CFR Part 63, Subpart CC	63CC	<p>Product Stored = Refined petroleum products</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,416 liters)</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is part of an existing source and is also subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Maximum TVP = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof a with mechanical shoe primary seal</p> <p>Applicability = The storage vessel is subject to the control requirements of 40 CFR Part 60, Subpart Kb</p>	
5592	40 CFR Part 63, Subpart OO	63OO	Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.	
5593	40 CFR Part 60, Subpart Kb	60KB	<p>Product Stored = Petroleum liquid (other than petroleum or condensate)</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof with mechanical shoe primary seal</p>	
5593	40 CFR Part 63, Subpart CC	63CC	<p>Product Stored = Refined petroleum products</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,416 liters)</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is part of an existing source and is also subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Maximum TVP = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof a with mechanical shoe primary seal</p> <p>Applicability = The storage vessel is subject to the control requirements of 40 CFR Part 60, Subpart Kb</p>	
5593	40 CFR Part 63, Subpart OO	63OO	Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.	
5596	40 CFR Part 60, Subpart Kb	60KB	<p>Product Stored = Petroleum liquid (other than petroleum or condensate)</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
5596	40 CFR Part 63, Subpart CC	63CC	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	
5596	40 CFR Part 63, Subpart OO	63OO	Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.	
5597	40 CFR Part 60, Subpart Kb	60KB	<p>Product Stored = Petroleum liquid (other than petroleum or condensate)</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof with mechanical shoe primary seal</p>	
5597	40 CFR Part 63, Subpart CC	63CC	<p>Product Stored = Refined petroleum products</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,416 liters)</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is part of an existing source and is also subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Maximum TVP = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof a with mechanical shoe primary seal</p> <p>Applicability = The storage vessel is subject to the control requirements of 40 CFR Part 60, Subpart Kb</p>	
5597	40 CFR Part 63, Subpart OO	63OO	Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.	
5599	40 CFR Part 60, Subpart Kb	60KB	<p>Product Stored = Petroleum liquid (other than petroleum or condensate)</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof with mechanical shoe primary seal</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
5599	40 CFR Part 63, Subpart CC	63CC	<p>Product Stored = Refined petroleum products</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,416 liters)</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is part of an existing source and is also subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Maximum TVP = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof a with mechanical shoe primary seal</p> <p>Applicability = The storage vessel is subject to the control requirements of 40 CFR Part 60, Subpart Kb</p>	
5599	40 CFR Part 63, Subpart OO	63OO	<p>Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.</p>	
8001	40 CFR Part 60, Subpart K	60K	<p>Construction/Modification Date = On or before June 11, 1973</p>	
8001	40 CFR Part 63, Subpart CC	63CC	<p>Existing Source = The storage vessel is at an existing source.</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = External floating roof</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641)</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p> <p>Seal Type = Two seals, one above the other, the primary seal being a metallic shoe seal</p>	
8001	40 CFR Part 63, Subpart OO	63OO	<p>Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.</p>	
8002	40 CFR Part 60, Subpart Kb	60KB	<p>Product Stored = Petroleum liquid (other than petroleum or condensate)</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof with mechanical shoe primary seal</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
8002	40 CFR Part 63, Subpart CC	63CC	<p>Product Stored = Refined petroleum products</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,416 liters)</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is part of an existing source and is also subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Maximum TVP = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof a with mechanical shoe primary seal</p> <p>Applicability = The storage vessel is subject to the control requirements of 40 CFR Part 60, Subpart Kb</p>	
8002	40 CFR Part 63, Subpart OO	63OO	<p>Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.</p>	
8010	40 CFR Part 60, Subpart Kb	60KB	<p>Product Stored = Petroleum liquid (other than petroleum or condensate)</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.5 psia but less than 0.75 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof with mechanical shoe primary seal</p>	
8010	40 CFR Part 63, Subpart CC	63CC	<p>Product Stored = Refined petroleum products</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,416 liters)</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is part of an existing source and is also subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Maximum TVP = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof a with mechanical shoe primary seal</p> <p>Applicability = The storage vessel is subject to the control requirements of 40 CFR Part 60, Subpart Kb</p>	
8010	40 CFR Part 63, Subpart OO	63OO	<p>Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.</p>	
8014	40 CFR Part 60, Subpart Kb	60KB	<p>Product Stored = Petroleum liquid (other than petroleum or condensate)</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.5 psia but less than 0.75 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof with mechanical shoe primary seal</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
8014	40 CFR Part 63, Subpart CC	63CC	<p>Product Stored = Refined petroleum products</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,416 liters)</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is part of an existing source and is also subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Maximum TVP = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof a with mechanical shoe primary seal</p> <p>Applicability = The storage vessel is subject to the control requirements of 40 CFR Part 60, Subpart Kb</p>	
8014	40 CFR Part 63, Subpart OO	63OO	<p>Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.</p>	
8031	40 CFR Part 60, Subpart Kb	60KB	<p>Product Stored = Petroleum liquid (other than petroleum or condensate)</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Fixed roof with an internal floating roof using a mechanical shoe seal</p>	
8031	40 CFR Part 63, Subpart CC	63CC	<p>Product Stored = Refined petroleum products</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,416 liters)</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is part of an existing source and is also subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Maximum TVP = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Fixed roof with an internal floating roof using a mechanical shoe seal</p>	
8031	40 CFR Part 63, Subpart OO	63OO	<p>Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.</p>	
8032	40 CFR Part 60, Subpart Kb	60KB	<p>Product Stored = Petroleum liquid (other than petroleum or condensate)</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof with mechanical shoe primary seal</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
8032	40 CFR Part 63, Subpart CC	63CC	<p>Product Stored = Refined petroleum products</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,416 liters)</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is part of an existing source and is also subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Maximum TVP = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof a with mechanical shoe primary seal</p> <p>Applicability = The storage vessel is subject to the control requirements of 40 CFR Part 60, Subpart Kb</p>	
8032	40 CFR Part 63, Subpart OO	63OO	<p>Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.</p>	
8034	40 CFR Part 60, Subpart Kb	60KB	<p>Product Stored = Petroleum liquid (other than petroleum or condensate)</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof with mechanical shoe primary seal</p>	
8034	40 CFR Part 63, Subpart CC	63CC	<p>Product Stored = Refined petroleum products</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,416 liters)</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is part of an existing source and is also subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Maximum TVP = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof a with mechanical shoe primary seal</p> <p>Applicability = The storage vessel is subject to the control requirements of 40 CFR Part 60, Subpart Kb</p>	
8034	40 CFR Part 63, Subpart OO	63OO	<p>Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.</p>	
8035	40 CFR Part 61, Subpart FF	61FF	<p>Waste Treatment Tank = The tank does not manage, treat or store a waste stream subject to 40 CFR Part 61, Subpart FF.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
8035	40 CFR Part 63, Subpart CC	63CC	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	
8035	40 CFR Part 63, Subpart OO	63OO	Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.	
8036	40 CFR Part 61, Subpart FF	61FF	Waste Treatment Tank = The tank does not manage, treat or store a waste stream subject to 40 CFR Part 61, Subpart FF.	
8036	40 CFR Part 63, Subpart CC	63CC	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	
8036	40 CFR Part 63, Subpart OO	63OO	Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.	
8037	40 CFR Part 61, Subpart FF	61FF	Waste Treatment Tank = The tank does not manage, treat or store a waste stream subject to 40 CFR Part 61, Subpart FF.	
8037	40 CFR Part 63, Subpart CC	63CC	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	
8037	40 CFR Part 63, Subpart OO	63OO	Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
9201	40 CFR Part 60, Subpart Kb	60KB	Product Stored = Petroleum liquid (other than petroleum or condensate) Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.5 psia but less than 0.75 psia Storage Vessel Description = Pontoon-type or double-deck-type external floating roof with mechanical shoe primary seal	
9201	40 CFR Part 63, Subpart CC	63CC	Product Stored = Refined petroleum products Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6). Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,416 liters) Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I. Existing Kb Source = The storage vessel is part of an existing source and is also subject to the provisions of 40 CFR Part 60, Subpart Kb. Maximum TVP = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia Storage Vessel Description = Pontoon-type or double-deck-type external floating roof a with mechanical shoe primary seal Applicability = The storage vessel is subject to the control requirements of 40 CFR Part 60, Subpart Kb	
9201	40 CFR Part 63, Subpart OO	63OO	Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.	
9202	40 CFR Part 60, Subpart Kb	60KB	Product Stored = Petroleum liquid (other than petroleum or condensate) Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia	
9202	40 CFR Part 63, Subpart CC	63CC	Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6). Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I. Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb. Group 1 Storage Vessel = The storage vessel is a Group 2 vessel. Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.	
9202	40 CFR Part 63, Subpart OO	63OO	Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.	
9400	40 CFR Part 61, Subpart FF	61FF	Waste Treatment Tank = The tank does not manage, treat or store a waste stream subject to 40 CFR Part 61, Subpart FF.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
9400	40 CFR Part 63, Subpart CC	63CC	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	
9400	40 CFR Part 63, Subpart OO	63OO	Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.	
9401	40 CFR Part 61, Subpart FF	61FF	Waste Treatment Tank = The tank does not manage, treat or store a waste stream subject to 40 CFR Part 61, Subpart FF.	
9401	40 CFR Part 63, Subpart CC	63CC	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	
9401	40 CFR Part 63, Subpart OO	63OO	Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.	
9500	40 CFR Part 60, Subpart Kb	60KB	<p>Product Stored = Petroleum liquid (other than petroleum or condensate)</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof with mechanical shoe primary seal</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
9500	40 CFR Part 63, Subpart CC	63CC	<p>Product Stored = Refined petroleum products</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,416 liters)</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is part of an existing source and is also subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Maximum TVP = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof a with mechanical shoe primary seal</p> <p>Applicability = The storage vessel is subject to the control requirements of 40 CFR Part 60, Subpart Kb</p>	
9500	40 CFR Part 63, Subpart OO	63OO	<p>Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.</p>	
9501	40 CFR Part 60, Subpart Kb	60KB	<p>Product Stored = Petroleum liquid (other than petroleum or condensate)</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof with mechanical shoe primary seal</p>	
9501	40 CFR Part 63, Subpart CC	63CC	<p>Product Stored = Refined petroleum products</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,416 liters)</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is part of an existing source and is also subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Maximum TVP = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof a with mechanical shoe primary seal</p> <p>Applicability = The storage vessel is subject to the control requirements of 40 CFR Part 60, Subpart Kb</p>	
9501	40 CFR Part 63, Subpart OO	63OO	<p>Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.</p>	
9502	40 CFR Part 60, Subpart Kb	60KB	<p>Product Stored = Petroleum liquid (other than petroleum or condensate)</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof with mechanical shoe primary seal</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
9502	40 CFR Part 63, Subpart CC	63CC	<p>Product Stored = Refined petroleum products</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,416 liters)</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is part of an existing source and is also subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Maximum TVP = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof a with mechanical shoe primary seal</p> <p>Applicability = The storage vessel is subject to the control requirements of 40 CFR Part 60, Subpart Kb</p>	
9502	40 CFR Part 63, Subpart OO	63OO	<p>Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.</p>	
9503	40 CFR Part 60, Subpart Kb	60KB	<p>Product Stored = Petroleum liquid (other than petroleum or condensate)</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof with mechanical shoe primary seal</p>	
9503	40 CFR Part 63, Subpart CC	63CC	<p>Product Stored = Refined petroleum products</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,416 liters)</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is part of an existing source and is also subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Maximum TVP = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia</p> <p>Storage Vessel Description = Pontoon-type or double-deck-type external floating roof a with mechanical shoe primary seal</p> <p>Applicability = The storage vessel is subject to the control requirements of 40 CFR Part 60, Subpart Kb</p>	
9503	40 CFR Part 63, Subpart OO	63OO	<p>Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
9600	40 CFR Part 60, Subpart QQQ	60QQQ	<p>Construction/Modification Date = After May 4, 1987</p> <p>Control Device Type = VOC recovery device other than a carbon adsorber</p> <p>Alternate Means of Emission Limitation = The EPA Administrator has not approved an alternate means of emission limitation.</p> <p>Alternative Monitoring = No alternative operational or process parameter is monitored.</p> <p>Alternative Standard = The storage vessel, slop oil tank, or auxiliary tank is not equipped with a floating roof.</p> <p>Subject to 40 CFR Part 60, Subpart K, Ka or Kb = No</p>	
9600	40 CFR Part 61, Subpart FF	61FF	<p>Waste Treatment Tank = The tank does not manage, treat or store a waste stream subject to 40 CFR Part 61, Subpart FF.</p>	
9600	40 CFR Part 63, Subpart CC	63CC	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	
9600	40 CFR Part 63, Subpart OO	63OO	<p>Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.</p>	
9601	40 CFR Part 60, Subpart QQQ	60QQQ	<p>Construction/Modification Date = After May 4, 1987</p> <p>Control Device Type = VOC recovery device other than a carbon adsorber</p> <p>Alternate Means of Emission Limitation = The EPA Administrator has not approved an alternate means of emission limitation.</p> <p>Alternative Monitoring = No alternative operational or process parameter is monitored.</p> <p>Alternative Standard = The storage vessel, slop oil tank, or auxiliary tank is not equipped with a floating roof.</p> <p>Subject to 40 CFR Part 60, Subpart K, Ka or Kb = No</p>	
9601	40 CFR Part 61, Subpart FF	61FF	<p>Waste Treatment Tank = The tank does not manage, treat or store a waste stream subject to 40 CFR Part 61, Subpart FF.</p>	
9601	40 CFR Part 63, Subpart CC	63CC	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
9601	40 CFR Part 63, Subpart OO	63OO	Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.	
9700	40 CFR Part 60, Subpart Ka	60Ka	Product Stored = Crude oil stored, processed, and/or treated after custody transfer Storage Capacity = Capacity is greater than 40,000 gallons (151,416 liters) True Vapor Pressure = TVP is less than 1.5 psia Storage Vessel Description = Emission controls not required (fixed roof) Reid Vapor Pressure = Physical properties of the crude oil precluded determination of true vapor pressure by the recommended method Maximum True Vapor Pressure = Maximum true vapor pressure is less than or equal to 1.0 psia Estimated True Vapor Pressure = Estimated true vapor pressure is less than or equal to 1.0 psia	
9700	40 CFR Part 63, Subpart CC	63CC	Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6). Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I. Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb. Group 1 Storage Vessel = The storage vessel is a Group 2 vessel. Applicability = The storage vessel is subject to the control requirements of 40 CFR Part 60, Subpart Ka Storage Vessel Description = Storage vessel does not have an external floating roof.	
9700	40 CFR Part 63, Subpart OO	63OO	Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.	
9701	40 CFR Part 60, Subpart Ka	60Ka	Product Stored = Crude oil stored, processed, and/or treated after custody transfer Storage Capacity = Capacity is greater than 40,000 gallons (151,416 liters) True Vapor Pressure = TVP is less than 1.5 psia Storage Vessel Description = Emission controls not required (fixed roof) Reid Vapor Pressure = Physical properties of the crude oil precluded determination of true vapor pressure by the recommended method Maximum True Vapor Pressure = Maximum true vapor pressure is less than or equal to 1.0 psia Estimated True Vapor Pressure = Estimated true vapor pressure is less than or equal to 1.0 psia	
9701	40 CFR Part 63, Subpart CC	63CC	Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6). Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I. Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb. Group 1 Storage Vessel = The storage vessel is a Group 2 vessel. Applicability = The storage vessel is subject to the control requirements of 40 CFR Part 60, Subpart Ka Storage Vessel Description = Storage vessel does not have an external floating roof.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
9701	40 CFR Part 63, Subpart OO	63OO	Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.	
9702	40 CFR Part 60, Subpart Ka	60Ka	<p>Product Stored = Crude oil stored, processed, and/or treated after custody transfer</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons (151,416 liters)</p> <p>True Vapor Pressure = TVP is less than 1.5 psia</p> <p>Storage Vessel Description = Emission controls not required (fixed roof)</p> <p>Reid Vapor Pressure = Physical properties of the crude oil precluded determination of true vapor pressure by the recommended method</p> <p>Maximum True Vapor Pressure = Maximum true vapor pressure is less than or equal to 1.0 psia</p> <p>Estimated True Vapor Pressure = Estimated true vapor pressure is less than or equal to 1.0 psia</p>	
9702	40 CFR Part 63, Subpart CC	63CC	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is subject to the control requirements of 40 CFR Part 60, Subpart Ka</p> <p>Storage Vessel Description = Storage vessel does not have an external floating roof.</p>	
9702	40 CFR Part 63, Subpart OO	63OO	Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.	
Do11	40 CFR Part 61, Subpart FF	61FF	<p>Bypass Line = The closed vent system does not contain any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Carbon adsorption system that does not regenerate the carbon bed directly in the control device</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Engineering Calculations = Results of performance tests are used to demonstrate that the control device achieves emission limitation.</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p> <p>Carbon Replacement Interval = The carbon in the carbon adsorption system is replaced when monitoring indicates breakthrough.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
Do11	40 CFR Part 63, Subpart CC	63CC	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	
Do11	40 CFR Part 63, Subpart OO	63OO	Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.	
GRP-CC-ToA	40 CFR Part 60, Subpart K	60K	Construction/Modification Date = On or before June 11, 1973	
GRP-CC-ToA	40 CFR Part 63, Subpart CC	63CC	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	
GRP-CC-ToA	40 CFR Part 63, Subpart OO	63OO	Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.	
GRP-FF-T3B	40 CFR Part 61, Subpart FF	61FF	<p>Bypass Line = The closed vent system does not contain any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Flare</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
GRP-FF-T3B	40 CFR Part 63, Subpart OO	63OO	Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
GRP-FF-T5A	40 CFR Part 60, Subpart Kb	60Kb	Product Stored = Petroleum (other than crude oil) or condensate stored, processed, and/or treated after custody transfer Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)	
GRP-FF-T5A	40 CFR Part 61, Subpart FF	61FF	Bypass Line = The closed vent system does not contain any by-pass line that could divert the vent stream away from the control device. Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF. Alternative Standard for Tanks = The tank is complying with the alternative standards in 40 CFR § 61.351. Bypass Line Valve = A flow indicator is used to monitor the by-pass line. Closed Vent System and Control Device = A closed vent system and control device is used. Control Device Type/Operations = Carbon adsorption system that does not regenerate the carbon bed directly in the control device Kb Tank Type = Using a fixed roof and internal floating roof, that meets the requirements of 40 CFR § 60.112b(a)(1) Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3). Engineering Calculations = Results of performance tests are used to demonstrate that the control device achieves emission limitation. Seal Type = Mechanical shoe seal Carbon Replacement Interval = The carbon in the carbon adsorption system is replaced when monitoring indicates breakthrough.	
GRP-FF-T5A	40 CFR Part 63, Subpart OO	63OO	Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.	
GRP-KB-T1A	40 CFR Part 60, Subpart Kb	60Kb	Product Stored = Petroleum (other than crude oil) or condensate stored, processed, and/or treated after custody transfer Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia Storage Vessel Description = Fixed roof with an internal floating roof using a mechanical shoe seal	
GRP-KB-T1A	40 CFR Part 63, Subpart OO	63OO	Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.	
GRP-KB-T2B	40 CFR Part 60, Subpart Kb	60Kb	Product Stored = Petroleum (other than crude oil) or condensate stored, processed, and/or treated after custody transfer Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia Storage Vessel Description = Pontoon-type or double-deck-type external floating roof with mechanical shoe primary seal	
GRP-KB-T2B	40 CFR Part 63, Subpart OO	63OO	Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
GRP-KB-T3B	40 CFR Part 60, Subpart Kb	60KB	Product Stored = Petroleum (other than crude oil) or condensate stored, processed, and/or treated after custody transfer Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia Storage Vessel Description = Pontoon-type or double-deck-type external floating roof with mechanical shoe primary seal	
GRP-KB-T3B	40 CFR Part 63, Subpart CC	63CC	Product Stored = Refined petroleum products Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6). Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,416 liters) Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I. Existing Kb Source = The storage vessel is part of an existing source and is also subject to the provisions of 40 CFR Part 60, Subpart Kb. Maximum TVP = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia Storage Vessel Description = Pontoon-type or double-deck-type external floating roof a with mechanical shoe primary seal	
GRP-KB-T3B	40 CFR Part 63, Subpart OO	63OO	Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.	
GRP-KB-TK3	40 CFR Part 60, Subpart Kb	60Kb	Product Stored = Petroleum liquid (other than petroleum or condensate) Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia Storage Vessel Description = Closed vent system (CVS) with a flare used as the control device (fixed roof)	
GRP-KB-TK3	40 CFR Part 63, Subpart OO	63OO	Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.	
GRP-K-TKO	40 CFR Part 60, Subpart K	60K	Construction/Modification Date = On or before June 11, 1973	
GRP-K-TKO	40 CFR Part 63, Subpart OO	63OO	Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.	
TK2530	40 CFR Part 60, Subpart Kb	60Kb	Product Stored = Petroleum (other than crude oil) or condensate stored, processed, and/or treated after custody transfer Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
UF17	40 CFR Part 61, Subpart FF	61FF	<p>Bypass Line = The closed vent system does not contain any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Flare</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
UF17	40 CFR Part 63, Subpart CC	63CC	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	
UF17	40 CFR Part 63, Subpart OO	63OO	<p>Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
VD114	40 CFR Part 61, Subpart FF	61FF	<p>Bypass Line = The closed vent system does not contain any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Vapor recovery system other than condenser or carbon adsorption system</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Engineering Calculations = Results of performance tests are used to demonstrate that the control device achieves emission limitation.</p> <p>Alternate Monitoring Parameters = Alternate monitoring parameters not requested</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
VD114	40 CFR Part 63, Subpart CC	63CC	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	
VD114	40 CFR Part 63, Subpart OO	63OO	<p>Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
VF02	40 CFR Part 61, Subpart FF	61FF	<p>Bypass Line = The closed vent system does not contain any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Flare</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
VF02	40 CFR Part 63, Subpart CC	63CC	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	
VF02	40 CFR Part 63, Subpart OO	63OO	<p>Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.</p>	
VF03	40 CFR Part 61, Subpart FF	61FF	<p>Bypass Line = The closed vent system does not contain any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Flare</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
VFo3	40 CFR Part 63, Subpart CC	63CC	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	
VFo3	40 CFR Part 63, Subpart OO	63OO	<p>Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.</p>	
VFo4	40 CFR Part 61, Subpart FF	61FF	<p>Bypass Line = The closed vent system does not contain any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A flow indicator is used to monitor the by-pass line.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Flare</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
VFo4	40 CFR Part 63, Subpart CC	63CC	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The storage vessel is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63 Subparts F, G, H or I = The storage vessel is not subject to 40 CFR Part 63, Subparts F, G, H, or I.</p> <p>Existing Kb Source = The storage vessel is not part of an existing source or is not subject to the provisions of 40 CFR Part 60, Subpart Kb.</p> <p>Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.</p> <p>Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.</p>	
VFo4	40 CFR Part 63, Subpart OO	63OO	<p>Subject to 40 CFR Part 61, 61 or 63 = The tank is not subject to another subpart within 40 CFR Part 60, 61, or 63 and references the use of this subpart for air emission control.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
GRP-LOAD	40 CFR Part 63, Subpart CC	63CC-1	Specified in 63.640(g)(1)-(6) = The gasoline loading rack or marine vessel loading operation is not part of a process specified in 40 CFR § 63.640(g)(1) - (6). Subject to 40 CFR Part 63, Subparts F, G, H or I = The gasoline loading rack or marine vessel loading operation is not subject to 40 CFR Part 63, Subparts F, G, H, or I. Unit Type = Gasoline loading rack classified under Standard Industrial Classification code 2911. Vapor Processing System = THERMAL OXIDATION SYSTEM	
10H1	40 CFR Part 63, Subpart DDDDD	63DDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
12H1	40 CFR Part 63, Subpart DDDDD	63DDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
19B1-H1	40 CFR Part 63, Subpart DDDDD	63DDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
19B1-H2#2	40 CFR Part 63, Subpart DDDDD	63DDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
19B1-H2#3	40 CFR Part 63, Subpart DDDDD	63DDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
19B2-H4	40 CFR Part 63, Subpart DDDDD	63DDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
19H3	40 CFR Part 63, Subpart DDDDD	63DDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
19H5#1	40 CFR Part 63, Subpart DDDDD	63DDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
19H5#2	40 CFR Part 63, Subpart DDDDD	63DDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
19H6	40 CFR Part 63, Subpart DDDDD	63DDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
22H1	40 CFR Part 63, Subpart DDDDD	63DDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
25H1	40 CFR Part 63, Subpart DDDDD	63DDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
26H1	40 CFR Part 63, Subpart DDDDD	63DDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
28H1	40 CFR Part 63, Subpart DDDDD	63DDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
29H4	40 CFR Part 63, Subpart DDDDD	63DDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
2H1	40 CFR Part 63, Subpart DDDDD	63DDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
2H2	40 CFR Part 63, Subpart DDDDD	63DDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
36H1	40 CFR Part 63, Subpart DDDDD	63DDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
40H1	40 CFR Part 63, Subpart DDDDD	63DDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
42H1	40 CFR Part 63, Subpart DDDDD	63DDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
42H2	40 CFR Part 63, Subpart DDDDD	63DDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
42H3	40 CFR Part 63, Subpart DDDDD	63DDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
4H1	40 CFR Part 63, Subpart DDDDD	63DDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
4H2	40 CFR Part 63, Subpart DDDDD	63DDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
50H1	40 CFR Part 63, Subpart DDDDD	63DDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
50HT1	40 CFR Part 63, Subpart DDDDD	63DDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
50HT2	40 CFR Part 63, Subpart DDDDD	63DDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
50HT3	40 CFR Part 63, Subpart DDDDD	63DDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
51H1	40 CFR Part 63, Subpart DDDDD	63DDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
5H1	40 CFR Part 63, Subpart DDDDD	63DDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
5H2	40 CFR Part 63, Subpart DDDDD	63DDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
5H3	40 CFR Part 63, Subpart DDDDD	63DDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
6H1	40 CFR Part 63, Subpart DDDDD	63DDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
6H3	40 CFR Part 63, Subpart DDDDD	63DDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
7H1	40 CFR Part 63, Subpart DDDDD	63DDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
7H2	40 CFR Part 63, Subpart DDDDD	63DDDDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
7H3	40 CFR Part 63, Subpart DDDDD	63DDDDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
7H4	40 CFR Part 63, Subpart DDDDD	63DDDDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
98H1	40 CFR Part 63, Subpart DDDDD	63DDDDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
9H1	40 CFR Part 63, Subpart DDDDD	63DDDDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began on or before June 4, 2010.	
81B17	40 CFR Part 60, Subpart D	60D	Construction/Modification Date = On or before August 17, 1971.	
81B17	40 CFR Part 60, Subpart Dc	60Dc	Construction/Modification Date = On or before June 9, 1989.	
81B17	40 CFR Part 63, Subpart DDDDD	63DDDDDD	Construction/Reconstruction Date = Construction or reconstruction began on or before June 4, 2010.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
85B2	40 CFR Part 60, Subpart Db	60Db-1	<p>Construction/Modification Date = Modified after February 28, 2005.</p> <p>D-Series Fuel Type #1 = Gaseous fossil fuel other than natural gas and coal-derived synthetic fuel meeting the definition of natural gas.</p> <p>Heat Input Capacity = Heat input capacity is greater than 250 MMBtu/hr (73 MW).</p> <p>PM Monitoring Type = No particulate monitoring.</p> <p>Facility Type = The affected facility includes a fuel gas combustion device.</p> <p>Opacity Monitoring Type = Continuous emissions monitoring system for carbon monoxide (CO) installed and operated per 40 CFR § 60.48b(j)(4)</p> <p>Subpart Da = The affected facility does not meet applicability requirements of 40 CFR Part 60, Subpart Da.</p> <p>60.43b(h)(2) Alternative = The facility is electing to use the alternative requirements of § 60.43b(h)(2) for PM.</p> <p>Changes to Existing Affected Facility = No change has been made to the existing steam generating unit, which was not previously subject to 40 CFR Part 60, Subpart Db, for the sole purpose of combusting gases containing totally reduced sulfur as defined under 40 CFR § 60.281.</p> <p>Monitoring Device = An instrument is in place for continuous monitoring and recording the concentration (dry basis) of hydrogen sulfide in fuel gasses before being burned in any fuel gas combustion device.</p> <p>NOx Monitoring Type = Continuous emission monitoring system.</p> <p>Common Fuel Source = The fuel gas combustion device has a common fuel source with other fuel gas combustion devices.</p> <p>Electrical or Mechanical Output = 10% or less of the annual output is electrical or mechanical.</p> <p>SO2 Monitoring Type = No SO₂ monitoring.</p> <p>Subpart Ea, Eb or AAAA = The affected facility does not meet applicability requirements of and is subject to 40 CFR Part 60, Subpart Ea, Eb or AAAA.</p> <p>Subpart J = The affected facility meets applicability requirements of 40 CFR Part 60, Subpart J.</p> <p>Subpart KKKK = The affected facility is not a heat recovery steam generator associated with combined cycle gas turbines and that meets applicability requirements of and is subject to 40 CFR Part 60, Subpart KKKK.</p> <p>Technology Type = None.</p> <p>ACF Option - SO₂ = Other ACF or no ACF.</p> <p>Subpart Cb or BBBB = The affected facility is not covered by an EPA approved State or Federal section 111(d)/129 plan implementing 40 CFR Part 60, Subpart Cb or BBBB emission guidelines.</p> <p>Unit Type = OTHER UNIT TYPE</p> <p>ACF Option - PM = Other ACF or no ACF.</p> <p>60.49Da(n) Alternative = The facility is not using the § 60.49Da(n) alternative.</p> <p>ACF Option - NO_x = Other ACF or no ACF.</p> <p>60.49Da(m) Alternative = The facility is not using the § 60.49Da(m) alternative.</p> <p>Heat Input Wood = The facility combusts no wood or less than 30% wood by heat input.</p>	
85B2	40 CFR Part 63, Subpart DDDDD	63DDDDDD	Construction/Reconstruction Date = Construction or reconstruction began on or before June 4, 2010.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
BLR12	40 CFR Part 60, Subpart Db	60Db-1	<p>60.42b(k)(2) Low Sulfur Exemption = The § 60.42b(k)(2) exemption applies.</p> <p>Construction/Modification Date = Constructed or reconstructed after February 28, 2005.</p> <p>D-Series Fuel Type #1 = Natural gas.</p> <p>Heat Input Capacity = Heat input capacity is greater than 250 MMBtu/hr (73 MW).</p> <p>PM Monitoring Type = No particulate monitoring.</p> <p>Facility Type = The affected facility includes a fuel gas combustion device.</p> <p>Opacity Monitoring Type = Continuous emissions monitoring system for carbon monoxide (CO) installed and operated per 40 CFR § 60.48b(j)(4)</p> <p>Subpart Da = The affected facility does not meet applicability requirements of 40 CFR Part 60, Subpart Da.</p> <p>Changes to Existing Affected Facility = No change has been made to the existing steam generating unit, which was not previously subject to 40 CFR Part 60, Subpart Db, for the sole purpose of combusting gases containing totally reduced sulfur as defined under 40 CFR § 60.281.</p> <p>Monitoring Device = An instrument is in place for continuous monitoring and recording the concentration (dry basis) of hydrogen sulfide in fuel gasses before being burned in any fuel gas combustion device.</p> <p>NOx Monitoring Type = Continuous emission monitoring system.</p> <p>Subpart D = The affected facility does not meet the applicability requirements of 40 CFR Part 60, Subpart D.</p> <p>Common Fuel Source = The fuel gas combustion device has a common fuel source with other fuel gas combustion devices.</p> <p>Electrical or Mechanical Output = 10% or less of the annual output is electrical or mechanical.</p> <p>SO2 Monitoring Type = No SO₂ monitoring.</p> <p>Subpart Ea, Eb or AAAA = The affected facility does not meet applicability requirements of and is subject to 40 CFR Part 60, Subpart Ea, Eb or AAAA.</p> <p>Subpart J = The affected facility meets applicability requirements of 40 CFR Part 60, Subpart J.</p> <p>Subpart KKKK = The affected facility is not a heat recovery steam generator associated with combined cycle gas turbines and that meets applicability requirements of and is subject to 40 CFR Part 60, Subpart KKKK.</p> <p>Technology Type = None.</p> <p>ACF Option - SO₂ = Other ACF or no ACF.</p> <p>Subpart Cb or BBBB = The affected facility is not covered by an EPA approved State or Federal section 111(d)/129 plan implementing 40 CFR Part 60, Subpart Cb or BBBB emission guidelines.</p> <p>Unit Type = OTHER UNIT TYPE</p> <p>ACF Option - PM = Other ACF or no ACF.</p> <p>Heat Release Rate = Natural gas oil with a heat release rate greater than 70 MBtu/hr/ft³.</p> <p>60.49Da(n) Alternative = The facility is not using the § 60.49Da(n) alternative.</p> <p>ACF Option - NOx = Other ACF or no ACF.</p> <p>60.49Da(m) Alternative = The facility is not using the § 60.49Da(m) alternative.</p>	<p>Replaced engine driven 40 CFR Part 60, Subpart Db/SO₂ results with manually added high level 40 CFR Part 60, Subpart Ja (since rules reference table have not yet been developed), per 60.40b(c).</p>

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
BLR12	40 CFR Part 60, Subpart Db	60Db-2	<p>60.42b(k)(2) Low Sulfur Exemption = The § 60.42b(k)(2) exemption applies.</p> <p>Construction/Modification Date = Constructed or reconstructed after February 28, 2005.</p> <p>D-Series Fuel Type #1 = Gaseous fossil fuel other than natural gas and coal-derived synthetic fuel meeting the definition of natural gas.</p> <p>Heat Input Capacity = Heat input capacity is greater than 250 MMBtu/hr (73 MW).</p> <p>PM Monitoring Type = No particulate monitoring.</p> <p>Facility Type = The affected facility includes a fuel gas combustion device.</p> <p>Opacity Monitoring Type = Continuous emissions monitoring system for carbon monoxide (CO) installed and operated per 40 CFR § 60.48b(j)(4)</p> <p>Subpart Da = The affected facility does not meet applicability requirements of 40 CFR Part 60, Subpart Da.</p> <p>Changes to Existing Affected Facility = No change has been made to the existing steam generating unit, which was not previously subject to 40 CFR Part 60, Subpart Db, for the sole purpose of combusting gases containing totally reduced sulfur as defined under 40 CFR § 60.281.</p> <p>Monitoring Device = An instrument is in place for continuous monitoring and recording the concentration (dry basis) of hydrogen sulfide in fuel gasses before being burned in any fuel gas combustion device.</p> <p>NOx Monitoring Type = Continuous emission monitoring system.</p> <p>Subpart D = The affected facility does not meet the applicability requirements of 40 CFR Part 60, Subpart D.</p> <p>Common Fuel Source = The fuel gas combustion device has a common fuel source with other fuel gas combustion devices.</p> <p>Electrical or Mechanical Output = 10% or less of the annual output is electrical or mechanical.</p> <p>SO2 Monitoring Type = No SO₂ monitoring.</p> <p>Subpart Ea, Eb or AAAA = The affected facility does not meet applicability requirements of and is subject to 40 CFR Part 60, Subpart Ea, Eb or AAAA.</p> <p>Subpart J = The affected facility meets applicability requirements of 40 CFR Part 60, Subpart J.</p> <p>Subpart KKKK = The affected facility is not a heat recovery steam generator associated with combined cycle gas turbines and that meets applicability requirements of and is subject to 40 CFR Part 60, Subpart KKKK.</p> <p>Technology Type = None.</p> <p>ACF Option - SO₂ = Other ACF or no ACF.</p> <p>Subpart Cb or BBBB = The affected facility is not covered by an EPA approved State or Federal section 111(d)/129 plan implementing 40 CFR Part 60, Subpart Cb or BBBB emission guidelines.</p> <p>Unit Type = OTHER UNIT TYPE</p> <p>ACF Option - PM = Other ACF or no ACF.</p> <p>Heat Release Rate = Natural gas oil with a heat release rate greater than 70 MBtu/hr/ft³.</p> <p>60.49Da(n) Alternative = The facility is not using the § 60.49Da(n) alternative.</p> <p>ACF Option - NOx = Other ACF or no ACF.</p> <p>60.49Da(m) Alternative = The facility is not using the § 60.49Da(m) alternative.</p>	Replaced engine driven 40 CFR Part 60, Subpart Db/SO ₂ results with manually added high level 40 CFR Part 60, Subpart Ja (since rules reference table have not yet been developed), per 60.40b(c).
BLR12	40 CFR Part 63, Subpart DDDDD	63DDDDDD	Construction/Reconstruction Date = Construction or reconstruction began after June 4, 2010.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
SKIDBLR	40 CFR Part 60, Subpart Db	60Db-1	<p>60.42b(k)(2) Low Sulfur Exemption = The § 60.42b(k)(2) exemption applies.</p> <p>Construction/Modification Date = Constructed or reconstructed after February 28, 2005.</p> <p>D-Series Fuel Type #1 = Natural gas.</p> <p>Heat Input Capacity = Heat input capacity is greater than 250 MMBtu/hr (73 MW).</p> <p>PM Monitoring Type = No particulate monitoring.</p> <p>Opacity Monitoring Type = No particulate (opacity) monitoring.</p> <p>Subpart Da = The affected facility does not meet applicability requirements of 40 CFR Part 60, Subpart Da.</p> <p>Changes to Existing Affected Facility = No change has been made to the existing steam generating unit, which was not previously subject to 40 CFR Part 60, Subpart Db, for the sole purpose of combusting gases containing totally reduced sulfur as defined under 40 CFR § 60.281.</p> <p>NOx Monitoring Type = Continuous emission monitoring system.</p> <p>Electrical or Mechanical Output = 10% or less of the annual output is electrical or mechanical.</p> <p>SO2 Monitoring Type = No SO₂ monitoring.</p> <p>Subpart Ea, Eb or AAAA = The affected facility does not meet applicability requirements of and is subject to 40 CFR Part 60, Subpart Ea, Eb or AAAA.</p> <p>Subpart J = The affected facility does not meet applicability requirements of 40 CFR Part 60, Subpart J.</p> <p>Subpart E = The affected facility does not meet applicability requirements of 40 CFR Part 60, Subpart E.</p> <p>Subpart KKKK = The affected facility is not a heat recovery steam generator associated with combined cycle gas turbines and that meets applicability requirements of and is subject to 40 CFR Part 60, Subpart KKKK.</p> <p>Technology Type = None.</p> <p>ACF Option - SO₂ = Other ACF or no ACF.</p> <p>Subpart Cb or BBBB = The affected facility is not covered by an EPA approved State or Federal section 111(d)/129 plan implementing 40 CFR Part 60, Subpart Cb or BBBB emission guidelines.</p> <p>Unit Type = OTHER UNIT TYPE</p> <p>ACF Option - PM = Other ACF or no ACF.</p> <p>Heat Release Rate = Natural gas oil with a heat release rate greater than 70 MBtu/hr/ft³.</p> <p>60.49Da(n) Alternative = The facility is not using the § 60.49Da(n) alternative.</p> <p>ACF Option - NO_x = Other ACF or no ACF.</p> <p>60.49Da(m) Alternative = The facility is not using the § 60.49Da(m) alternative.</p>	<p>Replaced engine driven 40 CFR Part 60, Subpart Db/SO₂ results with manually added high level 40 CFR Part 60, Subpart Ja (since rules reference table have not yet been developed), per 60.40b(c).</p>

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
SKIDBLR	40 CFR Part 60, Subpart Db	60Db-2	<p>60.42b(k)(2) Low Sulfur Exemption = The § 60.42b(k)(2) exemption applies.</p> <p>Construction/Modification Date = Constructed or reconstructed after February 28, 2005.</p> <p>D-Series Fuel Type #1 = Natural gas.</p> <p>D-Series Fuel Type #2 = Gaseous fossil fuel other than natural gas and coal-derived synthetic fuel meeting the definition of natural gas.</p> <p>Heat Input Capacity = Heat input capacity is greater than 250 MMBtu/hr (73 MW).</p> <p>PM Monitoring Type = No particulate monitoring.</p> <p>Facility Type = The affected facility includes a fuel gas combustion device.</p> <p>Opacity Monitoring Type = No particulate (opacity) monitoring.</p> <p>Subpart Da = The affected facility does not meet applicability requirements of 40 CFR Part 60, Subpart Da.</p> <p>Changes to Existing Affected Facility = No change has been made to the existing steam generating unit, which was not previously subject to 40 CFR Part 60, Subpart Db, for the sole purpose of combusting gases containing totally reduced sulfur as defined under 40 CFR § 60.281.</p> <p>Monitoring Device = An instrument is in place for continuous monitoring and recording the concentration (dry basis) of hydrogen sulfide in fuel gasses before being burned in any fuel gas combustion device.</p> <p>NOx Monitoring Type = Continuous emission monitoring system.</p> <p>Common Fuel Source = The fuel gas combustion device has a common fuel source with other fuel gas combustion devices.</p> <p>Electrical or Mechanical Output = 10% or less of the annual output is electrical or mechanical.</p> <p>SO2 Monitoring Type = No SO₂ monitoring.</p> <p>Subpart Ea, Eb or AAAA = The affected facility does not meet applicability requirements of and is subject to 40 CFR Part 60, Subpart Ea, Eb or AAAA.</p> <p>Subpart J = The affected facility does not meet applicability requirements of 40 CFR Part 60, Subpart J.</p> <p>Subpart E = The affected facility does not meet applicability requirements of 40 CFR Part 60, Subpart E.</p> <p>Subpart KKKK = The affected facility is not a heat recovery steam generator associated with combined cycle gas turbines and that meets applicability requirements of and is subject to 40 CFR Part 60, Subpart KKKK.</p> <p>Technology Type = None.</p> <p>ACF Option - SO₂ = Other ACF or no ACF.</p> <p>Subpart Cb or BBBB = The affected facility is not covered by an EPA approved State or Federal section 111(d)/129 plan implementing 40 CFR Part 60, Subpart Cb or BBBB emission guidelines.</p> <p>Unit Type = OTHER UNIT TYPE</p> <p>ACF Option - PM = Other ACF or no ACF.</p> <p>Heat Release Rate = Natural gas oil with a heat release rate greater than 70 MBtu/hr/ft³.</p> <p>60.49Da(n) Alternative = The facility is not using the § 60.49Da(n) alternative.</p> <p>ACF Option - NO_x = Other ACF or no ACF.</p> <p>60.49Da(m) Alternative = The facility is not using the § 60.49Da(m) alternative.</p>	Replaced engine driven 40 CFR Part 60, Subpart Db/SO ₂ results with manually added high level 40 CFR Part 60, Subpart Ja (since rules reference table have not yet been developed), per 60.40b(c).
SKIDBLR	40 CFR Part 63, Subpart DDDDD	63DDDDDD	Construction/Reconstruction Date = Construction or reconstruction began on or before June 4, 2010.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
66FL1	30 TAC Chapter 111, Visible Emissions	111.111FLARE	Acid Gases Only = Flare is not used only as an acid gas flare as defined in 30 TAC § 101.1. Emergency/Upset Conditions Only = Flare is used under conditions other than emergency or upset conditions. Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.	
66FL1	40 CFR Part 60, Subpart A	60.18-FLARE	Subject to 40 CFR § 60.18 = Flare is subject to 40 CFR § 60.18. Adhering to Heat Content Specifications = Adhering to the heat content specifications in 40 CFR § 60.18(c)(3)(ii) and the maximum tip velocity specifications in 40 CFR § 60.18(c)(4). Flare Assist Type = Steam-assisted Flare Exit Velocity = Flare exit velocity is less than 60 ft/s (18.3 m/sec)	
66FL1	40 CFR Part 63, Subpart A	63CC-FLARE	Required Under 40 CFR Part 63 = Flare is required by a Subpart under 40 CFR Part 63. Heat Content Specification = Adhering to the heat content specifications in 40 CFR § 63.11(b)(6)(ii) and the maximum tip velocity specifications in 40 CFR § 63.11(b)(7) or 40 CFR § 63.11(b)(8). Flare Assist Type = Steam assisted Flare Exit Velocity = Flare exit velocity is less than 60 ft/s (18.3 m/sec)	
66FL12	30 TAC Chapter 111, Visible Emissions	111.111FLARE	Acid Gases Only = Flare is not used only as an acid gas flare as defined in 30 TAC § 101.1. Emergency/Upset Conditions Only = Flare is used under conditions other than emergency or upset conditions. Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.	
66FL12	40 CFR Part 60, Subpart A	60.18 FLARE	Subject to 40 CFR § 60.18 = Flare is subject to 40 CFR § 60.18. Adhering to Heat Content Specifications = Adhering to the heat content specifications in 40 CFR § 60.18(c)(3)(ii) and the maximum tip velocity specifications in 40 CFR § 60.18(c)(4). Flare Assist Type = Steam-assisted Flare Exit Velocity = Flare exit velocity is less than 60 ft/s (18.3 m/sec)	
66FL12	40 CFR Part 63, Subpart A	60VV-FLARE	Required Under 40 CFR Part 63 = Flare is not required by a Subpart under 40 CFR Part 63.	
66FL12	40 CFR Part 63, Subpart A	63H-FLARE	Required Under 40 CFR Part 63 = Flare is required by a Subpart under 40 CFR Part 63. Heat Content Specification = Adhering to the heat content specifications in 40 CFR § 63.11(b)(6)(ii) and the maximum tip velocity specifications in 40 CFR § 63.11(b)(7) or 40 CFR § 63.11(b)(8). Flare Assist Type = Steam assisted Flare Exit Velocity = Flare exit velocity is less than 60 ft/s (18.3 m/sec) Heating Value of Gas = Heating value is less than or equal to 1000 Btu/scf (37.3 MJ/scm).	
66FL13	30 TAC Chapter 111, Visible Emissions	111.111ACF	Acid Gases Only = Flare is not used only as an acid gas flare as defined in 30 TAC § 101.1. Emergency/Upset Conditions Only = Flare is used only under emergency or upset conditions.	
66FL13	40 CFR Part 60, Subpart A	60.18 FLARE	Subject to 40 CFR § 60.18 = Flare is subject to 40 CFR § 60.18. Adhering to Heat Content Specifications = Adhering to the heat content specifications in 40 CFR § 60.18(c)(3)(ii) and the maximum tip velocity specifications in 40 CFR § 60.18(c)(4). Flare Assist Type = Non-assisted Flare Exit Velocity = Flare exit velocity is less than 60 ft/s (18.3 m/sec)	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
66FL13	40 CFR Part 63, Subpart A	63A	Required Under 40 CFR Part 63 = Flare is not required by a Subpart under 40 CFR Part 63.	
66FL13	40 CFR Part 63, Subpart A	63CC-FLARE	Required Under 40 CFR Part 63 = Flare is required by a Subpart under 40 CFR Part 63. Heat Content Specification = Adhering to the heat content specifications in 40 CFR § 63.11(b)(6)(ii) and the maximum tip velocity specifications in 40 CFR § 63.11(b)(7) or 40 CFR § 63.11(b)(8). Flare Assist Type = Non-assisted Flare Exit Velocity = Flare exit velocity is less than 60 ft/s (18.3 m/sec)	
66FL2	30 TAC Chapter 111, Visible Emissions	111.111FLARE	Acid Gases Only = Flare is not used only as an acid gas flare as defined in 30 TAC § 101.1. Emergency/Upset Conditions Only = Flare is used under conditions other than emergency or upset conditions. Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.	
66FL2	40 CFR Part 60, Subpart A	60.18-FLARE	Subject to 40 CFR § 60.18 = Flare is subject to 40 CFR § 60.18. Adhering to Heat Content Specifications = Adhering to the heat content specifications in 40 CFR § 60.18(c)(3)(ii) and the maximum tip velocity specifications in 40 CFR § 60.18(c)(4). Flare Assist Type = Steam-assisted Flare Exit Velocity = Flare exit velocity is less than 60 ft/s (18.3 m/sec)	
66FL2	40 CFR Part 63, Subpart A	63CC-FLARE	Required Under 40 CFR Part 63 = Flare is required by a Subpart under 40 CFR Part 63. Heat Content Specification = Adhering to the heat content specifications in 40 CFR § 63.11(b)(6)(ii) and the maximum tip velocity specifications in 40 CFR § 63.11(b)(7) or 40 CFR § 63.11(b)(8). Flare Assist Type = Steam assisted Flare Exit Velocity = Flare exit velocity is less than 60 ft/s (18.3 m/sec)	
66FL3	30 TAC Chapter 111, Visible Emissions	111.111FLARE	Acid Gases Only = Flare is not used only as an acid gas flare as defined in 30 TAC § 101.1. Emergency/Upset Conditions Only = Flare is used under conditions other than emergency or upset conditions. Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.	
66FL3	40 CFR Part 60, Subpart A	60A	Subject to 40 CFR § 60.18 = Flare is not subject to 40 CFR § 60.18.	
66FL3	40 CFR Part 63, Subpart A	63CC-FLARE	Required Under 40 CFR Part 63 = Flare is required by a Subpart under 40 CFR Part 63. Heat Content Specification = Adhering to the heat content specifications in 40 CFR § 63.11(b)(6)(ii) and the maximum tip velocity specifications in 40 CFR § 63.11(b)(7) or 40 CFR § 63.11(b)(8). Flare Assist Type = Steam assisted Flare Exit Velocity = Flare exit velocity is less than 60 ft/s (18.3 m/sec)	
F-11	40 CFR Part 60, Subpart GGGa	60GGGa-ALL	Construction/Modification Date = Affected facility was constructed, reconstructed or modified after November 7, 2006. Equipment Components = Components are present.	Since rules reference tables have not yet been developed for 40CFR Part 60, Subpart GGGa, the permit reviewer manually developed requirements based on applicant provided attributes.

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
F-11	40 CFR Part 63, Subpart CC	63CC	EQUIPMENT TYPE = FUGITIVE UNIT CONTAINS EQUIPMENT LISTED IN 40 CFR § 63.160(A) WHICH IS OPERATED IN ORGANIC HAZARDOUS AIR POLLUTANT SERVICE.	Due to 40 CFR Part 63, Subpart CC overlap, equipment leaks that are also subject to the provisions of 40 CFR Part 60, Subpart GGGa, are required to comply only with the provisions specified in 40 CFR Part 60, Subpart GGGa, per §63.640(p)(2).
F-11	40 CFR Part 63, Subpart H	63H	EQUIPMENT TYPE = FUGITIVE UNIT DOES NOT CONTAIN EQUIPMENT LISTED IN 40 CFR § 63.160(A) WHICH IS OPERATED IN ORGANIC HAZARDOUS AIR POLLUTANT SERVICE	
F-11	40 CFR Part 63, Subpart I	63I-1	PROCESS TYPE = NO	
F-13	40 CFR Part 60, Subpart KKK	60KKK	Facility Type = Affected facility is the group of all equipment except compressors within a process unit. Construction/Modification Date = On or before January 20, 1984.	
F-13	40 CFR Part 60, Subpart VV	60VV	Produces Chemicals = The fugitive unit is not part of a facility that produces as an intermediate or final product one or more of the chemicals listed in 40 CFR § 60.489.	
F-13	40 CFR Part 63, Subpart H	63H	EQUIPMENT TYPE = FUGITIVE UNIT DOES NOT CONTAIN EQUIPMENT LISTED IN 40 CFR § 63.160(A) WHICH IS OPERATED IN ORGANIC HAZARDOUS AIR POLLUTANT SERVICE	
F-1-6-PB	40 CFR Part 63, Subpart CC	63CCVV-ALL	CLOSED VENT (OR VAPOR COLLECTION) SYSTEMS = YES ENCLOSED COMBUSTION DEVICE = YES EXISTING SOURCE = YES FLARE = YES VAPOR RECOVERY SYSTEM = YES CLOSED VENT (OR VAPOR COLLETION) SYSTEMS EQUIVALENT EMISSION LIMITATION = NO COMPLYING WITH TITLE 40 CFR 60 SUBPART VV = YES ENCLOSED COMBUSTION DEVICE EQUIVALENT EMISSION LIMITATION = NO FLARE EQUIVALENT EMISSION LIMITATION = NO VAPOR RECOVERY SYSTEM EQUIVALENT EMISSION LIMITATION = NO CLOSED VENT (OR VAPOR COLLETION) SYSTEMS COMPLYING WITH § 60.482-10 = YES ENCLOSED COMBUSTION DEVICE COMPLYING WITH § 60.482-10 = YES FLARE COMPLYING WITH §60.482-10 = YES VAPOR RECOVERY SYSTEM COMPLYING WITH § 60.482-10 = YES	
F-19-1	40 CFR Part 60, Subpart GGGa	60GGGa-ALL	Construction/Modification Date = Affected facility was constructed, reconstructed or modified after November 7, 2006. Equipment Components = Components are present.	Since rules reference tables have not yet been developed for 40CFR Part 60, Subpart GGGa, the permit reviewer manually developed requirements based on applicant provided attributes.

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
F-19-1	40 CFR Part 63, Subpart CC	63CC	EQUIPMENT TYPE = FUGITIVE UNIT CONTAINS EQUIPMENT LISTED IN 40 CFR § 63.160(A) WHICH IS OPERATED IN ORGANIC HAZARDOUS AIR POLLUTANT SERVICE.	Due to 40 CFR Part 63, Subpart CC overlap, equipment leaks that are also subject to the provisions of 40 CFR Part 60, Subpart GGGa, are required to comply only with the provisions specified in 40 CFR Part 60, Subpart GGGa, per §63.640(p)(2).
F-19-1	40 CFR Part 60, Subpart VV	60VV-1	Produces Chemicals = The fugitive unit is not part of a facility that produces as an intermediate or final product one or more of the chemicals listed in 40 CFR § 60.489.	
F-19-1	40 CFR Part 61, Subpart V	61V-1	Vacuum Service = The fugitive unit does not contain components in vacuum service. VHAP Service = The fugitive unit contains no components in VHAP service.	
F-19-1	40 CFR Part 63, Subpart I	63I-1	PROCESS TYPE = NO	
F-19-2	40 CFR Part 60, Subpart GGGa	60GGGa-ALL	Construction/Modification Date = Affected facility was constructed, reconstructed or modified after November 7, 2006. Equipment Components = Components are present.	Since rules reference tables have not yet been developed for 40CFR Part 60, Subpart GGGa, the permit reviewer manually developed requirements based on applicant provided attributes.
F-19-2	40 CFR Part 63, Subpart CC	63CC	EQUIPMENT TYPE = FUGITIVE UNIT CONTAINS EQUIPMENT LISTED IN 40 CFR § 63.160(A) WHICH IS OPERATED IN ORGANIC HAZARDOUS AIR POLLUTANT SERVICE.	Due to 40 CFR Part 63, Subpart CC overlap, equipment leaks that are also subject to the provisions of 40 CFR Part 60, Subpart GGGa, are required to comply only with the provisions specified in 40 CFR Part 60, Subpart GGGa, per §63.640(p)(2).
F-19-2	40 CFR Part 60, Subpart VV	60VV-1	Produces Chemicals = The fugitive unit is not part of a facility that produces as an intermediate or final product one or more of the chemicals listed in 40 CFR § 60.489.	
F-19-2	40 CFR Part 61, Subpart V	61V-1	Vacuum Service = The fugitive unit does not contain components in vacuum service. VHAP Service = The fugitive unit contains no components in VHAP service.	
F-19-2	40 CFR Part 63, Subpart I	63I-1	PROCESS TYPE = NO	
F-19-3	40 CFR Part 60, Subpart GGGa	60GGGa-ALL	Construction/Modification Date = Affected facility was constructed, reconstructed or modified after November 7, 2006. Equipment Components = Components are present.	Since rules reference tables have not yet been developed for 40CFR Part 60, Subpart GGGa, the permit reviewer manually developed requirements based on applicant provided attributes.

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
F-19-3	40 CFR Part 63, Subpart CC	63CC	EQUIPMENT TYPE = FUGITIVE UNIT CONTAINS EQUIPMENT LISTED IN 40 CFR § 63.160(A) WHICH IS OPERATED IN ORGANIC HAZARDOUS AIR POLLUTANT SERVICE.	Due to 40 CFR Part 63, Subpart CC overlap, equipment leaks that are also subject to the provisions of 40 CFR Part 60, Subpart GGGa, are required to comply only with the provisions specified in 40 CFR Part 60, Subpart GGGa, per §63.640(p)(2).
F-2	40 CFR Part 60, Subpart GGGa	60GGGa-ALL	Construction/Modification Date = Affected facility was constructed, reconstructed or modified after November 7, 2006. Equipment Components = Components are present.	Since rules reference tables have not yet been developed for 40CFR Part 60, Subpart GGGa, the permit reviewer manually developed requirements based on applicant provided attributes.
F-2	40 CFR Part 63, Subpart CC	63CC	EQUIPMENT TYPE = FUGITIVE UNIT CONTAINS EQUIPMENT LISTED IN 40 CFR § 63.160(A) WHICH IS OPERATED IN ORGANIC HAZARDOUS AIR POLLUTANT SERVICE.	Due to 40 CFR Part 63, Subpart CC overlap, equipment leaks that are also subject to the provisions of 40 CFR Part 60, Subpart GGGa, are required to comply only with the provisions specified in 40 CFR Part 60, Subpart GGGa, per §63.640(p)(2).
F-2	40 CFR Part 63, Subpart I	63I-1	PROCESS TYPE = NO	
F-2-1	40 CFR Part 60, Subpart GGGa	60GGGa-ALL	Construction/Modification Date = Affected facility was constructed, reconstructed or modified after November 7, 2006. Equipment Components = Components are present.	Since rules reference tables have not yet been developed for 40CFR Part 60, Subpart GGGa, the permit reviewer manually developed requirements based on applicant provided attributes.
F-2-1	40 CFR Part 63, Subpart CC	63CC	EQUIPMENT TYPE = FUGITIVE UNIT CONTAINS EQUIPMENT LISTED IN 40 CFR § 63.160(A) WHICH IS OPERATED IN ORGANIC HAZARDOUS AIR POLLUTANT SERVICE.	Due to 40 CFR Part 63, Subpart CC overlap, equipment leaks that are also subject to the provisions of 40 CFR Part 60, Subpart GGGa, are required to comply only with the provisions specified in 40 CFR Part 60, Subpart GGGa, per §63.640(p)(2).
F-2-1	40 CFR Part 60, Subpart VV	60VV-1	Produces Chemicals = The fugitive unit is not part of a facility that produces as an intermediate or final product one or more of the chemicals listed in 40 CFR § 60.489.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
F-2-1	40 CFR Part 61, Subpart V	61V-1	Vacuum Service = The fugitive unit does not contain components in vacuum service. VHAP Service = The fugitive unit contains no components in VHAP service.	
F-2-1	40 CFR Part 63, Subpart I	63I-1	PROCESS TYPE = NO	
F-4	40 CFR Part 60, Subpart GGGa	60GGGa-ALL	Construction/Modification Date = Affected facility was constructed, reconstructed or modified after November 7, 2006. Equipment Components = Components are present.	Since rules reference tables have not yet been developed for 40CFR Part 60, Subpart GGGa, the permit reviewer manually developed requirements based on applicant provided attributes.
F-4	40 CFR Part 63, Subpart CC	63CC	EQUIPMENT TYPE = FUGITIVE UNIT CONTAINS EQUIPMENT LISTED IN 40 CFR § 63.160(A) WHICH IS OPERATED IN ORGANIC HAZARDOUS AIR POLLUTANT SERVICE.	Due to 40 CFR Part 63, Subpart CC overlap, equipment leaks that are also subject to the provisions of 40 CFR Part 60, Subpart GGGa, are required to comply only with the provisions specified in 40 CFR Part 60, Subpart GGGa, per §63.640(p)(2).
F-4	40 CFR Part 60, Subpart KKK	60KKK	Facility Type = Affected facility is the group of all equipment except compressors within a process unit. Construction/Modification Date = On or before January 20, 1984.	
F-4	40 CFR Part 60, Subpart VV	60VV	Produces Chemicals = The fugitive unit is not part of a facility that produces as an intermediate or final product one or more of the chemicals listed in 40 CFR § 60.489.	
F-4	40 CFR Part 63, Subpart H	63H	EQUIPMENT TYPE = FUGITIVE UNIT DOES NOT CONTAIN EQUIPMENT LISTED IN 40 CFR § 63.160(A) WHICH IS OPERATED IN ORGANIC HAZARDOUS AIR POLLUTANT SERVICE	
F-4	40 CFR Part 63, Subpart I	63I-1	PROCESS TYPE = NO	
F-5	40 CFR Part 60, Subpart GGGa	60GGGa-ALL	Construction/Modification Date = Affected facility was constructed, reconstructed or modified after November 7, 2006. Equipment Components = Components are present.	Since rules reference tables have not yet been developed for 40CFR Part 60, Subpart GGGa, the permit reviewer manually developed requirements based on applicant provided attributes.
F-5	40 CFR Part 63, Subpart CC	63CC	EQUIPMENT TYPE = FUGITIVE UNIT CONTAINS EQUIPMENT LISTED IN 40 CFR § 63.160(A) WHICH IS OPERATED IN ORGANIC HAZARDOUS AIR POLLUTANT SERVICE.	Due to 40 CFR Part 63, Subpart CC overlap, equipment leaks that are also subject to the provisions of 40 CFR Part 60, Subpart GGGa, are required to comply only with the provisions specified in 40 CFR Part 60, Subpart GGGa, per §63.640(p)(2).

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
F-5	40 CFR Part 60, Subpart VV	60VV-1	Produces Chemicals = The fugitive unit is not part of a facility that produces as an intermediate or final product one or more of the chemicals listed in 40 CFR § 60.489.	
F-5	40 CFR Part 61, Subpart V	61V-1	Vacuum Service = The fugitive unit does not contain components in vacuum service. VHAP Service = The fugitive unit contains no components in VHAP service.	
F-5	40 CFR Part 63, Subpart I	63I-1	PROCESS TYPE = NO	
F-53-2	40 CFR Part 63, Subpart CC	63CCVV-ALL	CLOSED VENT (OR VAPOR COLLECTION) SYSTEMS = YES ENCLOSED COMBUSTION DEVICE = YES EXISTING SOURCE = YES FLARE = YES VAPOR RECOVERY SYSTEM = YES CLOSED VENT (OR VAPOR COLLETION) SYSTEMS EQUIVALENT EMISSION LIMITATION = NO COMPLYING WITH TITLE 40 CFR 60 SUBPART VV = YES ENCLOSED COMBUSTION DEVICE EQUIVALENT EMISSION LIMITATION = NO FLARE EQUIVALENT EMISSION LIMITATION = NO VAPOR RECOVERY SYSTEM EQUIVALENT EMISSION LIMITATION = NO AMEL = NO CLOSED VENT (OR VAPOR COLLETION) SYSTEMS COMPLYING WITH § 60.482-10 = YES ENCLOSED COMBUSTION DEVICE COMPLYING WITH § 60.482-10 = YES FLARE COMPLYING WITH §60.482-10 = YES VAPOR RECOVERY SYSTEM COMPLYING WITH § 60.482-10 = YES	
F-6	40 CFR Part 60, Subpart VV	60VV-1	Produces Chemicals = The fugitive unit is not part of a facility that produces as an intermediate or final product one or more of the chemicals listed in 40 CFR § 60.489.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
F-6	40 CFR Part 63, Subpart CC	63CCVV-ALL	CLOSED VENT (OR VAPOR COLLECTION) SYSTEMS = YES ENCLOSED COMBUSTION DEVICE = YES EXISTING SOURCE = YES FLARE = YES VAPOR RECOVERY SYSTEM = YES CLOSED VENT (OR VAPOR COLLETION) SYSTEMS EQUIVALENT EMISSION LIMITATION = NO COMPLYING WITH TITLE 40 CFR 60 SUBPART VV = YES ENCLOSED COMBUSTION DEVICE EQUIVALENT EMISSION LIMITATION = NO FLARE EQUIVALENT EMISSION LIMITATION = NO VAPOR RECOVERY SYSTEM EQUIVALENT EMISSION LIMITATION = NO CLOSED VENT (OR VAPOR COLLETION) SYSTEMS COMPLYING WITH § 60.482-10 = YES ENCLOSED COMBUSTION DEVICE COMPLYING WITH § 60.482-10 = YES FLARE COMPLYING WITH §60.482-10 = YES VAPOR RECOVERY SYSTEM COMPLYING WITH § 60.482-10 = YES	
F-6	40 CFR Part 63, Subpart I	63I-1	PROCESS TYPE = NO	
F-66-3	40 CFR Part 63, Subpart CC	63CCVV-ALL	CLOSED VENT (OR VAPOR COLLECTION) SYSTEMS = YES ENCLOSED COMBUSTION DEVICE = YES EXISTING SOURCE = YES FLARE = YES VAPOR RECOVERY SYSTEM = YES CLOSED VENT (OR VAPOR COLLETION) SYSTEMS EQUIVALENT EMISSION LIMITATION = NO COMPLYING WITH TITLE 40 CFR 60 SUBPART VV = YES ENCLOSED COMBUSTION DEVICE EQUIVALENT EMISSION LIMITATION = NO FLARE EQUIVALENT EMISSION LIMITATION = NO VAPOR RECOVERY SYSTEM EQUIVALENT EMISSION LIMITATION = NO CLOSED VENT (OR VAPOR COLLETION) SYSTEMS COMPLYING WITH § 60.482-10 = YES ENCLOSED COMBUSTION DEVICE COMPLYING WITH § 60.482-10 = YES FLARE COMPLYING WITH §60.482-10 = YES VAPOR RECOVERY SYSTEM COMPLYING WITH § 60.482-10 = YES	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
F-66-FG	40 CFR Part 63, Subpart CC	63CCVV-ALL	<p>CLOSED VENT (OR VAPOR COLLECTION) SYSTEMS = YES</p> <p>ENCLOSED COMBUSTION DEVICE = YES</p> <p>EXISTING SOURCE = YES</p> <p>FLARE = YES</p> <p>VAPOR RECOVERY SYSTEM = YES</p> <p>CLOSED VENT (OR VAPOR COLLETION) SYSTEMS EQUIVALENT EMISSION LIMITATION = NO</p> <p>COMPLYING WITH TITLE 40 CFR 60 SUBPART VV = YES</p> <p>ENCLOSED COMBUSTION DEVICE EQUIVALENT EMISSION LIMITATION = NO</p> <p>FLARE EQUIVALENT EMISSION LIMITATION = NO</p> <p>VAPOR RECOVERY SYSTEM EQUIVALENT EMISSION LIMITATION = NO</p> <p>CLOSED VENT (OR VAPOR COLLETION) SYSTEMS COMPLYING WITH § 60.482-10 = YES</p> <p>ENCLOSED COMBUSTION DEVICE COMPLYING WITH § 60.482-10 = YES</p> <p>FLARE COMPLYING WITH §60.482-10 = YES</p> <p>VAPOR RECOVERY SYSTEM COMPLYING WITH § 60.482-10 = YES</p>	
F-67	40 CFR Part 60, Subpart GGGa	60GGGA-ALL	<p>Construction/Modification Date = Affected facility was constructed, reconstructed or modified after November 7, 2006.</p> <p>Equipment Components = Components are present.</p>	Since rules reference tables have not yet been developed for 40CFR Part 60, Subpart GGGa, the permit reviewer manually developed requirements based on applicant provided attributes.
F-67	40 CFR Part 63, Subpart CC	63CC	EQUIPMENT TYPE = FUGITIVE UNIT CONTAINS EQUIPMENT LISTED IN 40 CFR § 63.160(A) WHICH IS OPERATED IN ORGANIC HAZARDOUS AIR POLLUTANT SERVICE.	Due to 40 CFR Part 63, Subpart CC overlap, equipment leaks that are also subject to the provisions of 40 CFR Part 60, Subpart GGGa, are required to comply only with the provisions specified in 40 CFR Part 60, Subpart GGGa, per §63.640(p)(2).
F-68-1S	40 CFR Part 60, Subpart GGG	60GGG	CONSTRUCTION/MODIFICATION DATE = ON OR BEFORE JANUARY 4, 1983	
F-68-1S	40 CFR Part 60, Subpart KKK	60KKK	<p>Facility Type = Affected facility is the group of all equipment except compressors within a process unit.</p> <p>Construction/Modification Date = On or before January 20, 1984.</p>	
F-68-1S	40 CFR Part 60, Subpart VV	60VV	Produces Chemicals = The fugitive unit is not part of a facility that produces as an intermediate or final product one or more of the chemicals listed in 40 CFR § 60.489.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
F-68-1S	40 CFR Part 63, Subpart CC	63CCVV-ALL	CLOSED VENT (OR VAPOR COLLECTION) SYSTEMS = YES ENCLOSED COMBUSTION DEVICE = YES EXISTING SOURCE = YES FLARE = YES VAPOR RECOVERY SYSTEM = YES CLOSED VENT (OR VAPOR COLLETION) SYSTEMS EQUIVALENT EMISSION LIMITATION = NO COMPLYING WITH TITLE 40 CFR 60 SUBPART VV = YES ENCLOSED COMBUSTION DEVICE EQUIVALENT EMISSION LIMITATION = NO FLARE EQUIVALENT EMISSION LIMITATION = NO VAPOR RECOVERY SYSTEM EQUIVALENT EMISSION LIMITATION = NO CLOSED VENT (OR VAPOR COLLETION) SYSTEMS COMPLYING WITH § 60.482-10 = YES ENCLOSED COMBUSTION DEVICE COMPLYING WITH § 60.482-10 = YES FLARE COMPLYING WITH §60.482-10 = YES VAPOR RECOVERY SYSTEM COMPLYING WITH § 60.482-10 = YES	
F-68-1S	40 CFR Part 63, Subpart H	63H	EQUIPMENT TYPE = FUGITIVE UNIT DOES NOT CONTAIN EQUIPMENT LISTED IN 40 CFR § 63.160(A) WHICH IS OPERATED IN ORGANIC HAZARDOUS AIR POLLUTANT SERVICE	
F-68-2N	40 CFR Part 63, Subpart CC	63CCVV-ALL	CLOSED VENT (OR VAPOR COLLECTION) SYSTEMS = YES ENCLOSED COMBUSTION DEVICE = YES EXISTING SOURCE = YES FLARE = YES VAPOR RECOVERY SYSTEM = YES CLOSED VENT (OR VAPOR COLLETION) SYSTEMS EQUIVALENT EMISSION LIMITATION = NO COMPLYING WITH TITLE 40 CFR 60 SUBPART VV = YES ENCLOSED COMBUSTION DEVICE EQUIVALENT EMISSION LIMITATION = NO FLARE EQUIVALENT EMISSION LIMITATION = NO VAPOR RECOVERY SYSTEM EQUIVALENT EMISSION LIMITATION = NO CLOSED VENT (OR VAPOR COLLETION) SYSTEMS COMPLYING WITH § 60.482-10 = YES ENCLOSED COMBUSTION DEVICE COMPLYING WITH § 60.482-10 = YES FLARE COMPLYING WITH §60.482-10 = YES VAPOR RECOVERY SYSTEM COMPLYING WITH § 60.482-10 = YES	
F-68-3	40 CFR Part 60, Subpart GGG	60GGG	CONSTRUCTION/MODIFICATION DATE = ON OR BEFORE JANUARY 4, 1983	
F-68-3	40 CFR Part 60, Subpart KKK	60KKK	Facility Type = Affected facility is the group of all equipment except compressors within a process unit. Construction/Modification Date = On or before January 20, 1984.	
F-68-3	40 CFR Part 60, Subpart VV	60VV	Produces Chemicals = The fugitive unit is not part of a facility that produces as an intermediate or final product one or more of the chemicals listed in 40 CFR § 60.489.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
F-68-3	40 CFR Part 63, Subpart CC	63CCVV-ALL	CLOSED VENT (OR VAPOR COLLECTION) SYSTEMS = YES ENCLOSED COMBUSTION DEVICE = YES EXISTING SOURCE = YES FLARE = YES VAPOR RECOVERY SYSTEM = YES CLOSED VENT (OR VAPOR COLLETION) SYSTEMS EQUIVALENT EMISSION LIMITATION = NO COMPLYING WITH TITLE 40 CFR 60 SUBPART VV = YES ENCLOSED COMBUSTION DEVICE EQUIVALENT EMISSION LIMITATION = NO FLARE EQUIVALENT EMISSION LIMITATION = NO VAPOR RECOVERY SYSTEM EQUIVALENT EMISSION LIMITATION = NO CLOSED VENT (OR VAPOR COLLETION) SYSTEMS COMPLYING WITH § 60.482-10 = YES ENCLOSED COMBUSTION DEVICE COMPLYING WITH § 60.482-10 = YES FLARE COMPLYING WITH §60.482-10 = YES VAPOR RECOVERY SYSTEM COMPLYING WITH § 60.482-10 = YES	
F-68-3	40 CFR Part 63, Subpart H	63H	EQUIPMENT TYPE = FUGITIVE UNIT DOES NOT CONTAIN EQUIPMENT LISTED IN 40 CFR § 63.160(A) WHICH IS OPERATED IN ORGANIC HAZARDOUS AIR POLLUTANT SERVICE	
F-68-4TA	40 CFR Part 63, Subpart CC	63CCVV-ALL	CLOSED VENT (OR VAPOR COLLECTION) SYSTEMS = YES ENCLOSED COMBUSTION DEVICE = YES EXISTING SOURCE = YES FLARE = YES VAPOR RECOVERY SYSTEM = YES CLOSED VENT (OR VAPOR COLLETION) SYSTEMS EQUIVALENT EMISSION LIMITATION = NO COMPLYING WITH TITLE 40 CFR 60 SUBPART VV = YES ENCLOSED COMBUSTION DEVICE EQUIVALENT EMISSION LIMITATION = NO FLARE EQUIVALENT EMISSION LIMITATION = NO VAPOR RECOVERY SYSTEM EQUIVALENT EMISSION LIMITATION = NO CLOSED VENT (OR VAPOR COLLETION) SYSTEMS COMPLYING WITH § 60.482-10 = YES ENCLOSED COMBUSTION DEVICE COMPLYING WITH § 60.482-10 = YES FLARE COMPLYING WITH §60.482-10 = YES VAPOR RECOVERY SYSTEM COMPLYING WITH § 60.482-10 = YES	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
F-6-B	40 CFR Part 63, Subpart CC	63CCVV-ALL	<p>CLOSED VENT (OR VAPOR COLLECTION) SYSTEMS = YES</p> <p>ENCLOSED COMBUSTION DEVICE = YES</p> <p>EXISTING SOURCE = YES</p> <p>FLARE = YES</p> <p>VAPOR RECOVERY SYSTEM = YES</p> <p>CLOSED VENT (OR VAPOR COLLETION) SYSTEMS EQUIVALENT EMISSION LIMITATION = NO</p> <p>COMPLYING WITH TITLE 40 CFR 60 SUBPART VV = YES</p> <p>ENCLOSED COMBUSTION DEVICE EQUIVALENT EMISSION LIMITATION = NO</p> <p>FLARE EQUIVALENT EMISSION LIMITATION = NO</p> <p>VAPOR RECOVERY SYSTEM EQUIVALENT EMISSION LIMITATION = NO</p> <p>CLOSED VENT (OR VAPOR COLLETION) SYSTEMS COMPLYING WITH § 60.482-10 = YES</p> <p>ENCLOSED COMBUSTION DEVICE COMPLYING WITH § 60.482-10 = YES</p> <p>FLARE COMPLYING WITH §60.482-10 = YES</p> <p>VAPOR RECOVERY SYSTEM COMPLYING WITH § 60.482-10 = YES</p>	
F-7	40 CFR Part 60, Subpart GGGa	60GGGa-ALL	<p>Construction/Modification Date = Affected facility was constructed, reconstructed or modified after November 7, 2006.</p> <p>Equipment Components = Components are present.</p>	Since rules reference tables have not yet been developed for 40CFR Part 60, Subpart GGGa, the permit reviewer manually developed requirements based on applicant provided attributes.
F-7	40 CFR Part 63, Subpart CC	63CC	EQUIPMENT TYPE = FUGITIVE UNIT CONTAINS EQUIPMENT LISTED IN 40 CFR § 63.160(A) WHICH IS OPERATED IN ORGANIC HAZARDOUS AIR POLLUTANT SERVICE.	Due to 40 CFR Part 63, Subpart CC overlap, equipment leaks that are also subject to the provisions of 40 CFR Part 60, Subpart GGGa, are required to comply only with the provisions specified in 40 CFR Part 60, Subpart GGGa, per §63.640(p)(2).
F-7	40 CFR Part 60, Subpart VV	60VV-1	Produces Chemicals = The fugitive unit is not part of a facility that produces as an intermediate or final product one or more of the chemicals listed in 40 CFR § 60.489.	
F-7	40 CFR Part 61, Subpart V	61V-1	<p>Vacuum Service = The fugitive unit does not contain components in vacuum service.</p> <p>VHAP Service = The fugitive unit contains no components in VHAP service.</p>	
F-7	40 CFR Part 63, Subpart I	63I-1	PROCESS TYPE = NO	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
F-81	40 CFR Part 63, Subpart CC	63CCVV-ALL	CLOSED VENT (OR VAPOR COLLECTION) SYSTEMS = YES ENCLOSED COMBUSTION DEVICE = YES EXISTING SOURCE = YES FLARE = YES VAPOR RECOVERY SYSTEM = YES CLOSED VENT (OR VAPOR COLLETION) SYSTEMS EQUIVALENT EMISSION LIMITATION = NO COMPLYING WITH TITLE 40 CFR 60 SUBPART VV = YES ENCLOSED COMBUSTION DEVICE EQUIVALENT EMISSION LIMITATION = NO FLARE EQUIVALENT EMISSION LIMITATION = NO VAPOR RECOVERY SYSTEM EQUIVALENT EMISSION LIMITATION = NO CLOSED VENT (OR VAPOR COLLETION) SYSTEMS COMPLYING WITH § 60.482-10 = YES ENCLOSED COMBUSTION DEVICE COMPLYING WITH § 60.482-10 = YES FLARE COMPLYING WITH §60.482-10 = YES VAPOR RECOVERY SYSTEM COMPLYING WITH § 60.482-10 = YES	
FGR-FUG	40 CFR Part 60, Subpart GGGa	60GGGa-ALL	Construction/Modification Date = Affected facility was constructed, reconstructed or modified after November 7, 2006. Equipment Components = Components are present.	Since rules reference tables have not yet been developed for 40CFR Part 60, Subpart GGGa, the permit reviewer manually developed requirements based on applicant provided attributes.
FGR-FUG	40 CFR Part 60, Subpart VV	60VV-1	Produces Chemicals = The fugitive unit is not part of a facility that produces as an intermediate or final product one or more of the chemicals listed in 40 CFR § 60.489.	
FGR-FUG	40 CFR Part 61, Subpart V	61V-1	Vacuum Service = The fugitive unit does not contain components in vacuum service. VHAP Service = The fugitive unit contains no components in VHAP service.	
FGR-FUG	40 CFR Part 63, Subpart I	63I-1	PROCESS TYPE = NO	
GRP-CCHFUG	40 CFR Part 63, Subpart CC	63CCH-ALL	ENCLOSED COMBUSTION DEVICES = YES EXISTING SOURCE = YES ANY (CLOSED-VENT SYSTEMS) = YES COMPLYING WITH TITLE 40 CFR 60 SUBPART VV = YES FLARES = YES RECOVERY OR RECAPTURE DEVICES (CLOSED VENT SYSTEMS) = YES CLOSED VENT SYSTEM, BYPASS LINES = YES CLOSED VENT SYSTEM, UNSAFE TO INSPECT = YES CLOSED VENT SYSTEM, DIFFICULT TO INSPECT = YES	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
GRP-CCVVFUG	40 CFR Part 63, Subpart CC	63CCVV-ALL	SOP Index No. = OWNER/OPERATOR ASSUMES VOC/VHAP FUGITIVE CONTROL REQUIREMENTS FOR ALL COMPONENTS SUBJECT TO MACT CC AND COMPLYING WITH NSPS VV REQUIREMENTS WITH NO ALTERNATE CONTROL OR CONTROL DEVICES EXISTING SOURCE = YES COMPLYING WITH TITLE 40 CFR 60 SUBPART VV = YES	
SKIDBLRFUG	40 CFR Part 60, Subpart GGGa	60GGGa-ALL	Construction/Modification Date = Affected facility was constructed, reconstructed or modified after November 7, 2006. Equipment Components = Components are present.	Since rules reference tables have not yet been developed for 40CFR Part 60, Subpart GGGa, the permit reviewer manually developed requirements based on applicant provided attributes.
SKIDBLRFUG	40 CFR Part 63, Subpart CC	63CC	EQUIPMENT TYPE = FUGITIVE UNIT CONTAINS EQUIPMENT LISTED IN 40 CFR § 63.160(A) WHICH IS OPERATED IN ORGANIC HAZARDOUS AIR POLLUTANT SERVICE.	Due to 40 CFR Part 63, Subpart CC overlap, equipment leaks that are also subject to the provisions of 40 CFR Part 60, Subpart GGGa, are required to comply only with the provisions specified in 40 CFR Part 60, Subpart GGGa, per §63.640(p)(2).
SKIDBLRFUG	40 CFR Part 61, Subpart V	61V-1	Vacuum Service = The fugitive unit does not contain components in vacuum service. VHAP Service = The fugitive unit contains no components in VHAP service.	
SKIDBLRFUG	40 CFR Part 63, Subpart I	63I-1	PROCESS TYPE = NO	
1025	40 CFR Part 61, Subpart FF	61FF	Alternate Means of Compliance = NO By-Pass Line = THE CLOSED VENT SYSTEM HAS NO BY-PASS LINE Alternative Standards for Oil-Water Separator = NO Control Device Type/Operation = FLARE Fuel Gas System = EMISSIONS ARE ROUTED TO A CONTROL DEVICE Cover and Closed Vent = CLOSED VENT SYSTEM IS OPERATED SUCH THAT THE OIL-WATER SEPARATOR IS MAINTAINED AT NON-NEGATIVE PRESSURE (GREATER THAN ATMOSPHERIC) Close Vent System and Control Device AMOC = COMPLYING WITH THE REQUIREMENTS OF § 61.349	
25V1	30 TAC Chapter 111, Visible Emissions	R1111-B	Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113. Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit. Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3). Construction Date = After January 31, 1972 Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
25V1	40 CFR Part 63, Subpart CC	63CC	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The miscellaneous process vent is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63, Subparts F, G, H or I = The miscellaneous process vent is subject to 40 CFR Part 63, Subpart CC.</p> <p>Group 1 = The miscellaneous process vent is a Group 2 vent.</p> <p>Engineering Assessment = Engineering assessment is used to determine the total organic compound emission rate for the representative operating condition expected to yield the highest daily emission rate.</p>	
29P1	30 TAC Chapter 111, Visible Emissions	R1111-1	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = A continuous emissions monitoring system (CEMS) capable of measuring the opacity of emissions is installed in the vent in accordance with 30 TAC § 111.111(a)(1)(C).</p> <p>Total Feed Capacity = Total feed capacity is greater than 20,000 barrels per day.</p> <p>Construction Date = After January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is at least 100,000 actual cubic feet per minute.</p>	
40P1	30 TAC Chapter 111, Visible Emissions	R1111-1	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = A continuous emissions monitoring system (CEMS) capable of measuring the opacity of emissions is installed in the vent in accordance with 30 TAC § 111.111(a)(1)(C).</p> <p>Total Feed Capacity = Total feed capacity is greater than 20,000 barrels per day.</p> <p>Construction Date = After January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is at least 100,000 actual cubic feet per minute.</p>	
45V1	40 CFR Part 63, Subpart G	63G	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Thermal incinerator.</p> <p>Overlap = Title 40 CFR Part 63, Subpart G only</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>By-pass Lines = The vent system does not contain by-pass lines that can divert the vent stream from the control device.</p> <p>Performance Test = No previous performance test was conducted.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
45V2	40 CFR Part 63, Subpart G	63G	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Thermal incinerator.</p> <p>Overlap = Title 40 CFR Part 63, Subpart G only</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>By-pass Lines = The vent system does not contain by-pass lines that can divert the vent stream from the control device.</p> <p>Performance Test = No previous performance test was conducted.</p>	
66FLH1	40 CFR Part 63, Subpart CC	63CC-FLARE	<p>98% Reduction = Compliance with the 98% by reduction requirements specified in § 63.116(c)(1)(i) are chosen.</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The miscellaneous process vent is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Divert Vent Stream = The miscellaneous process vent utilizes a vent system that contains no by-pass lines.</p> <p>Subject to 40 CFR Part 63, Subparts F, G, H or I = The miscellaneous process vent is subject to 40 CFR Part 63, Subpart CC.</p> <p>Group 1 = The miscellaneous process vent is a Group 1 vent.</p> <p>Automated Data Compression Recording System = OWNER/OPERATOR DOES NOT USE AN AUTOMATED DATA COMPRESSION SYSTEM THAT RECORDS ALL VALUES THAT MEET SET CRITERIA FOR VARIATION FROM PREVIOUSLY RECORDED VALUES.</p> <p>Continuous Operating Parameter Provisions = The owner or operator does not use an alternative to the continuous operating parameter monitoring and recordkeeping provisions of 40 CFR § 63.654(i).</p> <p>Control Device = Flare</p> <p>Performance Test = A performance test was conducted to determine compliance with a regulation promulgated by EPA and was conducted using the same methods specified in Subpart G and no process changes have been made or results reliably demonstrate compliance.</p> <p>Additional Parameter Monitoring = Parameters specified in 40 CFR § 63.644(a) are being monitored.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
66FLH12	40 CFR Part 63, Subpart CC	63CC-FLARE	<p>98% Reduction = Compliance with the 98% by reduction requirements specified in § 63.116(c)(1)(i) are chosen.</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The miscellaneous process vent is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Divert Vent Stream = The miscellaneous process vent utilizes a vent system that contains no by-pass lines.</p> <p>Subject to 40 CFR Part 63, Subparts F, G, H or I = The miscellaneous process vent is subject to 40 CFR Part 63, Subpart CC.</p> <p>Group 1 = The miscellaneous process vent is a Group 1 vent.</p> <p>Automated Data Compression Recording System = OWNER/OPERATOR DOES NOT USE AN AUTOMATED DATA COMPRESSION SYSTEM THAT RECORDS ALL VALUES THAT MEET SET CRITERIA FOR VARIATION FROM PREVIOUSLY RECORDED VALUES.</p> <p>Continuous Operating Parameter Provisions = The owner or operator does not use an alternative to the continuous operating parameter monitoring and recordkeeping provisions of 40 CFR § 63.654(i).</p> <p>Control Device = Flare</p> <p>Performance Test = A performance test was conducted to determine compliance with a regulation promulgated by EPA and was conducted using the same methods specified in Subpart G and no process changes have been made or results reliably demonstrate compliance.</p> <p>Additional Parameter Monitoring = Parameters specified in 40 CFR § 63.644(a) are being monitored.</p>	
66FLH2	40 CFR Part 63, Subpart CC	63CC-FLARE	<p>98% Reduction = Compliance with the 98% by reduction requirements specified in § 63.116(c)(1)(i) are chosen.</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The miscellaneous process vent is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Divert Vent Stream = The miscellaneous process vent utilizes a vent system that contains no by-pass lines.</p> <p>Subject to 40 CFR Part 63, Subparts F, G, H or I = The miscellaneous process vent is subject to 40 CFR Part 63, Subpart CC.</p> <p>Group 1 = The miscellaneous process vent is a Group 1 vent.</p> <p>Automated Data Compression Recording System = OWNER/OPERATOR DOES NOT USE AN AUTOMATED DATA COMPRESSION SYSTEM THAT RECORDS ALL VALUES THAT MEET SET CRITERIA FOR VARIATION FROM PREVIOUSLY RECORDED VALUES.</p> <p>Continuous Operating Parameter Provisions = The owner or operator does not use an alternative to the continuous operating parameter monitoring and recordkeeping provisions of 40 CFR § 63.654(i).</p> <p>Control Device = Flare</p> <p>Performance Test = A performance test was conducted to determine compliance with a regulation promulgated by EPA and was conducted using the same methods specified in Subpart G and no process changes have been made or results reliably demonstrate compliance.</p> <p>Additional Parameter Monitoring = Parameters specified in 40 CFR § 63.644(a) are being monitored.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
66FLH3	40 CFR Part 63, Subpart CC	63CC-FLARE	<p>98% Reduction = Compliance with the 98% by reduction requirements specified in § 63.116(c)(1)(i) are chosen.</p> <p>Specified in 40 CFR § 63.640(g)(1)-(6) = The miscellaneous process vent is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Divert Vent Stream = The miscellaneous process vent utilizes a vent system that contains no by-pass lines.</p> <p>Subject to 40 CFR Part 63, Subparts F, G, H or I = The miscellaneous process vent is subject to 40 CFR Part 63, Subpart CC.</p> <p>Group 1 = The miscellaneous process vent is a Group 1 vent.</p> <p>Automated Data Compression Recording System = OWNER/OPERATOR DOES NOT USE AN AUTOMATED DATA COMPRESSION SYSTEM THAT RECORDS ALL VALUES THAT MEET SET CRITERIA FOR VARIATION FROM PREVIOUSLY RECORDED VALUES.</p> <p>Continuous Operating Parameter Provisions = The owner or operator does not use an alternative to the continuous operating parameter monitoring and recordkeeping provisions of 40 CFR § 63.654(i).</p> <p>Control Device = Flare</p> <p>Performance Test = A performance test was conducted to determine compliance with a regulation promulgated by EPA and was conducted using the same methods specified in Subpart G and no process changes have been made or results reliably demonstrate compliance.</p> <p>Additional Parameter Monitoring = Parameters specified in 40 CFR § 63.644(a) are being monitored.</p>	
85B2	30 TAC Chapter 111, Visible Emissions	111-FVent	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = A continuous emissions monitoring system (CEMS) capable of measuring the opacity of emissions is installed in the vent in accordance with 30 TAC § 111.111(a)(1)(C).</p> <p>Total Feed Capacity = Total feed capacity is greater than 20,000 barrels per day.</p> <p>Construction Date = After January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is at least 100,000 actual cubic feet per minute.</p>	
98H1	30 TAC Chapter 111, Visible Emissions	R1111-1	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = After January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is at least 100,000 actual cubic feet per minute.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
GRP-V100	30 TAC Chapter 111, Visible Emissions	111-LVent	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = After January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is at least 100,000 actual cubic feet per minute.</p>	
MEROX	40 CFR Part 63, Subpart CC	63CC-FLARE	<p>98% Reduction = Compliance with the 98% by reduction requirements specified in § 63.116(c)(1)(i) are chosen. Specified in 40 CFR § 63.640(g)(1)-(6) = The miscellaneous process vent is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Divert Vent Stream = The miscellaneous process vent utilizes a vent system that contains no by-pass lines.</p> <p>Subject to 40 CFR Part 63, Subparts F, G, H or I = The miscellaneous process vent is subject to 40 CFR Part 63, Subpart CC.</p> <p>Group 1 = The miscellaneous process vent is a Group 1 vent.</p> <p>Automated Data Compression Recording System = OWNER/OPERATOR DOES NOT USE AN AUTOMATED DATA COMPRESSION SYSTEM THAT RECORDS ALL VALUES THAT MEET SET CRITERIA FOR VARIATION FROM PREVIOUSLY RECORDED VALUES.</p> <p>Continuous Operating Parameter Provisions = The owner or operator does not use an alternative to the continuous operating parameter monitoring and recordkeeping provisions of 40 CFR § 63.654(i).</p> <p>Control Device = Flare</p> <p>Performance Test = A performance test was conducted to determine compliance with a regulation promulgated by EPA and was conducted using the same methods specified in Subpart G and no process changes have been made or results reliably demonstrate compliance.</p> <p>Additional Parameter Monitoring = Parameters specified in 40 CFR § 63.644(a) are being monitored.</p>	
VGo8	40 CFR Part 63, Subpart CC	63CC	<p>Specified in 40 CFR § 63.640(g)(1)-(6) = The miscellaneous process vent is not part of a process specified in 40 CFR § 63.640(g)(1) - (6).</p> <p>Subject to 40 CFR Part 63, Subparts F, G, H or I = The miscellaneous process vent is subject to 40 CFR Part 63, Subpart CC.</p> <p>Group 1 = The miscellaneous process vent is a Group 2 vent.</p> <p>Engineering Assessment = Engineering assessment is used to determine the total organic compound emission rate for the representative operating condition expected to yield the highest daily emission rate.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
29P1	40 CFR Part 60, Subpart J	60J-FLUID	<p>Facility Type = FCCU catalyst regenerator located at a petroleum refinery.</p> <p>Construction/Modification Date = After January 17, 1984 and on or before May 14, 2007.</p> <p>Contact Material = The FCCU catalyst regenerator does not have contact material that reacts with petroleum derivatives to improve feedstock quality in which the contact material is regenerated by burning off coke and/or other deposits.</p> <p>Sulfur Content = Measuring the total sulfur content in the FCCU fresh feed.</p> <p>Discharged Gases = Gases discharged by the FCCU catalyst regenerator do not pass through an incinerator or waste heat boiler in which auxiliary or supplemental liquid or solid fossil fuel is burned.</p> <p>CO Monitoring = It has not been demonstrated to the Administrator that the average CO emissions are less than 50 ppm (dry basis).</p>	
29P1	40 CFR Part 63, Subpart UUU	63UUU-1	<p>CCU CO Emission Limitation = CCU subject to the NSPS for CO in 40 CFR § 60.103 or electing to comply with the NSPS requirements (Option 1).</p> <p>CCU PM/Opacity Emission Limitation = CCU subject to the NSPS for PM in 40 CFR §60.102 - PM emissions not to exceed 1.0 kg/1,000 kg of coke burn-off in the catalyst regenerator and opacity of emissions not to exceed 30%, except for one 6-minute avg. opacity reading in any 1-hour period.</p> <p>CCU PM Control Device = Electrostatic Precipitator serving CCU over 20,000 barrels/day fresh feed capacity.</p> <p>CCU CO Monitoring Method = Continuous Emissions Monitoring System for measuring CO concentration.</p> <p>CCU PM Monitoring Method = Continuous Opacity Monitoring System.</p> <p>CCU Bypass Line = No bypass line serving the catalytic cracking unit.</p> <p>Alternate Method for Measuring Gas Flow Rate = Using an alternate method for measuring gas flow rate as listed in §63.1573(a)(1).</p>	
34I1	40 CFR Part 60, Subpart J	60J-SRU	<p>Facility Type = Claus sulfur recovery plant with a design capacity for sulfur feed greater than 20 LTPD with reduction control systems followed by incineration.</p> <p>Construction/Modification Date = After October 4, 1976 and on or before May 14, 2007.</p>	
34I1	40 CFR Part 63, Subpart UUU	63UUU-2	<p>SRU Emission Limitation = Claus SRU part of sulfur recovery plant greater than or equal to 20 long tons/day using oxidation or reduction system followed by incineration subject to 250 ppmv SO₂ emission limit in §60.104(a)(2).</p> <p>SRU Bypass Line = No bypass line serving the SRU.</p>	
40P1	40 CFR Part 60, Subpart J	60J-FLUID	<p>Facility Type = FCCU catalyst regenerator located at a petroleum refinery.</p> <p>Construction/Modification Date = After January 17, 1984 and on or before May 14, 2007.</p> <p>Contact Material = The FCCU catalyst regenerator does not have contact material that reacts with petroleum derivatives to improve feedstock quality in which the contact material is regenerated by burning off coke and/or other deposits.</p> <p>Sulfur Content = Measuring the total sulfur content in the FCCU fresh feed.</p> <p>Discharged Gases = Gases discharged by the FCCU catalyst regenerator do not pass through an incinerator or waste heat boiler in which auxiliary or supplemental liquid or solid fossil fuel is burned.</p> <p>CO Monitoring = It has not been demonstrated to the Administrator that the average CO emissions are less than 50 ppm (dry basis).</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
40P1	40 CFR Part 63, Subpart UUU	63UUU-1	<p>CCU CO Emission Limitation = CCU subject to the NSPS for CO in 40 CFR § 60.103 or electing to comply with the NSPS requirements (Option 1).</p> <p>CCU PM/Opacity Emission Limitation = CCU subject to the NSPS for PM in 40 CFR §60.102 - PM emissions not to exceed 1.0 kg/1,000 kg of coke burn-off in the catalyst regenerator and opacity of emissions not to exceed 30%, except for one 6-minute avg. opacity reading in any 1-hour period.</p> <p>CCU PM Control Device = Electrostatic Precipitator serving CCU over 20,000 barrels/day fresh feed capacity.</p> <p>CCU CO Monitoring Method = Continuous Emissions Monitoring System for measuring CO concentration.</p> <p>CCU PM Monitoring Method = Continuous Opacity Monitoring System.</p> <p>CCU Bypass Line = No bypass line serving the catalytic cracking unit.</p> <p>Alternate Method for Measuring Gas Flow Rate = Using an alternate method for measuring gas flow rate as listed in §63.1573(a)(1).</p>	
43I1	40 CFR Part 60, Subpart J	60J-SRU	<p>Facility Type = Claus sulfur recovery plant with a design capacity for sulfur feed greater than 20 LTPD with reduction control systems followed by incineration.</p> <p>Construction/Modification Date = After October 4, 1976 and on or before May 14, 2007.</p>	
43I1	40 CFR Part 63, Subpart UUU	63UUU-2	<p>SRU Emission Limitation = Claus SRU part of sulfur recovery plant greater than or equal to 20 long tons/day using oxidation or reduction system followed by incineration subject to 250 ppmv SO₂ emission limit in §60.104(a)(2).</p> <p>SRU Bypass Line = No bypass line serving the SRU.</p>	
66FL1	40 CFR Part 60, Subpart J	60J-FUEL	<p>Facility Type = Flare that is used for fuel gas combustion located at a petroleum refinery, that does NOT meet requirements in §§ 60.105(a)(4)(iv) or 60.105(b).</p> <p>Construction/Modification Date = After June 11, 1973 and on or before June 24, 2008.</p> <p>Monitoring Device = No instrument is in place for continuously monitoring and recording the concentration by volume of SO₂ emissions into the atmosphere.</p>	
66FL12	40 CFR Part 60, Subpart J	60J-FUEL	<p>Facility Type = Flare that is used for fuel gas combustion located at a petroleum refinery, that does NOT meet requirements in §§ 60.105(a)(4)(iv) or 60.105(b).</p> <p>Construction/Modification Date = After June 11, 1973 and on or before June 24, 2008.</p> <p>Monitoring Device = No instrument is in place for continuously monitoring and recording the concentration by volume of SO₂ emissions into the atmosphere.</p>	
66FL13	40 CFR Part 60, Subpart J	60J-FUEL	<p>Facility Type = Flare that is used for fuel gas combustion located at a petroleum refinery, that does NOT meet requirements in §§ 60.105(a)(4)(iv) or 60.105(b).</p> <p>Construction/Modification Date = After June 11, 1973 and on or before June 24, 2008.</p> <p>Monitoring Device = No instrument is in place for continuously monitoring and recording the concentration by volume of SO₂ emissions into the atmosphere.</p>	
66FL2	40 CFR Part 60, Subpart J	60J-FUEL	<p>Facility Type = Flare that is used for fuel gas combustion located at a petroleum refinery, that does NOT meet requirements in §§ 60.105(a)(4)(iv) or 60.105(b).</p> <p>Construction/Modification Date = After June 11, 1973 and on or before June 24, 2008.</p> <p>Monitoring Device = No instrument is in place for continuously monitoring and recording the concentration by volume of SO₂ emissions into the atmosphere.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
66FL3	40 CFR Part 60, Subpart J	60J-FUEL	<p>Facility Type = Flare that is used for fuel gas combustion located at a petroleum refinery, that does NOT meet requirements in §§ 60.105(a)(4)(iv) or 60.105(b).</p> <p>Construction/Modification Date = After June 11, 1973 and on or before June 24, 2008.</p> <p>Monitoring Device = No instrument is in place for continuously monitoring and recording the concentration by volume of SO₂ emissions into the atmosphere.</p>	
BLR12	40 CFR Part 60, Subpart Ja	60Ja-FUEL	<p>Facility Type = Fuel gas combustion device, other than a flare or process heater, that does NOT meet requirements in § 60.107a(a)(3)(i)-(iv).</p> <p>Construction/Modification Date = After June 24, 2008</p> <p>Sulfur Emission Limit = Owner or operator is choosing SO₂ limit in terms of ppmv H₂S in fuel gas.</p>	
GRP-RFUEL	40 CFR Part 60, Subpart J	60J-FUEL	<p>Facility Type = Fuel gas combustion device, other than a flare, that does not meet requirements in §§ 60.105(a)(4)(iv) or 60.105(b).</p> <p>Construction/Modification Date = After June 11, 1973 and on or before May 14, 2007.</p> <p>Monitoring Device = No instrument is in place for continuously monitoring and recording the concentration by volume of SO₂ emissions into the atmosphere.</p>	
SKIDBLR	40 CFR Part 60, Subpart Ja	60Ja-FUEL	<p>Facility Type = Fuel gas combustion device, other than a flare or process heater, that meets requirements in § 60.107a(a)(3)(i)-(iv) [inherently low in sulfur content].</p> <p>Construction/Modification Date = After June 24, 2008</p> <p>Sulfur Emission Limit = Owner or operator is choosing SO₂ limit in terms of ppmv H₂S in fuel gas.</p>	

* - The "unit attributes" or operating conditions that determine what requirements apply

** - Notes changes made to the automated results from the DSS, and a brief explanation why

NSR Versus Title V FOP

The state of Texas has two Air permitting programs, New Source Review (NSR) and Title V Federal Operating Permits. The two programs are substantially different both in intent and permit content.

NSR is a preconstruction permitting program authorized by the Texas Clean Air Act and Title I of the Federal Clean Air Act (FCAA). The processing of these permits is governed by 30 Texas Administrative Code (TAC) Chapter 116.111. The Title V Federal Operating Program is a federal program authorized under Title V of the FCAA that has been delegated to the state of Texas to administer and is governed by 30 TAC Chapter 122. The major differences between the two permitting programs are listed in the table below:

NSR Permit	Federal Operating Permit(FOP)
Issued Prior to new Construction or modification of an existing facility	For initial permit with application shield, can be issued after operation commences; significant revisions require approval prior to operation.
Authorizes air emissions	Codifies existing applicable requirements, does not authorize new emissions
Ensures issued permits are protective of the environment and human health by conducting a health effects review and that requirement for best available control technology (BACT) is implemented.	Applicable requirements listed in permit are used by the inspectors to ensure proper operation of the site as authorized. Ensures that adequate monitoring is in place to allow compliance determination with the FOP.
Up to two Public notices may be required. Opportunity for public comment and contested case hearings for some authorizations.	One public notice required. Opportunity for public comments. No contested case hearings.
Applies to all point source emissions in the state.	Applies to all major sources and some non-major sources identified by the EPA.
Applies to facilities: a portion of site or individual emission sources	One or multiple FOPs cover the entire site (consists of multiple facilities)
Permits include terms and conditions under which the applicant must construct and operate its various equipment and processes on a facility basis.	Permits include terms and conditions that specify the general operational requirements of the site; and also include codification of all applicable requirements for emission units at the site.
Opportunity for EPA review for Federal Prevention of Significant Deterioration (PSD) and Nonattainment (NA) permits for major sources.	Opportunity for EPA review, Affected states review, and a Public petition period for every FOP.
Permits have a table listing maximum emission limits for pollutants	Permit has an applicable requirements table and Periodic Monitoring (PM) / Compliance Assurance Monitoring (CAM) tables which document applicable monitoring requirements.
Permits can be altered or amended upon application by company. Permits must be issued before construction or modification of facilities can begin.	Permits can be revised through several revision processes, which provide for different levels of public notice and opportunity to comment. Changes that would be significant revisions require that a revised permit be issued before those changes can be operated.
NSR permits are issued independent of FOP requirements.	FOP are independent of NSR permits, but contain a list of all NSR permits incorporated by reference

New Source Review Requirements

Below is a list of the New Source Review (NSR) permits for the permitted area. These NSR permits are incorporated by reference into the operating permit and are enforceable under it. These permits can be found in the main TCEQ file room, located on the first floor of Building E, 12100 Park 35 Circle, Austin, Texas. The

Public Education Program may be contacted at 1-800-687-4040 or the Air Permits Division (APD) may be contacted at 1-512-239-1250 for help with any question.

Additionally, the site contains emission units that are permitted by rule under the requirements of 30 TAC Chapter 106, Permits by Rule. The following table specifies the permits by rule that apply to the site. All current permits by rule are contained in Chapter 106. Outdated 30 TAC Chapter 106 permits by rule may be viewed at the following Web site:

www.tceq.texas.gov/permitting/air/permitbyrule/historical_rules/old106list/index106.html

Outdated Standard Exemption lists may be viewed at the following Web site:

www.tceq.texas.gov/permitting/air/permitbyrule/historical_rules/oldselist/se_index.html

The status of air permits and applications and a link to the Air Permits Remote Document Server is located at the following Web site:

www.tceq.texas.gov/permitting/air/nav/air_status_permits.html

Prevention of Significant Deterioration (PSD) Permits	
PSD Permit No.: GHGPSDTX130	Issuance Date: 09/04/2015
PSD Permit No.: PSDTX102M7	Issuance Date: 09/24/2014
PSD Permit No.: PSDTX1158M1	Issuance Date: 09/04/2015
Title 30 TAC Chapter 116 Permits, Special Permits, and Other Authorizations (Other Than Permits By Rule, PSD Permits, or NA Permits) for the Application Area.	
Authorization No.: 100477	Issuance Date: 01/12/2012
Authorization No.: 104928	Issuance Date: 09/24/2014
Authorization No.: 14441A	Issuance Date: 05/30/2012
Authorization No.: 43073	Issuance Date: 11/17/2009
Authorization No.: 80799	Issuance Date: 10/09/2014
Authorization No.: 85872	Issuance Date: 09/04/2015
Authorization No.: 87458	Issuance Date: 03/02/2009
Authorization No.: 90208	Issuance Date: 08/05/2010
Authorization No.: 9868A	Issuance Date: 09/24/2014
Permits By Rule (30 TAC Chapter 106) for the Application Area	
Number: 106.261	Version No./Date: 11/01/2003
Number: 106.262	Version No./Date: 11/01/2003
Number: 106.263	Version No./Date: 11/01/2001
Number: 106.371	Version No./Date: 09/04/2000
Number: 106.472	Version No./Date: 09/04/2000
Number: 106.511	Version No./Date: 09/04/2000

Number: 106.512	Version No./Date: 06/13/2001
Number: 106.532	Version No./Date: 09/04/2000
Number: 106.533	Version No./Date: 07/04/2004

Emission Units and Emission Points

In air permitting terminology, any source capable of generating emissions (for example, an engine or a sandblasting area) is called an Emission Unit. For purposes of Title V, emission units are specifically listed in the operating permit when they have applicable requirements other than New Source Review (NSR), or when they are listed in the permit shield table.

The actual physical location where the emissions enter the atmosphere (for example, an engine stack or a sandblasting yard) is called an emission point. For New Source Review preconstruction permitting purposes, every emission unit has an associated emission point. Emission limits are listed in an NSR permit, associated with an emission point. This list of emission points and emission limits per pollutant is commonly referred to as the “Maximum Allowable Emission Rate Table”, or “MAERT” for short. Specifically, the MAERT lists the Emission Point Number (EPN) that identifies the emission point, followed immediately by the Source Name, identifying the emission unit that is the source of those emissions on this table.

Thus, by reference, an emission unit in a Title V operating permit is linked by reference number to an NSR authorization, and its related emission point.

Monitoring Sufficiency

Federal and state rules, 40 CFR § 70.6(a)(3)(i)(B) and 30 TAC § 122.142(c) respectively, require that each federal operating permit include additional monitoring for applicable requirements that lack periodic or instrumental monitoring (which may include recordkeeping that serves as monitoring) that yields reliable data from a relevant time period that are representative of the emission unit’s compliance with the applicable emission limitation or standard. Furthermore, the federal operating permit must include compliance assurance monitoring (CAM) requirements for emission sources that meet the applicability criteria of 40 CFR Part 64 in accordance with 40 CFR § 70.6(a)(3)(i)(A) and 30 TAC § 122.604(b).

With the exception of any emission units listed in the Periodic Monitoring or CAM Summaries in the FOP, the TCEQ Executive Director has determined that the permit contains sufficient monitoring, testing, recordkeeping, and reporting requirements that assure compliance with the applicable requirements. If applicable, each emission unit that requires additional monitoring in the form of periodic monitoring or CAM is described in further detail under the Rationale for CAM/PM Methods Selected section following this paragraph.

Rationale for Compliance Assurance Monitoring (CAM)/ Periodic Monitoring Methods Selected

Compliance Assurance Monitoring (CAM):

Compliance Assurance Monitoring (CAM) is a federal monitoring program established under Title 40 Code of Federal Regulations Part 64 (40 CFR Part 64).

Emission units are subject to CAM requirements if they meet the following criteria:

1. the emission unit is subject to an emission limitation or standard for an air pollutant (or surrogate thereof) in an applicable requirement;
2. the emission unit uses a control device to achieve compliance with the emission limitation or standard specified in the applicable requirement; and

3. the emission unit has the pre-control device potential to emit greater than or equal to the amount in tons per year for a site to be classified as a major source.

The following table(s) identify the emission unit(s) that are subject to CAM:

Unit/Group/Process Information	
ID No.: 29P1	
Control Device ID No.: N/A	Control Device Type: Wet or Dry Electrostatic Precipitator
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart J	SOP Index No.: 60J-FLUID
Pollutant: PM	Main Standard: § 60.102(a)(1)
Monitoring Information	
Indicator: Opacity	
Minimum Frequency: 6 times/minute	
Averaging Period: Six minutes	
Deviation Limit: >30% opacity	
Basis of CAM: The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.	

Unit/Group/Process Information	
ID No.: 29P1	
Control Device ID No.: N/A	Control Device Type: Wet or Dry Electrostatic Precipitator
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart J	SOP Index No.: 60J-FLUID
Pollutant: PM (OPACITY)	Main Standard: § 60.102(a)(2)
Monitoring Information	
Indicator: Opacity	
Minimum Frequency: 6 times/minute	
Averaging Period: Six minutes	
Deviation Limit: >30% opacity	
<p>Basis of CAM: The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p>	

Unit/Group/Process Information	
ID No.: 34I1	
Control Device ID No.: 34I1	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart J	SOP Index No.: 60J-SRU
Pollutant: SO ₂	Main Standard: § 60.104(a)(2)(i)
Monitoring Information	
Indicator: SO ₂ concentration	
Minimum Frequency: 4 times/hour	
Averaging Period: 12 hours	
Deviation Limit: >250 ppmv SO ₂ at 0% excess air	
Basis of CAM: It is widely practiced and accepted to calibrate and use a portable analyzer or CEMS to measure SO ₂ concentration with procedures such as EPA Test Method 6C. The measured concentration along with stack flow rate or AP-42 factors and fuel consumption records may be used to demonstrate compliance with an underlying emission limit or standard.	

Unit/Group/Process Information	
ID No.: 40P1	
Control Device ID No.: N/A	Control Device Type: Wet or Dry Electrostatic Precipitator
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart J	SOP Index No.: 60J-FLUID
Pollutant: PM	Main Standard: § 60.102(a)(1)
Monitoring Information	
Indicator: Opacity	
Minimum Frequency: 6 times/minute	
Averaging Period: Six minutes	
Deviation Limit: >30% opacity	
<p>Basis of CAM: The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p>	

Unit/Group/Process Information	
ID No.: 40P1	
Control Device ID No.: N/A	Control Device Type: Wet or Dry Electrostatic Precipitator
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart J	SOP Index No.: 60J-FLUID
Pollutant: PM (OPACITY)	Main Standard: § 60.102(a)(2)
Monitoring Information	
Indicator: Opacity	
Minimum Frequency: 6 times/minute	
Averaging Period: Six minutes	
Deviation Limit: >30% opacity	
<p>Basis of CAM: The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p>	

Unit/Group/Process Information	
ID No.: 43I1	
Control Device ID No.: 43I1	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart J	SOP Index No.: 60J-SRU
Pollutant: SO ₂	Main Standard: § 60.104(a)(2)(i)
Monitoring Information	
Indicator: SO ₂ concentration	
Minimum Frequency: 4 times/hour	
Averaging Period: 12 hours	
Deviation Limit: >250 ppmv SO ₂ at 0% excess air	
Basis of CAM: It is widely practiced and accepted to calibrate and use a portable analyzer or CEMS to measure SO ₂ concentration with procedures such as EPA Test Method 6C. The measured concentration along with stack flow rate or AP-42 factors and fuel consumption records may be used to demonstrate compliance with an underlying emission limit or standard.	

Periodic Monitoring:

The Federal Clean Air Act requires that each federal operating permit include monitoring sufficient to assure compliance with the terms and conditions of the permit. Most of the emission limits and standards applicable to emission units at Title V sources include adequate monitoring to show that the units meet the limits and standards. For those requirements that do not include monitoring, or where the monitoring is not sufficient to assure compliance, the federal operating permit must include such monitoring for the emission units affected. The following emission units are subject to periodic monitoring requirements because the emission units are subject to an emission limitation or standard for an air pollutant (or surrogate thereof) in an applicable requirement that does not already require monitoring, or the monitoring for the applicable requirement is not sufficient to assure compliance:

Unit/Group/Process Information	
ID No.: 25V1	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-B
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(B)
Monitoring Information	
Indicator: Visible emissions	
Minimum Frequency: Once per quarter	
Averaging Period: n/a	
Deviation Limit: Maximum opacity = 20%	
<p>Basis of monitoring: The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p>	

Unit/Group/Process Information	
ID No.: 98H1	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-1
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(C)
Monitoring Information	
Indicator: Visible Emissions	
Minimum Frequency: Once per week	
Averaging Period: n/a	
Deviation Limit: Maximum opacity = 15%	
<p>Basis of monitoring: The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p>	

Unit/Group/Process Information	
ID No.: GRP-V100	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: 111-LVent
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(C)
Monitoring Information	
Indicator: Visible Emissions	
Minimum Frequency: Once per week	
Averaging Period: n/a	
Deviation Limit: The presence of any visible emissions shall be considered a deviation unless a Method 9 observation is performed. If a Method 9 observation is performed, then the deviation limit shall be 15% opacity.	
<p>Basis of monitoring:</p> <p>The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p>	

Compliance Review

- 1. In accordance with 30 TAC Chapter 60, the compliance history was reviewed on 07/02/2015.
- 2. The compliance history review evaluated the period from 09/01/2009 to 07/02/2015.
 Site rating: 30.30 (satisfactory) Company rating: 12.76 (satisfactory)
(High < 0.10; Satisfactory > 0.10 and < 55; Unsatisfactory > 55)
- 3. Has the permit changed on the basis of the compliance history or site/company rating?No

Permit reviewer notes: n/a

Site/Permit Area Compliance Status Review

- 1. Were there any out-of-compliance units listed on Form OP-ACPS?No
- 2. Is a compliance plan and schedule included in the permit?.....No

Permit reviewer notes: n/a

Available Unit Attribute Forms

- OP-UA1 - Miscellaneous and Generic Unit Attributes
- OP-UA2 - Stationary Reciprocating Internal Combustion Engine Attributes
- OP-UA3 - Storage Tank/Vessel Attributes
- OP-UA4 - Loading/Unloading Operations Attributes
- OP-UA5 - Process Heater/Furnace Attributes
- OP-UA6 - Boiler/Steam Generator/Steam Generating Unit Attributes
- OP-UA7 - Flare Attributes
- OP-UA8 - Coal Preparation Plant Attributes
- OP-UA9 - Nonmetallic Mineral Process Plant Attributes
- OP-UA10 - Gas Sweetening/Sulfur Recovery Unit Attributes
- OP-UA11 - Stationary Turbine Attributes
- OP-UA12 - Fugitive Emission Unit Attributes
- OP-UA13 - Industrial Process Cooling Tower Attributes
- OP-UA14 - Water Separator Attributes
- OP-UA15 - Emission Point/Stationary Vent/Distillation Operation/Process Vent Attributes
- OP-UA16 - Solvent Degreasing Machine Attributes
- OP-UA17 - Distillation Unit Attributes
- OP-UA18 - Surface Coating Operations Attributes
- OP-UA19 - Wastewater Unit Attributes
- OP-UA20 - Asphalt Operations Attributes
- OP-UA21 - Grain Elevator Attributes
- OP-UA22 - Printing Attributes
- OP-UA24 - Wool Fiberglass Insulation Manufacturing Plant Attributes
- OP-UA25 - Synthetic Fiber Production Attributes
- OP-UA26 - Electroplating and Anodizing Unit Attributes
- OP-UA27 - Nitric Acid Manufacturing Attributes
- OP-UA28 - Polymer Manufacturing Attributes
- OP-UA29 - Glass Manufacturing Unit Attributes
- OP-UA30 - Kraft, Soda, Sulfite, and Stand-Alone Semicheical Pulp Mill Attributes
- OP-UA31 - Lead Smelting Attributes
- OP-UA32 - Copper and Zinc Smelting/Brass and Bronze Production Attributes
- OP-UA33 - Metallic Mineral Processing Plant Attributes
- OP-UA34 - Pharmaceutical Manufacturing
- OP-UA35 - Incinerator Attributes
- OP-UA36 - Steel Plant Unit Attributes
- OP-UA37 - Basic Oxygen Process Furnace Unit Attributes
- OP-UA38 - Lead-Acid Battery Manufacturing Plant Attributes

OP-UA39 - Sterilization Source Attributes
OP-UA40 - Ferroalloy Production Facility Attributes
OP-UA41 - Dry Cleaning Facility Attributes
OP-UA42 - Phosphate Fertilizer Manufacturing Attributes
OP-UA43 - Sulfuric Acid Production Attributes
OP-UA44 - Municipal Solid Waste Landfill/Waste Disposal Site Attributes
OP-UA45 - Surface Impoundment Attributes
OP-UA46 - Epoxy Resins and Non-Nylon Polyamides Production Attributes
OP-UA47 - Ship Building and Ship Repair Unit Attributes
OP-UA48 - Air Oxidation Unit Process Attributes
OP-UA49 - Vacuum-Producing System Attributes
OP-UA50 - Fluid Catalytic Cracking Unit Catalyst Regenerator/Fuel Gas Combustion Device/Claus Sulfur Recovery Plant Attributes
OP-UA51 - Dryer/Kiln/Oven Attributes
OP-UA52 - Closed Vent Systems and Control Devices
OP-UA53 - Beryllium Processing Attributes
OP-UA54 - Mercury Chlor-Alkali Cell Attributes
OP-UA55 - Transfer System Attributes
OP-UA56 - Vinyl Chloride Process Attributes
OP-UA57 - Cleaning/Depainting Operation Attributes
OP-UA58 - Treatment Process Attributes
OP-UA59 - Coke By-Product Recovery Plant Attributes
OP-UA60 - Chemical Manufacturing Process Unit Attributes
OP-UA61 - Pulp, Paper, or Paperboard Producing Process Attributes
OP-UA62 - Glycol Dehydration Unit Attributes
OP-UA63 - Vegetable Oil Production Attributes