

# Statement of Basis of the Federal Operating Permit

TPC Group LLC

Site Name: Port Neches Operations  
Area Name: PNO-C4 Plant  
Physical Location: 2102 Spur 136  
Nearest City: Port Neches  
County: Jefferson

Permit Number: O1327  
Project Type: Renewal

Standard Industrial Classification (SIC) Code: 2869  
SIC Name: Industrial Organic Chemicals

This Statement of Basis sets forth the legal and factual basis for the draft permit conditions in accordance with 30 TAC §122.201(a)(4). Per 30 TAC §§ 122.241 and 243, the permit holder has submitted an application under § 122.134 for permit renewal. This document may include the following information:

- A description of the facility/area process description;
- A basis for applying permit shields;
- A list of the federal regulatory applicability determinations;
- A table listing the determination of applicable requirements;
- A list of the New Source Review Requirements;
- The rationale for periodic monitoring methods selected;
- The rationale for compliance assurance methods selected;
- A compliance status; and
- A list of available unit attribute forms.

Prepared on: July 12, 2016

# Operating Permit Basis of Determination

## Permit Area Process Description

The C4 plant consists of a Butadiene Unit, with Storage and Production purification facilities, a MTBE Unit where MTBE is produced by reacting raw materials over a catalyst, a Vent Recovery System, Wastewater System, Reactor Regenerators, Bundle Furnaces, and Support Equipment.

Raw butadiene is received from barges, transport vessels, and pipeline. It is stored and then purified by washing and distillation. This material is later reacted and distilled to produce MTBE. All vents from processes and storage facilities are routed to one of three flares: North flare, South flare, or the Dock flare. Wastewater is sent to a joint wastewater treatment plant.

## FOPs at Site

The “application area” consists of the emission units and that portion of the site included in the application and this permit. Multiple FOPs may be issued to a site in accordance with 30 TAC § 122.201(e). When there is only one area for the site, then the application information and permit will include all units at the site. Additional FOPs that exist at the site, if any, are listed below.

Additional FOPs: None

## Major Source Pollutants

The table below specifies the pollutants for which the site is a major source:

Major Pollutants	VOC, NOX, HAPS, CO
------------------	--------------------

## Reading State of Texas’s Federal Operating Permit

The Title V Federal Operating Permit (FOP) lists all state and federal air emission regulations and New Source Review (NSR) authorizations (collectively known as “applicable requirements”) that apply at a particular site or permit area (in the event a site has multiple FOPs). **The FOP does not authorize new emissions or new construction activities.** The FOP begins with an introductory page which is common to all Title V permits. This page gives the details of the company, states the authority of the issuing agency, requires the company to operate in accordance with this permit and 30 Texas Administrative Code (TAC) Chapter 122, requires adherence with NSR requirements of 30 TAC Chapter 116, and finally indicates the permit number and the issuance date.

This is followed by the table of contents, which is generally composed of the following elements. Not all permits will have all of the elements.

- General Terms and Conditions
- Special Terms and Conditions
  - Emissions Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting
  - Additional Monitoring Requirements
  - New Source Review Authorization Requirements
  - Compliance Requirements
  - Protection of Stratosphere Ozone
  - Permit Location
  - Permit Shield (30 TAC § 122.148)
- Attachments
  - Applicable Requirements Summary
    - Unit Summary
    - Applicable Requirements Summary

- Additional Monitoring Requirements
- Permit Shield
- New Source Review Authorization References
- Compliance Plan
- Alternative Requirements
- Appendix A
  - Acronym list

## General Terms and Conditions

The General Terms and Conditions are the same and appear in all permits. The first paragraph lists the specific citations for 30 TAC Chapter 122 requirements that apply to all Title V permit holders. The second paragraph describes the requirements for record retention. The third paragraph provides details for voiding the permit, if applicable. The fourth paragraph states that the permit holder shall comply with the requirements of 30 TAC Chapter 116 by obtaining a New Source Review authorization prior to new construction or modification of emission units located in the area covered by this permit. The fifth paragraph provides details on submission of reports required by the permit.

## Special Terms and Conditions

**Emissions Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting:** The TCEQ has designated certain applicable requirements as site-wide requirements. A site-wide requirement is a requirement that applies uniformly to all the units or activities at the site. Units with only site-wide requirements are addressed on Form OP-REQ1 and are not required to be listed separately on a OP-UA Form or Form OP-SUM. Form OP-SUM must list all units addressed in the application and provide identifying information, applicable OP-UA Forms, and preconstruction authorizations. The various OP-UA Forms provide the characteristics of each unit from which applicable requirements are established. Some exceptions exist as a few units may have both site-wide requirements and unit specific requirements.

**Other conditions:** The other entries under special terms and conditions are in general terms referring to compliance with the more detailed data listed in the attachments.

## Attachments

**Applicable Requirements Summary:** The first attachment, the Applicable Requirements Summary, has two tables, addressing unit specific requirements. The first table, the Unit Summary, includes a list of units with applicable requirements, the unit type, the applicable regulation, and the requirement driver. The intent of the requirement driver is to inform the reader that a given unit may have several different operating scenarios and the differences between those operating scenarios.

The applicable requirements summary table provides the detailed citations of the rules that apply to the various units. For each unit and operating scenario, there is an added modifier called the “index number,” detailed citations specifying monitoring and testing requirements, recordkeeping requirements, and reporting requirements. The data for this table are based on data supplied by the applicant on the OP-SUM and various OP-UA forms.

**Additional Monitoring Requirement:** The next attachment includes additional monitoring the applicant must perform to ensure compliance with the applicable standard. Compliance assurance monitoring (CAM) is often required to provide a reasonable assurance of compliance with applicable emission limitations/standards for large emission units that use control devices to achieve compliance with applicant requirements. When necessary, periodic monitoring (PM) requirements are specified for certain parameters (i.e. feed rates, flow rates, temperature, fuel type and consumption, etc.) to determine if a term and condition or emission unit is operating within specified limits to control emissions. These additional monitoring approaches may be required for two reasons. First, the applicable rules do not adequately specify monitoring requirements (exception- Maximum Achievable Control Technology Standards (MACTs) generally have sufficient monitoring), and second, monitoring may be required to fill gaps in the monitoring requirements of certain

applicable requirements. In situations where the NSR permit is the applicable requirement requiring extra monitoring for a specific emission unit, the preferred solution is to have the monitoring requirements in the NSR permit updated so that all NSR requirements are consolidated in the NSR permit.

Permit Shield. A permit may or may not have a permit shield, depending on whether an applicant has applied for, and justified the granting of, a permit shield. A permit shield is a special condition included in the permit document stating that compliance with the conditions of the permit shall be deemed compliance with the specified potentially applicable requirement(s) or specified applicable state-only requirement(s).

New Source Review Authorization References: All activities which are related to emissions in the state of Texas must have a NSR authorization prior to beginning construction. This section lists all units in the permit and the NSR authorization that allowed the unit to be constructed or modified. Units that do not have unit specific applicable requirements other than the NSR authorization do not need to be listed in this attachment. While NSR permits are not physically a part of the Title V permit, they are legally incorporated into the Title V permit by reference. Those NSR permits whose emissions exceed certain PSD/NA thresholds must also undergo a Federal review of federally regulated pollutants in addition to review for state regulated pollutants.

Compliance Plan: A permit may have a compliance schedule attachment for listing corrective actions plans for any emission unit that is out of compliance with an applicable requirement.

Alternative Requirements: This attachment will list any alternative monitoring plans or alternative means of compliance for applicable requirements that have been approved by the EPA Administrator and/or the TCEQ Executive Director.

Appendix A

Acronym list: This attachment lists the common acronyms used when discussing the FOPs.

### **Stationary vents subject to 30 TAC Chapter 111, Subchapter A, § 111.111(a)(1)(B) addressed in the Special Terms and Conditions**

The site contains stationary vents with a flowrate less than 100,000 actual cubic feet per minute (acfm) and constructed after January 31, 1972 which are limited, over a six-minute average, to 20% opacity as required by 30 TAC § 111.111(a)(1)(B). As a site may have a large number of stationary vents that fall into this category, they are not required to be listed individually in the permit's Applicable Requirement Summary. This is consistent with EPA's White Paper for Streamlined Development of Part 70 Permit Applications, July 10, 1995, that states that requirements that apply identically to emission units at a site can be treated on a generic basis such as source-wide opacity limits.

Periodic monitoring is specified in Special Term and Condition 3 for stationary vents subject to 30 TAC § 111.111(a)(1)(B) to verify compliance with the 20% opacity limit. These vents are not expected to produce visible emissions during normal operation. The TCEQ evaluated the probability of these sources violating the opacity standards and determined that there is a very low potential that an opacity standard would be exceeded. It was determined that continuous monitoring for these sources is not warranted as there would be very limited environmental benefit in continuously monitoring sources that have a low potential to produce visible emissions. Therefore, the TCEQ set the visible observation monitoring frequency for these sources to once per calendar quarter.

The TCEQ has exempted vents that are not capable of producing visible emissions from periodic monitoring requirements. These vents include sources of colorless VOCs, non-fuming liquids, and other materials that cannot produce emissions that obstruct the transmission of light. Passive ventilation vents, such as plumbing vents, are also included in this category. Since this category of vents are not capable of producing opacity due to the physical or chemical characteristics of the emission source, periodic monitoring is not required as it would not yield any additional data to assure compliance with the 20% opacity standard of 30 TAC § 111.111(a)(1)(B).

In the event that visible emissions are detected, either through the quarterly observation or other credible evidence, such as observations from company personnel, the permit holder shall either report a deviation or perform a Test Method 9 observation to determine the opacity consistent with the 6-minute averaging time specified in 30 TAC § 111.111(a)(1)(B). An additional provision is included to monitor combustion sources more frequently than quarterly if alternate fuels are burned for periods greater than 24 consecutive hours. This will address possible emissions that may arise when switching fuel types.

**Stationary Vents subject to 30 TAC Chapter 111 not addressed in the Special Terms and Conditions**

All other stationary vents subject to 30 TAC Chapter 111 not covered in the Special Terms and Conditions are listed in the permit’s Applicable Requirement Summary. The basis for the applicability determinations for these vents are listed in the Determination of Applicable Requirements table.

**Federal Regulatory Applicability Determinations**

The following chart summarizes the applicability of the principal air pollution regulatory programs to the permit area:

Regulatory Program	Applicability (Yes/No)
Prevention of Significant Deterioration (PSD)	No
Nonattainment New Source Review (NNSR)	No
Minor NSR	Yes
40 CFR Part 60 - New Source Performance Standards	Yes
40 CFR Part 61 - National Emission Standards for Hazardous Air Pollutants (NESHAPs)	Yes
40 CFR Part 63 - NESHAPs for Source Categories	Yes
Title IV (Acid Rain) of the Clean Air Act (CAA)	No
Title V (Federal Operating Permits) of the CAA	Yes
Title VI (Stratospheric Ozone Protection) of the CAA	Yes
CAIR (Clean Air Interstate Rule)	No

**Basis for Applying Permit Shields**

An operating permit applicant has the opportunity to specifically request a permit shield to document that specific applicable requirements do not apply to emission units in the permit. A permit shield is a special condition stating that compliance with the conditions of the permit shall be deemed compliance with the specified potentially applicable requirements or specified potentially applicable state-only requirements. A permit shield has been requested in the application for specific emission units. For the permit shield requests that have been approved, the basis of determination for regulations that the owner/operator need not comply with are located in the “Permit Shield” attachment of the permit.

**Insignificant Activities**

In general, units not meeting the criteria for inclusion on either Form OP-SUM or Form OP-REQ1 are not required to be addressed in the operating permit application. Examples of these types of units include, but are not limited to, the following:

1. Office activities such as photocopying, blueprint copying, and photographic processes.
2. Sanitary sewage collection and treatment facilities other than those used to incinerate wastewater treatment plant sludge. Stacks or vents for sanitary sewer plumbing traps are also included.
3. Food preparation facilities including, but not limited to, restaurants and cafeterias used for preparing food or beverages primarily for consumption on the premises.
4. Outdoor barbecue pits, campfires, and fireplaces.
5. Laundry dryers, extractors, and tumblers processing bedding, clothing, or other fabric items generated primarily at the premises. This does not include emissions from dry cleaning systems using perchloroethylene or petroleum solvents.
6. Facilities storing only dry, sweet natural gas, including natural gas pressure regulator vents.
7. Any air separation or other industrial gas production, storage, or packaging facility. Industrial gases, for purposes of this list, include only oxygen, nitrogen, helium, neon, argon, krypton, and xenon.
8. Storage and handling of sealed portable containers, cylinders, or sealed drums.
9. Vehicle exhaust from maintenance or repair shops.
10. Storage and use of non-VOC products or equipment for maintaining motor vehicles operated at the site (including but not limited to, antifreeze and fuel additives).
11. Air contaminant detectors and recorders, combustion controllers and shut-off devices, product analyzers, laboratory analyzers, continuous emissions monitors, other analyzers and monitors, and emissions associated with sampling activities. Exception to this category includes sampling activities that are deemed fugitive emissions and under a regulatory leak detection and repair program.
12. Bench scale laboratory equipment and laboratory equipment used exclusively for chemical and physical analysis, including but not limited to, assorted vacuum producing devices and laboratory fume hoods.
13. Steam vents, steam leaks, and steam safety relief valves, provided the steam (or boiler feedwater) has not contacted other materials or fluids containing regulated air pollutants other than boiler water treatment chemicals.
14. Storage of water that has not contacted other materials or fluids containing regulated air pollutants other than boiler water treatment chemicals.
15. Well cellars.
16. Fire or emergency response equipment and training, including but not limited to, use of fire control equipment including equipment testing and training, and open burning of materials or fuels associated with firefighting training.
17. Crucible or pot furnaces with a brim full capacity of less than 450 cubic inches of any molten metal.
18. Equipment used exclusively for the melting or application of wax.
19. All closed tumblers used for the cleaning or deburring of metal products without abrasive blasting, and all open tumblers with a batch capacity of 1,000 lbs. or less.
20. Shell core and shell mold manufacturing machines.
21. Sand or investment molds with a capacity of 100 lbs. or less used for the casting of metals;
22. Equipment used for inspection of metal products.
23. Equipment used exclusively for rolling, forging, pressing, drawing, spinning, or extruding either hot or cold metals by some mechanical means.
24. Instrument systems utilizing air, natural gas, nitrogen, oxygen, carbon dioxide, helium, neon, argon, krypton, and xenon.
25. Battery recharging areas.
26. Brazing, soldering, or welding equipment.

### **Determination of Applicable Requirements**

The tables below include the applicability determinations for the emission units, the index number(s) where applicable, and all relevant unit attribute information used to form the basis of the applicability determination. The unit attribute information is a description of the physical properties of an emission unit which is used to determine the requirements to which the permit holder must comply. For more information about the descriptions of the unit attributes specific Unit Attribute Forms may be viewed at [www.tceq.texas.gov/permitting/air/nav/air\\_all\\_ua\\_forms.html](http://www.tceq.texas.gov/permitting/air/nav/air_all_ua_forms.html).

A list of unit attribute forms is included at the end of this document. Some examples of unit attributes include construction date; product stored in a tank; boiler fuel type; etc.. Generally, multiple attributes are needed to determine the requirements for a given emission unit and index number. The table below lists these attributes in the column entitled "Basis of Determination." Attributes that demonstrate that an applicable requirement applies will be the factual basis for the specific citations in an applicable requirement that apply to a unit for that index number. The TCEQ Air Permits Division has developed flowcharts for determining applicability of state and federal regulations based on the unit attribute information in a Decision Support System (DSS). These flowcharts can be accessed via the internet at [www.tceq.texas.gov/permitting/air/nav/air\\_supportsys.html](http://www.tceq.texas.gov/permitting/air/nav/air_supportsys.html). The Air Permits Division staff may also be contacted for assistance at (512) 239-1250.

The attributes for each unit and corresponding index number provide the basis for determining the specific legal citations in an applicable requirement that apply, including emission limitations or standards, monitoring, recordkeeping, and reporting. The rules were found to apply or not apply by using the unit attributes as answers to decision questions found in the flowcharts of the DSS. Some additional attributes indicate which legal citations of a rule apply. The legal citations that apply to each emission unit may be found in the Applicable Requirements Summary table of the draft permit. There may be some entries or rows of units and rules not found in the permit, or if the permit contains a permit shield, repeated in the permit shield area. These are sets of attributes that describe negative applicability, or; in other words, the reason why a potentially applicable requirement does not apply.

If applicability determinations have been made which differ from the available flowcharts, an explanation of the decisions involved in the applicability determination is specified in the column "Changes and Exceptions to RRT." If there were no exceptions to the DSS, then this column has been removed.

The draft permit includes all emission limitations or standards, monitoring, recordkeeping and reporting required by each applicable requirement. If an applicable requirement does not require monitoring, recordkeeping, or reporting, the word "None" will appear in the Applicable Requirements Summary table. If additional periodic monitoring is required for an applicable requirement, it will be explained in detail in the portion of this document entitled "Rationale for Compliance Assurance Monitoring (CAM)/ Periodic Monitoring Methods Selected."

When attributes demonstrate that a unit is not subject to an applicable requirement, the applicant may request a permit shield for those items. The portion of this document entitled "Basis for Applying Permit Shields" specifies which units, if any, have a permit shield.

#### Operational Flexibility

When an emission unit has multiple operating scenarios, it will have a different index number associated with each operating condition. This means that units are permitted to operate under multiple operating conditions. The applicable requirements for each operating condition are determined by a unique set of unit attributes. For example, a tank may store two different products at different points in time. The tank may, therefore, need to comply with two distinct sets of requirements, depending on the product that is stored. Both sets of requirements are included in the permit, so that the permit holder may store either product in the tank.

## Determination of Applicable Requirements

Unit ID	Regulation	Index Number	Basis of Determination*
6G228	30 TAC Chapter 117, Subchapter B	R7-103	<p>Horsepower Rating = HP is greater than or equal to 300</p> <p>RACT Date Placed in Service = On or before November 15, 1992</p> <p>Type of Service = Used exclusively in emergency situations [claiming the emergency service exemption under 30 TAC §§ 117.103(a)(6)(D), 117.203(a)(6)(D), 117.303(a)(6)(D) or 117.403(a)(7)(D)]</p> <p>Fuel Fired = Petroleum-based diesel fuel</p>
6G228	40 CFR Part 60, Subpart III	60III-1	<p>Applicability Date = Stationary CI ICE commenced construction, reconstruction, or modification on or before July 11, 2005.</p>
6G228	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-1	<p>HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2.</p> <p>Brake HP = Stationary RICE with a brake HP greater than or equal to 300 HP and less than or equal to 500 HP.</p> <p>Construction/Reconstruction Date = Commenced construction or reconstruction before December 19, 2002.</p> <p>Displacement = The stationary CI RICE has a displacement of 30 liters or more per cylinder and uses diesel fuel or has a displacement less than 30 liters per cylinder and does not use diesel fuel.</p> <p>Service Type = Emergency use where the RICE does not operate or is not contractually obligated to be available for more than 15 hours per calendar year as specified in 40 CFR §63.6640(f)(2)(ii)-(iii) or does not operate as specified in 40 CFR §63.6640(f)(4)(ii).</p> <p>Stationary RICE Type = Compression ignition engine</p>
6G233	30 TAC Chapter 117, Subchapter B	R7-103	<p>Horsepower Rating = HP is greater than or equal to 300</p> <p>RACT Date Placed in Service = On or before November 15, 1992</p> <p>Type of Service = Stationary diesel engine</p> <p>Fuel Fired = Petroleum-based diesel fuel</p>
6G233	40 CFR Part 60, Subpart III	60III-1	<p>Applicability Date = Stationary CI ICE commenced construction, reconstruction, or modification on or before July 11, 2005.</p>
6G233	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-1	<p>HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2.</p> <p>Brake HP = Stationary RICE with a brake HP greater than or equal to 300 HP and less than or equal to 500 HP.</p> <p>Construction/Reconstruction Date = Commenced construction or reconstruction before December 19, 2002.</p> <p>Displacement = The stationary CI RICE has a displacement of 30 liters or more per cylinder and uses diesel fuel or has a displacement less than 30 liters per cylinder and does not use diesel fuel.</p> <p>Service Type = Emergency use where the RICE does not operate or is not contractually obligated to be available for more than 15 hours per calendar year as specified in 40 CFR §63.6640(f)(2)(ii)-(iii) or does not operate as specified in 40 CFR §63.6640(f)(4)(ii).</p> <p>Stationary RICE Type = Compression ignition engine</p>
6G245	30 TAC Chapter 117, Subchapter B	R7-103	<p>Horsepower Rating = HP is greater than or equal to 300</p> <p>RACT Date Placed in Service = On or before November 15, 1992</p> <p>Type of Service = Stationary diesel engine</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			Fuel Fired = Petroleum-based diesel fuel
6G245	40 CFR Part 60, Subpart IIII	60IIII-1	Applicability Date = Stationary CI ICE commenced construction, reconstruction, or modification on or before July 11, 2005.
6G245	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-1	HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2. Brake HP = Stationary RICE with a brake HP greater than or equal to 300 HP and less than or equal to 500 HP. Construction/Reconstruction Date = Commenced construction or reconstruction before December 19, 2002. Displacement = The stationary CI RICE has a displacement of 30 liters or more per cylinder and uses diesel fuel or has a displacement less than 30 liters per cylinder and does not use diesel fuel. Service Type = Emergency use where the RICE does not operate or is not contractually obligated to be available for more than 15 hours per calendar year as specified in 40 CFR §63.6640(f)(2)(ii)-(iii) or does not operate as specified in 40 CFR §63.6640(f)(4)(ii). Stationary RICE Type = Compression ignition engine
6G260	30 TAC Chapter 117, Subchapter B	R7-103	Horsepower Rating = HP is less than 300 Type of Service = Stationary diesel engine Fuel Fired = Petroleum-based diesel fuel
6G260	40 CFR Part 60, Subpart IIII	60IIII-1	Applicability Date = Stationary CI ICE commenced construction, reconstruction, or modification on or before July 11, 2005.
6G260	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-2	HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2. Brake HP = Stationary RICE with a brake HP greater than or equal to 100 HP and less than 250 HP. Construction/Reconstruction Date = Commenced construction or reconstruction before December 19, 2002. Displacement = The stationary CI RICE has a displacement of 30 liters or more per cylinder and uses diesel fuel or has a displacement less than 30 liters per cylinder and does not use diesel fuel. Service Type = Emergency use where the RICE does not operate or is not contractually obligated to be available for more than 15 hours per calendar year as specified in 40 CFR §63.6640(f)(2)(ii)-(iii) or does not operate as specified in 40 CFR §63.6640(f)(4)(ii). Stationary RICE Type = Compression ignition engine
6G82	30 TAC Chapter 117, Subchapter B	R7-103	Horsepower Rating = HP is greater than or equal to 300 RACT Date Placed in Service = On or before November 15, 1992 Type of Service = Used exclusively in emergency situations [claiming the emergency service exemption under 30 TAC §§ 117.103(a)(6)(D), 117.203(a)(6)(D), 117.303(a)(6)(D) or 117.403(a)(7)(D)] Fuel Fired = Petroleum-based diesel fuel
6G82	40 CFR Part 60, Subpart IIII	60IIII-1	Applicability Date = Stationary CI ICE commenced construction, reconstruction, or modification on or before July 11, 2005.
6G82	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-1	HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2. Brake HP = Stationary RICE with a brake HP greater than or equal to 300 HP and less than or equal to 500 HP.

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>Construction/Reconstruction Date = Commenced construction or reconstruction before December 19, 2002.</p> <p>Displacement = The stationary CI RICE has a displacement of 30 liters or more per cylinder and uses diesel fuel or has a displacement less than 30 liters per cylinder and does not use diesel fuel.</p> <p>Service Type = Emergency use where the RICE does not operate or is not contractually obligated to be available for more than 15 hours per calendar year as specified in 40 CFR §63.6640(f)(2)(ii)-(iii) or does not operate as specified in 40 CFR §63.6640(f)(4)(ii).</p> <p>Stationary RICE Type = Compression ignition engine</p>
NBPG271	30 TAC Chapter 117, Subchapter B	R7-103	<p>Horsepower Rating = HP is less than 300</p> <p>Type of Service = Stationary diesel engine</p> <p>Fuel Fired = Petroleum-based diesel fuel</p>
NBPG271	40 CFR Part 60, Subpart IIII	60IIII-1	<p>Applicability Date = Stationary CI ICE commenced construction, reconstruction, or modification on or before July 11, 2005.</p>
NBPG271	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-2	<p>HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2.</p> <p>Brake HP = Stationary RICE with a brake HP greater than or equal to 100 HP and less than 250 HP.</p> <p>Construction/Reconstruction Date = Commenced construction or reconstruction before December 19, 2002.</p> <p>Displacement = The stationary CI RICE has a displacement of 30 liters or more per cylinder and uses diesel fuel or has a displacement less than 30 liters per cylinder and does not use diesel fuel.</p> <p>Service Type = Emergency use where the RICE does not operate or is not contractually obligated to be available for more than 15 hours per calendar year as specified in 40 CFR §63.6640(f)(2)(ii)-(iii) or does not operate as specified in 40 CFR §63.6640(f)(4)(ii).</p> <p>Stationary RICE Type = Compression ignition engine</p>
NBPG289	30 TAC Chapter 117, Subchapter B	R7-103	<p>Horsepower Rating = HP is less than 300</p> <p>Type of Service = Stationary diesel engine</p> <p>Fuel Fired = Petroleum-based diesel fuel</p>
NBPG289	40 CFR Part 60, Subpart IIII	60IIII-1	<p>Applicability Date = Stationary CI ICE commenced construction, reconstruction, or modification on or before July 11, 2005.</p>
NBPG289	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-2	<p>HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2.</p> <p>Brake HP = Stationary RICE with a brake HP greater than or equal to 100 HP and less than 250 HP.</p> <p>Construction/Reconstruction Date = Commenced construction or reconstruction before December 19, 2002.</p> <p>Displacement = The stationary CI RICE has a displacement of 30 liters or more per cylinder and uses diesel fuel or has a displacement less than 30 liters per cylinder and does not use diesel fuel.</p> <p>Service Type = Emergency use where the RICE does not operate or is not contractually obligated to be available for more than 15 hours per calendar year as specified in 40 CFR §63.6640(f)(2)(ii)-(iii) or does not operate as specified in 40 CFR §63.6640(f)(4)(ii).</p> <p>Stationary RICE Type = Compression ignition engine</p>
NBPG304	30 TAC Chapter 117, Subchapter	R7-103	<p>Horsepower Rating = HP is less than 300</p>

Unit ID	Regulation	Index Number	Basis of Determination*
	B		Type of Service = Stationary diesel engine Fuel Fired = Petroleum-based diesel fuel
NBPG304	40 CFR Part 60, Subpart IIII	60IIII-1	Applicability Date = Stationary CI ICE commenced construction, reconstruction, or modification on or before July 11, 2005.
NBPG304	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-2	HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2. Brake HP = Stationary RICE with a brake HP less than 100 HP. Construction/Reconstruction Date = Commenced construction or reconstruction before December 19, 2002. Service Type = Emergency use where the RICE does not operate or is not contractually obligated to be available for more than 15 hours per calendar year as specified in 40 CFR §63.6640(f)(2)(ii)-(iii) or does not operate as specified in 40 CFR §63.6640(f)(4)(ii). Stationary RICE Type = Compression ignition engine
27-TK-209	30 TAC Chapter 115, Storage of VOCs	R5112-056	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a vapor recovery system (VRS) True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons Control Device Type = Other vapor destruction unit
27-TK-209	40 CFR Part 63, Subpart G	63GT-024	MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G). Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y. Hard Piping = The closed vent system is constructed of hard piping. Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa) Emission Control Type = Emissions routed to a fuel gas system
27-TK-210	30 TAC Chapter 115, Storage of VOCs	R5112-056	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a vapor recovery system (VRS) True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons Control Device Type = Other vapor destruction unit
27-TK-210	40 CFR Part 63, Subpart G	63GT-024	MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Emissions routed to a fuel gas system</p>
27-TK-211	30 TAC Chapter 115, Storage of VOCs	R5112-056	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Other vapor destruction unit</p>
27-TK-211	40 CFR Part 63, Subpart G	63GT-024	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Emissions routed to a fuel gas system</p>
27-TK-212	30 TAC Chapter 115, Storage of VOCs	R5112-056	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Other vapor destruction unit</p>
27-TK-212	40 CFR Part 63, Subpart G	63GT-024	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa) Emission Control Type = Emissions routed to a fuel gas system
27-TK-213	30 TAC Chapter 115, Storage of VOCs	R5112-056	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a vapor recovery system (VRS) True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons Control Device Type = Other vapor destruction unit
27-TK-213	40 CFR Part 63, Subpart G	63GT-024	MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G). Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y. Hard Piping = The closed vent system is constructed of hard piping. Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa) Emission Control Type = Emissions routed to a fuel gas system
27-TK-216	30 TAC Chapter 115, Storage of VOCs	R5112-056	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a vapor recovery system (VRS) True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons Control Device Type = Other vapor destruction unit
27-TK-216	40 CFR Part 63, Subpart G	63GT-024	MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G). Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y. Hard Piping = The closed vent system is constructed of hard piping. Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa) Emission Control Type = Emissions routed to a fuel gas system
6-TK-1	30 TAC Chapter 115, Storage of VOCs	R5112-063	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a submerged fill pipe and vapor recovery system

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Other vapor destruction unit</p>
6-TK-1	40 CFR Part 63, Subpart G	63GT-040	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Emissions routed to a fuel gas system</p>
6-TK-10	30 TAC Chapter 115, Storage of VOCs	R5112-063	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Other vapor destruction unit</p>
6-TK-10	40 CFR Part 63, Subpart G	63GT-040	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Emissions routed to a fuel gas system</p>
6-TK-100	30 TAC Chapter 115, Storage of VOCs	R5112-063	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			Control Device Type = Other vapor destruction unit
6-TK-100	40 CFR Part 63, Subpart G	63GT-040	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Emissions routed to a fuel gas system</p>
6-TK-101	30 TAC Chapter 115, Storage of VOCs	R5112-063	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Other vapor destruction unit</p>
6-TK-101	40 CFR Part 63, Subpart G	63GT-040	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Emissions routed to a fuel gas system</p>
6-TK-103	30 TAC Chapter 115, Storage of VOCs	R5112-063	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Other vapor destruction unit</p>
6-TK-103	40 CFR Part 63, Subpart G	63GT-040	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Emissions routed to a fuel gas system</p>
6-TK-104	30 TAC Chapter 115, Storage of VOCs	R5112-063	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Other vapor destruction unit</p>
6-TK-104	40 CFR Part 63, Subpart G	63GT-040	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Emissions routed to a fuel gas system</p>
6-TK-109	30 TAC Chapter 115, Storage of VOCs	R5112-063	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Other vapor destruction unit</p>
6-TK-109	40 CFR Part 63, Subpart G	63GT-040	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Emissions routed to a fuel gas system</p>
6-TK-11	30 TAC Chapter 115, Storage of VOCs	R5112-063	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Other vapor destruction unit</p>
6-TK-11	40 CFR Part 63, Subpart G	63GT-040	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Emissions routed to a fuel gas system</p>
6-TK-12	30 TAC Chapter 115, Storage of VOCs	R5112-063	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Other vapor destruction unit</p>
6-TK-12	40 CFR Part 63, Subpart G	63GT-040	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Emissions routed to a fuel gas system</p>

Unit ID	Regulation	Index Number	Basis of Determination*
6-TK-13	30 TAC Chapter 115, Storage of VOCs	R5112-063	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Other vapor destruction unit</p>
6-TK-13	40 CFR Part 63, Subpart G	63GT-040	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Emissions routed to a fuel gas system</p>
6-TK-14	30 TAC Chapter 115, Storage of VOCs	R5112-063	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Other vapor destruction unit</p>
6-TK-14	40 CFR Part 63, Subpart G	63GT-040	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Emissions routed to a fuel gas system</p>
6-TK-15	30 TAC Chapter 115, Storage of VOCs	R5112-063	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Other vapor destruction unit</p>
6-TK-15	40 CFR Part 63, Subpart G	63GT-040	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Emissions routed to a fuel gas system</p>
6-TK-16	30 TAC Chapter 115, Storage of VOCs	R5112-063	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Other vapor destruction unit</p>
6-TK-16	40 CFR Part 63, Subpart G	63GT-040	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Emissions routed to a fuel gas system</p>
6-TK-17	30 TAC Chapter 115, Storage of VOCs	R5112-063	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			Control Device Type = Other vapor destruction unit
6-TK-17	40 CFR Part 63, Subpart G	63GT-040	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Emissions routed to a fuel gas system</p>
6-TK-18	30 TAC Chapter 115, Storage of VOCs	R5112-063	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Other vapor destruction unit</p>
6-TK-18	40 CFR Part 63, Subpart G	63GT-040	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Emissions routed to a fuel gas system</p>
6-TK-19	30 TAC Chapter 115, Storage of VOCs	R5112-063	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Other vapor destruction unit</p>
6-TK-19	40 CFR Part 63, Subpart G	63GT-040	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Emissions routed to a fuel gas system</p>
6-TK-2	30 TAC Chapter 115, Storage of VOCs	R5112-063	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Other vapor destruction unit</p>
6-TK-2	40 CFR Part 63, Subpart G	63GT-040	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Emissions routed to a fuel gas system</p>
6-TK-20	30 TAC Chapter 115, Storage of VOCs	R5112-063	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Other vapor destruction unit</p>
6-TK-20	40 CFR Part 63, Subpart G	63GT-040	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Emissions routed to a fuel gas system</p>
6-TK-21	30 TAC Chapter 115, Storage of VOCs	R5112-063	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Other vapor destruction unit</p>
6-TK-21	40 CFR Part 63, Subpart G	63GT-040	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Emissions routed to a fuel gas system</p>
6-TK-22	30 TAC Chapter 115, Storage of VOCs	R5112-063	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Other vapor destruction unit</p>
6-TK-22	40 CFR Part 63, Subpart G	63GT-040	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Emissions routed to a fuel gas system</p>

Unit ID	Regulation	Index Number	Basis of Determination*
6-TK-23	30 TAC Chapter 115, Storage of VOCs	R5112-063	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Other vapor destruction unit</p>
6-TK-23	40 CFR Part 63, Subpart G	63GT-040	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Emissions routed to a fuel gas system</p>
6-TK-24	30 TAC Chapter 115, Storage of VOCs	R5112-063	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Other vapor destruction unit</p>
6-TK-24	40 CFR Part 63, Subpart G	63GT-040	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Emissions routed to a fuel gas system</p>
6-TK-25	30 TAC Chapter 115, Storage of VOCs	R5112-063	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Other vapor destruction unit</p>
6-TK-25	40 CFR Part 63, Subpart G	63GT-040	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Emissions routed to a fuel gas system</p>
6-TK-26	30 TAC Chapter 115, Storage of VOCs	R5112-063	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Other vapor destruction unit</p>
6-TK-26	40 CFR Part 63, Subpart G	63GT-040	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Emissions routed to a fuel gas system</p>
6-TK-27	30 TAC Chapter 115, Storage of VOCs	R5112-063	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			Control Device Type = Other vapor destruction unit
6-TK-27	40 CFR Part 63, Subpart G	63GT-040	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Emissions routed to a fuel gas system</p>
6-TK-28	30 TAC Chapter 115, Storage of VOCs	R5112-063	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Other vapor destruction unit</p>
6-TK-28	40 CFR Part 63, Subpart G	63GT-040	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Emissions routed to a fuel gas system</p>
6-TK-29	30 TAC Chapter 115, Storage of VOCs	R5112-063	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Other vapor destruction unit</p>
6-TK-29	40 CFR Part 63, Subpart G	63GT-040	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Emissions routed to a fuel gas system</p>
6-TK-3	30 TAC Chapter 115, Storage of VOCs	R5112-063	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Other vapor destruction unit</p>
6-TK-3	40 CFR Part 63, Subpart G	63GT-040	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Emissions routed to a fuel gas system</p>
6-TK-30	30 TAC Chapter 115, Storage of VOCs	R5112-063	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Other vapor destruction unit</p>
6-TK-30	40 CFR Part 63, Subpart G	63GT-040	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Emissions routed to a fuel gas system</p>
6-TK-31	30 TAC Chapter 115, Storage of VOCs	R5112-063	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Other vapor destruction unit</p>
6-TK-31	40 CFR Part 63, Subpart G	63GT-040	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Emissions routed to a fuel gas system</p>
6-TK-32	30 TAC Chapter 115, Storage of VOCs	R5112-063	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Other vapor destruction unit</p>
6-TK-32	40 CFR Part 63, Subpart G	63GT-040	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Emissions routed to a fuel gas system</p>

Unit ID	Regulation	Index Number	Basis of Determination*
6-TK-33	30 TAC Chapter 115, Storage of VOCs	R5112-063	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Other vapor destruction unit</p>
6-TK-33	40 CFR Part 63, Subpart G	63GT-040	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Emissions routed to a fuel gas system</p>
6-TK-34	30 TAC Chapter 115, Storage of VOCs	R5112-063	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Other vapor destruction unit</p>
6-TK-34	40 CFR Part 63, Subpart G	63GT-040	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Emissions routed to a fuel gas system</p>
6-TK-35	30 TAC Chapter 115, Storage of VOCs	R5112-063	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Other vapor destruction unit</p>
6-TK-35	40 CFR Part 63, Subpart G	63GT-040	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Emissions routed to a fuel gas system</p>
6-TK-36	30 TAC Chapter 115, Storage of VOCs	R5112-063	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Other vapor destruction unit</p>
6-TK-36	40 CFR Part 63, Subpart G	63GT-040	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Emissions routed to a fuel gas system</p>
6-TK-37	30 TAC Chapter 115, Storage of VOCs	R5112-063	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			Control Device Type = Other vapor destruction unit
6-TK-38	30 TAC Chapter 115, Storage of VOCs	R5112-063	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a submerged fill pipe and vapor recovery system True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons Control Device Type = Other vapor destruction unit
6-TK-39	30 TAC Chapter 115, Storage of VOCs	R5112-063	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a submerged fill pipe and vapor recovery system True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons Control Device Type = Other vapor destruction unit
6-TK-39	40 CFR Part 63, Subpart G	63GT-040	MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G). Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y. Hard Piping = The closed vent system is constructed of hard piping. Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa) Emission Control Type = Emissions routed to a fuel gas system
6-TK-4	30 TAC Chapter 115, Storage of VOCs	R5112-063	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a submerged fill pipe and vapor recovery system True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons Control Device Type = Other vapor destruction unit
6-TK-4	40 CFR Part 63, Subpart G	63GT-040	MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G). Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Emissions routed to a fuel gas system</p>
6-TK-40	30 TAC Chapter 115, Storage of VOCs	R5112-063	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Other vapor destruction unit</p>
6-TK-40	40 CFR Part 63, Subpart G	63GT-040	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Emissions routed to a fuel gas system</p>
6-TK-41	30 TAC Chapter 115, Storage of VOCs	R5112-063	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Other vapor destruction unit</p>
6-TK-41	40 CFR Part 63, Subpart G	63GT-040	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa) Emission Control Type = Emissions routed to a fuel gas system
6-TK-42	30 TAC Chapter 115, Storage of VOCs	R5112-063	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a submerged fill pipe and vapor recovery system True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons Control Device Type = Other vapor destruction unit
6-TK-42	40 CFR Part 63, Subpart G	63GT-040	MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G). Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y. Hard Piping = The closed vent system is constructed of hard piping. Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa) Emission Control Type = Emissions routed to a fuel gas system
6-TK-48	30 TAC Chapter 115, Storage of VOCs	R5112-1.5-	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons
6-TK-5	30 TAC Chapter 115, Storage of VOCs	R5112-063	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a submerged fill pipe and vapor recovery system True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons Control Device Type = Other vapor destruction unit
6-TK-5	40 CFR Part 63, Subpart G	63GT-040	MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G). Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Emissions routed to a fuel gas system</p>
6-TK-50	30 TAC Chapter 115, Storage of VOCs	R5112-1.5-	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>
6-TK-55	30 TAC Chapter 115, Storage of VOCs	R5112-056	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>
6-TK-55	40 CFR Part 63, Subpart G	63GT-024	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Seal Type = Metallic shoe seal (as defined in 40 CFR § 63.111)</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Internal floating roof</p>
6-TK-56	30 TAC Chapter 115, Storage of VOCs	R5112-056	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof (IFR)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>
6-TK-56	40 CFR Part 63, Subpart G	63GT-024	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Seal Type = Metallic shoe seal (as defined in 40 CFR § 63.111)</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			Emission Control Type = Internal floating roof
6-TK-6	30 TAC Chapter 115, Storage of VOCs	R5112-063	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a submerged fill pipe and vapor recovery system True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons Control Device Type = Other vapor destruction unit
6-TK-6	40 CFR Part 63, Subpart G	63GT-040	MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G). Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y. Hard Piping = The closed vent system is constructed of hard piping. Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa) Emission Control Type = Emissions routed to a fuel gas system
6-TK-84	30 TAC Chapter 115, Storage of VOCs	R5112-063	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a submerged fill pipe and vapor recovery system True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons Control Device Type = Other vapor destruction unit
6-TK-84	40 CFR Part 63, Subpart G	63GT-040	MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G). Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y. Hard Piping = The closed vent system is constructed of hard piping. Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa) Emission Control Type = Emissions routed to a fuel gas system
6-TK-85	30 TAC Chapter 115, Storage of VOCs	R5112-063	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Other vapor destruction unit</p>
6-TK-85	40 CFR Part 63, Subpart G	63GT-040	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Emissions routed to a fuel gas system</p>
6-TK-86	30 TAC Chapter 115, Storage of VOCs	R5112-063	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Other vapor destruction unit</p>
6-TK-86	40 CFR Part 63, Subpart G	63GT-040	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Emissions routed to a fuel gas system</p>
6-TK-87	30 TAC Chapter 115, Storage of VOCs	R5112-063	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons Control Device Type = Other vapor destruction unit
6-TK-87	40 CFR Part 63, Subpart G	63GT-040	MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G). Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y. Hard Piping = The closed vent system is constructed of hard piping. Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa) Emission Control Type = Emissions routed to a fuel gas system
6-TK-88	30 TAC Chapter 115, Storage of VOCs	R5112-063	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a submerged fill pipe and vapor recovery system True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons Control Device Type = Other vapor destruction unit
6-TK-88	40 CFR Part 63, Subpart G	63GT-040	MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G). Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y. Hard Piping = The closed vent system is constructed of hard piping. Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa) Emission Control Type = Emissions routed to a fuel gas system
6-TK-89	30 TAC Chapter 115, Storage of VOCs	R5112-063	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a submerged fill pipe and vapor recovery system True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons Control Device Type = Other vapor destruction unit

Unit ID	Regulation	Index Number	Basis of Determination*
6-TK-89	40 CFR Part 63, Subpart G	63GT-040	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Emissions routed to a fuel gas system</p>
6-TK-9	30 TAC Chapter 115, Storage of VOCs	R5112-063	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Other vapor destruction unit</p>
6-TK-9	40 CFR Part 63, Subpart G	63GT-040	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Emissions routed to a fuel gas system</p>
6-TK-90	30 TAC Chapter 115, Storage of VOCs	R5112-063	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Other vapor destruction unit</p>
6-TK-90	40 CFR Part 63, Subpart G	63GT-040	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Emissions routed to a fuel gas system</p>
6-TK-91	30 TAC Chapter 115, Storage of VOCs	R5112-063	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Other vapor destruction unit</p>
6-TK-91	40 CFR Part 63, Subpart G	63GT-040	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Emissions routed to a fuel gas system</p>
6-TK-92	30 TAC Chapter 115, Storage of VOCs	R5112-063	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Other vapor destruction unit</p>
6-TK-92	40 CFR Part 63, Subpart G	63GT-040	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa) Emission Control Type = Emissions routed to a fuel gas system
6-TK-95	30 TAC Chapter 115, Storage of VOCs	R5112-056	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a vapor recovery system (VRS) True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons Control Device Type = Other vapor destruction unit
6-TK-95	40 CFR Part 63, Subpart G	63GT-024	MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G). Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y. Hard Piping = The closed vent system is constructed of hard piping. Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa) Emission Control Type = Emissions routed to a fuel gas system
6-TK-96	30 TAC Chapter 115, Storage of VOCs	R5112-063	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a submerged fill pipe and vapor recovery system True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons Control Device Type = Other vapor destruction unit
6-TK-96	40 CFR Part 63, Subpart G	63GT-040	MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G). Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y. Hard Piping = The closed vent system is constructed of hard piping. Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa) Emission Control Type = Emissions routed to a fuel gas system
6-TK-97	30 TAC Chapter 115, Storage of	R5112-063	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance

Unit ID	Regulation	Index Number	Basis of Determination*
	VOCs		<p>with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Other vapor destruction unit</p>
6-TK-97	40 CFR Part 63, Subpart G	63GT-040	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Emissions routed to a fuel gas system</p>
6-TK-98	30 TAC Chapter 115, Storage of VOCs	R5112-063	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Other vapor destruction unit</p>
6-TK-99	30 TAC Chapter 115, Storage of VOCs	R5112-063	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Other vapor destruction unit</p>
6-TK-99	40 CFR Part 63, Subpart G	63GT-040	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa) Emission Control Type = Emissions routed to a fuel gas system
GRPC4TK3	30 TAC Chapter 115, Storage of VOCs	R5112-056	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a vapor recovery system (VRS) True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons Control Device Type = Other vapor destruction unit
GRPC4TK3	40 CFR Part 63, Subpart G	63GT-024	MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G). Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y. Hard Piping = The closed vent system is constructed of hard piping. Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa) Emission Control Type = Emissions routed to a fuel gas system
GRPC4TK4	30 TAC Chapter 115, Storage of VOCs	R5112-063	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a submerged fill pipe and vapor recovery system True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons Control Device Type = Other vapor destruction unit
GRPC4TK4	40 CFR Part 63, Subpart G	63GT-040	MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G). Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y. Hard Piping = The closed vent system is constructed of hard piping. Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa) Emission Control Type = Emissions routed to a fuel gas system
GRPC4TK5	30 TAC Chapter 115, Storage of	R5112-1.5-	Today's Date = Today's date is March 1, 2013 or later.

Unit ID	Regulation	Index Number	Basis of Determination*
	VOCs		<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>
GRPC4TK6	30 TAC Chapter 115, Storage of VOCs	R5112-1.5-	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is less than or equal to 1,000 gallons</p>
N2-F-36	30 TAC Chapter 115, Storage of VOCs	R5112-1.5-	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>
S2-TK-73	30 TAC Chapter 115, Storage of VOCs	R5112-1.0-	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>
S3-F-50	30 TAC Chapter 115, Storage of VOCs	R5112-1.5-	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>
S4-F-14	30 TAC Chapter 115, Storage of VOCs	R5112-1.5-	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
S4-F-56	30 TAC Chapter 115, Storage of VOCs	R5112-1.5-	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>
S4-TK-72	30 TAC Chapter 115, Storage of VOCs	R5112-1.0-	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>
C4BARGE	40 CFR Part 63, Subpart Y	63Y-005	<p>Subpart Y Facility Type = Existing onshore loading terminal (located onshore or less than 0.5 miles from shore).</p> <p>Ballasting Operations = Operations other than or in addition to ballasting operations are performed at the facility.</p> <p>Vapor Pressure = Vapor pressure is greater than or equal to 10.3 kilopascals (1.5 psia) at standard conditions, 20° C and 760 mm Hg.</p> <p>Subpart BB Applicability = Marine vessel loading operations are not subject to and complying with 40 CFR Part 61, Subpart BB.</p> <p>Material Loaded = Material other than crude oil or gasoline.</p> <p>HAP Impurities Only = Marine vessel loading operations at loading berths transfer liquids containing organic hazardous air pollutants other than as impurities.</p> <p>Source Emissions = Source with emissions less than 10 and 25 tons.</p>
LDGPRSFUG	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-024	<p>Chapter 115 Control Device Type = Control device other than a flare, vapor combustor, catalytic incinerator, direct flame incinerator, chiller, or carbon adsorption system.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Only loading.</p> <p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Loading greater than or equal to 20,000 gallons per day.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>
LDGPRSFUG	40 CFR Part 63,	63GL-003	Transfer Rack Type = Group 1 transfer rack (as defined in 40 CFR § 63.111).

Unit ID	Regulation	Index Number	Basis of Determination*
	Subpart G		<p>Vapor Balancing System = A vapor balancing system is being used to reduce emissions of organic hazardous air pollutants.</p> <p>Bypass Lines = The vent system contains by-pass lines that could divert a vent stream flow away from the control device.</p> <p>Closed Vent System = Closed vent system is subject to § 63.172 of Subpart H.</p> <p>Flow Indicator = The by-pass line valve is secured with a carseal or lock-and-key configuration.</p>
LDGTKFUG	30 TAC Chapter 115, Loading and Unloading of VOC	R5217	<p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure less than 0.5 psia.</p>
BDMTS3BA	30 TAC Chapter 117, Subchapter B	R7ICI-502	<p>Unit Type = Process heater</p> <p>Maximum Rated Capacity = MRC is less than 40 MMBtu/hr.</p>
UW6BB8	30 TAC Chapter 117, Subchapter B	R7105	<p>NO<sub>x</sub> Emission Limitation = Title 30 TAC § 117.110(a)(1).</p> <p>Unit Type = Other industrial, commercial, or institutional boiler.</p> <p>Maximum Rated Capacity = MRC is greater than or equal to 250 MMBtu/hr.</p> <p>NO<sub>x</sub> Monitoring System = Continuous emissions monitoring system.</p> <p>Fuel Flow Monitoring = Unit operates with a NO<sub>x</sub> and diluent CEMS and monitors stack exhaust flow per 30 TAC §§ 117.140(a)(2)(A), 117.340(a)(2)(A) or 117.440(a)(2)(A).</p> <p>RACT Date Placed in Service = On or after the final compliance date specified in 30 TAC § 117.9000.</p> <p>CO Emission Limitation = Title 30 TAC § 117.110(c)(1).</p> <p>Functionally Identical Replacement = Unit is not a functionally identical replacement.</p> <p>CO Monitoring System = Continuous emissions monitoring system complying with 30 TAC § 117.8100(a)(1).</p> <p>Fuel Type #1 = Natural gas.</p> <p>Fuel Type #2 = Gaseous fuel other than natural gas landfill gas or renewable non-fossil fuel gases.</p> <p>NO<sub>x</sub> Emission Limit Average = Emission limit in pounds/hour on a block one-hour average.</p> <p>NO<sub>x</sub> Reductions = Post combustion control technique with ammonia injection.</p> <p>Annual Heat Input = Annual heat input is greater than 2.2(10<sup>11</sup>) Btu/yr, based on rolling 12-month average.</p> <p>Common Stack Combined = The unit is not vented through a common stack; or the total rated heat input from combined units is less than 250 MMBtu/hr; and the annual combined heat input is 2.2(10<sup>11</sup>) Btu/yr or less.</p>
UW6BB8	40 CFR Part 60, Subpart Db	60Db	<p>60.42b(k)(2) Low Sulfur Exemption = The § 60.42b(k)(2) exemption applies.</p> <p>Construction/Modification Date = Constructed or reconstructed after February 28, 2005.</p> <p>D-Series Fuel Type #1 = Natural gas.</p> <p>60.42b(k)(4) Alternative = The requirements of § 60.42b(k)(1) are used.</p> <p>Heat Input Capacity = Heat input capacity is greater than 250 MMBtu/hr (73 MW).</p> <p>PM Monitoring Type = No particulate monitoring.</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>Opacity Monitoring Type = No particulate (opacity) monitoring.</p> <p>Subpart Da = The affected facility does not meet applicability requirements of 40 CFR Part 60, Subpart Da.</p> <p>Changes to Existing Affected Facility = No change has been made to the existing steam generating unit, which was not previously subject to 40 CFR Part 60, Subpart Db, for the sole purpose of combusting gases containing totally reduced sulfur as defined under 40 CFR § 60.281.</p> <p>NOx Monitoring Type = Continuous emission monitoring system.</p> <p>Electrical or Mechanical Output = 10% or less of the annual output is electrical or mechanical.</p> <p>SO2 Monitoring Type = No SO<sub>2</sub> monitoring.</p> <p>Subpart Ea, Eb or AAAA = The affected facility does not meet applicability requirements of and is subject to 40 CFR Part 60, Subpart Ea, Eb or AAAA.</p> <p>Subpart J = The affected facility does not meet applicability requirements of 40 CFR Part 60, Subpart J.</p> <p>Subpart E = The affected facility does not meet applicability requirements of 40 CFR Part 60, Subpart E.</p> <p>Subpart KKKK = The affected facility is not a heat recovery steam generator associated with combined cycle gas turbines and that meets applicability requirements of and is subject to 40 CFR Part 60, Subpart KKKK.</p> <p>Technology Type = Other conventional technology.</p> <p>ACF Option - SO2 = Other ACF or no ACF.</p> <p>Subpart Cb or BBBB = The affected facility is not covered by an EPA approved State or Federal section 111(d)/129 plan implementing 40 CFR Part 60, Subpart Cb or BBBB emission guidelines.</p> <p>Unit Type = OTHER UNIT TYPE</p> <p>ACF Option - PM = Other ACF or no ACF.</p> <p>Heat Release Rate = Natural gas oil with a heat release rate greater than 70 MBtu/hr/ft<sup>3</sup>.</p> <p>60.49Da(n) Alternative = The facility is not using the § 60.49Da(n) alternative.</p> <p>ACF Option - NOx = Other ACF or no ACF.</p> <p>60.49Da(m) Alternative = The facility is not using the § 60.49Da(m) alternative.</p>
UW6BB8	40 CFR Part 60, Subpart Db	60Db-002Y	<p>60.42b(k)(2) Low Sulfur Exemption = The § 60.42b(k)(2) exemption applies.</p> <p>Alternate Emission Limit (AEL) = The facility combusts byproduct/waste with either natural gas or oil and did not petition the EPA Administrator to establish a NO<sub>x</sub> emission limit that applies specifically when the byproduct/waste is combusted.</p> <p>Construction/Modification Date = Constructed or reconstructed after February 28, 2005.</p> <p>D-Series Fuel Type #1 = Natural gas.</p> <p>60.42b(k)(4) Alternative = The requirements of § 60.42b(k)(1) are used.</p> <p>D-Series Fuel Type #2 = Gaseous fossil fuel other than natural gas and coal-derived synthetic fuel meeting the definition of natural gas.</p> <p>Heat Input Capacity = Heat input capacity is greater than 250 MMBtu/hr (73 MW).</p> <p>PM Monitoring Type = No particulate monitoring.</p> <p>Opacity Monitoring Type = No particulate (opacity) monitoring.</p> <p>Subpart Da = The affected facility does not meet applicability requirements of 40 CFR Part 60, Subpart Da.</p> <p>Changes to Existing Affected Facility = No change has been made to the existing steam generating unit, which was not previously subject to 40 CFR Part 60, Subpart Db, for the sole purpose of combusting gases containing totally reduced sulfur</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>as defined under 40 CFR § 60.281.</p> <p>NOx Monitoring Type = Continuous emission monitoring system.</p> <p>Electrical or Mechanical Output = 10% or less of the annual output is electrical or mechanical.</p> <p>SO2 Monitoring Type = No SO<sub>2</sub> monitoring.</p> <p>Subpart Ea, Eb or AAAA = The affected facility does not meet applicability requirements of and is subject to 40 CFR Part 60, Subpart Ea, Eb or AAAA.</p> <p>Subpart J = The affected facility does not meet applicability requirements of 40 CFR Part 60, Subpart J.</p> <p>Subpart E = The affected facility does not meet applicability requirements of 40 CFR Part 60, Subpart E.</p> <p>Subpart KKKK = The affected facility is not a heat recovery steam generator associated with combined cycle gas turbines and that meets applicability requirements of and is subject to 40 CFR Part 60, Subpart KKKK.</p> <p>Technology Type = Other conventional technology.</p> <p>ACF Option - SO2 = Other ACF or no ACF.</p> <p>Subpart Cb or BBBB = The affected facility is not covered by an EPA approved State or Federal section 111(d)/129 plan implementing 40 CFR Part 60, Subpart Cb or BBBB emission guidelines.</p> <p>Unit Type = OTHER UNIT TYPE</p> <p>ACF Option - PM = Other ACF or no ACF.</p> <p>Heat Release Rate = Natural gas oil with a heat release rate greater than 70 MBtu/hr/ft<sup>3</sup>.</p> <p>60.49Da(n) Alternative = The facility is not using the § 60.49Da(n) alternative.</p> <p>ACF Option - NOx = Other ACF or no ACF.</p> <p>60.49Da(m) Alternative = The facility is not using the § 60.49Da(m) alternative.</p>
UW6BB8	40 CFR Part 63, Subpart DDDDD	63DDDDD	Construction/Reconstruction Date = Construction or reconstruction began on or before June 4, 2010.
UW6BB9	30 TAC Chapter 117, Subchapter B	R7105	<p>NOx Emission Limitation = Title 30 TAC § 117.110(a)(1).</p> <p>Unit Type = Other industrial, commercial, or institutional boiler.</p> <p>Maximum Rated Capacity = MRC is greater than or equal to 250 MMBtu/hr.</p> <p>NOx Monitoring System = Continuous emissions monitoring system.</p> <p>Fuel Flow Monitoring = Unit operates with a NO<sub>x</sub> and diluent CEMS and monitors stack exhaust flow per 30 TAC §§ 117.140(a)(2)(A), 117.340(a)(2)(A) or 117.440(a)(2)(A).</p> <p>RACT Date Placed in Service = On or after the final compliance date specified in 30 TAC § 117.9000.</p> <p>CO Emission Limitation = Title 30 TAC § 117.110(c)(1).</p> <p>Functionally Identical Replacement = Unit is not a functionally identical replacement.</p> <p>CO Monitoring System = Continuous emissions monitoring system complying with 30 TAC § 117.8100(a)(1).</p> <p>Fuel Type #1 = Natural gas.</p> <p>Fuel Type #2 = Gaseous fuel other than natural gas landfill gas or renewable non-fossil fuel gases.</p> <p>NH3 Emission Limitation = Title 30 TAC § 117.110(c)(2).</p> <p>NOx Emission Limit Average = Emission limit in pounds/hour on a block one-hour average.</p> <p>NOx Reductions = Post combustion control technique with ammonia injection.</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>Annual Heat Input = Annual heat input is greater than 2.2(10<sup>11</sup>) Btu/yr, based on rolling 12-month average.</p> <p>Common Stack Combined = The unit is not vented through a common stack; or the total rated heat input from combined units is less than 250 MMBtu/hr; and the annual combined heat input is 2.2(10<sup>11</sup>) Btu/yr or less.</p>
UW6BB9	40 CFR Part 60, Subpart Db	60Db	<p>60.42b(k)(2) Low Sulfur Exemption = The § 60.42b(k)(2) exemption applies.</p> <p>Construction/Modification Date = Constructed or reconstructed after February 28, 2005.</p> <p>D-Series Fuel Type #1 = Natural gas.</p> <p>60.42b(k)(4) Alternative = The requirements of § 60.42b(k)(1) are used.</p> <p>Heat Input Capacity = Heat input capacity is greater than 250 MMBtu/hr (73 MW).</p> <p>PM Monitoring Type = No particulate monitoring.</p> <p>Opacity Monitoring Type = No particulate (opacity) monitoring.</p> <p>Subpart Da = The affected facility does not meet applicability requirements of 40 CFR Part 60, Subpart Da.</p> <p>Changes to Existing Affected Facility = No change has been made to the existing steam generating unit, which was not previously subject to 40 CFR Part 60, Subpart Db, for the sole purpose of combusting gases containing totally reduced sulfur as defined under 40 CFR § 60.281.</p> <p>NOx Monitoring Type = Continuous emission monitoring system.</p> <p>Electrical or Mechanical Output = 10% or less of the annual output is electrical or mechanical.</p> <p>SO2 Monitoring Type = No SO<sub>2</sub> monitoring.</p> <p>Subpart Ea, Eb or AAAA = The affected facility does not meet applicability requirements of and is subject to 40 CFR Part 60, Subpart Ea, Eb or AAAA.</p> <p>Subpart J = The affected facility does not meet applicability requirements of 40 CFR Part 60, Subpart J.</p> <p>Subpart E = The affected facility does not meet applicability requirements of 40 CFR Part 60, Subpart E.</p> <p>Subpart KKKK = The affected facility is not a heat recovery steam generator associated with combined cycle gas turbines and that meets applicability requirements of and is subject to 40 CFR Part 60, Subpart KKKK.</p> <p>Technology Type = Other conventional technology.</p> <p>ACF Option - SO2 = Other ACF or no ACF.</p> <p>Subpart Cb or BBBB = The affected facility is not covered by an EPA approved State or Federal section 111(d)/129 plan implementing 40 CFR Part 60, Subpart Cb or BBBB emission guidelines.</p> <p>Unit Type = OTHER UNIT TYPE</p> <p>ACF Option - PM = Other ACF or no ACF.</p> <p>Heat Release Rate = Natural gas oil with a heat release rate greater than 70 MBtu/hr/ft<sup>3</sup>.</p> <p>60.49Da(n) Alternative = The facility is not using the § 60.49Da(n) alternative.</p> <p>ACF Option - NOx = Other ACF or no ACF.</p> <p>60.49Da(m) Alternative = The facility is not using the § 60.49Da(m) alternative.</p>
UW6BB9	40 CFR Part 60, Subpart Db	60Db-002Y	<p>60.42b(k)(2) Low Sulfur Exemption = The § 60.42b(k)(2) exemption applies.</p> <p>Construction/Modification Date = Constructed or reconstructed after February 28, 2005.</p> <p>D-Series Fuel Type #1 = Natural gas.</p> <p>60.42b(k)(4) Alternative = The requirements of § 60.42b(k)(1) are used.</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>D-Series Fuel Type #2 = Gaseous fossil fuel other than natural gas and coal-derived synthetic fuel meeting the definition of natural gas.</p> <p>Heat Input Capacity = Heat input capacity is greater than 250 MMBtu/hr (73 MW).</p> <p>PM Monitoring Type = No particulate monitoring.</p> <p>Opacity Monitoring Type = No particulate (opacity) monitoring.</p> <p>Subpart Da = The affected facility does not meet applicability requirements of 40 CFR Part 60, Subpart Da.</p> <p>Changes to Existing Affected Facility = No change has been made to the existing steam generating unit, which was not previously subject to 40 CFR Part 60, Subpart Db, for the sole purpose of combusting gases containing totally reduced sulfur as defined under 40 CFR § 60.281.</p> <p>NOx Monitoring Type = Continuous emission monitoring system.</p> <p>Electrical or Mechanical Output = 10% or less of the annual output is electrical or mechanical.</p> <p>SO2 Monitoring Type = No SO<sub>2</sub> monitoring.</p> <p>Subpart Ea, Eb or AAAA = The affected facility does not meet applicability requirements of and is subject to 40 CFR Part 60, Subpart Ea, Eb or AAAA.</p> <p>Subpart J = The affected facility does not meet applicability requirements of 40 CFR Part 60, Subpart J.</p> <p>Subpart E = The affected facility does not meet applicability requirements of 40 CFR Part 60, Subpart E.</p> <p>Subpart KKKK = The affected facility is not a heat recovery steam generator associated with combined cycle gas turbines and that meets applicability requirements of and is subject to 40 CFR Part 60, Subpart KKKK.</p> <p>Technology Type = Other conventional technology.</p> <p>ACF Option - SO2 = Other ACF or no ACF.</p> <p>Subpart Cb or BBBB = The affected facility is not covered by an EPA approved State or Federal section 111(d)/129 plan implementing 40 CFR Part 60, Subpart Cb or BBBB emission guidelines.</p> <p>Unit Type = OTHER UNIT TYPE</p> <p>ACF Option - PM = Other ACF or no ACF.</p> <p>Heat Release Rate = Natural gas oil with a heat release rate greater than 70 MBtu/hr/ft<sup>3</sup>.</p> <p>60.49Da(n) Alternative = The facility is not using the § 60.49Da(n) alternative.</p> <p>ACF Option - NOx = Other ACF or no ACF.</p> <p>60.49Da(m) Alternative = The facility is not using the § 60.49Da(m) alternative.</p>
UW6BB9	40 CFR Part 63, Subpart DDDDD	63DDDD	Construction/Reconstruction Date = Construction or reconstruction began on or before June 4, 2010.
EPN-3	30 TAC Chapter 111, Visible Emissions	R1111-002	<p>Acid Gases Only = Flare is not used only as an acid gas flare as defined in 30 TAC § 101.1.</p> <p>Emergency/Upset Conditions Only = Flare is used under conditions other than emergency or upset conditions.</p> <p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p>
RSWLDFLR	30 TAC Chapter 111, Visible Emissions	R1111-002	<p>Acid Gases Only = Flare is not used only as an acid gas flare as defined in 30 TAC § 101.1.</p> <p>Emergency/Upset Conditions Only = Flare is used under conditions other than emergency or upset conditions.</p> <p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Construction Date = Newest source routing emissions to the flare began construction after January 31, 1972.</p>

Unit ID	Regulation	Index Number	Basis of Determination*
RSWLDFLR	40 CFR Part 60, Subpart A	60A	Subject to 40 CFR § 60.18 = Flare is subject to 40 CFR § 60.18. Adhering to Heat Content Specifications = Adhering to the heat content specifications in 40 CFR § 60.18(c)(3)(ii) and the maximum tip velocity specifications in 40 CFR § 60.18(c)(4). Flare Assist Type = Non-assisted Flare Exit Velocity = Flare exit velocity is greater than or equal to 60 ft/s (18.3 m/sec) but less than 400 ft/s (122 m/sec). Heating Value of Gas = Heating value is greater than 1000 Btu/scf (37.3 MJ/scm)
UWN6R1	30 TAC Chapter 111, Visible Emissions	R1111-002	Acid Gases Only = Flare is not used only as an acid gas flare as defined in 30 TAC § 101.1. Emergency/Upset Conditions Only = Flare is used under conditions other than emergency or upset conditions. Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.
UWN6R1	40 CFR Part 60, Subpart A	60A-003	Subject to 40 CFR § 60.18 = Flare is subject to 40 CFR § 60.18. Adhering to Heat Content Specifications = Adhering to the heat content specifications in 40 CFR § 60.18(c)(3)(ii) and the maximum tip velocity specifications in 40 CFR § 60.18(c)(4). Flare Assist Type = Steam-assisted Flare Exit Velocity = Flare exit velocity is less than 60 ft/s (18.3 m/sec)
UWS6R1	30 TAC Chapter 111, Visible Emissions	R1111-002	Acid Gases Only = Flare is not used only as an acid gas flare as defined in 30 TAC § 101.1. Emergency/Upset Conditions Only = Flare is used under conditions other than emergency or upset conditions. Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.
UWS6R1	40 CFR Part 60, Subpart A	60A-003	Subject to 40 CFR § 60.18 = Flare is subject to 40 CFR § 60.18. Adhering to Heat Content Specifications = Adhering to the heat content specifications in 40 CFR § 60.18(c)(3)(ii) and the maximum tip velocity specifications in 40 CFR § 60.18(c)(4). Flare Assist Type = Steam-assisted Flare Exit Velocity = Flare exit velocity is less than 60 ft/s (18.3 m/sec)
BDACETFUG	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	R5352-ALL	SOP/GOP Index No. = Owner/Operator assumes VOC fugitive control requirements for all components subject to 30 TAC Chapter 115, Subchapter D, Division 3 with no alternate control or control device.
BDACETFUG	40 CFR Part 63, Subpart H	63H-ALL	SOP Index No. = Owner/Operator assumes fugitive control requirements for all components in VOC or VHAP service subject to 40 CFR Part 63, Subpart H with no alternated control or control device.
BL-13	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	R5352-ALL	SOP/GOP Index No. = Owner/Operator assumes VOC fugitive control requirements for all components subject to 30 TAC Chapter 115, Subchapter D, Division 3 with no alternate control or control device.
BL-13	40 CFR Part 63, Subpart H	63H-ALL	SOP Index No. = Owner/Operator assumes fugitive control requirements for all components in VOC or VHAP service subject to 40 CFR Part 63, Subpart H with no alternated control or control device.
BL-4	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	R5352-ALL	SOP/GOP Index No. = Owner/Operator assumes VOC fugitive control requirements for all components subject to 30 TAC Chapter 115, Subchapter D, Division 3 with no alternate control or control device.

Unit ID	Regulation	Index Number	Basis of Determination*
BL-4	40 CFR Part 63, Subpart H	63H-ALL	SOP Index No. = Owner/Operator assumes fugitive control requirements for all components in VOC or VHAP service subject to 40 CFR Part 63, Subpart H with no alternated control or control device.
BL-5	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	R5352-ALL	SOP/GOP Index No. = Owner/Operator assumes VOC fugitive control requirements for all components subject to 30 TAC Chapter 115, Subchapter D, Division 3 with no alternate control or control device.
BL-5	40 CFR Part 63, Subpart H	63H-ALL	SOP Index No. = Owner/Operator assumes fugitive control requirements for all components in VOC or VHAP service subject to 40 CFR Part 63, Subpart H with no alternated control or control device.
BL-7	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	R5352-ALL	SOP/GOP Index No. = Owner/Operator assumes VOC fugitive control requirements for all components subject to 30 TAC Chapter 115, Subchapter D, Division 3 with no alternate control or control device.
BL-7	40 CFR Part 63, Subpart H	63H-ALL	SOP Index No. = Owner/Operator assumes fugitive control requirements for all components in VOC or VHAP service subject to 40 CFR Part 63, Subpart H with no alternated control or control device.
BL-8	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	R5352-ALL	SOP/GOP Index No. = Owner/Operator assumes VOC fugitive control requirements for all components subject to 30 TAC Chapter 115, Subchapter D, Division 3 with no alternate control or control device.
BL-8	40 CFR Part 63, Subpart H	63H-ALL	SOP Index No. = Owner/Operator assumes fugitive control requirements for all components in VOC or VHAP service subject to 40 CFR Part 63, Subpart H with no alternated control or control device.
BL-9	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	R5352-ALL	SOP/GOP Index No. = Owner/Operator assumes VOC fugitive control requirements for all components subject to 30 TAC Chapter 115, Subchapter D, Division 3 with no alternate control or control device.
BL-9	40 CFR Part 63, Subpart H	63H-ALL	SOP Index No. = Owner/Operator assumes fugitive control requirements for all components in VOC or VHAP service subject to 40 CFR Part 63, Subpart H with no alternated control or control device.
GRPC4FU1	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	R5352-ALL	SOP/GOP Index No. = Owner/Operator assumes VOC fugitive control requirements for all components subject to 30 TAC Chapter 115, Subchapter D, Division 3 with no alternate control or control device.
GRPC4FU1	40 CFR Part 63, Subpart H	63H-ALL	SOP Index No. = Owner/Operator assumes fugitive control requirements for all components in VOC or VHAP service subject to 40 CFR Part 63, Subpart H with no alternated control or control device.
NDBEFUG	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	R5352-ALL	SOP/GOP Index No. = Owner/Operator assumes VOC fugitive control requirements for all components subject to 30 TAC Chapter 115, Subchapter D, Division 3 with no alternate control or control device.
NDBEFUG	40 CFR Part 63, Subpart H	63H-ALL	SOP Index No. = Owner/Operator assumes fugitive control requirements for all components in VOC or VHAP service subject to 40 CFR Part 63, Subpart H with no alternated control or control device.
NMTBE	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	R5352-ALL	SOP/GOP Index No. = Owner/Operator assumes VOC fugitive control requirements for all components subject to 30 TAC Chapter 115, Subchapter D, Division 3 with no alternate control or control device.

Unit ID	Regulation	Index Number	Basis of Determination*
NMTBE	40 CFR Part 63, Subpart H	63H-ALL	SOP Index No. = Owner/Operator assumes fugitive control requirements for all components in VOC or VHAP service subject to 40 CFR Part 63, Subpart H with no alternated control or control device.
SBDEFUG	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	R5352-ALL	SOP/GOP Index No. = Owner/Operator assumes VOC fugitive control requirements for all components subject to 30 TAC Chapter 115, Subchapter D, Division 3 with no alternate control or control device.
SBDEFUG	40 CFR Part 63, Subpart H	63H-ALL	SOP Index No. = Owner/Operator assumes fugitive control requirements for all components in VOC or VHAP service subject to 40 CFR Part 63, Subpart H with no alternated control or control device.
SMTBE	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	R5352-ALL	SOP/GOP Index No. = Owner/Operator assumes VOC fugitive control requirements for all components subject to 30 TAC Chapter 115, Subchapter D, Division 3 with no alternate control or control device.
SMTBE	40 CFR Part 63, Subpart H	63H-ALL	SOP Index No. = Owner/Operator assumes fugitive control requirements for all components in VOC or VHAP service subject to 40 CFR Part 63, Subpart H with no alternated control or control device.
UWFUG	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	R5352-ALL	SOP/GOP Index No. = Owner/Operator assumes VOC fugitive control requirements for all components subject to 30 TAC Chapter 115, Subchapter D, Division 3 with no alternate control or control device.
UWFUG	40 CFR Part 63, Subpart H	63H-ALL	SOP Index No. = Owner/Operator assumes fugitive control requirements for all components in VOC or VHAP service subject to 40 CFR Part 63, Subpart H with no alternated control or control device.
API SEP	30 TAC Chapter 115, Water Separation	R5131-001	Alternate Control Requirement = The executive director (or the EPA Administrator) has not approved an ACR or exemption criteria in accordance with 30 TAC § 115.910. Exemption = Any single or multiple compartment VOC water separator which separates materials having a true vapor pressure less than 0.5 psia (3.4 kPa) obtained from any equipment.
N2-F-15	30 TAC Chapter 115, Water Separation	R5131-006	Alternate Control Requirement = The executive director (or the EPA Administrator) has not approved an ACR or exemption criteria in accordance with 30 TAC § 115.910. Exemption = Water separator does not qualify for exemption. Emission Control Option = Vapor recovery system which satisfies the provisions of 30 TAC § 115.131. Control Device = Control device or vapor recovery system other than a chiller, carbon adsorber, or incinerator.
N2-F-15	40 CFR Part 63, Subpart G	63G-WW1	Alternate Monitoring Parameters: = COMPLYING WITH THE MONITORING REQUIREMENTS OF SUBPART G Negative Pressure = FIXED ROOF AND CLOSED-VENT SYSTEM ARE NOT OPERATED AND MAINTAINED UNDER NEGATIVE PRESSURE Process Wastewater = OIL-WATER SEPARATOR RECEIVES, MANAGES, OR TREATS PROCESS WASTEWATER STREAMS AS DEFINED IN TITLE 40 CFR PART 63, SUBPART F Closed Vent System = CLOSED VENT SYSTEM IS SUBJECT TO AND COMPLYING WITH § 63.148 New Source = FACILITY IS A EXISTING SOURCE AS DEFINED IN MACT G Bypass Lines = NO BYPASS LINE Control Requirement = CLOSED VENT SYSTEM THAT ROUTES VAPORS TO A CONTROL DEVICE THAT MEETS THE REQUIREMENTS OF 40 CFR § 63.139(C) Combination of Control Devices = VENT STREAM IS NOT TREATED USING A COMBINATION OF CONTROL DEVICES

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>Oil-Water Separator Type = FIXED ROOF AND A CLOSED-VENT SYSTEM THAT ROUTES THE ORGANIC HAZARDOUS AIR POLLUTANT VAPORS VENTED FROM THE OIL-WATER SEPARATOR TO A CONTROL DEVICE</p> <p>Control Device Type = FLARE</p> <p>Floating Roof Alternate Monitoring Parameters = FLOATING ROOF ALTERNATE MONITORING PARAMETERS ARE NOT APPROVED OR ARE NOT REQUESTED</p> <p>Monitoring Options = CONTROL DEVICE IS USING THE MONITORING PARAMETERS SPECIFIED IN TABLE 13</p>
N6-F-144	30 TAC Chapter 115, Water Separation	R5131-006	<p>Alternate Control Requirement = The executive director (or the EPA Administrator) has not approved an ACR or exemption criteria in accordance with 30 TAC § 115.910.</p> <p>Exemption = Water separator does not qualify for exemption.</p> <p>Emission Control Option = Vapor recovery system which satisfies the provisions of 30 TAC § 115.131.</p> <p>Control Device = Control device or vapor recovery system other than a chiller, carbon adsorber, or incinerator.</p>
N6-F-144	40 CFR Part 63, Subpart G	63G-WW1	<p>Alternate Monitoring Parameters: = COMPLYING WITH THE MONITORING REQUIREMENTS OF SUBPART G</p> <p>Negative Pressure = FIXED ROOF AND CLOSED-VENT SYSTEM ARE NOT OPERATED AND MAINTAINED UNDER NEGATIVE PRESSURE</p> <p>Process Wastewater = OIL-WATER SEPARATOR RECEIVES, MANAGES, OR TREATS PROCESS WASTEWATER STREAMS AS DEFINED IN TITLE 40 CFR PART 63, SUBPART F</p> <p>Closed Vent System = CLOSED VENT SYSTEM IS SUBJECT TO AND COMPLYING WITH § 63.148</p> <p>New Source = FACILITY IS A EXISTING SOURCE AS DEFINED IN MACT G</p> <p>Bypass Lines = NO BYPASS LINE</p> <p>Control Requirement = CLOSED VENT SYSTEM THAT ROUTES VAPORS TO A CONTROL DEVICE THAT MEETS THE REQUIREMENTS OF 40 CFR § 63.139(C)</p> <p>Combination of Control Devices = VENT STREAM IS NOT TREATED USING A COMBINATION OF CONTROL DEVICES</p> <p>Oil-Water Separator Type = FIXED ROOF AND A CLOSED-VENT SYSTEM THAT ROUTES THE ORGANIC HAZARDOUS AIR POLLUTANT VAPORS VENTED FROM THE OIL-WATER SEPARATOR TO A CONTROL DEVICE</p> <p>Control Device Type = FLARE</p> <p>Floating Roof Alternate Monitoring Parameters = FLOATING ROOF ALTERNATE MONITORING PARAMETERS ARE NOT APPROVED OR ARE NOT REQUESTED</p> <p>Monitoring Options = CONTROL DEVICE IS USING THE MONITORING PARAMETERS SPECIFIED IN TABLE 13</p>
BMDTS3F105	30 TAC Chapter 111, Visible Emissions	111-111a1a	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = On or before January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.</p>
BMDTS3F105	30 TAC Chapter 115, Vent Gas	R5121-ATM	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p>

Unit ID	Regulation	Index Number	Basis of Determination*
	Controls		<p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p>
BMDTS3F105	30 TAC Chapter 115, Vent Gas Controls	R5121-FLARE	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p>
GRPC4VE1	30 TAC Chapter 115, Vent Gas Controls	R5121-FLARE	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>
GRPC4VE1	30 TAC Chapter 115, Vent Gas Controls	R5121-FUEL GAS	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Control Device Type = Vapor recovery system, as defined in 30 TAC § 115.10, other than an afterburner, blast furnace combustion device, boiler, catalytic or direct flame incinerator, carbon adsorption system, chiller, flare or vapor combustor.</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>
GRPC4VE1	40 CFR Part 63, Subpart G	63G-FLARE	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Flare</p> <p>Overlap = Title 40 CFR Part 63, Subpart G only</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>HAP Concentration = HAP concentration is not needed to determine applicability.</p> <p>By-pass Lines = The vent system does not contain by-pass lines that can divert the vent stream from the control device.</p> <p>Flow Rate = Flow rate is not needed to determine applicability.</p> <p>Electing Control = Electing to control the process vent to the levels required in 40 CFR § 63.113(a)(1) without calculating the TRE index value.</p> <p>Flow Indicator = By-pass line valve is secured with a car-seal or lock-and-key type configuration.</p>
N2-D-7	30 TAC Chapter 115, Vent Gas Controls	R5121-FLARE	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>
N2-D-7	40 CFR Part 63, Subpart G	63G-FLARE	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Flare</p> <p>Overlap = Title 40 CFR Part 63, Subpart G only</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>HAP Concentration = HAP concentration is not needed to determine applicability.</p> <p>By-pass Lines = The vent system does not contain by-pass lines that can divert the vent stream from the control device.</p> <p>Flow Rate = Flow rate is not needed to determine applicability.</p> <p>Electing Control = Electing to control the process vent to the levels required in 40 CFR § 63.113(a)(1) without calculating the TRE index value.</p> <p>Flow Indicator = By-pass line valve is secured with a car-seal or lock-and-key type configuration.</p>
N4-D-10	30 TAC Chapter 115, Vent Gas Controls	R5121-FLARE	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>
N4-D-10	30 TAC Chapter 115, Vent Gas Controls	R5121-FUEL GAS	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>
N4-D-10	40 CFR Part 63, Subpart G	63G-FLARE	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Flare</p> <p>Overlap = Title 40 CFR Part 63, Subpart G only</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>HAP Concentration = HAP concentration is not needed to determine applicability.</p> <p>By-pass Lines = The vent system does not contain by-pass lines that can divert the vent stream from the control device.</p> <p>Flow Rate = Flow rate is not needed to determine applicability.</p> <p>Electing Control = Electing to control the process vent to the levels required in 40 CFR § 63.113(a)(1) without calculating the TRE index value.</p> <p>Flow Indicator = By-pass line valve is secured with a car-seal or lock-and-key type configuration.</p>
N4-D-11	30 TAC Chapter 115, Vent Gas Controls	R5121-FLARE	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>Control Device Type = Smokeless flare</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>
N4-D-11	30 TAC Chapter 115, Vent Gas Controls	R5121-FUEL GAS	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>
N4-D-11	40 CFR Part 63, Subpart G	63G-FLARE	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Flare</p> <p>Overlap = Title 40 CFR Part 63, Subpart G only</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>HAP Concentration = HAP concentration is not needed to determine applicability.</p> <p>By-pass Lines = The vent system does not contain by-pass lines that can divert the vent stream from the control device.</p> <p>Flow Rate = Flow rate is not needed to determine applicability.</p> <p>Electing Control = Electing to control the process vent to the levels required in 40 CFR § 63.113(a)(1) without calculating the TRE index value.</p> <p>Flow Indicator = By-pass line valve is secured with a car-seal or lock-and-key type configuration.</p>
UWN6R1-V	30 TAC Chapter 115, Vent Gas	R5121	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115</p>

Unit ID	Regulation	Index Number	Basis of Determination*
	Controls		<p>establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p>
UWS6R1-V	30 TAC Chapter 115, Vent Gas Controls	R5121	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p>
C4DEGRSR	30 TAC Chapter 115, Degreasing Processes	R5412-003	<p>Solvent Degreasing Machine Type = Remote reservoir cold solvent cleaning machine.</p> <p>Alternate Control Requirement = The TCEQ Executive Director has not approved an alternative control requirement as allowed under 30 TAC § 115.413 or not alternative has been requested.</p> <p>Solvent Sprayed = A solvent is sprayed.</p> <p>Solvent Vapor Pressure = Solvent vapor pressure is less than or equal to 0.6 psia as measured at 100 degrees Fahrenheit.</p> <p>Solvent Heated = The solvent is not heated to a temperature greater than 120° F.</p> <p>Parts Larger than Drainage = Cleaned parts for which the machine is authorized to clean are larger than the internal drainage facility of the machine.</p> <p>Drainage Area = Area is greater than or equal to 16 square inches.</p> <p>Disposal in Enclosed Containers = Waste solvent is properly disposed of in enclosed containers.</p>
PROC4WW	40 CFR Part 63, Subpart G	63G-TPWWc	<p>Series of Processes = The wastewater stream is treated using a single treatment process.</p> <p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or no alternate has been requested.</p> <p>Vented to Control = Emissions from the treatment process are vented to a control device.</p> <p>Biological Treatment Process = Non-biological treatment process.</p> <p>Closed Vent System = Closed vent system is not maintained under negative pressure and is subject to 40 CFR § 63.148.</p> <p>By-Pass Lines = No by-pass lines.</p> <p>Wastewater Stream Designation = Group1 for Table 9 compounds.</p> <p>Combination of Control Devices = The vent stream is treated using a single control device.</p> <p>Monitoring Options = Control device is using the monitoring parameters specified in Table 13 of Subpart G.</p> <p>Wastewater Stream Treatment = Design steam stripper option.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of § 63.143(e)(1) or § 63.143(e)(2) in Table 13 of Subpart G.</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			Control Devices = Flare.
PROC4HON	40 CFR Part 63, Subpart F	63F-009	<p>Applicable Chemicals = The chemical manufacturing process unit manufactures, as a primary product, one or more of the chemicals listed in 40 CFR § 63.100(b)(1)(i) or 40 CFR § 63.100(b)(1)(ii).</p> <p>Intervening Cooling Fluid = There is no intervening cooling fluid containing less than 5 percent by weight of total HAPs listed in Table 4 of 40 CFR Part 63, Subpart F, between the process and cooling water.</p> <p>Table 2 HAP = The chemical manufacturing process unit uses as a reactant or manufactures, as a product or co-product, one or more of the organic hazardous air pollutants in Table 2.</p> <p>Table 4 HAP Content = The recirculating heat exchange system is not used exclusively to cool process fluids that contain less than 5 percent by weight of total HAPs listed in Table 4 of title 40 CFR Part 63, Subpart F.</p> <p>Alternate Means of Emission Limitation = No alternative means of emission limitation has been approved by the EPA Administrator to achieve a reduction in organic HAP emission or no alternate has been requested.</p> <p>NPDES Permit = The once-through heat exchange system is not subject to NPDES permit with an allowable discharge limit of 1 part per million or less above influent concentration or 10 percent or less above influent concentration.</p> <p>Meets 40 CFR 63.104(a)(4)(i)-(iv) = The once-through heat exchange system is not subject to an NPDES permit that meets 40 CFR § 63.104(a)(4)(i) - (iv).</p> <p>Heat Exchange System = A heat exchange system is utilized.</p> <p>Table 9 HAP Content = The once-through heat exchange system is not used exclusively to cool process fluids that contain less than 5 percent by weight of total HAPs listed in Table 9 of 40 CFR Part 63, Subpart G.</p> <p>Cooling Water Monitored = The cooling water is being monitored for the presence of one or more HAPs or other representative substances whose presence in cooling water indicates a leak.</p> <p>Cooling Water Pressure = The heat exchange system is not operated with the minimum pressure on the cooling water side at least 35 kilopascals greater than the maximum pressure on the process side.</p>

\* - The "unit attributes" or operating conditions that determine what requirements apply

## NSR Versus Title V FOP

The state of Texas has two Air permitting programs, New Source Review (NSR) and Title V Federal Operating Permits. The two programs are substantially different both in intent and permit content.

NSR is a preconstruction permitting program authorized by the Texas Clean Air Act and Title I of the Federal Clean Air Act (FCAA). The processing of these permits is governed by 30 Texas Administrative Code (TAC) Chapter 116.111. The Title V Federal Operating Program is a federal program authorized under Title V of the FCAA that has been delegated to the state of Texas to administer and is governed by 30 TAC Chapter 122. The major differences between the two permitting programs are listed in the table below:

NSR Permit	Federal Operating Permit(FOP)
Issued Prior to new Construction or modification of an existing facility	For initial permit with application shield, can be issued after operation commences; significant revisions require approval prior to operation.
Authorizes air emissions	Codifies existing applicable requirements, does not authorize new emissions
Ensures issued permits are protective of the environment and human health by conducting a health effects review and that requirement for best available control technology (BACT) is implemented.	Applicable requirements listed in permit are used by the inspectors to ensure proper operation of the site as authorized. Ensures that adequate monitoring is in place to allow compliance determination with the FOP.
Up to two Public notices may be required. Opportunity for public comment and contested case hearings for some authorizations.	One public notice required. Opportunity for public comments. No contested case hearings.
Applies to all point source emissions in the state.	Applies to all major sources and some non-major sources identified by the EPA.
Applies to facilities: a portion of site or individual emission sources	One or multiple FOPs cover the entire site (consists of multiple facilities)
Permits include terms and conditions under which the applicant must construct and operate its various equipment and processes on a facility basis.	Permits include terms and conditions that specify the general operational requirements of the site; and also include codification of all applicable requirements for emission units at the site.
Opportunity for EPA review for Federal Prevention of Significant Deterioration (PSD) and Nonattainment (NA) permits for major sources.	Opportunity for EPA review, Affected states review, and a Public petition period for every FOP.
Permits have a table listing maximum emission limits for pollutants	Permit has an applicable requirements table and Periodic Monitoring (PM) / Compliance Assurance Monitoring (CAM) tables which document applicable monitoring requirements.
Permits can be altered or amended upon application by company. Permits must be issued before construction or modification of facilities can begin.	Permits can be revised through several revision processes, which provide for different levels of public notice and opportunity to comment. Changes that would be significant revisions require that a revised permit be issued before those changes can be operated.
NSR permits are issued independent of FOP requirements.	FOP are independent of NSR permits, but contain a list of all NSR permits incorporated by reference

## New Source Review Requirements

Below is a list of the New Source Review (NSR) permits for the permitted area. These NSR permits are incorporated by reference into the operating permit and are enforceable under it. These permits can be found in the main TCEQ file room, located on the first floor of Building E, 12100 Park 35 Circle, Austin, Texas. The Public Education Program may be contacted at 1-800-687-4040 or the Air Permits Division (APD) may be contacted at 1-512-239-1250 for help with any question.

Additionally, the site contains emission units that are permitted by rule under the requirements of 30 TAC Chapter 106, Permits by Rule. The following table specifies the permits by rule that apply to the site. All current permits by rule are contained in Chapter 106. Outdated 30 TAC Chapter 106 permits by rule may be viewed at the following Web site:

[www.tceq.texas.gov/permitting/air/permitbyrule/historical\\_rules/old106list/index106.html](http://www.tceq.texas.gov/permitting/air/permitbyrule/historical_rules/old106list/index106.html)

Outdated Standard Exemption lists may be viewed at the following Web site:

[www.tceq.texas.gov/permitting/air/permitbyrule/historical\\_rules/oldselist/se\\_index.html](http://www.tceq.texas.gov/permitting/air/permitbyrule/historical_rules/oldselist/se_index.html)

The status of air permits and applications and a link to the Air Permits Remote Document Server is located at the following Web site:

[www.tceq.texas.gov/permitting/air/nav/air\\_status\\_permits.html](http://www.tceq.texas.gov/permitting/air/nav/air_status_permits.html)

<b>Title 30 TAC Chapter 116 Permits, Special Permits, and Other Authorizations (Other Than Permits By Rule, PSD Permits, or NA Permits) for the Application Area.</b>	
Authorization No.: 20485	Issuance Date: 04/09/2015
Authorization No.: 79198	Issuance Date: 01/15/2016
<b>Permits By Rule (30 TAC Chapter 106) for the Application Area</b>	
Number: 106.261	Version No./Date: 09/04/2000
Number: 106.261	Version No./Date: 11/01/2003
Number: 106.262	Version No./Date: 09/04/2000
Number: 106.262	Version No./Date: 11/01/2003
Number: 106.264	Version No./Date: 09/04/2000
Number: 106.433	Version No./Date: 09/04/2000
Number: 106.454	Version No./Date: 11/01/2001
Number: 106.475	Version No./Date: 09/04/2000
Number: 106.476	Version No./Date: 09/04/2000
Number: 106.478	Version No./Date: 09/04/2000

### **Emission Units and Emission Points**

In air permitting terminology, any source capable of generating emissions (for example, an engine or a sandblasting area) is called an Emission Unit. For purposes of Title V, emission units are specifically listed in the operating permit when they have applicable requirements other than New Source Review (NSR), or when they are listed in the permit shield table.

The actual physical location where the emissions enter the atmosphere (for example, an engine stack or a sand-blasting yard) is called an emission point. For New Source Review preconstruction permitting purposes, every emission unit has an associated emission point. Emission limits are listed in an NSR permit, associated with an emission point. This list of emission points and emission limits per pollutant is commonly referred to as the “Maximum Allowable Emission Rate Table”, or “MAERT” for short. Specifically, the MAERT lists the Emission Point Number (EPN) that identifies the emission point, followed immediately by the Source Name, identifying the emission unit that is the source of those emissions on this table.

Thus, by reference, an emission unit in a Title V operating permit is linked by reference number to an NSR authorization, and its related emission point.

**Monitoring Sufficiency**

Federal and state rules, 40 CFR § 70.6(a)(3)(i)(B) and 30 TAC § 122.142(c) respectively, require that each federal operating permit include additional monitoring for applicable requirements that lack periodic or instrumental monitoring (which may include recordkeeping that serves as monitoring) that yields reliable data from a relevant time period that are representative of the emission unit’s compliance with the applicable emission limitation or standard. Furthermore, the federal operating permit must include compliance assurance monitoring (CAM) requirements for emission sources that meet the applicability criteria of 40 CFR Part 64 in accordance with 40 CFR § 70.6(a)(3)(i)(A) and 30 TAC § 122.604(b).

With the exception of any emission units listed in the Periodic Monitoring or CAM Summaries in the FOP, the TCEQ Executive Director has determined that the permit contains sufficient monitoring, testing, recordkeeping, and reporting requirements that assure compliance with the applicable requirements. If applicable, each emission unit that requires additional monitoring in the form of periodic monitoring or CAM is described in further detail under the Rationale for CAM/PM Methods Selected section following this paragraph.

**Rationale for Compliance Assurance Monitoring (CAM)/ Periodic Monitoring Methods Selected**

**Compliance Assurance Monitoring (CAM):**

Compliance Assurance Monitoring (CAM) is a federal monitoring program established under Title 40 Code of Federal Regulations Part 64 (40 CFR Part 64).

Emission units are subject to CAM requirements if they meet the following criteria:

1. the emission unit is subject to an emission limitation or standard for an air pollutant (or surrogate thereof) in an applicable requirement;
2. the emission unit uses a control device to achieve compliance with the emission limitation or standard specified in the applicable requirement; and
3. the emission unit has the pre-control device potential to emit greater than or equal to the amount in tons per year for a site to be classified as a major source.

The following table(s) identifies the emission unit(s) that is subject to CAM:

<b>Unit/Group/Process Information</b>	
ID No.: UWN6R1-V	
Control Device ID No.: UWN6R1	Control Device Type: Flare
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121
Pollutant: VOC	Main Standard: § 115.122(a)(1)
<b>Monitoring Information</b>	
Indicator: Visible Emissions	

Minimum Frequency: once per day
Averaging Period: n/a
Deviation Limit: No visible emissions. If visible emissions are observed the permit holder shall either report a deviation or determine visible emissions consistent with Test Method 22 or Test Method 9
Basis of CAM: It is widely practiced and accepted to monitor flares for visible emissions by closed circuit cameras and visual inspection. Visible emissions observations indicate that the flare is not efficiently combusting the emissions or there is incomplete combustion. Visible emissions can indicate an improper inlet flow rate or net heating value of the emissions routed to the flare. Monitoring visible emissions is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart A; 30 TAC Chapter 111; and 30 TAC Chapter 115. This procedure is consistent with the EPA "CAM Technical Document" (August 1998) which provides an example of using "EPA Test Method 22-like" procedures for determining visible emissions.

<b>Unit/Group/Process Information</b>	
ID No.: UWS6R1-V	
Control Device ID No.: UWS6R1	Control Device Type: Flare
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121
Pollutant: VOC	Main Standard: § 115.122(a)(1)
<b>Monitoring Information</b>	
Indicator: Visible Emissions	
Minimum Frequency: once per day	
Averaging Period: n/a	
Deviation Limit: No visible emissions. If visible emissions are observed the permit holder shall either report a deviation or determine visible emissions consistent with Test Method 22 or Test Method 9	
Basis of CAM: It is widely practiced and accepted to monitor flares for visible emissions by closed circuit cameras and visual inspection. Visible emissions observations indicate that the flare is not efficiently combusting the emissions or there is incomplete combustion. Visible emissions can indicate an improper inlet flow rate or net heating value of the emissions routed to the flare. Monitoring visible emissions is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart A; 30 TAC Chapter 111; and 30 TAC Chapter 115. This procedure is consistent with the EPA "CAM Technical Document" (August 1998) which provides an example of using "EPA Test Method 22-like" procedures for determining visible emissions.	

**Periodic Monitoring:**

The Federal Clean Air Act requires that each federal operating permit include monitoring sufficient to assure compliance with the terms and conditions of the permit. Most of the emission limits and standards applicable to emission units at Title V sources include adequate monitoring to show that the units meet the limits and standards. For those requirements that do not include monitoring, or where the monitoring is not sufficient to assure compliance, the federal operating permit must include such monitoring for the emission units affected. The following emission units are subject to periodic monitoring requirements because the emission units are subject to an emission limitation or standard for an air pollutant (or surrogate thereof) in an applicable requirement that does not already require monitoring, or the monitoring for the applicable requirement is not sufficient to assure compliance:

<b>Unit/Group/Process Information</b>	
ID No.: BMDTS3F105	
Control Device ID No.: N/A	Control Device Type: N/A
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: 111-111a1a
Pollutant: PM (OPACITY)	Main Standard: § 111.111(a)(1)(A)
<b>Monitoring Information</b>	
Indicator: Visible Emissions	
Minimum Frequency: once per quarter	
Averaging Period: n/a	
Deviation Limit: 30% opacity	
Basis of monitoring: The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.	

<b>Unit/Group/Process Information</b>	
ID No.: C4DEGRSR	
Control Device ID No.: N/A	Control Device Type: N/A
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 115, Degreasing Processes	SOP Index No.: R5412-003
Pollutant: VOC	Main Standard: § 115.412(1)
<b>Monitoring Information</b>	
Indicator: Visual Inspection	
Minimum Frequency: Monthly	
Averaging Period: n/a	
Deviation Limit: Any monitoring data which indicates that the cold cleaner is not in compliance with the applicable requirements of § 115.412(1)(A)-(F) shall be considered and reported as a deviation.	
<p>Basis of monitoring:  The monitoring option to cover cold cleaner or the open-top vapor cleaner was included in the EPA "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources. In addition to covering the cleaner records of monthly inspections of equipment is an effective way to ensure that the system is operating in accordance with its design.</p>	

<b>Unit/Group/Process Information</b>	
ID No.: GRPC4VE1	
Control Device ID No.: N/A	Control Device Type: N/A
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-FUEL GAS
Pollutant: VOC	Main Standard: § 115.122(a)(2)
<b>Monitoring Information</b>	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: n/a*	
Deviation Limit: VOC concentration of no more than 20 ppmv (on a dry basis corrected to 3.0% oxygen for combustion devices)	
<p><b>Basis of monitoring:</b>  It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for boilers/process heaters. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of combustion temperature of a boiler/process heater is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, DD, and HH; and 30 TAC Chapter 115.</p>	

**Compliance Review**

1. In accordance with 30 TAC Chapter 60, the compliance history was reviewed on May 17, 2016.

Site rating: 7.56 / Satisfactory Company rating: 3.41 / Satisfactory

(High < 0.10; Satisfactory ≥ 0.10 and ≤ 55; Unsatisfactory > 55)

2. Has the permit changed on the basis of the compliance history or site/company rating? .....No

**Site/Permit Area Compliance Status Review**

1. Were there any out-of-compliance units listed on Form OP-ACPS? .....No

2. Is a compliance plan and schedule included in the permit? .....No

**Available Unit Attribute Forms**

- OP-UA1 - Miscellaneous and Generic Unit Attributes
- OP-UA2 - Stationary Reciprocating Internal Combustion Engine Attributes
- OP-UA3 - Storage Tank/Vessel Attributes
- OP-UA4 - Loading/Unloading Operations Attributes
- OP-UA5 - Process Heater/Furnace Attributes
- OP-UA6 - Boiler/Steam Generator/Steam Generating Unit Attributes
- OP-UA7 - Flare Attributes
- OP-UA8 - Coal Preparation Plant Attributes
- OP-UA9 - Nonmetallic Mineral Process Plant Attributes
- OP-UA10 - Gas Sweetening/Sulfur Recovery Unit Attributes
- OP-UA11 - Stationary Turbine Attributes
- OP-UA12 - Fugitive Emission Unit Attributes
- OP-UA13 - Industrial Process Cooling Tower Attributes
- OP-UA14 - Water Separator Attributes
- OP-UA15 - Emission Point/Stationary Vent/Distillation Operation/Process Vent Attributes
- OP-UA16 - Solvent Degreasing Machine Attributes
- OP-UA17 - Distillation Unit Attributes
- OP-UA18 - Surface Coating Operations Attributes
- OP-UA19 - Wastewater Unit Attributes
- OP-UA20 - Asphalt Operations Attributes
- OP-UA21 - Grain Elevator Attributes
- OP-UA22 - Printing Attributes
- OP-UA24 - Wool Fiberglass Insulation Manufacturing Plant Attributes
- OP-UA25 - Synthetic Fiber Production Attributes
- OP-UA26 - Electroplating and Anodizing Unit Attributes
- OP-UA27 - Nitric Acid Manufacturing Attributes
- OP-UA28 - Polymer Manufacturing Attributes
- OP-UA29 - Glass Manufacturing Unit Attributes
- OP-UA30 - Kraft, Soda, Sulfite, and Stand-Alone Semichemical Pulp Mill Attributes
- OP-UA31 - Lead Smelting Attributes
- OP-UA32 - Copper and Zinc Smelting/Brass and Bronze Production Attributes
- OP-UA33 - Metallic Mineral Processing Plant Attributes
- OP-UA34 - Pharmaceutical Manufacturing
- OP-UA35 - Incinerator Attributes
- OP-UA36 - Steel Plant Unit Attributes
- OP-UA37 - Basic Oxygen Process Furnace Unit Attributes
- OP-UA38 - Lead-Acid Battery Manufacturing Plant Attributes
- OP-UA39 - Sterilization Source Attributes
- OP-UA40 - Ferroalloy Production Facility Attributes
- OP-UA41 - Dry Cleaning Facility Attributes
- OP-UA42 - Phosphate Fertilizer Manufacturing Attributes
- OP-UA43 - Sulfuric Acid Production Attributes
- OP-UA44 - Municipal Solid Waste Landfill/Waste Disposal Site Attributes
- OP-UA45 - Surface Impoundment Attributes

OP-UA46 - Epoxy Resins and Non-Nylon Polyamides Production Attributes  
OP-UA47 - Ship Building and Ship Repair Unit Attributes  
OP-UA48 - Air Oxidation Unit Process Attributes  
OP-UA49 - Vacuum-Producing System Attributes  
OP-UA50 - Fluid Catalytic Cracking Unit Catalyst Regenerator/Fuel Gas Combustion Device/Claus Sulfur Recovery Plant Attributes  
OP-UA51 - Dryer/Kiln/Oven Attributes  
OP-UA52 - Closed Vent Systems and Control Devices  
OP-UA53 - Beryllium Processing Attributes  
OP-UA54 - Mercury Chlor-Alkali Cell Attributes  
OP-UA55 - Transfer System Attributes  
OP-UA56 - Vinyl Chloride Process Attributes  
OP-UA57 - Cleaning/Depainting Operation Attributes  
OP-UA58 - Treatment Process Attributes  
OP-UA59 - Coke By-Product Recovery Plant Attributes  
OP-UA60 - Chemical Manufacturing Process Unit Attributes  
OP-UA61 - Pulp, Paper, or Paperboard Producing Process Attributes  
OP-UA62 - Glycol Dehydration Unit Attributes  
OP-UA63 - Vegetable Oil Production Attributes