

FEDERAL OPERATING PERMIT

A FEDERAL OPERATING PERMIT IS HEREBY ISSUED TO
Intercontinental Terminals Company LLC

AUTHORIZING THE OPERATION OF
ITC Pasadena Terminal
Special Warehousing and Storage

LOCATED AT
Harris County, Texas
Latitude 29° 43' 24" Longitude 95° 9' 44"
Regulated Entity Number: RN106119175

This permit is issued in accordance with and subject to the Texas Clean Air Act (TCAA), Chapter 382 of the Texas Health and Safety Code and Title 30 Texas Administrative Code Chapter 122 (30 TAC Chapter 122), Federal Operating Permits. Under 30 TAC Chapter 122, this permit constitutes the permit holder's authority to operate the site and emission units listed in this permit. Operations of the site and emission units listed in this permit are subject to all additional rules or amended rules and orders of the Commission pursuant to the TCAA.

This permit does not relieve the permit holder from the responsibility of obtaining New Source Review authorization for new, modified, or existing facilities in accordance with 30 TAC Chapter 116, Control of Air Pollution by Permits for New Construction or Modification.

The site and emission units authorized by this permit shall be operated in accordance with 30 TAC Chapter 122, the general terms and conditions, special terms and conditions, and attachments contained herein.

This permit shall expire five years from the date of issuance. The renewal requirements specified in 30 TAC § 122.241 must be satisfied in order to renew the authorization to operate the site and emission units.

Permit No: 03785 Issuance Date: _____

For the Commission

Table of Contents

Section	Page
General Terms and Conditions	1
Special Terms and Conditions	1
Emission Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting	1
Additional Monitoring Requirements	15
New Source Review Authorization Requirements	16
Compliance Requirements.....	17
Risk Management Plan	18
Protection of Stratospheric Ozone.....	18
Temporary Fuel Shortages (30 TAC § 112.15)	19
Permit Location.....	19
Permit Shield (30 TAC § 122.148)	19
Attachments	20
Applicable Requirements Summary	21
Additional Monitoring Requirements	77
Permit Shield.....	87
New Source Review Authorization References.....	89
Appendix A	94
Acronym List	95

General Terms and Conditions

The permit holder shall comply with all terms and conditions contained in 30 TAC § 122.143 (General Terms and Conditions), 30 TAC § 122.144 (Recordkeeping Terms and Conditions), 30 TAC § 122.145 (Reporting Terms and Conditions), and 30 TAC § 122.146 (Compliance Certification Terms and Conditions).

In accordance with 30 TAC § 122.144(1), records of required monitoring data and support information required by this permit, or any applicable requirement codified in this permit, are required to be maintained for a period of five years from the date of the monitoring report, sample, or application unless a longer data retention period is specified in an applicable requirement. The five year record retention period supersedes any less stringent retention requirement that may be specified in a condition of a permit identified in the New Source Review Authorization attachment.

If the permit holder chooses to demonstrate that this permit is no longer required, a written request to void this permit shall be submitted to the Texas Commission on Environmental Quality (TCEQ) by the Responsible Official in accordance with 30 TAC § 122.161(e). The permit holder shall comply with the permit's requirements, including compliance certification and deviation reporting, until notified by the TCEQ that this permit is voided.

The permit holder shall comply with 30 TAC Chapter 116 by obtaining a New Source Review authorization prior to new construction or modification of emission units located in the area covered by this permit.

All reports required by this permit must include in the submittal a cover letter which identifies the following information: company name, TCEQ regulated entity number, air account number (if assigned), site name, area name (if applicable), and Air Permits Division permit number(s).

Special Terms and Conditions: Emission Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting

1. Permit holder shall comply with the following requirements:
 - A. Emission units (including groups and processes) in the Applicable Requirements Summary attachment shall meet the limitations, standards, equipment specifications, monitoring, recordkeeping, reporting, testing, and other requirements listed in the Applicable Requirements Summary attachment to assure compliance with the permit.
 - B. The textual description in the column titled "Textual Description" in the Applicable Requirements Summary attachment is not enforceable and is not deemed as a substitute for the actual regulatory language. The Textual Description is provided for information purposes only.

- C. A citation listed on the Applicable Requirements Summary attachment, which has a notation [G] listed before it, shall include the referenced section and subsection for all commission rules, or paragraphs for all federal and state regulations and all subordinate paragraphs, subparagraphs and clauses, subclauses, and items contained within the referenced citation as applicable requirements.
- D. When a grouped citation, notated with a [G] in the Applicable Requirements Summary, contains multiple compliance options, the permit holder must keep records of when each compliance option was used.
- E. Emission units subject to 40 CFR Part 63, Subpart ZZZZ as identified in the attached Applicable Requirements Summary table are subject to 30 TAC Chapter 113, Subchapter C, § 113.1090, which incorporates the 40 CFR Part 63 Subpart by reference.
- F. For the purpose of generating emission reduction credits through 30 TAC Chapter 101, Subchapter H, Division 1 (Emission Credit Banking and Trading), the permit holder shall comply with the following requirements:
 - (i) Title 30 TAC § 101.302 (relating to General Provisions)
 - (ii) Title 30 TAC § 101.303 (relating to Emission Reduction Credit Generation Certification)
 - (iii) Title 30 TAC § 101.304 (relating to Mobile Emission Reduction Credit Generation and Certification)
 - (iv) Title 30 TAC § 101.309 (relating to Emission Credit Banking and Trading)
 - (v) The terms and conditions by which the emission limits are established to generate the reduction credit are applicable requirements of this permit
- G. For the purpose of generating discrete emission reduction credits through 30 TAC Chapter 101, Subchapter H, Division 4 (Discrete Emission Credit Banking and Trading), the permit holder shall comply with the following requirements:
 - (i) Title 30 TAC § 101.372 (relating to General Provisions)
 - (ii) Title 30 TAC § 101.373 (relating to Discrete Emission Reduction Credit Generation and Certification)

- (iii) Title 30 TAC § 101.374 (relating to Mobile Discrete Emission Reduction Credit Generation and Certification)
 - (iv) Title 30 TAC § 101.378 (relating to Discrete Emission Credit Banking and Trading)
 - (v) The terms and conditions by which the emission limits are established to generate the discrete reduction credit are applicable requirements of this permit
- 2. The permit holder shall comply with the following sections of 30 TAC Chapter 101 (General Air Quality Rules):
 - A. Title 30 TAC § 101.1 (relating to Definitions), insofar as the terms defined in this section are used to define the terms used in other applicable requirements
 - B. Title 30 TAC § 101.3 (relating to Circumvention)
 - C. Title 30 TAC § 101.8 (relating to Sampling), if such action has been requested by the TCEQ
 - D. Title 30 TAC § 101.9 (relating to Sampling Ports), if such action has been requested by the TCEQ
 - E. Title 30 TAC § 101.10 (relating to Emissions Inventory Requirements)
 - F. Title 30 TAC § 101.201 (relating to Emission Event Reporting and Recordkeeping Requirements)
 - G. Title 30 TAC § 101.211 (relating to Scheduled Maintenance, Start-up, and Shutdown Reporting and Recordkeeping Requirements)
 - H. Title 30 TAC § 101.221 (relating to Operational Requirements)
 - I. Title 30 TAC § 101.222 (relating to Demonstrations)
 - J. Title 30 TAC § 101.223 (relating to Actions to Reduce Excessive Emissions)
- 3. Permit holder shall comply with the following requirements of 30 TAC Chapter 111:
 - A. Visible emissions from stationary vents with a flow rate of less than 100,000 actual cubic feet per minute and constructed after January 31, 1972 that are not listed in the Applicable Requirements Summary attachment for 30 TAC Chapter 111, Subchapter A, Division 1 , shall not exceed 20% opacity averaged over a six-minute period. The permit holder

shall comply with the following requirements for stationary vents at the site subject to this standard:

- (i) Title 30 TAC § 111.111(a)(1)(B) (relating to Requirements for Specified Sources)
- (ii) Title 30 TAC § 111.111(a)(1)(E)
- (iii) Title 30 TAC § 111.111(a)(1)(F)(i), (ii), (iii), or (iv)
- (iv) For emission units with vent emissions subject to 30 TAC § 111.111(a)(1)(B), complying with 30 TAC § 111.111(a)(1)(F)(ii), (iii), or (iv), and capable of producing visible emissions from, but not limited to, particulate matter, acid gases and NO_x, the permit holder shall also comply with the following periodic monitoring requirements for the purpose of annual compliance certification under 30 TAC § 122.146. These periodic monitoring requirements do not apply to vents that are not capable of producing visible emissions such as vents that emit only colorless VOCs; vents from non-fuming liquids; vents that provide passive ventilation, such as plumbing vents; or vent emissions from any other source that does not obstruct the transmission of light. Vents, as specified in the “Applicable Requirements Summary” attachment, that are subject to the emission limitation of 30 TAC § 111.111(a)(1)(B) are not subject to the following periodic monitoring requirements:
 - (1) An observation of stationary vents from emission units in operation shall be conducted at least once during each calendar quarter unless the emission unit is not operating for the entire quarter.
 - (2) For stationary vents from a combustion source, if an alternative to the normally fired fuel is fired for a period greater than or equal to 24 consecutive hours, the permit holder shall conduct an observation of the stationary vent for each such period to determine if visible emissions are present. If such period is greater than 3 months, observations shall be conducted once during each quarter. Supplementing the normally fired fuel with natural gas or fuel gas to increase the net heating value to the minimum required value does not constitute creation of an alternative fuel.
 - (3) Records of all observations shall be maintained.
 - (4) Visible emissions observations of emission units operated during daylight hours shall be conducted no earlier than one hour after sunrise and no later than one hour before sunset.

Visible emissions observations of emission units operated only at night must be made with additional lighting and the temporary installation of contrasting backgrounds. Visible emissions observations shall be made during times when the activities described in 30 TAC § 111.111(a)(1)(E) are not taking place. Visible emissions shall be determined with each stationary vent in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 mile, away from each stationary vent during the observation. For outdoor locations, the observer shall select a position where the sun is not directly in the observer's eyes. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. A certified opacity reader is not required for visible emissions observations.

(5) Compliance Certification:

- (a) If visible emissions are not present during the observation, the RO may certify that the source is in compliance with the applicable opacity requirement in 30 TAC § 111.111(a)(1) and (a)(1)(B).
- (b) However, if visible emissions are present during the observation, the permit holder shall either list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(1)(F) as soon as practicable, but no later than 24 hours after observing visible emissions to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.

- (c) Some vents may be subject to multiple visible emission or monitoring requirements. All credible data must be considered when certifying compliance with this requirement even if the observation or monitoring was performed to demonstrate compliance with a different requirement.
- B. For visible emissions from a building, enclosed facility, or other structure; the permit holder shall comply with the following requirements:
 - (i) Title 30 TAC § 111.111(a)(7)(A) (relating to Requirements for Specified Sources)
 - (ii) Title 30 TAC § 111.111(a)(7)(B)(i) or (ii)
 - (iii) For a building containing an air emission source, enclosed facility, or other structure containing or associated with an air emission source subject to 30 TAC § 111.111(a)(7)(A), complying with 30 TAC § 111.111(a)(7)(B)(i) or (ii), and capable of producing visible emissions from, but not limited to, particulate matter, acid gases and NO_x, the permit holder shall also comply with the following periodic monitoring requirements for the purpose of annual compliance certification under 30 TAC § 122.146:
 - (1) An observation of visible emissions from a building containing an air emission source, enclosed facility, or other structure containing or associated with an air emission source which is required to comply with 30 TAC § 111.111(a)(7)(A) shall be conducted at least once during each calendar quarter unless the air emission source or enclosed facility is not operating for the entire quarter.
 - (2) Records of all observations shall be maintained.
 - (3) Visible emissions observations of air emission sources or enclosed facilities operated during daylight hours shall be conducted no earlier than one hour after sunrise and no later than one hour before sunset. Visible emissions observations of air emission sources or enclosed facilities operated only at night must be made with additional lighting and the temporary installation of contrasting backgrounds. Visible emissions shall be determined with each emissions outlet in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 mile, away from each emissions outlet during the observation. For outdoor locations, the observer shall select a position where the sun is not directly in the observer's eyes. When condensed water vapor is present within the plume, as it emerges from the emissions

outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. A certified opacity reader is not required for visible emissions observations.

(4) Compliance Certification:

- (a) If visible emissions are not present during the observation, the RO may certify that the source is in compliance with the applicable opacity requirement in 30 TAC § 111.111(a)(7) and (a)(7)(A)
- (b) However, if visible emissions are present during the observation, the permit holder shall either list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(7)(B) as soon as practicable, but no later than 24 hours after observing visible emissions to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader

C. For visible emissions from all other sources not specified in 30 TAC § 111.111(a)(1), (4), or (7); the permit holder shall comply with the following requirements:

- (i) Title 30 TAC § 111.111(a)(8)(A) (relating to Requirements for Specified Sources)
- (ii) Title 30 TAC § 111.111(a)(8)(B)(i) or (ii)
- (iii) For a source subject to 30 TAC § 111.111(a)(8)(A), complying with 30 TAC § 111.111(a)(8)(B)(i) or (ii), and capable of producing visible emissions from, but not limited to, particulate matter, acid gases and NO_x, the permit holder shall also comply with the following

periodic monitoring requirements for the purpose of annual compliance certification under 30 TAC § 122.146:

- (1) An observation of visible emissions from a source which is required to comply with 30 TAC § 111.111(a)(8)(A) shall be conducted at least once during each calendar quarter unless the source is not operating for the entire quarter.
- (2) Records of all observations shall be maintained.
- (3) Visible emissions observations of sources operated during daylight hours shall be conducted no earlier than one hour after sunrise and no later than one hour before sunset. Visible emissions observations of sources operated only at night must be made with additional lighting and the temporary installation of contrasting backgrounds. Visible emissions shall be determined with each source in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 mile, away from each source during the observation. For outdoor locations, the observer shall select a position where the sun is not directly in the observer's eyes. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. A certified opacity reader is not required for visible emissions observations.
- (4) Compliance Certification:
 - (a) If visible emissions are not present during the observation, the RO may certify that the source is in compliance with the applicable opacity requirement in 30 TAC § 111.111(a)(8) and (a)(8)(A)
 - (b) However, if visible emissions are present during the observation, the permit holder shall either list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(8)(B) as soon as practicable, but no later than 24 hours after observing visible emissions to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in

compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.

- D. Certification of opacity readers determining opacities under Method 9 (as outlined in 40 CFR Part 60, Appendix A) to comply with opacity monitoring requirements shall be accomplished by completing the Visible Emissions Evaluators Course, or approved agency equivalent, no more than 180 days before the opacity reading.
- E. Permit holders for sites that have materials handling, construction, roads, streets, alleys, and parking lots shall comply with the following requirements:
 - (i) Title 30 TAC § 111.143 (relating to Materials Handling)
 - (ii) Title 30 TAC § 111.145 (relating to Construction and Demolition)
 - (iii) Title 30 TAC § 111.147 (relating to Roads, Streets, and Alleys)
 - (iv) Title 30 TAC § 111.149 (relating to Parking Lots)
- F. Emission limits on nonagricultural processes, except for the steam generators specified in 30 TAC § 111.153, shall comply with the following requirements:
 - (i) Emissions of PM from any source may not exceed the allowable rates as required in 30 TAC § 111.151(a) (relating to Allowable Emissions Limits)
 - (ii) Sources with an effective stack height (h_e) less than the standard effective stack height (H_e), must reduce the allowable emission level by multiplying it by $[h_e/H_e]^2$ as required in 30 TAC § 111.151(b)
 - (iii) Effective stack height shall be calculated by the equation specified in 30 TAC § 111.151(c)
- G. Outdoor burning, as stated in 30 TAC § 111.201, shall not be authorized unless the following requirements are satisfied:
 - (i) Title 30 TAC § 111.205 (relating to Exception for Fire Training)
 - (ii) Title 30 TAC § 111.221 (relating to Responsibility for Consequences of Outdoor Burning)

4. Permit holder shall comply with the following 30 TAC Chapter 115, Subchapter C requirements:
 - A. When filling stationary gasoline storage vessels (Stage I) for motor vehicle fuel dispensing facilities specified in 30 TAC Chapter 115, Subchapter C, the permit holder shall comply with the following requirements:
 - (i) Title 30 TAC § 115.221 (relating to Emission Specifications)
 - (ii) Title 30 TAC § 115.222 (relating to Control Requirements)
 - (iii) Title 30 TAC § 115.223 (relating to Alternate Control Requirements)
 - (iv) Title 30 TAC § 115.224 (relating to Inspection Requirements)
 - (v) Title 30 TAC § 115.225 (relating to Testing Requirements)
 - (vi) Title 30 TAC § 115.226 (relating to Recordkeeping Requirements)
5. The permit holder shall comply with the following requirements of 30 TAC Chapter 115, Subchapter F, Division 3, Degassing of Storage Tanks, Transport Vessels and Marine Vessels:
 - A. For degassing of stationary VOC storage tanks, the permit holder shall comply with the following requirements:
 - (i) Title 30 TAC § 115.541(a) - (c) (relating to Emission Specifications)
 - (ii) Title 30 TAC § 115.541(f) (relating to Emission Specifications), for floating roof storage tanks
 - (iii) Title 30 TAC § 115.542(a) and (a)(1), (a)(2), (a)(3) or (a)(4) (relating to Control Requirements). Where the requirements of 30 TAC Chapter 115, Subchapter F contain multiple compliance options, the permit holder shall keep records of when each compliance option was used.
 - (iv) Title 30 TAC § 115.542(b) - (d), (relating to Control Requirements)
 - (v) Title 30 TAC § 115.543 (relating to Alternate Control Requirements)
 - (vi) Title 30 TAC § 115.544(a)(1) and (a)(2) (relating to Inspection, Monitoring, and Testing Requirements), for inspections
 - (vii) Title 30 TAC § 115.544(b) (relating to Inspection, Monitoring, and Testing Requirements), for monitoring

- (viii) Title 30 TAC § 115.544(b)(1) and (b)(2) (relating to Inspection, Monitoring, and Testing Requirements), for monitoring of control devices
- (ix) Title 30 TAC § 115.544(b)(2)(A) - (J) (relating to Inspection, Monitoring, and Testing Requirements), for monitoring (as appropriate to the control device)
- (x) Title 30 TAC § 115.544(b)(3), (b)(4) and (b)(6) (relating to Inspection, Monitoring, and Testing Requirements), for VOC concentration or lower explosive limit threshold monitoring
- (xi) Title 30 TAC § 115.544(c), and (c)(1) - (c)(3) (relating to Inspection, Monitoring, and Testing Requirements), for testing of control devices used to comply with 30 TAC § 115.542(a)(1)
- (xii) Title 30 TAC § 115.545(1) - (7), (9) - (11) and (13) (relating to Approved Test Methods)
- (xiii) Title 30 TAC § 115.546(a), (a)(1) and (a)(3) (relating to Recordkeeping and Notification Requirements), for recordkeeping
- (xiv) Title 30 TAC § 115.546(a)(2) and (a)(2)(A) - (J) (relating to Recordkeeping and Notification Requirements), for recordkeeping (as appropriate to the control device)
- (xv) Title 30 TAC § 115.546(a)(4) (relating to Recordkeeping and Notification Requirements), for recordkeeping of testing of control devices used to comply with 30 TAC § 115.542(a)(1)
- (xvi) Title 30 TAC § 115.546(b) (relating to Recordkeeping and Notification Requirements), for notification
- (xvii) Title 30 TAC § 115.547(4) (relating to Exemptions)

6. The permit holder shall comply with the following requirements of 30 TAC Chapter 117:

- A. For boilers, process heaters, and stationary reciprocating engines exempt from Subchapter D, Division 1 at minor sources of NO_x under 30 TAC § 117.2003(a), the permit holder shall comply with 30 TAC §§ 117.2030(c), 117.2035(g), 117.2045(b) and 117.2045(c).

7. The permit holder shall comply with the following requirements for units subject to any subpart of 40 CFR Part 60, unless otherwise stated in the applicable subpart:

- A. Title 40 CFR § 60.7 (relating to Notification and Recordkeeping)

- B. Title 40 CFR § 60.8 (relating to Performance Tests)
 - C. Title 40 CFR § 60.11 (relating to Compliance with Standards and Maintenance Requirements)
 - D. Title 40 CFR § 60.12 (relating to Circumvention)
 - E. Title 40 CFR § 60.13 (relating to Monitoring Requirements)
 - F. Title 40 CFR § 60.14 (relating to Modification)
 - G. Title 40 CFR § 60.15 (relating to Reconstruction)
 - H. Title 40 CFR § 60.19 (relating to General Notification and Reporting Requirements)
8. For the bulk gasoline terminals specified in 40 CFR Part 60, Subpart XX, the permit holder shall comply with the following requirements:
- A. Title 40 CFR § 60.502(e) - (f) (relating to Standard for VOC Emissions from Bulk Gasoline Terminals)
 - B. Title 40 CFR § 60.505(a) - (b), and (d) (relating to Reporting and Recordkeeping)
9. The permit holder shall comply with the following requirements for units subject to any subpart of 40 CFR Part 61, unless otherwise stated in the applicable subpart:
- A. Title 40 CFR § 61.05 (relating to Prohibited Activities)
 - B. Title 40 CFR § 61.07 (relating to Application for Approval of Construction or Modification)
 - C. Title 40 CFR § 61.09 (relating to Notification of Start-up)
 - D. Title 40 CFR § 61.10 (relating to Source Reporting and Request Waiver)
 - E. Title 40 CFR § 61.12 (relating to Compliance with Standards and Maintenance Requirements)
 - F. Title 40 CFR § 61.13 (relating to Emissions Tests and Waiver of Emission Tests)
 - G. Title 40 CFR § 61.14 (relating to Monitoring Requirements)
 - H. Title 40 CFR § 61.15 (relating to Modification)
 - I. Title 40 CFR § 61.19 (relating to Circumvention)

10. For the benzene transfer operations to and from railcars and tank trucks specified in 40 CFR Part 61, Subpart BB, the permit holder shall comply with the following requirements:
 - A. Title 40 CFR § 61.302(d) (relating to Standards)
 - B. Title 40 CFR § 61.305(g) - (h) (relating to Reporting and Recordkeeping)
11. For the benzene transfer operations to and from marine vessels specified in 40 CFR Part 61, Subpart BB, the permit holder shall comply with the following requirements:
 - A. Title 40 CFR § 61.302(e) (relating to Standards)
 - B. Title 40 CFR § 61.303(f) (relating to Monitoring Requirements)
 - C. Title 40 CFR § 61.304(f) (relating to Test Methods and Procedures)
 - D. Title 40 CFR § 61.305(g) - (h) (relating to Reporting and Recordkeeping)
12. The permit holder shall comply with the requirements of 30 TAC Chapter 113, Subchapter C, § 113.100 for units subject to any subpart of 40 CFR Part 63, unless otherwise stated in the applicable subpart.
13. For the bulk gasoline terminals specified in 40 CFR Part 63, Subpart R, the permit holder shall comply with 40 CFR § 63.420(a)(2) (Title 30 TAC Chapter 113, Subchapter C, § 113.230 incorporated by reference).
14. For the pipeline breakout station specified in 40 CFR Part 63, Subpart R, the permit holder shall comply with 40 CFR § 63.420(b)(2) (Title 30 TAC Chapter 113, Subchapter C, § 113.230 incorporated by reference).
15. For each bulk gasoline terminal specified in 40 CFR Part 63, Subpart BBBBBB, the permit holder shall comply with the following requirements (Title 30 TAC, Subchapter C, § 113.1370 incorporated by reference):
 - A. Title 40 CFR § 60.502(e) - (f), as required by Title 40 CFR § 63.11088(a)
 - B. Title 40 CFR § 63.11085(a), for operation and maintenance of the affected source
 - C. Title 40 CFR § 63.11089(a), for leak inspections at the facility
 - D. Title 40 CFR § 63.11089(b) and (c), for log book maintenance and recordkeeping
 - E. Title 40 CFR § 63.11089(d), for delay of repair

- F. Title 40 CFR § 63.11092(f) and (f)(1), for annual certification of gasoline cargo tanks
 - G. Title 40 CFR § 63.11093(a), for Initial Notification
 - H. Title 40 CFR § 63.11093(b), for Notification of Compliance Status
 - I. Title 40 CFR § 63.11094(d), for recordkeeping
 - J. Title 40 CFR § 63.11094(e), for recordkeeping
 - K. Title 40 CFR § 63.11094(g), for recordkeeping
 - L. Title 40 CFR § 63.11095(a), (a)(3), (b), (b)(5) and (d), for reporting
16. For each pipeline breakout station specified in 40 CFR Part 63, Subpart BBBBBB, the permit holder shall comply with the following requirements (Title 30 TAC, Subchapter C, § 113.1370 incorporated by reference):
- A. Title 40 CFR § 63.11085(a), for operation and maintenance of the affected source
 - B. Title 40 CFR § 63.11089(a), for leak inspections at the facility
 - C. Title 40 CFR § 63.11089(b) and (c), for log book maintenance and recordkeeping
 - D. Title 40 CFR § 63.11089(d), for delay of repair
 - E. Title 40 CFR § 63.11093(a), for Initial Notification
 - F. Title 40 CFR § 63.11093(b), for Notification of Compliance Status
 - G. Title 40 CFR § 63.11094(d), for recordkeeping
 - H. Title 40 CFR § 63.11094(e), for recordkeeping
 - I. Title 40 CFR § 63.11094(g), for recordkeeping
 - J. Title 40 CFR § 63.11095(a), (a)(3), (b), (b)(5) and (d), for reporting
17. For each gasoline dispensing facility, with a throughput of less than 10,000 gallons per month as specified in 40 CFR Part 63, Subpart CCCCCC, the permit holder shall comply with the following requirements (Title 30 TAC, Subchapter C, § 113.1380 incorporated by reference):
- A. Title 40 CFR § 63.11111(e), for records of monthly throughput
 - B. Title 40 CFR § 63.11111(i), for compliance due to increase of throughput

- C. Title 40 CFR § 63.11113(c), for compliance due to increase of throughput
- D. Title 40 CFR § 63.11115(a), for operation of the source
- E. Title 40 CFR § 63.11116(a) and (a)(1) - (4), for work practices
- F. Title 40 CFR § 63.11116(b), for records availability
- G. Title 40 CFR § 63.11116(d), for portable gasoline containers

Additional Monitoring Requirements

- 18. Unless otherwise specified, the permit holder shall comply with the compliance assurance monitoring requirements as specified in the attached “CAM Summary” upon issuance of the permit. In addition, the permit holder shall comply with the following:
 - A. The permit holder shall comply with the terms and conditions contained in 30 TAC § 122.147 (General Terms and Conditions for Compliance Assurance Monitoring).
 - B. The permit holder shall report, consistent with the averaging time identified in the “CAM Summary,” deviations as defined by the deviation limit in the “CAM Summary.” Any monitoring data below a minimum limit or above a maximum limit, that is collected in accordance with the requirements specified in 40 CFR § 64.7(c), shall be reported as a deviation. Deviations shall be reported according to 30 TAC § 122.145 (Reporting Terms and Conditions).
 - C. The permit holder may elect to collect monitoring data on a more frequent basis and average the data, consistent with the averaging time specified in the “CAM Summary,” for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis. In no event shall data be collected and used in particular instances in order to avoid reporting deviations. All monitoring data shall be collected in accordance with the requirements specified in 40 CFR § 64.7(c).
 - D. The permit holder shall operate the monitoring, identified in the attached “CAM Summary,” in accordance with the provisions of 40 CFR § 64.7.
 - E. The permit holder shall comply with either of the following requirements for any capture system associated with the VOC control device subject to CAM. If the results of the following inspections indicate that the capture system is not working properly, the permit holder shall promptly take necessary corrective actions:

- (i) Once a year the permit holder shall inspect the capture system in compliance of CAM for leaks in accordance with 40 CFR Part 60, Appendix A, Test Method 21. Leaks shall be indicated by an instrument reading greater than or equal to 500 ppm above background or as defined by the underlying applicable requirement; or
 - (ii) Once a month, the permit holder shall conduct a visual, audible, and/or olfactory inspection of the capture system in compliance of CAM to detect leaking components.
- F. The permit holder shall comply with the requirements of 40 CFR § 70.6(a)(3)(ii)(A) and 30 TAC § 122.144(1)(A)-(F) for documentation of all required inspections.

New Source Review Authorization Requirements

- 19. Permit holder shall comply with the requirements of New Source Review authorizations issued or claimed by the permit holder for the permitted area, including permits, permits by rule, standard permits, flexible permits, special permits, permits for existing facilities including Voluntary Emissions Reduction Permits and Electric Generating Facility Permits issued under 30 TAC Chapter 116, Subchapter I, or special exemptions referenced in the New Source Review Authorization References attachment. These requirements:
 - A. Are incorporated by reference into this permit as applicable requirements
 - B. Shall be located with this operating permit
 - C. Are not eligible for a permit shield
- 20. The permit holder shall comply with the general requirements of 30 TAC Chapter 106, Subchapter A or the general requirements, if any, in effect at the time of the claim of any PBR.
- 21. The permit holder shall maintain records to demonstrate compliance with any emission limitation or standard that is specified in a permit by rule (PBR) or Standard Permit listed in the New Source Review Authorizations attachment. The records shall yield reliable data from the relevant time period that are representative of the emission unit's compliance with the PBR or Standard Permit. These records may include, but are not limited to, production capacity and throughput, hours of operation, safety data sheets (SDS), chemical composition of raw materials, speciation of air contaminant data, engineering calculations, maintenance records, fugitive data, performance tests, capture/control device efficiencies, direct pollutant monitoring (CEMS, COMS, or PEMS), or control device parametric monitoring. These records shall be made readily accessible and available as required by 30 TAC § 122.144. Any monitoring or recordkeeping data indicating noncompliance with the PBR or Standard

Permit shall be considered and reported as a deviation according to 30 TAC § 122.145 (Reporting Terms and Conditions).

Compliance Requirements

22. The permit holder shall certify compliance in accordance with 30 TAC § 122.146. The permit holder shall comply with 30 TAC § 122.146 using at a minimum, but not limited to, the continuous or intermittent compliance method data from monitoring, recordkeeping, reporting, or testing required by the permit and any other credible evidence or information. The certification period may not exceed 12 months and the certification must be submitted within 30 days after the end of the period being certified.
23. Use of Emission Credits to comply with applicable requirements:
 - A. Unless otherwise prohibited, the permit holder may use emission credits to comply with the following applicable requirements listed elsewhere in this permit:
 - (i) Title 30 TAC Chapter 115
 - (ii) Title 30 TAC Chapter 117
 - (iii) Offsets for Title 30 TAC Chapter 116
 - B. The permit holder shall comply with the following requirements in order to use the emission credits to comply with the applicable requirements:
 - (i) The permit holder must notify the TCEQ according to 30 TAC § 101.306(c)(2)
 - (ii) The emission credits to be used must meet all the geographic, timeliness, applicable pollutant type, and availability requirements listed in 30 TAC Chapter 101, Subchapter H, Division 1
 - (iii) The executive director has approved the use of the credit according to 30 TAC § 101.306(c)(2)
 - (iv) The permit holder keeps records of the use of credits towards compliance with the applicable requirements in accordance with 30 TAC § 101.302(g) and 30 TAC Chapter 122
 - (v) Title 30 TAC § 101.305 (relating to Emission Reductions Achieved Outside the United States)
24. Use of Discrete Emission Credits to comply with the applicable requirements:

- A. Unless otherwise prohibited, the permit holder may use discrete emission credits to comply with the following applicable requirements listed elsewhere in this permit:
 - (i) Title 30 TAC Chapter 115
 - (ii) Title 30 TAC Chapter 117
 - (iii) If applicable, offsets for Title 30 TAC Chapter 116
 - (iv) Temporarily exceed state NSR permit allowables

- B. The permit holder shall comply with the following requirements in order to use the credit to comply with the applicable requirements:
 - (i) The permit holder must notify the TCEQ according to 30 TAC § 101.376(d)
 - (ii) The discrete emission credits to be used must meet all the geographic, timeliness, applicable pollutant type, and availability requirements listed in 30 TAC Chapter 101, Subchapter H, Division 4
 - (iii) The executive director has approved the use of the discrete emission credits according to 30 TAC § 101.376(d)(1)(A)
 - (iv) The permit holder keeps records of the use of credits towards compliance with the applicable requirements in accordance with 30 TAC § 101.372(h) and 30 TAC Chapter 122
 - (v) Title 30 TAC § 101.375 (relating to Emission Reductions Achieved Outside the United States)

Risk Management Plan

- 25. For processes subject to 40 CFR Part 68 and specified in 40 CFR § 68.10, the permit holder shall comply with the requirements of the Accidental Release Prevention Provisions in 40 CFR Part 68. The permit holder shall submit to the appropriate agency either a compliance schedule for meeting the requirements of 40 CFR Part 68 by the date provided in 40 CFR § 68.10(a), or as part of the compliance certification submitted under this permit, a certification statement that the source is in compliance with all requirements of 40 CFR Part 68, including the registration and submission of a risk management plan.

Protection of Stratospheric Ozone

- 26. Permit holders at a site subject to Title VI of the FCAA Amendments shall meet the following requirements for protection of stratospheric ozone:

- A. Any on site servicing, maintenance, and repair on refrigeration and nonmotor vehicle air-conditioning appliances using ozone-depleting refrigerants or non-exempt substitutes shall be conducted in accordance with 40 CFR Part 82, Subpart F. Permit holders shall ensure that repairs on or refrigerant removal from refrigeration and nonmotor vehicle air-conditioning appliances using ozone-depleting refrigerants are performed only by properly certified technicians using certified equipment. Records shall be maintained as required by 40 CFR Part 82, Subpart F.

Temporary Fuel Shortages (30 TAC § 112.15)

- 27. The permit holder shall comply with the following 30 TAC Chapter 112 requirements:
 - A. Title 30 TAC § 112.15 (relating to Temporary Fuel Shortage Plan Filing Requirements)
 - B. Title 30 TAC § 112.16(a), (a)(1), and (a)(2)(B) - (C) (relating to Temporary Fuel Shortage Plan Operating Requirements)
 - C. Title 30 TAC § 112.17 (relating to Temporary Fuel Shortage Plan Notification Procedures)
 - D. Title 30 TAC § 112.18 (relating to Temporary Fuel Shortage Plan Reporting Requirements)

Permit Location

- 28. The permit holder shall maintain a copy of this permit and records related to requirements listed in this permit on site.

Permit Shield (30 TAC § 122.148)

- 29. A permit shield is granted for the emission units, groups, or processes specified in the attached "Permit Shield." Compliance with the conditions of the permit shall be deemed compliance with the specified potentially applicable requirements or specified potentially applicable state-only requirements listed in the attachment "Permit Shield." Permit shield provisions shall not be modified by the executive director until notification is provided to the permit holder. No later than 90 days after notification of a change in a determination made by the executive director, the permit holder shall apply for the appropriate permit revision to reflect the new determination. Provisional terms are not eligible for this permit shield. Any term or condition, under a permit shield, shall not be protected by the permit shield if it is replaced by a provisional term or condition on the basis of the term and condition changes.

Attachments

Applicable Requirements Summary

Additional Monitoring Requirements

Permit Shield

New Source Review Authorization References

Applicable Requirements Summary

Unit Summary 22

Applicable Requirements Summary 47

Note: A “none” entry may be noted for some emission sources in this permit’s “Applicable Requirements Summary” under the heading of “Monitoring and Testing Requirements” and/or “Recordkeeping Requirements” and/or “Reporting Requirements.” Such a notation indicates that there are no requirements for the indicated emission source as identified under the respective column heading(s) for the stated portion of the regulation when the emission source is operating under the conditions of the specified SOP Index Number. However, other relevant requirements pursuant to 30 TAC Chapter 122 including Recordkeeping Terms and Conditions (30 TAC § 122.144), Reporting Terms and Conditions (30 TAC § 122.145), and Compliance Certification Terms and Conditions (30 TAC § 122.146) continue to apply.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
EFWP-1	SRIC ENGINES	N/A	60III-1	40 CFR Part 60, Subpart III	No changing attributes.
EFWP-1	SRIC ENGINES	N/A	63ZZZZ-1	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
EFWP-2	SRIC ENGINES	N/A	60III-1	40 CFR Part 60, Subpart III	No changing attributes.
EFWP-2	SRIC ENGINES	N/A	63ZZZZ-1	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
EFWP-3	SRIC ENGINES	N/A	60III-1	40 CFR Part 60, Subpart III	No changing attributes.
EFWP-3	SRIC ENGINES	N/A	63ZZZZ-2	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
EGEN-1	SRIC ENGINES	N/A	60JJJJ-1	40 CFR Part 60, Subpart JJJJ	No changing attributes.
EGEN-1	SRIC ENGINES	N/A	63ZZZZ-3	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
EGEN-2	SRIC ENGINES	N/A	60JJJJ-2	40 CFR Part 60, Subpart JJJJ	No changing attributes.
EGEN-2	SRIC ENGINES	N/A	63ZZZZ-4	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
EGEN-3	SRIC ENGINES	N/A	60JJJJ-2	40 CFR Part 60, Subpart JJJJ	No changing attributes.
EGEN-3	SRIC ENGINES	N/A	63ZZZZ-4	40 CFR Part 63, Subpart ZZZZ	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
FL-001	FLARES	N/A	60A-1	40 CFR Part 60, Subpart A	No changing attributes.
FUG	FUGITIVE EMISSION UNITS	N/A	61J-ALL	40 CFR Part 61, Subpart J	No changing attributes.
FUG	FUGITIVE EMISSION UNITS	N/A	61V-ALL	40 CFR Part 61, Subpart V	No changing attributes.
GRP1&2	STORAGE TANKS/VESSELS	P100-001, P100-002, P100-003, P100-004, P100-005, P100-006, P100-007, P100-008, P100-009, P12-002, P12-003, P165-003, P165-004, P165-005, P165-006	R5112-1	30 TAC Chapter 115, Storage of VOCs	Product Stored = VOC other than crude oil or condensate, Storage Capacity = Capacity is greater than 40,000 gallons, True Vapor Pressure = True vapor pressure is less than 1.0 psia
GRP1&2	STORAGE TANKS/VESSELS	P100-001, P100-002, P100-003, P100-004, P100-005, P100-006, P100-007, P100-008, P100-009, P12-002, P12-003, P165-003, P165-004, P165-005, P165-006	R5112-2	30 TAC Chapter 115, Storage of VOCs	Product Stored = VOC other than crude oil or condensate, Storage Capacity = Capacity is greater than 40,000 gallons, True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia
GRP1&2	STORAGE TANKS/VESSELS	P100-001, P100-002, P100-003,	R5112-3	30 TAC Chapter 115, Storage of VOCs	Product Stored = VOC other than crude oil or condensate, Storage

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
		P100-004, P100-005, P100-006, P100-007, P100-008, P100-009, P12-002, P12-003, P165-003, P165-004, P165-005, P165-006			Capacity = Capacity is greater than 40,000 gallons, True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia
GRP1&2	STORAGE TANKS/VESSELS	P100-001, P100-002, P100-003, P100-004, P100-005, P100-006, P100-007, P100-008, P100-009, P12-002, P12-003, P165-003, P165-004, P165-005, P165-006	R5112-4	30 TAC Chapter 115, Storage of VOCs	Product Stored = Crude oil and/or condensate, Storage Capacity = Capacity is greater than 40,000 gallons, True Vapor Pressure = True vapor pressure is less than 1.0 psia
GRP1&2	STORAGE TANKS/VESSELS	P100-001, P100-002, P100-003, P100-004, P100-005, P100-006, P100-007, P100-008, P100-009, P12-002, P12-003, P165-003, P165-004, P165-005, P165-006	R5112-5	30 TAC Chapter 115, Storage of VOCs	Product Stored = Crude oil and/or condensate, Storage Capacity = Capacity is greater than 40,000 gallons, True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia
GRP1&2	STORAGE TANKS/VESSELS	P100-001, P100-002, P100-003,	R5112-6	30 TAC Chapter 115, Storage of VOCs	Product Stored = Crude oil and/or condensate, Storage

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
		P100-004, P100-005, P100-006, P100-007, P100-008, P100-009, P12-002, P12-003, P165-003, P165-004, P165-005, P165-006			Capacity = Capacity is greater than 40,000 gallons, True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia
GRP1&2	STORAGE TANKS/VESSELS	P100-001, P100-002, P100-003, P100-004, P100-005, P100-006, P100-007, P100-008, P100-009, P12-002, P12-003, P165-003, P165-004, P165-005, P165-006	60Kb-10	40 CFR Part 60, Subpart Kb	Product Stored = Crude oil stored, processed, and/or treated after custody transfer, Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia, Reid Vapor Pressure = Reid vapor pressure is greater than or equal to 2.0 psia
GRP1&2	STORAGE TANKS/VESSELS	P100-001, P100-002, P100-003, P100-004, P100-005, P100-006, P100-007, P100-008, P100-009, P12-002, P12-003, P165-003, P165-004, P165-005, P165-006	60Kb-2	40 CFR Part 60, Subpart Kb	Product Stored = Volatile organic liquid, Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.5 psia but less than 0.75 psia
GRP1&2	STORAGE TANKS/VESSELS	P100-001, P100-002, P100-003,	60Kb-3	40 CFR Part 60, Subpart Kb	Product Stored = Volatile organic liquid, Maximum True Vapor

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
		P100-004, P100-005, P100-006, P100-007, P100-008, P100-009, P12-002, P12-003, P165-003, P165-004, P165-005, P165-006			Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia
GRP1&2	STORAGE TANKS/VESSELS	P100-001, P100-002, P100-003, P100-004, P100-005, P100-006, P100-007, P100-008, P100-009, P12-002, P12-003, P165-003, P165-004, P165-005, P165-006	60Kb-5	40 CFR Part 60, Subpart Kb	Product Stored = Petroleum liquid (other than petroleum or condensate), Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.5 psia but less than 0.75 psia
GRP1&2	STORAGE TANKS/VESSELS	P100-001, P100-002, P100-003, P100-004, P100-005, P100-006, P100-007, P100-008, P100-009, P12-002, P12-003, P165-003, P165-004, P165-005, P165-006	60Kb-6	40 CFR Part 60, Subpart Kb	Product Stored = Petroleum liquid (other than petroleum or condensate), Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia
GRP1&2	STORAGE TANKS/VESSELS	P100-001, P100-002, P100-003,	60Kb-8	40 CFR Part 60, Subpart Kb	Product Stored = Petroleum (other than crude oil) or

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
		P100-004, P100-005, P100-006, P100-007, P100-008, P100-009, P12-002, P12-003, P165-003, P165-004, P165-005, P165-006			condensate stored, processed, and/or treated after custody transfer, Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.5 psia but less than 0.75 psia
GRP1&2	STORAGE TANKS/VESSELS	P100-001, P100-002, P100-003, P100-004, P100-005, P100-006, P100-007, P100-008, P100-009, P12-002, P12-003, P165-003, P165-004, P165-005, P165-006	60Kb-9	40 CFR Part 60, Subpart Kb	Product Stored = Petroleum (other than crude oil) or condensate stored, processed, and/or treated after custody transfer, Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia
GRP1&2	STORAGE TANKS/VESSELS	P100-001, P100-002, P100-003, P100-004, P100-005, P100-006, P100-007, P100-008, P100-009, P12-002, P12-003, P165-003, P165-004, P165-005, P165-006	61Y-1	40 CFR Part 61, Subpart Y	No changing attributes.
GRP1&2&WW	STORAGE TANKS/VESSELS	P12-001, P80-001	R5112-1	30 TAC Chapter 115, Storage of VOCs	Product Stored = VOC other than crude oil or condensate, Storage

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					Capacity = Capacity is greater than 40,000 gallons, True Vapor Pressure = True vapor pressure is less than 1.0 psia
GRP1&2&WW	STORAGE TANKS/VESSELS	P12-001, P80-001	R5112-2	30 TAC Chapter 115, Storage of VOCs	Product Stored = VOC other than crude oil or condensate, Storage Capacity = Capacity is greater than 40,000 gallons, True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia
GRP1&2&WW	STORAGE TANKS/VESSELS	P12-001, P80-001	R5112-3	30 TAC Chapter 115, Storage of VOCs	Product Stored = VOC other than crude oil or condensate, Storage Capacity = Capacity is greater than 40,000 gallons, True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia
GRP1&2&WW	STORAGE TANKS/VESSELS	P12-001, P80-001	R5112-4	30 TAC Chapter 115, Storage of VOCs	Product Stored = Crude oil and/or condensate, Storage Capacity = Capacity is greater than 40,000 gallons, True Vapor Pressure = True vapor pressure is less than 1.0 psia
GRP1&2&WW	STORAGE TANKS/VESSELS	P12-001, P80-001	R5112-5	30 TAC Chapter 115, Storage of VOCs	Product Stored = Crude oil and/or condensate, Storage Capacity = Capacity is greater than 40,000 gallons, True Vapor Pressure = True vapor pressure

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					is greater than or equal to 1.0 psia but less than 1.5 psia
GRP1&2&WW	STORAGE TANKS/VESSELS	P12-001, P80-001	R5112-6	30 TAC Chapter 115, Storage of VOCs	Product Stored = Crude oil and/or condensate, Storage Capacity = Capacity is greater than 40,000 gallons, True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia
GRP1&2&WW	STORAGE TANKS/VESSELS	P12-001, P80-001	60Kb-10	40 CFR Part 60, Subpart Kb	Product Stored = Crude oil stored, processed, and/or treated after custody transfer, Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia, Reid Vapor Pressure = Reid vapor pressure is greater than or equal to 2.0 psia
GRP1&2&WW	STORAGE TANKS/VESSELS	P12-001, P80-001	60Kb-12	40 CFR Part 60, Subpart Kb	Product Stored = Waste mixture of indeterminate or variable composition, Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.5 psia but less than 0.75 psia
GRP1&2&WW	STORAGE TANKS/VESSELS	P12-001, P80-001	60Kb-13	40 CFR Part 60, Subpart Kb	Product Stored = Waste mixture of indeterminate or variable composition, Maximum True Vapor Pressure = True vapor pressure is greater than or equal

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					to 0.75 psia but less than 11.1 psia
GRP1&2&WW	STORAGE TANKS/VESSELS	P12-001, P80-001	60Kb-2	40 CFR Part 60, Subpart Kb	Product Stored = Volatile organic liquid, Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.5 psia but less than 0.75 psia
GRP1&2&WW	STORAGE TANKS/VESSELS	P12-001, P80-001	60Kb-3	40 CFR Part 60, Subpart Kb	Product Stored = Volatile organic liquid, Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia
GRP1&2&WW	STORAGE TANKS/VESSELS	P12-001, P80-001	60Kb-5	40 CFR Part 60, Subpart Kb	Product Stored = Petroleum liquid (other than petroleum or condensate), Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.5 psia but less than 0.75 psia
GRP1&2&WW	STORAGE TANKS/VESSELS	P12-001, P80-001	60Kb-6	40 CFR Part 60, Subpart Kb	Product Stored = Petroleum liquid (other than petroleum or condensate), Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia
GRP1&2&WW	STORAGE TANKS/VESSELS	P12-001, P80-001	60Kb-8	40 CFR Part 60, Subpart Kb	Product Stored = Petroleum (other than crude oil) or condensate stored, processed,

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					and/or treated after custody transfer, Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.5 psia but less than 0.75 psia
GRP1&2&WW	STORAGE TANKS/VESSELS	P12-001, P80-001	60Kb-9	40 CFR Part 60, Subpart Kb	Product Stored = Petroleum (other than crude oil) or condensate stored, processed, and/or treated after custody transfer, Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia
GRP1&2&WW	STORAGE TANKS/VESSELS	P12-001, P80-001	61Y-1	40 CFR Part 61, Subpart Y	No changing attributes.
GRP2&3	STORAGE TANKS/VESSELS	P100-12, P100-13, P110-001, P110-002, P110-004, P120-001, P120-002, P120-003, P120-004, P165-001, P165-002	R5112-1	30 TAC Chapter 115, Storage of VOCs	Product Stored = VOC other than crude oil or condensate, Storage Capacity = Capacity is greater than 40,000 gallons, True Vapor Pressure = True vapor pressure is less than 1.0 psia
GRP2&3	STORAGE TANKS/VESSELS	P100-12, P100-13, P110-001, P110-002, P110-004, P120-001, P120-002, P120-003, P120-004, P165-001, P165-002	R5112-2	30 TAC Chapter 115, Storage of VOCs	Product Stored = VOC other than crude oil or condensate, Storage Capacity = Capacity is greater than 40,000 gallons, True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
GRP2&3	STORAGE TANKS/VESSELS	P100-12, P100-13, P110-001, P110- 002, P110-004, P120-001, P120- 002, P120-003, P120-004, P165- 001, P165-002	R5112-3	30 TAC Chapter 115, Storage of VOCs	Product Stored = VOC other than crude oil or condensate, Storage Capacity = Capacity is greater than 40,000 gallons, True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia
GRP2&3	STORAGE TANKS/VESSELS	P100-12, P100-13, P110-001, P110- 002, P110-004, P120-001, P120- 002, P120-003, P120-004, P165- 001, P165-002	R5112-4	30 TAC Chapter 115, Storage of VOCs	Product Stored = Crude oil and/or condensate, Storage Capacity = Capacity is greater than 40,000 gallons, True Vapor Pressure = True vapor pressure is less than 1.0 psia
GRP2&3	STORAGE TANKS/VESSELS	P100-12, P100-13, P110-001, P110- 002, P110-004, P120-001, P120- 002, P120-003, P120-004, P165- 001, P165-002	R5112-5	30 TAC Chapter 115, Storage of VOCs	Product Stored = Crude oil and/or condensate, Storage Capacity = Capacity is greater than 40,000 gallons, True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia
GRP2&3	STORAGE TANKS/VESSELS	P100-12, P100-13, P110-001, P110- 002, P110-004, P120-001, P120- 002, P120-003, P120-004, P165- 001, P165-002	R5112-6	30 TAC Chapter 115, Storage of VOCs	Product Stored = Crude oil and/or condensate, Storage Capacity = Capacity is greater than 40,000 gallons, True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia
GRP2&3	STORAGE	P100-12, P100-13,	60Kb-2	40 CFR Part 60, Subpart	Product Stored = Volatile organic

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	TANKS/VESSELS	P110-001, P110-002, P110-004, P120-001, P120-002, P120-003, P120-004, P165-001, P165-002		Kb	liquid, Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.5 psia but less than 0.75 psia
GRP2&3	STORAGE TANKS/VESSELS	P100-12, P100-13, P110-001, P110-002, P110-004, P120-001, P120-002, P120-003, P120-004, P165-001, P165-002	60Kb-3	40 CFR Part 60, Subpart Kb	Product Stored = Volatile organic liquid, Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia
GRP2&3	STORAGE TANKS/VESSELS	P100-12, P100-13, P110-001, P110-002, P110-004, P120-001, P120-002, P120-003, P120-004, P165-001, P165-002	60Kb-5	40 CFR Part 60, Subpart Kb	Product Stored = Petroleum liquid (other than petroleum or condensate), Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.5 psia but less than 0.75 psia
GRP2&3	STORAGE TANKS/VESSELS	P100-12, P100-13, P110-001, P110-002, P110-004, P120-001, P120-002, P120-003, P120-004, P165-001, P165-002	60Kb-6	40 CFR Part 60, Subpart Kb	Product Stored = Petroleum liquid (other than petroleum or condensate), Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia
GRPLOAD	LOADING/UNLOADING OPERATIONS	RACK-1, RACK-3, RACK-5	R5211-10	30 TAC Chapter 115, Loading and Unloading of	Chapter 115 Facility Type = Facility type other than a

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
				VOC	gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal., Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline., True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia., Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized., Chapter 115 Control Device Type = Vapor control system with a flare., Control Options = Vapor control system that maintains a control efficiency of at least 90%., Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.
GRPLOAD	LOADING/UNLOADING OPERATIONS	RACK-1, RACK-3, RACK-5	R5211-6	30 TAC Chapter 115, Loading and Unloading of VOC	Vapor Space Holding Tank = the gasoline terminal does not have a variable vapor space holding tank design that can process vapors independent of transport vessel loading or chooses

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					<p>compliance with 30 TAC 115.212(a)(4)(C), Chapter 115 Facility Type = Gasoline terminal, Product Transferred = Gasoline, True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia., Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(B), (b)(3)(B), (a)(2)(A), and (b)(3)(A) exemptions do not apply to marine terminals or gasoline terminals., Chapter 115 Control Device Type = Vapor control system with a vapor combustor., Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p>
GRPLOAD	LOADING/UNLOADING OPERATIONS	RACK-1, RACK-3, RACK-5	R5211-7	30 TAC Chapter 115, Loading and Unloading of VOC	<p>Vapor Space Holding Tank = the gasoline terminal does not have a variable vapor space holding tank design that can process vapors independent of transport vessel loading or chooses compliance with 30 TAC 115.212(a)(4)(C), Chapter 115 Facility Type = Gasoline</p>

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					terminal, Product Transferred = Gasoline, True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia., Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(B), (b)(3)(B), (a)(2)(A), and (b)(3)(A) exemptions do not apply to marine terminals or gasoline terminals., Chapter 115 Control Device Type = Vapor control system with a flare., Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.
GRPLOAD	LOADING/UNLOADING OPERATIONS	RACK-1, RACK-3, RACK-5	R5211-8	30 TAC Chapter 115, Loading and Unloading of VOC	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal., Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline., True Vapor Pressure = True vapor pressure less than 0.5 psia.
GRPLOAD	LOADING/UNLOADING	RACK-1, RACK-3,	R5211-9	30 TAC Chapter 115,	Chapter 115 Facility Type =

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	OPERATIONS	RACK-5		Loading and Unloading of VOC	Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal., Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline., True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia., Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized., Chapter 115 Control Device Type = Vapor control system with a vapor combustor., Control Options = Vapor control system that maintains a control efficiency of at least 90%., Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.
GRPLOAD	LOADING/UNLOADING OPERATIONS	RACK-1, RACK-3, RACK-5	60XX-1	40 CFR Part 60, Subpart XX	Flare = The facility is not using a flare, as defined in 40 CFR § 60.501, to control vapor emissions.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
GRPLOAD	LOADING/UNLOADING OPERATIONS	RACK-1, RACK-3, RACK-5	60XX-2	40 CFR Part 60, Subpart XX	Flare = The facility is using a flare, as defined in 40 CFR § 60.501, to control vapor emissions.
GRPLOAD	LOADING/UNLOADING OPERATIONS	RACK-1, RACK-3, RACK-5	61BB-5	40 CFR Part 61, Subpart BB	Benzene By Weight = Concentration of benzene by weight in the liquid which is loaded is less than 70% benzene by weight., Annual Amount Loaded = Annual amount loaded is greater than or equal to 1.3 million liters (343,424 gallons).
GRPLOAD	LOADING/UNLOADING OPERATIONS	RACK-1, RACK-3, RACK-5	61BB-6	40 CFR Part 61, Subpart BB	Benzene By Weight = Concentration of benzene by weight in the liquid which is loaded is greater than or equal to 70% benzene by weight., Annual Amount Loaded = Annual amount loaded is less than 1.3 million liters (343,424 gallons).
GRPLOAD	LOADING/UNLOADING OPERATIONS	RACK-1, RACK-3, RACK-5	61BB-7	40 CFR Part 61, Subpart BB	Benzene By Weight = Concentration of benzene by weight in the liquid which is loaded is greater than or equal to 70% benzene by weight., Annual Amount Loaded = Annual amount loaded is greater than or equal to 1.3 million liters (343,424 gallons)., Loading Location = Land loading only.,

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					Subpart BB Control Device Type = Incinerator other than a catalytic incinerator., Intermittent Control Device = The control device does not operate intermittently., Diverted Gas Stream = The vent gas stream cannot be diverted from the control device.
GRPLOAD	LOADING/UNLOADING OPERATIONS	RACK-1, RACK-3, RACK-5	61BB-8	40 CFR Part 61, Subpart BB	Benzene By Weight = Concentration of benzene by weight in the liquid which is loaded is greater than or equal to 70% benzene by weight., Annual Amount Loaded = Annual amount loaded is greater than or equal to 1.3 million liters (343,424 gallons), Loading Location = Land loading only., Subpart BB Control Device Type = Flare., Intermittent Control Device = The control device does not operate intermittently., Diverted Gas Stream = The vent gas stream cannot be diverted from the control device.
GRPLOADMARI NE	LOADING/UNLOADING OPERATIONS	BGDK-1, BGDK-2, BGDK-3, BGDK-4, SHDK-1, SHDK-2	R5211-1	30 TAC Chapter 115, Loading and Unloading of VOC	Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline., True Vapor Pressure =

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					True vapor pressure less than 0.5 psia.
GRPLOADMARI NE	LOADING/UNLOADING OPERATIONS	BGDK-1, BGDK-2, BGDK-3, BGDK-4, SHDK-1, SHDK-2	R5211-2	30 TAC Chapter 115, Loading and Unloading of VOC	Marine Terminal Exemptions = The marine terminal is not claiming one or more of the exemptions in 30 TAC § 115.217(a)(5)(B)., Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline., True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia., Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(B), (b)(3)(B), (a)(2)(A), and (b)(3)(A) exemptions do not apply to marine terminals or gasoline terminals., Chapter 115 Control Device Type = Vapor control system with a vapor combustor., Control Options = Vapor control system that maintains a control efficiency of at least 90%., Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
GRPLOADMARI NE	LOADING/UNLOADING OPERATIONS	BGDK-1, BGDK-2, BGDK-3, BGDK-4, SHDK-1, SHDK-2	R5211-3	30 TAC Chapter 115, Loading and Unloading of VOC	Marine Terminal Exemptions = The marine terminal is not claiming one or more of the exemptions in 30 TAC § 115.217(a)(5)(B)., Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline., True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia., Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(B), (b)(3)(B), (a)(2)(A), and (b)(3)(A) exemptions do not apply to marine terminals or gasoline terminals., Chapter 115 Control Device Type = Vapor control system with a flare., Control Options = Vapor control system that maintains a control efficiency of at least 90%., Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.
GRPLOADMARI NE	LOADING/UNLOADING OPERATIONS	BGDK-1, BGDK-2, BGDK-3, BGDK-4,	R5211-4	30 TAC Chapter 115, Loading and Unloading of	Marine Terminal Exemptions = The marine terminal is not

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
		SHDK-1, SHDK-2		VOC	claiming one or more of the exemptions in 30 TAC § 115.217(a)(5)(B)., Product Transferred = Gasoline, True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia., Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(B), (b)(3)(B), (a)(2)(A), and (b)(3)(A) exemptions do not apply to marine terminals or gasoline terminals., Chapter 115 Control Device Type = Vapor control system with a vapor combustor., Control Options = Vapor control system that maintains a control efficiency of at least 90%., Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.
GRPLOADMARI NE	LOADING/UNLOADING OPERATIONS	BGDK-1, BGDK-2, BGDK-3, BGDK-4, SHDK-1, SHDK-2	R5211-5	30 TAC Chapter 115, Loading and Unloading of VOC	Marine Terminal Exemptions = The marine terminal is not claiming one or more of the exemptions in 30 TAC § 115.217(a)(5)(B)., Product Transferred = Gasoline, True Vapor Pressure = True vapor

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					<p>pressure greater than or equal to 0.5 psia., Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(B), (b)(3)(B), (a)(2)(A), and (b)(3)(A) exemptions do not apply to marine terminals or gasoline terminals., Chapter 115 Control Device Type = Vapor control system with a flare., Control Options = Vapor control system that maintains a control efficiency of at least 90%., Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p>
GRPLOADMARI NE	LOADING/UNLOADING OPERATIONS	BGDK-1, BGDK-2, BGDK-3, BGDK-4, SHDK-1, SHDK-2	61BB-1	40 CFR Part 61, Subpart BB	Benzene By Weight = Concentration of benzene by weight in the liquid which is loaded is less than 70% benzene by weight., Annual Amount Loaded = Annual amount loaded is greater than or equal to 1.3 million liters (343,424 gallons).
GRPLOADMARI NE	LOADING/UNLOADING OPERATIONS	BGDK-1, BGDK-2, BGDK-3, BGDK-4, SHDK-1, SHDK-2	61BB-2	40 CFR Part 61, Subpart BB	Benzene By Weight = Concentration of benzene by weight in the liquid which is

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					loaded is greater than or equal to 70% benzene by weight., Annual Amount Loaded = Annual amount loaded is less than 1.3 million liters (343,424 gallons).
GRPLOADMARI NE	LOADING/UNLOADING OPERATIONS	BGDK-1, BGDK-2, BGDK-3, BGDK-4, SHDK-1, SHDK-2	61BB-3	40 CFR Part 61, Subpart BB	Benzene By Weight = Concentration of benzene by weight in the liquid which is loaded is greater than or equal to 70% benzene by weight., Annual Amount Loaded = Annual amount loaded is greater than or equal to 1.3 million liters (343,424 gallons)., Loading Location = Marine loading only., Subpart BB Control Device Type = Incinerator other than a catalytic incinerator., Intermittent Control Device = The control device does not operate intermittently., Diverted Gas Stream = The vent gas stream cannot be diverted from the control device.
GRPLOADMARI NE	LOADING/UNLOADING OPERATIONS	BGDK-1, BGDK-2, BGDK-3, BGDK-4, SHDK-1, SHDK-2	61BB-4	40 CFR Part 61, Subpart BB	Benzene By Weight = Concentration of benzene by weight in the liquid which is loaded is greater than or equal to 70% benzene by weight., Annual Amount Loaded = Annual

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					amount loaded is greater than or equal to 1.3 million liters (343,424 gallons), Loading Location = Marine loading only., Subpart BB Control Device Type = Flare., Intermittent Control Device = The control device does not operate intermittently., Diverted Gas Stream = The vent gas stream cannot be diverted from the control device.
GRPOWS	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	OWS-01A, OWS-01B	R5131-1	30 TAC Chapter 115, Water Separation	No changing attributes.
GRPWASTE	STORAGE TANKS/VESSELS	PW-H20-01, PW-S20-01	R5112-10	30 TAC Chapter 115, Storage of VOCs	True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia, Control Device Type = Flare
GRPWASTE	STORAGE TANKS/VESSELS	PW-H20-01, PW-S20-01	R5112-7	30 TAC Chapter 115, Storage of VOCs	True Vapor Pressure = True vapor pressure is less than 1.0 psia
GRPWASTE	STORAGE TANKS/VESSELS	PW-H20-01, PW-S20-01	R5112-8	30 TAC Chapter 115, Storage of VOCs	True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia
GRPWASTE	STORAGE TANKS/VESSELS	PW-H20-01, PW-S20-01	R5112-9	30 TAC Chapter 115, Storage of VOCs	True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia, Control Device

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					Type = Other vapor destruction unit

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
EFWP-1	EU	60III-1	NMHC and NO _x	40 CFR Part 60, Subpart IIII	§ 60.4205(c)-Table 4 § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218	Owners and operators of emergency stationary fire pump CI ICE with a maximum engine power greater than or equal to 130 KW and less than or equal to 560 KW and a displacement of less than 30 liters per cylinder and is a 2009 model year and later must comply with an NMHC+NO _x emission limit of 4.0 g/KW-hr, as listed in Table 4 to this subpart.	None	None	[G]§ 60.4214(d)
EFWP-1	EU	60III-1	PM	40 CFR Part 60, Subpart IIII	§ 60.4205(c)-Table 4 § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218	Owners and operators of emergency stationary fire pump CI ICE with a maximum engine power greater than or equal to 130 KW and less than or equal to 560 KW and a displacement of less than 30 liters per cylinder and is a 2009 model year and later must comply with a PM emission limit of 0.20 g/KW-hr, as listed in Table 4 to this subpart.	None	None	[G]§ 60.4214(d)
EFWP-1	EU	63ZZZZ-1	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(c)	Stationary RICE subject to Regulations under 40 CFR Part 60. An affected source that meets any of the criteria in paragraphs (c)(1) through (7) of this section must meet the requirements of this part by meeting the requirements of 40 CFR part 60 subpart IIII, for	None	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						compression ignition engines or 40 CFR part 60 subpart JJJJ, for spark ignition engines as applicable. No further requirements apply for such engines under this part.			
EFWP-2	EU	60III-1	NMHC and NO _x	40 CFR Part 60, Subpart IIII	§ 60.4205(c)-Table 4 § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218	Owners and operators of emergency stationary fire pump CI ICE with a maximum engine power greater than or equal to 130 KW and less than or equal to 560 KW and a displacement of less than 30 liters per cylinder and is a 2009 model year and later must comply with an NMHC+NO _x emission limit of 4.0 g/KW-hr, as listed in Table 4 to this subpart.	None	None	[G]§ 60.4214(d)
EFWP-2	EU	60III-1	PM	40 CFR Part 60, Subpart IIII	§ 60.4205(c)-Table 4 § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218	Owners and operators of emergency stationary fire pump CI ICE with a maximum engine power greater than or equal to 130 KW and less than or equal to 560 KW and a displacement of less than 30 liters per cylinder and is a 2009 model year and later must comply with a PM emission limit of 0.20 g/KW-hr, as listed in Table 4 to this subpart.	None	None	[G]§ 60.4214(d)
EFWP-2	EU	63ZZZZ-1	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(c)	Stationary RICE subject to Regulations under 40 CFR	None	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						Part 60. An affected source that meets any of the criteria in paragraphs (c)(1) through (7) of this section must meet the requirements of this part by meeting the requirements of 40 CFR part 60 subpart IIII, for compression ignition engines or 40 CFR part 60 subpart JJJJ, for spark ignition engines as applicable. No further requirements apply for such engines under this part.			
EFWP-3	EU	60III-1	NMHC and NO _x	40 CFR Part 60, Subpart IIII	§ 60.4205(c)-Table 4 § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218	Owners and operators of emergency stationary fire pump CI ICE with a maximum engine power greater than or equal to 130 KW and less than or equal to 560 KW and a displacement of less than 30 liters per cylinder and is a 2009 model year and later must comply with an NMHC+NO _x emission limit of 4.0 g/KW-hr, as listed in Table 4 to this subpart.	None	None	[G]§ 60.4214(d)
EFWP-3	EU	60III-1	PM	40 CFR Part 60, Subpart IIII	§ 60.4205(c)-Table 4 § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218	Owners and operators of emergency stationary fire pump CI ICE with a maximum engine power greater than or equal to 130 KW and less than or equal to 560 KW and a displacement of less than 30 liters per cylinder and is a	None	None	[G]§ 60.4214(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						2009 model year and later must comply with a PM emission limit of 0.20 g/KW-hr, as listed in Table 4 to this subpart.			
EFWP-3	EU	63ZZZZ-2	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(c)	Stationary RICE subject to Regulations under 40 CFR Part 60. An affected source that meets any of the criteria in paragraphs (c)(1) through (7) of this section must meet the requirements of this part by meeting the requirements of 40 CFR part 60 subpart IIII, for compression ignition engines or 40 CFR part 60 subpart JJJJ, for spark ignition engines as applicable. No further requirements apply for such engines under this part.	None	None	None
EGEN-1	EU	60JJJJ-1	CO	40 CFR Part 60, Subpart JJJJ	§ 60.4233(e)- Table1 § 60.4234 § 60.4243(b) § 60.4243(b)(1) [G]§ 60.4243(d) § 60.4243(g) § 60.4246	Owners and operators of stationary emergency SI ICE with a maximum engine power greater than or equal to 130 HP and were manufactured on or after 01/01/2009 must comply with a CO emission limit of 4.0 g/HP-hr, as listed in Table 1 to this subpart.	§ 60.4237(b)	§ 60.4243(a)(1) § 60.4245(a)(1) § 60.4245(a)(2) § 60.4245(a)(3) § 60.4245(b)	[G]§ 60.4245(e)
EGEN-1	EU	60JJJJ-1	NO _x	40 CFR Part 60, Subpart JJJJ	§ 60.4233(e)- Table1 § 60.4234 § 60.4243(b) § 60.4243(b)(1)	Owners and operators of stationary emergency SI ICE with a maximum engine power greater than or equal to 130 HP and were	§ 60.4237(b)	§ 60.4243(a)(1) § 60.4245(a)(1) § 60.4245(a)(2) § 60.4245(a)(3) § 60.4245(b)	[G]§ 60.4245(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 60.4243(d) § 60.4243(g) § 60.4246	manufactured on or after 01/01/2009 must comply with a NOx emission limit of 2.0 g/HP-hr, as listed in Table 1 to this subpart.			
EGEN-1	EU	60JJJJ-1	VOC	40 CFR Part 60, Subpart JJJJ	§ 60.4233(e)-Table1 § 60.4234 § 60.4243(b) § 60.4243(b)(1) [G]§ 60.4243(d) § 60.4243(g) § 60.4246	Owners and operators of stationary emergency SI ICE with a maximum engine power greater than or equal to 130 HP and were manufactured on or after 01/01/2009 must comply with a VOC emission limit of 1.0 g/HP-hr, as listed in Table 1 to this subpart.	§ 60.4237(b)	§ 60.4243(a)(1) § 60.4245(a)(1) § 60.4245(a)(2) § 60.4245(a)(3) § 60.4245(b)	[G]§ 60.4245(e)
EGEN-1	EU	63ZZZZ-3	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(c)	Stationary RICE subject to Regulations under 40 CFR Part 60. An affected source that meets any of the criteria in paragraphs (c)(1) through (7) of this section must meet the requirements of this part by meeting the requirements of 40 CFR part 60 subpart IIII, for compression ignition engines or 40 CFR part 60 subpart JJJJ, for spark ignition engines as applicable. No further requirements apply for such engines under this part.	None	None	None
EGEN-2	EU	60JJJJ-2	CO	40 CFR Part 60, Subpart JJJJ	§ 60.4233(d)-Table1 § 60.4234 § 60.4243(b) § 60.4243(b)(1)	Owners and operators of stationary emergency SI ICE with a maximum engine power greater than 25 HP and less than 130 HP	§ 60.4237(c)	§ 60.4243(a)(1) § 60.4245(a)(1) § 60.4245(a)(2) § 60.4245(a)(3) § 60.4245(b)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 60.4243(d) § 60.4243(g) § 60.4246	and were manufactured on or after 01/01/2009 must comply with a CO emission limit of 387 g/HP-hr, as listed in Table 1 to this subpart.			
EGEN-2	EU	60JJJJ-2	HC and NO _x	40 CFR Part 60, Subpart JJJJ	§ 60.4233(d)-Table1 § 60.4234 § 60.4243(b) § 60.4243(b)(1) [G]§ 60.4243(d) § 60.4243(g) § 60.4246	Owners and operators of stationary emergency SI ICE with a maximum engine power greater than 25 HP and less than 130 HP and were manufactured on or after 01/01/2009 must comply with an HC+NO _x emission limit of 10 g/HP-hr, as listed in Table 1 to this subpart.	§ 60.4237(c)	§ 60.4243(a)(1) § 60.4245(a)(1) § 60.4245(a)(2) § 60.4245(a)(3) § 60.4245(b)	None
EGEN-2	EU	63ZZZZ-4	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(c)	Stationary RICE subject to Regulations under 40 CFR Part 60. An affected source that meets any of the criteria in paragraphs (c)(1) through (7) of this section must meet the requirements of this part by meeting the requirements of 40 CFR part 60 subpart IIII, for compression ignition engines or 40 CFR part 60 subpart JJJJ, for spark ignition engines as applicable. No further requirements apply for such engines under this part.	None	None	None
EGEN-3	EU	60JJJJ-2	CO	40 CFR Part 60, Subpart JJJJ	§ 60.4233(d)-Table1 § 60.4234	Owners and operators of stationary emergency SI ICE with a maximum	§ 60.4237(c)	§ 60.4243(a)(1) § 60.4245(a)(1) § 60.4245(a)(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.4243(b) § 60.4243(b)(1) [G]§ 60.4243(d) § 60.4243(g) § 60.4246	engine power greater than 25 HP and less than 130 HP and were manufactured on or after 01/01/2009 must comply with a CO emission limit of 387 g/HP-hr, as listed in Table 1 to this subpart.		§ 60.4245(a)(3) § 60.4245(b)	
EGEN-3	EU	60JJJJ-2	HC and NO _x	40 CFR Part 60, Subpart JJJJ	§ 60.4233(d)-Table1 § 60.4234 § 60.4243(b) § 60.4243(b)(1) [G]§ 60.4243(d) § 60.4243(g) § 60.4246	Owners and operators of stationary emergency SI ICE with a maximum engine power greater than 25 HP and less than 130 HP and were manufactured on or after 01/01/2009 must comply with an HC+NO _x emission limit of 10 g/HP-hr, as listed in Table 1 to this subpart.	§ 60.4237(c)	§ 60.4243(a)(1) § 60.4245(a)(1) § 60.4245(a)(2) § 60.4245(a)(3) § 60.4245(b)	None
EGEN-3	EU	63ZZZZ-4	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(c)	Stationary RICE subject to Regulations under 40 CFR Part 60. An affected source that meets any of the criteria in paragraphs (c)(1) through (7) of this section must meet the requirements of this part by meeting the requirements of 40 CFR part 60 subpart IIII, for compression ignition engines or 40 CFR part 60 subpart JJJJ, for spark ignition engines as applicable. No further requirements apply for such engines under this part.	None	None	None
FL-001	CD	60A-1	OPACITY	40 CFR Part 60,	§ 60.18(b)	Flares shall comply with	§ 60.18(d)	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Subpart A	§ 60.18(c)(1) § 60.18(c)(2) § 60.18(c)(3)(ii) § 60.18(c)(4)(ii) § 60.18(c)(6) § 60.18(e)	paragraphs (c)-(f) of § 60.18.	§ 60.18(f)(1) § 60.18(f)(2) § 60.18(f)(3) § 60.18(f)(4)		
FUG	EU	61J-ALL	BENZENE	40 CFR Part 61, Subpart J	§ 61.112(a) § 61.112(b)	Each owner or operator subject to this subpart shall comply with the requirements of 40 CFR 61, Subpart V - National Emission Standard for Equipment Leaks (Fugitive Emission Sources).	None	None	None
FUG	EU	61V-ALL	VHAP	40 CFR Part 61, Subpart V	§ 61.242-1(e)	Equipment that is in vacuum service is excluded from the requirements of §61.242-2 to §61.242-11, if it is identified as required in §61.246(e)(5).	None	[G]§ 61.246(e)	None
FUG	EU	61V-ALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-2 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for pumps. §61.242-2(a)-(g)	[G]§ 61.242-2 [G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(b) [G]§ 61.246(c) [G]§ 61.246(e) [G]§ 61.246(h) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
FUG	EU	61V-ALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-3 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for compressors. §61.242-3(a)-(i)	[G]§ 61.242-3 [G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(b) [G]§ 61.246(c) [G]§ 61.246(e) [G]§ 61.246(h) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
FUG	EU	61V-ALL	VHAP	40 CFR Part 61,	[G]§ 61.242-4	Comply with standards for	[G]§ 61.242-4	[G]§ 61.246(a)	[G]§ 61.247(a)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Subpart V	§ 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	pressure relief devices in gas/vapor service. §61.242-4(a)-(c)	[G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
FUG	EU	61V-ALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-5 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for sampling connection systems. §61.242-5(a)-(c)	[G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
FUG	EU	61V-ALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-6 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for open-ended valves or lines. §61.242-6(a)-(c)	[G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
FUG	EU	61V-ALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-7 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10 [G]§ 61.243-1 [G]§ 61.243-2	Comply with standards for valves. §61.242-7(a)-(h)	[G]§ 61.242-7 [G]§ 61.243-1 [G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(b) [G]§ 61.246(c) [G]§ 61.246(e) [G]§ 61.246(f) [G]§ 61.246(g) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) § 61.247(d) [G]§ 61.247(e)
FUG	EU	61V-ALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-8 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for pressure relief devices in liquid service. § 61.242-8(a)-(d)	[G]§ 61.242-8 [G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(b) [G]§ 61.246(c) [G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
FUG	EU	61V-ALL	VHAP	40 CFR Part 61, Subpart V	§ 61.242-9 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d)	Each product accumulator vessel shall be equipped with a closed-vent system to capture and transport any leakage from the vessel to a control device as in §61.242-11, except in §61.242-1(c).	[G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
FUG	EU	61V-ALL	VHAP	40 CFR Part 61, Subpart V	[G]§ 61.242-8 § 61.242-1(a) § 61.242-1(b) § 61.242-1(d) [G]§ 61.242-10	Comply with standards for flanges and other connectors. § 61.242-8(a)-(d)	[G]§ 61.242-8 [G]§ 61.245(b) [G]§ 61.245(c) [G]§ 61.245(d)	[G]§ 61.246(a) [G]§ 61.246(b) [G]§ 61.246(c) [G]§ 61.246(e) [G]§ 61.246(i) § 61.246(j)	[G]§ 61.247(a) [G]§ 61.247(b) § 61.247(c) [G]§ 61.247(e)
GRP1&2	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
GRP1&2	EU	R5112-2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
GRP1&2	EU	R5112-3	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(D) § 115.112(e)(2)(F) [G]§ 115.112(e)(2)(I) § 115.114(a)(1)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(1)(B) § 115.118(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP1&2	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
GRP1&2	EU	R5112-5	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
GRP1&2	EU	R5112-6	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(D) § 115.112(e)(2)(F) [G]§ 115.112(e)(2)(I) § 115.114(a)(1)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(1)(B) § 115.118(a)(3)
GRP1&2	EU	60Kb-10	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	(ix).	§ 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)		
GRP1&2	EU	60Kb-2	VOC	40 CFR Part 60, Subpart Kb	§ 60.110b(a)	Except for §60.110b(b), this subpart applies to vessels with a capacity greater than or equal to 75 cubic meters (19,800 gal) used to store VOLs for which construction/reconstruction /modification began after 7/23/84.	§ 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(d) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.116b(d)
GRP1&2	EU	60Kb-3	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)
GRP1&2	EU	60Kb-5	VOC	40 CFR Part 60, Subpart Kb	§ 60.110b(a)	Except for §60.110b(b), this subpart applies to vessels with a capacity greater than or equal to 75 cubic meters (19,800 gal) used to store VOLs for which construction/reconstruction /modification began after 7/23/84.	§ 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(d) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.116b(d)
GRP1&2	EU	60Kb-6	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) §	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4)	§ 60.115b § 60.115b(a)(2) § 60.116b(a)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.116b(b) § 60.116b(c)	§ 60.115b(a)(1) § 60.115b(a)(3)
GRP1&2	EU	60Kb-8	VOC	40 CFR Part 60, Subpart Kb	§ 60.110b(a)	Except for §60.110b(b), this subpart applies to vessels with a capacity greater than or equal to 75 cubic meters (19,800 gal) used to store VOLs for which construction/reconstruction /modification began after 7/23/84.	§ 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(d) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.116b(d)
GRP1&2	EU	60Kb-9	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)
GRP1&2	EU	61Y-1	BENZENE	40 CFR Part 61, Subpart Y	§ 61.271(a) § 61.271(a)(1) § 61.271(a)(2) § 61.271(a)(2)(iii) § 61.271(a)(3) § 61.271(a)(4) [G]§ 61.271(a)(5) § 61.271(a)(6) [G]§ 61.271(d)	The owner or operator of each storage vessel with a design storage capacity greater than or equal to 38 cubic meters (10,000 gal.) shall equip the vessel with a fixed roof and an internal floating roof.	§ 61.272(a)(1) § 61.272(a)(2) § 61.272(a)(3) § 61.272(a)(3)(ii)	§ 61.276(a) § 61.276(b)	§ 61.272(a)(2) § 61.272(a)(3)(i) § 61.274(a) [G]§ 61.275(a) [G]§ 61.275(b) § 61.275(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 61.272(a)(3)(ii)				
GRP1&2&W W	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
GRP1&2&W W	EU	R5112-2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
GRP1&2&W W	EU	R5112-3	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(D) § 115.112(e)(2)(F) [G]§ 115.112(e)(2)(I) § 115.114(a)(1)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(1)(B) § 115.118(a)(3)
GRP1&2&W W	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						requirements of this division.			
GRP1&2&W W	EU	R5112-5	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
GRP1&2&W W	EU	R5112-6	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(D) § 115.112(e)(2)(F) [G]§ 115.112(e)(2)(I) § 115.114(a)(1)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(1)(B) § 115.118(a)(3)
GRP1&2&W W	EU	60Kb-10	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(f)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP1&2&W W	EU	60Kb-12	VOC	40 CFR Part 60, Subpart Kb	§ 60.110b(a)	Except for §60.110b(b), this subpart applies to vessels with a capacity greater than or equal to 75 cubic meters (19,800 gal) used to store VOLs for which construction/reconstruction /modification began after 7/23/84.	§ 60.116b(a) § 60.116b(b) § 60.116b(d) § 60.116b(f)(2)	§ 60.116b(a) § 60.116b(b)	§ 60.116b(d)
GRP1&2&W W	EU	60Kb-13	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3) § 60.116b(f)(1)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)
GRP1&2&W W	EU	60Kb-2	VOC	40 CFR Part 60, Subpart Kb	§ 60.110b(a)	Except for §60.110b(b), this subpart applies to vessels with a capacity greater than or equal to 75 cubic meters (19,800 gal) used to store VOLs for which construction/reconstruction /modification began after 7/23/84.	§ 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(d) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.116b(d)
GRP1&2&W W	EU	60Kb-3	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)		§ 60.116b(e)(1) [G]§ 60.116b(e)(3)		
GRP1&2&W W	EU	60Kb-5	VOC	40 CFR Part 60, Subpart Kb	§ 60.110b(a)	Except for §60.110b(b), this subpart applies to vessels with a capacity greater than or equal to 75 cubic meters (19,800 gal) used to store VOLs for which construction/reconstruction /modification began after 7/23/84.	§ 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(d) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.116b(d)
GRP1&2&W W	EU	60Kb-6	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)
GRP1&2&W W	EU	60Kb-8	VOC	40 CFR Part 60, Subpart Kb	§ 60.110b(a)	Except for §60.110b(b), this subpart applies to vessels with a capacity greater than or equal to 75 cubic meters (19,800 gal) used to store VOLs for which construction/reconstruction /modification began after 7/23/84.	§ 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(d) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.116b(d)
GRP1&2&W W	EU	60Kb-9	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.116b(c)	§ 60.115b(a)(3)
GRP1&2&W W	EU	61Y-1	BENZENE	40 CFR Part 61, Subpart Y	§ 61.271(a) § 61.271(a)(1) § 61.271(a)(2) § 61.271(a)(2)(iii) § 61.271(a)(3) § 61.271(a)(4) [G]§ 61.271(a)(5) § 61.271(a)(6) [G]§ 61.271(d) § 61.272(a)(3)(ii)	The owner or operator of each storage vessel with a design storage capacity greater than or equal to 38 cubic meters (10,000 gal.) shall equip the vessel with a fixed roof and an internal floating roof.	§ 61.272(a)(1) § 61.272(a)(2) § 61.272(a)(3) § 61.272(a)(3)(ii)	§ 61.276(a) § 61.276(b)	§ 61.272(a)(2) § 61.272(a)(3)(i) § 61.274(a) [G]§ 61.275(a) [G]§ 61.275(b) § 61.275(c)
GRP2&3	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
GRP2&3	EU	R5112-2	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
GRP2&3	EU	R5112-3	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(1)(B) § 115.118(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.112(e)(2)(D) § 115.112(e)(2)(F) [G]§ 115.112(e)(2)(I) § 115.114(a)(1)(A)	at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.			
GRP2&3	EU	R5112-4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
GRP2&3	EU	R5112-5	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
GRP2&3	EU	R5112-6	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(D) § 115.112(e)(2)(F) [G]§ 115.112(e)(2)(I) § 115.114(a)(1)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(1)(B) § 115.118(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.			
GRP2&3	EU	60Kb-2	VOC	40 CFR Part 60, Subpart Kb	§ 60.110b(a)	Except for §60.110b(b), this subpart applies to vessels with a capacity greater than or equal to 75 cubic meters (19,800 gal) used to store VOLs for which construction/reconstruction /modification began after 7/23/84.	§ 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(d) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.116b(d)
GRP2&3	EU	60Kb-3	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)
GRP2&3	EU	60Kb-5	VOC	40 CFR Part 60, Subpart Kb	§ 60.110b(a)	Except for §60.110b(b), this subpart applies to vessels with a capacity greater than or equal to 75 cubic meters (19,800 gal) used to store VOLs for which construction/reconstruction /modification began after 7/23/84.	§ 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(d) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.116b(d)
GRP2&3	EU	60Kb-6	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) §	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4)	§ 60.115b § 60.115b(a)(2) § 60.116b(a)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.116b(b) § 60.116b(c)	§ 60.115b(a)(1) § 60.115b(a)(3)
GRPLOAD	EU	R5211-10	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.212(a)(1) § 115.212(a)(1)(A) § 115.212(a)(2) § 115.212(a)(3)(A) § 115.212(a)(3)(A)(ii) § 115.212(a)(3)(B) [G]§ 115.212(a)(3)(C) § 115.212(a)(3)(D) § 115.212(a)(3)(E) § 115.214(a)(1)(B) § 115.214(a)(1)(C) § 60.18	At operations other than gasoline terminals, gasoline bulk plants, and marine terminals, vapors of VOC with a true vapor pressure of 0.5 psia or greater, must be controlled by one of the following methods.	§ 115.212(a)(3)(B) § 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.214(a)(1)(A)(ii) § 115.214(a)(1)(A)(iii) § 115.215 § 115.215(1) § 115.215(10) [G]§ 115.215(2) [G]§ 115.215(3) § 115.215(4) § 115.215(9) § 115.216(1) § 115.216(1)(B)	§ 115.216 § 115.216(1) § 115.216(1)(B) § 115.216(2) § 115.216(3)(A) § 115.216(3)(A)(i) § 115.216(3)(A)(ii) § 115.216(3)(A)(iii) § 115.216(3)(B)	None
GRPLOAD	EU	R5211-6	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.211(1) § 115.212(a)(2) § 115.212(a)(3)(A) § 115.212(a)(3)(A)(ii) § 115.212(a)(3)(B) [G]§ 115.212(a)(3)(C) § 115.212(a)(3)(D) § 115.212(a)(3)(E) § 115.212(a)(4)(A) § 115.212(a)(4)(B) § 115.212(a)(4)(C) § 115.214(a)(1)(B)	Gasoline terminals, in the covered non-attainment counties, shall ensure that VOC emissions do not exceed 0.09 lb/1,000 gal (10.8 mg/liter) of gasoline loaded into transport vessels.	§ 115.212(a)(3)(B) [G]§ 115.212(a)(3)(C) § 115.212(a)(4)(C) § 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.214(a)(1)(A)(ii) § 115.214(a)(1)(A)(iii) § 115.214(a)(2) § 115.215 § 115.215(1) § 115.215(10)	§ 115.216 § 115.216(1) § 115.216(1)(A) § 115.216(1)(A)(iv) § 115.216(2) § 115.216(3)(A) § 115.216(3)(A)(i) § 115.216(3)(A)(ii) § 115.216(3)(A)(iii) § 115.216(3)(B) [G]§ 115.216(3)(E)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.214(a)(1)(C)		[G]§ 115.215(2) § 115.215(4) § 115.215(5) § 115.215(6) § 115.215(9) § 115.216(1) § 115.216(1)(A) § 115.216(1)(A)(iv)		
GRPLOAD	EU	R5211-7	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.211(1) § 115.212(a)(2) § 115.212(a)(3)(A) § 115.212(a)(3)(A)(ii) § 115.212(a)(3)(B) [G]§ 115.212(a)(3)(C) § 115.212(a)(3)(D) § 115.212(a)(3)(E) § 115.212(a)(4)(A) § 115.212(a)(4)(B) § 115.212(a)(4)(C) § 115.214(a)(1)(B) § 115.214(a)(1)(C) § 60.18	Gasoline terminals, in the covered non-attainment counties, shall ensure that VOC emissions do not exceed 0.09 lb/1,000 gal (10.8 mg/liter) of gasoline loaded into transport vessels.	§ 115.212(a)(3)(B) [G]§ 115.212(a)(3)(C) § 115.212(a)(4)(C) § 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.214(a)(1)(A)(ii) § 115.214(a)(1)(A)(iii) § 115.214(a)(2) § 115.215 § 115.215(1) § 115.215(10) [G]§ 115.215(2) [G]§ 115.215(3) § 115.215(4) § 115.215(5) § 115.215(6) § 115.215(9) § 115.216(1) § 115.216(1)(B)	§ 115.216 § 115.216(1) § 115.216(1)(B) § 115.216(2) § 115.216(3)(A) § 115.216(3)(A)(i) § 115.216(3)(A)(ii) § 115.216(3)(A)(iii) § 115.216(3)(B) [G]§ 115.216(3)(E)	None
GRPLOAD	EU	R5211-8	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(a)(1) § 115.212(a)(2) § 115.214(a)(1)(B) § 115.214(a)(1)(D) § 115.214(a)(1)(D)(i)	Vapor pressure (at land-based operations). All land-based loading and unloading of VOC with a true vapor pressure less than 0.5 psia is exempt from the requirements of this division, except as	§ 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.215 § 115.215(4)	§ 115.216 § 115.216(2) § 115.216(3)(B)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						specified.			
GRPLOAD	EU	R5211-9	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.212(a)(1) § 115.212(a)(1)(A) § 115.212(a)(2) § 115.212(a)(3)(A) § 115.212(a)(3)(A)(ii) § 115.212(a)(3)(B) [G]§ 115.212(a)(3)(C) § 115.212(a)(3)(D) § 115.212(a)(3)(E) § 115.214(a)(1)(B) § 115.214(a)(1)(C)	At operations other than gasoline terminals, gasoline bulk plants, and marine terminals, vapors of VOC with a true vapor pressure of 0.5 psia or greater, must be controlled by one of the following methods.	§ 115.212(a)(3)(B) § 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.214(a)(1)(A)(ii) § 115.214(a)(1)(A)(iii) § 115.215 § 115.215(1) § 115.215(10) [G]§ 115.215(2) § 115.215(4) § 115.215(9) § 115.216(1) § 115.216(1)(A) § 115.216(1)(A)(iv)	§ 115.216 § 115.216(1) § 115.216(1)(A) § 115.216(1)(A)(iv) § 115.216(2) § 115.216(3)(A) § 115.216(3)(A)(i) § 115.216(3)(A)(ii) § 115.216(3)(A)(iii) § 115.216(3)(B)	None
GRPLOAD	EU	60XX-1	TOC	40 CFR Part 60, Subpart XX	§ 60.502(a) § 60.502(b) § 60.502(d) § 60.502(g) § 60.502(h) § 60.502(i)	Each bulk gasoline terminal facility shall be equipped with a vapor collection system designed to collect the total organic compounds vapors displaced from tank trucks during product loading.	§ 60.502(j) § 60.503(a) § 60.503(b) § 60.503(c)(1) § 60.503(c)(3) § 60.503(c)(4) § 60.503(c)(5)(i) § 60.503(c)(6) § 60.503(c)(7) § 60.503(d) § 60.503(d)(1) § 60.503(d)(2) ** See CAM Summary	§ 60.502(j) § 60.503(c)(4) § 60.503(d)(2) [G]§ 60.505(c) [G]§ 60.505(e)	[G]§ 60.505(e)
GRPLOAD	EU	60XX-2	TOC	40 CFR Part 60, Subpart XX	§ 60.502(a) § 60.18 § 60.502(b) § 60.502(d) § 60.502(g) § 60.502(h)	Each bulk gasoline terminal facility shall be equipped with a vapor collection system designed to collect the total organic compounds vapors	§ 60.502(j) § 60.503(a) § 60.503(b) § 60.503(d) § 60.503(d)(1) § 60.503(d)(2)	§ 60.502(j) § 60.503(d)(2) [G]§ 60.505(c) [G]§ 60.505(e)	[G]§ 60.505(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.502(i)	displaced from tank trucks during product loading.	§ 60.503(e) § 60.503(f) ** See CAM Summary		
GRPLOAD	EU	61BB-5	BENZENE	40 CFR Part 61, Subpart BB	§ 61.300(b)	Any affected facility as per § 61.300(a), loading only liquid containing < 70 weight-percent benzene is exempt from this subpart, except for the recordkeeping and reporting in § 61.305(i).	None	[G]§ 61.305(i)	[G]§ 61.305(i)
GRPLOAD	EU	61BB-6	BENZENE	40 CFR Part 61, Subpart BB	§ 61.300(d)	Any affected facility as per § 61.300(a), whose annual benzene loading is < 1.3 million liters of 70 weight-percent or more benzene is exempt from this subpart, except for § 61.305(i).	None	[G]§ 61.305(i)	[G]§ 61.305(i)
GRPLOAD	EU	61BB-7	BENZENE	40 CFR Part 61, Subpart BB	[G]§ 61.302(a) § 61.302(b) § 61.302(f) § 61.302(g) § 61.302(h) § 61.302(i) § 61.302(k)	Equip each loading rack with vapor collection system to collect all displaced benzene vapors and prevent it from passing from one loading rack through another to the atmosphere. § 61.302(a)(1)-(2)	§ 61.302(k) § 61.303(a) § 61.303(a)(1) § 61.304(a)(1) § 61.304(a)(2) § 61.304(a)(4) § 61.304(a)(4)(i) § 61.304(a)(4)(ii) § 61.304(a)(4)(iii) § 61.304(a)(4)(iv) § 61.304(a)(5) § 61.304(a)(6) § 61.304(a)(7) § 61.304(c)(1) § 61.304(c)(2) § 61.304(c)(3) § 61.304(c)(4) § 61.304(e)	§ 61.304(a)(4)(i) § 61.304(c)(3) § 61.305(a) [G]§ 61.305(a)(1) § 61.305(b) § 61.305(b)(1)	§ 61.305(a) § 61.305(a)(5) § 61.305(b) § 61.305(b)(1) § 61.305(f) § 61.305(f)(1)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRPLOAD	EU	61BB-8	BENZENE	40 CFR Part 61, Subpart BB	[G]§ 61.302(a) § 60.18 § 61.302(b) § 61.302(c) § 61.302(f) § 61.302(g) § 61.302(h) § 61.302(i) § 61.302(k)	Equip each loading rack with vapor collection system to collect all displaced benzene vapors and prevent it from passing from one loading rack through another to the atmosphere. § 61.302(a)(1)-(2)	§ 61.302(k) § 61.303(b) § 61.304(b) § 61.304(c)(1) § 61.304(c)(2) § 61.304(c)(3) § 61.304(c)(4) § 61.304(e)	§ 61.304(c)(3) § 61.305(a) § 61.305(a)(2) § 61.305(b) § 61.305(e)	§ 61.305(a) § 61.305(a)(5) § 61.305(b) § 61.305(f) § 61.305(f)(1) § 61.305(f)(4)
GRPLOADM ARINE	EU	R5211-1	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(a)(5)(B) § 115.212(a)(6)(D) § 115.214(a)(3)(C) § 115.214(a)(3)(G) § 115.214(a)(3)(G)(i) § 115.217(a)(5)(B)(iii)	The marine vessel transfer operations specified in § 115.217(a)(5)(B)(i)-(iv) are exempt from the requirements of §§ 115.212(a), 115.214(a), and 115.216 of this title, except as noted.	§ 115.214(a)(3)(B) § 115.214(a)(3)(B)(i) § 115.215 § 115.215(4)	§ 115.216 § 115.216(2)	None
GRPLOADM ARINE	EU	R5211-1	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(a)(5)(B) § 115.214(a)(3)(C) § 115.214(a)(3)(G) § 115.214(a)(3)(G)(i) § 115.217(a)(5)(B)(i)	The marine vessel transfer operations specified in § 115.217(a)(5)(B)(i)-(iv) are exempt from the requirements of §§ 115.212(a), 115.214(a), and 115.216 of this title, except as noted.	§ 115.214(a)(3)(B) § 115.214(a)(3)(B)(i)	§ 115.216 § 115.216(2)	None
GRPLOADM ARINE	EU	R5211-2	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.212(a)(6)(A) § 115.212(a)(6)(B) [G]§ 115.212(a)(6)(C) § 115.212(a)(6)(D) [G]§ 115.214(a)(3)(A) § 115.214(a)(3)(C) § 115.214(a)(3)(D) § 115.214(a)(3)(E)	Emissions shall not exceed 0.09lb/1,000gal loaded, or the vapor control system shall maintain a control efficiency of at least 90%, or a vapor balance system or pressurized loading may be used.	[G]§ 115.214(a)(3)(A) § 115.214(a)(3)(B) § 115.214(a)(3)(B)(i) § 115.214(a)(3)(B)(ii) § 115.214(a)(3)(B)(iii) § 115.214(a)(3)(D) § 115.215 § 115.215(1) § 115.215(10)	[G]§ 115.214(a)(3)(A) § 115.214(a)(3)(D) § 115.216 § 115.216(1) § 115.216(1)(A) § 115.216(1)(A)(iv) § 115.216(2) [G]§ 115.216(4)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							[G]§ 115.215(2) § 115.215(4) § 115.215(5) § 115.215(7) § 115.215(8) § 115.215(9) § 115.216(1) § 115.216(1)(A) § 115.216(1)(A)(iv) ** See CAM Summary		
GRPLOADM ARINE	EU	R5211-3	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.212(a)(6)(A) § 115.212(a)(6)(B) [G]§ 115.212(a)(6)(C) § 115.212(a)(6)(D) [G]§ 115.214(a)(3)(A) § 115.214(a)(3)(C) § 115.214(a)(3)(D) § 115.214(a)(3)(E) § 60.18	Emissions shall not exceed 0.09lb/1,000gal loaded, or the vapor control system shall maintain a control efficiency of at least 90%, or a vapor balance system or pressurized loading may be used.	[G]§ 115.214(a)(3)(A) § 115.214(a)(3)(B) § 115.214(a)(3)(B)(i) § 115.214(a)(3)(B)(ii) § 115.214(a)(3)(B)(iii) § 115.214(a)(3)(D) § 115.215 § 115.215(1) § 115.215(10) [G]§ 115.215(2) [G]§ 115.215(3) § 115.215(4) § 115.215(5) § 115.215(7) § 115.215(8) § 115.215(9) § 115.216(1) § 115.216(1)(B) ** See CAM Summary	[G]§ 115.214(a)(3)(A) § 115.214(a)(3)(D) § 115.216 § 115.216(1) § 115.216(1)(B) § 115.216(2) [G]§ 115.216(4)	None
GRPLOADM ARINE	EU	R5211-4	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.212(a)(6)(A) § 115.212(a)(6)(B) [G]§ 115.212(a)(6)(C)	Emissions shall not exceed 0.09lb/1,000gal loaded, or the vapor control system shall maintain a control	[G]§ 115.214(a)(3)(A) § 115.214(a)(3)(B) § 115.214(a)(3)(B)(i)	[G]§ 115.214(a)(3)(A) § 115.214(a)(3)(D) § 115.216 § 115.216(1)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.212(a)(6)(D) [G]§ 115.214(a)(3)(A) § 115.214(a)(3)(C) § 115.214(a)(3)(D) § 115.214(a)(3)(E)	efficiency of at least 90%, or a vapor balance system or pressurized loading may be used.	§ 115.214(a)(3)(B)(ii) § 115.214(a)(3)(B)(iii) § 115.214(a)(3)(D) § 115.215 § 115.215(1) § 115.215(10) [G]§ 115.215(2) § 115.215(4) § 115.215(5) § 115.215(7) § 115.215(8) § 115.215(9) § 115.216(1) § 115.216(1)(A) § 115.216(1)(A)(iv) ** See CAM Summary	§ 115.216(1)(A) § 115.216(1)(A)(iv) § 115.216(2) [G]§ 115.216(4)	
GRPLOADM ARINE	EU	R5211-5	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.212(a)(6)(A) § 115.212(a)(6)(B) [G]§ 115.212(a)(6)(C) § 115.212(a)(6)(D) [G]§ 115.214(a)(3)(A) § 115.214(a)(3)(C) § 115.214(a)(3)(D) § 115.214(a)(3)(E) § 60.18	Emissions shall not exceed 0.09lb/1,000gal loaded, or the vapor control system shall maintain a control efficiency of at least 90%, or a vapor balance system or pressurized loading may be used.	[G]§ 115.214(a)(3)(A) § 115.214(a)(3)(B) § 115.214(a)(3)(B)(i) § 115.214(a)(3)(B)(ii) § 115.214(a)(3)(B)(iii) § 115.214(a)(3)(D) § 115.215 § 115.215(1) § 115.215(10) [G]§ 115.215(2) [G]§ 115.215(3) § 115.215(4) § 115.215(5) § 115.215(7) § 115.215(8) § 115.215(9) § 115.216(1)	[G]§ 115.214(a)(3)(A) § 115.214(a)(3)(D) § 115.216 § 115.216(1) § 115.216(1)(B) § 115.216(2) [G]§ 115.216(4)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 115.216(1)(B) ** See CAM Summary		
GRPLOADM ARINE	EU	61BB-1	BENZENE	40 CFR Part 61, Subpart BB	§ 61.300(b)	Any affected facility as per § 61.300(a), loading only liquid containing < 70 weight-percent benzene is exempt from this subpart, except for the recordkeeping and reporting in § 61.305(i).	None	[G]§ 61.305(i)	[G]§ 61.305(i)
GRPLOADM ARINE	EU	61BB-2	BENZENE	40 CFR Part 61, Subpart BB	§ 61.300(d)	Any affected facility as per § 61.300(a), whose annual benzene loading is < 1.3 million liters of 70 weight-percent or more benzene is exempt from this subpart, except for § 61.305(i).	None	[G]§ 61.305(i)	[G]§ 61.305(i)
GRPLOADM ARINE	EU	61BB-3	BENZENE	40 CFR Part 61, Subpart BB	[G]§ 61.302(a) § 61.302(b) § 61.302(f) § 61.302(g) § 61.302(j) § 61.302(k)	Equip each loading rack with vapor collection system to collect all displaced benzene vapors and prevent it from passing from one loading rack through another to the atmosphere. § 61.302(a)(1)-(2)	§ 61.302(k) § 61.303(a) § 61.303(a)(1) § 61.304(a)(1) § 61.304(a)(2) § 61.304(a)(4) § 61.304(a)(4)(i) § 61.304(a)(4)(ii) § 61.304(a)(4)(iii) § 61.304(a)(4)(iv) § 61.304(a)(5) § 61.304(a)(6) § 61.304(a)(7) § 61.304(d)(1) § 61.304(d)(2) § 61.304(d)(3) § 61.304(e) ** See CAM Summary	§ 61.304(a)(4)(i) § 61.304(d)(3) § 61.305(a) [G]§ 61.305(a)(1) § 61.305(b) § 61.305(b)(1)	§ 61.305(a) § 61.305(a)(5) § 61.305(b) § 61.305(b)(1) § 61.305(f) § 61.305(f)(1)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRPLOADM ARINE	EU	61BB-4	BENZENE	40 CFR Part 61, Subpart BB	[G]§ 61.302(a) § 60.18 § 61.302(b) § 61.302(c) § 61.302(f) § 61.302(g) § 61.302(j) § 61.302(k)	Equip each loading rack with vapor collection system to collect all displaced benzene vapors and prevent it from passing from one loading rack through another to the atmosphere. § 61.302(a)(1)-(2)	§ 61.302(k) § 61.303(b) § 61.304(b) § 61.304(d)(1) § 61.304(d)(2) § 61.304(d)(3) § 61.304(e)	§ 61.304(d)(3) § 61.305(a) § 61.305(a)(2) § 61.305(b) § 61.305(e)	§ 61.305(a) § 61.305(a)(5) § 61.305(b) § 61.305(f) § 61.305(f)(1) § 61.305(f)(4)
GRPOWS	EU	R5131-1	VOC	30 TAC Chapter 115, Water Separation	§ 115.132(a)(3) § 115.131(a)	VOC water separator compartments must be equipped with a vapor recovery system which satisfies the provisions of §115.131(a) of this title.	[G]§ 115.135(a) § 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	§ 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	None
GRPWASTE	EU	R5112-10	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(3) § 115.112(e)(3)(C) § 60.18	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.115(a) § 115.115(a)(6) § 115.116(a)(2) [G]§ 115.117 ** See CAM Summary	§ 115.118(a)(4) § 115.118(a)(4)(F) § 115.118(a)(5) § 115.118(a)(7)	None
GRPWASTE	EU	R5112-7	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRPWASTE	EU	R5112-8	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
GRPWASTE	EU	R5112-9	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(3) § 115.112(e)(3)(A) § 115.112(e)(3)(A)(i)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.115(a) § 115.115(a)(6) § 115.116(a)(1) [G]§ 115.117 ** See CAM Summary	§ 115.118(a)(4) § 115.118(a)(4)(F) § 115.118(a)(5) § 115.118(a)(7)	None

Additional Monitoring Requirements

Compliance Assurance Monitoring Summary 78

CAM Summary

Unit/Group/Process Information	
ID No.: GRPLOAD	
Control Device ID No.: VC-001	Control Device Type: Vapor Combustor
Control Device ID No.: VC-002	Control Device Type: Vapor Combustor
Control Device ID No.: VC-003	Control Device Type: Vapor Combustor
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart XX	SOP Index No.: 60XX-1
Pollutant: TOC	Main Standard: § 60.502(a)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: once per day	
Averaging Period: n/a*	
Deviation Limit: Prior to completion of the initial stack test (IST), VC firebox temp < 1400°F with waste gas flows shall be considered a deviation. Following successful completion of the IST, 6 min avg temp shall be > min 1 hr avg temp maintained during the IST.	
CAM Text: The monitoring device should be installed in the combustion chamber or immediately downstream of the combustion chamber. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following: ± 2% of reading; or ± 2.5 degrees Celsius.	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

CAM Summary

Unit/Group/Process Information	
ID No.: GRPLOAD	
Control Device ID No.: FL-001	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart XX	SOP Index No.: 60XX-2
Pollutant: TOC	Main Standard: § 60.502(a)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: n/a	
Deviation Limit: No flame present and no pilot flame with waste gas flows indicate a deviation.	
<p>CAM Text: Monitor the presence of a flare pilot flame using a thermocouple or other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. Maintain records of alarm events and duration of alarm events. Each monitoring device shall be accurate to within manufacturer's recommendations. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications or other written procedures that provide an adequate assurance that the device is calibrated accurately.</p>	

CAM Summary

Unit/Group/Process Information	
ID No.: GRPLOADMARINE	
Control Device ID No.: VC-001	Control Device Type: Vapor Combustor
Control Device ID No.: VC-002	Control Device Type: Vapor Combustor
Control Device ID No.: VC-003	Control Device Type: Vapor Combustor
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Loading and Unloading of VOC	SOP Index No.: R5211-2
Pollutant: VOC	Main Standard: § 115.212(a)(6)(A)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: once per day	
Averaging Period: n/a*	
Deviation Limit: Prior to completion of the initial stack test (IST), VC firebox temp < 1400°F with waste gas flows shall be considered a deviation. Following successful completion of the IST, 6 min avg temp shall be > min 1 hr avg temp maintained during the IST.	
<p>CAM Text: The monitoring device should be installed in the combustion chamber or immediately downstream of the combustion chamber. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following:</p> <ul style="list-style-type: none"> ± 2% of reading; or ± 2.5 degrees Celsius. 	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

CAM Summary

Unit/Group/Process Information	
ID No.: GRPLOADMARINE	
Control Device ID No.: FL-001	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Loading and Unloading of VOC	SOP Index No.: R5211-3
Pollutant: VOC	Main Standard: § 115.212(a)(6)(A)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: n/a	
Deviation Limit: No flame present and no pilot flame with waste gas flows indicate a deviation.	
<p>CAM Text: Monitor the presence of a flare pilot flame using a thermocouple or other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. Maintain records of alarm events and duration of alarm events. Each monitoring device shall be accurate to within manufacturer's recommendations. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications or other written procedures that provide an adequate assurance that the device is calibrated accurately.</p>	

CAM Summary

Unit/Group/Process Information	
ID No.: GRPLOADMARINE	
Control Device ID No.: VC-001	Control Device Type: Vapor Combustor
Control Device ID No.: VC-002	Control Device Type: Vapor Combustor
Control Device ID No.: VC-003	Control Device Type: Vapor Combustor
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Loading and Unloading of VOC	SOP Index No.: R5211-4
Pollutant: VOC	Main Standard: § 115.212(a)(6)(A)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: once per day	
Averaging Period: n/a*	
Deviation Limit: Prior to completion of the initial stack test (IST), VC firebox temp < 1400°F with waste gas flows shall be considered a deviation. Following successful completion of the IST, 6 min avg temp shall be > min 1 hr avg temp maintained during the IST.	
<p>CAM Text: The monitoring device should be installed in the combustion chamber or immediately downstream of the combustion chamber. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following:</p> <ul style="list-style-type: none"> ± 2% of reading; or ± 2.5 degrees Celsius. 	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

CAM Summary

Unit/Group/Process Information	
ID No.: GRPLOADMARINE	
Control Device ID No.: FL-001	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Loading and Unloading of VOC	SOP Index No.: R5211-5
Pollutant: VOC	Main Standard: § 115.212(a)(6)(A)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: n/a	
Deviation Limit: No flame present and no pilot flame with waste gas flows indicate a deviation.	
<p>CAM Text: Monitor the presence of a flare pilot flame using a thermocouple or other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. Maintain records of alarm events and duration of alarm events. Each monitoring device shall be accurate to within manufacturer's recommendations. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications or other written procedures that provide an adequate assurance that the device is calibrated accurately.</p>	

CAM Summary

Unit/Group/Process Information	
ID No.: GRPLOADMARINE	
Control Device ID No.: VC-001	Control Device Type: Vapor Combustor
Control Device ID No.: VC-002	Control Device Type: Vapor Combustor
Control Device ID No.: VC-003	Control Device Type: Vapor Combustor
Applicable Regulatory Requirement	
Name: 40 CFR Part 61, Subpart BB	SOP Index No.: 61BB-3
Pollutant: BENZENE	Main Standard: [G]§ 61.302(a)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: once per day	
Averaging Period: n/a*	
Deviation Limit: Prior to completion of the initial stack test (IST), VC firebox temp < 1400°F with waste gas flows shall be considered a deviation. Following successful completion of the IST, 6 min avg temp shall be > min 1 hr avg temp maintained during the IST.	
<p>CAM Text: The monitoring device should be installed in the combustion chamber or immediately downstream of the combustion chamber. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following:</p> <ul style="list-style-type: none"> ± 2% of reading; or ± 2.5 degrees Celsius. 	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

CAM Summary

Unit/Group/Process Information	
ID No.: GRPWASTE	
Control Device ID No.: FL-001	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-10
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: n/a	
Deviation Limit: No flame present and no pilot flame with waste gas flows indicate a deviation.	
<p>CAM Text: Monitor the presence of a flare pilot flame using a thermocouple or other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. Maintain records of alarm events and duration of alarm events. Each monitoring device shall be accurate to within manufacturer's recommendations. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications or other written procedures that provide an adequate assurance that the device is calibrated accurately.</p>	

CAM Summary

Unit/Group/Process Information	
ID No.: GRPWASTE	
Control Device ID No.: VC-001	Control Device Type: Vapor Combustor
Control Device ID No.: VC-002	Control Device Type: Vapor Combustor
Control Device ID No.: VC-003	Control Device Type: Vapor Combustor
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-9
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: once per day	
Averaging Period: n/a*	
Deviation Limit: Prior to completion of the initial stack test (IST), VC firebox temp < 1400°F with waste gas flows shall be considered a deviation. Following successful completion of the IST, 6 min avg temp shall be > min 1 hr avg temp maintained during the IST.	
<p>CAM Text: The monitoring device should be installed in the combustion chamber or immediately downstream of the combustion chamber. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following:</p> <ul style="list-style-type: none"> ± 2% of reading; or ± 2.5 degrees Celsius. 	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Permit Shield

Permit Shield88

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
DIESELFUEL TK	N/A	30 TAC Chapter 115, Storage of VOCs	Storage tank with a capacity less than 1000 gallons.
DIESELFUEL TK	N/A	40 CFR Part 60, Subpart Kb	Storage vessel with a capacity less than 75m ³ ,
GASFUEL TK	N/A	30 TAC Chapter 115, Storage of VOCs	Storage tank with a capacity less than 1000 gallons.
GASFUEL TK	N/A	40 CFR Part 60, Subpart Kb	Storage vessel with a capacity less than 75m ³ .
GASFUEL TK	N/A	40 CFR Part 63, Subpart R	Storage tank with a capacity less than 75 m ³ (20,000 gallons).
GRP1K	EFWP-1 TK, EFWP-2 TK, EFWP-3 TK	30 TAC Chapter 115, Storage of VOCs	Storage tank with a capacity less than 1000 gallons.
GRP1K	EFWP-1 TK, EFWP-2 TK, EFWP-3 TK	40 CFR Part 60, Subpart Kb	Storage vessel with a capacity less than 75m ³ .
GRP2&3	P100-12, P100-13, P110-001, P110-002, P110-004, P120-001, P120-002, P120-003, P120-004, P165-001, P165-002	40 CFR Part 61, Subpart Y	Storage unit does not store benzene.
GRPWASTE	PW-H20-01, PW-S20-01	40 CFR Part 60, Subpart Kb	Storage vessel with a capacity less than 75m ³ .

New Source Review Authorization References

New Source Review Authorization References90

New Source Review Authorization References by Emission Unit..... 91

New Source Review Authorization References

The New Source Review authorizations listed in the table below are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Title 30 TAC Chapter 116 Permits, Special Permits, and Other Authorizations (Other Than Permits By Rule, PSD Permits, or NA Permits) for the Application Area.	
Authorization No.: 95754	Issuance Date: 08/05/2015
Permits By Rule (30 TAC Chapter 106) for the Application Area	
Number: 106.261	Version No./Date: 11/01/2003
Number: 106.263	Version No./Date: 11/01/2001
Number: 106.472	Version No./Date: 09/04/2000
Number: 106.478	Version No./Date: 09/04/2000

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
BGDK-1	BARGE LOADING DOCK 1	95754
BGDK-2	BARGE LOADING DOCK 2	95754
BGDK-3	BARGE LOADING DOCK 3	95754
BGDK-4	BARGE LOADING DOCK 4	95754
DIESELFUEL TK	DIESEL FUEL TANK	95754
EFWP-1 TK	STORAGE TANK	95754
EFWP-1	EMERGENCY FIRE WATER PUMP	95754
EFWP-2 TK	STORAGE TANK	95754
EFWP-2	EMERGENCY FIRE WATER PUMP	95754
EFWP-3 TK	STORAGE TANK	95754
EFWP-3	EMERGENCY FIRE WATER PUMP	95754
EGEN-1	EMERGENCY GENERATOR	95754
EGEN-2	EMERGENCY GENERATOR	95754
EGEN-3	EMERGENCY GENERATOR	95754
FL-001	FLARE	95754
FUG	FUGITIVE COMPONENTS	95754
GASFUEL TK	GASOLINE FUEL TANK	95754
OWS-01A	OIL WATER SEPARATOR	95754

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
OWS-01B	OIL WATER SEPARATOR	95754
P100-001	STORAGE TANK	95754
P100-002	STORAGE TANK	95754
P100-003	STORAGE TANK	95754
P100-004	STORAGE TANK	95754
P100-005	STORAGE TANK	95754
P100-006	STORAGE TANK	95754
P100-007	STORAGE TANK	95754
P100-008	STORAGE TANK	95754
P100-009	STORAGE TANK	95754
P100-12	STORAGE TANK	95754
P100-13	STORAGE TANK	95754
P110-001	STORAGE TANK	95754
P110-002	STORAGE TANK	95754
P110-004	STORAGE TANK	95754
P120-001	STORAGE TANK	95754
P120-002	STORAGE TANK	95754
P120-003	STORAGE TANK	95754

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
P120-004	STORAGE TANK	95754
P12-001	STORAGE TANK	95754
P12-002	STORAGE TANK	95754
P12-003	STORAGE TANK	95754
P165-001	STORAGE TANK	95754
P165-002	STORAGE TANK	95754
P165-003	STORAGE TANK	95754
P165-004	STORAGE TANK	95754
P165-005	STORAGE TANK	95754
P165-006	STORAGE TANK	95754
P80-001	STORAGE TANK	95754
PW-H20-01	WASTEWATER TANK	95754
PW-S20-01	WASTEWATER TANK	95754
RACK-1	TRUCK AND RAILCAR LOADING RACK NO. 1	95754
RACK-3	TRUCK AND RAILCAR LOADING RACK NO. 3	95754
RACK-5	TRUCK AND RAILCAR LOADING RACK NO. 5	95754
SHDK-1	SHIP LOADING DOCK 1	95754
SHDK-2	SHIP LOADING DOCK 2	95754

Appendix A

Acronym List 95

Acronym List

The following abbreviations or acronyms may be used in this permit:

ACFM	actual cubic feet per minute
AMOC	alternate means of control
ARP	Acid Rain Program
ASTM	American Society of Testing and Materials
B/PA	Beaumont/Port Arthur (nonattainment area)
CAM	Compliance Assurance Monitoring
CD	control device
COMS	continuous opacity monitoring system
CVS	closed-vent system
D/FW	Dallas/Fort Worth (nonattainment area)
DR	Designated Representative
ELP	El Paso (nonattainment area)
EP	emission point
EPA	U.S. Environmental Protection Agency
EU	emission unit
FCAA Amendments	Federal Clean Air Act Amendments
FOP	federal operating permit
GF	grandfathered
gr/100 scf	grains per 100 standard cubic feet
HAP	hazardous air pollutant
H/G/B	Houston/Galveston/Brazoria (nonattainment area)
H ₂ S	hydrogen sulfide
ID No.	identification number
lb/hr	pound(s) per hour
MMBtu/hr	Million British thermal units per hour
MRRT	monitoring, recordkeeping, reporting, and testing
NA	nonattainment
N/A	not applicable
NADB	National Allowance Data Base
NO _x	nitrogen oxides
NSPS	New Source Performance Standard (40 CFR Part 60)
NSR	New Source Review
ORIS	Office of Regulatory Information Systems
Pb	lead
PBR	Permit By Rule
PM	particulate matter
ppmv	parts per million by volume
PSD	prevention of significant deterioration
RO	Responsible Official
SO ₂	sulfur dioxide
TCEQ	Texas Commission on Environmental Quality
TSP	total suspended particulate
TVP	true vapor pressure
U.S.C.	United States Code
VOC	volatile organic compound