

Statement of Basis of the Federal Operating Permit

Invista S.à r.l.

Site Name: Victoria Site
Area Name: Adiponitrile Unit
Physical Location: 2695 Old Bloomington Rd N
Nearest City: Victoria
County: Victoria

Permit Number: O1904
Project Type: Significant Revision

Standard Industrial Classification (SIC) Code: 2869
SIC Name: Industrial Organic Chemicals

This Statement of Basis sets forth the legal and factual basis for the draft changes to the permit conditions resulting from the significant revision project in accordance with 30 TAC §122.201(a)(4). The applicant has submitted an application for a significant permit revision per §§ 122.219-211. This document may include the following information:

- A description of the facility/area process description;
- A description of the revision project;
- A basis for applying permit shields;
- A list of the federal regulatory applicability determinations;
- A table listing the determination of applicable requirements;
- A list of the New Source Review Requirements;
- The rationale for periodic monitoring methods selected;
- The rationale for compliance assurance methods selected;
- A compliance status; and
- A list of available unit attribute forms.

Prepared on: June 9, 2016

Operating Permit Basis of Determination

Description of Revisions

This expedited significant revision incorporates changes to NSR 7186/PSDTX1079M1 and for the addition of GHGPSDTX145 for Inivsta S.à r.l's Adiponitrile (ADN) manufacturing unit in Victoria, Texas that produces an intermediate in the production of nylon. A temporary flare 10FLRTMP was also removed, and is reflected in the Federal Operating Permit (FOP). Unit requirements and preconstruction authorizations were also updated in this revision.

Permit Area Process Description

ADN is produced by combining Hydrogen Cyanide (HCN; manufactured on site) and butadiene (BD). The HCN process is a three step process: 1) Synthesis, 2) Ammonia Recovery and Recycle, and 3) HCN Recovery and Refining.

HCN is synthesized from the reaction of natural gas (methane) and ammonia. Natural gas is received by pipeline. Ammonia is received at the facility by barge. Ammonia natural gas is fed into the HCN converters. Ammonia must be recovered before the HCN can be processed. This is done by passing the off-gas from the HCN converters through an ammonia recovery system. The ammonia recovery system uses ammonium phosphate solution to remove the unreacted ammonia. Waste gases from the HCN unit are sent to the Adipic Power House (APH) as fuel or to the operating flare. The liquid waste streams are presently disposed of by deep well injection.

Hydrogen cyanide (HCN) from the HCN unit is fed to the Step I and Step II process units (Areas II and III). In Step I, HCN is reacted with butadiene in the presence of catalysts to produce intermediate nitrile products. These intermediates are further reacted in the Step II process.

FOPs at Site

The "application area" consists of the emission units and that portion of the site included in the application and this permit. Multiple FOPs may be issued to a site in accordance with 30 TAC § 122.201(e). When there is only one area for the site, then the application information and permit will include all units at the site. Additional FOPs that exist at the site, if any, are listed below.

Additional FOPs: O1415, O1867, O1902

Major Source Pollutants

The table below specifies the pollutants for which the site is a major source:

Major Pollutants	VOC, PM, NOX, HAPS, CO, GHG
------------------	-----------------------------

Reading State of Texas's Federal Operating Permit

The Title V Federal Operating Permit (FOP) lists all state and federal air emission regulations and New Source Review (NSR) authorizations (collectively known as "applicable requirements") that apply at a particular site or permit area (in the event a site has multiple FOPs). **The FOP does not authorize new emissions or new construction activities.** The FOP begins with an introductory page which is common to all Title V permits. This page gives the details of the company, states the authority of the issuing agency, requires the company to operate in accordance with this permit and 30 Texas Administrative Code (TAC) Chapter 122, requires adherence with NSR requirements of 30 TAC Chapter 116, and finally indicates the permit number and the issuance date.

This is followed by the table of contents, which is generally composed of the following elements. Not all permits will have all of the elements.

- General Terms and Conditions
- Special Terms and Conditions
 - Emissions Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting
 - Additional Monitoring Requirements
 - New Source Review Authorization Requirements
 - Compliance Requirements
 - Protection of Stratosphere Ozone
 - Permit Location
 - Permit Shield (30 TAC § 122.148)
- Attachments
 - Applicable Requirements Summary
 - Unit Summary
 - Applicable Requirements Summary
 - Additional Monitoring Requirements
 - Permit Shield
 - New Source Review Authorization References
 - Compliance Plan
 - Alternative Requirements
- Appendix A
 - Acronym list
- Appendix B
 - Copies of major NSR authorizations

General Terms and Conditions

The General Terms and Conditions are the same and appear in all permits. The first paragraph lists the specific citations for 30 TAC Chapter 122 requirements that apply to all Title V permit holders. The second paragraph describes the requirements for record retention. The third paragraph provides details for voiding the permit, if applicable. The fourth paragraph states that the permit holder shall comply with the requirements of 30 TAC Chapter 116 by obtaining a New Source Review authorization prior to new construction or modification of emission units located in the area covered by this permit. The fifth paragraph provides details on submission of reports required by the permit.

Special Terms and Conditions

Emissions Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting. The TCEQ has designated certain applicable requirements as site-wide requirements. A site-wide requirement is a requirement that applies uniformly to all the units or activities at the site. Units with only site-wide requirements are addressed on Form OP-REQ1 and are not required to be listed separately on a OP-UA Form or Form OP-SUM. Form OP-SUM must list all units addressed in the application and provide identifying information, applicable OP-UA Forms, and preconstruction authorizations. The various OP-UA Forms provide the characteristics of each unit from which applicable requirements are established. Some exceptions exist as a few units may have both site-wide requirements and unit specific requirements.

Other conditions. The other entries under special terms and conditions are in general terms referring to compliance with the more detailed data listed in the attachments.

Attachments

Applicable Requirements Summary. The first attachment, the Applicable Requirements Summary, has two tables, addressing unit specific requirements. The first table, the Unit Summary, includes a list of units with applicable requirements, the unit type, the applicable regulation, and the requirement driver. The intent of the requirement driver is to inform the reader that a given unit may have several different operating scenarios and the differences between those operating scenarios.

The applicable requirements summary table provides the detailed citations of the rules that apply to the various units. For each unit and operating scenario, there is an added modifier called the “index number,” detailed citations specifying monitoring and testing requirements, recordkeeping requirements, and reporting requirements. The data for this table are based on data supplied by the applicant on the OP-SUM and various OP-UA forms.

Additional Monitoring Requirement. The next attachment includes additional monitoring the applicant must perform to ensure compliance with the applicable standard. Compliance assurance monitoring (CAM) is often required to provide a reasonable assurance of compliance with applicable emission limitations/standards for large emission units that use control devices to achieve compliance with applicant requirements. When necessary, periodic monitoring (PM) requirements are specified for certain parameters (i.e. feed rates, flow rates, temperature, fuel type and consumption, etc.) to determine if a term and condition or emission unit is operating within specified limits to control emissions. These additional monitoring approaches may be required for two reasons. First, the applicable rules do not adequately specify monitoring requirements (exception- Maximum Achievable Control Technology Standards (MACTs) generally have sufficient monitoring), and second, monitoring may be required to fill gaps in the monitoring requirements of certain applicable requirements. In situations where the NSR permit is the applicable requirement requiring extra monitoring for a specific emission unit, the preferred solution is to have the monitoring requirements in the NSR permit updated so that all NSR requirements are consolidated in the NSR permit.

Permit Shield. A permit may or may not have a permit shield, depending on whether an applicant has applied for, and justified the granting of, a permit shield. A permit shield is a special condition included in the permit document stating that compliance with the conditions of the permit shall be deemed compliance with the specified potentially applicable requirement(s) or specified applicable state-only requirement(s).

New Source Review Authorization References. All activities which are related to emissions in the state of Texas must have a NSR authorization prior to beginning construction. This section lists all units in the permit and the NSR authorization that allowed the unit to be constructed or modified. Units that do not have unit specific applicable requirements other than the NSR authorization do not need to be listed in this attachment. While NSR permits are not physically a part of the Title V permit, they are legally incorporated into the Title V permit by reference. Those NSR permits whose emissions exceed certain PSD/NA thresholds must also undergo a Federal review of federally regulated pollutants in addition to review for state regulated pollutants.

Compliance Plan. A permit may have a compliance schedule attachment for listing corrective actions plans for any emission unit that is out of compliance with an applicable requirement.

Alternative Requirements. This attachment will list any alternative monitoring plans or alternative means of compliance for applicable requirements that have been approved by the EPA Administrator and/or the TCEQ Executive Director.

Appendix A

Acronym list. This attachment lists the common acronyms used when discussing the FOPs.

Appendix B

Copies of major NSR authorizations applicable to the units covered by this permit have been included in this Appendix, to ensure that all interested persons can access those authorizations.

Stationary vents subject to 30 TAC Chapter 111, Subchapter A, § 111.111(a)(1)(B) addressed in the Special Terms and Conditions

The site contains stationary vents with a flowrate less than 100,000 actual cubic feet per minute (acfm) and constructed after January 31, 1972 which are limited, over a six-minute average, to 20% opacity as required by 30 TAC § 111.111(a)(1)(B). As a site may have a large number of stationary vents that fall into this category, they are not required to be listed individually in the permit's Applicable Requirement Summary. This is consistent with EPA's White Paper for Streamlined Development of Part 70 Permit Applications, July 10, 1995, that states that requirements that apply identically to emission units at a site can be treated on a generic basis such as source-wide opacity limits.

Periodic monitoring is specified in Special Term and Condition 3 for stationary vents subject to 30 TAC § 111.111(a)(1)(B) to verify compliance with the 20% opacity limit. These vents are not expected to produce visible emissions during normal operation. The TCEQ evaluated the probability of these sources violating the opacity standards and determined that there is a very low potential that an opacity standard would be exceeded. It was determined that continuous monitoring for these sources is not warranted as there would be very limited environmental benefit in continuously monitoring sources that have a low potential to produce visible emissions. Therefore, the TCEQ set the visible observation monitoring frequency for these sources to once per calendar quarter.

The TCEQ has exempted vents that are not capable of producing visible emissions from periodic monitoring requirements. These vents include sources of colorless VOCs, non-fuming liquids, and other materials that cannot produce emissions that obstruct the transmission of light. Passive ventilation vents, such as plumbing vents, are also included in this category. Since this category of vents are not capable of producing opacity due to the physical or chemical characteristics of the emission source, periodic monitoring is not required as it would not yield any additional data to assure compliance with the 20% opacity standard of 30 TAC § 111.111(a)(1)(B).

In the event that visible emissions are detected, either through the quarterly observation or other credible evidence, such as observations from company personnel, the permit holder shall either report a deviation or perform a Test Method 9 observation to determine the opacity consistent with the 6-minute averaging time specified in 30 TAC § 111.111(a)(1)(B). An additional provision is included to monitor combustion sources more frequently than quarterly if alternate fuels are burned for periods greater than 24 consecutive hours. This will address possible emissions that may arise when switching fuel types.

Stationary Vents subject to 30 TAC Chapter 111 not addressed in the Special Terms and Conditions

All other stationary vents subject to 30 TAC Chapter 111 not covered in the Special Terms and Conditions are listed in the permit's Applicable Requirement Summary. The basis for the applicability determinations for these vents are listed in the Determination of Applicable Requirements table.

Federal Regulatory Applicability Determinations

The following chart summarizes the applicability of the principal air pollution regulatory programs to the permit area:

Regulatory Program	Applicability (Yes/No)
Prevention of Significant Deterioration (PSD)	Yes
Nonattainment New Source Review (NNSR)	No
Minor NSR	Yes
40 CFR Part 60 - New Source Performance Standards	Yes
40 CFR Part 61 - National Emission Standards for Hazardous Air Pollutants (NESHAPs)	Yes
40 CFR Part 63 - NESHAPs for Source Categories	Yes
Title IV (Acid Rain) of the Clean Air Act (CAA)	No
Title V (Federal Operating Permits) of the CAA	Yes
Title VI (Stratospheric Ozone Protection) of the CAA	Yes
CAIR (Clean Air Interstate Rule)	No

Basis for Applying Permit Shields

An operating permit applicant has the opportunity to specifically request a permit shield to document that specific applicable requirements do not apply to emission units in the permit. A permit shield is a special condition stating that compliance with the conditions of the permit shall be deemed compliance with the specified potentially applicable requirements or specified potentially applicable state-only requirements. A permit shield has been requested in the application for specific emission units. For the permit shield requests that have been approved, the basis of determination for regulations that the owner/operator need not comply with are located in the "Permit Shield" attachment of the permit.

Insignificant Activities

In general, units not meeting the criteria for inclusion on either Form OP-SUM or Form OP-REQ1 are not required to be addressed in the operating permit application. Examples of these types of units include, but are not limited to, the following:

1. Office activities such as photocopying, blueprint copying, and photographic processes.
2. Sanitary sewage collection and treatment facilities other than those used to incinerate wastewater treatment plant sludge. Stacks or vents for sanitary sewer plumbing traps are also included.
3. Food preparation facilities including, but not limited to, restaurants and cafeterias used for preparing food or beverages primarily for consumption on the premises.
4. Outdoor barbecue pits, campfires, and fireplaces.
5. Laundry dryers, extractors, and tumblers processing bedding, clothing, or other fabric items generated primarily at the premises. This does not include emissions from dry cleaning systems using perchloroethylene or petroleum solvents.

6. Facilities storing only dry, sweet natural gas, including natural gas pressure regulator vents.
7. Any air separation or other industrial gas production, storage, or packaging facility. Industrial gases, for purposes of this list, include only oxygen, nitrogen, helium, neon, argon, krypton, and xenon.
8. Storage and handling of sealed portable containers, cylinders, or sealed drums.
9. Vehicle exhaust from maintenance or repair shops.
10. Storage and use of non-VOC products or equipment for maintaining motor vehicles operated at the site (including but not limited to, antifreeze and fuel additives).
11. Air contaminant detectors and recorders, combustion controllers and shut-off devices, product analyzers, laboratory analyzers, continuous emissions monitors, other analyzers and monitors, and emissions associated with sampling activities. Exception to this category includes sampling activities that are deemed fugitive emissions and under a regulatory leak detection and repair program.
12. Bench scale laboratory equipment and laboratory equipment used exclusively for chemical and physical analysis, including but not limited to, assorted vacuum producing devices and laboratory fume hoods.
13. Steam vents, steam leaks, and steam safety relief valves, provided the steam (or boiler feedwater) has not contacted other materials or fluids containing regulated air pollutants other than boiler water treatment chemicals.
14. Storage of water that has not contacted other materials or fluids containing regulated air pollutants other than boiler water treatment chemicals.
15. Well cellars.
16. Fire or emergency response equipment and training, including but not limited to, use of fire control equipment including equipment testing and training, and open burning of materials or fuels associated with firefighting training.
17. Crucible or pot furnaces with a brim full capacity of less than 450 cubic inches of any molten metal.
18. Equipment used exclusively for the melting or application of wax.
19. All closed tumblers used for the cleaning or deburring of metal products without abrasive blasting, and all open tumblers with a batch capacity of 1,000 lbs. or less.
20. Shell core and shell mold manufacturing machines.
21. Sand or investment molds with a capacity of 100 lbs. or less used for the casting of metals;
22. Equipment used for inspection of metal products.
23. Equipment used exclusively for rolling, forging, pressing, drawing, spinning, or extruding either hot or cold metals by some mechanical means.
24. Instrument systems utilizing air, natural gas, nitrogen, oxygen, carbon dioxide, helium, neon, argon, krypton, and xenon.
25. Battery recharging areas.
26. Brazing, soldering, or welding equipment.

Determination of Applicable Requirements

The tables below include the applicability determinations for the emission units, the index number(s) where applicable, and all relevant unit attribute information used to form the basis of the applicability determination. The unit attribute information is a description of the physical properties of an emission unit which is used to determine the requirements to which the permit holder must comply. For more information about the descriptions of the unit attributes specific Unit Attribute Forms may be viewed at www.tceq.texas.gov/permitting/air/nav/air_all_ua_forms.html.

A list of unit attribute forms is included at the end of this document. Some examples of unit attributes include construction date; product stored in a tank; boiler fuel type; etc.. Generally, multiple attributes are needed to determine the requirements for a given emission unit and index number. The table below lists these attributes in the column entitled "Basis of Determination." Attributes that demonstrate that an applicable requirement applies will be the factual basis for the specific citations in an applicable requirement that apply to a unit for that index number. The TCEQ Air Permits Division has developed flowcharts for determining applicability of state and federal regulations based on the unit attribute information in a Decision Support System (DSS).

These flowcharts can be accessed via the internet at www.tceq.texas.gov/permitting/air/nav/air_supportsys.html. The Air Permits Division staff may also be contacted for assistance at (512) 239-1250.

The attributes for each unit and corresponding index number provide the basis for determining the specific legal citations in an applicable requirement that apply, including emission limitations or standards, monitoring, recordkeeping, and reporting. The rules were found to apply or not apply by using the unit attributes as answers to decision questions found in the flowcharts of the DSS. Some additional attributes indicate which legal citations of a rule apply. The legal citations that apply to each emission unit may be found in the Applicable Requirements Summary table of the draft permit. There may be some entries or rows of units and rules not found in the permit, or if the permit contains a permit shield, repeated in the permit shield area. These are sets of attributes that describe negative applicability, or; in other words, the reason why a potentially applicable requirement does not apply.

If applicability determinations have been made which differ from the available flowcharts, an explanation of the decisions involved in the applicability determination is specified in the column "Changes and Exceptions to RRT." If there were no exceptions to the DSS, then this column has been removed.

The draft permit includes all emission limitations or standards, monitoring, recordkeeping and reporting required by each applicable requirement. If an applicable requirement does not require monitoring, recordkeeping, or reporting, the word "None" will appear in the Applicable Requirements Summary table. If additional periodic monitoring is required for an applicable requirement, it will be explained in detail in the portion of this document entitled "Rationale for Compliance Assurance Monitoring (CAM)/ Periodic Monitoring Methods Selected."

When attributes demonstrate that a unit is not subject to an applicable requirement, the applicant may request a permit shield for those items. The portion of this document entitled "Basis for Applying Permit Shields" specifies which units, if any, have a permit shield.

Operational Flexibility

When an emission unit has multiple operating scenarios, it will have a different index number associated with each operating condition. This means that units are permitted to operate under multiple operating conditions. The applicable requirements for each operating condition are determined by a unique set of unit attributes. For example, a tank may store two different products at different points in time. The tank may, therefore, need to comply with two distinct sets of requirements, depending on the product that is stored. Both sets of requirements are included in the permit, so that the permit holder may store either product in the tank.

Determination of Applicable Requirements

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
10ENG001	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-1	<p>HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2.</p> <p>Brake HP = Stationary RICE with a brake HP greater than 500 HP.</p> <p>Construction/Reconstruction Date = Commenced construction or reconstruction before December 19, 2002.</p> <p>Service Type = Emergency use where the RICE does not operate or is not contractually obligated to be available for more than 15 hours per calendar year as specified in 40 CFR §63.6640(f)(2)(ii)-(iii) or does not operate as specified in 40 CFR §63.6640(f)(4)(ii).</p>	
10ENG002	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-2	<p>HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2.</p> <p>Brake HP = Stationary RICE with a brake HP greater than 500 HP.</p> <p>Construction/Reconstruction Date = Commenced construction or reconstruction before December 19, 2002.</p> <p>Service Type = Emergency use where the RICE does not operate or is not contractually obligated to be available for more than 15 hours per calendar year as specified in 40 CFR §63.6640(f)(2)(ii)-(iii) or does not operate as specified in 40 CFR §63.6640(f)(4)(ii).</p>	
10SMP048	40 CFR Part 63, Subpart YY	63YY	<p>Source Type = Tank is storing cyanide at a cyanide chemicals manufacturing facility.</p> <p>Subject to §63.1106(e)(3) = Tank is controlled at least as stringently as Table 35 of 40 CFR Part 63, Subpart G.</p>	
10TFX006E	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
10TFX006E	40 CFR Part 61, Subpart FF	61FF-4	<p>Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A car-seal or lock and key configuration are used to secure the by-pass line valve in the closed position.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Flare</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	61.356(j)(11) was deleted from recordkeeping at the applicant's request because alternative monitoring is not used.

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
10TFX006E	40 CFR Part 63, Subpart G	63G-1	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has by-pass lines that are sealed with a carseal or lock and key mechanism</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Flare</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p>	
10TFX009	30 TAC Chapter 115, Storage of VOCs	R5112-4	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p> <p>Control Device Type = Flare</p>	
10TFX009	40 CFR Part 60, Subpart Kb	60KB-3	<p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)</p>	
10TFX009	40 CFR Part 63, Subpart G	63G-1	<p>MACT Subpart F/G Applicability = The unit is a Group 2 vessel.</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.</p>	
10TFX021B	30 TAC Chapter 115, Storage of VOCs	R5112-6	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Flare</p>	
10TFX021B	30 TAC Chapter 115, Storage of VOCs	R5112-7	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Flare</p>	
10TFX021B	40 CFR Part 63, Subpart G	63G-1	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>NSPS Subpart Kb Applicability = The unit is subject to 40 CFR Part 60, Subpart Kb.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Flare</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p>	
10TFX021C	30 TAC Chapter 115, Storage of VOCs	R5112-6	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Flare</p>	
10TFX021C	40 CFR Part 63, Subpart G	63G-1	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>NSPS Subpart Kb Applicability = The unit is subject to 40 CFR Part 60, Subpart Kb.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Flare</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p>	
10TFX035A	30 TAC Chapter 115, Storage of VOCs	R5112-3	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Storage Capacity = Capacity is greater than 40,000 gallons	
10TFX035A	40 CFR Part 63, Subpart G	63G-1	MACT Subpart F/G Applicability = The unit is a Group 2 vessel. NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y. NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.	
10TFX038	40 CFR Part 63, Subpart G	63G-1	MACT Subpart F/G Applicability = The unit is a Group 2 vessel. NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y. NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.	
10TFX039	40 CFR Part 61, Subpart FF	61FF-4	Bypass Line = The closed vent system does not contain any by-pass line that could divert the vent stream away from the control device. Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device. Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF. Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351. Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system. Control Device Type/Operations = Flare Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3). Closed Vent System and Control Device AMOC = Not using an alternate means of compliance Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.	
10TFX039	40 CFR Part 63, Subpart G	63G-15	Process Wastewater = The tank receives, manages, or treats process wastewater streams Wastewater Tank Usage = The wastewater tank is not used for heating wastewater, treating by means of an exothermic reaction, nor are the contents of the tank are sparged. Wastewater Tank Properties = Volume of the wastewater tank is less than 75m ³ and storing liquid with any vapor pressure	
10TFX047	30 TAC Chapter 115, Storage of VOCs	R5112-16	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a submerged fill pipe True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
10TFX047	40 CFR Part 63, Subpart G	63G-1	MACT Subpart F/G Applicability = The unit is a Group 2 vessel. NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y. NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.	
10TFX057	30 TAC Chapter 115, Storage of VOCs	R5112-3	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
10TFX068	30 TAC Chapter 115, Storage of VOCs	R5112-15	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is less than or equal to 1,000 gallons</p>	
10TFX068	40 CFR Part 60, Subpart Kb	60KB-7	<p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)</p>	
10TFX087	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is less than or equal to 1,000 gallons</p>	
10TFX324	40 CFR Part 61, Subpart FF	61FF-4	<p>Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A car-seal or lock and key configuration are used to secure the by-pass line valve in the closed position.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Flare</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
10TFX345	40 CFR Part 61, Subpart FF	61FF-4	<p>Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A car-seal or lock and key configuration are used to secure the by-pass line valve in the closed position.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Flare</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
10TFX350	40 CFR Part 61, Subpart FF	61FF-4	<p>Bypass Line = The closed vent system contains any by-pass line that could divert the vent stream away from the control device.</p> <p>Tank Control Requirements = The tank has a fixed roof and closed vent system routing vapors to either a fuel gas system or control device.</p> <p>Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF.</p> <p>Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351.</p> <p>Bypass Line Valve = A car-seal or lock and key configuration are used to secure the by-pass line valve in the closed position.</p> <p>Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system.</p> <p>Control Device Type/Operations = Flare</p> <p>Cover and Closed Vent = The cover and closed vent system are not operated such that the tank is maintained at a pressure less than atmospheric pressure and meets the conditions of 40 CFR § 61.343(a)(1)(i)(C)(1) - (3).</p> <p>Closed Vent System and Control Device AMOC = Not using an alternate means of compliance</p> <p>Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.</p>	
10WTU237	40 CFR Part 63, Subpart YY	63YY	Source Type = Tank is storing cyanide at a cyanide chemicals manufacturing facility.	
11TFX036	30 TAC Chapter 115, Storage of VOCs	R5112-3	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	
11TFX036	40 CFR Part 60, Subpart Kb	60KB-8	<p>Product Stored = Waste mixture of indeterminate or variable composition</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia</p>	
11TFX036	40 CFR Part 63, Subpart YY	63YY	Source Type = Tank is storing cyanide at a cyanide chemicals manufacturing facility.	
11TFX047	30 TAC Chapter 115, Storage of VOCs	R5112-3	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
11TFX047	40 CFR Part 63, Subpart YY	63YY	Source Type = Tank is storing cyanide at a cyanide chemicals manufacturing facility.	
11TFX048	30 TAC Chapter 115, Storage of VOCs	R5112-3	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons	
11TFX055	30 TAC Chapter 115, Storage of VOCs	R5112-14	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
11TFX055	40 CFR Part 60, Subpart Kb	60KB-9	Product Stored = Waste mixture of indeterminate or variable composition Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)	
11TFX055	40 CFR Part 63, Subpart YY	63YY	Source Type = Tank is storing cyanide at a cyanide chemicals manufacturing facility.	
11TFX064	30 TAC Chapter 115, Storage of VOCs	R5112-5	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons	
11TFX064	40 CFR Part 60, Subpart Kb	60KB-9	Product Stored = Waste mixture of indeterminate or variable composition Storage Capacity = Capacity is greater than or equal to 19,800 gallons (75,000 liters) but less than 39,900 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia	
GRP1oTKo13	30 TAC Chapter 115, Storage of VOCs	R5112-14	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
GRP1oTKo14	30 TAC Chapter 115, Storage of	R5112-15	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	VOCs		compliance with applicable control requirements or exemption criteria. Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is less than or equal to 1,000 gallons	
GRP10TK014	40 CFR Part 60, Subpart Kb	60KB-7	Product Stored = Volatile organic liquid Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)	
GRP10TK032	30 TAC Chapter 115, Storage of VOCs	R5112-15	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is less than or equal to 1,000 gallons	
GRP10TK032	40 CFR Part 60, Subpart Kb	60KB-7	Product Stored = Volatile organic liquid Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)	
GRP10TK035	30 TAC Chapter 115, Storage of VOCs	R5112-3	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons	
GRP10TK036	30 TAC Chapter 115, Storage of VOCs	R5112-14	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	
10LBA061B	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-3	Chapter 115 Facility Type = Marine terminal	
10LBA061B	40 CFR Part 63, Subpart Y	63Y-1	Subpart Y Facility Type = Existing onshore loading terminal (located onshore or less than 0.5 miles from shore). Ballasting Operations = Operations other than or in addition to ballasting operations are performed at the facility. Vapor Pressure = Vapor pressure is less than 10.3 kilopascals (1.5 psia) at standard conditions, 20° C and 760 mm Hg.	
10LBA061C	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-3	Chapter 115 Facility Type = Marine terminal	
10LTR037A	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-1	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal. Alternate Control Requirement (ACR) = No alternate control requirements are being utilized. Product Transferred = Volatile organic compounds other than liquefied petroleum gas, crude oil, condensate and gasoline.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Transfer Type = Only unloading. True Vapor Pressure = True vapor pressure is less than 1.5 psia.	
1oLTR056A	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-1	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal. Alternate Control Requirement (ACR) = No alternate control requirements are being utilized. Product Transferred = Volatile organic compounds other than liquefied petroleum gas, crude oil, condensate and gasoline. Transfer Type = Only loading. True Vapor Pressure = True vapor pressure is less than 1.5 psia.	
1oLTR056A	40 CFR Part 63, Subpart G	63G-1	Transfer Rack Type = Group 2 transfer rack (as defined in 40 CFR § 63.111). Subject to Subpart BB = The transfer rack is subject to 40 CFR Part 61, Subpart BB. Compliance Options = The Group 2 transfer rack is subject to only the reporting and recordkeeping requirements of 40 CFR Part 61, Subpart BB.	
1oLTR056C	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-1	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal. Alternate Control Requirement (ACR) = No alternate control requirements are being utilized. Product Transferred = Volatile organic compounds other than liquefied petroleum gas, crude oil, condensate and gasoline. Transfer Type = Loading and unloading. True Vapor Pressure = True vapor pressure is less than 1.5 psia.	
1oLTR056C	40 CFR Part 61, Subpart BB	61BB-1	Negative Applicability = The loading rack loads materials other than benzene-laden waste, gasoline, crude oil, natural gas liquids, petroleum distillates or benzene-laden liquid from a coke by-product plant. Benzene By Weight = Concentration of benzene by weight in the liquid which is loaded is greater than or equal to 70% benzene by weight. Annual Amount Loaded = Annual amount loaded is less than 1.3 million liters (343,424 gallons).	
1oLTR056C	40 CFR Part 63, Subpart G	63G-7	Transfer Rack Type = Group 2 transfer rack (as defined in 40 CFR § 63.111). Subject to Subpart BB = The transfer rack is subject to 40 CFR Part 61, Subpart BB. Compliance Options = The Group 2 transfer rack is subject to only the reporting and recordkeeping requirements of 40 CFR Part 61, Subpart BB.	
1oLTR061A	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-1	Chapter 115 Control Device Type = Vapor control system with a flare. Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal. Alternate Control Requirement (ACR) = No alternate control requirements are being utilized. Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected. Product Transferred = Volatile organic compounds other than liquefied petroleum gas, crude oil, condensate and gasoline. Transfer Type = Only loading. True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized. Control Options = Vapor control system that maintains a control efficiency of at least 90%.	
10LTR061A	40 CFR Part 61, Subpart BB	61BB-1	Negative Applicability = The loading rack loads materials other than benzene-laden waste, gasoline, crude oil, natural gas liquids, petroleum distillates or benzene-laden liquid from a coke by-product plant. Benzene By Weight = Concentration of benzene by weight in the liquid which is loaded is greater than or equal to 70% benzene by weight. Annual Amount Loaded = Annual amount loaded is less than 1.3 million liters (343,424 gallons).	
10LTR061A	40 CFR Part 63, Subpart G	63G-1	Control Device = Flare. Halogenated Emissions = There are no halogenated emission streams from the transfer rack. Transfer Rack Type = Group 1 transfer rack (as defined in 40 CFR § 63.111). Vapor Balancing System = A vapor balancing system is not being used to reduce emissions of organic hazardous air pollutants. Emissions Routing = Emissions of organic hazardous air pollutants are not routed to a fuel gas system nor to a process where the organic hazardous air pollutants meet one or more of the ends specified in 40 CFR § 63.126(b)(4)(i) - (iv). Bypass Lines = The vent system does not contain by-pass lines that could divert a vent stream flow away from the control device. Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system or is subject to § 63.148 of Subpart G. Hard Piping = The closed vent system is constructed of hard piping.	
10LTR061E	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-1	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal. Alternate Control Requirement (ACR) = No alternate control requirements are being utilized. Product Transferred = Volatile organic compounds other than liquefied petroleum gas, crude oil, condensate and gasoline. Transfer Type = Only loading. True Vapor Pressure = True vapor pressure is less than 1.5 psia.	
10LTR061F	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-1	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal. Alternate Control Requirement (ACR) = No alternate control requirements are being utilized. Vapor Tight = All liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected. Product Transferred = Volatile organic compounds other than liquefied petroleum gas, crude oil, condensate and gasoline. Transfer Type = Only unloading. True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia.	
10LTR072	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-1	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal. Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas, crude oil, condensate and gasoline.</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure is less than 1.5 psia.</p>	
10LTR073	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-1	<p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = All liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas, crude oil, condensate and gasoline.</p> <p>Transfer Type = Only unloading.</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia.</p>	
10LTR073	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-8	<p>Chapter 115 Control Device Type = Vapor control system with a carbon adsorption system.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas, crude oil, condensate and gasoline.</p> <p>Transfer Type = Only loading.</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>	
10LTR073	40 CFR Part 63, Subpart G	63G-9	<p>Transfer Rack Type = Group 2 transfer rack (as defined in 40 CFR § 63.111).</p> <p>Subject to Subpart BB = The transfer rack is not subject to 40 CFR Part 61, Subpart BB.</p>	
10LTR087	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-1	<p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas, crude oil, condensate and gasoline.</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure is less than 1.5 psia.</p>	
GRP10LD001	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-1	<p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas, crude oil, condensate and gasoline. Transfer Type = Only loading. True Vapor Pressure = True vapor pressure is less than 1.5 psia.	
GRP1oLD001	40 CFR Part 61, Subpart BB	61BB-1	Negative Applicability = The loading rack loads materials other than benzene-laden waste, gasoline, crude oil, natural gas liquids, petroleum distillates or benzene-laden liquid from a coke by-product plant. Benzene By Weight = Concentration of benzene by weight in the liquid which is loaded is greater than or equal to 70% benzene by weight. Annual Amount Loaded = Annual amount loaded is less than 1.3 million liters (343,424 gallons).	
GRP1oLD002	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-1	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal. Alternate Control Requirement (ACR) = No alternate control requirements are being utilized. Product Transferred = Volatile organic compounds other than liquefied petroleum gas, crude oil, condensate and gasoline. Transfer Type = Only loading. True Vapor Pressure = True vapor pressure is less than 1.5 psia.	
GRP1oLD002	40 CFR Part 63, Subpart G	63G-1	Transfer Rack Type = Group 2 transfer rack (as defined in 40 CFR § 63.111). Subject to Subpart BB = The transfer rack is subject to 40 CFR Part 61, Subpart BB. Compliance Options = The Group 2 transfer rack is subject to only the reporting and recordkeeping requirements of 40 CFR Part 61, Subpart BB.	
GRP1oLD003	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-1	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal. Alternate Control Requirement (ACR) = No alternate control requirements are being utilized. Product Transferred = Volatile organic compounds other than liquefied petroleum gas, crude oil, condensate and gasoline. Transfer Type = Only unloading. True Vapor Pressure = True vapor pressure is less than 1.5 psia.	
GRP1oLD005	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-1	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal. Alternate Control Requirement (ACR) = No alternate control requirements are being utilized. Product Transferred = Volatile organic compounds other than liquefied petroleum gas, crude oil, condensate and gasoline. Transfer Type = Only loading. True Vapor Pressure = True vapor pressure is less than 1.5 psia.	
1oFLR004	30 TAC Chapter 111, Visible Emissions	R1111-1	Acid Gases Only = Flare is not used only as an acid gas flare as defined in 30 TAC § 101.1. Emergency/Upset Conditions Only = Flare is used under conditions other than emergency or upset conditions. Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
1oFLR004	40 CFR Part 60, Subpart A	60A-2	Subject to 40 CFR § 60.18 = Flare is not subject to 40 CFR § 60.18.	
1oFLR004	40 CFR Part 63, Subpart A	63A-2	Required Under 40 CFR Part 63 = Flare is required by a Subpart under 40 CFR Part 63. Heat Content Specification = Adhering to the heat content specifications in 40 CFR § 63.11(b)(6)(ii) and the maximum tip velocity specifications in 40 CFR § 63.11(b)(7) or 40 CFR § 63.11(b)(8). Flare Assist Type = Non-assisted Flare Exit Velocity = Flare exit velocity is less than 60 ft/s (18.3 m/sec)	
1oFLR004A	30 TAC Chapter 111, Visible Emissions	R1111-1	Acid Gases Only = Flare is not used only as an acid gas flare as defined in 30 TAC § 101.1. Emergency/Upset Conditions Only = Flare is used under conditions other than emergency or upset conditions. Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.	
1oFLR004B	30 TAC Chapter 111, Visible Emissions	R1111-1	Acid Gases Only = Flare is not used only as an acid gas flare as defined in 30 TAC § 101.1. Emergency/Upset Conditions Only = Flare is used under conditions other than emergency or upset conditions. Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.	
1oFLR004C	30 TAC Chapter 111, Visible Emissions	R1111-1	Acid Gases Only = Flare is not used only as an acid gas flare as defined in 30 TAC § 101.1. Emergency/Upset Conditions Only = Flare is used under conditions other than emergency or upset conditions. Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.	
1oFLR005	30 TAC Chapter 111, Visible Emissions	R1111-1	Acid Gases Only = Flare is not used only as an acid gas flare as defined in 30 TAC § 101.1. Emergency/Upset Conditions Only = Flare is used under conditions other than emergency or upset conditions. Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.	
1oFLR005	40 CFR Part 60, Subpart A	60A-2	Subject to 40 CFR § 60.18 = Flare is subject to 40 CFR § 60.18. Adhering to Heat Content Specifications = Adhering to the heat content specifications in 40 CFR § 60.18(c)(3)(ii) and the maximum tip velocity specifications in 40 CFR § 60.18(c)(4). Flare Assist Type = Non-assisted Flare Exit Velocity = Flare exit velocity is less than 60 ft/s (18.3 m/sec)	
1oFLR005	40 CFR Part 60, Subpart A	60A-3	Subject to 40 CFR § 60.18 = Flare is subject to 40 CFR § 60.18. Adhering to Heat Content Specifications = Adhering to the requirements in 40 CFR § 60.18(c)(3)(i).	
1oFLR005	40 CFR Part 63, Subpart A	63A-2	Required Under 40 CFR Part 63 = Flare is required by a Subpart under 40 CFR Part 63. Heat Content Specification = Adhering to the heat content specifications in 40 CFR § 63.11(b)(6)(ii) and the maximum tip velocity specifications in 40 CFR § 63.11(b)(7) or 40 CFR § 63.11(b)(8). Flare Assist Type = Non-assisted Flare Exit Velocity = Flare exit velocity is less than 60 ft/s (18.3 m/sec)	
1oFLR005	40 CFR Part 63, Subpart A	63A-3	Required Under 40 CFR Part 63 = Flare is required by a Subpart under 40 CFR Part 63. Heat Content Specification = Adhering to the heat content specifications in 40 CFR § 63.11(b)(6)(i).	
GRP1oFLR01	30 TAC Chapter 111, Visible Emissions	R1111-1	Acid Gases Only = Flare is not used only as an acid gas flare as defined in 30 TAC § 101.1. Emergency/Upset Conditions Only = Flare is used under conditions other than emergency or upset conditions.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.	
GRP10FLR01	40 CFR Part 63, Subpart A	63A-1	Required Under 40 CFR Part 63 = Flare is required by a Subpart under 40 CFR Part 63. Heat Content Specification = Adhering to the heat content specifications in 40 CFR § 63.11(b)(6)(ii) and the maximum tip velocity specifications in 40 CFR § 63.11(b)(7) or 40 CFR § 63.11(b)(8). Flare Assist Type = Non-assisted Flare Exit Velocity = Flare exit velocity is less than 60 ft/s (18.3 m/sec)	
GRP10FLR01	40 CFR Part 63, Subpart A	63A-2	Required Under 40 CFR Part 63 = Flare is required by a Subpart under 40 CFR Part 63. Heat Content Specification = Adhering to the heat content specifications in 40 CFR § 63.11(b)(6)(i).	
10FUG	40 CFR Part 60, Subpart KKK	60KKK-ALL	SOP/GOP Index No. = OWNER/OPERATOR ASSUMES FUGITIVE CONTROL REQUIREMENTS FOR ALL COMPONENTS IN VOC SERVICE SUBJECT TO NSPS KKK WITH NO ALTERNATE CONTROL OR CONTROL DEVICE Facility Type = Affected facility is the group of all equipment except compressors within a process unit. Construction/Modification Date = After January 20, 1984 and on or before August 23, 2011. Facility Covered by 40 CFR Part 60, Subparts VV or GGG = Facility not covered by NSPS Subpart VV or Subpart GGG or NESHAP Subpart V. Control Devices Used to Comply With AMEL = No control devices used to comply with AMEL. Flare = No flare control device addressed in 40 CFR 60 (NSPS) Subpart KKK.	
10FUG	40 CFR Part 60, Subpart VVa	60VVa-1	OWNER/OPERATOR ASSUMES VOC FUGITIVE CONTROL REQUIREMENTS FOR ALL COMPONENTS SUBJECT TO NSPS VVA WITH NO ALTERNATE CONTROL OR CONTROL DEVICE	The rule citations were determined from an analysis of the rule text and the basis of determination.
10FUG	40 CFR Part 63, Subpart H	63H-1	ANY (CLOSED VENT SYSTEMS) = COMPONENT NOT PRESENT ANY (OPEN-ENDED VALVES OR LINES) = COMPONENT NOT PRESENT ENCLOSED-VENTED PROCESS UNIT AMEL = UNIT DOES NOT CONTAIN A TOTALLY ENCLOSED VENTED PROCESS UNIT COMPLYING WITH AN ALTERNATE MEANS OF EMISSION LIMITATION IN § 63.179 EQUIPMENT TYPE = FUGITIVE UNIT CONTAINS EQUIPMENT LISTED IN 40 CFR § 63.160(A) WHICH IS OPERATED IN ORGANIC HAZARDOUS AIR POLLUTANT SERVICE GAS/VAPOR OR LIGHT LIQUID SERVICE (AGITATORS) = COMPONENT PRESENT LIGHT LIQUID SERVICE (PUMPS) = COMPONENT PRESENT HEAVY LIQUID SERVICE (AGITATORS) = COMPONENT PRESENT HEAVY LIQUID SERVICE (OPEN-ENDED VALVES OR LINES) = COMPONENT PRESENT HEAVY LIQUID SERVICE (PUMPS) = COMPONENT PRESENT NON RESEARCH AND DEVELOPMENT/BATCH PROCESSES = FUGITIVE UNIT CONTAINS PROCESSES OTHER THAN RESEARCH AND DEVELOPMENT FACILITIES AND BENCH-SCALE BATCH PROCESSES RECOVERY OR RECAPTURE DEVICES (CLOSED VENT SYSTEMS) = COMPONENT NOT PRESENT ANY (INSTRUMENTATION SYSTEMS) = COMPONENT NOT PRESENT BATCH PROCESS AMEL = UNIT DOES NOT CONTAIN A BATCH PROCESS UNIT COMPLYING WITH AN ALTERNATE MEANS OF EMISSION LIMITATION IN § 63.178 GAS/VAPOR OR LIGHT LIQUID SERVICE (VALVES) = COMPONENT PRESENT QIP = UNIT DOES NOT OPT TO COMPLY WITH A QUALITY IMPROVEMENT PROGRAM FOR PUMPS	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>VACUUM SERVICE = NOT ALL OF THE EQUIPMENT IN THE FUGITIVE UNIT IS IN VACUUM SERVICE ANY (COMPRESSORS) = COMPONENT NOT PRESENT EMPLOYEE NUMBER = THE CORPORATION EMPLOYS 100 OR MORE PERSONS ENCLOSED COMBUSTION DEVICES (CLOSED VENT SYSTEMS) = COMPONENT NOT PRESENT HEAVY LIQUID SERVICE (INSTRUMENTATION SYSTEMS) = COMPONENT PRESENT HEAVY LIQUID SERVICE (VALVES) = COMPONENT PRESENT LESS THAN 300 OPERATING HOURS = THE FUGITIVE UNIT DOES NOT CONTAIN ANY EQUIPMENT IN ORGANIC HAZARDOUS AIR POLLUTANT (HAP) SERVICE THAT IS INTENDED TO OPERATE LESS THAN 300 HOURS PER CALENDAR YEAR ANY (SURGE CONTROL VESSELS OR BOTTOMS RECEIVERS) = COMPONENT PRESENT GAS VAPOR SERVICE (PRESSURE RELIEF DEVICES) = COMPONENT PRESENT QIP = UNIT DOES NOT OPT TO COMPLY WITH A QUALITY IMPROVEMENT PROGRAM FOR VALVES AMEL = FUGITIVE UNIT SOURCE OWNER/OPERATOR IS NOT ELECTING TO COMPLY WITH AN ALTERNATIVE MEANS OF EMISSION LIMITATION (AMEL) FLARES (CLOSED VENT SYSTEMS) = COMPONENT NOT PRESENT GAS/VAPOR OR LIGHT LIQUID SERVICE (CONNECTORS) = COMPONENT PRESENT GENERAL AMEL = UNIT IS NOT COMPLYING WITH AN ALTERNATE MEANS OF EMISSION LIMITATION UNDER § 63.177 HEAVY LIQUID SERVICE (SURGE CONTROL VESSELS OR BOTTOMS RECEIVERS) = COMPONENT PRESENT LIQUID SERVICE (PRESSURE RELIEF DEVICES) = COMPONENT PRESENT HEAVY LIQUID SERVICE (CONNECTORS) = COMPONENT PRESENT HEAVY LIQUID SERVICE (PRESSURE RELIEF DEVICES) = COMPONENT PRESENT ANY (SAMPLING CONNECTION SYSTEMS) = COMPONENT PRESENT HEAVY LIQUID SERVICE (SAMPLING CONNECTION SYSTEMS) = COMPONENT PRESENT UNITS WITHOUT AMEL = FUGITIVE UNIT EQUIPMENT OR PROCESS UNITS ARE NOT COMPLYING WITH AN ALTERNATE MEANS OF EMISSION LIMITATION.</p>	
10FUG	40 CFR Part 63, Subpart YY	63YY	<p>Source Type = Cyanide Chemicals Production. Equipment Type = The fugitive unit contains equipment, as defined in § 63.1101, contactin hazardous air pollutants in Tables 1 through 7 or Table 9, as appropriate.</p>	
10FUG2	40 CFR Part 60, Subpart VVa	60VVa-1	OWNER/OPERATOR ASSUMES VOC FUGITIVE CONTROL REQUIREMENTS FOR ALL COMPONENTS SUBJECT TO NSPS VVA WITH NO ALTERNATE CONTROL OR CONTROL DEVICE	The rule citations were determined from an analysis of the rule text and the basis of determination.
10FUG2	40 CFR Part 63, Subpart H	63H-1	<p>ANY (CLOSED VENT SYSTEMS) = COMPONENT NOT PRESENT ANY (OPEN-ENDED VALVES OR LINES) = COMPONENT NOT PRESENT ENCLOSED-VENTED PROCESS UNIT AMEL = UNIT DOES NOT CONTAIN A TOTALLY ENCLOSED VENTED PROCESS UNIT COMPLYING WITH AN ALTERNATE MEANS OF EMISSION LIMITATION IN § 63.179 EQUIPMENT TYPE = FUGITIVE UNIT CONTAINS EQUIPMENT LISTED IN 40 CFR § 63.160(A) WHICH IS OPERATED IN ORGANIC HAZARDOUS AIR POLLUTANT SERVICE</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>GAS/VAPOR OR LIGHT LIQUID SERVICE (AGITATORS) = COMPONENT PRESENT</p> <p>LIGHT LIQUID SERVICE (PUMPS) = COMPONENT PRESENT</p> <p>HEAVY LIQUID SERVICE (AGITATORS) = COMPONENT PRESENT</p> <p>HEAVY LIQUID SERVICE (OPEN-ENDED VALVES OR LINES) = COMPONENT PRESENT</p> <p>HEAVY LIQUID SERVICE (PUMPS) = COMPONENT PRESENT</p> <p>NON RESEARCH AND DEVELOPMENT/BATCH PROCESSES = FUGITIVE UNIT CONTAINS PROCESSES OTHER THAN RESEARCH AND DEVELOPMENT FACILITIES AND BENCH-SCALE BATCH PROCESSES</p> <p>RECOVERY OR RECAPTURE DEVICES (CLOSED VENT SYSTEMS) = COMPONENT NOT PRESENT</p> <p>ANY (INSTRUMENTATION SYSTEMS) = COMPONENT NOT PRESENT</p> <p>BATCH PROCESS AMEL = UNIT DOES NOT CONTAIN A BATCH PROCESS UNIT COMPLYING WITH AN ALTERNATE MEANS OF EMISSION LIMITATION IN § 63.178</p> <p>GAS/VAPOR OR LIGHT LIQUID SERVICE (VALVES) = COMPONENT PRESENT</p> <p>QIP = UNIT DOES NOT OPT TO COMPLY WITH A QUALITY IMPROVEMENT PROGRAM FOR PUMPS</p> <p>VACUUM SERVICE = NOT ALL OF THE EQUIPMENT IN THE FUGITIVE UNIT IS IN VACUUM SERVICE</p> <p>ANY (COMPRESSORS) = COMPONENT NOT PRESENT</p> <p>EMPLOYEE NUMBER = THE CORPORATION EMPLOYS 100 OR MORE PERSONS</p> <p>ENCLOSED COMBUSTION DEVICES (CLOSED VENT SYSTEMS) = COMPONENT NOT PRESENT</p> <p>HEAVY LIQUID SERVICE (INSTRUMENTATION SYSTEMS) = COMPONENT PRESENT</p> <p>HEAVY LIQUID SERVICE (VALVES) = COMPONENT PRESENT</p> <p>LESS THAN 300 OPERATING HOURS = THE FUGITIVE UNIT DOES NOT CONTAIN ANY EQUIPMENT IN ORGANIC HAZARDOUS AIR POLLUTANT (HAP) SERVICE THAT IS INTENDED TO OPERATE LESS THAN 300 HOURS PER CALENDAR YEAR</p> <p>ANY (SURGE CONTROL VESSELS OR BOTTOMS RECEIVERS) = COMPONENT PRESENT</p> <p>GAS VAPOR SERVICE (PRESSURE RELIEF DEVICES) = COMPONENT PRESENT</p> <p>QIP = UNIT DOES NOT OPT TO COMPLY WITH A QUALITY IMPROVEMENT PROGRAM FOR VALVES</p> <p>AMEL = FUGITIVE UNIT SOURCE OWNER/OPERATOR IS NOT ELECTING TO COMPLY WITH AN ALTERNATIVE MEANS OF EMISSION LIMITATION (AMEL)</p> <p>FLARES (CLOSED VENT SYSTEMS) = COMPONENT NOT PRESENT</p> <p>GAS/VAPOR OR LIGHT LIQUID SERVICE (CONNECTORS) = COMPONENT PRESENT</p> <p>GENERAL AMEL = UNIT IS NOT COMPLYING WITH AN ALTERNATE MEANS OF EMISSION LIMITATION UNDER § 63.177</p> <p>HEAVY LIQUID SERVICE (SURGE CONTROL VESSELS OR BOTTOMS RECEIVERS) = COMPONENT PRESENT</p> <p>LIQUID SERVICE (PRESSURE RELIEF DEVICES) = COMPONENT PRESENT</p> <p>HEAVY LIQUID SERVICE (CONNECTORS) = COMPONENT PRESENT</p> <p>HEAVY LIQUID SERVICE (PRESSURE RELIEF DEVICES) = COMPONENT PRESENT</p> <p>ANY (SAMPLING CONNECTION SYSTEMS) = COMPONENT PRESENT</p> <p>HEAVY LIQUID SERVICE (SAMPLING CONNECTION SYSTEMS) = COMPONENT PRESENT</p> <p>UNITS WITHOUT AMEL = FUGITIVE UNIT EQUIPMENT OR PROCESS UNITS ARE NOT COMPLYING WITH</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			AN ALTERNATE MEANS OF EMISSION LIMITATION.	
10FUGMSS2	40 CFR Part 63, Subpart H	63H-2	EQUIPMENT TYPE = FUGITIVE UNIT DOES NOT CONTAIN EQUIPMENT LISTED IN 40 CFR § 63.160(A) WHICH IS OPERATED IN ORGANIC HAZARDOUS AIR POLLUTANT SERVICE	
10CLT040	40 CFR Part 63, Subpart Q	63Q-1	Used Compounds Containing Chromium on or After September 8, 1994 = The industrial process cooling tower has not used compounds containing chromium on or after September 8, 1994.	
10SEP251	30 TAC Chapter 115, Water Separation	R5131-2	Alternate Control Requirement = The executive director (or the EPA Administrator) has not approved an ACR or exemption criteria in accordance with 30 TAC § 115.910. Exemption = Any single or multiple compartment VOC water separator which separates materials having a TVP less than 1.5 psia (10.3 kPa) obtained from any equipment.	
10SEP252	30 TAC Chapter 115, Water Separation	R5131-1	Alternate Control Requirement = The executive director (or the EPA Administrator) has not approved an ACR or exemption criteria in accordance with 30 TAC § 115.910. Exemption = Water separator does not qualify for exemption. Emission Control Option = Vapor recovery system which satisfies the provisions of 30 TAC § 115.131. Control Device = Control device or vapor recovery system other than a chiller, carbon adsorber, or incinerator.	
10SEP303	30 TAC Chapter 115, Water Separation	R5131-1	Alternate Control Requirement = The executive director (or the EPA Administrator) has not approved an ACR or exemption criteria in accordance with 30 TAC § 115.910. Exemption = Water separator does not qualify for exemption. Emission Control Option = Vapor recovery system which satisfies the provisions of 30 TAC § 115.131. Control Device = Control device or vapor recovery system other than a chiller, carbon adsorber, or incinerator.	
10SEP303	40 CFR Part 61, Subpart FF	61FF-1	Alternate Means of Compliance = NO By-Pass Line = THE CLOSED VENT SYSTEM HAS NO BY-PASS LINE Alternative Standards for Oil-Water Separator = NO Control Device Type/Operation = FLARE Fuel Gas System = EMISSIONS ARE ROUTED TO A CONTROL DEVICE Cover and Closed Vent = CLOSED VENT SYSTEM IS OPERATED SUCH THAT THE OIL-WATER SEPARATOR IS MAINTAINED AT NON-NEGATIVE PRESSURE (GREATER THAN ATMOSPHERIC) Close Vent System and Control Device AMOC = COMPLYING WITH THE REQUIREMENTS OF § 61.349	61.356(j)(11) was deleted from recordkeeping at the applicant's request because alternative monitoring is not used.
11SEP055A	30 TAC Chapter 115, Water Separation	R5131-2	Alternate Control Requirement = The executive director (or the EPA Administrator) has not approved an ACR or exemption criteria in accordance with 30 TAC § 115.910. Exemption = Any single or multiple compartment VOC water separator which separates materials having a TVP less than 1.5 psia (10.3 kPa) obtained from any equipment.	
11SEP055A	40 CFR Part 63, Subpart YY	63YY-1	Facility Type = CYANIDE CHEMICALS PRODUCTION FACILITY Process Wastewater = OIL-WATER SEPARATOR RECEIVES, MANAGES OR TREATS A PROCESS WASTEWATER STREAM AS DEFINED IN 40 CFR § 63.1101 Meets 40 CFR § 63.149(d) = OIL-WATER SEPARATOR DOES NOT MEET THE CRITERIA OF 40 CFR § 63.1106(C)(3) OR (C)(4)(I)	
10DIS243	30 TAC Chapter 115, Vent Gas	R5121-3	Alternate Control Requirement = Alternate control is not used.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	Controls		<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Vent gas stream emissions of the specified classes of VOCs including aldehydes, alcohols, aromatics, ethers, olefins, peroxides, amines, acids, esters, ketones, sulfides, and branched chain hydrocarbons (C8 and above).</p>	
10DIS243	40 CFR Part 63, Subpart G	63G-13	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Flare</p> <p>Overlap = Title 40 CFR Part 60, Subpart NNN</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>By-pass Lines = The vent system contains by-pass lines that can divert the vent stream from the control device.</p> <p>Flow Indicator = By-pass line valve is secured with a car-seal or lock-and-key type configuration.</p>	
10DIS245	30 TAC Chapter 115, Vent Gas Controls	R5121-2	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Vent gas steam emissions of the specific VOCs ethylene, butadiene, isobutylene, styrene, isoprene, propylene, and/or methylstyrene.</p>	
10DIS245	40 CFR Part 63, Subpart G	63G-13	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Flare</p> <p>Overlap = Title 40 CFR Part 60, Subpart NNN</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>By-pass Lines = The vent system contains by-pass lines that can divert the vent stream from the control device.</p> <p>Flow Indicator = By-pass line valve is secured with a car-seal or lock-and-key type configuration.</p>	
10DSY206	30 TAC Chapter 111, Visible Emissions	R1111-1	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is from colorless VOCs, non-fuming liquids, or other sources that are not</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>capable of producing visible emissions. Periodic monitoring to demonstrate compliance is not required.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = After January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.</p>	
10DSY206	30 TAC Chapter 115, Vent Gas Controls	R5121-3	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Vent gas stream emissions of the specified classes of VOCs including aldehydes, alcohols, aromatics, ethers, olefins, peroxides, amines, acids, esters, ketones, sulfides, and branched chain hydrocarbons (C8 and above).</p>	
10DSY206	30 TAC Chapter 115, Vent Gas Controls	R5121-8	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Vapor recovery system, as defined in 30 TAC § 115.10, other than an afterburner, blast furnace combustion device, boiler, catalytic or direct flame incinerator, carbon adsorption system, chiller, flare or vapor combustor.</p> <p>Vent Type = Vent gas stream emissions of the specified classes of VOCs including aldehydes, alcohols, aromatics, ethers, olefins, peroxides, amines, acids, esters, ketones, sulfides, and branched chain hydrocarbons (C8 and above).</p>	
10DSY206	30 TAC Chapter 115, Vent Gas Controls	R5121-9	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Vapor recovery system, as defined in 30 TAC § 115.10, other than an afterburner, blast furnace combustion device, boiler, catalytic or direct flame incinerator, carbon adsorption system, chiller, flare or vapor combustor.</p> <p>Vent Type = Vent gas stream emissions of the specified classes of VOCs including aldehydes, alcohols, aromatics, ethers, olefins, peroxides, amines, acids, esters, ketones, sulfides, and branched chain hydrocarbons (C8 and above).</p>	
10DSY206	40 CFR Part 63, Subpart YY	63YY	Source Type = Cyanide chemical production	
10DSY208	30 TAC Chapter	R5121-3	Alternate Control Requirement = Alternate control is not used.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	115, Vent Gas Controls		<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Vent gas steam emissions of the specific VOCs ethylene, butadiene, isobutylene, styrene, isoprene, propylene, and/or methylstyrene.</p>	
10DSY208	40 CFR Part 63, Subpart G	63G-12	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Flare</p> <p>Overlap = Title 40 CFR Part 60, Subpart NNN</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>By-pass Lines = The vent system does not contain by-pass lines that can divert the vent stream from the control device.</p>	
10DSY215	30 TAC Chapter 115, Vent Gas Controls	R5121-2	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Vent gas steam emissions of the specific VOCs ethylene, butadiene, isobutylene, styrene, isoprene, propylene, and/or methylstyrene.</p>	
10DSY215	40 CFR Part 63, Subpart G	63G-13	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Flare</p> <p>Overlap = Title 40 CFR Part 60, Subpart NNN</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>By-pass Lines = The vent system does not contain by-pass lines that can divert the vent stream from the control device.</p>	
10DSY216	30 TAC Chapter 115, Vent Gas Controls	R5121-3	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Vent gas steam emissions of the specific VOCs ethylene, butadiene, isobutylene, styrene, isoprene, propylene, and/or methylstyrene.</p>	
10DSY216	40 CFR Part 63, Subpart G	63G-12	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Flare</p> <p>Overlap = Title 40 CFR Part 60, Subpart NNN</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>By-pass Lines = The vent system does not contain by-pass lines that can divert the vent stream from the control device.</p>	
10DSY217	30 TAC Chapter 115, Vent Gas Controls	R5121-3	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Vent gas steam emissions of the specific VOCs ethylene, butadiene, isobutylene, styrene, isoprene, propylene, and/or methylstyrene.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is greater than 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 30,000 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.</p>	
10DSY217	40 CFR Part 63, Subpart G	63G-12	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Flare</p> <p>Overlap = Title 40 CFR Part 60, Subpart NNN</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>By-pass Lines = The vent system contains by-pass lines that can divert the vent stream from the control device.</p> <p>Flow Indicator = By-pass line valve is secured with a car-seal or lock-and-key type configuration.</p>	
10DSY226PV	30 TAC Chapter 115, Vent Gas	R5121-3	Alternate Control Requirement = Alternate control is not used.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	Controls		<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Vent gas steam emissions of the specific VOCs ethylene, butadiene, isobutylene, styrene, isoprene, propylene, and/or methylstyrene.</p>	
10DSY230	30 TAC Chapter 115, Vent Gas Controls	R5121-3	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Vent gas stream emissions of the specified classes of VOCs including aldehydes, alcohols, aromatics, ethers, olefins, peroxides, amines, acids, esters, ketones, sulfides, and branched chain hydrocarbons (C8 and above).</p>	
10DSY230	40 CFR Part 63, Subpart G	63G-13	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Flare</p> <p>Overlap = Title 40 CFR Part 60, Subpart NNN</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>By-pass Lines = The vent system does not contain by-pass lines that can divert the vent stream from the control device.</p>	
10MSV260	30 TAC Chapter 111, Visible Emissions	R1111-1	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is from colorless VOCs, non-fuming liquids, or other sources that are not capable of producing visible emissions. Periodic monitoring to demonstrate compliance is not required.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = After January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.</p>	
10MSV260	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Control Device Type = Smokeless flare</p> <p>Vent Type = Vent gas steam emissions of the specific VOCs ethylene, butadiene, isobutylene, styrene, isoprene, propylene, and/or methylstyrene.</p>	
10MSV260	30 TAC Chapter 115, Vent Gas Controls	R5121-6	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Vapor recovery system, as defined in 30 TAC § 115.10, other than an afterburner, blast furnace combustion device, boiler, catalytic or direct flame incinerator, carbon adsorption system, chiller, flare or vapor combustor.</p> <p>Vent Type = Vent gas steam emissions of the specific VOCs ethylene, butadiene, isobutylene, styrene, isoprene, propylene, and/or methylstyrene.</p>	
10MSV260	30 TAC Chapter 115, Vent Gas Controls	R5121-7	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Vapor recovery system, as defined in 30 TAC § 115.10, other than an afterburner, blast furnace combustion device, boiler, catalytic or direct flame incinerator, carbon adsorption system, chiller, flare or vapor combustor.</p> <p>Vent Type = Vent gas steam emissions of the specific VOCs ethylene, butadiene, isobutylene, styrene, isoprene, propylene, and/or methylstyrene.</p>	
10MSV260	30 TAC Chapter 115, Vent Gas Controls	R5121-8	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Vapor recovery system, as defined in 30 TAC § 115.10, other than an afterburner, blast furnace combustion device, boiler, catalytic or direct flame incinerator, carbon adsorption system, chiller, flare or vapor combustor.</p> <p>Vent Type = Vent gas steam emissions of the specific VOCs ethylene, butadiene, isobutylene, styrene, isoprene, propylene, and/or methylstyrene.</p>	
10MSV260	30 TAC Chapter 115, Vent Gas Controls	R5121-9	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Vapor recovery system, as defined in 30 TAC § 115.10, other than an afterburner, blast furnace combustion device, boiler, catalytic or direct flame incinerator, carbon adsorption system, chiller, flare or</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>vapor combustor.</p> <p>Vent Type = Vent gas steam emissions of the specific VOCs ethylene, butadiene, isobutylene, styrene, isoprene, propylene, and/or methylstyrene.</p>	
10MSV261	30 TAC Chapter 111, Visible Emissions	R1111-1	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is from colorless VOCs, non-fuming liquids, or other sources that are not capable of producing visible emissions. Periodic monitoring to demonstrate compliance is not required.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = After January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.</p>	
10MSV261	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Vent gas steam emissions of the specific VOCs ethylene, butadiene, isobutylene, styrene, isoprene, propylene, and/or methylstyrene.</p>	
10MSV261	30 TAC Chapter 115, Vent Gas Controls	R5121-6	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Vapor recovery system, as defined in 30 TAC § 115.10, other than an afterburner, blast furnace combustion device, boiler, catalytic or direct flame incinerator, carbon adsorption system, chiller, flare or vapor combustor.</p> <p>Vent Type = Vent gas steam emissions of the specific VOCs ethylene, butadiene, isobutylene, styrene, isoprene, propylene, and/or methylstyrene.</p>	
10MSV261	30 TAC Chapter 115, Vent Gas Controls	R5121-7	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Vapor recovery system, as defined in 30 TAC § 115.10, other than an afterburner, blast furnace combustion device, boiler, catalytic or direct flame incinerator, carbon adsorption system, chiller, flare or vapor combustor.</p> <p>Vent Type = Vent gas steam emissions of the specific VOCs ethylene, butadiene, isobutylene, styrene, isoprene, propylene, and/or methylstyrene.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
10MSV261	30 TAC Chapter 115, Vent Gas Controls	R5121-8	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Vapor recovery system, as defined in 30 TAC § 115.10, other than an afterburner, blast furnace combustion device, boiler, catalytic or direct flame incinerator, carbon adsorption system, chiller, flare or vapor combustor.</p> <p>Vent Type = Vent gas steam emissions of the specific VOCs ethylene, butadiene, isobutylene, styrene, isoprene, propylene, and/or methylstyrene.</p>	
10MSV261	30 TAC Chapter 115, Vent Gas Controls	R5121-9	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Vapor recovery system, as defined in 30 TAC § 115.10, other than an afterburner, blast furnace combustion device, boiler, catalytic or direct flame incinerator, carbon adsorption system, chiller, flare or vapor combustor.</p> <p>Vent Type = Vent gas steam emissions of the specific VOCs ethylene, butadiene, isobutylene, styrene, isoprene, propylene, and/or methylstyrene.</p>	
10NGP	30 TAC Chapter 115, Vent Gas Controls	R5121-3	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Vent gas stream emissions of the specified classes of VOCs including aldehydes, alcohols, aromatics, ethers, olefins, peroxides, amines, acids, esters, ketones, sulfides, and branched chain hydrocarbons (C8 and above).</p>	
10RCT201A	30 TAC Chapter 115, Vent Gas Controls	R5121-2	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Vent gas steam emissions of the specific VOCs ethylene, butadiene, isobutylene, styrene, isoprene, propylene, and/or methylstyrene.</p>	
10RCT201A	40 CFR Part 63, Subpart G	63G-12	Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Control Device = Flare</p> <p>Overlap = Title 40 CFR Part 60, Subpart RRR</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>By-pass Lines = The vent system does not contain by-pass lines that can divert the vent stream from the control device.</p>	
10RCT222	30 TAC Chapter 115, Vent Gas Controls	R5121-2	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Vent gas steam emissions of the specific VOCs ethylene, butadiene, isobutylene, styrene, isoprene, propylene, and/or methylstyrene.</p>	
10RCT222	40 CFR Part 63, Subpart G	63G-12	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Flare</p> <p>Overlap = Title 40 CFR Part 60, Subpart RRR</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>By-pass Lines = The vent system does not contain by-pass lines that can divert the vent stream from the control device.</p>	
10RCT223	30 TAC Chapter 115, Vent Gas Controls	R5121-3	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Vent gas stream emissions of the specified classes of VOCs including aldehydes, alcohols, aromatics, ethers, olefins, peroxides, amines, acids, esters, ketones, sulfides, and branched chain hydrocarbons (C8 and above).</p>	
10RCT223	40 CFR Part 63, Subpart G	63G-12	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Flare</p> <p>Overlap = Title 40 CFR Part 60, Subpart RRR</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>By-pass Lines = The vent system does not contain by-pass lines that can divert the vent stream from the control device.</p>	
10RSY201	30 TAC Chapter 115, Vent Gas Controls	R5121-2	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Vent gas steam emissions of the specific VOCs ethylene, butadiene, isobutylene, styrene, isoprene, propylene, and/or methylstyrene.</p>	
10RSY201	40 CFR Part 63, Subpart G	63G-12	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Flare</p> <p>Overlap = Title 40 CFR Part 60, Subpart RRR</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>By-pass Lines = The vent system does not contain by-pass lines that can divert the vent stream from the control device.</p>	
10RSY219-1	30 TAC Chapter 115, Vent Gas Controls	R5121-2	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Vent gas stream emissions of the specified classes of VOCs including aldehydes, alcohols, aromatics, ethers, olefins, peroxides, amines, acids, esters, ketones, sulfides, and branched chain hydrocarbons (C8 and above).</p>	
10RSY219-1	40 CFR Part 63, Subpart YY	63YY	Source Type = Cyanide chemical production	
10RSY219-2	30 TAC Chapter 115, Vent Gas Controls	R5121-2	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2. Control Device Type = Smokeless flare Vent Type = Vent gas stream emissions of the specified classes of VOCs including aldehydes, alcohols, aromatics, ethers, olefins, peroxides, amines, acids, esters, ketones, sulfides, and branched chain hydrocarbons (C8 and above).	
10RSY219-2	40 CFR Part 63, Subpart YY	63YY	Source Type = Cyanide chemical production	
10RSY219-3	30 TAC Chapter 115, Vent Gas Controls	R5121-2	Alternate Control Requirement = Alternate control is not used. Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source. Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2. Control Device Type = Smokeless flare Vent Type = Vent gas stream emissions of the specified classes of VOCs including aldehydes, alcohols, aromatics, ethers, olefins, peroxides, amines, acids, esters, ketones, sulfides, and branched chain hydrocarbons (C8 and above).	
10RSY219-3	40 CFR Part 63, Subpart YY	63YY	Source Type = Cyanide chemical production	
10RSY219-4	30 TAC Chapter 115, Vent Gas Controls	R5121-2	Alternate Control Requirement = Alternate control is not used. Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source. Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2. Control Device Type = Smokeless flare Vent Type = Vent gas stream emissions of the specified classes of VOCs including aldehydes, alcohols, aromatics, ethers, olefins, peroxides, amines, acids, esters, ketones, sulfides, and branched chain hydrocarbons (C8 and above).	
10RSY219-4	40 CFR Part 63, Subpart YY	63YY	Source Type = Cyanide chemical production	
10TFX015	30 TAC Chapter 115, Vent Gas Controls	R5121-2	Alternate Control Requirement = Alternate control is not used. Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source. Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2. Control Device Type = Smokeless flare Vent Type = Vent gas steam emissions of the specific VOCs ethylene, butadiene, isobutylene, styrene, isoprene, propylene, and/or methylstyrene.	
10TFX018	30 TAC Chapter	R5121-2	Alternate Control Requirement = Alternate control is not used.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	115, Vent Gas Controls		<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Vent gas steam emissions of the specific VOCs ethylene, butadiene, isobutylene, styrene, isoprene, propylene, and/or methylstyrene.</p>	
10TFX037	30 TAC Chapter 111, Visible Emissions	R1111-1	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is from colorless VOCs, non-fuming liquids, or other sources that are not capable of producing visible emissions. Periodic monitoring to demonstrate compliance is not required.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = On or before January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.</p>	
10TFX037	30 TAC Chapter 115, Vent Gas Controls	R5121-3	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Vent gas stream emissions of the specified classes of VOCs including aldehydes, alcohols, aromatics, ethers, olefins, peroxides, amines, acids, esters, ketones, sulfides, and branched chain hydrocarbons (C8 and above).</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
10TFX067	30 TAC Chapter 115, Vent Gas Controls	R5121-3	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Vent gas stream emissions of the specified classes of VOCs including aldehydes, alcohols, aromatics, ethers, olefins, peroxides, amines, acids, esters, ketones, sulfides, and branched chain hydrocarbons (C8 and above).</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
10TFX307	30 TAC Chapter 115, Vent Gas Controls	R5121-3	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Vent gas steam emissions of the specific VOCs ethylene, butadiene, isobutylene, styrene, isoprene, propylene, and/or methylstyrene.</p>	
10TFX324	30 TAC Chapter 115, Vent Gas Controls	R5121-3	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Vent gas steam emissions of the specific VOCs ethylene, butadiene, isobutylene, styrene, isoprene, propylene, and/or methylstyrene.</p>	
10TFX340	30 TAC Chapter 115, Vent Gas Controls	R5121-2	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Vent gas steam emissions of the specific VOCs ethylene, butadiene, isobutylene, styrene, isoprene, propylene, and/or methylstyrene.</p>	
10TFX341	30 TAC Chapter 115, Vent Gas Controls	R5121-2	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Vent gas steam emissions of the specific VOCs ethylene, butadiene, isobutylene, styrene, isoprene, propylene, and/or methylstyrene.</p>	
10TFX343	30 TAC Chapter 111, Visible Emissions	R1111-1	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is from colorless VOCs, non-fuming liquids, or other sources that are not capable of producing visible emissions. Periodic monitoring to demonstrate compliance is not required.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = After January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
10TFX343	30 TAC Chapter 115, Vent Gas Controls	R5121-2	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Vent gas steam emissions of the specific VOCs ethylene, butadiene, isobutylene, styrene, isoprene, propylene, and/or methylstyrene.</p>	
10TFX344	30 TAC Chapter 111, Visible Emissions	R1111-1	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is from colorless VOCs, non-fuming liquids, or other sources that are not capable of producing visible emissions. Periodic monitoring to demonstrate compliance is not required.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = After January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.</p>	
10TFX344	30 TAC Chapter 115, Vent Gas Controls	R5121-2	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Vent gas steam emissions of the specific VOCs ethylene, butadiene, isobutylene, styrene, isoprene, propylene, and/or methylstyrene.</p>	
10TFX345	30 TAC Chapter 115, Vent Gas Controls	R5121-2	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Vent gas stream emissions of the specified classes of VOCs including aldehydes, alcohols, aromatics, ethers, olefins, peroxides, amines, acids, esters, ketones, sulfides, and branched chain hydrocarbons (C8 and above).</p>	
10TFX350	30 TAC Chapter 115, Vent Gas Controls	R5121-3	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Control Device Type = Smokeless flare</p> <p>Vent Type = Vent gas steam emissions of the specific VOCs ethylene, butadiene, isobutylene, styrene, isoprene, propylene, and/or methylstyrene.</p>	
10TFX351	30 TAC Chapter 115, Vent Gas Controls	R5121-3	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Vent gas stream emissions of the specified classes of VOCs including aldehydes, alcohols, aromatics, ethers, olefins, peroxides, amines, acids, esters, ketones, sulfides, and branched chain hydrocarbons (C8 and above).</p>	
10VNT001	30 TAC Chapter 115, Vent Gas Controls	R5121-3	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Vent gas stream emissions of the specified classes of VOCs including aldehydes, alcohols, aromatics, ethers, olefins, peroxides, amines, acids, esters, ketones, sulfides, and branched chain hydrocarbons (C8 and above).</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
10VNT002	30 TAC Chapter 115, Vent Gas Controls	R5121-3	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Vent gas stream emissions of the specified classes of VOCs including aldehydes, alcohols, aromatics, ethers, olefins, peroxides, amines, acids, esters, ketones, sulfides, and branched chain hydrocarbons (C8 and above).</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
10VNT003	30 TAC Chapter 111, Visible Emissions	R1111-1	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is from colorless VOCs, non-fuming liquids, or other sources that are not capable of producing visible emissions. Periodic monitoring to demonstrate compliance is not required.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Construction Date = After January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.</p>	
10VNT003	30 TAC Chapter 115, Vent Gas Controls	R5121-3	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Vent gas steam emissions of the specific VOCs ethylene, butadiene, isobutylene, styrene, isoprene, propylene, and/or methylstyrene.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
GRP10DIS01	30 TAC Chapter 115, Vent Gas Controls	R5121-3	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Vent gas steam emissions of the specific VOCs ethylene, butadiene, isobutylene, styrene, isoprene, propylene, and/or methylstyrene.</p>	
GRP10DIS01	40 CFR Part 63, Subpart G	63G-13	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Flare</p> <p>Overlap = Title 40 CFR Part 60, Subpart NNN</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>By-pass Lines = The vent system contains by-pass lines that can divert the vent stream from the control device.</p> <p>Flow Indicator = By-pass line valve is secured with a car-seal or lock-and-key type configuration.</p>	
GRP10DIS03	30 TAC Chapter 111, Visible Emissions	R1111-1	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is from colorless VOCs, non-fuming liquids, or other sources that are not capable of producing visible emissions. Periodic monitoring to demonstrate compliance is not required.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = After January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
GRP1oDISo3	30 TAC Chapter 115, Vent Gas Controls	R5121-3	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Vent gas stream emissions of the specified classes of VOCs including aldehydes, alcohols, aromatics, ethers, olefins, peroxides, amines, acids, esters, ketones, sulfides, and branched chain hydrocarbons (C8 and above).</p>	
GRP1oDISo3	40 CFR Part 63, Subpart G	63G-13	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Flare</p> <p>Overlap = Title 40 CFR Part 60, Subpart NNN</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>By-pass Lines = The vent system does not contain by-pass lines that can divert the vent stream from the control device.</p>	
GRP1oDISo4	30 TAC Chapter 115, Vent Gas Controls	R5121-2	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Vent gas steam emissions of the specific VOCs ethylene, butadiene, isobutylene, styrene, isoprene, propylene, and/or methylstyrene.</p>	
GRP1oDISo4	40 CFR Part 63, Subpart G	63G-13	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Flare</p> <p>Overlap = Title 40 CFR Part 60, Subpart NNN</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>By-pass Lines = The vent system does not contain by-pass lines that can divert the vent stream from the control device.</p>	
GRP1oDISo5	30 TAC Chapter 115, Vent Gas	R5121-2	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	Controls		<p>Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Vent gas steam emissions of the specific VOCs ethylene, butadiene, isobutylene, styrene, isoprene, propylene, and/or methylstyrene.</p>	
GRP1oDISo5	40 CFR Part 63, Subpart G	63G-13	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Flare</p> <p>Overlap = Title 40 CFR Part 60, Subpart NNN</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>By-pass Lines = The vent system contains by-pass lines that can divert the vent stream from the control device.</p> <p>Flow Indicator = By-pass line valve is secured with a car-seal or lock-and-key type configuration.</p>	
GRP1oDISo6	30 TAC Chapter 115, Vent Gas Controls	R5121-3	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Vent gas steam emissions of the specific VOCs ethylene, butadiene, isobutylene, styrene, isoprene, propylene, and/or methylstyrene.</p>	
GRP1oDISo6	40 CFR Part 63, Subpart G	63G-13	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Flare</p> <p>Overlap = Title 40 CFR Part 60, Subpart NNN</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>By-pass Lines = The vent system does not contain by-pass lines that can divert the vent stream from the control device.</p>	
GRP1oDIS16	30 TAC Chapter 111, Visible Emissions	R1111-1	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is from colorless VOCs, non-fuming liquids, or other sources that are not capable of producing visible emissions. Periodic monitoring to demonstrate compliance is not required.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = After January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.</p>	
GRP10DIS16	30 TAC Chapter 115, Vent Gas Controls	R5121-3	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Vent gas stream emissions of the specified classes of VOCs including aldehydes, alcohols, aromatics, ethers, olefins, peroxides, amines, acids, esters, ketones, sulfides, and branched chain hydrocarbons (C8 and above).</p>	
GRP10DIS16	30 TAC Chapter 115, Vent Gas Controls	R5121-5	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Vent gas stream emissions of the specified classes of VOCs including aldehydes, alcohols, aromatics, ethers, olefins, peroxides, amines, acids, esters, ketones, sulfides, and branched chain hydrocarbons (C8 and above).</p>	
GRP10DIS16	30 TAC Chapter 115, Vent Gas Controls	R5121-8	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Vapor recovery system, as defined in 30 TAC § 115.10, other than an afterburner, blast furnace combustion device, boiler, catalytic or direct flame incinerator, carbon adsorption system, chiller, flare or vapor combustor.</p> <p>Vent Type = Vent gas stream emissions of the specified classes of VOCs including aldehydes, alcohols, aromatics, ethers, olefins, peroxides, amines, acids, esters, ketones, sulfides, and branched chain hydrocarbons (C8 and above).</p>	
GRP10DIS16	30 TAC Chapter 115, Vent Gas Controls	R5121-9	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Vapor recovery system, as defined in 30 TAC § 115.10, other than an afterburner, blast furnace combustion device, boiler, catalytic or direct flame incinerator, carbon adsorption system, chiller, flare or</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			vapor combustor. Vent Type = Vent gas stream emissions of the specified classes of VOCs including aldehydes, alcohols, aromatics, ethers, olefins, peroxides, amines, acids, esters, ketones, sulfides, and branched chain hydrocarbons (C8 and above).	
GRP1oDIS16	40 CFR Part 63, Subpart YY	63YY	Source Type = Cyanide chemical production	
GRP1oPV001	30 TAC Chapter 111, Visible Emissions	R1111-1	Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113. Vent Source = The source of the vent is from colorless VOCs, non-fuming liquids, or other sources that are not capable of producing visible emissions. Periodic monitoring to demonstrate compliance is not required. Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3). Construction Date = After January 31, 1972 Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.	
GRP1oPV001	30 TAC Chapter 115, Vent Gas Controls	R5121-3	Alternate Control Requirement = Alternate control is not used. Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source. Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2. Control Device Type = Smokeless flare Vent Type = Vent gas stream emissions of the specified classes of VOCs including aldehydes, alcohols, aromatics, ethers, olefins, peroxides, amines, acids, esters, ketones, sulfides, and branched chain hydrocarbons (C8 and above).	
GRP1oPV002	30 TAC Chapter 115, Vent Gas Controls	R5121-3	Alternate Control Requirement = Alternate control is not used. Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source. Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2. Control Device Type = Vapor recovery system, as defined in 30 TAC § 115.10, other than an afterburner, blast furnace combustion device, boiler, catalytic or direct flame incinerator, carbon adsorption system, chiller, flare or vapor combustor. Vent Type = Vent gas stream emissions of the specified classes of VOCs including aldehydes, alcohols, aromatics, ethers, olefins, peroxides, amines, acids, esters, ketones, sulfides, and branched chain hydrocarbons (C8 and above).	
GRP1oPV002	40 CFR Part 63, Subpart YY	63YY	Source Type = Cyanide chemical production	
GRP1oPV003	30 TAC Chapter 111, Visible Emissions	R1111-1	Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113. Vent Source = The source of the vent is from colorless VOCs, non-fuming liquids, or other sources that are not capable of producing visible emissions. Periodic monitoring to demonstrate compliance is not required. Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			not qualify for the exemption in § 111.111(a)(3). Construction Date = After January 31, 1972 Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.	
GRP1oPV003	30 TAC Chapter 115, Vent Gas Controls	R5121-2	Alternate Control Requirement = Alternate control is not used. Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source. Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2. Control Device Type = Smokeless flare Vent Type = Vent gas steam emissions of the specific VOCs ethylene, butadiene, isobutylene, styrene, isoprene, propylene, and/or methylstyrene.	
GRP1oPV004	30 TAC Chapter 111, Visible Emissions	R1111-1	Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113. Vent Source = The source of the vent is from colorless VOCs, non-fuming liquids, or other sources that are not capable of producing visible emissions. Periodic monitoring to demonstrate compliance is not required. Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3). Construction Date = After January 31, 1972 Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.	
GRP1oPV004	30 TAC Chapter 115, Vent Gas Controls	R5121-3	Alternate Control Requirement = Alternate control is not used. Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source. Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2. Control Device Type = Smokeless flare Vent Type = Vent gas steam emissions of the specific VOCs ethylene, butadiene, isobutylene, styrene, isoprene, propylene, and/or methylstyrene.	
GRP1oPV005	30 TAC Chapter 111, Visible Emissions	R1111-1	Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113. Vent Source = The source of the vent is from colorless VOCs, non-fuming liquids, or other sources that are not capable of producing visible emissions. Periodic monitoring to demonstrate compliance is not required. Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3). Construction Date = On or before January 31, 1972 Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.	
GRP1oPV005	30 TAC Chapter 115, Vent Gas Controls	R5121-2	Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source. Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115,	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Subchapter B, Division 2.</p> <p>Vent Type = Vent gas stream emissions of the specific VOCs ethylene, butadiene, isobutylene, styrene, isoprene, propylene, and/or methylstyrene.</p> <p>VOC Concentration = VOC concentration is less than 30,000 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
GRP1oPV006	30 TAC Chapter 111, Visible Emissions	R1111-1	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is from colorless VOCs, non-fuming liquids, or other sources that are not capable of producing visible emissions. Periodic monitoring to demonstrate compliance is not required.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = On or before January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.</p>	
GRP1oPV006	30 TAC Chapter 115, Vent Gas Controls	R5121-3	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Vent gas stream emissions of the specified classes of VOCs including aldehydes, alcohols, aromatics, ethers, olefins, peroxides, amines, acids, esters, ketones, sulfides, and branched chain hydrocarbons (C8 and above).</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
GRP1oPV007	30 TAC Chapter 111, Visible Emissions	R1111-1	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is from colorless VOCs, non-fuming liquids, or other sources that are not capable of producing visible emissions. Periodic monitoring to demonstrate compliance is not required.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = After January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.</p>	
GRP1oPV007	30 TAC Chapter 115, Vent Gas Controls	R5121-3	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Vent gas stream emissions of the specified classes of VOCs including aldehydes, alcohols, aromatics, ethers, olefins, peroxides, amines, acids, esters, ketones, sulfides, and branched chain hydrocarbons (C8 and above).</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
GRP10RX001	30 TAC Chapter 115, Vent Gas Controls	R5121-2	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Vent gas steam emissions of the specific VOCs ethylene, butadiene, isobutylene, styrene, isoprene, propylene, and/or methylstyrene.</p>	
GRP10RX001	40 CFR Part 63, Subpart G	63G-12	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Flare</p> <p>Overlap = Title 40 CFR Part 60, Subpart RRR</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>By-pass Lines = The vent system does not contain by-pass lines that can divert the vent stream from the control device.</p>	
10DEGo68	30 TAC Chapter 115, Degreasing Processes	R5412-1	<p>Solvent Degreasing Machine Type = Cold solvent cleaning machine.</p> <p>Alternate Control Requirement = The TCEQ Executive Director has not approved an alternative control requirement as allowed under 30 TAC § 115.413 or not alternative has been requested.</p> <p>Solvent Sprayed = A solvent is sprayed.</p> <p>Solvent Vapor Pressure = Solvent vapor pressure is less than or equal to 0.6 psia as measured at 100 degrees Fahrenheit.</p> <p>Solvent Heated = The solvent is not heated to a temperature greater than 120° F.</p> <p>Parts Larger than Drainage = No cleaned parts for which the machine is authorized to clean are larger than the internal drainage facility of the machine.</p> <p>Drainage Area = Area is greater than or equal to 16 square inches.</p> <p>Disposal in Enclosed Containers = Waste solvent is properly disposed of in enclosed containers.</p>	
10FLR005	40 CFR Part 61, Subpart FF	61FF-1	<p>Unit Type = Individual drain system</p> <p>CLOSED VENT SYSTEM AND CONTROL DEVICE AMOC = Complying with the requirements of § 61.349</p> <p>By-pass Line = System does not contain by-pass lines</p> <p>Control Device Type/Operation = Flare.</p>	
10FLR005	40 CFR Part 63, Subpart G	63G-4	Alternate Monitoring Parameters = Complying with the monitoring parameters specified in Subpart G.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Unit Type = Individual drain system New Source = Source is an existing source Closed Vent System = Closed vent system is subject to and complying with 40 CFR § 63.148. By-pass Lines = No by-pass lines. Combination of Control Devices = Vent stream is treated using a single control device. Control Device Type = Flare. Monitoring Options = Control device is using the monitoring parameters specified in Table 13 of Subpart G.	
GRP10PV004	40 CFR Part 61, Subpart FF	61FF-4	Unit Type = Individual drain system CLOSED VENT SYSTEM AND CONTROL DEVICE AMOC = Complying with the requirements of § 61.349 By-pass Line = System does not contain by-pass lines Control Device Type/Operation = Flare.	
GRP10PV004	40 CFR Part 63, Subpart G	63G-4	Alternate Monitoring Parameters = Complying with the monitoring parameters specified in Subpart G. Unit Type = Individual drain system New Source = Source is an existing source Closed Vent System = Closed vent system is subject to and complying with 40 CFR § 63.148. By-pass Lines = No by-pass lines. Combination of Control Devices = Vent stream is treated using a single control device. Control Device Type = Flare. Monitoring Options = Control device is using the monitoring parameters specified in Table 13 of Subpart G.	
10DSY226	40 CFR Part 61, Subpart FF	61FF-1	AMOC = An alternate means of compliance (AMOC) to meet the requirements of 40 CFR § 61.348 for treatment processes is not used. By-Pass Line = The closed-vent system contains a by-pass line that could divert the vent stream away from the control device. Continuous Monitoring = The wastewater treatment system unit process parameters are continuously monitored to indicate proper system operation. By-Pass Line Valve = A car-seal or lock and key configuration is used to secure the by-pass line valve in the closed position. Treatment Stream Unit Exempt = There are units in the wastewater treatment system that are exempt according to 40 CFR § 61.348(b)(2). Complying with § 61.342(e) = The facility is not complying with 40 CFR § 61.342(e). Control Device Type/Operation = Flare. Openings = The treatment process or wastewater treatment system unit has openings. Fuel Gas System = Not all gaseous vent streams from the treatment process or wastewater treatment system are routed to a fuel gas system. Stream Combination = The process wastewater, product tank drawdown, or landfill leachate is combined with other waste streams for the purpose of facilitating management or treatment in the wastewater treatment system. Less Than Atmospheric = A cover and closed-vent system are operated such that the treatment process or wastewater system unit is maintained at ambient atmospheric pressure.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Closed-Vent System and Control Device = A closed-vent system and control device is used.</p> <p>Process Or Stream Exemption = The treatment process or waste stream is not complying with 40 CFR §61.348(d).</p> <p>AMOC = No alternate means of compliance (AMOC) to meet the requirements of 40 CFR § 61.349 for a closed-vent system and control device is used.</p> <p>Treatment Process Engineering Calculations = Performance tests are used to show that the treatment process or wastewater treatment system unit achieves its emission limitation.</p>	
10DSY226	40 CFR Part 63, Subpart G	63G-1	<p>Series of Processes = The wastewater stream is treated using a single treatment process.</p> <p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or no alternate has been requested.</p> <p>Vented to Control = Emissions from the treatment process are vented to a control device.</p> <p>Biological Treatment Process = Non-biological treatment process.</p> <p>Closed Vent System = Closed vent system is not maintained under negative pressure and is subject to 40 CFR § 63.148.</p> <p>By-Pass Lines = By-pass line valves are secured in the closed position with a car-seal or lock-and-key configuration.</p> <p>Wastewater Stream Designation = Group1 for Table 9 compounds.</p> <p>Combination of Control Devices = The vent stream is treated using a single control device.</p> <p>Monitoring Options = Control device is using the monitoring parameters specified in Table 13 of Subpart G.</p> <p>Wastewater Stream Treatment = Required Mass Removal (RMR) option under § 63.138(f).</p> <p>Control Devices = Flare.</p> <p>Treatment Process Design Evaluation = Compliance for the treatment process will be demonstrated by performance test.</p>	
10MSV260	40 CFR Part 63, Subpart FFFF	63FFFF-SV260	<p>Designated Grp1 = The emission stream is not designated as Group 1.</p> <p>Designated HAL = The emission stream is not designated as halogenated.</p> <p>Determined Grp1 = The emission stream is determined to be Group 1.</p> <p>Determined HAL = The emission stream is determined not to be halogenated.</p> <p>Vent Emission Control = Reduce uncontrolled organic HAP emissions from all batch process vents within the process by venting through a closed-vent system to a flare per Table 2.1.c.</p> <p>Prior Eval = The data from a prior evaluation or assessment is used.</p> <p>Negative Pressure = The closed vent system is operated and maintained at atmospheric pressure.</p> <p>Bypass Line = No bypass lines.</p>	
10MSV261	40 CFR Part 63, Subpart FFFF	63FFFF-SV261	<p>Designated Grp1 = The emission stream is not designated as Group 1.</p> <p>Designated HAL = The emission stream is not designated as halogenated.</p> <p>Determined Grp1 = The emission stream is determined to be Group 1.</p> <p>Determined HAL = The emission stream is determined not to be halogenated.</p> <p>Vent Emission Control = Reduce uncontrolled organic HAP emissions from all batch process vents within the process by venting through a closed-vent system to a flare per Table 2.1.c.</p> <p>Prior Eval = The data from a prior evaluation or assessment is used.</p> <p>Negative Pressure = The closed vent system is operated and maintained at atmospheric pressure.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Bypass Line = No bypass lines.	
PRO-ADN	40 CFR Part 63, Subpart F	63F-1	<p>Applicable Chemicals = The chemical manufacturing process unit manufactures, as a primary product, one or more of the chemicals listed in 40 CFR § 63.100(b)(1)(i) or 40 CFR § 63.100(b)(1)(ii).</p> <p>Intervening Cooling Fluid = There is no intervening cooling fluid containing less than 5 percent by weight of total HAPs listed in Table 4 of 40 CFR Part 63, Subpart F, between the process and cooling water.</p> <p>Table 2 HAP = The chemical manufacturing process unit uses as a reactant or manufactures, as a product or co-product, one or more of the organic hazardous air pollutants in Table 2.</p> <p>Table 4 HAP Content = The recirculating heat exchange system is not used exclusively to cool process fluids that contain less than 5 percent by weight of total HAPs listed in Table 4 of title 40 CFR Part 63, Subpart F.</p> <p>Alternate Means of Emission Limitation = No alternative means of emission limitation has been approved by the EPA Administrator to achieve a reduction in organic HAP emission or no alternate has been requested.</p> <p>NPDES Permit = The once-through heat exchange system is not subject to NPDES permit with an allowable discharge limit of 1 part per million or less above influent concentration or 10 percent or less above influent concentration.</p> <p>Meets 40 CFR 63.104(a)(4)(i)-(iv) = The once-through heat exchange system is not subject to an NPDES permit that meets 40 CFR § 63.104(a)(4)(i) - (iv).</p> <p>Heat Exchange System = A heat exchange system is utilized.</p> <p>Table 9 HAP Content = The once-through heat exchange system is not used exclusively to cool process fluids that contain less than 5 percent by weight of total HAPs listed in Table 9 of 40 CFR Part 63, Subpart G.</p> <p>Cooling Water Monitored = The cooling water is being monitored for the presence of one or more HAPs or other representative substances whose presence in cooling water indicates a leak.</p> <p>Cooling Water Pressure = The heat exchange system is not operated with the minimum pressure on the cooling water side at least 35 kilopascals greater than the maximum pressure on the process side.</p>	

* - The "unit attributes" or operating conditions that determine what requirements apply

** - Notes changes made to the automated results from the DSS, and a brief explanation why

NSR Versus Title V FOP

The state of Texas has two Air permitting programs, New Source Review (NSR) and Title V Federal Operating Permits. The two programs are substantially different both in intent and permit content.

NSR is a preconstruction permitting program authorized by the Texas Clean Air Act and Title I of the Federal Clean Air Act (FCAA). The processing of these permits is governed by 30 Texas Administrative Code (TAC) Chapter 116.111. The Title V Federal Operating Program is a federal program authorized under Title V of the FCAA that has been delegated to the state of Texas to administer and is governed by 30 TAC Chapter 122. The major differences between the two permitting programs are listed in the table below:

NSR Permit	Federal Operating Permit(FOP)
Issued Prior to new Construction or modification of an existing facility	For initial permit with application shield, can be issued after operation commences; significant revisions require approval prior to operation.
Authorizes air emissions	Codifies existing applicable requirements, does not authorize new emissions
Ensures issued permits are protective of the environment and human health by conducting a health effects review and that requirement for best available control technology (BACT) is implemented.	Applicable requirements listed in permit are used by the inspectors to ensure proper operation of the site as authorized. Ensures that adequate monitoring is in place to allow compliance determination with the FOP.
Up to two Public notices may be required. Opportunity for public comment and contested case hearings for some authorizations.	One public notice required. Opportunity for public comments. No contested case hearings.
Applies to all point source emissions in the state.	Applies to all major sources and some non-major sources identified by the EPA.
Applies to facilities: a portion of site or individual emission sources	One or multiple FOPs cover the entire site (consists of multiple facilities)
Permits include terms and conditions under which the applicant must construct and operate its various equipment and processes on a facility basis.	Permits include terms and conditions that specify the general operational requirements of the site; and also include codification of all applicable requirements for emission units at the site.
Opportunity for EPA review for Federal Prevention of Significant Deterioration (PSD) and Nonattainment (NA) permits for major sources.	Opportunity for EPA review, Affected states review, and a Public petition period for every FOP.
Permits have a table listing maximum emission limits for pollutants	Permit has an applicable requirements table and Periodic Monitoring (PM) / Compliance Assurance Monitoring (CAM) tables which document applicable monitoring requirements.
Permits can be altered or amended upon application by company. Permits must be issued before construction or modification of facilities can begin.	Permits can be revised through several revision processes, which provide for different levels of public notice and opportunity to comment. Changes that would be significant revisions require that a revised permit be issued before those changes can be operated.
NSR permits are issued independent of FOP requirements.	FOP are independent of NSR permits, but contain a list of all NSR permits incorporated by reference

New Source Review Requirements

Below is a list of the New Source Review (NSR) permits for the permitted area. These NSR permits are incorporated by reference into the operating permit and are enforceable under it. These permits can be found in the main TCEQ file room, located on the first floor of Building E, 12100 Park 35 Circle, Austin, Texas. The Public Education Program may be contacted at 1-800-687-4040 or the Air Permits Division (APD) may be contacted at 1-512-239-1250 for help with any question.

Additionally, the site contains emission units that are permitted by rule under the requirements of 30 TAC Chapter 106, Permits by Rule. The following table specifies the permits by rule that apply to the site. All current permits by rule are contained in Chapter 106. Outdated 30 TAC Chapter 106 permits by rule may be viewed at the following Web site:

www.tceq.texas.gov/permitting/air/permitbyrule/historical_rules/old106list/index106.html

Outdated Standard Exemption lists may be viewed at the following Web site:

www.tceq.texas.gov/permitting/air/permitbyrule/historical_rules/oldselist/se_index.html

The status of air permits and applications and a link to the Air Permits Remote Document Server is located at the following Web site:

www.tceq.texas.gov/permitting/air/nav/air_status_permits.html

Prevention of Significant Deterioration (PSD) Permits	
PSD Permit No.: GHGPSDTX145	Issuance Date: 07/15/2016
PSD Permit No.: PSDTX1079M1	Issuance Date: 07/15/2016
Title 30 TAC Chapter 116 Permits, Special Permits, and Other Authorizations (Other Than Permits By Rule, PSD Permits, or NA Permits) for the Application Area.	
Authorization No.: 7186	Issuance Date: 07/15/2016
Permits By Rule (30 TAC Chapter 106) for the Application Area	
Number: 106.183	Version No./Date: 09/04/2000
Number: 106.261	Version No./Date: 11/01/2003
Number: 106.262	Version No./Date: 11/01/2003
Number: 106.263	Version No./Date: 11/01/2001
Number: 106.371	Version No./Date: 09/04/2000
Number: 106.373	Version No./Date: 09/04/2000
Number: 106.454	Version No./Date: 11/01/2001
Number: 106.472	Version No./Date: 03/14/1997
Number: 106.472	Version No./Date: 09/04/2000
Number: 106.478	Version No./Date: 09/04/2000
Number: 106.492	Version No./Date: 09/04/2000
Number: 106.511	Version No./Date: 09/04/2000

Emission Units and Emission Points

In air permitting terminology, any source capable of generating emissions (for example, an engine or a sandblasting area) is called an Emission Unit. For purposes of Title V, emission units are specifically listed in the operating permit when they have applicable requirements other than New Source Review (NSR), or when they are listed in the permit shield table.

The actual physical location where the emissions enter the atmosphere (for example, an engine stack or a sandblasting yard) is called an emission point. For New Source Review preconstruction permitting purposes, every emission unit has an associated emission point. Emission limits are listed in an NSR permit, associated with an emission point. This list of emission points and emission limits per pollutant is commonly referred to as the “Maximum Allowable Emission Rate Table”, or “MAERT” for short. Specifically, the MAERT lists the Emission Point Number (EPN) that identifies the emission point, followed immediately by the Source Name, identifying the emission unit that is the source of those emissions on this table.

Thus, by reference, an emission unit in a Title V operating permit is linked by reference number to an NSR authorization, and its related emission point.

Monitoring Sufficiency

Federal and state rules, 40 CFR § 70.6(a)(3)(i)(B) and 30 TAC § 122.142(c) respectively, require that each federal operating permit include additional monitoring for applicable requirements that lack periodic or instrumental monitoring (which may include recordkeeping that serves as monitoring) that yields reliable data from a relevant time period that are representative of the emission unit’s compliance with the applicable emission limitation or standard. Furthermore, the federal operating permit must include compliance assurance monitoring (CAM) requirements for emission sources that meet the applicability criteria of 40 CFR Part 64 in accordance with 40 CFR § 70.6(a)(3)(i)(A) and 30 TAC § 122.604(b).

With the exception of any emission units listed in the Periodic Monitoring or CAM Summaries in the FOP, the TCEQ Executive Director has determined that the permit contains sufficient monitoring, testing, recordkeeping, and reporting requirements that assure compliance with the applicable requirements. If applicable, each emission unit that requires additional monitoring in the form of periodic monitoring or CAM is described in further detail under the Rationale for CAM/PM Methods Selected section following this paragraph.

Rationale for Compliance Assurance Monitoring (CAM)/ Periodic Monitoring Methods Selected

Compliance Assurance Monitoring (CAM):

Compliance Assurance Monitoring (CAM) is a federal monitoring program established under Title 40 Code of Federal Regulations Part 64 (40 CFR Part 64).

Emission units are subject to CAM requirements if they meet the following criteria:

1. the emission unit is subject to an emission limitation or standard for an air pollutant (or surrogate thereof) in an applicable requirement;
2. the emission unit uses a control device to achieve compliance with the emission limitation or standard specified in the applicable requirement; and

3. the emission unit has the pre-control device potential to emit greater than or equal to the amount in tons per year for a site to be classified as a major source.

The following table(s) identify the emission unit(s) that are subject to CAM:

Unit/Group/Process Information	
ID No.: 10DSY206	
Control Device ID No.: 10FLR005	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-3
Pollutant: VOC	Main Standard: § 115.122(b)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: n/a	
Deviation Limit: Lack of pilot flame or failure to record status of pilot flame at least once every 15 minutes when the vent from 10DSY206 is routed to Flare 10FLR005.	
Basis of CAM: It is widely practiced and accepted to monitor the flare pilot flame by closed circuit cameras, thermocouples and visual inspection. The presence of the pilot flame demonstrates that VOC emissions are combusted. Monitoring the presence of a pilot flame is required in many federal rules, including: 40 CFR Part 60, Subparts K, III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; and 40 CFR Part 63, Subparts G, R, W, DD, and HH.	

Unit/Group/Process Information	
ID No.: 10DSY206	
Control Device ID No.: 15BLR003	Control Device Type: Steam Generating Unit (Boiler)/Process Heater (Design heat input is greater than or equal to 44MW)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-8
Pollutant: VOC	Main Standard: § 115.122(b)
Monitoring Information	
Indicator: Period of Operation	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: Any period when any unit in 10DSY206 is routed to the steam generating unit, and the steam generating unit is not operating.	
<p>Basis of CAM: A common way to control VOC emissions is to route emissions to a boiler or process heater with a design heat input capacity of 44 MW or greater with minimum temperatures of 1100 °C and residence times greater than one second. Boilers and process heaters with the stated design have demonstrated to meet 98% reduction efficiency; therefore, it is only necessary to document the period of operation of the control equipment. Additionally, in the October, 21, 1983 preamble to 40 CFR Part 60, Subpart III, (48 FR 48945), the EPA determined that installing a steam generating unit, with a design heat input capacity of 44 MW or greater, to control VOC emissions, is an acceptable means of demonstrating compliance with 40 CFR Part 60, Subpart III and waived the requirement for a performance test on such devices. Monitoring the period of operation of a boiler/process heater greater than 44 MW is commonly required in federal rules, including: 40 CFR Part 60, Subparts III and NNN; 40 CFR Part 61, Subpart BB; 40 CFR Part 63, Subpart G.</p>	

Unit/Group/Process Information	
ID No.: 10DSY206	
Control Device ID No.: 15BLR004	Control Device Type: Steam Generating Unit (Boiler)/Process Heater (Design heat input is greater than or equal to 44MW)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-9
Pollutant: VOC	Main Standard: § 115.122(b)
Monitoring Information	
Indicator: Period of Operation	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: Any period when any unit in 10DSY206 is routed to the steam generating unit, and the steam generating unit is not operating.	
<p>Basis of CAM: A common way to control VOC emissions is to route emissions to a boiler or process heater with a design heat input capacity of 44 MW or greater with minimum temperatures of 1100 °C and residence times greater than one second. Boilers and process heaters with the stated design have demonstrated to meet 98% reduction efficiency; therefore, it is only necessary to document the period of operation of the control equipment. Additionally, in the October, 21, 1983 preamble to 40 CFR Part 60, Subpart III, (48 FR 48945), the EPA determined that installing a steam generating unit, with a design heat input capacity of 44 MW or greater, to control VOC emissions, is an acceptable means of demonstrating compliance with 40 CFR Part 60, Subpart III and waived the requirement for a performance test on such devices. Monitoring the period of operation of a boiler/process heater greater than 44 MW is commonly required in federal rules, including: 40 CFR Part 60, Subparts III and NNN; 40 CFR Part 61, Subpart BB; 40 CFR Part 63, Subpart G.</p>	

Unit/Group/Process Information	
ID No.: 10DSY226PV	
Control Device ID No.: 10DSY005	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-3
Pollutant: VOC	Main Standard: § 115.122(b)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: n/a	
Deviation Limit: Except for periods during which 10DSY226PV is shut down, lack of a pilot flame shall be reported as a deviation, or failure to record status of the pilot flame at least once every 15 minutes shall be reported as a deviation.	
Basis of CAM: It is widely practiced and accepted to monitor the flare pilot flame by closed circuit cameras, thermocouples and visual inspection. The presence of the pilot flame demonstrates that VOC emissions are combusted. Monitoring the presence of a pilot flame is required in many federal rules, including: 40 CFR Part 60, Subparts K, III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; and 40 CFR Part 63, Subparts G, R, W, DD, and HH.	

Unit/Group/Process Information	
ID No.: 10MSV260	
Control Device ID No.: 10FLR005	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-1
Pollutant: VOC	Main Standard: § 115.122(b)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: n/a	
Deviation Limit: Lack of pilot flame or failure to record status of pilot flame at least once every 15 minutes when the vent from 10MSV260 is routed to Flare 10FLR005.	
Basis of CAM: It is widely practiced and accepted to monitor the flare pilot flame by closed circuit cameras, thermocouples and visual inspection. The presence of the pilot flame demonstrates that VOC emissions are combusted. Monitoring the presence of a pilot flame is required in many federal rules, including: 40 CFR Part 60, Subparts K, III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; and 40 CFR Part 63, Subparts G, R, W, DD, and HH.	

Unit/Group/Process Information	
ID No.: 10MSV260	
Control Device ID No.: 15BLR001	Control Device Type: Steam Generating Unit (Boiler)/Process Heater (Design heat input is greater than or equal to 44MW)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-6
Pollutant: VOC	Main Standard: § 115.122(b)
Monitoring Information	
Indicator: Period of Operation	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: Any period when any unit in 10MSV260 is routed to the steam generating unit, and the steam generating unit is not operating.	
<p>Basis of CAM: A common way to control VOC emissions is to route emissions to a boiler or process heater with a design heat input capacity of 44 MW or greater with minimum temperatures of 1100 °C and residence times greater than one second. Boilers and process heaters with the stated design have demonstrated to meet 98% reduction efficiency; therefore, it is only necessary to document the period of operation of the control equipment. Additionally, in the October, 21, 1983 preamble to 40 CFR Part 60, Subpart III, (48 FR 48945), the EPA determined that installing a steam generating unit, with a design heat input capacity of 44 MW or greater, to control VOC emissions, is an acceptable means of demonstrating compliance with 40 CFR Part 60, Subpart III and waived the requirement for a performance test on such devices. Monitoring the period of operation of a boiler/process heater greater than 44 MW is commonly required in federal rules, including: 40 CFR Part 60, Subparts III and NNN; 40 CFR Part 61, Subpart BB; 40 CFR Part 63, Subpart G.</p>	

Unit/Group/Process Information	
ID No.: 10MSV260	
Control Device ID No.: 15BLR002	Control Device Type: Steam Generating Unit (Boiler)/Process Heater (Design heat input is greater than or equal to 44MW)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-7
Pollutant: VOC	Main Standard: § 115.122(b)
Monitoring Information	
Indicator: Period of Operation	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: Any period when any unit in 10MSV260 is routed to the steam generating unit, and the steam generating unit is not operating.	
<p>Basis of CAM: A common way to control VOC emissions is to route emissions to a boiler or process heater with a design heat input capacity of 44 MW or greater with minimum temperatures of 1100 °C and residence times greater than one second. Boilers and process heaters with the stated design have demonstrated to meet 98% reduction efficiency; therefore, it is only necessary to document the period of operation of the control equipment. Additionally, in the October, 21, 1983 preamble to 40 CFR Part 60, Subpart III, (48 FR 48945), the EPA determined that installing a steam generating unit, with a design heat input capacity of 44 MW or greater, to control VOC emissions, is an acceptable means of demonstrating compliance with 40 CFR Part 60, Subpart III and waived the requirement for a performance test on such devices. Monitoring the period of operation of a boiler/process heater greater than 44 MW is commonly required in federal rules, including: 40 CFR Part 60, Subparts III and NNN; 40 CFR Part 61, Subpart BB; 40 CFR Part 63, Subpart G.</p>	

Unit/Group/Process Information	
ID No.: 10MSV260	
Control Device ID No.: 15BLR003	Control Device Type: Steam Generating Unit (Boiler)/Process Heater (Design heat input is greater than or equal to 44MW)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-8
Pollutant: VOC	Main Standard: § 115.122(b)
Monitoring Information	
Indicator: Period of Operation	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: Any period when any unit in 10MSV260 is routed to the steam generating unit, and the steam generating unit is not operating.	
<p>Basis of CAM: A common way to control VOC emissions is to route emissions to a boiler or process heater with a design heat input capacity of 44 MW or greater with minimum temperatures of 1100 °C and residence times greater than one second. Boilers and process heaters with the stated design have demonstrated to meet 98% reduction efficiency; therefore, it is only necessary to document the period of operation of the control equipment. Additionally, in the October, 21, 1983 preamble to 40 CFR Part 60, Subpart III, (48 FR 48945), the EPA determined that installing a steam generating unit, with a design heat input capacity of 44 MW or greater, to control VOC emissions, is an acceptable means of demonstrating compliance with 40 CFR Part 60, Subpart III and waived the requirement for a performance test on such devices. Monitoring the period of operation of a boiler/process heater greater than 44 MW is commonly required in federal rules, including: 40 CFR Part 60, Subparts III and NNN; 40 CFR Part 61, Subpart BB; 40 CFR Part 63, Subpart G.</p>	

Unit/Group/Process Information	
ID No.: 10MSV260	
Control Device ID No.: 15BLR004	Control Device Type: Steam Generating Unit (Boiler)/Process Heater (Design heat input is greater than or equal to 44MW)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-9
Pollutant: VOC	Main Standard: § 115.122(b)
Monitoring Information	
Indicator: Period of Operation	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: Any period when any unit in 10MSV260 is routed to the steam generating unit, and the steam generating unit is not operating.	
<p>Basis of CAM: A common way to control VOC emissions is to route emissions to a boiler or process heater with a design heat input capacity of 44 MW or greater with minimum temperatures of 1100 °C and residence times greater than one second. Boilers and process heaters with the stated design have demonstrated to meet 98% reduction efficiency; therefore, it is only necessary to document the period of operation of the control equipment. Additionally, in the October, 21, 1983 preamble to 40 CFR Part 60, Subpart III, (48 FR 48945), the EPA determined that installing a steam generating unit, with a design heat input capacity of 44 MW or greater, to control VOC emissions, is an acceptable means of demonstrating compliance with 40 CFR Part 60, Subpart III and waived the requirement for a performance test on such devices. Monitoring the period of operation of a boiler/process heater greater than 44 MW is commonly required in federal rules, including: 40 CFR Part 60, Subparts III and NNN; 40 CFR Part 61, Subpart BB; 40 CFR Part 63, Subpart G.</p>	

Unit/Group/Process Information	
ID No.: 10MSV261	
Control Device ID No.: 10FLR005	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-1
Pollutant: VOC	Main Standard: § 115.122(b)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: n/a	
Deviation Limit: Lack of pilot flame or failure to record status of pilot flame at least once every 15 minutes when the vent from 10MSV261 is routed to Flare 10FLR005.	
Basis of CAM: It is widely practiced and accepted to monitor the flare pilot flame by closed circuit cameras, thermocouples and visual inspection. The presence of the pilot flame demonstrates that VOC emissions are combusted. Monitoring the presence of a pilot flame is required in many federal rules, including: 40 CFR Part 60, Subparts K, III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; and 40 CFR Part 63, Subparts G, R, W, DD, and HH.	

Unit/Group/Process Information	
ID No.: 10MSV261	
Control Device ID No.: 15BLR001	Control Device Type: Steam Generating Unit (Boiler)/Process Heater (Design heat input is greater than or equal to 44MW)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-6
Pollutant: VOC	Main Standard: § 115.122(b)
Monitoring Information	
Indicator: Period of Operation	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: Any period when any unit in 10MSV261 is routed to the steam generating unit, and the steam generating unit is not operating.	
<p>Basis of CAM: A common way to control VOC emissions is to route emissions to a boiler or process heater with a design heat input capacity of 44 MW or greater with minimum temperatures of 1100 °C and residence times greater than one second. Boilers and process heaters with the stated design have demonstrated to meet 98% reduction efficiency; therefore, it is only necessary to document the period of operation of the control equipment. Additionally, in the October, 21, 1983 preamble to 40 CFR Part 60, Subpart III, (48 FR 48945), the EPA determined that installing a steam generating unit, with a design heat input capacity of 44 MW or greater, to control VOC emissions, is an acceptable means of demonstrating compliance with 40 CFR Part 60, Subpart III and waived the requirement for a performance test on such devices. Monitoring the period of operation of a boiler/process heater greater than 44 MW is commonly required in federal rules, including: 40 CFR Part 60, Subparts III and NNN; 40 CFR Part 61, Subpart BB; 40 CFR Part 63, Subpart G.</p>	

Unit/Group/Process Information	
ID No.: 10MSV261	
Control Device ID No.: 15BLR002	Control Device Type: Steam Generating Unit (Boiler)/Process Heater (Design heat input is greater than or equal to 44MW)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-7
Pollutant: VOC	Main Standard: § 115.122(b)
Monitoring Information	
Indicator: Period of Operation	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: Any period when any unit in 10MSV261 is routed to the steam generating unit, and the steam generating unit is not operating.	
<p>Basis of CAM: A common way to control VOC emissions is to route emissions to a boiler or process heater with a design heat input capacity of 44 MW or greater with minimum temperatures of 1100 °C and residence times greater than one second. Boilers and process heaters with the stated design have demonstrated to meet 98% reduction efficiency; therefore, it is only necessary to document the period of operation of the control equipment. Additionally, in the October, 21, 1983 preamble to 40 CFR Part 60, Subpart III, (48 FR 48945), the EPA determined that installing a steam generating unit, with a design heat input capacity of 44 MW or greater, to control VOC emissions, is an acceptable means of demonstrating compliance with 40 CFR Part 60, Subpart III and waived the requirement for a performance test on such devices. Monitoring the period of operation of a boiler/process heater greater than 44 MW is commonly required in federal rules, including: 40 CFR Part 60, Subparts III and NNN; 40 CFR Part 61, Subpart BB; 40 CFR Part 63, Subpart G.</p>	

Unit/Group/Process Information	
ID No.: 10MSV261	
Control Device ID No.: 15BLR003	Control Device Type: Steam Generating Unit (Boiler)/Process Heater (Design heat input is greater than or equal to 44MW)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-8
Pollutant: VOC	Main Standard: § 115.122(b)
Monitoring Information	
Indicator: Period of Operation	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: Any period when any unit in 10MSV261 is routed to the steam generating unit, and the steam generating unit is not operating.	
<p>Basis of CAM: A common way to control VOC emissions is to route emissions to a boiler or process heater with a design heat input capacity of 44 MW or greater with minimum temperatures of 1100 °C and residence times greater than one second. Boilers and process heaters with the stated design have demonstrated to meet 98% reduction efficiency; therefore, it is only necessary to document the period of operation of the control equipment. Additionally, in the October, 21, 1983 preamble to 40 CFR Part 60, Subpart III, (48 FR 48945), the EPA determined that installing a steam generating unit, with a design heat input capacity of 44 MW or greater, to control VOC emissions, is an acceptable means of demonstrating compliance with 40 CFR Part 60, Subpart III and waived the requirement for a performance test on such devices. Monitoring the period of operation of a boiler/process heater greater than 44 MW is commonly required in federal rules, including: 40 CFR Part 60, Subparts III and NNN; 40 CFR Part 61, Subpart BB; 40 CFR Part 63, Subpart G.</p>	

Unit/Group/Process Information	
ID No.: 10MSV261	
Control Device ID No.: 15BLR004	Control Device Type: Steam Generating Unit (Boiler)/Process Heater (Design heat input is greater than or equal to 44MW)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-9
Pollutant: VOC	Main Standard: § 115.122(b)
Monitoring Information	
Indicator: Period of Operation	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: Any period when any unit in 10MSV261 is routed to the steam generating unit, and the steam generating unit is not operating.	
<p>Basis of CAM: A common way to control VOC emissions is to route emissions to a boiler or process heater with a design heat input capacity of 44 MW or greater with minimum temperatures of 1100 °C and residence times greater than one second. Boilers and process heaters with the stated design have demonstrated to meet 98% reduction efficiency; therefore, it is only necessary to document the period of operation of the control equipment. Additionally, in the October, 21, 1983 preamble to 40 CFR Part 60, Subpart III, (48 FR 48945), the EPA determined that installing a steam generating unit, with a design heat input capacity of 44 MW or greater, to control VOC emissions, is an acceptable means of demonstrating compliance with 40 CFR Part 60, Subpart III and waived the requirement for a performance test on such devices. Monitoring the period of operation of a boiler/process heater greater than 44 MW is commonly required in federal rules, including: 40 CFR Part 60, Subparts III and NNN; 40 CFR Part 61, Subpart BB; 40 CFR Part 63, Subpart G.</p>	

Unit/Group/Process Information	
ID No.: 10NGP	
Control Device ID No.: 10FLR005	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-3
Pollutant: VOC	Main Standard: § 115.122(b)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: n/a	
Deviation Limit: Lack of pilot flame or failure to record status of pilot flame at least once every 15 minutes when the vent from 10NGP is routed to Flare 10FLR005.	
Basis of CAM: It is widely practiced and accepted to monitor the flare pilot flame by closed circuit cameras, thermocouples and visual inspection. The presence of the pilot flame demonstrates that VOC emissions are combusted. Monitoring the presence of a pilot flame is required in many federal rules, including: 40 CFR Part 60, Subparts K, III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; and 40 CFR Part 63, Subparts G, R, W, DD, and HH.	

Unit/Group/Process Information	
ID No.: 10RSY219-1	
Control Device ID No.: 10FLR001	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-2
Pollutant: VOC	Main Standard: § 115.122(b)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: n/a	
Deviation Limit: Except for periods during which 10RSY219-1 is shut down, lack of a pilot flame shall be reported as a deviation, or failure to record status of the pilot flame at least once every 15 minutes shall be reported as a deviation.	
Basis of CAM: It is widely practiced and accepted to monitor the flare pilot flame by closed circuit cameras, thermocouples and visual inspection. The presence of the pilot flame demonstrates that VOC emissions are combusted. Monitoring the presence of a pilot flame is required in many federal rules, including: 40 CFR Part 60, Subparts K, III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; and 40 CFR Part 63, Subparts G, R, W, DD, and HH.	

Unit/Group/Process Information	
ID No.: 10RSY219-2	
Control Device ID No.: 10FLR002	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-2
Pollutant: VOC	Main Standard: § 115.122(b)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: n/a	
Deviation Limit: Except for periods during which 10RSY219-2 is shut down, lack of a pilot flame shall be reported as a deviation, or failure to record status of the pilot flame at least once every 15 minutes shall be reported as a deviation.	
Basis of CAM: It is widely practiced and accepted to monitor the flare pilot flame by closed circuit cameras, thermocouples and visual inspection. The presence of the pilot flame demonstrates that VOC emissions are combusted. Monitoring the presence of a pilot flame is required in many federal rules, including: 40 CFR Part 60, Subparts K, III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; and 40 CFR Part 63, Subparts G, R, W, DD, and HH.	

Unit/Group/Process Information	
ID No.: 10RSY219-3	
Control Device ID No.: 10FLR003	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-2
Pollutant: VOC	Main Standard: § 115.122(b)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: n/a	
Deviation Limit: Except for periods during which 10RSY219-3 is shut down, lack of a pilot flame shall be reported as a deviation, or failure to record status of the pilot flame at least once every 15 minutes shall be reported as a deviation.	
Basis of CAM: It is widely practiced and accepted to monitor the flare pilot flame by closed circuit cameras, thermocouples and visual inspection. The presence of the pilot flame demonstrates that VOC emissions are combusted. Monitoring the presence of a pilot flame is required in many federal rules, including: 40 CFR Part 60, Subparts K, III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; and 40 CFR Part 63, Subparts G, R, W, DD, and HH.	

Unit/Group/Process Information	
ID No.: 10RSY219-4	
Control Device ID No.: 10FLR003A	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-2
Pollutant: VOC	Main Standard: § 115.122(b)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: n/a	
Deviation Limit: Except for periods during which 10RSY219-4 is shut down, lack of a pilot flame shall be reported as a deviation, or failure to record status of the pilot flame at least once every 15 minutes shall be reported as a deviation.	
Basis of CAM: It is widely practiced and accepted to monitor the flare pilot flame by closed circuit cameras, thermocouples and visual inspection. The presence of the pilot flame demonstrates that VOC emissions are combusted. Monitoring the presence of a pilot flame is required in many federal rules, including: 40 CFR Part 60, Subparts K, III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; and 40 CFR Part 63, Subparts G, R, W, DD, and HH.	

Unit/Group/Process Information	
ID No.: 10TFX015	
Control Device ID No.: 10FLR005	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-2
Pollutant: VOC	Main Standard: § 115.122(b)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: n/a	
Deviation Limit: Lack of pilot flame or failure to record status of pilot flame at least once every 15 minutes when the vent from 10TFX15 is routed to Flare 10FLR005.	
Basis of CAM: It is widely practiced and accepted to monitor the flare pilot flame by closed circuit cameras, thermocouples and visual inspection. The presence of the pilot flame demonstrates that VOC emissions are combusted. Monitoring the presence of a pilot flame is required in many federal rules, including: 40 CFR Part 60, Subparts K, III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; and 40 CFR Part 63, Subparts G, R, W, DD, and HH.	

Unit/Group/Process Information	
ID No.: 10TFX018	
Control Device ID No.: 10TFX005	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-2
Pollutant: VOC	Main Standard: § 115.122(b)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: n/a	
Deviation Limit: Lack of pilot flame or failure to record status of pilot flame at least once every 15 minutes when the vent from 10TFX018 is routed to Flare 10FLR005.	
Basis of CAM: It is widely practiced and accepted to monitor the flare pilot flame by closed circuit cameras, thermocouples and visual inspection. The presence of the pilot flame demonstrates that VOC emissions are combusted. Monitoring the presence of a pilot flame is required in many federal rules, including: 40 CFR Part 60, Subparts K, III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; and 40 CFR Part 63, Subparts G, R, W, DD, and HH.	

Unit/Group/Process Information	
ID No.: 10TFX340	
Control Device ID No.: 10FLR005	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-2
Pollutant: VOC	Main Standard: § 115.122(b)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: n/a	
Deviation Limit: Lack of pilot flame or failure to record status of pilot flame at least once every 15 minutes when the vent from 10TFX340 is routed to Flare 10FLR005.	
Basis of CAM: It is widely practiced and accepted to monitor the flare pilot flame by closed circuit cameras, thermocouples and visual inspection. The presence of the pilot flame demonstrates that VOC emissions are combusted. Monitoring the presence of a pilot flame is required in many federal rules, including: 40 CFR Part 60, Subparts K, III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; and 40 CFR Part 63, Subparts G, R, W, DD, and HH.	

Unit/Group/Process Information	
ID No.: 10TFX341	
Control Device ID No.: 10TFLO05	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-2
Pollutant: VOC	Main Standard: § 115.122(b)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: n/a	
Deviation Limit: Lack of pilot flame or failure to record status of pilot flame at least once every 15 minutes when the vent from 10TFX341 is routed to Flare 10FLR005.	
Basis of CAM: It is widely practiced and accepted to monitor the flare pilot flame by closed circuit cameras, thermocouples and visual inspection. The presence of the pilot flame demonstrates that VOC emissions are combusted. Monitoring the presence of a pilot flame is required in many federal rules, including: 40 CFR Part 60, Subparts K, III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; and 40 CFR Part 63, Subparts G, R, W, DD, and HH.	

Unit/Group/Process Information	
ID No.: 10TFX343	
Control Device ID No.: 10FLR005	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-2
Pollutant: VOC	Main Standard: § 115.122(b)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: n/a	
Deviation Limit: Lack of pilot flame or failure to record status of pilot flame at least once every 15 minutes when the vent from 10TFX343 is routed to Flare 10FLR005.	
Basis of CAM: It is widely practiced and accepted to monitor the flare pilot flame by closed circuit cameras, thermocouples and visual inspection. The presence of the pilot flame demonstrates that VOC emissions are combusted. Monitoring the presence of a pilot flame is required in many federal rules, including: 40 CFR Part 60, Subparts K, III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; and 40 CFR Part 63, Subparts G, R, W, DD, and HH.	

Unit/Group/Process Information	
ID No.: 10TFX344	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-2
Pollutant: VOC	Main Standard: § 115.122(b)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: n/a	
Deviation Limit: Lack of pilot flame or failure to record status of pilot flame at least once every 15 minutes when the vent from 10TFX344 is routed to Flare 10FLR005.	
Basis of CAM: It is widely practiced and accepted to monitor the flare pilot flame by closed circuit cameras, thermocouples and visual inspection. The presence of the pilot flame demonstrates that VOC emissions are combusted. Monitoring the presence of a pilot flame is required in many federal rules, including: 40 CFR Part 60, Subparts K, III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; and 40 CFR Part 63, Subparts G, R, W, DD, and HH.	

Unit/Group/Process Information	
ID No.: 10TFX345	
Control Device ID No.: 10FLR005	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-2
Pollutant: VOC	Main Standard: § 115.122(b)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: n/a	
Deviation Limit: Lack of pilot flame or failure to record status of pilot flame at least once every 15 minutes when the vent from 10TFX345 is routed to Flare 10FLR005.	
Basis of CAM: It is widely practiced and accepted to monitor the flare pilot flame by closed circuit cameras, thermocouples and visual inspection. The presence of the pilot flame demonstrates that VOC emissions are combusted. Monitoring the presence of a pilot flame is required in many federal rules, including: 40 CFR Part 60, Subparts K, III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; and 40 CFR Part 63, Subparts G, R, W, DD, and HH.	

Unit/Group/Process Information	
ID No.: 10TFX350	
Control Device ID No.: 10FLR005	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-3
Pollutant: VOC	Main Standard: § 115.122(b)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: n/a	
Deviation Limit: Except for periods during which 10TFX350 is shut down, lack of a pilot flame shall be reported as a deviation, or failure to record status of the pilot flame at least once every 15 minutes shall be reported as a deviation.	
Basis of CAM: It is widely practiced and accepted to monitor the flare pilot flame by closed circuit cameras, thermocouples and visual inspection. The presence of the pilot flame demonstrates that VOC emissions are combusted. Monitoring the presence of a pilot flame is required in many federal rules, including: 40 CFR Part 60, Subparts K, III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; and 40 CFR Part 63, Subparts G, R, W, DD, and HH.	

Unit/Group/Process Information	
ID No.: GRP10DIS01	
Control Device ID No.: 10FLR005	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-3
Pollutant: VOC	Main Standard: § 115.122(b)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: n/a	
Deviation Limit: Lack of pilot flame or failure to record status of pilot flame at least once every 15 minutes when the vent from GRP10DIS01 is routed to Flare 10FLR005.	
Basis of CAM: It is widely practiced and accepted to monitor the flare pilot flame by closed circuit cameras, thermocouples and visual inspection. The presence of the pilot flame demonstrates that VOC emissions are combusted. Monitoring the presence of a pilot flame is required in many federal rules, including: 40 CFR Part 60, Subparts K, III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; and 40 CFR Part 63, Subparts G, R, W, DD, and HH.	

Unit/Group/Process Information	
ID No.: GRP10DISo3	
Control Device ID No.: 10FLR005	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-3
Pollutant: VOC	Main Standard: § 115.122(b)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: n/a	
Deviation Limit: Lack of pilot flame or failure to record status of pilot flame at least once every 15 minutes when the vent from GRP10DISo3 is routed to Flare 10FLR005.	
Basis of CAM: It is widely practiced and accepted to monitor the flare pilot flame by closed circuit cameras, thermocouples and visual inspection. The presence of the pilot flame demonstrates that VOC emissions are combusted. Monitoring the presence of a pilot flame is required in many federal rules, including: 40 CFR Part 60, Subparts K, III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; and 40 CFR Part 63, Subparts G, R, W, DD, and HH.	

Unit/Group/Process Information	
ID No.: GRP10DIS05	
Control Device ID No.: 10FLR005	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-2
Pollutant: VOC	Main Standard: § 115.122(b)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: n/a	
Deviation Limit: Lack of pilot flame or failure to record status of pilot flame at least once every 15 minutes when the vent from GRP10DIS05 is routed to Flare 10FLR005.	
Basis of CAM: It is widely practiced and accepted to monitor the flare pilot flame by closed circuit cameras, thermocouples and visual inspection. The presence of the pilot flame demonstrates that VOC emissions are combusted. Monitoring the presence of a pilot flame is required in many federal rules, including: 40 CFR Part 60, Subparts K, III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; and 40 CFR Part 63, Subparts G, R, W, DD, and HH.	

Unit/Group/Process Information	
ID No.: GRP10DIS06	
Control Device ID No.: 10FLR005	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-3
Pollutant: VOC	Main Standard: § 115.122(b)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: n/a	
Deviation Limit: Lack of pilot flame or failure to record status of pilot flame at least once every 15 minutes when the vent from GRP10DIS06 is routed to Flare 10FLR005.	
Basis of CAM: It is widely practiced and accepted to monitor the flare pilot flame by closed circuit cameras, thermocouples and visual inspection. The presence of the pilot flame demonstrates that VOC emissions are combusted. Monitoring the presence of a pilot flame is required in many federal rules, including: 40 CFR Part 60, Subparts K, III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; and 40 CFR Part 63, Subparts G, R, W, DD, and HH.	

Unit/Group/Process Information	
ID No.: GRP10DIS16	
Control Device ID No.: 10FLR005	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-3
Pollutant: VOC	Main Standard: § 115.122(b)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: n/a	
Deviation Limit: Lack of pilot flame or failure to record status of pilot flame at least once every 15 minutes when the vent from GRP10DIS16 is routed to Flare 10FLR005.	
Basis of CAM: It is widely practiced and accepted to monitor the flare pilot flame by closed circuit cameras, thermocouples and visual inspection. The presence of the pilot flame demonstrates that VOC emissions are combusted. Monitoring the presence of a pilot flame is required in many federal rules, including: 40 CFR Part 60, Subparts K, III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; and 40 CFR Part 63, Subparts G, R, W, DD, and HH.	

Unit/Group/Process Information	
ID No.: GRP10DIS16	
Control Device ID No.: 10FLR004	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-5
Pollutant: VOC	Main Standard: § 115.122(b)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: n/a	
Deviation Limit: Lack of pilot flame or failure to record status of pilot flame at least once every 15 minutes when the vent from GRP10DIS16 is routed to Flare 10FLR004.	
Basis of CAM: It is widely practiced and accepted to monitor the flare pilot flame by closed circuit cameras, thermocouples and visual inspection. The presence of the pilot flame demonstrates that VOC emissions are combusted. Monitoring the presence of a pilot flame is required in many federal rules, including: 40 CFR Part 60, Subparts K, III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; and 40 CFR Part 63, Subparts G, R, W, DD, and HH.	

Unit/Group/Process Information	
ID No.: GRP10DIS16	
Control Device ID No.: 15BLR003	Control Device Type: Steam Generating Unit (Boiler)/Process Heater (Design heat input is greater than or equal to 44MW)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-8
Pollutant: VOC	Main Standard: § 115.122(b)
Monitoring Information	
Indicator: Period of Operation	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: Any period when any unit in GRP10DIS16 is routed to the steam generating unit, and the steam generating unit is not operating.	
<p>Basis of CAM: A common way to control VOC emissions is to route emissions to a boiler or process heater with a design heat input capacity of 44 MW or greater with minimum temperatures of 1100 °C and residence times greater than one second. Boilers and process heaters with the stated design have demonstrated to meet 98% reduction efficiency; therefore, it is only necessary to document the period of operation of the control equipment. Additionally, in the October, 21, 1983 preamble to 40 CFR Part 60, Subpart III, (48 FR 48945), the EPA determined that installing a steam generating unit, with a design heat input capacity of 44 MW or greater, to control VOC emissions, is an acceptable means of demonstrating compliance with 40 CFR Part 60, Subpart III and waived the requirement for a performance test on such devices. Monitoring the period of operation of a boiler/process heater greater than 44 MW is commonly required in federal rules, including: 40 CFR Part 60, Subparts III and NNN; 40 CFR Part 61, Subpart BB; 40 CFR Part 63, Subpart G.</p>	

Unit/Group/Process Information	
ID No.: GRP10DIS16	
Control Device ID No.: 15BLR004	Control Device Type: Steam Generating Unit (Boiler)/Process Heater (Design heat input is greater than or equal to 44MW)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-9
Pollutant: VOC	Main Standard: § 115.122(b)
Monitoring Information	
Indicator: Period of Operation	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: Any period when any unit in GRP10DIS16 is routed to the steam generating unit, and the steam generating unit is not operating.	
<p>Basis of CAM: A common way to control VOC emissions is to route emissions to a boiler or process heater with a design heat input capacity of 44 MW or greater with minimum temperatures of 1100 °C and residence times greater than one second. Boilers and process heaters with the stated design have demonstrated to meet 98% reduction efficiency; therefore, it is only necessary to document the period of operation of the control equipment. Additionally, in the October, 21, 1983 preamble to 40 CFR Part 60, Subpart III, (48 FR 48945), the EPA determined that installing a steam generating unit, with a design heat input capacity of 44 MW or greater, to control VOC emissions, is an acceptable means of demonstrating compliance with 40 CFR Part 60, Subpart III and waived the requirement for a performance test on such devices. Monitoring the period of operation of a boiler/process heater greater than 44 MW is commonly required in federal rules, including: 40 CFR Part 60, Subparts III and NNN; 40 CFR Part 61, Subpart BB; 40 CFR Part 63, Subpart G.</p>	

Unit/Group/Process Information	
ID No.: GRP10PV002	
Control Device ID No.: 10VNT255	Control Device Type: Wet Scrubber
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-3
Pollutant: VOC	Main Standard: § 115.122(b)
Monitoring Information	
Indicator: Temperature and Flow Rate	
Minimum Frequency: Once per hour	
Averaging Period: Daily	
Deviation Limit: Daily average scrubbing liquid temperature greater than 30 C during normal operation or 65 C during maintenance, startup and shutdown (MSS) activities, or daily average scrubbing liquid flow rate less than 16,000 lbs/hr, except for periods during whi	
Basis of CAM: The option to monitor pressure drop and liquid flow rate may indicate malfunctions in the liquid pumping equipment, blockage of pipes or spray nozzles or the need to adjust the variable throat opening (if applicable). This type monitoring for wet scrubbers is commonly required in federal rules including 40 CFR Part 60, Subparts Y, HH, LL, NN, OOO, and PPP.	

Periodic Monitoring:

The Federal Clean Air Act requires that each federal operating permit include monitoring sufficient to assure compliance with the terms and conditions of the permit. Most of the emission limits and standards applicable to emission units at Title V sources include adequate monitoring to show that the units meet the limits and standards. For those requirements that do not include monitoring, or where the monitoring is not sufficient to assure compliance, the federal operating permit must include such monitoring for the emission units affected. The following emission units are subject to periodic monitoring requirements because the emission units are subject to an emission limitation or standard for an air pollutant (or surrogate thereof) in an applicable requirement that does not already require monitoring, or the monitoring for the applicable requirement is not sufficient to assure compliance:

Unit/Group/Process Information	
ID No.: 10DEG068	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Degreasing Processes	SOP Index No.: R5412-1
Pollutant: VOC	Main Standard: § 115.412(1)
Monitoring Information	
Indicator: Visual Inspection	
Minimum Frequency: Monthly	
Averaging Period: n/a	
Deviation Limit: Any monitoring data that indicates that the cold solvent cleaner is not in compliance with the applicable requirements of 30 TAC §115.412(1)(A)-(F) shall be considered and reported as a deviation.	
Basis of monitoring: The monitoring option to cover cold cleaner or the open-top vapor cleaner was included in the EPA “Periodic Monitoring Technical Reference Document” (April 1999) to monitor VOC sources. In addition to covering the cleaner records of monthly inspections of equipment is an effective way to ensure that the system is operating in accordance with its design.	

Unit/Group/Process Information	
ID No.: 10TFX047	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-16
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Liquid Level	
Minimum Frequency: Once per day*	
Averaging Period: n/a	
Deviation Limit: Liquid level below fill pipe level.	
<p>Basis of monitoring: The periodic monitoring option provided for emission units using a submerged fill pipe is location of the submerged fill pipe and structural integrity of the pipe. The location and the integrity of the pipe ensure that loading operations are controlled to prevent splash fill and reduce generated vapors; therefore, less emissions are released to the atmosphere. This approach was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources.</p>	

Unit/Group/Process Information	
ID No.: 10TFX047	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-16
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Structural Integrity of the Pipe	
Minimum Frequency: Emptied and degassed	
Averaging Period: n/a	
Deviation Limit: Repairs to fill pipe not completed prior to refilling the storage vessel.	
<p>Basis of monitoring: The periodic monitoring option provided for emission units using a submerged fill pipe is location of the submerged fill pipe and structural integrity of the pipe. The location and the integrity of the pipe ensure that loading operations are controlled to prevent splash fill and reduce generated vapors; therefore, less emissions are released to the atmosphere. This approach was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources.</p>	

Compliance History Review

1. In accordance with 30 TAC Chapter 60, the compliance history was reviewed on June 9, 2016.

Site rating: 2.30 / Satisfactory Company rating: 8.15 / Satisfactory

(High < 0.10; Satisfactory ≥ 0.10 and < 55; Unsatisfactory > 55)

2. Has the permit changed on the basis of the compliance history or site/company rating?No

Available Unit Attribute Forms

- OP-UA1 - Miscellaneous and Generic Unit Attributes
- OP-UA2 - Stationary Reciprocating Internal Combustion Engine Attributes
- OP-UA3 - Storage Tank/Vessel Attributes
- OP-UA4 - Loading/Unloading Operations Attributes
- OP-UA5 - Process Heater/Furnace Attributes
- OP-UA6 - Boiler/Steam Generator/Steam Generating Unit Attributes
- OP-UA7 - Flare Attributes
- OP-UA8 - Coal Preparation Plant Attributes
- OP-UA9 - Nonmetallic Mineral Process Plant Attributes
- OP-UA10 - Gas Sweetening/Sulfur Recovery Unit Attributes
- OP-UA11 - Stationary Turbine Attributes
- OP-UA12 - Fugitive Emission Unit Attributes
- OP-UA13 - Industrial Process Cooling Tower Attributes
- OP-UA14 - Water Separator Attributes
- OP-UA15 - Emission Point/Stationary Vent/Distillation Operation/Process Vent Attributes
- OP-UA16 - Solvent Degreasing Machine Attributes
- OP-UA17 - Distillation Unit Attributes
- OP-UA18 - Surface Coating Operations Attributes
- OP-UA19 - Wastewater Unit Attributes
- OP-UA20 - Asphalt Operations Attributes
- OP-UA21 - Grain Elevator Attributes
- OP-UA22 - Printing Attributes
- OP-UA24 - Wool Fiberglass Insulation Manufacturing Plant Attributes
- OP-UA25 - Synthetic Fiber Production Attributes
- OP-UA26 - Electroplating and Anodizing Unit Attributes
- OP-UA27 - Nitric Acid Manufacturing Attributes
- OP-UA28 - Polymer Manufacturing Attributes
- OP-UA29 - Glass Manufacturing Unit Attributes
- OP-UA30 - Kraft, Soda, Sulfite, and Stand-Alone Semichemical Pulp Mill Attributes
- OP-UA31 - Lead Smelting Attributes
- OP-UA32 - Copper and Zinc Smelting/Brass and Bronze Production Attributes
- OP-UA33 - Metallic Mineral Processing Plant Attributes
- OP-UA34 - Pharmaceutical Manufacturing
- OP-UA35 - Incinerator Attributes
- OP-UA36 - Steel Plant Unit Attributes
- OP-UA37 - Basic Oxygen Process Furnace Unit Attributes
- OP-UA38 - Lead-Acid Battery Manufacturing Plant Attributes
- OP-UA39 - Sterilization Source Attributes
- OP-UA40 - Ferroalloy Production Facility Attributes
- OP-UA41 - Dry Cleaning Facility Attributes
- OP-UA42 - Phosphate Fertilizer Manufacturing Attributes
- OP-UA43 - Sulfuric Acid Production Attributes
- OP-UA44 - Municipal Solid Waste Landfill/Waste Disposal Site Attributes
- OP-UA45 - Surface Impoundment Attributes

OP-UA46 - Epoxy Resins and Non-Nylon Polyamides Production Attributes
OP-UA47 - Ship Building and Ship Repair Unit Attributes
OP-UA48 - Air Oxidation Unit Process Attributes
OP-UA49 - Vacuum-Producing System Attributes
OP-UA50 - Fluid Catalytic Cracking Unit Catalyst Regenerator/Fuel Gas Combustion Device/Claus Sulfur Recovery Plant Attributes
OP-UA51 - Dryer/Kiln/Oven Attributes
OP-UA52 - Closed Vent Systems and Control Devices
OP-UA53 - Beryllium Processing Attributes
OP-UA54 - Mercury Chlor-Alkali Cell Attributes
OP-UA55 - Transfer System Attributes
OP-UA56 - Vinyl Chloride Process Attributes
OP-UA57 - Cleaning/Depainting Operation Attributes
OP-UA58 - Treatment Process Attributes
OP-UA59 - Coke By-Product Recovery Plant Attributes
OP-UA60 - Chemical Manufacturing Process Unit Attributes
OP-UA61 - Pulp, Paper, or Paperboard Producing Process Attributes
OP-UA62 - Glycol Dehydration Unit Attributes
OP-UA63 - Vegetable Oil Production Attributes