FEDERAL OPERATING PERMIT

A FEDERAL OPERATING PERMIT IS HEREBY ISSUED TO
The Premcor Refining Group Inc.

AUTHORIZING THE OPERATION OF
Valero Port Arthur Refinery
Petroleum Refineries

LOCATED AT
Jefferson County, Texas
Latitude 29° 51' 14" Longitude 93° 57' 57"
Regulated Entity Number: RN102584026

This permit is issued in accordance with and subject to the Texas Clean Air Act (TCAA), Chapter 382 of the Texas Health and Safety Code and Title 30 Texas Administrative Code Chapter 122 (30 TAC Chapter 122), Federal Operating Permits. Under 30 TAC Chapter 122, this permit constitutes the permit holder's authority to operate the site and emission units listed in this permit. Operations of the site and emission units listed in this permit are subject to all additional rules or amended rules and orders of the Commission pursuant to the TCAA.

This permit does not relieve the permit holder from the responsibility of obtaining New Source Review authorization for new, modified, or existing facilities in accordance with 30 TAC Chapter 116, Control of Air Pollution by Permits for New Construction or Modification.

The site and emission units authorized by this permit shall be operated in accordance with 30 TAC Chapter 122, the general terms and conditions, special terms and conditions, and attachments contained herein.

This permit shall expire five years from the date of issuance. The renewal requirements specified in 30 TAC § 122.241 must be satisfied in order to renew the authorization to operate the site and emission units.

Permit No: O1498 Issuance Date: January 2, 2018

For the Commission

Table of Contents

Section **Page**

General Terms and Conditions 1

Special Terms and Conditions: 1
- Emission Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting 1
- Additional Monitoring Requirements 11
- New Source Review Authorization Requirements 13
- Compliance Requirements 14
- Risk Management Plan 16
- Protection of Stratospheric Ozone 16
- Alternative Requirements 16
- Permit Location 16
- Permit Shield (30 TAC § 122.148) 16

Attachments 18
- Applicable Requirements Summary 19
- Additional Monitoring Requirements 343
- Permit Shield 357
- New Source Review Authorization References 365
- Alternative Requirement 382

Appendix A 385
- Acronym List 386

Appendix B 387

General Terms and Conditions

The permit holder shall comply with all terms and conditions contained in 30 TAC § 122.143 (General Terms and Conditions), 30 TAC § 122.144 (Recordkeeping Terms and Conditions), 30 TAC § 122.145 (Reporting Terms and Conditions), and 30 TAC § 122.146 (Compliance Certification Terms and Conditions).

In accordance with 30 TAC § 122.144(1), records of required monitoring data and support information required by this permit, or any applicable requirement codified in this permit, are required to be maintained for a period of five years from the date of the monitoring report, sample, or application unless a longer data retention period is specified in an applicable requirement. The five year record retention period supersedes any less stringent retention requirement that may be specified in a condition of a permit identified in the New Source Review Authorization attachment.

If the permit holder chooses to demonstrate that this permit is no longer required, a written request to void this permit shall be submitted to the Texas Commission on Environmental Quality (TCEQ) by the Responsible Official in accordance with 30 TAC § 122.161(e). The permit holder shall comply with the permit's requirements, including compliance certification and deviation reporting, until notified by the TCEQ that this permit is voided.

The permit holder shall comply with 30 TAC Chapter 116 by obtaining a New Source Review authorization prior to new construction or modification of emission units located in the area covered by this permit.

All reports required by this permit must include in the submittal a cover letter which identifies the following information: company name, TCEQ regulated entity number, air account number (if assigned), site name, area name (if applicable), and Air Permits Division permit number(s).

Special Terms and Conditions:

Emission Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting

1. Permit holder shall comply with the following requirements:

    A. Emission units (including groups and processes) in the Applicable Requirements Summary attachment shall meet the limitations, standards, equipment specifications, monitoring, recordkeeping, reporting, testing, and other requirements listed in the Applicable Requirements Summary attachment to assure compliance with the permit.

    B. The textual description in the column titled "Textual Description" in the Applicable Requirements Summary attachment is not enforceable and is not deemed as a substitute for the actual regulatory language. The Textual Description is provided for information purposes only.

    C. A citation listed on the Applicable Requirements Summary attachment, which has a notation [G] listed before it, shall include the referenced section and subsection for all commission rules, or paragraphs for all federal and state regulations and all subordinate paragraphs, subparagraphs and clauses, subclauses, and items contained within the referenced citation as applicable requirements.

    D. When a grouped citation, notated with a [G] in the Applicable Requirements Summary, contains multiple compliance options, the permit holder must keep records of when each compliance option was used.

    E. Emission units subject to 40 CFR Part 63, Subparts A, G, Y, CC, VV, UUU, ZZZZ, and DDDDD as identified in the attached Applicable Requirements Summary table are

subject to 30 TAC Chapter 113, Subchapter C, §§ 113.100, 113.120, 113.300, 113.340, 113.530, 113.780, 113.1090, and 113.1130 respectively, which incorporate the 40 CFR Part 63 Subparts by reference.

2. The permit holder shall comply with the following sections of 30 TAC Chapter 101 (General Air Quality Rules):

   A. Title 30 TAC § 101.1 (relating to Definitions), insofar as the terms defined in this section are used to define the terms used in other applicable requirements

   B. Title 30 TAC § 101.3 (relating to Circumvention)

   C. Title 30 TAC § 101.8 (relating to Sampling), if such action has been requested by the TCEQ

   D. Title 30 TAC § 101.9 (relating to Sampling Ports), if such action has been requested by the TCEQ

   E. Title 30 TAC § 101.10 (relating to Emissions Inventory Requirements)

   F. Title 30 TAC § 101.201 (relating to Emission Event Reporting and Recordkeeping Requirements)

   G. Title 30 TAC § 101.211 (relating to Scheduled Maintenance, Start-up, and Shutdown Reporting and Recordkeeping Requirements)

   H. Title 30 TAC § 101.221 (relating to Operational Requirements)

   I. Title 30 TAC § 101.222 (relating to Demonstrations)

   J. Title 30 TAC § 101.223 (relating to Actions to Reduce Excessive Emissions)

3. Permit holder shall comply with the following requirements of 30 TAC Chapter 111:

   A. Visible emissions from stationary vents with a flow rate of less than 100,000 actual cubic feet per minute and constructed after January 31, 1972 that are not listed in the Applicable Requirements Summary attachment for 30 TAC Chapter 111, Subchapter A, Division 1, shall not exceed 20% opacity averaged over a six-minute period. The permit holder shall comply with the following requirements for stationary vents at the site subject to this standard:

      (i) Title 30 TAC § 111.111(a)(1)(B) (relating to Requirements for Specified Sources)

      (ii) Title 30 TAC § 111.111(a)(1)(E)

      (iii) Title 30 TAC § 111.111(a)(1)(F)(i), (ii), (iii), or (iv)

      (iv) For emission units with vent emissions subject to 30 TAC § 111.111(a)(1)(B), complying with 30 TAC § 111.111(a)(1)(F)(ii), (iii), or (iv), and capable of producing visible emissions from, but not limited to, particulate matter, acid gases and NO_x, the permit holder shall also comply with the following periodic monitoring requirements for the purpose of annual compliance certification under 30 TAC § 122.146. These periodic monitoring requirements do not apply to vents that are not capable of producing visible emissions such as vents that emit only colorless VOCs; vents from non-fuming liquids; vents that provide passive

ventilation, such as plumbing vents; or vent emissions from any other source that does not obstruct the transmission of light. Vents, as specified in the "Applicable Requirements Summary" attachment, that are subject to the emission limitation of 30 TAC § 111.111(a)(1)(B) are not subject to the following periodic monitoring requirements:

(1) An observation of stationary vents from emission units in operation shall be conducted at least once during each calendar quarter unless the emission unit is not operating for the entire quarter.

(2) For stationary vents from a combustion source, if an alternative to the normally fired fuel is fired for a period greater than or equal to 24 consecutive hours, the permit holder shall conduct an observation of the stationary vent for each such period to determine if visible emissions are present. If such period is greater than 3 months, observations shall be conducted once during each quarter. Supplementing the normally fired fuel with natural gas or fuel gas to increase the net heating value to the minimum required value does not constitute creation of an alternative fuel.

(3) Records of all observations shall be maintained.

(4) Visible emissions observations of emission units operated during daylight hours shall be conducted no earlier than one hour after sunrise and no later than one hour before sunset. Visible emissions observations of emission units operated only at night must be made with additional lighting and the temporary installation of contrasting backgrounds. Visible emissions observations shall be made during times when the activities described in 30 TAC § 111.111(a)(1)(E) are not taking place. Visible emissions shall be determined with each stationary vent in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 mile, away from each stationary vent during the observation. For outdoor locations, the observer shall select a position where the sun is not directly in the observer's eyes. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. A certified opacity reader is not required for visible emissions observations.

(5) Compliance Certification:

(a) If visible emissions are not present during the observation, the RO may certify that the source is in compliance with the applicable opacity requirement in 30 TAC § 111.111(a)(1) and (a)(1)(B).

(b) However, if visible emissions are present during the observation, the permit holder shall either list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(1)(F) as soon as practicable, but no later than 24 hours after observing visible emissions to determine if the source is in compliance with the opacity

requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.

(c) Some vents may be subject to multiple visible emission or monitoring requirements. All credible data must be considered when certifying compliance with this requirement even if the observation or monitoring was performed to demonstrate compliance with a different requirement.

B. For visible emissions from a building, enclosed facility, or other structure; the permit holder shall comply with the following requirements:

(i) Title 30 TAC § 111.111(a)(7)(A) (relating to Requirements for Specified Sources)

(ii) Title 30 TAC § 111.111(a)(7)(B)(i) or (ii)

(iii) For a building containing an air emission source, enclosed facility, or other structure containing or associated with an air emission source subject to 30 TAC § 111.111(a)(7)(A), complying with 30 TAC § 111.111(a)(7)(B)(i) or (ii), and capable of producing visible emissions from, but not limited to, particulate matter, acid gases and NO_x, the permit holder shall also comply with the following periodic monitoring requirements for the purpose of annual compliance certification under 30 TAC § 122.146:

(1) An observation of visible emissions from a building containing an air emission source, enclosed facility, or other structure containing or associated with an air emission source which is required to comply with 30 TAC § 111.111(a)(7)(A) shall be conducted at least once during each calendar quarter unless the air emission source or enclosed facility is not operating for the entire quarter.

(2) Records of all observations shall be maintained.

(3) Visible emissions observations of air emission sources or enclosed facilities operated during daylight hours shall be conducted no earlier than one hour after sunrise and no later than one hour before sunset. Visible emissions observations of air emission sources or enclosed facilities operated only at night must be made with additional lighting and the temporary installation of contrasting backgrounds. Visible emissions shall be determined with each emissions outlet in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 mile, away from each emissions outlet during the observation. For outdoor locations, the observer shall select a position where the sun is not directly in the observer's eyes. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to

condensation of water vapor. A certified opacity reader is not required for visible emissions observations.

(4) Compliance Certification:

(a) If visible emissions are not present during the observation, the RO may certify that the source is in compliance with the applicable opacity requirement in 30 TAC § 111.111(a)(7) and (a)(7)(A)

(b) However, if visible emissions are present during the observation, the permit holder shall either list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(7)(B) as soon as practicable, but no later than 24 hours after observing visible emissions to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.

C. Certification of opacity readers determining opacities under Method 9 (as outlined in 40 CFR Part 60, Appendix A) to comply with opacity monitoring requirements shall be accomplished by completing the Visible Emissions Evaluators Course, or approved agency equivalent, no more than 180 days before the opacity reading.

D. Emission limits on nonagricultural processes, except for the steam generators specified in 30 TAC § 111.153, shall comply with the following requirements:

(i) Emissions of PM from any source may not exceed the allowable rates as required in 30 TAC § 111.151(a) (relating to Allowable Emissions Limits)

(ii) Sources with an effective stack height (h_e) less than the standard effective stack height (H_e), must reduce the allowable emission level by multiplying it by $[h_e/H_e]^2$ as required in 30 TAC § 111.151(b)

(iii) Effective stack height shall be calculated by the equation specified in 30 TAC § 111.151(c)

4. For storage vessels maintaining working pressure as specified in 30 TAC Chapter 115, Subchapter B, Division 1: "Storage of Volatile Organic Compounds," the permit holder shall comply with the requirements of 30 TAC § 115.112(a)(1).

5. Permit holder shall comply with the following 30 TAC Chapter 115, Subchapter C requirements:

A. When filling stationary gasoline storage vessels (Stage I) for motor vehicle fuel dispensing facilities specified in 30 TAC Chapter 115, Subchapter C, the permit holder shall comply with the following requirements:

(i) Title 30 TAC § 115.221 (relating to Emission Specifications)

(ii) Title 30 TAC § 115.222 (relating to Control Requirements)

(iii) Title 30 TAC § 115.223 (relating to Alternate Control Requirements)

(iv) Title 30 TAC § 115.224 (relating to Inspection Requirements)

(v) Title 30 TAC § 115.225 (relating to Testing Requirements)

(vi) Title 30 TAC § 115.226 (relating to Recordkeeping Requirements)

6. Permit holder shall comply with the following 30 TAC Chapter 115, Subchapter D requirements:

A. Title 30 TAC § 115.312(a)(1) (relating to Control Requirements), for emissions during Process Unit Shutdown or Turnaround

B. Title 30 TAC § 115.316(a)(2) (relating to Recordkeeping Requirements), for Process Unit Shutdown or Turnaround

7. The permit holder shall comply with the following requirements of 30 TAC Chapter 115, Subchapter F, Division 3, Degassing of Storage Tanks, Transport Vessels and Marine Vessels:

A. For degassing of stationary VOC storage tanks, the permit holder shall comply with the following requirements:

(i) Title 30 TAC § 115.541(a) - (c) (relating to Emission Specifications)

(ii) Title 30 TAC § 115.541(f) (relating to Emission Specifications), for floating roof storage tanks

(iii) Title 30 TAC § 115.542(a) and (a)(1), (a)(2), (a)(3) or (a)(4) (relating to Control Requirements). Where the requirements of 30 TAC Chapter 115, Subchapter F contain multiple compliance options, the permit holder shall keep records of when each compliance option was used.

(iv) Title 30 TAC § 115.542(b) - (d), (relating to Control Requirements)

(v) Title 30 TAC § 115.543 (relating to Alternate Control Requirements)

(vi) Title 30 TAC § 115.544(a)(1) and (a)(2) (relating to Inspection, Monitoring, and Testing Requirements), for inspections

(vii) Title 30 TAC § 115.544(b) (relating to Inspection, Monitoring, and Testing Requirements), for monitoring

(viii) Title 30 TAC § 115.544(b)(1) and (b)(2) (relating to Inspection, Monitoring, and Testing Requirements), for monitoring of control devices

(ix) Title 30 TAC § 115.544(b)(2)(A) - (J) (relating to Inspection, Monitoring, and Testing Requirements), for monitoring (as appropriate to the control device)

(x) Title 30 TAC § 115.544(b)(3), (b)(4) and (b)(6) (relating to Inspection, Monitoring, and Testing Requirements), for VOC concentration or lower explosive limit threshold monitoring

(xi) Title 30 TAC § 115.544(c), and (c)(1) - (c)(3) (relating to Inspection, Monitoring, and Testing Requirements), for testing of control devices used to comply with 30 TAC § 115.542(a)(1)

(xii) Title 30 TAC § 115.545(1) - (7), (9) - (11) and (13) (relating to Approved Test Methods)

(xiii) Title 30 TAC § 115.546(a), (a)(1) and (a)(3) (relating to Recordkeeping and Notification Requirements), for recordkeeping

(xiv) Title 30 TAC § 115.546(a)(2) and (a)(2)(A) - (J) (relating to Recordkeeping and Notification Requirements), for recordkeeping (as appropriate to the control device)

(xv) Title 30 TAC § 115.546(a)(4) (relating to Recordkeeping and Notification Requirements), for recordkeeping of testing of control devices used to comply with 30 TAC § 115.542(a)(1)

(xvi) Title 30 TAC § 115.547(4) (relating to Exemptions)

B. For the degassing of all transport vessels with a nominal capacity of 8,000 gallons or more, the permit holder shall comply with the following requirements:

(i) Title 30 TAC § 115.541(a) - (c) and (d) (relating to Emission Specifications)

(ii) Title 30 TAC § 115.542(a) and (a)(1), (a)(2), (a)(3) or (a)(4) (relating to Control Requirements). Where the requirements of 30 TAC Chapter 115, Subchapter F contain multiple compliance options, the permit holder shall keep records of when each compliance option was used.

(iii) Title 30 TAC § 115.542(b), (c) and (e) (relating to Control Requirements)

(iv) Title 30 TAC § 115.543 (relating to Alternate Control Requirements)

(v) Title 30 TAC § 115.544(a)(1) and (a)(2) (relating to Inspection, Monitoring, and Testing Requirements), for inspections

(vi) Title 30 TAC § 115.544(b) (relating to Inspection, Monitoring, and Testing Requirements), for monitoring

(vii) Title 30 TAC § 115.544(b)(1) and (b)(2) (relating to Inspection, Monitoring, and Testing Requirements), for monitoring of control devices

(viii) Title 30 TAC § 115.544(b)(2)(A) - (J) (relating to Inspection, Monitoring, and Testing Requirements), for monitoring (as appropriate to the control device)

(ix) Title 30 TAC § 115.544(b)(3), (b)(4) and (b)(6) (relating to Inspection, Monitoring, and Testing Requirements), for VOC concentration or lower explosive limit threshold monitoring

(x) Title 30 TAC § 115.544(c), and (c)(1) - (c)(3) (relating to Inspection, Monitoring, and Testing Requirements), for testing of control devices used to comply with 30 TAC § 115.542(a)(1)

(xi) Title 30 TAC § 115.545(1) - (11) and (13) (relating to Approved Test Methods)

(xii) Title 30 TAC § 115.546(a), (a)(1) and (a)(3) (relating to Recordkeeping and Notification Requirements), for recordkeeping

(xiii) Title 30 TAC § 115.546(a)(2) and (a)(2)(A) - (J) (relating to Recordkeeping and Notification Requirements), for recordkeeping (as appropriate to the control device)

(xiv) Title 30 TAC § 115.546(a)(4) (relating to Recordkeeping and Notification Requirements), for recordkeeping of testing of control devices used to comply with 30 TAC § 115.542(a)(1)

8. The permit holder shall comply with the following requirements for units subject to any subpart of 40 CFR Part 60, unless otherwise stated in the applicable subpart:

A. Title 40 CFR § 60.7 (relating to Notification and Recordkeeping)

B. Title 40 CFR § 60.8 (relating to Performance Tests)

C. Title 40 CFR § 60.11 (relating to Compliance with Standards and Maintenance Requirements)

D. Title 40 CFR § 60.12 (relating to Circumvention)

E. Title 40 CFR § 60.13 (relating to Monitoring Requirements)

F. Title 40 CFR § 60.14 (relating to Modification)

G. Title 40 CFR § 60.15 (relating to Reconstruction)

H. Title 40 CFR § 60.19 (relating to General Notification and Reporting Requirements)

9. For petroleum refinery facilities subject to 40 CFR Part 60, Subpart QQQ, the permit holder shall comply with the following requirements:

A. Title 40 CFR § 60.692-1(a) - (c) (relating to Standards: General)

B. Title 40 CFR § 60.692-2(a) - (c), (e) (relating to Standards: Individual Drain Systems)

C. Title 40 CFR § 60.692-6(a) - (b) (relating to Standards: Delay of Repair)

D. Title 40 CFR § 60.692-7(a) - (b) (relating to Standards: Delay of Compliance)

E. Title 40 CFR § 60.693-1(a) - (d), (e)(1) - (3) (relating to Alternative Standards for Individual Drain Systems)

F. Title 40 CFR § 60.697(a), (b)(1) - (3) (relating to Recordkeeping Requirements), as applicable to Individual Drain Systems

G. Title 40 CFR § 60.697(f)(1) - (2), (g) (relating to Recordkeeping Requirements), as applicable to Individual Drain Systems

H. Title 40 CFR § 60.697(h) (relating to Recordkeeping Requirements), as applicable to excluded Stormwater Sewer Systems

I. Title 40 CFR § 60.697(i) (relating to Recordkeeping Requirements), as applicable to excluded Ancillary Equipment

J. Title 40 CFR § 60.698(a), and (b)(1) (relating to Reporting Requirements), as applicable to Individual Drain Systems

K. Title 40 CFR § 60.698(c) (relating to Reporting Requirements), for water seal breaches in Drain Systems

L. Title 40 CFR § 60.698(e) (relating to Reporting Requirements), as applicable to Individual Drain Systems

10. The permit holder shall comply with the following requirements for units subject to any subpart of 40 CFR Part 61, unless otherwise stated in the applicable subpart:

A. Title 40 CFR § 61.05 (relating to Prohibited Activities)

B. Title 40 CFR § 61.07 (relating to Application for Approval of Construction or Modification)

C. Title 40 CFR § 61.09 (relating to Notification of Start-up)

D. Title 40 CFR § 61.10 (relating to Source Reporting and Request Waiver)

E. Title 40 CFR § 61.12 (relating to Compliance with Standards and Maintenance Requirements)

F. Title 40 CFR § 61.13 (relating to Emissions Tests and Waiver of Emission Tests)

G. Title 40 CFR § 61.14 (relating to Monitoring Requirements)

H. Title 40 CFR § 61.15 (relating to Modification)

I. Title 40 CFR § 61.19 (relating to Circumvention)

11. For facilities where total annual benzene quantity from waste is greater than or equal to 10 megagrams per year and subject to emission standards in 40 CFR Part 61, Subpart FF, the permit holder shall comply with the following requirements:

A. Title 40 CFR § 61.342(c)(1)(i) - (iii) (relating to Standards: General)

B. Title 40 CFR § 61.342(e)(1) (relating to Standards: General)

C. Title 40 CFR § 61.342(e)(2)(i) - (ii) (relating to Standards: General)

D. Title 40 CFR § 61.342(g) (relating to Standards: General)

E. Title 40 CFR § 61.350(a) and (b) (relating to Standards: Delay of Repair)

F. Title 40 CFR § 61.355(a)(1)(iii), (a)(2), (a)(6), (b), and (c)(1) - (3) (relating to Test Methods, Procedures, and Compliance Provisions)

G. Title 40 CFR § 61.355(k)(1) - (6), and (7)(i) - (iv) (relating to Test Methods, Procedures, and Compliance Provisions), for calculation procedures

H. Title 40 CFR § 61.356(a) (relating to Recordkeeping Requirements)

I. Title 40 CFR § 61.356(b), and (b)(1) (relating to Recordkeeping Requirements)

J. Title 40 CFR § 61.356(b)(4) (relating to Recordkeeping Requirements)

K. Title 40 CFR § 61.356(b)(5) (relating to Recordkeeping Requirements)

L. Title 40 CFR § 61.357(a), (d)(1), (d)(2) (d)(6) and (d)(8) (relating to Reporting Requirements)

M. Title 40 CFR § 61.357(d)(5) (relating to Reporting Requirements)

N. Waste generated by remediation activities at these facilities are subject to the requirements identified under 40 CFR § 61.342 for treatment and management of waste

12. For facilities with containers subject to emission standards in 40 CFR Part 61, Subpart FF, the permit holder shall comply with the following requirements:

A. Title 40 CFR § 61.345(a)(1) - (3), (b), and (c) (relating to Standards: Containers)

B. Title 40 CFR § 61.355(h) (relating to Test Methods, Procedures and Compliance Provisions)

C. Title 40 CFR § 61.356(g) (relating to Recordkeeping Requirements)

D. Title 40 CFR § 61.356(h) (relating to Recordkeeping Requirements)

13. The permit holder shall comply with the requirements of 30 TAC Chapter 113, Subchapter C, § 113.100 for units subject to any subpart of 40 CFR Part 63, unless otherwise stated in the applicable subpart.

14. For the operations pertaining to the loading and unloading of marine tank vessels specified in 40 CFR Part 63, Subpart Y, the permit holder shall comply with the following requirements (Title 30 TAC Chapter 113, Subchapter C, § 113.300 incorporated by reference):

A. Title 40 CFR § 63.560(c) (relating to Designation of Affected Source), for applicability of the General Provisions of Subpart A

B. Title 40 CFR § 63.563(a)(4) (relating to Compliance and Performance Testing), for vapor tightness requirements of the marine vessels

C. Title 40 CFR § 63.564(a)(1) and (d) (relating to Monitoring Requirements)

D. Title 40 CFR § 63.565(a) (relating to Test Methods and Procedures), for performance testing requirements

E. Title 40 CFR § 63.565(c) (relating to Test Methods and Procedures), for vapor tightness requirements of the marine vessels

F. Title 40 CFR § 63.566 (relating to Construction and Reconstruction)

G. Title 40 CFR § 63.567(a) - (b) and (h) - (i) (relating to Reporting and Recordkeeping Requirements)

15. For sources subject to emission standards in 40 CFR Part 63, Subpart CC, the permit holder shall comply with the following requirements (Title 30 TAC Chapter 113, Subchapter C, § 113.340 incorporated by reference):

    A. Title 40 CFR § 63.640(l)(3) - (4) (relating to Applicability and Designation of Affected Source), for units and equipment added to an existing source

    B. Title 40 CFR § 63.640(m)(1) - (2) (relating to Applicability and Designation of Affected Source), for units and emission points changing from Group 2 to Group 1 status

    C. Title 40 CFR § 63.642(c) (relating to General Standards), for applicability of the General Provisions of Subpart A

    D. Title 40 CFR § 63.642(e) (relating to General Standards), for recordkeeping

    E. Title 40 CFR § 63.642(f) (relating to General Standards), for reporting

    F. Process wastewater streams managed in a wastewater management unit subject to 40 CFR Part 63, Subpart G shall comply with 40 CFR Part 63, Subpart G and 40 CFR Part 61, Subpart FF as specified in 40 CFR § 63.640(o)(2)(i)

16. The permit holder shall comply with the requirement to prepare and implement an Operations and Maintenance plan in accordance with 40 CFR Part 63, Subpart UUU, § 63.1574(f) (Title 30 TAC Chapter 113, Subchapter C, § 113.780 incorporated by reference).

17. For site remediation projects subject to 40 CFR Part 63, Subpart GGGGG that will remove remediation material containing less than 1 megagram per year of the HAP listed in Table 1 to Subpart GGGGG, the permit holder shall comply with 40 CFR § 63.7881(c)(1) - (3) (Title 30 TAC Chapter 113, Subchapter C, § 113.1160 incorporated by reference).

18. The permit holder shall comply with certified registrations submitted to the TCEQ for purposes of establishing federally enforceable emission limits. A copy of the certified registration shall be maintained with the permit. Records sufficient to demonstrate compliance with the established limits shall be maintained. The certified registration and records demonstrating compliance shall be provided, on request, to representatives of the appropriate TCEQ regional office and any local air pollution control agency having jurisdiction over the site. The permit holder shall submit updated certified registrations when changes at the site require establishment of new emission limits. If changes result in emissions that do not remain below major source thresholds, the permit holder shall submit a revision application to codify the appropriate requirements in the permit.

Additional Monitoring Requirements

19. Unless otherwise specified, the permit holder shall comply with the compliance assurance monitoring requirements as specified in the attached “CAM Summary” upon issuance of the permit. In addition, the permit holder shall comply with the following:

    A. The permit holder shall comply with the terms and conditions contained in 30 TAC § 122.147 (General Terms and Conditions for Compliance Assurance Monitoring).

    B. The permit holder shall report, consistent with the averaging time identified in the “CAM Summary,” deviations as defined by the deviation limit in the “CAM Summary.” Any monitoring data below a minimum limit or above a maximum limit, that is collected in accordance with the requirements specified in 40 CFR § 64.7(c), shall be reported as a

deviation. Deviations shall be reported according to 30 TAC § 122.145 (Reporting Terms and Conditions).

C. The permit holder may elect to collect monitoring data on a more frequent basis and average the data, consistent with the averaging time or minimum frequency specified in the "CAM Summary," for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis. In no event shall data be collected and used in particular instances in order to avoid reporting deviations. All monitoring data shall be collected in accordance with the requirements specified in 40 CFR § 64.7(c).

D. The permit holder shall operate the monitoring, identified in the attached "CAM Summary," in accordance with the provisions of 40 CFR § 64.7. The permit holder shall calibrate and maintain monitoring devices and instrumentation in accordance with manufacturer's specifications or other written procedures as identified in the "CAM Summary." These specific QA/QC procedures shall be maintained with the site's operation and maintenance (O&M) plan.

E. Except for emission units using a CEMS, COMS or PEMS which meets the requirements of 40 CFR § 64.3(d)(2), the permit holder shall conduct a once a month visual, audible, and/or olfactory inspection of the capture system to detect leaking components for any capture system associated with the control device subject to CAM. If the results of the following inspections indicate that the capture system is not working properly, the permit holder shall promptly take necessary corrective actions.

F. Except for emission units using a CEMS, COMS or PEMS which meets the requirements of 40 CFR § 64.3(d)(2), the permit holder shall comply with either of the following requirements for any bypass of the control device subject to CAM. If the results of the following inspections or monitoring indicate bypass of the control device, the permit holder shall promptly take necessary corrective actions and report a deviation:

(i) Install a flow indicator that is capable of recording flow, at least once every fifteen minutes, immediately downstream of each valve that if opened would allow a vent stream to bypass the control device and be emitted, either directly or indirectly, to the atmosphere; or

(ii) Once a month, the permit holder shall inspect the valves checking the position of the valves and the condition of the car seals. Identify all times when the car seal has been broken and the valve position has been changed to allow a vent stream to bypass the control device and be emitted, either directly or indirectly, to the atmosphere.

G. The permit holder shall comply with the requirements of 40 CFR § 70.6(a)(3)(ii)(A) and 30 TAC § 122.144(1)(A)-(F) for documentation of all required inspections.

20. The permit holder shall comply with the periodic monitoring requirements as specified in the attached "Periodic Monitoring Summary" upon issuance of the permit. The permit holder shall calibrate and maintain monitoring devices and instrumentation in accordance with manufacturer's specifications or other written procedures as identified in the "Periodic Monitoring Summary." These specific QA/QC procedures shall be maintained with the site's operation and maintenance (O&M) plan. Except for, as applicable, monitoring malfunctions, associated repairs, and required quality assurance or control activities (including, as applicable, calibration checks and required zero and span adjustments), the permit holder shall conduct all monitoring in continuous operation (or shall collect data at all required intervals) at all times that the pollutant-specific emissions unit is operating. The permit holder may elect to collect monitoring data on a more frequent basis and average the data, consistent with the averaging time or minimum frequency

specified in the "Periodic Monitoring Summary," for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis. In no event shall data be collected and used in particular instances to avoid reporting deviations. Deviations shall be reported according to 30 TAC § 122.145 (Reporting Terms and Conditions).

New Source Review Authorization Requirements

21. Permit holder shall comply with the requirements of New Source Review authorizations issued or claimed by the permit holder for the permitted area, including permits, permits by rule, standard permits, flexible permits, special permits, permits for existing facilities including Voluntary Emissions Reduction Permits and Electric Generating Facility Permits issued under 30 TAC Chapter 116, Subchapter I, or special exemptions referenced in the New Source Review Authorization References attachment. These requirements:

    A. Are incorporated by reference into this permit as applicable requirements

    B. Shall be located with this operating permit

    C. Are not eligible for a permit shield

22. The permit holder shall comply with the general requirements of 30 TAC Chapter 106, Subchapter A or the general requirements, if any, in effect at the time of the claim of any PBR.

23. The permit holder shall maintain records to demonstrate compliance with any emission limitation or standard that is specified in a permit by rule (PBR) or Standard Permit listed in the New Source Review Authorizations attachment. The records shall yield reliable data from the relevant time period that are representative of the emission unit's compliance with the PBR or Standard Permit. These records may include, but are not limited to, production capacity and throughput, hours of operation, safety data sheets (SDS), chemical composition of raw materials, speciation of air contaminant data, engineering calculations, maintenance records, fugitive data, performance tests, capture/control device efficiencies, direct pollutant monitoring (CEMS, COMS, or PEMS), or control device parametric monitoring. These records shall be made readily accessible and available as required by 30 TAC § 122.144. Any monitoring or recordkeeping data indicating noncompliance with the PBR or Standard Permit shall be considered and reported as a deviation according to 30 TAC § 122.145 (Reporting Terms and Conditions).

24. The permit holder shall comply with the following requirements for Air Quality Standard Permits:

    A. Registration requirements listed in 30 TAC § 116.611, unless otherwise provided for in an Air Quality Standard Permit

    B. General Conditions listed in 30 TAC § 116.615, unless otherwise provided for in an Air Quality Standard Permit

    C. Applicable requirements of 30 TAC § 116.617 for Pollution Control Projects based on the information contained in the registration application.

    D. Requirements of the non-rule Air Quality Standard Permit for Pollution Control Projects

25. For marine vapor combustors, the permit holder shall comply with the following requirements:

    A. The vapor combustor shall achieve 98% control efficiency of the waste gas directed to it. This shall be ensured by maintaining the temperature in or immediately downstream of, the combustion chamber above preconstruction estimate prior to the initial stack test. Following the completion of that stack test, the six minute average temperature shall be

maintained above the minimum one hour average temperature maintained during the last satisfactory stack test.

B. The temperature measurement device shall reduce the temperature readings to an averaging period of six minutes or less and record it at that frequency. The temperature monitor shall be installed, calibrated at least annually, and maintained according to the manufacturer's specifications. The device shall have an accuracy of the greater of ±2 percent of the temperature being measured expressed in degrees Celsius or ±2.5ºC.

C. Quality assured (or valid) data must be generated when the VCU is operating except during the performance of a daily zero and span check. Loss of valid data due to periods of monitor break down, out-of-control operation (producing inaccurate data), repair, maintenance, or calibration may be exempted provided it does not exceed 5 percent of the time (in minutes) that the VCU operated over the previous rolling 12 month period. The measurements missed shall be estimated using engineering judgment and the methods used recorded.

D. The vapor combustor shall be operated with no visible emissions and have a constant pilot flame during all times waste gas could be directed to it. The pilot flame shall be continuously monitored by a thermocouple or an infrared monitor. The time, date, and duration of any loss of pilot flame shall be recorded. Each monitoring device shall be accurate to, and shall be calibrated at a frequency in accordance with, the manufacturer's specifications.

26. For leak detection and repair relating to fugitive emission units in VOC Service, the permit holder shall comply with the requirements of Title 40 CFR § 60.482-9 (relating to Standards: Delay of Repair) as incorporated under 40 CFR Part 63, Subpart CC. A leaking component shall be repaired as soon as practicable, but no later than 15 days after the leak is detected, except as specified in 40 CFR § 60.482-9. This requirement supersedes any less stringent requirement that may be specified in a condition of a permit identified in the New Source Review Authorization attachment.

Compliance Requirements

27. The permit holder shall certify compliance in accordance with 30 TAC § 122.146. The permit holder shall comply with 30 TAC § 122.146 using at a minimum, but not limited to, the continuous or intermittent compliance method data from monitoring, recordkeeping, reporting, or testing required by the permit and any other credible evidence or information. The certification period may not exceed 12 months and the certification must be submitted within 30 days after the end of the period being certified.

28. Permit holder shall comply with the following 30 TAC Chapter 117 requirements:

A. The permit holder shall comply with the compliance schedules and submit written notification to the TCEQ Executive Director as required in 30 TAC Chapter 117, Subchapter H, Division 1:

(i) For sources in the Beaumont-Port Arthur Nonattainment area, 30 TAC § 117.9000

B. The permit holder shall comply with the Initial Control Plan unit listing requirement in 30 TAC § 117.150(c) and (c)(1).

29. Use of Emission Credits to comply with applicable requirements:

A. Unless otherwise prohibited, the permit holder may use emission credits to comply with the following applicable requirements listed elsewhere in this permit:

(i) Title 30 TAC Chapter 115

(ii) Title 30 TAC Chapter 117

(iii) Offsets for Title 30 TAC Chapter 116

B. The permit holder shall comply with the following requirements in order to use the emission credits to comply with the applicable requirements:

(i) The permit holder must notify the TCEQ according to 30 TAC § 101.306(c)-(d)

(ii) The emission credits to be used must meet all the geographic, timeliness, applicable pollutant type, and availability requirements listed in 30 TAC Chapter 101, Subchapter H, Division 1

(iii) The executive director has approved the use of the credit according to 30 TAC § 101.306(c)-(d)

(iv) The permit holder keeps records of the use of credits towards compliance with the applicable requirements in accordance with 30 TAC § 101.302(g) and 30 TAC Chapter 122

(v) Title 30 TAC § 101.305 (relating to Emission Reductions Achieved Outside the United States)

30. Use of Discrete Emission Credits to comply with the applicable requirements:

A. Unless otherwise prohibited, the permit holder may use discrete emission credits to comply with the following applicable requirements listed elsewhere in this permit:

(i) Title 30 TAC Chapter 115

(ii) Title 30 TAC Chapter 117

(iii) If applicable, offsets for Title 30 TAC Chapter 116

(iv) Temporarily exceed state NSR permit allowables

B. The permit holder shall comply with the following requirements in order to use the credit to comply with the applicable requirements:

(i) The permit holder must notify the TCEQ according to 30 TAC § 101.376(d)

(ii) The discrete emission credits to be used must meet all the geographic, timeliness, applicable pollutant type, and availability requirements listed in 30 TAC Chapter 101, Subchapter H, Division 4

(iii) The executive director has approved the use of the discrete emission credits according to 30 TAC § 101.376(d)(1)(A)

(iv) The permit holder keeps records of the use of credits towards compliance with the applicable requirements in accordance with 30 TAC § 101.372(h) and 30 TAC Chapter 122

(v) Title 30 TAC § 101.375 (relating to Emission Reductions Achieved Outside the United States)

Risk Management Plan

31. For processes subject to 40 CFR Part 68 and specified in 40 CFR § 68.10, the permit holder shall comply with the requirements of the Accidental Release Prevention Provisions in 40 CFR Part 68. The permit holder shall submit to the appropriate agency either a compliance schedule for meeting the requirements of 40 CFR Part 68 by the date provided in 40 CFR § 68.10(a), or as part of the compliance certification submitted under this permit, a certification statement that the source is in compliance with all requirements of 40 CFR Part 68, including the registration and submission of a risk management plan.

Protection of Stratospheric Ozone

32. Permit holders at a site subject to Title VI of the FCAA Amendments shall meet the following requirements for protection of stratospheric ozone:

    A. Any on site servicing, maintenance, and repair on refrigeration and nonmotor vehicle air-conditioning appliances using ozone-depleting refrigerants or non-exempt substitutes shall be conducted in accordance with 40 CFR Part 82, Subpart F. Permit holders shall ensure that repairs on or refrigerant removal from refrigeration and nonmotor vehicle air-conditioning appliances using ozone-depleting refrigerants are performed only by properly certified technicians using certified equipment. Records shall be maintained as required by 40 CFR Part 82, Subpart F.

Alternative Requirements

33. The permit holder shall comply with the approved alternative means of control (AMOC); alternative monitoring, recordkeeping, or reporting requirements; or requirements determined to be equivalent to an otherwise applicable requirement contained in the Alternative Requirements attachment of this permit. Units complying with an approved alternative requirement have reference to the approval in the Applicable Requirements summary listing for the unit. The permit holder shall maintain the original documentation, from the EPA Administrator, demonstrating the method or limitation utilized. Documentation shall be maintained and made available in accordance with 30 TAC § 122.144.

Permit Location

34. The permit holder shall maintain a copy of this permit and records related to requirements listed in this permit on site.

Permit Shield (30 TAC § 122.148)

35. A permit shield is granted for the emission units, groups, or processes specified in the attached “Permit Shield.” Compliance with the conditions of the permit shall be deemed compliance with the specified potentially applicable requirements or specified potentially applicable state-only requirements listed in the attachment “Permit Shield.” Permit shield provisions shall not be modified by the executive director until notification is provided to the permit holder. No later than 90 days after notification of a change in a determination made by the executive director, the permit holder shall apply for the appropriate permit revision to reflect the new determination.

Provisional terms are not eligible for this permit shield. Any term or condition, under a permit shield, shall not be protected by the permit shield if it is replaced by a provisional term or condition or the basis of the term and condition changes.

Attachments

Applicable Requirements Summary

Additional Monitoring Requirements

Permit Shield

New Source Review Authorization References

Alternative Requirement

Applicable Requirements Summary

Unit Summary **20**

Applicable Requirements Summary **60**

Note: A “none” entry may be noted for some emission sources in this permit’s “Applicable Requirements Summary” under the heading of “Monitoring and Testing Requirements” and/or “Recordkeeping Requirements” and/or “Reporting Requirements.” Such a notation indicates that there are no requirements for the indicated emission source as identified under the respective column heading(s) for the stated portion of the regulation when the emission source is operating under the conditions of the specified SOP Index Number. However, other relevant requirements pursuant to 30 TAC Chapter 122 including Recordkeeping Terms and Conditions (30 TAC § 122.144), Reporting Terms and Conditions (30 TAC § 122.145), and Compliance Certification Terms and Conditions (30 TAC § 122.146) continue to apply.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
1334-RVENT	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	63UUU-2000	40 CFR Part 63, Subpart UUU	No changing attributes.
16BHSW	SRIC ENGINES	N/A	60IIII-004	40 CFR Part 60, Subpart IIII	No changing attributes.
16BHSW	SRIC ENGINES	N/A	63ZZZZ-007	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
ADMNGEN	SRIC ENGINES	N/A	63ZZZZ-008	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
AVU-146H1	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0023	40 CFR Part 60, Subpart J	No changing attributes.
AVU-146H1	PROCESS HEATERS/FURNACES	N/A	63DDDDD-001	40 CFR Part 63, Subpart DDDDD	No changing attributes.
AVU-146H2AB	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60Ja-01	40 CFR Part 60, Subpart Ja	No changing attributes.
AVU-146H2AB	PROCESS HEATERS/FURNACES	N/A	63DDDDD-001	40 CFR Part 63, Subpart DDDDD	No changing attributes.
BERTH-1A	LOADING/UNLOADING OPERATIONS	N/A	63CC-2502	40 CFR Part 63, Subpart CC	No changing attributes.
BERTH-1A	LOADING/UNLOADING OPERATIONS	N/A	63Y-0041	40 CFR Part 63, Subpart Y	No changing attributes.
BERTH-1B	LOADING/UNLOADING OPERATIONS	N/A	63CC-2502	40 CFR Part 63, Subpart CC	No changing attributes.
BERTH-2A	LOADING/UNLOADING OPERATIONS	N/A	63CC-2502	40 CFR Part 63, Subpart CC	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
BERTH-2A	LOADING/UNLOADING OPERATIONS	N/A	63Y-0041	40 CFR Part 63, Subpart Y	No changing attributes.
BERTH-2B	LOADING/UNLOADING OPERATIONS	N/A	63CC-2502	40 CFR Part 63, Subpart CC	No changing attributes.
BERTH-3A	LOADING/UNLOADING OPERATIONS	N/A	63CC-2502	40 CFR Part 63, Subpart CC	No changing attributes.
BERTH-3A	LOADING/UNLOADING OPERATIONS	N/A	63Y-0041	40 CFR Part 63, Subpart Y	No changing attributes.
BERTH-3B	LOADING/UNLOADING OPERATIONS	N/A	63CC-2502	40 CFR Part 63, Subpart CC	No changing attributes.
BERTH-5	LOADING/UNLOADING OPERATIONS	N/A	63CC-2502	40 CFR Part 63, Subpart CC	No changing attributes.
BERTH-6	LOADING/UNLOADING OPERATIONS	N/A	63CC-2502	40 CFR Part 63, Subpart CC	No changing attributes.
BH15-41	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	R7117-001	30 TAC Chapter 117, Subchapter B	No changing attributes.
BH15-41	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	63DDDDD-001	40 CFR Part 63, Subpart DDDDD	No changing attributes.
BH15-42	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	R7117-001	30 TAC Chapter 117, Subchapter B	No changing attributes.
BH15-42	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	63DDDDD-001	40 CFR Part 63, Subpart DDDDD	No changing attributes.
BH15-43	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	R7117-001	30 TAC Chapter 117, Subchapter B	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
BH15-43	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	63DDDDD-001	40 CFR Part 63, Subpart DDDDD	No changing attributes.
CARBON-1	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	60QQQ-001	40 CFR Part 60, Subpart QQQ	No changing attributes.
CARBON-1	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	61FF-001	40 CFR Part 61, Subpart FF	No changing attributes.
CARBON-2	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	60QQQ-001	40 CFR Part 60, Subpart QQQ	No changing attributes.
CARBON-2	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	61FF-001	40 CFR Part 61, Subpart FF	No changing attributes.
CRU-1344H1	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0023	40 CFR Part 60, Subpart J	No changing attributes.
CRU-1344H1	PROCESS HEATERS/FURNACES	N/A	63DDDDD-001	40 CFR Part 63, Subpart DDDDD	No changing attributes.
CRU-1344H2	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0023	40 CFR Part 60, Subpart J	No changing attributes.
CRU-1344H2	PROCESS HEATERS/FURNACES	N/A	63DDDDD-001	40 CFR Part 63, Subpart DDDDD	No changing attributes.
CRU-1344H3	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0023	40 CFR Part 60, Subpart J	No changing attributes.
CRU-1344H3	PROCESS HEATERS/FURNACES	N/A	63DDDDD-001	40 CFR Part 63, Subpart DDDDD	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
CSV843	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5131-1	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
DCU-843H1	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0024	40 CFR Part 60, Subpart J	No changing attributes.
DCU-843H2	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0024	40 CFR Part 60, Subpart J	No changing attributes.
DCU-843H3	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0024	40 CFR Part 60, Subpart J	No changing attributes.
E-01-147	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0023	40 CFR Part 60, Subpart J	No changing attributes.
E-01-147	PROCESS HEATERS/FURNACES	N/A	63DDDDD-001	40 CFR Part 63, Subpart DDDDD	No changing attributes.
E-01-245	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0023	40 CFR Part 60, Subpart J	No changing attributes.
E-01-245	PROCESS HEATERS/FURNACES	N/A	63DDDDD-001	40 CFR Part 63, Subpart DDDDD	No changing attributes.
E-01-246	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0023	40 CFR Part 60, Subpart J	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
E-01-246	PROCESS HEATERS/FURNACES	N/A	63DDDDD-001	40 CFR Part 63, Subpart DDDDD	No changing attributes.
E-02-147	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0023	40 CFR Part 60, Subpart J	No changing attributes.
E-02-147	PROCESS HEATERS/FURNACES	N/A	63DDDDD-001	40 CFR Part 63, Subpart DDDDD	No changing attributes.
E-03-SCOT	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0024	40 CFR Part 60, Subpart J	No changing attributes.
E-04-SCOT	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0023	40 CFR Part 60, Subpart J	No changing attributes.
ENG-15PS	SRIC ENGINES	N/A	63ZZZZ-003	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
ENG-443 NORTH	SRIC ENGINES	N/A	60IIII-002	40 CFR Part 60, Subpart IIII	No changing attributes.
ENG-443 NORTH	SRIC ENGINES	N/A	63ZZZZ-006	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
ENG-443 SOUTH	SRIC ENGINES	N/A	60IIII-002	40 CFR Part 60, Subpart IIII	No changing attributes.
ENG-443 SOUTH	SRIC ENGINES	N/A	63ZZZZ-006	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
ENG-70AC2	SRIC ENGINES	N/A	63ZZZZ-004	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
ENG-70AC3	SRIC ENGINES	N/A	63ZZZZ-004	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
ENG-843NORTH	SRIC ENGINES	N/A	60IIII-004	40 CFR Part 60, Subpart IIII	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
ENG-843NORTH	SRIC ENGINES	N/A	63ZZZZ-007	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
ENG-843SOUTH	SRIC ENGINES	N/A	60IIII-006	40 CFR Part 60, Subpart IIII	No changing attributes.
ENG-843SOUTH	SRIC ENGINES	N/A	63ZZZZ-007	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
F-1747	FUGITIVE EMISSION UNITS	N/A	60GGGa-ALL	40 CFR Part 60, Subpart GGGa	No changing attributes.
F-432CT	INDUSTRIAL PROCESS COOLING TOWERS	N/A	63CC-3000	40 CFR Part 63, Subpart CC	No changing attributes.
F-446CT	INDUSTRIAL PROCESS COOLING TOWERS	N/A	63CC-3000	40 CFR Part 63, Subpart CC	No changing attributes.
F-544	FUGITIVE EMISSION UNITS	N/A	R5352-ALL	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	No changing attributes.
F-546	FUGITIVE EMISSION UNITS	N/A	R5352-ALL	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	No changing attributes.
F-7042	FUGITIVE EMISSION UNITS	N/A	60GGGa-ALL	40 CFR Part 60, Subpart GGGa	No changing attributes.
F-7043	FUGITIVE EMISSION UNITS	N/A	60GGGa-ALL	40 CFR Part 60, Subpart GGGa	No changing attributes.
F-7044	FUGITIVE EMISSION UNITS	N/A	60GGGa-ALL	40 CFR Part 60, Subpart GGGa	No changing attributes.
F-7843	FUGITIVE EMISSION UNITS	N/A	63CCH-ALL	40 CFR Part 63, Subpart CC	No changing attributes.
F-7945	FUGITIVE EMISSION UNITS	N/A	63CCH-ALL	40 CFR Part 63, Subpart CC	No changing attributes.
F-8748-SWS	FUGITIVE EMISSION UNITS	N/A	63CCH-ALL	40 CFR Part 63, Subpart CC	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
F-943	FUGITIVE EMISSION UNITS	N/A	63CCH-ALL	40 CFR Part 63, Subpart CC	No changing attributes.
FCC-1241H1	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	R117-005	30 TAC Chapter 117, Subchapter B	No changing attributes.
FCC-1241H2	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	R117-005	30 TAC Chapter 117, Subchapter B	No changing attributes.
FCCU-1241	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0011	40 CFR Part 60, Subpart J	No changing attributes.
FCCU-1241	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	63UUU-1000	40 CFR Part 63, Subpart UUU	No changing attributes.
F-DOCKS	FUGITIVE EMISSION UNITS	N/A	R5352-ALL	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	No changing attributes.
F-DOCKS	FUGITIVE EMISSION UNITS	N/A	61J-001	40 CFR Part 61, Subpart J	No changing attributes.
F-DOCKS	FUGITIVE EMISSION UNITS	N/A	63CCVV-ALL	40 CFR Part 63, Subpart CC	No changing attributes.
FF-1241-1	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	60QQQ-001	40 CFR Part 60, Subpart QQQ	No changing attributes.
FF-1241-1	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	61FF-0001	40 CFR Part 61, Subpart FF	No changing attributes.
FF-1241-2	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	61FF-0001	40 CFR Part 61, Subpart FF	No changing attributes.
FF-1242	CLOSED VENT SYSTEM	N/A	61FF-0001	40 CFR Part 61, Subpart FF	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	AND CONTROL DEVICE				
FF-1344	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	61FF-0001	40 CFR Part 61, Subpart FF	No changing attributes.
FF-146	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	61FF-0001	40 CFR Part 61, Subpart FF	No changing attributes.
FF-147	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	61FF-0001	40 CFR Part 61, Subpart FF	No changing attributes.
FF-241	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	61FF-0001	40 CFR Part 61, Subpart FF	No changing attributes.
FF-244	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	61FF-0001	40 CFR Part 61, Subpart FF	No changing attributes.
FF-246	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	61FF-0001	40 CFR Part 61, Subpart FF	No changing attributes.
FF-443-1	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	61FF-0001	40 CFR Part 61, Subpart FF	No changing attributes.
FF-443-2	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	61FF-0001	40 CFR Part 61, Subpart FF	No changing attributes.
FF-84PH	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	61FF-0001	40 CFR Part 61, Subpart FF	No changing attributes.
FF-CCS	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	61FF-0001	40 CFR Part 61, Subpart FF	No changing attributes.
FF-D-108	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	60QQQ-001	40 CFR Part 60, Subpart QQQ	No changing attributes.
FF-D-108	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	61FF-001	40 CFR Part 61, Subpart FF	No changing attributes.
FF-D-108	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	63G-008	40 CFR Part 63, Subpart G	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
FF-DOCKS-1	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	61FF-0001	40 CFR Part 61, Subpart FF	No changing attributes.
FF-DOCKS-2	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	61FF-0001	40 CFR Part 61, Subpart FF	No changing attributes.
FF-DOCKS-3	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	61FF-0001	40 CFR Part 61, Subpart FF	No changing attributes.
FF-DOCKS-4	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	61FF-0001	40 CFR Part 61, Subpart FF	No changing attributes.
FF-DOCKS-5	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	61FF-0001	40 CFR Part 61, Subpart FF	No changing attributes.
FF-DOCKS-6	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	61FF-0001	40 CFR Part 61, Subpart FF	No changing attributes.
FF-GHU-245	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	61FF-0001	40 CFR Part 61, Subpart FF	No changing attributes.
FF-KELAB	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	61FF-0001	40 CFR Part 61, Subpart FF	No changing attributes.
FF-LAB	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	61FF-0001	40 CFR Part 61, Subpart FF	No changing attributes.
FF-PS-1215	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	60QQQ-001	40 CFR Part 60, Subpart QQQ	No changing attributes.
FF-PS-1215	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	61FF-001	40 CFR Part 61, Subpart FF	No changing attributes.
FF-PS-1215	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	63G-008	40 CFR Part 63, Subpart G	No changing attributes.
FF-PS-162	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	60QQQ-001	40 CFR Part 60, Subpart QQQ	No changing attributes.
FF-PS-162	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	61FF-001	40 CFR Part 61, Subpart FF	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
FF-PS-162	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	63G-008	40 CFR Part 63, Subpart G	No changing attributes.
FF-PS-1650	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	60QQQ-001	40 CFR Part 60, Subpart QQQ	No changing attributes.
FF-PS-1650	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	61FF-001	40 CFR Part 61, Subpart FF	No changing attributes.
FF-PS-1650	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	63G-008	40 CFR Part 63, Subpart G	No changing attributes.
FF-PS-236	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	60QQQ-001	40 CFR Part 60, Subpart QQQ	No changing attributes.
FF-PS-236	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	61FF-001	40 CFR Part 61, Subpart FF	No changing attributes.
FF-PS-236	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	63G-008	40 CFR Part 63, Subpart G	No changing attributes.
FF-PS-274	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	60QQQ-001	40 CFR Part 60, Subpart QQQ	No changing attributes.
FF-PS-274	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	61FF-001	40 CFR Part 61, Subpart FF	No changing attributes.
FF-PS-274	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	63G-008	40 CFR Part 63, Subpart G	No changing attributes.
FF-PS-3650	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	60QQQ-001	40 CFR Part 60, Subpart QQQ	No changing attributes.
FF-PS-3650	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	61FF-001	40 CFR Part 61, Subpart FF	No changing attributes.
FF-PS-3650	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	63G-008	40 CFR Part 63, Subpart G	No changing attributes.
FF-PS-402	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	60QQQ-001	40 CFR Part 60, Subpart QQQ	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
FF-PS-402	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	61FF-001	40 CFR Part 61, Subpart FF	No changing attributes.
FF-PS-402	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	63G-008	40 CFR Part 63, Subpart G	No changing attributes.
FF-PS-403	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	60QQQ-001	40 CFR Part 60, Subpart QQQ	No changing attributes.
FF-PS-403	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	61FF-001	40 CFR Part 61, Subpart FF	No changing attributes.
FF-PS-403	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	63G-008	40 CFR Part 63, Subpart G	No changing attributes.
FF-PS-404	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	60QQQ-001	40 CFR Part 60, Subpart QQQ	No changing attributes.
FF-PS-404	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	61FF-001	40 CFR Part 61, Subpart FF	No changing attributes.
FF-PS-404	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	63G-008	40 CFR Part 63, Subpart G	No changing attributes.
FF-PS-405	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	60QQQ-001	40 CFR Part 60, Subpart QQQ	No changing attributes.
FF-PS-405	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	61FF-001	40 CFR Part 61, Subpart FF	No changing attributes.
FF-PS-405	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	63G-008	40 CFR Part 63, Subpart G	No changing attributes.
FF-PS-406	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	60QQQ-001	40 CFR Part 60, Subpart QQQ	No changing attributes.
FF-PS-406	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	61FF-001	40 CFR Part 61, Subpart FF	No changing attributes.
FF-PS-406	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	63G-008	40 CFR Part 63, Subpart G	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
FF-PS-427	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	60QQQ-001	40 CFR Part 60, Subpart QQQ	No changing attributes.
FF-PS-427	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	61FF-001	40 CFR Part 61, Subpart FF	No changing attributes.
FF-PS-427	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	63G-008	40 CFR Part 63, Subpart G	No changing attributes.
FF-PS-434	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	60QQQ-001	40 CFR Part 60, Subpart QQQ	No changing attributes.
FF-PS-434	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	61FF-001	40 CFR Part 61, Subpart FF	No changing attributes.
FF-PS-434	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	63G-008	40 CFR Part 63, Subpart G	No changing attributes.
FF-PS-435	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	60QQQ-001	40 CFR Part 60, Subpart QQQ	No changing attributes.
FF-PS-435	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	61FF-001	40 CFR Part 61, Subpart FF	No changing attributes.
FF-PS-435	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	63G-008	40 CFR Part 63, Subpart G	No changing attributes.
FF-PS-436	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	60QQQ-001	40 CFR Part 60, Subpart QQQ	No changing attributes.
FF-PS-436	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	61FF-001	40 CFR Part 61, Subpart FF	No changing attributes.
FF-PS-436	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	63G-008	40 CFR Part 63, Subpart G	No changing attributes.
FF-PS-439	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	60QQQ-001	40 CFR Part 60, Subpart QQQ	No changing attributes.
FF-PS-439	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	61FF-001	40 CFR Part 61, Subpart FF	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
FF-PS-439	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	63G-008	40 CFR Part 63, Subpart G	No changing attributes.
FF-PS-441	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	60QQQ-001	40 CFR Part 60, Subpart QQQ	No changing attributes.
FF-PS-441	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	61FF-001	40 CFR Part 61, Subpart FF	No changing attributes.
FF-PS-441	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	63G-008	40 CFR Part 63, Subpart G	No changing attributes.
FF-PS-449	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	60QQQ-001	40 CFR Part 60, Subpart QQQ	No changing attributes.
FF-PS-449	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	61FF-001	40 CFR Part 61, Subpart FF	No changing attributes.
FF-PS-449	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	63G-008	40 CFR Part 63, Subpart G	No changing attributes.
FF-PS-451	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	60QQQ-001	40 CFR Part 60, Subpart QQQ	No changing attributes.
FF-PS-451	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	61FF-001	40 CFR Part 61, Subpart FF	No changing attributes.
FF-PS-451	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	63G-008	40 CFR Part 63, Subpart G	No changing attributes.
FF-PS-457	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	60QQQ-001	40 CFR Part 60, Subpart QQQ	No changing attributes.
FF-PS-457	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	61FF-001	40 CFR Part 61, Subpart FF	No changing attributes.
FF-PS-457	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	63G-008	40 CFR Part 63, Subpart G	No changing attributes.
FF-PS-4600	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	60QQQ-001	40 CFR Part 60, Subpart QQQ	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
FF-PS-4600	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	61FF-001	40 CFR Part 61, Subpart FF	No changing attributes.
FF-PS-4600	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	63G-008	40 CFR Part 63, Subpart G	No changing attributes.
FF-PS-475	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	60QQQ-001	40 CFR Part 60, Subpart QQQ	No changing attributes.
FF-PS-475	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	61FF-001	40 CFR Part 61, Subpart FF	No changing attributes.
FF-PS-475	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	63G-008	40 CFR Part 63, Subpart G	No changing attributes.
FF-PS-476	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	60QQQ-001	40 CFR Part 60, Subpart QQQ	No changing attributes.
FF-PS-476	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	61FF-001	40 CFR Part 61, Subpart FF	No changing attributes.
FF-PS-476	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	63G-008	40 CFR Part 63, Subpart G	No changing attributes.
FF-PS-6400	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	60QQQ-001	40 CFR Part 60, Subpart QQQ	No changing attributes.
FF-PS-6400	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	61FF-001	40 CFR Part 61, Subpart FF	No changing attributes.
FF-PS-6400	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	63G-008	40 CFR Part 63, Subpart G	No changing attributes.
FF-PS-J-8	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	60QQQ-001	40 CFR Part 60, Subpart QQQ	No changing attributes.
FF-PS-J-8	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	61FF-001	40 CFR Part 61, Subpart FF	No changing attributes.
FF-PS-J-8	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	63G-008	40 CFR Part 63, Subpart G	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
FF-SC-1907	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	60QQQ-001	40 CFR Part 60, Subpart QQQ	No changing attributes.
FF-SC-1907	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	61FF-001	40 CFR Part 61, Subpart FF	No changing attributes.
FF-SC-1907	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	63G-008	40 CFR Part 63, Subpart G	No changing attributes.
FF-TETRA-1	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	61FF-0001	40 CFR Part 61, Subpart FF	No changing attributes.
FF-TETRA-2	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	61FF-0001	40 CFR Part 61, Subpart FF	No changing attributes.
FF-TK-8010	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	60QQQ-001	40 CFR Part 60, Subpart QQQ	No changing attributes.
FF-TK-8010	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	61FF-001	40 CFR Part 61, Subpart FF	No changing attributes.
FF-TK-8010	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	63G-008	40 CFR Part 63, Subpart G	No changing attributes.
FF-WORU	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	61FF-0001	40 CFR Part 61, Subpart FF	No changing attributes.
FF-WWTU	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	60QQQ-002	40 CFR Part 60, Subpart QQQ	No changing attributes.
FF-WWTU	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	61FF-001	40 CFR Part 61, Subpart FF	No changing attributes.
FF-WWTU	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	63G-008	40 CFR Part 63, Subpart G	No changing attributes.
FIREWTR2013-1	SRIC ENGINES	N/A	60IIII-007	40 CFR Part 60, Subpart IIII	No changing attributes.
FIREWTR2013-1	SRIC ENGINES	N/A	63ZZZZ-010	40 CFR Part 63, Subpart ZZZZ	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
FIREWTR2013-2	SRIC ENGINES	N/A	60IIII-007	40 CFR Part 60, Subpart IIII	No changing attributes.
FIREWTR2013-2	SRIC ENGINES	N/A	63ZZZZ-010	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
FLARE-05	FLARES	N/A	R1111-0001	30 TAC Chapter 111, Visible Emissions	No changing attributes.
FLARE-05	FLARES	N/A	60A-0004	40 CFR Part 60, Subpart A	No changing attributes.
FLARE-05	FLARES	N/A	63A-0004	40 CFR Part 63, Subpart A	No changing attributes.
FLARE-05	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	63CC-1	40 CFR Part 63, Subpart CC	No changing attributes.
FLARE-103B	FLARES	N/A	R1111-0001	30 TAC Chapter 111, Visible Emissions	No changing attributes.
FLARE-103B	FLARES	N/A	60A-0004	40 CFR Part 60, Subpart A	No changing attributes.
FLARE-103B	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0024	40 CFR Part 60, Subpart J	No changing attributes.
FLARE-103B	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60Ja-0121	40 CFR Part 60, Subpart Ja	No changing attributes.
FLARE-103B	FLARES	N/A	63A-0004	40 CFR Part 63, Subpart A	No changing attributes.
FLARE-103B	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	63CC-1	40 CFR Part 63, Subpart CC	No changing attributes.
FLARE-13	FLARES	N/A	R1111-0001	30 TAC Chapter 111, Visible Emissions	No changing attributes.
FLARE-13	FLARES	N/A	60A-0004	40 CFR Part 60, Subpart A	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
FLARE-13	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0024	40 CFR Part 60, Subpart J	No changing attributes.
FLARE-13	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60Ja-0121	40 CFR Part 60, Subpart Ja	No changing attributes.
FLARE-13	FLARES	N/A	63A-0004	40 CFR Part 63, Subpart A	No changing attributes.
FLARE-13	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	63CC-1	40 CFR Part 63, Subpart CC	No changing attributes.
FLARE-15	FLARES	N/A	R1111-0001	30 TAC Chapter 111, Visible Emissions	No changing attributes.
FLARE-15	FLARES	N/A	60A-0004	40 CFR Part 60, Subpart A	No changing attributes.
FLARE-15	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0024	40 CFR Part 60, Subpart J	No changing attributes.
FLARE-15	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60Ja-0121	40 CFR Part 60, Subpart Ja	No changing attributes.
FLARE-15	FLARES	N/A	63A-0004	40 CFR Part 63, Subpart A	No changing attributes.
FLARE-15	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	63CC-1	40 CFR Part 63, Subpart CC	No changing attributes.
FLARE-18	FLARES	N/A	R1111-0001	30 TAC Chapter 111, Visible Emissions	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
FLARE-18	FLARES	N/A	60A-0004	40 CFR Part 60, Subpart A	No changing attributes.
FLARE-18	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0024	40 CFR Part 60, Subpart J	No changing attributes.
FLARE-18	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60Ja-0121	40 CFR Part 60, Subpart Ja	No changing attributes.
FLARE-18	FLARES	N/A	63A-0004	40 CFR Part 63, Subpart A	No changing attributes.
FLARE-18	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	63CC-1	40 CFR Part 63, Subpart CC	No changing attributes.
FLARE-19	FLARES	N/A	R1111-0001	30 TAC Chapter 111, Visible Emissions	No changing attributes.
FLARE-19	FLARES	N/A	60A-0004	40 CFR Part 60, Subpart A	No changing attributes.
FLARE-19	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0024	40 CFR Part 60, Subpart J	No changing attributes.
FLARE-19	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60Ja-0121	40 CFR Part 60, Subpart Ja	No changing attributes.
FLARE-19	FLARES	N/A	63A-0004	40 CFR Part 63, Subpart A	No changing attributes.
FLARE-19	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	63CC-1	40 CFR Part 63, Subpart CC	No changing attributes.
FLARE-20	FLARES	N/A	R1111-0001	30 TAC Chapter 111, Visible	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
				Emissions	
FLARE-20	FLARES	N/A	60A-0004	40 CFR Part 60, Subpart A	No changing attributes.
FLARE-20	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0024	40 CFR Part 60, Subpart J	No changing attributes.
FLARE-20	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60Ja-0121	40 CFR Part 60, Subpart Ja	No changing attributes.
FLARE-20	FLARES	N/A	63A-0004	40 CFR Part 63, Subpart A	No changing attributes.
FLARE-20	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	63CC-1	40 CFR Part 63, Subpart CC	No changing attributes.
FLARE-22	FLARES	N/A	R1111-0001	30 TAC Chapter 111, Visible Emissions	No changing attributes.
FLARE-22	FLARES	N/A	60A-0004	40 CFR Part 60, Subpart A	No changing attributes.
FLARE-22	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0024	40 CFR Part 60, Subpart J	No changing attributes.
FLARE-22	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60Ja-0121	40 CFR Part 60, Subpart Ja	No changing attributes.
FLARE-22	FLARES	N/A	63A-0004	40 CFR Part 63, Subpart A	No changing attributes.
FLARE-22	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	63CC-1	40 CFR Part 63, Subpart CC	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
FLARE-23	FLARES	N/A	R1111-0001	30 TAC Chapter 111, Visible Emissions	No changing attributes.
FLARE-23	FLARES	N/A	60A-0004	40 CFR Part 60, Subpart A	No changing attributes.
FLARE-23	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0024	40 CFR Part 60, Subpart J	No changing attributes.
FLARE-23	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60Ja-0121	40 CFR Part 60, Subpart Ja	No changing attributes.
FLARE-23	FLARES	N/A	63A-0004	40 CFR Part 63, Subpart A	No changing attributes.
FLARE-23	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	63CC-1	40 CFR Part 63, Subpart CC	No changing attributes.
FLARE-26	FLARES	N/A	R1111-0001	30 TAC Chapter 111, Visible Emissions	No changing attributes.
FLARE-26	FLARES	N/A	60A-0005	40 CFR Part 60, Subpart A	No changing attributes.
FLARE-26	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60Ja-0121	40 CFR Part 60, Subpart Ja	No changing attributes.
FLARE-26	FLARES	N/A	63A-0007	40 CFR Part 63, Subpart A	No changing attributes.
FLARE-26	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	63CC-1	40 CFR Part 63, Subpart CC	No changing attributes.
F-T-L3010	STORAGE TANKS/VESSELS	N/A	R5112-0003	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
F-T-L3010	STORAGE	N/A	60QQQ-0014	40 CFR Part 60, Subpart	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	TANKS/VESSELS			QQQ	
F-T-L3010	STORAGE TANKS/VESSELS	N/A	61FF-0027	40 CFR Part 61, Subpart FF	No changing attributes.
F-T-L3210	STORAGE TANKS/VESSELS	N/A	R5112-0002	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
F-T-L3210	STORAGE TANKS/VESSELS	N/A	60QQQ-0007	40 CFR Part 60, Subpart QQQ	No changing attributes.
F-T-L3210	STORAGE TANKS/VESSELS	N/A	61FF-0005	40 CFR Part 61, Subpart FF	No changing attributes.
F-T-L3210	STORAGE TANKS/VESSELS	N/A	63G-004	40 CFR Part 63, Subpart G	No changing attributes.
F-T-L5010	STORAGE TANKS/VESSELS	N/A	R5112-0006	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
F-T-L5010	STORAGE TANKS/VESSELS	N/A	60QQQ-0014	40 CFR Part 60, Subpart QQQ	No changing attributes.
F-T-L5010	STORAGE TANKS/VESSELS	N/A	61FF-0027	40 CFR Part 61, Subpart FF	No changing attributes.
F-T-L5010	STORAGE TANKS/VESSELS	N/A	63G-001	40 CFR Part 63, Subpart G	No changing attributes.
F-T-L5020	STORAGE TANKS/VESSELS	N/A	R5112-0006	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
F-T-L5020	STORAGE TANKS/VESSELS	N/A	60QQQ-0008	40 CFR Part 60, Subpart QQQ	No changing attributes.
F-T-L5020	STORAGE TANKS/VESSELS	N/A	63G-001	40 CFR Part 63, Subpart G	No changing attributes.
GFU-241-H1	PROCESS HEATERS/FURNACES	N/A	63DDDDD-001	40 CFR Part 63, Subpart DDDDD	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
GFU-242-H	PROCESS HEATERS/FURNACES	N/A	63DDDDD-001	40 CFR Part 63, Subpart DDDDD	No changing attributes.
GFU-243-H	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60Ja-0161	40 CFR Part 60, Subpart Ja	No changing attributes.
GFU-243-H	PROCESS HEATERS/FURNACES	N/A	63DDDDD-001	40 CFR Part 63, Subpart DDDDD	No changing attributes.
GFU-244-HA	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0023	40 CFR Part 60, Subpart J	No changing attributes.
GFU-244-HA	PROCESS HEATERS/FURNACES	N/A	63DDDDD-001	40 CFR Part 63, Subpart DDDDD	No changing attributes.
GFU-244-HB	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0023	40 CFR Part 60, Subpart J	No changing attributes.
GFU-244-HB	PROCESS HEATERS/FURNACES	N/A	63DDDDD-001	40 CFR Part 63, Subpart DDDDD	No changing attributes.
GRPAPI	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	F-T-L1010, F-T-L1020, F-T-L1030	R5131-0004	30 TAC Chapter 115, Water Separation	No changing attributes.
GRPAPI	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	F-T-L1010, F-T-L1020, F-T-L1030	60QQQ-0099	40 CFR Part 60, Subpart QQQ	No changing attributes.
GRPAPI	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	F-T-L1010, F-T-L1020, F-T-L1030	61FF-1657	40 CFR Part 61, Subpart FF	No changing attributes.
GRPAPI	VOLATILE ORGANIC	F-T-L1010, F-T-	63G-007	40 CFR Part 63, Subpart G	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	COMPOUND WATER SEPARATORS	L1020, F-T-L1030			
GRPAPI	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	F-T-L1010, F-T-L1020, F-T-L1030	63VV-0001	40 CFR Part 63, Subpart VV	No changing attributes.
GRP-C8456	STORAGE TANKS/VESSELS	T-133, T-889	R5112-0010	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
GRPCC2VENT	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	843-VENT	R5131-1000	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
GRPCC2VENT	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	843-VENT	63CC-1010	40 CFR Part 63, Subpart CC	No changing attributes.
GRPCCEFRMS	STORAGE TANKS/VESSELS	T-2101, T-2117, T-2132, T-2137, T-2148, T-2159, T-2160, T-2161, T-77, T-896	R5112-0004	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
GRPCCEFRMS	STORAGE TANKS/VESSELS	T-2101, T-2117, T-2132, T-2137, T-2148, T-2159, T-2160, T-2161, T-77, T-896	63CC-0254	40 CFR Part 63, Subpart CC	Group 1 Storage Vessel = The storage vessel is a Group 2 vessel., Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.
GRPCCEFRMS	STORAGE TANKS/VESSELS	T-2101, T-2117, T-2132, T-2137, T-2148, T-2159, T-2160, T-2161, T-77, T-896	63CC-1254	40 CFR Part 63, Subpart CC	Existing Source = The storage vessel is at an existing source., True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa), Emission Control Type = External floating roof, Seal

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					Type = Two seals, one above the other, the primary seal being a metallic shoe seal, Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641)
GRP-CCFUG	FUGITIVE EMISSION UNITS	F-147, F-246, F-7842	R5352-ALL	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	No changing attributes.
GRP-CCFUG	FUGITIVE EMISSION UNITS	F-147, F-246, F-7842	63CCH-ALL	40 CFR Part 63, Subpart CC	No changing attributes.
GRPCCIFRMS	STORAGE TANKS/VESSELS	T-2110, T-925, T-926	R5112-0001	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
GRPCCIFRMS	STORAGE TANKS/VESSELS	T-2110, T-925, T-926	63CC-0250	40 CFR Part 63, Subpart CC	No changing attributes.
GRPCONE1	STORAGE TANKS/VESSELS	T-100, T-103, T-2105, T-2163, T-2164, T-99	R5112-0006	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
GRPCONE1	STORAGE TANKS/VESSELS	T-100, T-103, T-2105, T-2163, T-2164, T-99	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
GRPCOOL	INDUSTRIAL PROCESS COOLING TOWERS	CT-100, CT-147, CT-244, CT-246, CT-400, F-101CT, F-136ACT, F-136BCT, F-233PS, F-314CT, F-316CT, F-360PS, F-364CT, F-366CT	63CC-3000	40 CFR Part 63, Subpart CC	No changing attributes.
GRPFFEFRMS	STORAGE TANKS/VESSELS	T-151, T-2145, T-2588, T-2590, T-78, T-88	R5112-0004	30 TAC Chapter 115, Storage of VOCs	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
GRPFFEFRMS	STORAGE TANKS/VESSELS	T-151, T-2145, T-2588, T-2590, T-78, T-88	61FF-0006	40 CFR Part 61, Subpart FF	No changing attributes.
GRPFFEFRMS	STORAGE TANKS/VESSELS	T-151, T-2145, T-2588, T-2590, T-78, T-88	63CC-0082	40 CFR Part 63, Subpart CC	Group 1 Storage Vessel = The storage vessel is a Group 2 vessel., Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.
GRPFFEFRMS	STORAGE TANKS/VESSELS	T-151, T-2145, T-2588, T-2590, T-78, T-88	63CC-0182	40 CFR Part 63, Subpart CC	Existing Source = The storage vessel is at an existing source., True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa), Emission Control Type = External floating roof, Seal Type = Two seals, one above the other, the primary seal being a metallic shoe seal, Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641)
GRPFFIFRMS	STORAGE TANKS/VESSELS	T-1790, T-1791	R5112-0001	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
GRPFFIFRMS	STORAGE TANKS/VESSELS	T-1790, T-1791	61FF-0005	40 CFR Part 61, Subpart FF	No changing attributes.
GRPFFIFRMS	STORAGE TANKS/VESSELS	T-1790, T-1791	63CC-0082	40 CFR Part 63, Subpart CC	No changing attributes.
GRPFFIFRMS	STORAGE TANKS/VESSELS	T-1790, T-1791	63G-006	40 CFR Part 63, Subpart G	No changing attributes.
GRP-FUGCC	FUGITIVE EMISSION	F-545, F-843, F-942	R5352-ALL	30 TAC Chapter 115, Pet.	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	UNITS			Refinery & Petrochemicals	
GRP-FUGCC	FUGITIVE EMISSION UNITS	F-545, F-843, F-942	63CCVV-ALL	40 CFR Part 63, Subpart CC	No changing attributes.
GRPGEFRMS	STORAGE TANKS/VESSELS	F-T-L1110, F-T-L1120, F-T-L2010, F-T-L3310, F-T-L3320	R5112-0004	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
GRPGEFRMS	STORAGE TANKS/VESSELS	F-T-L1110, F-T-L1120, F-T-L2010, F-T-L3310, F-T-L3320	60QQQ-0006	40 CFR Part 60, Subpart QQQ	No changing attributes.
GRPGEFRMS	STORAGE TANKS/VESSELS	F-T-L1110, F-T-L1120, F-T-L2010, F-T-L3310, F-T-L3320	61FF-0006	40 CFR Part 61, Subpart FF	No changing attributes.
GRPGEFRMS	STORAGE TANKS/VESSELS	F-T-L1110, F-T-L1120, F-T-L2010, F-T-L3310, F-T-L3320	63G-002	40 CFR Part 63, Subpart G	No changing attributes.
GRPGFIFRMS	STORAGE TANKS/VESSELS	T-1848, T-1849	R5112-0001	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
GRPGFIFRMS	STORAGE TANKS/VESSELS	T-1848, T-1849	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
GRP-GGGFUG	FUGITIVE EMISSION UNITS	F-1241, F-1242, F-241, F-243, F-244, F-443, F-6341, F-7542, F-8742, F-PH163	R5352-ALL	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	No changing attributes.
GRP-GGGFUG	FUGITIVE EMISSION UNITS	F-1241, F-1242, F-241, F-243, F-244,	60GGG-ALL	40 CFR Part 60, Subpart GGG	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
		F-443, F-6341, F-7542, F-8742, F-PH163			
GRP-GGGFUG	FUGITIVE EMISSION UNITS	F-1241, F-1242, F-241, F-243, F-244, F-443, F-6341, F-7542, F-8742, F-PH163	63CCVV-ALL	40 CFR Part 63, Subpart CC	No changing attributes.
GRPGIFRMS1	STORAGE TANKS/VESSELS	F-T-L1310, F-T-L1410	R5112-0001	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
GRPGIFRMS1	STORAGE TANKS/VESSELS	F-T-L1310, F-T-L1410	60QQQ-0007	40 CFR Part 60, Subpart QQQ	No changing attributes.
GRPGIFRMS1	STORAGE TANKS/VESSELS	F-T-L1310, F-T-L1410	61FF-0005	40 CFR Part 61, Subpart FF	No changing attributes.
GRPGIFRMS1	STORAGE TANKS/VESSELS	F-T-L1310, F-T-L1410	63G-005	40 CFR Part 63, Subpart G	No changing attributes.
GRPGIFRMS2	STORAGE TANKS/VESSELS	F-T-L1210, F-T-L8010	R5112-0002	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
GRPGIFRMS2	STORAGE TANKS/VESSELS	F-T-L1210, F-T-L8010	60QQQ-0007	40 CFR Part 60, Subpart QQQ	No changing attributes.
GRPGIFRMS2	STORAGE TANKS/VESSELS	F-T-L1210, F-T-L8010	61FF-0005	40 CFR Part 61, Subpart FF	No changing attributes.
GRPGIFRMS2	STORAGE TANKS/VESSELS	F-T-L1210, F-T-L8010	63G-003	40 CFR Part 63, Subpart G	No changing attributes.
GRPKVOC	STORAGE TANKS/VESSELS	T-2182, T-2183	R5112-0004	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
GRPKVOC	STORAGE TANKS/VESSELS	T-2182, T-2183	60K-003	40 CFR Part 60, Subpart K	No changing attributes.
GRPKVOC	STORAGE	T-2182, T-2183	63CC-0254	40 CFR Part 63, Subpart CC	Group 1 Storage Vessel = The

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	TANKS/VESSELS				storage vessel is a Group 2 vessel., Applicability = The storage vessel is subject to the control requirements of 40 CFR Part 60, Subpart K.
GRPKVOC	STORAGE TANKS/VESSELS	T-2182, T-2183	63CC-1254	40 CFR Part 63, Subpart CC	Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641)., Existing Source = The storage vessel is at an existing source., True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa), Emission Control Type = External floating roof, Seal Type = Two seals, one above the other, the primary seal being a metallic shoe seal.
GRPRTOTKS	STORAGE TANKS/VESSELS	F-T-L3110, F-T-L3120	R5112-0006	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
GRPRTOTKS	STORAGE TANKS/VESSELS	F-T-L3110, F-T-L3120	60QQQ-0014	40 CFR Part 60, Subpart QQQ	No changing attributes.
GRPRTOTKS	STORAGE TANKS/VESSELS	F-T-L3110, F-T-L3120	61FF-0027	40 CFR Part 61, Subpart FF	No changing attributes.
GRPRTOTKS	STORAGE TANKS/VESSELS	F-T-L3110, F-T-L3120	63G-001	40 CFR Part 63, Subpart G	No changing attributes.
GRP-RVFUG	FUGITIVE EMISSION UNITS	AUCT, E-01-SUMP, F-15BH, F-16BH, F-18BH, F-242, F-441, F-541/3, F-7846, F-7848, F-8748, F-BH-15, F-BH-16, F-BH-18, F-FGMD, F-PH	R5352-ALL	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
		11, F-PH41, F-PH84, F-PIPING, FUGITIVE, F-WORU			
GRPTK5491	STORAGE TANKS/VESSELS	T-110, T-111	R5112-0005	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
GRPTK5491	STORAGE TANKS/VESSELS	T-110, T-111	60K-001	40 CFR Part 60, Subpart K	No changing attributes.
GRPTK5491	STORAGE TANKS/VESSELS	T-110, T-111	63CC-0254	40 CFR Part 63, Subpart CC	Group 1 Storage Vessel = The storage vessel is a Group 2 vessel., Applicability = The storage vessel is subject to the control requirements of 40 CFR Part 60, Subpart K.
GRPTK5491	STORAGE TANKS/VESSELS	T-110, T-111	63CC-1254	40 CFR Part 63, Subpart CC	Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR §63.641)., Existing Source = The storage vessel is at an existing source., True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa), Emission Control Type = External floating roof, Seal Type = Two seals, one above the other, the primary seal being a metallic shoe seal.
GRPTK7600	STORAGE TANKS/VESSELS	T-283, T-284, T-285	R5112-0005	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
GRPTK7600	STORAGE TANKS/VESSELS	T-283, T-284, T-285	60Ka-002	40 CFR Part 60, Subpart Ka	No changing attributes.
GRPTK7600	STORAGE TANKS/VESSELS	T-283, T-284, T-285	63CC-0254	40 CFR Part 63, Subpart CC	Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.,

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					Applicability = The storage vessel is subject to the control requirements of 40 CFR Part 60, Subpart Ka, Storage Vessel Description = Pontoon-type or double-deck-type external floating roof with mechanical shoe primary seal, Reid Vapor Pressure = RVP is greater than or equal to 2.0 psia
GRPTK7600	STORAGE TANKS/VESSELS	T-283, T-284, T-285	63CC-1254	40 CFR Part 63, Subpart CC	Existing Source = The storage vessel is at an existing source., True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa), Emission Control Type = External floating roof, Seal Type = Two seals, one above the other, the primary seal being a metallic shoe seal, Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641)
GRPVENTCC1	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	443-VENT-1, 443-VENT-10, 443-VENT-2, 443-VENT-3, 443-VENT-4, 443-VENT-5, 443-VENT-6, 443-VENT-7, 443-VENT-8, 443-VENT-9	R5131-1001	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
GRPVENTCC1	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	443-VENT-1, 443-VENT-10, 443-VENT-2, 443-VENT-	63CC-1011	40 CFR Part 63, Subpart CC	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
		3, 443-VENT-4, 443-VENT-5, 443-VENT-6, 443-VENT-7, 443-VENT-8, 443-VENT-9			
GRP-VVFUG	FUGITIVE EMISSION UNITS	F-1344, F-146, F-243-MOD, F-245, F-PIPE, F-SRTF	R5352-ALL	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	No changing attributes.
GRP-VVFUG	FUGITIVE EMISSION UNITS	F-1344, F-146, F-243-MOD, F-245, F-PIPE, F-SRTF	60VV-ALL	40 CFR Part 60, Subpart VV	No changing attributes.
GRP-VVFUG	FUGITIVE EMISSION UNITS	F-1344, F-146, F-243-MOD, F-245, F-PIPE, F-SRTF	63CCVV-ALL	40 CFR Part 63, Subpart CC	No changing attributes.
GRP-WASH1	SOLVENT DEGREASING MACHINES	PW-LVP-1, PW-LVP-2, PW-LVP-3, PW-LVP-4	R5412-0057	30 TAC Chapter 115, Degreasing Processes	No changing attributes.
GRP-WASH2	SOLVENT DEGREASING MACHINES	PW-HVP-1	R5412-0057	30 TAC Chapter 115, Degreasing Processes	No changing attributes.
HCU-942H1/2	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0024	40 CFR Part 60, Subpart J	No changing attributes.
HCU-942H3	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0024	40 CFR Part 60, Subpart J	No changing attributes.
HCU-943-A/B	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60Ja-0161	40 CFR Part 60, Subpart Ja	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
HCU-943-C	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60Ja-0161	40 CFR Part 60, Subpart Ja	No changing attributes.
HFAU-443-H	PROCESS HEATERS/FURNACES	N/A	63DDDDD-001	40 CFR Part 63, Subpart DDDDD	No changing attributes.
MC-24/25	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	63CC-1003	40 CFR Part 63, Subpart CC	No changing attributes.
NSTF TK 100 99	SRIC ENGINES	N/A	60IIII-005	40 CFR Part 60, Subpart IIII	No changing attributes.
NSTF TK 100 99	SRIC ENGINES	N/A	63ZZZZ-009	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
NSTF TK 151	SRIC ENGINES	N/A	60IIII-004	40 CFR Part 60, Subpart IIII	No changing attributes.
NSTF TK 151	SRIC ENGINES	N/A	63ZZZZ-009	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
PRO-WWTU	TREATMENT PROCESS	N/A	61FF-0216	40 CFR Part 61, Subpart FF	No changing attributes.
PRO-WWTU	TREATMENT PROCESS	N/A	63G-009	40 CFR Part 63, Subpart G	No changing attributes.
RTO	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	60QQQ-0002	40 CFR Part 60, Subpart QQQ	No changing attributes.
RTO	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	61FF-002	40 CFR Part 61, Subpart FF	No changing attributes.
SRU-543	GAS SWEETENING/SULFUR RECOVERY UNITS	N/A	R2007-0003	30 TAC Chapter 112, Sulfur Compounds	No changing attributes.
SRU-543	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60Ja-0177	40 CFR Part 60, Subpart Ja	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
SRU-543	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	63UUU-3000	40 CFR Part 63, Subpart UUU	No changing attributes.
SRU-544	GAS SWEETENING/SULFUR RECOVERY UNITS	N/A	R2007-0003	30 TAC Chapter 112, Sulfur Compounds	No changing attributes.
SRU-544	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60Ja-0177	40 CFR Part 60, Subpart Ja	No changing attributes.
SRU-544	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	63UUU-3000	40 CFR Part 63, Subpart UUU	No changing attributes.
SRU-545	GAS SWEETENING/SULFUR RECOVERY UNITS	N/A	R2007-0003	30 TAC Chapter 112, Sulfur Compounds	No changing attributes.
SRU-545	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60Ja-0177	40 CFR Part 60, Subpart Ja	No changing attributes.
SRU-545	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	63UUU-3001	40 CFR Part 63, Subpart UUU	No changing attributes.
SRU-546	GAS SWEETENING/SULFUR RECOVERY UNITS	N/A	R2007-0003	30 TAC Chapter 112, Sulfur Compounds	No changing attributes.
SRU-546	FCCU CAT REGEN/FUEL GAS	N/A	60Ja-0177	40 CFR Part 60, Subpart Ja	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	COMBUSTION/CLAUS SRU				
SRU-546	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	63UUU-3001	40 CFR Part 63, Subpart UUU	No changing attributes.
T-106	STORAGE TANKS/VESSELS	N/A	R5112-0005	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-106	STORAGE TANKS/VESSELS	N/A	60K-001	40 CFR Part 60, Subpart K	No changing attributes.
T-106	STORAGE TANKS/VESSELS	N/A	63CC-0254	40 CFR Part 63, Subpart CC	Group 1 Storage Vessel = The storage vessel is a Group 2 vessel., Applicability = The storage vessel is subject to the control requirements of 40 CFR Part 60, Subpart K.
T-106	STORAGE TANKS/VESSELS	N/A	63CC-1254	40 CFR Part 63, Subpart CC	Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641)., Existing Source = The storage vessel is at an existing source., True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa), Emission Control Type = External floating roof, Seal Type = Two seals, one above the other, the primary seal being a metallic shoe seal.
T-107	STORAGE TANKS/VESSELS	N/A	R5112-0005	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-107	STORAGE	N/A	60K-001	40 CFR Part 60, Subpart K	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	TANKS/VESSELS				
T-107	STORAGE TANKS/VESSELS	N/A	63CC-0254	40 CFR Part 63, Subpart CC	Group 1 Storage Vessel = The storage vessel is a Group 2 vessel., Applicability = The storage vessel is subject to the control requirements of 40 CFR Part 60, Subpart K.
T-107	STORAGE TANKS/VESSELS	N/A	63CC-1254	40 CFR Part 63, Subpart CC	Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR §63.641)., Existing Source = The storage vessel is at an existing source., True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa), Emission Control Type = External floating roof, Seal Type = Two seals, one above the other, the primary seal being a metallic shoe seal.
T-1912	STORAGE TANKS/VESSELS	N/A	R5112-0001	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-1912	STORAGE TANKS/VESSELS	N/A	60QQQ-0007	40 CFR Part 60, Subpart QQQ	No changing attributes.
T-1912	STORAGE TANKS/VESSELS	N/A	61FF-0005	40 CFR Part 61, Subpart FF	No changing attributes.
T-2111	STORAGE TANKS/VESSELS	N/A	R5112-0004	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-2111	STORAGE TANKS/VESSELS	N/A	63CC-0254	40 CFR Part 63, Subpart CC	Group 1 Storage Vessel = The storage vessel is a Group 2 vessel., Applicability = The storage vessel is required to comply with 40 CFR Part

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					63, Subpart CC and is part of a process unit.
T-2111	STORAGE TANKS/VESSELS	N/A	63CC-1254	40 CFR Part 63, Subpart CC	Existing Source = The storage vessel is at an existing source., True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa), Emission Control Type = External floating roof, Seal Type = Two seals, one above the other, the primary seal being a metallic shoe seal, Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641)
T-2112	STORAGE TANKS/VESSELS	N/A	R5112-0004	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-2112	STORAGE TANKS/VESSELS	N/A	63CC-0254	40 CFR Part 63, Subpart CC	Group 1 Storage Vessel = The storage vessel is a Group 2 vessel., Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.
T-2112	STORAGE TANKS/VESSELS	N/A	63CC-1254	40 CFR Part 63, Subpart CC	Existing Source = The storage vessel is at an existing source., True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa), Emission Control Type = External floating roof, Seal Type = Two seals, one above the other, the primary seal being a metallic shoe seal, Group 1 Storage

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641)
T-2113	STORAGE TANKS/VESSELS	N/A	R5112-0004	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-2113	STORAGE TANKS/VESSELS	N/A	60K-002	40 CFR Part 60, Subpart K	No changing attributes.
T-2113	STORAGE TANKS/VESSELS	N/A	61FF-0006	40 CFR Part 61, Subpart FF	No changing attributes.
T-2113	STORAGE TANKS/VESSELS	N/A	63CC-0254	40 CFR Part 63, Subpart CC	Group 1 Storage Vessel = The storage vessel is a Group 2 vessel., Applicability = The storage vessel is subject to the control requirements of 40 CFR Part 60, Subpart K.
T-2113	STORAGE TANKS/VESSELS	N/A	63CC-1254	40 CFR Part 63, Subpart CC	Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR §63.641)., Existing Source = The storage vessel is at an existing source., True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa), Emission Control Type = External floating roof, Seal Type = Two seals, one above the other, the primary seal being a metallic shoe seal.
T-2133	STORAGE TANKS/VESSELS	N/A	R5112-0001	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-2133	STORAGE TANKS/VESSELS	N/A	60Kb-003	40 CFR Part 60, Subpart Kb	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
T-2133	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.
T-2133	STORAGE TANKS/VESSELS	N/A	63CC-0013	40 CFR Part 63, Subpart CC	Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641)
T-2162	STORAGE TANKS/VESSELS	N/A	R5112-0001	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-2162	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
T-2186	STORAGE TANKS/VESSELS	N/A	R5112-0010A	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-2186	STORAGE TANKS/VESSELS	N/A	60Kb-004	40 CFR Part 60, Subpart Kb	No changing attributes.
T-2186	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.
T-2186	STORAGE TANKS/VESSELS	N/A	63CC-0013	40 CFR Part 63, Subpart CC	Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641)
T-2401	STORAGE TANKS/VESSELS	N/A	R5112-0001	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-2401	STORAGE TANKS/VESSELS	N/A	61FF-0005	40 CFR Part 61, Subpart FF	No changing attributes.
T-2401	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
T-2900	STORAGE TANKS/VESSELS	N/A	R5112-0001	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-2900	STORAGE	N/A	60Kb-0177	40 CFR Part 60, Subpart Kb	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	TANKS/VESSELS				
T-2900	STORAGE TANKS/VESSELS	N/A	63CC-0082	40 CFR Part 63, Subpart CC	No changing attributes.
T-5	STORAGE TANKS/VESSELS	N/A	R5112-0004	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-5	STORAGE TANKS/VESSELS	N/A	60Kb-001	40 CFR Part 60, Subpart Kb	No changing attributes.
T-5	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	Group 1 Storage Vessel = The storage vessel is a Group 2 vessel.
T-5	STORAGE TANKS/VESSELS	N/A	63CC-0013	40 CFR Part 63, Subpart CC	Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641)
T-5002	STORAGE TANKS/VESSELS	N/A	R5112-0006	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-5002	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
T-5003	STORAGE TANKS/VESSELS	N/A	R5112-0007	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-5003	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
T-8010	STORAGE TANKS/VESSELS	N/A	R5112-3	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-8010	STORAGE TANKS/VESSELS	N/A	61FF-1	40 CFR Part 61, Subpart FF	No changing attributes.
T-8010	STORAGE TANKS/VESSELS	N/A	63CC-3	40 CFR Part 63, Subpart CC	No changing attributes.
T-82	STORAGE	N/A	R5112-0004	30 TAC Chapter 115,	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	TANKS/VESSELS			Storage of VOCs	
T-82	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	Group 1 Storage Vessel = The storage vessel is a Group 2 vessel., Applicability = The storage vessel is required to comply with 40 CFR Part 63, Subpart CC and is part of a process unit.
T-82	STORAGE TANKS/VESSELS	N/A	63CC-0013	40 CFR Part 63, Subpart CC	Existing Source = The storage vessel is at an existing source., True Vapor Pressure = Maximum true vapor pressure of the total organic HAPs in the liquid is less than 11.11 psi (76.6 kPa), Emission Control Type = External floating roof, Seal Type = Two seals, one above the other, the primary seal being a metallic shoe seal, Group 1 Storage Vessel = The storage vessel is a Group 1 storage vessel (as defined in 40 CFR § 63.641)
TRACHWPUMP	SRIC ENGINES	N/A	63ZZZZ-002	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
VACUUM	VACUUM PRODUCING SYSTEMS	N/A	R5131-2000	30 TAC Chapter 115, Unit Turn & Vac System-Pet Ref	No changing attributes.

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
1334-RVENT	EU	63UUU-2000	TOC	40 CFR Part 63, Subpart UUU	§ 63.1566(a)(1)(i)-Table15.1 § 63.1566(a)(1) § 63.1566(a)(2) § 63.1566(a)(2)-Table16.1 § 63.1566(a)(3) § 63.1566(a)(4) § 63.1566(a)(5) § 63.1566(b)(3) § 63.1566(b)(4) § 63.1566(b)(6) § 63.1566(b)(6)-Table19.1 § 63.1566(c)(1) § 63.1566(c)(2) § 63.1570(a) § 63.1570(b) § 63.1570(c) § 63.1570(d) § 63.1570(g) [G]§ 63.1571(e)	For each applicable process vent for a new or existing catalytic reforming unit, you must vent emissions of total organic compounds (TOC) to a flare that meets the control device requirements in §63.11(b) (Option 1). Visible emissions from a flare must not exceed a total of 5 minutes during any 2-hour operating period.	§ 63.1566(b)(1) § 63.1566(b)(1)-Table17.1 § 63.1566(b)(2) § 63.1566(b)(2)-Table18.1.a § 63.1566(b)(2)-Table18.1.b § 63.1566(c)(1)-Table20.1 § 63.1566(c)(1)-Table21.1 § 63.1571(a) § 63.1571(a)(1) [G]§ 63.1571(b) [G]§ 63.1572(d)	§ 63.1566(c)(1)-Table21.1 § 63.1570(c) [G]§ 63.1576(a) § 63.1576(c) § 63.1576(d) § 63.1576(e) § 63.1576(f) § 63.1576(g) § 63.1576(h) § 63.1576(i)	§ 63.1566(b)(7) § 63.1566(b)(8) § 63.1570(f) § 63.1571(a) [G]§ 63.1574(a) § 63.1574(d) § 63.1574(d)-Table42.1 § 63.1574(d)-Table42.2 § 63.1574(d)-Table42.3 § 63.1575(a) § 63.1575(a)-Table43.1 [G]§ 63.1575(b) [G]§ 63.1575(c) [G]§ 63.1575(d) [G]§ 63.1575(f) § 63.1575(g) [G]§ 63.1575(h)
16BHSW	EU	60IIII-004	NO_X	40 CFR Part 60, Subpart IIII	§ 60.4205(a)-Table 1 § 60.4206 § 60.4207(b) § 60.4211(b) § 60.4211(b)(1) [G]§ 60.4211(f) § 60.4218	Owners and operators of emergency stationary CI ICE, that are not fire pump engines, with a maximum engine power greater than or equal to 37 KW and a displacement of less than 10 liters per cylinder and is a pre-2007 model year must comply with a NOx emission limit of 9.2 g/KW-hr, as listed in Table 1 to this subpart.	§ 60.4209(a)	§ 60.4214(b)	[G]§ 60.4214(d)
16BHSW	EU	63ZZZZ-007	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(c)	Stationary RICE subject to Regulations under 40	None	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						CFR Part 60. An affected source that meets any of the criteria in paragraphs (c)(1) through (7) of this section must meet the requirements of this part by meeting the requirements of 40 CFR part 60 subpart IIII, for compression ignition engines or 40 CFR part 60 subpart JJJJ, for spark ignition engines as applicable. No further requirements apply for such engines under this part.			
ADMNGEN	EU	63ZZZZ-008	Exempt	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(b)(1) § 63.6595(c) § 63.6640(f)(1) [G]§ 63.6640(f)(2) § 63.6640(f)(3)	An affected source which meets either of the criteria in paragraphs §63.6590(b)(1)(i)-(ii) of this section does not have to meet the requirements of this subpart and of subpart A of this part except for the initial notification requirements of §63.6645(f).	None	None	§ 63.6645(c) § 63.6645(f)
AVU-146H1	EU	60J-0023	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
AVU-146H1	EU	63DDDDD-001	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
AVU-146H2AB	EU	60Ja-01	Hydrogen Sulfide	40 CFR Part 60, Subpart Ja	§ 60.100a(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 60, Subpart Ja
AVU-146H2AB	EU	63DDDDD-001	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
BERTH-1A	EU	63CC-2502	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.651(a)	Except as provided in §63.651(b)-(d), each owner or operator of a marine tank vessel loading operation located at a petroleum refinery shall comply with the requirements of §63.560	§ 63.642(d)(1) § 63.642(d)(3) § 63.642(d)(4)	§ 63.642(e) § 63.655(c) § 63.655(i)(5)	§ 63.642(d)(2) § 63.642(f) § 63.655(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						through §63.567.			
BERTH-1A	EU	63Y-0041	112(B) HAPS	40 CFR Part 63, Subpart Y	§ 63.562(b) [G]§ 63.562(b)(1) § 63.562(e) § 63.562(e)(1) [G]§ 63.562(e)(2) [G]§ 63.562(e)(3) § 63.562(e)(4) § 63.562(e)(5) § 63.562(e)(6) § 63.562(e)(7) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) § 63.563(a)(2) § 63.563(a)(3)	Marine tank vessel loading operations shall apply MACT standards, except for the VMT source.	[G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) § 63.563(b)(3) [G]§ 63.563(c) § 63.564(a)(2) § 63.564(a)(3) § 63.564(a)(4) § 63.564(a)(5) § 63.564(c) [G]§ 63.565(b) § 63.565(l)	§ 63.562(e)(5) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) § 63.567(f) [G]§ 63.567(g) § 63.567(j)(2) § 63.567(j)(4) [G]§ 63.567(k)	§ 63.562(e)(7)(ii) § 63.564(a)(5) § 63.567(c) § 63.567(e)(1) [G]§ 63.567(e)(2) § 63.567(e)(3) § 63.567(e)(4) § 63.567(e)(5) § 63.567(e)(6) § 63.567(f) § 63.567(j)(3) § 63.567(m) § 63.567(n)(1) § 63.567(n)(2)
BERTH-1B	EU	63CC-2502	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.651(a)	Except as provided in §63.651(b)-(d), each owner or operator of a marine tank vessel loading operation located at a petroleum refinery shall comply with the requirements of §63.560 through §63.567.	§ 63.642(d)(1) § 63.642(d)(3) § 63.642(d)(4)	§ 63.642(e) § 63.655(c) § 63.655(i)(5)	§ 63.642(d)(2) § 63.642(f) § 63.655(c)
BERTH-2A	EU	63CC-2502	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.651(a)	Except as provided in §63.651(b)-(d), each owner or operator of a marine tank vessel loading operation located at a petroleum refinery shall comply with the requirements of §63.560 through §63.567.	§ 63.642(d)(1) § 63.642(d)(3) § 63.642(d)(4)	§ 63.642(e) § 63.655(c) § 63.655(i)(5)	§ 63.642(d)(2) § 63.642(f) § 63.655(c)
BERTH-2A	EU	63Y-0041	112(B) HAPS	40 CFR Part 63, Subpart Y	§ 63.562(b) [G]§ 63.562(b)(1) § 63.562(e) § 63.562(e)(1)	Marine tank vessel loading operations shall apply MACT standards, except for the VMT	[G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) § 63.563(b)(3) [G]§ 63.563(c)	§ 63.562(e)(5) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) § 63.567(f)	§ 63.562(e)(7)(ii) § 63.564(a)(5) § 63.567(c) § 63.567(e)(1)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 63.562(e)(2) [G]§ 63.562(e)(3) § 63.562(e)(4) § 63.562(e)(5) § 63.562(e)(6) § 63.562(e)(7) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) § 63.563(a)(2) § 63.563(a)(3)	source.	§ 63.564(a)(2) § 63.564(a)(3) § 63.564(a)(4) § 63.564(a)(5) § 63.564(c) [G]§ 63.565(b) § 63.565(l)	[G]§ 63.567(g) § 63.567(j)(2) § 63.567(j)(4) [G]§ 63.567(k)	[G]§ 63.567(e)(2) § 63.567(e)(3) § 63.567(e)(4) § 63.567(e)(5) § 63.567(e)(6) § 63.567(f) § 63.567(j)(3) § 63.567(m) § 63.567(n)(1) § 63.567(n)(2)
BERTH-2B	EU	63CC-2502	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.651(a)	Except as provided in §63.651(b)-(d), each owner or operator of a marine tank vessel loading operation located at a petroleum refinery shall comply with the requirements of §63.560 through §63.567.	§ 63.642(d)(1) § 63.642(d)(3) § 63.642(d)(4)	§ 63.642(e) § 63.655(c) § 63.655(i)(5)	§ 63.642(d)(2) § 63.642(f) § 63.655(c)
BERTH-3A	EU	63CC-2502	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.651(a)	Except as provided in §63.651(b)-(d), each owner or operator of a marine tank vessel loading operation located at a petroleum refinery shall comply with the requirements of §63.560 through §63.567.	§ 63.642(d)(1) § 63.642(d)(3) § 63.642(d)(4)	§ 63.642(e) § 63.655(c) § 63.655(i)(5)	§ 63.642(d)(2) § 63.642(f) § 63.655(c)
BERTH-3A	EU	63Y-0041	112(B) HAPS	40 CFR Part 63, Subpart Y	§ 63.562(b) [G]§ 63.562(b)(1) § 63.562(e) § 63.562(e)(1) [G]§ 63.562(e)(2) [G]§ 63.562(e)(3) § 63.562(e)(4) § 63.562(e)(5) § 63.562(e)(6) § 63.562(e)(7)	Marine tank vessel loading operations shall apply MACT standards, except for the VMT source.	[G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) § 63.563(b)(3) [G]§ 63.563(c) § 63.564(a)(2) § 63.564(a)(3) § 63.564(a)(4) § 63.564(a)(5) § 63.564(c) [G]§ 63.565(b)	§ 63.562(e)(5) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) § 63.567(f) [G]§ 63.567(g) § 63.567(j)(2) § 63.567(j)(4) [G]§ 63.567(k)	§ 63.562(e)(7)(ii) § 63.564(a)(5) § 63.567(c) § 63.567(e)(1) [G]§ 63.567(e)(2) § 63.567(e)(3) § 63.567(e)(4) § 63.567(e)(5) § 63.567(e)(6) § 63.567(f)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) § 63.563(a)(2) § 63.563(a)(3)		§ 63.565(l)		§ 63.567(j)(3) § 63.567(m) § 63.567(n)(1) § 63.567(n)(2)
BERTH-3B	EU	63CC-2502	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.651(a)	Except as provided in §63.651(b)-(d), each owner or operator of a marine tank vessel loading operation located at a petroleum refinery shall comply with the requirements of §63.560 through §63.567.	§ 63.642(d)(1) § 63.642(d)(3) § 63.642(d)(4)	§ 63.642(e) § 63.655(c) § 63.655(i)(5)	§ 63.642(d)(2) § 63.642(f) § 63.655(c)
BERTH-5	EU	63CC-2502	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.651(a)	Except as provided in §63.651(b)-(d), each owner or operator of a marine tank vessel loading operation located at a petroleum refinery shall comply with the requirements of §63.560 through §63.567.	§ 63.642(d)(1) § 63.642(d)(3) § 63.642(d)(4)	§ 63.642(e) § 63.655(c) § 63.655(i)(5)	§ 63.642(d)(2) § 63.642(f) § 63.655(c)
BERTH-6	EU	63CC-2502	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.651(a)	Except as provided in §63.651(b)-(d), each owner or operator of a marine tank vessel loading operation located at a petroleum refinery shall comply with the requirements of §63.560 through §63.567.	§ 63.642(d)(1) § 63.642(d)(3) § 63.642(d)(4)	§ 63.642(e) § 63.655(c) § 63.655(i)(5)	§ 63.642(d)(2) § 63.642(f) § 63.655(c)
BH15-41	EU	R7117-001	CO	30 TAC Chapter 117, Subchapter B	§ 117.110(c)(1) § 117.110(c) § 117.110(c)(1)(A) § 117.110(c)(3)	No person shall allow the discharge into the atmosphere from any boiler subject to NO_x emission specifications in § 117.110(a) CO in	[G]§ 117.135(a)(1) § 117.135(a)(4) § 117.135(b) § 117.135(c) § 117.135(d) § 117.135(f)	§ 117.145(a) § 117.145(f) [G]§ 117.145(f)(2) § 117.145(f)(7) § 117.145(f)(8) § 117.145(f)(9)	§ 117.135(b) § 117.135(g) [G]§ 117.145(b) [G]§ 117.145(c) § 117.145(d) § 117.145(d)(1)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						excess of 400 ppmv at 3.0% oxygen, dry basis, except as provided in § 117.125 or § 117.110(c)(3).	§ 117.135(f)(3) § 117.135(g) § 117.140(a)(2)(A) § 117.140(b)(1) § 117.140(b)(3) § 117.140(d) § 117.140(e) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)	§ 117.8100(a)(5)(C)	§ 117.145(d)(2) § 117.145(d)(3) § 117.145(d)(4) § 117.145(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
BH15-41	EU	R7117-001	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.123(a) § 117.123(b) § 117.123(b)(1) § 117.123(b)(2) § 117.123(b)(3) [G]§ 117.123(g) [G]§ 117.123(h) § 117.123(i) § 117.123(k) § 117.130(c) § 117.130(d) § 117.130(d)(1)	Compliance with the NOx emission specifications §117.110 may be achieved by a source cap limitation. Each equipment category at a source whose individual emission units would otherwise be subject to the NOx emission specifications of §117.105 or §117.110 of	§ 117.123(c) § 117.123(c)(1) § 117.123(c)(1)(A) § 117.123(c)(2) § 117.123(f) [G]§ 117.135(a)(1) § 117.135(a)(3)(B) § 117.135(a)(4) § 117.135(b) § 117.135(c) § 117.135(d) § 117.135(f) § 117.135(f)(2)	§ 117.123(d) § 117.145(a) § 117.145(f) [G]§ 117.145(f)(2) § 117.145(f)(8) § 117.145(f)(9) § 117.8100(a)(5)(C)	§ 117.123(e) § 117.135(b) § 117.135(g) [G]§ 117.145(b) [G]§ 117.145(c) § 117.145(d) § 117.145(d)(1) § 117.145(d)(1)(B) § 117.145(d)(2) § 117.145(d)(3) § 117.145(d)(4) § 117.145(d)(5) § 117.8010

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						this title may be included in the source cap as specified. All emission units not included in the source cap must comply with the requirements of §117.105, §117.110 or §117.115 of this title.	§ 117.135(f)(4) § 117.135(g) § 117.140(a)(2)(A) § 117.140(b)(1) § 117.140(b)(3) § 117.140(c)(1) [G]§ 117.140(c)(3) § 117.140(e) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)		[G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
BH15-41	EU	63DDDDD-001	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
BH15-42	EU	R7117-001	CO	30 TAC Chapter 117, Subchapter B	§ 117.110(c)(1) § 117.110(c) § 117.110(c)(1)(A) § 117.110(c)(3)	No person shall allow the discharge into the atmosphere from any boiler subject to NO_x	[G]§ 117.135(a)(1) § 117.135(a)(4) § 117.135(b) § 117.135(c)	§ 117.145(a) § 117.145(f) [G]§ 117.145(f)(2) § 117.145(f)(7)	§ 117.135(b) § 117.135(g) [G]§ 117.145(b) [G]§ 117.145(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						emission specifications in § 117.110(a) CO in excess of 400 ppmv at 3.0% oxygen, dry basis, except as provided in § 117.125 or § 117.110(c)(3).	§ 117.135(d) § 117.135(f) § 117.135(f)(3) § 117.135(g) § 117.140(a)(2)(A) § 117.140(b)(1) § 117.140(b)(3) § 117.140(d) § 117.140(e) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)	§ 117.145(f)(8) § 117.145(f)(9) § 117.8100(a)(5)(C)	§ 117.145(d) § 117.145(d)(1) § 117.145(d)(2) § 117.145(d)(3) § 117.145(d)(4) § 117.145(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
BH15-42	EU	R7117-001	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.123(a) § 117.123(b) § 117.123(b)(1) § 117.123(b)(2) § 117.123(b)(3) [G]§ 117.123(g) [G]§ 117.123(h) § 117.123(i) § 117.123(k) § 117.130(c) § 117.130(d)	Compliance with the NOx emission specifications §117.110 may be achieved by a source cap limitation. Each equipment category at a source whose individual emission units would otherwise be subject to the NOx emission	§ 117.123(c) § 117.123(c)(1) § 117.123(c)(1)(A) § 117.123(c)(2) § 117.123(f) [G]§ 117.135(a)(1) § 117.135(a)(3)(B) § 117.135(a)(4) § 117.135(b) § 117.135(c) § 117.135(d)	§ 117.123(d) § 117.145(a) § 117.145(f) [G]§ 117.145(f)(2) § 117.145(f)(8) § 117.145(f)(9) § 117.8100(a)(5)(C)	§ 117.123(e) § 117.135(b) § 117.135(g) [G]§ 117.145(b) [G]§ 117.145(c) § 117.145(d) § 117.145(d)(1) § 117.145(d)(1)(B) § 117.145(d)(2) § 117.145(d)(3) § 117.145(d)(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 117.130(d)(1)	specifications of §117.105 or §117.110 of this title may be included in the source cap as specified. All emission units not included in the source cap must comply with the requirements of §117.105, §117.110 or §117.115 of this title.	§ 117.135(f) § 117.135(f)(2) § 117.135(f)(4) § 117.135(g) § 117.140(a)(2)(A) § 117.140(b)(1) § 117.140(b)(3) § 117.140(c)(1) [G]§ 117.140(c)(3) § 117.140(e) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)		§ 117.145(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
BH15-42	EU	63DDDDD-001	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
BH15-43	EU	R7117-001	CO	30 TAC Chapter 117,	§ 117.110(c)(1) § 117.110(c)	No person shall allow the discharge into the	[G]§ 117.135(a)(1) § 117.135(a)(4)	§ 117.145(a) § 117.145(f)	§ 117.135(b) § 117.135(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Subchapter B	§ 117.110(c)(1)(A) § 117.110(c)(3)	atmosphere from any boiler subject to NO_x emission specifications in § 117.110(a) CO in excess of 400 ppmv at 3.0% oxygen, dry basis, except as provided in § 117.125 or § 117.110(c)(3).	§ 117.135(b) § 117.135(c) § 117.135(d) § 117.135(f) § 117.135(f)(3) § 117.135(g) § 117.140(a)(2)(A) § 117.140(b)(1) § 117.140(b)(3) § 117.140(d) § 117.140(e) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)	[G]§ 117.145(f)(2) § 117.145(f)(7) § 117.145(f)(8) § 117.145(f)(9) § 117.8100(a)(5)(C)	[G]§ 117.145(b) [G]§ 117.145(c) § 117.145(d) § 117.145(d)(1) § 117.145(d)(2) § 117.145(d)(3) § 117.145(d)(4) § 117.145(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
BH15-43	EU	R7117-001	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.123(a) § 117.123(b) § 117.123(b)(1) § 117.123(b)(2) § 117.123(b)(3) [G]§ 117.123(g) [G]§ 117.123(h) § 117.123(i) § 117.123(k)	Compliance with the NOx emission specifications §117.110 may be achieved by a source cap limitation. Each equipment category at a source whose individual emission units would	§ 117.123(c) § 117.123(c)(1) § 117.123(c)(1)(A) § 117.123(c)(2) § 117.123(f) [G]§ 117.135(a)(1) § 117.135(a)(3)(B) § 117.135(a)(4) § 117.135(b)	§ 117.123(d) § 117.145(a) § 117.145(f) [G]§ 117.145(f)(2) § 117.145(f)(8) § 117.145(f)(9) § 117.8100(a)(5)(C)	§ 117.123(e) § 117.135(b) § 117.135(g) [G]§ 117.145(b) [G]§ 117.145(c) § 117.145(d) § 117.145(d)(1) § 117.145(d)(1)(B) § 117.145(d)(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 117.130(c) § 117.130(d) § 117.130(d)(1)	otherwise be subject to the NOx emission specifications of §117.105 or §117.110 of this title may be included in the source cap as specified. All emission units not included in the source cap must comply with the requirements of §117.105, §117.110 or §117.115 of this title.	§ 117.135(c) § 117.135(d) § 117.135(f) § 117.135(f)(2) § 117.135(f)(4) § 117.135(g) § 117.140(a)(2)(A) § 117.140(b)(1) § 117.140(b)(3) § 117.140(c)(1) [G]§ 117.140(c)(3) § 117.140(e) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)		§ 117.145(d)(3) § 117.145(d)(4) § 117.145(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
BH15-43	EU	63DDDDD-001	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
CARBON-1	EU	60QQQ -001	VOC	40 CFR Part 60, Subpart QQQ	§ 60.692-5 § 60.692-1(a) § 60.692-5(b) § 60.692-5(d) [G]§ 60.692-5(e) § 60.692-6(a) § 60.692-6(b) § 60.692-7(b)	Standard for closed vent system and control devices.	§ 60.695(a) § 60.695(a)(3) § 60.695(a)(3)(ii) § 60.696(a) [G]§ 60.696(b)	§ 60.695(a)(3) § 60.697(a) § 60.697(d) [G]§ 60.697(e) § 60.697(f)(1) [G]§ 60.697(f)(2) § 60.697(f)(3) § 60.697(f)(3)(i) § 60.697(f)(3)(ii) § 60.697(f)(3)(iii) § 60.697(f)(3)(iv) § 60.697(f)(3)(v) § 60.697(f)(3)(vi) § 60.697(f)(3)(vii) § 60.697(f)(3)(x) § 60.697(f)(3)(x)(B)	§ 60.698(b)(1) § 60.698(d) § 60.698(d)(3) § 60.698(d)(3)(ii) § 60.698(e)
CARBON-1	CD	61FF-001	Benzene	40 CFR Part 61, Subpart FF	§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	For each closed-vent system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 61.349(a)(1)(i) § 61.349(e) § 61.349(f) § 61.354(d) [G]§ 61.355(h)	§ 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3)	None
CARBON-2	EU	60QQQ -001	VOC	40 CFR Part 60, Subpart QQQ	§ 60.692-5 § 60.692-1(a) § 60.692-5(b) § 60.692-5(d) [G]§ 60.692-5(e) § 60.692-6(a) § 60.692-6(b) § 60.692-7(b)	Standard for closed vent system and control devices.	§ 60.695(a) § 60.695(a)(3) § 60.695(a)(3)(ii) § 60.696(a) [G]§ 60.696(b)	§ 60.695(a)(3) § 60.697(a) § 60.697(d) [G]§ 60.697(e) § 60.697(f)(1) [G]§ 60.697(f)(2) § 60.697(f)(3) § 60.697(f)(3)(i) § 60.697(f)(3)(ii) § 60.697(f)(3)(iii) § 60.697(f)(3)(iv)	§ 60.698(b)(1) § 60.698(d) § 60.698(d)(3) § 60.698(d)(3)(ii) § 60.698(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
								§ 60.697(f)(3)(v) § 60.697(f)(3)(vi) § 60.697(f)(3)(vii) § 60.697(f)(3)(x) § 60.697(f)(3)(x)(B)	
CARBON-2	CD	61FF-001	Benzene	40 CFR Part 61, Subpart FF	§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	For each closed-vent system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 61.349(a)(1)(i) § 61.349(e) § 61.349(f) § 61.354(d) [G]§ 61.355(h)	§ 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3)	None
CRU-1344H1	EU	60J-0023	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
CRU-1344H1	EU	63DDDDD-001	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
CRU-1344H2	EU	60J-0023	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions	§ 60.105(a)(4) § 60.105(a)(4)(i)	§ 60.105(a)(4) § 60.105(a)(4)(i)	§ 60.105(e)(3)(ii) § 60.107(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4)(iii)	§ 60.107(f) § 60.107(g)
CRU-1344H2	EU	63DDDDD-001	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
CRU-1344H3	EU	60J-0023	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
CRU-1344H3	EU	63DDDDD-001	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
CSV843	EP	R5131-	VOC	30 TAC Chapter	§ 115.127(a)(2)(A)	A vent gas stream	[G]§ 115.125	§ 115.126	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		1		115, Vent Gas Controls	[G]§ 115.122(a)(4) § 115.127(a)(2)	having a combined weight of volatile organic compounds (VOC) equal to or less than 100 pounds in any continuous 24-hour period is exempt from §115.121(a)(1) of this title.	§ 115.126(2)	§ 115.126(2) § 115.126(4)	
CSV843	EP	R5131-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(B) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream specified in §115.121(a)(1) of this title with a concentration of VOC less than 612 parts per million by volume (ppmv) is exempt from §115.121(a)(1) of this title.	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
DCU-843H1	EU	60J-0024	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
DCU-843H2	EU	60J-0024	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
DCU-843H3	EU	60J-	Hydrogen	40 CFR Part 60,	§ 60.104(a)(1)	No owner or operator	§ 60.105(a)(4)	§ 60.105(a)(4)	§ 60.105(e)(3)(ii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		0024	Sulfide	Subpart J		subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.107(d) § 60.107(f) § 60.107(g)
E-01-147	EU	60J-0023	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
E-01-147	EU	63DDDDD-001	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
E-01-245	EU	60J-0023	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
E-01-245	EU	63DDD	112(B)	40 CFR Part 63,	§ 63.7505	The permit holder shall	The permit holder shall	The permit holder shall	The permit holder shall

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		DD-001	HAPS	Subpart DDDDD	The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
E-01-246	EU	60J-0023	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
E-01-246	EU	63DDD DD-001	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
E-02-147	EU	60J-0023	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
E-02-147	EU	63DDDDD-001	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
E-03-SCOT	EU	60J-0024	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
E-04-SCOT	EU	60J-0023	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
ENG-15PS	EU	63ZZZZ-003	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6602-Table2c.1 § 63.6595(a)(1) § 63.6605(a) § 63.6605(b) § 63.6625(e) § 63.6625(h) § 63.6625(i) § 63.6640(b) § 63.6640(f)(1) [G]§ 63.6640(f)(2)	For each existing emergency stationary CI RICE and black start stationary CI RICE, located at a major source, you must comply with the requirements as specified in Table 2c.1.a-c.	§ 63.6625(f) § 63.6625(i) § 63.6640(a) § 63.6640(a)-Table6.9.a.i § 63.6640(a)-Table6.9.a.ii § 63.6640(b)	§ 63.6625(i) § 63.6655(a) § 63.6655(a)(1) § 63.6655(d) § 63.6655(e) § 63.6655(f) § 63.6660(a) § 63.6660(b) § 63.6660(c)	§ 63.6640(b) § 63.6640(e) § 63.6650(f)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.6640(f)(3)				
ENG-443 NORTH	EU	60IIII-002	CO	40 CFR Part 60, Subpart IIII	§ 60.4205(b) § 60.4202(e)(1) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218 § 94.8(a)(2)	Owners and operators of emergency stationary CI ICE, that are not fire pump engines, with a displacement of greater than or equal to 10 liters per cylinder and less than 30 liters per cylinder and is a 2007 model year and later must comply with a CO emission limit of 5.0 g/KW-hr, as stated in 40 CFR 60.4202(e)-(f) and 40 CFR 94.8(a)(2) and 40 CFR 1042.101.	§ 60.4209(a)	§ 60.4214(b)	[G]§ 60.4214(d)
ENG-443 NORTH	EU	60IIII-002	Total Hydrocarbons/NO_X	40 CFR Part 60, Subpart IIII	§ 60.4205(b) § 60.4202(e)(1) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218 § 94.8(a)(2)	Owners and operators of emergency stationary CI ICE, that are not fire pump engines, with a displacement of greater than or equal to 15 liters per cylinder and less than 20 liters per cylinder and is a 2007 - 2012 model year must comply with a THC+NOx emission limit of 8.7 g/KW-hr, as stated in 40 CFR 60.4202(e)(1) and 40 CFR 94.8(a)(2).	§ 60.4209(a)	§ 60.4214(b)	[G]§ 60.4214(d)
ENG-443 NORTH	EU	60IIII-002	PM	40 CFR Part 60, Subpart IIII	§ 60.4205(b) § 60.4202(e)(1) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c)	Owners and operators of emergency stationary CI ICE, that are not fire pump engines, with a displacement of greater than or equal to 15 liters	§ 60.4209(a)	§ 60.4214(b)	[G]§ 60.4214(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 60.4211(f) § 60.4218 § 94.8(a)(2)	per cylinder and less than 30 liters per cylinder and is a 2007 - 2013 model year must comply with a PM emission limit of 0.50 g/KW-hr, as stated in 40 CFR 60.4202(e)(1), (e)(3) and 40 CFR 94.8(a)(2).			
ENG-443 NORTH	EU	63ZZZZ -006	Exempt	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(b)(1) § 63.6595(c) § 63.6640(f)(1) [G]§ 63.6640(f)(2) § 63.6640(f)(3)	An affected source which meets either of the criteria in paragraphs §63.6590(b)(1)(i)-(ii) of this section does not have to meet the requirements of this subpart and of subpart A of this part except for the initial notification requirements of §63.6645(f).	None	None	§ 63.6645(c) § 63.6645(f)
ENG-443 SOUTH	EU	60IIII-002	CO	40 CFR Part 60, Subpart IIII	§ 60.4205(b) § 60.4202(e)(1) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218 § 94.8(a)(2)	Owners and operators of emergency stationary CI ICE, that are not fire pump engines, with a displacement of greater than or equal to 10 liters per cylinder and less than 30 liters per cylinder and is a 2007 model year and later must comply with a CO emission limit of 5.0 g/KW-hr, as stated in 40 CFR 60.4202(e)-(f) and 40 CFR 94.8(a)(2) and 40 CFR 1042.101.	§ 60.4209(a)	§ 60.4214(b)	[G]§ 60.4214(d)
ENG-443	EU	60IIII-	Total	40 CFR Part 60,	§ 60.4205(b)	Owners and operators of	§ 60.4209(a)	§ 60.4214(b)	[G]§ 60.4214(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
SOUTH		002	Hydrocarbons/NO_X	Subpart IIII	§ 60.4202(e)(1) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218 § 94.8(a)(2)	emergency stationary CI ICE, that are not fire pump engines, with a displacement of greater than or equal to 15 liters per cylinder and less than 20 liters per cylinder and is a 2007 - 2012 model year must comply with a THC+NOx emission limit of 8.7 g/KW-hr, as stated in 40 CFR 60.4202(e)(1) and 40 CFR 94.8(a)(2).			
ENG-443 SOUTH	EU	60IIII-002	PM	40 CFR Part 60, Subpart IIII	§ 60.4205(b) § 60.4202(e)(1) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218 § 94.8(a)(2)	Owners and operators of emergency stationary CI ICE, that are not fire pump engines, with a displacement of greater than or equal to 15 liters per cylinder and less than 30 liters per cylinder and is a 2007 - 2013 model year must comply with a PM emission limit of 0.50 g/KW-hr, as stated in 40 CFR 60.4202(e)(1), (e)(3) and 40 CFR 94.8(a)(2).	§ 60.4209(a)	§ 60.4214(b)	[G]§ 60.4214(d)
ENG-443 SOUTH	EU	63ZZZZ-006	Exempt	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(b)(1) § 63.6595(c) § 63.6640(f)(1) [G]§ 63.6640(f)(2) § 63.6640(f)(3)	An affected source which meets either of the criteria in paragraphs §63.6590(b)(1)(i)-(ii) of this section does not have to meet the requirements of this subpart and of subpart A of this part except for the	None	None	§ 63.6645(c) § 63.6645(f)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						initial notification requirements of §63.6645(f).			
ENG-70AC2	EU	63ZZZZ-004	Exempt	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(b)(1) § 63.6595(c) § 63.6640(f)(1) [G]§ 63.6640(f)(2) § 63.6640(f)(3)	An affected source which meets either of the criteria in paragraphs §63.6590(b)(1)(i)-(ii) of this section does not have to meet the requirements of this subpart and of subpart A of this part except for the initial notification requirements of §63.6645(f).	None	None	§ 63.6645(c) § 63.6645(f)
ENG-70AC3	EU	63ZZZZ-004	Exempt	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(b)(1) § 63.6595(c) § 63.6640(f)(1) [G]§ 63.6640(f)(2) § 63.6640(f)(3)	An affected source which meets either of the criteria in paragraphs §63.6590(b)(1)(i)-(ii) of this section does not have to meet the requirements of this subpart and of subpart A of this part except for the initial notification requirements of §63.6645(f).	None	None	§ 63.6645(c) § 63.6645(f)
ENG-843NORTH	EU	60IIII-004	NO_X	40 CFR Part 60, Subpart IIII	§ 60.4205(a)-Table 1 § 60.4206 § 60.4207(b) § 60.4211(b) § 60.4211(b)(1) [G]§ 60.4211(f) § 60.4218	Owners and operators of emergency stationary CI ICE, that are not fire pump engines, with a maximum engine power greater than or equal to 37 KW and a displacement of less than 10 liters per cylinder and is a pre-2007 model year must comply with a	§ 60.4209(a)	§ 60.4214(b)	[G]§ 60.4214(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						NOx emission limit of 9.2 g/KW-hr, as listed in Table 1 to this subpart.			
ENG-843NORTH	EU	63ZZZZ-007	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(c)	Stationary RICE subject to Regulations under 40 CFR Part 60. An affected source that meets any of the criteria in paragraphs (c)(1) through (7) of this section must meet the requirements of this part by meeting the requirements of 40 CFR part 60 subpart IIII, for compression ignition engines or 40 CFR part 60 subpart JJJJ, for spark ignition engines as applicable. No further requirements apply for such engines under this part.	None	None	None
ENG-843SOUTH	EU	60IIII-006	CO	40 CFR Part 60, Subpart IIII	§ 60.4205(b) § 60.4202(a)(2) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218 § 89.112(a)	Owners and operators of emergency stationary CI ICE, that are not fire pump engines, with a maximum engine power greater than or equal to 37 KW and less than 130 KW and a displacement of less than 10 liters per cylinder and is a 2007 model year and later must comply with a CO emission limit of 5.0 g/KW-hr, as stated in 40 CFR 60.4202(a)(2) and 40 CFR 89.112(a).	§ 60.4209(a)	§ 60.4214(b)	[G]§ 60.4214(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
ENG-843SOUTH	EU	60IIII-006	PM (Opacity)	40 CFR Part 60, Subpart IIII	§ 60.4205(b) § 60.4202(a)(2) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218 § 89.113(a)(1) § 89.113(a)(2) § 89.113(a)(3)	Emergency stationary CI ICE, that are not fire pump engines, with displacement < 10 lpc and not constant-speed engines, with max engine power < 2237 KW and a 2007 model year and later or max engine power > 2237 KW and a 2011 model year and later, must comply with following opacity emission limits: 20% during acceleration, 15% during lugging, 50% during peaks in either acceleration or lugging modes as stated in §60.4202(a)(1)-(2), (b)(2) and §89.113(a)(1)-(3) and §1039.105(b)(1)-(3).	§ 60.4209(a)	§ 60.4214(b)	[G]§ 60.4214(d)
ENG-843SOUTH	EU	60IIII-006	PM	40 CFR Part 60, Subpart IIII	§ 60.4205(b) § 60.4202(a)(2) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218 § 89.112(a)	Owners and operators of emergency stationary CI ICE, that are not fire pump engines, with a maximum engine power greater than or equal to 37 KW and less than 75 KW and a displacement of less than 10 liters per cylinder and is a 2007 model year and later must comply with a PM emission limit of 0.40 g/KW-hr, as stated in 40 CFR 60.4202(a)(2) and 40 CFR 89.112(a).	§ 60.4209(a)	§ 60.4214(b)	[G]§ 60.4214(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
ENG-843SOUTH	EU	63ZZZZ-007	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(c)	Stationary RICE subject to Regulations under 40 CFR Part 60. An affected source that meets any of the criteria in paragraphs (c)(1) through (7) of this section must meet the requirements of this part by meeting the requirements of 40 CFR part 60 subpart IIII, for compression ignition engines or 40 CFR part 60 subpart JJJJ, for spark ignition engines as applicable. No further requirements apply for such engines under this part.	None	None	None
F-1747	EU	60GGGa-ALL	VOC	40 CFR Part 60, Subpart GGGa	[G]§ 60.590a(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 60, Subpart GGGa
F-432CT	EU	63CC-3000	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.654(a) § 63.640(h)(6)	Except as specified in paragraph (b) of this section, the owner or operator of a heat exchange system that meets the criteria in §63.640(c)(8) must comply with the requirements of	§ 63.642(d)(1) § 63.642(d)(3) § 63.642(d)(4) [G]§ 63.654(c) [G]§ 63.654(d) § 63.654(e) [G]§ 63.654(f) [G]§ 63.654(g)	§ 63.642(e) § 63.655(h)(1) [G]§ 63.655(i)(4) § 63.655(i)(5)	§ 63.642(d)(2) § 63.642(f) § 63.655(f) § 63.655(f)(1)(vi) § 63.655(f)(4) § 63.655(g) [G]§ 63.655(g)(9) § 63.655(h)(1)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						paragraphs (c) through (g) of this section.			
F-446CT	EU	63CC-3000	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.654(a) § 63.640(h)(6)	Except as specified in paragraph (b) of this section, the owner or operator of a heat exchange system that meets the criteria in §63.640(c)(8) must comply with the requirements of paragraphs (c) through (g) of this section.	§ 63.642(d)(1) § 63.642(d)(3) § 63.642(d)(4) [G]§ 63.654(c) [G]§ 63.654(d) § 63.654(e) [G]§ 63.654(f) [G]§ 63.654(g)	§ 63.642(e) § 63.655(h)(1) [G]§ 63.655(i)(4) § 63.655(i)(5)	§ 63.642(d)(2) § 63.642(f) § 63.655(f) § 63.655(f)(1)(vi) § 63.655(f)(4) § 63.655(g) [G]§ 63.655(g)(9) § 63.655(h)(1)
F-544	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(6)	Components at a petroleum refinery or synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process, that contact a process fluid that contains less than 10% VOC by weight and components at a natural gas/gasoline processing operation that contact a process fluid that contains less than 1.0% VOC by weight are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
F-544	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(5)	Reciprocating compressors and positive displacement pumps used in natural gas/gasoline processing	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						operations are exempt from the requirements of this division except §115.356(3)(C) of this title.			
F-544	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(10)	Instrumentation systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet 40 CFR §63.169 (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
F-544	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(11)	Sampling connection systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet the requirements of 40 CFR §63.166(a) and (b) (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
F-544	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(13)	Components/systems that contact a process fluid containing VOC having a true vapor pressure equal to or less than 0.002 psia at 68 degrees Fahrenheit are exempt from the requirements of this division except §115.356(3)(C) of this	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						title.			
F-544	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(2) § 115.352(9)	Each pressure relief valve equipped with a rupture disk must comply with §115.352(9) and §115.356(3)(C).	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
F-544	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.353(a) § 115.353(b) § 115.910	For all affected persons in the Beaumont-Port Arthur, Dallas-Fort Worth, El Paso, and Houston-Galveston areas, as defined in §115.10, any alternate methods of demonstrating and documenting continuous compliance with the applicable control requirements or exemption criteria in this division may be approved by the executive director in accordance with §115.910 if emission reductions are demonstrated to be substantially equivalent.	None	None	None
F-544	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(C) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii)	No component shall be allowed to have a VOC leak, for more than 15 days, after discovery. If the owner or operator elects to use the alternative work practice in §115.358 of this title, any leak detected as defined in §115.358 of	§ 115.354(1) § 115.354(11) § 115.354(13)(A) § 115.354(13)(B) § 115.354(13)(C) § 115.354(13)(D) § 115.354(13)(E) § 115.354(13)(F) § 115.354(4) § 115.354(5)	§ 115.352(7) § 115.354(13)(D) § 115.354(13)(E) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C)	[G]§ 115.358(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.352(8) § 115.357(8) § 115.358(c)(1) [G]§ 115.358(h)	this title, including any leak detected using the alternative work practice on a component that is subject to the requirements of this division but not specifically selected for alternative work practice monitoring.	§ 115.354(9) [G]§ 115.355 § 115.358(c)(2) § 115.358(d) [G]§ 115.358(e) § 115.358(f)	[G]§ 115.356(4) § 115.356(5)	
F-544	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7) § 115.357(1)	No process drains shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
F-544	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7)	No process drains shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(5)	None
F-544	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet.	§ 115.352(1)(A) § 115.352(1)	No pressure relief valves shall be allowed to have	§ 115.354(1) § 115.354(2)	§ 115.352(7) § 115.356	[G]§ 115.354(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Refinery & Petrochemicals	§ 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(9) § 115.357(1) § 115.357(8) § 115.357(9)	a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 § 115.357(1)	[G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	
F-544	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(9) § 115.357(12) § 115.357(8) § 115.357(9)	No pressure relief valves shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
F-544	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1)	No open-ended valves or lines shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.357(8) § 115.357(9)	based on sight, smell, or sound.			
F-544	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8) § 115.357(9)	No open-ended valves or lines shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
F-544	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(8) § 115.357(9)	No valves shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
F-544	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4)	No valves shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B)	[G]§ 115.354(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8) § 115.357(9)	above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.		[G]§ 115.356(3)(C) § 115.356(5)	
F-544	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(8) § 115.357(1) § 115.357(12) § 115.357(8)	No flanges or other connectors shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
F-544	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(8) § 115.357(12) § 115.357(8)	No flanges or other connectors shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
F-544	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2)	No agitators shall be allowed to have a VOC leak, for more than 15 days after discovery	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(7) § 115.357(1) § 115.357(12) § 115.357(8)	which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(9) [G]§ 115.355 § 115.357(1)	[G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	
F-544	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(7) § 115.357(1) § 115.357(12) § 115.357(8)	No agitators shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
F-544	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(7) § 115.357(12) § 115.357(8)	No agitators shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
F-544	EU	R5352-	VOC	30 TAC Chapter	§ 115.352(1)(B)	No compressor seals	[G]§ 115.355	§ 115.352(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		ALL		115, Pet. Refinery & Petrochemicals	§ 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(3) § 115.357(8)	shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.		§ 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	
F-544	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(4) § 115.357(8)	No compressor seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None
F-544	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5)	No compressor seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(7) § 115.357(1) § 115.357(8)	exuding of process fluid based on sight, smell, or sound.			
F-544	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	No compressor seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
F-544	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(4) § 115.357(8)	No pump seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None
F-544	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i)	No pump seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1) § 115.357(8)	parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.			
F-544	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	No pump seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
F-546	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(6)	Components at a petroleum refinery or synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process, that contact a process fluid that contains less than 10% VOC by weight and components at a natural gas/gasoline processing operation that contact a process fluid that contains less than 1.0% VOC by weight are exempt from the requirements of this	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						division except §115.356(3)(C) of this title.			
F-546	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(5)	Reciprocating compressors and positive displacement pumps used in natural gas/gasoline processing operations are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
F-546	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(10)	Instrumentation systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet 40 CFR §63.169 (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
F-546	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(11)	Sampling connection systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet the requirements of 40 CFR §63.166(a) and (b) (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
F-546	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet.	§ 115.357(13)	Components/systems that contact a process	None	§ 115.356 § 115.356(3)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Refinery & Petrochemicals		fluid containing VOC having a true vapor pressure equal to or less than 0.002 psia at 68 degrees Fahrenheit are exempt from the requirements of this division except §115.356(3)(C) of this title.		[G]§ 115.356(3)(C)	
F-546	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(2) § 115.352(9)	Each pressure relief valve equipped with a rupture disk must comply with §115.352(9) and §115.356(3)(C).	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
F-546	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.353(a) § 115.353(b) § 115.910	For all affected persons in the Beaumont-Port Arthur, Dallas-Fort Worth, El Paso, and Houston-Galveston areas, as defined in §115.10, any alternate methods of demonstrating and documenting continuous compliance with the applicable control requirements or exemption criteria in this division may be approved by the executive director in accordance with §115.910 if emission reductions are demonstrated to be substantially equivalent.	None	None	None
F-546	EU	R5352-	VOC	30 TAC Chapter	§ 115.352(1)(C)	No component shall be	§ 115.354(1)	§ 115.352(7)	[G]§ 115.358(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		ALL		115, Pet. Refinery & Petrochemicals	§ 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.352(8) § 115.357(8) § 115.358(c)(1) [G]§ 115.358(h)	allowed to have a VOC leak, for more than 15 days, after discovery. If the owner or operator elects to use the alternative work practice in §115.358 of this title, any leak detected as defined in §115.358 of this title, including any leak detected using the alternative work practice on a component that is subject to the requirements of this division but not specifically selected for alternative work practice monitoring.	§ 115.354(11) § 115.354(13)(A) § 115.354(13)(B) § 115.354(13)(C) § 115.354(13)(D) § 115.354(13)(E) § 115.354(13)(F) § 115.354(4) § 115.354(5) § 115.354(9) [G]§ 115.355 § 115.358(c)(2) § 115.358(d) [G]§ 115.358(e) § 115.358(f)	§ 115.354(13)(D) § 115.354(13)(E) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) [G]§ 115.356(4) § 115.356(5)	
F-546	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7) § 115.357(1)	No process drains shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
F-546	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3)	No process drains shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(7)	greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.		§ 115.356(3)(A) § 115.356(3)(B) § 115.356(5)	
F-546	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(9) § 115.357(1) § 115.357(8) § 115.357(9)	No pressure relief valves shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
F-546	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(9) § 115.357(12) § 115.357(8) § 115.357(9)	No pressure relief valves shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
F-546	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery &	§ 115.352(1)(A) § 115.352(1) § 115.352(10)	No open-ended valves or lines shall be allowed to have a VOC leak, for	§ 115.354(1) § 115.354(2) § 115.354(5)	§ 115.352(7) § 115.356 [G]§ 115.356(1)	[G]§ 115.354(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Petrochemicals	§ 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(8) § 115.357(9)	more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 § 115.357(1)	[G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	
F-546	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8) § 115.357(9)	No open-ended valves or lines shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
F-546	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(8)	No valves shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.357(9)				
F-546	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8) § 115.357(9)	No valves shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
F-546	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(8) § 115.357(1) § 115.357(12) § 115.357(8)	No flanges or other connectors shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
F-546	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(8)	No flanges or other connectors shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.357(12) § 115.357(8)	above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.		§ 115.356(5)	
F-546	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(7) § 115.357(1) § 115.357(12) § 115.357(8)	No agitators shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
F-546	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(7) § 115.357(1) § 115.357(12) § 115.357(8)	No agitators shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
F-546	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A)	No agitators shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(7) § 115.357(12) § 115.357(8)	screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	[G]§ 115.355 § 115.357(1)	§ 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	
F-546	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(3) § 115.357(8)	No compressor seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None
F-546	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(4) § 115.357(8)	No compressor seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None
F-546	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet.	§ 115.352(1)(B) § 115.352(1)	No compressor seals shall be allowed to have	§ 115.354(1) § 115.354(2)	§ 115.352(7) § 115.356	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Refinery & Petrochemicals	§ 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1) § 115.357(8)	a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	[G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	
F-546	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	No compressor seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
F-546	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7)	No pump seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.357(4) § 115.357(8)	based on sight, smell, or sound.			
F-546	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1) § 115.357(8)	No pump seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None
F-546	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	No pump seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
F-7042	EU	60GGGa-ALL	VOC	40 CFR Part 60, Subpart GGGa	[G]§ 60.590a(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40	The permit holder shall comply with the applicable requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 60, Subpart GGGa

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					CFR Part 60, Subpart GGGa				
F-7043	EU	60GGGa-ALL	VOC	40 CFR Part 60, Subpart GGGa	[G]§ 60.590a(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 60, Subpart GGGa
F-7044	EU	60GGGa-ALL	VOC	40 CFR Part 60, Subpart GGGa	[G]§ 60.590a(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 60, Subpart GGGa
F-7843	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(c)(1) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.163 [G]§ 63.171 [G]§ 63.176 § 63.648(f) § 63.655(d)(2)	Comply with the specified Subpart H requirements for pumps in light liquid service, instrument readings that define a leak are specified in Subpart CC, table 2.	[G]§ 63.163 [G]§ 63.176 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(3) § 63.648(c)(4) § 63.648(c)(6) § 63.648(c)(7) § 63.648(c)(8)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(3) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(8) § 63.181(h)(9) § 63.648(h) § 63.655(d)(1)(i) § 63.655(d)(6) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(v)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
F-7843	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for non-reciprocating pumps in heavy liquid service.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(6)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
F-7843	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.164 [G]§ 63.171 § 63.648(i) § 63.655(d)(2)	Comply with the specified Subpart H requirements for compressors which are not in hydrogen service.	[G]§ 63.164 [G]§ 63.180(b) [G]§ 63.180(c) [G]§ 63.180(d) [G]§ 63.648(b)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(f) § 63.648(h) § 63.655(d)(1)(i) § 63.655(d)(6) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
F-7843	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.165 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for pressure relief devices in gas/vapor service.	[G]§ 63.165 [G]§ 63.180(b) [G]§ 63.180(c) [G]§ 63.180(d) [G]§ 63.648(b)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(f) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
F-7843	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for pressure relief device in liquid service.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(6)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
F-7843	EU	63CCH-	112(B)	40 CFR Part 63,	§ 63.648(a)	Comply with the	[G]§ 63.180(b)	§ 63.181(a)	[G]§ 63.182(a)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		ALL	HAPS	Subpart CC	§ 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.166 [G]§ 63.171 § 63.655(d)(2)	specified Subpart H requirements for sampling connection systems.	[G]§ 63.180(d) [G]§ 63.648(b)	[G]§ 63.181(b) § 63.181(c) [G]§ 63.181(i) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
F-7843	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.167 [G]§ 63.171 [G]§ 63.175 § 63.655(d)(2)	Comply with the specified Subpart H requirements for open-ended valves and lines.	[G]§ 63.175 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(9) [G]§ 63.181(i) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
F-7843	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(c)(1) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.168 [G]§ 63.171 [G]§ 63.175 § 63.648(c)(9) § 63.655(d)(2)	Comply with the specified Subpart H requirements for valves in gas/vapor and light liquid service, instrument readings defining a leak are specified in Subpart CC, table 2.	[G]§ 63.168 [G]§ 63.175 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(3) § 63.648(c)(4) § 63.648(c)(8)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(9) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(v)
F-7843	EU	63CCH-	112(B)	40 CFR Part 63,	§ 63.648(a)	Comply with the	[G]§ 63.169	§ 63.181(a)	[G]§ 63.182(a)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		ALL	HAPS	Subpart CC	§ 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.655(d)(2)	specified Subpart H requirements for valves in heavy liquid service.	[G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(6)	[G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
F-7843	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(c)(5) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.649(a) § 63.655(d)(2)	Connectors in gas/vapor or light liquid are subject to the requirements in heavy liquid service in §63.169. The leak definition for specified systems subject to §63.169 is 1,000 parts per million.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(4)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(v)
F-7843	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for connectors in heavy liquid service.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(6)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
F-7843	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for instrumentation systems.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(6)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
F-7843	EU	63CCH-	112(B)	40 CFR Part 63,	§ 63.648(a)	Comply with the	§ 63.172(e)	§ 63.181(a)	[G]§ 63.182(a)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		ALL	HAPS	Subpart CC	§ 63.11(b) § 63.172(d) § 63.172(e) [G]§ 63.172(h) § 63.172(m) § 63.655(d)(2)	specified Subpart H requirements for flares.	[G]§ 63.172(h) [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.180(e)	[G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(g) § 63.181(g)(1)(i) § 63.181(g)(1)(ii) § 63.181(g)(1)(iii) § 63.181(g)(1)(iv) [G]§ 63.181(g)(2) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e) [G]§ 63.655(f)(1)(i)(D)
F-7843	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	[G]§ 63.648(g)	Compressors in hydrogen service are exempt from the requirements of §63.648(a) and (c), if an owner or operator demonstrates that a compressor is in hydrogen service. §63.648(g)(1)-(2).	[G]§ 63.648(g)	§ 63.648(h) § 63.655(d)(3)	None
F-7945	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(c)(1) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.163 [G]§ 63.171 [G]§ 63.176 § 63.648(f) § 63.655(d)(2)	Comply with the specified Subpart H requirements for pumps in light liquid service, instrument readings that define a leak are specified in Subpart CC, table 2.	[G]§ 63.163 [G]§ 63.176 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(3) § 63.648(c)(4) § 63.648(c)(6) § 63.648(c)(7) § 63.648(c)(8)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(3) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(8) § 63.181(h)(9) § 63.648(h) § 63.655(d)(1)(i) § 63.655(d)(6) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(v)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
F-7945	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for non-reciprocating pumps in heavy liquid service.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(6)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
F-7945	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.164 [G]§ 63.171 § 63.648(i) § 63.655(d)(2)	Comply with the specified Subpart H requirements for compressors which are not in hydrogen service.	[G]§ 63.164 [G]§ 63.180(b) [G]§ 63.180(c) [G]§ 63.180(d) [G]§ 63.648(b)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(f) § 63.648(h) § 63.655(d)(1)(i) § 63.655(d)(6) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
F-7945	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.165 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for pressure relief devices in gas/vapor service.	[G]§ 63.165 [G]§ 63.180(b) [G]§ 63.180(c) [G]§ 63.180(d) [G]§ 63.648(b)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(f) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
F-7945	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for pressure relief device in liquid service.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(6)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
F-7945	EU	63CCH-	112(B)	40 CFR Part 63,	§ 63.648(a)	Comply with the	[G]§ 63.180(b)	§ 63.181(a)	[G]§ 63.182(a)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		ALL	HAPS	Subpart CC	§ 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.166 [G]§ 63.171 § 63.655(d)(2)	specified Subpart H requirements for sampling connection systems.	[G]§ 63.180(d) [G]§ 63.648(b)	[G]§ 63.181(b) § 63.181(c) [G]§ 63.181(i) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
F-7945	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.167 [G]§ 63.171 [G]§ 63.175 § 63.655(d)(2)	Comply with the specified Subpart H requirements for open-ended valves and lines.	[G]§ 63.175 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(9) [G]§ 63.181(i) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
F-7945	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(c)(1) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.168 [G]§ 63.171 [G]§ 63.175 § 63.648(c)(9) § 63.655(d)(2)	Comply with the specified Subpart H requirements for valves in gas/vapor and light liquid service, instrument readings defining a leak are specified in Subpart CC, table 2.	[G]§ 63.168 [G]§ 63.175 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(3) § 63.648(c)(4) § 63.648(c)(8)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(9) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(v)
F-7945	EU	63CCH-	112(B)	40 CFR Part 63,	§ 63.648(a)	Comply with the	[G]§ 63.169	§ 63.181(a)	[G]§ 63.182(a)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		ALL	HAPS	Subpart CC	§ 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.655(d)(2)	specified Subpart H requirements for valves in heavy liquid service.	[G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(6)	[G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
F-7945	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(c)(5) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.649(a) § 63.655(d)(2)	Connectors in gas/vapor or light liquid are subject to the requirements in heavy liquid service in §63.169. The leak definition for specified systems subject to §63.169 is 1,000 parts per million.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(4)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(v)
F-7945	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for connectors in heavy liquid service.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(6)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
F-7945	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for instrumentation systems.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(6)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
F-7945	EU	63CCH-	112(B)	40 CFR Part 63,	§ 63.648(a)	Comply with the	§ 63.172(e)	§ 63.181(a)	[G]§ 63.182(a)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		ALL	HAPS	Subpart CC	§ 63.11(b) § 63.172(d) § 63.172(e) [G]§ 63.172(h) § 63.172(m) § 63.655(d)(2)	specified Subpart H requirements for flares.	[G]§ 63.172(h) [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.180(e)	[G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(g) § 63.181(g)(1)(i) § 63.181(g)(1)(ii) § 63.181(g)(1)(iii) § 63.181(g)(1)(iv) [G]§ 63.181(g)(2) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e) [G]§ 63.655(f)(1)(i)(D)
F-7945	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	[G]§ 63.648(g)	Compressors in hydrogen service are exempt from the requirements of §63.648(a) and (c), if an owner or operator demonstrates that a compressor is in hydrogen service. §63.648(g)(1)-(2).	[G]§ 63.648(g)	§ 63.648(h) § 63.655(d)(3)	None
F-8748-SWS	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(c)(1) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.163 [G]§ 63.171 [G]§ 63.176 § 63.648(f) § 63.655(d)(2)	Comply with the specified Subpart H requirements for pumps in light liquid service, instrument readings that define a leak are specified in Subpart CC, table 2.	[G]§ 63.163 [G]§ 63.176 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(3) § 63.648(c)(4) § 63.648(c)(6) § 63.648(c)(7) § 63.648(c)(8)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(3) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(8) § 63.181(h)(9) § 63.648(h) § 63.655(d)(1)(i) § 63.655(d)(6) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(v)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
F-8748-SWS	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for non-reciprocating pumps in heavy liquid service.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(6)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
F-8748-SWS	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.164 [G]§ 63.171 § 63.648(i) § 63.655(d)(2)	Comply with the specified Subpart H requirements for compressors which are not in hydrogen service.	[G]§ 63.164 [G]§ 63.180(b) [G]§ 63.180(c) [G]§ 63.180(d) [G]§ 63.648(b)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(f) § 63.648(h) § 63.655(d)(1)(i) § 63.655(d)(6) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
F-8748-SWS	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.165 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for pressure relief devices in gas/vapor service.	[G]§ 63.165 [G]§ 63.180(b) [G]§ 63.180(c) [G]§ 63.180(d) [G]§ 63.648(b)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(f) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
F-8748-SWS	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for pressure relief device in liquid service.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(6)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
F-8748-SWS	EU	63CCH-	112(B)	40 CFR Part 63,	§ 63.648(a)	Comply with the	[G]§ 63.180(b)	§ 63.181(a)	[G]§ 63.182(a)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		ALL	HAPS	Subpart CC	§ 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.166 [G]§ 63.171 § 63.655(d)(2)	specified Subpart H requirements for sampling connection systems.	[G]§ 63.180(d) [G]§ 63.648(b)	[G]§ 63.181(b) § 63.181(c) [G]§ 63.181(i) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
F-8748-SWS	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.167 [G]§ 63.171 [G]§ 63.175 § 63.655(d)(2)	Comply with the specified Subpart H requirements for open-ended valves and lines.	[G]§ 63.175 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(9) [G]§ 63.181(i) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
F-8748-SWS	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(c)(1) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.168 [G]§ 63.171 [G]§ 63.175 § 63.648(c)(9) § 63.655(d)(2)	Comply with the specified Subpart H requirements for valves in gas/vapor and light liquid service, instrument readings defining a leak are specified in Subpart CC, table 2.	[G]§ 63.168 [G]§ 63.175 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(3) § 63.648(c)(4) § 63.648(c)(8)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(9) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(v)
F-8748-SWS	EU	63CCH-	112(B)	40 CFR Part 63,	§ 63.648(a)	Comply with the	[G]§ 63.169	§ 63.181(a)	[G]§ 63.182(a)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		ALL	HAPS	Subpart CC	§ 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.655(d)(2)	specified Subpart H requirements for valves in heavy liquid service.	[G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(6)	[G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
F-8748-SWS	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(c)(5) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.649(a) § 63.655(d)(2)	Connectors in gas/vapor or light liquid are subject to the requirements in heavy liquid service in §63.169. The leak definition for specified systems subject to §63.169 is 1,000 parts per million.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(4)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(v)
F-8748-SWS	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for connectors in heavy liquid service.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(6)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
F-8748-SWS	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for instrumentation systems.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(6)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
F-8748-SWS	EU	63CCH-	112(B)	40 CFR Part 63,	§ 63.648(a)	Comply with the	§ 63.172(e)	§ 63.181(a)	[G]§ 63.182(a)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		ALL	HAPS	Subpart CC	§ 63.11(b) § 63.172(d) § 63.172(e) [G]§ 63.172(h) § 63.172(m) § 63.655(d)(2)	specified Subpart H requirements for flares.	[G]§ 63.172(h) [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.180(e)	[G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(g) § 63.181(g)(1)(i) § 63.181(g)(1)(ii) § 63.181(g)(1)(iii) § 63.181(g)(1)(iv) [G]§ 63.181(g)(2) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e) [G]§ 63.655(f)(1)(i)(D)
F-8748-SWS	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	[G]§ 63.648(g)	Compressors in hydrogen service are exempt from the requirements of §63.648(a) and (c), if an owner or operator demonstrates that a compressor is in hydrogen service. §63.648(g)(1)-(2).	[G]§ 63.648(g)	§ 63.648(h) § 63.655(d)(3)	None
F-943	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(c)(1) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.163 [G]§ 63.171 [G]§ 63.176 § 63.648(f) § 63.655(d)(2)	Comply with the specified Subpart H requirements for pumps in light liquid service, instrument readings that define a leak are specified in Subpart CC, table 2.	[G]§ 63.163 [G]§ 63.176 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(3) § 63.648(c)(4) § 63.648(c)(6) § 63.648(c)(7) § 63.648(c)(8)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(3) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(8) § 63.181(h)(9) § 63.648(h) § 63.655(d)(1)(i) § 63.655(d)(6) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(v)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
F-943	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for non-reciprocating pumps in heavy liquid service.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(6)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
F-943	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.164 [G]§ 63.171 § 63.648(i) § 63.655(d)(2)	Comply with the specified Subpart H requirements for compressors which are not in hydrogen service.	[G]§ 63.164 [G]§ 63.180(b) [G]§ 63.180(c) [G]§ 63.180(d) [G]§ 63.648(b)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(f) § 63.648(h) § 63.655(d)(1)(i) § 63.655(d)(6) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
F-943	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.165 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for pressure relief devices in gas/vapor service.	[G]§ 63.165 [G]§ 63.180(b) [G]§ 63.180(c) [G]§ 63.180(d) [G]§ 63.648(b)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(f) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
F-943	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for pressure relief device in liquid service.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(6)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
F-943	EU	63CCH-	112(B)	40 CFR Part 63,	§ 63.648(a)	Comply with the	[G]§ 63.180(b)	§ 63.181(a)	[G]§ 63.182(a)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		ALL	HAPS	Subpart CC	§ 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.166 [G]§ 63.171 § 63.655(d)(2)	specified Subpart H requirements for sampling connection systems.	[G]§ 63.180(d) [G]§ 63.648(b)	[G]§ 63.181(b) § 63.181(c) [G]§ 63.181(i) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
F-943	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.167 [G]§ 63.171 [G]§ 63.175 § 63.655(d)(2)	Comply with the specified Subpart H requirements for open-ended valves and lines.	[G]§ 63.175 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(9) [G]§ 63.181(i) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
F-943	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(c)(1) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.168 [G]§ 63.171 [G]§ 63.175 § 63.648(c)(9) § 63.655(d)(2)	Comply with the specified Subpart H requirements for valves in gas/vapor and light liquid service, instrument readings defining a leak are specified in Subpart CC, table 2.	[G]§ 63.168 [G]§ 63.175 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(3) § 63.648(c)(4) § 63.648(c)(8)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(9) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(v)
F-943	EU	63CCH-	112(B)	40 CFR Part 63,	§ 63.648(a)	Comply with the	[G]§ 63.169	§ 63.181(a)	[G]§ 63.182(a)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		ALL	HAPS	Subpart CC	§ 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.655(d)(2)	specified Subpart H requirements for valves in heavy liquid service.	[G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(6)	[G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
F-943	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(c)(5) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.649(a) § 63.655(d)(2)	Connectors in gas/vapor or light liquid are subject to the requirements in heavy liquid service in §63.169. The leak definition for specified systems subject to §63.169 is 1,000 parts per million.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(4)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(v)
F-943	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for connectors in heavy liquid service.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(6)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
F-943	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for instrumentation systems.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(6)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
F-943	EU	63CCH-	112(B)	40 CFR Part 63,	§ 63.648(a)	Comply with the	§ 63.172(e)	§ 63.181(a)	[G]§ 63.182(a)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		ALL	HAPS	Subpart CC	§ 63.11(b) § 63.172(d) § 63.172(e) [G]§ 63.172(h) § 63.172(m) § 63.655(d)(2)	specified Subpart H requirements for flares.	[G]§ 63.172(h) [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.180(e)	[G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(g) § 63.181(g)(1)(i) § 63.181(g)(1)(ii) § 63.181(g)(1)(iii) § 63.181(g)(1)(iv) [G]§ 63.181(g)(2) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e) [G]§ 63.655(f)(1)(i)(D)
F-943	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	[G]§ 63.648(g)	Compressors in hydrogen service are exempt from the requirements of §63.648(a) and (c), if an owner or operator demonstrates that a compressor is in hydrogen service. §63.648(g)(1)-(2).	[G]§ 63.648(g)	§ 63.648(h) § 63.655(d)(3)	None
FCC-1241H1	EU	R117-005	Exempt	30 TAC Chapter 117, Subchapter B	§ 117.103(b)(2) § 117.103(c)	Units exempted from §117.105 of this title include any low annual capacity factor boiler, process heater, stationary gas turbine, or stationary internal combustion engine as defined in §117.10 of this title (relating to Definitions).	None	§ 117.145(f)(6) § 117.145(f)(6)(A)	[G]§ 117.140(m)
FCC-1241H2	EU	R117-005	Exempt	30 TAC Chapter 117, Subchapter B	§ 117.103(b)(2) § 117.103(c)	Units exempted from §117.105 of this title include any low annual capacity factor boiler, process heater,	None	§ 117.145(f)(6) § 117.145(f)(6)(A)	[G]§ 117.140(m)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						stationary gas turbine, or stationary internal combustion engine as defined in §117.10 of this title (relating to Definitions).			
FCCU-1241	EU	60J-0011	SO_2	40 CFR Part 60, Subpart J	§ 60.104(b)(1) § 60.104(c) § 60.104(d)	For each affected fluid catalytic cracking unit catalyst regenerator with an add-on control device, reduce sulfur dioxide emissions to the atmosphere by 90 percent or maintain sulfur dioxide emissions to the atmosphere less than or equal to 50 ppm by volume, whichever is less stringent.	§ 60.105(a)(10) § 60.105(a)(11) [G]§ 60.105(a)(12) [G]§ 60.105(a)(13) [G]§ 60.105(a)(8) [G]§ 60.105(a)(9) § 60.106(a) § 60.106(g) [G]§ 60.106(h) [G]§ 60.106(k) § 60.108(a) § 60.108(c) § 60.108(d) § 60.108(e)	§ 60.105(a)(10) § 60.105(a)(11) [G]§ 60.105(a)(12) [G]§ 60.105(a)(13) [G]§ 60.105(a)(8) [G]§ 60.105(a)(9) [G]§ 60.107(b)(1) § 60.107(b)(4)	§ 60.107(a) § 60.107(c) [G]§ 60.107(c)(1) § 60.107(c)(2) [G]§ 60.107(c)(3) [G]§ 60.107(c)(4) § 60.107(d) § 60.107(f) § 60.107(g) § 60.108(e)
FCCU-1241	EU	60J-0011	CO	40 CFR Part 60, Subpart J	§ 60.103(a) § 60.105(a)(2)	No owner or operator shall discharge or cause the discharge into the atmosphere from any fluid catalytic cracking unit catalyst regenerator any gases that contain carbon monoxide (CO) in excess of 500 ppm by volume (dry basis).	§ 60.105(a)(2) § 60.105(a)(2)(i) § 60.106(a) § 60.106(d)	§ 60.105(a)(2) § 60.105(c)	§ 60.105(e)(2) § 60.107(f) § 60.107(g)
FCCU-1241	EU	60J-0011	PM	40 CFR Part 60, Subpart J	§ 60.102(a)(1)	No owner or operator subject to the provisions of this subpart shall discharge or cause the discharge into the atmosphere from any fluid catalytic cracking unit catalyst regenerator	§ 60.106(a) § 60.106(b) § 60.106(b)(1) § 60.106(b)(2) [G]§ 60.106(b)(3)	§ 60.105(c)	§ 60.107(f) § 60.107(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						particulate matter in excess of 1.0 kg/Mg (2.0 lb/ton) of coke burn-off in the catalyst regenerator.			
FCCU-1241	EU	60J-0011	PM (Opacity)	40 CFR Part 60, Subpart J	§ 60.102(a)(2)	No owner or operator subject to the provisions of this subpart shall discharge or cause the discharge into the atmosphere from any fluid catalytic cracking unit catalyst regenerator gases exhibiting greater than 30 percent opacity, except for one six-minute average opacity reading in any one hour period.	§ 60.105(a)(1) § 60.106(a) § 60.106(b) § 60.106(b)(4) ** See Alternative Requirement	§ 60.105(a)(1) § 60.105(c)	§ 60.105(e)(1) § 60.107(f) § 60.107(g)
FCCU-1241	EU	63UUU-1000	CO	40 CFR Part 63, Subpart UUU	§ 63.1565(a)(1)-Table8.1 § 63.1565(a)(1) § 63.1565(a)(2) § 63.1565(a)(2)-Table9.1 § 63.1565(a)(3) § 63.1565(a)(4) § 63.1565(b)(3) § 63.1565(b)(4) § 63.1565(b)(4)-Table12.1 § 63.1565(c)(1) § 63.1565(c)(2) § 63.1570(a) § 63.1570(c) § 63.1570(d) § 63.1570(g) [G]§ 63.1571(e)	For each new and existing CCU subject to the NSPS for CO in 40 CFR §60.103 or electing to comply with the NSPS requirements (Option 1), CO emissions from the catalyst regenerator vent or CO boiler serving the CCU must not exceed 500 parts per million volume (ppmv) (dry basis).	§ 63.1565(b)(1) § 63.1565(b)(1)-Table10.1 § 63.1565(c)(1)-Table13.1 § 63.1565(c)(1)-Table14.1 [G]§ 63.1571(b) § 63.1572(a) § 63.1572(a)(1) § 63.1572(a)(1)-Table40.2 § 63.1572(a)(2) § 63.1572(a)(3) § 63.1572(a)(4) [G]§ 63.1572(d) [G]§ 63.1573(a)(2)	§ 63.1565(b)(1)-Table10.1 § 63.1570(c) [G]§ 63.1576(a) [G]§ 63.1576(b) § 63.1576(d) § 63.1576(e) § 63.1576(f) § 63.1576(g) § 63.1576(h) § 63.1576(i)	§ 63.1565(b)(5) § 63.1565(b)(6) § 63.1570(f) § 63.1571(a) [G]§ 63.1574(a) § 63.1574(d) § 63.1574(d)-Table42.1 § 63.1574(d)-Table42.2 § 63.1574(d)-Table42.3 § 63.1575(a) § 63.1575(a)-Table43.1 [G]§ 63.1575(b) [G]§ 63.1575(c) [G]§ 63.1575(e) [G]§ 63.1575(f) § 63.1575(g) [G]§ 63.1575(h) [G]§ 63.1575(i)
FCCU-1241	EU	63UUU-1000	PM	40 CFR Part 63, Subpart UUU	§ 63.1564(a)(1)-Table1.1	For each new or existing CCU subject to NSPS for	§ 63.1564(c)(1)-Table6.1.a.i	§ 63.1564(c)(2) § 63.1570(c)	§ 63.1564(b)(6) § 63.1564(b)(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.1564(a)(1) § 63.1564(a)(3) § 63.1564(a)(4) § 63.1564(b)(5) § 63.1564(b)(5)-Table5.1 § 63.1570(a) § 63.1570(c) § 63.1570(d) § 63.1570(g) [G]§ 63.1573(f)(1) § 63.1573(f)(2)	PM in 40 CFR §60.102, PM emissions must not exceed 1.0 kg/1,000 kg (1.0 lb/1,000 lbs) of coke burn-off in the catalyst regenerator and, if applicable, the incremental rate of PM emissions must not exceed 43.0 g/GJ (0.10 lb/MMBtu) of heat input attributable to auxiliary or supplemental fired liquid or solid fossil fuel.	[G]§ 63.1572(d)	[G]§ 63.1576(a) § 63.1576(d) § 63.1576(e) § 63.1576(f) § 63.1576(g) § 63.1576(h) § 63.1576(i)	§ 63.1570(f) § 63.1573(f)(3) [G]§ 63.1574(a) § 63.1574(d) § 63.1574(d)-Table42.1 § 63.1574(d)-Table42.2 § 63.1574(d)-Table42.3 § 63.1575(a) § 63.1575(a)-Table43.1 [G]§ 63.1575(b) [G]§ 63.1575(c) [G]§ 63.1575(d) [G]§ 63.1575(f) § 63.1575(g) [G]§ 63.1575(h) [G]§ 63.1575(i)
FCCU-1241	EU	63UUU-1000	PM (Opacity)	40 CFR Part 63, Subpart UUU	§ 63.1564(a)(1)-Table1.1 § 63.1564(a)(1) § 63.1564(a)(3) § 63.1564(a)(4) § 63.1564(b)(5) § 63.1564(b)(5)-Table5.1 § 63.1570(b) § 63.1570(c) § 63.1570(d) § 63.1570(g) [G]§ 63.1573(f)(1) § 63.1573(f)(2)	For each new or existing CCU subject to NSPS for PM in 40 CFR §60.102, opacity of emissions must not exceed 30%, except for one 6-minute average opacity reading in any 1-hour period.	§ 63.1564(c)(1)-Table6.1.a.i [G]§ 63.1572(d) ** See Alternative Requirement	§ 63.1564(c)(2) § 63.1570(c) [G]§ 63.1576(a) [G]§ 63.1576(b) § 63.1576(d) § 63.1576(e) § 63.1576(f) § 63.1576(g) § 63.1576(h) § 63.1576(i)	§ 63.1564(b)(6) § 63.1564(b)(7) § 63.1570(f) § 63.1573(f)(3) [G]§ 63.1574(a) § 63.1574(d) § 63.1574(d)-Table42.1 § 63.1574(d)-Table42.2 § 63.1574(d)-Table42.3 § 63.1575(a) § 63.1575(a)-Table43.1 [G]§ 63.1575(b) [G]§ 63.1575(c) [G]§ 63.1575(d) [G]§ 63.1575(f) § 63.1575(g) [G]§ 63.1575(h) [G]§ 63.1575(i)
F-DOCKS	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(6)	Components at a petroleum refinery or synthetic organic chemical, polymer, resin,	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						or methyl-tert-butyl ether manufacturing process, that contact a process fluid that contains less than 10% VOC by weight and components at a natural gas/gasoline processing operation that contact a process fluid that contains less than 1.0% VOC by weight are exempt from the requirements of this division except §115.356(3)(C) of this title.			
F-DOCKS	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(5)	Reciprocating compressors and positive displacement pumps used in natural gas/gasoline processing operations are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
F-DOCKS	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(10)	Instrumentation systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet 40 CFR §63.169 (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
F-DOCKS	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet.	§ 115.357(11)	Sampling connection systems, as defined in	None	§ 115.356 § 115.356(3)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Refinery & Petrochemicals		40 CFR §63.161 (January 17, 1997), that meet the requirements of 40 CFR §63.166(a) and (b) (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.		[G]§ 115.356(3)(C)	
F-DOCKS	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(13)	Components/systems that contact a process fluid containing VOC having a true vapor pressure equal to or less than 0.002 psia at 68 degrees Fahrenheit are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
F-DOCKS	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(2) § 115.352(9)	Each pressure relief valve equipped with a rupture disk must comply with §115.352(9) and §115.356(3)(C).	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
F-DOCKS	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.353(a) § 115.353(b) § 115.910	For all affected persons in the Beaumont-Port Arthur, Dallas-Fort Worth, El Paso, and Houston-Galveston areas, as defined in §115.10, any alternate methods of demonstrating and documenting continuous compliance with the	None	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						applicable control requirements or exemption criteria in this division may be approved by the executive director in accordance with §115.910 if emission reductions are demonstrated to be substantially equivalent.			
F-DOCKS	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(C) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.352(8) § 115.357(8) § 115.358(c)(1) [G]§ 115.358(h)	No component shall be allowed to have a VOC leak, for more than 15 days, after discovery. If the owner or operator elects to use the alternative work practice in §115.358 of this title, any leak detected as defined in §115.358 of this title, including any leak detected using the alternative work practice on a component that is subject to the requirements of this division but not specifically selected for alternative work practice monitoring.	§ 115.354(1) § 115.354(11) § 115.354(13)(A) § 115.354(13)(B) § 115.354(13)(C) § 115.354(13)(D) § 115.354(13)(E) § 115.354(13)(F) § 115.354(4) § 115.354(5) § 115.354(9) [G]§ 115.355 § 115.358(c)(2) § 115.358(d) [G]§ 115.358(e) § 115.358(f)	§ 115.352(7) § 115.354(13)(D) § 115.354(13)(E) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) [G]§ 115.356(4) § 115.356(5)	[G]§ 115.358(g)
F-DOCKS	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7)	No process drains shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts	§ 115.354(1) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.357(1)	per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.		[G]§ 115.356(3)(C) § 115.356(5)	
F-DOCKS	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7)	No process drains shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(5)	None
F-DOCKS	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(9) § 115.357(1) § 115.357(8) § 115.357(9)	No pressure relief valves shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
F-DOCKS	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A)	No pressure relief valves shall be allowed to have a VOC leak, for more than 15 days after discovery, which	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(4) § 115.354(5)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2)	[G]§ 115.354(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(9) § 115.357(12) § 115.357(8) § 115.357(9)	exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355	§ 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	
F-DOCKS	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(8) § 115.357(9)	No open-ended valves or lines shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
F-DOCKS	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8) § 115.357(9)	No open-ended valves or lines shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
F-DOCKS	EU	R5352-	VOC	30 TAC Chapter	§ 115.352(1)(A)	No valves shall be	§ 115.354(1)	§ 115.352(7)	[G]§ 115.354(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		ALL		115, Pet. Refinery & Petrochemicals	§ 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(8) § 115.357(9)	allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	
F-DOCKS	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8) § 115.357(9)	No valves shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
F-DOCKS	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(8) § 115.357(1) § 115.357(12)	No flanges or other connectors shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping	§ 115.354(1) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.357(8)	or exuding of process fluid based on sight, smell, or sound.			
F-DOCKS	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(8) § 115.357(12) § 115.357(8)	No flanges or other connectors shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
F-DOCKS	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(7) § 115.357(1) § 115.357(12) § 115.357(8)	No agitators shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
F-DOCKS	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i)	No agitators shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts	§ 115.354(1) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(7) § 115.357(1) § 115.357(12) § 115.357(8)	per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.		[G]§ 115.356(3)(C) § 115.356(5)	
F-DOCKS	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(7) § 115.357(12) § 115.357(8)	No agitators shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
F-DOCKS	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(3) § 115.357(8)	No compressor seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None
F-DOCKS	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2)	No compressor seals shall be allowed to have a VOC leak, for more than 15 days after	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(4) § 115.357(8)	discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.		§ 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	
F-DOCKS	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1) § 115.357(8)	No compressor seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None
F-DOCKS	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	No compressor seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
F-DOCKS	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(4) § 115.357(8)	No pump seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None
F-DOCKS	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1) § 115.357(8)	No pump seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None
F-DOCKS	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3)	No pump seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane,	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	or the dripping or exuding of process fluid based on sight, smell, or sound.			
F-DOCKS	EU	61J-001	Benzene	40 CFR Part 61, Subpart J	§ 61.112(a) § 61.112(b)	Each owner or operator subject to this subpart shall comply with the requirements of 40 CFR 61, Subpart V - National Emission Standard for Equipment Leaks (Fugitive Emission Sources).	None	None	None
F-DOCKS	EU	63CCV V-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(d)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for equipment in vacuum service.	None	§ 60.486(e) § 60.486(e)(1) § 60.486(e)(5)	None
F-DOCKS	EU	63CCV V-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-2 [G]§ 60.482-9 § 63.648(a)(2) § 63.648(f) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pumps in light liquid service complying with §60.482-2.	[G]§ 60.482-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(d)(6) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
F-DOCKS	EU	63CCV V-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-3 [G]§ 60.482-9	Comply with the specified 40 CFR Part 60, Subpart VV requirements for compressors complying	[G]§ 60.482-3 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.648(a)(2) § 63.648(i) § 63.655(d)(2)	with §60.482-3.	§ 60.485(f)	[G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(d)(6) § 63.655(i)(5)	
F-DOCKS	EU	63CCV V-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) § 60.482-4(a) § 60.482-4(b)(1) [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pressure relief devices in gas/vapor service.	§ 60.482-4(b)(2) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(3) [G]§ 60.486(e)(4) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
F-DOCKS	EU	63CCV V-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-5 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for sampling connection systems complying with §60.482-5.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
F-DOCKS	EU	63CCV V-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-6 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for open-ended valves or lines complying with §60.482-6.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
F-DOCKS	EU	63CCV V-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-7 [G]§ 60.482-9 [G]§ 60.483-1	Comply with the specified 40 CFR Part 60, Subpart VV requirements for valves in gas/vapor service or in light liquid service	[G]§ 60.482-7 [G]§ 60.483-1 [G]§ 60.483-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(d) § 60.487(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 60.483-2 § 63.648(a)(2) § 63.655(d)(2)	complying with §60.482-7.	[G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(e)(4) [G]§ 60.486(f) [G]§ 60.486(g) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	
F-DOCKS	EU	63CCV V-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for valves in heavy liquid service complying with §60.482-8.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
F-DOCKS	EU	63CCV V-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pumps in heavy liquid service complying with §60.482-8.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
F-DOCKS	EU	63CCV V-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for flanges or other connectors complying with §60.482-8.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
F-DOCKS	EU	63CCV V-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b)	Comply with the specified 40 CFR Part 60, Subpart VV	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	requirements for pressure relief devices in light liquid service complying with §60.482-8.	[G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) [G]§ 63.648(b)	§ 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(e)
F-DOCKS	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pressure relief devices in heavy liquid service complying with §60.482-8.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
F-DOCKS	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	[G]§ 63.648(g)	Compressors in hydrogen service are exempt from the requirements of §63.648(a) and (c), if an owner or operator demonstrates that a compressor is in hydrogen service. §63.648(g)(1)-(2).	[G]§ 63.648(g)	§ 63.648(h) § 63.655(d)(3) § 63.655(i)(5)	None
FF-1241-1	EU	60QQQ-001	VOC	40 CFR Part 60, Subpart QQQ	§ 60.692-5 § 60.692-1(a) § 60.692-5(b) § 60.692-5(d) [G]§ 60.692-5(e) § 60.692-6(a) § 60.692-6(b) § 60.692-7(b)	Standard for closed vent system and control devices.	§ 60.695(a) § 60.695(a)(3) § 60.695(a)(3)(ii) § 60.696(a) [G]§ 60.696(b)	§ 60.695(a)(3) § 60.697(a) § 60.697(d) [G]§ 60.697(e) § 60.697(f)(1) [G]§ 60.697(f)(2) § 60.697(f)(3) § 60.697(f)(3)(i) § 60.697(f)(3)(ii) § 60.697(f)(3)(iii) § 60.697(f)(3)(iv) § 60.697(f)(3)(v) § 60.697(f)(3)(vi)	§ 60.698(b)(1) § 60.698(d) § 60.698(d)(3) § 60.698(d)(3)(ii) § 60.698(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
								§ 60.697(f)(3)(vii) § 60.697(f)(3)(x) § 60.697(f)(3)(x)(B)	
FF-1241-1	CD	61FF-0001	Benzene	40 CFR Part 61, Subpart FF	§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	For each closed-vent system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 61.349(a)(1)(i) § 61.349(e) § 61.349(f) § 61.354(d) [G]§ 61.355(h)	§ 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(I)
FF-1241-2	CD	61FF-0001	Benzene	40 CFR Part 61, Subpart FF	§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	For each closed-vent system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 61.349(a)(1)(i) § 61.349(e) § 61.349(f) § 61.354(d) [G]§ 61.355(h)	§ 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(I)
FF-1242	CD	61FF-0001	Benzene	40 CFR Part 61, Subpart FF	§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	For each closed-vent system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 61.349(a)(1)(i) § 61.349(e) § 61.349(f) § 61.354(d) [G]§ 61.355(h)	§ 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(I)
FF-1344	CD	61FF-	Benzene	40 CFR Part 61,	§ 61.349(a)	For each closed-vent	§ 61.349(a)(1)(i)	§ 61.356(f)	§ 61.357(d)(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		0001		Subpart FF	§ 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 61.349(e) § 61.349(f) § 61.354(d) [G]§ 61.355(h)	§ 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3)	§ 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(I)
FF-146	CD	61FF-0001	Benzene	40 CFR Part 61, Subpart FF	§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	For each closed-vent system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 61.349(a)(1)(i) § 61.349(e) § 61.349(f) § 61.354(d) [G]§ 61.355(h)	§ 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(I)
FF-147	CD	61FF-0001	Benzene	40 CFR Part 61, Subpart FF	§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	For each closed-vent system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 61.349(a)(1)(i) § 61.349(e) § 61.349(f) § 61.354(d) [G]§ 61.355(h)	§ 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(I)
FF-241	CD	61FF-0001	Benzene	40 CFR Part 61, Subpart FF	§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b)	For each closed-vent system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain	§ 61.349(a)(1)(i) § 61.349(e) § 61.349(f) § 61.354(d) [G]§ 61.355(h)	§ 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(h)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(I)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 61.349(e) § 61.349(f) § 61.349(g)	the closed-vent system and control device.		§ 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3)	
FF-244	CD	61FF-0001	Benzene	40 CFR Part 61, Subpart FF	§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	For each closed-vent system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 61.349(a)(1)(i) § 61.349(e) § 61.349(f) § 61.354(d) [G]§ 61.355(h)	§ 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(I)
FF-246	CD	61FF-0001	Benzene	40 CFR Part 61, Subpart FF	§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	For each closed-vent system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 61.349(a)(1)(i) § 61.349(e) § 61.349(f) § 61.354(d) [G]§ 61.355(h)	§ 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(I)
FF-443-1	CD	61FF-0001	Benzene	40 CFR Part 61, Subpart FF	§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	For each closed-vent system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 61.349(a)(1)(i) § 61.349(e) § 61.349(f) § 61.354(d) [G]§ 61.355(h)	§ 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(I)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
FF-443-2	CD	61FF-0001	Benzene	40 CFR Part 61, Subpart FF	§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	For each closed-vent system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 61.349(a)(1)(i) § 61.349(e) § 61.349(f) § 61.354(d) [G]§ 61.355(h)	§ 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(I)
FF-84PH	CD	61FF-0001	Benzene	40 CFR Part 61, Subpart FF	§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	For each closed-vent system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 61.349(a)(1)(i) § 61.349(e) § 61.349(f) § 61.354(d) [G]§ 61.355(h)	§ 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(I)
FF-CCS	CD	61FF-0001	Benzene	40 CFR Part 61, Subpart FF	§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	For each closed-vent system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 61.349(a)(1)(i) § 61.349(e) § 61.349(f) § 61.354(d) [G]§ 61.355(h)	§ 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(I)
FF-D-108	EU	60QQQ-001	VOC	40 CFR Part 60, Subpart QQQ	§ 60.692-5 § 60.692-1(a) § 60.692-5(b) § 60.692-5(d) [G]§ 60.692-5(e)	Standard for closed vent system and control devices.	§ 60.695(a) § 60.695(a)(3) § 60.695(a)(3)(ii) § 60.696(a) [G]§ 60.696(b)	§ 60.695(a)(3) § 60.697(a) § 60.697(d) [G]§ 60.697(e) § 60.697(f)(1)	§ 60.698(b)(1) § 60.698(d) § 60.698(d)(3) § 60.698(d)(3)(ii) § 60.698(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.692-6(a) § 60.692-6(b) § 60.692-7(b)			[G]§ 60.697(f)(2) § 60.697(f)(3) § 60.697(f)(3)(i) § 60.697(f)(3)(ii) § 60.697(f)(3)(iii) § 60.697(f)(3)(iv) § 60.697(f)(3)(v) § 60.697(f)(3)(vi) § 60.697(f)(3)(vii) § 60.697(f)(3)(x) § 60.697(f)(3)(x)(B)	
FF-D-108	CD	61FF-001	Benzene	40 CFR Part 61, Subpart FF	§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	For each closed-vent system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(d) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.349(a)(1)(ii) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i)	None
FF-D-108	CD	63G-008	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.136(b) § 63.139(b) § 63.139(c)(1) § 63.139(c)(1)(i) § 63.139(f) § 63.140(a) § 63.140(b) § 63.140(c) [G]§ 63.148(d) § 63.148(e)	Compliance with this paragraph requires operation and maintenance of a cover and vent, as specified, on each opening in the individual drain system and meeting § 63.136(b)(1) through b(5) .	§ 63.139(d)(2)(i) § 63.139(e) § 63.143(a) § 63.143(e) § 63.143(e)(1) § 63.143(f) § 63.143(g) § 63.145(a) § 63.145(a)(2) § 63.148(b)(1)(ii) § 63.148(b)(2)(iii) § 63.148(b)(3) [G]§ 63.148(c) § 63.148(g)	§ 63.143(f) § 63.147(b)(2) § 63.147(b)(5) § 63.147(d) § 63.148(g)(2) § 63.148(h)(2) § 63.148(i)(1) § 63.148(i)(2) [G]§ 63.148(i)(4) § 63.148(i)(5) § 63.148(i)(6) [G]§ 63.152(a) [G]§ 63.152(f)	§ 63.146(b)(2) § 63.146(b)(5) § 63.146(b)(7) § 63.146(b)(7)(ii) § 63.146(b)(7)(ii)(A) § 63.146(b)(7)(ii)(B) § 63.146(c) § 63.146(e) § 63.146(e)(1) § 63.148(j) § 63.148(j)(1) [G]§ 63.151(a)(6) [G]§ 63.151(b) § 63.151(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 63.148(g)(2) § 63.148(h) § 63.148(h)(2)		§ 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(2)(iv) § 63.152(c)(3) § 63.152(c)(3)(i) § 63.152(c)(3)(ii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
FF-DOCKS-1	CD	61FF-0001	Benzene	40 CFR Part 61, Subpart FF	§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	For each closed-vent system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 61.349(a)(1)(i) § 61.349(e) § 61.349(f) § 61.354(d) [G]§ 61.355(h)	§ 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(I)
FF-DOCKS-2	CD	61FF-0001	Benzene	40 CFR Part 61, Subpart FF	§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f)	For each closed-vent system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 61.349(a)(1)(i) § 61.349(e) § 61.349(f) § 61.354(d) [G]§ 61.355(h)	§ 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(h) § 61.356(j) § 61.356(j)(1)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(I)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 61.349(g)			§ 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3)	
FF-DOCKS-3	CD	61FF-0001	Benzene	40 CFR Part 61, Subpart FF	§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	For each closed-vent system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 61.349(a)(1)(i) § 61.349(e) § 61.349(f) § 61.354(d) [G]§ 61.355(h)	§ 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(I)
FF-DOCKS-4	CD	61FF-0001	Benzene	40 CFR Part 61, Subpart FF	§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	For each closed-vent system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 61.349(a)(1)(i) § 61.349(e) § 61.349(f) § 61.354(d) [G]§ 61.355(h)	§ 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(I)
FF-DOCKS-5	CD	61FF-0001	Benzene	40 CFR Part 61, Subpart FF	§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	For each closed-vent system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 61.349(a)(1)(i) § 61.349(e) § 61.349(f) § 61.354(d) [G]§ 61.355(h)	§ 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(I)
FF-DOCKS-6	CD	61FF-	Benzene	40 CFR Part 61,	§ 61.349(a)	For each closed-vent	§ 61.349(a)(1)(i)	§ 61.356(f)	§ 61.357(d)(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		0001		Subpart FF	§ 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 61.349(e) § 61.349(f) § 61.354(d) [G]§ 61.355(h)	§ 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3)	§ 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(I)
FF-GHU-245	CD	61FF-0001	Benzene	40 CFR Part 61, Subpart FF	§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	For each closed-vent system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 61.349(a)(1)(i) § 61.349(e) § 61.349(f) § 61.354(d) [G]§ 61.355(h)	§ 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(I)
FF-KELAB	CD	61FF-0001	Benzene	40 CFR Part 61, Subpart FF	§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	For each closed-vent system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 61.349(a)(1)(i) § 61.349(e) § 61.349(f) § 61.354(d) [G]§ 61.355(h)	§ 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(I)
FF-LAB	CD	61FF-0001	Benzene	40 CFR Part 61, Subpart FF	§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b)	For each closed-vent system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain	§ 61.349(a)(1)(i) § 61.349(e) § 61.349(f) § 61.354(d) [G]§ 61.355(h)	§ 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(h)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(I)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 61.349(e) § 61.349(f) § 61.349(g)	the closed-vent system and control device.		§ 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3)	
FF-PS-1215	EU	60QQQ-001	VOC	40 CFR Part 60, Subpart QQQ	§ 60.692-5 § 60.692-1(a) § 60.692-5(b) § 60.692-5(d) [G]§ 60.692-5(e) § 60.692-6(a) § 60.692-6(b) § 60.692-7(b)	Standard for closed vent system and control devices.	§ 60.695(a) § 60.695(a)(3) § 60.695(a)(3)(ii) § 60.696(a) [G]§ 60.696(b)	§ 60.695(a)(3) § 60.697(a) § 60.697(d) [G]§ 60.697(e) § 60.697(f)(1) [G]§ 60.697(f)(2) § 60.697(f)(3) § 60.697(f)(3)(i) § 60.697(f)(3)(ii) § 60.697(f)(3)(iii) § 60.697(f)(3)(iv) § 60.697(f)(3)(v) § 60.697(f)(3)(vi) § 60.697(f)(3)(vii) § 60.697(f)(3)(x) § 60.697(f)(3)(x)(B)	§ 60.698(b)(1) § 60.698(d) § 60.698(d)(3) § 60.698(d)(3)(ii) § 60.698(e)
FF-PS-1215	CD	61FF-001	Benzene	40 CFR Part 61, Subpart FF	§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	For each closed-vent system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(d) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.349(a)(1)(ii) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i)	None
FF-PS-1215	CD	63G-008	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.136(b) § 63.139(b) § 63.139(c)(1) § 63.139(c)(1)(i)	Compliance with this paragraph requires operation and maintenance of a cover	§ 63.139(d)(2)(i) § 63.139(e) § 63.143(a) § 63.143(e)	§ 63.143(f) § 63.147(b)(2) § 63.147(b)(5) § 63.147(d)	§ 63.146(b)(2) § 63.146(b)(5) § 63.146(b)(7) § 63.146(b)(7)(ii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.139(f) § 63.140(a) § 63.140(b) § 63.140(c) [G]§ 63.148(d) § 63.148(e)	and vent, as specified, on each opening in the individual drain system and meeting § 63.136(b)(1) through b(5) .	§ 63.143(e)(1) § 63.143(f) § 63.143(g) § 63.145(a) § 63.145(a)(2) § 63.148(b)(1)(ii) § 63.148(b)(2)(iii) § 63.148(b)(3) [G]§ 63.148(c) § 63.148(g) § 63.148(g)(2) § 63.148(h) § 63.148(h)(2)	§ 63.148(g)(2) § 63.148(h)(2) § 63.148(i)(1) § 63.148(i)(2) [G]§ 63.148(i)(4) § 63.148(i)(5) § 63.148(i)(6) [G]§ 63.152(a) [G]§ 63.152(f)	§ 63.146(b)(7)(ii)(A) § 63.146(b)(7)(ii)(B) § 63.146(c) § 63.146(e) § 63.146(e)(1) § 63.148(j) § 63.148(j)(1) [G]§ 63.151(a)(6) [G]§ 63.151(b) § 63.151(e) § 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(2)(iv) § 63.152(c)(3) § 63.152(c)(3)(i) § 63.152(c)(3)(ii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
FF-PS-162	EU	60QQQ -001	VOC	40 CFR Part 60, Subpart QQQ	§ 60.692-5 § 60.692-1(a) § 60.692-5(b) § 60.692-5(d) [G]§ 60.692-5(e) § 60.692-6(a) § 60.692-6(b) § 60.692-7(b)	Standard for closed vent system and control devices.	§ 60.695(a) § 60.695(a)(3) § 60.695(a)(3)(ii) § 60.696(a) [G]§ 60.696(b)	§ 60.695(a)(3) § 60.697(a) § 60.697(d) [G]§ 60.697(e) § 60.697(f)(1) [G]§ 60.697(f)(2) § 60.697(f)(3) § 60.697(f)(3)(i) § 60.697(f)(3)(ii) § 60.697(f)(3)(iii)	§ 60.698(b)(1) § 60.698(d) § 60.698(d)(3) § 60.698(d)(3)(ii) § 60.698(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
								§ 60.697(f)(3)(iv) § 60.697(f)(3)(v) § 60.697(f)(3)(vi) § 60.697(f)(3)(vii) § 60.697(f)(3)(x) § 60.697(f)(3)(x)(B)	
FF-PS-162	CD	61FF-001	Benzene	40 CFR Part 61, Subpart FF	§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	For each closed-vent system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(d) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.349(a)(1)(ii) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i)	None
FF-PS-162	CD	63G-008	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.136(b) § 63.139(b) § 63.139(c)(1) § 63.139(c)(1)(i) § 63.139(f) § 63.140(a) § 63.140(b) § 63.140(c) [G]§ 63.148(d) § 63.148(e)	Compliance with this paragraph requires operation and maintenance of a cover and vent, as specified, on each opening in the individual drain system and meeting § 63.136(b)(1) through b(5) .	§ 63.139(d)(2)(i) § 63.139(e) § 63.143(a) § 63.143(e) § 63.143(e)(1) § 63.143(f) § 63.143(g) § 63.145(a) § 63.145(a)(2) § 63.148(b)(1)(ii) § 63.148(b)(2)(iii) § 63.148(b)(3) [G]§ 63.148(c) § 63.148(g) § 63.148(g)(2) § 63.148(h) § 63.148(h)(2)	§ 63.143(f) § 63.147(b)(2) § 63.147(b)(5) § 63.147(d) § 63.148(g)(2) § 63.148(h)(2) § 63.148(i)(1) § 63.148(i)(2) [G]§ 63.148(i)(4) § 63.148(i)(5) § 63.148(i)(6) [G]§ 63.152(a) [G]§ 63.152(f)	§ 63.146(b)(2) § 63.146(b)(5) § 63.146(b)(7) § 63.146(b)(7)(ii) § 63.146(b)(7)(ii)(A) § 63.146(b)(7)(ii)(B) § 63.146(c) § 63.146(e) § 63.146(e)(1) § 63.148(j) § 63.148(j)(1) [G]§ 63.151(a)(6) [G]§ 63.151(b) § 63.151(e) § 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
									§ 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(2)(iv) § 63.152(c)(3) § 63.152(c)(3)(i) § 63.152(c)(3)(ii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
FF-PS-1650	EU	60QQQ-001	VOC	40 CFR Part 60, Subpart QQQ	§ 60.692-5 § 60.692-1(a) § 60.692-5(b) § 60.692-5(d) [G]§ 60.692-5(e) § 60.692-6(a) § 60.692-6(b) § 60.692-7(b)	Standard for closed vent system and control devices.	§ 60.695(a) § 60.695(a)(3) § 60.695(a)(3)(ii) § 60.696(a) [G]§ 60.696(b)	§ 60.695(a)(3) § 60.697(a) § 60.697(d) [G]§ 60.697(e) § 60.697(f)(1) [G]§ 60.697(f)(2) § 60.697(f)(3) § 60.697(f)(3)(i) § 60.697(f)(3)(ii) § 60.697(f)(3)(iii) § 60.697(f)(3)(iv) § 60.697(f)(3)(v) § 60.697(f)(3)(vi) § 60.697(f)(3)(vii) § 60.697(f)(3)(x) § 60.697(f)(3)(x)(B)	§ 60.698(b)(1) § 60.698(d) § 60.698(d)(3) § 60.698(d)(3)(ii) § 60.698(e)
FF-PS-1650	CD	61FF-001	Benzene	40 CFR Part 61, Subpart FF	§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b)	For each closed-vent system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(d) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.349(a)(1)(ii) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(h) § 61.356(j)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 61.349(e) § 61.349(f) § 61.349(g)			§ 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i)	
FF-PS-1650	CD	63G-008	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.136(b) § 63.139(b) § 63.139(c)(1) § 63.139(c)(1)(i) § 63.139(f) § 63.140(a) § 63.140(b) § 63.140(c) [G]§ 63.148(d) § 63.148(e)	Compliance with this paragraph requires operation and maintenance of a cover and vent, as specified, on each opening in the individual drain system and meeting § 63.136(b)(1) through b(5) .	§ 63.139(d)(2)(i) § 63.139(e) § 63.143(a) § 63.143(e) § 63.143(e)(1) § 63.143(f) § 63.143(g) § 63.145(a) § 63.145(a)(2) § 63.148(b)(1)(ii) § 63.148(b)(2)(iii) § 63.148(b)(3) [G]§ 63.148(c) § 63.148(g) § 63.148(g)(2) § 63.148(h) § 63.148(h)(2)	§ 63.143(f) § 63.147(b)(2) § 63.147(b)(5) § 63.147(d) § 63.148(g)(2) § 63.148(h)(2) § 63.148(i)(1) § 63.148(i)(2) [G]§ 63.148(i)(4) § 63.148(i)(5) § 63.148(i)(6) [G]§ 63.152(a) [G]§ 63.152(f)	§ 63.146(b)(2) § 63.146(b)(5) § 63.146(b)(7) § 63.146(b)(7)(ii) § 63.146(b)(7)(ii)(A) § 63.146(b)(7)(ii)(B) § 63.146(c) § 63.146(e) § 63.146(e)(1) § 63.148(j) § 63.148(j)(1) [G]§ 63.151(a)(6) [G]§ 63.151(b) § 63.151(e) § 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(2)(iv) § 63.152(c)(3) § 63.152(c)(3)(i) § 63.152(c)(3)(ii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
FF-PS-236	EU	60QQQ-001	VOC	40 CFR Part 60, Subpart QQQ	§ 60.692-5 § 60.692-1(a) § 60.692-5(b) § 60.692-5(d) [G]§ 60.692-5(e) § 60.692-6(a) § 60.692-6(b) § 60.692-7(b)	Standard for closed vent system and control devices.	§ 60.695(a) § 60.695(a)(3) § 60.695(a)(3)(ii) § 60.696(a) [G]§ 60.696(b)	§ 60.695(a)(3) § 60.697(a) § 60.697(d) [G]§ 60.697(e) § 60.697(f)(1) [G]§ 60.697(f)(2) § 60.697(f)(3) § 60.697(f)(3)(i) § 60.697(f)(3)(ii) § 60.697(f)(3)(iii) § 60.697(f)(3)(iv) § 60.697(f)(3)(v) § 60.697(f)(3)(vi) § 60.697(f)(3)(vii) § 60.697(f)(3)(x) § 60.697(f)(3)(x)(B)	§ 60.698(b)(1) § 60.698(d) § 60.698(d)(3) § 60.698(d)(3)(ii) § 60.698(e)
FF-PS-236	CD	61FF-001	Benzene	40 CFR Part 61, Subpart FF	§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	For each closed-vent system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(d) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.349(a)(1)(ii) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i)	None
FF-PS-236	CD	63G-008	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.136(b) § 63.139(b) § 63.139(c)(1) § 63.139(c)(1)(i) § 63.139(f) § 63.140(a) § 63.140(b) § 63.140(c) [G]§ 63.148(d)	Compliance with this paragraph requires operation and maintenance of a cover and vent, as specified, on each opening in the individual drain system and meeting § 63.136(b)(1) through	§ 63.139(d)(2)(i) § 63.139(e) § 63.143(a) § 63.143(e) § 63.143(e)(1) § 63.143(f) § 63.143(g) § 63.145(a) § 63.145(a)(2)	§ 63.143(f) § 63.147(b)(2) § 63.147(b)(5) § 63.147(d) § 63.148(g)(2) § 63.148(h)(2) § 63.148(i)(1) § 63.148(i)(2) [G]§ 63.148(i)(4)	§ 63.146(b)(2) § 63.146(b)(5) § 63.146(b)(7) § 63.146(b)(7)(ii) § 63.146(b)(7)(ii)(A) § 63.146(b)(7)(ii)(B) § 63.146(c) § 63.146(e) § 63.146(e)(1)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.148(e)	b(5) .	§ 63.148(b)(1)(ii) § 63.148(b)(2)(iii) § 63.148(b)(3) [G]§ 63.148(c) § 63.148(g) § 63.148(g)(2) § 63.148(h) § 63.148(h)(2)	§ 63.148(i)(5) § 63.148(i)(6) [G]§ 63.152(a) [G]§ 63.152(f)	§ 63.148(j) § 63.148(j)(1) [G]§ 63.151(a)(6) [G]§ 63.151(b) § 63.151(e) § 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(2)(iv) § 63.152(c)(3) § 63.152(c)(3)(i) § 63.152(c)(3)(ii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
FF-PS-274	EU	60QQQ -001	VOC	40 CFR Part 60, Subpart QQQ	§ 60.692-5 § 60.692-1(a) § 60.692-5(b) § 60.692-5(d) [G]§ 60.692-5(e) § 60.692-6(a) § 60.692-6(b) § 60.692-7(b)	Standard for closed vent system and control devices.	§ 60.695(a) § 60.695(a)(3) § 60.695(a)(3)(ii) § 60.696(a) [G]§ 60.696(b)	§ 60.695(a)(3) § 60.697(a) § 60.697(d) [G]§ 60.697(e) § 60.697(f)(1) [G]§ 60.697(f)(2) § 60.697(f)(3) § 60.697(f)(3)(i) § 60.697(f)(3)(ii) § 60.697(f)(3)(iii) § 60.697(f)(3)(iv) § 60.697(f)(3)(v) § 60.697(f)(3)(vi) § 60.697(f)(3)(vii) § 60.697(f)(3)(x)	§ 60.698(b)(1) § 60.698(d) § 60.698(d)(3) § 60.698(d)(3)(ii) § 60.698(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
								§ 60.697(f)(3)(x)(B)	
FF-PS-274	CD	61FF-001	Benzene	40 CFR Part 61, Subpart FF	§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	For each closed-vent system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(d) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.349(a)(1)(ii) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i)	None
FF-PS-274	CD	63G-008	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.136(b) § 63.139(b) § 63.139(c)(1) § 63.139(c)(1)(i) § 63.139(f) § 63.140(a) § 63.140(b) § 63.140(c) [G]§ 63.148(d) § 63.148(e)	Compliance with this paragraph requires operation and maintenance of a cover and vent, as specified, on each opening in the individual drain system and meeting § 63.136(b)(1) through b(5) .	§ 63.139(d)(2)(i) § 63.139(e) § 63.143(a) § 63.143(e) § 63.143(e)(1) § 63.143(f) § 63.143(g) § 63.145(a) § 63.145(a)(2) § 63.148(b)(1)(ii) § 63.148(b)(2)(iii) § 63.148(b)(3) [G]§ 63.148(c) § 63.148(g) § 63.148(g)(2) § 63.148(h) § 63.148(h)(2)	§ 63.143(f) § 63.147(b)(2) § 63.147(b)(5) § 63.147(d) § 63.148(g)(2) § 63.148(h)(2) § 63.148(i)(1) § 63.148(i)(2) [G]§ 63.148(i)(4) § 63.148(i)(5) § 63.148(i)(6) [G]§ 63.152(a) [G]§ 63.152(f)	§ 63.146(b)(2) § 63.146(b)(5) § 63.146(b)(7) § 63.146(b)(7)(ii) § 63.146(b)(7)(ii)(A) § 63.146(b)(7)(ii)(B) § 63.146(c) § 63.146(e) § 63.146(e)(1) § 63.148(j) § 63.148(j)(1) [G]§ 63.151(a)(6) [G]§ 63.151(b) § 63.151(e) § 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
									§ 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(2)(iv) § 63.152(c)(3) § 63.152(c)(3)(i) § 63.152(c)(3)(ii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
FF-PS-3650	EU	60QQQ-001	VOC	40 CFR Part 60, Subpart QQQ	§ 60.692-5 § 60.692-1(a) § 60.692-5(b) § 60.692-5(d) [G]§ 60.692-5(e) § 60.692-6(a) § 60.692-6(b) § 60.692-7(b)	Standard for closed vent system and control devices.	§ 60.695(a) § 60.695(a)(3) § 60.695(a)(3)(ii) § 60.696(a) [G]§ 60.696(b)	§ 60.695(a)(3) § 60.697(a) § 60.697(d) [G]§ 60.697(e) § 60.697(f)(1) [G]§ 60.697(f)(2) § 60.697(f)(3) § 60.697(f)(3)(i) § 60.697(f)(3)(ii) § 60.697(f)(3)(iii) § 60.697(f)(3)(iv) § 60.697(f)(3)(v) § 60.697(f)(3)(vi) § 60.697(f)(3)(vii) § 60.697(f)(3)(x) § 60.697(f)(3)(x)(B)	§ 60.698(b)(1) § 60.698(d) § 60.698(d)(3) § 60.698(d)(3)(ii) § 60.698(e)
FF-PS-3650	CD	61FF-001	Benzene	40 CFR Part 61, Subpart FF	§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	For each closed-vent system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(d) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.349(a)(1)(ii) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
FF-PS-3650	CD	63G-008	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.136(b) § 63.139(b) § 63.139(c)(1) § 63.139(c)(1)(i) § 63.139(f) § 63.140(a) § 63.140(b) § 63.140(c) [G]§ 63.148(d) § 63.148(e)	Compliance with this paragraph requires operation and maintenance of a cover and vent, as specified, on each opening in the individual drain system and meeting § 63.136(b)(1) through b(5) .	§ 63.139(d)(2)(i) § 63.139(e) § 63.143(a) § 63.143(e) § 63.143(e)(1) § 63.143(f) § 63.143(g) § 63.145(a) § 63.145(a)(2) § 63.148(b)(1)(ii) § 63.148(b)(2)(iii) § 63.148(b)(3) [G]§ 63.148(c) § 63.148(g) § 63.148(g)(2) § 63.148(h) § 63.148(h)(2)	§ 63.143(f) § 63.147(b)(2) § 63.147(b)(5) § 63.147(d) § 63.148(g)(2) § 63.148(h)(2) § 63.148(i)(1) § 63.148(i)(2) [G]§ 63.148(i)(4) § 63.148(i)(5) § 63.148(i)(6) [G]§ 63.152(a) [G]§ 63.152(f)	§ 63.146(b)(2) § 63.146(b)(5) § 63.146(b)(7) § 63.146(b)(7)(ii) § 63.146(b)(7)(ii)(A) § 63.146(b)(7)(ii)(B) § 63.146(c) § 63.146(e) § 63.146(e)(1) § 63.148(j) § 63.148(j)(1) [G]§ 63.151(a)(6) [G]§ 63.151(b) § 63.151(e) § 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(2)(iv) § 63.152(c)(3) § 63.152(c)(3)(i) § 63.152(c)(3)(ii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
FF-PS-402	EU	60QQQ-001	VOC	40 CFR Part 60, Subpart QQQ	§ 60.692-5 § 60.692-1(a) § 60.692-5(b) § 60.692-5(d) [G]§ 60.692-5(e) § 60.692-6(a)	Standard for closed vent system and control devices.	§ 60.695(a) § 60.695(a)(3) § 60.695(a)(3)(ii) § 60.696(a) [G]§ 60.696(b)	§ 60.695(a)(3) § 60.697(a) § 60.697(d) [G]§ 60.697(e) § 60.697(f)(1) [G]§ 60.697(f)(2)	§ 60.698(b)(1) § 60.698(d) § 60.698(d)(3) § 60.698(d)(3)(ii) § 60.698(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.692-6(b) § 60.692-7(b)			§ 60.697(f)(3) § 60.697(f)(3)(i) § 60.697(f)(3)(ii) § 60.697(f)(3)(iii) § 60.697(f)(3)(iv) § 60.697(f)(3)(v) § 60.697(f)(3)(vi) § 60.697(f)(3)(vii) § 60.697(f)(3)(x) § 60.697(f)(3)(x)(B)	
FF-PS-402	CD	61FF-001	Benzene	40 CFR Part 61, Subpart FF	§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	For each closed-vent system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(d) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.349(a)(1)(ii) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i)	None
FF-PS-402	CD	63G-008	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.136(b) § 63.139(b) § 63.139(c)(1) § 63.139(c)(1)(i) § 63.139(f) § 63.140(a) § 63.140(b) § 63.140(c) [G]§ 63.148(d) § 63.148(e)	Compliance with this paragraph requires operation and maintenance of a cover and vent, as specified, on each opening in the individual drain system and meeting § 63.136(b)(1) through b(5) .	§ 63.139(d)(2)(i) § 63.139(e) § 63.143(a) § 63.143(e) § 63.143(e)(1) § 63.143(f) § 63.143(g) § 63.145(a) § 63.145(a)(2) § 63.148(b)(1)(ii) § 63.148(b)(2)(iii) § 63.148(b)(3) [G]§ 63.148(c) § 63.148(g) § 63.148(g)(2)	§ 63.143(f) § 63.147(b)(2) § 63.147(b)(5) § 63.147(d) § 63.148(g)(2) § 63.148(h)(2) § 63.148(i)(1) § 63.148(i)(2) [G]§ 63.148(i)(4) § 63.148(i)(5) § 63.148(i)(6) [G]§ 63.152(a) [G]§ 63.152(f)	§ 63.146(b)(2) § 63.146(b)(5) § 63.146(b)(7) § 63.146(b)(7)(ii) § 63.146(b)(7)(ii)(A) § 63.146(b)(7)(ii)(B) § 63.146(c) § 63.146(e) § 63.146(e)(1) § 63.148(j) § 63.148(j)(1) [G]§ 63.151(a)(6) [G]§ 63.151(b) § 63.151(e) § 63.151(e)(1)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 63.148(h) § 63.148(h)(2)		§ 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(2)(iv) § 63.152(c)(3) § 63.152(c)(3)(i) § 63.152(c)(3)(ii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
FF-PS-403	EU	60QQQ-001	VOC	40 CFR Part 60, Subpart QQQ	§ 60.692-5 § 60.692-1(a) § 60.692-5(b) § 60.692-5(d) [G]§ 60.692-5(e) § 60.692-6(a) § 60.692-6(b) § 60.692-7(b)	Standard for closed vent system and control devices.	§ 60.695(a) § 60.695(a)(3) § 60.695(a)(3)(ii) § 60.696(a) [G]§ 60.696(b)	§ 60.695(a)(3) § 60.697(a) § 60.697(d) [G]§ 60.697(e) § 60.697(f)(1) [G]§ 60.697(f)(2) § 60.697(f)(3) § 60.697(f)(3)(i) § 60.697(f)(3)(ii) § 60.697(f)(3)(iii) § 60.697(f)(3)(iv) § 60.697(f)(3)(v) § 60.697(f)(3)(vi) § 60.697(f)(3)(vii) § 60.697(f)(3)(x) § 60.697(f)(3)(x)(B)	§ 60.698(b)(1) § 60.698(d) § 60.698(d)(3) § 60.698(d)(3)(ii) § 60.698(e)
FF-PS-403	CD	61FF-001	Benzene	40 CFR Part 61, Subpart FF	§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B)	For each closed-vent system and control device used to comply with §§61.343-61.348,	§ 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f)	§ 61.349(a)(1)(ii) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	properly design, install, operate, and maintain the closed-vent system and control device.	§ 61.354(d) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i)	
FF-PS-403	CD	63G-008	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.136(b) § 63.139(b) § 63.139(c)(1) § 63.139(c)(1)(i) § 63.139(f) § 63.140(a) § 63.140(b) § 63.140(c) [G]§ 63.148(d) § 63.148(e)	Compliance with this paragraph requires operation and maintenance of a cover and vent, as specified, on each opening in the individual drain system and meeting § 63.136(b)(1) through b(5) .	§ 63.139(d)(2)(i) § 63.139(e) § 63.143(a) § 63.143(e) § 63.143(e)(1) § 63.143(f) § 63.143(g) § 63.145(a) § 63.145(a)(2) § 63.148(b)(1)(ii) § 63.148(b)(2)(iii) § 63.148(b)(3) [G]§ 63.148(c) § 63.148(g) § 63.148(g)(2) § 63.148(h) § 63.148(h)(2)	§ 63.143(f) § 63.147(b)(2) § 63.147(b)(5) § 63.147(d) § 63.148(g)(2) § 63.148(h)(2) § 63.148(i)(1) § 63.148(i)(2) [G]§ 63.148(i)(4) § 63.148(i)(5) § 63.148(i)(6) [G]§ 63.152(a) [G]§ 63.152(f)	§ 63.146(b)(2) § 63.146(b)(5) § 63.146(b)(7) § 63.146(b)(7)(ii) § 63.146(b)(7)(ii)(A) § 63.146(b)(7)(ii)(B) § 63.146(c) § 63.146(e) § 63.146(e)(1) § 63.148(j) § 63.148(j)(1) [G]§ 63.151(a)(6) [G]§ 63.151(b) § 63.151(e) § 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(2)(iv) § 63.152(c)(3) § 63.152(c)(3)(i)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
									§ 63.152(c)(3)(ii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
FF-PS-404	EU	60QQQ-001	VOC	40 CFR Part 60, Subpart QQQ	§ 60.692-5 § 60.692-1(a) § 60.692-5(b) § 60.692-5(d) [G]§ 60.692-5(e) § 60.692-6(a) § 60.692-6(b) § 60.692-7(b)	Standard for closed vent system and control devices.	§ 60.695(a) § 60.695(a)(3) § 60.695(a)(3)(ii) § 60.696(a) [G]§ 60.696(b)	§ 60.695(a)(3) § 60.697(a) § 60.697(d) [G]§ 60.697(e) § 60.697(f)(1) [G]§ 60.697(f)(2) § 60.697(f)(3) § 60.697(f)(3)(i) § 60.697(f)(3)(ii) § 60.697(f)(3)(iii) § 60.697(f)(3)(iv) § 60.697(f)(3)(v) § 60.697(f)(3)(vi) § 60.697(f)(3)(vii) § 60.697(f)(3)(x) § 60.697(f)(3)(x)(B)	§ 60.698(b)(1) § 60.698(d) § 60.698(d)(3) § 60.698(d)(3)(ii) § 60.698(e)
FF-PS-404	CD	61FF-001	Benzene	40 CFR Part 61, Subpart FF	§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	For each closed-vent system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(d) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.349(a)(1)(ii) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i)	None
FF-PS-404	CD	63G-008	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.136(b) § 63.139(b) § 63.139(c)(1) § 63.139(c)(1)(i) § 63.139(f) § 63.140(a)	Compliance with this paragraph requires operation and maintenance of a cover and vent, as specified, on each opening in the	§ 63.139(d)(2)(i) § 63.139(e) § 63.143(a) § 63.143(e) § 63.143(e)(1) § 63.143(f)	§ 63.143(f) § 63.147(b)(2) § 63.147(b)(5) § 63.147(d) § 63.148(g)(2) § 63.148(h)(2)	§ 63.146(b)(2) § 63.146(b)(5) § 63.146(b)(7) § 63.146(b)(7)(ii) § 63.146(b)(7)(ii)(A) § 63.146(b)(7)(ii)(B)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.140(b) § 63.140(c) [G]§ 63.148(d) § 63.148(e)	individual drain system and meeting § 63.136(b)(1) through b(5) .	§ 63.143(g) § 63.145(a) § 63.145(a)(2) § 63.148(b)(1)(ii) § 63.148(b)(2)(iii) § 63.148(b)(3) [G]§ 63.148(c) § 63.148(g) § 63.148(g)(2) § 63.148(h) § 63.148(h)(2)	§ 63.148(i)(1) § 63.148(i)(2) [G]§ 63.148(i)(4) § 63.148(i)(5) § 63.148(i)(6) [G]§ 63.152(a) [G]§ 63.152(f)	§ 63.146(c) § 63.146(e) § 63.146(e)(1) § 63.148(j) § 63.148(j)(1) [G]§ 63.151(a)(6) [G]§ 63.151(b) § 63.151(e) § 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(2)(iv) § 63.152(c)(3) § 63.152(c)(3)(i) § 63.152(c)(3)(ii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
FF-PS-405	EU	60QQQ -001	VOC	40 CFR Part 60, Subpart QQQ	§ 60.692-5 § 60.692-1(a) § 60.692-5(b) § 60.692-5(d) [G]§ 60.692-5(e) § 60.692-6(a) § 60.692-6(b) § 60.692-7(b)	Standard for closed vent system and control devices.	§ 60.695(a) § 60.695(a)(3) § 60.695(a)(3)(ii) § 60.696(a) [G]§ 60.696(b)	§ 60.695(a)(3) § 60.697(a) § 60.697(d) [G]§ 60.697(e) § 60.697(f)(1) [G]§ 60.697(f)(2) § 60.697(f)(3) § 60.697(f)(3)(i) § 60.697(f)(3)(ii) § 60.697(f)(3)(iii) § 60.697(f)(3)(iv) § 60.697(f)(3)(v)	§ 60.698(b)(1) § 60.698(d) § 60.698(d)(3) § 60.698(d)(3)(ii) § 60.698(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
								§ 60.697(f)(3)(vi) § 60.697(f)(3)(vii) § 60.697(f)(3)(x) § 60.697(f)(3)(x)(B)	
FF-PS-405	CD	61FF-001	Benzene	40 CFR Part 61, Subpart FF	§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	For each closed-vent system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(d) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.349(a)(1)(ii) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i)	None
FF-PS-405	CD	63G-008	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.136(b) § 63.139(b) § 63.139(c)(1) § 63.139(c)(1)(i) § 63.139(f) § 63.140(a) § 63.140(b) § 63.140(c) [G]§ 63.148(d) § 63.148(e)	Compliance with this paragraph requires operation and maintenance of a cover and vent, as specified, on each opening in the individual drain system and meeting § 63.136(b)(1) through b(5) .	§ 63.139(d)(2)(i) § 63.139(e) § 63.143(a) § 63.143(e) § 63.143(e)(1) § 63.143(f) § 63.143(g) § 63.145(a) § 63.145(a)(2) § 63.148(b)(1)(ii) § 63.148(b)(2)(iii) § 63.148(b)(3) [G]§ 63.148(c) § 63.148(g) § 63.148(g)(2) § 63.148(h) § 63.148(h)(2)	§ 63.143(f) § 63.147(b)(2) § 63.147(b)(5) § 63.147(d) § 63.148(g)(2) § 63.148(h)(2) § 63.148(i)(1) § 63.148(i)(2) [G]§ 63.148(i)(4) § 63.148(i)(5) § 63.148(i)(6) [G]§ 63.152(a) [G]§ 63.152(f)	§ 63.146(b)(2) § 63.146(b)(5) § 63.146(b)(7) § 63.146(b)(7)(ii) § 63.146(b)(7)(ii)(A) § 63.146(b)(7)(ii)(B) § 63.146(c) § 63.146(e) § 63.146(e)(1) § 63.148(j) § 63.148(j)(1) [G]§ 63.151(a)(6) [G]§ 63.151(b) § 63.151(e) § 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
									§ 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(2)(iv) § 63.152(c)(3) § 63.152(c)(3)(i) § 63.152(c)(3)(ii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
FF-PS-406	EU	60QQQ-001	VOC	40 CFR Part 60, Subpart QQQ	§ 60.692-5 § 60.692-1(a) § 60.692-5(b) § 60.692-5(d) [G]§ 60.692-5(e) § 60.692-6(a) § 60.692-6(b) § 60.692-7(b)	Standard for closed vent system and control devices.	§ 60.695(a) § 60.695(a)(3) § 60.695(a)(3)(ii) § 60.696(a) [G]§ 60.696(b)	§ 60.695(a)(3) § 60.697(a) § 60.697(d) [G]§ 60.697(e) § 60.697(f)(1) [G]§ 60.697(f)(2) § 60.697(f)(3) § 60.697(f)(3)(i) § 60.697(f)(3)(ii) § 60.697(f)(3)(iii) § 60.697(f)(3)(iv) § 60.697(f)(3)(v) § 60.697(f)(3)(vi) § 60.697(f)(3)(vii) § 60.697(f)(3)(x) § 60.697(f)(3)(x)(B)	§ 60.698(b)(1) § 60.698(d) § 60.698(d)(3) § 60.698(d)(3)(ii) § 60.698(e)
FF-PS-406	CD	61FF-001	Benzene	40 CFR Part 61, Subpart FF	§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f)	For each closed-vent system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(d) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.349(a)(1)(ii) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 61.349(g)			§ 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i)	
FF-PS-406	CD	63G-008	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.136(b) § 63.139(b) § 63.139(c)(1) § 63.139(c)(1)(i) § 63.139(f) § 63.140(a) § 63.140(b) § 63.140(c) [G]§ 63.148(d) § 63.148(e)	Compliance with this paragraph requires operation and maintenance of a cover and vent, as specified, on each opening in the individual drain system and meeting § 63.136(b)(1) through b(5) .	§ 63.139(d)(2)(i) § 63.139(e) § 63.143(a) § 63.143(e) § 63.143(e)(1) § 63.143(f) § 63.143(g) § 63.145(a) § 63.145(a)(2) § 63.148(b)(1)(ii) § 63.148(b)(2)(iii) § 63.148(b)(3) [G]§ 63.148(c) § 63.148(g) § 63.148(g)(2) § 63.148(h) § 63.148(h)(2)	§ 63.143(f) § 63.147(b)(2) § 63.147(b)(5) § 63.147(d) § 63.148(g)(2) § 63.148(h)(2) § 63.148(i)(1) § 63.148(i)(2) [G]§ 63.148(i)(4) § 63.148(i)(5) § 63.148(i)(6) [G]§ 63.152(a) [G]§ 63.152(f)	§ 63.146(b)(2) § 63.146(b)(5) § 63.146(b)(7) § 63.146(b)(7)(ii) § 63.146(b)(7)(ii)(A) § 63.146(b)(7)(ii)(B) § 63.146(c) § 63.146(e) § 63.146(e)(1) § 63.148(j) § 63.148(j)(1) [G]§ 63.151(a)(6) [G]§ 63.151(b) § 63.151(e) § 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(2)(iv) § 63.152(c)(3) § 63.152(c)(3)(i) § 63.152(c)(3)(ii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
FF-PS-427	EU	60QQQ-001	VOC	40 CFR Part 60, Subpart QQQ	§ 60.692-5 § 60.692-1(a)	Standard for closed vent system and control	§ 60.695(a) § 60.695(a)(3)	§ 60.695(a)(3) § 60.697(a)	§ 60.698(b)(1) § 60.698(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.692-5(b) § 60.692-5(d) [G]§ 60.692-5(e) § 60.692-6(a) § 60.692-6(b) § 60.692-7(b)	devices.	§ 60.695(a)(3)(ii) § 60.696(a) [G]§ 60.696(b)	§ 60.697(d) [G]§ 60.697(e) § 60.697(f)(1) [G]§ 60.697(f)(2) § 60.697(f)(3) § 60.697(f)(3)(i) § 60.697(f)(3)(ii) § 60.697(f)(3)(iii) § 60.697(f)(3)(iv) § 60.697(f)(3)(v) § 60.697(f)(3)(vi) § 60.697(f)(3)(vii) § 60.697(f)(3)(x) § 60.697(f)(3)(x)(B)	§ 60.698(d)(3) § 60.698(d)(3)(ii) § 60.698(e)
FF-PS-427	CD	61FF-001	Benzene	40 CFR Part 61, Subpart FF	§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	For each closed-vent system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(d) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.349(a)(1)(ii) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i)	None
FF-PS-427	CD	63G-008	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.136(b) § 63.139(b) § 63.139(c)(1) § 63.139(c)(1)(i) § 63.139(f) § 63.140(a) § 63.140(b) § 63.140(c) [G]§ 63.148(d) § 63.148(e)	Compliance with this paragraph requires operation and maintenance of a cover and vent, as specified, on each opening in the individual drain system and meeting § 63.136(b)(1) through b(5) .	§ 63.139(d)(2)(i) § 63.139(e) § 63.143(a) § 63.143(e) § 63.143(e)(1) § 63.143(f) § 63.143(g) § 63.145(a) § 63.145(a)(2) § 63.148(b)(1)(ii) § 63.148(b)(2)(iii)	§ 63.143(f) § 63.147(b)(2) § 63.147(b)(5) § 63.147(d) § 63.148(g)(2) § 63.148(h)(2) § 63.148(i)(1) § 63.148(i)(2) [G]§ 63.148(i)(4) § 63.148(i)(5) § 63.148(i)(6)	§ 63.146(b)(2) § 63.146(b)(5) § 63.146(b)(7) § 63.146(b)(7)(ii) § 63.146(b)(7)(ii)(A) § 63.146(b)(7)(ii)(B) § 63.146(c) § 63.146(e) § 63.146(e)(1) § 63.148(j) § 63.148(j)(1)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 63.148(b)(3) [G]§ 63.148(c) § 63.148(g) § 63.148(g)(2) § 63.148(h) § 63.148(h)(2)	[G]§ 63.152(a) [G]§ 63.152(f)	[G]§ 63.151(a)(6) [G]§ 63.151(b) § 63.151(e) § 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(2)(iv) § 63.152(c)(3) § 63.152(c)(3)(i) § 63.152(c)(3)(ii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
FF-PS-434	EU	60QQQ -001	VOC	40 CFR Part 60, Subpart QQQ	§ 60.692-5 § 60.692-1(a) § 60.692-5(b) § 60.692-5(d) [G]§ 60.692-5(e) § 60.692-6(a) § 60.692-6(b) § 60.692-7(b)	Standard for closed vent system and control devices.	§ 60.695(a) § 60.695(a)(3) § 60.695(a)(3)(ii) § 60.696(a) [G]§ 60.696(b)	§ 60.695(a)(3) § 60.697(a) § 60.697(d) [G]§ 60.697(e) § 60.697(f)(1) [G]§ 60.697(f)(2) § 60.697(f)(3) § 60.697(f)(3)(i) § 60.697(f)(3)(ii) § 60.697(f)(3)(iii) § 60.697(f)(3)(iv) § 60.697(f)(3)(v) § 60.697(f)(3)(vi) § 60.697(f)(3)(vii) § 60.697(f)(3)(x) § 60.697(f)(3)(x)(B)	§ 60.698(b)(1) § 60.698(d) § 60.698(d)(3) § 60.698(d)(3)(ii) § 60.698(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
FF-PS-434	CD	61FF-001	Benzene	40 CFR Part 61, Subpart FF	§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	For each closed-vent system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(d) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.349(a)(1)(ii) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i)	None
FF-PS-434	CD	63G-008	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.136(b) § 63.139(b) § 63.139(c)(1) § 63.139(c)(1)(i) § 63.139(f) § 63.140(a) § 63.140(b) § 63.140(c) [G]§ 63.148(d) § 63.148(e)	Compliance with this paragraph requires operation and maintenance of a cover and vent, as specified, on each opening in the individual drain system and meeting § 63.136(b)(1) through b(5) .	§ 63.139(d)(2)(i) § 63.139(e) § 63.143(a) § 63.143(e) § 63.143(e)(1) § 63.143(f) § 63.143(g) § 63.145(a) § 63.145(a)(2) § 63.148(b)(1)(ii) § 63.148(b)(2)(iii) § 63.148(b)(3) [G]§ 63.148(c) § 63.148(g) § 63.148(g)(2) § 63.148(h) § 63.148(h)(2)	§ 63.143(f) § 63.147(b)(2) § 63.147(b)(5) § 63.147(d) § 63.148(g)(2) § 63.148(h)(2) § 63.148(i)(1) § 63.148(i)(2) [G]§ 63.148(i)(4) § 63.148(i)(5) § 63.148(i)(6) [G]§ 63.152(a) [G]§ 63.152(f)	§ 63.146(b)(2) § 63.146(b)(5) § 63.146(b)(7) § 63.146(b)(7)(ii) § 63.146(b)(7)(ii)(A) § 63.146(b)(7)(ii)(B) § 63.146(c) § 63.146(e) § 63.146(e)(1) § 63.148(j) § 63.148(j)(1) [G]§ 63.151(a)(6) [G]§ 63.151(b) § 63.151(e) § 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
									§ 63.152(c)(2)(iii) § 63.152(c)(2)(iv) § 63.152(c)(3) § 63.152(c)(3)(i) § 63.152(c)(3)(ii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
FF-PS-435	EU	60QQQ-001	VOC	40 CFR Part 60, Subpart QQQ	§ 60.692-5 § 60.692-1(a) § 60.692-5(b) § 60.692-5(d) [G]§ 60.692-5(e) § 60.692-6(a) § 60.692-6(b) § 60.692-7(b)	Standard for closed vent system and control devices.	§ 60.695(a) § 60.695(a)(3) § 60.695(a)(3)(ii) § 60.696(a) [G]§ 60.696(b)	§ 60.695(a)(3) § 60.697(a) § 60.697(d) [G]§ 60.697(e) § 60.697(f)(1) [G]§ 60.697(f)(2) § 60.697(f)(3) § 60.697(f)(3)(i) § 60.697(f)(3)(ii) § 60.697(f)(3)(iii) § 60.697(f)(3)(iv) § 60.697(f)(3)(v) § 60.697(f)(3)(vi) § 60.697(f)(3)(vii) § 60.697(f)(3)(x) § 60.697(f)(3)(x)(B)	§ 60.698(b)(1) § 60.698(d) § 60.698(d)(3) § 60.698(d)(3)(ii) § 60.698(e)
FF-PS-435	CD	61FF-001	Benzene	40 CFR Part 61, Subpart FF	§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	For each closed-vent system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(d) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.349(a)(1)(ii) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i)	None
FF-PS-435	CD	63G-008	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.136(b) § 63.139(b)	Compliance with this paragraph requires	§ 63.139(d)(2)(i) § 63.139(e)	§ 63.143(f) § 63.147(b)(2)	§ 63.146(b)(2) § 63.146(b)(5)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.139(c)(1) § 63.139(c)(1)(i) § 63.139(f) § 63.140(a) § 63.140(b) § 63.140(c) [G]§ 63.148(d) § 63.148(e)	operation and maintenance of a cover and vent, as specified, on each opening in the individual drain system and meeting § 63.136(b)(1) through b(5) .	§ 63.143(a) § 63.143(e) § 63.143(e)(1) § 63.143(f) § 63.143(g) § 63.145(a) § 63.145(a)(2) § 63.148(b)(1)(ii) § 63.148(b)(2)(iii) § 63.148(b)(3) [G]§ 63.148(c) § 63.148(g) § 63.148(g)(2) § 63.148(h) § 63.148(h)(2)	§ 63.147(b)(5) § 63.147(d) § 63.148(g)(2) § 63.148(h)(2) § 63.148(i)(1) § 63.148(i)(2) [G]§ 63.148(i)(4) § 63.148(i)(5) § 63.148(i)(6) [G]§ 63.152(a) [G]§ 63.152(f)	§ 63.146(b)(7) § 63.146(b)(7)(ii) § 63.146(b)(7)(ii)(A) § 63.146(b)(7)(ii)(B) § 63.146(c) § 63.146(e) § 63.146(e)(1) § 63.148(j) § 63.148(j)(1) [G]§ 63.151(a)(6) [G]§ 63.151(b) § 63.151(e) § 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(2)(iv) § 63.152(c)(3) § 63.152(c)(3)(i) § 63.152(c)(3)(ii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
FF-PS-436	EU	60QQQ -001	VOC	40 CFR Part 60, Subpart QQQ	§ 60.692-5 § 60.692-1(a) § 60.692-5(b) § 60.692-5(d) [G]§ 60.692-5(e) § 60.692-6(a) § 60.692-6(b) § 60.692-7(b)	Standard for closed vent system and control devices.	§ 60.695(a) § 60.695(a)(3) § 60.695(a)(3)(ii) § 60.696(a) [G]§ 60.696(b)	§ 60.695(a)(3) § 60.697(a) § 60.697(d) [G]§ 60.697(e) § 60.697(f)(1) [G]§ 60.697(f)(2) § 60.697(f)(3) § 60.697(f)(3)(i)	§ 60.698(b)(1) § 60.698(d) § 60.698(d)(3) § 60.698(d)(3)(ii) § 60.698(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
								§ 60.697(f)(3)(ii) § 60.697(f)(3)(iii) § 60.697(f)(3)(iv) § 60.697(f)(3)(v) § 60.697(f)(3)(vi) § 60.697(f)(3)(vii) § 60.697(f)(3)(x) § 60.697(f)(3)(x)(B)	
FF-PS-436	CD	61FF-001	Benzene	40 CFR Part 61, Subpart FF	§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	For each closed-vent system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(d) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.349(a)(1)(ii) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i)	None
FF-PS-436	CD	63G-008	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.136(b) § 63.139(b) § 63.139(c)(1) § 63.139(c)(1)(i) § 63.139(f) § 63.140(a) § 63.140(b) § 63.140(c) [G]§ 63.148(d) § 63.148(e)	Compliance with this paragraph requires operation and maintenance of a cover and vent, as specified, on each opening in the individual drain system and meeting § 63.136(b)(1) through b(5) .	§ 63.139(d)(2)(i) § 63.139(e) § 63.143(a) § 63.143(e) § 63.143(e)(1) § 63.143(f) § 63.143(g) § 63.145(a) § 63.145(a)(2) § 63.148(b)(1)(ii) § 63.148(b)(2)(iii) § 63.148(b)(3) [G]§ 63.148(c) § 63.148(g) § 63.148(g)(2) § 63.148(h) § 63.148(h)(2)	§ 63.143(f) § 63.147(b)(2) § 63.147(b)(5) § 63.147(d) § 63.148(g)(2) § 63.148(h)(2) § 63.148(i)(1) § 63.148(i)(2) [G]§ 63.148(i)(4) § 63.148(i)(5) § 63.148(i)(6) [G]§ 63.152(a) [G]§ 63.152(f)	§ 63.146(b)(2) § 63.146(b)(5) § 63.146(b)(7) § 63.146(b)(7)(ii) § 63.146(b)(7)(ii)(A) § 63.146(b)(7)(ii)(B) § 63.146(c) § 63.146(e) § 63.146(e)(1) § 63.148(j) § 63.148(j)(1) [G]§ 63.151(a)(6) [G]§ 63.151(b) § 63.151(e) § 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
									[G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(2)(iv) § 63.152(c)(3) § 63.152(c)(3)(i) § 63.152(c)(3)(ii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
FF-PS-439	EU	60QQQ-001	VOC	40 CFR Part 60, Subpart QQQ	§ 60.692-5 § 60.692-1(a) § 60.692-5(b) § 60.692-5(d) [G]§ 60.692-5(e) § 60.692-6(a) § 60.692-6(b) § 60.692-7(b)	Standard for closed vent system and control devices.	§ 60.695(a) § 60.695(a)(3) § 60.695(a)(3)(ii) § 60.696(a) [G]§ 60.696(b)	§ 60.695(a)(3) § 60.697(a) § 60.697(d) [G]§ 60.697(e) § 60.697(f)(1) [G]§ 60.697(f)(2) § 60.697(f)(3) § 60.697(f)(3)(i) § 60.697(f)(3)(ii) § 60.697(f)(3)(iii) § 60.697(f)(3)(iv) § 60.697(f)(3)(v) § 60.697(f)(3)(vi) § 60.697(f)(3)(vii) § 60.697(f)(3)(x) § 60.697(f)(3)(x)(B)	§ 60.698(b)(1) § 60.698(d) § 60.698(d)(3) § 60.698(d)(3)(ii) § 60.698(e)
FF-PS-439	CD	61FF-001	Benzene	40 CFR Part 61, Subpart FF	§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv)	For each closed-vent system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain	§ 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(d) § 61.354(f)(1)	§ 61.349(a)(1)(ii) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	the closed-vent system and control device.	[G]§ 61.355(h)	§ 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i)	
FF-PS-439	CD	63G-008	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.136(b) § 63.139(b) § 63.139(c)(1) § 63.139(c)(1)(i) § 63.139(f) § 63.140(a) § 63.140(b) § 63.140(c) [G]§ 63.148(d) § 63.148(e)	Compliance with this paragraph requires operation and maintenance of a cover and vent, as specified, on each opening in the individual drain system and meeting § 63.136(b)(1) through b(5) .	§ 63.139(d)(2)(i) § 63.139(e) § 63.143(a) § 63.143(e) § 63.143(e)(1) § 63.143(f) § 63.143(g) § 63.145(a) § 63.145(a)(2) § 63.148(b)(1)(ii) § 63.148(b)(2)(iii) § 63.148(b)(3) [G]§ 63.148(c) § 63.148(g) § 63.148(g)(2) § 63.148(h) § 63.148(h)(2)	§ 63.143(f) § 63.147(b)(2) § 63.147(b)(5) § 63.147(d) § 63.148(g)(2) § 63.148(h)(2) § 63.148(i)(1) § 63.148(i)(2) [G]§ 63.148(i)(4) § 63.148(i)(5) § 63.148(i)(6) [G]§ 63.152(a) [G]§ 63.152(f)	§ 63.146(b)(2) § 63.146(b)(5) § 63.146(b)(7) § 63.146(b)(7)(ii) § 63.146(b)(7)(ii)(A) § 63.146(b)(7)(ii)(B) § 63.146(c) § 63.146(e) § 63.146(e)(1) § 63.148(j) § 63.148(j)(1) [G]§ 63.151(a)(6) [G]§ 63.151(b) § 63.151(e) § 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(2)(iv) § 63.152(c)(3) § 63.152(c)(3)(i) § 63.152(c)(3)(ii) § 63.152(c)(4)(ii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
									[G]§ 63.152(c)(6)
FF-PS-441	EU	60QQQ-001	VOC	40 CFR Part 60, Subpart QQQ	§ 60.692-5 § 60.692-1(a) § 60.692-5(b) § 60.692-5(d) [G]§ 60.692-5(e) § 60.692-6(a) § 60.692-6(b) § 60.692-7(b)	Standard for closed vent system and control devices.	§ 60.695(a) § 60.695(a)(3) § 60.695(a)(3)(ii) § 60.696(a) [G]§ 60.696(b)	§ 60.695(a)(3) § 60.697(a) § 60.697(d) [G]§ 60.697(e) § 60.697(f)(1) [G]§ 60.697(f)(2) § 60.697(f)(3) § 60.697(f)(3)(i) § 60.697(f)(3)(ii) § 60.697(f)(3)(iii) § 60.697(f)(3)(iv) § 60.697(f)(3)(v) § 60.697(f)(3)(vi) § 60.697(f)(3)(vii) § 60.697(f)(3)(x) § 60.697(f)(3)(x)(B)	§ 60.698(b)(1) § 60.698(d) § 60.698(d)(3) § 60.698(d)(3)(ii) § 60.698(e)
FF-PS-441	CD	61FF-001	Benzene	40 CFR Part 61, Subpart FF	§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	For each closed-vent system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(d) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.349(a)(1)(ii) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i)	None
FF-PS-441	CD	63G-008	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.136(b) § 63.139(b) § 63.139(c)(1) § 63.139(c)(1)(i) § 63.139(f) § 63.140(a) § 63.140(b) § 63.140(c)	Compliance with this paragraph requires operation and maintenance of a cover and vent, as specified, on each opening in the individual drain system and meeting §	§ 63.139(d)(2)(i) § 63.139(e) § 63.143(a) § 63.143(e) § 63.143(e)(1) § 63.143(f) § 63.143(g) § 63.145(a)	§ 63.143(f) § 63.147(b)(2) § 63.147(b)(5) § 63.147(d) § 63.148(g)(2) § 63.148(h)(2) § 63.148(i)(1) § 63.148(i)(2)	§ 63.146(b)(2) § 63.146(b)(5) § 63.146(b)(7) § 63.146(b)(7)(ii) § 63.146(b)(7)(ii)(A) § 63.146(b)(7)(ii)(B) § 63.146(c) § 63.146(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 63.148(d) § 63.148(e)	63.136(b)(1) through b(5) .	§ 63.145(a)(2) § 63.148(b)(1)(ii) § 63.148(b)(2)(iii) § 63.148(b)(3) [G]§ 63.148(c) § 63.148(g) § 63.148(g)(2) § 63.148(h) § 63.148(h)(2)	[G]§ 63.148(i)(4) § 63.148(i)(5) § 63.148(i)(6) [G]§ 63.152(a) [G]§ 63.152(f)	§ 63.146(e)(1) § 63.148(j) § 63.148(j)(1) [G]§ 63.151(a)(6) [G]§ 63.151(b) § 63.151(e) § 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(2)(iv) § 63.152(c)(3) § 63.152(c)(3)(i) § 63.152(c)(3)(ii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
FF-PS-449	EU	60QQQ -001	VOC	40 CFR Part 60, Subpart QQQ	§ 60.692-5 § 60.692-1(a) § 60.692-5(b) § 60.692-5(d) [G]§ 60.692-5(e) § 60.692-6(a) § 60.692-6(b) § 60.692-7(b)	Standard for closed vent system and control devices.	§ 60.695(a) § 60.695(a)(3) § 60.695(a)(3)(ii) § 60.696(a) [G]§ 60.696(b)	§ 60.695(a)(3) § 60.697(a) § 60.697(d) [G]§ 60.697(e) § 60.697(f)(1) [G]§ 60.697(f)(2) § 60.697(f)(3) § 60.697(f)(3)(i) § 60.697(f)(3)(ii) § 60.697(f)(3)(iii) § 60.697(f)(3)(iv) § 60.697(f)(3)(v) § 60.697(f)(3)(vi) § 60.697(f)(3)(vii)	§ 60.698(b)(1) § 60.698(d) § 60.698(d)(3) § 60.698(d)(3)(ii) § 60.698(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
								§ 60.697(f)(3)(x) § 60.697(f)(3)(x)(B)	
FF-PS-449	CD	61FF-001	Benzene	40 CFR Part 61, Subpart FF	§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	For each closed-vent system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(d) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.349(a)(1)(ii) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i)	None
FF-PS-449	CD	63G-008	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.136(b) § 63.139(b) § 63.139(c)(1) § 63.139(c)(1)(i) § 63.139(f) § 63.140(a) § 63.140(b) § 63.140(c) [G]§ 63.148(d) § 63.148(e)	Compliance with this paragraph requires operation and maintenance of a cover and vent, as specified, on each opening in the individual drain system and meeting § 63.136(b)(1) through b(5) .	§ 63.139(d)(2)(i) § 63.139(e) § 63.143(a) § 63.143(e) § 63.143(e)(1) § 63.143(f) § 63.143(g) § 63.145(a) § 63.145(a)(2) § 63.148(b)(1)(ii) § 63.148(b)(2)(iii) § 63.148(b)(3) [G]§ 63.148(c) § 63.148(g) § 63.148(g)(2) § 63.148(h) § 63.148(h)(2)	§ 63.143(f) § 63.147(b)(2) § 63.147(b)(5) § 63.147(d) § 63.148(g)(2) § 63.148(h)(2) § 63.148(i)(1) § 63.148(i)(2) [G]§ 63.148(i)(4) § 63.148(i)(5) § 63.148(i)(6) [G]§ 63.152(a) [G]§ 63.152(f)	§ 63.146(b)(2) § 63.146(b)(5) § 63.146(b)(7) § 63.146(b)(7)(ii) § 63.146(b)(7)(ii)(A) § 63.146(b)(7)(ii)(B) § 63.146(c) § 63.146(e) § 63.146(e)(1) § 63.148(j) § 63.148(j)(1) [G]§ 63.151(a)(6) [G]§ 63.151(b) § 63.151(e) § 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
									§ 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(2)(iv) § 63.152(c)(3) § 63.152(c)(3)(i) § 63.152(c)(3)(ii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
FF-PS-451	EU	60QQQ-001	VOC	40 CFR Part 60, Subpart QQQ	§ 60.692-5 § 60.692-1(a) § 60.692-5(b) § 60.692-5(d) [G]§ 60.692-5(e) § 60.692-6(a) § 60.692-6(b) § 60.692-7(b)	Standard for closed vent system and control devices.	§ 60.695(a) § 60.695(a)(3) § 60.695(a)(3)(ii) § 60.696(a) [G]§ 60.696(b)	§ 60.695(a)(3) § 60.697(a) § 60.697(d) [G]§ 60.697(e) § 60.697(f)(1) [G]§ 60.697(f)(2) § 60.697(f)(3) § 60.697(f)(3)(i) § 60.697(f)(3)(ii) § 60.697(f)(3)(iii) § 60.697(f)(3)(iv) § 60.697(f)(3)(v) § 60.697(f)(3)(vi) § 60.697(f)(3)(vii) § 60.697(f)(3)(x) § 60.697(f)(3)(x)(B)	§ 60.698(b)(1) § 60.698(d) § 60.698(d)(3) § 60.698(d)(3)(ii) § 60.698(e)
FF-PS-451	CD	61FF-001	Benzene	40 CFR Part 61, Subpart FF	§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	For each closed-vent system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(d) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.349(a)(1)(ii) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
								§ 61.356(j)(3)(i)	
FF-PS-451	CD	63G-008	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.136(b) § 63.139(b) § 63.139(c)(1) § 63.139(c)(1)(i) § 63.139(f) § 63.140(a) § 63.140(b) § 63.140(c) [G]§ 63.148(d) § 63.148(e)	Compliance with this paragraph requires operation and maintenance of a cover and vent, as specified, on each opening in the individual drain system and meeting § 63.136(b)(1) through b(5) .	§ 63.139(d)(2)(i) § 63.139(e) § 63.143(a) § 63.143(e) § 63.143(e)(1) § 63.143(f) § 63.143(g) § 63.145(a) § 63.145(a)(2) § 63.148(b)(1)(ii) § 63.148(b)(2)(iii) § 63.148(b)(3) [G]§ 63.148(c) § 63.148(g) § 63.148(g)(2) § 63.148(h) § 63.148(h)(2)	§ 63.143(f) § 63.147(b)(2) § 63.147(b)(5) § 63.147(d) § 63.148(g)(2) § 63.148(h)(2) § 63.148(i)(1) § 63.148(i)(2) [G]§ 63.148(i)(4) § 63.148(i)(5) § 63.148(i)(6) [G]§ 63.152(a) [G]§ 63.152(f)	§ 63.146(b)(2) § 63.146(b)(5) § 63.146(b)(7) § 63.146(b)(7)(ii) § 63.146(b)(7)(ii)(A) § 63.146(b)(7)(ii)(B) § 63.146(c) § 63.146(e) § 63.146(e)(1) § 63.148(j) § 63.148(j)(1) [G]§ 63.151(a)(6) [G]§ 63.151(b) § 63.151(e) § 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(2)(iv) § 63.152(c)(3) § 63.152(c)(3)(i) § 63.152(c)(3)(ii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
FF-PS-457	EU	60QQQ-001	VOC	40 CFR Part 60, Subpart QQQ	§ 60.692-5 § 60.692-1(a) § 60.692-5(b) § 60.692-5(d)	Standard for closed vent system and control devices.	§ 60.695(a) § 60.695(a)(3) § 60.695(a)(3)(ii) § 60.696(a)	§ 60.695(a)(3) § 60.697(a) § 60.697(d) [G]§ 60.697(e)	§ 60.698(b)(1) § 60.698(d) § 60.698(d)(3) § 60.698(d)(3)(ii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 60.692-5(e) § 60.692-6(a) § 60.692-6(b) § 60.692-7(b)		[G]§ 60.696(b)	§ 60.697(f)(1) [G]§ 60.697(f)(2) § 60.697(f)(3) § 60.697(f)(3)(i) § 60.697(f)(3)(ii) § 60.697(f)(3)(iii) § 60.697(f)(3)(iv) § 60.697(f)(3)(v) § 60.697(f)(3)(vi) § 60.697(f)(3)(vii) § 60.697(f)(3)(x) § 60.697(f)(3)(x)(B)	§ 60.698(e)
FF-PS-457	CD	61FF-001	Benzene	40 CFR Part 61, Subpart FF	§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	For each closed-vent system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(d) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.349(a)(1)(ii) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i)	None
FF-PS-457	CD	63G-008	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.136(b) § 63.139(b) § 63.139(c)(1) § 63.139(c)(1)(i) § 63.139(f) § 63.140(a) § 63.140(b) § 63.140(c) [G]§ 63.148(d) § 63.148(e)	Compliance with this paragraph requires operation and maintenance of a cover and vent, as specified, on each opening in the individual drain system and meeting § 63.136(b)(1) through b(5) .	§ 63.139(d)(2)(i) § 63.139(e) § 63.143(a) § 63.143(e) § 63.143(e)(1) § 63.143(f) § 63.143(g) § 63.145(a) § 63.145(a)(2) § 63.148(b)(1)(ii) § 63.148(b)(2)(iii) § 63.148(b)(3) [G]§ 63.148(c)	§ 63.143(f) § 63.147(b)(2) § 63.147(b)(5) § 63.147(d) § 63.148(g)(2) § 63.148(h)(2) § 63.148(i)(1) § 63.148(i)(2) [G]§ 63.148(i)(4) § 63.148(i)(5) § 63.148(i)(6) [G]§ 63.152(a) [G]§ 63.152(f)	§ 63.146(b)(2) § 63.146(b)(5) § 63.146(b)(7) § 63.146(b)(7)(ii) § 63.146(b)(7)(ii)(A) § 63.146(b)(7)(ii)(B) § 63.146(c) § 63.146(e) § 63.146(e)(1) § 63.148(j) § 63.148(j)(1) [G]§ 63.151(a)(6) [G]§ 63.151(b)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 63.148(g) § 63.148(g)(2) § 63.148(h) § 63.148(h)(2)		§ 63.151(e) § 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(2)(iv) § 63.152(c)(3) § 63.152(c)(3)(i) § 63.152(c)(3)(ii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
FF-PS-4600	EU	60QQQ-001	VOC	40 CFR Part 60, Subpart QQQ	§ 60.692-5 § 60.692-1(a) § 60.692-5(b) § 60.692-5(d) [G]§ 60.692-5(e) § 60.692-6(a) § 60.692-6(b) § 60.692-7(b)	Standard for closed vent system and control devices.	§ 60.695(a) § 60.695(a)(3) § 60.695(a)(3)(ii) § 60.696(a) [G]§ 60.696(b)	§ 60.695(a)(3) § 60.697(a) § 60.697(d) [G]§ 60.697(e) § 60.697(f)(1) [G]§ 60.697(f)(2) § 60.697(f)(3) § 60.697(f)(3)(i) § 60.697(f)(3)(ii) § 60.697(f)(3)(iii) § 60.697(f)(3)(iv) § 60.697(f)(3)(v) § 60.697(f)(3)(vi) § 60.697(f)(3)(vii) § 60.697(f)(3)(x) § 60.697(f)(3)(x)(B)	§ 60.698(b)(1) § 60.698(d) § 60.698(d)(3) § 60.698(d)(3)(ii) § 60.698(e)
FF-PS-4600	CD	61FF-001	Benzene	40 CFR Part 61, Subpart FF	§ 61.349(a) § 61.349(a)(1)(i)	For each closed-vent system and control	§ 61.349(a)(1)(i) § 61.349(a)(1)(ii)	§ 61.349(a)(1)(ii) § 61.356(f)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	device used to comply with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 61.349(e) § 61.349(f) § 61.354(d) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i)	
FF-PS-4600	CD	63G-008	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.136(b) § 63.139(b) § 63.139(c)(1) § 63.139(c)(1)(i) § 63.139(f) § 63.140(a) § 63.140(b) § 63.140(c) [G]§ 63.148(d) § 63.148(e)	Compliance with this paragraph requires operation and maintenance of a cover and vent, as specified, on each opening in the individual drain system and meeting § 63.136(b)(1) through b(5) .	§ 63.139(d)(2)(i) § 63.139(e) § 63.143(a) § 63.143(e) § 63.143(e)(1) § 63.143(f) § 63.143(g) § 63.145(a) § 63.145(a)(2) § 63.148(b)(1)(ii) § 63.148(b)(2)(iii) § 63.148(b)(3) [G]§ 63.148(c) § 63.148(g) § 63.148(g)(2) § 63.148(h) § 63.148(h)(2)	§ 63.143(f) § 63.147(b)(2) § 63.147(b)(5) § 63.147(d) § 63.148(g)(2) § 63.148(h)(2) § 63.148(i)(1) § 63.148(i)(2) [G]§ 63.148(i)(4) § 63.148(i)(5) § 63.148(i)(6) [G]§ 63.152(a) [G]§ 63.152(f)	§ 63.146(b)(2) § 63.146(b)(5) § 63.146(b)(7) § 63.146(b)(7)(ii) § 63.146(b)(7)(ii)(A) § 63.146(b)(7)(ii)(B) § 63.146(c) § 63.146(e) § 63.146(e)(1) § 63.148(j) § 63.148(j)(1) [G]§ 63.151(a)(6) [G]§ 63.151(b) § 63.151(e) § 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(2)(iv)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
									§ 63.152(c)(3) § 63.152(c)(3)(i) § 63.152(c)(3)(ii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
FF-PS-475	EU	60QQQ-001	VOC	40 CFR Part 60, Subpart QQQ	§ 60.692-5 § 60.692-1(a) § 60.692-5(b) § 60.692-5(d) [G]§ 60.692-5(e) § 60.692-6(a) § 60.692-6(b) § 60.692-7(b)	Standard for closed vent system and control devices.	§ 60.695(a) § 60.695(a)(3) § 60.695(a)(3)(ii) § 60.696(a) [G]§ 60.696(b)	§ 60.695(a)(3) § 60.697(a) § 60.697(d) [G]§ 60.697(e) § 60.697(f)(1) [G]§ 60.697(f)(2) § 60.697(f)(3) § 60.697(f)(3)(i) § 60.697(f)(3)(ii) § 60.697(f)(3)(iii) § 60.697(f)(3)(iv) § 60.697(f)(3)(v) § 60.697(f)(3)(vi) § 60.697(f)(3)(vii) § 60.697(f)(3)(x) § 60.697(f)(3)(x)(B)	§ 60.698(b)(1) § 60.698(d) § 60.698(d)(3) § 60.698(d)(3)(ii) § 60.698(e)
FF-PS-475	CD	61FF-001	Benzene	40 CFR Part 61, Subpart FF	§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	For each closed-vent system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(d) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.349(a)(1)(ii) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i)	None
FF-PS-475	CD	63G-008	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.136(b) § 63.139(b) § 63.139(c)(1) § 63.139(c)(1)(i)	Compliance with this paragraph requires operation and maintenance of a cover	§ 63.139(d)(2)(i) § 63.139(e) § 63.143(a) § 63.143(e)	§ 63.143(f) § 63.147(b)(2) § 63.147(b)(5) § 63.147(d)	§ 63.146(b)(2) § 63.146(b)(5) § 63.146(b)(7) § 63.146(b)(7)(ii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.139(f) § 63.140(a) § 63.140(b) § 63.140(c) [G]§ 63.148(d) § 63.148(e)	and vent, as specified, on each opening in the individual drain system and meeting § 63.136(b)(1) through b(5) .	§ 63.143(e)(1) § 63.143(f) § 63.143(g) § 63.145(a) § 63.145(a)(2) § 63.148(b)(1)(ii) § 63.148(b)(2)(iii) § 63.148(b)(3) [G]§ 63.148(c) § 63.148(g) § 63.148(g)(2) § 63.148(h) § 63.148(h)(2)	§ 63.148(g)(2) § 63.148(h)(2) § 63.148(i)(1) § 63.148(i)(2) [G]§ 63.148(i)(4) § 63.148(i)(5) § 63.148(i)(6) [G]§ 63.152(a) [G]§ 63.152(f)	§ 63.146(b)(7)(ii)(A) § 63.146(b)(7)(ii)(B) § 63.146(c) § 63.146(e) § 63.146(e)(1) § 63.148(j) § 63.148(j)(1) [G]§ 63.151(a)(6) [G]§ 63.151(b) § 63.151(e) § 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(2)(iv) § 63.152(c)(3) § 63.152(c)(3)(i) § 63.152(c)(3)(ii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
FF-PS-476	EU	60QQQ -001	VOC	40 CFR Part 60, Subpart QQQ	§ 60.692-5 § 60.692-1(a) § 60.692-5(b) § 60.692-5(d) [G]§ 60.692-5(e) § 60.692-6(a) § 60.692-6(b) § 60.692-7(b)	Standard for closed vent system and control devices.	§ 60.695(a) § 60.695(a)(3) § 60.695(a)(3)(ii) § 60.696(a) [G]§ 60.696(b)	§ 60.695(a)(3) § 60.697(a) § 60.697(d) [G]§ 60.697(e) § 60.697(f)(1) [G]§ 60.697(f)(2) § 60.697(f)(3) § 60.697(f)(3)(i) § 60.697(f)(3)(ii) § 60.697(f)(3)(iii)	§ 60.698(b)(1) § 60.698(d) § 60.698(d)(3) § 60.698(d)(3)(ii) § 60.698(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
								§ 60.697(f)(3)(iv) § 60.697(f)(3)(v) § 60.697(f)(3)(vi) § 60.697(f)(3)(vii) § 60.697(f)(3)(x) § 60.697(f)(3)(x)(B)	
FF-PS-476	CD	61FF-001	Benzene	40 CFR Part 61, Subpart FF	§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	For each closed-vent system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(d) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.349(a)(1)(ii) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i)	None
FF-PS-476	CD	63G-008	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.136(b) § 63.139(b) § 63.139(c)(1) § 63.139(c)(1)(i) § 63.139(f) § 63.140(a) § 63.140(b) § 63.140(c) [G]§ 63.148(d) § 63.148(e)	Compliance with this paragraph requires operation and maintenance of a cover and vent, as specified, on each opening in the individual drain system and meeting § 63.136(b)(1) through b(5) .	§ 63.139(d)(2)(i) § 63.139(e) § 63.143(a) § 63.143(e) § 63.143(e)(1) § 63.143(f) § 63.143(g) § 63.145(a) § 63.145(a)(2) § 63.148(b)(1)(ii) § 63.148(b)(2)(iii) § 63.148(b)(3) [G]§ 63.148(c) § 63.148(g) § 63.148(g)(2) § 63.148(h) § 63.148(h)(2)	§ 63.143(f) § 63.147(b)(2) § 63.147(b)(5) § 63.147(d) § 63.148(g)(2) § 63.148(h)(2) § 63.148(i)(1) § 63.148(i)(2) [G]§ 63.148(i)(4) § 63.148(i)(5) § 63.148(i)(6) [G]§ 63.152(a) [G]§ 63.152(f)	§ 63.146(b)(2) § 63.146(b)(5) § 63.146(b)(7) § 63.146(b)(7)(ii) § 63.146(b)(7)(ii)(A) § 63.146(b)(7)(ii)(B) § 63.146(c) § 63.146(e) § 63.146(e)(1) § 63.148(j) § 63.148(j)(1) [G]§ 63.151(a)(6) [G]§ 63.151(b) § 63.151(e) § 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
									§ 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(2)(iv) § 63.152(c)(3) § 63.152(c)(3)(i) § 63.152(c)(3)(ii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
FF-PS-6400	EU	60QQQ-001	VOC	40 CFR Part 60, Subpart QQQ	§ 60.692-5 § 60.692-1(a) § 60.692-5(b) § 60.692-5(d) [G]§ 60.692-5(e) § 60.692-6(a) § 60.692-6(b) § 60.692-7(b)	Standard for closed vent system and control devices.	§ 60.695(a) § 60.695(a)(3) § 60.695(a)(3)(ii) § 60.696(a) [G]§ 60.696(b)	§ 60.695(a)(3) § 60.697(a) § 60.697(d) [G]§ 60.697(e) § 60.697(f)(1) [G]§ 60.697(f)(2) § 60.697(f)(3) § 60.697(f)(3)(i) § 60.697(f)(3)(ii) § 60.697(f)(3)(iii) § 60.697(f)(3)(iv) § 60.697(f)(3)(v) § 60.697(f)(3)(vi) § 60.697(f)(3)(vii) § 60.697(f)(3)(x) § 60.697(f)(3)(x)(B)	§ 60.698(b)(1) § 60.698(d) § 60.698(d)(3) § 60.698(d)(3)(ii) § 60.698(e)
FF-PS-6400	CD	61FF-001	Benzene	40 CFR Part 61, Subpart FF	§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b)	For each closed-vent system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(d) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.349(a)(1)(ii) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(h) § 61.356(j)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 61.349(e) § 61.349(f) § 61.349(g)			§ 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i)	
FF-PS-6400	CD	63G-008	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.136(b) § 63.139(b) § 63.139(c)(1) § 63.139(c)(1)(i) § 63.139(f) § 63.140(a) § 63.140(b) § 63.140(c) [G]§ 63.148(d) § 63.148(e)	Compliance with this paragraph requires operation and maintenance of a cover and vent, as specified, on each opening in the individual drain system and meeting § 63.136(b)(1) through b(5) .	§ 63.139(d)(2)(i) § 63.139(e) § 63.143(a) § 63.143(e) § 63.143(e)(1) § 63.143(f) § 63.143(g) § 63.145(a) § 63.145(a)(2) § 63.148(b)(1)(ii) § 63.148(b)(2)(iii) § 63.148(b)(3) [G]§ 63.148(c) § 63.148(g) § 63.148(g)(2) § 63.148(h) § 63.148(h)(2)	§ 63.143(f) § 63.147(b)(2) § 63.147(b)(5) § 63.147(d) § 63.148(g)(2) § 63.148(h)(2) § 63.148(i)(1) § 63.148(i)(2) [G]§ 63.148(i)(4) § 63.148(i)(5) § 63.148(i)(6) [G]§ 63.152(a) [G]§ 63.152(f)	§ 63.146(b)(2) § 63.146(b)(5) § 63.146(b)(7) § 63.146(b)(7)(ii) § 63.146(b)(7)(ii)(A) § 63.146(b)(7)(ii)(B) § 63.146(c) § 63.146(e) § 63.146(e)(1) § 63.148(j) § 63.148(j)(1) [G]§ 63.151(a)(6) [G]§ 63.151(b) § 63.151(e) § 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(2)(iv) § 63.152(c)(3) § 63.152(c)(3)(i) § 63.152(c)(3)(ii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
FF-PS-J-8	EU	60QQQ-001	VOC	40 CFR Part 60, Subpart QQQ	§ 60.692-5 § 60.692-1(a) § 60.692-5(b) § 60.692-5(d) [G]§ 60.692-5(e) § 60.692-6(a) § 60.692-6(b) § 60.692-7(b)	Standard for closed vent system and control devices.	§ 60.695(a) § 60.695(a)(3) § 60.695(a)(3)(ii) § 60.696(a) [G]§ 60.696(b)	§ 60.695(a)(3) § 60.697(a) § 60.697(d) [G]§ 60.697(e) § 60.697(f)(1) [G]§ 60.697(f)(2) § 60.697(f)(3) § 60.697(f)(3)(i) § 60.697(f)(3)(ii) § 60.697(f)(3)(iii) § 60.697(f)(3)(iv) § 60.697(f)(3)(v) § 60.697(f)(3)(vi) § 60.697(f)(3)(vii) § 60.697(f)(3)(x) § 60.697(f)(3)(x)(B)	§ 60.698(b)(1) § 60.698(d) § 60.698(d)(3) § 60.698(d)(3)(ii) § 60.698(e)
FF-PS-J-8	CD	61FF-001	Benzene	40 CFR Part 61, Subpart FF	§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	For each closed-vent system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(d) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.349(a)(1)(ii) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i)	None
FF-PS-J-8	CD	63G-008	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.136(b) § 63.139(b) § 63.139(c)(1) § 63.139(c)(1)(i) § 63.139(f) § 63.140(a) § 63.140(b) § 63.140(c) [G]§ 63.148(d)	Compliance with this paragraph requires operation and maintenance of a cover and vent, as specified, on each opening in the individual drain system and meeting § 63.136(b)(1) through	§ 63.139(d)(2)(i) § 63.139(e) § 63.143(a) § 63.143(e) § 63.143(e)(1) § 63.143(f) § 63.143(g) § 63.145(a) § 63.145(a)(2)	§ 63.143(f) § 63.147(b)(2) § 63.147(b)(5) § 63.147(d) § 63.148(g)(2) § 63.148(h)(2) § 63.148(i)(1) § 63.148(i)(2) [G]§ 63.148(i)(4)	§ 63.146(b)(2) § 63.146(b)(5) § 63.146(b)(7) § 63.146(b)(7)(ii) § 63.146(b)(7)(ii)(A) § 63.146(b)(7)(ii)(B) § 63.146(c) § 63.146(e) § 63.146(e)(1)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.148(e)	b(5) .	§ 63.148(b)(1)(ii) § 63.148(b)(2)(iii) § 63.148(b)(3) [G]§ 63.148(c) § 63.148(g) § 63.148(g)(2) § 63.148(h) § 63.148(h)(2)	§ 63.148(i)(5) § 63.148(i)(6) [G]§ 63.152(a) [G]§ 63.152(f)	§ 63.148(j) § 63.148(j)(1) [G]§ 63.151(a)(6) [G]§ 63.151(b) § 63.151(e) § 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(2)(iv) § 63.152(c)(3) § 63.152(c)(3)(i) § 63.152(c)(3)(ii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
FF-SC-1907	EU	60QQQ -001	VOC	40 CFR Part 60, Subpart QQQ	§ 60.692-5 § 60.692-1(a) § 60.692-5(b) § 60.692-5(d) [G]§ 60.692-5(e) § 60.692-6(a) § 60.692-6(b) § 60.692-7(b)	Standard for closed vent system and control devices.	§ 60.695(a) § 60.695(a)(3) § 60.695(a)(3)(ii) § 60.696(a) [G]§ 60.696(b)	§ 60.695(a)(3) § 60.697(a) § 60.697(d) [G]§ 60.697(e) § 60.697(f)(1) [G]§ 60.697(f)(2) § 60.697(f)(3) § 60.697(f)(3)(i) § 60.697(f)(3)(ii) § 60.697(f)(3)(iii) § 60.697(f)(3)(iv) § 60.697(f)(3)(v) § 60.697(f)(3)(vi) § 60.697(f)(3)(vii) § 60.697(f)(3)(x)	§ 60.698(b)(1) § 60.698(d) § 60.698(d)(3) § 60.698(d)(3)(ii) § 60.698(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
								§ 60.697(f)(3)(x)(B)	
FF-SC-1907	CD	61FF-001	Benzene	40 CFR Part 61, Subpart FF	§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	For each closed-vent system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(d) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.349(a)(1)(ii) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i)	None
FF-SC-1907	CD	63G-008	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.136(b) § 63.139(b) § 63.139(c)(1) § 63.139(c)(1)(i) § 63.139(f) § 63.140(a) § 63.140(b) § 63.140(c) [G]§ 63.148(d) § 63.148(e)	Compliance with this paragraph requires operation and maintenance of a cover and vent, as specified, on each opening in the individual drain system and meeting § 63.136(b)(1) through b(5) .	§ 63.139(d)(2)(i) § 63.139(e) § 63.143(a) § 63.143(e) § 63.143(e)(1) § 63.143(f) § 63.143(g) § 63.145(a) § 63.145(a)(2) § 63.148(b)(1)(ii) § 63.148(b)(2)(iii) § 63.148(b)(3) [G]§ 63.148(c) § 63.148(g) § 63.148(g)(2) § 63.148(h) § 63.148(h)(2)	§ 63.143(f) § 63.147(b)(2) § 63.147(b)(5) § 63.147(d) § 63.148(g)(2) § 63.148(h)(2) § 63.148(i)(1) § 63.148(i)(2) [G]§ 63.148(i)(4) § 63.148(i)(5) § 63.148(i)(6) [G]§ 63.152(a) [G]§ 63.152(f)	§ 63.146(b)(2) § 63.146(b)(5) § 63.146(b)(7) § 63.146(b)(7)(ii) § 63.146(b)(7)(ii)(A) § 63.146(b)(7)(ii)(B) § 63.146(c) § 63.146(e) § 63.146(e)(1) § 63.148(j) § 63.148(j)(1) [G]§ 63.151(a)(6) [G]§ 63.151(b) § 63.151(e) § 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
									§ 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(2)(iv) § 63.152(c)(3) § 63.152(c)(3)(i) § 63.152(c)(3)(ii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
FF-TETRA-1	CD	61FF-0001	Benzene	40 CFR Part 61, Subpart FF	§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	For each closed-vent system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 61.349(a)(1)(i) § 61.349(e) § 61.349(f) § 61.354(d) [G]§ 61.355(h)	§ 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(I)
FF-TETRA-2	CD	61FF-0001	Benzene	40 CFR Part 61, Subpart FF	§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	For each closed-vent system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 61.349(a)(1)(i) § 61.349(e) § 61.349(f) § 61.354(d) [G]§ 61.355(h)	§ 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(I)
FF-TK-8010	EU	60QQQ-001	VOC	40 CFR Part 60, Subpart QQQ	§ 60.692-5 § 60.692-1(a) § 60.692-5(b) § 60.692-5(d) [G]§ 60.692-5(e) § 60.692-6(a) § 60.692-6(b)	Standard for closed vent system and control devices.	§ 60.695(a) § 60.695(a)(3) § 60.695(a)(3)(ii) § 60.696(a) [G]§ 60.696(b)	§ 60.695(a)(3) § 60.697(a) § 60.697(d) [G]§ 60.697(e) § 60.697(f)(1) [G]§ 60.697(f)(2) § 60.697(f)(3)	§ 60.698(b)(1) § 60.698(d) § 60.698(d)(3) § 60.698(d)(3)(ii) § 60.698(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.692-7(b)			§ 60.697(f)(3)(i) § 60.697(f)(3)(ii) § 60.697(f)(3)(iii) § 60.697(f)(3)(iv) § 60.697(f)(3)(v) § 60.697(f)(3)(vi) § 60.697(f)(3)(vii) § 60.697(f)(3)(x) § 60.697(f)(3)(x)(B)	
FF-TK-8010	CD	61FF-001	Benzene	40 CFR Part 61, Subpart FF	§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	For each closed-vent system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(d) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.349(a)(1)(ii) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i)	None
FF-TK-8010	CD	63G-008	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.136(b) § 63.139(b) § 63.139(c)(1) § 63.139(c)(1)(i) § 63.139(f) § 63.140(a) § 63.140(b) § 63.140(c) [G]§ 63.148(d) § 63.148(e)	Compliance with this paragraph requires operation and maintenance of a cover and vent, as specified, on each opening in the individual drain system and meeting § 63.136(b)(1) through b(5) .	§ 63.139(d)(2)(i) § 63.139(e) § 63.143(a) § 63.143(e) § 63.143(e)(1) § 63.143(f) § 63.143(g) § 63.145(a) § 63.145(a)(2) § 63.148(b)(1)(ii) § 63.148(b)(2)(iii) § 63.148(b)(3) [G]§ 63.148(c) § 63.148(g) § 63.148(g)(2) § 63.148(h)	§ 63.143(f) § 63.147(b)(2) § 63.147(b)(5) § 63.147(d) § 63.148(g)(2) § 63.148(h)(2) § 63.148(i)(1) § 63.148(i)(2) [G]§ 63.148(i)(4) § 63.148(i)(5) § 63.148(i)(6) [G]§ 63.152(a) [G]§ 63.152(f)	§ 63.146(b)(2) § 63.146(b)(5) § 63.146(b)(7) § 63.146(b)(7)(ii) § 63.146(b)(7)(ii)(A) § 63.146(b)(7)(ii)(B) § 63.146(c) § 63.146(e) § 63.146(e)(1) § 63.148(j) § 63.148(j)(1) [G]§ 63.151(a)(6) [G]§ 63.151(b) § 63.151(e) § 63.151(e)(1) § 63.151(e)(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 63.148(h)(2)		§ 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(2)(iv) § 63.152(c)(3) § 63.152(c)(3)(i) § 63.152(c)(3)(ii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
FF-WORU	CD	61FF-0001	Benzene	40 CFR Part 61, Subpart FF	§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	For each closed-vent system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 61.349(a)(1)(i) § 61.349(e) § 61.349(f) § 61.354(d) [G]§ 61.355(h)	§ 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(I)
FF-WWTU	EU	60QQQ-002	VOC	40 CFR Part 60, Subpart QQQ	§ 60.692-5 § 60.692-1(a) § 60.692-5(a) § 60.692-5(d) [G]§ 60.692-5(e) § 60.692-6(a) § 60.692-6(b) § 60.692-7(b)	Standard for closed vent system and control devices.	§ 60.695(a) § 60.695(a)(1) § 60.696(a)	§ 60.695(a)(1) § 60.697(a) § 60.697(d) [G]§ 60.697(e) § 60.697(f)(1) [G]§ 60.697(f)(2) § 60.697(f)(3) § 60.697(f)(3)(i) § 60.697(f)(3)(iii) § 60.697(f)(3)(iv)	§ 60.698(b)(1) § 60.698(d) § 60.698(d)(1) § 60.698(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
								§ 60.697(f)(3)(v) § 60.697(f)(3)(vi) § 60.697(f)(3)(vii) § 60.697(f)(3)(viii)	
FF-WWTU	EU	61FF-001	Benzene	40 CFR Part 61, Subpart FF	§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(i)(A) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	For each closed-vent system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(c) § 61.354(c)(1) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.349(a)(1)(ii) § 61.354(c) § 61.354(c)(1) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(A) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i) § 61.356(j)(4)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(A)
FF-WWTU	EU	63G-008	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.136(b) § 63.139(b) § 63.139(c)(1) § 63.139(c)(1)(i) § 63.139(f) § 63.140(a) § 63.140(b) § 63.140(c) [G]§ 63.148(d) § 63.148(e)	Compliance with this paragraph requires operation and maintenance of a cover and vent, as specified, on each opening in the individual drain system and meeting § 63.136(b)(1) through b(5) .	§ 63.139(d)(2)(i) § 63.139(e) § 63.143(a) § 63.143(e) § 63.143(e)(1) § 63.143(f) § 63.143(g) § 63.145(a) § 63.145(a)(2) § 63.148(b)(1)(ii) § 63.148(b)(2)(iii) § 63.148(b)(3) [G]§ 63.148(c) § 63.148(g) § 63.148(g)(2) § 63.148(h) § 63.148(h)(2)	§ 63.143(f) § 63.147(b)(2) § 63.147(b)(5) § 63.147(d) § 63.148(g)(2) § 63.148(h)(2) § 63.148(i)(1) § 63.148(i)(2) [G]§ 63.148(i)(4) § 63.148(i)(5) § 63.148(i)(6) [G]§ 63.152(a) [G]§ 63.152(f)	§ 63.146(b)(2) § 63.146(b)(5) § 63.146(b)(7) § 63.146(b)(7)(ii) § 63.146(b)(7)(ii)(A) § 63.146(b)(7)(ii)(B) § 63.146(c) § 63.146(e) § 63.146(e)(1) § 63.148(j) § 63.148(j)(1) [G]§ 63.151(a)(6) [G]§ 63.151(b) § 63.151(e) § 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
									§ 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(2)(iv) § 63.152(c)(3) § 63.152(c)(3)(i) § 63.152(c)(3)(ii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
FIREWTR2013-1	EU	60IIII-007	CO	40 CFR Part 60, Subpart IIII	§ 60.4205(b) § 60.4202(e)(3) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218 § 94.8(a)(2)	Owners and operators of emergency stationary CI ICE, that are not fire pump engines, with a displacement of greater than or equal to 10 liters per cylinder and less than 30 liters per cylinder and is a 2007 model year and later must comply with a CO emission limit of 5.0 g/KW-hr, as stated in 40 CFR 60.4202(e)-(f) and 40 CFR 94.8(a)(2) and 40 CFR 1042.101.	§ 60.4209(a)	§ 60.4214(b)	[G]§ 60.4214(d)
FIREWTR2013-1	EU	60IIII-007	Total Hydrocarbons/NO_X	40 CFR Part 60, Subpart IIII	§ 60.4205(b) § 60.4202(e)(3) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218	Owners and operators of emergency stationary CI ICE, that are not fire pump engines, with a maximum engine power less than 3300 KW and a displacement of greater than or equal to 15 liters	§ 60.4209(a)	§ 60.4214(b)	[G]§ 60.4214(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 94.8(a)(2)	per cylinder and less than 20 liters per cylinder and is a 2013 model year must comply with a THC+NOx emission limit of 8.7 g/KW-hr, as stated in 40 CFR 60.4202(e)(3) and 40 CFR 94.8(a)(2).			
FIREWTR2013-1	EU	60IIII-007	PM	40 CFR Part 60, Subpart IIII	§ 60.4205(b) § 60.4202(e)(3) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218 § 94.8(a)(2)	Owners and operators of emergency stationary CI ICE, that are not fire pump engines, with a displacement of greater than or equal to 15 liters per cylinder and less than 30 liters per cylinder and is a 2007 - 2013 model year must comply with a PM emission limit of 0.50 g/KW-hr, as stated in 40 CFR 60.4202(e)(1), (e)(3) and 40 CFR 94.8(a)(2).	§ 60.4209(a)	§ 60.4214(b)	[G]§ 60.4214(d)
FIREWTR2013-1	EU	63ZZZZ-010	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(c)	Stationary RICE subject to Regulations under 40 CFR Part 60. An affected source that meets any of the criteria in paragraphs (c)(1) through (7) of this section must meet the requirements of this part by meeting the requirements of 40 CFR part 60 subpart IIII, for compression ignition engines or 40 CFR part 60 subpart JJJJ, for spark ignition engines as	None	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						applicable. No further requirements apply for such engines under this part.			
FIREWTR2013-2	EU	60IIII-007	CO	40 CFR Part 60, Subpart IIII	§ 60.4205(b) § 60.4202(e)(3) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218 § 94.8(a)(2)	Owners and operators of emergency stationary CI ICE, that are not fire pump engines, with a displacement of greater than or equal to 10 liters per cylinder and less than 30 liters per cylinder and is a 2007 model year and later must comply with a CO emission limit of 5.0 g/KW-hr, as stated in 40 CFR 60.4202(e)-(f) and 40 CFR 94.8(a)(2) and 40 CFR 1042.101.	§ 60.4209(a)	§ 60.4214(b)	[G]§ 60.4214(d)
FIREWTR2013-2	EU	60IIII-007	Total Hydrocarbons/NO_X	40 CFR Part 60, Subpart IIII	§ 60.4205(b) § 60.4202(e)(3) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218 § 94.8(a)(2)	Owners and operators of emergency stationary CI ICE, that are not fire pump engines, with a maximum engine power less than 3300 KW and a displacement of greater than or equal to 15 liters per cylinder and less than 20 liters per cylinder and is a 2013 model year must comply with a THC+NOx emission limit of 8.7 g/KW-hr, as stated in 40 CFR 60.4202(e)(3) and 40 CFR 94.8(a)(2).	§ 60.4209(a)	§ 60.4214(b)	[G]§ 60.4214(d)
FIREWTR2013-2	EU	60IIII-007	PM	40 CFR Part 60, Subpart IIII	§ 60.4205(b) § 60.4202(e)(3)	Owners and operators of emergency stationary CI	§ 60.4209(a)	§ 60.4214(b)	[G]§ 60.4214(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218 § 94.8(a)(2)	ICE, that are not fire pump engines, with a displacement of greater than or equal to 15 liters per cylinder and less than 30 liters per cylinder and is a 2007 - 2013 model year must comply with a PM emission limit of 0.50 g/KW-hr, as stated in 40 CFR 60.4202(e)(1), (e)(3) and 40 CFR 94.8(a)(2).			
FIREWTR2013-2	EU	63ZZZZ-010	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(c)	Stationary RICE subject to Regulations under 40 CFR Part 60. An affected source that meets any of the criteria in paragraphs (c)(1) through (7) of this section must meet the requirements of this part by meeting the requirements of 40 CFR part 60 subpart IIII, for compression ignition engines or 40 CFR part 60 subpart JJJJ, for spark ignition engines as applicable. No further requirements apply for such engines under this part.	None	None	None
FLARE-05	EU	R1111-0001	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(4)(A)	Visible emissions from a process gas flare shall not be permitted for more than five minutes in any two-hour period, except for emission	§ 111.111(a)(4)(A)(i) § 111.111(a)(4)(A)(ii)	§ 111.111(a)(4)(A)(ii)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						event emissions as provided in §101.222(b).			
FLARE-05	CD	60A-0004	Opacity	40 CFR Part 60, Subpart A	§ 60.18(b) § 60.18(c)(1) § 60.18(c)(2) § 60.18(c)(3)(ii) § 60.18(c)(4)(i) § 60.18(c)(6) § 60.18(e)	Flares shall comply with paragraphs (c)-(f) of § 60.18.	§ 60.18(d) § 60.18(f)(1) § 60.18(f)(2) § 60.18(f)(3) § 60.18(f)(4)	None	None
FLARE-05	CD	63A-0004	112(B) HAPS	40 CFR Part 63, Subpart A	§ 63.11(b)(4) § 63.11(b)(1) § 63.11(b)(2) § 63.11(b)(3) § 63.11(b)(5) § 63.11(b)(6)(ii) § 63.11(b)(7)(i)	Flares shall be designed and operated with no visible emissions, except for periods of a total of 5 minutes or less during any 2 consecutive hrs. Test Method 22 in App. A of part 60 of this chapter shall be used.	§ 63.11(b)(4) § 63.11(b)(5) § 63.11(b)(7)(i)	None	None
FLARE-05	EP	63CC-1	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.643(a) § 63.11(b) § 63.643(a)(1)	The owner or operator of a Group 1 miscellaneous process vent as defined in §63.641 shall comply with the requirements of either §63.643(a)(1)-(2).	§ 63.116(a)(2) § 63.116(a)(3) § 63.644(a) § 63.644(a)(2) § 63.644(e) § 63.645(a) § 63.645(i)	§ 63.642(e) § 63.655(h)(1) § 63.655(i)(5)	§ 63.642(f) [G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(ii) [G]§ 63.655(f)(1)(iv) [G]§ 63.655(f)(2) § 63.655(f)(4) § 63.655(g) § 63.655(g)(6) § 63.655(h) § 63.655(h)(1)
FLARE-103B	EU	R1111-0001	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(4)(A)	Visible emissions from a process gas flare shall not be permitted for more than five minutes in any two-hour period, except for upset emissions as provided in §101.222(b).	§ 111.111(a)(4)(A)(i) § 111.111(a)(4)(A)(ii)	§ 111.111(a)(4)(A)(ii)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
FLARE-103B	CD	60A-0004	Opacity	40 CFR Part 60, Subpart A	§ 60.18(b) § 60.18(c)(1) § 60.18(c)(2) § 60.18(c)(3)(ii) § 60.18(c)(4)(i) § 60.18(c)(6) § 60.18(e)	Flares shall comply with paragraphs (c)-(f) of § 60.18.	§ 60.18(d) § 60.18(f)(1) § 60.18(f)(2) § 60.18(f)(3) § 60.18(f)(4)	None	None
FLARE-103B	EU	60J-0024	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
FLARE-103B	EU	60Ja-0121	Hydrogen Sulfide	40 CFR Part 60, Subpart Ja	§ 60.100a(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 60, Subpart Ja
FLARE-103B	CD	63A-0004	112(B) HAPS	40 CFR Part 63, Subpart A	§ 63.11(b)(4) § 63.11(b)(1) § 63.11(b)(2) § 63.11(b)(3) § 63.11(b)(5) § 63.11(b)(6)(ii) § 63.11(b)(7)(i)	Flares shall be designed and operated with no visible emissions, except for periods of a total of 5 minutes or less during any 2 consecutive hrs. Test Method 22 in App. A of part 60 of this chapter shall be used.	§ 63.11(b)(4) § 63.11(b)(5) § 63.11(b)(7)(i)	None	None
FLARE-103B	EP	63CC-1	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.643(a) § 63.11(b)	The owner or operator of a Group 1 miscellaneous	§ 63.116(a)(2) § 63.116(a)(3)	§ 63.642(e) § 63.655(h)(1)	§ 63.642(f) [G]§ 63.655(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.643(a)(1)	process vent as defined in §63.641 shall comply with the requirements of either §63.643(a)(1)-(2).	§ 63.644(a) § 63.644(a)(2) § 63.644(e) § 63.645(a) § 63.645(i)	§ 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(ii) [G]§ 63.655(f)(1)(iv) [G]§ 63.655(f)(2) § 63.655(f)(4) § 63.655(g) § 63.655(g)(6) § 63.655(h) § 63.655(h)(1)
FLARE-13	EU	R1111-0001	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(4)(A)	Visible emissions from a process gas flare shall not be permitted for more than five minutes in any two-hour period, except for emission event emissions as provided in §101.222(b).	§ 111.111(a)(4)(A)(i) § 111.111(a)(4)(A)(ii)	§ 111.111(a)(4)(A)(ii)	None
FLARE-13	CD	60A-0004	Opacity	40 CFR Part 60, Subpart A	§ 60.18(b) § 60.18(c)(1) § 60.18(c)(2) § 60.18(c)(3)(ii) § 60.18(c)(4)(i) § 60.18(c)(6) § 60.18(e)	Flares shall comply with paragraphs (c)-(f) of § 60.18.	§ 60.18(d) § 60.18(f)(1) § 60.18(f)(2) § 60.18(f)(3) § 60.18(f)(4)	None	None
FLARE-13	EU	60J-0024	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1) § 60.105(a)(4)(iv) § 60.105(a)(4)(iv)(B)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.106(a)	§ 60.107(e)	§ 60.107(f) § 60.107(g)
FLARE-13	EU	60Ja-0121	Hydrogen Sulfide	40 CFR Part 60, Subpart Ja	§ 60.100a(a) The permit holder shall comply with the applicable limitation,	The permit holder shall comply with the applicable requirements of 40 CFR Part 60,	The permit holder shall comply with the applicable monitoring and testing	The permit holder shall comply with the applicable recordkeeping	The permit holder shall comply with the applicable reporting requirements of 40 CFR

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					standard and/or equipment specification requirements of 40 CFR Part 60, Subpart Ja	Subpart Ja	requirements of 40 CFR Part 60, Subpart Ja	requirements of 40 CFR Part 60, Subpart Ja	Part 60, Subpart Ja
FLARE-13	CD	63A-0004	112(B) HAPS	40 CFR Part 63, Subpart A	§ 63.11(b)(4) § 63.11(b)(1) § 63.11(b)(2) § 63.11(b)(3) § 63.11(b)(5) § 63.11(b)(6)(ii) § 63.11(b)(7)(i)	Flares shall be designed and operated with no visible emissions, except for periods of a total of 5 minutes or less during any 2 consecutive hrs. Test Method 22 in App. A of part 60 of this chapter shall be used.	§ 63.11(b)(4) § 63.11(b)(5) § 63.11(b)(7)(i)	None	None
FLARE-13	EP	63CC-1	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.643(a) § 63.11(b) § 63.643(a)(1)	The owner or operator of a Group 1 miscellaneous process vent as defined in §63.641 shall comply with the requirements of either §63.643(a)(1)-(2).	§ 63.116(a)(2) § 63.116(a)(3) § 63.644(a) § 63.644(a)(2) § 63.644(e) § 63.645(a) § 63.645(i)	§ 63.642(e) § 63.655(h)(1) § 63.655(i)(5)	§ 63.642(f) [G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(ii) [G]§ 63.655(f)(1)(iv) [G]§ 63.655(f)(2) § 63.655(f)(4) § 63.655(g) § 63.655(g)(6) § 63.655(h) § 63.655(h)(1)
FLARE-15	EU	R1111-0001	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(4)(A)	Visible emissions from a process gas flare shall not be permitted for more than five minutes in any two-hour period, except for emission event emissions as provided in §101.222(b).	§ 111.111(a)(4)(A)(i) § 111.111(a)(4)(A)(ii)	§ 111.111(a)(4)(A)(ii)	None
FLARE-15	CD	60A-0004	Opacity	40 CFR Part 60, Subpart A	§ 60.18(b) § 60.18(c)(1) § 60.18(c)(2)	Flares shall comply with paragraphs (c)-(f) of § 60.18.	§ 60.18(d) § 60.18(f)(1) § 60.18(f)(2)	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.18(c)(3)(ii) § 60.18(c)(4)(i) § 60.18(c)(6) § 60.18(e)		§ 60.18(f)(3) § 60.18(f)(4)		
FLARE-15	EU	60J-0024	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
FLARE-15	EU	60Ja-0121	Hydrogen Sulfide	40 CFR Part 60, Subpart Ja	§ 60.100a(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 60, Subpart Ja
FLARE-15	CD	63A-0004	112(B) HAPS	40 CFR Part 63, Subpart A	§ 63.11(b)(4) § 63.11(b)(1) § 63.11(b)(2) § 63.11(b)(3) § 63.11(b)(5) § 63.11(b)(6)(ii) § 63.11(b)(7)(i)	Flares shall be designed and operated with no visible emissions, except for periods of a total of 5 minutes or less during any 2 consecutive hrs. Test Method 22 in App. A of part 60 of this chapter shall be used.	§ 63.11(b)(4) § 63.11(b)(5) § 63.11(b)(7)(i)	None	None
FLARE-15	EP	63CC-1	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.643(a) § 63.11(b) § 63.643(a)(1)	The owner or operator of a Group 1 miscellaneous process vent as defined in §63.641 shall comply with the requirements of	§ 63.116(a)(2) § 63.116(a)(3) § 63.644(a) § 63.644(a)(2) § 63.644(e)	§ 63.642(e) § 63.655(h)(1) § 63.655(i)(5)	§ 63.642(f) [G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(ii) [G]§ 63.655(f)(1)(iv)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						either §63.643(a)(1)-(2).	§ 63.645(a) § 63.645(i)		[G]§ 63.655(f)(2) § 63.655(f)(4) § 63.655(g) § 63.655(g)(6) § 63.655(h) § 63.655(h)(1)
FLARE-18	EU	R1111-0001	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(4)(A)	Visible emissions from a process gas flare shall not be permitted for more than five minutes in any two-hour period, except for emission event emissions as provided in §101.222(b).	§ 111.111(a)(4)(A)(i) § 111.111(a)(4)(A)(ii)	§ 111.111(a)(4)(A)(ii)	None
FLARE-18	CD	60A-0004	Opacity	40 CFR Part 60, Subpart A	§ 60.18(b) § 60.18(c)(1) § 60.18(c)(2) § 60.18(c)(3)(ii) § 60.18(c)(4)(i) § 60.18(c)(6) § 60.18(e)	Flares shall comply with paragraphs (c)-(f) of § 60.18.	§ 60.18(d) § 60.18(f)(1) § 60.18(f)(2) § 60.18(f)(3) § 60.18(f)(4)	None	None
FLARE-18	EU	60J-0024	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
FLARE-18	EU	60Ja-0121	Hydrogen Sulfide	40 CFR Part 60, Subpart Ja	§ 60.100a(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification	The permit holder shall comply with the applicable requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 60, Subpart Ja

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					requirements of 40 CFR Part 60, Subpart Ja				
FLARE-18	CD	63A-0004	112(B) HAPS	40 CFR Part 63, Subpart A	§ 63.11(b)(4) § 63.11(b)(1) § 63.11(b)(2) § 63.11(b)(3) § 63.11(b)(5) § 63.11(b)(6)(ii) § 63.11(b)(7)(i)	Flares shall be designed and operated with no visible emissions, except for periods of a total of 5 minutes or less during any 2 consecutive hrs. Test Method 22 in App. A of part 60 of this chapter shall be used.	§ 63.11(b)(4) § 63.11(b)(5) § 63.11(b)(7)(i)	None	None
FLARE-18	EP	63CC-1	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.643(a) § 63.11(b) § 63.643(a)(1)	The owner or operator of a Group 1 miscellaneous process vent as defined in §63.641 shall comply with the requirements of either §63.643(a)(1)-(2).	§ 63.116(a)(2) § 63.116(a)(3) § 63.644(a) § 63.644(a)(2) § 63.644(e) § 63.645(a) § 63.645(i)	§ 63.642(e) § 63.655(h)(1) § 63.655(i)(5)	§ 63.642(f) [G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(ii) [G]§ 63.655(f)(1)(iv) [G]§ 63.655(f)(2) § 63.655(f)(4) § 63.655(g) § 63.655(g)(6) § 63.655(h) § 63.655(h)(1)
FLARE-19	EU	R1111-0001	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(4)(A)	Visible emissions from a process gas flare shall not be permitted for more than five minutes in any two-hour period, except for emission event emissions as provided in §101.222(b).	§ 111.111(a)(4)(A)(i) § 111.111(a)(4)(A)(ii)	§ 111.111(a)(4)(A)(ii)	None
FLARE-19	CD	60A-0004	Opacity	40 CFR Part 60, Subpart A	§ 60.18(b) § 60.18(c)(1) § 60.18(c)(2) § 60.18(c)(3)(ii) § 60.18(c)(4)(i) § 60.18(c)(6)	Flares shall comply with paragraphs (c)-(f) of § 60.18.	§ 60.18(d) § 60.18(f)(1) § 60.18(f)(2) § 60.18(f)(3) § 60.18(f)(4)	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.18(e)				
FLARE-19	EU	60J-0024	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
FLARE-19	EU	60Ja-0121	Hydrogen Sulfide	40 CFR Part 60, Subpart Ja	§ 60.100a(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 60, Subpart Ja
FLARE-19	CD	63A-0004	112(B) HAPS	40 CFR Part 63, Subpart A	§ 63.11(b)(4) § 63.11(b)(1) § 63.11(b)(2) § 63.11(b)(3) § 63.11(b)(5) § 63.11(b)(6)(ii) § 63.11(b)(7)(i)	Flares shall be designed and operated with no visible emissions, except for periods of a total of 5 minutes or less during any 2 consecutive hrs. Test Method 22 in App. A of part 60 of this chapter shall be used.	§ 63.11(b)(4) § 63.11(b)(5) § 63.11(b)(7)(i)	None	None
FLARE-19	EP	63CC-1	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.643(a) § 63.11(b) § 63.643(a)(1)	The owner or operator of a Group 1 miscellaneous process vent as defined in §63.641 shall comply with the requirements of either §63.643(a)(1)-(2).	§ 63.116(a)(2) § 63.116(a)(3) § 63.644(a) § 63.644(a)(2) § 63.644(e) § 63.645(a) § 63.645(i)	§ 63.642(e) § 63.655(h)(1) § 63.655(i)(5)	§ 63.642(f) [G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(ii) [G]§ 63.655(f)(1)(iv) [G]§ 63.655(f)(2) § 63.655(f)(4) § 63.655(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
									§ 63.655(g)(6) § 63.655(h) § 63.655(h)(1)
FLARE-20	EU	R1111-0001	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(4)(A)	Visible emissions from a process gas flare shall not be permitted for more than five minutes in any two-hour period, except for emission event emissions as provided in §101.222(b).	§ 111.111(a)(4)(A)(i) § 111.111(a)(4)(A)(ii)	§ 111.111(a)(4)(A)(ii)	None
FLARE-20	CD	60A-0004	Opacity	40 CFR Part 60, Subpart A	§ 60.18(b) § 60.18(c)(1) § 60.18(c)(2) § 60.18(c)(3)(ii) § 60.18(c)(4)(i) § 60.18(c)(6) § 60.18(e)	Flares shall comply with paragraphs (c)-(f) of § 60.18.	§ 60.18(d) § 60.18(f)(1) § 60.18(f)(2) § 60.18(f)(3) § 60.18(f)(4)	None	None
FLARE-20	EU	60J-0024	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
FLARE-20	EU	60Ja-0121	Hydrogen Sulfide	40 CFR Part 60, Subpart Ja	§ 60.100a(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 60, Subpart Ja

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
FLARE-20	CD	63A-0004	112(B) HAPS	40 CFR Part 63, Subpart A	§ 63.11(b)(4) § 63.11(b)(1) § 63.11(b)(2) § 63.11(b)(3) § 63.11(b)(5) § 63.11(b)(6)(ii) § 63.11(b)(7)(i)	Flares shall be designed and operated with no visible emissions, except for periods of a total of 5 minutes or less during any 2 consecutive hrs. Test Method 22 in App. A of part 60 of this chapter shall be used.	§ 63.11(b)(4) § 63.11(b)(5) § 63.11(b)(7)(i)	None	None
FLARE-20	EP	63CC-1	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.643(a) § 63.11(b) § 63.643(a)(1)	The owner or operator of a Group 1 miscellaneous process vent as defined in §63.641 shall comply with the requirements of either §63.643(a)(1)-(2).	§ 63.116(a)(2) § 63.116(a)(3) § 63.644(a) § 63.644(a)(2) § 63.644(e) § 63.645(a) § 63.645(i)	§ 63.642(e) § 63.655(h)(1) § 63.655(i)(5)	§ 63.642(f) [G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(ii) [G]§ 63.655(f)(1)(iv) [G]§ 63.655(f)(2) § 63.655(f)(4) § 63.655(g) § 63.655(g)(6) § 63.655(h) § 63.655(h)(1)
FLARE-22	EU	R1111-0001	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(4)(A)	Visible emissions from a process gas flare shall not be permitted for more than five minutes in any two-hour period, except for emission event emissions as provided in §101.222(b).	§ 111.111(a)(4)(A)(i) § 111.111(a)(4)(A)(ii)	§ 111.111(a)(4)(A)(ii)	None
FLARE-22	CD	60A-0004	Opacity	40 CFR Part 60, Subpart A	§ 60.18(b) § 60.18(c)(1) § 60.18(c)(2) § 60.18(c)(3)(ii) § 60.18(c)(4)(i) § 60.18(c)(6) § 60.18(e)	Flares shall comply with paragraphs (c)-(f) of § 60.18.	§ 60.18(d) § 60.18(f)(1) § 60.18(f)(2) § 60.18(f)(3) § 60.18(f)(4)	None	None
FLARE-22	EU	60J-0024	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions	§ 60.105(a)(4) § 60.105(a)(4)(i)	§ 60.105(a)(4) § 60.105(a)(4)(i)	§ 60.105(e)(3)(ii) § 60.107(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4)(iii)	§ 60.107(f) § 60.107(g)
FLARE-22	EU	60Ja-0121	Hydrogen Sulfide	40 CFR Part 60, Subpart Ja	§ 60.100a(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 60, Subpart Ja
FLARE-22	CD	63A-0004	112(B) HAPS	40 CFR Part 63, Subpart A	§ 63.11(b)(4) § 63.11(b)(1) § 63.11(b)(2) § 63.11(b)(3) § 63.11(b)(5) § 63.11(b)(6)(ii) § 63.11(b)(7)(i)	Flares shall be designed and operated with no visible emissions, except for periods of a total of 5 minutes or less during any 2 consecutive hrs. Test Method 22 in App. A of part 60 of this chapter shall be used.	§ 63.11(b)(4) § 63.11(b)(5) § 63.11(b)(7)(i)	None	None
FLARE-22	EP	63CC-1	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.643(a) § 63.11(b) § 63.643(a)(1)	The owner or operator of a Group 1 miscellaneous process vent as defined in §63.641 shall comply with the requirements of either §63.643(a)(1)-(2).	§ 63.116(a)(2) § 63.116(a)(3) § 63.644(a) § 63.644(a)(2) § 63.644(e) § 63.645(a) § 63.645(i)	§ 63.642(e) § 63.655(h)(1) § 63.655(i)(5)	§ 63.642(f) [G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(ii) [G]§ 63.655(f)(1)(iv) [G]§ 63.655(f)(2) § 63.655(f)(4) § 63.655(g) § 63.655(g)(6) § 63.655(h) § 63.655(h)(1)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
FLARE-23	EU	R1111-0001	PM (Opacity)	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(4)(A)	Visible emissions from a process gas flare shall not be permitted for more than five minutes in any two-hour period, except for emission event emissions as provided in §101.222(b).	§ 111.111(a)(4)(A)(i) § 111.111(a)(4)(A)(ii)	§ 111.111(a)(4)(A)(ii)	None
FLARE-23	CD	60A-0004	Opacity	40 CFR Part 60, Subpart A	§ 60.18(b) § 60.18(c)(1) § 60.18(c)(2) § 60.18(c)(3)(ii) § 60.18(c)(4)(i) § 60.18(c)(6) § 60.18(e)	Flares shall comply with paragraphs (c)-(f) of § 60.18.	§ 60.18(d) § 60.18(f)(1) § 60.18(f)(2) § 60.18(f)(3) § 60.18(f)(4)	None	None
FLARE-23	EU	60J-0024	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
FLARE-23	EU	60Ja-0121	Hydrogen Sulfide	40 CFR Part 60, Subpart Ja	§ 60.100a(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 60, Subpart Ja
FLARE-23	CD	63A-0004	112(B) HAPS	40 CFR Part 63, Subpart A	§ 63.11(b)(4) § 63.11(b)(1) § 63.11(b)(2)	Flares shall be designed and operated with no visible emissions, except	§ 63.11(b)(4) § 63.11(b)(5) § 63.11(b)(7)(i)	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.11(b)(3) § 63.11(b)(5) § 63.11(b)(6)(ii) § 63.11(b)(7)(i)	for periods of a total of 5 minutes or less during any 2 consecutive hrs. Test Method 22 in App. A of part 60 of this chapter shall be used.			
FLARE-23	EP	63CC-1	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.643(a) § 63.11(b) § 63.643(a)(1)	The owner or operator of a Group 1 miscellaneous process vent as defined in §63.641 shall comply with the requirements of either §63.643(a)(1)-(2).	§ 63.116(a)(2) § 63.116(a)(3) § 63.644(a) § 63.644(a)(2) § 63.644(e) § 63.645(a) § 63.645(i)	§ 63.642(e) § 63.655(h)(1) § 63.655(i)(5)	§ 63.642(f) [G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(ii) [G]§ 63.655(f)(1)(iv) [G]§ 63.655(f)(2) § 63.655(f)(4) § 63.655(g) § 63.655(g)(6) § 63.655(h) § 63.655(h)(1)
FLARE-26	EU	R1111-0001	PM (Opacity)	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(4)(A)	Visible emissions from a process gas flare shall not be permitted for more than five minutes in any two-hour period, except for emission event emissions as provided in §101.222(b).	§ 111.111(a)(4)(A)(i) § 111.111(a)(4)(A)(ii)	§ 111.111(a)(4)(A)(ii)	None
FLARE-26	CD	60A-0005	Opacity	40 CFR Part 60, Subpart A	§ 60.18(b) § 60.18(c)(1) § 60.18(c)(2) § 60.18(c)(3)(ii) § 60.18(c)(4)(iii) § 60.18(c)(6) § 60.18(e)	Flares shall comply with paragraphs (c)-(f) of § 60.18.	§ 60.18(d) § 60.18(f)(1) § 60.18(f)(2) § 60.18(f)(3) § 60.18(f)(4) § 60.18(f)(5)	None	None
FLARE-26	EU	60Ja-0121	Hydrogen Sulfide	40 CFR Part 60, Subpart Ja	§ 60.100a(a) The permit holder shall comply with the applicable limitation, standard and/or	The permit holder shall comply with the applicable requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable monitoring and testing requirements of 40	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 60, Subpart Ja

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					equipment specification requirements of 40 CFR Part 60, Subpart Ja		CFR Part 60, Subpart Ja	Part 60, Subpart Ja	
FLARE-26	CD	63A-0007	112(B) HAPS	40 CFR Part 63, Subpart A	§ 63.11(b)(4) § 63.11(b)(1) § 63.11(b)(2) § 63.11(b)(3) § 63.11(b)(5) § 63.11(b)(6)(ii) § 63.11(b)(7)(iii)	Flares shall be designed and operated with no visible emissions, except for periods of a total of 5 minutes or less during any 2 consecutive hrs. Test Method 22 in App. A of part 60 of this chapter shall be used.	§ 63.11(b)(4) § 63.11(b)(5) § 63.11(b)(7)(i)	None	None
FLARE-26	EP	63CC-1	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.643(a) § 63.11(b) § 63.643(a)(1)	The owner or operator of a Group 1 miscellaneous process vent as defined in §63.641 shall comply with the requirements of either §63.643(a)(1)-(2).	§ 63.116(a)(2) § 63.116(a)(3) § 63.644(a) § 63.644(a)(2) § 63.644(e) § 63.645(a) § 63.645(i)	§ 63.642(e) § 63.655(h)(1) § 63.655(i)(5)	§ 63.642(f) [G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(ii) [G]§ 63.655(f)(1)(iv) [G]§ 63.655(f)(2) § 63.655(f)(4) § 63.655(g) § 63.655(g)(6) § 63.655(h) § 63.655(h)(1)
F-T-L3010	EU	R5112-0003	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
F-T-L3010	EU	60QQQ-0014	VOC	40 CFR Part 60, Subpart QQQ	§ 60.692-3(a) § 60.692-1(a) § 60.692-3(a)(1) § 60.692-3(a)(2) § 60.692-3(a)(3)	Except as noted, each oil-water separator tank, slop oil tank, storage vessel, or other auxiliary equipment shall be	§ 60.692-3(a)(4) § 60.695(a) § 60.695(a)(1) § 60.696(a)	§ 60.695(a)(1) § 60.697(a) § 60.697(c) [G]§ 60.697(e) § 60.697(f)(1)	§ 60.698(b)(1) § 60.698(d) § 60.698(d)(1) § 60.698(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.692-3(a)(5) § 60.692-3(e) § 60.692-3(f) § 60.692-5(a) § 60.692-5(d) [G]§ 60.692-5(e) § 60.692-6(a) § 60.692-6(b) § 60.692-7(b)	equipped with fixed roof, meeting following specifications:		[G]§ 60.697(f)(2) § 60.697(f)(3) § 60.697(f)(3)(i) § 60.697(f)(3)(iii) § 60.697(f)(3)(iv) § 60.697(f)(3)(v) § 60.697(f)(3)(vi) § 60.697(f)(3)(vii) § 60.697(f)(3)(viii)	
F-T-L3010	EU	61FF-0027	Benzene	40 CFR Part 61, Subpart FF	§ 61.343(a)(1) § 61.343(a)(1)(i)(A) § 61.343(a)(1)(i)(B) § 61.343(c) § 61.343(d) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(i)(C) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	The owner or operator shall install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the tank to a control device.	§ 61.343(a)(1)(i)(A) § 61.343(c) § 61.349(a)(1)(i) § 61.349(e) § 61.349(f) § 61.354(c) § 61.354(c)(1) [G]§ 61.355(h)	§ 61.354(c) § 61.354(c)(1) § 61.356(d) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(A) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(4)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(A)
F-T-L3210	EU	R5112-0002	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(a)(1) § 115.112(a)(2) § 115.112(a)(2)(A) § 115.112(a)(2)(B) § 115.112(a)(2)(C) § 115.112(a)(2)(D) § 115.112(a)(2)(E) § 115.114(a)(1)(A)	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(7)	§ 115.114(a)(1)(B) § 115.118(a)(3)
F-T-L3210	EU	60QQQ-0007	VOC	40 CFR Part 60, Subpart QQQ	§ 60.692-3(d) § 60.692-1(a) § 60.692-6(a) § 60.692-6(b) § 60.692-7(b)	Storage vessels, including slop oil tanks and other auxiliary tanks that are subject to the requirements of 40 CFR subparts K, Ka, or Kb,	§ 60.692-3(a)(4) § 60.696(a)	§ 60.697(a) § 60.697(c) [G]§ 60.697(e) § 60.697(f)(1) [G]§ 60.697(f)(2)	§ 60.698(b)(1) § 60.698(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						are not subject to the requirements of this section.			
F-T-L3210	EU	61FF-0005	Benzene	40 CFR Part 61, Subpart FF	§ 61.351(a) § 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii) § 61.351(a)(1) § 61.351(b)	As an alternative to the standards for tanks specified in § 61.343, an owner or operator may elect to comply with one of the following §61.351(a)(1)-(3):	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5)	§ 60.115b § 60.115b(a)(2) § 61.356(k)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3) § 61.357(e) § 61.357(f)
F-T-L3210	EU	63G-004	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.133(a)(1)	A fixed roof shall be operated and maintained except that if the wastewater tank is used for specified purpose, then owner or operator shall comply with requirements of § 63.133(a)(2).	None	None	§ 63.146(b)(2) § 63.146(b)(5) [G]§ 63.151(b) § 63.151(e) § 63.151(e)(1) § 63.151(e)(2) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(c)(1) § 63.152(c)(4)(ii)
F-T-L3210	EU	63G-004	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(b) § 63.119(a)(1) [G]§ 63.119(b)(1) § 63.119(b)(2) § 63.119(b)(3)(i) § 63.119(b)(4) § 63.119(b)(5)(i) § 63.119(b)(5)(ii) § 63.119(b)(5)(iii) § 63.119(b)(5)(iv)	Tanks using a fixed roof and an internal floating roof (defined in §63.111) to comply with §63.119(a)(1) must comply with: §63.119(b)(1)-(6).	§ 63.120(a)(2)(i) § 63.120(a)(2)(ii)	§ 63.120(a)(4) § 63.123(a) § 63.123(c) § 63.123(g) [G]§ 63.152(a)	§ 63.120(a)(5) § 63.120(a)(6) § 63.122(d) § 63.122(d)(1)(ii) § 63.122(d)(1)(iii) § 63.122(d)(2)(ii) § 63.151(a)(7) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.119(b)(5)(v) § 63.119(b)(5)(vi) § 63.119(b)(5)(vii) [G]§ 63.119(b)(5)(viii) § 63.119(b)(6) § 63.120(a)(4) § 63.120(a)(7)				§ 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(4)(ii)
F-T-L5010	EU	R5112-0006	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
F-T-L5010	EU	60QQQ-0014	VOC	40 CFR Part 60, Subpart QQQ	§ 60.692-3(a) § 60.692-1(a) § 60.692-3(a)(1) § 60.692-3(a)(2) § 60.692-3(a)(3) § 60.692-3(a)(5) § 60.692-3(e) § 60.692-3(f) § 60.692-5(a) § 60.692-5(d) [G]§ 60.692-5(e) § 60.692-6(a) § 60.692-6(b) § 60.692-7(b)	Except as noted, each oil-water separator tank, slop oil tank, storage vessel, or other auxiliary equipment shall be equipped with fixed roof, meeting following specifications:	§ 60.692-3(a)(4) § 60.695(a) § 60.695(a)(1) § 60.696(a)	§ 60.695(a)(1) § 60.697(a) § 60.697(c) [G]§ 60.697(e) § 60.697(f)(1) [G]§ 60.697(f)(2) § 60.697(f)(3) § 60.697(f)(3)(i) § 60.697(f)(3)(iii) § 60.697(f)(3)(iv) § 60.697(f)(3)(v) § 60.697(f)(3)(vi) § 60.697(f)(3)(vii) § 60.697(f)(3)(viii)	§ 60.698(b)(1) § 60.698(d) § 60.698(d)(1) § 60.698(e)
F-T-L5010	EU	61FF-0027	Benzene	40 CFR Part 61, Subpart FF	§ 61.343(a)(1) § 61.343(a)(1)(i)(A) § 61.343(a)(1)(i)(B) § 61.343(c) § 61.343(d) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(i)(C)	The owner or operator shall install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the tank to a control device.	§ 61.343(a)(1)(i)(A) § 61.343(c) § 61.349(a)(1)(i) § 61.349(e) § 61.349(f) § 61.354(c) § 61.354(c)(1) [G]§ 61.355(h)	§ 61.354(c) § 61.354(c)(1) § 61.356(d) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(A) § 61.356(g) § 61.356(h)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(A)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)			§ 61.356(j) § 61.356(j)(1) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(4)	
F-T-L5010	EU	63G-001	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.133(a)(1)	A fixed roof shall be operated and maintained except that if the wastewater tank is used for specified purpose, then owner or operator shall comply with requirements of § 63.133(a)(2).	None	None	§ 63.146(b)(2) § 63.146(b)(5) [G]§ 63.151(b) § 63.151(e) § 63.151(e)(1) § 63.151(e)(2) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(c)(1) § 63.152(c)(4)(ii)
F-T-L5010	EU	63G-001	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(e) § 63.119(a)(1) § 63.119(e)(1) § 63.119(e)(3) § 63.119(e)(4) § 63.119(e)(5) [G]§ 63.148(d) § 63.148(e)	The owner or operator who elects to use a closed vent system and control device (defined in § 63.111) to comply with§63.119(a)(1) or (a)(2) shall comply with §63.119(e)(1)-(5).	§ 63.120(d)(1) § 63.120(d)(5) § 63.120(d)(6) § 63.148(b)(1)(ii) [G]§ 63.148(c) § 63.148(g) § 63.148(g)(2) § 63.148(h) § 63.148(h)(2)	§ 63.120(d)(1)(i) § 63.120(d)(1)(i)(A) § 63.120(d)(1)(i)(C) § 63.123(a) § 63.123(f)(1) [G]§ 63.123(f)(2) § 63.148(g)(2) § 63.148(h)(2) § 63.148(i)(1) § 63.148(i)(2) [G]§ 63.148(i)(4) § 63.148(i)(5) § 63.148(i)(6) [G]§ 63.152(a)	§ 63.120(d)(1) § 63.120(d)(2) § 63.120(d)(2)(i) § 63.120(d)(2)(ii) § 63.120(d)(3) § 63.120(d)(3)(i) § 63.120(d)(4) § 63.122(b) § 63.122(c)(1) [G]§ 63.122(g)(1) [G]§ 63.122(g)(2) § 63.148(j) § 63.151(a)(7) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
									§ 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(3) § 63.152(c)(3)(i) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
F-T-L5020	EU	R5112-0006	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
F-T-L5020	EU	60QQQ-0008	VOC	40 CFR Part 60, Subpart QQQ	§ 60.692-3(a) § 60.692-1(a) § 60.692-3(a)(1) § 60.692-3(a)(2) § 60.692-3(a)(3) § 60.692-3(a)(5) § 60.692-3(e) § 60.692-3(f) § 60.692-6(a) § 60.692-6(b) § 60.692-7(b)	Except as noted, each oil-water separator tank, slop oil tank, storage vessel, or other auxiliary equipment shall be equipped with fixed roof, meeting following specifications:	§ 60.692-3(a)(4) § 60.696(a)	§ 60.697(a) § 60.697(c) [G]§ 60.697(e) § 60.697(f)(1) [G]§ 60.697(f)(2)	§ 60.698(b)(1) § 60.698(e)
F-T-L5020	EU	63G-001	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.133(a)(1)	A fixed roof shall be operated and maintained except that if the wastewater tank is used for specified purpose, then owner or operator shall comply with requirements of § 63.133(a)(2).	None	None	§ 63.146(b)(2) § 63.146(b)(5) [G]§ 63.151(b) § 63.151(e) § 63.151(e)(1) § 63.151(e)(2) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(c)(1) § 63.152(c)(4)(ii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
F-T-L5020	EU	63G-001	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(e) § 63.119(a)(1) § 63.119(e)(1) § 63.119(e)(3) § 63.119(e)(4) § 63.119(e)(5) [G]§ 63.148(d) § 63.148(e)	The owner or operator who elects to use a closed vent system and control device (defined in § 63.111) to comply with§63.119(a)(1) or (a)(2) shall comply with §63.119(e)(1)-(5).	§ 63.120(d)(1) § 63.120(d)(5) § 63.120(d)(6) § 63.148(b)(1)(ii) [G]§ 63.148(c) § 63.148(g) § 63.148(g)(2) § 63.148(h) § 63.148(h)(2)	§ 63.120(d)(1)(i) § 63.120(d)(1)(i)(A) § 63.120(d)(1)(i)(C) § 63.123(a) § 63.123(f)(1) [G]§ 63.123(f)(2) § 63.148(g)(2) § 63.148(h)(2) § 63.148(i)(1) § 63.148(i)(2) [G]§ 63.148(i)(4) § 63.148(i)(5) § 63.148(i)(6) [G]§ 63.152(a)	§ 63.120(d)(1) § 63.120(d)(2) § 63.120(d)(2)(i) § 63.120(d)(2)(ii) § 63.120(d)(3) § 63.120(d)(3)(i) § 63.120(d)(4) § 63.122(b) § 63.122(c)(1) [G]§ 63.122(g)(1) [G]§ 63.122(g)(2) § 63.148(j) § 63.151(a)(7) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(3) § 63.152(c)(3)(i) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
GFU-241-H1	EU	63DDDD-001	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GFU-242-H	EU	63DDDDD-001	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
GFU-243-H	EU	60Ja-0161	Hydrogen Sulfide	40 CFR Part 60, Subpart Ja	§ 60.100a(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 60, Subpart Ja
GFU-243-H	EU	63DDDDD-001	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
GFU-244-HA	EU	60J-0023	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						mg/dscm (0.10 gr/dscf).			
GFU-244-HA	EU	63DDDDD-001	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
GFU-244-HB	EU	60J-0023	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
GFU-244-HB	EU	63DDDDD-001	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
GRPAPI	EU	R5131-0004	VOC	30 TAC Chapter 115, Water Separation	§ 115.132(a)(3) § 115.131(a)	VOC water separator compartments must be equipped with a vapor recovery system which satisfies the provisions of §115.131(a) of this title.	[G]§ 115.135(a) § 115.136(a)(2) § 115.136(a)(2)(A) § 115.136(a)(3) § 115.136(a)(4)	§ 115.136(a)(2) § 115.136(a)(2)(A) § 115.136(a)(3) § 115.136(a)(4)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRPAPI	EU	60QQQ-0099	VOC	40 CFR Part 60, Subpart QQQ	§ 60.692-3(a) § 60.692-1(a) § 60.692-3(a)(1) § 60.692-3(a)(2) § 60.692-3(a)(3) § 60.692-3(a)(5) § 60.692-3(b) § 60.692-3(e) § 60.692-5(a) § 60.692-5(d) [G]§ 60.692-5(e) § 60.692-6(a) § 60.692-6(b) § 60.692-7(b)	Except as noted, each oil-water separator tank, slop oil tank, storage vessel, or other auxiliary equipment shall be equipped with fixed roof, meeting following specifications:	§ 60.692-3(a)(4) § 60.695(a) § 60.695(a)(1) § 60.696(a)	§ 60.695(a)(1) § 60.697(a) § 60.697(c) § 60.697(d) [G]§ 60.697(e) § 60.697(f)(1) [G]§ 60.697(f)(2) § 60.697(f)(3) § 60.697(f)(3)(i) § 60.697(f)(3)(iii) § 60.697(f)(3)(iv) § 60.697(f)(3)(v) § 60.697(f)(3)(vi) § 60.697(f)(3)(vii) § 60.697(f)(3)(viii)	§ 60.698(b)(1) § 60.698(d) § 60.698(d)(1) § 60.698(e)
GRPAPI	EU	61FF-1657	Benzene	40 CFR Part 61, Subpart FF	§ 61.347(a)(1) § 61.347(a)(1)(i)(A) § 61.347(a)(1)(i)(B) § 61.347(b) § 61.347(c) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(i)(C) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	Install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the oil-water separator to a control device.	§ 61.347(a)(1)(i)(A) § 61.347(b) § 61.349(a)(1)(i) § 61.349(e) § 61.349(f) § 61.354(c) § 61.354(c)(1) [G]§ 61.355(h)	§ 61.354(c) § 61.354(c)(1) § 61.356(d) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(A) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(4)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(A)
GRPAPI	EU	63G-007	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.137(a)(1) § 63.132(a)(2)(i)(A) § 63.132(a)(2)(i)(B) [G]§ 63.132(f) § 63.137(b)(1)(ii) § 63.137(d) § 63.137(e)(3) § 63.137(f)	A fixed roof and a closed vent system that routes the organic hazardous air pollutants vapors vented from the oil-water separator to a control device and which meets §63.137(b).	[G]§ 63.137(e)(1) § 63.137(e)(2) § 63.137(e)(3) § 63.139(d)(2)(i) § 63.139(e) § 63.143(a) § 63.143(e) § 63.143(e)(1)	§ 63.143(f) § 63.147(b) § 63.147(b)(1) § 63.147(b)(2) § 63.147(b)(5) § 63.147(d) § 63.148(g)(2) § 63.148(h)(2)	§ 63.146(b)(2) § 63.146(b)(5) § 63.146(b)(6) § 63.146(b)(7) § 63.146(b)(7)(ii) § 63.146(b)(7)(ii)(A) § 63.146(b)(7)(ii)(B) § 63.146(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.139(b) § 63.139(c)(1) § 63.139(c)(1)(i) § 63.139(f) § 63.140(a) § 63.140(b) § 63.140(c) § 63.144(a) [G]§ 63.148(d) § 63.148(e)		§ 63.143(f) § 63.143(g) § 63.145(a) § 63.145(a)(2) § 63.148(b)(1)(ii) § 63.148(b)(2)(iii) § 63.148(b)(3) [G]§ 63.148(c) § 63.148(g) § 63.148(g)(2) § 63.148(h) § 63.148(h)(2)	§ 63.148(i)(1) § 63.148(i)(2) [G]§ 63.148(i)(4) § 63.148(i)(5) § 63.148(i)(6) [G]§ 63.152(a) [G]§ 63.152(f)	§ 63.146(e) § 63.146(e)(1) § 63.148(j) § 63.148(j)(1) [G]§ 63.151(b) § 63.151(e) § 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) [G]§ 63.152(b)(2) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(2)(iv) § 63.152(c)(3) § 63.152(c)(3)(i) § 63.152(c)(3)(ii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
GRPAPI	EU	63VV-0001	112(B) HAPS	40 CFR Part 63, Subpart VV	[G]§ 63.1043(b) [G]§ 63.1043(c) [G]§ 63.1047(b) [G]§ 63.1047(d)	The separator shall be equipped with a floating roof designed to meet the specifications listed in §63.1043(b)(1)-(4).	[G]§ 63.1046(b) [G]§ 63.1047(b)	[G]§ 63.1048(a) § 63.1048(b)	§ 63.1049(a)
GRP-C8456	EU	R5112-0010	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRPCC2VENT	EP	R5131-1000	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
GRPCC2VENT	EP	R5131-1000	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(B) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream specified in § 115.121(a)(1) of this title with a concentration of VOC < 612 ppmv is exempt from § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
GRPCC2VENT	EP	63CC-1010	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.643(a) § 63.11(b) § 63.643(a)(1)	The owner or operator of a Group 1 miscellaneous process vent as defined in §63.641 shall comply with the requirements of either §63.643(a)(1)-(2).	§ 63.116(a)(2) § 63.116(a)(3) § 63.644(a) § 63.644(a)(2) § 63.644(e) § 63.645(a) § 63.645(i)	§ 63.642(e) § 63.655(h)(1) § 63.655(i)(5)	§ 63.642(f) [G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(ii) [G]§ 63.655(f)(1)(iv) [G]§ 63.655(f)(2) § 63.655(f)(4) § 63.655(g) § 63.655(g)(6) § 63.655(h) § 63.655(h)(1)
GRPCCEFRMS	EU	R5112-0004	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(a)(1) § 115.112(a)(2) § 115.112(a)(2)(A) § 115.112(a)(2)(B) § 115.112(a)(2)(C) § 115.112(a)(2)(D) § 115.112(a)(2)(E) § 115.112(a)(2)(F) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRPCCEFRMS	EU	63CC-0254	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
GRPCCEFRMS	EU	63CC-1254	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.119(a)(1) § 63.119(c)(1) § 63.119(c)(1)(i) § 63.119(c)(1)(ii) § 63.119(c)(1)(iii) [G]§ 63.119(c)(3) § 63.119(c)(4) § 63.120(b)(10)(i) § 63.120(b)(5)(i) § 63.120(b)(5)(ii) § 63.120(b)(6)(i) § 63.120(b)(6)(ii) [G]§ 63.120(b)(7) § 63.120(b)(8) [G]§ 63.646(f) § 63.646(g)	Each owner or operator of a Group 1 storage vessel subject to this subpart shall comply with the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.120(b)(1)(i) § 63.120(b)(1)(iii) § 63.120(b)(1)(iv) § 63.120(b)(10) § 63.120(b)(2)(i) § 63.120(b)(2)(ii) § 63.120(b)(2)(iii) § 63.120(b)(3) § 63.120(b)(4) § 63.646(b)(1) § 63.646(e)	[G]§ 63.120(b)(7) § 63.120(b)(8) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1) § 63.655(i)(5)	§ 63.120(b)(10)(ii) § 63.120(b)(10)(iii) § 63.120(b)(9) § 63.642(f) § 63.655(f) [G]§ 63.655(f)(1)(i)(B) § 63.655(f)(6) § 63.655(g) [G]§ 63.655(g)(3) § 63.655(h) § 63.655(h)(1) § 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(B) § 63.655(h)(2)(i)(C) § 63.655(h)(2)(ii) [G]§ 63.655(h)(6)
GRP-CCFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(6)	Components at a petroleum refinery or synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process, that contact a process fluid that contains less than 10% VOC by weight and components at a natural gas/gasoline processing operation that contact a process	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						fluid that contains less than 1.0% VOC by weight are exempt from the requirements of this division except §115.356(3)(C) of this title.			
GRP-CCFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(5)	Reciprocating compressors and positive displacement pumps used in natural gas/gasoline processing operations are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
GRP-CCFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(10)	Instrumentation systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet 40 CFR §63.169 (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
GRP-CCFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(11)	Sampling connection systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet the requirements of 40 CFR §63.166(a) and (b) (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						title.			
GRP-CCFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(13)	Components/systems that contact a process fluid containing VOC having a true vapor pressure equal to or less than 0.002 psia at 68 degrees Fahrenheit are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
GRP-CCFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(2) § 115.352(9)	Each pressure relief valve equipped with a rupture disk must comply with §115.352(9) and §115.356(3)(C).	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
GRP-CCFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.353(a) § 115.353(b) § 115.910	For all affected persons in the Beaumont-Port Arthur, Dallas-Fort Worth, El Paso, and Houston-Galveston areas, as defined in §115.10, any alternate methods of demonstrating and documenting continuous compliance with the applicable control requirements or exemption criteria in this division may be approved by the executive director in accordance with §115.910 if emission reductions are	None	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						demonstrated to be substantially equivalent.			
GRP-CCFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(C) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.352(8) § 115.357(8) § 115.358(c)(1) [G]§ 115.358(h)	No component shall be allowed to have a VOC leak, for more than 15 days, after discovery. If the owner or operator elects to use the alternative work practice in §115.358 of this title, any leak detected as defined in §115.358 of this title, including any leak detected using the alternative work practice on a component that is subject to the requirements of this division but not specifically selected for alternative work practice monitoring.	§ 115.354(1) § 115.354(11) § 115.354(13)(A) § 115.354(13)(B) § 115.354(13)(C) § 115.354(13)(D) § 115.354(13)(E) § 115.354(13)(F) § 115.354(4) § 115.354(5) § 115.354(9) [G]§ 115.355 § 115.358(c)(2) § 115.358(d) [G]§ 115.358(e) § 115.358(f)	§ 115.352(7) § 115.354(13)(D) § 115.354(13)(E) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) [G]§ 115.356(4) § 115.356(5)	[G]§ 115.358(g)
GRP-CCFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7) § 115.357(1)	No process drains shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
GRP-CCFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery &	§ 115.352(1)(A) § 115.352(1) § 115.352(10)	No process drains shall be allowed to have a VOC leak, for more than	§ 115.354(1) § 115.354(10) § 115.354(5)	§ 115.352(7) § 115.354(10) § 115.356	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Petrochemicals	§ 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7)	15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(6) § 115.354(9) [G]§ 115.355	[G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(5)	
GRP-CCFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(9) § 115.357(1) § 115.357(8) § 115.357(9)	No pressure relief valves shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
GRP-CCFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(9) § 115.357(12) § 115.357(8) § 115.357(9)	No pressure relief valves shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-CCFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(8) § 115.357(9)	No open-ended valves or lines shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
GRP-CCFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8) § 115.357(9)	No open-ended valves or lines shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
GRP-CCFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6)	No valves shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(7) § 115.357(1) § 115.357(8) § 115.357(9)	or exuding of process fluid based on sight, smell, or sound.			
GRP-CCFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8) § 115.357(9)	No valves shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
GRP-CCFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(8) § 115.357(1) § 115.357(12) § 115.357(8)	No flanges or other connectors shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
GRP-CCFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3)	No flanges or other connectors shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(5) § 115.352(7) § 115.352(8) § 115.357(12) § 115.357(8)	screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	
GRP-CCFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(7) § 115.357(1) § 115.357(12) § 115.357(8)	No agitators shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
GRP-CCFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(7) § 115.357(1) § 115.357(12) § 115.357(8)	No agitators shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
GRP-CCFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet.	§ 115.352(1)(A) § 115.352(1)	No agitators shall be allowed to have a VOC	§ 115.354(1) § 115.354(10)	§ 115.352(7) § 115.354(10)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Refinery & Petrochemicals	§ 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(7) § 115.357(12) § 115.357(8)	leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	
GRP-CCFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(3) § 115.357(8)	No compressor seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None
GRP-CCFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(4)	No compressor seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.357(8)	sound.			
GRP-CCFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1) § 115.357(8)	No compressor seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None
GRP-CCFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	No compressor seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
GRP-CCFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii)	No pump seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(3) § 115.352(5) § 115.352(7) § 115.357(4) § 115.357(8)	background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.			
GRP-CCFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1) § 115.357(8)	No pump seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None
GRP-CCFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	No pump seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
GRP-CCFUG	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(c)(1) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g)	Comply with the specified Subpart H requirements for pumps in light liquid service, instrument readings that	[G]§ 63.163 [G]§ 63.176 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.162(h) [G]§ 63.163 [G]§ 63.171 [G]§ 63.176 § 63.648(f) § 63.655(d)(2)	define a leak are specified in Subpart CC, table 2.	§ 63.648(c)(3) § 63.648(c)(4) § 63.648(c)(6) § 63.648(c)(7) § 63.648(c)(8)	[G]§ 63.181(h)(3) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(8) § 63.181(h)(9) § 63.648(h) § 63.655(d)(1)(i) § 63.655(d)(6) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(v)
GRP-CCFUG	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for non-reciprocating pumps in heavy liquid service.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(6)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
GRP-CCFUG	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.164 [G]§ 63.171 § 63.648(i) § 63.655(d)(2)	Comply with the specified Subpart H requirements for compressors which are not in hydrogen service.	[G]§ 63.164 [G]§ 63.180(b) [G]§ 63.180(c) [G]§ 63.180(d) [G]§ 63.648(b)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(f) § 63.648(h) § 63.655(d)(1)(i) § 63.655(d)(6) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
GRP-CCFUG	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.165 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for pressure relief devices in gas/vapor service.	[G]§ 63.165 [G]§ 63.180(b) [G]§ 63.180(c) [G]§ 63.180(d) [G]§ 63.648(b)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(f) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-CCFUG	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for pressure relief device in liquid service.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(6)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
GRP-CCFUG	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.166 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for sampling connection systems.	[G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(i) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
GRP-CCFUG	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.167 [G]§ 63.171 [G]§ 63.175 § 63.655(d)(2)	Comply with the specified Subpart H requirements for open-ended valves and lines.	[G]§ 63.175 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(9) [G]§ 63.181(i) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
GRP-CCFUG	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(c)(1) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h)	Comply with the specified Subpart H requirements for valves in gas/vapor and light liquid service, instrument readings defining a leak	[G]§ 63.168 [G]§ 63.175 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(1)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e) § 63.655(f)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 63.168 [G]§ 63.171 [G]§ 63.175 § 63.648(c)(9) § 63.655(d)(2)	are specified in Subpart CC, table 2.	§ 63.648(c)(3) § 63.648(c)(4) § 63.648(c)(8)	[G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(9) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 63.655(f)(1)(v)
GRP-CCFUG	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for valves in heavy liquid service.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(6)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
GRP-CCFUG	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(c)(5) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.649(a) § 63.655(d)(2)	Connectors in gas/vapor or light liquid are subject to the requirements in heavy liquid service in §63.169. The leak definition for specified systems subject to §63.169 is 1,000 parts per million.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(4)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(v)
GRP-CCFUG	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for connectors in heavy liquid service.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(6)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-CCFUG	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 § 63.655(d)(2)	Comply with the specified Subpart H requirements for instrumentation systems.	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.648(b) § 63.648(c)(2)(i) § 63.648(c)(6)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 63.182(a) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(d) [G]§ 63.655(e)
GRP-CCFUG	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	[G]§ 63.648(g)	Compressors in hydrogen service are exempt from the requirements of §63.648(a) and (c), if an owner or operator demonstrates that a compressor is in hydrogen service. §63.648(g)(1)-(2).	[G]§ 63.648(g)	§ 63.648(h) § 63.655(d)(3)	None
GRPCCIFRMS	EU	R5112-0001	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(a)(1) § 115.112(a)(2) § 115.112(a)(2)(A) § 115.112(a)(2)(B) § 115.112(a)(2)(C) § 115.112(a)(2)(D) § 115.112(a)(2)(E) § 115.114(a)(1)(A)	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(7)	§ 115.114(a)(1)(B) § 115.118(a)(3)
GRPCCIFRMS	EU	63CC-0250	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.119(a)(1) [G]§ 63.119(b)(1) § 63.119(b)(2) § 63.119(b)(3)(ii) § 63.119(b)(4) § 63.120(a)(4) § 63.120(a)(7) [G]§ 63.646(f) § 63.646(g)	Each owner or operator of a Group 1 storage vessel subject to this subpart shall comply with the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.120(a)(2)(i) § 63.120(a)(2)(ii) § 63.646(b)(1) § 63.646(e)	§ 63.120(a)(4) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1) § 63.655(i)(5)	§ 63.120(a)(5) § 63.120(a)(6) § 63.642(f) § 63.655(f) [G]§ 63.655(f)(1)(i)(B) § 63.655(f)(6) § 63.655(g) § 63.655(g)(2) [G]§ 63.655(g)(2)(i) [G]§ 63.655(g)(2)(ii) § 63.655(h)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
									§ 63.655(h)(1) § 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(B) § 63.655(h)(2)(i)(C) [G]§ 63.655(h)(6)
GRPCONE1	EU	R5112-0006	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
GRPCONE1	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
GRPCOOL	EU	63CC-3000	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.654(a) § 63.640(h)(6)	Except as specified in paragraph (b) of this section, the owner or operator of a heat exchange system that meets the criteria in §63.640(c)(8) must comply with the requirements of paragraphs (c) through (g) of this section.	§ 63.642(d)(1) § 63.642(d)(3) § 63.642(d)(4) [G]§ 63.654(c) [G]§ 63.654(d) § 63.654(e) [G]§ 63.654(f) [G]§ 63.654(g)	§ 63.642(e) § 63.655(h)(1) [G]§ 63.655(i)(4) § 63.655(i)(5)	§ 63.642(d)(2) § 63.642(f) § 63.655(f) § 63.655(f)(1)(vi) § 63.655(f)(4) § 63.655(g) [G]§ 63.655(g)(9) § 63.655(h)(1)
GRPFFEFRMS	EU	R5112-0004	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(a)(1) § 115.112(a)(2) § 115.112(a)(2)(A) § 115.112(a)(2)(B) § 115.112(a)(2)(C)	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.112(a)(2)(D) § 115.112(a)(2)(E) § 115.112(a)(2)(F) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	control device specified in Table I(a) or Table II(a).			
GRPFFEFRMS	EU	61FF-0006	Benzene	40 CFR Part 61, Subpart FF	§ 61.351(a) [G]§ 60.112b(a)(2) § 61.351(a)(2) § 61.351(b)	As an alternative to the standards for tanks specified in § 61.343, an owner or operator may elect to comply with one of the following §61.351(a)(1)-(3):	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6)	§ 60.115b [G]§ 60.115b(b)(3) § 61.356(k)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 61.357(e) § 61.357(f)
GRPFFEFRMS	EU	63CC-0082	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
GRPFFEFRMS	EU	63CC-0182	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.119(a)(1) § 63.119(c)(1) § 63.119(c)(1)(i) § 63.119(c)(1)(ii) § 63.119(c)(1)(iii) [G]§ 63.119(c)(3) § 63.119(c)(4) § 63.120(b)(10)(i) § 63.120(b)(5)(i) § 63.120(b)(5)(ii) § 63.120(b)(6)(i) § 63.120(b)(6)(ii) [G]§ 63.120(b)(7)	Each owner or operator of a Group 1 storage vessel subject to this subpart shall comply with the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.120(b)(1)(i) § 63.120(b)(1)(iii) § 63.120(b)(1)(iv) § 63.120(b)(10) § 63.120(b)(2)(i) § 63.120(b)(2)(ii) § 63.120(b)(2)(iii) § 63.120(b)(3) § 63.120(b)(4) § 63.646(b)(1) § 63.646(e)	[G]§ 63.120(b)(7) § 63.120(b)(8) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1) § 63.655(i)(5)	§ 63.120(b)(10)(ii) § 63.120(b)(10)(iii) § 63.120(b)(9) § 63.642(f) § 63.655(f) [G]§ 63.655(f)(1)(i)(B) § 63.655(f)(6) § 63.655(g) [G]§ 63.655(g)(3) § 63.655(h) § 63.655(h)(1) § 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(B)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.120(b)(8) [G]§ 63.646(f) § 63.646(g)				§ 63.655(h)(2)(i)(C) § 63.655(h)(2)(ii) [G]§ 63.655(h)(6)
GRPFFIFRMS	EU	R5112-0001	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(a)(1) § 115.112(a)(2) § 115.112(a)(2)(A) § 115.112(a)(2)(B) § 115.112(a)(2)(C) § 115.112(a)(2)(D) § 115.112(a)(2)(E) § 115.114(a)(1)(A)	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(7)	§ 115.114(a)(1)(B) § 115.118(a)(3)
GRPFFIFRMS	EU	61FF-0005	Benzene	40 CFR Part 61, Subpart FF	§ 61.351(a) § 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii) § 61.351(a)(1) § 61.351(b)	As an alternative to the standards for tanks specified in § 61.343, an owner or operator may elect to comply with one of the following §61.351(a)(1)-(3):	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5)	§ 60.115b § 60.115b(a)(2) § 61.356(k)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3) § 61.357(e) § 61.357(f)
GRPFFIFRMS	EU	63CC-0082	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) § 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) [G]§ 60.116b(e)(3) § 60.116b(f)(1) § 63.640(n)(8)(ii)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRPFFIFRMS	EU	63G-006	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.133(a)(1)	A fixed roof shall be operated and maintained except that if the wastewater tank is used for specified purpose, then owner or operator shall comply with requirements of § 63.133(a)(2).	None	None	§ 63.146(b)(2) § 63.146(b)(5) [G]§ 63.151(b) § 63.151(e) § 63.151(e)(1) § 63.151(e)(2) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(c)(1) § 63.152(c)(4)(ii)
GRPFFIFRMS	EU	63G-006	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(b) § 63.119(a)(1) [G]§ 63.119(b)(1) § 63.119(b)(2) § 63.119(b)(3)(ii) § 63.119(b)(4) § 63.119(b)(5)(i) § 63.119(b)(5)(ii) § 63.119(b)(5)(iii) § 63.119(b)(5)(iv) § 63.119(b)(5)(v) § 63.119(b)(5)(vi) § 63.119(b)(5)(vii) [G]§ 63.119(b)(5)(viii) § 63.119(b)(6) § 63.120(a)(4) § 63.120(a)(7)	Tanks using a fixed roof and an internal floating roof (defined in §63.111) to comply with §63.119(a)(1) must comply with: §63.119(b)(1)-(6).	§ 63.120(a)(2)(i) § 63.120(a)(2)(ii)	§ 63.120(a)(4) § 63.123(a) § 63.123(c) § 63.123(g) [G]§ 63.152(a)	§ 63.120(a)(5) § 63.120(a)(6) § 63.122(d) § 63.122(d)(1)(ii) § 63.122(d)(1)(iii) § 63.122(d)(2)(ii) § 63.151(a)(7) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(4)(ii)
GRP-FUGCC	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(6)	Components at a petroleum refinery or synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process, that contact a process fluid that contains less than 10% VOC by weight	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						and components at a natural gas/gasoline processing operation that contact a process fluid that contains less than 1.0% VOC by weight are exempt from the requirements of this division except §115.356(3)(C) of this title.			
GRP-FUGCC	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(5)	Reciprocating compressors and positive displacement pumps used in natural gas/gasoline processing operations are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
GRP-FUGCC	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(10)	Instrumentation systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet 40 CFR §63.169 (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
GRP-FUGCC	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(11)	Sampling connection systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet the requirements of 40 CFR §63.166(a) and (b) (June 20, 1996) are	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						exempt from the requirements of this division except §115.356(3)(C) of this title.			
GRP-FUGCC	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(13)	Components/systems that contact a process fluid containing VOC having a true vapor pressure equal to or less than 0.002 psia at 68 degrees Fahrenheit are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
GRP-FUGCC	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(2) § 115.352(9)	Each pressure relief valve equipped with a rupture disk must comply with §115.352(9) and §115.356(3)(C).	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
GRP-FUGCC	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.353(a) § 115.353(b) § 115.910	For all affected persons in the Beaumont-Port Arthur, Dallas-Fort Worth, El Paso, and Houston-Galveston areas, as defined in §115.10, any alternate methods of demonstrating and documenting continuous compliance with the applicable control requirements or exemption criteria in this division may be approved by the	None	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						executive director in accordance with §115.910 if emission reductions are demonstrated to be substantially equivalent.			
GRP-FUGCC	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(C) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.352(8) § 115.357(8) § 115.358(c)(1) [G]§ 115.358(h)	No component shall be allowed to have a VOC leak, for more than 15 days, after discovery. If the owner or operator elects to use the alternative work practice in §115.358 of this title, any leak detected as defined in §115.358 of this title, including any leak detected using the alternative work practice on a component that is subject to the requirements of this division but not specifically selected for alternative work practice monitoring.	§ 115.354(1) § 115.354(11) § 115.354(13)(A) § 115.354(13)(B) § 115.354(13)(C) § 115.354(13)(D) § 115.354(13)(E) § 115.354(13)(F) § 115.354(4) § 115.354(5) § 115.354(9) [G]§ 115.355 § 115.358(c)(2) § 115.358(d) [G]§ 115.358(e) § 115.358(f)	§ 115.352(7) § 115.354(13)(D) § 115.354(13)(E) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) [G]§ 115.356(4) § 115.356(5)	[G]§ 115.358(g)
GRP-FUGCC	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7) § 115.357(1)	No process drains shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight,	§ 115.354(1) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						smell, or sound.			
GRP-FUGCC	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7)	No process drains shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(5)	None
GRP-FUGCC	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(9) § 115.357(1) § 115.357(8) § 115.357(9)	No pressure relief valves shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
GRP-FUGCC	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(9)	No pressure relief valves shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane,	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.357(12) § 115.357(8) § 115.357(9)	or the dripping or exuding of process fluid based on sight, smell, or sound.			
GRP-FUGCC	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(8) § 115.357(9)	No open-ended valves or lines shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
GRP-FUGCC	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8) § 115.357(9)	No open-ended valves or lines shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
GRP-FUGCC	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B)	No valves shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C)	[G]§ 115.354(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(8) § 115.357(9)	greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	[G]§ 115.355 § 115.357(1)	§ 115.356(5)	
GRP-FUGCC	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8) § 115.357(9)	No valves shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
GRP-FUGCC	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(8) § 115.357(1) § 115.357(12) § 115.357(8)	No flanges or other connectors shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
GRP-FUGCC	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet.	§ 115.352(1)(A) § 115.352(1)	No flanges or other connectors shall be	§ 115.354(1) § 115.354(10)	§ 115.352(7) § 115.354(10)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Refinery & Petrochemicals	§ 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(8) § 115.357(12) § 115.357(8)	allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	
GRP-FUGCC	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(7) § 115.357(1) § 115.357(12) § 115.357(8)	No agitators shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
GRP-FUGCC	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(7) § 115.357(1)	No agitators shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight,	§ 115.354(1) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.357(12) § 115.357(8)	smell, or sound.			
GRP-FUGCC	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(7) § 115.357(12) § 115.357(8)	No agitators shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
GRP-FUGCC	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(3) § 115.357(8)	No compressor seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None
GRP-FUGCC	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii)	No compressor seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(3) § 115.352(5) § 115.352(7) § 115.357(4) § 115.357(8)	background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.			
GRP-FUGCC	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1) § 115.357(8)	No compressor seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None
GRP-FUGCC	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	No compressor seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
GRP-FUGCC	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A)	No pump seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(4) § 115.357(8)	screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.		[G]§ 115.356(3)(C) § 115.356(5)	
GRP-FUGCC	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1) § 115.357(8)	No pump seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None
GRP-FUGCC	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	No pump seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
GRP-FUGCC	EU	63CCV	112(B)	40 CFR Part 63,	§ 63.648(a)	Comply with the	None	§ 60.486(e)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		V-ALL	HAPS	Subpart CC	§ 60.482-1(d)	specified 40 CFR Part 60, Subpart VV requirements for equipment in vacuum service.		§ 60.486(e)(1) § 60.486(e)(5)	
GRP-FUGCC	EU	63CCV V-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-2 [G]§ 60.482-9 § 63.648(a)(2) § 63.648(f) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pumps in light liquid service complying with §60.482-2.	[G]§ 60.482-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(d)(6) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
GRP-FUGCC	EU	63CCV V-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-3 [G]§ 60.482-9 § 63.648(a)(2) § 63.648(i) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for compressors complying with §60.482-3.	[G]§ 60.482-3 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(d)(6) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
GRP-FUGCC	EU	63CCV V-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) § 60.482-4(a) § 60.482-4(b)(1) [G]§ 60.482-9 § 63.648(a)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pressure relief devices in gas/vapor service.	§ 60.482-4(b)(2) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(3) [G]§ 60.486(e)(4) § 60.486(j) § 63.648(h)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.655(d)(2)			§ 63.655(d)(1)(i) § 63.655(i)(5)	
GRP-FUGCC	EU	63CCV V-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-5 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for sampling connection systems complying with §60.482-5.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
GRP-FUGCC	EU	63CCV V-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-6 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for open-ended valves or lines complying with §60.482-6.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
GRP-FUGCC	EU	63CCV V-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-7 [G]§ 60.482-9 [G]§ 60.483-1 [G]§ 60.483-2 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for valves in gas/vapor service or in light liquid service complying with §60.482-7.	[G]§ 60.482-7 [G]§ 60.483-1 [G]§ 60.483-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) [G]§ 60.486(g) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(d) § 60.487(e)
GRP-FUGCC	EU	63CCV V-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for valves in heavy liquid service complying with §60.482-8.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
								§ 63.655(i)(5)	
GRP-FUGCC	EU	63CCV V-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pumps in heavy liquid service complying with §60.482-8.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
GRP-FUGCC	EU	63CCV V-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for flanges or other connectors complying with §60.482-8.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
GRP-FUGCC	EU	63CCV V-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pressure relief devices in light liquid service complying with §60.482-8.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
GRP-FUGCC	EU	63CCV V-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pressure relief devices in heavy liquid service complying with §60.482-8.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-FUGCC	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	[G]§ 63.648(g)	Compressors in hydrogen service are exempt from the requirements of §63.648(a) and (c), if an owner or operator demonstrates that a compressor is in hydrogen service. §63.648(g)(1)-(2).	[G]§ 63.648(g)	§ 63.648(h) § 63.655(d)(3) § 63.655(i)(5)	None
GRPGEFRMS	EU	R5112-0004	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(a)(1) § 115.112(a)(2) § 115.112(a)(2)(A) § 115.112(a)(2)(B) § 115.112(a)(2)(C) § 115.112(a)(2)(D) § 115.112(a)(2)(E) § 115.112(a)(2)(F) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)
GRPGEFRMS	EU	60QQQ-0006	VOC	40 CFR Part 60, Subpart QQQ	§ 60.693-2(a) § 60.692-1(a) § 60.692-6(a) § 60.692-6(b) § 60.692-7(b) § 60.693-2(a)(1) § 60.693-2(a)(1)(i) § 60.693-2(a)(1)(i)(B) § 60.693-2(a)(1)(i)(C) [G]§ 60.693-2(a)(1)(ii) § 60.693-2(a)(1)(iii) § 60.693-2(a)(1)(iv) § 60.693-2(a)(2) § 60.693-2(a)(3) § 60.693-2(a)(4) § 60.693-2(a)(5)(ii) § 60.693-2(c)	May elect to install a floating roof on an oil-water separator tank, slop oil tank or other auxiliary equipment subject to this subpart which meets the following specifications:	§ 60.693-2(a)(1)(iii)(A) § 60.693-2(a)(1)(iii)(B) § 60.693-2(a)(5)(i) § 60.696(a) [G]§ 60.696(d)	§ 60.697(a) [G]§ 60.697(e) § 60.697(f)(1) [G]§ 60.697(f)(2) [G]§ 60.697(k)	§ 60.693-2(b) § 60.698(a) § 60.698(b)(1) § 60.698(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRPGEFRMS	EU	61FF-0006	Benzene	40 CFR Part 61, Subpart FF	§ 61.351(a) [G]§ 60.112b(a)(2) § 61.351(a)(2) § 61.351(b)	As an alternative to the standards for tanks specified in § 61.343, an owner or operator may elect to comply with one of the following §61.351(a)(1)-(3):	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6)	§ 60.115b [G]§ 60.115b(b)(3) § 61.356(k)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 61.357(e) § 61.357(f)
GRPGEFRMS	EU	63G-002	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.133(a)(2)(iii) § 63.132(a)(2)(i)(A) § 63.132(a)(2)(i)(B) [G]§ 63.132(f) § 63.133(e)(2) § 63.133(f) § 63.133(h) § 63.140(a) § 63.140(b) § 63.140(c) § 63.144(a)	An external floating roof that meets the requirements specified in §63.119(c), §63.120(b)(5), and §63.120(b)(6) of this subpart; or	§ 63.133(e)(1) § 63.133(f) § 63.133(g) § 63.133(g)(2) § 63.133(g)(3) § 63.143(a) § 63.143(g)	§ 63.133(e)(2) § 63.133(h) § 63.147(b) § 63.147(b)(1) § 63.147(b)(2) § 63.147(b)(6) § 63.147(b)(7) [G]§ 63.152(a)	§ 63.146(b)(2) § 63.146(b)(5) § 63.146(b)(6) § 63.146(c) § 63.146(g) [G]§ 63.151(b) § 63.151(e) § 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(3) § 63.152(c)(3)(i) § 63.152(c)(3)(ii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
GRPGEFRMS	EU	63G-002	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(c) § 63.119(a)(1) § 63.119(c)(1) § 63.119(c)(1)(i) § 63.119(c)(1)(ii) § 63.119(c)(1)(iii)	Tanks using an external floating roof, (defined in § 63.111), to comply with §63.119(a)(1) shall comply with §63.119(c)(1)-(4).	§ 63.120(b)(1)(i) § 63.120(b)(1)(iii) § 63.120(b)(1)(iv) § 63.120(b)(10) § 63.120(b)(2)(i) § 63.120(b)(2)(ii)	[G]§ 63.120(b)(7) § 63.120(b)(8) § 63.123(a) § 63.123(d) § 63.123(g) [G]§ 63.152(a)	§ 63.120(b)(10)(ii) § 63.120(b)(10)(iii) § 63.120(b)(9) [G]§ 63.122(e)(1) § 63.122(e)(2) § 63.122(e)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.119(c)(2)(i) § 63.119(c)(2)(ii) § 63.119(c)(2)(iii) § 63.119(c)(2)(iv) § 63.119(c)(2)(ix) § 63.119(c)(2)(v) § 63.119(c)(2)(vi) § 63.119(c)(2)(vii) § 63.119(c)(2)(viii) § 63.119(c)(2)(x) § 63.119(c)(2)(xi) § 63.119(c)(2)(xii) [G]§ 63.119(c)(3) § 63.119(c)(4) § 63.120(b)(10)(i) § 63.120(b)(5)(i) § 63.120(b)(5)(ii) § 63.120(b)(6)(i) § 63.120(b)(6)(ii) [G]§ 63.120(b)(7) § 63.120(b)(8)		§ 63.120(b)(2)(iii) § 63.120(b)(3) § 63.120(b)(4)		§ 63.122(e)(3)(ii) § 63.151(a)(7) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(4)(ii)
GRPGFIFRMS	EU	R5112-0001	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(a)(1) § 115.112(a)(2) § 115.112(a)(2)(A) § 115.112(a)(2)(B) § 115.112(a)(2)(C) § 115.112(a)(2)(D) § 115.112(a)(2)(E) § 115.114(a)(1)(A)	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(7)	§ 115.114(a)(1)(B) § 115.118(a)(3)
GRPGFIFRMS	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.119(a)(1) [G]§ 63.119(b)(1) § 63.119(b)(2) § 63.119(b)(3)(ii) § 63.119(b)(4) § 63.120(a)(4) § 63.120(a)(7) [G]§ 63.646(f)	Each owner or operator of a Group 1 storage vessel subject to this subpart shall comply with the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.120(a)(2)(i) § 63.120(a)(2)(ii) § 63.646(b)(1) § 63.646(e)	§ 63.120(a)(4) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1) § 63.655(i)(5)	§ 63.120(a)(5) § 63.120(a)(6) § 63.642(f) § 63.655(f) [G]§ 63.655(f)(1)(i)(B) § 63.655(f)(6) § 63.655(g) § 63.655(g)(2) [G]§ 63.655(g)(2)(i)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.646(g)				[G]§ 63.655(g)(2)(ii) § 63.655(h) § 63.655(h)(1) § 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(B) § 63.655(h)(2)(i)(C) [G]§ 63.655(h)(6)
GRP-GGGFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(6)	Components at a petroleum refinery or synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process, that contact a process fluid that contains less than 10% VOC by weight and components at a natural gas/gasoline processing operation that contact a process fluid that contains less than 1.0% VOC by weight are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
GRP-GGGFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(5)	Reciprocating compressors and positive displacement pumps used in natural gas/gasoline processing operations are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-GGGFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(10)	Instrumentation systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet 40 CFR §63.169 (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
GRP-GGGFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(11)	Sampling connection systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet the requirements of 40 CFR §63.166(a) and (b) (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
GRP-GGGFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(13)	Components/systems that contact a process fluid containing VOC having a true vapor pressure equal to or less than 0.002 psia at 68 degrees Fahrenheit are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
GRP-GGGFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(2) § 115.352(9)	Each pressure relief valve equipped with a rupture disk must comply with §115.352(9) and	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						§115.356(3)(C).			
GRP-GGGFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.353(a) § 115.353(b) § 115.910	For all affected persons in the Beaumont-Port Arthur, Dallas-Fort Worth, El Paso, and Houston-Galveston areas, as defined in §115.10, any alternate methods of demonstrating and documenting continuous compliance with the applicable control requirements or exemption criteria in this division may be approved by the executive director in accordance with §115.910 if emission reductions are demonstrated to be substantially equivalent.	None	None	None
GRP-GGGFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(C) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7)	No component shall be allowed to have a VOC leak, for more than 15 days, after discovery. If the owner or operator elects to use the alternative work practice in §115.358 of this title, any leak detected as defined in §115.358 of this title, including any leak detected using the alternative work practice on a component that is subject to the	§ 115.354(1) § 115.354(11) § 115.354(13)(A) § 115.354(13)(B) § 115.354(13)(C) § 115.354(13)(D) § 115.354(13)(E) § 115.354(13)(F) § 115.354(4) § 115.354(5) § 115.354(9) [G]§ 115.355 § 115.358(c)(2) § 115.358(d) [G]§ 115.358(e)	§ 115.352(7) § 115.354(13)(D) § 115.354(13)(E) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) [G]§ 115.356(4) § 115.356(5)	[G]§ 115.358(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(8) § 115.357(8) § 115.358(c)(1) [G]§ 115.358(h)	requirements of this division but not specifically selected for alternative work practice monitoring.	§ 115.358(f)		
GRP-GGGFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7) § 115.357(1)	No process drains shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
GRP-GGGFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7)	No process drains shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(5)	None
GRP-GGGFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3)	No pressure relief valves shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater	§ 115.354(1) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(5) § 115.352(7) § 115.352(9) § 115.357(1) § 115.357(8) § 115.357(9)	than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	[G]§ 115.355 § 115.357(1)		
GRP-GGGFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(9) § 115.357(12) § 115.357(8) § 115.357(9)	No pressure relief valves shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
GRP-GGGFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(8) § 115.357(9)	No open-ended valves or lines shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
GRP-GGGFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery &	§ 115.352(1)(A) § 115.352(1) § 115.352(10)	No open-ended valves or lines shall be allowed to have a VOC leak, for	§ 115.354(1) § 115.354(10) § 115.354(2)	§ 115.352(7) § 115.354(10) § 115.356	[G]§ 115.354(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Petrochemicals	§ 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8) § 115.357(9)	more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355	[G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	
GRP-GGGFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(8) § 115.357(9)	No valves shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
GRP-GGGFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8)	No valves shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.357(9)				
GRP-GGGFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(8) § 115.357(1) § 115.357(12) § 115.357(8)	No flanges or other connectors shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
GRP-GGGFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(8) § 115.357(12) § 115.357(8)	No flanges or other connectors shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
GRP-GGGFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii)	No agitators shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(3) § 115.352(7) § 115.357(1) § 115.357(12) § 115.357(8)	methane, or the dripping or exuding of process fluid based on sight, smell, or sound.		§ 115.356(5)	
GRP-GGGFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(7) § 115.357(1) § 115.357(12) § 115.357(8)	No agitators shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
GRP-GGGFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(7) § 115.357(12) § 115.357(8)	No agitators shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
GRP-GGGFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C)	No compressor seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(3) § 115.357(8)	concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.		§ 115.356(5)	
GRP-GGGFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(4) § 115.357(8)	No compressor seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None
GRP-GGGFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1) § 115.357(8)	No compressor seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None
GRP-GGGFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet.	§ 115.352(1)(B) § 115.352(1)	No compressor seals shall be allowed to have	§ 115.354(1) § 115.354(10)	§ 115.352(7) § 115.354(10)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Refinery & Petrochemicals	§ 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	
GRP-GGGFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(4) § 115.357(8)	No pump seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None
GRP-GGGFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7)	No pump seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.357(1) § 115.357(8)	based on sight, smell, or sound.			
GRP-GGGFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	No pump seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
GRP-GGGFUG	EU	60GGG-ALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(d)	Comply with the requirements as stated in §60.482-1(d) for equipment in vacuum service.	None	§ 60.486(e) § 60.486(e)(1) § 60.486(e)(5)	None
GRP-GGGFUG	EU	60GGG-ALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-2 [G]§ 60.482-9	Comply with the requirements as stated in §60.482-2 for pumps in light-liquid service.	[G]§ 60.482-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d) § 60.593(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-GGGFUG	EU	60GGG-ALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) § 60.482-3(f) § 60.482-3(g)(1) § 60.482-3(g)(2)	Comply with the requirements as stated in §60.482-3 for reciprocating compressors that become subject under	§ 60.482-3(f) § 60.482-3(g)(1) § 60.482-3(g)(2) [G]§ 60.482-3(i) § 60.482-3(j) § 60.485(a)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 60.482-3(i) § 60.482-3(j) [G]§ 60.482-9 § 60.593(c)	§60.14 and §60.15.	[G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	
GRP-GGGFUG	EU	60GGG -ALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-3 [G]§ 60.482-9	Comply with the requirements as stated in §60.482-3 for compressors.	[G]§ 60.482-3 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-GGGFUG	EU	60GGG -ALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-4 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-4 for pressure relief devices in gas/vapor service.	[G]§ 60.482-4 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(3) [G]§ 60.486(e)(4) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-GGGFUG	EU	60GGG -ALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-5 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-5 for sampling connection systems.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-GGGFUG	EU	60GGG -ALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-6 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-6 for open-ended valves and lines.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-GGGFUG	EU	60GGG -ALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-7 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-7 for valves in gas/vapor or light-liquid service.	[G]§ 60.482-7 [G]§ 60.483-1 [G]§ 60.483-2 § 60.485(a) [G]§ 60.485(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(d) § 60.487(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 60.483-1 [G]§ 60.483-2 § 60.592(b)		[G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d) § 60.593(d)	[G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) [G]§ 60.486(g) § 60.486(j) § 60.592(e)	§ 60.592(e)
GRP-GGGFUG	EU	60GGG -ALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for pumps in heavy-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-GGGFUG	EU	60GGG -ALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for valves in heavy-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-GGGFUG	EU	60GGG -ALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for flanges or other connectors.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-GGGFUG	EU	60GGG -ALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for pressure relief devices in light-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-GGGFUG	EU	63CCV V-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(d)	Comply with the specified 40 CFR Part	None	§ 60.486(e) § 60.486(e)(1)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						60, Subpart VV requirements for equipment in vacuum service.		§ 60.486(e)(5)	
GRP-GGGFUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-2 [G]§ 60.482-9 § 63.648(a)(2) § 63.648(f) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pumps in light liquid service complying with §60.482-2.	[G]§ 60.482-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(d)(6) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
GRP-GGGFUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-3 [G]§ 60.482-9 § 63.648(a)(2) § 63.648(i) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for compressors complying with §60.482-3.	[G]§ 60.482-3 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(d)(6) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
GRP-GGGFUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) § 60.482-4(a) § 60.482-4(b)(1) [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pressure relief devices in gas/vapor service.	§ 60.482-4(b)(2) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(3) [G]§ 60.486(e)(4) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
								§ 63.655(i)(5)	
GRP-GGGFUG	EU	63CCV V-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-5 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for sampling connection systems complying with §60.482-5.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
GRP-GGGFUG	EU	63CCV V-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-6 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for open-ended valves or lines complying with §60.482-6.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
GRP-GGGFUG	EU	63CCV V-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-7 [G]§ 60.482-9 [G]§ 60.483-1 [G]§ 60.483-2 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for valves in gas/vapor service or in light liquid service complying with §60.482-7.	[G]§ 60.482-7 [G]§ 60.483-1 [G]§ 60.483-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) [G]§ 60.486(g) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(d) § 60.487(e)
GRP-GGGFUG	EU	63CCV V-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for valves in heavy liquid service complying with §60.482-8.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-GGGFUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pumps in heavy liquid service complying with §60.482-8.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
GRP-GGGFUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for flanges or other connectors complying with §60.482-8.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
GRP-GGGFUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pressure relief devices in light liquid service complying with §60.482-8.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
GRP-GGGFUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pressure relief devices in heavy liquid service complying with §60.482-8.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
GRP-GGGFUG	EU	63CCV	112(B)	40 CFR Part 63,	[G]§ 63.648(g)	Compressors in	[G]§ 63.648(g)	§ 63.648(h)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		V-ALL	HAPS	Subpart CC		hydrogen service are exempt from the requirements of §63.648(a) and (c), if an owner or operator demonstrates that a compressor is in hydrogen service. §63.648(g)(1)-(2).		§ 63.655(d)(3) § 63.655(i)(5)	
GRPGIFRMS1	EU	R5112-0001	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(a)(1) § 115.112(a)(2) § 115.112(a)(2)(A) § 115.112(a)(2)(B) § 115.112(a)(2)(C) § 115.112(a)(2)(D) § 115.112(a)(2)(E) § 115.114(a)(1)(A)	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(7)	§ 115.114(a)(1)(B) § 115.118(a)(3)
GRPGIFRMS1	EU	60QQQ-0007	VOC	40 CFR Part 60, Subpart QQQ	§ 60.692-3(d) § 60.692-1(a) § 60.692-6(a) § 60.692-6(b) § 60.692-7(b)	Storage vessels, including slop oil tanks and other auxiliary tanks that are subject to the requirements of 40 CFR subparts K, Ka, or Kb, are not subject to the requirements of this section.	§ 60.692-3(a)(4) § 60.696(a)	§ 60.697(a) § 60.697(c) [G]§ 60.697(e) § 60.697(f)(1) [G]§ 60.697(f)(2)	§ 60.698(b)(1) § 60.698(e)
GRPGIFRMS1	EU	61FF-0005	Benzene	40 CFR Part 61, Subpart FF	§ 61.351(a) § 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii) § 61.351(a)(1)	As an alternative to the standards for tanks specified in § 61.343, an owner or operator may elect to comply with one of the following §61.351(a)(1)-(3):	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5)	§ 60.115b § 60.115b(a)(2) § 61.356(k)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3) § 61.357(e) § 61.357(f)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 61.351(b)				
GRPGIFRMS1	EU	63G-005	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.133(a)(2)(ii) § 63.132(a)(2)(i)(A) § 63.132(a)(2)(i)(B) [G]§ 63.132(f) § 63.133(f) § 63.133(h) § 63.140(a) § 63.140(b) § 63.140(c) § 63.144(a)	A fixed roof and an internal floating roof that meets the requirements specified in Sec. 63.119(b) of this subpart;	§ 63.133(f) § 63.133(g) § 63.133(g)(2) § 63.133(g)(3) § 63.143(a) § 63.143(g)	§ 63.133(h) § 63.147(b) § 63.147(b)(1) § 63.147(b)(6) § 63.147(b)(7) [G]§ 63.152(a)	§ 63.146(b)(2) § 63.146(b)(5) § 63.146(b)(6) § 63.146(c) § 63.146(g) [G]§ 63.151(b) § 63.151(e) § 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(3) § 63.152(c)(3)(i) § 63.152(c)(3)(ii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
GRPGIFRMS1	EU	63G-005	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(b) § 63.119(a)(1) [G]§ 63.119(b)(1) § 63.119(b)(2) § 63.119(b)(3)(ii) § 63.119(b)(4) § 63.119(b)(5)(i) § 63.119(b)(5)(ii) § 63.119(b)(5)(iii) § 63.119(b)(5)(iv) § 63.119(b)(5)(v) § 63.119(b)(5)(vi) § 63.119(b)(5)(vii) [G]§ 63.119(b)(5)(viii) § 63.119(b)(6) § 63.120(a)(4)	Tanks using a fixed roof and an internal floating roof (defined in §63.111) to comply with §63.119(a)(1) must comply with: §63.119(b)(1)-(6).	§ 63.120(a)(2)(i) § 63.120(a)(2)(ii)	§ 63.120(a)(4) § 63.123(a) § 63.123(c) § 63.123(g) [G]§ 63.152(a)	§ 63.120(a)(5) § 63.120(a)(6) § 63.122(d) § 63.122(d)(1)(ii) § 63.122(d)(1)(iii) § 63.122(d)(2)(ii) § 63.151(a)(7) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(4)(ii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.120(a)(7)				
GRPGIFRMS2	EU	R5112-0002	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(a)(1) § 115.112(a)(2) § 115.112(a)(2)(A) § 115.112(a)(2)(B) § 115.112(a)(2)(C) § 115.112(a)(2)(D) § 115.112(a)(2)(E) § 115.114(a)(1)(A)	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(7)	§ 115.114(a)(1)(B) § 115.118(a)(3)
GRPGIFRMS2	EU	60QQQ-0007	VOC	40 CFR Part 60, Subpart QQQ	§ 60.692-3(d) § 60.692-1(a) § 60.692-6(a) § 60.692-6(b) § 60.692-7(b)	Storage vessels, including slop oil tanks and other auxiliary tanks that are subject to the requirements of 40 CFR subparts K, Ka, or Kb, are not subject to the requirements of this section.	§ 60.692-3(a)(4) § 60.696(a)	§ 60.697(a) § 60.697(c) [G]§ 60.697(e) § 60.697(f)(1) [G]§ 60.697(f)(2)	§ 60.698(b)(1) § 60.698(e)
GRPGIFRMS2	EU	61FF-0005	Benzene	40 CFR Part 61, Subpart FF	§ 61.351(a) § 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii) § 61.351(a)(1) § 61.351(b)	As an alternative to the standards for tanks specified in § 61.343, an owner or operator may elect to comply with one of the following §61.351(a)(1)-(3):	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5)	§ 60.115b § 60.115b(a)(2) § 61.356(k)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3) § 61.357(e) § 61.357(f)
GRPGIFRMS2	EU	63G-003	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.133(a)(1)	A fixed roof shall be operated and maintained except that if the wastewater tank is used for specified purpose, then owner or operator	None	None	§ 63.146(b)(2) § 63.146(b)(5) [G]§ 63.151(b) § 63.151(e) § 63.151(e)(1) § 63.151(e)(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						shall comply with requirements of § 63.133(a)(2).			[G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(c)(1) § 63.152(c)(4)(ii)
GRPGIFRMS2	EU	63G-003	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(b) § 63.119(a)(1) [G]§ 63.119(b)(1) § 63.119(b)(2) § 63.119(b)(3)(iii) § 63.119(b)(4) § 63.119(b)(5)(i) § 63.119(b)(5)(ii) § 63.119(b)(5)(iii) § 63.119(b)(5)(iv) § 63.119(b)(5)(v) § 63.119(b)(5)(vi) § 63.119(b)(5)(vii) [G]§ 63.119(b)(5)(viii) § 63.119(b)(6) § 63.120(a)(4) § 63.120(a)(7)	Tanks using a fixed roof and an internal floating roof (defined in §63.111) to comply with §63.119(a)(1) must comply with: §63.119(b)(1)-(6).	§ 63.120(a)(3)(i) § 63.120(a)(3)(ii) § 63.120(a)(3)(iii)	§ 63.120(a)(4) § 63.123(a) § 63.123(c) § 63.123(g) [G]§ 63.152(a)	§ 63.120(a)(5) § 63.120(a)(6) § 63.122(d) § 63.122(d)(1)(ii) § 63.122(d)(1)(iii) § 63.122(d)(2)(ii) § 63.151(a)(7) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(4)(ii)
GRPKVOC	EU	R5112-0004	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(a)(1) § 115.112(a)(2) § 115.112(a)(2)(A) § 115.112(a)(2)(B) § 115.112(a)(2)(C) § 115.112(a)(2)(D) § 115.112(a)(2)(E) § 115.112(a)(2)(F) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)
GRPKVOC	EU	60K-003	VOC	40 CFR Part 60, Subpart K	§ 60.112(a)(1)	Storage vessels holding petroleum liquids with a true vapor pressure of 78 mm Hg (1.5 psia) or greater but not greater	§ 60.113(a) § 60.113(b) ** See Periodic Monitoring Summary	§ 60.113(a)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						than 570 mm Hg (11.1 psia) shall have a floating roof, a vapor recovery system, or their equivalents.			
GRPKVOC	EU	63CC-0254	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(6)	After compliance dates specified in paragraph (h) of this section, a Group 2 storage vessel that is subject to the control requirements of 40 CFR Part 60, Subpart K is required to comply only with the provisions of 40 CFR Part 60, Subpart K.	None	None	None
GRPKVOC	EU	63CC-1254	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.119(a)(1) § 63.119(c)(1) § 63.119(c)(1)(i) § 63.119(c)(1)(ii) § 63.119(c)(1)(iii) [G]§ 63.119(c)(3) § 63.119(c)(4) § 63.120(b)(10)(i) § 63.120(b)(5)(i) § 63.120(b)(5)(ii) § 63.120(b)(6)(i) § 63.120(b)(6)(ii) [G]§ 63.120(b)(7) § 63.120(b)(8) [G]§ 63.646(f) § 63.646(g)	Each owner or operator of a Group 1 storage vessel subject to this subpart shall comply with the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.120(b)(1)(i) § 63.120(b)(1)(iii) § 63.120(b)(1)(iv) § 63.120(b)(10) § 63.120(b)(2)(i) § 63.120(b)(2)(ii) § 63.120(b)(2)(iii) § 63.120(b)(3) § 63.120(b)(4) § 63.646(b)(1) § 63.646(e)	[G]§ 63.120(b)(7) § 63.120(b)(8) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1) § 63.655(i)(5)	§ 63.120(b)(10)(ii) § 63.120(b)(10)(iii) § 63.120(b)(9) § 63.642(f) § 63.655(f) [G]§ 63.655(f)(1)(i)(B) § 63.655(f)(6) § 63.655(g) [G]§ 63.655(g)(3) § 63.655(h) § 63.655(h)(1) § 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(B) § 63.655(h)(2)(i)(C) § 63.655(h)(2)(ii) [G]§ 63.655(h)(6)
GRPRTOTKS	EU	R5112-0006	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						the requirements of this division.			
GRPRTOTKS	EU	60QQQ -0014	VOC	40 CFR Part 60, Subpart QQQ	§ 60.692-3(a) § 60.692-1(a) § 60.692-3(a)(1) § 60.692-3(a)(2) § 60.692-3(a)(3) § 60.692-3(a)(5) § 60.692-3(e) § 60.692-3(f) § 60.692-5(a) § 60.692-5(d) [G]§ 60.692-5(e) § 60.692-6(a) § 60.692-6(b) § 60.692-7(b)	Except as noted, each oil-water separator tank, slop oil tank, storage vessel, or other auxiliary equipment shall be equipped with fixed roof, meeting following specifications:	§ 60.692-3(a)(4) § 60.695(a) § 60.695(a)(1) § 60.696(a)	§ 60.695(a)(1) § 60.697(a) § 60.697(c) [G]§ 60.697(e) § 60.697(f)(1) [G]§ 60.697(f)(2) § 60.697(f)(3) § 60.697(f)(3)(i) § 60.697(f)(3)(iii) § 60.697(f)(3)(iv) § 60.697(f)(3)(v) § 60.697(f)(3)(vi) § 60.697(f)(3)(vii) § 60.697(f)(3)(viii)	§ 60.698(b)(1) § 60.698(d) § 60.698(d)(1) § 60.698(e)
GRPRTOTKS	EU	61FF-0027	Benzene	40 CFR Part 61, Subpart FF	§ 61.343(a)(1) § 61.343(a)(1)(i)(A) § 61.343(a)(1)(i)(B) § 61.343(c) § 61.343(d) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(i)(C) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	The owner or operator shall install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the tank to a control device.	§ 61.343(a)(1)(i)(A) § 61.343(c) § 61.349(a)(1)(i) § 61.349(e) § 61.349(f) § 61.354(c) § 61.354(c)(1) [G]§ 61.355(h)	§ 61.354(c) § 61.354(c)(1) § 61.356(d) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(A) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(4)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(A)
GRPRTOTKS	EU	63G-001	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.133(a)(1)	A fixed roof shall be operated and maintained except that if the wastewater tank is used for specified purpose, then owner or operator shall comply with	None	None	§ 63.146(b)(2) § 63.146(b)(5) [G]§ 63.151(b) § 63.151(e) § 63.151(e)(1) § 63.151(e)(2) [G]§ 63.151(j)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						requirements of § 63.133(a)(2).			[G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(c)(1) § 63.152(c)(4)(ii)
GRPRTOTKS	EU	63G-001	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(e) § 63.119(a)(1) § 63.119(e)(1) § 63.119(e)(3) § 63.119(e)(4) § 63.119(e)(5) [G]§ 63.148(d) § 63.148(e)	The owner or operator who elects to use a closed vent system and control device (defined in § 63.111) to comply with§63.119(a)(1) or (a)(2) shall comply with §63.119(e)(1)-(5).	§ 63.120(d)(1) § 63.120(d)(5) § 63.120(d)(6) § 63.148(b)(1)(ii) [G]§ 63.148(c) § 63.148(g) § 63.148(g)(2) § 63.148(h) § 63.148(h)(2)	§ 63.120(d)(1)(i) § 63.120(d)(1)(i)(A) § 63.120(d)(1)(i)(C) § 63.123(a) § 63.123(f)(1) [G]§ 63.123(f)(2) § 63.148(g)(2) § 63.148(h)(2) § 63.148(i)(1) § 63.148(i)(2) [G]§ 63.148(i)(4) § 63.148(i)(5) § 63.148(i)(6) [G]§ 63.152(a)	§ 63.120(d)(1) § 63.120(d)(2) § 63.120(d)(2)(i) § 63.120(d)(2)(ii) § 63.120(d)(3) § 63.120(d)(3)(i) § 63.120(d)(4) § 63.122(b) § 63.122(c)(1) [G]§ 63.122(g)(1) [G]§ 63.122(g)(2) § 63.148(j) § 63.151(a)(7) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(3) § 63.152(c)(3)(i) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
GRP-RVFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(6)	Components at a petroleum refinery or synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						manufacturing process, that contact a process fluid that contains less than 10% VOC by weight and components at a natural gas/gasoline processing operation that contact a process fluid that contains less than 1.0% VOC by weight are exempt from the requirements of this division except §115.356(3)(C) of this title.			
GRP-RVFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(5)	Reciprocating compressors and positive displacement pumps used in natural gas/gasoline processing operations are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
GRP-RVFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(10)	Instrumentation systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet 40 CFR §63.169 (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
GRP-RVFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery &	§ 115.357(11)	Sampling connection systems, as defined in 40 CFR §63.161	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Petrochemicals		(January 17, 1997), that meet the requirements of 40 CFR §63.166(a) and (b) (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.			
GRP-RVFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(13)	Components/systems that contact a process fluid containing VOC having a true vapor pressure equal to or less than 0.002 psia at 68 degrees Fahrenheit are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
GRP-RVFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(2) § 115.352(9)	Each pressure relief valve equipped with a rupture disk must comply with §115.352(9) and §115.356(3)(C).	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
GRP-RVFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.353(a) § 115.353(b) § 115.910	For all affected persons in the Beaumont-Port Arthur, Dallas-Fort Worth, El Paso, and Houston-Galveston areas, as defined in §115.10, any alternate methods of demonstrating and documenting continuous compliance with the applicable control	None	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						requirements or exemption criteria in this division may be approved by the executive director in accordance with §115.910 if emission reductions are demonstrated to be substantially equivalent.			
GRP-RVFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(C) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.352(8) § 115.357(8) § 115.358(c)(1) [G]§ 115.358(h)	No component shall be allowed to have a VOC leak, for more than 15 days, after discovery. If the owner or operator elects to use the alternative work practice in §115.358 of this title, any leak detected as defined in §115.358 of this title, including any leak detected using the alternative work practice on a component that is subject to the requirements of this division but not specifically selected for alternative work practice monitoring.	§ 115.354(1) § 115.354(11) § 115.354(13)(A) § 115.354(13)(B) § 115.354(13)(C) § 115.354(13)(D) § 115.354(13)(E) § 115.354(13)(F) § 115.354(4) § 115.354(5) § 115.354(9) [G]§ 115.355 § 115.358(c)(2) § 115.358(d) [G]§ 115.358(e) § 115.358(f)	§ 115.352(7) § 115.354(13)(D) § 115.354(13)(E) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) [G]§ 115.356(4) § 115.356(5)	[G]§ 115.358(g)
GRP-RVFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7) § 115.357(1)	No process drains shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume	§ 115.354(1) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.		§ 115.356(5)	
GRP-RVFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7)	No process drains shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(5)	None
GRP-RVFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(9) § 115.357(1) § 115.357(8) § 115.357(9)	No pressure relief valves shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
GRP-RVFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B)	No pressure relief valves shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3)	[G]§ 115.354(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(3) § 115.352(5) § 115.352(7) § 115.352(9) § 115.357(12) § 115.357(8) § 115.357(9)	concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	[G]§ 115.354(7) § 115.354(9) [G]§ 115.355	§ 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	
GRP-RVFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(8) § 115.357(9)	No open-ended valves or lines shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
GRP-RVFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8) § 115.357(9)	No open-ended valves or lines shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
GRP-RVFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet.	§ 115.352(1)(A) § 115.352(1)	No valves shall be allowed to have a VOC	§ 115.354(1) § 115.354(2)	§ 115.352(7) § 115.356	[G]§ 115.354(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Refinery & Petrochemicals	§ 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(8) § 115.357(9)	leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 § 115.357(1)	[G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	
GRP-RVFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8) § 115.357(9)	No valves shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
GRP-RVFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(8) § 115.357(1) § 115.357(12) § 115.357(8)	No flanges or other connectors shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process	§ 115.354(1) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						fluid based on sight, smell, or sound.			
GRP-RVFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(8) § 115.357(12) § 115.357(8)	No flanges or other connectors shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
GRP-RVFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(7) § 115.357(1) § 115.357(12) § 115.357(8)	No agitators shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
GRP-RVFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii)	No agitators shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume	§ 115.354(1) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(2)(C)(iii) § 115.352(3) § 115.352(7) § 115.357(1) § 115.357(12) § 115.357(8)	above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.		§ 115.356(5)	
GRP-RVFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(7) § 115.357(12) § 115.357(8)	No agitators shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
GRP-RVFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(3) § 115.357(8)	No compressor seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None
GRP-RVFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A)	No compressor seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(4) § 115.357(8)	a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.		[G]§ 115.356(3)(C) § 115.356(5)	
GRP-RVFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1) § 115.357(8)	No compressor seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None
GRP-RVFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	No compressor seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
GRP-RVFUG	EU	R5352-	VOC	30 TAC Chapter	§ 115.352(1)(B)	No pump seals shall be	[G]§ 115.355	§ 115.352(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		ALL		115, Pet. Refinery & Petrochemicals	§ 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(4) § 115.357(8)	allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.		§ 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	
GRP-RVFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1) § 115.357(8)	No pump seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None
GRP-RVFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5)	No pump seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(7) § 115.357(12) § 115.357(8)	exuding of process fluid based on sight, smell, or sound.			
GRPTK5491	EU	R5112-0005	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(a)(1) § 115.112(a)(2) § 115.112(a)(2)(A) § 115.112(a)(2)(B) § 115.112(a)(2)(C) § 115.112(a)(2)(D) § 115.112(a)(2)(E) § 115.112(a)(2)(F) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)
GRPTK5491	EU	60K-001	VOC	40 CFR Part 60, Subpart K	§ 60.112(a)(1)	Storage vessels holding petroleum liquids with a true vapor pressure of 78 mm Hg (1.5 psia) or greater but not greater than 570 mm Hg (11.1 psia) shall have a floating roof, a vapor recovery system, or their equivalents.	§ 60.113(a) § 60.113(b) ** See Periodic Monitoring Summary	§ 60.113(a)	None
GRPTK5491	EU	63CC-0254	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(6)	After compliance dates specified in paragraph (h) of this section, a Group 2 storage vessel that is subject to the control requirements of 40 CFR Part 60, Subpart K is required to comply only with the provisions of 40 CFR Part 60, Subpart K.	None	None	None
GRPTK5491	EU	63CC-1254	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.119(a)(1) § 63.119(c)(1)	Each owner or operator of a Group 1 storage vessel subject to this	§ 63.120(b)(1)(i) § 63.120(b)(1)(iii) § 63.120(b)(1)(iv)	[G]§ 63.120(b)(7) § 63.120(b)(8) § 63.642(e)	§ 63.120(b)(10)(ii) § 63.120(b)(10)(iii) § 63.120(b)(9)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.119(c)(1)(i) § 63.119(c)(1)(ii) § 63.119(c)(1)(iii) [G]§ 63.119(c)(3) § 63.119(c)(4) § 63.120(b)(10)(i) § 63.120(b)(5)(i) § 63.120(b)(5)(ii) § 63.120(b)(6)(i) § 63.120(b)(6)(ii) [G]§ 63.120(b)(7) § 63.120(b)(8) [G]§ 63.646(f) § 63.646(g)	subpart shall comply with the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.120(b)(10) § 63.120(b)(2)(i) § 63.120(b)(2)(ii) § 63.120(b)(2)(iii) § 63.120(b)(3) § 63.120(b)(4) § 63.646(b)(1) § 63.646(e)	§ 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1) § 63.655(i)(5)	§ 63.642(f) § 63.655(f) [G]§ 63.655(f)(1)(i)(B) § 63.655(f)(6) § 63.655(g) [G]§ 63.655(g)(3) § 63.655(h) § 63.655(h)(1) § 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(B) § 63.655(h)(2)(i)(C) § 63.655(h)(2)(ii) [G]§ 63.655(h)(6)
GRPTK7600	EU	R5112-0005	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(a)(1) § 115.112(a)(2) § 115.112(a)(2)(A) § 115.112(a)(2)(B) § 115.112(a)(2)(C) § 115.112(a)(2)(D) § 115.112(a)(2)(E) § 115.112(a)(2)(F) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)
GRPTK7600	EU	60Ka-002	VOC	40 CFR Part 60, Subpart Ka	§ 60.112a(a)(1) § 60.112a(a)(1)(i) § 60.112a(a)(1)(i)(A) § 60.112a(a)(1)(i)(C) § 60.112a(a)(1)(i)(D) § 60.112a(a)(1)(ii)(A) § 60.112a(a)(1)(ii)(B) § 60.112a(a)(1)(ii)(C) § 60.112a(a)(1)(ii)(D) § 60.112a(a)(1)(iii) § 60.112a(a)(1)(iv)	Vessels storing petroleum liquids with a TVP > 10.3 kPa (1.5 psia) but < 76.6 kPa (11.1 psia) shall be equipped with an external floating roof and closure device as specified.	§ 60.113a(a)(1) § 60.113a(a)(1)(i) § 60.113a(a)(1)(i)(A) § 60.113a(a)(1)(i)(B) § 60.113a(a)(1)(i)(C) § 60.113a(a)(1)(i)(D) § 60.113a(a)(1)(i)(E) § 60.113a(a)(1)(ii)(A) § 60.113a(a)(1)(ii)(B) § 60.113a(a)(1)(ii)(C) § 60.113a(a)(1)(iii) § 60.113a(a)(1)(iv) § 60.115a(a) § 60.115a(b)	§ 60.113a(a)(1)(i)(D) § 60.115a(a)	§ 60.113a(a)(1)(i)(E) § 60.113a(a)(1)(iv)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRPTK7600	EU	63CC-0254	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(9) § 60.112a(a)(1) § 60.112a(a)(1)(i) § 60.112a(a)(1)(i)(A) § 60.112a(a)(1)(i)(C) § 60.112a(a)(1)(i)(D) § 60.112a(a)(1)(ii)(A) § 60.112a(a)(1)(ii)(B) § 60.112a(a)(1)(ii)(C) § 60.112a(a)(1)(ii)(D) § 60.112a(a)(1)(iii) § 60.112a(a)(1)(iv) § 63.640(n)(9)(i) § 63.640(n)(9)(ii)	Vessels described by paragraph §60.640(n)(6) that are to comply with 40 CFR part 60, subpart Ka, are to comply with only subpart Ka except as provided for in §63.640(n)(9)(i)-(iv).	[G]§ 60.113a(a)(1) § 60.115a(a) § 60.115a(b) § 63.640(n)(9)(i)	§ 60.113a(a)(1)(i)(D) § 60.115a(a)	§ 60.113a(a)(1)(i)(E) § 60.113a(a)(1)(iv) § 63.640(n)(9)(iii) § 63.640(n)(9)(iv)
GRPTK7600	EU	63CC-1254	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.119(a)(1) § 63.119(c)(1) § 63.119(c)(1)(i) § 63.119(c)(1)(ii) § 63.119(c)(1)(iii) [G]§ 63.119(c)(3) § 63.119(c)(4) § 63.120(b)(10)(i) § 63.120(b)(5)(i) § 63.120(b)(5)(ii) § 63.120(b)(6)(i) § 63.120(b)(6)(ii) [G]§ 63.120(b)(7) § 63.120(b)(8) [G]§ 63.646(f) § 63.646(g)	Each owner or operator of a Group 1 storage vessel subject to this subpart shall comply with the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.120(b)(1)(i) § 63.120(b)(1)(iii) § 63.120(b)(1)(iv) § 63.120(b)(10) § 63.120(b)(2)(i) § 63.120(b)(2)(ii) § 63.120(b)(2)(iii) § 63.120(b)(3) § 63.120(b)(4) § 63.646(b)(1) § 63.646(e)	[G]§ 63.120(b)(7) § 63.120(b)(8) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1) § 63.655(i)(5)	§ 63.120(b)(10)(ii) § 63.120(b)(10)(iii) § 63.120(b)(9) § 63.642(f) § 63.655(f) [G]§ 63.655(f)(1)(i)(B) § 63.655(f)(6) § 63.655(g) [G]§ 63.655(g)(3) § 63.655(h) § 63.655(h)(1) § 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(B) § 63.655(h)(2)(i)(C) § 63.655(h)(2)(ii) [G]§ 63.655(h)(6)
GRPVENTCC1	EP	R5131-1001	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(1) § 115.122(a)(1) § 115.122(a)(1)(B) § 60.18	No person may allow a vent gas stream containing VOC to be emitted from any process vent, unless the vent gas stream is burned properly in	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						accordance with §115.122(a)(1) of this title.			
GRPVENTCC1	EP	63CC-1011	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.643(a) § 63.11(b) § 63.643(a)(1)	The owner or operator of a Group 1 miscellaneous process vent as defined in §63.641 shall comply with the requirements of either §63.643(a)(1)-(2).	§ 63.116(a)(2) § 63.116(a)(3) § 63.644(a) § 63.644(a)(2) § 63.644(e) § 63.645(a) § 63.645(i)	§ 63.642(e) § 63.655(h)(1) § 63.655(i)(5)	§ 63.642(f) [G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(ii) [G]§ 63.655(f)(1)(iv) [G]§ 63.655(f)(2) § 63.655(f)(4) § 63.655(g) § 63.655(g)(6) § 63.655(h) § 63.655(h)(1)
GRP-VVFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(6)	Components at a petroleum refinery or synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process, that contact a process fluid that contains less than 10% VOC by weight and components at a natural gas/gasoline processing operation that contact a process fluid that contains less than 1.0% VOC by weight are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
GRP-VVFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(5)	Reciprocating compressors and positive displacement pumps used in natural	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						gas/gasoline processing operations are exempt from the requirements of this division except §115.356(3)(C) of this title.			
GRP-VVFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(10)	Instrumentation systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet 40 CFR §63.169 (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
GRP-VVFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(11)	Sampling connection systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet the requirements of 40 CFR §63.166(a) and (b) (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
GRP-VVFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(13)	Components/systems that contact a process fluid containing VOC having a true vapor pressure equal to or less than 0.002 psia at 68 degrees Fahrenheit are exempt from the requirements of this division except	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						§115.356(3)(C) of this title.			
GRP-VVFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(2) § 115.352(9)	Each pressure relief valve equipped with a rupture disk must comply with §115.352(9) and §115.356(3)(C).	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
GRP-VVFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.353(a) § 115.353(b) § 115.910	For all affected persons in the Beaumont-Port Arthur, Dallas-Fort Worth, El Paso, and Houston-Galveston areas, as defined in §115.10, any alternate methods of demonstrating and documenting continuous compliance with the applicable control requirements or exemption criteria in this division may be approved by the executive director in accordance with §115.910 if emission reductions are demonstrated to be substantially equivalent.	None	None	None
GRP-VVFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(C) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii)	No component shall be allowed to have a VOC leak, for more than 15 days, after discovery. If the owner or operator elects to use the alternative work practice in §115.358 of this title, any leak detected as	§ 115.354(1) § 115.354(11) § 115.354(13)(A) § 115.354(13)(B) § 115.354(13)(C) § 115.354(13)(D) § 115.354(13)(E) § 115.354(13)(F) § 115.354(4)	§ 115.352(7) § 115.354(13)(D) § 115.354(13)(E) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B)	[G]§ 115.358(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(2)(C)(iii) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.352(8) § 115.357(8) § 115.358(c)(1) [G]§ 115.358(h)	defined in §115.358 of this title, including any leak detected using the alternative work practice on a component that is subject to the requirements of this division but not specifically selected for alternative work practice monitoring.	§ 115.354(5) § 115.354(9) [G]§ 115.355 § 115.358(c)(2) § 115.358(d) [G]§ 115.358(e) § 115.358(f)	[G]§ 115.356(3)(C) [G]§ 115.356(4) § 115.356(5)	
GRP-VVFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7) § 115.357(1)	No process drains shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
GRP-VVFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7)	No process drains shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(5)	None
GRP-VVFUG	EU	R5352-	VOC	30 TAC Chapter	§ 115.352(1)(A)	No pressure relief valves	§ 115.354(1)	§ 115.352(7)	[G]§ 115.354(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		ALL		115, Pet. Refinery & Petrochemicals	§ 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(9) § 115.357(1) § 115.357(8) § 115.357(9)	shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	
GRP-VVFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(9) § 115.357(12) § 115.357(8) § 115.357(9)	No pressure relief valves shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
GRP-VVFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7)	No open-ended valves or lines shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.357(1) § 115.357(8) § 115.357(9)	exuding of process fluid based on sight, smell, or sound.			
GRP-VVFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8) § 115.357(9)	No open-ended valves or lines shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
GRP-VVFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(8) § 115.357(9)	No valves shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
GRP-VVFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3)	No valves shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A)	[G]§ 115.354(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8) § 115.357(9)	per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	[G]§ 115.355	§ 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	
GRP-VVFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(8) § 115.357(1) § 115.357(12) § 115.357(8)	No flanges or other connectors shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
GRP-VVFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(8) § 115.357(12) § 115.357(8)	No flanges or other connectors shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
GRP-VVFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery &	§ 115.352(1)(A) § 115.352(1) § 115.352(10)	No agitators shall be allowed to have a VOC leak, for more than 15	§ 115.354(1) § 115.354(10) § 115.354(5)	§ 115.352(7) § 115.354(10) § 115.356	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Petrochemicals	§ 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(7) § 115.357(1) § 115.357(12) § 115.357(8)	days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	[G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	
GRP-VVFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(7) § 115.357(1) § 115.357(12) § 115.357(8)	No agitators shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
GRP-VVFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(7) § 115.357(12) § 115.357(8)	No agitators shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-VVFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(3) § 115.357(8)	No compressor seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None
GRP-VVFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(4) § 115.357(8)	No compressor seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None
GRP-VVFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3)	No compressor seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane,	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(5) § 115.352(7) § 115.357(1) § 115.357(8)	or the dripping or exuding of process fluid based on sight, smell, or sound.			
GRP-VVFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	No compressor seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
GRP-VVFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(4) § 115.357(8)	No pump seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None
GRP-VVFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C)	No pump seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1) § 115.357(8)	greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.357(1)	§ 115.356(5)	
GRP-VVFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	No pump seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
GRP-VVFUG	EU	60VV-ALL	VOC	40 CFR Part 60, Subpart VV	§ 60.482-1(d) § 60.486(k)	Equipment that is in vacuum service is excluded from the requirements of §60.482-2 to §60.482-10, if it is identified as required in §60.486(e)(5).	None	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(5) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
GRP-VVFUG	EU	60VV-ALL	VOC	40 CFR Part 60, Subpart VV	§ 60.482-2(b)(1) § 60.482-1(a) § 60.482-1(b) § 60.482-1(g) § 60.482-2(a)(2) [G]§ 60.482-2(b)(2) § 60.482-2(c)(1) [G]§ 60.482-2(c)(2) § 60.482-2(d)	If an instrument reading of 10,000 ppm or greater is measured for pumps in light liquid service, a leak is detected.	§ 60.482-1(f)(1) § 60.482-1(f)(2) [G]§ 60.482-1(f)(3) § 60.482-2(a)(1) [G]§ 60.482-2(b)(2) [G]§ 60.482-2(d)(4) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c)	§ 60.482-1(g) [G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 60.482-2(d)(1) § 60.482-2(d)(2) § 60.482-2(d)(3) [G]§ 60.482-2(d)(4) [G]§ 60.482-2(d)(5) [G]§ 60.482-2(d)(6) [G]§ 60.482-2(e) § 60.482-2(f) [G]§ 60.482-2(g) § 60.482-2(h) § 60.482-9(a) § 60.482-9(b) [G]§ 60.482-9(d) § 60.482-9(f) § 60.486(k)		[G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f)	[G]§ 60.486(h) § 60.486(j)	
GRP-VVFUG	EU	60VV-ALL	VOC	40 CFR Part 60, Subpart VV	§ 60.482-3(a) § 60.482-1(a) § 60.482-1(b) § 60.482-1(g) [G]§ 60.482-3(b) § 60.482-3(c) § 60.482-3(d) § 60.482-3(e)(1) § 60.482-3(e)(2) § 60.482-3(f) § 60.482-3(g)(1) § 60.482-3(g)(2) § 60.482-3(h) [G]§ 60.482-3(i) § 60.482-3(j) § 60.482-9(a) § 60.482-9(b) § 60.486(k)	Each compressor shall be equipped with a seal system that includes a barrier fluid system and that prevents leakage of VOC to the atmosphere, except as provided in §60.482-1(c) and paragraphs (h), (i), and (j) of this section.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f)	§ 60.482-1(g) [G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
GRP-VVFUG	EU	60VV-ALL	VOC	40 CFR Part 60, Subpart VV	§ 60.482-4(a) § 60.482-1(a) § 60.482-1(b) § 60.482-1(g) § 60.482-4(b)(1)	Except during pressure releases, each pressure relief device in gas/vapor service shall be operated with no detectable	§ 60.482-4(b)(2) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d)	§ 60.482-1(g) [G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(3)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.482-4(c) § 60.482-4(d)(1) § 60.482-4(d)(2) § 60.482-9(a) § 60.482-9(b) § 60.486(k)	emissions, as indicated by an instrument reading of less than 500 ppm above background, as determined by the methods specified in § 60.485(c).	§ 60.485(f)	[G]§ 60.486(e)(4) § 60.486(j)	
GRP-VVFUG	EU	60VV-ALL	VOC	40 CFR Part 60, Subpart VV	§ 60.482-5(a) § 60.482-1(a) § 60.482-1(b) § 60.482-1(g) [G]§ 60.482-5(b) § 60.482-5(c) § 60.486(k)	Each sampling connection system shall be equipped with a closed-purge, closed-loop, or closed-vent system, except as provided in §60.482-1(c) and paragraph (c) of this section.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f)	§ 60.482-1(g) [G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
GRP-VVFUG	EU	60VV-ALL	VOC	40 CFR Part 60, Subpart VV	§ 60.482-6(a)(1) § 60.482-1(a) § 60.482-1(b) § 60.482-1(g) § 60.482-6(a)(2) § 60.482-6(b) § 60.482-6(c) § 60.482-6(d) § 60.482-6(e) § 60.486(k)	Each open-ended valve or line shall be equipped with a cap, blind flange, plug, or a second valve, except as provided in §60.482-1(c) and paragraphs (d) and (e) of this section.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f)	§ 60.482-1(g) [G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
GRP-VVFUG	EU	60VV-ALL	VOC	40 CFR Part 60, Subpart VV	§ 60.482-7(b) § 60.482-1(a) § 60.482-1(b) § 60.482-1(g) § 60.482-7(d)(1) § 60.482-7(d)(2) [G]§ 60.482-7(e) [G]§ 60.482-7(f) [G]§ 60.482-7(g) [G]§ 60.482-7(h) § 60.482-9(a) § 60.482-9(b)	If an instrument reading of 10,000 ppm or greater is measured for valves in gas/vapor service and in light liquid service, a leak is detected.	§ 60.482-1(f)(1) § 60.482-1(f)(2) [G]§ 60.482-1(f)(3) § 60.482-7(a)(1) [G]§ 60.482-7(a)(2) § 60.482-7(c)(1)(i) § 60.482-7(c)(1)(ii) § 60.482-7(c)(2) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d)	§ 60.482-1(g) [G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 60.482-9(c) § 60.482-9(e) § 60.482-9(f) § 60.486(k)		[G]§ 60.485(e) § 60.485(f)		
GRP-VVFUG	EU	60VV-ALL	VOC	40 CFR Part 60, Subpart VV	§ 60.482-8(b) § 60.482-1(a) § 60.482-1(b) § 60.482-1(g) § 60.482-8(a) § 60.482-8(a)(2) § 60.482-8(c)(1) § 60.482-8(c)(2) § 60.482-8(d) § 60.482-9(a) § 60.482-9(b) [G]§ 60.482-9(d) § 60.482-9(f) § 60.486(k)	For pumps in heavy liquid service, if an instrument reading of 10,000 ppm or greater is measured, a leak is detected.	§ 60.482-8(a)(1) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f)	§ 60.482-1(g) [G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
GRP-VVFUG	EU	60VV-ALL	VOC	40 CFR Part 60, Subpart VV	§ 60.482-8(b) § 60.482-1(a) § 60.482-1(b) § 60.482-1(g) § 60.482-8(a) § 60.482-8(a)(2) § 60.482-8(c)(1) § 60.482-8(c)(2) § 60.482-8(d) § 60.482-9(a) § 60.482-9(b) § 60.482-9(e) § 60.482-9(f) § 60.486(k)	For valves in heavy liquid service, if an instrument reading of 10,000 ppm or greater is measured, a leak is detected.	§ 60.482-8(a)(1) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f)	§ 60.482-1(g) [G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
GRP-VVFUG	EU	60VV-ALL	VOC	40 CFR Part 60, Subpart VV	§ 60.482-8(b) § 60.482-1(a) § 60.482-1(b) § 60.482-1(g) § 60.482-8(a) § 60.482-8(a)(2)	For pressure relief devices in light liquid or in heavy liquid service, if an instrument reading of 10,000 ppm or greater is measured, a leak is	§ 60.482-8(a)(1) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f)	§ 60.482-1(g) [G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.482-8(c)(1) § 60.482-8(c)(2) § 60.482-8(d) § 60.482-9(a) § 60.482-9(b) § 60.486(k)	detected.		§ 60.486(j)	
GRP-VVFUG	EU	60VV-ALL	VOC	40 CFR Part 60, Subpart VV	§ 60.482-8(b) § 60.482-1(a) § 60.482-1(b) § 60.482-1(g) § 60.482-8(a) § 60.482-8(a)(2) § 60.482-8(c)(1) § 60.482-8(c)(2) § 60.482-8(d) § 60.482-9(a) § 60.482-9(b) § 60.486(k)	For flanges and other connectors, if an instrument reading of 10,000 ppm or greater is measured, a leak is detected.	§ 60.482-8(a)(1) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f)	§ 60.482-1(g) [G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
GRP-VVFUG	EU	60VV-ALL	VOC	40 CFR Part 60, Subpart VV	[G]§ 60.482-1(e) § 60.486(k)	Equipment that an owner or operator designates as being in VOC service less than 300 hours (hr)/yr is excluded from the requirements of §§ 60.482-2 through 60.482-10 if it is identified as required in §60.486(e)(6) and it meets any of the conditions specified in paragraphs (e)(1) through (3) of this section. §60.482-1(e)(1)-(3)	None	§ 60.486 [G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(6) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
GRP-VVFUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(d)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for	None	§ 60.486(e) § 60.486(e)(1) § 60.486(e)(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						equipment in vacuum service.			
GRP-VVFUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-2 [G]§ 60.482-9 § 63.648(a)(2) § 63.648(f) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pumps in light liquid service complying with §60.482-2.	[G]§ 60.482-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(d)(6) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
GRP-VVFUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-3 [G]§ 60.482-9 § 63.648(a)(2) § 63.648(i) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for compressors complying with §60.482-3.	[G]§ 60.482-3 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(d)(6) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
GRP-VVFUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) § 60.482-4(a) § 60.482-4(b)(1) [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pressure relief devices in gas/vapor service.	§ 60.482-4(b)(2) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(3) [G]§ 60.486(e)(4) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-VVFUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-5 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for sampling connection systems complying with §60.482-5.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
GRP-VVFUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-6 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for open-ended valves or lines complying with §60.482-6.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
GRP-VVFUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-7 [G]§ 60.482-9 [G]§ 60.483-1 [G]§ 60.483-2 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for valves in gas/vapor service or in light liquid service complying with §60.482-7.	[G]§ 60.482-7 [G]§ 60.483-1 [G]§ 60.483-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) [G]§ 60.486(g) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(d) § 60.487(e)
GRP-VVFUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for valves in heavy liquid service complying with §60.482-8.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
GRP-VVFUG	EU	63CCV	112(B)	40 CFR Part 63,	§ 63.648(a)	Comply with the	[G]§ 60.482-8	[G]§ 60.486(a)	§ 60.487(a)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		V-ALL	HAPS	Subpart CC	§ 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	specified 40 CFR Part 60, Subpart VV requirements for pumps in heavy liquid service complying with §60.482-8.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	[G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
GRP-VVFUG	EU	63CCV V-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for flanges or other connectors complying with §60.482-8.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
GRP-VVFUG	EU	63CCV V-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pressure relief devices in light liquid service complying with §60.482-8.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
GRP-VVFUG	EU	63CCV V-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pressure relief devices in heavy liquid service complying with §60.482-8.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
GRP-VVFUG	EU	63CCV V-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	[G]§ 63.648(g)	Compressors in hydrogen service are	[G]§ 63.648(g)	§ 63.648(h) § 63.655(d)(3)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						exempt from the requirements of §63.648(a) and (c), if an owner or operator demonstrates that a compressor is in hydrogen service. §63.648(g)(1)-(2).		§ 63.655(i)(5)	
GRP-WASH1	EU	R5412-0057	VOC	30 TAC Chapter 115, Degreasing Processes	§ 115.412(1) [G]§ 115.412(1)(A) § 115.412(1)(C) § 115.412(1)(D) [G]§ 115.412(1)(F) § 115.417(1)	Cold solvent cleaning. No person shall own or operate a system utilizing a VOC for the cold solvent cleaning of objects without the controls listed in §115.412(1)(A)-(F).	[G]§ 115.415(1) § 115.415(3) ** See Periodic Monitoring Summary	None	None
GRP-WASH2	EU	R5412-0057	VOC	30 TAC Chapter 115, Degreasing Processes	§ 115.412(1) [G]§ 115.412(1)(A) § 115.412(1)(C) § 115.412(1)(D) [G]§ 115.412(1)(F) § 115.417(1)	Cold solvent cleaning. No person shall own or operate a system utilizing a VOC for the cold solvent cleaning of objects without the controls listed in §115.412(1)(A)-(F).	[G]§ 115.415(1) § 115.415(3) ** See Periodic Monitoring Summary	None	None
HCU-942H1/2	EU	60J-0024	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
HCU-942H3	EU	60J-0024	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.106(a) [G]§ 60.106(e)(1)		
HCU-943-A/B	EU	60Ja-0161	Hydrogen Sulfide	40 CFR Part 60, Subpart Ja	§ 60.100a(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 60, Subpart Ja
HCU-943-C	EU	60Ja-0161	Hydrogen Sulfide	40 CFR Part 60, Subpart Ja	§ 60.100a(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 60, Subpart Ja
HFAU-443-H	EU	63DDDDD-001	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
MC-24/25	EP	63CC-1003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(1)	All miscellaneous process vents from	[G]§ 63.645(g) § 63.645(h)	§ 63.655(g)(7)(ii) § 63.655(i)(5)	§ 63.645(h)(2) § 63.655(f)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.645(h)(1) § 63.645(h)(2)		§ 63.655(f)(1)(ii) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i)
NSTF TK 100 99	EU	60IIII-005	CO	40 CFR Part 60, Subpart IIII	§ 60.4205(b) § 60.4202(a)(2) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218 § 89.112(a)	Owners and operators of emergency stationary CI ICE, that are not fire pump engines, with a maximum engine power greater than or equal to 37 KW and less than 130 KW and a displacement of less than 10 liters per cylinder and is a 2007 model year and later must comply with a CO emission limit of 5.0 g/KW-hr, as stated in 40 CFR 60.4202(a)(2) and 40 CFR 89.112(a).	§ 60.4209(a)	§ 60.4214(b)	[G]§ 60.4214(d)
NSTF TK 100 99	EU	60IIII-005	NMHC and NO_X	40 CFR Part 60, Subpart IIII	§ 60.4205(b) § 60.4202(a)(2) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218 § 89.112(a)	Owners and operators of emergency stationary CI ICE, that are not fire pump engines, with a maximum engine power greater than or equal to 75 KW and less than or equal to 560 KW and a displacement of less than 10 liters per cylinder and is a 2007 model year and later must comply with an NMHC+NOx emission limit of 4.0 g/KW-hr, as stated in 40 CFR	§ 60.4209(a)	§ 60.4214(b)	[G]§ 60.4214(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						60.4202(a)(2) and 40 CFR 89.112(a).			
NSTF TK 100 99	EU	60IIII-005	PM (Opacity)	40 CFR Part 60, Subpart IIII	§ 60.4205(b) § 60.4202(a)(2) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218 § 89.113(a)(1) § 89.113(a)(2) § 89.113(a)(3)	Emergency stationary CI ICE, that are not fire pump engines, with displacement < 10 lpc and not constant-speed engines, with max engine power < 2237 KW and a 2007 model year and later or max engine power > 2237 KW and a 2011 model year and later, must comply with following opacity emission limits: 20% during acceleration, 15% during lugging, 50% during peaks in either acceleration or lugging modes as stated in §60.4202(a)(1)-(2), (b)(2) and §89.113(a)(1)-(3) and §1039.105(b)(1)-(3).	§ 60.4209(a)	§ 60.4214(b)	[G]§ 60.4214(d)
NSTF TK 100 99	EU	60IIII-005	PM	40 CFR Part 60, Subpart IIII	§ 60.4205(b) § 60.4202(a)(2) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218 § 89.112(a)	Owners and operators of emergency stationary CI ICE, that are not fire pump engines, with a maximum engine power greater than or equal to 75 KW and less than 130 KW and a displacement of less than 10 liters per cylinder and is a 2007 model year and later must comply with a PM emission limit of 0.30 g/KW-hr, as stated in 40	§ 60.4209(a)	§ 60.4214(b)	[G]§ 60.4214(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						CFR 60.4202(a)(2) and 40 CFR 89.112(a).			
NSTF TK 100 99	EU	63ZZZZ -009	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(c)	Stationary RICE subject to Regulations under 40 CFR Part 60. An affected source that meets any of the criteria in paragraphs (c)(1) through (7) of this section must meet the requirements of this part by meeting the requirements of 40 CFR part 60 subpart IIII, for compression ignition engines or 40 CFR part 60 subpart JJJJ, for spark ignition engines as applicable. No further requirements apply for such engines under this part.	None	None	None
NSTF TK 151	EU	60IIII-004	NO_X	40 CFR Part 60, Subpart IIII	§ 60.4205(a)-Table 1 § 60.4206 § 60.4207(b) § 60.4211(b) § 60.4211(b)(1) [G]§ 60.4211(f) § 60.4218	Owners and operators of emergency stationary CI ICE, that are not fire pump engines, with a maximum engine power greater than or equal to 37 KW and a displacement of less than 10 liters per cylinder and is a pre-2007 model year must comply with a NOx emission limit of 9.2 g/KW-hr, as listed in Table 1 to this subpart.	§ 60.4209(a)	§ 60.4214(b)	[G]§ 60.4214(d)
NSTF TK 151	EU	63ZZZZ -009	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(c)	Stationary RICE subject to Regulations under 40 CFR Part 60. An affected	None	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						source that meets any of the criteria in paragraphs (c)(1) through (7) of this section must meet the requirements of this part by meeting the requirements of 40 CFR part 60 subpart IIII, for compression ignition engines or 40 CFR part 60 subpart JJJJ, for spark ignition engines as applicable. No further requirements apply for such engines under this part.			
PRO-WWTU	EU	61FF-0216	Benzene	40 CFR Part 61, Subpart FF	§ 61.348(a)(1) § 61.348(a)(1)(i) § 61.348(a)(2) § 61.348(a)(3) § 61.348(a)(4) § 61.348(f) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(i)(C) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	The owner or operator shall design, install, operate and maintain a treatment process that removes or destroys benzene as specified.	§ 61.348(f) § 61.349(a)(1)(i) § 61.349(e) § 61.349(f) § 61.354(a)(2) § 61.354(c) § 61.354(c)(1) [G]§ 61.355(h)	§ 61.354(a)(2) § 61.354(c) § 61.354(c)(1) § 61.356(e) § 61.356(e)(1) § 61.356(e)(2) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(A) § 61.356(h) [G]§ 61.356(i) § 61.356(j) § 61.356(j)(1) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(4)	§ 61.357(d)(7) § 61.357(d)(7)(ii) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(A)
PRO-WWTU	EU	63G-009	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.138(a)(7)(i)(A) [G]§ 63.132(f) § 63.139(b) § 63.139(c)(1)	For combinations of treatment processes or control devices, the wastewater stream or	§ 63.138(a)(7)(i)(D) § 63.138(j)(1) § 63.139(d)(2)(i) § 63.139(e)	§ 63.138(a)(7)(i)(C) § 63.138(j)(1) § 63.143(f) § 63.147(b)	§ 63.138(a)(7)(i)(C) § 63.146(b)(2) § 63.146(b)(4) § 63.146(b)(6)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.139(c)(1)(i) § 63.139(f) § 63.140(a) § 63.140(b) § 63.140(c) [G]§ 63.148(d) § 63.148(e)	vented gas stream shall be conveyed by hard-piping between the treatment processes or control devices.	§ 63.143(e) § 63.143(e)(1) § 63.143(f) § 63.143(g) § 63.145(a) § 63.145(a)(1) § 63.145(a)(2) § 63.148(b)(1)(ii) § 63.148(b)(2)(iii) § 63.148(b)(3) [G]§ 63.148(c) § 63.148(g) § 63.148(g)(2) § 63.148(h) § 63.148(h)(2)	§ 63.147(b)(2) § 63.147(b)(5) § 63.147(b)(7) § 63.147(d) § 63.148(g)(2) § 63.148(h)(2) § 63.148(i)(1) § 63.148(i)(2) [G]§ 63.148(i)(4) § 63.148(i)(5) § 63.148(i)(6) [G]§ 63.152(a) [G]§ 63.152(f)	§ 63.146(b)(7) § 63.146(b)(7)(ii) § 63.146(b)(7)(ii)(A) § 63.146(b)(7)(ii)(B) § 63.146(b)(9) § 63.146(b)(9)(i) § 63.146(e) § 63.146(e)(1) § 63.148(j) § 63.148(j)(1) [G]§ 63.152(a) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(2)(iv) § 63.152(c)(3) § 63.152(c)(3)(i) § 63.152(c)(3)(ii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
RTO	EU	60QQQ -0002	VOC	40 CFR Part 60, Subpart QQQ	§ 60.692-5 § 60.692-1(a) § 60.692-5(a) § 60.692-5(d) [G]§ 60.692-5(e) § 60.692-6(a) § 60.692-6(b) § 60.692-7(b)	Standard for closed vent system and control devices.	§ 60.695(a) § 60.695(a)(1) § 60.696(a)	§ 60.695(a)(1) § 60.697(a) § 60.697(d) [G]§ 60.697(e) § 60.697(f)(1) [G]§ 60.697(f)(2) § 60.697(f)(3) § 60.697(f)(3)(i) § 60.697(f)(3)(iii) § 60.697(f)(3)(iv) § 60.697(f)(3)(v) § 60.697(f)(3)(vi) § 60.697(f)(3)(vii) § 60.697(f)(3)(viii)	§ 60.698(b)(1) § 60.698(d) § 60.698(d)(1) § 60.698(e)
RTO	CD	61FF-	Benzene	40 CFR Part 61,	§ 61.349(a)	For each closed-vent	§ 61.349(a)(1)(i)	§ 61.354(c)	§ 61.357(d)(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		002		Subpart FF	§ 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(i)(C) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 61.349(e) § 61.349(f) § 61.354(c) § 61.354(c)(1) [G]§ 61.355(h) ** See CAM Summary	§ 61.354(c)(1) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(A) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(4)	§ 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(A)
SRU-543	EU	R2007-0003	SO_2	30 TAC Chapter 112, Sulfur Compounds	§ 112.7(a)	No person may cause, suffer, allow, or permit emissions of SO2 to exceed the emission limits specified for stack effluent flow rates < 4,000 scfm as determined by the specified equation.	§ 112.2(a) ** See CAM Summary	§ 112.2(c)	§ 112.2(b)
SRU-543	EU	60Ja-0177	Hydrogen Sulfide	40 CFR Part 60, Subpart Ja	§ 60.100a(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 60, Subpart Ja
SRU-543	EU	63UUU-3000	SO_2	40 CFR Part 63, Subpart UUU	§ 63.1568(a)(1)-Table29.1.a § 63.1568(a)(1) § 63.1568(a)(2) § 63.1568(a)(2)-Table30.1 § 63.1568(a)(3)	For each new or existing Claus SRU part of a sulfur recovery plant of 20 long tons per day or more and subject to NSPS for sulfur oxides in 40 CFR §60.104(a)(2),	§ 63.1568(b)(1) § 63.1568(b)(1)-Table31.1.a § 63.1568(c)(1)-Table34.1.a § 63.1572(a)(1)-Table40.4	§ 63.1568(b)(1)-Table31.1.a § 63.1568(c)(1)-Table34.1.a § 63.1570(c) [G]§ 63.1576(a) [G]§ 63.1576(b)	§ 63.1568(b)(6) § 63.1568(b)(7) § 63.1570(f) § 63.1571(a) [G]§ 63.1574(a) § 63.1574(d) § 63.1574(d)-Table42.1

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.1568(b)(3) § 63.1568(b)(4) § 63.1568(b)(5) § 63.1568(b)(5)-Table33.1.a § 63.1568(c)(1) § 63.1568(c)(1)-Table35.1 § 63.1568(c)(2) § 63.1570(a) § 63.1570(c) § 63.1570(d) § 63.1570(g)	you must meet the emission limit for each process vent of 250ppmv (dry basis) of sulfur dioxide (SO2) at zero percent excess air if you use an oxidation or reduction control system followed by incineration.	§ 63.1572(a)(1)-Table40.8 § 63.1572(a)(2) § 63.1572(a)(3) § 63.1572(a)(4) [G]§ 63.1572(d)	§ 63.1576(d) § 63.1576(e) § 63.1576(f) § 63.1576(g) § 63.1576(h) § 63.1576(i)	§ 63.1574(d)-Table42.2 § 63.1574(d)-Table42.3 § 63.1575(a) § 63.1575(a)-Table43.1 [G]§ 63.1575(b) [G]§ 63.1575(c) [G]§ 63.1575(e) [G]§ 63.1575(f) § 63.1575(g) [G]§ 63.1575(h)
SRU-544	EU	R2007-0003	SO_2	30 TAC Chapter 112, Sulfur Compounds	§ 112.7(a)	No person may cause, suffer, allow, or permit emissions of SO2 to exceed the emission limits specified for stack effluent flow rates < 4,000 scfm as determined by the specified equation.	§ 112.2(a) ** See CAM Summary	§ 112.2(c)	§ 112.2(b)
SRU-544	EU	60Ja-0177	Hydrogen Sulfide	40 CFR Part 60, Subpart Ja	§ 60.100a(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 60, Subpart Ja
SRU-544	EU	63UUU-3000	SO_2	40 CFR Part 63, Subpart UUU	§ 63.1568(a)(1)-Table29.1.a § 63.1568(a)(1) § 63.1568(a)(2) § 63.1568(a)(2)-Table30.1	For each new or existing Claus SRU part of a sulfur recovery plant of 20 long tons per day or more and subject to NSPS for sulfur oxides in	§ 63.1568(b)(1) § 63.1568(b)(1)-Table31.1.a § 63.1568(c)(1)-Table34.1.a § 63.1572(a)(1)-	§ 63.1568(b)(1)-Table31.1.a § 63.1568(c)(1)-Table34.1.a § 63.1570(c) [G]§ 63.1576(a)	§ 63.1568(b)(6) § 63.1568(b)(7) § 63.1570(f) § 63.1571(a) [G]§ 63.1574(a) § 63.1574(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.1568(a)(3) § 63.1568(b)(3) § 63.1568(b)(4) § 63.1568(b)(5) § 63.1568(b)(5)-Table33.1.a § 63.1568(c)(1) § 63.1568(c)(1)-Table35.1 § 63.1568(c)(2) § 63.1570(a) § 63.1570(c) § 63.1570(d) § 63.1570(g)	40 CFR §60.104(a)(2), you must meet the emission limit for each process vent of 250ppmv (dry basis) of sulfur dioxide (SO2) at zero percent excess air if you use an oxidation or reduction control system followed by incineration.	Table40.4 § 63.1572(a)(1)-Table40.8 § 63.1572(a)(2) § 63.1572(a)(3) § 63.1572(a)(4) [G]§ 63.1572(d)	[G]§ 63.1576(b) § 63.1576(d) § 63.1576(e) § 63.1576(f) § 63.1576(g) § 63.1576(h) § 63.1576(i)	§ 63.1574(d)-Table42.1 § 63.1574(d)-Table42.2 § 63.1574(d)-Table42.3 § 63.1575(a) § 63.1575(a)-Table43.1 [G]§ 63.1575(b) [G]§ 63.1575(c) [G]§ 63.1575(e) [G]§ 63.1575(f) § 63.1575(g) [G]§ 63.1575(h)
SRU-545	EU	R2007-0003	SO_2	30 TAC Chapter 112, Sulfur Compounds	§ 112.7(a)	No person may cause, suffer, allow, or permit emissions of SO2 to exceed the emission limits specified for stack effluent flow rates < 4,000 scfm as determined by the specified equation.	§ 112.2(a) ** See CAM Summary	§ 112.2(c)	§ 112.2(b)
SRU-545	EU	60Ja-0177	Hydrogen Sulfide	40 CFR Part 60, Subpart Ja	§ 60.100a(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 60, Subpart Ja
SRU-545	EU	63UUU-3001	112(B) HAPS	40 CFR Part 63, Subpart UUU	§ 63.1569(a)(1)(i)-Table36.1 § 63.1569(a)(1) § 63.1569(a)(3) § 63.1569(b)(2)	If you elect to install an automated system (Option 1), you must install and operate a device (including a flow	§ 63.1569(b)(1) § 63.1569(b)(1)-Table37.1 § 63.1569(c)(1)-Table39.1	§ 63.1569(b)(1)-Table37.1 § 63.1569(c)(1)-Table39.1 § 63.1569(c)(1)-	§ 63.1569(b)(3) § 63.1569(b)(4) § 63.1569(c)(1)-Table39.5 § 63.1570(f)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.1569(b)(2)-Table38.1.a § 63.1569(c)(1) § 63.1570(a) § 63.1570(c) § 63.1570(d) § 63.1570(g)	indicator, level recorder, or electronic valve position monitor) to demonstrate, either continuously or at least every hour, whether flow is present in the bypass line. Install the device at or near as practical to the entrance to any bypass line that could divert the vent stream away from the control device to the atmosphere.	§ 63.1571(a) § 63.1571(a)(1) [G]§ 63.1571(b)	Table39.5 § 63.1570(c) [G]§ 63.1576(a) § 63.1576(d) § 63.1576(e) § 63.1576(f) § 63.1576(g) § 63.1576(h) § 63.1576(i)	§ 63.1571(a) [G]§ 63.1574(a) § 63.1574(d) § 63.1574(d)-Table42.1 § 63.1574(d)-Table42.2 § 63.1574(d)-Table42.3 § 63.1575(a) § 63.1575(a)-Table43.1 [G]§ 63.1575(b) [G]§ 63.1575(c) [G]§ 63.1575(d) [G]§ 63.1575(f) § 63.1575(g) [G]§ 63.1575(h)
SRU-545	EU	63UUU-3001	SO_2	40 CFR Part 63, Subpart UUU	§ 63.1568(a)(1)-Table29.1.a § 63.1568(a)(1) § 63.1568(a)(2) § 63.1568(a)(2)-Table30.1 § 63.1568(a)(3) § 63.1568(b)(3) § 63.1568(b)(4) § 63.1568(b)(5) § 63.1568(b)(5)-Table33.1.a § 63.1568(c)(1) § 63.1568(c)(1)-Table35.1 § 63.1568(c)(2) § 63.1570(a) § 63.1570(c) § 63.1570(d) § 63.1570(g)	For each new or existing Claus SRU part of a sulfur recovery plant of 20 long tons per day or more and subject to NSPS for sulfur oxides in 40 CFR §60.104(a)(2), you must meet the emission limit for each process vent of 250ppmv (dry basis) of sulfur dioxide (SO2) at zero percent excess air if you use an oxidation or reduction control system followed by incineration.	§ 63.1568(b)(1) § 63.1568(b)(1)-Table31.1.a § 63.1568(c)(1)-Table34.1.a § 63.1572(a)(1)-Table40.4 § 63.1572(a)(1)-Table40.8 § 63.1572(a)(2) § 63.1572(a)(3) § 63.1572(a)(4) [G]§ 63.1572(d)	§ 63.1568(b)(1)-Table31.1.a § 63.1568(c)(1)-Table34.1.a § 63.1570(c) [G]§ 63.1576(a) [G]§ 63.1576(b) § 63.1576(d) § 63.1576(e) § 63.1576(f) § 63.1576(g) § 63.1576(h) § 63.1576(i)	§ 63.1568(b)(6) § 63.1568(b)(7) § 63.1570(f) § 63.1571(a) [G]§ 63.1574(a) § 63.1574(d) § 63.1574(d)-Table42.1 § 63.1574(d)-Table42.2 § 63.1574(d)-Table42.3 § 63.1575(a) § 63.1575(a)-Table43.1 [G]§ 63.1575(b) [G]§ 63.1575(c) [G]§ 63.1575(e) [G]§ 63.1575(f) § 63.1575(g) [G]§ 63.1575(h)
SRU-546	EU	R2007-0003	SO_2	30 TAC Chapter 112, Sulfur Compounds	§ 112.7(a)	No person may cause, suffer, allow, or permit emissions of SO2 to	§ 112.2(a) ** See CAM Summary	§ 112.2(c)	§ 112.2(b)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						exceed the emission limits specified for stack effluent flow rates < 4,000 scfm as determined by the specified equation.			
SRU-546	EU	60Ja-0177	Hydrogen Sulfide	40 CFR Part 60, Subpart Ja	§ 60.100a(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 60, Subpart Ja
SRU-546	EU	63UUU-3001	112(B) HAPS	40 CFR Part 63, Subpart UUU	§ 63.1569(a)(1)(i)-Table36.1 § 63.1569(a)(1) § 63.1569(a)(3) § 63.1569(b)(2) § 63.1569(b)(2)-Table38.1.a § 63.1569(c)(1) § 63.1570(a) § 63.1570(c) § 63.1570(d) § 63.1570(g)	If you elect to install an automated system (Option 1), you must install and operate a device (including a flow indicator, level recorder, or electronic valve position monitor) to demonstrate, either continuously or at least every hour, whether flow is present in the bypass line. Install the device at or near as practical to the entrance to any bypass line that could divert the vent stream away from the control device to the atmosphere.	§ 63.1569(b)(1) § 63.1569(b)(1)-Table37.1 § 63.1569(c)(1)-Table39.1 § 63.1571(a) § 63.1571(a)(1) [G]§ 63.1571(b)	§ 63.1569(b)(1)-Table37.1 § 63.1569(c)(1)-Table39.1 § 63.1569(c)(1)-Table39.5 § 63.1570(c) [G]§ 63.1576(a) § 63.1576(d) § 63.1576(e) § 63.1576(f) § 63.1576(g) § 63.1576(h) § 63.1576(i)	§ 63.1569(b)(3) § 63.1569(b)(4) § 63.1569(c)(1)-Table39.5 § 63.1570(f) § 63.1571(a) [G]§ 63.1574(a) § 63.1574(d) § 63.1574(d)-Table42.1 § 63.1574(d)-Table42.2 § 63.1574(d)-Table42.3 § 63.1575(a) § 63.1575(a)-Table43.1 [G]§ 63.1575(b) [G]§ 63.1575(c) [G]§ 63.1575(d) [G]§ 63.1575(f) § 63.1575(g) [G]§ 63.1575(h)
SRU-546	EU	63UUU-3001	SO_2	40 CFR Part 63, Subpart UUU	§ 63.1568(a)(1)-Table29.1.a	For each new or existing Claus SRU part of a	§ 63.1568(b)(1) § 63.1568(b)(1)-	§ 63.1568(b)(1)-Table31.1.a	§ 63.1568(b)(6) § 63.1568(b)(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.1568(a)(1) § 63.1568(a)(2) § 63.1568(a)(2)-Table30.1 § 63.1568(a)(3) § 63.1568(b)(3) § 63.1568(b)(4) § 63.1568(b)(5) § 63.1568(b)(5)-Table33.1.a § 63.1568(c)(1) § 63.1568(c)(1)-Table35.1 § 63.1568(c)(2) § 63.1570(a) § 63.1570(c) § 63.1570(d) § 63.1570(g)	sulfur recovery plant of 20 long tons per day or more and subject to NSPS for sulfur oxides in 40 CFR §60.104(a)(2), you must meet the emission limit for each process vent of 250ppmv (dry basis) of sulfur dioxide (SO2) at zero percent excess air if you use an oxidation or reduction control system followed by incineration.	Table31.1.a § 63.1568(c)(1)-Table34.1.a § 63.1572(a)(1)-Table40.4 § 63.1572(a)(1)-Table40.8 § 63.1572(a)(2) § 63.1572(a)(3) § 63.1572(a)(4) [G]§ 63.1572(d)	§ 63.1568(c)(1)-Table34.1.a § 63.1570(c) [G]§ 63.1576(a) [G]§ 63.1576(b) § 63.1576(d) § 63.1576(e) § 63.1576(f) § 63.1576(g) § 63.1576(h) § 63.1576(i)	§ 63.1570(f) § 63.1571(a) [G]§ 63.1574(a) § 63.1574(d) § 63.1574(d)-Table42.1 § 63.1574(d)-Table42.2 § 63.1574(d)-Table42.3 § 63.1575(a) § 63.1575(a)-Table43.1 [G]§ 63.1575(b) [G]§ 63.1575(c) [G]§ 63.1575(e) [G]§ 63.1575(f) § 63.1575(g) [G]§ 63.1575(h)
T-106	EU	R5112-0005	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(a)(1) § 115.112(a)(2) § 115.112(a)(2)(A) § 115.112(a)(2)(B) § 115.112(a)(2)(C) § 115.112(a)(2)(D) § 115.112(a)(2)(E) § 115.112(a)(2)(F) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)
T-106	EU	60K-001	VOC	40 CFR Part 60, Subpart K	§ 60.112(a)(1)	Storage vessels holding petroleum liquids with a true vapor pressure of 78 mm Hg (1.5 psia) or greater but not greater than 570 mm Hg (11.1 psia) shall have a floating roof, a vapor recovery system, or their equivalents.	§ 60.113(a) § 60.113(b) ** See Periodic Monitoring Summary	§ 60.113(a)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T-106	EU	63CC-0254	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(6)	After compliance dates specified in paragraph (h) of this section, a Group 2 storage vessel that is subject to the control requirements of 40 CFR Part 60, Subpart K is required to comply only with the provisions of 40 CFR Part 60, Subpart K.	None	None	None
T-106	EU	63CC-1254	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.119(a)(1) § 63.119(c)(1) § 63.119(c)(1)(i) § 63.119(c)(1)(ii) § 63.119(c)(1)(iii) [G]§ 63.119(c)(3) § 63.119(c)(4) § 63.120(b)(10)(i) § 63.120(b)(5)(i) § 63.120(b)(5)(ii) § 63.120(b)(6)(i) § 63.120(b)(6)(ii) [G]§ 63.120(b)(7) § 63.120(b)(8) [G]§ 63.646(f) § 63.646(g)	Each owner or operator of a Group 1 storage vessel subject to this subpart shall comply with the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.120(b)(1)(i) § 63.120(b)(1)(iii) § 63.120(b)(1)(iv) § 63.120(b)(10) § 63.120(b)(2)(i) § 63.120(b)(2)(ii) § 63.120(b)(2)(iii) § 63.120(b)(3) § 63.120(b)(4) § 63.646(b)(1) § 63.646(e)	[G]§ 63.120(b)(7) § 63.120(b)(8) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1) § 63.655(i)(5)	§ 63.120(b)(10)(ii) § 63.120(b)(10)(iii) § 63.120(b)(9) § 63.642(f) § 63.655(f) [G]§ 63.655(f)(1)(i)(B) § 63.655(f)(6) § 63.655(g) [G]§ 63.655(g)(3) § 63.655(h) § 63.655(h)(1) § 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(B) § 63.655(h)(2)(i)(C) § 63.655(h)(2)(ii) [G]§ 63.655(h)(6)
T-107	EU	R5112-0005	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(a)(1) § 115.112(a)(2) § 115.112(a)(2)(A) § 115.112(a)(2)(B) § 115.112(a)(2)(C) § 115.112(a)(2)(D) § 115.112(a)(2)(E) § 115.112(a)(2)(F) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T-107	EU	60K-001	VOC	40 CFR Part 60, Subpart K	§ 60.112(a)(1)	Storage vessels holding petroleum liquids with a true vapor pressure of 78 mm Hg (1.5 psia) or greater but not greater than 570 mm Hg (11.1 psia) shall have a floating roof, a vapor recovery system, or their equivalents.	§ 60.113(a) § 60.113(b) ** See Periodic Monitoring Summary	§ 60.113(a)	None
T-107	EU	63CC-0254	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(6)	After compliance dates specified in paragraph (h) of this section, a Group 2 storage vessel that is subject to the control requirements of 40 CFR Part 60, Subpart K is required to comply only with the provisions of 40 CFR Part 60, Subpart K.	None	None	None
T-107	EU	63CC-1254	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.119(a)(1) § 63.119(c)(1) § 63.119(c)(1)(i) § 63.119(c)(1)(ii) § 63.119(c)(1)(iii) [G]§ 63.119(c)(3) § 63.119(c)(4) § 63.120(b)(10)(i) § 63.120(b)(5)(i) § 63.120(b)(5)(ii) § 63.120(b)(6)(i) § 63.120(b)(6)(ii) [G]§ 63.120(b)(7) § 63.120(b)(8) [G]§ 63.646(f) § 63.646(g)	Each owner or operator of a Group 1 storage vessel subject to this subpart shall comply with the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.120(b)(1)(i) § 63.120(b)(1)(iii) § 63.120(b)(1)(iv) § 63.120(b)(10) § 63.120(b)(2)(i) § 63.120(b)(2)(ii) § 63.120(b)(2)(iii) § 63.120(b)(3) § 63.120(b)(4) § 63.646(b)(1) § 63.646(e)	[G]§ 63.120(b)(7) § 63.120(b)(8) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1) § 63.655(i)(5)	§ 63.120(b)(10)(ii) § 63.120(b)(10)(iii) § 63.120(b)(9) § 63.642(f) § 63.655(f) [G]§ 63.655(f)(1)(i)(B) § 63.655(f)(6) § 63.655(g) [G]§ 63.655(g)(3) § 63.655(h) § 63.655(h)(1) § 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(B) § 63.655(h)(2)(i)(C) § 63.655(h)(2)(ii) [G]§ 63.655(h)(6)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T-1912	EU	R5112-0001	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(a)(1) § 115.112(a)(2) § 115.112(a)(2)(A) § 115.112(a)(2)(B) § 115.112(a)(2)(C) § 115.112(a)(2)(D) § 115.112(a)(2)(E) § 115.114(a)(1)(A)	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(7)	§ 115.114(a)(1)(B) § 115.118(a)(3)
T-1912	EU	60QQQ-0007	VOC	40 CFR Part 60, Subpart QQQ	§ 60.692-3(d) § 60.692-1(a) § 60.692-6(a) § 60.692-6(b) § 60.692-7(b)	Storage vessels, including slop oil tanks and other auxiliary tanks that are subject to the requirements of 40 CFR subparts K, Ka, or Kb, are not subject to the requirements of this section.	§ 60.692-3(a)(4) § 60.696(a)	§ 60.697(a) § 60.697(c) [G]§ 60.697(e) § 60.697(f)(1) [G]§ 60.697(f)(2)	§ 60.698(b)(1) § 60.698(e)
T-1912	EU	61FF-0005	Benzene	40 CFR Part 61, Subpart FF	§ 61.351(a) § 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii) § 61.351(a)(1) § 61.351(b)	As an alternative to the standards for tanks specified in § 61.343, an owner or operator may elect to comply with one of the following §61.351(a)(1)-(3):	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5)	§ 60.115b § 60.115b(a)(2) § 61.356(k)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3) § 61.357(e) § 61.357(f)
T-2111	EU	R5112-0004	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(a)(1) § 115.112(a)(2) § 115.112(a)(2)(A) § 115.112(a)(2)(B) § 115.112(a)(2)(C) § 115.112(a)(2)(D) § 115.112(a)(2)(E) § 115.112(a)(2)(F)	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.114(a)(2)(A) § 115.114(a)(4)(A)				
T-2111	EU	63CC-0254	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
T-2111	EU	63CC-1254	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.119(a)(1) § 63.119(c)(1) § 63.119(c)(1)(i) § 63.119(c)(1)(ii) § 63.119(c)(1)(iii) [G]§ 63.119(c)(3) § 63.119(c)(4) § 63.120(b)(10)(i) § 63.120(b)(5)(i) § 63.120(b)(5)(ii) § 63.120(b)(6)(i) § 63.120(b)(6)(ii) [G]§ 63.120(b)(7) § 63.120(b)(8) [G]§ 63.646(f) § 63.646(g)	Each owner or operator of a Group 1 storage vessel subject to this subpart shall comply with the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.120(b)(1)(i) § 63.120(b)(1)(iii) § 63.120(b)(1)(iv) § 63.120(b)(10) § 63.120(b)(2)(i) § 63.120(b)(2)(ii) § 63.120(b)(2)(iii) § 63.120(b)(3) § 63.120(b)(4) § 63.646(b)(1) § 63.646(e)	[G]§ 63.120(b)(7) § 63.120(b)(8) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1) § 63.655(i)(5)	§ 63.120(b)(10)(ii) § 63.120(b)(10)(iii) § 63.120(b)(9) § 63.642(f) § 63.655(f) [G]§ 63.655(f)(1)(i)(B) § 63.655(f)(6) § 63.655(g) [G]§ 63.655(g)(3) § 63.655(h) § 63.655(h)(1) § 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(B) § 63.655(h)(2)(i)(C) § 63.655(h)(2)(ii) [G]§ 63.655(h)(6)
T-2112	EU	R5112-0004	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(a)(1) § 115.112(a)(2) § 115.112(a)(2)(A) § 115.112(a)(2)(B) § 115.112(a)(2)(C) § 115.112(a)(2)(D) § 115.112(a)(2)(E) § 115.112(a)(2)(F) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T-2112	EU	63CC-0254	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
T-2112	EU	63CC-1254	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.119(a)(1) § 63.119(c)(1) § 63.119(c)(1)(i) § 63.119(c)(1)(ii) § 63.119(c)(1)(iii) [G]§ 63.119(c)(3) § 63.119(c)(4) § 63.120(b)(10)(i) § 63.120(b)(5)(i) § 63.120(b)(5)(ii) § 63.120(b)(6)(i) § 63.120(b)(6)(ii) [G]§ 63.120(b)(7) § 63.120(b)(8) [G]§ 63.646(f) § 63.646(g)	Each owner or operator of a Group 1 storage vessel subject to this subpart shall comply with the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.120(b)(1)(i) § 63.120(b)(1)(iii) § 63.120(b)(1)(iv) § 63.120(b)(10) § 63.120(b)(2)(i) § 63.120(b)(2)(ii) § 63.120(b)(2)(iii) § 63.120(b)(3) § 63.120(b)(4) § 63.646(b)(1) § 63.646(e)	[G]§ 63.120(b)(7) § 63.120(b)(8) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1) § 63.655(i)(5)	§ 63.120(b)(10)(ii) § 63.120(b)(10)(iii) § 63.120(b)(9) § 63.642(f) § 63.655(f) [G]§ 63.655(f)(1)(i)(B) § 63.655(f)(6) § 63.655(g) [G]§ 63.655(g)(3) § 63.655(h) § 63.655(h)(1) § 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(B) § 63.655(h)(2)(i)(C) § 63.655(h)(2)(ii) [G]§ 63.655(h)(6)
T-2113	EU	R5112-0004	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(a)(1) § 115.112(a)(2) § 115.112(a)(2)(A) § 115.112(a)(2)(B) § 115.112(a)(2)(C) § 115.112(a)(2)(D) § 115.112(a)(2)(E) § 115.112(a)(2)(F) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)
T-2113	EU	60K-002	VOC	40 CFR Part 60, Subpart K	§ 60.112(a)(1)	Storage vessels holding petroleum liquids with a true vapor pressure of 78	§ 60.113(a) § 60.113(b) ** See Periodic	§ 60.113(a)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						mm Hg (1.5 psia) or greater but not greater than 570 mm Hg (11.1 psia) shall have a floating roof, a vapor recovery system, or their equivalents.	Monitoring Summary		
T-2113	EU	61FF-0006	Benzene	40 CFR Part 61, Subpart FF	§ 61.351(a) [G]§ 60.112b(a)(2) § 61.351(a)(2) § 61.351(b)	As an alternative to the standards for tanks specified in § 61.343, an owner or operator may elect to comply with one of the following §61.351(a)(1)-(3):	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6)	§ 60.115b [G]§ 60.115b(b)(3) § 61.356(k)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 61.357(e) § 61.357(f)
T-2113	EU	63CC-0254	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(6)	After compliance dates specified in paragraph (h) of this section, a Group 2 storage vessel that is subject to the control requirements of 40 CFR Part 60, Subpart K is required to comply only with the provisions of 40 CFR Part 60, Subpart K.	None	None	None
T-2113	EU	63CC-1254	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.119(a)(1) § 63.119(c)(1) § 63.119(c)(1)(i) § 63.119(c)(1)(ii) § 63.119(c)(1)(iii) [G]§ 63.119(c)(3) § 63.119(c)(4) § 63.120(b)(10)(i)	Each owner or operator of a Group 1 storage vessel subject to this subpart shall comply with the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.120(b)(1)(i) § 63.120(b)(1)(iii) § 63.120(b)(1)(iv) § 63.120(b)(10) § 63.120(b)(2)(i) § 63.120(b)(2)(ii) § 63.120(b)(2)(iii) § 63.120(b)(3) § 63.120(b)(4)	[G]§ 63.120(b)(7) § 63.120(b)(8) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1) § 63.655(i)(5)	§ 63.120(b)(10)(ii) § 63.120(b)(10)(iii) § 63.120(b)(9) § 63.642(f) § 63.655(f) [G]§ 63.655(f)(1)(i)(B) § 63.655(f)(6) § 63.655(g) [G]§ 63.655(g)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.120(b)(5)(i) § 63.120(b)(5)(ii) § 63.120(b)(6)(i) § 63.120(b)(6)(ii) [G]§ 63.120(b)(7) § 63.120(b)(8) [G]§ 63.646(f) § 63.646(g)		§ 63.646(b)(1) § 63.646(e)		§ 63.655(h) § 63.655(h)(1) § 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(B) § 63.655(h)(2)(i)(C) § 63.655(h)(2)(ii) [G]§ 63.655(h)(6)
T-2133	EU	R5112-0001	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(a)(1) § 115.112(a)(2) § 115.112(a)(2)(A) § 115.112(a)(2)(B) § 115.112(a)(2)(C) § 115.112(a)(2)(D) § 115.112(a)(2)(E) § 115.112(a)(2)(F) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)
T-2133	EU	60Kb-003	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)
T-2133	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) [G]§ 60.112b(a)(2) § 63.640(n)(8)(i) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 63.640(n)(8)(vi)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							[G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) [G]§ 63.120(b)(7) § 63.640(n)(8)(ii)		
T-2133	EU	63CC-0013	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) [G]§ 60.112b(a)(2) § 63.640(n)(8)(i) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) [G]§ 63.120(b)(7) § 63.640(n)(8)(ii)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 63.640(n)(8)(vi)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)
T-2162	EU	R5112-0001	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(a)(1) § 115.112(a)(2) § 115.112(a)(2)(A) § 115.112(a)(2)(B) § 115.112(a)(2)(C) § 115.112(a)(2)(D) § 115.112(a)(2)(E) § 115.114(a)(1)(A)	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(7)	§ 115.114(a)(1)(B) § 115.118(a)(3)
T-2162	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.119(a)(1) [G]§ 63.119(b)(1) § 63.119(b)(2)	Each owner or operator of a Group 1 storage vessel subject to this subpart shall comply with	§ 63.120(a)(2)(i) § 63.120(a)(2)(ii) § 63.646(b)(1) § 63.646(e)	§ 63.120(a)(4) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1)	§ 63.120(a)(5) § 63.120(a)(6) § 63.642(f) § 63.655(f)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.119(b)(3)(ii) § 63.119(b)(4) § 63.120(a)(4) § 63.120(a)(7) [G]§ 63.646(f) § 63.646(g)	the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).		[G]§ 63.655(i)(1) § 63.655(i)(5)	[G]§ 63.655(f)(1)(i)(B) § 63.655(f)(6) § 63.655(g) § 63.655(g)(2) [G]§ 63.655(g)(2)(i) [G]§ 63.655(g)(2)(ii) § 63.655(h) § 63.655(h)(1) § 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(B) § 63.655(h)(2)(i)(C) [G]§ 63.655(h)(6)
T-2186	EU	R5112-0010A	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(a)(1) § 115.112(a)(2) § 115.112(a)(2)(A) § 115.112(a)(2)(B) § 115.112(a)(2)(C) § 115.112(a)(2)(D) § 115.112(a)(2)(E) § 115.112(a)(2)(F) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)
T-2186	EU	60Kb-004	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 60.116b(e)(1) § 60.116b(e)(2)(i)		
T-2186	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) [G]§ 60.112b(a)(2) § 63.640(n)(8)(i) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) [G]§ 63.120(b)(7) § 63.640(n)(8)(ii)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 63.640(n)(8)(vi)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)
T-2186	EU	63CC-0013	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) [G]§ 60.112b(a)(2) § 63.640(n)(8)(i) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) [G]§ 63.120(b)(7) § 63.640(n)(8)(ii)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 63.640(n)(8)(vi)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T-2401	EU	R5112-0001	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(a)(1) § 115.112(a)(2) § 115.112(a)(2)(A) § 115.112(a)(2)(B) § 115.112(a)(2)(C) § 115.112(a)(2)(D) § 115.112(a)(2)(E) § 115.114(a)(1)(A)	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(7)	§ 115.114(a)(1)(B) § 115.118(a)(3)
T-2401	EU	61FF-0005	Benzene	40 CFR Part 61, Subpart FF	§ 61.351(a) § 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii) § 61.351(a)(1) § 61.351(b)	As an alternative to the standards for tanks specified in § 61.343, an owner or operator may elect to comply with one of the following §61.351(a)(1)-(3):	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5)	§ 60.115b § 60.115b(a)(2) § 61.356(k)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3) § 61.357(e) § 61.357(f)
T-2401	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
T-2900	EU	R5112-0001	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(a)(1) § 115.112(a)(2) § 115.112(a)(2)(A) § 115.112(a)(2)(B) § 115.112(a)(2)(C) § 115.112(a)(2)(D) § 115.112(a)(2)(E) § 115.114(a)(1)(A)	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(7)	§ 115.114(a)(1)(B) § 115.118(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T-2900	EU	60Kb-0177	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)
T-2900	EU	63CC-0082	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) § 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(B) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii) § 63.640(n)(8)(ii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	§ 60.113b(a)(1) [G]§ 60.113b(a)(3) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) [G]§ 60.116b(e)(3) § 63.640(n)(8)(ii)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(4)
T-5	EU	R5112-0004	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(a)(1) § 115.112(a)(2) § 115.112(a)(2)(A) § 115.112(a)(2)(B) § 115.112(a)(2)(C) § 115.112(a)(2)(D) § 115.112(a)(2)(E) § 115.112(a)(2)(F) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)
T-5	EU	60Kb-001	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						specifications of §60.112b(a)(2)(i)-(iii).	§ 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)		§ 60.115b(b)(4)
T-5	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) [G]§ 60.112b(a)(2) § 63.640(n)(8)(i) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) [G]§ 63.120(b)(7) § 63.640(n)(8)(ii)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 63.640(n)(8)(vi)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)
T-5	EU	63CC-0013	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) [G]§ 60.112b(a)(2) § 63.640(n)(8)(i) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 63.640(n)(8)(vi)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) [G]§ 63.120(b)(7) § 63.640(n)(8)(ii)		
T-5002	EU	R5112-0006	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-5002	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
T-5003	EU	R5112-0007	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-5003	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						part of the affected source.			§ 63.655(h)(6) § 63.655(h)(6)(ii)
T-8010	EU	R5112-3	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-8010	EU	61FF-1	Benzene	40 CFR Part 61, Subpart FF	§ 61.343(a)(1) § 61.343(a)(1)(i)(A) § 61.343(a)(1)(i)(B) § 61.343(c) § 61.343(d) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	The owner or operator shall install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the tank to a control device.	§ 61.343(a)(1)(i)(A) § 61.343(c) § 61.349(a)(1)(i) § 61.349(e) § 61.349(f) § 61.354(d) [G]§ 61.355(h) § 61.355(i)(1) § 61.355(i)(2) § 61.355(i)(3)(i) § 61.355(i)(3)(ii) § 61.355(i)(3)(ii)(A) § 61.355(i)(3)(ii)(B) § 61.355(i)(3)(ii)(C) § 61.355(i)(3)(iii) § 61.355(i)(3)(iv) § 61.355(i)(4)	§ 61.355(i)(1) § 61.355(i)(3)(ii)(A) § 61.356(d) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2)(i)(G) [G]§ 61.356(f)(3) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3)	None
T-8010	EU	63CC-3	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC
T-82	EU	R5112-	VOC	30 TAC Chapter	§ 115.112(a)(1)	Tanks shall not store	§ 115.114(a)(2)	§ 115.118(a)(3)	§ 115.114(a)(2)(B)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		0004		115, Storage of VOCs	§ 115.112(a)(2) § 115.112(a)(2)(A) § 115.112(a)(2)(B) § 115.112(a)(2)(C) § 115.112(a)(2)(D) § 115.112(a)(2)(E) § 115.112(a)(2)(F) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	§ 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(5) § 115.118(a)(7)	§ 115.114(a)(4)(B) § 115.118(a)(3)
T-82	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
T-82	EU	63CC-0013	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.119(a)(1) § 63.119(c)(1) § 63.119(c)(1)(i) § 63.119(c)(1)(ii) § 63.119(c)(1)(iii) [G]§ 63.119(c)(3) § 63.119(c)(4) § 63.120(b)(10)(i) § 63.120(b)(5)(i) § 63.120(b)(5)(ii) § 63.120(b)(6)(i) § 63.120(b)(6)(ii) [G]§ 63.120(b)(7) § 63.120(b)(8) [G]§ 63.646(f) § 63.646(g)	Each owner or operator of a Group 1 storage vessel subject to this subpart shall comply with the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.120(b)(1)(i) § 63.120(b)(1)(iii) § 63.120(b)(1)(iv) § 63.120(b)(10) § 63.120(b)(2)(i) § 63.120(b)(2)(ii) § 63.120(b)(2)(iii) § 63.120(b)(3) § 63.120(b)(4) § 63.646(b)(1) § 63.646(e)	[G]§ 63.120(b)(7) § 63.120(b)(8) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1) § 63.655(i)(5)	§ 63.120(b)(10)(ii) § 63.120(b)(10)(iii) § 63.120(b)(9) § 63.642(f) § 63.655(f) [G]§ 63.655(f)(1)(i)(B) § 63.655(f)(6) § 63.655(g) [G]§ 63.655(g)(3) § 63.655(h) § 63.655(h)(1) § 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(B) § 63.655(h)(2)(i)(C) § 63.655(h)(2)(ii) [G]§ 63.655(h)(6)
TRACHWPUMP	EU	63ZZZZ-002	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(c)	Stationary RICE subject to Regulations under 40 CFR Part 60. An affected source that meets any of	None	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						the criteria in paragraphs (c)(1) through (7) of this section must meet the requirements of this part by meeting the requirements of 40 CFR part 60 subpart IIII, for compression ignition engines or 40 CFR part 60 subpart JJJJ, for spark ignition engines as applicable. No further requirements apply for such engines under this part.			
VACUUM	EU	R5131-2000	VOC	30 TAC Chapter 115, Unit Turn & Vac System-Pet Ref	§ 115.311(a)(1) § 115.312(a)(2) § 115.312(a)(2)(B)	No emission of VOC from steam ejector or mechanical vacuum pump in a petroleum refinery unless vent stream is burned in accordance with §115.312(a) of this title.	[G]§ 115.315(a) ** See Periodic Monitoring Summary	§ 115.316(a)(3) § 115.316(a)(4)	None

Additional Monitoring Requirements

Compliance Assurance Monitoring Summary **344**

Periodic Monitoring Summary **349**

CAM Summary

Unit/Group/Process Information	
ID No.: RTO	
Control Device ID No.: RTO	Control Device Type: Vapor Combustor
Applicable Regulatory Requirement	
Name: 40 CFR Part 61, Subpart FF	SOP Index No.: 61FF-002
Pollutant: Benzene	Main Standard: § 61.349(a)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: four times per hour	
Averaging Period: one hour	
Deviation Limit: Minimum Temperature = 1400 degrees Fahrenheit	
CAM Text: The monitoring device should be installed in the combustion chamber or immediately downstream of the combustion chamber. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following: ± 0.75% of the temperature being measured expressed in degrees Celsius; or ± 2.5 degrees Celsius.	

CAM Summary

Unit/Group/Process Information	
ID No.: SRU-543	
Control Device ID No.: E-01-SCOT	Control Device Type: Sulfur Recovery Unit With Incinerator
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 112, Sulfur Compounds	SOP Index No.: R2007-0003
Pollutant: SO_2	Main Standard: § 112.7(a)
Monitoring Information	
Indicator: Sulfur Dioxide Concentration	
Minimum Frequency: four times per hour	
Averaging Period: one hour	
Deviation Limit: 1650 Lbs SO2/hr	
CAM Text: Use a continuous emission monitoring system (CEMS) to measure and record sulfur dioxide emissions in the exhaust stream of the control device. The CEMS shall be operated in accordance with the monitoring requirements of 40 CFR § 60.13 and the performance specifications of 40 CFR Part 60, Appendix B. In addition, monitor oxygen or carbon dioxide with a CEMS operated in accordance with above CEMS procedures.	

CAM Summary

Unit/Group/Process Information	
ID No.: SRU-544	
Control Device ID No.: E-02-SCOT	Control Device Type: Sulfur Recovery Unit With Incinerator
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 112, Sulfur Compounds	SOP Index No.: R2007-0003
Pollutant: SO_2	Main Standard: § 112.7(a)
Monitoring Information	
Indicator: Sulfur Dioxide Concentration	
Minimum Frequency: four times per hour	
Averaging Period: one hour	
Deviation Limit: 1596 Lbs SO2/hr	
CAM Text: Use a continuous emission monitoring system (CEMS) to measure and record sulfur dioxide emissions in the exhaust stream of the control device. The CEMS shall be operated in accordance with the monitoring requirements of 40 CFR § 60.13 and the performance specifications of 40 CFR Part 60, Appendix B. In addition, monitor oxygen or carbon dioxide with a CEMS operated in accordance with above CEMS procedures.	

CAM Summary

Unit/Group/Process Information	
ID No.: SRU-545	
Control Device ID No.: E-03-SCOT	Control Device Type: Sulfur Recovery Unit With Incinerator
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 112, Sulfur Compounds	SOP Index No.: R2007-0003
Pollutant: SO_2	Main Standard: § 112.7(a)
Monitoring Information	
Indicator: Sulfur Dioxide Concentration	
Minimum Frequency: four times per hour	
Averaging Period: one hour	
Deviation Limit: 1693 LBS SO2/hr	
CAM Text: Use a continuous emission monitoring system (CEMS) to measure and record sulfur dioxide emissions in the exhaust stream of the control device. The CEMS shall be operated in accordance with the monitoring requirements of 40 CFR § 60.13 and the performance specifications of 40 CFR Part 60, Appendix B. In addition, monitor oxygen or carbon dioxide with a CEMS operated in accordance with above CEMS procedures.	

CAM Summary

Unit/Group/Process Information	
ID No.: SRU-546	
Control Device ID No.: E-04-SCOT	Control Device Type: Sulfur Recovery Unit With Incinerator
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 112, Sulfur Compounds	SOP Index No.: R2007-0003
Pollutant: SO_2	Main Standard: § 112.7(a)
Monitoring Information	
Indicator: Sulfur Dioxide Concentration	
Minimum Frequency: four times per hour	
Averaging Period: one hour	
Deviation Limit: 1539 lbs SO2/hr	
CAM Text: Use a continuous emission monitoring system (CEMS) to measure and record sulfur dioxide emissions in the exhaust stream of the control device. The CEMS shall be operated in accordance with the monitoring requirements of 40 CFR § 60.13 and the performance specifications of 40 CFR Part 60, Appendix B. In addition, monitor oxygen or carbon dioxide with a CEMS operated in accordance with above CEMS procedures.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: GRPKVOC	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart K	SOP Index No.: 60K-003
Pollutant: VOC	Main Standard: § 60.112(a)(1)
Monitoring Information	
Indicator: External Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: The roof is not floating on the surface of the VOC, liquid has accumulated on the external floating roof, the seals are detached, or any holes/tears in the seal fabric	
Periodic Monitoring Text: Visually inspect and record the inspection of the external floating roof to ensure: the roof is floating on the surface of the VOC and not on the leg supports, liquid has not accumulated on the external floating roof, the seals are not detached, and there are no holes or tears in the seal fabric. Any monitoring data in which the roof is not floating on the surface of the VOC, if liquid has accumulated on the external floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: GRPTK5491	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart K	SOP Index No.: 60K-001
Pollutant: VOC	Main Standard: § 60.112(a)(1)
Monitoring Information	
Indicator: External Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: The roof is not floating on the surface of the VOC, liquid has accumulated on the external floating roof, the seals are detached, or any holes/tears in the seal fabric	
Periodic Monitoring Text: Visually inspect and record the inspection of the external floating roof to ensure: the roof is floating on the surface of the VOC and not on the leg supports, liquid has not accumulated on the external floating roof, the seals are not detached, and there are no holes or tears in the seal fabric. Any monitoring data in which the roof is not floating on the surface of the VOC, if liquid has accumulated on the external floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: GRP-WASH1	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Degreasing Processes	SOP Index No.: R5412-0057
Pollutant: VOC	Main Standard: § 115.412(1)
Monitoring Information	
Indicator: Visual Inspection	
Minimum Frequency: Monthly	
Averaging Period: n/a	
Deviation Limit: Cover shall be kept closed whenever cleaner is not in use	
Periodic Monitoring Text: Inspect equipment and record data monthly to ensure compliance with any applicable requirements in § 115.412(1)(A)-(F). Any monitoring data which indicates that the cold cleaner is not in compliance with the applicable requirements of § 115.412(1)(A)-(F) shall be considered and reported as a deviation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: GRP-WASH2	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Degreasing Processes	SOP Index No.: R5412-0057
Pollutant: VOC	Main Standard: § 115.412(1)
Monitoring Information	
Indicator: Visual Inspection	
Minimum Frequency: Monthly	
Averaging Period: n/a	
Deviation Limit: Cover shall be kept closed whenever cleaner is not in use.	
Periodic Monitoring Text: Inspect equipment and record data monthly to ensure compliance with any applicable requirements in § 115.412(1)(A)-(F). Any monitoring data which indicates that the cold cleaner is not in compliance with the applicable requirements of § 115.412(1)(A)-(F) shall be considered and reported as a deviation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: T-106	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart K	SOP Index No.: 60K-001
Pollutant: VOC	Main Standard: § 60.112(a)(1)
Monitoring Information	
Indicator: External Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: The roof is not floating on the surface of the VOC, liquid has accumulated on the external floating roof, the seals are detached, or any holes/tears in the seal fabric	
Periodic Monitoring Text: Visually inspect and record the inspection of the external floating roof to ensure: the roof is floating on the surface of the VOC and not on the leg supports, liquid has not accumulated on the external floating roof, the seals are not detached, and there are no holes or tears in the seal fabric. Any monitoring data in which the roof is not floating on the surface of the VOC, if liquid has accumulated on the external floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: T-107	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart K	SOP Index No.: 60K-001
Pollutant: VOC	Main Standard: § 60.112(a)(1)
Monitoring Information	
Indicator: External Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: The roof is not floating on the surface of the VOC, liquid has accumulated on the external floating roof, the seals are detached, or any holes/tears in the seal fabric	
Periodic Monitoring Text: Visually inspect and record the inspection of the external floating roof to ensure: the roof is floating on the surface of the VOC and not on the leg supports, liquid has not accumulated on the external floating roof, the seals are not detached, and there are no holes or tears in the seal fabric. Any monitoring data in which the roof is not floating on the surface of the VOC, if liquid has accumulated on the external floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: T-2113	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart K	SOP Index No.: 60K-002
Pollutant: VOC	Main Standard: § 60.112(a)(1)
Monitoring Information	
Indicator: External Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: The roof is not floating on the surface of the VOC, liquid has accumulated on the external floating roof, the seals are detached, or any holes/tears in the seal fabric	
Periodic Monitoring Text: Visually inspect and record the inspection of the external floating roof to ensure: the roof is floating on the surface of the VOC and not on the leg supports, liquid has not accumulated on the external floating roof, the seals are not detached, and there are no holes or tears in the seal fabric. Any monitoring data in which the roof is not floating on the surface of the VOC, if liquid has accumulated on the external floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: VACUUM	
Control Device ID No.: FLARE-19	Control Device Type: Flare
Control Device ID No.: FLARE-23	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Unit Turn & Vac System-Pet Ref	SOP Index No.: R5131-2000
Pollutant: VOC	Main Standard: § 115.311(a)(1)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Once per hour	
Averaging Period: n/a	
Deviation Limit: No pilot flame	
Periodic Monitoring Text: Measure and record the presence of the pilot flame or maintain records of alarm events and duration of alarm events. The presence of a flare pilot flame shall be monitored using a thermocouple or any other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. The monitoring instrumentation shall be maintained, calibrated and operated in accordance with manufacturer's specifications or other written procedures. Any monitoring data which indicates the lack of a pilot flame shall be considered and reported as a deviation.	

Permit Shield

Permit Shield **358**

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
AVU-146H1	N/A	30 TAC Chapter 112, Sulfur Compounds	Combustion unit burns gaseous fuels only.
AVU-146H2AB	N/A	30 TAC Chapter 112, Sulfur Compounds	Combustion unit burns gaseous fuels only.
BERTH-1A	N/A	30 TAC Chapter 115, Loading and Unloading of VOC	All loading and unloading of marine vessels in ozone nonattainment areas other than the Houston/Galveston area are exempt from this division.
BERTH-1A	N/A	40 CFR Part 61, Subpart BB	Unit does not load benzene.
BERTH-1B	N/A	30 TAC Chapter 115, Loading and Unloading of VOC	All loading and unloading of marine vessels in ozone nonattainment areas other than the Houston/Galveston area are exempt from this division.
BERTH-1B	N/A	40 CFR Part 61, Subpart BB	Unit does not load benzene.
BERTH-2A	N/A	30 TAC Chapter 115, Loading and Unloading of VOC	All loading and unloading of marine vessels in ozone nonattainment areas other than the Houston/Galveston area are exempt from this division.
BERTH-2A	N/A	40 CFR Part 61, Subpart BB	Unit does not load benzene.
BERTH-2B	N/A	30 TAC Chapter 115, Loading and Unloading of VOC	All loading and unloading of marine vessels in ozone nonattainment areas other than the Houston/Galveston area are exempt from this division.
BERTH-2B	N/A	40 CFR Part 61, Subpart BB	Unit does not load benzene.
BERTH-3A	N/A	30 TAC Chapter 115, Loading and Unloading of VOC	All loading and unloading of marine vessels in ozone nonattainment areas other than the Houston/Galveston area are exempt from this

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
			division.
BERTH-3A	N/A	40 CFR Part 61, Subpart BB	Unit does not load benzene.
BERTH-3B	N/A	30 TAC Chapter 115, Loading and Unloading of VOC	All loading and unloading of marine vessels in ozone nonattainment areas other than the Houston/Galveston area are exempt from this division.
BERTH-3B	N/A	40 CFR Part 61, Subpart BB	Unit does not load benzene.
BERTH-5	N/A	30 TAC Chapter 115, Loading and Unloading of VOC	All loading and unloading of marine vessels in ozone nonattainment areas other than the Houston/Galveston area are exempt from this division.
BERTH-5	N/A	40 CFR Part 61, Subpart BB	Unit does not load benzene.
BERTH-5	N/A	40 CFR Part 63, Subpart Y	Berth does not load a commodity with vapor pressure greater than 10 kPa (1.5 psia) at standard conditions.
BERTH-6	N/A	30 TAC Chapter 115, Loading and Unloading of VOC	All loading and unloading of marine vessels in ozone nonattainment areas other than the Houston/Galveston area are exempt from this division.
BERTH-6	N/A	40 CFR Part 61, Subpart BB	Unit does not load benzene.
BERTH-6	N/A	40 CFR Part 63, Subpart Y	Berth does not load a commodity with vapor pressure greater than 10 kPa (1.5 psia) at standard conditions.
BH15-41	N/A	30 TAC Chapter 112, Sulfur Compounds	Combustion unit burns gaseous fuels only.
BH15-41	N/A	40 CFR Part 60, Subpart D	All power plant boilers were built prior to

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
			August 17, 1971, and there has been no modification or reconstruction since completion of the initial construction.
BH15-41	N/A	40 CFR Part 60, Subpart Da	Equipment is not an electric utility steam generating unit.
BH15-41	N/A	40 CFR Part 60, Subpart Db	All power plant boilers were built prior to June 19, 1984, and there has been no modification or reconstruction since completion of the initial construction.
BH15-42	N/A	30 TAC Chapter 112, Sulfur Compounds	Combustion unit burns gaseous fuels only.
BH15-42	N/A	40 CFR Part 60, Subpart D	All power plant boilers were built prior to August 17, 1971, and there has been no modification or reconstruction since completion of the initial construction.
BH15-42	N/A	40 CFR Part 60, Subpart Da	Equipment is not an electric utility steam generating unit.
BH15-42	N/A	40 CFR Part 60, Subpart Db	All power plant boilers were built prior to June 19, 1984, and there has been no modification or reconstruction since completion of the initial construction.
BH15-43	N/A	30 TAC Chapter 112, Sulfur Compounds	Combustion unit burns gaseous fuels only.
BH15-43	N/A	40 CFR Part 60, Subpart D	All power plant boilers were built prior to August 17, 1971, and there has been no modification or reconstruction since completion of the initial construction.
BH15-43	N/A	40 CFR Part 60, Subpart Da	Equipment is not an electric utility steam

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
			generating unit.
BH15-43	N/A	40 CFR Part 60, Subpart Db	All power plant boilers were built prior to June 19, 1984, and there has been no modification or reconstruction since completion of the initial construction.
CRU-1344H1	N/A	30 TAC Chapter 112, Sulfur Compounds	Combustion unit burns gaseous fuels only.
CRU-1344H2	N/A	30 TAC Chapter 112, Sulfur Compounds	Combustion unit burns gaseous fuels only.
CRU-1344H3	N/A	30 TAC Chapter 112, Sulfur Compounds	Combustion unit burns gaseous fuels only.
CSV843	N/A	40 CFR Part 63, Subpart CC	Emissions associated with delayed coking unit decoking operations are excluded from the definition of miscellaneous process vent.
DCU-843C1	N/A	30 TAC Chapter 112, Sulfur Compounds	Combustion unit burns gaseous fuels only.
DCU-843C2	N/A	30 TAC Chapter 112, Sulfur Compounds	Combustion unit burns gaseous fuels only.
DCU-843H1	N/A	30 TAC Chapter 112, Sulfur Compounds	Combustion unit burns gaseous fuels only.
DCU-843H2	N/A	30 TAC Chapter 112, Sulfur Compounds	Combustion unit burns gaseous fuels only.
DCU-843H3	N/A	30 TAC Chapter 112, Sulfur Compounds	Combustion unit burns gaseous fuels only.
E-01-147	N/A	30 TAC Chapter 117, Subchapter B	Unit placed into service after the final compliance date as specified in §117.9000.
E-01-245	N/A	30 TAC Chapter 112, Sulfur Compounds	Combustion units use gaseous fuel only.
E-01-245	N/A	30 TAC Chapter 117, Subchapter B	Maximum Rated Capacity is less than 40 MMBTU/HR.
E-01-246	N/A	30 TAC Chapter 117, Subchapter B	Maximum Rated Capacity is less than 40 MMBTU/HR.

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
E-01-SCOT	N/A	30 TAC Chapter 117, Subchapter B	Incinerators are exempt from the provisions of Chapter 117, Subchapter B, Division 1.
E-01-SCOT	N/A	40 CFR Part 60, Subpart J	Combusts only purchased natural gas.
E-02-SCOT	N/A	30 TAC Chapter 117, Subchapter B	NOX RACT Oxidizers are exempt from the provisions of NOx RACT.
E-02-SCOT	N/A	40 CFR Part 60, Subpart J	Combusts only purchased natural gas.
E-03-SCOT	N/A	30 TAC Chapter 112, Sulfur Compounds	Combustion unit burns gaseous fuels only.
E-04-SCOT	N/A	30 TAC Chapter 117, Subchapter B	Incinerators are exempt from the provisions of Chapter 117, Subchapter B, Division 1.
F-432CT	N/A	40 CFR Part 63, Subpart Q	Cooling tower does not operate with chromium-based water treatment chemicals.
F-446CT	N/A	40 CFR Part 63, Subpart Q	Cooling tower does not operate with chromium-based water treatment chemicals.
FLARE-05	N/A	40 CFR Part 60, Subpart J	Unit is a fuel gas combustion device which is also a flare that has not commenced construction or reconstruction/modification after 06/11/1973 and on or before 06/24/2008.
GFU-241-H1	N/A	40 CFR Part 63, Subpart DDDDD	Existing sources are only required to comply with the initial notifications specified in 63.9(b)
GFU-242-H	N/A	40 CFR Part 63, Subpart DDDDD	Existing sources are only required to comply with the initial notifications specified in 63.9(b)
GFU-243-H	N/A	30 TAC Chapter 112, Sulfur Compounds	Combustion unit burns gaseous fuels only.
GFU-244-HA	N/A	30 TAC Chapter 112, Sulfur Compounds	Combustion unit burns gaseous fuels only.
GRP-C8456	T-133, T-889	40 CFR Part 60, Subpart Ka	Storage vessels are storing a petroleum liquid

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
			with a Reid vapor pressure of less than 1.0 psia, and the maximum true vapor pressure does not exceed 1.0 psia.
GRPCLAR	F-T-L6002	40 CFR Part 60, Subpart Kb	Tanks have a capacity less than 75 cubic meters.
GRPCOOL	CT-100, CT-147, CT-244, CT-246, CT-400, F-101CT, F-136ACT, F-136BCT, F-233PS, F-314CT, F-316CT, F-360PS, F-364CT, F-366CT	40 CFR Part 63, Subpart Q	Unit is not operated with chromium-based water treatment chemicals.
HCU-942H1/2	N/A	30 TAC Chapter 112, Sulfur Compounds	Combustion unit burns gaseous fuels only.
HCU-942H3	N/A	30 TAC Chapter 112, Sulfur Compounds	Combustion unit burns gaseous fuels only.
HCU-943-A/B	N/A	30 TAC Chapter 112, Sulfur Compounds	Combustion units use gaseous fuels only.
HCU-943-A/B	N/A	30 TAC Chapter 117, Subchapter B	Source constructed after November 15, 1992
HCU-943-C	N/A	30 TAC Chapter 112, Sulfur Compounds	Combustion units use gaseous fuels only.
HCU-943-C	N/A	30 TAC Chapter 117, Subchapter B	Source constructed after November 15, 1992
HFAU-443-H	N/A	30 TAC Chapter 112, Sulfur Compounds	Combustion unit burns gaseous fuels only.
PRO-WWTU	N/A	30 TAC Chapter 115, Industrial Wastewater	Petroleum refineries in the Beaumont/Port Arthur area are exempt from the requirements of this division.
PRO-WWTU	N/A	40 CFR Part 63, Subpart DD	Plant does not receive off-site material
PRO-WWTU	N/A	40 CFR Part 63, Subpart F	The facility does not manufacture as a primary product any of the chemicals listed in paragraphs (b)(1)(i) or (b)(1)(ii) of this section.

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
RTO	N/A	40 CFR Part 60, Subpart J	Combusts purchased natural gas
T-5002	N/A	40 CFR Part 60, Subpart Kb	Storage vessel capacity is greater than or equal to 151 cubic meters and stores a liquid with a maximum true vapor pressure less than 3.5 kPa.
T-5003	N/A	40 CFR Part 60, Subpart Kb	Storage vessel capacity is less than 75 cubic meters.
T-8010	N/A	40 CFR Part 60, Subpart Kb	This unit is not a storage vessel; it is a process tank. In addition, storage capacity is less than 75 cubic meters.

New Source Review Authorization References

New Source Review Authorization References 366

New Source Review Authorization References by Emission Unit 367

New Source Review Authorization References

The New Source Review authorizations listed in the table below are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Prevention of Significant Deterioration (PSD) Permits	
PSD Permit No.: GHGPSDTX167	Issuance Date: 11/16/2018
PSD Permit No.: PSDTX49M1	Issuance Date: 11/16/2018
Nonattainment (NA) Permits	
NA Permit No.: N65	Issuance Date: 11/16/2018
Title 30 TAC Chapter 116 Permits, Special Permits, and Other Authorizations (Other Than Permits By Rule, PSD Permits, or NA Permits) for the Application Area.	
Authorization No.: 6825A	Issuance Date: 11/16/2018
Authorization No.: 80812	Issuance Date: 12/07/2018
Authorization No.: 86757	Issuance Date: 12/07/2018
Authorization No.: 91911	Issuance Date: 03/22/2010
Permits By Rule (30 TAC Chapter 106) for the Application Area	
Number: 106.183	Version No./Date: 09/04/2000
Number: 106.261	Version No./Date: 11/01/2003
Number: 106.262	Version No./Date: 11/01/2003
Number: 106.263	Version No./Date: 11/01/2001
Number: 106.371	Version No./Date: 09/04/2000
Number: 106.412	Version No./Date: 09/04/2000
Number: 106.472	Version No./Date: 09/04/2000
Number: 106.473	Version No./Date: 09/04/2000
Number: 106.478	Version No./Date: 09/04/2000
Number: 106.511	Version No./Date: 09/04/2000
Number: 106.512	Version No./Date: 06/13/2001
Number: 5	Version No./Date: 08/30/1988
Number: 61	Version No./Date: 07/20/1992
Number: 68	Version No./Date: 07/20/1992
Number: 86	Version No./Date: 11/25/1985
Number: 88	Version No./Date: 07/20/1992
Number: 111	Version No./Date: 09/23/1982
Number: 124	Version No./Date: 05/12/1981
Number: 124	Version No./Date: 09/23/1982
Number: 125	Version No./Date: 09/23/1982

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
1334-RVENT	REGENT VENT	6825A, N65, PSDTX49M1, GHGPSDTX167
16BHSW	STORMWATER REMOVAL	106.511/09/04/2000
443-VENT-10	443 STATIONARY PROCESS VENT 10	6825A, N65, PSDTX49M1, GHGPSDTX167
443-VENT-1	443 STATIONARY PROCESS VENT 1	6825A, N65, PSDTX49M1, GHGPSDTX167
443-VENT-2	443 STATIONARY PROCESS VENT 2	6825A, N65, PSDTX49M1, GHGPSDTX167
443-VENT-3	443 STATIONARY PROCESS VENT 3	6825A, N65, PSDTX49M1, GHGPSDTX167
443-VENT-4	443 STATIONARY PROCESS VENT 4	6825A, N65, PSDTX49M1, GHGPSDTX167
443-VENT-5	443 STATIONARY PROCESS VENT 5	6825A, N65, PSDTX49M1, GHGPSDTX167
443-VENT-6	443 STATIONARY PROCESS VENT 6	6825A, N65, PSDTX49M1, GHGPSDTX167
443-VENT-7	443 STATIONARY PROCESS VENT 7	6825A, N65, PSDTX49M1, GHGPSDTX167
443-VENT-8	443 STATIONARY PROCESS VENT 8	6825A, N65, PSDTX49M1, GHGPSDTX167
443-VENT-9	443 STATIONARY PROCESS VENT 9	6825A, N65, PSDTX49M1, GHGPSDTX167
843-VENT	MERICHEM OFFGAS VENT TO KO DRUM H-030	6825A, N65, PSDTX49M1, GHGPSDTX167
ADMNGEN	ADMINISTRATION BLDG GENERATOR	106.511/09/04/2000
AUCT	ALYLATION UNIT/COOLING TOWER AREA	6825A, N65, PSDTX49M1, GHGPSDTX167
AVU-146H1	AUV 146 HEATER H-101	6825A, N65, PSDTX49M1, GHGPSDTX167
AVU-146H1	AVU 146 HEATER H-101	6825A, N65, PSDTX49M1, GHGPSDTX167
AVU-146H2AB	AVU 146 HEATER H-102A/B	6825A, N65, PSDTX49M1, GHGPSDTX167
BERTH-1A	MARINE LOADING EMISSIONS - BERTH 1	6825A, N65, PSDTX49M1, GHGPSDTX167
BERTH-1B	MARINE LOADING EMISSIONS - BERTH 1	6825A, N65, PSDTX49M1, GHGPSDTX167
BERTH-2A	MARINE LOADING EMISSIONS - BERTH 2	6825A, N65, PSDTX49M1, GHGPSDTX167

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
BERTH-2B	MARINE LOADING EMISSIONS - BERTH 2	6825A, N65, PSDTX49M1, GHGPSDTX167
BERTH-3A	MARINE LOADING EMISSIONS - BERTH 3	6825A, N65, PSDTX49M1, GHGPSDTX167
BERTH-3B	MARINE LOADING EMISSIONS - BERTH 3	6825A, N65, PSDTX49M1, GHGPSDTX167
BERTH-5	MARINE LOADING EMISSIONS - BERTH 5	6825A, N65, PSDTX49M1, GHGPSDTX167
BERTH-6	MARINE LOADING EMISSIONS - BERTH 6	6825A, N65, PSDTX49M1, GHGPSDTX167
BH15-41	BH15 BOILER 15-41	6825A, 91911, N65, PSDTX49M1, GHGPSDTX167
BH15-42	BH15 BOILER 15-42	6825A, 91911, N65, PSDTX49M1, GHGPSDTX167
BH15-43	BH15 BOILER 15-43	6825A, 91911, N65, PSDTX49M1, GHGPSDTX167
CARBON-1	NESHAPS FF SUMP CONTROL 1	6825A, N65, PSDTX49M1, GHGPSDTX167
CARBON-2	NESHAPS FF SUMP CONTROL 2	6825A, N65, PSDTX49M1, GHGPSDTX167
CRU-1344H1	CRU-1344 HEATER H-1	6825A, N65, PSDTX49M1, GHGPSDTX167
CRU-1344H2	CRU-1344 HEATER H-31 AND H-33	6825A, N65, PSDTX49M1, GHGPSDTX167
CRU-1344H3	CRU-1344 HEATERS H-2, H-3, H-32	6825A, N65, PSDTX49M1, GHGPSDTX167
CSV843	DCU 843 COKER VENT	6825A, N65, PSDTX49M1, GHGPSDTX167
CT-100	COOLING TOWER 100 AT GFU 241/242	6825A, N65, PSDTX49M1, GHGPSDTX167
CT-147	AVU-147 COOLING TOWER	6825A, N65, PSDTX49M1, GHGPSDTX167
CT-244	HFAU 443 COOLING TOWER	6825A, N65, PSDTX49M1, GHGPSDTX167
CT-246	DHU-246 COOLING TOWER	6825A, N65, PSDTX49M1, GHGPSDTX167
CT-400	COOLING TOWER FOR UNIT GHU-245	6825A, N65, PSDTX49M1, GHGPSDTX167

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
DCU-843C1	COKER CHARGE TANK HEATER 1	6825A, N65, PSDTX49M1, GHGPSDTX167
DCU-843C2	COKER CHARGE TANK HEATER 2	6825A, N65, PSDTX49M1, GHGPSDTX167
DCU-843H1	HEATER 843-H1 / DCU-843 H-101 CHARGE HEATER	6825A, N65, PSDTX49M1, GHGPSDTX167
DCU-843H2	HEATER 843-H2	6825A, N65, PSDTX49M1, GHGPSDTX167
DCU-843H3	HEATER 843-H3 / DCU-843 H-103 CHARGE HEATER	6825A, N65, PSDTX49M1, GHGPSDTX167
E-01-147	ATMOSPHERIC HEATER	6825A, N65, PSDTX49M1, GHGPSDTX167
E-01-245	REACTOR HEATER	6825A, N65, PSDTX49M1, GHGPSDTX167
E-01-246	REACTOR FEED FURNACE	6825A, N65, PSDTX49M1, GHGPSDTX167
E-01-SCOT	SCOT I TAIL GAS F-103 INCINERATOR	6825A, N65, PSDTX49M1, GHGPSDTX167
E-01-SUMP	AMINE SUMP FUGITIVES AT SRU 544	6825A, N65, PSDTX49M1, GHGPSDTX167
E-02-147	VACUUM HEATER	6825A, N65, PSDTX49M1, GHGPSDTX167
E-02-SCOT	SRU 544 SCOT TAIL GAS COMBUSTION UNIT	6825A, N65, PSDTX49M1, GHGPSDTX167
E-03-SCOT	SRU 545 INCINERATOR H-9003	6825A, N65, PSDTX49M1, GHGPSDTX167
E-04-SCOT	SRU 546 INCINERATOR	6825A, N65, PSDTX49M1, GHGPSDTX167
ENG-15PS	STORMWATER BACKUP PUMP	5/08/30/1988
ENG-443 NORTH	EMERGENCY HF RELEASE WATER SUPPLY	106.511/09/04/2000
ENG-443 SOUTH	EMERGENCY HF RELEASE WATER SUPPLY	106.511/09/04/2000
ENG-70AC2	PLANT AIR BACKUP	106.511/09/04/2000
ENG-70AC3	PLANT AIR BACKUP	106.511/09/04/2000
ENG-843NORTH	COKER MAZE CLEANING - NORTH	106.511/09/04/2000
ENG-843SOUTH	COKER MAZE CLEANING - SOUTH	106.511/09/04/2000

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
F-101CT	GFU 243 COOLING TOWER	6825A, N65, PSDTX49M1, GHGPSDTX167
F-1241	FCCU 1241 FUGITIVES	6825A, N65, PSDTX49M1, GHGPSDTX167
F-1242	SGRU 1242 FUGITIVES	6825A, N65, PSDTX49M1, GHGPSDTX167
F-1344	CRU 1344 FUGITIVES	6825A, N65, PSDTX49M1, GHGPSDTX167
F-136ACT	FCCU 1241 COOLING TOWER	6825A, N65, PSDTX49M1, GHGPSDTX167
F-136BCT	SGRU 1242 COOLING TOWER	6825A, N65, PSDTX49M1, GHGPSDTX167
F-146	AVU 146 FUGITIVES	6825A, N65, PSDTX49M1, GHGPSDTX167
F-147	AVU-147 FUGITIVES	6825A, N65, PSDTX49M1, GHGPSDTX167
F-15BH	BH 15 FUGITIVES	6825A, 91911, N65, PSDTX49M1, GHGPSDTX167
F-16BH	BH 16 FUGITIVES	6825A, N65, PSDTX49M1, GHGPSDTX167
F-1747	RSU-1747 FUGITIVES	6825A, N65, PSDTX49M1, GHGPSDTX167
F-18BH	BH 18 FUGITIVES	6825A, N65, PSDTX49M1, GHGPSDTX167
F-233PS	GFU 244 COOLING TOWER	6825A, N65, PSDTX49M1, GHGPSDTX167
F-241	GFU 241 FUGITIVES	6825A, N65, PSDTX49M1, GHGPSDTX167
F-242	GFU 242 FUGITIVES	6825A, N65, PSDTX49M1, GHGPSDTX167
F-243	GFU 243 FUGITIVES	6825A, N65, PSDTX49M1, GHGPSDTX167
F-243-MOD	GFU-243 REVAMP PROJECT	6825A, N65, PSDTX49M1, GHGPSDTX167
F-244	GFU 244 FUGITIVES	6825A, N65, PSDTX49M1, GHGPSDTX167
F-245	FUGITIVES GASOLINE HYDROTREATING	6825A, N65, PSDTX49M1, GHGPSDTX167
F-246	DHU-246 COOLING TOWER	6825A, N65, PSDTX49M1, GHGPSDTX167

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
F-314CT	BH 16 COOLING TOWER	6825A, N65, PSDTX49M1, GHGPSDTX167
F-316CT	BH 15 COOLING TOWER	6825A, N65, PSDTX49M1, GHGPSDTX167
F-360PS	CRU 1344 COOLING TOWER	6825A, N65, PSDTX49M1, GHGPSDTX167
F-364CT	SRU COMPLEX COOLING TOWER	6825A, N65, PSDTX49M1, GHGPSDTX167
F-366CT	AVU 146 COOLING TOWER	6825A, N65, PSDTX49M1, GHGPSDTX167
F-432CT	COOLING TOWER-432CT	6825A, N65, PSDTX49M1, GHGPSDTX167
F-441	SAU 441 ALKYLATION UNIT AREA FUGITIVES	6825A, N65, PSDTX49M1, GHGPSDTX167
F-443	ALKY DEBUTANIZER	6825A, N65, PSDTX49M1, GHGPSDTX167
F-446CT	COOLING TOWER 446	6825A, N65, PSDTX49M1, GHGPSDTX167
F-541/3	SRU 543 FUGITIVES	6825A, N65, PSDTX49M1, GHGPSDTX167
F-544	SRU 544 FUGITIVES	6825A, N65, PSDTX49M1, GHGPSDTX167
F-545	SRU 545 FUGITIVES	6825A, N65, PSDTX49M1, GHGPSDTX167
F-546	SRU-546 FUGITIVES	6825A, N65, PSDTX49M1, GHGPSDTX167
F-6341	LHSU-6341 FUGITIVES	6825A, N65, PSDTX49M1, GHGPSDTX167
F-7042	FGRU-7042 FUGITIVES	6825A, N65, PSDTX49M1, GHGPSDTX167
F-7043	FGRU-7043 FUGITIVES	6825A, N65, PSDTX49M1, GHGPSDTX167
F-7044	FGRU-7044 FUGITIVES	6825A, N65, PSDTX49M1, GHGPSDTX167
F-7542	MERCAPTAN REMOVAL UNIT 7542 FUGITIVES	6825A, N65, PSDTX49M1, GHGPSDTX167
F-7842	ATU-7842 FUGITIVES	6825A, N65, PSDTX49M1, GHGPSDTX167
F-7843	HCU-NH3 STORAGE AND PIPING	6825A, N65, PSDTX49M1, GHGPSDTX167
F-7846	AMINE TREATING UNIT 7846 FUGITIVES	6825A, N65, PSDTX49M1, GHGPSDTX167

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
F-7848	ATU 7848 FUGITIVES	6825A, N65, PSDTX49M1, GHGPSDTX167
F-7945	SGRU-7945 FUGITIVES	6825A, N65, PSDTX49M1, GHGPSDTX167
F-843	DCU-843 FUGITIVES	6825A, N65, PSDTX49M1, GHGPSDTX167
F-8742	WWTU 8742 FUGITIVES	61/07/20/1992, 68/07/20/1992
F-8748	SWS-8748	6825A, N65, PSDTX49M1, GHGPSDTX167
F-8748-SWS	SOUR WATER STRIPPER 8748	6825A, N65, PSDTX49M1, GHGPSDTX167
F-942	HCU 942 FUGITIVES	6825A, N65, PSDTX49M1, GHGPSDTX167
F-943	HCU-943 FUGITIVES	6825A, N65, PSDTX49M1, GHGPSDTX167
F-BH-15	BOILER HOUSE FUGITIVES	6825A, N65, PSDTX49M1, GHGPSDTX167
F-BH-16	BOILER HOUSE FUGITIVES	6825A, N65, PSDTX49M1, GHGPSDTX167
F-BH-18	BOILER HOUSE FUGITIVES	6825A, N65, PSDTX49M1, GHGPSDTX167
FCC-1241H1	FCCU 1241 HEATER B-103A	6825A, N65, PSDTX49M1, GHGPSDTX167
FCC-1241H2	FCCU 1241 HEATER B-103B	6825A, N65, PSDTX49M1, GHGPSDTX167
FCCU-1241	FCCU 1241	6825A, N65, PSDTX49M1, GHGPSDTX167
F-DOCKS	DOCKS FUGITIVES	6825A, N65, PSDTX49M1, GHGPSDTX167
FF-1241-1	CLOSED VENT SYSTEM	6825A, N65, PSDTX49M1, GHGPSDTX167
FF-1241-2	CLOSED VENT SYSTEM	6825A, N65, PSDTX49M1, GHGPSDTX167
FF-1242	CLOSED VENT SYSTEM	6825A, N65, PSDTX49M1, GHGPSDTX167
FF-1344	CLOSED VENT SYSTEM	6825A, N65, PSDTX49M1, GHGPSDTX167
FF-146	CLOSED VENT SYSTEM	6825A, N65, PSDTX49M1, GHGPSDTX167
FF-147	PROCESS WASTEWATER SUMP CONTROL	6825A, N65, PSDTX49M1, GHGPSDTX167

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
FF-241	CLOSED VENT SYSTEM	6825A, N65, PSDTX49M1, GHGPSDTX167
FF-244	CLOSED VENT SYSTEM	6825A, N65, PSDTX49M1, GHGPSDTX167
FF-246	CLOSED VENT SYSTEM	6825A, N65, PSDTX49M1, GHGPSDTX167
FF-443-1	CLOSED VENT SYSTEM	6825A, N65, PSDTX49M1, GHGPSDTX167
FF-443-2	CLOSED VENT SYSTEM	6825A, N65, PSDTX49M1, GHGPSDTX167
FF-84PH	CLOSED VENT SYSTEM	6825A, N65, PSDTX49M1, GHGPSDTX167
FF-CCS	CLOSED VENT SYSTEM	6825A, N65, PSDTX49M1, GHGPSDTX167
FF-D-108	CLOSED VENT SYSTEM	6825A, N65, PSDTX49M1, GHGPSDTX167
FF-DOCKS-1	CLOSED VENT SYSTEM	6825A, N65, PSDTX49M1, GHGPSDTX167
FF-DOCKS-2	CLOSED VENT SYSTEM	6825A, N65, PSDTX49M1, GHGPSDTX167
FF-DOCKS-3	CLOSED VENT SYSTEM	6825A, N65, PSDTX49M1, GHGPSDTX167
FF-DOCKS-4	CLOSED VENT SYSTEM	6825A, N65, PSDTX49M1, GHGPSDTX167
FF-DOCKS-5	CLOSED VENT SYSTEM	6825A, N65, PSDTX49M1, GHGPSDTX167
FF-DOCKS-6	CLOSED VENT SYSTEM	6825A, N65, PSDTX49M1, GHGPSDTX167
FF-GHU-245	CLOSED VENT SYSTEM	6825A, N65, PSDTX49M1, GHGPSDTX167
F-FGMD	FUEL GAS MIX DRUM FUGITIVES	6825A, N65, PSDTX49M1, GHGPSDTX167
FF-KELAB	CLOSED VENT SYSTEM	6825A, N65, PSDTX49M1, GHGPSDTX167
FF-LAB	CLOSED VENT SYSTEM	6825A, N65, PSDTX49M1, GHGPSDTX167
FF-PS-1215	CLOSED VENT SYSTEM	6825A, N65, PSDTX49M1, GHGPSDTX167
FF-PS-162	CLOSED VENT SYSTEM	6825A, N65, PSDTX49M1, GHGPSDTX167
FF-PS-1650	CLOSED VENT SYSTEM	6825A, N65, PSDTX49M1, GHGPSDTX167

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
FF-PS-236	CLOSED VENT SYSTEM	6825A, N65, PSDTX49M1, GHGPSDTX167
FF-PS-274	CLOSED VENT SYSTEM	6825A, N65, PSDTX49M1, GHGPSDTX167
FF-PS-3650	CLOSED VENT SYSTEM	6825A, N65, PSDTX49M1, GHGPSDTX167
FF-PS-402	CLOSED VENT SYSTEM	6825A, N65, PSDTX49M1, GHGPSDTX167
FF-PS-403	CLOSED VENT SYSTEM	6825A, N65, PSDTX49M1, GHGPSDTX167
FF-PS-404	CLOSED VENT SYSTEM	6825A, N65, PSDTX49M1, GHGPSDTX167
FF-PS-405	CLOSED VENT SYSTEM	6825A, N65, PSDTX49M1, GHGPSDTX167
FF-PS-406	CLOSED VENT SYSTEM	6825A, N65, PSDTX49M1, GHGPSDTX167
FF-PS-427	CLOSED VENT SYSTEM	6825A, N65, PSDTX49M1, GHGPSDTX167
FF-PS-434	CLOSED VENT SYSTEM	6825A, N65, PSDTX49M1, GHGPSDTX167
FF-PS-435	CLOSED VENT SYSTEM	6825A, N65, PSDTX49M1, GHGPSDTX167
FF-PS-436	CLOSED VENT SYSTEM	6825A, N65, PSDTX49M1, GHGPSDTX167
FF-PS-439	CLOSED VENT SYSTEM	6825A, N65, PSDTX49M1, GHGPSDTX167
FF-PS-441	CLOSED VENT SYSTEM	6825A, N65, PSDTX49M1, GHGPSDTX167
FF-PS-449	CLOSED VENT SYSTEM	6825A, N65, PSDTX49M1, GHGPSDTX167
FF-PS-451	CLOSED VENT SYSTEM	6825A, N65, PSDTX49M1, GHGPSDTX167
FF-PS-457	CLOSED VENT SYSTEM	6825A, N65, PSDTX49M1, GHGPSDTX167
FF-PS-4600	CLOSED VENT SYSTEM	6825A, N65, PSDTX49M1, GHGPSDTX167
FF-PS-475	CLOSED VENT SYSTEM	6825A, N65, PSDTX49M1, GHGPSDTX167
FF-PS-476	CLOSED VENT SYSTEM	6825A, N65, PSDTX49M1, GHGPSDTX167
FF-PS-6400	CLOSED VENT SYSTEM	6825A, N65, PSDTX49M1, GHGPSDTX167

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
FF-PS-J-8	CLOSED VENT SYSTEM	6825A, N65, PSDTX49M1, GHGPSDTX167
FF-SC-1907	CLOSED VENT SYSTEM	6825A, N65, PSDTX49M1, GHGPSDTX167
FF-TETRA-1	CLOSED VENT SYSTEM	6825A, N65, PSDTX49M1, GHGPSDTX167
FF-TETRA-2	CLOSED VENT SYSTEM	6825A, N65, PSDTX49M1, GHGPSDTX167
FF-TK-8010	CLOSED VENT SYSTEM	6825A, N65, PSDTX49M1, GHGPSDTX167
FF-WORU	CLOSED VENT SYSTEM	6825A, N65, PSDTX49M1, GHGPSDTX167
FF-WWTU	CLOSED VENT SYSTEM	6825A, N65, PSDTX49M1, GHGPSDTX167
FIREWTR2013-1	FIREWATER 2013-1	106.511/09/04/2000
FIREWTR2013-2	FIREWATER 2013-2	106.511/09/04/2000
FLARE-05	FLARE NO. 5	6825A, N65, PSDTX49M1, GHGPSDTX167
FLARE-103B	FLARE NO. B-103	6825A, N65, PSDTX49M1, GHGPSDTX167
FLARE-13	FLARE NO.13	6825A, N65, PSDTX49M1, GHGPSDTX167
FLARE-15	FLARE NO.15	6825A, N65, PSDTX49M1, GHGPSDTX167
FLARE-18	FLARE NO.18	6825A, N65, PSDTX49M1, GHGPSDTX167
FLARE-19	FLARE NO.19	6825A, N65, PSDTX49M1, GHGPSDTX167
FLARE-20	FLARE NO.20	6825A, N65, PSDTX49M1, GHGPSDTX167
FLARE-22	FLARE NO.22	6825A, N65, PSDTX49M1, GHGPSDTX167
FLARE-23	EMERGENCY FLARE NO. 23	6825A, N65, PSDTX49M1, GHGPSDTX167
FLARE-26	FLARE-26	6825A, N65, PSDTX49M1, GHGPSDTX167
F-PH 11	PUMP HOUSE 11 FUGITIVES	6825A, N65, PSDTX49M1, GHGPSDTX167
F-PH163	PUMP HOUSE 163 FUGITIVES	6825A, N65, PSDTX49M1, GHGPSDTX167

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
F-PH41	PUMP HOUSE 41 FUGITIVES	6825A, N65, PSDTX49M1, GHGPSDTX167
F-PH84	PUMP HOUSE 84 FUGITIVES	6825A, N65, PSDTX49M1, GHGPSDTX167
F-PIPE	PIPING ACROSS PLANT	6825A, N65, PSDTX49M1, GHGPSDTX167
F-PIPING	PIPING FUGITIVEES	6825A, N65, PSDTX49M1, GHGPSDTX167
F-SRTF	SRTF FUGITIVE	6825A, N65, PSDTX49M1, GHGPSDTX167
F-T-L1010	API SEPARATOR AT WWTU 8742	61/07/20/1992, 68/07/20/1992
F-T-L1020	API SEPARATOR AT WWTU 8742	61/07/20/1992, 68/07/20/1992
F-T-L1030	API SEPARATOR AT WWTU 8742	61/07/20/1992, 68/07/20/1992
F-T-L1110	API EFFLUENT TANK	61/07/20/1992, 68/07/20/1992
F-T-L1120	API EFFLUENT TANK	61/07/20/1992, 68/07/20/1992
F-T-L1210	API RECOVERED SKIM OIL TRANSFER TANK	61/07/20/1992, 68/07/20/1992
F-T-L1310	API RECOVERED SKIM OIL TRANSFER TANK	61/07/20/1992, 68/07/20/1992
F-T-L1410	API SLUDGE TANK	61/07/20/1992, 68/07/20/1992
F-T-L2010	EQUALIZATION TANK FROM API EFFLUENT	61/07/20/1992, 68/07/20/1992
F-T-L3010	WASTEWATER FLOCCULATION UNITS-FIXED ROOF TANKS	61/07/20/1992, 68/07/20/1992
F-T-L3110	DISSOLVED NITROGEN FLOTATION UNITS-FIXED ROOF TANK	61/07/20/1992, 68/07/20/1992
F-T-L3120	DISSOLVED NITROGEN FLOTATION UNITS-FIXED ROOF TANK	61/07/20/1992, 68/07/20/1992
F-T-L3210	DNF FLOAT TANK	61/07/20/1992, 68/07/20/1992
F-T-L3310	DNF EFFLUENT TANK	61/07/20/1992, 68/07/20/1992
F-T-L3320	DNF EFFLUENT TANK	61/07/20/1992, 68/07/20/1992
F-T-L5010	ACTIVATED SLUDGE W/DIFFUSED AERATION FIXED ROOF TK	61/07/20/1992, 68/07/20/1992

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
F-T-L5020	ACTIVATED SLUDGE W/DIFFUSED AERATION FIXED ROOF TK	61/07/20/1992, 68/07/20/1992
F-T-L6002	TANK	61/07/20/1992, 68/07/20/1992
F-T-L6010	WASTEWATER TANK	61/07/20/1992, 68/07/20/1992
F-T-L6020	WASTEWATER TANK	61/07/20/1992, 68/07/20/1992
F-T-L6110	WASTEWATER TANK	61/07/20/1992, 68/07/20/1992
F-T-L7010	WASTEWATER TANK	61/07/20/1992, 68/07/20/1992
F-T-L8010	TANK	61/07/20/1992, 68/07/20/1992
FUGITIVE	FUGITIVES FOR CRUDE OIL STORAGE TKS	6825A, N65, PSDTX49M1, GHGPSDTX167
F-WORU	WASTE OIL RECOVERY UNIT FUGITIVE	6825A, N65, PSDTX49M1, GHGPSDTX167
GFU-241-H1	GFU 241 HEATER B-101	6825A, N65, PSDTX49M1, GHGPSDTX167
GFU-242-H	GFU-242 HEATER	6825A, N65, PSDTX49M1, GHGPSDTX167
GFU-243-H	GFU-243-HEATER B-301	6825A, N65, PSDTX49M1, GHGPSDTX167
GFU-244-HA	GFU-244 HEATERS F-101	6825A, N65, PSDTX49M1, GHGPSDTX167
GFU-244-HB	GFU-244 HEATERS F-102	6825A, N65, PSDTX49M1, GHGPSDTX167
HCU-942H1/2	HCU 942 HEATER F1000	6825A, N65, PSDTX49M1, GHGPSDTX167
HCU-942H3	HCU-942 HEATER F2000	6825A, N65, PSDTX49M1, GHGPSDTX167
HCU-943-A/B	HCU-943 REACTOR HEATER 1	6825A, N65, PSDTX49M1, GHGPSDTX167
HCU-943-C	HCU-943 REACTOR HTR 3	6825A, N65, PSDTX49M1, GHGPSDTX167
HFAU-443-H	HFAU 443 HEATER H-1	6825A, N65, PSDTX49M1, GHGPSDTX167
MC-24/25	MARINE VAPOR COMBUSTORS 24 AND 25	6825A, N65, PSDTX49M1, GHGPSDTX167
NSTF TK 100 99	WATER DRAW	106.511/09/04/2000

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
NSTF TK 151	WATER DRAW	106.511/09/04/2000
PRO-WWTU	WASTEWATER TREATMENT UNIT 8742	61/07/20/1992, 68/07/20/1992
PW-HVP-1	CENTRAL SHOP HIGH TVP PARTS WASHER 1	125/09/23/1982
PW-LVP-1	CENTRAL SHOP LOW TVP PARTS WASHER 1	125/09/23/1982
PW-LVP-2	CENTRAL SHOP LOW TVP PARTS WASHER 2	125/09/23/1982
PW-LVP-3	CENTRAL SHOP LOW TVP PARTS WASHER 3	125/09/23/1982
PW-LVP-4	CENTRAL SHOP LOW TVP PARTS WASHER 4	125/09/23/1982
RTO	WWTU-8742 REGENERATIVE THERMAL OXIDIZER	88/07/20/1992
SRU-543	SULFUR RECOVERY UNIT 543	6825A, N65, PSDTX49M1, GHGPSDTX167
SRU-544	SULFUR RECOVERY UNIT 544	6825A, N65, PSDTX49M1, GHGPSDTX167
SRU-545	SULFUR RECOVERY UNIT 545	6825A, N65, PSDTX49M1, GHGPSDTX167
SRU-546	SULFER RECOVERY UNIT 546	6825A, N65, PSDTX49M1, GHGPSDTX167
T-100	TANK 100	6825A, N65, PSDTX49M1, GHGPSDTX167
T-103	TANK 103	6825A, N65, PSDTX49M1, GHGPSDTX167
T-106	TANK 106	6825A, N65, PSDTX49M1, GHGPSDTX167
T-107	TANK 107	6825A, N65, PSDTX49M1, GHGPSDTX167
T-108	TANK 108	6825A, N65, PSDTX49M1, GHGPSDTX167
T-109	TANK 109	6825A, N65, PSDTX49M1, GHGPSDTX167
T-110	TANK 110	6825A, N65, PSDTX49M1, GHGPSDTX167
T-111	TANK 111	6825A, N65, PSDTX49M1, GHGPSDTX167
T-133	TANK 133	6825A, N65, PSDTX49M1, GHGPSDTX167

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
T-151	FF OIL RECOVERY TANK	6825A, N65, PSDTX49M1, GHGPSDTX167
T-1790	DNF FLOATS MLE TANK	111/09/23/1982
T-1791	DNF FLOATS MLE TANK	111/09/23/1982
T-1848	NON-MACT VOC TANK	6825A, N65, PSDTX49M1, GHGPSDTX167
T-1849	NON-MACT VOC TANK	6825A, N65, PSDTX49M1, GHGPSDTX167
T-1912	TANK 1912	124/05/12/1981
T-2101	TANK 2101	6825A, N65, PSDTX49M1, GHGPSDTX167
T-2105	TANK 2105	6825A, N65, PSDTX49M1, GHGPSDTX167
T-2110	TANK 2110	6825A, N65, PSDTX49M1, GHGPSDTX167
T-2111	TANK 2111	6825A, N65, PSDTX49M1, GHGPSDTX167
T-2112	TANK 2112	6825A, N65, PSDTX49M1, GHGPSDTX167
T-2113	FF OIL RECOVERY TANK	6825A, N65, PSDTX49M1, GHGPSDTX167
T-2117	TANK 2117	6825A, N65, PSDTX49M1, GHGPSDTX167
T-2132	TANK 2132	6825A, N65, PSDTX49M1, GHGPSDTX167
T-2133	TANK 2133	6825A, N65, PSDTX49M1, GHGPSDTX167
T-2137	TANK 2137	6825A, N65, PSDTX49M1, GHGPSDTX167
T-2145	FF OIL RECOVERY TANK	6825A, N65, PSDTX49M1, GHGPSDTX167
T-2148	TANK 2148	6825A, N65, PSDTX49M1, GHGPSDTX167
T-2159	TANK 2159	6825A, N65, PSDTX49M1, GHGPSDTX167
T-2160	TANK 2160	6825A, N65, PSDTX49M1, GHGPSDTX167
T-2161	TANK 2161	6825A, N65, PSDTX49M1, GHGPSDTX167

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
T-2162	TANK 2162	6825A, N65, PSDTX49M1, GHGPSDTX167
T-2163	TANK 2163	6825A, N65, PSDTX49M1, GHGPSDTX167
T-2164	TANK 2164	6825A, N65, PSDTX49M1, GHGPSDTX167
T-2182	TANK 2182	6825A, N65, PSDTX49M1, GHGPSDTX167
T-2183	TANK 2183	6825A, N65, PSDTX49M1, GHGPSDTX167
T-2186	TANK 2186	6825A, N65, PSDTX49M1, GHGPSDTX167
T-2401	TANK 2401	86/11/25/1985
T-2588	FF OIL RECOVERY TANK	6825A, N65, PSDTX49M1, GHGPSDTX167
T-2590	FF OIL RECOVERY TANK	6825A, N65, PSDTX49M1, GHGPSDTX167
T-283	TANK 283	6825A, N65, PSDTX49M1, GHGPSDTX167
T-284	TANK 284	6825A, N65, PSDTX49M1, GHGPSDTX167
T-285	TANK 285	6825A, N65, PSDTX49M1, GHGPSDTX167
T-2900	TANK 2900	86757
T-5002	STORAGE TANK 5002	6825A, N65, PSDTX49M1, GHGPSDTX167
T-5003	STORAGE TANK 5003	6825A, N65, PSDTX49M1, GHGPSDTX167
T-5	TANK 5	6825A, N65, PSDTX49M1, GHGPSDTX167
T-77	TANK 77	6825A, N65, PSDTX49M1, GHGPSDTX167
T-78	SOUR WATER STORAGE TANK 78	6825A, N65, PSDTX49M1, GHGPSDTX167
T-8010	COKER 843 SLUDGE TANK	6825A, N65, PSDTX49M1, GHGPSDTX167
T-82	TANK 82	6825A, N65, PSDTX49M1, GHGPSDTX167
T-889	TANK 889	6825A, N65, PSDTX49M1, GHGPSDTX167

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
T-88	SOUR WATER STORAGE TANK 88	6825A, N65, PSDTX49M1, GHGPSDTX167
T-896	TANK 896	6825A, N65, PSDTX49M1, GHGPSDTX167
T-925	TANK 925	6825A, N65, PSDTX49M1, GHGPSDTX167
T-926	TANK 926	6825A, N65, PSDTX49M1, GHGPSDTX167
T-99	TANK 99	6825A, N65, PSDTX49M1, GHGPSDTX167
TRACHWPUMP	TRACT H WEST PUMP	106.512/06/13/2001
VACUUM	VACUUM PRODUCING SYSTEMS	124/09/23/1982

Alternative Requirement

Alternative Requirement..... 383

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
REGION 6
1445 ROSS AVENUE, SUITE 1200
DALLAS, TX 75202-2733

JUN 2 0 2014

NSR
RECEIVED
JUN 26 2014
TCEQ-Region 10
Beaumont

Paula LaRocca, Manager Environmental Engineering
Valero Port Arthur Refinery, Complex E
P.O. Box 909
Port Arthur, TX 77614-0909

Re: Request for Approval - Alternative Monitoring Plan (AMP)
Valero Port Arthur Refinery RN 102584026
Fluid Catalytic Cracking Unit
Wet Gas Scrubber Opacity Interference
NSPS Part 60, Subparts J and A
NESHAP Part 63, Subparts UUU and A
Consent Decree No. SA-05-CA-0569

Dear Mr. Hopper:

This letter is in response to Valero Port Arthur Refinery's letter dated January 23, 2009, requesting approval of an Alternative Monitoring Plan (AMP) pursuant to the Valero Consent Decree (Civil Action No. SA-05-CA-0569), New Source Performance Standards (NSPS) for Petroleum Refineries (Subpart J), and National Emission Standards for Hazardous Air Pollutants (NESHAP) for Source Categories, Petroleum Refineries (Subpart UUU). The AMP proposes wet gas scrubber (WGS) process parameter monitoring as an alternative to a Continuous Opacity Monitoring System (COMS) for Valero Port Arthur Refinery's Fluid Catalytic Cracking Unit (FCCU) regenerator stack, due to moisture interference in the stack. Based upon the particular design of your WGS unit, process specific information, and performance test data provided for the FCCU WGS, the United States Environmental Protection Agency (EPA) approves your AMP for the FCCU WGS, as delineated within this letter. However, EPA Region 6 does not approve adjusting the WGS operating parameter limits (OPLs) to 70 percent of the operating parameter values that were measured during performance. Instead, the OPLs must be based on the operating parameter values established from the performance test.

The AMP request, emails from Robert Hill of your staff, and performance test results from October 9, 10, and 11, 2012, provided by email on May 17, 2013, were used to establish acceptable WGS OPLs. EPA approves the following OPLs, based on three-hour rolling averages:

- Minimum Liquid-to-Gas (L/G) Ratio of 0.057: The total liquid flow rate divided by the total gas flow rate in the scrubber. The L value will be in gallons per minute and the G value will be in dry standard cubic feet per minute (dscfm).
- Minimum differential pressure across the quench tower scrubber of 7.6 inches of water.
- Maximum agglo-filtering modules (AFM) recirculation pump (P-0002) discharge pressure of 102.9 pounds per square inch gauge (psig).

Valero Port Arthur Refinery will calculate hourly averages for L using either discharge pressure data and pump curve diagrams, or flow monitors, for each operating pump that provides liquid flow to any portion of the wet gas scrubber. Valero Port Arthur Refinery will calculate hourly averages for G using the result of the Qr calculation from 40 CFR §63.1573(a)(2), which is an allowable alternative to

INFORMATION COPY

directly measuring the gas flow rate. The main air blower flow rate data (Q_a) will be converted to dscfm for the regenerator gas flow rate calculation using contemporaneous ambient humidity data.

This AMP approval should be referenced and attached to the facility's New Source Review (NSR) and Title V permits for federal enforceability. An excess emissions deviation shall be reported and recorded for each one-hour period in which the three-hour rolling average of one or more of the OPLs listed above exceeds a maximum value, or is less than a minimum value. OPLs may be updated if any conditions under which this AMP was approved have changed, by requesting an AMP modification with submittal of performance test results that demonstrate compliance. If you have any questions about this AMP request response, please contact Charles Handrich of my staff at (214) 665-6553.

Sincerely,

Margaret Osborne

for Steve Thompson
Associate Director
Air, Toxics & Inspection
Coordination Branch

cc: Kathryn Sauceda, Region 10, Texas Commission on Environmental Quality (TCEQ)
Michael De La Cruz, Office of Compliance and Enforcement, TCEQ
Frank Burleson, Office of Compliance and Enforcement, TCEQ

Appendix A

Acronym List 386

Acronym List

The following abbreviations or acronyms may be used in this permit:

ACFM ..... actual cubic feet per minute
AMOC ..... alternate means of control
ARP ..... Acid Rain Program
ASTM ..... American Society of Testing and Materials
B/PA ..... Beaumont/Port Arthur (nonattainment area)
CAM ..... Compliance Assurance Monitoring
CD ..... control device
CEMS ..... continuous emissions monitoring system
CFR ..... Code of Federal Regulations
COMS ..... continuous opacity monitoring system
CVS ..... closed vent system
D/FW ..... Dallas/Fort Worth (nonattainment area)
EP ..... emission point
EPA ..... U.S. Environmental Protection Agency
EU ..... emission unit
FCAA Amendments ..... Federal Clean Air Act Amendments
FOP ..... federal operating permit
gr/100 scf ..... grains per 100 standard cubic feet
HAP ..... hazardous air pollutant
H/G/B ..... Houston/Galveston/Brazoria (nonattainment area)
H_2S ..... hydrogen sulfide
ID No. ..... identification number
lb/hr ..... pound(s) per hour
MACT ..... Maximum Achievable Control Technology (40 CFR Part 63)
MMBtu/hr ..... Million British thermal units per hour
NA ..... nonattainment
N/A ..... not applicable
NADB ..... National Allowance Data Base
NESHAP ..... National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61)
NO_x ..... nitrogen oxides
NSPS ..... New Source Performance Standard (40 CFR Part 60)
NSR ..... New Source Review
ORIS ..... Office of Regulatory Information Systems
Pb ..... lead
PBR ..... Permit By Rule
PEMS ..... predictive emissions monitoring system
PM ..... particulate matter
ppmv ..... parts per million by volume
PRO ..... process unit
PSD ..... prevention of significant deterioration
psia ..... pounds per square inch absolute
SIP ..... state implementation plan
SO_2 ..... sulfur dioxide
TCEQ ..... Texas Commission on Environmental Quality
TSP ..... total suspended particulate
TVP ..... true vapor pressure
U.S.C. ..... United States Code
VOC ..... volatile organic compound

Appendix B

Major NSR Summary Table 388

Major NSR Summary Table

Permit Number 6825A, PSDTX49M1, N65					Issuance Date: November 16, 2018		
Emission Point No. (1)	**Source Name (2)**	**Air Contaminant Name (3)**	**Emission Rates**		**Monitoring and Testing Requirements**	**Recordkeeping Requirements**	**Reporting Requirements**
			lbs/hour	**TPY (4)**	**Spec. Cond.**	**Spec. Cond.**	**Spec. Cond.**
Emission Caps (11)							
		SO_2	771.9	1,977 (12)	3, 4, 5, 6, 7, 9, 10, 11, 13, 15, 16, 17, 18, 19, 20, 21, 22, 24, 26, 27, 28, 30, 31, 32, 34, 36, 44, 46, 47, 48, 49, 50, 51, 52, 53, 55, 56, 57, 59, 62, 66, 87, 89	3, 4, 5, 6, 7, 9, 10, 13, 15, 16, 17, 19, 20, 21, 22, 24, 26, 27, 29, 30, 32, 34, 36, 41, 44, 46, 47, 50, 51, 52, 53, 55, 56, 57, 64, 66, 87, 89	3, 4, 5, 7, 21, 26, 27, 28, 32, 36, 50, 51, 53, 57, 66, 67, 68
		SO_2	705.4 (12)	1,503 (6) (12)			
		NO_x	885.8	3,191 (12)			
		NO_x	859.9	1,611 (6) (12)			
		CO	1207	3,780.00 (12)			
		CO	1174	2,950 (6) (12)			
		PM	132.6	538.00			
		PM	120.8	455.00 (6)			
		Ammonia	0.10	0.20			
		Ammonia (5)	1.43	4.87			
		Ammonia (6)	2.66	8.99			

Major NSR Summary Table

Permit Number 6825A, PSDTX49M1, N65					Issuance Date: November 16, 2018		
Emission Point No. (1)	**Source Name (2)**	**Air Contaminant Name (3)**	**Emission Rates**		**Monitoring and Testing Requirements**	**Recordkeeping Requirements**	**Reporting Requirements**
			lbs/hour	**TPY (4)**	**Spec. Cond.**	**Spec. Cond.**	**Spec. Cond.**
		H_2S	4.64	11.40			
		Benzene	2.77	9.39			
		HF	0.33	1.64			
		MTBE	12.11	27.89			
		VOC	564	1,592			
		VOC (14)	562.2	1,557			
		VOC (18)		1,729			
Emissions not in permit emission caps:							
BH15MSS	Burner Installation (15)	NO_x	130.50	1.44	66, 87	64, 66, 87	66
		CO	283.10	3.11			
E-01-1241	Heater 1241-H1 MSS	VOC	0.10	0.40	3, 34, 50, 66, 87	3, 34, 50, 64, 66, 85, 87	3, 50, 66
		NO_x	0.20	0.90			
		SO_2	0.01	0.01			

Major NSR Summary Table

Permit Number 6825A, PSDTX49M1, N65					Issuance Date: November 16, 2018		
Emission Point No. (1)	**Source Name (2)**	**Air Contaminant Name (3)**	**Emission Rates**		**Monitoring and Testing Requirements**	**Recordkeeping Requirements**	**Reporting Requirements**
			lbs/hour	**TPY (4)**	**Spec. Cond.**	**Spec. Cond.**	**Spec. Cond.**
		CO	0.20	0.90			
		PM	0.10	0.40			
E-02-1241	Heater 1241-H2 MSS	VOC	0.10	0.40	3, 34, 50, 66, 87	3, 34, 50, 64, 66, 85, 87	3, 50, 66
		NO_x	0.20	0.90			
		SO_2	0.01	0.01			
		CO	0.20	0.90			
		PM	0.10	0.40			

Major NSR Summary Table

Permit Number 6825A, PSDTX49M1, N65					Issuance Date: November 16, 2018		
Emission Point No. (1)	**Source Name (2)**	**Air Contaminant Name (3)**	**Emission Rates**		**Monitoring and Testing Requirements**	**Recordkeeping Requirements**	**Reporting Requirements**
			lbs/hour	**TPY (4)**	**Spec. Cond.**	**Spec. Cond.**	**Spec. Cond.**
E-01-245	Heater 245	NO_x	1.44	6.31	3, 34, 35, 50, 66, 87	3, 34, 35, 50, 64, 66, 87	3, 50, 66
		VOC	0.18	0.77			
		SO_2	0.85	3.73			
		SO_2 (20)	0.85	0.96			
		CO	2.48	10.84			
		PM	0.26	1.07			
		PM_{10}	0.26	1.07			
		$PM_{2.5}$	0.26	1.07			
E-V54	CCR Regen Vent	HCl	0.02	0.07	66, 87	64, 66, 87	66
		VOC	0.16	0.70			

Major NSR Summary Table

Permit Number 6825A, PSDTX49M1, N65					Issuance Date: November 16, 2018		
Emission Point No. (1)	**Source Name (2)**	**Air Contaminant Name (3)**	**Emission Rates**		**Monitoring and Testing Requirements**	**Recordkeeping Requirements**	**Reporting Requirements**
			lbs/hour	**TPY (4)**	**Spec. Cond.**	**Spec. Cond.**	**Spec. Cond.**
F-20-Flare	Flare 20 MSS	VOC	0.06	0.28	3, 5, 6, 62, 66, 87, 89	3, 5, 6, 64, 66, 85, 87, 89	3, 5, 66
		NO_x	0.87	3.81			
		SO_2	0.80	3.50			
		CO	2.40	10.50			
F-PIPE	F-PIPE	VOC	0.18	0.78	3, 57, 59, 66, 87	3, 57, 64, 66, 87	3, 57, 66

Major NSR Summary Table

Permit Number 6825A, PSDTX49M1, N65					Issuance Date: November 16, 2018		
Emission Point No. (1)	**Source Name (2)**	**Air Contaminant Name (3)**	**Emission Rates**		**Monitoring and Testing Requirements**	**Recordkeeping Requirements**	**Reporting Requirements**
			lbs/hour	**TPY (4)**	**Spec. Cond.**	**Spec. Cond.**	**Spec. Cond.**
F-943, F-7843, F-7945, F-8748-SWS, E-26-FLARE, T-CX2-SW-2, T-CX2-CRUDE-1, T-CX2-CRUDE-2, T-CX2-NAPTH-1, T-CX2-GASOL-1, T-CX2-GASOL-2, T-2186, T-CX2-RESID-1, T-CX2-RESID-2, T-CX2-Amine-1, T-CX2-Amine-2, E-01-943, E-02-943, F-432-CT, F-446CT	COEXII VOC Cap (9)	VOC	37.92	108.25	3, 5, 6, 9, 10, 11, 21, 50, 52, 53, 54, 58, 59, 62, 66, 87	3, 5, 6, 9, 10, 21,50, 52, 53, 54, 58, 64, 66, 87	3, 5, 21, 50, 58, 53, 66
1913FUG	Tank 1913 Fugitives (4) (17)	VOC	0.02	0.09	66, 87	64, 66, 87	66
1913	Tank 1913 (17)	VOC	0.32	1.41	3, 5, 9, 10, 11, 66, 87	3, 5, 9, 10, 64, 66, 87	3, 5, 66
T-82	Tank 82	VOC	0.62	0.15	5, 9, 10, 11, 66, 87	5, 9, 10, 64, 66, 87	5, 66
T-283	Tank 283	VOC	6.62	3.05	3, 5, 9, 10, 11, 66, 87	3, 5, 9, 10, 64, 66, 87	3, 5, 66

Major NSR Summary Table

Permit Number 6825A, PSDTX49M1, N65					Issuance Date: November 16, 2018		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Spec. Cond.	Spec. Cond.	Spec. Cond.
T-284	Tank 284	VOC	6.62	3.05	3, 5, 9, 10, 11, 66, 87	3, 5, 9, 10, 64, 66, 87	3, 5, 66
T-285	Tank 285	VOC	6.62	3.05	3, 5, 9, 10, 11, 66, 87	3, 5, 9, 10, 64, 66, 87	3, 5, 66
T-106	Tank 106	VOC	8.99	2.70	3, 5, 9, 10, 11, 66, 87	3, 5, 9, 10, 64, 66, 87	3, 5, 66
T-107	Tank 107	VOC	9.01	2.73	3, 5, 9, 10, 11, 66, 87	3, 5, 9, 10, 64, 66, 87	3, 5, 66
T-100	Tank 100	VOC	42.70	2.98	5, 9, 10, 11, 66, 87	5, 9, 10, 64, 66, 87	5, 66
T-103	Tank 103	VOC	31.80	2.98	5, 66, 87	5, 64, 66, 87	5, 66
T-110	Tank 110	VOC	7.26	2.48	3, 5, 9, 10, 11, 66, 87	3, 5, 9, 10, 64, 66, 87	3, 5, 66
T-926	Tank 926	VOC	2.98	6.89	5, 9, 10, 11, 66, 87	5, 9, 10, 64, 66, 87	5, 66
T-1848	Tank 1848	VOC	1.26	0.30	5, 9, 10, 11, 66, 87	5, 9, 10, 64, 66, 87	5, 66
T-2164	Tank 2164	VOC	34.28	10.97	5, 9, 66, 87	5, 9, 64, 66, 87	5, 66
T-2163	Tank 2163	VOC	34.28	10.97	5, 9, 66, 87	5, 9, 64, 66, 87	5, 66
T-2105	Tank 2105	VOC	36.04	7.55	5, 9, 66, 87	5, 9, 64, 66, 87	5, 66
T-99	Tank 99	VOC	26.97	2.98	5, 9, 66, 87	5, 9, 64, 66, 87	5, 66

Major NSR Summary Table

Permit Number 6825A, PSDTX49M1, N65					Issuance Date: November 16, 2018		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Spec. Cond.	Spec. Cond.	Spec. Cond.
T-111	Tank 111	VOC	7.26	2.48	3, 5, 9, 10, 11, 66, 87	3, 5, 9, 10, 64, 66, 87	3, 5, 66
T-112	112	VOC	9.49	3.50	66, 86	64, 66, 86	66
		H_2S	0.14	0.24			
T-113	113	VOC	9.49	3.50	66, 86	64, 66, 86	66
		H_2S	0.14	0.24			
T-114	114	VOC	9.49	3.50	66, 86	64, 66, 86	66
		H_2S	0.14	0.24			
T-8010	Coker 843 sludge tank	VOC	0.04	0.18	63, 66, 87	63, 64, 66, 87	66
T-8400	Coker 844 sludge tank	VOC	0.04	0.18	63, 66, 87	63, 64, 66, 87	66
T-8002	547 Sulfur Tank	H_2S	0.48	0.39	27, 66, 87	27, 64, 66, 87	27, 66
T-2162	Tank 2162	VOC	2.06	1.11	5, 9, 10, 11, 66, 87	5, 9, 10, 64, 66, 87	5, 66
T-896	Tank 896	VOC	2.75	7.26	5, 9, 10, 11, 66, 87	5, 9, 10, 64, 66, 87	5, 66

Major NSR Summary Table

Permit Number 6825A, PSDTX49M1, N65					Issuance Date: November 16, 2018		
Emission Point No. (1)	**Source Name (2)**	**Air Contaminant Name (3)**	**Emission Rates**		**Monitoring and Testing Requirements**	**Recordkeeping Requirements**	**Reporting Requirements**
			lbs/hour	**TPY (4)**	**Spec. Cond.**	**Spec. Cond.**	**Spec. Cond.**
T-1849	Tank 1849	VOC	1.68	2.30	5, 9, 10, 11, 66, 87	5, 9, 10, 64, 66, 87	5, 66
T-2133	Tank 2133	VOC	4.53	11.15	5, 9, 10, 11, 66, 87	5, 9, 10, 64, 66, 87	5, 66
F-136ACT	Cooling Tower 136A	PM	0.73	2.14	5, 20, 66, 87	5, 20, 64, 66, 87	5, 66
		PM_{10}	0.73	2.14			
		$PM_{2.5}$	0.73	2.14			
F-136BCT	Cooling Tower 136B	PM	0.74	2.17	5, 20, 66, 87	5, 20, 64, 66, 87	5, 66
		PM_{10}	0.74	2.17			
		$PM_{2.5}$	0.74	2.17			
F-366CT	Cooling Tower 366	PM	0.56	1.64	5, 20, 66, 87	5, 20, 64, 66, 87	5, 66
		PM_{10}	0.56	1.64			
		$PM_{2.5}$	0.56	1.64			
E-01-844	DCU 844 Coker Furnace #1	NO_x	3.45	13.75	34, 50, 52, 53, 54, 66, 87	34, 50, 52, 53, 54, 64, 66, 87	50, 53, 66
		NO_x (MSS)	34.55	(22)			

Major NSR Summary Table

Permit Number 6825A, PSDTX49M1, N65					Issuance Date: November 16, 2018		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Spec. Cond.	Spec. Cond.	Spec. Cond.
		VOC	1.24	4.94			
		SO_2	5.34	3.93			
		CO	16.57	32.97			
		CO (MSS)	82.83	(22)			
		PM	1.84	6.99			
		PM_{10}	1.84	6.99			
		$PM_{2.5}$	1.84	6.99			
		NH_3	1.01	4.00			

Major NSR Summary Table

Permit Number 6825A, PSDTX49M1, N65					Issuance Date: November 16, 2018		
Emission Point No. (1)	**Source Name (2)**	**Air Contaminant Name (3)**	**Emission Rates**		**Monitoring and Testing Requirements**	**Recordkeeping Requirements**	**Reporting Requirements**
			lbs/hour	**TPY (4)**	**Spec. Cond.**	**Spec. Cond.**	**Spec. Cond.**
E-02-844	DCU 844 Coker Furnace #2	NO_x	3.45	13.75	34, 50, 52, 53, 54, 66, 87	34, 50, 52, 53, 54, 64, 66, 87	50, 53, 66
		NO_x (MSS)	34.55	(22)			
		VOC	1.24	4.94			
		SO_2	5.34	3.93			
		CO	16.57	32.97			
		CO (MSS)	82.83	(22)			
		PM	1.84	6.99			
		PM_{10}	1.84	6.99			
		$PM_{2.5}$	1.84	6.99			
		NH_3	1.01	4.00			
F-LOADING	SRU 547 Truck Sulfur Loading	H_2S	0.72	0.62	27, 66, 87	27, 64, 66, 87	27, 66

Major NSR Summary Table

Permit Number 6825A, PSDTX49M1, N65					Issuance Date: November 16, 2018		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Spec. Cond.	Spec. Cond.	Spec. Cond.
E-05-SCOT	SRU 547	VOC	0.45	1.96	27, 30, 50, 52, 53, 66, 87	27, 30, 50, 52, 53, 64, 66, 87	27, 50, 53, 66, 67
		NO_x	6.63	29.03			
		CO	36.19	63.41			
		SO_2	81.46	142.72			
		PM	1.23	5.41			
		PM_{10}	1.23	5.41			
		$PM_{2.5}$	1.23`	5.41			
		H_2S	0.88	3.85			
CSV844	Coker Unit 844 Steam Vent	VOC	55.00	35.50	39, 66, 87	39, 64, 66, 87	66
		PM	1.31	0.85			
		PM_{10}	1.31	0.85			
		$PM_{2.5}$	1.31	0.85			
		H_2S	3.13	2.02			

Major NSR Summary Table

Permit Number 6825A, PSDTX49M1, N65					Issuance Date: November 16, 2018		
Emission Point No. (1)	**Source Name (2)**	**Air Contaminant Name (3)**	**Emission Rates**		**Monitoring and Testing Requirements**	**Recordkeeping Requirements**	**Reporting Requirements**
			lbs/hour	**TPY (4)**	**Spec. Cond.**	**Spec. Cond.**	**Spec. Cond.**
CSV843	Coker Unit 843 Steam Vent	VOC	55.00	61.38	39, 66, 87	39, 64, 66, 87	66
		PM	7.72	8.61			
		PM_{10}	7.72	8.61			
		$PM_{2.5}$	7.72	8.61			
		H_2S	18.38	20.51			
		PM (21)	2.28	1.75			
		PM_{10} (21)	2.28	1.75			
		$PM_{2.5}$ (21)	2.28	1.75			
		H_2S (21)	5.43	4.18			
F-844PM	Unit 844 coke handling (FINS F-844-1 to F-844-6)	PM	0.26	0.40	5, 44, 46, 47, 48, 49, 66, 87	5, 41, 44, 46, 47, 64, 66, 87	5, 66
		PM_{10}	0.12	0.19			
		$PM_{2.5}$	0.02	0.03			
WWC	Coker 844 Wastewater	VOC	0.01	0.03	60, 61, 66, 87	61, 64, 66, 87	66

Major NSR Summary Table

Permit Number 6825A, PSDTX49M1, N65					Issuance Date: November 16, 2018		
Emission Point No. (1)	**Source Name (2)**	**Air Contaminant Name (3)**	**Emission Rates**		**Monitoring and Testing Requirements**	**Recordkeeping Requirements**	**Reporting Requirements**
			lbs/hour	**TPY (4)**	**Spec. Cond.**	**Spec. Cond.**	**Spec. Cond.**
	Collection System						
MSS	Coker 844 Project MSS (23)	VOC	542.76	5.49	66, 86, 87	64, 66, 84, 85, 86, 87	66
		NO_x	29.03	0.51			
		CO	194.71	3.27			
		SO_2	299.15	8.97			
		H_2S	3.18	0.19			
		PM	1.48	<0.01			
		PM_{10}	1.48	<0.01			
		$PM_{2.5}$	1.48	<0.01			

Major NSR Summary Table

Permit Number 6825A, PSDTX49M1, N65					Issuance Date: November 16, 2018		
Emission Point No. (1)	**Source Name (2)**	**Air Contaminant Name (3)**	**Emission Rates**		**Monitoring and Testing Requirements**	**Recordkeeping Requirements**	**Reporting Requirements**
			lbs/hour	**TPY (4)**	**Spec. Cond.**	**Spec. Cond.**	**Spec. Cond.**
Emissions in permit emission caps:							
E-01-BH 15	Boiler 15-41, Pre-mod. (7)	NO_x	26.10	114.32	5, 32, 34, 50, 52, 53, 66, 87	5, 32, 34, 50, 52, 53, 64, 66, 87	5, 32, 50, 53, 66
		VOC	2.35	9.97			
		SO_2	19.58	21.63			
		CO	35.82	72.33			
		PM	3.05	13.34			
E-02-BH 15, E-03-BH 15, E-04-BH 15	Boilerhouse 15 Subcap, Pre-mod (7)	NO_x	213.56	314.3	5, 34, 50, 66, 87	5, 34, 50, 64, 66, 87	5, 50, 66
		VOC	12.30	26.99			
		SO_2	129.01	211.9			
		CO	101.29	222.21			
		PM	8.62	37.78			
E-01-BH 15, E-02-BH 15, E-03-BH 15	Boilerhouse 15 Subcap, Post-mod Phase I (8)	NO_x	78.03	247.5	5, 32, 34, 50, 52, 53, 66, 87	5, 32, 34, 50, 52, 53, 64, 66, 87	5, 32, 50, 53, 66
		VOC	7.05	22.27			

Major NSR Summary Table

Permit Number 6825A, PSDTX49M1, N65					Issuance Date: November 16, 2018		
Emission Point No. (1)	**Source Name (2)**	**Air Contaminant Name (3)**	**Emission Rates**		**Monitoring and Testing Requirements**	**Recordkeeping Requirements**	**Reporting Requirements**
			lbs/hour	**TPY (4)**	**Spec. Cond.**	**Spec. Cond.**	**Spec. Cond.**
		SO_2	58.74	37.12			
		CO	107.46	169.9			
		PM	9.15	31.09			
E-01-BH 15, E-02-BH 15, E-03-BH 15	Boilerhouse 15 Subcap Post-mod PhaseII (13)	NO_x	78.03	339.0	5, 32, 34, 50, 52, 53, 66, 87	5, 32, 34, 50, 52, 53, 64, 66, 87	5, 32, 50, 53, 66
		VOC	7.05	30.51			
		SO_2	58.74	50.85			
		CO	107.46	232.8			
		PM	9.15	31.09			
E-06-BH 16	Boiler 16-34 (10)	NO_x (16)	6.50	28.60	5, 34, 50, 52, 53, 66, 87	5, 34, 50, 52, 53, 64, 66, 68, 87	5, 50, 53, 66, 68
E-07-BH 16	Boiler 16-35 (10)	NO_x (16)	9.00	39.40	5, 34, 50, 52, 53, 66, 87	5, 34, 50, 52, 53, 64, 66, 68, 87	5, 50, 53, 66,68
E-08-BH 16	Boiler 16-36 (10)	NO_x (16)	42.00	72.67	5, 34, 50, 52, 53, 66, 87	5, 34, 50, 52, 53, 64, 66, 68, 87	5, 50, 53, 66, 68
E-06-BH 16,	Boilerhouse 16	NO_x	200.41	414.5	5, 34, 50, 52, 53, 66, 87	5, 34, 50, 52, 53, 64, 66,	5, 50, 53, 66,68

Major NSR Summary Table

Permit Number 6825A, PSDTX49M1, N65					Issuance Date: November 16, 2018		
Emission Point No. (1)	**Source Name (2)**	**Air Contaminant Name (3)**	**Emission Rates**		**Monitoring and Testing Requirements**	**Recordkeeping Requirements**	**Reporting Requirements**
			lbs/hour	**TPY (4)**	**Spec. Cond.**	**Spec. Cond.**	**Spec. Cond.**
E-07-BH 16, E-08-BH 16	Subcap (10)	VOC	12.55	27.49		68, 87	
		SO_2	98.37	161.58			
		CO	103.35	226.36			
		PM	8.79	38.49			
E-01-146	Heater 146-H101	NO_x	49.56	146.99	3, 5, 32, 34, 50, 52, 53, 66, 87	3, 5, 32, 34, 50, 52, 53, 64, 66, 87	3, 5, 32, 50, 53, 66
		VOC	3.34	12.18			
		SO_2	11.36	18.67			
		CO	48.78	67.14			
		PM	4.34	16.83			

Major NSR Summary Table

Permit Number 6825A, PSDTX49M1, N65					Issuance Date: November 16, 2018		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Spec. Cond.	Spec. Cond.	Spec. Cond.
		NOx (20)	36.85	149.66			
		VOC (20	2.97	12.05			
		SO2 (20)	19.73	14.84			
		CO (20)	37.22	75.58			
		CO (MSS) (20)	87.97	(22)			
		PM (20)	4.10	16.64			
		PM10 (20)	4.10	16.64			
		PM2.5 (20)	4.10	16.64			
E-02-146	Heater 146-H102AB	NO_x	19.88	52.36	3, 5, 32, 34, 50, 52, 53, 66, 87	3, 5, 32, 34, 50, 52, 53, 64, 66, 87	3, 5, 32, 50, 53, 66
		VOC	1.60	5.04			
		SO_2	5.43	8.92			
		CO	19.59	27.76			
		PM	2.08	6.96			

Major NSR Summary Table

Permit Number 6825A, PSDTX49M1, N65					Issuance Date: November 16, 2018		
Emission Point No. (1)	**Source Name (2)**	**Air Contaminant Name (3)**	**Emission Rates**		**Monitoring and Testing Requirements**	**Recordkeeping Requirements**	**Reporting Requirements**
			lbs/hour	**TPY (4)**	**Spec. Cond.**	**Spec. Cond.**	**Spec. Cond.**
		NO_x (20)	16.12	70.61			
		VOC (20)	1.40	6.14			
		SO_2 (20)	9.33	7.57			
		CO (20)	17.59	38.53			
		CO (MSS) (20)	87.97	(22)			
		PM (20)	1.94	8.49			
		PM_{10} (20)	1.94	8.49			
		$PM_{2.5}$ (20)	1.94	8.49			
E-01-147	Heater 147-F-1100	NO_x	13.86	60.71	3, 5, 32, 34, 50, 52, 53, 66, 87	3, 5, 32, 34, 50, 52, 53, 64, 66, 87	3, 5, 32, 50, 53, 66
		VOC	2.14	9.35			
		SO_2	10.59	17.39			
		SO_2 (20)	10.59	7.58			
		CO	32.61	68.93			

Major NSR Summary Table

Permit Number 6825A, PSDTX49M1, N65					Issuance Date: November 16, 2018		
Emission Point No. (1)	**Source Name (2)**	**Air Contaminant Name (3)**	**Emission Rates**		**Monitoring and Testing Requirements**	**Recordkeeping Requirements**	**Reporting Requirements**
			lbs/hour	**TPY (4)**	**Spec. Cond.**	**Spec. Cond.**	**Spec. Cond.**
		PM	2.95	12.92			
		PM_{10}	2.95	12.92			
		$PM_{2.5}$	2.95	12.92			
E-02-147	Heater 147-F-1200	NO_x	7.80	17.28	3, 5, 32, 34, 50, 52, 53, 66, 87	3, 5, 32, 34, 50, 52, 53, 64, 66, 87	3, 5, 32, 50, 53, 66
		VOC	0.92	3.29			
		SO_2	4.10	5.66			
		SO2 (20)	4.10	3.29			
		CO	10.89	19.25			
		PM	1.28	5.60			
		PM_{10}	1.28	5.60			
		$PM_{2.5}$	1.28	5.60			

Major NSR Summary Table

Permit Number 6825A, PSDTX49M1, N65					Issuance Date: November 16, 2018		
Emission Point No. (1)	**Source Name (2)**	**Air Contaminant Name (3)**	**Emission Rates**		**Monitoring and Testing Requirements**	**Recordkeeping Requirements**	**Reporting Requirements**
			lbs/hour	**TPY (4)**	**Spec. Cond.**	**Spec. Cond.**	**Spec. Cond.**
E-01-1344	Heater 1344-H1	NO_x	34.09	115.39	3, 5, 32, 34, 50, 52, 53, 66, 87	3, 5, 32, 34, 50, 52, 53, 64, 66, 87	3, 5, 32, 50, 53, 66
		VOC	3.65	14.80			
		SO_2	11.95	19.64			
		SO_2 (20)	11.95	18.53			
		CO	40.45	82.24			
		PM	5.05	20.45			
		PM_{10}	5.05	20.45			
		$PM_{2.5}$	5.05	20.45			
E-02-1344	Heater 1344-H33	NO_x	3.82	9.06	3, 5, 32, 34, 35, 66, 87	3, 5, 34, 35, 64, 66, 87	3, 5, 66
		VOC	0.28	1.22			
		SO_2	0.85	1.39			
		CO	4.26	9.33			
		PM	0.38	1.69			

Major NSR Summary Table

Permit Number 6825A, PSDTX49M1, N65					Issuance Date: November 16, 2018		
Emission Point No. (1)	**Source Name (2)**	**Air Contaminant Name (3)**	**Emission Rates**		**Monitoring and Testing Requirements**	**Recordkeeping Requirements**	**Reporting Requirements**
			lbs/hour	**TPY (4)**	**Spec. Cond.**	**Spec. Cond.**	**Spec. Cond.**
		PM_{10}	0.38	1.69			
		$PM_{2.5}$	0.38	1.69			
E-03-1344	Heater 1344-H2_3_32	NO_x	12.80	26.81	3, 5, 32, 34, 50, 52, 53, 66, 87	3, 5, 32, 34, 50, 52, 53, 64, 66, 87	3, 5, 32, 50, 53, 66
		VOC	0.86	2.41			
		SO_2	2.89	4.75			
		SO_2 (20)	2.89	3.02			
		CO	10.64	13.43			
		PM	1.19	3.33			
		PM_{10}	1.19	3.33			
		$PM_{2.5}$	1.19	3.33			

Major NSR Summary Table

Permit Number 6825A, PSDTX49M1, N65					Issuance Date: November 16, 2018		
Emission Point No. (1)	**Source Name (2)**	**Air Contaminant Name (3)**	**Emission Rates**		**Monitoring and Testing Requirements**	**Recordkeeping Requirements**	**Reporting Requirements**
			lbs/hour	**TPY (4)**	**Spec. Cond.**	**Spec. Cond.**	**Spec. Cond.**
E-01-843	Heater 843-H1	NO_x	16.00	53.40	3, 5, 32, 34, 50, 52, 53, 66, 87	3, 5, 32, 34, 50, 52, 53, 64, 66, 87	3, 5, 32, 50, 53, 66
		VOC	1.44	5.42			
		SO_2	6.79	9.32			
		SO_2 (20)	6.79	4.38			
		CO	21.96	31.76			
		PM	1.99	7.50			
		PM_{10}	1.99	7.50			
		$PM_{2.5}$	1.99	7.50			
E-02-843	Heater 843-H2	NO_x	16.00	53.40	3, 5, 32, 34, 50, 52, 53, 66, 87	3, 5, 32, 34, 50, 52, 53, 64, 66, 87	3, 5, 32, 50, 53, 66
		VOC	1.44	5.42			
		SO_2	6.79	9.32			
		SO_2 (20)	6.79	4.38			
		CO	21.96	31.76			

Major NSR Summary Table

Permit Number 6825A, PSDTX49M1, N65					Issuance Date: November 16, 2018		
Emission Point No. (1)	**Source Name (2)**	**Air Contaminant Name (3)**	**Emission Rates**		**Monitoring and Testing Requirements**	**Recordkeeping Requirements**	**Reporting Requirements**
			lbs/hour	**TPY (4)**	**Spec. Cond.**	**Spec. Cond.**	**Spec. Cond.**
		PM	1.99	7.50			
		PM_{10}	1.99	7.50			
		$PM_{2.5}$	1.99	7.50			
E-03-843	Heater 843-H3	NO_x	16.00	53.40	3, 5, 32, 34, 50, 52, 53, 66, 87	3, 5,32, 34, 50, 52, 53, 64, 66, 87	3, 5, 32, 50, 53, 66
		VOC	1.44	5.42			
		SO_2	6.79	9.32			
		SO_2 (20)	6.79	4.38			
		CO	21.96	31.76			
		PM	1.99	7.50			
		PM_{10}	1.99	7.50			
		$PM_{2.5}$	1.99	7.50			

Major NSR Summary Table

Permit Number 6825A, PSDTX49M1, N65					Issuance Date: November 16, 2018		
Emission Point No. (1)	**Source Name (2)**	**Air Contaminant Name (3)**	**Emission Rates**		**Monitoring and Testing Requirements**	**Recordkeeping Requirements**	**Reporting Requirements**
			lbs/hour	**TPY (4)**	**Spec. Cond.**	**Spec. Cond.**	**Spec. Cond.**
E-01-246	Heater 246-H1	NO_x	2.20	7.51	3, 5, 34, 35, 66, 87	3, 5, 34, 35, 64, 66, 87	3, 5, 66
		VOC	0.34	1.06			
		SO_2	1.44	1.86			
		SO_2 (20)	1.44	0.88			
		CO	4.07	6.19			
		PM	0.47	1.47			
		PM_{10}	0.47	1.47			
		$PM_{2.5}$	0.47	1.47			
E-01-1241	Heater 1241-H1	NO_x	4.96	1.24	3, 5, 34, 50, 66, 87	3, 5, 34, 50, 64, 66, 87	3, 5, 50, 66
		VOC	0.33	0.08			
		SO_2	1.64	0.15			
		CO	4.86	0.64			
		PM	0.43	0.11			

Major NSR Summary Table

Permit Number 6825A, PSDTX49M1, N65					Issuance Date: November 16, 2018		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Spec. Cond.	Spec. Cond.	Spec. Cond.
E-02-1241	Heater 1241-H2	NO_x	4.96	1.24	3, 5, 34, 50, 66, 87	3, 5, 34, 50, 64, 66, 87	3, 5, 50, 66
		VOC	0.33	0.08			
		SO_2	1.64	0.15			
		CO	4.86	0.64			
		PM	0.43	0.11			

Major NSR Summary Table

Permit Number 6825A, PSDTX49M1, N65					Issuance Date: November 16, 2018		
Emission Point No. (1)	**Source Name (2)**	**Air Contaminant Name (3)**	**Emission Rates**		**Monitoring and Testing Requirements**	**Recordkeeping Requirements**	**Reporting Requirements**
			lbs/hour	**TPY (4)**	**Spec. Cond.**	**Spec. Cond.**	**Spec. Cond.**
E-01-241	Heater 241-B101AB	NO_x	7.92	19.51	3, 5, 32, 34, 50, 66, 87	3, 5, 34, 50, 64, 66, 87	3, 5, 50, 66
		VOC	0.53	2.34			
		SO_2	2.23	3.66			
		SO_2 (20)	2.23	2.93			
		CO	8.15	13.49			
		PM	0. 73	3.24			
		PM_{10}	0. 73	3.24			
		$PM_{2.5}$	0. 73	3.24			
E-01-242	Heater 242-B201AB	NO_x	6.62	17.45	3, 5, 32, 34, 35, 66, 87	3, 5, 34, 35, 64, 66, 87	3, 5, 66
		VOC	0.36	1.58			
		SO_2	1.87	3.11			
		SO_2 (20)	1.87	1.80			
		CO	4.04	11.91			

Major NSR Summary Table

Permit Number 6825A, PSDTX49M1, N65					Issuance Date: November 16, 2018		
Emission Point No. (1)	**Source Name (2)**	**Air Contaminant Name (3)**	**Emission Rates**		**Monitoring and Testing Requirements**	**Recordkeeping Requirements**	**Reporting Requirements**
			lbs/hour	**TPY (4)**	**Spec. Cond.**	**Spec. Cond.**	**Spec. Cond.**
		PM	0.50	2.00			
		PM_{10}	0.50	2.00			
		$PM_{2.5}$	0.50	2.00			
E-01-243	Heater 243	NO_x	7.10	19.43	3, 5, 32, 34, 50, 66, 87	3, 5, 32, 34, 50, 64, 66, 87	3, 5, 32, 50, 66
		VOC	0.48	1.87			
		SO_2	1.78	2.92			
		SO_2 (20)	1.78	2.32			
		CO	6.74	10.31			
		PM	0.66	2.58			
		PM_{10}	0.66	2.58			
		$PM_{2.5}$	0.66	2.58			
E-01-244	Heater 244 F-101/102	NO_x	7.92	34.70	3, 5, 34, 50, 66, 87	3, 5, 34, 50, 64, 66, 87	3, 5, 50, 66
		VOC	0.36	1.60			

Major NSR Summary Table

Permit Number 6825A, PSDTX49M1, N65					Issuance Date: November 16, 2018		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Spec. Cond.	Spec. Cond.	Spec. Cond.
		SO_2	1.90	3.11			
		SO_2 (20)	1.90	1.80			
		CO	5.13	11.91			
		PM	0.49	2.00			
		PM_{10}	0.49	2.00			
		$PM_{2.5}$	0.49	2.00			

Major NSR Summary Table

Permit Number 6825A, PSDTX49M1, N65					Issuance Date: November 16, 2018		
Emission Point No. (1)	**Source Name (2)**	**Air Contaminant Name (3)**	**Emission Rates**		**Monitoring and Testing Requirements**	**Recordkeeping Requirements**	**Reporting Requirements**
			lbs/hour	**TPY (4)**	**Spec. Cond.**	**Spec. Cond.**	**Spec. Cond.**
E-01-942	Heater 942-H1_2_3	NO_x	12.83	45.56	3, 5, 32, 34, 50, 52, 53, 66, 87	3, 5, 32, 34, 50, 52, 53, 64, 66, 87	3, 5, 32, 50, 53, 66
		VOC	1.15	4.55			
		SO_2	5.45	7.98			
		SO_2 (20)	5.45	3.68			
		CO	17.61	26.75			
		PM	1.60	6.29			
		PM_{10}	1.60	6.29			
		$PM_{2.5}$	1.60	6.29			
E-01-443	Heater 443	NO_x	14.20	42.83	3, 5, 32, 34, 50, 52, 53, 66, 87	3, 5, 32, 34, 50, 52, 53, 64, 66, 87	3, 5, 32, 50, 53, 66
		VOC	1.09	3.88			
		SO_2	3.34	5.49			
		SO_2 (20)	3.34	4.86			
		CO	16.67	21.44			

Major NSR Summary Table

Permit Number 6825A, PSDTX49M1, N65					Issuance Date: November 16, 2018		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Spec. Cond.	Spec. Cond.	Spec. Cond.
		PM	1.51	5.35			
		PM_{10}	1.51	5.35			
		$PM_{2.5}$	1.51	5.35			

Major NSR Summary Table

Permit Number 6825A, PSDTX49M1, N65					Issuance Date: November 16, 2018		
Emission Point No. (1)	**Source Name (2)**	**Air Contaminant Name (3)**	**Emission Rates**		**Monitoring and Testing Requirements**	**Recordkeeping Requirements**	**Reporting Requirements**
			lbs/hour	**TPY (4)**	**Spec. Cond.**	**Spec. Cond.**	**Spec. Cond.**
REFFUG Includes: F-1241, F-1242, F-1344, F-146, F-147, F-15BH, F-16BH, F-241, F-242, F-243, F-244, F-245, F-246, F-443, F-545, F-546, F-547, F-6341, F-7542, F-7841, F-7842, F-7848, F-843, F-844, F-8746, F-8747, F-942, FUAUCT, F-DOCKS, F-544, F-Fueling Station, F-163PH, F-41PH, F-FGMD, F-SRTF, F-Utilities, F-8741, F-543/4, F-NSTF, F-BH-19, F-7843, F-943-75K, F-844, F-547	Refinery Fugitives VOC Subcap (4)	VOC	259.49	1132.81	3, 5, 36, 55, 56, 57, 59, 66, 87	3, 5, 36, 55, 56, 57, 64, 66, 87	3, 5, 36, 57, 66
		H_2S	5.60	24.54			
		NH_3	1.47	5.06			
		HF	0.36	1.75			
100, 103, 106,	Refinery Tank	VOC	218.70	153.30	3, 4, 5, 9, 10, 11, 26, 66,	3, 4, 5, 9, 10, 26, 64, 66,	3, 4, 5, 26, 66

Major NSR Summary Table

Permit Number 6825A, PSDTX49M1, N65					Issuance Date: November 16, 2018		
Emission Point No. (1)	**Source Name (2)**	**Air Contaminant Name (3)**	**Emission Rates**		**Monitoring and Testing Requirements**	**Recordkeeping Requirements**	**Reporting Requirements**
			lbs/hour	**TPY (4)**	**Spec. Cond.**	**Spec. Cond.**	**Spec. Cond.**
107, 110, 111, 133, 151, 1848, 1849, 2101, 2105, 2106, 2110, 2111, 2112, 2113, 2117, 2132, 2133, 2137, 2145, 2147, 2148, 2159, 2160, 2161, 2162, 2163, 2164, 2182, 2183, 2588, 2590, 283, 284, 285, 31, 5, 77, 78, 82, 88, 889, 896, 925, 926, 99, T-108, T-109, T-546-1, T-546-2, T-7842-1, T-7842-2	Subcap				87	87	
E-05-FLARE, F-13-FLARE, F-15-FLARE, F-18-FLARE, F-19-FLARE, F-20-FLARE, F-22-FLARE, E-	Flares Subcap	NO_x	43.93	48.03	3, 5, 6, 62, 66, 87, 89	3, 5, 6, 64, 66, 87, 89	3, 5, 66
		VOC	65.74	85.10			
		SO_2	24.87	13.57			

Major NSR Summary Table

Permit Number 6825A, PSDTX49M1, N65					Issuance Date: November 16, 2018		
Emission Point No. (1)	**Source Name (2)**	**Air Contaminant Name (3)**	**Emission Rates**		**Monitoring and Testing Requirements**	**Recordkeeping Requirements**	**Reporting Requirements**
			lbs/hour	**TPY (4)**	**Spec. Cond.**	**Spec. Cond.**	**Spec. Cond.**
23-FLARE, F-103-FLARE		CO	302.8	309.30			
E-05-FLARE, F-13-FLARE, F-15-FLARE, F-18-FLARE, F-19-FLARE, F-20-FLARE, F-22-FLARE, E-23-FLARE, F-103-FLARE	Flares Subcap (14)	NO_x	43.93	38.67	3, 5, 6, 62, 66, 87, 89	3, 5, 6, 64, 66, 87, 89	3, 5, 66
		VOC	65.74	57.86			
		SO_2	24.87	8.11			
		CO	302.8	266.50			
		H_2S	0.26	0.09			
F-DOCK	Uncontrolled Marine Loading F-03-DOCK, F-02-DOCK, F-05-DOCK, F-06-DOCK, F-08-DOCK, F-07-DOCK, F-11-DOCK, F-12-DOCK, F-14-DOCK, F-15-DOCK	VOC	97.92	63.93	11, 13, 14, 66, 87	13, 14, 64, 66, 87	66

Major NSR Summary Table

Permit Number 6825A, PSDTX49M1, N65					Issuance Date: November 16, 2018		
Emission Point No. (1)	**Source Name (2)**	**Air Contaminant Name (3)**	**Emission Rates**		**Monitoring and Testing Requirements**	**Recordkeeping Requirements**	**Reporting Requirements**
			lbs/hour	**TPY (4)**	**Spec. Cond.**	**Spec. Cond.**	**Spec. Cond.**
E-01-SCOT, E-02-SCOT, E-03-SCOT, E-04-SCOT	SRUs Subcap	NO_x	49.68	118.40	3, 22, 24, 27, 28, 30, 31, 34, 50, 52, 53, 62, 66, 87	3, 22, 24, 27, 29, 30, 34, 50, 52, 53, 64, 66, 87	3, 27, 28, 50, 53, 66
		VOC	64.24	151.90			
		SO_2	345.83	1056.82			
		CO	192.20	896.29			
		PM	24.58	58.60			
		PM_{10}	24.58	58.60			
		$PM_{2.5}$	24.58	58.60			
		H_2S	3.67	11.23			
E-01-SCOT	SRU 543	SO_2	57.90	--	3, 22, 24, 27, 28, 30, 31, 34, 50, 52, 53, 62, 66, 87	3, 22, 24, 27, 29, 30, 34, 50, 52, 53, 64, 66, 87	3, 27, 28, 50, 53, 66, 67
		H_2S	0.62	--			
E-02-SCOT	SRU 544	SO_2	82.77	--	3, 22, 24, 27, 28, 30, 31, 34, 50, 52, 53, 62, 66, 87	3, 22, 24, 27, 29, 30, 34, 50, 52, 53, 64, 66, 87	3, 27, 28, 50, 53, 66, 67
		H2S	0.88	--			

Major NSR Summary Table

Permit Number 6825A, PSDTX49M1, N65					Issuance Date: November 16, 2018		
Emission Point No. (1)	**Source Name (2)**	**Air Contaminant Name (3)**	**Emission Rates**		**Monitoring and Testing Requirements**	**Recordkeeping Requirements**	**Reporting Requirements**
			lbs/hour	**TPY (4)**	**Spec. Cond.**	**Spec. Cond.**	**Spec. Cond.**
E-03-SCOT	SRU 545	SO_2	137.89	--	3, 22, 24, 27, 28, 30, 31, 34, 50, 52, 53, 62, 66, 87	3, 22, 24, 27, 29, 30, 34, 50, 52, 53, 64, 66, 87	3, 27, 28, 50, 53, 66, 67
		H_2S	1.47	--			
E-04-SCOT	SRU 546	SO_2	137.89	--	3, 22, 24, 27, 28, 30, 31, 34, 50, 52, 53, 62, 66, 87	3, 22, 24, 27, 29, 30, 34, 50, 52, 53, 64, 66, 87	3, 27, 28, 50, 53, 66, 67
		H_2S	1.47	--			
E-02-SRK	SRU 543 and 544 sulfur loading	H_2S	0.36	0.28			
E-06-843	Two Tank Heaters for Charge Tanks	NO_x	1.18	5.15	3, 5, 34, 66, 87	3, 5, 34, 64, 66, 87	3, 5, 66
		VOC	0.06	0.28			
		SO_2	0.31	0.51			
		CO	1.02	4.47			
		PM	0.09	0.39			
E-01-943	HCU - Reactor 1 and Reactor 2 Furnaces	NO_x	7.81	28.51	3, 5, 32, 34, 50, 52, 53, 66, 87	3, 5, 32, 34, 50, 52, 53, 64, 66, 87	3, 5, 32, 50, 53, 66
		VOC (19)	0.60	2.20			

Major NSR Summary Table

Permit Number 6825A, PSDTX49M1, N65					Issuance Date: November 16, 2018		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Spec. Cond.	Spec. Cond.	Spec. Cond.
		SO_2	8.20	11.23			
		SO_2 (20)	8.20	5.87			
		CO	14.93	27.27			
		PM	1.66	6.07			
		PM_{10}	1.66	6.07			
		$PM_{2.5}$	1.66	6.07			

Major NSR Summary Table

Permit Number 6825A, PSDTX49M1, N65					Issuance Date: November 16, 2018		
Emission Point No. (1)	**Source Name (2)**	**Air Contaminant Name (3)**	**Emission Rates**		**Monitoring and Testing Requirements**	**Recordkeeping Requirements**	**Reporting Requirements**
			lbs/hour	**TPY (4)**	**Spec. Cond.**	**Spec. Cond.**	**Spec. Cond.**
E-02-943	HCU - Fractionator Feed Furnace	NO_x	5.22	22.86	3, 5, 32, 34, 50, 52, 53, 54, 66, 87	3, 5, 32, 34, 50, 52, 53, 54, 64, 66, 87	3, 5, 32, 50, 53, 66
		NO_x (Start-up)	52.20	(22)			
		VOC (19)	1.88	8.22			
		SO_2	13.31	17.51			
		SO_2 (20)	13.31	10.79			
		CO	23.27	50.97			
		CO (Start-up)	116.37	(22)			
		PM	2.90	11.81			
		PM_{10}	2.90	11.81			
		$PM_{2.5}$	2.90	11.81			
		Ammonia	1.41	6.19			
E-26-FLARE	HCU 943 Flare	NO_x	0.31	1.38	3, 5, 6, 62, 66, 87, 89	3, 5, 6, 64, 66, 87, 89	3, 5, 66
		SO_2	0.01	0.03			

Major NSR Summary Table

Permit Number 6825A, PSDTX49M1, N65					Issuance Date: November 16, 2018		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Spec. Cond.	Spec. Cond.	Spec. Cond.
		CO	2.27	9.94			

Major NSR Summary Table

Permit Number 6825A, PSDTX49M1, N65					Issuance Date: November 16, 2018		
Emission Point No. (1)	**Source Name (2)**	**Air Contaminant Name (3)**	**Emission Rates**		**Monitoring and Testing Requirements**	**Recordkeeping Requirements**	**Reporting Requirements**
			lbs/hour	**TPY (4)**	**Spec. Cond.**	**Spec. Cond.**	**Spec. Cond.**
E-01-WGS	FCCU Wet Gas Scrubber	NO_x	327.70	271.93	3, 18, 19, 50, 52, 53, 62, 66, 87	3, 19, 50, 52, 53, 64, 66, 87	3, 50, 53, 66
		VOC	15.70	68.80			
		SO_2	114.10	256.08			
		CO	498.80	896.29			
		PM	63.50	278.13			
		NH_3	3.19	12.37			
		HCN	89.80	347.95			
		H_2SO_4	18.26	80.00			
E-MC-24-25	DOCK-MC (24)	NO_x	49.68	20.83	7, 11, 13, 15, 16, 17, 51, 62, 66, 87, 89	7, 13, 15, 16, 17, 51, 64, 66, 87, 89	7, 51, 66
		VOC	33.19	20.08			
		CO	99.18	41.58			
		SO_2	0.19	0.07			
		PM	2.68	1.12			

Major NSR Summary Table

Permit Number 6825A, PSDTX49M1, N65					Issuance Date: November 16, 2018		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Spec. Cond.	Spec. Cond.	Spec. Cond.
		PM_{10}	2.68	1.12			
		$PM_{2.5}$	2.68	1.12			
F-101CT	Cool Twr 101	VOC	1.30	5.70	5, 20, 66, 87	5, 20, 64, 66, 87	5, 66
F-136ACT	Cool Twr 136A	VOC	2.73	11.96	5, 20, 66, 87	5, 20, 64, 66, 87	5, 66
F-136BCT	Cool Twr 136B	VOC	2.77	11.96	5, 20, 66, 87	5, 20, 64, 66, 87	5, 66
F-233PS	Cool Twr 233	VOC	0.53	1.24	5. 20, 66, 87	5, 20, 64, 66, 87	5, 66
F-314PS	Cool Twr 314	VOC	0.01	0.01	5, 20, 66, 87	5, 20, 64, 66, 87	5, 66
F-316PS	Cool Twr 316	VOC	0.01	0.01	5, 20, 66, 87	5, 20, 64, 66, 87	5, 66
F-354CT	Cool Twr 354	VOC	0.25	1.10	5, 20, 66, 87	5, 20, 64, 66, 87	5, 66
F-360PS	Cool Twr 360	VOC	0.92	4.05	5, 20, 66, 87	5, 20, 64, 66, 87	5, 66
F-363CT	Cool Twr 363	VOC	0.42	0.89	5, 20, 66, 87	5, 20, 64, 66, 87	5, 66
F-366CT	Cool Twr 366	VOC	2.10	2.45	5, 20, 66, 87	5, 20, 64, 66, 87	5, 66
CT-100	Cool Twr 100	VOC	1.05	4.60	5, 20, 66, 87	5, 20, 64, 66, 87	5, 66

Major NSR Summary Table

Permit Number 6825A, PSDTX49M1, N65					Issuance Date: November 16, 2018		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Spec. Cond.	Spec. Cond.	Spec. Cond.
E-432-CT	Cool Twr 432	VOC	0.84	3.68	5, 20, 66, 87	5, 20, 64, 66, 87	5, 66
		PM	0.01	0.02			
		PM_{10}	0.01	0.02			
		$PM_{2.5}$	0.01	0.02			
E-433-CT	Cool Twr 433	VOC	1.26	0.69	5, 20, 21, 66, 87	5, 20, 21, 64, 66, 87	5, 21, 66
		VOC (20)	1.89	8.28			
		PM (20)	0.56	1.97			
		PM_{10} (20)	0.56	1.95			
		$PM_{2.5}$ (20)	0.13	0.44			
CT-244	Cool Twr 244	VOC	1.18	5.15	5, 20, 21, 66, 87	5, 20, 21, 64, 66, 87	5, 21, 66
		VOC (20)	1.60	6.99			
		PM (20)	0.48	6.99			
		PM_{10} (20)	0.47	1.64			

Major NSR Summary Table

Permit Number 6825A, PSDTX49M1, N65					Issuance Date: November 16, 2018		
Emission Point No. (1)	**Source Name (2)**	**Air Contaminant Name (3)**	**Emission Rates**		**Monitoring and Testing Requirements**	**Recordkeeping Requirements**	**Reporting Requirements**
			lbs/hour	**TPY (4)**	**Spec. Cond.**	**Spec. Cond.**	**Spec. Cond.**
		$PM_{2.5}$ (20)	0.11	0.37			
F-446CT	Cooling Tower 446	PM	0.03	0.11	5, 20, 21, 66, 87	5, 20, 21, 64, 66, 87	5, 21, 66
		PM_{10}	0.03	0.11			
		$PM_{2.5}$	0.03	0.11			
		VOC (19)(20)	1.99	8.72			
		PM (20)	0.59	8.72			
		PM_{10} (20)	0.59	2.05			
		$PM_{2.5}$ (20)	0.13	0.47			
F-843PM	Unit 843 coke storage and loading (FINS F-843-1 to F-843-17)	PM	2.41	10.56	5, 44, 46, 47, 48, 49, 66, 87	5, 41, 44, 46,47, 64, 66, 87	5, 66
		$PM_{2.5}$	0.06	0.26			
		PM (20)	5.17	8.71			
		PM_{10} (20)	2.48	4.26			
		$PM_{2.5}$ (20)	0.37	0.63			

Emission point identification - either specific equipment designation or emission point number (EPN) from a plot plan per Attachment 1.

(2) Specific point source names. For fugitive sources use area name or fugitive source name.

(3) VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1
NO_x - total oxides of nitrogen
SO_2 - sulfur dioxide
CH_4 - methane
CO - carbon monoxide
CO_2 - carbon dioxide
CO_2e - carbon dioxide equivalents based on the following Global Warming Potentials (1/2015):
CO_2 (1), N_2O (298), CH_4(25), SF_6 (22,800), HFC (various), PFC (various).
N_2O - nitrous oxide
PM - particulate matter, suspended in the atmosphere, including PM_{10} and $PM_{2.5}$.
PM_{10} - particulate matter equal to or less than 10 microns in diameter.
$PM_{2.5}$ - particulate matter equal to or less than 2.5 microns in diameter
H_2S - hydrogen sulfide
HCl - hydrogen chloride
HF - hydrogen fluoride
MTBE - methyl-tertiary-butyl ether
N_2O - nitrous oxide
NH_3 - ammonia
HCN - hydrogen cyanide
H_2SO_4 - sulfuric acid

(4) Emission rate is an estimate and compliance is demonstrated by meeting the requirements of the applicable special conditions and permit application representations.

(5) Rates effective after facilities associated with COEX II Project are operating.

(6) Caps effective after sources associated with COEX II Project and EPNs E-01-19BH, E 02 19BH, and E-03-19BH are operating. Boilerhouse 15 low NO_x burner project and shutdown of Boilerhouse 16 combustion units must be complete.

(7) Allowable emission rates prior to the Boilerhouse 15 low NO_x burner project (Pre-mod).

(8) Post-mod Phase I: Allowable emission rates after the Boilerhouse 15 low NO_x burner project authorized by Standard Permit 91911. The turbine GTG-1 shall be shutdown as part of this project.

(9) These facilities were subject to nonattainment review for VOC for Permit N65. The MSS emissions associated with the COEX II facilities authorized in Permit Number 80812 must also be added to the routine emissions from the COEX II facilities to determine compliance with this annual emission cap.

(10) The Boilerhouse 16 units must be shutdown and the Boilerhouse 15 low NO_x burner project completed prior to the end of the 180 day shakedown period for Boilerhouse 19 Boilers 1, 2, and 3 {authorized by Permit 103765).

(11) These emission caps have been carried forward from the flexible permit. With the exception of VOC emissions from COEXII facilities, these caps apply to the sum total of all emissions of that pollutant from the facilities listed on Attachment I. In addition, the maintenance, startup, and shutdown (MSS) emissions authorized in Permit Number 80812 must also be added to the routine emissions from the facilities in Attachment I to determine compliance with these emission caps unless the cap is designated with a footnote (12). The emission caps that are not designated with a footnote (12) are those that are more limiting than the sum of the individual emission rate limits for those facilities. VOC MSS emissions from COEX II facilities do not need to be included when showing compliance with the annual VOC cap.

(12) These emission caps are the sum of the individual and subcap emission rates for the pollutant and are shown for information only.

(13) Post-mod Phase II: These allowable emission rates shall apply in lieu of those designated with footnote (8) (aka Post-mod Phase I) if the permit holder samples these facilities for $PM_{2.5}$ per Special Condition 40 after completing the Boilerhouse 15 low NO_x burner project and the results show $PM_{2.5}$ emissions are less than 73 percent of the maximum hourly total PM emission rate limit.

(14) Caps effective after start of operation of entire flare gas recovery system.

(15) Installation of low NO_x burners in Boilerhouse 15 boilers authorized by Standard Permit 91911.

(16) Installation of low NO_x burners in Boilerhouse 16 boilers authorized by Standard Permit 94365.

(17) Tank authorized by PBR Registration 84905.
(18) This emission cap applies to the sum of VOC emissions from all facilities listed in Attachment 1 and MSS activities authorized in this permit and from all facilities and MSS activities authorized in Permit 80812.
(19) Emissions are a subcap of COEXII VOC Cap.
(20) Emissions shall supersede all existing authorized limits of that pollutant upon completion of the facility's modification as represented in the Coker Project, PI-1 dated February 27, 2018. The modifications shall be completed preceding the initial startup of the Coker Unit's DCU 844. **(11/18)**
(21) Limits apply January 1, 2019.
(22) Annual emissions are included as part of annual emissions authorized for normal facility operation.
(23) Hourly emissions from Flare EPNs E-23-Flare and E-26-Flare are a subcap of the emissions authorized for the flare in MSS permit 80812.
(24) Includes emissions from marine vapor combustors E-MC-24 and E-MC-25

* Emission rates are based on operating 8,760 hrs/year.

** Compliance with annual emission limits is based on a rolling 12-month period

Major NSR Summary Table

Permit Number GHGPSDTX167					Issuance Date: November 16, 2018		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Spec. Cond.	Spec. Cond.	Spec. Cond.
E-01-245	Heater 245	CO_2 (5)	--	18,687.00	74	74	74
		N_2O (5)	--	0.03			
		CH_4 (5)	--	0.32			
		CO_2e	--	18,704.00			
T-112	112	CH_4 (5)	-	0.03	82	82	
		CO_2e	-	0.87			
T-113	113	CH_4 (5)	-	0.03	82	82	
		CO_2e	-	0.87			
T-114	114	CH4 (5)	-	0.03	82	82	
		CO_2e	-	0.87			
E-01-844	DCU 844 Coker Furnace #1	CO_2 (5)	--	119,242.00	74	74	74
		N_2O (5)	--	0.20			
		CH_4 (5)	--	2.02			

Major NSR Summary Table

Permit Number GHGPSDTX167					Issuance Date: November 16, 2018		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Spec. Cond.	Spec. Cond.	Spec. Cond.
		CO_2e	--	119,353.00			
E-02-844	DCU 844 Coker Furnace #2	CO_2 (5)	--	119,242.00	74	74	74
		N_2O (5)	--	0.20			
		CH_4 (5)	--	2.02			
		CO_2e	--	119,353.00			
E-05-SCOT	SRU 547	CO_2 (5)	--	90,029.00	74, 79	74, 79	74
		N_2O (5)	--	0.08			
		CH_4 (5)	--	0.80			
		CO_2e	--	90,072.00			
CSV844	Coker Unit 844 Steam Vent	CH4 (5)	--	161.38	74, 78, 80	74, 78, 80	74
		CO_2e	--	4,034.00			

Major NSR Summary Table

Permit Number GHGPSDTX167					Issuance Date: November 16, 2018		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Spec. Cond.	Spec. Cond.	Spec. Cond.
CSV843	Coker Unit 843 Steam Vent	CH_4 (5)	--	279.00	74, 78, 80	74, 78, 80	74
		CO_2e	--	6,975.00			
MSS	Coker 844 Project MSS	CO_2 (5)	--	1,101.00	74, 76, 83	74, 76, 83	74
		N_2O (5)	--	<0.01			
		CH_4 (5)	--	0.02			
		CO_2e	--	1,102.00			
E-01-146	Heater 146-H101	CO_2 (5)	--	290,556	74	74	74
		N_2O (5)	--	0.49			
		CH_4 (5)	--	4.92			
		CO_2e	--	290,826.00			

Major NSR Summary Table

Permit Number GHGPSDTX167					Issuance Date: November 16, 2018		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Spec. Cond.	Spec. Cond.	Spec. Cond.
E-02-146	Heater 146-H102AB	CO_2 (5)	--	148,127.00	74	74	74
		N_2O (5)	--	0.25			
		CH_4 (5)	--	2.51			
		CO_2e	--	148.264.00			
E-01-147	Heater 147-F-1100	CO_2 (5)	--	225,609.00	74	74	74
		N_2O (5)	--	0.38			
		CH_4 (5)	--	3.82			
		CO_2e	--	225,818.00			
E-02-147	Heater 147-F-1200	CO_2 (5)	--	97,764.00	74	74	74
		N_2O (5)	--	0.17			
		CH_4 (5)	--	1.66			
		CO_2e (5)	--	97,855.00			

Major NSR Summary Table

Permit Number GHGPSDTX167					Issuance Date: November 16, 2018		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Spec. Cond.	Spec. Cond.	Spec. Cond.
E-01-1344	Heater 1344-H1	CO_2 (5)	--	356,986.00	74	74	74
		N_2O (5)	--	0.61			
		CH_4 (5)	--	6.05			
		CO_2e	--	357,317.00			
E-02-1344	Heater 1344-H33	CO_2 (5)	--	29,568.00	74	74	74
		N_2O (5)	--	0.05			
		CH_4 (5)	--	0.50			
		CO_2e	--	29,596.00			

Major NSR Summary Table

Permit Number GHGPSDTX167					Issuance Date: November 16, 2018		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Spec. Cond.	Spec. Cond.	Spec. Cond.
E-03-1344	Heater 1344-H2_3_32	CO_2 (5)	--	58,111.00	74	74	74
		N_2O (5)	--	0.10			
		CH_4 (5)	--	0.98			
		CO_2e	--	58,165.00			
E-01-843	Heater 843-H1	CO_2 (5)	--	130,921.00	74	74	74
		N_2O (5)	--	0.22			
		CH_4 (5)	--	2.22			
		CO_2e	--	131,043.00			
E-02-843	Heater 843-H2	CO_2 (5)	--	130,921.00	74	74	74
		N_2O (5)	--	0.22			
		CH_4 (5)	--	2.22			
		CO_2e	--	131,043.00			
E-03-843	Heater 843-H3	CO_2 (5)	--	130,921.00	74	74	74

Major NSR Summary Table

Permit Number GHGPSDTX167					Issuance Date: November 16, 2018		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Spec. Cond.	Spec. Cond.	Spec. Cond.
		N_2O (5)	--	0.22			
		CH_4 (5)	--	2.22			
		CO_2e	--	131,043.00			
E-01-246	Heater 246-H1	CO_2 (5)	--	25,637.00	74	74	74
		N_2O (5)	--	0.04			
		CH_4 (5)	--	0.43			
		CO_2e	--	25,661.00			
E-01-241	Heater 241-B101AB	CO_2 (5)	CO2 (5)	CO2 (5)	74	74	74
		N_2O (5)	N2O (5)	N2O (5)			
		CH_4 (5)	CH4 (5)	CH4 (5)			
		CO_2e	CO2e	CO2e			
E-01-242	Heater 242-B201AB	CO_2 (5)	--	34,924.00	74	74	74
		N_2O (5)	--	0.06			

Major NSR Summary Table

Permit Number GHGPSDTX167					Issuance Date: November 16, 2018		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Spec. Cond.	Spec. Cond.	Spec. Cond.
		CH_4 (5)	--	0.59			
		CO_2e	--	34,956.00			
E-01-243	Heater 243	CO_2 (5)	CO2 (5)	CO2 (5)	74	74	74
		N_2O (5)	N2O (5)	N2O (5)			
		CH_4 (5)	CH4 (5)	CH4 (5)			
		CO_2e	CO2e	CO2e			
E-01-244	Heater 244 F-101/102	CO_2 (5)	--	34,924.00	74	74	74
		N_2O (5)	--	0.06			
		CH_4 (5)	--	0.59			
		CO_2e	--	34,956.00			

Major NSR Summary Table

Permit Number GHGPSDTX167					Issuance Date: November 16, 2018		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Spec. Cond.	Spec. Cond.	Spec. Cond.
E-01-942	Heater 942-H1_2_3	CO_2 (5)	--	109,785.00	74	74	74
		N_2O (5)	--	0.19			
		CH_4 (5)	--	1.86			
		CO_2e	--	109,887.00			
E-01-443	Heater 443	CO_2 (5)	--	93,377.00	74	74	74
		N_2O (5)	--	0.16			
		CH_4 (5)	--	1.58			
		CO_2e	--	93,464.00			

Major NSR Summary Table

Permit Number GHGPSDTX167					Issuance Date: November 16, 2018		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Spec. Cond.	Spec. Cond.	Spec. Cond.
REFFUG Includes: F-1241, F-1242, F-1344, F-146, F-147, F-15BH, F-16BH, F-241, F-242, F-243, F-244, F-245, F-246, F-443, F-545, F-546, F-547, F-6341, F-7542, F-7841, F-7842, F-7848, F-843, F-844, F-8746, F-8747, F-942, FUAUCT, F-DOCKS, F-544, F-Fueling Station, F-163PH, F-41PH, F-FGMD, F-SRTF, F-Utilities, F-8741, F-543/4, F-NSTF, F-BH-19, F-7843, F-943-75K, F-844, F-547,	Refinery Fugitives VOC Subcap (4)	CH_4 (5)	-	113.03	75, 81	75, 81	
		CO_2e	-	2826.00			
E-01-943	HCU - Reactor	CO_2 (5)	--	105,968.00			

Major NSR Summary Table

Permit Number GHGPSDTX167					Issuance Date: November 16, 2018		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Spec. Cond.	Spec. Cond.	Spec. Cond.
	1 and Reactor 2 Furnaces	N_2O (5)	--	0.18	74	74	74
		CH_4 (5)	--	1.80			
		CO_2e	--	106,066.00			
E-02-943	HCU - Fractionator Feed Furnace	CO_2 (5)	--	198,262.00	74	74	74
		N_2O (5)	--	0.34			
		CH_4 (5)	--	3.36			
		CO_2e	--	198,446.00			
E-MC-24-25	DOCK-MC	CO_2 (5)	--	184450.00	77	77	
		N_2O (5)	--	0.35			
		CH_4 (5)	--	3.48			
		CO_2e	--	184,640.00			

(1) Emission point identification - either specific equipment designation or emission point number from plot plan.
(2) Specific point source name. For fugitive sources, use area name or fugitive source name.
(3) CO_2 - carbon dioxide
N_2O - nitrous oxide
CH_4 - methane
CO_2e - carbon dioxide equivalents based on the following Global Warming Potentials (GWP) found in Table A-1 of Subpart A 40 CFR Part 98 (78 FR 71904) for each pollutant: CO_2 (1), N_2O (298), CH_4(25)
(4) Compliance with annual emission limits (tons per year) is based on a 12-month rolling period. These rates include emissions from maintenance, startup, and shutdown.
(5) Emission rate is given for informational purposes only and does not constitute enforceable limit.

Texas Commission on Environmental Quality
Air Quality Permit

A Permit Is Hereby Issued To
The Premcor Refining Group Inc.
Authorizing the Construction and Operation of
Valero Port Arthur Refinery
Located at **Port Arthur, Jefferson County, Texas**
Latitude 29° 52′ 6″ Longitude−93° 58′ 6″

Permit: 6825A, PSDTX49M1, GHGPSDTX167 and N65
Revision Date: November 16, 2018
Expiration Date: March 30, 2019

For the Commission

1. **Facilities** covered by this permit shall be constructed and operated as specified in the application for the permit. All representations regarding construction plans and operation procedures contained in the permit application shall be conditions upon which the permit is issued. Variations from these representations shall be unlawful unless the permit holder first makes application to the Texas Commission on Environmental Quality (commission) Executive Director to amend this permit in that regard and such amendment is approved. [Title 30 Texas Administrative Code (TAC) Section 116.116 (30 TAC § 116.116)] [1]
2. **Voiding of Permit**. A permit or permit amendment is automatically void if the holder fails to begin construction within 18 months of the date of issuance, discontinues construction for more than 18 months prior to completion, or fails to complete construction within a reasonable time. Upon request, the executive director may grant an 18-month extension. Before the extension is granted the permit may be subject to revision based on best available control technology, lowest achievable emission rate, and netting or offsets as applicable. One additional extension of up to 18 months may be granted if the permit holder demonstrates that emissions from the facility will comply with all rules and regulations of the commission, the intent of the Texas Clean Air Act (TCAA), including protection of the public's health and physical property; and (b)(1)the permit holder is a party to litigation not of the permit holder's initiation regarding the issuance of the permit; or (b)(2) the permit holder has spent, or committed to spend, at least 10 percent of the estimated total cost of the project up to a maximum of $5 million. A permit holder granted an extension under subsection (b)(1) of this section may receive one subsequent extension if the permit holder meets the conditions of subsection (b)(2) of this section. [30 TAC § 116.120]
3. **Construction Progress**. Start of construction, construction interruptions exceeding 45 days, and completion of construction shall be reported to the appropriate regional office of the commission not later than 15 working days after occurrence of the event. [30 TAC § 116.115(b)(2)(A)]
4. **Start-up Notification**. The appropriate air program regional office shall be notified prior to the commencement of operations of the facilities authorized by the permit in such a manner that a representative of the commission may be present. The permit holder shall provide a separate notification for the commencement of operations for each unit of phased construction, which may involve a series of units commencing operations at different times. Prior to operation of the facilities authorized by the permit, the permit holder shall identify the source or sources of allowances to be utilized for compliance with Chapter 101, Subchapter H, Division 3 of this title (relating to Mass Emissions Cap and Trade Program). [30 TAC § 116.115(b)(2)(B)]
5. **Sampling Requirements**. If sampling is required, the permit holder shall contact the commission's Office of Compliance and Enforcement prior to sampling to obtain the proper data forms and procedures. All sampling and testing procedures must be approved by the executive director and coordinated with the regional representatives of the commission. The permit holder is also responsible for providing sampling facilities and conducting the sampling operations or contracting with an independent sampling consultant. [30 TAC § 116.115(b)(2)(C)]
6. **Equivalency of Methods.** The permit holder must demonstrate or otherwise justify the equivalency of emission control methods, sampling or other emission testing methods, and monitoring methods proposed as alternatives to methods indicated in the conditions of the permit. Alternative methods shall be applied for in writing and must be reviewed and approved by the executive director prior to their use in fulfilling any requirements of the permit. [30 TAC § 116.115(b)(2)(D)]
7. **Recordkeeping.** The permit holder shall maintain a copy of the permit along with records containing the information and data sufficient to demonstrate compliance with the permit, including production records and

operating hours; keep all required records in a file at the plant site. If, however, the facility normally operates unattended, records shall be maintained at the nearest staffed location within Texas specified in the application; make the records available at the request of personnel from the commission or any air pollution control program having jurisdiction in a timely manner; comply with any additional recordkeeping requirements specified in special conditions in the permit; and retain information in the file for at least two years following the date that the information or data is obtained. [30 TAC § 116.115(b)(2)(E)]

8. **Maximum Allowable Emission Rates**. The total emissions of air contaminants from any of the sources of emissions must not exceed the values stated on the table attached to the permit entitled "Emission Sources--Maximum Allowable Emission Rates." [30 TAC § 116.115(b)(2)(F)] [1]
9. **Maintenance of Emission Control**. The permitted facilities shall not be operated unless all air pollution emission capture and abatement equipment is maintained in good working order and operating properly during normal facility operations. The permit holder shall provide notification in accordance with 30 TAC §101.201, 101.211, and 101.221 of this title (relating to Emissions Event Reporting and Recordkeeping Requirements; Scheduled Maintenance, Startup, and Shutdown Reporting and Recordkeeping Requirements; and Operational Requirements). [30 TAC§ 116.115(b)(2)(G)]
10. **Compliance with Rules**. Acceptance of a permit by an applicant constitutes an acknowledgment and agreement that the permit holder will comply with all rules and orders of the commission issued in conformity with the TCAA and the conditions precedent to the granting of the permit. If more than one state or federal rule or regulation or permit condition is applicable, the most stringent limit or condition shall govern and be the standard by which compliance shall be demonstrated. Acceptance includes consent to the entrance of commission employees and agents into the permitted premises at reasonable times to investigate conditions relating to the emission or concentration of air contaminants, including compliance with the permit. [30 TAC § 116.115(b)(2)(H)]
11. **This** permit may not be transferred, assigned, or conveyed by the holder except as provided by rule. [30 TAC § 116.110(e)]
12. **There** may be additional special conditions attached to a permit upon issuance or modification of the permit. Such conditions in a permit may be more restrictive than the requirements of Title 30 of the Texas Administrative Code. [30 TAC § 116.115(c)]
13. **Emissions** from this facility must not cause or contribute to "air pollution" as defined in Texas Health and Safety Code (THSC) §382.003(3) or violate THSC § 382.085. If the executive director determines that such a condition or violation occurs, the holder shall implement additional abatement measures as necessary to control or prevent the condition or violation.
14. **The** permit holder shall comply with all the requirements of this permit. Emissions that exceed the limits of this permit are not authorized and are violations of this permit. [1]

[1] Please be advised that the requirements of this provision of the general conditions may not be applicable to greenhouse gas emissions.

SPECIAL CONDITIONS

Permit Numbers 6825A, PSDTX49M1, N65, and GHGPSDTX167

Emission Caps and Individual Emission Limitations

1. This permit covers only those sources of emissions listed in the attached table entitled “Emission Sources - Maximum Allowable Emission Rates” (MAERT), and tho se sources are limited to the emission limits and other conditions specified in this permit.

   Planned startup and shutdown emissions due to the activities from facilities and emission points identified in Special Conditions 84-86 are authorized provided the facility and emissions are compliant with the respective MAERT and Special Conditions 84-90 of this permit. (**09/18**)

2. Non-fugitive emissions from relief valves, safety valves, or rupture discs of gases containing volatile organic compounds (VOC) at a concentration of greater than 1 percent are not authorized by this permit unless authorized on the MAERT. Any releases directly to atmosphere from relief valves, safety valves, or rupture discs of gases containing VOC at a concentration greater than 1 weight percent are not consistent with good practice for minimizing emissions with the exception of those listed in Attachment 2 to this permit. **(1/13)**

Federal Applicability

3. These facilities shall comply with all applicable requirements of the U.S. Environmental Protection Agency (EPA) regulations on Standards of Performance for New Stationary Sources (NSPS) promulgated for the following:

   A. Petroleum Refineries in Title 40 Code of Federal Regulations Part 60 (40 CFR Part 60), Subparts A, J and Ja. (**04/16)**

      (1) All heaters and boilers, except those subject to Subpart Ja (E-01-943, E-02-943, and E-01-243), listed in Special Condition 32.D and the following heaters: E-01-1241, E-02-1241, E-01-245, E-01-246, E-01-244, and E-06-843 are subject to the requirements of 40 CFR Part 60, Subpart J

      (2) Heaters E-01-943, E-02-943, E-01-243, E-01-844, E-02-146, and E-02-844 are subject to the requirements of 40 CFR Part 60, Subpart Ja (**09/18**)

      (3) Sulfur Recovery Units (SRUs) 543, 544, 545, 546, and 547 are subject to the requirements of 40 CFR Part 60, Subpart Ja (**09/18**)

      (4) The Fluidized Catalytic Cracking Unit (Emission Point No. [EPN] E-01-WGS) is subject to the requirements of 40 CFR Part 60, Subpart J

      (5) Flares F-13-FLARE, F-15-FLARE, F-18-FLARE, F-19-FLARE, F-20-FLARE, F-22-FLARE, E-23-FLARE, F-103-FLARE, and E-26-FLARE are subject to the requirements of 40 CFR Part 60, Subpart Ja

   B. Storage Vessels for Petroleum Liquids for Which Construction, Reconstruction, or Modification Commenced after June 11, 1973, and prior to May 19, 1978, in 40 CFR Part 60, Subparts A and K.

C. Storage Vessels for Petroleum Liquids for Which Construction, Reconstruction, or Modification Commenced after May 18, 1978, and prior to July 23, 1984, in 40 CFR Part 60, Subparts A and Ka.

D. Storage Vessels for Petroleum Liquids for Which Construction, Reconstruction, or Modification Commenced after July 23, 1984, in 40 CFR Part 60, Subparts A and Kb.

E. Standards of Performance for Equipment Leaks of VOC in Petroleum Refineries for which Construction, Reconstruction, or Modification Commenced After January 4, 1983, and on or Before November 7, 2006 in 40 CFR Part 60, Subparts A and GGG.

F. Standards of Performance for Equipment Leaks of VOC in Petroleum Refineries for Which Construction, Reconstruction, or Modification Commenced After November 7, 2006 in 40 CFR Part 60, Subparts A and GGGa. (**09/18**)

G. The VOC Emissions from Petroleum Refinery Wastewater Systems in 40 CFR Part 60, Subparts A and QQQ. **(07/08)**

4. These facilities shall comply with all applicable requirements of the EPA regulations on National Emission Standards for Hazardous Air Pollutants (NESHAPS) promulgated for the following:

A. Benzene Transfer Operations in 40 CFR Part 61, Subparts A and BB.

B. Benzene Waste Operations in 40 CFR Part 61, Subparts A and FF. **(7/03)**

5. These facilities shall comply with all applicable requirements of EPA regulations on NESHAPS for Source Categories promulgated for the following:

A. Petroleum Refineries, including the referenced requirements contained in 40 CFR Part 63, Subparts A and CC.

B. Petroleum Refineries: Catalytic Cracking Units, Catalytic Reforming Units, and Sulfur Recovery Units, including the referenced requirements contained in 40 CFR Part 63, Subparts A and UUU. **(02/08)**

C. National Emission Standards for Hazardous Air Pollutants for Major Sources: Industrial, Commercial and Institutional Boilers and Process Heaters in 40 CFR Part 63, Subparts A and DDDDD. (**09/18**)

6. Flares shall be designed and operated in accordance with the following requirements:

A. Flares shall operate with no less than 98 percent efficiency in disposing of the carbon compounds captured by the collection system.

B. Each flare system shall be designed such that the combined assist natural gas and waste stream to each flare meets the 40 CFR § 60.18 specifications of minimum heating value and maximum tip velocity under normal, upset, and maintenance flow conditions.

The heating value and velocity requirements shall be satisfied during operations authorized by this permit. Flare testing per 40 CFR § 60.18(f) may be requested by the Texas Commission on Environmental Quality (TCEQ) Beaumont Regional Office to demonstrate compliance with these requirements.

C. Each flare shall be operated with a flame present at all times that waste gas is routed to it and have a constant pilot flame. The pilot flame shall be continuously monitored by a thermocouple or an infrared monitor. The time, date, and duration of any loss of pilot flame shall be recorded. Each monitoring device shall be accurate to, and shall be calibrated at a frequency in accordance with, the manufacturer's specifications.

D. Each flare shall be operated with no visible emissions except for periods not to exceed a total of five minutes during any two consecutive hours. This shall be ensured by the use of steam assist to each flare.

E. The flare system shall be equipped with a continuous flow monitors and reduced sulfur analyzers that provide a record of the total waste gas flow to the flares and the sulfur concentration in the flared gas.

The flow monitor and sulfur analyzer sample points shall be installed such that the total vent stream(s) to the flares is measured and analyzed. Monitors to measure the flow rate and sulfur content of flared gas shall continuously monitor and record the flow rate and the reduced sulfur content of the gas. The flow monitors shall be installed and operating in accordance with the specifications in 40 CFR § 60.107a(f)(1) by July 1, 2013. The sulfur instrument shall be installed and operated according to the specifications set out in 40 CFR § 60.107a(e).

The monitors and analyzers shall operate as required by this section at least 95% of the time when the flare is operational, averaged over a rolling 12 month period. Flared gas reduced sulfur concentration and actual exit velocity shall be recorded at least once every 15 minutes.

F. Under the following circumstances, Flare 26 is exempt from the requirement in Special Condition No. 6B to be designed to maintain a maximum tip velocity during worst-case upset conditions: global power failure and low rate depress, global cooling water failure and low rate depress, max single emergency to HP Header, Maximum single emergency to LP header, and less severe upset conditions that result in lower flare gas flow rates.

G. The permit holder shall submit an alteration request for Permit 80812 to the TCEQ APD prior to January 1, 2013. This submittal shall identify how the permit holder will monitor and operate the flares to ensure that the 40 CFR § 60.18 specifications of minimum heating value and maximum tip velocity are met when venting to a flare to control maintenance, startup, and shutdown emissions. **(1/13)**

7. The marine loading vapor combustor shall be designed and operated in accordance with the following requirements: (**09/18**)

A. The vapor combustor unit (EPN E-MC-24-25) shall achieve 99% destruction removal efficiency (DRE) of the VOCs in the waste gas directed to it. This shall be ensured by maintaining the temperature in or immediately downstream of the combustion chamber above 568°F for MC-24 and 457°F for MC-25 prior to the initial stack test performed in accordance with Special Condition 51. Following the completion of that stack test, the six minute average temperature shall be maintained above the minimum one hour average temperature maintained during the last satisfactory stack test.

B. The temperature measurement device shall reduce the temperature readings to an averaging period of 6 minutes or less and record it at that frequency. The temperature monitor shall be installed, calibrated or have a calibration check performed at least annually, and maintained according to the manufacturer's specifications. The device shall have an accuracy of the greater of ±2 percent of the temperature being measured expressed in degrees Celsius or ±2.5ºC.

C. Quality assured (or valid) data must be generated when the VCU is operating except during the performance of a daily zero and span check. Loss of valid data due to periods of monitor break down, out-of-control operation (producing inaccurate data), repair, maintenance, or calibration may be exempted provided it does not exceed 5 percent of the time (in minutes) that the VCU operated over the previous rolling 12 month period. The measurements missed shall be estimated using engineering judgment and the methods used recorded.

The vapor combustor shall be operated with no visible emissions and have a constant pilot flame during all times waste gas could be directed to it. The pilot flame shall be continuously

monitored by a thermocouple or an infrared monitor. The time, date, and duration of any loss of pilot flame shall be recorded. Each monitoring device shall be accurate to, and shall be calibrated or have a calibration check performed at a frequency in accordance with, the manufacturer's specifications. For purposes of this permit a calibration check means, at a minimum, using a second device or method to verify that the monitor is within the accuracy specifications of the permit.

D. Fuel gas combusted in the VCU shall be sweet natural gas containing no more than 0.2 grains of total sulfur per 100 dry standard cubic feet. The natural gas shall be sampled every 6 months to determine total sulfur and net heating value. Test results from the fuel supplier may be used to satisfy this requirement.

8. Reserved

Atmospheric Storage Tanks

9. Atmospheric storage tanks are subject to the following requirements. The control requirements specified in Paragraphs A-D of this condition shall not apply (1) where the VOC has an aggregate partial pressure of less than 0.50 pound per square inch, absolute (psia) at the maximum feed temperature or 95°F, whichever is greater, or (2) to storage tanks smaller than 25,000 gallons.

A. An internal floating deck or roof or equivalent control shall be installed in all tanks. The floating roof shall be equipped with one of the following closure devices between the wall of the storage vessel and the edge of the internal floating roof: (1) a liquid-mounted seal, (2) two continuous seals mounted one above the other, or (3) a mechanical shoe seal. Installation of equivalent control requires prior review and approval by the TCEQ Executive Director.

B. An open-top tank containing a floating roof (external floating roof tank) which uses double seal or secondary seal technology shall be an approved control alternative to an internal floating roof tank provided the primary seal consists of either a mechanical shoe seal or a liquid-mounted seal and the secondary seal is rim-mounted.

A weathershield is not approvable as a secondary seal unless specifically reviewed and determined to be vapor-tight. (**09/18**)

C. For any tank equipped with a floating roof, the permit holder shall perform the visual inspections and seal gap measurements as specified in 40 CFR § 60.113b, Testing and Procedures (as amended at 54 FR 32973, Aug. 11, 1989), to verify fitting and seal integrity. Records shall be maintained of the dates seals were inspected and seal gap measurements made, results of inspections and measurements made (including raw data), and actions taken to correct any deficiencies noted.

D. The floating roof design shall incorporate sufficient flotation to conform to the requirements of American Petroleum Institute (API) Code 650 dated November 1, 1998, except that an internal floating cover need not be designed to meet rainfall support requirements and the materials of construction may be steel or other materials.

E. Uninsulated tank exterior surfaces exposed to the sun shall be white, aluminum, or equivalent light color, except where a dark color is necessary to help the tank absorb or retain heat in order to maintain the material in the tank in a liquid state. Storage tanks must be equipped with permanent submerged fill pipes. **(07/08)**

F. The true vapor pressure of any liquid stored at this facility in an atmospheric tank shall not exceed 11.0 psia. (**04/18**)

G. Storage tanks T-112, T-113, and T-114 are authorized to store crude oil with each having a maximum fill/withdrawal rate of 45,000 bbls/hr. (**09/18**)

The permit holder shall maintain an emissions record which includes calculated emissions of VOC and H2S from all storage tanks during the previous calendar month and the past consecutive 12 month period. The record shall include tank identification number, control method used, tank capacity in gallons, name of the material stored, VOC molecular weight, VOC monthly average temperature in degrees Fahrenheit, VOC vapor pressure at the monthly average material temperature in psia, VOC throughput for the previous month and year-to-date. Records of VOC monthly average temperature are not required to be kept for unheated tanks which receive liquids that are at or below ambient temperatures.

Emissions from tanks shall be calculated using the methods that were used to determine the MAERT limits in the permit application. Sample calculations from the application shall be attached to a copy of this permit at the plant site

H. Storage tanks T-112, T-113, and T-114 shall be constructed with a sloped bottom and a sump that can be emptied to less than 1 percent of the sumps nominal volume. The mesa floor tank design is an acceptable alternative for a drain dry tank. The tanks shall be constructed or equipped with a connection to a vapor recovery system that routes vapors from the vapor space under the landed roof to a control device. (**09/18**)

I. The dissolved hydrogen sulfide in the crude oil in storage tanks T-112, T-113, and T-114 shall not exceed 600 ppmw in any sample. (**09/18**)

(1) In order to demonstrate compliance with this Special Condition, the permit holder shall determine the dissolved hydrogen sulfide concentration of each crude oil stock to be stored in the storage tanks identified above. The hydrogen sulfide concentration may be determined using method ASTM UOP163-10 or ASTM D7621-14. Any additional method of sampling method and analysis used must be approved by the TCEQ.

(2) Sampling for hydrogen sulfide concentration shall occur monthly.

(3) Records of H_2S concentrations measured to meet the requirements of this condition shall be maintained at the plant site. Records shall be retained for a period of five (5) years.

J. The following requirements apply to Coker Sludge Feed Tanks, Facility Identification Numbers (FINs) T-8010 and T-8400. (**09/18**)

(1) Emissions shall be vented to a Carbon Adsorption System according to the requirements of Special Condition 63.

(2) The tanks are limited to a maximum filling rate of 12,000 gallons per hour per tank.

(3) The permit holder shall maintain a record of tank throughput for the previous month and the past consecutive 12 month period for each tank.

10. The following requirements apply to liquid storage tanks storing those products identified in Special Condition 13 authorized for marine loading. **(4/18)**

A. The holder of this permit shall install and maintain a temperature monitor to monitor the bulk liquid temperature of the liquid stored in the tank. The bulk liquid temperature shall be continuously monitored and the temperature shall be recorded prior to each loading occurrence as defined in SC 13.D.

B. The temperature monitor shall be installed, calibrated or have a calibration check performed at least annually, and maintained according to the manufacturer's specifications. The device shall have an accuracy of ±3.00 percent of the temperature being measured expressed in degrees Fahrenheit or ±3°F.

C. For storage tanks in Residual Oil or Lube Oil service, the permit holder may assume an emission rate of 1 lb/hr for each loading occurrence as defined in Special Condition 13.D when calculating the total calculated VOC emission rate (ER) specified in Special Condition 13.C in lieu of temperature monitoring specified in this condition.

11. Opacity of emissions from tanks used to store residual oil (resid) shall not exceed 15 percent averaged over a six-minute period, as determined by a certified observer using EPA Test Method 9. **(07/08)**

12. All external floating roof storage tank slotted guide/gauge poles shall be equipped with a gasketed sliding cover, a pole wiper and either (1) a pole sleeve or (2) a float. **(07/08)**

Marine Loading

13. The following limits apply to marine loading of ocean-going vessels and inland barges. For purposes of this permit ocean-going vessels include ships and ocean barges. **(4/18)**

A. The loading of liquids having a vapor pressure less than 0.5 psia to ocean-going vessels and inland barges are limited to the products identified below at the rates indicated.

Table 1. Marine loading rates for materials less than 0.5 psia.

Compound	Maximum Combined Loading Rate for Ocean-Going Vessels (bbls/hr)	Maximum Combined Loading Rate for Inland Barges (bbls/hr)
Kerosene/Jet Fuel	25,000	5,000
Diesel/Light Cycle Oil (LCO)	25,000	5,000
Heavy Gas Oil	8,000	8,000
Residual Oil	6,000	6,000
Lube Oil	6,700	6,700
Carbon Black Oil	6,700	6,700

B. The following requirements apply to loading of products having a vapor pressure greater than or equal to 0.5 psia at 95°F to ocean-going vessels and inland barges.

(1) Collected vapors from all marine loading shall be routed to the marine vapor combustor.

(2) The total combined loading rate is limited to no more than 25,000 bbls/hr.

(3) Loading is limited to the liquids identified below at the rate indicated:

Table 2. Marine loading rates for materials greater than 0.5 psia

Compound	Maximum Combined Loading Rate for Ocean-Going Vessels (bbls/hr)	Maximum Combined Loading Rate for Inland Barges (bbls/hr)
Gasoline/Gasoline Blendstocks	25,000	5,000
Naphtha	25,000	5,000
Reformate	25,000	5,000
Raffinate	25,000	5,000
Benzene Concentrate	0	5,000
Pyrolysis Gasoline*	500	500
Cyclohexane*	4,800	4,800

*Increase in these throughputs or loading of other compounds for the adjacent company will require approval of the TCEQ Executive Director through permit action

(4) The loading of Pyrolysis Gasoline is limited to a total combined loading rate of 500 bbls/hr and 200,000 bbls/yr on a rolling 12-month basis. (**08/18**)

(5) The loading of Cyclohexane is limited to a total combined loading rate of 4800 bbls/hr and 1,100,000 bbls/yr on a rolling 12-month basis. (**08/18**)

(6) Gasoline Blendstocks include those blendstocks having a short term Effects Screening Level (ESL) of at least 3500 micrograms per cubic meter. Records of each blendstock loaded including the blendstock name, CAS number, and the short term ESL shall be maintained and made available upon request.

C. Compliance with the short-term (hourly) maximum allowable VOC emission rate limits for dock loading fugitives (EPN F-DOCK) and the Dock VCU (EPN E-MC-24-25) during periods of loading of authorized products to authorized vessel types shall be determined using the following equation:

$ER = \Sigma L_L (i) * FR(i) * \text{Actual } TVP_A (i)/\text{Reference } TVP_R (i) * \text{Reference Temperature } T_R (j) / \text{Actual Temperature } T_A (i)$

ER = The total calculated VOC emission rate (lb/hour) for all loading occurrences based on the combination of vessel type and product loaded for each loading occurrence during the loading event (lb/hour).

L_L = Loading Loss Factor (lb/Mbbl) for the combination of product and vessel type being loaded from Table 3.

FR = Volume loaded for each vessel type and product loaded in each hour (Mbbls/hr).

Actual TVP_A/reference TVP_R = the ratio of the actual True Vapor Pressure of the liquid being loaded (psia) to the reference True Vapor Pressure from Table 3. For products other than gasoline, reformate, raffinate (including gasoline blendstocks) or kerosene/jet, the ratio (Actual TVP_A /Reference TVP_R) may be assumed to be equal to 1 provided the actual bulk liquid temperature does not exceed the reference temperature for the product.

Reference Temperature T_R /Actual Temperature T_A = the ratio of the reference liquid temperature from Table 3 to the actual bulk liquid temperature. Reference Temperature T_R (°F + 460) = the liquid temperature at which the L_L (lbs/Mbbl) is calculated. Actual Temperature, T_A, (°F + 460) = the actual bulk liquid temperature at which the product is loaded. For products other than gasoline, reformate, raffinate (including gasoline blendstock) or kerosene/jet the ratio (Reference Temperature, T_R/Actual Temperature, T_A) may be assumed to be equal 1 provided the actual bulk liquid temperature does not exceed the reference temperature for the product.

D. For purposes of this permit, a loading occurrence is defined as the loading of an authorized product to an authorized vessel type. A loading event is defined as one or more loading occurrences. A new loading event is defined by the additional of any new loading occurrences.

E. Prior to the start of each loading occurrence, the permit holder shall determine the maximum loading rate for each combination of product loaded and vessel type that will occur within the loading event from the method identified in paragraph c and data contained in Table 3; “Marine Loading Factors” in order to demonstrate compliance with the maximum short-term maximum loading rate for controlled and uncontrolled emissions from marine loading. The maximum loading rate calculated for each occurrence will not be exceeded during the event. At no time shall the loading rates for any product exceed those specified in paragraphs A and B of this condition.

Table 3: Marine Loading Factors

Product	Reference TVP	Reference Temp.	Uncontrolled (EPN F-DOCK)		Controlled (EPN E-MC-24-25)	
	P	T	Ocean Going Vessels	Inland Barges	Ocean Going Vessels	Inland Barges
	psia	F°	lb/Mbbl	lb/Mbbl	lb/Mbbl	lb/Mbbl
Gasoline/Gasoline Blendstocks	11.0	105	1.264	0	1.264	3.160
Pyrolysis Gasoline	11.0	105	1.264	0	1.263	3.158
Naphtha	3.47	105	0.514	0	0.514	1.285
Reformate	11.0	105	1.264	0	1.264	3.160
Raffinate	5.78	105	0.729	0	0.729	1.821
Benzene Conc	5.25	105	N/A	0	N/A	1.899
Cyclohexane	3.64	105	0.568	0	0.568	1.42
Kerosene/Jet	0.163	105	3.917	9.792	0	0
Diesel/LCO	0.025	105	0.602	1.505	0	0
Heavy Gas Oil	0.158	105	0.469	1.173	0	0
Residual Oil	0.0002	105	0.008	0.019	0	0
Lube Oil	0.0002	105	0.008	0.019	0	0
Carbon Black Oil	0.0002	105	0.008	0.019	0	0

F. In lieu of paragraph E of this condition, the permit holder may develop and maintain a record of loading events of vessel types, products, and maximum loading rate that have been determined to demonstrate compliance with maximum short-term VOC loading emissions using the method in paragraph C with the data contained in Table 3. The record and associated data and calculations used to demonstrate compliance for the loading event shall be kept and made available upon request.

G. The permit holder shall maintain a record of all monitored parameters and calculations or record maintained as compared to the current loading event.

14. All marine loading at the site is subject to the following conditions: (**09/18**)

A. All lines and connectors shall be visually inspected for any defects prior to hookup. Lines and connectors that are visibly damaged shall be removed from service. Operations shall cease immediately upon detection of any liquid leaking from the lines or connections.

B. All shore-based equipment is subject to the piping fugitive emissions monitoring requirements of Special Condition No. 57. Shore-based equipment includes (but is not limited to) all equipment such as loading arms, pumps, meters, shutoff valves, relief valves, and other piping and valves between the inland barge marine loading facility and the vapor recovery system and between the marine loading facility and the associated land-based storage tanks

C. Collected vapors from loading liquids having a vapor pressure greater than or equal to 0.5 psia to marine vessels shall be routed to the marine vapor combustors (EPN E-MC-24-25).

15. Unless otherwise specified in this permit, all vapors associated with negative pressure loading of inland barges as allowed under USCG regulations with liquids having a vapor pressure greater than or equal to 0.5 psia at 95°F shall be routed through a vacuum-assisted collection system as specified below. (**09/18**)

A. Barges shall not be loaded unless the vapor collection system is properly connected and the entire collection system is working as designed.

B. A blower system shall be installed to produce a vacuum in the inland barges during all loading operations. A pressure/vacuum measurement device shall be installed as close as possible to the vessel's vapor return port to continuously monitor and record the vacuum pressure while loading is taking place. Loading shall not occur unless there is a vacuum of at least 1.5 inch water column being maintained by the vacuum-assist vapor collection system while loading is occurring. The monitor shall be calibrated or have a calibration check performed on an annual basis to meet an accuracy of ±1.0 mm Hg.

C. Quality-assured (or valid) data must be generated when barge loading is occurring. Loss of valid data due to periods of monitor break down, out-of-control operation (producing inaccurate data), repair, maintenance, or calibration may be exempted provided it does not exceed 5 percent of the time (in minutes) that barge loading is occurring over the previous rolling 12-month period. The measurements missed shall be estimated using engineering judgment and the methods used recorded.

D. Vacuum data shall be recorded every 6 minutes while loading is occurring.

16. The following additional requirements apply to loading of a VOC represented at 99% collection efficiency and has a vapor pressure equal to or greater than 0.5 pounds per square inch absolute (psia) under actual storage conditions onto inerted marine vessels (ships and ocean going barges). (**04/18)**

A. Before loading, the owner or operator of the marine terminal shall verify that the marine vessel has passed an annual vapor tightness test as specified in 40 CFR §63.565(c) (September 19, 1995) or 40 CFR §61.304(f) (October 17, 2000) within the previous twelve months.

B. The pressure at the vapor collection connection of an inerted marine vessel must be maintained such that the pressure in a vessels' cargo tanks do not go below 0.2 pounds per square inch gauge (psig) or exceed 80% of the lowest setting of any of the vessel's pressure relief valves. The lowest vessel cargo tank or vent header pressure relief valve setting for the vessel being loaded shall be recorded. Pressure shall be continuously monitored while the vessel is being loaded. Pressure shall be recorded at fifteen minute intervals.

C. VOC loading rates shall be recorded during loading. The loading rate must not exceed the maximum permitted loading rate.

D. During loading, the owner or operator of the marine terminal or of the marine vessel shall conduct audio, olfactory, and visual (AVO) checks for leaks once every 8 hours for on-shore equipment and on board the ship.

(1) If a liquid leak is detected during loading and cannot be repaired immediately (for example, by tightening a bolt or packing gland), then the loading operation shall cease until the leak is repaired.

(2) If a vapor leak is detected by sight, sound, smell, or hydro gas analyzer during the loading operation, then a "first attempt" shall be made to repair the leak. Loading operations need not be ceased if the first attempt to repair the leak is not successful provided that the first attempt effort is documented by the owner or operator of the marine vessel and a copy of the repair log is made available to a representative of the marine terminal.

(3) If the attempt to repair the leak is not successful and loading continues, emissions from the loading operation for that ship shall be calculated assuming a collection efficiency of 95%.

E. Date and time of each AVO inspection shall be noted in the operator's log or equivalent. Records with date, time and signature of operator shall be maintained at the plant site of all repairs and replacements made due to leaks. These records shall be made available to representatives of the Texas Commission on Environmental Quality (TCEQ) upon request.

17. The permit holder shall maintain and update a monthly emissions record which includes calculated emissions of VOC from all loading operations over the previous rolling 12 month period. The record shall include the loading spot, type of marine vessel loaded, control method used, quantity loaded in gallons, name of the liquid loaded, vapor molecular weight, liquid temperature in degrees Fahrenheit, liquid vapor pressure at the liquid temperature in psia, liquid throughput for the previous month and rolling 12 months to date. Records of VOC temperature are not required to be kept for liquids loaded from unheated tanks which receive liquids at or below ambient temperatures. Emissions shall be calculated using the methods represented in the permit amendment PI-1 dated August 10, 2017. (**09/18**)

Fluidized Catalytic Cracking Unit (FCCU)

18. Emissions from the FCCU Wet Gas Scrubber (Emission Point No. [EPN] E-01-WGS) shall not exceed the following:

A. Opacity of shall not exceed 20 percent averaged over a six-minute period, as determined by a certified observer using EPA Test Method 9.

B. The SO_2 concentration from the FCCU to the atmosphere shall be no greater than 25 ppmvd measured as a 365-day rolling average and 50 ppmvd measured as a 7-day rolling average, both at 0 percent O_2. **(04/16)**

C. The NO_x concentration from the FCCU to the atmosphere shall be no greater than 50 ppmvd measured as a 365-day rolling average and 100 ppmvd measured as a 7-day rolling average both at 0 percent O_2. The beginning date of the averaging periods for these limits is January 1, 2014. **(04/16)**

D. The emissions of sulfuric acid (H_2SO_4) from the FCCU to the atmosphere shall be tracked by monitoring the coke burn rate and applying the represented H_2SO_4 factor of 0.288 pounds per 1,000 pounds of coke burned (lb/1000 lb) on a 365-day rolling average. **(05/15)**

E. The emissions of particulate matter shall be limited to one (1) pound per 1,000 pounds of coke burned (front half only according to Method 5B or 5F, as appropriate), measured as a one-hour aver-age over three performance test runs. **(04/16)**

F. The emissions of carbon monoxide shall be limited to 500 ppmvd (at 0% O_2), measured as a one-hour block average. **(04/16)**

19. The FCCU Wet Gas Scrubber liquid flow rate shall be continuously monitored and be maintained at levels greater than the minimum one-hour average value observed in the last satisfactory stack test performed in accordance with Special Condition No. 50. The liquid-to-air ratio and pressure drop across the Agglo Filtering Modules shall also be continuously monitored and be maintained greater than the minimum one hour average value observed in the last satisfactory stack test performed in accordance with Special Condition No. 50. **(05/15)**

    The flow rates and pressures shall be recorded every six minutes as six-minute averages. Each flow and pressure monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, or at least annually, whichever is more frequent, and shall be accurate to within 2 percent of span or 5 percent of the design value.

    Quality-assured (or valid) data must be generated when the FCCU is operating except during the performance of a daily zero and span check. Loss of valid data due to periods of monitor break down, out-of-control operation (producing inaccurate data), repair, maintenance, or calibration may be exempted provided it does not exceed 5 percent of the time (in minutes) that the FCCU operated over the previous rolling 12-month period. The measurements missed shall be estimated using engineering judgement and the methods used recorded. **(02/08)**

    Alternatively the FCCU Wet Gas Scrubber shall demonstrate compliance with the most recent alternative monitoring plan (AMP) and exemption from continuous emissions monitoring requirements (ECEMR) requests approved by EPA and/or TCEQ as provided by 40 CFR 60.13(i)(1), 40 CFR 63.1573(e), and 30 TAC 111.111(a)(3). **(05/15)**

Cooling Towers

20. Cooling Towers shall be monitored as follows:

    A. The VOC associated with cooling tower water shall be monitored monthly with an air stripping system meeting the requirements of the TCEQ Sampling Procedures Manual, Appendix P (dated January 2003 or a later edition) or an approved equivalent sampling method. The monitoring results, cooling water flow rate, and maintenance activities on the cooling water system shall be recorded.

    B. The cooling water for Cooling Tower Nos. CT-136A, CT-136B, CT-366, CT-432 and CT-446 shall be sampled once a week for total dissolved solids (TDS). Dissolved solids in the cooling water drift are considered to be emitted as particulate matter. **(8/13)**

21. The following requirements shall apply to Cooling Towers F-446CT, E-433-CT and CT-244 upon startup of the DCU 844 represented in Coker Project, PI-1 dated February 27, 2017. **(11/18)**

    A. The VOC associated with cooling tower water shall be monitored monthly with an air stripping system meeting the requirements of the TCEQ Sampling Procedures Manual, Appendix P (dated January 2003 or a later edition) or an approved equivalent sampling method

    B. Cooling tower water VOC concentrations above 0.08 ppmw indicate faulty equipment. Equipment shall be maintained so as to minimize VOC emissions into the cooling water. Faulty equipment shall be repaired at the earliest opportunity but no later than the next scheduled shutdown of the process unit in which the leak occurs.

       Emissions from the cooling tower are not authorized if the VOC concentration of the water returning to the cooling tower exceeds 0.8 ppmw. VOC concentrations above 0.8 ppmw are not subject to extensions for delay of repair under this permit condition.

C. The results of the monitoring, cooling water flow rate and maintenance activities on the cooling water system shall be recorded. The monitoring results and cooling water hourly mass flow rate shall be used to determine cooling tower hourly VOC emissions. The rolling 12 month cooling water emission rate shall be recorded on a monthly basis and be determined by summing the VOC emissions between VOC monitoring periods over the rolling 12 month period. The emissions between VOC monitoring periods shall be obtained by multiplying the total cooling water mass flow between cooling water monitoring periods by the higher of the 2 VOC monitored results.

D. The cooling towers shall be operated and monitored in accordance with the following:

(1) Each cooling tower shall be equipped with drift eliminators having manufacturer's design assurance of 0.001% drift or less. Drifts eliminators shall be maintained and inspected at least annually. The permit holder shall maintain records of all inspections and repairs.

(2) Total dissolved solids (TDS) shall not exceed 2,500 parts per million by weight (ppmw). Dissolved solids in the cooling water drift are considered to be emitted as PM, PM_{10}, and $PM_{2.5}$ as represented in the permit application calculations.

(3) Cooling water shall be sampled at least once per week for TDS.

(4) Cooling water sampling shall be representative of the cooling tower feed water and shall be conducted using approved methods.

(a) The analysis method for TDS shall be EPA Method 160.1, ASTM D5907, and SM 2540 C [SM - 19th edition of Standard Methods for Examination of Water]. Water samples should be capped upon collection, and transferred to a laboratory area for analysis.

(b) Alternate sampling and analysis methods may be used to comply with B(4)(a) with written approval from the TCEQ Regional Director.

(c) Records of all instrument calibrations and test results and process measurements used for the emission calculations shall be retained.

E. Emission rates of PM, PM_{10} and $PM_{2.5}$ shall be calculated using the measured TDS, the design drift rate and the daily maximum and average actual cooling water circulation rate for the short term and annual average rates. Alternately, the design maximum circulation rate may be used for all calculations. Emission records shall be updated monthly.

F. The actual cooling water circulation rate shall be measured at least hourly. Measurements shall be reduced to an hourly average and recorded for use in emission calculation.

G. The permit holder shall notify the TCEQ's Regional Office within 30 days of completion the cooling towers' additional cell and/or increasing the circulation rate. **(11/18)**

Sulfur Recovery

22. There shall be a minimum of 44 H_2S monitors placed throughout the sulfur recovery complexes. These monitors shall be arranged in such a way that provides coverage for wind directions varying through 360°. The monitors shall be set to alarm at a concentration of 10 ppmv and shall alarm in the control room and in the local plant area. The monitors shall be tested and calibrated at least once every three months. A diagram of the operating units and the location of the monitors shall be provided at the plant site and made available to representatives of the TCEQ upon request. **(06/04)**

23. Each individual SRU train shall not exceed the sulfur recovery rates indicated. (**09/18**)

SRU	Train	Recovery (LTPD)
543	543	107
	300	200
544	400	170
	500	170
545	100	260
	200	260
546	600	260
	700	260
547	800	208.5
	900	208.5

Upon startup of SRU 547 or upon operation of the coker 844 the total combined sulfur recovered from the Sulfur Recovery Units (SRUs) shall not exceed 1,850 long tons per day (LTPD) on a 12 month rolling average basis. (**09/18**)

24. The minimum sulfur recovery efficiency for the permitted Sulfur Recovery Units (SRUs) 543, 544, 545, 546, shall be 99.8 percent for air-based operations and 99.95 percent for oxygen (O_2)-based (COPE) operations. For the range of unit operations between air only and O_2 only, the required sulfur recovery efficiency shall be determined by linear interpolation between the values specified for each mode (air only, O_2 only), on the basis of the extent of volume-percent O_2 enrichment.

The required sulfur recovery efficiency shall be determined by the following calculation:

$99.8 + [0.15 \times (\text{percent-}O_2/100)]$

The minimum sulfur recovery efficiency for SRU 547 shall be 99.8 percent for air-based operations. (**09/18**)

The actual sulfur recovery efficiency for each unit shall be determined by the following calculation:

Efficiency = (sulfur recovered)*(100)/(sulfur acid gas)

Where: Efficiency = sulfur recovery efficiency, percent

Sulfur recovered = (sulfur acid gas-sulfur stack), pounds per hour (lbs/hr)

Sulfur acid gas = sulfur in acid gas stream, lbs/hr

Sulfur stack = sulfur in incinerator stack, lbs/hr

The average sulfur emission reduction efficiency (sulfur recovery efficiency) shall be demonstrated for each 24-hour period by a mass balance calculation using data obtained daily from the incinerator stack sulfur dioxide (SO_2) monitor, daily sulfur production records, and other daily process flow data. The daily sulfur recovery efficiencies shall be calculated on a monthly basis. Records and copies of the compliance calculations shall be maintained and retained not less than 5 years. **(09/18)**

25. All waste gas streams from the Shell Claus Off-Gas Treating Unit (SCOT) amine regeneration units containing H_2S and/or VOC shall be routed to the SRUs. **(06/04)**

26. The sour water storage tanks shall be subject to the following conditions:

    A. Tank Nos. 78, 88, 2588, and 2590 shall be used as sour water storage tanks.

    B. The sour water storage tanks shall be continuously monitored for hydrocarbon layer (HL) thickness by electronic gauge when in service. High and low level alarms, to be activated at HL thicknesses of four feet and six inches, respectively, shall be incorporated into the gauge system. Records of all high and low HL alarms shall be maintained.

    C. Thirteen feet of sour water shall be maintained in a sour water storage tank when in service. If the sour water level is discovered at or below 13 feet, steps shall be taken to restore the sour water level back to the 13 foot level no later than 24 hours after discovery, unless the tank is being taken out of service. Records of the date and time of discovery of a low sour water level and date and time the sour water level is restored to a minimum of 13 feet shall be maintained. Any automated monitoring system used to demonstrate compliance with this condition shall be calibrated and maintained according to manufacturer's specifications. **(09/18)**

    D. The sour water storage tank system shall be maintained by either of the following methods: **(09/18)**

        (1) A minimum sour water retention time of 2.0 days in conjunction with a hydrocarbon detection and flow diversion system designed to prevent hydrocarbon carryover to the SRUs by routing sour waters with unacceptable levels of hydrocarbons to the tanks listed in A of this condition. Retention time shall be calculated and recorded daily using the daily average combined tank volume of all sour water tanks and the daily average combined feed rates to the sour water strippers.

        (2) A minimum sour water retention time of 3.0 days

    E. Holdup (excess) capacity is sour water tank capacity used for sour water storage when necessary to avoid flaring of sour water stripper gas due to reduced sulfur recovery capacity. There shall be at least 3.0 days of holdup (excess) capacity available for sour water storage. The holding storage requirement shall be based on the unplanned shut down of the largest SRU and the corresponding loss of water treatment capacity.

        The holdup (excess) capacity shall be restored within 21 days of the return of the SRUs and sour water system to normal operations. The daily average sour water storage tank holdup (excess) volume shall be calculated and recorded.

    F. If acid gas flaring takes place that might be traced to hydrocarbon carryover from the sour water system, the operator shall engage a third party consultant to complete a Root Cause Failure Analysis (RCFA) within 90 days after the acid gas flaring event in question. The Beaumont Regional Office shall be supplied with a copy of the RFCA within 10 days of it being completed. If the RCFA determines that the acid gas flaring event can be traced to sour water system hydrocarbon carryover that is partially or totally caused by inadequate retention or hold up times, the holder of this permit shall implement one of the following options within 60 days after completion of the RFCA:

(1) The holder of this permit shall submit design information and a proposed implementation schedule to the TCEQ Office of Permitting and Registration for three days of sour water retention and hold up time based on maximum expected feed rates to the sour water strippers, or

(2) Design information and implementation schedule of a proposed alternative other than increased sour water retention time.

27. The handling of the liquid sulfur product from SRU 543, SRU 544, SRU 545, SRU 546, and 547 shall be subject to the following conditions:

A. Liquid sulfur from SRU 543, SRU 544, SRU 545, and SRU 546 will be routed to covered sulfur storage pits. The breathing vents from the sulfur storage pits shall be routed to a TGI or to the front end of a Claus reactor.

Liquid sulfur shall be degassed by an air stripping system to an H_2S content of 100 ppmw or less prior to loading into tank trucks. The effluent from the liquid sulfur being degassed shall be routed to the front end of a Claus reactor

B. Liquid sulfur from SRU 547 shall be degassed by an air stripping system to an H_2S content of 100 ppmw or less prior to loading into sulfur storage tank 8002. The effluent from the liquid sulfur being degassed shall be routed to the front end of a Claus reactor. During periods that the sulfur degasser is out of service due to planned startup and shutdown, the H2S concentration of liquid sulfur shall not exceed 200 ppmw prior to loading into storage tank 8002. Shutdown of the sulfur degasser due to scheduled maintenance is limited to no more than 10 days per rolling 12-month period. Records of scheduled sulfur degasser maintenance downtime shall be maintained. (**09/18**)

C. For the purpose of determining compliance with Paragraph A and B of this condition, the holder of this permit shall perform at his or her expense sampling and other testing as required to determine the H2S content of the liquid sulfur prior to degassing (ppmw) and to demonstrate compliance with the 100 ppmw degassed concentration. The SRU shall operate at maximum sulfur production rate during sampling. Sampling methods and procedures must be approved prior to sampling by the TCEQ Beaumont Regional Director. The TCEQ Executive Director or designated representative shall be afforded the opportunity to observe all such sampling.

D. The sampling required in Paragraph C of this condition shall occur within 30 days after each SRU degassing system starts operation and, after that, sampling shall occur at least once every 12 months. The H2S concentration of liquid sulfur prior to degassing shall be determined from each source of liquid sulfur at least once every 12 months. Within 30 days after such sampling is completed, copies of the final sampling report shall be forwarded to the TCEQ Beaumont Regional Office.

E. The permit holder shall sample the vapor space of sulfur storage tank 8002 and a tank truck receiving liquid sulfur from each storage pit being loaded with liquid sulfur for H_2S using stain tubes monthly. The sampling procedure used for the stain tube testing shall be reviewed and approved by the TCEQ Beaumont Regional Office. Records of the monthly sampling shall be kept. **(09/18)**

F. No more than 180 long tons of sulfur may be loaded to trucks in any one hour at each of the sulfur loading racks. (EPNs F-LOADING) **(09/18)**

G. Records shall be maintained of each truck loaded including weight of sulfur loaded.

28. The sulfur recovery complexes shall be operated and maintained such that there is no period greater than 24 hours where at least 200 long tons per day of sulfur recovery capacity is held in reserve and immediately available, except as noted below.

    Operation for greater than 24 hours without the reserve capacity is only allowed during periods of maintenance and repair of sulfur recovery equipment. The TCEQ Beaumont Regional Office shall be informed prior to all such periods of operation. **(02/08)**

29. Sulfur load shedding plans shall be revisited daily to reflect refinery activity. **(02/08)**

30. Tail Gas Incinerators shall operate with no less than 99.9 percent efficiency (on an hourly average) in disposing of the carbon compounds captured by the collection system and the hydrogen sulfide (H_2S) in the exhaust shall not exceed 5.0 parts per million by volume, dry (ppmvd) (corrected to 3 percent O_2) on an hourly average. TGI operation and H_2S emissions shall be monitored and maintained in accordance with Paragraph A or B below.

    A. The TGI firebox exit temperatures and O_2 concentrations shall be continuously monitored and recorded. The temperature measurement device shall reduce the temperature readings to an averaging period of six minutes or less and record it at that frequency. The temperature monitor shall be installed, calibrated at least annually, and maintained according to the manufacturer's specifications. The device shall have an accuracy of the greater of ±2 percent of the temperature being measured expressed in degrees Celsius or ±2.5°C.

    Quality-assured (or valid) data must be generated when waste gas is being fed to the TGI except during the performance of a daily zero and span check. Loss of valid data due to periods of monitor break down, out-of-control operation (producing inaccurate data), repair, maintenance, or calibration may be exempted provided it does not exceed 5 percent of the time (in minutes) that the TGI operated over the previous rolling 12-month period. The measurements missed shall be estimated using engineering judgement and the methods used recorded.

    The TGI shall be operated with not less than the O_2 concentration maintained during the last satisfactory stack test performed in accordance with Special Condition No. 50. The firebox chamber six-minute average temperature shall be maintained above the hourly average temperature maintained during the last satisfactory stack test performed in accordance with Special Condition No. 50.

    B. The permit holder shall operate a continuous emissions monitoring system (CEMS) to monitor H_2S concentrations and emission rates. The CEMS shall meet the requirements of Special Condition No. 53. The hourly average H_2S exhaust concentration shall be maintained at less than 5.0 ppmvd (corrected to 3 percent O_2) when monitoring the incinerator this way. **(02/08)**

    C. The follow additional requirements apply to SRU 547 (EPN E-05-SCOT) (**09/18**)

    (1) The TGI firebox exit temperature shall be maintained at not less than 1,400 °F and exhaust oxygen concentration not less than 3 percent while waste gas is being fed into it prior to initial stack testing. After the initial stack test has been completed, the TGI shall be operated with not less than the oxygen concentration maintained during the last satisfactory stack test performed in accordance with Special Condition 50. The firebox chamber 6 minute average temperature shall be maintained above the hourly average temperature maintained during the last satisfactory stack test performed in accordance with Special Condition 50.

    (2) The tailgas incinerator exhaust stack flow rate shall be continuously monitored and recorded. The flow shall be recorded at least every 15 minutes and the hourly average flow rate shall be recorded. Each flow monitoring device shall be calibrated at a frequency in accordance with the manufacturer’s specifications, or at least annually,

whichever is more frequent, and shall be accurate to within 2 percent of span or 5 percent of the lesser of the design value or the flow measured during the most recent stack test.

Quality assured (or valid) data must be generated when the tail gas incinerator is operating except during the performance of a daily zero and span check. Loss of valid data due to periods of monitor break down, out-of-control operation (producing inaccurate data), repair, maintenance, or calibration may be exempted provided it does not exceed 5 percent of the time (in minutes) that the tailgas incinerator operated over the previous rolling 12 month period. The measurements missed shall be estimated using engineering judgment and the methods used recorded.

(3) Fuel gas combusted at this facility shall be sweet natural gas.

(4) The in-stack concentration of SO2 from the tailgas incinerator, EPN E-05-SCOT, shall not exceed the following limits.

(a) 250 parts per million by volume calculated on a 1-hour average on a dry and air-free basis (ppmvd).

(b) 97 parts per million by volume calculated on a rolling 24-hour average on a dry and air-free basis (ppmvd) updated each hour. The rolling 24-hour average concentration may exceed this limit provided it does not exceed a cumulative total of 200 hours per year.

(c) 100 parts per million by volume calculated on an annual average on a dry and air-free basis (ppmvd)

31. There shall be no visible emissions from the TGI stacks.

Heaters and Boilers

32. Heaters and boilers are subject to the limitations below:

A. Heaters and boilers shall be operated with no visible emission, except for those periods described in 30 TAC § 111.111(a)(1)(E).

B. With the exception of the period prior to initial stack testing required by Special Condition No. 50, the heaters for atmospheric and Vacuum Crude Unit 147 (AVU-147) and Diesel Hydrotreating Unit 246 (DHT-246) shall each maintain nitrogen oxide (NO_x) emissions less than or equal to 0.035 lb/MMBtu on a daily average.

C. The NO_x and carbon monoxide (CO) emissions from Hydrocracker Unit 943 Reactor 1 and 2 Furnaces shall not exceed the following, with the exception of the period prior to initial stack testing required by Special Condition No. 50:

0.035 lb NO_x/MMBtu on an hourly average,

100 ppmvd CO hourly average (corrected to 3 percent O_2), and

50 ppmvd CO annual average (corrected to 3 percent O_2).

D. The NO_x emission limits (in lb/MMBtu at the fuel higher heating value [HHV] for a 365 day rolling average) for the following heaters and boilers authorized by this permit required to be monitored with a CEMS are identified in the table below. The heaters and boilers shall not exceed the individual emissions limitation. **(04/16)**

EPN	Unit Name	Description	NO_x Limit[1]
E-01-147	AVU147	AVU No. 147 F-1100	0.035
E-02-147	AVU147	AVU No. 147 F-1200	0.035
E-01-942[2]	HCU942	HCU No. 942 F-1300 Fractionator Feed Furnace and F-1000 First Stage Reactor Furnace	0.044
E-01-943[2]	HCU943	HCU 943 Reactor 1 Furnace	0.035
		HCU 943 Reactor 2 Furnace	0.035
E-02-943	HCU943	HCU 943 Fractionator Feed Furnace	0.015
E-01-146[3]	AVU146	AVU No. 146 H-101	0.080 **(07/16)**
E-02-146[3]	AVU146	AVU No. 146 H-102A and H-102B	0.080 **(07/16)**
E-01-243	GFU243	Gulfining Unit No. 243 B-301	0.050 **(07/16)**
E-01-443	HFAU443	HF Alkylation Unit No. 443 H-1	0.060 **(07/16)**
E-01-843	DCU843	DCU No. 843 F-1000	0.060 **(07/16)**
E-02-843	DCU843	DCU No. 843 F-2000	0.060 **(07/16)**
E-03-843	DCU843	DCU No. 843 F-3000	0.060 **(07/16)**
E-01-1344	CRU1344	CRU No. 1344 Heater H-1	0.070 **(07/16)**
E-03-1344	CRU1344	CRU No. 1344 Heaters H-2 and H-32	0.060 **(07/16)**
E-01-BH 15	BH15	Boiler House 15 BLR 41	0.060 **(07/16)**
E-02-BH 15	BH15	Boiler House 15 BLR 42	0.060 **(07/16)**
E-03-BH 15	BH15	Boiler House 15 BLR 43	0.060 **(07/16)**

[1]in lb/MMBtu, HHV, 365 day rolling average
[2]Compliance will be demonstrated with combined stack CEMS. **(2/14)**
[3]NOx limits shall supersede limits listed in Special Condition 33.C before the start of DCU 844 represented in the Coker Project, PI-1 dated February 27, 2017. The permit holder shall notify the TCEQ's Regional Office of the low NO_x burners' installation within 30 days of completion. **(11/18)**

NO_x emission limits (in lb/MMBtu, HHV) for the following heaters and boilers authorized by this permit are identified in the table below. The heaters and boilers shall not exceed the individual emissions limitation. **(04/16)**

EPN	Unit Name	Description	NO_x Limit[1]
E-01-241	GFU241	Gulfining Unit No. 241 B-101	0.045
E-01-242	GFU242	Gulfining Unit No. 242 B-201	0.065
E-02-1344	CRU1344	CRU No. 1344 Heater H-33	0.040 **(07/16)**

[1] - in lb/MMBtu, HHV **(2/14)**

E. Heaters and boilers are prohibited from burning or combusting fuel oil. For purposes of this paragraph, fuel oil is predominately in the liquid phase at the point of combustion with a sulfur content greater than 0.05% by weight. **(07/16)**

33. The following requirements shall apply to the DCU 844 coker Furnace #1 (EPN E-01-844), DCU 844 coker Furnace #2 (EPN E-02-844), Hydrocracker Unit 943 Fractionator Feed Furnace (EPN E-02-943), Heater 146-H101 (EPN E-01-146), and Heaters AVU No. 146 H-102A and H-102B (EPN E-02-146). **(09/18)**

A. NO_x, CO, and ammonia (NH_3) emissions from DCU 844 coker Furnace #1 (EPN E-01-844) and DCU 844 coker Furnace #2 (EPN E-02-844), shall not exceed the following, with the exception of the period prior to initial stack testing required by Special Condition No. 50. **(09/18)**

0.015 lb NO_x/MMBtu on an hourly average,

CO emissions shall not exceed the 100 ppmv CO on an hourly average and 50 ppmv on an annual average basis

10 ppmvd NH3 hourly average (corrected to 3 percent O_2)

B. Following heater modifications associated with the-coker project, PI-1 dated February 27, 2017 NO_x, CO, and NH_3 emissions from the Hydrocracker Unit 943 Fractionator Feed Furnace (EPN E-02-943) shall not exceed the following. **(09/18)**

0.015 lb NO_x/MMBtu on an hourly average,

CO emissions shall not exceed the 100 ppmv CO on an hourly average and 50 ppmv on an annual average basis,

10 ppmvd NH3 hourly average (corrected to 3 percent O_2)

C. Following heater modifications associated with the coker project, PI-1 dated February 27, 2017 Heater 146-H101 (EPN E-01-146), and Heaters AVU No. 146 H-102A and H-102B (EPN E-02-146) shall comply with the following. **(09/18)**

(1) Heaters shall be equipped with low-NOx burners meeting the following limits:

0.067 lb NO_x/MMBtu on an hourly average (EPN E-01-146),

0.062 lb NO_x/MMBtu on an hourly average (EPN E-02-146),

(2) CO emissions shall not exceed the 100 ppmv CO on an hourly average and 50 ppmv on an annual average basis (corrected to 3 percent O_2).

34. Fuel gas for the heaters and boilers covered under this permit shall meet the following requirements:

A. FCCU 1241 Heaters B-103A (EPN E-01-1241) and B-103B (EPN E-02-1241) shall be fired with fuel gas containing no more than 5 grains of total sulfur per 100 dscf.

B. The composition and the level of H_2S treatment of the fuel gas stream from Chevron/CPC's EU1544, routed to Premcor's Boiler House 16, and identified as EU1544, shall be as described in Table 4 of the permit modification application dated November 2000.

C. The fuel gas for all other combustion sources constructed, modified or reconstructed prior to April 30, 2007, shall be limited to no more than 10 grains total sulfur per 100 dscf (160 ppmv) on a three hour rolling average. **(11/14)**

D. The fuel gas for all other combustion sources constructed, modified or reconstructed on or after April 30, 2007, shall be limited to no more than 10 grains total sulfur per 100 dscf (160 ppmv) on a three hour rolling average and to no more than 3.70 grains per 100 dscf (60 ppmv) on a 365-day rolling average.

E. Following heater modifications associated with the coker project, PI-1 dated February 27, 2017, the fuel gas for the following heaters shall be limited to no more than 5.56 grains total sulfur per 100 dscf (90 ppmvd) on a one hour rolling average and to no more than 1.88 grains per 100 dscf (30 ppmvd) on a 365-day rolling average. Heaters may fire fuel gas with a sulfur content no more than 10 grains total sulfur per 100 dscf (160 ppmv) on a one hour average provided it does not exceed a combined total for individual heaters of 200 hours per year on a rolling twelve-month basis. **(09/18)**

FIN	EPN
844-H1	E-01-844
844-H2	E-02-844
AVU-146-H1	E-01-146
AVU-146-H2	E-02-146
147-F-1100	E-01-147
GFU-241-H1	E-01-241
GFU-242-H	E-01-242
GFU-243-H	E-01-243
GFU-244-H1	E-01-244
GFU-245-H1	E-01-245
GFU-246-H1	E-01-246
HFAU-443-H	E-01-443
DCU-843-H1	E-01-843
DCU-843-H2	E-02-843
DCU-843-H3	E-03-843
HCU-942-H1	E-01-942
HCU-943-H1	E-01-943
HCU-943	E-02-943
CRU1344H1	E-01-1344

FIN	EPN
CRU1344H2	E-02-1344
CRU1344H3	E-03-1344

F. The sulfur content and Higher Heating Value (HHV) of the fuel gas for the heaters and boilers shall be monitored as follows.

(1) A continuous monitor shall be installed at the fuel gas mix drum in the fuel feed line header for all heaters and boilers to continuously monitor and record the gas for H_2S content of the fuel. The instrument shall be installed according to the specifications set out in 40 CFR § 60.105.

The fuel gas from the fuel gas mix drum shall be sampled once per week to determine HHV. Test results from the fuel supplier may be used to satisfy this requirement for purchased fuel gas supplies.

Process fuel gases that are not routed to the fuel gas mix drum shall be monitored for H_2S content and HHV prior to being used as fuel.

On a monthly basis, the monthly average and 12 month rolling average fuel sulfur content and HHV shall be determined and records maintained. Upon request by the Executive Director of the Texas Commission of Environmental Quality (TCEQ) or any local air pollution control program having jurisdiction, the holder of this permit shall provide a sample and/or analysis of the fuel, or shall allow the air pollution control agency representatives to obtain a sample for analysis. (**09/18**)

(2) As an exception to Paragraph A of this condition, the fuel gas stream from Chevron/CPC's EU1544, routed to Premcor's Boiler House 16, and identified as EU1544, shall be monitored upstream from Boiler House 16 for H_2S content at least once per calendar month. This exception shall remain in effect for as long as the composition and the level of H_2S treatment of this gas stream remains as described in Table 4 of the permit modification application dated November 2000. **(07/08)**

35. For boilers and heaters with maximum firing rates less than 40 MMBtu/hr, the permit holder shall install and operate totalizing fuel flow meters to measure the fuel gas usage for each boiler and heater and fuel usage for each shall be recorded daily.

For boilers and heaters with maximum firing rates greater than 40 MMBtu/hr, the permit holder shall install and operate totalizing fuel flow meters to measure the fuel gas usage for each boiler and heater and fuel usage for each shall be recorded hourly.

Each totalizing fuel flow meter shall be calibrated at a frequency in accordance with the manufacturer's specifications or at least annually, whichever is more frequent, and shall be accurate to within 5 percent of the unit's maximum flow.

Quality-assured (or valid) data must be generated when the boiler or heater is operating. Loss of valid data due to periods of monitor break down, out-of-control operation (producing inaccurate data), repair, maintenance, or calibration may be exempted provided it does not exceed 5 percent of the time (in minutes) that the boiler or heater operated over the previous rolling 12-month period. The measurements missed shall be estimated using engineering judgment and the methods used recorded. **(07/08)**

On a monthly basis, the monthly average and 12 month rolling average fuel usage for each boiler and heater shall be determined and records maintained. (**09/18**)

HF Emission Control

36. The HF detection paint shall be used on all potential fugitive sources and possible leak sites. After a HF leak has impacted and become visible on the HF detection paint, the permit holder shall clean and repaint the affected area no later than 30 days after repairing the HF leak. If there is a problem with HF sensitive paint availability, the holder of this permit shall notify the TCEQ Beaumont Regional Office and request additional time for painting or request alternate leak detection methods pending availability of the HF sensitive paint. **(02/08)**

37. In the event of an HF release which may have the potential for off-site impacts, the holder of this permit shall implement the procedures outlined in the emergency contingency and response plans.

38. There shall be no overhead work in the HF process unit where equipment is being lifted over unprotected vessels or lines without first completing a safe work checklist in accordance with Occupational Safety and Health Administration Process Safety Management rules. The safe work checklist shall be used to ensure that every effort is made to minimize the potential for an accident that would result in loss of integrity of HF-containing equipment.

Delayed Coking Units

39. The following operational restrictions apply to the delayed coking units (EPNs CSV843 and CSV844) (**09/18**)

    A. No more than one coke drum from each coker may be opened to the atmosphere to depressurize, drain, and remove coke per hour.

    B. No more than 2232 drum cycles from coker 843 and 1291 drum cycles from coker 844 (i.e., drum depressurizations to atmosphere and drum openings) may occur per year on a rolling twelve-month average.

    C. Prior to depressuring a drum to atmosphere, the drum shall be routed to a closed blowdown system which recovers and directs the gas flows to the coker fractionator or to the fuel gas system.

    D. The permit holder shall install, operate, calibrate, and maintain a pressure monitor capable of determining the coke drum vessel pressure for each coke drum. The monitor shall be calibrated annually or have a calibration check performed on an annual basis to meet an accuracy ±0.5 psig.

    E. On and after January 30, 2019 coke drums from coker 843 shall not be depressurized and drained to atmosphere until the drum reaches a top or blowdown pressure of 3.50 psig based on a five minute average and 2.4 psig or less based on a 60 event rolling average with a 5 minute average per event. Prior to January 30, 2019 coke drums from coker 843 shall not be depressured and drained to atmosphere until the drum reaches a top or blowdown pressure of 14 psig or less based on a 5 minute average.

    F. Coke drums from coker 844 shall not be depressurized and drained to atmosphere until the drum reaches a top or blowdown pressure of 2.0 psig or less based on a 5 minute average.

    G. The permit holder shall maintain a record of the number of cycles for each coker for the previous calendar month and the past consecutive 12 month period. Records of the coke drum pressure prior to depressurizing to atmosphere for each event shall be maintained to verify compliance with this condition.

Coke Handling, Storage, and Loading

40. Cutting of coke from the coking drums at the delayed coking complex shall be accomplished by the use of high-pressure water. Coke shall be shipped only by railcar, truck, or marine vessel. **(7/03)**

41. The coke transfer rate from coker 843 upstream of the active stockpile shall not exceed 2,000 tons per hour (tph). The coke transfer rate downstream of the active stockpile shall not exceed 3,500 tph. Upon start-up of the coker project, PI-1 dated February 27, 2017, the coke transfer rate from cokers 843 and 844 upstream of the active stockpile shall not exceed 500 tph each. Rates of hourly and annual coke production and loading shall be recorded. **(11/18)**

42. The footprint of the active coke stockpile shall not exceed 21.0 acres. Permanent markers shall be installed to outline the stockpile perimeter. **(02/08)**

43. All coke handling conveyors and loading shall be equipped with covers and sides (partially enclosed). **(07/03)**

44. Stationary water sprays shall be installed throughout the coke storage and handling facility as necessary to ensure that the minimum coke moisture contents specified in Special Condition Nos. 46 and 47 are maintained to achieve control of coke dust emissions. These water sprays shall be maintained in an operable condition at all times and shall be operated prior to and following all loading and unloading operations and at other times as necessary, to ensure that the minimum coke moisture contents specified in Special Condition Nos. 46 and 47 are maintained to achieve control of coke dust emissions.

    An observer shall verify using EPA Test Method 22 that there are no visible coke emissions upon resumption of loading if marine vessel loading has been interrupted for more than two hours. The results of this observation shall be recorded. **(02/08)**

45. The coke conveyors shall not be left with the belt stationary (idle, not transferring coke) and loaded for more than two consecutive hours. **(02/08)**

46. Soft Coke Moisture Sampling Requirements. Soft coke is defined for this purpose as coke with a Hardgrove Index of greater than 45. When this permit condition is in effect, the permit holder shall take coke samples for moisture analysis as follows. This permit condition becomes effective when, according to Special Condition No. 47A, hard coke is not being handled at this site.

    A. The permit holder shall take samples of the coke at transfer point CO-3 when loading coke. The permit holder shall take samples of the coke at the coke stockpiles. Sampling at the coke stockpiles shall include at least one sample per 0.7-acre each sampling period. The permit holder shall maintain a map of the coke stockpile footprint indicating each 0.7-acre sample zone. The zones containing coke and the sample locations should be recorded on a map for each sample period. Samples shall be taken to ensure adequate coverage of all areas of the coke piles and shall be taken within one hour prior to the scheduled application of water. Only those sample zones covered by the coke pile need to be sampled.

    B. The samples shall be analyzed for moisture content using American Society for Testing and Materials (ASTM) methods as agreed upon by the TCEQ Beaumont Regional Office.

    C. The coke stockpile zones shall be sampled every other day for 30 consecutive days during a period from January through March and every other day for 30 consecutive days during a period from June through August. There will be a total of 15 sampling events during each 30-day period.

    D. The coke stockpile zones shall be sampled once a week during those time periods when the sampling in paragraph C of this condition is not required.

E. The permit holder will ensure that a minimum coke moisture content of 8 percent (by weight) is maintained. If two consecutive samples at a sampling point have a moisture content less than 8 percent, additional daily coke samples must be taken at that sample point. The sample point may return to the normal sampling routine after seven consecutive daily samples meet the 8 percent moisture requirement. (**09/18**)

F. Satisfactory sampling exception. The permit holder may obtain an exception to the sampling frequencies mandated in paragraphs C and D of this condition. This exception is subject to the following:

(1) The permit holder may request in writing to the TCEQ Beaumont Regional Office that sampling may be reduced in frequency to a monthly sampling period after the permit holder has completed a year of satisfactory sampling. This submittal must also include a continuous compliance plan for the coke handling facilities.

(2) The satisfactory sampling results referenced above are defined as at least 95 percent of the samples at each sampling point exceeding 8 percent moisture. Each coke pile sampling zone (0.7 acre) is considered a sample point.

G. The results and location of all sampling shall be recorded. The results will be collated in a monthly format showing the number of samples below 8 percent moisture content, total number of samples taken, and the percentage of samples below 8 percent moisture content. **(02/08)**

47. Hard Coke Moisture Sampling Requirements. Hard coke is defined for this purpose as coke with a Hardgrove Index equal to or less than 45. When this permit condition is in effect, the permit holder shall take coke samples for moisture analysis as follows. This permit condition is in effect unless hard coke is not being handled at this site, according to Paragraph A of this condition.

A. At least once per week, the coke shall be sampled and the Hardgrove Index measured. The coke handled at this site shall be considered to be hard coke unless the Hardgrove Index weekly average exceeds 45. Should this exceedance occur, the permit holder may continue to operate under this permit condition if the subsequent weekly average Hardgrove Index equals or is less than 45.

B. When loading coke into marine vessels, the coke moisture content shall be measured by taking samples of the coke at transfer point CO-4. When loading directly into trucks and/or railcars, the coke moisture content shall be measured by sampling directly from trucks and/or railcars.

C. The samples shall be analyzed for moisture content using ASTM methods as agreed upon by the TCEQ Beaumont Regional Office.

D. The permit holder will ensure that a minimum coke moisture content of 4.8 percent (by weight) is maintained. Compliance with this condition will be demonstrated if at least 90 percent of the moisture samples equal or exceed 4.8 percent. A minimum of ten samples must be taken in accordance with Paragraph B of this condition to determine compliance.

E. The results and location of all sampling shall be recorded. The results will be collated in a monthly format showing the number of samples below 4.8 percent moisture content, total number of samples taken, and the percentage of samples below 4.8 percent moisture content.

F. The permit holder may choose to cease to operate under this permit condition at any time. When doing so, the permit holder may cease measuring the coke Hardgrove Index. After doing so, the permit holder may return to operation under this permit condition by measuring the coke Hardgrove Index and demonstrating that this results in an average of any two consecutive measurements being equal to or less than 45. **(02/02)**

48. Upon the request of the Executive Director of the TCEQ, the holder of this permit shall perform high volume air sampling, one and/or three-hour tests, for net ground level concentrations of total particulate matter (PM). Each test shall consist of at least one upwind and one downwind sample taken simultaneously. The test(s) shall be performed during normal operation of the facility. High volume sampling shall be performed in accordance with Chapter 11 PM of the TCEQ Sampling Procedures Manual. **(07/03)**

49. No visible coke emissions as determined using EPA Test Method 22 shall leave the property. **(01/07)**

    The holder of this permit shall conduct a weekly visible fugitive emissions determination to demonstrate compliance with the visible fugitive emissions limitation specified in this permit. This visible fugitive emissions determination shall be performed: 1) during normal plant operations, 2) for a minimum of six minutes, 3) approximately perpendicular to plume direction, 4) with the sun behind the observer (to the extent practicable), 5) at least 15 feet, but not more than 0.25 mile, from the plume, and 6) in accordance with EPA 40 CFR Part 60, Appendix A, Test Method 22, except where stated otherwise in this condition. If visible fugitive emissions are observed leaving the property, the owner or operator shall take immediate action (as appropriate) to eliminate the excessive visible fugitive emissions. The corrective action shall be documented within 24 business hours of completion. (**09/18**)

Initial and Periodic Stack Sampling

50. The holder of this permit shall perform stack sampling and other testing, as required, to establish the actual pattern and quantities of air contaminants being emitted into the atmosphere from the following sources:

    - The FCCU Wet Gas Scrubber Stack (EPN E-01-WGS);
    - The TGI Stacks of the SRUs 543, 544, 545, and 546 (EPNs E-01-SCOT, E-02-SCOT, E-03-SCOT, and E-04-SCOT, respectively);
    - All boilers, heaters, etc., with firing rates of 40 MMBtu/hr or greater;
    - The Gasoline Hydrotreater (EPN E-01-245); one-time stack test;
    - Heaters DCU 844 coker Furnace #1 (EPN E-01-844) and DCU 844 coker Furnace #2 (EPN E-02-844); and **(09/18)**
    - The TGI Stack of the SRU547 (EPN E-05-SCOT) **(09/18)**

    The holder of this permit is responsible for providing sampling and testing facilities and conducting the sampling and testing operations at his expense.

    Sampling shall be conducted in accordance with the appropriate procedures of the TCEQ Sampling Procedures Manual and the EPA Reference Methods.

    Requests to waive testing for any pollutant specified in this condition shall be submitted to the TCEQ Office of Permitting and Registration, Air Permits Division. Test waivers and alternate/equivalent procedure proposals for 40 CFR Part 60 testing which must have EPA approval shall be submitted to the TCEQ Beaumont Regional Director.

A. The TCEQ Beaumont Regional Office shall be contacted as soon as testing is scheduled, but not less than 45 days prior to sampling to schedule a pretest meeting.

The notice shall include:

(1) Date for pretest meeting.

(2) Date sampling will occur.

(3) Name of firm conducting sampling.

(4) Type of sampling equipment to be used.

(5) Method or procedure to be used in sampling.

The purpose of the pretest meeting is to review the necessary sampling and testing procedures, to provide the proper data forms for recording pertinent data, and to review the format procedures for the test reports. The TCEQ Beaumont Regional Director must approve any deviation from specified sampling procedures.

B. Air contaminants emitted from the listed sources to be tested for include (but are not limited to) the following:

FCCU WGS:	NO_x, CO, SO_2, PM*, VOC, sulfuric acid, and O_2
SRU TGIs:	SO_2, H_2S, NO_x, CO, PM**, and O_2
Boilers and Heaters:	NO_x, CO, VOC, PM**, and O_2.

* particulate matter (PM), includes condensable and non-condensable sample.
** Testing for PM applies to EPNs E-05-SCOT, E-01-844, E-02-844, and E-02-943 only and includes PM

C. Sampling shall occur as follows:

(1) Within 90 days after the completion of modifications to a specific unit as identified in the permit amendment application, PI-1, dated January 9, 1996.

(2) Within 90 days of December 16, 1996 if a specific unit was not modified.

(3) Within 90 days after the completion of construction of or modifications to a specific unit as identified in the permit amendment applications, PI-1, dated April 30, 1998, December 5, 2003, January 31, 2006, January 31, 2008, and March 25, 2008.

(4) At other such times as determined necessary to verify compliance with the emissions cap as required by the TCEQ Beaumont Regional Director or the TCEQ Executive Director.

(5) Boilers 6, 7, 34, 35, 42, and 43 shall be stack tested and have relative accuracy test audits (RATA) testing performed on them no later than December 31, 2002.

(6) Upon completing construction of Heaters DCU 844 coker Furnace #1 (EPN E-01-844), DCU 844 coker Furnace #2 (EPN E-02-844) and SRU547 (EPN E-05-SCOT) and modifications to Hydrocracker Unit 943 Fractionator Feed Furnace (EPN E-02-943), Heater 146-H101 (EPN E-01-146), and Heater AVU No. 146 H-102A and H-102B (EPN E-02-146) sampling shall be performed to establish the actual pattern and quantities of air contaminants being emitted into the atmosphere from the units. Sampling shall occur within 60 days after achieving the maximum operating rate, but no later than 180 days after initial start-up of the facilities and at such other times as may be required by the TCEQ Executive Director. Requests for additional time to perform sampling shall be submitted to the appropriate regional office. **(09/18)**

(7) Every five years at those units which are not equipped with a CEMS for the pollutants specified in Paragraph B of this condition, except for VOC testing if the source has an installed CO CEMS.

Sampling of a heater and boiler emission points may be delayed if necessary to perform the sampling for that emission point in conjunction with the installation of a continuous monitoring system required by Special Condition No. 53. Requests for additional time to perform sampling shall be submitted to the TCEQ Beaumont Regional Office.

D. The EPN being tested shall operate at maximum production or firing rates during stack emission testing. Primary operating parameters that enable determination of a production rate shall be monitored and recorded during the stack test. These parameters are to be determined at the pretest meeting. If the EPN is unable to operate at maximum rates during testing, then future production rates may be limited to the rates established during testing. Additional stack testing may be required if the firing rate exceeds the tested firing rate by more than 10 percent (additional testing will not be required if the EPN is equipped with a CEMS).

E. A copy of the final sampling report shall be forwarded to the TCEQ within 60 days after sampling is completed. Sampling reports shall comply with the attached provisions of Chapter 14 of the TCEQ Sampling Procedures Manual. The reports shall be distributed as follows:

One copy to the TCEQ Beaumont Regional Office. **(12/10)**

51. The permit holder shall perform stack sampling and other testing as required to establish the actual pattern and quantities of air contaminants being emitted into the atmosphere from the Marine Vapor Combustors (FINS E-MC-24 and E-MC-25, EPN E-MC-24-25) to demonstrate compliance with the MAERT. The permit holder is responsible for providing sampling and testing facilities and conducting the sampling and testing operations at his expense. Sampling shall be conducted in accordance with the appropriate procedures of the Texas Commission on Environmental Quality (TCEQ) Sampling Procedures Manual and the U.S. Environmental Protection Agency (EPA) Reference Methods. **(09/18)**

Requests to waive testing for any pollutant specified in this condition shall be submitted to the TCEQ Office of Air, Air Permits Division. Test waivers and alternate/equivalent procedure proposals for Title 40 Code of Federal Regulation Part 60 (40 CFR Part 60) testing which must have EPA approval shall be submitted to the TCEQ Regional Director.

A. The appropriate TCEQ Regional Office shall be notified not less than 45 days prior to sampling. The notice shall include:

(1) Proposed date for pretest meeting.

(2) Date sampling will occur.

(3) Name of firm conducting sampling.

(4) Type of sampling equipment to be used.

(5) Method or procedure to be used in sampling.

(6) Description of any proposed deviation from the sampling procedures specified in this permit or TCEQ/EPA sampling procedures.

(7) Procedure/parameters to be used to determine worst case emissions during the sampling period.

The purpose of the pretest meeting is to review the necessary sampling and testing procedures, to provide the proper data forms for recording pertinent data, and to review the

format procedures for the test reports. The TCEQ Regional Director must approve any deviation from specified sampling procedures.

B. Air contaminants emitted from the listed sources to be tested for include (but are not limited to) NO_x, VOC, CO and O_2.

C. Sampling shall occur within 180 days after the permit issued dated April 16, 2018 and at such other times as may be required by the TCEQ Executive Director. Requests for additional time to perform sampling shall be submitted to the appropriate regional office.

D. Marine loading shall be at the maximum authorized controlled loading rate during stack emission testing of each marine vapor combustor. These conditions/parameters and any other primary operating parameters that affect the emission rate shall be monitored and recorded during the stack test. Any additional parameters shall be determined at the pretest meeting and shall be stated in the sampling report. Permit conditions and parameter limits may be waived during stack testing performed under this condition if the proposed condition/parameter range is identified in the test notice specified in paragraph A and accepted by the TCEQ Regional Office. Permit allowable emissions and emission control requirements are not waived and still apply during stack testing period.

During subsequent operations, if the controlled loading rate is greater than that recorded during the test period, stack sampling shall be performed at the new operating conditions within 120 days. This sampling may be waived by the TCEQ Air Section Manager for the region.

E. Copies of the final sampling report shall be forwarded to the offices below within 60 days after sampling is completed. Sampling reports shall comply with the attached provisions entitled “Chapter 14, Contents of Sampling Reports” of the TCEQ Sampling Procedures Manual. The reports shall be distributed as follows:

One copy to the appropriate TCEQ Regional Office.

Continuous Emission Monitoring

52. The holder of this permit shall install, calibrate, and maintain a CEMS to measure and record the in-stack concentrations of the following compounds from the indicated sources:

A. FCCU Wet Gas Scrubber (EPN E-01-WGS): SO_2, NO_x, CO, and O_2.

B. The TGI stacks of the SRUs 543, 544, 545, and 546 (EPNs E-01-SCOT, E-02-SCOT, E-03-SCOT, and E-04-SCOT, respectively): SO_2, H_2S, and O_2.

C. For boilers and heaters with maximum firing rates greater than 100 MMBtu/hr: NO_x, CO, and O_2.

All monitoring systems shall be installed and operational by December 16, 1999 or within two months after the completion of modifications to or construction of a specific unit, whichever is later. The SO_2 and O_2 CEMS for SRU 544 TGI Stack (EPN E-02-SCOT) shall be operational as of January 1999. The CEMS for Boilers 6, 7, 34, 35, 41, 42, and 43 shall be operational by October 31, 2002. The H_2S CEMS for SRU 543 and 544 TGI Stacks (EPNs E-01-SCOT and E-02-SCOT, respectively) shall be operational as of June 30, 2002. **(12/10)**

D. Coker heater vents EPNs E-01-844 and E-02-844: NO_x, CO, and O_2 **(09/18)**

E. The TGI Stack of the SRU547 (EPN E-05-SCOT): SO_2, H_2S, and O_2. **(09/18)**

53. All CEMS monitoring systems shall meet the following requirements:

A. The CEMS shall meet the design and performance specifications, pass the field tests, and meet the installation requirements and the data analysis and reporting requirements specified in the applicable Performance Specification Nos. 1 through 9, 40 CFR Part 60, Appendix B. If there are no applicable performance specifications in 40 CFR Part 60, Appendix B, contact the TCEQ Office of Permitting and Registration, Air Permits Division for requirements to be met.

B. Paragraph (1) below applies to sources subject to the quality-assurance requirements of 40 CFR Part 60, Appendix F, Paragraph (2) applies to all other sources:

(1) The permit holder shall assure that the CEMS meets the applicable quality-assurance requirements specified in 40 CFR Part 60, Appendix F, Procedure 1. Relative accuracy exceedances, as specified in 40 CFR Part 60, Appendix F, § 5.2.3 and any CEMS downtime shall be reported to the TCEQ Beaumont Regional Director and necessary corrective action shall be taken. Supplemental stack concentration measurements may be required at the discretion of the TCEQ Beaumont Regional Director.

(2) The system shall be zeroed and spanned daily, and corrective action taken when the 24-hour span drift exceeds two times the amounts specified in the applicable Performance Specification Nos. 1 through 9, 40 CFR Part 60, Appendix B, or as specified by the TCEQ if not specified in Appendix B. Zero and span is not required on weekends and plant holidays if instrument technicians are not normally scheduled on those days.

Each monitor shall be quality-assured at least quarterly using Cylinder Gas Audits (CGA) in accordance with 40 CFR Part 60, Appendix F, Procedure 1, § 5.1.2, with the following exception: a RATA is not required once every four quarters (i.e., four successive quarterly CGA may be conducted). An equivalent quality-assurance method approved by the TCEQ may also be used. Successive quarterly audits shall occur no closer than two months.

All CGA exceedances of ±15 percent accuracy indicate that the CEMS is out of control.

C. The CEMS monitoring data shall be reduced to hourly average concentrations at least once everyday, using a minimum of four equally-spaced data points from each one-hour period. The individual average concentrations shall be reduced to units of lbs/hr at least once every week as follows:

The measured hourly average concentration from the CEMS shall be multiplied by the flow rate measured during the latest stack test performed in accordance with Special Condition No. 50 to determine the hourly emission rate or by using "F" Factors for Various Fuels under 40 CFR Part 60, Appendix A, Method 19.

D. All CEMS monitoring data and quality-assurance data shall be maintained by the source. The data from the CEMS shall, at the discretion of the TCEQ, be used to determine compliance with the conditions of this permit.

E. The TCEQ Beaumont Regional Office shall be notified at least 30 days prior to any required RATA in order to provide them the opportunity to observe the testing.

F. Quality-assured (or valid) data must be generated when the sources with installed CEMS are operating except during the performance of a daily zero and span check. Loss of valid data due to periods of monitor break down, out-of-control operation (producing inaccurate data), repair, maintenance, or calibration may be exempted provided it does not exceed 5 percent of the time (in minutes) that the sources with installed CEMS operated over the previous rolling 12-month period. The measurements missed shall be estimated using engineering judgement and the methods used recorded. Options to increase system reliability to an acceptable value, including a redundant CEMS, may be required by the TCEQ Beaumont Regional Director. **(02/08)**

G. This paragraph applies to the NOx, SO2, O2 and CO CEMS listed in Special Condition No. 52.A. and NOx CEMS listed in Special Condition Nos. 32.D and 52.D. In addition to the requirements of Special Condition No.53.A-F., the CEMS shall be installed, certified, calibrated, maintained and operated in accordance with the provisions of 40 CFR §60.13 which are applicable only to CEMs (excluding those provisions applicable only to continuous opacity monitoring systems) and Part 60, Appendices A and F, and the applicable performance specification test of 40 CFR Part 60, Appendix B. With respect to 40 CFR Part 60 Appendix F, in lieu of the requirements of 40 CFR Part 60, Appendix F §§5.1.1, 5.1.3 and 5.1.4, the source must conduct either a RAA or a RATA on each CEMS at least once every three (3) years. The source must also conduct CGA each calendar quarter during which a RAA or a RATA is not performed. **(09/18)**

54. The permit holder shall continuously monitor ammonia emissions from EPNs E-01-844, E-02-844, and E-02-943 using one of the following methods: **(09/18)**

A. Install and operate two NO_x CEMS, one located upstream of the Selective Catalytic Reduction (SCR) system and the other located downstream of the SCR system, which are used in association with NH_3 injection rate and the following calculation procedure to estimate NH_3 slip.

NH_3 slip, ppmvd = (a - (b x c / 1,000,000)) x 1,000,000 / b) x d

where:

a = ammonia injection rate (lb/hr)/17 (lb/lb-mole);

b = dry exhaust gas flow rate (lb/hr)/29 (lb/lb-mole);

c = change in measured NO_x concentration, ppmvd, across catalyst; and

d = appropriate correction factor.

The correction factor shall be derived during compliance testing by comparing the measured and calculated ammonia slip. The ammonia inject rate and exhaust gas flow rate shall be recorded at least every 15 minutes and be recorded as hourly averages. Each flow monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, or at least annually, whichever is more frequent, and shall be accurate to within 2 percent of span or 5 percent of the design value.

B. Install and operate a dual stream system of NO_x CEMS at the exit of the SCR system. One of the exhaust streams would be routed, in an unconverted state, to one NO_x CEMS and the other exhaust stream would be routed through a NH_3 converter to convert NH_3 to NO_x and then to a second NO_x CEMS. The NH_3 slip concentration shall be calculated from the delta between the two NO_x CEMS readings (converted and unconverted).

C. Install an ammonia CEMS.

All CEMS specified in this condition must meet the requirements of Special Condition No. 53. Quality-assured (or valid) data must be generated when gas is directed to the SCR system. Loss of valid data due to periods of monitor break down, out-of-control operation (producing

inaccurate data), repair, maintenance, or calibration may be exempted provided it does not exceed 5 percent of the time that gas is directed to the SCR system over the previous rolling 12-month period. The measurements missed shall be estimated using engineering judgment and the methods used recorded. **(07/08)**

Fugitive Emission Monitoring Programs

55. Piping, Valves, Pumps, and Compressors in H_2S or Ammonia (NH_3) Service **(07/08)**

The following is required for all process streams with greater than 1 percent H_2S or NH_3 by weight.

A. Audio, olfactory, and visual checks for H_2S leaks within the sulfur recovery complexes operating areas shall be made at least twice per shift. . (**09/18**)

Audio, olfactory, and visual checks for H_2S leaks within the operating area of the Amine Treating Unit represented in the permit amendment application dated March 25, 2008, shall be made once per shift.

Audio, olfactory, and visual checks for H_2S leaks within the operating area of Coker 844 represented in the permit amendment application dated February 27, 2017, shall be made once per shift. (**09/18**)

Audio, olfactory, and visual checks for NH_3 leaks within the NH_3 handling system for the SCR Units represented in the permit amendment applications dated January 31, 2008, March 25, 2008, and February 27, 2017 shall be made once per shift. (**09/18**)

Audio, olfactory, and visual checks for NH_3 leaks within the operating area of the Sour Water Stripper Unit represented in the permit amendment application March 25, 2008, shall be made once per shift.

B. Immediately, but no later than one-hour upon detection of a leak, plant personnel shall take the following actions:

(1) Stop the leak by taking the equipment out of service or bypass the equipment so that it is no longer in service,

(2) Isolate the leak; or,

(3) Commence repair or replacement of the leaking component.

Records shall be maintained of the time leaks were detected and all repairs and replacements made due to leaks.

56. Piping, Valves, Pumps, and Compressors in Hydrogen Fluoride (HF) Service **(02/08)**

The following requirements apply to any process streams with greater than 1 weight percent HF.

A. Audio, olfactory, and visual checks of the HF detection paint for HF leaks within the operating area shall be made every four hours.

B. Immediately, but no later than one-hour upon detection of a leak, plant personnel shall take the following actions:

(1) Stop the leak by taking the equipment out of service or bypass the equipment so that it is no longer in service.

(2) Isolate the leak.

(3) Commence repair or replacement of the leaking component.

C. The above actions shall be taken immediately, but no later than one-hour into the next day shift, upon detection of a leak by night shift personnel.

D. Records shall be maintained of the time leaks were detected and all repairs and replacements made due to leaks.

57. Piping, Valves, Flanges, Pumps, and Compressors in VOC Service - 28 VHP

Except as may be provided for in the special conditions of this permit, the following requirements apply to the above-referenced equipment unless monitored per Special Condition 58.

A. The requirements of paragraphs F and G shall not apply (1) where the Volatile Organic Compound (VOC) has an aggregate partial pressure or vapor pressure of less than 0.044 pounds per square inch, absolute (psia) at 68°F or (2) operating pressure is at least 5 kilopascals (0.725 psi) below ambient pressure. Equipment excluded from this condition shall be identified in a list or by one of the methods described below to be made readily available upon request.

The exempted components may be identified by one or more of the following methods:

(1) piping and instrumentation diagram (PID);

(2) a written or electronic database or electronic file;

(3) color coding;

(4) a form of weatherproof identification; or

(5) designation of exempted process unit boundaries.

B. Construction of new and reworked piping, valves, pump systems, and compressor systems shall conform to applicable American National Standards Institute (ANSI), American Petroleum Institute (API), American Society of Mechanical Engineers (ASME), or equivalent codes.

C. New and reworked underground process pipelines shall contain no buried valves such that fugitive emission monitoring is rendered impractical. New and reworked buried connectors shall be welded.

D. To the extent that good engineering practice will permit, new and reworked valves and piping connections shall be so located to be reasonably accessible for leak-checking during plant operation. Difficult-to-monitor and unsafe-to-monitor valves, as defined by Title 30 Texas Administrative Code Chapter 115 (30 TAC Chapter 115), shall be identified in a list to be made readily available upon request. The difficult-to-monitor and unsafe-to-monitor valves may be identified by one or more of the methods described in subparagraph A above. If an unsafe to monitor component is not considered safe to monitor within a calendar year, then it shall be monitored as soon as possible during safe to monitor times. A difficult to monitor component for which quarterly monitoring is specified may instead be monitored annually.

E. New and reworked piping connections shall be welded or flanged. Screwed connections are permissible only on piping smaller than two-inch diameter. Gas or hydraulic testing of the new and reworked piping connections at no less than operating pressure shall be performed prior to returning the components to service or they shall be monitored for leaks using an approved gas analyzer within 15 days of the components being returned to service. Adjustments shall be made as necessary to obtain leak-free performance. Connectors shall be inspected by visual, audible, and/or olfactory means at least weekly by operating personnel walk-through.

Each open-ended valve or line shall be equipped with an appropriately sized cap, blind flange, plug, or a second valve to seal the line. Except during sampling, both valves shall be closed. If the isolation of equipment for hot work or the removal of a component for repair or replacement results in an open ended line or valve, it is exempt from the requirement to install a cap, blind flange, plug, or second valve for 72 hours. If the repair or replacement is not completed within 72 hours, the permit holder must complete either of the following actions within that time period;

(1) a cap, blind flange, plug, or second valve must be installed on the line or valve; or

(2) the open-ended valve or line shall be monitored once for leaks above background for a plant or unit turnaround lasting up to 45 days with an approved gas analyzer and the results recorded. For all other situations, the open-ended valve or line shall be monitored once within the 72 hour period following the creation of the open ended line and monthly thereafter with an approved gas analyzer and the results recorded. For turnarounds and all other situations, leaks are indicated by readings of 500 ppmv and must be repaired within 24 hours or a cap, blind flange, plug, or second valve must be installed on the line or valve.

F. Accessible valves shall be monitored by leak checking for fugitive emissions at least quarterly using an approved gas analyzer. Sealless/leakless valves (including, but not limited to, welded bonnet bellows and diaphragm valves) and relief valves equipped with a rupture disc upstream or venting to a control device are not required to be monitored. If a relief valve is equipped with rupture disc, a pressure-sensing device shall be installed between the relief valve and rupture disc to monitor disc integrity.

A check of the reading of the pressure-sensing device to verify disc integrity shall be performed at least quarterly and recorded in the unit log or equivalent. Pressure-sensing devices that are continuously monitored with alarms are exempt from recordkeeping requirements specified in this paragraph. All leaking discs shall be replaced at the earliest opportunity but no later than the next process shutdown.

The gas analyzer shall conform to requirements listed in Method 21 of 40 CFR part 60, appendix A. The gas analyzer shall be calibrated with methane. In addition, the response factor of the instrument for a specific VOC of interest shall be determined and meet the requirements of Section 8 of Method 21. If a mixture of VOCs is being monitored, the response factor shall be calculated for the average composition of the process fluid. A calculated average is not required when all of the compounds in the mixture have a response factor less than 10 using methane. If a response factor less than 10 cannot be achieved using methane, then the instrument may be calibrated with one of the VOC to be measured or any other VOC so long as the instrument has a response factor of less than 10 for each of the VOC to be measured.

Replacements for leaking components shall be re-monitored within 15 days of being placed back into VOC service.

G. Except as may be provided for in the special conditions of this permit, all pump, compressor, and agitator seals shall be monitored with an approved gas analyzer at least quarterly or be equipped with a shaft sealing system that prevents or detects emissions of VOC from the seal. Seal systems designed and operated to prevent emissions or seals equipped with an automatic seal failure detection and alarm system need not be monitored. These seal systems may include (but are not limited to) dual pump seals with barrier fluid at higher pressure than process pressure, seals degassing to vent control systems kept in good working order, or seals equipped with an automatic seal failure detection and alarm system. Submerged pumps or sealless pumps (including, but not limited to, diaphragm, canned, or magnetic-driven pumps) may be used to satisfy the requirements of this condition and need not be monitored.

H. Damaged or leaking valves or connectors found to be emitting VOC in excess of 500 parts per million by volume (ppmv) or found by visual inspection to be leaking (e.g., dripping process fluids) shall be tagged and replaced or repaired. Damaged or leaking pump, compressor, and agitator seals found to be emitting VOC in excess of 2,000 ppmv or found by visual inspection to be leaking (e.g., dripping process fluids) shall be tagged and replaced or repaired. A first attempt to repair the leak must be made within 5 days and a record of the attempt shall be maintained.

I. A leaking component shall be repaired as soon as practicable but no later than 15 days after the leak is found. If the repair of a component would require a unit shutdown that would create more emissions than the repair would eliminate, the repair may be delayed until the next scheduled shutdown. All leaking components which cannot be repaired until a scheduled shutdown shall be identified for such repair by tagging within 15 days of the detection of the leak. A listing of all components that qualify for delay of repair shall be maintained on a delay of repair list. The cumulative daily emissions from all components on the delay of repair list shall be estimated by multiplying by 24 the mass emission rate for each component calculated in accordance with the instructions in 30 TAC 115.782 (c)(1)(B)(i)(II). The calculations of the cumulative daily emissions from all components on the delay of repair list shall be updated within ten days of when the latest leaking component is added to the delay of repair list. When the cumulative daily emission rate of all components on the delay of repair list times the number of days until the next scheduled unit shutdown is equal to or exceeds the total emissions from a unit shutdown as calculated in accordance with 30 TAC 115.782 (c)(1)(B)(i)(I), the TCEQ Regional Manager and any local programs shall be notified and may require early unit shutdown or other appropriate action based on the number and severity of tagged leaks awaiting shutdown. This notification shall be made within 15 days of making this determination.

J. Records of repairs shall include date of repairs, repair results, justification for delay of repairs, and corrective actions taken for all components. Records of instrument monitoring shall indicate dates and times, test methods, and instrument readings. The instrument monitoring record shall include the time that monitoring took place for no less than 95% of the instrument readings recorded. Records of physical inspections shall be noted in the operator's log or equivalent.

K. Alternative monitoring frequency schedules of 30 TAC '' 115.352 - 115.359 or National Emission Standards for Organic Hazardous Air Pollutants, 40 CFR Part 63, Subpart H, may be used in lieu of Items F through G of this condition.

L. Compliance with the requirements of this condition does not assure compliance with requirements of 30 TAC Chapter 115, an applicable New Source Performance Standard (NSPS), or an applicable National Emission Standard for Hazardous Air Pollutants (NESHAPS) and does not constitute approval of alternative standards for these regulations. **(8/13)**

58. Piping, Valves, Flanges, Pumps, and Compressors - 28 LAER

Except as may be provided for in the special conditions of this permit, the following requirements apply to the above-referenced equipment associated with the COEX II project (fugitive EPNs F-943, F-7843, F-7945, and F-8748-SWS).

A. The requirements of paragraphs F and G shall not apply (1) where the VOC has an aggregate partial pressure or vapor pressure of less than 0.044 pounds per square inch, absolute (psia) at 68°F or (2) operating pressure is at least 5 kilopascals (0.725 psi) below ambient pressure. Equipment excluded from this condition shall be identified in a list or by one of the methods described below to be made readily available upon request.

The exempted components may be identified by one or more of the following methods:

(1) piping and instrumentation diagram (PID);

(2) a written or electronic database or electronic file;

(3) color coding;

(4) a form of weatherproof identification; or

(5) designation of exempted process unit boundaries.

B. Construction of new and reworked piping, valves, pump systems, and compressor systems shall conform to applicable American National Standards Institute (ANSI), American Petroleum Institute (API), American Society of Mechanical Engineers (ASME),, or equivalent codes.

C. New and reworked underground process pipelines shall contain no buried valves such that fugitive emission monitoring is rendered impractical. New and reworked buried connectors shall be welded.

D. To the extent that good engineering practice will permit, new and reworked valves and piping connections shall be so located to be reasonably accessible for leak-checking during plant operation. Difficult-to-monitor and unsafe-to-monitor valves, as defined by Title 30 Texas Administrative Code Chapter 115 (30 TAC Chapter 115), shall be identified in a list to be made readily available upon request. The difficult-to-monitor and unsafe-to-monitor valves may be identified by one or more of the methods described in subparagraph A above. If an unsafe to monitor component is not considered safe to monitor within a calendar year, then it shall be monitored as soon as possible during safe to monitor times. A difficult to monitor component for which quarterly monitoring is specified may instead be monitored annually.

E. New and reworked piping connections shall be welded or flanged. Screwed connections are permissible only on piping smaller than two-inch diameter. Gas or hydraulic testing of the new and reworked piping connections at no less than operating pressure shall be performed prior to returning the components to service or they shall be monitored for leaks using an approved gas analyzer within 15 days of the components being returned to service. Adjustments shall be made as necessary to obtain leak-free performance.

Connectors shall be inspected by visual, audible, and/or olfactory means at least weekly by operating personnel walk-through. In addition, all connectors shall be monitored by leak-checking for fugitive emissions at least quarterly using an approved gas analyzer with a directed maintenance program in accordance with items F thru J of this special condition.

In lieu of the monitoring frequency specified above, connectors may be monitored on a semiannual basis if the percent of connectors leaking for two consecutive quarterly monitoring periods is less than 0.5 percent.

Connectors may be monitored on an annual basis if the percent of connectors leaking for two consecutive semiannual monitoring periods is less than 0.5 percent.

If the percent of connectors leaking for any semiannual or annual monitoring period is 0.5 percent or greater, the facility shall revert to quarterly monitoring until the facility again qualifies for the alternative monitoring schedules previously outlined in this paragraph.

The percent of connectors leaking used in paragraph B shall be determined using the following formula:

$(Cl + Cs) \times 100/Ct = Cp$

Where:

Cl = the number of connectors found leaking by the end of the monitoring period, either by Method 21 or sight, sound, and smell.

Cs = the number of connectors for which repair has been delayed and are listed on the facility shutdown log.

Ct = the total number of connectors in the facility subject to the monitoring requirements, as of the last day of the monitoring period, not including non-accessible and unsafe to monitor connectors.

Cp = the percentage of leaking connectors for the monitoring period..

Each open-ended valve or line shall be equipped with an appropriately sized cap, blind flange, plug, or a second valve to seal the line. Except during sampling, both valves shall be closed. If the isolation of equipment for hot work or the removal of a component for repair or replacement results in an open ended line or valve, it is exempt from the requirement to install a cap, blind flange, plug, or second valve for 72 hours. If the repair or replacement is not completed within 72 hours, the permit holder must complete either of the following actions within that time period;

(1) a cap, blind flange, plug, or second valve must be installed on the line or valve; or

(2) the open-ended valve or line shall be monitored once for leaks above background for a plant or unit turnaround lasting up to 45 days with an approved gas analyzer and the results recorded. For all other situations, the open-ended valve or line shall be monitored once by the end of the 72 hours period following the creation of the open ended line and monthly thereafter with an approved gas analyzer and the results recorded. For turnarounds and all other situations, leaks are indicated by readings of 500 ppmv and must be repaired within 24 hours or a cap, blind flange, plug, or second valve must be installed on the line or valve.

F. Accessible valves shall be monitored by leak checking for fugitive emissions at least quarterly using an approved gas analyzer with a directed maintenance program. Non accessible valves shall be monitored by leak-checking for fugitive emissions at least annually using an approved gas analyzer with a directed maintenance program. Sealless/leakless valves (including, but not limited to, welded bonnet bellows and diaphragm valves) and relief valves equipped with a rupture disc upstream or venting to a control device are not required to be monitored. For valves equipped with rupture discs, a pressure-sensing device shall be installed between the relief valve and rupture disc to monitor disc integrity. All leaking discs shall be replaced at the earliest opportunity but no later than the next process shutdown. A check of the reading of the pressure-sensing device to verify disc integrity shall be performed at least quarterly and recorded in the unit log or equivalent. Pressure-sensing devices that are continuously monitored with alarms are exempt from recordkeeping requirements specified in this paragraph.

The gas analyzer shall conform to requirements listed in Method 21 of 40 CFR part 60, appendix A. The gas analyzer shall be calibrated with methane. In addition, the response factor of the instrument for a specific VOC of interest shall be determined and meet the requirements of Section 8 of Method 21. If a mixture of VOCs is being monitored, the response factor shall be calculated for the average composition of the process fluid. A calculated average is not required when all of the compounds in the mixture have a response factor less than 10 using methane. If a response factor less than 10 cannot be achieved using methane, than the instrument may be calibrated with one of the VOC to be measured or any other VOC so long as the instrument has a response factor of less than 10 for each of the VOC to be measured.

A directed maintenance program shall consist of the repair and maintenance of components assisted simultaneously by the use of an approved gas analyzer such that a minimum concentration of leaking VOC is obtained for each component being maintained. Replaced components shall be re-monitored within 15 days of being placed back into VOC service.

G. All new and replacement pumps, compressors, and agitators shall be equipped with a shaft sealing system that prevents or detects emissions of VOC from the seal. These seal systems need not be monitored and may include (but are not limited to) dual pump seals with barrier fluid at higher pressure than process pressure, seals degassing to vent control systems kept in good working order, or seals equipped with an automatic seal failure detection and alarm system. Submerged pumps or sealless pumps (including, but not limited to, diaphragm, canned, or magnetic-driven pumps) may be used to satisfy the requirements of this condition and need not be monitored.

All other pump, compressor, and agitator seals shall be monitored with an approved gas analyzer at least quarterly.

H. Damaged or leaking valves, connectors, compressor seals, pump seals, and agitator seals found to be emitting VOC in excess of 500 parts per million by volume (ppmv) or found by visual inspection to be leaking (e.g., dripping process fluids) shall be tagged and replaced or repaired. A first attempt to repair the leak must be made within 5 days. Records of the first attempt to repair shall be maintained. A leaking component shall be repaired as soon as practicable, but no later than 15 days after the leak is found. If the repair of a component would require a unit shutdown that would create more emissions than the repair would eliminate, the repair may be delayed until the next scheduled shutdown. All leaking components which cannot be repaired until a scheduled shutdown shall be identified for such repair by tagging. A listing of all components that qualify for delay of repair shall be maintained on a delay of repair list. The cumulative daily emissions from all components on the delay of repair list shall be estimated by multiplying by 24 the mass emission rate for each component calculated in accordance with the instructions in 30 TAC 115.782 (c)(1)(B)(i)(II). The calculations of the cumulative daily emissions from all components on the delay of repair list shall be updated within ten days of when the latest leaking component is

added to the delay of repair list. When the cumulative daily emission rate of all components on the delay of repair list times the number of days until the next scheduled unit shutdown is equal to or exceeds the total emissions from a unit shutdown as calculated in accordance with 30 TAC 115.782 (c)(1)(B)(i)(I), the TCEQ Regional Manager and any local programs shall be notified and may require early unit shutdown or other appropriate action based on the number and severity of tagged leaks awaiting shutdown. This notification shall be made within 15 days of making this determination.

I. Records of repairs shall include date of repairs, repair results, justification for delay of repairs, and corrective actions taken for all components. Records of instrument monitoring shall indicate dates and times, test methods, and instrument readings. The instrument monitoring record shall include the time that monitoring took place for no less than 95% of the instrument readings recorded. Records of physical inspections shall be noted in the operator's log or equivalent.

J. Compliance with the requirements of this condition does not assure compliance with requirements of 30 TAC Chapter 115, an applicable New Source Performance Standard (NSPS), or an applicable National Emission Standard for Hazardous Air Pollutants (NESHAPS), and does not constitute approval of alternative standards for these regulations.

K. In lieu of the monitoring frequency specified in paragraph F, valves in gas and light liquid service may be monitored on a semiannual basis if the percent of valves leaking for two consecutive quarterly monitoring periods is less than 0.5 percent.

Valves in gas and light liquid service may be monitored on an annual basis if the percent of valves leaking for two consecutive semiannual monitoring periods is less than 0.5 percent.

If the percent of valves leaking for any semiannual or annual monitoring period is 0.5 percent or greater, the facility shall revert to quarterly monitoring until the facility again qualifies for the alternative monitoring schedules previously outlined in this paragraph.

L. The percent of valves leaking used in paragraph K shall be determined using the following formula:

$(Vl + Vs) \times 100/Vt = Vp$

Where:

Vl = the number of valves found leaking by the end of the monitoring period, either by Method 21 or sight, sound, and smell.

Vs = the number of valves for which repair has been delayed and are listed on the facility shutdown log.

Vt = the total number of valves in the facility subject to the monitoring requirements, as of the last day of the monitoring period, not including nonaccessible and unsafe to monitor valves.

Vp = the percentage of leaking valves for the monitoring period.

M. Any component found to be leaking by physical inspection (i.e., sight, sound, or smell) shall be repaired or monitored with an approved gas analyzer within 15 days to determine whether the component is leaking in excess of 500 ppmv of VOC. If the component is found to be leaking in excess of 500 ppmv of VOC, it shall be subject to the repair and replacement requirements contained in this special condition. **(8/13)**

59. The following paragraphs modify the requirements in the fugitive monitoring requirements in Special Conditions 57 and 58.

    A. All components in heavy liquid service shall be inspected by visual, audible, and/or olfactory means at least weekly by operating personnel walk-through in the same manner as required for connectors in Special Conditions 57.E and 58.E.

    B. As an alternative to comparing the potential cumulative emissions of the components on the delay of repair (DOR) list until the next process unit shutdown to the total emissions from a process unit shutdown per the requirements of Special Conditions 57.I and 58.H, the cumulative hourly emission rate of all process unit components on the DOR list may be compared to 10 percent of the total short term process unit fugitive allowable emission rate in order to determine if the TCEQ Regional Director and any local program is to be notified.

Monitoring of Process Wastewater Collection Systems

60. All process wastewater drains shall be monitored quarterly at a leak definition of 500 ppmv. Water shall be added to flush and displace hydrocarbons floating inside the process drains if a leak is detected. **(02/08)**

61. Wastewater collection system components associated with Hydrocracker Unit 943 (HCU-943) and Saturated Gas Recovery Unit (SGRU- 7945), and Delayed Coker 844 (EPN WWC) shall comply with the following: (**09/18**)

    A. Process wastewater drains shall be equipped with water seals or equivalent. Water seals shall be checked by visual or physical inspection quarterly for indications of low water levels or other conditions that would reduce the effectiveness of water seal controls. Water seals shall be restored as necessary within 24 hours. Records shall be maintained of these inspections and corrective actions taken.

    B. Lift stations, manholes, junction boxes, any other wastewater collection system components, and conveyance shall be equipped with a closed vent system that routes all organic vapors to a control device. **(5/12)**

    C. The annual average daily flow of wastewater from the refinery shall not exceed 10.3419 million gallons per day (MGD). The daily flow of wastewater flow into the wastewater treatment plant shall be monitored and recorded. The rolling twelve month wastewater flow shall be totaled on a monthly basis. (**09/18**)

Monitoring of Vapor Collection Systems

62. The following requirements apply to capture systems for the FCCU Wet Gas Scrubber, flares, marine vapor combustor, and Tail Gas Incinerators.

    A. If used for particulate control, complete either of the following once a year

        (1) Inspect any fan and verify proper operation and inspect the capture system to verify there are no cracks, holes, tears, and other defects once a year; or

        (2) Verify there are no fugitive emissions escaping from the capture system by performing a visible emissions observation for a period of at least six minutes in accordance with 40 CFR Part 60, Appendix A, Test Method 22.

    B. If used to control pollutants other than particulate, either:

        (1) Conduct a once a month visual, audible, and/or olfactory inspection of the capture system to verify there are no leaking components in the capture system; or

        (2) Once a year, verify the capture system is leak-free by inspecting in accordance with 40 CFR Part 60, Appendix A, Test Method 21. Leaks shall be indicated by an instrument reading greater than or equal to 500 ppmv above background.

    C. The control device shall not have a bypass.

    D. If any of the above inspections is not satisfactory, the permit holder shall promptly take necessary corrective action. **(02/08)**

63. Coker Unit Sludge Tanks (FINS T-8010 and T-8400) shall each vent through a carbon adsorption system (CAS) consisting of at least two activated carbon canisters that are connected in series EPNs (T-8010 and T-8400). **(09/18)**

    A. The CAS shall be sampled daily to determine breakthrough of volatile organic compounds (VOC). The sampling point shall be at the outlet of the initial canister but before the inlet to the second or final polishing canister. Sampling shall be done during tank filling. Sampling is not required on those days that tank filling does not occur.

    B. The VOC sampling and analysis shall be performed using an instrument with a flame ionization detector (FID), or a TCEQ-approved alternative detector. The instrument/FID must meet all requirements specified in Section 8.1 of EPA Method 21 (40 CFR 60, Appendix A). Sampling and analysis for VOC breakthrough shall be performed as follows:

        (1) Immediately prior to performing sampling, the instrument/FID shall be calibrated with zero and span calibration gas mixtures. Zero gas shall be certified to contain less than 0.1 ppmv total hydrocarbons. Span calibration gas shall be methane at a concentration within ± 10 percent of 100 ppmv, and certified by the manufacturer to be ± 2 percent accurate. Calibration error for the zero and span calibration gas checks must be less than ± 5 percent of the span calibration gas value before sampling may be conducted.

        (2) The sampling point shall be at the outlet of the initial canister but before the inlet to the second or final polishing canister. Sample ports or connections must be designed such that air leakage into the sample port does not occur during sampling.

        (3) During sampling, data recording shall not begin until after two times the instrument response time. The VOC concentration shall be monitored for at least 5 minutes, recording 1-minute averages, during tank filling.

C. Breakthrough shall be defined as the highest 1 minute average measured VOC concentration at or exceeding 100 ppmv. When the condition of breakthrough of VOC from the initial saturation canister occurs, the waste gas flow shall be switched to the second canister and a fresh canister shall be placed as the new final polishing canister within 24 hours. Sufficient new activated carbon canisters shall be maintained at the site to replace spent carbon canisters such that replacements can be done in the above specified time frame.

D. Records of the CAS monitoring maintained at the plant site, shall include (but are not limited to) the following:

(1) Sample time and date.

(2) Monitoring results (ppmv).

(3) Corrective action taken including the time and date of that action.

(4) Process operations occurring at the time of sampling.

E. Alternate monitoring or sampling requirements that are equivalent or better may be approved by the TCEQ Regional Manager. Alternate requirements must be approved in writing before they can be used for compliance purposes

Emission Cap Compliance

64. Recordkeeping programs for those facilities authorized by this permit shall be established and maintained such that the ability to demonstrate compliance with all authorized emission caps and individual emission rates (short-term and annual) is ensured. Records of all compliance testing, CEMS results, and process parameters necessary to demonstrate compliance with the emission rate caps shall be maintained.

Compliance with annual (TPY) emissions shall be based on calendar basis through the year 2004 and on a 12-month rolling average thereafter. Emissions calculations for verifying compliance with the emission caps shall be performed at least once every month to demonstrate compliance with the annual rolling average requirement. The holder of this permit shall maintain all records necessary to demonstrate compliance with the short-term (lb/hr) and annual TPY emissions cap and provide such demonstration of compliance to the TCEQ Beaumont Regional Office upon request.

The emissions from each emission point shall be determined as follows:

A. Piping Fugitives - Piping fugitive emissions shall be calculated in accordance with the TCEQ publication titled “Technical Guidance Package for Chemical Sources - Equipment Leak Fugitives,” dated October 2000.

B. Cooling Towers - Measured strippable VOC concentration as specified in Special Condition Nos. 20 and 21 and the cooling tower circulation rate.

C. Atmospheric VOC Storage Tanks - Emissions from storage tanks shall be calculated in accordance with the TCEQ publication titled “Technical Guidance Package for Chemical Sources - Storage Tanks," dated February 2001.

D. Heaters and Boilers

(1) If a CEMS is installed, as specified in Special Condition No. 52.

(2) If stack tested per Special Condition No. 50, using the most recent stack test result and recorded firing rate for the period.

(3) If no CEMS or stack sampling is required, use the emission factors represented in the most recent permit activity for each source and the recorded firing rate for the period.

E. VOC Loading - Emissions from VOC loading operations shall be calculated in accordance with the TCEQ publication titled "Technical Guidance Package for Chemical Sources - Loading Operations," dated October 2000.

F. Sulfur Loading - H_2S emissions from loading liquid sulfur into tank trucks shall be determined by multiplying the weight of sulfur loaded by the concentration of the most recent monthly stain tube sample.

G. TGIs

(1) If a CEMS is installed, as specified in Special Condition No. 52.

(2) If stack tested per Special Condition No. 50, using the most recent stack test result and recorded operating rate for the period.

(3) For those contaminants not monitored with a CEMS, or stack sampled, using the emission factor in the flexible permit renewal application, PI-1R dated December 14, 2006, and the average value of the appropriate operating parameter for the period.

(4) The CO emissions from the SRU TGIs without a CO CEMs shall be determined using the lowest incinerator temperature stack test results or using results from the most recent stack testing performed at multiple incinerator temperatures. The permit holder may then use this data to determine CO emissions as a function of temperature.

H. Coke - The coke production and transfer rates recorded per Special Condition No. 41, the PM_{10} emission factor of 0.00167 pounds per ton of coke handled, and the control efficiencies for each coke emission point represented in the permit amendment application, PI-1 dated January 31, 2008.

I. Flares - In accordance with the TCEQ Technical Guidance Document, Flares and Vapor Oxidizers, dated October 2000. Monitored flow rates and sulfur composition, and the most recent fuel gas analysis shall be used as inputs after the monitors are installed. **(1/13)**

Nonattainment New Source Review Offsets

65. This nonattainment new source review permit is issued based on the reduction of 169.84 TPY of VOC emissions to offset VOC project increases of 141.5 (includes maintenance, startup, and shutdown (MSS) emissions as well as normal operating emissions) TPY represented in the amendment, PI-1 dated March 21, 2011, COEX II clean up application submitted on March 26, 2008 and the Coker Permit application submitted on February 6, 2008, at the rate of 1.2. 169.8 TPY of VOC emission reductions shall be provided by the permanent retirement of TCEQ Emission Reduction Credit Certificate (ERCC) Nos. 1227, 1230, 1698, 2218, and 2530 having VOC credits of 44.5 TPY, 21.6 TPY, 48.4 TPY, 55.8, and 7.0 TPY respectively. **(1/13)**

Recordkeeping

66. All records, calculations, copies of the manufacturer's specifications for temperature monitors and flow monitoring devices, and the most recent satisfactory stack test reports required by this permit shall be maintained on-site for a period of five years and shall be made available to representatives of the TCEQ or any air pollution control agencies having jurisdiction upon request.

    The amendment application, PI-1 dated May 29, 2013, was determined not to be subject to major new source review by identifying projected actual emission rates for one or more facilities potentially affected by the project. Actual emissions from these facilities shall be monitored, recorded and reports made in accordance with 30 TAC § 116.127. **(8/13)**

Periodic Reports

67. The holder of this permit shall submit to the TCEQ Beaumont Regional Office quarterly reports. Each report shall contain the number of days of SRU downtime for the previous four-year period. **(06/04)**

Shakedowns and Shutdowns

68. Boiler House (BH) 16 Boiler 16-31 (EPN E 03-16BH), BH16 Boiler 16-32 (EPN E 04-16BH), BH16 Boiler 16-33 (EPN E 05-16BH), BH16 Duct Burners 16-34 and 16-35 (EPNs E 06-16BH and E 07-16BH), and Gas Turbine Generator - 5 (EPN E 08-16BH) shall be permanently shutdown by the end of the Boilerhouse 19 shakedown period (Permit 103765). **(7/12)**

69. The following sources and/or activities are authorized under a Permit by Rule (PBR) by Title 30 Texas Administrative Code Chapter 106 (30 TAC Chapter 106). These lists are not intended to be all inclusive and can be altered without modifications to this permit. **(09/18)**

Authorization	EPN	Source or Activity
139815	E-1241CILD	Catalyst Loading Bin Vent and Vacuum Jet

70. The following sources and/or activities are authorized under a Permit by Rule (PBR) by Title 30 Texas Administrative Code Chapter 106 (30 TAC Chapter 106). These lists are not intended to be all inclusive and can be altered without modifications to this permit. Facilities authorized by these PBRs are affected facilities authorized under federal permit numbers PSDTX167 and GHGPSDTX167. **(09/18)**

Authorization	EPN	Source or Activity
Standard Exemption 61, 68, and 88 (Effective April 27/1993)	WWTP	Wastewater treatment plant

Greenhouse Gases (GHG)

71. Emission limitations, monitoring, recordkeeping, and reporting requirements of this section shall not become effective until construction and startup of coker DCU 844 as authorized in the coker project PI-1 dated, February 27, 2017). The permit holder shall retain a copy of any start-up notifications required under General Condition 4.

72. Any calculation for carbon dioxide equivalent (CO_2e) emission rates required by this permit shall employ Global Warming Potentials (GWP) contained in Greenhouse Gas Regulations, 40 CFR Part 98, Subpart A, Table A-1, as amended on December 11, 2014 (79 FR 73779).

73. Where a methodology of 40 CFR Part 98 is referenced in this permit, such reference method shall be modified as follows:

    A. References to annual measurements shall be construed as rolling 12-month totals if the relevant parameter is measured on a monthly or more frequent basis.

    B. References to annual measurements that are not measured at a frequency greater than one month (e.g., quarterly or semiannual) shall be construed as the average of the most recent measurements based on a rolling 12-month period (e.g., average of 4 quarterly or 2 semiannual measurements).

74. Operational and Monitoring requirements for Combustion Devices

    A. Rolling 12-month CO_2e emissions shall be calculated each month using the methods provided at 40 CFR § 98.34(a)

    B. Combustion devices shall be operated with a net thermal efficiency of no less than 80 percent on a 12-month rolling average, excluding periods of maintenance, startup and shutdown. This shall be ensured by using the following good combustion practices: operating each device at an optimum air-fuel ratio, limiting the device's operating temperature to the extent practicable, and reducing heat loss through the use of insulating materials where feasible.

    C. Thermal efficiency shall be calculated and recorded at least monthly using equation G-1 from American Petroleum Institute (API) method 560 (4th ed. or later), Annex G using monitoring data collected as required under this permit and Permit No. 80812, other quality-assured data, and engineering judgment. **(11/18)**

    If the maximum range between twelve or more consecutive monthly efficiency calculations does not exceed 5 percentage points, and each calculation demonstrates compliance with the minimum efficiency requirements of this paragraph, the permit holder may elect to reduce the frequency of performing the calculation to quarterly (skipping up to two monthly calculations); provided, however, that:

    (1) In case a quarterly efficiency calculation yields an efficiency value outside of the maximum range specified in this previous paragraph, monthly efficiency calculations shall be resumed.

    (2) In case a quarterly efficiency calculation shows non-compliance with the minimum efficiency requirement of this paragraph, the permit holder shall assume that a condition of non-compliance occurred during each month of the previous quarter where a calculation was skipped.

    D. The higher heating value (HHV) of the fuel shall be determined and recorded on a semiannual basis following procedures provided at 40 CFR § 98.34(a)(6).

The carbon content of the fuel shall be determined and recorded on a semiannual basis following the procedures provided at 40 CFR § 98.34(b)(3)

E. For facilities not equipped with a CEMS, the permit holder shall continuously monitor and record the exhaust temperature and the oxygen content of the flue gas for each combustion device. Monitoring devices shall reduce temperature and oxygen readings to six-minute averages or less and record readings at that frequency.

The temperature monitor shall be installed, calibrated or have a calibration check performed at least annually, and maintained according to the manufacturer's specifications. The device shall have an accuracy of the greater of ±2 percent of the temperature being measured expressed in degrees Celsius or ±2.5ºC.

Oxygen analyzers shall be quality-assured at least quarterly using cylinder gas audits (CGAs) in accordance with 40 CFR Part 60, Appendix F, Procedure 1, § 5.1.2. A relative accuracy test audit (RATA) is required once every four quarter in accordance with 40 CFR Part 60, Appendix F, Procedure 1, § 5.1.1.

Quality assured (or valid) data must be generated when the combustion device is operating except during the performance of a daily zero and span check. Loss of valid data due to periods of monitor break down, out-of-control operation (producing inaccurate data), repair, maintenance, or calibration may be exempted provided it does not exceed 5 percent of the time (in minutes) that the VCU operated over the previous rolling 12 month period. The measurements missed shall be estimated using engineering judgment and the methods used recorded.

F. The permit holder shall install, calibrate, maintain, and operate a continuous fuel flow monitor and record the average hourly fuel gas consumption of each combustion device. Fuel flow meters shall be calibrated as provided for at 40 CFR § 98.34(b)(1).

75. Emissions from leaking fugitive components (EPN REFFUG) shall be minimized as follows.

The permit holder shall implement a Leak Detection and Repair Program for emissions of VOC as a surrogate for methane, as specified in Special Condition 57. The permit holder shall tag all components and maintain a record of all fugitive components subject to this provision. The record shall be made available upon requests.

76. Each flare covered by this permit shall be subject to the following requirements.

A. The flare shall be operated as specified in Special Condition 6, as applicable in order to minimize emissions of methane from the flare.

B. Emissions of GHG shall be calculated as specified in 40 CFR § 98.253(b), and rolling 12-month GHG emission totals from each flare shall be updated on a monthly basis.

77. The following requirements apply to the marine loading vapor combustor (EPN E-MC-24-25) and temporary vapor combustor units authorized pursuant to Special Condition 89.

A. The minimum destruction/removal efficiency requirements of Special Conditions 7 and 89 shall apply to emissions of methane from the control device.

B. In addition to pollutants specified in paragraph B of Special Condition 51, the permit holder shall perform stack sampling for emissions of methane from the control device in order to demonstrate compliance with paragraph A of this Special Condition. This provision does not apply to temporary control devices used to control emissions from MSS activities per Special Condition 89.

C. Emissions of GHG shall be calculated as specified in 40 CFR §§ 98.253(j), (n), as applicable, and rolling 12-month GHG emission totals from each control device shall be updated on a monthly basis.

78. The following requirements apply to delayed coking operations covered by the permit.

A. Emissions of methane from coke drum depressurization and opening operations shall be controlled as specified in Special Condition 39 of the permit.

B. Emissions of GHG shall be calculated as specified in 40 CFR §§ 98.253(i), as applicable, and rolling 12-month GHG emission totals from delayed coking operations shall be updated on a monthly basis.

79. The following requirements apply to each sulfur recovery plant covered by the permit.

A. Emissions of GHG shall be calculated as specified in 40 CFR §§ 98.253(f), as applicable, and rolling 12-month GHG emission totals from the sulfur recovery plant shall be updated on a monthly basis.

80. The following requirements apply to process vents covered by the permit.

A. The prohibition on non-fugitive releases of process vent emissions specified in Special Condition 2 shall apply to emissions of methane.

B. Control devices used to control process vent emissions shall comply with Special Condition 1 or 2 of this permit, as applicable.

C. Emissions of GHG from process vents shall be calculated as specified in 40 CFR §§ 98.253(i), or any other method of calculation otherwise specified in this permit, and rolling 12-month GHG emission totals from process vents shall be updated on a monthly basis.

81. Emissions from leaking piping components (EPN REFFUG) shall be minimized as follows.

A. The permit holder shall implement a Leak Detection and Repair Program for emissions of VOC as a surrogate for methane, as specified in Special Condition 57. The permit holder shall tag all components and maintain a record of all fugitive components subject to this provision. The record shall be made available upon requests

B. Total rolling 12-month GHG emissions shall be calculated as provided for at 40 CFR § 98.253(l), except that mass emission rates shall be converted and recorded in units of short tons per year.

82. The following requirements apply to storage tanks T-112, T-113, and T-114 covered by this permit. **(11/18)**

A. Storage tanks shall be designed and operated as specified in Special Condition 9, except that paragraph 1 of Special Condition 9, concerning aggregate partial pressures above which additional control is required, is revised to apply to total hydrocarbons rather than to VOC.

B. Emissions of GHG from storage tanks shall be calculated as specified in 40 CFR §§ 98.253(m), or any other method of calculation otherwise specified in this permit, and rolling 12-month GHG emission totals from each storage shall be updated on a monthly basis.

83. The permit holder shall comply with all applicable control monitoring and recordkeeping requirements of permits 6825A, PSDTX49M1, and 80812 pertaining to planned MSS activities. **(11/18)**

Planned Maintenance, Start-Up, and Shutdown

84. Process units and facilities identified in Special Condition 85.C through 85.F shall be depressurized, emptied, degassed, and placed in service in accordance with the following requirements. (**09/18**)

A. The process equipment shall be depressurized to a control device or a controlled recovery system prior to venting to atmosphere, degassing, or draining liquid. Equipment that only contains material that is liquid with VOC partial pressure less than 0.50 psi at the normal process temperature and 95°F may be opened to atmosphere and drained in accordance with paragraph C of this special condition. The vapor pressure at 95°F may be used if the actual temperature of the liquid is verified to be less than 95°F and the temperature is recorded.

B. If mixed phase materials must be removed from process equipment, the cleared material shall be routed to a knockout drum or equivalent to allow for managed initial phase separation. If the VOC partial pressure is greater than 0.50 psi at either the normal process temperature or 95°F, any vents in the system must be routed to a control device or a controlled recovery system. The vapor pressure at 95°F may be used if the actual temperature of the liquid is verified to be less than 95°F and the temperature is recorded. Control must remain in place until degassing has been completed or the system is no longer vented to atmosphere.

C. All liquids from process equipment must be removed to the maximum extent practical prior to opening equipment to commence degassing and/or maintenance. Liquids must be drained into a closed system such that there are no emissions to the atmosphere.

D. If the VOC partial pressure is greater than 0.50 psi at the normal process temperature or 95°F, facilities shall be degassed using good engineering practice to ensure air contaminants are removed from the system through the control device or controlled recovery system to the extent allowed by process equipment or storage vessel design. The vapor pressure at 95°F may be used if the actual temperature of the liquid is verified to be less than 95°F and the temperature is recorded. The facilities to be degassed shall not be vented directly to atmosphere, except as necessary to establish isolation of the work area or to monitor VOC concentration following controlled depressurization. The venting shall be minimized to the maximum extent practicable and actions taken recorded. The control device or recovery system utilized shall be recorded with the estimated emissions from controlled and uncontrolled degassing calculated using the methods that were used to determine allowable emissions for the permit application.

(1) The locations and/or identifiers where the purge gas or steam enters the process equipment and the exit points for the exhaust gases shall be recorded (process flow diagrams [PFDs] or piping and instrumentation diagrams [P&IDs] may be used to demonstrate compliance with the requirement). If the process equipment is purged with a gas, two system volumes of purge gas must have passed through the control device or controlled recovery system before the vent stream may be sampled to verify acceptable VOC concentration prior to uncontrolled venting. The VOC sampling and analysis shall be performed using an instrument meeting the requirements of Special Condition 87. The sampling point shall be upstream of the inlet to the control device or controlled recovery system. The sample ports and the collection system must be designed and operated such that there is no air leakage into the sample probe or the collection system downstream of the process equipment or vessel being purged. If there is not a connection (such as a sample, vent, or drain valve) available from which a representative sample may be obtained, a sample may be taken upon entry into the system after degassing has been completed. The sample shall be taken from inside the vessel so as to minimize any air or dilution from the entry point. The facilities shall be degassed to a control device or controlled recovery system until the VOC

concentration is less than 10,000 ppmv or 10 percent of the LEL. Documented site procedures used to de-inventory equipment to a control device for safety purposes (i.e., hot work or vessel entry procedures) that achieve at least the same level of purging may be used in lieu of the above.

85. A. This permit authorizes emissions from Flare No. 20 (EPN E-20-FLARE) for the following planned MSS activities associated with the low sulfur gasoline desulfurization unit:

Intermittent Blowdown

Routine Maintenance

B. This permit authorizes emissions from FCCU 1241 Heaters B-103A (EPN E-01-1241) and B-103B (EPN E-02-1241) to heat the charge to FCCU 1241 and establish circulation during planned start-ups of FCCU 1241. The FCCU 1241 Heaters B-103A (EPN E-01-1241) and B-103B (EPN E-02-1241) shall each operate no more than 500 hours in any calendar year. The hours of operation of each heater shall be recorded. **(04/16)**

C. Controlled startup, shutdown, and maintenance emissions from facilities associated with Coker Unit 844 (compressor, depropanizer, and debutanizer) as well as uncontrolled venting due to facility opening. Controlled emissions shall be vented to Flare 26. Emissions are authorized under EPN MSS. (**09/18**)

D. Controlled SRU 547 shutdown emissions as well as uncontrolled equipment degassing and venting. Controlled emissions shall be vented to Flare 23 (EPN E-23-FLARE). Emissions are authorized under EPN MSS (**09/18**)

E. Start-up of Coker furnaces 844-H1 and 844-H2 (EPNs E-01-844 and E-02-844) MSS). (**09/18**)

F. Controlled and uncontrolled tank roof landings from floating roof storage tanks 112, 113, and 114 (EPN MSS). (**09/18**)

G. Any MSS activity not included in Paragraph A, B, C, D, E, or F of this special condition is not authorized by this permit.

H. Emissions from the planned MSS activities listed in Paragraphs A and B of this special condition are subject to the maximum allowable emission rates indicated on the MAERT. Emissions from the planned MSS activities listed in Paragraphs C through F of this special condition are subject to the maximum allowable emission rates indicated on the MAERT. The performance of each planned MSS activity and the emissions associated with it shall be recorded and the rolling 12-month emissions shall be updated on a monthly basis. These records shall include at least the following information:

(1) the physical location at which emissions from the planned MSS activity occurred, including the emission point number, common name, and any other identifier for the point at which the emissions were released into the atmosphere

(2) the type of planned MSS activity and the reason for the planned activity

(3) the common name and the facility identification number of the facilities at which the planned MSS activity and emissions occurred

(4) the date and time of the planned MSS activity and its duration

(5) the estimated quantity of each air contaminant, or mixture of air contaminants, emitted with the data and methods used to determine it. The emissions shall be estimated using the methods identified in the application submitted April 11, 2002, for the low sulfur gasoline desulfurization unit and the permit amendment application, PI-1, dated April 30, 1998, for the FCCU 1241 heaters, consistent with good engineering practice. **(7/12)**

86. This permit authorizes emissions from EPN MSS (uncontrolled and controlled activities) for the storage tanks T-112, T-113, and T-114 during planned floating roof landings. Tank roof landings include all operations when the tank floating roof is on its supporting legs. These emissions are subject to the maximum allowable emission rates indicated in the MAERT. The following requirements apply to tank roof landings. (**09/18**)

A. Landings are limited to one event per rolling 12 month period.

B. At all times that the roof is resting on its leg supports, the tank emissions shall be controlled by a closed vent system and control device meeting the following specifications:

(1) The closed vent system shall be designed to collect all VOC vapors and gases discharged from the storage vessel and operated with no detectable emissions as indicated by an instrument reading of less than 500 ppm above background and visual inspections, as determined in part 60, subpart VV, § 60.485(b).

(2) The locations and identifiers of vents other than permanent roof fittings and seals, control device or controlled recovery system, and controlled exhaust stream shall be recorded. There shall be no other gas/vapor flow out of the vapor space under the floating roof when the vapor space is directed to the control device. The vapor recovery system collection rate shall be no less than 100 cubic feet per minute when the tank is idle or the tank is being drained, and two times the fill rate when the tank is being refilled.

(3) Controlled emissions shall be vented to a vapor combustor satisfying the requirements of special condition 89.

The roof shall be landed on its lowest legs unless entry or inspection is planned.

The requirements of this paragraph do not apply to uncontrolled degassing and/or ventilation conducted pursuant to paragraphs C–F of this Special Condition.

C. After the tank has been completely emptied, the tank shall not be opened except as necessary to set up for degassing and cleaning. Controlled degassing of the vapor space under the landed roof shall be completed as follows:

(1) Any gas or vapor removed from the vapor space under the floating roof must be routed to a control device or controlled recovery system and controlled degassing must be maintained until the VOC concentration is less than 10,000 ppmv or 10 percent of the LEL. The locations and identifiers of vents other than permanent roof fittings and seals, control device or controlled recovery system, and controlled exhaust stream shall be recorded. There shall be no other gas/vapor flow out of the vapor space under the floating roof when degassing to the control device or controlled recovery system.

(2) The vapor space under the floating roof shall be vented using good engineering practice to ensure air contaminants are flushed out of the tank through the control device or controlled recovery system to the extent allowed by the storage tank design.

(3) A volume of purge gas equivalent to twice the volume of the vapor space under the floating roof must have passed through the control device or into a controlled recovery system, before the vent stream may be sampled to verify acceptable VOC concentration. The measurement of purge gas volume shall not include any make-up air introduced into the control device or recovery system. The VOC sampling and analysis shall be performed as specified in Special Condition 87.

(4) The sampling point shall be upstream of the inlet to the control device or controlled recovery system. The sample ports and the collection system must be designed and operated such that there is no air leakage into the sample probe or the collection system downstream of the process equipment or vessel being purged.

(5) Degassing must be performed every 24 hours unless there is no standing liquid in the tank or the VOC partial pressure of the remaining liquid in the tank is less than 0.15 psia.

D. The tank shall not be opened or ventilated without control, except as allowed by (1) or (2) below until one of the criteria in paragraph D of this condition is satisfied.

(1) Minimize air circulation in the tank vapor space.

(a) One manway may be opened to allow access to the tank to remove or de-volatilize the remaining liquid. Other manways or access points may be opened as necessary to remove or de-volatilize the remaining liquid. Wind barriers shall be installed at all open manways and access points to minimize air flow through the tank.

(b) Access points shall be closed when not in use.

E. The tank may be opened without restriction and ventilated without control after all standing liquid has been removed from the tank or the liquid remaining in the tank has a VOC partial pressure of less than 0.02 psia. These criteria shall be demonstrated in one of the following ways:

(1) Low VOC partial pressure liquid that is soluble with the liquid previously stored may be added to the tank to lower the VOC partial pressure of the liquid mixture remaining in the tank to less than 0.02 psia. This liquid shall be added during tank degassing if practicable. The estimated volume of liquid remaining in the drained tank and the volume and type of liquid added shall be recorded. The liquid VOC partial pressure may be estimated based on this information and engineering calculations.

(2) If water is added or sprayed into the tank to remove standing VOC, one of the following must be demonstrated:

(a) Take a representative sample of the liquid remaining in the tank and verify no visible sheen using the static sheen test from 40 CFR 435 Subpart A, Appendix 1.

(b) Take a representative sample of the liquid remaining in the tank and verify that the hexane soluble VOC concentration is less than 1000 ppmw using EPA method 1664.

(c) Stop ventilation and close the tank for at least 24 hours. When the tank manway is opened after this period, verify that the VOC concentration is less than 1000 ppmw through the procedure in Special Condition 87.

(3) No standing liquid, verified through visual inspection.

(4) The manway opening limits of paragraph D(1)(a) apply during uncontrolled venting of emissions. Mechanical ventilation used to remove vapors during uncontrolled venting shall not exceed a combined rating of 330 cubic feet per minute.

The permit holder shall maintain records to document the method used to release the tank.

F. The tank fill rate shall not exceed 10,000 bbls/hr until the roof is refloated.

G. The occurrence of each roof landing and the associated emissions shall be recorded and the rolling 12 month tank roof landing emissions shall be updated on a monthly basis. These records shall include at least the following information (as applicable):

(1) The identification of the tank and emission point number, and any control devices or controlled recovery systems used to reduce emissions;

(2) The reason for the tank roof landing;

(3) For the purpose of estimating emissions, the date, time, and other information specified for each of the following events:

(a) The roof was initially landed;

(b) All liquid was pumped from the tank to the extent practicable;

(c) Start and completion of controlled degassing, and total volumetric flow;

(d) All standing liquid was removed from the tank or any transfers of low VOC partial pressure liquid to or from the tank including volumes and vapor pressures to reduce tank liquid VOC partial pressure to < 0.02 psia.

(e) If there is liquid in the tank, VOC partial pressure of liquid, start and completion of uncontrolled degassing, and total volumetric flow;

(f) Refilling commenced, liquid filling the tank, and the volume necessary to float the roof; and

(g) Tank roof off supporting legs, floating on liquid.

(4) The estimated quantity of each air contaminant, or mixture of air contaminants, emitted between events (c) and (g) with the data and methods used to determine it. The emissions associated with roof landing activities shall be calculated using the methods described in Section 7.1.3.2 of AP-42 “Compilation of Air Pollution Emission Factors, Chapter 7—Storage of Organic Liquids” dated November 2006 (or later edition) and the permit application.

87. Air contaminant concentration shall be measured using an instrument/detector meeting one set of requirements specified below. (**09/18**)

A. VOC concentration shall be measured using an instrument meeting all the requirements specified in EPA Method 21 (40 CFR 60, Appendix A) with the following exceptions:

(1) The instrument shall be calibrated within 24 hours of use with a calibration gas such that the response factor (RF) of the VOC (or mixture of VOCs) to be monitored shall be less than 2.0. The calibration gas and the gas to be measured, and its approximate RF shall be recorded. If the RF of the VOC (or mixture of VOCs) to be monitored is greater than 2.0, the VOC concentration shall be determined as follows:

VOC Concentration = Concentration as read from the instrument*RF

In no case should a calibration gas be used such that the RF of the VOC (or mixture of VOCs) to be monitored is greater than 5.0.

(2) Sampling shall be performed as directed by this permit in lieu of section 8.3 of Method 21. During sampling, data recording shall not begin until after two times the instrument response time. The date and time shall be recorded, and VOC concentration shall be monitored for at least 5 minutes, recording VOC concentration each minute. As an alternative the VOC concentration may be monitored over a five-minute period with an instrument designed to continuously measure concentration and record the highest concentration read. The highest measured VOC concentration shall be recorded and shall not exceed the specified VOC concentration limit prior to uncontrolled venting.

B. Colorimetric gas detector tubes may be used to determine air contaminant concentrations if they are used in accordance with the following requirements.

(1) The air contaminant concentration measured as defined in (3) is less than 80 percent of the range of the tube and is at least 20 percent of the maximum range of the tube.

(2) The tube is used in accordance with the manufacturer's guidelines.

(3) At least 2 samples taken at least 5 minutes apart must satisfy the following prior to uncontrolled venting:

measured contaminant concentration (ppmv) < release concentration.

Where the release concentration is:

10,000*mole fraction of the total air contaminants present that can be detected by the tube.

The mole fraction may be estimated based on process knowledge. The release concentration and basis for its determination shall be recorded.

Records shall be maintained of the tube type, range, measured concentrations, and time the samples were taken.

C. Lower explosive limit measured with a lower explosive limit detector.

(1) The detector shall be calibrated within 30 days of use with a certified pentane gas standard at 25% of the lower explosive limit (LEL) for pentane. Records of the calibration date/time and calibration result (pass/fail) shall be maintained.

(2) A functionality test shall be performed on each detector within 24 hours of use with a certified gas standard at 25% of the LEL for pentane. The LEL monitor shall read no lower than 90% of the calibration gas certified value. Records, including the date/time and test results, shall be maintained.

(3) A certified methane gas standard equivalent to 25% of the LEL for pentane may be used for calibration and functionality tests provided that the LEL response is within 95% of that for pentane.

88. A. The limits identified below apply to the operations of the specified facilities during startup and shutdown. (**09/18**)

EPN	Source Name	Pollutant or Criteria	Limit	Duration
E-01-844 E-02-844	DCU 844 Coker Furnaces 1 and 2	NO_x	0.15 lb/MMBtu	8 hours[1]
		CO	500 ppmv	8 hours
E-05-SCOT	SRU 547	Efficiency	97.5 percent	24 Hours
		H_2S	45 ppm	24 Hours
		Visible Emissions	20 percent	24 Hours
E-01-146	Heater 146 H-101	CO	500ppmv	8 Hours
E-02-146	Heater 146 H-102A/B	CO	500ppmv	8 Hours
E-02-943	HCU-943 F-3	NO_x	0.15 lb/MMBtu	8 Hours
		CO	500ppmv	8 Hours

1. Duration represents the total number of hours on a 12 month basis.

B. Controlled SRU 547 shut-down emissions to flare EPN E-23-FLARE are limited to 4 hours in any 12 month period.

89. A. This permit authorizes emissions from the following temporary facilities used to support planned MSS activities at permanent site facilities: portable control devices identified in this special condition and controlled recovery systems. Emissions from temporary facilities are authorized provided the temporary facility (a) does not remain on the plant site for more than 12 consecutive months, (b) is used solely to support planned MSS activities at the permanent site facilities listed in this Attachment, and (c) does not operate as a replacement for an existing authorized facility. (**09/18**)

B. Control devices required by this permit for emissions from planned MSS activities are limited to those types identified in this condition. Except as specified in this condition, control devices shall be operated with no visible emissions except periods not to exceed a total of five minutes during any two consecutive hours. Each device used must meet all the requirements identified for that type of control device. Fuel gas combusted in the control devices shall be sweet natural gas containing no more than 0.2 grains of total sulfur per 100 dry standard cubic feet.

Controlled recovery systems identified in this permit shall be directed to an operating process or to a collection system that is vented through a control device meeting the requirements of this permit condition

(1) Vapor Combustor.

(a) The vapor combustor unit (VCU) shall achieve a 99% control of the waste gas directed to it.

(b) The temperature in, or immediately downstream of the combustion chamber of the vapor combustor shall be maintained at not less than 1400°F and waste gas flows shall be limited to assure at least a 0.5 second residence time in the fire box while waste gas is being fed into the combustor.

(c) The combustor exhaust temperature shall be continuously monitored and recorded when waste gas is directed to the oxidizer. The temperature measurements shall be made at intervals of six minutes or less and recorded at that frequency.

The temperature measurement device shall be installed, calibrated, and maintained according to accepted practice and the manufacturer's specifications. The device shall have an accuracy of the greater of ±0.75 percent of the temperature being measured expressed in degrees Celsius or ±2.5ºC.

(d) The vapor combustor shall be operated with no visible emissions.

(2) The plant flare system

(a) The heating value and velocity requirements in 40 CFR 60.18 shall be satisfied during operations authorized by this permit.

(b) The flare shall be operated with a flame present at all times and/or have a constant pilot flame. The pilot flame shall be continuously monitored by a thermocouple or an infrared monitor. The time, date, and duration of any loss of pilot flame shall be recorded. Each monitoring device shall be accurate to, and shall be calibrated at a frequency in accordance with, the manufacturer's specifications.

(c) Each flare controlling MSS activities shall be equipped with a continuous flow monitor that provides a record of the flare gas flow and a heating value monitor that measures the heating value of the flare gas. The flow monitor and heating value monitor sample point shall be installed as near as possible to the flare inlet such that the total vent stream to the flare is measured and analyzed. Readings shall be taken at least once every 15 minutes and the average hourly values of the flow and heating value shall be recorded each hour.

90. The following requirements apply to capture systems for the plant flare system.

A. Either conduct a once a month visual, audible, and/or olfactory inspection of the capture system to verify there are no leaking components in the capture system; or verify the capture system is leak-free by inspecting in accordance with 40 CFR Part 60, Appendix A, Test Method 21 once a year. Leaks shall be indicated by an instrument reading greater than or equal to 500 ppmv above background.

B. The control device shall not have a bypass.

or

If there is a bypass for the control device, comply with either of the following requirements:

(1) Install a flow indicator that records and verifies zero flow at least once every fifteen minutes immediately downstream of each valve that if opened would allow a vent stream to bypass the control device and be emitted, either directly or indirectly, to the atmosphere; or

(2) Once a month, inspect the valves, verifying the position of the valves and the condition of the car seals that prevent flow out the bypass.

These requirements do not apply to high point vent and low point drain valves. A deviation shall be reported if the monitoring or inspections indicate bypass of the control device when required to be in service per this permit.

C. If any of the above inspections is not satisfactory, the permit holder shall promptly take necessary corrective action. Records shall be maintained documenting the performance and results of the inspections required above.

Additional Permit Requirements

91. The permit holder shall submit a complete as built representation to the coker project amendment, PI-1 dated February 27, 2017 no later than 30 days the start of operation of coker CSV844. (**09/18**)

Referenced PBRs

92. The following sources and/or activities are authorized under a Permit by Rule (PBR) by Title 30 Texas Administrative Code Chapter 106 (30 TAC Chapter 106). These lists are not intended to be all inclusive and can be altered without modifications to this permit. (**4/18**)

Authorization	Source or Activity
PBR No. 87917	Increase butane defluorinator operation
PBR No. 109221	MSS fugitives emissions
PBR No. 131468	Increase in MSS fugitive emissions
PBR No. 135706	Amine Improvement Project

Dated: November 16, 2018

Attachment 1

Permit Numbers 6825A, PSD-TX-49, and N65

Cap Emission Points by Source Category

Source Category: COEX II (1) (2)	
EPN	SOURCE DESCRIPTION
E-01-943	HCU-943 Reactor 1 Furnace
E-01-943	HCU-943 Reactor 2 Furnace
E-02-943	HCU-943 Fractionator Feed Furnace
E-26-FLARE	HCU-943 Flare
F-446CT	Cooling Tower 446
E-432-CT	Cooling Tower 432
F-943	HCU-943 Fugitives
F-943-SCR	HCU-943 Ammonia Storage and Piping
F-7843	Amine Treating Unit
F-7945	SGRU-7945 Fugitives
F-8748-SWS	Sour Water Stripper Fugitives
T-CX2-SW-2	Sour Water Storage Tank
T-CX2-CRUDE-1	Crude Oil Storage Tank
T-CX2-CRUDE-2	Crude Oil Storage Tank
T-CX2-NAPTH-1	Naphtha Storage Tank
T-CX2-GASOL-1	Gasoline (RVP 12) Storage Tank
T-CX2-GASOL-2	Gasoline (RVP 12) Storage Tank
T-2186	Diesel Storage Tank
T-CX2-RESID-1	Residual/No. 8 Oil Storage Tank 106
T-CX2-RESID-2	Residual/No. 8 Oil Storage Tank 3006
T-CX2-Amine-1	Spent Amine Storage Tank 5002
T-CX2-Amine-2	Fresh Amine Storage Tank 5003

Source Category: Coke	
EPN	SOURCE DESCRIPTION
F-843PM	DCU-843 PM Fugitives
FIN	SOURCE DESCRIPTION
F-843-1	Coke Drum to Pit
F-843-2	Coke Pit/Pad Stockpile
F-843-2A	Coke CO-2A to ST-2 and ST-3
F-843-3	Coke Pit to Coke Pad
F-843-4	Coke Feeder/Breaker
F-843-4A	Coke Drop to Hopper
F-843-4B	Coke Drop to CO-1
F-843-4C	Coke Feeder/Breaker
F-843-4D	Coke Drop to Hopper
F-843-5	Coke CO-1 to CO-2
F-843-6	Coke CO-2 to ST-1
F-843-7	Coke ST-1 to West Stockpile
F-843-7A	Coke ST-2 to East Stockpile

Source Category: Coke	
EPN	SOURCE DESCRIPTION
F-843-7B	Coke ST-3 to East Stockpile
F-843-8	Coke Active Stockpile
F-843-9	Coke CO-3a to CO-4
F-843-9A	Coke CO-3c to Hopper
F-843-9B	Coke Truck/Railcar Loading
F-843-9C	Coke FO-1 to CO-4a
F-843-9D	Coke FO-2 to CO-4a
F-843-10	Coke CO-3b to CO-4
F-843-10A	Coke CO-4a Outbound from East Pile
F-843-11	Coke CO-4 to CO-5
F-843-12	Coke CO-4 to Shiploader 1
F-843-13	Coke CO-5 to Shiploader 2
F-843-14	Coke Shiploader 1 to Ship
F-843-15	Coke Shiploader 2 to Ship
F-843-16	Coke Conveyor CO-2 to West Pile Section
F-843-16A	Coke Conveyor CO-2a to East Pile Section
F-843-17	Coke Conveyor CO-4 to Ship

Source Category: Cooling Towers	
EPN	SOURCE DESCRIPTION
CT-100	GFU-241/242 Cooling Tower
F-101CT	GFU-243 Cooling Tower
F-136ACT	FCCU-1241 Cooling Tower
F-136BCT	SGRU-1242 Cooling Tower
F-233PS	GFU-244 Cooling Tower
CT-244	HFAU-443 Cooling Tower
F-360PS	CRU-1344 Cooling Tower
F-363CT	GHU-245 Cooling Tower
F-354CT	SRU-543 Cooling Tower
F-366CT	AVU-146 Cooling Tower
F-432-CT	AVU-147 Cooling Tower
F-433-CT	DHT-246 Cooling Tower
F-169BCT	DCU-841/842 Cooling Tower
F-191CT	DCU 843/HCU 942 Cooling Tower
F-314PS	BH16 Cooling Tower
F-316PS	BH15 Cooling Tower

Source Category: FCCU	
EPN	SOURCE DESCRIPTION
E-01-WGS	FCCU Regenerator

Source Category: Fired Units	
EPN	SOURCE DESCRIPTION
E-01-BH15	Boiler House 15 Boiler 41

Source Category: Fired Units	
EPN	SOURCE DESCRIPTION
E-01-146	Atmospheric Crude Unit No. 146 H-101
E-01-147	Atmospheric Crude Unit 147 HTR-1
E-01-241	Gulfining Unit No. 241 B-101
E-01-242	Gulfining Unit No. 242 B-201
E-01-243	Gulfining Unit No. 243 B-301
E-01-244	GFU-244 Heater F-101
E-01-244	GFU-244 Heater F-102
E-01-246	DHT-246 Heater H-1
E-01-443	HF Alkylation Unit No. 443 H-1
E-01-841	DCU-841 Heater H-1B
E-01-842	DCU-842 Heater 101-BA
E-01-843	DCU No. 843 F-1000
E-01-942	HCU No. 942 F-1300 Fractionator Feed Furnace
E-01-942	HCU No. 942 F-1000 First Stage Reactor Furnace
E-01-942	HCU No. 942 Second Stage Reactor Furnace
E-01-ESP	CO 9 Boiler
E-02-BH15	Boiler House 15 Boiler 42
E-02-18BH	Boiler House 18 Boiler 4
E-02-146	Vacuum Crude Unit No. 146 H-102A
E-02-146	AVU-146 Vacuum Heater H-102B
E-02-147	AVU-147 Vacuum Heater H-101
E-02-842	DCU-842 Heater 101-BB
E-02-843	DCU No. 843 F-2000
E-03-15BH	Boiler House 15 Boiler 43
E-03-16BH	Boiler House 16 Boiler 31 (3)
E-03-18BH	Boiler House 18 Boiler 5
E-03-842	DCU-842 Heater 201-B
E-03-843	DCU No. 843 F-3000
E-04-15BH	GTG-1 (4)
E-04-16BH	Boiler House 16 Boiler 32 (3)
E-05-16BH	Boiler House 16 Boiler 33 (3)
E-06-16BH	GTG-5 and Boiler House 16 Boiler 34 (3)
E-06-843	DCU-843 Two Tank Heaters for Charge Tanks
E-07-16BH	GTG-5 and Boiler House 16 Boiler 35 (3)
E-01-1344	CRU-1344 Heater H-1
H-02-1344	CRU-1344 Heater H-31
E-02-1344	CRU-1344 Heater H-33
E-03-1344	CRU-1344 Heater H-2
E-03-1344	CRU-1344 Heater H-3
E-03-1344	CRU-1344 Heater H-32

Source Category: Flares	
EPN	SOURCE DESCRIPTION
E-05-FLARE	Flare No. 5
E-07-FLARE	Flare No. 7
E-12-FLARE	Flare No. 12
F-13-FLARE	Flare No. 13

Source Category: Flares	
EPN	SOURCE DESCRIPTION
F-15-FLARE	Flare No. 15
F-18-FLARE	Flare No. 18
F-19-FLARE	Flare No. 19
F-20-FLARE	Flare No. 20
F-22-FLARE	Flare No. 22
E-23-FLARE	Flare No. 23
F-103FLARE	Flare No. B-103

Source Category: Fugitive	
EPN	SOURCE DESCRIPTION
F-15BH	BH 15 Fugitives
F-16BH	BH 16 Fugitives
F-18BH	BH-18 Fugitives
F-146	AVU-146 Fugitives
F-147	AVU-147 Fugitives
F-241	GFU-241 Fugitives
F-242	GFU-242 Fugitives
F-243	GFU-243 Fugitives
F-244	GFU-244 Fugitives
F-245	GHU-245 Fugitives
F-246	DHT-246 Fugitives
F-443	HFAU-443 Fugitives
F-541/3	SRU-541/2/3 Fugitives
F-544	SRU-544 Fugitives
F-545	SRU-545 Fugitives
F-546	SRU-546 Fugitives
F-841	DCU-841 Fugitives
F-842	DCU-842 Fugitives
F-843	DCU-843 Fugitives
F-942	HCU-942 Fugitives
F-1241	FCCU-1241 Fugitives
F-1242	SGRU-1242 Fugitives
F-1344	CRU-1344 Fugitives
F-7542	MRU-7542 Fugitives
F-7842	ATU-7842 Fugitives
F-7848	ATU-7848 Fugitives
F-DOCKS	DOCKS Fugitives
F-FGMD	FGMD Fugitives
F-41PH	PH41 Fugitives
F-PH84	PH84 Fugitives
F-163PH	PH163 Fugitives
F-PIPING	Piping Fugitives
F-SRTF	Sabine Road Tank Farm (SRTF) Fugitives
F-SRTF-BUT	SRTF-BUT Fugitives
Fugitive	Fugitives
F-Tanks	Fugitives from Tanks Rollover

Source Category: Land Loading	
EPN	SOURCE DESCRIPTION
E-02-SRK	Sulfur Truck Loading Rack
E-03-SRURK	Sulfur Truck Loading Rack
F-LOADING	Sulfur Truck Loading Rack

Source Category: Marine Loading	
EPN	SOURCE DESCRIPTION
E-BERTH0-0	Marine loading emissions - berth 0
E-BERTH1-1	Marine loading emissions - berth 1
E-BERTH1-2	Marine loading emissions - berth 1
E-BERTH2-5	Marine loading emissions - berth 2
E-BERTH2-6	Marine loading emissions - berth 2
E-BERTH3-7	Marine loading emissions - berth 3
E-BERTH3-8	Marine loading emissions - berth 3
E-BERTH5-11	Marine loading emissions - berth 5
E-BERTH5-12	Marine loading emissions - berth 5
E-BERTH6-14	Marine loading emissions - berth 6
E-BERTH6-15	Marine loading emissions - berth 6
E-MC-24-25	Marine Vapor Combustors 24 and 25

Source Category: Storage Tanks	
EPN	SOURCE DESCRIPTION
5110	Tank 1802
5207	Tank 2136
2101	Tank 2101
E-01-SUMP	Sump
5	Distillate Storage Tank 5
31	Tank 31
T-36	Tank 36
77	Gasoline (RVP 12) Storage Tank 77
78	Sour Water Storage Tank 78
88	Sour Water Storage Tank 88
T-108	Residual/No. 6 Oil Storage Tank 108
T-109	Residual/No. 6 Oil Storage Tank 109
133	Tank 133
151	Crude Oil Storage Tank 151
T-546-1	SRU-546 Storage Tank
T-546-2	SRU-546 Storage Tank
889	Tank 889
925	Naphtha Storage Tank 925
TK-2109	Tank 2109
2110	Gasoline (RVP 12) Storage Tank 2110
2111	Gasoline (RVP 12) Storage Tank 2111
2112	Gasoline (RVP 12) Storage Tank 2112

Source Category: Storage Tanks	
EPN	SOURCE DESCRIPTION
2113	Tank 2113
2117	Gasoline (RVP 12) Storage Tank 2117
T-2118	Gasoline (RVP 12) Storage Tank 2118
2132	Gasoline (RVP 12) Storage Tank 2132
2137	Gasoline (RVP 12) Storage Tank 2137
2145	Gasoline (RVP 12) Storage Tank 2145
2148	Gasoline (RVP 12) Storage Tank 2148
2159	Gasoline (RVP 12) Storage Tank 2159
2160	Gasoline (RVP 12) Storage Tank 2160
2161	Gasoline (RVP 12) Storage Tank 2161
2182	Tank 2182
2183	Naphtha Tank 2183
2588	Sour Water Storage Tank 2588
2590	Sour Water Storage Tank 2590
T-7842-1	Tank T-7842-1
T-7842-2	Tank T-7842-2

Source Category: Sulfur Recovery Units	
EPN	SOURCE DESCRIPTION
E-01-SCOT	SCOT I TGCU Incinerator
E-02-SCOT	SCOT II TGCU Incinerator
E-03-SCOT	SCOT III TGCU Incinerator
E-04-SCOT	SCOT IV TGCU Incinerator

NOTES:

(1) Facilities associated with COEX II project authorized by amendment approved on July 24, 2008. Nonattainment Permit N65 applies to VOC emissions from COEX II facilities.

(2) The facilities are not included in the emission caps in the MAERT.

(3) Boiler House No. 19, Boiler No. 1 (EPN E-01-19BH), Boiler No. 2 (EPN E-02-19BH), Boiler No. 3 (EPN E-03-19BH) , and BH 19 Fugitives (EPN F-19BH) are authorized by Permit 103765. Boiler House (BH) 16 Boiler 16-31 (EPN E 03-16BH), BH16 Boiler 16-32 (EPN E 04-16BH), BH16 Boiler 16-33 (EPN E 05-16BH), BH16 Duct Burners 16-34 and 16-35 (EPNs E 06-16BH and E 07-16BH), and Gas Turbine Generator - 2 (EPN E 08-16BH) must be shutdown before the shakedown of the Boiler House 19 boilers (EPNs E-01-19BH, E-02-19BH, and E-03-19BH) is completed. CHeck

(4) Unit will be shutdown with Boilerhouse 15 low NOx burner project.

Dated: August 5, 2013

ATTACHMENT 2

Permit Numbers 6825A, PSD-TX-49, and N65

Relief Valves Not Vented to Control

Unit Description	Component Tag	Comments
F-1241	4794	Route to flare in next scheduled T/A
F-1241	4799	Route to flare in next scheduled T/A
F-1241	4829	Route to flare in next scheduled T/A
F-1241	4832	Route to flare in next scheduled T/A
F-1241	4836	Route to flare in next scheduled T/A
F-1344	1867	Recycle Hydrogen Service
F-1344	1957	Recycle Hydrogen Service
F-1344	1981	Recycle Hydrogen Service
F-1344	2100	Recycle Hydrogen Service
F-15BH	12	Knock-out drum for 15 BH.
F-16BH	17	Remove from service by 2017.
F-16BH	94	Remove from service by 2017.
F-16BH	140	Remove from service by 2017.
F-16BH	222	Remove from service by 2017.
F-16BH	236	Remove from service by 2017.
F-16BH	250	Remove from service by 2017.
F-241	2334	PSV routed to flare 1/2" pilot routed to atmosphere
F-241	2354	PSV routed to flare 1/2" pilot routed to atmosphere
F-241	2390	PSV routed to flare 1/2" pilot routed to atmosphere
F-241	2396	PSV routed to flare 1/2" pilot routed to atmosphere
F-241	2406	PSV routed to flare 1/2" pilot routed to atmosphere
F-241	2414	PSV routed to flare 1/2" pilot routed to atmosphere
F-241	2420	PSV routed to flare 1/2" pilot routed to atmosphere
F-243	50484.1	PSV routed to flare 1/2" pilot routed to atmosphere
F-245	1223	PSV routed to flare 1/2" pilot routed to atmosphere
F-245	1224	PSV routed to flare 1/2" pilot routed to atmosphere
F-245	2152	PSV routed to flare 1/2" pilot routed to atmosphere
F-6341	133042	Route to flare in next scheduled T/A
F-6341	133043	Route to flare in next scheduled T/A
F-AUCT	100073	LPG Service
F-AUCT	100074	LPG Service
F-AUCT	100088	LPG Service
F-AUCT	100089	LPG Service
F-AUCT	100109	LPG Service
F-AUCT	100110	LPG Service
F-DOCKS	1215	Low potential for Relief - no flare nearby
F-DOCKS	1560	Low potential for Relief - no flare nearby
F-DOCKS	1674	Low potential for Relief - no flare nearby
F-DOCKS	1900	Low potential for Relief - no flare nearby
F-DOCKS	2108	Low potential for Relief - no flare nearby
F-DOCKS	2581	Low potential for Relief - no flare nearby
F-FUELING STATION	2639	Mobile equipment fueling station, no flare nearby
F-FUELING STATION	2641	Mobile equipment fueling station, no flare nearby
F-FUELING STATION	2644	Mobile equipment fueling station, no flare nearby

Unit Description	Component Tag	Comments
F-FUELING STATION	2645	Mobile equipment fueling station, no flare nearby
F-PH163 F-163PH	213	Tank Relief, not normally routed to flare
F-PH163 F-163PH	217	Tank Relief, not normally routed to flare
F-PH84	12072	LPG Service
F-PH84	12072.1	LPG Service
F-PH84	12074	LPG Service
F-PH84	12074.1	LPG Service
F-PH84	12189	LPG Service
F-PH84	12189.1	LPG Service
F-PH84	12192	LPG Service
F-PH84	12192.1	LPG Service
F-PH84	12330	LPG Service
F-PH84	12330.2	LPG Service
F-PH84	12332	LPG Service
F-PH84	12332.2	LPG Service

Dated: January 24, 2013

Emission Sources - Maximum Allowable Emission Rates

Permit Number 6825A, PSDTX49M1, N65

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities, sources, and related activities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

Air Contaminants Data

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
Emission Caps (11)				
		SO_2	771.9	1,977 (12)
		SO_2	705.4 (12)	1,503 (6) (12)
		NO_x	885.8	3,191 (12)
		NO_x	859.9	1,611 (6) (12)
		CO	1207	3,780.00 (12)
		CO	1174	2,950 (6) (12)
		PM	132.6	538.00
		PM	120.8	455.00 (6)
		Ammonia	0.10	0.20
		Ammonia (5)	1.43	4.87
		Ammonia (6)	2.66	8.99
		H_2S	4.64	11.40
		Benzene	2.77	9.39
		HF	0.33	1.64
		MTBE	12.11	27.89
		VOC	564	1,592
		VOC (14)	562.2	1,557
		VOC (18)		1,729

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
Emissions not in permit emission caps:				
BH15MSS	Burner Installation (15)	NO_x	130.50	1.44
		CO	283.10	3.11
E-01-1241	Heater 1241-H1 MSS	VOC	0.10	0.40
		NO_x	0.20	0.90
		SO_2	0.01	0.01
		CO	0.20	0.90
		PM	0.10	0.40
E-02-1241	Heater 1241-H2 MSS	VOC	0.10	0.40
		NO_x	0.20	0.90
		SO_2	0.01	0.01
		CO	0.20	0.90
		PM	0.10	0.40
E-01-245	Heater 245	NO_x	1.44	6.31
		VOC	0.18	0.77
		SO_2	0.85	3.73
		SO_2 (20)	0.85	0.96
		CO	2.48	10.84
		PM	0.26	1.07
		PM_{10}	0.26	1.07
		$PM_{2.5}$	0.26	1.07
E-V54	CCR Regen Vent	HCl	0.02	0.07

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
		VOC	0.16	0.70
F-20-Flare	Flare 20 MSS	VOC	0.06	0.28
		NO_x	0.87	3.81
		SO_2	0.80	3.50
		CO	2.40	10.50
F-PIPE	F-PIPE	VOC	0.18	0.78
F-943, F-7843, F-7945, F-8748-SWS, E-26-FLARE, T-CX2-SW-2, T-CX2-CRUDE-1, T-CX2-CRUDE-2, T-CX2-NAPTH-1, T-CX2-GASOL-1, T-CX2-GASOL-2, T-2186, T-CX2-RESID-1, T-CX2-RESID-2, T-CX2-Amine-1, T-CX2-Amine-2, E-01-943, E-02-943, F-432-CT, F-446CT	COEXII VOC Cap (9)	VOC	37.92	108.25
1913FUG	Tank 1913 Fugitives (4) (17)	VOC	0.02	0.09
1913	Tank 1913 (17)	VOC	0.32	1.41
T-82	Tank 82	VOC	0.62	0.15
T-283	Tank 283	VOC	6.62	3.05
T-284	Tank 284	VOC	6.62	3.05
T-285	Tank 285	VOC	6.62	3.05
T-106	Tank 106	VOC	8.99	2.70
T-107	Tank 107	VOC	9.01	2.73
T-100	Tank 100	VOC	42.70	2.98

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
T-103	Tank 103	VOC	31.80	2.98
T-110	Tank 110	VOC	7.26	2.48
T-926	Tank 926	VOC	2.98	6.89
T-1848	Tank 1848	VOC	1.26	0.30
T-2164	Tank 2164	VOC	34.28	10.97
T-2163	Tank 2163	VOC	34.28	10.97
T-2105	Tank 2105	VOC	36.04	7.55
T-99	Tank 99	VOC	26.97	2.98
T-111	Tank 111	VOC	7.26	2.48
T-112	112	VOC	9.49	3.50
		H_2S	0.14	0.24
T-113	113	VOC	9.49	3.50
		H_2S	0.14	0.24
T-114	114	VOC	9.49	3.50
		H_2S	0.14	0.24
T-8010	Coker 843 sludge tank	VOC	0.04	0.18
T-8400	Coker 844 sludge tank	VOC	0.04	0.18
T-8002	547 Sulfur Tank	H_2S	0.48	0.39
T-2162	Tank 2162	VOC	2.06	1.11
T-896	Tank 896	VOC	2.75	7.26
T-1849	Tank 1849	VOC	1.68	2.30
T-2133	Tank 2133	VOC	4.53	11.15

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
F-136ACT	Cooling Tower 136A	PM	0.73	2.14
		PM_{10}	0.73	2.14
		$PM_{2.5}$	0.73	2.14
F-136BCT	Cooling Tower 136B	PM	0.74	2.17
		PM_{10}	0.74	2.17
		$PM_{2.5}$	0.74	2.17
F-366CT	Cooling Tower 366	PM	0.56	1.64
		PM_{10}	0.56	1.64
		$PM_{2.5}$	0.56	1.64
E-01-844	DCU 844 Coker Furnace #1	NO_x	3.45	13.75
		NO_x (MSS)	34.55	(22)
		VOC	1.24	4.94
		SO_2	5.34	3.93
		CO	16.57	32.97
		CO (MSS)	82.83	(22)
		PM	1.84	6.99
		PM_{10}	1.84	6.99
		$PM_{2.5}$	1.84	6.99
		NH_3	1.01	4.00

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
E-02-844	DCU 844 Coker Furnace #2	NO_x	3.45	13.75
		NO_x (MSS)	34.55	(22)
		VOC	1.24	4.94
		SO_2	5.34	3.93
		CO	16.57	32.97
		CO (MSS)	82.83	(22)
		PM	1.84	6.99
		PM_{10}	1.84	6.99
		$PM_{2.5}$	1.84	6.99
		NH_3	1.01	4.00
F-LOADING	SRU 547 Truck Sulfur Loading	H_2S	0.72	0.62

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
E-05-SCOT	SRU 547	VOC	0.45	1.96
		NO_x	6.63	29.03
		CO	36.19	63.41
		SO_2	81.46	142.72
		PM	1.23	5.41
		PM_{10}	1.23	5.41
		$PM_{2.5}$	1.23`	5.41
		H_2S	0.88	3.85
CSV844	Coker Unit 844 Steam Vent	VOC	55.00	35.50
		PM	1.31	0.85
		PM_{10}	1.31	0.85
		$PM_{2.5}$	1.31	0.85
		H_2S	3.13	2.02
CSV843	Coker Unit 843 Steam Vent	VOC	55.00	61.38
		PM	7.72	8.61
		PM_{10}	7.72	8.61
		$PM_{2.5}$	7.72	8.61
		H_2S	18.38	20.51
		PM (21)	2.28	1.75
		PM_{10} (21)	2.28	1.75
		$PM_{2.5}$ (21)	2.28	1.75
		H_2S (21)	5.43	4.18

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
F-844PM	Unit 844 coke handling (FINS F-844-1 to F-844-6)	PM	0.26	0.40
		PM_{10}	0.12	0.19
		$PM_{2.5}$	0.02	0.03
WWC	Coker 844 Wastewater Collection System	VOC	0.01	0.03
MSS	Coker 844 Project MSS (23)	VOC	542.76	5.49
		NO_x	29.03	0.51
		CO	194.71	3.27
		SO_2	299.15	8.97
		H_2S	3.18	0.19
		PM	1.48	<0.01
		PM_{10}	1.48	<0.01
		$PM_{2.5}$	1.48	<0.01

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
Emissions in permit emission caps:				
E-01-BH 15	Boiler 15-41, Pre-mod. (7)	NO_x	26.10	114.32
		VOC	2.35	9.97
		SO_2	19.58	21.63
		CO	35.82	72.33
		PM	3.05	13.34
E-02-BH 15, E-03-BH 15, E-04-BH 15	Boilerhouse 15 Subcap, Pre-mod (7)	NO_x	213.56	314.3
		VOC	12.30	26.99
		SO_2	129.01	211.9
		CO	101.29	222.21
		PM	8.62	37.78
E-01-BH 15, E-02-BH 15, E-03-BH 15	Boilerhouse 15 Subcap, Post-mod Phase I (8)	NO_x	78.03	247.5
		VOC	7.05	22.27
		SO_2	58.74	37.12
		CO	107.46	169.9
		PM	9.15	31.09
E-01-BH 15, E-02-BH 15, E-03-BH 15	Boilerhouse 15 Subcap Post-mod PhaseII (13)	NO_x	78.03	339.0
		VOC	7.05	30.51
		SO_2	58.74	50.85
		CO	107.46	232.8
		PM	9.15	31.09
E-06-BH 16	Boiler 16-34 (10)	NO_x (16)	6.50	28.60
E-07-BH 16	Boiler 16-35 (10)	NO_x (16)	9.00	39.40

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
E-08-BH 16	Boiler 16-36 (10)	NO_x (16)	42.00	72.67
E-06-BH 16, E-07-BH 16, E-08-BH 16	Boilerhouse 16 Subcap (10)	NO_x	200.41	414.5
		VOC	12.55	27.49
		SO_2	98.37	161.58
		CO	103.35	226.36
		PM	8.79	38.49
E-01-146	Heater 146-H101	NO_x	49.56	146.99
		VOC	3.34	12.18
		SO_2	11.36	18.67
		CO	48.78	67.14
		PM	4.34	16.83
		NO_x (20)	36.85	149.66
		VOC (20)	2.97	12.05
		SO_2 (20)	19.73	14.84
		CO (20)	37.22	75.58
		CO (MSS) (20)	87.97	(22)
		PM (20)	4.10	16.64
		PM_{10} (20)	4.10	16.64
		$PM_{2.5}$ (20)	4.10	16.64

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
E-02-146	Heater 146-H102AB	NO_x	19.88	52.36
		VOC	1.60	5.04
		SO_2	5.43	8.92
		CO	19.59	27.76
		PM	2.08	6.96
		NO_x (20)	16.12	70.61
		VOC (20)	1.40	6.14
		SO_2 (20)	9.33	7.57
		CO (20)	17.59	38.53
		CO (MSS) (20)	87.97	(22)
		PM (20)	1.94	8.49
		PM_{10} (20)	1.94	8.49
		$PM_{2.5}$ (20)	1.94	8.49
E-01-147	Heater 147-F-1100	NO_x	13.86	60.71
		VOC	2.14	9.35
		SO_2	10.59	17.39
		SO_2 (20)	10.59	7.58
		CO	32.61	68.93
		PM	2.95	12.92
		PM_{10}	2.95	12.92
		$PM_{2.5}$	2.95	12.92
E-02-147	Heater 147-F-1200	NO_x	7.80	17.28
		VOC	0.92	3.29

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
		SO_2	4.10	5.66
		SO_2 (20)	4.10	3.29
		CO	10.89	19.25
		PM	1.28	5.60
		PM_{10}	1.28	5.60
		$PM_{2.5}$	1.28	5.60
E-01-1344	Heater 1344-H1	NO_x	34.09	115.39
		VOC	3.65	14.80
		SO_2	11.95	19.64
		SO_2 (20)	11.95	18.53
		CO	40.45	82.24
		PM	5.05	20.45
		PM_{10}	5.05	20.45
		$PM_{2.5}$	5.05	20.45
E-02-1344	Heater 1344-H33	NO_x	3.82	9.06
		VOC	0.28	1.22
		SO_2	0.85	1.39
		CO	4.26	9.33
		PM	0.38	1.69
		PM_{10}	0.38	1.69
		$PM_{2.5}$	0.38	1.69
E-03-1344	Heater 1344-H2_3_32	NO_x	12.80	26.81
		VOC	0.86	2.41

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
		SO_2	2.89	4.75
		SO_2 (20)	2.89	3.02
		CO	10.64	13.43
		PM	1.19	3.33
		PM_{10}	1.19	3.33
		$PM_{2.5}$	1.19	3.33
E-01-843	Heater 843-H1	NO_x	16.00	53.40
		VOC	1.44	5.42
		SO_2	6.79	9.32
		SO_2 (20)	6.79	4.38
		CO	21.96	31.76
		PM	1.99	7.50
		PM_{10}	1.99	7.50
		$PM_{2.5}$	1.99	7.50
E-02-843	Heater 843-H2	NO_x	16.00	53.40
		VOC	1.44	5.42
		SO_2	6.79	9.32
		SO_2 (20)	6.79	4.38
		CO	21.96	31.76
		PM	1.99	7.50
		PM_{10}	1.99	7.50
		$PM_{2.5}$	1.99	7.50
E-03-843	Heater 843-H3	NO_x	16.00	53.40

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
		VOC	1.44	5.42
		SO_2	6.79	9.32
		SO_2 (20)	6.79	4.38
		CO	21.96	31.76
		PM	1.99	7.50
		PM_{10}	1.99	7.50
		$PM_{2.5}$	1.99	7.50
E-01-246	Heater 246-H1	NO_x	2.20	7.51
		VOC	0.34	1.06
		SO_2	1.44	1.86
		SO_2 (20)	1.44	0.88
		CO	4.07	6.19
		PM	0.47	1.47
		PM_{10}	0.47	1.47
		$PM_{2.5}$	0.47	1.47
E-01-1241	Heater 1241-H1	NO_x	4.96	1.24
		VOC	0.33	0.08
		SO_2	1.64	0.15
		CO	4.86	0.64
		PM	0.43	0.11
E-02-1241	Heater 1241-H2	NO_x	4.96	1.24
		VOC	0.33	0.08
		SO_2	1.64	0.15

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
		CO	4.86	0.64
		PM	0.43	0.11
E-01-241	Heater 241-B101AB	NO_x	7.92	19.51
		VOC	0.53	2.34
		SO_2	2.23	3.66
		SO_2 (20)	2.23	2.93
		CO	8.15	13.49
		PM	0. 73	3.24
		PM_{10}	0. 73	3.24
		$PM_{2.5}$	0. 73	3.24
E-01-242	Heater 242-B201AB	NO_x	6.62	17.45
		VOC	0.36	1.58
		SO_2	1.87	3.11
		SO_2 (20)	1.87	1.80
		CO	4.04	11.91
		PM	0.50	2.00
		PM_{10}	0.50	2.00
		$PM_{2.5}$	0.50	2.00

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
E-01-243	Heater 243	NO_x	7.10	19.43
		VOC	0.48	1.87
		SO_2	1.78	2.92
		SO_2 (20)	1.78	2.32
		CO	6.74	10.31
		PM	0.66	2.58
		PM_{10}	0.66	2.58
		$PM_{2.5}$	0.66	2.58
E-01-244	Heater 244 F-101/102	NO_x	7.92	34.70
		VOC	0.36	1.60
		SO_2	1.90	3.11
		SO_2 (20)	1.90	1.80
		CO	5.13	11.91
		PM	0.49	2.00
		PM_{10}	0.49	2.00
		$PM_{2.5}$	0.49	2.00

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
E-01-942	Heater 942-H1_2_3	NO_x	12.83	45.56
		VOC	1.15	4.55
		SO_2	5.45	7.98
		SO_2 (20)	5.45	3.68
		CO	17.61	26.75
		PM	1.60	6.29
		PM_{10}	1.60	6.29
		$PM_{2.5}$	1.60	6.29
E-01-443	Heater 443	NO_x	14.20	42.83
		VOC	1.09	3.88
		SO_2	3.34	5.49
		SO_2 (20)	3.34	4.86
		CO	16.67	21.44
		PM	1.51	5.35
		PM_{10}	1.51	5.35
		$PM_{2.5}$	1.51	5.35

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
REFFUG Includes: F-1241, F-1242, F-1344, F-146, F-147, F-15BH, F-16BH, F-241, F-242, F-243, F-244, F-245, F-246, F-443, F-545, F-546, F-547, F-6341, F-7542, F-7841, F-7842, F-7848, F-843, F-844, F-8746, F-8747, F-942, FUAUCT, F-DOCKS, F-544, F-Fueling Station, F-163PH, F-41PH, F-FGMD, F-SRTF, F-Utilities, F-8741, F-543/4, F-NSTF, F-BH-19, F-7843, F-943-75K, F-844, F-547,	Refinery Fugitives VOC Subcap (4)	VOC	259.49	1132.81
		H_2S	5.60	24.54
		NH_3	1.47	5.06
		HF	0.36	1.75
100, 103, 106, 107, 110, 111, 133, 151, 1848, 1849, 2101, 2105, 2106, 2110, 2111, 2112, 2113, 2117, 2132, 2133, 2137, 2145, 2147, 2148, 2159, 2160, 2161, 2162, 2163, 2164, 2182, 2183, 2588, 2590, 283, 284, 285, 31, 5, 77, 78, 82, 88, 889, 896, 925, 926, 99, T-108, T-109, T-546-1, T-546-2, T-7842-1, T-7842-2	Refinery Tank Subcap	VOC	218.70	153.30
E-05-FLARE, F-13-FLARE, F-15-FLARE, F-18-FLARE, F-19-FLARE, F-20-FLARE, F-22-FLARE, E-23-	Flares Subcap	NO_x	43.93	48.03
		VOC	65.74	85.10
		SO_2	24.87	13.57

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
FLARE, F-103-FLARE		CO	302.8	309.30
E-05-FLARE, F-13-FLARE, F-15-FLARE, F-18-FLARE, F-19-FLARE, F-20-FLARE, F-22-FLARE, E-23-FLARE, F-103-FLARE	Flares Subcap (14)	NO_x	43.93	38.67
		VOC	65.74	57.86
		SO_2	24.87	8.11
		CO	302.8	266.50
		H_2S	0.26	0.09
F-DOCK	Uncontrolled Marine Loading F-03-DOCK, F-02-DOCK, F-05-DOCK, F-06-DOCK, F-08-DOCK, F-07-DOCK, F-11-DOCK, F-12-DOCK, F-14-DOCK, F-15-DOCK	VOC	97.92	63.93
E-01-SCOT, E-02-SCOT, E-03-SCOT, E-04-SCOT	SRUs Subcap	NO_x	49.68	118.40
		VOC	64.24	151.90
		SO_2	345.83	1056.82
		CO	192.20	896.29
		PM	24.58	58.60
		PM_{10}	24.58	58.60
		$PM_{2.5}$	24.58	58.60
		H_2S	3.67	11.23
E-01-SCOT	SRU 543	SO_2	57.90	--
		H_2S	0.62	--
E-02-SCOT	SRU 544	SO_2	82.77	--

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
		H2S	0.88	--
E-03-SCOT	SRU 545	SO_2	137.89	--
		H_2S	1.47	--
E-04-SCOT	SRU 546	SO_2	137.89	--
		H_2S	1.47	--
E-02-SRK	SRU 543 and 544 sulfur loading	H_2S	0.36	0.28
E-06-843	Two Tank Heaters for Charge Tanks	NO_x	1.18	5.15
		VOC	0.06	0.28
		SO_2	0.31	0.51
		CO	1.02	4.47
		PM	0.09	0.39
E-01-943	HCU - Reactor 1 and Reactor 2 Furnaces	NO_x	7.81	28.51
		VOC (19)	0.60	2.20
		SO_2	8.20	11.23
		SO_2 (20)	8.20	5.87
		CO	14.93	27.27
		PM	1.66	6.07
		PM_{10}	1.66	6.07
		$PM_{2.5}$	1.66	6.07

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
E-02-943	HCU - Fractionator Feed Furnace	NO_x	5.22	22.86
		NO_x (Start-up)	52.20	(22)
		VOC (19)	1.88	8.22
		SO_2	13.31	17.51
		SO_2 (20)	13.31	10.79
		CO	23.27	50.97
		CO (Start-up)	116.37	(22)
		PM	2.90	11.81
		PM_{10}	2.90	11.81
		$PM_{2.5}$	2.90	11.81
		Ammonia	1.41	6.19
E-26-FLARE	HCU 943 Flare	NO_x	0.31	1.38
		SO_2	0.01	0.03
		CO	2.27	9.94

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
E-01-WGS	FCCU Wet Gas Scrubber	NO_x	327.70	271.93
		VOC	15.70	68.80
		SO_2	114.10	256.08
		CO	498.80	896.29
		PM	63.50	278.13
		NH_3	3.19	12.37
		HCN	89.80	347.95
		H_2SO_4	18.26	80.00
E-MC-24-25	DOCK-MC (24)	NO_x	49.68	20.83
		VOC	33.19	20.08
		CO	99.18	41.58
		SO_2	0.19	0.07
		PM	2.68	1.12
		PM_{10}	2.68	1.12
		$PM_{2.5}$	2.68	1.12
F-101CT	Cool Twr 101	VOC	1.30	5.70
F-136ACT	Cool Twr 136A	VOC	2.73	11.96
F-136BCT	Cool Twr 136B	VOC	2.77	11.96
F-233PS	Cool Twr 233	VOC	0.53	1.24
F-314PS	Cool Twr 314	VOC	0.01	0.01
F-316PS	Cool Twr 316	VOC	0.01	0.01
F-354CT	Cool Twr 354	VOC	0.25	1.10
F-360PS	Cool Twr 360	VOC	0.92	4.05

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
F-363CT	Cool Twr 363	VOC	0.42	0.89
F-366CT	Cool Twr 366	VOC	2.10	2.45
CT-100	Cool Twr 100	VOC	1.05	4.60
E-432-CT	Cool Twr 432	VOC	0.84	3.68
		PM	0.01	0.02
		PM_{10}	0.01	0.02
		$PM_{2.5}$	0.01	0.02
E-433-CT	Cool Twr 433	VOC	1.26	0.69
		VOC (20)	1.89	8.28
		PM (20)	0.56	1.97
		PM_{10} (20)	0.56	1.95
		$PM_{2.5}$ (20)	0.13	0.44
CT-244	Cool Twr 244	VOC	1.18	5.15
		VOC (20)	1.60	6.99
		PM (20)	0.48	6.99
		PM_{10} (20)	0.47	1.64
		$PM_{2.5}$ (20)	0.11	0.37

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
F-446CT	Cooling Tower 446	PM	0.03	0.11
		PM_{10}	0.03	0.11
		$PM_{2.5}$	0.03	0.11
		VOC (19)(20)	1.99	8.72
		PM (20)	0.59	8.72
		PM_{10} (20)	0.59	2.05
		$PM_{2.5}$ (20)	0.13	0.47
F-843PM	Unit 843 coke storage and loading (FINS F-843-1 to F-843-17)	PM	2.41	10.56
		$PM_{2.5}$	0.06	0.26
		PM (20)	5.17	8.71
		PM_{10} (20)	2.48	4.26
		$PM_{2.5}$ (20)	0.37	0.63

(1) Emission point identification - either specific equipment designation or emission point number (EPN) from a plot plan per Attachment 1.
(2) Specific point source names. For fugitive sources use area name or fugitive source name.
(3) VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1
NO_x - total oxides of nitrogen
SO_2 - sulfur dioxide
CH_4 - methane
CO - carbon monoxide
CO_2 - carbon dioxide
CO_2e - carbon dioxide equivalents based on the following Global Warming Potentials (1/2015): CO_2 (1), N_2O (298), CH_4(25), SF_6 (22,800), HFC (various), PFC (various).
N_2O - nitrous oxide
PM - particulate matter, suspended in the atmosphere, including PM_{10} and $PM_{2.5}$.
PM_{10} - particulate matter equal to or less than 10 microns in diameter.
$PM_{2.5}$ - particulate matter equal to or less than 2.5 microns in diameter
H_2S - hydrogen sulfide
HCl - hydrogen chloride
HF - hydrogen fluoride
MTBE - methyl-tertiary-butyl ether

Emission Sources - Maximum Allowable Emission Rates

N_2O - nitrous oxide
NH_3 - ammonia
HCN - hydrogen cyanide
H_2SO_4 - sulfuric acid

(4) Emission rate is an estimate and compliance is demonstrated by meeting the requirements of the applicable special conditions and permit application representations.
(5) Rates effective after facilities associated with COEX II Project are operating.
(6) Caps effective after sources associated with COEX II Project and EPNs E-01-19BH, E 02 19BH, and E-03-19BH are operating. Boilerhouse 15 low NO_x burner project and shutdown of Boilerhouse 16 combustion units must be complete.
(7) Allowable emission rates prior to the Boilerhouse 15 low NO_x burner project (Pre-mod).
(8) Post-mod Phase I: Allowable emission rates after the Boilerhouse 15 low NO_x burner project authorized by Standard Permit 91911. The turbine GTG-1 shall be shutdown as part of this project.
(9) These facilities were subject to nonattainment review for VOC for Permit N65. The MSS emissions associated with the COEX II facilities authorized in Permit Number 80812 must also be added to the routine emissions from the COEX II facilities to determine compliance with this annual emission cap.
(10) The Boilerhouse 16 units must be shutdown and the Boilerhouse 15 low NO_x burner project completed prior to the end of the 180 day shakedown period for Boilerhouse 19 Boilers 1, 2, and 3 {authorized by Permit 103765).
(11) These emission caps have been carried forward from the flexible permit. With the exception of VOC emissions from COEXII facilities, these caps apply to the sum total of all emissions of that pollutant from the facilities listed on Attachment I. In addition, the maintenance, startup, and shutdown (MSS) emissions authorized in Permit Number 80812 must also be added to the routine emissions from the facilities in Attachment I to determine compliance with these emission caps unless the cap is designated with a footnote (12). The emission caps that are not designated with a footnote (12) are those that are more limiting than the sum of the individual emission rate limits for those facilities. VOC MSS emissions from COEX II facilities do not need to be included when showing compliance with the annual VOC cap.
(12) These emission caps are the sum of the individual and subcap emission rates for the pollutant and are shown for information only.
(13) Post-mod Phase II: These allowable emission rates shall apply in lieu of those designated with footnote (8) (aka Post-mod Phase I) if the permit holder samples these facilities for $PM_{2.5}$ per Special Condition 40 after completing the Boilerhouse 15 low NO_x burner project and the results show $PM_{2.5}$ emissions are less than 73 percent of the maximum hourly total PM emission rate limit.
(14) Caps effective after start of operation of entire flare gas recovery system.
(15) Installation of low NO_x burners in Boilerhouse 15 boilers authorized by Standard Permit 91911.
(16) Installation of low NO_x burners in Boilerhouse 16 boilers authorized by Standard Permit 94365.
(17) Tank authorized by PBR Registration 84905.
(18) This emission cap applies to the sum of VOC emissions from all facilities listed in Attachment 1 and MSS activities authorized in this permit and from all facilities and MSS activities authorized in Permit 80812.
(19) Emissions are a subcap of COEXII VOC Cap.
(20) Emissions shall supersede all existing authorized limits of that pollutant upon completion of the facility's modification as represented in the Coker Project, PI-1 dated February 27, 2018. The modification shall be completed preceding the initial startup of the Coker Unit's DCU 844. **(11/18)**

Emission Sources - Maximum Allowable Emission Rates

(21) Limits apply January 1, 2019.
(22) Annual emissions are included as part of annual emissions authorized for normal facility operation.
(23) Hourly emissions from Flare EPNs E-23-Flare and E-26-Flare are a subcap of the emissions authorized for the flare in MSS permit 80812.
(24) Includes emissions from marine vapor combustors E-MC-24 and E-MC-25.

* Emission rates are based on operating 8,760 hrs/year.

** Compliance with annual emission limits is based on a rolling 12-month period

Date: November 16, 2018

Emission Sources - Maximum Allowable Emission Rates

Permit Number GHGPSDTX167

This table lists the maximum allowable emission rates of greenhouse gas (GHG) emissions, as defined in Title 30 Texas Administrative Code § 101.1, for all sources of GHG air contaminants on the applicant's property that are authorized by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities, sources, and related activities. Any proposed increase in emission rates may require an application for a modification of the facilities authorized by this permit.

Air Contaminants Data

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
E-01-245	Heater 245	CO_2 (5)	--	18,687.00
		N_2O (5)	--	0.03
		CH_4 (5)	--	0.32
		CO_2e	--	18,704.00
T-112	112	CH_4 (5)	-	0.03
		CO_2e	-	0.87
T-113	113	CH_4 (5)	-	0.03
		CO_2e	-	0.87
T-114	114	CH4 (5)	-	0.03
		CO_2e	-	0.87
E-01-844	DCU 844 Coker Furnace #1	CO_2 (5)	--	119,242.00
		N_2O (5)	--	0.20
		CH_4 (5)	--	2.02
		CO_2e	--	119,353.00
E-02-844	DCU 844 Coker Furnace #2	CO_2 (5)	--	119,242.00
		N_2O (5)	--	0.20
		CH_4 (5)	--	2.02
		CO_2e	--	119,353.00

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
E-05-SCOT	SRU 547	CO_2 (5)	--	90,029.00
		N_2O (5)	--	0.08
		CH_4 (5)	--	0.80
		CO_2e	--	90,072.00
CSV844	Coker Unit 844 Steam Vent	CH4 (5)	--	161.38
		CO_2e	--	4,034.00
CSV843	Coker Unit 843 Steam Vent	CH_4 (5)	--	279.00
		CO_2e	--	6,975.00
MSS	Coker 844 Project MSS	CO_2 (5)	--	1,101.00
		N_2O (5)	--	<0.01
		CH_4 (5)	--	0.02
		CO_2e	--	1,102.00
E-01-146	Heater 146-H101	CO_2 (5)	--	290,556
		N_2O (5)	--	0.49
		CH_4 (5)	--	4.92
		CO_2e	--	290,826.00

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
E-02-146	Heater 146-H102AB	CO_2 (5)	--	148,127.00
		N_2O (5)	--	0.25
		CH_4 (5)	--	2.51
		CO_2e	--	148.264.00
E-01-147	Heater 147-F-1100	CO_2 (5)	--	225,609.00
		N_2O (5)	--	0.38
		CH_4 (5)	--	3.82
		CO_2e	--	225,818.00
E-02-147	Heater 147-F-1200	CO_2 (5)	--	97,764.00
		N_2O (5)	--	0.17
		CH_4 (5)	--	1.66
		CO_2e (5)	--	97,855.00
E-01-1344	Heater 1344-H1	CO_2 (5)	--	356,986.00
		N_2O (5)	--	0.61
		CH_4 (5)	--	6.05
		CO_2e	--	357,317.00
E-02-1344	Heater 1344-H33	CO_2 (5)	--	29,568.00
		N_2O (5)	--	0.05
		CH_4 (5)	--	0.50
		CO_2e	--	29,596.00

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
E-03-1344	Heater 1344-H2_3_32	CO_2 (5)	--	58,111.00
		N_2O (5)	--	0.10
		CH_4 (5)	--	0.98
		CO_2e	--	58,165.00
E-01-843	Heater 843-H1	CO_2 (5)	--	130,921.00
		N_2O (5)	--	0.22
		CH_4 (5)	--	2.22
		CO_2e	--	131,043.00
E-02-843	Heater 843-H2	CO_2 (5)	--	130,921.00
		N_2O (5)	--	0.22
		CH_4 (5)	--	2.22
		CO_2e	--	131,043.00
E-03-843	Heater 843-H3	CO_2 (5)	--	130,921.00
		N_2O (5)	--	0.22
		CH_4 (5)	--	2.22
		CO_2e	--	131,043.00

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
E-01-246	Heater 246-H1	CO_2 (5)	--	25,637.00
		N_2O (5)	--	0.04
		CH_4 (5)	--	0.43
		CO_2e	--	25,661.00
E-01-241	Heater 241-B101AB	CO_2 (5)	--	56,516
		N_2O (5)	--	0.10
		CH_4 (5)	--	0.96
		CO_2e	--	56,569
E-01-242	Heater 242-B201AB	CO_2 (5)	--	34,924.00
		N_2O (5)	--	0.06
		CH_4 (5)	--	0.59
		CO_2e	--	34,956.00
E-01-243	Heater 243	CO_2 (5)	--	45,065
		N_2O (5)	--	0.08
		CH_4 (5)	--	0.76
		CO_2e	--	45,107
E-01-244	Heater 244 F-101/102	CO_2 (5)	--	34,924.00
		N_2O (5)	--	0.06
		CH_4 (5)	--	0.59
		CO_2e	--	34,956.00

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
E-01-942	Heater 942-H1_2_3	CO_2 (5)	--	109,785.00
		N_2O (5)	--	0.19
		CH_4 (5)	--	1.86
		CO_2e	--	109,887.00
E-01-443	Heater 443	CO_2 (5)	--	93,377.00
		N_2O (5)	--	0.16
		CH_4 (5)	--	1.58
		CO_2e	--	93,464.00
REFFUG Includes: F-1241, F-1242, F-1344, F-146, F-147, F-15BH, F-16BH, F-241, F-242, F-243, F-244, F-245, F-246, F-443, F-545, F-546, F-547, F-6341, F-7542, F-7841, F-7842, F-7848, F-843, F-844, F-8746, F-8747, F-942, FUAUCT, F-DOCKS, F-544, F-Fueling Station, F-163PH, F-41PH, F-FGMD, F-SRTF, F-Utilities, F-8741, F-543/4, F-NSTF, F-BH-19, F-7843, F-943-75K, F-844, F-547,	Refinery Fugitives VOC Subcap (4)	CH_4 (5)	-	113.03
		CO_2e	-	2826.00
E-01-943	HCU - Reactor 1 and Reactor 2 Furnaces	CO_2 (5)	--	105,968.00
		N_2O (5)	--	0.18
		CH_4 (5)	--	1.80
		CO_2e	--	106,066.00

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
E-02-943	HCU - Fractionator Feed Furnace	CO_2 (5)	--	198,262.00
		N_2O (5)	--	0.34
		CH_4 (5)	--	3.36
		CO_2e	--	198,446.00
E-MC-24-25	DOCK-MC	CO_2 (5)	--	184450.00
		N_2O (5)	--	0.35
		CH_4 (5)	--	3.48
		CO_2e	--	184,640.00

(1) Emission point identification - either specific equipment designation or emission point number from plot plan.
(2) Specific point source name. For fugitive sources, use area name or fugitive source name.
(3) CO_2 - carbon dioxide
N_2O - nitrous oxide
CH_4 - methane
CO_2e - carbon dioxide equivalents based on the following Global Warming Potentials (GWP) found in Table A-1 of Subpart A 40 CFR Part 98 (78 FR 71904) for each pollutant: CO_2 (1), N_2O (298), CH_4(25)
(4) Compliance with annual emission limits (tons per year) is based on a 12-month rolling period. These rates include emissions from maintenance, startup, and shutdown.
(5) Emission rate is given for informational purposes only and does not constitute enforceable limit.

Date: November 16, 2018