FEDERAL OPERATING PERMIT

A FEDERAL OPERATING PERMIT IS HEREBY ISSUED TO
Blanchard Refining Company LLC

AUTHORIZING THE OPERATION OF
Galveston Bay Refinery
Petroleum Refineries

LOCATED AT
Galveston County, Texas
Latitude 29° 22' 28" Longitude 94° 55' 30"
Regulated Entity Number: RN102535077

This permit is issued in accordance with and subject to the Texas Clean Air Act (TCAA), Chapter 382 of the Texas Health and Safety Code and Title 30 Texas Administrative Code Chapter 122 (30 TAC Chapter 122), Federal Operating Permits. Under 30 TAC Chapter 122, this permit constitutes the permit holder's authority to operate the site and emission units listed in this permit. Operations of the site and emission units listed in this permit are subject to all additional rules or amended rules and orders of the Commission pursuant to the TCAA.

This permit does not relieve the permit holder from the responsibility of obtaining New Source Review authorization for new, modified, or existing facilities in accordance with 30 TAC Chapter 116, Control of Air Pollution by Permits for New Construction or Modification.

The site and emission units authorized by this permit shall be operated in accordance with 30 TAC Chapter 122, the general terms and conditions, special terms and conditions, and attachments contained herein.

This permit shall expire five years from the date of issuance. The renewal requirements specified in 30 TAC § 122.241 must be satisfied in order to renew the authorization to operate the site and emission units.

Permit No: O1541 Issuance Date: February 22, 2017

For the Commission

Table of Contents

Section **Page**

General Terms and Conditions 1

Special Terms and Conditions: 1
- Emission Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting 1
- Additional Monitoring Requirements 15
- New Source Review Authorization Requirements 17
- Compliance Requirements 18
- Risk Management Plan 20
- Protection of Stratospheric Ozone 20
- Temporary Fuel Shortages (30 TAC § 112.15) 20
- Alternative Requirements 21
- Permit Location 21
- Permit Shield (30 TAC § 122.148) 21

Attachments 22
- Applicable Requirements Summary 23
- Additional Monitoring Requirements 726
- Permit Shield 785
- New Source Review Authorization References 838
- Schedules 892
- Alternative Requirement 898

Appendix A 911
- Acronym List 912

Appendix B 913

General Terms and Conditions

The permit holder shall comply with all terms and conditions contained in 30 TAC § 122.143 (General Terms and Conditions), 30 TAC § 122.144 (Recordkeeping Terms and Conditions), 30 TAC § 122.145 (Reporting Terms and Conditions), and 30 TAC § 122.146 (Compliance Certification Terms and Conditions).

In accordance with 30 TAC § 122.144(1), records of required monitoring data and support information required by this permit, or any applicable requirement codified in this permit, are required to be maintained for a period of five years from the date of the monitoring report, sample, or application unless a longer data retention period is specified in an applicable requirement. The five year record retention period supersedes any less stringent retention requirement that may be specified in a condition of a permit identified in the New Source Review Authorization attachment.

If the permit holder chooses to demonstrate that this permit is no longer required, a written request to void this permit shall be submitted to the Texas Commission on Environmental Quality (TCEQ) by the Responsible Official in accordance with 30 TAC § 122.161(e). The permit holder shall comply with the permit's requirements, including compliance certification and deviation reporting, until notified by the TCEQ that this permit is voided.

The permit holder shall comply with 30 TAC Chapter 116 by obtaining a New Source Review authorization prior to new construction or modification of emission units located in the area covered by this permit.

All reports required by this permit must include in the submittal a cover letter which identifies the following information: company name, TCEQ regulated entity number, air account number (if assigned), site name, area name (if applicable), and Air Permits Division permit number(s).

Special Terms and Conditions:

Emission Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting

1. Permit holder shall comply with the following requirements:

    A. Emission units (including groups and processes) in the Applicable Requirements Summary attachment shall meet the limitations, standards, equipment specifications, monitoring, recordkeeping, reporting, testing, and other requirements listed in the Applicable Requirements Summary attachment to assure compliance with the permit.

    B. The textual description in the column titled "Textual Description" in the Applicable Requirements Summary attachment is not enforceable and is not deemed as a substitute for the actual regulatory language. The Textual Description is provided for information purposes only.

    C. A citation listed on the Applicable Requirements Summary attachment, which has a notation [G] listed before it, shall include the referenced section and subsection for all commission rules, or paragraphs for all federal and state regulations and all subordinate paragraphs, subparagraphs and clauses, subclauses, and items contained within the referenced citation as applicable requirements.

    D. When a grouped citation, notated with a [G] in the Applicable Requirements Summary, contains multiple compliance options, the permit holder must keep records of when each compliance option was used.

    E. Emission units subject to 40 CFR Part 63, Subparts A, F, G, H, Y, CC, UUU, EEEE, ZZZZ, and DDDDD, as identified in the attached Applicable Requirements Summary

table are subject to 30 TAC Chapter 113, Subchapters C, § 113.100, § 113.110, § 113.120, § 113.130, § 113.300, § 113.340, § 113.780, § 113.880, § 113.1090, and § 113.1130, respectively which incorporates the 40 CFR Part 63 Subparts by reference.

F. For the purpose of generating emission reduction credits through 30 TAC Chapter 101, Subchapter H, Division 1 (Emission Credit Banking and Trading), the permit holder shall comply with the following requirements:

(i) Title 30 TAC § 101.302 (relating to General Provisions)

(ii) Title 30 TAC § 101.303 (relating to Emission Reduction Credit Generation Certification)

(iii) Title 30 TAC § 101.304 (relating to Mobile Emission Reduction Credit Generation and Certification)

(iv) Title 30 TAC § 101.309 (relating to Emission Credit Banking and Trading)

(v) The terms and conditions by which the emission limits are established to generate the reduction credit are applicable requirements of this permit

G. The permit holder shall comply with the following 30 TAC Chapter 101, Subchapter H, Division 3 (Mass Emission Cap and Trade Program) Requirements:

(i) Title 30 TAC § 101.352 (relating to General Provisions)

(ii) Title 30 TAC § 101.353 (relating to Allocation of Allowances)

(iii) Title 30 TAC § 101.354 (relating to Allowance Deductions)

(iv) Title 30 TAC § 101.356 (relating to Allowance Banking and Trading)

(v) Title 30 TAC § 101.359 (relating to Reporting)

(vi) Title 30 TAC § 101.360 (relating to Level of Activity Certification)

(vii) The terms and conditions by which the emission limits are established to meet or exceed the cap are applicable requirements of this permit

H. For the purpose of generating discrete emission reduction credits through 30 TAC Chapter 101, Subchapter H, Division 4 (Discrete Emission Credit Banking and Trading), the permit holder shall comply with the following requirements:

(i) Title 30 TAC § 101.372 (relating to General Provisions)

(ii) Title 30 TAC § 101.373 (relating to Discrete Emission Reduction Credit Generation and Certification)

(iii) Title 30 TAC § 101.374 (relating to Mobile Discrete Emission Reduction Credit Generation and Certification)

(iv) Title 30 TAC § 101.378 (relating to Discrete Emission Credit Banking and Trading)

(v) The terms and conditions by which the emission limits are established to generate the discrete reduction credit are applicable requirements of this permit

I. The permit holder shall comply with the following 30 TAC Chapter 101, Subchapter H, Division 6 (Highly Reactive Volatile Organic Compound Emissions Cap and Trade Program) requirements:

(i) Title 30 TAC § 101.392 (relating to Exemptions)

(ii) Title 30 TAC § 101.401 (relating to Level of Activity Certification)

2. The permit holder shall comply with the following sections of 30 TAC Chapter 101 (General Air Quality Rules):

A. Title 30 TAC § 101.1 (relating to Definitions), insofar as the terms defined in this section are used to define the terms used in other applicable requirements

B. Title 30 TAC § 101.3 (relating to Circumvention)

C. Title 30 TAC § 101.8 (relating to Sampling), if such action has been requested by the TCEQ

D. Title 30 TAC § 101.9 (relating to Sampling Ports), if such action has been requested by the TCEQ

E. Title 30 TAC § 101.10 (relating to Emissions Inventory Requirements)

F. Title 30 TAC § 101.201 (relating to Emission Event Reporting and Recordkeeping Requirements)

G. Title 30 TAC § 101.211 (relating to Scheduled Maintenance, Start-up, and Shutdown Reporting and Recordkeeping Requirements)

H. Title 30 TAC § 101.221 (relating to Operational Requirements)

I. Title 30 TAC § 101.222 (relating to Demonstrations)

J. Title 30 TAC § 101.223 (relating to Actions to Reduce Excessive Emissions)

3. Permit holder shall comply with the following requirements of 30 TAC Chapter 111:

A. Visible emissions from stationary vents with a flow rate of less than 100,000 actual cubic feet per minute that are not listed in the Applicable Requirements Summary attachment for 30 TAC Chapter 111, Subchapter A, Division 1, shall not exceed 20% opacity averaged over a six minute period. The permit holder shall comply with the following requirements for stationary vents at the site subject to this standard:

(i) Title 30 TAC § 111.111(a)(1)(B) (relating to Requirements for Specified Sources)

(ii) Title 30 TAC § 111.111(a)(1)(E)

(iii) Title 30 TAC § 111.111(a)(1)(F)(i), (ii), (iii), or (iv)

(iv) For emission units with vent emissions subject to 30 TAC § 111.111(a)(1)(B), complying with 30 TAC § 111.111(a)(1)(F)(ii), (iii), or (iv), and capable of

producing visible emissions from, but not limited to, particulate matter, acid gases and NO_x, the permit holder shall also comply with the following periodic monitoring requirements for the purpose of annual compliance certification under 30 TAC § 122.146. These periodic monitoring requirements do not apply to vents that are not capable of producing visible emissions such as vents that emit only colorless VOCs; vents from non-fuming liquids; vents that provide passive ventilation, such as plumbing vents; or vent emissions from any other source that does not obstruct the transmission of light. Vents, as specified in the "Applicable Requirements Summary" attachment, that are subject to the emission limitation of 30 TAC § 111.111(a)(1)(B) are not subject to the following periodic monitoring requirements:

(1) An observation of stationary vents from emission units in operation shall be conducted at least once during each calendar quarter unless the emission unit is not operating for the entire quarter.

(2) For stationary vents from a combustion source, if an alternative to the normally fired fuel is fired for a period greater than or equal to 24 consecutive hours, the permit holder shall conduct an observation of the stationary vent for each such period to determine if visible emissions are present. If such period is greater than 3 months, observations shall be conducted once during each quarter. Supplementing the normally fired fuel with natural gas or fuel gas to increase the net heating value to the minimum required value does not constitute creation of an alternative fuel.

(3) Records of all observations shall be maintained.

(4) Visible emissions observations of emission units operated during daylight hours shall be conducted no earlier than one hour after sunrise and no later than one hour before sunset. Visible emissions observations of emission units operated only at night must be made with additional lighting and the temporary installation of contrasting backgrounds. Visible emissions observations shall be made during times when the activities described in 30 TAC § 111.111(a)(1)(E) are not taking place. Visible emissions shall be determined with each stationary vent in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 mile, away from each stationary vent during the observation. For outdoor locations, the observer shall select a position where the sun is not directly in the observer's eyes. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. A certified opacity reader is not required for visible emissions observations.

(5) Compliance Certification:

(a) If visible emissions are not present during the observation, the RO may certify that the source is in compliance with the applicable opacity requirement in 30 TAC § 111.111(a)(1) and (a)(1)(B).

(b) However, if visible emissions are present during the observation, the permit holder shall either list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(1)(F) as soon as practicable, but no later than 24 hours after observing visible emissions to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.

(c) Some vents may be subject to multiple visible emission or monitoring requirements. All credible data must be considered when certifying compliance with this requirement even if the observation or monitoring was performed to demonstrate compliance with a different requirement.

B. For visible emissions from a building, enclosed facility, or other structure; the permit holder shall comply with the following requirements:

(i) Title 30 TAC § 111.111(a)(7)(A) (relating to Requirements for Specified Sources)

(ii) Title 30 TAC § 111.111(a)(7)(B)(i) or (ii)

(iii) For a building containing an air emission source, enclosed facility, or other structure containing or associated with an air emission source subject to 30 TAC § 111.111(a)(7)(A), complying with 30 TAC § 111.111(a)(7)(B)(i) or (ii), and capable of producing visible emissions from, but not limited to, particulate matter, acid gases and NO_x, the permit holder shall also comply with the following periodic monitoring requirements for the purpose of annual compliance certification under 30 TAC § 122.146:

(1) An observation of visible emissions from a building containing an air emission source, enclosed facility, or other structure containing or associated with an air emission source which is required to comply with 30 TAC § 111.111(a)(7)(A) shall be conducted at least once during each calendar quarter unless the air emission source or enclosed facility is not operating for the entire quarter.

(2) Records of all observations shall be maintained.

(3) Visible emissions observations of air emission sources or enclosed facilities operated during daylight hours shall be conducted no earlier than one hour after sunrise and no later than one hour before sunset. Visible emissions observations of air emission sources or enclosed facilities operated only at night must be made with additional lighting and the temporary installation of contrasting backgrounds. Visible emissions shall be determined with each emissions outlet in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 mile, away from each emissions outlet during the observation. For outdoor locations, the observer shall select a position where the sun is

not directly in the observer's eyes. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. A certified opacity reader is not required for visible emissions observations.

(4) Compliance Certification:

(a) If visible emissions are not present during the observation, the RO may certify that the source is in compliance with the applicable opacity requirement in 30 TAC § 111.111(a)(7) and (a)(7)(A)

(b) However, if visible emissions are present during the observation, the permit holder shall either list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(7)(B) as soon as practicable, but no later than 24 hours after observing visible emissions to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.

C. For visible emissions from all other sources not specified in 30 TAC § 111.111(a)(1), (4), or (7); the permit holder shall comply with the following requirements:

(i) Title 30 TAC § 111.111(a)(8)(A) (relating to Requirements for Specified Sources)

(ii) Title 30 TAC § 111.111(a)(8)(B)(i) or (ii)

(iii) For a source subject to 30 TAC § 111.111(a)(8)(A), complying with 30 TAC § 111.111(a)(8)(B)(i) or (ii), and capable of producing visible emissions from, but not limited to, particulate matter, acid gases and NO_x, the permit holder shall also comply with the following periodic monitoring requirements for the purpose of annual compliance certification under 30 TAC § 122.146:

(1) An observation of visible emissions from a source which is required to comply with 30 TAC § 111.111(a)(8)(A) shall be conducted at least once during each calendar quarter unless the source is not operating for the entire quarter.

(2) Records of all observations shall be maintained.

(3) Visible emissions observations of sources operated during daylight hours shall be conducted no earlier than one hour after sunrise and no later than one hour before sunset. Visible emissions observations of sources

operated only at night must be made with additional lighting and the temporary installation of contrasting backgrounds. Visible emissions shall be determined with each source in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 mile, away from each source during the observation. For outdoor locations, the observer shall select a position where the sun is not directly in the observer's eyes. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. A certified opacity reader is not required for visible emissions observations.

(4) Compliance Certification:

(a) If visible emissions are not present during the observation, the RO may certify that the source is in compliance with the applicable opacity requirement in 30 TAC § 111.111(a)(8) and (a)(8)(A)

(b) However, if visible emissions are present during the observation, the permit holder shall either list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(8)(B) as soon as practicable, but no later than 24 hours after observing visible emissions to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.

D. Certification of opacity readers determining opacities under Method 9 (as outlined in 40 CFR Part 60, Appendix A) to comply with opacity monitoring requirements shall be accomplished by completing the Visible Emissions Evaluators Course, or approved agency equivalent, no more than 180 days before the opacity reading.

E. Emission limits on nonagricultural processes, except for the steam generators specified in 30 TAC § 111.153, shall comply with the following requirements:

(i) Emissions of PM from any source may not exceed the allowable rates as required in 30 TAC § 111.151(a) (relating to Allowable Emissions Limits)

(ii) Sources with an effective stack height (h_e) less than the standard effective stack height (H_e), must reduce the allowable emission level by multiplying it by $[h_e/H_e]^2$ as required in 30 TAC § 111.151(b)

(iii) Effective stack height shall be calculated by the equation specified in 30 TAC § 111.151(c)

F. Outdoor burning, as stated in 30 TAC § 111.201, shall not be authorized unless the following requirements are satisfied:

(i) Title 30 TAC § 111.205 (relating to Exception for Fire Training)

(ii) Title 30 TAC § 111.207 (relating to Exception for Recreation, Ceremony, Cooking, and Warmth)

(iii) Title 30 TAC § 111.219 (relating to General Requirements for Allowable Outdoor Burning)

(iv) Title 30 TAC § 111.221 (relating to Responsibility for Consequences of Outdoor Burning)

4. For storage vessels maintaining working pressure as specified in 30 TAC Chapter 115, Subchapter B, Division 1: Storage of Volatile Organic Compounds, the permit holder shall comply with the requirements of 30 TAC § 115.112(e)(1).

5. For industrial wastewater specified in 30 TAC Chapter 115, Subchapter B, the permit holder shall comply with the following requirements for wastewater drains, junction boxes, lift stations and weirs:

A. Title 30 TAC § 115.142(1)(E) and (F) (relating to Control Requirements)

B. Title 30 TAC § 115.146 (relating to Recordkeeping Requirements)

C. Title 30 TAC § 115.147(7), (7)(A) and (B) (relating to Exemptions)

6. Permit holder shall comply with the following 30 TAC Chapter 115, Subchapter C requirements:

A. When filling stationary gasoline storage vessels (Stage I) for motor vehicle fuel dispensing facilities specified in 30 TAC Chapter 115, Subchapter C, the permit holder shall comply with the following requirements:

(i) Title 30 TAC § 115.221 (relating to Emission Specifications)

(ii) Title 30 TAC § 115.222 (relating to Control Requirements)

(iii) Title 30 TAC § 115.223 (relating to Alternate Control Requirements)

(iv) Title 30 TAC § 115.224 (relating to Inspection Requirements)

(v) Title 30 TAC § 115.225 (relating to Testing Requirements)

(vi) Title 30 TAC § 115.226 (relating to Recordkeeping Requirements)

B. For filling of motor vehicle fuel tanks (Stage II) at motor vehicle fuel dispensing facilities constructed after May 16, 2012 as specified in 30 TAC Chapter 115, Subchapter C, the permit holder shall comply with the following requirements:

(i) Title 30 TAC § 115.241 (relating to Decommissioning of Stage II Vapor Recovery Equipment)

(ii) Title 30 TAC § 115.242 (relating to Control Requirements)

(iii) Title 30 TAC § 115.243 (relating to Alternate Control Requirements)

(iv) Title 30 TAC § 115.244 (relating to Inspection Requirements)

(v) Title 30 TAC § 115.245 (relating to Testing Requirements)

(vi) Title 30 TAC § 115.246 (relating to Recordkeeping Requirements)

7. Permit holder shall comply with the following 30 TAC Chapter 115, Subchapter D requirements:

A. Title 30 TAC § 115.312(a)(1) (relating to Control Requirements), for emissions during Process Unit Shutdown or Turnaround

B. Title 30 TAC § 115.316(a)(2) (relating to Recordkeeping Requirements), for Process Unit Shutdown or Turnaround

8. The permit holder shall comply with the following requirements of 30 TAC Chapter 115, Subchapter F, Division 3, Degassing of Storage Tanks, Transport Vessels and Marine Vessels:

A. For degassing of stationary VOC storage tanks, the permit holder shall comply with the following requirements:

(i) Title 30 TAC § 115.541(a) - (c) (relating to Emission Specifications)

(ii) Title 30 TAC § 115.541(f) (relating to Emission Specifications), for floating roof storage tanks

(iii) Title 30 TAC § 115.542(a) and (a)(1), (a)(2), (a)(3) or (a)(4) (relating to Control Requirements). Where the requirements of 30 TAC Chapter 115, Subchapter F contain multiple compliance options, the permit holder shall keep records of when each compliance option was used.

(iv) Title 30 TAC § 115.542(b) - (d), (relating to Control Requirements)

(v) Title 30 TAC § 115.543 (relating to Alternate Control Requirements)

(vi) Title 30 TAC § 115.544(a)(1) and (a)(2) (relating to Inspection, Monitoring, and Testing Requirements), for inspections

(vii) Title 30 TAC § 115.544(b) (relating to Inspection, Monitoring, and Testing Requirements), for monitoring

(viii) Title 30 TAC § 115.544(b)(1) and (b)(2) (relating to Inspection, Monitoring, and Testing Requirements), for monitoring of control devices

(ix) Title 30 TAC § 115.544(b)(2)(A) - (J) (relating to Inspection, Monitoring, and Testing Requirements), for monitoring (as appropriate to the control device)

(x) Title 30 TAC § 115.544(b)(3), (b)(4) and (b)(6) (relating to Inspection, Monitoring, and Testing Requirements), for VOC concentration or lower explosive limit threshold monitoring

(xi) Title 30 TAC § 115.544(c), and (c)(1) - (c)(3) (relating to Inspection, Monitoring, and Testing Requirements), for testing of control devices used to comply with 30 TAC § 115.542(a)(1)

(xii) Title 30 TAC § 115.545(1) - (7), (9) - (11) and (13) (relating to Approved Test Methods)

(xiii) Title 30 TAC § 115.546(a), (a)(1) and (a)(3) (relating to Recordkeeping and Notification Requirements), for recordkeeping

(xiv) Title 30 TAC § 115.546(a)(2) and (a)(2)(A) - (J) (relating to Recordkeeping and Notification Requirements), for recordkeeping (as appropriate to the control device)

(xv) Title 30 TAC § 115.546(a)(4) (relating to Recordkeeping and Notification Requirements), for recordkeeping of testing of control devices used to comply with 30 TAC § 115.542(a)(1)

(xvi) Title 30 TAC § 115.546(b) (relating to Recordkeeping and Notification Requirements), for notification

(xvii) Title 30 TAC § 115.547(4) (relating to Exemptions)

9. The permit holder shall comply with the following requirements for units subject to any subpart of 40 CFR Part 60, unless otherwise stated in the applicable subpart:

A. Title 40 CFR § 60.7 (relating to Notification and Recordkeeping)

B. Title 40 CFR § 60.8 (relating to Performance Tests)

C. Title 40 CFR § 60.11 (relating to Compliance with Standards and Maintenance Requirements)

D. Title 40 CFR § 60.12 (relating to Circumvention)

E. Title 40 CFR § 60.13 (relating to Monitoring Requirements)

F. Title 40 CFR § 60.14 (relating to Modification)

G. Title 40 CFR § 60.15 (relating to Reconstruction)

H. Title 40 CFR § 60.19 (relating to General Notification and Reporting Requirements)

10. For petroleum refinery facilities subject to 40 CFR Part 60, Subpart QQQ, the permit holder shall comply with the following requirements:

A. Title 40 CFR § 60.692-1(a) - (c) (relating to Standards: General)

B. Title 40 CFR § 60.692-2(a) - (c), (e) (relating to Standards: Individual Drain Systems)

C. Title 40 CFR § 60.692-6(a) - (b) (relating to Standards: Delay of Repair)

D. Title 40 CFR § 60.692-7(a) - (b) (relating to Standards: Delay of Compliance)

E. Title 40 CFR § 60.693-1(a) - (d), (e)(1) - (3) (relating to Alternative Standards for Individual Drain Systems)

F. Title 40 CFR § 60.697(a), (b)(1) - (3) (relating to Recordkeeping Requirements), as applicable to Individual Drain Systems

G. Title 40 CFR § 60.697(f)(1) - (2), (g) (relating to Recordkeeping Requirements), as applicable to Individual Drain Systems

H. Title 40 CFR § 60.697(h) (relating to Recordkeeping Requirements), as applicable to excluded Stormwater Sewer Systems

I. Title 40 CFR § 60.697(i) (relating to Recordkeeping Requirements), as applicable to excluded Ancillary Equipment

J. Title 40 CFR § 60.697(j) (relating to Recordkeeping Requirements), as applicable to excluded Non-contact Cooling Water Systems

K. Title 40 CFR § 60.698(a), and (b)(1) (relating to Reporting Requirements), as applicable to Individual Drain Systems

L. Title 40 CFR § 60.698(c) (relating to Reporting Requirements), for water seal breaches in Drain Systems

M. Title 40 CFR § 60.698(e) (relating to Reporting Requirements), as applicable to Individual Drain Systems

11. The permit holder shall comply with the following requirements for units subject to any subpart of 40 CFR Part 61, unless otherwise stated in the applicable subpart:

A. Title 40 CFR § 61.05 (relating to Prohibited Activities)

B. Title 40 CFR § 61.07 (relating to Application for Approval of Construction or Modification)

C. Title 40 CFR § 61.09 (relating to Notification of Start-up)

D. Title 40 CFR § 61.10 (relating to Source Reporting and Request Waiver)

E. Title 40 CFR § 61.12 (relating to Compliance with Standards and Maintenance Requirements)

F. Title 40 CFR § 61.13 (relating to Emissions Tests and Waiver of Emission Tests)

G. Title 40 CFR § 61.14 (relating to Monitoring Requirements)

H. Title 40 CFR § 61.15 (relating to Modification)

I. Title 40 CFR § 61.19 (relating to Circumvention)

12. For the National Emissions Standards for Asbestos specified in 40 CFR Part 61, Subpart M, the permit holder shall comply with the following requirements:

A. For insulating materials other than spray-applied: Title 40 CFR § 61.148 (relating to Standards for Insulating Materials), for installation and reinstallation of asbestos-containing insulation).

13. For the benzene transfer operations to and from marine vessels specified in 40 CFR Part 61, Subpart BB, the permit holder shall comply with the following requirements:

A. Title 40 CFR § 61.302(e) (relating to Standards)

B. Title 40 CFR § 61.303(f) (relating to Monitoring Requirements)

C. Title 40 CFR § 61.304(f) (relating to Test Methods and Procedures)

D. Title 40 CFR § 61.305(g) - (h) (relating to Reporting and Recordkeeping)

14. For facilities where total annual benzene quantity from waste is greater than or equal to 10 megagrams per year and subject to emission standards in 40 CFR Part 61, Subpart FF, the permit holder shall comply with the following requirements:

A. Title 40 CFR § 61.342(c)(1)(i) - (iii) (relating to Standards: General)

B. Title 40 CFR § 61.342(e)(1) (relating to Standards: General)

C. Title 40 CFR § 61.342(e)(2)(i) - (ii) (relating to Standards: General)

D. Title 40 CFR § 61.342(g) (relating to Standards: General)

E. Title 40 CFR § 61.350(a) and (b) (relating to Standards: Delay of Repair)

F. Title 40 CFR § 61.355(a)(1)(iii), (a)(2), (a)(6), (b), and (c)(1) - (3) (relating to Test Methods, Procedures, and Compliance Provisions)

G. Title 40 CFR § 61.355(k)(1) - (6), and (7)(i) - (iv) (relating to Test Methods, Procedures, and Compliance Provisions), for calculation procedures

H. Title 40 CFR § 61.356(a) (relating to Recordkeeping Requirements)

I. Title 40 CFR § 61.356(b), and (b)(1) (relating to Recordkeeping Requirements)

J. Title 40 CFR § 61.356(b)(4) (relating to Recordkeeping Requirements)

K. Title 40 CFR § 61.356(b)(5) (relating to Recordkeeping Requirements)

L. Title 40 CFR § 61.357(a), (d)(1), (d)(2) (d)(6) and (d)(8) (relating to Reporting Requirements)

M. Title 40 CFR § 61.357(d)(5) (relating to Reporting Requirements)

N. Waste generated by remediation activities at these facilities are subject to the requirements identified under 40 CFR § 61.342 for treatment and management of waste

15. For facilities with containers subject to emission standards in 40 CFR Part 61, Subpart FF, the permit holder shall comply with the following requirements:

A. Title 40 CFR § 61.345(a)(1) - (3), (b), and (c) (relating to Standards: Containers)

B. Title 40 CFR § 61.355(h) (relating to Test Methods, Procedures and Compliance Provisions)

C. Title 40 CFR § 61.356(g) (relating to Recordkeeping Requirements)

D. Title 40 CFR § 61.356(h) (relating to Recordkeeping Requirements)

16. For facilities with individual drain systems subject to emission standards in 40 CFR Part 61, Subpart FF, the permit holder shall comply with the following requirements:

    A. Title 40 CFR § 61.346(a)(1)(i)(A), (B), (ii), (2), and (3) (relating to Standards: Individual Drain Systems)

    B. Title 40 CFR § 61.346(b)(1), (2), (2)(i), (3), (4)(i) - (iv), and (5) (relating to Standards: Individual Drain Systems)

    C. Title 40 CFR § 61.346(b)(2)(ii)(A) (relating to Standards: Individual Drain Systems), for junction boxes

    D. Title 40 CFR § 61.346(b)(2)(ii)(B) (relating to Standards: Individual Drain Systems), for junction boxes

    E. Title 40 CFR § 61.355(h) (relating to Test Methods, Procedures and Compliance Provisions)

    F. Title 40 CFR § 61.356(g) (relating to Recordkeeping Requirements)

    G. Title 40 CFR § 61.356(h) (relating to Recordkeeping Requirements)

17. The permit holder shall comply with the requirements of 30 TAC Chapter 113, Subchapter C, § 113.100 for units subject to any subpart of 40 CFR Part 63, unless otherwise stated in the applicable subpart.

18. For the chemical manufacturing process specified in 40 CFR Part 63, Subpart F, the permit holder shall comply with 40 CFR § 63.103(a) (relating to General Compliance, Reporting, and Recordkeeping Provisions) (Title 30 TAC Chapter 113, Subchapter C, § 113.110 incorporated by reference).

19. For the chemical manufacturing facilities with a 40 CFR Part 63, Subpart G Group 1 or Group 2 wastewater streams that are also subject to 40 CFR Part 61, Subpart FF, the permit holder shall comply with the following requirements (Title 30 TAC Chapter 113, Subchapter C, § 113.120 incorporated by reference):

    A. Title 40 CFR § 63.110(e)(1) (relating to Applicability), for 40 CFR Part 63, Subpart G applicability to Group 1 or 2 Wastewater Streams

20. For the chemical manufacturing facilities with a 40 CFR Part 63, Subpart G Group 2 wastewater stream, the permit holder shall comply with (Title 30 TAC Chapter 113, Subchapter C, § 113.120 incorporated by reference):

    A. Title 40 CFR § 63.132(a), (a)(1), and (a)(1)(i) (relating to Process Wastewater Provisions - General)

    B. Title 40 CFR § 63.146(b)(1) (relating to Process Wastewater Provisions - Reporting)

    C. Title 40 CFR § 63.147(b)(8) (relating to Process Wastewater Provisions - Recordkeeping)

21. For the chemical manufacturing facilities subject to leak detection requirements in 40 CFR Part 63, Subpart G, the permit holder shall comply with the following requirements (Title 30 TAC Chapter 113, Subchapter C, § 113.120 incorporated by reference):

    A. General Leak Detection Requirements:

(i) Title 40 CFR § 63.148(d)(1) - (3), and (e) (relating to Leak Inspection Provisions)

(ii) Title 40 CFR § 63.148(c), (g), (g)(2), (h), and (h)(2) (relating to Leak Inspection Provisions), for monitoring and testing requirements

(iii) Title 40 CFR §§ 63.148(g)(2), (h)(2), (i)(1) - (2), (i)(4)(i) - (viii), (i)(5), and 63.152(a)(1) - (5), for recordkeeping requirements

(iv) Title 40 CFR §§ 63.148(j), 63.151(a)(6)(i) - (iii), (b)(1) - (2), (j)(1) - (3), 63.152(a)(1) - (5), (b), (b)(1)(i) - (ii), and (b)(4), for reporting requirements

B. For closed vent system or vapor collection systems constructed of hard piping:

(i) Title 40 CFR § 63.148(b)(1)(ii) (relating to Leak Inspection Provisions), for monitoring and testing requirements

(ii) Title 40 CFR § 63.148(i)(6) (relating to Leak Inspection Provisions), for recordkeeping requirements

22. For the operations pertaining to the loading and unloading of marine tank vessels specified in 40 CFR Part 63, Subpart Y, the permit holder shall comply with the following requirements (Title 30 TAC Chapter 113, Subchapter C, § 113.300 incorporated by reference):

A. Title 40 CFR § 63.560(c) (relating to Designation of Affected Source), for applicability of the General Provisions of Subpart A

B. Title 40 CFR § 63.563(a)(4) (relating to Compliance and Performance Testing), for vapor tightness requirements of the marine vessels

C. Title 40 CFR § 63.564(a)(1) and (d) (relating to Monitoring Requirements)

D. Title 40 CFR § 63.565(a) (relating to Test Methods and Procedures), for performance testing requirements

E. Title 40 CFR § 63.565(c) (relating to Test Methods and Procedures), for vapor tightness requirements of the marine vessels

F. Title 40 CFR § 63.566 (relating to Construction and Reconstruction)

G. Title 40 CFR § 63.567(a) - (b) and (h) - (i) (relating to Reporting and Recordkeeping Requirements)

23. For sources subject to emission standards in 40 CFR Part 63, Subpart CC, the permit holder shall comply with the following requirements (Title 30 TAC Chapter 113, Subchapter C, § 113.340 incorporated by reference):

A. Title 40 CFR § 63.640(l)(3) - (4) (relating to Applicability and Designation of Affected Source), for units and equipment added to an existing source

B. Title 40 CFR § 63.640(m)(1) - (2) (relating to Applicability and Designation of Affected Source), for units and emission points changing from Group 2 to Group 1 status

C. Title 40 CFR § 63.642(c) (relating to General Standards), for applicability of the General Provisions of Subpart A

D. Title 40 CFR § 63.642(e) (relating to General Standards), for recordkeeping

E. Title 40 CFR § 63.642(f) (relating to General Standards), for reporting

F. Group 1 process wastewater streams not managed in a wastewater management unit subject to 40 CFR Part 63, Subpart G shall comply with 40 CFR Part 61, Subpart FF as specified in 40 CFR §§ 63.647(a) - (c) and 63.655(a)

24. The permit holder shall comply with the requirement to prepare and implement an Operations and Maintenance plan in accordance with 40 CFR Part 63, Subpart UUU, § 63.1574(f) (Title 30 TAC Chapter 113, Subchapter C, § 113.780 incorporated by reference).

25. For containers managing remediation materials subject to 40 CFR Part 63, Subpart GGGGG, the permit holder shall comply with the following requirements (Title 30 TAC Chapter 113, Subchapter C, § 113.1160 incorporated by reference):

A. Title 40 CFR § 63.922(b)(1) - (3), (c), (d), (d)(1) - (5), (e), and (f), (f)(1) - (4) (relating to Standards - Container Level 1 Controls)

B. Title 40 CFR § 63.923(b)(1) - (3), (c), (d), (d)(1) - (5), (e), and (f), (f)(1) - (4) (relating to Standards - Container Level 2 Controls)

C. Title 40 CFR § 63.925(a)(1) - (8), and (b)(1) - (3) (relating to Test Methods and Procedures)

D. Title 40 CFR § 63.926(a)(1) - (3) (relating to Inspection and Monitoring Requirements)

E. Title 40 CFR § 63.7901(b) and (b)(1), for initial demonstration of compliance

F. Title 40 CFR § 63.7901(b)(2), for initial demonstration of compliance

G. Title 40 CFR § 63.7901(c), (c)(1), and (c)(2), for initial demonstration of compliance

H. Title 40 CFR § 63.7901(d), and (d)(1) - (4), for initial demonstration of compliance

I. Title 40 CFR § 63.7903(b) and (b)(1), for continuous demonstration of compliance

J. Title 40 CFR § 63.7903(b)(2), (b)(2)(i), (b)(2)(ii), for continuous demonstration of compliance

K. Title 40 CFR § 63.7903(c)(4), (c)(4)(i), and (c)(4)(ii), for continuous demonstration of compliance

L. Title 40 CFR § 63.7903(d)(5), (d)(5)(i), and (d)(5)(ii), for continuous demonstration of compliance

M. Title 40 CFR § 63.7952(c), for recordkeeping

Additional Monitoring Requirements

26. Unless otherwise specified, the permit holder shall comply with the compliance assurance monitoring requirements as specified in the attached “CAM Summary” upon issuance of the permit. In addition, the permit holder shall comply with the following:

A. The permit holder shall comply with the terms and conditions contained in 30 TAC § 122.147 (General Terms and Conditions for Compliance Assurance Monitoring).

B. The permit holder shall report, consistent with the averaging time identified in the "CAM Summary," deviations as defined by the deviation limit in the "CAM Summary." Any monitoring data below a minimum limit or above a maximum limit, that is collected in accordance with the requirements specified in 40 CFR § 64.7(c), shall be reported as a deviation. Deviations shall be reported according to 30 TAC § 122.145 (Reporting Terms and Conditions).

C. The permit holder may elect to collect monitoring data on a more frequent basis and average the data, consistent with the averaging time or minimum frequency specified in the "CAM Summary," for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis. In no event shall data be collected and used in particular instances in order to avoid reporting deviations. All monitoring data shall be collected in accordance with the requirements specified in 40 CFR § 64.7(c).

D. The permit holder shall operate the monitoring, identified in the attached "CAM Summary," in accordance with the provisions of 40 CFR § 64.7.

E. Except for emission units using a CEMS, COMS or PEMS which meets the requirements of 40 CFR § 64.3(d)(2), the permit holder shall comply with either of the following requirements for any capture system associated with the VOC control device subject to CAM. If the results of the following inspections indicate that the capture system is not working properly, the permit holder shall promptly take necessary corrective actions:

(i) Once a year the permit holder shall inspect the capture system in compliance of CAM for leaks in accordance with 40 CFR Part 60, Appendix A, Test Method 21. Leaks shall be indicated by an instrument reading greater than or equal to 500 ppm above background or as defined by the underlying applicable requirement; or

(ii) Once a month, the permit holder shall conduct a visual, audible, and/or olfactory inspection of the capture system in compliance of CAM to detect leaking components.

F. Except for emission units using a CEMS, COMS or PEMS which meets the requirements of 40 CFR § 64.3(d)(2), the permit holder shall comply with either of the following requirements for any bypass of the control device subject to CAM. If the results of the following inspections or monitoring indicate bypass of the control device, the permit holder shall promptly take necessary corrective actions and report a deviation:

(i) Install a flow indicator that is capable of recording flow, at least once every fifteen minutes, immediately downstream of each valve that if opened would allow a vent stream to bypass the control device and be emitted, either directly or indirectly, to the atmosphere; or

(ii) Once a month, the permit holder shall inspect the valves checking the position of the valves and the condition of the car seals. Identify all times when the car seal has been broken and the valve position has been changed to allow a vent stream to bypass the control device and be emitted, either directly or indirectly, to the atmosphere.

G. The permit holder shall comply with the requirements of 40 CFR § 70.6(a)(3)(ii)(A) and 30 TAC § 122.144(1)(A)-(F) for documentation of all required inspections.

27. The permit holder shall comply with the periodic monitoring requirements as specified in the attached "Periodic Monitoring Summary" upon issuance of the permit. Except for, as applicable, monitoring malfunctions, associated repairs, and required quality assurance or control activities (including, as applicable, calibration checks and required zero and span adjustments), the permit holder shall conduct all monitoring in continuous operation (or shall collect data at all required intervals) at all times that the pollutant-specific emissions unit is operating. The permit holder may elect to collect monitoring data on a more frequent basis and average the data, consistent with the averaging time or minimum frequency specified in the "Periodic Monitoring Summary," for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis. In no event shall data be collected and used in particular instances to avoid reporting deviations. Deviations shall be reported according to 30 TAC § 122.145 (Reporting Terms and Conditions).

New Source Review Authorization Requirements

28. Permit holder shall comply with the requirements of New Source Review authorizations issued or claimed by the permit holder for the permitted area, including permits, permits by rule, standard permits, flexible permits, special permits, permits for existing facilities including Voluntary Emissions Reduction Permits and Electric Generating Facility Permits issued under 30 TAC Chapter 116, Subchapter I, or special exemptions referenced in the New Source Review Authorization References attachment. These requirements:

    A. Are incorporated by reference into this permit as applicable requirements

    B. Shall be located with this operating permit

    C. Are not eligible for a permit shield

29. The permit holder shall comply with the general requirements of 30 TAC Chapter 106, Subchapter A or the general requirements, if any, in effect at the time of the claim of any PBR.

30. The permit holder shall maintain records to demonstrate compliance with any emission limitation or standard that is specified in a permit by rule (PBR) or Standard Permit listed in the New Source Review Authorizations attachment. The records shall yield reliable data from the relevant time period that are representative of the emission unit's compliance with the PBR or Standard Permit. These records may include, but are not limited to, production capacity and throughput, hours of operation, safety data sheets (SDS), chemical composition of raw materials, speciation of air contaminant data, engineering calculations, maintenance records, fugitive data, performance tests, capture/control device efficiencies, direct pollutant monitoring (CEMS, COMS, or PEMS), or control device parametric monitoring. These records shall be made readily accessible and available as required by 30 TAC § 122.144. Any monitoring or recordkeeping data indicating noncompliance with the PBR or Standard Permit shall be considered and reported as a deviation according to 30 TAC § 122.145 (Reporting Terms and Conditions).

31. The permit holder shall comply with the following requirements for Air Quality Standard Permits:

    A. Registration requirements listed in 30 TAC § 116.611, unless otherwise provided for in an Air Quality Standard Permit

    B. General Conditions listed in 30 TAC § 116.615, unless otherwise provided for in an Air Quality Standard Permit

C. Applicable requirements of 30 TAC § 116.617 for Pollution Control Projects based on the information contained in the registration application.

D. Requirements of the non-rule Air Quality Standard Permit for Pollution Control Projects

32. The permit holder shall comply with the following requirements for flexible permits of 30 TAC Chapter 116:

A. Title 30 TAC § 116.715 (relating to General and Special Conditions)

B. Title 30 TAC § 116.716 (relating to Emission Caps and Individual Emission Limitations)

C. Title 30 TAC § 116.717 (relating to Implementation Schedule for Additional Controls)

D. Title 30 TAC § 116.718 (relating to Significant Emission Increase)

E. Title 30 TAC § 116.720 (relating to Limitation on Physical and Operational Changes)

F. Title 30 TAC § 116.721(a) (relating to requirements for Amendments and Alterations)

Compliance Requirements

33. The permit holder shall certify compliance in accordance with 30 TAC § 122.146. The permit holder shall comply with 30 TAC § 122.146 using at a minimum, but not limited to, the continuous or intermittent compliance method data from monitoring, recordkeeping, reporting, or testing required by the permit and any other credible evidence or information. The certification period may not exceed 12 months and the certification must be submitted within 30 days after the end of the period being certified.

34. The permit holder shall adhere to the provisions in the Compliance Schedule attachment of this permit and submit certified progress reports consistent with the schedule established under 30 TAC § 122.132(e)(4)(C) and including the information specified in 30 TAC § 122.142(e)(2). Those emission units listed in the Compliance Schedule attachment shall adhere with the requirements in the Compliance Schedule attachment until operating fully in compliance with the applicable requirements.

35. Permit holder shall comply with the following 30 TAC Chapter 117 requirements:

A. The permit holder shall comply with the compliance schedules and submit written notification to the TCEQ Executive Director as required in 30 TAC Chapter 117, Subchapter H, Division 1:

(i) For sources in the Houston-Galveston-Brazoria Nonattainment area, 30 TAC § 117.9020:

(1) Title 30 TAC § 117.9020(2)(A), (C), and (D)

B. The permit holder shall comply with the Initial Control Plan unit listing requirement in 30 TAC § 117.350(c) and (c)(1).

C. The permit holder shall comply with the requirements of 30 TAC § 117.354 for Final Control Plan Procedures for Attainment Demonstration Emission Specifications and 30 TAC § 117.356 for Revision of Final Control Plan.

36. Use of Emission Credits to comply with applicable requirements:

A. Unless otherwise prohibited, the permit holder may use emission credits to comply with the following applicable requirements listed elsewhere in this permit:

(i) Title 30 TAC Chapter 115

(ii) Title 30 TAC Chapter 117

(iii) Offsets for Title 30 TAC Chapter 116

B. The permit holder shall comply with the following requirements in order to use the emission credits to comply with the applicable requirements:

(i) The permit holder must notify the TCEQ according to 30 TAC § 101.306(c)-(d)

(ii) The emission credits to be used must meet all the geographic, timeliness, applicable pollutant type, and availability requirements listed in 30 TAC Chapter 101, Subchapter H, Division 1

(iii) The executive director has approved the use of the credit according to 30 TAC § 101.306(c)-(d)

(iv) The permit holder keeps records of the use of credits towards compliance with the applicable requirements in accordance with 30 TAC § 101.302(g) and 30 TAC Chapter 122

(v) Title 30 TAC § 101.305 (relating to Emission Reductions Achieved Outside the United States)

37. Use of Discrete Emission Credits to comply with the applicable requirements:

A. Unless otherwise prohibited, the permit holder may use discrete emission credits to comply with the following applicable requirements listed elsewhere in this permit:

(i) Title 30 TAC Chapter 115

(ii) Title 30 TAC Chapter 117

(iii) If applicable, offsets for Title 30 TAC Chapter 116

(iv) Temporarily exceed state NSR permit allowables

B. The permit holder shall comply with the following requirements in order to use the credit to comply with the applicable requirements:

(i) The permit holder must notify the TCEQ according to 30 TAC § 101.376(d)

(ii) The discrete emission credits to be used must meet all the geographic, timeliness, applicable pollutant type, and availability requirements listed in 30 TAC Chapter 101, Subchapter H, Division 4

(iii) The executive director has approved the use of the discrete emission credits according to 30 TAC § 101.376(d)(1)(A)

(iv) The permit holder keeps records of the use of credits towards compliance with the applicable requirements in accordance with 30 TAC § 101.372(h) and 30 TAC Chapter 122

(v) Title 30 TAC § 101.375 (relating to Emission Reductions Achieved Outside the United States)

Risk Management Plan

38. For processes subject to 40 CFR Part 68 and specified in 40 CFR § 68.10, the permit holder shall comply with the requirements of the Accidental Release Prevention Provisions in 40 CFR Part 68. The permit holder shall submit to the appropriate agency either a compliance schedule for meeting the requirements of 40 CFR Part 68 by the date provided in 40 CFR § 68.10(a), or as part of the compliance certification submitted under this permit, a certification statement that the source is in compliance with all requirements of 40 CFR Part 68, including the registration and submission of a risk management plan.

Protection of Stratospheric Ozone

39. Permit holders at a site subject to Title VI of the FCAA Amendments shall meet the following requirements for protection of stratospheric ozone:

A. Any on site servicing, maintenance, and repair on refrigeration and nonmotor vehicle air-conditioning appliances using ozone-depleting refrigerants or non-exempt substitutes shall be conducted in accordance with 40 CFR Part 82, Subpart F. Permit holders shall ensure that repairs on or refrigerant removal from refrigeration and nonmotor vehicle air-conditioning appliances using ozone-depleting refrigerants are performed only by properly certified technicians using certified equipment. Records shall be maintained as required by 40 CFR Part 82, Subpart F.

B. The permit holder shall comply with 40 CFR Part 82, Subpart F related to the disposal requirements for appliances using Class I or Class II (ozone-depleting) substances or non-exempt substitutes as specified in 40 CFR §§ 82.150 - 82.166 and the applicable Part 82 Appendices.

C. The permit holder shall comply with 40 CFR Part 82, Subpart H related to Halon Emissions Reduction requirements as specified in 40 CFR § 82.250 - § 82.270 and the applicable Part 82 Appendices.

Temporary Fuel Shortages (30 TAC § 112.15)

40. The permit holder shall comply with the following 30 TAC Chapter 112 requirements:

A. Title 30 TAC § 112.15 (relating to Temporary Fuel Shortage Plan Filing Requirements)

B. Title 30 TAC § 112.16(a), (a)(1), and (a)(2)(B) - (C) (relating to Temporary Fuel Shortage Plan Operating Requirements)

C. Title 30 TAC § 112.17 (relating to Temporary Fuel Shortage Plan Notification Procedures)

D. Title 30 TAC § 112.18 (relating to Temporary Fuel Shortage Plan Reporting Requirements)

Alternative Requirements

41. The permit holder shall comply with the approved alternative means of control (AMOC); alternative monitoring, recordkeeping, or reporting requirements; or requirements determined to be equivalent to an otherwise applicable requirement contained in the Alternative Requirements attachment of this permit. Units complying with an approved alternative requirement have reference to the approval in the Applicable Requirements summary listing for the unit. The permit holder shall maintain the original documentation, from the EPA Administrator and TCEQ Executive Director, demonstrating the method or limitation utilized. Documentation shall be maintained and made available in accordance with 30 TAC § 122.144.

Permit Location

42. The permit holder shall maintain a copy of this permit and records related to requirements listed in this permit on site.

Permit Shield (30 TAC § 122.148)

43. A permit shield is granted for the emission units, groups, or processes specified in the attached "Permit Shield." Compliance with the conditions of the permit shall be deemed compliance with the specified potentially applicable requirements or specified potentially applicable state-only requirements listed in the attachment "Permit Shield." Permit shield provisions shall not be modified by the executive director until notification is provided to the permit holder. No later than 90 days after notification of a change in a determination made by the executive director, the permit holder shall apply for the appropriate permit revision to reflect the new determination. Provisional terms are not eligible for this permit shield. Any term or condition, under a permit shield, shall not be protected by the permit shield if it is replaced by a provisional term or condition or the basis of the term and condition changes.

Attachments

Applicable Requirements Summary

Additional Monitoring Requirements

Permit Shield

New Source Review Authorization References

Schedules

Alternative Requirement

Applicable Requirements Summary

Unit Summary **24**

Applicable Requirements Summary **121**

Note: A “none” entry may be noted for some emission sources in this permit’s “Applicable Requirements Summary” under the heading of “Monitoring and Testing Requirements” and/or “Recordkeeping Requirements” and/or “Reporting Requirements.” Such a notation indicates that there are no requirements for the indicated emission source as identified under the respective column heading(s) for the stated portion of the regulation when the emission source is operating under the conditions of the specified SOP Index Number. However, other relevant requirements pursuant to 30 TAC Chapter 122 including Recordkeeping Terms and Conditions (§ 122.144), Reporting Terms and Conditions (§ 122.145), and Compliance Certification Terms and Conditions (§ 122.146) continue to apply.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
ALK2-CTWR	INDUSTRIAL PROCESS COOLING TOWERS	N/A	R5760-0206	30 TAC Chapter 115, HRVOC Cooling Towers	No changing attributes.
ALK2-CTWR	INDUSTRIAL PROCESS COOLING TOWERS	N/A	63CC-002	40 CFR Part 63, Subpart CC	No changing attributes.
ALK3-CTWR	INDUSTRIAL PROCESS COOLING TOWERS	N/A	R5760-0206	30 TAC Chapter 115, HRVOC Cooling Towers	No changing attributes.
ALK3-CTWR	INDUSTRIAL PROCESS COOLING TOWERS	N/A	63CC-002	40 CFR Part 63, Subpart CC	No changing attributes.
ALK3DEBCT	INDUSTRIAL PROCESS COOLING TOWERS	N/A	63CC-002	40 CFR Part 63, Subpart CC	No changing attributes.
ALK3-F1001	PROCESS HEATERS/FURNACES	N/A	R7300-1289	30 TAC Chapter 117, Subchapter B	No changing attributes.
ALK3-F1001	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60Ja-165	40 CFR Part 60, Subpart Ja	No changing attributes.
ALK3-F1001	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
ALKY2-FUG	FUGITIVE EMISSION UNITS	N/A	60GGG-0001	40 CFR Part 60, Subpart GGG	No changing attributes.
ALKY3-FUG	FUGITIVE EMISSION UNITS	N/A	60GGG-0001	40 CFR Part 60, Subpart GGG	No changing attributes.
API3CD-SEP	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	R5131-0005	30 TAC Chapter 115, Water Separation	Emission Control Option = The compartment is equipped with a floating roof or internal floating cover that rests on the contents and has closure seals to close space between the roof edge and tank wall with gauging and sampling devices that are vapor tight except when in

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					use.
API3CD-SEP	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	R5131-0006	30 TAC Chapter 115, Water Separation	Emission Control Option = Vapor recovery system which satisfies the provisions of 30 TAC § 115.131., Control Device = Carbon adsorption system.
API3CD-SEP	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	61FF-1780	40 CFR Part 61, Subpart FF	No changing attributes.
ARU-619FA	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	R5131-0010	30 TAC Chapter 115, Water Separation	No changing attributes.
ARU-619FA	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	61FF-1733	40 CFR Part 61, Subpart FF	No changing attributes.
ARU-FUG1	FUGITIVE EMISSION UNITS	N/A	60GGGa-01	40 CFR Part 60, Subpart GGGa	No changing attributes.
ARU-SEP	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	R5131-0010	30 TAC Chapter 115, Water Separation	No changing attributes.
ARU-SEP	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	61FF-1781	40 CFR Part 61, Subpart FF	No changing attributes.
AU2-B601	PROCESS HEATERS/FURNACES	N/A	R7300-1493	30 TAC Chapter 117, Subchapter B	No changing attributes.
AU2-B601	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.
AU2-B601	PROCESS	N/A	63DDDDD-1	40 CFR Part 63, Subpart	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	HEATERS/FURNACES			DDDDD	
AU2-B621A	PROCESS HEATERS/FURNACES	N/A	R7300-1289	30 TAC Chapter 117, Subchapter B	No changing attributes.
AU2-B621A	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.
AU2-B621A	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
AU2-B621B	PROCESS HEATERS/FURNACES	N/A	R7300-1289	30 TAC Chapter 117, Subchapter B	No changing attributes.
AU2-B621B	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.
AU2-B621B	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
AU2-CTWR	INDUSTRIAL PROCESS COOLING TOWERS	N/A	63CC-002	40 CFR Part 63, Subpart CC	No changing attributes.
AU2-FUG	FUGITIVE EMISSION UNITS	N/A	R5352-ALL	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	No changing attributes.
AU2-FUG	FUGITIVE EMISSION UNITS	N/A	63H-ALL	40 CFR Part 63, Subpart H	No changing attributes.
AU2-SEP	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	R5131-0010	30 TAC Chapter 115, Water Separation	No changing attributes.
AU2-SEP	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	61FF-1781	40 CFR Part 61, Subpart FF	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
CAT1-SEP19	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	R5131-0010	30 TAC Chapter 115, Water Separation	No changing attributes.
CAT1-SEP19	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	61FF-1781	40 CFR Part 61, Subpart FF	No changing attributes.
CAT3-SEP21	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	R5131-0010	30 TAC Chapter 115, Water Separation	No changing attributes.
CAT3-SEP21	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	61FF-1781	40 CFR Part 61, Subpart FF	No changing attributes.
CAT3-SEP22	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	R5131-0010	30 TAC Chapter 115, Water Separation	No changing attributes.
CAT3-SEP22	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	61FF-1781	40 CFR Part 61, Subpart FF	No changing attributes.
CFHU-101B	PROCESS HEATERS/FURNACES	N/A	R7300-1086	30 TAC Chapter 117, Subchapter B	No changing attributes.
CFHU-101B	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.
CFHU-101B	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
CFHU-102B	PROCESS HEATERS/FURNACES	N/A	R7300-1086	30 TAC Chapter 117, Subchapter B	No changing attributes.
CFHU-102B	FCCU CAT REGEN/FUEL GAS	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	COMBUSTION/CLAUS SRU				
CFHU-102B	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
CFHU-CTWR	INDUSTRIAL PROCESS COOLING TOWERS	N/A	R5760-0022	30 TAC Chapter 115, HRVOC Cooling Towers	No changing attributes.
CFHU-CTWR	INDUSTRIAL PROCESS COOLING TOWERS	N/A	63CC-002	40 CFR Part 63, Subpart CC	No changing attributes.
CFHU-FUG1	FUGITIVE EMISSION UNITS	N/A	60GGGa-001	40 CFR Part 60, Subpart GGGa	No changing attributes.
CFHU-SEP	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	R5131-0010	30 TAC Chapter 115, Water Separation	No changing attributes.
CFHU-SEP	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	61FF-1781	40 CFR Part 61, Subpart FF	No changing attributes.
CKR-BDS	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121-0003	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
CKR-BDS	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	63CC-1003	40 CFR Part 63, Subpart CC	No changing attributes.
COKERLOAD	LOADING/UNLOADING OPERATIONS	N/A	R5211-0009	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.
COKR-B101	PROCESS HEATERS/FURNACES	N/A	R7300-1086	30 TAC Chapter 117, Subchapter B	No changing attributes.
COKR-B101	FCCU CAT REGEN/FUEL GAS	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	COMBUSTION/CLAUS SRU				
COKR-B101	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
COKR-B201	PROCESS HEATERS/FURNACES	N/A	R7300-1289	30 TAC Chapter 117, Subchapter B	No changing attributes.
COKR-B201	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.
COKR-B201	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
COKR-B203	PROCESS HEATERS/FURNACES	N/A	R7300-1097	30 TAC Chapter 117, Subchapter B	No changing attributes.
COKR-B203	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.
COKR-B203	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
COKR-B301	PROCESS HEATERS/FURNACES	N/A	R7300-1289	30 TAC Chapter 117, Subchapter B	No changing attributes.
COKR-B301	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.
COKR-B301	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
COKR-B302	PROCESS	N/A	R7300-1086	30 TAC Chapter 117,	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	HEATERS/FURNACES			Subchapter B	
COKR-B302	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.
COKR-B302	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
COKR-CTWR	INDUSTRIAL PROCESS COOLING TOWERS	N/A	R5760-0022	30 TAC Chapter 115, HRVOC Cooling Towers	No changing attributes.
COKR-CTWR	INDUSTRIAL PROCESS COOLING TOWERS	N/A	63CC-002	40 CFR Part 63, Subpart CC	No changing attributes.
COKR-FUG1	FUGITIVE EMISSION UNITS	N/A	60GGGa-01	40 CFR Part 60, Subpart GGGa	No changing attributes.
COKR-SEP	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	R5131-0010	30 TAC Chapter 115, Water Separation	No changing attributes.
COKR-SEP	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	61FF-1781	40 CFR Part 61, Subpart FF	No changing attributes.
DDU-101B	PROCESS HEATERS/FURNACES	N/A	R7300-1086	30 TAC Chapter 117, Subchapter B	No changing attributes.
DDU-101B	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.
DDU-101B	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
DDU-102B	PROCESS HEATERS/FURNACES	N/A	R7300-1018	30 TAC Chapter 117, Subchapter B	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
DDU-102B	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.
DDU-102B	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
DDU-201B	PROCESS HEATERS/FURNACES	N/A	R7300-1086	30 TAC Chapter 117, Subchapter B	No changing attributes.
DDU-201B	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.
DDU-201B	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
DDU-202B	PROCESS HEATERS/FURNACES	N/A	R7300-1018	30 TAC Chapter 117, Subchapter B	No changing attributes.
DDU-202B	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.
DDU-202B	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
DDU-315A	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	R5131-0010	30 TAC Chapter 115, Water Separation	No changing attributes.
DDU-315A	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	61FF-1733	40 CFR Part 61, Subpart FF	No changing attributes.
DDU-B301	PROCESS HEATERS/FURNACES	N/A	R7300-1086	30 TAC Chapter 117, Subchapter B	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
DDU-B301	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.
DDU-B301	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
DDU-B302	PROCESS HEATERS/FURNACES	N/A	R7300-1086	30 TAC Chapter 117, Subchapter B	No changing attributes.
DDU-B302	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.
DDU-B302	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
DDU-FUG	FUGITIVE EMISSION UNITS	N/A	60GGG-0001	40 CFR Part 60, Subpart GGG	No changing attributes.
DDU-SEP	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	R5131-0010	30 TAC Chapter 115, Water Separation	No changing attributes.
DDU-SEP	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	61FF-1781	40 CFR Part 61, Subpart FF	No changing attributes.
DHT-101B	PROCESS HEATERS/FURNACES	N/A	R7300-0006	30 TAC Chapter 117, Subchapter B	NH3 Monitoring = Continuous emission monitoring system.
DHT-101B	PROCESS HEATERS/FURNACES	N/A	R7300-0007	30 TAC Chapter 117, Subchapter B	NH3 Monitoring = Stain tube.
DHT-101B	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60Ja-0002	40 CFR Part 60, Subpart Ja	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
DHT-101B	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
DHT-201B	PROCESS HEATERS/FURNACES	N/A	R7300-0008	30 TAC Chapter 117, Subchapter B	NH3 Monitoring = Continuous emission monitoring system.
DHT-201B	PROCESS HEATERS/FURNACES	N/A	R7300-0009	30 TAC Chapter 117, Subchapter B	NH3 Monitoring = Stain tube.
DHT-201B	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60Ja-0003	40 CFR Part 60, Subpart Ja	No changing attributes.
DHT-201B	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
DHT-FUG1	FUGITIVE EMISSION UNITS	N/A	60GGGa-001	40 CFR Part 60, Subpart GGGa	No changing attributes.
DKTO294-1	INCINERATOR	N/A	R7300-3688	30 TAC Chapter 117, Subchapter B	No changing attributes.
DKTO294-2	INCINERATOR	N/A	R7300-3688	30 TAC Chapter 117, Subchapter B	No changing attributes.
DKTO294-3	INCINERATOR	N/A	R7300-3688	30 TAC Chapter 117, Subchapter B	No changing attributes.
DOCK32	LOADING/UNLOADING OPERATIONS	N/A	R5211-0190	30 TAC Chapter 115, Loading and Unloading of VOC	Product Transferred = Gasoline
DOCK32	LOADING/UNLOADING OPERATIONS	N/A	R5211-0226	30 TAC Chapter 115, Loading and Unloading of VOC	Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
DOCK32	LOADING/UNLOADING OPERATIONS	N/A	61BB-0012	40 CFR Part 61, Subpart BB	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
DOCK32	LOADING/UNLOADING OPERATIONS	N/A	63CC-2502	40 CFR Part 63, Subpart CC	No changing attributes.
DOCK32	LOADING/UNLOADING OPERATIONS	N/A	63Y-0465	40 CFR Part 63, Subpart Y	Material Loaded = Material other than crude oil or gasoline.
DOCK32	LOADING/UNLOADING OPERATIONS	N/A	63Y-1665	40 CFR Part 63, Subpart Y	Material Loaded = Gasoline., Throughput = Source with throughput of 10 M barrels or 200 M barrels.
DOCK33	LOADING/UNLOADING OPERATIONS	N/A	R5211-0226	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.
DOCK33	LOADING/UNLOADING OPERATIONS	N/A	61BB-0012	40 CFR Part 61, Subpart BB	No changing attributes.
DOCK33	LOADING/UNLOADING OPERATIONS	N/A	63CC-2502	40 CFR Part 63, Subpart CC	No changing attributes.
DOCK33	LOADING/UNLOADING OPERATIONS	N/A	63Y-0465	40 CFR Part 63, Subpart Y	Material Loaded = Material other than crude oil or gasoline.
DOCK33	LOADING/UNLOADING OPERATIONS	N/A	63Y-1665	40 CFR Part 63, Subpart Y	Material Loaded = Gasoline., Throughput = Source with throughput of 10 M barrels or 200 M barrels.
DOCK34	LOADING/UNLOADING OPERATIONS	N/A	R5211-0226	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.
DOCK34	LOADING/UNLOADING OPERATIONS	N/A	61BB-0012	40 CFR Part 61, Subpart BB	No changing attributes.
DOCK34	LOADING/UNLOADING OPERATIONS	N/A	63CC-2502	40 CFR Part 63, Subpart CC	No changing attributes.
DOCK34	LOADING/UNLOADING	N/A	63Y-0465	40 CFR Part 63, Subpart Y	Material Loaded = Material other

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	OPERATIONS				than crude oil or gasoline.
DOCK34	LOADING/UNLOADING OPERATIONS	N/A	63Y-1665	40 CFR Part 63, Subpart Y	Material Loaded = Gasoline., Throughput = Source with throughput of 10 M barrels or 200 M barrels.
DOCK37	LOADING/UNLOADING OPERATIONS	N/A	R5211-0226	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.
DOCK37	LOADING/UNLOADING OPERATIONS	N/A	61BB-0012	40 CFR Part 61, Subpart BB	No changing attributes.
DOCK37	LOADING/UNLOADING OPERATIONS	N/A	63CC-2502	40 CFR Part 63, Subpart CC	No changing attributes.
DOCK37	LOADING/UNLOADING OPERATIONS	N/A	63Y-0465	40 CFR Part 63, Subpart Y	Material Loaded = Material other than crude oil or gasoline.
DOCK37	LOADING/UNLOADING OPERATIONS	N/A	63Y-1665	40 CFR Part 63, Subpart Y	Material Loaded = Gasoline., Throughput = Source with throughput of 10 M barrels or 200 M barrels.
DOCK38	LOADING/UNLOADING OPERATIONS	N/A	R5211-0226	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.
DOCK38	LOADING/UNLOADING OPERATIONS	N/A	61BB-0012	40 CFR Part 61, Subpart BB	No changing attributes.
DOCK38	LOADING/UNLOADING OPERATIONS	N/A	63CC-2502	40 CFR Part 63, Subpart CC	No changing attributes.
DOCK38	LOADING/UNLOADING OPERATIONS	N/A	63Y-0465	40 CFR Part 63, Subpart Y	Material Loaded = Material other than crude oil or gasoline.
DOCK38	LOADING/UNLOADING OPERATIONS	N/A	63Y-1665	40 CFR Part 63, Subpart Y	Material Loaded = Gasoline.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
DOCK40-41	LOADING/UNLOADING OPERATIONS	N/A	R55211-0207	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.
DOCK40-41	LOADING/UNLOADING OPERATIONS	N/A	61BB-0002	40 CFR Part 61, Subpart BB	No changing attributes.
DOCK54LOAD	LOADING/UNLOADING OPERATIONS	N/A	R5211-0225	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.
DOCK54LOAD	LOADING/UNLOADING OPERATIONS	N/A	61BB-0012	40 CFR Part 61, Subpart BB	No changing attributes.
DOCK54LOAD	LOADING/UNLOADING OPERATIONS	N/A	63Y-0391	40 CFR Part 63, Subpart Y	No changing attributes.
EMERGEN	SRIC ENGINES	N/A	R7300-0005	30 TAC Chapter 117, Subchapter B	No changing attributes.
EMERGEN	SRIC ENGINES	N/A	63ZZZZ-0001	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
ENVFC-FUG1	FUGITIVE EMISSION UNITS	N/A	60GGGa-01	40 CFR Part 60, Subpart GGGa	No changing attributes.
ENVFP-SEP	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	R5131-0010	30 TAC Chapter 115, Water Separation	No changing attributes.
ENVFP-SEP	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	61FF-1781	40 CFR Part 61, Subpart FF	No changing attributes.
EPN-34A	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R1111-0197	30 TAC Chapter 111, Visible Emissions	No changing attributes.
EPN-93	EMISSION POINTS/STATIONARY	N/A	R1111-0193	30 TAC Chapter 111, Visible Emissions	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	VENTS/PROCESS VENTS				
EPN-REFWWV	OP-REQ2 ONLY	N/A	61FF-IDS1	40 CFR Part 61, Subpart FF	Engineering Calculations = Engineering calculations show that the control device is proven to achieve its emission limitation., Control Device Type/Operation = Catalytic vapor incinerator with a reduction of organics being greater than or equal to 95 weight percent.
EPN-REFWWV	OP-REQ2 ONLY	N/A	61FF-IDS2	40 CFR Part 61, Subpart FF	Control Device Type/Operation = Catalytic vapor incinerator that provides a minimum residence time of 0.5 seconds at a minimum temperature of 760° C.
ESBGEN	SRIC ENGINES	N/A	R7300-0004	30 TAC Chapter 117, Subchapter B	No changing attributes.
ESBGEN	SRIC ENGINES	N/A	60IIII-0006	40 CFR Part 60, Subpart IIII	No changing attributes.
ESBGEN	SRIC ENGINES	N/A	63ZZZZ-0004	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
F-29	STORAGE TANKS/VESSELS	N/A	R5112-0006	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
F-501	STORAGE TANKS/VESSELS	N/A	63EEEE-1	40 CFR Part 63, Subpart EEEE	No changing attributes.
F-502	STORAGE TANKS/VESSELS	N/A	63EEEE-1	40 CFR Part 63, Subpart EEEE	No changing attributes.
F-603	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
F-603	STORAGE TANKS/VESSELS	N/A	61FF-0041	40 CFR Part 61, Subpart FF	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
F-604	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
F-604	STORAGE TANKS/VESSELS	N/A	61FF-0041	40 CFR Part 61, Subpart FF	No changing attributes.
F-605	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
F-605	STORAGE TANKS/VESSELS	N/A	61FF-0041	40 CFR Part 61, Subpart FF	No changing attributes.
F-606	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
F-606	STORAGE TANKS/VESSELS	N/A	61FF-0041	40 CFR Part 61, Subpart FF	No changing attributes.
F607/T-30	STORAGE TANKS/VESSELS	N/A	R5112-0013	30 TAC Chapter 115, Storage of VOCs	Control Device Type = Carbon adsorber (non-regenerative).
F607/T-30	STORAGE TANKS/VESSELS	N/A	R5112-0014	30 TAC Chapter 115, Storage of VOCs	Control Device Type = Direct-flame incinerator
F607/T-30	STORAGE TANKS/VESSELS	N/A	60Kb-0073	40 CFR Part 60, Subpart Kb	Control Device Type = Direct-flame incinerator
F607/T-30	STORAGE TANKS/VESSELS	N/A	60Kb-0074	40 CFR Part 60, Subpart Kb	Control Device Type = Carbon adsorber (non-regenerative).
F607/T-30	STORAGE TANKS/VESSELS	N/A	61F-0041	40 CFR Part 61, Subpart FF	Carbon Replacement Interval = The carbon in the carbon adsorption system is replaced when monitoring indicates breakthrough., Engineering Calculations = Engineering calculations show that the control device is proven to achieve its emission limitation., Control Device Type/Operations = Carbon adsorption system that does

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					not regenerate the carbon bed directly in the control device
F607/T-30	STORAGE TANKS/VESSELS	N/A	61F-0042	40 CFR Part 61, Subpart FF	Alternate Monitoring Parameters = Alternate monitoring parameters not requested, Engineering Calculations = Results of performance tests are used to demonstrate that the control device achieves emission limitation., Control Device Type/Operations = Thermal vapor incinerator with a reduction of organics being greater than or equal to 95 weight percent
F607/T-30	STORAGE TANKS/VESSELS	N/A	63EEEE-2	40 CFR Part 63, Subpart EEEE	Control Device Type = Direct-flame incinerator
F607/T-30	STORAGE TANKS/VESSELS	N/A	63EEEE-3	40 CFR Part 63, Subpart EEEE	Control Device Type = Carbon adsorber (non-regenerative).
F607/T-31	STORAGE TANKS/VESSELS	N/A	R5112-0013	30 TAC Chapter 115, Storage of VOCs	Control Device Type = Carbon adsorber (non-regenerative).
F607/T-31	STORAGE TANKS/VESSELS	N/A	R5112-0014	30 TAC Chapter 115, Storage of VOCs	Control Device Type = Direct-flame incinerator
F607/T-31	STORAGE TANKS/VESSELS	N/A	60Kb-0073	40 CFR Part 60, Subpart Kb	Control Device Type = Direct-flame incinerator
F607/T-31	STORAGE TANKS/VESSELS	N/A	60Kb-0074	40 CFR Part 60, Subpart Kb	Control Device Type = Carbon adsorber (non-regenerative).
F607/T-31	STORAGE TANKS/VESSELS	N/A	61F-0041	40 CFR Part 61, Subpart FF	Carbon Replacement Interval = The carbon in the carbon adsorption system is replaced when monitoring indicates breakthrough., Engineering Calculations = Engineering calculations show that the control device is proven to

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					achieve its emission limitation., Control Device Type/Operations = Carbon adsorption system that does not regenerate the carbon bed directly in the control device
F607/T-31	STORAGE TANKS/VESSELS	N/A	61F-0042	40 CFR Part 61, Subpart FF	Alternate Monitoring Parameters = Alternate monitoring parameters not requested, Engineering Calculations = Results of performance tests are used to demonstrate that the control device achieves emission limitation., Control Device Type/Operations = Thermal vapor incinerator with a reduction of organics being greater than or equal to 95 weight percent
F607/T-31	STORAGE TANKS/VESSELS	N/A	63EEEE-2	40 CFR Part 63, Subpart EEEE	Control Device Type = Direct-flame incinerator
F607/T-31	STORAGE TANKS/VESSELS	N/A	63EEEE-3	40 CFR Part 63, Subpart EEEE	Control Device Type = Carbon adsorber (non-regenerative).
F607/T-32	STORAGE TANKS/VESSELS	N/A	R5112-0013	30 TAC Chapter 115, Storage of VOCs	Control Device Type = Carbon adsorber (non-regenerative).
F607/T-32	STORAGE TANKS/VESSELS	N/A	R5112-0014	30 TAC Chapter 115, Storage of VOCs	Control Device Type = Direct-flame incinerator
F607/T-32	STORAGE TANKS/VESSELS	N/A	60Kb-0073	40 CFR Part 60, Subpart Kb	Control Device Type = Direct-flame incinerator
F607/T-32	STORAGE TANKS/VESSELS	N/A	60Kb-0074	40 CFR Part 60, Subpart Kb	Control Device Type = Carbon adsorber (non-regenerative).
F607/T-32	STORAGE TANKS/VESSELS	N/A	61F-0041	40 CFR Part 61, Subpart FF	Carbon Replacement Interval = The carbon in the carbon adsorption system is replaced when monitoring indicates breakthrough.,

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					Engineering Calculations = Engineering calculations show that the control device is proven to achieve its emission limitation., Control Device Type/Operations = Carbon adsorption system that does not regenerate the carbon bed directly in the control device
F607/T-32	STORAGE TANKS/VESSELS	N/A	61F-0042	40 CFR Part 61, Subpart FF	Alternate Monitoring Parameters = Alternate monitoring parameters not requested, Engineering Calculations = Results of performance tests are used to demonstrate that the control device achieves emission limitation., Control Device Type/Operations = Thermal vapor incinerator with a reduction of organics being greater than or equal to 95 weight percent
F607/T-32	STORAGE TANKS/VESSELS	N/A	63EEEE-2	40 CFR Part 63, Subpart EEEE	Control Device Type = Direct-flame incinerator
F607/T-32	STORAGE TANKS/VESSELS	N/A	63EEEE-3	40 CFR Part 63, Subpart EEEE	Control Device Type = Carbon adsorber (non-regenerative).
FCU3	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	R7300-5000	30 TAC Chapter 117, Subchapter B	No changing attributes.
FCU3	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	63UUU-0002	40 CFR Part 63, Subpart UUU	No changing attributes.
FCU3-CTWR	INDUSTRIAL PROCESS COOLING TOWERS	N/A	R5760-0206	30 TAC Chapter 115, HRVOC Cooling Towers	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
FCU3-CTWR	INDUSTRIAL PROCESS COOLING TOWERS	N/A	63CC-002	40 CFR Part 63, Subpart CC	No changing attributes.
GRP65CAR1	MISCELLANEOUS UNITS	AU2 E-610, AU2 E-620, AU2 E-630, AU2 E-640	65CAR-0001	40 CFR Part 65, Subpart D	No changing attributes.
GRP65CAR3	MISCELLANEOUS UNITS	ALK3 C1003, ALK3 C1004, ALK3 C1005, ALK3 C1006, FCCU3 405-E, FCCU3 407-E, PS3B 503-E	65CAR-0003	40 CFR Part 65, Subpart D	No changing attributes.
GRP65CAR4	MISCELLANEOUS UNITS	ALKY3V1005, FCCU1 D-1, FCCU3 401-D, UU3 301-D, UU3 302-D, UU3 303-D, UU3 304-D, UU3 305-D, UU3 306-D, UU4 D-401, UU4 D-402, UU4 D-403, UU4 D-404, UU4 D-405, UU4 D-406	65CAR-0004	40 CFR Part 65, Subpart D	No changing attributes.
GRP65CAR5	MISCELLANEOUS UNITS	ALK3 C1001, ALKY2 C-601, ALKY2 C-602, ALKY2 C-902, ALKY2 C101, ALKY2 C102, ARU 610-E, ARU 611-E, ARU 612-E, ARU 612-EB, COKERAE101, COKERAE403,	65CAR-0001	40 CFR Part 65, Subpart D	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
		COKERBE201, COKERBE403, COKERCE301, COKERCE403, FCCU3 401-E, FCCU3 505-E, FCCU3 506-E, PS3A 201-E, PS3A 202-E, PS3A 204-F, PS3A 376-F, PS3B 501-E, PS3B 502-E, PS3B 504-E, RHU 603-E, RHU 604-E, RHU 605-E, ULC 102-E, ULC 103-E, ULC 104-E, ULC 105-E, ULC 106-E, ULC 107-E, ULC 108-E, UU3 305-E, UU3 305-F, UU3 307-E, UU3 310-E, UU3 311-E, UU4 E-404, UU4 E-405, UU4 E-408			
GRP65CAR5	MISCELLANEOUS UNITS	ALK3 C1001, ALKY2 C-601, ALKY2 C-602, ALKY2 C-902, ALKY2 C101, ALKY2 C102, ARU 610-E, ARU 611-E, ARU 612-E, ARU 612-EB, COKERAE101, COKERAE403,	65CAR-0003	40 CFR Part 65, Subpart D	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
		COKERBE201, COKERBE403, COKERCE301, COKERCE403, FCCU3 401-E, FCCU3 505-E, FCCU3 506-E, PS3A 201-E, PS3A 202-E, PS3A 204-F, PS3A 376-F, PS3B 501-E, PS3B 502-E, PS3B 504-E, RHU 603-E, RHU 604-E, RHU 605-E, ULC 102-E, ULC 103-E, ULC 104-E, ULC 105-E, ULC 106-E, ULC 107-E, ULC 108-E, UU3 305-E, UU3 305-F, UU3 307-E, UU3 310-E, UU3 311-E, UU4 E-404, UU4 E-405, UU4 E-408			
GRP65CAR6	MISCELLANEOUS UNITS	DHT 851-D, DHT 852-D, ULC 100-D, ULC 101-D, ULC 102-D	65CAR-0002	40 CFR Part 65, Subpart D	Control device = nonflare control device.
GRP65CAR6	MISCELLANEOUS UNITS	DHT 851-D, DHT 852-D, ULC 100-D, ULC 101-D, ULC 102-D	65CAR-0004	40 CFR Part 65, Subpart D	Control device = flare
GRP-APISEP	VOLATILE ORGANIC	API-SEP1, API-	R5131-001	30 TAC Chapter 115, Water	Control Device = Direct flame

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	COMPOUND WATER SEPARATORS	SEP2		Separation	incinerator.
GRP-APISEP	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	API-SEP1, API-SEP2	R5131-002	30 TAC Chapter 115, Water Separation	Control Device = Carbon adsorption system.
GRP-APISEP	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	API-SEP1, API-SEP2	61FF-002	40 CFR Part 61, Subpart FF	Alternate Monitoring Parameters = COMPLYING WITH THE MONITORING REQUIREMENTS OF SUBPART FF, Control Device Type/Operation = THERMAL VAPOR INCINERATOR PROVIDING MIN. RESIDENCE TIME OF 0.5 SEC @ 760° C
GRP-APISEP	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	API-SEP1, API-SEP2	61FF-003	40 CFR Part 61, Subpart FF	Carbon Replacement Interval = EXHAUST IS MONITORED ON A REGULAR SCHEDULE AND CARBON IS REPLACED IMMEDIATELY UPON BREAKTHROUGH, Control Device Type/Operation = CARBON ADSORPTION SYSTEM NOT REGENERATING BED DIRECTLY IN DEVICE
GRP-TDUVENT	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	TDU-CB, TDU-CFG1, TDU-CFG2, TDU-GSR	R5121-0004	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
GRPVENT1	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	ALK2-CTWR, ALK3-CTWR, ALK3DEBCT, AU2-CTWR, CFHU-CTWR, COKR-CTWR, DKTO294-1,	R1111-0112	30 TAC Chapter 111, Visible Emissions	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
		DKTO294-2, DKTO294-3, EMERGEN, FCU3-CTWR, LAB-CTWR1, LAB-CTWR2, NDU-CTWR, P-617, P-618, P-J16A, P-J16B, P-J35A, P-J35B, P-J53A, P-J53B, P-J615, P-J616, P-J682, PRS3-CTWR, PS3-CTWR, SRU-F8CD, T1046PUMP, T1053APUMP, TK117APUMP, TK20PUMP, TK4000PUMP, TODOCK54, ULC-CTWR, UU3-CT, UU4-CTW			
GRPVENT2	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	ALK3-F1001, AU2-B601, AU2-B621A, AU2-B621B, CFHU101/2B, COKR-B101, COKR-B201, COKR-B203, COKR-B301, COKR-B302, DDU-101/2B, DDU-201/2B, DDU-B301, DDU-B302, DHT-101B, DHT-201B,	R1111-0112	30 TAC Chapter 111, Visible Emissions	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
		NDU1, NDU2-B201, NDU2-B202, PS3A101BAB, PS3A102BAB, PS3A-103B, PS3B-401BA, PS3B-401BB, PS3B-401BC, PS3B-402BE, PS3B402BFG, RDU-601B, RHU201B/2B, RHU301B/2B, RHU401B/2B, RHU501B/2B, RHU-601B, SHU3-B301, ULC-100B, ULC-101B, ULC-102B, ULC-103B, ULC104BABB, ULC105BABB, UU3-161A, UU3-301BN, UU3-301BS, UU3-302BN, UU3-302BS, UU3-306B, UU3307BABB, UU3-308BN, UU3-308BS, UU3-309B, UU3-313B, UU4-B401A, UU4-B401B, UU4B402ABC, UU4-B404, UU4-B405, UU4-B406			
GRPVENT2	EMISSION POINTS/STATIONARY	ALK3-F1001, AU2-B601, AU2-B621A,	R5720-0561	30 TAC Chapter 115, HRVOC Vent Gas	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	VENTS/PROCESS VENTS	AU2-B621B, CFHU101/2B, COKR-B101, COKR-B201, COKR-B203, COKR-B301, COKR-B302, DDU-101/2B, DDU-201/2B, DDU-B301, DDU-B302, DHT-101B, DHT-201B, NDU1, NDU2-B201, NDU2-B202, PS3A101BAB, PS3A102BAB, PS3A-103B, PS3B-401BA, PS3B-401BB, PS3B-401BC, PS3B-402BE, PS3B402BFG, RDU-601B, RHU201B/2B, RHU301B/2B, RHU401B/2B, RHU501B/2B, RHU-601B, SHU3-B301, ULC-100B, ULC-101B, ULC-102B, ULC-103B, ULC104BABB, ULC105BABB, UU3-161A, UU3-301BN, UU3-301BS, UU3-302BN, UU3-302BS,			

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
		UU3-306B, UU3307BABB, UU3-308BN, UU3-308BS, UU3-309B, UU3-313B, UU4-B401A, UU4-B401B, UU4B402ABC, UU4-B404, UU4-B405, UU4-B406			
HRU-FUG	FUGITIVE EMISSION UNITS	N/A	60GGG-0001	40 CFR Part 60, Subpart GGG	No changing attributes.
HRU-FUG1	FUGITIVE EMISSION UNITS	N/A	60GGGa-01	40 CFR Part 60, Subpart GGGa	No changing attributes.
HRU-OWS	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	R5131-0010	30 TAC Chapter 115, Water Separation	No changing attributes.
HRU-OWS	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	61FF-1769	40 CFR Part 61, Subpart FF	No changing attributes.
J803PUMP	SRIC ENGINES	N/A	R7300-0001	30 TAC Chapter 117, Subchapter B	No changing attributes.
J803PUMP	SRIC ENGINES	N/A	60IIII-0005	40 CFR Part 60, Subpart IIII	No changing attributes.
J803PUMP	SRIC ENGINES	N/A	63ZZZZ-0001	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
J804PUMP	SRIC ENGINES	N/A	R7300-0001	30 TAC Chapter 117, Subchapter B	No changing attributes.
J804PUMP	SRIC ENGINES	N/A	60IIII-0005	40 CFR Part 60, Subpart IIII	No changing attributes.
J804PUMP	SRIC ENGINES	N/A	63ZZZZ-0001	40 CFR Part 63, Subpart ZZZZ	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
LAB-DWS	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	R5131-0010	30 TAC Chapter 115, Water Separation	No changing attributes.
LAB-DWS	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	61FF-1781	40 CFR Part 61, Subpart FF	No changing attributes.
LAMPUMP	SRIC ENGINES	N/A	R7300-0001	30 TAC Chapter 117, Subchapter B	No changing attributes.
LAMPUMP	SRIC ENGINES	N/A	60IIII-0006	40 CFR Part 60, Subpart IIII	No changing attributes.
LAMPUMP	SRIC ENGINES	N/A	63ZZZZ-0002	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
NDU1	PROCESS HEATERS/FURNACES	N/A	R7300-1086	30 TAC Chapter 117, Subchapter B	No changing attributes.
NDU1	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.
NDU1	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
NDU2-B201	PROCESS HEATERS/FURNACES	N/A	R7300-0001	30 TAC Chapter 117, Subchapter B	No changing attributes.
NDU2-B201	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60Ja-0001	40 CFR Part 60, Subpart Ja	No changing attributes.
NDU2-B201	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
NDU2-B202	PROCESS HEATERS/FURNACES	N/A	R7300-0001	30 TAC Chapter 117, Subchapter B	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
NDU2-B202	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60Ja-0001	40 CFR Part 60, Subpart Ja	No changing attributes.
NDU2-B202	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
NDU2-FUG1	FUGITIVE EMISSION UNITS	N/A	60GGGa-01	40 CFR Part 60, Subpart GGGa	No changing attributes.
NDU-CTWR	INDUSTRIAL PROCESS COOLING TOWERS	N/A	63CC-002	40 CFR Part 63, Subpart CC	No changing attributes.
NDU-FUG	FUGITIVE EMISSION UNITS	N/A	60GGG-0001	40 CFR Part 60, Subpart GGG	No changing attributes.
NDU-OWS	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	R5131-0010	30 TAC Chapter 115, Water Separation	No changing attributes.
NDU-OWS	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	61FF-1769	40 CFR Part 61, Subpart FF	No changing attributes.
OILUNLOAD	LOADING/UNLOADING OPERATIONS	N/A	R5211-0008	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.
P-617	SRIC ENGINES	N/A	R7300-0005	30 TAC Chapter 117, Subchapter B	No changing attributes.
P-617	SRIC ENGINES	N/A	63ZZZZ-0007	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
P-618	SRIC ENGINES	N/A	R7300-0005	30 TAC Chapter 117, Subchapter B	No changing attributes.
P-618	SRIC ENGINES	N/A	63ZZZZ-0007	40 CFR Part 63, Subpart ZZZZ	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
P-J16A	SRIC ENGINES	N/A	R7300-0003	30 TAC Chapter 117, Subchapter B	No changing attributes.
P-J16A	SRIC ENGINES	N/A	63ZZZZ-0011	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
P-J16B	SRIC ENGINES	N/A	R7300-0003	30 TAC Chapter 117, Subchapter B	No changing attributes.
P-J16B	SRIC ENGINES	N/A	63ZZZZ-0011	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
P-J35A	SRIC ENGINES	N/A	R7300-0005	30 TAC Chapter 117, Subchapter B	No changing attributes.
P-J35A	SRIC ENGINES	N/A	63ZZZZ-0010	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
P-J35B	SRIC ENGINES	N/A	R7300-0005	30 TAC Chapter 117, Subchapter B	No changing attributes.
P-J35B	SRIC ENGINES	N/A	63ZZZZ-0010	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
P-J53A	SRIC ENGINES	N/A	R7300-0005	30 TAC Chapter 117, Subchapter B	No changing attributes.
P-J53A	SRIC ENGINES	N/A	63ZZZZ-0010	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
P-J53B	SRIC ENGINES	N/A	R7300-0005	30 TAC Chapter 117, Subchapter B	No changing attributes.
P-J53B	SRIC ENGINES	N/A	63ZZZZ-0010	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
P-J615	SRIC ENGINES	N/A	R7300-0005	30 TAC Chapter 117, Subchapter B	No changing attributes.
P-J615	SRIC ENGINES	N/A	63ZZZZ-0005	40 CFR Part 63, Subpart ZZZZ	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
P-J616	SRIC ENGINES	N/A	R7300-0005	30 TAC Chapter 117, Subchapter B	No changing attributes.
P-J616	SRIC ENGINES	N/A	63ZZZZ-0005	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
P-J682	SRIC ENGINES	N/A	R7300-0005	30 TAC Chapter 117, Subchapter B	No changing attributes.
P-J682	SRIC ENGINES	N/A	63ZZZZ-0004	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
PRESSURE1	SRIC ENGINES	N/A	R7300-0005	30 TAC Chapter 117, Subchapter B	No changing attributes.
PRESSURE1	SRIC ENGINES	N/A	60IIII-0007	40 CFR Part 60, Subpart IIII	No changing attributes.
PRESSURE1	SRIC ENGINES	N/A	63ZZZZ-0005	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
PRESSURE2	SRIC ENGINES	N/A	R7300-0005	30 TAC Chapter 117, Subchapter B	No changing attributes.
PRESSURE2	SRIC ENGINES	N/A	60IIII-0007	40 CFR Part 60, Subpart IIII	No changing attributes.
PRESSURE2	SRIC ENGINES	N/A	63ZZZZ-0005	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
PRO-AU2	CHEMICAL MANUFACTURING PROCESS	N/A	63F-0010	40 CFR Part 63, Subpart F	No changing attributes.
PRO-BIOTRT	TREATMENT PROCESS	N/A	61FF-0550	40 CFR Part 61, Subpart FF	No changing attributes.
PRO-SRU	GAS SWEETENING/SULFUR RECOVERY UNITS	N/A	R2007-0002	30 TAC Chapter 112, Sulfur Compounds	No changing attributes.
PRO-WWTP	WASTEWATER UNITS	N/A	R5142-0004	30 TAC Chapter 115, Industrial Wastewater	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
PRS3-CTWR	INDUSTRIAL PROCESS COOLING TOWERS	N/A	63CC-002	40 CFR Part 63, Subpart CC	No changing attributes.
PS2-FUG	FUGITIVE EMISSION UNITS	N/A	R5780-ALL	30 TAC Chapter 115, HRVOC Fugitive Emissions	No changing attributes.
PS2-FUG	FUGITIVE EMISSION UNITS	N/A	R5352-ALL	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	No changing attributes.
PS2-FUG	FUGITIVE EMISSION UNITS	N/A	60GGGa-001	40 CFR Part 60, Subpart GGGa	No changing attributes.
PS2-FUG	FUGITIVE EMISSION UNITS	N/A	63CCVV-ALL	40 CFR Part 63, Subpart CC	No changing attributes.
PS3A-101BA	PROCESS HEATERS/FURNACES	N/A	R7300-1493	30 TAC Chapter 117, Subchapter B	No changing attributes.
PS3A-101BA	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.
PS3A-101BA	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
PS3A-101BB	PROCESS HEATERS/FURNACES	N/A	R7300-1493	30 TAC Chapter 117, Subchapter B	No changing attributes.
PS3A-101BB	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.
PS3A-101BB	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
PS3A-102BA	PROCESS HEATERS/FURNACES	N/A	R7300-1289	30 TAC Chapter 117, Subchapter B	No changing attributes.
PS3A-102BA	FCCU CAT REGEN/FUEL	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	GAS COMBUSTION/CLAUS SRU				
PS3A-102BA	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
PS3A-102BB	PROCESS HEATERS/FURNACES	N/A	R7300-1289	30 TAC Chapter 117, Subchapter B	No changing attributes.
PS3A-102BB	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.
PS3A-102BB	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
PS3A-103B	PROCESS HEATERS/FURNACES	N/A	R7300-1289	30 TAC Chapter 117, Subchapter B	No changing attributes.
PS3A-103B	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.
PS3A-103B	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
PS3A-205F	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	R5131-0010	30 TAC Chapter 115, Water Separation	No changing attributes.
PS3A-205F	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	61FF-1733	40 CFR Part 61, Subpart FF	No changing attributes.
PS3A-FUG1	FUGITIVE EMISSION UNITS	N/A	60GGGa-01	40 CFR Part 60, Subpart GGGa	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
PS3A-OWS	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	R5131-0010	30 TAC Chapter 115, Water Separation	No changing attributes.
PS3A-OWS	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	61FF-1781	40 CFR Part 61, Subpart FF	No changing attributes.
PS3B-401BA	PROCESS HEATERS/FURNACES	N/A	R7300-1493	30 TAC Chapter 117, Subchapter B	No changing attributes.
PS3B-401BA	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.
PS3B-401BA	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
PS3B-401BB	PROCESS HEATERS/FURNACES	N/A	R7300-1493	30 TAC Chapter 117, Subchapter B	No changing attributes.
PS3B-401BB	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.
PS3B-401BB	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
PS3B-401BC	PROCESS HEATERS/FURNACES	N/A	R7300-1493	30 TAC Chapter 117, Subchapter B	No changing attributes.
PS3B-401BC	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.
PS3B-401BC	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
PS3B-402BE	PROCESS HEATERS/FURNACES	N/A	R7300-1291	30 TAC Chapter 117, Subchapter B	NH3 Monitoring = Mass balance
PS3B-402BE	PROCESS HEATERS/FURNACES	N/A	R7300-1292	30 TAC Chapter 117, Subchapter B	NH3 Monitoring = Stain tube.
PS3B-402BE	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.
PS3B-402BE	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
PS3B-402BF	PROCESS HEATERS/FURNACES	N/A	R7300-1291	30 TAC Chapter 117, Subchapter B	NH3 Monitoring = Mass balance
PS3B-402BF	PROCESS HEATERS/FURNACES	N/A	R7300-1292	30 TAC Chapter 117, Subchapter B	NH3 Monitoring = Stain tube.
PS3B-402BF	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.
PS3B-402BF	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
PS3B-402BG	PROCESS HEATERS/FURNACES	N/A	R7300-1494	30 TAC Chapter 117, Subchapter B	NH3 Monitoring = Mass balance
PS3B-402BG	PROCESS HEATERS/FURNACES	N/A	R7300-1495	30 TAC Chapter 117, Subchapter B	NH3 Monitoring = Stain tube.
PS3B-402BG	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.
PS3B-402BG	PROCESS	N/A	63DDDDD-1	40 CFR Part 63, Subpart	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	HEATERS/FURNACES			DDDDD	
PS3B-515F	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	R5131-0010	30 TAC Chapter 115, Water Separation	No changing attributes.
PS3B-515F	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	61FF-1733	40 CFR Part 61, Subpart FF	No changing attributes.
PS3B-516F	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	R5131-0010	30 TAC Chapter 115, Water Separation	No changing attributes.
PS3B-516F	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	61FF-1733	40 CFR Part 61, Subpart FF	No changing attributes.
PS3B-F510	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	R5131-0010	30 TAC Chapter 115, Water Separation	No changing attributes.
PS3B-F510	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	61FF-1733	40 CFR Part 61, Subpart FF	No changing attributes.
PS3B-FUG1	FUGITIVE EMISSION UNITS	N/A	60GGGa-001	40 CFR Part 60, Subpart GGGa	No changing attributes.
PS3B-SEP1	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	R5131-0010	30 TAC Chapter 115, Water Separation	No changing attributes.
PS3B-SEP1	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	61FF-1781	40 CFR Part 61, Subpart FF	No changing attributes.
PS3B-SEP2	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	R5131-0010	30 TAC Chapter 115, Water Separation	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
PS3B-SEP2	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	61FF-1781	40 CFR Part 61, Subpart FF	No changing attributes.
PS3-CTWR	INDUSTRIAL PROCESS COOLING TOWERS	N/A	R5760-0206	30 TAC Chapter 115, HRVOC Cooling Towers	No changing attributes.
PS3-CTWR	INDUSTRIAL PROCESS COOLING TOWERS	N/A	63CC-002	40 CFR Part 63, Subpart CC	No changing attributes.
RDU-601B	PROCESS HEATERS/FURNACES	N/A	R7300-1289	30 TAC Chapter 117, Subchapter B	No changing attributes.
RDU-601B	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	60Db-1	40 CFR Part 60, Subpart Db	No changing attributes.
RDU-601B	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.
RDU-601B	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
RDU-FUG	FUGITIVE EMISSION UNITS	N/A	60GGG-0001	40 CFR Part 60, Subpart GGG	No changing attributes.
RDU-FUG1	FUGITIVE EMISSION UNITS	N/A	60GGGa-001	40 CFR Part 60, Subpart GGGa	No changing attributes.
RDU-SEP	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	R5131-0010	30 TAC Chapter 115, Water Separation	No changing attributes.
RDU-SEP	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	61FF-1781	40 CFR Part 61, Subpart FF	No changing attributes.
REFDOCKFUG	FUGITIVE EMISSION	N/A	R5352-0001	30 TAC Chapter 115, Pet.	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	UNITS			Refinery & Petrochemicals	
REFDOCKFUG	FUGITIVE EMISSION UNITS	N/A	63CCVV-0001	40 CFR Part 63, Subpart CC	No changing attributes.
REF-FUG	FUGITIVE EMISSION UNITS	N/A	R5780-ALL	30 TAC Chapter 115, HRVOC Fugitive Emissions	No changing attributes.
REF-FUG	FUGITIVE EMISSION UNITS	N/A	R5352-ALL	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	No changing attributes.
REF-FUG	FUGITIVE EMISSION UNITS	N/A	63CCVV-ALL	40 CFR Part 63, Subpart CC	No changing attributes.
RHU-201B	PROCESS HEATERS/FURNACES	N/A	R7300-1018	30 TAC Chapter 117, Subchapter B	No changing attributes.
RHU-201B	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.
RHU-201B	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
RHU-202B	PROCESS HEATERS/FURNACES	N/A	R7300-1018	30 TAC Chapter 117, Subchapter B	No changing attributes.
RHU-202B	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.
RHU-202B	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
RHU-301B	PROCESS HEATERS/FURNACES	N/A	R7300-1018	30 TAC Chapter 117, Subchapter B	No changing attributes.
RHU-301B	FCCU CAT REGEN/FUEL GAS	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	COMBUSTION/CLAUS SRU				
RHU-301B	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
RHU-302B	PROCESS HEATERS/FURNACES	N/A	R7300-1018	30 TAC Chapter 117, Subchapter B	No changing attributes.
RHU-302B	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.
RHU-302B	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
RHU-401B	PROCESS HEATERS/FURNACES	N/A	R7300-1018	30 TAC Chapter 117, Subchapter B	No changing attributes.
RHU-401B	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.
RHU-401B	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
RHU-402B	PROCESS HEATERS/FURNACES	N/A	R7300-1018	30 TAC Chapter 117, Subchapter B	No changing attributes.
RHU-402B	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.
RHU-402B	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
RHU-501B	PROCESS	N/A	R7300-1097	30 TAC Chapter 117,	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	HEATERS/FURNACES			Subchapter B	
RHU-501B	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.
RHU-501B	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
RHU-502B	PROCESS HEATERS/FURNACES	N/A	R7300-1290	30 TAC Chapter 117, Subchapter B	No changing attributes.
RHU-502B	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60Ja-0003	40 CFR Part 60, Subpart Ja	No changing attributes.
RHU-502B	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
RHU-601B	PROCESS HEATERS/FURNACES	N/A	R7300-1086	30 TAC Chapter 117, Subchapter B	No changing attributes.
RHU-601B	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.
RHU-601B	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
RHUCP-FUG1	FUGITIVE EMISSION UNITS	N/A	60GGGa-001	40 CFR Part 60, Subpart GGGa	No changing attributes.
RHU-FUG	FUGITIVE EMISSION UNITS	N/A	60GGG-0001	40 CFR Part 60, Subpart GGG	No changing attributes.
RHU-SEP1	VOLATILE ORGANIC COMPOUND WATER	N/A	R5131-0010	30 TAC Chapter 115, Water Separation	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	SEPARATORS				
RHU-SEP1	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	61FF-1781	40 CFR Part 61, Subpart FF	No changing attributes.
RHU-SEP2	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	R5131-0010	30 TAC Chapter 115, Water Separation	No changing attributes.
RHU-SEP2	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	61FF-1781	40 CFR Part 61, Subpart FF	No changing attributes.
RHU-T1012	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
RHU-T1012	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
RHU-T1013	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
RHU-T1013	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
SHU3-B301	PROCESS HEATERS/FURNACES	N/A	R7300-0001	30 TAC Chapter 117, Subchapter B	No changing attributes.
SHU3-B301	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60Ja-0001	40 CFR Part 60, Subpart Ja	No changing attributes.
SHU3-B301	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
SHU3-FUG1	FUGITIVE EMISSION UNITS	N/A	60GGGa-01	40 CFR Part 60, Subpart GGGa	No changing attributes.
SRU-CT	INDUSTRIAL PROCESS	N/A	R5760-0025	30 TAC Chapter 115,	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	COOLING TOWERS			HRVOC Cooling Towers	
SRU-CT	INDUSTRIAL PROCESS COOLING TOWERS	N/A	63CC-002	40 CFR Part 63, Subpart CC	No changing attributes.
SRU-F8C	INCINERATOR	N/A	R7300-3144	30 TAC Chapter 117, Subchapter B	No changing attributes.
SRU-F8C	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0029	40 CFR Part 60, Subpart J	No changing attributes.
SRU-F8D	INCINERATOR	N/A	R7300-3144	30 TAC Chapter 117, Subchapter B	No changing attributes.
SRU-F8D	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0029	40 CFR Part 60, Subpart J	No changing attributes.
T1003	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T1046PUMP	SRIC ENGINES	N/A	R7300-0004	30 TAC Chapter 117, Subchapter B	No changing attributes.
T1046PUMP	SRIC ENGINES	N/A	60IIII-0006	40 CFR Part 60, Subpart IIII	No changing attributes.
T1046PUMP	SRIC ENGINES	N/A	63ZZZZ-0002	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
T1053APUMP	SRIC ENGINES	N/A	R7300-0004	30 TAC Chapter 117, Subchapter B	No changing attributes.
T1053APUMP	SRIC ENGINES	N/A	60IIII-0006	40 CFR Part 60, Subpart IIII	No changing attributes.
T1053APUMP	SRIC ENGINES	N/A	63ZZZZ-0002	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
T280-10	STORAGE	N/A	R5112-0019	30 TAC Chapter 115,	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	TANKS/VESSELS			Storage of VOCs	
T280-10	STORAGE TANKS/VESSELS	N/A	60Kb-0069	40 CFR Part 60, Subpart Kb	No changing attributes.
T280-10	STORAGE TANKS/VESSELS	N/A	63CC-0004	40 CFR Part 63, Subpart CC	No changing attributes.
T280-100	STORAGE TANKS/VESSELS	N/A	R5112-0090	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-100	STORAGE TANKS/VESSELS	N/A	60Kb-0070	40 CFR Part 60, Subpart Kb	No changing attributes.
T280-100	STORAGE TANKS/VESSELS	N/A	63CC-0256	40 CFR Part 63, Subpart CC	No changing attributes.
T280-1004	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-1004	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
T280-1005	STORAGE TANKS/VESSELS	N/A	R5112-0010	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-1005	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
T280-101	STORAGE TANKS/VESSELS	N/A	R5112-0019	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-101	STORAGE TANKS/VESSELS	N/A	63CC-0248	40 CFR Part 63, Subpart CC	No changing attributes.
T280-101	STORAGE TANKS/VESSELS	N/A	63G-0001	40 CFR Part 63, Subpart G	No changing attributes.
T280-1010	STORAGE TANKS/VESSELS	N/A	R5111	30 TAC Chapter 115, Storage of VOCs	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
T280-1018	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-1018	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
T280-102	STORAGE TANKS/VESSELS	N/A	R5112-0019	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-102	STORAGE TANKS/VESSELS	N/A	63CC-0081	40 CFR Part 63, Subpart CC	No changing attributes.
T280-102	STORAGE TANKS/VESSELS	N/A	63G-0001	40 CFR Part 63, Subpart G	No changing attributes.
T280-1020	STORAGE TANKS/VESSELS	N/A	R5112-0096	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-1020	STORAGE TANKS/VESSELS	N/A	60Kb-0419	40 CFR Part 60, Subpart Kb	No changing attributes.
T280-1020	STORAGE TANKS/VESSELS	N/A	63CC-0256	40 CFR Part 63, Subpart CC	No changing attributes.
T280-1021	STORAGE TANKS/VESSELS	N/A	R5112-0096	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-1021	STORAGE TANKS/VESSELS	N/A	60Kb-0419	40 CFR Part 60, Subpart Kb	No changing attributes.
T280-1021	STORAGE TANKS/VESSELS	N/A	63CC-0131	40 CFR Part 63, Subpart CC	No changing attributes.
T280-1023	STORAGE TANKS/VESSELS	N/A	R5112-0096	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-1023	STORAGE TANKS/VESSELS	N/A	63CC-0256	40 CFR Part 63, Subpart CC	No changing attributes.
T280-1024	STORAGE TANKS/VESSELS	N/A	R5112-0096	30 TAC Chapter 115, Storage of VOCs	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
T280-1024	STORAGE TANKS/VESSELS	N/A	63CC-0256	40 CFR Part 63, Subpart CC	No changing attributes.
T280-1025	STORAGE TANKS/VESSELS	N/A	R5112-0096	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-1025	STORAGE TANKS/VESSELS	N/A	63CC-0256	40 CFR Part 63, Subpart CC	No changing attributes.
T280-103	STORAGE TANKS/VESSELS	N/A	R5112-0090	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-103	STORAGE TANKS/VESSELS	N/A	63CC-0059	40 CFR Part 63, Subpart CC	No changing attributes.
T280-1039	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-1039	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
T280-104	STORAGE TANKS/VESSELS	N/A	R5112-0090	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-104	STORAGE TANKS/VESSELS	N/A	63CC-0059	40 CFR Part 63, Subpart CC	No changing attributes.
T280-1041	STORAGE TANKS/VESSELS	N/A	R5112-0090	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-1041	STORAGE TANKS/VESSELS	N/A	60Kb-0070	40 CFR Part 60, Subpart Kb	No changing attributes.
T280-1041	STORAGE TANKS/VESSELS	N/A	63CC-0256	40 CFR Part 63, Subpart CC	No changing attributes.
T280-1042	STORAGE TANKS/VESSELS	N/A	R5112-0090	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-1042	STORAGE TANKS/VESSELS	N/A	63CC-0256	40 CFR Part 63, Subpart CC	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
T280-1044	STORAGE TANKS/VESSELS	N/A	R5112-0090	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-1044	STORAGE TANKS/VESSELS	N/A	63CC-0059	40 CFR Part 63, Subpart CC	No changing attributes.
T280-1045	STORAGE TANKS/VESSELS	N/A	R5112-0096	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-1045	STORAGE TANKS/VESSELS	N/A	60Kb-0419	40 CFR Part 60, Subpart Kb	No changing attributes.
T280-1045	STORAGE TANKS/VESSELS	N/A	63CC-0131	40 CFR Part 63, Subpart CC	No changing attributes.
T280-1046	STORAGE TANKS/VESSELS	N/A	R5112-0096	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-1046	STORAGE TANKS/VESSELS	N/A	61FF-0006	40 CFR Part 61, Subpart FF	No changing attributes.
T280-1046	STORAGE TANKS/VESSELS	N/A	63CC-0131	40 CFR Part 63, Subpart CC	No changing attributes.
T280-1047	STORAGE TANKS/VESSELS	N/A	R5112-0096	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-1047	STORAGE TANKS/VESSELS	N/A	63CC-0256	40 CFR Part 63, Subpart CC	No changing attributes.
T280-1048	STORAGE TANKS/VESSELS	N/A	R5112-0096	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-1048	STORAGE TANKS/VESSELS	N/A	61FF-0006	40 CFR Part 61, Subpart FF	No changing attributes.
T280-1048	STORAGE TANKS/VESSELS	N/A	63CC-0071	40 CFR Part 63, Subpart CC	No changing attributes.
T280-105	STORAGE TANKS/VESSELS	N/A	R5112-0090	30 TAC Chapter 115, Storage of VOCs	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
T280-105	STORAGE TANKS/VESSELS	N/A	61FF-0006	40 CFR Part 61, Subpart FF	No changing attributes.
T280-105	STORAGE TANKS/VESSELS	N/A	63CC-0059	40 CFR Part 63, Subpart CC	No changing attributes.
T280-1051	STORAGE TANKS/VESSELS	N/A	R5112-0096	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-1051	STORAGE TANKS/VESSELS	N/A	60Kb-0419	40 CFR Part 60, Subpart Kb	No changing attributes.
T280-1051	STORAGE TANKS/VESSELS	N/A	63CC-0256	40 CFR Part 63, Subpart CC	No changing attributes.
T280-1052	STORAGE TANKS/VESSELS	N/A	R5112-0096	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-1052	STORAGE TANKS/VESSELS	N/A	60Kb-0419	40 CFR Part 60, Subpart Kb	No changing attributes.
T280-1052	STORAGE TANKS/VESSELS	N/A	63CC-0256	40 CFR Part 63, Subpart CC	No changing attributes.
T280-1053	STORAGE TANKS/VESSELS	N/A	R5112-0096	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-1053	STORAGE TANKS/VESSELS	N/A	63CC-0131	40 CFR Part 63, Subpart CC	No changing attributes.
T280-1054	STORAGE TANKS/VESSELS	N/A	R5112-0090	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-1054	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	R5131-0005	30 TAC Chapter 115, Water Separation	No changing attributes.
T280-1054	STORAGE TANKS/VESSELS	N/A	60KB-0124	40 CFR Part 60, Subpart Kb	No changing attributes.
T280-1054	STORAGE	N/A	61FF-0006	40 CFR Part 61, Subpart FF	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	TANKS/VESSELS				
T280-1054	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	61FF-1003	40 CFR Part 61, Subpart FF	No changing attributes.
T280-1054	STORAGE TANKS/VESSELS	N/A	63CC-0071	40 CFR Part 63, Subpart CC	No changing attributes.
T280-1055	STORAGE TANKS/VESSELS	N/A	R5112-0096	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-1055	STORAGE TANKS/VESSELS	N/A	63CC-0131	40 CFR Part 63, Subpart CC	No changing attributes.
T280-1056	STORAGE TANKS/VESSELS	N/A	R5112-0090	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-1056	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	R5131-0005	30 TAC Chapter 115, Water Separation	No changing attributes.
T280-1056	STORAGE TANKS/VESSELS	N/A	60KB-0124	40 CFR Part 60, Subpart Kb	No changing attributes.
T280-1056	STORAGE TANKS/VESSELS	N/A	61FF-0006	40 CFR Part 61, Subpart FF	No changing attributes.
T280-1056	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	61FF-1003	40 CFR Part 61, Subpart FF	No changing attributes.
T280-1056	STORAGE TANKS/VESSELS	N/A	63CC-0071	40 CFR Part 63, Subpart CC	No changing attributes.
T280-1057	STORAGE TANKS/VESSELS	N/A	R5112-0090	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-1057	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	R5131-0005	30 TAC Chapter 115, Water Separation	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
T280-1057	STORAGE TANKS/VESSELS	N/A	61FF-0006	40 CFR Part 61, Subpart FF	No changing attributes.
T280-1057	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	61FF-1003	40 CFR Part 61, Subpart FF	No changing attributes.
T280-1057	STORAGE TANKS/VESSELS	N/A	63CC-0071	40 CFR Part 63, Subpart CC	No changing attributes.
T280-1058	STORAGE TANKS/VESSELS	N/A	R5112-0010	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-1058	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	R5131-005	30 TAC Chapter 115, Water Separation	No changing attributes.
T280-1058	STORAGE TANKS/VESSELS	N/A	60Kb-001	40 CFR Part 60, Subpart Kb	No changing attributes.
T280-1058	STORAGE TANKS/VESSELS	N/A	61FF-001	40 CFR Part 61, Subpart FF	No changing attributes.
T280-1058	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	61FF-1003	40 CFR Part 61, Subpart FF	No changing attributes.
T280-1058	STORAGE TANKS/VESSELS	N/A	63CC-0071	40 CFR Part 63, Subpart CC	No changing attributes.
T280-106	STORAGE TANKS/VESSELS	N/A	R5112-0090	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-106	STORAGE TANKS/VESSELS	N/A	60Kb-0070	40 CFR Part 60, Subpart Kb	No changing attributes.
T280-106	STORAGE TANKS/VESSELS	N/A	61FF-0006	40 CFR Part 61, Subpart FF	No changing attributes.
T280-106	STORAGE TANKS/VESSELS	N/A	63CC-0059	40 CFR Part 63, Subpart CC	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
T280-107	STORAGE TANKS/VESSELS	N/A	R5112-0019	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-107	STORAGE TANKS/VESSELS	N/A	63CC-0081	40 CFR Part 63, Subpart CC	No changing attributes.
T280-107	STORAGE TANKS/VESSELS	N/A	63G-0001	40 CFR Part 63, Subpart G	No changing attributes.
T280-108	STORAGE TANKS/VESSELS	N/A	R5112-0019	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-108	STORAGE TANKS/VESSELS	N/A	63CC-0081	40 CFR Part 63, Subpart CC	No changing attributes.
T280-108	STORAGE TANKS/VESSELS	N/A	63G-0001	40 CFR Part 63, Subpart G	No changing attributes.
T280-11	STORAGE TANKS/VESSELS	N/A	R5112-0090	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-11	STORAGE TANKS/VESSELS	N/A	60Kb-0070	40 CFR Part 60, Subpart Kb	No changing attributes.
T280-11	STORAGE TANKS/VESSELS	N/A	63CC-0256	40 CFR Part 63, Subpart CC	No changing attributes.
T280-110	STORAGE TANKS/VESSELS	N/A	R5112-0019	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-110	STORAGE TANKS/VESSELS	N/A	60Kb-0026	40 CFR Part 60, Subpart Kb	No changing attributes.
T280-110	STORAGE TANKS/VESSELS	N/A	63CC-0004	40 CFR Part 63, Subpart CC	No changing attributes.
T280-112	STORAGE TANKS/VESSELS	N/A	R5112-0019	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-112	STORAGE TANKS/VESSELS	N/A	63CC-0081	40 CFR Part 63, Subpart CC	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
T280-112	STORAGE TANKS/VESSELS	N/A	63G-0001	40 CFR Part 63, Subpart G	No changing attributes.
T280-114	STORAGE TANKS/VESSELS	N/A	R5112-0019	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-114	STORAGE TANKS/VESSELS	N/A	63CC-0081	40 CFR Part 63, Subpart CC	No changing attributes.
T280-114	STORAGE TANKS/VESSELS	N/A	63G-0001	40 CFR Part 63, Subpart G	No changing attributes.
T280-115	STORAGE TANKS/VESSELS	N/A	R5112-0019	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-115	STORAGE TANKS/VESSELS	N/A	63CC-0248	40 CFR Part 63, Subpart CC	No changing attributes.
T280-115	STORAGE TANKS/VESSELS	N/A	63G-0001	40 CFR Part 63, Subpart G	No changing attributes.
T280-116	STORAGE TANKS/VESSELS	N/A	R5112-0019	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-116	STORAGE TANKS/VESSELS	N/A	63CC-0081	40 CFR Part 63, Subpart CC	No changing attributes.
T280-116	STORAGE TANKS/VESSELS	N/A	63G-0001	40 CFR Part 63, Subpart G	No changing attributes.
T280-117	STORAGE TANKS/VESSELS	N/A	R5112-0019	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-117	STORAGE TANKS/VESSELS	N/A	60Kb-0068	40 CFR Part 60, Subpart Kb	No changing attributes.
T280-117	STORAGE TANKS/VESSELS	N/A	61FF-0005	40 CFR Part 61, Subpart FF	No changing attributes.
T280-117	STORAGE TANKS/VESSELS	N/A	63CC-0081	40 CFR Part 63, Subpart CC	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
T280-118	STORAGE TANKS/VESSELS	N/A	R5112-0019	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-118	STORAGE TANKS/VESSELS	N/A	60Kb-0068	40 CFR Part 60, Subpart Kb	No changing attributes.
T280-118	STORAGE TANKS/VESSELS	N/A	61FF-0005	40 CFR Part 61, Subpart FF	No changing attributes.
T280-118	STORAGE TANKS/VESSELS	N/A	63CC-0081	40 CFR Part 63, Subpart CC	No changing attributes.
T280-128	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-128	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
T280-129	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-129	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
T280-12A	STORAGE TANKS/VESSELS	N/A	R115-0019	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-12A	STORAGE TANKS/VESSELS	N/A	60Kb-0026	40 CFR Part 60, Subpart Kb	No changing attributes.
T280-12A	STORAGE TANKS/VESSELS	N/A	63CC	40 CFR Part 63, Subpart CC	No changing attributes.
T280-13	STORAGE TANKS/VESSELS	N/A	R5112-0090	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-13	STORAGE TANKS/VESSELS	N/A	63CC-0059	40 CFR Part 63, Subpart CC	No changing attributes.
T280-130	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
T280-130	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
T280-132	STORAGE TANKS/VESSELS	N/A	R5112-0132	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-132	STORAGE TANKS/VESSELS	N/A	60KB-0072	40 CFR Part 60, Subpart Kb	No changing attributes.
T280-132	STORAGE TANKS/VESSELS	N/A	61FF-0009	40 CFR Part 61, Subpart FF	No changing attributes.
T280-133	STORAGE TANKS/VESSELS	N/A	R5112-0132	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-133	STORAGE TANKS/VESSELS	N/A	60KB-0072	40 CFR Part 60, Subpart Kb	No changing attributes.
T280-133	STORAGE TANKS/VESSELS	N/A	61FF-0009	40 CFR Part 61, Subpart FF	No changing attributes.
T280-134	STORAGE TANKS/VESSELS	N/A	R5112-0132	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-134	STORAGE TANKS/VESSELS	N/A	60KB-0072	40 CFR Part 60, Subpart Kb	No changing attributes.
T280-134	STORAGE TANKS/VESSELS	N/A	61FF-0009	40 CFR Part 61, Subpart FF	No changing attributes.
T280-135	STORAGE TANKS/VESSELS	N/A	R5112-0139	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-135	STORAGE TANKS/VESSELS	N/A	61FF-0014	40 CFR Part 61, Subpart FF	No changing attributes.
T280-135	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
T280-136	STORAGE TANKS/VESSELS	N/A	R5112-0139	30 TAC Chapter 115, Storage of VOCs	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
T280-136	STORAGE TANKS/VESSELS	N/A	61FF-0014	40 CFR Part 61, Subpart FF	No changing attributes.
T280-136	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
T280-137	STORAGE TANKS/VESSELS	N/A	R5112-0139	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-137	STORAGE TANKS/VESSELS	N/A	61FF-0014	40 CFR Part 61, Subpart FF	No changing attributes.
T280-137	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
T280-138	STORAGE TANKS/VESSELS	N/A	R5112-0139	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-138	STORAGE TANKS/VESSELS	N/A	61FF-0014	40 CFR Part 61, Subpart FF	No changing attributes.
T280-138	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
T280-14	STORAGE TANKS/VESSELS	N/A	R5112-0090	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-14	STORAGE TANKS/VESSELS	N/A	63CC-0059	40 CFR Part 63, Subpart CC	No changing attributes.
T280-140	STORAGE TANKS/VESSELS	N/A	R5112-0090	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-140	STORAGE TANKS/VESSELS	N/A	61FF-0006	40 CFR Part 61, Subpart FF	No changing attributes.
T280-140	STORAGE TANKS/VESSELS	N/A	63CC-0071	40 CFR Part 63, Subpart CC	No changing attributes.
T280-15	STORAGE TANKS/VESSELS	N/A	R5112-0090	30 TAC Chapter 115, Storage of VOCs	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
T280-15	STORAGE TANKS/VESSELS	N/A	63CC-0059	40 CFR Part 63, Subpart CC	No changing attributes.
T280-160	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-160	STORAGE TANKS/VESSELS	N/A	61FF-0015	40 CFR Part 61, Subpart FF	No changing attributes.
T280-161	STORAGE TANKS/VESSELS	N/A	R5112-0132	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-161	STORAGE TANKS/VESSELS	N/A	60KB-0072	40 CFR Part 60, Subpart Kb	No changing attributes.
T280-161	STORAGE TANKS/VESSELS	N/A	61FF-0015	40 CFR Part 61, Subpart FF	No changing attributes.
T280-16A	STORAGE TANKS/VESSELS	N/A	R5112-0021	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-16A	STORAGE TANKS/VESSELS	N/A	60Kb-0025	40 CFR Part 60, Subpart Kb	No changing attributes.
T280-16A	STORAGE TANKS/VESSELS	N/A	63CC-0059	40 CFR Part 63, Subpart CC	No changing attributes.
T280-17	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-17	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
T280-18	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-18	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
T280-181	STORAGE TANKS/VESSELS	N/A	R5112-0090	30 TAC Chapter 115, Storage of VOCs	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
T280-181	STORAGE TANKS/VESSELS	N/A	60Kb-0070	40 CFR Part 60, Subpart Kb	No changing attributes.
T280-181	STORAGE TANKS/VESSELS	N/A	63CC-0083	40 CFR Part 63, Subpart CC	No changing attributes.
T280-184	STORAGE TANKS/VESSELS	N/A	R5112-0090	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-184	STORAGE TANKS/VESSELS	N/A	63CC-0071	40 CFR Part 63, Subpart CC	No changing attributes.
T280-187	STORAGE TANKS/VESSELS	N/A	R5112-0090	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-187	STORAGE TANKS/VESSELS	N/A	63CC-0256	40 CFR Part 63, Subpart CC	No changing attributes.
T280-188	STORAGE TANKS/VESSELS	N/A	R5112-0090	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-188	STORAGE TANKS/VESSELS	N/A	60Kb-0070	40 CFR Part 60, Subpart Kb	No changing attributes.
T280-188	STORAGE TANKS/VESSELS	N/A	63CC-0083	40 CFR Part 63, Subpart CC	No changing attributes.
T280-19	STORAGE TANKS/VESSELS	N/A	R5112-0019	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-19	STORAGE TANKS/VESSELS	N/A	60Kb-0068	40 CFR Part 60, Subpart Kb	No changing attributes.
T280-19	STORAGE TANKS/VESSELS	N/A	63CC-0081	40 CFR Part 63, Subpart CC	No changing attributes.
T280-20	STORAGE TANKS/VESSELS	N/A	R5112-0019	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-20	STORAGE TANKS/VESSELS	N/A	63CC-0248	40 CFR Part 63, Subpart CC	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
T280-22	STORAGE TANKS/VESSELS	N/A	R5112-0090	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-22	STORAGE TANKS/VESSELS	N/A	63CC-0256	40 CFR Part 63, Subpart CC	No changing attributes.
T280-222	STORAGE TANKS/VESSELS	N/A	R5112-0132	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-222	STORAGE TANKS/VESSELS	N/A	60KB-0072	40 CFR Part 60, Subpart Kb	No changing attributes.
T280-222	STORAGE TANKS/VESSELS	N/A	61FF-0015	40 CFR Part 61, Subpart FF	No changing attributes.
T280-223	STORAGE TANKS/VESSELS	N/A	R5112-0132	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-223	STORAGE TANKS/VESSELS	N/A	60KB-0072	40 CFR Part 60, Subpart Kb	No changing attributes.
T280-223	STORAGE TANKS/VESSELS	N/A	61FF-0015	40 CFR Part 61, Subpart FF	No changing attributes.
T280-23	STORAGE TANKS/VESSELS	N/A	R5112-0090	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-23	STORAGE TANKS/VESSELS	N/A	63CC-0059	40 CFR Part 63, Subpart CC	No changing attributes.
T280-24	STORAGE TANKS/VESSELS	N/A	R5112-0019	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-24	STORAGE TANKS/VESSELS	N/A	63CC-0004	40 CFR Part 63, Subpart CC	No changing attributes.
T280-25	STORAGE TANKS/VESSELS	N/A	R5112-0090	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-25	STORAGE TANKS/VESSELS	N/A	60Kb-0070	40 CFR Part 60, Subpart Kb	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
T280-25	STORAGE TANKS/VESSELS	N/A	63CC-0256	40 CFR Part 63, Subpart CC	No changing attributes.
T280-26	STORAGE TANKS/VESSELS	N/A	R5112-0090	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-26	STORAGE TANKS/VESSELS	N/A	63CC-0059	40 CFR Part 63, Subpart CC	No changing attributes.
T280-269	STORAGE TANKS/VESSELS	N/A	R5112-0090	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-269	STORAGE TANKS/VESSELS	N/A	61FF-0006	40 CFR Part 61, Subpart FF	No changing attributes.
T280-269	STORAGE TANKS/VESSELS	N/A	63CC-0059	40 CFR Part 63, Subpart CC	No changing attributes.
T280-27	STORAGE TANKS/VESSELS	N/A	R5112-0090	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-27	STORAGE TANKS/VESSELS	N/A	63CC-0059	40 CFR Part 63, Subpart CC	No changing attributes.
T280-270	STORAGE TANKS/VESSELS	N/A	R5112-0090	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-270	STORAGE TANKS/VESSELS	N/A	61FF-0006	40 CFR Part 61, Subpart FF	No changing attributes.
T280-270	STORAGE TANKS/VESSELS	N/A	63CC-0059	40 CFR Part 63, Subpart CC	No changing attributes.
T280-271	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-271	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
T280-28	STORAGE TANKS/VESSELS	N/A	R5112-0019	30 TAC Chapter 115, Storage of VOCs	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
T280-28	STORAGE TANKS/VESSELS	N/A	63CC-0083	40 CFR Part 63, Subpart CC	No changing attributes.
T280-28	STORAGE TANKS/VESSELS	N/A	63G-0001	40 CFR Part 63, Subpart G	No changing attributes.
T280-29	STORAGE TANKS/VESSELS	N/A	R5112-0019	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-29	STORAGE TANKS/VESSELS	N/A	63CC-0081	40 CFR Part 63, Subpart CC	No changing attributes.
T280-29	STORAGE TANKS/VESSELS	N/A	63G-0001	40 CFR Part 63, Subpart G	No changing attributes.
T280-30	STORAGE TANKS/VESSELS	N/A	R5112-0019	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-30	STORAGE TANKS/VESSELS	N/A	61Y-0017	40 CFR Part 61, Subpart Y	No changing attributes.
T280-30	STORAGE TANKS/VESSELS	N/A	63CC-0248	40 CFR Part 63, Subpart CC	No changing attributes.
T280-3003	STORAGE TANKS/VESSELS	N/A	R5112-0006	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-3006	STORAGE TANKS/VESSELS	N/A	R5112-0006	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-3007	STORAGE TANKS/VESSELS	N/A	R5112-0006	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-3007	STORAGE TANKS/VESSELS	N/A	63EEEE-1	40 CFR Part 63, Subpart EEEE	No changing attributes.
T280-3010	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
T280-3022	STORAGE TANKS/VESSELS	N/A	R5112-0006	30 TAC Chapter 115, Storage of VOCs	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
T280-3023	STORAGE TANKS/VESSELS	N/A	R5112-0006	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-3024	STORAGE TANKS/VESSELS	N/A	R5112-0006	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-3025	STORAGE TANKS/VESSELS	N/A	R5112-0006	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-3026	STORAGE TANKS/VESSELS	N/A	R5112-0006	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-3027	STORAGE TANKS/VESSELS	N/A	R5112-0006	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-3027	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
T280-3040	STORAGE TANKS/VESSELS	N/A	R5112-0006	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-3041	STORAGE TANKS/VESSELS	N/A	R5112-0006	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-3042	STORAGE TANKS/VESSELS	N/A	R5112-0006	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-3043	STORAGE TANKS/VESSELS	N/A	R5112-0006	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-3044	STORAGE TANKS/VESSELS	N/A	R5112-0006	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-3045	STORAGE TANKS/VESSELS	N/A	R5112-0006	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-3103	STORAGE TANKS/VESSELS	N/A	R5112-0006	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-3105	STORAGE TANKS/VESSELS	N/A	R5112-0006	30 TAC Chapter 115, Storage of VOCs	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
T280-3106	STORAGE TANKS/VESSELS	N/A	R5112-0006	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-3107	STORAGE TANKS/VESSELS	N/A	R5112-0006	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-3107	STORAGE TANKS/VESSELS	N/A	63EEEE-1	40 CFR Part 63, Subpart EEEE	No changing attributes.
T280-33A	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-33A	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
T280-34	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-34	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
T280-36	STORAGE TANKS/VESSELS	N/A	R5112-0090	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-36	STORAGE TANKS/VESSELS	N/A	63CC-0256	40 CFR Part 63, Subpart CC	No changing attributes.
T280-37	STORAGE TANKS/VESSELS	N/A	R5112-0090	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-37	STORAGE TANKS/VESSELS	N/A	63CC-0256	40 CFR Part 63, Subpart CC	No changing attributes.
T280-38	STORAGE TANKS/VESSELS	N/A	R5112-0090	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-38	STORAGE TANKS/VESSELS	N/A	63CC-0256	40 CFR Part 63, Subpart CC	No changing attributes.
T280-39	STORAGE TANKS/VESSELS	N/A	R5112-0090	30 TAC Chapter 115, Storage of VOCs	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
T280-39	STORAGE TANKS/VESSELS	N/A	63CC-0256	40 CFR Part 63, Subpart CC	No changing attributes.
T280-4000	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-4000	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
T280-4001	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-4001	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
T280-4002	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-4002	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
T280-4003	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-4003	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
T280-42	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-42	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
T280-43	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-43	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
T280-44	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
T280-44	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
T280-45	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-45	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
T280-46	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-46	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
T280-47	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-47	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
T280-48	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-48	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
T280-49	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-49	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
T280-50	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-50	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
T280-501	STORAGE TANKS/VESSELS	N/A	R5112-0090	30 TAC Chapter 115, Storage of VOCs	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
T280-501	STORAGE TANKS/VESSELS	N/A	63CC-0059	40 CFR Part 63, Subpart CC	No changing attributes.
T280-502	STORAGE TANKS/VESSELS	N/A	R5112-0090	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-502	STORAGE TANKS/VESSELS	N/A	63CC-0083	40 CFR Part 63, Subpart CC	No changing attributes.
T280-503	STORAGE TANKS/VESSELS	N/A	R5112-0090	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-503	STORAGE TANKS/VESSELS	N/A	63CC-0083	40 CFR Part 63, Subpart CC	No changing attributes.
T280-504	STORAGE TANKS/VESSELS	N/A	R5112-0090	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-504	STORAGE TANKS/VESSELS	N/A	60Kb-0070	40 CFR Part 60, Subpart Kb	No changing attributes.
T280-504	STORAGE TANKS/VESSELS	N/A	63CC-0083	40 CFR Part 63, Subpart CC	No changing attributes.
T280-51	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-51	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
T280-52	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-52	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
T280-520	STORAGE TANKS/VESSELS	N/A	R5112-0019	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-520	STORAGE TANKS/VESSELS	N/A	60Kb-0068	40 CFR Part 60, Subpart Kb	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
T280-520	STORAGE TANKS/VESSELS	N/A	63CC-0004	40 CFR Part 63, Subpart CC	No changing attributes.
T280-528	STORAGE TANKS/VESSELS	N/A	R5112-0090	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-528	STORAGE TANKS/VESSELS	N/A	63CC-0256	40 CFR Part 63, Subpart CC	No changing attributes.
T280-529	STORAGE TANKS/VESSELS	N/A	R5112-0019	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-529	STORAGE TANKS/VESSELS	N/A	60Kb-0005	40 CFR Part 60, Subpart Kb	No changing attributes.
T280-529	STORAGE TANKS/VESSELS	N/A	63CC-0004	40 CFR Part 63, Subpart CC	No changing attributes.
T280-53	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-53	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
T280-530	STORAGE TANKS/VESSELS	N/A	R5112-0090	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-530	STORAGE TANKS/VESSELS	N/A	63CC-0059	40 CFR Part 63, Subpart CC	No changing attributes.
T280-531	STORAGE TANKS/VESSELS	N/A	R5112-0090	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-531	STORAGE TANKS/VESSELS	N/A	60Kb-0025	40 CFR Part 60, Subpart Kb	No changing attributes.
T280-531	STORAGE TANKS/VESSELS	N/A	63CC-0059	40 CFR Part 63, Subpart CC	No changing attributes.
T280-532	STORAGE TANKS/VESSELS	N/A	R5112-0090	30 TAC Chapter 115, Storage of VOCs	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
T280-532	STORAGE TANKS/VESSELS	N/A	63CC-0059	40 CFR Part 63, Subpart CC	No changing attributes.
T280-533	STORAGE TANKS/VESSELS	N/A	R5112-0090	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-533	STORAGE TANKS/VESSELS	N/A	63Kb-0070	40 CFR Part 60, Subpart Kb	No changing attributes.
T280-533	STORAGE TANKS/VESSELS	N/A	63CC-0256	40 CFR Part 63, Subpart CC	No changing attributes.
T280-534	STORAGE TANKS/VESSELS	N/A	R5112-0090	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-534	STORAGE TANKS/VESSELS	N/A	63CC-0256	40 CFR Part 63, Subpart CC	No changing attributes.
T280-535	STORAGE TANKS/VESSELS	N/A	R5112-0019	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-535	STORAGE TANKS/VESSELS	N/A	60Kb-0026	40 CFR Part 60, Subpart Kb	No changing attributes.
T280-535	STORAGE TANKS/VESSELS	N/A	63CC-0004	40 CFR Part 63, Subpart CC	No changing attributes.
T280-536	STORAGE TANKS/VESSELS	N/A	R5112-0090	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-536	STORAGE TANKS/VESSELS	N/A	63CC-0256	40 CFR Part 63, Subpart CC	No changing attributes.
T280-537	STORAGE TANKS/VESSELS	N/A	R5112-0090	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-537	STORAGE TANKS/VESSELS	N/A	63CC-0059	40 CFR Part 63, Subpart CC	No changing attributes.
T280-538	STORAGE TANKS/VESSELS	N/A	R5112-0090	30 TAC Chapter 115, Storage of VOCs	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
T280-538	STORAGE TANKS/VESSELS	N/A	63CC-0256	40 CFR Part 63, Subpart CC	No changing attributes.
T280-54	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-54	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
T280-55	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-55	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
T280-56	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-56	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
T280-561	STORAGE TANKS/VESSELS	N/A	R5112-0090	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-561	STORAGE TANKS/VESSELS	N/A	61FF-0006	40 CFR Part 61, Subpart FF	No changing attributes.
T280-561	STORAGE TANKS/VESSELS	N/A	63CC-0071	40 CFR Part 63, Subpart CC	No changing attributes.
T280-57	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-57	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
T280-60	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-60	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
T280-61	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-61	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
T280-63	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-63	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
T280-65	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-65	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
T280-652	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-652	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
T280-653	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-653	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
T280-66	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-66	STORAGE TANKS/VESSELS	N/A	61FF-0006	40 CFR Part 61, Subpart FF	No changing attributes.
T280-66	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
T280-67	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
T280-67	STORAGE TANKS/VESSELS	N/A	61FF-0006	40 CFR Part 61, Subpart FF	No changing attributes.
T280-67	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
T280-7	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-7	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
T280-71	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-71	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
T280-72	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-72	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
T280-73	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-73	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
T280-8	STORAGE TANKS/VESSELS	N/A	R5112-0019	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-8	STORAGE TANKS/VESSELS	N/A	63CC-0248	40 CFR Part 63, Subpart CC	No changing attributes.
T280-80	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-80	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
T280-9	STORAGE TANKS/VESSELS	N/A	R5112-0019	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-9	STORAGE TANKS/VESSELS	N/A	63CC-0248	40 CFR Part 63, Subpart CC	No changing attributes.
T280-90	STORAGE TANKS/VESSELS	N/A	R5112-0090	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-90	STORAGE TANKS/VESSELS	N/A	63CC-0256	40 CFR Part 63, Subpart CC	No changing attributes.
T280-91	STORAGE TANKS/VESSELS	N/A	R5112-0090	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-91	STORAGE TANKS/VESSELS	N/A	63CC-0256	40 CFR Part 63, Subpart CC	No changing attributes.
T280-92	STORAGE TANKS/VESSELS	N/A	R5112-0090	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-92	STORAGE TANKS/VESSELS	N/A	60Kb-0070	40 CFR Part 60, Subpart Kb	No changing attributes.
T280-92	STORAGE TANKS/VESSELS	N/A	63CC-0083	40 CFR Part 63, Subpart CC	No changing attributes.
T280-94	STORAGE TANKS/VESSELS	N/A	R5112-0090	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-94	STORAGE TANKS/VESSELS	N/A	63CC-0256	40 CFR Part 63, Subpart CC	No changing attributes.
T280-95	STORAGE TANKS/VESSELS	N/A	R5112-0090	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-95	STORAGE TANKS/VESSELS	N/A	63CC-0256	40 CFR Part 63, Subpart CC	No changing attributes.
T280-97	STORAGE TANKS/VESSELS	N/A	R5112-0090	30 TAC Chapter 115, Storage of VOCs	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
T280-97	STORAGE TANKS/VESSELS	N/A	63CC-0059	40 CFR Part 63, Subpart CC	No changing attributes.
T280-98	STORAGE TANKS/VESSELS	N/A	R5112-0090	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T280-98	STORAGE TANKS/VESSELS	N/A	63CC-0059	40 CFR Part 63, Subpart CC	No changing attributes.
TCH-2	FLARES	N/A	R1111-0001	30 TAC Chapter 111, Visible Emissions	No changing attributes.
TCH-2	FLARES	N/A	R5720-0225	30 TAC Chapter 115, HRVOC Vent Gas	No changing attributes.
TCH-2	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5720-0505	30 TAC Chapter 115, HRVOC Vent Gas	No changing attributes.
TCH-2	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121-0016	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
TCH-2	FLARES	N/A	60A-0004	40 CFR Part 60, Subpart A	No changing attributes.
TCH-2	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60Ja-163	40 CFR Part 60, Subpart Ja	No changing attributes.
TCH-2	FLARES	N/A	63A-0004	40 CFR Part 63, Subpart A	No changing attributes.
TCH-2	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	63CC-1176	40 CFR Part 63, Subpart CC	No changing attributes.
TCH-3	FLARES	N/A	R1111-0001	30 TAC Chapter 111, Visible Emissions	No changing attributes.
TCH-3	FLARES	N/A	R5720-0225	30 TAC Chapter 115, HRVOC Vent Gas	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
TCH-3	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5720-0505	30 TAC Chapter 115, HRVOC Vent Gas	No changing attributes.
TCH-3	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121-0016	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
TCH-3	FLARES	N/A	60A-0004	40 CFR Part 60, Subpart A	No changing attributes.
TCH-3	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60Ja-163	40 CFR Part 60, Subpart Ja	No changing attributes.
TCH-3	FLARES	N/A	63A-0004	40 CFR Part 63, Subpart A	No changing attributes.
TCH-3	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	63CC-1176	40 CFR Part 63, Subpart CC	No changing attributes.
TCH-4	FLARES	N/A	R1111-0001	30 TAC Chapter 111, Visible Emissions	No changing attributes.
TCH-4	FLARES	N/A	R5720-0225	30 TAC Chapter 115, HRVOC Vent Gas	No changing attributes.
TCH-4	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5720-0505	30 TAC Chapter 115, HRVOC Vent Gas	No changing attributes.
TCH-4	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121-0016	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
TCH-4	FLARES	N/A	60A-0004	40 CFR Part 60, Subpart A	No changing attributes.
TCH-4	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS	N/A	60Ja-163	40 CFR Part 60, Subpart Ja	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	SRU				
TCH-4	FLARES	N/A	63A-0004	40 CFR Part 63, Subpart A	No changing attributes.
TCH-4	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	63CC-1176	40 CFR Part 63, Subpart CC	No changing attributes.
TCH-6	FLARES	N/A	R1111-0001	30 TAC Chapter 111, Visible Emissions	No changing attributes.
TCH-6	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5720-0505	30 TAC Chapter 115, HRVOC Vent Gas	No changing attributes.
TCH-6	FLARES	N/A	R5726.0016AMOC	30 TAC Chapter 115, HRVOC Vent Gas	No changing attributes.
TCH-6	VACUUM PRODUCING SYSTEMS	N/A	R5313-0016AMOC	30 TAC Chapter 115, Unit Turn & Vac System-Pet Ref	No changing attributes.
TCH-6	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121-0016AMOC	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
TCH-6	FLARES	N/A	60A-0003	40 CFR Part 60, Subpart A	No changing attributes.
TCH-6	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60Ja-164	40 CFR Part 60, Subpart Ja	No changing attributes.
TCH-6	FLARES	N/A	63A-0003	40 CFR Part 63, Subpart A	No changing attributes.
TCH-6	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	63CC-1176	40 CFR Part 63, Subpart CC	No changing attributes.
TCH-8	FLARES	N/A	R1111-0001	30 TAC Chapter 111, Visible Emissions	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
TCH-8	FLARES	N/A	R5720-0225	30 TAC Chapter 115, HRVOC Vent Gas	No changing attributes.
TCH-8	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5720-0505	30 TAC Chapter 115, HRVOC Vent Gas	No changing attributes.
TCH-8	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121-0016	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
TCH-8	FLARES	N/A	60A-0004	40 CFR Part 60, Subpart A	No changing attributes.
TCH-8	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60Ja-163	40 CFR Part 60, Subpart Ja	No changing attributes.
TCH-8	FLARES	N/A	63A-0004	40 CFR Part 63, Subpart A	No changing attributes.
TCH-8	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	63CC-1176	40 CFR Part 63, Subpart CC	No changing attributes.
TCH-AU2	FLARES	N/A	R1111-0001	30 TAC Chapter 111, Visible Emissions	No changing attributes.
TCH-AU2	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121-0016	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
TCH-AU2	FLARES	N/A	60A-0004	40 CFR Part 60, Subpart A	No changing attributes.
TCH-AU2	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60Ja-163	40 CFR Part 60, Subpart Ja	No changing attributes.
TCH-AU2	FLARES	N/A	63A-0004	40 CFR Part 63, Subpart A	No changing attributes.
TCH-AU2	EMISSION	N/A	63G-0330	40 CFR Part 63, Subpart G	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	POINTS/STATIONARY VENTS/PROCESS VENTS				
TCH-CFHU	FLARES	N/A	R1111-0001	30 TAC Chapter 111, Visible Emissions	No changing attributes.
TCH-CFHU	FLARES	N/A	R5720-0225	30 TAC Chapter 115, HRVOC Vent Gas	No changing attributes.
TCH-CFHU	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5720-0505	30 TAC Chapter 115, HRVOC Vent Gas	No changing attributes.
TCH-CFHU	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121-0016	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
TCH-CFHU	FLARES	N/A	60A-0004	40 CFR Part 60, Subpart A	No changing attributes.
TCH-CFHU	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60Ja-163	40 CFR Part 60, Subpart Ja	No changing attributes.
TCH-CFHU	FLARES	N/A	63A-0004	40 CFR Part 63, Subpart A	No changing attributes.
TCH-CFHU	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	63CC-1176	40 CFR Part 63, Subpart CC	No changing attributes.
TCH-DDU	FLARES	N/A	R1111-0001	30 TAC Chapter 111, Visible Emissions	No changing attributes.
TCH-DDU	FLARES	N/A	R5720-0225	30 TAC Chapter 115, HRVOC Vent Gas	No changing attributes.
TCH-DDU	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5720-0505	30 TAC Chapter 115, HRVOC Vent Gas	No changing attributes.
TCH-DDU	EMISSION	N/A	R5121-0016	30 TAC Chapter 115, Vent	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	POINTS/STATIONARY VENTS/PROCESS VENTS			Gas Controls	
TCH-DDU	FLARES	N/A	60A-0004	40 CFR Part 60, Subpart A	No changing attributes.
TCH-DDU	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60Ja-163	40 CFR Part 60, Subpart Ja	No changing attributes.
TCH-DDU	FLARES	N/A	63A-0004	40 CFR Part 63, Subpart A	No changing attributes.
TCH-DDU	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	63CC-1176	40 CFR Part 63, Subpart CC	No changing attributes.
TCH-ULC	FLARES	N/A	R1111-0001	30 TAC Chapter 111, Visible Emissions	No changing attributes.
TCH-ULC	FLARES	N/A	R5720-0225	30 TAC Chapter 115, HRVOC Vent Gas	No changing attributes.
TCH-ULC	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5720-0505	30 TAC Chapter 115, HRVOC Vent Gas	No changing attributes.
TCH-ULC	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121-0016	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
TCH-ULC	FLARES	N/A	60A-0004	40 CFR Part 60, Subpart A	No changing attributes.
TCH-ULC	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60Ja-163	40 CFR Part 60, Subpart Ja	No changing attributes.
TCH-ULC	FLARES	N/A	63A-0004	40 CFR Part 63, Subpart A	No changing attributes.
TCH-ULC	EMISSION POINTS/STATIONARY	N/A	63CC-1176	40 CFR Part 63, Subpart CC	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	VENTS/PROCESS VENTS				
TDU-BH	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R1111-0112	30 TAC Chapter 111, Visible Emissions	No changing attributes.
TDU-BH	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121-0003	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
TDU-CONVEYOR	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R1111-0113	30 TAC Chapter 111, Visible Emissions	No changing attributes.
TDU-CT	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R1111-0112	30 TAC Chapter 111, Visible Emissions	No changing attributes.
TDU-DRYER	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R1111-0112	30 TAC Chapter 111, Visible Emissions	No changing attributes.
TDU-DRYER	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121-0003	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
TDU-FUG	FUGITIVE EMISSION UNITS	N/A	63EEEE-4	40 CFR Part 63, Subpart EEEE	No changing attributes.
TDU-OWS	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	R5131-0011	30 TAC Chapter 115, Water Separation	Control Device = Direct flame incinerator.
TDU-OWS	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	R5131-0012	30 TAC Chapter 115, Water Separation	Control Device = Carbon adsorption system.
TDU-OWS	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	61FF-1782	40 CFR Part 61, Subpart FF	Carbon Replacement Interval = EXHAUST IS MONITORED ON A REGULAR SCHEDULE AND

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					CARBON IS REPLACED IMMEDIATELY UPON BREAKTHROUGH, Engineering Calculations = ENGINEERING CALCULATIONS ARE USED TO DEMONSTRATE CONTROL DEVICE PERFORMANCE, Control Device Type/Operation = CARBON ADSORPTION SYSTEM NOT REGENERATING BED DIRECTLY IN DEVICE
TDU-OWS	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	61FF-1783	40 CFR Part 61, Subpart FF	Alternate Monitoring Parameters = COMPLYING WITH THE MONITORING REQUIREMENTS OF SUBPART FF, Engineering Calculations = PERFORANCE TEST IS BEING USED TO DETERMINE COMPLIANCE OF A CONTROL DEVICE, Control Device Type/Operation = THERMAL VAPOR INCINERATOR REDUCING ORGANICS BY 95 WEIGHT PERCENT OR GREATER
TDU-TO	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R1111-0112	30 TAC Chapter 111, Visible Emissions	No changing attributes.
TDU-TRANSFER	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R1111-0113	30 TAC Chapter 111, Visible Emissions	No changing attributes.
TDU-VETURI	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R1111-0112	30 TAC Chapter 111, Visible Emissions	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
TDU-VETURI	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121-0003	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
TEMPPJ16B	SRIC ENGINES	N/A	R7300-0001	30 TAC Chapter 117, Subchapter B	No changing attributes.
TEMPPJ16B	SRIC ENGINES	N/A	60IIII-001	40 CFR Part 60, Subpart IIII	No changing attributes.
TEMPPJ16B	SRIC ENGINES	N/A	63ZZZZ-0001	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
TGUF201C/D	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	63UUU-0003	40 CFR Part 63, Subpart UUU	No changing attributes.
TK-1	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
TK-10	STORAGE TANKS/VESSELS	N/A	R5112-0008	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
TK117APUMP	SRIC ENGINES	N/A	R7300-0004	30 TAC Chapter 117, Subchapter B	No changing attributes.
TK117APUMP	SRIC ENGINES	N/A	60IIII-0006	40 CFR Part 60, Subpart IIII	No changing attributes.
TK117APUMP	SRIC ENGINES	N/A	63ZZZZ-0002	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
TK-2	STORAGE TANKS/VESSELS	N/A	R5112-0008	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
TK-201	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
TK206CMP	SRIC ENGINES	N/A	R7300-0003	30 TAC Chapter 117, Subchapter B	No changing attributes.
TK206CMP	SRIC ENGINES	N/A	60IIII-0003	40 CFR Part 60, Subpart IIII	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
TK206CMP	SRIC ENGINES	N/A	63ZZZZ-0003	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
TK207CMP	SRIC ENGINES	N/A	R7300-0003	30 TAC Chapter 117, Subchapter B	No changing attributes.
TK207CMP	SRIC ENGINES	N/A	60IIII-0004	40 CFR Part 60, Subpart IIII	No changing attributes.
TK207CMP	SRIC ENGINES	N/A	63ZZZZ-0003	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
TK20PUMP	SRIC ENGINES	N/A	R7300-0005	30 TAC Chapter 117, Subchapter B	No changing attributes.
TK20PUMP	SRIC ENGINES	N/A	60IIII-0005	40 CFR Part 60, Subpart IIII	No changing attributes.
TK20PUMP	SRIC ENGINES	N/A	63ZZZZ-0001	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
TK-210F	STORAGE TANKS/VESSELS	N/A	R5112-0008	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
TK-210F	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
TK-264F	STORAGE TANKS/VESSELS	N/A	R5112-0132	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
TK-264F	STORAGE TANKS/VESSELS	N/A	60KB-0063	40 CFR Part 60, Subpart Kb	No changing attributes.
TK-329F	STORAGE TANKS/VESSELS	N/A	R5112-0132	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
TK-329F	STORAGE TANKS/VESSELS	N/A	60KB-0063	40 CFR Part 60, Subpart Kb	No changing attributes.
TK-330F	STORAGE TANKS/VESSELS	N/A	R5112-0132	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
TK-330F	STORAGE	N/A	60KB-0063	40 CFR Part 60, Subpart Kb	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	TANKS/VESSELS				
TK4000PUMP	SRIC ENGINES	N/A	R7300-0004	30 TAC Chapter 117, Subchapter B	No changing attributes.
TK4000PUMP	SRIC ENGINES	N/A	60IIII-0006	40 CFR Part 60, Subpart IIII	No changing attributes.
TK4000PUMP	SRIC ENGINES	N/A	63ZZZZ-0002	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
TK536CMPB	SRIC ENGINES	N/A	R7300-0002	30 TAC Chapter 117, Subchapter B	No changing attributes.
TK536CMPB	SRIC ENGINES	N/A	60IIII-0002	40 CFR Part 60, Subpart IIII	No changing attributes.
TK536CMPB	SRIC ENGINES	N/A	63ZZZZ-0002	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
TK-565F	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
TK-600	STORAGE TANKS/VESSELS	N/A	R5112-0132	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
TK-600	STORAGE TANKS/VESSELS	N/A	63CC-0295	40 CFR Part 63, Subpart CC	No changing attributes.
TK-601	STORAGE TANKS/VESSELS	N/A	R5112-0132	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
TK-601	STORAGE TANKS/VESSELS	N/A	63CC-0295	40 CFR Part 63, Subpart CC	No changing attributes.
TK-608F	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
TK-9	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
TK-F170	STORAGE TANKS/VESSELS	N/A	R5112-0006	30 TAC Chapter 115, Storage of VOCs	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
TK-F209	STORAGE TANKS/VESSELS	N/A	R5112-0006	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
TK-F215	STORAGE TANKS/VESSELS	N/A	R5112-0090	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
TK-F215	STORAGE TANKS/VESSELS	N/A	60KB-0124	40 CFR Part 60, Subpart Kb	No changing attributes.
TK-F215	STORAGE TANKS/VESSELS	N/A	61FF-0006	40 CFR Part 61, Subpart FF	No changing attributes.
TK-F215	STORAGE TANKS/VESSELS	N/A	63CC-0071	40 CFR Part 63, Subpart CC	No changing attributes.
TK-F216	STORAGE TANKS/VESSELS	N/A	R5112-0090	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
TK-F216	STORAGE TANKS/VESSELS	N/A	60KB-0124	40 CFR Part 60, Subpart Kb	No changing attributes.
TK-F216	STORAGE TANKS/VESSELS	N/A	61FF-0006	40 CFR Part 61, Subpart FF	No changing attributes.
TK-F216	STORAGE TANKS/VESSELS	N/A	63CC-0071	40 CFR Part 63, Subpart CC	No changing attributes.
TK-F221	STORAGE TANKS/VESSELS	N/A	R5112-0006	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
TK-F617	STORAGE TANKS/VESSELS	N/A	R5112-0006	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
TK-F620	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
TK-F620	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
TK-FUELTK	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
TK-FUELTK	STORAGE TANKS/VESSELS	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.
TK-G405	STORAGE TANKS/VESSELS	N/A	R5112-0008	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
TK-SM1001	STORAGE TANKS/VESSELS	N/A	R5112-0006	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
TNT402	STORAGE TANKS/VESSELS	N/A	R5112-0012	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
TNTGRP-1	STORAGE TANKS/VESSELS	TNT003, TNT004, TNT017, TNT151, TNT153, TNT154, TNT156, TNT165, TNT313, TNT368	R5112-0007	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
TNTGRP-2	STORAGE TANKS/VESSELS	280-4011, 280-4016, TNT022, TNT029, TNT030, TNT037, TNT052, TNT053, TNT054, TNT058, TNT059, TNT078, TNT079, TNT081, TNT082, TNT083, TNT084, TNT085, TNT087, TNT088, TNT090, TNT094, TNT095, TNT096, TNT131, TNT132, TNT133, TNT140, TNT144, TNT150, TNT155, TNT157, TNT161, TNT162, TNT164, TNT166, TNT167, TNT168,	R5112-0007	30 TAC Chapter 115, Storage of VOCs	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
		TNT171, TNT172, TNT173, TNT175, TNT176, TNT177, TNT178, TNT179, TNT181, TNT182, TNT183, TNT184, TNT185, TNT186, TNT187, TNT189, TNT190, TNT191, TNT192, TNT194, TNT195, TNT196, TNT197, TNT210, TNT211, TNT212, TNT214, TNT224, TNT227, TNT252, TNT257, TNT332, TNT339, TNT362, TNT363, TNT367, TNT374, TNT375, TNT376, TNT388, TNT389, TNT394, TNT395, TNT398, TNT399, TNT405, TNT406, TNT423, TNT430, TNT432, TNT433, TNT434, TNT441, TNT442, TNT461, TNT462, TNT463			
TOTE 9272A	STORAGE TANKS/VESSELS	N/A	R5112-0006	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
TO-WWTP	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R1111-0112	30 TAC Chapter 111, Visible Emissions	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
TO-WWTP	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121-0019	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
TO-WWTP	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	63CC-1272	40 CFR Part 63, Subpart CC	No changing attributes.
UF4-413F	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	R5131-0010	30 TAC Chapter 115, Water Separation	No changing attributes.
UF4-413F	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	61FF-1733	40 CFR Part 61, Subpart FF	No changing attributes.
ULC-100B	PROCESS HEATERS/FURNACES	N/A	R7300-1086	30 TAC Chapter 117, Subchapter B	No changing attributes.
ULC-100B	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.
ULC-100B	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
ULC-101B	PROCESS HEATERS/FURNACES	N/A	R7300-1086	30 TAC Chapter 117, Subchapter B	No changing attributes.
ULC-101B	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.
ULC-101B	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
ULC-102B	PROCESS HEATERS/FURNACES	N/A	R7300-1086	30 TAC Chapter 117, Subchapter B	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
ULC-102B	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.
ULC-102B	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
ULC-103B	PROCESS HEATERS/FURNACES	N/A	R7300-1086	30 TAC Chapter 117, Subchapter B	No changing attributes.
ULC-103B	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.
ULC-103B	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
ULC-104BA	PROCESS HEATERS/FURNACES	N/A	R7300-1097	30 TAC Chapter 117, Subchapter B	No changing attributes.
ULC-104BA	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.
ULC-104BA	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
ULC-104BB	PROCESS HEATERS/FURNACES	N/A	R7300-1097	30 TAC Chapter 117, Subchapter B	No changing attributes.
ULC-104BB	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.
ULC-104BB	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
ULC-105BA	PROCESS HEATERS/FURNACES	N/A	R7300-1086	30 TAC Chapter 117, Subchapter B	No changing attributes.
ULC-105BA	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.
ULC-105BA	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
ULC-105BB	PROCESS HEATERS/FURNACES	N/A	R7300-1086	30 TAC Chapter 117, Subchapter B	No changing attributes.
ULC-105BB	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.
ULC-105BB	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
ULC-127FA	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	R5131-0010	30 TAC Chapter 115, Water Separation	No changing attributes.
ULC-127FA	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	61FF-1733	40 CFR Part 61, Subpart FF	No changing attributes.
ULC-143F	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	R5131-0010	30 TAC Chapter 115, Water Separation	No changing attributes.
ULC-143F	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	61FF-1733	40 CFR Part 61, Subpart FF	No changing attributes.
ULCARU-SEP4	VOLATILE ORGANIC COMPOUND WATER	N/A	R5131-0010	30 TAC Chapter 115, Water Separation	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	SEPARATORS				
ULCARU-SEP4	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	61FF-1781	40 CFR Part 61, Subpart FF	No changing attributes.
ULC-CTWR	INDUSTRIAL PROCESS COOLING TOWERS	N/A	R5760-0206	30 TAC Chapter 115, HRVOC Cooling Towers	No changing attributes.
ULC-CTWR	INDUSTRIAL PROCESS COOLING TOWERS	N/A	63CC-002	40 CFR Part 63, Subpart CC	No changing attributes.
ULC-FUG1	FUGITIVE EMISSION UNITS	N/A	60GGGa-001	40 CFR Part 60, Subpart GGGa	No changing attributes.
ULC-SEP7	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	R5131-0010	30 TAC Chapter 115, Water Separation	No changing attributes.
ULC-SEP7	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	61FF-1781	40 CFR Part 61, Subpart FF	No changing attributes.
UU3	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	63UUU-0004	40 CFR Part 63, Subpart UUU	No changing attributes.
UU3 BYPASS	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	63UUU-0005	40 CFR Part 63, Subpart UUU	No changing attributes.
UU3-301BA	PROCESS HEATERS/FURNACES	N/A	R7300-1289	30 TAC Chapter 117, Subchapter B	No changing attributes.
UU3-301BA	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
UU3-301BA	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
UU3-301BB	PROCESS HEATERS/FURNACES	N/A	R7300-1289	30 TAC Chapter 117, Subchapter B	No changing attributes.
UU3-301BB	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.
UU3-301BB	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
UU3-301BC	PROCESS HEATERS/FURNACES	N/A	R7300-1289	30 TAC Chapter 117, Subchapter B	No changing attributes.
UU3-301BC	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.
UU3-301BC	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
UU3-301BD	PROCESS HEATERS/FURNACES	N/A	R7300-1289	30 TAC Chapter 117, Subchapter B	No changing attributes.
UU3-301BD	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.
UU3-301BD	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
UU3-302BA	PROCESS HEATERS/FURNACES	N/A	R7300-1289	30 TAC Chapter 117, Subchapter B	No changing attributes.
UU3-302BA	FCCU CAT REGEN/FUEL	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	GAS COMBUSTION/CLAUS SRU				
UU3-302BA	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
UU3-302BB	PROCESS HEATERS/FURNACES	N/A	R7300-1289	30 TAC Chapter 117, Subchapter B	No changing attributes.
UU3-302BB	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.
UU3-302BB	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
UU3-302BC	PROCESS HEATERS/FURNACES	N/A	R7300-1097	30 TAC Chapter 117, Subchapter B	No changing attributes.
UU3-302BC	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.
UU3-302BC	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
UU3-306B	PROCESS HEATERS/FURNACES	N/A	R7300-1493	30 TAC Chapter 117, Subchapter B	No changing attributes.
UU3-306B	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.
UU3-306B	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
UU3-307BA	PROCESS HEATERS/FURNACES	N/A	R7300-1018	30 TAC Chapter 117, Subchapter B	No changing attributes.
UU3-307BA	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.
UU3-307BA	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
UU3-307BB	PROCESS HEATERS/FURNACES	N/A	R7300-1018	30 TAC Chapter 117, Subchapter B	No changing attributes.
UU3-307BB	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.
UU3-307BB	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
UU3-308B	PROCESS HEATERS/FURNACES	N/A	R7300-1289	30 TAC Chapter 117, Subchapter B	No changing attributes.
UU3-308B	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.
UU3-308B	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
UU3-309B	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	R7300-0001	30 TAC Chapter 117, Subchapter B	No changing attributes.
UU3-309B	PROCESS HEATERS/FURNACES	N/A	R7300-0001	30 TAC Chapter 117, Subchapter B	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
UU3-309B	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	60Db-0001	40 CFR Part 60, Subpart Db	No changing attributes.
UU3-309B	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60Ja-0001	40 CFR Part 60, Subpart Ja	No changing attributes.
UU3-309B	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
UU3-310BA	PROCESS HEATERS/FURNACES	N/A	R7300-0001	30 TAC Chapter 117, Subchapter B	No changing attributes.
UU3-310BA	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60Ja-0001	40 CFR Part 60, Subpart Ja	No changing attributes.
UU3-310BA	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
UU3-310BB	PROCESS HEATERS/FURNACES	N/A	R7300-0001	30 TAC Chapter 117, Subchapter B	No changing attributes.
UU3-310BB	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60Ja-0001	40 CFR Part 60, Subpart Ja	No changing attributes.
UU3-310BB	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
UU3-311BA	PROCESS HEATERS/FURNACES	N/A	R7300-0001	30 TAC Chapter 117, Subchapter B	No changing attributes.
UU3-311BA	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS	N/A	60Ja-0001	40 CFR Part 60, Subpart Ja	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	SRU				
UU3-311BA	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
UU3-311BB	PROCESS HEATERS/FURNACES	N/A	R7300-0001	30 TAC Chapter 117, Subchapter B	No changing attributes.
UU3-311BB	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60Ja-0001	40 CFR Part 60, Subpart Ja	No changing attributes.
UU3-311BB	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
UU3-312BA	PROCESS HEATERS/FURNACES	N/A	R7300-0001	30 TAC Chapter 117, Subchapter B	No changing attributes.
UU3-312BA	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60Ja-0001	40 CFR Part 60, Subpart Ja	No changing attributes.
UU3-312BA	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
UU3-312BB	PROCESS HEATERS/FURNACES	N/A	R7300-0001	30 TAC Chapter 117, Subchapter B	No changing attributes.
UU3-312BB	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60Ja-0001	40 CFR Part 60, Subpart Ja	No changing attributes.
UU3-312BB	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
UU3-312BC	PROCESS HEATERS/FURNACES	N/A	R7300-0001	30 TAC Chapter 117, Subchapter B	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
UU3-312BC	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60Ja-0001	40 CFR Part 60, Subpart Ja	No changing attributes.
UU3-312BC	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
UU3-313B	PROCESS HEATERS/FURNACES	N/A	R7300-0002	30 TAC Chapter 117, Subchapter B	No changing attributes.
UU3-313B	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60Ja-0002	40 CFR Part 60, Subpart Ja	No changing attributes.
UU3-313B	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
UU3-CT	INDUSTRIAL PROCESS COOLING TOWERS	N/A	R5760-0025	30 TAC Chapter 115, HRVOC Cooling Towers	No changing attributes.
UU3-CT	INDUSTRIAL PROCESS COOLING TOWERS	N/A	63CC-002	40 CFR Part 63, Subpart CC	No changing attributes.
UU3-FUG1	FUGITIVE EMISSION UNITS	N/A	60GGGa-01	40 CFR Part 60, Subpart GGGa	No changing attributes.
UU3-SEP12	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	R5131-0010	30 TAC Chapter 115, Water Separation	No changing attributes.
UU3-SEP12	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	61FF-1781	40 CFR Part 61, Subpart FF	No changing attributes.
UU3W-OWS	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	R5131-0010	30 TAC Chapter 115, Water Separation	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
UU3W-OWS	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	61FF-1781	40 CFR Part 61, Subpart FF	No changing attributes.
UU4	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	63UUU-0004	40 CFR Part 63, Subpart UUU	No changing attributes.
UU4 BYPASS	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	63UUU-0005	40 CFR Part 63, Subpart UUU	No changing attributes.
UU4-B401A	PROCESS HEATERS/FURNACES	N/A	R7300-1493	30 TAC Chapter 117, Subchapter B	No changing attributes.
UU4-B401A	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.
UU4-B401A	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
UU4-B401B	PROCESS HEATERS/FURNACES	N/A	R7300-1493	30 TAC Chapter 117, Subchapter B	No changing attributes.
UU4-B401B	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.
UU4-B401B	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
UU4-B402A	PROCESS HEATERS/FURNACES	N/A	R7300-1289	30 TAC Chapter 117, Subchapter B	No changing attributes.
UU4-B402A	FCCU CAT REGEN/FUEL	N/A	60J-0008	40 CFR Part 60, Subpart J	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	GAS COMBUSTION/CLAUS SRU				
UU4-B402A	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
UU4-B402B	PROCESS HEATERS/FURNACES	N/A	R7300-1289	30 TAC Chapter 117, Subchapter B	No changing attributes.
UU4-B402B	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.
UU4-B402B	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
UU4-B402C	PROCESS HEATERS/FURNACES	N/A	R7300-1097	30 TAC Chapter 117, Subchapter B	No changing attributes.
UU4-B402C	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.
UU4-B402C	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
UU4-B404	PROCESS HEATERS/FURNACES	N/A	R7300-1018	30 TAC Chapter 117, Subchapter B	No changing attributes.
UU4-B404	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.
UU4-B404	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
UU4-B405	PROCESS HEATERS/FURNACES	N/A	R7300-1493	30 TAC Chapter 117, Subchapter B	No changing attributes.
UU4-B405	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.
UU4-B405	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
UU4-B406	PROCESS HEATERS/FURNACES	N/A	R7300-1289	30 TAC Chapter 117, Subchapter B	No changing attributes.
UU4-B406	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-0025	40 CFR Part 60, Subpart J	No changing attributes.
UU4-B406	PROCESS HEATERS/FURNACES	N/A	63DDDDD-1	40 CFR Part 63, Subpart DDDDD	No changing attributes.
UU4-CTW	INDUSTRIAL PROCESS COOLING TOWERS	N/A	R5760-0025	30 TAC Chapter 115, HRVOC Cooling Towers	No changing attributes.
UU4-CTW	INDUSTRIAL PROCESS COOLING TOWERS	N/A	63CC-002	40 CFR Part 63, Subpart CC	No changing attributes.
UU4-FUG1	FUGITIVE EMISSION UNITS	N/A	60GGGa-001	40 CFR Part 60, Subpart GGGa	No changing attributes.
UU4-SEP1	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	R5131-0010	30 TAC Chapter 115, Water Separation	No changing attributes.
UU4-SEP1	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	61FF-1781	40 CFR Part 61, Subpart FF	No changing attributes.
VEH GAS TK	STORAGE	N/A	63CC-0003	40 CFR Part 63, Subpart CC	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	TANKS/VESSELS				
WIFCMP	SRIC ENGINES	N/A	R7300-0003	30 TAC Chapter 117, Subchapter B	No changing attributes.
WIFCMP	SRIC ENGINES	N/A	60IIII-0003	40 CFR Part 60, Subpart IIII	No changing attributes.
WIFCMP	SRIC ENGINES	N/A	63ZZZZ-0003	40 CFR Part 63, Subpart ZZZZ	No changing attributes.

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
ALK2-CTWR	EU	R5760-0206	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Cooling Towers	§ 115.767(6) § 115.764(a)(1) § 115.766(i)	All sites that are subject to this division and that are located in the Houston/ Galveston/Brazoria area as defined in § 115.10, excluding Harris County, are exempt from § 115.761(b) and (c)(2), except as provided in § 115.769(a)(3).	§ 115.764(a)(1) § 115.764(a)(3) [G]§ 115.764(a)(6) § 115.764(c)	§ 115.766(a)(1) § 115.766(a)(2) § 115.766(a)(3) § 115.766(a)(5) § 115.766(a)(6) § 115.766(c) [G]§ 115.766(g) § 115.766(i)(1)	§ 115.766(i)(2)
ALK2-CTWR	EU	63CC-002	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.654(a) § 63.640(h)(6)	Except as specified in paragraph (b) of this section, the owner or operator of a heat exchange system that meets the criteria in §63.640(c)(8) must comply with the requirements of paragraphs (c) through (g) of this section.	§ 63.642(d)(1) § 63.642(d)(3) § 63.642(d)(4) [G]§ 63.654(c) [G]§ 63.654(d) § 63.654(e) [G]§ 63.654(f) [G]§ 63.654(g)	§ 63.642(e) § 63.655(h)(1) [G]§ 63.655(i)(4) § 63.655(i)(5)	§ 63.642(d)(2) § 63.642(f) § 63.655(f) § 63.655(f)(1)(vi) § 63.655(f)(4) § 63.655(g) [G]§ 63.655(g)(9) § 63.655(h)(1)
ALK3-CTWR	EU	R5760-0206	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Cooling Towers	§ 115.767(6) § 115.764(a)(1) § 115.766(i)	All sites that are subject to this division and that are located in the Houston/ Galveston/Brazoria area as defined in § 115.10, excluding Harris County, are exempt from § 115.761(b) and (c)(2), except as provided in § 115.769(a)(3).	§ 115.764(a)(1) § 115.764(a)(3) [G]§ 115.764(a)(6) § 115.764(c)	§ 115.766(a)(1) § 115.766(a)(2) § 115.766(a)(3) § 115.766(a)(5) § 115.766(a)(6) § 115.766(c) [G]§ 115.766(g) § 115.766(i)(1)	§ 115.766(i)(2)
ALK3-CTWR	EU	63CC-002	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.654(a) § 63.640(h)(6)	Except as specified in paragraph (b) of this section, the owner or operator of a heat exchange system that meets the criteria in §63.640(c)(8) must comply with the requirements of paragraphs	§ 63.642(d)(1) § 63.642(d)(3) § 63.642(d)(4) [G]§ 63.654(c) [G]§ 63.654(d) § 63.654(e) [G]§ 63.654(f) [G]§ 63.654(g)	§ 63.642(e) § 63.655(h)(1) [G]§ 63.655(i)(4) § 63.655(i)(5)	§ 63.642(d)(2) § 63.642(f) § 63.655(f) § 63.655(f)(1)(vi) § 63.655(f)(4) § 63.655(g) [G]§ 63.655(g)(9) § 63.655(h)(1)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						(c) through (g) of this section.			
ALK3DEBCT	EU	63CC-002	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.654(a) § 63.640(h)(6)	Except as specified in paragraph (b) of this section, the owner or operator of a heat exchange system that meets the criteria in §63.640(c)(8) must comply with the requirements of paragraphs (c) through (g) of this section.	§ 63.642(d)(1) § 63.642(d)(3) § 63.642(d)(4) [G]§ 63.654(c) [G]§ 63.654(d) § 63.654(e) [G]§ 63.654(f) [G]§ 63.654(g)	§ 63.642(e) § 63.655(h)(1) [G]§ 63.655(i)(4) § 63.655(i)(5)	§ 63.642(d)(2) § 63.642(f) § 63.655(f) § 63.655(f)(1)(vi) § 63.655(f)(4) § 63.655(g) [G]§ 63.655(g)(9) § 63.655(h)(1)
ALK3-F1001	EU	R7300-1289	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(2) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) § 117.340(c)(3)(D) [G]§ 117.340(c)(3)(E) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							[G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)		
ALK3-F1001	EU	R7300-1289	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(e) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.8120(1)(A)		
ALK3-F1001	EU	60Ja-165		40 CFR Part 60, Subpart Ja	§ 60.100a(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 60, Subpart Ja
ALK3-F1001	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
ALKY2-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(d)	Comply with the requirements as stated in §60.482-1(d) for equipment in vacuum service.	None	§ 60.486(e) § 60.486(e)(1) § 60.486(e)(5)	None
ALKY2-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-2 [G]§ 60.482-9	Comply with the requirements as stated in §60.482-2 for pumps in light-liquid service.	[G]§ 60.482-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d) § 60.593(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
ALKY2-FUG	EU	60GGG-	VOC	40 CFR Part 60,	§ 60.593(b)(1)	Compressors in hydrogen	§ 60.593(b)(2)	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		0001		Subpart GGG		service are exempt from the requirements of §60.592 if an owner or operator demonstrates that a compressor is in hydrogen service.	[G]§ 60.593(b)(3)		
ALKY2-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-3 [G]§ 60.482-9	Comply with the requirements as stated in §60.482-3 for compressors.	[G]§ 60.482-3 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
ALKY2-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-4 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-4 for pressure relief devices in gas/vapor service.	[G]§ 60.482-4 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(3) [G]§ 60.486(e)(4) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
ALKY2-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-5 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-5 for sampling connection systems.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
ALKY2-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-6 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-6 for open-ended valves and lines.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
ALKY2-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b)	Comply with the requirements in as stated in §60.482-7 for valves in	[G]§ 60.482-7 [G]§ 60.483-1 [G]§ 60.483-2	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 60.482-7 [G]§ 60.482-9 [G]§ 60.483-1 [G]§ 60.483-2 § 60.592(b)	gas/vapor or light-liquid service.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d) § 60.593(d)	§ 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) [G]§ 60.486(g) § 60.486(j) § 60.592(e)	§ 60.487(d) § 60.487(e) § 60.592(e)
ALKY2-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for pumps in heavy-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
ALKY2-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) § 60.482-10(b) § 60.482-10(e) § 60.482-10(m)	Comply with the requirements in as stated in §60.482-10 for vapor recovery devices.	§ 60.485(a) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
ALKY2-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.18 § 60.482-1(a) § 60.482-1(b) § 60.482-10(d) § 60.482-10(e) § 60.482-10(m)	Comply with the requirements in as stated in §60.482-10 for flares.	§ 60.485(a) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) [G]§ 60.485(g) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
ALKY2-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) § 60.482-10(e) [G]§ 60.482-10(g) § 60.482-10(h) § 60.482-10(m)	Comply with the requirements in as stated in §60.482-10 for closed-vent systems.	[G]§ 60.482-10(f) § 60.482-10(i) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.482-10(j) [G]§ 60.482-10(k) [G]§ 60.482-10(l) [G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
ALKY2-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for valves in heavy-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
ALKY2-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for flanges or other connectors.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
ALKY2-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for pressure relief devices in light-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
ALKY3-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(d)	Comply with the requirements as stated in §60.482-1(d) for equipment in vacuum service.	None	§ 60.486(e) § 60.486(e)(1) § 60.486(e)(5)	None
ALKY3-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-2 [G]§ 60.482-9	Comply with the requirements as stated in §60.482-2 for pumps in light-liquid service.	[G]§ 60.482-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d) § 60.593(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
ALKY3-FUG	EU	60GGG-	VOC	40 CFR Part 60,	§ 60.593(b)(1)	Compressors in hydrogen	§ 60.593(b)(2)	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		0001		Subpart GGG		service are exempt from the requirements of §60.592 if an owner or operator demonstrates that a compressor is in hydrogen service.	[G]§ 60.593(b)(3)		
ALKY3-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-3 [G]§ 60.482-9	Comply with the requirements as stated in §60.482-3 for compressors.	[G]§ 60.482-3 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
ALKY3-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-4 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-4 for pressure relief devices in gas/vapor service.	[G]§ 60.482-4 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(3) [G]§ 60.486(e)(4) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
ALKY3-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-5 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-5 for sampling connection systems.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
ALKY3-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-6 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-6 for open-ended valves and lines.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
ALKY3-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b)	Comply with the requirements in as stated in §60.482-7 for valves in	[G]§ 60.482-7 [G]§ 60.483-1 [G]§ 60.483-2	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 60.482-7 [G]§ 60.482-9 [G]§ 60.483-1 [G]§ 60.483-2 § 60.592(b)	gas/vapor or light-liquid service.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d) § 60.593(d)	§ 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) [G]§ 60.486(g) § 60.486(j) § 60.592(e)	§ 60.487(d) § 60.487(e) § 60.592(e)
ALKY3-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for pumps in heavy-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
ALKY3-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) § 60.482-10(b) § 60.482-10(e) § 60.482-10(m)	Comply with the requirements in as stated in §60.482-10 for vapor recovery devices.	§ 60.485(a) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
ALKY3-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.18 § 60.482-1(a) § 60.482-1(b) § 60.482-10(d) § 60.482-10(e) § 60.482-10(m)	Comply with the requirements in as stated in §60.482-10 for flares.	§ 60.485(a) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) [G]§ 60.485(g) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
ALKY3-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) § 60.482-10(e) [G]§ 60.482-10(g) § 60.482-10(h) § 60.482-10(m)	Comply with the requirements in as stated in §60.482-10 for closed-vent systems.	[G]§ 60.482-10(f) § 60.482-10(i) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.482-10(j) [G]§ 60.482-10(k) [G]§ 60.482-10(l) [G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
ALKY3-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for valves in heavy-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
ALKY3-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for flanges or other connectors.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
ALKY3-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for pressure relief devices in light-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
API3CD-SEP	EU	R5131-0005	VOC	30 TAC Chapter 115, Water Separation	§ 115.132(a)(2)	VOC water separator compartments must have a floating roof or internal-floating cover resting on the surface with closure seals. Gauging and sampling devices shall be vapor-tight except during use.	[G]§ 115.135(a) § 115.136(a)(3) § 115.136(a)(4) ** See Periodic Monitoring Summary	§ 115.136(a)(3) § 115.136(a)(4)	None
API3CD-SEP	EU	R5131-0006	VOC	30 TAC Chapter 115, Water Separation	§ 115.132(a)(3) § 115.131(a)	VOC water separator compartments must be equipped with a vapor recovery system which satisfies the provisions of §115.131(a) of this title.	[G]§ 115.135(a) § 115.136(a)(2) § 115.136(a)(2)(C) § 115.136(a)(3) § 115.136(a)(4)	§ 115.136(a)(2) § 115.136(a)(2)(C) § 115.136(a)(3) § 115.136(a)(4)	None
API3CD-SEP	EU	61FF-1780	Benzene	40 CFR Part 61,	§ 61.347(a)(1)	Install, operate, and	§ 61.347(a)(1)(i)(A)	§ 61.349(a)(1)(ii)	§ 61.357(d)(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Subpart FF	§ 61.347(a)(1)(i)(A) § 61.347(a)(1)(i)(C) § 61.347(a)(1)(i)(C)(1) § 61.347(a)(1)(i)(C)(2) § 61.347(a)(1)(i)(C)(3) § 61.347(b) § 61.347(c) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the oil-water separator to a control device.	§ 61.347(a)(1)(i)(C)(2) § 61.347(a)(1)(i)(C)(3) § 61.347(b) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(d) § 61.354(f)(1) § 61.354(g) [G]§ 61.355(h)	§ 61.354(g) § 61.356(d) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i) § 61.356(m)	§ 61.357(d)(7)(v)
ARU-619FA	EU	R5131-0010	VOC	30 TAC Chapter 115, Water Separation	§ 115.132(a)(3) § 115.131(a)	VOC water separator compartments must be equipped with a vapor recovery system which satisfies the provisions of §115.131(a) of this title.	[G]§ 115.135(a) § 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	§ 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	None
ARU-619FA	EU	61FF-1733	Benzene	40 CFR Part 61, Subpart FF	§ 61.347(a)(1) § 60.18 § 61.347(a)(1)(i)(A) § 61.347(a)(1)(i)(B) § 61.347(b) § 61.347(c) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(b) § 61.349(e)	Install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the oil-water separator to a control device.	§ 60.18(f)(2) § 61.347(a)(1)(i)(A) § 61.347(b) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(c) § 61.354(c)(3) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.349(a)(1)(ii) § 61.354(c) § 61.354(c)(3) § 61.356(d) § 61.356(f) § 61.356(f)(1) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i) § 61.356(j)(7)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(F)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 61.349(f) § 61.349(g)				
ARU-FUG1	EU	60GGGa-01	VOC	40 CFR Part 60, Subpart GGGa	[G]§ 60.590a(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 60, Subpart GGGa
ARU-SEP	EU	R5131-0010	VOC	30 TAC Chapter 115, Water Separation	§ 115.132(a)(3) § 115.131(a)	VOC water separator compartments must be equipped with a vapor recovery system which satisfies the provisions of §115.131(a) of this title.	[G]§ 115.135(a) § 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	§ 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	None
ARU-SEP	EU	61FF-1781	Benzene	40 CFR Part 61, Subpart FF	§ 61.347(a)(1) § 61.347(a)(1)(i)(A) § 61.347(a)(1)(i)(B) § 61.347(b) § 61.347(c) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	Install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the oil-water separator to a control device.	§ 61.347(a)(1)(i)(A) § 61.347(b) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.349(a)(1)(ii) § 61.356(d) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i)	None
AU2-B601	EU	R7300-1493	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i)	An owner or operator may not use the alternative methods specified in §§	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b)	§ 117.345(a) § 117.345(f) § 117.345(f)(2)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	§ 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(2) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) § 117.340(c)(3)(D) [G]§ 117.340(c)(3)(E) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)	[G]§ 117.345(f)(2)(C) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	[G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
AU2-B601	EU	R7300-1493	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(e) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)	§ 117.8100(a)(5)(C)	§ 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
AU2-B601	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
AU2-B601	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63,	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					specification requirements of 40 CFR Part 63, Subpart DDDDD		DDDDD	Subpart DDDDD	
AU2-B621A	EU	R7300-1289	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(2) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) § 117.340(c)(3)(D) [G]§ 117.340(c)(3)(E) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
AU2-B621A	EU	R7300-1289	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(e) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
AU2-B621A	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						mg/dscm (0.10 gr/dscf).			
AU2-B621A	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
AU2-B621B	EU	R7300-1289	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(2) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) § 117.340(c)(3)(D) [G]§ 117.340(c)(3)(E) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)		
AU2-B621B	EU	R7300-1289	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(e) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
AU2-B621B	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
AU2-B621B	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
AU2-CTWR	EU	63CC-002	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.654(a) § 63.640(h)(6)	Except as specified in paragraph (b) of this section, the owner or operator of a heat exchange system that meets the criteria in §63.640(c)(8) must comply with the requirements of paragraphs (c) through (g) of this section.	§ 63.642(d)(1) § 63.642(d)(3) § 63.642(d)(4) [G]§ 63.654(c) [G]§ 63.654(d) § 63.654(e) [G]§ 63.654(f) [G]§ 63.654(g)	§ 63.642(e) § 63.655(h)(1) [G]§ 63.655(i)(4) § 63.655(i)(5)	§ 63.642(d)(2) § 63.642(f) § 63.655(f) § 63.655(f)(1)(vi) § 63.655(f)(4) § 63.655(g) [G]§ 63.655(g)(9) § 63.655(h)(1)
AU2-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(6)	Components at a petroleum refinery or synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process, that contact a process fluid that contains less than 10% VOC by weight and components at a natural gas/gasoline processing	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						operation that contact a process fluid that contains less than 1.0% VOC by weight are exempt from the requirements of this division except §115.356(3)(C) of this title.			
AU2-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(5)	Reciprocating compressors and positive displacement pumps used in natural gas/gasoline processing operations are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
AU2-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(10)	Instrumentation systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet 40 CFR §63.169 (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
AU2-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(11)	Sampling connection systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet the requirements of 40 CFR §63.166(a) and (b) (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
AU2-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(13)	Components/systems that contact a process fluid containing VOC having a true vapor pressure equal to	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						or less than 0.002 psia at 68 degrees Fahrenheit are exempt from the requirements of this division except §115.356(3)(C) of this title.			
AU2-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(2) § 115.352(9)	Each pressure relief valve equipped with a rupture disk must comply with §115.352(9) and §115.356(3)(C).	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
AU2-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.353(a) § 115.353(b) § 115.910	For all affected persons in the Beaumont-Port Arthur, Dallas-Fort Worth, El Paso, and Houston-Galveston areas, as defined in §115.10, any alternate methods of demonstrating and documenting continuous compliance with the applicable control requirements or exemption criteria in this division may be approved by the executive director in accordance with §115.910 if emission reductions are demonstrated to be substantially equivalent.	None	None	None
AU2-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(C) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii)	No component shall be allowed to have a VOC leak, for more than 15 days, after discovery. If the owner or operator elects to use the alternative work practice in §115.358 of this title, any leak detected as defined in §115.358 of this title,	§ 115.354(1) § 115.354(11) § 115.354(13)(A) § 115.354(13)(B) § 115.354(13)(C) § 115.354(13)(D) § 115.354(13)(E) § 115.354(13)(F) § 115.354(4)	§ 115.352(7) § 115.354(13)(D) § 115.354(13)(E) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B)	[G]§ 115.358(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(2)(C)(iii) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.352(8) § 115.357(8) § 115.358(c)(1) [G]§ 115.358(h)	including any leak detected using the alternative work practice on a component that is subject to the requirements of this division but not specifically selected for alternative work practice monitoring.	§ 115.354(5) § 115.354(9) [G]§ 115.355 § 115.358(c)(2) § 115.358(d) [G]§ 115.358(e) § 115.358(f)	[G]§ 115.356(3)(C) [G]§ 115.356(4) § 115.356(5)	
AU2-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7) § 115.357(1)	No process drains shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
AU2-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7)	No process drains shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(5)	None
AU2-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2)	No pressure relief valves shall be allowed to have a VOC leak, for more than 15 days after discovery, which	§ 115.354(1) § 115.354(2) § 115.354(4) § 115.354(5)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2)	[G]§ 115.354(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(9) § 115.357(1) § 115.357(8) § 115.357(9)	exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	
AU2-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(9) § 115.357(12) § 115.357(8) § 115.357(9)	No pressure relief valves shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
AU2-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(8) § 115.357(9)	No open-ended valves or lines shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
AU2-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet.	§ 115.352(1)(A) § 115.352(1)	No open-ended valves or lines shall be allowed to	§ 115.354(1) § 115.354(10)	§ 115.352(7) § 115.354(10)	[G]§ 115.354(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Refinery & Petrochemicals	§ 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8) § 115.357(9)	have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355	§ 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	
AU2-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(8) § 115.357(9)	No valves shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
AU2-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12)	No valves shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.357(8) § 115.357(9)				
AU2-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(8) § 115.357(1) § 115.357(12) § 115.357(8)	No flanges or other connectors shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
AU2-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(8) § 115.357(12) § 115.357(8)	No flanges or other connectors shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
AU2-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(7) § 115.357(1)	No agitators shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.357(12) § 115.357(8)				
AU2-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(7) § 115.357(1) § 115.357(12) § 115.357(8)	No agitators shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
AU2-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(7) § 115.357(12) § 115.357(8)	No agitators shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
AU2-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii)	No compressor seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(3) § 115.352(5) § 115.352(7) § 115.357(3) § 115.357(8)	or exuding of process fluid based on sight, smell, or sound.			
AU2-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(4) § 115.357(8)	No compressor seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None
AU2-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1) § 115.357(8)	No compressor seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None
AU2-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A)	No compressor seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(9) [G]§ 115.355	§ 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	
AU2-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(4) § 115.357(8)	No pump seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None
AU2-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1) § 115.357(8)	No pump seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None
AU2-FUG	EU	R5352-	VOC	30 TAC Chapter	§ 115.352(1)(B)	No pump seals shall be	§ 115.354(1)	§ 115.352(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		ALL		115, Pet. Refinery & Petrochemicals	§ 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	
AU2-FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	§ 63.162(e) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h)	Equipment that is in organic HAP service less than 300 hours per year is excluded from the requirements of §§63.163 - 63.174 and §63.178 if it is identified as required in §63.181(j).	[G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(i) § 63.181(j)	[G]§ 63.182(a) [G]§ 63.182(b)
AU2-FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.164 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Compressors. §63.164(a)-(i)	[G]§ 63.164 [G]§ 63.180(b) [G]§ 63.180(c) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(f)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
AU2-FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.165 § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Pressure relief device in gas/vapor service. §63.165(a)-(d)	[G]§ 63.165 [G]§ 63.180(b) [G]§ 63.180(c) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(f)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
AU2-FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.166 § 63.162(a) § 63.162(c) [G]§ 63.162(g)	Standards: Sampling connection systems. §63.166(a)-(c)	[G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.162(h) [G]§ 63.171				§ 63.182(c)(4) [G]§ 63.182(d)
AU2-FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Pumps in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
AU2-FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Valves in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
AU2-FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Connectors in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
AU2-FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Agitators in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
AU2-FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h)	Standards: Instrumentation systems. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 63.171				
AU2-FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Pressure relief devices in liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
AU2-FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	§ 63.170 § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Surge control vessels and bottom receivers.	[G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
AU2-FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.173 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Agitators gas/vapor service and in light liquid service. §63.173(a)-(j).	[G]§ 63.173 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
AU2-FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.174 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Connectors in gas/vapor service and in light liquid service. §63.174(a)-(j)	[G]§ 63.174 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
AU2-FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.163 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.176	Standards: Pumps in light liquid service. §63.163(a)-(j)	[G]§ 63.163 [G]§ 63.176 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(3) § 63.181(h)(4) [G]§ 63.181(h)(5)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
								§ 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(8)	
AU2-FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.167 § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.175	Standards: Open-ended valves or lines. §63.167(a)-(e).	[G]§ 63.175 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
AU2-FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.168 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.175	Standards: Valves in gas/vapor service and in light liquid service. §63.168(a)-(j)	[G]§ 63.168 [G]§ 63.175 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
AU2-SEP	EU	R5131-0010	VOC	30 TAC Chapter 115, Water Separation	§ 115.132(a)(3) § 115.131(a)	VOC water separator compartments must be equipped with a vapor recovery system which satisfies the provisions of §115.131(a) of this title.	[G]§ 115.135(a) § 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	§ 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	None
AU2-SEP	EU	61FF-1781	Benzene	40 CFR Part 61, Subpart FF	§ 61.347(a)(1) § 61.347(a)(1)(i)(A) § 61.347(a)(1)(i)(B) § 61.347(b) § 61.347(c) § 61.349(a)	Install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the oil-water separator to a control	§ 61.347(a)(1)(i)(A) § 61.347(b) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f)	§ 61.349(a)(1)(ii) § 61.356(d) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	device.	§ 61.354(f)(1) [G]§ 61.355(h)	§ 61.356(f)(2)(i)(G) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i)	
CAT1-SEP19	EU	R5131-0010	VOC	30 TAC Chapter 115, Water Separation	§ 115.132(a)(3) § 115.131(a)	VOC water separator compartments must be equipped with a vapor recovery system which satisfies the provisions of §115.131(a) of this title.	[G]§ 115.135(a) § 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	§ 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	None
CAT1-SEP19	EU	61FF-1781	Benzene	40 CFR Part 61, Subpart FF	§ 61.347(a)(1) § 61.347(a)(1)(i)(A) § 61.347(a)(1)(i)(B) § 61.347(b) § 61.347(c) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	Install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the oil-water separator to a control device.	§ 61.347(a)(1)(i)(A) § 61.347(b) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.349(a)(1)(ii) § 61.356(d) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i)	None
CAT3-SEP21	EU	R5131-0010	VOC	30 TAC Chapter 115, Water Separation	§ 115.132(a)(3) § 115.131(a)	VOC water separator compartments must be equipped with a vapor recovery system which satisfies the provisions of §115.131(a) of this title.	[G]§ 115.135(a) § 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	§ 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
CAT3-SEP21	EU	61FF-1781	Benzene	40 CFR Part 61, Subpart FF	§ 61.347(a)(1) § 61.347(a)(1)(i)(A) § 61.347(a)(1)(i)(B) § 61.347(b) § 61.347(c) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	Install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the oil-water separator to a control device.	§ 61.347(a)(1)(i)(A) § 61.347(b) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.349(a)(1)(ii) § 61.356(d) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i)	None
CAT3-SEP22	EU	R5131-0010	VOC	30 TAC Chapter 115, Water Separation	§ 115.132(a)(3) § 115.131(a)	VOC water separator compartments must be equipped with a vapor recovery system which satisfies the provisions of §115.131(a) of this title.	[G]§ 115.135(a) § 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	§ 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	None
CAT3-SEP22	EU	61FF-1781	Benzene	40 CFR Part 61, Subpart FF	§ 61.347(a)(1) § 61.347(a)(1)(i)(A) § 61.347(a)(1)(i)(B) § 61.347(b) § 61.347(c) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	Install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the oil-water separator to a control device.	§ 61.347(a)(1)(i)(A) § 61.347(b) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(d) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.349(a)(1)(ii) § 61.356(d) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(I)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
CFHU-101B	EU	R7300-1086	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C) § 117.8000(b) § 117.8000(c) § 117.8000(c)(1) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
CFHU-101B	EU	R7300-1086	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B) § 117.310(c)(3)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.8000(b) § 117.8000(c) § 117.8000(c)(2) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8120 § 117.8120(2) [G]§ 117.8120(2)(A) § 117.8120(2)(B)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
CFHU-101B	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
CFHU-101B	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
CFHU-102B	EU	R7300-1086	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C) § 117.8000(b) § 117.8000(c) § 117.8000(c)(1) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
CFHU-102B	EU	R7300-1086	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B) § 117.310(c)(3)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.8000(b) § 117.8000(c) § 117.8000(c)(2) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8120 § 117.8120(2) [G]§ 117.8120(2)(A) § 117.8120(2)(B)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
CFHU-102B	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
CFHU-102B	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
CFHU-CTWR	EU	R5760-0022	Highly Reactive	30 TAC Chapter 115, HRVOC	§ 115.767(3) § 115.764(a)(1)	Any site for which no stream directed to a cooling tower	§ 115.764(a)(1) § 115.764(a)(3)	§ 115.766(c) § 115.766(d)	§ 115.766(i)(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
			VOC	Cooling Towers	§ 115.766(i)	heat exchange system contains 5.0% or greater by weight HRVOC is exempt from the requirements of _115.761 of this title (relating to Site-wide Cap).	§ 115.764(c) § 115.764(d)	§ 115.766(i)(1)	
CFHU-CTWR	EU	63CC-002	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.654(a) § 63.640(h)(6)	Except as specified in paragraph (b) of this section, the owner or operator of a heat exchange system that meets the criteria in §63.640(c)(8) must comply with the requirements of paragraphs (c) through (g) of this section.	§ 63.642(d)(1) § 63.642(d)(3) § 63.642(d)(4) [G]§ 63.654(c) [G]§ 63.654(d) § 63.654(e) [G]§ 63.654(f) [G]§ 63.654(g)	§ 63.642(e) § 63.655(h)(1) [G]§ 63.655(i)(4) § 63.655(i)(5)	§ 63.642(d)(2) § 63.642(f) § 63.655(f) § 63.655(f)(1)(vi) § 63.655(f)(4) § 63.655(g) [G]§ 63.655(g)(9) § 63.655(h)(1)
CFHU-FUG1	EU	60GGGa-001	VOC	40 CFR Part 60, Subpart GGGa	[G]§ 60.590a(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 60, Subpart GGGa
CFHU-SEP	EU	R5131-0010	VOC	30 TAC Chapter 115, Water Separation	§ 115.132(a)(3) § 115.131(a)	VOC water separator compartments must be equipped with a vapor recovery system which satisfies the provisions of §115.131(a) of this title.	[G]§ 115.135(a) § 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	§ 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	None
CFHU-SEP	EU	61FF-1781	Benzene	40 CFR Part 61, Subpart FF	§ 61.347(a)(1) § 61.347(a)(1)(i)(A) § 61.347(a)(1)(i)(B) § 61.347(b) § 61.347(c)	Install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the oil-water	§ 61.347(a)(1)(i)(A) § 61.347(b) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e)	§ 61.349(a)(1)(ii) § 61.356(d) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	separator to a control device.	§ 61.349(f) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i)	
CKR-BDS	EP	R5121-0003	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
CKR-BDS	EP	63CC-1003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(1)	All miscellaneous process vents from petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	[G]§ 63.645(g) § 63.645(h) § 63.645(h)(1) § 63.645(h)(2)	§ 63.655(g)(7)(ii) § 63.655(i)(5)	§ 63.645(h)(2) § 63.655(f) § 63.655(f)(1)(ii) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i)
COKERLOAD	EU	R5211-0009	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(a)(1) § 115.214(a)(1)(B) § 115.214(a)(1)(D) § 115.214(a)(1)(D)(i)	Vapor pressure (at land-based operations). All land-based loading and unloading of VOC with a true vapor pressure less than 0.5 psia is exempt from the requirements of this division, except as specified.	§ 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.215 § 115.215(4)	§ 115.216 § 115.216(2) § 115.216(3)(B)	None
COKR-B101	EU	R7300-1086	NO_X	30 TAC Chapter 117,	§ 117.310(d)(3) § 117.310(a)	An owner or operator may not use the alternative	[G]§ 117.335(a)(1) § 117.335(a)(4)	§ 117.345(a) § 117.345(f)	§ 117.335(b) § 117.335(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Subchapter B	§ 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	§ 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C) § 117.8000(b) § 117.8000(c) § 117.8000(c)(1) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d)	§ 117.345(f)(1) § 117.345(f)(9)	§ 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
COKR-B101	EU	R7300-1086	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B) § 117.310(c)(3)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.8000(b) § 117.8000(c) § 117.8000(c)(2) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8120 § 117.8120(2) [G]§ 117.8120(2)(A) § 117.8120(2)(B)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
COKR-B101	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of	§ 60.105(a)(4) § 60.105(a)(4)(i)	§ 60.105(a)(4) § 60.105(a)(4)(i)	§ 60.105(e)(3)(ii) § 60.107(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4)(iii)	§ 60.107(f) § 60.107(g)
COKR-B101	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
COKR-B201	EU	R7300-1289	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(2) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) § 117.340(c)(3)(D) [G]§ 117.340(c)(3)(E) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)		
COKR-B201	EU	R7300-1289	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(e) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							[G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)		
COKR-B201	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
COKR-B201	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
COKR-B203	EU	R7300-1097	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of §	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(2) § 117.335(g) § 117.340(a)(2)(B) § 117.340(c)(1) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	§ 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)		[G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
COKR-B203	EU	R7300-1097	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a)(2)(B) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							[G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)		
COKR-B203	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
COKR-B203	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
COKR-B301	EU	R7300-1289	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of §	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(2) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) [G]§ 117.340(c)(3) [G]§ 117.340(f)(2) § 117.340(l)(2)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	§ 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)		[G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
COKR-B301	EU	R7300-1289	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(e) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2)	§ 117.345(a) § 117.345(f) [G]§ 117.345(f)(2) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							[G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)		
COKR-B301	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
COKR-B301	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
COKR-B302	EU	R7300-1086	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(l)(2)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101,	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.340(l)(2) § 117.340(o)(1)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	§ 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C) § 117.8000(b) § 117.8000(c) § 117.8000(c)(1) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d)		§ 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
COKR-B302	EU	R7300-1086	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B) § 117.310(c)(3)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.8000(b) § 117.8000(c) § 117.8000(c)(2) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8120 § 117.8120(2) [G]§ 117.8120(2)(A) § 117.8120(2)(B)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
COKR-B302	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
COKR-B302	EU	63DDDDD	112(B)	40 CFR Part 63,	§ 63.7505	The permit holder shall	The permit holder shall	The permit holder	The permit holder shall

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		-1	HAPS	Subpart DDDDD	The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
COKR-CTWR	EU	R5760-0022	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Cooling Towers	§ 115.767(3) § 115.764(a)(1) § 115.766(i)	Any site for which no stream directed to a cooling tower heat exchange system contains 5.0% or greater by weight HRVOC is exempt from the requirements of _115.761 of this title (relating to Site-wide Cap).	§ 115.764(a)(1) § 115.764(a)(3) § 115.764(c) § 115.764(d)	§ 115.766(c) § 115.766(d) § 115.766(i)(1)	§ 115.766(i)(2)
COKR-CTWR	EU	63CC-002	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.654(a) § 63.640(h)(6)	Except as specified in paragraph (b) of this section, the owner or operator of a heat exchange system that meets the criteria in §63.640(c)(8) must comply with the requirements of paragraphs (c) through (g) of this section.	§ 63.642(d)(1) § 63.642(d)(3) § 63.642(d)(4) [G]§ 63.654(c) [G]§ 63.654(d) § 63.654(e) [G]§ 63.654(f) [G]§ 63.654(g)	§ 63.642(e) § 63.655(h)(1) [G]§ 63.655(i)(4) § 63.655(i)(5)	§ 63.642(d)(2) § 63.642(f) § 63.655(f) § 63.655(f)(1)(vi) § 63.655(f)(4) § 63.655(g) [G]§ 63.655(g)(9) § 63.655(h)(1)
COKR-FUG1	EU	60GGGa-01	VOC	40 CFR Part 60, Subpart GGGa	[G]§ 60.590a(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 60, Subpart GGGa

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
COKR-SEP	EU	R5131-0010	VOC	30 TAC Chapter 115, Water Separation	§ 115.132(a)(3) § 115.131(a)	VOC water separator compartments must be equipped with a vapor recovery system which satisfies the provisions of §115.131(a) of this title.	[G]§ 115.135(a) § 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4) ** See CAM Summary	§ 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	None
COKR-SEP	EU	61FF-1781	Benzene	40 CFR Part 61, Subpart FF	§ 61.347(a)(1) § 61.347(a)(1)(i)(A) § 61.347(a)(1)(i)(B) § 61.347(b) § 61.347(c) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	Install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the oil-water separator to a control device.	§ 61.347(a)(1)(i)(A) § 61.347(b) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.349(a)(1)(ii) § 61.356(d) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i)	None
DDU-101B	EU	R7300-1086	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C) § 117.8000(b) § 117.8000(c) § 117.8000(c)(1)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	§ 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d)		[G]§ 117.8010(7) [G]§ 117.8010(8)
DDU-101B	EU	R7300-1086	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B) § 117.310(c)(3)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.8000(b) § 117.8000(c) § 117.8000(c)(2) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8120 § 117.8120(2) [G]§ 117.8120(2)(A) § 117.8120(2)(B)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
DDU-101B	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
DDU-101B	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					CFR Part 63, Subpart DDDDD				
DDU-102B	EU	R7300-1018	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(ii) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C) § 117.8000(b) § 117.8000(c) § 117.8000(c)(1) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
DDU-102B	EU	R7300-1018	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B) § 117.310(c)(3)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.8000(b) § 117.8000(c) § 117.8000(c)(2) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8120 § 117.8120(2)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							[G]§ 117.8120(2)(A) § 117.8120(2)(B)		
DDU-102B	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
DDU-102B	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
DDU-201B	EU	R7300-1086	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C) § 117.8000(b) § 117.8000(c) § 117.8000(c)(1) § 117.8000(c)(3) § 117.8000(c)(5)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						specified in § 117.9800 to comply with § 117.320.	§ 117.8000(c)(6) [G]§ 117.8000(d)		
DDU-201B	EU	R7300-1086	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B) § 117.310(c)(3)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.8000(b) § 117.8000(c) § 117.8000(c)(2) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8120 § 117.8120(2) [G]§ 117.8120(2)(A) § 117.8120(2)(B)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
DDU-201B	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
DDU-201B	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
DDU-202B	EU	R7300-1018	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(ii) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C) § 117.8000(b) § 117.8000(c) § 117.8000(c)(1) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
DDU-202B	EU	R7300-1018	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B) § 117.310(c)(3)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.8000(b) § 117.8000(c) § 117.8000(c)(2) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8120 § 117.8120(2) [G]§ 117.8120(2)(A) § 117.8120(2)(B)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
DDU-202B	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
DDU-202B	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
DDU-315A	EU	R5131-0010	VOC	30 TAC Chapter 115, Water Separation	§ 115.132(a)(3) § 115.131(a)	VOC water separator compartments must be equipped with a vapor recovery system which satisfies the provisions of §115.131(a) of this title.	[G]§ 115.135(a) § 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4) ** See CAM Summary	§ 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	None
DDU-315A	EU	61FF-1733	Benzene	40 CFR Part 61, Subpart FF	§ 61.347(a)(1) § 60.18 § 61.347(a)(1)(i)(A) § 61.347(a)(1)(i)(B) § 61.347(b) § 61.347(c) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(b) § 61.349(e)	Install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the oil-water separator to a control device.	§ 60.18(f)(2) § 61.347(a)(1)(i)(A) § 61.347(b) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(c) § 61.354(c)(3) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.349(a)(1)(ii) § 61.354(c) § 61.354(c)(3) § 61.356(d) § 61.356(f) § 61.356(f)(1) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i) § 61.356(j)(7)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(F)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 61.349(f) § 61.349(g)				
DDU-B301	EU	R7300-1086	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C) § 117.8000(b) § 117.8000(c) § 117.8000(c)(1) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
DDU-B301	EU	R7300-1086	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B) § 117.310(c)(3)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.8000(b) § 117.8000(c) § 117.8000(c)(2) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8120 § 117.8120(2)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							[G]§ 117.8120(2)(A) § 117.8120(2)(B)		
DDU-B301	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
DDU-B301	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
DDU-B302	EU	R7300-1086	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C) § 117.8000(b) § 117.8000(c) § 117.8000(c)(1) § 117.8000(c)(3) § 117.8000(c)(5)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						specified in § 117.9800 to comply with § 117.320.	§ 117.8000(c)(6) [G]§ 117.8000(d)		
DDU-B302	EU	R7300-1086	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B) § 117.310(c)(3)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.8000(b) § 117.8000(c) § 117.8000(c)(2) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8120 § 117.8120(2) [G]§ 117.8120(2)(A) § 117.8120(2)(B)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
DDU-B302	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
DDU-B302	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
DDU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(d)	Comply with the requirements as stated in §60.482-1(d) for equipment in vacuum service.	None	§ 60.486(e) § 60.486(e)(1) § 60.486(e)(5)	None
DDU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-2 [G]§ 60.482-9	Comply with the requirements as stated in §60.482-2 for pumps in light-liquid service.	[G]§ 60.482-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d) § 60.593(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
DDU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.593(b)(1)	Compressors in hydrogen service are exempt from the requirements of §60.592 if an owner or operator demonstrates that a compressor is in hydrogen service.	§ 60.593(b)(2) [G]§ 60.593(b)(3)	None	None
DDU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-3 [G]§ 60.482-9	Comply with the requirements as stated in §60.482-3 for compressors.	[G]§ 60.482-3 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
DDU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-4 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-4 for pressure relief devices in gas/vapor service.	[G]§ 60.482-4 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(3) [G]§ 60.486(e)(4) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 60.592(d)	§ 60.592(e)	
DDU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-5 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-5 for sampling connection systems.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
DDU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-6 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-6 for open-ended valves and lines.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
DDU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-7 [G]§ 60.482-9 [G]§ 60.483-1 [G]§ 60.483-2 § 60.592(b)	Comply with the requirements in as stated in §60.482-7 for valves in gas/vapor or light-liquid service.	[G]§ 60.482-7 [G]§ 60.483-1 [G]§ 60.483-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d) § 60.593(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) [G]§ 60.486(g) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(d) § 60.487(e) § 60.592(e)
DDU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for pumps in heavy-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
DDU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) § 60.482-10(b) § 60.482-10(e) § 60.482-10(m)	Comply with the requirements in as stated in §60.482-10 for vapor recovery devices.	§ 60.485(a) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
DDU-FUG	EU	60GGG-	VOC	40 CFR Part 60,	§ 60.592(a)	Comply with the	§ 60.485(a)	[G]§ 60.486(a)	§ 60.487(a)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		0001		Subpart GGG	§ 60.18 § 60.482-1(a) § 60.482-1(b) § 60.482-10(d) § 60.482-10(e) § 60.482-10(m)	requirements in as stated in §60.482-10 for flares.	[G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) [G]§ 60.485(g) § 60.592(d)	[G]§ 60.486(d) § 60.486(e) § 60.486(e)(1) § 60.592(e)	[G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
DDU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) § 60.482-10(e) [G]§ 60.482-10(g) § 60.482-10(h) § 60.482-10(m)	Comply with the requirements in as stated in §60.482-10 for closed-vent systems.	[G]§ 60.482-10(f) § 60.482-10(i) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.482-10(j) [G]§ 60.482-10(k) [G]§ 60.482-10(l) [G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
DDU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for valves in heavy-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
DDU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for flanges or other connectors.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
DDU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for pressure relief devices in light-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
DDU-SEP	EU	R5131-	VOC	30 TAC Chapter	§ 115.132(a)(3)	VOC water separator	[G]§ 115.135(a)	§ 115.136(a)(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		0010		115, Water Separation	§ 115.131(a)	compartments must be equipped with a vapor recovery system which satisfies the provisions of §115.131(a) of this title.	§ 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	§ 115.136(a)(3) § 115.136(a)(4)	
DDU-SEP	EU	61FF-1781	Benzene	40 CFR Part 61, Subpart FF	§ 61.347(a)(1) § 61.347(a)(1)(i)(A) § 61.347(a)(1)(i)(B) § 61.347(b) § 61.347(c) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	Install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the oil-water separator to a control device.	§ 61.347(a)(1)(i)(A) § 61.347(b) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.349(a)(1)(ii) § 61.356(d) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i)	None
DHT-101B	EU	R7300-0006	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(2) § 117.335(g) § 117.340(a) § 117.340(c)(1) [G]§ 117.340(c)(3) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						alternative methods specified in § 117.9800 to comply with § 117.320.	§ 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)		[G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
DHT-101B	EU	R7300-0006	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a) § 117.340(e) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							[G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)		
DHT-101B	EU	R7300-0006	NH_3	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(2) § 117.310(c)(2)(B) § 117.340(f)(1)	For process heaters that inject urea or ammonia into the exhaust stream for NO_x control, ammonia emissions must not exceed 10 ppmv at 3.0% O_2, dry.	§ 117.335(a)(2) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(g) § 117.340(d) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8130 § 117.8130(4)	§ 117.345(a) § 117.345(f) § 117.345(f)(11) [G]§ 117.345(f)(2) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
DHT-101B	EU	R7300-0007	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(2) § 117.335(g)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	§ 117.340(a) § 117.340(c)(1) [G]§ 117.340(c)(3) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)		§ 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
DHT-101B	EU	R7300-0007	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a) § 117.340(e) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)		[G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
DHT-101B	EU	R7300-0007	NH_3	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(2) § 117.310(c)(2)(A)	For process heaters that inject urea or ammonia into the exhaust stream for NO_x control, ammonia emissions must not exceed 10 ppmv at 3.0% O_2, dry.	§ 117.335(a)(2) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(d) § 117.8000(b) § 117.8000(c) § 117.8000(c)(3) § 117.8000(c)(4) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8130 § 117.8130(3)	§ 117.345(a) § 117.345(f) § 117.345(f)(11) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
DHT-101B	EU	60Ja-0002	§111 Pollutant	40 CFR Part 60, Subpart Ja	§ 60.100a(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40	The permit holder shall comply with the applicable requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 60, Subpart Ja

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					CFR Part 60, Subpart Ja				
DHT-101B	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
DHT-201B	EU	R7300-0008	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(2) § 117.335(g) § 117.340(a) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) [G]§ 117.340(c)(3) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)		
DHT-201B	EU	R7300-0008	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a) § 117.340(b)(1) § 117.340(b)(3) § 117.340(e) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
DHT-201B	EU	R7300-0008	NH_3	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(2) § 117.310(c)(2)(B) § 117.340(f)(1)	For process heaters that inject urea or ammonia into the exhaust stream for NO_x control, ammonia emissions must not exceed 10 ppmv at 3.0% O_2, dry.	§ 117.335(a)(2) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(g) § 117.340(b)(1) § 117.340(b)(3) § 117.340(d) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8130 § 117.8130(4)	§ 117.345(a) § 117.345(f) § 117.345(f)(11) [G]§ 117.345(f)(2) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
DHT-201B	EU	R7300-0009	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(2) § 117.335(g) § 117.340(a) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.340(c)(3) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)		§ 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
DHT-201B	EU	R7300-0009	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a) § 117.340(b)(1) § 117.340(b)(3) § 117.340(e) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)		[G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
DHT-201B	EU	R7300-0009	NH_3	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(2) § 117.310(c)(2)(A)	For process heaters that inject urea or ammonia into the exhaust stream for NO_x control, ammonia emissions must not exceed 10 ppmv at 3.0% O_2, dry.	§ 117.335(a)(2) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(b)(1) § 117.340(b)(3) § 117.340(d) § 117.8000(b) § 117.8000(c) § 117.8000(c)(3) § 117.8000(c)(4) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8130 § 117.8130(3)	§ 117.345(a) § 117.345(f) § 117.345(f)(11) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
DHT-201B	EU	60Ja-0003	§111 Pollutant	40 CFR Part 60, Subpart Ja	§ 60.100a(a) The permit holder shall comply with the applicable limitation, standard and/or equipment	The permit holder shall comply with the applicable requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 60,	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 60, Subpart Ja

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					specification requirements of 40 CFR Part 60, Subpart Ja			Subpart Ja	
DHT-201B	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
DHT-FUG1	EU	60GGGa-001	VOC	40 CFR Part 60, Subpart GGGa	[G]§ 60.590a(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 60, Subpart GGGa
DKTO294-1	EU	R7300-3688	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) [G]§ 117.310(a)(16) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(g) § 117.340(a)(2)(B) § 117.340(c)(1) [G]§ 117.340(c)(3) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	§ 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)		§ 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
DKTO294-2	EU	R7300-3688	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) [G]§ 117.310(a)(16) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(g) § 117.340(a)(2)(B) § 117.340(c)(1) [G]§ 117.340(c)(3) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)		
DKTO294-3	EU	R7300-3688	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) [G]§ 117.310(a)(16) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(g) § 117.340(a)(2)(B) § 117.340(c)(1) [G]§ 117.340(c)(3) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
DOCK32	EU	R5211-	VOC	30 TAC Chapter	§ 115.212(a)(6)(A)	Emissions shall not exceed	[G]§ 115.214(a)(3)(A)	[G]§	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		0190		115, Loading and Unloading of VOC	§ 115.212(a)(6)(B) [G]§ 115.212(a)(6)(C) § 115.212(a)(6)(D) [G]§ 115.214(a)(3)(A) § 115.214(a)(3)(C) § 115.214(a)(3)(D) § 115.214(a)(3)(E)	0.09lb/1,000gal loaded, or the vapor control system shall maintain a control efficiency of at least 90%, or a vapor balance system or pressurized loading may be used.	§ 115.214(a)(3)(B) § 115.214(a)(3)(B)(i) § 115.214(a)(3)(B)(ii) § 115.214(a)(3)(B)(iii) § 115.214(a)(3)(D) § 115.215 § 115.215(1) § 115.215(10) [G]§ 115.215(2) § 115.215(4) § 115.215(5) § 115.215(7) § 115.215(8) § 115.215(9) § 115.216(1) § 115.216(1)(A) § 115.216(1)(A)(i) ** See CAM Summary	115.214(a)(3)(A) § 115.214(a)(3)(D) § 115.216 § 115.216(1) § 115.216(1)(A) § 115.216(1)(A)(i) § 115.216(2) [G]§ 115.216(4)	
DOCK32	EU	R5211-0226	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.212(a)(6)(A) § 115.212(a)(6)(B) [G]§ 115.212(a)(6)(C) § 115.212(a)(6)(D) [G]§ 115.214(a)(3)(A) § 115.214(a)(3)(C) § 115.214(a)(3)(D) § 115.214(a)(3)(E)	Emissions shall not exceed 0.09lb/1,000gal loaded, or the vapor control system shall maintain a control efficiency of at least 90%, or a vapor balance system or pressurized loading may be used.	[G]§ 115.214(a)(3)(A) § 115.214(a)(3)(B) § 115.214(a)(3)(B)(i) § 115.214(a)(3)(B)(ii) § 115.214(a)(3)(B)(iii) § 115.214(a)(3)(D) § 115.215 § 115.215(1) § 115.215(10) [G]§ 115.215(2) § 115.215(4) § 115.215(5) § 115.215(7) § 115.215(8) § 115.215(9) § 115.216(1) § 115.216(1)(A) § 115.216(1)(A)(i) ** See CAM Summary	[G]§ 115.214(a)(3)(A) § 115.214(a)(3)(D) § 115.216 § 115.216(1) § 115.216(1)(A) § 115.216(1)(A)(i) § 115.216(2) [G]§ 115.216(4)	None
DOCK32	EU	61BB-	Benzene	40 CFR Part 61,	[G]§ 61.302(a)	Equip each loading rack	§ 61.302(k)	§ 61.304(a)(4)(i)	§ 61.305(a)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		0012		Subpart BB	§ 61.302(b) § 61.302(f) § 61.302(g) § 61.302(j) § 61.302(k)	with vapor collection system to collect all displaced benzene vapors and prevent it from passing from one loading rack through another to the atmosphere. § 61.302(a)(1)-(2)	§ 61.303(a) § 61.303(a)(1) § 61.304(a)(1) § 61.304(a)(2) § 61.304(a)(4) § 61.304(a)(4)(i) § 61.304(a)(4)(ii) § 61.304(a)(4)(iii) § 61.304(a)(4)(iv) § 61.304(a)(5) § 61.304(a)(6) § 61.304(a)(7) § 61.304(d)(1) § 61.304(d)(2) § 61.304(d)(3) § 61.304(e) ** See CAM Summary	§ 61.304(d)(3) § 61.305(a) [G]§ 61.305(a)(1) § 61.305(b) § 61.305(b)(1)	§ 61.305(a)(5) § 61.305(b) § 61.305(b)(1) § 61.305(f) § 61.305(f)(1)
DOCK32	EU	63CC-2502	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.651(a)	Except as provided in §63.651(b)-(d), each owner or operator of a marine tank vessel loading operation located at a petroleum refinery shall comply with the requirements of §63.560 through §63.567.	§ 63.642(d)(1) § 63.642(d)(3) § 63.642(d)(4)	§ 63.642(e) § 63.655(c) § 63.655(i)(5)	§ 63.640(l) § 63.640(l)(3) § 63.640(l)(3)(i) § 63.640(l)(3)(iii) § 63.640(l)(3)(iv) § 63.640(l)(3)(v) § 63.640(l)(3)(vi) § 63.640(l)(3)(vii) § 63.642(d)(2) § 63.642(f) § 63.655(c) § 63.655(e) § 63.655(e)(1) § 63.655(f)
DOCK32	EU	63Y-0465	112(B) HAPS	40 CFR Part 63, Subpart Y	§ 63.562(b) [G]§ 63.562(b)(1) § 63.562(b)(2) [G]§ 63.562(b)(6) § 63.562(e) § 63.562(e)(1) [G]§ 63.562(e)(2)	Marine tank vessel loading operations shall apply MACT standards, except for the VMT source.	[G]§ 63.562(b)(6) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) § 63.563(b) § 63.563(b)(1) § 63.563(b)(10) § 63.563(b)(3)	[G]§ 63.562(b)(6) § 63.562(e)(5) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) § 63.564(b)(1) § 63.564(e)(3) [G]§ 63.565(d)	[G]§ 63.562(b)(6) § 63.562(e)(7)(ii) § 63.567(b)(5) § 63.567(c) § 63.567(e)(1) [G]§ 63.567(e)(2) § 63.567(e)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 63.562(e)(3) § 63.562(e)(4) § 63.562(e)(5) § 63.562(e)(6) § 63.562(e)(7) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) [G]§ 63.563(a)(1) § 63.563(a)(2) § 63.563(a)(3)		§ 63.563(b)(4) § 63.563(b)(4)(ii) [G]§ 63.563(c) § 63.564(a)(2) § 63.564(a)(3) § 63.564(a)(4) § 63.564(b)(1) § 63.564(c) § 63.564(e)(3) § 63.564(e)(4) [G]§ 63.565(b) [G]§ 63.565(d) § 63.565(f) § 63.565(f)(2) § 63.565(l)	§ 63.567(f) [G]§ 63.567(g) § 63.567(j)(1) § 63.567(j)(2) § 63.567(j)(4) [G]§ 63.567(k)	§ 63.567(e)(4) § 63.567(e)(5) § 63.567(e)(6) § 63.567(f) § 63.567(j)(3) § 63.567(m) § 63.567(n)(1) § 63.567(n)(2)
DOCK32	EU	63Y-1665	112(B) HAPS	40 CFR Part 63, Subpart Y	§ 63.562(b) [G]§ 63.562(b)(1) § 63.562(b)(2) [G]§ 63.562(b)(6) § 63.562(e) § 63.562(e)(1) [G]§ 63.562(e)(2) [G]§ 63.562(e)(3) § 63.562(e)(4) § 63.562(e)(5) § 63.562(e)(6) § 63.562(e)(7) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) [G]§ 63.563(a)(1) § 63.563(a)(2) § 63.563(a)(3)	Marine tank vessel loading operations shall apply MACT standards, except for the VMT source.	[G]§ 63.562(b)(6) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) § 63.563(b) § 63.563(b)(1) § 63.563(b)(10) § 63.563(b)(3) § 63.563(b)(4) § 63.563(b)(4)(ii) [G]§ 63.563(c) § 63.564(a)(2) § 63.564(a)(3) § 63.564(a)(4) § 63.564(b)(1) § 63.564(c) § 63.564(e)(3) § 63.564(e)(4) [G]§ 63.565(b) [G]§ 63.565(d) § 63.565(f) § 63.565(f)(2) § 63.565(l)	[G]§ 63.562(b)(6) § 63.562(e)(5) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) § 63.564(b)(1) § 63.564(e)(3) [G]§ 63.565(d) § 63.567(f) [G]§ 63.567(g) § 63.567(j)(1) § 63.567(j)(2) § 63.567(j)(4) [G]§ 63.567(k)	[G]§ 63.562(b)(6) § 63.562(e)(7)(ii) § 63.567(b)(5) § 63.567(c) § 63.567(e)(1) [G]§ 63.567(e)(2) § 63.567(e)(3) § 63.567(e)(4) § 63.567(e)(5) § 63.567(e)(6) § 63.567(f) § 63.567(j)(3) § 63.567(m) § 63.567(n)(1) § 63.567(n)(2)
DOCK32	EU	63Y-1665	VOC	40 CFR Part 63,	§ 63.562(c)	RACT standards, except the	[G]§ 63.562(e)(7)(i)	§ 63.562(e)(5)	§ 63.562(c)(1)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Subpart Y	[G]§ 63.562(c)(2) § 63.562(c)(3) § 63.562(c)(4) [G]§ 63.562(c)(6) § 63.562(e) § 63.562(e)(1) [G]§ 63.562(e)(2) [G]§ 63.562(e)(3) § 63.562(e)(4) § 63.562(e)(5) § 63.562(e)(6) § 63.562(e)(7) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) [G]§ 63.563(a)(1) § 63.563(a)(2) § 63.563(a)(3)	VMT source.	§ 63.562(e)(7)(ii) § 63.563(b) § 63.563(b)(1) § 63.563(b)(3) § 63.563(b)(4) § 63.563(b)(4)(ii) [G]§ 63.563(c) § 63.564(a)(2) § 63.564(a)(3) § 63.564(a)(4) § 63.564(b)(1) § 63.564(c) § 63.564(e)(3) § 63.564(e)(4) [G]§ 63.565(b) [G]§ 63.565(d) § 63.565(f) § 63.565(f)(2) § 63.565(l)	[G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) § 63.564(b)(1) § 63.564(e)(3) [G]§ 63.565(d) § 63.567(f) [G]§ 63.567(g) § 63.567(j)(1) § 63.567(j)(2) § 63.567(j)(4) [G]§ 63.567(k)	§ 63.562(e)(7)(ii) [G]§ 63.567(b)(2) § 63.567(b)(3) [G]§ 63.567(b)(4) § 63.567(c) § 63.567(e)(1) [G]§ 63.567(e)(2) § 63.567(e)(3) § 63.567(e)(4) § 63.567(e)(5) § 63.567(e)(6) § 63.567(f) § 63.567(j)(3) § 63.567(m) § 63.567(n)(1) § 63.567(n)(2)
DOCK33	EU	R5211-0226	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.212(a)(6)(A) § 115.212(a)(6)(B) [G]§ 115.212(a)(6)(C) § 115.212(a)(6)(D) [G]§ 115.214(a)(3)(A) § 115.214(a)(3)(C) § 115.214(a)(3)(D) § 115.214(a)(3)(E)	Emissions shall not exceed 0.09lb/1,000gal loaded, or the vapor control system shall maintain a control efficiency of at least 90%, or a vapor balance system or pressurized loading may be used.	[G]§ 115.214(a)(3)(A) § 115.214(a)(3)(B) § 115.214(a)(3)(B)(i) § 115.214(a)(3)(B)(ii) § 115.214(a)(3)(B)(iii) § 115.214(a)(3)(D) § 115.215 § 115.215(1) § 115.215(10) [G]§ 115.215(2) § 115.215(4) § 115.215(5) § 115.215(7) § 115.215(8) § 115.215(9) § 115.216(1) § 115.216(1)(A) § 115.216(1)(A)(i) ** See CAM Summary	[G]§ 115.214(a)(3)(A) § 115.214(a)(3)(D) § 115.216 § 115.216(1) § 115.216(1)(A) § 115.216(1)(A)(i) § 115.216(2) [G]§ 115.216(4)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
DOCK33	EU	61BB-0012	Benzene	40 CFR Part 61, Subpart BB	[G]§ 61.302(a) § 61.302(b) § 61.302(f) § 61.302(g) § 61.302(j) § 61.302(k)	Equip each loading rack with vapor collection system to collect all displaced benzene vapors and prevent it from passing from one loading rack through another to the atmosphere. § 61.302(a)(1)-(2)	§ 61.302(k) § 61.303(a) § 61.303(a)(1) § 61.304(a)(1) § 61.304(a)(2) § 61.304(a)(4) § 61.304(a)(4)(i) § 61.304(a)(4)(ii) § 61.304(a)(4)(iii) § 61.304(a)(4)(iv) § 61.304(a)(5) § 61.304(a)(6) § 61.304(a)(7) § 61.304(d)(1) § 61.304(d)(2) § 61.304(d)(3) § 61.304(e) ** See CAM Summary	§ 61.304(a)(4)(i) § 61.304(d)(3) § 61.305(a) [G]§ 61.305(a)(1) § 61.305(b) § 61.305(b)(1)	§ 61.305(a) § 61.305(a)(5) § 61.305(b) § 61.305(b)(1) § 61.305(f) § 61.305(f)(1)
DOCK33	EU	63CC-2502	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.651(a)	Except as provided in §63.651(b)-(d), each owner or operator of a marine tank vessel loading operation located at a petroleum refinery shall comply with the requirements of §63.560 through §63.567.	§ 63.642(d)(1) § 63.642(d)(3) § 63.642(d)(4)	§ 63.642(e) § 63.655(c) § 63.655(i)(5)	§ 63.640(l) § 63.640(l)(3) § 63.640(l)(3)(i) § 63.640(l)(3)(iii) § 63.640(l)(3)(iv) § 63.640(l)(3)(v) § 63.640(l)(3)(vi) § 63.640(l)(3)(vii) § 63.642(d)(2) § 63.642(f) § 63.655(c) § 63.655(e) § 63.655(e)(1) § 63.655(f)
DOCK33	EU	63Y-0465	112(B) HAPS	40 CFR Part 63, Subpart Y	§ 63.562(b) [G]§ 63.562(b)(1) § 63.562(b)(2) [G]§ 63.562(b)(6) § 63.562(e) § 63.562(e)(1)	Marine tank vessel loading operations shall apply MACT standards, except for the VMT source.	[G]§ 63.562(b)(6) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) § 63.563(b) § 63.563(b)(1) § 63.563(b)(10)	[G]§ 63.562(b)(6) § 63.562(e)(5) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) § 63.564(b)(1) § 63.564(e)(3)	[G]§ 63.562(b)(6) § 63.562(e)(7)(ii) § 63.567(b)(5) § 63.567(c) § 63.567(e)(1) [G]§ 63.567(e)(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 63.562(e)(2) [G]§ 63.562(e)(3) § 63.562(e)(4) § 63.562(e)(5) § 63.562(e)(6) § 63.562(e)(7) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) [G]§ 63.563(a)(1) § 63.563(a)(2) § 63.563(a)(3)		§ 63.563(b)(3) § 63.563(b)(4) § 63.563(b)(4)(ii) [G]§ 63.563(c) § 63.564(a)(2) § 63.564(a)(3) § 63.564(a)(4) § 63.564(b)(1) § 63.564(c) § 63.564(e)(3) § 63.564(e)(4) [G]§ 63.565(b) [G]§ 63.565(d) § 63.565(f) § 63.565(f)(2) § 63.565(l)	[G]§ 63.565(d) § 63.567(f) [G]§ 63.567(g) § 63.567(j)(1) § 63.567(j)(2) § 63.567(j)(4) [G]§ 63.567(k)	§ 63.567(e)(3) § 63.567(e)(4) § 63.567(e)(5) § 63.567(e)(6) § 63.567(f) § 63.567(j)(3) § 63.567(m) § 63.567(n)(1) § 63.567(n)(2)
DOCK33	EU	63Y-1665	112(B) HAPS	40 CFR Part 63, Subpart Y	§ 63.562(b) [G]§ 63.562(b)(1) § 63.562(b)(2) [G]§ 63.562(b)(6) § 63.562(e) § 63.562(e)(1) [G]§ 63.562(e)(2) [G]§ 63.562(e)(3) § 63.562(e)(4) § 63.562(e)(5) § 63.562(e)(6) § 63.562(e)(7) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) [G]§ 63.563(a)(1) § 63.563(a)(2) § 63.563(a)(3)	Marine tank vessel loading operations shall apply MACT standards, except for the VMT source.	[G]§ 63.562(b)(6) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) § 63.563(b) § 63.563(b)(1) § 63.563(b)(10) § 63.563(b)(3) § 63.563(b)(4) § 63.563(b)(4)(ii) [G]§ 63.563(c) § 63.564(a)(2) § 63.564(a)(3) § 63.564(a)(4) § 63.564(b)(1) § 63.564(c) § 63.564(e)(3) § 63.564(e)(4) [G]§ 63.565(b) [G]§ 63.565(d) § 63.565(f) § 63.565(f)(2) § 63.565(l)	[G]§ 63.562(b)(6) § 63.562(e)(5) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) § 63.564(b)(1) § 63.564(e)(3) [G]§ 63.565(d) § 63.567(f) [G]§ 63.567(g) § 63.567(j)(1) § 63.567(j)(2) § 63.567(j)(4) [G]§ 63.567(k)	[G]§ 63.562(b)(6) § 63.562(e)(7)(ii) § 63.567(b)(5) § 63.567(c) § 63.567(e)(1) [G]§ 63.567(e)(2) § 63.567(e)(3) § 63.567(e)(4) § 63.567(e)(5) § 63.567(e)(6) § 63.567(f) § 63.567(j)(3) § 63.567(m) § 63.567(n)(1) § 63.567(n)(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
DOCK33	EU	63Y-1665	VOC	40 CFR Part 63, Subpart Y	§ 63.562(c) [G]§ 63.562(c)(2) § 63.562(c)(3) § 63.562(c)(4) [G]§ 63.562(c)(6) § 63.562(e) § 63.562(e)(1) [G]§ 63.562(e)(2) [G]§ 63.562(e)(3) § 63.562(e)(4) § 63.562(e)(5) § 63.562(e)(6) § 63.562(e)(7) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) [G]§ 63.563(a)(1) § 63.563(a)(2) § 63.563(a)(3)	RACT standards, except the VMT source.	[G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) § 63.563(b) § 63.563(b)(1) § 63.563(b)(3) § 63.563(b)(4) § 63.563(b)(4)(ii) [G]§ 63.563(c) § 63.564(a)(2) § 63.564(a)(3) § 63.564(a)(4) § 63.564(b)(1) § 63.564(c) § 63.564(e)(3) § 63.564(e)(4) [G]§ 63.565(b) [G]§ 63.565(d) § 63.565(f) § 63.565(f)(2) § 63.565(l)	§ 63.562(e)(5) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) § 63.564(b)(1) § 63.564(e)(3) [G]§ 63.565(d) § 63.567(f) [G]§ 63.567(g) § 63.567(j)(1) § 63.567(j)(2) § 63.567(j)(4) [G]§ 63.567(k)	§ 63.562(c)(1) § 63.562(e)(7)(ii) [G]§ 63.567(b)(2) § 63.567(b)(3) [G]§ 63.567(b)(4) § 63.567(c) § 63.567(e)(1) [G]§ 63.567(e)(2) § 63.567(e)(3) § 63.567(e)(4) § 63.567(e)(5) § 63.567(e)(6) § 63.567(f) § 63.567(j)(3) § 63.567(m) § 63.567(n)(1) § 63.567(n)(2)
DOCK34	EU	R5211-0226	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.212(a)(6)(A) § 115.212(a)(6)(B) [G]§ 115.212(a)(6)(C) § 115.212(a)(6)(D) [G]§ 115.214(a)(3)(A) § 115.214(a)(3)(C) § 115.214(a)(3)(D) § 115.214(a)(3)(E)	Emissions shall not exceed 0.09lb/1,000gal loaded, or the vapor control system shall maintain a control efficiency of at least 90%, or a vapor balance system or pressurized loading may be used.	[G]§ 115.214(a)(3)(A) § 115.214(a)(3)(B) § 115.214(a)(3)(B)(i) § 115.214(a)(3)(B)(ii) § 115.214(a)(3)(B)(iii) § 115.214(a)(3)(D) § 115.215 § 115.215(1) § 115.215(10) [G]§ 115.215(2) § 115.215(4) § 115.215(5) § 115.215(7) § 115.215(8) § 115.215(9) § 115.216(1) § 115.216(1)(A) § 115.216(1)(A)(i) ** See CAM Summary	[G]§ 115.214(a)(3)(A) § 115.214(a)(3)(D) § 115.216 § 115.216(1) § 115.216(1)(A) § 115.216(1)(A)(i) § 115.216(2) [G]§ 115.216(4)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
DOCK34	EU	61BB-0012	Benzene	40 CFR Part 61, Subpart BB	[G]§ 61.302(a) § 61.302(b) § 61.302(f) § 61.302(g) § 61.302(j) § 61.302(k)	Equip each loading rack with vapor collection system to collect all displaced benzene vapors and prevent it from passing from one loading rack through another to the atmosphere. § 61.302(a)(1)-(2)	§ 61.302(k) § 61.303(a) § 61.303(a)(1) § 61.304(a)(1) § 61.304(a)(2) § 61.304(a)(4) § 61.304(a)(4)(i) § 61.304(a)(4)(ii) § 61.304(a)(4)(iii) § 61.304(a)(4)(iv) § 61.304(a)(5) § 61.304(a)(6) § 61.304(a)(7) § 61.304(d)(1) § 61.304(d)(2) § 61.304(d)(3) § 61.304(e) ** See CAM Summary	§ 61.304(a)(4)(i) § 61.304(d)(3) § 61.305(a) [G]§ 61.305(a)(1) § 61.305(b) § 61.305(b)(1)	§ 61.305(a) § 61.305(a)(5) § 61.305(b) § 61.305(b)(1) § 61.305(f) § 61.305(f)(1)
DOCK34	EU	63CC-2502	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.651(a)	Except as provided in §63.651(b)-(d), each owner or operator of a marine tank vessel loading operation located at a petroleum refinery shall comply with the requirements of §63.560 through §63.567.	§ 63.642(d)(1) § 63.642(d)(3) § 63.642(d)(4)	§ 63.642(e) § 63.655(c) § 63.655(i)(5)	§ 63.640(l) § 63.640(l)(3) § 63.640(l)(3)(i) § 63.640(l)(3)(iii) § 63.640(l)(3)(iv) § 63.640(l)(3)(v) § 63.640(l)(3)(vi) § 63.640(l)(3)(vii) § 63.642(d)(2) § 63.642(f) § 63.655(c) § 63.655(e) § 63.655(e)(1) § 63.655(f)
DOCK34	EU	63Y-0465	112(B) HAPS	40 CFR Part 63, Subpart Y	§ 63.562(b) [G]§ 63.562(b)(1) § 63.562(b)(2) [G]§ 63.562(b)(6) § 63.562(e) § 63.562(e)(1)	Marine tank vessel loading operations shall apply MACT standards, except for the VMT source.	[G]§ 63.562(b)(6) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) § 63.563(b) § 63.563(b)(1) § 63.563(b)(10)	[G]§ 63.562(b)(6) § 63.562(e)(5) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) § 63.564(b)(1) § 63.564(e)(3)	[G]§ 63.562(b)(6) § 63.562(e)(7)(ii) § 63.567(b)(5) § 63.567(c) § 63.567(e)(1) [G]§ 63.567(e)(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 63.562(e)(2) [G]§ 63.562(e)(3) § 63.562(e)(4) § 63.562(e)(5) § 63.562(e)(6) § 63.562(e)(7) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) [G]§ 63.563(a)(1) § 63.563(a)(2) § 63.563(a)(3)		§ 63.563(b)(3) § 63.563(b)(4) § 63.563(b)(4)(ii) [G]§ 63.563(c) § 63.564(a)(2) § 63.564(a)(3) § 63.564(a)(4) § 63.564(b)(1) § 63.564(c) § 63.564(e)(3) § 63.564(e)(4) [G]§ 63.565(b) [G]§ 63.565(d) § 63.565(f) § 63.565(f)(2) § 63.565(l)	[G]§ 63.565(d) § 63.567(f) [G]§ 63.567(g) § 63.567(j)(1) § 63.567(j)(2) § 63.567(j)(4) [G]§ 63.567(k)	§ 63.567(e)(3) § 63.567(e)(4) § 63.567(e)(5) § 63.567(e)(6) § 63.567(f) § 63.567(j)(3) § 63.567(m) § 63.567(n)(1) § 63.567(n)(2)
DOCK34	EU	63Y-1665	112(B) HAPS	40 CFR Part 63, Subpart Y	§ 63.562(b) [G]§ 63.562(b)(1) § 63.562(b)(2) [G]§ 63.562(b)(6) § 63.562(e) § 63.562(e)(1) [G]§ 63.562(e)(2) [G]§ 63.562(e)(3) § 63.562(e)(4) § 63.562(e)(5) § 63.562(e)(6) § 63.562(e)(7) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) [G]§ 63.563(a)(1) § 63.563(a)(2) § 63.563(a)(3)	Marine tank vessel loading operations shall apply MACT standards, except for the VMT source.	[G]§ 63.562(b)(6) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) § 63.563(b) § 63.563(b)(1) § 63.563(b)(10) § 63.563(b)(3) § 63.563(b)(4) § 63.563(b)(4)(ii) [G]§ 63.563(c) § 63.564(a)(2) § 63.564(a)(3) § 63.564(a)(4) § 63.564(b)(1) § 63.564(c) § 63.564(e)(3) § 63.564(e)(4) [G]§ 63.565(b) [G]§ 63.565(d) § 63.565(f) § 63.565(f)(2) § 63.565(l)	[G]§ 63.562(b)(6) § 63.562(e)(5) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) § 63.564(b)(1) § 63.564(e)(3) [G]§ 63.565(d) § 63.567(f) [G]§ 63.567(g) § 63.567(j)(1) § 63.567(j)(2) § 63.567(j)(4) [G]§ 63.567(k)	[G]§ 63.562(b)(6) § 63.562(e)(7)(ii) § 63.567(b)(5) § 63.567(c) § 63.567(e)(1) [G]§ 63.567(e)(2) § 63.567(e)(3) § 63.567(e)(4) § 63.567(e)(5) § 63.567(e)(6) § 63.567(f) § 63.567(j)(3) § 63.567(m) § 63.567(n)(1) § 63.567(n)(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
DOCK34	EU	63Y-1665	VOC	40 CFR Part 63, Subpart Y	§ 63.562(c) [G]§ 63.562(c)(2) § 63.562(c)(3) § 63.562(c)(4) [G]§ 63.562(c)(6) § 63.562(e) § 63.562(e)(1) [G]§ 63.562(e)(2) [G]§ 63.562(e)(3) § 63.562(e)(4) § 63.562(e)(5) § 63.562(e)(6) § 63.562(e)(7) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) [G]§ 63.563(a)(1) § 63.563(a)(2) § 63.563(a)(3)	RACT standards, except the VMT source.	[G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) § 63.563(b) § 63.563(b)(1) § 63.563(b)(3) § 63.563(b)(4) § 63.563(b)(4)(ii) [G]§ 63.563(c) § 63.564(a)(2) § 63.564(a)(3) § 63.564(a)(4) § 63.564(b)(1) § 63.564(c) § 63.564(e)(3) § 63.564(e)(4) [G]§ 63.565(b) [G]§ 63.565(d) § 63.565(f) § 63.565(f)(2) § 63.565(l)	§ 63.562(e)(5) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) § 63.564(b)(1) § 63.564(e)(3) [G]§ 63.565(d) § 63.567(f) [G]§ 63.567(g) § 63.567(j)(1) § 63.567(j)(2) § 63.567(j)(4) [G]§ 63.567(k)	§ 63.562(c)(1) § 63.562(e)(7)(ii) [G]§ 63.567(b)(2) § 63.567(b)(3) [G]§ 63.567(b)(4) § 63.567(c) § 63.567(e)(1) [G]§ 63.567(e)(2) § 63.567(e)(3) § 63.567(e)(4) § 63.567(e)(5) § 63.567(e)(6) § 63.567(f) § 63.567(j)(3) § 63.567(m) § 63.567(n)(1) § 63.567(n)(2)
DOCK37	EU	R5211-0226	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.212(a)(6)(A) § 115.212(a)(6)(B) [G]§ 115.212(a)(6)(C) § 115.212(a)(6)(D) [G]§ 115.214(a)(3)(A) § 115.214(a)(3)(C) § 115.214(a)(3)(D) § 115.214(a)(3)(E)	Emissions shall not exceed 0.09lb/1,000gal loaded, or the vapor control system shall maintain a control efficiency of at least 90%, or a vapor balance system or pressurized loading may be used.	[G]§ 115.214(a)(3)(A) § 115.214(a)(3)(B) § 115.214(a)(3)(B)(i) § 115.214(a)(3)(B)(ii) § 115.214(a)(3)(B)(iii) § 115.214(a)(3)(D) § 115.215 § 115.215(1) § 115.215(10) [G]§ 115.215(2) § 115.215(4) § 115.215(5) § 115.215(7) § 115.215(8) § 115.215(9) § 115.216(1) § 115.216(1)(A) § 115.216(1)(A)(i) ** See CAM Summary	[G]§ 115.214(a)(3)(A) § 115.214(a)(3)(D) § 115.216 § 115.216(1) § 115.216(1)(A) § 115.216(1)(A)(i) § 115.216(2) [G]§ 115.216(4)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
DOCK37	EU	61BB-0012	Benzene	40 CFR Part 61, Subpart BB	[G]§ 61.302(a) § 61.302(b) § 61.302(f) § 61.302(g) § 61.302(j) § 61.302(k)	Equip each loading rack with vapor collection system to collect all displaced benzene vapors and prevent it from passing from one loading rack through another to the atmosphere. § 61.302(a)(1)-(2)	§ 61.302(k) § 61.303(a) § 61.303(a)(1) § 61.304(a)(1) § 61.304(a)(2) § 61.304(a)(4) § 61.304(a)(4)(i) § 61.304(a)(4)(ii) § 61.304(a)(4)(iii) § 61.304(a)(4)(iv) § 61.304(a)(5) § 61.304(a)(6) § 61.304(a)(7) § 61.304(d)(1) § 61.304(d)(2) § 61.304(d)(3) § 61.304(e) ** See CAM Summary	§ 61.304(a)(4)(i) § 61.304(d)(3) § 61.305(a) [G]§ 61.305(a)(1) § 61.305(b) § 61.305(b)(1)	§ 61.305(a) § 61.305(a)(5) § 61.305(b) § 61.305(b)(1) § 61.305(f) § 61.305(f)(1)
DOCK37	EU	63CC-2502	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.651(a)	Except as provided in §63.651(b)-(d), each owner or operator of a marine tank vessel loading operation located at a petroleum refinery shall comply with the requirements of §63.560 through §63.567.	§ 63.642(d)(1) § 63.642(d)(3) § 63.642(d)(4)	§ 63.642(e) § 63.655(c) § 63.655(i)(5)	§ 63.640(l) § 63.640(l)(3) § 63.640(l)(3)(i) § 63.640(l)(3)(iii) § 63.640(l)(3)(iv) § 63.640(l)(3)(v) § 63.640(l)(3)(vi) § 63.640(l)(3)(vii) § 63.642(d)(2) § 63.642(f) § 63.655(c) § 63.655(e) § 63.655(e)(1) § 63.655(f)
DOCK37	EU	63Y-0465	112(B) HAPS	40 CFR Part 63, Subpart Y	§ 63.562(b) [G]§ 63.562(b)(1) § 63.562(b)(2) [G]§ 63.562(b)(6) § 63.562(e) § 63.562(e)(1)	Marine tank vessel loading operations shall apply MACT standards, except for the VMT source.	[G]§ 63.562(b)(6) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) § 63.563(b) § 63.563(b)(1) § 63.563(b)(10)	[G]§ 63.562(b)(6) § 63.562(e)(5) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) § 63.564(b)(1) § 63.564(e)(3)	[G]§ 63.562(b)(6) § 63.562(e)(7)(ii) § 63.567(b)(5) § 63.567(c) § 63.567(e)(1) [G]§ 63.567(e)(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 63.562(e)(2) [G]§ 63.562(e)(3) § 63.562(e)(4) § 63.562(e)(5) § 63.562(e)(6) § 63.562(e)(7) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) [G]§ 63.563(a)(1) § 63.563(a)(2) § 63.563(a)(3)		§ 63.563(b)(3) § 63.563(b)(4) § 63.563(b)(4)(ii) [G]§ 63.563(c) § 63.564(a)(2) § 63.564(a)(3) § 63.564(a)(4) § 63.564(b)(1) § 63.564(c) § 63.564(e)(3) § 63.564(e)(4) [G]§ 63.565(b) [G]§ 63.565(d) § 63.565(f) § 63.565(f)(2) § 63.565(l)	[G]§ 63.565(d) § 63.567(f) [G]§ 63.567(g) § 63.567(j)(1) § 63.567(j)(2) § 63.567(j)(4) [G]§ 63.567(k)	§ 63.567(e)(3) § 63.567(e)(4) § 63.567(e)(5) § 63.567(e)(6) § 63.567(f) § 63.567(j)(3) § 63.567(m) § 63.567(n)(1) § 63.567(n)(2)
DOCK37	EU	63Y-1665	112(B) HAPS	40 CFR Part 63, Subpart Y	§ 63.562(b) [G]§ 63.562(b)(1) § 63.562(b)(2) [G]§ 63.562(b)(6) § 63.562(e) § 63.562(e)(1) [G]§ 63.562(e)(2) [G]§ 63.562(e)(3) § 63.562(e)(4) § 63.562(e)(5) § 63.562(e)(6) § 63.562(e)(7) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) [G]§ 63.563(a)(1) § 63.563(a)(2) § 63.563(a)(3)	Marine tank vessel loading operations shall apply MACT standards, except for the VMT source.	[G]§ 63.562(b)(6) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) § 63.563(b) § 63.563(b)(1) § 63.563(b)(10) § 63.563(b)(3) § 63.563(b)(4) § 63.563(b)(4)(ii) [G]§ 63.563(c) § 63.564(a)(2) § 63.564(a)(3) § 63.564(a)(4) § 63.564(b)(1) § 63.564(c) § 63.564(e)(3) § 63.564(e)(4) [G]§ 63.565(b) [G]§ 63.565(d) § 63.565(f) § 63.565(f)(2) § 63.565(l)	[G]§ 63.562(b)(6) § 63.562(e)(5) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) § 63.564(b)(1) § 63.564(e)(3) [G]§ 63.565(d) § 63.567(f) [G]§ 63.567(g) § 63.567(j)(1) § 63.567(j)(2) § 63.567(j)(4) [G]§ 63.567(k)	[G]§ 63.562(b)(6) § 63.562(e)(7)(ii) § 63.567(b)(5) § 63.567(c) § 63.567(e)(1) [G]§ 63.567(e)(2) § 63.567(e)(3) § 63.567(e)(4) § 63.567(e)(5) § 63.567(e)(6) § 63.567(f) § 63.567(j)(3) § 63.567(m) § 63.567(n)(1) § 63.567(n)(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
DOCK37	EU	63Y-1665	VOC	40 CFR Part 63, Subpart Y	§ 63.562(c) [G]§ 63.562(c)(2) § 63.562(c)(3) § 63.562(c)(4) [G]§ 63.562(c)(6) § 63.562(e) § 63.562(e)(1) [G]§ 63.562(e)(2) [G]§ 63.562(e)(3) § 63.562(e)(4) § 63.562(e)(5) § 63.562(e)(6) § 63.562(e)(7) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) [G]§ 63.563(a)(1) § 63.563(a)(2) § 63.563(a)(3)	RACT standards, except the VMT source.	[G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) § 63.563(b) § 63.563(b)(1) § 63.563(b)(3) § 63.563(b)(4) § 63.563(b)(4)(ii) [G]§ 63.563(c) § 63.564(a)(2) § 63.564(a)(3) § 63.564(a)(4) § 63.564(b)(1) § 63.564(c) § 63.564(e)(3) § 63.564(e)(4) [G]§ 63.565(b) [G]§ 63.565(d) § 63.565(f) § 63.565(f)(2) § 63.565(l)	§ 63.562(e)(5) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) § 63.564(b)(1) § 63.564(e)(3) [G]§ 63.565(d) § 63.567(f) [G]§ 63.567(g) § 63.567(j)(1) § 63.567(j)(2) § 63.567(j)(4) [G]§ 63.567(k)	§ 63.562(c)(1) § 63.562(e)(7)(ii) [G]§ 63.567(b)(2) § 63.567(b)(3) [G]§ 63.567(b)(4) § 63.567(c) § 63.567(e)(1) [G]§ 63.567(e)(2) § 63.567(e)(3) § 63.567(e)(4) § 63.567(e)(5) § 63.567(e)(6) § 63.567(f) § 63.567(j)(3) § 63.567(m) § 63.567(n)(1) § 63.567(n)(2)
DOCK38	EU	R5211-0226	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.212(a)(6)(A) § 115.212(a)(6)(B) [G]§ 115.212(a)(6)(C) § 115.212(a)(6)(D) [G]§ 115.214(a)(3)(A) § 115.214(a)(3)(C) § 115.214(a)(3)(D) § 115.214(a)(3)(E)	Emissions shall not exceed 0.09lb/1,000gal loaded, or the vapor control system shall maintain a control efficiency of at least 90%, or a vapor balance system or pressurized loading may be used.	[G]§ 115.214(a)(3)(A) § 115.214(a)(3)(B) § 115.214(a)(3)(B)(i) § 115.214(a)(3)(B)(ii) § 115.214(a)(3)(B)(iii) § 115.214(a)(3)(D) § 115.215 § 115.215(1) § 115.215(10) [G]§ 115.215(2) § 115.215(4) § 115.215(5) § 115.215(7) § 115.215(8) § 115.215(9) § 115.216(1) § 115.216(1)(A) § 115.216(1)(A)(i) ** See CAM Summary	[G]§ 115.214(a)(3)(A) § 115.214(a)(3)(D) § 115.216 § 115.216(1) § 115.216(1)(A) § 115.216(1)(A)(i) § 115.216(2) [G]§ 115.216(4)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
DOCK38	EU	61BB-0012	Benzene	40 CFR Part 61, Subpart BB	[G]§ 61.302(a) § 61.302(b) § 61.302(f) § 61.302(g) § 61.302(j) § 61.302(k)	Equip each loading rack with vapor collection system to collect all displaced benzene vapors and prevent it from passing from one loading rack through another to the atmosphere. § 61.302(a)(1)-(2)	§ 61.302(k) § 61.303(a) § 61.303(a)(1) § 61.304(a)(1) § 61.304(a)(2) § 61.304(a)(4) § 61.304(a)(4)(i) § 61.304(a)(4)(ii) § 61.304(a)(4)(iii) § 61.304(a)(4)(iv) § 61.304(a)(5) § 61.304(a)(6) § 61.304(a)(7) § 61.304(d)(1) § 61.304(d)(2) § 61.304(d)(3) § 61.304(e) ** See CAM Summary	§ 61.304(a)(4)(i) § 61.304(d)(3) § 61.305(a) [G]§ 61.305(a)(1) § 61.305(b) § 61.305(b)(1)	§ 61.305(a) § 61.305(a)(5) § 61.305(b) § 61.305(b)(1) § 61.305(f) § 61.305(f)(1)
DOCK38	EU	63CC-2502	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.651(a)	Except as provided in §63.651(b)-(d), each owner or operator of a marine tank vessel loading operation located at a petroleum refinery shall comply with the requirements of §63.560 through §63.567.	§ 63.642(d)(1) § 63.642(d)(3) § 63.642(d)(4)	§ 63.642(e) § 63.655(c) § 63.655(i)(5)	§ 63.640(l) § 63.640(l)(3) § 63.640(l)(3)(i) § 63.640(l)(3)(iii) § 63.640(l)(3)(iv) § 63.640(l)(3)(v) § 63.640(l)(3)(vi) § 63.640(l)(3)(vii) § 63.642(d)(2) § 63.642(f) § 63.655(c) § 63.655(e) § 63.655(e)(1) § 63.655(f)
DOCK38	EU	63Y-0465	112(B) HAPS	40 CFR Part 63, Subpart Y	§ 63.562(b) [G]§ 63.562(b)(1) § 63.562(b)(2) [G]§ 63.562(b)(6) § 63.562(e) § 63.562(e)(1)	Marine tank vessel loading operations shall apply MACT standards, except for the VMT source.	[G]§ 63.562(b)(6) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) § 63.563(b) § 63.563(b)(1) § 63.563(b)(10)	[G]§ 63.562(b)(6) § 63.562(e)(5) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) § 63.564(b)(1) § 63.564(e)(3)	[G]§ 63.562(b)(6) § 63.562(e)(7)(ii) § 63.567(b)(5) § 63.567(c) § 63.567(e)(1) [G]§ 63.567(e)(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 63.562(e)(2) [G]§ 63.562(e)(3) § 63.562(e)(4) § 63.562(e)(5) § 63.562(e)(6) § 63.562(e)(7) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) [G]§ 63.563(a)(1) § 63.563(a)(2) § 63.563(a)(3)		§ 63.563(b)(3) § 63.563(b)(4) § 63.563(b)(4)(ii) [G]§ 63.563(c) § 63.564(a)(2) § 63.564(a)(3) § 63.564(a)(4) § 63.564(b)(1) § 63.564(c) § 63.564(e)(3) § 63.564(e)(4) [G]§ 63.565(b) [G]§ 63.565(d) § 63.565(f) § 63.565(f)(2) § 63.565(l)	[G]§ 63.565(d) § 63.567(f) [G]§ 63.567(g) § 63.567(j)(1) § 63.567(j)(2) § 63.567(j)(4) [G]§ 63.567(k)	§ 63.567(e)(3) § 63.567(e)(4) § 63.567(e)(5) § 63.567(e)(6) § 63.567(f) § 63.567(j)(3) § 63.567(m) § 63.567(n)(1) § 63.567(n)(2)
DOCK38	EU	63Y-1665	112(B) HAPS	40 CFR Part 63, Subpart Y	§ 63.562(b) [G]§ 63.562(b)(1) § 63.562(b)(2) [G]§ 63.562(b)(6) § 63.562(e) § 63.562(e)(1) [G]§ 63.562(e)(2) [G]§ 63.562(e)(3) § 63.562(e)(4) § 63.562(e)(5) § 63.562(e)(6) § 63.562(e)(7) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) [G]§ 63.563(a)(1) § 63.563(a)(2) § 63.563(a)(3)	Marine tank vessel loading operations shall apply MACT standards, except for the VMT source.	[G]§ 63.562(b)(6) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) § 63.563(b) § 63.563(b)(1) § 63.563(b)(10) § 63.563(b)(3) § 63.563(b)(4) § 63.563(b)(4)(ii) [G]§ 63.563(c) § 63.564(a)(2) § 63.564(a)(3) § 63.564(a)(4) § 63.564(b)(1) § 63.564(c) § 63.564(e)(3) § 63.564(e)(4) [G]§ 63.565(b) [G]§ 63.565(d) § 63.565(f) § 63.565(f)(2) § 63.565(l)	[G]§ 63.562(b)(6) § 63.562(e)(5) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) § 63.564(b)(1) § 63.564(e)(3) [G]§ 63.565(d) § 63.567(f) [G]§ 63.567(g) § 63.567(j)(1) § 63.567(j)(2) § 63.567(j)(4) [G]§ 63.567(k)	[G]§ 63.562(b)(6) § 63.562(e)(7)(ii) § 63.567(b)(5) § 63.567(c) § 63.567(e)(1) [G]§ 63.567(e)(2) § 63.567(e)(3) § 63.567(e)(4) § 63.567(e)(5) § 63.567(e)(6) § 63.567(f) § 63.567(j)(3) § 63.567(m) § 63.567(n)(1) § 63.567(n)(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
DOCK38	EU	63Y-1665	VOC	40 CFR Part 63, Subpart Y	§ 63.562(c) [G]§ 63.562(c)(2) § 63.562(c)(3) § 63.562(c)(4) [G]§ 63.562(c)(6) § 63.562(e) § 63.562(e)(1) [G]§ 63.562(e)(2) [G]§ 63.562(e)(3) § 63.562(e)(4) § 63.562(e)(5) § 63.562(e)(6) § 63.562(e)(7) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) [G]§ 63.563(a)(1) § 63.563(a)(2) § 63.563(a)(3)	RACT standards, except the VMT source.	[G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) § 63.563(b) § 63.563(b)(1) § 63.563(b)(3) § 63.563(b)(4) § 63.563(b)(4)(ii) [G]§ 63.563(c) § 63.564(a)(2) § 63.564(a)(3) § 63.564(a)(4) § 63.564(b)(1) § 63.564(c) § 63.564(e)(3) § 63.564(e)(4) [G]§ 63.565(b) [G]§ 63.565(d) § 63.565(f) § 63.565(f)(2) § 63.565(l)	§ 63.562(e)(5) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) § 63.564(b)(1) § 63.564(e)(3) [G]§ 63.565(d) § 63.567(f) [G]§ 63.567(g) § 63.567(j)(1) § 63.567(j)(2) § 63.567(j)(4) [G]§ 63.567(k)	§ 63.562(c)(1) § 63.562(e)(7)(ii) [G]§ 63.567(b)(2) § 63.567(b)(3) [G]§ 63.567(b)(4) § 63.567(c) § 63.567(e)(1) [G]§ 63.567(e)(2) § 63.567(e)(3) § 63.567(e)(4) § 63.567(e)(5) § 63.567(e)(6) § 63.567(f) § 63.567(j)(3) § 63.567(m) § 63.567(n)(1) § 63.567(n)(2)
DOCK40-41	EU	R55211-0207	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(a)(5)(B) § 115.212(a)(6)(D) § 115.214(a)(3)(C) § 115.214(a)(3)(G) § 115.214(a)(3)(G)(i) § 115.217(a)(5)(B)(iii)	The marine vessel transfer operations specified in § 115.217(a)(5)(B)(i)-(iv) are exempt from the requirements of §§ 115.212(a), 115.214(a), and 115.216 of this title, except as noted.	§ 115.214(a)(3)(B) § 115.214(a)(3)(B)(i) § 115.215 § 115.215(4)	§ 115.216 § 115.216(2)	None
DOCK40-41	EU	R55211-0207	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(a)(5)(B) § 115.214(a)(3)(C) § 115.214(a)(3)(G) § 115.214(a)(3)(G)(i) § 115.217(a)(5)(B)(i)	The marine vessel transfer operations specified in § 115.217(a)(5)(B)(i)-(iv) are exempt from the requirements of §§ 115.212(a), 115.214(a), and 115.216 of this title, except as noted.	§ 115.214(a)(3)(B) § 115.214(a)(3)(B)(i)	§ 115.216 § 115.216(2)	None
DOCK40-41	EU	61BB-0002	Benzene	40 CFR Part 61, Subpart BB	§ 61.300(b)	Any affected facility as per § 61.300(a), loading only	None	[G]§ 61.305(i)	[G]§ 61.305(i)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						liquid containing < 70 weight-percent benzene is exempt from this subpart, except for the recordkeeping and reporting in § 61.305(i).			
DOCK54LOAD	EU	R5211-0225	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.212(a)(6)(A) § 115.212(a)(6)(B) [G]§ 115.212(a)(6)(C) § 115.212(a)(6)(D) [G]§ 115.214(a)(3)(A) § 115.214(a)(3)(C) § 115.214(a)(3)(D) § 115.214(a)(3)(E)	Emissions shall not exceed 0.09lb/1,000gal loaded, or the vapor control system shall maintain a control efficiency of at least 90%, or a vapor balance system or pressurized loading may be used.	[G]§ 115.214(a)(3)(A) § 115.214(a)(3)(B) § 115.214(a)(3)(B)(i) § 115.214(a)(3)(B)(ii) § 115.214(a)(3)(B)(iii) § 115.214(a)(3)(D) § 115.215 § 115.215(1) § 115.215(10) [G]§ 115.215(2) § 115.215(4) § 115.215(5) § 115.215(7) § 115.215(8) § 115.215(9) § 115.216(1) § 115.216(1)(A) § 115.216(1)(A)(i) ** See CAM Summary	[G]§ 115.214(a)(3)(A) § 115.214(a)(3)(D) § 115.216 § 115.216(1) § 115.216(1)(A) § 115.216(1)(A)(i) § 115.216(2) [G]§ 115.216(4)	None
DOCK54LOAD	EU	61BB-0012	Benzene	40 CFR Part 61, Subpart BB	[G]§ 61.302(a) § 61.302(b) § 61.302(f) § 61.302(g) § 61.302(j) § 61.302(k)	Equip each loading rack with vapor collection system to collect all displaced benzene vapors and prevent it from passing from one loading rack through another to the atmosphere. § 61.302(a)(1)-(2)	§ 61.302(k) § 61.303(a) § 61.303(a)(1) § 61.304(a)(1) § 61.304(a)(2) § 61.304(a)(4) § 61.304(a)(4)(i) § 61.304(a)(4)(ii) § 61.304(a)(4)(iii) § 61.304(a)(4)(iv) § 61.304(a)(5) § 61.304(a)(6) § 61.304(a)(7)	§ 61.304(a)(4)(i) § 61.304(d)(3) § 61.305(a) [G]§ 61.305(a)(1) § 61.305(b) § 61.305(b)(1)	§ 61.305(a) § 61.305(a)(5) § 61.305(b) § 61.305(b)(1) § 61.305(f) § 61.305(f)(1)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 61.304(d)(1) § 61.304(d)(2) § 61.304(d)(3) § 61.304(e) ** See CAM Summary		
DOCK54LOAD	EU	63Y-0391	112(B) HAPS	40 CFR Part 63, Subpart Y	§ 63.562(b) [G]§ 63.562(b)(1) § 63.562(b)(2) [G]§ 63.562(b)(6) § 63.562(e) § 63.562(e)(1) [G]§ 63.562(e)(2) [G]§ 63.562(e)(3) § 63.562(e)(4) § 63.562(e)(5) § 63.562(e)(6) § 63.562(e)(7) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) § 63.563(a)(2) § 63.563(a)(3)	Marine tank vessel loading operations shall apply MACT standards, except for the VMT source.	[G]§ 63.562(b)(6) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) § 63.563(b) § 63.563(b)(1) § 63.563(b)(10) § 63.563(b)(3) § 63.563(b)(4) § 63.563(b)(4)(ii) [G]§ 63.563(c) § 63.564(a)(2) § 63.564(a)(3) § 63.564(a)(4) § 63.564(c) § 63.564(e)(2) § 63.564(e)(4) [G]§ 63.565(b) [G]§ 63.565(d) § 63.565(f) § 63.565(f)(1) § 63.565(l)	[G]§ 63.562(b)(6) § 63.562(e)(5) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) § 63.564(e)(2) [G]§ 63.565(d) § 63.567(f) [G]§ 63.567(g) § 63.567(j)(1) § 63.567(j)(2) [G]§ 63.567(k)	[G]§ 63.562(b)(6) § 63.562(e)(7)(ii) § 63.567(b)(5)(ii) § 63.567(c) § 63.567(e)(1) [G]§ 63.567(e)(2) § 63.567(e)(3) § 63.567(e)(4) § 63.567(e)(5) § 63.567(e)(6) § 63.567(f) § 63.567(j)(3) § 63.567(m) § 63.567(n)(1) § 63.567(n)(2)
EMERGEN	EU	R7300-0005	Exempt	30 TAC Chapter 117, Subchapter B	§ 117.303(a)(6)(D) [G]§ 117.310(f)	Units exempted from the provisions of this division, except as specified in §§117.310(f), 117.340(j), 117.345(f)(6) and (10), 117.350(c)(1), and 117.354(a)(5), include stationary gas turbines and stationary internal combustion engines that are used exclusively in emergency situations,	[G]§ 117.8140(a) § 117.8140(b)	§ 117.340(j) [G]§ 117.345(f)(10) [G]§ 117.345(f)(6)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						except that operation for testing or maintenance purposes is allowed for up to 52 hours per year, based on a rolling 12-month average.			
EMERGEN	EU	63ZZZZ-0001	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6602-Table2c.1 § 63.6595(a)(1) § 63.6605(a) § 63.6605(b) § 63.6625(e) § 63.6625(h) § 63.6625(i) § 63.6640(b) § 63.6640(f)(1) [G]§ 63.6640(f)(2) § 63.6640(f)(3)	For each existing emergency stationary CI RICE and black start stationary CI RICE, located at a major source, you must comply with the requirements as specified in Table 2c.1.a-c.	§ 63.6625(f) § 63.6625(i) § 63.6640(a) § 63.6640(a)-Table6.9.a.i § 63.6640(a)-Table6.9.a.ii § 63.6640(b)	§ 63.6625(i) § 63.6655(a) § 63.6655(a)(1) § 63.6655(d) § 63.6655(e) § 63.6655(f) § 63.6660(a) § 63.6660(b) § 63.6660(c)	§ 63.6640(b) § 63.6640(e) § 63.6650(f)
ENVFC-FUG1	EU	60GGGa-01	VOC	40 CFR Part 60, Subpart GGGa	[G]§ 60.590a(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 60, Subpart GGGa
ENVFP-SEP	EU	R5131-0010	VOC	30 TAC Chapter 115, Water Separation	§ 115.132(a)(3) § 115.131(a)	VOC water separator compartments must be equipped with a vapor recovery system which satisfies the provisions of §115.131(a) of this title.	[G]§ 115.135(a) § 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	§ 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	None
ENVFP-SEP	EU	61FF-1781	Benzene	40 CFR Part 61, Subpart FF	§ 61.347(a)(1) § 61.347(a)(1)(i)(A) § 61.347(a)(1)(i)(B) § 61.347(b)	Install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors	§ 61.347(a)(1)(i)(A) § 61.347(b) § 61.349(a)(1)(i) § 61.349(a)(1)(ii)	§ 61.349(a)(1)(ii) § 61.356(d) § 61.356(f) § 61.356(f)(1)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 61.347(c) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	vented from the oil-water separator to a control device.	§ 61.349(e) § 61.349(f) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i)	
EPN-34A	EP	R1111-0197	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(A) § 111.111(a)(1)(E) § 111.111(a)(3)	Visible emissions from any stationary vent shall not exceed an opacity of 30% averaged over a six minute period.	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None
EPN-93	EP	R1111-0193	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(B) § 111.111(a)(1)(C) § 111.111(a)(1)(E) § 111.111(a)(2)	Visible emissions from any stationary vent shall not exceed an opacity of 20% averaged over a six minute period for any source on which construction was begun after January 31, 1972.	§ 111.111(a)(1)(D) [G]§ 111.111(a)(1)(F) § 111.111(a)(2)	§ 111.111(a)(1)(C) § 111.111(a)(1)(D)	None
EPN-REFWWV	CD	61FF-IDS1	Benzene	40 CFR Part 61, Subpart FF	§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(i)(A) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	For each closed-vent system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(c) § 61.354(c)(2) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.349(a)(1)(ii) § 61.354(c) § 61.354(c)(2) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(B) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(2) § 61.356(j)(3)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(B)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
								§ 61.356(j)(3)(i) § 61.356(j)(5)	
EPN-REFWWV	CD	61FF-IDS2	Benzene	40 CFR Part 61, Subpart FF	§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(i)(C) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	For each closed-vent system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(c) § 61.354(c)(2) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.349(a)(1)(ii) § 61.354(c) § 61.354(c)(2) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(B) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i) § 61.356(j)(5)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(B)
ESBGEN	EU	R7300-0004	Exempt	30 TAC Chapter 117, Subchapter B	[G]§ 117.303(a)(11) [G]§ 117.310(f)	Units exempted from the provisions of this division except as specified in §§117.310(f), 117.340(j), 117.345(f)(6) and (10), 117.350(c)(1) and 117.354(a)(5) include new, modified, reconstructed, or relocated stationary diesel engine placed into service on or after October 1, 2001, that operates less than 100 hours per year, based on a rolling 12-month average, in other than emergency situations; and meets the requirements for non-road engines as specified. §117.303(a)(11)(A)-(B)	None	§ 117.340(j) [G]§ 117.345(f)(10) [G]§ 117.345(f)(6)	None
ESBGEN	EU	60IIII-0006	CO	40 CFR Part 60, Subpart IIII	§ 60.4205(b) § 60.4202(a)(2)	Owners and operators of emergency stationary CI	None	None	[G]§ 60.4214(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218 § 89.112(a)	ICE, that are not fire pump engines, with a maximum engine power greater than or equal to 130 KW and less than or equal to 2237 KW and a displacement of less than 10 liters per cylinder and is a 2007 model year and later must comply with a CO emission limit of 3.5 g/KW-hr, as stated in 40 CFR 60.4202(a)(2) and 40 CFR 89.112(a).			
ESBGEN	EU	60IIII-0006	NMHC and NO_X	40 CFR Part 60, Subpart IIII	§ 60.4205(b) § 60.4202(a)(2) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218 § 89.112(a)	Owners and operators of emergency stationary CI ICE, that are not fire pump engines, with a maximum engine power greater than or equal to 75 KW and less than or equal to 560 KW and a displacement of less than 10 liters per cylinder and is a 2007 model year and later must comply with an NMHC+NOx emission limit of 4.0 g/KW-hr, as stated in 40 CFR 60.4202(a)(2) and 40 CFR 89.112(a).	None	None	[G]§ 60.4214(d)
ESBGEN	EU	60IIII-0006	PM (Opacity)	40 CFR Part 60, Subpart IIII	§ 60.4205(b) § 60.4202(a)(2) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218 § 89.113(a)(1)	Emergency stationary CI ICE, that are not fire pump engines, with displacement < 10 lpc and not constant-speed engines, with max engine power < 2237 KW and a 2007 model year and later or max engine power > 2237 KW and a 2011 model	None	None	[G]§ 60.4214(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 89.113(a)(2) § 89.113(a)(3)	year and later, must comply with following opacity emission limits: 20% during acceleration, 15% during lugging, 50% during peaks in either acceleration or lugging modes as stated in §60.4202(a)(1)-(2), (b)(2) and §89.113(a)(1)-(3) and §1039.105(b)(1)-(3).			
ESBGEN	EU	60IIII-0006	PM	40 CFR Part 60, Subpart IIII	§ 60.4205(b) § 60.4202(a)(2) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218 § 89.112(a)	Owners and operators of emergency stationary CI ICE, that are not fire pump engines, with a maximum engine power greater than or equal to 130 KW and less than or equal to 2237 KW and a displacement of less than 10 liters per cylinder and is a 2007 model year and later must comply with a PM emission limit of 0.20 g/KW-hr, as stated in 40 CFR 60.4202(a)(2) and 40 CFR 89.112(a).	None	None	[G]§ 60.4214(d)
ESBGEN	EU	63ZZZZ-0004	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(c)	Stationary RICE subject to Regulations under 40 CFR Part 60. An affected source that meets any of the criteria in paragraphs (c)(1) through (7) of this section must meet the requirements of this part by meeting the requirements of 40 CFR part 60 subpart IIII, for compression ignition engines or 40 CFR part 60 subpart JJJJ, for spark	None	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						ignition engines as applicable. No further requirements apply for such engines under this part.			
F-29	EU	R5112-0006	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
F-501	EU	63EEEE-1	112(B) HAPS	40 CFR Part 63, Subpart EEEE	§ 63.2338(b) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart EEEE
F-502	EU	63EEEE-1	112(B) HAPS	40 CFR Part 63, Subpart EEEE	§ 63.2338(b) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart EEEE
F-603	EU	R5112-0012	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						division.			
F-603	EU	61FF-0041	Benzene	40 CFR Part 61, Subpart FF	§ 61.343(a)(1) § 61.343(a)(1)(i)(A) § 61.343(a)(1)(i)(B) § 61.343(c) § 61.343(d) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	The owner or operator shall install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the tank to a control device.	§ 61.343(a)(1)(i)(A) § 61.343(c) § 61.349(a)(1)(i) § 61.349(e) § 61.349(f) § 61.354(d) [G]§ 61.355(h)	§ 61.356(d) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3)	None
F-604	EU	R5112-0012	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
F-604	EU	61FF-0041	Benzene	40 CFR Part 61, Subpart FF	§ 61.343(a)(1) § 61.343(a)(1)(i)(A) § 61.343(a)(1)(i)(B) § 61.343(c) § 61.343(d) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	The owner or operator shall install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the tank to a control device.	§ 61.343(a)(1)(i)(A) § 61.343(c) § 61.349(a)(1)(i) § 61.349(e) § 61.349(f) § 61.354(d) [G]§ 61.355(h)	§ 61.356(d) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3)	None
F-605	EU	R5112-	VOC	30 TAC Chapter	§ 115.111(a)(1)	Except as provided in §	[G]§ 115.117	§ 115.118(a)(1)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		0012		115, Storage of VOCs		115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.		§ 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	
F-605	EU	61FF-0041	Benzene	40 CFR Part 61, Subpart FF	§ 61.343(a)(1) § 61.343(a)(1)(i)(A) § 61.343(a)(1)(i)(B) § 61.343(c) § 61.343(d) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	The owner or operator shall install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the tank to a control device.	§ 61.343(a)(1)(i)(A) § 61.343(c) § 61.349(a)(1)(i) § 61.349(e) § 61.349(f) § 61.354(d) [G]§ 61.355(h)	§ 61.356(d) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3)	None
F-606	EU	R5112-0012	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
F-606	EU	61FF-0041	Benzene	40 CFR Part 61, Subpart FF	§ 61.343(a)(1) § 61.343(a)(1)(i)(A) § 61.343(a)(1)(i)(B) § 61.343(c) § 61.343(d) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b)	The owner or operator shall install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the tank to a control device.	§ 61.343(a)(1)(i)(A) § 61.343(c) § 61.349(a)(1)(i) § 61.349(e) § 61.349(f) § 61.354(d) [G]§ 61.355(h)	§ 61.356(d) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 61.349(e) § 61.349(f) § 61.349(g)			§ 61.356(j)(2) § 61.356(j)(3)	
F607/T-30	EU	R5112-0013	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(3) § 115.112(e)(3)(A) § 115.112(e)(3)(A)(i) § 115.112(e)(3)(A)(ii)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.115(a) § 115.115(a)(3) § 115.115(a)(3)(B) § 115.116(a)(1) [G]§ 115.117	§ 115.118(a)(4) § 115.118(a)(4)(C) § 115.118(a)(4)(C)(ii) § 115.118(a)(5) § 115.118(a)(7)	None
F607/T-30	EU	R5112-0014	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(3) § 115.112(e)(3)(A) § 115.112(e)(3)(A)(i) § 115.112(e)(3)(A)(ii)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.115(a) § 115.115(a)(1) § 115.116(a)(1) [G]§ 115.117	§ 115.118(a)(4) § 115.118(a)(4)(A) § 115.118(a)(5) § 115.118(a)(7)	None
F607/T-30	EU	60Kb-0073	VOC	40 CFR Part 60,	§ 60.112b(b)(1)	Storage vessels specified in	[G]§ 60.113b(c)(1)	§ 60.115b	[G]§ 60.113b(c)(1)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Subpart Kb		§60.112b(b) and equipped with a closed vent system and control device are to meet the specifications in §60.112b(a)(3).	§ 60.113b(c)(2) § 60.116b(a) § 60.116b(b) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3) § 60.116b(f)(1) [G]§ 60.485(b) ** See Periodic Monitoring Summary	[G]§ 60.115b(c) § 60.116b(a) § 60.116b(b)	§ 60.115b
F607/T-30	EU	60Kb-0074	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(b)(1)	Storage vessels specified in §60.112b(b) and equipped with a closed vent system and control device are to meet the specifications in §60.112b(a)(3).	[G]§ 60.113b(c)(1) § 60.113b(c)(2) § 60.116b(a) § 60.116b(b) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3) § 60.116b(f)(1) [G]§ 60.485(b) ** See Periodic Monitoring Summary	§ 60.115b [G]§ 60.115b(c) § 60.116b(a) § 60.116b(b)	[G]§ 60.113b(c)(1) § 60.115b
F607/T-30	EU	61F-0041	Benzene	40 CFR Part 61, Subpart FF	§ 61.343(a)(1) § 61.343(a)(1)(i)(A) § 61.343(a)(1)(i)(C) § 61.343(a)(1)(i)(C)(1) § 61.343(a)(1)(i)(C)(2) § 61.343(a)(1)(i)(C)(3) § 61.343(c) § 61.343(d) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	The owner or operator shall install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the tank to a control device.	§ 61.343(a)(1)(i)(A) § 61.343(a)(1)(i)(C)(2) § 61.343(a)(1)(i)(C)(3) § 61.343(c) § 61.349(a)(1)(i) § 61.349(e) § 61.349(f) § 61.354(d) § 61.354(g) [G]§ 61.355(h)	§ 61.354(g) § 61.356(d) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3) § 61.356(m)	§ 61.357(d)(7) § 61.357(d)(7)(v)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
F607/T-30	EU	61F-0042	Benzene	40 CFR Part 61, Subpart FF	§ 61.343(a)(1) § 61.343(a)(1)(i)(A) § 61.343(a)(1)(i)(C) § 61.343(a)(1)(i)(C)(1) § 61.343(a)(1)(i)(C)(2) § 61.343(a)(1)(i)(C)(3) § 61.343(c) § 61.343(d) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(i)(A) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	The owner or operator shall install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the tank to a control device.	§ 61.343(a)(1)(i)(A) § 61.343(a)(1)(i)(C)(2) § 61.343(a)(1)(i)(C)(3) § 61.343(c) § 61.349(a)(1)(i) § 61.349(e) § 61.349(f) § 61.354(c) § 61.354(c)(1) § 61.354(g) [G]§ 61.355(h) § 61.355(i)(1) § 61.355(i)(2) § 61.355(i)(3)(i) § 61.355(i)(3)(ii) § 61.355(i)(3)(ii)(A) § 61.355(i)(3)(ii)(B) § 61.355(i)(3)(ii)(C) § 61.355(i)(3)(iii) § 61.355(i)(3)(iv) § 61.355(i)(4)	§ 61.354(c) § 61.354(c)(1) § 61.354(g) § 61.355(i)(1) § 61.355(i)(3)(ii)(A) § 61.356(d) § 61.356(f) § 61.356(f)(1) [G]§ 61.356(f)(3) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(4) § 61.356(m)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(A) § 61.357(d)(7)(v)
F607/T-30	EU	63EEEE-2	112(B) HAPS	40 CFR Part 63, Subpart EEEE	§ 63.2338(b) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart EEEE
F607/T-30	EU	63EEEE-3	112(B) HAPS	40 CFR Part 63, Subpart EEEE	§ 63.2338(b) The permit holder shall comply with the applicable limitation, standard and/or equipment specification	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart EEEE

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					requirements of 40 CFR Part 63, Subpart EEEE				
F607/T-31	EU	R5112-0013	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(3) § 115.112(e)(3)(A) § 115.112(e)(3)(A)(i) § 115.112(e)(3)(A)(ii)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.115(a) § 115.115(a)(3) § 115.115(a)(3)(B) § 115.116(a)(1) [G]§ 115.117	§ 115.118(a)(4) § 115.118(a)(4)(C) § 115.118(a)(4)(C)(ii) § 115.118(a)(5) § 115.118(a)(7)	None
F607/T-31	EU	R5112-0014	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(3) § 115.112(e)(3)(A) § 115.112(e)(3)(A)(i) § 115.112(e)(3)(A)(ii)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.115(a) § 115.115(a)(1) § 115.116(a)(1) [G]§ 115.117	§ 115.118(a)(4) § 115.118(a)(4)(A) § 115.118(a)(5) § 115.118(a)(7)	None
F607/T-31	EU	60Kb-0073	VOC	40 CFR Part 60,	§ 60.112b(b)(1)	Storage vessels specified in	[G]§ 60.113b(c)(1)	§ 60.115b	[G]§ 60.113b(c)(1)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Subpart Kb		§60.112b(b) and equipped with a closed vent system and control device are to meet the specifications in §60.112b(a)(3).	§ 60.113b(c)(2) § 60.116b(a) § 60.116b(b) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3) § 60.116b(f)(1) [G]§ 60.485(b) ** See Periodic Monitoring Summary	[G]§ 60.115b(c) § 60.116b(a) § 60.116b(b)	§ 60.115b
F607/T-31	EU	60Kb-0074	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(b)(1)	Storage vessels specified in §60.112b(b) and equipped with a closed vent system and control device are to meet the specifications in §60.112b(a)(3).	[G]§ 60.113b(c)(1) § 60.113b(c)(2) § 60.116b(a) § 60.116b(b) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3) § 60.116b(f)(1) [G]§ 60.485(b) ** See Periodic Monitoring Summary	§ 60.115b [G]§ 60.115b(c) § 60.116b(a) § 60.116b(b)	[G]§ 60.113b(c)(1) § 60.115b
F607/T-31	EU	61F-0041	Benzene	40 CFR Part 61, Subpart FF	§ 61.343(a)(1) § 61.343(a)(1)(i)(A) § 61.343(a)(1)(i)(C) § 61.343(a)(1)(i)(C)(1) § 61.343(a)(1)(i)(C)(2) § 61.343(a)(1)(i)(C)(3) § 61.343(c) § 61.343(d) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	The owner or operator shall install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the tank to a control device.	§ 61.343(a)(1)(i)(A) § 61.343(a)(1)(i)(C)(2) § 61.343(a)(1)(i)(C)(3) § 61.343(c) § 61.349(a)(1)(i) § 61.349(e) § 61.349(f) § 61.354(d) § 61.354(g) [G]§ 61.355(h)	§ 61.354(g) § 61.356(d) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3) § 61.356(m)	§ 61.357(d)(7) § 61.357(d)(7)(v)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
F607/T-31	EU	61F-0042	Benzene	40 CFR Part 61, Subpart FF	§ 61.343(a)(1) § 61.343(a)(1)(i)(A) § 61.343(a)(1)(i)(C) § 61.343(a)(1)(i)(C)(1) § 61.343(a)(1)(i)(C)(2) § 61.343(a)(1)(i)(C)(3) § 61.343(c) § 61.343(d) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(i)(A) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	The owner or operator shall install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the tank to a control device.	§ 61.343(a)(1)(i)(A) § 61.343(a)(1)(i)(C)(2) § 61.343(a)(1)(i)(C)(3) § 61.343(c) § 61.349(a)(1)(i) § 61.349(e) § 61.349(f) § 61.354(c) § 61.354(c)(1) § 61.354(g) [G]§ 61.355(h) § 61.355(i)(1) § 61.355(i)(2) § 61.355(i)(3)(i) § 61.355(i)(3)(ii) § 61.355(i)(3)(ii)(A) § 61.355(i)(3)(ii)(B) § 61.355(i)(3)(ii)(C) § 61.355(i)(3)(iii) § 61.355(i)(3)(iv) § 61.355(i)(4)	§ 61.354(c) § 61.354(c)(1) § 61.354(g) § 61.355(i)(1) § 61.355(i)(3)(ii)(A) § 61.356(d) § 61.356(f) § 61.356(f)(1) [G]§ 61.356(f)(3) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(4) § 61.356(m)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(A) § 61.357(d)(7)(v)
F607/T-31	EU	63EEEE-2	112(B) HAPS	40 CFR Part 63, Subpart EEEE	§ 63.2338(b) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart EEEE
F607/T-31	EU	63EEEE-3	112(B) HAPS	40 CFR Part 63, Subpart EEEE	§ 63.2338(b) The permit holder shall comply with the applicable limitation, standard and/or equipment specification	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart EEEE

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					requirements of 40 CFR Part 63, Subpart EEEE				
F607/T-32	EU	R5112-0013	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(3) § 115.112(e)(3)(A) § 115.112(e)(3)(A)(i) § 115.112(e)(3)(A)(ii)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.115(a) § 115.115(a)(3) § 115.115(a)(3)(B) § 115.116(a)(1) [G]§ 115.117	§ 115.118(a)(4) § 115.118(a)(4)(C) § 115.118(a)(4)(C)(ii) § 115.118(a)(5) § 115.118(a)(7)	None
F607/T-32	EU	R5112-0014	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(3) § 115.112(e)(3)(A) § 115.112(e)(3)(A)(i) § 115.112(e)(3)(A)(ii)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.115(a) § 115.115(a)(1) § 115.116(a)(1) [G]§ 115.117	§ 115.118(a)(4) § 115.118(a)(4)(A) § 115.118(a)(5) § 115.118(a)(7)	None
F607/T-32	EU	60Kb-0073	VOC	40 CFR Part 60,	§ 60.112b(b)(1)	Storage vessels specified in	[G]§ 60.113b(c)(1)	§ 60.115b	[G]§ 60.113b(c)(1)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Subpart Kb		§60.112b(b) and equipped with a closed vent system and control device are to meet the specifications in §60.112b(a)(3).	§ 60.113b(c)(2) § 60.116b(a) § 60.116b(b) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3) § 60.116b(f)(1) [G]§ 60.485(b) ** See Periodic Monitoring Summary	[G]§ 60.115b(c) § 60.116b(a) § 60.116b(b)	§ 60.115b
F607/T-32	EU	60Kb-0074	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(b)(1)	Storage vessels specified in §60.112b(b) and equipped with a closed vent system and control device are to meet the specifications in §60.112b(a)(3).	[G]§ 60.113b(c)(1) § 60.113b(c)(2) § 60.116b(a) § 60.116b(b) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3) § 60.116b(f)(1) [G]§ 60.485(b) ** See Periodic Monitoring Summary	§ 60.115b [G]§ 60.115b(c) § 60.116b(a) § 60.116b(b)	[G]§ 60.113b(c)(1) § 60.115b
F607/T-32	EU	61F-0041	Benzene	40 CFR Part 61, Subpart FF	§ 61.343(a)(1) § 61.343(a)(1)(i)(A) § 61.343(a)(1)(i)(C) § 61.343(a)(1)(i)(C)(1) § 61.343(a)(1)(i)(C)(2) § 61.343(a)(1)(i)(C)(3) § 61.343(c) § 61.343(d) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	The owner or operator shall install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the tank to a control device.	§ 61.343(a)(1)(i)(A) § 61.343(a)(1)(i)(C)(2) § 61.343(a)(1)(i)(C)(3) § 61.343(c) § 61.349(a)(1)(i) § 61.349(e) § 61.349(f) § 61.354(d) § 61.354(g) [G]§ 61.355(h)	§ 61.354(g) § 61.356(d) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3) § 61.356(m)	§ 61.357(d)(7) § 61.357(d)(7)(v)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
F607/T-32	EU	61F-0042	Benzene	40 CFR Part 61, Subpart FF	§ 61.343(a)(1) § 61.343(a)(1)(i)(A) § 61.343(a)(1)(i)(C) § 61.343(a)(1)(i)(C)(1) § 61.343(a)(1)(i)(C)(2) § 61.343(a)(1)(i)(C)(3) § 61.343(c) § 61.343(d) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(i)(A) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	The owner or operator shall install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the tank to a control device.	§ 61.343(a)(1)(i)(A) § 61.343(a)(1)(i)(C)(2) § 61.343(a)(1)(i)(C)(3) § 61.343(c) § 61.349(a)(1)(i) § 61.349(e) § 61.349(f) § 61.354(c) § 61.354(c)(1) § 61.354(g) [G]§ 61.355(h) § 61.355(i)(1) § 61.355(i)(2) § 61.355(i)(3)(i) § 61.355(i)(3)(ii) § 61.355(i)(3)(ii)(A) § 61.355(i)(3)(ii)(B) § 61.355(i)(3)(ii)(C) § 61.355(i)(3)(iii) § 61.355(i)(3)(iv) § 61.355(i)(4)	§ 61.354(c) § 61.354(c)(1) § 61.354(g) § 61.355(i)(1) § 61.355(i)(3)(ii)(A) § 61.356(d) § 61.356(f) § 61.356(f)(1) [G]§ 61.356(f)(3) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(4) § 61.356(m)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(A) § 61.357(d)(7)(v)
F607/T-32	EU	63EEEE-2	112(B) HAPS	40 CFR Part 63, Subpart EEEE	§ 63.2338(b) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart EEEE
F607/T-32	EU	63EEEE-3	112(B) HAPS	40 CFR Part 63, Subpart EEEE	§ 63.2338(b) The permit holder shall comply with the applicable limitation, standard and/or equipment specification	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart EEEE

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					requirements of 40 CFR Part 63, Subpart EEEE				
FCU3	EU	R7300-5000	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) [G]§ 117.310(a)(2)(C) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.310(a)(2)(C) [G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(2) § 117.335(g) § 117.340(c)(1) § 117.340(c)(1)(H) [G]§ 117.340(c)(3) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)	§ 117.345(a) § 117.345(f) [G]§ 117.345(f)(2) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	[G]§ 117.310(a)(2)(C) § 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
FCU3	EU	R7300-5000	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b)	§ 117.345(a) § 117.345(f) [G]§ 117.345(f)(2)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 117.340(f)(1)		§ 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(e) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)	§ 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	[G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
FCU3	EU	63UUU-0002	CO	40 CFR Part 63, Subpart UUU	§ 63.1565(a)(1)(i)-Table 8.2.a § 63.1565(a)(1) § 63.1565(a)(2) § 63.1565(a)(2)-Table9.2 § 63.1565(a)(3) § 63.1565(a)(4) § 63.1565(b)(3) § 63.1565(b)(4) § 63.1565(b)(4)-Table12.2.a.ii § 63.1565(c)(1)	For each new and existing CCU not subject to the NSPS for CO in 40 CFR §60.103 and electing to comply with the CO emission limit (Option 2), CO emissions from the catalyst regenerator vent or CO boiler serving the CCU must not exceed 500 parts per million volume (ppmv) (dry basis).	§ 63.1565(a)(3) § 63.1565(b)(1) § 63.1565(b)(1)-Table10.2.d § 63.1565(b)(2) § 63.1565(b)(2)-Table11.1.a § 63.1565(b)(2)-Table11.1.b § 63.1565(b)(2)-Table11.1.c § 63.1565(b)(2)-Table11.1.d	§ 63.1565(b)(1)-Table10.2.d § 63.1570(c) [G]§ 63.1576(a) [G]§ 63.1576(b) § 63.1576(d) § 63.1576(e) § 63.1576(f) § 63.1576(g) § 63.1576(h) § 63.1576(i)	§ 63.1565(b)(5) § 63.1565(b)(6) § 63.1570(f) § 63.1571(a) [G]§ 63.1574(a) § 63.1574(d) § 63.1574(d)-Table42.1 § 63.1574(d)-Table42.2 § 63.1574(d)-Table42.3 § 63.1575(a) § 63.1575(a)-Table43.1 [G]§ 63.1575(b) [G]§ 63.1575(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.1565(c)(2) § 63.1570(a) § 63.1570(c) § 63.1570(d) § 63.1570(g) [G]§ 63.1571(e)		§ 63.1565(b)(2)-Table11.2 § 63.1565(b)(3) § 63.1565(b)(4)-Table 12.2.a.ii § 63.1565(c)(1)-Table13.2.i § 63.1565(c)(1)-Table14.2.a § 63.1565(c)(2) § 63.1571(a) § 63.1571(a)(1) [G]§ 63.1571(b) § 63.1572(a) § 63.1572(a)(1) § 63.1572(a)(1)-Table40.2 § 63.1572(a)(2) § 63.1572(a)(3) § 63.1572(a)(4) [G]§ 63.1572(d) [G]§ 63.1573(a)(2)		[G]§ 63.1575(e) [G]§ 63.1575(f) § 63.1575(g) [G]§ 63.1575(h) [G]§ 63.1575(i)
FCU3-CTWR	EU	R5760-0206	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Cooling Towers	§ 115.767(6) § 115.764(a)(1) § 115.766(i)	All sites that are subject to this division and that are located in the Houston/ Galveston/Brazoria area as defined in § 115.10, excluding Harris County, are exempt from § 115.761(b) and (c)(2), except as provided in § 115.769(a)(3).	§ 115.764(a)(1) § 115.764(a)(3) [G]§ 115.764(a)(6) § 115.764(c)	§ 115.766(a)(1) § 115.766(a)(2) § 115.766(a)(3) § 115.766(a)(5) § 115.766(a)(6) § 115.766(c) [G]§ 115.766(g) § 115.766(i)(1)	§ 115.766(i)(2)
FCU3-CTWR	EU	63CC-002	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.654(a) § 63.640(h)(6)	Except as specified in paragraph (b) of this section, the owner or operator of a heat exchange system that meets the criteria in §63.640(c)(8)	§ 63.642(d)(1) § 63.642(d)(3) § 63.642(d)(4) [G]§ 63.654(c) [G]§ 63.654(d) § 63.654(e)	§ 63.642(e) § 63.655(h)(1) [G]§ 63.655(i)(4) § 63.655(i)(5)	§ 63.642(d)(2) § 63.642(f) § 63.655(f) § 63.655(f)(1)(vi) § 63.655(f)(4) § 63.655(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						must comply with the requirements of paragraphs (c) through (g) of this section.	[G]§ 63.654(f) [G]§ 63.654(g)		[G]§ 63.655(g)(9) § 63.655(h)(1)
GRP65CAR1	EU	65CAR-0001	VOC	40 CFR Part 65, Subpart D	§ 60.660(d) § 60.660(a)-(b) § 60.660(d)(1) § 60.660(d)(2) § 65.1(a)-(e) [G]§ 65.1(f) § 65.140 § 65.142(b)(2) § 65.143(a) § 65.143(a)(1) § 65.143(a)(2) [G]§ 65.149(a) § 65.149(b)(2) § 65.149(b)(2)(ii) § 65.3(a)(1) § 65.3(a)(3) § 65.3(a)(4) § 65.3(a)(5) § 65.3(b)(3) [G]§ 65.3(b)(5) § 65.3(c) [G]§ 65.3(d) [G]§ 65.6(b) § 65.62(a) § 65.62(b)(1) § 65.63(a) § 65.63(a)(2) § 65.63(a)(2)(i)	Option to comply with part 65. Owners or operators of process vents that are subject to this subpart may choose to comply with the provisions of 40 CFR part 65, subpart D, to satisfy the requirements of §§60.662 through 60.665 and 60.668. The provisions of 40 CFR part 65 also satisfy the criteria of paragraphs (c)(4) and (6) of this section. Other provisions applying to an owner or operator who chooses to comply with 40 CFR part 65 are provided in 40 CFR 65.1.	None	§ 65.163(c)(1) § 65.163(c)(2) § 65.4(a)(1) § 65.4(b) § 65.4(c) § 65.4(c)(1) § 65.4(c)(3)	§ 60.660(d)(4) § 65.165(f) § 65.166(a) § 65.167(b) [G]§ 65.5(a) [G]§ 65.5(d) [G]§ 65.5(e) [G]§ 65.5(f) [G]§ 65.5(g) [G]§ 65.5(h) [G]§ 65.5(i) [G]§ 65.6
GRP65CAR3	EU	65CAR-0003	VOC	40 CFR Part 65, Subpart D	§ 60.660(d) § 60.660(a)-(b) § 60.660(d)(1) § 60.660(d)(2) § 65.1(a)-(e) [G]§ 65.1(f)	Option to comply with part 65. Owners or operators of process vents that are subject to this subpart may choose to comply with the provisions of 40 CFR part	§ 65.147(b)(1) § 65.147(b)(3) § 65.147(b)(3)(i) § 65.147(b)(3)(ii) § 65.147(b)(3)(iii) § 65.147(b)(3)(iv)	§ 65.159(a) [G]§ 65.159(b) § 65.159(c) [G]§ 65.159(d) § 65.163(c)(1) § 65.163(c)(2)	§ 60.660(d)(4) [G]§ 65.164(a) [G]§ 65.164(b) § 65.166(a) § 65.166(c) § 65.167(b)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 65.140 § 65.142(b)(1) § 65.143(a) § 65.143(a)(1) § 65.143(a)(2) [G]§ 65.147(a) § 65.3(a)(1) § 65.3(a)(3) § 65.3(a)(4) § 65.3(a)(5) § 65.3(b)(3) [G]§ 65.3(b)(5) § 65.3(c) [G]§ 65.3(d) [G]§ 65.6(b) § 65.62(a) § 65.62(b)(1) § 65.63(a) § 65.63(a)(1)	65, subpart D, to satisfy the requirements of §§60.662 through 60.665 and 60.668. The provisions of 40 CFR part 65 also satisfy the criteria of paragraphs (c)(4) and (6) of this section. Other provisions applying to an owner or operator who chooses to comply with 40 CFR part 65 are provided in 40 CFR 65.1.	§ 65.147(c)	§ 65.4(a)(1) § 65.4(b) § 65.4(c) § 65.4(c)(1) § 65.4(c)(3)	[G]§ 65.5(a) [G]§ 65.5(d) [G]§ 65.5(e) [G]§ 65.5(f) [G]§ 65.5(g) [G]§ 65.5(h) [G]§ 65.5(i) [G]§ 65.6
GRP65CAR4	EU	65CAR-0004	VOC	40 CFR Part 65, Subpart D	§ 60.700(d) § 60.700(a)-(b) § 60.700(d)(1) § 60.700(d)(2) § 65.1(a)-(e) [G]§ 65.1(f) § 65.140 § 65.142(b)(1) § 65.143(a) § 65.143(a)(1) § 65.143(a)(2) [G]§ 65.147(a) § 65.3(a)(1) § 65.3(a)(3) § 65.3(a)(4) § 65.3(a)(5) § 65.3(b)(3) [G]§ 65.3(b)(5) § 65.3(c) [G]§ 65.3(d)	Option to comply with part 65. Owners or operators of process vents that are subject to this subpart may choose to comply with the provisions of 40 CFR part 65, subpart D, to satisfy the requirements of §§60.702 through 60.705 and 60.708. The provisions of 40 CFR part 65 also satisfy the criteria of paragraphs (c)(2), (4), and (8) of this section. Other provisions applying to an owner or operator who chooses to comply with 40 CFR part 65 are provided in 40 CFR 65.1.	§ 65.147(b)(1) § 65.147(b)(3) § 65.147(b)(3)(i) § 65.147(b)(3)(ii) § 65.147(b)(3)(iii) § 65.147(b)(3)(iv) § 65.147(c)	§ 65.159(a) [G]§ 65.159(b) § 65.159(c) [G]§ 65.159(d) § 65.163(c)(1) § 65.163(c)(2) § 65.4(a)(1) § 65.4(b) § 65.4(c) § 65.4(c)(1) § 65.4(c)(3)	§ 60.700(d)(4) [G]§ 65.164(a) [G]§ 65.164(b) § 65.166(a) § 65.166(c) § 65.167(b) [G]§ 65.5(a) [G]§ 65.5(d) [G]§ 65.5(e) [G]§ 65.5(f) [G]§ 65.5(g) [G]§ 65.5(h) [G]§ 65.5(i) [G]§ 65.6

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 65.6(b) § 65.62(a) § 65.62(b)(1) § 65.63(a) § 65.63(a)(1)				
GRP65CAR5	EU	65CAR-0001	VOC	40 CFR Part 65, Subpart D	§ 60.660(d) [G]§ 65.6(b) § 60.660(a)-(b) § 60.660(d)(1) § 60.660(d)(2) § 65.1(a)-(e) [G]§ 65.1(f) § 65.140 § 65.142(b)(2) § 65.143(a) § 65.143(a)(1) § 65.143(a)(2) [G]§ 65.149(a) § 65.149(b)(2) § 65.149(b)(2)(ii) § 65.3(a)(1) § 65.3(a)(3) § 65.3(a)(4) § 65.3(a)(5) § 65.3(b)(3) [G]§ 65.3(b)(5) § 65.3(c) [G]§ 65.3(d) § 65.62(a) § 65.62(b)(1) § 65.63(a) § 65.63(a)(2) § 65.63(a)(2)(i)	Option to comply with part 65. Owners or operators of process vents that are subject to this subpart may choose to comply with the provisions of 40 CFR part 65, subpart D, to satisfy the requirements of §§60.662 through 60.665 and 60.668. The provisions of 40 CFR part 65 also satisfy the criteria of paragraphs (c)(4) and (6) of this section. Other provisions applying to an owner or operator who chooses to comply with 40 CFR part 65 are provided in 40 CFR 65.1.	None	§ 65.163(c)(1) § 65.163(c)(2) § 65.4(a)(1) § 65.4(b) § 65.4(c) § 65.4(c)(1) § 65.4(c)(3)	§ 60.660(d)(4) § 65.165(f) § 65.166(a) § 65.167(b) [G]§ 65.5(a) [G]§ 65.5(d) [G]§ 65.5(e) [G]§ 65.5(f) [G]§ 65.5(g) [G]§ 65.5(h) [G]§ 65.5(i) [G]§ 65.6
GRP65CAR5	EU	65CAR-0003	VOC	40 CFR Part 65, Subpart D	§ 60.660(d) § 60.660(a)-(b) § 60.660(d)(1) § 60.660(d)(2) § 65.1(a)-(e)	Option to comply with part 65. Owners or operators of process vents that are subject to this subpart may choose to comply with the	§ 65.147(b)(1) § 65.147(b)(3) § 65.147(b)(3)(i) § 65.147(b)(3)(ii) § 65.147(b)(3)(iii)	§ 65.159(a) [G]§ 65.159(b) § 65.159(c) [G]§ 65.159(d) § 65.163(c)(1)	§ 60.660(d)(4) [G]§ 65.164(a) [G]§ 65.164(b) § 65.166(a) § 65.166(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 65.1(f) § 65.140 § 65.142(b)(1) § 65.143(a) § 65.143(a)(1) § 65.143(a)(2) [G]§ 65.147(a) § 65.3(a)(1) § 65.3(a)(3) § 65.3(a)(4) § 65.3(a)(5) § 65.3(b)(3) [G]§ 65.3(b)(5) § 65.3(c) [G]§ 65.3(d) [G]§ 65.6(b) § 65.62(a) § 65.62(b)(1) § 65.63(a) § 65.63(a)(1)	provisions of 40 CFR part 65, subpart D, to satisfy the requirements of §§60.662 through 60.665 and 60.668. The provisions of 40 CFR part 65 also satisfy the criteria of paragraphs (c)(4) and (6) of this section. Other provisions applying to an owner or operator who chooses to comply with 40 CFR part 65 are provided in 40 CFR 65.1.	§ 65.147(b)(3)(iv) § 65.147(c)	§ 65.163(c)(2) § 65.4(a)(1) § 65.4(b) § 65.4(c) § 65.4(c)(1) § 65.4(c)(3)	§ 65.167(b) [G]§ 65.5(a) [G]§ 65.5(d) [G]§ 65.5(e) [G]§ 65.5(f) [G]§ 65.5(g) [G]§ 65.5(h) [G]§ 65.5(i) [G]§ 65.6
GRP65CAR6					None				
GRP65CAR6	EU	65CAR-0002	VOC	40 CFR Part 65, Subpart D	§ 60.700(d) § 60.700(a)-(b) § 60.700(d)(1) § 60.700(d)(2) § 65.1(a)-(e) [G]§ 65.1(f) § 65.140 § 65.142(b)(2) § 65.143(a) § 65.143(a)(1) § 65.143(a)(2) [G]§ 65.149(a) § 65.149(b)(2) § 65.149(b)(2)(ii) § 65.3(a)(1) § 65.3(a)(3) § 65.3(a)(4)	Option to comply with part 65. Owners or operators of process vents that are subject to this subpart may choose to comply with the provisions of 40 CFR part 65, subpart D, to satisfy the requirements of §§60.702 through 60.705 and 60.708. The provisions of 40 CFR part 65 also satisfy the criteria of paragraphs (c)(2), (4), and (8) of this section. Other provisions applying to an owner or operator who chooses to comply with 40 CFR part 65 are provided in	None	§ 65.163(c)(1) § 65.163(c)(2) § 65.4(a)(1) § 65.4(b) § 65.4(c) § 65.4(c)(1) § 65.4(c)(3)	§ 60.700(d)(4) § 65.165(f) § 65.166(a) § 65.167(b) [G]§ 65.5(a) [G]§ 65.5(d) [G]§ 65.5(e) [G]§ 65.5(f) [G]§ 65.5(g) [G]§ 65.5(h) [G]§ 65.5(i) [G]§ 65.6

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 65.3(a)(5) § 65.3(b)(3) [G]§ 65.3(b)(5) § 65.3(c) [G]§ 65.3(d) [G]§ 65.6(b) § 65.62(a) § 65.62(b)(1) § 65.63(a) § 65.63(a)(2) § 65.63(a)(2)(i)	40 CFR 65.1.			
GRP65CAR6	EU	65CAR-0004	VOC	40 CFR Part 65, Subpart D	§ 60.700(d) § 60.700(a)-(b) § 60.700(d)(1) § 60.700(d)(2) § 65.1(a)-(e) [G]§ 65.1(f) § 65.140 § 65.142(b)(1) § 65.143(a) § 65.143(a)(1) § 65.143(a)(2) [G]§ 65.147(a) § 65.3(a)(1) § 65.3(a)(3) § 65.3(a)(4) § 65.3(a)(5) [G]§ 65.3(b)(5) § 65.3(c) [G]§ 65.3(d) [G]§ 65.6(b) § 65.62(a) § 65.62(b)(1) § 65.63(a) § 65.63(a)(1)	Option to comply with part 65. Owners or operators of process vents that are subject to this subpart may choose to comply with the provisions of 40 CFR part 65, subpart D, to satisfy the requirements of §§60.702 through 60.705 and 60.708. The provisions of 40 CFR part 65 also satisfy the criteria of paragraphs (c)(2), (4), and (8) of this section. Other provisions applying to an owner or operator who chooses to comply with 40 CFR part 65 are provided in 40 CFR 65.1.	§ 65.147(b)(1) § 65.147(b)(3) § 65.147(b)(3)(i) § 65.147(b)(3)(ii) § 65.147(b)(3)(iii) § 65.147(b)(3)(iv) § 65.147(c)	§ 65.159(a) [G]§ 65.159(b) § 65.159(c) [G]§ 65.159(d) § 65.163(c)(1) § 65.163(c)(2) § 65.4(a)(1) § 65.4(b) § 65.4(c) § 65.4(c)(1) § 65.4(c)(3)	§ 60.700(d)(4) [G]§ 65.164(a) [G]§ 65.164(b) § 65.166(a) § 65.166(c) § 65.167(b) [G]§ 65.5(a) [G]§ 65.5(d) [G]§ 65.5(e) [G]§ 65.5(f) [G]§ 65.5(g) [G]§ 65.5(h) [G]§ 65.5(i) [G]§ 65.6
GRP-APISEP	EU	R5131-001	VOC	30 TAC Chapter 115, Water Separation	§ 115.132(a)(3) § 115.131(a)	VOC water separator compartments must be equipped with a vapor	[G]§ 115.135(a) § 115.136(a)(2) § 115.136(a)(2)(A)	§ 115.136(a)(2) § 115.136(a)(2)(A) § 115.136(a)(3)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						recovery system which satisfies the provisions of §115.131(a) of this title.	§ 115.136(a)(3) § 115.136(a)(4)	§ 115.136(a)(4)	
GRP-APISEP	EU	R5131-002	VOC	30 TAC Chapter 115, Water Separation	§ 115.132(a)(3) § 115.131(a)	VOC water separator compartments must be equipped with a vapor recovery system which satisfies the provisions of §115.131(a) of this title.	[G]§ 115.135(a) § 115.136(a)(2) § 115.136(a)(2)(C) § 115.136(a)(3) § 115.136(a)(4)	§ 115.136(a)(2) § 115.136(a)(2)(C) § 115.136(a)(3) § 115.136(a)(4)	None
GRP-APISEP	EU	61FF-002	Benzene	40 CFR Part 61, Subpart FF	§ 61.347(a)(1) § 61.347(a)(1)(i)(A) § 61.347(a)(1)(i)(C) § 61.347(a)(1)(i)(C)(1) § 61.347(a)(1)(i)(C)(2) § 61.347(a)(1)(i)(C)(3) § 61.347(b) § 61.347(c) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(i)(C) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	Install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the oil-water separator to a control device.	§ 61.347(a)(1)(i)(A) § 61.347(a)(1)(i)(C)(2) § 61.347(a)(1)(i)(C)(3) § 61.347(b) § 61.349(a)(1)(i) § 61.349(e) § 61.349(f) § 61.354(c) § 61.354(c)(1) § 61.354(g) [G]§ 61.355(h)	§ 61.354(c) § 61.354(c)(1) § 61.354(g) § 61.356(d) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(A) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(4) § 61.356(m)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(A) § 61.357(d)(7)(v)
GRP-APISEP	EU	61FF-003	Benzene	40 CFR Part 61, Subpart FF	§ 61.347(a)(1) § 61.347(a)(1)(i)(A) § 61.347(a)(1)(i)(C) § 61.347(a)(1)(i)(C)(1) § 61.347(a)(1)(i)(C)(2) § 61.347(a)(1)(i)(C)(3) § 61.347(b) § 61.347(c) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv)	Install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the oil-water separator to a control device.	§ 61.347(a)(1)(i)(A) § 61.347(a)(1)(i)(C)(2) § 61.347(a)(1)(i)(C)(3) § 61.347(b) § 61.349(a)(1)(i) § 61.349(e) § 61.349(f) § 61.354(d) § 61.354(g) [G]§ 61.355(h)	§ 61.354(g) § 61.356(d) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10)	§ 61.357(d)(7) § 61.357(d)(7)(v)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)			§ 61.356(j)(2) § 61.356(j)(3) § 61.356(m)	
GRP-TDUVENT	EP	R5121-0004	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(a)(1) § 115.121(a)(1) § 115.122(a)(1)(A)	Vent gas streams affected by §115.121(a)(1) must be controlled properly with a control efficiency of at least 90% or to a volatile organic compound (VOC) concentration of no more than 20 parts per million (ppmv) (on a dry basis corrected to 3.0% oxygen for combustion devices).	[G]§ 115.125 § 115.126(1) § 115.126(1)(A) § 115.126(1)(A)(i) § 115.126(2)	§ 115.126 § 115.126(1) § 115.126(1)(A) § 115.126(1)(A)(i) § 115.126(2)	None
GRPVENT1	EP	R1111-0112	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(B) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall not exceed an opacity of 20% averaged over a six minute period for any source on which construction was begun after January 31, 1972.	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None
GRPVENT2	EP	R1111-0112	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(B) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall not exceed an opacity of 20% averaged over a six minute period for any source on which construction was begun after January 31, 1972.	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None
GRPVENT2	EP	R5720-0561	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Vent Gas	§ 115.727(f) § 115.725(a)(1)(A) § 115.725(a)(1)(B) § 115.725(a)(1)(C) § 115.725(a)(3)	All sites that are subject to this division and that are located in the Houston/Galveston/ Brazoria area as defined in	§ 115.725(a) § 115.725(a)(1)(A) § 115.725(a)(1)(B) § 115.725(a)(1)(C) § 115.725(a)(3)	§ 115.726(b)(1) § 115.726(b)(2) § 115.726(b)(3) § 115.726(i) § 115.726(j)(1)	[G]§ 115.725(a)(4) § 115.725(a)(5) § 115.725(n) [G]§ 115.726(a)(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 115.725(a)(4) [G]§ 115.725(l) [G]§ 115.726(a)(2)	§115.10 of this title (relating to Definitions), excluding Harris County, are exempt from § 115.722(b) and (c)(2) of this title, except as provided in § 115.729(a)(3) of this title (relating to Counties and Compliance Schedules).	§ 115.725(a)(3)(B) [G]§ 115.725(a)(4) § 115.725(a)(5) [G]§ 115.725(l) § 115.725(n)	§ 115.726(j)(2)	
HRU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(d)	Comply with the requirements as stated in §60.482-1(d) for equipment in vacuum service.	None	§ 60.486(e) § 60.486(e)(1) § 60.486(e)(5)	None
HRU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-2 [G]§ 60.482-9	Comply with the requirements as stated in §60.482-2 for pumps in light-liquid service.	[G]§ 60.482-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d) § 60.593(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
HRU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.593(b)(1)	Compressors in hydrogen service are exempt from the requirements of §60.592 if an owner or operator demonstrates that a compressor is in hydrogen service.	§ 60.593(b)(2) [G]§ 60.593(b)(3)	None	None
HRU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-3 [G]§ 60.482-9	Comply with the requirements as stated in §60.482-3 for compressors.	[G]§ 60.482-3 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
								[G]§ 60.486(h) § 60.486(j) § 60.592(e)	
HRU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-4 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-4 for pressure relief devices in gas/vapor service.	[G]§ 60.482-4 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(3) [G]§ 60.486(e)(4) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
HRU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-5 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-5 for sampling connection systems.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
HRU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-6 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-6 for open-ended valves and lines.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
HRU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-7 [G]§ 60.482-9 [G]§ 60.483-1 [G]§ 60.483-2 § 60.592(b)	Comply with the requirements in as stated in §60.482-7 for valves in gas/vapor or light-liquid service.	[G]§ 60.482-7 [G]§ 60.483-1 [G]§ 60.483-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d) § 60.593(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) [G]§ 60.486(g) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(d) § 60.487(e) § 60.592(e)
HRU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for pumps in heavy-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 60.485(f) § 60.592(d)	§ 60.486(j) § 60.592(e)	
HRU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) § 60.482-10(b) § 60.482-10(e) § 60.482-10(m)	Comply with the requirements in as stated in §60.482-10 for vapor recovery devices.	§ 60.485(a) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
HRU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.18 § 60.482-1(a) § 60.482-1(b) § 60.482-10(d) § 60.482-10(e) § 60.482-10(m)	Comply with the requirements in as stated in §60.482-10 for flares.	§ 60.485(a) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) [G]§ 60.485(g) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
HRU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) § 60.482-10(e) [G]§ 60.482-10(g) § 60.482-10(h) § 60.482-10(m)	Comply with the requirements in as stated in §60.482-10 for closed-vent systems.	[G]§ 60.482-10(f) § 60.482-10(i) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.482-10(j) [G]§ 60.482-10(k) [G]§ 60.482-10(l) [G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
HRU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for valves in heavy-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
HRU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for flanges or other connectors.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 60.592(d)	§ 60.592(e)	
HRU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for pressure relief devices in light-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
HRU-FUG1	EU	60GGGa-01	VOC	40 CFR Part 60, Subpart GGGa	[G]§ 60.590a(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 60, Subpart GGGa
HRU-OWS	EU	R5131-0010	VOC	30 TAC Chapter 115, Water Separation	§ 115.132(a)(3) § 115.131(a)	VOC water separator compartments must be equipped with a vapor recovery system which satisfies the provisions of §115.131(a) of this title.	[G]§ 115.135(a) § 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	§ 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	None
HRU-OWS	EU	61FF-1769	Benzene	40 CFR Part 61, Subpart FF	§ 61.347(a)(1) § 61.347(a)(1)(i)(A) § 61.347(a)(1)(i)(B) § 61.347(b) § 61.347(c) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b)	Install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the oil-water separator to a control device.	§ 61.347(a)(1)(i)(A) § 61.347(b) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(d) § 61.354(f)(1) [G]§ 61.355(h) § 61.355(i)(1) § 61.355(i)(2) § 61.355(i)(3)(i) § 61.355(i)(3)(ii)	§ 61.349(a)(1)(ii) § 61.355(i)(1) § 61.355(i)(3)(ii)(A) § 61.356(d) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2)(i)(G) [G]§ 61.356(f)(3) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(I)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 61.349(e) § 61.349(f) § 61.349(g)		§ 61.355(i)(3)(ii)(A) § 61.355(i)(3)(ii)(B) § 61.355(i)(3)(ii)(C) § 61.355(i)(3)(iii) § 61.355(i)(3)(iv) § 61.355(i)(4)	§ 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i)	
J803PUMP	EU	R7300-0001	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B)	CO emissions must not exceed 3.0 g/hp-hr for stationary internal combustion engines.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a)(2)(C) § 117.340(h) § 117.345(f)(3) § 117.345(f)(3)(A) § 117.345(f)(3)(A)(ii) § 117.8000(b) § 117.8000(c) § 117.8000(c)(2) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8120 § 117.8120(2) [G]§ 117.8120(2)(A) § 117.8120(2)(B) § 117.8140(a) § 117.8140(a)(1) § 117.8140(a)(2) § 117.8140(a)(2)(A) [G]§ 117.8140(a)(2)(B) § 117.8140(b)	§ 117.345(a) § 117.345(f) [G]§ 117.345(f)(10) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
J803PUMP	EU	60IIII-0005	CO	40 CFR Part 60, Subpart IIII	§ 60.4204(b) § 60.4201(a) § 60.4206 § 60.4207(b)	Owners and operators of non-emergency stationary CI ICE with a maximum engine power greater than	None	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 60.4211(a) § 60.4211(c) § 60.4218 § 89.112(a)	or equal to 37 KW and less than 130 KW and a displacement of less than 10 liters per cylinder and is a 2007 model year and later must comply with a CO emission limit of 5.0 g/KW-hr as stated in 40 CFR 60.4201(a) and 40 CFR 89.112(a) and 40 CFR 1039.102 and 40 CFR 1039.101.			
J803PUMP	EU	60IIII-0005	NMHC and NO_X	40 CFR Part 60, Subpart IIII	§ 60.4204(b) § 60.4201(a) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) § 60.4218 § 89.112(a)	Owners and operators of non-emergency stationary CI ICE with a maximum engine power greater than or equal to 75 KW but less than 560 KW and a displacement of less than 10 liters per cylinder and is a 2007 - 2013 model year must comply with an NMHC+NOx emission limit of 4.0 g/KW-hr as stated in 40 CFR 60.4201(a) and 40 CFR 89.112(a) and 40 CFR 1039.102.	None	None	None
J803PUMP	EU	60IIII-0005	PM (Opacity)	40 CFR Part 60, Subpart IIII	§ 60.4204(b) § 60.4201(a) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) § 60.4218 § 89.113(a)(1) § 89.113(a)(2) § 89.113(a)(3)	Owners and operators of non-emergency stationary CI ICE with a displacement of less than 10 liters per cylinder and is not a constant-speed engine and is a 2007 model year and later must comply with the following opacity emission limits: 20% during the acceleration mode, 15%	None	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						during the lugging mode, and 50% during the peaks in either the acceleration or lugging modes as stated in 40 CFR 60.4201(a)-(c) and 40 CFR 89.113(a)(1)-(3) and 40 CFR 1039.105(b)(1)-(3).			
J803PUMP	EU	60IIII-0005	PM	40 CFR Part 60, Subpart IIII	§ 60.4204(b) § 60.4201(a) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) § 60.4218 § 89.112(a)	Owners and operators of non-emergency stationary CI ICE with a maximum engine power greater than or equal to 75 KW and less than 130 KW and a displacement of less than 10 liters per cylinder and is a 2007 - 2011 model year must comply with a PM emission limit of 0.30g/KW-hr as stated in 40 CFR 60.4201(a) and 40 CFR 89.112(a).	None	None	None
J803PUMP	EU	63ZZZZ-0001	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(c)	Stationary RICE subject to Regulations under 40 CFR Part 60. An affected source that meets any of the criteria in paragraphs (c)(1) through (7) of this section must meet the requirements of this part by meeting the requirements of 40 CFR part 60 subpart IIII, for compression ignition engines or 40 CFR part 60 subpart JJJJ, for spark ignition engines as applicable. No further requirements apply for such	None	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						engines under this part.			
J804PUMP	EU	R7300-0001	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B)	CO emissions must not exceed 3.0 g/hp-hr for stationary internal combustion engines.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a)(2)(C) § 117.340(h) § 117.345(f)(3) § 117.345(f)(3)(A) § 117.345(f)(3)(A)(ii) § 117.8000(b) § 117.8000(c) § 117.8000(c)(2) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8120 § 117.8120(2) [G]§ 117.8120(2)(A) § 117.8120(2)(B) § 117.8140(a) § 117.8140(a)(1) § 117.8140(a)(2) § 117.8140(a)(2)(A) [G]§ 117.8140(a)(2)(B) § 117.8140(b)	§ 117.345(a) § 117.345(f) [G]§ 117.345(f)(10) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
J804PUMP	EU	60IIII-0005	CO	40 CFR Part 60, Subpart IIII	§ 60.4204(b) § 60.4201(a) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) § 60.4218 § 89.112(a)	Owners and operators of non-emergency stationary CI ICE with a maximum engine power greater than or equal to 37 KW and less than 130 KW and a displacement of less than 10 liters per cylinder and is a 2007 model year and later	None	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						must comply with a CO emission limit of 5.0 g/KW-hr as stated in 40 CFR 60.4201(a) and 40 CFR 89.112(a) and 40 CFR 1039.102 and 40 CFR 1039.101.			
J804PUMP	EU	60IIII-0005	NMHC and NO_X	40 CFR Part 60, Subpart IIII	§ 60.4204(b) § 60.4201(a) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) § 60.4218 § 89.112(a)	Owners and operators of non-emergency stationary CI ICE with a maximum engine power greater than or equal to 75 KW but less than 560 KW and a displacement of less than 10 liters per cylinder and is a 2007 - 2013 model year must comply with an NMHC+NOx emission limit of 4.0 g/KW-hr as stated in 40 CFR 60.4201(a) and 40 CFR 89.112(a) and 40 CFR 1039.102.	None	None	None
J804PUMP	EU	60IIII-0005	PM (Opacity)	40 CFR Part 60, Subpart IIII	§ 60.4204(b) § 60.4201(a) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) § 60.4218 § 89.113(a)(1) § 89.113(a)(2) § 89.113(a)(3)	Owners and operators of non-emergency stationary CI ICE with a displacement of less than 10 liters per cylinder and is not a constant-speed engine and is a 2007 model year and later must comply with the following opacity emission limits: 20% during the acceleration mode, 15% during the lugging mode, and 50% during the peaks in either the acceleration or lugging modes as stated in 40 CFR 60.4201(a)-(c) and	None	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						40 CFR 89.113(a)(1)-(3) and 40 CFR 1039.105(b)(1)-(3).			
J804PUMP	EU	60IIII-0005	PM	40 CFR Part 60, Subpart IIII	§ 60.4204(b) § 60.4201(a) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) § 60.4218 § 89.112(a)	Owners and operators of non-emergency stationary CI ICE with a maximum engine power greater than or equal to 75 KW and less than 130 KW and a displacement of less than 10 liters per cylinder and is a 2007 - 2011 model year must comply with a PM emission limit of 0.30g/KW-hr as stated in 40 CFR 60.4201(a) and 40 CFR 89.112(a).	None	None	None
J804PUMP	EU	63ZZZZ-0001	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(c)	Stationary RICE subject to Regulations under 40 CFR Part 60. An affected source that meets any of the criteria in paragraphs (c)(1) through (7) of this section must meet the requirements of this part by meeting the requirements of 40 CFR part 60 subpart IIII, for compression ignition engines or 40 CFR part 60 subpart JJJJ, for spark ignition engines as applicable. No further requirements apply for such engines under this part.	None	None	None
LAB-DWS	EU	R5131-0010	VOC	30 TAC Chapter 115, Water Separation	§ 115.132(a)(3) § 115.131(a)	VOC water separator compartments must be equipped with a vapor recovery system which	[G]§ 115.135(a) § 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	§ 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						satisfies the provisions of §115.131(a) of this title.			
LAB-DWS	EU	61FF-1781	Benzene	40 CFR Part 61, Subpart FF	§ 61.347(a)(1) § 61.347(a)(1)(i)(A) § 61.347(a)(1)(i)(B) § 61.347(b) § 61.347(c) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	Install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the oil-water separator to a control device.	§ 61.347(a)(1)(i)(A) § 61.347(b) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.349(a)(1)(ii) § 61.356(d) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i)	None
LAMPUMP	EU	R7300-0001	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(9)(E)(iv)(III) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) [G]§ 117.310(f) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a)(2)(C) § 117.340(h) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C) § 117.345(f)(3)(A) § 117.345(f)(3)(A)(ii) § 117.8000(b) § 117.8000(c) § 117.8000(c)(1) § 117.8000(c)(3)	§ 117.345(a) § 117.345(f) [G]§ 117.345(f)(10) § 117.345(f)(3) § 117.345(f)(3)(B) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8140(a) § 117.8140(a)(1) § 117.8140(a)(2) § 117.8140(a)(2)(A) [G]§ 117.8140(a)(2)(B) § 117.8140(b)		
LAMPUMP	EU	R7300-0001	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B)	CO emissions must not exceed 3.0 g/hp-hr for stationary internal combustion engines.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a)(2)(C) § 117.340(h) § 117.345(f)(3) § 117.345(f)(3)(A) § 117.345(f)(3)(A)(ii) § 117.8000(b) § 117.8000(c) § 117.8000(c)(2) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8120 § 117.8120(2) [G]§ 117.8120(2)(A) § 117.8120(2)(B) § 117.8140(a) § 117.8140(a)(1) § 117.8140(a)(2) § 117.8140(a)(2)(A) [G]§ 117.8140(a)(2)(B) § 117.8140(b)	§ 117.345(a) § 117.345(f) [G]§ 117.345(f)(10) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
LAMPUMP	EU	60IIII-0006	CO	40 CFR Part 60,	§ 60.4204(b)	Owners and operators of	None	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Subpart IIII	§ 60.4201(a) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) § 60.4218 § 89.112(a)	non-emergency stationary CI ICE with a maximum engine power greater than or equal to 37 KW and less than 130 KW and a displacement of less than 10 liters per cylinder and is a 2007 model year and later must comply with a CO emission limit of 5.0 g/KW-hr as stated in 40 CFR 60.4201(a) and 40 CFR 89.112(a) and 40 CFR 1039.102 and 40 CFR 1039.101.			
LAMPUMP	EU	60IIII-0006	NMHC and NO_X	40 CFR Part 60, Subpart IIII	§ 60.4204(b) § 60.4201(a) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) § 60.4218 § 89.112(a)	Owners and operators of non-emergency stationary CI ICE with a maximum engine power greater than or equal to 75 KW but less than 560 KW and a displacement of less than 10 liters per cylinder and is a 2007 - 2013 model year must comply with an NMHC+NOx emission limit of 4.0 g/KW-hr as stated in 40 CFR 60.4201(a) and 40 CFR 89.112(a) and 40 CFR 1039.102.	None	None	None
LAMPUMP	EU	60IIII-0006	PM (Opacity)	40 CFR Part 60, Subpart IIII	§ 60.4204(b) § 60.4201(a) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) § 60.4218 § 89.113(a)(1)	Owners and operators of non-emergency stationary CI ICE with a displacement of less than 10 liters per cylinder and is not a constant-speed engine and is a 2007 model year and later must comply with the	None	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 89.113(a)(2) § 89.113(a)(3)	following opacity emission limits: 20% during the acceleration mode, 15% during the lugging mode, and 50% during the peaks in either the acceleration or lugging modes as stated in 40 CFR 60.4201(a)-(c) and 40 CFR 89.113(a)(1)-(3) and 40 CFR 1039.105(b)(1)-(3).			
LAMPUMP	EU	60IIII-0006	PM	40 CFR Part 60, Subpart IIII	§ 60.4204(b) § 60.4201(a) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) § 60.4218 § 89.112(a)	Owners and operators of non-emergency stationary CI ICE with a maximum engine power greater than or equal to 75 KW and less than 130 KW and a displacement of less than 10 liters per cylinder and is a 2007 - 2011 model year must comply with a PM emission limit of 0.30g/KW-hr as stated in 40 CFR 60.4201(a) and 40 CFR 89.112(a).	None	None	None
LAMPUMP	EU	63ZZZZ-0002	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(c)	Stationary RICE subject to Regulations under 40 CFR Part 60. An affected source that meets any of the criteria in paragraphs (c)(1) through (7) of this section must meet the requirements of this part by meeting the requirements of 40 CFR part 60 subpart IIII, for compression ignition engines or 40 CFR part 60 subpart JJJJ, for spark	None	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						ignition engines as applicable. No further requirements apply for such engines under this part.			
NDU1	EU	R7300-1086	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C) § 117.8000(b) § 117.8000(c) § 117.8000(c)(1) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
NDU1	EU	R7300-1086	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B) § 117.310(c)(3)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.8000(b) § 117.8000(c) § 117.8000(c)(2) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.8120 § 117.8120(2) [G]§ 117.8120(2)(A) § 117.8120(2)(B)		[G]§ 117.8010(8)
NDU1	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
NDU1	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
NDU2-B201	EU	R7300-0001	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(2) § 117.335(g) § 117.340(a) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) [G]§ 117.340(c)(3) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	§ 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)		§ 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
NDU2-B201	EU	R7300-0001	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a) § 117.340(b)(1) § 117.340(b)(3) § 117.340(e) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)		
NDU2-B201	EU	R7300-0001	NH_3	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(2) § 117.310(c)(2)(B) § 117.340(f)(1)	For process heaters that inject urea or ammonia into the exhaust stream for NO_x control, ammonia emissions must not exceed 10 ppmv at 3.0% O_2, dry.	§ 117.335(a)(2) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(g) § 117.340(b)(1) § 117.340(b)(3) § 117.340(d) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8130 § 117.8130(4)	§ 117.345(a) § 117.345(f) § 117.345(f)(11) [G]§ 117.345(f)(2) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
NDU2-B201	EU	60Ja-0001	NO_X	40 CFR Part 60,	§ 60.102a(a)	Each owner or operator that	§ 60.104a(a)	§ 60.108a	§ 60.108a

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Subpart Ja	§ 60.100a § 60.100a(a) § 60.100a(b) § 60.102a § 60.102a(g) § 60.102a(g)(2) § 60.102a(g)(2)(ii) § 60.102a(g)(2)(ii)(B)	is subject to the requirements of this subpart shall comply with the emissions limitations in § 60.102a(b)-(h) on and after the date on which the initial performance test, required by § 60.8, is completed, but not later than 60 days after achieving the maximum production rate at which the affected facility will be operated, or 180 days after initial startup, whichever comes first.	§ 60.104a(c) § 60.104a(i) § 60.104a(i)(1) § 60.104a(i)(2) § 60.104a(i)(3) § 60.104a(i)(5) § 60.104a(i)(7) § 60.104a(i)(8) § 60.107a(c)(1) § 60.107a(c)(2) § 60.107a(c)(3) § 60.107a(c)(4) § 60.107a(c)(5) § 60.107a(d) § 60.107a(d)(1) § 60.107a(d)(2) § 60.107a(d)(4) § 60.107a(d)(5) § 60.107a(d)(7) § 60.107a(i) § 60.107a(i)(3) § 60.107a(i)(3)(ii)	§ 60.108a(a)	§ 60.108a(a) § 60.108a(b) § 60.108a(d) § 60.108a(d)(1) § 60.108a(d)(2) § 60.108a(d)(3) § 60.108a(d)(4) § 60.108a(d)(5) § 60.108a(d)(6) § 60.108a(d)(7)
NDU2-B201	EU	60Ja-0001	Hydrogen Sulfide	40 CFR Part 60, Subpart Ja	§ 60.102a(a) § 60.100a § 60.100a(a) § 60.100a(b) § 60.102a § 60.102a(g) § 60.102a(g)(1) § 60.102a(g)(1)(ii) § 60.103a § 60.103a(c) § 60.103a(c)(2) § 60.103a(d) § 60.103a(d)(1) § 60.103a(d)(5) § 60.103a(e) § 60.103a(e)(1) § 60.103a(e)(2)	Each owner or operator that is subject to the requirements of this subpart shall comply with the emissions limitations in § 60.102a(b)-(h) on and after the date on which the initial performance test, required by § 60.8, is completed, but not later than 60 days after achieving the maximum production rate at which the affected facility will be operated, or 180 days after initial startup, whichever comes first.	§ 60.104a § 60.104a(a) § 60.104a(c) § 60.104a(j) § 60.104a(j)(4)(iv) § 60.107a § 60.107a(a) § 60.107a(a)(2) § 60.107a(a)(2)(i) § 60.107a(a)(2)(ii) § 60.107a(a)(2)(iii) § 60.107a(a)(2)(iv) § 60.107a(i) § 60.107a(i)(1) § 60.107a(i)(1)(ii)	§ 60.108a § 60.108a(a) § 60.108a(c) § 60.108a(c)(6) § 60.108a(c)(6)(i) § 60.108a(c)(6)(ii) § 60.108a(c)(6)(iii) § 60.108a(c)(6)(ix) § 60.108a(c)(6)(v) § 60.108a(c)(6)(vii) § 60.108a(c)(6)(viii) § 60.108a(c)(6)(x)	§ 60.108a § 60.108a(a) § 60.108a(b) § 60.108a(d) § 60.108a(d)(1) § 60.108a(d)(2) § 60.108a(d)(3) § 60.108a(d)(4) § 60.108a(d)(5) § 60.108a(d)(6) § 60.108a(d)(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.103a(e)(3)				
NDU2-B201	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7500(a)(1)-Table 3.1 § 63.7499(l) § 63.7500(a) § 63.7500(a)(3) § 63.7500(e) § 63.7505(a) § 63.7510(g) § 63.7515(g) § 63.7530(f) § 63.7540(a)(12) § 63.7540(a)(13)	A new or existing limited use boiler or process heater with a heat input capacity of less than or equal to 5 million Btu per hour must conduct a tune-up of the boiler or process heater every 5 years as specified in § 63.7540.	§ 63.7510(g) § 63.7515(d) § 63.7515(g) § 63.7540(a)(12) § 63.7540(a)(13)	§ 63.7555(a) § 63.7555(a)(1) § 63.7555(h) § 63.7560(a) § 63.7560(b) § 63.7560(c)	§ 63.7530(f) § 63.7545(a) § 63.7545(c) § 63.7545(e) § 63.7545(e)(1) § 63.7545(e)(6) § 63.7545(e)(7) § 63.7545(e)(8) § 63.7545(e)(8)(i) § 63.7545(f) [G]§ 63.7545(h) § 63.7550(a) [G]§ 63.7550(b) § 63.7550(c) § 63.7550(c)(1) § 63.7550(c)(5)(i) § 63.7550(c)(5)(ii) § 63.7550(c)(5)(iii) § 63.7550(c)(5)(xiv) § 63.7550(c)(5)(xvii) § 63.7550(h) § 63.7550(h)(3)
NDU2-B202	EU	R7300-0001	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of §	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(2) § 117.335(g) § 117.340(a) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) [G]§ 117.340(c)(3) [G]§ 117.340(f)(2) § 117.340(l)(2)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	§ 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)		[G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
NDU2-B202	EU	R7300-0001	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a) § 117.340(b)(1) § 117.340(b)(3) § 117.340(e) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							[G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)		
NDU2-B202	EU	R7300-0001	NH_3	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(2) § 117.310(c)(2)(B) § 117.340(f)(1)	For process heaters that inject urea or ammonia into the exhaust stream for NO_x control, ammonia emissions must not exceed 10 ppmv at 3.0% O_2, dry.	§ 117.335(a)(2) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(g) § 117.340(b)(1) § 117.340(b)(3) § 117.340(d) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8130 § 117.8130(4)	§ 117.345(a) § 117.345(f) § 117.345(f)(11) [G]§ 117.345(f)(2) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
NDU2-B202	EU	60Ja-0001	NO_X	40 CFR Part 60, Subpart Ja	§ 60.102a(a) § 60.100a § 60.100a(a) § 60.100a(b) § 60.102a § 60.102a(g) § 60.102a(g)(2) § 60.102a(g)(2)(ii) § 60.102a(g)(2)(ii)(B)	Each owner or operator that is subject to the requirements of this subpart shall comply with the emissions limitations in § 60.102a(b)-(h) on and after the date on which the initial performance test, required by § 60.8, is completed, but not later than 60 days after achieving the maximum production rate at which the affected facility will be operated, or 180 days after initial startup, whichever comes first.	§ 60.104a(a) § 60.104a(c) § 60.104a(i) § 60.104a(i)(1) § 60.104a(i)(2) § 60.104a(i)(3) § 60.104a(i)(5) § 60.104a(i)(7) § 60.104a(i)(8) § 60.107a(c)(1) § 60.107a(c)(2) § 60.107a(c)(3) § 60.107a(c)(4) § 60.107a(c)(5) § 60.107a(d) § 60.107a(d)(1) § 60.107a(d)(2) § 60.107a(d)(4) § 60.107a(d)(5) § 60.107a(d)(7) § 60.107a(i) § 60.107a(i)(3) § 60.107a(i)(3)(ii)	§ 60.108a § 60.108a(a)	§ 60.108a § 60.108a(a) § 60.108a(b) § 60.108a(d) § 60.108a(d)(1) § 60.108a(d)(2) § 60.108a(d)(3) § 60.108a(d)(4) § 60.108a(d)(5) § 60.108a(d)(6) § 60.108a(d)(7)
NDU2-B202	EU	60Ja-0001	Hydrogen Sulfide	40 CFR Part 60, Subpart Ja	§ 60.102a(a) § 60.100a § 60.100a(a) § 60.100a(b) § 60.102a § 60.102a(g) § 60.102a(g)(1) § 60.102a(g)(1)(ii) § 60.103a § 60.103a(c) § 60.103a(c)(2) § 60.103a(d) § 60.103a(d)(1) § 60.103a(d)(5) § 60.103a(e) § 60.103a(e)(1)	Each owner or operator that is subject to the requirements of this subpart shall comply with the emissions limitations in § 60.102a(b)-(h) on and after the date on which the initial performance test, required by § 60.8, is completed, but not later than 60 days after achieving the maximum production rate at which the affected facility will be operated, or 180 days after initial startup, whichever comes first.	§ 60.104a § 60.104a(a) § 60.104a(c) § 60.104a(j) § 60.104a(j)(4)(iv) § 60.107a § 60.107a(a) § 60.107a(a)(2) § 60.107a(a)(2)(i) § 60.107a(a)(2)(ii) § 60.107a(a)(2)(iii) § 60.107a(a)(2)(iv) § 60.107a(i) § 60.107a(i)(1) § 60.107a(i)(1)(ii)	§ 60.108a § 60.108a(a) § 60.108a(c) § 60.108a(c)(6) § 60.108a(c)(6)(i) § 60.108a(c)(6)(ii) § 60.108a(c)(6)(iii) § 60.108a(c)(6)(ix) § 60.108a(c)(6)(v) § 60.108a(c)(6)(vii) § 60.108a(c)(6)(viii) § 60.108a(c)(6)(x)	§ 60.108a § 60.108a(a) § 60.108a(b) § 60.108a(d) § 60.108a(d)(1) § 60.108a(d)(2) § 60.108a(d)(3) § 60.108a(d)(4) § 60.108a(d)(5) § 60.108a(d)(6) § 60.108a(d)(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.103a(e)(2) § 60.103a(e)(3)				
NDU2-B202	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7500(a)(1)-Table 3.1 § 63.7499(l) § 63.7500(a) § 63.7500(a)(3) § 63.7500(e) § 63.7505(a) § 63.7510(g) § 63.7515(g) § 63.7530(f) § 63.7540(a)(12) § 63.7540(a)(13)	A new or existing limited use boiler or process heater with a heat input capacity of less than or equal to 5 million Btu per hour must conduct a tune-up of the boiler or process heater every 5 years as specified in § 63.7540.	§ 63.7510(g) § 63.7515(d) § 63.7515(g) § 63.7540(a)(12) § 63.7540(a)(13)	§ 63.7555(a) § 63.7555(a)(1) § 63.7555(h) § 63.7560(a) § 63.7560(b) § 63.7560(c)	§ 63.7530(f) § 63.7545(a) § 63.7545(c) § 63.7545(e) § 63.7545(e)(1) § 63.7545(e)(6) § 63.7545(e)(7) § 63.7545(e)(8) § 63.7545(e)(8)(i) § 63.7545(f) [G]§ 63.7545(h) § 63.7550(a) [G]§ 63.7550(b) § 63.7550(c) § 63.7550(c)(1) § 63.7550(c)(5)(i) § 63.7550(c)(5)(ii) § 63.7550(c)(5)(iii) § 63.7550(c)(5)(xiv) § 63.7550(c)(5)(xvii) § 63.7550(h) § 63.7550(h)(3)
NDU2-FUG1	EU	60GGGa-01	VOC	40 CFR Part 60, Subpart GGGa	§ 60.592a(a) § 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(g) [G]§ 60.482-2a(b)(1) § 60.482-2a(b)(2) § 60.482-2a(b)(2)(ii) § 60.482-2a(c)(1) [G]§ 60.482-2a(c)(2) § 60.482-2a(d) [G]§ 60.482-2a(d)(1) § 60.482-2a(d)(2) § 60.482-2a(d)(3) [G]§ 60.482-2a(d)(6)	Comply with the requirements as stated in §60.482-2a for pumps in light liquid service.	§ 60.482-1a(f)(1) § 60.482-1a(f)(2) [G]§ 60.482-1a(f)(3) § 60.482-1a(g) § 60.482-2a(a)(1) § 60.482-2a(a)(2) § 60.482-2a(b)(2)(i) [G]§ 60.482-2a(d)(4) [G]§ 60.482-2a(d)(5) § 60.482-9a(a) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2) § 60.485a(c)(2)	§ 60.482-1a(g) § 60.485a(b)(2) [G]§ 60.486a(a)(3) [G]§ 60.486a(b) [G]§ 60.486a(c) § 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(2) [G]§ 60.486a(e)(4) § 60.486a(e)(7) [G]§ 60.486a(e)(8) § 60.486a(f) § 60.486a(f)(1) [G]§ 60.486a(h)	§ 60.487a(a) § 60.487a(b) § 60.487a(b)(1) § 60.487a(b)(3) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(iii) § 60.487a(c)(2)(iv) § 60.487a(c)(2)(ix) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 60.482-2a(e) § 60.482-2a(f) [G]§ 60.482-2a(g) § 60.482-2a(h) § 60.482-9a(a) § 60.482-9a(b) [G]§ 60.482-9a(d) § 60.482-9a(f) § 60.485a(b) § 60.485a(c) § 60.485a(c)(1) § 60.485a(f) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k) § 60.592a(d) § 60.592a(e)		[G]§ 60.485a(d) [G]§ 60.485a(e)		
NDU2-FUG1	EU	60GGGa-01	VOC	40 CFR Part 60, Subpart GGGa	§ 60.592a(a) § 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(g) § 60.482-6a(a)(1) § 60.482-6a(a)(2) § 60.482-6a(b) § 60.482-6a(e) § 60.485a(b) § 60.485a(f) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k) § 60.592a(d) § 60.592a(e)	Comply with the requirements as stated in §60.482-6a for open-ended valves and lines.	§ 60.482-1a(g) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2) [G]§ 60.485a(d)	§ 60.482-1a(g) § 60.485a(b)(2) § 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(8)	§ 60.487a(a) § 60.487a(b) § 60.487a(b)(1) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(ix) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)
NDU2-FUG1	EU	60GGGa-01	VOC	40 CFR Part 60, Subpart GGGa	§ 60.592a(a) § 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(g) § 60.482-7a(a)(1) § 60.482-7a(b)	Comply with the requirements as stated in §60.482-7a for valves in gas/vapor or light liquid service.	§ 60.482-1a(f)(1) § 60.482-1a(f)(2) [G]§ 60.482-1a(f)(3) § 60.482-1a(g) § 60.482-7a(a)(1) [G]§ 60.482-7a(a)(2)	§ 60.482-1a(g) § 60.485a(b)(2) § 60.486a(a)(2) [G]§ 60.486a(a)(3) [G]§ 60.486a(b) [G]§ 60.486a(c)	§ 60.482-1a(g) § 60.487a(a) § 60.487a(b) § 60.487a(b)(1) § 60.487a(b)(2) § 60.487a(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 60.482-7a(d) [G]§ 60.482-7a(e) [G]§ 60.482-7a(h) § 60.485a(b) § 60.485a(c) § 60.485a(c)(1) § 60.485a(f) § 60.486a(a)(1) § 60.486a(k) § 60.592a(d) § 60.592a(e)		[G]§ 60.482-7a(c) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2) § 60.485a(c)(2) [G]§ 60.485a(d) [G]§ 60.485a(e) § 60.593a(d)	§ 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(2) [G]§ 60.486a(e)(4) [G]§ 60.486a(e)(8) § 60.486a(f) § 60.486a(f)(1) § 60.486a(f)(2)	§ 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(i) § 60.487a(c)(2)(ii) § 60.487a(c)(2)(ix) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)
NDU2-FUG1	EU	60GGGa-01	VOC	40 CFR Part 60, Subpart GGGa	§ 60.592a(a) § 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(g) [G]§ 60.482-2a(c)(2) [G]§ 60.482-7a(e) § 60.482-8a(a) § 60.482-8a(a)(2) § 60.482-8a(b) [G]§ 60.482-8a(c) § 60.482-8a(d) § 60.482-9a(a) § 60.482-9a(b) [G]§ 60.482-9a(d) § 60.482-9a(f) § 60.485a(b) § 60.485a(f) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k) § 60.592a(d) § 60.592a(e)	Comply with the requirements as stated in §60.482-8a for pumps in heavy liquid service.	§ 60.482-1a(g) § 60.482-8a(a)(1) § 60.482-9a(a) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2) [G]§ 60.485a(d)	§ 60.482-1a(g) § 60.485a(b)(2) [G]§ 60.486a(a)(3) [G]§ 60.486a(b) [G]§ 60.486a(c) § 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(8)	§ 60.487a(a) § 60.487a(b) § 60.487a(b)(1) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(ix) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)
NDU2-FUG1	EU	60GGGa-01	VOC	40 CFR Part 60, Subpart GGGa	§ 60.592a(a) § 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(g) [G]§ 60.482-2a(c)(2)	Comply with the requirements as stated in §60.482-8a for valves in heavy liquid service.	§ 60.482-1a(g) § 60.482-8a(a)(1) § 60.482-9a(a) § 60.485a(a) [G]§ 60.485a(b)(1)	§ 60.482-1a(g) § 60.485a(b)(2) [G]§ 60.486a(a)(3) [G]§ 60.486a(b) [G]§ 60.486a(c)	§ 60.487a(a) § 60.487a(b) § 60.487a(b)(1) § 60.487a(c) § 60.487a(c)(1)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 60.482-7a(e) § 60.482-8a(a) § 60.482-8a(a)(2) § 60.482-8a(b) [G]§ 60.482-8a(c) § 60.482-8a(d) § 60.482-9a(a) § 60.482-9a(b) § 60.482-9a(c) § 60.482-9a(c)(1) § 60.482-9a(e) § 60.482-9a(f) § 60.485a(b) § 60.485a(f) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k) § 60.592a(d) § 60.592a(e)		§ 60.485a(b)(2) [G]§ 60.485a(d)	§ 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(8)	§ 60.487a(c)(2) § 60.487a(c)(2)(ix) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)
NDU2-FUG1	EU	60GGGa-01	VOC	40 CFR Part 60, Subpart GGGa	§ 60.592a(a) § 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(g) [G]§ 60.482-2a(c)(2) [G]§ 60.482-7a(e) § 60.482-8a(a) § 60.482-8a(a)(2) § 60.482-8a(b) [G]§ 60.482-8a(c) § 60.482-8a(d) § 60.482-9a(a) § 60.482-9a(b) § 60.482-9a(c) § 60.482-9a(c)(1) § 60.482-9a(c)(2) § 60.482-9a(f) § 60.485a(b) § 60.485a(f) § 60.486a(a)(1)	Comply with the requirements as stated in §60.482-8a for connectors in heavy liquid service.	§ 60.482-1a(g) § 60.482-8a(a)(1) § 60.482-9a(a) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2) [G]§ 60.485a(d)	§ 60.482-1a(g) § 60.485a(b)(2) [G]§ 60.486a(a)(3) [G]§ 60.486a(b) [G]§ 60.486a(c) § 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(8)	§ 60.487a(a) § 60.487a(b) § 60.487a(b)(1) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(ix) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.486a(a)(2) § 60.486a(k) § 60.592a(d) § 60.592a(e)				
NDU2-FUG1	EU	60GGGa-01	VOC	40 CFR Part 60, Subpart GGGa	§ 60.593a(g) § 60.482-11a(b)(2) § 60.482-11a(b)(3) § 60.482-11a(b)(3)(i) § 60.482-11a(d) [G]§ 60.482-11a(e) [G]§ 60.482-11a(f)(1) § 60.482-11a(f)(2) § 60.482-11a(g) § 60.485a(b) § 60.486a(a)(1) § 60.486a(a)(2) § 60.592a(d) § 60.592a(e)	Connectors in gas/vapor or light liquid service are exempt from the requirements in §60.482-11a, provided the owner or operator complies with §60.482-8a for all connectors, not just those in heavy liquid service.	§ 60.482-11a(a) § 60.482-11a(b) § 60.482-11a(b)(1) § 60.482-11a(b)(3) § 60.482-11a(b)(3)(ii) [G]§ 60.482-11a(b)(3)(iii) § 60.482-11a(b)(3)(iv) § 60.482-11a(c) § 60.485a(b)(2) [G]§ 60.485a(e) § 60.593a(d)	§ 60.482-11a(b)(3)(v) § 60.485a(b)(2) [G]§ 60.486a(a)(3) [G]§ 60.486a(b) [G]§ 60.486a(c) § 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(8) § 60.486a(e)(9) § 60.486a(f) § 60.486a(f)(1)	§ 60.487a(b) § 60.487a(b)(1) § 60.487a(b)(5) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(i) § 60.487a(c)(2)(ix) § 60.487a(c)(2)(vii) § 60.487a(c)(2)(viii) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)
NDU-CTWR	EU	63CC-002	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.654(a) § 63.640(h)(6)	Except as specified in paragraph (b) of this section, the owner or operator of a heat exchange system that meets the criteria in §63.640(c)(8) must comply with the requirements of paragraphs (c) through (g) of this section.	§ 63.642(d)(1) § 63.642(d)(3) § 63.642(d)(4) [G]§ 63.654(c) [G]§ 63.654(d) § 63.654(e) [G]§ 63.654(f) [G]§ 63.654(g)	§ 63.642(e) § 63.655(h)(1) [G]§ 63.655(i)(4) § 63.655(i)(5)	§ 63.642(d)(2) § 63.642(f) § 63.655(f) § 63.655(f)(1)(vi) § 63.655(f)(4) § 63.655(g) [G]§ 63.655(g)(9) § 63.655(h)(1)
NDU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(d)	Comply with the requirements as stated in §60.482-1(d) for equipment in vacuum service.	None	§ 60.486(e) § 60.486(e)(1) § 60.486(e)(5)	None
NDU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-2 [G]§ 60.482-9	Comply with the requirements as stated in §60.482-2 for pumps in light-liquid service.	[G]§ 60.482-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							[G]§ 60.485(e) § 60.485(f) § 60.592(d) § 60.593(d)	[G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	
NDU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.593(b)(1)	Compressors in hydrogen service are exempt from the requirements of §60.592 if an owner or operator demonstrates that a compressor is in hydrogen service.	§ 60.593(b)(2) [G]§ 60.593(b)(3)	None	None
NDU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-3 [G]§ 60.482-9	Comply with the requirements as stated in §60.482-3 for compressors.	[G]§ 60.482-3 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
NDU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-4 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-4 for pressure relief devices in gas/vapor service.	[G]§ 60.482-4 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(3) [G]§ 60.486(e)(4) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
NDU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-5 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-5 for sampling connection systems.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
NDU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a)	Comply with the requirements in as stated in	§ 60.485(a) [G]§ 60.485(b)	[G]§ 60.486(a) § 60.486(e)	§ 60.487(a) [G]§ 60.487(b)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.482-1(b) [G]§ 60.482-6 [G]§ 60.482-9	§60.482-6 for open-ended valves and lines.	[G]§ 60.485(d) § 60.485(f) § 60.592(d)	§ 60.486(e)(1) § 60.486(j) § 60.592(e)	[G]§ 60.487(c) § 60.487(e) § 60.592(e)
NDU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-7 [G]§ 60.482-9 [G]§ 60.483-1 [G]§ 60.483-2 § 60.592(b)	Comply with the requirements in as stated in §60.482-7 for valves in gas/vapor or light-liquid service.	[G]§ 60.482-7 [G]§ 60.483-1 [G]§ 60.483-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d) § 60.593(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) [G]§ 60.486(g) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(d) § 60.487(e) § 60.592(e)
NDU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for pumps in heavy-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
NDU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) § 60.482-10(b) § 60.482-10(e) § 60.482-10(m)	Comply with the requirements in as stated in §60.482-10 for vapor recovery devices.	§ 60.485(a) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
NDU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.18 § 60.482-1(a) § 60.482-1(b) § 60.482-10(d) § 60.482-10(e) § 60.482-10(m)	Comply with the requirements in as stated in §60.482-10 for flares.	§ 60.485(a) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) [G]§ 60.485(g) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
NDU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a)	Comply with the requirements in as stated in	[G]§ 60.482-10(f) § 60.482-10(i)	[G]§ 60.482-10(j) [G]§ 60.482-10(k)	§ 60.487(a) [G]§ 60.487(b)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.482-1(b) § 60.482-10(e) [G]§ 60.482-10(g) § 60.482-10(h) § 60.482-10(m)	§60.482-10 for closed-vent systems.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.482-10(l) [G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1) § 60.592(e)	[G]§ 60.487(c) § 60.487(e) § 60.592(e)
NDU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for valves in heavy-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
NDU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for flanges or other connectors.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
NDU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for pressure relief devices in light-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
NDU-OWS	EU	R5131-0010	VOC	30 TAC Chapter 115, Water Separation	§ 115.132(a)(3) § 115.131(a)	VOC water separator compartments must be equipped with a vapor recovery system which satisfies the provisions of §115.131(a) of this title.	[G]§ 115.135(a) § 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	§ 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	None
NDU-OWS	EU	61FF-1769	Benzene	40 CFR Part 61, Subpart FF	§ 61.347(a)(1) § 61.347(a)(1)(i)(A) § 61.347(a)(1)(i)(B)	Install, operate, and maintain a fixed-roof and closed-vent system that	§ 61.347(a)(1)(i)(A) § 61.347(b) § 61.349(a)(1)(i)	§ 61.349(a)(1)(ii) § 61.355(i)(1) § 61.355(i)(3)(ii)(A)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(I)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 61.347(b) § 61.347(c) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	routes all organic vapors vented from the oil-water separator to a control device.	§ 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(d) § 61.354(f)(1) [G]§ 61.355(h) § 61.355(i)(1) § 61.355(i)(2) § 61.355(i)(3)(i) § 61.355(i)(3)(ii) § 61.355(i)(3)(ii)(A) § 61.355(i)(3)(ii)(B) § 61.355(i)(3)(ii)(C) § 61.355(i)(3)(iii) § 61.355(i)(3)(iv) § 61.355(i)(4)	§ 61.356(d) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2)(i)(G) [G]§ 61.356(f)(3) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i)	
OILUNLOAD	EU	R5211-0008	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(a)(1) § 115.212(a)(2) § 115.214(a)(1)(B) § 115.214(a)(1)(D) § 115.214(a)(1)(D)(i)	Vapor pressure (at land-based operations). All land-based loading and unloading of VOC with a true vapor pressure less than 0.5 psia is exempt from the requirements of this division, except as specified.	§ 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.215 § 115.215(4)	§ 115.216 § 115.216(2) § 115.216(3)(B)	None
P-617	EU	R7300-0005	Exempt	30 TAC Chapter 117, Subchapter B	§ 117.303(a)(6)(D) [G]§ 117.310(f)	Units exempted from the provisions of this division, except as specified in §§117.310(f), 117.340(j), 117.345(f)(6) and (10), 117.350(c)(1), and 117.354(a)(5), include stationary gas turbines and stationary internal combustion engines that are used exclusively in emergency situations, except that operation for	[G]§ 117.8140(a) § 117.8140(b)	§ 117.340(j) [G]§ 117.345(f)(10) [G]§ 117.345(f)(6)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						testing or maintenance purposes is allowed for up to 52 hours per year, based on a rolling 12-month average.			
P-617	EU	63ZZZZ-0007	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6602-Table2c.1 § 63.6595(a)(1) § 63.6605(a) § 63.6605(b) § 63.6625(e) § 63.6625(h) § 63.6625(i) § 63.6640(b) § 63.6640(f)(1) [G]§ 63.6640(f)(2) § 63.6640(f)(3)	For each existing emergency stationary CI RICE and black start stationary CI RICE, located at a major source, you must comply with the requirements as specified in Table 2c.1.a-c.	§ 63.6625(f) § 63.6625(i) § 63.6640(a) § 63.6640(a)-Table6.9.a.i § 63.6640(a)-Table6.9.a.ii § 63.6640(b)	§ 63.6625(i) § 63.6655(a) § 63.6655(a)(1) § 63.6655(d) § 63.6655(e) § 63.6655(f) § 63.6660(a) § 63.6660(b) § 63.6660(c)	§ 63.6640(b) § 63.6640(e) § 63.6650(f)
P-618	EU	R7300-0005	Exempt	30 TAC Chapter 117, Subchapter B	§ 117.303(a)(6)(D) [G]§ 117.310(f)	Units exempted from the provisions of this division, except as specified in §§117.310(f), 117.340(j), 117.345(f)(6) and (10), 117.350(c)(1), and 117.354(a)(5), include stationary gas turbines and stationary internal combustion engines that are used exclusively in emergency situations, except that operation for testing or maintenance purposes is allowed for up to 52 hours per year, based on a rolling 12-month average.	[G]§ 117.8140(a) § 117.8140(b)	§ 117.340(j) [G]§ 117.345(f)(10) [G]§ 117.345(f)(6)	None
P-618	EU	63ZZZZ-0007	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6602-Table2c.1 § 63.6595(a)(1) § 63.6605(a) § 63.6605(b)	For each existing emergency stationary CI RICE and black start stationary CI RICE, located	§ 63.6625(f) § 63.6625(i) § 63.6640(a) § 63.6640(a)-	§ 63.6625(i) § 63.6655(a) § 63.6655(a)(1) § 63.6655(d)	§ 63.6640(b) § 63.6640(e) § 63.6650(f)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.6625(e) § 63.6625(h) § 63.6625(i) § 63.6640(b) § 63.6640(f)(1) [G]§ 63.6640(f)(2) § 63.6640(f)(3)	at a major source, you must comply with the requirements as specified in Table 2c.1.a-c.	Table6.9.a.i § 63.6640(a)-Table6.9.a.ii § 63.6640(b)	§ 63.6655(e) § 63.6655(f) § 63.6660(a) § 63.6660(b) § 63.6660(c)	
P-J16A	EU	R7300-0003	Exempt	30 TAC Chapter 117, Subchapter B	[G]§ 117.303(a)(11) [G]§ 117.310(f)	Units exempted from the provisions of this division except as specified in §§117.310(f), 117.340(j), 117.345(f)(6) and (10), 117.350(c)(1) and 117.354(a)(5) include new, modified, reconstructed, or relocated stationary diesel engine placed into service on or after October 1, 2001, that operates less than 100 hours per year, based on a rolling 12-month average, in other than emergency situations; and meets the requirements for non-road engines as specified. §117.303(a)(11)(A)-(B)	[G]§ 117.8140(a) § 117.8140(b)	§ 117.340(j) [G]§ 117.345(f)(10) [G]§ 117.345(f)(6)	None
P-J16A	EU	63ZZZZ-0011	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6602-Table2c.1 § 63.6595(a)(1) § 63.6605(a) § 63.6605(b) § 63.6625(e) § 63.6625(h) § 63.6625(i) § 63.6640(b) § 63.6640(f)(1) [G]§ 63.6640(f)(2) § 63.6640(f)(3)	For each existing emergency stationary CI RICE and black start stationary CI RICE, located at a major source, you must comply with the requirements as specified in Table 2c.1.a-c.	§ 63.6625(f) § 63.6625(i) § 63.6640(a) § 63.6640(a)-Table6.9.a.i § 63.6640(a)-Table6.9.a.ii § 63.6640(b)	§ 63.6625(i) § 63.6655(a) § 63.6655(a)(1) § 63.6655(d) § 63.6655(e) § 63.6655(f) § 63.6660(a) § 63.6660(b) § 63.6660(c)	§ 63.6640(b) § 63.6640(e) § 63.6650(f)
P-J16B	EU	R7300-	Exempt	30 TAC Chapter	[G]§ 117.303(a)(11)	Units exempted from the	[G]§ 117.8140(a)	§ 117.340(j)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		0003		117, Subchapter B	[G]§ 117.310(f)	provisions of this division except as specified in §§117.310(f), 117.340(j), 117.345(f)(6) and (10), 117.350(c)(1) and 117.354(a)(5) include new, modified, reconstructed, or relocated stationary diesel engine placed into service on or after October 1, 2001, that operates less than 100 hours per year, based on a rolling 12-month average, in other than emergency situations; and meets the requirements for non-road engines as specified. §117.303(a)(11)(A)-(B)	§ 117.8140(b)	[G]§ 117.345(f)(10) [G]§ 117.345(f)(6)	
P-J16B	EU	63ZZZZ-0011	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6602-Table2c.1 § 63.6595(a)(1) § 63.6605(a) § 63.6605(b) § 63.6625(e) § 63.6625(h) § 63.6625(i) § 63.6640(b) § 63.6640(f)(1) [G]§ 63.6640(f)(2) § 63.6640(f)(3)	For each existing emergency stationary CI RICE and black start stationary CI RICE, located at a major source, you must comply with the requirements as specified in Table 2c.1.a-c.	§ 63.6625(f) § 63.6625(i) § 63.6640(a) § 63.6640(a)-Table6.9.a.i § 63.6640(a)-Table6.9.a.ii § 63.6640(b)	§ 63.6625(i) § 63.6655(a) § 63.6655(a)(1) § 63.6655(d) § 63.6655(e) § 63.6655(f) § 63.6660(a) § 63.6660(b) § 63.6660(c)	§ 63.6640(b) § 63.6640(e) § 63.6650(f)
P-J35A	EU	R7300-0005	Exempt	30 TAC Chapter 117, Subchapter B	§ 117.303(a)(6)(D) [G]§ 117.310(f)	Units exempted from the provisions of this division, except as specified in §§117.310(f), 117.340(j), 117.345(f)(6) and (10), 117.350(c)(1), and 117.354(a)(5), include stationary gas turbines and stationary internal	[G]§ 117.8140(a) § 117.8140(b)	§ 117.340(j) [G]§ 117.345(f)(10) [G]§ 117.345(f)(6)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						combustion engines that are used exclusively in emergency situations, except that operation for testing or maintenance purposes is allowed for up to 52 hours per year, based on a rolling 12-month average.			
P-J35A	EU	63ZZZZ-0010	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6602-Table2c.1 § 63.6595(a)(1) § 63.6605(a) § 63.6605(b) § 63.6625(e) § 63.6625(h) § 63.6625(i) § 63.6640(b) § 63.6640(f)(1) [G]§ 63.6640(f)(2) § 63.6640(f)(3)	For each existing emergency stationary CI RICE and black start stationary CI RICE, located at a major source, you must comply with the requirements as specified in Table 2c.1.a-c.	§ 63.6625(f) § 63.6625(i) § 63.6640(a) § 63.6640(a)-Table6.9.a.i § 63.6640(a)-Table6.9.a.ii § 63.6640(b)	§ 63.6625(i) § 63.6655(a) § 63.6655(a)(1) § 63.6655(d) § 63.6655(e) § 63.6655(f) § 63.6660(a) § 63.6660(b) § 63.6660(c)	§ 63.6640(b) § 63.6640(e) § 63.6650(f)
P-J35B	EU	R7300-0005	Exempt	30 TAC Chapter 117, Subchapter B	§ 117.303(a)(6)(D) [G]§ 117.310(f)	Units exempted from the provisions of this division, except as specified in §§117.310(f), 117.340(j), 117.345(f)(6) and (10), 117.350(c)(1), and 117.354(a)(5), include stationary gas turbines and stationary internal combustion engines that are used exclusively in emergency situations, except that operation for testing or maintenance purposes is allowed for up to 52 hours per year, based on a rolling 12-month average.	[G]§ 117.8140(a) § 117.8140(b)	§ 117.340(j) [G]§ 117.345(f)(10) [G]§ 117.345(f)(6)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
P-J35B	EU	63ZZZZ-0010	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6602-Table2c.1 § 63.6595(a)(1) § 63.6605(a) § 63.6605(b) § 63.6625(e) § 63.6625(h) § 63.6625(i) § 63.6640(b) § 63.6640(f)(1) [G]§ 63.6640(f)(2) § 63.6640(f)(3)	For each existing emergency stationary CI RICE and black start stationary CI RICE, located at a major source, you must comply with the requirements as specified in Table 2c.1.a-c.	§ 63.6625(f) § 63.6625(i) § 63.6640(a) § 63.6640(a)-Table6.9.a.i § 63.6640(a)-Table6.9.a.ii § 63.6640(b)	§ 63.6625(i) § 63.6655(a) § 63.6655(a)(1) § 63.6655(d) § 63.6655(e) § 63.6655(f) § 63.6660(a) § 63.6660(b) § 63.6660(c)	§ 63.6640(b) § 63.6640(e) § 63.6650(f)
P-J53A	EU	R7300-0005	Exempt	30 TAC Chapter 117, Subchapter B	§ 117.303(a)(6)(D) [G]§ 117.310(f)	Units exempted from the provisions of this division, except as specified in §§117.310(f), 117.340(j), 117.345(f)(6) and (10), 117.350(c)(1), and 117.354(a)(5), include stationary gas turbines and stationary internal combustion engines that are used exclusively in emergency situations, except that operation for testing or maintenance purposes is allowed for up to 52 hours per year, based on a rolling 12-month average.	[G]§ 117.8140(a) § 117.8140(b)	§ 117.340(j) [G]§ 117.345(f)(10) [G]§ 117.345(f)(6)	None
P-J53A	EU	63ZZZZ-0010	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6602-Table2c.1 § 63.6595(a)(1) § 63.6605(a) § 63.6605(b) § 63.6625(e) § 63.6625(h) § 63.6625(i) § 63.6640(b) § 63.6640(f)(1)	For each existing emergency stationary CI RICE and black start stationary CI RICE, located at a major source, you must comply with the requirements as specified in Table 2c.1.a-c.	§ 63.6625(f) § 63.6625(i) § 63.6640(a) § 63.6640(a)-Table6.9.a.i § 63.6640(a)-Table6.9.a.ii § 63.6640(b)	§ 63.6625(i) § 63.6655(a) § 63.6655(a)(1) § 63.6655(d) § 63.6655(e) § 63.6655(f) § 63.6660(a) § 63.6660(b) § 63.6660(c)	§ 63.6640(b) § 63.6640(e) § 63.6650(f)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 63.6640(f)(2) § 63.6640(f)(3)				
P-J53B	EU	R7300-0005	Exempt	30 TAC Chapter 117, Subchapter B	§ 117.303(a)(6)(D) [G]§ 117.310(f)	Units exempted from the provisions of this division, except as specified in §§117.310(f), 117.340(j), 117.345(f)(6) and (10), 117.350(c)(1), and 117.354(a)(5), include stationary gas turbines and stationary internal combustion engines that are used exclusively in emergency situations, except that operation for testing or maintenance purposes is allowed for up to 52 hours per year, based on a rolling 12-month average.	[G]§ 117.8140(a) § 117.8140(b)	§ 117.340(j) [G]§ 117.345(f)(10) [G]§ 117.345(f)(6)	None
P-J53B	EU	63ZZZZ-0010	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6602-Table2c.1 § 63.6595(a)(1) § 63.6605(a) § 63.6605(b) § 63.6625(e) § 63.6625(h) § 63.6625(i) § 63.6640(b) § 63.6640(f)(1) [G]§ 63.6640(f)(2) § 63.6640(f)(3)	For each existing emergency stationary CI RICE and black start stationary CI RICE, located at a major source, you must comply with the requirements as specified in Table 2c.1.a-c.	§ 63.6625(f) § 63.6625(i) § 63.6640(a) § 63.6640(a)-Table6.9.a.i § 63.6640(a)-Table6.9.a.ii § 63.6640(b)	§ 63.6625(i) § 63.6655(a) § 63.6655(a)(1) § 63.6655(d) § 63.6655(e) § 63.6655(f) § 63.6660(a) § 63.6660(b) § 63.6660(c)	§ 63.6640(b) § 63.6640(e) § 63.6650(f)
P-J615	EU	R7300-0005	Exempt	30 TAC Chapter 117, Subchapter B	§ 117.303(a)(6)(D) [G]§ 117.310(f)	Units exempted from the provisions of this division, except as specified in §§117.310(f), 117.340(j), 117.345(f)(6) and (10), 117.350(c)(1), and 117.354(a)(5), include	[G]§ 117.8140(a) § 117.8140(b)	§ 117.340(j) [G]§ 117.345(f)(10) [G]§ 117.345(f)(6)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						stationary gas turbines and stationary internal combustion engines that are used exclusively in emergency situations, except that operation for testing or maintenance purposes is allowed for up to 52 hours per year, based on a rolling 12-month average.			
P-J615	EU	63ZZZZ-0005	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6602-Table2c.1 § 63.6595(a)(1) § 63.6605(a) § 63.6605(b) § 63.6625(e) § 63.6625(h) § 63.6625(i) § 63.6640(b) § 63.6640(f)(1) [G]§ 63.6640(f)(2) § 63.6640(f)(3)	For each existing emergency stationary CI RICE and black start stationary CI RICE, located at a major source, you must comply with the requirements as specified in Table 2c.1.a-c.	§ 63.6625(f) § 63.6625(i) § 63.6640(a) § 63.6640(a)-Table6.9.a.i § 63.6640(a)-Table6.9.a.ii § 63.6640(b)	§ 63.6625(i) § 63.6655(a) § 63.6655(a)(1) § 63.6655(d) § 63.6655(e) § 63.6655(f) § 63.6660(a) § 63.6660(b) § 63.6660(c)	§ 63.6640(b) § 63.6640(e) § 63.6650(f)
P-J616	EU	R7300-0005	Exempt	30 TAC Chapter 117, Subchapter B	§ 117.303(a)(6)(D) [G]§ 117.310(f)	Units exempted from the provisions of this division, except as specified in §§117.310(f), 117.340(j), 117.345(f)(6) and (10), 117.350(c)(1), and 117.354(a)(5), include stationary gas turbines and stationary internal combustion engines that are used exclusively in emergency situations, except that operation for testing or maintenance purposes is allowed for up to 52 hours per year, based	[G]§ 117.8140(a) § 117.8140(b)	§ 117.340(j) [G]§ 117.345(f)(10) [G]§ 117.345(f)(6)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						on a rolling 12-month average.			
P-J616	EU	63ZZZZ-0005	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6602-Table2c.1 § 63.6595(a)(1) § 63.6605(a) § 63.6605(b) § 63.6625(e) § 63.6625(h) § 63.6625(i) § 63.6640(b) § 63.6640(f)(1) [G]§ 63.6640(f)(2) § 63.6640(f)(3)	For each existing emergency stationary CI RICE and black start stationary CI RICE, located at a major source, you must comply with the requirements as specified in Table 2c.1.a-c.	§ 63.6625(f) § 63.6625(i) § 63.6640(a) § 63.6640(a)-Table6.9.a.i § 63.6640(a)-Table6.9.a.ii § 63.6640(b)	§ 63.6625(i) § 63.6655(a) § 63.6655(a)(1) § 63.6655(d) § 63.6655(e) § 63.6655(f) § 63.6660(a) § 63.6660(b) § 63.6660(c)	§ 63.6640(b) § 63.6640(e) § 63.6650(f)
P-J682	EU	R7300-0005	Exempt	30 TAC Chapter 117, Subchapter B	§ 117.303(a)(6)(D) [G]§ 117.310(f)	Units exempted from the provisions of this division, except as specified in §§117.310(f), 117.340(j), 117.345(f)(6) and (10), 117.350(c)(1), and 117.354(a)(5), include stationary gas turbines and stationary internal combustion engines that are used exclusively in emergency situations, except that operation for testing or maintenance purposes is allowed for up to 52 hours per year, based on a rolling 12-month average.	[G]§ 117.8140(a) § 117.8140(b)	§ 117.340(j) [G]§ 117.345(f)(10) [G]§ 117.345(f)(6)	None
P-J682	EU	63ZZZZ-0004	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6602-Table2c.1 § 63.6595(a)(1) § 63.6605(a) § 63.6605(b) § 63.6625(e) § 63.6625(h) § 63.6625(i)	For each existing emergency stationary CI RICE and black start stationary CI RICE, located at a major source, you must comply with the requirements as specified in	§ 63.6625(f) § 63.6625(i) § 63.6640(a) § 63.6640(a)-Table6.9.a.i § 63.6640(a)-Table6.9.a.ii	§ 63.6625(i) § 63.6655(a) § 63.6655(a)(1) § 63.6655(d) § 63.6655(e) § 63.6655(f) § 63.6660(a)	§ 63.6640(b) § 63.6640(e) § 63.6650(f)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.6640(b) § 63.6640(f)(1) [G]§ 63.6640(f)(2) § 63.6640(f)(3)	Table 2c.1.a-c.	§ 63.6640(b)	§ 63.6660(b) § 63.6660(c)	
PRESSURE1	EU	R7300-0005	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B)	CO emissions must not exceed 3.0 g/hp-hr for stationary internal combustion engines.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a)(2)(C) § 117.340(h) § 117.345(f)(3) § 117.345(f)(3)(A) § 117.345(f)(3)(A)(ii) § 117.8000(b) § 117.8000(c) § 117.8000(c)(2) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8120 § 117.8120(2) [G]§ 117.8120(2)(A) § 117.8120(2)(B) § 117.8140(a) § 117.8140(a)(1) § 117.8140(a)(2) § 117.8140(a)(2)(A) [G]§ 117.8140(a)(2)(B) § 117.8140(b)	§ 117.345(a) § 117.345(f) [G]§ 117.345(f)(10) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
PRESSURE1	EU	60IIII-0007	CO	40 CFR Part 60, Subpart IIII	§ 60.4204(b) § 1039.101 § 60.4201(a) § 60.4206 § 60.4207(b) [G]§ 60.4211(a)	Owners and operators of non-emergency stationary CI ICE with a maximum engine power greater than or equal to 8 KW and less than 19 KW and a	None	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.4211(c) § 60.4218	displacement of less than 10 liters per cylinder and is a 2007 model year and later must comply with a CO emission limit of 6.6 g/KW-hr as stated in 40 CFR 60.4201(a) and 40 CFR 89.112(a) and 40 CFR 1039.102 and 40 CFR 1039.101.			
PRESSURE1	EU	60IIII-0007	NMHC and NO_X	40 CFR Part 60, Subpart IIII	§ 60.4204(b) § 1039.101 § 60.4201(a) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) § 60.4218	Owners and operators of non-emergency stationary CI ICE with a maximum engine power less than 19 KW and a displacement of less than 10 liters per cylinder and is a 2008 model year or later must comply with an NMHC+NOx emission limit of 7.5 g/KW-hr, as stated in 40 CFR 60.4201(a) and 40 CFR 1039.102 and 40 CFR 1039.101.	None	None	None
PRESSURE1	EU	60IIII-0007	PM (Opacity)	40 CFR Part 60, Subpart IIII	§ 60.4204(b) § 1039.105(b)(1) § 1039.105(b)(2) § 1039.105(b)(3) § 60.4201(a) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) § 60.4218	Owners and operators of non-emergency stationary CI ICE with a displacement of less than 10 liters per cylinder and is not a constant-speed engine and is a 2007 model year and later must comply with the following opacity emission limits: 20% during the acceleration mode, 15% during the lugging mode, and 50% during the peaks in either the acceleration or	None	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						lugging modes as stated in 40 CFR 60.4201(a)-(c) and 40 CFR 89.113(a)(1)-(3) and 40 CFR 1039.105(b)(1)-(3).			
PRESSURE1	EU	60IIII-0007	PM	40 CFR Part 60, Subpart IIII	§ 60.4204(b) § 1039.101 § 60.4201(a) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) § 60.4218	Owners and operators of non-emergency stationary CI ICE with a maximum engine power less than 19 KW and a displacement of less than 10 liters per cylinder and is a 2008 model year and later must comply with a PM emission limit of 0.40 g/KW-hr as stated in 40 CFR 60.4201(a) and 40 CFR 1039.102 and 40 CFR 1039.101.	None	None	None
PRESSURE1	EU	63ZZZZ-0005	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(c)	Stationary RICE subject to Regulations under 40 CFR Part 60. An affected source that meets any of the criteria in paragraphs (c)(1) through (7) of this section must meet the requirements of this part by meeting the requirements of 40 CFR part 60 subpart IIII, for compression ignition engines or 40 CFR part 60 subpart JJJJ, for spark ignition engines as applicable. No further requirements apply for such engines under this part.	None	None	None
PRESSURE2	EU	R7300-0005	CO	30 TAC Chapter 117,	§ 117.310(c)(1) § 117.310(c)(1)(B)	CO emissions must not exceed 3.0 g/hp-hr for	[G]§ 117.335(a)(1) § 117.335(a)(4)	§ 117.345(a) § 117.345(f)	§ 117.335(b) § 117.335(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Subchapter B		stationary internal combustion engines.	§ 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a)(2)(C) § 117.340(h) § 117.345(f)(3) § 117.345(f)(3)(A) § 117.345(f)(3)(A)(ii) § 117.8000(b) § 117.8000(c) § 117.8000(c)(2) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8120 § 117.8120(2) [G]§ 117.8120(2)(A) § 117.8120(2)(B) § 117.8140(a) § 117.8140(a)(1) § 117.8140(a)(2) § 117.8140(a)(2)(A) [G]§ 117.8140(a)(2)(B) § 117.8140(b)	[G]§ 117.345(f)(10) § 117.345(f)(9)	[G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
PRESSURE2	EU	60IIII-0007	CO	40 CFR Part 60, Subpart IIII	§ 60.4204(b) § 1039.101 § 60.4201(a) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) § 60.4218	Owners and operators of non-emergency stationary CI ICE with a maximum engine power greater than or equal to 8 KW and less than 19 KW and a displacement of less than 10 liters per cylinder and is a 2007 model year and later must comply with a CO emission limit of 6.6 g/KW-hr as stated in 40 CFR 60.4201(a) and 40 CFR	None	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						89.112(a) and 40 CFR 1039.102 and 40 CFR 1039.101.			
PRESSURE2	EU	60IIII-0007	NMHC and NO_X	40 CFR Part 60, Subpart IIII	§ 60.4204(b) § 1039.101 § 60.4201(a) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) § 60.4218	Owners and operators of non-emergency stationary CI ICE with a maximum engine power less than 19 KW and a displacement of less than 10 liters per cylinder and is a 2008 model year or later must comply with an NMHC+NOx emission limit of 7.5 g/KW-hr, as stated in 40 CFR 60.4201(a) and 40 CFR 1039.102 and 40 CFR 1039.101.	None	None	None
PRESSURE2	EU	60IIII-0007	PM (Opacity)	40 CFR Part 60, Subpart IIII	§ 60.4204(b) § 1039.105(b)(1) § 1039.105(b)(2) § 1039.105(b)(3) § 60.4201(a) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) § 60.4218	Owners and operators of non-emergency stationary CI ICE with a displacement of less than 10 liters per cylinder and is not a constant-speed engine and is a 2007 model year and later must comply with the following opacity emission limits: 20% during the acceleration mode, 15% during the lugging mode, and 50% during the peaks in either the acceleration or lugging modes as stated in 40 CFR 60.4201(a)-(c) and 40 CFR 89.113(a)(1)-(3) and 40 CFR 1039.105(b)(1)-(3).	None	None	None
PRESSURE2	EU	60IIII-0007	PM	40 CFR Part 60, Subpart IIII	§ 60.4204(b) § 1039.101	Owners and operators of non-emergency stationary	None	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.4201(a) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) § 60.4218	CI ICE with a maximum engine power less than 19 KW and a displacement of less than 10 liters per cylinder and is a 2008 model year and later must comply with a PM emission limit of 0.40 g/KW-hr as stated in 40 CFR 60.4201(a) and 40 CFR 1039.102 and 40 CFR 1039.101.			
PRESSURE2	EU	63ZZZZ-0005	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(c)	Stationary RICE subject to Regulations under 40 CFR Part 60. An affected source that meets any of the criteria in paragraphs (c)(1) through (7) of this section must meet the requirements of this part by meeting the requirements of 40 CFR part 60 subpart IIII, for compression ignition engines or 40 CFR part 60 subpart JJJJ, for spark ignition engines as applicable. No further requirements apply for such engines under this part.	None	None	None
PRO-AU2	PRO	63F-0010	112(B) HAPS	40 CFR Part 63, Subpart F	§ 63.100(b) [G]§ 63.102(a) [G]§ 63.102(c) § 63.104(a) [G]§ 63.104(d) § 63.104(e) § 63.104(e)(1) [G]§ 63.104(e)(2) § 63.105(d)	Except as provided in paragraphs (b)(4) and (c) of this section, the provisions of subparts F, G, and H apply to chemical manufacturing process units that meet the criteria.	§ 63.103(b)(1) § 63.103(b)(3) § 63.103(b)(4) [G]§ 63.103(b)(5) [G]§ 63.104(b)	[G]§ 63.103(c) [G]§ 63.104(e)(2) [G]§ 63.104(f)(1) [G]§ 63.105(b) § 63.105(c) § 63.105(e)	§ 63.103(b)(2) [G]§ 63.103(b)(5) [G]§ 63.103(d) [G]§ 63.104(f)(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
PRO-BIOTRT	PRO	61FF-0550	Benzene	40 CFR Part 61, Subpart FF	§ 61.348(a)(1) § 61.348(a)(1)(i) § 61.348(a)(2) § 61.348(a)(3) § 61.348(a)(4) § 61.348(e) § 61.348(e)(1) § 61.348(e)(2) § 61.348(f) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(A) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(i)(C) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	The owner or operator shall design, install, operate and maintain a treatment process that removes or destroys benzene as specified.	§ 61.348(c) § 61.348(c)(2) § 61.348(e)(1) § 61.348(f) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(c) § 61.349(c)(1) § 61.349(e) § 61.349(f) § 61.354(a)(1) § 61.354(c) § 61.354(c)(1) § 61.354(f)(2) § 61.355(d) [G]§ 61.355(h)	§ 61.349(a)(1)(ii) § 61.354(c) § 61.354(c)(1) § 61.355(d) § 61.356(e) § 61.356(e)(1) [G]§ 61.356(e)(3) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(A) § 61.356(h) [G]§ 61.356(i) § 61.356(j) § 61.356(j)(1) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(ii) § 61.356(j)(4)	§ 61.357(d)(7) § 61.357(d)(7)(i) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(A)
PRO-SRU	EU	R2007-0002	SO_2	30 TAC Chapter 112, Sulfur Compounds	§ 112.7(a) § 112.7(b)	No person may cause, suffer, allow, or permit emissions of SO2 to exceed the emission limits specified for stack effluent flow rates < 4,000 scfm as determined by the specified equation.	§ 112.2(a) ** See CAM Summary	§ 112.2(c)	§ 112.2(b)
PRO-WWTP	EU	R5142-0004	VOC	30 TAC Chapter 115, Industrial Wastewater	§ 115.143(b) § 115.143(b)(3) [G]§ 115.148	As an alternative to the control requirements of §115.142 of this title (relating to Control Requirements), the owner or operator of a wastewater storage, handling, transfer, or treatment facility may elect to ensure that the overall control of volatile organic compounds (VOC)	§ 115.145 § 115.145(1) § 115.145(10) [G]§ 115.145(2) [G]§ 115.145(3) § 115.145(4) § 115.145(5) § 115.145(6) § 115.145(7) § 115.145(9) [G]§ 115.148	§ 115.146(1) § 115.146(2) § 115.146(3) § 115.146(4)	§ 115.143(b)(1) § 115.143(b)(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						emissions at the account from wastewater from affected source categories is at least 90% less than the 1990 baseline emissions inventory, provided that the following requirements are met.			
PRS3-CTWR	EU	63CC-002	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.654(a) § 63.640(h)(6)	Except as specified in paragraph (b) of this section, the owner or operator of a heat exchange system that meets the criteria in §63.640(c)(8) must comply with the requirements of paragraphs (c) through (g) of this section.	§ 63.642(d)(1) § 63.642(d)(3) § 63.642(d)(4) [G]§ 63.654(c) [G]§ 63.654(d) § 63.654(e) [G]§ 63.654(f) [G]§ 63.654(g)	§ 63.642(e) § 63.655(h)(1) [G]§ 63.655(i)(4) § 63.655(i)(5)	§ 63.642(d)(2) § 63.642(f) § 63.655(f) § 63.655(f)(1)(vi) § 63.655(f)(4) § 63.655(g) [G]§ 63.655(g)(9) § 63.655(h)(1)
PS2-FUG	EU	R5780-ALL	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Fugitive Emissions	§ 115.787(d) § 115.780(b) [G]§ 115.781(a) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) [G]§ 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) [G]§ 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv) § 115.782(c)(1)(C)(i) § 115.782(c)(1)(C)(i)(I) § 115.782(c)(1)(C)(i)(II) §	All pumps that are equipped with a shaft sealing system that prevents or detects emissions of VOC from the seal are exempt from the monitoring requirement of §115.781(b) and (c). Submerged pumps or sealless pumps may be used to satisfy the requirements of this subsection.	§ 115.782(d)(2)	[G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g)	[G]§ 115.782(c)(1)(B)(i) § 115.783(3)(C) [G]§ 115.786(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					115.782(c)(1)(C)(i)(III) § 115.782(c)(1)(C)(ii) § 115.783(3) [G]§ 115.783(3)(A) [G]§ 115.783(3)(B) § 115.787(b) § 115.787(b)(1) § 115.787(g)				
PS2-FUG	EU	R5780-ALL	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Fugitive Emissions	§ 115.787(d) § 115.780(b) [G]§ 115.781(a) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) [G]§ 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) [G]§ 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv) § 115.782(c)(1)(C)(i) § 115.782(c)(1)(C)(i)(I) § 115.782(c)(1)(C)(i)(II) § 115.782(c)(1)(C)(i)(III) § 115.782(c)(1)(C)(ii) § 115.783(3) [G]§ 115.783(3)(A) [G]§ 115.783(3)(B) § 115.787(b) § 115.787(b)(1) § 115.787(g)	All compressors that are equipped with a shaft sealing system that prevents or detects emissions of VOC from the seal are exempt from the monitoring requirement of §115.781(b) and (c). Submerged pumps or sealless pumps may be used to satisfy the requirements of this subsection.	§ 115.782(d)(2)	[G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g)	[G]§ 115.782(c)(1)(B)(i) § 115.783(3)(C) [G]§ 115.786(c)
PS2-FUG	EU	R5780-ALL	Highly Reactive	30 TAC Chapter 115, HRVOC	§ 115.787(d) § 115.780(b)	All agitators that are equipped with a shaft	§ 115.782(d)(2)	[G]§ 115.782(c)(1)(B)(i)	[G]§ 115.782(c)(1)(B)(i) § 115.783(3)(C)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
			VOC	Fugitive Emissions	[G]§ 115.781(a) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) [G]§ 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) [G]§ 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv) § 115.782(c)(1)(C)(i) § 115.782(c)(1)(C)(i)(I) § 115.782(c)(1)(C)(i)(II) § 115.782(c)(1)(C)(i)(III) § 115.782(c)(1)(C)(ii) § 115.783(3) [G]§ 115.783(3)(A) [G]§ 115.783(3)(B) § 115.787(b) § 115.787(b)(1) § 115.787(g)	sealing system that prevents or detects emissions of VOC from the seal are exempt from the monitoring requirement of §115.781(b) and (c). Submerged pumps or sealless pumps may be used to satisfy the requirements of this subsection.		[G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g)	[G]§ 115.786(c)
PS2-FUG	EU	R5780-ALL	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Fugitive Emissions	§ 115.781(b)(9) § 115.780(b) [G]§ 115.781(a) § 115.781(g)(3) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) [G]§ 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii)	Process drains within a petroleum refinery; synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process; or natural gas/gasoline processing operation in which a highly-reactive volatile organic compound is a raw material, intermediate, final product, or in a waste stream is subject to the requirements	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) § 115.781(b) § 115.781(b)(10) § 115.781(b)(3) § 115.781(b)(4) § 115.781(b)(5) § 115.781(b)(6) § 115.781(b)(7) § 115.781(b)(7)(A)	§ 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5) § 115.781(b)(10) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2)	[G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv) § 115.783(4)(A)(i) § 115.783(4)(A)(ii) § 115.783(4)(A)(ii)(I) § 115.783(4)(A)(ii)(II) § 115.783(4)(B) § 115.783(4)(B)(i) § 115.783(4)(B)(ii)	of this division. A leak is defined as a screening concentration greater than 500 ppmv above background as methane for all components.	§ 115.781(b)(7)(B) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.782(d)(2)	§ 115.781(g)(3) [G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g)	
PS2-FUG	EU	R5780-ALL	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Fugitive Emissions	§ 115.781(b)(9) § 115.780(b) [G]§ 115.781(a) § 115.781(g)(3) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) [G]§ 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) [G]§ 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv) § 115.787(e) § 115.787(f) § 115.787(g) § 115.788(a) § 115.788(a)(1) § 115.788(a)(2) § 115.788(a)(2)(A) § 115.788(a)(2)(B) § 115.788(a)(2)(C) § 115.788(a)(2)(C)(i) § 115.788(a)(2)(C)(ii)	Pressure relief valves (in gaseous service) within a petroleum refinery; synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process; or natural gas/gasoline processing operation in which a highly-reactive volatile organic compound is a raw material, intermediate, final product, or in a waste stream is subject to the requirements of this division. A leak is defined as a screening concentration greater than 500 ppmv above background as methane for all components.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) § 115.781(b) § 115.781(b)(10) § 115.781(b)(4) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) § 115.781(b)(8) § 115.781(e) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.782(d)(2)	§ 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5) § 115.781(b)(10) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) [G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g) [G]§ 115.788(g)	[G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.788(c) [G]§ 115.788(d) § 115.788(e) [G]§ 115.788(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.788(a)(2)(C)(iii) § 115.788(a)(2)(D) § 115.788(a)(3) § 115.788(a)(3)(A) § 115.788(a)(3)(B) [G]§ 115.788(g)				
PS2-FUG	EU	R5780-ALL	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Fugitive Emissions	§ 115.781(b)(9) § 115.780(b) [G]§ 115.781(a) [G]§ 115.781(d) § 115.781(g)(3) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(2) § 115.782(c)(2)(A) § 115.782(c)(2)(A)(i) § 115.782(c)(2)(A)(ii) § 115.782(c)(2)(B) § 115.783(1) § 115.783(1)(A) § 115.783(1)(B) § 115.783(5) § 115.787(f) § 115.787(f)(4) § 115.787(g) § 115.788(a) § 115.788(a)(1) § 115.788(a)(2) § 115.788(a)(2)(A) § 115.788(a)(2)(B) § 115.788(a)(2)(C) § 115.788(a)(2)(C)(i) § 115.788(a)(2)(C)(ii) § 115.788(a)(2)(C)(iii) § 115.788(a)(2)(D) § 115.788(a)(3) § 115.788(a)(3)(A) § 115.788(a)(3)(B)	Bypass line valves within a petroleum refinery; synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process; or natural gas/gasoline processing operation in which a highly-reactive volatile organic compound is a raw material, intermediate, final product, or in a waste stream is subject to the requirements of this division. A leak is defined as a screening concentration greater than 500 ppmv above background as methane for all components.	§ 115.781(b) § 115.781(b)(10) § 115.781(b)(4) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) [G]§ 115.781(d) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.782(d)(2) § 115.786(a)(1)	§ 115.781(b)(10) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) § 115.782(c)(2)(A)(ii) § 115.786(a)(1) § 115.786(a)(2) § 115.786(a)(2)(A) § 115.786(a)(2)(B) § 115.786(b)(1) § 115.786(b)(2) § 115.786(b)(2)(A) § 115.786(b)(2)(B) § 115.786(b)(2)(C) [G]§ 115.786(b)(3) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(2) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g) [G]§ 115.788(g)	§ 115.782(c)(2)(A)(ii) [G]§ 115.786(c) § 115.788(c) [G]§ 115.788(d) § 115.788(e) [G]§ 115.788(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 115.788(g)				
PS2-FUG	EU	R5780-ALL	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Fugitive Emissions	§ 115.781(b)(9) § 115.780(b) [G]§ 115.781(a) § 115.781(g)(3) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(2) § 115.782(c)(2)(A) § 115.782(c)(2)(A)(i) § 115.782(c)(2)(A)(ii) § 115.782(c)(2)(B) § 115.783(5) § 115.787(f) § 115.787(f)(4) § 115.787(g) § 115.788(a) § 115.788(a)(1) § 115.788(a)(2) § 115.788(a)(2)(A) § 115.788(a)(2)(B) § 115.788(a)(2)(C) § 115.788(a)(2)(C)(i) § 115.788(a)(2)(C)(ii) § 115.788(a)(2)(C)(iii) § 115.788(a)(2)(D) § 115.788(a)(3) § 115.788(a)(3)(A) § 115.788(a)(3)(B) [G]§ 115.788(g)	Valves within a petroleum refinery; synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process; or natural gas/gasoline processing operation which a highly-reactive volatile organic compound is a raw material, intermediate, final product, or in a waste stream is subject to the requirements of this division. A leak is defined as a screening concentration greater than 500 ppmv above background as methane for all components.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) § 115.781(b) § 115.781(b)(10) § 115.781(b)(4) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.782(d)(2)	§ 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5) § 115.781(b)(10) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) § 115.782(c)(2)(A)(ii) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(2) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g) [G]§ 115.788(g)	§ 115.782(c)(2)(A)(ii) [G]§ 115.786(c) § 115.788(c) [G]§ 115.788(d) § 115.788(e) [G]§ 115.788(g)
PS2-FUG	EU	R5780-ALL	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Fugitive Emissions	§ 115.781(b)(9) § 115.780(b) [G]§ 115.781(a) § 115.781(g)(3) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2)	Flanges or other connectors within a petroleum refinery; synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process; or natural gas/gasoline	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9)	§ 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B)	[G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.789(1)(B)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) [G]§ 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) [G]§ 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv)	processing operation in which a highly-reactive volatile organic compound is a raw material, intermediate, final product, or in a waste stream is subject to the requirements of this division. A leak is defined as a screening concentration greater than 500 ppmv above background as methane for all components.	§ 115.781(b) § 115.781(b)(10) § 115.781(b)(3) § 115.781(b)(4) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) § 115.781(f) § 115.781(f)(1) § 115.781(f)(2) § 115.781(f)(3) § 115.781(f)(4) § 115.781(f)(5) § 115.781(f)(6) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.782(d)(2) § 115.789(1)(B)	[G]§ 115.356(3)(C) § 115.356(5) § 115.781(b)(10) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) [G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g)	
PS2-FUG	EU	R5780-ALL	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Fugitive Emissions	§ 115.781(b)(9) § 115.780(b) [G]§ 115.781(a) § 115.781(g)(3) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) [G]§ 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) [G]§ 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv) § 115.782(c)(1)(C)(i) § 115.782(c)(1)(C)(i)(I) § 115.782(c)(1)(C)(i)(II)	Compressor seals within a petroleum refinery; synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process; or natural gas/gasoline processing operation in which a highly-reactive volatile organic compound is a raw material, intermediate, final product, or in a waste stream is subject to the requirements of this division. A leak is defined as a screening concentration greater than 500 ppmv above background as methane for all components.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) § 115.781(b) § 115.781(b)(10) § 115.781(b)(4) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) § 115.781(c)(1) § 115.781(c)(2) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.782(d)(2)	§ 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5) § 115.781(b)(10) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) [G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2)	[G]§ 115.782(c)(1)(B)(i) § 115.783(3)(C) [G]§ 115.786(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.782(c)(1)(C)(i)(III) § 115.782(c)(1)(C)(ii) § 115.783(3) [G]§ 115.783(3)(A) [G]§ 115.783(3)(B) § 115.787(b)			§ 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g)	
PS2-FUG	EU	R5780-ALL	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Fugitive Emissions	§ 115.781(b)(9) § 115.780(b) [G]§ 115.781(a) § 115.781(g)(3) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) [G]§ 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) [G]§ 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv) § 115.782(c)(1)(C)(i) § 115.782(c)(1)(C)(i)(I) § 115.782(c)(1)(C)(i)(II) § 115.782(c)(1)(C)(i)(III) § 115.782(c)(1)(C)(ii) § 115.783(3) [G]§ 115.783(3)(A) [G]§ 115.783(3)(B) § 115.787(b) § 115.787(b)(1)	Pump seals within a petroleum refinery; synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process; or natural gas/gasoline processing operation in which a highly-reactive volatile organic compound is a raw material, intermediate, final product, or in a waste stream is subject to the requirements of this division. A leak is defined as a screening concentration greater than 500 ppmv above background as methane for all components.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) § 115.781(b) § 115.781(b)(10) § 115.781(b)(4) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) § 115.781(c)(1) § 115.781(c)(2) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.782(d)(2)	§ 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5) § 115.781(b)(10) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) [G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g)	[G]§ 115.782(c)(1)(B)(i) § 115.783(3)(C) [G]§ 115.786(c)
PS2-FUG	EU	R5780-ALL	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Fugitive	§ 115.781(b)(9) § 115.780(b) [G]§ 115.781(a)	Agitators within a petroleum refinery; synthetic organic chemical, polymer, resin, or	§ 115.354(1) § 115.354(10) § 115.354(5)	§ 115.354(10) § 115.356 [G]§ 115.356(1)	[G]§ 115.782(c)(1)(B)(i) § 115.783(3)(C) [G]§ 115.786(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Emissions	§ 115.781(g)(3) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) [G]§ 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) [G]§ 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv) § 115.782(c)(1)(C)(i) § 115.782(c)(1)(C)(i)(I) § 115.782(c)(1)(C)(i)(II) § 115.782(c)(1)(C)(i)(III) § 115.782(c)(1)(C)(ii) § 115.783(3) [G]§ 115.783(3)(A) [G]§ 115.783(3)(B) § 115.787(b)	methyl-tert-butyl ether manufacturing process; or natural gas/gasoline processing operation in which a highly-reactive volatile organic compound is a raw material, intermediate, final product, or in a waste stream is subject to the requirements of this division. A leak is defined as a screening concentration greater than 500 ppmv above background as methane for all components.	§ 115.354(6) § 115.354(9) § 115.781(b) § 115.781(b)(10) § 115.781(b)(3) § 115.781(b)(4) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) § 115.781(c)(1) § 115.781(c)(2) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.782(d)(2)	[G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5) § 115.781(b)(10) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) [G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g)	
PS2-FUG	EU	R5780-ALL	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Fugitive Emissions	§ 115.781(b)(9) § 115.780(b) [G]§ 115.781(a) § 115.781(g)(3) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) [G]§ 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) [G]§ 115.782(c)(1)(B)(iii)	Heat exchanger heads, sight glasses, meters, gauges, sampling connections, bolted manways, hatches, sump covers, junction box vents, and covers and seals on VOC water separators within the process unit or processes listed in §115.780(a) in which a HRVOC is a raw material, intermediate, final product, or in a waste stream is subject to the requirements	§ 115.781(b) § 115.781(b)(10) § 115.781(b)(3) § 115.781(b)(4) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) § 115.781(f) § 115.781(f)(1) § 115.781(f)(2) § 115.781(f)(3) § 115.781(f)(4) § 115.781(f)(5) § 115.781(f)(6) § 115.781(g)	§ 115.781(b)(10) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) [G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e)	[G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.789(1)(B)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.782(c)(1)(B)(iv)	of this division. A leak is defined as a screening concentration greater than 500 ppmv above background as methane for all components.	§ 115.781(g)(1) § 115.781(g)(2) § 115.782(d)(2) § 115.789(1)(B)	§ 115.786(g)	
PS2-FUG	EU	R5780-ALL	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Fugitive Emissions	§ 115.781(b)(9) § 115.358(c)(1) [G]§ 115.358(h) § 115.780(b) [G]§ 115.781(a) § 115.781(g)(3) § 115.782(a) § 115.782(b)(2) § 115.782(b)(3) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) [G]§ 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) [G]§ 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv)	Components within the process unit or processes listed in §115.780(a) is subject to the requirements of this division. If the owner of operator elects to use the alternative work practice in §115.358 of this title, a leak is defined as specified in §115.358 of this title, including any leak detected using the alternative work practice on a component that is subject to the requirements of this division but not specifically selected for alternative work practice monitoring.	§ 115.354(1) § 115.354(11) § 115.354(13)(A) § 115.354(13)(B) § 115.354(13)(C) § 115.354(13)(D) § 115.354(13)(E) § 115.354(13)(F) § 115.354(4) § 115.354(5) § 115.354(9) § 115.358(c)(2) § 115.358(d) [G]§ 115.358(e) § 115.358(f) § 115.781(b) § 115.781(b)(4) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(h)(1) § 115.781(h)(2) § 115.781(h)(3) § 115.781(h)(4) § 115.781(h)(5) [G]§ 115.781(h)(6) § 115.782(b)(4) § 115.782(d)(1) § 115.788(h)(1) [G]§ 115.788(h)(2)	§ 115.354(13)(D) § 115.354(13)(E) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) [G]§ 115.356(4) § 115.356(5) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) [G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) [G]§ 115.786(f) § 115.786(g)	[G]§ 115.358(g) [G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 115.788(h)(3)		
PS2-FUG	EU	R5780-ALL	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Fugitive Emissions	§ 115.781(b)(9) § 115.780(b) [G]§ 115.781(a) § 115.781(g)(3) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(2) § 115.782(c)(2)(A) § 115.782(c)(2)(A)(i) § 115.782(c)(2)(A)(ii) § 115.782(c)(2)(B) § 115.783(5) § 115.787(f) § 115.787(f)(2) § 115.787(f)(3) § 115.787(f)(4) § 115.787(g) § 115.788(a) § 115.788(a)(1) § 115.788(a)(2) § 115.788(a)(2)(A) § 115.788(a)(2)(B) § 115.788(a)(2)(C) § 115.788(a)(2)(C)(i) § 115.788(a)(2)(C)(ii) § 115.788(a)(2)(C)(iii) § 115.788(a)(2)(D) § 115.788(a)(3) § 115.788(a)(3)(A) § 115.788(a)(3)(B) [G]§ 115.788(g)	Open-ended valves or lines within a petroleum refinery; synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process; or natural gas/gasoline processing operation in which a highly-reactive volatile organic compound is a raw material, intermediate, final product, or in a waste stream is subject to the requirements of this division. A leak is defined as a screening concentration greater than 500 ppmv above background as methane for all components.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) § 115.781(b) § 115.781(b)(10) § 115.781(b)(3) § 115.781(b)(4) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) § 115.781(f) § 115.781(f)(1) § 115.781(f)(2) § 115.781(f)(3) § 115.781(f)(4) § 115.781(f)(5) § 115.781(f)(6) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.782(d)(2) § 115.789(1)(B)	§ 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5) § 115.781(b)(10) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) § 115.782(c)(2)(A)(ii) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(2) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g) [G]§ 115.788(g)	§ 115.782(c)(2)(A)(ii) [G]§ 115.786(c) § 115.788(c) [G]§ 115.788(d) § 115.788(e) [G]§ 115.788(g) § 115.789(1)(B)
PS2-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(6)	Components at a petroleum refinery or synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process, that	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						contact a process fluid that contains less than 10% VOC by weight and components at a natural gas/gasoline processing operation that contact a process fluid that contains less than 1.0% VOC by weight are exempt from the requirements of this division except §115.356(3)(C) of this title.			
PS2-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(5)	Reciprocating compressors and positive displacement pumps used in natural gas/gasoline processing operations are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
PS2-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(10)	Instrumentation systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet 40 CFR §63.169 (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
PS2-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(11)	Sampling connection systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet the requirements of 40 CFR §63.166(a) and (b) (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
PS2-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(13)	Components/systems that contact a process fluid containing VOC having a true vapor pressure equal to or less than 0.002 psia at 68 degrees Fahrenheit are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
PS2-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(2) § 115.352(9)	Each pressure relief valve equipped with a rupture disk must comply with §115.352(9) and §115.356(3)(C).	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
PS2-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.353(a) § 115.353(b) § 115.910	For all affected persons in the Beaumont-Port Arthur, Dallas-Fort Worth, El Paso, and Houston-Galveston areas, as defined in §115.10, any alternate methods of demonstrating and documenting continuous compliance with the applicable control requirements or exemption criteria in this division may be approved by the executive director in accordance with §115.910 if emission reductions are demonstrated to be substantially equivalent.	None	None	None
PS2-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(C) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A)	No component shall be allowed to have a VOC leak, for more than 15 days, after discovery. If the owner or operator elects to use the	§ 115.354(1) § 115.354(11) § 115.354(13)(A) § 115.354(13)(B) § 115.354(13)(C)	§ 115.352(7) § 115.354(13)(D) § 115.354(13)(E) § 115.356 [G]§ 115.356(1)	[G]§ 115.358(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(2)(B) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.352(8) § 115.357(8) § 115.358(c)(1) [G]§ 115.358(h)	alternative work practice in §115.358 of this title, any leak detected as defined in §115.358 of this title, including any leak detected using the alternative work practice on a component that is subject to the requirements of this division but not specifically selected for alternative work practice monitoring.	§ 115.354(13)(D) § 115.354(13)(E) § 115.354(13)(F) § 115.354(4) § 115.354(5) § 115.354(9) [G]§ 115.355 § 115.358(c)(2) § 115.358(d) [G]§ 115.358(e) § 115.358(f)	[G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) [G]§ 115.356(4) § 115.356(5)	
PS2-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7) § 115.357(1)	No process drains shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
PS2-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7)	No process drains shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
PS2-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(9) § 115.357(1) § 115.357(8) § 115.357(9)	No pressure relief valves shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
PS2-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(9) § 115.357(12) § 115.357(8) § 115.357(9)	No pressure relief valves shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
PS2-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1)	No open-ended valves or lines shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.357(8) § 115.357(9)				
PS2-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8) § 115.357(9)	No open-ended valves or lines shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
PS2-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(8) § 115.357(9)	No valves shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
PS2-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4)	No valves shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B)	[G]§ 115.354(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8) § 115.357(9)	the dripping or exuding of process fluid based on sight, smell, or sound.		[G]§ 115.356(3)(C) § 115.356(5)	
PS2-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(8) § 115.357(1) § 115.357(12) § 115.357(8)	No flanges or other connectors shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
PS2-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(8) § 115.357(12) § 115.357(8)	No flanges or other connectors shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
PS2-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii)	No agitators shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(2)(C)(iii) § 115.352(3) § 115.352(7) § 115.357(1) § 115.357(12) § 115.357(8)	as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.		[G]§ 115.356(3)(C) § 115.356(5)	
PS2-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(7) § 115.357(1) § 115.357(12) § 115.357(8)	No agitators shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
PS2-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(7) § 115.357(12) § 115.357(8)	No agitators shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
PS2-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A)	No compressor seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(3) § 115.357(8)	concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.		[G]§ 115.356(3)(C) § 115.356(5)	
PS2-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(4) § 115.357(8)	No compressor seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None
PS2-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1) § 115.357(8)	No compressor seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None
PS2-FUG	EU	R5352-	VOC	30 TAC Chapter	§ 115.352(1)(B)	No compressor seals shall	§ 115.354(1)	§ 115.352(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		ALL		115, Pet. Refinery & Petrochemicals	§ 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	
PS2-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(4) § 115.357(8)	No pump seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None
PS2-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5)	No pump seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(7) § 115.357(1) § 115.357(8)	sound.			
PS2-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	No pump seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
PS2-FUG	EU	60GGGa-001	VOC	40 CFR Part 60, Subpart GGGa	[G]§ 60.590a(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 60, Subpart GGGa
PS2-FUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(d)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for equipment in vacuum service.	None	§ 60.486(e) § 60.486(e)(1) § 60.486(e)(5)	None
PS2-FUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-2 [G]§ 60.482-9	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pumps in light liquid service complying with §60.482-2.	[G]§ 60.482-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.648(a)(2) § 63.648(f) § 63.655(d)(2)		[G]§ 60.485(e) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(d)(6) § 63.655(i)(5)	
PS2-FUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-3 [G]§ 60.482-9 § 63.648(a)(2) § 63.648(i) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for compressors complying with §60.482-3.	[G]§ 60.482-3 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(d)(6) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
PS2-FUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) § 60.482-4(a) § 60.482-4(b)(1) [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pressure relief devices in gas/vapor service.	§ 60.482-4(b)(2) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(3) [G]§ 60.486(e)(4) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
PS2-FUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-5 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for sampling connection systems complying with §60.482-5.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
PS2-FUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-6 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for open-ended valves or lines complying with §60.482-6.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
PS2-FUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-7 [G]§ 60.482-9 [G]§ 60.483-1 [G]§ 60.483-2 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for valves in gas/vapor service or in light liquid service complying with §60.482-7.	[G]§ 60.482-7 [G]§ 60.483-1 [G]§ 60.483-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) [G]§ 60.486(g) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(d) § 60.487(e)
PS2-FUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for valves in heavy liquid service complying with §60.482-8.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
PS2-FUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pumps in heavy liquid service complying with §60.482-8.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
PS2-FUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for flanges or other connectors complying with §60.482-8.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
PS2-FUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pressure relief devices in light liquid service complying with §60.482-8.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
PS2-FUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pressure relief devices in heavy liquid service complying with §60.482-8.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
PS2-FUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	[G]§ 63.648(g)	Compressors in hydrogen service are exempt from the requirements of §63.648(a) and (c), if an owner or operator demonstrates that a compressor is in hydrogen service. §63.648(g)(1)-(2).	[G]§ 63.648(g)	§ 63.648(h) § 63.655(d)(3) § 63.655(i)(5)	None
PS3A-101BA	EU	R7300-1493	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i)	An owner or operator may not use the alternative methods specified in §§	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b)	§ 117.345(a) § 117.345(f) § 117.345(f)(2)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	§ 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(2) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) § 117.340(c)(3)(D) [G]§ 117.340(c)(3)(E) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)	[G]§ 117.345(f)(2)(C) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	[G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
PS3A-101BA	EU	R7300-1493	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(e) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)	§ 117.8100(a)(5)(C)	§ 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
PS3A-101BA	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
PS3A-101BA	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63,	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					specification requirements of 40 CFR Part 63, Subpart DDDDD		DDDDD	Subpart DDDDD	
PS3A-101BB	EU	R7300-1493	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(2) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) § 117.340(c)(3)(D) [G]§ 117.340(c)(3)(E) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
PS3A-101BB	EU	R7300-1493	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(e) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
PS3A-101BB	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						mg/dscm (0.10 gr/dscf).			
PS3A-101BB	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
PS3A-102BA	EU	R7300-1289	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(2) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) § 117.340(c)(3)(D) [G]§ 117.340(c)(3)(E) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)		
PS3A-102BA	EU	R7300-1289	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(e) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
PS3A-102BA	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
PS3A-102BA	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
PS3A-102BB	EU	R7300-1289	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(2) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) § 117.340(c)(3)(D) [G]§ 117.340(c)(3)(E) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)		
PS3A-102BB	EU	R7300-1289	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(e) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							[G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)		
PS3A-102BB	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
PS3A-102BB	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
PS3A-103B	EU	R7300-1289	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(2) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) § 117.340(c)(3)(D) [G]§ 117.340(c)(3)(E)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)		§ 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
PS3A-103B	EU	R7300-1289	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(e) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)		[G]§ 117.8010(8) § 117.8100(c)
PS3A-103B	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
PS3A-103B	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
PS3A-205F	EU	R5131-0010	VOC	30 TAC Chapter 115, Water Separation	§ 115.132(a)(3) § 115.131(a)	VOC water separator compartments must be equipped with a vapor recovery system which satisfies the provisions of §115.131(a) of this title.	[G]§ 115.135(a) § 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	§ 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
PS3A-205F	EU	61FF-1733	Benzene	40 CFR Part 61, Subpart FF	§ 61.347(a)(1) § 60.18 § 61.347(a)(1)(i)(A) § 61.347(a)(1)(i)(B) § 61.347(b) § 61.347(c) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(iii) § 61.349(b) § 61.349(d) § 61.349(e) § 61.349(f) § 61.349(g)	Install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the oil-water separator to a control device.	§ 60.18(f)(2) § 61.347(a)(1)(i)(A) § 61.347(b) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(c) § 61.354(c)(3) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.349(a)(1)(ii) § 61.354(c) § 61.354(c)(3) § 61.356(d) § 61.356(f) § 61.356(f)(1) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i) § 61.356(j)(7)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(F)
PS3A-FUG1	EU	60GGGa-001	VOC	40 CFR Part 60, Subpart GGGa	[G]§ 60.590a(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 60, Subpart GGGa
PS3A-OWS	EU	R5131-0010	VOC	30 TAC Chapter 115, Water Separation	§ 115.132(a)(3) § 115.131(a)	VOC water separator compartments must be equipped with a vapor recovery system which satisfies the provisions of §115.131(a) of this title.	[G]§ 115.135(a) § 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4) ** See CAM Summary	§ 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	None
PS3A-OWS	EU	61FF-1781	Benzene	40 CFR Part 61, Subpart FF	§ 61.347(a)(1) § 61.347(a)(1)(i)(A) § 61.347(a)(1)(i)(B) § 61.347(b)	Install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors	§ 61.347(a)(1)(i)(A) § 61.347(b) § 61.349(a)(1)(i) § 61.349(a)(1)(ii)	§ 61.349(a)(1)(ii) § 61.356(d) § 61.356(f) § 61.356(f)(1)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 61.347(c) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	vented from the oil-water separator to a control device.	§ 61.349(e) § 61.349(f) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i)	
PS3B-401BA	EU	R7300-1493	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(2) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) § 117.340(c)(3)(D) [G]§ 117.340(c)(3)(E) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)		
PS3B-401BA	EU	R7300-1493	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(e) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
PS3B-401BA	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
PS3B-401BA	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
PS3B-401BB	EU	R7300-1493	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(2) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) § 117.340(c)(3)(D) [G]§ 117.340(c)(3)(E) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)		
PS3B-401BB	EU	R7300-1493	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(e) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)		
PS3B-401BB	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
PS3B-401BB	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
PS3B-401BC	EU	R7300-1493	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(2) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) § 117.340(c)(3)(D)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.340(c)(3)(E) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)		[G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
PS3B-401BC	EU	R7300-1493	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(e) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)		[G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
PS3B-401BC	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
PS3B-401BC	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
PS3B-402BE	EU	R7300-1291	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(8) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	§ 117.335(f)(2) § 117.335(g) § 117.340(a) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) [G]§ 117.340(c)(3) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)	§ 117.8100(a)(5)(C)	§ 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
PS3B-402BE	EU	R7300-1291	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a) § 117.340(b)(1) § 117.340(b)(3) § 117.340(e)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							[G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)		§ 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
PS3B-402BE	EU	R7300-1291	NH_3	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(2) § 117.310(c)(2)(A)	For process heaters that inject urea or ammonia into the exhaust stream for NO_x control, ammonia emissions must not exceed 10 ppmv at 3.0% O_2, dry.	§ 117.335(a)(2) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(b)(1) § 117.340(b)(3) § 117.340(d) § 117.8000(b) § 117.8000(c) § 117.8000(c)(3) § 117.8000(c)(4) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8130 § 117.8130(1)	§ 117.345(a) § 117.345(f) § 117.345(f)(11) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
PS3B-402BE	EU	R7300-1292	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(2) § 117.335(g) § 117.340(a) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) [G]§ 117.340(c)(3) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
PS3B-402BE	EU	R7300-1292	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(7) § 117.345(f)(8)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.335(f)(3) § 117.335(g) § 117.340(a) § 117.340(b)(1) § 117.340(b)(3) § 117.340(e) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)	§ 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
PS3B-402BE	EU	R7300-1292	NH_3	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(2) § 117.310(c)(2)(A)	For process heaters that inject urea or ammonia into the exhaust stream for NO_x control, ammonia emissions must not exceed 10 ppmv at 3.0% O_2, dry.	§ 117.335(a)(2) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(b)(1) § 117.340(b)(3) § 117.340(d) § 117.8000(b) § 117.8000(c) § 117.8000(c)(3) § 117.8000(c)(4)	§ 117.345(a) § 117.345(f) § 117.345(f)(11) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8130 § 117.8130(3)		[G]§ 117.8010(7) [G]§ 117.8010(8)
PS3B-402BE	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
PS3B-402BE	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
PS3B-402BF	EU	R7300-1291	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of §	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(2) § 117.335(g) § 117.340(a) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) [G]§ 117.340(c)(3) [G]§ 117.340(f)(2) § 117.340(l)(2)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	§ 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)		[G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
PS3B-402BF	EU	R7300-1291	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a) § 117.340(b)(1) § 117.340(b)(3) § 117.340(e) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							[G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)		
PS3B-402BF	EU	R7300-1291	NH_3	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(2) § 117.310(c)(2)(A)	For process heaters that inject urea or ammonia into the exhaust stream for NO_x control, ammonia emissions must not exceed 10 ppmv at 3.0% O_2, dry.	§ 117.335(a)(2) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(b)(1) § 117.340(b)(3) § 117.340(d) § 117.8000(b) § 117.8000(c) § 117.8000(c)(3) § 117.8000(c)(4) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8130 § 117.8130(1)	§ 117.345(a) § 117.345(f) § 117.345(f)(11) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
PS3B-402BF	EU	R7300-1292	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101,	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(2) § 117.335(g) § 117.340(a)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	§ 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) [G]§ 117.340(c)(3) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)		§ 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
PS3B-402BF	EU	R7300-1292	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a) § 117.340(b)(1) § 117.340(b)(3) § 117.340(e) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)		§ 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
PS3B-402BF	EU	R7300-1292	NH_3	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(2) § 117.310(c)(2)(A)	For process heaters that inject urea or ammonia into the exhaust stream for NO_x control, ammonia emissions must not exceed 10 ppmv at 3.0% O_2, dry.	§ 117.335(a)(2) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(b)(1) § 117.340(b)(3) § 117.340(d) § 117.8000(b) § 117.8000(c) § 117.8000(c)(3) § 117.8000(c)(4) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8130 § 117.8130(3)	§ 117.345(a) § 117.345(f) § 117.345(f)(11) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
PS3B-402BF	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)		§ 60.107(g)
PS3B-402BF	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
PS3B-402BG	EU	R7300-1494	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(2) § 117.335(g) § 117.340(a) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) [G]§ 117.340(c)(3) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)		
PS3B-402BG	EU	R7300-1494	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a) § 117.340(b)(1) § 117.340(b)(3) § 117.340(e) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.8120 § 117.8120(1) § 117.8120(1)(A)		
PS3B-402BG	EU	R7300-1494	NH_3	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(2) § 117.310(c)(2)(A)	For process heaters that inject urea or ammonia into the exhaust stream for NO_x control, ammonia emissions must not exceed 10 ppmv at 3.0% O_2, dry.	§ 117.335(a)(2) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(b)(1) § 117.340(b)(3) § 117.340(d) § 117.8000(b) § 117.8000(c) § 117.8000(c)(3) § 117.8000(c)(4) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8130 § 117.8130(1)	§ 117.345(a) § 117.345(f) § 117.345(f)(11) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
PS3B-402BG	EU	R7300-1495	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(2) § 117.335(g) § 117.340(a) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) [G]§ 117.340(c)(3) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						alternative methods specified in § 117.9800 to comply with § 117.320.	§ 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)		[G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
PS3B-402BG	EU	R7300-1495	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a) § 117.340(b)(1) § 117.340(b)(3) § 117.340(e) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)		
PS3B-402BG	EU	R7300-1495	NH_3	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(2) § 117.310(c)(2)(A)	For process heaters that inject urea or ammonia into the exhaust stream for NO_x control, ammonia emissions must not exceed 10 ppmv at 3.0% O_2, dry.	§ 117.335(a)(2) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(b)(1) § 117.340(b)(3) § 117.340(d) § 117.8000(b) § 117.8000(c) § 117.8000(c)(3) § 117.8000(c)(4) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8130 § 117.8130(3)	§ 117.345(a) § 117.345(f) § 117.345(f)(11) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
PS3B-402BG	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
PS3B-402BG	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the	The permit holder shall comply with the applicable requirements of 40 CFR	The permit holder shall comply with the applicable monitoring	The permit holder shall comply with the applicable	The permit holder shall comply with the applicable reporting

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	Part 63, Subpart DDDDD	and testing requirements of 40 CFR Part 63, Subpart DDDDD	recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	requirements of 40 CFR Part 63, Subpart DDDDD
PS3B-515F	EU	R5131-0010	VOC	30 TAC Chapter 115, Water Separation	§ 115.132(a)(3) § 115.131(a)	VOC water separator compartments must be equipped with a vapor recovery system which satisfies the provisions of §115.131(a) of this title.	[G]§ 115.135(a) § 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	§ 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	None
PS3B-515F	EU	61FF-1733	Benzene	40 CFR Part 61, Subpart FF	§ 61.347(a)(1) § 60.18 § 61.347(a)(1)(i)(A) § 61.347(a)(1)(i)(B) § 61.347(b) § 61.347(c) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(iil) § 61.349(b) § 61.349(d) § 61.349(e) § 61.349(f) § 61.349(g)	Install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the oil-water separator to a control device.	§ 60.18(f)(2) § 61.347(a)(1)(i)(A) § 61.347(b) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(c) § 61.354(c)(3) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.349(a)(1)(ii) § 61.354(c) § 61.354(c)(3) § 61.356(d) § 61.356(f) § 61.356(f)(1) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i) § 61.356(j)(7)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(F)
PS3B-516F	EU	R5131-0010	VOC	30 TAC Chapter 115, Water Separation	§ 115.132(a)(3) § 115.131(a)	VOC water separator compartments must be equipped with a vapor recovery system which satisfies the provisions of §115.131(a) of this title.	[G]§ 115.135(a) § 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	§ 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
PS3B-516F	EU	61FF-1733	Benzene	40 CFR Part 61, Subpart FF	§ 61.347(a)(1) § 60.18 § 61.347(a)(1)(i)(A) § 61.347(a)(1)(i)(B) § 61.347(b) § 61.347(c) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(iii) § 61.349(b) § 61.349(d) § 61.349(e) § 61.349(f) § 61.349(g)	Install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the oil-water separator to a control device.	§ 60.18(f)(2) § 61.347(a)(1)(i)(A) § 61.347(b) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(c) § 61.354(c)(3) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.349(a)(1)(ii) § 61.354(c) § 61.354(c)(3) § 61.356(d) § 61.356(f) § 61.356(f)(1) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i) § 61.356(j)(7)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(F)
PS3B-F510	EU	R5131-0010	VOC	30 TAC Chapter 115, Water Separation	§ 115.132(a)(3) § 115.131(a)	VOC water separator compartments must be equipped with a vapor recovery system which satisfies the provisions of §115.131(a) of this title.	[G]§ 115.135(a) § 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	§ 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	None
PS3B-F510	EU	61FF-1733	Benzene	40 CFR Part 61, Subpart FF	§ 61.347(a)(1) § 60.18 § 61.347(a)(1)(i)(A) § 61.347(a)(1)(i)(B) § 61.347(b) § 61.347(c) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(iii) § 61.349(b)	Install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the oil-water separator to a control device.	§ 60.18(f)(2) § 61.347(a)(1)(i)(A) § 61.347(b) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(c) § 61.354(c)(3) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.349(a)(1)(ii) § 61.354(c) § 61.354(c)(3) § 61.356(d) § 61.356(f) § 61.356(f)(1) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i) § 61.356(j)(7)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(F)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 61.349(d) § 61.349(e) § 61.349(f) § 61.349(g)				
PS3B-FUG1	EU	60GGGa-001	VOC	40 CFR Part 60, Subpart GGGa	[G]§ 60.590a(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 60, Subpart GGGa
PS3B-SEP1	EU	R5131-0010	VOC	30 TAC Chapter 115, Water Separation	§ 115.132(a)(3) § 115.131(a)	VOC water separator compartments must be equipped with a vapor recovery system which satisfies the provisions of §115.131(a) of this title.	[G]§ 115.135(a) § 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	§ 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	None
PS3B-SEP1	EU	61FF-1781	Benzene	40 CFR Part 61, Subpart FF	§ 61.347(a)(1) § 61.347(a)(1)(i)(A) § 61.347(a)(1)(i)(B) § 61.347(b) § 61.347(c) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	Install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the oil-water separator to a control device.	§ 61.347(a)(1)(i)(A) § 61.347(b) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.349(a)(1)(ii) § 61.356(d) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i)	None
PS3B-SEP2	EU	R5131-	VOC	30 TAC Chapter	§ 115.132(a)(3)	VOC water separator	[G]§ 115.135(a)	§ 115.136(a)(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		0010		115, Water Separation	§ 115.131(a)	compartments must be equipped with a vapor recovery system which satisfies the provisions of §115.131(a) of this title.	§ 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	§ 115.136(a)(3) § 115.136(a)(4)	
PS3B-SEP2	EU	61FF-1781	Benzene	40 CFR Part 61, Subpart FF	§ 61.347(a)(1) § 61.347(a)(1)(i)(A) § 61.347(a)(1)(i)(B) § 61.347(b) § 61.347(c) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	Install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the oil-water separator to a control device.	§ 61.347(a)(1)(i)(A) § 61.347(b) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.349(a)(1)(ii) § 61.356(d) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i)	None
PS3-CTWR	EU	R5760-0206	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Cooling Towers	§ 115.767(6) § 115.764(a)(1) § 115.766(i)	All sites that are subject to this division and that are located in the Houston/ Galveston/Brazoria area as defined in § 115.10, excluding Harris County, are exempt from § 115.761(b) and (c)(2), except as provided in § 115.769(a)(3).	§ 115.764(a)(1) § 115.764(a)(3) [G]§ 115.764(a)(6) § 115.764(c)	§ 115.766(a)(1) § 115.766(a)(2) § 115.766(a)(3) § 115.766(a)(5) § 115.766(a)(6) § 115.766(c) [G]§ 115.766(g) § 115.766(i)(1)	§ 115.766(i)(2)
PS3-CTWR	EU	63CC-002	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.654(a) § 63.640(h)(6)	Except as specified in paragraph (b) of this section, the owner or operator of a heat exchange system that meets the criteria in §63.640(c)(8) must comply with the	§ 63.642(d)(1) § 63.642(d)(3) § 63.642(d)(4) [G]§ 63.654(c) [G]§ 63.654(d) § 63.654(e) [G]§ 63.654(f)	§ 63.642(e) § 63.655(h)(1) [G]§ 63.655(i)(4) § 63.655(i)(5)	§ 63.642(d)(2) § 63.642(f) § 63.655(f) § 63.655(f)(1)(vi) § 63.655(f)(4) § 63.655(g) [G]§ 63.655(g)(9)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						requirements of paragraphs (c) through (g) of this section.	[G]§ 63.654(g)		§ 63.655(h)(1)
RDU-601B	EU	R7300-1289	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(2) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) § 117.340(c)(3)(D) [G]§ 117.340(c)(3)(E) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
RDU-601B	EU	R7300-	CO	30 TAC Chapter	§ 117.310(c)(1)	CO emissions must not	[G]§ 117.335(a)(1)	§ 117.345(a)	§ 117.335(b)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		1289		117, Subchapter B	§ 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	exceed 400 ppmv at 3.0% O 2, dry basis.	§ 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(e) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)	§ 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
RDU-601B	EU	60Db-1	SO_2	40 CFR Part 60, Subpart Db	§ 60.104(a)(1) § 60.104	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide in excess of 230 mg/dscm (0.10 gr/dscf). The	§ 60.105(a) § 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.105(e) § 60.105(e)(3)(ii) § 60.106(a)	§ 60.105(a)(4)	§ 60.105(e) § 60.105(e)(3)(ii) § 60.107(e) § 60.107(f)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						combustion in a flare of process upset gases or fuel gas that is released to the flare as a result of relief valve leakage or other emergency malfunctions is exempt from this paragraph.	[G]§ 60.106(e)(1)		
RDU-601B	EU	60Db-1	PM	40 CFR Part 60, Subpart Db	§ 60.40b(a)	This subpart applies to each steam generating unit constructed, modified, or reconstructed after 6/19/84, and that has a heat input capacity from fuels combusted in the unit > 29 MW (100 MMBtu/hr).	None	[G]§ 60.49b(d) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3)
RDU-601B	EU	60Db-1	PM (Opacity)	40 CFR Part 60, Subpart Db	§ 60.40b(a)	This subpart applies to each steam generating unit constructed, modified, or reconstructed after 6/19/84, and that has a heat input capacity from fuels combusted in the unit > 29 MW (100 MMBtu/hr).	None	[G]§ 60.49b(d) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3)
RDU-601B	EU	60Db-1	NO_X	40 CFR Part 60, Subpart Db	§ 60.40b(a)	This subpart applies to each steam generating unit constructed, modified, or reconstructed after 6/19/84, and that has a heat input capacity from fuels combusted in the unit > 29 MW (100 MMBtu/hr).	None	[G]§ 60.49b(d) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3)
RDU-601B	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						(H2S) in excess of 230 mg/dscm (0.10 gr/dscf).			
RDU-601B	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
RDU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(d)	Comply with the requirements as stated in §60.482-1(d) for equipment in vacuum service.	None	§ 60.486(e) § 60.486(e)(1) § 60.486(e)(5)	None
RDU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-2 [G]§ 60.482-9	Comply with the requirements as stated in §60.482-2 for pumps in light-liquid service.	[G]§ 60.482-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d) § 60.593(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
RDU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.593(b)(1)	Compressors in hydrogen service are exempt from the requirements of §60.592 if an owner or operator demonstrates that a compressor is in hydrogen service.	§ 60.593(b)(2) [G]§ 60.593(b)(3)	None	None
RDU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b)	Comply with the requirements as stated in §60.482-3 for compressors.	[G]§ 60.482-3 § 60.485(a) [G]§ 60.485(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 60.482-3 [G]§ 60.482-9		[G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	§ 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(e) § 60.592(e)
RDU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-4 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-4 for pressure relief devices in gas/vapor service.	[G]§ 60.482-4 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(3) [G]§ 60.486(e)(4) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
RDU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-5 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-5 for sampling connection systems.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
RDU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-6 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-6 for open-ended valves and lines.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
RDU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-7 [G]§ 60.482-9 [G]§ 60.483-1 [G]§ 60.483-2 § 60.592(b)	Comply with the requirements in as stated in §60.482-7 for valves in gas/vapor or light-liquid service.	[G]§ 60.482-7 [G]§ 60.483-1 [G]§ 60.483-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d) § 60.593(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) [G]§ 60.486(g) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(d) § 60.487(e) § 60.592(e)
RDU-FUG	EU	60GGG-	VOC	40 CFR Part 60,	§ 60.592(a)	Comply with the	[G]§ 60.482-8	[G]§ 60.486(a)	§ 60.487(a)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		0001		Subpart GGG	§ 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	requirements in as stated in §60.482-8 for pumps in heavy-liquid service.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	[G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
RDU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) § 60.482-10(b) § 60.482-10(e) § 60.482-10(m)	Comply with the requirements in as stated in §60.482-10 for vapor recovery devices.	§ 60.485(a) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
RDU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.18 § 60.482-1(a) § 60.482-1(b) § 60.482-10(d) § 60.482-10(e) § 60.482-10(m)	Comply with the requirements in as stated in §60.482-10 for flares.	§ 60.485(a) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) [G]§ 60.485(g) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
RDU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) § 60.482-10(e) [G]§ 60.482-10(g) § 60.482-10(h) § 60.482-10(m)	Comply with the requirements in as stated in §60.482-10 for closed-vent systems.	[G]§ 60.482-10(f) § 60.482-10(i) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.482-10(j) [G]§ 60.482-10(k) [G]§ 60.482-10(l) [G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
RDU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for valves in heavy-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
RDU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a)	Comply with the requirements in as stated in	[G]§ 60.482-8 § 60.485(a)	[G]§ 60.486(a) [G]§ 60.486(b)	§ 60.487(a) [G]§ 60.487(b)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	§60.482-8 for flanges or other connectors.	[G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	[G]§ 60.487(c) § 60.487(e) § 60.592(e)
RDU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for pressure relief devices in light-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
RDU-FUG1	EU	60GGGa-001	VOC	40 CFR Part 60, Subpart GGGa	[G]§ 60.590a(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 60, Subpart GGGa
RDU-SEP	EU	R5131-0010	VOC	30 TAC Chapter 115, Water Separation	§ 115.132(a)(3) § 115.131(a)	VOC water separator compartments must be equipped with a vapor recovery system which satisfies the provisions of §115.131(a) of this title.	[G]§ 115.135(a) § 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	§ 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	None
RDU-SEP	EU	61FF-1781	Benzene	40 CFR Part 61, Subpart FF	§ 61.347(a)(1) § 61.347(a)(1)(i)(A) § 61.347(a)(1)(i)(B) § 61.347(b) § 61.347(c) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B)	Install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the oil-water separator to a control device.	§ 61.347(a)(1)(i)(A) § 61.347(b) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.349(a)(1)(ii) § 61.356(d) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(g) § 61.356(h)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)			§ 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i)	
REFDOCKFUG	EU	R5352-0001	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(10)	Instrumentation systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet 40 CFR §63.169 (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
REFDOCKFUG	EU	R5352-0001	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(11)	Sampling connection systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet the requirements of 40 CFR §63.166(a) and (b) (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
REFDOCKFUG	EU	R5352-0001	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(13)	Components/systems that contact a process fluid containing VOC having a true vapor pressure equal to or less than 0.002 psia at 68 degrees Fahrenheit are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
REFDOCKFUG	EU	R5352-0001	VOC	30 TAC Chapter 115, Pet.	§ 115.352(1)(A) § 115.352(1)	No process drains shall be allowed to have a VOC	§ 115.354(1) § 115.354(5)	§ 115.352(7) § 115.356	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Refinery & Petrochemicals	§ 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7) § 115.357(1)	leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	[G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	
REFDOCKFUG	EU	R5352-0001	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7)	No process drains shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(5)	None
REFDOCKFUG	EU	R5352-0001	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(8) § 115.357(1) § 115.357(12) § 115.357(8)	No flanges or other connectors shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
REFDOCKFUG	EU	R5352-0001	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2)	No flanges or other connectors shall be allowed to have a VOC leak, for more than 15 days after	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(8) § 115.357(12) § 115.357(8)	discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	[G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	
REFDOCKFUG	EU	R5352-0001	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1) § 115.357(8)	No pump seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None
REFDOCKFUG	EU	R5352-0001	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	No pump seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
REFDOCKFUG	EU	63CCVV-0001	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(d)	Comply with the specified 40 CFR Part 60, Subpart	None	§ 60.486(e) § 60.486(e)(1)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						VV requirements for equipment in vacuum service.		§ 60.486(e)(5)	
REFDOCKFUG	EU	63CCVV-0001	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-2 [G]§ 60.482-9 § 63.648(a)(2) § 63.648(f) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pumps in light liquid service complying with §60.482-2.	[G]§ 60.482-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(d)(6) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
REFDOCKFUG	EU	63CCVV-0001	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-5 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for sampling connection systems complying with §60.482-5.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
REFDOCKFUG	EU	63CCVV-0001	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-6 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for open-ended valves or lines complying with §60.482-6.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
REFDOCKFUG	EU	63CCVV-0001	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-7 [G]§ 60.482-9 [G]§ 60.483-1 [G]§ 60.483-2	Comply with the specified 40 CFR Part 60, Subpart VV requirements for valves in gas/vapor service or in light liquid service complying with §60.482-7.	[G]§ 60.482-7 [G]§ 60.483-1 [G]§ 60.483-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(d) § 60.487(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.648(a)(2) § 63.655(d)(2)		[G]§ 60.485(e) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(f) [G]§ 60.486(g) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	
REFDOCKFUG	EU	63CCVV-0001	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for valves in heavy liquid service complying with §60.482-8.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
REFDOCKFUG	EU	63CCVV-0001	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for flanges or other connectors complying with §60.482-8.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
REFDOCKFUG	EU	63CCVV-0001	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) § 60.482-10(c) § 60.482-10(e) § 60.482-10(m) § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for enclosed combustion devices complying with §60.482-10.	§ 60.485(a) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
REF-FUG	EU	R5780-ALL	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Fugitive Emissions	§ 115.787(d) § 115.780(b) [G]§ 115.781(a) § 115.782(a) § 115.782(b)(1)	All pumps that are equipped with a shaft sealing system that prevents or detects emissions of VOC from the seal are exempt from the	§ 115.782(d)(2)	[G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1)	[G]§ 115.782(c)(1)(B)(i) § 115.783(3)(C) [G]§ 115.786(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.782(b)(2) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) [G]§ 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) [G]§ 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv) § 115.782(c)(1)(C)(i) § 115.782(c)(1)(C)(i)(I) § 115.782(c)(1)(C)(i)(II) § 115.782(c)(1)(C)(i)(III) § 115.782(c)(1)(C)(ii) § 115.783(3) [G]§ 115.783(3)(A) [G]§ 115.783(3)(B) § 115.787(b) § 115.787(b)(1) § 115.787(g)	monitoring requirement of §115.781(b) and (c). Submerged pumps or sealless pumps may be used to satisfy the requirements of this subsection.		§ 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g)	
REF-FUG	EU	R5780-ALL	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Fugitive Emissions	§ 115.787(d) § 115.780(b) [G]§ 115.781(a) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) [G]§ 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) [G]§ 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv) § 115.782(c)(1)(C)(i)	All compressors that are equipped with a shaft sealing system that prevents or detects emissions of VOC from the seal are exempt from the monitoring requirement of §115.781(b) and (c). Submerged pumps or sealless pumps may be used to satisfy the requirements of this subsection.	§ 115.782(d)(2)	[G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g)	[G]§ 115.782(c)(1)(B)(i) § 115.783(3)(C) [G]§ 115.786(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.782(c)(1)(C)(i)(I) § 115.782(c)(1)(C)(i)(II) § 115.782(c)(1)(C)(i)(III) § 115.782(c)(1)(C)(ii) § 115.783(3) [G]§ 115.783(3)(A) [G]§ 115.783(3)(B) § 115.787(b) § 115.787(b)(1) § 115.787(g)				
REF-FUG	EU	R5780-ALL	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Fugitive Emissions	§ 115.787(d) § 115.780(b) [G]§ 115.781(a) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) [G]§ 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) [G]§ 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv) § 115.782(c)(1)(C)(i) § 115.782(c)(1)(C)(i)(I) § 115.782(c)(1)(C)(i)(II) § 115.782(c)(1)(C)(i)(III) § 115.782(c)(1)(C)(ii) § 115.783(3) [G]§ 115.783(3)(A) [G]§ 115.783(3)(B) § 115.787(b) § 115.787(b)(1)	All agitators that are equipped with a shaft sealing system that prevents or detects emissions of VOC from the seal are exempt from the monitoring requirement of §115.781(b) and (c). Submerged pumps or sealless pumps may be used to satisfy the requirements of this subsection.	§ 115.782(d)(2)	[G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g)	[G]§ 115.782(c)(1)(B)(i) § 115.783(3)(C) [G]§ 115.786(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.787(g)				
REF-FUG	EU	R5780-ALL	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Fugitive Emissions	§ 115.781(b)(9) § 115.780(b) [G]§ 115.781(a) § 115.781(g)(3) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) [G]§ 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) [G]§ 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv) § 115.783(4)(A)(i) § 115.783(4)(A)(ii) § 115.783(4)(A)(ii)(I) § 115.783(4)(A)(ii)(II) § 115.783(4)(B) § 115.783(4)(B)(i) § 115.783(4)(B)(ii)	Process drains within a petroleum refinery; synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process; or natural gas/gasoline processing operation in which a highly-reactive volatile organic compound is a raw material, intermediate, final product, or in a waste stream is subject to the requirements of this division. A leak is defined as a screening concentration greater than 500 ppmv above background as methane for all components.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) § 115.781(b) § 115.781(b)(10) § 115.781(b)(3) § 115.781(b)(4) § 115.781(b)(5) § 115.781(b)(6) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.782(d)(2)	§ 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5) § 115.781(b)(10) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) [G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g)	[G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c)
REF-FUG	EU	R5780-ALL	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Fugitive Emissions	§ 115.781(b)(9) § 115.780(b) [G]§ 115.781(a) § 115.781(g)(3) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) [G]§ 115.782(c)(1)(B)(i)	Pressure relief valves (in gaseous service) within a petroleum refinery; synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process; or natural gas/gasoline processing operation in which a highly-reactive volatile organic compound is a raw material, intermediate, final product,	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) § 115.781(b) § 115.781(b)(10) § 115.781(b)(4) § 115.781(b)(7)	§ 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5) § 115.781(b)(10) § 115.781(g) § 115.781(g)(1)	[G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.788(c) [G]§ 115.788(d) § 115.788(e) [G]§ 115.788(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.782(c)(1)(B)(ii) [G]§ 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv) § 115.787(e) § 115.787(f) § 115.787(g) § 115.788(a) § 115.788(a)(1) § 115.788(a)(2) § 115.788(a)(2)(A) § 115.788(a)(2)(B) § 115.788(a)(2)(C) § 115.788(a)(2)(C)(i) § 115.788(a)(2)(C)(ii) § 115.788(a)(2)(C)(iii) § 115.788(a)(2)(D) § 115.788(a)(3) § 115.788(a)(3)(A) § 115.788(a)(3)(B) [G]§ 115.788(g)	or in a waste stream is subject to the requirements of this division. A leak is defined as a screening concentration greater than 500 ppmv above background as methane for all components.	§ 115.781(b)(7)(A) § 115.781(b)(7)(B) § 115.781(b)(8) § 115.781(e) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.782(d)(2)	§ 115.781(g)(2) § 115.781(g)(3) [G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g) [G]§ 115.788(g)	
REF-FUG	EU	R5780-ALL	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Fugitive Emissions	§ 115.781(b)(9) § 115.780(b) [G]§ 115.781(a) [G]§ 115.781(d) § 115.781(g)(3) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(2) § 115.782(c)(2)(A) § 115.782(c)(2)(A)(i) § 115.782(c)(2)(A)(ii) § 115.782(c)(2)(B) § 115.783(1) § 115.783(1)(A) § 115.783(1)(B) § 115.783(5) § 115.787(f)	Bypass line valves within a petroleum refinery; synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process; or natural gas/gasoline processing operation in which a highly-reactive volatile organic compound is a raw material, intermediate, final product, or in a waste stream is subject to the requirements of this division. A leak is defined as a screening concentration greater than 500 ppmv above background as methane for	§ 115.781(b) § 115.781(b)(10) § 115.781(b)(4) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) [G]§ 115.781(d) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.782(d)(2) § 115.786(a)(1)	§ 115.781(b)(10) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) § 115.782(c)(2)(A)(ii) § 115.786(a)(1) § 115.786(a)(2) § 115.786(a)(2)(A) § 115.786(a)(2)(B) § 115.786(b)(1) § 115.786(b)(2) § 115.786(b)(2)(A) § 115.786(b)(2)(B) § 115.786(b)(2)(C) [G]§ 115.786(b)(3) [G]§ 115.786(c)	§ 115.782(c)(2)(A)(ii) [G]§ 115.786(c) § 115.788(c) [G]§ 115.788(d) § 115.788(e) [G]§ 115.788(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.787(f)(4) § 115.787(g) § 115.788(a) § 115.788(a)(1) § 115.788(a)(2) § 115.788(a)(2)(A) § 115.788(a)(2)(B) § 115.788(a)(2)(C) § 115.788(a)(2)(C)(i) § 115.788(a)(2)(C)(ii) § 115.788(a)(2)(C)(iii) § 115.788(a)(2)(D) § 115.788(a)(3) § 115.788(a)(3)(A) § 115.788(a)(3)(B) [G]§ 115.788(g)	all components.		§ 115.786(d) § 115.786(d)(2) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g) [G]§ 115.788(g)	
REF-FUG	EU	R5780-ALL	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Fugitive Emissions	§ 115.781(b)(9) § 115.780(b) [G]§ 115.781(a) § 115.781(g)(3) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(2) § 115.782(c)(2)(A) § 115.782(c)(2)(A)(i) § 115.782(c)(2)(A)(ii) § 115.782(c)(2)(B) § 115.783(5) § 115.787(f) § 115.787(f)(4) § 115.787(g) § 115.788(a) § 115.788(a)(1) § 115.788(a)(2) § 115.788(a)(2)(A) § 115.788(a)(2)(B) § 115.788(a)(2)(C) § 115.788(a)(2)(C)(i)	Valves within a petroleum refinery; synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process; or natural gas/gasoline processing operation which a highly-reactive volatile organic compound is a raw material, intermediate, final product, or in a waste stream is subject to the requirements of this division. A leak is defined as a screening concentration greater than 500 ppmv above background as methane for all components.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) § 115.781(b) § 115.781(b)(10) § 115.781(b)(4) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.782(d)(2)	§ 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5) § 115.781(b)(10) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) § 115.782(c)(2)(A)(ii) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(2) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g) [G]§ 115.788(g)	§ 115.782(c)(2)(A)(ii) [G]§ 115.786(c) § 115.788(c) [G]§ 115.788(d) § 115.788(e) [G]§ 115.788(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.788(a)(2)(C)(ii) § 115.788(a)(2)(C)(iii) § 115.788(a)(2)(D) § 115.788(a)(3) § 115.788(a)(3)(A) § 115.788(a)(3)(B) [G]§ 115.788(g)				
REF-FUG	EU	R5780-ALL	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Fugitive Emissions	§ 115.781(b)(9) § 115.780(b) [G]§ 115.781(a) § 115.781(g)(3) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) [G]§ 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) [G]§ 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv)	Flanges or other connectors within a petroleum refinery; synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process; or natural gas/gasoline processing operation in which a highly-reactive volatile organic compound is a raw material, intermediate, final product, or in a waste stream is subject to the requirements of this division. A leak is defined as a screening concentration greater than 500 ppmv above background as methane for all components.	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) § 115.781(b) § 115.781(b)(10) § 115.781(b)(3) § 115.781(b)(4) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) § 115.781(f) § 115.781(f)(1) § 115.781(f)(2) § 115.781(f)(3) § 115.781(f)(4) § 115.781(f)(5) § 115.781(f)(6) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.782(d)(2) § 115.789(1)(B)	§ 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5) § 115.781(b)(10) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) [G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g)	[G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.789(1)(B)
REF-FUG	EU	R5780-ALL	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Fugitive Emissions	§ 115.781(b)(9) § 115.780(b) [G]§ 115.781(a) § 115.781(g)(3) § 115.782(a)	Compressor seals within a petroleum refinery; synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6)	§ 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3)	[G]§ 115.782(c)(1)(B)(i) § 115.783(3)(C) [G]§ 115.786(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) [G]§ 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) [G]§ 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv) § 115.782(c)(1)(C)(i) § 115.782(c)(1)(C)(i)(I) § 115.782(c)(1)(C)(i)(II) § 115.782(c)(1)(C)(i)(III) § 115.782(c)(1)(C)(ii) § 115.783(3) [G]§ 115.783(3)(A) [G]§ 115.783(3)(B) § 115.787(b)	process; or natural gas/gasoline processing operation in which a highly-reactive volatile organic compound is a raw material, intermediate, final product, or in a waste stream is subject to the requirements of this division. A leak is defined as a screening concentration greater than 500 ppmv above background as methane for all components.	§ 115.354(9) § 115.781(b) § 115.781(b)(10) § 115.781(b)(4) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) § 115.781(c)(1) § 115.781(c)(2) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.782(d)(2)	§ 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5) § 115.781(b)(10) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) [G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g)	
REF-FUG	EU	R5780-ALL	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Fugitive Emissions	§ 115.781(b)(9) § 115.780(b) [G]§ 115.781(a) § 115.781(g)(3) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) [G]§ 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) [G]§ 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv) § 115.782(c)(1)(C)(i)	Pump seals within a petroleum refinery; synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process; or natural gas/gasoline processing operation in which a highly-reactive volatile organic compound is a raw material, intermediate, final product, or in a waste stream is subject to the requirements of this division. A leak is defined as a screening concentration greater than 500 ppmv above	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) § 115.781(b) § 115.781(b)(10) § 115.781(b)(4) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) § 115.781(c)(1) § 115.781(c)(2) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2)	§ 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5) § 115.781(b)(10) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) [G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c)	[G]§ 115.782(c)(1)(B)(i) § 115.783(3)(C) [G]§ 115.786(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.782(c)(1)(C)(i)(I) § 115.782(c)(1)(C)(i)(II) § 115.782(c)(1)(C)(i)(III) § 115.782(c)(1)(C)(ii) § 115.783(3) [G]§ 115.783(3)(A) [G]§ 115.783(3)(B) § 115.787(b) § 115.787(b)(1)	background as methane for all components.	§ 115.782(d)(2)	§ 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g)	
REF-FUG	EU	R5780-ALL	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Fugitive Emissions	§ 115.781(b)(9) § 115.780(b) [G]§ 115.781(a) § 115.781(g)(3) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) [G]§ 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) [G]§ 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv) § 115.782(c)(1)(C)(i) § 115.782(c)(1)(C)(i)(I) § 115.782(c)(1)(C)(i)(II) § 115.782(c)(1)(C)(i)(III) § 115.782(c)(1)(C)(ii) § 115.783(3) [G]§ 115.783(3)(A) [G]§ 115.783(3)(B) § 115.787(b)	Agitators within a petroleum refinery; synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process; or natural gas/gasoline processing operation in which a highly-reactive volatile organic compound is a raw material, intermediate, final product, or in a waste stream is subject to the requirements of this division. A leak is defined as a screening concentration greater than 500 ppmv above background as methane for all components.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) § 115.781(b) § 115.781(b)(10) § 115.781(b)(3) § 115.781(b)(4) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) § 115.781(c)(1) § 115.781(c)(2) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.782(d)(2)	§ 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5) § 115.781(b)(10) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) [G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g)	[G]§ 115.782(c)(1)(B)(i) § 115.783(3)(C) [G]§ 115.786(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
REF-FUG	EU	R5780-ALL	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Fugitive Emissions	§ 115.781(b)(9) § 115.780(b) [G]§ 115.781(a) § 115.781(g)(3) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) [G]§ 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) [G]§ 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv)	Heat exchanger heads, sight glasses, meters, gauges, sampling connections, bolted manways, hatches, sump covers, junction box vents, and covers and seals on VOC water separators within the process unit or processes listed in §115.780(a) in which a HRVOC is a raw material, intermediate, final product, or in a waste stream is subject to the requirements of this division. A leak is defined as a screening concentration greater than 500 ppmv above background as methane for all components.	§ 115.781(b) § 115.781(b)(10) § 115.781(b)(3) § 115.781(b)(4) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) § 115.781(f) § 115.781(f)(1) § 115.781(f)(2) § 115.781(f)(3) § 115.781(f)(4) § 115.781(f)(5) § 115.781(f)(6) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.782(d)(2) § 115.789(1)(B)	§ 115.781(b)(10) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) [G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g)	[G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.789(1)(B)
REF-FUG	EU	R5780-ALL	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Fugitive Emissions	§ 115.781(b)(9) § 115.358(c)(1) [G]§ 115.358(h) § 115.780(b) [G]§ 115.781(a) § 115.781(g)(3) § 115.782(a) § 115.782(b)(2) § 115.782(b)(3) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) [G]§ 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) [G]§ 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv)	Components within the process unit or processes listed in §115.780(a) is subject to the requirements of this division. If the owner of operator elects to use the alternative work practice in §115.358 of this title, a leak is defined as specified in §115.358 of this title, including any leak detected using the alternative work practice on a component that is subject to the requirements of this division but not specifically selected for alternative work practice monitoring.	§ 115.354(1) § 115.354(11) § 115.354(13)(A) § 115.354(13)(B) § 115.354(13)(C) § 115.354(13)(D) § 115.354(13)(E) § 115.354(13)(F) § 115.354(4) § 115.354(5) § 115.354(9) § 115.358(c)(2) § 115.358(d) [G]§ 115.358(e) § 115.358(f) § 115.781(b) § 115.781(b)(4) § 115.781(b)(7)	§ 115.354(13)(D) § 115.354(13)(E) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) [G]§ 115.356(4) § 115.356(5) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) [G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c)	[G]§ 115.358(g) [G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 115.781(b)(7)(A) § 115.781(b)(7)(B) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(h)(1) § 115.781(h)(2) § 115.781(h)(3) § 115.781(h)(4) § 115.781(h)(5) [G]§ 115.781(h)(6) § 115.782(b)(4) § 115.782(d)(1) § 115.788(h)(1) [G]§ 115.788(h)(2) § 115.788(h)(3)	§ 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) [G]§ 115.786(f) § 115.786(g)	
REF-FUG	EU	R5780-ALL	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Fugitive Emissions	§ 115.781(b)(9) § 115.780(b) [G]§ 115.781(a) § 115.781(g)(3) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(2) § 115.782(c)(2)(A) § 115.782(c)(2)(A)(i) § 115.782(c)(2)(A)(ii) § 115.782(c)(2)(B) § 115.783(5) § 115.787(f) § 115.787(f)(2) § 115.787(f)(3) § 115.787(f)(4) § 115.787(g) § 115.788(a) § 115.788(a)(1) § 115.788(a)(2) § 115.788(a)(2)(A) § 115.788(a)(2)(B)	Open-ended valves or lines within a petroleum refinery; synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process; or natural gas/gasoline processing operation in which a highly-reactive volatile organic compound is a raw material, intermediate, final product, or in a waste stream is subject to the requirements of this division. A leak is defined as a screening concentration greater than 500 ppmv above background as methane for all components.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) § 115.781(b) § 115.781(b)(10) § 115.781(b)(3) § 115.781(b)(4) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) § 115.781(f) § 115.781(f)(1) § 115.781(f)(2) § 115.781(f)(3) § 115.781(f)(4) § 115.781(f)(5) § 115.781(f)(6) § 115.781(g) § 115.781(g)(1)	§ 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5) § 115.781(b)(10) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) § 115.782(c)(2)(A)(ii) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(2) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g) [G]§ 115.788(g)	§ 115.782(c)(2)(A)(ii) [G]§ 115.786(c) § 115.788(c) [G]§ 115.788(d) § 115.788(e) [G]§ 115.788(g) § 115.789(1)(B)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.788(a)(2)(C) § 115.788(a)(2)(C)(i) § 115.788(a)(2)(C)(ii) § 115.788(a)(2)(C)(iii) § 115.788(a)(2)(D) § 115.788(a)(3) § 115.788(a)(3)(A) § 115.788(a)(3)(B) [G]§ 115.788(g)		§ 115.781(g)(2) § 115.782(d)(2) § 115.789(1)(B)		
REF-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(6)	Components at a petroleum refinery or synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process, that contact a process fluid that contains less than 10% VOC by weight and components at a natural gas/gasoline processing operation that contact a process fluid that contains less than 1.0% VOC by weight are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
REF-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(5)	Reciprocating compressors and positive displacement pumps used in natural gas/gasoline processing operations are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
REF-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(10)	Instrumentation systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet 40 CFR §63.169	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						(June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.			
REF-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(11)	Sampling connection systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet the requirements of 40 CFR §63.166(a) and (b) (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
REF-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(13)	Components/systems that contact a process fluid containing VOC having a true vapor pressure equal to or less than 0.002 psia at 68 degrees Fahrenheit are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
REF-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(2) § 115.352(9)	Each pressure relief valve equipped with a rupture disk must comply with §115.352(9) and §115.356(3)(C).	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
REF-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.353(a) § 115.353(b) § 115.910	For all affected persons in the Beaumont-Port Arthur, Dallas-Fort Worth, El Paso, and Houston-Galveston areas, as defined in §115.10, any alternate methods of demonstrating and documenting	None	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						continuous compliance with the applicable control requirements or exemption criteria in this division may be approved by the executive director in accordance with §115.910 if emission reductions are demonstrated to be substantially equivalent.			
REF-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(C) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.352(8) § 115.357(8) § 115.358(c)(1) [G]§ 115.358(h)	No component shall be allowed to have a VOC leak, for more than 15 days, after discovery. If the owner or operator elects to use the alternative work practice in §115.358 of this title, any leak detected as defined in §115.358 of this title, including any leak detected using the alternative work practice on a component that is subject to the requirements of this division but not specifically selected for alternative work practice monitoring.	§ 115.354(1) § 115.354(11) § 115.354(13)(A) § 115.354(13)(B) § 115.354(13)(C) § 115.354(13)(D) § 115.354(13)(E) § 115.354(13)(F) § 115.354(4) § 115.354(5) § 115.354(9) [G]§ 115.355 § 115.358(c)(2) § 115.358(d) [G]§ 115.358(e) § 115.358(f)	§ 115.352(7) § 115.354(13)(D) § 115.354(13)(E) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) [G]§ 115.356(4) § 115.356(5)	[G]§ 115.358(g)
REF-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7) § 115.357(1)	No process drains shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping	§ 115.354(1) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						or exuding of process fluid based on sight, smell, or sound.			
REF-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7)	No process drains shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(5)	None
REF-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(9) § 115.357(1) § 115.357(8) § 115.357(9)	No pressure relief valves shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
REF-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(9)	No pressure relief valves shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.357(12) § 115.357(8) § 115.357(9)	based on sight, smell, or sound.			
REF-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(8) § 115.357(9)	No open-ended valves or lines shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
REF-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8) § 115.357(9)	No open-ended valves or lines shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
REF-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3)	No valves shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(8) § 115.357(9)	background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.357(1)		
REF-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8) § 115.357(9)	No valves shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
REF-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(8) § 115.357(1) § 115.357(12) § 115.357(8)	No flanges or other connectors shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
REF-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A)	No flanges or other connectors shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(3) § 115.352(5) § 115.352(7) § 115.352(8) § 115.357(12) § 115.357(8)	screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	
REF-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(7) § 115.357(1) § 115.357(12) § 115.357(8)	No agitators shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
REF-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(7) § 115.357(1) § 115.357(12) § 115.357(8)	No agitators shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
REF-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery &	§ 115.352(1)(A) § 115.352(1) § 115.352(10)	No agitators shall be allowed to have a VOC leak, for more than 15 days	§ 115.354(1) § 115.354(10) § 115.354(5)	§ 115.352(7) § 115.354(10) § 115.356	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Petrochemicals	§ 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(7) § 115.357(12) § 115.357(8)	after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	[G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	
REF-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(3) § 115.357(8)	No compressor seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None
REF-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(4) § 115.357(8)	No compressor seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
REF-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1) § 115.357(8)	No compressor seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None
REF-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	No compressor seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
REF-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3)	No pump seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(5) § 115.352(7) § 115.357(4) § 115.357(8)	based on sight, smell, or sound.			
REF-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1) § 115.357(8)	No pump seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None
REF-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	No pump seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
REF-FUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(d)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for equipment in vacuum service.	None	§ 60.486(e) § 60.486(e)(1) § 60.486(e)(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
REF-FUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-2 [G]§ 60.482-9 § 63.648(a)(2) § 63.648(f) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pumps in light liquid service complying with §60.482-2.	[G]§ 60.482-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(d)(6) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
REF-FUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-3 [G]§ 60.482-9 § 63.648(a)(2) § 63.648(i) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for compressors complying with §60.482-3.	[G]§ 60.482-3 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(d)(6) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
REF-FUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) § 60.482-4(a) § 60.482-4(b)(1) [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pressure relief devices in gas/vapor service.	§ 60.482-4(b)(2) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(3) [G]§ 60.486(e)(4) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
REF-FUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 60.482-5 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	sampling connection systems complying with §60.482-5.	§ 60.485(f)	§ 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(e)
REF-FUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-6 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for open-ended valves or lines complying with §60.482-6.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
REF-FUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-7 [G]§ 60.482-9 [G]§ 60.483-1 [G]§ 60.483-2 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for valves in gas/vapor service or in light liquid service complying with §60.482-7.	[G]§ 60.482-7 [G]§ 60.483-1 [G]§ 60.483-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) [G]§ 60.486(g) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(d) § 60.487(e)
REF-FUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for valves in heavy liquid service complying with §60.482-8.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
REF-FUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pumps in heavy liquid service	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	complying with §60.482-8.	§ 60.485(f) [G]§ 63.648(b)	§ 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	
REF-FUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for flanges or other connectors complying with §60.482-8.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
REF-FUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pressure relief devices in light liquid service complying with §60.482-8.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
REF-FUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9 § 63.648(a)(2) § 63.655(d)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pressure relief devices in heavy liquid service complying with §60.482-8.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) [G]§ 63.648(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i)(5)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
REF-FUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	[G]§ 63.648(g)	Compressors in hydrogen service are exempt from the requirements of §63.648(a) and (c), if an owner or operator demonstrates that	[G]§ 63.648(g)	§ 63.648(h) § 63.655(d)(3) § 63.655(i)(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						a compressor is in hydrogen service. §63.648(g)(1)-(2).			
RHU-201B	EU	R7300-1018	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(ii) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C) § 117.8000(b) § 117.8000(c) § 117.8000(c)(1) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
RHU-201B	EU	R7300-1018	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B) § 117.310(c)(3)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.8000(b) § 117.8000(c) § 117.8000(c)(2) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8120 § 117.8120(2)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							[G]§ 117.8120(2)(A) § 117.8120(2)(B)		
RHU-201B	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
RHU-201B	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
RHU-202B	EU	R7300-1018	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(ii) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C) § 117.8000(b) § 117.8000(c) § 117.8000(c)(1) § 117.8000(c)(3) § 117.8000(c)(5)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						specified in § 117.9800 to comply with § 117.320.	§ 117.8000(c)(6) [G]§ 117.8000(d)		
RHU-202B	EU	R7300-1018	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B) § 117.310(c)(3)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.8000(b) § 117.8000(c) § 117.8000(c)(2) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8120 § 117.8120(2) [G]§ 117.8120(2)(A) § 117.8120(2)(B)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
RHU-202B	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
RHU-202B	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
RHU-301B	EU	R7300-1018	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(ii) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C) § 117.8000(b) § 117.8000(c) § 117.8000(c)(1) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
RHU-301B	EU	R7300-1018	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B) § 117.310(c)(3)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.8000(b) § 117.8000(c) § 117.8000(c)(2) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8120 § 117.8120(2) [G]§ 117.8120(2)(A) § 117.8120(2)(B)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
RHU-301B	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
RHU-301B	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
RHU-302B	EU	R7300-1018	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(ii) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C) § 117.8000(b) § 117.8000(c) § 117.8000(c)(1) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
RHU-302B	EU	R7300-1018	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B) § 117.310(c)(3)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.8000(b) § 117.8000(c) § 117.8000(c)(2) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8120 § 117.8120(2) [G]§ 117.8120(2)(A) § 117.8120(2)(B)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
RHU-302B	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
RHU-302B	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
RHU-401B	EU	R7300-1018	NO_X	30 TAC Chapter 117,	§ 117.310(d)(3) § 117.310(a)	An owner or operator may not use the alternative	[G]§ 117.335(a)(1) § 117.335(a)(4)	§ 117.345(a) § 117.345(f)	§ 117.335(b) § 117.335(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Subchapter B	§ 117.310(a)(8)(A)(ii) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	§ 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C) § 117.8000(b) § 117.8000(c) § 117.8000(c)(1) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d)	§ 117.345(f)(1) § 117.345(f)(9)	§ 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
RHU-401B	EU	R7300-1018	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B) § 117.310(c)(3)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.8000(b) § 117.8000(c) § 117.8000(c)(2) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8120 § 117.8120(2) [G]§ 117.8120(2)(A) § 117.8120(2)(B)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
RHU-401B	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of	§ 60.105(a)(4) § 60.105(a)(4)(i)	§ 60.105(a)(4) § 60.105(a)(4)(i)	§ 60.105(e)(3)(ii) § 60.107(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4)(iii)	§ 60.107(f) § 60.107(g)
RHU-401B	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
RHU-402B	EU	R7300-1018	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(ii) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C) § 117.8000(b) § 117.8000(c) § 117.8000(c)(1) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
RHU-402B	EU	R7300-1018	CO	30 TAC Chapter 117,	§ 117.310(c)(1) § 117.310(c)(1)(B)	CO emissions must not exceed 400 ppmv at 3.0%	[G]§ 117.335(a)(1) § 117.335(a)(4)	§ 117.345(a) § 117.345(f)	§ 117.335(b) § 117.335(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Subchapter B	§ 117.310(c)(3)	O 2, dry basis.	§ 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.8000(b) § 117.8000(c) § 117.8000(c)(2) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8120 § 117.8120(2) [G]§ 117.8120(2)(A) § 117.8120(2)(B)	§ 117.345(f)(1) § 117.345(f)(9)	[G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
RHU-402B	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
RHU-402B	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
RHU-501B	EU	R7300-1097	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	§ 117.335(d) § 117.335(f) § 117.335(f)(2) § 117.335(g) § 117.340(a)(2)(B) § 117.340(c)(1) [G]§ 117.340(c)(3) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)	117.345(f)(2)(C) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
RHU-501B	EU	R7300-1097	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a)(2)(B) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)		§ 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
RHU-501B	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
RHU-501B	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
RHU-502B	EU	R7300-1290	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i)	An owner or operator may not use the alternative methods specified in §§	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b)	§ 117.345(a) § 117.345(f) § 117.345(f)(1)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	§ 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(2) § 117.335(g) § 117.340(a) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) [G]§ 117.340(c)(3) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)	[G]§ 117.345(f)(2) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	[G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
RHU-502B	EU	R7300-1290	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.340(b)(1) § 117.340(b)(3) § 117.340(e) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)		§ 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
RHU-502B	EU	60Ja-0003	§111 Pollutant	40 CFR Part 60, Subpart Ja	§ 60.100a(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 60, Subpart Ja
RHU-502B	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR	The permit holder shall comply with the applicable recordkeeping requirements of 40	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					equipment specification requirements of 40 CFR Part 63, Subpart DDDDD		Part 63, Subpart DDDDD	CFR Part 63, Subpart DDDDD	
RHU-601B	EU	R7300-1086	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C) § 117.8000(b) § 117.8000(c) § 117.8000(c)(1) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
RHU-601B	EU	R7300-1086	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B) § 117.310(c)(3)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.8000(b) § 117.8000(c) § 117.8000(c)(2) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							[G]§ 117.8000(d) § 117.8120 § 117.8120(2) [G]§ 117.8120(2)(A) § 117.8120(2)(B)		[G]§ 117.8010(7) [G]§ 117.8010(8)
RHU-601B	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
RHU-601B	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
RHUCP-FUG1	EU	60GGGa-001	VOC	40 CFR Part 60, Subpart GGGa	[G]§ 60.590a(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 60, Subpart GGGa
RHU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(d)	Comply with the requirements as stated in §60.482-1(d) for equipment in vacuum service.	None	§ 60.486(e) § 60.486(e)(1) § 60.486(e)(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
RHU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-2 [G]§ 60.482-9	Comply with the requirements as stated in §60.482-2 for pumps in light-liquid service.	[G]§ 60.482-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d) § 60.593(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
RHU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.593(b)(1)	Compressors in hydrogen service are exempt from the requirements of §60.592 if an owner or operator demonstrates that a compressor is in hydrogen service.	§ 60.593(b)(2) [G]§ 60.593(b)(3)	None	None
RHU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-3 [G]§ 60.482-9	Comply with the requirements as stated in §60.482-3 for compressors.	[G]§ 60.482-3 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
RHU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-4 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-4 for pressure relief devices in gas/vapor service.	[G]§ 60.482-4 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(3) [G]§ 60.486(e)(4) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
RHU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b)	Comply with the requirements in as stated in §60.482-5 for sampling	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 60.482-5 [G]§ 60.482-9	connection systems.	§ 60.485(f) § 60.592(d)	§ 60.486(j) § 60.592(e)	§ 60.487(e) § 60.592(e)
RHU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-6 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-6 for open-ended valves and lines.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
RHU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-7 [G]§ 60.482-9 [G]§ 60.483-1 [G]§ 60.483-2 § 60.592(b)	Comply with the requirements in as stated in §60.482-7 for valves in gas/vapor or light-liquid service.	[G]§ 60.482-7 [G]§ 60.483-1 [G]§ 60.483-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d) § 60.593(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) [G]§ 60.486(g) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(d) § 60.487(e) § 60.592(e)
RHU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for pumps in heavy-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
RHU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) § 60.482-10(b) § 60.482-10(e) § 60.482-10(m)	Comply with the requirements in as stated in §60.482-10 for vapor recovery devices.	§ 60.485(a) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
RHU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.18 § 60.482-1(a) § 60.482-1(b) § 60.482-10(d)	Comply with the requirements in as stated in §60.482-10 for flares.	§ 60.485(a) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) [G]§ 60.485(g)	[G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.482-10(e) § 60.482-10(m)		§ 60.592(d)		
RHU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) § 60.482-10(e) [G]§ 60.482-10(g) § 60.482-10(h) § 60.482-10(m)	Comply with the requirements in as stated in §60.482-10 for closed-vent systems.	[G]§ 60.482-10(f) § 60.482-10(i) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.482-10(j) [G]§ 60.482-10(k) [G]§ 60.482-10(l) [G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
RHU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for valves in heavy-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
RHU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for flanges or other connectors.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
RHU-FUG	EU	60GGG-0001	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for pressure relief devices in light-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
RHU-SEP1	EU	R5131-0010	VOC	30 TAC Chapter 115, Water Separation	§ 115.132(a)(3) § 115.131(a)	VOC water separator compartments must be equipped with a vapor recovery system which satisfies the provisions of	[G]§ 115.135(a) § 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	§ 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						§115.131(a) of this title.			
RHU-SEP1	EU	61FF-1781	Benzene	40 CFR Part 61, Subpart FF	§ 61.347(a)(1) § 61.347(a)(1)(i)(A) § 61.347(a)(1)(i)(B) § 61.347(b) § 61.347(c) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	Install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the oil-water separator to a control device.	§ 61.347(a)(1)(i)(A) § 61.347(b) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.349(a)(1)(ii) § 61.356(d) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i)	None
RHU-SEP2	EU	R5131-0010	VOC	30 TAC Chapter 115, Water Separation	§ 115.132(a)(3) § 115.131(a)	VOC water separator compartments must be equipped with a vapor recovery system which satisfies the provisions of §115.131(a) of this title.	[G]§ 115.135(a) § 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	§ 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	None
RHU-SEP2	EU	61FF-1781	Benzene	40 CFR Part 61, Subpart FF	§ 61.347(a)(1) § 61.347(a)(1)(i)(A) § 61.347(a)(1)(i)(B) § 61.347(b) § 61.347(c) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f)	Install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the oil-water separator to a control device.	§ 61.347(a)(1)(i)(A) § 61.347(b) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.349(a)(1)(ii) § 61.356(d) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 61.349(g)				
RHU-T1012	EU	R5112-0012	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
RHU-T1012	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2) § 63.640(n)(7)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
RHU-T1013	EU	R5112-0012	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
RHU-T1013	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2) § 63.640(n)(7)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
SHU3-B301	EU	R7300-0001	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(8)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	§ 117.335(f) § 117.335(f)(2) § 117.335(g) § 117.340(a) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) [G]§ 117.340(c)(3) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)	§ 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
SHU3-B301	EU	R7300-0001	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a) § 117.340(b)(1) § 117.340(b)(3)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.340(e) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)		§ 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
SHU3-B301	EU	R7300-0001	NH_3	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(2) § 117.310(c)(2)(B) § 117.340(f)(1)	For process heaters that inject urea or ammonia into the exhaust stream for NO_x control, ammonia emissions must not exceed 10 ppmv at 3.0% O_2, dry.	§ 117.335(a)(2) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(g) § 117.340(b)(1) § 117.340(b)(3) § 117.340(d) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3)	§ 117.345(a) § 117.345(f) § 117.345(f)(11) [G]§ 117.345(f)(2) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8130 § 117.8130(4)		[G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
SHU3-B301	EU	60Ja-0001	NO_X	40 CFR Part 60, Subpart Ja	§ 60.102a(a) § 60.100a § 60.100a(a) § 60.100a(b) § 60.102a § 60.102a(g) § 60.102a(g)(2) § 60.102a(g)(2)(ii) § 60.102a(g)(2)(ii)(B)	Each owner or operator that is subject to the requirements of this subpart shall comply with the emissions limitations in § 60.102a(b)-(h) on and after the date on which the initial performance test, required by § 60.8, is completed, but not later than 60 days after achieving the maximum production rate at which the affected facility will be operated, or 180 days after initial startup, whichever comes first.	§ 60.104a(a) § 60.104a(c) § 60.104a(i) § 60.104a(i)(1) § 60.104a(i)(2) § 60.104a(i)(3) § 60.104a(i)(5) § 60.104a(i)(7) § 60.104a(i)(8) § 60.107a(c)(1) § 60.107a(c)(2) § 60.107a(c)(3) § 60.107a(c)(4) § 60.107a(c)(5) § 60.107a(d) § 60.107a(d)(1) § 60.107a(d)(2) § 60.107a(d)(4) § 60.107a(d)(5) § 60.107a(d)(7) § 60.107a(i) § 60.107a(i)(3) § 60.107a(i)(3)(ii)	§ 60.108a § 60.108a(a)	§ 60.108a § 60.108a(a) § 60.108a(b) § 60.108a(d) § 60.108a(d)(1) § 60.108a(d)(2) § 60.108a(d)(3) § 60.108a(d)(4) § 60.108a(d)(5) § 60.108a(d)(6) § 60.108a(d)(7)
SHU3-B301	EU	60Ja-0001	Hydrogen Sulfide	40 CFR Part 60, Subpart Ja	§ 60.102a(a) § 60.100a § 60.100a(a) § 60.100a(b) § 60.102a § 60.102a(g)	Each owner or operator that is subject to the requirements of this subpart shall comply with the emissions limitations in § 60.102a(b)-(h) on and after	§ 60.104a § 60.104a(a) § 60.104a(c) § 60.104a(j) § 60.104a(j)(4)(iv) § 60.107a	§ 60.108a § 60.108a(a) § 60.108a(c) § 60.108a(c)(6) § 60.108a(c)(6)(i) § 60.108a(c)(6)(ii)	§ 60.108a § 60.108a(a) § 60.108a(b) § 60.108a(d) § 60.108a(d)(1) § 60.108a(d)(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.102a(g)(1) § 60.102a(g)(1)(ii) § 60.103a § 60.103a(c) § 60.103a(c)(2) § 60.103a(d) § 60.103a(d)(1) § 60.103a(d)(5) § 60.103a(e) § 60.103a(e)(1) § 60.103a(e)(2) § 60.103a(e)(3)	the date on which the initial performance test, required by § 60.8, is completed, but not later than 60 days after achieving the maximum production rate at which the affected facility will be operated, or 180 days after initial startup, whichever comes first.	§ 60.107a(a) § 60.107a(a)(2) § 60.107a(a)(2)(i) § 60.107a(a)(2)(ii) § 60.107a(a)(2)(iii) § 60.107a(a)(2)(iv) § 60.107a(i) § 60.107a(i)(1) § 60.107a(i)(1)(ii)	§ 60.108a(c)(6)(iii) § 60.108a(c)(6)(ix) § 60.108a(c)(6)(v) § 60.108a(c)(6)(vii) § 60.108a(c)(6)(viii) § 60.108a(c)(6)(x)	§ 60.108a(d)(3) § 60.108a(d)(4) § 60.108a(d)(5) § 60.108a(d)(6) § 60.108a(d)(7)
SHU3-B301	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7500(a)(1)-Table 3.1 § 63.7499(l) § 63.7500(a) § 63.7500(a)(3) § 63.7500(e) § 63.7505(a) § 63.7510(g) § 63.7515(g) § 63.7530(f) § 63.7540(a)(12) § 63.7540(a)(13)	A new or existing limited use boiler or process heater with a heat input capacity of less than or equal to 5 million Btu per hour must conduct a tune-up of the boiler or process heater every 5 years as specified in § 63.7540.	§ 63.7510(g) § 63.7515(d) § 63.7515(g) § 63.7540(a)(12) § 63.7540(a)(13)	§ 63.7555(a) § 63.7555(a)(1) § 63.7555(h) § 63.7560(a) § 63.7560(b) § 63.7560(c)	§ 63.7530(f) § 63.7545(a) § 63.7545(c) § 63.7545(e) § 63.7545(e)(1) § 63.7545(e)(6) § 63.7545(e)(7) § 63.7545(e)(8) § 63.7545(e)(8)(i) § 63.7545(f) [G]§ 63.7545(h) § 63.7550(a) [G]§ 63.7550(b) § 63.7550(c) § 63.7550(c)(1) § 63.7550(c)(5)(i) § 63.7550(c)(5)(ii) § 63.7550(c)(5)(iii) § 63.7550(c)(5)(xiv) § 63.7550(c)(5)(xvii) § 63.7550(h) § 63.7550(h)(3)
SHU3-FUG1	EU	60GGGa-01	VOC	40 CFR Part 60, Subpart GGGa	§ 60.592a(a) § 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(g)	Comply with the requirements as stated in §60.482-2a for pumps in light liquid service.	§ 60.482-1a(f)(1) § 60.482-1a(f)(2) [G]§ 60.482-1a(f)(3) § 60.482-1a(g)	§ 60.482-1a(g) § 60.485a(b)(2) [G]§ 60.486a(a)(3) [G]§ 60.486a(b)	§ 60.487a(a) § 60.487a(b) § 60.487a(b)(1) § 60.487a(b)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 60.482-2a(b)(1) § 60.482-2a(b)(2) § 60.482-2a(b)(2)(ii) § 60.482-2a(c)(1) [G]§ 60.482-2a(c)(2) § 60.482-2a(d) [G]§ 60.482-2a(d)(1) § 60.482-2a(d)(2) § 60.482-2a(d)(3) [G]§ 60.482-2a(d)(6) [G]§ 60.482-2a(e) § 60.482-2a(f) [G]§ 60.482-2a(g) § 60.482-2a(h) § 60.482-9a(a) § 60.482-9a(b) [G]§ 60.482-9a(d) § 60.482-9a(f) § 60.485a(b) § 60.485a(c) § 60.485a(c)(1) § 60.485a(f) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k) § 60.592a(d) § 60.592a(e)		§ 60.482-2a(a)(1) § 60.482-2a(a)(2) § 60.482-2a(b)(2)(i) [G]§ 60.482-2a(d)(4) [G]§ 60.482-2a(d)(5) § 60.482-9a(a) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2) § 60.485a(c)(2) [G]§ 60.485a(d) [G]§ 60.485a(e)	[G]§ 60.486a(c) § 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(2) [G]§ 60.486a(e)(4) § 60.486a(e)(7) [G]§ 60.486a(e)(8) § 60.486a(f) § 60.486a(f)(1) [G]§ 60.486a(h)	§ 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(iii) § 60.487a(c)(2)(iv) § 60.487a(c)(2)(ix) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)
SHU3-FUG1	EU	60GGGa-01	VOC	40 CFR Part 60, Subpart GGGa	§ 60.592a(a) § 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(g) § 60.482-4a(a) § 60.482-4a(b)(1) § 60.482-4a(b)(2) § 60.482-4a(c) § 60.482-4a(d)(1) § 60.482-4a(d)(2) § 60.482-9a(a) § 60.482-9a(b)	Comply with the requirements as stated in §60.482-4a for pressure relief devices in gas/vapor service.	§ 60.482-1a(g) § 60.482-8a(a)(1) § 60.482-9a(a) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2) [G]§ 60.485a(d) [G]§ 60.485a(e)	§ 60.482-1a(g) § 60.485a(b)(2) § 60.486a(e) § 60.486a(e)(1) § 60.486a(e)(10) § 60.486a(e)(3) § 60.486a(e)(4) [G]§ 60.486a(e)(8)	§ 60.487a(a) § 60.487a(b) § 60.487a(b)(1) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(ix) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.485a(b) § 60.485a(c) § 60.485a(c)(1) § 60.485a(f) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k) § 60.592a(d) § 60.592a(e)				
SHU3-FUG1	EU	60GGGa-01	VOC	40 CFR Part 60, Subpart GGGa	§ 60.592a(a) § 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(g) § 60.482-6a(a)(1) § 60.482-6a(a)(2) § 60.482-6a(b) § 60.482-6a(e) § 60.485a(b) § 60.485a(f) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k) § 60.592a(d) § 60.592a(e)	Comply with the requirements as stated in §60.482-6a for open-ended valves and lines.	§ 60.482-1a(g) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2) [G]§ 60.485a(d)	§ 60.482-1a(g) § 60.485a(b)(2) § 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(8)	§ 60.487a(a) § 60.487a(b) § 60.487a(b)(1) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(ix) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)
SHU3-FUG1	EU	60GGGa-01	VOC	40 CFR Part 60, Subpart GGGa	§ 60.592a(a) § 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(g) § 60.482-7a(a)(1) § 60.482-7a(b) [G]§ 60.482-7a(d) [G]§ 60.482-7a(e) [G]§ 60.482-7a(h) § 60.485a(b) § 60.485a(c) § 60.485a(c)(1) § 60.485a(f) § 60.486a(a)(1)	Comply with the requirements as stated in §60.482-7a for valves in gas/vapor or light liquid service.	§ 60.482-1a(f)(1) § 60.482-1a(f)(2) [G]§ 60.482-1a(f)(3) § 60.482-1a(g) § 60.482-7a(a)(1) [G]§ 60.482-7a(a)(2) [G]§ 60.482-7a(c) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2) § 60.485a(c)(2) [G]§ 60.485a(d) [G]§ 60.485a(e) § 60.593a(d)	§ 60.482-1a(g) § 60.485a(b)(2) § 60.486a(a)(2) [G]§ 60.486a(a)(3) [G]§ 60.486a(b) [G]§ 60.486a(c) § 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(2) [G]§ 60.486a(e)(4) [G]§ 60.486a(e)(8) § 60.486a(f) § 60.486a(f)(1) § 60.486a(f)(2)	§ 60.482-1a(g) § 60.487a(a) § 60.487a(b) § 60.487a(b)(1) § 60.487a(b)(2) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(i) § 60.487a(c)(2)(ii) § 60.487a(c)(2)(ix) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.486a(k) § 60.592a(d) § 60.592a(e)				
SHU3-FUG1	EU	60GGGa-01	VOC	40 CFR Part 60, Subpart GGGa	§ 60.592a(a) § 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(g) [G]§ 60.482-2a(c)(2) [G]§ 60.482-7a(e) § 60.482-8a(a) § 60.482-8a(a)(2) § 60.482-8a(b) [G]§ 60.482-8a(c) § 60.482-8a(d) § 60.482-9a(a) § 60.482-9a(b) § 60.482-9a(c) § 60.482-9a(c)(1) § 60.482-9a(e) § 60.482-9a(f) § 60.485a(b) § 60.485a(f) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k) § 60.592a(d) § 60.592a(e)	Comply with the requirements as stated in §60.482-8a for valves in heavy liquid service.	§ 60.482-1a(g) § 60.482-8a(a)(1) § 60.482-9a(a) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2) [G]§ 60.485a(d)	§ 60.482-1a(g) § 60.485a(b)(2) [G]§ 60.486a(a)(3) [G]§ 60.486a(b) [G]§ 60.486a(c) § 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(8)	§ 60.487a(a) § 60.487a(b) § 60.487a(b)(1) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(ix) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)
SHU3-FUG1	EU	60GGGa-01	VOC	40 CFR Part 60, Subpart GGGa	§ 60.592a(a) § 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(g) [G]§ 60.482-2a(c)(2) [G]§ 60.482-7a(e) § 60.482-8a(a) § 60.482-8a(a)(2) § 60.482-8a(b) [G]§ 60.482-8a(c) § 60.482-8a(d)	Comply with the requirements as stated in §60.482-8a for connectors in heavy liquid service.	§ 60.482-1a(g) § 60.482-8a(a)(1) § 60.482-9a(a) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2) [G]§ 60.485a(d)	§ 60.482-1a(g) § 60.485a(b)(2) [G]§ 60.486a(a)(3) [G]§ 60.486a(b) [G]§ 60.486a(c) § 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(8)	§ 60.487a(a) § 60.487a(b) § 60.487a(b)(1) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(ix) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.482-9a(a) § 60.482-9a(b) § 60.482-9a(c) § 60.482-9a(c)(1) § 60.482-9a(c)(2) § 60.482-9a(f) § 60.485a(b) § 60.485a(f) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k) § 60.592a(d) § 60.592a(e)				
SHU3-FUG1	EU	60GGGa-01	VOC	40 CFR Part 60, Subpart GGGa	§ 60.592a(a) § 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(g) [G]§ 60.482-2a(c)(2) [G]§ 60.482-7a(e) § 60.482-8a(a) § 60.482-8a(a)(2) § 60.482-8a(b) [G]§ 60.482-8a(c) § 60.482-8a(d) § 60.482-9a(a) § 60.482-9a(b) § 60.485a(b) § 60.485a(f) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k) § 60.592a(d) § 60.592a(e)	Comply with the requirements as stated in §60.482-8a for pressure relief devices in light liquid service.	§ 60.482-1a(g) § 60.482-8a(a)(1) § 60.482-9a(a) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2) [G]§ 60.485a(d) [G]§ 60.485a(e) § 60.593a(d)	§ 60.482-1a(g) § 60.485a(b)(2) [G]§ 60.486a(a)(3) [G]§ 60.486a(b) [G]§ 60.486a(c) § 60.486a(e) § 60.486a(e)(1) § 60.486a(e)(10) [G]§ 60.486a(e)(8)	§ 60.487a(a) § 60.487a(b) § 60.487a(b)(1) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(ix) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)
SHU3-FUG1	EU	60GGGa-01	VOC	40 CFR Part 60, Subpart GGGa	§ 60.593a(g) § 60.482-11a(b)(2) § 60.482-11a(b)(3) § 60.482-11a(b)(3)(i) § 60.482-11a(d)	Connectors in gas/vapor or light liquid service are exempt from the requirements in §60.482-11a, provided the owner or	§ 60.482-11a(a) § 60.482-11a(b) § 60.482-11a(b)(1) § 60.482-11a(b)(3) § 60.482-11a(b)(3)(ii)	§ 60.482-11a(b)(3)(v) § 60.485a(b)(2) [G]§ 60.486a(a)(3) [G]§ 60.486a(b)	§ 60.487a(b) § 60.487a(b)(1) § 60.487a(b)(5) § 60.487a(c) § 60.487a(c)(1)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 60.482-11a(e) [G]§ 60.482-11a(f)(1) § 60.482-11a(f)(2) § 60.482-11a(g) § 60.485a(b) § 60.486a(a)(1) § 60.486a(a)(2) § 60.592a(d) § 60.592a(e)	operator complies with §60.482-8a for all connectors, not just those in heavy liquid service.	[G]§ 60.482-11a(b)(3)(iii) § 60.482-11a(b)(3)(iv) § 60.482-11a(c) § 60.485a(b)(2) [G]§ 60.485a(e) § 60.593a(d)	[G]§ 60.486a(c) § 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(8) § 60.486a(e)(9) § 60.486a(f) § 60.486a(f)(1)	§ 60.487a(c)(2) § 60.487a(c)(2)(i) § 60.487a(c)(2)(ix) § 60.487a(c)(2)(vii) § 60.487a(c)(2)(viii) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)
SRU-CT	EU	R5760-0025	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Cooling Towers	§ 115.767(3) § 115.766(i)	Any site for which no stream directed to a cooling tower heat exchange system contains 5.0% or greater by weight HRVOC is exempt from the requirements of _115.761 of this title (relating to Site-wide Cap).	§ 115.764(c) § 115.764(d) § 115.764(e)(1)	§ 115.766(c) § 115.766(d) [G]§ 115.766(e) § 115.766(i)(1)	§ 115.766(i)(2)
SRU-CT	EU	63CC-002	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC
SRU-F8C	EU	R7300-3144	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) [G]§ 117.310(a)(16) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 117.340(p)(3)	generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	§ 117.340(p)(2)(B) § 117.340(p)(2)(C) § 117.8000(b) § 117.8000(c) § 117.8000(c)(1) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d)		§ 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
SRU-F8C	EU	R7300-3144	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.8000(b) § 117.8000(c) § 117.8000(c)(2) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8120 § 117.8120(2) [G]§ 117.8120(2)(A) § 117.8120(2)(B)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
SRU-F8C	EU	60J-0029	SO_2	40 CFR Part 60, Subpart J	§ 60.104(a)(2)(i)	No owner or operator subject to the provisions of this subpart shall discharge or cause the discharge into the atmosphere from any Claus sulfur recovery plant with an oxidation control system any gases containing in excess of 250 ppm by volume of SO2 at zero percent excess air.	[G]§ 60.105(a)(5) § 60.106(a) [G]§ 60.106(f)	[G]§ 60.105(a)(5)	§ 60.105(e)(4)(i) § 60.107(d) § 60.107(f) § 60.107(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
SRU-F8D	EU	R7300-3144	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) [G]§ 117.310(a)(16) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C) § 117.8000(b) § 117.8000(c) § 117.8000(c)(1) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
SRU-F8D	EU	R7300-3144	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.8000(b) § 117.8000(c) § 117.8000(c)(2) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8120 § 117.8120(2) [G]§ 117.8120(2)(A) § 117.8120(2)(B)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
SRU-F8D	EU	60J-0029	SO_2	40 CFR Part 60, Subpart J	§ 60.104(a)(2)(i)	No owner or operator subject to the provisions of this subpart shall discharge or cause the discharge into the atmosphere from any Claus sulfur recovery plant with an oxidation control system any gases containing in excess of 250 ppm by volume of SO2 at zero percent excess air.	[G]§ 60.105(a)(5) § 60.106(a) [G]§ 60.106(f)	[G]§ 60.105(a)(5)	§ 60.105(e)(4)(i) § 60.107(d) § 60.107(f) § 60.107(g)
T1003	EU	R5112-0012	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
T1046PUMP	EU	R7300-0004	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(9)(E)(iv)(III) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) [G]§ 117.310(f) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a)(2)(C) § 117.340(h) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C) § 117.345(f)(3)(A) § 117.345(f)(3)(A)(ii) § 117.8000(b) § 117.8000(c) § 117.8000(c)(1) § 117.8000(c)(3)	§ 117.345(a) § 117.345(f) [G]§ 117.345(f)(10) § 117.345(f)(3) § 117.345(f)(3)(B) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8140(a) § 117.8140(a)(1) § 117.8140(a)(2) § 117.8140(a)(2)(A) [G]§ 117.8140(a)(2)(B) § 117.8140(b)		
T1046PUMP	EU	R7300-0004	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B)	CO emissions must not exceed 3.0 g/hp-hr for stationary internal combustion engines.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a)(2)(C) § 117.340(h) § 117.345(f)(3) § 117.345(f)(3)(A) § 117.345(f)(3)(A)(ii) § 117.8000(b) § 117.8000(c) § 117.8000(c)(2) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8120 § 117.8120(2) [G]§ 117.8120(2)(A) § 117.8120(2)(B) § 117.8140(a) § 117.8140(a)(1) § 117.8140(a)(2) § 117.8140(a)(2)(A) [G]§ 117.8140(a)(2)(B) § 117.8140(b)	§ 117.345(a) § 117.345(f) [G]§ 117.345(f)(10) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
T1046PUMP	EU	60IIII-0006	CO	40 CFR Part 60,	§ 60.4204(b)	Owners and operators of	§ 60.4209(b)	§ 60.4214(c)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Subpart IIII	§ 1039.102 § 60.4201(a) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) § 60.4218	non-emergency stationary CI ICE with a maximum engine power greater than or equal to 37 KW and less than 130 KW and a displacement of less than 10 liters per cylinder and is a 2007 model year and later must comply with a CO emission limit of 5.0 g/KW-hr as stated in 40 CFR 60.4201(a) and 40 CFR 89.112(a) and 40 CFR 1039.102 and 40 CFR 1039.101.			
T1046PUMP	EU	60IIII-0006	NMHC and NO_X	40 CFR Part 60, Subpart IIII	§ 60.4204(b) § 1039.102 § 60.4201(a) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) § 60.4218	Owners and operators of non-emergency stationary CI ICE with a maximum engine power greater than or equal to 37 KW but less than 56 KW and a displacement of less than 10 liters per cylinder and is a 2008 model year and later must comply with an NMHC+NOx emission limit of 4.7 g/KW-hr as stated in 40 CFR 60.4201(a) and 40 CFR 89.112(a) and 40 CFR 1039.102 and 40 CFR 1039.101.	§ 60.4209(b)	§ 60.4214(c)	None
T1046PUMP	EU	60IIII-0006	PM (Opacity)	40 CFR Part 60, Subpart IIII	§ 60.4204(b) § 1039.105(b)(1) § 1039.105(b)(2) § 1039.105(b)(3) § 60.4201(a) § 60.4206 § 60.4207(b)	Owners and operators of non-emergency stationary CI ICE with a displacement of less than 10 liters per cylinder and is not a constant-speed engine and is a 2007 model year and	§ 60.4209(b)	§ 60.4214(c)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 60.4211(a) § 60.4211(c) § 60.4218	later must comply with the following opacity emission limits: 20% during the acceleration mode, 15% during the lugging mode, and 50% during the peaks in either the acceleration or lugging modes as stated in 40 CFR 60.4201(a)-(c) and 40 CFR 89.113(a)(1)-(3) and 40 CFR 1039.105(b)(1)-(3).			
T1046PUMP	EU	60IIII-0006	PM	40 CFR Part 60, Subpart IIII	§ 60.4204(b) § 1039.102 § 60.4201(a) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) § 60.4218	Owners and operators of non-emergency stationary CI ICE with a maximum engine power greater than or equal to 19 KW and less than 56 KW and a displacement of less than 10 liters per cylinder and is a 2008 - 2012 model year must comply with a PM emission limit of 0.30 g/KW-hr as stated in 40 CFR 60.4201(a) and 40 CFR 1039.102.	§ 60.4209(b)	§ 60.4214(c)	None
T1046PUMP	EU	63ZZZZ-0002	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(c)	Stationary RICE subject to Regulations under 40 CFR Part 60. An affected source that meets any of the criteria in paragraphs (c)(1) through (7) of this section must meet the requirements of this part by meeting the requirements of 40 CFR part 60 subpart IIII, for compression ignition engines or 40 CFR part 60	None	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						subpart JJJJ, for spark ignition engines as applicable. No further requirements apply for such engines under this part.			
T1053APUMP	EU	R7300-0004	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(9)(E)(iv)(III) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) [G]§ 117.310(f) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a)(2)(C) § 117.340(h) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C) § 117.345(f)(3)(A) § 117.345(f)(3)(A)(ii) § 117.8000(b) § 117.8000(c) § 117.8000(c)(1) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8140(a) § 117.8140(a)(1) § 117.8140(a)(2) § 117.8140(a)(2)(A) [G]§ 117.8140(a)(2)(B) § 117.8140(b)	§ 117.345(a) § 117.345(f) [G]§ 117.345(f)(10) § 117.345(f)(3) § 117.345(f)(3)(B) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
T1053APUMP	EU	R7300-0004	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B)	CO emissions must not exceed 3.0 g/hp-hr for stationary internal combustion engines.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d)	§ 117.345(a) § 117.345(f) [G]§ 117.345(f)(10) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.335(e) § 117.335(g) § 117.340(a)(2)(C) § 117.340(h) § 117.345(f)(3) § 117.345(f)(3)(A) § 117.345(f)(3)(A)(ii) § 117.8000(b) § 117.8000(c) § 117.8000(c)(2) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8120 § 117.8120(2) [G]§ 117.8120(2)(A) § 117.8120(2)(B) § 117.8140(a) § 117.8140(a)(1) § 117.8140(a)(2) § 117.8140(a)(2)(A) [G]§ 117.8140(a)(2)(B) § 117.8140(b)		§ 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
T1053APUMP	EU	60IIII-0006	CO	40 CFR Part 60, Subpart IIII	§ 60.4204(b) § 1039.102 § 60.4201(a) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) § 60.4218	Owners and operators of non-emergency stationary CI ICE with a maximum engine power greater than or equal to 37 KW and less than 130 KW and a displacement of less than 10 liters per cylinder and is a 2007 model year and later must comply with a CO emission limit of 5.0 g/KW-hr as stated in 40 CFR 60.4201(a) and 40 CFR 89.112(a) and 40 CFR 1039.102 and 40 CFR	§ 60.4209(b)	§ 60.4214(c)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						1039.101.			
T1053APUMP	EU	60IIII-0006	NMHC and NO_X	40 CFR Part 60, Subpart IIII	§ 60.4204(b) § 1039.102 § 60.4201(a) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) § 60.4218	Owners and operators of non-emergency stationary CI ICE with a maximum engine power greater than or equal to 37 KW but less than 56 KW and a displacement of less than 10 liters per cylinder and is a 2008 model year and later must comply with an NMHC+NOx emission limit of 4.7 g/KW-hr as stated in 40 CFR 60.4201(a) and 40 CFR 89.112(a) and 40 CFR 1039.102 and 40 CFR 1039.101.	§ 60.4209(b)	§ 60.4214(c)	None
T1053APUMP	EU	60IIII-0006	PM (Opacity)	40 CFR Part 60, Subpart IIII	§ 60.4204(b) § 1039.105(b)(1) § 1039.105(b)(2) § 1039.105(b)(3) § 60.4201(a) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) § 60.4218	Owners and operators of non-emergency stationary CI ICE with a displacement of less than 10 liters per cylinder and is not a constant-speed engine and is a 2007 model year and later must comply with the following opacity emission limits: 20% during the acceleration mode, 15% during the lugging mode, and 50% during the peaks in either the acceleration or lugging modes as stated in 40 CFR 60.4201(a)-(c) and 40 CFR 89.113(a)(1)-(3) and 40 CFR 1039.105(b)(1)-(3).	§ 60.4209(b)	§ 60.4214(c)	None
T1053APUMP	EU	60IIII-0006	PM	40 CFR Part 60, Subpart IIII	§ 60.4204(b) § 1039.102	Owners and operators of non-emergency stationary	§ 60.4209(b)	§ 60.4214(c)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.4201(a) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) § 60.4218	CI ICE with a maximum engine power greater than or equal to 19 KW and less than 56 KW and a displacement of less than 10 liters per cylinder and is a 2008 - 2012 model year must comply with a PM emission limit of 0.30 g/KW-hr as stated in 40 CFR 60.4201(a) and 40 CFR 1039.102.			
T1053APUMP	EU	63ZZZZ-0002	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(c)	Stationary RICE subject to Regulations under 40 CFR Part 60. An affected source that meets any of the criteria in paragraphs (c)(1) through (7) of this section must meet the requirements of this part by meeting the requirements of 40 CFR part 60 subpart IIII, for compression ignition engines or 40 CFR part 60 subpart JJJJ, for spark ignition engines as applicable. No further requirements apply for such engines under this part.	None	None	None
T280-10	EU	R5112-0019	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(D) § 115.112(e)(2)(F) [G]§ 115.112(e)(2)(I) § 115.114(a)(1)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(1)(B) § 115.118(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.			
T280-10	EU	60Kb-0069	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(B) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) [G]§ 60.113b(a)(3) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(4)
T280-10	EU	63CC-0004	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC
T280-100	EU	R5112-0090	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.114(a)(2)(A) § 115.114(a)(4)(A)	requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.			
T280-100	EU	60Kb-0070	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)
T280-100	EU	63CC-0256	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC
T280-1004	EU	R5112-0012	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						1.5 psia is exempt from the requirements of this division.			
T280-1004	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2) § 63.640(n)(7)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
T280-1005	EU	R5112-0010	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T280-1005	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC
T280-101	EU	R5112-0019	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(D) § 115.112(e)(2)(F) [G]§ 115.112(e)(2)(I) § 115.114(a)(1)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(1)(B) § 115.118(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.			
T280-101	EU	63CC-0248	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC
T280-101	EU	63G-0001	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(d) § 63.110(b)(2) § 63.119(a)(1) [G]§ 63.119(b)(1) § 63.119(b)(2) § 63.119(b)(3)(iii) § 63.119(c)(2)(i) § 63.119(c)(2)(ii) § 63.119(c)(2)(iii) § 63.119(c)(2)(iv) § 63.119(c)(2)(ix) § 63.119(c)(2)(v) § 63.119(c)(2)(vi) § 63.119(c)(2)(vii) § 63.119(c)(2)(viii) § 63.119(c)(2)(x) § 63.119(c)(2)(xi) § 63.119(c)(2)(xii) § 63.120(a)(4) § 63.120(a)(7)	External floating roofs converted to an internal floating roof (i.e., fixed roof installed above external floating roof) to comply with §63.119(a)(1) shall comply with §63.119(d)(1)-(2).	§ 63.120(a)(3)(i) § 63.120(a)(3)(ii) § 63.120(a)(3)(iii)	§ 63.120(a)(4) § 63.123(a) § 63.123(e) § 63.123(g) [G]§ 63.152(a)	§ 63.120(a)(5) § 63.120(a)(6) § 63.122(d) § 63.122(d)(1)(ii) § 63.122(d)(1)(iii) § 63.122(d)(2)(ii) § 63.122(f) § 63.151(a)(7) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(4)(ii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T280-1010	EU	R5111	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T280-1018	EU	R5112-0012	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
T280-1018	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
T280-102	EU	R5112-0019	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(D) § 115.112(e)(2)(F) [G]§ 115.112(e)(2)(I) § 115.114(a)(1)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(1)(B) § 115.118(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						condensate.			
T280-102	EU	63CC-0081	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC
T280-102	EU	63G-0001	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(d) § 63.110(b)(1) § 63.110(b)(2) § 63.119(a)(1) [G]§ 63.119(b)(1) § 63.119(b)(2) § 63.119(b)(3)(iii) § 63.119(c)(2)(i) § 63.119(c)(2)(ii) § 63.119(c)(2)(iii) § 63.119(c)(2)(iv) § 63.119(c)(2)(ix) § 63.119(c)(2)(v) § 63.119(c)(2)(vi) § 63.119(c)(2)(vii) § 63.119(c)(2)(viii) § 63.119(c)(2)(x) § 63.119(c)(2)(xi) § 63.119(c)(2)(xii) § 63.120(a)(4) § 63.120(a)(7)	External floating roofs converted to an internal floating roof (i.e., fixed roof installed above external floating roof) to comply with §63.119(a)(1) shall comply with §63.119(d)(1)-(2).	§ 63.120(a)(3)(i) § 63.120(a)(3)(ii) § 63.120(a)(3)(iii)	§ 63.120(a)(4) § 63.123(a) § 63.123(e) § 63.123(g) [G]§ 63.152(a)	§ 63.120(a)(5) § 63.120(a)(6) § 63.122(d) § 63.122(d)(1)(ii) § 63.122(d)(1)(iii) § 63.122(d)(2)(ii) § 63.122(f) § 63.151(a)(7) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(4)(ii)
T280-1020	EU	R5112-0096	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all	§ 115.114(a)(2) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.			
T280-1020	EU	60Kb-0419	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)
T280-1020	EU	63CC-0256	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.119(a)(1) § 63.119(c)(1) § 63.119(c)(1)(i) § 63.119(c)(1)(ii) § 63.119(c)(1)(iii) [G]§ 63.119(c)(3) § 63.119(c)(4) § 63.120(b)(10)(i) § 63.120(b)(5)(i)	Each owner or operator of a Group 1 storage vessel subject to this subpart shall comply with the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.120(b)(1)(i) § 63.120(b)(1)(iii) § 63.120(b)(1)(iv) § 63.120(b)(10) § 63.120(b)(2)(i) § 63.120(b)(2)(ii) § 63.120(b)(2)(iii) § 63.120(b)(3) § 63.120(b)(4) § 63.646(b)(1)	[G]§ 63.120(b)(7) § 63.120(b)(8) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1) § 63.655(i)(5)	§ 63.120(b)(10)(ii) § 63.120(b)(10)(iii) § 63.120(b)(9) § 63.642(f) § 63.655(f) § 63.655(f)(1)(i) [G]§ 63.655(f)(1)(i)(A) § 63.655(f)(6) § 63.655(g) § 63.655(g)(1)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.120(b)(5)(ii) § 63.120(b)(6)(i) § 63.120(b)(6)(ii) [G]§ 63.120(b)(7) § 63.120(b)(8) [G]§ 63.646(f) § 63.646(g)		§ 63.646(b)(2) § 63.646(e)		[G]§ 63.655(g)(3) § 63.655(h) § 63.655(h)(1) § 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(B) § 63.655(h)(2)(i)(C) § 63.655(h)(2)(ii) [G]§ 63.655(h)(6)
T280-1021	EU	R5112-0096	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(2) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)
T280-1021	EU	60Kb-0419	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)		
T280-1021	EU	63CC-0131	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) [G]§ 60.112b(a)(2) § 63.640(n)(8)(i) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) [G]§ 63.120(b)(7) § 63.640(n)(8)(ii)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 63.640(n)(8)(vi)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)
T280-1023	EU	R5112-0096	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this	§ 115.114(a)(2) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						paragraph for crude oil and condensate.			
T280-1023	EU	63CC-0256	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.119(a)(1) § 63.119(c)(1) § 63.119(c)(1)(i) § 63.119(c)(1)(ii) § 63.119(c)(1)(iii) [G]§ 63.119(c)(3) § 63.119(c)(4) § 63.120(b)(10)(i) § 63.120(b)(5)(i) § 63.120(b)(5)(ii) § 63.120(b)(6)(i) § 63.120(b)(6)(ii) [G]§ 63.120(b)(7) § 63.120(b)(8) § 63.640(n)(5) [G]§ 63.646(f) § 63.646(g)	Each owner or operator of a Group 1 storage vessel subject to this subpart shall comply with the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.120(b)(1)(i) § 63.120(b)(1)(iii) § 63.120(b)(1)(iv) § 63.120(b)(10) § 63.120(b)(2)(i) § 63.120(b)(2)(ii) § 63.120(b)(2)(iii) § 63.120(b)(3) § 63.120(b)(4) § 63.646(b)(1) § 63.646(b)(2) § 63.646(e)	[G]§ 63.120(b)(7) § 63.120(b)(8) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1) § 63.655(i)(5)	§ 63.120(b)(10)(ii) § 63.120(b)(10)(iii) § 63.120(b)(9) § 63.642(f) § 63.655(f) § 63.655(f)(1)(i) [G]§ 63.655(f)(1)(i)(A) § 63.655(f)(6) § 63.655(g) § 63.655(g)(1) [G]§ 63.655(g)(3) § 63.655(h) § 63.655(h)(1) § 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(B) § 63.655(h)(2)(i)(C) § 63.655(h)(2)(ii) [G]§ 63.655(h)(6)
T280-1024	EU	R5112-0096	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(2) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T280-1024	EU	63CC-0256	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.119(a)(1) § 63.119(c)(1) § 63.119(c)(1)(i) § 63.119(c)(1)(ii) § 63.119(c)(1)(iii) [G]§ 63.119(c)(3) § 63.119(c)(4) § 63.120(b)(10)(i) § 63.120(b)(5)(i) § 63.120(b)(5)(ii) § 63.120(b)(6)(i) § 63.120(b)(6)(ii) [G]§ 63.120(b)(7) § 63.120(b)(8) [G]§ 63.646(f) § 63.646(g)	Each owner or operator of a Group 1 storage vessel subject to this subpart shall comply with the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.120(b)(1)(i) § 63.120(b)(1)(iii) § 63.120(b)(1)(iv) § 63.120(b)(10) § 63.120(b)(2)(i) § 63.120(b)(2)(ii) § 63.120(b)(2)(iii) § 63.120(b)(3) § 63.120(b)(4) § 63.646(b)(1) § 63.646(b)(2) § 63.646(e)	[G]§ 63.120(b)(7) § 63.120(b)(8) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1) § 63.655(i)(5)	§ 63.120(b)(10)(ii) § 63.120(b)(10)(iii) § 63.120(b)(9) § 63.642(f) § 63.655(f) § 63.655(f)(1)(i) [G]§ 63.655(f)(1)(i)(A) § 63.655(f)(6) § 63.655(g) § 63.655(g)(1) [G]§ 63.655(g)(3) § 63.655(h) § 63.655(h)(1) § 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(B) § 63.655(h)(2)(i)(C) § 63.655(h)(2)(ii) [G]§ 63.655(h)(6)
T280-1025	EU	R5112-0096	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(2) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)
T280-1025	EU	63CC-0256	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.119(a)(1)	Each owner or operator of a Group 1 storage vessel	§ 63.120(b)(1)(i) § 63.120(b)(1)(iii)	[G]§ 63.120(b)(7) § 63.120(b)(8)	§ 63.120(b)(10)(ii) § 63.120(b)(10)(iii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.119(c)(1) § 63.119(c)(1)(i) § 63.119(c)(1)(ii) § 63.119(c)(1)(iii) [G]§ 63.119(c)(3) § 63.119(c)(4) § 63.120(b)(10)(i) § 63.120(b)(5)(i) § 63.120(b)(5)(ii) § 63.120(b)(6)(i) § 63.120(b)(6)(ii) [G]§ 63.120(b)(7) § 63.120(b)(8) [G]§ 63.646(f) § 63.646(g)	subject to this subpart shall comply with the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.120(b)(1)(iv) § 63.120(b)(10) § 63.120(b)(2)(i) § 63.120(b)(2)(ii) § 63.120(b)(2)(iii) § 63.120(b)(3) § 63.120(b)(4) § 63.646(b)(1) § 63.646(b)(2) § 63.646(e)	§ 63.642(e) § 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1) § 63.655(i)(5)	§ 63.120(b)(9) § 63.642(f) § 63.655(f) § 63.655(f)(1)(i) [G]§ 63.655(f)(1)(i)(A) § 63.655(f)(6) § 63.655(g) § 63.655(g)(1) [G]§ 63.655(g)(3) § 63.655(h) § 63.655(h)(1) § 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(B) § 63.655(h)(2)(i)(C) § 63.655(h)(2)(ii) [G]§ 63.655(h)(6)
T280-103	EU	R5112-0090	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)
T280-103	EU	63CC-0059	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) [G]§ 60.112b(a)(2) § 63.640(n)(8)(i) § 63.640(n)(8)(ii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.640(n)(8)(iii)	provided for in §63.640(n)(8)(i)-(vi).	§ 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) [G]§ 63.120(b)(7) § 63.640(n)(8)(ii)	§ 60.116b(c) § 63.640(n)(8)(vi)	§ 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)
T280-1039	EU	R5112-0012	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
T280-1039	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
T280-104	EU	R5112-0090	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.			
T280-104	EU	63CC-0059	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) [G]§ 60.112b(a)(2) § 63.640(n)(8)(i) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) [G]§ 63.120(b)(7) § 63.640(n)(8)(ii)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 63.640(n)(8)(vi)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)
T280-1041	EU	R5112-0090	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.			
T280-1041	EU	60Kb-0070	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)
T280-1041	EU	63CC-0256	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.119(a)(1) § 63.119(c)(1) § 63.119(c)(1)(i) § 63.119(c)(1)(ii) § 63.119(c)(1)(iii) [G]§ 63.119(c)(3) § 63.119(c)(4) § 63.120(b)(10)(i) § 63.120(b)(5)(i) § 63.120(b)(5)(ii) § 63.120(b)(6)(i) § 63.120(b)(6)(ii) [G]§ 63.120(b)(7) § 63.120(b)(8) [G]§ 63.646(f)	Each owner or operator of a Group 1 storage vessel subject to this subpart shall comply with the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.120(b)(1)(i) § 63.120(b)(1)(iii) § 63.120(b)(1)(iv) § 63.120(b)(10) § 63.120(b)(2)(i) § 63.120(b)(2)(ii) § 63.120(b)(2)(iii) § 63.120(b)(3) § 63.120(b)(4) § 63.646(b)(1) § 63.646(b)(2) § 63.646(e)	[G]§ 63.120(b)(7) § 63.120(b)(8) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1) § 63.655(i)(5)	§ 63.120(b)(10)(ii) § 63.120(b)(10)(iii) § 63.120(b)(9) § 63.642(f) § 63.655(f) § 63.655(f)(1)(i) [G]§ 63.655(f)(1)(i)(A) § 63.655(f)(6) § 63.655(g) § 63.655(g)(1) [G]§ 63.655(g)(3) § 63.655(h) § 63.655(h)(1) § 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(B)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.646(g)				§ 63.655(h)(2)(i)(C) § 63.655(h)(2)(ii) [G]§ 63.655(h)(6)
T280-1042	EU	R5112-0090	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)
T280-1042	EU	63CC-0256	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.119(a)(1) § 63.119(c)(1) § 63.119(c)(1)(i) § 63.119(c)(1)(ii) § 63.119(c)(1)(iii) [G]§ 63.119(c)(3) § 63.119(c)(4) § 63.120(b)(10)(i) § 63.120(b)(5)(i) § 63.120(b)(5)(ii) § 63.120(b)(6)(i) § 63.120(b)(6)(ii) [G]§ 63.120(b)(7) § 63.120(b)(8) [G]§ 63.646(f) § 63.646(g)	Each owner or operator of a Group 1 storage vessel subject to this subpart shall comply with the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.120(b)(1)(i) § 63.120(b)(1)(iii) § 63.120(b)(1)(iv) § 63.120(b)(10) § 63.120(b)(2)(i) § 63.120(b)(2)(ii) § 63.120(b)(2)(iii) § 63.120(b)(3) § 63.120(b)(4) § 63.646(b)(1) § 63.646(b)(2) § 63.646(e)	[G]§ 63.120(b)(7) § 63.120(b)(8) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1) § 63.655(i)(5)	§ 63.120(b)(10)(ii) § 63.120(b)(10)(iii) § 63.120(b)(9) § 63.642(f) § 63.655(f) § 63.655(f)(1)(i) [G]§ 63.655(f)(1)(i)(A) § 63.655(f)(6) § 63.655(g) § 63.655(g)(1) [G]§ 63.655(g)(3) § 63.655(h) § 63.655(h)(1) § 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(B) § 63.655(h)(2)(i)(C) § 63.655(h)(2)(ii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
									[G]§ 63.655(h)(6)
T280-1044	EU	R5112-0090	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)
T280-1044	EU	63CC-0059	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) [G]§ 60.112b(a)(2) § 63.640(n)(8)(i) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) [G]§ 63.120(b)(7) § 63.640(n)(8)(ii)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 63.640(n)(8)(vi)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)
T280-1045	EU	R5112-0096	VOC	30 TAC Chapter 115, Storage of	§ 115.112(e)(1) § 115.112(e)(2)	No person shall place, store, or hold VOC in any	§ 115.114(a)(2) § 115.114(a)(4)	§ 115.118(a)(3) § 115.118(a)(5)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				VOCs	§ 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.118(a)(3)
T280-1045	EU	60Kb-0419	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)
T280-1045	EU	63CC-0131	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63,	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					specification requirements of 40 CFR Part 63, Subpart CC			Subpart CC	
T280-1046	EU	R5112-0096	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(2) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)
T280-1046	EU	61FF-0006	Benzene	40 CFR Part 61, Subpart FF	§ 61.351(a) [G]§ 60.112b(a)(2) § 61.351(a)(2) § 61.351(b)	As an alternative to the standards for tanks specified in § 61.343, an owner or operator may elect to comply with one of the following §61.351(a)(1)-(3):	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6)	§ 60.115b [G]§ 60.115b(b)(3) § 61.356(k)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 61.357(e) § 61.357(f)
T280-1046	EU	63CC-0131	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) [G]§ 60.112b(a)(2) § 63.640(n)(8)(i) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 63.640(n)(8)(vi)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) [G]§ 63.120(b)(7) § 63.640(n)(8)(ii)		§ 60.115b(b)(4) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)
T280-1047	EU	R5112-0096	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(2) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)
T280-1047	EU	63CC-0256	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.119(a)(1) § 63.119(c)(1) § 63.119(c)(1)(i) § 63.119(c)(1)(ii) § 63.119(c)(1)(iii) [G]§ 63.119(c)(3) § 63.119(c)(4) § 63.120(b)(10)(i)	Each owner or operator of a Group 1 storage vessel subject to this subpart shall comply with the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.120(b)(1)(i) § 63.120(b)(1)(iii) § 63.120(b)(1)(iv) § 63.120(b)(10) § 63.120(b)(2)(i) § 63.120(b)(2)(ii) § 63.120(b)(2)(iii) § 63.120(b)(3) § 63.120(b)(4)	[G]§ 63.120(b)(7) § 63.120(b)(8) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1) § 63.655(i)(5)	§ 63.120(b)(10)(ii) § 63.120(b)(10)(iii) § 63.120(b)(9) § 63.642(f) § 63.655(f) § 63.655(f)(1)(i) [G]§ 63.655(f)(1)(i)(A) § 63.655(f)(6) § 63.655(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.120(b)(5)(i) § 63.120(b)(5)(ii) § 63.120(b)(6)(i) § 63.120(b)(6)(ii) [G]§ 63.120(b)(7) § 63.120(b)(8) [G]§ 63.646(f) § 63.646(g)		§ 63.646(b)(1) § 63.646(b)(2) § 63.646(e)		§ 63.655(g)(1) [G]§ 63.655(g)(3) § 63.655(h) § 63.655(h)(1) § 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(B) § 63.655(h)(2)(i)(C) § 63.655(h)(2)(ii) [G]§ 63.655(h)(6)
T280-1048	EU	R5112-0096	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(2) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)
T280-1048	EU	61FF-0006	Benzene	40 CFR Part 61, Subpart FF	§ 61.351(a) [G]§ 60.112b(a)(2) § 61.351(a)(2) § 61.351(b)	As an alternative to the standards for tanks specified in § 61.343, an owner or operator may elect to comply with one of the following §61.351(a)(1)-(3):	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6)	§ 60.115b [G]§ 60.115b(b)(3) § 61.356(k)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 61.357(e) § 61.357(f)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T280-1048	EU	63CC-0071	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) [G]§ 60.112b(a)(2) § 63.640(n)(8)(i) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(e)(1) [G]§ 60.116b(e)(3) § 60.116b(f)(1) [G]§ 63.120(b)(7) § 63.640(n)(8)(ii)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 63.640(n)(8)(vi)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)
T280-105	EU	R5112-0090	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)
T280-105	EU	61FF-0006	Benzene	40 CFR Part 61, Subpart FF	§ 61.351(a) [G]§ 60.112b(a)(2) § 61.351(a)(2)	As an alternative to the standards for tanks specified in § 61.343, an	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3)	§ 60.115b [G]§ 60.115b(b)(3) § 61.356(k)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 61.351(b)	owner or operator may elect to comply with one of the following §61.351(a)(1)-(3):	§ 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6)		§ 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 61.357(e) § 61.357(f)
T280-105	EU	63CC-0059	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) [G]§ 60.112b(a)(2) § 63.640(n)(8)(i) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) [G]§ 63.120(b)(7) § 63.640(n)(8)(ii)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 63.640(n)(8)(vi)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)
T280-1051	EU	R5112-0096	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for	§ 115.114(a)(2) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.			
T280-1051	EU	60Kb-0419	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)
T280-1051	EU	63CC-0256	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.119(a)(1) § 63.119(c)(1) § 63.119(c)(1)(i) § 63.119(c)(1)(ii) § 63.119(c)(1)(iii) [G]§ 63.119(c)(3) § 63.119(c)(4) § 63.120(b)(10)(i) § 63.120(b)(5)(i) § 63.120(b)(5)(ii) § 63.120(b)(6)(i) § 63.120(b)(6)(ii) [G]§ 63.120(b)(7) § 63.120(b)(8) § 63.640(n)(5)	Each owner or operator of a Group 1 storage vessel subject to this subpart shall comply with the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.120(b)(1)(i) § 63.120(b)(1)(iii) § 63.120(b)(1)(iv) § 63.120(b)(10) § 63.120(b)(2)(i) § 63.120(b)(2)(ii) § 63.120(b)(2)(iii) § 63.120(b)(3) § 63.120(b)(4) § 63.646(b)(1) § 63.646(b)(2) § 63.646(e)	[G]§ 63.120(b)(7) § 63.120(b)(8) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1) § 63.655(i)(5)	§ 63.120(b)(10)(ii) § 63.120(b)(10)(iii) § 63.120(b)(9) § 63.642(f) § 63.655(f) § 63.655(f)(1)(i) [G]§ 63.655(f)(1)(i)(A) § 63.655(f)(6) § 63.655(g) § 63.655(g)(1) [G]§ 63.655(g)(3) § 63.655(h) § 63.655(h)(1) § 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(B)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 63.646(f) § 63.646(g)				§ 63.655(h)(2)(i)(C) § 63.655(h)(2)(ii) [G]§ 63.655(h)(6)
T280-1052	EU	R5112-0096	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(2) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)
T280-1052	EU	60Kb-0419	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)
T280-1052	EU	63CC-	112(B)	40 CFR Part 63,	§ 63.646(a)	Each owner or operator of a	§ 63.120(b)(1)(i)	[G]§ 63.120(b)(7)	§ 63.120(b)(10)(ii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		0256	HAPS	Subpart CC	§ 63.119(a)(1) § 63.119(c)(1) § 63.119(c)(1)(i) § 63.119(c)(1)(ii) § 63.119(c)(1)(iii) [G]§ 63.119(c)(3) § 63.119(c)(4) § 63.120(b)(10)(i) § 63.120(b)(5)(i) § 63.120(b)(5)(ii) § 63.120(b)(6)(i) § 63.120(b)(6)(ii) [G]§ 63.120(b)(7) § 63.120(b)(8) § 63.640(n)(5) [G]§ 63.646(f) § 63.646(g)	Group 1 storage vessel subject to this subpart shall comply with the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.120(b)(1)(iii) § 63.120(b)(1)(iv) § 63.120(b)(10) § 63.120(b)(2)(i) § 63.120(b)(2)(ii) § 63.120(b)(2)(iii) § 63.120(b)(3) § 63.120(b)(4) § 63.646(b)(1) § 63.646(b)(2) § 63.646(e)	§ 63.120(b)(8) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1) § 63.655(i)(5)	§ 63.120(b)(10)(iii) § 63.120(b)(9) § 63.642(f) § 63.655(f) § 63.655(f)(1)(i) [G]§ 63.655(f)(1)(i)(A) § 63.655(f)(6) § 63.655(g) § 63.655(g)(1) [G]§ 63.655(g)(3) § 63.655(h) § 63.655(h)(1) § 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(B) § 63.655(h)(2)(i)(C) § 63.655(h)(2)(ii) [G]§ 63.655(h)(6)
T280-1053	EU	R5112-0096	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(2) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)
T280-1053	EU	63CC-0131	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) [G]§ 60.112b(a)(2) § 63.640(n)(8)(i)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	§ 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) [G]§ 63.120(b)(7) § 63.640(n)(8)(ii)	§ 60.116b(b) § 60.116b(c) § 63.640(n)(8)(vi)	§ 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)
T280-1054	EU	R5112-0090	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)
T280-1054	EU	R5131-0005	VOC	30 TAC Chapter 115, Water Separation	§ 115.132(a)(2)	VOC water separator compartments must have a floating roof or internal-floating cover resting on the surface with closure seals. Gauging and sampling	[G]§ 115.135(a) § 115.136(a)(3) § 115.136(a)(4) ** See Periodic Monitoring Summary	§ 115.136(a)(3) § 115.136(a)(4)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						devices shall be vapor-tight except during use.			
T280-1054	EU	60KB-0124	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3) § 60.116b(f)(1)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)
T280-1054	EU	61FF-0006	Benzene	40 CFR Part 61, Subpart FF	§ 61.351(a) [G]§ 60.112b(a)(2) § 61.351(a)(2) § 61.351(b)	As an alternative to the standards for tanks specified in § 61.343, an owner or operator may elect to comply with one of the following §61.351(a)(1)-(3):	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6)	§ 60.115b [G]§ 60.115b(b)(3) § 61.356(k)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 61.357(e) § 61.357(f)
T280-1054	EU	61FF-1003	Benzene	40 CFR Part 61, Subpart FF	§ 61.352(a) § 61.352(a)(1) § 61.352(c)	As an alternative to the standards for oil-water separators specified in §61.347, an owner or operator may elect to comply with one of the following: §61.352(a)(1)-(2)	None	[G]§ 61.356(l)	§ 61.357(e) § 61.357(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T280-1054	EU	63CC-0071	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC
T280-1055	EU	R5112-0096	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(2) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)
T280-1055	EU	63CC-0131	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) [G]§ 60.112b(a)(2) § 63.640(n)(8)(i) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 63.640(n)(8)(vi)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) [G]§ 63.120(b)(7) § 63.640(n)(8)(ii)		
T280-1056	EU	R5112-0090	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)
T280-1056	EU	R5131-0005	VOC	30 TAC Chapter 115, Water Separation	§ 115.132(a)(2)	VOC water separator compartments must have a floating roof or internal-floating cover resting on the surface with closure seals. Gauging and sampling devices shall be vapor-tight except during use.	[G]§ 115.135(a) § 115.136(a)(3) § 115.136(a)(4) ** See Periodic Monitoring Summary	§ 115.136(a)(3) § 115.136(a)(4)	None
T280-1056	EU	60KB-0124	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						§60.112b(a)(2)(i)-(iii).	§ 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3) § 60.116b(f)(1)		§ 60.115b(b)(4)
T280-1056	EU	61FF-0006	Benzene	40 CFR Part 61, Subpart FF	§ 61.351(a) [G]§ 60.112b(a)(2) § 61.351(a)(2) § 61.351(b)	As an alternative to the standards for tanks specified in § 61.343, an owner or operator may elect to comply with one of the following §61.351(a)(1)-(3):	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6)	§ 60.115b [G]§ 60.115b(b)(3) § 61.356(k)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 61.357(e) § 61.357(f)
T280-1056	EU	61FF-1003	Benzene	40 CFR Part 61, Subpart FF	§ 61.352(a) § 61.352(a)(1) § 61.352(c)	As an alternative to the standards for oil-water separators specified in §61.347, an owner or operator may elect to comply with one of the following: §61.352(a)(1)-(2)	None	[G]§ 61.356(l)	§ 61.357(e) § 61.357(g)
T280-1056	EU	63CC-0071	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					CC				
T280-1057	EU	R5112-0090	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)
T280-1057	EU	R5131-0005	VOC	30 TAC Chapter 115, Water Separation	§ 115.132(a)(2)	VOC water separator compartments must have a floating roof or internal-floating cover resting on the surface with closure seals. Gauging and sampling devices shall be vapor-tight except during use.	[G]§ 115.135(a) § 115.136(a)(3) § 115.136(a)(4) ** See Periodic Monitoring Summary	§ 115.136(a)(3) § 115.136(a)(4)	None
T280-1057	EU	61FF-0006	Benzene	40 CFR Part 61, Subpart FF	§ 61.351(a) [G]§ 60.112b(a)(2) § 61.351(a)(2) § 61.351(b)	As an alternative to the standards for tanks specified in § 61.343, an owner or operator may elect to comply with one of the following §61.351(a)(1)-(3):	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6)	§ 60.115b [G]§ 60.115b(b)(3) § 61.356(k)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 61.357(e) § 61.357(f)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T280-1057	EU	61FF-1003	Benzene	40 CFR Part 61, Subpart FF	§ 61.352(a) § 61.352(a)(1) § 61.352(c)	As an alternative to the standards for oil-water separators specified in §61.347, an owner or operator may elect to comply with one of the following: §61.352(a)(1)-(2)	None	[G]§ 61.356(l)	§ 61.357(e) § 61.357(g)
T280-1057	EU	63CC-0071	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC
T280-1058	EU	R5112-0010	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T280-1058	EU	R5131-005	VOC	30 TAC Chapter 115, Water Separation	§ 115.132(a)(2)	VOC water separator compartments must have a floating roof or internal-floating cover resting on the surface with closure seals. Gauging and sampling devices shall be vapor-tight except during use.	[G]§ 115.135(a) § 115.136(a)(3) § 115.136(a)(4) ** See Periodic Monitoring Summary	§ 115.136(a)(3) § 115.136(a)(4)	None
T280-1058	EU	60Kb-001	VOC	40 CFR Part 60, Subpart Kb	§ 60.110b(a)	Except for §60.110b(b), this subpart applies to vessels with a capacity greater than or equal to 75 cubic meters (19,800 gal) used to store	§ 60.116b(a) § 60.116b(b) § 60.116b(d) § 60.116b(f)(2)	§ 60.116b(a) § 60.116b(b)	§ 60.116b(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						VOLs for which construction/reconstruction/ modification began after 7/23/84.			
T280-1058	EU	61FF-001	Benzene	40 CFR Part 61, Subpart FF	§ 61.351(a) [G]§ 60.112b(a)(2) § 61.351(a)(2) § 61.351(b)	As an alternative to the standards for tanks specified in § 61.343, an owner or operator may elect to comply with one of the following §61.351(a)(1)-(3):	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6)	§ 60.115b [G]§ 60.115b(b)(3) § 61.356(k)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 61.357(e) § 61.357(f)
T280-1058	EU	61FF-1003	Benzene	40 CFR Part 61, Subpart FF	§ 61.352(a) § 61.352(a)(1) § 61.352(c)	As an alternative to the standards for oil-water separators specified in §61.347, an owner or operator may elect to comply with one of the following: §61.352(a)(1)-(2)	None	[G]§ 61.356(l)	§ 61.357(e) § 61.357(g)
T280-1058	EU	63CC-0071	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC
T280-106	EU	R5112-0090	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.			
T280-106	EU	60Kb-0070	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)
T280-106	EU	61FF-0006	Benzene	40 CFR Part 61, Subpart FF	§ 61.351(a) [G]§ 60.112b(a)(2) § 61.351(a)(2) § 61.351(b)	As an alternative to the standards for tanks specified in § 61.343, an owner or operator may elect to comply with one of the following §61.351(a)(1)-(3):	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii)	§ 60.115b [G]§ 60.115b(b)(3) § 61.356(k)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 61.357(e) § 61.357(f)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 60.113b(b)(5) [G]§ 60.113b(b)(6)		
T280-106	EU	63CC-0059	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC
T280-107	EU	R5112-0019	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(D) § 115.112(e)(2)(F) [G]§ 115.112(e)(2)(I) § 115.114(a)(1)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(1)(B) § 115.118(a)(3)
T280-107	EU	63CC-0081	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					CC				
T280-107	EU	63G-0001	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(d) § 63.110(b)(1) § 63.110(b)(2) § 63.119(a)(1) [G]§ 63.119(b)(1) § 63.119(b)(2) § 63.119(b)(3)(iii) § 63.119(c)(2)(i) § 63.119(c)(2)(ii) § 63.119(c)(2)(iii) § 63.119(c)(2)(iv) § 63.119(c)(2)(ix) § 63.119(c)(2)(v) § 63.119(c)(2)(vi) § 63.119(c)(2)(vii) § 63.119(c)(2)(viii) § 63.119(c)(2)(x) § 63.119(c)(2)(xi) § 63.119(c)(2)(xii) § 63.120(a)(4) § 63.120(a)(7)	External floating roofs converted to an internal floating roof (i.e., fixed roof installed above external floating roof) to comply with §63.119(a)(1) shall comply with §63.119(d)(1)-(2).	§ 63.120(a)(3)(i) § 63.120(a)(3)(ii) § 63.120(a)(3)(iii)	§ 63.120(a)(4) § 63.123(a) § 63.123(e) § 63.123(g) [G]§ 63.152(a)	§ 63.120(a)(5) § 63.120(a)(6) § 63.122(d) § 63.122(d)(1)(ii) § 63.122(d)(1)(iii) § 63.122(d)(2)(ii) § 63.122(f) § 63.151(a)(7) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(4)(ii)
T280-108	EU	R5112-0019	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(D) § 115.112(e)(2)(F) [G]§ 115.112(e)(2)(I) § 115.114(a)(1)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(1)(B) § 115.118(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						condensate.			
T280-108	EU	63CC-0081	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC
T280-108	EU	63G-0001	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(d) § 63.110(b)(1) § 63.110(b)(2) § 63.119(a)(1) [G]§ 63.119(b)(1) § 63.119(b)(2) § 63.119(b)(3)(iii) § 63.119(c)(2)(i) § 63.119(c)(2)(ii) § 63.119(c)(2)(iii) § 63.119(c)(2)(iv) § 63.119(c)(2)(ix) § 63.119(c)(2)(v) § 63.119(c)(2)(vi) § 63.119(c)(2)(vii) § 63.119(c)(2)(viii) § 63.119(c)(2)(x) § 63.119(c)(2)(xi) § 63.119(c)(2)(xii) § 63.120(a)(4) § 63.120(a)(7)	External floating roofs converted to an internal floating roof (i.e., fixed roof installed above external floating roof) to comply with §63.119(a)(1) shall comply with §63.119(d)(1)-(2).	§ 63.120(a)(3)(i) § 63.120(a)(3)(ii) § 63.120(a)(3)(iii)	§ 63.120(a)(4) § 63.123(a) § 63.123(e) § 63.123(g) [G]§ 63.152(a)	§ 63.120(a)(5) § 63.120(a)(6) § 63.122(d) § 63.122(d)(1)(ii) § 63.122(d)(1)(iii) § 63.122(d)(2)(ii) § 63.122(f) § 63.151(a)(7) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(4)(ii)
T280-11	EU	R5112-0090	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.			
T280-11	EU	60Kb-0070	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)
T280-11	EU	63CC-0256	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.119(a)(1) § 63.119(c)(1) § 63.119(c)(1)(i) § 63.119(c)(1)(ii) § 63.119(c)(1)(iii) [G]§ 63.119(c)(3) § 63.119(c)(4) § 63.120(b)(10)(i) § 63.120(b)(5)(i)	Each owner or operator of a Group 1 storage vessel subject to this subpart shall comply with the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.120(b)(1)(i) § 63.120(b)(1)(iii) § 63.120(b)(1)(iv) § 63.120(b)(10) § 63.120(b)(2)(i) § 63.120(b)(2)(ii) § 63.120(b)(2)(iii) § 63.120(b)(3) § 63.120(b)(4) § 63.646(b)(1)	[G]§ 63.120(b)(7) § 63.120(b)(8) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1) § 63.655(i)(5)	§ 63.120(b)(10)(ii) § 63.120(b)(10)(iii) § 63.120(b)(9) § 63.642(f) § 63.655(f) § 63.655(f)(1)(i) [G]§ 63.655(f)(1)(i)(A) § 63.655(f)(6) § 63.655(g) § 63.655(g)(1)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.120(b)(5)(ii) § 63.120(b)(6)(i) § 63.120(b)(6)(ii) [G]§ 63.120(b)(7) § 63.120(b)(8) [G]§ 63.646(f) § 63.646(g)		§ 63.646(b)(2) § 63.646(e)		[G]§ 63.655(g)(3) § 63.655(h) § 63.655(h)(1) § 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(B) § 63.655(h)(2)(i)(C) § 63.655(h)(2)(ii) [G]§ 63.655(h)(6)
T280-110	EU	R5112-0019	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(D) § 115.112(e)(2)(F) [G]§ 115.112(e)(2)(I) § 115.114(a)(1)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(1)(B) § 115.118(a)(3)
T280-110	EU	60Kb-0026	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(B) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) [G]§ 60.113b(a)(3) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(4)
T280-110	EU	63CC-0004	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall	The permit holder shall comply with the applicable	The permit holder shall comply with the	The permit holder shall comply with	The permit holder shall comply with the

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	requirements of 40 CFR Part 63, Subpart CC	applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	applicable reporting requirements of 40 CFR Part 63, Subpart CC
T280-112	EU	R5112-0019	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(D) § 115.112(e)(2)(F) [G]§ 115.112(e)(2)(I) § 115.114(a)(1)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(1)(B) § 115.118(a)(3)
T280-112	EU	63CC-0081	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC
T280-112	EU	63G-0001	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(d) § 63.110(b)(1) § 63.110(b)(2)	External floating roofs converted to an internal floating roof (i.e., fixed roof	§ 63.120(a)(3)(i) § 63.120(a)(3)(ii) § 63.120(a)(3)(iii)	§ 63.120(a)(4) § 63.123(a) § 63.123(e)	§ 63.120(a)(5) § 63.120(a)(6) § 63.122(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.119(a)(1) [G]§ 63.119(b)(1) § 63.119(b)(2) § 63.119(b)(3)(iii) § 63.119(c)(2)(i) § 63.119(c)(2)(ii) § 63.119(c)(2)(iii) § 63.119(c)(2)(iv) § 63.119(c)(2)(ix) § 63.119(c)(2)(v) § 63.119(c)(2)(vi) § 63.119(c)(2)(vii) § 63.119(c)(2)(viii) § 63.119(c)(2)(x) § 63.119(c)(2)(xi) § 63.119(c)(2)(xii) § 63.120(a)(4) § 63.120(a)(7)	installed above external floating roof) to comply with §63.119(a)(1) shall comply with §63.119(d)(1)-(2).		§ 63.123(g) [G]§ 63.152(a)	§ 63.122(d)(1)(ii) § 63.122(d)(1)(iii) § 63.122(d)(2)(ii) § 63.122(f) § 63.151(a)(7) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(4)(ii)
T280-114	EU	R5112-0019	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(D) § 115.112(e)(2)(F) [G]§ 115.112(e)(2)(I) § 115.114(a)(1)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(1)(B) § 115.118(a)(3)
T280-114	EU	63CC-0081	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the	The permit holder shall comply with the applicable requirements of 40 CFR	The permit holder shall comply with the applicable monitoring	The permit holder shall comply with the applicable	The permit holder shall comply with the applicable reporting

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	Part 63, Subpart CC	and testing requirements of 40 CFR Part 63, Subpart CC	recordkeeping requirements of 40 CFR Part 63, Subpart CC	requirements of 40 CFR Part 63, Subpart CC
T280-114	EU	63G-0001	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(d) § 63.110(b)(1) § 63.110(b)(2) § 63.119(a)(1) [G]§ 63.119(b)(1) § 63.119(b)(2) § 63.119(b)(3)(iii) § 63.119(c)(2)(i) § 63.119(c)(2)(ii) § 63.119(c)(2)(iii) § 63.119(c)(2)(iv) § 63.119(c)(2)(ix) § 63.119(c)(2)(v) § 63.119(c)(2)(vi) § 63.119(c)(2)(vii) § 63.119(c)(2)(viii) § 63.119(c)(2)(x) § 63.119(c)(2)(xi) § 63.119(c)(2)(xii) § 63.120(a)(4) § 63.120(a)(7)	External floating roofs converted to an internal floating roof (i.e., fixed roof installed above external floating roof) to comply with §63.119(a)(1) shall comply with §63.119(d)(1)-(2).	§ 63.120(a)(3)(i) § 63.120(a)(3)(ii) § 63.120(a)(3)(iii)	§ 63.120(a)(4) § 63.123(a) § 63.123(e) § 63.123(g) [G]§ 63.152(a)	§ 63.120(a)(5) § 63.120(a)(6) § 63.122(d) § 63.122(d)(1)(ii) § 63.122(d)(1)(iii) § 63.122(d)(2)(ii) § 63.122(f) § 63.151(a)(7) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(4)(ii)
T280-115	EU	R5112-0019	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(D) § 115.112(e)(2)(F) [G]§ 115.112(e)(2)(I) § 115.114(a)(1)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(1)(B) § 115.118(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.			
T280-115	EU	63CC-0248	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC
T280-115	EU	63G-0001	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(d) § 63.110(b)(2) § 63.119(a)(1) [G]§ 63.119(b)(1) § 63.119(b)(2) § 63.119(b)(3)(iii) § 63.119(c)(2)(i) § 63.119(c)(2)(ii) § 63.119(c)(2)(iii) § 63.119(c)(2)(iv) § 63.119(c)(2)(ix) § 63.119(c)(2)(v) § 63.119(c)(2)(vi) § 63.119(c)(2)(vii) § 63.119(c)(2)(viii) § 63.119(c)(2)(x) § 63.119(c)(2)(xi) § 63.119(c)(2)(xii) § 63.120(a)(4) § 63.120(a)(7)	External floating roofs converted to an internal floating roof (i.e., fixed roof installed above external floating roof) to comply with §63.119(a)(1) shall comply with §63.119(d)(1)-(2).	§ 63.120(a)(3)(i) § 63.120(a)(3)(ii) § 63.120(a)(3)(iii)	§ 63.120(a)(4) § 63.123(a) § 63.123(e) § 63.123(g) [G]§ 63.152(a)	§ 63.120(a)(5) § 63.120(a)(6) § 63.122(d) § 63.122(d)(1)(ii) § 63.122(d)(1)(iii) § 63.122(d)(2)(ii) § 63.122(f) § 63.151(a)(7) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(4)(ii)
T280-116	EU	R5112-	VOC	30 TAC Chapter	§ 115.112(e)(1)	No person shall place,	§ 115.114(a)(1)	§ 115.118(a)(3)	§ 115.114(a)(1)(B)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		0019		115, Storage of VOCs	§ 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(D) § 115.112(e)(2)(F) [G]§ 115.112(e)(2)(I) § 115.114(a)(1)(A)	store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.118(a)(3)
T280-116	EU	63CC-0081	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC
T280-116	EU	63G-0001	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(d) § 63.110(b)(1) § 63.110(b)(2) § 63.119(a)(1) [G]§ 63.119(b)(1) § 63.119(b)(2) § 63.119(b)(3)(iii) § 63.119(c)(2)(i) § 63.119(c)(2)(ii) § 63.119(c)(2)(iii) § 63.119(c)(2)(iv) § 63.119(c)(2)(ix)	External floating roofs converted to an internal floating roof (i.e., fixed roof installed above external floating roof) to comply with §63.119(a)(1) shall comply with §63.119(d)(1)-(2).	§ 63.120(a)(3)(i) § 63.120(a)(3)(ii) § 63.120(a)(3)(iii)	§ 63.120(a)(4) § 63.123(a) § 63.123(e) § 63.123(g) [G]§ 63.152(a)	§ 63.120(a)(5) § 63.120(a)(6) § 63.122(d) § 63.122(d)(1)(ii) § 63.122(d)(1)(iii) § 63.122(d)(2)(ii) § 63.122(f) § 63.151(a)(7) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.119(c)(2)(v) § 63.119(c)(2)(vi) § 63.119(c)(2)(vii) § 63.119(c)(2)(viii) § 63.119(c)(2)(x) § 63.119(c)(2)(xi) § 63.119(c)(2)(xii) § 63.120(a)(4) § 63.120(a)(7)				[G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(4)(ii)
T280-117	EU	R5112-0019	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(D) § 115.112(e)(2)(F) [G]§ 115.112(e)(2)(I) § 115.114(a)(1)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(1)(B) § 115.118(a)(3)
T280-117	EU	60Kb-0068	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(B) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) [G]§ 60.113b(a)(3) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(4)
T280-117	EU	61FF-0005	Benzene	40 CFR Part 61, Subpart FF	§ 61.351(a) § 60.112b(a)(1)	As an alternative to the standards for tanks	§ 60.113b(a)(1) § 60.113b(a)(2)	§ 60.115b § 60.115b(a)(2)	§ 60.113b(a)(2) § 60.113b(a)(5)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii) § 61.351(a)(1) § 61.351(b)	specified in § 61.343, an owner or operator may elect to comply with one of the following §61.351(a)(1)-(3):	§ 60.113b(a)(4) § 60.113b(a)(5)	§ 61.356(k)	§ 60.115b § 60.115b(a)(1) § 60.115b(a)(3) § 61.357(e) § 61.357(f)
T280-117	EU	63CC-0081	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC
T280-118	EU	R5112-0019	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(D) § 115.112(e)(2)(F) [G]§ 115.112(e)(2)(I) § 115.114(a)(1)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(1)(B) § 115.118(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T280-118	EU	60Kb-0068	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(B) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) [G]§ 60.113b(a)(3) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(4)
T280-118	EU	61FF-0005	Benzene	40 CFR Part 61, Subpart FF	§ 61.351(a) § 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii) § 61.351(a)(1) § 61.351(b)	As an alternative to the standards for tanks specified in § 61.343, an owner or operator may elect to comply with one of the following §61.351(a)(1)-(3):	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5)	§ 60.115b § 60.115b(a)(2) § 61.356(k)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3) § 61.357(e) § 61.357(f)
T280-118	EU	63CC-0081	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC
T280-128	EU	R5112-0012	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						requirements of this division.			
T280-128	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
T280-129	EU	R5112-0012	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
T280-129	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
T280-12A	EU	R115-0019	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(D) § 115.112(e)(2)(F) [G]§ 115.112(e)(2)(I) § 115.114(a)(1)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(1)(B) § 115.118(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.			
T280-12A	EU	60Kb-0026	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(B) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) [G]§ 60.113b(a)(3) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(4)
T280-12A	EU	63CC	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC
T280-13	EU	R5112-0090	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.			
T280-13	EU	63CC-0059	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) [G]§ 60.112b(a)(2) § 63.640(n)(8)(i) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) [G]§ 63.120(b)(7) § 63.640(n)(8)(ii)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 63.640(n)(8)(vi)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)
T280-130	EU	R5112-0012	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
T280-130	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T280-132	EU	R5112-0132	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(3) § 115.112(e)(3)(C) § 60.18	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.115(a) § 115.115(a)(6) § 115.116(a)(2) [G]§ 115.117	§ 115.118(a)(4) § 115.118(a)(4)(F) § 115.118(a)(5) § 115.118(a)(7)	None
T280-132	EU	60KB-0072	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(3) § 60.18 § 63.640(n)(1)	Storage vessels specified in §60.112b(a) and equipped with a closed vent system/control device are to meet the specifications of §60.112b(a)(3)(i)-(ii).	§ 60.113b(d) § 60.116b(a) § 60.116b(b) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3) [G]§ 60.485(b) ** See Periodic Monitoring Summary	§ 60.115b § 60.115b(d)(2) § 60.116b(a) § 60.116b(b)	§ 60.115b § 60.115b(d)(1) § 60.115b(d)(3)
T280-132	EU	61FF-0009	Benzene	40 CFR Part 61, Subpart FF	§ 61.343(a)(1) § 61.340(d) § 61.343(a)(1)(i)(A) § 61.343(a)(1)(i)(B) § 61.343(c) § 61.343(d)	The owner or operator shall install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the tank to a control device.	§ 61.343(a)(1)(i)(A) § 61.343(c)	§ 61.356(d) § 61.356(g)	None
T280-133	EU	R5112-0132	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(3) § 115.112(e)(3)(C) § 60.18	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working	§ 115.115(a) § 115.115(a)(6) § 115.116(a)(2) [G]§ 115.117	§ 115.118(a)(4) § 115.118(a)(4)(F) § 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.			
T280-133	EU	60KB-0072	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(3) § 60.18 § 63.640(n)(1)	Storage vessels specified in §60.112b(a) and equipped with a closed vent system/control device are to meet the specifications of §60.112b(a)(3)(i)-(ii).	§ 60.113b(d) § 60.116b(a) § 60.116b(b) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3) [G]§ 60.485(b) ** See Periodic Monitoring Summary	§ 60.115b § 60.115b(d)(2) § 60.116b(a) § 60.116b(b)	§ 60.115b § 60.115b(d)(1) § 60.115b(d)(3)
T280-133	EU	61FF-0009	Benzene	40 CFR Part 61, Subpart FF	§ 61.343(a)(1) § 61.340(d) § 61.343(a)(1)(i)(A) § 61.343(a)(1)(i)(B) § 61.343(c) § 61.343(d)	The owner or operator shall install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the tank to a control device.	§ 61.343(a)(1)(i)(A) § 61.343(c)	§ 61.356(d) § 61.356(g)	None
T280-134	EU	R5112-0132	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(3) § 115.112(e)(3)(C) § 60.18	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control	§ 115.115(a) § 115.115(a)(6) § 115.116(a)(2) [G]§ 115.117	§ 115.118(a)(4) § 115.118(a)(4)(F) § 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.			
T280-134	EU	60KB-0072	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(3) § 60.18 § 63.640(n)(1)	Storage vessels specified in §60.112b(a) and equipped with a closed vent system/control device are to meet the specifications of §60.112b(a)(3)(i)-(ii).	§ 60.113b(d) § 60.116b(a) § 60.116b(b) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3) [G]§ 60.485(b) ** See Periodic Monitoring Summary	§ 60.115b § 60.115b(d)(2) § 60.116b(a) § 60.116b(b)	§ 60.115b § 60.115b(d)(1) § 60.115b(d)(3)
T280-134	EU	61FF-0009	Benzene	40 CFR Part 61, Subpart FF	§ 61.343(a)(1) § 61.340(d) § 61.343(a)(1)(i)(A) § 61.343(a)(1)(i)(B) § 61.343(c) § 61.343(d)	The owner or operator shall install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the tank to a control device.	§ 61.343(a)(1)(i)(A) § 61.343(c)	§ 61.356(d) § 61.356(g)	None
T280-135	EU	R5112-0139	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(3) § 115.112(e)(3)(C) § 60.18	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this	§ 115.115(a) § 115.115(a)(6) § 115.116(a)(2) [G]§ 115.117	§ 115.118(a)(4) § 115.118(a)(4)(F) § 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						paragraph for crude oil and condensate.			
T280-135	EU	61FF-0014	Benzene	40 CFR Part 61, Subpart FF	§ 61.343(a)(1) § 60.18 § 61.343(a)(1)(i)(A) § 61.343(a)(1)(i)(B) § 61.343(c) § 61.343(d) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(iii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	The owner or operator shall install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the tank to a control device.	§ 60.18(f)(2) § 61.343(a)(1)(i)(A) § 61.343(c) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(c) § 61.354(c)(3) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.349(a)(1)(ii) § 61.354(c) § 61.354(c)(3) § 61.356(d) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2)(i)(D) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i) § 61.356(j)(7)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(F)
T280-135	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
T280-136	EU	R5112-0139	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(3) § 115.112(e)(3)(C) § 60.18	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in	§ 115.115(a) § 115.115(a)(6) § 115.116(a)(2) [G]§ 115.117	§ 115.118(a)(4) § 115.118(a)(4)(F) § 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.			
T280-136	EU	61FF-0014	Benzene	40 CFR Part 61, Subpart FF	§ 61.343(a)(1) § 60.18 § 61.343(a)(1)(i)(A) § 61.343(a)(1)(i)(B) § 61.343(c) § 61.343(d) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(iii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	The owner or operator shall install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the tank to a control device.	§ 60.18(f)(2) § 61.343(a)(1)(i)(A) § 61.343(c) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(c) § 61.354(c)(3) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.349(a)(1)(ii) § 61.354(c) § 61.354(c)(3) § 61.356(d) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2)(i)(D) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i) § 61.356(j)(7)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(F)
T280-136	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
T280-137	EU	R5112-0139	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(3) § 115.112(e)(3)(C) § 60.18	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor	§ 115.115(a) § 115.115(a)(6) § 115.116(a)(2) [G]§ 115.117	§ 115.118(a)(4) § 115.118(a)(4)(F) § 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.			
T280-137	EU	61FF-0014	Benzene	40 CFR Part 61, Subpart FF	§ 61.343(a)(1) § 60.18 § 61.343(a)(1)(i)(A) § 61.343(a)(1)(i)(B) § 61.343(c) § 61.343(d) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(iii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	The owner or operator shall install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the tank to a control device.	§ 60.18(f)(2) § 61.343(a)(1)(i)(A) § 61.343(c) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(c) § 61.354(c)(3) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.349(a)(1)(ii) § 61.354(c) § 61.354(c)(3) § 61.356(d) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2)(i)(D) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i) § 61.356(j)(7)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(F)
T280-137	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
T280-138	EU	R5112-0139	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(3) § 115.112(e)(3)(C)	No person shall place, store, or hold VOC in any storage tank unless the	§ 115.115(a) § 115.115(a)(6) § 115.116(a)(2)	§ 115.118(a)(4) § 115.118(a)(4)(F) § 115.118(a)(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.18	storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	[G]§ 115.117	§ 115.118(a)(7)	
T280-138	EU	61FF-0014	Benzene	40 CFR Part 61, Subpart FF	§ 61.343(a)(1) § 60.18 § 61.343(a)(1)(i)(A) § 61.343(a)(1)(i)(B) § 61.343(c) § 61.343(d) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(iii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	The owner or operator shall install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the tank to a control device.	§ 60.18(f)(2) § 61.343(a)(1)(i)(A) § 61.343(c) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(c) § 61.354(c)(3) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.349(a)(1)(ii) § 61.354(c) § 61.354(c)(3) § 61.356(d) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2)(i)(D) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i) § 61.356(j)(7)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(F)
T280-138	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
									§ 63.655(h)(6)(ii)
T280-14	EU	R5112-0090	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)
T280-14	EU	63CC-0059	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) [G]§ 60.112b(a)(2) § 63.640(n)(8)(i) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) [G]§ 63.120(b)(7) § 63.640(n)(8)(ii)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 63.640(n)(8)(vi)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)
T280-140	EU	R5112-0090	VOC	30 TAC Chapter 115, Storage of	§ 115.112(e)(1) § 115.112(e)(2)	No person shall place, store, or hold VOC in any	§ 115.114(a)(2) § 115.114(a)(3)	§ 115.118(a)(3) § 115.118(a)(5)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				VOCs	§ 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.118(a)(3)
T280-140	EU	61FF-0006	Benzene	40 CFR Part 61, Subpart FF	§ 61.351(a) [G]§ 60.112b(a)(2) § 61.351(a)(2) § 61.351(b)	As an alternative to the standards for tanks specified in § 61.343, an owner or operator may elect to comply with one of the following §61.351(a)(1)-(3):	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6)	§ 60.115b [G]§ 60.115b(b)(3) § 61.356(k)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 61.357(e) § 61.357(f)
T280-140	EU	63CC-0071	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) [G]§ 60.112b(a)(2) § 63.640(n)(8)(i) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 63.640(n)(8)(vi)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 60.116b(b) § 60.116b(e)(1) [G]§ 60.116b(e)(3) § 60.116b(f)(1) [G]§ 63.120(b)(7) § 63.640(n)(8)(ii)		
T280-15	EU	R5112-0090	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)
T280-15	EU	63CC-0059	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) [G]§ 60.112b(a)(2) § 63.640(n)(8)(i) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 63.640(n)(8)(vi)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 60.116b(e)(2)(i) [G]§ 63.120(b)(7) § 63.640(n)(8)(ii)		
T280-160	EU	R5112-0012	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
T280-160	EU	61FF-0015	Benzene	40 CFR Part 61, Subpart FF	§ 61.343(a)(1) § 60.18 § 61.343(a)(1)(i)(A) § 61.343(a)(1)(i)(B) § 61.343(c) § 61.343(d) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	The owner or operator shall install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the tank to a control device.	§ 60.18(f)(2) § 61.343(a)(1)(i)(A) § 61.343(c) § 61.349(a)(1)(i) § 61.349(e) § 61.349(f) § 61.354(c) § 61.354(c)(3) [G]§ 61.355(h)	§ 61.354(c) § 61.354(c)(3) § 61.356(d) § 61.356(f) § 61.356(f)(1) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(7)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(F)
T280-161	EU	R5112-0132	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(3) § 115.112(e)(3)(C) § 60.18	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2	§ 115.115(a) § 115.115(a)(6) § 115.116(a)(2) [G]§ 115.117	§ 115.118(a)(4) § 115.118(a)(4)(F) § 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						of subsection (a)(1) of this paragraph for crude oil and condensate.			
T280-161	EU	60KB-0072	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(3) § 60.18 § 63.640(n)(1)	Storage vessels specified in §60.112b(a) and equipped with a closed vent system/control device are to meet the specifications of §60.112b(a)(3)(i)-(ii).	§ 60.113b(d) § 60.116b(a) § 60.116b(b) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3) [G]§ 60.485(b) ** See Periodic Monitoring Summary	§ 60.115b § 60.115b(d)(2) § 60.116b(a) § 60.116b(b)	§ 60.115b § 60.115b(d)(1) § 60.115b(d)(3)
T280-161	EU	61FF-0015	Benzene	40 CFR Part 61, Subpart FF	§ 61.343(a)(1) § 60.18 § 61.343(a)(1)(i)(A) § 61.343(a)(1)(i)(B) § 61.343(c) § 61.343(d) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	The owner or operator shall install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the tank to a control device.	§ 60.18(f)(2) § 61.343(a)(1)(i)(A) § 61.343(c) § 61.349(a)(1)(i) § 61.349(e) § 61.349(f) § 61.354(c) § 61.354(c)(3) [G]§ 61.355(h)	§ 61.354(c) § 61.354(c)(3) § 61.356(d) § 61.356(f) § 61.356(f)(1) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(7)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(F)
T280-16A	EU	R5112-0021	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.			
T280-16A	EU	60Kb-0025	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)
T280-16A	EU	63CC-0059	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC
T280-17	EU	R5112-0012	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						division.			
T280-17	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
T280-18	EU	R5112-0012	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
T280-18	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
T280-181	EU	R5112-0090	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.			
T280-181	EU	60Kb-0070	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)
T280-181	EU	63CC-0083	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) [G]§ 60.112b(a)(2) § 63.640(n)(8)(i) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) [G]§ 60.116b(e)(3) [G]§ 63.120(b)(7)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 63.640(n)(8)(vi)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 63.640(n)(8)(ii)		
T280-184	EU	R5112-0090	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)
T280-184	EU	63CC-0071	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) [G]§ 60.112b(a)(2) § 63.640(n)(8)(i) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(e)(1) [G]§ 60.116b(e)(3) § 60.116b(f)(1) [G]§ 63.120(b)(7) § 63.640(n)(8)(ii)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 63.640(n)(8)(vi)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)
T280-187	EU	R5112-0090	VOC	30 TAC Chapter 115, Storage of	§ 115.112(e)(1) § 115.112(e)(2)	No person shall place, store, or hold VOC in any	§ 115.114(a)(2) § 115.114(a)(3)	§ 115.118(a)(3) § 115.118(a)(5)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				VOCs	§ 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.118(a)(3)
T280-187	EU	63CC-0256	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.119(a)(1) § 63.119(c)(1) § 63.119(c)(1)(i) § 63.119(c)(1)(ii) § 63.119(c)(1)(iii) [G]§ 63.119(c)(3) § 63.119(c)(4) § 63.120(b)(10)(i) § 63.120(b)(5)(i) § 63.120(b)(5)(ii) § 63.120(b)(6)(i) § 63.120(b)(6)(ii) [G]§ 63.120(b)(7) § 63.120(b)(8) [G]§ 63.646(f) § 63.646(g)	Each owner or operator of a Group 1 storage vessel subject to this subpart shall comply with the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.120(b)(1)(i) § 63.120(b)(1)(iii) § 63.120(b)(1)(iv) § 63.120(b)(10) § 63.120(b)(2)(i) § 63.120(b)(2)(ii) § 63.120(b)(2)(iii) § 63.120(b)(3) § 63.120(b)(4) § 63.646(b)(1) § 63.646(b)(2) § 63.646(e)	[G]§ 63.120(b)(7) § 63.120(b)(8) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1) § 63.655(i)(5)	§ 63.120(b)(10)(ii) § 63.120(b)(10)(iii) § 63.120(b)(9) § 63.642(f) § 63.655(f) § 63.655(f)(1)(i) [G]§ 63.655(f)(1)(i)(A) § 63.655(f)(6) § 63.655(g) § 63.655(g)(1) [G]§ 63.655(g)(3) § 63.655(h) § 63.655(h)(1) § 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(B) § 63.655(h)(2)(i)(C) § 63.655(h)(2)(ii) [G]§ 63.655(h)(6)
T280-188	EU	R5112-0090	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A)	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	[G]§ 115.117		
T280-188	EU	60Kb-0070	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)
T280-188	EU	63CC-0083	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) [G]§ 60.112b(a)(2) § 63.640(n)(8)(i) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 63.640(n)(8)(vi)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 63.640(n)(8)(iv)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) [G]§ 60.116b(e)(3) [G]§ 63.120(b)(7) § 63.640(n)(8)(ii)		§ 63.640(n)(8)(v)
T280-19	EU	R5112-0019	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(D) § 115.112(e)(2)(F) [G]§ 115.112(e)(2)(I) § 115.114(a)(1)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(1)(B) § 115.118(a)(3)
T280-19	EU	60Kb-0068	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(B) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) [G]§ 60.113b(a)(3) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(4)
T280-19	EU	63CC-	112(B)	40 CFR Part 63,	§ 63.640(n)(8)	Vessels described by §	§ 60.113b(a)(1)	§ 60.115b	§ 60.113b(a)(5)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		0081	HAPS	Subpart CC	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(B) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii) § 63.640(n)(8)(ii)	63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	[G]§ 60.113b(a)(3) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) [G]§ 60.116b(e)(3) § 63.640(n)(8)(ii)	§ 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.115b § 60.115b(a)(1) § 60.115b(a)(4)
T280-20	EU	R5112-0019	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(D) § 115.112(e)(2)(F) [G]§ 115.112(e)(2)(I) § 115.114(a)(1)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(1)(B) § 115.118(a)(3)
T280-20	EU	63CC-0248	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.119(a)(1) [G]§ 63.119(b)(1) § 63.119(b)(2) § 63.119(b)(3)(iii) § 63.119(d) § 63.120(a)(4) § 63.120(a)(7) [G]§ 63.646(f) § 63.646(g)	Each owner or operator of a Group 1 storage vessel subject to this subpart shall comply with the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.120(a)(3)(i) § 63.120(a)(3)(ii) § 63.120(a)(3)(iii) § 63.646(b)(1) § 63.646(e)	§ 63.120(a)(4) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1) § 63.655(i)(5)	§ 63.120(a)(5) § 63.120(a)(6) § 63.642(f) § 63.655(f) § 63.655(f)(1)(i) [G]§ 63.655(f)(1)(i)(A) § 63.655(f)(6) § 63.655(g) § 63.655(g)(1) § 63.655(g)(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
									[G]§ 63.655(g)(2)(ii) § 63.655(h) § 63.655(h)(1) § 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(B) § 63.655(h)(2)(i)(C) [G]§ 63.655(h)(6)
T280-22	EU	R5112-0090	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)
T280-22	EU	63CC-0256	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.119(a)(1) § 63.119(c)(1) § 63.119(c)(1)(i) § 63.119(c)(1)(ii) § 63.119(c)(1)(iii) [G]§ 63.119(c)(3) § 63.119(c)(4) § 63.120(b)(10)(i) § 63.120(b)(5)(i) § 63.120(b)(5)(ii) § 63.120(b)(6)(i) § 63.120(b)(6)(ii)	Each owner or operator of a Group 1 storage vessel subject to this subpart shall comply with the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.120(b)(1)(i) § 63.120(b)(1)(iii) § 63.120(b)(1)(iv) § 63.120(b)(10) § 63.120(b)(2)(i) § 63.120(b)(2)(ii) § 63.120(b)(2)(iii) § 63.120(b)(3) § 63.120(b)(4) § 63.646(b)(1) § 63.646(b)(2) § 63.646(e)	[G]§ 63.120(b)(7) § 63.120(b)(8) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1) § 63.655(i)(5)	§ 63.120(b)(10)(ii) § 63.120(b)(10)(iii) § 63.120(b)(9) § 63.642(f) § 63.655(f) § 63.655(f)(1)(i) [G]§ 63.655(f)(1)(i)(A) § 63.655(f)(6) § 63.655(g) § 63.655(g)(1) [G]§ 63.655(g)(3) § 63.655(h) § 63.655(h)(1)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 63.120(b)(7) § 63.120(b)(8) [G]§ 63.646(f) § 63.646(g)				§ 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(B) § 63.655(h)(2)(i)(C) § 63.655(h)(2)(ii) [G]§ 63.655(h)(6)
T280-222	EU	R5112-0132	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(3) § 115.112(e)(3)(C) § 60.18	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.115(a) § 115.115(a)(6) § 115.116(a)(2) [G]§ 115.117	§ 115.118(a)(4) § 115.118(a)(4)(F) § 115.118(a)(5) § 115.118(a)(7)	None
T280-222	EU	60KB-0072	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(3) § 60.18 § 63.640(n)(1)	Storage vessels specified in §60.112b(a) and equipped with a closed vent system/control device are to meet the specifications of §60.112b(a)(3)(i)-(ii).	§ 60.113b(d) § 60.116b(a) § 60.116b(b) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3) [G]§ 60.485(b) ** See Periodic Monitoring Summary	§ 60.115b § 60.115b(d)(2) § 60.116b(a) § 60.116b(b)	§ 60.115b § 60.115b(d)(1) § 60.115b(d)(3)
T280-222	EU	61FF-0015	Benzene	40 CFR Part 61, Subpart FF	§ 61.343(a)(1) § 60.18 § 61.343(a)(1)(i)(A) § 61.343(a)(1)(i)(B) § 61.343(c) § 61.343(d)	The owner or operator shall install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the tank to a	§ 60.18(f)(2) § 61.343(a)(1)(i)(A) § 61.343(c) § 61.349(a)(1)(i) § 61.349(e) § 61.349(f)	§ 61.354(c) § 61.354(c)(3) § 61.356(d) § 61.356(f) § 61.356(f)(1) § 61.356(g)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(F)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	control device.	§ 61.354(c) § 61.354(c)(3) [G]§ 61.355(h)	§ 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(7)	
T280-223	EU	R5112-0132	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(3) § 115.112(e)(3)(C) § 60.18	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.115(a) § 115.115(a)(6) § 115.116(a)(2) [G]§ 115.117	§ 115.118(a)(4) § 115.118(a)(4)(F) § 115.118(a)(5) § 115.118(a)(7)	None
T280-223	EU	60KB-0072	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(3) § 60.18 § 63.640(n)(1)	Storage vessels specified in §60.112b(a) and equipped with a closed vent system/control device are to meet the specifications of §60.112b(a)(3)(i)-(ii).	§ 60.113b(d) § 60.116b(a) § 60.116b(b) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3) [G]§ 60.485(b) ** See Periodic Monitoring Summary	§ 60.115b § 60.115b(d)(2) § 60.116b(a) § 60.116b(b)	§ 60.115b § 60.115b(d)(1) § 60.115b(d)(3)
T280-223	EU	61FF-0015	Benzene	40 CFR Part 61, Subpart FF	§ 61.343(a)(1) § 60.18 § 61.343(a)(1)(i)(A) § 61.343(a)(1)(i)(B)	The owner or operator shall install, operate, and maintain a fixed-roof and closed-vent system that	§ 60.18(f)(2) § 61.343(a)(1)(i)(A) § 61.343(c) § 61.349(a)(1)(i)	§ 61.354(c) § 61.354(c)(3) § 61.356(d) § 61.356(f)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(F)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 61.343(c) § 61.343(d) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	routes all organic vapors vented from the tank to a control device.	§ 61.349(e) § 61.349(f) § 61.354(c) § 61.354(c)(3) [G]§ 61.355(h)	§ 61.356(f)(1) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(7)	
T280-23	EU	R5112-0090	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)
T280-23	EU	63CC-0059	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) [G]§ 60.112b(a)(2) § 63.640(n)(8)(i) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 63.640(n)(8)(vi)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) [G]§ 63.120(b)(7) § 63.640(n)(8)(ii)		
T280-24	EU	R5112-0019	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(D) § 115.112(e)(2)(F) [G]§ 115.112(e)(2)(I) § 115.114(a)(1)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(1)(B) § 115.118(a)(3)
T280-24	EU	63CC-0004	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC
T280-25	EU	R5112-0090	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A)	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	[G]§ 115.117		
T280-25	EU	60Kb-0070	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)
T280-25	EU	63CC-0256	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.119(a)(1) § 63.119(c)(1) § 63.119(c)(1)(i) § 63.119(c)(1)(ii) § 63.119(c)(1)(iii) [G]§ 63.119(c)(3) § 63.119(c)(4)	Each owner or operator of a Group 1 storage vessel subject to this subpart shall comply with the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.120(b)(1)(i) § 63.120(b)(1)(iii) § 63.120(b)(1)(iv) § 63.120(b)(10) § 63.120(b)(2)(i) § 63.120(b)(2)(ii) § 63.120(b)(2)(iii) § 63.120(b)(3)	[G]§ 63.120(b)(7) § 63.120(b)(8) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1) § 63.655(i)(5)	§ 63.120(b)(10)(ii) § 63.120(b)(10)(iii) § 63.120(b)(9) § 63.642(f) § 63.655(f) § 63.655(f)(1)(i) [G]§ 63.655(f)(1)(i)(A) § 63.655(f)(6)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.120(b)(10)(i) § 63.120(b)(5)(i) § 63.120(b)(5)(ii) § 63.120(b)(6)(i) § 63.120(b)(6)(ii) [G]§ 63.120(b)(7) § 63.120(b)(8) [G]§ 63.646(f) § 63.646(g)		§ 63.120(b)(4) § 63.646(b)(1) § 63.646(b)(2) § 63.646(e)		§ 63.655(g) § 63.655(g)(1) [G]§ 63.655(g)(3) § 63.655(h) § 63.655(h)(1) § 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(B) § 63.655(h)(2)(i)(C) § 63.655(h)(2)(ii) [G]§ 63.655(h)(6)
T280-26	EU	R5112-0090	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)
T280-26	EU	63CC-0059	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) [G]§ 60.112b(a)(2) § 63.640(n)(8)(i) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 63.640(n)(8)(vi)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							[G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) [G]§ 63.120(b)(7) § 63.640(n)(8)(ii)		
T280-269	EU	R5112-0090	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)
T280-269	EU	61FF-0006	Benzene	40 CFR Part 61, Subpart FF	§ 61.351(a) [G]§ 60.112b(a)(2) § 61.351(a)(2) § 61.351(b)	As an alternative to the standards for tanks specified in § 61.343, an owner or operator may elect to comply with one of the following §61.351(a)(1)-(3):	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6)	§ 60.115b [G]§ 60.115b(b)(3) § 61.356(k)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 61.357(e) § 61.357(f)
T280-269	EU	63CC-0059	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) [G]§ 60.112b(a)(2)	Vessels described by § 63.640(n)(1) and (n)(3) are	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2)	§ 60.115b [G]§ 60.115b(b)(3)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.640(n)(8)(i) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	§ 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) [G]§ 63.120(b)(7) § 63.640(n)(8)(ii)	§ 60.116b(a) § 60.116b(b) § 60.116b(c) § 63.640(n)(8)(vi)	§ 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)
T280-27	EU	R5112-0090	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)
T280-27	EU	63CC-0059	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) [G]§ 60.112b(a)(2) § 63.640(n)(8)(i) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						§63.640(n)(8)(i)-(vi).	§ 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) [G]§ 63.120(b)(7) § 63.640(n)(8)(ii)	§ 63.640(n)(8)(vi)	[G]§ 60.115b(b)(2) § 60.115b(b)(4) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)
T280-270	EU	R5112-0090	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)
T280-270	EU	61FF-0006	Benzene	40 CFR Part 61, Subpart FF	§ 61.351(a) [G]§ 60.112b(a)(2) § 61.351(a)(2) § 61.351(b)	As an alternative to the standards for tanks specified in § 61.343, an owner or operator may elect to comply with one of the following §61.351(a)(1)-(3):	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii)	§ 60.115b [G]§ 60.115b(b)(3) § 61.356(k)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 61.357(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6)		§ 61.357(f)
T280-270	EU	63CC-0059	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) [G]§ 60.112b(a)(2) § 63.640(n)(8)(i) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) [G]§ 63.120(b)(7) § 63.640(n)(8)(ii)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 63.640(n)(8)(vi)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)
T280-271	EU	R5112-0012	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
T280-271	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
T280-28	EU	R5112-	VOC	30 TAC Chapter	§ 115.112(e)(1)	No person shall place,	§ 115.114(a)(1)	§ 115.118(a)(3)	§ 115.114(a)(1)(B)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		0019		115, Storage of VOCs	§ 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(D) § 115.112(e)(2)(F) [G]§ 115.112(e)(2)(I) § 115.114(a)(1)(A)	store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.118(a)(3)
T280-28	EU	63CC-0083	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC
T280-28	EU	63G-0001	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(d) § 63.110(b)(1) § 63.110(b)(2) § 63.119(a)(1) [G]§ 63.119(b)(1) § 63.119(b)(2) § 63.119(b)(3)(iii) § 63.119(c)(2)(i) § 63.119(c)(2)(ii) § 63.119(c)(2)(iii) § 63.119(c)(2)(iv) § 63.119(c)(2)(ix)	External floating roofs converted to an internal floating roof (i.e., fixed roof installed above external floating roof) to comply with §63.119(a)(1) shall comply with §63.119(d)(1)-(2).	§ 63.120(a)(3)(i) § 63.120(a)(3)(ii) § 63.120(a)(3)(iii)	§ 63.120(a)(4) § 63.123(a) § 63.123(e) § 63.123(g) [G]§ 63.152(a)	§ 63.120(a)(5) § 63.120(a)(6) § 63.122(d) § 63.122(d)(1)(ii) § 63.122(d)(1)(iii) § 63.122(d)(2)(ii) § 63.122(f) § 63.151(a)(7) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.119(c)(2)(v) § 63.119(c)(2)(vi) § 63.119(c)(2)(vii) § 63.119(c)(2)(viii) § 63.119(c)(2)(x) § 63.119(c)(2)(xi) § 63.119(c)(2)(xii) § 63.120(a)(4) § 63.120(a)(7)				[G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(4)(ii)
T280-29	EU	R5112-0019	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(D) § 115.112(e)(2)(F) [G]§ 115.112(e)(2)(I) § 115.114(a)(1)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(1)(B) § 115.118(a)(3)
T280-29	EU	63CC-0081	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC
T280-29	EU	63G-0001	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(d) § 63.110(b)(1)	External floating roofs converted to an internal	§ 63.120(a)(3)(i) § 63.120(a)(3)(ii)	§ 63.120(a)(4) § 63.123(a)	§ 63.120(a)(5) § 63.120(a)(6)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.110(b)(2) § 63.119(a)(1) [G]§ 63.119(b)(1) § 63.119(b)(2) § 63.119(b)(3)(iii) § 63.119(c)(2)(i) § 63.119(c)(2)(ii) § 63.119(c)(2)(iii) § 63.119(c)(2)(iv) § 63.119(c)(2)(ix) § 63.119(c)(2)(v) § 63.119(c)(2)(vi) § 63.119(c)(2)(vii) § 63.119(c)(2)(viii) § 63.119(c)(2)(x) § 63.119(c)(2)(xi) § 63.119(c)(2)(xii) § 63.120(a)(4) § 63.120(a)(7)	floating roof (i.e., fixed roof installed above external floating roof) to comply with §63.119(a)(1) shall comply with §63.119(d)(1)-(2).	§ 63.120(a)(3)(iii)	§ 63.123(e) § 63.123(g) [G]§ 63.152(a)	§ 63.122(d) § 63.122(d)(1)(ii) § 63.122(d)(1)(iii) § 63.122(d)(2)(ii) § 63.122(f) § 63.151(a)(7) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(4)(ii)
T280-30	EU	R5112-0019	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(D) § 115.112(e)(2)(F) [G]§ 115.112(e)(2)(I) § 115.114(a)(1)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(1)(B) § 115.118(a)(3)
T280-30	EU	61Y-0017	Benzene	40 CFR Part 61, Subpart Y	§ 61.271(a) § 61.271(a)(1)	The owner or operator of each storage vessel with a	§ 61.272(a)(1) § 61.272(a)(2)	§ 61.276(a) § 61.276(b)	§ 61.272(a)(2) § 61.272(a)(3)(i)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 61.271(a)(2) § 61.271(a)(2)(ii) § 61.271(a)(3) § 61.271(a)(4) [G]§ 61.271(a)(5) § 61.271(a)(6) [G]§ 61.271(d) § 61.272(a)(3)(ii)	design storage capacity greater than or equal to 38 cubic meters (10,000 gal.) shall equip the vessel with a fixed roof and an internal floating roof.	§ 61.272(a)(3) § 61.272(a)(3)(ii) [G]§ 61.272(a)(4)		§ 61.274(a) [G]§ 61.275(a) [G]§ 61.275(b) § 61.275(c)
T280-30	EU	63CC-0248	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.119(a)(1) [G]§ 63.119(b)(1) § 63.119(b)(2) § 63.119(b)(3)(iii) § 63.119(d) § 63.120(a)(4) § 63.120(a)(7) [G]§ 63.646(f) § 63.646(g)	Each owner or operator of a Group 1 storage vessel subject to this subpart shall comply with the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.120(a)(3)(i) § 63.120(a)(3)(ii) § 63.120(a)(3)(iii) § 63.646(b)(1) § 63.646(e)	§ 63.120(a)(4) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1) § 63.655(i)(5)	§ 63.120(a)(5) § 63.120(a)(6) § 63.642(f) § 63.655(f) § 63.655(f)(1)(i) [G]§ 63.655(f)(1)(i)(A) § 63.655(f)(6) § 63.655(g) § 63.655(g)(1) § 63.655(g)(2) [G]§ 63.655(g)(2)(ii) § 63.655(h) § 63.655(h)(1) § 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(B) § 63.655(h)(2)(i)(C) [G]§ 63.655(h)(6)
T280-3003	EU	R5112-0006	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T280-3006	EU	R5112-0006	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						requirements of this division.			
T280-3007	EU	R5112-0006	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T280-3007	EU	63EEEE-1	112(B) HAPS	40 CFR Part 63, Subpart EEEE	§ 63.2338(b) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart EEEE
T280-3010	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
T280-3022	EU	R5112-0006	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T280-3023	EU	R5112-0006	VOC	30 TAC Chapter 115, Storage of	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				VOCs		storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.		§ 115.118(a)(7)	
T280-3024	EU	R5112-0006	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T280-3025	EU	R5112-0006	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T280-3026	EU	R5112-0006	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T280-3027	EU	R5112-0006	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T280-3027	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						meeting the criteria in paragraph (a) of this section are part of the affected source.		§ 63.655(i)(5)	§ 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
T280-3040	EU	R5112-0006	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T280-3041	EU	R5112-0006	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T280-3042	EU	R5112-0006	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T280-3043	EU	R5112-0006	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T280-3044	EU	R5112-0006	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						vapor pressure less than 1.5 psia is exempt from the requirements of this division.			
T280-3045	EU	R5112-0006	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T280-3103	EU	R5112-0006	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T280-3105	EU	R5112-0006	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T280-3106	EU	R5112-0006	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T280-3107	EU	R5112-0006	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						1.5 psia is exempt from the requirements of this division.			
T280-3107	EU	63EEEE-1	112(B) HAPS	40 CFR Part 63, Subpart EEEE	§ 63.2338(b) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart EEEE
T280-33A	EU	R5112-0012	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
T280-33A	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC
T280-34	EU	R5112-0012	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T280-34	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
T280-36	EU	R5112-0090	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)
T280-36	EU	63CC-0256	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.119(a)(1) § 63.119(c)(1) § 63.119(c)(1)(i) § 63.119(c)(1)(ii) § 63.119(c)(1)(iii) [G]§ 63.119(c)(3) § 63.119(c)(4) § 63.120(b)(10)(i) § 63.120(b)(5)(i) § 63.120(b)(5)(ii) § 63.120(b)(6)(i) § 63.120(b)(6)(ii)	Each owner or operator of a Group 1 storage vessel subject to this subpart shall comply with the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.120(b)(1)(i) § 63.120(b)(1)(iii) § 63.120(b)(1)(iv) § 63.120(b)(10) § 63.120(b)(2)(i) § 63.120(b)(2)(ii) § 63.120(b)(2)(iii) § 63.120(b)(3) § 63.120(b)(4) § 63.646(b)(1) § 63.646(b)(2) § 63.646(e)	[G]§ 63.120(b)(7) § 63.120(b)(8) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1) § 63.655(i)(5)	§ 63.120(b)(10)(ii) § 63.120(b)(10)(iii) § 63.120(b)(9) § 63.642(f) § 63.655(f) § 63.655(f)(1)(i) [G]§ 63.655(f)(1)(i)(A) § 63.655(f)(6) § 63.655(g) § 63.655(g)(1) [G]§ 63.655(g)(3) § 63.655(h) § 63.655(h)(1)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 63.120(b)(7) § 63.120(b)(8) [G]§ 63.646(f) § 63.646(g)				§ 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(B) § 63.655(h)(2)(i)(C) § 63.655(h)(2)(ii) [G]§ 63.655(h)(6)
T280-37	EU	R5112-0090	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)
T280-37	EU	63CC-0256	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.119(a)(1) § 63.119(c)(1) § 63.119(c)(1)(i) § 63.119(c)(1)(ii) § 63.119(c)(1)(iii) [G]§ 63.119(c)(3) § 63.119(c)(4) § 63.120(b)(10)(i) § 63.120(b)(5)(i) § 63.120(b)(5)(ii) § 63.120(b)(6)(i) § 63.120(b)(6)(ii) [G]§ 63.120(b)(7) § 63.120(b)(8)	Each owner or operator of a Group 1 storage vessel subject to this subpart shall comply with the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.120(b)(1)(i) § 63.120(b)(1)(iii) § 63.120(b)(1)(iv) § 63.120(b)(10) § 63.120(b)(2)(i) § 63.120(b)(2)(ii) § 63.120(b)(2)(iii) § 63.120(b)(3) § 63.120(b)(4) § 63.646(b)(1) § 63.646(b)(2) § 63.646(e)	[G]§ 63.120(b)(7) § 63.120(b)(8) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1) § 63.655(i)(5)	§ 63.120(b)(10)(ii) § 63.120(b)(10)(iii) § 63.120(b)(9) § 63.642(f) § 63.655(f) § 63.655(f)(1)(i) [G]§ 63.655(f)(1)(i)(A) § 63.655(f)(6) § 63.655(g) § 63.655(g)(1) [G]§ 63.655(g)(3) § 63.655(h) § 63.655(h)(1) § 63.655(h)(2)(i) § 63.655(h)(2)(i)(A)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 63.646(f) § 63.646(g)				§ 63.655(h)(2)(i)(B) § 63.655(h)(2)(i)(C) § 63.655(h)(2)(ii) [G]§ 63.655(h)(6)
T280-38	EU	R5112-0090	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)
T280-38	EU	63CC-0256	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.119(a)(1) § 63.119(c)(1) § 63.119(c)(1)(i) § 63.119(c)(1)(ii) § 63.119(c)(1)(iii) [G]§ 63.119(c)(3) § 63.119(c)(4) § 63.120(b)(10)(i) § 63.120(b)(5)(i) § 63.120(b)(5)(ii) § 63.120(b)(6)(i) § 63.120(b)(6)(ii) [G]§ 63.120(b)(7) § 63.120(b)(8) [G]§ 63.646(f) § 63.646(g)	Each owner or operator of a Group 1 storage vessel subject to this subpart shall comply with the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.120(b)(1)(i) § 63.120(b)(1)(iii) § 63.120(b)(1)(iv) § 63.120(b)(10) § 63.120(b)(2)(i) § 63.120(b)(2)(ii) § 63.120(b)(2)(iii) § 63.120(b)(3) § 63.120(b)(4) § 63.646(b)(1) § 63.646(b)(2) § 63.646(e)	[G]§ 63.120(b)(7) § 63.120(b)(8) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1) § 63.655(i)(5)	§ 63.120(b)(10)(ii) § 63.120(b)(10)(iii) § 63.120(b)(9) § 63.642(f) § 63.655(f) § 63.655(f)(1)(i) [G]§ 63.655(f)(1)(i)(A) § 63.655(f)(6) § 63.655(g) § 63.655(g)(1) [G]§ 63.655(g)(3) § 63.655(h) § 63.655(h)(1) § 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(B) § 63.655(h)(2)(i)(C)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
									§ 63.655(h)(2)(ii) [G]§ 63.655(h)(6)
T280-39	EU	R5112-0090	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)
T280-39	EU	63CC-0256	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.119(a)(1) § 63.119(c)(1) § 63.119(c)(1)(i) § 63.119(c)(1)(ii) § 63.119(c)(1)(iii) [G]§ 63.119(c)(3) § 63.119(c)(4) § 63.120(b)(10)(i) § 63.120(b)(5)(i) § 63.120(b)(5)(ii) § 63.120(b)(6)(i) § 63.120(b)(6)(ii) [G]§ 63.120(b)(7) § 63.120(b)(8) [G]§ 63.646(f) § 63.646(g)	Each owner or operator of a Group 1 storage vessel subject to this subpart shall comply with the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.120(b)(1)(i) § 63.120(b)(1)(iii) § 63.120(b)(1)(iv) § 63.120(b)(10) § 63.120(b)(2)(i) § 63.120(b)(2)(ii) § 63.120(b)(2)(iii) § 63.120(b)(3) § 63.120(b)(4) § 63.646(b)(1) § 63.646(b)(2) § 63.646(e)	[G]§ 63.120(b)(7) § 63.120(b)(8) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1) § 63.655(i)(5)	§ 63.120(b)(10)(ii) § 63.120(b)(10)(iii) § 63.120(b)(9) § 63.642(f) § 63.655(f) § 63.655(f)(1)(i) [G]§ 63.655(f)(1)(i)(A) § 63.655(f)(6) § 63.655(g) § 63.655(g)(1) [G]§ 63.655(g)(3) § 63.655(h) § 63.655(h)(1) § 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(B) § 63.655(h)(2)(i)(C) § 63.655(h)(2)(ii) [G]§ 63.655(h)(6)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T280-4000	EU	R5112-0012	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
T280-4000	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2) § 63.640(n)(7)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
T280-4001	EU	R5112-0012	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
T280-4001	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2) § 63.640(n)(7)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
T280-4002	EU	R5112-0012	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T280-4002	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2) § 63.640(n)(7)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
T280-4003	EU	R5112-0012	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
T280-4003	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2) § 63.640(n)(7)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
T280-42	EU	R5112-0012	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
T280-42	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
									§ 63.655(h)(6)(ii)
T280-43	EU	R5112-0012	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
T280-43	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
T280-44	EU	R5112-0012	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
T280-44	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
T280-45	EU	R5112-0012	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						requirements of this division.			
T280-45	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
T280-46	EU	R5112-0012	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
T280-46	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
T280-47	EU	R5112-0012	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
T280-47	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						paragraph (a) of this section are part of the affected source.			§ 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
T280-48	EU	R5112-0012	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
T280-48	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
T280-49	EU	R5112-0012	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
T280-49	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
T280-50	EU	R5112-0012	VOC	30 TAC Chapter 115, Storage of	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				VOCs		storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.		§ 115.118(a)(6)(A) § 115.118(a)(7)	
T280-50	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
T280-501	EU	R5112-0090	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)
T280-501	EU	63CC-0059	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) [G]§ 60.112b(a)(2) § 63.640(n)(8)(i) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 63.640(n)(8)(vi)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 63.640(n)(8)(iv)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) [G]§ 63.120(b)(7) § 63.640(n)(8)(ii)		§ 63.640(n)(8)(v)
T280-502	EU	R5112-0090	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)
T280-502	EU	63CC-0083	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) [G]§ 60.112b(a)(2) § 63.640(n)(8)(i) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 63.640(n)(8)(vi)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) [G]§ 60.116b(e)(3) [G]§ 63.120(b)(7) § 63.640(n)(8)(ii)		
T280-503	EU	R5112-0090	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)
T280-503	EU	63CC-0083	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) [G]§ 60.112b(a)(2) § 63.640(n)(8)(i) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 63.640(n)(8)(vi)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 60.116b(e)(1) [G]§ 60.116b(e)(3) [G]§ 63.120(b)(7) § 63.640(n)(8)(ii)		
T280-504	EU	R5112-0090	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)
T280-504	EU	60Kb-0070	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T280-504	EU	63CC-0083	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) [G]§ 60.112b(a)(2) § 63.640(n)(8)(i) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) [G]§ 60.116b(e)(3) [G]§ 63.120(b)(7) § 63.640(n)(8)(ii)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 63.640(n)(8)(vi)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)
T280-51	EU	R5112-0012	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
T280-51	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
T280-52	EU	R5112-0012	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						requirements of this division.			
T280-52	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
T280-520	EU	R5112-0019	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(D) § 115.112(e)(2)(F) [G]§ 115.112(e)(2)(I) § 115.114(a)(1)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(1)(B) § 115.118(a)(3)
T280-520	EU	60Kb-0068	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(B) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) [G]§ 60.113b(a)(3) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T280-520	EU	63CC-0004	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC
T280-528	EU	R5112-0090	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)
T280-528	EU	63CC-0256	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.119(a)(1) § 63.119(c)(1) § 63.119(c)(1)(i) § 63.119(c)(1)(ii) § 63.119(c)(1)(iii) [G]§ 63.119(c)(3) § 63.119(c)(4) § 63.120(b)(10)(i) § 63.120(b)(5)(i) § 63.120(b)(5)(ii)	Each owner or operator of a Group 1 storage vessel subject to this subpart shall comply with the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.120(b)(1)(i) § 63.120(b)(1)(iii) § 63.120(b)(1)(iv) § 63.120(b)(10) § 63.120(b)(2)(i) § 63.120(b)(2)(ii) § 63.120(b)(2)(iii) § 63.120(b)(3) § 63.120(b)(4) § 63.646(b)(1) § 63.646(b)(2)	[G]§ 63.120(b)(7) § 63.120(b)(8) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1) § 63.655(i)(5)	§ 63.120(b)(10)(ii) § 63.120(b)(10)(iii) § 63.120(b)(9) § 63.642(f) § 63.655(f) § 63.655(f)(1)(i) [G]§ 63.655(f)(1)(i)(A) § 63.655(f)(6) § 63.655(g) § 63.655(g)(1) [G]§ 63.655(g)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.120(b)(6)(i) § 63.120(b)(6)(ii) [G]§ 63.120(b)(7) § 63.120(b)(8) [G]§ 63.646(f) § 63.646(g)		§ 63.646(e)		§ 63.655(h) § 63.655(h)(1) § 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(B) § 63.655(h)(2)(i)(C) § 63.655(h)(2)(ii) [G]§ 63.655(h)(6)
T280-529	EU	R5112-0019	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(D) § 115.112(e)(2)(F) [G]§ 115.112(e)(2)(I) § 115.114(a)(1)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(1)(B) § 115.118(a)(3)
T280-529	EU	60Kb-0005	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)
T280-529	EU	63CC-0004	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the	The permit holder shall comply with the applicable requirements of 40 CFR	The permit holder shall comply with the applicable monitoring	The permit holder shall comply with the applicable	The permit holder shall comply with the applicable reporting

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	Part 63, Subpart CC	and testing requirements of 40 CFR Part 63, Subpart CC	recordkeeping requirements of 40 CFR Part 63, Subpart CC	requirements of 40 CFR Part 63, Subpart CC
T280-53	EU	R5112-0012	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
T280-53	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
T280-530	EU	R5112-0090	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						condensate.			
T280-530	EU	63CC-0059	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) [G]§ 60.112b(a)(2) § 63.640(n)(8)(i) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) [G]§ 63.120(b)(7) § 63.640(n)(8)(ii)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 63.640(n)(8)(vi)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)
T280-531	EU	R5112-0090	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)
T280-531	EU	60Kb-0025	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2)	§ 60.115b [G]§ 60.115b(b)(3)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	§ 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)
T280-531	EU	63CC-0059	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC
T280-532	EU	R5112-0090	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.			
T280-532	EU	63CC-0059	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) [G]§ 60.112b(a)(2) § 63.640(n)(8)(i) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) [G]§ 63.120(b)(7) § 63.640(n)(8)(ii)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 63.640(n)(8)(vi)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)
T280-533	EU	R5112-0090	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						condensate.			
T280-533	EU	63Kb-0070	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)
T280-533	EU	63CC-0256	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.119(a)(1) § 63.119(c)(1) § 63.119(c)(1)(i) § 63.119(c)(1)(ii) § 63.119(c)(1)(iii) [G]§ 63.119(c)(3) § 63.119(c)(4) § 63.120(b)(10)(i) § 63.120(b)(5)(i) § 63.120(b)(5)(ii) § 63.120(b)(6)(i) § 63.120(b)(6)(ii) [G]§ 63.120(b)(7) § 63.120(b)(8) [G]§ 63.646(f) § 63.646(g)	Each owner or operator of a Group 1 storage vessel subject to this subpart shall comply with the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.120(b)(1)(i) § 63.120(b)(1)(iii) § 63.120(b)(1)(iv) § 63.120(b)(10) § 63.120(b)(2)(i) § 63.120(b)(2)(ii) § 63.120(b)(2)(iii) § 63.120(b)(3) § 63.120(b)(4) § 63.646(b)(1) § 63.646(b)(2) § 63.646(e)	[G]§ 63.120(b)(7) § 63.120(b)(8) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1) § 63.655(i)(5)	§ 63.120(b)(10)(ii) § 63.120(b)(10)(iii) § 63.120(b)(9) § 63.642(f) § 63.655(f) § 63.655(f)(1)(i) [G]§ 63.655(f)(1)(i)(A) § 63.655(f)(6) § 63.655(g) § 63.655(g)(1) [G]§ 63.655(g)(3) § 63.655(h) § 63.655(h)(1) § 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(B) § 63.655(h)(2)(i)(C) § 63.655(h)(2)(ii) [G]§ 63.655(h)(6)
T280-534	EU	R5112-	VOC	30 TAC Chapter	§ 115.112(e)(1)	No person shall place,	§ 115.114(a)(2)	§ 115.118(a)(3)	§ 115.114(a)(2)(B)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		0090		115, Storage of VOCs	§ 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(4)(B) § 115.118(a)(3)
T280-534	EU	63CC-0256	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.119(a)(1) § 63.119(c)(1) § 63.119(c)(1)(i) § 63.119(c)(1)(ii) § 63.119(c)(1)(iii) [G]§ 63.119(c)(3) § 63.119(c)(4) § 63.120(b)(10)(i) § 63.120(b)(5)(i) § 63.120(b)(5)(ii) § 63.120(b)(6)(i) § 63.120(b)(6)(ii) [G]§ 63.120(b)(7) § 63.120(b)(8) [G]§ 63.646(f) § 63.646(g)	Each owner or operator of a Group 1 storage vessel subject to this subpart shall comply with the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.120(b)(1)(i) § 63.120(b)(1)(iii) § 63.120(b)(1)(iv) § 63.120(b)(10) § 63.120(b)(2)(i) § 63.120(b)(2)(ii) § 63.120(b)(2)(iii) § 63.120(b)(3) § 63.120(b)(4) § 63.646(b)(1) § 63.646(b)(2) § 63.646(e)	[G]§ 63.120(b)(7) § 63.120(b)(8) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1) § 63.655(i)(5)	§ 63.120(b)(10)(ii) § 63.120(b)(10)(iii) § 63.120(b)(9) § 63.642(f) § 63.655(f) § 63.655(f)(1)(i) [G]§ 63.655(f)(1)(i)(A) § 63.655(f)(6) § 63.655(g) § 63.655(g)(1) [G]§ 63.655(g)(3) § 63.655(h) § 63.655(h)(1) § 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(B) § 63.655(h)(2)(i)(C) § 63.655(h)(2)(ii) [G]§ 63.655(h)(6)
T280-535	EU	R5112-0019	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A)	No person shall place, store, or hold VOC in any storage tank unless the	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C)	§ 115.114(a)(1)(B) § 115.118(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(D) § 115.112(e)(2)(F) [G]§ 115.112(e)(2)(I) § 115.114(a)(1)(A)	storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.		§ 115.118(a)(7)	
T280-535	EU	60Kb-0026	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(B) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) [G]§ 60.113b(a)(3) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(4)
T280-535	EU	63CC-0004	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC
T280-536	EU	R5112-0090	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A)	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	[G]§ 115.117		
T280-536	EU	63CC-0256	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.119(a)(1) § 63.119(c)(1) § 63.119(c)(1)(i) § 63.119(c)(1)(ii) § 63.119(c)(1)(iii) [G]§ 63.119(c)(3) § 63.119(c)(4) § 63.120(b)(10)(i) § 63.120(b)(5)(i) § 63.120(b)(5)(ii) § 63.120(b)(6)(i) § 63.120(b)(6)(ii) [G]§ 63.120(b)(7) § 63.120(b)(8) [G]§ 63.646(f) § 63.646(g)	Each owner or operator of a Group 1 storage vessel subject to this subpart shall comply with the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.120(b)(1)(i) § 63.120(b)(1)(iii) § 63.120(b)(1)(iv) § 63.120(b)(10) § 63.120(b)(2)(i) § 63.120(b)(2)(ii) § 63.120(b)(2)(iii) § 63.120(b)(3) § 63.120(b)(4) § 63.646(b)(1) § 63.646(b)(2) § 63.646(e)	[G]§ 63.120(b)(7) § 63.120(b)(8) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1) § 63.655(i)(5)	§ 63.120(b)(10)(ii) § 63.120(b)(10)(iii) § 63.120(b)(9) § 63.642(f) § 63.655(f) § 63.655(f)(1)(i) [G]§ 63.655(f)(1)(i)(A) § 63.655(f)(6) § 63.655(g) § 63.655(g)(1) [G]§ 63.655(g)(3) § 63.655(h) § 63.655(h)(1) § 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(B) § 63.655(h)(2)(i)(C) § 63.655(h)(2)(ii) [G]§ 63.655(h)(6)
T280-537	EU	R5112-0090	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.			
T280-537	EU	63CC-0059	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) [G]§ 60.112b(a)(2) § 63.640(n)(8)(i) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) [G]§ 63.120(b)(7) § 63.640(n)(8)(ii)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 63.640(n)(8)(vi)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)
T280-538	EU	R5112-0090	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.			
T280-538	EU	63CC-0256	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.119(a)(1) § 63.119(c)(1) § 63.119(c)(1)(i) § 63.119(c)(1)(ii) § 63.119(c)(1)(iii) [G]§ 63.119(c)(3) § 63.119(c)(4) § 63.120(b)(10)(i) § 63.120(b)(5)(i) § 63.120(b)(5)(ii) § 63.120(b)(6)(i) § 63.120(b)(6)(ii) [G]§ 63.120(b)(7) § 63.120(b)(8) § 63.640(n)(5) [G]§ 63.646(f) § 63.646(g)	Each owner or operator of a Group 1 storage vessel subject to this subpart shall comply with the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.120(b)(1)(i) § 63.120(b)(1)(iii) § 63.120(b)(1)(iv) § 63.120(b)(10) § 63.120(b)(2)(i) § 63.120(b)(2)(ii) § 63.120(b)(2)(iii) § 63.120(b)(3) § 63.120(b)(4) § 63.646(b)(1) § 63.646(b)(2) § 63.646(e)	[G]§ 63.120(b)(7) § 63.120(b)(8) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1) § 63.655(i)(5)	§ 63.120(b)(10)(ii) § 63.120(b)(10)(iii) § 63.120(b)(9) § 63.642(f) § 63.655(f) § 63.655(f)(1)(i) [G]§ 63.655(f)(1)(i)(A) § 63.655(f)(6) § 63.655(g) § 63.655(g)(1) [G]§ 63.655(g)(3) § 63.655(h) § 63.655(h)(1) § 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(B) § 63.655(h)(2)(i)(C) § 63.655(h)(2)(ii) [G]§ 63.655(h)(6)
T280-54	EU	R5112-0012	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
T280-54	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						paragraph (a) of this section are part of the affected source.			§ 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
T280-55	EU	R5112-0012	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
T280-55	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
T280-56	EU	R5112-0012	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
T280-56	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
T280-561	EU	R5112-0090	VOC	30 TAC Chapter 115, Storage of	§ 115.112(e)(1) § 115.112(e)(2)	No person shall place, store, or hold VOC in any	§ 115.114(a)(2) § 115.114(a)(3)	§ 115.118(a)(3) § 115.118(a)(5)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				VOCs	§ 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.118(a)(3)
T280-561	EU	61FF-0006	Benzene	40 CFR Part 61, Subpart FF	§ 61.351(a) [G]§ 60.112b(a)(2) § 61.351(a)(2) § 61.351(b)	As an alternative to the standards for tanks specified in § 61.343, an owner or operator may elect to comply with one of the following §61.351(a)(1)-(3):	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6)	§ 60.115b [G]§ 60.115b(b)(3) § 61.356(k)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 61.357(e) § 61.357(f)
T280-561	EU	63CC-0071	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) [G]§ 60.112b(a)(2) § 63.640(n)(8)(i) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 63.640(n)(8)(vi)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 60.116b(b) § 60.116b(e)(1) [G]§ 60.116b(e)(3) § 60.116b(f)(1) [G]§ 63.120(b)(7) § 63.640(n)(8)(ii)		
T280-57	EU	R5112-0012	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
T280-57	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2) § 63.640(n)(7)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
T280-60	EU	R5112-0012	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
T280-60	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T280-61	EU	R5112-0012	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
T280-61	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
T280-63	EU	R5112-0012	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
T280-63	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
T280-65	EU	R5112-0012	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T280-65	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
T280-652	EU	R5112-0012	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
T280-652	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
T280-653	EU	R5112-0012	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
T280-653	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
									§ 63.655(h)(6)(ii)
T280-66	EU	R5112-0012	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
T280-66	EU	61FF-0006	Benzene	40 CFR Part 61, Subpart FF	§ 61.351(a) [G]§ 60.112b(a)(2) § 61.351(a)(2) § 61.351(b)	As an alternative to the standards for tanks specified in § 61.343, an owner or operator may elect to comply with one of the following §61.351(a)(1)-(3):	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6)	§ 60.115b [G]§ 60.115b(b)(3) § 61.356(k)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 61.357(e) § 61.357(f)
T280-66	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2) § 63.640(n)(7)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
T280-67	EU	R5112-0012	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
T280-67	EU	61FF-0006	Benzene	40 CFR Part 61, Subpart FF	§ 61.351(a) [G]§ 60.112b(a)(2)	As an alternative to the standards for tanks	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2)	§ 60.115b [G]§ 60.115b(b)(3)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 61.351(a)(2) § 61.351(b)	specified in § 61.343, an owner or operator may elect to comply with one of the following §61.351(a)(1)-(3):	§ 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6)	§ 61.356(k)	§ 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 61.357(e) § 61.357(f)
T280-67	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2) § 63.640(n)(7)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
T280-7	EU	R5112-0012	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
T280-7	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
T280-71	EU	R5112-0012	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						requirements of this division.			
T280-71	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
T280-72	EU	R5112-0012	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
T280-72	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
T280-73	EU	R5112-0012	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
T280-73	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						paragraph (a) of this section are part of the affected source.			§ 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
T280-8	EU	R5112-0019	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(D) § 115.112(e)(2)(F) [G]§ 115.112(e)(2)(I) § 115.114(a)(1)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(1)(B) § 115.118(a)(3)
T280-8	EU	63CC-0248	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.119(a)(1) [G]§ 63.119(b)(1) § 63.119(b)(2) § 63.119(b)(3)(iii) § 63.119(d) § 63.120(a)(4) § 63.120(a)(7) [G]§ 63.646(f) § 63.646(g)	Each owner or operator of a Group 1 storage vessel subject to this subpart shall comply with the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.120(a)(3)(i) § 63.120(a)(3)(ii) § 63.120(a)(3)(iii) § 63.646(b)(1) § 63.646(e)	§ 63.120(a)(4) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1) § 63.655(i)(5)	§ 63.120(a)(5) § 63.120(a)(6) § 63.642(f) § 63.655(f) § 63.655(f)(1)(i) [G]§ 63.655(f)(1)(i)(A) § 63.655(f)(6) § 63.655(g) § 63.655(g)(1) § 63.655(g)(2) [G]§ 63.655(g)(2)(ii) § 63.655(h) § 63.655(h)(1) § 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(B) § 63.655(h)(2)(i)(C)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
									[G]§ 63.655(h)(6)
T280-80	EU	R5112-0012	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
T280-80	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
T280-9	EU	R5112-0019	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(D) § 115.112(e)(2)(F) [G]§ 115.112(e)(2)(I) § 115.114(a)(1)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(1)(B) § 115.118(a)(3)
T280-9	EU	63CC-0248	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.119(a)(1) [G]§ 63.119(b)(1) § 63.119(b)(2)	Each owner or operator of a Group 1 storage vessel subject to this subpart shall comply with the	§ 63.120(a)(3)(i) § 63.120(a)(3)(ii) § 63.120(a)(3)(iii) § 63.646(b)(1)	§ 63.120(a)(4) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1)	§ 63.120(a)(5) § 63.120(a)(6) § 63.642(f) § 63.655(f)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.119(b)(3)(iii) § 63.119(d) § 63.120(a)(4) § 63.120(a)(7) [G]§ 63.646(f) § 63.646(g)	requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.646(e)	[G]§ 63.655(i)(1) § 63.655(i)(5)	§ 63.655(f)(1)(i) [G]§ 63.655(f)(1)(i)(A) § 63.655(f)(6) § 63.655(g) § 63.655(g)(1) § 63.655(g)(2) [G]§ 63.655(g)(2)(ii) § 63.655(h) § 63.655(h)(1) § 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(B) § 63.655(h)(2)(i)(C) [G]§ 63.655(h)(6)
T280-90	EU	R5112-0090	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)
T280-90	EU	63CC-0256	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.119(a)(1) § 63.119(c)(1) § 63.119(c)(1)(i) § 63.119(c)(1)(ii) § 63.119(c)(1)(iii) [G]§ 63.119(c)(3)	Each owner or operator of a Group 1 storage vessel subject to this subpart shall comply with the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.120(b)(1)(i) § 63.120(b)(1)(iii) § 63.120(b)(1)(iv) § 63.120(b)(10) § 63.120(b)(2)(i) § 63.120(b)(2)(ii) § 63.120(b)(2)(iii)	[G]§ 63.120(b)(7) § 63.120(b)(8) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1) § 63.655(i)(5)	§ 63.120(b)(10)(ii) § 63.120(b)(10)(iii) § 63.120(b)(9) § 63.642(f) § 63.655(f) § 63.655(f)(1)(i) [G]§ 63.655(f)(1)(i)(A)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.119(c)(4) § 63.120(b)(10)(i) § 63.120(b)(5)(i) § 63.120(b)(5)(ii) § 63.120(b)(6)(i) § 63.120(b)(6)(ii) [G]§ 63.120(b)(7) § 63.120(b)(8) [G]§ 63.646(f) § 63.646(g)		§ 63.120(b)(3) § 63.120(b)(4) § 63.646(b)(1) § 63.646(b)(2) § 63.646(e)		§ 63.655(f)(6) § 63.655(g) § 63.655(g)(1) [G]§ 63.655(g)(3) § 63.655(h) § 63.655(h)(1) § 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(B) § 63.655(h)(2)(i)(C) § 63.655(h)(2)(ii) [G]§ 63.655(h)(6)
T280-91	EU	R5112-0090	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)
T280-91	EU	63CC-0256	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.119(a)(1) § 63.119(c)(1) § 63.119(c)(1)(i) § 63.119(c)(1)(ii) § 63.119(c)(1)(iii) [G]§ 63.119(c)(3) § 63.119(c)(4) § 63.120(b)(10)(i)	Each owner or operator of a Group 1 storage vessel subject to this subpart shall comply with the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.120(b)(1)(i) § 63.120(b)(1)(iii) § 63.120(b)(1)(iv) § 63.120(b)(10) § 63.120(b)(2)(i) § 63.120(b)(2)(ii) § 63.120(b)(2)(iii) § 63.120(b)(3) § 63.120(b)(4)	[G]§ 63.120(b)(7) § 63.120(b)(8) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1) § 63.655(i)(5)	§ 63.120(b)(10)(ii) § 63.120(b)(10)(iii) § 63.120(b)(9) § 63.642(f) § 63.655(f) § 63.655(f)(1)(i) [G]§ 63.655(f)(1)(i)(A) § 63.655(f)(6) § 63.655(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.120(b)(5)(i) § 63.120(b)(5)(ii) § 63.120(b)(6)(i) § 63.120(b)(6)(ii) [G]§ 63.120(b)(7) § 63.120(b)(8) [G]§ 63.646(f) § 63.646(g)		§ 63.646(b)(1) § 63.646(b)(2) § 63.646(e)		§ 63.655(g)(1) [G]§ 63.655(g)(3) § 63.655(h) § 63.655(h)(1) § 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(B) § 63.655(h)(2)(i)(C) § 63.655(h)(2)(ii) [G]§ 63.655(h)(6)
T280-92	EU	R5112-0090	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)
T280-92	EU	60Kb-0070	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)		
T280-92	EU	63CC-0083	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) [G]§ 60.112b(a)(2) § 63.640(n)(8)(i) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) [G]§ 60.116b(e)(3) [G]§ 63.120(b)(7) § 63.640(n)(8)(ii)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 63.640(n)(8)(vi)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)
T280-94	EU	R5112-0090	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						of subsection (a)(1) of this paragraph for crude oil and condensate.			
T280-94	EU	63CC-0256	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.119(a)(1) § 63.119(c)(1) § 63.119(c)(1)(i) § 63.119(c)(1)(ii) § 63.119(c)(1)(iii) [G]§ 63.119(c)(3) § 63.119(c)(4) § 63.120(b)(10)(i) § 63.120(b)(5)(i) § 63.120(b)(5)(ii) § 63.120(b)(6)(i) § 63.120(b)(6)(ii) [G]§ 63.120(b)(7) § 63.120(b)(8) [G]§ 63.646(f) § 63.646(g)	Each owner or operator of a Group 1 storage vessel subject to this subpart shall comply with the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.120(b)(1)(i) § 63.120(b)(1)(iii) § 63.120(b)(1)(iv) § 63.120(b)(10) § 63.120(b)(2)(i) § 63.120(b)(2)(ii) § 63.120(b)(2)(iii) § 63.120(b)(3) § 63.120(b)(4) § 63.646(b)(1) § 63.646(b)(2) § 63.646(e)	[G]§ 63.120(b)(7) § 63.120(b)(8) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1) § 63.655(i)(5)	§ 63.120(b)(10)(ii) § 63.120(b)(10)(iii) § 63.120(b)(9) § 63.642(f) § 63.655(f) § 63.655(f)(1)(i) [G]§ 63.655(f)(1)(i)(A) § 63.655(f)(6) § 63.655(g) § 63.655(g)(1) [G]§ 63.655(g)(3) § 63.655(h) § 63.655(h)(1) § 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(B) § 63.655(h)(2)(i)(C) § 63.655(h)(2)(ii) [G]§ 63.655(h)(6)
T280-95	EU	R5112-0090	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						condensate.			
T280-95	EU	63CC-0256	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.119(a)(1) § 63.119(c)(1) § 63.119(c)(1)(i) § 63.119(c)(1)(ii) § 63.119(c)(1)(iii) [G]§ 63.119(c)(3) § 63.119(c)(4) § 63.120(b)(10)(i) § 63.120(b)(5)(i) § 63.120(b)(5)(ii) § 63.120(b)(6)(i) § 63.120(b)(6)(ii) [G]§ 63.120(b)(7) § 63.120(b)(8) [G]§ 63.646(f) § 63.646(g)	Each owner or operator of a Group 1 storage vessel subject to this subpart shall comply with the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.120(b)(1)(i) § 63.120(b)(1)(iii) § 63.120(b)(1)(iv) § 63.120(b)(10) § 63.120(b)(2)(i) § 63.120(b)(2)(ii) § 63.120(b)(2)(iii) § 63.120(b)(3) § 63.120(b)(4) § 63.646(b)(1) § 63.646(b)(2) § 63.646(e)	[G]§ 63.120(b)(7) § 63.120(b)(8) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1) § 63.655(i)(5)	§ 63.120(b)(10)(ii) § 63.120(b)(10)(iii) § 63.120(b)(9) § 63.642(f) § 63.655(f) § 63.655(f)(1)(i) [G]§ 63.655(f)(1)(i)(A) § 63.655(f)(6) § 63.655(g) § 63.655(g)(1) [G]§ 63.655(g)(3) § 63.655(h) § 63.655(h)(1) § 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(B) § 63.655(h)(2)(i)(C) § 63.655(h)(2)(ii) [G]§ 63.655(h)(6)
T280-97	EU	R5112-0090	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)
T280-97	EU	63CC-	112(B)	40 CFR Part 63,	§ 63.640(n)(8)	Vessels described by §	[G]§ 60.113b(b)(1)	§ 60.115b	§ 60.113b(b)(4)(iii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		0059	HAPS	Subpart CC	[G]§ 60.112b(a)(2) § 63.640(n)(8)(i) § 63.640(n)(8)(ii) § 63.640(n)(8)(iii)	63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as provided for in §63.640(n)(8)(i)-(vi).	[G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) [G]§ 63.120(b)(7) § 63.640(n)(8)(ii)	[G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 63.640(n)(8)(vi)	§ 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)
T280-98	EU	R5112-0090	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)
T280-98	EU	63CC-0059	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(n)(8) [G]§ 60.112b(a)(2) § 63.640(n)(8)(i) § 63.640(n)(8)(ii)	Vessels described by § 63.640(n)(1) and (n)(3) are to comply with 40 CFR part 60, subpart Kb, except as	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.640(n)(8)(iii)	provided for in §63.640(n)(8)(i)-(vi).	§ 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e)(1) § 60.116b(e)(2)(i) [G]§ 63.120(b)(7) § 63.640(n)(8)(ii)	§ 60.116b(c) § 63.640(n)(8)(vi)	§ 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 63.640(n)(8)(iv) § 63.640(n)(8)(v)
TCH-2	EU	R1111-0001	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(4)(A)	Visible emissions from a process gas flare shall not be permitted for more than five minutes in any two-hour period, except for emission event emissions as provided in §101.222(b).	§ 111.111(a)(4)(A)(i) § 111.111(a)(4)(A)(ii)	§ 111.111(a)(4)(A)(ii)	None
TCH-2	EP	R5720-0225	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Vent Gas	§ 115.722(d) § 115.722(d)(1) § 115.722(d)(2) [G]§ 115.725(d)(1) § 115.725(d)(2) § 115.725(d)(2)(A)(i) [G]§ 115.725(d)(2)(A)(ii) § 115.725(d)(2)(A)(iii) § 115.725(d)(2)(A)(iv) § 115.725(d)(2)(B) § 115.725(d)(2)(B)(i) § 115.725(d)(2)(B)(ii) § 115.725(d)(2)(B)(iii) § 115.725(d)(2)(B)(iv) [G]§ 115.725(l) § 115.725(m)(2)(A)	All flares must continuously meet the requirements of 40 CFR § 60.18(c)(2)-(6) and (d) as amended through October 17, 2000 (65 FR 61744) when vent gas containing HRVOC is being routed to the flare.	[G]§ 115.725(d)(1) § 115.725(d)(2) § 115.725(d)(2)(A)(i) [G]§ 115.725(d)(2)(A)(ii) § 115.725(d)(2)(A)(iii) § 115.725(d)(2)(A)(iv) § 115.725(d)(2)(B) § 115.725(d)(2)(B)(i) § 115.725(d)(2)(B)(ii) § 115.725(d)(2)(B)(iii) § 115.725(d)(2)(B)(iv) § 115.725(d)(3) § 115.725(d)(4) § 115.725(d)(5) § 115.725(d)(6) § 115.725(d)(7) § 115.725(k)(1)	§ 115.726(a)(1) § 115.726(a)(1)(A) § 115.726(d)(1) § 115.726(d)(10) § 115.726(d)(2) § 115.726(d)(3) § 115.726(d)(4) § 115.726(d)(7) § 115.726(d)(7)(A) § 115.726(d)(7)(B) § 115.726(d)(7)(C) § 115.726(i) § 115.726(j)(1) § 115.726(j)(2)	§ 115.725(n) § 115.726(a)(1)(B)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.725(m)(2)(B)		[G]§ 115.725(l) § 115.725(m)(1) § 115.725(m)(2)(A) § 115.725(m)(2)(B) § 115.725(n)		
TCH-2	EP	R5720-0505	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Vent Gas	§ 115.727(f) § 115.722(d) § 115.722(d)(1) § 115.722(d)(2)	All sites that are subject to this division and that are located in the Houston/Galveston/ Brazoria area as defined in §115.10 of this title (relating to Definitions), excluding Harris County, are exempt from § 115.722(b) and (c)(2) of this title, except as provided in § 115.729(a)(3) of this title (relating to Counties and Compliance Schedules).	§ 115.725(n)	§ 115.726(d)(1) § 115.726(d)(2) § 115.726(d)(3) § 115.726(d)(4) § 115.726(i) § 115.726(j)(1) § 115.726(j)(2)	§ 115.725(n)
TCH-2	EP	R5121-0016	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(1) § 115.122(a)(1) § 115.122(a)(1)(B) § 60.18	No person may allow a vent gas stream containing VOC to be emitted from any process vent, unless the vent gas stream is burned properly in accordance with §115.122(a)(1) of this title.	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None
TCH-2	CD	60A-0004	Opacity	40 CFR Part 60, Subpart A	§ 60.18(b) § 60.18(c)(1) § 60.18(c)(2) § 60.18(c)(3)(ii) § 60.18(c)(4)(i) § 60.18(c)(6) § 60.18(e)	Flares shall comply with paragraphs (c)-(f) of § 60.18.	§ 60.18(d) § 60.18(f)(1) § 60.18(f)(2) § 60.18(f)(3) § 60.18(f)(4)	None	None
TCH-2	EU	60Ja-163		40 CFR Part 60, Subpart Ja	§ 60.100a(a) The permit holder shall comply with the applicable limitation,	The permit holder shall comply with the applicable requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable monitoring and testing	The permit holder shall comply with the applicable recordkeeping	The permit holder shall comply with the applicable reporting requirements of 40 CFR

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					standard and/or equipment specification requirements of 40 CFR Part 60, Subpart Ja		requirements of 40 CFR Part 60, Subpart Ja	requirements of 40 CFR Part 60, Subpart Ja	Part 60, Subpart Ja
TCH-2	CD	63A-0004	112(B) HAPS	40 CFR Part 63, Subpart A	§ 63.11(b)(4) § 63.11(b)(1) § 63.11(b)(2) § 63.11(b)(3) § 63.11(b)(5) § 63.11(b)(6)(ii) § 63.11(b)(7)(i)	Flares shall be designed and operated with no visible emissions, except for periods of a total of 5 minutes or less during any 2 consecutive hrs. Test Method 22 in App. A of part 60 of this chapter shall be used.	§ 63.11(b)(4) § 63.11(b)(5) § 63.11(b)(7)(i)	None	None
TCH-2	EP	63CC-1176	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.643(a) § 63.11(b) § 63.643(a)(1)	The owner or operator of a Group 1 miscellaneous process vent as defined in §63.641 shall comply with the requirements of either §63.643(a)(1)-(2).	§ 63.116(a)(2) § 63.116(a)(3) § 63.644(a) § 63.644(a)(2) § 63.644(c) § 63.644(c)(2) § 63.644(e) § 63.645(a) § 63.645(i) § 63.655(g)(6)(i) § 63.655(g)(6)(i)(B)	§ 63.642(e) § 63.655(h)(1) § 63.655(i)(5)	§ 63.642(f) [G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(ii) [G]§ 63.655(f)(1)(iv) [G]§ 63.655(f)(2) § 63.655(g) § 63.655(g)(6) § 63.655(g)(6)(ii) § 63.655(h) § 63.655(h)(1)
TCH-3	EU	R1111-0001	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(4)(A)	Visible emissions from a process gas flare shall not be permitted for more than five minutes in any two-hour period, except for emission event emissions as provided in §101.222(b).	§ 111.111(a)(4)(A)(i) § 111.111(a)(4)(A)(ii)	§ 111.111(a)(4)(A)(ii)	None
TCH-3	EP	R5720-0225	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Vent Gas	§ 115.722(d) § 115.722(d)(1) § 115.722(d)(2) [G]§ 115.725(d)(1)	All flares must continuously meet the requirements of 40 CFR § 60.18(c)(2)-(6) and (d) as amended through	[G]§ 115.725(d)(1) § 115.725(d)(2) § 115.725(d)(2)(A)(i) [G]§ 115.725(d)(2)(A)(ii)	§ 115.726(a)(1) § 115.726(a)(1)(A) § 115.726(d)(1) § 115.726(d)(10)	§ 115.725(n) § 115.726(a)(1)(B)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.725(d)(2) § 115.725(d)(2)(A)(i) [G]§ 115.725(d)(2)(A)(ii) § 115.725(d)(2)(A)(iii) § 115.725(d)(2)(A)(iv) § 115.725(d)(2)(B) § 115.725(d)(2)(B)(i) § 115.725(d)(2)(B)(ii) § 115.725(d)(2)(B)(iii) § 115.725(d)(2)(B)(iv) [G]§ 115.725(l) § 115.725(m)(2)(A) § 115.725(m)(2)(B)	October 17, 2000 (65 FR 61744) when vent gas containing HRVOC is being routed to the flare.	§ 115.725(d)(2)(A)(iii) § 115.725(d)(2)(A)(iv) § 115.725(d)(2)(B) § 115.725(d)(2)(B)(i) § 115.725(d)(2)(B)(ii) § 115.725(d)(2)(B)(iii) § 115.725(d)(2)(B)(iv) § 115.725(d)(3) § 115.725(d)(4) § 115.725(d)(5) § 115.725(d)(6) § 115.725(d)(7) § 115.725(k)(1) [G]§ 115.725(l) § 115.725(m)(1) § 115.725(m)(2)(A) § 115.725(m)(2)(B) § 115.725(n)	§ 115.726(d)(2) § 115.726(d)(3) § 115.726(d)(4) § 115.726(d)(7) § 115.726(d)(7)(A) § 115.726(d)(7)(B) § 115.726(d)(7)(C) § 115.726(i) § 115.726(j)(1) § 115.726(j)(2)	
TCH-3	EP	R5720-0505	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Vent Gas	§ 115.727(f) § 115.722(d) § 115.722(d)(1) § 115.722(d)(2)	All sites that are subject to this division and that are located in the Houston/Galveston/ Brazoria area as defined in §115.10 of this title (relating to Definitions), excluding Harris County, are exempt from § 115.722(b) and (c)(2) of this title, except as provided in § 115.729(a)(3) of this title (relating to Counties and Compliance Schedules).	§ 115.725(n)	§ 115.726(d)(1) § 115.726(d)(2) § 115.726(d)(3) § 115.726(d)(4) § 115.726(i) § 115.726(j)(1) § 115.726(j)(2)	§ 115.725(n)
TCH-3	EP	R5121-0016	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(1) § 115.122(a)(1) § 115.122(a)(1)(B) § 60.18	No person may allow a vent gas stream containing VOC to be emitted from any process vent, unless the vent gas stream is burned properly in accordance with	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						§115.122(a)(1) of this title.			
TCH-3	CD	60A-0004	Opacity	40 CFR Part 60, Subpart A	§ 60.18(b) § 60.18(c)(1) § 60.18(c)(2) § 60.18(c)(3)(ii) § 60.18(c)(4)(i) § 60.18(c)(6) § 60.18(e)	Flares shall comply with paragraphs (c)-(f) of § 60.18.	§ 60.18(d) § 60.18(f)(1) § 60.18(f)(2) § 60.18(f)(3) § 60.18(f)(4)	None	None
TCH-3	EU	60Ja-163		40 CFR Part 60, Subpart Ja	§ 60.100a(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 60, Subpart Ja
TCH-3	CD	63A-0004	112(B) HAPS	40 CFR Part 63, Subpart A	§ 63.11(b)(4) § 63.11(b)(1) § 63.11(b)(2) § 63.11(b)(3) § 63.11(b)(5) § 63.11(b)(6)(ii) § 63.11(b)(7)(i)	Flares shall be designed and operated with no visible emissions, except for periods of a total of 5 minutes or less during any 2 consecutive hrs. Test Method 22 in App. A of part 60 of this chapter shall be used.	§ 63.11(b)(4) § 63.11(b)(5) § 63.11(b)(7)(i)	None	None
TCH-3	EP	63CC-1176	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.643(a) § 63.11(b) § 63.643(a)(1) § 63.644(c)	The owner or operator of a Group 1 miscellaneous process vent as defined in §63.641 shall comply with the requirements of either §63.643(a)(1)-(2).	§ 63.116(a)(2) § 63.116(a)(3) § 63.644(a) § 63.644(a)(2) § 63.644(c)(2) § 63.644(e) § 63.645(a) § 63.645(i) § 63.655(g)(6)(i) § 63.655(g)(6)(i)(B)	§ 63.642(e) § 63.655(h)(1) § 63.655(i)(5)	§ 63.642(f) [G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(ii) [G]§ 63.655(f)(1)(iv) [G]§ 63.655(f)(2) § 63.655(g) § 63.655(g)(6) § 63.655(g)(6)(ii) § 63.655(h)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
									§ 63.655(h)(1)
TCH-4	EU	R1111-0001	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(4)(A)	Visible emissions from a process gas flare shall not be permitted for more than five minutes in any two-hour period, except for emission event emissions as provided in §101.222(b).	§ 111.111(a)(4)(A)(i) § 111.111(a)(4)(A)(ii)	§ 111.111(a)(4)(A)(ii)	None
TCH-4	EP	R5720-0225	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Vent Gas	§ 115.722(d) § 115.722(d)(1) § 115.722(d)(2) [G]§ 115.725(d)(1) § 115.725(d)(2) § 115.725(d)(2)(A)(i) [G]§ 115.725(d)(2)(A)(ii) § 115.725(d)(2)(A)(iii) § 115.725(d)(2)(A)(iv) § 115.725(d)(2)(B) § 115.725(d)(2)(B)(i) § 115.725(d)(2)(B)(ii) § 115.725(d)(2)(B)(iii) § 115.725(d)(2)(B)(iv) [G]§ 115.725(l) § 115.725(m)(2)(A) § 115.725(m)(2)(B)	All flares must continuously meet the requirements of 40 CFR § 60.18(c)(2)-(6) and (d) as amended through October 17, 2000 (65 FR 61744) when vent gas containing HRVOC is being routed to the flare.	[G]§ 115.725(d)(1) § 115.725(d)(2) § 115.725(d)(2)(A)(i) [G]§ 115.725(d)(2)(A)(ii) § 115.725(d)(2)(A)(iii) § 115.725(d)(2)(A)(iv) § 115.725(d)(2)(B) § 115.725(d)(2)(B)(i) § 115.725(d)(2)(B)(ii) § 115.725(d)(2)(B)(iii) § 115.725(d)(2)(B)(iv) § 115.725(d)(3) § 115.725(d)(4) § 115.725(d)(5) § 115.725(d)(6) § 115.725(d)(7) § 115.725(k)(1) [G]§ 115.725(l) § 115.725(m)(1) § 115.725(m)(2)(A) § 115.725(m)(2)(B) § 115.725(n)	§ 115.726(a)(1) § 115.726(a)(1)(A) § 115.726(d)(1) § 115.726(d)(10) § 115.726(d)(2) § 115.726(d)(3) § 115.726(d)(4) § 115.726(d)(7) § 115.726(d)(7)(A) § 115.726(d)(7)(B) § 115.726(d)(7)(C) § 115.726(i) § 115.726(j)(1) § 115.726(j)(2)	§ 115.725(n) § 115.726(a)(1)(B)
TCH-4	EP	R5720-0505	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Vent Gas	§ 115.727(f) § 115.722(d) § 115.722(d)(1) § 115.722(d)(2)	All sites that are subject to this division and that are located in the Houston/Galveston/ Brazoria area as defined in §115.10 of this title (relating to Definitions), excluding Harris County, are exempt	§ 115.725(n)	§ 115.726(d)(1) § 115.726(d)(2) § 115.726(d)(3) § 115.726(d)(4) § 115.726(i) § 115.726(j)(1) § 115.726(j)(2)	§ 115.725(n)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						from § 115.722(b) and (c)(2) of this title, except as provided in § 115.729(a)(3) of this title (relating to Counties and Compliance Schedules).			
TCH-4	EP	R5121-0016	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(1) § 115.122(a)(1) § 115.122(a)(1)(B) § 60.18	No person may allow a vent gas stream containing VOC to be emitted from any process vent, unless the vent gas stream is burned properly in accordance with §115.122(a)(1) of this title.	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None
TCH-4	CD	60A-0004	Opacity	40 CFR Part 60, Subpart A	§ 60.18(b) § 60.18(c)(1) § 60.18(c)(2) § 60.18(c)(3)(ii) § 60.18(c)(4)(i) § 60.18(c)(6) § 60.18(e)	Flares shall comply with paragraphs (c)-(f) of § 60.18.	§ 60.18(d) § 60.18(f)(1) § 60.18(f)(2) § 60.18(f)(3) § 60.18(f)(4)	None	None
TCH-4	EU	60Ja-163		40 CFR Part 60, Subpart Ja	§ 60.100a(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 60, Subpart Ja
TCH-4	CD	63A-0004	112(B) HAPS	40 CFR Part 63, Subpart A	§ 63.11(b)(4) § 63.11(b)(1) § 63.11(b)(2) § 63.11(b)(3) § 63.11(b)(5) § 63.11(b)(6)(ii) § 63.11(b)(7)(i)	Flares shall be designed and operated with no visible emissions, except for periods of a total of 5 minutes or less during any 2 consecutive hrs. Test Method 22 in App. A of part	§ 63.11(b)(4) § 63.11(b)(5) § 63.11(b)(7)(i)	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						60 of this chapter shall be used.			
TCH-4	EP	63CC-1176	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.643(a) § 63.11(b) § 63.643(a)(1)	The owner or operator of a Group 1 miscellaneous process vent as defined in §63.641 shall comply with the requirements of either §63.643(a)(1)-(2).	§ 63.116(a)(2) § 63.116(a)(3) § 63.644(a) § 63.644(a)(2) § 63.644(c) § 63.644(c)(2) § 63.644(e) § 63.645(a) § 63.645(i) § 63.655(g)(6)(i) § 63.655(g)(6)(i)(B)	§ 63.642(e) § 63.655(h)(1) § 63.655(i)(5)	§ 63.642(f) [G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(ii) [G]§ 63.655(f)(1)(iv) [G]§ 63.655(f)(2) § 63.655(g) § 63.655(g)(6) § 63.655(g)(6)(ii) § 63.655(h) § 63.655(h)(1)
TCH-6	EU	R1111-0001	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(4)(A)	Visible emissions from a process gas flare shall not be permitted for more than five minutes in any two-hour period, except for upset emissions as provided in §101.222(b).	§ 111.111(a)(4)(A)(i) § 111.111(a)(4)(A)(ii)	§ 111.111(a)(4)(A)(ii)	None
TCH-6	EP	R5720-0505	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Vent Gas	§ 115.727(f) § 115.722(d) § 115.722(d)(1) § 115.722(d)(2)	All sites that are subject to this division and that are located in the Houston/Galveston/ Brazoria area as defined in §115.10 of this title (relating to Definitions), excluding Harris County, are exempt from § 115.722(b) and (c)(2) of this title, except as provided in § 115.729(a)(3) of this title (relating to Counties and Compliance Schedules).	§ 115.725(n)	§ 115.726(d)(1) § 115.726(d)(2) § 115.726(d)(3) § 115.726(d)(4) § 115.726(i) § 115.726(j)(1) § 115.726(j)(2)	§ 115.725(n)
TCH-6	EP	R5726.0016AMOC	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Vent Gas	§ 115.722(d) § 115.722(d)(1) § 115.722(d)(2)	All flares must continuously meet the requirements of 40 CFR § 60.18(c)(2)-(6) and	[G]§ 115.725(d)(1) § 115.725(d)(2) § 115.725(d)(2)(A)(i)	§ 115.726(a)(1) § 115.726(a)(1)(A) § 115.726(d)(1)	§ 115.725(n) § 115.726(a)(1)(B) [G]§ 115.726(a)(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 115.725(d)(1) § 115.725(d)(2) § 115.725(d)(2)(A)(i) [G]§ 115.725(d)(2)(A)(ii) § 115.725(d)(2)(A)(iii) § 115.725(d)(2)(A)(iv) § 115.725(d)(2)(B) § 115.725(d)(2)(B)(i) § 115.725(d)(2)(B)(ii) § 115.725(d)(2)(B)(iii) § 115.725(d)(2)(B)(iv) [G]§ 115.725(l) § 115.725(m)(2)(A) § 115.725(m)(2)(B) [G]§ 115.726(a)(2)	(d) as amended through October 17, 2000 (65 FR 61744) when vent gas containing HRVOC is being routed to the flare.	[G]§ 115.725(d)(2)(A)(ii) § 115.725(d)(2)(A)(iii) § 115.725(d)(2)(A)(iv) § 115.725(d)(2)(B) § 115.725(d)(2)(B)(i) § 115.725(d)(2)(B)(ii) § 115.725(d)(2)(B)(iii) § 115.725(d)(2)(B)(iv) § 115.725(d)(3) § 115.725(d)(4) § 115.725(d)(5) § 115.725(d)(6) § 115.725(d)(7) § 115.725(k)(1) [G]§ 115.725(l) § 115.725(m) § 115.725(m)(1) § 115.725(m)(2)(A) § 115.725(m)(2)(B) § 115.725(n) See Alternative Requirement	§ 115.726(d)(10) § 115.726(d)(2) § 115.726(d)(3) § 115.726(d)(4) § 115.726(i) § 115.726(j)(1) § 115.726(j)(2)	
TCH-6	EU	R5313-0016AMOC	VOC	30 TAC Chapter 115, Unit Turn & Vac System-Pet Ref	§ 115.313(a) § 115.910	For Beaumont/Port Arthur, Dallas/Fort Worth, El Paso, and Houston/Galveston areas, alternate methods of compliance with applicable control requirements may be approved in accordance with §115.910.	See Alternative Requirement	None	None
TCH-6	EP	R5121-0016AMOC	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.123(a)(1) § 115.910	Alternate methods of demonstrating and documenting continuous compliance with the applicable control requirements or exemption criteria in this division may be approved by the	[G]§ 115.125 § 115.126(2) See Alternative Requirement ** See Periodic Monitoring Summary	§ 115.126 § 115.126(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						Executive Director in accordance with §115.910 of this title if emission reduction are demonstrated to be substantially equivalent.			
TCH-6	CD	60A-0003	Opacity	40 CFR Part 60, Subpart A	§ 60.18(b) § 60.18(c)(1) § 60.18(c)(2) § 60.18(c)(3)(ii) § 60.18(c)(5) § 60.18(c)(6) § 60.18(e) § 60.18(f)(4)	Flares shall comply with paragraphs (c)-(f) of § 60.18.	§ 60.18(d) § 60.18(f)(1) § 60.18(f)(2) § 60.18(f)(3) § 60.18(f)(6)	None	None
TCH-6	EU	60Ja-164		40 CFR Part 60, Subpart Ja	§ 60.100a(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 60, Subpart Ja
TCH-6	CD	63A-0003	112(B) HAPS	40 CFR Part 63, Subpart A	§ 63.11(b)(4) § 63.11(b)(1) § 63.11(b)(2) § 63.11(b)(3) § 63.11(b)(5) § 63.11(b)(6)(ii) § 63.11(b)(7)(i) § 63.11(b)(8)	Flares shall be designed and operated with no visible emissions, except for periods of a total of 5 minutes or less during any 2 consecutive hrs. Test Method 22 in App. A of part 60 of this chapter shall be used.	§ 63.11(b)(4) § 63.11(b)(5)	None	None
TCH-6	EP	63CC-1176	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation,	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing	The permit holder shall comply with the applicable recordkeeping	The permit holder shall comply with the applicable reporting requirements of 40 CFR

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC		requirements of 40 CFR Part 63, Subpart CC	requirements of 40 CFR Part 63, Subpart CC	Part 63, Subpart CC
TCH-8	EU	R1111-0001	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(4)(A)	Visible emissions from a process gas flare shall not be permitted for more than five minutes in any two-hour period, except for emission event emissions as provided in §101.222(b).	§ 111.111(a)(4)(A)(i) § 111.111(a)(4)(A)(ii)	§ 111.111(a)(4)(A)(ii)	None
TCH-8	EP	R5720-0225	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Vent Gas	§ 115.722(d) § 115.722(d)(1) § 115.722(d)(2) [G]§ 115.725(d)(1) § 115.725(d)(2) § 115.725(d)(2)(A)(i) [G]§ 115.725(d)(2)(A)(ii) § 115.725(d)(2)(A)(iii) § 115.725(d)(2)(A)(iv) § 115.725(d)(2)(B) § 115.725(d)(2)(B)(i) § 115.725(d)(2)(B)(ii) § 115.725(d)(2)(B)(iii) § 115.725(d)(2)(B)(iv) [G]§ 115.725(l) § 115.725(m)(2)(A) § 115.725(m)(2)(B)	All flares must continuously meet the requirements of 40 CFR § 60.18(c)(2)-(6) and (d) as amended through October 17, 2000 (65 FR 61744) when vent gas containing HRVOC is being routed to the flare.	[G]§ 115.725(d)(1) § 115.725(d)(2) § 115.725(d)(2)(A)(i) [G]§ 115.725(d)(2)(A)(ii) § 115.725(d)(2)(A)(iii) § 115.725(d)(2)(A)(iv) § 115.725(d)(2)(B) § 115.725(d)(2)(B)(i) § 115.725(d)(2)(B)(ii) § 115.725(d)(2)(B)(iii) § 115.725(d)(2)(B)(iv) § 115.725(d)(3) § 115.725(d)(4) § 115.725(d)(5) § 115.725(d)(6) § 115.725(d)(7) § 115.725(k)(1) [G]§ 115.725(l) § 115.725(m)(1) § 115.725(m)(2)(A) § 115.725(m)(2)(B) § 115.725(n)	§ 115.726(a)(1) § 115.726(a)(1)(A) § 115.726(d)(1) § 115.726(d)(10) § 115.726(d)(2) § 115.726(d)(3) § 115.726(d)(4) § 115.726(d)(7) § 115.726(d)(7)(A) § 115.726(d)(7)(B) § 115.726(d)(7)(C) § 115.726(i) § 115.726(j)(1) § 115.726(j)(2)	§ 115.725(n) § 115.726(a)(1)(B)
TCH-8	EP	R5720-0505	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Vent Gas	§ 115.727(f) § 115.722(d) § 115.722(d)(1)	All sites that are subject to this division and that are located in the	§ 115.725(n)	§ 115.726(d)(1) § 115.726(d)(2) § 115.726(d)(3)	§ 115.725(n)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.722(d)(2)	Houston/Galveston/ Brazoria area as defined in §115.10 of this title (relating to Definitions), excluding Harris County, are exempt from § 115.722(b) and (c)(2) of this title, except as provided in § 115.729(a)(3) of this title (relating to Counties and Compliance Schedules).		§ 115.726(d)(4) § 115.726(i) § 115.726(j)(1) § 115.726(j)(2)	
TCH-8	EP	R5121-0016	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(1) § 115.122(a)(1) § 115.122(a)(1)(B) § 60.18	No person may allow a vent gas stream containing VOC to be emitted from any process vent, unless the vent gas stream is burned properly in accordance with §115.122(a)(1) of this title.	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None
TCH-8	CD	60A-0004	Opacity	40 CFR Part 60, Subpart A	§ 60.18(b) § 60.18(c)(1) § 60.18(c)(2) § 60.18(c)(3)(ii) § 60.18(c)(4)(i) § 60.18(c)(6) § 60.18(e)	Flares shall comply with paragraphs (c)-(f) of § 60.18.	§ 60.18(d) § 60.18(f)(1) § 60.18(f)(2) § 60.18(f)(3) § 60.18(f)(4)	None	None
TCH-8	EU	60Ja-163		40 CFR Part 60, Subpart Ja	§ 60.100a(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 60, Subpart Ja
TCH-8	CD	63A-0004	112(B) HAPS	40 CFR Part 63, Subpart A	§ 63.11(b)(4) § 63.11(b)(1)	Flares shall be designed and operated with no visible	§ 63.11(b)(4) § 63.11(b)(5)	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.11(b)(2) § 63.11(b)(3) § 63.11(b)(5) § 63.11(b)(6)(ii) § 63.11(b)(7)(i)	emissions, except for periods of a total of 5 minutes or less during any 2 consecutive hrs. Test Method 22 in App. A of part 60 of this chapter shall be used.	§ 63.11(b)(7)(i)		
TCH-8	EP	63CC-1176	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.643(a) § 63.11(b) § 63.643(a)(1)	The owner or operator of a Group 1 miscellaneous process vent as defined in §63.641 shall comply with the requirements of either §63.643(a)(1)-(2).	§ 63.116(a)(2) § 63.116(a)(3) § 63.644(a) § 63.644(a)(2) § 63.644(c) § 63.644(c)(2) § 63.644(e) § 63.645(a) § 63.645(i) § 63.655(g)(6)(i) § 63.655(g)(6)(i)(B)	§ 63.642(e) § 63.655(h)(1) § 63.655(i)(5)	§ 63.642(f) [G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(ii) [G]§ 63.655(f)(1)(iv) [G]§ 63.655(f)(2) § 63.655(g) § 63.655(g)(6) § 63.655(g)(6)(ii) § 63.655(h) § 63.655(h)(1)
TCH-AU2	EU	R1111-0001	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(4)(A)	Visible emissions from a process gas flare shall not be permitted for more than five minutes in any two-hour period, except for emission event emissions as provided in §101.222(b).	§ 111.111(a)(4)(A)(i) § 111.111(a)(4)(A)(ii)	§ 111.111(a)(4)(A)(ii)	None
TCH-AU2	EP	R5121-0016	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(1) § 115.122(a)(1) § 115.122(a)(1)(B) § 60.18	No person may allow a vent gas stream containing VOC to be emitted from any process vent, unless the vent gas stream is burned properly in accordance with §115.122(a)(1) of this title.	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None
TCH-AU2	CD	60A-0004	Opacity	40 CFR Part 60, Subpart A	§ 60.18(b) § 60.18(c)(1) § 60.18(c)(2) § 60.18(c)(3)(ii) § 60.18(c)(4)(i)	Flares shall comply with paragraphs (c)-(f) of § 60.18.	§ 60.18(d) § 60.18(f)(1) § 60.18(f)(2) § 60.18(f)(3) § 60.18(f)(4)	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.18(c)(6) § 60.18(e)				
TCH-AU2	EU	60Ja-163		40 CFR Part 60, Subpart Ja	§ 60.100a(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 60, Subpart Ja
TCH-AU2	CD	63A-0004	112(B) HAPS	40 CFR Part 63, Subpart A	§ 63.11(b)(4) § 63.11(b)(1) § 63.11(b)(2) § 63.11(b)(3) § 63.11(b)(5) § 63.11(b)(6)(ii) § 63.11(b)(7)(i)	Flares shall be designed and operated with no visible emissions, except for periods of a total of 5 minutes or less during any 2 consecutive hrs. Test Method 22 in App. A of part 60 of this chapter shall be used.	§ 63.11(b)(4) § 63.11(b)(5) § 63.11(b)(7)(i)	None	None
TCH-AU2	EP	63G-0330	112(B) HAPS	40 CFR Part 63, Subpart G	[G]§ 63.113(a)(1) § 63.11 § 63.113(h) [G]§ 63.115(f)	Reduce emissions of organic HAP using a flare.§63.113(a)(1)(i)-(ii)	§ 63.114(a) § 63.114(a)(2) [G]§ 63.115(f) [G]§ 63.116(a)	[G]§ 63.117(a)(5) § 63.118(a)(1) § 63.118(a)(2) [G]§ 63.152(a) [G]§ 63.152(f)	§ 63.114(e) [G]§ 63.117(a)(5) § 63.117(f) § 63.118(f)(2) § 63.118(f)(5) [G]§ 63.151(b) § 63.151(e) [G]§ 63.151(e)(1) § 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) [G]§ 63.152(b)(2) § 63.152(c)(1) § 63.152(c)(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
									§ 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
TCH-CFHU	EU	R1111-0001	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(4)(A)	Visible emissions from a process gas flare shall not be permitted for more than five minutes in any two-hour period, except for emission event emissions as provided in §101.222(b).	§ 111.111(a)(4)(A)(i) § 111.111(a)(4)(A)(ii)	§ 111.111(a)(4)(A)(ii)	None
TCH-CFHU	EP	R5720-0225	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Vent Gas	§ 115.722(d) § 115.722(d)(1) § 115.722(d)(2) [G]§ 115.725(d)(1) § 115.725(d)(2) § 115.725(d)(2)(A)(i) [G]§ 115.725(d)(2)(A)(ii) § 115.725(d)(2)(A)(iii) § 115.725(d)(2)(A)(iv) § 115.725(d)(2)(B) § 115.725(d)(2)(B)(i) § 115.725(d)(2)(B)(ii) § 115.725(d)(2)(B)(iii) § 115.725(d)(2)(B)(iv) [G]§ 115.725(l) § 115.725(m)(2)(A) § 115.725(m)(2)(B)	All flares must continuously meet the requirements of 40 CFR § 60.18(c)(2)-(6) and (d) as amended through October 17, 2000 (65 FR 61744) when vent gas containing HRVOC is being routed to the flare.	[G]§ 115.725(d)(1) § 115.725(d)(2) § 115.725(d)(2)(A)(i) [G]§ 115.725(d)(2)(A)(ii) § 115.725(d)(2)(A)(iii) § 115.725(d)(2)(A)(iv) § 115.725(d)(2)(B) § 115.725(d)(2)(B)(i) § 115.725(d)(2)(B)(ii) § 115.725(d)(2)(B)(iii) § 115.725(d)(2)(B)(iv) § 115.725(d)(3) § 115.725(d)(4) § 115.725(d)(5) § 115.725(d)(6) § 115.725(d)(7) § 115.725(k)(1) [G]§ 115.725(l) § 115.725(m)(1) § 115.725(m)(2)(A) § 115.725(m)(2)(B) § 115.725(n)	§ 115.726(a)(1) § 115.726(a)(1)(A) § 115.726(d)(1) § 115.726(d)(10) § 115.726(d)(2) § 115.726(d)(3) § 115.726(d)(4) § 115.726(d)(7) § 115.726(d)(7)(A) § 115.726(d)(7)(B) § 115.726(d)(7)(C) § 115.726(i) § 115.726(j)(1) § 115.726(j)(2)	§ 115.725(n) § 115.726(a)(1)(B)
TCH-CFHU	EP	R5720-0505	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Vent Gas	§ 115.727(f) § 115.722(d) § 115.722(d)(1) § 115.722(d)(2)	All sites that are subject to this division and that are located in the Houston/Galveston/	§ 115.725(n)	§ 115.726(d)(1) § 115.726(d)(2) § 115.726(d)(3) § 115.726(d)(4)	§ 115.725(n)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						Brazoria area as defined in §115.10 of this title (relating to Definitions), excluding Harris County, are exempt from § 115.722(b) and (c)(2) of this title, except as provided in § 115.729(a)(3) of this title (relating to Counties and Compliance Schedules).		§ 115.726(i) § 115.726(j)(1) § 115.726(j)(2)	
TCH-CFHU	EP	R5121-0016	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(1) § 115.122(a)(1) § 115.122(a)(1)(B) § 60.18	No person may allow a vent gas stream containing VOC to be emitted from any process vent, unless the vent gas stream is burned properly in accordance with §115.122(a)(1) of this title.	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None
TCH-CFHU	CD	60A-0004	Opacity	40 CFR Part 60, Subpart A	§ 60.18(b) § 60.18(c)(1) § 60.18(c)(2) § 60.18(c)(3)(ii) § 60.18(c)(4)(i) § 60.18(c)(6) § 60.18(e)	Flares shall comply with paragraphs (c)-(f) of § 60.18.	§ 60.18(d) § 60.18(f)(1) § 60.18(f)(2) § 60.18(f)(3) § 60.18(f)(4)	None	None
TCH-CFHU	EU	60Ja-163		40 CFR Part 60, Subpart Ja	§ 60.100a(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 60, Subpart Ja
TCH-CFHU	CD	63A-0004	112(B) HAPS	40 CFR Part 63, Subpart A	§ 63.11(b)(4) § 63.11(b)(1) § 63.11(b)(2)	Flares shall be designed and operated with no visible emissions, except for	§ 63.11(b)(4) § 63.11(b)(5) § 63.11(b)(7)(i)	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.11(b)(3) § 63.11(b)(5) § 63.11(b)(6)(ii) § 63.11(b)(7)(i)	periods of a total of 5 minutes or less during any 2 consecutive hrs. Test Method 22 in App. A of part 60 of this chapter shall be used.			
TCH-CFHU	EP	63CC-1176	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.643(a) § 63.11(b) § 63.643(a)(1)	The owner or operator of a Group 1 miscellaneous process vent as defined in §63.641 shall comply with the requirements of either §63.643(a)(1)-(2).	§ 63.116(a)(2) § 63.116(a)(3) § 63.644(a) § 63.644(a)(2) § 63.644(c) § 63.644(c)(2) § 63.644(e) § 63.645(a) § 63.645(i) § 63.655(g)(6)(i) § 63.655(g)(6)(i)(B)	§ 63.642(e) § 63.655(h)(1) § 63.655(i)(5)	§ 63.642(f) [G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(ii) [G]§ 63.655(f)(1)(iv) [G]§ 63.655(f)(2) § 63.655(g) § 63.655(g)(6) § 63.655(g)(6)(ii) § 63.655(h) § 63.655(h)(1)
TCH-DDU	EU	R1111-0001	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(4)(A)	Visible emissions from a process gas flare shall not be permitted for more than five minutes in any two-hour period, except for emission event emissions as provided in §101.222(b).	§ 111.111(a)(4)(A)(i) § 111.111(a)(4)(A)(ii)	§ 111.111(a)(4)(A)(ii)	None
TCH-DDU	EP	R5720-0225	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Vent Gas	§ 115.722(d) § 115.722(d)(1) § 115.722(d)(2) [G]§ 115.725(d)(1) § 115.725(d)(2) § 115.725(d)(2)(A)(i) [G]§ 115.725(d)(2)(A)(ii) § 115.725(d)(2)(A)(iii) § 115.725(d)(2)(A)(iv) § 115.725(d)(2)(B) § 115.725(d)(2)(B)(i) § 115.725(d)(2)(B)(ii) § 115.725(d)(2)(B)(iii)	All flares must continuously meet the requirements of 40 CFR § 60.18(c)(2)-(6) and (d) as amended through October 17, 2000 (65 FR 61744) when vent gas containing HRVOC is being routed to the flare.	[G]§ 115.725(d)(1) § 115.725(d)(2) § 115.725(d)(2)(A)(i) [G]§ 115.725(d)(2)(A)(ii) § 115.725(d)(2)(A)(iii) § 115.725(d)(2)(A)(iv) § 115.725(d)(2)(B) § 115.725(d)(2)(B)(i) § 115.725(d)(2)(B)(ii) § 115.725(d)(2)(B)(iii) § 115.725(d)(2)(B)(iv) § 115.725(d)(3) § 115.725(d)(4) § 115.725(d)(5)	§ 115.726(a)(1) § 115.726(a)(1)(A) § 115.726(d)(1) § 115.726(d)(10) § 115.726(d)(2) § 115.726(d)(3) § 115.726(d)(4) § 115.726(d)(7) § 115.726(d)(7)(A) § 115.726(d)(7)(B) § 115.726(d)(7)(C) § 115.726(i) § 115.726(j)(1) § 115.726(j)(2)	§ 115.725(n) § 115.726(a)(1)(B)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.725(d)(2)(B)(iv) [G]§ 115.725(l) § 115.725(m)(2)(A) § 115.725(m)(2)(B)		§ 115.725(d)(6) § 115.725(d)(7) § 115.725(k)(1) [G]§ 115.725(l) § 115.725(m)(1) § 115.725(m)(2)(A) § 115.725(m)(2)(B) § 115.725(n)		
TCH-DDU	EP	R5720-0505	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Vent Gas	§ 115.727(f) § 115.722(d) § 115.722(d)(1) § 115.722(d)(2)	All sites that are subject to this division and that are located in the Houston/Galveston/ Brazoria area as defined in §115.10 of this title (relating to Definitions), excluding Harris County, are exempt from § 115.722(b) and (c)(2) of this title, except as provided in § 115.729(a)(3) of this title (relating to Counties and Compliance Schedules).	§ 115.725(n)	§ 115.726(d)(1) § 115.726(d)(2) § 115.726(d)(3) § 115.726(d)(4) § 115.726(i) § 115.726(j)(1) § 115.726(j)(2)	§ 115.725(n)
TCH-DDU	EP	R5121-0016	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(1) § 115.122(a)(1) § 115.122(a)(1)(B) § 60.18	No person may allow a vent gas stream containing VOC to be emitted from any process vent, unless the vent gas stream is burned properly in accordance with §115.122(a)(1) of this title.	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None
TCH-DDU	CD	60A-0004	Opacity	40 CFR Part 60, Subpart A	§ 60.18(b) § 60.18(c)(1) § 60.18(c)(2) § 60.18(c)(3)(ii) § 60.18(c)(4)(i) § 60.18(c)(6) § 60.18(e)	Flares shall comply with paragraphs (c)-(f) of § 60.18.	§ 60.18(d) § 60.18(f)(1) § 60.18(f)(2) § 60.18(f)(3) § 60.18(f)(4)	None	None
TCH-DDU	EU	60Ja-163		40 CFR Part 60,	§ 60.100a(a)	The permit holder shall	The permit holder shall	The permit holder	The permit holder shall

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Subpart Ja	The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 60, Subpart Ja	comply with the applicable requirements of 40 CFR Part 60, Subpart Ja	comply with the applicable monitoring and testing requirements of 40 CFR Part 60, Subpart Ja	shall comply with the applicable recordkeeping requirements of 40 CFR Part 60, Subpart Ja	comply with the applicable reporting requirements of 40 CFR Part 60, Subpart Ja
TCH-DDU	CD	63A-0004	112(B) HAPS	40 CFR Part 63, Subpart A	§ 63.11(b)(4) § 63.11(b)(1) § 63.11(b)(2) § 63.11(b)(3) § 63.11(b)(5) § 63.11(b)(6)(ii) § 63.11(b)(7)(i)	Flares shall be designed and operated with no visible emissions, except for periods of a total of 5 minutes or less during any 2 consecutive hrs. Test Method 22 in App. A of part 60 of this chapter shall be used.	§ 63.11(b)(4) § 63.11(b)(5) § 63.11(b)(7)(i)	None	None
TCH-DDU	EP	63CC-1176	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.643(a) § 63.11(b) § 63.643(a)(1)	The owner or operator of a Group 1 miscellaneous process vent as defined in §63.641 shall comply with the requirements of either §63.643(a)(1)-(2).	§ 63.116(a)(2) § 63.116(a)(3) § 63.644(a) § 63.644(a)(2) § 63.644(c) § 63.644(c)(2) § 63.644(e) § 63.645(a) § 63.645(i) § 63.655(g)(6)(i) § 63.655(g)(6)(i)(B)	§ 63.642(e) § 63.655(h)(1) § 63.655(i)(5)	§ 63.642(f) [G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(ii) [G]§ 63.655(f)(1)(iv) [G]§ 63.655(f)(2) § 63.655(g) § 63.655(g)(6) § 63.655(g)(6)(ii) § 63.655(h) § 63.655(h)(1)
TCH-ULC	EU	R1111-0001	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(4)(A)	Visible emissions from a process gas flare shall not be permitted for more than five minutes in any two-hour period, except for emission event emissions as provided in §101.222(b).	§ 111.111(a)(4)(A)(i) § 111.111(a)(4)(A)(ii)	§ 111.111(a)(4)(A)(ii)	None
TCH-ULC	EP	R5720-	Highly	30 TAC Chapter	§ 115.722(d)	All flares must continuously	[G]§ 115.725(d)(1)	§ 115.726(a)(1)	§ 115.725(n)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		0225	Reactive VOC	115, HRVOC Vent Gas	§ 115.722(d)(1) § 115.722(d)(2) [G]§ 115.725(d)(1) § 115.725(d)(2) § 115.725(d)(2)(A)(i) [G]§ 115.725(d)(2)(A)(ii) § 115.725(d)(2)(A)(iii) § 115.725(d)(2)(A)(iv) § 115.725(d)(2)(B) § 115.725(d)(2)(B)(i) § 115.725(d)(2)(B)(ii) § 115.725(d)(2)(B)(iii) § 115.725(d)(2)(B)(iv) [G]§ 115.725(l) § 115.725(m)(2)(A) § 115.725(m)(2)(B)	meet the requirements of 40 CFR § 60.18(c)(2)-(6) and (d) as amended through October 17, 2000 (65 FR 61744) when vent gas containing HRVOC is being routed to the flare.	§ 115.725(d)(2) § 115.725(d)(2)(A)(i) [G]§ 115.725(d)(2)(A)(ii) § 115.725(d)(2)(A)(iii) § 115.725(d)(2)(A)(iv) § 115.725(d)(2)(B) § 115.725(d)(2)(B)(i) § 115.725(d)(2)(B)(ii) § 115.725(d)(2)(B)(iii) § 115.725(d)(2)(B)(iv) § 115.725(d)(3) § 115.725(d)(4) § 115.725(d)(5) § 115.725(d)(6) § 115.725(d)(7) § 115.725(k)(1) [G]§ 115.725(l) § 115.725(m)(1) § 115.725(m)(2)(A) § 115.725(m)(2)(B) § 115.725(n)	§ 115.726(a)(1)(A) § 115.726(d)(1) § 115.726(d)(10) § 115.726(d)(2) § 115.726(d)(3) § 115.726(d)(4) § 115.726(d)(7) § 115.726(d)(7)(A) § 115.726(d)(7)(B) § 115.726(d)(7)(C) § 115.726(i) § 115.726(j)(1) § 115.726(j)(2)	§ 115.726(a)(1)(B)
TCH-ULC	EP	R5720-0505	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Vent Gas	§ 115.727(f) § 115.722(d) § 115.722(d)(1) § 115.722(d)(2)	All sites that are subject to this division and that are located in the Houston/Galveston/ Brazoria area as defined in §115.10 of this title (relating to Definitions), excluding Harris County, are exempt from § 115.722(b) and (c)(2) of this title, except as provided in § 115.729(a)(3) of this title (relating to Counties and Compliance Schedules).	§ 115.725(n)	§ 115.726(d)(1) § 115.726(d)(2) § 115.726(d)(3) § 115.726(d)(4) § 115.726(i) § 115.726(j)(1) § 115.726(j)(2)	§ 115.725(n)
TCH-ULC	EP	R5121-0016	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(1) § 115.122(a)(1) § 115.122(a)(1)(B)	No person may allow a vent gas stream containing VOC to be emitted from any	[G]§ 115.125 § 115.126(1) § 115.126(1)(B)	§ 115.126 § 115.126(1) § 115.126(1)(B)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.18	process vent, unless the vent gas stream is burned properly in accordance with §115.122(a)(1) of this title.	§ 115.126(2)	§ 115.126(2)	
TCH-ULC	CD	60A-0004	Opacity	40 CFR Part 60, Subpart A	§ 60.18(b) § 60.18(c)(1) § 60.18(c)(2) § 60.18(c)(3)(ii) § 60.18(c)(4)(i) § 60.18(c)(6) § 60.18(e)	Flares shall comply with paragraphs (c)-(f) of § 60.18.	§ 60.18(d) § 60.18(f)(1) § 60.18(f)(2) § 60.18(f)(3) § 60.18(f)(4)	None	None
TCH-ULC	EU	60Ja-163		40 CFR Part 60, Subpart Ja	§ 60.100a(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 60, Subpart Ja
TCH-ULC	CD	63A-0004	112(B) HAPS	40 CFR Part 63, Subpart A	§ 63.11(b)(4) § 63.11(b)(1) § 63.11(b)(2) § 63.11(b)(3) § 63.11(b)(5) § 63.11(b)(6)(ii) § 63.11(b)(7)(i)	Flares shall be designed and operated with no visible emissions, except for periods of a total of 5 minutes or less during any 2 consecutive hrs. Test Method 22 in App. A of part 60 of this chapter shall be used.	§ 63.11(b)(4) § 63.11(b)(5) § 63.11(b)(7)(i)	None	None
TCH-ULC	EP	63CC-1176	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.643(a) § 63.11(b) § 63.643(a)(1)	The owner or operator of a Group 1 miscellaneous process vent as defined in §63.641 shall comply with the requirements of either §63.643(a)(1)-(2).	§ 63.116(a)(2) § 63.116(a)(3) § 63.644(a) § 63.644(a)(2) § 63.644(c) § 63.644(c)(2) § 63.644(e)	§ 63.642(e) § 63.655(h)(1) § 63.655(i)(5)	§ 63.642(f) [G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(ii) [G]§ 63.655(f)(1)(iv) [G]§ 63.655(f)(2) § 63.655(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 63.645(a) § 63.645(i) § 63.655(g)(6)(i) § 63.655(g)(6)(i)(B)		§ 63.655(g)(6) § 63.655(g)(6)(ii) § 63.655(h) § 63.655(h)(1)
TDU-BH	EP	R1111-0112	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(B) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall not exceed an opacity of 20% averaged over a six minute period for any source on which construction was begun after January 31, 1972.	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None
TDU-BH	EP	R5121-0003	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) equal to or less than 100 pounds in any continuous 24-hour period is exempt from §115.121(a)(1) of this title.	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
TDU-CONVEYOR	EP	R1111-0113	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(B) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall not exceed an opacity of 20% averaged over a six minute period for any source on which construction was begun after January 31, 1972.	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None
TDU-CT	EP	R1111-0112	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(B) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall not exceed an opacity of 20% averaged over a six minute period for any source on which construction was begun after January 31, 1972.	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
TDU-DRYER	EP	R1111-0112	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(B) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall not exceed an opacity of 20% averaged over a six minute period for any source on which construction was begun after January 31, 1972.	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None
TDU-DRYER	EP	R5121-0003	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) equal to or less than 100 pounds in any continuous 24-hour period is exempt from §115.121(a)(1) of this title.	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
TDU-FUG	EU	63EEEE-4	112(B) HAPS	40 CFR Part 63, Subpart EEEE	§ 63.2338(b) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart EEEE	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart EEEE
TDU-OWS	EU	R5131-0011	VOC	30 TAC Chapter 115, Water Separation	§ 115.132(a)(3) § 115.131(a)	VOC water separator compartments must be equipped with a vapor recovery system which satisfies the provisions of §115.131(a) of this title.	[G]§ 115.135(a) § 115.136(a)(2) § 115.136(a)(2)(A) § 115.136(a)(3) § 115.136(a)(4)	§ 115.136(a)(2) § 115.136(a)(2)(A) § 115.136(a)(3) § 115.136(a)(4)	None
TDU-OWS	EU	R5131-0012	VOC	30 TAC Chapter 115, Water Separation	§ 115.132(a)(3) § 115.131(a)	VOC water separator compartments must be equipped with a vapor recovery system which satisfies the provisions of	[G]§ 115.135(a) § 115.136(a)(2) § 115.136(a)(2)(C) § 115.136(a)(3) § 115.136(a)(4)	§ 115.136(a)(2) § 115.136(a)(2)(C) § 115.136(a)(3) § 115.136(a)(4)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						§115.131(a) of this title.			
TDU-OWS	EU	61FF-1782	Benzene	40 CFR Part 61, Subpart FF	§ 61.347(a)(1) § 61.347(a)(1)(i)(A) § 61.347(a)(1)(i)(C) § 61.347(a)(1)(i)(C)(1) § 61.347(a)(1)(i)(C)(2) § 61.347(a)(1)(i)(C)(3) § 61.347(b) § 61.347(c) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	Install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the oil-water separator to a control device.	§ 61.347(a)(1)(i)(A) § 61.347(a)(1)(i)(C)(2) § 61.347(a)(1)(i)(C)(3) § 61.347(b) § 61.349(a)(1)(i) § 61.349(e) § 61.349(f) § 61.354(d) § 61.354(g) [G]§ 61.355(h)	§ 61.354(g) § 61.356(d) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3) § 61.356(m)	§ 61.357(d)(7) § 61.357(d)(7)(v)
TDU-OWS	EU	61FF-1783	Benzene	40 CFR Part 61, Subpart FF	§ 61.347(a)(1) § 61.347(a)(1)(i)(A) § 61.347(a)(1)(i)(C) § 61.347(a)(1)(i)(C)(1) § 61.347(a)(1)(i)(C)(2) § 61.347(a)(1)(i)(C)(3) § 61.347(b) § 61.347(c) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	Install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the oil-water separator to a control device.	§ 61.347(a)(1)(i)(A) § 61.347(a)(1)(i)(C)(2) § 61.347(a)(1)(i)(C)(3) § 61.347(b) § 61.349(a)(1)(i) § 61.349(e) § 61.349(f) § 61.354(c) § 61.354(c)(1) § 61.354(g) [G]§ 61.355(h) § 61.355(i)(1) § 61.355(i)(2) § 61.355(i)(3)(i) § 61.355(i)(3)(ii) § 61.355(i)(3)(ii)(A) § 61.355(i)(3)(ii)(B) § 61.355(i)(3)(ii)(C) § 61.355(i)(3)(iii) § 61.355(i)(3)(iv)	§ 61.354(c) § 61.354(c)(1) § 61.354(g) § 61.355(i)(1) § 61.355(i)(3)(ii)(A) § 61.356(d) § 61.356(f) § 61.356(f)(1) [G]§ 61.356(f)(3) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(4) § 61.356(m)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(A) § 61.357(d)(7)(v)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 61.355(i)(4)		
TDU-TO	EP	R1111-0112	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(B) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall not exceed an opacity of 20% averaged over a six minute period for any source on which construction was begun after January 31, 1972.	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None
TDU-TRANSFER	EP	R1111-0113	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(B) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall not exceed an opacity of 20% averaged over a six minute period for any source on which construction was begun after January 31, 1972.	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None
TDU-VETURI	EP	R1111-0112	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(B) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall not exceed an opacity of 20% averaged over a six minute period for any source on which construction was begun after January 31, 1972.	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None
TDU-VETURI	EP	R5121-0003	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) equal to or less than 100 pounds in any continuous 24-hour period is exempt from §115.121(a)(1) of this title.	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
TEMPPJ16B	EU	R7300-0001	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) §	An owner or operator may not use the alternative methods specified in §§	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b)	§ 117.345(a) § 117.345(f) [G]§ 117.345(f)(10)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					117.310(a)(9)(E)(vi)(III) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) [G]§ 117.310(f) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	§ 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a)(2)(C) § 117.340(h) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C) § 117.345(f)(3)(A) § 117.345(f)(3)(A)(ii) § 117.8000(b) § 117.8000(c) § 117.8000(c)(1) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8140(a) § 117.8140(a)(1) § 117.8140(a)(2) § 117.8140(a)(2)(A) [G]§ 117.8140(a)(2)(B) § 117.8140(b)	§ 117.345(f)(3) § 117.345(f)(3)(B) § 117.345(f)(9)	[G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
TEMPPJ16B	EU	R7300-0001	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B)	CO emissions must not exceed 3.0 g/hp-hr for stationary internal combustion engines.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a)(2)(C) § 117.340(h) § 117.345(f)(3) § 117.345(f)(3)(A) § 117.345(f)(3)(A)(ii) § 117.8000(b) § 117.8000(c)	§ 117.345(a) § 117.345(f) [G]§ 117.345(f)(10) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.8000(c)(2) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8120 § 117.8120(2) [G]§ 117.8120(2)(A) § 117.8120(2)(B) § 117.8140(a) § 117.8140(a)(1) § 117.8140(a)(2) § 117.8140(a)(2)(A) [G]§ 117.8140(a)(2)(B) § 117.8140(b)		[G]§ 117.8010(7) [G]§ 117.8010(8)
TEMPPJ16B	EU	60IIII-001	CO	40 CFR Part 60, Subpart IIII	§ 60.4204(b) § 1039.102 § 60.4201(a) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) § 60.4218	Owners and operators of non-emergency stationary CI ICE with a maximum engine power greater than or equal to 130 KW and less than or equal to 2237 KW and a displacement of less than 10 liters per cylinder and is a 2007 model year and later must comply with a CO emission limit of 3.5 g/KW-hr as stated in 40 CFR 60.4201(a) and 40 CFR 89.112(a) and 40 CFR 1039.102 and 40 CFR 1039.101.	None	None	None
TEMPPJ16B	EU	60IIII-001	NMHC and NO_X	40 CFR Part 60, Subpart IIII	§ 60.4204(b) § 1039.102 § 60.4201(a) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c)	Owners and operators of non-emergency stationary CI ICE with a maximum engine power greater than or equal to 75 KW but less than 560 KW and a displacement of less than	None	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.4218	10 liters per cylinder and is a 2007 - 2013 model year must comply with an NMHC+NOx emission limit of 4.0 g/KW-hr as stated in 40 CFR 60.4201(a) and 40 CFR 89.112(a) and 40 CFR 1039.102.			
TEMPPJ16B	EU	60IIII-001	PM	40 CFR Part 60, Subpart IIII	§ 60.4204(b) § 1039.102 § 60.4201(a) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) § 60.4218	Owners and operators of non-emergency stationary CI ICE with a maximum engine power greater than or equal to 130 KW and less than 560 KW and a displacement of less than 10 liters per cylinder and is a 2011 model year and later must comply with a PM emission limit of 0.02 g/KW-hr as stated in 40 CFR 60.4201(a) and 40 CFR 1039.102 and 40 CFR 1039.101.	None	None	[G]§ 60.4214(d)
TEMPPJ16B	EU	63ZZZZ-0001	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(c)	Stationary RICE subject to Regulations under 40 CFR Part 60. An affected source that meets any of the criteria in paragraphs (c)(1) through (7) of this section must meet the requirements of this part by meeting the requirements of 40 CFR part 60 subpart IIII, for compression ignition engines or 40 CFR part 60 subpart JJJJ, for spark ignition engines as applicable. No further	None	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						requirements apply for such engines under this part.			
TGUF201C/D	EU	63UUU-0003	SO_2	40 CFR Part 63, Subpart UUU	§ 63.1568(a)(1)-Table29.1.a § 63.1568(a)(1) § 63.1568(a)(3) § 63.1568(b)(4) § 63.1568(b)(5) § 63.1568(b)(5)-Table33.1.a § 63.1568(c)(1) § 63.1568(c)(1)-Table35.1 § 63.1568(c)(2) § 63.1570(a) § 63.1570(c) § 63.1570(d) § 63.1570(g)	For each new or existing Claus SRU part of a sulfur recovery plant of 20 long tons per day or more and subject to NSPS for sulfur oxides in 40 CFR §60.104(a)(2), you must meet the emission limit for each process vent of 250ppmv (dry basis) of sulfur dioxide (SO2) at zero percent excess air if you use an oxidation or reduction control system followed by incineration.	§ 63.1568(b)(1) § 63.1568(b)(1)-Table31.1.a § 63.1568(c)(1)-Table34.1.a § 63.1572(a)(1)-Table40.4 § 63.1572(a)(1)-Table40.8 § 63.1572(a)(2) § 63.1572(a)(3) § 63.1572(a)(4) [G]§ 63.1572(d)	§ 63.1568(b)(1)-Table31.1.a § 63.1568(c)(1)-Table34.1.a § 63.1570(c) [G]§ 63.1576(a) § 63.1576(b)(1) § 63.1576(b)(3) § 63.1576(b)(4) § 63.1576(b)(5) § 63.1576(d) § 63.1576(e) § 63.1576(f) § 63.1576(g) § 63.1576(h) § 63.1576(i)	§ 63.1568(b)(6) § 63.1568(b)(7) § 63.1570(f) § 63.1571(a) [G]§ 63.1574(a) § 63.1574(d) § 63.1574(d)-Table42.1 § 63.1574(d)-Table42.2 § 63.1574(d)-Table42.3 § 63.1575(a) § 63.1575(a)-Table43.1 [G]§ 63.1575(b) [G]§ 63.1575(c) [G]§ 63.1575(e) [G]§ 63.1575(f) § 63.1575(g) [G]§ 63.1575(h)
TK-1	EU	R5112-0012	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
TK-10	EU	R5112-0008	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
TK117APUMP	EU	R7300-0004	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(9)(E)(iv)(III)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d)	§ 117.345(a) § 117.345(f) [G]§ 117.345(f)(10) § 117.345(f)(3)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) [G]§ 117.310(f) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	§ 117.335(e) § 117.335(g) § 117.340(a)(2)(C) § 117.340(h) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C) § 117.345(f)(3)(A) § 117.345(f)(3)(A)(ii) § 117.8000(b) § 117.8000(c) § 117.8000(c)(1) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8140(a) § 117.8140(a)(1) § 117.8140(a)(2) § 117.8140(a)(2)(A) [G]§ 117.8140(a)(2)(B) § 117.8140(b)	§ 117.345(f)(3)(B) § 117.345(f)(9)	[G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
TK117APUMP	EU	R7300-0004	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B)	CO emissions must not exceed 3.0 g/hp-hr for stationary internal combustion engines.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a)(2)(C) § 117.340(h) § 117.345(f)(3) § 117.345(f)(3)(A) § 117.345(f)(3)(A)(ii) § 117.8000(b) § 117.8000(c) § 117.8000(c)(2)	§ 117.345(a) § 117.345(f) [G]§ 117.345(f)(10) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8120 § 117.8120(2) [G]§ 117.8120(2)(A) § 117.8120(2)(B) § 117.8140(a) § 117.8140(a)(1) § 117.8140(a)(2) § 117.8140(a)(2)(A) [G]§ 117.8140(a)(2)(B) § 117.8140(b)		[G]§ 117.8010(8)
TK117APUMP	EU	60IIII-0006	CO	40 CFR Part 60, Subpart IIII	§ 60.4204(b) § 1039.102 § 60.4201(a) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) § 60.4218	Owners and operators of non-emergency stationary CI ICE with a maximum engine power greater than or equal to 37 KW and less than 130 KW and a displacement of less than 10 liters per cylinder and is a 2007 model year and later must comply with a CO emission limit of 5.0 g/KW-hr as stated in 40 CFR 60.4201(a) and 40 CFR 89.112(a) and 40 CFR 1039.102 and 40 CFR 1039.101.	§ 60.4209(b)	§ 60.4214(c)	None
TK117APUMP	EU	60IIII-0006	NMHC and NO_X	40 CFR Part 60, Subpart IIII	§ 60.4204(b) § 1039.102 § 60.4201(a) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) § 60.4218	Owners and operators of non-emergency stationary CI ICE with a maximum engine power greater than or equal to 37 KW but less than 56 KW and a displacement of less than 10 liters per cylinder and is	§ 60.4209(b)	§ 60.4214(c)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						a 2008 model year and later must comply with an NMHC+NOx emission limit of 4.7 g/KW-hr as stated in 40 CFR 60.4201(a) and 40 CFR 89.112(a) and 40 CFR 1039.102 and 40 CFR 1039.101.			
TK117APUMP	EU	60IIII-0006	PM (Opacity)	40 CFR Part 60, Subpart IIII	§ 60.4204(b) § 1039.105(b)(1) § 1039.105(b)(2) § 1039.105(b)(3) § 60.4201(a) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) § 60.4218	Owners and operators of non-emergency stationary CI ICE with a displacement of less than 10 liters per cylinder and is not a constant-speed engine and is a 2007 model year and later must comply with the following opacity emission limits: 20% during the acceleration mode, 15% during the lugging mode, and 50% during the peaks in either the acceleration or lugging modes as stated in 40 CFR 60.4201(a)-(c) and 40 CFR 89.113(a)(1)-(3) and 40 CFR 1039.105(b)(1)-(3).	§ 60.4209(b)	§ 60.4214(c)	None
TK117APUMP	EU	60IIII-0006	PM	40 CFR Part 60, Subpart IIII	§ 60.4204(b) § 1039.102 § 60.4201(a) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) § 60.4218	Owners and operators of non-emergency stationary CI ICE with a maximum engine power greater than or equal to 19 KW and less than 56 KW and a displacement of less than 10 liters per cylinder and is a 2008 - 2012 model year must comply with a PM emission limit of 0.30 g/KW-	§ 60.4209(b)	§ 60.4214(c)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						hr as stated in 40 CFR 60.4201(a) and 40 CFR 1039.102.			
TK117APUMP	EU	63ZZZZ-0002	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(c)	Stationary RICE subject to Regulations under 40 CFR Part 60. An affected source that meets any of the criteria in paragraphs (c)(1) through (7) of this section must meet the requirements of this part by meeting the requirements of 40 CFR part 60 subpart IIII, for compression ignition engines or 40 CFR part 60 subpart JJJJ, for spark ignition engines as applicable. No further requirements apply for such engines under this part.	None	None	None
TK-2	EU	R5112-0008	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
TK-201	EU	R5112-0012	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
TK206CMP	EU	R7300-0003	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) §	An owner or operator may not use the alternative methods specified in §§	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b)	§ 117.345(a) § 117.345(f) [G]§ 117.345(f)(10)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					117.310(a)(9)(E)(vii)(II) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) [G]§ 117.310(f) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	§ 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a)(2)(C) § 117.340(h) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C) § 117.345(f)(3)(A) § 117.345(f)(3)(A)(ii) § 117.8000(b) § 117.8000(c) § 117.8000(c)(1) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8140(a) § 117.8140(a)(1) § 117.8140(a)(2) § 117.8140(a)(2)(A) [G]§ 117.8140(a)(2)(B) § 117.8140(b)	§ 117.345(f)(3) § 117.345(f)(3)(B) § 117.345(f)(9)	[G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
TK206CMP	EU	R7300-0003	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B)	CO emissions must not exceed 3.0 g/hp-hr for stationary internal combustion engines.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a)(2)(C) § 117.340(h) § 117.345(f)(3) § 117.345(f)(3)(A) § 117.345(f)(3)(A)(ii) § 117.8000(b) § 117.8000(c)	§ 117.345(a) § 117.345(f) [G]§ 117.345(f)(10) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.8000(c)(2) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8120 § 117.8120(2) [G]§ 117.8120(2)(A) § 117.8120(2)(B) § 117.8140(a) § 117.8140(a)(1) § 117.8140(a)(2) § 117.8140(a)(2)(A) [G]§ 117.8140(a)(2)(B) § 117.8140(b)		[G]§ 117.8010(7) [G]§ 117.8010(8)
TK206CMP	EU	60IIII-0003	CO	40 CFR Part 60, Subpart IIII	§ 60.4204(b) § 1039.102 § 60.4201(a) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) § 60.4218	Owners and operators of non-emergency stationary CI ICE with a maximum engine power greater than or equal to 130 KW and less than or equal to 2237 KW and a displacement of less than 10 liters per cylinder and is a 2007 model year and later must comply with a CO emission limit of 3.5 g/KW-hr as stated in 40 CFR 60.4201(a) and 40 CFR 89.112(a) and 40 CFR 1039.102 and 40 CFR 1039.101.	§ 60.4209(b)	§ 60.4214(c)	None
TK206CMP	EU	60IIII-0003	NMHC and NO_X	40 CFR Part 60, Subpart IIII	§ 60.4204(b) § 1039.102 § 60.4201(a) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c)	Owners and operators of non-emergency stationary CI ICE with a maximum engine power greater than or equal to 75 KW but less than 560 KW and a displacement of less than	§ 60.4209(b)	§ 60.4214(c)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.4218	10 liters per cylinder and is a 2007 - 2013 model year must comply with an NMHC+NOx emission limit of 4.0 g/KW-hr as stated in 40 CFR 60.4201(a) and 40 CFR 89.112(a) and 40 CFR 1039.102.			
TK206CMP	EU	60IIII-0003	PM	40 CFR Part 60, Subpart IIII	§ 60.4204(b) § 1039.102 § 60.4201(a) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) § 60.4218	Owners and operators of non-emergency stationary CI ICE with a maximum engine power greater than or equal to 130 KW and less than 560 KW and a displacement of less than 10 liters per cylinder and is a 2011 model year and later must comply with a PM emission limit of 0.02 g/KW-hr as stated in 40 CFR 60.4201(a) and 40 CFR 1039.102 and 40 CFR 1039.101.	§ 60.4209(b)	§ 60.4214(c)	None
TK206CMP	EU	63ZZZZ-0003	CO	40 CFR Part 63, Subpart ZZZZ	§ 63.6600(b)-Table2a.3.a § 63.6595(c) § 63.6600(b)-Table2b.1.a § 63.6600(b)-Table2b.1.b § 63.6605(a) § 63.6605(b) § 63.6625(h) § 63.6630(a) § 63.6640(b)	For each new or reconstructed CI stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions, operating at 100% load plus or minus 10%, you must reduce CO emissions by 70% or more.	§ 63.6610(a) § 63.6610(b) § 63.6610(c) [G]§ 63.6610(d) § 63.6615 § 63.6620(a) § 63.6620(a)-Table3.1 § 63.6620(a)-Table4.1.a.i § 63.6620(a)-Table4.1.a.ii § 63.6620(a)-Table4.1.a.iii § 63.6620(b) § 63.6620(b)(4)	§ 63.6620(i) § 63.6630(a)-Table5.1.a.iii § 63.6635(a) § 63.6635(c) § 63.6655(a) § 63.6655(a)(1) § 63.6655(a)(2) § 63.6655(a)(3) § 63.6655(a)(4) § 63.6655(a)(5) [G]§ 63.6655(b) § 63.6655(d) § 63.6660(a) § 63.6660(b)	§ 63.6620(i) § 63.6630(c) § 63.6640(b) § 63.6640(e) § 63.6645(a) § 63.6645(c) § 63.6645(g) § 63.6645(h) § 63.6645(h)(2) § 63.6650(a) § 63.6650(a)-Table7.1.a.i § 63.6650(a)-Table7.1.a.ii § 63.6650(a)-Table7.1.b § 63.6650(a)-Table7.1.c

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 63.6620(d) § 63.6620(e)(1) [G]§ 63.6620(e)(2) [G]§ 63.6625(b) § 63.6630(a)-Table5.1.a.i § 63.6630(a)-Table5.1.a.ii § 63.6630(a)-Table5.1.a.iii § 63.6635(a) § 63.6635(b) § 63.6640(a) § 63.6640(a)-Table6.1.a.i § 63.6640(a)-Table6.1.a.ii § 63.6640(a)-Table6.1.a.iii § 63.6640(a)-Table6.1.a.iv § 63.6640(a)-Table6.1.a.v § 63.6640(b)	§ 63.6660(c)	§ 63.6650(b) § 63.6650(b)(1) § 63.6650(b)(2) § 63.6650(b)(3) § 63.6650(b)(4) § 63.6650(b)(6) § 63.6650(b)(7) § 63.6650(b)(8) § 63.6650(b)(9) [G]§ 63.6650(c) [G]§ 63.6650(e) § 63.6650(f)
TK207CMP	EU	R7300-0003	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(9)(E)(vii)(II) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) [G]§ 117.310(f) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of §	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a)(2)(C) § 117.340(h) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C) § 117.345(f)(3)(A)	§ 117.345(a) § 117.345(f) [G]§ 117.345(f)(10) § 117.345(f)(3) § 117.345(f)(3)(B) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	§ 117.345(f)(3)(A)(ii) § 117.8000(b) § 117.8000(c) § 117.8000(c)(1) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8140(a) § 117.8140(a)(1) § 117.8140(a)(2) § 117.8140(a)(2)(A) [G]§ 117.8140(a)(2)(B) § 117.8140(b)		§ 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
TK207CMP	EU	R7300-0003	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B)	CO emissions must not exceed 3.0 g/hp-hr for stationary internal combustion engines.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a)(2)(C) § 117.340(h) § 117.345(f)(3) § 117.345(f)(3)(A) § 117.345(f)(3)(A)(ii) § 117.8000(b) § 117.8000(c) § 117.8000(c)(2) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8120 § 117.8120(2) [G]§ 117.8120(2)(A) § 117.8120(2)(B) § 117.8140(a) § 117.8140(a)(1) § 117.8140(a)(2)	§ 117.345(a) § 117.345(f) [G]§ 117.345(f)(10) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.8140(a)(2)(A) [G]§ 117.8140(a)(2)(B) § 117.8140(b)		
TK207CMP	EU	60IIII-0004	CO	40 CFR Part 60, Subpart IIII	§ 60.4204(b) § 1039.102 § 60.4201(a) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) § 60.4218	Owners and operators of non-emergency stationary CI ICE with a maximum engine power greater than or equal to 130 KW and less than or equal to 2237 KW and a displacement of less than 10 liters per cylinder and is a 2007 model year and later must comply with a CO emission limit of 3.5 g/KW-hr as stated in 40 CFR 60.4201(a) and 40 CFR 89.112(a) and 40 CFR 1039.102 and 40 CFR 1039.101.	§ 60.4209(b)	§ 60.4214(c)	None
TK207CMP	EU	60IIII-0004	NMHC and NO_X	40 CFR Part 60, Subpart IIII	§ 60.4204(b) § 1039.102 § 60.4201(a) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) § 60.4218	Owners and operators of non-emergency stationary CI ICE with a maximum engine power greater than or equal to 75 KW but less than 560 KW and a displacement of less than 10 liters per cylinder and is a 2007 - 2013 model year must comply with an NMHC+NOx emission limit of 4.0 g/KW-hr as stated in 40 CFR 60.4201(a) and 40 CFR 89.112(a) and 40 CFR 1039.102.	§ 60.4209(b)	§ 60.4214(c)	None
TK207CMP	EU	60IIII-0004	PM	40 CFR Part 60, Subpart IIII	§ 60.4204(b) § 1039.102 § 60.4201(a) § 60.4206	Owners and operators of non-emergency stationary CI ICE with a maximum engine power greater than	§ 60.4209(b)	§ 60.4214(c)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) § 60.4218	or equal to 130 KW and less than 560 KW and a displacement of less than 10 liters per cylinder and is a 2011 model year and later must comply with a PM emission limit of 0.02 g/KW-hr as stated in 40 CFR 60.4201(a) and 40 CFR 1039.102 and 40 CFR 1039.101.			
TK207CMP	EU	63ZZZZ-0003	CO	40 CFR Part 63, Subpart ZZZZ	§ 63.6600(b)-Table2a.3.a § 63.6595(c) § 63.6600(b)-Table2b.1.a § 63.6600(b)-Table2b.1.b § 63.6605(a) § 63.6605(b) § 63.6625(h) § 63.6630(a) § 63.6640(b)	For each new or reconstructed CI stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions, operating at 100% load plus or minus 10%, you must reduce CO emissions by 70% or more.	§ 63.6610(a) § 63.6610(b) § 63.6610(c) [G]§ 63.6610(d) § 63.6615 § 63.6620(a) § 63.6620(a)-Table3.1 § 63.6620(a)-Table4.1.a.i § 63.6620(a)-Table4.1.a.ii § 63.6620(a)-Table4.1.a.iii § 63.6620(b) § 63.6620(b)(4) § 63.6620(d) § 63.6620(e)(1) [G]§ 63.6620(e)(2) [G]§ 63.6625(b) § 63.6630(a)-Table5.1.a.i § 63.6630(a)-Table5.1.a.ii § 63.6630(a)-Table5.1.a.iii § 63.6635(a) § 63.6635(b) § 63.6640(a)	§ 63.6620(i) § 63.6630(a)-Table5.1.a.iii § 63.6635(a) § 63.6635(c) § 63.6655(a) § 63.6655(a)(1) § 63.6655(a)(2) § 63.6655(a)(3) § 63.6655(a)(4) § 63.6655(a)(5) [G]§ 63.6655(b) § 63.6655(d) § 63.6660(a) § 63.6660(b) § 63.6660(c)	§ 63.6620(i) § 63.6630(c) § 63.6640(b) § 63.6640(e) § 63.6645(a) § 63.6645(c) § 63.6645(g) § 63.6645(h) § 63.6645(h)(2) § 63.6650(a) § 63.6650(a)-Table7.1.a.i § 63.6650(a)-Table7.1.a.ii § 63.6650(a)-Table7.1.b § 63.6650(a)-Table7.1.c § 63.6650(b) § 63.6650(b)(1) § 63.6650(b)(2) § 63.6650(b)(3) § 63.6650(b)(4) § 63.6650(b)(6) § 63.6650(b)(7) § 63.6650(b)(8) § 63.6650(b)(9) [G]§ 63.6650(c) [G]§ 63.6650(e) § 63.6650(f)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 63.6640(a)-Table6.1.a.i § 63.6640(a)-Table6.1.a.ii § 63.6640(a)-Table6.1.a.iii § 63.6640(a)-Table6.1.a.iv § 63.6640(a)-Table6.1.a.v § 63.6640(b)		
TK20PUMP	EU	R7300-0005	Exempt	30 TAC Chapter 117, Subchapter B	[G]§ 117.303(a)(11) [G]§ 117.310(f)	Units exempted from the provisions of this division except as specified in §§117.310(f), 117.340(j), 117.345(f)(6) and (10), 117.350(c)(1) and 117.354(a)(5) include new, modified, reconstructed, or relocated stationary diesel engine placed into service on or after October 1, 2001, that operates less than 100 hours per year, based on a rolling 12-month average, in other than emergency situations; and meets the requirements for non-road engines as specified. §117.303(a)(11)(A)-(B)	None	§ 117.340(j) [G]§ 117.345(f)(10) [G]§ 117.345(f)(6)	None
TK20PUMP	EU	60IIII-0005	CO	40 CFR Part 60, Subpart IIII	§ 60.4204(b) § 1039.102 § 60.4201(a) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) § 60.4218	Owners and operators of non-emergency stationary CI ICE with a maximum engine power greater than or equal to 37 KW and less than 130 KW and a displacement of less than 10 liters per cylinder and is	§ 60.4209(b)	§ 60.4214(c)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						a 2007 model year and later must comply with a CO emission limit of 5.0 g/KW-hr as stated in 40 CFR 60.4201(a) and 40 CFR 89.112(a) and 40 CFR 1039.102 and 40 CFR 1039.101.			
TK20PUMP	EU	60IIII-0005	NMHC and NO_X	40 CFR Part 60, Subpart IIII	§ 60.4204(b) § 1039.102 § 60.4201(a) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) § 60.4218	Owners and operators of non-emergency stationary CI ICE with a maximum engine power greater than or equal to 37 KW but less than 56 KW and a displacement of less than 10 liters per cylinder and is a 2008 model year and later must comply with an NMHC+NOx emission limit of 4.7 g/KW-hr as stated in 40 CFR 60.4201(a) and 40 CFR 89.112(a) and 40 CFR 1039.102 and 40 CFR 1039.101.	§ 60.4209(b)	§ 60.4214(c)	None
TK20PUMP	EU	60IIII-0005	PM (Opacity)	40 CFR Part 60, Subpart IIII	§ 60.4204(b) § 1039.105(b)(1) § 1039.105(b)(2) § 1039.105(b)(3) § 60.4201(a) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) § 60.4218	Owners and operators of non-emergency stationary CI ICE with a displacement of less than 10 liters per cylinder and is not a constant-speed engine and is a 2007 model year and later must comply with the following opacity emission limits: 20% during the acceleration mode, 15% during the lugging mode, and 50% during the peaks in either the acceleration or	§ 60.4209(b)	§ 60.4214(c)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						lugging modes as stated in 40 CFR 60.4201(a)-(c) and 40 CFR 89.113(a)(1)-(3) and 40 CFR 1039.105(b)(1)-(3).			
TK20PUMP	EU	60IIII-0005	PM	40 CFR Part 60, Subpart IIII	§ 60.4204(b) § 1039.102 § 60.4201(a) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) § 60.4218	Owners and operators of non-emergency stationary CI ICE with a maximum engine power greater than or equal to 19 KW and less than 56 KW and a displacement of less than 10 liters per cylinder and is a 2008 - 2012 model year must comply with a PM emission limit of 0.30 g/KW-hr as stated in 40 CFR 60.4201(a) and 40 CFR 1039.102.	§ 60.4209(b)	§ 60.4214(c)	None
TK20PUMP	EU	63ZZZZ-0001	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(c)	Stationary RICE subject to Regulations under 40 CFR Part 60. An affected source that meets any of the criteria in paragraphs (c)(1) through (7) of this section must meet the requirements of this part by meeting the requirements of 40 CFR part 60 subpart IIII, for compression ignition engines or 40 CFR part 60 subpart JJJJ, for spark ignition engines as applicable. No further requirements apply for such engines under this part.	None	None	None
TK-210F	EU	R5112-0008	VOC	30 TAC Chapter 115, Storage of	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				VOCs		storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.		§ 115.118(a)(6)(A) § 115.118(a)(7)	
TK-210F	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
TK-264F	EU	R5112-0132	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(3) § 115.112(e)(3)(C) § 60.18	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.115(a) § 115.115(a)(6) § 115.116(a)(2) [G]§ 115.117	§ 115.118(a)(4) § 115.118(a)(4)(F) § 115.118(a)(5) § 115.118(a)(7)	None
TK-264F	EU	60KB-0063	VOC	40 CFR Part 60, Subpart Kb	§ 60.110b(a) § 63.640(n)(1)	Except for §60.110b(b), this subpart applies to vessels with a capacity greater than or equal to 75 cubic meters (19,800 gal) used to store VOLs for which construction/reconstruction/ modification began after	§ 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(d) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.116b(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						7/23/84.			
TK-329F	EU	R5112-0132	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(3) § 115.112(e)(3)(C) § 60.18	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.115(a) § 115.115(a)(6) § 115.116(a)(2) [G]§ 115.117	§ 115.118(a)(4) § 115.118(a)(4)(F) § 115.118(a)(5) § 115.118(a)(7)	None
TK-329F	EU	60KB-0063	VOC	40 CFR Part 60, Subpart Kb	§ 60.110b(a) § 63.640(n)(1)	Except for §60.110b(b), this subpart applies to vessels with a capacity greater than or equal to 75 cubic meters (19,800 gal) used to store VOLs for which construction/reconstruction/ modification began after 7/23/84.	§ 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(d) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.116b(d)
TK-330F	EU	R5112-0132	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(3) § 115.112(e)(3)(C) § 60.18	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in	§ 115.115(a) § 115.115(a)(6) § 115.116(a)(2) [G]§ 115.117	§ 115.118(a)(4) § 115.118(a)(4)(F) § 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.			
TK-330F	EU	60KB-0063	VOC	40 CFR Part 60, Subpart Kb	§ 60.110b(a) § 63.640(n)(1)	Except for §60.110b(b), this subpart applies to vessels with a capacity greater than or equal to 75 cubic meters (19,800 gal) used to store VOLs for which construction/reconstruction/ modification began after 7/23/84.	§ 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(d) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.116b(d)
TK4000PUMP	EU	R7300-0004	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(9)(E)(iv)(II) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) [G]§ 117.310(f) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a)(2)(C) § 117.340(h) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C) § 117.345(f)(3)(A) § 117.345(f)(3)(A)(ii) § 117.8000(b) § 117.8000(c) § 117.8000(c)(1) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d)	§ 117.345(a) § 117.345(f) [G]§ 117.345(f)(10) § 117.345(f)(3) § 117.345(f)(3)(B) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.8140(a) § 117.8140(a)(1) § 117.8140(a)(2) § 117.8140(a)(2)(A) [G]§ 117.8140(a)(2)(B) § 117.8140(b)		
TK4000PUMP	EU	R7300-0004	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B)	CO emissions must not exceed 3.0 g/hp-hr for stationary internal combustion engines.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a)(2)(C) § 117.340(h) § 117.345(f)(3) § 117.345(f)(3)(A) § 117.345(f)(3)(A)(ii) § 117.8000(b) § 117.8000(c) § 117.8000(c)(2) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8120 § 117.8120(2) [G]§ 117.8120(2)(A) § 117.8120(2)(B) § 117.8140(a) § 117.8140(a)(1) § 117.8140(a)(2) § 117.8140(a)(2)(A) [G]§ 117.8140(a)(2)(B) § 117.8140(b)	§ 117.345(a) § 117.345(f) [G]§ 117.345(f)(10) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
TK4000PUMP	EU	60IIII-0006	CO	40 CFR Part 60, Subpart IIII	§ 60.4204(b) § 1039.102 § 60.4201(a) § 60.4206	Owners and operators of non-emergency stationary CI ICE with a maximum engine power greater than	§ 60.4209(b)	§ 60.4214(c)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) § 60.4218	or equal to 37 KW and less than 130 KW and a displacement of less than 10 liters per cylinder and is a 2007 model year and later must comply with a CO emission limit of 5.0 g/KW-hr as stated in 40 CFR 60.4201(a) and 40 CFR 89.112(a) and 40 CFR 1039.102 and 40 CFR 1039.101.			
TK4000PUMP	EU	60IIII-0006	NMHC and NO_X	40 CFR Part 60, Subpart IIII	§ 60.4204(b) § 1039.102 § 60.4201(a) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) § 60.4218	Owners and operators of non-emergency stationary CI ICE with a maximum engine power greater than or equal to 37 KW but less than 56 KW and a displacement of less than 10 liters per cylinder and is a 2008 model year and later must comply with an NMHC+NOx emission limit of 4.7 g/KW-hr as stated in 40 CFR 60.4201(a) and 40 CFR 89.112(a) and 40 CFR 1039.102 and 40 CFR 1039.101.	§ 60.4209(b)	§ 60.4214(c)	None
TK4000PUMP	EU	60IIII-0006	PM (Opacity)	40 CFR Part 60, Subpart IIII	§ 60.4204(b) § 1039.105(b)(1) § 1039.105(b)(2) § 1039.105(b)(3) § 60.4201(a) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) § 60.4218	Owners and operators of non-emergency stationary CI ICE with a displacement of less than 10 liters per cylinder and is not a constant-speed engine and is a 2007 model year and later must comply with the following opacity emission limits: 20% during the	§ 60.4209(b)	§ 60.4214(c)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						acceleration mode, 15% during the lugging mode, and 50% during the peaks in either the acceleration or lugging modes as stated in 40 CFR 60.4201(a)-(c) and 40 CFR 89.113(a)(1)-(3) and 40 CFR 1039.105(b)(1)-(3).			
TK4000PUMP	EU	60IIII-0006	PM	40 CFR Part 60, Subpart IIII	§ 60.4204(b) § 1039.102 § 60.4201(a) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) § 60.4218	Owners and operators of non-emergency stationary CI ICE with a maximum engine power greater than or equal to 19 KW and less than 56 KW and a displacement of less than 10 liters per cylinder and is a 2008 - 2012 model year must comply with a PM emission limit of 0.30 g/KW-hr as stated in 40 CFR 60.4201(a) and 40 CFR 1039.102.	§ 60.4209(b)	§ 60.4214(c)	None
TK4000PUMP	EU	63ZZZZ-0002	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(c)	Stationary RICE subject to Regulations under 40 CFR Part 60. An affected source that meets any of the criteria in paragraphs (c)(1) through (7) of this section must meet the requirements of this part by meeting the requirements of 40 CFR part 60 subpart IIII, for compression ignition engines or 40 CFR part 60 subpart JJJJ, for spark ignition engines as applicable. No further	None	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						requirements apply for such engines under this part.			
TK536CMPB	EU	R7300-0002	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(9)(E)(iii)(II) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) [G]§ 117.310(f) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a)(2)(C) § 117.340(h) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C) § 117.345(f)(3)(A) § 117.345(f)(3)(A)(ii) § 117.8000(b) § 117.8000(c) § 117.8000(c)(1) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8140(a) § 117.8140(a)(1) § 117.8140(a)(2) § 117.8140(a)(2)(A) [G]§ 117.8140(a)(2)(B) § 117.8140(b)	§ 117.345(a) § 117.345(f) [G]§ 117.345(f)(10) § 117.345(f)(3) § 117.345(f)(3)(B) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
TK536CMPB	EU	R7300-0002	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B)	CO emissions must not exceed 3.0 g/hp-hr for stationary internal combustion engines.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a)(2)(C)	§ 117.345(a) § 117.345(f) [G]§ 117.345(f)(10) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.340(h) § 117.345(f)(3) § 117.345(f)(3)(A) § 117.345(f)(3)(A)(ii) § 117.8000(b) § 117.8000(c) § 117.8000(c)(2) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8120 § 117.8120(2) [G]§ 117.8120(2)(A) § 117.8120(2)(B) § 117.8140(a) § 117.8140(a)(1) § 117.8140(a)(2) § 117.8140(a)(2)(A) [G]§ 117.8140(a)(2)(B) § 117.8140(b)		§ 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
TK536CMPB	EU	60IIII-0002	CO	40 CFR Part 60, Subpart IIII	§ 60.4204(b) § 1039.102 § 60.4201(a) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) § 60.4218	Owners and operators of non-emergency stationary CI ICE with a maximum engine power greater than or equal to 19 KW and less than 37 KW and a displacement of less than 10 liters per cylinder and is a 2007 model year and later must comply with a CO emission limit of 5.5 g/KW-hr as stated in 40 CFR 60.4201(a) and 40 CFR 89.112(a) and 40 CFR 1039.102 and 40 CFR 1039.101.	None	None	None
TK536CMPB	EU	60IIII-0002	NMHC and	40 CFR Part 60,	§ 60.4204(b)	Owners and operators of	None	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
			NO_X	Subpart IIII	§ 1039.102 § 60.4201(a) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) § 60.4218	non-emergency stationary CI ICE with a maximum engine power greater than or equal to 19 KW but less than 37 KW and a displacement of less than 10 liters per cylinder and is a 2008 - 2012 model year must comply with an NMHC+NO_X emission limit of 7.5 g/KW-hr as stated in 40 CFR 60.4201(a) and 40 CFR 1039.102.			
TK536CMPB	EU	60IIII-0002	PM (Opacity)	40 CFR Part 60, Subpart IIII	§ 60.4204(b) § 1039.105(b)(1) § 1039.105(b)(2) § 1039.105(b)(3) § 60.4201(a) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) § 60.4218	Owners and operators of non-emergency stationary CI ICE with a displacement of less than 10 liters per cylinder and is not a constant-speed engine and is a 2007 model year and later must comply with the following opacity emission limits: 20% during the acceleration mode, 15% during the lugging mode, and 50% during the peaks in either the acceleration or lugging modes as stated in 40 CFR 60.4201(a)-(c) and 40 CFR 89.113(a)(1)-(3) and 40 CFR 1039.105(b)(1)-(3).	None	None	None
TK536CMPB	EU	60IIII-0002	PM	40 CFR Part 60, Subpart IIII	§ 60.4204(b) § 1039.102 § 60.4201(a) § 60.4206 § 60.4207(b) [G]§ 60.4211(a)	Owners and operators of non-emergency stationary CI ICE with a maximum engine power greater than or equal to 19 KW and less than 56 KW and a	None	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.4211(c) § 60.4218	displacement of less than 10 liters per cylinder and is a 2008 - 2012 model year must comply with a PM emission limit of 0.30 g/KW-hr as stated in 40 CFR 60.4201(a) and 40 CFR 1039.102.			
TK536CMPB	EU	63ZZZZ-0002	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(c)	Stationary RICE subject to Regulations under 40 CFR Part 60. An affected source that meets any of the criteria in paragraphs (c)(1) through (7) of this section must meet the requirements of this part by meeting the requirements of 40 CFR part 60 subpart IIII, for compression ignition engines or 40 CFR part 60 subpart JJJJ, for spark ignition engines as applicable. No further requirements apply for such engines under this part.	None	None	None
TK-565F	EU	R5112-0012	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
TK-600	EU	R5112-0132	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(3) § 115.112(e)(3)(C) § 60.18	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all	§ 115.115(a) § 115.115(a)(6) § 115.116(a)(2) [G]§ 115.117	§ 115.118(a)(4) § 115.118(a)(4)(F) § 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.			
TK-600	EU	63CC-0295	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.11 § 63.119(a)(2) § 63.119(e) § 63.119(e)(1) § 63.119(e)(3) § 63.119(e)(4) § 63.119(e)(5) [G]§ 63.148(d) § 63.148(e) § 63.640(n)(5) § 63.646(g)	Each owner or operator of a Group 1 storage vessel subject to this subpart shall comply with the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.120(e)(1) § 63.120(e)(4) § 63.120(e)(5) § 63.148(b)(1)(ii) [G]§ 63.148(c) § 63.148(g) § 63.148(g)(1) § 63.148(g)(2) § 63.148(h) § 63.148(h)(1) § 63.148(h)(2) § 63.646(b)(1) § 63.646(b)(2)	§ 63.148(g)(2) § 63.148(h)(2) § 63.148(i)(1) § 63.148(i)(2) [G]§ 63.148(i)(4) § 63.148(i)(5) § 63.148(i)(6) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1) § 63.655(i)(5)	[G]§ 63.120(e)(2) § 63.122(c)(2) [G]§ 63.122(g)(3) § 63.148(j) § 63.642(f) § 63.655(f) § 63.655(f)(1)(i) [G]§ 63.655(f)(1)(i)(A) [G]§ 63.655(f)(1)(i)(D) § 63.655(f)(6) § 63.655(g) [G]§ 63.655(g)(5) § 63.655(h) § 63.655(h)(1) § 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(C) [G]§ 63.655(h)(6)
TK-601	EU	R5112-0132	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(3) § 115.112(e)(3)(C) § 60.18	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in	§ 115.115(a) § 115.115(a)(6) § 115.116(a)(2) [G]§ 115.117	§ 115.118(a)(4) § 115.118(a)(4)(F) § 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.			
TK-601	EU	63CC-0295	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.646(a) § 63.11 § 63.119(a)(2) § 63.119(e) § 63.119(e)(1) § 63.119(e)(3) § 63.119(e)(4) § 63.119(e)(5) [G]§ 63.148(d) § 63.148(e) § 63.640(n)(5) § 63.646(g)	Each owner or operator of a Group 1 storage vessel subject to this subpart shall comply with the requirements of §63.119 - §63.121 except as provided in §63.646(b)-(l).	§ 63.120(e)(1) § 63.120(e)(4) § 63.120(e)(5) § 63.148(b)(1)(ii) [G]§ 63.148(c) § 63.148(g) § 63.148(g)(1) § 63.148(g)(2) § 63.148(h) § 63.148(h)(1) § 63.148(h)(2) § 63.646(b)(1) § 63.646(b)(2)	§ 63.148(g)(2) § 63.148(h)(2) § 63.148(i)(1) § 63.148(i)(2) [G]§ 63.148(i)(4) § 63.148(i)(5) § 63.148(i)(6) § 63.642(e) § 63.646(b)(1) § 63.655(h)(1) [G]§ 63.655(i)(1) § 63.655(i)(5)	[G]§ 63.120(e)(2) § 63.122(c)(2) [G]§ 63.122(g)(3) § 63.148(j) § 63.642(f) § 63.655(f) § 63.655(f)(1) [G]§ 63.655(f)(1)(i)(A) [G]§ 63.655(f)(1)(i)(D) § 63.655(f)(6) § 63.655(g) [G]§ 63.655(g)(5) § 63.655(h) § 63.655(h)(1) § 63.655(h)(2)(i) § 63.655(h)(2)(i)(A) § 63.655(h)(2)(i)(C) [G]§ 63.655(h)(6)
TK-608F	EU	R5112-0012	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
TK-9	EU	R5112-0012	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						requirements of this division.			
TK-F170	EU	R5112-0006	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
TK-F209	EU	R5112-0006	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
TK-F215	EU	R5112-0090	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)
TK-F215	EU	60KB-0124	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	§ 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3) § 60.116b(f)(1)		§ 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)
TK-F215	EU	61FF-0006	Benzene	40 CFR Part 61, Subpart FF	§ 61.351(a) [G]§ 60.112b(a)(2) § 61.351(a)(2) § 61.351(b)	As an alternative to the standards for tanks specified in § 61.343, an owner or operator may elect to comply with one of the following §61.351(a)(1)-(3):	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6)	§ 60.115b [G]§ 60.115b(b)(3) § 61.356(k)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 61.357(e) § 61.357(f)
TK-F215	EU	63CC-0071	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC
TK-F216	EU	R5112-0090	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A)	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.112(e)(2)(C) § 115.112(e)(2)(E) § 115.112(e)(2)(F) § 115.112(e)(2)(G) [G]§ 115.112(e)(2)(H) [G]§ 115.112(e)(2)(I) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	[G]§ 115.117		
TK-F216	EU	60KB-0124	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3) § 60.116b(f)(1)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)
TK-F216	EU	61FF-0006	Benzene	40 CFR Part 61, Subpart FF	§ 61.351(a) [G]§ 60.112b(a)(2) § 61.351(a)(2) § 61.351(b)	As an alternative to the standards for tanks specified in § 61.343, an owner or operator may elect to comply with one of the following §61.351(a)(1)-(3):	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii)	§ 60.115b [G]§ 60.115b(b)(3) § 61.356(k)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 61.357(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6)		§ 61.357(f)
TK-F216	EU	63CC-0071	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC
TK-F221	EU	R5112-0006	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
TK-F617	EU	R5112-0006	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
TK-F620	EU	R5112-0012	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
TK-F620	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii)	§ 63.655(f) § 63.655(f)(1)(i)(A)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.		§ 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
TK-FUELTK	EU	R5112-0012	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
TK-FUELTK	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6) § 63.655(h)(6)(ii)
TK-G405	EU	R5112-0008	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
TK-SM1001	EU	R5112-0006	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
TNT402	EU	R5112-	VOC	30 TAC Chapter	§ 115.111(a)(1)	Except as provided in §	[G]§ 115.117	§ 115.118(a)(1)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		0012		115, Storage of VOCs		115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.		§ 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	
TNTGRP-1	EU	R5112-0007	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
TNTGRP-2	EU	R5112-0007	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
TOTE 9272A	EU	R5112-0006	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
TO-WWTP	EP	R1111-0112	PM (Opacity)	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(B) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall not exceed an opacity of 20% averaged over a six minute period for any source on which construction was begun after January 31, 1972.	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None
TO-WWTP	EP	R5121-	VOC	30 TAC Chapter	§ 115.121(a)(1)	No person may allow a vent	[G]§ 115.125	§ 115.126	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		0019		115, Vent Gas Controls	§ 115.122(a)(1) § 115.122(a)(1)(C)	gas stream containing VOC to be emitted from any process vent, unless the vent gas stream is burned properly in accordance with §115.122(a)(1) of this title.	§ 115.126(1) § 115.126(1)(C) § 115.126(2) ** See CAM Summary	§ 115.126(1) § 115.126(1)(C) § 115.126(2)	
TO-WWTP	EU	63CC-1272	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.643(a) § 63.643(a)(2)	The owner or operator of a Group 1 miscellaneous process vent as defined in §63.641 shall comply with the requirements of either §63.643(a)(1)-(2).	§ 63.116(c) § 63.116(c)(1) § 63.116(c)(1)(i) § 63.116(c)(1)(i)(A) § 63.116(c)(1)(i)(B) § 63.116(c)(2) § 63.116(c)(4) § 63.116(c)(4)(i) [G]§ 63.116(c)(4)(ii) § 63.116(c)(4)(iii) § 63.642(d)(1) § 63.642(d)(3) § 63.642(d)(4) § 63.644(a) § 63.644(a)(1) § 63.644(a)(1)(i) § 63.644(c) § 63.644(c)(2) § 63.644(d) § 63.644(e) § 63.645(a) § 63.645(b) § 63.645(c) § 63.655(g)(6)(i) § 63.655(g)(6)(i)(A) § 63.655(g)(6)(i)(C)	§ 63.642(e) § 63.655(h)(1) § 63.655(i)(2) [G]§ 63.655(i)(3) § 63.655(i)(5)	§ 63.642(d)(2) § 63.642(f) § 63.644(d) [G]§ 63.655(e) § 63.655(f) § 63.655(f)(1)(ii) [G]§ 63.655(f)(1)(iii) [G]§ 63.655(f)(2) [G]§ 63.655(f)(3) § 63.655(g) § 63.655(g)(6) § 63.655(g)(6)(ii) § 63.655(h) § 63.655(h)(1)
UF4-413F	EU	R5131-0010	VOC	30 TAC Chapter 115, Water Separation	§ 115.132(a)(3) § 115.131(a)	VOC water separator compartments must be equipped with a vapor recovery system which satisfies the provisions of §115.131(a) of this title.	[G]§ 115.135(a) § 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	§ 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
UF4-413F	EU	61FF-1733	Benzene	40 CFR Part 61, Subpart FF	§ 61.347(a)(1) § 60.18 § 61.347(a)(1)(i)(A) § 61.347(a)(1)(i)(B) § 61.347(b) § 61.347(c) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(iii) § 61.349(b) § 61.349(d) § 61.349(e) § 61.349(f) § 61.349(g)	Install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the oil-water separator to a control device.	§ 60.18(f)(2) § 61.347(a)(1)(i)(A) § 61.347(b) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(c) § 61.354(c)(3) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.349(a)(1)(ii) § 61.354(c) § 61.354(c)(3) § 61.356(d) § 61.356(f) § 61.356(f)(1) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i) § 61.356(j)(7)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(F)
ULC-100B	EU	R7300-1086	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C) § 117.8000(b) § 117.8000(c) § 117.8000(c)(1) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
ULC-100B	EU	R7300-1086	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B) § 117.310(c)(3)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.8000(b) § 117.8000(c) § 117.8000(c)(2) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8120 § 117.8120(2) [G]§ 117.8120(2)(A) § 117.8120(2)(B)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
ULC-100B	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
ULC-100B	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
ULC-101B	EU	R7300-1086	NO_X	30 TAC Chapter 117,	§ 117.310(d)(3) § 117.310(a)	An owner or operator may not use the alternative	[G]§ 117.335(a)(1) § 117.335(a)(4)	§ 117.345(a) § 117.345(f)	§ 117.335(b) § 117.335(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Subchapter B	§ 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	§ 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C) § 117.8000(b) § 117.8000(c) § 117.8000(c)(1) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d)	§ 117.345(f)(1) § 117.345(f)(9)	§ 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
ULC-101B	EU	R7300-1086	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B) § 117.310(c)(3)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.8000(b) § 117.8000(c) § 117.8000(c)(2) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8120 § 117.8120(2) [G]§ 117.8120(2)(A) § 117.8120(2)(B)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
ULC-101B	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of	§ 60.105(a)(4) § 60.105(a)(4)(i)	§ 60.105(a)(4) § 60.105(a)(4)(i)	§ 60.105(e)(3)(ii) § 60.107(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4)(iii)	§ 60.107(f) § 60.107(g)
ULC-101B	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
ULC-102B	EU	R7300-1086	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C) § 117.8000(b) § 117.8000(c) § 117.8000(c)(1) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
ULC-102B	EU	R7300-1086	CO	30 TAC Chapter 117,	§ 117.310(c)(1) § 117.310(c)(1)(B)	CO emissions must not exceed 400 ppmv at 3.0%	[G]§ 117.335(a)(1) § 117.335(a)(4)	§ 117.345(a) § 117.345(f)	§ 117.335(b) § 117.335(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Subchapter B	§ 117.310(c)(3)	O 2, dry basis.	§ 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.8000(b) § 117.8000(c) § 117.8000(c)(2) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8120 § 117.8120(2) [G]§ 117.8120(2)(A) § 117.8120(2)(B)	§ 117.345(f)(1) § 117.345(f)(9)	[G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
ULC-102B	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
ULC-102B	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
ULC-103B	EU	R7300-1086	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	§ 117.335(e) § 117.335(g) § 117.340(a) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C) § 117.8000(b) § 117.8000(c) § 117.8000(c)(1) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d)		[G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
ULC-103B	EU	R7300-1086	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B) § 117.310(c)(3)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.8000(b) § 117.8000(c) § 117.8000(c)(2) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8120 § 117.8120(2) [G]§ 117.8120(2)(A) § 117.8120(2)(B)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
ULC-103B	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.106(a) [G]§ 60.106(e)(1)		
ULC-103B	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
ULC-104BA	EU	R7300-1097	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(2) § 117.335(g) § 117.340(a)(2)(B) § 117.340(c)(1) [G]§ 117.340(c)(3) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)		
ULC-104BA	EU	R7300-1097	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a)(2)(B) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
ULC-104BA	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of	§ 60.105(a)(4) § 60.105(a)(4)(i)	§ 60.105(a)(4) § 60.105(a)(4)(i)	§ 60.105(e)(3)(ii) § 60.107(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4)(iii)	§ 60.107(f) § 60.107(g)
ULC-104BA	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
ULC-104BB	EU	R7300-1097	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(2) § 117.335(g) § 117.340(a)(2)(B) § 117.340(c)(1) [G]§ 117.340(c)(3) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) § 117.345(f)(2)(c)[g] § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)		
ULC-104BB	EU	R7300-1097	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a)(2)(B) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
ULC-104BB	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
ULC-104BB	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
ULC-105BA	EU	R7300-1086	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C) § 117.8000(b) § 117.8000(c) § 117.8000(c)(1) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
ULC-105BA	EU	R7300-1086	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B) § 117.310(c)(3)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.8000(b) § 117.8000(c) § 117.8000(c)(2) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8120 § 117.8120(2) [G]§ 117.8120(2)(A) § 117.8120(2)(B)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
ULC-105BA	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
ULC-105BA	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
ULC-105BB	EU	R7300-1086	NO_X	30 TAC Chapter 117,	§ 117.310(d)(3) § 117.310(a)	An owner or operator may not use the alternative	[G]§ 117.335(a)(1) § 117.335(a)(4)	§ 117.345(a) § 117.345(f)	§ 117.335(b) § 117.335(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Subchapter B	§ 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	§ 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C) § 117.8000(b) § 117.8000(c) § 117.8000(c)(1) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d)	§ 117.345(f)(1) § 117.345(f)(9)	§ 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
ULC-105BB	EU	R7300-1086	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B) § 117.310(c)(3)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.8000(b) § 117.8000(c) § 117.8000(c)(2) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8120 § 117.8120(2) [G]§ 117.8120(2)(A) § 117.8120(2)(B)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
ULC-105BB	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of	§ 60.105(a)(4) § 60.105(a)(4)(i)	§ 60.105(a)(4) § 60.105(a)(4)(i)	§ 60.105(e)(3)(ii) § 60.107(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4)(iii)	§ 60.107(f) § 60.107(g)
ULC-105BB	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
ULC-127FA	EU	R5131-0010	VOC	30 TAC Chapter 115, Water Separation	§ 115.132(a)(3) § 115.131(a)	VOC water separator compartments must be equipped with a vapor recovery system which satisfies the provisions of §115.131(a) of this title.	[G]§ 115.135(a) § 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	§ 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	None
ULC-127FA	EU	61FF-1733	Benzene	40 CFR Part 61, Subpart FF	§ 61.347(a)(1) § 60.18 § 61.347(a)(1)(i)(A) § 61.347(a)(1)(i)(B) § 61.347(b) § 61.347(c) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(iii) § 61.349(b) § 61.349(d) § 61.349(e)	Install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the oil-water separator to a control device.	§ 60.18(f)(2) § 61.347(a)(1)(i)(A) § 61.347(b) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(c) § 61.354(c)(3) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.349(a)(1)(ii) § 61.354(c) § 61.354(c)(3) § 61.356(d) § 61.356(f) § 61.356(f)(1) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i) § 61.356(j)(7)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(F)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 61.349(f) § 61.349(g)				
ULC-143F	EU	R5131-0010	VOC	30 TAC Chapter 115, Water Separation	§ 115.132(a)(3) § 115.131(a)	VOC water separator compartments must be equipped with a vapor recovery system which satisfies the provisions of §115.131(a) of this title.	[G]§ 115.135(a) § 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	§ 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	None
ULC-143F	EU	61FF-1733	Benzene	40 CFR Part 61, Subpart FF	§ 61.347(a)(1) § 60.18 § 61.347(a)(1)(i)(A) § 61.347(a)(1)(i)(B) § 61.347(b) § 61.347(c) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(iii) § 61.349(b) § 61.349(d) § 61.349(e) § 61.349(f) § 61.349(g)	Install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the oil-water separator to a control device.	§ 60.18(f)(2) § 61.347(a)(1)(i)(A) § 61.347(b) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(c) § 61.354(c)(3) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.349(a)(1)(ii) § 61.354(c) § 61.354(c)(3) § 61.356(d) § 61.356(f) § 61.356(f)(1) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i) § 61.356(j)(7)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(F)
ULCARU-SEP4	EU	R5131-0010	VOC	30 TAC Chapter 115, Water Separation	§ 115.132(a)(3) § 115.131(a)	VOC water separator compartments must be equipped with a vapor recovery system which satisfies the provisions of §115.131(a) of this title.	[G]§ 115.135(a) § 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	§ 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	None
ULCARU-SEP4	EU	61FF-1781	Benzene	40 CFR Part 61, Subpart FF	§ 61.347(a)(1) § 61.347(a)(1)(i)(A) § 61.347(a)(1)(i)(B) § 61.347(b) § 61.347(c)	Install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the oil-water	§ 61.347(a)(1)(i)(A) § 61.347(b) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e)	§ 61.349(a)(1)(ii) § 61.356(d) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	separator to a control device.	§ 61.349(f) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i)	
ULC-CTWR	EU	R5760-0206	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Cooling Towers	§ 115.767(6) § 115.764(a)(1) § 115.766(i)	All sites that are subject to this division and that are located in the Houston/ Galveston/Brazoria area as defined in § 115.10, excluding Harris County, are exempt from § 115.761(b) and (c)(2), except as provided in § 115.769(a)(3).	§ 115.764(a)(1) § 115.764(a)(3) [G]§ 115.764(a)(6) § 115.764(c)	§ 115.766(a)(1) § 115.766(a)(2) § 115.766(a)(3) § 115.766(a)(5) § 115.766(a)(6) § 115.766(c) [G]§ 115.766(g) § 115.766(i)(1)	§ 115.766(i)(2)
ULC-CTWR	EU	63CC-002	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.654(a) § 63.640(h)(6)	Except as specified in paragraph (b) of this section, the owner or operator of a heat exchange system that meets the criteria in §63.640(c)(8) must comply with the requirements of paragraphs (c) through (g) of this section.	§ 63.642(d)(1) § 63.642(d)(3) § 63.642(d)(4) [G]§ 63.654(c) [G]§ 63.654(d) § 63.654(e) [G]§ 63.654(f) [G]§ 63.654(g)	§ 63.642(e) § 63.655(h)(1) [G]§ 63.655(i)(4) § 63.655(i)(5)	§ 63.642(d)(2) § 63.642(f) § 63.655(f) § 63.655(f)(1)(vi) § 63.655(f)(4) § 63.655(g) [G]§ 63.655(g)(9) § 63.655(h)(1)
ULC-FUG1	EU	60GGGa-001	VOC	40 CFR Part 60, Subpart GGGa	[G]§ 60.590a(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification	The permit holder shall comply with the applicable requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 60, Subpart GGGa

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					requirements of 40 CFR Part 60, Subpart GGGa				
ULC-SEP7	EU	R5131-0010	VOC	30 TAC Chapter 115, Water Separation	§ 115.132(a)(3) § 115.131(a)	VOC water separator compartments must be equipped with a vapor recovery system which satisfies the provisions of §115.131(a) of this title.	[G]§ 115.135(a) § 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	§ 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	None
ULC-SEP7	EU	61FF-1781	Benzene	40 CFR Part 61, Subpart FF	§ 61.347(a)(1) § 61.347(a)(1)(i)(A) § 61.347(a)(1)(i)(B) § 61.347(b) § 61.347(c) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	Install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the oil-water separator to a control device.	§ 61.347(a)(1)(i)(A) § 61.347(b) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.349(a)(1)(ii) § 61.356(d) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i)	None
UU3	EU	63UUU-0004	Hydrogen Chloride	40 CFR Part 63, Subpart UUU	§ 63.1567(a)(1)-Table 22.2 § 63.1567(a)(1) § 63.1567(a)(1)(ii) § 63.1567(a)(2) § 63.1567(a)(2)-Table23.1 § 63.1567(a)(3) § 63.1567(b)(3) § 63.1567(b)(4) § 63.1567(b)(4)(i) § 63.1567(b)(5) § 63.1567(b)(5)-	For each existing cyclic or continuous CRU, you must reduce uncontrolled emissions of HCl to a concentration of 10 ppmv (dry basis), corrected to 3% oxygen.	§ 63.1567(b)(1) § 63.1567(b)(1)-Table24.1 § 63.1567(b)(2) § 63.1567(b)(2)-Table25.1.a.(2) § 63.1567(b)(2)-Table25.1.b § 63.1567(b)(2)-Table25.1.c § 63.1567(b)(2)-Table25.1.d § 63.1567(b)(2)-	§ 63.1567(b)(1)-Table24.1 § 63.1567(b)(2)-Table25.2.a.i § 63.1567(b)(2)-Table25.2.b.i § 63.1567(c)(1)-Table28.1.a § 63.1567(c)(1)-Table28.1.b § 63.1567(c)(2) § 63.1570(c) § 63.1572(c)(4)	§ 63.1567(b)(6) § 63.1567(b)(7) § 63.1570(f) § 63.1571(a) § 63.1571(d)(4) § 63.1574(a) § 63.1574(a)(1) § 63.1574(a)(2) § 63.1574(a)(3) § 63.1574(a)(3)(ii) § 63.1574(d) § 63.1574(d)-Table42.1 § 63.1574(d)-Table42.2

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					Table26.2 § 63.1567(c)(1) § 63.1570(a) § 63.1570(c) § 63.1570(d) § 63.1570(g) § 63.1571(d)(4) [G]§ 63.1571(e)		Table25.1.e.(1) § 63.1567(b)(2)-Table25.1.e.(2) § 63.1567(b)(2)-Table25.1.e.(4) § 63.1567(b)(2)-Table25.2.a.i § 63.1567(b)(2)-Table25.2.b.i § 63.1567(c)(1)-Table27.2 § 63.1567(c)(1)-Table28.1.a § 63.1567(c)(1)-Table28.1.b § 63.1571(a) § 63.1571(a)(1) [G]§ 63.1571(b) § 63.1572(c) § 63.1572(c)(1) § 63.1572(c)(2) § 63.1572(c)(3) § 63.1572(c)(4) [G]§ 63.1572(d)	§ 63.1572(c)(5) [G]§ 63.1576(a) § 63.1576(d) § 63.1576(e) § 63.1576(f) § 63.1576(g) § 63.1576(h) § 63.1576(i)	§ 63.1574(d)-Table42.3 § 63.1575(a) § 63.1575(a)-Table43.1 [G]§ 63.1575(b) [G]§ 63.1575(c) [G]§ 63.1575(d) [G]§ 63.1575(f) § 63.1575(g) [G]§ 63.1575(h)
UU3	EU	63UUU-0004	TOC	40 CFR Part 63, Subpart UUU	§ 63.1566(a)(1)(i)-Table15.1 § 63.1566(a)(1) § 63.1566(a)(2) § 63.1566(a)(2)-Table16.1 § 63.1566(a)(3) § 63.1566(a)(4) § 63.1566(a)(5) § 63.1566(b)(3) § 63.1566(b)(4) § 63.1566(b)(6) § 63.1566(b)(6)-Table19.1 § 63.1566(b)(7)	For each applicable process vent for a new or existing catalytic reforming unit, you must vent emissions of total organic compounds (TOC) to a flare that meets the control device requirements in §63.11(b) (Option 1). Visible emissions from a flare must not exceed a total of 5 minutes during any 2-hour operating period.	§ 63.1566(b)(1) § 63.1566(b)(1)-Table17.1 § 63.1566(b)(2) § 63.1566(b)(2)-Table18.1.a § 63.1566(b)(2)-Table18.1.b § 63.1566(b)(5)(i) § 63.1566(c)(1)-Table20.1 § 63.1566(c)(1)-Table21.1 § 63.1566(c)(2) § 63.1571(a)	§ 63.1566(c)(1)-Table21.1 § 63.1570(c) § 63.1574(a) § 63.1574(a)(1) § 63.1574(a)(2) § 63.1574(a)(3) § 63.1574(a)(3)(ii) [G]§ 63.1576(a) § 63.1576(c) § 63.1576(d) § 63.1576(e) § 63.1576(f) § 63.1576(g) § 63.1576(h)	§ 63.1566(b)(7) § 63.1566(b)(8) § 63.1570(f) § 63.1571(a) [G]§ 63.1574(a) § 63.1574(d) § 63.1574(d)-Table42.1 § 63.1574(d)-Table42.2 § 63.1574(d)-Table42.3 § 63.1575(a) § 63.1575(a)-Table43.1 [G]§ 63.1575(b) [G]§ 63.1575(c) [G]§ 63.1575(d) [G]§ 63.1575(f)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.1566(c)(1) § 63.1566(c)(2) § 63.1570(a) § 63.1570(b) § 63.1570(c) § 63.1570(d) § 63.1570(g) [G]§ 63.1571(e)		§ 63.1571(a)(1) [G]§ 63.1571(b) [G]§ 63.1572(d)	§ 63.1576(i)	§ 63.1575(g) [G]§ 63.1575(h)
UU3 BYPASS	EU	63UUU-0005	112(B) HAPS	40 CFR Part 63, Subpart UUU	§ 63.1569(a)(1)(i)-Table36.1 § 63.1569(a)(1) § 63.1569(a)(1)(i) § 63.1569(a)(3) § 63.1569(b)(2) § 63.1569(b)(2)-Table38.1.a § 63.1569(c)(1) § 63.1570(a) § 63.1570(c) § 63.1570(d) § 63.1570(g)	If you elect to install an automated system (Option 1), you must install and operate a device (including a flow indicator, level recorder, or electronic valve position monitor) to demonstrate, either continuously or at least every hour, whether flow is present in the bypass line. Install the device at or near as practical to the entrance to any bypass line that could divert the vent stream away from the control device to the atmosphere.	§ 63.1569(b)(1) § 63.1569(b)(1)-Table37.1 § 63.1569(c)(1)-Table39.1 § 63.1571(a) § 63.1571(a)(1) [G]§ 63.1571(b)	§ 63.1569(b)(1)-Table37.1 § 63.1569(c)(1)-Table39.1 § 63.1569(c)(1)-Table39.5 § 63.1570(c) [G]§ 63.1576(a) § 63.1576(d) § 63.1576(e) § 63.1576(f) § 63.1576(g) § 63.1576(h) § 63.1576(i)	§ 63.1569(b)(3) § 63.1569(b)(4) § 63.1569(c)(1)-Table39.5 § 63.1570(f) § 63.1571(a) [G]§ 63.1574(a) § 63.1574(d) § 63.1574(d)-Table42.1 § 63.1574(d)-Table42.2 § 63.1574(d)-Table42.3 § 63.1575(a) § 63.1575(a)-Table43.1 [G]§ 63.1575(b) [G]§ 63.1575(c) [G]§ 63.1575(d) [G]§ 63.1575(f) § 63.1575(g) [G]§ 63.1575(h)
UU3-301BA	EU	R7300-1289	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(2) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 117.340(p)(3)	generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	§ 117.340(c)(1) § 117.340(c)(3)(D) [G]§ 117.340(c)(3)(E) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)		§ 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
UU3-301BA	EU	R7300-1289	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(e) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)		§ 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
UU3-301BA	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
UU3-301BA	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
UU3-301BB	EU	R7300-1289	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(c)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	§ 117.335(f) § 117.335(f)(2) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) § 117.340(c)(3)(D) [G]§ 117.340(c)(3)(E) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)	§ 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
UU3-301BB	EU	R7300-1289	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.340(b)(3) § 117.340(e) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)		[G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
UU3-301BB	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
UU3-301BB	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					CFR Part 63, Subpart DDDDD				
UU3-301BC	EU	R7300-1289	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(2) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) § 117.340(c)(3)(D) [G]§ 117.340(c)(3)(E) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
UU3-301BC	EU	R7300-1289	CO	30 TAC Chapter 117,	§ 117.310(c)(1) § 117.310(c)(1)(A)	CO emissions must not exceed 400 ppmv at 3.0%	[G]§ 117.335(a)(1) § 117.335(a)(4)	§ 117.345(a) § 117.345(f)	§ 117.335(b) § 117.335(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Subchapter B	§ 117.310(c)(3) § 117.340(f)(1)	O 2, dry basis.	§ 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(e) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)	§ 117.345(f)(2) [G]§ 117.345(f)(2)(C § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	[G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
UU3-301BC	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
UU3-301BC	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
UU3-301BD	EU	R7300-1289	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(2) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) § 117.340(c)(3)(D) [G]§ 117.340(c)(3)(E) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)		
UU3-301BD	EU	R7300-1289	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(e) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
UU3-301BD	EU	60J-0025	Hydrogen	40 CFR Part 60,	§ 60.104(a)(1)	No owner or operator	§ 60.105(a)(4)	§ 60.105(a)(4)	§ 60.105(e)(3)(ii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
			Sulfide	Subpart J		subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.107(d) § 60.107(f) § 60.107(g)
UU3-301BD	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
UU3-302BA	EU	R7300-1289	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(2) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) § 117.340(c)(3)(D) [G]§ 117.340(c)(3)(E) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)		
UU3-302BA	EU	R7300-1289	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(e) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							[G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)		
UU3-302BA	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
UU3-302BA	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
UU3-302BB	EU	R7300-1289	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(2) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) § 117.340(c)(3)(D) [G]§ 117.340(c)(3)(E)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)		§ 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
UU3-302BB	EU	R7300-1289	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(e) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)		[G]§ 117.8010(8) § 117.8100(c)
UU3-302BB	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
UU3-302BB	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
UU3-302BC	EU	R7300-1097	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(2)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(8) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	§ 117.335(g) § 117.340(a)(2)(B) § 117.340(c)(1) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)	§ 117.8100(a)(5)(C)	[G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
UU3-302BC	EU	R7300-1097	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a)(2)(B) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii)	§ 117.345(a) § 117.345(f) [G]§ 117.345(f)(2) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)		[G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
UU3-302BC	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
UU3-302BC	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
UU3-306B	EU	R7300-1493	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(2)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(8) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	§ 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) § 117.340(c)(3)(D) [G]§ 117.340(c)(3)(E) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)	§ 117.8100(a)(5)(C)	[G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
UU3-306B	EU	R7300-1493	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(e)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							[G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)		§ 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
UU3-306B	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
UU3-306B	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
UU3-307BA	EU	R7300-1018	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(ii) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C) § 117.8000(b) § 117.8000(c) § 117.8000(c)(1) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
UU3-307BA	EU	R7300-1018	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B) § 117.310(c)(3)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.8000(b) § 117.8000(c) § 117.8000(c)(2) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8120 § 117.8120(2) [G]§ 117.8120(2)(A) § 117.8120(2)(B)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
UU3-307BA	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
UU3-307BA	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
UU3-307BB	EU	R7300-1018	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(ii) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C) § 117.8000(b) § 117.8000(c) § 117.8000(c)(1) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
UU3-307BB	EU	R7300-1018	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B) § 117.310(c)(3)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.8000(b) § 117.8000(c) § 117.8000(c)(2) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8120 § 117.8120(2) [G]§ 117.8120(2)(A) § 117.8120(2)(B)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
UU3-307BB	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
UU3-307BB	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
UU3-308B	EU	R7300-1289	NO_X	30 TAC Chapter 117,	§ 117.310(d)(3) § 117.310(a)	An owner or operator may not use the alternative	[G]§ 117.335(a)(1) § 117.335(a)(4)	§ 117.345(a) § 117.345(f)	§ 117.335(b) § 117.335(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Subchapter B	§ 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	§ 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(2) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) § 117.340(c)(3)(D) [G]§ 117.340(c)(3)(E) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)	§ 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	[G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
UU3-308B	EU	R7300-1289	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(7) § 117.345(f)(8)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(e) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)	§ 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
UU3-308B	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
UU3-308B	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR	The permit holder shall comply with the applicable recordkeeping requirements of 40	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					equipment specification requirements of 40 CFR Part 63, Subpart DDDDD		Part 63, Subpart DDDDD	CFR Part 63, Subpart DDDDD	
UU3-309B	EU	R7300-0001	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(1)(A) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(1) § 117.335(g) § 117.340(a) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) [G]§ 117.340(c)(3) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(2)(A) § 117.345(f)(2)(A)(C) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
UU3-309B	EU	R7300-0001	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1) § 117.8120	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a) § 117.340(b)(1) § 117.340(b)(3) § 117.340(e) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120(1) § 117.8120(1)(A)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(2)(B) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
UU3-309B	EU	R7300-0001	NH_3	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(2) § 117.310(c)(2)(B) § 117.340(f)(1)	For boilers that inject urea or ammonia into the exhaust stream for NO_x control, ammonia emissions must not exceed 10 ppmv at 3.0% O_2, dry.	§ 117.335(a)(2) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(g) § 117.340(b)(1) § 117.340(b)(3)	§ 117.345(a) § 117.345(f) § 117.345(f)(11) § 117.345(f)(2)(B) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.340(d) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8130 § 117.8130(4)		§ 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
UU3-309B	EU	R7300-0001	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(2) § 117.335(g) § 117.340(a) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) [G]§ 117.340(c)(3) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(2)(A) § 117.345(f)(2)(C) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)		
UU3-309B	EU	R7300-0001	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a) § 117.340(b)(1) § 117.340(b)(3) § 117.340(e) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(2)(B) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							[G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)		
UU3-309B	EU	R7300-0001	NH_3	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(2) § 117.310(c)(2)(B) § 117.340(f)(1)	For process heaters that inject urea or ammonia into the exhaust stream for NO_x control, ammonia emissions must not exceed 10 ppmv at 3.0% O_2, dry.	§ 117.335(a)(2) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(g) § 117.340(b)(1) § 117.340(b)(3) § 117.340(d) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8130 § 117.8130(4)	§ 117.345(a) § 117.345(f) § 117.345(f)(11) § 117.345(f)(2)(B) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
UU3-309B	EU	60Db-0001	PM	40 CFR Part 60, Subpart Db	§ 60.40b(a)	This subpart applies to each steam generating unit constructed, modified, or reconstructed after 6/19/84, and that has a heat input	None	[G]§ 60.49b(d) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						capacity from fuels combusted in the unit > 29 MW (100 MMBtu/hr).			
UU3-309B	EU	60Db-0001	PM (Opacity)	40 CFR Part 60, Subpart Db	§ 60.40b(a)	This subpart applies to each steam generating unit constructed, modified, or reconstructed after 6/19/84, and that has a heat input capacity from fuels combusted in the unit > 29 MW (100 MMBtu/hr).	None	[G]§ 60.49b(d) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3)
UU3-309B	EU	60Db-0001	NO_X	40 CFR Part 60, Subpart Db	§ 60.44b(l)(1) § 60.44b(h) § 60.44b(i) § 60.46b(a)	Affected facilities combusting coal, oil, or natural gas, or a mixture of these fuels, or any other fuels: a limit of 86 ng/JI (0.20 lb/million Btu) heat input unless the affected facility meets the specified requirements.	§ 60.46b(c) § 60.46b(e) § 60.46b(e)(1) § 60.46b(e)(3) [G]§ 60.48b(b) § 60.48b(c) § 60.48b(d) § 60.48b(e) [G]§ 60.48b(e)(2) § 60.48b(e)(3) § 60.48b(f)	[G]§ 60.48b(b) § 60.48b(c) [G]§ 60.49b(d) [G]§ 60.49b(g) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3) § 60.49b(b) § 60.49b(h) § 60.49b(i) § 60.49b(v) § 60.49b(w)
UU3-309B	EU	60Ja-0001		40 CFR Part 60, Subpart Ja	§ 60.100a(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 60, Subpart Ja
UU3-309B	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7500(a)(1)-Table 3.1 § 63.7499(l) § 63.7500(a) § 63.7500(a)(3)	A new or existing limited use boiler or process heater with a heat input capacity of less than or equal to 5 million Btu per hour must	§ 63.7510(g) § 63.7515(d) § 63.7515(g) § 63.7540(a)(12) § 63.7540(a)(13)	§ 63.7555(a) § 63.7555(a)(1) § 63.7555(h) § 63.7560(a) § 63.7560(b)	§ 63.7530(f) § 63.7545(a) § 63.7545(c) § 63.7545(e) § 63.7545(e)(1)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.7500(e) § 63.7505(a) § 63.7510(g) § 63.7515(g) § 63.7530(f) § 63.7540(a)(12) § 63.7540(a)(13)	conduct a tune-up of the boiler or process heater every 5 years as specified in § 63.7540.		§ 63.7560(c)	§ 63.7545(e)(6) § 63.7545(e)(7) § 63.7545(e)(8) § 63.7545(e)(8)(i) § 63.7545(f) [G]§ 63.7545(h) § 63.7550(a) [G]§ 63.7550(b) § 63.7550(c) § 63.7550(c)(1) § 63.7550(c)(5)(i) § 63.7550(c)(5)(ii) § 63.7550(c)(5)(iii) § 63.7550(c)(5)(xiv) § 63.7550(c)(5)(xvii) § 63.7550(h) § 63.7550(h)(3)
UU3-310BA	EU	R7300-0001	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(2) § 117.335(g) § 117.340(a) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) [G]§ 117.340(c)(3) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)		
UU3-310BA	EU	R7300-0001	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a) § 117.340(b)(1) § 117.340(b)(3) § 117.340(e) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)		
UU3-310BA	EU	R7300-0001	NH_3	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(2) § 117.310(c)(2)(B) § 117.340(f)(1)	For process heaters that inject urea or ammonia into the exhaust stream for NO_x control, ammonia emissions must not exceed 10 ppmv at 3.0% O_2, dry.	§ 117.335(a)(2) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(g) § 117.340(b)(1) § 117.340(b)(3) § 117.340(d) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8130 § 117.8130(4)	§ 117.345(a) § 117.345(f) § 117.345(f)(11) [G]§ 117.345(f)(2) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
UU3-310BA	EU	60Ja-0001	NO_X	40 CFR Part 60, Subpart Ja	§ 60.102a(a) § 60.100a § 60.100a(a) § 60.100a(b) § 60.102a § 60.102a(g) § 60.102a(g)(2)	Each owner or operator that is subject to the requirements of this subpart shall comply with the emissions limitations in § 60.102a(b)-(h) on and after the date on which the initial	§ 60.104a(a) § 60.104a(c) § 60.104a(i) § 60.104a(i)(1) § 60.104a(i)(2) § 60.104a(i)(3) § 60.104a(i)(5)	§ 60.108a § 60.108a(a)	§ 60.108a § 60.108a(a) § 60.108a(b) § 60.108a(d) § 60.108a(d)(1) § 60.108a(d)(2) § 60.108a(d)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.102a(g)(2)(ii) § 60.102a(g)(2)(ii)(B)	performance test, required by § 60.8, is completed, but not later than 60 days after achieving the maximum production rate at which the affected facility will be operated, or 180 days after initial startup, whichever comes first.	§ 60.104a(i)(7) § 60.104a(i)(8) § 60.107a(c)(1) § 60.107a(c)(2) § 60.107a(c)(3) § 60.107a(c)(4) § 60.107a(c)(5) § 60.107a(d) § 60.107a(d)(1) § 60.107a(d)(2) § 60.107a(d)(4) § 60.107a(d)(5) § 60.107a(d)(7) § 60.107a(i) § 60.107a(i)(3) § 60.107a(i)(3)(ii)		§ 60.108a(d)(4) § 60.108a(d)(5) § 60.108a(d)(6) § 60.108a(d)(7)
UU3-310BA	EU	60Ja-0001	Hydrogen Sulfide	40 CFR Part 60, Subpart Ja	§ 60.102a(a) § 60.100a § 60.100a(a) § 60.100a(b) § 60.102a § 60.102a(g) § 60.102a(g)(1) § 60.102a(g)(1)(ii) § 60.103a § 60.103a(c) § 60.103a(c)(2) § 60.103a(d) § 60.103a(d)(1) § 60.103a(d)(5) § 60.103a(e) § 60.103a(e)(1) § 60.103a(e)(2) § 60.103a(e)(3)	Each owner or operator that is subject to the requirements of this subpart shall comply with the emissions limitations in § 60.102a(b)-(h) on and after the date on which the initial performance test, required by § 60.8, is completed, but not later than 60 days after achieving the maximum production rate at which the affected facility will be operated, or 180 days after initial startup, whichever comes first.	§ 60.104a § 60.104a(a) § 60.104a(c) § 60.104a(j) § 60.104a(j)(4)(iv) § 60.107a § 60.107a(a) § 60.107a(a)(2) § 60.107a(a)(2)(i) § 60.107a(a)(2)(ii) § 60.107a(a)(2)(iii) § 60.107a(a)(2)(iv) § 60.107a(i) § 60.107a(i)(1) § 60.107a(i)(1)(ii)	§ 60.108a § 60.108a(a) § 60.108a(c) § 60.108a(c)(6) § 60.108a(c)(6)(i) § 60.108a(c)(6)(ii) § 60.108a(c)(6)(iii) § 60.108a(c)(6)(ix) § 60.108a(c)(6)(v) § 60.108a(c)(6)(vii) § 60.108a(c)(6)(viii) § 60.108a(c)(6)(x)	§ 60.108a § 60.108a(a) § 60.108a(b) § 60.108a(d) § 60.108a(d)(1) § 60.108a(d)(2) § 60.108a(d)(3) § 60.108a(d)(4) § 60.108a(d)(5) § 60.108a(d)(6) § 60.108a(d)(7)
UU3-310BA	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7500(a)(1)-Table 3.1 § 63.7499(l) § 63.7500(a)	A new or existing limited use boiler or process heater with a heat input capacity of less than or equal to 5	§ 63.7510(g) § 63.7515(d) § 63.7515(g) § 63.7540(a)(12)	§ 63.7555(a) § 63.7555(a)(1) § 63.7555(h) § 63.7560(a)	§ 63.7530(f) § 63.7545(a) § 63.7545(c) § 63.7545(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.7500(a)(3) § 63.7500(e) § 63.7505(a) § 63.7510(g) § 63.7515(g) § 63.7530(f) § 63.7540(a)(12) § 63.7540(a)(13)	million Btu per hour must conduct a tune-up of the boiler or process heater every 5 years as specified in § 63.7540.	§ 63.7540(a)(13)	§ 63.7560(b) § 63.7560(c)	§ 63.7545(e)(1) § 63.7545(e)(6) § 63.7545(e)(7) § 63.7545(e)(8) § 63.7545(e)(8)(i) § 63.7545(f) [G]§ 63.7545(h) § 63.7550(a) [G]§ 63.7550(b) § 63.7550(c) § 63.7550(c)(1) § 63.7550(c)(5)(i) § 63.7550(c)(5)(ii) § 63.7550(c)(5)(iii) § 63.7550(c)(5)(xiv) § 63.7550(c)(5)(xvii) § 63.7550(h) § 63.7550(h)(3)
UU3-310BB	EU	R7300-0001	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(2) § 117.335(g) § 117.340(a) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) [G]§ 117.340(c)(3) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)		
UU3-310BB	EU	R7300-0001	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a) § 117.340(b)(1) § 117.340(b)(3) § 117.340(e) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							[G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)		
UU3-310BB	EU	R7300-0001	NH_3	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(2) § 117.310(c)(2)(B) § 117.340(f)(1)	For process heaters that inject urea or ammonia into the exhaust stream for NO_x control, ammonia emissions must not exceed 10 ppmv at 3.0% O_2, dry.	§ 117.335(a)(2) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(g) § 117.340(b)(1) § 117.340(b)(3) § 117.340(d) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8130 § 117.8130(4)	§ 117.345(a) § 117.345(f) § 117.345(f)(11) [G]§ 117.345(f)(2) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
UU3-310BB	EU	60Ja-0001	NO_X	40 CFR Part 60, Subpart Ja	§ 60.102a(a) § 60.100a § 60.100a(a) § 60.100a(b) § 60.102a § 60.102a(g)	Each owner or operator that is subject to the requirements of this subpart shall comply with the emissions limitations in § 60.102a(b)-(h) on and after	§ 60.104a(a) § 60.104a(c) § 60.104a(i) § 60.104a(i)(1) § 60.104a(i)(2) § 60.104a(i)(3)	§ 60.108a § 60.108a(a)	§ 60.108a § 60.108a(a) § 60.108a(b) § 60.108a(d) § 60.108a(d)(1) § 60.108a(d)(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.102a(g)(2) § 60.102a(g)(2)(ii) § 60.102a(g)(2)(ii)(B)	the date on which the initial performance test, required by § 60.8, is completed, but not later than 60 days after achieving the maximum production rate at which the affected facility will be operated, or 180 days after initial startup, whichever comes first.	§ 60.104a(i)(5) § 60.104a(i)(7) § 60.104a(i)(8) § 60.107a(c)(1) § 60.107a(c)(2) § 60.107a(c)(3) § 60.107a(c)(4) § 60.107a(c)(5) § 60.107a(d) § 60.107a(d)(1) § 60.107a(d)(2) § 60.107a(d)(4) § 60.107a(d)(5) § 60.107a(d)(7) § 60.107a(i) § 60.107a(i)(3) § 60.107a(i)(3)(ii)		§ 60.108a(d)(3) § 60.108a(d)(4) § 60.108a(d)(5) § 60.108a(d)(6) § 60.108a(d)(7)
UU3-310BB	EU	60Ja-0001	Hydrogen Sulfide	40 CFR Part 60, Subpart Ja	§ 60.102a(a) § 60.100a § 60.100a(a) § 60.100a(b) § 60.102a § 60.102a(g) § 60.102a(g)(1) § 60.102a(g)(1)(ii) § 60.103a § 60.103a(c) § 60.103a(c)(2) § 60.103a(d) § 60.103a(d)(1) § 60.103a(d)(5) § 60.103a(e) § 60.103a(e)(1) § 60.103a(e)(2) § 60.103a(e)(3)	Each owner or operator that is subject to the requirements of this subpart shall comply with the emissions limitations in § 60.102a(b)-(h) on and after the date on which the initial performance test, required by § 60.8, is completed, but not later than 60 days after achieving the maximum production rate at which the affected facility will be operated, or 180 days after initial startup, whichever comes first.	§ 60.104a § 60.104a(a) § 60.104a(c) § 60.104a(j) § 60.104a(j)(4)(iv) § 60.107a § 60.107a(a) § 60.107a(a)(2) § 60.107a(a)(2)(i) § 60.107a(a)(2)(ii) § 60.107a(a)(2)(iii) § 60.107a(a)(2)(iv) § 60.107a(i) § 60.107a(i)(1) § 60.107a(i)(1)(ii)	§ 60.108a § 60.108a(a) § 60.108a(c) § 60.108a(c)(6) § 60.108a(c)(6)(i) § 60.108a(c)(6)(ii) § 60.108a(c)(6)(iii) § 60.108a(c)(6)(ix) § 60.108a(c)(6)(v) § 60.108a(c)(6)(vii) § 60.108a(c)(6)(viii) § 60.108a(c)(6)(x)	§ 60.108a § 60.108a(a) § 60.108a(b) § 60.108a(d) § 60.108a(d)(1) § 60.108a(d)(2) § 60.108a(d)(3) § 60.108a(d)(4) § 60.108a(d)(5) § 60.108a(d)(6) § 60.108a(d)(7)
UU3-310BB	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7500(a)(1)-Table 3.1 § 63.7499(l)	A new or existing limited use boiler or process heater with a heat input capacity of	§ 63.7510(g) § 63.7515(d) § 63.7515(g)	§ 63.7555(a) § 63.7555(a)(1) § 63.7555(h)	§ 63.7530(f) § 63.7545(a) § 63.7545(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.7500(a) § 63.7500(a)(3) § 63.7500(e) § 63.7505(a) § 63.7510(g) § 63.7515(g) § 63.7530(f) § 63.7540(a)(12) § 63.7540(a)(13)	less than or equal to 5 million Btu per hour must conduct a tune-up of the boiler or process heater every 5 years as specified in § 63.7540.	§ 63.7540(a)(12) § 63.7540(a)(13)	§ 63.7560(a) § 63.7560(b) § 63.7560(c)	§ 63.7545(e) § 63.7545(e)(1) § 63.7545(e)(6) § 63.7545(e)(7) § 63.7545(e)(8) § 63.7545(e)(8)(i) § 63.7545(f) [G]§ 63.7545(h) § 63.7550(a) [G]§ 63.7550(b) § 63.7550(c) § 63.7550(c)(1) § 63.7550(c)(5)(i) § 63.7550(c)(5)(ii) § 63.7550(c)(5)(iii) § 63.7550(c)(5)(xiv) § 63.7550(c)(5)(xvii) § 63.7550(h) § 63.7550(h)(3)
UU3-311BA	EU	R7300-0001	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(2) § 117.335(g) § 117.340(a) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) [G]§ 117.340(c)(3) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)		
UU3-311BA	EU	R7300-0001	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a) § 117.340(b)(1) § 117.340(b)(3) § 117.340(e) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							[G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)		
UU3-311BA	EU	R7300-0001	NH_3	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(2) § 117.310(c)(2)(B) § 117.340(f)(1)	For process heaters that inject urea or ammonia into the exhaust stream for NO_x control, ammonia emissions must not exceed 10 ppmv at 3.0% O_2, dry.	§ 117.335(a)(2) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(g) § 117.340(b)(1) § 117.340(b)(3) § 117.340(d) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8130 § 117.8130(4)	§ 117.345(a) § 117.345(f) § 117.345(f)(11) [G]§ 117.345(f)(2) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
UU3-311BA	EU	60Ja-0001	NO_X	40 CFR Part 60, Subpart Ja	§ 60.102a(a) § 60.100a § 60.100a(a) § 60.100a(b) § 60.102a	Each owner or operator that is subject to the requirements of this subpart shall comply with the emissions limitations in §	§ 60.104a(a) § 60.104a(c) § 60.104a(i) § 60.104a(i)(1) § 60.104a(i)(2)	§ 60.108a § 60.108a(a)	§ 60.108a § 60.108a(a) § 60.108a(b) § 60.108a(d) § 60.108a(d)(1)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.102a(g) § 60.102a(g)(2) § 60.102a(g)(2)(ii) § 60.102a(g)(2)(ii)(B)	60.102a(b)-(h) on and after the date on which the initial performance test, required by § 60.8, is completed, but not later than 60 days after achieving the maximum production rate at which the affected facility will be operated, or 180 days after initial startup, whichever comes first.	§ 60.104a(i)(3) § 60.104a(i)(5) § 60.104a(i)(7) § 60.104a(i)(8) § 60.107a(c)(1) § 60.107a(c)(2) § 60.107a(c)(3) § 60.107a(c)(4) § 60.107a(c)(5) § 60.107a(d) § 60.107a(d)(1) § 60.107a(d)(2) § 60.107a(d)(4) § 60.107a(d)(5) § 60.107a(d)(7) § 60.107a(i) § 60.107a(i)(3) § 60.107a(i)(3)(ii)		§ 60.108a(d)(2) § 60.108a(d)(3) § 60.108a(d)(4) § 60.108a(d)(5) § 60.108a(d)(6) § 60.108a(d)(7)
UU3-311BA	EU	60Ja-0001	Hydrogen Sulfide	40 CFR Part 60, Subpart Ja	§ 60.102a(a) § 60.100a § 60.100a(a) § 60.100a(b) § 60.102a § 60.102a(g) § 60.102a(g)(1) § 60.102a(g)(1)(ii) § 60.103a § 60.103a(c) § 60.103a(c)(2) § 60.103a(d) § 60.103a(d)(1) § 60.103a(d)(5) § 60.103a(e) § 60.103a(e)(1) § 60.103a(e)(2) § 60.103a(e)(3)	Each owner or operator that is subject to the requirements of this subpart shall comply with the emissions limitations in § 60.102a(b)-(h) on and after the date on which the initial performance test, required by § 60.8, is completed, but not later than 60 days after achieving the maximum production rate at which the affected facility will be operated, or 180 days after initial startup, whichever comes first.	§ 60.104a § 60.104a(a) § 60.104a(c) § 60.104a(j) § 60.104a(j)(4)(iv) § 60.107a § 60.107a(a) § 60.107a(a)(2) § 60.107a(a)(2)(i) § 60.107a(a)(2)(ii) § 60.107a(a)(2)(iii) § 60.107a(a)(2)(iv) § 60.107a(i) § 60.107a(i)(1) § 60.107a(i)(1)(ii)	§ 60.108a § 60.108a(a) § 60.108a(c) § 60.108a(c)(6) § 60.108a(c)(6)(i) § 60.108a(c)(6)(ii) § 60.108a(c)(6)(iii) § 60.108a(c)(6)(ix) § 60.108a(c)(6)(v) § 60.108a(c)(6)(vii) § 60.108a(c)(6)(viii) § 60.108a(c)(6)(x)	§ 60.108a § 60.108a(a) § 60.108a(b) § 60.108a(d) § 60.108a(d)(1) § 60.108a(d)(2) § 60.108a(d)(3) § 60.108a(d)(4) § 60.108a(d)(5) § 60.108a(d)(6) § 60.108a(d)(7)
UU3-311BA	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart	§ 63.7500(a)(1)-Table 3.1	A new or existing limited use boiler or process heater	§ 63.7510(g) § 63.7515(d)	§ 63.7555(a) § 63.7555(a)(1)	§ 63.7530(f) § 63.7545(a)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				DDDDD	§ 63.7499(l) § 63.7500(a) § 63.7500(a)(3) § 63.7500(e) § 63.7505(a) § 63.7510(g) § 63.7515(g) § 63.7530(f) § 63.7540(a)(12) § 63.7540(a)(13)	with a heat input capacity of less than or equal to 5 million Btu per hour must conduct a tune-up of the boiler or process heater every 5 years as specified in § 63.7540.	§ 63.7515(g) § 63.7540(a)(12) § 63.7540(a)(13)	§ 63.7555(h) § 63.7560(a) § 63.7560(b) § 63.7560(c)	§ 63.7545(c) § 63.7545(e) § 63.7545(e)(1) § 63.7545(e)(6) § 63.7545(e)(7) § 63.7545(e)(8) § 63.7545(e)(8)(i) § 63.7545(f) [G]§ 63.7545(h) § 63.7550(a) [G]§ 63.7550(b) § 63.7550(c) § 63.7550(c)(1) § 63.7550(c)(5)(i) § 63.7550(c)(5)(ii) § 63.7550(c)(5)(iii) § 63.7550(c)(5)(xiv) § 63.7550(c)(5)(xvii) § 63.7550(h) § 63.7550(h)(3)
UU3-311BB	EU	R7300-0001	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(2) § 117.335(g) § 117.340(a) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) [G]§ 117.340(c)(3) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						comply with § 117.320.	§ 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)		§ 117.8100(c)
UU3-311BB	EU	R7300-0001	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a) § 117.340(b)(1) § 117.340(b)(3) § 117.340(e) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)		
UU3-311BB	EU	R7300-0001	NH_3	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(2) § 117.310(c)(2)(B) § 117.340(f)(1)	For process heaters that inject urea or ammonia into the exhaust stream for NO_x control, ammonia emissions must not exceed 10 ppmv at 3.0% O_2, dry.	§ 117.335(a)(2) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(g) § 117.340(b)(1) § 117.340(b)(3) § 117.340(d) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8130 § 117.8130(4)	§ 117.345(a) § 117.345(f) § 117.345(f)(11) [G]§ 117.345(f)(2) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
UU3-311BB	EU	60Ja-0001	NO_X	40 CFR Part 60, Subpart Ja	§ 60.102a(a) § 60.100a § 60.100a(a) § 60.100a(b)	Each owner or operator that is subject to the requirements of this subpart shall comply with the	§ 60.104a(a) § 60.104a(c) § 60.104a(i) § 60.104a(i)(1)	§ 60.108a § 60.108a(a)	§ 60.108a § 60.108a(a) § 60.108a(b) § 60.108a(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.102a § 60.102a(g) § 60.102a(g)(2) § 60.102a(g)(2)(ii) § 60.102a(g)(2)(ii)(B)	emissions limitations in § 60.102a(b)-(h) on and after the date on which the initial performance test, required by § 60.8, is completed, but not later than 60 days after achieving the maximum production rate at which the affected facility will be operated, or 180 days after initial startup, whichever comes first.	§ 60.104a(i)(2) § 60.104a(i)(3) § 60.104a(i)(5) § 60.104a(i)(7) § 60.104a(i)(8) § 60.107a(c)(1) § 60.107a(c)(2) § 60.107a(c)(3) § 60.107a(c)(4) § 60.107a(c)(5) § 60.107a(d) § 60.107a(d)(1) § 60.107a(d)(2) § 60.107a(d)(4) § 60.107a(d)(5) § 60.107a(d)(7) § 60.107a(i) § 60.107a(i)(3) § 60.107a(i)(3)(ii)		§ 60.108a(d)(1) § 60.108a(d)(2) § 60.108a(d)(3) § 60.108a(d)(4) § 60.108a(d)(5) § 60.108a(d)(6) § 60.108a(d)(7)
UU3-311BB	EU	60Ja-0001	Hydrogen Sulfide	40 CFR Part 60, Subpart Ja	§ 60.102a(a) § 60.100a § 60.100a(a) § 60.100a(b) § 60.102a § 60.102a(g) § 60.102a(g)(1) § 60.102a(g)(1)(ii) § 60.103a § 60.103a(c) § 60.103a(c)(2) § 60.103a(d) § 60.103a(d)(1) § 60.103a(d)(5) § 60.103a(e) § 60.103a(e)(1) § 60.103a(e)(2) § 60.103a(e)(3)	Each owner or operator that is subject to the requirements of this subpart shall comply with the emissions limitations in § 60.102a(b)-(h) on and after the date on which the initial performance test, required by § 60.8, is completed, but not later than 60 days after achieving the maximum production rate at which the affected facility will be operated, or 180 days after initial startup, whichever comes first.	§ 60.104a § 60.104a(a) § 60.104a(c) § 60.104a(j) § 60.104a(j)(4)(iv) § 60.107a § 60.107a(a) § 60.107a(a)(2) § 60.107a(a)(2)(i) § 60.107a(a)(2)(ii) § 60.107a(a)(2)(iii) § 60.107a(a)(2)(iv) § 60.107a(i) § 60.107a(i)(1) § 60.107a(i)(1)(ii)	§ 60.108a § 60.108a(a) § 60.108a(c) § 60.108a(c)(6) § 60.108a(c)(6)(i) § 60.108a(c)(6)(ii) § 60.108a(c)(6)(iii) § 60.108a(c)(6)(ix) § 60.108a(c)(6)(v) § 60.108a(c)(6)(vii) § 60.108a(c)(6)(viii) § 60.108a(c)(6)(x)	§ 60.108a § 60.108a(a) § 60.108a(b) § 60.108a(d) § 60.108a(d)(1) § 60.108a(d)(2) § 60.108a(d)(3) § 60.108a(d)(4) § 60.108a(d)(5) § 60.108a(d)(6) § 60.108a(d)(7)
UU3-311BB	EU	63DDDDD	112(B)	40 CFR Part 63,	§ 63.7500(a)(1)-Table	A new or existing limited	§ 63.7510(g)	§ 63.7555(a)	§ 63.7530(f)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		-1	HAPS	Subpart DDDDD	3.1 § 63.7499(l) § 63.7500(a) § 63.7500(a)(3) § 63.7500(e) § 63.7505(a) § 63.7510(g) § 63.7515(g) § 63.7530(f) § 63.7540(a)(12) § 63.7540(a)(13)	use boiler or process heater with a heat input capacity of less than or equal to 5 million Btu per hour must conduct a tune-up of the boiler or process heater every 5 years as specified in § 63.7540.	§ 63.7515(d) § 63.7515(g) § 63.7540(a)(12) § 63.7540(a)(13)	§ 63.7555(a)(1) § 63.7555(h) § 63.7560(a) § 63.7560(b) § 63.7560(c)	§ 63.7545(a) § 63.7545(c) § 63.7545(e) § 63.7545(e)(1) § 63.7545(e)(6) § 63.7545(e)(7) § 63.7545(e)(8) § 63.7545(e)(8)(i) § 63.7545(f) [G]§ 63.7545(h) § 63.7550(a) [G]§ 63.7550(b) § 63.7550(c) § 63.7550(c)(1) § 63.7550(c)(5)(i) § 63.7550(c)(5)(ii) § 63.7550(c)(5)(iii) § 63.7550(c)(5)(xiv) § 63.7550(c)(5)(xvii) § 63.7550(h) § 63.7550(h)(3)
UU3-312BA	EU	R7300-0001	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(2) § 117.335(g) § 117.340(a) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) [G]§ 117.340(c)(3) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						specified in § 117.9800 to comply with § 117.320.	§ 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)		[G]§ 117.8010(8) § 117.8100(c)
UU3-312BA	EU	R7300-0001	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a) § 117.340(b)(1) § 117.340(b)(3) § 117.340(e) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)		
UU3-312BA	EU	R7300-0001	NH_3	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(2) § 117.310(c)(2)(B) § 117.340(f)(1)	For process heaters that inject urea or ammonia into the exhaust stream for NO_x control, ammonia emissions must not exceed 10 ppmv at 3.0% O_2, dry.	§ 117.335(a)(2) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(g) § 117.340(b)(1) § 117.340(b)(3) § 117.340(d) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8130 § 117.8130(4)	§ 117.345(a) § 117.345(f) § 117.345(f)(11) [G]§ 117.345(f)(2) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
UU3-312BA	EU	60Ja-0001	NO_X	40 CFR Part 60, Subpart Ja	§ 60.102a(a) § 60.100a § 60.100a(a)	Each owner or operator that is subject to the requirements of this subpart	§ 60.104a(a) § 60.104a(c) § 60.104a(i)	§ 60.108a § 60.108a(a)	§ 60.108a § 60.108a(a) § 60.108a(b)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.100a(b) § 60.102a § 60.102a(g) § 60.102a(g)(2) § 60.102a(g)(2)(ii) § 60.102a(g)(2)(ii)(B)	shall comply with the emissions limitations in § 60.102a(b)-(h) on and after the date on which the initial performance test, required by § 60.8, is completed, but not later than 60 days after achieving the maximum production rate at which the affected facility will be operated, or 180 days after initial startup, whichever comes first.	§ 60.104a(i)(1) § 60.104a(i)(2) § 60.104a(i)(3) § 60.104a(i)(5) § 60.104a(i)(7) § 60.104a(i)(8) § 60.107a(c)(1) § 60.107a(c)(2) § 60.107a(c)(3) § 60.107a(c)(4) § 60.107a(c)(5) § 60.107a(d) § 60.107a(d)(1) § 60.107a(d)(2) § 60.107a(d)(4) § 60.107a(d)(5) § 60.107a(d)(7) § 60.107a(i) § 60.107a(i)(3) § 60.107a(i)(3)(ii)		§ 60.108a(d) § 60.108a(d)(1) § 60.108a(d)(2) § 60.108a(d)(3) § 60.108a(d)(4) § 60.108a(d)(5) § 60.108a(d)(6) § 60.108a(d)(7)
UU3-312BA	EU	60Ja-0001	Hydrogen Sulfide	40 CFR Part 60, Subpart Ja	§ 60.102a(a) § 60.100a § 60.100a(a) § 60.100a(b) § 60.102a § 60.102a(g) § 60.102a(g)(1) § 60.102a(g)(1)(ii) § 60.103a § 60.103a(c) § 60.103a(c)(2) § 60.103a(d) § 60.103a(d)(1) § 60.103a(d)(5) § 60.103a(e) § 60.103a(e)(1) § 60.103a(e)(2) § 60.103a(e)(3)	Each owner or operator that is subject to the requirements of this subpart shall comply with the emissions limitations in § 60.102a(b)-(h) on and after the date on which the initial performance test, required by § 60.8, is completed, but not later than 60 days after achieving the maximum production rate at which the affected facility will be operated, or 180 days after initial startup, whichever comes first.	§ 60.104a § 60.104a(a) § 60.104a(c) § 60.104a(j) § 60.104a(j)(4)(iv) § 60.107a § 60.107a(a) § 60.107a(a)(2) § 60.107a(a)(2)(i) § 60.107a(a)(2)(ii) § 60.107a(a)(2)(iii) § 60.107a(a)(2)(iv) § 60.107a(i) § 60.107a(i)(1) § 60.107a(i)(1)(ii)	§ 60.108a § 60.108a(a) § 60.108a(c) § 60.108a(c)(6) § 60.108a(c)(6)(i) § 60.108a(c)(6)(ii) § 60.108a(c)(6)(iii) § 60.108a(c)(6)(ix) § 60.108a(c)(6)(v) § 60.108a(c)(6)(vii) § 60.108a(c)(6)(viii) § 60.108a(c)(6)(x)	§ 60.108a § 60.108a(a) § 60.108a(b) § 60.108a(d) § 60.108a(d)(1) § 60.108a(d)(2) § 60.108a(d)(3) § 60.108a(d)(4) § 60.108a(d)(5) § 60.108a(d)(6) § 60.108a(d)(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
UU3-312BA	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7500(a)(1)-Table 3.1 § 63.7499(l) § 63.7500(a) § 63.7500(a)(3) § 63.7500(e) § 63.7505(a) § 63.7510(g) § 63.7515(g) § 63.7530(f) § 63.7540(a)(12) § 63.7540(a)(13)	A new or existing limited use boiler or process heater with a heat input capacity of less than or equal to 5 million Btu per hour must conduct a tune-up of the boiler or process heater every 5 years as specified in § 63.7540.	§ 63.7510(g) § 63.7515(d) § 63.7515(g) § 63.7540(a)(12) § 63.7540(a)(13)	§ 63.7555(a) § 63.7555(a)(1) § 63.7555(h) § 63.7560(a) § 63.7560(b) § 63.7560(c)	§ 63.7530(f) § 63.7545(a) § 63.7545(c) § 63.7545(e) § 63.7545(e)(1) § 63.7545(e)(6) § 63.7545(e)(7) § 63.7545(e)(8) § 63.7545(e)(8)(i) § 63.7545(f) [G]§ 63.7545(h) § 63.7550(a) [G]§ 63.7550(b) § 63.7550(c) § 63.7550(c)(1) § 63.7550(c)(5)(i) § 63.7550(c)(5)(ii) § 63.7550(c)(5)(iii) § 63.7550(c)(5)(xiv) § 63.7550(c)(5)(xvii) § 63.7550(h) § 63.7550(h)(3)
UU3-312BB	EU	R7300-0001	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(2) § 117.335(g) § 117.340(a) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) [G]§ 117.340(c)(3) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						alternative methods specified in § 117.9800 to comply with § 117.320.	§ 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)		[G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
UU3-312BB	EU	R7300-0001	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a) § 117.340(b)(1) § 117.340(b)(3) § 117.340(e) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)		
UU3-312BB	EU	R7300-0001	NH_3	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(2) § 117.310(c)(2)(B) § 117.340(f)(1)	For process heaters that inject urea or ammonia into the exhaust stream for NO_x control, ammonia emissions must not exceed 10 ppmv at 3.0% O_2, dry.	§ 117.335(a)(2) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(g) § 117.340(b)(1) § 117.340(b)(3) § 117.340(d) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8130 § 117.8130(4)	§ 117.345(a) § 117.345(f) § 117.345(f)(11) [G]§ 117.345(f)(2) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
UU3-312BB	EU	60Ja-0001	NO_X	40 CFR Part 60, Subpart Ja	§ 60.102a(a) § 60.100a	Each owner or operator that is subject to the	§ 60.104a(a) § 60.104a(c)	§ 60.108a § 60.108a(a)	§ 60.108a § 60.108a(a)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.100a(a) § 60.100a(b) § 60.102a § 60.102a(g) § 60.102a(g)(2) § 60.102a(g)(2)(ii) § 60.102a(g)(2)(ii)(B)	requirements of this subpart shall comply with the emissions limitations in § 60.102a(b)-(h) on and after the date on which the initial performance test, required by § 60.8, is completed, but not later than 60 days after achieving the maximum production rate at which the affected facility will be operated, or 180 days after initial startup, whichever comes first.	§ 60.104a(i) § 60.104a(i)(1) § 60.104a(i)(2) § 60.104a(i)(3) § 60.104a(i)(5) § 60.104a(i)(7) § 60.104a(i)(8) § 60.107a(c)(1) § 60.107a(c)(2) § 60.107a(c)(3) § 60.107a(c)(4) § 60.107a(c)(5) § 60.107a(d) § 60.107a(d)(1) § 60.107a(d)(2) § 60.107a(d)(4) § 60.107a(d)(5) § 60.107a(d)(7) § 60.107a(i) § 60.107a(i)(3) § 60.107a(i)(3)(ii)		§ 60.108a(b) § 60.108a(d) § 60.108a(d)(1) § 60.108a(d)(2) § 60.108a(d)(3) § 60.108a(d)(4) § 60.108a(d)(5) § 60.108a(d)(6) § 60.108a(d)(7)
UU3-312BB	EU	60Ja-0001	Hydrogen Sulfide	40 CFR Part 60, Subpart Ja	§ 60.102a(a) § 60.100a § 60.100a(a) § 60.100a(b) § 60.102a § 60.102a(g) § 60.102a(g)(1) § 60.102a(g)(1)(ii) § 60.103a § 60.103a(c) § 60.103a(c)(2) § 60.103a(d) § 60.103a(d)(1) § 60.103a(d)(5) § 60.103a(e) § 60.103a(e)(1) § 60.103a(e)(2) § 60.103a(e)(3)	Each owner or operator that is subject to the requirements of this subpart shall comply with the emissions limitations in § 60.102a(b)-(h) on and after the date on which the initial performance test, required by § 60.8, is completed, but not later than 60 days after achieving the maximum production rate at which the affected facility will be operated, or 180 days after initial startup, whichever comes first.	§ 60.104a § 60.104a(a) § 60.104a(c) § 60.104a(j) § 60.104a(j)(4)(iv) § 60.107a § 60.107a(a) § 60.107a(a)(2) § 60.107a(a)(2)(i) § 60.107a(a)(2)(ii) § 60.107a(a)(2)(iii) § 60.107a(a)(2)(iv) § 60.107a(i) § 60.107a(i)(1) § 60.107a(i)(1)(ii)	§ 60.108a § 60.108a(a) § 60.108a(c) § 60.108a(c)(6) § 60.108a(c)(6)(i) § 60.108a(c)(6)(ii) § 60.108a(c)(6)(iii) § 60.108a(c)(6)(ix) § 60.108a(c)(6)(v) § 60.108a(c)(6)(vii) § 60.108a(c)(6)(viii) § 60.108a(c)(6)(x)	§ 60.108a § 60.108a(a) § 60.108a(b) § 60.108a(d) § 60.108a(d)(1) § 60.108a(d)(2) § 60.108a(d)(3) § 60.108a(d)(4) § 60.108a(d)(5) § 60.108a(d)(6) § 60.108a(d)(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
UU3-312BB	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7500(a)(1)-Table 3.1 § 63.7499(l) § 63.7500(a) § 63.7500(a)(3) § 63.7500(e) § 63.7505(a) § 63.7510(g) § 63.7515(g) § 63.7530(f) § 63.7540(a)(12) § 63.7540(a)(13)	A new or existing limited use boiler or process heater with a heat input capacity of less than or equal to 5 million Btu per hour must conduct a tune-up of the boiler or process heater every 5 years as specified in § 63.7540.	§ 63.7510(g) § 63.7515(d) § 63.7515(g) § 63.7540(a)(12) § 63.7540(a)(13)	§ 63.7555(a) § 63.7555(a)(1) § 63.7555(h) § 63.7560(a) § 63.7560(b) § 63.7560(c)	§ 63.7530(f) § 63.7545(a) § 63.7545(c) § 63.7545(e) § 63.7545(e)(1) § 63.7545(e)(6) § 63.7545(e)(7) § 63.7545(e)(8) § 63.7545(e)(8)(i) § 63.7545(f) [G]§ 63.7545(h) § 63.7550(a) [G]§ 63.7550(b) § 63.7550(c) § 63.7550(c)(1) § 63.7550(c)(5)(i) § 63.7550(c)(5)(ii) § 63.7550(c)(5)(iii) § 63.7550(c)(5)(xiv) § 63.7550(c)(5)(xvii) § 63.7550(h) § 63.7550(h)(3)
UU3-312BC	EU	R7300-0001	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(2) § 117.335(g) § 117.340(a) § 117.340(c)(1) [G]§ 117.340(c)(3) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						alternative methods specified in § 117.9800 to comply with § 117.320.	§ 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)		[G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
UU3-312BC	EU	R7300-0001	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a) § 117.340(b)(1) § 117.340(b)(3) § 117.340(e) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) [G]§ 117.345(f)(2) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)		
UU3-312BC	EU	R7300-0001	NH_3	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(2) § 117.310(c)(2)(B) § 117.340(f)(1)	For process heaters that inject urea or ammonia into the exhaust stream for NO_x control, ammonia emissions must not exceed 10 ppmv at 3.0% O_2, dry.	§ 117.335(a)(2) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(g) § 117.340(d) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8130 § 117.8130(4)	§ 117.345(a) § 117.345(f) § 117.345(f)(11) [G]§ 117.345(f)(2) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
UU3-312BC	EU	60Ja-0001	NO_X	40 CFR Part 60, Subpart Ja	§ 60.102a(a) § 60.100a § 60.100a(a) § 60.100a(b) § 60.102a § 60.102a(g)	Each owner or operator that is subject to the requirements of this subpart shall comply with the emissions limitations in § 60.102a(b)-(h) on and after	§ 60.104a(a) § 60.104a(c) § 60.104a(i) § 60.104a(i)(1) § 60.104a(i)(2) § 60.104a(i)(3)	§ 60.108a § 60.108a(a)	§ 60.108a § 60.108a(a) § 60.108a(b) § 60.108a(d) § 60.108a(d)(1) § 60.108a(d)(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.102a(g)(2) § 60.102a(g)(2)(ii) § 60.102a(g)(2)(ii)(B)	the date on which the initial performance test, required by § 60.8, is completed, but not later than 60 days after achieving the maximum production rate at which the affected facility will be operated, or 180 days after initial startup, whichever comes first.	§ 60.104a(i)(5) § 60.104a(i)(7) § 60.104a(i)(8) § 60.107a(c)(1) § 60.107a(c)(2) § 60.107a(c)(3) § 60.107a(c)(4) § 60.107a(c)(5) § 60.107a(d) § 60.107a(d)(1) § 60.107a(d)(2) § 60.107a(d)(4) § 60.107a(d)(5) § 60.107a(d)(7) § 60.107a(i) § 60.107a(i)(3) § 60.107a(i)(3)(ii)		§ 60.108a(d)(3) § 60.108a(d)(4) § 60.108a(d)(5) § 60.108a(d)(6) § 60.108a(d)(7)
UU3-312BC	EU	60Ja-0001	Hydrogen Sulfide	40 CFR Part 60, Subpart Ja	§ 60.102a(a) § 60.100a § 60.100a(a) § 60.100a(b) § 60.102a § 60.102a(g) § 60.102a(g)(1) § 60.102a(g)(1)(ii) § 60.103a § 60.103a(c) § 60.103a(c)(2) § 60.103a(d) § 60.103a(d)(1) § 60.103a(d)(5) § 60.103a(e) § 60.103a(e)(1) § 60.103a(e)(2) § 60.103a(e)(3)	Each owner or operator that is subject to the requirements of this subpart shall comply with the emissions limitations in § 60.102a(b)-(h) on and after the date on which the initial performance test, required by § 60.8, is completed, but not later than 60 days after achieving the maximum production rate at which the affected facility will be operated, or 180 days after initial startup, whichever comes first.	§ 60.104a § 60.104a(a) § 60.104a(c) § 60.104a(j) § 60.104a(j)(4)(iv) § 60.107a § 60.107a(a) § 60.107a(a)(2) § 60.107a(a)(2)(i) § 60.107a(a)(2)(ii) § 60.107a(a)(2)(iii) § 60.107a(a)(2)(iv) § 60.107a(i) § 60.107a(i)(1) § 60.107a(i)(1)(ii)	§ 60.108a § 60.108a(a) § 60.108a(c) § 60.108a(c)(6) § 60.108a(c)(6)(i) § 60.108a(c)(6)(ii) § 60.108a(c)(6)(iii) § 60.108a(c)(6)(ix) § 60.108a(c)(6)(v) § 60.108a(c)(6)(vii) § 60.108a(c)(6)(viii) § 60.108a(c)(6)(x)	§ 60.108a § 60.108a(a) § 60.108a(b) § 60.108a(d) § 60.108a(d)(1) § 60.108a(d)(2) § 60.108a(d)(3) § 60.108a(d)(4) § 60.108a(d)(5) § 60.108a(d)(6) § 60.108a(d)(7)
UU3-312BC	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7500(a)(1)-Table 3.1 § 63.7499(l)	A new or existing limited use boiler or process heater with a heat input capacity of	§ 63.7510(g) § 63.7515(d) § 63.7515(g)	§ 63.7555(a) § 63.7555(a)(1) § 63.7555(h)	§ 63.7530(f) § 63.7545(a) § 63.7545(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.7500(a) § 63.7500(a)(3) § 63.7500(e) § 63.7505(a) § 63.7510(g) § 63.7515(g) § 63.7530(f) § 63.7540(a)(12) § 63.7540(a)(13)	less than or equal to 5 million Btu per hour must conduct a tune-up of the boiler or process heater every 5 years as specified in § 63.7540.	§ 63.7540(a)(12) § 63.7540(a)(13)	§ 63.7560(a) § 63.7560(b) § 63.7560(c)	§ 63.7545(e) § 63.7545(e)(1) § 63.7545(e)(6) § 63.7545(e)(7) § 63.7545(e)(8) § 63.7545(e)(8)(i) § 63.7545(f) [G]§ 63.7545(h) § 63.7550(a) [G]§ 63.7550(b) § 63.7550(c) § 63.7550(c)(1) § 63.7550(c)(5)(i) § 63.7550(c)(5)(ii) § 63.7550(c)(5)(iii) § 63.7550(c)(5)(xiv) § 63.7550(c)(5)(xvii) § 63.7550(h) § 63.7550(h)(3)
UU3-313B	EU	R7300-0002	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C) § 117.8000(b) § 117.8000(c) § 117.8000(c)(1) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
UU3-313B	EU	R7300-0002	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B) § 117.310(c)(3)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.8000(b) § 117.8000(c) § 117.8000(c)(2) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8120 § 117.8120(2) [G]§ 117.8120(2)(A) § 117.8120(2)(B)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
UU3-313B	EU	60Ja-0002	NO_X	40 CFR Part 60, Subpart Ja	§ 60.102a(a) § 60.100a § 60.100a(a) § 60.100a(b) § 60.102a § 60.102a(g) § 60.102a(g)(2) § 60.102a(g)(2)(i) § 60.102a(g)(2)(i)(B)	Each owner or operator that is subject to the requirements of this subpart shall comply with the emissions limitations in paragraphs (b) through (i) of this section on and after the date on which the initial performance test, required by §60.8, is completed, but not later than 60 days after achieving the maximum production rate at which the affected facility will be operated or 180 days after initial startup, whichever comes first.	§ 60.104a § 60.104a(a) § 60.104a(c) § 60.104a(i) § 60.104a(i)(1) § 60.104a(i)(2) § 60.104a(i)(3) § 60.104a(i)(5) § 60.104a(i)(6) § 60.104a(i)(7) § 60.104a(i)(8) § 60.107a § 60.107a(c)(3) § 60.107a(c)(4) § 60.107a(c)(5) § 60.107a(d) § 60.107a(d)(1) § 60.107a(d)(2) § 60.107a(d)(5) § 60.107a(d)(7) § 60.107a(i)	§ 60.108a § 60.108a(a)	§ 60.108a § 60.108a(a) § 60.108a(b) § 60.108a(d) § 60.108a(d)(1) § 60.108a(d)(2) § 60.108a(d)(3) § 60.108a(d)(4) § 60.108a(d)(5) § 60.108a(d)(6) § 60.108a(d)(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 60.107a(i)(3) § 60.107a(i)(3)(i) § 60.107a(i)(5)		
UU3-313B	EU	60Ja-0002	H2S	40 CFR Part 60, Subpart Ja	§ 60.102a(a) § 60.100a § 60.100a(a) § 60.100a(b) § 60.102a § 60.102a(g) § 60.102a(g)(1) § 60.102a(g)(1)(ii) § 60.103a § 60.103a(c) § 60.103a(c)(2) § 60.103a(d) § 60.103a(d)(1) § 60.103a(d)(5) § 60.103a(e) § 60.103a(e)(1) § 60.103a(e)(2) § 60.103a(e)(3)	Each owner or operator that is subject to the requirements of this subpart shall comply with the emissions limitations in paragraphs (b) through (i) of this section on and after the date on which the initial performance test, required by §60.8, is completed, but not later than 60 days after achieving the maximum production rate at which the affected facility will be operated or 180 days after initial startup, whichever comes first.	§ 60.104a § 60.104a(a) § 60.104a(c) § 60.104a(j) § 60.104a(j)(4)(iv) § 60.107a § 60.107a(a) § 60.107a(a)(2) § 60.107a(a)(2)(i) § 60.107a(a)(2)(ii) § 60.107a(a)(2)(iii) § 60.107a(a)(2)(iv) § 60.107a(i) § 60.107a(i)(1) § 60.107a(i)(1)(ii)	§ 60.108a § 60.108a(a) § 60.108a(c) § 60.108a(c)(6) § 60.108a(c)(6)(i) § 60.108a(c)(6)(ii) § 60.108a(c)(6)(iii) § 60.108a(c)(6)(ix) § 60.108a(c)(6)(v) § 60.108a(c)(6)(vii) § 60.108a(c)(6)(viii) § 60.108a(c)(6)(x)	§ 60.108a § 60.108a(a) § 60.108a(b) § 60.108a(d) § 60.108a(d)(1) § 60.108a(d)(2) § 60.108a(d)(3) § 60.108a(d)(4) § 60.108a(d)(5) § 60.108a(d)(6) § 60.108a(d)(7)
UU3-313B	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7500(a)(1)-Table 3.1 § 63.7499(l) § 63.7500(a) § 63.7500(a)(3) § 63.7500(e) § 63.7505(a) § 63.7510(g) § 63.7515(g) § 63.7530(f) § 63.7540(a)(12) § 63.7540(a)(13)	A new or existing limited use boiler or process heater with a heat input capacity of less than or equal to 5 million Btu per hour must conduct a tune-up of the boiler or process heater every 5 years as specified in § 63.7540.	§ 63.7510(g) § 63.7515(d) § 63.7515(g) § 63.7540(a)(12) § 63.7540(a)(13)	§ 63.7555(a) § 63.7555(a)(1) § 63.7555(h) § 63.7560(a) § 63.7560(b) § 63.7560(c)	§ 63.7530(f) § 63.7545(a) § 63.7545(c) § 63.7545(e) § 63.7545(e)(1) § 63.7545(e)(6) § 63.7545(e)(7) § 63.7545(e)(8) § 63.7545(e)(8)(i) § 63.7545(f) [G]§ 63.7545(h) § 63.7550(a) [G]§ 63.7550(b) § 63.7550(c) § 63.7550(c)(1) § 63.7550(c)(5)(i) § 63.7550(c)(5)(ii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
									§ 63.7550(c)(5)(iii) § 63.7550(c)(5)(xiv) § 63.7550(c)(5)(xvii) § 63.7550(h) § 63.7550(h)(3)
UU3-CT	EU	R5760-0025	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Cooling Towers	§ 115.767(3) § 115.766(i)	Any site for which no stream directed to a cooling tower heat exchange system contains 5.0% or greater by weight HRVOC is exempt from the requirements of _115.761 of this title (relating to Site-wide Cap).	§ 115.764(c) § 115.764(d) § 115.764(e)(1)	§ 115.766(c) § 115.766(d) [G]§ 115.766(e) § 115.766(i)(1)	§ 115.766(i)(2)
UU3-CT	EU	63CC-002	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.654(a) § 63.640(h)(6)	Except as specified in paragraph (b) of this section, the owner or operator of a heat exchange system that meets the criteria in §63.640(c)(8) must comply with the requirements of paragraphs (c) through (g) of this section.	§ 63.642(d)(1) § 63.642(d)(3) § 63.642(d)(4) [G]§ 63.654(c) [G]§ 63.654(d) § 63.654(e) [G]§ 63.654(f) [G]§ 63.654(g)	§ 63.642(e) § 63.655(h)(1) [G]§ 63.655(i)(4) § 63.655(i)(5)	§ 63.642(d)(2) § 63.642(f) § 63.655(f) § 63.655(f)(1)(vi) § 63.655(f)(4) § 63.655(g) [G]§ 63.655(g)(9) § 63.655(h)(1)
UU3-FUG1	EU	60GGGa-01	VOC	40 CFR Part 60, Subpart GGGa	§ 60.592a(a) § 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(g) § 60.482-7a(a)(1) § 60.482-7a(b) [G]§ 60.482-7a(d) [G]§ 60.482-7a(e) [G]§ 60.482-7a(h) § 60.485a(b) § 60.485a(c) § 60.485a(c)(1) § 60.485a(f) § 60.486a(a)(1) § 60.486a(k)	Comply with the requirements as stated in §60.482-7a for valves in gas/vapor or light liquid service.	§ 60.482-1a(f)(1) § 60.482-1a(f)(2) [G]§ 60.482-1a(f)(3) § 60.482-1a(g) § 60.482-7a(a)(1) [G]§ 60.482-7a(a)(2) [G]§ 60.482-7a(c) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2) § 60.485a(c)(2) [G]§ 60.485a(d) [G]§ 60.485a(e) § 60.593a(d)	§ 60.482-1a(g) § 60.485a(b)(2) § 60.486a(a)(2) [G]§ 60.486a(a)(3) [G]§ 60.486a(b) [G]§ 60.486a(c) § 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(2) [G]§ 60.486a(e)(4) [G]§ 60.486a(e)(8) § 60.486a(f) § 60.486a(f)(1) § 60.486a(f)(2)	§ 60.482-1a(g) § 60.487a(a) § 60.487a(b) § 60.487a(b)(1) § 60.487a(b)(2) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(i) § 60.487a(c)(2)(ii) § 60.487a(c)(2)(ix) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.592a(d) § 60.592a(e)				
UU3-FUG1	EU	60GGGa-01	VOC	40 CFR Part 60, Subpart GGGa	§ 60.592a(a) § 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(g) [G]§ 60.482-2a(c)(2) [G]§ 60.482-7a(e) § 60.482-8a(a) § 60.482-8a(a)(2) § 60.482-8a(b) [G]§ 60.482-8a(c) § 60.482-8a(d) § 60.482-9a(a) § 60.482-9a(b) § 60.482-9a(c) § 60.482-9a(c)(1) § 60.482-9a(e) § 60.482-9a(f) § 60.485a(b) § 60.485a(f) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k) § 60.592a(d) § 60.592a(e)	Comply with the requirements as stated in §60.482-8a for valves in heavy liquid service.	§ 60.482-1a(g) § 60.482-8a(a)(1) § 60.482-9a(a) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2) [G]§ 60.485a(d)	§ 60.482-1a(g) § 60.485a(b)(2) [G]§ 60.486a(a)(3) [G]§ 60.486a(b) [G]§ 60.486a(c) § 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(8)	§ 60.487a(a) § 60.487a(b) § 60.487a(b)(1) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(ix) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)
UU3-FUG1	EU	60GGGa-01	VOC	40 CFR Part 60, Subpart GGGa	§ 60.592a(a) § 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(g) [G]§ 60.482-2a(c)(2) [G]§ 60.482-7a(e) § 60.482-8a(a) § 60.482-8a(a)(2) § 60.482-8a(b) [G]§ 60.482-8a(c) § 60.482-8a(d) § 60.482-9a(a)	Comply with the requirements as stated in §60.482-8a for connectors in heavy liquid service.	§ 60.482-1a(g) § 60.482-8a(a)(1) § 60.482-9a(a) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2) [G]§ 60.485a(d)	§ 60.482-1a(g) § 60.485a(b)(2) [G]§ 60.486a(a)(3) [G]§ 60.486a(b) [G]§ 60.486a(c) § 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(8)	§ 60.487a(a) § 60.487a(b) § 60.487a(b)(1) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(ix) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.482-9a(b) § 60.482-9a(c) § 60.482-9a(c)(1) § 60.482-9a(c)(2) § 60.482-9a(f) § 60.485a(b) § 60.485a(f) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k) § 60.592a(d) § 60.592a(e)				
UU3-FUG1	EU	60GGGa-01	VOC	40 CFR Part 60, Subpart GGGa	§ 60.593a(g) § 60.482-11a(b)(2) § 60.482-11a(b)(3) § 60.482-11a(b)(3)(i) § 60.482-11a(d) [G]§ 60.482-11a(e) [G]§ 60.482-11a(f)(1) § 60.482-11a(f)(2) § 60.482-11a(g) § 60.485a(b) § 60.486a(a)(1) § 60.486a(a)(2) § 60.592a(d) § 60.592a(e)	Connectors in gas/vapor or light liquid service are exempt from the requirements in §60.482-11a, provided the owner or operator complies with §60.482-8a for all connectors, not just those in heavy liquid service.	§ 60.482-11a(a) § 60.482-11a(b) § 60.482-11a(b)(1) § 60.482-11a(b)(3) § 60.482-11a(b)(3)(ii) [G]§ 60.482-11a(b)(3)(iii) § 60.482-11a(b)(3)(iv) § 60.482-11a(c) § 60.485a(b)(2) [G]§ 60.485a(e) § 60.593a(d)	§ 60.482-11a(b)(3)(v) § 60.485a(b)(2) [G]§ 60.486a(a)(3) [G]§ 60.486a(b) [G]§ 60.486a(c) § 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(8) § 60.486a(e)(9) § 60.486a(f) § 60.486a(f)(1)	§ 60.487a(b) § 60.487a(b)(1) § 60.487a(b)(5) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(i) § 60.487a(c)(2)(ix) § 60.487a(c)(2)(vii) § 60.487a(c)(2)(viii) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)
UU3-SEP12	EU	R5131-0010	VOC	30 TAC Chapter 115, Water Separation	§ 115.132(a)(3) § 115.131(a)	VOC water separator compartments must be equipped with a vapor recovery system which satisfies the provisions of §115.131(a) of this title.	[G]§ 115.135(a) § 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	§ 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	None
UU3-SEP12	EU	61FF-1781	Benzene	40 CFR Part 61, Subpart FF	§ 61.347(a)(1) § 61.347(a)(1)(i)(A) § 61.347(a)(1)(i)(B) § 61.347(b) § 61.347(c) § 61.349(a)	Install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the oil-water separator to a control	§ 61.347(a)(1)(i)(A) § 61.347(b) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f)	§ 61.349(a)(1)(ii) § 61.356(d) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	device.	§ 61.354(f)(1) [G]§ 61.355(h)	§ 61.356(f)(2)(i)(G) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i)	
UU3W-OWS	EU	R5131-0010	VOC	30 TAC Chapter 115, Water Separation	§ 115.132(a)(3) § 115.131(a)	VOC water separator compartments must be equipped with a vapor recovery system which satisfies the provisions of §115.131(a) of this title.	[G]§ 115.135(a) § 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	§ 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	None
UU3W-OWS	EU	61FF-1781	Benzene	40 CFR Part 61, Subpart FF	§ 61.347(a)(1) § 61.347(a)(1)(i)(A) § 61.347(a)(1)(i)(B) § 61.347(b) § 61.347(c) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	Install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the oil-water separator to a control device.	§ 61.347(a)(1)(i)(A) § 61.347(b) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.349(a)(1)(ii) § 61.356(d) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i)	None
UU4	EU	63UUU-0004	Hydrogen Chloride	40 CFR Part 63, Subpart UUU	§ 63.1567(a)(1)-Table 22.2 § 63.1567(a)(1) § 63.1567(a)(1)(ii) § 63.1567(a)(2) § 63.1567(a)(2)-	For each existing cyclic or continuous CRU, you must reduce uncontrolled emissions of HCl to a concentration of 10 ppmv (dry basis), corrected to 3%	§ 63.1567(b)(1) § 63.1567(b)(1)-Table24.1 § 63.1567(b)(2) § 63.1567(b)(2)-Table25.1.a.(2)	§ 63.1567(b)(1)-Table24.1 § 63.1567(b)(2)-Table25.2.a.i § 63.1567(b)(2)-Table25.2.b.i	§ 63.1567(b)(6) § 63.1567(b)(7) § 63.1570(f) § 63.1571(a) § 63.1571(d)(4) § 63.1574(a)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					Table23.1 § 63.1567(a)(3) § 63.1567(b)(3) § 63.1567(b)(4) § 63.1567(b)(4)(i) § 63.1567(b)(5) § 63.1567(b)(5)-Table26.2 § 63.1567(c)(1) § 63.1570(a) § 63.1570(c) § 63.1570(d) § 63.1570(g) § 63.1571(d)(4) [G]§ 63.1571(e)	oxygen.	§ 63.1567(b)(2)-Table25.1.b § 63.1567(b)(2)-Table25.1.c § 63.1567(b)(2)-Table25.1.d § 63.1567(b)(2)-Table25.1.e.(1) § 63.1567(b)(2)-Table25.1.e.(2) § 63.1567(b)(2)-Table25.1.e.(4) § 63.1567(b)(2)-Table25.2.a.i § 63.1567(b)(2)-Table25.2.b.i § 63.1567(c)(1)-Table27.2 § 63.1567(c)(1)-Table28.1.a § 63.1567(c)(1)-Table28.1.b § 63.1571(a) § 63.1571(a)(1) [G]§ 63.1571(b) § 63.1572(c) § 63.1572(c)(1) § 63.1572(c)(2) § 63.1572(c)(3) [G]§ 63.1572(d)	§ 63.1567(c)(1)-Table28.1.a § 63.1567(c)(1)-Table28.1.b § 63.1567(c)(2) § 63.1570(c) § 63.1572(c)(4) § 63.1572(c)(5) [G]§ 63.1576(a) § 63.1576(d) § 63.1576(e) § 63.1576(f) § 63.1576(g) § 63.1576(h) § 63.1576(i)	§ 63.1574(a)(1) § 63.1574(a)(2) § 63.1574(a)(3) § 63.1574(a)(3)(ii) § 63.1574(d) § 63.1574(d)-Table42.1 § 63.1574(d)-Table42.2 § 63.1574(d)-Table42.3 § 63.1575(a) § 63.1575(a)-Table43.1 [G]§ 63.1575(b) [G]§ 63.1575(c) [G]§ 63.1575(d) [G]§ 63.1575(f) § 63.1575(g) [G]§ 63.1575(h)
UU4	EU	63UUU-0004	TOC	40 CFR Part 63, Subpart UUU	§ 63.1566(a)(1)(i)-Table15.1 § 63.1566(a)(1) § 63.1566(a)(2) § 63.1566(a)(2)-Table16.1 § 63.1566(a)(3) § 63.1566(a)(4) § 63.1566(a)(5)	For each applicable process vent for a new or existing catalytic reforming unit, you must vent emissions of total organic compounds (TOC) to a flare that meets the control device requirements in §63.11(b) (Option 1). Visible emissions from a	§ 63.1566(b)(1) § 63.1566(b)(1)-Table17.1 § 63.1566(b)(2) § 63.1566(b)(2)-Table18.1.a § 63.1566(b)(2)-Table18.1.b § 63.1566(b)(5)(i)	§ 63.1566(c)(1)-Table21.1 § 63.1570(c) [G]§ 63.1576(a) § 63.1576(c) § 63.1576(d) § 63.1576(e) § 63.1576(f) § 63.1576(g)	§ 63.1566(b)(7) § 63.1566(b)(8) § 63.1570(f) § 63.1571(a) [G]§ 63.1574(a) § 63.1574(d) § 63.1574(d)-Table42.1 § 63.1574(d)-Table42.2 § 63.1574(d)-Table42.3

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.1566(b)(3) § 63.1566(b)(4) § 63.1566(b)(6) § 63.1566(b)(6)-Table19.1 § 63.1566(b)(7) § 63.1566(c)(1) § 63.1566(c)(2) § 63.1570(a) § 63.1570(b) § 63.1570(c) § 63.1570(d) § 63.1570(g) [G]§ 63.1571(e)	flare must not exceed a total of 5 minutes during any 2-hour operating period.	§ 63.1566(c)(1)-Table20.1 § 63.1566(c)(1)-Table21.1 § 63.1566(c)(2) § 63.1571(a) § 63.1571(a)(1) [G]§ 63.1571(b) [G]§ 63.1572(d)	§ 63.1576(h) § 63.1576(i)	§ 63.1575(a) § 63.1575(a)-Table43.1 [G]§ 63.1575(b) [G]§ 63.1575(c) [G]§ 63.1575(d) [G]§ 63.1575(f) § 63.1575(g) [G]§ 63.1575(h)
UU4 BYPASS	EU	63UUU-0005	112(B) HAPS	40 CFR Part 63, Subpart UUU	§ 63.1569(a)(1)(i)-Table36.1 § 63.1569(a)(1) § 63.1569(a)(3) § 63.1569(b)(2) § 63.1569(b)(2)-Table38.1.a § 63.1569(c)(1) § 63.1570(a) § 63.1570(c) § 63.1570(d) § 63.1570(g)	If you elect to install an automated system (Option 1), you must install and operate a device (including a flow indicator, level recorder, or electronic valve position monitor) to demonstrate, either continuously or at least every hour, whether flow is present in the bypass line. Install the device at or near as practical to the entrance to any bypass line that could divert the vent stream away from the control device to the atmosphere.	§ 63.1569(b)(1) § 63.1569(b)(1)-Table37.1 § 63.1569(c)(1)-Table39.1 § 63.1571(a) § 63.1571(a)(1) [G]§ 63.1571(b)	§ 63.1569(b)(1)-Table37.1 § 63.1569(c)(1)-Table39.1 § 63.1569(c)(1)-Table39.5 § 63.1570(c) [G]§ 63.1576(a) § 63.1576(d) § 63.1576(e) § 63.1576(f) § 63.1576(g) § 63.1576(h) § 63.1576(i)	§ 63.1569(b)(3) § 63.1569(b)(4) § 63.1569(c)(1)-Table39.5 § 63.1570(f) § 63.1571(a) [G]§ 63.1574(a) § 63.1574(d) § 63.1574(d)-Table42.1 § 63.1574(d)-Table42.2 § 63.1574(d)-Table42.3 § 63.1575(a) § 63.1575(a)-Table43.1 [G]§ 63.1575(b) [G]§ 63.1575(c) [G]§ 63.1575(d) [G]§ 63.1575(f) § 63.1575(g) [G]§ 63.1575(h)
UU4-B401A	EU	R7300-1493	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	§ 117.335(f) § 117.335(f)(2) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) § 117.340(c)(3)(D) [G]§ 117.340(c)(3)(E) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)	§ 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
UU4-B401A	EU	R7300-1493	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.340(b)(3) § 117.340(e) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)		[G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
UU4-B401A	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
UU4-B401A	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					CFR Part 63, Subpart DDDDD				
UU4-B401B	EU	R7300-1493	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(2) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) § 117.340(c)(3)(D) [G]§ 117.340(c)(3)(E) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
UU4-B401B	EU	R7300-1493	CO	30 TAC Chapter 117,	§ 117.310(c)(1) § 117.310(c)(1)(A)	CO emissions must not exceed 400 ppmv at 3.0%	[G]§ 117.335(a)(1) § 117.335(a)(4)	§ 117.345(a) § 117.345(f)	§ 117.335(b) § 117.335(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Subchapter B	§ 117.310(c)(3) § 117.340(f)(1)	O 2, dry basis.	§ 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(e) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)	§ 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	[G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
UU4-B401B	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
UU4-B401B	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
UU4-B402A	EU	R7300-1289	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(2) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) § 117.340(c)(3)(D) [G]§ 117.340(c)(3)(E) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)		
UU4-B402A	EU	R7300-1289	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(e) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
UU4-B402A	EU	60J-0008	Hydrogen	40 CFR Part 60,	§ 60.104(a)(1)	No owner or operator	§ 60.105(a)(4)	§ 60.105(a)(4)	§ 60.105(e)(3)(ii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
			Sulfide	Subpart J		subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.107(d) § 60.107(f) § 60.107(g)
UU4-B402A	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
UU4-B402B	EU	R7300-1289	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(2) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) § 117.340(c)(3)(D) [G]§ 117.340(c)(3)(E) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)		
UU4-B402B	EU	R7300-1289	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(e) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							[G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)		
UU4-B402B	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
UU4-B402B	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
UU4-B402C	EU	R7300-1097	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(g) § 117.340(a)(2)(B) § 117.340(c)(1) [G]§ 117.340(c)(3) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	§ 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)		§ 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
UU4-B402C	EU	R7300-1097	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a)(2)(B) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							[G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)		
UU4-B402C	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
UU4-B402C	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
UU4-B404	EU	R7300-1018	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(ii) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C) § 117.8000(b)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	§ 117.8000(c) § 117.8000(c)(1) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d)		[G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
UU4-B404	EU	R7300-1018	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B) § 117.310(c)(3)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a) § 117.8000(b) § 117.8000(c) § 117.8000(c)(2) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8120 § 117.8120(2) [G]§ 117.8120(2)(A) § 117.8120(2)(B)	§ 117.345(a) § 117.345(f) § 117.345(f)(1) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
UU4-B404	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
UU4-B404	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63,	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					specification requirements of 40 CFR Part 63, Subpart DDDDD		DDDDD	Subpart DDDDD	
UU4-B405	EU	R7300-1493	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(2) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) § 117.340(c)(3)(D) [G]§ 117.340(c)(3)(E) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
UU4-B405	EU	R7300-1493	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(e) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)
UU4-B405	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						mg/dscm (0.10 gr/dscf).			
UU4-B405	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
UU4-B406	EU	R7300-1289	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(8)(A)(i) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) § 117.340(f)(1) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(2) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(c)(1) § 117.340(c)(3)(D) [G]§ 117.340(c)(3)(E) [G]§ 117.340(f)(2) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(i) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(3) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6)		
UU4-B406	EU	R7300-1289	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(A) § 117.310(c)(3) § 117.340(f)(1)	CO emissions must not exceed 400 ppmv at 3.0% O 2, dry basis.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(c) § 117.335(d) § 117.335(f) § 117.335(f)(3) § 117.335(g) § 117.340(a)(2)(B) § 117.340(b)(1) § 117.340(b)(3) § 117.340(e) [G]§ 117.340(f)(2) § 117.8100(a) § 117.8100(a)(1) § 117.8100(a)(1)(A) § 117.8100(a)(1)(B) § 117.8100(a)(1)(B)(ii) § 117.8100(a)(1)(B)(iii) § 117.8100(a)(1)(C) § 117.8100(a)(2) [G]§ 117.8100(a)(3) § 117.8100(a)(4) § 117.8100(a)(5) § 117.8100(a)(5)(A) § 117.8100(a)(5)(B) [G]§ 117.8100(a)(5)(D) [G]§ 117.8100(a)(5)(E) § 117.8100(a)(6) § 117.8120 § 117.8120(1) § 117.8120(1)(A)	§ 117.345(a) § 117.345(f) § 117.345(f)(2) [G]§ 117.345(f)(2)(C) § 117.345(f)(7) § 117.345(f)(8) § 117.345(f)(9) § 117.8100(a)(5)(C)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.345(d) § 117.345(d)(2) § 117.345(d)(3) § 117.345(d)(4) § 117.345(d)(5) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8) § 117.8100(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
UU4-B406	EU	60J-0025	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
UU4-B406	EU	63DDDDD-1	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
UU4-CTW	EU	R5760-0025	Highly Reactive VOC	30 TAC Chapter 115, HRVOC Cooling Towers	§ 115.767(3) § 115.766(i)	Any site for which no stream directed to a cooling tower heat exchange system contains 5.0% or greater by weight HRVOC is exempt from the requirements of _115.761 of this title (relating to Site-wide Cap).	§ 115.764(c) § 115.764(d) § 115.764(e)(1)	§ 115.766(c) § 115.766(d) [G]§ 115.766(e) § 115.766(i)(1)	§ 115.766(i)(2)
UU4-CTW	EU	63CC-002	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.654(a) § 63.640(h)(6)	Except as specified in paragraph (b) of this section, the owner or operator of a heat exchange system that meets the criteria in §63.640(c)(8) must comply with the requirements of paragraphs (c) through (g) of this section.	§ 63.642(d)(1) § 63.642(d)(3) § 63.642(d)(4) [G]§ 63.654(c) [G]§ 63.654(d) § 63.654(e) [G]§ 63.654(f) [G]§ 63.654(g)	§ 63.642(e) § 63.655(h)(1) [G]§ 63.655(i)(4) § 63.655(i)(5)	§ 63.642(d)(2) § 63.642(f) § 63.655(f) § 63.655(f)(1)(vi) § 63.655(f)(4) § 63.655(g) [G]§ 63.655(g)(9) § 63.655(h)(1)
UU4-FUG1	EU	60GGGa-	VOC	40 CFR Part 60,	[G]§ 60.590a(a)	The permit holder shall	The permit holder shall	The permit holder	The permit holder shall

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		001		Subpart GGGa	The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 60, Subpart GGGa	comply with the applicable requirements of 40 CFR Part 60, Subpart GGGa	comply with the applicable monitoring and testing requirements of 40 CFR Part 60, Subpart GGGa	shall comply with the applicable recordkeeping requirements of 40 CFR Part 60, Subpart GGGa	comply with the applicable reporting requirements of 40 CFR Part 60, Subpart GGGa
UU4-SEP1	EU	R5131-0010	VOC	30 TAC Chapter 115, Water Separation	§ 115.132(a)(3) § 115.131(a)	VOC water separator compartments must be equipped with a vapor recovery system which satisfies the provisions of §115.131(a) of this title.	[G]§ 115.135(a) § 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	§ 115.136(a)(2) § 115.136(a)(3) § 115.136(a)(4)	None
UU4-SEP1	EU	61FF-1781	Benzene	40 CFR Part 61, Subpart FF	§ 61.347(a)(1) § 61.347(a)(1)(i)(A) § 61.347(a)(1)(i)(B) § 61.347(b) § 61.347(c) § 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(a)(1)(ii)(B) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	Install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the oil-water separator to a control device.	§ 61.347(a)(1)(i)(A) § 61.347(b) § 61.349(a)(1)(i) § 61.349(a)(1)(ii) § 61.349(e) § 61.349(f) § 61.354(f)(1) [G]§ 61.355(h)	§ 61.349(a)(1)(ii) § 61.356(d) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(G) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(3)(i)	None
VEH GAS TK	EU	63CC-0003	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(c)(2)	All Group 2 storage vessels associated with petroleum refining process units meeting the criteria in paragraph (a) of this section are part of the affected source.	§ 63.646(b)(1) § 63.646(b)(2)	§ 63.646(b)(1) § 63.655(g)(7)(ii) § 63.655(i)(1)(iv) § 63.655(i)(5)	§ 63.655(f) § 63.655(f)(1)(i)(A) § 63.655(g) § 63.655(g)(7) § 63.655(g)(7)(i) § 63.655(h) § 63.655(h)(6)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
									§ 63.655(h)(6)(ii)
WIFCMP	EU	R7300-0003	NO_X	30 TAC Chapter 117, Subchapter B	§ 117.310(d)(3) § 117.310(a) § 117.310(a)(9)(E)(vii)(II) § 117.310(b) [G]§ 117.310(e)(1) § 117.310(e)(2) [G]§ 117.310(e)(3) § 117.310(e)(4) [G]§ 117.310(f) § 117.340(l)(2) § 117.340(p)(1) § 117.340(p)(2)(C) § 117.340(p)(3)	An owner or operator may not use the alternative methods specified in §§ 117.315, 117.323 and 117.9800 to comply with the NO_x emission specifications but shall use the mass emissions cap and trade program in Chapter 101, Subchapter H, Division 3, except that electric generating facilities must also comply with the daily and 30-day system cap emission limitations of § 117.320. An owner or operator may use the alternative methods specified in § 117.9800 to comply with § 117.320.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a)(2)(C) § 117.340(h) § 117.340(l)(2) § 117.340(o)(1) § 117.340(p)(1) § 117.340(p)(2)(A) § 117.340(p)(2)(B) § 117.340(p)(2)(C) § 117.345(f)(3)(A) § 117.345(f)(3)(A)(ii) § 117.8000(b) § 117.8000(c) § 117.8000(c)(1) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8140(a) § 117.8140(a)(1) § 117.8140(a)(2) § 117.8140(a)(2)(A) [G]§ 117.8140(a)(2)(B) § 117.8140(b)	§ 117.345(a) § 117.345(f) [G]§ 117.345(f)(10) § 117.345(f)(3) § 117.345(f)(3)(B) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) § 117.340(p)(2)(D) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A) § 117.8010(2)(B) § 117.8010(2)(C) § 117.8010(2)(D) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
WIFCMP	EU	R7300-0003	CO	30 TAC Chapter 117, Subchapter B	§ 117.310(c)(1) § 117.310(c)(1)(B)	CO emissions must not exceed 3.0 g/hp-hr for stationary internal combustion engines.	[G]§ 117.335(a)(1) § 117.335(a)(4) § 117.335(b) § 117.335(d) § 117.335(e) § 117.335(g) § 117.340(a)(2)(C) § 117.340(h)	§ 117.345(a) § 117.345(f) [G]§ 117.345(f)(10) § 117.345(f)(9)	§ 117.335(b) § 117.335(g) [G]§ 117.345(b) [G]§ 117.345(c) § 117.8010 [G]§ 117.8010(1) § 117.8010(2) § 117.8010(2)(A)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 117.345(f)(3) § 117.345(f)(3)(A) § 117.345(f)(3)(A)(ii) § 117.8000(b) § 117.8000(c) § 117.8000(c)(2) § 117.8000(c)(3) § 117.8000(c)(5) § 117.8000(c)(6) [G]§ 117.8000(d) § 117.8120 § 117.8120(2) [G]§ 117.8120(2)(A) § 117.8120(2)(B) § 117.8140(a) § 117.8140(a)(1) § 117.8140(a)(2) § 117.8140(a)(2)(A) [G]§ 117.8140(a)(2)(B) § 117.8140(b)		§ 117.8010(2)(B) [G]§ 117.8010(3) § 117.8010(4) [G]§ 117.8010(5) § 117.8010(6) [G]§ 117.8010(7) [G]§ 117.8010(8)
WIFCMP	EU	60IIII-0003	CO	40 CFR Part 60, Subpart IIII	§ 60.4204(b) § 1039.102 § 60.4201(a) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) § 60.4218	Owners and operators of non-emergency stationary CI ICE with a maximum engine power greater than or equal to 130 KW and less than or equal to 2237 KW and a displacement of less than 10 liters per cylinder and is a 2007 model year and later must comply with a CO emission limit of 3.5 g/KW-hr as stated in 40 CFR 60.4201(a) and 40 CFR 89.112(a) and 40 CFR 1039.102 and 40 CFR 1039.101.	§ 60.4209(b)	§ 60.4214(c)	None
WIFCMP	EU	60IIII-0003	NMHC and NO_X	40 CFR Part 60, Subpart IIII	§ 60.4204(b) § 1039.102	Owners and operators of non-emergency stationary	§ 60.4209(b)	§ 60.4214(c)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.4201(a) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) § 60.4218	CI ICE with a maximum engine power greater than or equal to 75 KW but less than 560 KW and a displacement of less than 10 liters per cylinder and is a 2007 - 2013 model year must comply with an NMHC+NOx emission limit of 4.0 g/KW-hr as stated in 40 CFR 60.4201(a) and 40 CFR 89.112(a) and 40 CFR 1039.102.			
WIFCMP	EU	60IIII-0003	PM	40 CFR Part 60, Subpart IIII	§ 60.4204(b) § 1039.102 § 60.4201(a) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) § 60.4218	Owners and operators of non-emergency stationary CI ICE with a maximum engine power greater than or equal to 130 KW and less than 560 KW and a displacement of less than 10 liters per cylinder and is a 2011 model year and later must comply with a PM emission limit of 0.02 g/KW-hr as stated in 40 CFR 60.4201(a) and 40 CFR 1039.102 and 40 CFR 1039.101.	§ 60.4209(b)	§ 60.4214(c)	None
WIFCMP	EU	63ZZZZ-0003	CO	40 CFR Part 63, Subpart ZZZZ	§ 63.6600(b)-Table2a.3.a § 63.6595(c) § 63.6600(b)-Table2b.1.a § 63.6600(b)-Table2b.1.b § 63.6605(a) § 63.6605(b) § 63.6625(h)	For each new or reconstructed CI stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions, operating at 100% load plus or minus 10%, you must reduce CO emissions by 70% or more.	§ 63.6610(a) § 63.6610(b) § 63.6610(c) [G]§ 63.6610(d) § 63.6615 § 63.6620(a) § 63.6620(a)-Table3.1 § 63.6620(a)-Table4.1.a.i § 63.6620(a)-	§ 63.6620(i) § 63.6630(a)-Table5.1.a.iii § 63.6635(a) § 63.6635(c) § 63.6655(a) § 63.6655(a)(1) § 63.6655(a)(2) § 63.6655(a)(3) § 63.6655(a)(4)	§ 63.6620(i) § 63.6630(c) § 63.6640(b) § 63.6640(e) § 63.6645(a) § 63.6645(c) § 63.6645(g) § 63.6645(h) § 63.6645(h)(2) § 63.6650(a)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.6630(a) § 63.6640(b)		Table4.1.a.ii § 63.6620(a)-Table4.1.a.iii § 63.6620(b) § 63.6620(b)(4) § 63.6620(d) § 63.6620(e)(1) [G]§ 63.6620(e)(2) [G]§ 63.6625(b) § 63.6630(a)-Table5.1.a.i § 63.6630(a)-Table5.1.a.ii § 63.6630(a)-Table5.1.a.iii § 63.6635(a) § 63.6635(b) § 63.6640(a) § 63.6640(a)-Table6.1.a.i § 63.6640(a)-Table6.1.a.ii § 63.6640(a)-Table6.1.a.iii § 63.6640(a)-Table6.1.a.iv § 63.6640(a)-Table6.1.a.v § 63.6640(b)	§ 63.6655(a)(5) [G]§ 63.6655(b) § 63.6655(d) § 63.6660(a) § 63.6660(b) § 63.6660(c)	§ 63.6650(a)-Table7.1.a.i § 63.6650(a)-Table7.1.a.ii § 63.6650(a)-Table7.1.b § 63.6650(a)-Table7.1.c § 63.6650(b) § 63.6650(b)(1) § 63.6650(b)(2) § 63.6650(b)(3) § 63.6650(b)(4) § 63.6650(b)(6) § 63.6650(b)(7) § 63.6650(b)(8) § 63.6650(b)(9) [G]§ 63.6650(c) [G]§ 63.6650(e) § 63.6650(f)

Additional Monitoring Requirements

Compliance Assurance Monitoring Summary **727**

Periodic Monitoring Summary **746**

CAM Summary

Unit/Group/Process Information	
ID No.: COKR-SEP	
Control Device ID No.: E32	Control Device Type: Carbon Adsorption System (Non-Regenerative)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Water Separation	SOP Index No.: R5131-0010
Pollutant: VOC	Main Standard: § 115.132(a)(3)
Monitoring Information	
Indicator: VOC breakthrough as indicated by a sample result greater than or equal to100 ppm VOC	
Minimum Frequency: Once per week	
Averaging Period: n/a	
Deviation Limit: Any instance when the carbon is not changed out within 24-hours of receiving sampling results that indicates breakthrough has occurred (100 ppm VOC).	
CAM Text: On each day that sampling is to occur, the analyzer shall be calibrated prior to sampling with a certified gas mixture at 100 ppmv ± 10 percent. VOC sampling and analysis shall be photo-ionization detector (PID), Ultraray, or a TCEQ equivalent as approved by the Compliance Support Division. Samples should be taken between the beds of the dual-bed system.	

CAM Summary

Unit/Group/Process Information	
ID No.: DDU-315A	
Control Device ID No.: TCH-DDU	Control Device Type: Flare
Control Device ID No.: TCH-ULC	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Water Separation	SOP Index No.: R5131-0010
Pollutant: VOC	Main Standard: § 115.132(a)(3)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: n/a	
Deviation Limit: No pilot flame	
CAM Text: Monitor the presence of a flare pilot flame using a thermocouple or other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. Maintain records of alarm events and duration of alarm events. Each monitoring device shall be accurate to within manufacturer's recommendations. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications or other written procedures that provide an adequate assurance that the device is calibrated accurately.	

CAM Summary

Unit/Group/Process Information	
ID No.: DOCK32	
Control Device ID No.: DKTO294-1	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Control Device ID No.: DKTO294-2	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Control Device ID No.: DKTO294-3	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Loading and Unloading of VOC	SOP Index No.: R5211-0190
Pollutant: VOC	Main Standard: § 115.212(a)(6)(A)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: four times per hour	
Averaging Period: one hour	
Deviation Limit: Minimum combustion temperature = 1250 degrees Fahrenheit during loading operations.	
CAM Text: The monitoring device should be installed in the combustion chamber or immediately downstream of the combustion chamber. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following: ± 0.75% of the temperature being measured expressed in degrees Celsius; or ± 2.5 degrees Celsius.	

CAM Summary

Unit/Group/Process Information	
ID No.: DOCK32	
Control Device ID No.: DKTO294-1	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Control Device ID No.: DKTO294-2	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Control Device ID No.: DKTO294-3	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Loading and Unloading of VOC	SOP Index No.: R5211-0226
Pollutant: VOC	Main Standard: § 115.212(a)(6)(A)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: four times per hour	
Averaging Period: one hour	
Deviation Limit: Minimum combustion temperature = 1250 degrees Fahrenheit during loading operations.	
CAM Text: The monitoring device should be installed in the combustion chamber or immediately downstream of the combustion chamber. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following: ± 0.75% of the temperature being measured expressed in degrees Celsius; or ± 2.5 degrees Celsius.	

CAM Summary

Unit/Group/Process Information	
ID No.: DOCK32	
Control Device ID No.: DKTO294-1	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Control Device ID No.: DKTO294-2	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Control Device ID No.: DKTO294-3	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 40 CFR Part 61, Subpart BB	SOP Index No.: 61BB-0012
Pollutant: Benzene	Main Standard: [G]§ 61.302(a)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: once per day	
Averaging Period: n/a	
Deviation Limit: Minimum combustion temperature = 1250 degrees Fahrenheit during loading operations.	
CAM Text: The monitoring device should be installed in the combustion chamber or immediately downstream of the combustion chamber. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following: ± 2% of reading; or ± 2.5 degrees Celsius.	

CAM Summary

Unit/Group/Process Information	
ID No.: DOCK33	
Control Device ID No.: DKTO294-1	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Control Device ID No.: DKTO294-2	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Control Device ID No.: DKTO294-3	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Loading and Unloading of VOC	SOP Index No.: R5211-0226
Pollutant: VOC	Main Standard: § 115.212(a)(6)(A)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: four times per hour	
Averaging Period: one hour	
Deviation Limit: Minimum combustion temperature = 1250 degrees Fahrenheit during loading operations.	
CAM Text: The monitoring device should be installed in the combustion chamber or immediately downstream of the combustion chamber. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following: ± 0.75% of the temperature being measured expressed in degrees Celsius; or ± 2.5 degrees Celsius.	

CAM Summary

Unit/Group/Process Information	
ID No.: DOCK33	
Control Device ID No.: DKTO294-1	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Control Device ID No.: DKTO294-2	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Control Device ID No.: DKTO294-3	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 40 CFR Part 61, Subpart BB	SOP Index No.: 61BB-0012
Pollutant: Benzene	Main Standard: [G]§ 61.302(a)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: once per day	
Averaging Period: n/a	
Deviation Limit: Minimum combustion temperature = 1250 degrees Fahrenheit during loading operations.	
CAM Text: The monitoring device should be installed in the combustion chamber or immediately downstream of the combustion chamber. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following: ± 2% of reading; or ± 2.5 degrees Celsius.	

CAM Summary

Unit/Group/Process Information	
ID No.: DOCK34	
Control Device ID No.: DKTO294-1	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Control Device ID No.: DKTO294-2	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Control Device ID No.: DKTO294-3	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Loading and Unloading of VOC	SOP Index No.: R5211-0226
Pollutant: VOC	Main Standard: § 115.212(a)(6)(A)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: four times per hour	
Averaging Period: one hour	
Deviation Limit: Minimum combustion temperature = 1250 degrees Fahrenheit during loading operations.	
CAM Text: The monitoring device should be installed in the combustion chamber or immediately downstream of the combustion chamber. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following: ± 0.75% of the temperature being measured expressed in degrees Celsius; or ± 2.5 degrees Celsius.	

CAM Summary

Unit/Group/Process Information	
ID No.: DOCK34	
Control Device ID No.: DKTO294-1	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Control Device ID No.: DKTO294-2	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Control Device ID No.: DKTO294-3	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 40 CFR Part 61, Subpart BB	SOP Index No.: 61BB-0012
Pollutant: Benzene	Main Standard: [G]§ 61.302(a)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: once per day	
Averaging Period: n/a	
Deviation Limit: Minimum combustion temperature = 1250 degrees Fahrenheit during loading operations.	
CAM Text: The monitoring device should be installed in the combustion chamber or immediately downstream of the combustion chamber. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following: ± 2% of reading; or ± 2.5 degrees Celsius.	

CAM Summary

Unit/Group/Process Information	
ID No.: DOCK37	
Control Device ID No.: DKTO294-1	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Control Device ID No.: DKTO294-2	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Control Device ID No.: DKTO294-3	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Loading and Unloading of VOC	SOP Index No.: R5211-0226
Pollutant: VOC	Main Standard: § 115.212(a)(6)(A)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: four times per hour	
Averaging Period: one hour	
Deviation Limit: Minimum combustion temperature = 1250 degrees Fahrenheit during loading operations.	
CAM Text: The monitoring device should be installed in the combustion chamber or immediately downstream of the combustion chamber. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following: ± 0.75% of the temperature being measured expressed in degrees Celsius; or ± 2.5 degrees Celsius.	

CAM Summary

Unit/Group/Process Information	
ID No.: DOCK37	
Control Device ID No.: DKTO294-1	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Control Device ID No.: DKTO294-2	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Control Device ID No.: DKTO294-3	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 40 CFR Part 61, Subpart BB	SOP Index No.: 61BB-0012
Pollutant: Benzene	Main Standard: [G]§ 61.302(a)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: once per day	
Averaging Period: n/a	
Deviation Limit: Minimum combustion temperature = 1250 degrees Fahrenheit during loading operations.	
CAM Text: The monitoring device should be installed in the combustion chamber or immediately downstream of the combustion chamber. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following: ± 2% of reading; or ± 2.5 degrees Celsius.	

CAM Summary

Unit/Group/Process Information	
ID No.: DOCK38	
Control Device ID No.: DTKO294-1	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Control Device ID No.: DTKO294-2	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Control Device ID No.: DTKO294-3	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Loading and Unloading of VOC	SOP Index No.: R5211-0226
Pollutant: VOC	Main Standard: § 115.212(a)(6)(A)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: four times per hour	
Averaging Period: one hour	
Deviation Limit: Minimum combustion temperature = 1250 degrees Fahrenheit during loading operations.	
CAM Text: The monitoring device should be installed in the combustion chamber or immediately downstream of the combustion chamber. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following: ± 0.75% of the temperature being measured expressed in degrees Celsius; or ± 2.5 degrees Celsius.	

CAM Summary

Unit/Group/Process Information	
ID No.: DOCK38	
Control Device ID No.: DKT0294-2	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Control Device ID No.: DKTO294-1	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Control Device ID No.: DKTO294-3	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 40 CFR Part 61, Subpart BB	SOP Index No.: 61BB-0012
Pollutant: Benzene	Main Standard: [G]§ 61.302(a)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: once per day	
Averaging Period: n/a	
Deviation Limit: Minimum combustion temperature = 1250 degrees Fahrenheit during loading operations.	
CAM Text: The monitoring device should be installed in the combustion chamber or immediately downstream of the combustion chamber. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following: ± 2% of reading; or ± 2.5 degrees Celsius.	

CAM Summary

Unit/Group/Process Information	
ID No.: DOCK54LOAD	
Control Device ID No.: TODOCK54	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Loading and Unloading of VOC	SOP Index No.: R5211-0225
Pollutant: VOC	Main Standard: § 115.212(a)(6)(A)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: once per day	
Averaging Period: n/a	
Deviation Limit: Minimum combustion temperature = 1250 degrees Fahrenheit during loading operations.	
CAM Text: The monitoring device should be installed in the combustion chamber or immediately downstream of the combustion chamber. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following: ± 0.75% of the temperature being measured expressed in degrees Celsius; or ± 2.5 degrees Celsius.	

CAM Summary

Unit/Group/Process Information	
ID No.: DOCK54LOAD	
Control Device ID No.: TODOCK54	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 40 CFR Part 61, Subpart BB	SOP Index No.: 61BB-0012
Pollutant: Benzene	Main Standard: [G]§ 61.302(a)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: once per day	
Averaging Period: n/a	
Deviation Limit: Minimum combustion temperature = 1250 degrees Fahrenheit during loading operations.	
CAM Text: The monitoring device should be installed in the combustion chamber or immediately downstream of the combustion chamber. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following: ± 2% of reading; or ± 2.5 degrees Celsius.	

CAM Summary

Unit/Group/Process Information	
ID No.: PRO-SRU	
Control Device ID No.: SRU-F8C	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Control Device ID No.: SRU-F8D	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 112, Sulfur Compounds	SOP Index No.: R2007-0002
Pollutant: SO_2	Main Standard: § 112.7(a)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: four times per hour	
Averaging Period: one hour	
Deviation Limit: Incinerator combustion chamber minimum temperature = 1200 degrees Fahrenheit when operating.	
CAM Text: The monitoring device should be installed in the combustion chamber or immediately downstream of the combustion chamber. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following: ± 2% of reading; or ± 2.5 degrees Celsius.	

CAM Summary

Unit/Group/Process Information	
ID No.: PRO-SRU	
Control Device ID No.: SRU-F8C	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Control Device ID No.: SRU-F8D	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 112, Sulfur Compounds	SOP Index No.: R2007-0002
Pollutant: SO_2	Main Standard: § 112.7(a)
Monitoring Information	
Indicator: SO2 Mass Emissions in Pounds per Hour	
Minimum Frequency: four times per hour	
Averaging Period: one hour	
Deviation Limit: Maximum sulfur dioxide emission rate = 520 lb/hr	
CAM Text: Use a continuous emission monitoring system (CEMS) to measure and record the mass emissions rate of sulfur dioxide expressed in pounds per hour in the exhaust stream of the control device. The CEMS shall be operated in accordance with the monitoring requirements of 40 CFR § 60.13 and the Performance Specifications of 40 CFR Part 60, Appendix B.	

CAM Summary

Unit/Group/Process Information	
ID No.: PS3A-OWS	
Control Device ID No.: E09	Control Device Type: Carbon Adsorption System (Non-Regenerative)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Water Separation	SOP Index No.: R5131-0010
Pollutant: VOC	Main Standard: § 115.132(a)(3)
Monitoring Information	
Indicator: VOC breakthrough as indicated by a sample result greater than or equal to 100 ppm VOC	
Minimum Frequency: Once per week	
Averaging Period: n/a	
Deviation Limit: Any instance when the carbon is not changed out within 24-hours of receiving sampling results that indicates breakthrough has occurred (100 ppm VOC).	
CAM Text: On each day that sampling is to occur, the analyzer shall be calibrated prior to sampling with a certified gas mixture at 100 ppmv ± 10 percent. Samples should be taken between the beds of the dual-bed system. VOC sampling and analysis shall be photo-ionization detector (PID), Ultraray, or a TCEQ equivalent as approved by the Compliance Support Division.	

CAM Summary

Unit/Group/Process Information	
ID No.: TO-WWTP	
Control Device ID No.: TO-WWTP	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-0019
Pollutant: VOC	Main Standard: § 115.121(a)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: four times per hour	
Averaging Period: one hour	
Deviation Limit: Minimum combustion temperature = 1270 degrees Fahrenheit when operating.	
CAM Text: The monitoring device should be installed in the combustion chamber or immediately downstream of the combustion chamber. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following: ± 0.75% of the temperature being measured expressed in degrees Celsius; or ± 2.5 degrees Celsius.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: API3CD-SEP	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Water Separation	SOP Index No.: R5131-0005
Pollutant: VOC	Main Standard: § 115.132(a)(2)
Monitoring Information	
Indicator: VOC breakthrough as indicated by a sample result greater than or equal to 100 ppm VOC	
Minimum Frequency: Once per week	
Averaging Period: n/a	
Deviation Limit: Any instance when the carbon is not changed out within 24-hours of receiving sampling results that indicates breakthrough has occurred (100 ppm VOC).	
Periodic Monitoring Text: On each day that sampling is to occur, the analyzer shall be calibrated prior to sampling with a certified gas mixture at 100 ppmv ± 10 percent. Samples should be taken between the beds of the dual-bed system. VOC sampling and analysis shall be photo-ionization detector (PID), Ultraray, or a TCEQ equivalent as approved by the Compliance Support Division. On each day that sampling is to occur, the analyzer shall be calibrated prior to sampling with a certified gas mixture at 100 ppmv ± 10 percent. VOC sampling and analysis shall be photo-ionization detector (PID), Ultraray, or a TCEQ equivalent as approved by the Compliance Support Division. Samples should be taken between the beds of the dual-bed system.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: EPN-34A	
Control Device ID No.: FCCU3 WGS	Control Device Type: Wet Scrubber
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-0197
Pollutant: Opacity	Main Standard: § 111.111(a)(1)(A)
Monitoring Information	
Indicator: Liquid/gas ratio	
Minimum Frequency: Every 6 minutes	
Averaging Period: 6-minute averages	
Deviation Limit: Liquid to gas ratio less than the minimum 24-hour average value observed in the most recent satisfactory stack test.	
Periodic Monitoring Text: The FCCU 3 Regenerator Scrubber (EPN 34) liquid to gas ratio shall be continuously monitored and be maintained greater than the minimum one hour average value observed in the last satisfactory stack test performed. The flow rates shall be recorded every 6 minutes as six minute averages. Each flow monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, or at least annually, whichever is more frequent, and shall be accurate to within 2 percent of span or 5 percent of the design value.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: EPN-34A	
Control Device ID No.: FCCU WGS	Control Device Type: Wet Scrubber
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-0197
Pollutant: Opacity	Main Standard: § 111.111(a)(1)(A)
Monitoring Information	
Indicator: Gas pressure drop	
Minimum Frequency: Every 6 minutes	
Averaging Period: 6-minute averages	
Deviation Limit: Gas pressure drop less than the minimum 24-hour average value observed in the most recent satisfactory stack test.	
Periodic Monitoring Text: The FCCU 3 Regenerator Scrubber (EPN 34) gas pressure drop shall be continuously monitored and be maintained greater than the minimum one hour average value observed in the last satisfactory stack test performed. The pressures shall be recorded every 6 minutes as six minute averages. Each pressure monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, or at least annually, whichever is more frequent, and shall be accurate to within 2 percent of span or 5 percent of the design value.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: F607/T-30	
Control Device ID No.: TDU-TO	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart Kb	SOP Index No.: 60Kb-0073
Pollutant: VOC	Main Standard: § 60.112b(b)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: n/a	
Deviation Limit: Any monitoring data below the minimum limit for destruction efficiency established during testing shall be considered and reported as a deviation.	
Periodic Monitoring Text: Measure and record the combustion temperature in the combustion chamber or immediately downstream of the combustion chamber. The monitoring instrumentation shall be maintained, calibrated and operated in accordance with manufacturer's specifications or other written procedures. Any monitoring data below the minimum limit shall be considered and reported as a deviation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: F607/T-30	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart Kb	SOP Index No.: 60Kb-0074
Pollutant: VOC	Main Standard: § 60.112b(b)(1)
Monitoring Information	
Indicator: VOC Concentration	
Minimum Frequency: Once per year	
Averaging Period: n/a	
Deviation Limit: Failure to record fugitive emissions from the vapor collection system in accordance with 40 CFR Part 60, Appendix A, Method 21.	
Periodic Monitoring Text: Measure and record fugitive emissions from the vapor collection system in accordance with part 60, appendix A, method 21.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: F607/T-30	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart Kb	SOP Index No.: 60Kb-0074
Pollutant: VOC	Main Standard: § 60.112b(b)(1)
Monitoring Information	
Indicator: Visual Inspection	
Minimum Frequency: Once per year	
Averaging Period: n/a	
Deviation Limit: Defects, such as cracks, holes, gaps, loose connections, or broken or missing covers or other closure devices, that could result in air emissions.	
Periodic Monitoring Text: Visually inspect all components of the vapor collection system for defects, such as cracks, holes, gaps, loose connections, or broken or missing covers or other closure devices, that could result in air emissions.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: F607/T-31	
Control Device ID No.: TDU-TO	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart Kb	SOP Index No.: 60Kb-0073
Pollutant: VOC	Main Standard: § 60.112b(b)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: n/a	
Deviation Limit: Any monitoring data below the minimum limit for destruction efficiency established during testing shall be considered and reported as a deviation.	
Periodic Monitoring Text: Measure and record the combustion temperature in the combustion chamber or immediately downstream of the combustion chamber. The monitoring instrumentation shall be maintained, calibrated and operated in accordance with manufacturer's specifications or other written procedures. Any monitoring data below the minimum limit shall be considered and reported as a deviation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: F607/T-31	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart Kb	SOP Index No.: 60Kb-0074
Pollutant: VOC	Main Standard: § 60.112b(b)(1)
Monitoring Information	
Indicator: VOC Concentration	
Minimum Frequency: Once per year	
Averaging Period: n/a	
Deviation Limit: Failure to record fugitive emissions from the vapor collection system in accordance with 40 CFR Part 60, Appendix A, Method 21.	
Periodic Monitoring Text: Measure and record fugitive emissions from the vapor collection system in accordance with part 60, appendix A, method 21.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: F607/T-31	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart Kb	SOP Index No.: 60Kb-0074
Pollutant: VOC	Main Standard: § 60.112b(b)(1)
Monitoring Information	
Indicator: Visual Inspection	
Minimum Frequency: Once per year	
Averaging Period: n/a	
Deviation Limit: Defects, such as cracks, holes, gaps, loose connections, or broken or missing covers or other closure devices, that could result in air emissions.	
Periodic Monitoring Text: Visually inspect all components of the vapor collection system for defects, such as cracks, holes, gaps, loose connections, or broken or missing covers or other closure devices, that could result in air emissions.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: F607/T-32	
Control Device ID No.: TDU-TO	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart Kb	SOP Index No.: 60Kb-0073
Pollutant: VOC	Main Standard: § 60.112b(b)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: n/a	
Deviation Limit: Any monitoring data below the minimum limit shall be considered and reported as a deviation.	
Periodic Monitoring Text: Measure and record the combustion temperature in the combustion chamber or immediately downstream of the combustion chamber. The monitoring instrumentation shall be maintained, calibrated and operated in accordance with manufacturer's specifications or other written procedures. Any monitoring data below the minimum limit shall be considered and reported as a deviation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: F607/T-32	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart Kb	SOP Index No.: 60Kb-0074
Pollutant: VOC	Main Standard: § 60.112b(b)(1)
Monitoring Information	
Indicator: VOC Concentration	
Minimum Frequency: Once per year	
Averaging Period: n/a	
Deviation Limit: Failure to record fugitive emissions from the vapor collection system in accordance with 40 CFR Part 60, Appendix A, Method 21.	
Periodic Monitoring Text: Measure and record fugitive emissions from the vapor collection system in accordance with part 60, appendix A, method 21.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: F607/T-32	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart Kb	SOP Index No.: 60Kb-0074
Pollutant: VOC	Main Standard: § 60.112b(b)(1)
Monitoring Information	
Indicator: Visual Inspection	
Minimum Frequency: Once per year	
Averaging Period: n/a	
Deviation Limit: Defects, such as cracks, holes, gaps, loose connections, or broken or missing covers or other closure devices, that could result in air emissions.	
Periodic Monitoring Text: Visually inspect all components of the vapor collection system for defects, such as cracks, holes, gaps, loose connections, or broken or missing covers or other closure devices, that could result in air emissions.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: GRPVENT1	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-0112
Pollutant: Opacity	Main Standard: § 111.111(a)(1)(B)
Monitoring Information	
Indicator: Visible Emissions	
Minimum Frequency: Once per quarter	
Averaging Period: n/a	
Deviation Limit: Opacity greater than 20%, or any visible emissions if site chooses not to perform Method 9 observation.	
Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. If visible emissions are observed, the permit holder shall report a deviation. As an alternative, the permit holder may determine the opacity consistent with Test Method 9, as soon as practicable, but no later than 24 hours after observing visible emissions. If the result of the Test Method 9 is opacity above the corresponding opacity limit, the permit holder shall report a deviation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: GRPVENT2	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-0112
Pollutant: Opacity	Main Standard: § 111.111(a)(1)(B)
Monitoring Information	
Indicator: Visible emissions	
Minimum Frequency: Once per quarter	
Averaging Period: n/a	
Deviation Limit: Opacity greater than 20%, or any visible emissions if site chooses not to perform Method 9 observation.	
Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. If visible emissions are observed, the permit holder shall report a deviation. As an alternative, the permit holder may determine the opacity consistent with Test Method 9, as soon as practicable, but no later than 24 hours after observing visible emissions. If the result of the Test Method 9 is opacity above the corresponding opacity limit, the permit holder shall report a deviation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: T280-1054	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Water Separation	SOP Index No.: R5131-0005
Pollutant: VOC	Main Standard: § 115.132(a)(2)
Monitoring Information	
Indicator: External Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Any monitoring data in which the roof is not floating on the surface of the VOC, if liquid has accumulated on the external floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a	
Periodic Monitoring Text: Visually inspect and record the inspection of the external floating roof to ensure: the roof is floating on the surface of the VOC and not on the leg supports, liquid has not accumulated on the external floating roof, the seals are not detached, and there are no holes or tears in the seal fabric. Any monitoring data in which the roof is not floating on the surface of the VOC, if liquid has accumulated on the external floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: T280-1056	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Water Separation	SOP Index No.: R5131-0005
Pollutant: VOC	Main Standard: § 115.132(a)(2)
Monitoring Information	
Indicator: External Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Any monitoring data in which the roof is not floating on the surface of the VOC, if liquid has accumulated on the external floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a	
Periodic Monitoring Text: Visually inspect and record the inspection of the external floating roof to ensure: the roof is floating on the surface of the VOC and not on the leg supports, liquid has not accumulated on the external floating roof, the seals are not detached, and there are no holes or tears in the seal fabric. Any monitoring data in which the roof is not floating on the surface of the VOC, if liquid has accumulated on the external floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: T280-1057	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Water Separation	SOP Index No.: R5131-0005
Pollutant: VOC	Main Standard: § 115.132(a)(2)
Monitoring Information	
Indicator: External Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Any monitoring data in which the roof is not floating on the surface of the VOC, if liquid has accumulated on the external floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a	
Periodic Monitoring Text: Visually inspect and record the inspection of the external floating roof to ensure: the roof is floating on the surface of the VOC and not on the leg supports, liquid has not accumulated on the external floating roof, the seals are not detached, and there are no holes or tears in the seal fabric. Any monitoring data in which the roof is not floating on the surface of the VOC, if liquid has accumulated on the external floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: T280-1058	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Water Separation	SOP Index No.: R5131-005
Pollutant: VOC	Main Standard: § 115.132(a)(2)
Monitoring Information	
Indicator: External Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: Any monitoring data in which the roof is not floating on the surface of the VOC, if liquid has accumulated on the external floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a	
Periodic Monitoring Text: Visually inspect and record the inspection of the external floating roof to ensure: the roof is floating on the surface of the VOC and not on the leg supports, liquid has not accumulated on the external floating roof, the seals are not detached, and there are no holes or tears in the seal fabric. Any monitoring data in which the roof is not floating on the surface of the VOC, if liquid has accumulated on the external floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: T280-132	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart Kb	SOP Index No.: 60KB-0072
Pollutant: VOC	Main Standard: [G]§ 60.112b(a)(3)
Monitoring Information	
Indicator: VOC Concentration	
Minimum Frequency: Once per year	
Averaging Period: n/a	
Deviation Limit: Failure to repair leaking components equal to or greater than 500 ppm within time limits specified in part 60, subpart VV or place on Delay of Repair in accordance with 40 CFR §60.482-9.	
Periodic Monitoring Text: Measure and record fugitive emissions from the vapor collection system in accordance with part 60, appendix A, method 21.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: T280-132	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart Kb	SOP Index No.: 60KB-0072
Pollutant: VOC	Main Standard: [G]§ 60.112b(a)(3)
Monitoring Information	
Indicator: Visual Inspection	
Minimum Frequency: Once per year	
Averaging Period: n/a	
Deviation Limit: Failure to inspect defects that could result in air emissions.	
Periodic Monitoring Text: Visually inspect all components of the vapor collection system for defects, such as cracks, holes, gaps, loose connections, or broken or missing covers or other closure devices, that could result in air emissions.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: T280-133	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart Kb	SOP Index No.: 60KB-0072
Pollutant: VOC	Main Standard: [G]§ 60.112b(a)(3)
Monitoring Information	
Indicator: VOC Concentration	
Minimum Frequency: Once per year	
Averaging Period: n/a	
Deviation Limit: Failure to repair leaking components equal to or greater than 500 ppm within time limits specified in part 60, subpart VV or place on Delay of Repair in accordance with 40 CFR §60.482-9.	
Periodic Monitoring Text: Measure and record fugitive emissions from the vapor collection system in accordance with part 60, appendix A, method 21.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: T280-133	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart Kb	SOP Index No.: 60KB-0072
Pollutant: VOC	Main Standard: [G]§ 60.112b(a)(3)
Monitoring Information	
Indicator: Visual Inspection	
Minimum Frequency: Once per year	
Averaging Period: n/a	
Deviation Limit: Failure to inspect defects that could result in air emissions.	
Periodic Monitoring Text: Visually inspect all components of the vapor collection system for defects, such as cracks, holes, gaps, loose connections, or broken or missing covers or other closure devices, that could result in air emissions.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: T280-134	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart Kb	SOP Index No.: 60KB-0072
Pollutant: VOC	Main Standard: [G]§ 60.112b(a)(3)
Monitoring Information	
Indicator: VOC Concentration	
Minimum Frequency: Once per year	
Averaging Period: n/a	
Deviation Limit: Failure to repair leaking components equal to or greater than 500 ppm within time limits specified in part 60, subpart VV or place on Delay of Repair in accordance with 40 CFR §60.482-9.	
Periodic Monitoring Text: Measure and record fugitive emissions from the vapor collection system in accordance with part 60, appendix A, method 21.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: T280-134	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart Kb	SOP Index No.: 60KB-0072
Pollutant: VOC	Main Standard: [G]§ 60.112b(a)(3)
Monitoring Information	
Indicator: Visual Inspection	
Minimum Frequency: Once per year	
Averaging Period: n/a	
Deviation Limit: Failure to inspect defects that could result in air emissions.	
Periodic Monitoring Text: Visually inspect all components of the vapor collection system for defects, such as cracks, holes, gaps, loose connections, or broken or missing covers or other closure devices, that could result in air emissions.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: T280-161	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart Kb	SOP Index No.: 60KB-0072
Pollutant: VOC	Main Standard: [G]§ 60.112b(a)(3)
Monitoring Information	
Indicator: VOC Concentration	
Minimum Frequency: Once per year	
Averaging Period: n/a	
Deviation Limit: Failure to repair leaking components equal to or greater than 500 ppm within time limits specified in part 60, subpart VV or place on Delay of Repair in accordance with 40 CFR §60.482-9.	
Periodic Monitoring Text: Measure and record fugitive emissions from the vapor collection system in accordance with part 60, appendix A, method 21.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: T280-161	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart Kb	SOP Index No.: 60KB-0072
Pollutant: VOC	Main Standard: [G]§ 60.112b(a)(3)
Monitoring Information	
Indicator: Visual Inspection	
Minimum Frequency: Once per year	
Averaging Period: n/a	
Deviation Limit: Failure to inspect defects that could result in air emissions.	
Periodic Monitoring Text: Visually inspect all components of the vapor collection system for defects, such as cracks, holes, gaps, loose connections, or broken or missing covers or other closure devices, that could result in air emissions.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: T280-222	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart Kb	SOP Index No.: 60KB-0072
Pollutant: VOC	Main Standard: [G]§ 60.112b(a)(3)
Monitoring Information	
Indicator: VOC Concentration	
Minimum Frequency: Once per year	
Averaging Period: n/a	
Deviation Limit: Failure to repair leaking components equal to or greater than 500 ppm within time limits specified in part 60, subpart VV or place on Delay of Repair in accordance with 40 CFR §60.482-9.	
Periodic Monitoring Text: Measure and record fugitive emissions from the vapor collection system in accordance with part 60, appendix A, method 21.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: T280-222	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart Kb	SOP Index No.: 60KB-0072
Pollutant: VOC	Main Standard: [G]§ 60.112b(a)(3)
Monitoring Information	
Indicator: Visual Inspection	
Minimum Frequency: Once per year	
Averaging Period: n/a	
Deviation Limit: Failure to inspect defects that could result in air emissions.	
Periodic Monitoring Text: Visually inspect all components of the vapor collection system for defects, such as cracks, holes, gaps, loose connections, or broken or missing covers or other closure devices, that could result in air emissions.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: T280-223	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart Kb	SOP Index No.: 60KB-0072
Pollutant: VOC	Main Standard: [G]§ 60.112b(a)(3)
Monitoring Information	
Indicator: VOC Concentration	
Minimum Frequency: Once per year	
Averaging Period: n/a	
Deviation Limit: Failure to repair leaking components equal to or greater than 500 ppm within time limits specified in part 60, subpart VV or place on Delay of Repair in accordance with 40 CFR §60.482-9.	
Periodic Monitoring Text: Measure and record fugitive emissions from the vapor collection system in accordance with part 60, appendix A, method 21.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: T280-223	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart Kb	SOP Index No.: 60KB-0072
Pollutant: VOC	Main Standard: [G]§ 60.112b(a)(3)
Monitoring Information	
Indicator: Visual Inspection	
Minimum Frequency: Once per year	
Averaging Period: n/a	
Deviation Limit: Failure to inspect defects that could result in air emissions.	
Periodic Monitoring Text: Visually inspect all components of the vapor collection system for defects, such as cracks, holes, gaps, loose connections, or broken or missing covers or other closure devices, that could result in air emissions.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: TCH-6	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-0016AMOC
Pollutant: VOC	Main Standard: § 115.123(a)(1)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Once per hour	
Averaging Period: n/a	
Deviation Limit: No pilot flame	
Periodic Monitoring Text: Measure and record the presence of the pilot flame or maintain records of alarm events and duration of alarm events. The presence of a flare pilot flame shall be monitored using a thermocouple or any other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. The monitoring instrumentation shall be maintained, calibrated and operated in accordance with manufacturer's specifications or other written procedures. Any monitoring data which indicates the lack of a pilot flame shall be considered and reported as a deviation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: TDU-BH	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-0112
Pollutant: Opacity	Main Standard: § 111.111(a)(1)(B)
Monitoring Information	
Indicator: Visible Emissions	
Minimum Frequency: once per calendar quarter	
Averaging Period: n/a	
Deviation Limit: Opacity greater than 20% averaged over a six-minute period.	
Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. If visible emissions are observed, the permit holder shall report a deviation. As an alternative, the permit holder may determine the opacity consistent with Test Method 9, as soon as practicable, but no later than 24 hours after observing visible emissions. If the result of the Test Method 9 is opacity above the opacity limit in the applicable requirement, the permit holder shall report a deviation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: TDU-CONVEYOR	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-0113
Pollutant: Opacity	Main Standard: § 111.111(a)(1)(B)
Monitoring Information	
Indicator: Visible Emissions	
Minimum Frequency: once per calendar quarter	
Averaging Period: n/a	
Deviation Limit: Opacity greater than 20% averaged over a six-minute period.	
Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. If visible emissions are observed, the permit holder shall report a deviation. As an alternative, the permit holder may determine the opacity consistent with Test Method 9, as soon as practicable, but no later than 24 hours after observing visible emissions. If the result of the Test Method 9 is opacity above the opacity limit in the applicable requirement, the permit holder shall report a deviation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: TDU-CT	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-0112
Pollutant: Opacity	Main Standard: § 111.111(a)(1)(B)
Monitoring Information	
Indicator: Visible Emissions	
Minimum Frequency: once per calendar quarter	
Averaging Period: n/a	
Deviation Limit: Opacity greater than 20% averaged over a six-minute period.	
Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. If visible emissions are observed, the permit holder shall report a deviation. As an alternative, the permit holder may determine the opacity consistent with Test Method 9, as soon as practicable, but no later than 24 hours after observing visible emissions. If the result of the Test Method 9 is opacity above the opacity limit in the applicable requirement, the permit holder shall report a deviation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: TDU-DRYER	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-0112
Pollutant: Opacity	Main Standard: § 111.111(a)(1)(B)
Monitoring Information	
Indicator: Visible Emissions	
Minimum Frequency: once per calendar quarter	
Averaging Period: n/a	
Deviation Limit: Opacity greater than 20% averaged over a six-minute period.	
Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. If visible emissions are observed, the permit holder shall report a deviation. As an alternative, the permit holder may determine the opacity consistent with Test Method 9, as soon as practicable, but no later than 24 hours after observing visible emissions. If the result of the Test Method 9 is opacity above the opacity limit in the applicable requirement, the permit holder shall report a deviation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: TDU-TO	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-0112
Pollutant: Opacity	Main Standard: § 111.111(a)(1)(B)
Monitoring Information	
Indicator: Visible Emissions	
Minimum Frequency: once per calendar quarter	
Averaging Period: n/a	
Deviation Limit: Opacity greater than 20% averaged over a six-minute period.	
Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. If visible emissions are observed, the permit holder shall report a deviation. As an alternative, the permit holder may determine the opacity consistent with Test Method 9, as soon as practicable, but no later than 24 hours after observing visible emissions. If the result of the Test Method 9 is opacity above the opacity limit in the applicable requirement, the permit holder shall report a deviation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: TDU-TRANSFER	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-0113
Pollutant: Opacity	Main Standard: § 111.111(a)(1)(B)
Monitoring Information	
Indicator: Visible Emissions	
Minimum Frequency: once per calendar quarter	
Averaging Period: n/a	
Deviation Limit: Opacity greater than 20% averaged over a six-minute period.	
Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. If visible emissions are observed, the permit holder shall report a deviation. As an alternative, the permit holder may determine the opacity consistent with Test Method 9, as soon as practicable, but no later than 24 hours after observing visible emissions. If the result of the Test Method 9 is opacity above the opacity limit in the applicable requirement, the permit holder shall report a deviation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: TDU-VETURI	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-0112
Pollutant: Opacity	Main Standard: § 111.111(a)(1)(B)
Monitoring Information	
Indicator: Visible Emissions	
Minimum Frequency: once per calendar quarter	
Averaging Period: n/a	
Deviation Limit: Opacity greater than 20% averaged over a six-minute period.	
Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. If visible emissions are observed, the permit holder shall report a deviation. As an alternative, the permit holder may determine the opacity consistent with Test Method 9, as soon as practicable, but no later than 24 hours after observing visible emissions. If the result of the Test Method 9 is opacity above the opacity limit in the applicable requirement, the permit holder shall report a deviation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: TO-WWTP	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-0112
Pollutant: PM (Opacity)	Main Standard: § 111.111(a)(1)(B)
Monitoring Information	
Indicator: Visible emissions	
Minimum Frequency: Once per quarter	
Averaging Period: n/a	
Deviation Limit: Opacity greater than 20%, or any visible emissions if site chooses not to perform Method 9 observation.	
Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. If visible emissions are observed, the permit holder shall report a deviation. As an alternative, the permit holder may determine the opacity consistent with Test Method 9, as soon as practicable, but no later than 24 hours after observing visible emissions. If the result of the Test Method 9 is opacity above the corresponding opacity limit, the permit holder shall report a deviation.	

Permit Shield

Permit Shield **786**

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
ALK2-CTWR	N/A	40 CFR Part 63, Subpart Q	Cooling tower not operated with chromium-based water treatment chemicals on or after 9/8/94
ALK3-CTWR	N/A	40 CFR Part 63, Subpart Q	Cooling tower not operated with chromium-based water treatment chemicals on or after 9/8/94
ALK3DEBCT	N/A	40 CFR Part 63, Subpart Q	Cooling tower not operated with chromium-based water treatment chemicals on or after 9/8/94
ALK3-F1001	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.
API3CD-SEP	N/A	40 CFR Part 60, Subpart QQQ	Group 1 wastewater stream managed in a piece of equipment that is also subject to the provisions of 40 CFR Part 60, subpart QQQ is required to comply only with 40 CFR 63, Subpart CC.
ARU-SEP	N/A	40 CFR Part 60, Subpart QQQ	Group 1 wastewater stream managed in a piece of equipment that is also subject to the provisions of 40 CFR Part 60, subpart QQQ is required to comply only with 40 CFR 63, Subpart CC.
AU2 D-601	N/A	40 CFR Part 60, Subpart RRR	Group 1 HON process vent that is also subject to the provisions of NSPS RRR is required to comply only with the provisions of the HON rule.
AU2-B601	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
AU2-B601	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.
AU2-B621A	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.
AU2-B621A	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.
AU2-B621B	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.
AU2-B621B	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.
AU2-CTWR	N/A	40 CFR Part 63, Subpart Q	Cooling tower not operated with chromium-based water treatment chemicals on or after 9/8/94.
AU2-FUG	N/A	40 CFR Part 63, Subpart CC	Process units or emission points subject to subparts F, G, H, and I of Part 63 are exempt from MACT CC.
AU2-SEP	N/A	40 CFR Part 60, Subpart QQQ	Group 1 wastewater stream managed in a piece of equipment that is also subject to the provisions of 40 CFR Part 60, subpart QQQ is required to comply only with 40 CFR 63, Subpart CC.
BALLAS-BAS	N/A	40 CFR Part 61, Subpart FF	Segregated storm water is excluded from NESHAP FF.

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
BALLAS-BAS	N/A	40 CFR Part 63, Subpart CC	Segregated storm water is excluded from MACT CC.
BALLAS-BAS	N/A	40 CFR Part 63, Subpart QQ	Affected facility not referenced by another 40 CFR Part 60, 61, or 63 Subpart.
BOOTH 1	N/A	30 TAC Chapter 115, Subchapter E, Division 5	Aerosol coatings (spray paint) are exempt from this division.
BOOTH 1	N/A	30 TAC Chapter 115, Surface Coating Operations	The re-coating of used miscellaneous metal parts and products at a designated on-site maintenance shop that begins operation on or after January 1, 2012.
CAT1-SEP19	N/A	40 CFR Part 60, Subpart QQQ	Group 1 wastewater stream managed in a piece of equipment that is also subject to the provisions of 40 CFR Part 60, subpart QQQ is required to comply only with 40 CFR 63, Subpart CC.
CAT3-SEP21	N/A	40 CFR Part 60, Subpart QQQ	Group 1 wastewater stream managed in a piece of equipment that is also subject to the provisions of 40 CFR Part 60, subpart QQQ is required to comply only with 40 CFR 63, Subpart CC.
CAT3-SEP22	N/A	40 CFR Part 60, Subpart QQQ	Group 1 wastewater stream managed in a piece of equipment that is also subject to the provisions of 40 CFR Part 60, subpart QQQ is required to comply only with 40 CFR 63, Subpart CC.
CFHU-101B	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
CFHU-101B	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.
CFHU-102B	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.
CFHU-102B	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.
CFHU-CTWR	N/A	40 CFR Part 63, Subpart Q	Cooling tower not operated with chromium-based water treatment chemicals on or after 9/8/94
COKR-B101	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.
COKR-B101	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.
COKR-B201	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.
COKR-B201	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.
COKR-B203	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.
COKR-B203	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
COKR-B301	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.
COKR-B302	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.
COKR-B302	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.
COKR-CTWR	N/A	40 CFR Part 63, Subpart Q	Cooling tower not operated with chromium-based water treatment chemicals on or after 9/8/94
COKR-SEP	N/A	40 CFR Part 60, Subpart QQQ	Group 1 wastewater stream managed in a piece of equipment that is also subject to the provisions of 40 CFR Part 60, subpart QQQ is required to comply only with 40 CFR 63, Subpart CC.
D2A	N/A	30 TAC Chapter 115, Storage of VOCs	Tank capacity is less than 1,000 gallons.
D2A	N/A	40 CFR Part 60, Subpart Kb	Tank capacity is less than 75 cubic meters (19,813 gallons).
D2A	N/A	40 CFR Part 63, Subpart CC	Tank capacity is less than 40 cubic meters (10,567 gallons).
D2R	N/A	30 TAC Chapter 115, Storage of VOCs	Tank capacity is less than 1,000 gallons.
D2R	N/A	40 CFR Part 60, Subpart Kb	Tank capacity is less than 75 cubic meters (19,813 gallons).
D2R	N/A	40 CFR Part 63, Subpart CC	Tank capacity is less than 40 cubic meters

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
			(10,567 gallons).
D3A	N/A	30 TAC Chapter 115, Storage of VOCs	Tank capacity is less than 1,000 gallons.
D3A	N/A	40 CFR Part 60, Subpart Kb	Tank capacity is less than 75 cubic meters (19,813 gallons).
D3A	N/A	40 CFR Part 63, Subpart CC	Tank capacity is less than 40 cubic meters (10,567 gallons).
D3R	N/A	30 TAC Chapter 115, Storage of VOCs	Tank capacity is less than 1,000 gallons.
D3R	N/A	40 CFR Part 60, Subpart Kb	Tank capacity is less than 75 cubic meters (19,813 gallons).
D3R	N/A	40 CFR Part 63, Subpart CC	Tank c apacity is less than 40 cubic meters(10,567 gallons).
D4A	N/A	40 CFR Part 60, Subpart Kb	Tank capacity is less than 75 cubic meters (19,813 gallons).
D4A	N/A	40 CFR Part 63, Subpart CC	Tank capacity is less than 40 cubic meters (10,567 gallons).
D4R	N/A	30 TAC Chapter 115, Storage of VOCs	Tank capacity is less than 1,000 gallons.
D4R	N/A	40 CFR Part 60, Subpart Kb	Tank capacity is less than 75 cubic meters (19,813 gallons).
D4R	N/A	40 CFR Part 63, Subpart CC	Tank capacity is less than 40 cubic meters (10,567 gallons).
D5A	N/A	40 CFR Part 60, Subpart Kb	Tank capacity is less than 75 cubic meters (19,813 gallons).
D5A	N/A	40 CFR Part 63, Subpart CC	Tank capacity is less than 40 cubic meters (10,567 gallons).

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
D5R	N/A	30 TAC Chapter 115, Storage of VOCs	Tank capacity is less than 1,000 gallons.
D5R	N/A	40 CFR Part 60, Subpart Kb	Tank capacity is less than 75 cubic meters (19,813 gallons).
D5R	N/A	40 CFR Part 63, Subpart CC	Tank capacity is less than 40 cubic meters (10,567 gallons).
D6A	N/A	30 TAC Chapter 115, Storage of VOCs	Tank capacity is less than 1,000 gallons.
D6A	N/A	40 CFR Part 60, Subpart Kb	Tank capacity is less than 75 cubic meters (19,813 gallons).
D6A	N/A	40 CFR Part 63, Subpart CC	Tank capacity is less than 40 cubic meters (10,567 gallons).
D7R	N/A	40 CFR Part 60, Subpart Kb	Tank capacity is less than 75 cubic meters (19,813 gallons).
D7R	N/A	40 CFR Part 63, Subpart CC	Tank capacity is less than 40 cubic meters (10,567 gallons).
DDU-101B	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.
DDU-101B	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.
DDU-102B	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.
DDU-102B	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
DDU-201B	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.
DDU-201B	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.
DDU-202B	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.
DDU-202B	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.
DDU-B301	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.
DDU-B301	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.
DDU-B302	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.
DDU-B302	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.
DDU-SEP	N/A	40 CFR Part 60, Subpart QQQ	Group 1 wastewater stream managed in a piece of equipment that is also subject to the provisions of 40 CFR Part 60, subpart QQQ is required to comply only with 40 CFR 63, Subpart CC.
DEGREASE08	N/A	30 TAC Chapter 115, Degreasing Processes	Remote reservoir cold solvent cleaner which

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
			uses solvent with a TVP equal to or less than 0.6 psia @ 100 deg. F and which has a drain area less than 16 in^2 and properly disposes of waste solvent in enclosed containers.
DHT-101B	N/A	40 CFR Part 60, Subpart J	Unit for which construction, modification or reconstruction commenced after May 14, 2007.
DHT-201B	N/A	40 CFR Part 60, Subpart J	Unit for which construction, modification or reconstruction commenced after May 14, 2007.
DKTO294-1	N/A	30 TAC Chapter 111, Incineration	Does not burn domestic, municipal, commercial, or industrial solid waste.
DKTO294-2	N/A	30 TAC Chapter 111, Incineration	Does not burn domestic, municipal, commercial, or industrial solid waste.
DKTO294-3	N/A	30 TAC Chapter 111, Incineration	Does not burn domestic, municipal, commercial, or industrial solid waste.
ENVFP-SEP	N/A	40 CFR Part 60, Subpart QQQ	Group 1 wastewater stream managed in a piece of equipment that is also subject to the provisions of 40 CFR Part 60, subpart QQQ is required to comply only with 40 CFR 63, Subpart CC.
EPN-REFWWV	N/A	30 TAC Chapter 117, Subchapter B	Incinerator runs on electric power and is therefore a noncombustion source.
F-29	N/A	40 CFR Part 60, Subpart Kb	Tank capacity is less than 75 cubic meters (19,813 gallons).
FCU1-CTWR	N/A	40 CFR Part 63, Subpart Q	Cooling tower not operated with chromium-

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
			based water treatment chemicals on or after 9/8/94
FCU3	N/A	40 CFR Part 60, Subpart J	Fluid catalytic cracking unit catalyst regenerator which commenced construction, reconstruction, or modification prior to June 11, 1973.
FCU3	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.
FCU3-CTWR	N/A	40 CFR Part 63, Subpart Q	Cooling tower not operated with chromium-based water treatment chemicals on or after 9/8/94
GASLOAD	N/A	30 TAC Chapter 115, Loading and Unloading of VOC	Facility is a motor vehicle fuel dispensing facility.
GRP-APISEP	API-SEP1, API-SEP2	40 CFR Part 60, Subpart QQQ	Group 1 wastewater stream managed in a piece of equipment that is also subject to the provisions of 40 CFR Part 60, subpart QQQ is required to comply only with 40 CFR 63, Subpart CC.
HRU-OWS	N/A	40 CFR Part 60, Subpart QQQ	Group 1 wastewater stream managed in a piece of equipment that is also subject to the provisions of 40 CFR Part 60, subpart QQQ is required to comply only with 40 CFR 63, Subpart CC.
LAB-CTWR1	N/A	40 CFR Part 63, Subpart Q	Cooling tower not operated with chromium-based water treatment chemicals on or after 9/8/94.

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
LAB-CTWR2	N/A	40 CFR Part 63, Subpart Q	Cooling tower not operated with chromium-based water treatment chemicals on or after 9/8/94.
LAB-DWS	N/A	40 CFR Part 60, Subpart QQQ	Group 1 wastewater stream managed in a piece of equipment that is also subject to the provisions of 40 CFR Part 60, subpart QQQ is required to comply only with 40 CFR 63, Subpart CC.
NDU1	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.
NDU1	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.
NDU-CTWR	N/A	40 CFR Part 63, Subpart Q	Cooling tower not operated with chromium-based water treatment chemicals on or after 9/8/94
NDU-OWS	N/A	40 CFR Part 60, Subpart QQQ	Group 1 wastewater stream managed in a piece of equipment that is also subject to the provisions of 40 CFR Part 60, subpart QQQ is required to comply only with 40 CFR 63, Subpart CC.
OVERFLOW-1	N/A	40 CFR Part 61, Subpart FF	Segregated storm water is excluded from NESHAP FF.
OVERFLOW-1	N/A	40 CFR Part 63, Subpart CC	Segregated storm water is excluded from MACT CC.
OVERFLOW-1	N/A	40 CFR Part 63, Subpart QQ	Affected facility not referenced by another 40

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
			CFR Part 60, 61, or 63 Subpart.
PRS3-CTWR	N/A	40 CFR Part 63, Subpart Q	Cooling tower not operated with chromium-based water treatment chemicals on or after 9/8/94
PS3A-101BA	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.
PS3A-101BA	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 15, 2007.
PS3A-101BB	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.
PS3A-101BB	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.
PS3A-102BA	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.
PS3A-102BA	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.
PS3A-102BB	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.
PS3A-102BB	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.
PS3A-103B	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator,

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
			furnace, or process heater.
PS3A-103B	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.
PS3A-OWS	N/A	40 CFR Part 60, Subpart QQQ	Group 1 wastewater stream managed in a piece of equipment that is also subject to the provisions of 40 CFR Part 60, subpart QQQ is required to comply only with 40 CFR 63, Subpart CC.
PS3B-401BA	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.
PS3B-401BA	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.
PS3B-401BB	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.
PS3B-401BB	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.
PS3B-401BC	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.
PS3B-401BC	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.
PS3B-402BE	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
PS3B-402BE	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.
PS3B-402BF	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.
PS3B-402BF	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.
PS3B-402BG	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.
PS3B-402BG	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.
PS3B-SEP1	N/A	40 CFR Part 60, Subpart QQQ	Group 1 wastewater stream managed in a piece of equipment that is also subject to the provisions of 40 CFR Part 60, subpart QQQ is required to comply only with 40 CFR 63, Subpart CC.
PS3B-SEP2	N/A	40 CFR Part 60, Subpart QQQ	Group 1 wastewater stream managed in a piece of equipment that is also subject to the provisions of 40 CFR Part 60, subpart QQQ is required to comply only with 40 CFR 63, Subpart CC.
PS3-CTWR	N/A	40 CFR Part 63, Subpart Q	Cooling tower not operated with chromium-based water treatment chemicals on or after 9/8/94

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
RDU-601B	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.
RDU-601B	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.
RDU-SEP	N/A	40 CFR Part 60, Subpart QQQ	Group 1 wastewater stream managed in a piece of equipment that is also subject to the provisions of 40 CFR Part 60, subpart QQQ is required to comply only with 40 CFR 63, Subpart CC.
RHU-201B	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.
RHU-201B	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.
RHU-202B	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.
RHU-202B	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.
RHU-301B	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.
RHU-301B	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.
RHU-302B	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator,

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
			furnace, or process heater.
RHU-302B	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.
RHU-401B	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.
RHU-401B	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.
RHU-402B	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.
RHU-402B	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.
RHU-501B	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.
RHU-501B	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.
RHU-502B	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.
RHU-502B	N/A	40 CFR Part 60, Subpart J	Unit for which construction, modification or reconstruction commenced after May 14, 2007.
RHU-601B	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator,

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
			furnace, or process heater.
RHU-601B	N/A	40 CFR Part 60, Subpart Dc	Constructed prior to June 9, 1989 and has not been reconstructed or modified after the applicability date.
RHU-601B	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.
RHU-SEP1	N/A	40 CFR Part 60, Subpart QQQ	Group 1 wastewater stream managed in a piece of equipment that is also subject to the provisions of 40 CFR Part 60, subpart QQQ is required to comply only with 40 CFR 63, Subpart CC.
RHU-SEP2	N/A	40 CFR Part 60, Subpart QQQ	Group 1 wastewater stream managed in a piece of equipment that is also subject to the provisions of 40 CFR Part 60, subpart QQQ is required to comply only with 40 CFR 63, Subpart CC.
RHU-T1012	N/A	40 CFR Part 60, Subpart Ka	Vessel stores a petroleum liquid with a Reid vapor pressure < 6.9 kPa and maximum TVP < 6.9 kPa (1.0 psia).
RHU-T1013	N/A	40 CFR Part 60, Subpart Ka	Vessel stores a petroleum liquid with a Reid vapor pressure < 6.9 kPa and maximum TVP < 6.9 kPa (1.0 psia).
SHOCK-BAS	N/A	40 CFR Part 61, Subpart FF	Segregated storm water is excluded from NESHAP FF.
SHOCK-BAS	N/A	40 CFR Part 63, Subpart CC	Segregated storm water is excluded from

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
			MACT CC.
SHOCK-BAS	N/A	40 CFR Part 63, Subpart QQ	Affected facility not referenced by another 40 CFR Part 60, 61, or 63 Subpart.
SRU12LOAD	N/A	30 TAC Chapter 115, Loading and Unloading of VOC	Sulfur loading operations are not VOC loading operations.
SRU1LOAD	N/A	30 TAC Chapter 115, Loading and Unloading of VOC	Sulfur loading operations are not VOC loading operations.
SRU-F8C	N/A	30 TAC Chapter 111, Incineration	Does not burn municipal, commercial, or industrial solid waste.
SRU-F8C	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.
SRU-F8D	N/A	30 TAC Chapter 111, Incineration	Does not burn municipal, commercial, or industrial solid waste.
SRU-F8D	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.
SURGE-1	N/A	40 CFR Part 61, Subpart FF	Segregated storm water is excluded from NESHAP FF.
SURGE-1	N/A	40 CFR Part 63, Subpart CC	Segregated storm water is excluded from MACT CC.
SURGE-1	N/A	40 CFR Part 63, Subpart QQ	Affected facility not referenced by another 40 CFR Part 60, 61, or 63 Subpart.
SURGE-2	N/A	40 CFR Part 61, Subpart FF	Segregated storm water is excluded from NESHAP FF.

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
SURGE-2	N/A	40 CFR Part 63, Subpart CC	Segregated storm water is excluded from MACT CC.
SURGE-2	N/A	40 CFR Part 63, Subpart QQ	Affected facility not referenced by another 40 CFR Part 60, 61, or 63 Subpart.
SURGE-3	N/A	40 CFR Part 61, Subpart FF	Segregated storm water is excluded from NESHAP FF.
SURGE-3	N/A	40 CFR Part 63, Subpart CC	Segregated storm water is excluded from MACT CC.
SURGE-3	N/A	40 CFR Part 63, Subpart QQ	Affected facility not referenced by another 40 CFR Part 60, 61, or 63 Subpart.
T1003	N/A	40 CFR Part 60, Subpart Kb	Storage vessels with capacity greater than 39,900 gal storing liquid with TVP < 0.5 psia and vessels with capacity between 19,800 and 39,900 gal and storing liquid with TVP < 2.2 psia are not subject to this subpart.
T280-1004	N/A	40 CFR Part 60, Subpart Kb	Storage vessels with capacity greater than 39,900 gal storing liquid with TVP < 0.5 psia and vessels with capacity between 19,800 and 39,900 gal and storing liquid with TVP < 2.2 psia are not subject to this subpart.
T280-101	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-101	N/A	40 CFR Part 61, Subpart Y	Group 1 tank subject to 40 CFR 63, Subpart G.
T280-1010	N/A	40 CFR Part 60, Subpart Kb	Storage vessels with capacity greater than 39,900 gal storing liquid with TVP < 0.5 psia and vessels with capacity between 19,800 and

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
			39,900 gal and storing liquid with TVP < 2.2 psia are not subject to this subpart.
T280-1010	N/A	40 CFR Part 63, Subpart CC	MACT CC provisions do not apply to processes specified in 40 CFR §63.640(g)(1)-(6).
T280-1018	N/A	40 CFR Part 60, Subpart Kb	Storage vessels with capacity greater than 39,900 gal storing liquid with TVP < 0.5 psia and vessels with capacity between 19,800 and 39,900 gal and storing liquid with TVP < 2.2 psia are not subject to this subpart.
T280-102	N/A	40 CFR Part 60, Subpart Kb	Group 1 tank subject to 40 CFR 63, Subpart G.
T280-102	N/A	40 CFR Part 61, Subpart Y	Group 1 tank subject to 40 CFR 63, Subpart G.
T280-1021	N/A	40 CFR Part 60, Subpart K	Reconstructed after 5/19/1978.
T280-1021	N/A	40 CFR Part 60, Subpart Ka	Reconstructed after 7/23/1984
T280-1024	N/A	40 CFR Part 60, Subpart K	constructed prior to 6/11/73
T280-1025	N/A	40 CFR Part 60, Subpart K	constructed prior to 6/11/73
T280-1039	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-1042	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-1045	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-1046	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-1047	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
T280-1048	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-1054	N/A	40 CFR Part 60, Subpart QQQ	Group 1 wastewater stream managed in a piece of equipment that is also subject to the provisions of 40 CFR Part 60, subpart QQQ is required to comply only with 40 CFR 63, Subpart CC.
T280-1056	N/A	40 CFR Part 60, Subpart QQQ	Group 1 wastewater stream managed in a piece of equipment that is also subject to the provisions of 40 CFR Part 60, subpart QQQ is required to comply only with 40 CFR 63, Subpart CC.
T280-1057	N/A	40 CFR Part 60, Subpart QQQ	Group 1 wastewater stream managed in a piece of equipment that is also subject to the provisions of 40 CFR Part 60, subpart QQQ is required to comply only with 40 CFR 63, Subpart CC.
T280-107	N/A	40 CFR Part 60, Subpart Kb	Group 1 tank subject to 40 CFR 63, Subpart G.
T280-107	N/A	40 CFR Part 61, Subpart Y	Group 1 tank subject to 40 CFR 63, Subpart G.
T280-108	N/A	40 CFR Part 60, Subpart Kb	Group 1 tank subject to 40 CFR 63, Subpart G.
T280-108	N/A	40 CFR Part 61, Subpart Y	Group 1 tank subject to 40 CFR 63, Subpart G.
T280-110	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-112	N/A	40 CFR Part 60, Subpart Kb	Group 1 tank subject to 40 CFR 63, Subpart

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
			G.
T280-112	N/A	40 CFR Part 61, Subpart Y	Group 1 tank subject to 40 CFR 63, Subpart G.
T280-114	N/A	40 CFR Part 60, Subpart Kb	Group 1 tank subject to 40 CFR 63, Subpart G.
T280-114	N/A	40 CFR Part 61, Subpart Y	Group 1 tank subject to 40 CFR 63, Subpart G.
T280-115	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-115	N/A	40 CFR Part 61, Subpart Y	Group 1 tank subject to 40 CFR 63, Subpart G.
T280-116	N/A	40 CFR Part 60, Subpart Kb	Group 1 tank subject to 40 CFR 63, Subpart G.
T280-116	N/A	40 CFR Part 61, Subpart Y	Group 1 tank subject to 40 CFR 63, Subpart G.
T280-128	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-129	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-130	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-135	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-136	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-137	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-138	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-160	N/A	40 CFR Part 60, Subpart K	Not storing petroleum liquid.

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
T280-160	N/A	40 CFR Part 63, Subpart CC	Process specified in 63.640(g)(1)-(6).
T280-17	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-18	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-181	N/A	40 CFR Part 60, Subpart K	Reconstructed after 5/19/1978.
T280-181	N/A	40 CFR Part 60, Subpart Ka	Reconstructed after 7/23/1984
T280-184	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-187	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-188	N/A	40 CFR Part 60, Subpart K	Reconstructed after 5/19/1978.
T280-188	N/A	40 CFR Part 60, Subpart Ka	Reconstructed after 7/23/1984
T280-19	N/A	40 CFR Part 60, Subpart K	Reconstructed after 5/19/1978.
T280-19	N/A	40 CFR Part 60, Subpart Ka	Reconstructed after 7/23/1984
T280-20	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-22	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-24	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-26	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-271	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-28	N/A	40 CFR Part 60, Subpart Kb	Group 1 tank subject to 40 CFR 63, Subpart G.
T280-28	N/A	40 CFR Part 61, Subpart Y	Group 1 tank subject to 40 CFR 63, Subpart G.
T280-29	N/A	40 CFR Part 60, Subpart Kb	Group 1 tank subject to 40 CFR 63, Subpart

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
			G.
T280-29	N/A	40 CFR Part 61, Subpart Y	Group 1 tank subject to 40 CFR 63, Subpart G.
T280-30	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-3003	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-3003	N/A	40 CFR Part 63, Subpart CC	Process specified in 63.640(g)(1)-(6).
T280-3004	N/A	30 TAC Chapter 115, Storage of VOCs	Not storing VOC.
T280-3004	N/A	40 CFR Part 60, Subpart Kb	Not storing VOL.
T280-3004	N/A	40 CFR Part 63, Subpart CC	Process specified in 63.640(g)(2).
T280-3006	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-3006	N/A	40 CFR Part 63, Subpart CC	Process specified in 63.640(g)(1)-(6).
T280-3007	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-3007	N/A	40 CFR Part 63, Subpart CC	Process specified in 63.640(g)(1)-(6).
T280-3010	N/A	30 TAC Chapter 115, Storage of VOCs	Located in BPA, DFW, El Paso or HGA and in a motor vehicle fuel dispensing service and has a nominal capacity < 25,000 gallons.
T280-3010	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-3021	N/A	30 TAC Chapter 115, Storage of VOCs	Not storing VOC.
T280-3021	N/A	40 CFR Part 60, Subpart Kb	Not storing VOL.
T280-3021	N/A	40 CFR Part 63, Subpart CC	Process specified in 63.640(g)(1)-(6).
T280-3022	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
T280-3022	N/A	40 CFR Part 63, Subpart CC	Process specified in 63.640(g)(1)-(6).
T280-3023	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-3023	N/A	40 CFR Part 63, Subpart CC	Process specified in 63.640(g)(1)-(6).
T280-3024	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-3024	N/A	40 CFR Part 63, Subpart CC	Process specified in 63.640(g)(1)-(6).
T280-3025	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-3025	N/A	40 CFR Part 63, Subpart CC	Process specified in 63.640(g)(1)-(6).
T280-3026	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-3026	N/A	40 CFR Part 63, Subpart CC	Process specified in 63.640(g)(1)-(6).
T280-3040	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-3040	N/A	40 CFR Part 63, Subpart CC	Process specified in 63.640(g)(1)-(6).
T280-3041	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-3041	N/A	40 CFR Part 63, Subpart CC	Process specified in 63.640(g)(1)-(6).
T280-3042	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-3042	N/A	40 CFR Part 63, Subpart CC	Process specified in 63.640(g)(1)-(6).
T280-3043	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-3043	N/A	40 CFR Part 63, Subpart CC	Process specified in 63.640(g)(1)-(6).
T280-3044	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-3044	N/A	40 CFR Part 63, Subpart CC	Process specified in 63.640(g)(1)-(6).
T280-3045	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
T280-3045	N/A	40 CFR Part 63, Subpart CC	Process specified in 63.640(g)(1)-(6).
T280-3103	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-3103	N/A	40 CFR Part 63, Subpart CC	Process specified in 63.640(g)(1)-(6).
T280-3106	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-3106	N/A	40 CFR Part 63, Subpart CC	Process specified in 63.640(g)(1)-(6).
T280-3107	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-3107	N/A	40 CFR Part 63, Subpart CC	Process specified in 63.640(g)(1)-(6).
T280-3121	N/A	30 TAC Chapter 115, Storage of VOCs	Not storing VOC.
T280-3121	N/A	40 CFR Part 60, Subpart Kb	Not storing VOL.
T280-3121	N/A	40 CFR Part 63, Subpart CC	Process specified in 63.640(g)(1)-(6).
T280-34	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-36	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-37	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-38	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-39	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-4000	N/A	40 CFR Part 60, Subpart Ka	Vessel stores a petroleum liquid with a Reid vapor pressure < 6.9 kPa and maximum TVP<6.9 kPA (1.0 psia).
T280-4001	N/A	40 CFR Part 60, Subpart Ka	Vessel stores a petroleum liquid with a Reid vapor pressure < 6.9 kPa and maximum TVP<6.9 kPA (1.0 psia).
T280-4002	N/A	40 CFR Part 60, Subpart Ka	Vessel stores a petroleum liquid with a Reid

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
			vapor pressure < 6.9 kPa and maximum TVP<6.9 kPA (1.0 psia).
T280-4003	N/A	40 CFR Part 60, Subpart Ka	Vessel stores a petroleum liquid with a Reid vapor pressure < 6.9 kPa and maximum TVP<6.9 kPA (1.0 psia).
T280-42	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-43	N/A	40 CFR Part 60, Subpart Kb	Storage vessels with capacity greater than 39,000 gal storing liquid with TVP < 0.5 psia and vessels with capacity between 19,800 and 39,900 gal and storing liquid with TVP < 2.2 psia are not subject to this subpart.
T280-44	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-45	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-46	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-47	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-48	N/A	40 CFR Part 60, Subpart Kb	Storage vessels with capacity greater than 39,000 gal storing liquid with TVP < 0.5 psia and vessels with capacity between 19,800 and 39,900 gal and storing liquid with TVP < 2.2 psia are not subject to this subpart.
T280-49	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-50	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-504	N/A	40 CFR Part 60, Subpart K	Reconstructed after 5/19/1978.
T280-504	N/A	40 CFR Part 60, Subpart Ka	Reconstructed after 7/23/1984

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
T280-51	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-515	N/A	30 TAC Chapter 115, Storage of VOCs	Not storing VOC.
T280-515	N/A	40 CFR Part 60, Subpart Kb	Not storing VOL.
T280-515	N/A	40 CFR Part 63, Subpart CC	Process specified in 63.640(g)(1)-(6).
T280-516	N/A	30 TAC Chapter 115, Storage of VOCs	Not storing VOC.
T280-516	N/A	40 CFR Part 60, Subpart Kb	Not storing VOL.
T280-516	N/A	40 CFR Part 63, Subpart CC	Process specified in 63.640(g)(1)-(6).
T280-518	N/A	30 TAC Chapter 115, Storage of VOCs	Not storing VOC.
T280-518	N/A	40 CFR Part 60, Subpart Kb	Not storing VOL.
T280-518	N/A	40 CFR Part 63, Subpart CC	Process specified in 63.640(g)(1)-(6).
T280-52	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-528	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-529	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-53	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-530	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-531	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-532	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-534	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-535	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-536	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
T280-537	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-54	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-55	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-56	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-561	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-57	N/A	40 CFR Part 60, Subpart Ka	Vessel stores a petroleum liquid with a Reid vapor pressure < 6.9 kPa and maximum TVP < 6.9 kPa (1.0 psia).
T280-60	N/A	40 CFR Part 60, Subpart Kb	Storage vessels with capacity greater than 39,000 gal storing liquid with TVP < 0.5 psia and vessels with capacity between 19,800 and 39,900 gal and storing liquid with TVP < 2.2 psia are not subject to this subpart.
T280-61	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-63	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-65	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-652	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-653	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-7	N/A	40 CFR Part 60, Subpart Kb	Storage vessels with capacity greater than 39,000 gal storing liquid with TVP < 0.5 psia and vessels with capacity between 19,800 and 39,900 gal and storing liquid with TVP < 2.2 psia are not subject to this subpart.
T280-71	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
T280-72	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-73	N/A	40 CFR Part 60, Subpart Kb	Storage vessels with capacity greater than 39,000 gal storing liquid with TVP < 0.5 psia and vessels with capacity between 19,800 and 39,900 gal and storing liquid with TVP < 2.2 psia are not subject to this subpart.
T280-8	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-80	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-9	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-90	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-91	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-92	N/A	40 CFR Part 60, Subpart K	Reconstructed after 5/19/1978.
T280-92	N/A	40 CFR Part 60, Subpart Ka	Reconstructed after 7/23/1984
T280-94	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-95	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
T280-97	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
TDU-OWS	N/A	40 CFR Part 60, Subpart QQQ	Group 1 wastewater stream managed in a piece of equipment that is also subject to the provisions of 40 CFR Part 60, subpart QQQ is required to comply only with 40 CFR 63, Subpart CC.
TK-1	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
TK-1	N/A	40 CFR Part 63, Subpart CC	Process specified in 63.640(g)(1)-(6).

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
TK-10	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
TK-10	N/A	40 CFR Part 63, Subpart CC	Process specified in 63.640(g)(1)-(6).
TK-2	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
TK-2	N/A	40 CFR Part 63, Subpart CC	Process specified in 63.640(g)(1)-(6).
TK-201	N/A	40 CFR Part 63, Subpart CC	Process specified in 63.640(g)(1)-(6).
TK-210F	N/A	40 CFR Part 60, Subpart Kb	Storage vessels with capacity greater than 39,000 gal storing liquid with TVP < 0.5 psia and vessels with capacity between 19,800 and 39,900 gal and storing liquid with TVP < 2.2 psia are not subject to this subpart.
TK-303F	N/A	30 TAC Chapter 115, Storage of VOCs	Not storing VOC.
TK-303F	N/A	40 CFR Part 60, Subpart Kb	Not storing VOL.
TK-303F	N/A	40 CFR Part 63, Subpart CC	Process specified in 63.640(g)(1)-(6).
TK-304F	N/A	40 CFR Part 60, Subpart Kb	Pressure vessels designed to operate in excess of 204.9 kPa and without emissions to the atmosphere.
TK-304F	N/A	40 CFR Part 63, Subpart CC	Pressure vessels designed to operate in excess of 204.9 kPa and without emissions to the atmosphere.
TK-305F	N/A	30 TAC Chapter 115, Storage of VOCs	Not storing VOC.
TK-305F	N/A	40 CFR Part 60, Subpart Kb	Not storing VOL.
TK-305F	N/A	40 CFR Part 63, Subpart CC	Process specified in 63.640(g)(1)-(6).
TK-314F	N/A	30 TAC Chapter 115, Storage of VOCs	Not storing VOC.

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
TK-314F	N/A	40 CFR Part 60, Subpart Kb	Not storing VOL.
TK-314F	N/A	40 CFR Part 63, Subpart CC	Process specified in 63.640(g)(1)-(6).
TK-315F	N/A	30 TAC Chapter 115, Storage of VOCs	Not storing VOC.
TK-315F	N/A	40 CFR Part 60, Subpart Kb	Not storing VOL.
TK-315F	N/A	40 CFR Part 63, Subpart CC	Process specified in 63.640(g)(1)-(6).
TK-356F	N/A	30 TAC Chapter 115, Storage of VOCs	Not storing VOC.
TK-356F	N/A	40 CFR Part 60, Subpart Kb	Not storing VOL.
TK-356F	N/A	40 CFR Part 63, Subpart CC	Process specified in 63.640(g)(1)-(6).
TK-440F	N/A	30 TAC Chapter 115, Storage of VOCs	Not storing VOC.
TK-440F	N/A	40 CFR Part 60, Subpart Kb	Not storing VOL.
TK-440F	N/A	40 CFR Part 63, Subpart CC	Process specified in 63.640(g)(1)-(6).
TK-517F	N/A	30 TAC Chapter 115, Storage of VOCs	Not storing VOC.
TK-517F	N/A	40 CFR Part 60, Subpart Kb	Not storing VOL.
TK-517F	N/A	40 CFR Part 63, Subpart CC	Process specified in 63.640(g)(1)-(6).
TK-527F	N/A	30 TAC Chapter 115, Storage of VOCs	Not storing VOC.
TK-527F	N/A	40 CFR Part 60, Subpart Kb	Not storing VOL.
TK-527F	N/A	40 CFR Part 63, Subpart CC	Process specified in 63.640(g)(1)-(6).
TK-602	N/A	40 CFR Part 60, Subpart Kb	Pressure vessels designed to operate in excess of 204.9 kPa and without emissions to the atmosphere.
TK-602	N/A	40 CFR Part 63, Subpart CC	Pressure vessel designed to operate in excess

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
			of 204.9 kPa and without emissions to the atmosphere.
TK-603	N/A	40 CFR Part 60, Subpart Kb	Pressure vessels designed to operate in excess of 204.9 kPa and without emissions to the atmosphere.
TK-603	N/A	40 CFR Part 63, Subpart CC	Pressure vessel designed to operate in excess of 204.9 kPa and without emissions to the atmosphere.
TK-604	N/A	40 CFR Part 60, Subpart Kb	Pressure vessels designed to operate in excess of 204.9 kPa and without emissions to the atmosphere.
TK-604	N/A	40 CFR Part 63, Subpart CC	Pressure vessel designed to operate in excess of 204.9 kPa and without emissions to the atmosphere.
TK-610	N/A	40 CFR Part 60, Subpart Kb	Pressure vessels designed to operate in excess of 204.9 kPa and without emissions to the atmosphere.
TK-610	N/A	40 CFR Part 63, Subpart CC	Pressure vessel designed to operate in excess of 204.9 kPa and without emissions to the atmosphere.
TK-611	N/A	40 CFR Part 60, Subpart Kb	Pressure vessels designed to operate in excess of 204.9 kPa and without emissions to the atmosphere.
TK-611	N/A	40 CFR Part 63, Subpart CC	Pressure vessel designed to operate in excess of 204.9 kPa and without emissions to the atmosphere.

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
TK-612	N/A	40 CFR Part 60, Subpart Kb	Pressure vessels designed to operate in excess of 204.9 kPa and without emissions to the atmosphere.
TK-612	N/A	40 CFR Part 63, Subpart CC	Pressure vessel designed to operate in excess of 204.9 kPa and without emissions to the atmosphere.
TK-613	N/A	40 CFR Part 60, Subpart Kb	Pressure vessels designed to operate in excess of 204.9 kPa and without emissions to the atmosphere.
TK-613	N/A	40 CFR Part 63, Subpart CC	Pressure vessel designed to operate in excess of 204.9 kPa and without emissions to the atmosphere.
TK-614	N/A	40 CFR Part 60, Subpart Kb	Pressure vessels designed to operate in excess of 204.9 kPa and without emissions to the atmosphere.
TK-614	N/A	40 CFR Part 63, Subpart CC	Pressure vessel designed to operate in excess of 204.9 kPa and without emissions to the atmosphere.
TK-615	N/A	40 CFR Part 60, Subpart Kb	Pressure vessels designed to operate in excess of 204.9 kPa and without emissions to the atmosphere.
TK-615	N/A	40 CFR Part 63, Subpart CC	Pressure vessel designed to operate in excess of 204.9 kPa and without emissions to the atmosphere.
TK-616	N/A	40 CFR Part 60, Subpart Kb	Pressure vessels designed to operate in excess of 204.9 kPa and without emissions to

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
			the atmosphere.
TK-616	N/A	40 CFR Part 63, Subpart CC	Pressure vessel designed to operate in excess of 204.9 kPa and without emissions to the atmosphere.
TK-618	N/A	40 CFR Part 60, Subpart Kb	Pressure vessels designed to operate in excess of 204.9 kPa and without emissions to the atmosphere.
TK-618	N/A	40 CFR Part 63, Subpart CC	Pressure vessel designed to operate in excess of 204.9 kPa and without emissions to the atmosphere.
TK-620	N/A	40 CFR Part 60, Subpart Kb	Pressure vessels designed to operate in excess of 204.9 kPa and without emissions to the atmosphere.
TK-620	N/A	40 CFR Part 63, Subpart CC	Pressure vessel designed to operate in excess of 204.9 kPa and without emissions to the atmosphere.
TK-622	N/A	40 CFR Part 60, Subpart Kb	Pressure vessels designed to operate in excess of 204.9 kPa and without emissions to the atmosphere.
TK-622	N/A	40 CFR Part 63, Subpart CC	Pressure vessel designed to operate in excess of 204.9 kPa and without emissions to the atmosphere.
TK-624	N/A	40 CFR Part 60, Subpart Kb	Pressure vessels designed to operate in excess of 204.9 kPa and without emissions to the atmosphere.
TK-624	N/A	40 CFR Part 63, Subpart CC	Pressure vessel designed to operate in excess

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
			of 204.9 kPa and without emissions to the atmosphere.
TK-626	N/A	40 CFR Part 60, Subpart Kb	Pressure vessels designed to operate in excess of 204.9 kPa and without emissions to the atmosphere.
TK-626	N/A	40 CFR Part 63, Subpart CC	Pressure vessel designed to operate in excess of 204.9 kPa and without emissions to the atmosphere.
TK-9	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
TK-9	N/A	40 CFR Part 63, Subpart CC	Process specified in 63.640(g)(1)-(6).
TK-ACIDTK	N/A	30 TAC Chapter 115, Storage of VOCs	Not storing VOC.
TK-ACIDTK	N/A	40 CFR Part 60, Subpart Kb	Not storing VOL.
TK-ACIDTK	N/A	40 CFR Part 63, Subpart CC	Process specified in 63.640(g)(1)-(6).
TK-F109	N/A	30 TAC Chapter 115, Storage of VOCs	Not storing VOC.
TK-F109	N/A	40 CFR Part 60, Subpart Kb	Not storing VOL.
TK-F109	N/A	40 CFR Part 63, Subpart CC	Process specified in 63.640(g)(1)-(6).
TK-F170	N/A	40 CFR Part 60, Subpart Kb	Storage vessel has a design capacity < 75 m3 (19,800 gal).
TK-F170	N/A	40 CFR Part 63, Subpart CC	Process specified in 63.640(g)(1)-(6).
TK-F180	N/A	30 TAC Chapter 115, Storage of VOCs	Not storing VOC.
TK-F180	N/A	40 CFR Part 60, Subpart Kb	Not storing VOL.
TK-F180	N/A	40 CFR Part 63, Subpart CC	Process specified in 63.640(g)(1)-(6).

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
TK-F190	N/A	30 TAC Chapter 115, Storage of VOCs	Not storing VOC.
TK-F190	N/A	40 CFR Part 60, Subpart Kb	Not storing VOL.
TK-F190	N/A	40 CFR Part 63, Subpart CC	Process specified in 63.640(g)(1)-(6).
TK-F209	N/A	40 CFR Part 60, Subpart Kb	Storage vessel has a design capacity < 75 m3 (19,800 gal).
TK-F209	N/A	40 CFR Part 63, Subpart CC	Process specified in 63.640(g)(1)-(6).
TK-F617	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
TK-F617	N/A	40 CFR Part 63, Subpart CC	Process specified in 63.640(g)(1)-(6).
TK-F620	N/A	40 CFR Part 60, Subpart Kb	Storage vessels with capacity greater than 39,900 gal storing liquid with TVP < 0.5 psia and vessels with capacity between 19,800 and 39,900 gal and storing liquid with TVP < 2.2 psia are not subject to this subpart.
TK-FUELTK	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
TK-G405	N/A	40 CFR Part 60, Subpart K	Storage vessel constructed prior to 6/11/73.
TK-G405	N/A	40 CFR Part 63, Subpart CC	Process specified in 63.640(g)(1)-(6).
TK-I656	N/A	30 TAC Chapter 115, Storage of VOCs	Not storing VOC.
TK-I656	N/A	40 CFR Part 60, Subpart Kb	Not storing VOL.
TK-I656	N/A	40 CFR Part 63, Subpart CC	Process specified in 63.640(g)(1)-(6).
TK-I657	N/A	30 TAC Chapter 115, Storage of VOCs	Not storing VOC.
TK-I657	N/A	40 CFR Part 60, Subpart Kb	Not storing VOL.
TK-I657	N/A	40 CFR Part 63, Subpart CC	Process specified in 63.640(g)(1)-(6).

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
TK-IWCP	N/A	30 TAC Chapter 115, Storage of VOCs	Not storing VOC.
TK-IWCP	N/A	40 CFR Part 60, Subpart Kb	Not storing VOL.
TK-IWCP	N/A	40 CFR Part 63, Subpart CC	Process specified in 63.640(g)(1)-(6).
TK-L1501	N/A	30 TAC Chapter 115, Storage of VOCs	Not storing VOC.
TK-L1501	N/A	40 CFR Part 60, Subpart Kb	Not storing VOL.
TK-L1501	N/A	40 CFR Part 63, Subpart CC	Process specified in 63.640(g)(1)-(6).
TK-L1502	N/A	30 TAC Chapter 115, Storage of VOCs	Not storing VOC.
TK-L1502	N/A	40 CFR Part 60, Subpart Kb	Not storing VOL.
TK-L1502	N/A	40 CFR Part 63, Subpart CC	Process specified in 63.640(g)(1)-(6).
TK-R602	N/A	30 TAC Chapter 115, Storage of VOCs	Not storing VOC.
TK-R602	N/A	40 CFR Part 60, Subpart Kb	Not storing VOL.
TK-R602	N/A	40 CFR Part 63, Subpart CC	Process specified in 63.640(g)(1)-(6).
TK-SM1001	N/A	40 CFR Part 60, Subpart Kb	Tank capacity is less than 75 cubic meters (19,813 gallons).
TK-T1000	N/A	30 TAC Chapter 115, Storage of VOCs	Not storing VOC.
TK-T1000	N/A	40 CFR Part 60, Subpart Kb	Not storing VOL.
TK-T1000	N/A	40 CFR Part 63, Subpart CC	Process specified in 63.640(g)(1)-(6).
TK-T1001	N/A	30 TAC Chapter 115, Storage of VOCs	Not storing VOC.
TK-T1001	N/A	40 CFR Part 60, Subpart Kb	Not storing VOL.
TK-T1001	N/A	40 CFR Part 63, Subpart CC	Process specified in 63.640(g)(1)-(6).

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
TK-T1002	N/A	30 TAC Chapter 115, Storage of VOCs	Not storing VOC.
TK-T1002	N/A	40 CFR Part 60, Subpart Kb	Not storing VOL.
TK-T1002	N/A	40 CFR Part 63, Subpart CC	Process specified in 63.640(g)(1)-(6).
TK-V305	N/A	30 TAC Chapter 115, Storage of VOCs	Not storing VOC.
TK-V305	N/A	40 CFR Part 60, Subpart Kb	Not storing VOL.
TK-V305	N/A	40 CFR Part 63, Subpart CC	Process specified in 63.640(g)(1)-(6).
TNT402	N/A	40 CFR Part 60, Subpart Kb	Storage vessels with capacity greater than 39,900 gal storing liquid with TVP < 0.5 psia and vessels with capacity between 19,800 and 39,900 gal and storing liquid with TVP < 2.2 psia are not subject to this subpart.
TNTGRP-1	TNT003, TNT004, TNT017, TNT151, TNT153, TNT154, TNT156, TNT165, TNT313, TNT368	40 CFR Part 60, Subpart Kb	Tank capacity is less than 75 cubic meters (19,813 gallons).
TNTGRP-2	280-4011, 280-4016, TNT022, TNT029, TNT030, TNT037, TNT052, TNT053, TNT054, TNT058, TNT059, TNT078, TNT079, TNT081, TNT082, TNT083, TNT084, TNT085, TNT087, TNT088, TNT090, TNT094, TNT095, TNT096, TNT131, TNT132, TNT133, TNT140, TNT144, TNT150, TNT155, TNT157, TNT161,	40 CFR Part 60, Subpart Kb	Tank capacity is less than 75 cubic meters (19,813 gallons).

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
	TNT162, TNT164, TNT166, TNT167, TNT168, TNT171, TNT172, TNT173, TNT175, TNT176, TNT177, TNT178, TNT179, TNT181, TNT182, TNT183, TNT184, TNT185, TNT186, TNT187, TNT189, TNT190, TNT191, TNT192, TNT194, TNT195, TNT196, TNT197, TNT210, TNT211, TNT212, TNT214, TNT224, TNT227, TNT252, TNT257, TNT332, TNT339, TNT362, TNT363, TNT367, TNT374, TNT375, TNT376, TNT388, TNT389, TNT394, TNT395, TNT398, TNT399, TNT405, TNT406, TNT423, TNT430, TNT432, TNT433, TNT434, TNT441, TNT442, TNT461, TNT462, TNT463		
TNTGRP-3	ALKY3 NACT, ARU NACT, TNT038, TNT040, TNT043, TNT045, TNT048, TNT049, TNT051, TNT057, TNT086, TNT092, TNT093, TNT145, TNT146, TNT147, TNT152, TNT169, TNT174, TNT180, TNT188, TNT193, TNT198, TNT199, TNT200, TNT201,	30 TAC Chapter 115, Storage of VOCs	Tank capacity is less than 1,000 gallons.

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
	TNT202, TNT203, TNT204, TNT205, TNT206, TNT207, TNT208, TNT209, TNT213, TNT215, TNT216, TNT217, TNT218, TNT219, TNT220, TNT221, TNT222, TNT223, TNT225, TNT226, TNT228, TNT229, TNT230, TNT231, TNT232, TNT233, TNT234, TNT235, TNT236, TNT237, TNT238, TNT239, TNT240, TNT241, TNT242, TNT243, TNT244, TNT245, TNT246, TNT247, TNT248, TNT249, TNT250, TNT251, TNT253, TNT254, TNT255, TNT256, TNT258, TNT259, TNT260, TNT261, TNT262, TNT263, TNT264, TNT265, TNT266, TNT267, TNT268, TNT269, TNT270, TNT271, TNT272, TNT273, TNT274, TNT275, TNT276, TNT277, TNT278, TNT279, TNT280, TNT281, TNT282, TNT283, TNT284, TNT285, TNT286, TNT287, TNT288, TNT289, TNT290, TNT291, TNT292, TNT293, TNT294, TNT295, TNT296, TNT297, TNT298, TNT299, TNT300, TNT301, TNT302,		

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
	TNT303, TNT304, TNT305, TNT306, TNT307, TNT308, TNT309, TNT310, TNT311, TNT312, TNT314, TNT315, TNT316, TNT317, TNT318, TNT319, TNT320, TNT321, TNT322, TNT323, TNT324, TNT325, TNT326, TNT327, TNT328, TNT329, TNT330, TNT331, TNT333, TNT334, TNT335, TNT336, TNT337, TNT338, TNT340, TNT341, TNT342, TNT343, TNT344, TNT345, TNT346, TNT347, TNT348, TNT349, TNT350, TNT351, TNT352, TNT353, TNT354, TNT355, TNT356, TNT357, TNT358, TNT359, TNT360, TNT361, TNT369, TNT370, TNT371, TNT372, TNT373, TNT383, TNT386, TNT387, TNT397, TNT401, TNT404, TNT411, TNT413, TNT414, TNT416, TNT417, TNT418, TNT419, TNT420, TNT421, TNT422, TNT425, TNT426, TNT427, TNT428, TNT429, TNT431, TNT435, TNT437, TNT438, TNT439, TNT440, TNT444, TNT445, TNT446, TNT447, TNT459,		

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
	TNTALKY3, TNTARU, TNTUU3, UU3 NACT		
TNTGRP-3	ALKY3 NACT, ARU NACT, TNT038, TNT040, TNT043, TNT045, TNT048, TNT049, TNT051, TNT057, TNT086, TNT092, TNT093, TNT145, TNT146, TNT147, TNT152, TNT169, TNT174, TNT180, TNT188, TNT193, TNT198, TNT199, TNT200, TNT201, TNT202, TNT203, TNT204, TNT205, TNT206, TNT207, TNT208, TNT209, TNT213, TNT215, TNT216, TNT217, TNT218, TNT219, TNT220, TNT221, TNT222, TNT223, TNT225, TNT226, TNT228, TNT229, TNT230, TNT231, TNT232, TNT233, TNT234, TNT235, TNT236, TNT237, TNT238, TNT239, TNT240, TNT241, TNT242, TNT243, TNT244, TNT245, TNT246, TNT247, TNT248, TNT249, TNT250, TNT251, TNT253, TNT254, TNT255, TNT256, TNT258, TNT259, TNT260, TNT261, TNT262, TNT263, TNT264, TNT265, TNT266,	40 CFR Part 60, Subpart Kb	Tank capacity is less than 75 cubic meters (19,813 gallons).

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
	TNT267, TNT268, TNT269, TNT270, TNT271, TNT272, TNT273, TNT274, TNT275, TNT276, TNT277, TNT278, TNT279, TNT280, TNT281, TNT282, TNT283, TNT284, TNT285, TNT286, TNT287, TNT288, TNT289, TNT290, TNT291, TNT292, TNT293, TNT294, TNT295, TNT296, TNT297, TNT298, TNT299, TNT300, TNT301, TNT302, TNT303, TNT304, TNT305, TNT306, TNT307, TNT308, TNT309, TNT310, TNT311, TNT312, TNT314, TNT315, TNT316, TNT317, TNT318, TNT319, TNT320, TNT321, TNT322, TNT323, TNT324, TNT325, TNT326, TNT327, TNT328, TNT329, TNT330, TNT331, TNT333, TNT334, TNT335, TNT336, TNT337, TNT338, TNT340, TNT341, TNT342, TNT343, TNT344, TNT345, TNT346, TNT347, TNT348, TNT349, TNT350, TNT351, TNT352, TNT353, TNT354, TNT355, TNT356, TNT357, TNT358, TNT359, TNT360, TNT361, TNT369,		

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
	TNT370, TNT371, TNT372, TNT373, TNT383, TNT386, TNT387, TNT397, TNT401, TNT404, TNT411, TNT413, TNT414, TNT416, TNT417, TNT418, TNT419, TNT420, TNT421, TNT422, TNT425, TNT426, TNT427, TNT428, TNT429, TNT431, TNT435, TNT437, TNT438, TNT439, TNT440, TNT444, TNT445, TNT446, TNT447, TNT459, TNTALKY3, TNTARU, TNTUU3, UU3 NACT		
TOTE 9272A	N/A	40 CFR Part 60, Subpart Kb	Tank capacity is less than 75 cubic meters (19,813 gallons).
TOTE 9272B	N/A	30 TAC Chapter 115, Storage of VOCs	Tank capacity is less than 1,000 gallons.
TOTE 9272B	N/A	40 CFR Part 60, Subpart Kb	Tank capacity is less than 75 cubic meters (19,813 gallons).
TO-WWTP	N/A	30 TAC Chapter 111, Incineration	Does not burn municipal, commercial, or industrial solid waste.
TO-WWTP	N/A	30 TAC Chapter 117, Subchapter B	Incinerator less than 40 MMBtu/hr.
ULC-100B	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.
ULC-100B	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
ULC-101B	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.
ULC-101B	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.
ULC-102B	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.
ULC-102B	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.
ULC-103B	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.
ULC-103B	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.
ULC-104BA	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.
ULC-104BA	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.
ULC-104BB	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.
ULC-104BB	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
ULC-105BA	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.
ULC-105BA	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.
ULC-105BB	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.
ULC-105BB	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.
ULCARU-SEP4	N/A	40 CFR Part 60, Subpart QQQ	Group 1 wastewater stream managed in a piece of equipment that is also subject to the provisions of 40 CFR Part 60, subpart QQQ is required to comply only with 40 CFR 63, Subpart CC.
ULC-CTWR	N/A	40 CFR Part 63, Subpart Q	Cooling tower not operated with chromium-based water treatment chemicals on or after 9/8/94.
ULC-SEP7	N/A	40 CFR Part 60, Subpart QQQ	Group 1 wastewater stream managed in a piece of equipment that is also subject to the provisions of 40 CFR Part 60, subpart QQQ is required to comply only with 40 CFR 63, Subpart CC.
UU3-301BA	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.
UU3-301BA	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction,

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
			modification, or reconstruction prior to May 14, 2007.
UU3-301BB	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.
UU3-301BB	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.
UU3-301BC	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.
UU3-301BC	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.
UU3-301BD	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.
UU3-301BD	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.
UU3-302BA	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.
UU3-302BA	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.
UU3-302BB	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.
UU3-302BB	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction,

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
			modification, or reconstruction prior to May 14, 2007.
UU3-302BC	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.
UU3-302BC	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.
UU3-306B	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.
UU3-306B	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.
UU3-307BA	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.
UU3-307BA	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.
UU3-307BB	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.
UU3-307BB	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.
UU3-308B	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.
UU3-308B	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction,

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
			modification, or reconstruction prior to May 14, 2007.
UU3-CT	N/A	40 CFR Part 63, Subpart Q	Cooling tower not operated with chromium-based water treatment chemicals on or after 9/8/94
UU3-SEP12	N/A	40 CFR Part 60, Subpart QQQ	Group 1 wastewater stream managed in a piece of equipment that is also subject to the provisions of 40 CFR Part 60, subpart QQQ is required to comply only with 40 CFR 63, Subpart CC.
UU3W-OWS	N/A	40 CFR Part 60, Subpart QQQ	Group 1 wastewater stream managed in a piece of equipment that is also subject to the provisions of 40 CFR Part 60, subpart QQQ is required to comply only with 40 CFR 63, Subpart CC.
UU4-B401A	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.
UU4-B401A	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.
UU4-B401B	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.
UU4-B401B	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.
UU4-B402A	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator,

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
			furnace, or process heater.
UU4-B402A	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.
UU4-B402B	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.
UU4-B402B	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.
UU4-B402C	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.
UU4-B402C	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.
UU4-B404	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.
UU4-B404	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.
UU4-B405	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.
UU4-B405	N/A	40 CFR Part 60, Subpart Db	Constructed prior to June 19, 1984 and has not been reconstructed or modified after the applicability date.
UU4-B405	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction,

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/Inclusive Units		
			modification, or reconstruction prior to May 14, 2007.
UU4-B406	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a liquid fuel-fired steam generator, furnace, or process heater.
UU4-B406	N/A	40 CFR Part 60, Subpart Ja	Unit which commenced construction, modification, or reconstruction prior to May 14, 2007.
UU4-CTW	N/A	40 CFR Part 63, Subpart Q	Cooling tower not operated with chromium-based water treatment chemicals on or after 9/8/94
UU4-SEP1	N/A	40 CFR Part 60, Subpart QQQ	Group 1 wastewater stream managed in a piece of equipment that is also subject to the provisions of 40 CFR Part 60, subpart QQQ is required to comply only with 40 CFR 63, Subpart CC.
VEH GAS TK	N/A	30 TAC Chapter 115, Storage of VOCs	Located in BPA, DFW, El Paso or HGA and in a motor vehicle fuel dispensing service and has a nominal capacity < 25,000 gallons.
VEH GAS TK	N/A	40 CFR Part 60, Subpart Kb	Tank capacity is less than 75 cubic meters (19,813 gallons).
VEHGASTK	N/A	40 CFR Part 60, Subpart Kb	Tank capacity is less than 75 cubic meters (19,813 gallons).

New Source Review Authorization References

New Source Review Authorization References 839

New Source Review Authorization References by Emission Unit 843

New Source Review Authorization References

The New Source Review authorizations listed in the table below are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Prevention of Significant Deterioration (PSD) Permits	
PSD Permit No.: PSDTX023	Issuance Date: 11/30/2018
PSD Permit No.: PSDTX402M4	Issuance Date: 11/30/2018
PSD Permit No.: GHGPSDTX166	Issuance Date: 11/30/2018
Nonattainment (NA) Permits	
NA Permit No.: N258	Issuance Date: 11/30/2018
Title 30 TAC Chapter 116 Permits, Special Permits, and Other Authorizations (Other Than Permits By Rule, PSD Permits, or NA Permits) for the Application Area.	
Authorization No.: 110345	Issuance Date: 07/03/2013
Authorization No.: 139286	Issuance Date: 04/15/2016
Authorization No.: 139805	Issuance Date: 05/27/2016
Authorization No.: 149517	Issuance Date: 01/19/2018
Authorization No.: 150222	Issuance Date: 02/21/2018
Authorization No.: 1940	Issuance Date: 10/22/2013
Authorization No.: 19599	Issuance Date: 11/30/2018
Authorization No.: 22107	Issuance Date: 03/25/2015
Authorization No.: 2231	Issuance Date: 03/20/2017
Authorization No.: 2315	Issuance Date: 07/13/2006
Authorization No.: 24608	Issuance Date: 03/23/1994
Authorization No.: 2612	Issuance Date: 11/30/2010
Authorization No.: 46052	Issuance Date: 04/25/2017
Authorization No.: 4714	Issuance Date: 07/13/2009
Authorization No.: 47256	Issuance Date: 11/30/2018
Authorization No.: 47696	Issuance Date: 11/15/2010
Authorization No.: 47954	Issuance Date: 12/09/2010
Authorization No.: 47956	Issuance Date: 01/04/2011
Authorization No.: 49771	Issuance Date: 12/12/2012
Authorization No.: 51875	Issuance Date: 10/30/2012
Authorization No.: 6488	Issuance Date: 06/30/2014
Authorization No.: 83422	Issuance Date: 07/25/2017
Authorization No.: 84658	Issuance Date: 04/30/2008
Authorization No.: 86558	Issuance Date: 12/01/2008
Authorization No.: 87463	Issuance Date: 02/19/2009

New Source Review Authorization References

The New Source Review authorizations listed in the table below are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Authorization No.: 94345	Issuance Date: 01/21/2011
Authorization No.: 94424	Issuance Date: 07/26/2013
Authorization No.: 9606	Issuance Date: 10/27/2014
Authorization No.: 97907	Issuance Date: 09/12/2011
Authorization No.: 99917	Issuance Date: 12/07/2011
Permits By Rule (30 TAC Chapter 106) for the Application Area	
Number: 106.122	Version No./Date: 09/04/2000
Number: 106.124	Version No./Date: 09/04/2000
Number: 106.183	Version No./Date: 06/18/1997
Number: 106.227	Version No./Date: 03/14/1997
Number: 106.231	Version No./Date: 09/04/2000
Number: 106.261	Version No./Date: 09/04/2000
Number: 106.261	Version No./Date: 11/01/2003
Number: 106.262	Version No./Date: 09/04/2000
Number: 106.262	Version No./Date: 11/01/2003
Number: 106.263	Version No./Date: 11/01/2001
Number: 106.264	Version No./Date: 09/04/2000
Number: 106.353	Version No./Date: 03/14/1997
Number: 106.355	Version No./Date: 03/14/1997
Number: 106.371	Version No./Date: 03/14/1997
Number: 106.371	Version No./Date: 09/04/2000
Number: 106.373	Version No./Date: 03/14/1997
Number: 106.373	Version No./Date: 07/08/1998
Number: 106.412	Version No./Date: 09/04/2000
Number: 106.432	Version No./Date: 03/14/1997
Number: 106.433	Version No./Date: 03/14/1997
Number: 106.433	Version No./Date: 09/04/2000
Number: 106.451	Version No./Date: 03/14/1997
Number: 106.452	Version No./Date: 03/14/1997
Number: 106.471	Version No./Date: 03/14/1997
Number: 106.472	Version No./Date: 03/14/1997
Number: 106.472	Version No./Date: 09/04/2000

New Source Review Authorization References

The New Source Review authorizations listed in the table below are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Number: 106.473	Version No./Date: 03/14/1997
Number: 106.473	Version No./Date: 09/04/2000
Number: 106.476	Version No./Date: 03/14/1997
Number: 106.476	Version No./Date: 09/04/2000
Number: 106.478	Version No./Date: 03/14/1997
Number: 106.478	Version No./Date: 09/04/2000
Number: 106.511	Version No./Date: 03/14/1997
Number: 106.511	Version No./Date: 09/04/2000
Number: 106.512	Version No./Date: 03/14/1997
Number: 106.512	Version No./Date: 09/04/2000
Number: 106.512	Version No./Date: 06/13/2001
Number: 106.532	Version No./Date: 03/14/1997
Number: 106.533	Version No./Date: 03/14/1997
Number: 5	Version No./Date: 09/12/1989
Number: 5	Version No./Date: 07/20/1992
Number: 5	Version No./Date: 09/13/1993
Number: 5	Version No./Date: 04/05/1995
Number: 5	Version No./Date: 10/04/1995
Number: 5	Version No./Date: 06/07/1996
Number: 6	Version No./Date: 07/20/1992
Number: 6	Version No./Date: 10/04/1995
Number: 7	Version No./Date: 07/20/1992
Number: 7	Version No./Date: 10/04/1995
Number: 8	Version No./Date: 07/20/1992
Number: 8	Version No./Date: 10/04/1995
Number: 21	Version No./Date: 07/20/1992
Number: 21	Version No./Date: 10/04/1995
Number: 31	Version No./Date: 07/20/1992
Number: 31	Version No./Date: 10/04/1995
Number: 39	Version No./Date: 07/20/1992
Number: 39	Version No./Date: 10/04/1995
Number: 50	Version No./Date: 07/20/1992

New Source Review Authorization References

The New Source Review authorizations listed in the table below are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Number: 50	Version No./Date: 10/04/1995
Number: 51	Version No./Date: 11/05/1986
Number: 51	Version No./Date: 07/20/1992
Number: 51	Version No./Date: 10/04/1995
Number: 53	Version No./Date: 07/20/1992
Number: 53	Version No./Date: 10/04/1995
Number: 61	Version No./Date: 09/12/1989
Number: 61	Version No./Date: 07/20/1992
Number: 61	Version No./Date: 05/04/1994
Number: 61	Version No./Date: 10/04/1995
Number: 67	Version No./Date: 07/20/1992
Number: 67	Version No./Date: 10/04/1995
Number: 68	Version No./Date: 07/20/1992
Number: 68	Version No./Date: 10/04/1995
Number: 69	Version No./Date: 04/04/1975
Number: 75	Version No./Date: 07/20/1992
Number: 75	Version No./Date: 10/04/1995
Number: 80	Version No./Date: 07/20/1992
Number: 80	Version No./Date: 10/04/1995
Number: 86	Version No./Date: 09/12/1989
Number: 88	Version No./Date: 07/20/1992
Number: 88	Version No./Date: 10/04/1995
Number: 100	Version No./Date: 07/20/1992
Number: 100	Version No./Date: 10/04/1995
Number: 102	Version No./Date: 07/20/1992
Number: 102	Version No./Date: 10/04/1995
Number: 103	Version No./Date: 07/20/1992
Number: 103	Version No./Date: 10/04/1995
Number: 107	Version No./Date: 05/04/1994

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
280-40116	TANK 4011 (EPN 280-4011)	47256, N258, PSDTX402M4
280-4016	TANK 4016 (EPN 280-4016)	47256, N258, PSDTX402M4
ALK2-CTWR	ALKY2 COOLING TOWER (EPN 411)	47256, 106.371/09/04/2000, N258, PSDTX402M4
ALK3 C1001	ALKY3 DISTILLATION COLUMN	9606
ALK3 C1003	ALKY3 DISTILLATION COLUMN	9606
ALK3 C1004	ALKY3 DISTILLATION COLUMN	9606
ALK3 C1005	ALKY3 DISTILLATION COLUMN	9606
ALK3 C1006	ALKY3 DISTILLATION COLUMN	9606
ALK3-CTWR	ALKY3 COOLING TOWER (EPN 428)	9606
ALK3DEBCT	ALKY3 DEBUT COOLING TOWER (EPN 523)	9606
ALK3-F1001	ISO STRIPPER REBOILER (EPN 521)	9606
ALKY2 C101	ALKY2 DISTILLATION COLUMN	47256, N258, PSDTX402M4
ALKY2 C102	ALKY2 DISTILLATION COLUMN	47256, N258, PSDTX402M4
ALKY2 C-601	ALKY2 DISTILLATION COLUMN	47256, N258, PSDTX402M4
ALKY2 C-602	ALKY2 DISTILLATION COLUMN	47256, N258, PSDTX402M4
ALKY2 C-902	DEISOBUTANIZER	47256, N258, PSDTX402M4
ALKY2-FUG	ALKYLATION UNIT NO. 2 FUGITIVES (EPN F-489, F-489-RAH)	47256, 9606, 106.261[139885, 144839]/11/01/2003 N258, PSDTX402M4
ALKY3-FUG	ALKYLATION UNIT NO. 3 FUGITIVES (EPN F-520)	9606, 106.261[139885, 147521,146224, 151214, 151368]/11/01/2003, 106.262[147521]/11/01/2003
ALKY3 NACT	ALKY 3 NACE TOTE (EPN ALKY3NT)	47256, N258, PSDTX402M4

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
ALKY3V1005	ALKY3 REACTOR	9606
API3CD-SEP	API SEPARATOR 3D	106.532[116275]/03/14/1997
API-SEP1	API OIL-WATER SEPARATOR	139805
API-SEP2	API OIL-WATER SEPARATOR	139805
ARU NACT	ARU NACE TOTE (EPN ARUNT)	47256, N258, PSDTX402M4
ARU 610-E	ARU DISTILLATION COLUMN	2231
ARU 611-E	ARU DISTILLATION UNIT	2231
ARU 612-E	ARU DISTILLATION COLUMN	2231
ARU 612-EB	ARU DISTILLATION COLUMN	2231
ARU-619FA	ARU FLARE KNOCK-OUT POT	2231
ARU-FUG1	ARU FUGITIVES (EPN F-180A)	2231, 106.261[139759, 144843, 146174, 151196]/11/01/2003
ARU-SEP	ARU OIL-WATER SEPARATOR (EPN-441)	2231
AU2 D-601	AU2 REACTOR	2612
AU2 E-610	AU2 DISTILLATION COLUMN	2612
AU2 E-620	AU2 DISTILLATION COLUMN	2612
AU2 E-630	AU2 DISTILLATION COLUMN	2612
AU2 E-640	AU2 DISTILLATION COLUMN	2612
AU2-B601	REACTOR PREHEAT FURNACE (EPN 601)	2612, 106.261[92273, 92585, 75507, 103075]/11/01/2003
AU2-B621A	B-3 HEATER (EPN 171)	2612

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
AU2-B621B	B-1 HEATER (EPN 173)	2612
AU2-CTWR	AU2 COOLING TOWER (EPN 420)	2612
AU2-FUG	AU2 FUGITIVES (EPN F-170)	2612, 106.261[151205, 139780]/11/01/2003
AU2-SEP	AU2 OIL-WATER SEPARATOR (EPN 455)	2612
BALLAS-BAS	SURFACE IMPOUNDMENT	69/04/04/1975
BOOTH 1	PAINT BOOTH (EPN BOOTH1)	22107, 106.433[105480]/09/04/2000
CAT1-SEP19	CAT1 OIL-WATER SEPARATOR (EPN E-03)	47256, N258, PSDTX402M4
CAT3-SEP21	CAT3 OIL-WATER SEPARATOR #1 (EPN E-06)	47256, N258, PSDTX402M4
CAT3-SEP22	CAT3 OIL-WATER SEPARATOR #2 (EPN E-13)	47256, N258, PSDTX402M4
CFHU101/2B	CFHU-101/2B COMMON VENT	47256, N258, PSDTX402M4
CFHU-101B	HEATER CFHU-101B (EPN 471)	47256, N258, PSDTX402M4
CFHU-102B	HEATER CFHU-102B (EPN 471)	47256, N258, PSDTX402M4
CFHU-CTWR	COOLING TOWER - RHU/CFHU (EPN 426)	47256, N258, PSDTX402M4
CFHU-FUG1	CFHU FUGITIVES (EPN F-470-RAH)	47256, N258, PSDTX402M4
CFHU-SEP	CFHU OIL-WATER SEPARATOR (EPN E-35)	47256, N258, PSDTX402M4
CKR-BDS	COKER COOLDOWN STACK (EPN CKR-BDS)	106.261[56657]/11/01/2003
COKERAE101	COCER A DISTILLATION COLUMN	2315
COKERAE403	COKER A DISTILLATION COLUMN	2315
COKERBE201	COKER B DISTILLATION COLUMN	2315
COKERBE403	COKER B DISTILLATION COLUMN	2315
COKERCE301	COKER C DISTILLATION COLUMN	2315

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
COKERCE403	COKER C DISTILLATION COLUMN	2315
COKERLOAD	COKER TRUCK LOAD	2315
COKR-B101	COKER COMPLEX (EPN 71)	2315, 106.261[87993, 101884, 131516, 131519, 131527]/11/01/2003
COKR-B201	COKER FURNACES (EPN 72)	2315, 83422, 106.261[87993, 101884, 131516, 131519, 131527, 99544]/11/01/2003
COKR-B203	HEATER B-203 (EPN 77)	6592, 106.261[87993, 101884, 131516, 131519, 131527, 99544]/11/01/2003
COKR-B301	HEATER B-301 (EPN 74)	2315, 87463, [87993, 101884, 131516, 1, 106.261/11/01/2003
COKR-B302	COKER FEED PREHEATER (EPN 78, HEATERCAP)	47256, N258, PSDTX402M4, 106.261[87993]/11/01/2003
COKR-CTWR	COKER COOLING TOWER (EPN 412)	47256, N258, PSDTX402M4
COKR-FUG1	COKR FUGITIVES (EPN 445, EPN F-70-RAH)	47256, N258, PSDTX402M4, 106.261[146162]/11/01/2003
COKR-SEP	COKR OIL-WATER SEPARATOR (EPN 445)	47256, N258, PSDTX402M4
D2A	TANK STORAGE (EPN D2A)	106.476/09/04/2000
D2R	TANK STORAGE (EPN D2R)	106.476/09/04/2000
D3A	TANK STORAGE (EPN D3A)	106.476/09/04/2000
D3R	TANK STORAGE (EPN D3R)	106.476/09/04/2000
D4A	TANK STORAGE (EPN D4A)	106.476/09/04/2000
D4R	TANK STORAGE (EPN D4R)	106.476/09/04/2000
D5A	TANK STORAGE (EPN D5A)	106.476/09/04/2000

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
D5R	TANK STORAGE (EPN D5R)	106.476/09/04/2000
D6A	TANK STORAGE (EPN D6A)	106.476/09/04/2000
D7R	TANK STORAGE (EPN D7R)	106.476/09/04/2000
DDU-101/2B	DDU-101B/2B COMMON VENT (EPN 391)	47256, N258, PSDTX402M4, 106.261[5471]/09/04/2000
DDU-101B	HEATER DDU-101B (EPN 391)	47256, N258, PSDTX402M4, 106.261[5471]/09/04/2000
DDU-102B	HEATER DDU-102B (EPN 391, HEATERPM)	47256, N258, PSDTX402M4, 106.261[5471]/09/04/2000
DDU-201/2B	DDU201-2B COMMON VENT (EPN 392)	47256, N258, PSDTX402M4, 106.261[5471]/09/04/2000
DDU-201B	HEATER DDU-201B (EPN 392)	47256, N258, PSDTX402M4, 106.261[5471]/09/04/2000
DDU-202B	HEATER DDU-202B (EPN 392, HEATERPM)	47256, N258, PSDTX402M4, 106.261[5471]/09/04/2000
DDU-315A	DDU FLARE KNOCK-OUT POT	47256, N258, PSDTX402M4
DDU-B301	B301 HEATER (EPN 394)	47256, N258, PSDTX402M4
DDU-B302	B302 REBOILER (EPN 394)	47256, N258, PSDTX402M4
DDU-FUG	DISTILLATE DESULPHURIZATION UNIT FUGITIVES (EPN F-390, EPN F-393, EPN F-390-RAH, EPN F-393-RAH)	47256, N258, PSDTX402M4, 106.261[146159, 151206]11/01/2003
DDU-SEP	DDU OIL-WATER SEPARATOR	47256, N258, PSDTX402M4
DEGREASE08	WAREHOUSE TOOL ROOM	107/05/04/1994
DHT 851-D	DHT REACTOR 1	47256, N258, PSDTX402M4

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
DHT 852-D	DHT REACTOR 2	47256, N258, PSDTX402M4
DHT-101B	DHT PROCESS HEATER 101B	47256, N258, PSDTX402M4, GHGPSDTX166
DHT-201B	DHT PROCESS HEATER 201B	47256, N258, PSDTX402M4, GHGPSDTX166
DHT-FUG1	DHT FUGITIVES (EPN F-DHT)	47256, N258, PSDTX402M4, GHGPSDTX166
DKTO294-1	DOCKS THERMAL OXIDIZER (EPN F-705, CONTMARINE)	47256, N258, PSDTX402M4
DKTO294-2	DOCKS THERMAL OXIDIZER (EPN F-708, CONTMARINE)	47256, N258, PSDTX402M4
DKTO294-3	DOCKS THERMAL OXIDIZER (EPN F-711, CONTMARINE)	47256, N258, PSDTX402M4
DOCK32	DOCK 32 VENTING TO 294-1,2,3 (EPN 299-32, MARINE1)	47256, N258, PSDTX402M4, 106.478[114957]/09/04/2000
DOCK33	DOCK 33 VENTING TO 294-1,2,4 (EPN 299-32, MARINE1)	47256, N258, PSDTX402M4, 106.478[114957]/09/04/2000
DOCK34	DOCK 34 VENTING TO 294-1,2,5 (EPN 299-32, MARINE1)	47256, N258, PSDTX402M4, 106.478[114957]/09/04/2000
DOCK37	DOCK 37 VENTING TO 294-1,2,6 (EPN 299-32, MARINE)	47256, N258, PSDTX402M4, 106.478[114957]/09/04/2000
DOCK38	DOCK 38 VENTING TO 294-1,2,7 (EPN 299-32, MARINE1)	47256, N258, PSDTX402M4, 106.478[114957]/09/04/2000
DOCK40-41	MARINE DOCKS UNCONTROLLED LOADING (EPN 299-40,41)	47256, N258, PSDTX402M4
DOCK54LOAD	LOADING TOLUENE (EPN 397)	2231
EMERGEN	FIRE HOUSE GENERATOR	106.511/09/04/2000
ENVFC-FUG1	ENVIRONMENTAL FACILITY FUGITIVES (EPN E-69)	22107, 106.261[146177,151213]/11/01/2003
ENVFP-SEP	ENVFP OIL-WATER SEPARATOR (EPN E-69)	47256, N258, PSDTX402M4

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
EPN-34A	FCCU3 REGENERATOR STACK (EPN -34A)	47256, N258, PSDTX402M4
EPN-93	FCCU 1 REGENERATOR STACK (EPN -93)	47256, 99917, N258, PSDTX402M4
EPN-REFWWV	WWTP CAT OXIDIZER FOR LS21 (EPN REF-WWVOX,WWWV)	22107
ESBGEN	ESB BUILDING EMERGENCY GENERATOR	106.511/09/04/2000
F-29	TANK STORAGE	106.472/09/04/2000
F-501	TOLAD 3920 - KEROSENE CORROSION INHIBITOR TANK	106.262[101884]/11/01/2003, 106.478[97043]/09/04/2000
F-502	TOLAD 3514 - ANTI-STATIC ADDITIVE TANK	106.262[101884]/11/01/2003, 106.478[97043]/09/04/2000
F-603	DAF SLUDGE TANK (EPN E-53/56)	22107
F-604	DAF SLUDGE TANK (EPN E-53/56)	22107
F-605	DAF SLUDGE TANK (EPN E-53/56)	22107
F-606	DAF SLUDGE TANK (EPN E-53/56)	22107
F607/T-30	F607/T30 SHAKER TANK	22107
F607/T-31	F607/T-31 FEED TANK	22107
F607/T-32	F607/T-32	22107
FCCU1 D-1	FCCU1 REACTOR	47256, N258, PSDTX402M4
FCCU3 401-D	FCCU3 REACTOR	47256, N258, PSDTX402M4
FCCU3 401-E	FCCU3 DISTILLATION COLUMN	47256, N258, PSDTX402M4
FCCU3 405-E	FCCU3 DISTILLATION COLUMN	47256, N258, PSDTX402M4
FCCU3 407-E	FCCU3 DISTILLATION COLUMN	47256, N258, PSDTX402M4

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
FCCU3 505-E	FCCU3 DISTILLATION COLUMN	47256, N258, PSDTX402M4
FCCU3 506-E	FCCU3 DISTILLATION COLUMN	47256, N258, PSDTX402M4
FCU1-CTWR	FCU1 COOLING TOWER (EPN 413)	47256, N258, PSDTX402M4
FCU3-CTWR	FCU3 COOLING TOWER (EPN 415)	47256, N258, PSDTX402M4
FCU3	FCU3 (EPN 34A)	47256, N258, PSDTX402M4
GASLOAD	MOTOR VEHICLE FUEL DISPENSING	47256, N258, PSDTX402M4
HRU-FUG1	HRU FUGITIVES (EPN F-486)	47256, N258, PSDTX402M4
HRU-FUG	HYDROGEN RECOVERY UNIT FUGITIVES (EPN F-486)	47256, N258, PSDTX402M4
HRU-OWS	HRU OIL-WATER SEPARATOR (EPN 860H)	47256, N258, PSDTX402M4
J803PUMP	J-803 TEMPORARY PUMP	106.512/06/13/2001
J804PUMP	POWER 2, J-804 PUMP	106.512/06/13/2001
LAB-CTWR1	LAB COOLING TOWER NO. 1	106.371/09/04/2000
LAB-CTWR2	LAB COOLING TOWER NO. 2	106.371/09/04/2000
LAB-DWS	LABORATORY OIL-WATER SEPARATOR DWS (EPN E-68)	47256, N258, PSDTX402M4
LAMPUMP	LAMELLA PUMP	106.512/06/13/2001
NDU1	FEED HEATER #1 - 71 MMBTU/HR (EPN 80)	46052
NDU2-B201	NDU2-B201 HDS REACTOR (EPN 81)	46052
NDU2-B202	NDU2-B202 HDS REACTOR (EPN 82)	46052
NDU2-FUG1	NDU2 FUGITIVES (EPN F-NDU2)	46052
NDU-CTWR	NDU COOLING TOWER (EPN 419)	47256, N258, PSDTX402M4
NDU-FUG	NAPHTHA DESULPHURIZATION UNIT FUGITIVES (EPN F-84)	46052, 106.261[146170]/11/01/2003

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
NDU-OWS	NDU OIL-WATER SEPARATOR (EPN F-514)	46052
OILUNLOAD	SITEWIDE UNLOADING OF SEAL OIL/LUBE OIL/ & DIESEL	106.472/09/04/2000
OVERFLOW-1	SURFACE IMPOUNDMENT	069/04/04/1975
P-617	FIRE WATER PUMP	106.511/09/04/2000
P-618	FIRE WATER PUMP	106.511/09/04/2000
P-J16A	DOCKS FIRE WATER PUMP P-J16A	106.511/09/04/2000
P-J16B	DOCKS FIRE WATER PUMP P-J16B	106.511/09/04/2000
P-J35A	DOCKS FIRE WATER PUMP P-J35A	106.511/09/04/2000
P-J35B	DOCKS FIRE WATER PUMP P-J35B	106.511/09/04/2000
P-J53A	DOCKS FIRE WATER PUMP P-J53A	106.511/09/04/2000
P-J53B	DOCKS FIRE WATER PUMP P-J53B	106.511/09/04/2000
P-J615	FIRE WATER PUMP	106.511/09/04/2000
P-J616	FIRE WATER PUMP	106.511/09/04/2000
P-J682	FIRE WATER PUMP	106.511/09/04/2000
PRESSURE1	PRESSURE 1 (EPN PRESSURE1)	106.512/06/13/2001
PRESSURE2	PRESSURE 2 (EPN PRESSURE2)	106.512/06/13/2001
PRO-AU2	AROMATICS UNIT #2	2612
PRO-BIOTRT	BIOLOGICAL TREATMENT	22107, 47256, N258, PSDTX402M4
PRO-SRU	SULFUR RECOVERY UNIT	47256, N258, PSDTX402M4
PRO-WWTP	WASTEWATER TREATMENT PLANT	22107
PRS3-CTWR	POWER STATION 3 (ANNEX) COOLING TOWER (EPN 416)	47256, N258, PSDTX402M4

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
PS2-FUG	PS2 FUGITIVES (EPN F-120)	47256, N258, PSDTX402M4, 106.261[146159, 151206]/11/01/2003
PS3A 201-E	PS3A DISTILLATION COLUMN	19599, PSDTX023
PS3A 202-E	PS3A DISTILLATION COLUMN	19599, PSDTX023
PS3A 204-F	PS3A DISTILLATION COLUMN	19599, PSDTX023
PS3A 376-F	PS3A DISTILLATION COLUMN	19599, PSDTX023
PS3A101BAB	PS3A-101BA/BB COMMON VENT (EPN 51)	19599, PSDTX023
PS3A-101BA	PIPESTILL 3-A (EPN 51)	19599, PSDTX023
PS3A-101BB	HEATER PS3A-101BB (EPN 51)	19599, PSDTX023
PS3A102BAB	PS3A-102BA/BB COMMON VENT (EPN 53)	19599, PSDTX023
PS3A-102BA	PIPESTILL 3-A (EPN 53)	19599, PSDTX023
PS3A-102BB	HEAT, STEAM AND POWER (EPN 53)	19599, PSDTX023
PS3A-103B	PIPESTILL 3A (EPN 55)	19599, PSDTX023
PS3A-205F	PS3A FLARE KNOCK-OUT POT	19599, PSDTX023
PS3A-FUG1	PS3A FUGITIVES (EPN-50, EPN F-50-RAH)	19599, 106.261[139775,146310, 151210]/11/01/2003, PSDTX023
PS3A-OWS	PS3A OIL-WATER SEPARATOR (EPN 56)	19599, PSDTX023
PS3B 501-E	PS3B DISTILLATION COLUMN	19599, PSDTX023
PS3B 502-E	PS3B DISTILLATION COLUMN	19599, PSDTX023
PS3B 503-E	PS3B DISTILLATION COLUMN	19599, PSDTX023
PS3B 504-E	NAPTHA SPLITTER	47256, N258, PSDTX402M4

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
PS3B-401BA	PIPESTILL NO. 3B (EPN 41)	19599, 49771, PSDTX023
PS3B-401BB	PS3B 401B CRUDE HEATER (EPN 42)	19599, 49771, PSDTX023
PS3B-401BC	PIPESTILL 3B CRUDE HEATER (EPN 44)	19599, PSDTX023
PS3B-402BE	402-BE (EPN 43A)	19599, 49771, PSDTX023
PS3B402BFG	PS3B-402BF/BG COMMON VENT (EPN 43A)	19599, 49771, PSDTX023
PS3B-402BF	PIPESTILL 3B HEATER (EPN 43A)	19599, 49771, PSDTX023
PS3B-402BG	PIPESTILL 3B HEATER (EPN 43A)	19599, 49771, PSDTX023
PS3B-515F	PS3B KNOCK-OUT POT	19599, PSDTX023
PS3B-516F	PS3B KNOCK-OUT POT	19599, PSDTX023
PS3B-F510	F-510 DRUM IN PS3B	19599, PSDTX023
PS3B-FUG1	PIPESTILL 3B FUGITIVES 1 (EPN-40, EPN F-40-RAH)	19599, 106.261[139775,145255, 146310, 151210]/11/01/2003, PSDTX023
PS3B-SEP1	PS3B OIL-WATER SEPARATOR #1/PS3B-SEP24 (EPN E-46)	19599, PSDTX023
PS3B-SEP2	PS3B OIL-WATER SEPARATOR #2/PS3B-SEP25 (EPN E-47)	19599, PSDTX023
PS3-CTWR	PS3A/B COOLING TOWER (EPN 417)	19599, 106.371/09/04/2000, PSDTX023
RDU-601B	VRS HOT OIL HEATER (EPN 550, HEATERCAP)	47256, 84658, N258, PSDTX402M4
RDU-FUG1	RESID DEASPHALTING UNIT FUGITIVES 1 (EPN 551)	47256, N258, PSDTX402M4
RDU-FUG	RESID DEASPHALTING UNIT FUGITIVES (EPN 551)	47256, N258, PSDTX402M4, 106.261[146159, 151206, 139863]/11/01/2003
RDU-SEP	RDU OIL-WATER SEPARATOR (EPN E-34)	47256, N258, PSDTX402M4
REFDOCKFUG	MAIN DOCK FUGITIVES (EPN F-294)	47256, 106.261[146913, 146161]/11/01/2003, 106.262[146161,151206, 139863]/11/01/2003

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
		N258, PSDTX402M4
REF-FUG	PLANT WIDE REFINERY FUGITIVES (EPNs F-30, F-90, F-160, F-200, F-280, F-270, F-390, F-393, F-470, F-480, F-486, F-390-RAH, F-393-RAH, F-DHT, F-480-RAH, F-70-RAH, F-40-RAH, F-489-RAH, F-50-RAH, F-380-RAH, F-470-RAH, F-280-RAH, F-380-RAH)	19599, 22107, 2315, 2612, 46052, 4714, 47256, 6488, 6592, 83422, 84658, 94345, 9606, 106.261[54721]/09/04/2000, 106.261[82308, 81516, 83941, 84396, 84567, 85681, 92585, 92587, 92586, 92671, 92953, 92956, 95036, 95591, 96506, 97071, 98466, 98040, 98703, 98718, 98719, 98820, 98995, 99250, 101201, 101323, 107552, 108602, 109388, 106661, 113463, 114330, 11457, 115881, 115895, 116240, 116273, 117317, 117331, 118077, 118087, 118213, 118764, 118768, 118771, 118787, 118792, 118838, 12373, 120375, 120621, 121515, 131543, 131545, 122217, 123536, 129712, 13121, 131546, 131659, 134145, 239738, 136511, 13757, 137937, 134793, 144847,145795, 146161, 146159, 151206, 151201, 139863, 151368, 140017]/11/01/2003, 106.262[83432, 83941, 85681, 84396, 84454, 87193, 87296, 87825, 88697, 92585, 92587, 92586, 92671, 92953, 95036, 92956, 95591, 96506, 97071, 98466, 98040, 98703, 98718, 98719, 98820, 99901, 98995, 99250, 100681, 101201, 101323, 102758, 104842, 107175, 104842, 107175, 107552, 108602, 108594, 107735, 108971, 109388, 109502, 110915, 113394, 114330, 114957, 116273, 117025, 117317, 117331, 118077, 118087, 118213, 118764, 118789, 118838, 119654, 120373, 120375, 120621, 122217, 124015, 124139, 129712, 13121, 131543, 136511, 13757, 137937, 134793]/11/01/2003, PSDTX023, N258, PSDTX402M4

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
RHU 603-E	RHU DISTILLATION COLUMN	47256, N258, PSDTX402M4
RHU 604-E	RHU DISTILLATION COLUMN	47256, N258, PSDTX402M4
RHU 605-E	RHU DISTILLATION COLUMN	47256, N258, PSDTX402M4
RHU201B/2B	RHU-201B/2B COMMON VENT (EPN 481)	47256, N258, PSDTX402M4
RHU-201B	RHU HEATERS TRAIN “200” (EPN 481)	47256, N258, PSDTX402M4
RHU-202B	RHU HEATERS TRAIN “200” (EPN 481)	47256, N258, PSDTX402M4
RHU301B/2B	RHU-301B/2B COMMON VENT (EPN 482)	47256, N258, PSDTX402M4
RHU-301B	RHU HEATERS TRAIN “300”	47256, N258, PSDTX402M4
RHU-301B	RHU HEATERS TRAIN “300” (EPN 482)	47256, N258, PSDTX402M4
RHU-302B	RHU HEATERS TRAIN “300” (EPN 482)	47256, N258, PSDTX402M4
RHU401B/2B	RHU-401B/2B COMMON VENT (EPN 483)	47256, N258, PSDTX402M4
RHU-401B	RHU HEATERS TRAIN “400” (EPN 483)	47256, N258, PSDTX402M4
RHU-402B	RHU HEATERS TRAIN “400” (EPN 483)	47256, N258, PSDTX402M4
RHU501B/2B	RHU-501B/2B COMMON VENT (EPN 484)	47256, 84658, N258, PSDTX402M4
RHU-501B	ATMOSPHERIC TOWER HEATER (EPN 484, HEATERCAP)	47256, N258, PSDTX402M4
RHU-502B	VACUUM TOWER HEATER (EPN 482, HEATERCAP)	84658
RHU-601B	VRS HOT OIL HEATER (EPN 485, HEATERCAP)	84658
RHUCP-FUG1	RHU FUGITIVES (EPN F-480-RAH)	47256, N258, PSDTX402M4
RHU-FUG	RESID HYDROTREATING UNIT FUGITIVES (EPN F-480)	47256, N258, PSDTX402M4, 106.261[146159, 151206, 139863]/11/01/2003
RHU-SEP1	RHU OIL-WATER SEPARATOR #1/RHU-SEP28 (EPN E-48)	47256, N258, PSDTX402M4

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
RHU-SEP2	RHU OIL-WATER SEPARATOR #2/RHU-SEP29 (EPN E-63)	47256, N258, PSDTX402M4
RHU-T1012	RESID HYDROTREATER (EPN 480-1012)	47256, N258, PSDTX402M4
RHU-T1013	HOT RESID TANK (EPN 480-1013)	47256, N258, PSDTX402M4
SHOCK-BAS	SURFACE IMPOUNDMENT	069/04/04/1975
SHU3-B301	SHU3-B301 SPLITTER REBOILER HEATER (EPN 83)	46052
SHU3-FUG1	SHU3 FUGITIVES (EPN F-SHU3)	46052
SRU12LOAD	SRU RAIL CAR LOADING	47256, N258, PSDTX402M4
SRU1LOAD	SRU TRUCK LOADING	47256, N258, PSDTX402M4
SRU-CT	SRU COOLING TOWER #2	47256, N258, PSDTX402M4
SRU-F8CD	SRU INCINERATOR C AND D COMMON VENT (EPN 384)	47256, 106.264[86677]/09/04/2000, N258, PSDTX402M4
SRU-F8C	SRU INCINERATOR C (EPN 384)	47256, 106.264/09/04/2000, N258, PSDTX402M4
SRU-F8D	SRU INCINERATOR D (EPN 384)	47256, 106.264/09/04/2000, N258, PSDTX402M4
SURGE-1	SURFACE IMPOUNDMENT	069/04/04/1975
SURGE-2	SURFACE IMPOUNDMENT	069/04/04/1975
SURGE-3	SURFACE IMPOUNDMENT	069/04/04/1975
T1003	FLUORIDE PRECIPITATOR (SPENT CAUSTIC)	106.472/09/04/2000
T1046PUMP	TANK 1046, 75 HP	106.512/06/13/2001
T1053APUMP	TANK 1053A, 75 HP	106.512/06/13/2001
T280-1004	TANK STORAGE (EPN 280-1004)	47256, 106.478[141185]/08/09/2000, N258, PSDTX402M4

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
T280-1005	TANK 280-1005	47256, N258, PSDTX402M4
T280-100	TANK 100 - SRU SOUR WATER TANK	47256, N258, PSDTX402M4
T280-1010	COOLING WATER	106.472/09/04/2000
T280-1018	TANK STORAGE (EPN 280-1018)	47256, 106.472/09/04/2000, N258, PSDTX402M4
T280-101	TANK STORAGE (EPN 280-101)	2231
T280-1020	TANK STORAGE (EPN 280-1020)	47256, N258, PSDTX402M4
T280-1021	TANK STORAGE (EPN 280-1021)	47256, N258, PSDTX402M4
T280-1023	TANK STORAGE (EPN 280-1023)	47256, N258, PSDTX402M4
T280-1024	TANK STORAGE (EPN 280-1024)	47256, N258, PSDTX402M4
T280-1025	TANK STORAGE (EPN 280-1025)	47256, N258, PSDTX402M4
T280-102	TANK STORAGE (EPN 280-102)	2231, 106.262[100703]/11/01/2003
T280-1039	TANK STORAGE (EPN 280-1039)	47256, N258, PSDTX402M4
T280-103	TANK STORAGE (EPN 280-103, TANKCAP)	47256, N258, PSDTX402M4
T280-1041	STORAGE TK 1041 (EPN 280-1041)	2231
T280-1042	STORAGE TK 1042 (EPN 280-1042)	2231, 106.478[97519]/09/04/2000
T280-1044	TANK STORAGE (EPN 280-1044)	2231, 106.478/09/04/2000
T280-1045	TANK STORAGE (EPN 280-1045)	47256, 106.261/11/01/2003, N258, PSDTX402M4
T280-1046	TANK STORAGE (EPN 280-1046)	47256, N258, PSDTX402M4
T280-1047	CRUDE NAPHTHA CHARGE TANK (EPN 280-1047)	47256, N258, PSDTX402M4
T280-1048	TANK STORAGE (EPN 280-1048)	47256, N258, PSDTX402M4
T280-104	TANK STORAGE (EPN 280-104, TANKCAP)	47256, 106.478[97548]/09/04/2000, N258,

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
		PSDTX402M4
T280-1051	CRUDE OIL STORAGE TANK (EPN 280-1051)	47256, N258, PSDTX402M4
T280-1052	TANK STORAGE (EPN 280-1052)	4714, 106.478[101487]/09/04/2000
T280-1053	TANK STORAGE (EPN 280-1053)	4714
T280-1054	STORMWATER TANK (EPN 280-1054)	22107, 106.478/03/14/1997
T280-1055	TANK STORAGE (EPN 280-1055)	47256, 106.478[130379]/09/04/2000, N258, PSDTX402M4
T280-1056	STORMWATER TANK (EPN 280-1056)	22107
T280-1057	STORM WATER TANK (EPN 280-1057)	22107
T280-1058	STORMWATER STORAGE TANK	139805
T280-105	TANK STORAGE (EPN 280-105)	47256, N258, PSDTX402M4
T280-106	TANK STORAGE (EPN 280-106)	47256, 106.478/09/04/2000, N258, PSDTX402M4
T280-107	TANK STORAGE (EPN 280-107)	2231
T280-108	TANK STORAGE (EPN 280-108)	2231
T280-10	TANK STORAGE	2231
T280-110	TANK STORAGE (EPN 280-110)	47256, 106.261[146161]/11/01/2003, N258, PSDTX402M4
T280-112	TANK STORAGE (EPN 280-112)	2231
T280-114	TANK STORAGE (EPN 280-114)	2231, 51875
T280-115	TANK STORAGE (EPN 280-115)	2231
T280-116	TANK STORAGE (EPN 280-116)	2231

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
T280-117	TANK STORAGE (EPN 280-117)	47256, N258, PSDTX402M4
T280-118	TANK STORAGE (EPN 280-118)	47256, N258, PSDTX402M4
T280-11	TANK STORAGE (EPN 280-11)	47256, 106.478/09/04/2000, N258, PSDTX402M4
T280-12A	TANK 12A	47256, N258, PSDTX402M4
T280-128	TANK STORAGE (EPN 280-128)	47256, 106.478[13510]/09/04/2000, N258, PSDTX402M4
T280-129	TANK 129 (EPN 280-129)	47256, 106.478[114767]/09/04/2000, N258, PSDTX402M4
T280-130	TANK 130 (EPN 280-130)	47256, N258, PSDTX402M4
T280-132	TANK 132 (EPN 280-132)	106.476/09/04/2000
T280-133	TANK 133 (EPN 280-133)	106.476/09/04/2000
T280-134	TANK 134 (EPN 280-134)	106.476/09/04/2000
T280-135	TANK STORAGE (EPN 280-135)	106.476/03/14/1997
T280-136	TANK STORAGE (EPN 280-136)	106.476/03/14/1997
T280-137	TANK STORAGE (EPN 280-137)	106.476/03/14/1997
T280-138	TANK STORAGE (EPN 280-138)	106.476/03/14/1997
T280-13	TANK STORAGE (EPN 280-13)	47256, N258, PSDTX402M4
T280-140	TANK STORAGE (EPN 280-140)	47256, N258, PSDTX402M4
T280-14	TANK STORAGE (EPN 280-14)	47256, N258, PSDTX402M4
T280-15	TANK STORAGE (EPN 280-15)	106.478[136200]/09/04/2000
T280-160	UNFILTERED SOUR WATER (EPN 280-160)	106.476/09/04/2000

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
T280-161	OIL SKIMMER TANK (EPN 280-161)	106.476/09/04/2000
T280-16A	STORAGE TANK	106.264[144879]/09/04/2000
T280-17	TANK STORAGE (EPN 280-17)	47256, N258, PSDTX402M4
T280-181	TANK STORAGE (EPN 280-181)	47256, 106.261[134247], N258, PSDTX402M4
T280-184	TANK STORAGE (EPN 280-184)	2231
T280-187	TANK STORAGE (EPN 280-187)	2231
T280-188	TANK STORAGE (EPN 280-188)	2231
T280-18	TANK STORAGE (EPN 280-18)	47256, N258, PSDTX402M4
T280-19	TANK STORAGE (EPN 280-19)	2231
T280-20	TANK STORAGE (EPN 280-20)	2231
T280-222	OIL SKIMMER TANK (EPN 280-222)	106.476/09/04/2000
T280-223	OIL SKIMMER TANK (EPN 280-223)	106.476/09/04/2000
T280-22	TANK STORAGE (EPN 280-22)	47256, N258, PSDTX402M4
T280-23	TANK STORAGE (EPN 280-23)	47256, 106.478[93697]/09/04/2000, N258, PSDTX402M4
T280-24	TANK STORAGE (EPN 280-24)	47256, N258, PSDTX402M4
T280-25	TANK STORAGE (EPN 280-25)	47256, 106.478[98134]/09/04/2000, N258, PSDTX402M4
T280-269	DOCKS SLOP TANK 269 (EPN 280-269)	47256, N258, PSDTX402M4
T280-26	TANK STORAGE (EPN 280-26)	47256, N258, PSDTX402M4
T280-270	TANK 270 (EPN 280-270)	47256, 106.478/09/04/2000, N258, PSDTX402M4

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
T280-271	DIESEL (EPN 280-271)	106.472/09/04/2000
T280-27	TANK STORAGE (EPN 280-27)	47256, 106.478[93742]/09/04/2000, N258, PSDTX402M4
T280-28	TANK STORAGE (EPN 280-28)	2231
T280-29	TANK STORAGE (EPN 280-29)	2231, 106.261/11/01/2003
T280-3003	AMOCO COCKTAIL (EPN 280-3003)	106.472/09/04/2000
T280-3004	CHEVRO OGA 492D DETERGENT DEPOSIT (EPN 280-3004)	106.472/09/04/2000
T280-3006	NALCO 5403 - 50% (EPN 280-3006)	106.472/09/04/2000
T280-3007	ISONOX 133 ANTIOXIDANT COCKTAIL (EPN 280-3007)	106.472/09/04/2000
T280-3010	AMOCO SILVER (EPN 280-3010)	47256, N258, PSDTX402M4
T280-3021	BLACK DYE COCKTAIL (EPN 280-3021)	106.472/09/04/2000
T280-3022	DETERGENT (EPN 280-3022)	106.472/09/04/2000
T280-3023	DETERGENT (EPN 280-3023)	106.472/09/04/2000
T280-3024	DETERGENT (EPN 280-3024)	106.472/09/04/2000
T280-3025	NALCO 5403 CORROSION CLCOTAIL/CHEMLINK IPC	106.472/09/04/2000
T280-3026	ISONOX 133 ANTIOXIDANT COCKTAIL 9EPN 280-3026)	106.472/09/04/2000
T280-3027	ADDITIVE TANK 3027 (EPN 280-3027)	106.478/09/04/2000
T280-3040	PETOLITE TOLAD 368 POUR POINT DEPRESSANT	106.472/09/04/2000
T280-3041	NALCO 5308 CETANE IMPROVER (EPN 280-3041)	106.472/09/04/2000
T280-3042	NALCO 5300 STABILIZER (EPN 280-3042)	106.472/09/04/2000
T280-3043	NALCO 89BD009 DEHAZER (EPN 280-3043)	106.472/09/04/2000

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
T280-3044	PETOLITE TOLAD T-361 FURNACE OIL ADDITIVE	106.472/09/04/2000
T280-3045	AMOCO 6869 RED D-GUARD (EPN 280-3045)	106.472/09/04/2000
T280-30	TANK STORAGE (EPN 280-30)	2231
T280-3103	AMOCO COCKTAIL (EPN 280-3103)	106.472/09/04/2000
T280-3105	ADDITIVE TANK 3105 (EPN 280-3105)	106.261/11/01/2003
T280-3106	AMOCO COCKTAIL (EPN 280-3106)	106.472/09/04/2000
T280-3107	AMOCO COCKTAIL (EPN 280-3107)	106.472/09/04/2000
T280-3121	BLACK DYE FOR SILVER GASOLINE (EPN 280-3121)	106.472/09/04/2000
T280-33A	STORAGE TANK	106.478/09/04/2000
T280-34	TANK 34 (EPN 280-34)	47256, 106.478[140391]/09/04/2000, N258, PSDTX402M4
T280-36	TANK STORAGE (EPN 280-36)	2231
T280-37	TANK STORAGE (EPN 280-37)	2231
T280-38	TANK STORAGE (EPN 280-38)	2231
T280-39	ISOMERATE TANK (EPN 280-39)	2231
T280-4000	TANK 4000 (EPN 280-4000, TANKCAP)	47256, N258, PSDTX402M4
T280-4001	TANK 4001 (EPN 280-4001)	106.478[107970]/03/14/1997
T280-4002	TANK 4002 (EPN 280-4002)	106.478[107970]/03/14/1997
T280-4003	TANK 4003 (EPN 280-4003)	106.478[107970]/03/14/1997
T280-42	TANK STORAGE (EPN 280-42, TANKCAP)	47256, N258, PSDTX402M4
T280-43	TANK STORAGE (EPN 280-43, TANKCAP)	47256, N258, PSDTX402M4

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
T280-44	TANK STORAGE (EPN 280-44)	47256, N258, PSDTX402M4
T280-45	TANK STORAGE (EPN 280-45)	47256, N258, PSDTX402M4
T280-46	TANK STORAGE (EPN 280-46)	47256, N258, PSDTX402M4
T280-47	TANK STORAGE (EPN 280-47)	47256, N258, PSDTX402M4
T280-48	TANK STORAGE (EPN 280-48)	47256, N258, PSDTX402M4
T280-49	TANK 49 (EPN 280-49)	47256, N258, PSDTX402M4
T280-501	TANK STORAGE (EPN 280-501)	47256, 106.478[97043]/09/04/2000, N258, PSDTX402M4
T280-502	TANK STORAGE (EPN 280-502)	47256, N258, PSDTX402M4
T280-503	TANK STORAGE (EPN 280-503)	47256, 106.261/11/01/2003, N258, PSDTX402M4
T280-504	TANK STORAGE (EPN 280-504)	47256, 106.478[107838]/09/04/2000, N258, PSDTX402M4
T280-50	TANK 50 (EPN 280-50)	47256, N258, PSDTX402M4
T280-515	CAUSTIC (EPN 280-515)	106.472/03/14/1997
T280-516	SULFURIC ACID (EPN 280-516)	106.472/03/14/1997
T280-518	HYDRATED LIME (EPN 280-518)	106.472/09/04/2000
T280-51	TANK STORAGE (EPN 280-51)	47256, N258, PSDTX402M4
T280-520	STORAGE TANK NO. 520 (EPN 280-520)	2231
T280-528	TANK STORAGE (EPN 280-528)	47256, N258, PSDTX402M4
T280-529	PREMIUM LEAD FREE STORAGE TANK (EPN 280-529)	47256, 106.261[146161]/11/01/2003, N258, PSDTX402M4
T280-52	TANK STORAGE (EPN 280-52)	47256, N258, PSDTX402M4

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
T280-530	TANK STORAGE (EPN 280-530)	47256, 106.261[134247]/11/01/2003, N258, PSDTX402M4
T280-531	TANK STORAGE (EPN 280-531)	47256, 106.261/11/01/2003, N258, PSDTX402M4
T280-532	TANK STORAGE (EPN 280-532)	2231
T280-533	TANK STORAGE (EPN 280-533)	2231
T280-534	TANK STORAGE (EPN 280-534)	2231
T280-535	TANK STORAGE (EPN 280-535)	2231, 106.261/11/01/2003
T280-536	TANK STORAGE (EPN 280-536)	47256, N258, PSDTX402M4
T280-537	TANK STORAGE (EPN 280-537)	1940
T280-538	TANK STORAGE (EPN 280-538)	2231
T280-53	TANK 53 (EPN 280-53)	47256, N258, PSDTX402M4
T280-54	TANK 54 (EPN 280-54)	47256, N258, PSDTX402M4
T280-55	TANK STORAGE (EPN 280-55)	47256, N258, PSDTX402M4
T280-561	TANK STORAGE	47256, N258, PSDTX402M4
T280-56	TANK STORAGE (EPN 280-56)	47256, N258, PSDTX402M4
T280-57	TANK STORAGE (EPN 280-56)	47256, N258, PSDTX402M4
T280-60	TANK STORAGE (EPN 280-60)	47256, N258, PSDTX402M4
T280-61	TANK STORAGE (EPN 280-561)	47256, N258, PSDTX402M4
T280-63	TANK STORAGE (EPN 280-63, TANKCAP)	47256, N258, PSDTX402M4
T280-652	TANK STORAGE (EPN 280-652)	47256, N258, PSDTX402M4
T280-653	TANK STORAGE (EPN 280-653)	47256, N258, PSDTX402M4

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
T280-65	TANK STORAGE (EPN 280-65)	47256, N258, PSDTX402M4
T280-66	TANK STORAGE (EPN 280-66)	47256, N258, PSDTX402M4
T280-67	TANK STORAGE (EPN 280-67)	47256, N258, PSDTX402M4
T280-71	TANK STORAGE (EPN 280-71)	47256, N258, PSDTX402M4
T280-72	TANK STORAGE (EPN 280-72)	47256, N258, PSDTX402M4
T280-73	TANK STORAGE (EPN 280-73)	47256, N258, PSDTX402M4
T280-7	TANK 7 (EPN 280-7)	106.478[78120]/09/04/2000
T280-80	TANK 80 (EPN 280-80)	47256, N258, PSDTX402M4
T280-8	TANK STORAGE (EPN 280-8)	2231
T280-90	TANK STORAGE (EPN 280-90)	47256, N258, PSDTX402M4
T280-91	TANK STORAGE (EPN 280-91)	47256, N258, PSDTX402M4
T280-92	TANK STORAGE (EPN 280-92)	47256, N258, PSDTX402M4
T280-94	STORAGE TANK (EPN 280-94)	47256, N258, PSDTX402M4
T280-95	TANK STORAGE (EPN 280-95)	47256, N258, PSDTX402M4
T280-97	TANK STORAGE (EPN 280-97)	47256, 106.261[134247]/11/01/2003, N258, PSDTX402M4
T280-98	TANK STORAGE (EPN 280-98)	47256, 106.478[97644]/09/04/2000, N258, PSDTX402M4
T280-9	TANK STORAGE (EPN 280-9)	2231, 106.261[146161]/11/01/2003
TCH-2	FLARE #2 (EPN 311)	47256, N258, PSDTX402M4
TCH-3	FLARE #3 (EPN 321)	47256, 86558, N258, PSDTX402M4

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
TCH-4	FLARE #4 (EPN 331)	47256, N258, PSDTX402M4
TCH-6	FLARE #6 (EPN 530)	9606
TCH-8	FLARE #8 (EPN 400)	47256, N258, PSDTX402M4
TCH-AU2	AU2 FLARE (EPN 611)	2612
TCH-AU2	COMMON VENT TO FLARE TCH-AU2 (EPN 611)	2612
TCH-CFHU	CFHU FLARE 1 (EPN 501)	47256, N258, PSDTX402M4
TCH-DDU	COMMON VENT TO FLARE TCH-DDU (EPN 501)	47256, N258, PSDTX402M4
TCH-DDU	DISTILLATE DESULFURIZER FLARE (EPN 396A)	47256, N258, PSDTX402M4
TCH-ULC	ULC FLARE (EPN 351A)	150222, 47256, N258, PSDTX402M4
TDU-BH	TDU BAGHOUSE	22107
TDU-CB	TDU CAKE BOX	22107
TDU-CFG1	TDU CENTRIFUGE 1	22107
TDU-CFG2	TDU CENTRIFUGE 2	22107
TDU-CONVEYOR	TDU CONVEYOR	22107
TDU-CT	TDU COOLING TOWER	22107
TDU-DRYER	THERMAL DESORPTION UNIT (TDU)	22107
TDU-FUG	TDU PIPING FUGITIVES	22107
TDU-GSR	TDU GAS STREAM REFINING PROCESS VENT	22107
TDU-OWS	TDU OIL WATER SEPARATOR	22107
TDU-TO	TDU THERMAL OXIDIZER	22107
TDU-TRANSFER	TDU TRANSFER	22107

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
TDU-VETURI	TDU SCRUBBER	22107
TEMPPJ16B	TEMP PJ16B DOCK WATER PUMP	106.512/06/13/2001
TGUF201C/D	TGUF201C/D	47256, N258, PSDTX402M4
TK-10	MONOETHANOLAMINE	106.472/09/04/2000
TK117APUMP	EAST OF TANK 117A, 75 HP	106.512/06/13/2001
TK-1	25% MONOETHANOLAMINE	106.472/09/04/2000
TK-201	METHYLDIETHANOLAMINE TANK	106.472/09/04/2000
TK206CMP	TANK 206 COMPRESSOR (EPN TK206CMP)	106.512[13501]/06/13/2001
TK207CMP	TANK 207 COMPRESSOR (EPN TK207CMP)	106.512[13501]/06/13/2001
TK20PUMP	TANK 20 LUF, 75 HP (EPN TK20 PUMP)	106.512/06/13/2001
TK-210F	SEAL OIL TANK (COKERS)	106.472/03/14/1997
TK-2	25% MONOETHANOLAMINE	106.472/09/04/2000
TK-264F	CAUSTIC	106.472/03/14/1997
TK-303F	CAUSTIC	106.472/03/14/1997
TK-304F	METHANOL STORAGE TANK	106.476/03/14/1997
TK-305F	CAUSTIC (EPN TK-305F)	106.472/03/14/1997
TK-314F	5% CAUSTIC (EPN TK-314F)	106.472/03/14/1997
TK-315F	50% CAUSTIC (EPN TK-315F)	106.472/03/14/1997
TK-329F	15% CAUSTIC (EPN TK-329F)	47256, N258, PSDTX402M4
TK-330F	15% CAUSTIC (EPN TK-330F)	47256, N258, PSDTX402M4
TK-356F	25% 50% CAUSTIC (EPN TK-356F)	106.472/03/14/1997

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
TK4000PUMP	TANK 4000, 55 HP	106.512/06/13/2001
TK-440F	5% CAUSTIC (EPN TK-440F)	106.472/03/14/1997
TK-517F	10% CAUSTIC (EPN TK-517F)	106.472/03/14/1997
TK-527F	50% CAUSTIC (EPN TK-527F)	106.472/03/14/1997
TK536CMPB	TANK 536 COMPRESSOR (EPN TK536 COMP)	106.512/06/13/2001
TK-565F	RHU TANK 565-F (EPN 280-RHU575F)	106.472/09/04/2000
TK-600	LIGHT SLOP OIL (EPN 280-600)	106.472/03/14/1997
TK-601	LIGHT SLOP OIL (EPN 280-601)	47256, 106.472/03/14/1997, N258, PSDTX402M4
TK-602	ISOPENTANE (EPN 280-602)	47256, 106.472/03/14/1997, N258, PSDTX402M4
TK-603	ISOPENTANE (EPN 280-603)	106.472/03/14/1997
TK-604	ISOPSENTANE (EPN 280-604)	106.472/03/14/1997
TK-608F	FRESH SULFOLANE (EPN 108-608)	2231, 106.261/11/01/2003
TK-610	TREATED ISOBUTANE (EPN 280-610)	47256, N258, PSDTX402M4
TK-611	FIELD BUTANE (EPN 280-611)	47256, N258, PSDTX402M4
TK-612	UNTREATED ISOBUTANE (EPN 280-612)	47256, N258, PSDTX402M4
TK-613	NORMAL BUTANE (EPN 280-613)	47256, N258, PSDTX402M4
TK-614	TREATED ISOBUTANE (EPN 280-614)	47256, N258, PSDTX402M4
TK-615	NORMAL BUTANE (EPN 280-615)	47256, N258, PSDTX402M4
TK-616	UNTREATED ISOBUTANE (EPN 280-616)	47256, N258, PSDTX402M4
TK-618	MIXED BUTANE (EPN 280-618)	47256, N258, PSDTX402M4
TK-620	ALKY FEED MIXED B-B (EPN 280-620)	47256, N258, PSDTX402M4

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
TK-622	UNTREATED ISOBUTANE (EPN 280-622)	47256, N258, PSDTX402M4
TK-624	ALKY FEED MIXED B-B (EPN 280-624)	47256, N258, PSDTX402M4
TK-626	PRESSURE TANK (EPN 280-626)	47256, N258, PSDTX402M4
TK-9	MONOETHANOLAMINE (EPN 280-SRU9)	106.472/09/04/2000
TK-ACIDTK	98% SULFURIC ACID (EPN TK-ACIDTK)	106.472/03/14/1997
TK-F109	HYDRATED LIME (EPN TK-F109)	106.472/09/04/2000
TK-F170	NALCO N-7192 POLYMER (EPN TK-F170)	106.472/09/04/2000
TK-F180	50% CAUSTIC (EPN TK-F180)	106.472/03/14/1997
TK-F190	50% CAUSTIC (EPN TK-F190)	106.472/03/14/1997
TK-F209	NALCO N-7192 POLYMER (EPN TK-F209)	106.472/09/04/2000
TK-F215	WASTEWATER TANK TK-F215 (EPN 280-215)	22107
TK-F216	SURGE TANK (EPN 280-216)	22107
TK-F221	COKER TANK F-221 (EPN 280-COKRF221)	106.472/09/04/2000
TK-F617	NALCO L -931M (EPN TK-F617)	106.472/09/04/2000
TK-F620	LCCO (EPN TK-F620)	86/09/12/1989
TK-FUELTK	DIESEL (EPN TK-FUELTK)	106.472/03/14/1997
TK-G405	MONETHANOLAMINE	106.472/09/04/2000
TK-I656	98% SULFURIC ACID (EPN TK-I656)	106.472/03/14/1997
TK-I657	50% RAYON GRADE CAUSTIC (EPN TK-I657)	106.472/03/14/1997
TK-IWCP	POLYMER	106.472/09/04/2000
TK-L1501	TREATED WATER (EPN TK-L1501)	106.472/03/14/1997

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
TK-L1502	TREATED WATER (EPN TK-L1502)	106.472/03/14/1997
TK-R602	HYDRATED LIME	106.472/09/04/2000
TK-SM1001	OMCC ADDITIVE TANK (EPN ADD-T100)	106.261/11/01/2003, 106.478/09/04/2000
TK-T1000	5% CAUSTIC (EPN TK-T1000)	106.472[97249]/03/14/1997
TK-T1001	50% CAUSTIC (EPN TK-T1001)	106.472[97249]/03/14/1997
TK-T1002	38% CALCIUM CHLORIDE (EPN TK-T1002)	106.472/03/14/1997
TK-V305	50% CAUSTIC (EPN TK-V305)	106.472/03/14/1997
TNT003	BULK TANK AT WWTP CLARIFIER (EPN TNT003	106.472/09/04/2000
TNT004	BULK TANK AT WWTP DAF (EPN TNT004)	106.472/09/04/2000
TNT017	BULK TANK AT PWR3 (EPN TNT017)	106.472/09/04/2000
TNT022	BULK TANK AT PWR2 (EPN TNT022)	106.261[88241]/11/01/2003, 106.262[88241]/11/01/2003
TNT029	BULK TANK AT UU3 (EPN TNT029)	106.472/09/04/2000
TNT030	BULK TANK AT PWR2 (EPN TNT030)	106.472/09/04/2000
TNT037	BULK TANK AT ULC (EPN TNT037)	106.472/09/04/2000
TNT038	BULK TANK AT UU4 (EPN TNT038)	106.472/09/04/2000
TNT040	BULK TANK AT FCCU1 (EPN TNT040)	106.472/09/04/2000
TNT043	BULK TANK AT FCCU3 (EPN TNT043)	106.472/09/04/2000
TNT045	BULK TANK AT PS3B (EPN TNT045)	106.472/09/04/2000
TNT048	BULK TANK AT PS3A/B (EPN TNT048)	106.472/09/04/2000
TNT049	BULK TANK AT FCCU1 (EPN TNT049)	106.472/09/04/2000

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
TNT051	BULK TANK AT FCCU3 (EPN TNT051)	106.472/09/04/2000
TNT052	BULK TANK AT ALKY3 (EPN TNT052)	106.472/09/04/2000
TNT053	BULK TANK AT ALKY2 (EPN TNT053)	106.472/09/04/2000
TNT054	BULK TANK AT UU3 (EPN TNT054)	106.472/09/04/2000
TNT057	BULK TANK AT FCCU1 (EPN TNT057)	106.472/09/04/2000
TNT058	BULK TANK AT FCCU2 (EPN TNT058)	106.472/09/04/2000
TNT059	TANK AT FCCU2 (EPN TNT059)	106.472/09/04/2000
TNT078	BULK TANK AT FCCU3 (EPN TNT078)	106.472/09/04/2000
TNT079	BULK TANK AT UU4 (EPN TNT079)	106.472/09/04/2000
TNT081	BULK TANK AT ULC (EPN TNT081)	106.472/09/04/2000
TNT082	BULK TANK AT CFHU (EPN TNT082)	106.472/09/04/2000
TNT083	BULK TANK AT COKER (EPN TNT083)	106.472/09/04/2000
TNT084	BULK TANK AT PS3B (EPN TNT084)	106.472/09/04/2000
TNT085	BULK TANK AT PS3A/B (EPN TNT085)	106.472/09/04/2000
TNT086	BULK TANK AT FCCU1 (EPN TNT086)	106.472/09/04/2000
TNT087	BULK TANK AT FCCU3 (EPN TNT087)	106.472/09/04/2000
TNT088	BULK TANK AT ALKY3 (EPN TNT088)	106.472/09/04/2000
TNT090	BULK TANK AT WWTP (EPN TNT090)	106.472/09/04/2000
TNT092	BULK TANK AT WWTP (EPN TNT092)	106.472/09/04/2000
TNT093	BULK TANK AT WWTP (EPN TNT093)	106.472/09/04/2000
TNT094	BULK TANK AT UU3 (EPN TNT094)	106.472/09/04/2000

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
TNT095	BULK TANK AT ALKY2 (EPN TNT095)	106.472/09/04/2000
TNT096	BULK TANK AT ALKY3 (EPN TNT096)	106.472/09/04/2000
TNT131	BULK TANK AT ARU (EPN TNT131)	106.261[88241]/11/01/2003, 106.262[88241]/11/01/2003
TNT132	BULK TANK AT ULC (EPN TNT132)	106.261[88241]/11/01/2003, 106.262[88241]/11/01/2003
TNT133	BULK TANK AT UU4 (EPN TNT133)	106.261[88241]/11/01/2003, 106.262[88241]/11/01/2003
TNT140	BULK TANK AT PWR2 (EPN TNT140)	106.261[88241]/11/01/2003, 106.262[88241]/11/01/2003
TNT144	BULK TANK AT REFINERY DOCK	106.261[88241]/11/01/2003, 106.262[88241]/11/01/2003
TNT145	TOTE AT OMCC (EPN TNT145)	106.261[88241]/11/01/2003, 106.262[88241]/11/01/2003
TNT146	TOTE AT OMCC OMCC (EPN TNT146)	106.261[88241]/11/01/2003, 106.262[88241]/11/01/2003
TNT147	TOTE AT OMCC (EPN TNT147)	106.261/11/01/2003, 106.262/11/01/2003
TNT150	TANK AT OMCC (EPN TNT150)	106.472/09/04/2000
TNT151	TANK AT OMCC (EPN TNT151)	106.472/09/04/2000
TNT152	TOTE AT OMCC (EPN TNT152)	106.472/09/04/2000
TNT153	TANK AT OMCC (EPN TNT153)	106.472/09/04/2000
TNT154	TANK AT OMCC (EPN TNT154)	106.472/09/04/2000
TNT155	TANK AT REFINERY DOCK (EPN TNT155)	106.261[88241]/11/01/2003, 106.262[88241]/11/01/2003

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
TNT156	TANK AT OMCC (EPN TNT156)	106.472/09/04/2000
TNT157	TANK AT OMCC (EPN TNT157)	106.261[88241]/11/01/2003, 106.262[88241]/11/01/2003
TNT161	TANK AT FCCU3 (EPN TNT161)	106.261[88241]/11/01/2003, 106.262[88241]/11/01/2003
TNT162	TANK AT OMCC (EPN TNT162)	106.261[88241]/11/01/2003, 106.262[88241]/11/01/2003
TNT164	TANK AT OMCC (EPN TNT164)	106.261[88241]/11/01/2003, 106.262[88241]/11/01/2003
TNT165	TANK AT OMCC (EPN TNT165)	106.478/09/04/2000
TNT166	TANK AT PS3A/B (EPN TNT166)	106.472/09/04/2000
TNT167	TANK AT PS3A/B (EPN TNT167)	106.472/09/04/2000
TNT168	TANK AT UU3 (EPN TNT168)	106.261[88241]/11/01/2003, 106.262[88241]/11/01/2003
TNT169	TANK AT FCCU3 (EPN TNT169)	106.261[88241]/11/01/2003, 106.262[88241]/11/01/2003
TNT171	TANK AT COKER (EPN TNT171)	106.472/09/04/2000
TNT172	TANK AT PS3A/B (EPN TNT172)	106.261[88241]/11/01/2003, 106.262[88241]/11/01/2003
TNT173	TANK AT DDU (EPN TNT173)	106.261[88241]/11/01/2003, 106.262[88241]/11/01/2003
TNT174	TANK AT DDU (EPN TNT174)	106.261[88241]/11/01/2003, 106.262[88241]/11/01/2003
TNT175	TANK AT PS3A/B (EPN TNT175)	106.261[88241]/11/01/2003,

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
		106.262[88241]/11/01/2003
TNT176	TANK AT PS3A/B (EPN TNT176)	106.261[88241]/11/01/2003, 106.262[88241]/11/01/2003
TNT177	TANK AT UU4 (EPN TNT177)	106.261[88241]/11/01/2003, 106.262[88241]/11/01/2003
TNT178	TANK AT UU4 (EPN TNT178)	106.261[88241]/11/01/2003, 106.262[88241]/11/01/2003
TNT179	TANK AT UU4 (EPN TNT179)	106.261[88241]/11/01/2003, 106.262[88241]/11/01/2003
TNT180	TANK AT UU4 (EPN TNT180)	106.261[88241]/11/01/2003, 106.262[88241]/11/01/2003
TNT181	TANK AT UU3 (EPN TNT181)	106.261[88241]/11/01/2003, 106.262[88241]/11/01/2003
TNT182	TANK AT UU3 (EPN TNT182)	106.261[88241]/11/01/2003, 106.262[88241]/11/01/2003
TNT183	TANK AT UU3 (EPN TNT183)	106.261[88241]/11/01/2003, 106.262[88241]/11/01/2003
TNT184	TANK AT FCCU1 (EPN TNT184)	106.472/09/04/2000
TNT185	TANK AT FCCU2 (EPN TNT185)	106.472/09/04/2000
TNT186	TANK AT FCCU3 (EPN TNT186)	106.472/09/04/2000
TNT187	TANK AT PS3A/B (EPN TNT187)	106.472/09/04/2000
TNT188	TANK AT RHU (EPN TNT188)	106.472/09/04/2000
TNT189	TANK AT UU4 (EPN TNT189)	106.472/09/04/2000
TNT190	TANK AT UU4 (EPN TNT190)	106.472/09/04/2000

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
TNT191	TANK AT UU4 (EPN TNT191)	106.472/09/04/2000
TNT192	TANK AT UU3 (EPN TNT192)	106.472/09/04/2000
TNT193	TANK AT UU3 (EPN TNT193)	106.472/09/04/2000
TNT194	TANK AT UU3 (EPN TNT194)	106.472/09/04/2000
TNT195	TANK AT ULC (EPN TNT195)	106.472/09/04/2000
TNT196	TANK AT ULC (EPN TNT196)	106.472/09/04/2000
TNT197	TANK AT ARU (EPN TNT197)	106.261[88241]/11/01/2003, 106.262[88241]/11/01/2003
TNT198	TANK AT ARU (EPN TNT198)	106.261[88241]/11/01/2003, 106.262[88241]/11/01/2003
TNT199	TOTE AT PS3A/B (EPN TNT199)	106.261[88241]/11/01/2003, 106.262[88241]/11/01/2003
TNT200	TOTE AT PS3A/B (EPN TNT200)	106.261[88241]/11/01/2003, 106.262[88241]/11/01/2003
TNT201	TANK AT SRU (EPN TNT201)	106.472/09/04/2000
TNT202	TANK AT SRU (EPN TNT202)	106.472/09/04/2000
TNT203	TANK AT SRU (EPN TNT203)	106.472/09/04/2000
TNT204	TANK AT SRU (EPN TNT204)	106.472/09/04/2000
TNT205	TANK AT CFHU (EPN TNT205)	106.472/09/04/2000
TNT206	TANK AT CFHU (EPN TNT206)	106.472/09/04/2000
TNT207	TANK AT CFHU (EPN TNT207)	106.472/09/04/2000
TNT208	TANK AT CFHU (EPN TNT208)	106.472/09/04/2000

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
TNT209	TANK AT RHU (EPN TNT209)	106.472/09/04/2000
TNT210	TANK AT RHU (EPN TNT210)	106.472/09/04/2000
TNT211	TANK AT RHU (EPN TNT211)	106.472/09/04/2000
TNT212	TANK AT RHU (EPN TNT212)	106.472/09/04/2000
TNT213	TANK AT RHU (EPN TNT213)	106.472/09/04/2000
TNT214	TANK AT RHU (EPN TNT214)	106.472/09/04/2000
TNT215	TANK AT RHU (EPN TNT215)	106.472/09/04/2000
TNT216	TANK AT RHU (EPN TNT216)	106.472/09/04/2000
TNT217	TANK AT RHU (EPN TNT217)	106.472/09/04/2000
TNT218	TANK AT ALKY2 (EPN TNT218)	106.472/09/04/2000
TNT219	TANK AT ALKY2 (EPN TNT219)	106.472/09/04/2000
TNT220	TANK AT ALKY2 (EPN TNT220)	106.472/09/04/2000
TNT221	TANK AT FCCU3 (EPN TNT221)	106.472/09/04/2000
TNT222	TANK AT FCCU3 (EPN TNT222)	106.472/09/04/2000
TNT223	TANK AT FCCU3 (EPN TNT223)	106.472/09/04/2000
TNT224	TANK AT FCCU1 (EPN TNT224)	106.472/09/04/2000
TNT225	TANK AT FCCU1 (EPN TNT 225)	106.472/09/04/2000
TNT226	TANK AT FCCU2 (EPN TNT226)	106.472/09/04/2000
TNT227	TANK AT FCCU2 (EPN TNT227)	106.472/09/04/2000
TNT228	TANK AT PS3A (EPN TNT228)	106.472/09/04/2000
TNT229	TANK AT PS3A (EPN TNT229)	106.472/09/04/2000

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
TNT230	TANK AT PS3A (EPN TNT230)	106.472/09/04/2000
TNT231	TANK AT PS3A (EPN TNT231)	106.472/09/04/2000
TNT232	TANK AT PS3A (EPN TNT232)	106.472/09/04/2000
TNT233	TANK AT PS3A (EPN TNT233)	106.472/09/04/2000
TNT234	TANK AT PS3A (EPN TNT234)	106.472/09/04/2000
TNT235	TANK AT PS3A (EPN TNT235)	106.472/09/04/2000
TNT236	TANK AT PS3A (EPN TNT236)	106.472/09/04/2000
TNT237	TANK AT PS3A (EPN TNT237)	106.472/09/04/2000
TNT238	TANK AT PS3B (EPN TNT238)	106.472/09/04/2000
TNT239	TANK AT PS3B (EPN TNT239)	106.472/09/04/2000
TNT240	TANK AT PS3B (EPN TNT240)	106.472/09/04/2000
TNT241	TANK AT PS3B (EPN TNT241)	106.472/09/04/2000
TNT242	TANK AT PS3B (EPN TNT242)	106.472/09/04/2000
TNT243	TANK AT PS3B (EPN TNT243)	106.472/09/04/2000
TNT244	TANK AT PS3B (EPN TNT244)	106.472/09/04/2000
TNT245	TANK AT PS3B (EPN TNT245)	106.472/09/04/2000
TNT246	TANK AT OMCC (EPN TNT246)	106.472/09/04/2000
TNT247	TANK AT ENVF (EPN TNT247)	106.472/09/04/2000
TNT248	TANK AT ENVF (EPN TNT248)	106.472/09/04/2000
TNT249	TANK AT ENVF (EPN TNT249)	106.472/09/04/2000
TNT250	TANK AT ENVF (EPN TNT250)	106.472/09/04/2000

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
TNT251	TANK AT ENVF (EPN TNT251)	106.472/09/04/2000
TNT252	TANK AT HYDROSLAB (EPN TNT252)	106.472/09/04/2000
TNT253	TANK AT COKER (EPN TNT253)	106.472/09/04/2000
TNT254	TANK AT COKER (EPN TNT254)	106.472/09/04/2000
TNT255	TANK AT COKER (EPN TNT255)	106.472/09/04/2000
TNT256	TANK AT COKER (EPN TNT256)	106.472/09/04/2000
TNT257	TANK AT COKER (EPN TNT257)	106.472/09/04/2000
TNT258	TANK AT COKER (EPN TNT258)	106.472/09/04/2000
TNT259	TANK AT COKER (EPN TNT259)	106.472/09/04/2000
TNT260	TANK AT COKER (EPN TNT260)	106.472/09/04/2000
TNT261	TANK AT COKER (EPN TNT261)	106.472/09/04/2000
TNT262	TANK AT RDU (EPN TNT262)	106.472/09/04/2000
TNT263	TANK AT RDU (EPN TNT263)	106.472/09/04/2000
TNT264	TANK AT RDU (EPN TNT264)	106.472/09/04/2000
TNT265	TANK AT RDU (EPN TNT265)	106.472/09/04/2000
TNT266	TANK AT AU2 (EPN TNT266)	106.472/09/04/2000
TNT267	TANK AT AU2 (EPN TNT267)	106.472/09/04/2000
TNT268	TANK AT AU2 (EPN TNT268)	106.472/09/04/2000
TNT269	TANK AT ISOM (EPN TNT269)	106.472/09/04/2000
TNT270	TANK AT ISOM (EPN TNT270)	106.472/09/04/2000
TNT271	TANK AT NDU (EPN TNT271)	106.472/09/04/2000

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
TNT272	TANK AT UU3 (EPN TNT272)	106.472/09/04/2000
TNT273	TANK AT UU3 (EPN TNT273)	106.472/09/04/2000
TNT274	TANK AT UU3 (EPN TNT274)	106.472/09/04/2000
TNT275	TANK AT UU4 (EPN TNT275)	106.472/09/04/2000
TNT276	TANK AT UU4 (EPN TNT276)	106.472/09/04/2000
TNT277	TANK AT UU4 (EPN TNT277)	106.472/09/04/2000
TNT278	TANK AT UU4 (EPN TNT278)	106.472/09/04/2000
TNT279	TANK AT UU4 (EPN TNT279)	106.472/09/04/2000
TNT280	TANK AT GARAGE (EPN TNT280)	106.472/09/04/2000
TNT281	TANK AT MACHINE SHOP (EPN TNT281)	106.472/09/04/2000
TNT282	TANK AT ALKY3 (EPN TNT282)	106.472/09/04/2000
TNT283	TANK AT ALKY3 (EPN TNT283)	106.472/09/04/2000
TNT284	TANK AT ALKY3 (EPN TNT284)	106.472/09/04/2000
TNT285	TANK AT ULC (EPN TNT285)	106.472/09/04/2000
TNT286	TANK AT ULC (EPN TNT286)	106.472/09/04/2000
TNT287	TANK AT ULC (EPN TNT287)	106.472/09/04/2000
TNT288	TANK AT ULC (EPN TNT288)	106.472/09/04/2000
TNT289	TANK AT ULC (EPN TNT289)	106.472/09/04/2000
TNT290	TANK AT ULC (EPN TNT290)	106.472/09/04/2000
TNT291	TANK AT PWR2 (EPN TNT291)	106.472/09/04/2000
TNT292	TANK AT PWR2 (EPN TNT292)	106.472/09/04/2000

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
TNT293	TANK AT PWR2 (EPN TNT293)	106.472/09/04/2000
TNT294	TANK AT PWR2 (EPN TNT294)	106.472/09/04/2000
TNT295	TANK AT PWR2 (EPN TNT295)	106.472/09/04/2000
TNT296	TANK AT PWR2 (EPN TNT296)	106.472/09/04/2000
TNT297	TANK AT PWR3 (EPN TNT297)	106.472/09/04/2000
TNT298	TANK AT PWR3 (EPN TNT298)	106.472/09/04/2000
TNT299	TANK AT PWR3 (EPN TNT299)	106.472/09/04/2000
TNT300	TANK AT DOCKS (EPN TNT300)	106.472/09/04/2000
TNT301	TANK AT DOCKS (EPN TNT301)	106.472/09/04/2000
TNT302	TANK AT ARU (EPN TNT302)	106.472/09/04/2000
TNT303	TANK AT ARU (EPN TNT303)	106.472/09/04/2000
TNT304	TANK AT ARU (EPN TNT304)	106.472/09/04/2000
TNT305	TANK AT ARU (EPN TNT305)	106.472/09/04/2000
TNT306	TANK AT DDU (EPN TNT306)	106.472/09/04/2000
TNT307	TANK AT DDU (EPN TNT307)	106.472/09/04/2000
TNT308	TANK AT DDU (EPN TNT308)	106.472/09/04/2000
TNT309	TANK AT DDU (EPN TNT309)	106.472/09/04/2000
TNT310	TANK AT DDU (EPN TNT310)	106.472/09/04/2000
TNT311	TANK AT DDU (EPN TNT311)	106.472/09/04/2000
TNT312	TANK AT DDU (EPN TNT312)	106.472/09/04/2000
TNT313	MOTHER TANK (EPN TNT313)	106.472/09/04/2000

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
TNT314	S&S CLEANER TANK AT PS3A (EPN TNT314)	106.472/09/04/2000
TNT315	S&S CLEANER TANK AT PS3A (EPN TNT315)	106.472/09/04/2000
TNT316	S&S CLEANER TANK AT COKER (EPN TNT316)	106.472/09/04/2000
TNT317	S&S CLEANER TOTE AT SRU (EPN TNT317)	106.472/09/04/2000
TNT318	S&S CLEANER TOTE AT SRU (EPN TNT318)	106.472/09/04/2000
TNT319	S&S CLEANER TANK AT COKER (EPN TNT319)	106.472/09/04/2000
TNT320	S&S CLEANER TANK AT COKER (EPN TNT320)	106.472/09/04/2000
TNT321	S&S CLEANER TANK AT COKER (EPN TNT321)	106.472/09/04/2000
TNT322	S&S CLEANER TANK AT HYDROSLAB (EPN TNT322)	106.472/09/04/2000
TNT323	S&S CLEANER TANK AT HYDROSLAB (EPN TNT323)	106.472/09/04/2000
TNT324	S&S CLEANER FRAC TANK AT HYDROSLAB (EPN TNT324)	106.472/09/04/2000
TNT325	S&S CLEANER TOTE AT HYDROSLAB (EPN TNT325)	106.472/09/04/2000
TNT326	S&S CLEANER TOTE AT HYDROSLAB (EPN TNT326)	106.472/09/04/2000
TNT327	S&S CLEANER TOTE AT HYDROSLAB (EPN TNT327)	106.472/09/04/2000
TNT328	S&S CLEANER TOTE AT HYDROSLAB (EPN TNT328)	106.472/09/04/2000
TNT329	S&S CLEANER TOTE AT HYDROSLAB (EPN TNT329)	106.472/09/04/2000
TNT330	S&S CLEANER TOTE AT HYDROSLAB (EPN TNT330)	106.472/09/04/2000
TNT331	S&S CLEANER TOTE AT HYDROSLAB (EPN TNT331)	106.472/09/04/2000
TNT332	S&S CLEANER TOTE AT DECON STATION (EPN TNT332)	106.472/09/04/2000
TNT333	S&S CLEANER TANK AT FCCU1 (EPN TNT333)	106.472/09/04/2000
TNT334	S&S CLEANER TANK AT FCCU3 (EPN TNT334)	106.472/09/04/2000

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
TNT335	S&S CLEANER TANK AT FCCU3 (EPN TNT335)	106.472/09/04/2000
TNT336	S&S CLEANER TANK AT FCCU3 (EPN TNT336)	106.472/09/04/2000
TNT337	S&S CLEANER TANK AT FCCU3 (EPN TNT337)	106.472/09/04/2000
TNT338	S&S CLEANER TOTE AT FCCU3 (EPN TNT338)	106.472/09/04/2000
TNT339	S&S CLEANER TANK AT RHU (EPN TNT339)	106.472/09/04/2000
TNT340	S&S CLEANER TOTE AT RHU (EPN TNT340)	106.472/09/04/2000
TNT341	S&S CLEANER TANK AT RHU (EPN TNT341)	106.472/09/04/2000
TNT342	S&S CLEANER TOTE AT OMCC (EPN TNT342)	106.472/09/04/2000
TNT343	S&S CLEANER TANK AT VRU (EPN TNT343)	106.472/09/04/2000
TNT344	S&S CLEANER TANK AT COKER (EPN TNT344)	106.472/09/04/2000
TNT345	S&S CLEANER TANK AT COKER (EPN TNT345)	106.472/09/04/2000
TNT346	S&S CLEANER TANK AT COKER (EPN TNT346)	106.472/09/04/2000
TNT347	S&S CLEANER TANK AT PS3A/B (EPN TNT347)	106.472/09/04/2000
TNT348	S&S CLEANER TANK AT PS3A/B (EPN TNT348)	106.472/09/04/2000
TNT349	S&S CLEANER TANK AT PS3A/B (EPN TNT349)	106.472/09/04/2000
TNT350	S&S CLEANER TANK AT PS3A/B (EPN TNT350)	106.472/09/04/2000
TNT351	S&S CLEANER TANK AT OMCC (EPN TNT351)	106.472/09/04/2000
TNT352	S&S CLEANER TANK AT OMCC (EPN TNT352)	106.472/09/04/2000
TNT353	S&S CLEANER TANK AT OMCC (EPN TNT353)	106.472/09/04/2000
TNT354	S&S CLEANER TANK AT OMCC (EPN TNT354)	106.472/09/04/2000
TNT355	S&S CLEANER TANK AT SEPERATOR 3 (EPN TNT355)	106.472/09/04/2000

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
TNT356	S&S CLEANER TANK AT SEPERATOR 3 (EPN TNT356)	106.472/09/04/2000
TNT357	S&S CLEANER TOTE AT SEPERATOR 3 (EPN TNT357)	106.472/09/04/2000
TNT358	S&S CLEANER TANK AT OMCC (EPN TNT358)	106.472/09/04/2000
TNT359	S&S CLEANER TANK AT OMCC (EPN TNT359)	106.472/09/04/2000
TNT360	S&S CLEANER TANK AT OMCC (EPN TNT360)	106.472/09/04/2000
TNT361	S&S CLEANER TANK AT HEAVY EQUIPMENT GROUP (EPN TNT	106.472/09/04/2000
TNT362	FIREFIGHTING FOAM BLADDER TANK (EPN TNT362)	106.261[88241]/11/01/2003, 106.262[88241]/11/01/2003
TNT363	FIREFIGHTING FOAM TANK (EPN TNT363)	106.261[88241]/11/01/2003, 106.262[88241]/11/01/2003
TNT367	OFF ROAD DIESEL TANK AT SAVAGE YARD (EPN TNT367)	106.472/09/04/2000
TNT368	ON ROAD DIESEL TANK AT SAVAGE YARD (EPN TNT368)	106.472/09/04/2000
TNT369	HYDRAULIC OIL TANK AT SAVAGE YARD (EPN TNT369)	106.472/09/04/2000
TNT370	MOTOR OIL TANK AT SAVAGE YARD (EPN TNT370)	106.472/09/04/2000
TNT371	660-F GEAR BOX OIL TANK AT ARU (EPN TNT371)	106.472/09/04/2000
TNT372	661-F BEARING OIL TANK AT ARU (EPN TNT372)	106.472/09/04/2000
TNT373	662-F OIL MIST TANK AT ARU (EPN TNT373)	106.472/09/04/2000
TNT374	BULK OIL, BP TURBINOL SELECT 32 AT CFHU	106.472/09/04/2000
TNT375	LUBE OIL TANK ON NORTH SIDE OF UNIT AT CFHU (EPN 3	106.472/09/04/2000
TNT376	LUBE OIL TANK FOR COOLING TOWER AT CFHU (EPN TNT37	106.472/09/04/2000
TNT383	METAL DRUM ON NE OF J110 AT DDU (EPN TNT383)	106.472/09/04/2000

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
TNT386	METAL TANK WITH HEAT BLANKET AT DDU (EPN TNT386)	106.472/09/04/2000
TNT387	BULK OIL, BP TURBINOL SELECT 100 AT DDU	106.472/09/04/2000
TNT388	F-32A AT FCCU1 (EPN TNT388)	106.472/09/04/2000
TNT389	F-32C AT FCCU1 (EPN TNT389)	106.472/09/04/2000
TNT394	TK-100 AT FCCU2 (EPN TNT394)	106.472/09/04/2000
TNT395	TK-101 AT FCCU2 (EPN TNT395)	106.472/09/04/2000
TNT397	TURBINOL T-100 AT FCCU3 (EPN TNT397)	106.472/09/04/2000
TNT398	401J LUBE OIL/402J LUBE OIL/SEAL OIL AT FCCU3 (EPN	106.472/09/04/2000
TNT399	K-302 AT HYDROGEN (EPN TNT399)	106.472/09/04/2000
TNT401	#460 BULK OIL TANK AT RHU (EPN TNT401)	106.472/09/04/2000
TNT402	565-F SEAL OIL STORAGE TANK AT RHU (EPN TNT402)	106.472/09/04/2000
TNT404	#68 BULK OIL TANK AT RHU (EPN TNT404)	106.472/09/04/2000
TNT405	#46 LUBE/SEAL BULK OIL TANK AT RHU (EPN TNT405)	106.472/09/04/2000
TNT406	#46 LUBE/SEAL OIL TANK AT RHU (EPN TNT406)	106.472/09/04/2000
TNT411	175-F AT ULC (EPN TNT411)	106.472/09/04/2000
TNT413	BULK OIL, BP TURBINOL SELECT 150 AT ULTRACRACKER (	106.472/09/04/2000
TNT414	BULK OIL, BP TURBINOL SELECT 46 AT ULTRACRACKER (E	106.472/09/04/2000
TNT416	209-D AT ULTRACRACKER (EPN TNT416)	106.472/09/04/2000
TNT417	ULC BULK OIL AT ULTRACRACKER (EPN TNT417)	106.472/09/04/2000
TNT418	204-D AT ULTRACRACKER (EPN TNT418)	106.472/09/04/2000
TNT419	205-D AT ULTRACRACKER (EPN TNT419)	106.472/09/04/2000

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
TNT420	206-D AT ULTRACRACKER (EPN TNT420)	106.472/09/04/2000
TNT421	203-D AT ULTRACRACKER (EPN TNT421)	106.472/09/04/2000
TNT422	362-F AT ULTRAFORMER #3 (EPN TNT422)	106.472/09/04/2000
TNT423	363-F AT ULTRAFORMER #3 (EPN TNT423)	106.472/09/04/2000
TNT425	365-F AT ULTRAFORMER #3 (EPN TNT425)	106.472/09/04/2000
TNT426	LUBE OIL #220 AT ULTRAFORMER #3 (EPN TNT426)	106.472/09/04/2000
TNT427	LUBE OIL #46 AT ULTRAFORMER #3 (EPN TNT427)	106.472/09/04/2000
TNT428	LUBE OIL #68 AT ULTRAFORMER #3 (EPN TNT428)	106.472/09/04/2000
TNT429	BULK OIL, BP TURBINOL SELECT 46 AT ULTRAFORMER #3	106.472/09/04/2000
TNT430	46 LUBE OIL TANK AT ULTRAFORMER #4 (EPN TNT430)	106.472/09/04/2000
TNT431	68 OIL TANK AT ULTRAFORMER #4 (EPN TNT431)	106.472/09/04/2000
TNT432	NALCO TRI-ACT 1850 TOTE AT PWR2 (EPN TNT432)	106.472/09/04/2000
TNT433	NALCO TRI-ACT 1805 TOTE AT PWR2 (EPN TNT433)	106.472/09/04/2000
TNT434	NALCO 22130 BULK TANK AT PWR2 (EPN TNT434)	106.261[88241]/11/01/2003, 106.262[88241]/11/01/2003
TNT435	DOCKS WASTE WATER (EPN TNT435)	106.478[108602]/09/04/2000
TNT437	PIPESTILLS CORROSION INHIBITOR TOTE 1 (EPN TNT437)	106.478[108602]/09/04/2000
TNT438	PIPESTILLS CORROSION INHIBITOR TOTE 2 (EPN TNT438)	106.478[108602]/09/04/2000
TNT439	PIPESTILLS CORROSION INHIBITOR TOTE 3 (EPN TNT439)	106.478[108602]/09/04/2000
TNT440	PIPESTILLS CORROSION INHIBITOR TOTE 4 (EPN TNT440)	106.478[108602]/09/04/2000
TNT441	DOCKS H2S SCAVENGER TOTE (EPN TNT441)	106.261[88241]/11/01/2003,

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
		106.262[88241]/11/01/2003
TNT442	DOCKS H2S SCAVENGER TEMP TANK (EPN TNT442)	106.261[88241]/11/01/2003, 106.262[88241]/11/01/2003
TNT444	COOLING WATER TREATMENT (EPN TNT444)	106.371/09/04/2000
TNT445	COOLING WATER TREATMENT (EPN TNT445)	106.371/09/04/2000
TNT446	COOLING WATER TREATMENT (EPN TNT446)	106.371/09/04/2000
TNT447	COOLING WATER TREATMENT (EPN TNT447)	106.371/09/04/2000
TNT459	TANK AT ARU (EPN TNT459)	106.472/09/04/2000
TNT461	TOTE (EPN TNT461)	106.472/09/04/2000, 106.478[120373]/09/04/2000
TNT462	PHILMPLUS 5068 CKR B (EPN TNT462)	106.261[88241]/11/01/2003, 106.262[88241]/11/01/2003
TNT463	PHILMPLUS 5968 CKR C (EPN TNT463)	106.261[88241]/11/01/2003, 106.262[88241]/11/01/2003
TNTALKY3	ALKY3 NACE TOTE	106.472/09/04/2000
TNTARU	ARU NACE TOTE	106.472/09/04/2000
TNTUU3	UU3 NACE TOTE	106.472/09/04/2000
TODOCK54	DOCK 54E THERMAL OXIDIZER (EPN1300)	2231
TOTE 9272A	TOTE-SCAVENGER9272A (EPN TOTE 9272A)	106.261[88241]/11/01/2003, 106.262[88241]/11/01/2003
TOTE 9272B	TOTE-SCAVENGER9272B (EPN TOTE 9272B)	106.261[88241]/11/01/2003, 106.262[88241]/11/01/2003
TO-WWTP	WWTP THERMAL OXIDIZER (EPN 293, F-293)	22107, 106.261[139784]/11/01/2003

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
UF4-413F	UF4 FLARE KNOCK-OUT POT	47256, N258, PSDTX402M4
ULC 100-D	ULC REACTOR	47256, N258, PSDTX402M4
ULC 101-D	ULC REACTOR	47256, N258, PSDTX402M4
ULC 102-D	ULC REACTOR	47256, N258, PSDTX402M4
ULC 102-E	ULC DISTILLATION COLUMN	47256, N258, PSDTX402M4
ULC 103-E	ULC DISTILLATION COLUMN	47256, N258, PSDTX402M4
ULC 104-E	ULC DISTILLATION COLUMN	47256, N258, PSDTX402M4
ULC 105-E	ULC DISTILLATION COLUMN	47256, N258, PSDTX402M4
ULC 106-E	ULC DISTILLATION COLUMN	47256, N258, PSDTX402M4
ULC 107-E	ULC DISTILLATION COLUMN	47256, N258, PSDTX402M4
ULC 108-E	ULC DISTILLATION COLUMN	47256, N258, PSDTX402M4
ULC-100B	ULTRACRACKER NO. 1 (EPN 201, HEATERPM)	47256, N258, PSDTX402M4
ULC-101B	ULTRACRACKER NO. 1 (EPN 202, HEATERPM)	47256, N258, PSDTX402M4
ULC-102B	ULTRACRACKER NO. 1 (EPN 203, HEATERPM)	47256, N258, PSDTX402M4
ULC-103B	ULTRACRACKER NO. 1 (EPN 204, HEATERPM)	47256, N258, PSDTX402M4
ULC104BABB	ULC-104BA/BB COMMON VENT (EPN 205)	47256, N258, PSDTX402M4
ULC-104BA	HEATER ULC-104BA (EPN 205)	47256, N258, PSDTX402M4
ULC-104BB	HEATER ULC-104BB (EPN 205)	47256, N258, PSDTX402M4
ULC105BABB	ULC-105BA/BB COMMON VENT (EPN 206, HEATERPM)	47256, N258, PSDTX402M4
ULC-105BA	HEATER ULC-105BA (EPN 206, HEATERPM)	47256, N258, PSDTX402M4
ULC-105BB	HEATER ULC-105BB (EPN 206, HEATERPM)	47256, N258, PSDTX402M4

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
ULC-127FA	ULC FLARE KNOCK-OUT POT	47256, N258, PSDTX402M4
ULC-143F	ULC FLARE KNOCK-OUT POT	47256, N258, PSDTX402M4
ULCARU-SEP4	ULC OIL-WATER SEPARATOR 4 (EPN W-06)	47256, N258, PSDTX402M4
ULC-CTWR	ULTRACRACKER COOLING TOWER (EPN 418)	47256, 106.371/09/04/2000, N258, PSDTX402M4
ULC-FUG1	ULTRACRACKER FUGITIVES 1 (EPN F-200)	47256, 106.261[146159, 151206, 139863]/11/01/2003, N258, PSDTX402M4
ULC-SEP7	ULC OIL-WATER SEPARATOR 7 (EPN W-07)	47256, N258, PSDTX402M4
UU3 301-D	UU3 REACTOR	47256, N258, PSDTX402M4
UU3 302-D	UU3 REACTOR	47256, N258, PSDTX402M4
UU3 303-D	UU3 REACTOR	47256, N258, PSDTX402M4
UU3 304-D	UU3 REACTOR	47256, N258, PSDTX402M4
UU3 305-D	UU3 REACTOR	47256, N258, PSDTX402M4
UU3 305-E	UU3 DISTILLATION COLUMN	47256, N258, PSDTX402M4
UU3 305-F	UU3 DISTILLATION COLUMN	47256, N258, PSDTX402M4
UU3 306-D	UU3 REACTOR	47256, N258, PSDTX402M4
UU3 307-E	UU3 DISTILLATION COLUMN	47256, N258, PSDTX402M4
UU3 310-E	UU3 DISTILLATION COLUMN	47256, N258, PSDTX402M4
UU3 311-E	UU3 DISTILLATION COLUMN	47256, N258, PSDTX402M4
UU3 BYPASS	UU3 BYPASS	47256, N258, PSDTX402M4
UU3 NACT	UU3 NACT TOTE (EPN UU3NT)	47256, N258, PSDTX402M4
UU3-161A	UU3-310A/310BB/311BA/311BB/312BA/312BB/312BC VENT	149517, 47256, N258, PSDTX402M4

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
UU3-301BA	ULTRAFORMER NO. 3 (EPN 161)	47256, N258, PSDTX402M4
UU3-301BB	HEATER UU3-301BB (EPN 161)	47256, N258, PSDTX402M4
UU3-301BC	HEATER UU3-301BC (EPN 161)	47256, N258, PSDTX402M4
UU3-301BD	HEATER UU3-301BD (EPN 161)	47256, N258, PSDTX402M4
UU3-301BN	UU3-301BA/BB/BC/BD COMMON VENT N STACK (EPN 161)	47256, N258, PSDTX402M4
UU3-301BS	UU3-301BA/BB/BC/BD COMMON VENT S STACK (EPN 161)	47256, N258, PSDTX402M4
UU3-302BA	ULTRAFORMER NO.3 HEATER (EPN 162)	47256, 97907, N258, PSDTX402M4
UU3-302BB	ULTRAFORMER NO.3 HEATER (EPN 162)	47256, 97907, N258, PSDTX402M4
UU3-302BC	ULTRAFORMER NO.3 HEATER (EPN 162)	47256, 97907, N258, PSDTX402M4
UU3-302BN	UU3-301BA/BB/BC/BD COMMON VENT N STACK (EPN 162)	47256, N258, PSDTX402M4
UU3-302BS	UU3-302BA/BB/BC COMMON VENT S STACK (EPN 162)	47256, N258, PSDTX402M4
UU3-306B	ULTRAFORMER NO. 3 (EPN 167)	47256, N258, PSDTX402M4
UU3-307BA	307-BA DESULFURIZER FURNACE (EPN 168)	47256, N258, PSDTX402M4
UU3307BABB	UU3-307BA/BB COMMON VENT (EPN 168)	47256, N258, PSDTX402M4
UU3-307BB	307BB DESULFURIZER (EPN 168)	47256, N258, PSDTX402M4
UU3-308B	FURNACE STACK 308B (EPN 169)	47256, N258, PSDTX402M4
UU3-308BN	UU3-308B VENT NORTH STACK (EPN 169)	47256, N258, PSDTX402M4
UU3-308BS	UU3-308B VENT SOUTH STACK (EPN 169)	47256, N258, PSDTX402M4
UU3-309B	UU3 309-B PROCESS HEATER (EPN 165A)	47256, N258, PSDTX402M4
UU3-310BA	UU3-310BA PROCESS HEATER (EPN 161A, FIN 310BA)	47256, N258, PSDTX402M4
UU3-310BB	UU3-310BB PROCESS HEATER (EPN 161A, FIN 310BB)	47256, N258, PSDTX402M4

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
UU3-311BA	UU3-311BA PROCESS HEATER (EPN 161A, FIN 311BA)	47256, N258, PSDTX402M4
UU3-311BB	UU3-311BB PROCESS HEATER (EPN 161A, FIN 311BB)	47256, N258, PSDTX402M4
UU3-312BA	UU3-312BA PROCESS HEATER (EPN 161A, FIN 312BA)	47256, N258, PSDTX402M4
UU3-312BB	UU3-312BB PROCESS HEATER (EPN 161A, FIN 312BB)	47256, N258, PSDTX402M4
UU3-312BC	UU3-312BC PROCESS HEATER (EPN 161A, FIN 312BC)	47256, N258, PSDTX402M4
UU3-313B	UU3 313-B PROCESS HEATER (EPN 164A)	47256, N258, PSDTX402M4
UU3-CT	UU3 COOLING TOWER (EPN 421)	47256, N258, PSDTX402M4
UU3-FUG1	UU3 FUGITIVES (EPN-160)	47256, 106.261[146159, 146680, 151206, 139863]/11/01/2003, N258, PSDTX402M4
UU3-SEP12	UU3 OIL-WATER SEPARATOR 12 (EPN W-12)	47256, N258, PSDTX402M4
UU3	ULTRAFORMER UNIT NO. 3	47256, N258, PSDTX402M4
UU3W-OWS	UU3 OIL-WATER SEPARATOR 13 (EPN W-13)	47256, N258, PSDTX402M4
UU4 BYPASS	UU4 BYPASS	6488
UU4 D-401	UU4 REACTOR	6488
UU4 D-402	UU4 REACTOR	6488
UU4 D-403	UU4 REACTOR	6488
UU4 D-404	UU4 REACTOR	6488
UU4 D-405	UU4 REACTOR	6488
UU4 D-406	UU4 REACTOR	6488
UU4 E-404	UU4 DISTILLATION COLUMN	6488
UU4 E-405	UU4 DISTILLATION COLUMN	6488

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
UU4 E-408	UU4 DISTILLATION COLUMN	6488
UU4-B401A	PREHEAT FURNACE (EPN 211)	6488
UU4-B401B	ULTRAFORMER NO. 4 (EPN 212)	6488
UU4B402ABC	UU4-B402A/B/C COMMON VENT (EPN 213) (EPN 213)	6488
UU4-B402A	ULTRAFORMER NO. 4 (EPN 213)	6488
UU4-B402B	HEATER UU4-B402B (EPN 213)	6488
UU4-B402C	HEATER UU4-B402C (EPN 213)	6488
UU4-B404	ULTRAFORMER NO. 4 (EPN 215)	6488
UU4-B405	ULTRAFORMER NO. 4 (EPN 216)	6488
UU4-B406	ULTRAFORMER NO. 4 (EPN 218)	6488
UU4-CTW	UU4 COOLING TOWER (EPN 422)	6488
UU4-FUG1	ULTRAFORMER 4 FUGITIVES 1 (EPN F-210)	6488, 106.261[139765, 146158, 151208]/11/01/2003
UU4-SEP1	UU4 OIL-WATER SEPARATOR 1 (EPN W-01)	47256, N258, PSDTX402M4
UU4	ULTRAFORMER UNIT NO. 4	6488
VEH GAS TK	GASOLINE STORAGE TANK	106.412/09/04/2000
VEHGASTK	VEHICLE FUELING STATION TANK	106.473/09/04/2000
WIFCMP	WIF COMPRESSOR (EPN WIF COMP)	106.512[131706]/06/13/2001

Schedules

Compliance Schedule **893**

Compliance Schedule

A. Compliance Schedule				
1. Specific Non-Compliance Situation				
Unit/Group/ Process ID. No(s).	**SOP Index No.**	**Pollutant**	**Applicable Requirement**	
			Citation	**Text Description**
TCH-AU2		VOC	Permit 2612, SC 1	This permit authorizes emissions from those points listed in the attached table entitled “Emission Sources - Maximum Allowable Emission Rates”

2. Compliance Status Assessment Method and Records Location		
Compliance Status Assessment Method		**Location of Records/Documentation**
Citation	**Text Description**	
Permit 2612, SC 1	The attached table entitled “Emission Sources - Maximum Allowable Emission Rates	Records located on site

3. Non-compliance Situation Description
TCH-AU2 intermittently exceeds the VOC lb/hr limit listed in the MAERT table.
4. Corrective Action Plan Description
Blanchard submitted an amendment on 1/29/2016 to incorporate an increased VOC limit for TCH-AU2.
5. List of Activities/Milestones to Implement the Corrective Action Plan

1	Blanchard will submit deviation on deviation report when source exceeds MAERT limit until amendment is issued.

6. Previously Submitted Compliance Plan(s)	Type of Action	Date Submitted
	N/A	

7. Progress Report Submission Schedule	Progress report will be submitted with Title V deviation report

Compliance Schedule

A. Compliance Schedule				
1. Specific Non-Compliance Situation				
Unit/Group/ Process ID. No(s).	**SOP Index No.**	**Pollutant**	**Applicable Requirement**	
			Citation	**Text Description**
Site-wide		VOC	60.690	Determine compliance for NSPS QQQ for refinery wastewater systems.

2. Compliance Status Assessment Method and Records Location		
Compliance Status Assessment Method		**Location of Records/Documentation**
Citation	**Text Description**	
60.690	Determine compliance for NSPS QQQ for refinery wastewater systems.	On-site

3. Non-compliance Situation Description
Sections of the refinery sewer systems have triggered NSPS QQQ control standards but have not been upgraded to meet the standards.
4. Corrective Action Plan Description
Blanchard will meet the applicable requirements for subject facilities post modification, by re-routing of drains, control components, or a combination of these.
5. List of Activities/Milestones to Implement the Corrective Action Plan

1	Blanchard entered into a Consent Decree on November 4, 2013 with US EPA that outlines corrective actions to bring the sections of the refinery wastewater system into compliance with NSPS QQQ controls by December 31, 2019.
2	Blanchard will submit deviation reports until compliance is achieved.

6. Previously Submitted Compliance Plan(s)	**Type of Action**	**Date Submitted**
	N/A	

7. Progress Report Submission Schedule	Semi-annual with submittal of Title V deviation report

Compliance Schedule

A. Compliance Schedule				
1. Specific Non-Compliance Situation				
Unit/Group/ Process ID. No(s).	**SOP Index No.**	**Pollutant**	**Applicable Requirement**	
			Citation	**Text Description**
TCH-6	60A-0003	VOC	60.18(c)(5)	Air-assisted flares shall be operated with an exit velocity less than Vmax.

2. Compliance Status Assessment Method and Records Location		
Compliance Status Assessment Method		**Location of Records/Documentation**
Citation	**Text Description**	
60.18(c)(5)	Torch 6 is a pressure-assisted ground flare that is designated to operate at higher velocities than standard elevated steam-assisted, air-assisted, or non-assisted flares. The pressure-assisted burners can achieve proper combustion efficiency even though the velocity is greater than Vmax. 40 CFR 60.18 was not written with pressure assisted ground flare technology in mind	Data including supporting documentation maintained onsite.

3. Non-compliance Situation Description
Failure to maintain exit velocity less than Vmax per the methodology in 60.18 for pressure-assisted ground flares.

4. Corrective Action Plan Description
The prior owner previously submitted an alternative means of control (AMOC) plan to TCEQ for approval. Recently, EPA Region 6 has indicated that the approval of alternative compliance parameters for pressure assisted flares is not delegable to the states. As a result, Blanchard will submit an Alternate Means of Emission Limitation (AMEL) to EPA by December 31, 2016.

5. List of Activities/Milestones to Implement the Corrective Action Plan	
1	Blanchard shall pursue approval from EPA of an alternative emissions standard that addresses alternative compliance parameters for Torch 6. Blanchard shall submit an Alternate Means of Emissions Limitation (AMEL) to EPA by December 31, 2016. Blanchard submitted an AMEL on 10/17/2016, and an AMOC was submitted to TCEQ on 12-5-2016. [AMOC issued by TCEQ on 2/21/2018; AMEL published in Federal Register on April 25, 2018.]
2	Blanchard will submit deviation reports until compliance is achieved.

6. Previously Submitted Compliance Plan(s)	Type of Action	Date Submitted
	N/A	

7. Progress Report Submission Schedule	Semi-annual with submittal of Title V deviation report

Compliance Schedule

A. Compliance Schedule				
1. Specific Non-Compliance Situation				
Unit/Group/ Process ID. No(s).	**SOP Index No.**	**Pollutant**	**Applicable Requirement**	
			Citation	**Text Description**
TCH-6	63A-0003	VOC	63.11(b)(8)	Air-assisted flares shall be operated with an exit velocity less than Vmax.

2. Compliance Status Assessment Method and Records Location		
Compliance Status Assessment Method		**Location of Records/Documentation**
Citation	**Text Description**	
63.11(b)(8)	Torch 6 is a pressure-assisted ground flare that is designated to operate at higher velocities than standard elevated steam-assisted, air-assisted, or non-assisted flares. The pressure-assisted burners can achieve proper combustion efficiency even though the velocity is greater than Vmax. 40 CFR 60.18 was not written with pressure assisted ground flare technology in mind	Data including supporting documentation maintained onsite.

3. Non-compliance Situation Description
Failure to maintain exit velocity less than Vmax per the methodology in 63.11(b)(8) for ground flares.

4. Corrective Action Plan Description
The prior owner previously submitted an alternative means of control (AMOC) plan to TCEQ for approval. Recently, EPA Region 6 has indicated that the approval of alternative compliance parameters for pressure assisted flares is not delegable to the states. As a result, Blanchard will. submit an Alternate Means of Emission Limitation (AMEL) to EPA by December 31, 2016.

5. List of Activities/Milestones to Implement the Corrective Action Plan	
1	Blanchard shall pursue approval from EPA of an alternative emissions standard that addresses alternative compliance parameters for Torch 6. Blanchard shall submit an Alternate Means of Emissions Limitation (AMEL) to EPA by December 31, 2016. Blanchard submitted an AMEL on 10/17/2016, and an AMOC was submitted to TCEQ on 12-5-2016. [AMOC issued by TCEQ on 2/21/2018; AMEL published in Federal Register on April 25, 2018.]
2	Blanchard will submit deviation reports until compliance is achieved.

6. Previously Submitted Compliance Plan(s)	Type of Action	Date Submitted
	N/A	

7. Progress Report Submission Schedule	Semi-annual with submittal of Title V deviation report

Compliance Schedule

A. Compliance Schedule				
1. Specific Non-Compliance Situation				
Unit/Group/ Process ID. No(s).	**SOP Index No.**	**Pollutant**	**Applicable Requirement**	
			Citation	**Text Description**
PRO-SRU			Permit 47256 SC25	The sour water stripper system feeding the SRU shall have a minimum on-line retention and separation (hold up) time of 3 days based on normal operational levels and maximum expected feed rates.

2. Compliance Status Assessment Method and Records Location		
Compliance Status Assessment Method		**Location of Records/Documentation**
Citation	**Text Description**	
Permit 47256, SC 25	Evaluation of the sour water stripper system retention time based on normal operational levels and maximum expected feed rates.	Detailed documentation of specific compliance/non-compliance activities is located on-site

3. Non-compliance Situation Description
During a review of the sour water stripper feed system, Blanchard discovered the sour water stripper feed system does not meet the minimum three (3) day retention time at normal operation levels and maximum expected feed rates as specified in the permit Special Condition 25.

4. Corrective Action Plan Description
Blanchard will propose an alternative compliance parameter to the three (3) day minimum retention time contained in Special Condition 25.

5. List of Activities/Milestones to Implement the Corrective Action Plan	
1	Blanchard submitted a permit amendment on June 23, 2015 to Permit 47256 to modify Special Condition 25 that provides the justification that the existing sour water stripper system is equivalent BACT in lieu of the 3 day on-line retention and separation time.
2	Blanchard will submit deviation reports until compliance is achieved.

6. Previously Submitted Compliance Plan(s)	Type of Action	Date Submitted
	N/A	

7. Progress Report Submission Schedule	Semi-annual with submittal of Title V deviation report

Alternative Requirement

Alternative Requirement..... 899

ENTAL

anchard Refin.in
01 5th Avenue

RE: Blanchard Refining Company, LLC – Galveston Bay Refinery (Blachard)
Fluidized Catalytic Cracking Unit Number 3 (FCCU 3) Wet Gas Scrubber (WGS)
Alternative Monitoring Plan (AMP)

Dear Mr. Marra:

This letter is in response to your AMP dated September 12, 2014, which included data from the testing of two conditions for the FCCU3 WGS performed June 10-17, 2014. After reviewing your AMP, the design of the BELCO WGS, and the performance test report, the Environmental Protection Agency (EPA) Region 6 approves the following operating parameter limits (OPLs) for your WGS:

luding

Sincerely,

Steve Thompson
Director

Bryan W. Shaw, Ph.D., P.E., *Chairman*
Toby Baker, *Commissioner*
Jon Niermann, *Commissioner*
Richard A. Hyde, P.E., *Executive Director*

TEXAS COMMISSION ON ENVIRONMENTAL QUALITY

Protecting Texas by Reducing and Preventing Pollution

March 30, 2018

MR ERIC R KAYSEN, P.E.
ENVIRONMENTAL SUPERVISOR
BLANCHARD REFINING COMPANY LLC
GALVESTON BAY REFINERY
P O BOX 401
2401 5TH AVENUE SOUTH
TEXAS CITY TX 77592

Re: Alternative Method of Control (AMOC) No.: 2
Blanchard Refining Company, LLC
Multi-Point Ground-level Flare (MPGF) System
Galveston Bay Refinery
Texas City, Galveston County
Regulated Entity Number: RN102535077
Customer Reference Number: CN604166868
Affected Permit: 9606 and O0541

Dear Mr. Kaysen:

This letter corrects a minor typographical error regarding the Permit No. referenced on page 2. Please replace this letter with the one dated February 21, 2018 and attach it to the AMOC Plan sent on that date. Dates and references below have been also updated to reflect the date of this letter and the original final approval of the AMOC on February 21, 2018.

The Executive Director of the Texas Commission on Environmental Quality (TCEQ) has made a final decision to approve Blanchard Refining Company LLC's (Blanchard's) above-referenced Alternate Means of Control (AMOC) Plan for the construction and use of a multi-point ground flare (MPGF) system to control emissions from limited high-pressure maintenance, startup, and shutdown events as well emergency situations. This AMOC Plan will allow the Galveston Bay Refinery (GBR) to use the MPGF system with the specified provisions as an alternative to complying with the following:

General Applicability	Standards & Requirements
Subchapter B; Division 2; Vent Gas Control	§115.122(a)(1)-(2)
Subchapter D; Division 1; Process Unit Turnaround	§115.312(a)
Subchapter D; Division 3; Fugitive Emissions	§115.352
Subchapter H; Division 1; HRVOC Vent Gas Control	§115.722
Subchapter H; Division 3; HRVOC Fugitives	§115.781

During the required public comment period, no comments were received.

The TCEQ has been delegated authority to enforce the above cited standards and is authorized to approve this AMOC. You are reminded that approval of any AMOC shall not abrogate the Executive Director or Administrator's authority under the Act or in any way prohibit later canceling the AMOC.

The authorized AMOC Plan and Provisions were sent by certified mail on February 21, 2018.

You are reminded per §115.913(c) that all representations with regard to this AMOC application and Plan become conditions upon which the AMOC is approved and varying from these representations is not allowed if the change will cause a change in the method of control of emissions, the character of the emissions, result in an increase in the discharge of the various emissions, emission limits, control requirements, monitoring, testing, reporting, or recordkeeping requirements.

Please note you had an opportunity to appeal the Executive Director's determination on the AMOC Plan to the commission within 15 days from February 21, 2018 under § 115.914(7). Also, under § 115.914(8), the EPA has 45 days from February 21, 2018 to inform the Air Permits Division that it disapproves the AMOC Plan. Following § 115.914(9)-(11), the AMOC plan will become effective with the latter of either EPA acceptance of, or the Commission's issuance of the AMOC plan. Once effective, the AMOC becomes part of the State Implementation Plan.

This AMOC approval may supersede certain requirements or representations in Permit No. 9606. To ensure effective and consistent enforceability, we request that Blanchard incorporate this AMOC into the permit through submittal of an alteration no later than 90 days after February 21, 2018.

This AMOC Plan and Provisions change applicable requirements for the site, including existing monitoring, reporting, recordkeeping, and testing requirements which has implications for the applicability of any Site Operating Permit (SOP) requirements. We request that Blanchard update the appropriate SOP referenced above to incorporate this AMOC Plan and Provisions.

If you need further information or have any questions, please contact Ms. Anne Inman, P.E. at (512) 239-1276 or write to the Texas Commission on Environmental Quality, Office of Air, Air Permits Division, MC-163, P.O. Box 13087, Austin, Texas 78711-3087.

This action is taken under authority delegated by the Executive Director of the TCEQ.

Sincerely,

Michael Wilson, P.E., Director
Air Permits Division
Office of Air
Texas Commission on Environmental Quality

cc: Mr. John Bigham, Refining Environmental Technologist, Blanchard Refining Company
Mr. Bharat Contractor, Blanchard Refining Company
Air Permits Section Chief, New Source Review Section (6PD-R), U.S. Environmental Protection Agency, Region 6, Dallas
Ms. Lori FitzSimmons-Evans, Program Manager, Galveston County Health District
Air Section Manager, Region 12 - Houston
Sam Short, Manager, Energy/Combustion Section, Air Permits Division, OA: MC-163
Jesse Chacon, Manager, Operating Permits Section, Air Permits Division, OA: MC-163

Project Number: 137959

TEXAS COMMISSION ON ENVIRONMENTAL QUALITY

Alternative Method of Control (AMOC) Plan
AMOC No.: AMOC-2
Blanchard Refining Company LLC
Galveston Bay Refinery Multi-Point Ground Flare (MPGF) System
Galveston, Galveston County
Regulated Entity Number: RN102535077

A. This AMOC Plan Authorization shall apply at the Blanchard Refining Company LLC, Galveston Bay Refinery (GBR) located in Galveston, Galveston County. This site is identified by Regulated Entity Number RN102535077. Under Title 30 Texas Administrative Code Section 115.910 (30 TAC § 115.910) GBR is authorized for the high pressure stages of a multi-point ground flare (MPGF) system for use during high-pressure emission events such as planned maintenance, start-ups and shut-downs (MSS) as well as unplanned emergency and upset situations.

B. A copy of the AMOC application and the AMOC Plan provisions must be kept on-site or at a centralized location and made available at the request of personnel from the TCEQ or any pollution control agency with jurisdiction. The AMOC application is defined by the application initially received September 1, 2006 and all technical information received as of December 12, 2016, and supporting documentation submitted through December 6, 2017.

C. This authorization is granted under § 115.910 for emissions sources regulated by 30 TAC Chapter 115:
   1. Subchapter B: General Volatile Organic Compound Sources, Division 2: Vent Gas Control;
   2. Subchapter D: Petroleum Refining, Natural Gas Processing, and Petrochemical Processes, Division 1: Process Unit Turnaround;
   3. Subchapter D: Petroleum Refining, Natural Gas Processing, and Petrochemical Processes, Division 3: Fugitive Emissions;
   4. Subchapter H: Highly Reactive Volatile Organic Compounds (HRVOC), Division 1: Vent Gas Control; and
   5. Subchapter H: HRVOC, Division 3: Fugitives.

   This AMOC shall apply in lieu of the requirements §§ 115.122(a)(1)-(2), 115.312(a), 115.352, 115.722, and 115.781, as applicable.

   Compliance with this AMOC is independent of GBR's obligation to comply with all other applicable requirements of 30 TAC Chapter 115, TCEQ permits and applicable state and federal law. The monitoring and testing requirements of 30 TAC Chapter 115 shall continue to apply. Compliance with the requirements of this plan does not assure compliance with requirements of an applicable New Source Performance Standard, applicable National Emission Standard for Hazardous Air Pollutants, or an Alternative Means of Emission Limitation (AMEL) and does not constitute approval of alternative standards for these regulations. If an AMEL is finalized by the U.S. Environmental Protection Agency (EPA), within 90 days this AMOC shall be revised for any changes needed for consistency.

D. In accordance with 30 TAC § 115.913(c), all representations submitted for this plan, as well as the provisions listed here, become conditions upon which this AMOC Plan is issued. It is unlawful to vary from the emission limits, control requirements, monitoring, testing, reporting or recordkeeping requirements of this Plan.

E. The high pressure stages of the MPGF system identified as EPN Flare 6 and is authorized under Permit No. 9606 and subject to this AMOC plan. The system collects and combusts hydrocarbon streams during high pressure MSS activities and emergencies. Operations of the pressure-assisted MPGF will achieve a reduction in emissions at least equivalent to the reduction in emissions being controlled by a steam-assisted, air-assisted, or non-assisted flare complying with the requirements of §§ 115.122(a)(1)-(2), 115.312(a), 115.352, 115.722, 115.781, 40 CFR 63.11(b), or 40 CFR 60.18(b).

F. The high pressure MPGF system stages must be designed and operated such that the following are met:

1. Operating Requirements: For Stages 2 through 8, the net heating value of the flare vent gas combustion zone (*NHVcz*) is greater than or equal to 600 British thermal units per standard cubic foot (Btu/scf); or the combustion zone gas lower flammability limit (*LFLcz*) is less than or equal to 6.5 percent by volume.

   The owner or operator must demonstrate compliance with the *NHVcz* or *LFLcz* metric by continuously complying with a 15-minute block average. The operator must calculate and monitor for the *NHVcz* or *LFLcz* according to the following:

   a. Calculation of *NHVcz*

      i. The owner or operator shall determine the net heating value using the following equation:

$$NHV_{vg} = \sum_{i=1}^{n} x_i \, NHV_i$$

Where:

NHVvg = Net heating value of flare vent gas, British thermal units per standard cubic foot (Btu/scf).

Flare vent gas means all gas found just prior to the MPGF. This gas includes all flare waste gas (*i.e.*, gas from facility operations that is directed to a flare for the purpose of disposing of the gas), flare sweep gas, flare purge gas and flare supplemental gas, but does not include pilot gas.

i = Individual component in flare vent gas.

n = Number of components in flare vent gas.

x_i = Concentration of component i in flare vent gas, volume percent (vol %).

NHV_i = Net heating value of component i determined as the heat of combustion where the net enthalpy per mole of offgas is based on combustion at 25 degrees Celsius (°C) and 1 atmosphere (or constant pressure) with water in the gaseous state from values published in the literature, and then the values converted to a volumetric basis using 20 °C for "standard temperature." Table 1 (Appendix) summarizes component properties including net heating values.

      ii. For MPGF Stages 2 - 8, *NHVvg* = *NHVcz*.

b. Calculation of *LFLcz*

i. The owner or operator shall determine *LFLcz* from compositional analysis data by using the following equation:

$$LFL_{vg} = \frac{1}{\sum_{i=1}^{n}\left[\frac{X_i}{LFL_i}\right]} * 100\ \%$$

Where:

LFLvg = Lower flammability limit of flare vent gas, volume percent (vol %)

n = Number of components in the vent gas.

i = Individual component in the vent gas.

χi = Concentration of component i in the vent gas, vol %.

LFLi = Lower flammability limit of component *i* as determined using values published by the U.S. Bureau of Mines (Zabetakis, 1965), vol %. All inerts, including nitrogen, are assumed to have an infinite LFL (*e.g., LFLN2* = ∞, so that c*N2/ LFLN2* = 0). LFL values for common flare vent gas components are provided in Table 1 (Appendix).

ii. For MPGF Stages 2 - 8, *LFLvg* = *LFLcz*.

c. The operator shall install, operate, calibrate and maintain a monitoring system capable of continuously measuring flare vent gas volumetric flow rate (Qvg).

i. The flow rate monitoring system must be able to correct for the temperature and pressure of the system and output parameters in standard conditions (i.e., a temperature of 20 degrees C (68 ° F) and a pressure of 1 atmosphere).

ii. Mass flow monitors may be used for determining volumetric flow rate of flare vent gas provided the molecular weight of the flare vent gas is determined using compositional analysis so that the mass flow rate can be converted to volumetric flow at standard conditions using the following equation:

$$Qvol = \frac{Qmass\ x\ 385.3}{MWt}$$

Where:

Qvol = volumetric flow rate in scf per second (scf/s).

Qmass = mass flow rate in pounds per second (lb/s)

385.3 = conversion factor scf per pound-mole

MW_t = molecular weight of the gas at the flow monitoring location, pounds per pound-mole

d. The operator shall install, operate, calibrate and maintain a monitoring system capable of continuously measuring (*i.e.,* at least once every 15-minutes), calculating, and recording the individual component concentrations present in the flare vent gas or install, operate, calibrate and maintain a monitoring system capable of continuously measuring, calculating and recording *NHVvg* (in Btu/scf).

e. For each measurement produced by the monitoring system, the operator shall determine the 15-minute block average as the arithmetic average of all measurements made by the monitoring system within the 15-minute period.

f. The operator must follow the calibration and maintenance procedures according to Table 2 (Appendix). Monitor downtime associated with maintenance periods, instrument adjustments or checks to maintain precision and accuracy. Zero and span adjustments may not exceed 5 percent of the time the flare is receiving regulated material. Calibration and maintenance procedures conducted when the flare is not receiving regulated material are excluded from the monitor downtime calculation.

2. Pilot Flame Requirements: The MPGF system shall be operated with a flame present at all times when in use. Each of Stages 2 – 8 burners must be equipped with at least two pilots with a continuously lit pilot flame.

   The pilot flame(s) must be continuously monitored by a thermocouple or any other equivalent device used to detect the presence of a flame. The time, date and duration of any complete loss of pilot flame on any stage of MPGF burners must be recorded. Each monitoring device must be maintained or replaced at a frequency in accordance with the manufacturer's specifications.

3. Visible Emission Requirements: When the flare is receiving regulated material, the MPGF system shall be operated with no visible emissions except for periods not to exceed a total of 5 minutes during any 2 consecutive hours. A video camera that is capable of continuously recording (*i.e.,* at least one frame every 15 seconds with time and date stamps) images of the flare flame and a reasonable distance above the flare flame at an angle suitable for visible emissions observations must be used to demonstrate compliance with this requirement. The owner or operator must provide real-time video surveillance camera output to the control room or other continuously manned location where the video camera images may be viewed at any time.

4. Monitor Requirements: The operator of a MPGF system shall install and operate pressure monitor(s) on the main flare header, as well as a valve position indicator monitoring system for each staging valve to ensure that the MPGF operates within the range of tested conditions or within the range of the manufacturer's specifications. The pressure monitor shall meet the requirements in Table 2 (Appendix). An interim monitoring system is approved and shall meet the requirements in Table 2 (Appendix). The interim monitoring must meet the following compliance schedule and semi-annual status reports sent to the TCEQ regional office:

   a. Start design engineering no later than December 31, 2017;
   b. Begin construction no later than September 30, 2019;
   c. End of interim monitoring no later than June 30, 2020.

   Monitor downtime associated with maintenance periods, instrument adjustments or checks to maintain precision and accuracy and zero and span adjustments may not exceed 5 percent of the time the flare is receiving regulated material. Calibration and maintenance procedures conducted when the flare is not receiving regulated material are excluded from the monitor downtime calculation.

5. Recordkeeping Requirements: All data must be recorded and maintained for a minimum of five years or for as long as applicable rule subpart(s) specify flare records should be kept, whichever is longer. Records must be maintained onsite and made available upon request by authorized representatives of the executive director, U.S. EPA, and any local air pollution control agency with jurisdiction.

6. Reporting Requirements

   a. The information specified in (b) and (c) below should be reported in the timeline specified by the applicable rules for which the MPGF will control emissions.

   b. Owners or operators should include the following information in their initial Notification of Compliance status report:

      i. Specify flare design as a MPGF with clear notations that Stages 2- 8 are pressure assisted.

      ii. All visible emission readings, *NHVcz* and/or *LFLcz* determinations, and flow rate measurements. For MPGF, exit velocity determinations do not need to be reported.

      iii. All periods during the compliance determination when a complete loss of pilot flame on any stage of MPGF burners occurs.

      iv. All periods during the compliance determination when the pressure monitor(s) on the main flare header show the MPGF burners operating outside the range of tested conditions or outside the range of the manufacturer's specifications.

      v. All periods during the compliance determination when the staging valve position indicator monitoring system indicates a stage of the MPGF should not be in operation, but is; or when a stage of the MPGF should be in operation, but is not.

   c. The owner or operator shall notify the executive director of periods of excess emissions in their Title V Periodic Reports. These periods of excess emissions shall include:

      i. Each 15-minute block during which there was at least one minute when regulated material was routed to the MPGF and a complete loss of pilot flame on Stages 2 - 8 occurred.

      ii. Periods of visible emissions events that are time and date stamped and exceed more than 5 minutes in any 2 hour consecutive period.

      iii. Each 15-minute block period for which an applicable combustion zone operating limit (*i.e., NHVcz* or *LFLcz*) is not met for the MPGF when regulated material is being combusted in the flare. Indicate the date and time for each period, the *NHVcz* and/or *LFLcz* operating parameter for the period, the type of monitoring system used to determine compliance with the operating parameters (*e.g.,* gas chromatograph or calorimeter), and the MPGF stages which were in use.

      iv. Periods when the pressure monitor(s) on the main flare header show the MPGF burners are operating outside the range of tested conditions or outside the range of the manufacturer's specifications. Indicate the date and time for each period, the pressure measurement, the stage(s) and number of MPGF burners affected and the range of tested conditions or manufacturer's specifications.

      v. Periods when the staging valve position indicator monitoring system indicates a stage of the MPGF should not be in operation, but is; or when a stage of the MPGF should be in operation, but is not. Indicate the date and time for each period, whether the stage was supposed to be open but was closed or vice versa and the stage(s) and number of MPGF burners affected.

APPENDIX Table 1 — Individual Component Properties

Component	Molecular Formula	MWi (lb/ lb mol)	NHVi (Btu/scf)	LFLi (volume %)
Acetylene	C2H2	26.04	1,404	2.5
Benzene	C6H6	78.11	3,591	1.3
1,2- Butadiene	C4H6	54.09	2,794	2.0
1,3- Butadiene	C4H6	54.09	2,690	2.0
iso-Butane	C4H10	58.12	2,957	1.8
n-Butane	C4H10	58.12	2,968	1.8
cis-Butene	C4H8	56.11	2,830	1.6
iso-Butene	C4H8	56.11	2,928	1.8
trans-Butene	C4H8	56.11	2,826	1.7
Carbon Dioxide	CO2	44.01	0	∞
Carbon Monoxide	CO	28.01	316	12.5
Cyclopropane	C3H6	42.08	2,185	2.4
Ethane	C2H6	30.07	1,595	3.0
Ethylene	C2H4	28.05	1,477	2.7
Hydrogen	H2	2.02	274 or 1,212 (1)	4.0
Hydrogen Sulfide	H2S	34.08	587	4.0
Methane	CH4	16.04	896	5.0
MethylAcetylene	C3H4	40.06	2,088	1.7
Nitrogen	N2	28.01	0	∞
Oxygen	O2	32.00	0	∞
Pentane+ (C5+)	C5H12	72.15	3,655	1.4
Propadiene	C3H4	40.06	2,066	2.16
Propane	C3H8	44.10	2,281	2.1
Propylene	C3H6	42.08	2,150	2.4
Water	H2O	18.02	0	∞

(1) A hydrogen net heating value of 1,212 btu/scf shall be used for determining compliance with the Combustion Zone Net Heating Value. A net heating value of 274 btu/scf will be used to determine compliance with vent gas net heating value. This is the same as Table 12 of Appendix to 40 CFR 63 Subpart CC.

APPENDIX Table 2 — Accuracy and Calibration Requirements

Parameter	Accuracy requirements	Calibration requirements
Flare Vent Gas Flow Rate	±20 percent of flow rate at velocities ranging from 0.1 to 1 feet per second. ±5 percent of flow rate at velocities greater than 1 foot per second.	Performance evaluation biennially (every two years) and following any period of more than 24 hours throughout which the flow rate exceeded the maximum rated flow rate of the sensor, or the data recorder was off scale. Checks of all mechanical connections for leakage monthly. Visual inspections and checks of system operation every 3 months, unless the system has a redundant flow sensor. Select a representative measurement location where swirling flow or abnormal velocity distributions due to upstream and downstream disturbances at the point of measurement are minimized.
Pressure	±5 percent over the normal range measured or 0.12 kilopascals (0.5 inches of water column), whichever is greater.	Review pressure sensor readings (header and staging valve pressure transmitters) at least once a week for straight-line (unchanging) pressure and perform corrective action to ensure proper pressure sensor operation if blockage is indicated. Performance evaluation annually and following any period of more than 24 hours throughout which the pressure exceeded the maximum rated pressure of the sensor, or the data recorder was off scale. Checks of all mechanical connections for leakage monthly. Visual inspection of all components for integrity, oxidation and galvanic corrosion every 3 months, unless the system has a redundant pressure sensor. Select a representative measurement location that minimizes or eliminates pulsating pressure, vibration, and internal and external corrosion. Interim provisions: 1. Record the control system (DCS) command signals to open an individual staging valve and keep a history of the commands in a database: 2. Record the control system (DCS) command signals to close an individual staging valve and keep a history of the commands in a database; 3. Record the control system (DCS) alarm for when the common valve open alarm and no staging valve command to open was given; and 4. Record common alarm when flare header pressure is in range to open or close a staging valve and no command to open or close is given. a. When the pressure goes above 27 psig but below 30 psig and no valves commanded open, a "Fail to Stage Open Flare Valve" alarm will annunciate. b. When pressure goes above 30 psig and not all of the staging valves are commanded open, a "At Max Pressure, Not all valves commanded Open" alarm will annunciate. c. When pressure goes below 20 psig and not all valves are commanded closed, a "Not all staging valves commanded closed" alarm will annunciate.

Temperature	±1 percent over the normal range of temperature measured, expressed in degrees Celsius (C), or 2.8 degrees C, whichever is greater	See Table 13 – Calibration and Quality Control Requirements for CPMS 40 CFR 63, Subpart CC Appendix
Net Heating Value by Calorimeter	±2 percent of span	Calibration requirements should follow manufacturer's recommendations at a minimum. Temperature control (heated and/or cooled as necessary) the sampling system to ensure proper year-round operation. Where feasible, select a sampling location at least two equivalent diameters downstream from and 0.5 equivalent diameters upstream from the nearest disturbance. Select the sampling location at least two equivalent duct diameters from the nearest control device, point of pollutant generation, air in leakages, or other point at which a change in the pollutant concentration or emission rate occurs.
Net Heating Value by Gas Chromatograph	As specified in Performance Specification 9 of 40 CFR part 60 Appendix B.	Follow the procedure in Performance Specification 9 of 40 CFR Part 60 Appendix B, except that a single daily mid-level calibration check can be used, a triplicate mid-level check weekly, and the multi-point calibration can be conducted quarterly (rather than monthly), and the sampling line temperature must be maintained at a minimum temperature of 60 °C (rather than 120 °C). Net heating value daily validations and quarterly RATA and CGA will be determined by calibration gas net heating value until January 30, 2019, after which it will follow the requirements under 40 CFR 60.670 and 40 CFR 60.671.

APPENDIX 3 — Acronyms and Abbreviations

The AMOC uses multiple acronyms and terms, defined here (please note this list is not exhaustive):

AMEL	alternative means of emission limitation
AMOC	Alternate Method of Compliance or Control
Btu/scf	British thermal units per standard cubic foot
CAA	Clean Air Act
CBI	confidential business information
CFR	Code of Federal Regulations
EPA	Environmental Protection Agency
EPN	Emission Point Number
Eqn	equation
HAP	hazardous air pollutants
HP	high pressure
LFL	lower flammability limit
LFLcz	lower flammability limit of combustion zone gas
LFLvg	lower flammability limit of flare vent gas
MPGF	multi-point ground flares
MSS	planned maintenance, start-ups and shut-downs
NESHAP	National Emission Standards for Hazardous Air Pollutants
NHV	net heating value
NHVcz	net heating value of combustion zone gas
NHVvg	net heating value of flare vent gas
NSPS	New Source Performance Standards
OAQPS	Office of Air Quality Planning and Standards
TAC	Texas Administrative Code
TCEQ	Texas Commission on Environmental Quality
scf	standard cubic feet
VOC	volatile organic compounds

Appendix A

Acronym List 912

Acronym List

The following abbreviations or acronyms may be used in this permit:

ACFM ..... actual cubic feet per minute
AMOC ..... alternate means of control
ARP ..... Acid Rain Program
ASTM ..... American Society of Testing and Materials
B/PA ..... Beaumont/Port Arthur (nonattainment area)
CAM ..... Compliance Assurance Monitoring
CD ..... control device
CEMS ..... continuous emissions monitoring system
CFR ..... Code of Federal Regulations
COMS ..... continuous opacity monitoring system
CVS ..... closed vent system
D/FW ..... Dallas/Fort Worth (nonattainment area)
EP ..... emission point
EPA ..... U.S. Environmental Protection Agency
EU ..... emission unit
FCAA Amendments ..... Federal Clean Air Act Amendments
FOP ..... federal operating permit
gr/100 scf ..... grains per 100 standard cubic feet
HAP ..... hazardous air pollutant
H/G/B ..... Houston/Galveston/Brazoria (nonattainment area)
H_2S ..... hydrogen sulfide
ID No. ..... identification number
lb/hr ..... pound(s) per hour
MACT ..... Maximum Achievable Control Technology (40 CFR Part 63)
MMBtu/hr ..... Million British thermal units per hour
NA ..... nonattainment
N/A ..... not applicable
NADB ..... National Allowance Data Base
NESHAP ..... National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61)
NO_x ..... nitrogen oxides
NSPS ..... New Source Performance Standard (40 CFR Part 60)
NSR ..... New Source Review
ORIS ..... Office of Regulatory Information Systems
Pb ..... lead
PBR ..... Permit By Rule
PEMS ..... predictive emissions monitoring system
PM ..... particulate matter
ppmv ..... parts per million by volume
PRO ..... process unit
PSD ..... prevention of significant deterioration
psia ..... pounds per square inch absolute
SIP ..... state implementation plan
SO_2 ..... sulfur dioxide
TCEQ ..... Texas Commission on Environmental Quality
TSP ..... total suspended particulate
TVP ..... true vapor pressure
U.S.C. ..... United States Code
VOC ..... volatile organic compound

Appendix B

Major NSR Summary Table 914

Major NSR Summary Table

Permit Number: 19599 and PSDTX023			Issuance Date: 11/30/2018				
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Special Condition/ Application Information	Special Condition/ Application Information	Special Condition/ Application Information
46	Oil Water Separator	VOC	5.80	25.00	2, 6, 7	2, 6, 7	6, 7
47	Oil Water Separator	VOC	0.90	4.00	2, 6, 7	2, 6, 7	6, 7
51	101-BA/BB	CO	29.90	109.00	2, 6, 7	2, 6, 7	6, 7
		NO_X	47.62	173.80			
		PM_{10} (6)	3.70	13.60			
		SO_2 (6)	20.10	73.30			
		VOC	1.00	3.80			
53	102-BA/BB	CO	2.45	81.94	2, 6, 7	2, 6, 7	6, 7
		NO_X	10.62	38.75			
		PM_{10} (6)	1.40	5.20			
		SO_2 (6)	7.70	28.00			
		VOC	0.80	3.00			
55	103-B	CO	5.65	24.72	2, 3, 6, 7, 8	2, 3, 6, 7, 8, 12	6, 7, 8
		NO_X	15.80	65.70			
		PM_{10} (6)	2.42	10.61			
		SO_2 (6)	3.80	16.62			
		VOC	0.20	0.87			
56	Oil Water Separator	VOC	4.40	19.00	2, 6, 7	2, 6, 7	6, 7
417	Cooling Tower	VOC	1.26	5.52	2, 4, 6, 7	2, 4, 6, 7, 12	6, 7
F-40	Process Fugitives Pipestill No. 3B (5)	H_2S	0.28	1.24	6, 7, 9	6, 7, 9, 12	6, 7
		VOC	22.36	97.94			
F-50	Process Fugitives Pipestill	H_2S	0.34	1.47	6, 7, 9	6, 7, 9, 12	6, 7

Major NSR Summary Table

Permit Number: 19599 and PSDTX023			Issuance Date: 11/30/2018				
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Special Condition/ Application Information	Special Condition/ Application Information	Special Condition/ Application Information
	No. 3A (5)	VOC	26.65	116.76			

(1) Emission point identification – either specific equipment designation or emission point number from plot plan.
(2) Specific point source name. For fugitive sources, use area name or fugitive source name.
(3) CO - carbon monoxide
H_2S - hydrogen sulfide
NO_X - total oxides of nitrogen
PM_{10} - total particulate matter equal to or less than 10 microns in diameter, including $PM_{2.5}$, as represented
SO_2 - sulfur dioxide
VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1
(4) Compliance with annual emission limits (tons per year) is based on a 12-month rolling period.
(5) Emission rate is an estimate and is enforceable through compliance with the applicable special condition(s) and permit application representations.
(6) PSD-TX-023 pollutant.

Major NSR Summary Table

Permit Number: 47256, N258, and PSDTX402M4					Issuance Date: 11/30/2018		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY (4)	Special Condition/ Application Information	Special Condition/ Application Information	Special Condition/ Application Information
Normal Operations							
See Special Conditions Attachment E	See Special Conditions Attachment E	VOC	1429.67	1475.87	2, 3, 4, 5, 8, 9, 11, 14, 15, 21, 27, 36, 39, 40, 44, 46, 47, 48, 51, 52, 55, 69, 70, 71, 72, 74	2, 3, 4, 5, 8, 9, 10, 11, 14, 15, 21, 24, 27, 36, 39, 40, 44, 46, 47, 48, 51, 52, 55, 56, 69, 70, 71, 72, 74, 77	2, 3, 4, 8, 24, 39, 40, 46, 69, 70, 71, 72,
See Special Conditions Attachment E	See Special Conditions Attachment E	NO_X	617.98	1495.19	2, 4, 27, 31, 35, 39, 41, 42, 43, 44, 55, 69, 70, 71	2, 4, 27, 31, 36, 39, 41, 42, 43, 44, 55, 56, 69, 70, 71,77	2, 4, 31, 39, 42, 69, 70, 71
See Special Conditions Attachment E	See Special Conditions Attachment E	CO	1057.41	2264.19	2, 4, 27, 39, 41, 42, 43, 44, 55, 69, 70, 71	2, 4, 27, 36, 39, 41, 42, 43, 44, 55, 56, 69, 70, 71, 77	2, 4, 39, 42, 69, 70, 71
See Special Conditions Attachment E	See Special Conditions Attachment E	SO2	1240.69	4073.98	2, 4, 16, 18, 20, 21, 22, 27, 31, 33, 39, 41, 42, 43, 44, 54, 55, 69, 70, 71, 76	2, 4, 16, 18, 21, 23, 24, 27, 31, 33, 36, 39, 41, 42, 43, 44, 54, 55, 56, 69 70, 71, 76, 77	2, 4, 23, 24, 31, 39, 42, 69, 70, 71
See Special Conditions Attachment E	See Special Conditions Attachment E	H2S	1.87	2.11	14, 16, 18, 19, 20, 21, 25, 33, 39, 43, 44, 53, 54, 55	14, 16, 18, 21, 23, 24, 33, 39, 43, 44, 53, 54, 55, 56	23, 24, 39
See Special Conditions Attachment E	See Special Conditions Attachment E	PM10	142.60	155.79	2, 4, 14, 22, 28, 30, 34, 39, 41, 42, 55, 69, 70, 71	2, 4, 14, 28, 39, 41, 42, 55, 56, 69, 70, 71, 77	2, 4, 39, 42, 69, 70, 71
See Special Conditions Attachment E	See Special Conditions Attachment E	Benzene (5)	29.87	66.09	2, 3, 4, 5, 9, 11, 14, 15, 21, 36, 39, 40, 44, 46, 47, 48, 51, 52, 55, 74	2, 3, 4, 5, 9, 10, 11, 14, 15, 21, 24, 36, 39, 40,44, 46, 47, 48, 51, 52, 55, 56, 74	2, 3, 4, 24, 39, 40, 46,
See Special Conditions Attachment E	See Special Conditions Attachment E	NH3	8.45	22.95	29, 35 39, 45, 55, 54	29, 35, 39, 45, 54, 55, 56	39, 45
Planned Maintenance, Startup, and Shutdown Activities							

Major NSR Summary Table

Permit Number: 47256, N258, and PSDTX402M4				Issuance Date: 11/30/2018			
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY (4)	Special Condition/ Application Information	Special Condition/ Application Information	Special Condition/ Application Information
See Special Conditions Attachment A-D	See Special Conditions Attachment A-D	VOC	2433.78	172.50	58, 59, 60, 61, 62, 63, 64, 67, 68	57, 58, 59, 60, 61, 62, 63, 64, 67, 68	
See Special Conditions Attachment A-D	See Special Conditions Attachment A-D	NO_X	157.86	24.36	66, 68	57, 58, 66, 68	
See Special Conditions Attachment A-D	See Special Conditions Attachment A-D	CO	790.56	136.31	66, 68	57, 58, 66, 68	
See Special Conditions Attachment A-D	See Special Conditions Attachment A-D	SO2	8419.88	842.16	66, 68	57, 58, 66, 68	
See Special Conditions Attachment A-D	See Special Conditions Attachment A-D	H2S	89.57	9.31	58, 66, 68	57, 58, 66, 68	
See Special Conditions Attachment A-D	See Special Conditions Attachment A-D	Benzene (5)	33.12	2.05	58, 59, 60, 61, 62, 63, 64, 67, 68	57, 58, 59, 60, 61, 62, 63, 64, 67, 68	
See Special Conditions Attachment A-D	See Special Conditions Attachment A-D	NH3	18.40	1.86	58, 66, 68	57, 58, 66, 68	
Planned Turnaround Maintenance, Startup, and Shutdown Activities							
See Special Conditions Attachment A-D	See Special Conditions Attachment A-D	VOC (6)	3133.28	91.70	58, 59, 60, 61, 62, 63, 64, 67, 68	57, 58, 59, 60, 61, 62, 63, 64, 67, 68	
See Special Conditions Attachment A-D	See Special Conditions Attachment A-D	NO_X (6)	325.87	10.56	66, 68	57, 58, 66, 68	

Major NSR Summary Table

Permit Number: 47256, N258, and PSDTX402M4				Issuance Date: 11/30/2018			
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY (4)	Special Condition/ Application Information	Special Condition/ Application Information	Special Condition/ Application Information
See Special Conditions Attachment A-D	See Special Conditions Attachment A-D	CO (6)	3627.58	75.48	66, 68	57, 58, 66, 68	
See Special Conditions Attachment A-D	See Special Conditions Attachment A-D	SO2 (6)	8089.14	20.68	66, 68	57, 58, 66, 68	
See Special Conditions Attachment A-D	See Special Conditions Attachment A-D	H2S (6)	87.70	0.32	58, 66, 68	57, 58, 66, 68	
See Special Conditions Attachment A-D	See Special Conditions Attachment A-D	PM10 (6)	123.64	1.04	58, 66, 68	57, 58, 66, 68	
See Special Conditions Attachment A-D	See Special Conditions Attachment A-D	Benzene (5) (6)	28.05	0.23	58, 59, 60, 61, 62, 63, 64, 67, 68	57, 58, 59, 60, 61, 62, 63, 64, 67, 68	
Individual Emission Limits							
34A	FCCU No. 3	VOC	(9)	33.98	27, 28, 30 31, 32, 39, 41, 42, 48, 66, 70, 73, 74	27, 28, 31, 32, 39, 41, 42, 48, 56, 66, 70, 73, 74	31, 39, 42, 70, 73,
		PM10/PM2.5	(9)	299.67			
		CO	(9)	499.23			
		H2SO4 (7)	31.68	108.20			
		O3	10.00	25.00			
		HCN	28.07	84.06			
203	ULC-102B Heater	VOC	(9)	1.60	33, 34, 39, 71, 76	33, 34, 39, 56, 71, 76	34, 39, 71, 76
		NO_X	(9)	28.36			
		CO	(9)	21.65			
		SO2(11)	(9)	7.91			
		PM10	(9)	2.21			
		PM2.5	(9)	2.21			

Major NSR Summary Table

Permit Number: 47256, N258, and PSDTX402M4				Issuance Date: 11/30/2018			
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY (4)	Special Condition/ Application Information	Special Condition/ Application Information	Special Condition/ Application Information
205	ULC-104BA/BB Heater	VOC	(9)	5.16	41, 42, 33, 34, 39, 71, 76	41, 42,33, 34, 56, 39, 71, 76	34, 41, 42, 39, 71, 76
		NO_X	(9)	115.52			
		CO	(9)	69.79			
		SO2(11)	(9)	25.37			
		PM10	(9)	7.14			
		PM2.5	(9)	7.14			
280-118	Tank 118	VOC	0.48	1.26	5, 61	5, 56, 61	
		Benzene	0.13	0.07			
F-30	FCCU3 2016 TAR Fugitives	VOC	0.04	0.16	51	51, 56	
		H2S	<0.01	<0.01			
F-PLANTFUG	Piping Equipment Fugitives for Fugitive EPNs 551, F-490, F-491, F470, F-390, F-393, F-90, F-60, F-30, F486, 195-F, F-294, 551, F-480, F-380, F-280, F-200, F-160, and F-400(8)	VOC	74.22	325.06	51, 54, 60	51, 54, 56, 60	
		Benzene (5)	3.02	13.23			
		H2S	2.32	10.18			
		NH3	0.09	0.42			
161	UU3 301-B Heater (10)	VOC	(9)	11.93	33, 34, 39, 41, 42	33, 34, 39, 41, 42, 56	39
		NO_X	(9)	376.02			
		CO	(9)	88.48			
		SO2	(9)	88.55			
		$PM_{10}/PM_{2.5}$	(9)	16.48			
162	UU3 302-B ReHeater (10)	VOC	(9)	7.01	33, 34, 39, 41, 42	33, 34, 39, 41, 42, 56	39
		NO_X	(9)	91.06			
		CO	(9)	48.81			

Major NSR Summary Table

Permit Number: 47256, N258, and PSDTX402M4				Issuance Date: 11/30/2018			
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY (4)	Special Condition/ Application Information	Special Condition/ Application Information	Special Condition/ Application Information
		SO2	(9)	52.08			
		$PM_{10}/PM_{2.5}$	(9)	9.69			
167	UU3 306-B Hot Oil Heater (10)	VOC	(9)	8.27	33, 34, 39, 41, 42	33, 34, 39, 41, 42, 56	39
		NO_X	(9)	122.64			
		CO	(9)	28.21			
		SO2	(9)	61.37			
		$PM_{10}/PM_{2.5}$	(9)	11.42			
161A	UU3-311B, UU3-312B, and UU3-310B (10)	VOC	2.14	9.37	33, 34, 39, 41, 42, 76	33, 34, 39, 41, 42, 56, 57, 76	39, 76
		NO_X	10.70	51.6613			
		NO_X -MSS	106.96				
		CO	77.79	49.24			
		CO-MSS	311.17				
		SO2 (15)	29.69	110.04			
		$PM_{10}/PM_{2.5}$	7.97	34.91			
		NH3	4.72	20.69			
164A	UU3 313-B Flue Gas Heater	VOC	0.12	0.52	33, 34, 39, 43, 44	33, 34, 39, 43, 56, 57	39
		NO_X	1.76	7.73			
		CO	3.62	8.56			
		CO-MSS	14.44				
		SO2	1.29	5.66			
		$PM_{10}/PM_{2.5}$	0.37	1.61			
165A	UU3 309-B Hot Oil Heater	VOC	0.84	3.2	33, 34, 39, 41, 42	33, 34, 39, 41, 42, 56, 57	39
		NO_X	4.2	17.17			
		NO_X -MSS	41.96				
		CO	31	64.59			
		CO-MSS	124.05				

Major NSR Summary Table

Permit Number: 47256, N258, and PSDTX402M4				Issuance Date: 11/30/2018			
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY (4)	Special Condition/ Application Information	Special Condition/ Application Information	Special Condition/ Application Information
		SO2	11.07	42.24			
		$PM_{10}/PM_{2.5}$	3.15	12.01			
		NH3	1.88	4.66			
280-12A	Tank 12A	VOC	1.21	2.10	33, 34, 39, 41, 42	33, 34, 39, 41, 42, 56, 57	39
299-40,41	Docks 40 and 41	VOC	17.69	3.75		13, 56, 57, 77, 79	
D-07	Dock40/41 Sumps	VOC	0.01	0.02		13, 56, 57, 77, 79	

(1) Emission point identification - either specific equipment designation or emission point number from a plot plan.

(2) Specific point source names. For fugitive sources, use an area name or fugitive source name.

(3) VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1

NOx - total oxides of nitrogen

CO - carbon monoxide

SO2 - sulfur dioxide

H2S - hydrogen sulfide

H2SO4 - sulfuric acid mist

O3 - ozone

PM - particulate matter

PM10 - particulate matter (PM) equal to or less than 10 microns in diameter. Where PM is not listed, it shall be assumed that no PM greater than 10 microns is emitted.

PM2.5 - PM equal to or less than 2.5 microns in diameter.

NH3 – ammonia

HCN - hydrogen cyanide

(4) Compliance with annual emission limits (tons per year) is based on a 12-month rolling period.

(5) The emission rates listed for the benzene cap are included in the VOC cap.

(6) Annual emissions from planned turnaround maintenance, startup, and shutdown (MSS) activities are above and beyond the emissions from normal operations and planned MSS activities. Short-term emissions from the plant due to normal operations, planned MSS activities, and planned turnaround MSS activities should not exceed the short-term planned turnaround MSS activities emission rates.

(7) Short term H2SO4 emission rate is included in the short-term routine PM10 cap. Annual H2SO4 emission rate is included in the individual annual PM emission rate for EPN 34A.

(8) Facility emissions associated with this EPN are from piping equipment only. Fugitive emissions from process drains are authorized under the flexible permit cap.

(9) Hourly emissions are contained within the flexible permit hourly cap.

(10) EPN 161, 162, and 167 are not authorized to emit simultaneously with EPN 161A.
(11) Interim emissions before the total sulfur reduction project are represented in Special Condition No. 76, to be completed no later than December 31, 2020.

Major NSR Summary Table

Permit Number: GHGPSDTX166				Issuance Date: 11/30/2018		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			TPY (4)	Special Condition/ Application Information	Special Condition/ Application Information	Special Condition/ Application Information
F-RAH-PLTFUG	Fugitives for EPNs F-390-RAH, F-470-RAH, F-393-RAH, F-480-RAH, F-280-RAH, F-50-RAH, F56-RAH, F54-RAH, TDOCK-RAH, F-380-RAH. F-489-RAH, F48-RAH, F-40-RAH, F-70-RAH	CH_4 (5)	1.32	90		
		CO_2 (5)	0.02			
		CO_2e	33			
F-DHT	DHT Fugitive Components	CH_4 (5)	1.12	90		
		CO_2 (5)	<0.01			
		CO_2e	28			
DHT-101B	DHT Stripper Reboiler	CH_4 (5)	2.45	49, 88, 89, 90	49, 88, 89	49
		CO_2 (5)	45,552			
		N_2O (5)	0.35			
		CO_2e	45,718			
DHT-201B	DHT Reactor Charge Heater	CH_4 (5)	3.53	49, 88, 89, 90	49, 88, 89	49
		CO_2 (5)	65,481			
		N_2O (5)	0.50			
		CO_2e	65,719			

Major NSR Summary Table

Permit Number: GHGPSDTX166				Issuance Date: 11/30/2018		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			TPY (4)	Special Condition/ Application Information	Special Condition/ Application Information	Special Condition/ Application Information
EPNs 484 and 384	RHU Heater 501B and 502B and SRU Incinerator C&D	CH_4 (5)	15.45	85, 88, 89, 90	85, 88, 89	85
		CO_2 (5)	626,451			
		N_2O (5)	2.21			
		CO_2e	627,495			

(1) Emission point identification - either specific equipment designation or emission point number from plot plan.
(2) Specific point source name. For fugitive sources, use area name or fugitive source name.
(3) CO_2 - carbon dioxide
N_2O - nitrous oxide
CH_4 - methane
CO_2e - carbon dioxide equivalents based on the following Global Warming Potentials (GWP) found in Table A-1 of Subpart A 40 CFR Part 98 (78 FR 71904) for each pollutant: CO_2 (1), N_2O (298), CH_4(25)
(4) Compliance with annual emission limits (tons per year) is based on a 12-month rolling period. These rates include emissions from maintenance, startup, and shutdown.
(5) Emission rate is given for informational purposes only and does not constitute enforceable limit.

Texas Commission on Environmental Quality
Air Quality Permit

A Permit Is Hereby Issued To
Blanchard Refining Company LLC
Authorizing the Construction and Operation of
Blanchard Refining Galveston Bay Refinery
Located at **Texas City, Galveston County, Texas**
Latitude 29° 22′ 44″ Longitude −94° 55′ 42″

Permit: 19599 and PSDTX023

Revision Date: November 30, 2018

Expiration Date: November 13, 2016

For the Commission

1. **Facilities** covered by this permit shall be constructed and operated as specified in the application for the permit. All representations regarding construction plans and operation procedures contained in the permit application shall be conditions upon which the permit is issued. Variations from these representations shall be unlawful unless the permit holder first makes application to the Texas Commission on Environmental Quality (commission) Executive Director to amend this permit in that regard and such amendment is approved. [Title 30 Texas Administrative Code (TAC) Section 116.116 (30 TAC § 116.116)] [1]
2. **Voiding of Permit**. A permit or permit amendment is automatically void if the holder fails to begin construction within 18 months of the date of issuance, discontinues construction for more than 18 months prior to completion, or fails to complete construction within a reasonable time. Upon request, the executive director may grant an 18-month extension. Before the extension is granted the permit may be subject to revision based on best available control technology, lowest achievable emission rate, and netting or offsets as applicable. One additional extension of up to 18 months may be granted if the permit holder demonstrates that emissions from the facility will comply with all rules and regulations of the commission, the intent of the Texas Clean Air Act (TCAA), including protection of the public's health and physical property; and (b)(1)the permit holder is a party to litigation not of the permit holder's initiation regarding the issuance of the permit; or (b)(2) the permit holder has spent, or committed to spend, at least 10 percent of the estimated total cost of the project up to a maximum of $5 million. A permit holder granted an extension under subsection (b)(1) of this section may receive one subsequent extension if the permit holder meets the conditions of subsection (b)(2) of this section. [30 TAC § 116.120]
3. **Construction Progress**. Start of construction, construction interruptions exceeding 45 days, and completion of construction shall be reported to the appropriate regional office of the commission not later than 15 working days after occurrence of the event. [30 TAC § 116.115(b)(2)(A)]
4. **Start-up Notification**. The appropriate air program regional office shall be notified prior to the commencement of operations of the facilities authorized by the permit in such a manner that a representative of the commission may be present. The permit holder shall provide a separate notification for the commencement of operations for each unit of phased construction, which may involve a series of units commencing operations at different times. Prior to operation of the facilities authorized by the permit, the permit holder shall identify the source or sources of allowances to be utilized for compliance with Chapter 101, Subchapter H, Division 3 of this title (relating to Mass Emissions Cap and Trade Program). [30 TAC § 116.115(b)(2)(B)]
5. **Sampling Requirements**. If sampling is required, the permit holder shall contact the commission's Office of Compliance and Enforcement prior to sampling to obtain the proper data forms and procedures. All sampling and testing procedures must be approved by the executive director and coordinated with the regional representatives of the commission. The permit holder is also responsible for providing sampling facilities and conducting the sampling operations or contracting with an independent sampling consultant. [30 TAC § 116.115(b)(2)(C)]
6. **Equivalency of Methods.** The permit holder must demonstrate or otherwise justify the equivalency of emission control methods, sampling or other emission testing methods, and monitoring methods proposed as alternatives to methods indicated in the conditions of the permit. Alternative methods shall be applied for in writing and must be reviewed and approved by the executive director prior to their use in fulfilling any requirements of the permit. [30 TAC § 116.115(b)(2)(D)]
7. **Recordkeeping.** The permit holder shall maintain a copy of the permit along with records containing the information and data sufficient to demonstrate compliance with the permit, including production records and

operating hours; keep all required records in a file at the plant site. If, however, the facility normally operates unattended, records shall be maintained at the nearest staffed location within Texas specified in the application; make the records available at the request of personnel from the commission or any air pollution control program having jurisdiction in a timely manner; comply with any additional recordkeeping requirements specified in special conditions in the permit; and retain information in the file for at least two years following the date that the information or data is obtained. [30 TAC § 116.115(b)(2)(E)]

8. **Maximum Allowable Emission Rates**. The total emissions of air contaminants from any of the sources of emissions must not exceed the values stated on the table attached to the permit entitled "Emission Sources--Maximum Allowable Emission Rates." [30 TAC § 116.115(b)(2)(F)] [1]
9. **Maintenance of Emission Control**. The permitted facilities shall not be operated unless all air pollution emission capture and abatement equipment is maintained in good working order and operating properly during normal facility operations. The permit holder shall provide notification in accordance with 30 TAC §101.201, 101.211, and 101.221 of this title (relating to Emissions Event Reporting and Recordkeeping Requirements; Scheduled Maintenance, Startup, and Shutdown Reporting and Recordkeeping Requirements; and Operational Requirements). [30 TAC§ 116.115(b)(2)(G)]
10. **Compliance with Rules**. Acceptance of a permit by an applicant constitutes an acknowledgment and agreement that the permit holder will comply with all rules and orders of the commission issued in conformity with the TCAA and the conditions precedent to the granting of the permit. If more than one state or federal rule or regulation or permit condition is applicable, the most stringent limit or condition shall govern and be the standard by which compliance shall be demonstrated. Acceptance includes consent to the entrance of commission employees and agents into the permitted premises at reasonable times to investigate conditions relating to the emission or concentration of air contaminants, including compliance with the permit. [30 TAC § 116.115(b)(2)(H)]
11. **This** permit may not be transferred, assigned, or conveyed by the holder except as provided by rule. [30 TAC § 116.110(e)]
12. **There** may be additional special conditions attached to a permit upon issuance or modification of the permit. Such conditions in a permit may be more restrictive than the requirements of Title 30 of the Texas Administrative Code. [30 TAC § 116.115(c)]
13. **Emissions** from this facility must not cause or contribute to "air pollution" as defined in Texas Health and Safety Code (THSC) §382.003(3) or violate THSC § 382.085. If the executive director determines that such a condition or violation occurs, the holder shall implement additional abatement measures as necessary to control or prevent the condition or violation.
14. **The** permit holder shall comply with all the requirements of this permit. Emissions that exceed the limits of this permit are not authorized and are violations of this permit. [1]

[1] Please be advised that the requirements of this provision of the general conditions may not be applicable to greenhouse gas emissions.

Special Conditions

Permit Numbers 19599 and PSDTX023

Emission Standards

1. This permit authorizes emissions only from those points listed in the attached table entitled “Emission Sources - Maximum Allowable Emission Rates (MAERT)” and the facilities covered by this permit are authorized to emit subject to the emission rate limits on that table and other operating conditions specified in this permit.

2. The feed rate to Pipe Still No. 3A shall not exceed 260,000 barrels per calendar day. A record of feed rate (daily throughput in barrels) to Pipe Still No. 3A shall be kept on a rolling five-year basis and made available to the Texas Commission on Environmental Quality (TCEQ) Executive Director or his designated representatives upon request. **(11/18*)***

3. The GOF Heater designated as Emission Point No. (EPN) 55 shall be fired at a maximum duty of 185.2 MMBtu/hr. A record of the daily average firing rate (in MMBtu/hr) for GOF Heater 103-B shall be kept on a rolling five-year basis and made readily available to the TCEQ Executive Director or his designated representatives upon request

4. The cooling tower water authorized in this permit shall be monitored monthly for VOC leakage from heat exchangers in accordance with the requirements of the TCEQ Sampling Procedures Manual, Appendix P (dated January 2003 or a later edition) or another air stripping method approved by the TCEQ Executive Director. The results of the monitoring and maintenance activities required by this special condition (SC) shall be kept on a rolling five-year basis and made available to the TCEQ Executive Director or his designated representatives upon request.

5. Emissions of NO_X from heaters in this condition shall meet the following emissions limits: **(11/18)**

   A. Emissions of NO_X from heaters 102-BA and 102-BB (EPN 53) shall not exceed 0.10 lbs NO_X /MMBTU (hourly block average) at any time, except during the operating modes defined in C of this permit condition, and 0.035 lbs NO_X/MMBTU on an annual basis.

   B. Operating modes during which the hourly block average NO_X emission limits in A of this condition do not apply are defined as follows:

      (1) Hot Standby Mode, defined as the period when the heater is firing at 50 percent or less of the maximum allowable firing rate and no hydrocarbon

feed is being charged to the heater.

(2) Decoking Mode, defined as the period starting when air is introduced to the heater for the purpose of decoking and ending when air flow to the heater ceases.

(3) Start-up and Refractory Dry Out Modes, defined as the period beginning when fuel is introduced to the heater and ending when the heater process outlet temperature reaches the desired operating temperature for 15 consecutive minutes. A planned startup for each heater firebox is limited to 96 hours at 25 percent or less of the maximum allowable firing rate.

(4) Shutdown Mode, defined as the period beginning when the heater outlet temperature first drops below its stable operating temperature and ending when the fuel flow to the heater ceases.

(5) Feed-in Mode, defined as the period beginning when hydrocarbon feed is introduced to the heater and ending when the heater reaches 70 percent of the maximum allowable firing rate.

(6) Feed-out Mode, defined as the period beginning when a heater drops below 70 percent of the maximum allowable firing rate and ending when hydrocarbon feed to the heater ceases.

C. The emission rate limits on the MAERT remain in effect during the operating modes defined in B of this condition.

Federal Applicability

6. These facilities shall comply with all applicable requirements of the U.S. Environmental Protection Agency (EPA) Regulations on Standards of Performance for New Stationary Sources promulgated for Petroleum Refineries in Title 40 Code of Federal Regulations Part 60 (40 CFR Part 60), Subparts A and J.

7. These facilities shall comply with the applicable requirements of Title 30 Texas Administrative Code (30 TAC) § 113.340, including the referenced requirements promulgated for National Emission Standards for Hazardous Air Pollutants From Petroleum Refineries in 40 CFR Part 63, Subpart CC.

Initial Determination of Compliance

8. Upon request of the TCEQ Executive Director, the permit holder shall perform stack sampling and other testing as required to establish the actual pattern and quantities of air contaminants being emitted into the atmosphere upon installation of low-NO_x technology, from the GOF Heater 103-B (EPN 55). The permit holder is responsible for providing sampling and testing facilities and conducting the sampling and testing operations at his expense. Sampling shall be conducted in accordance with the appropriate procedures of the TCEQ Sampling Procedures Manual and the U.S. EPA Reference Methods. **(11/18)**

   Requests to waive testing for any pollutant specified in this condition shall be submitted to the TCEQ Office of Air, Air Permits Division. Test waivers and alternate/equivalent procedure proposals for 40 CFR Part 60 testing which must have EPA approval shall be submitted to the TCEQ Regional Director.

   A. The appropriate TCEQ Regional Office shall be notified not less than 45 days prior to sampling. The notice shall include:

      (1) Proposed date for pretest meeting.
      (2) Date sampling will occur.
      (3) Name of firm conducting sampling.
      (4) Type of sampling equipment to be used.
      (5) Method or procedure to be used in sampling.
      (6) Description of any proposed deviation from the sampling procedures specified in this permit or TCEQ/EPA sampling procedures.
      (7) Procedure or parameters to be used to determine worst case, such as firing rate during the sampling period.

      The purpose of the pretest meeting is to review the necessary sampling and testing procedures, to provide the proper data forms for recording pertinent data, and to review the format procedures for the test reports. The TCEQ Regional Director must approve any deviation from specified sampling procedures.

   B. Air contaminants emitted from the GOF Heater 103-B to be tested for include (but are not limited to) NO_X, CO, and PM_{10}. The PM_{10} shall be sampled using EPA Method 5, but including both front and back halves of the sampling train, and all PM is considered to be PM_{10} unless sampling demonstrated otherwise.

   C. Sampling shall occur within 60 days after initial start-up of the facilities and at

such other times as may be required by the Executive Director of the TCEQ. Requests for additional time to perform sampling shall be submitted to the TCEQ Regional Office.

D. The heater being sampled shall operate at maximum firing rates during stack emission testing. Primary operating parameters that enable determination of the firing rate shall be monitored and during the stack test. Any additional parameters shall be determined at the pretest meeting and shall be stated in the sampling report. Permit conditions and parameter limits may be waived during stack testing performed under this condition if the proposed condition/parameter range is identified in the test notice specified in paragraph A and accepted by the TCEQ Regional Office. Permit allowable emissions and emission control requirements are not waived and still apply during stack testing periods.

   During subsequent operations, if the heater or furnace firing rate is greater than that recorded during the test period, stack sampling shall be performed at the new operating conditions within 120 days. This sampling may be waived by the TCEQ Air Section Manager for the region.

E. Copies of the final sampling report shall be forwarded to the offices below within 60 days after sampling is completed. Sampling reports shall comply with the attached provisions entitled “Chapter 14, Contents of Sampling Reports” of the TCEQ Sampling Procedures Manual. The reports shall be distributed as follows:

   One copy to the TCEQ Houston Regional Office,
   One copy to each local air pollution control program.

Process Fugitive Monitoring Requirements

9. Piping, Valves, Connectors, Pumps, Agitators, and Compressors in Volatile Organic Compounds (VOC) Service - 28VHP **(05/14)**

   Except as may be provided for in the special conditions of this permit, the following requirements apply to the above-referenced equipment:

   A. These conditions shall not apply where (1) the VOC has an aggregate partial pressure or vapor pressure equal to or less than 0.044 pounds per square inch, absolute (psia) at 68°F or (2) the operating pressure is at least 5 kilopascals

(0.725 psi) below ambient pressure. Equipment excluded from this condition shall be identified in a list or by one of the methods described below to be made available upon request.

The exempted components may be identified by one or more of the following methods:

(1) piping and instrumentation diagram (PID);
(2) a written or electronic database or electronic file;
(3) color coding;
(4) a form of weatherproof identification; or
(5) designation of exempted process unit boundaries.

B. Construction of new and reworked piping, valves, pump systems, and compressor systems shall conform to applicable American National Standards Institute (ANSI), American Petroleum Institute (API), American Society of Mechanical Engineers (ASME), or equivalent codes.

C. New and reworked underground process pipelines shall contain no buried valves such that fugitive emission monitoring is rendered impractical. New and reworked buried connectors shall be welded.

D. To the extent that good engineering practice will permit, new and reworked valves and piping connections shall be so located to be reasonably accessible for leak-checking during plant operation. Difficult-to-monitor and unsafe-to-monitor valves, as defined by 30 TAC Chapter 115 (30 TAC Chapter 115), shall be identified in a list to be made readily available upon request. The difficult-to-monitor and unsafe-to-monitor valves may be identified by one or more of the methods described in subparagraph A above. If an unsafe-to-monitor component is not considered safe to monitor within a calendar year, then it shall be monitored as soon as possible during safe-to-monitor times. A difficult-to-monitor component for which quarterly monitoring is specified may instead be monitored annually.

E. New and reworked piping connections shall be welded or flanged. Screwed connections are permissible only on piping smaller than two-inch diameter. Gas or hydraulic testing of the new and reworked piping connections at no less than operating pressure shall be performed prior to returning the components to service or they shall be monitored for leaks using an approved gas analyzer within 15 days of the components being returned to service. Adjustments shall be made as necessary to obtain leak-free performance. Connectors shall be

inspected by visual, audible, and/or olfactory means at least weekly by operating personnel walk-through.

Each open-ended valve or line shall be equipped with an appropriately sized cap, blind flange, plug, or a second valve to seal the line. Except during sampling, both valves shall be closed. If the removal of a component for repair or replacement results in an open ended line or valve, it is exempt from the requirement to install a cap, blind flange, plug, or second valve for 72 hours. If the repair or replacement is not completed within 72 hours, the permit holder must complete either of the following actions within that time period: the line or valve must have a cap, blind flange, plug, or second valve installed; or the permit holder shall verify that there is no leakage from the open-ended line or valve. The open-ended line or valve shall be monitored on a weekly basis in accordance with the applicable NSR permit condition for fugitive emission monitoring except that a leak is defined as any VOC reading greater than background. Leaks must be repaired within 24 hours or a cap, blind flange, plug, or second valve must be installed on the line or valve. The results of this weekly check and any corrective actions taken shall be recorded.

F. Accessible valves shall be monitored by leak-checking for fugitive emissions at least quarterly using an approved gas analyzer. Sealless/leakless valves (including, but not limited to, welded bonnet bellows and diaphragm valves) and relief valves equipped with a rupture disc upstream or venting to a control device are not required to be monitored. For valves equipped with rupture discs, a pressure-sensing device shall be installed between the relief valve and rupture disc to monitor disc integrity. All leaking discs shall be replaced at the earliest opportunity but no later than the next process shutdown.

A check of the reading of the pressure-sensing device to verify disc integrity shall be performed weekly and recorded in the unit log or equivalent. Pressure-sensing devices that are continuously monitored with alarms are exempt from recordkeeping requirements specified in this paragraph.

The gas analyzer shall conform to requirements listed in Method 21 of 40 CFR part 60, appendix A. The gas analyzer shall be calibrated with methane. In addition, the response factor of the instrument for a specific VOC of interest shall be determined and meet the requirements of Section 8 of Method 21. If a mixture of VOCs are being monitored, the response factor shall be calculated for the average composition of the process fluid. A calculated average is not

required when all of the compounds in the mixture have a response factor less than 10 using methane. If a response factor less than 10 cannot be achieved using methane, then the instrument may be calibrated with one of the VOC to be measured or any other VOC so long as the instrument has a response factor of less than 10 for each of the VOC to be measured.

Replacements for leaking components shall be re-monitored within 15 days of being placed back into VOC service.

G. Except as may be provided for in the special conditions of this permit, all pump, compressor, and agitator seals shall be monitored with an approved gas analyzer at least quarterly or be equipped with a shaft sealing system that prevents or detects emissions of VOC from the seal. Seal systems designed and operated to prevent emissions or seals equipped with an automatic seal failure detection and alarm system need not be monitored. These seal systems may include (but are not limited to) dual pump seals with barrier fluid at higher pressure than process pressure, seals degassing to vent control systems kept in good working order, or seals equipped with an automatic seal failure detection and alarm system. Submerged pumps or sealless pumps (including, but not limited to, diaphragm, canned, or magnetic-driven pumps) may be used to satisfy the requirements of this condition and need not be monitored.

H. Damaged or leaking valves or connectors found to be emitting VOC in excess of 500 parts per million by volume (ppmv) or found by visual inspection to be leaking (e.g., dripping process fluids) shall be tagged and replaced or repaired. Damaged or leaking pump, compressor, and agitator seals found to be emitting VOC in excess of 2,000 ppmv or found by visual inspection to be leaking (e.g., dripping process fluids) shall be tagged and replaced or repaired. A first attempt to repair the leak must be made within 5 days. Records of the first attempt to repair shall be maintained.

I. Every reasonable effort shall be made to repair a leaking component, as specified in this paragraph, within 15 days after the leak is found. If the repair of a component would require a unit shutdown that would create more emissions than the repair would eliminate, the repair may be delayed until the next scheduled shutdown. All leaking components which cannot be repaired until a scheduled shutdown shall be identified for such repair by tagging within 15 days of the detection of the leak. A listing of all components that qualify for delay of repair shall be maintained on a delay of repair list. The cumulative daily emissions from all components on the delay of repair list shall be estimated by multiplying by 24 the mass emission rate for each component

calculated in accordance with the instructions in 30 TAC 115.782 (c)(1)(B)(i)(II). The calculations of the cumulative daily emissions from all components on the delay of repair list shall be updated within ten days of when the latest leaking component is added to the delay of repair list. When the cumulative daily emission rate of all components on the delay of repair list times the number of days until the next scheduled unit shutdown is equal to or exceeds the total emissions from a unit shutdown as calculated in accordance with 30 TAC 115.782 (c)(1)(B)(i)(I), the TCEQ Regional Manager and any local programs shall be notified and may require early unit shutdown or other appropriate action based on the number and severity of tagged leaks awaiting shutdown. This notification shall be made within 15 days of making this determination.

J. Records of repairs shall include date of repairs, repair results, justification for delay of repairs, and corrective actions taken for all components. Records of instrument monitoring shall indicate dates and times, test methods, and instrument readings. The instrument monitoring record shall include the time that monitoring took place for no less than 95% of the instrument readings recorded. Records of physical inspections shall be noted in the operator's log or equivalent.

K. Alternative monitoring frequency schedules of 30 TAC §§ 115.352 - 115.359 or National Emission Standards for Organic Hazardous Air Pollutants, 40 CFR Part 63, Subpart H, may be used in lieu of Items F through G of this condition.

L. Compliance with the requirements of this condition does not assure compliance with requirements of 30 TAC Chapter 115, an applicable NSPS, or an applicable National Emission Standard for Hazardous Air Pollutants (NESHAPS) and does not constitute approval of alternative standards for these regulations.

10. Components which contact a process fluid that contains less than 10 percent VOC by weight are exempt from SC No. 9 requirements.

Standard Permits (SPs) and Permits by Rule (PBRs)

11. The following Permits by Rule (PBRs) are consolidated by reference into this permit: **(11/18)**

PBR Registration Number	Authorized by:
81516	30 TAC § 106.261 [Facilities (Emission Limitations)]
84567	30 TAC § 106.261 [Facilities (Emission Limitations)]
87825	30 TAC § 106.262 [Facilities (Emission and Distance Limitations)]
87883	30 TAC § 106.261 [Facilities (Emission Limitations)] and 30 TAC § 106.262 [Facilities (Emission and Distance Limitations)]
92273	30 TAC § 106.261 [Facilities (Emission Limitations)] and 30 TAC § 106.262 [Facilities (Emission and Distance Limitations)]
92585	30 TAC § 106.261 [Facilities (Emission Limitations)]
95591	30 TAC § 106.261 [Facilities (Emission Limitations)] and 30 TAC § 106.262 [Facilities (Emission and Distance Limitations)]
101884	30 TAC § 106.261 [Facilities (Emission Limitations)] and 30 TAC § 106.262 [Facilities (Emission and Distance Limitations)]
108602	30 TAC § 106.261 [Facilities (Emission Limitations)], 30 TAC § 106.262 [Facilities (Emission and Distance Limitations)], and 30 TAC § 106.478 (Storage Tank and Change of Service)
109502	30 TAC § 106.262 [Facilities (Emission and Distance Limitations)]
110915	30 TAC § 106.261 [Facilities (Emission Limitations)] and 30 TAC § 106.262 [Facilities (Emission and Distance Limitations)]

PBR Registration Number	Authorized by:
113463	30 TAC § 106.261 [Facilities (Emission Limitations)]
117317	30 TAC § 106.261 [Facilities (Emission Limitations)] and 30 TAC § 106.262 [Facilities (Emission and Distance Limitations)]
118767	30 TAC § 106.261 [Facilities (Emission Limitations)]
Unregistered	Claimed in December, 2008 under 30 TAC § 106.371 [Cooling Water Units]

Recordkeeping

12. The following written records demonstrating compliance shall be made and maintained by the holder of this permit. These records shall be kept at the plant site at least five years and shall be made immediately available upon request to designated representatives of the TCEQ or EPA. **(05/14)**

    A. Records of feed rate (daily throughput in barrels) to Pipe Still No. 3A, as specified in SC No. 2.

    B. Records of the daily average firing rate (in MMBtu/hr) for GOF Heater 103-B, as specified in SC No. 3.

    C. Records of the required cooling tower water monitoring and maintenance activities, as specified in SC No. 4.

    D. Records of open-ended line or valve monitoring and corrective actions, as specified in SC No. 9.E.

    E. Records of pressure-sensing device readings, as specified in SC No. 9.F.

    F. Records of leaky component repairs, as specified in SC Nos. 9.H and 9.J.

    G. Records of instrument monitoring and physical inspections, as specified in SC

No. 9.J.

Dated November 30, 2018

Emission Sources - Maximum Allowable Emission Rates

Permit Number 19599 and PSDTX023

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities, sources, and related activities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

Air Contaminants Data

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
46	Oil Water Separator	VOC	5.80	25.00
47	Oil Water Separator	VOC	0.90	4.00
51	101-BA/BB	CO	29.90	109.00
		NO_X	47.62	173.80
		PM_{10} (6)	3.70	13.60
		SO_2 (6)	20.10	73.30
		VOC	1.00	3.80
53	102-BA/BB	CO	22.45	81.94
		NO_X	10.62	38.75
		PM_{10} (6)	1.40	5.20
		SO_2 (6)	7.70	28.00
		VOC	0.80	3.00
55	103-B	CO	5.65	24.72
		NO_X	15.80	65.70
		PM_{10} (6)	2.42	10.61
		SO_2 (6)	3.80	16.62
		VOC	0.20	0.87
56	Oil Water Separator	VOC	4.40	19.00
417	Cooling Tower	VOC	1.26	5.52
F-40	Process Fugitives Pipestill No. 3B (5)	H_2S	0.28	1.24
		VOC	22.36	97.94
F-50	Process Fugitives Pipestill No. 3A (5)	H_2S	0.34	1.47
		VOC	26.65	116.76

Emission Sources - Maximum Allowable Emission Rates

(1) Emission point identification – either specific equipment designation or emission point number from plot plan.
(2) Specific point source name. For fugitive sources, use area name or fugitive source name.
(3) CO - carbon monoxide
H_2S - hydrogen sulfide
NO_X - total oxides of nitrogen
PM_{10} - total particulate matter equal to or less than 10 microns in diameter, including $PM_{2.5}$, as represented
SO_2 - sulfur dioxide
VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1
(4) Compliance with annual emission limits (tons per year) is based on a 12-month rolling period.
(5) Emission rate is an estimate and is enforceable through compliance with the applicable special condition(s) and permit application representations.
(6) PSD-TX-023 pollutant.

Date: November 30, 2018

Texas Commission on Environmental Quality
Air Quality Permit

A Flexible Permit Is Hereby Issued To
Blanchard Refining Company LLC
Authorizing the Construction and Operation of
Blanchard Refining Galveston Bay Refinery
Located at **Texas City, Galveston County, Texas**
Latitude 29° 22′ 28″ Longitude −94° 55′ 30″

Permits: 47256, N258, PSDTX402M4, and GHGPSDTX166
Amendment Date: November 30, 2018
Expiration Date: July 13, 2015

For the Commission

1. **Facilities** covered by this permit shall be constructed and operated as specified in the application for the permit. All representations regarding construction plans and operation procedures contained in the permit application shall be conditions upon which the permit is issued. Variations from these representations shall be unlawful unless the permit holder first makes application to the Texas Commission on Environmental Quality (commission) Executive Director to amend this permit in that regard and such amendment is approved. It shall be unlawful for any person to vary from such representation or flexible permit provision if the change will cause a change in the method of control of emissions, the character of the emissions, will relax emission controls or will result in a significant increase in emissions, unless application is made to the executive director to amend the flexible permit in that regard and such amendment is approved by the executive director. [Title 30 Texas Administrative Code (TAC) Sections 116.715(c)(8) and 116.721 (30 TAC § 116.721)] [1]
2. **Voiding of Permit**. A permit or permit amendment is automatically void if the holder fails to begin construction within 18 months of the date of issuance, discontinues construction for more than 18 months prior to completion, or fails to complete construction within a reasonable time. Upon request, the executive director may grant an 18-month extension. Before the extension is granted the permit may be subject to revision based on best available control technology, lowest achievable emission rate, and netting or offsets as applicable. One additional extension of up to 18 months may be granted if the permit holder demonstrates that emissions from the facility will comply with all rules and regulations of the commission, the intent of the Texas Clean Air Act (TCAA), including protection of the public's health and physical property; and (b)(1)the permit holder is a party to litigation not of the permit holder's initiation regarding the issuance of the permit; or (b)(2) the permit holder has spent, or committed to spend, at least 10 percent of the estimated total cost of the project up to a maximum of $5 million. A permit holder granted an extension under subsection (b)(1) of this section may receive one subsequent extension if the permit holder meets the conditions of subsection (b)(2) of this section. [30 TAC § 116.120]
3. **Construction Progress**. Start of construction, construction interruptions exceeding 45 days, and completion of construction shall be reported to the appropriate regional office of the commission not later than 15 working days after occurrence of the event. [30 TAC § 116.715(c)(2)]
4. **Start-up Notification**. The appropriate air program regional office shall be notified prior to the commencement of operations of the facilities authorized by the permit in such a manner that a representative of the commission may be present. The permit holder shall provide a separate notification for the commencement of operations for each unit of phased construction, which may involve a series of units commencing operations at different times. Prior to operation of the facilities authorized by the permit, the permit holder shall identify the source or sources of allowances to be utilized for compliance with Chapter 101, Subchapter H, Division 3 of this title (relating to Mass Emissions Cap and Trade Program). [30 TAC § 116.715(c)(3)]
5. **Sampling Requirements**. If sampling is required, the flexible permit holder shall contact the commission's Office of Compliance and Enforcement prior to sampling to obtain the proper data forms and procedures. All sampling and testing procedures must be approved by the executive director and coordinated with the regional representatives of the commission. The flexible permit holder is also responsible for providing sampling facilities and conducting the sampling operations or contracting with an independent sampling consultant. [30 TAC § 116.715(c)(4)]
6. **Equivalency of Methods.** The permit holder must demonstrate or otherwise justify the equivalency of emission control methods, sampling or other emission testing methods, and monitoring methods proposed as alternatives to

methods indicated in the conditions of the permit. Alternative methods shall be applied for in writing and must be reviewed and approved by the executive director prior to their use in fulfilling any requirements of the permit. [30 TAC § 116.715(c)(5)]

7. **Recordkeeping.** A copy of the flexible permit along with information and data sufficient to demonstrate continuous compliance with the emission caps and individual emission limitations contained in the flexible permit shall be maintained in a file at the plant site and made available at the request of personnel from the commission or any air pollution control program having jurisdiction. This information shall include, but is not limited to, emission cap and individual emission limitation calculations based on a 12-month rolling basis; emission cap and individual emission limitation calculations corresponding to any short term emission limitation; production records and operating hours; and additional recordkeeping requirements specified in special conditions attached to the flexible permit. Information in the file shall be retained for at least two years following the date that the information or data is obtained. For facilities that normally operate unattended, this information shall be maintained at the nearest staffed location within Texas specified by the permit holder in the permit application. [30 TAC § 116.715(c)(6)]
8. **Maximum Allowable Emission Rates**A flexible permit covers only those sources of emissions and those air contaminants listed in the table entitled "Emission Sources, Emissions Caps and Individual Emission Limitations" in the flexible permit. Each permitted facility, group of facilities or account is limited to the emission limits and other conditions specified in the table in the flexible permit. [30 TAC § 116.715(c)(7)] [1]
9. **Emission Cap Readjustment.** If a schedule to install additional controls is included in the flexible permit and a facility subject to such a schedule is taken out of service, the emission cap contained in the flexible permit will be readjusted for the period the unit is out of service to a level as if no schedule had been established. Unless a special condition specifies the method of readjustment of the emission cap, a permit alteration shall be obtained. [30 TAC § 116.715(c)(9)]
10. **Maintenance of Emission Control**. The permitted facilities shall not be operated unless all air pollution emission capture and abatement equipment is maintained in good working order and operating properly during normal facility operations. The flexible permit holder shall provide notification in accordance with 30 TAC §101.201, 101.211, and 101.221 of this title (relating to Emissions Event Reporting and Recordkeeping Requirements; Scheduled Maintenance, Startup, and Shutdown Reporting and Recordkeeping Requirements; and Operational Requirements). [30 TAC § 116.715(c)
11. **Compliance with Rules**. Acceptance of a flexible permit by an applicant constitutes an acknowledgment and agreement that the flexible permit holder will comply with all rules and orders of the commission issued in conformity with the TCAA and the conditions precedent to the granting of the permit. If more than one state or federal rule or regulation or permit condition is applicable, the most stringent limit or condition shall govern and be the standard by which compliance shall be demonstrated. Acceptance includes consent to the entrance of commission employees and agents into the permitted premises at reasonable times to investigate conditions relating to the emission or concentration of air contaminants, including compliance with the flexible permit. [30 TAC § 116.715(c)(11)]
12. **This** permit may not be transferred, assigned, or conveyed by the holder except as provided by rule. [30 TAC § 116.110(e)]
13. **There** may be additional special conditions attached to a permit upon issuance or modification of the permit. Such conditions in a permit may be more restrictive than the requirements of Title 30 of the Texas Administrative Code. [30 TAC § 116.715(d)]
14. **Emissions** from this facility must not cause or contribute to "air pollution" as defined in Texas Health and Safety Code (THSC) §382.003(3) or violate THSC § 382.085. If the executive director determines that such a condition or violation occurs, the holder shall implement additional abatement measures as necessary to control or prevent the condition or violation.
15. **The** permit holder shall comply with all the requirements of this permit. Emissions that exceed the limits of this permit are not authorized and are violations of this permit. [1]

[1] Please be advised that the requirements of this provision of the general conditions may not be applicable to greenhouse gas emissions.

Special Conditions

Flexible Permit Number 47256 and Permit Numbers PSDTX402M4, N258, and GHGPSDTX166

Special Condition Nos. 5 through 64 apply to the normal operations of the facilities authorized under this permit. Special Condition Nos. 65 through 76 apply to the planned maintenance, startup, and shutdown activities authorized by this permit.

Emission Caps and Individual Limitations

1. This permit authorizes emissions from those points listed in the attached table entitled "Emission Sources - Emission Caps and Individual Emission Limitations," (ECIELT) and the facilities covered by this permit are authorized to emit subject to the emission rate limits on the ECIELT and other requirements specified in the special conditions.

   Planned startup and shutdown emissions due to the activities identified in Special Condition No. 65 are authorized from facilities and emission points identified in Attachment D in other construction permits at the site provided the facility and emissions are compliant with the respective ECIELT and special conditions, or Special Condition No. 74 of this permit. **(8/10)**

Federal Applicability

2. These facilities shall comply with all applicable requirements of the U. S. Environmental Protection Agency (EPA) regulations on Standards of Performance for New Stationary Sources in Title 40 Code of Federal Regulations (40 CFR) Part 60, Subparts A, and: **(01/15)**

   A. Petroleum Refineries, Subpart J **(per Agreed Order Docket No. 2005-0224-AIR-E)**;

   B. Storage Vessels for Petroleum Liquids, Subpart K;

   C. Volatile Organic Liquid Storage Vessels, Subpart Kb; and

   D. Equipment Leaks of Volatile Organic Compounds (VOC) in Petroleum Refineries, Subpart GGG. **(8/10)**

3. These facilities shall comply with all applicable requirements of EPA regulations on National Emission Standards for Hazardous Air Pollutants (NESHAPS) in 40 CFR Part 61, Subparts A, and:

   A. Equipment Leaks of Benzene, Subpart J;

   B. Equipment Leaks, Subpart V;

   C. Benzene Transfer Operations, Subpart BB; and

   D. Benzene Waste Operations, Subpart FF.

4. These facilities shall comply with all applicable requirements of EPA regulations on NESHAPS in 40 CFR Part 63, Subparts A, and:

   A. Petroleum Refineries, Subparts CC;

   B. Petroleum Refineries: Catalytic Cracking Units, Catalytic Reforming Units, and Sulfur Recover Units, Subpart UUU; and

   C. Marine Vessel Loading Operations, Subpart Y.

Operational Limitations, Work Practices, and Plant Design

5. Storage tanks are subject to the following requirements: The control requirements specified in paragraphs A-D of this condition shall not apply (1) where the VOC has an aggregate partial pressure of less than 0.50 psia at the maximum feed temperature or 95°F, whichever is greater, or (2) to storage tanks smaller than 25,000 gallons.

   A. An internal floating deck or “roof” or equivalent control shall be installed in all tanks. The floating roof shall be equipped with one of the following closure devices between the wall of the storage vessel and the edge of the internal floating roof: (1) a liquid mounted seal, (2) two continuous seals mounted one above the other, or (3) a mechanical shoe seal. Installation of equivalent control requires prior review and approval by the Texas Commission on Environmental Quality (TCEQ) Executive Director.

   B. An open-top tank containing a floating roof (external floating roof tank) which uses double seal or secondary seal technology shall be an approved control alternative to an internal floating roof tank provided the primary seal consists of either a mechanical shoe seal or a liquid-mounted seal and the secondary seal is rim-mounted. A weathershield is not approvable as a secondary seal unless specifically reviewed and determined to be vapor-tight.

   C. For any tank equipped with a floating roof, the permit holder shall perform the visual inspections and seal gap measurements as specified in 40 CFR § 60.113b, Testing and Procedures (as amended at 54 FR 32973, Aug. 11, 1989), to verify fitting and seal integrity. Records shall be maintained of the dates seals were inspected and seal gap measurements made, results of inspections and measurements made (including raw data), and actions taken to correct any deficiencies noted.

   D. The floating roof design shall incorporate sufficient flotation to conform to the requirements of American Petroleum Institute (API) Code 650, or an equivalent degree of flotation, except that an internal floating cover need not be designed to meet rainfall support requirements and the materials of construction may be steel or other materials.

      The floating roof design for all new or retrofitted roofs shall incorporate sufficient flotation to conform to the requirements of API Code 650 dated November 1, 1998 or later except that an internal floating cover need not be designed to meet rainfall support requirements and the materials of construction may be steel or other materials.

   E. Tanks constructed after May 8, 2018 shall be designed to completely drain the entire contents to a sump in a manner that leaves no more than 75 gallons of free-standing liquid in the tank or the sump. New tanks with sump diameters less than 60 inches or sump drain lines less than 6 inches in diameter shall require a case-by-case determination for allowable free-standing liquid volume. **(05/18)**

F. Tanks constructed or modified after May 8, 2018 shall be equipped with a connection to a vapor recovery system, or with a fitting that enables connection to such system. The vapor recovery system shall route vapors from the vapor space under the landed roof to a control device. **(05/18)**

G. Except for labels, logos, etc. not to exceed fifteen (15) percent of the tank total surface area, uninsulated tank exterior surfaces exposed to the sun shall be white or aluminum except where a dark color is necessary to help the tank absorb or retain heat in order to maintain the material in the tank in a liquid state. The following existing tanks are exempt from the white or aluminum requirement: Fixed-Roof Tanks 41, 42, 59, 60, 60A, 73, 73A, 1012, and 1013. Storage tanks must be equipped with permanent submerged fill pipes. **(10/13)**

H. The permit holder shall maintain records which includes tank identification number, control method used, tank capacity in gallons, name of the material stored, VOC molecular weight, VOC monthly average temperature in degrees Fahrenheit, VOC vapor pressure at the monthly average material temperature in psia, VOC throughput for the previous month and year-to-date. Records of VOC monthly average temperature are not required to be kept for unheated tanks which receive liquids that are at or below ambient temperatures. **(8/10)**

6. Pressure tanks shall be maintained such that there are no emissions of VOC to the atmosphere during normal operating conditions (including filling operations). If emissions occur during normal operations, they shall be routed to a flare which achieves at least 98 percent destruction efficiency.

7. Marine vessel loading operations at this facility are limited to the handling of gasolines, gasoline blending components, gasoline boiling range products, toluene, benzene, distillates, black oils, and light aromatics. Benzene, toluene, and light aromatics shall only be loaded at one dock at any time, including the docks authorized in this permit and Dock 54E, authorized in Permit No. 2231. **(06/15)**

8. Inerted Vessel Loading and Testing **(06/15)**

A. The following additional requirements apply to loading of hydrocarbons with VOC vapor pressure greater than or equal to 0.50 psia onto inerted marine vessels that cannot be loaded under vacuum as specified in Condition 11.

(1) Before loading, the owner or operator from the marine terminal shall verify that the marine vessel has passed an annual vapor tightness test as specified in 40 CFR §63.565(c) (September 19, 1995) or 40 CFR §61.304(f) (October 17, 2000).

(2) The pressure at the vapor recovery connection of an inerted marine vessel must be maintained at no more than 1.6 psig or 0.2 psig below the lowest vessel cargo tank or vent header pressure relief valve setting for the vessel being loaded, whichever is lower. Pressure shall be continuously monitored and recorded while the vessel is being loaded.

(3) The loading rate shall be continuously monitored and recorded during loading. The loading rate must not result in an exceedance of the permit emissions cap and must be limited to the rate necessary to avoid exceeding the maximum pressure as required by paragraph B of this condition.

B. VOC collection efficiency tests of inerted ocean-going marine vessels shall be conducted as follows to demonstrate a collection efficiency of 99.9% as represented in the permit application.

(1) Testing shall be conducted using the protocol agreed to by the Executive Director. Any revision to the approved testing protocol shall require approval from the Executive Director prior to implementation. The permittee shall maintain a copy of the approved protocol on site.

(2) Complying test results shall be obtained for a minimum of 6 vessels or the number of inerted ocean-going vessels loaded, whichever is less, for each calendar year upon written approval by the Executive Director of the test protocol. Testing may be suspended after five years provided that all tests confirm a collection efficiency of 99.9% or greater.

Complying test results shall be obtained at a pro-rated number for the 2015 Calendar Year. The rate shall be proportional to 6 vessels tested over a 12 month period.

(3) The results of the tests shall be submitted to the TCEQ Air Permits Division and the TCEQ Regional Office within 60 days of the end of each quarter.

(4) The TCEQ Regional Office must be notified at least 48 hours prior to testing. The facility owner or operator may request a waiver from the 48 hour advance notification requirement from the TCEQ Regional Office.

(5) The permit holder shall maintain the following records for each vessel tested for a period of 5 years from the date of testing:

i. The most recent vapor tightness certificate;

ii. A recent, completed Standard Tanker Chartering Questionnaire form (Q88); and

iii. Records of each incidence of testing conducted in accordance with this condition.

9. Loading emissions from marine loading operations at docks other than Dock 54E shall be routed to thermal oxidizers (EPNs 294-1, 294-2, and 294-3). These thermal oxidizers (vapor combustors) shall operate at a minimum VOC destruction efficiency of 99 percent by weight and operate with greater than a stoichiometric quantity of air at all times. During loading operations, the minimum operating temperature of the thermal oxidizers shall be 1250°F. Records of thermal oxidizer operating temperatures shall be kept for each loading operation. **(11/13)**

10. Loading rates at the marine docks other than Dock 54 shall be reduced as needed in the event that two of the thermal oxidizers (vapor combustors) are inoperable. Loading of hydrocarbons with a true vapor pressure of greater than or equal to 0.5 psia at maximum temperature shall cease in the event that all thermal oxidizers are inoperable. Records shall be kept for each loading operation and shall include the name and quantity of material loaded. Operation without visible liquid leaks or spills shall be maintained at all loading/unloading facilities, regardless of vapor pressure. **(2/13)**

11. The holder of this permit shall maintain marine vessel loading equipment in such a manner that vapor-tight connections are made between the dock and the marine vessel. A blower system shall be installed which will produce a vacuum during vapor controlled loading operations (liquid VOC vapor pressure greater than or equal to 0.50 psia except when loaded to an inert marine vessel). Should the blower system cease operating for any reason, loading operations shall cease immediately. The vacuum system shall be repaired before loading operations can resume. A pressure/vacuum gauge shall be installed on the suction side of the loading rack blower such that a negative pressure can be verified in the vapor return header, except for loading of inert gas system

marine vessels. The vacuum shall be recorded every 15 minutes when loading, except for loading of inert gas system marine vessels. A vacuum of at least 1.5 inches of water shall be maintained during loading. Records of all blower system repairs and associated downtime shall be maintained. **(06/15)**

12. The marine dock thermal oxidizers (vapor combustors) shall be equipped with an automatic ignition system that assures gas ignition before loading and provides immediate notification of appropriate personnel when the ignition system ceases to function. **(06/15)**

13. Uncontrolled loading of marine vessels without the use of vapor control is allowable under this permit for those materials that have a true vapor pressure of less than 0.50 psia at the actual loading temperature, provided that all applicable federal and state rules and regulations are met.

14. All flares shall be designed and operated in accordance with the following requirements:

    A. The combined refinery fuel natural gas and waste stream to the flare shall meet the 40 CFR § 60.18 specifications of minimum heating value and maximum tip velocity under normal, upset, and maintenance flow conditions. Compliance with this condition shall be demonstrated by monitoring required in Paragraph D of this condition. Flare testing per 40 CFR § 60.18(f) may be requested by the TCEQ Houston Regional Office, in addition to New Source Performance Standards (NSPS) or federal requirements, to demonstrate compliance with this condition. Testing to confirm the heating value (Btu per standard cubic feet [scf]) may be requested by the TCEQ Houston Regional Office to demonstrate compliance with this condition.

    B. The flare(s) shall be operated with a pilot flame present at all times and have a constant pilot flame or an automatic re-ignition system. The pilot flame shall be monitored by a thermocouple or an infrared monitor.

    C. The flares shall be operated with no visible emissions except periods not to exceed a total of five minutes during any two consecutive hours. This shall be ensured by the use of steam assist to the flare (for steam-assisted flares). The permit holder shall ensure proper flare operation through monitoring by Paragraph D of this condition.

    D. The holder of this permit shall install a continuous flow monitor that provides a record of the vent stream flow to the flare. The flow monitor sensor should be installed in the vent stream such that the total vent stream to the flare is measured. The average hourly values of the flow shall be recorded and maintained electronically. The holder of this permit shall provide the daily average flow rate (24-hour average) to each flare. These monitors shall be operational no later than July 13, 2010.

    The holder of this permit shall conduct an analysis (grab sample) of the flare composition (total VOC, benzene, hydrogen sulfide (H_2S), and Btu content) on or before May 31, 2007. The analysis shall be conducted on a semiannual basis (once during the summer months and once during the winter months). The holder of this permit may submit a request to the TCEQ Houston Regional Office to reduce the sampling frequency. The sampling shall be conducted such that the total vent stream to the flare is included in the analysis. Records of the grab sampling results, including flare identification number, sampling date, sampling location, flare composition, and calculated net heating value in Btu/scf for each flare, shall be maintained. **(PSD) (9/06)**

15. Safety relief valves that discharge to the atmosphere only as a result of fire shall be equipped with a rupture disc and pressure gauge. The pressure gauge shall be installed between the relief valve and the rupture disc to monitor disc integrity.

    Atmospheric relief valves which are not equipped with a rupture disc shall be monitored for leaks on a quarterly basis with an approved gas analyzer beginning no later than July 13, 2007. A leak shall be defined as 500 parts per million by volume (ppmv). There shall be no variance for inaccessible valves which are not equipped with a rupture disc and pressure gauge or pressure transmitting device.

    All leaking discs shall be replaced at the earliest opportunity, but no later than the next unit shutdown. Discs to be replaced shall be identified on an equipment list, and this list shall be made available to TCEQ or local air pollution control program representative.

    Records of quarterly atmospheric relief valve monitoring results, including the relief valve identification, monitoring date, monitoring result, disk replacement or installation date, and next unit shutdown date after leak discovery shall be maintained. **(8/10)**

Sulfur Recovery/Amine Treating Units

16. The minimum sulfur recovery efficiency for these permitted units shall be 99.8 percent. The sulfur recovery efficiency shall be determined by calculation as follows:

$$\text{Efficiency} = \frac{(\text{S recovered})*(100)}{(\text{S acid gas})}$$

    Where:

    Efficiency = sulfur recovery efficiency, percent
    S recovered = (S acid gas - S stack, or S produced), long tons per day (LTPD)
    S acid gas = (S recovered plus S stack), LTPD
    S stack = sulfur in incinerator stack, LTPD

    The average sulfur emission reduction efficiency (sulfur recovery efficiency) shall be demonstrated for each 24-hour period by a mass balance calculation using data obtained from the incinerator stack sulfur dioxide (SO_2) monitor, sulfur production records, stack mass flow rate, and other process flow data. Records of the calculated recovery efficiency, sulfur in the incinerator stack, sulfur produced, sulfur in the acid gas, the compliance calculations, and a detailed example of the compliance calculations shown above shall be maintained on-site. The sulfur recovery efficiency of this condition is not applicable during start-up, shutdown, or upset conditions if proper procedures of 30 TAC Chapter 101 are followed. **(PSD)**

17. The total sulfur recovered from the combined SRU Trains (Trains 1 through 4) shall not exceed 1,462.5 LTPD of sulfur (based on a 24-hour period). At no time during normal operation shall the excess capacity be less than 75 percent redundancy. **(PSD) (11/30)**

18. The SRU thermal reactors that receive ammonia (NH_3) acid gas from the sour water stripper overheads shall at all times be operated with a stable flame, and the SRUs shall operate with a flame temperature within recommended design specifications, but shall operate at no less than

2000°F. The flame temperature of each SRU thermal reactor shall be continuously monitored and recorded.

19. All acid gas streams from the amine regeneration units, and sour water stripper overheads, containing H_2S shall be routed to the SRUs or other process units under normal operating conditions. It is not permissible under any conditions to vent acid gases directly to the atmosphere. **(PSD)**

20. Emissions from the sulfur pits, sulfur storage, and sulfur loading operations shall be collected by a vapor collection system and routed either back to the SRU thermal reactor or to the SRU Tail Gas Incinerator (TGI). **(PSD)**

21. The TGI shall operate with no less than 99.9 percent efficiency in disposing of the acid gas waste streams. The TGI firebox exit temperature shall be maintained at not less than 1200°F and exhaust oxygen concentration not less than 1.2% percent while waste gas is being fed into it prior to initial stack testing. After the initial stack test has been completed, the TGI shall be operated with not less than the oxygen concentration maintained during the last satisfactory stack test performed in accordance with Special Condition No. 41. If stack testing in the TGI exhaust indicates that a higher temperature is necessary to obtain a minimum H_2S and VOC destruction efficiency of 99.9 percent, then the temperature obtained during the stack test will become the new minimum incinerator firebox chamber temperature. The firebox chamber 6 minute average temperature shall be maintained above the hourly average temperature maintained during the last satisfactory stack test performed in accordance with Special Condition No. 41. **(PSD) (11/18)**

    The TGI firebox exit temperature and oxygen concentration shall be continuously monitored and recorded. The temperature measurement device shall reduce the temperature readings to an averaging period of 6 minutes or less and record it at that frequency. The temperature monitor shall be installed, calibrated at least annually, and maintained according to the manufacturer's specifications. The device shall have an accuracy of the greater of ±2 percent of the temperature being measured expressed in degrees Celsius or ±2.5ºC.

    The TGI exhaust stack flow rate shall be continuously monitored and recorded. The flow shall be recorded at least every 15 minutes and the hourly average flow rate shall be recorded. Each flow monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, or at least annually, whichever is more frequent, and shall be accurate to within 2 percent of span or 5 percent of the lesser of the design value or the flow measured during the most recent stack test.

    Quality assured (or valid) data must be generated when the tail gas incinerator is operating except during the performance of a daily zero and span check. Loss of valid data due to periods of monitor break down, out-of-control operation (producing inaccurate data), repair, maintenance, or calibration may be exempted provided it does not exceed 5 percent of the time (in minutes) that the TGI operated over the previous rolling 12 month period. The measurements missed shall be estimated using engineering judgment and the methods used recorded.

22. The SRU TGIs shall operate with no visible emissions except for uncombined steam. The in-stack concentration of SO_2 from the tail gas incinerator shall not exceed 250 ppm by volume calculated as an hourly average on a dry and air-free basis**. (PSD) (11/18)**

23. **Contingency Plan for the SRU**

Should there be loss of sulfur recovery potential from the Claus trains, TGTU, or TGIs, any combination of the following steps shall be taken as soon as possible, but no later than two hours from the start of the event:

A. Reroute the maximum amount of acid gas to the operating SRUs or equipment (such as the remaining sulfur recovery trains, TGTU, and TGI). This action can include increasing the oxygen (O_2) injection rate to add SRU capacity.

B. Reroute any remaining acid gas to the TGIs. If the TGIs are not operable, the acid gas should be routed to the emergency flares.

C. Shut down the sour water strippers and accumulate sour water in tankage for future processing.

D. Reduce production, reduce charge rates at upstream units, and switch to lower-sulfur purchased gas oils and crude oils as necessary to reduce the amine loading and cease acid gas flaring within eight hours of the event. This action may include shutting down one and/or all units which supply acid gas to the SRU complex.

E. Any other action not listed that will allow the SRU to recover from the loss of sulfur recovery potential. All actions conducted under this paragraph shall be documented. The documentation shall include the specific action taken, time the action was taken, effect on upstream/downstream facilities (heaters, other control devices, etc.), and overall effect on emissions from the SRU or other facilities. This documentation shall be included in any reports submitted to the TCEQ Houston Regional Office or local air pollution control program representative. This information shall also be maintained on-site and made available to TCEQ or local air pollution control program representatives upon request.

The permit holder shall meet the recordkeeping and reporting requirements of 30 TAC §§ 101.201 and 101.211 in addition to this permit condition.

24. Records shall be maintained for all SRU, Tail Gas Treating Unit (TGTU), and TGI downtime. These records shall include the date and duration of downtime, amount of bypassed acid gas flared, the cause of the downtime, and corrective action taken. The permit holder shall meet the recordkeeping and reporting requirements of 30 TAC §§ 101.201 and 101.211 in addition to this permit condition.

25. The sour water stripper system feeding the SRUs shall have a minimum on-line retention and separation (hold up) time of three days based on normal operational levels and maximum expected feed rates.

26. The retention time of the rich amine and lean amine drums shall meet at least 30 minutes of retention at maximum production levels.

FCCUs

27. The final emission caps are based on FCCU 3 (Emission Point No. [EPN] 34A) meeting the following concentrations, averaged over a one-hour period.

Pollutant	Concentration
carbon monoxide (CO)	500 ppmv
SO_2	200 ppmv
nitrogen oxide (NO_x)	200 ppmv
VOC	10 ppmv

The initial emission caps are based on the following: 500 ppmv CO from FCCU 3. **(05/17)**

28. The final hourly emission cap and individual annual emission limit for FCCU 3 are based on the FCCU stack meeting 0.914 pounds of PM per 1,000 pounds of coke burn-off. The individual hourly and annual emission limits for FCCU 3 are based on the FCCU 3 stack meeting 0.33 pounds of H_2SO_4 per 1,000 pounds of coke burn-off. The PM and H_2SO_4 emissions will be measured per the EPA Methods 5B and 8/TCEQ 24 or other applicable method approved by the TCEQ). **(05/17)**

29. [RESERVED]

30. The opacity of emissions from the FCCU shall not exceed 20 percent averaged over a six minute period, as determined by an opacity monitoring device or trained observer, except as provided for in 30 TAC § 111.111(a)(1)(E).

31. The seven-day rolling average of NO_x and SO_2 concentration limits below shall not apply during periods of start-up, shutdown, or malfunction. **(05/17)**

    A. [RESERVED]

    B. FCCU 3 NO_x Concentration Limits

    If the permit holder has installed a selective catalytic reduction (SCR) unit on FCCU 3, then beginning July 1, 2007, FCCU 3 shall comply with a NO_x limit of 20 ppmvd at zero percent O_2 on a 365-day rolling average and 40 ppmvd at zero percent O_2 on a 7-day rolling average basis.

    If the permit holder has not installed an SCR on FCCU 3, then beginning July 1, 2007, FCCU 3 shall comply with a NO_x limit of 30 ppmvd at zero percent O_2 on a 365-day rolling average and 60 ppmvd at zero percent O_2 on a 7-day rolling average basis.

    The seven-day rolling average may increase temporarily to 120 ppmvd if, pursuant to the Consent Decree amendment issued October 7, 2005, the permit holder submits and EPA approves a report detailing reasons for the outage(s) of the SCR or NO_x control device within 30 days after the outage occurs. The outages can only be due to reasons other than startup, shutdown or malfunction.

    C. [RESERVED]

    D. FCCU 3 SO_2 Concentration Limits

    Beginning July 1, 2007, FCCU 3 (EPN34A) shall comply with a SO_2 limit of 25 ppmvd at zero percent O_2 on a 365-day rolling average and 50 ppmvd at zero percent O_2 on a 7-day rolling average basis.

32. The FCCU 3 Regenerator Scrubber (EPN 34A) liquid to gas ratio and gas pressure drop shall be continuously monitored and be maintained greater than the minimum one hour average value observed in the last satisfactory stack test performed in accordance with Special Condition 41. The initial stack test for EPN 34A was completed on May 6, 2008. A subsequent stack test will be performed in accordance with Special Condition 41 upon completion of the FCCU 3 Regeneration Project proposed in the amendment, PI-1 dated April 26, 2011.

    The flow rates and pressures shall be recorded every 6 minutes as six minute averages and the pH shall be recorded every 15 minutes as 15 minute averages. Each flow and pressure monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, or at least annually, whichever is more frequent, and shall be accurate to within 2 percent of span or 5 percent of the design value.

    Quality assured (or valid) data must be generated when the FCCU is operating except during the performance of a daily zero and span check, if conducted. Loss of valid data due to periods of monitor break down, out-of-control operation (producing inaccurate data), repair, maintenance, or calibration may be exempted provided it does not exceed 5 percent of the time (in minutes) that the FCCU operated over the previous rolling 12 month period. The measurements missed shall be estimated using engineering judgment and the methods used recorded. **(12/11)**

Fired Units (Heaters and Boilers)

33. The final emission caps are based on fuel gas (used to fire all heaters, boilers, oxidizers, incinerators, flares, and other combustion devices) having an H_2S concentration of 162 ppmv or 0.1 grain per dry standard cubic foot on a one-hour average basis. The H_2S concentration in the fuel gas system shall be continuously monitored and recorded. **(PSD) (10/10)**

34. The opacity from all heaters, boilers, etc., shall not exceed 5 percent averaged over a six minute period, except for those periods described in 30 TAC § 111.111(a)(1)(E).

35. The final emissions cap is based on a combined average NO_x emission value of 0.035 lb NO_x/MMBtu from all boilers and heaters. For the final ammonia emission cap, any heater with a SCR shall not exceed 10 ppmv ammonia slip. **(05/16)**

36. The following heaters shall meet the listed limits during routine operations. The heaters shall be excluded from the limits when maintenance, startup, and shutdown is performed on each heater. **(11/18)**

    A. RHU-502B (part of EPN 484) shall not exceed a 0.035 lb NO_x/MMBtu on a 365 day rolling average.

    B. RHU-601B (EPN 485) shall not exceed a 0.035 lb NO_x/MMBtu on a 365 day rolling average.

    C. DHT-101B and DHT-201B shall not exceed 0.01 lb NO_x/MMBtu on a 365 day rolling average, and shall not exceed CO on an annual average of 25 ppmv.

37. The ULC-103B is limited to firing no more than 99 MMBtu/hr. Records verifying the firing rate for this unit shall be maintained on-site.

38. Emissions of NO_x from heater 401-BC (EPN 44) shall meet the following: **(11/18)**

A. Emissions of NO_x from heater 401-BC (EPN 44) shall not exceed 0.10 lbs NO_x/MMBTU (hourly block average) at any time, except during the operating modes defined in B of this permit condition, and 0.035 lbs NO_x/MMBTU on an annual basis.

B. Operating modes during which the hourly block average NO_X emission limits in A of this condition do not apply are defined as follows:

(1) Hot Standby Mode, defined as the period when the heater is firing at 50 percent or less of the maximum allowable firing rate and no hydrocarbon feed is being charged to the heater.

(2) Decoking Mode, defined as the period starting when air is introduced to the heater for the purpose of decoking and ending when air flow to the heater ceases.

(3) Start-up and Refractory Dry Out Modes, defined as the period beginning when fuel is introduced to the heater and ending when the heater process outlet temperature reaches the desired operating temperature for 15 consecutive minutes. A planned startup for each heater firebox is limited to 96 hours at 25 percent or less of the maximum allowable firing rate.

(4) Shutdown Mode, defined as the period beginning when the heater outlet temperature first drops below its stable operating temperature and ending when the fuel flow to the heater ceases.

(5) Feed-in Mode, defined as the period beginning when hydrocarbon feed is introduced to the heater and ending when the heater reaches 70 percent of the maximum allowable firing rate.

(6) Feed-out Mode, defined as the period beginning when a heater drops below 70 percent of the maximum allowable firing rate and ending when hydrocarbon feed to the heater ceases.

C. The emission rate limits on the MAERT remain in effect during the operating modes defined in B of this condition.

Wastewater

39. Emissions from wastewater process equipment shall be controlled as follows:

A. Emissions from the dissolved air flotation, gravity thickener, and API No. 2 shall be routed to a thermal oxidizer capable of obtaining a VOC destruction efficiency of 99.9 percent.

B. Emissions from APIs 1 and 3 shall be routed to a carbon adsorption system. The carbon adsorption system shall be installed and operating no later than July 13, 2010. The carbon adsorption system shall meet the requirements of Special Condition No. 52 of this permit.

C. Wastewater process equipment upstream of the biological treatment units (activated sludge) shall either be covered and/or routed to a control device (either a thermal oxidizer, flare, or carbon canister system). **(10/10)**

Initial and Periodic Sampling Requirements

40. Sampling port(s) and platforms(s) shall be incorporated into the design of the combustion source stack(s) per specifications in the attachment entitled "Chapter 2, Stack Sampling Facilities" of the TCEQ Sampling Procedures Manual. Platform(s) will not be necessary for existing stacks of combustion facilities that will not be equipped with continuous emissions monitoring system (CEMS) and do not currently have platform(s) included in their design. Alternate sampling facility designs may be submitted for approval by the Executive Director of the TCEQ.

41. The holder of this permit shall perform stack sampling and other testing, as required, to establish the actual pattern and quantities of air contaminants being emitted into the atmosphere from the following sources: **(05/17)**

    FCCU 3 Stack (EPN 34A)

    SRU TGI Common Stack (EPN 384)

    Marine Dock Thermal Oxidizers (Vapor Combustors) (EPNs 294-1, 294-2, 294-3)

    All boilers and heaters with firing rates of 40 MMBtu/hr or greater

    In addition, common stacks (if any) containing units capable of 40 MMBtu/hr or greater shall also be sampled.

    The permit holder is responsible for providing sampling and testing facilities and conducting the sampling and testing operations at his expense. Sampling shall be conducted in accordance with the appropriate procedures of the TCEQ Sampling Procedures Manual and the EPA Reference Methods.

    Requests to waive testing for any pollutant specified in this condition shall be submitted to the TCEQ Air Permits Division. Test waivers and alternate/equivalent procedure proposals for 40 CFR Part 60 testing which must have EPA approval shall be submitted to the TCEQ Regional Director. **(1/14)**

    A. The TCEQ Houston Regional Office shall be contacted as soon as testing is scheduled, but not less than 45 days prior to sampling to schedule a pretest meeting.

       The notice shall include:

       (1) Date for pretest meeting.

       (2) Date sampling will occur.

       (3) Name of firm conducting sampling.

       (4) Type of sampling equipment to be used.

       (5) Method or procedure to be used in sampling.

       The purpose of the pretest meeting is to review the necessary sampling and testing procedures, to provide the proper data forms for recording pertinent data, and to review the format procedures for the test reports. The TCEQ Houston Regional Director must approve any deviation from specified sampling procedures.

    B. Air contaminants emitted from the listed sources to be tested for include (but are not limited to) the following: **(11/15)**

Source	Air Contaminants
FCCU	NO_x, CO, SO_2, VOC, TSP*, PM_{10}*, H_2SO_4, and O_2
SRU TGI(s)	SO_2, H_2S, NO_x, CO, VOC, and O_2
Boilers, Heaters, Furnaces, etc	NO_x, CO, and O_2
Marine Dock Thermal Oxidizers (Vapor Combustors)	NO_x, CO, VOC, and O_2
Units equipped with ammonia injection	ammonia

* TSP - total suspended particulate
* PM_{10} - particulate matter equal to or less than 10 microns in diameter

C. Sampling shall occur within 60 days after achieving the maximum production rate at which the facility will be operated, but no later than 180 days after start-up following modification or installation of a emission source (facility), or within 60 days after achieving normal operation (for those units being restarted due to Hurricane Rita), and other such times as determined necessary to verify compliance with the emissions cap as required by the TCEQ Houston Regional Director or the TCEQ Executive Director. Requests for additional time to perform sampling shall be submitted to the TCEQ Houston Regional Office.

The permit holder may submit a request to perform representative sampling for combustion units that are similar in function, heat input, etc. The request shall be submitted to, and approved by, the TCEQ Houston Regional Office before sampling begins.

D. The EPN being tested shall operate at maximum production, loading, or firing rates during stack emission testing. Primary operating parameters that enable determination of production rate shall be monitored and recorded during the stack test. These parameters are to be determined at the pretest meeting. If the EPN is unable to operate at maximum rates during testing, then additional stack testing may be required when higher firing rates are achieved. (Additional testing will not be required if the EPN is equipped with a CEMS.)

E. Copies of the final sampling report shall be forwarded to the TCEQ within 60 days after sampling is completed. Sampling reports shall comply with the attached provisions of Chapter 14 of the TCEQ Sampling Procedures Manual. The reports shall be distributed to the TCEQ Houston Regional Office.

F. Stack sampling for those units which are not equipped with a CEMS shall be repeated every five years after the initial sampling in conformity with A, B, and D of this condition. Facilities which are not being modified and have been tested in the last five years shall be tested within five years of the last test date (even if those sources have not been tested for VOC during previous tests).

G. For fired units equipped with ammonia injection, the initial compliance stack test shall test for the presence of ammonia slip in the stack. After the initial stack test one of the following methods shall be used:**(11/18)**

(1) Monitoring conducted pursuant to Special Condition No. 47.

(2) Grab samples for ammonia shall be conducted weekly during the first 60 days of operation. After operating procedures have been developed to prevent excess amounts of ammonia from being injected, the frequency of ammonia grab sampling

can be reduced to a quarterly basis. If the grab samples exceed 10 ppmv at any time, the holder of this permit shall return to weekly ammonia sampling until such time as repairs are conducted, or the sampling indicates that the ammonia slip is 5 ppmv or less.

H. The FCCU shall be stack sampled for the presence of H_2SO_4 within 60 days after achieving normal operation (after the restart due to Hurricane Rita). The holder of this permit shall submit a permit amendment application within 60 days of completing the stack sampling of the FCCU to incorporate the H_2SO_4 into an emissions cap, or list the H_2SO_4 emissions as an individual emission limitation. If necessary, the holder of this permit shall include netting calculations, and/or Prevention of Significant Deterioration forms, tables, etc. in the amendment package. The amendment package shall include all calculations, assumptions, best available control technology (BACT) determinations, and a proposal for determining compliance with the short-term and annual emission rate or caps. FCCU 3 satisfied this condition with the PSD amendment application (PI-1 dated April 26, 2011). **(05/17)**

I. Within 180 days after the issuance of the permit amendment dated December 8, 2014, the holder of this permit shall perform stack sampling and other testing, as required, to establish the actual pattern and quantities of HCN being emitted into the atmosphere from the FCCU (EPN: 34A) to demonstrate compliance with the MAERT.

The FCCU Regenerator shall operate at the maximum coke burn rate during stack emission testing. These conditions/parameters and any other primary operating parameters that affect the emission rate shall be monitored and recorded during the stack test. Any additional parameters shall be determined at the pretest meeting and shall be stated in the sampling report. Permit conditions and parameter limits may be waived during stack testing performed under this condition if the proposed condition/parameter range is identified in the test notice specified in paragraph A and accepted by the TCEQ Regional Office. Permit allowable emissions and emission control requirements are not waived and still apply during stack testing periods.

42. The holder of this permit shall submit a sampling and testing plan to the TCEQ Houston Regional Office (with a copy routed to the TCEQ Air Permits Division) for review and approval no later than September 13, 2005.

The sampling plan shall specify the sampling methods and other testing, as necessary, to establish the emissions (lb/hr and TPY) of VOC being emitted to the atmosphere from the wastewater system associated with this permit. Sampling and testing shall begin within 60 days of plan approval.

Within 30 days after completion of the sampling, copies of the sampling report shall be submitted to the following:

One copy to the TCEQ Air Permits Division, Austin.

One copy to the TCEQ Houston Regional Office.

Sampling of the wastewater system, as specified in this section, is waived if the permit holder determines that sufficient information is currently available to adequately model the wastewater treating system through the use of Water 8 or Water 9 wastewater model. The applicant shall submit revised emission calculations using one of these models, to the Air Permits Division for

review and approval, no later than September 13, 2005 and one of the following permit applications.

A. If the wastewater models show a decrease in the emission contribution from the wastewater treating facilities compared to the emissions obtained from using AP 42 emission factors, the holder of this permit shall submit a permit alteration to adjust emissions cap to reflect the emissions obtained from the use of the water models.

B. If the wastewater models show an increase in emissions compared to the emissions obtained from using AP-42 emission factors, the holder of this permit shall submit a permit amendment to increase the final emissions cap. **(8/10)**

Ongoing Monitoring Requirements

43. The holder of this permit shall install, calibrate, and maintain a CEMS to measure and record the in-stack concentrations of the following compounds from all of the following facilities:

A. FCCU Stack (EPN 34A): SO_2, NO_x, CO, Opacity, and O_2

B. SRU TGI Stacks (EPNs 384): SO_2 and O_2.

C. A CEMS to measure and record the in-stack concentrations of NO_x, CO, and O_2 shall be operational and used to monitor emissions from any boiler, heater, or combustion device with a maximum firing rate greater than or equal to 100 MMBtu/hr.

D. A CEMS to measure and record the in-stack concentrations of NO_X, CO, and O_2 shall be operational and used to monitor emissions from EPN: DHT-101B and DHT-201B. **(PSD)(11/18)**

44. Each CEMS required by these conditions shall comply with the following:

A. The CEMS shall meet the design and performance specifications, pass the field tests, and meet the installation requirements and the data analysis and reporting requirements specified in the applicable Performance Specification Nos. 1 through 9, 40 CFR Part 60, Appendix B. If there are no applicable performance specifications in 40 CFR Part 60, Appendix B, contact the TCEQ Air Permits Division for requirements to be met.

B. Paragraph B(1) of this condition applies to sources subject to the quality-assurance requirements of 40 CFR Part 60, Appendix F; Paragraph B(2) of this condition applies to all other sources:

(1) The permit holder shall assure that the CEMS meets the applicable quality assurance requirements specified in 40 CFR Part 60, Appendix F, Procedure 1. Relative accuracy exceedances, as specified in 40 CFR Part 60, Appendix F, § 5.2.3 and any CEMS downtime shall be reported to the TCEQ Houston Regional Director, and necessary corrective action shall be taken. Supplemental stack concentration measurements may be required at the discretion of the TCEQ Houston Regional Director.

(2) The system shall be zeroed and spanned daily, and corrective action taken when the 24-hour span drift exceeds two times the amounts specified in the applicable Performance Specification Nos. 1 through 9, 40 CFR Part 60, Appendix B, or as specified by the TCEQ if not specified in Appendix B. Zero and span is not required on

weekends and plant holidays if instrument technicians are not normally scheduled on those days.

Each monitor shall be quality-assured at least quarterly using Cylinder Gas Audits (CGA) in accordance with 40 CFR Part 60, Appendix F, Procedure 1, Section 5.1.2, with the following exception: a relative accuracy test audit (RATA) is not required once every four quarters (i.e., four successive quarterly CGA may be conducted). An equivalent quality-assurance method approved by the TCEQ may also be used. Successive quarterly audits shall occur no closer than two months.

All CGA exceedances of ±15 percent accuracy indicate that the CEMS is out of control.

C. The monitoring data shall be reduced to hourly averages concentrations at least once every day, using a minimum of four equally-spaced data points from each one-hour period. The individual average concentrations shall be reduced to units of lb/hr at least once every week as follows:

The measured hourly average concentration from the CEMS shall be multiplied by the exhaust gas flow rate of the source (measured by true exhaust flow meters, or measured during the latest stack test performed in accordance with Special Condition No. 41, or calculated using fuel flow meters required by §117.340) to determine the hourly emission rate.

D. All monitoring data and quality-assurance data shall be maintained by the source. The data from the CEMS may, at the discretion of the TCEQ, be used to determine compliance with the conditions of this permit.

E. The TCEQ Houston Regional Office shall be notified at least 30 days prior to any required RATA in order to provide them the opportunity to observe the testing.

If a temporary CEMS replacement analyzer is used in-place of a permanent non-redundant CEMS analyzer, the 30 day notification requirement is waived for the temporary CEMS and reinstallation of the rebuilt CEMS (in the case of a rebuild of an existing CEMS), and notification shall be made as soon as practicable. The temporary CEMS analyzer shall meet the applicable requirements of the permanent non-redundant CEMS analyzer which it replaced, and shall use the same probe and interface. **(11/15)**

F. Quality-assured (or valid) data must be generated when the facility generating emissions is operating except during the performance of a daily zero and span check. Loss of valid data due to periods of monitor break down, out-of-control operation (producing inaccurate data), repair, maintenance, or calibration may be exempted provided it does not exceed 5 percent of the time (in minutes) that the facility generating emissions operated over the previous rolling 12-month period. The measurements missed shall be estimated using engineering judgement and the methods used recorded. Options to increase system reliability to an acceptable value, including a redundant CEMS, may be required by the TCEQ Houston Regional Director. **(PSD) (8/10)**

45. Boilers, heaters, etc., with maximum firing rates of greater than or equal to 40 MMBtu/hr and less than 100 MMBtu shall be sampled in accordance with this condition. The terms of this condition are effective upon implementation of BACT for a particular device or for combustion devices for which additional controls are not anticipated no later than July 13, 2006.

After completion of the initial stack test, the holder of this permit shall conduct annual stack tests for NO_x and CO. The stack test shall be comprised of no less than the average of three one-hour readings for each pollutant.

The results of the stack test shall be recorded in terms of ppm and converted into values of lb/hr and TPY within 30 days of sampling (unless a mass emission rate can be estimated at the time of the test). The annual stack tests shall start after the initial stack test for each unit and shall occur during the same quarter annually. Stack tests for those boilers and heaters that will not be modified, and are not required to complete the initial stack test in the first year from the issuance of the flexible permit (because they were tested within the last five years), will be completed no later than July 13, 2006. The SO_2 emissions from the unit being tested shall also be estimated on an annual basis using the H_2S concentrations obtained from the H_2S fuel gas monitoring system and the fuel flow rate to the unit being tested.

In addition to the above testing requirements, the fuel flow rate (along with other parameters determined at the pretest meeting to be essential for monitoring a unit's performance) shall be continuously monitored and recorded. Beginning no later than September 13, 2005, the heating value of the fuel (Btu/scf) shall be determined on a quarterly basis through grab sampling.

Should the stack test from a particular unit indicate an exceedance of the short-term (lb/hr) and/or annual (TPY) emission rate used in the emission cap calculation, the applicant shall provide adequate information to demonstrate continuing compliance with the emissions cap.

Records shall be maintained indicating any exceedance of units represented firing rates. Should the firing rate of any unit exceed its permit representations (represented contribution to the emission cap), the holder of this permit shall provide adequate information to demonstrate continuing compliance with the emissions cap. **(8/10)**

46. For boilers, heaters, etc., with maximum firing rates less than 40 MMBtu/hr, the fuel flow rate shall be continuously monitored and recorded. The heating value of the fuel (Btu/scf) shall be determined on a quarterly basis through grab sampling. In addition, H_2S concentrations shall be obtained from the H_2S fuel gas monitoring system. Records, including the flow, quarterly Btu, and H_2S, shall be maintained and used to indicate any exceedance of a unit's represented firing rate(s). Should the firing rate of any unit exceed its permit representations, the holder of this permit shall provide adequate information to demonstrate continuing compliance with the emissions cap.

47. The permit holder shall continuously monitor ammonia (NH_3) emissions from the heater SCR systems (EPNs DHT-101B and DHT-201B), when SCR is operating, using one of the following methods. **(11/18)**

    A. Install and operate two NOx CEMS, one located upstream of the SCR system and the other located downstream of the SCR system, which are used in association with ammonia injection rate and the following calculation procedure to estimate ammonia slip as specified in 30 TAC §117.8130.

    Ammonia slip, ppmvd = [(a/b x 1,000,000) – c] x d

    Where:

    a = ammonia injection rate (lb/hr)/17 (lb/lb-mole);

    b = dry exhaust gas flow rate (lb/hr)/29 (lb/lb-mole);

    c = change in measured NO_x concentration, ppmvd, across catalyst; and

    d = correction factor.

The correction factor shall be derived during compliance testing by comparing the measured and calculated ammonia slip. The ammonia injection rate and exhaust gas flow rate shall be recorded at least every 15 minutes and be recorded as hourly averages. Each flow monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, or at least annually, whichever is more frequent, and shall be accurate to within 2 percent of span or 5 percent of the design value.

B. Install and operate a dual stream system of NO_x CEMS at the exit of the SCR system. One of the exhaust streams would be routed, in an unconverted state, to one NO_x CEMS and the other exhaust stream would be routed through a NH_3 converter to convert NH_3 to NO_x and then to a second NO_x CEMS. The NH_3 slip concentration shall be calculated from the delta between the two NO_x CEMS readings (converted and unconverted).

All CEMS specified in A and B of this condition must meet the requirements of Special Condition No. 44. Quality-assured (or valid) data must be generated when gas is directed to the SCR system. Loss of valid data due to periods of monitor break down, out-of-control operation (producing inaccurate data), repair, maintenance, or calibration may be exempted provided it does not exceed 5 percent of the time (in minutes) that gas is directed to the SCR system over the previous rolling 12-month period. The measurements missed shall be estimated using engineering judgment and the methods used recorded

C. Install a continuous ammonia monitoring system that meets the design and performance specifications, passes the field tests, and meets the installation requirements and data analysis and reporting requirements specified below:

(1) An initial performance test to verify accuracy of the analyzer. The initial performance test shall be performed within 60 days of achieving maximum production rate at which either of the affected facilities will be operated, but not later than 180 days after initial startup of either such facility. Any analyzer downtime shall be reported to the appropriate TCEQ Regional Manager in a semiannual report, and necessary corrective action shall be taken. Semiannual reports are not required for any 6 month period where no downtime events occurred.

(2) Each monitoring device shall be calibrated and inspected at a frequency in accordance with the manufacturer's specifications or at least annually, whichever is more frequent, and shall be accurate to within 5 percent.

(3) The monitoring data shall be reduced to hourly average concentrations at least weekly, using a minimum of four equally-spaced data points from each one-hour period. The individual average concentrations shall be reduced to units of pounds per hour at least once every calendar quarter as follows:

The measured hourly average concentration from the analyzer shall be multiplied by the exhaust flow rate as measured directly, or determined by monitoring fuel flow and stack oxygen concentration to determine the hourly emission rate.

(4) All monitoring data and quality-assurance data shall be maintained by the permit holder. The data from the analyzer may, at the discretion of the TCEQ, be used to determine compliance with the conditions of this permit.

(5) Quality-assured (or valid) data must be generated when the ammonia injection system is operating. Loss of valid data due to periods of monitor break down, out-of-control operation (producing inaccurate data), repair, maintenance, or calibration may be exempted provided it does not exceed 5 percent of the time (in minutes) that the

ammonia injection system operated over the previous rolling 12-month period. The data availability shall be calculated as the total ammonia injection system operating hours for which quality assured data was recorded divided by the total ammonia injection system operating hours. The measurements missed shall be estimated using engineering judgment and the methods used recorded.

D. Grab samples for ammonia shall be conducted weekly during the first 60 days of operation. After operating procedures have been developed to prevent excess amounts of ammonia from being injected, the frequency of ammonia grab sampling can be reduced to a quarterly basis. If the grab samples exceed 10 ppmv at any time, the holder of this permit shall return to weekly ammonia sampling until such time as repairs are conducted, or the sampling indicates that the ammonia slip is 5 ppmv or less.

48. The holder of this permit shall install, calibrate, maintain, and operate a continuous emission monitoring system (CEMS) to measure and record the refinery fuel gas concentration of H_2S and total sulfur in the refinery fuel gas that is fed to EPNs: DHT-101B and DHT-201B. **(PSD) (11/18)**

A. The CEMS shall meet the design and performance specifications, pass the field tests, and meet the installation requirements and the data analysis and reporting requirements specified in the applicable Performance Specification No. 7, 40 CFR Part 60, Appendix B.

B. The system shall be zeroed and spanned daily and corrective action taken when the 24-hour span drift exceeds two times the amounts specified in 40 CFR Part 60, Appendix B or as specified by the TCEQ if not specified in Appendix B. Zero and span is not required on weekends and plant holidays if instrument technicians are not normally scheduled on those days, unless the monitor is required by a subpart of NSPS or NESHAPS, in which case zero and span shall be done daily without exception.

The monitor shall be quality-assured at least quarterly in accordance with 40 CFR Part 60, Appendix F, Procedure 1, Section 5.1.2.

All cylinder gas audit exceedances of ± 15 percent accuracy and any CEMS downtime shall be reported to the appropriate TCEQ Regional Director in a semiannual report, and necessary corrective action shall be taken. Semiannual reports are not required for any 6 month period where no downtime events occurred. Supplemental stack concentration measurements may be required at the discretion of the appropriate TCEQ Regional Director.

C. The monitoring data shall be reduced to hourly average concentrations at least once every day, using a minimum of four equally-spaced data points from each one-hour period.

D. All monitoring data and quality-assurance data shall be maintained by the source for a period of two years and shall be made available to the TCEQ Executive Director or his designated representative upon request.

E. For NSPS sources subject to Appendix F, the appropriate TCEQ Regional Office shall be notified at least 30 days prior to each annual relative accuracy testing audit in order to provide the TCEQ staff the opportunity to observe the testing.

F. Quality-assured (or valid) data must be generated when the facility generating emissions is operating except during the performance of a daily zero and span check. Loss of valid data due to periods of monitor break down, out-of-control operation (producing inaccurate data), repair, maintenance, or calibration may be exempted provided it does not exceed 5 percent of the time (in minutes) that the facility generating emissions operated over the previous rolling 12-month period. The measurements missed shall be estimated using engineering judgement and the methods used recorded. Options to increase system reliability to an

acceptable value, including a redundant CEMS, may be required by the TCEQ Houston Regional Director.

49. Permit holder shall install, operate, and maintain an oxygen analyzer in the stacks of DHT Heaters (EPN: DHT-101B & DHT-201B). The oxygen analyzer shall continuously monitor and record oxygen concentration in the stack. Readings shall be taken at least once every 15 minutes and the average hourly value shall be recorded each hour. **(PSD) (GHG) (11/18)**

    A. The oxygen analyzer shall be quality-assured at least quarterly using Cylinder Gas Audits (CGA) in accordance with 40 CFR Part 60, Appendix F, Procedure 1, Section § 5.1.2, with the following exception: a relative accuracy test audit (RATA) is not required once every four quarters (i.e., four successive quarterly CGA may be conducted).

    B. The permit holder shall perform an initial visual inspection of the heater and duct work to identify sources of air leaks when the oxygen analyzer indicates an oxygen concentration greater than 10% during normal operation (excluding MSS activities). Subsequent inspections shall be performed as needed on a calendar-month basis.

    C. Oxygen readings recorded during periods of monitoring instrumentation malfunction and maintenance shall be excluded from the calculation of hourly averages provided. The monitoring operation downtime shall not exceed 5% of the heater operating time (in minutes) during any 12-month rolling period.

50. For SRUs that handle ammonia acid gas from sour water stripper overheads, the holder of this permit may do either of the following:

    A. The acid gas exiting the waste heat boilers shall be sampled for ammonia on a quarterly basis. When the ammonia concentration exceeds 300 ppmv, the holder of this permit shall implement procedures or actions that are needed to ensure that the sampled ammonia concentration drops below 300 ppmv by the time the next quarterly sample is taken. Drager tubes or another sampling method, as approved by the TCEQ, shall be used to sample for ammonia.

    B. The holder of this permit shall inspect the sulfur condenser outlets (each sulfur condenser) on each SRU for the presence of ammonia salt formation or buildup. The inspections shall be conducted on an annual basis, and the TCEQ Houston Regional Office shall be informed prior to conducting the inspection (and given the opportunity to observe the sulfur condenser inspection). If ammonia salts are present, the holder of this permit shall implement a monthly ammonia sampling frequency as described in Paragraph A of this condition and the TCEQ Houston Regional Office shall be notified within 30 days.

    The sampling results shall be presented in terms of ppmv. The ammonia sampling of the acid gas exiting the SRUs, or inspections of the sulfur condensers for each SRU shall commence no later than May 13, 2006. Records of sampling/inspection time, date, and sampling/inspection results shall be maintained. **(2/13)**

51. The holder of this permit shall perform sampling and other testing as necessary to establish and demonstrate ongoing compliance with the VOC emission limits, pounds per hour (lb/hr) and tons per year (TPY), from the cooling towers. The cooling tower return water shall be monitored monthly with an approved air stripping system, or approved equivalent, when the cooling towers are in service. The minimum detection level of the testing system shall be equivalent to no more than approximately 5 ppmv. The appropriate equipment shall be maintained so as to minimize fugitive

VOC emissions from the cooling tower. The results of the monitoring and maintenance efforts shall be recorded.

If a leak equivalent to more than the ppmv value listed above is detected, the owner or operator shall repair the leak as soon as practical but not later than 45 calendar days after the holder of this permit receives results of monitoring indicating a leak. Documentation of a decision to delay repair shall state the reasons repair was delayed and shall specify a schedule for completing the repair as soon as possible. For the purposes of this permit condition, delay of repair means exceeding the 45-day time frame described above. Prior to exceeding the time frame described above, all documentation of a decision to delay repair shall be submitted to the TCEQ Houston Regional Office for review and approval.

Delay of repair on heat exchanger systems for which leaks have been detected is allowed if the equipment is isolated from the process. In addition, delay of repair is also allowed in the following situations:

A. If repair is technically infeasible without a shutdown, and a shutdown is expected within the next two months.

B. Delay of repair is also allowed for up to 120 calendar days if necessary parts or personnel were not available.

C. Delay of repair is also allowed if repair is technically infeasible without a shutdown and the shutdown would cause greater emissions than the potential emissions from delaying repair. The owner or operator may delay repair until the next shutdown of the process equipment associated with the leaking heat exchanger. The owner or operator shall document the basis for the determination that a shutdown for repair would cause greater emissions than the emissions likely to result from delaying repair.

Carbon Canister Sampling

52. The carbon adsorption system controlling emissions from APIs 1 and 3 shall consist of a dual carbon system. **(10/10)**

A. The carbon canisters shall be sampled and recorded, three times per week, to determine breakthrough of VOC for the dual carbon systems controlling the APIs and Lift Stations. The carbon canisters shall be sampled and recorded one time per week, to determine breakthrough of VOC for the dual carbon systems controlling Oil Water Separators (OWS) or Dry Weather Sumps (DWS) on the units in or outside battery limit (OSBL) areas. The sampling point shall be at the outlet of the first carbon bed but before the inlet to the second carbon bed.

B. Breakthrough shall be defined as a VOC concentration of 100 ppmv as measured as methane. When VOC breakthrough is detected, the waste gas flow shall be directed to a portable dual carbon system while the saturated carbon is replaced with fresh carbon. Sufficient fresh activated carbon shall be maintained at the site such that spent carbon can be replaced as specified.

C. The method of VOC sampling and analysis shall be by photo-ionization detector (PID), Ultraray, or a TCEQ equivalent as approved by the Regional Office. On each day that

sampling is to occur, the analyzer shall be calibrated prior to sampling with a certified gas mixture at 100 ppmv ± 10 percent.

D. Records of the carbon canister monitoring maintained at the plant site shall include (but are not limited to) the following:

(1) Monitoring results;

(2) Corrective action taken (including the time and date of that action) when breakthrough occurs; and

(3) Process operations at the time that breakthrough occurs. **(3/08)**

Compliance Assurance Monitoring

53. The following requirements apply to capture systems for the plant flare system and the FCCU 3 scrubber.

A. Either conduct a once a month visual, audible, and/or olfactory inspection of the capture system to verify there are no leaking components in the capture system; or verify the capture system is leak-free by inspecting in accordance with 40 CFR Part 60, Appendix A, Test Method 21 once a year. Leaks shall be indicated by an instrument reading greater than or equal to 500 ppmv above background.

B. The control device shall not have a bypass.

or

If there is a bypass for the control device, comply with either of the following requirements:

(1) Install a flow indicator that records and verifies zero flow at least once every 15 minutes immediately downstream of each valve that if opened would allow a vent stream to bypass the control device and be emitted, either directly or indirectly, to the atmosphere; or

(2) Once a month, inspect the valves, verifying the position of the valves and the condition of the car seals that prevent flow out the bypass.

A bypass does not include authorized analyzer vents, highpoint bleeder vents, low point drains, conservation vents on tanks, or rupture discs upstream of pressure relief valves if the pressure between the disc and relief valve is monitored and recorded at least weekly. A deviation shall be reported if the monitoring or inspections indicate bypass of the control device when it is required to be in service.

C. If any of the above inspections is not satisfactory, the permit holder shall promptly take necessary corrective action. Records shall be maintained documenting the performance and results of the inspections required above. **(12/11)**

Cooling Towers ALKY2, CFHU, and CT-SRU

54. The VOC associated with cooling tower water from ALKY2 (EPN 411), CFHU (EPN 426), and CT-SRU (EPN CT-SRU) cooling towers shall be monitored monthly with an air stripping system meeting the requirements of the TCEQ Sampling Procedures Manual, Appendix P (dated January 2003 or a later edition) or an approved equivalent sampling method. The results of the monitoring,

cooling water flow rate and maintenance activities on the cooling water system shall be recorded. The monitoring results and cooling water hourly mass flow rate shall be used to determine cooling tower hourly VOC emissions. The rolling 12 month cooling water emission rate shall be recorded on a monthly basis and be determined by summing the VOC emissions between VOC monitoring periods over the rolling 12 month period. The emissions between VOC monitoring periods shall be obtained by multiplying the total cooling water mass flow between cooling water monitoring periods by the higher of the 2 VOC monitored results. **(11/18)**

55. The CT-SRU cooling tower (EPN CT-SRU) shall be operated and monitored in accordance with the following: **(11/18)**

A. Each cooling tower shall be equipped with drift eliminators having manufacturer's design assurance of 0.0005% drift or less. Drifts eliminators shall be maintained and inspected at least annually. The permit holder shall maintain records of all inspections and repairs.

B. Total dissolved solids (TDS) shall not exceed 2,500 parts per million by weight (ppmw) on an annual average. Dissolved solids in the cooling water drift are considered to be emitted as PM, PM_{10}, and $PM_{2.5}$ as represented in the permit application calculations.

C. Cooling towers shall be analyzed for particulate emissions using one of the following methods:

(1) Cooling water shall be sampled at least once per week for TDS; or

(2) TDS monitoring may be reduced to monthly if conductivity is monitored weekly and TDS is calculated using a ratio of TDS-to-conductivity (in ppmw per μ mho/cm or ppmw/siemens). The ratio of TDS-to-conductivity shall be determined by concurrently monitoring TDS and conductivity on a monthly basis. The permit holder may use the average of two consecutive TDS-to-conductivity ratios to calculate weekly TDS; or.

(3) TDS monitoring may be reduced to quarterly if conductivity is monitored daily and TDS is calculated using a correlation factor established for each cooling tower. The correlation factor shall be the average of nine consecutive weekly TDS-to-conductivity ratios determined using C(2) above provided the highest ratio is not more than 10% larger than the smallest ratio.

(4) The permit holder shall validate the TDS-to-conductivity correlation factor once each calendar quarter. If the ratio of concurrently sampled TDS and conductivity is more than 10% higher or lower than the established factor, the permit holder shall increase TDS monitoring to weekly until a new correlation factor can be established.

D. Cooling water sampling shall be representative of the cooling tower feed water and shall be conducted using approved methods.

(1) The analysis method for TDS shall be EPA Method 160.1, ASTM D5907, and SM 2540 C [SM - 19th edition of Standard Methods for Examination of Water]. Water samples should be capped upon collection, and transferred to a laboratory area for analysis.

(2) Alternate sampling and analysis methods may be used to comply with D(1) with written approval from the TCEQ Regional Director.

(3) Records of all instrument calibrations and test results and process measurements used for the emission calculations shall be retained.

E. Emission rates of PM, PM_{10} and $PM_{2.5}$ shall be calculated using the measured TDS, the design drift rate and the daily maximum and average actual cooling water circulation rate for

the short term and annual average rates. Alternately, the design maximum circulation rate may be used for all calculations. Emission records shall be updated monthly.

56. The ALKY 2 and CFHU cooling towers (EPNs 411 and 426) shall be operated and monitored in accordance with the following requirements which must be implemented before start of operation of the PS3B Revamp/RHU Revamp/New DHT Project (application received on January 19, 2017,) or at the latest by December 31, 2022: **(11/18)**

A. Cooling towers shall each be equipped with drift eliminators having manufacturer's design assurance of 0.001% drift or less. Drift eliminators shall be maintained and inspected at least annually. The permit holder shall maintain records of all inspections and repairs.

B. Total dissolved solids (TDS) shall not exceed 2,500 ppmw on an annual average for EPN 411 and 2,320 ppmw on an annual average for EPN 426. Dissolved solids in the cooling water drift are considered to be emitted as PM, PM_{10}, and $PM_{2.5}$ as represented in the permit application calculations.

C. Cooling towers shall be analyzed for particulate emissions using one of the following methods:

(1) Cooling water shall be sampled at least once per day for total dissolved solids (TDS); or

(2) TDS monitoring may be reduced to weekly if conductivity is monitored daily and TDS is calculated using a ratio of TDS-to-conductivity (in ppmw per µmho/cm or ppmw/siemens). The ratio of TDS-to-conductivity shall be determined by concurrently monitoring TDS and conductivity on a weekly basis. The permit holder may use the average of two consecutive TDS-to-conductivity ratios to calculate daily TDS; or

(3) TDS monitoring may be reduced to quarterly if conductivity is monitored daily and TDS is calculated using a correlation factor established for each cooling tower. The correlation factor shall be the average of nine consecutive weekly TDS-to-conductivity ratios determined using C(2) above provided the highest ratio is not more than 10% larger than the smallest ratio.

(4) The permit holder shall validate the TDS-to-conductivity correlation factor once each calendar quarter. If the ratio of concurrently sampled TDS and conductivity is more than 10% higher or lower than the established factor, the permit holder shall increase TDS monitoring to weekly until a new correlation factor can be established.

D. Cooling water sampling shall be representative of the cooling tower feed water and shall be conducted using approved methods.

(1) The analysis method for TDS shall be EPA Method 160.1, ASTM D5907, or SM 2540 C [SM - 19th edition of Standard Methods for Examination of Water]. Water samples should be capped upon collection, and transferred to a laboratory area for analysis.

(2) The analysis method for conductivity shall be either ASTM D1125-14 Test Method A (field or routine laboratory testing) or ASTM D1125-14 Test Method B (continuous monitor). The analysis may be conducted at the sample site or with a calibrated process conductivity meter. If a conductivity meter is used, it shall be calibrated at least annually. Documentation of the method and any associated calibration records shall be maintained.

(3) Alternate sampling and analysis methods may be used to comply with D(1) and D(2) with written approval from the TCEQ Regional Director.

(4) Records of all instrument calibrations and test results and process measurements used for the emission calculations shall be retained.

E. Emission rates of PM, PM_{10} and $PM_{2.5}$ shall be calculated using the measured TDS and the ratio or correlation of TDS to conductivity measurements, the design drift rate and the daily maximum and average actual cooling water circulation rate for the short term and annual average rates. Alternately, the design maximum circulation rate may be used for all calculations. Emission records shall be updated monthly.

Leak Detection and Repair (LDAR) Programs

57. Piping, Valves, Connectors, Pumps and Compressors in VOC Service - 28VHP **(05/17)**

Except as may be provided for in the special conditions of this permit, the following requirements apply to all fugitive components at the units authorized under this permit:

A. These conditions shall not apply (1) where the VOC has an aggregate partial pressure or vapor pressure of less than 0.044 psia at 68°F or (2) to piping and valves two inches nominal size and smaller or (3) operating pressure is at least 5 kilopascals (0.725 psi) below ambient pressure. Equipment excluded from this condition shall be identified in a list to be made available upon request.

B. Construction of new and reworked piping, valves, pump systems, and compressor systems shall conform to applicable ANSI, API, ASME, or equivalent codes.

C. New and reworked underground process pipelines shall contain no buried valves such that fugitive emission monitoring is rendered impractical.

D. To the extent that good engineering practice will permit, new and reworked valves and piping connections shall be so located to be reasonably accessible for leak checking during plant operation. Non-accessible valves, as defined by 30 TAC Chapter 115, shall be identified in a list to be made available upon request.

E. New and reworked piping connections shall be welded or flanged. Screwed connections are permissible only on piping smaller than two-inch diameter. No later than the next scheduled quarterly monitoring after initial installation or replacement, all new or reworked connections shall be gas-tested or hydraulically-tested at no less than normal operating pressure and adjustments made as necessary to obtain leak-free performance. Connectors shall be inspected by visual, audible, and/or olfactory means at least weekly by operating personnel walk-through.

Each open-ended valve or line shall be equipped with an appropriately sized cap, blind flange, plug, or a second valve to seal the line. Except during sampling, both valves shall be closed. If the removal of a component for repair or replacement results in an open ended line or valve, it is exempt from the requirement to install a cap, blind flange, plug, or second valve for 72 hours. If the repair or replacement is not completed within 72 hours, the line or valve must have a cap, blind flange, plug, or second valve installed, or the open-ended valve or line shall be monitored for leaks above background within 72 hours. The open-ended valve or line shall be monitored weekly thereafter with an approved gas analyzer and the results

recorded. Leakage indicated by readings above background must be repaired within 24 hours or a cap, blind flange, plug, or second valve must be installed on the line or valve.

F. Accessible valves shall be monitored by leak-checking for fugitive emissions at least quarterly using an approved gas analyzer. Sealless/leakless valves (including, but not limited to, welded bonnet bellows and diaphragm valves) and relief valves equipped with a rupture disc upstream or venting to a control device are not required to be monitored. For valves equipped with rupture discs, a pressure-sensing device shall be installed between the relief valve and rupture disc to monitor disc integrity. All leaking discs shall be replaced at the earliest opportunity but no later than the next process shutdown.

An approved gas analyzer shall conform to requirements listed in 40 CFR § 60.485(a) – (b).

Replaced components shall be re-monitored within 15 days of being placed back into VOC service.

G. Except as may be provided for in the special conditions of this permit, all pump and compressor seals shall be monitored with an approved gas analyzer at least quarterly or be equipped with a shaft sealing system that prevents or detects emissions of VOC from the seal. Seal systems designed and operated to prevent emissions or seals equipped with an automatic seal failure detection and alarm system need not be monitored. These seal systems may include (but are not limited to) dual pump seals with barrier fluid at higher pressure than process pressure, seals degassing to vent control systems kept in good working order, or seals equipped with an automatic seal failure detection and alarm system. Submerged pumps or sealless pumps (including, but not limited to, diaphragm, canned, or magnetic-driven pumps) may be used to satisfy the requirements of this condition and need not be monitored.

H. Damaged or leaking valves or connectors found to be emitting VOC in excess of 500 ppmv or found by visual inspection to be leaking (e.g., dripping process fluids) shall be tagged and replaced or repaired. Damaged or leaking pump and compressor seals found to be emitting VOC in excess of 2,000 ppmv or found by visual inspection to be leaking (e.g., dripping process fluids) shall be tagged and replaced or repaired.

I. Every reasonable effort shall be made to repair a leaking component, as specified in this paragraph, within 15 days after the leak is found. If the repair of a component would require a unit shutdown, the repair may be delayed until the next scheduled shutdown. All leaking components which cannot be repaired until a scheduled shutdown shall be identified for such repair by tagging. At the discretion of the TCEQ Executive Director or designated representative, early unit shutdown or other appropriate action may be required based on the number and severity of tagged leaks awaiting shutdown.

J. The results of the required fugitive instrument monitoring and maintenance program shall be made available to the TCEQ Executive Director or designated representative upon request. Records shall indicate appropriate dates, test methods, instrument readings, repair results, justification for delay of repairs, and corrective actions taken for all components. Records of physical inspections are not required unless a leak is detected.

K. Alternative monitoring frequency schedules of 30 TAC §§ 115.352 - 115.359 or National Emission Standards for Organic Hazardous Air Pollutants, 40 CFR Part 63, Subpart H, may be used in lieu of Paragraphs F through G of this condition.

L. Compliance with the requirements of this condition does not assure compliance with requirements of 30 TAC Chapter 115, an applicable NSPS, or an applicable NESHAPS and does not constitute approval of alternative standards for these regulations.

Piping, Valves, Pumps, Agitators, and Compressors – Low Leak Components – 28RAH

58. Except as may be provided for in the special conditions of this permit, the following requirements apply to EPNs F-40-RAH, F-480-RAH, F-470-RAH, F-280-RAH, F-489-RAH, F48-RAH, F-390-RAH, F-393-RAH: **(11/18)**

A. The requirements of paragraphs E, F and G shall not apply (1) where the VOC has an aggregate partial pressure or vapor pressure of less than 0.044 pounds per square inch, absolute (psia) at 68°F, (2) operating pressure is at least 5 kilopascals (0.725 psi) below ambient pressure, or (3) fluids contain less than 5.0% VOC by weight on an annual average basis. Equipment excluded from this condition shall be identified in a list or by one of the methods described below to be made readily available upon request.

The exempted components may be identified by one or more of the following methods:

(1) piping and instrumentation diagram (PID);

(2) a written or electronic database or electronic file;

(3) color coding;

(4) a form of weatherproof identification; or

(5) Designation of exempted process unit boundaries.

B. Construction of new and reworked piping, valves, pump systems, and compressor systems shall conform to applicable American National Standards Institute (ANSI), American Petroleum Institute (API), American Society of Mechanical Engineers (ASME), or equivalent codes.

C. New and reworked underground process pipelines shall contain no buried valves such that fugitive emission monitoring is rendered impractical. New and reworked buried connectors shall be welded.

D. To the extent that good engineering practice will permit, new and reworked valves and piping connections shall be so located to be reasonably accessible for leak-checking during plant operation. Difficult-to-monitor and unsafe-to-monitor valves, as defined by Title 30 Texas Administrative Code Chapter 115 (30 TAC Chapter 115), shall be identified in a list to be made readily available upon request. The difficult-to-monitor and unsafe-to-monitor valves may be identified by one or more of the methods described in Paragraph A above. If an unsafe to monitor component is not considered safe to monitor within a calendar year, then it shall be monitored as soon as possible during safe to monitor times. A difficult to monitor component for which quarterly monitoring is specified may instead be monitored annually.

New and reworked piping connections shall be welded or flanged. Screwed connections are permissible only on piping smaller than two-inch diameter. Gas or hydraulic testing of the new and reworked piping connections at no less than operating pressure shall be performed prior to returning the components to service or they shall be monitored for leaks using an approved gas analyzer within 15 days of the components being returned to service. Adjustments shall be made as necessary to obtain leak-free performance.

Each open-ended valve or line shall be equipped with an appropriately sized cap, blind flange, plug, or a second valve to seal the line. Except during sampling, both valves shall be closed. If the isolation of equipment for hot work or the removal of a component for repair or replacement results in an open-ended line or valve, it is exempt from the requirement to install a cap, blind flange, plug, or second valve for 72 hours. If the repair or replacement is

not completed within 72 hours, the permit holder must complete either of the following actions within that time period;

(1) a cap, blind flange, plug, or second valve must be installed on the line or valve; or

(2) The open-ended valve or line shall be monitored once for leaks above background for a plant or unit turnaround lasting up to 45 days with an approved gas analyzer and the results recorded. For all other situations, the open-ended valve or line shall be monitored once by the end of the 72 hours period following the creation of the open-ended line and monthly thereafter with an approved gas analyzer and the results recorded. For turnarounds and all other situations, leaks are indicated by readings of 500 ppmv and must be repaired within 24 hours or a cap, blind flange, plug, or second valve must be installed on the line or valve.

E. All accessible connectors shall be monitored by leak-checking for fugitive emissions at least quarterly using an approved gas analyzer in accordance with items F, H & I of this special condition.

In lieu of the monitoring frequency specified above, connectors may be monitored on a semiannual basis if the percent of connectors leaking for four consecutive quarterly monitoring periods is less than 0.5 percent.

Connectors may be monitored on an annual basis if the percent of connectors leaking for two consecutive semiannual monitoring periods is less than 0.5 percent.

If the percent of connectors leaking for any semiannual or annual monitoring period is 0.5 percent or greater, the facility shall revert to quarterly monitoring until the facility again qualifies for the alternative monitoring schedules previously outlined in this paragraph.

The percent of connectors leaking shall be determined using the following formula:

$$(Cl + Cs) \times 100/Ct = Cp$$

Where:

Cl = the number of connectors found leaking by the end of the monitoring period (excluding those for which repair was delayed prior to the monitoring period), either by Method 21 or sight, sound, and smell.

Cs = the number of connectors for which repair has been delayed and are listed on the facility shutdown log.

Ct = the total number of connectors in the facility subject to the monitoring requirements, as of the last day of the monitoring period, not including difficult-to-monitor and unsafe to monitor connectors.

Cp = the percentage of leaking connectors for the monitoring period.

F. Accessible valves shall be monitored by leak checking for fugitive emissions at least quarterly using an approved gas analyzer. Difficult-to-monitor valves shall be monitored by leak-checking for fugitive emissions at least annually using an approved gas analyzer. Sealless/leakless valves (including, but not limited to, welded bonnet bellows and diaphragm valves) and relief valves equipped with a rupture disc upstream or venting to a control device are not required to be monitored. For valves equipped with rupture discs, a pressure-sensing device shall be installed between the relief valve and rupture disc to monitor disc integrity. All

leaking discs shall be replaced at the earliest opportunity but no later than the next process shutdown. A check of the reading of the pressure-sensing device to verify disc integrity shall be performed at least quarterly and recorded in the unit log or equivalent. Pressure-sensing devices that are continuously monitored with alarms are exempt from recordkeeping requirements specified in this paragraph.

The gas analyzer shall be a TVA-2020 and/or TVA-1000b or shall meet the requirements provided in Method 21 of 40 CFR Part 60, Appendix A with the added provision that the instrument response factor for a process stream is equal to or less than 3. The gas analyzer shall be calibrated with methane for the FID and isobutylene for the PID, or other calibration gases approved by the analyzer manufacturer. If the process stream response factor is greater than 1 then the permit holder shall multiply the reading by the response factor to determine the actual concentration. The instrument response factor for each of the streams shall be determined following the same methodology demonstrated in the spreadsheet entitled “NDU Response Factors” dated August 19, 2016. The response factor information records shall be maintained at the site and made available to a representative of the TCEQ upon request.

G. Except as may be provided for in the special conditions of this permit, all pump, compressor, and agitator seals shall be monitored with an approved gas analyzer at least quarterly or be equipped with a shaft sealing system that prevents or detects emissions of VOC from the seal. Seal systems designed and operated to prevent emissions or seals equipped with an automatic seal failure detection and alarm system need not be monitored. These seal systems may include (but are not limited to) dual pump seals with barrier fluid at higher pressure than process pressure, seals degassing to vent control systems kept in good working order, or seals equipped with an automatic seal failure detection and alarm system. Submerged pumps or sealless pumps (including, but not limited to, diaphragm, canned, or magnetic-driven pumps) may be used to satisfy the requirements of this condition and need not be monitored.

H. Damaged or leaking valves or connectors found to be emitting VOC in excess of 100 parts per million by volume (ppmv) or found by visual inspection to be leaking (e.g., dripping process fluids) shall be tagged and replaced or repaired. Damaged or leaking compressor seals, pump seals, and agitator seals found to be emitting VOC in excess of 2,000 ppmv or found by visual inspection to be leaking (e.g., dripping process fluids) shall be tagged and replaced or repaired. A first attempt to repair the leak must be made within 5 days. Records of the first attempt to repair shall be maintained. A leaking component shall be repaired as soon as practicable, but no later than 15 days after the leak is found. If the repair of a component would require a unit shutdown that would create more emissions than the repair would eliminate, the repair may be delayed until the next scheduled shutdown. All leaking components which cannot be repaired until a scheduled shutdown shall be identified for such repair by tagging. A list of all components that qualify for delay of repair shall be maintained. The cumulative daily emissions from all components on the delay of repair list shall be estimated by multiplying by 24 the mass emission rate for each component calculated in accordance with the instructions in 30 TAC 115.782 (c)(1)(B)(i)(II). The calculations of the cumulative daily emissions from all components on the delay of repair list shall be updated within ten days of when the latest leaking component is added to the delay of repair list. When the cumulative daily emission rate of all components on the delay of repair list times the number of days until the next scheduled unit shutdown is equal to or exceeds the total emissions from a unit shut down as calculated in accordance with 30 TAC 115.782 (c)(1)(B)(i)(I), the TCEQ Regional Manager and any local programs shall be notified and may require early unit shut down or other appropriate action based on the number and severity of

tagged leaks awaiting shutdown. This notification shall be made within 15 days of making this determination.

I. Records of repairs shall include date of repairs, repair results, justification for delay of repairs, and corrective actions taken for all components. Records of instrument monitoring shall indicate dates, times, test methods, and instrument readings. The instrument monitoring record shall include the time that monitoring took place for no less than 95% of the instrument readings recorded. Records of physical inspections shall be noted in the operator's log or equivalent.

J. Compliance with the requirements of this condition does not assure compliance with requirements of 30 TAC Chapter 115, an applicable New Source Performance Standard (NSPS), or an applicable National Emission Standard for Hazardous Air Pollutants (NESHAPS), and does not constitute approval of alternative standards for these regulations.

K. In lieu of the monitoring frequency specified in paragraph F, valves in gas and light liquid service may be monitored on a semiannual basis if the percent of valves leaking for two consecutive quarterly monitoring periods is less than 0.5 percent.

Valves in gas and light liquid service may be monitored on an annual basis if the percent of valves leaking for two consecutive semiannual monitoring periods is less than 0.5 percent.

If the percent of valves leaking for any semiannual or annual monitoring period is 0.5 percent or greater, the facility shall revert to quarterly monitoring until the facility again qualifies for the alternative monitoring schedules previously outlined in this paragraph.

L. The percent of valves leaking used in paragraph L shall be determined using the following formula:

$$(Vl + Vs) \times 100/Vt = Vp$$

Where:

Vl = the number of valves found leaking by the end of the monitoring period (excluding those for which repair was delayed prior to the monitoring period), either by Method 21 or sight, sound, and smell.

Vs = the number of valves for which repair has been delayed and are listed on the facility shutdown log.

Vt = the total number of valves in the facility subject to the monitoring requirements, as of the last day of the monitoring period, not including difficult-to-monitor and unsafe to monitor valves.

Vp = the percentage of leaking valves for the monitoring period.

M. Any component found to be leaking by physical inspection (i.e., sight, sound, or smell) shall be repaired or monitored with an approved gas analyzer within 15 days to determine whether the component is leaking in excess of its corresponding leak definition. If the component is found to be leaking in excess its corresponding leak definition, it shall be subject to the repair and replacement requirements contained in this special condition.

Piping, Valves, Pumps, Agitators, and Compressors - Intensive Directed Maintenance – 28LAER

59. Except as may be provided for in the special conditions of this permit, the following requirements apply to fugitive components within EPNs F-40-RAH, F-480-RAH, F-470-RAH, F-280-RAH, F-489-RAH, F48-RAH, F-390-RAH, F-393-RAH, and F-DHT: **(11/18)**

    A. The requirements of paragraphs F and G shall not apply (1) where the VOC has an aggregate partial pressure or vapor pressure of less than 0.044 pounds per square inch, absolute (psia) at 68°F, (2) operating pressure is at least 5 kilopascals (0.725 psi) below ambient pressure, or (3) fluids contain less than 5.0% VOC by weight on an annual average basis. Equipment excluded from this condition shall be identified in a list or by one of the methods described below to be made readily available upon request.

    The exempted components may be identified by one or more of the following methods:

    - piping and instrumentation diagram (PID);
    - a written or electronic database or electronic file;
    - color coding;
    - a form of weatherproof identification; or
    - designation of exempted process unit boundaries.

    B. Construction of new and reworked piping, valves, pump systems, and compressor systems shall conform to applicable American National Standards Institute (ANSI), American Petroleum Institute (API), American Society of Mechanical Engineers (ASME), or equivalent codes.

    C. New and reworked underground process pipelines shall contain no buried valves such that fugitive emission monitoring is rendered impractical. New and reworked buried connectors shall be welded.

    D. To the extent that good engineering practice will permit, new and reworked valves and piping connections shall be so located to be reasonably accessible for leak-checking during plant operation. Difficult-to-monitor and unsafe-to-monitor valves, as defined by Title 30 Texas Administrative Code Chapter 115 (30 TAC Chapter 115), shall be identified in a list to be made readily available upon request. The difficult-to-monitor and unsafe-to-monitor valves may be identified by one or more of the methods described in paragraph A above. If an unsafe to monitor component is not considered safe to monitor within a calendar year, then it shall be monitored as soon as possible during safe to monitor times. A difficult to monitor component for which quarterly monitoring is specified may instead be monitored annually.

    E. New and reworked piping connections shall be welded or flanged. Screwed connections are permissible only on piping smaller than two-inch diameter. Gas or hydraulic testing of the new and reworked piping connections at no less than operating pressure shall be performed prior to returning the components to service or they shall be monitored for leaks using an approved gas analyzer within 15 days of the components being returned to service. Adjustments shall be made as necessary to obtain leak-free performance.

    Connectors shall be inspected by visual, audible, and/or olfactory means at least weekly by operating personnel walk-through. In addition, all connectors shall be monitored by leak-checking for fugitive emissions at least quarterly using an approved gas analyzer with a directed maintenance program in accordance with items F thru J of this special condition.

In lieu of the monitoring frequency specified above, connectors may be monitored on a semiannual basis if the percent of connectors leaking for two consecutive quarterly monitoring periods is less than 0.5 percent.

Connectors may be monitored on an annual basis if the percent of connectors leaking for two consecutive semiannual monitoring periods is less than 0.5 percent.

If the percent of connectors leaking for any semiannual or annual monitoring period is 0.5 percent or greater, the facility shall revert to quarterly monitoring until the facility again qualifies for the alternative monitoring schedules previously outlined in this paragraph.

The percent of connectors leaking shall be determined using the following formula:

$$(Cl + Cs) \times 100/Ct = Cp$$

Where:

Cl = the number of connectors found leaking by the end of the monitoring period, either by Method 21 or sight, sound, and smell.

Cs = the number of connectors for which repair has been delayed and are listed on the facility shutdown log.

Ct = the total number of connectors in the facility subject to the monitoring requirements, as of the last day of the monitoring period, not including non-accessible and unsafe to monitor connectors.

Cp = the percentage of leaking connectors for the monitoring period.

Each open-ended valve or line shall be equipped with an appropriately sized cap, blind flange, plug, or a second valve to seal the line. Except during sampling, both valves shall be closed. If the isolation of equipment for hot work or the removal of a component for repair or replacement results in an open ended line or valve, it is exempt from the requirement to install a cap, blind flange, plug, or second valve for 72 hours. If the repair or replacement is not completed within 72 hours, the permit holder must complete either of the following actions within that time period;

(1) a cap, blind flange, plug, or second valve must be installed on the line or valve; or

(2) The open-ended valve or line shall be monitored once for leaks above background for a plant or unit turnaround lasting up to 45 days with an approved gas analyzer and the results recorded. For all other situations, the open-ended valve or line shall be monitored once by the end of the 72 hours period following the creation of the open ended line and monthly thereafter with an approved gas analyzer and the results recorded. For turnarounds and all other situations, leaks are indicated by readings of 500 ppmv and must be repaired within 24 hours or a cap, blind flange, plug, or second valve must be installed on the line or valve.

F. Accessible valves shall be monitored by leak-checking for fugitive emissions at least quarterly using an approved gas analyzer with a directed maintenance program. Non accessible valves shall be monitored by leak-checking for fugitive emissions at least annually using an approved gas analyzer with a directed maintenance program. Sealless/leakless valves (including, but not limited to, welded bonnet bellows and diaphragm valves) and relief valves equipped with a rupture disc upstream or venting to a control device are not required to be monitored. For valves equipped with rupture discs, a pressure-sensing device shall be installed between the relief valve and rupture disc to monitor disc integrity. All leaking discs shall be replaced at the earliest opportunity but no later than the next process shutdown. A

check of the reading of the pressure-sensing device to verify disc integrity shall be performed at least quarterly and recorded in the unit log or equivalent. Pressure-sensing devices that are continuously monitored with alarms are exempt from recordkeeping requirements specified in this paragraph.

The gas analyzer shall conform to requirements listed in Method 21 of 40 CFR part 60, appendix A. The gas analyzer shall be calibrated with methane. In addition, the response factor of the instrument for a specific VOC of interest shall be determined and meet the requirements of Section 8 of Method 21. If a mixture of VOCs is being monitored, the response factor shall be calculated for the average composition of the process fluid. A calculated average is not required when all of the compounds in the mixture have a response factor less than 10 using methane. If a response factor less than 10 cannot be achieved using methane, than the instrument may be calibrated with one of the VOC to be measured or any other VOC so long as the instrument has a response factor of less than 10 for each of the VOC to be measured.

A directed maintenance program shall consist of the repair and maintenance of components assisted simultaneously by the use of an approved gas analyzer such that a minimum concentration of leaking VOC is obtained for each component being maintained. Replaced components shall be re-monitored within 15 days of being placed back into VOC service.

G. All new and replacement pumps, compressors, and agitators shall be equipped with a shaft sealing system that prevents or detects emissions of VOC from the seal. These seal systems need not be monitored and may include (but are not limited to) dual pump seals with barrier fluid at higher pressure than process pressure, seals degassing to vent control systems kept in good working order, or seals equipped with an automatic seal failure detection and alarm system. Submerged pumps or sealless pumps (including, but not limited to, diaphragm, canned, or magnetic-driven pumps) may be used to satisfy the requirements of this condition and need not be monitored.

All other pump, compressor, and agitator seals shall be monitored with an approved gas analyzer at least quarterly.

H. Damaged or leaking valves, connectors, compressor seals, pump seals, and agitator seals found to be emitting VOC in excess of 500 parts per million by volume (ppmv) or found by visual inspection to be leaking (e.g., dripping process fluids) shall be tagged and replaced or repaired. A first attempt to repair the leak must be made within 5 days. Records of the first attempt to repair shall be maintained. A leaking component shall be repaired as soon as practicable, but no later than 15 days after the leak is found. If the repair of a component would require a unit shutdown that would create more emissions than the repair would eliminate, the repair may be delayed until the next scheduled shutdown. All leaking components which cannot be repaired until a scheduled shutdown shall be identified for such repair by tagging. A listing of all components that qualify for delay of repair shall be maintained on a delay of repair list. The cumulative daily emissions from all components on the delay of repair list shall be estimated by multiplying by 24 the mass emission rate for each component calculated in accordance with the instructions in 30 TAC 115.782 (c)(1)(B)(i)(II). The calculations of the cumulative daily emissions from all components on the delay of repair list shall be updated within ten days of when the latest leaking component is added to the delay of repair list. When the cumulative daily emission rate of all components on the delay of repair list times the number of days until the next scheduled unit shutdown is equal to or exceeds the total emissions from a unit shutdown as calculated in accordance with 30 TAC 115.782 (c)(1)(B)(i)(I), the TCEQ Regional Manager and any local programs shall be notified and may require early unit shutdown or other appropriate action based on

the number and severity of tagged leaks awaiting shutdown. This notification shall be made within 15 days of making this determination.

I. Records of repairs shall include date of repairs, repair results, justification for delay of repairs, and corrective actions taken for all components. Records of instrument monitoring shall indicate dates, times, test methods, and instrument readings. The instrument monitoring record shall include the time that monitoring took place for no less than 95% of the instrument readings recorded. Records of physical inspections shall be noted in the operator's log or equivalent.

J. Compliance with the requirements of this condition does not assure compliance with requirements of 30 TAC Chapter 115, an applicable New Source Performance Standard (NSPS), or an applicable National Emission Standard for Hazardous Air Pollutants (NESHAPS), and does not constitute approval of alternative standards for these regulations.

K. In lieu of the monitoring frequency specified in paragraph F, valves in gas and light liquid service may be monitored on a semiannual basis if the percent of valves leaking for two consecutive quarterly monitoring periods is less than 0.5 percent.

Valves in gas and light liquid service may be monitored on an annual basis if the percent of valves leaking for two consecutive semiannual monitoring periods is less than 0.5 percent.

If the percent of valves leaking for any semiannual or annual monitoring period is 0.5 percent or greater, the facility shall revert to quarterly monitoring until the facility again qualifies for the alternative monitoring schedules previously outlined in this paragraph.

L. The percent of valves leaking used in paragraph K shall be determined using the following formula:

$$(Vl + Vs) \times 100/Vt = Vp$$

Where:

Vl = the number of valves found leaking by the end of the monitoring period, either by Method 21 or sight, sound, and smell.

Vs = the number of valves for which repair has been delayed and are listed on the facility shutdown log.

Vt = the total number of valves in the facility subject to the monitoring requirements, as of the last day of the monitoring period, not including nonaccessible and unsafe to monitor valves.

Vp = the percentage of leaking valves for the monitoring period.

M. Any component found to be leaking by physical inspection (i.e., sight, sound, or smell) shall be repaired or monitored with an approved gas analyzer within 15 days to determine whether the component is leaking in excess of 500 ppmv of VOC. If the component is found to be leaking in excess of 500 ppmv of VOC, it shall be subject to the repair and replacement requirements contained in this special condition.

60. All process drains shall be instrument-monitored with an approved gas analyzer on an annual basis using a 500 ppmv leak definition. The gas analyzer shall conform to the requirements listed in 40 CFR § 60.485(a)-(b).

61. Ambient H2S monitors shall be placed through the sulfur recovery, amine regeneration, and sour water stripper areas. These monitors shall be arranged in such a way that coverage is provided for

all wind directions. The monitors shall be set to alarm at 10 ppmv and shall alarm in the control room. A plot identifying the number and location of each monitor shall be maintained in the control room handling each one of the areas described above.

62. **Piping, Valves, Pumps, and Compressors in NH_3, H_2S, and SO_2 Service (05/17)**

A. Audio, olfactory, and visual checks for NH_3, H_2S, and SO_2 leaks within the following operating areas shall be made once per shift (once every 12 hours):

Pollutant(s)	Operating Area(s)
NH_3	Aqueous ammonia storage and piping
H_2S and SO_2	SRU, sour water stripper area, amine contactor and regenerator, and hydrotreater areas handling H_2S and SO_2

B. Immediately, but no later than one hour upon detection of a leak, plant personnel shall:

(1) Stop the leak by taking the equipment out of service, or

(2) Bypass the equipment so that it is no longer in service, or

(3) Isolate the leak, or

(4) Commence repair or replacement of the leaking component.

If the leak cannot be repaired within six hours, the holder of this permit shall use clamping procedures to prevent the leak until replacement or repair can be performed.

Records shall be maintained at the plant site of all repairs and replacements made due to leaks. A reminder that visual checks for NH_3, H_2S, and SO_2 leaks need to be made once per shift shall be included in the appropriate unit operator manual no later than September 13, 2005. **(8/10)**

Emission Cap Compliance Recordkeeping

63. The holder of this permit shall use continuous emissions data, sampling data, firing rates, throughput, fill rates, etc., to perform emission calculations at least once every month in order to verify compliance with the annual (TPY) emission caps. The holder of this permit shall maintain all records necessary to demonstrate compliance with the short-term (lb/hr) and TPY emissions caps and individual emission limitations and provide such demonstration of compliance to the TCEQ or local air pollution control program representatives upon request. **(11/18)**

If any information obtained from parameter monitoring (throughput, pump rates, etc.), sampling data or continuous emission monitor (CEM) data indicates that a facility is exceeding its proposed contribution to the emissions cap (lb/hr and/or TPY), the holder of this permit shall provide adequate information to demonstrate that the lb/hr and/or TPY emissions caps were not exceeded, and that the BACT representations for the facilities contributing to the emissions CAP is being met.

After July 31, 2006, compliance with the annual emission caps and individual emission limitations of this flexible permit shall be based on a rolling 12-month basis.

64. Emissions from sources covered under this permit shall be determined as follows. If a source type is not listed below, the permit holder shall use the methodology which was used in the permit application.

Atmospheric Storage Tanks: Emissions for tanks shall be calculated using: (a) AP-42 "Compilation of Air Pollution Emission Factors, Chapter 7 - Storage of Organic Liquids" and (b) the TCEQ publication titled "Technical Guidance Package for Chemical Sources - Storage Tanks." Short-term emission rate shall be based on the maximum expected pumping rate (fixed-roof) and the higher of the pumping rate or withdrawal rate (IFR and EFR).

Marine Loading: AP-42 Chapter 5.2-4 (Fifth Edition) LL Equation - The collection efficiency is 100 percent collection (vacuum loading system) for all compounds equal to or greater than 0.5 psia except compounds loaded to inerted marine vessels for which the collection efficiency is 99.9 percent collection per Special Condition 8.

Piping Fugitives: Component counts, emission factors, and reduction credits specified in the permit application for the various inspection and maintenance programs.

Boilers and Heaters: CEMS information if such a device is installed. The most recent stack test results if a CEM is not installed. If no stack sampling is required, use the proper emission factor for the specific unit and the measured Btu value and flow rate of the fuel.

SRU and FCCU: CEMS information. Use the most recent stack test for those compounds which are not subject to CEM requirements. **(06/15)**

Maintenance, Startup, and Shutdown (MSS) Activities

65. This permit authorizes the emissions from the facilities identified in Attachment D for the planned maintenance, startup, and shutdown (MSS) activities summarized in the MSS Activity Summary (Attachment C) attached to this permit.

Attachment A identifies the inherently low emitting MSS activities that may be performed at the refinery. Emissions from activities identified in Attachment A shall be considered to be equal to the potential to emit represented in the permit application. The estimated emissions from the activities listed in Attachment A must be revalidated annually. This revalidation shall consist of the estimated emissions for each type of activity and the basis for that emission estimate.

Routine maintenance activities, as identified in Attachment B may be tracked through the work orders or equivalent. Emissions from activities identified in Attachment B shall be calculated using the number of work orders or equivalent that month and the emissions associated with that activity identified in the permit application.

The performance of each planned MSS activity not identified in Attachments A or B and the emissions associated with it shall be recorded and include at least the following information:

A. The process unit at which emissions from the MSS activity occurred, including the emission point number and common name of the process unit;

B. The type of planned MSS activity and the reason for the planned activity;

C. The common name and the facility identification number, if applicable, of the facilities at which the MSS activity and emissions occurred;

D. The date and time of the MSS activity and its duration;

E. The estimated quantity of each air contaminant, or mixture of air contaminants, emitted with the data and methods used to determine it. The emissions shall be estimated using the methods identified in the permit application, consistent with good engineering practice.

All MSS emissions authorized by this permit shall be summed monthly and the rolling 12 month emissions shall be updated on a monthly basis. **(8/10)**

66. Process units and facilities, with the exception of those identified in Special Condition Nos. 69, 70, 72, and Attachment A shall be depressurized, emptied, degassed, and placed in service in accordance with the following requirements.

A. The process equipment shall be depressurized to a control device or a controlled recovery system prior to venting to atmosphere, degassing, or draining liquid. Equipment that only contains material that is liquid with VOC partial pressure less than 0.50 psi at the normal process temperature and 95°F may be opened to atmosphere and drained in accordance with Paragraph C of this condition. The vapor pressure at 95°F may be used if the actual temperature of the liquid is verified to be less than 95°F and the temperature is recorded.

B. If mixed phase materials must be removed from process equipment, the cleared material shall be routed to a knockout drum or equivalent to allow for managed initial phase separation. If the VOC partial pressure is greater than 0.50 psi at either the normal process temperature or 95°F, any vents in the system must be routed to a control device or a controlled recovery system. The vapor pressure at 95°F may be used if the actual temperature of the liquid is verified to be less than 95°F and the temperature is recorded. Control must remain in place until degassing has been completed or the system is no longer vented to atmosphere.

C. All liquids from process equipment or storage vessels must be removed to the maximum extent practical prior to opening equipment to commence degassing and/or maintenance. Liquids must be drained into a closed vessel unless prevented by the physical configuration of the equipment. If it is necessary to drain liquid into an open pan or sump, the liquid must be covered or transferred to a covered vessel within one hour of being drained.

D. If the VOC partial pressure is greater than 0.50 psi at the normal process temperature or 95°F, facilities shall be degassed using good engineering practice to ensure air contaminants are removed from the system through the control device or controlled recovery system to the extent allowed by process equipment or storage vessel design. The vapor pressure at 95°F may be used if the actual temperature of the liquid is verified to be less than 95°F and the temperature is recorded. The facilities to be degassed shall not be vented directly to atmosphere, except as necessary to establish isolation of the work area or to monitor VOC concentration following controlled depressurization. The venting shall be minimized to the maximum extent practicable and actions taken recorded. The control device or recovery system utilized shall be recorded with the estimated emissions from controlled and uncontrolled degassing calculated using the methods that were used to determine allowable emissions for the permit application.

(1) For MSS activities identified in Attachment B, the following option may be used in lieu of Paragraph D(2) of this condition. The facilities being prepared for maintenance shall not be vented directly to atmosphere, except as necessary to verify an acceptable VOC

concentration and establish isolation of the work area, until the VOC concentration has been verified to be less than 10 percent of the lower explosive limit (LEL) (or equivalent) per the site safety procedures.

(2) The locations and/or identifiers where the purge gas or steam enters the process equipment or storage vessel and the exit points for the exhaust gases shall be recorded (PFD's or P&ID's may be used to demonstrate compliance with the requirement). Documented refinery procedures used to deinventory equipment to a control device for safety purposes (i.e., hot work or vessel entry procedures) that achieve at least the same level of purging may be used in lieu of the above. If the process equipment is purged with a gas, purge gas must have passed through the control device or controlled recovery system for a sufficient period of time in accordance with the applicable site operating procedures before the vent stream may be sampled to verify acceptable VOC concentration prior to uncontrolled venting. The VOC sampling and analysis shall be performed using an instrument meeting the requirements of Special Condition No. 67. The sampling point shall be upstream of the inlet to the control device or controlled recovery system. The sample locations and collection systems must be located downstream of the process equipment or vessel being purged. The facilities shall be degassed to a control device or controlled recovery system until the VOC concentration is less than or equal to 10,000 ppmv or 10 percent of the LEL.

E. Gases and vapors with VOC partial pressure greater than 0.50 psi may be vented directly to atmosphere if all the following criteria are met:

(1) It is not technically practicable to depressurize or degas, as applicable, into the process.

(2) There is not an available connection to a plant control system (flare).

(3) There is no more than 50 lb of air contaminant to be vented to atmosphere during shutdown or startup, as applicable.

All instances of venting directly to atmosphere per Paragraph E of Special Condition No. 66 must be documented when occurring as part of any MSS activity. The emissions associated with venting without control must be included in the work order or equivalent for those planned MSS activities identified in Attachment B. **(8/10)**

67. Air contaminant concentration shall be measured using an instrument/detector meeting one set of requirements specified below.

A. VOC concentration shall be measured using an instrument meeting all the requirements specified in EPA Method 21 (40 CFR 60, Appendix A) with the following exceptions:

(1) The instrument shall be calibrated within 24 hours of use with a calibration gas such that the response factor of the VOC (or mixture of VOCs) to be monitored shall be less than 2.0. The calibration gas and the gas to be measured, and its approximate response factor shall be recorded.

(2) Sampling shall be performed as directed by this permit in lieu of section 8.3 of Method 21. During sampling, data recording shall not begin until after two times the instrument response time. The date and time shall be recorded, and VOC concentration shall be monitored for at least five minutes, recording VOC concentration each minute. The highest measured VOC concentration shall not exceed the specified VOC concentration limit prior to uncontrolled venting.

B. Colorimetric gas detector tubes may be used to determine air contaminant concentrations if they are used in accordance with the following requirements.

(1) The air contaminant concentration measured is less than 80 percent of the range of the tube. If the maximum range of the tube is greater than the release concentration defined in Subparagraph (3) of this condition, the concentration measured is at least 20 percent of the maximum range of the tube.

(2) The tube is used in accordance with the manufacturer's guidelines.

(3) At least 2 samples taken at least 5 minutes apart must satisfy the following prior to uncontrolled venting:

measured contaminant concentration (ppmv) less than release concentration.

Where the release concentration is:

10,000* mole fraction of the total air contaminants present that can be detected by the tube.

The mole fraction may be estimated based on process knowledge. The release concentration and basis for its determination shall be recorded.

Records shall be maintained of the tube type, range, measured concentrations, and time the samples were taken.

C. Lower explosive limit measured with a lower explosive limit detector.

(1) The detector shall be calibrated monthly with a certified pentane gas standard at 25 percent of the lower explosive limit (LEL) for pentane. Records of the calibration date/time and calibration result (pass/fail) shall be maintained.

(2) A daily functionality test shall be performed on each detector using the same certified gas standard used for calibration. The LEL monitor shall read no lower than 90 percent of the calibration gas certified value. Records, including the date/time and test results, shall be maintained.

(3) A certified methane gas standard equivalent to 25 percent of the LEL for pentane may be used for calibration and functionality tests provided that the LEL response is within 95 percent of that for pentane. **(8/10)**

68. Each open-ended valve or line shall be equipped with an appropriately sized cap, blind flange, plug, or a second valve to seal the line. Except during sampling, both valves shall be closed. If the removal of a component for repair or replacement results in an open ended line or valve, it is exempt from the requirement to install a cap, blind flange, plug, or second valve for 72 hours. If the repair or replacement is not completed within 72 hours, the permit holder must complete either of the following actions within that time period;

A. a cap, blind flange, plug, or second valve must be installed on the line or valve; or

B. the open-ended valve or line shall be monitored once for leaks above background for a plant or unit turnaround lasting up to 45 days with an approved gas analyzer and the results recorded. For all other situations, the open-ended valve or line shall be monitored once at the end of the 72 hour period following the creation of the open ended line and monthly thereafter with an approved gas analyzer and the results recorded. For turnarounds and all other situations, leaks are indicated by readings 20 ppmv above background and must be

repaired within 24 hours or a cap, blind flange, plug, or second valve must be installed on the line or valve. **(8/10)**

69. This permit authorizes emissions from the storage tanks identified in Attachment D during planned floating roof landings. Tank roofs may only be landed for changes of tank service or tank inspection/maintenance as identified in the permit application. Tank change of service includes landings to accommodate seasonal RVP spec changes and landings to correct off-spec material that cannot be blended into finished product tanks. Emissions from change of service tank landings shall not exceed 10 tons of VOC in any rolling 12 month period. Tank roof landings include all operations when the tank floating roof is on its supporting legs. These emissions are subject to the maximum allowable emission rates indicated on the ECIELT. The following requirements apply to tank roof landings.

A. The tank liquid level shall be continuously lowered after the tank floating roof initially lands on its supporting legs until the tank has been drained to the maximum extent practicable without entering the tank. Liquid level may be maintained steady for a period of up to two hours if necessary to allow for valve lineups and pump changes necessary to drain the tank. This requirement does not apply where the vapor under a floating roof is routed to control or a controlled recovery system during this process.

B. If the VOC partial pressure of the liquid previously stored in the tank is greater than 0.50 psi at 95°F, tank refilling or degassing of the vapor space under the landed floating roof must begin within 24 hours after the tank has been drained unless the vapor under the floating roof is routed to control or a controlled recovery system during this period. Floating roof tanks with liquid capacities less than 100,000 gallons may be degassed without control if the VOC partial pressure of the standing liquid in the tank has been reduced to less than 0.02 psia prior to ventilating the tank. Controlled degassing of the vapor space under landed roofs shall be completed as follows:

(1) Any gas or vapor removed from the vapor space under the floating roof must be routed to a control device or a controlled recovery system and controlled degassing must be maintained until the VOC concentration is less than 10,000 ppmv or 10 percent of the LEL. The locations and identifiers of vents other than permanent roof fittings and seals, control device or controlled recovery system, and controlled exhaust stream shall be recorded. There shall be no other gas/vapor flow out of the vapor space under the floating roof when degassing to the control device or controlled recovery system.

(2) The vapor space under the floating roof shall be vented using good engineering practice to ensure air contaminants are flushed out of the tank through the control device or controlled recovery system to the extent allowed by the storage tank design.

(3) A volume of purge gas equivalent to twice the volume of the vapor space under the floating roof must have passed through the control device or into a controlled recovery system, before the vent stream may be sampled to verify acceptable VOC concentration. The measurement of purge gas volume shall not include any make-up air introduced into the control device or recovery system. The VOC sampling and analysis shall be performed as specified in Special Condition No. 67.

(4) The sampling point shall be upstream of the inlet to the control device or controlled recovery system. The sample ports and the collection system must be designed and operated such that there is no air leakage into the sample probe or the collection system downstream of the process equipment or vessel being purged.

(5) Degassing must be performed every 24 hours unless there is no standing liquid in the tank or the VOC partial pressure of the remaining liquid in the tank is less than 0.15 psia.

C. The tank shall not be opened or ventilated without control, except as allowed by (1) or (2) below until one of the criteria in Paragraph D of this condition is satisfied.

(1) Minimize air circulation in the tank vapor space.

(a) One manway may be opened to allow access to the tank to remove or de-volatilize the remaining liquid. Other manways or access points may be opened as necessary to remove or de-volatilize the remaining liquid. Wind barriers shall be installed at all open manways and access points to minimize air flow through the tank.

(b) Access points shall be closed when not in use.

(2) Minimize time and VOC partial pressure.

(a) The VOC partial pressure of the liquid remaining in the tank shall not exceed 0.044 psi as documented by the method specified in Paragraph D(1) of this condition;

(b) Blowers may be used to move air through the tank without emission control at a rate not to exceed 12,000 cubic feet per minute for no more than 12 hours. All standing liquid shall be removed from the tank during this period; and

(c) Records shall be maintained of the blower circulation rate, the duration of uncontrolled ventilation, and the date and time all standing liquid was removed from the tank.

D. The tank shall not be opened except as necessary to set up for degassing and cleaning, or ventilated without control, until either all standing liquid has been removed from the tank or the liquid in the tank has a VOC partial pressure less than 0.02 psia. These criteria may be demonstrated in any one of the following ways.

(1) Low VOC partial pressure liquid that is soluble with the liquid previously stored may be added to the tank to lower the VOC partial pressure of the liquid mixture remaining in the tank to less than 0.02 psia. This liquid shall be added during tank degassing if practicable. The estimated volume of liquid remaining in the drained tank and the volume and type of liquid added shall be recorded. The liquid VOC partial pressure may be estimated based on this information and engineering calculations.

(2) If water is added or sprayed into the tank to remove standing VOC, one of the following must be demonstrated:

(a) Take a representative sample of the liquid remaining in the tank and verify no visible sheen using the static sheen test from 40 CFR 435 Subpart A Appendix 1.

(b) Take a representative sample of the liquid remaining in the tank and verify hexane soluble VOC concentration is less than 1000 ppmw using EPA Method 1664 (may also use 8260B or 5030 with 8015 from SW-846).

(c) Stop ventilation and close the tank for at least 24 hours. When the tank manway is opened after this period, verify VOC concentration is less than 1,000 ppmv through the procedure in Special Condition No. 67.

(3) No standing liquid verified through visual inspection.

The permit holder shall maintain records to document the method used to release the tank.

E. Tanks shall be refilled as rapidly as practicable until the roof is off its legs with the following exceptions:

(1) Only one benzene tank with a landed floating roof can be filled at any time at a rate not to exceed 1,000 bbl/hr.

(2) The vapor space below the tank roof is directed to a control device when the tank is refilled until the roof is floating on the liquid. The control device used and the method and locations used to connect the control device shall be recorded. All vents from the tank being filled must exit through the control device.

F. The occurrence of each roof landing and the associated emissions shall be recorded and the rolling 12-month tank roof landing emissions shall be updated on a monthly basis. These records shall include at least the following information:

(1) the identification of the tank and emission point number, and any control devices or recovery systems used to reduce emissions;

(2) the reason for the tank roof landing;

(3) for the purpose of estimating emissions, the date, time, and other information specified for each of the following events:

(a) the roof was initially landed,

(b) all liquid was pumped from the tank to the extent practical,

(c) start and completion of controlled degassing, and total volumetric flow,

(d) all standing liquid was removed from the tank or any transfers of low VOC partial pressure liquid to or from the tank including volumes and vapor pressures to reduce tank liquid VOC partial pressure to <0.02 psi,

(e) if there is liquid in the tank, VOC partial pressure of liquid, start and completion of uncontrolled degassing, and total volumetric flow,

(f) refilling commenced, liquid filling the tank, and the volume necessary to float the roof; and

(g) tank roof off supporting legs, floating on liquid.

(4) the estimated quantity of each air contaminant, or mixture of air contaminants, emitted between events c and g with the data and methods used to determine it. The emissions associated with roof landing activities shall be calculated using the methods described in Section 7.1.3.2 of AP-42 "Compilation of Air Pollution Emission Factors, Chapter 7 - Storage of Organic Liquids" dated November 2006 and the permit application, PI-1, submitted January 5, 2007. **(8/10)**

70. Storage tanks shall not be ventilated without control, until either all standing liquid has been removed from the tank or the liquid in the tank has a VOC partial pressure less than 0.02 psia. This shall be verified and documented through one of the criteria identified in Paragraph C of Special Condition No. 69. Storage tanks manways may be opened without emission controls when there is standing liquid with a VOC partial pressure greater than 0.02 psi vapor as necessary to set up for degassing and cleaning. One manway may be opened to allow access to the tank to remove or de-volatilize the remaining liquid. The emission control system shall meet the requirements of Subparagraphs B(1) through B(5) of Special Condition No. 69 and records maintained per

Subparagraphs F(3)c through F(3)e, and F(4) of Special Condition No. 69. Low vapor pressure liquid may be added to and removed from the tank as necessary to lower the vapor pressure of the liquid mixture remaining in the tank to less than 0.02 psia. **(8/10)**

71. The following requirements apply to vacuum and air mover truck operations to support planned MSS at this site:

    A. Vacuum pumps and blowers shall not be operated on trucks containing or vacuuming liquids with VOC partial pressure greater than 0.50 psi at 95°F unless the vacuum/blower exhaust is routed to a control device or a controlled recovery system.

    B. Equip fill line intake with a “duckbill” or equivalent attachment if the hose end cannot be submerged in the liquid being collected.

    C. A daily record containing the information identified below is required for each vacuum truck in operation at the site each day.

        (1) Prior to initial use, identify any liquid in the truck. Record the liquid level and document that the VOC partial pressure is less than 0.50 psi if the vacuum exhaust is not routed to a control device or a controlled recovery system. After each liquid transfer, identify the liquid transferred and document that the VOC partial pressure is less than 0.50 psi if the vacuum exhaust is not routed to a control device or a controlled recovery system.

        (2) For each liquid transfer made with the vacuum operating, record the duration of any periods when air may have been entrained with the liquid transfer. The reason for operating in this manner and whether a “duckbill” or equivalent was used shall be recorded. Short, incidental periods, such as those necessary to walk from the truck to the fill line intake, do not need to be documented.

        (3) If the vacuum truck exhaust is controlled with a control device other than an engine or oxidizer, VOC exhaust concentration upon commencing each transfer, at the end of each transfer, and as required by Special Condition No. 75, measured using an instrument meeting the requirements of Special Condition No. 67.

        (4) The volume in the vacuum truck at the end of the day, or the volume unloaded, as applicable.

    D. The permit holder shall determine the vacuum truck emissions each month using the vacuum truck records and the calculation methods utilized in the permit application. If records of the volume of liquid transferred for each pick-up are not maintained, the emissions shall be determined using the physical properties of the liquid vacuumed with the greatest potential emissions. Rolling 12 month vacuum truck emissions shall also be determined on a monthly basis.

    E. If the VOC partial pressure of all the liquids vacuumed into the truck is less than 0.10 psi, this shall be recorded when the truck is unloaded or leaves the plant site and the emissions may be estimated as the maximum potential to emit for a truck in that service as documented in the permit application. The recordkeeping requirements in Paragraphs A through D of this condition do not apply. **(8/10)**

72. The following requirements apply to frac, or temporary, tanks and vessels used in support of MSS activities.

A. The exterior surfaces of these tanks/vessels that are exposed to the sun shall be white or aluminum effective May 1, 2013. This requirement does not apply to tanks/vessels that only vent to atmosphere when being filled.

B. These tanks/vessels must be covered and equipped with fill pipes that discharge within 6 inches of the tank/vessel bottom.

C. These requirements do not apply to vessels storing less than 100 gallons of liquid that are closed such that the vessel does not vent to atmosphere.

D. The permit holder shall maintain an emissions record which includes calculated emissions of VOC from all frac tanks during the previous calendar month and the past consecutive 12 month period. The record shall include tank identification number, dates put into and removed from service, control method used, tank capacity and volume of liquid stored in gallons, name of the material stored, VOC molecular weight, and VOC partial pressure at the estimated monthly average material temperature in psia. Filling emissions for tanks shall be calculated using the TCEQ publication titled "Technical Guidance Package for Chemical Sources - Loading Operations" and standing emissions determined using: the TCEQ publication titled "Technical Guidance Package for Chemical Sources - Storage Tanks."

E. If the tank/vessel is used to store liquid with VOC partial pressure less than 0.10 psi at 95°F, records may be limited to the days the tank is in service and the liquid stored. Emissions may be estimated based upon the potential to emit as identified in the permit application. **(8/10)**

73. MSS activities represented in the permit application may be authorized under permit by rule only if the procedures, emission controls, monitoring, and recordkeeping are the same as those required by this permit. **(8/10)**

74. All permanent facilities must comply with all operating requirements, limits, and representations in the permits identified in Attachment D during planned startup and shutdown unless alternate requirements and limits are identified in this permit. Alternate requirements for emissions from routine emission points are identified below.

A. Combustion units, with the exception of flares, at this site are exempt from NO_x and CO operating requirements identified in special conditions in other NSR permits during planned startup and shutdown if the following criteria are satisfied.

(1) The maximum allowable emission rates in the permit authorizing the facility are not exceeded.

(2) The startup period does not exceed 8 hours in duration and the firing rate does not exceed 75 percent of the design firing rate. The time it takes to complete the shutdown does not exceed 4 hours.

(3) Control devices are started and operating properly when venting a waste gas stream.

B. The limits identified below apply to the operations of the specified facilities during startup and shutdown.

During periods of startup of FCCU-3, the CO emissions are not required to comply with 30 TAC § 117.310(c)(1)(A), 400 ppmv at 3 percent O_2 on a rolling 24-hour average basis. A CO continuous emission monitor must be properly operated and maintained. The emissions during startup can average 1,500 ppmv at 3 percent O_2 on a rolling 24-hour average basis for up to two days.

C. FCCU-3 is authorized to operate in hot standby mode for up to 336 hours per event as necessary to accommodate planned maintenance and repair of components associated with the unit. Torch oil combustion emissions through the wet scrubber control for EPN 34A shall be continuously monitored as required for normal operation and start up and shutdown, but the emissions shall be accounted and show compliance hourly and 12 month rolling in the Planned MSS Emissions Cap. During these periods of hot standby the CO is not required to comply with 30 TAC § 117.310(c)(1)(A), 400 ppmvd at 3 percent O_2 on a rolling 24-hour average basis. The vent emission shall not exceed a 1,500 ppmvd at 3 percent O_2 on a rolling 24-hour average basis during hot standby mode.

D. A record shall be maintained indicating that the start and end times each of the activities identified above occur and documentation that the requirements for each have been satisfied. **(4/13)**

75. Additional or temporary control devices required by this permit for emissions from planned MSS activities are limited to those types identified in this condition. Control devices shall be operated with no visible emissions except periods not to exceed a total of five minutes during any two consecutive hours. Each device used must meet all the requirements identified for that type of control device. **(4/13)**

Controlled recovery systems identified in this permit shall be directed to an operating refinery process or to a collection system that is vented through a control device meeting the requirements of this permit condition.

A. Carbon Adsorption System (CAS). **(12/11)**

(1) The CAS shall consist of 2 carbon canisters in series with adequate carbon supply for the emission control operation.

(2) The CAS shall be sampled downstream of the first can and the concentration recorded at least once every hour of CAS run time to determine breakthrough of the VOC. The sampling frequency may be extended using either of the following methods:

(a) CAS systems equipped with an upstream liquid scrubber may be sampled once every 12 hours of CAS run time to determine breakthrough.

(b) Sampling frequency may be extended to up to 30 percent of the minimum potential saturation time for a new can of carbon. The permit holder shall maintain records including the calculations performed to determine the minimum saturation time.

(c) The carbon sampling frequency may be extended to longer periods based on previous experience with carbon control of a MSS waste gas stream. The past experience must be with the same VOC, type of facility, and MSS activity. The basis for the sampling frequency shall be recorded. If the VOC concentration on the initial sample downstream of the first carbon canister following a new polishing canister being put in place is greater than 100 ppmv above background, it shall be assumed that breakthrough occurred while that canister functioned as the final polishing canister and a permit deviation shall be recorded.

(3) The method of VOC sampling and analysis shall be by detector meeting the requirements of Special Condition No. 67.

(4) Breakthrough is defined as the highest measured VOC or benzene concentration at or exceeding 100 ppmv or 5 ppmv, respectively, above background. When the condition of breakthrough of VOC from the initial saturation canister occurs, the waste gas flow shall be switched to the second canister and a fresh canister shall be placed as the new final polishing canister within 24 hours. In lieu of replacing canisters, the flow of waste gas may be discontinued until the canisters are switched. Sufficient new activated carbon shall be maintained at the site to replace spent carbon such that replacements can be done in the above specified time frame.

(5) Records of CAS monitoring shall include the following:

(a) Sample time and date.

(b) Monitoring results (ppmv).

(c) Canister replacement log.

(6) Single canister systems are allowed if the time the carbon canister is in service is limited to no more than 30 percent of the minimum potential saturation time. The permit holder shall maintain records for these systems, including the calculations performed to determine the saturation time. The time limit on carbon canister service shall be recorded and the expiration date attached to the carbon can.

(7) Liquid scrubbers may be used upstream of carbon canisters to enhance VOC capture provided such systems are closed systems and the spent absorbing solution is discharged into a closed container, vessel, or system.

B. Thermal Oxidizer or Vapor Combustors

(1) The thermal oxidizer firebox exit temperature shall be maintained at not less than 1,250°F and waste gas flows shall be limited to assure at least a 0.5 second residence time in the fire box while waste gas is being fed into the oxidizer.

The thermal oxidizer combustion chamber exhaust temperature shall be continuously monitored and recorded when waste gas is directed to the oxidizer. The temperature measurements shall be made at intervals of six minutes or less and recorded at that frequency. Temperature measurements recorded in continuous strip charts may be used to meet the requirements of this section.

The temperature measurement device shall be installed, calibrated, and maintained according to accepted practice and the manufacturer's specifications. The device shall have an accuracy of the greater of ±0.75 percent of the temperature being measured expressed in degrees Celsius or ±2.5ºC.

(2) As an alternative to Paragraph B(1) of this condition, the thermal oxidizer may be tested to confirm a minimum of 99 weight percent destruction efficiency. The results of the test will be used to determine the minimum operating temperature and residence time. A stack test must have been performed within the last 12 months. Stack VOC concentrations and flow rates shall be measured in accordance with applicable EPA Reference Methods. A copy of the test report shall be maintained with the thermal oxidizer and a summary of the testing results shall be included with the emission calculations.

(3) As an alternative to Paragraphs B(1) and B(2) of this condition, the thermal oxidizer may be equipped with continuous VOC monitors (inlet and outlet). The VOC monitors shall be calibrated and maintained in accordance with Special Conditions No. 67, except Paragraph C of Special Condition No. 67. In order to demonstrate compliance

with this requirement, inlet VOC and outlet VOC concentrations shall be measured and inlet and outlet VOC mass rates shall be calculated on an hourly basis to confirm minimum 99 weight percents destruction efficiency or an exhaust concentration no greater than 20 ppmv.

C. Internal Combustion Engine.

(1) The internal combustion engine shall have a VOC destruction efficiency of at least 99 percent.

(2) The engine must have been stack tested with butane or propane to confirm the required destruction efficiency within the past 12 months. VOC shall be measured in accordance with the applicable EPA Reference Method during the stack test and the exhaust flow rate may be determined from measured fuel flow rate and measured oxygen concentration. A copy of the stack test report shall be maintained with the engine. There shall also be documentation of acceptable VOC emissions following each occurrence of engine maintenance which may reasonably be expected to increase emissions including oxygen sensor replacement and catalyst cleaning or replacement. Stain tube indicators specifically designed to measure VOC concentration shall be acceptable for this documentation, provided a hot air probe or equivalent device is used to prevent error due to high stack temperature, and three sets of concentration measurements are made and averaged. Portable VOC analyzers meeting the requirements of Special Condition No. 67 are also acceptable for this documentation.

The test period may be extended to 24 months if the engine exhaust is sampled once an hour when waste gas is directed to the engine using a detector meeting the requirements of Special Condition No. 67A. The sample ports and the collection system must be designed and operated such that there is no air leakage into the sample probe or the collection system downstream of the engine. The concentrations shall be recorded and the MSS activity shall be stopped as soon as possible if the VOC concentration exceeds 100 ppmv above background.

(3) The engine shall be operated with an oxygen sensor-based air-to-fuel ratio (AFR) controller. Documentation for each AFR controller that the, manufacturer's, or supplier's recommended maintenance has been performed, including replacement of the oxygen sensor as necessary for oxygen sensor based controllers shall be maintained with the engine. The oxygen sensor shall be replaced at least quarterly in the absence of a specific written recommendation.

D. Flares

(1) The heating value and velocity requirements in 40 CFR § 60.18 shall be satisfied during operations authorized by this permit.

(2) The flare shall be operated with a flame present at all times and/or have a constant pilot flame. The pilot flame shall be continuously monitored by a thermal couple or an infrared monitor. The time, date, and duration of any loss of pilot flame shall be recorded. Each monitoring device shall be accurate to, and shall be calibrated at a frequency in accordance with, the manufacturer’s specifications.

(3) The permit holder shall either demonstrate 40 CFR § 60.18 BTU requirements are met during the MSS flaring activity using engineering calculations or install a continuous flow monitor and either a composition analyzer that provides a record of the vent stream flow and total VOC content to the flare or a calorimeter that provides a record of

the Btu content of the vent stream flow to the flare. The flow monitor sensor and analyzer sample points shall be installed in the vent stream as near as possible to the flare inlet such that the total vent stream to the flare is measured and analyzed. Readings shall be taken at least once every 15 minutes and the average hourly values of the flow and composition or BTU content shall be recorded each hour.

The monitors shall be calibrated on an annual basis to meet the following accuracy specifications: the flow monitor shall be ±5.0 percent, temperature monitor shall be ±2.0 percent at absolute temperature, and pressure monitor shall be ±5.0 mm Hg;

If a total VOC analyzer is installed, calibration of the composition analyzer shall follow the procedures and requirements of Section 10.0 of 40 CFR Part 60, Appendix B, Performance Specification 9, as amended through October 17, 2000 (65 FR 61744), except that the multi-point calibration procedure in Section 10.1 of Performance Specification 9 shall be performed at least once every calendar quarter instead of once every month, and the mid-level calibration check procedure in Section 10.2 of Performance Specification 9 shall be performed at least once every calendar week instead of once every 24 hours. The calibration gases used for calibration procedures shall be in accordance with Section 7.1 of Performance Specification 9. Net heating value of the gas combusted in the flare shall be calculated according to the equation given in 40 CFR § 60.18(f)(3) as amended through October 17, 2000 (65 FR 61744).

If a calorimeter is installed, the calorimeter shall be calibrated, installed, operated, and maintained, in accordance with manufacturer recommendations, to continuously measure and record the net heating value of the gas sent to the flare, in British thermal units/standard cubic foot of the gas.

The monitors and analyzers shall operate as required by this section at least 95 percent of the time when the flare is operational, averaged over a rolling 12 month period. Flared gas net heating value and actual exit velocity determined in accordance with 40 CFR § 60.18(f)(4) shall be recorded at least once every 15 minutes. If a total VOC analyzer is installed, hourly mass emission rates shall be determined and recorded using the above readings and the emission factors used in the permit amendment application, PI-1 dated January 5, 2007. **(8/10)**

E. A liquid scrubbing system may be used upstream of carbon adsorption. A single carbon can or a liquid scrubbing system may be used as the sole control device if the requirements below are satisfied.

(1) The exhaust to atmosphere shall be monitored continuously and the VOC concentration recorded at least once every 15 minutes when waste gas is directed to the scrubber.

(2) The method of VOC sampling and analysis shall be by detector meeting the requirements of Special Condition No. 67A.

(3) An alarm shall be installed such that an operator is alerted when outlet VOC concentration exceeds 100 ppmv above background. The MSS activity shall be stopped as soon as possible when the VOC concentration exceeds 100 ppmv above background for more than one minute. The date and time of all alarms and the actions taken shall be recorded.

F. A closed loop refrigerated vapor recovery system

(1) The vapor recovery system shall be installed on the facility to be degassed using good engineering practice to ensure air contaminants are flushed from the facility through

the refrigerated vapor condensers and back to the facility being degassed. The vapor recovery system and facility being degassed shall be enclosed except as necessary to insure structural integrity (such as roof vents on a floating roof tank).

(2) VOC concentration in vapor being circulated by the system shall be sampled and recorded at least once every 4 hours at the inlet of the condenser unit with an instrument meeting the requirements of Special Condition No. 67.

(3) The quantity of liquid recovered from the tank vapors and the tank pressure shall be monitored and recorded each hour. The liquid recovered must increase with each reading and the tank pressure shall not exceed one inch water pressure while the system is operating.

76. With the exception of the ECIELT emission limits, Special Condition Nos. 65 through 75 become effective 180 days after the permit amendment received by the TCEQ on January 5, 2007, has been approved. During this period, monitoring and recordkeeping shall satisfy the requirements of Paragraphs A through D of Special Condition No. 65. Emissions shall be estimated using good engineering practice and methods to provide reasonably accurate representations for emissions. The basis used for determining the quantity of air contaminants to be emitted shall be recorded. The permit holder may maintain abbreviated records of emissions from Attachment A and B activities as allowed in Special Condition No. 65 rather than documenting all the information required by Paragraphs A through D of Special Condition No. 65.

Other Requirements

77. The FCCU3 project authorized by the amendment application, dated April 26, 2011, was determined not to be subject to major new source review for CO, NO_x, PM/PM_{10}/$PM_{2.5}$, SO_2, or VOC by identifying projected actual emission rates for the facilities potentially affected by the project. Projected actual and baseline emission rates for the potentially affected facilities are as follows:

Baseline Actual Emissions (tpy):

EPN	FIN	Permit	CO	NO_x	PM/PM_{10}/$PM_{2.5}$	SO_2	VOC
34A	FCCU No. 3	47256	851.73	173.86	289.77	199.94	38.61
280-13	Tank 13	47256					6.46
280-39	Tank 39	2231					9.44
280-16	Tank 16	47256					2.51
280-532	Tank 532	2231					2.58
280-533	Tank 533	2231					3.01
280-536	Tank 536	47256					13.83
80	Feed Heater No. 1	46052	10.65	5.49	1.14	3.04	0.83
521	Isostripper Reboiler Furnace	9606	0.83	10.86	2.47	3.36	1.78
384	SRU Incinerator C&D	47256	378.26	26.19		366.62	2.14

Projected Actual Emissions (tpy):

EPN	FIN	Permit	CO	NO_x	$PM/PM_{10}/PM_{2.5}$	SO_2	VOC
34A	FCCU No. 3	47256	499.23	109.33	299.67	190.29	33.98
280-13	Tank 13	47256					6.46
280-39	Tank 39	2231					9.45
280-16	Tank 16	47256					2.51
280-532	Tank 532	2231					2.58
280-533	Tank 533	2231					3.01
280-536	Tank 536	47256					13.83
80	Feed Heater No. 1	46052	10.65	5.49	1.14	3.04	0.83
521	Isostripper Reboiler Furnace	9606	0.83	10.87	2.47	3.36	1.78
384	SRU Incinerator C&D	47256	378.29	26.19		366.65	2.14

Actual emissions from those facilities shall be monitored, recorded and reports made in accordance 30 TAC § 116.127 for the time period specified in 30 TAC § 116.127(b)(1). **(12/11)**

78. The ULC Feedstock and Conversion Flexibility project per the amendment application dated May 23, 2014, was determined not to be subject to major new source review. The projected actual emissions, baseline actual emissions, capable of accommodating emissions, and the facilities affected by the project were provided in the latest addendum to the application, dated August 26, 2014. The ULC project projected actual emission including Emissions Unit (EPNs) is as follows **(09/14):**

EPN	FIN	Permit	CO	NO_x	PM/PM/ PM_{10}	SO_2	VOC
201	100-B Process Heater	47256	0.48	25.04	2.35	7.32	1.71
202	101-B Process Heater	47256	0.67	7.00	1.91	7.32	1.39
203	102-B Process Heater	47256	0.61	21.96	2.21	7.17	1.60
204	103-B Process Heater	47256	0.66	35.09	2.57	7.94	1.87
205	104-BA Process Heater	47256	19.45	89.92	7.14	23.13	5.16
205	104-BB Process Heater	47256					
206	105-BA Process Heater	47256	0.79	44.05	3.37	10.44	2.45
206	105-BB Process Heater	47256					
351-A	ULC Flare	47256	53.94	7.68		0.10	1.83
280-4	Tank 4	47256					7.73
280-5	Tank 5	47256					
280-7	Tank 7	47256					

EPN	FIN	Permit	CO	NO_x	PM/PM/ PM_{10}	SO_2	VOC
280-31	Tank 31	47256					42.47
280-32	Tank 32	47256					
280-34	Tank 34	47256					
280-45	Tank 45	47256					
280-80	Tank 80	47256					
280-46	Tank 46	47256					47.4
280-47	Tank 47	47256					
280-48	Tank 48a	47256					
280-53	Tank 53	47256					
280-54	Tank 54	47256					
280-51	Tank 51	47256					
280-52	Tank 52	47256					
280-55	Tank 55	47256					
280-56	Tank 56	47256					
280-57	Tank 57	47256					
Total ULC Project PAE (TPY)			**76.59**	**230.65**	**19.55**	**63.41**	**113.61**

Actual emissions from the project shall be monitored, recorded, and reports made in accordance with 30 TAC § 116.27 for the time period specified in 30 TAC § 116.127(b)(2).

The ULC flare gas recovery system must be fully operational before the new, larger ULC feed pumps begin operation. The creditable reductions for NOx and VOC from the ULC flare gas recovery system is provided under “Creditable Reductions – ULC Flare Gas Recovery” calculations in the permit application addendum dated August 26, 2014.

79. The Tank 117 throughput increase project associated with the permit amendment application, PI-1 dated October 22, 2012, was determined not to be subject to major new source review by identifying projected actual emission rates for the facilities modified or potentially affected by the project. Actual emissions from tank 117 shall be monitored, recorded, and reports made in accordance with 30 TAC §116.127 for the time period specified in 30 TAC §116.127(b) (1). The projected actual rate for tank 117 is 1.55 tpy VOC. **(2/13)**

80. Within 60 days upon submission of FCCU stack testing reports to the regional office, but no later than December 31, 2015, for the stack testing as specified in Special Condition 41 I of this permit, the permit holder shall submit an application to TCEQ Air Permits Division to provide the results of stack testing and update the representation of HCN emissions from the FCCU, if needed. Permit conditions related to monitoring, testing, recordkeeping, and reporting may be added or updated based on results of the stack test and evaluation of Best Available Control Technology (BACT) and/or Best Management Practices (BMP) during this project. **(06/15)**

81. The RDU Revamp Project, per the amendment application dated September 4, 2015, and June 28, 2017, was determined to not be subject to major new source review. Upon startup of the DCO Filtration/RDU Repurpose and RDU Revamp/Resid Expansion projects, the following monitoring

and recordkeeping requirements shall apply in order to demonstrate compliance with the incremental project increase represented in the permit amendment application PI-1, dated September 4, 2015, and June 28, 2017. These monitoring and recordkeeping requirements shall be performed in accordance with limits represented in the document entitled, "RDU Revamp Project Technical Basis and Compliance Demonstration and The Technical Basis Table", dated March 11, 2016, updated June 2017, in the aforementioned permit amendment application. A copy of the "RDU Revamp Project Technical Basis and Compliance Demonstration and The Technical Basis Table", dated March 11, 2016, updated June 2017, shall be kept with the permit at the site. Additionally, The Technical Basis Table is contained in Attachment F. **(9/17)**

A. The permit holder shall install and operate a flow meter to measure and record the resid feed to the RDU.

B. The resid feed shall be sampled once each calendar month to determine and record the total sulfur content (wt%) and density (lb/gal). The amount of sulfur production attributable to the resid feed shall be determined based on the sulfur content of the resid feed, the throughput of resid to the RDU, density, and the minimum required amount of sulfur recovery from the SRU as specified in Special Condition 16.

C. The permit holder shall install and operate a flow meter to measure and record the backwash flow from the DCO filtration unit to the FCCU3 and Coker Complex.

   Backwash shall be routed to either FCCU3 or the coker complex. The amount of solids collected in the filter shall be determined by sampling the DCO upstream and downstream of the filter. Sampling shall occur once each calendar month. Compliance with this limit shall be demonstrated by monitoring and recording the volumetric flow of DCO to the filter and the mass of solids collected as determined by sampling. Records of sampling reports, DCO flow to the filtration unit, and mass of solids collected shall be kept.

D. The permit holder shall install and operate a flow meter to measure and record the asphaltene feed from the RDU to the Coker complex.

E. The permit holder shall install and operate a flow meter to measure and record the resid feed to the RHU.

F. The permit holder shall install and operate a flow meter to measure and record the flow of DAO from the RDU to the FCCU3.

G. Flow monitoring devices shall be calibrated at a frequency in accordance with the manufacturer's specifications or at least annually, whichever is more frequent, and shall be accurate to within 5 percent.

   Quality assured (or valid) data must be generated during periods that flow is occurring. Loss of valid data due to periods of monitor break down, out-of-control operation (producing inaccurate data), repair, maintenance, or calibration may be exempted provided it does not exceed 5 percent of the time (in minutes) that the unit is operated over the previous rolling 12 month period. The measurements missed shall be estimated using engineering judgment and the methods used recorded.

H. Records shall be updated monthly and kept based on a 12 month rolling average. All records shall be kept for a period of 5 years.

82. The RDU Revamp Project, per the amendment application dated September 4, 2015, and June 28, 2017, was determined to not be subject to major new source review by identifying projected actual

emission rates for the facilities potentially affected by the project. Projected actual emission rates for the potentially affected facilities are as follows: **(9/17)**

Projected Actual Emissions (tpy):

EPN	FIN	Permit	CO	NO_x	$PM/PM_{10}/PM_{2.5}$	SO_2	VOC
550	RDU-601B	47256	23.34	37.82	4.33	26.61	3.14
HEATERPM	Process heater 100-B, 101-B, 102-B, 103-B, 105-BA, 105-BB, DDU-102B, and DDU-202B				16.97		

Actual emissions from those facilities shall be monitored, recorded and reports made in accordance 30 TAC § 116.127 for the time period specified in 30 TAC § 116.127(b)(1).

83. The Naphtha Optimization Project, per the amendment application dated July 13, 2016 and updated Sept. 30, 2016, was determined to not be subject to major new source review. Upon startup of the Naphtha Optimization project, the requirements listed in the application will be in effect. In addition, under TCEQ Audit Privilege Blanchard discovered and disclosed elevated concentrations of sulfur higher than previously authorized. Blanchard has entered into a Compliance Agreement with the TCEQ dated July 27, 2016 to reduce the total sulfur in the refinery fuel gas to 162 ppmv no later than December 31, 2020. Until that time, Blanchard shall demonstrate compliance based on an interim SO2 emission cap over a rolling 12 month average. Projected actual emission rates for the potentially affected facilities are as follows: **(05/17)**

EPN	FIN	Permit	SO_2 (Interim) tpy	SO_2 (Final) tpy
161A	Ultraformer Reheat Furnaces (310B, 311B, 312B)	47256	148.45	130.04
164A	UU3 313B Regeneration Flue Gas Heater	47256	9.05	5.66
165A	UU3 Hot Oil Heater	47256	67.39	42.24
168	UU3 Desulfurizer Furnace	47256	18.15	12.17
169	UF Splitter Reboiler	47256	33.34	21.11
171	AU2 B-621B Toluene Tower Reboiler	2612	43.21	27.47
173	AU2 B-621A Toluene Tower Reboiler	2612		
601	AU2 B-601 Reactor Charge Furnace	2612	49.85	33.03
201	ULC 100B Recycle Gas Furnace	47256	13.62	8.62
202	ULC 101B Recycle Gas Furnace	47256	13.62	8.62
203	ULC 102B Recycle Gas Furnace	47256	12.58	7.91
204	ULC 103B Recycle Oil Furnace	47256	15.09	9.55
205	ULC 104B Debutanizer Reboiler	47256	40.62	25.37

EPN	FIN	Permit	SO_2 (Interim) tpy	SO_2 (Final) tpy
206	ULC 105B Splitter Reboiler	47256	20.31	17.32
		Emission Cap	485.28	

Actual emissions from those facilities shall be monitored, recorded and reports made in accordance 30 TAC § 116.127 for the time period specified in 30 TAC § 116.127(b)(1). **(01/17)**

84. The Finished Products Export Project, per the amendment application dated September 2, 2016 and updated February 2, 2018, was determined to not be subject to major new source review by identifying projected actual emission rates for the facilities potentially affected by the project. Projected actual emission rates and baseline actual emission rates for the potentially affected facilities are as follows. **(05/18)**

Projected Actual Emissions (tpy):

EPN	FIN	Permit	CO	NO_x	$PM/PM_{10}/PM_{2.5}$	SO_2	VOC
299-32, 33, 34, 37, 38	DOCKS	47256					8.48
294-1, 2, 3	LD-RKS	47256	32.34	26.24	3.26	0.75	4.87
280-16A	T280-16A	47256					7.28
280-22	T280-22	47256					6.25
280-23	T280-23	47256					6.69
280-24	T280-24	47256					1.37
280-37	T280-37	2231					6.85
280-38	T280-38	2231					2.68
280-39	T280-39	2231					6.33
280-530	T280-530	47256					5.40
280-531	T280-531	47256					6.53

Actual emissions from those facilities shall be monitored, recorded and reports made in accordance 30 TAC § 116.127 for the time period specified in 30 TAC § 116.127(b)(1).

Baseline Actual Emissions (tpy):

EPN	FIN	Permit	CO	NO_x	$PM/PM_{10}/PM_{2.5}$	SO_2	VOC
299-32, 33, 34, 37, 38	DOCKS	47256	9.65	23.93	1.73	0.63	5.47
294-1, 2, 3	LD-RKS	47256					2.87
280-16A	T280-16A	47256					0.00
280-22	T280-22	47256					6.96

EPN	FIN	Permit	CO	NO_x	$PM/PM_{10}/PM_{2.5}$	SO_2	VOC
280-23	T280-23	47256					2.97
280-24	T280-24	47256					2.93
280-37	T280-37	2231					4.38
280-38	T280-38	2231					2.91
280-39	T280-39	2231					3.75
280-530	T280-530	47256					1.91
280-531	T280-531	47256					2.42

85. The PS3B Revamp/RHU Revamp/New DHT Project per the amendment application dated January 19, 2017, and subsequent application updates, was determined to be subject to major new source review for CO, $PM/PM_{10}/PM_{2.5}$, SO_2, and VOC and minor new source review for NO_X. **(PSD) (NNSR) (GHG) (11/18)**

A. The PS3B Revamp/RHU Revamp/New DHT Project's baseline emissions (BAE), projected actual emissions (PAE), and project emissions increases (PEIs) for new/modified/affect units were provided in the January 19, 2017 application and subsequent application updates.

Projected Actual Emissions (tpy):

EPN	FIN	Permit	NO_x
72	COKR-B201	2315	16.72
74	COKR-B301	2315	16.72
78	COKR-B302	2315	36.14
481	RHU-201B/202B	47256	28.42
482	RHU-301B/302B	47256	27.36
483	RHU-401B/402B	47256	25.28
484	RHU-501B/502B	47256	55.85
485	RHU-601B	47256	17.28
391	DDU-101B	47256	23.90
41	PS3B-401BA	47256	14.62
42	PS3B-401BB	47256	14.75
44	PS3B-401BC	47256	37.26
471	CFHU-101B/102B	47256	37.98
43A	PS3B-402BE/BF/BG	47256	35.56
	Total		387.84

Actual emissions from those facilities shall be monitored, recorded and reports made in accordance 30 TAC § 116.127 for the time period specified in 30 TAC § 116.127(b)(2).

B. Distillate marine loading shall not exceed 210,000 barrels per day, annual average.

C. Fuel gas shall be sampled periodically (at least monthly) to determine total sulfur concentration to verify permitted SO_2 emissions

86. This Nonattainment New Source Review (NNSR) permit is issued/approved based on the requirement that the permit holder offset the project emission increase for facilities authorized by this permit prior to the commencement of operation, through participation in the TCEQ Emission Banking and Trading (EBT) Program in accordance with the rules in 30 TAC Chapter 101, Subchapter H. **(PSD) (GHG (11/18)**

The permit holder shall use 125 tons per year (tpy) of credits to offset the 108.64 tpy VOC project emission increase for the facilities authorized by this permit at an offset ratio of 1.15 to 1.0. The 125 tpy of offsets may be divided between the PS3B Revamp and RHU Revamp Project and the DHT Project. Offsets obtained for the PS3B Revamp and RHU Revamp Project shall equal 118.0 tpy. Offsets obtained for the DHT Project shall equal 7.0 tpy.

Prior to the commencement of operation of each project, the permit holder shall obtain approval from the TCEQ EBT Program for the credits being used and then submit a permit alteration or amendment request to the TCEQ Air Permits Division (and copy the TCEQ Regional Office) to identify approved credits by TCEQ credit certificate number.

87. This permit is conditioned on the completion of all emission reduction projects represented in the Table 3F, Project Contemporaneous Changes received by the TCEQ on August 9, 2018 (see Permit Number 47256 application file) for the PS3B Revamp/RHU Revamp/New DHT Project (application received on January 19, 2017.) This reduction of emissions shall occur not later than the commencement of operation of the permitted facilities represented by this permit. The holder of this permit shall maintain records of the emission reductions and provide access and/or copies upon request to the TCEQ Executive Director, or representatives, or any local air pollution control program having jurisdiction. Construction of these facilities must commence as defined in 40 CFR 52.21(b)(9) Prevention of Significant Deterioration or 40 CFR 51.165(a)(1)(xvi) (nonattainment) no later than five years after the reductions are actually accomplished, or the above reductions are no longer creditable and the permit is automatically void. **(PSD) (11/18)**

Additional GHG Specific Conditions

88. The annual firing rates of the following heaters shall not exceed the following MMBtu/hr limits on a higher heating value (HHV) basis: **(PSD) (GHG) (11/18)**

EPN	Name	Annual Firing Rate (MMBtu/hr)
DHT-101B	DHT Stripper Reboiler	80
DHT-201B	DHT Reactor Charge Heater	115
Part of 484	RHU-502B RHU Fractionation Heater	126

A. The permit holder shall continuously monitor and record the average hourly fuel consumption of the heaters with individual flow measurements being taken no less frequently than once every 15 minutes. The fuel flow meters shall be installed, calibrated, maintained, and operated according to the manufacturer's instructions. The flow meters shall be accurate to ±

5.0 percent of the unit's maximum flow. The monitoring system data shall be used to demonstrate continuous compliance with the emission limits of CO_{2e} in the attached MAERT.

B. Fuel gas readings recorded during periods of monitoring instrumentation malfunction and maintenance shall be excluded from calculation of the monthly and 12-month totals. The monitoring operation downtime shall not exceed 5% of the combustion unit operating time during any 12-month rolling period.

89. The heaters (EPN: DHT-101B, DHT-201B, and 484 for RHU-502B) have the following requirements**. (PSD) (GHG) (11/18)**

A. The exhaust temperature shall be less than or equal to the temperature listed on a 12-month rolling average basis.

EPN	Name	Exhaust Temperature (°F)
DHT-101B	DHT Stripper Reboiler	665
DHT-201B	DHT Reactor Charge Heater	665
Part of 484	RHU-502B RHU Fractionation Heater	525

The permit holder shall continuously monitor and record the stack exhaust temperature. The outlet temperature must be recorded at least four times an hour (once every fifteen minutes). Stack temperatures recorded during periods of monitoring instrumentation malfunction and maintenance shall be excluded from calculation of the 12-month rolling average. The monitoring operation downtime shall not exceed 5% of the operating time during any 12-month rolling period. The temperature measurement device shall be installed, calibrated, and maintained according to the manufacturer's specifications. The device shall be accurate to within 2 percent of the temperature being measured or 10 degrees Fahrenheit, whichever is greater.

B. This stack temperature limit applies only during normal operations and does not apply during commissioning, startup, or shutdown, and stack temperature readings during such periods shall be excluded from calculation of the 12-month rolling average.

C. In addition to the above requirements, the permit holder shall implement the work practices of the following:

(1) Inspect and tune burners and conduct a visual inspection of the heater components at least annually.

(2) Perform preventative maintenance as required

90. Emission calculation methodologies and monitoring and quality assurance/quality control requirements related to GHG emissions shall adhere to the applicable requirements in 40 CFR Part 98 and in this permit. **(GHG) (PSD) (11/18)**

If any condition of this permit conflicts with applicable requirements in 40 CFR Part 98, then for the purposes of complying with this permit, the requirements in 40 CFR Part 98 shall govern and be the standard by which compliance shall be demonstrated.

91. No later than June 30, 2019 the permit holder shall submit an application to consolidate NSR permits 22433 and 47256. **(02/17)**

Docks 40/41 (09/18)

92. Loading operations at Docks 40/41 shall be limited to distillate products, including diesel fuel, kerosene, jet fuel, and light catalytic cycle oil (LCCO). The combined throughput from all distillate product loading lines shall not exceed 14,000 barrels per hour. In order to demonstrate compliance with the MAERT limit of 17.69 lb/hr VOC, the engineering analysis provided on May 18, 2018 shall be maintained to show that the sum of maximum throughput from all distillate product loading pumps and cargo lines cannot exceed 14,000 bbl/hr at any given time. The analysis shall be kept on site and made available to TCEQ or local air pollution control program representative upon request. The permit holder shall maintain and update a monthly emissions record which includes calculated emissions of VOC over the previous rolling 12-month period. Records of the actual type and volume of product loaded shall be maintained.

Referenced Permits by Rule

93. The following sources and/or activities are authorized under a Standard Permit (SP) by 30 TAC Chapter 116 or a Permit by Rule (PBR) by Title 30 Texas Administrative Code Chapter 106 (30 TAC Chapter 106). These lists are not intended to be all inclusive and can be altered without modifications to this permit. **(11/18)**

Authorization	Source or Activity
30 TAC § 106.472 (effective 09/04/00)	Corrosion Inhibitor Storage Tanks (EPN NACE Tote)
SP 49771	Authorizes SCRs on heaters, EPN 41 (PS3B-401BA), EPN 42 (PS3B-401BB), and EPN 43A (PS3B Heaters 402BE, 402BF, and 402BG

Date: November 30, 2018

Attachment A

Flexible Permit Numbers 47256 and PSDTX402M4

Inherently Low Emitting Activities

Activity	Emissions				
	VOC	NO_x	CO	SO_2	H_2S
Analyzer calibration	X	X	X	X	X
Analyzer filter changeouts	X				X
Carbon canister replacement	X				
Equipment Lubrication (WD-40, etc.)	X				
Injection quill repairs / replacement	X				
Instrumentation repairs / replacement	X				
Meter proving	X				
Process Sampling	X				X
Sight glass or level instrument maintenance / repair / replacement	X				X
Solvent cleaning of fixed, immovable objects	X				

Date: December 13, 2011

Attachment B

Flexible Permit Numbers 47256 and PSDTX402M4

Routine Maintenance Activities

Planned MSS activities performed with work orders where the isolated system volume is less than 30 cubic feet. These include activities such as:

Pump repair/replacement

Fugitive component (valve, pipe, flange) repair/replacement

Compressor repair/replacement

Heat exchanger repair/replacement

Vessel repair/replacement

Date: December 13, 2011

Attachment C

Flexible Permit Numbers 47256 and PSDTX402M4

MSS Activity Summary

Facilities	Description	Emissions Activity	EPN or Group
all process units	process unit shutdown/depressurize/drain	vent to Flare or Tail Gas Incinerator	Flares and Incinerators
all process units	process unit purge/degas/drain	vent to atmosphere	F-1000
all process units	process unit startup	vent to Flare or Tail Gas Incinerator	Flares and Incinerators
all process units and storage tanks	preparation for facility/component repair/replacement	vent to Flare or Tail Gas Incinerator	Flares and Incinerators
FCCU-3	hot standby to allow ancillary equipment repair/replacement	Torch oil firing in the regenerator to maintain temperature	34A
all process units and storage tanks	preparation for facility/component repair/replacement	vent to atmosphere	F-1000
all process units and storage tanks	recovery from facility/component repair/replacement	vent to flare	Flares and Incinerators
all process units and storage tanks	recovery from facility/component repair/replacement	vent to atmosphere	F-1000
all process units and storage tanks	preparation for unit turnaround or facility/component repair/replacement	remove liquid	F-1000
all floating roof storage tanks	tank roof landing	operation with landed roof	F-1000
all floating roof storage tanks	degas of tank with landed roof	vent to control device	311, 321, 331, 400, TEMP1, and TEMP2
all storage tanks	tank cleaning	cleaning activity and solvents	F-1000
see Attachment A	miscellaneous low emitting activities	see Attachment A	F-1000

Date: April 15, 2013

Attachment D

Flexible Permit Number 47256 and PSDTX402M4

Facility List

This permit authorizes emissions from the following temporary facilities used to support planned maintenance, startup, and shutdown (MSS) activities at permanent site facilities: frac tanks, containers, vacuum trucks, portable control devices identified in Special Condition No. 75 and controlled recovery systems. Emissions from temporary facilities are authorized provided the temporary facility (a) does not remain on the plant site for more than 12 consecutive months, (b) is used solely to support planned MSS activities at the permanent site facilities listed in this Attachment, and (c) does not operate as a replacement for an existing authorized facility.

This permit authorizes MSS emissions from the permanent site facilities identified below. The headings for each group of facilities (Process Units, Tanks, etc.) are used in the MSS Activity Summary to identify all facilities in the respective group.

Process Units		
Unit Name	**Abbreviation**	**NSR Permit No.**
Alkylate 3 Debutanizer Unit	ALKY3DB	20850
Alkylation Unit No. 2	ALKY2	47256/PSDTX402M4
Alkylation Unit no. 3	ALKY3	9606
Aromatics Recovery Unit	ARU	2231
Aromatics Unit 2	AU2	2612
Cat Feed Hydrotreater Unit	CFHU	47256/PSDTX402M4
Coker Residuum Preheat System	N/A	6592
Coking Complex	Coker	2315
Distillate Desulphurization Unit	DDU	47256/PSDTX402M4
Distillate Hydrotreater Unit **(11/18)**	DHT	47256/PSDTX402M4
Distillate Ultrafiner Facility	N/A	47256/PSDTX402M4
Docks	Docks	47256/PSDTX402M4
Docks 40/41 **(09/18)**	Docks 40/41	47256/PSDTX402M4
Dock 54	Dock 54	2231
Environmental Facility	ENVF	47256/PSDTX402M4
Fluid Catalytic Cracking Unit 1 Ancillary Equipment	FCCU1	47256/PSDTX402M4
Fluid Catalytic Cracking Unit 3	FCCU3	47256/PSDTX402M4
Hydrocarbon Tank 537	N/A	1940
Hydrogen Recovery Unit	HRU	47256/PSDTX402M4
Naphtha Desulphurization Unit	NDU	46052
Pipestills 3A	PS3A	19599
Pipestills 3B	PS3B	47256/PSDTX402M4
Power Station No. 2	PWRS2	47256/PSDTX402M4
Raffinate Splitter Tower	N/A	47256/PSDTX402M4

Process Units		
Unit Name	**Abbreviation**	**NSR Permit No.**
Resid Deasphalting Unit	RDU	47256/PSDTX402M4
Resid Hydrotreating Unit	RHU	47256/PSDTX402M4
Sulfur Recovery Unit	SRU	47256/PSDTX402M4
Tank Farm	OMCC	2231 and 47256/PSDTX402M4
Ultracracker Unit	ULC ancillary	2609
Ultraformer Unit No. 3	UU3	47256/PSDTX402M4
Ultraformer Unit No. 4	UU4	6488
Wastewater Treatment Unit	WWTP	22107

Flares, Incinerators and other Control		
Flare or Incinerator Number	**EPN**	**NSR Permit No.**
Refinery Flare No. 2	311	47256/PSDTX402M4
Refinery Flare No. 3	321	47256/PSDTX402M4
Refinery Flare No. 4	331	47256/PSDTX402M4
ULC Flare	351A	47256/PSDTX402M4
SRU A/B Flare	381	47256/PSDTX402M4
SRU C/D Flare	383	47256/PSDTX402M4
SRU Incinerator C and D	384	47256/PSDTX402M4
DDU Flare	396A	47256/PSDTX402M4
Flare 8	400	47256/PSDTX402M4
CFHU Flare 1	501	47256/PSDTX402M4
SRU Sour Water System Flare	FLR-SW	47256/PSDTX402M4
Ground Flare #5	TCH-5	15497
Flare 6	530	9606
AU2 Flare	611	2612
Temporary Control Device No. 1	TEMP1	47256/PSDTX402M4
Temporary Control Device No. 2	TEMP2	47256/PSDTX402M4
FCCU-3 Regenerator Scrubber	34A	47256/PSDTX402M4

Storage Tanks		
Tank Number	**EPN**	**NSR Permit No.**
Tank 4	280-4	47256/PSDTX402M4
Tank 5	280-5	47256/PSDTX402M4
Tank 7	280-7	47256/PSDTX402M4

Storage Tanks		
Tank Number	**EPN**	**NSR Permit No.**
Tank 8	280-8	2231
Tank 9	280-9	2231
Tank 10	280-10	2231
Tank 11	280-11	47256/PSDTX402M4
Tank 12A	280-12A	47256/PSDTX402M4
Tank 13	280-13	47256/PSDTX402M4
Tank 13A	280-13A	47256/PSDTX402M4
Tank 14	280-14	47256/PSDTX402M4
Tank 14A	280-14A	47256/PSDTX402M4
Tank 16A	280-16A	47256/PSDTX402M4
Tank 17	280-17	47256/PSDTX402M4
Tank 18	280-18	47256/PSDTX402M4
Tank 19	280-19	2231
Tank 20	280-20	2231
Tank 22	280-22	47256/PSDTX402M4
Tank 23	280-23	47256/PSDTX402M4
Tank 24	280-24	47256/PSDTX402M4
Tank 25	280-25	47256/PSDTX402M4
Tank 26	280-26	47256/PSDTX402M4
Tank 27	280-27	47256/PSDTX402M4
Tank 28	280-28	2231
Tank 29	280-29	2231
Tank 30	280-30	2231
Tank 31	280-31	47256/PSDTX402M4
Tank 32	280-32	47256/PSDTX402M4
Tank 34	280-34	47256/PSDTX402M4
Tank 36	280-36	2231
Tank 37	280-37	2231 and 47256/PSDTX402M4
Tank 38	280-38	2231 and 47256/PSDTX402M4
Tank 39	280-39	2231
Tank 41	280-41	47256/PSDTX402M4
Tank 42	280-42	47256/PSDTX402M4
Tank 43	280-43	47256/PSDTX402M4
Tank 43A	280-43A	47256/PSDTX402M4
Tank 44	280-44	47256/PSDTX402M4
Tank 45	280-45	47256/PSDTX402M4

Storage Tanks		
Tank Number	**EPN**	**NSR Permit No.**
Tank 46	280-46	47256/PSDTX402M4
Tank 47	280-47	47256/PSDTX402M4
Tank 48	280-48	47256/PSDTX402M4
Tank 48A	280-48A	47256/PSDTX402M4
Tank 49	280-49	47256/PSDTX402M4
Tank 50	280-50	47256/PSDTX402M4
Tank 51	280-51	47256/PSDTX402M4
Tank 52	280-52	47256/PSDTX402M4
Tank 53	280-53	47256/PSDTX402M4
Tank 54	280-54	47256/PSDTX402M4
Tank 55	280-55	47256/PSDTX402M4
Tank 56	280-56	47256/PSDTX402M4
Tank 57	280-57	47256/PSDTX402M4
Tank 59	280-59	47256/PSDTX402M4
Tank 60	280-60	47256/PSDTX402M4
Tank 60A	280-60A	47256/PSDTX402M4
Tank 61	280-61	47256/PSDTX402M4
Tank 63	280-63	47256/PSDTX402M4
Tank 64	280-64	47256/PSDTX402M4
Tank 65	280-65	47256/PSDTX402M4
Tank 66	280-66	47256/PSDTX402M4
Tank 67	280-67	47256/PSDTX402M4
Tank 71	280-71	47256/PSDTX402M4
Tank 72	280-72	47256/PSDTX402M4
Tank 73	280-73	47256/PSDTX402M4
Tank 73A	280-73A	47256/PSDTX402M4
Tank 80	280-80	47256/PSDTX402M4
Tank 90	280-90	47256/PSDTX402M4
Tank 91	280-91	47256/PSDTX402M4
Tank 92	280-92	47256/PSDTX402M4
Tank 93	280-93	47256/PSDTX402M4
Tank 94	280-94	47256/PSDTX402M4
Tank 95	280-95	47256/PSDTX402M4
Tank 97	280-97	47256/PSDTX402M4
Tank 98	280-98	47256/PSDTX402M4
Tank 100	280-100	47256/PSDTX402M4

Storage Tanks		
Tank Number	**EPN**	**NSR Permit No.**
Tank 101	280-101	2231
Tank 102	280-102	2231
Tank 103	280-103	47256/PSDTX402M4
Tank 103A	280-103A	47256/PSDTX402M4
Tank 104	280-104	47256/PSDTX402M4
Tank 105	280-105	47256/PSDTX402M4
Tank 106	280-106	47256/PSDTX402M4
Tank 107	280-107	2231
Tank 108A	280-108A	2231
Tank 110	280-110	47256/PSDTX402M4
Tank 111	280-111	2231
Tank 112	280-112	2231
Tank 113	280-113	2231
Tank 114	280-114	2231
Tank 115	280-115	2231
Tank 116	280-116	2231
Tank 117	280-117	47256/PSDTX402M4
Tank 117A	280-117A	47256/PSDTX402M4
Tank 118	280-118	47256/PSDTX402M4
Tank 127	280-127	47256/PSDTX402M4
Tank 128	280-128	47256/PSDTX402M4
Tank 129	280-129	47256/PSDTX402M4
Tank 130	280-130	47256/PSDTX402M4
Tank 131	280-131	47256/PSDTX402M4
Tank 140	280-140	47256/PSDTX402M4
Tank 181	280-181	47256/PSDTX402M4
Tank 183	280-183	2231
Tank 184	280-184	2231
Tank 185	280-185	2231
Tank 186	280-186	2231
Tank 187	280-187	2231
Tank 188	280-188	2231
Tank 269	280-269	47256/PSDTX402M4
Tank 269A	280-269A	47256/PSDTX402M4
Tank 270	280-270	47256/PSDTX402M4
Tank 295	280-295	47256/PSDTX402M4

Storage Tanks		
Tank Number	**EPN**	**NSR Permit No.**
Tank 296	280-296	47256/PSDTX402M4
Tank 297	280-297	47256/PSDTX402M4
Tank 298	280-298	47256/PSDTX402M4
Tank 501	280-501	47256/PSDTX402M4
Tank 502	280-502	47256/PSDTX402M4
Tank 503	280-503	47256/PSDTX402M4
Tank 504	280-504	47256/PSDTX402M4
Tank 520	280-520	2231
Tank 528	280-528	47256/PSDTX402M4
Tank 529	280-529	47256/PSDTX402M4
Tank 530	280-530	47256/PSDTX402M4
Tank 531	280-531	47256/PSDTX402M4
Tank 532	280-532	2231
Tank 533	280-533	2231
Tank 534	280-534	2231
Tank 535	280-535	2231
Tank 536	280-536	47256/PSDTX402M4
Tank 537	280-537	1940
Tank 538	280-538	2231
Tank 560	280-560	47256/PSDTX402M4
Tank 561	280-561	47256/PSDTX402M4
Tank 608-F	108-608	2231
Tank 609-F	108-609	2231
Tank 652	280-652	47256/PSDTX402M4
Tank 653	280-653	47256/PSDTX402M4
Tank 1004	280-1004	47256/PSDTX402M4
Tank 1004A	280-1004A	47256/PSDTX402M4
Tank 1005 **(11/18)**	280-1005	47256/PSDTX402M4
Tank 1011	76	6592
Tank 1012	480-1012	47256/PSDTX402M4
Tank 1013	480-1013	47256/PSDTX402M4
Tank 1018	280-1018	47256/PSDTX402M4
Tank 1020	280-1020	47256/PSDTX402M4
Tank 1021	280-1021	47256/PSDTX402M4
Tank 1023	280-1023	47256/PSDTX402M4
Tank 1024	280-1024	47256/PSDTX402M4

Storage Tanks		
Tank Number	**EPN**	**NSR Permit No.**
Tank 1025	280-1025	47256/PSDTX402M4
Tank 1039	280-1039	47256/PSDTX402M4
Tank 1041	280-1041	2231
Tank 1042	280-1042	2231
Tank 1044	280-1044	2231
Tank 1045	280-1045	47256/PSDTX402M4
Tank 1046	280-1046	47256/PSDTX402M4
Tank 1047	280-1047	47256/PSDTX402M4
Tank 1048	280-1048	47256/PSDTX402M4
Tank 1051	280-1051	47256/PSDTX402M4
Tank 1052	280-1052	4714
Tank 1053	280-1053	4714
Tank 1055	280-1055	47256/PSDTX402M4
Tank 3010	280-3010	47256/PSDTX402M4
Tank 4000	280-4000	47256/PSDTX402M4
Tank 4011	280-4011	47256/PSDTX402M4
Tank 4016	280-4016	47256/PSDTX402M4

Date: November 30, 2018

Attachment E

Flexible Permit Numbers 47256 and PSDTX402M4

Emission Points included in Normal Operation Emission Caps

This table indicates the emission caps which normal operations emissions from an emission point are included in.

EPN	Source Name	Emissions from emission point included in normal operations emission caps for:							
		VOC	NO_x	CO	SO_2	H_2S	PM_{10}	Benzene	NH_3
33	FCCU 3 404B Heater	X	X	X	X		X		
34A	FCCU No. 3 (1)	X	X	X	X		X		
61	FCCU 2 BA201 Heater	X	X	X	X		X		
78	Coker Feed Preheater B302	X	X	X	X		X		
161	301-B Reheat Heaters (2)	X	X	X	X		X		
162	302-B Reheat Heaters (2)	X	X	X	X		X		
167	UU3 306-B Preheat Heater (2)	X	X	X	X		X		
168	307-A/B Desulfurizer Heater	X	X	X	X		X		
169	UU3 308-B Process Heater	X	X	X	X		X		
201	ULC 100B Heater	X	X	X	X		X		
202	ULC 101B Heater	X	X	X	X		X		
203	ULC 102B Heater (2)	X	X	X	X		X		
204	ULC 103B Heater	X	X	X	X		X		
205	ULC 104BA Heater (2)	X	X	X	X		X		
205	ULC 104BB Heater (2)	X	X	X	X		X		
206	ULC 105BA Heater	X	X	X	X		X		
206	ULC 105BB Heater	X	X	X	X		X		
280-4	Tank 4	X						X	
280-5	Tank 5	X						X	
280-11	Tank 11	X						X	
280-13	Tank 13	X						X	
280-13A	Tank 13A	X						X	
280-14	Tank 14	X						X	
280-14A	Tank 14A	X						X	

EPN	Source Name	Emissions from emission point included in normal operations emission caps for:							
		VOC	NO_x	CO	SO_2	H_2S	PM_{10}	Benzene	NH_3
280-16A	Tank 16A	X						X	
280-17	Tank 17	X						X	
280-18	Tank 18	X						X	
280-22	Tank 22	X						X	
280-23	Tank 23	X						X	
280-24	Tank 24	X						X	
280-25	Tank 25	X						X	
280-26	Tank 26	X						X	
280-27	Tank 27	X						X	
280-31	Tank 31	X						X	
280-32	Tank 32	X						X	
280-34	Tank 34	X						X	
280-37	Tank 37	X						X	
280-38	Tank 38	X						X	
280-41	Tank 41	X						X	
280-42	Tank 42	X						X	
280-43	Tank 43	X						X	
280-43A	Tank 43A	X						X	
280-44	Tank 44	X						X	
280-45	Tank 45	X						X	
280-46	Tank 46	X						X	
280-47	Tank 47	X						X	
280-48	Tank 48	X						X	
280-48A	Tank 48A	X						X	
280-49	Tank 49	X						X	
280-50	Tank 50	X						X	
280-51	Tank 51	X						X	
280-52	Tank 52	X						X	
280-53	Tank 53	X						X	
280-54	Tank 54	X						X	
280-55	Tank 55	X						X	
280-56	Tank 56	X						X	

EPN	Source Name	Emissions from emission point included in normal operations emission caps for:							
		VOC	NO_x	CO	SO_2	H_2S	PM_{10}	Benzene	NH_3
280-57	Tank 57	X						X	
280-59	Tank 59	X						X	
280-60	Tank 60	X						X	
280-60A	Tank 60A	X						X	
280-61	Tank 61	X						X	
280-63	Tank 63	X						X	
280-64	Tank 64	X						X	
280-65	Tank 65	X						X	
280-66	Tank 66	X						X	
280-67	Tank 67	X						X	
280-71	Tank 71	X						X	
280-72	Tank 72	X						X	
280-73	Tank 73	X						X	
280-73A	Tank 73A	X						X	
280-80	Tank 80	X						X	
280-90	Tank 90	X						X	
280-91	Tank 91	X						X	
280-92	Tank 92	X						X	
280-93	Tank 93	X						X	
280-94	Tank 94	X						X	
280-95	Tank 95	X						X	
280-97	Tank 97	X						X	
280-98	Tank 98	X						X	
280-100	Tank 100	X				X			X
280-103	Tank 103	X						X	
280-103A	Tank 103A	X						X	
280-104	Tank 104	X						X	
280-105	Tank 105	X						X	
280-106	Tank 106	X						X	
280-110	Tank 110	X						X	
280-117	Tank 117	X						X	
280-117A	Tank 117A	X						X	

EPN	Source Name	Emissions from emission point included in normal operations emission caps for:							
		VOC	NO_x	CO	SO_2	H_2S	PM_{10}	Benzene	NH_3
280-118	Tank 118	X						X	
280-127	Tank 127	X						X	
280-128	Tank 128	X						X	
280-129	Tank 129	X						X	
280-130	Tank 130	X						X	
280-131	Tank 131	X						X	
280-140	Tank 140	X						X	
280-181	Tank 181	X						X	
280-269	Tank 269	X						X	
280-269A	Tank 269A	X						X	
280-270	Tank 270	X						X	
280-295	Tank 295	X						X	
280-296	Tank 296	X						X	
280-297	Tank 297	X						X	
280-298	Tank 298	X						X	
280-501	Tank 501	X						X	
280-502	Tank 502	X						X	
280-503	Tank 503	X						X	
280-504	Tank 504	X						X	
280-528	Tank 528	X						X	
280-529	Tank 529	X						X	
280-530	Tank 530	X						X	
280-531	Tank 531	X						X	
280-536	Tank 536	X						X	
280-560	Tank 560	X						X	
280-561	Tank 561	X						X	
280-652	Tank 652	X						X	
280-653	Tank 653	X						X	
280-1004	Tank 1004	X						X	
280-1004A	Tank 1004A	X						X	
280-1018	Tank 1018	X						X	
280-1020	Tank 1020	X						X	

EPN	Source Name	Emissions from emission point included in normal operations emission caps for:							
		VOC	NO_x	CO	SO_2	H_2S	PM_{10}	Benzene	NH_3
280-1021	Tank 1021	X						X	
280-1023	Tank 1023	X						X	X
280-1024	Tank 1024	X						X	
280-1025	Tank 1025	X						X	
280-1039	Tank 1039	X						X	
280-1045	Tank 1045	X						X	
280-1046	Tank 1046	X						X	
280-1047	Tank 1047	X						X	
280-1048	Tank 1048	X						X	
280-1051	Tank 1051	X						X	X
280-1055	Tank 1055	X						X	
280-3010	Tank 3010	X						X	
280-4000	Tank 4000	X						X	
280-4011	Tank 4011	X						X	
280-4016	Tank 4016	X						X	
294-1	Thermal Oxidizer (Vapor Combustor)	X	X	X	X			X	
294-2	Thermal Oxidizer (Vapor Combustor)	X	X	X	X			X	
294-3	Thermal Oxidizer (Vapor Combustor)	X	X	X	X			X	
299-32	Marine Dock	X						X	
299-33	Marine Docks	X						X	
299-34	Marine Docks	X						X	
299-37	Marine Docks	X						X	
299-38	Marine Docks	X						X	
311	Refinery Flare No. 2	X	X	X	X	X		X	X
321	Refinery Flare No. 3	X	X	X	X	X		X	X
331	Refinery Flare No. 4	X	X	X	X	X		X	X
351A	ULC Flare	X	X	X	X	X		X	X
381	SRU A/B Flare	X	X	X	X	X		X	X
383	SRU C/D Flare	X	X	X	X	X		X	X
384	SRU Incinerator C and D	X	X	X	X		X		

EPN	Source Name	Emissions from emission point included in normal operations emission caps for:							
		VOC	NO_x	CO	SO_2	H_2S	PM_{10}	Benzene	NH_3
391	DDU B-101/102 Heaters	X	X	X	X		X		
392	DDU B-201/202 Heaters	X	X	X	X		X		
394	DDU B-301 Heater	X	X	X	X		X		
395	DDU B-302 Reboiler	X	X	X	X		X		
396A	DDU Flare	X	X	X	X	X		X	X
400	Flare 8	X	X	X	X	X		X	X
411	Alky 2 Cooling Tower	X					X		
412	Coker Cooling Tower	X					X		
413	FCCU 1 Cooling Tower	X					X		
415	FCCU 3 Cooling Tower	X					X		
416	Power 3 Cooling Tower	X					X		
418	ULC Cooling Tower	X					X		
421	UU3 Cooling Tower	X					X		
426	CFHU Cooling Tower	X					X		
453	Oil/Water Separator	X						X	
454	Oil/Water Separator	X						X	
471	CFHU Heaters 101-B and 102-B	X	X	X	X		X		
480-1012	Tank 1012	X						X	
480-1013	Tank 1013	X						X	
481	RHU Heaters Train 200	X	X	X	X		X		
482	RHU Heaters Train 300	X	X	X	X		X		
483	RHU Heaters Train 400	X	X	X	X		X		
484	RHU Fractionation Heaters	X	X	X	X		X		
485	RHU VRS Hot Oil Heater	X	X	X	X		X		
501	CFHU Flare 1	X	X	X	X	X		X	X
550	RDU Heater	X	X	X	X		X		
E-02/03	FCCU1 Waste Water Vent 3	X						X	
E-06	Oil/Water Separator - FCCU 3 Unit	X						X	

EPN	Source Name	Emissions from emission point included in normal operations emission caps for:							
		VOC	NO_x	CO	SO_2	H_2S	PM_{10}	Benzene	NH_3
E-08	Oil/Water Separator - FCCU 2 Unit	X						X	
E-13	Oil/Water Separator - FCCU 3 Unit	X						X	
E-14	Oil/Water Separator - Pipe Stills Unit	X						X	
E-16	Oil/Water Separator - Pipe Stills Unit	X						X	
E-34	Oil/Water Separator - RDU Unit	X						X	
E-35	Oil/Water Separator - CFHU Unit	X						X	
E-48	Oil/Water Separator - RHU Unit	X						X	
E-63	Oil/Water Separator - RHU Unit	X						X	
E-68	Lab Wastewater Collection Sump	X						X	
E-69	Environmental Facilities Sump	X						X	
E-98	Exchanger Pad Dry Weather Sump #30	X						X	
E-99	Dry Weather Sump #33	X						X	
F-8	Activated Sludge Unit No. 1	X						X	X
F-9	Activated Sludge Unit No. 2	X						X	X
F-11	Final Clarifier Tank No. 2	X						X	X
F-22	Clarifier Effluent Tank	X						X	X
F-30	FCCU 3 Fugitives (4)	X							
F-30	Final Effluent Tank	X						X	X
F-60	FCCU 2 Fugitives (3)	X							
F-90	FCCU1 Fugitives (3)	X							
F-160	UU3 Fugitives (3)	X							X
F-200	Ultracracker Fugitives (3)	X							

EPN	Source Name	Emissions from emission point included in normal operations emission caps for:							
		VOC	NO_x	CO	SO_2	H_2S	PM_{10}	Benzene	NH_3
F-270	API Separator No. 3A	X						X	
F-280	Tank Farm Fugitives (3)	X							
F-294	Marine Loading Fugitives (3)	X							
F-390	DDU 100/200 Fugitives (3)	X							
F-393	DDU 300 Fugitives (3)	X							
F-470	CFHU Fugitives (3)	X							
F-480	RHU Fugitives (3)	X							
F-486	HRU Fugitives (3)	X							
FLR-SW	SRU Sour Water System Flare	X	X	X	X	X		X	X
W-01	Oil/Water Separator - UU4 Unit	X						X	
W-02	Oil/Water Separator - DDU Unit	X						X	
W-06	Oil/Water Separator - ULC/ARU Unit	X						X	
W-07	Oil/Water Separator - ULC Unit	X						X	
W-12	Oil/Water Separator - UU3 Unit	X						X	
W-13	Oil/Water Separator - UU3 Unit	X						X	

X Emissions from this EPN are included in both the initial and final emission cap.

(1) Facility does not participate in normal operation annual cap for VOC, PM_{10}, or CO. The facility does participate in the normal operation short-term cap (lb/hr) and the MSS cap for all air contaminants.

(2) Facility does not participate in normal operation annual cap for VOC, NO_x, CO, SO_2, or PM_{10}. The facility does participate in the normal operation short-term cap (lb/hr) and the MSS cap for all air contaminants.

(3) Facility emissions contribution associated with this EPN are from process drains only. Piping Equipment emissions are authorized under fugitive EPN F-PLANTFUG.

(4) Facility emissions contribution associated with this EPN are from process drains only. Piping Equipment emissions are authorized under fugitive EPNs F-PLANTFUG and F-30.

Date: May 8, 2018

Attachment F

RDU Revamp Project - Technical Basis Table

Facilities	Facilities	Facilities	Facilities	Limits (1)	Monitoring/Sampling and Recordkeeping (2)(3)
Gas Oil Tanks	280-4000, 280-4001, 280-4002, and 280-4003	TANKCAP	1. Gas oil sent to storage based on the volume of combined DAO and LVGO production from the RDU to Cat Feed Hydrotreating Unit (CFHU), RHU, or FCCU3 with the representation that FCCU3 is operating at capacity.	1. Combined production of DAO and LVGO to CFHU/FCCU3/RHU from the RDU will not exceed 18,000 bbls/day.	1. Combined DA0 and LVGO production from the RDU.
Uncontrolled Marine Loading	docks 299-32, 299-33, 299-34-299-37, and 299-38	MARINE1	Increased gas oil loading (18,000 bbls/day) due to supplemental DAO and LVGO production to CFHU/FCCU3/RHU from the RDU with the representation that FCCU3 is operating at capacity.	Combined production of DAO and LVGO to CFHU/FCCU3/RHU from the RDU will not exceed 18,000 bbls/day (gas oil).	Combined DAO and LVGO production from the RDU.
Coker Heaters	COKR-B201, COKR-B301, COKR-B302	72, 74, and 78	Increased Asphaltene feed to the Coker complex with the representation that the Coker complex is operating at capacity	Total feed rate of asphaltenes (from the RDU) to the Coker complex will not exceed 10,000 bbl/day.	1. Total feed rate of asphaltenes (from the RDU) and backwash from the DCU filtration unit to the Coker complex. 2. Records of all sampling for solids upstream and downstream of DCO Filter. 3. Sampling Date

Facilities	Facilities	Facilities	Facilities	Limits (1)	Monitoring/Sampling and Recordkeeping (2)(3)
FCCU3	FCCU3	34A	1. Combined production of DAO and LVGO to CFHU/FCCU3/RHU from the RDU. 2. Solids backwashed from the DCO filtration unit to FCCU3.	1. Combined production of DAO and LVGO to CFHU/FCCU3/RHU from the RDU will not exceed 18,000 bbls/day. 2. Solids backwashed from the DCO filtration unit to FCCU3 will not exceed 3,420 lb/day.	1. Combined production rate of DAO and LVGO from the RDU. 2. Solids content of DCO upstream and downstream of the DCO filtration unit (monthly). 3. Sampling date 4. Flow rate of DCO feed to the DCO filtration unit.
SRU	SRU C & D	384	1. Increased resid feed to the RDU. 2. Increased sulfur removed at the SRU	1. Total sulfur in the resid feed to the RDU will not exceed 127.4 LTPD.	1. Total resid feed to the RDU. 2. Sulfur content and density of the resid feed to the RDU, as determined by sampling (monthly) 3. Date of sampling 4. Sulfur produced
Coke Handling System	YARD-FUG	75	1. Increased asphaltene feed to the Coker complex from the RDU.	1. Total feed rate of asphaltenes (from the RDU) to the Coker complex will not exceed 10,000 bbl/day.	1. Total feed rate of asphaltenes (from the RDU) to the Coker complex.

1. All limits are based on a 12-month rolling average, unless otherwise specified.
2. Monitoring must be performed on a continuous basis, unless otherwise specified.
3. All records must be kept for a period of 5 years.

Date: November 30, 2018

Emission Sources – Emission Caps and Individual Emission Limits

Flexible Permit Numbers 47256, N258, and PSDTX402M4

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities, sources, and related activities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

Air Contaminants Data

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
Normal Operations				
See Attachment E	See Attachment E	VOC	1429.67	1475.87
		NO_x	617.98	1495.19
		CO	1057.41	2264.19
		SO_2	1240.69	4073.98
		H_2S	1.87	2.11
		PM_{10}	142.60	155.79
		Benzene (5)	29.87	66.09
		NH_3	8.45	22.95
Planned Maintenance, Startup, and Shutdown Activities				
See Attachments A-D	See Attachments A-D	VOC	2433.78	172.50
		NO_x	157.86	24.36
		CO	790.56	136.31
		SO_2	8419.88	842.16
		H_2S	89.57	9.31
		Benzene (5)	33.12	2.05
		NH_3	18.40	1.86

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
Planned Turnaround Maintenance, Startup, and Shutdown Activities				
See Attachments A-D	See Attachments A-D	VOC (6)	3133.28	91.70
		NO_x (6)	325.87	10.56
		CO (6)	3627.58	75.48
		SO_2 (6)	8089.14	20.68
		H_2S (6)	87.70	0.32
		PM_{10} (6)	123.64	1.04
		Benzene (5) (6)	28.05	0.23
Individual Emission Limits				
34A	FCCU No. 3 (13)	VOC	(9)	33.98
		$PM_{10}/PM_{2.5}$	(9)	299.67
		CO	(9)	499.23
		H_2SO_4 (7)	31.68	108.20
		O_3	10.00	25.00
		HCN	28.07	84.06
203	ULC-102B Heater	VOC	(9)	1.60
		NO_x	(9)	28.36
		CO	(9)	21.65
		SO_2 (11)	(9)	7.91
		PM_{10}	(9)	2.21
		$PM_{2.5}$	(9)	2.21
205	ULC-104BA/BB Heaters	VOC	(9)	5.16
		NO_x	(9)	115.52
		CO	(9)	69.79
		SO_2 (11)	(9)	25.37
		PM_{10}	(9)	7.14
		$PM_{2.5}$	(9)	7.14

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
280-118	Tank 118	VOC	0.48	1.26
		Benzene	0.13	0.07
F-30	FCCU3 2016 TAR Fugitives (14)	VOC	0.04	0.16
		H_2S	<0.01	<0.01
F-PLANTFUG	Piping Equipment Fugitives for Fugitive EPNs 551, F-490, F-491, F470, F-390, F-393, F-60, F-30, F486, 195-F, F-294, 551, F-480, F-380, F-280, F-200, F-160, and F-400 (8) (14)	VOC	74.22	325.06
		Benzene (5)	3.02	13.23
		H_2S	2.32	10.18
		NH_3	0.09	0.42
161	UU3 301-B Reheater (10)	VOC	(9)	11.93
		NO_x	(9)	376.02
		CO	(9)	88.48
		SO_2	(9)	88.55
		PM_{10} / $PM_{2.5}$	(9)	16.48
162		VOC	(9)	7.01

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
	UU3 302-B Reheater (10)	NO_x	(9)	91.06
		CO	(9)	48.81
		SO_2	(9)	52.08
		PM_{10} / $PM_{2.5}$	(9)	9.69
167	UU3 306-B Hot Oil Heater (10)	VOC	(9)	8.27
		NO_x	(9)	122.64
		CO	(9)	28.21
		SO_2	(9)	61.37
		PM_{10} / $PM_{2.5}$	(9)	11.42
161A	UU3-311B, UU3-312B, and UU3-310B (10)	VOC	2.14	9.37
		NO_x	10.70	51.66
		NO_x - MSS	106.96	
		CO	77.79	49.24
		CO - MSS	311.17	
		SO_2 (11)	29.69	130.04
		PM_{10} / $PM_{2.5}$	7.97	34.91
		NH_3	4.72	20.69
164A	UU3 313-B Flue Gas Heater	VOC	0.12	0.52

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
		NO_x	1.76	7.73
		CO	3.62	8.56
		CO - MSS	14.44	
		SO_2 (11)	1.29	5.66
		$PM_{10}/PM_{2.5}$	0.37	1.61
165A	UU3 309-B Hot Oil Heater	VOC	0.84	3.2
		NO_x	4.2	17.17
		NO_x - MSS	41.96	
		CO	31	64.59
		CO - MSS	124.05	
		SO_2 (11)	11.07	42.24
		$PM_{10}/PM_{2.5}$	3.15	12.01
		NH_3	1.88	4.66
280-12A	Tank 12A	VOC	1.21	2.10
299-40,41	Docks 40 and 41	VOC	17.69	3.75

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
D-07	Dock 40/41 Sumps	VOC	0.01	0.02
41	PS3B-401BA	VOC	0.40	1.50
		NO_x	37.00	135.00
		CO	11.60	42.30
		SO_2	7.80	28.40
		PM_{10}	1.50	5.30
		$PM_{2.5}$	1.50	5.30
42	PS3B-401BB	VOC	0.40	1.50
		NO_x	37.00	135.00
		CO	11.60	42.30
		SO_2	7.80	28.40
		PM_{10}	1.50	5.30
		$PM_{2.5}$	1.50	5.30
43A	PS3B Heaters 402BE, 402 BF, and 402BG	VOC	1.91	8.20
		NO_x	32.56	87.86
		CO	26.74	114.12
		SO_2	11.08	46.79
		PM_{10}	3.77	16.87
		$PM_{2.5}$	3.77	16.87
44	PS3B Heater 401BC	VOC	1.73	6.14
		NO_x	11.20	39.86
		CO	23.68	84.27
		SO_2	8.11	34.10
		PM_{10}	2.38	8.49
		$PM_{2.5}$	2.38	8.49

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
F-RAH-PLTFUG	Fugitives for EPNs F-390-RAH, F-470-RAH, F-393-RAH, F-480-RAH, F-280-RAH, F-50-RAH, F56-RAH, F54-RAH, TDOCK-RAH, F-380-RAH. F-489-RAH, F48-RAH, F-40-RAH, F-70-RAH (14)	VOC	6.02	26.37
		NH_3	<0.01	<0.01
		H_2S	0.05	0.21
F-DHT	DHT Fugitive Components (14)	VOC	0.74	3.25
		NH_3	0.02	0.10
		H_2S	0.03	0.15
DHT-101B	DHT Stripper Reboiler	VOC	0.24	1.05
		NO_x	0.80	4.30
		NO_x - MSS	3.20	
		CO	5.91	12.38
		CO - MSS	23.64	
		SO_2	6.89	13.28
		PM_{10}	1.31	3.98
		$PM_{2.5}$	1.31	3.98
		NH_3	0.31	1.35
DHT-201B	DHT Reactor Charge Heater	VOC	0.35	1.51
		NO_x	1.15	6.76
		NO_x - MSS	6.90	
		CO	8.50	17.80
		CO - MSS	33.99	
		SO_2	9.91	19.09
		PM_{10}	1.88	5.72
		$PM_{2.5}$	1.88	5.72
		NH_3	0.44	1.93
280-1005	Tank 1005 (DHT Feed Tank)	VOC	0.57	0.28

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
CT-SRU	SRU Cooling Tower	VOC	0.80	1.75
		PM	0.16	0.55
		PM_{10}	0.06	0.21
		$PM_{2.5}$	0.06	0.20
Individual Emission Limits (After Start-Up of PS3B Revamp/RHU Revamp/DHT Project)				
NOxCAP-168, 169, 392, 550, 201, 202, 204, 206, 34A (12)	Heaters UU3-307 BA/BB, UU3-308B, DDU-202B, RDU-601B, ULC-100B, ULC-101B- ULC-103B, ULC-105BA/BB, FCCU No. 3 (13)	NO_x	(9)	514.42
DOCKCAP (12)	Marine Loading Docks and Marine Loading Docks Vapor Combustors (EPNs 294-1, 2, and 3, 299-32, 33, 34, 37, 38, and 299-40 and 41)	VOC	(9)	22.87
		NO_x	(9)	33.08
		CO	(9)	40.78
		SO_2	(9)	0.87
		PM_{10}	(9)	4.11
		$PM_{2.5}$	(9)	4.11
CTCAP-411 and 426 (12)	Alky2 Cooling Tower and CFHU Cooling Tower	VOC	(9)	14.03
		PM	(9)	8.43
		PM_{10}	(9)	3.30
		$PM_{2.5}$	(9)	3.15
CAP-484 and 384 (12)	RHU Heater 501B and 502B and SRU Incinerator C&D	VOC	(9)	29.44
		NO_x	(9)	121.20
		CO	(9)	328.45
		SO_2	(9)	419.97
		PM	(9)	29.47
		PM_{10}	(9)	29.47
		$PM_{2.5}$	(9)	29.47

Emission Sources - Maximum Allowable Emission Rates

(1) Emission point identification - either specific equipment designation or emission point number from a plot plan.
(2) Specific point source names. For fugitive sources, use an area name or fugitive source name.
(3) VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1
NO_x - total oxides of nitrogen
CO - carbon monoxide
SO_2 - sulfur dioxide
H_2S - hydrogen sulfide
H_2SO_4 - sulfuric acid mist
O_3 - ozone
PM - particulate matter
PM_{10} - particulate matter (PM) equal to or less than 10 microns in diameter. Where PM is not listed, it shall be assumed that no PM greater than 10 microns is emitted.
$PM_{2.5}$ - PM equal to or less than 2.5 microns in diameter.
NH_3 - ammonia
HCN - hydrogen cyanide
(4) Compliance with annual emission limits (tons per year) is based on a 12 month rolling period.
(5) The emission rates listed for the benzene cap are included in the VOC cap.
(6) Annual emissions from planned turnaround maintenance, startup, and shutdown (MSS) activities are above and beyond the emissions from normal operations and planned MSS activities. Short-term emissions from the plant due to normal operations, planned MSS activities, and planned turnaround MSS activities should not exceed the short-term planned turnaround MSS activities emission rates.
(7) Short term H_2SO_4 emission rate is included in the short term routine PM_{10} cap. Annual H_2SO_4 emission rate is included in the individual annual PM emission rate for EPN 34A.
(8) Facility emissions associated with this EPN are from piping equipment only. Fugitive emissions from process drains are authorized under the flexible permit cap.
(9) Hourly emissions are contained within the flexible permit hourly cap.
(10) EPN 161, 162, and 167 are not authorized to emit simultaneously with EPN 161A.
(11) Interim emissions before the total sulfur reduction project are represented in Special Condition No. 83, to be completed no later than December 31, 2020.
(12) Annual emissions are a subcap of the flexible permit cap.
(13) NO_X emissions from FCCU-3 are limited per the PS3B Revamp/RHU Revamp/DHT Project NO_X cap.
(14) Emission rate is an estimate and is enforceable through compliance with the applicable special condition(s) and permit application representations.

Date: November 30, 2018

Emission Sources - Maximum Allowable Emission Rates

Permit Number GHGPSDTX166

This table lists the maximum allowable emission rates of greenhouse gas (GHG) emissions, as defined in Title 30 Texas Administrative Code § 101.1, for all sources of GHG air contaminants on the applicant's property that are authorized by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities, sources, and related activities. Any proposed increase in emission rates may require an application for a modification of the facilities authorized by this permit.

Air Contaminants Data

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates
			TPY (4)
F-RAH-PLTFUG	Fugitives for EPNs F-390-RAH, F-470-RAH, F-393-RAH, F-480-RAH, F-280-RAH, F-50-RAH, F56-RAH, F54-RAH, TDOCK-RAH, F-380-RAH. F-489-RAH, F48-RAH, F-40-RAH, F-70-RAH	CH_4 (5)	1.32
		CO_2 (5)	0.02
		CO_2e	33
F-DHT	DHT Fugitive Components	CH_4 (5)	1.12
		CO_2 (5)	<0.01
		CO_2e	28
DHT-101B	DHT Stripper Reboiler	CH_4 (5)	2.45
		CO_2 (5)	45,552
		N_2O (5)	0.35
		CO_2e	45,718
DHT-201B	DHT Reactor Charge Heater	CH_4 (5)	3.53
		CO_2 (5)	65,481
		N_2O (5)	0.50
		CO_2e	65,719
EPNs 484 and 384	RHU Heater 501B and 502B and SRU Incinerator C&D	CH_4 (5)	15.45
		CO_2 (5)	626,451
		N_2O (5)	2.21
		CO_2e	627,495

Emission Sources - Maximum Allowable Emission Rates

(1) Emission point identification - either specific equipment designation or emission point number from plot plan.
(2) Specific point source name. For fugitive sources, use area name or fugitive source name.
(3) CO_2 - carbon dioxide
N_2O - nitrous oxide
CH_4 - methane
CO_2e - carbon dioxide equivalents based on the following Global Warming Potentials (GWP) found in Table A-1 of Subpart A 40 CFR Part 98 (78 FR 71904) for each pollutant: CO_2 (1), N_2O (298), CH_4(25)
(4) Compliance with annual emission limits (tons per year) is based on a 12-month rolling period. These rates include emissions from maintenance, startup, and shutdown.
(5) Emission rate is given for informational purposes only and does not constitute enforceable limit.

Date: November 30, 2018