

FEDERAL OPERATING PERMIT

A FEDERAL OPERATING PERMIT IS HEREBY ISSUED TO
Valero Refining-Texas, L.P.

AUTHORIZING THE OPERATION OF
Valero Corpus Christi Refinery West Plant
Petroleum Refineries

LOCATED AT
Nueces County, Texas
Latitude 27° 48' 54" Longitude 97° 29' 21"
Regulated Entity Number: RN100214386

This permit is issued in accordance with and subject to the Texas Clean Air Act (TCAA), Chapter 382 of the Texas Health and Safety Code and Title 30 Texas Administrative Code Chapter 122 (30 TAC Chapter 122), Federal Operating Permits. Under 30 TAC Chapter 122, this permit constitutes the permit holder's authority to operate the site and emission units listed in this permit. Operations of the site and emission units listed in this permit are subject to all additional rules or amended rules and orders of the Commission pursuant to the TCAA.

This permit does not relieve the permit holder from the responsibility of obtaining New Source Review authorization for new, modified, or existing facilities in accordance with 30 TAC Chapter 116, Control of Air Pollution by Permits for New Construction or Modification.

The site and emission units authorized by this permit shall be operated in accordance with 30 TAC Chapter 122, the general terms and conditions, special terms and conditions, and attachments contained herein.

This permit shall expire five years from the date of issuance. The renewal requirements specified in 30 TAC § 122.241 must be satisfied in order to renew the authorization to operate the site and emission units.

Permit No: 01458 Issuance Date: January 30, 2019

A handwritten signature in black ink, appearing to read "K. Keel", is written over a horizontal line.

For the Commission

Table of Contents

Section	Page
General Terms and Conditions	1
Special Terms and Conditions:	1
Emission Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting.....	1
Additional Monitoring Requirements	12
New Source Review Authorization Requirements	14
Compliance Requirements.....	14
Risk Management Plan	15
Protection of Stratospheric Ozone	15
Alternative Requirements.....	16
Permit Location	16
Permit Shield (30 TAC § 122.148)	16
Attachments	17
Applicable Requirements Summary.....	18
Additional Monitoring Requirements	252
Permit Shield	289
New Source Review Authorization References	300
Schedules	311
Alternative Requirement.....	313
Appendix A.....	327
Acronym List	328
Appendix B.....	329

General Terms and Conditions

The permit holder shall comply with all terms and conditions contained in 30 TAC § 122.143 (General Terms and Conditions), 30 TAC § 122.144 (Recordkeeping Terms and Conditions), 30 TAC § 122.145 (Reporting Terms and Conditions), and 30 TAC § 122.146 (Compliance Certification Terms and Conditions).

In accordance with 30 TAC § 122.144(1), records of required monitoring data and support information required by this permit, or any applicable requirement codified in this permit, are required to be maintained for a period of five years from the date of the monitoring report, sample, or application unless a longer data retention period is specified in an applicable requirement. The five year record retention period supersedes any less stringent retention requirement that may be specified in a condition of a permit identified in the New Source Review Authorization attachment.

If the permit holder chooses to demonstrate that this permit is no longer required, a written request to void this permit shall be submitted to the Texas Commission on Environmental Quality (TCEQ) by the Responsible Official in accordance with 30 TAC § 122.161(e). The permit holder shall comply with the permit's requirements, including compliance certification and deviation reporting, until notified by the TCEQ that this permit is voided.

The permit holder shall comply with 30 TAC Chapter 116 by obtaining a New Source Review authorization prior to new construction or modification of emission units located in the area covered by this permit.

All reports required by this permit must include in the submittal a cover letter which identifies the following information: company name, TCEQ regulated entity number, air account number (if assigned), site name, area name (if applicable), and Air Permits Division permit number(s).

Special Terms and Conditions:

Emission Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting

1. Permit holder shall comply with the following requirements:
 - A. Emission units (including groups and processes) in the Applicable Requirements Summary attachment shall meet the limitations, standards, equipment specifications, monitoring, recordkeeping, reporting, testing, and other requirements listed in the Applicable Requirements Summary attachment to assure compliance with the permit.
 - B. The textual description in the column titled "Textual Description" in the Applicable Requirements Summary attachment is not enforceable and is not deemed as a substitute for the actual regulatory language. The Textual Description is provided for information purposes only.
 - C. A citation listed on the Applicable Requirements Summary attachment, which has a notation [G] listed before it, shall include the referenced section and subsection for all commission rules, or paragraphs for all federal and state regulations and all subordinate paragraphs, subparagraphs and clauses, subclauses, and items contained within the referenced citation as applicable requirements.
 - D. When a grouped citation, notated with a [G] in the Applicable Requirements Summary, contains multiple compliance options, the permit holder must keep records of when each compliance option was used.
 - E. Emission units subject to 40 CFR Part 63, Subparts A, Y, CC, UUU, ZZZZ, DDDDD, or GGGGG as identified in the attached Applicable Requirements Summary table are

subject to 30 TAC Chapter 113, Subchapter C, § 113.100, 113.300, 113.340, 113.780, 113.1090, 113.1130, or 113.1160, respectively, which incorporates the 40 CFR Part 63 Subpart by reference.

2. The permit holder shall comply with the following sections of 30 TAC Chapter 101 (General Air Quality Rules):
 - A. Title 30 TAC § 101.1 (relating to Definitions), insofar as the terms defined in this section are used to define the terms used in other applicable requirements
 - B. Title 30 TAC § 101.3 (relating to Circumvention)
 - C. Title 30 TAC § 101.8 (relating to Sampling), if such action has been requested by the TCEQ
 - D. Title 30 TAC § 101.9 (relating to Sampling Ports), if such action has been requested by the TCEQ
 - E. Title 30 TAC § 101.10 (relating to Emissions Inventory Requirements)
 - F. Title 30 TAC § 101.201 (relating to Emission Event Reporting and Recordkeeping Requirements)
 - G. Title 30 TAC § 101.211 (relating to Scheduled Maintenance, Start-up, and Shutdown Reporting and Recordkeeping Requirements)
 - H. Title 30 TAC § 101.221 (relating to Operational Requirements)
 - I. Title 30 TAC § 101.222 (relating to Demonstrations)
 - J. Title 30 TAC § 101.223 (relating to Actions to Reduce Excessive Emissions)
3. Permit holder shall comply with the following requirements of 30 TAC Chapter 111:
 - A. Visible emissions from stationary vents with a flow rate of less than 100,000 actual cubic feet per minute and constructed after January 31, 1972 that are not listed in the Applicable Requirements Summary attachment for 30 TAC Chapter 111, Subchapter A, Division 1, shall not exceed 20% opacity averaged over a six-minute period. The permit holder shall comply with the following requirements for stationary vents at the site subject to this standard:
 - (i) Title 30 TAC § 111.111(a)(1)(B) (relating to Requirements for Specified Sources)
 - (ii) Title 30 TAC § 111.111(a)(1)(E)
 - (iii) Title 30 TAC § 111.111(a)(1)(F)(i), (ii), (iii), or (iv)
 - (iv) For emission units with vent emissions subject to 30 TAC § 111.111(a)(1)(B), complying with 30 TAC § 111.111(a)(1)(F)(ii), (iii), or (iv), and capable of producing visible emissions from, but not limited to, particulate matter, acid gases and NO_x, the permit holder shall also comply with the following periodic monitoring requirements for the purpose of annual compliance certification under 30 TAC § 122.146. These periodic monitoring requirements do not apply to vents that are not capable of producing visible emissions such as vents that emit only colorless VOCs; vents from non-fuming liquids; vents that provide passive

ventilation, such as plumbing vents; or vent emissions from any other source that does not obstruct the transmission of light. Vents, as specified in the "Applicable Requirements Summary" attachment, that are subject to the emission limitation of 30 TAC § 111.111(a)(1)(B) are not subject to the following periodic monitoring requirements:

- (1) An observation of stationary vents from emission units in operation shall be conducted at least once during each calendar quarter unless the emission unit is not operating for the entire quarter.
- (2) For stationary vents from a combustion source, if an alternative to the normally fired fuel is fired for a period greater than or equal to 24 consecutive hours, the permit holder shall conduct an observation of the stationary vent for each such period to determine if visible emissions are present. If such period is greater than 3 months, observations shall be conducted once during each quarter. Supplementing the normally fired fuel with natural gas or fuel gas to increase the net heating value to the minimum required value does not constitute creation of an alternative fuel.
- (3) Records of all observations shall be maintained.
- (4) Visible emissions observations of emission units operated during daylight hours shall be conducted no earlier than one hour after sunrise and no later than one hour before sunset. Visible emissions observations of emission units operated only at night must be made with additional lighting and the temporary installation of contrasting backgrounds. Visible emissions observations shall be made during times when the activities described in 30 TAC § 111.111(a)(1)(E) are not taking place. Visible emissions shall be determined with each stationary vent in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 mile, away from each stationary vent during the observation. For outdoor locations, the observer shall select a position where the sun is not directly in the observer's eyes. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. A certified opacity reader is not required for visible emissions observations.
- (5) Compliance Certification:
 - (a) If visible emissions are not present during the observation, the RO may certify that the source is in compliance with the applicable opacity requirement in 30 TAC § 111.111(a)(1) and (a)(1)(B).
 - (b) However, if visible emissions are present during the observation, the permit holder shall either list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(1)(F) as soon as practicable, but no later than 24 hours after observing visible emissions to determine if the source is in compliance with the opacity

requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.

- (c) Some vents may be subject to multiple visible emission or monitoring requirements. All credible data must be considered when certifying compliance with this requirement even if the observation or monitoring was performed to demonstrate compliance with a different requirement.

B. For visible emissions from a building, enclosed facility, or other structure; the permit holder shall comply with the following requirements:

- (i) Title 30 TAC § 111.111(a)(7)(A) (relating to Requirements for Specified Sources)
- (ii) Title 30 TAC § 111.111(a)(7)(B)(i) or (ii)
- (iii) For a building containing an air emission source, enclosed facility, or other structure containing or associated with an air emission source subject to 30 TAC § 111.111(a)(7)(A), complying with 30 TAC § 111.111(a)(7)(B)(i) or (ii), and capable of producing visible emissions from, but not limited to, particulate matter, acid gases and NO_x, the permit holder shall also comply with the following periodic monitoring requirements for the purpose of annual compliance certification under 30 TAC § 122.146:
 - (1) An observation of visible emissions from a building containing an air emission source, enclosed facility, or other structure containing or associated with an air emission source which is required to comply with 30 TAC § 111.111(a)(7)(A) shall be conducted at least once during each calendar quarter unless the air emission source or enclosed facility is not operating for the entire quarter.
 - (2) Records of all observations shall be maintained.
 - (3) Visible emissions observations of air emission sources or enclosed facilities operated during daylight hours shall be conducted no earlier than one hour after sunrise and no later than one hour before sunset. Visible emissions observations of air emission sources or enclosed facilities operated only at night must be made with additional lighting and the temporary installation of contrasting backgrounds. Visible emissions shall be determined with each emissions outlet in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 mile, away from each emissions outlet during the observation. For outdoor locations, the observer shall select a position where the sun is not directly in the observer's eyes. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to

condensation of water vapor. A certified opacity reader is not required for visible emissions observations.

(4) Compliance Certification:

- (a) If visible emissions are not present during the observation, the RO may certify that the source is in compliance with the applicable opacity requirement in 30 TAC § 111.111(a)(7) and (a)(7)(A)
- (b) However, if visible emissions are present during the observation, the permit holder shall either list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(7)(B) as soon as practicable, but no later than 24 hours after observing visible emissions to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.

C. For visible emissions from all other sources not specified in 30 TAC § 111.111(a)(1), (4), or (7); the permit holder shall comply with the following requirements:

- (i) Title 30 TAC § 111.111(a)(8)(A) (relating to Requirements for Specified Sources)
- (ii) Title 30 TAC § 111.111(a)(8)(B)(i) or (ii)
- (iii) For a source subject to 30 TAC § 111.111(a)(8)(A), complying with 30 TAC § 111.111(a)(8)(B)(i) or (ii), and capable of producing visible emissions from, but not limited to, particulate matter, acid gases and NO_x, the permit holder shall also comply with the following periodic monitoring requirements for the purpose of annual compliance certification under 30 TAC § 122.146:
 - (1) An observation of visible emissions from a source which is required to comply with 30 TAC § 111.111(a)(8)(A) shall be conducted at least once during each calendar quarter unless the source is not operating for the entire quarter.
 - (2) Records of all observations shall be maintained.
 - (3) Visible emissions observations of sources operated during daylight hours shall be conducted no earlier than one hour after sunrise and no later than one hour before sunset. Visible emissions observations of sources operated only at night must be made with additional lighting and the temporary installation of contrasting backgrounds. Visible emissions shall be determined with each source in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 mile, away from each source during the observation. For outdoor locations, the observer shall select a position where the sun is not directly in the observer's

eyes. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. A certified opacity reader is not required for visible emissions observations.

(4) Compliance Certification:

- (a) If visible emissions are not present during the observation, the RO may certify that the source is in compliance with the applicable opacity requirement in 30 TAC § 111.111(a)(8) and (a)(8)(A)
- (b) However, if visible emissions are present during the observation, the permit holder shall either list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(8)(B) as soon as practicable, but no later than 24 hours after observing visible emissions to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.

- D. Certification of opacity readers determining opacities under Method 9 (as outlined in 40 CFR Part 60, Appendix A) to comply with opacity monitoring requirements shall be accomplished by completing the Visible Emissions Evaluators Course, or approved agency equivalent, no more than 180 days before the opacity reading.
- E. For emission units with contributions from uncombined water, the permit holder shall comply with the requirements of 30 TAC § 111.111(b).
- F. Emission limits on nonagricultural processes, except for the steam generators specified in 30 TAC § 111.153, shall comply with the following requirements:
 - (i) Emissions of PM from any source may not exceed the allowable rates as required in 30 TAC § 111.151(a) (relating to Allowable Emissions Limits)
 - (ii) Sources with an effective stack height (h_e) less than the standard effective stack height (H_e), must reduce the allowable emission level by multiplying it by $[h_e/H_e]^2$ as required in 30 TAC § 111.151(b)
 - (iii) Effective stack height shall be calculated by the equation specified in 30 TAC § 111.151(c)
- 4. For storage vessels maintaining working pressure as specified in 30 TAC Chapter 115, Subchapter B, Division 1: "Storage of Volatile Organic Compounds," the permit holder shall comply with the requirements of 30 TAC § 115.112(b)(1).

5. Permit holder shall comply with the following 30 TAC Chapter 115, Subchapter D requirements:
 - A. Title 30 TAC § 115.312(b)(1) (relating to Control Requirements), for emissions during Process Unit Shutdown or Turnaround
6. The permit holder shall comply with the following 30 TAC Chapter 115, Subchapter F requirements (relating to Cutback Asphalt Requirements):
 - A. Title 30 TAC § 115.512(3) (relating to Control Requirements)
7. The permit holder shall comply with the following requirements for units subject to any subpart of 40 CFR Part 60, unless otherwise stated in the applicable subpart:
 - A. Title 40 CFR § 60.7 (relating to Notification and Recordkeeping)
 - B. Title 40 CFR § 60.8 (relating to Performance Tests)
 - C. Title 40 CFR § 60.11 (relating to Compliance with Standards and Maintenance Requirements)
 - D. Title 40 CFR § 60.12 (relating to Circumvention)
 - E. Title 40 CFR § 60.13 (relating to Monitoring Requirements)
 - F. Title 40 CFR § 60.14 (relating to Modification)
 - G. Title 40 CFR § 60.15 (relating to Reconstruction)
 - H. Title 40 CFR § 60.19 (relating to General Notification and Reporting Requirements)
8. For the bulk gasoline terminals specified in 40 CFR Part 60, Subpart XX, the permit holder shall comply with the following requirements:
 - A. Title 40 CFR § 60.502(e) - (f) (relating to Standard for VOC Emissions from Bulk Gasoline Terminals)
 - B. Title 40 CFR § 60.505(a) - (b), and (d) (relating to Reporting and Recordkeeping)
9. For petroleum refinery facilities subject to 40 CFR Part 60, Subpart QQQ, the permit holder shall comply with the following requirements:
 - A. Title 40 CFR § 60.692-1(a) - (c) (relating to Standards: General)
 - B. Title 40 CFR § 60.692-2(a) - (c), (e) (relating to Standards: Individual Drain Systems)
 - C. Title 40 CFR § 60.692-2(d) (relating to Standards: Individual Drain Systems)
 - D. Title 40 CFR § 60.692-6(a) - (b) (relating to Standards: Delay of Repair)
 - E. Title 40 CFR § 60.692-7(a) - (b) (relating to Standards: Delay of Compliance)
 - F. Title 40 CFR § 60.693-1(a) - (d), (e)(1) - (3) (relating to Alternative Standards for Individual Drain Systems)

- G. Title 40 CFR § 60.697(a), (b)(1) - (3) (relating to Recordkeeping Requirements), as applicable to Individual Drain Systems
 - H. Title 40 CFR § 60.697(f)(1) - (2), (g) (relating to Recordkeeping Requirements), as applicable to Individual Drain Systems
 - I. Title 40 CFR § 60.697(h) (relating to Recordkeeping Requirements), as applicable to excluded Stormwater Sewer Systems
 - J. Title 40 CFR § 60.697(i) (relating to Recordkeeping Requirements), as applicable to excluded Ancillary Equipment
 - K. Title 40 CFR § 60.697(j) (relating to Recordkeeping Requirements), as applicable to excluded Non-contact Cooling Water Systems
 - L. Title 40 CFR § 60.698(a), and (b)(1) (relating to Reporting Requirements), as applicable to Individual Drain Systems
 - M. Title 40 CFR § 60.698(c) (relating to Reporting Requirements), for water seal breaches in Drain Systems
 - N. Title 40 CFR § 60.698(e) (relating to Reporting Requirements), as applicable to Individual Drain Systems
10. The permit holder shall comply with the following requirements for units subject to any subpart of 40 CFR Part 61, unless otherwise stated in the applicable subpart:
- A. Title 40 CFR § 61.05 (relating to Prohibited Activities)
 - B. Title 40 CFR § 61.07 (relating to Application for Approval of Construction or Modification)
 - C. Title 40 CFR § 61.09 (relating to Notification of Start-up)
 - D. Title 40 CFR § 61.10 (relating to Source Reporting and Request Waiver)
 - E. Title 40 CFR § 61.12 (relating to Compliance with Standards and Maintenance Requirements)
 - F. Title 40 CFR § 61.13 (relating to Emissions Tests and Waiver of Emission Tests)
 - G. Title 40 CFR § 61.14 (relating to Monitoring Requirements)
 - H. Title 40 CFR § 61.15 (relating to Modification)
 - I. Title 40 CFR § 61.19 (relating to Circumvention)
11. For facilities where total annual benzene quantity from waste is greater than or equal to 10 megagrams per year and subject to emission standards in 40 CFR Part 61, Subpart FF, the permit holder shall comply with the following requirements:
- A. Title 40 CFR § 61.342(c)(1)(i) - (iii) (relating to Standards: General)
 - B. Title 40 CFR § 61.342(e)(1) (relating to Standards: General)
 - C. Title 40 CFR § 61.342(e)(2)(i) - (ii) (relating to Standards: General)

- D. Title 40 CFR § 61.342(f)(1), and (2) (relating to Standards: General)
 - E. Title 40 CFR § 61.342(g) (relating to Standards: General)
 - F. Title 40 CFR § 61.350(a) and (b) (relating to Standards: Delay of Repair)
 - G. Title 40 CFR § 61.355(a)(1)(iii), (a)(2), (a)(6), (b), and (c)(1) - (3) (relating to Test Methods, Procedures, and Compliance Provisions)
 - H. Title 40 CFR § 61.355(k)(1) - (6), and (7)(i) - (iv) (relating to Test Methods, Procedures, and Compliance Provisions), for calculation procedures
 - I. Title 40 CFR § 61.356(a) (relating to Recordkeeping Requirements)
 - J. Title 40 CFR § 61.356(b), and (b)(1) (relating to Recordkeeping Requirements)
 - K. Title 40 CFR § 61.356(b)(4) (relating to Recordkeeping Requirements)
 - L. Title 40 CFR § 61.356(b)(5) (relating to Recordkeeping Requirements)
 - M. Title 40 CFR § 61.356(c) (relating to Recordkeeping Requirements)
 - N. Title 40 CFR § 61.357(a), (d)(1), (d)(2) (d)(6) and (d)(8) (relating to Reporting Requirements)
 - O. Title 40 CFR § 61.357(d)(5) (relating to Reporting Requirements)
 - P. Waste generated by remediation activities at these facilities are subject to the requirements identified under 40 CFR § 61.342 for treatment and management of waste
12. For facilities with containers subject to emission standards in 40 CFR Part 61, Subpart FF, the permit holder shall comply with the following requirements:
- A. Title 40 CFR § 61.345(a)(1) - (3), (b), and (c) (relating to Standards: Containers)
 - B. Title 40 CFR § 61.355(h) (relating to Test Methods, Procedures and Compliance Provisions)
 - C. Title 40 CFR § 61.356(g) (relating to Recordkeeping Requirements)
 - D. Title 40 CFR § 61.356(h) (relating to Recordkeeping Requirements)
13. For facilities with individual drain systems subject to emission standards in 40 CFR Part 61, Subpart FF, the permit holder shall comply with the following requirements:
- A. Title 40 CFR § 61.346(a)(1)(i)(A), (B), (ii), (2), and (3) (relating to Standards: Individual Drain Systems)
 - B. Title 40 CFR § 61.346(b)(1), (2), (2)(i), (3), (4)(i) - (iv), and (5) (relating to Standards: Individual Drain Systems)
 - C. Title 40 CFR § 61.346(b)(2)(ii)(A) (relating to Standards: Individual Drain Systems), for junction boxes

- D. Title 40 CFR § 61.346(b)(2)(ii)(B) (relating to Standards: Individual Drain Systems), for junction boxes
 - E. Title 40 CFR § 61.353(a) - (c) (relating to Alternative Means of Emission Limitation)
 - F. Title 40 CFR § 61.355(h) (relating to Test Methods, Procedures and Compliance Provisions)
 - G. Title 40 CFR § 61.356(g) (relating to Recordkeeping Requirements)
 - H. Title 40 CFR § 61.356(h) (relating to Recordkeeping Requirements)
14. The permit holder shall comply with the requirements of 30 TAC Chapter 113, Subchapter C, § 113.100 for units subject to any subpart of 40 CFR Part 63, unless otherwise stated in the applicable subpart.
15. For the bulk gasoline terminals specified in 40 CFR Part 63, Subpart R, the permit holder shall comply with the following requirements (Title 30 TAC Chapter 113, Subchapter C, § 113.230 incorporated by reference):
- A. Title 40 CFR § 63.420(h), for applicability of the General Provisions of Subpart A
 - B. Title 40 CFR § 63.422(c), (c)(1) - (2) (relating to Standards: Loading Racks)
 - C. Title 40 CFR § 63.424(f) (relating to Standards: Equipment Leaks)
 - D. Title 40 CFR § 63.424(g) (relating to Standards: Equipment Leaks)
 - E. Title 40 CFR § 63.425(e) - (h) (relating to Test Methods and Procedures)
 - F. Title 40 CFR § 63.428(a) - (b), (g)(1), and (h)(2) - (3) (relating to Reporting and Recordkeeping)
 - G. Title 40 CFR § 63.428(f)(1) - (2) (relating to Reporting and Recordkeeping)
16. For the operations pertaining to the loading and unloading of marine tank vessels specified in 40 CFR Part 63, Subpart Y, the permit holder shall comply with the following requirements (Title 30 TAC Chapter 113, Subchapter C, § 113.300 incorporated by reference):
- A. Title 40 CFR § 63.560(c) (relating to Designation of Affected Source), for applicability of the General Provisions of Subpart A
 - B. Title 40 CFR § 63.563(a)(4) (relating to Compliance and Performance Testing), for vapor tightness requirements of the marine vessels
 - C. Title 40 CFR § 63.564(a)(1) and (d) (relating to Monitoring Requirements)
 - D. Title 40 CFR § 63.565(a) (relating to Test Methods and Procedures), for performance testing requirements
 - E. Title 40 CFR § 63.565(c) (relating to Test Methods and Procedures), for vapor tightness requirements of the marine vessels
 - F. Title 40 CFR § 63.566 (relating to Construction and Reconstruction)

- G. Title 40 CFR § 63.567(a) - (b) and (h) - (i) (relating to Reporting and Recordkeeping Requirements)
17. For sources subject to emission standards in 40 CFR Part 63, Subpart CC, the permit holder shall comply with the following requirements (Title 30 TAC Chapter 113, Subchapter C, § 113.340 incorporated by reference):
- A. Title 40 CFR § 63.640(l)(3) - (4) (relating to Applicability and Designation of Affected Source), for units and equipment added to an existing source
 - B. Title 40 CFR § 63.640(m)(1) - (2) (relating to Applicability and Designation of Affected Source), for units and emission points changing from Group 2 to Group 1 status
 - C. Title 40 CFR § 63.642(c) (relating to General Standards), for applicability of the General Provisions of Subpart A
 - D. Title 40 CFR § 63.642(e) (relating to General Standards), for recordkeeping
 - E. Title 40 CFR § 63.642(f) (relating to General Standards), for reporting
18. For containers using controls specified in 40 CFR Part 63, Subpart PP, the permit holder shall comply with the following requirements (Title 30 TAC Chapter 113, Subchapter C, § 113.470 incorporated by reference):
- A. Title 40 CFR § 63.922(b)(1) - (3), (c), (d), (d)(1) - (5), (e), and (f), (f)(1) - (4) (relating to Standards Container Level 1 Controls)
 - B. Title 40 CFR § 63.923(b)(1) - (3), (c), (d), (d)(1) - (5), (e), and (f), (f)(1) - (4) (relating to Standards - Container Level 2 Controls)
 - C. Title 40 CFR § 63.924(b)(1) - (2), (c)(1) - (2), and (d) (relating to Standards - Container Level 3 Controls)
 - D. Title 40 CFR § 63.925(a)(1) - (8), and (b)(1) - (3) (relating to Test Methods and Procedures)
 - E. Title 40 CFR § 63.926(a)(1) - (3) (relating to Inspection and Monitoring Requirements)
 - F. Title 40 CFR § 63.926(b) (relating to Inspection and Monitoring Requirements)
 - G. Title 40 CFR § 63.927(a)(1) - (2) (relating to Recordkeeping Requirements)
 - H. Title 40 CFR § 63.928(a) (relating to Reporting Requirements)
19. The permit holder shall comply with the requirement to prepare and implement an Operations and Maintenance plan in accordance with 40 CFR Part 63, Subpart UUU, § 63.1574(f) (Title 30 TAC Chapter 113, Subchapter C, § 113.780 incorporated by reference).
20. For the transfer of site remediation materials subject to 40 CFR Part 63, Subpart GGGGG off-site to another facility, the permit holder shall comply with the following requirements (Title 30 TAC, Subchapter C, § 113.1160 incorporated by reference):
- A. Title 40 CFR § 63.7936(a), for the transfer of site remediation materials
 - B. Title 40 CFR § 63.7936(b)(1), for transfer to a landfill or land disposal unit

- C. Title 40 CFR § 63.7936(b)(2), for transfer to a facility subject to 40 CFR Part 63, Subpart DD
 - D. Title 40 CFR § 63.7936(b)(3), (b)(3)(i) - (iv), for transfer to a facility managing the site remediation material according to the requirements of 40 CFR Part 63, Subpart GGGGG
21. The permit holder shall comply with certified registrations submitted to the TCEQ for purposes of establishing federally enforceable emission limits. A copy of the certified registration shall be maintained with the permit. Records sufficient to demonstrate compliance with the established limits shall be maintained. The certified registration and records demonstrating compliance shall be provided, on request, to representatives of the appropriate TCEQ regional office and any local air pollution control agency having jurisdiction over the site. The permit holder shall submit updated certified registrations when changes at the site require establishment of new emission limits. If changes result in emissions that do not remain below major source thresholds, the permit holder shall submit a revision application to codify the appropriate requirements in the permit.

Additional Monitoring Requirements

22. Unless otherwise specified, the permit holder shall comply with the compliance assurance monitoring requirements as specified in the attached "CAM Summary" upon issuance of the permit. In addition, the permit holder shall comply with the following:
- A. The permit holder shall comply with the terms and conditions contained in 30 TAC § 122.147 (General Terms and Conditions for Compliance Assurance Monitoring).
 - B. The permit holder shall report, consistent with the averaging time identified in the "CAM Summary," deviations as defined by the deviation limit in the "CAM Summary." Any monitoring data below a minimum limit or above a maximum limit, that is collected in accordance with the requirements specified in 40 CFR § 64.7(c), shall be reported as a deviation. Deviations shall be reported according to 30 TAC § 122.145 (Reporting Terms and Conditions).
 - C. The permit holder may elect to collect monitoring data on a more frequent basis and average the data, consistent with the averaging time or minimum frequency specified in the "CAM Summary," for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis. In no event shall data be collected and used in particular instances in order to avoid reporting deviations. All monitoring data shall be collected in accordance with the requirements specified in 40 CFR § 64.7(c).
 - D. The permit holder shall operate the monitoring, identified in the attached "CAM Summary," in accordance with the provisions of 40 CFR § 64.7.
 - E. Except for emission units using a CEMS, COMS or PEMS which meets the requirements of 40 CFR § 64.3(d)(2), the permit holder shall comply with either of the following requirements for any particulate matter capture system associated with the control device subject to CAM. If the results of the following inspections indicate that the capture system is not working properly, the permit holder shall promptly take necessary corrective action:
 - (i) Once per year the permit holder shall inspect any fan for proper operation and inspect the capture system used in compliance of CAM for cracks, holes, tears, and other defects; or

- (ii) Once per year, the permit holder shall inspect for fugitive emissions escaping from the capture system in compliance of CAM by performing a visible emissions observation for a period of at least six minutes in accordance with 40 CFR Part 60, Appendix A, Test Method 22.
- F. Except for emission units using a CEMS, COMS or PEMS which meets the requirements of 40 CFR § 64.3(d)(2), the permit holder shall comply with either of the following requirements for any capture system associated with the VOC control device subject to CAM. If the results of the following inspections indicate that the capture system is not working properly, the permit holder shall promptly take necessary corrective actions:
 - (i) Once a year the permit holder shall inspect the capture system in compliance of CAM for leaks in accordance with 40 CFR Part 60, Appendix A, Test Method 21. Leaks shall be indicated by an instrument reading greater than or equal to 500 ppm above background or as defined by the underlying applicable requirement; or
 - (ii) Once a month, the permit holder shall conduct a visual, audible, and/or olfactory inspection of the capture system in compliance of CAM to detect leaking components.
- G. Except for emission units using a CEMS, COMS or PEMS which meets the requirements of 40 CFR § 64.3(d)(2), the permit holder shall comply with either of the following requirements for any bypass of the control device subject to CAM. If the results of the following inspections or monitoring indicate bypass of the control device, the permit holder shall promptly take necessary corrective actions and report a deviation:
 - (i) Install a flow indicator that is capable of recording flow, at least once every fifteen minutes, immediately downstream of each valve that if opened would allow a vent stream to bypass the control device and be emitted, either directly or indirectly, to the atmosphere; or
 - (ii) Once a month, the permit holder shall inspect the valves checking the position of the valves and the condition of the car seals. Identify all times when the car seal has been broken and the valve position has been changed to allow a vent stream to bypass the control device and be emitted, either directly or indirectly, to the atmosphere.
- H. The permit holder shall comply with the requirements of 40 CFR § 70.6(a)(3)(ii)(A) and 30 TAC § 122.144(1)(A)-(F) for documentation of all required inspections.
- 23. The permit holder shall comply with the periodic monitoring requirements as specified in the attached "Periodic Monitoring Summary" upon issuance of the permit. Except for, as applicable, monitoring malfunctions, associated repairs, and required quality assurance or control activities (including, as applicable, calibration checks and required zero and span adjustments), the permit holder shall conduct all monitoring in continuous operation (or shall collect data at all required intervals) at all times that the pollutant-specific emissions unit is operating. The permit holder may elect to collect monitoring data on a more frequent basis and average the data, consistent with the averaging time or minimum frequency specified in the "Periodic Monitoring Summary," for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis. In no event shall data be collected and used in particular instances to avoid reporting deviations. Deviations shall be reported according to 30 TAC § 122.145 (Reporting Terms and Conditions).

New Source Review Authorization Requirements

24. Permit holder shall comply with the requirements of New Source Review authorizations issued or claimed by the permit holder for the permitted area, including permits, permits by rule, standard permits, flexible permits, special permits, permits for existing facilities including Voluntary Emissions Reduction Permits and Electric Generating Facility Permits issued under 30 TAC Chapter 116, Subchapter I, or special exemptions referenced in the New Source Review Authorization References attachment. These requirements:
 - A. Are incorporated by reference into this permit as applicable requirements
 - B. Shall be located with this operating permit
 - C. Are not eligible for a permit shield
25. The permit holder shall comply with the general requirements of 30 TAC Chapter 106, Subchapter A or the general requirements, if any, in effect at the time of the claim of any PBR.
26. The permit holder shall maintain records to demonstrate compliance with any emission limitation or standard that is specified in a permit by rule (PBR) or Standard Permit listed in the New Source Review Authorizations attachment. The records shall yield reliable data from the relevant time period that are representative of the emission unit's compliance with the PBR or Standard Permit. These records may include, but are not limited to, production capacity and throughput, hours of operation, safety data sheets (SDS), chemical composition of raw materials, speciation of air contaminant data, engineering calculations, maintenance records, fugitive data, performance tests, capture/control device efficiencies, direct pollutant monitoring (CEMS, COMS, or PEMS), or control device parametric monitoring. These records shall be made readily accessible and available as required by 30 TAC § 122.144. Any monitoring or recordkeeping data indicating noncompliance with the PBR or Standard Permit shall be considered and reported as a deviation according to 30 TAC § 122.145 (Reporting Terms and Conditions).

Compliance Requirements

27. The permit holder shall certify compliance in accordance with 30 TAC § 122.146. The permit holder shall comply with 30 TAC § 122.146 using at a minimum, but not limited to, the continuous or intermittent compliance method data from monitoring, recordkeeping, reporting, or testing required by the permit and any other credible evidence or information. The certification period may not exceed 12 months and the certification must be submitted within 30 days after the end of the period being certified.
28. The permit holder shall adhere to the provisions in the Compliance Schedule attachment of this permit and submit certified progress reports consistent with the schedule established under 30 TAC § 122.132(d)(4)(C) and including the information specified in 30 TAC § 122.142(d)(2). Those emission units listed in the Compliance Schedule attachment shall adhere with the requirements in the Compliance Schedule attachment until operating fully in compliance with the applicable requirements.
29. Use of Discrete Emission Credits to comply with the applicable requirements:
 - A. Unless otherwise prohibited, the permit holder may use discrete emission credits to comply with the following applicable requirements listed elsewhere in this permit:
 - (i) Title 30 TAC Chapter 115
 - (ii) Title 30 TAC Chapter 117

- (iii) If applicable, offsets for Title 30 TAC Chapter 116
 - (iv) Temporarily exceed state NSR permit allowables
- B. The permit holder shall comply with the following requirements in order to use the credit to comply with the applicable requirements:
- (i) The permit holder must notify the TCEQ according to 30 TAC § 101.376(d)
 - (ii) The discrete emission credits to be used must meet all the geographic, timeliness, applicable pollutant type, and availability requirements listed in 30 TAC Chapter 101, Subchapter H, Division 4
 - (iii) The executive director has approved the use of the discrete emission credits according to 30 TAC § 101.376(d)(1)(A)
 - (iv) The permit holder keeps records of the use of credits towards compliance with the applicable requirements in accordance with 30 TAC § 101.372(h) and 30 TAC Chapter 122
 - (v) Title 30 TAC § 101.375 (relating to Emission Reductions Achieved Outside the United States)

Risk Management Plan

30. For processes subject to 40 CFR Part 68 and specified in 40 CFR § 68.10, the permit holder shall comply with the requirements of the Accidental Release Prevention Provisions in 40 CFR Part 68. The permit holder shall submit to the appropriate agency either a compliance schedule for meeting the requirements of 40 CFR Part 68 by the date provided in 40 CFR § 68.10(a), or as part of the compliance certification submitted under this permit, a certification statement that the source is in compliance with all requirements of 40 CFR Part 68, including the registration and submission of a risk management plan.

Protection of Stratospheric Ozone

31. Permit holders at a site subject to Title VI of the FCAA Amendments shall meet the following requirements for protection of stratospheric ozone:
- A. Any on site servicing, maintenance, and repair on refrigeration and nonmotor vehicle air-conditioning appliances using ozone-depleting refrigerants or non-exempt substitutes shall be conducted in accordance with 40 CFR Part 82, Subpart F. Permit holders shall ensure that repairs on or refrigerant removal from refrigeration and nonmotor vehicle air-conditioning appliances using ozone-depleting refrigerants are performed only by properly certified technicians using certified equipment. Records shall be maintained as required by 40 CFR Part 82, Subpart F.
 - B. The permit holder shall comply with the following 40 CFR Part 82, Subpart E requirements for labeling products using ozone-depleting substances:
 - (i) Title 40 CFR § 82.100 (relating to Purpose)
 - (ii) Title 40 CFR § 82.102(a)(1) - (3), (b), (c) (relating to Applicability);
 - (iii) Title 40 CFR § 82.104 (relating to Definitions)

- (iv) Title 40 CFR § 82.106 - 112 (relating to Warning Statements and Labels)
 - (v) Title 40 CFR § 82.114 (relating to Labeling Containers of Controlled [ozone - depleting] Substances)
 - (vi) Title 40 CFR § 82.116 (relating to Incorporation of Products Manufactured with Controlled [ozone-depleting] Substances)
 - (vii) Title 40 CFR § 82.120 (relating to Petitions)
 - (viii) Title 40 CFR § 82.122 (relating Certification, Recordkeeping, and Notice requirements)
 - (ix) Title 40 CFR § 82.124 (relating to Prohibitions)
- C. The permit holder shall comply with 40 CFR Part 82, Subpart H related to Halon Emissions Reduction requirements as specified in 40 CFR § 82.250 - § 82.270 and the applicable Part 82 Appendices.

Alternative Requirements

32. The permit holder shall comply with the approved alternative means of control (AMOC); alternative monitoring, recordkeeping, or reporting requirements; or requirements determined to be equivalent to an otherwise applicable requirement contained in the Alternative Requirements attachment of this permit. Units complying with an approved alternative requirement have reference to the approval in the Applicable Requirements summary listing for the unit. The permit holder shall maintain the original documentation, from the EPA Administrator and TCEQ Executive Director, demonstrating the method or limitation utilized. Documentation shall be maintained and made available in accordance with 30 TAC § 122.144.

Permit Location

33. The permit holder shall maintain a copy of this permit and records related to requirements listed in this permit on site.

Permit Shield (30 TAC § 122.148)

34. A permit shield is granted for the emission units, groups, or processes specified in the attached "Permit Shield." Compliance with the conditions of the permit shall be deemed compliance with the specified potentially applicable requirements or specified potentially applicable state-only requirements listed in the attachment "Permit Shield." Permit shield provisions shall not be modified by the executive director until notification is provided to the permit holder. No later than 90 days after notification of a change in a determination made by the executive director, the permit holder shall apply for the appropriate permit revision to reflect the new determination. Provisional terms are not eligible for this permit shield. Any term or condition, under a permit shield, shall not be protected by the permit shield if it is replaced by a provisional term or condition or the basis of the term and condition changes.

Attachments

Applicable Requirements Summary

Additional Monitoring Requirements

Permit Shield

New Source Review Authorization References

Schedules

Alternative Requirement

Applicable Requirements Summary

Unit Summary	19
---------------------------	-----------

Applicable Requirements Summary	53
--	-----------

Note: A “none” entry may be noted for some emission sources in this permit’s “Applicable Requirements Summary” under the heading of “Monitoring and Testing Requirements” and/or “Recordkeeping Requirements” and/or “Reporting Requirements.” Such a notation indicates that there are no requirements for the indicated emission source as identified under the respective column heading(s) for the stated portion of the regulation when the emission source is operating under the conditions of the specified SOP Index Number. However, other relevant requirements pursuant to 30 TAC Chapter 122 including Recordkeeping Terms and Conditions (30 TAC § 122.144), Reporting Terms and Conditions (30 TAC § 122.145), and Compliance Certification Terms and Conditions (30 TAC § 122.146) continue to apply.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
02-V-12	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
02-V-12	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	63CC	40 CFR Part 63, Subpart CC	No changing attributes.
05-CT-109	INDUSTRIAL PROCESS COOLING TOWERS	N/A	63CC-c	40 CFR Part 63, Subpart CC	No changing attributes.
13-H-01A	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J	40 CFR Part 60, Subpart J	Facility Type = Fuel gas combustion device, other than a flare, that does not meet requirements in §§ 60.105(a)(4)(iv) or 60.105(b)., Monitoring Device = No instrument is in place for continuously monitoring and recording the concentration by volume of SO ₂ emissions into the atmosphere.
13-H-01A	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-low	40 CFR Part 60, Subpart J	Facility Type = Fuel gas combustion device located at a petroleum refinery, other than a flare, that meets requirements in §§ 60.105(a)(4)(iv) or 60.105(b) [inherently low in sulfur content], Low Sulfur = Fuel gas stream that is intolerant to sulfur contamination.
13-H-01A	PROCESS HEATERS/FURNACES	N/A	63DDDDD	40 CFR Part 63, Subpart DDDDD	No changing attributes.
13-H-01B	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J	40 CFR Part 60, Subpart J	Facility Type = Fuel gas combustion device, other than a flare, that does not meet requirements in §§ 60.105(a)(4)(iv) or 60.105(b)., Monitoring Device = No instrument

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					is in place for continuously monitoring and recording the concentration by volume of SO ₂ emissions into the atmosphere.
13-H-01B	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-low	40 CFR Part 60, Subpart J	Facility Type = Fuel gas combustion device located at a petroleum refinery, other than a flare, that meets requirements in §§ 60.105(a)(4)(iv) or 60.105(b) [inherently low in sulfur content], Low Sulfur = Fuel gas stream that is intolerant to sulfur contamination.
13-H-01B	PROCESS HEATERS/FURNACES	N/A	63DDDDDD	40 CFR Part 63, Subpart DDDDDD	No changing attributes.
13-H-01C	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J	40 CFR Part 60, Subpart J	Facility Type = Fuel gas combustion device, other than a flare, that does not meet requirements in §§ 60.105(a)(4)(iv) or 60.105(b)., Monitoring Device = No instrument is in place for continuously monitoring and recording the concentration by volume of SO ₂ emissions into the atmosphere.
13-H-01C	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-low	40 CFR Part 60, Subpart J	Facility Type = Fuel gas combustion device located at a petroleum refinery, other than a flare, that meets requirements in §§ 60.105(a)(4)(iv) or 60.105(b) [inherently low in sulfur content], Low Sulfur = Fuel gas stream that is intolerant to sulfur contamination.
13-H-01C	BOILERS/STEAM	N/A	63DDDDDD	40 CFR Part 63, Subpart	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	GENERATORS/STEAM GENERATING UNITS			DDDDD	
16-P-11-EN	SRIC ENGINES	N/A	60III-2	40 CFR Part 60, Subpart IIII	No changing attributes.
16-P-11-EN	SRIC ENGINES	N/A	63ZZZZ-2	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
16-P-12-EN	SRIC ENGINES	N/A	60III-2	40 CFR Part 60, Subpart IIII	No changing attributes.
16-P-12-EN	SRIC ENGINES	N/A	63ZZZZ-2	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
16-P-13-EN	SRIC ENGINES	N/A	60III-2	40 CFR Part 60, Subpart IIII	No changing attributes.
16-P-13-EN	SRIC ENGINES	N/A	63ZZZZ-2	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
16-P-14-EN	SRIC ENGINES	N/A	60III-2	40 CFR Part 60, Subpart IIII	No changing attributes.
16-P-14-EN	SRIC ENGINES	N/A	63ZZZZ-2	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
16-P-4-EN	SRIC ENGINES	N/A	63ZZZZ-1	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
16-P-7-EN	SRIC ENGINES	N/A	63ZZZZ-1	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
17-FUG	FUGITIVE EMISSION UNITS	N/A	R5322-ALL	30 TAC Chapter 115, Fugitives Pet Ref B Counties	No changing attributes.
17-FUG	FUGITIVE EMISSION UNITS	N/A	60GGGaVVa	40 CFR Part 60, Subpart GGGa	No changing attributes.
17-FUG	FUGITIVE EMISSION UNITS	N/A	63CCH-ALL	40 CFR Part 63, Subpart CC	No changing attributes.
17-H-1	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS	N/A	60Ja	40 CFR Part 60, Subpart Ja	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	SRU				
17-H-1	PROCESS HEATERS/FURNACES	N/A	63DDDDD	40 CFR Part 63, Subpart DDDDD	No changing attributes.
24-ST-01	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J	40 CFR Part 60, Subpart J	No changing attributes.
24-ST-01	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60Ja	40 CFR Part 60, Subpart Ja	No changing attributes.
24-ST-01	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	63UUU-J	40 CFR Part 63, Subpart UUU	CCU PM/Ni Monitoring Method = Alternative to COMS approved under §63.1573(f)., CCU PM/Ni Emission Limitation = CCU subject to the NSPS for PM in 40 CFR § 60.102 and not electing § 60.100(e) complying with Table 1.1 to Subpart UUU
24-ST-01	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	63UUU-Ja	40 CFR Part 63, Subpart UUU	CCU PM/Ni Monitoring Method = Monitoring approved alternative parameters under §63.1573(e)., CCU PM/Ni Emission Limitation = CCU subject to the NSPS for PM in 40 CFR § 60.102a(b)(1)(i) or 40 CFR §60.102 and electing § 60.100(e) and complying with the 1.0 g/kg (1.0 lb PM/1,000 lb) of coke burn-off in Table 1.2 to Subpart UUU
30-B-02	BOILERS/STEAM GENERATORS/STEAM	N/A	60Db	40 CFR Part 60, Subpart Db	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	GENERATING UNITS				
30-B-02	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	63DDDDD	40 CFR Part 63, Subpart DDDDD	No changing attributes.
30-B-03	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	60Db	40 CFR Part 60, Subpart Db	No changing attributes.
30-B-03	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	63DDDDD	40 CFR Part 63, Subpart DDDDD	No changing attributes.
30-B-04	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	60Db	40 CFR Part 60, Subpart Db	No changing attributes.
30-B-04	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60Ja	40 CFR Part 60, Subpart Ja	No changing attributes.
30-B-04	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	63DDDDD	40 CFR Part 63, Subpart DDDDD	No changing attributes.
30-B-05	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	60Db	40 CFR Part 60, Subpart Db	No changing attributes.
30-B-05	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60Ja-1	40 CFR Part 60, Subpart Ja	§60.107a(b) Exemption = The fuel gas combustion device is not eligible for the exemption in §60.107a(b)
30-B-05	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS	N/A	60Ja-2	40 CFR Part 60, Subpart Ja	§60.107a(b) Exemption = The fuel gas combustion device is eligible for the exemption in §60.107a(b)

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	SRU				
30-B-05	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	63DDDDD	40 CFR Part 63, Subpart DDDDD	No changing attributes.
31-H-01	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60Ja	40 CFR Part 60, Subpart Ja	No changing attributes.
31-H-01	PROCESS HEATERS/FURNACES	N/A	63DDDDD	40 CFR Part 63, Subpart DDDDD	No changing attributes.
38-H-01	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J	40 CFR Part 60, Subpart J	Facility Type = Fuel gas combustion device, other than a flare, that does not meet requirements in §§ 60.105(a)(4)(iv) or 60.105(b)., Monitoring Device = No instrument is in place for continuously monitoring and recording the concentration by volume of SO ₂ emissions into the atmosphere.
38-H-01	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-low	40 CFR Part 60, Subpart J	Facility Type = Fuel gas combustion device located at a petroleum refinery, other than a flare, that meets requirements in §§ 60.105(a)(4)(iv) or 60.105(b) [inherently low in sulfur content], Low Sulfur = Fuel gas stream that has been demonstrated to the Administrator according to § 60.105(a)(4)(iv)(D) and §60.105(b).
38-H-01	PROCESS HEATERS/FURNACES	N/A	63DDDDD	40 CFR Part 63, Subpart DDDDD	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
38-H-02	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J	40 CFR Part 60, Subpart J	Facility Type = Fuel gas combustion device, other than a flare, that does not meet requirements in §§ 60.105(a)(4)(iv) or 60.105(b)., Monitoring Device = No instrument is in place for continuously monitoring and recording the concentration by volume of SO ₂ emissions into the atmosphere.
38-H-02	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-low	40 CFR Part 60, Subpart J	Facility Type = Fuel gas combustion device located at a petroleum refinery, other than a flare, that meets requirements in §§ 60.105(a)(4)(iv) or 60.105(b) [inherently low in sulfur content], Low Sulfur = Fuel gas stream that has been demonstrated to the Administrator according to § 60.105(a)(4)(iv)(D) and §60.105(b).
38-H-02	PROCESS HEATERS/FURNACES	N/A	63DDDDD	40 CFR Part 63, Subpart DDDDD	No changing attributes.
38-V-54	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
38-V-54	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	63CC	40 CFR Part 63, Subpart CC	No changing attributes.
38-V-55	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
38-V-55	EMISSION POINTS/STATIONARY	N/A	63CC	40 CFR Part 63, Subpart CC	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	VENTS/PROCESS VENTS				
41-H-07	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J	40 CFR Part 60, Subpart J	No changing attributes.
44-V-01	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
44-V-01	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	63CCa	40 CFR Part 63, Subpart CC	No changing attributes.
46-H-01	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J	40 CFR Part 60, Subpart J	No changing attributes.
46-H-01	BOILERS/STEAM GENERATORS/STEAM GENERATING UNITS	N/A	63DDDDD	40 CFR Part 63, Subpart DDDDD	No changing attributes.
47-V-02	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
47-V-02	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	63CC	40 CFR Part 63, Subpart CC	No changing attributes.
48-H-01	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J	40 CFR Part 60, Subpart J	Monitoring Device = An instrument is in place for continuously monitoring and recording the concentration (dry basis) of hydrogen sulfide in fuel gases before being burned in any fuel gas combustion device.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
48-H-01	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-AMP	40 CFR Part 60, Subpart J	Monitoring Device = Concentrations of Total Sulfur in the Combined Feed and the temperature of the contents in the Feed Surge Drum (48-V-01) will be used as a means of monitoring the vent stream that is combusted in the NHT Charge Heater (48-H-01).
48-V-01	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
48-V-01	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	63CC	40 CFR Part 63, Subpart CC	No changing attributes.
49-H-91	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J	40 CFR Part 60, Subpart J	No changing attributes.
49-H-91	PROCESS HEATERS/FURNACES	N/A	63DDDDD	40 CFR Part 63, Subpart DDDDD	No changing attributes.
49-V-01	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
49-V-01	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	63CC	40 CFR Part 63, Subpart CC	No changing attributes.
49CRU	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	63UUU	40 CFR Part 63, Subpart UUU	No changing attributes.
52-H-01	FCCU CAT REGEN/FUEL	N/A	60J	40 CFR Part 60, Subpart J	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	GAS COMBUSTION/CLAUS SRU				
52-H-01	PROCESS HEATERS/FURNACES	N/A	63DDDDD	40 CFR Part 63, Subpart DDDDD	No changing attributes.
54F-MTBE	FUGITIVE EMISSION UNITS	N/A	R5322ALL	30 TAC Chapter 115, Fugitives Pet Ref B Counties	No changing attributes.
54F-MTBE	FUGITIVE EMISSION UNITS	N/A	60GGGALL	40 CFR Part 60, Subpart GGG	No changing attributes.
54F-MTBE	FUGITIVE EMISSION UNITS	N/A	63CCH-ALL	40 CFR Part 63, Subpart CC	No changing attributes.
54F-TAME	FUGITIVE EMISSION UNITS	N/A	R5322ALL	30 TAC Chapter 115, Fugitives Pet Ref B Counties	No changing attributes.
54F-TAME	FUGITIVE EMISSION UNITS	N/A	60GGGALL	40 CFR Part 60, Subpart GGG	No changing attributes.
54F-TAME	FUGITIVE EMISSION UNITS	N/A	63CCVVALL	40 CFR Part 63, Subpart CC	No changing attributes.
70-TK-137	STORAGE TANKS/VESSELS	N/A	R5112-b	30 TAC Chapter 115, Storage of VOCs	Product Stored = VOC other than crude oil or condensate, Storage Capacity = Capacity is greater than 40,000 gallons
70-TK-137	STORAGE TANKS/VESSELS	N/A	R5112-c	30 TAC Chapter 115, Storage of VOCs	Product Stored = Crude oil and/or condensate, Storage Capacity = Capacity is greater than 40,000 gallons
70-TK-137	STORAGE TANKS/VESSELS	N/A	60K-b	40 CFR Part 60, Subpart K	Reid Vapor Pressure = Reid vapor pressure not determined, Maximum True Vapor Pressure = Maximum true vapor pressure is not

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					determined, True Vapor Pressure = True vapor pressure is less than 1.5 psia, Product Stored = Petroleum liquid (other than petroleum or condensate)
70-TK-137	STORAGE TANKS/VESSELS	N/A	60K-c	40 CFR Part 60, Subpart K	Reid Vapor Pressure = Reid vapor pressure not determined, True Vapor Pressure = True vapor pressure is at least 1.5 psia and less than 11.1 psia, Product Stored = Petroleum liquid (other than petroleum or condensate)
70-TK-137	STORAGE TANKS/VESSELS	N/A	60K-d	40 CFR Part 60, Subpart K	Reid Vapor Pressure = Reid vapor pressure is at least 2.0 psia, True Vapor Pressure = True vapor pressure is at least 1.5 psia and less than 11.1 psia, Product Stored = Crude oil
70-TK-137	STORAGE TANKS/VESSELS	N/A	63CC	40 CFR Part 63, Subpart CC	No changing attributes.
70-TK-138	STORAGE TANKS/VESSELS	N/A	60K-b	40 CFR Part 60, Subpart K	No changing attributes.
70-TK-140	STORAGE TANKS/VESSELS	N/A	63GGGGG-1	40 CFR Part 63, Subpart GGGGG	No changing attributes.
73-TK-168	STORAGE TANKS/VESSELS	N/A	R5112-d	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
73-TK-168	STORAGE TANKS/VESSELS	N/A	60Kb-e	40 CFR Part 60, Subpart Kb	No changing attributes.
73-TK-168	STORAGE TANKS/VESSELS	N/A	63CC-c	40 CFR Part 63, Subpart CC	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
73-TK-9	STORAGE TANKS/VESSELS	N/A	60KA-b	40 CFR Part 60, Subpart Ka	No changing attributes.
73-TK-9	STORAGE TANKS/VESSELS	N/A	63CC	40 CFR Part 63, Subpart CC	No changing attributes.
83-TK-155	STORAGE TANKS/VESSELS	N/A	R5112-b	30 TAC Chapter 115, Storage of VOCs	Product Stored = VOC other than crude oil or condensate, Storage Capacity = Capacity is greater than 40,000 gallons
83-TK-155	STORAGE TANKS/VESSELS	N/A	R5112-c	30 TAC Chapter 115, Storage of VOCs	Product Stored = Crude oil and/or condensate, Storage Capacity = Capacity is greater than 40,000 gallons
83-TK-155	STORAGE TANKS/VESSELS	N/A	60KB-b	40 CFR Part 60, Subpart Kb	Product Stored = Petroleum liquid (other than petroleum or condensate)
83-TK-155	STORAGE TANKS/VESSELS	N/A	60KB-c	40 CFR Part 60, Subpart Kb	Product Stored = Volatile organic liquid
83-TK-155	STORAGE TANKS/VESSELS	N/A	60KB-d	40 CFR Part 60, Subpart Kb	Product Stored = Crude oil stored, processed, and/or treated after custody transfer, Reid Vapor Pressure = Reid vapor pressure is greater than or equal to 2.0 psia
83-TK-155	STORAGE TANKS/VESSELS	N/A	60QQQ	40 CFR Part 60, Subpart QQQ	No changing attributes.
83-TK-155	STORAGE TANKS/VESSELS	N/A	61FF	40 CFR Part 61, Subpart FF	No changing attributes.
83-TK-162	STORAGE TANKS/VESSELS	N/A	R5112-b	30 TAC Chapter 115, Storage of VOCs	Product Stored = VOC other than crude oil or condensate, Storage Capacity = Capacity is greater than 40,000 gallons

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
83-TK-162	STORAGE TANKS/VESSELS	N/A	R5112-c	30 TAC Chapter 115, Storage of VOCs	Product Stored = Crude oil and/or condensate, Storage Capacity = Capacity is greater than 40,000 gallons
83-TK-162	STORAGE TANKS/VESSELS	N/A	60KB-b	40 CFR Part 60, Subpart Kb	Product Stored = Petroleum liquid (other than petroleum or condensate)
83-TK-162	STORAGE TANKS/VESSELS	N/A	60KB-c	40 CFR Part 60, Subpart Kb	Product Stored = Volatile organic liquid
83-TK-162	STORAGE TANKS/VESSELS	N/A	60KB-d	40 CFR Part 60, Subpart Kb	Product Stored = Crude oil stored, processed, and/or treated after custody transfer, Reid Vapor Pressure = Reid vapor pressure is greater than or equal to 2.0 psia
83-TK-162	STORAGE TANKS/VESSELS	N/A	60QQQ	40 CFR Part 60, Subpart QQQ	No changing attributes.
83-TK-162	STORAGE TANKS/VESSELS	N/A	61FF	40 CFR Part 61, Subpart FF	No changing attributes.
83-TK-23	STORAGE TANKS/VESSELS	N/A	R5112-b	30 TAC Chapter 115, Storage of VOCs	Product Stored = VOC other than crude oil or condensate, Storage Capacity = Capacity is greater than 40,000 gallons
83-TK-23	STORAGE TANKS/VESSELS	N/A	R5112-c	30 TAC Chapter 115, Storage of VOCs	Product Stored = Crude oil and/or condensate, Storage Capacity = Capacity is greater than 40,000 gallons
83-TK-23	STORAGE TANKS/VESSELS	N/A	60KA-b	40 CFR Part 60, Subpart Ka	Product Stored = Petroleum liquid (other than petroleum or condensate), Reid Vapor Pressure = RVP not determined since 40 CFR § 60.115a(d)(1) exemption

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					is not utilized, Maximum True Vapor Pressure = Maximum true vapor pressure is not determined since 40 CFR § 60.115a(d)(1) exemption is not utilized, True Vapor Pressure = TVP is less than 1.5 psia
83-TK-23	STORAGE TANKS/VESSELS	N/A	60KA-c	40 CFR Part 60, Subpart Ka	Product Stored = Petroleum liquid (other than petroleum or condensate), Reid Vapor Pressure = RVP not determined since 40 CFR § 60.115a(d)(1) exemption is not utilized, True Vapor Pressure = TVP is greater than or equal to 1.5 but less than or equal to 11.1 psia
83-TK-23	STORAGE TANKS/VESSELS	N/A	60KA-d	40 CFR Part 60, Subpart Ka	Product Stored = Crude oil stored, processed, and/or treated after custody transfer, Reid Vapor Pressure = Reid vapor pressure is greater than or equal to 2.0 psia, True Vapor Pressure = TVP is greater than or equal to 1.5 but less than or equal to 11.1 psia
83-TK-23	STORAGE TANKS/VESSELS	N/A	60QQQ	40 CFR Part 60, Subpart QQQ	No changing attributes.
83-TK-25	STORAGE TANKS/VESSELS	N/A	R5112-a	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
83-TK-25	STORAGE TANKS/VESSELS	N/A	60KA-b	40 CFR Part 60, Subpart Ka	No changing attributes.
83-TK-25	STORAGE TANKS/VESSELS	N/A	61FF	40 CFR Part 61, Subpart FF	No changing attributes.
83-TK-26	STORAGE	N/A	R5112-b	30 TAC Chapter 115,	Product Stored = VOC other than

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	TANKS/VESSELS			Storage of VOCs	crude oil or condensate, Storage Capacity = Capacity is greater than 40,000 gallons
83-TK-26	STORAGE TANKS/VESSELS	N/A	R5112-c	30 TAC Chapter 115, Storage of VOCs	Product Stored = Crude oil and/or condensate, Storage Capacity = Capacity is greater than 40,000 gallons
83-TK-26	STORAGE TANKS/VESSELS	N/A	60KB-b	40 CFR Part 60, Subpart Kb	Product Stored = Petroleum liquid (other than petroleum or condensate)
83-TK-26	STORAGE TANKS/VESSELS	N/A	60KB-c	40 CFR Part 60, Subpart Kb	Product Stored = Volatile organic liquid
83-TK-26	STORAGE TANKS/VESSELS	N/A	60KB-d	40 CFR Part 60, Subpart Kb	Product Stored = Crude oil stored, processed, and/or treated after custody transfer, Reid Vapor Pressure = Reid vapor pressure is greater than or equal to 2.0 psia
83-TK-26	STORAGE TANKS/VESSELS	N/A	63CC	40 CFR Part 63, Subpart CC	Product Stored = Refined petroleum products
83-TK-26	STORAGE TANKS/VESSELS	N/A	63CC-b	40 CFR Part 63, Subpart CC	Reid Vapor Pressure = Reid vapor pressure is greater than or equal to 2.0 psia, Product Stored = Crude oil
83-V-97	STORAGE TANKS/VESSELS	N/A	R5112-b	30 TAC Chapter 115, Storage of VOCs	Product Stored = VOC other than crude oil or condensate, Storage Capacity = Capacity is greater than 40,000 gallons
83-V-97	STORAGE TANKS/VESSELS	N/A	R5112-c	30 TAC Chapter 115, Storage of VOCs	Product Stored = Crude oil and/or condensate, Storage Capacity = Capacity is greater than 40,000 gallons

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
83-V-97	STORAGE TANKS/VESSELS	N/A	60KB-b	40 CFR Part 60, Subpart Kb	Product Stored = Petroleum liquid (other than petroleum or condensate)
83-V-97	STORAGE TANKS/VESSELS	N/A	60KB-c	40 CFR Part 60, Subpart Kb	Product Stored = Volatile organic liquid
83-V-97	STORAGE TANKS/VESSELS	N/A	60KB-d	40 CFR Part 60, Subpart Kb	Product Stored = Crude oil stored, processed, and/or treated after custody transfer, Reid Vapor Pressure = Reid vapor pressure is greater than or equal to 2.0 psia
83-V-97	STORAGE TANKS/VESSELS	N/A	60QQQ	40 CFR Part 60, Subpart QQQ	No changing attributes.
83-V-97	STORAGE TANKS/VESSELS	N/A	61FF	40 CFR Part 61, Subpart FF	No changing attributes.
83-V-98	STORAGE TANKS/VESSELS	N/A	R5112-b	30 TAC Chapter 115, Storage of VOCs	Product Stored = VOC other than crude oil or condensate, Storage Capacity = Capacity is greater than 40,000 gallons
83-V-98	STORAGE TANKS/VESSELS	N/A	R5112-c	30 TAC Chapter 115, Storage of VOCs	Product Stored = Crude oil and/or condensate, Storage Capacity = Capacity is greater than 40,000 gallons
83-V-98	STORAGE TANKS/VESSELS	N/A	60KB-b	40 CFR Part 60, Subpart Kb	Product Stored = Petroleum liquid (other than petroleum or condensate), Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.5 psia but less than 0.75 psia
83-V-98	STORAGE TANKS/VESSELS	N/A	60KB-c	40 CFR Part 60, Subpart Kb	Product Stored = Petroleum liquid (other than petroleum or condensate), Maximum True Vapor

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia
83-V-98	STORAGE TANKS/VESSELS	N/A	60KB-d	40 CFR Part 60, Subpart Kb	Product Stored = Crude oil stored, processed, and/or treated after custody transfer, Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia, Reid Vapor Pressure = Reid vapor pressure is greater than or equal to 2.0 psia
83-V-98	STORAGE TANKS/VESSELS	N/A	61FF	40 CFR Part 61, Subpart FF	No changing attributes.
83-V-98	STORAGE TANKS/VESSELS	N/A	63CC	40 CFR Part 63, Subpart CC	No changing attributes.
83P136A-EN	SRIC ENGINES	N/A	60III-3	40 CFR Part 60, Subpart III	No changing attributes.
83P136A-EN	SRIC ENGINES	N/A	63ZZZZ-3	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
83P136B-EN	SRIC ENGINES	N/A	60III-3	40 CFR Part 60, Subpart III	No changing attributes.
83P136B-EN	SRIC ENGINES	N/A	63ZZZZ-3	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
APISEP	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	R5131	30 TAC Chapter 115, Water Separation	No changing attributes.
APISEP	VOLATILE ORGANIC COMPOUND WATER SEPARATORS	N/A	60QQQ	40 CFR Part 60, Subpart QQQ	No changing attributes.
APISEP	VOLATILE ORGANIC	N/A	60FF-a	40 CFR Part 61, Subpart FF	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	COMPOUND WATER SEPARATORS				
BARGEDOCKS	LOADING/UNLOADING OPERATIONS	N/A	61BB	40 CFR Part 61, Subpart BB	No changing attributes.
BARGEDOCKS	LOADING/UNLOADING OPERATIONS	N/A	63CC	40 CFR Part 63, Subpart CC	No changing attributes.
BARGEDOCKS	LOADING/UNLOADING OPERATIONS	N/A	63Ya	40 CFR Part 63, Subpart Y	Material Loaded = Material other than crude oil or gasoline., Source Emissions = Source with emissions less than 10 and 25 tons.
BARGEDOCKS	LOADING/UNLOADING OPERATIONS	N/A	63Yb	40 CFR Part 63, Subpart Y	Alternate Monitoring = Complying with the control device specific monitoring procedures in 40 CFR § 63.564., Alternate Test Procedure = Complying with the test procedures in 40 CFR § 63.565., Bypass Flow Indicator = Visual inspection of seal or closure mechanism., Vent Stream By-Pass = There are valves that could route displaced vapors to the atmosphere., Material Loaded = Gasoline., Source Emissions = Source with emissions of 10 or 25 tons., Throughput = Source with throughput of 10 M barrels or 200 M barrels., Vapor Balancing System = Emissions are not reduced by a vapor balancing system., CEMS = Continuous emissions monitoring system (CEMS) is not being used., Documenting Vapor Tightness = Electing to comply with the emissions reporting requirements in

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					40 CFR § 63.567(b)(5)(i)., Subpart Y Control Device Type = Carbon adsorber with vacuum regeneration., Performance Test = Baseline temperature from manufacturer.
BUTAMER	FUGITIVE EMISSION UNITS	N/A	60GGGALL	40 CFR Part 60, Subpart GGG	No changing attributes.
BWS	FUGITIVE EMISSION UNITS	N/A	R5322-ALL	30 TAC Chapter 115, Fugitives Pet Ref B Counties	No changing attributes.
BWS	FUGITIVE EMISSION UNITS	N/A	60GGGaVVa	40 CFR Part 60, Subpart GGGa	No changing attributes.
BWS	FUGITIVE EMISSION UNITS	N/A	63CCH-ALL	40 CFR Part 63, Subpart CC	No changing attributes.
CD-LOADING	LOADING/UNLOADING OPERATIONS	N/A	63CC	40 CFR Part 63, Subpart CC	No changing attributes.
CD-PIPING	FUGITIVE EMISSION UNITS	N/A	R5322ALL	30 TAC Chapter 115, Fugitives Pet Ref B Counties	No changing attributes.
CD-PIPING	FUGITIVE EMISSION UNITS	N/A	63CCVVALL	40 CFR Part 63, Subpart CC	No changing attributes.
DEGREASE-F	SOLVENT DEGREASING MACHINES	N/A	R5412	30 TAC Chapter 115, Degreasing Processes	No changing attributes.
FUELDRM	FUGITIVE EMISSION UNITS	N/A	R5322ALL	30 TAC Chapter 115, Fugitives Pet Ref B Counties	No changing attributes.
GDFUG	FUGITIVE EMISSION UNITS	N/A	R5322ALL	30 TAC Chapter 115, Fugitives Pet Ref B Counties	No changing attributes.
GDFUG	FUGITIVE EMISSION UNITS	N/A	60GGGALL	40 CFR Part 60, Subpart GGG	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
GDFUG	FUGITIVE EMISSION UNITS	N/A	63CCHALL	40 CFR Part 63, Subpart CC	No changing attributes.
GF-1	FLARES	N/A	R1111	30 TAC Chapter 111, Visible Emissions	No changing attributes.
GF-1	FLARES	N/A	60A	40 CFR Part 60, Subpart A	No changing attributes.
GF-1	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60Ja	40 CFR Part 60, Subpart Ja	No changing attributes.
GF-1	FLARES	N/A	63A	40 CFR Part 63, Subpart A	No changing attributes.
GRP-49HTR	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	49-H-01, 49-H-02, 49-H-03, 49-H-04	60J	40 CFR Part 60, Subpart J	Facility Type = Fuel gas combustion device, other than a flare, that does not meet requirements in §§ 60.105(a)(4)(iv) or 60.105(b)., Monitoring Device = No instrument is in place for continuously monitoring and recording the concentration by volume of SO ₂ emissions into the atmosphere.
GRP-49HTR	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	49-H-01, 49-H-02, 49-H-03, 49-H-04	60J-low	40 CFR Part 60, Subpart J	Facility Type = Fuel gas combustion device located at a petroleum refinery, other than a flare, that meets requirements in §§ 60.105(a)(4)(iv) or 60.105(b) [inherently low in sulfur content], Low Sulfur = Fuel gas stream that is intolerant to sulfur contamination.
GRP-49HTR	PROCESS HEATERS/FURNACES	49-H-01, 49-H-02, 49-H-03, 49-H-04	63DDDDDD	40 CFR Part 63, Subpart DDDDDD	No changing attributes.
GRP-5GCCVV	FUGITIVE EMISSION UNITS	11F-HOC, 49-RSU, 49-XFU, 4F, CRU-	R5322ALL	30 TAC Chapter 115, Fugitives Pet Ref B Counties	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
		FUG, CRUDE UNIT, HCU-FUG, HOC- FUG, HRLEU-FUG, LRU, NHT-FUG			
GRP-5GCCVV	FUGITIVE EMISSION UNITS	11F-HOC, 49-RSU, 49-XFU, 4F, CRU- FUG, CRUDE UNIT, HCU-FUG, HOC- FUG, HRLEU-FUG, LRU, NHT-FUG	60GGGALL	40 CFR Part 60, Subpart GGG	No changing attributes.
GRP-5GCCVV	FUGITIVE EMISSION UNITS	11F-HOC, 49-RSU, 49-XFU, 4F, CRU- FUG, CRUDE UNIT, HCU-FUG, HOC- FUG, HRLEU-FUG, LRU, NHT-FUG	63CCVVALL	40 CFR Part 63, Subpart CC	No changing attributes.
GRP-BLR-DB	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	30-B-02, 30-B-03	60J	40 CFR Part 60, Subpart J	No changing attributes.
GRP-EPN118	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	13T01, SMR-CO2- VT	R5121	30 TAC Chapter 115, Vent Gas Controls	Control Device = Condenser System
GRP-EPN118	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	13T01, SMR-CO2- VT	R5121a	30 TAC Chapter 115, Vent Gas Controls	Control Device = Process Heater
GRP-EPN121	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	2202-L, 2203-L, 24- ST-02, SCOT, SULFTEN	R1151	30 TAC Chapter 111, Nonagricultural Processes	No changing attributes.
GRP-EPN121	EMISSION POINTS/STATIONARY	2202-L, 2203-L, 24- ST-02, SCOT,	R1111	30 TAC Chapter 111, Visible Emissions	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	VENTS/PROCESS VENTS	SULFTEN			
GRP-EPN126A	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	31V05, 47L01PSA	R5121	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
GRP-EPN126A	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	31V05, 47L01PSA	63CC	40 CFR Part 63, Subpart CC	No changing attributes.
GRP-EPN126B	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	49V06, 49V07	R5121	30 TAC Chapter 115, Vent Gas Controls	Control Device Type = Smokeless flare
GRP-EPN126B	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	49V06, 49V07	R5121a	30 TAC Chapter 115, Vent Gas Controls	Control Device Type = Vapor recovery system, as defined in 30 TAC § 115.10, other than an afterburner, blast furnace combustion device, boiler, catalytic or direct flame incinerator, carbon adsorption system, chiller, flare or vapor combustor.
GRP-EPN126B	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	49V06, 49V07	63CCa	40 CFR Part 63, Subpart CC	Control Device = Flare
GRP-EPN126B	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	49V06, 49V07	63CCb	40 CFR Part 63, Subpart CC	Control Device = Boiler or process heater with a design heat input capacity of greater or equal to than 44 MW or a boiler or process heater in which all vent streams are introduced into the flame zone.
GRP-EPN135	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	01V01, 01V13, 01V16, 24V36	R5121	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
GRP-EPN135	EMISSION	01V01, 01V13,	63CCa	40 CFR Part 63, Subpart CC	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	POINTS/STATIONARY VENTS/PROCESS VENTS	01V16, 24V36			
GRP-ERLQA	STORAGE TANKS/VESSELS	83-V-58, 83-V-59	R5112-b	30 TAC Chapter 115, Storage of VOCs	Product Stored = VOC other than crude oil or condensate, Storage Capacity = Capacity is greater than 40,000 gallons
GRP-ERLQA	STORAGE TANKS/VESSELS	83-V-58, 83-V-59	R5112-c	30 TAC Chapter 115, Storage of VOCs	Product Stored = Crude oil and/or condensate, Storage Capacity = Capacity is greater than 40,000 gallons
GRP-ERLQA	STORAGE TANKS/VESSELS	83-V-58, 83-V-59	60KB-b	40 CFR Part 60, Subpart Kb	Product Stored = Petroleum liquid (other than petroleum or condensate), Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.5 psia but less than 0.75 psia
GRP-ERLQA	STORAGE TANKS/VESSELS	83-V-58, 83-V-59	60KB-c	40 CFR Part 60, Subpart Kb	Product Stored = Petroleum liquid (other than petroleum or condensate), Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia
GRP-ERLQA	STORAGE TANKS/VESSELS	83-V-58, 83-V-59	60KB-d	40 CFR Part 60, Subpart Kb	Product Stored = Crude oil stored, processed, and/or treated after custody transfer, Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia, Reid Vapor Pressure = Reid vapor pressure is greater than or equal to 2.0 psia
GRP-ERLQA	STORAGE	83-V-58, 83-V-59	61FF	40 CFR Part 61, Subpart FF	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	TANKS/VESSELS				
GRP-ERLQA	STORAGE TANKS/VESSELS	83-V-58, 83-V-59	63CC	40 CFR Part 63, Subpart CC	No changing attributes.
GRP-HTR	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	01-H-01, 01-H-02, 01-H-03, 02-H-01, 11-H-01, 12-H-01A, 12-H-01B, 12-H-02, 36-H-01, 38-H-03, 49-H-71, 49-H-90	60J	40 CFR Part 60, Subpart J	No changing attributes.
GRP-HTR	PROCESS HEATERS/FURNACES	01-H-01, 01-H-02, 01-H-03, 02-H-01, 11-H-01, 12-H-01A, 12-H-01B, 12-H-02, 36-H-01, 38-H-03, 49-H-71, 49-H-90	63DDDDD	40 CFR Part 63, Subpart DDDDD	No changing attributes.
GRP-HTRJ	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	47-H-01, 47-H-02, 47-H-03, 47-H-04	60J	40 CFR Part 60, Subpart J	Monitoring Device = An instrument is in place for continuously monitoring and recording the concentration (dry basis) of hydrogen sulfide in fuel gases before being burned in any fuel gas combustion device.
GRP-HTRJ	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	47-H-01, 47-H-02, 47-H-03, 47-H-04	60J-AMP	40 CFR Part 60, Subpart J	Monitoring Device = Concentrations of Total Sulfur in the Combined Feed and the temperature of the contents in the Feed Surge Drum (47-V-02) will be used as a means of monitoring the vent stream that is combusted in the Hydrocracker Heaters.
GRP-HTRJ	PROCESS HEATERS/FURNACES	47-H-01, 47-H-02, 47-H-03, 47-H-04,	63DDDDD	40 CFR Part 63, Subpart DDDDD	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
		48-H-01			
GRP-IRMTBQ	STORAGE TANKS/VESSELS	83-TK-159, 83-TK-160	R5112-b	30 TAC Chapter 115, Storage of VOCs	Product Stored = VOC other than crude oil or condensate, Storage Capacity = Capacity is greater than 40,000 gallons
GRP-IRMTBQ	STORAGE TANKS/VESSELS	83-TK-159, 83-TK-160	R5112-c	30 TAC Chapter 115, Storage of VOCs	Product Stored = Crude oil and/or condensate, Storage Capacity = Capacity is greater than 40,000 gallons
GRP-IRMTBQ	STORAGE TANKS/VESSELS	83-TK-159, 83-TK-160	60KB-b	40 CFR Part 60, Subpart Kb	Product Stored = Petroleum liquid (other than petroleum or condensate)
GRP-IRMTBQ	STORAGE TANKS/VESSELS	83-TK-159, 83-TK-160	60KB-c	40 CFR Part 60, Subpart Kb	Product Stored = Volatile organic liquid
GRP-IRMTBQ	STORAGE TANKS/VESSELS	83-TK-159, 83-TK-160	60KB-d	40 CFR Part 60, Subpart Kb	Product Stored = Crude oil stored, processed, and/or treated after custody transfer, Reid Vapor Pressure = Reid vapor pressure is greater than or equal to 2.0 psia
GRP-IRMTBQ	STORAGE TANKS/VESSELS	83-TK-159, 83-TK-160	61FF	40 CFR Part 61, Subpart FF	No changing attributes.
GRP-IRMTBQ	STORAGE TANKS/VESSELS	83-TK-159, 83-TK-160	63CC	40 CFR Part 63, Subpart CC	Product Stored = Refined petroleum products
GRP-IRMTBQ	STORAGE TANKS/VESSELS	83-TK-159, 83-TK-160	63CC-b	40 CFR Part 63, Subpart CC	Reid Vapor Pressure = Reid vapor pressure is greater than or equal to 2.0 psia, Product Stored = Crude oil
GRP-NNN	DISTILLATION OPERATIONS	20-V-03, 25-T-03, 36-T-02, 36-V-06, 37-V-03, 37-V-05, 49-V-01, 54-V-42	60NNNa	40 CFR Part 60, Subpart NNN	Subpart NNN Control Device = EPA Administrator approved demonstration of compliance with 40 CFR § 60.662(a) other than 40

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					CFR § 60.663(a), (b), (c), or (d)
GRP-NNN	DISTILLATION OPERATIONS	20-V-03, 25-T-03, 36-T-02, 36-V-06, 37-V-03, 37-V-05, 49-V-01, 54-V-42	60NNNb	40 CFR Part 60, Subpart NNN	Subpart NNN Control Device = Flare.
GRP-R5-1	FUGITIVE EMISSION UNITS	41F, AMINE-FUG, SMR-FUG, SWS- FUG	R5322ALL	30 TAC Chapter 115, Fugitives Pet Ref B Counties	No changing attributes.
GRP-R5-2	FUGITIVE EMISSION UNITS	30B01F, 30B02F, 30B03F, 30B04F	R5322-ALL	30 TAC Chapter 115, Fugitives Pet Ref B Counties	No changing attributes.
GRP-R5CC	FUGITIVE EMISSION UNITS	11F-HDS, ALKY- FUG, HDS FUG	R5322ALL	30 TAC Chapter 115, Fugitives Pet Ref B Counties	No changing attributes.
GRP-R5CC	FUGITIVE EMISSION UNITS	11F-HDS, ALKY- FUG, HDS FUG	63CCHALL	40 CFR Part 63, Subpart CC	No changing attributes.
GRP-R5CC2	FUGITIVE EMISSION UNITS	DOCKS-F, GAS BLEND, PIPING FUG, TERMIN 2/2A, TERMINAL 1, TERMINAL 3	R5322ALL	30 TAC Chapter 115, Fugitives Pet Ref B Counties	No changing attributes.
GRP-R5CC2	FUGITIVE EMISSION UNITS	DOCKS-F, GAS BLEND, PIPING FUG, TERMIN 2/2A, TERMINAL 1, TERMINAL 3	63CCHALL	40 CFR Part 63, Subpart CC	No changing attributes.
GRP-R5G	FUGITIVE EMISSION UNITS	46F/24F, 47PSA, VACUUMUNIT	R5322ALL	30 TAC Chapter 115, Fugitives Pet Ref B Counties	No changing attributes.
GRP-R5G	FUGITIVE EMISSION UNITS	46F/24F, 47PSA, VACUUMUNIT	60GGGALL	40 CFR Part 60, Subpart GGG	No changing attributes.
GRP-RRR	REACTOR	38-V-23, 38-V-32	60RRRa	40 CFR Part 60, Subpart	Control Device = Boiler or process

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
				RRR	heater with design heat input less than 44 MW (150 MMBTU/hr)., Secondary Fuel = The vent stream is introduced with the primary fuel.
GRP-RRR	REACTOR	38-V-23, 38-V-32	60RRRb	40 CFR Part 60, Subpart RRR	Control Device = Boiler or process heater with design heat input of 44 MW (150MMBTU/hr) or greater.
GRP-RRR	REACTOR	38-V-23, 38-V-32	60RRRc	40 CFR Part 60, Subpart RRR	Control Device = Flare that meets the requirements of 40 CFR § 60.18.
GRP-SRU3	FUGITIVE EMISSION UNITS	ATU3FUG, SCOTFUG, SRU3FUG	R5322ALL	30 TAC Chapter 115, Fugitives Pet Ref B Counties	No changing attributes.
GRP-SRU3	FUGITIVE EMISSION UNITS	ATU3FUG, SCOTFUG, SRU3FUG	60GGGALL	40 CFR Part 60, Subpart GGG	No changing attributes.
GRP-VACJET	VACUUM PRODUCING SYSTEMS	02J01, 02J02, 02J03, 02J04, 02J05, 02J06	R5311a	30 TAC Chapter 115, Unit Turn & Vac System-Pet Ref	Control Device = Any other vapor recovery system.
GRP-VACJET	VACUUM PRODUCING SYSTEMS	02J01, 02J02, 02J03, 02J04, 02J05, 02J06	R5311b	30 TAC Chapter 115, Unit Turn & Vac System-Pet Ref	Control Device = Smokeless flare.
GRPTURNJET	VACUUM PRODUCING SYSTEMS	36J01, 38J01, 47J01, 49J01, SP-1271	R5311a	30 TAC Chapter 115, Unit Turn & Vac System-Pet Ref	No changing attributes.
HOC-PP-CT	INDUSTRIAL PROCESS COOLING TOWERS	N/A	63CC	40 CFR Part 63, Subpart CC	No changing attributes.
HOCPP-FUG	FUGITIVE EMISSION UNITS	N/A	R5322-ALL	30 TAC Chapter 115, Fugitives Pet Ref B Counties	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
HOCPP-FUG	FUGITIVE EMISSION UNITS	N/A	60GGGA-ALL	40 CFR Part 60, Subpart GGGa	No changing attributes.
HOCPP-FUG	FUGITIVE EMISSION UNITS	N/A	63CCVV-ALL	40 CFR Part 63, Subpart CC	No changing attributes.
LPG STORAG	FUGITIVE EMISSION UNITS	N/A	R5322ALL	30 TAC Chapter 115, Fugitives Pet Ref B Counties	No changing attributes.
MEROX	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121a	30 TAC Chapter 115, Vent Gas Controls	Control Device Type = Other vapor control/recovery system, as defined in 30 TAC § 115.10
MEROX	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121b	30 TAC Chapter 115, Vent Gas Controls	Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).
MEROX	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	63CCa	40 CFR Part 63, Subpart CC	Control Device = Boiler or process heater with a design heat input capacity of greater or equal to than 44 MW or a boiler or process heater in which all vent streams are introduced into the flame zone.
MEROX	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	63CCb	40 CFR Part 63, Subpart CC	Control Device = Thermal incinerator, 98% Reduction = Compliance with the 20 ppmv concentration requirements specified in § 63.116(c)(1)(ii) are chosen., Performance Test = No previous performance test was conducted., Continuous Operating Parameter Alternative = The owner or operator is not using an alternative to the continuous operating parameter monitoring and recordkeeping provisions of 40 CFR

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					§ 63.655(i)
MFL-1	FLARES	N/A	R1111	30 TAC Chapter 111, Visible Emissions	No changing attributes.
MFL-1	FLARES	N/A	60A	40 CFR Part 60, Subpart A	No changing attributes.
MFL-1	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60Ja	40 CFR Part 60, Subpart Ja	No changing attributes.
MFL-1	FLARES	N/A	63A	40 CFR Part 63, Subpart A	No changing attributes.
MFL-1B	FLARES	N/A	R1111	30 TAC Chapter 111, Visible Emissions	No changing attributes.
MFL-1B	FLARES	N/A	63A	40 CFR Part 63, Subpart A	No changing attributes.
MTBE FL-2	FLARES	N/A	R1111	30 TAC Chapter 111, Visible Emissions	No changing attributes.
MTBE FL-2	FLARES	N/A	60A	40 CFR Part 60, Subpart A	No changing attributes.
MTBE FL-2	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60Ja	40 CFR Part 60, Subpart Ja	No changing attributes.
MTBE FL-2	FLARES	N/A	63A	40 CFR Part 63, Subpart A	No changing attributes.
MTBE-FUG	FUGITIVE EMISSION UNITS	N/A	R5322ALL	30 TAC Chapter 115, Fugitives Pet Ref B Counties	No changing attributes.
MTBE-FUG	FUGITIVE EMISSION UNITS	N/A	60GGGALL	40 CFR Part 60, Subpart GGG	No changing attributes.
MVRUF	FUGITIVE EMISSION UNITS	N/A	R5322ALL	30 TAC Chapter 115, Fugitives Pet Ref B Counties	No changing attributes.
MVRUF	FUGITIVE EMISSION	N/A	63CCVVALL	40 CFR Part 63, Subpart CC	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	UNITS				
OLEFLEX-FU	FUGITIVE EMISSION UNITS	N/A	60VV-ALL	40 CFR Part 60, Subpart VV	No changing attributes.
RAIL-FUG	FUGITIVE EMISSION UNITS	N/A	R5322ALL	30 TAC Chapter 115, Fugitives Pet Ref B Counties	No changing attributes.
RAIL-FUG	FUGITIVE EMISSION UNITS	N/A	63CCALL	40 CFR Part 63, Subpart CC	No changing attributes.
RAILRACK1	LOADING/UNLOADING OPERATIONS	N/A	R5211	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.
SHIPDOCKS	LOADING/UNLOADING OPERATIONS	N/A	61BB	40 CFR Part 61, Subpart BB	No changing attributes.
SHIPDOCKS	LOADING/UNLOADING OPERATIONS	N/A	63CC	40 CFR Part 63, Subpart CC	No changing attributes.
SHIPDOCKS	LOADING/UNLOADING OPERATIONS	N/A	63Ya	40 CFR Part 63, Subpart Y	Material Loaded = Material other than crude oil or gasoline., Source Emissions = Source with emissions less than 10 and 25 tons.
SHIPDOCKS	LOADING/UNLOADING OPERATIONS	N/A	63Yb	40 CFR Part 63, Subpart Y	Alternate Monitoring = Complying with the control device specific monitoring procedures in 40 CFR § 63.564., Alternate Test Procedure = Complying with the test procedures in 40 CFR § 63.565., Bypass Flow Indicator = Visual inspection of seal or closure mechanism., Vent Stream By-Pass = There are valves that could route displaced vapors to the atmosphere., Material Loaded = Gasoline., Source Emissions = Source with emissions of 10 or 25

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					tons., Throughput = Source with throughput of 10 M barrels or 200 M barrels., Vapor Balancing System = Emissions are not reduced by a vapor balancing system., CEMS = Continuous emissions monitoring system (CEMS) is not being used., Documenting Vapor Tightness = Electing to comply with the emissions reporting requirements in 40 CFR § 63.567(b)(5)(i)., Subpart Y Control Device Type = Carbon adsorber with vacuum regeneration., Performance Test = Baseline temperature from manufacturer.
SRU	GAS SWEETENING/SULFUR RECOVERY UNITS	N/A	REG2	30 TAC Chapter 112, Sulfur Compounds	No changing attributes.
SRU	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J	40 CFR Part 60, Subpart J	Monitoring Device = An instrument is in place for continuously monitoring and recording the concentration by volume of SO ₂ emissions into the atmosphere.
SRU	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-AMP	40 CFR Part 60, Subpart J	Monitoring Device = The temperature of the molten sulfur (139°C) shall not generate sufficient vapors to exceed 250 ppmv of sulfur dioxide at 0% oxygen in the combusted gas.
SRU	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS	N/A	63UUU	40 CFR Part 63, Subpart UUU	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	SRU				
SRU3	GAS SWEETENING/SULFUR RECOVERY UNITS	N/A	REG2	30 TAC Chapter 112, Sulfur Compounds	No changing attributes.
SRU3	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J	40 CFR Part 60, Subpart J	Monitoring Device = An instrument is in place for continuously monitoring and recording the concentration by volume of SO ₂ emissions into the atmosphere.
SRU3	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J-AMP	40 CFR Part 60, Subpart J	Monitoring Device = The HOC LPG Merox Oxidizer vent gas stream will meet the exemption provided at 40 CFR § 60.105(a)(4)(iv)(D), provided certain parametric monitoring provisions are maintained as represented in the AMP.
SRU3	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	63UUU	40 CFR Part 63, Subpart UUU	No changing attributes.
T-RACK	LOADING/UNLOADING OPERATIONS	N/A	R5211a	30 TAC Chapter 115, Loading and Unloading of VOC	Vapor Space Holding Tank = the gasoline terminal does not have a variable vapor space holding tank design that can process vapors independent of transport vessel loading or chooses compliance with 30 TAC 115.212(a)(4)(C)., Chapter 115 Facility Type = Gasoline terminal, Product Transferred = Gasoline, True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia., Daily

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(B), (b)(3)(B), (a)(2)(A), and (b)(3)(A) exemptions do not apply to marine terminals or gasoline terminals., Chapter 115 Control Device Type = Vapor control system with a vapor combustor., Transfer Type = Only loading., Vapor Tight = All liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.
T-RACK	LOADING/UNLOADING OPERATIONS	N/A	R5211b	30 TAC Chapter 115, Loading and Unloading of VOC	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal., Product Transferred = Volatile organic compounds other than liquefied petroleum gas, crude oil, condensate and gasoline., True Vapor Pressure = True vapor pressure is less than 1.5 psia., Transfer Type = Loading and unloading.
T-RACK	LOADING/UNLOADING OPERATIONS	N/A	R5211c	30 TAC Chapter 115, Loading and Unloading of VOC	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal., Product Transferred = Liquefied petroleum gas (LPG), crude oil, or condensate., Transfer Type = Loading and unloading.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
T-RACK	LOADING/UNLOADING OPERATIONS	N/A	63CC	40 CFR Part 63, Subpart CC	No changing attributes.
TRUCKCOMB	FCCU CAT REGEN/FUEL GAS COMBUSTION/CLAUS SRU	N/A	60J	40 CFR Part 60, Subpart J	No changing attributes.
WWTP-FUG	FUGITIVE EMISSION UNITS	N/A	R5322ALL	30 TAC Chapter 115, Fugitives Pet Ref B Counties	No changing attributes.
WWTP-FUG	CLOSED VENT SYSTEM AND CONTROL DEVICE	N/A	61FF-DRAINS	40 CFR Part 61, Subpart FF	No changing attributes.

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
02-V-12	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(b) § 115.121(b) § 115.122(b)(2)	For all persons in Nueces and Victoria Counties, any vent gas streams affected by §115.121(b) of this title must be controlled properly with a control efficiency of at least 90% or to a VOC concentration of no more than 20 ppmv (on a dry basis corrected to 3.0% oxygen for combustion devices).	[G]§ 115.125 § 115.126(2) ** See Periodic Monitoring Summary	§ 115.126 § 115.126(2)	None
02-V-12	EP	63CC	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC
05-CT-109	EU	63CC-c	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC
13-H-01A	EU	60J	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						(H2S) in excess of 230 mg/dscm (0.10 gr/dscf).			
13-H-01A	EU	60J-low	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1) § 60.105(a)(4)(iv) § 60.105(a)(4)(iv)(C)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.106(a)	§ 60.107(e)	§ 60.107(f) § 60.107(g)
13-H-01A	EU	63DDDDD	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
13-H-01B	EU	60J	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
13-H-01B	EU	60J-low	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1) § 60.105(a)(4)(iv) § 60.105(a)(4)(iv)(C)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.106(a)	§ 60.107(e)	§ 60.107(f) § 60.107(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
13-H-01B	EU	63DDDDD	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
13-H-01C	EU	60J	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H ₂ S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
13-H-01C	EU	60J-low	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1) § 60.105(a)(4)(iv) § 60.105(a)(4)(iv)(C)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H ₂ S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.106(a)	§ 60.107(e)	§ 60.107(f) § 60.107(g)
13-H-01C	EU	63DDDDD	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
16-P-11-EN	EU	60III-2	CO	40 CFR Part 60,	§ 60.4205(b)	Owners and operators of	None	None	[G]§ 60.4214(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Subpart IIII	§ 60.4202(e)(1) § 60.4206 [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218 § 94.8(a)(2)	emergency stationary CI ICE, that are not fire pump engines, with a displacement of greater than or equal to 10 liters per cylinder and less than 30 liters per cylinder and is a 2007 model year and later must comply with a CO emission limit of 5.0 g/KW-hr, as stated in 40 CFR 60.4202(e)-(f) and 40 CFR 94.8(a)(2) and 40 CFR 1042.101.			
16-P-11-EN	EU	60IIII-2	PM	40 CFR Part 60, Subpart IIII	§ 60.4205(b) § 60.4202(e)(1) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218 § 94.8(a)(2)	Owners and operators of emergency stationary CI ICE, that are not fire pump engines, with a displacement of greater than or equal to 15 liters per cylinder and less than 30 liters per cylinder and is a 2007 - 2013 model year must comply with a PM emission limit of 0.50 g/KW-hr, as stated in 40 CFR 60.4202(e)(1), (e)(3) and 40 CFR 94.8(a)(2).	None	None	[G]§ 60.4214(d)
16-P-11-EN	EU	60IIII-2	Total Hydrocarbons/NO _x	40 CFR Part 60, Subpart IIII	§ 60.4205(b) § 60.4202(e)(1) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218 § 94.8(a)(2)	Owners and operators of emergency stationary CI ICE, that are not fire pump engines, with a displacement of greater than or equal to 15 liters per cylinder and less than 20 liters per cylinder and is a 2007 - 2012 model year must comply with a	None	None	[G]§ 60.4214(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						THC+NOx emission limit of 8.7 g/KW-hr, as stated in 40 CFR 60.4202(e)(1) and 40 CFR 94.8(a)(2).			
16-P-11-EN	EU	63ZZZZ-2	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(b)(1) § 63.6595(c) § 63.6640(f)(1) § 63.6640(f)(2) § 63.6640(f)(2)(i) § 63.6640(f)(3)	An affected source which meets either of the criteria in paragraphs §63.6590(b)(1)(i)-(ii) of this section does not have to meet the requirements of this subpart and of subpart A of this part except for the initial notification requirements of §63.6645(f).	None	None	§ 63.6645(c) § 63.6645(f)
16-P-12-EN	EU	60IIII-2	CO	40 CFR Part 60, Subpart IIII	§ 60.4205(b) § 60.4202(e)(1) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218 § 94.8(a)(2)	Owners and operators of emergency stationary CI ICE, that are not fire pump engines, with a displacement of greater than or equal to 10 liters per cylinder and less than 30 liters per cylinder and is a 2007 model year and later must comply with a CO emission limit of 5.0 g/KW-hr, as stated in 40 CFR 60.4202(e)-(f) and 40 CFR 94.8(a)(2) and 40 CFR 1042.101.	None	None	[G]§ 60.4214(d)
16-P-12-EN	EU	60IIII-2	PM	40 CFR Part 60, Subpart IIII	§ 60.4205(b) § 60.4202(e)(1) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218	Owners and operators of emergency stationary CI ICE, that are not fire pump engines, with a displacement of greater than or equal to 15 liters per cylinder and less than 30 liters per cylinder and is a	None	None	[G]§ 60.4214(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 94.8(a)(2)	2007 - 2013 model year must comply with a PM emission limit of 0.50 g/KW-hr, as stated in 40 CFR 60.4202(e)(1), (e)(3) and 40 CFR 94.8(a)(2).			
16-P-12-EN	EU	60III-2	Total Hydrocarbons/NO _x	40 CFR Part 60, Subpart IIII	§ 60.4205(b) § 60.4202(e)(1) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218 § 94.8(a)(2)	Owners and operators of emergency stationary CI ICE, that are not fire pump engines, with a displacement of greater than or equal to 15 liters per cylinder and less than 20 liters per cylinder and is a 2007 - 2012 model year must comply with a THC+NO _x emission limit of 8.7 g/KW-hr, as stated in 40 CFR 60.4202(e)(1) and 40 CFR 94.8(a)(2).	None	None	[G]§ 60.4214(d)
16-P-12-EN	EU	63ZZZZ-2	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(b)(1) § 63.6595(c) § 63.6640(f)(1) § 63.6640(f)(2) § 63.6640(f)(2)(i) § 63.6640(f)(3)	An affected source which meets either of the criteria in paragraphs §63.6590(b)(1)(i)-(ii) of this section does not have to meet the requirements of this subpart and of subpart A of this part except for the initial notification requirements of §63.6645(f).	None	None	§ 63.6645(c) § 63.6645(f)
16-P-13-EN	EU	60III-2	CO	40 CFR Part 60, Subpart IIII	§ 60.4205(b) § 60.4202(e)(1) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f)	Owners and operators of emergency stationary CI ICE, that are not fire pump engines, with a displacement of greater than or equal to 10 liters per cylinder and less than 30	None	None	[G]§ 60.4214(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.4218 § 94.8(a)(2)	liters per cylinder and is a 2007 model year and later must comply with a CO emission limit of 5.0 g/KW-hr, as stated in 40 CFR 60.4202(e)-(f) and 40 CFR 94.8(a)(2) and 40 CFR 1042.101.			
16-P-13-EN	EU	60III-2	PM	40 CFR Part 60, Subpart IIII	§ 60.4205(b) § 60.4202(e)(1) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218 § 94.8(a)(2)	Owners and operators of emergency stationary CI ICE, that are not fire pump engines, with a displacement of greater than or equal to 15 liters per cylinder and less than 30 liters per cylinder and is a 2007 - 2013 model year must comply with a PM emission limit of 0.50 g/KW-hr, as stated in 40 CFR 60.4202(e)(1), (e)(3) and 40 CFR 94.8(a)(2).	None	None	[G]§ 60.4214(d)
16-P-13-EN	EU	60III-2	Total Hydrocarbons/NO _x	40 CFR Part 60, Subpart IIII	§ 60.4205(b) § 60.4202(e)(1) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218 § 94.8(a)(2)	Owners and operators of emergency stationary CI ICE, that are not fire pump engines, with a displacement of greater than or equal to 15 liters per cylinder and less than 20 liters per cylinder and is a 2007 - 2012 model year must comply with a THC+NO _x emission limit of 8.7 g/KW-hr, as stated in 40 CFR 60.4202(e)(1) and 40 CFR 94.8(a)(2).	None	None	[G]§ 60.4214(d)
16-P-13-EN	EU	63ZZZZ-2	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(b)(1) § 63.6595(c)	An affected source which meets either of the criteria	None	None	§ 63.6645(c) § 63.6645(f)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.6640(f)(1) § 63.6640(f)(2) § 63.6640(f)(2)(i) § 63.6640(f)(3)	in paragraphs §63.6590(b)(1)(i)-(ii) of this section does not have to meet the requirements of this subpart and of subpart A of this part except for the initial notification requirements of §63.6645(f).			
16-P-14-EN	EU	60III-2	CO	40 CFR Part 60, Subpart IIII	§ 60.4205(b) § 60.4202(e)(1) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218 § 94.8(a)(2)	Owners and operators of emergency stationary CI ICE, that are not fire pump engines, with a displacement of greater than or equal to 10 liters per cylinder and less than 30 liters per cylinder and is a 2007 model year and later must comply with a CO emission limit of 5.0 g/KW-hr, as stated in 40 CFR 60.4202(e)-(f) and 40 CFR 94.8(a)(2) and 40 CFR 1042.101.	None	None	[G]§ 60.4214(d)
16-P-14-EN	EU	60III-2	PM	40 CFR Part 60, Subpart IIII	§ 60.4205(b) § 60.4202(e)(1) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218 § 94.8(a)(2)	Owners and operators of emergency stationary CI ICE, that are not fire pump engines, with a displacement of greater than or equal to 15 liters per cylinder and less than 30 liters per cylinder and is a 2007 - 2013 model year must comply with a PM emission limit of 0.50 g/KW-hr, as stated in 40 CFR 60.4202(e)(1), (e)(3) and 40 CFR 94.8(a)(2).	None	None	[G]§ 60.4214(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
16-P-14-EN	EU	60III-2	Total Hydrocarbons/NO _x	40 CFR Part 60, Subpart IIII	§ 60.4205(b) § 60.4202(e)(1) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218 § 94.8(a)(2)	Owners and operators of emergency stationary CI ICE, that are not fire pump engines, with a displacement of greater than or equal to 15 liters per cylinder and less than 20 liters per cylinder and is a 2007 - 2012 model year must comply with a THC+NO _x emission limit of 8.7 g/KW-hr, as stated in 40 CFR 60.4202(e)(1) and 40 CFR 94.8(a)(2).	None	None	[G]§ 60.4214(d)
16-P-14-EN	EU	63ZZZZ-2	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(b)(1) § 63.6595(c) § 63.6640(f)(1) § 63.6640(f)(2) § 63.6640(f)(2)(i) § 63.6640(f)(3)	An affected source which meets either of the criteria in paragraphs §63.6590(b)(1)(i)-(ii) of this section does not have to meet the requirements of this subpart and of subpart A of this part except for the initial notification requirements of §63.6645(f).	None	None	§ 63.6645(c) § 63.6645(f)
16-P-4-EN	EU	63ZZZZ-1	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6602-Table2c.1 § 63.6595(a)(1) § 63.6605(a) § 63.6605(b) § 63.6625(e) § 63.6625(h) § 63.6625(i) § 63.6640(f)(1) § 63.6640(f)(2) § 63.6640(f)(2)(i) § 63.6640(f)(3)	For each existing emergency stationary CI RICE and black start stationary CI RICE, located at a major source, you must comply with the requirements as specified in Table 2c.1.a-c.	§ 63.6625(f) § 63.6625(i) § 63.6640(a) § 63.6640(a)-Table6.9.a.i § 63.6640(a)-Table6.9.a.ii	§ 63.6625(i) § 63.6655(d) § 63.6655(e) § 63.6655(f) § 63.6660(a) § 63.6660(b) § 63.6660(c)	§ 63.6640(e) § 63.6650(f)
16-P-7-EN	EU	63ZZZZ-1	112(B)	40 CFR Part 63,	§ 63.6602-	For each existing	§ 63.6625(f)	§ 63.6625(i)	§ 63.6640(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
			HAPS	Subpart ZZZZ	Table2c.1 § 63.6595(a)(1) § 63.6605(a) § 63.6605(b) § 63.6625(e) § 63.6625(h) § 63.6625(i) § 63.6640(f)(1) § 63.6640(f)(2) § 63.6640(f)(2)(i) § 63.6640(f)(3)	emergency stationary CI RICE and black start stationary CI RICE, located at a major source, you must comply with the requirements as specified in Table 2c.1.a-c.	§ 63.6625(i) § 63.6640(a) § 63.6640(a)-Table6.9.a.i § 63.6640(a)-Table6.9.a.ii	§ 63.6655(d) § 63.6655(e) § 63.6655(f) § 63.6660(a) § 63.6660(b) § 63.6660(c)	§ 63.6650(f)
17-FUG	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No connector, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
17-FUG	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(5)	No pressure relief valve in gaseous service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(C) § 115.324(4) § 115.324(5) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
17-FUG	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(5)	No pressure relief valve in gaseous service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
17-FUG	EU	R5322-	VOC	30 TAC Chapter	§ 115.322(1)	No elevated valve may be	§ 115.324	[G]§ 115.326(1)	[G]§ 115.324(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		ALL		115, Fugitives Pet Ref B Counties	§ 115.322(2) § 115.322(3) § 115.322(4)	allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324(1) § 115.324(1)(D) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
17-FUG	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No elevated valve, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
17-FUG	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No compressor seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(A) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
17-FUG	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3) § 115.327(6)	No compressor seal, as described in § 115.327(3), (5) or (6), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
17-FUG	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No process drain may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(C) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
17-FUG	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No process drain, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
17-FUG	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No valve in liquid service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
17-FUG	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No valve in liquid service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
17-FUG	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.322(5)	No valve (gaseous service) may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
17-FUG	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(5)	No valve (gaseous service), as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						after the leak is found, except as provided in §115.322(2).			
17-FUG	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No pump seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(A) § 115.324(3) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
17-FUG	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No pump seal, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
17-FUG	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.327(1)	Valves of nominal size of 2" (5 cm) or less are exempt, provided allowable emissions from sources affected by this division after controls are applied with exemptions will not exceed by more than 5.0% such allowable emissions with no exemptions.	None	None	§ 115.327(1)(A) § 115.327(1)(B) § 115.327(1)(C)
17-FUG	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No connector may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
17-FUG	EU	60GGGaV	VOC	40 CFR Part 60,	[G]§ 60.590a(a)	The permit holder shall	The permit holder	The permit holder shall	The permit holder shall

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		Va		Subpart GGGa	The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 60, Subpart GGGa	comply with the applicable requirements of 40 CFR Part 60, Subpart GGGa	shall comply with the applicable monitoring and testing requirements of 40 CFR Part 60, Subpart GGGa	comply with the applicable recordkeeping requirements of 40 CFR Part 60, Subpart GGGa	comply with the applicable reporting requirements of 40 CFR Part 60, Subpart GGGa
17-FUG	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC
17-H-1	EU	60Ja	§111 Pollutant	40 CFR Part 60, Subpart Ja	§ 60.100a(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 60, Subpart Ja
17-H-1	EU	63DDDDD	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63,	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					Subpart DDDDD				
24-ST-01	EU	60J	CO	40 CFR Part 60, Subpart J	§ 60.103(a) § 60.105(a)(2)	No owner or operator shall discharge or cause the discharge into the atmosphere from any fluid catalytic cracking unit catalyst regenerator any gases that contain carbon monoxide (CO) in excess of 500 ppm by volume (dry basis).	§ 60.105(a)(2) § 60.105(a)(2)(i) § 60.106(a) § 60.106(d)	§ 60.105(a)(2) § 60.105(c)	§ 60.105(e)(2) § 60.107(f) § 60.107(g)
24-ST-01	EU	60J	PM	40 CFR Part 60, Subpart J	§ 60.102(a)(1)	No owner or operator subject to the provisions of this subpart shall discharge or cause the discharge into the atmosphere from any fluid catalytic cracking unit catalyst regenerator particulate matter in excess of 1.0 kg/Mg (2.0 lb/ton) of coke burn-off in the catalyst regenerator.	§ 60.106(a) § 60.106(b) § 60.106(b)(1) § 60.106(b)(2) [G]§ 60.106(b)(3) ** See CAM Summary	§ 60.105(c)	§ 60.107(f) § 60.107(g)
24-ST-01	EU	60J	PM (Opacity)	40 CFR Part 60, Subpart J	§ 60.102(a)(2)	No owner or operator subject to the provisions of this subpart shall discharge or cause the discharge into the atmosphere from any fluid catalytic cracking unit catalyst regenerator gases exhibiting greater than 30 percent opacity, except for one six-minute average opacity reading in any one hour period.	§ 60.106(a) § 60.106(b) ** See CAM Summary **See Alternative Requirement	§ 60.105(c)	§ 60.107(f) § 60.107(g)
24-ST-01	EU	60J	SO ₂	40 CFR Part 60, Subpart J	§ 60.104(b)(1) § 60.104(c) § 60.104(d)	For each affected fluid catalytic cracking unit catalyst regenerator with an	§ 60.105(a)(10) § 60.105(a)(11) [G]§ 60.105(a)(12)	§ 60.105(a)(10) § 60.105(a)(11) [G]§ 60.105(a)(12)	§ 60.107(a) § 60.107(c) [G]§ 60.107(c)(1)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						add-on control device, reduce sulfur dioxide emissions to the atmosphere by 90 percent or maintain sulfur dioxide emissions to the atmosphere less than or equal to 50 ppm by volume, whichever is less stringent.	[G]§ 60.105(a)(13) [G]§ 60.105(a)(8) [G]§ 60.105(a)(9) § 60.106(a) § 60.106(g) [G]§ 60.106(h) [G]§ 60.106(k) § 60.108(a) § 60.108(c) § 60.108(d) § 60.108(e)	[G]§ 60.105(a)(13) [G]§ 60.105(a)(8) [G]§ 60.105(a)(9) [G]§ 60.107(b)(1) § 60.107(b)(4)	§ 60.107(c)(2) [G]§ 60.107(c)(3) [G]§ 60.107(c)(4) § 60.107(d) § 60.107(f) § 60.107(g) § 60.108(e)
24-ST-01	EU	60Ja	CO	40 CFR Part 60, Subpart Ja	§ 60.102a(b)(4) § 60.102a(a) § 60.102a(b)	An owner or operator shall not discharge or cause the discharge into the atmosphere from any FCCU or FCU carbon monoxide in excess of 500 ppmv, dry basis corrected to 0 percent excess air, on an hourly average basis.	§ 60.104a(a) § 60.104a(c) § 60.104a(d) § 60.104a(d)(1) § 60.104a(d)(2) § 60.104a(d)(3) § 60.104a(d)(7) § 60.104a(d)(8) § 60.105a(b)(2)(iii) § 60.105a(b)(2)(iv) § 60.105a(h) § 60.105a(h)(1) § 60.105a(h)(2) § 60.105a(i) § 60.105a(i)(7)	§ 60.108a(a) [G]§ 60.108a(d)	§ 60.108a(a) § 60.108a(b) [G]§ 60.108a(d)
24-ST-01	EU	60Ja	NO _x	40 CFR Part 60, Subpart Ja	§ 60.102a(b)(2) § 60.102a(a) § 60.102a(b)	An owner or operator shall not discharge or cause the discharge into the atmosphere from any FCCU or FCU NO _x in excess of 80 ppmv, dry basis corrected to 0 percent excess air, on a 7-day rolling average basis.	§ 60.104a(a) § 60.104a(c) § 60.104a(d) § 60.104a(d)(1) § 60.104a(d)(2) § 60.104a(d)(3) § 60.104a(d)(6) § 60.104a(d)(8) [G]§ 60.105a(f) § 60.105a(i) § 60.105a(i)(5)	§ 60.108a(a) [G]§ 60.108a(d)	§ 60.108a(a) § 60.108a(b) [G]§ 60.108a(d)
24-ST-01	EU	60Ja	PM	40 CFR Part 60,	§ 60.102a(b)(1)(i)	An owner or operator shall	§ 60.104a(a)	§ 60.108a(a)	§ 60.108a(a)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Subpart Ja	§ 60.102a(a) § 60.102a(b) § 60.102a(b)(1) § 60.102a(c)(2)(i) § 60.102a(c)(2)(ii)	not discharge or cause the discharge into the atmosphere particulate matter (PM) in excess of 1.0 kg/Mg (1lb/1,000 lb) coke burn-off for each modified or reconstructed FCCU (if a PM CEMS is not used).	§ 60.104a(b) § 60.104a(c) § 60.104a(d) § 60.104a(d)(1) § 60.104a(d)(2) § 60.104a(d)(3) [G]§ 60.104a(d)(4) § 60.104a(d)(8) [G]§ 60.104a(e) § 60.105a(a) § 60.105a(b) § 60.105a(b)(1) [G]§ 60.105a(b)(1)(ii) § 60.105a(b)(1)(iii) § 60.105a(b)(1)(iv) § 60.105a(b)(2) § 60.105a(b)(2)(i) § 60.105a(b)(2)(ii) § 60.105a(b)(2)(v) § 60.105a(i) § 60.105a(i)(1)	§ 60.108a(c) § 60.108a(c)(4) [G]§ 60.108a(d)	§ 60.108a(b) [G]§ 60.108a(d)
24-ST-01	EU	60Ja	SO ₂	40 CFR Part 60, Subpart Ja	§ 60.102a(b)(3) § 60.102a(a) § 60.102a(b)	An owner or operator shall not discharge or cause the discharge into the atmosphere from any FCCU or FCU SO ₂ in excess of 50 ppmv dry basis corrected to 0 percent excess air, on a 7-day rolling average basis and 25 ppmv, dry basis corrected to 0 percent excess air, on a 365-day rolling average basis.	§ 60.104a(a) § 60.104a(c) § 60.104a(d) § 60.104a(d)(1) § 60.104a(d)(2) § 60.104a(d)(3) § 60.104a(d)(5) § 60.104a(d)(8) [G]§ 60.105a(g) § 60.105a(i) § 60.105a(i)(6)	§ 60.108a(a) [G]§ 60.108a(d)	§ 60.108a(a) § 60.108a(b) [G]§ 60.108a(d)
24-ST-01	EU	63UUU-J	CO	40 CFR Part 63, Subpart UUU	§ 63.1565(a)(1)-Table 8.1 § 63.1565(a)(1) § 63.1565(a)(2)	For each new and existing CCU subject to the NSPS for CO in 40 CFR §60.103 or §60.102a(b)(4) or	§ 63.1565(b)(1) § 63.1565(b)(1)-Table 10.1 § 63.1565(b)(1)-	§ 63.1565(b)(1)-Table 10.1 § 63.1565(c)(1)-Table 14.3	§ 63.1565(b)(5) § 63.1565(b)(6) § 63.1570(f) § 63.1571(a)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.1565(a)(2)-Table 9.1 § 63.1565(a)(2)-Table 9.3 § 63.1565(a)(3) § 63.1565(a)(4) § 63.1565(a)(5) § 63.1565(b)(4) § 63.1565(b)(4)-Table 12.1 § 63.1565(c)(1) § 63.1565(c)(2) § 63.1570(a) § 63.1570(c) § 63.1570(d)	electing to comply with the NSPS requirements (Option 1), CO emissions from the catalyst regenerator vent or CO boiler serving the CCU must not exceed 500 parts per million volume (ppmv) (dry basis).	Table 10.3 § 63.1565(c)(1)-Table 13.1 § 63.1565(c)(1)-Table 14.1 § 63.1565(c)(1)-Table 14.3 § 63.1571(a) § 63.1571(a)(1) § 63.1571(a)(2) [G]§ 63.1571(a)(6) § 63.1572(a) § 63.1572(a)(1) § 63.1572(a)(1)-Table 40.3 § 63.1572(a)(2) § 63.1572(a)(3) § 63.1572(a)(4) [G]§ 63.1572(d)	§ 63.1570(c) § 63.1570(d) [G]§ 63.1576(a) [G]§ 63.1576(b) § 63.1576(d) § 63.1576(e) § 63.1576(f) § 63.1576(g) § 63.1576(h) § 63.1576(i)	[G]§ 63.1574(a) § 63.1574(d) § 63.1574(d)-Table 42.1 § 63.1574(d)-Table 42.2 § 63.1574(d)-Table 42.3 § 63.1575(a) § 63.1575(a)-Table 43.1 [G]§ 63.1575(b) [G]§ 63.1575(c) [G]§ 63.1575(e) [G]§ 63.1575(f) § 63.1575(g) [G]§ 63.1575(h) [G]§ 63.1575(i) § 63.1575(k) § 63.1575(k)(1) [G]§ 63.1575(k)(2) § 63.1575(l) § 63.1576(b)
24-ST-01	EU	63UUU-J	PM	40 CFR Part 63, Subpart UUU	§ 63.1564(a)(1)-Table 1.1 § 63.1564(a)(1) § 63.1564(a)(2) § 63.1564(a)(2)-Table 2.10 § 63.1564(a)(3) § 63.1564(a)(4) [G]§ 63.1564(a)(5) § 63.1564(b)(3) § 63.1564(b)(5) § 63.1564(b)(5)-Table 5.1 § 63.1564(c)(1) § 63.1564(c)(1)-Table 7.10 [G]§ 63.1564(c)(5) § 63.1570(a) § 63.1570(c) § 63.1570(d)	For each new or existing CCU subject to NSPS for PM in 40 CFR §60.102, PM emissions must not exceed 1.0 g/kg (1.0 lb/1,000 lbs) of coke burn-off.	§ 63.1564(b)(1) § 63.1564(b)(1)-Table 3.12 § 63.1564(b)(2) [G]§ 63.1564(b)(2)-Table 4.1 § 63.1564(b)(2)-Table 4.2.a § 63.1564(b)(2)-Table 4.2.b [G]§ 63.1564(c)(1)-Table 6.1.a § 63.1571(a) § 63.1571(a)(1) § 63.1571(a)(5)(ii) [G]§ 63.1571(b) [G]§ 63.1572(d) § 63.1573(d) § 63.1573(e)	§ 63.1564(b)(1)-Table 3.12 [G]§ 63.1564(c)(1)-Table 6.1.a § 63.1564(c)(2) § 63.1570(c) § 63.1570(d) [G]§ 63.1576(a) § 63.1576(d) § 63.1576(e) § 63.1576(f) § 63.1576(g) § 63.1576(h) § 63.1576(i)	§ 63.1564(b)(6) § 63.1564(b)(7) § 63.1570(f) § 63.1571(a) [G]§ 63.1573(f) § 63.1573(g)(3) [G]§ 63.1574(a) § 63.1574(c) § 63.1574(d) § 63.1574(d)-Table 42.1 § 63.1574(d)-Table 42.2 § 63.1574(d)-Table 42.3 § 63.1575(a) § 63.1575(a)-Table 43.1 § 63.1575(a)-Table 43.2 [G]§ 63.1575(b) [G]§ 63.1575(c) [G]§ 63.1575(e) [G]§ 63.1575(f) § 63.1575(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 63.1573(g)(1) § 63.1573(g)(2)				[G]§ 63.1575(i) § 63.1575(k) [G]§ 63.1575(k)(1) § 63.1575(l)
24-ST-01	EU	63UUU-J	PM (Opacity)	40 CFR Part 63, Subpart UUU	§ 63.1564(a)(1)-Table 1.1 § 63.1564(a)(1) § 63.1564(a)(2) § 63.1564(a)(2)-Table 2.10 § 63.1564(a)(3) § 63.1564(a)(4) [G]§ 63.1564(a)(5) § 63.1564(b)(3) § 63.1564(b)(5) § 63.1564(b)(5)-Table 5.1 § 63.1564(c)(1) § 63.1564(c)(1)-Table 7.10 [G]§ 63.1564(c)(5) § 63.1570(b) § 63.1570(c) § 63.1570(d) [G]§ 63.1573(g)(1) [G]§ 63.1573(g)(2)	For each new or existing CCU subject to NSPS for PM in 40 CFR §60.102, the opacity of emissions must not exceed 30%, except for one 6-minute average opacity reading in any 1-hour period.	§ 63.1564(b)(1) § 63.1564(b)(1)-Table 3.12 § 63.1564(b)(2) § 63.1564(b)(2)-Table 4.1 § 63.1571(a) § 63.1571(a)(1) [G]§ 63.1571(b) [G]§ 63.1572(d) [G]§ 63.1573(d) § 63.1573(e) **See Alternative Requirement	§ 63.1564(b)(1)-Table 3.12 § 63.1564(c)(2) § 63.1570(c) § 63.1570(d) [G]§ 63.1576(a) § 63.1576(d) § 63.1576(e) § 63.1576(f) § 63.1576(g) § 63.1576(h) § 63.1576(i)	§ 63.1564(b)(6) § 63.1564(b)(7) § 63.1570(f) § 63.1571(a) [G]§ 63.1573(f) § 63.1573(g)(3) [G]§ 63.1574(a) § 63.1574(c) § 63.1574(d) § 63.1574(d)-Table 42.1 § 63.1574(d)-Table 42.2 § 63.1574(d)-Table 42.3 § 63.1575(a) § 63.1575(a)-Table 43.1 § 63.1575(a)-Table 43.2 [G]§ 63.1575(b) [G]§ 63.1575(c) [G]§ 63.1575(e) [G]§ 63.1575(f) § 63.1575(g) [G]§ 63.1575(i) § 63.1575(k) [G]§ 63.1575(k)(1) [G]§ 63.1575(l)
24-ST-01	EU	63UUU-Ja	CO	40 CFR Part 63, Subpart UUU	§ 63.1565(a)(1)-Table 8.1 § 63.1565(a)(1) § 63.1565(a)(2) § 63.1565(a)(2)-Table 9.1 § 63.1565(a)(2)-Table 9.3 § 63.1565(a)(3) § 63.1565(a)(4)	For each new and existing CCU subject to the NSPS for CO in 40 CFR §60.103 or §60.102a(b)(4) or electing to comply with the NSPS requirements (Option 1), CO emissions from the catalyst regenerator vent or CO boiler serving the CCU must not exceed 500 parts	§ 63.1565(b)(1) § 63.1565(b)(1)-Table 10.1 § 63.1565(b)(1)-Table 10.3 § 63.1565(c)(1)-Table 13.1 § 63.1565(c)(1)-Table 14.1 § 63.1565(c)(1)-	§ 63.1565(b)(1)-Table 10.1 § 63.1565(c)(1)-Table 14.3 § 63.1570(c) § 63.1570(d) [G]§ 63.1576(a) [G]§ 63.1576(b) § 63.1576(d) § 63.1576(e)	§ 63.1565(b)(5) § 63.1565(b)(6) § 63.1570(f) § 63.1571(a) [G]§ 63.1574(a) § 63.1574(d) § 63.1574(d)-Table 42.1 § 63.1574(d)-Table 42.2 § 63.1574(d)-Table 42.3 § 63.1575(a)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.1565(a)(5) § 63.1565(b)(4) § 63.1565(b)(4)-Table 12.1 § 63.1565(c)(1) § 63.1565(c)(2) § 63.1570(a) § 63.1570(c) § 63.1570(d)	per million volume (ppmv) (dry basis).	Table 14.3 § 63.1571(a) § 63.1571(a)(1) § 63.1571(a)(2) [G]§ 63.1571(a)(6) § 63.1572(a) § 63.1572(a)(1) § 63.1572(a)(1)-Table 40.3 § 63.1572(a)(2) § 63.1572(a)(3) § 63.1572(a)(4) [G]§ 63.1572(d)	§ 63.1576(f) § 63.1576(g) § 63.1576(h) § 63.1576(i)	§ 63.1575(a)-Table 43.1 [G]§ 63.1575(b) [G]§ 63.1575(c) [G]§ 63.1575(e) [G]§ 63.1575(f) § 63.1575(g) [G]§ 63.1575(h) [G]§ 63.1575(i) § 63.1575(k) § 63.1575(k)(1) [G]§ 63.1575(k)(2) § 63.1575(l) § 63.1576(b)
24-ST-01	EU	63UUU-Ja	PM	40 CFR Part 63, Subpart UUU	§ 63.1564(a)(1)-Table 1.2 § 63.1564(a)(1) § 63.1564(a)(2) § 63.1564(a)(2)-Table 2.10 [G]§ 63.1564(a)(2)-Table 2.2.d § 63.1564(a)(3) § 63.1564(a)(4) [G]§ 63.1564(a)(5) § 63.1564(b)(3) § 63.1564(b)(5) § 63.1564(b)(5)-Table 5.2 § 63.1564(c)(1) § 63.1564(c)(1)-Table 7.10 [G]§ 63.1564(c)(5) § 63.1570(a) § 63.1570(c) § 63.1570(d) § 63.1571(d) § 63.1571(d)(4) [G]§ 63.1571(e) § 63.1573(b)(3)	For each new or existing CCU subject to NSPS for PM in 40 CFR §60.102a(b)(1)(i) or §60.102 and electing §60.100(e), PM emissions must not exceed 1.0 g/kg (1.0 lb/1,000 lbs) of coke burn-off.	§ 63.1564(b)(1) § 63.1564(b)(1)-Table 3.12 § 63.1564(b)(1)-Table 3.2.c § 63.1564(b)(2) [G]§ 63.1564(b)(2)-Table 4.1 § 63.1564(b)(2)-Table 4.3.b § 63.1564(c)(1)-Table 6.2 [G]§ 63.1564(c)(1)-Table 7.2.c § 63.1571(a) § 63.1571(a)(1) § 63.1571(a)(5) [G]§ 63.1571(b) § 63.1572(c) § 63.1572(c)(1) § 63.1572(c)(1)-Table 41.8 § 63.1572(c)(2) § 63.1572(c)(3) § 63.1572(c)(4) [G]§ 63.1572(d)	§ 63.1564(b)(1)-Table 3.12 § 63.1564(b)(1)-Table 3.2.c § 63.1564(c)(1)-Table 6.2 [G]§ 63.1564(c)(1)-Table 7.2.c § 63.1564(c)(2) § 63.1570(c) § 63.1570(d) § 63.1572(c)(4) § 63.1572(c)(5) § 63.1573(b)(2) [G]§ 63.1576(a) § 63.1576(d) § 63.1576(e) § 63.1576(f) § 63.1576(g) § 63.1576(h) § 63.1576(i)	§ 63.1564(b)(6) § 63.1564(b)(7) § 63.1570(f) § 63.1571(a) § 63.1571(d)(4) [G]§ 63.1573(f) [G]§ 63.1574(a) § 63.1574(c) § 63.1574(d) § 63.1574(d)-Table 42.1 § 63.1574(d)-Table 42.2 § 63.1574(d)-Table 42.3 § 63.1575(a) § 63.1575(a)-Table 43.1 § 63.1575(a)-Table 43.2 [G]§ 63.1575(b) [G]§ 63.1575(c) [G]§ 63.1575(d) [G]§ 63.1575(f) § 63.1575(g) [G]§ 63.1575(i) § 63.1575(k) [G]§ 63.1575(k)(1) [G]§ 63.1575(l)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 63.1573(b) § 63.1573(b)(1) [G]§ 63.1573(d) § 63.1573(e)		
30-B-02	EU	60Db	NO _x	40 CFR Part 60, Subpart Db	§ 60.40b(a)	This subpart applies to each steam generating unit constructed, modified, or reconstructed after 6/19/84, and that has a heat input capacity from fuels combusted in the unit > 29 MW (100 MMBtu/hr).	None	[G]§ 60.49b(d) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3)
30-B-02	EU	60Db	PM	40 CFR Part 60, Subpart Db	§ 60.40b(a)	This subpart applies to each steam generating unit constructed, modified, or reconstructed after 6/19/84, and that has a heat input capacity from fuels combusted in the unit > 29 MW (100 MMBtu/hr).	None	[G]§ 60.49b(d) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3)
30-B-02	EU	60Db	PM (Opacity)	40 CFR Part 60, Subpart Db	§ 60.40b(a)	This subpart applies to each steam generating unit constructed, modified, or reconstructed after 6/19/84, and that has a heat input capacity from fuels combusted in the unit > 29 MW (100 MMBtu/hr).	None	[G]§ 60.49b(d) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3)
30-B-02	EU	60Db	SO ₂	40 CFR Part 60, Subpart Db	§ 60.104(a)(1) § 60.104	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide in excess of 230 mg/dscm (0.10 gr/dscf). The combustion in a flare of	§ 60.105(a) § 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.105(e) § 60.105(e)(3)(ii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4)	§ 60.105(e) § 60.105(e)(3)(ii) § 60.107(e) § 60.107(f)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						process upset gases or fuel gas that is released to the flare as a result of relief valve leakage or other emergency malfunctions is exempt from this paragraph.			
30-B-02	EU	63DDDDD	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
30-B-03	EU	60Db	NO _x	40 CFR Part 60, Subpart Db	§ 60.40b(a)	This subpart applies to each steam generating unit constructed, modified, or reconstructed after 6/19/84, and that has a heat input capacity from fuels combusted in the unit > 29 MW (100 MMBtu/hr).	None	[G]§ 60.49b(d) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3)
30-B-03	EU	60Db	PM	40 CFR Part 60, Subpart Db	§ 60.40b(a)	This subpart applies to each steam generating unit constructed, modified, or reconstructed after 6/19/84, and that has a heat input capacity from fuels combusted in the unit > 29 MW (100 MMBtu/hr).	None	[G]§ 60.49b(d) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3)
30-B-03	EU	60Db	PM (Opacity)	40 CFR Part 60, Subpart Db	§ 60.40b(a)	This subpart applies to each steam generating unit constructed, modified, or reconstructed after 6/19/84, and that has a heat input	None	[G]§ 60.49b(d) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						capacity from fuels combusted in the unit > 29 MW (100 MMBtu/hr).			
30-B-03	EU	60Db	SO ₂	40 CFR Part 60, Subpart Db	§ 60.104(a)(1) § 60.104	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide in excess of 230 mg/dscm (0.10 gr/dscf). The combustion in a flare of process upset gases or fuel gas that is released to the flare as a result of relief valve leakage or other emergency malfunctions is exempt from this paragraph.	§ 60.105(a) § 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.105(e) § 60.105(e)(3)(ii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4)	§ 60.105(e) § 60.105(e)(3)(ii) § 60.107(e) § 60.107(f)
30-B-03	EU	63DDDDD	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
30-B-04	EU	60Db	NO _x	40 CFR Part 60, Subpart Db	§ 60.44b(l)(1) § 60.44b(h) § 60.44b(i) § 60.46b(a)	Affected facilities combusting coal, oil, or natural gas, or a mixture of these fuels, or any other fuels: a limit of 86 ng/JI (0.20 lb/million Btu) heat input unless the affected facility meets the specified requirements.	§ 60.46b(c) § 60.46b(e) § 60.46b(e)(1) § 60.46b(e)(3) [G]§ 60.48b(b) § 60.48b(c) § 60.48b(d) § 60.48b(e) [G]§ 60.48b(e)(2) § 60.48b(e)(3)	[G]§ 60.48b(b) § 60.48b(c) [G]§ 60.49b(d) [G]§ 60.49b(g) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3) § 60.49b(b) § 60.49b(h) § 60.49b(i) § 60.49b(v) § 60.49b(w)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 60.48b(f)		
30-B-04	EU	60Db	PM	40 CFR Part 60, Subpart Db	§ 60.40b(a)	This subpart applies to each steam generating unit constructed, modified, or reconstructed after 6/19/84, and that has a heat input capacity from fuels combusted in the unit > 29 MW (100 MMBtu/hr).	None	[G]§ 60.49b(d) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3)
30-B-04	EU	60Db	PM (Opacity)	40 CFR Part 60, Subpart Db	§ 60.40b(a)	This subpart applies to each steam generating unit constructed, modified, or reconstructed after 6/19/84, and that has a heat input capacity from fuels combusted in the unit > 29 MW (100 MMBtu/hr).	None	[G]§ 60.49b(d) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3)
30-B-04	EU	60Ja	Hydrogen Sulfide	40 CFR Part 60, Subpart Ja	§ 60.102a(g)(1)(ii) § 60.102a(a) § 60.102a(g) § 60.102a(g)(1) § 60.103a(c) § 60.103a(d) § 60.103a(d)(1) § 60.103a(d)(5) [G]§ 60.103a(e)	For each fuel gas combustion device the owner or operator shall not burn in any fuel gas combustion device any fuel gas that contains H ₂ S in excess of 162 ppmv determined hourly on a 3-hour rolling average basis and H ₂ S in excess of 60 ppmv determined daily on a 365 successive calendar day rolling average basis.	§ 60.104a(a) § 60.104a(c) [G]§ 60.104a(j) § 60.107a(a) § 60.107a(a)(2) § 60.107a(a)(2)(i) § 60.107a(a)(2)(ii) § 60.107a(a)(2)(iii) § 60.107a(a)(2)(iv) § 60.107a(i) § 60.107a(i)(1)(ii)	§ 60.108a(a) § 60.108a(c) [G]§ 60.108a(c)(6) [G]§ 60.108a(d)	§ 60.108a(a) § 60.108a(b) [G]§ 60.108a(d)
30-B-04	EU	63DDDDD	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7500(a)(1)-Table 3.1 § 63.7500(a)(1) § 63.7500(a)(3) § 63.7505(a) § 63.7540(a) [G]§ 63.7540(a)(10)	A new or existing boiler or process heater with a continuous oxygen trim system that maintains an optimum air to fuel ratio must conduct a tune-up of the boiler or process heater	§ 63.7510(g) § 63.7515(d) § 63.7525(a)(7) § 63.7540(a) [G]§ 63.7540(a)(10)	§ 63.7555(a) § 63.7555(a)(1) § 63.7560(a) § 63.7560(b) § 63.7560(c)	§ 63.7530(e) § 63.7530(f) § 63.7545(a) § 63.7545(b) § 63.7545(c) [G]§ 63.7545(e) § 63.7550(a)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.7540(a)(12) § 63.7540(a)(13)	every 5 years as specified in § 63.7540.			[G]§ 63.7550(b) [G]§ 63.7550(c) [G]§ 63.7550(h)
30-B-05	EU	60Db	NO _x	40 CFR Part 60, Subpart Db	§ 60.44b(l)(1) § 60.44b(h) § 60.44b(i) § 60.46b(a)	Affected facilities combusting coal, oil, or natural gas, or a mixture of these fuels, or any other fuels: a limit of 86 ng/Jl (0.20 lb/million Btu) heat input unless the affected facility meets the specified requirements.	§ 60.46b(c) § 60.46b(e) § 60.46b(e)(1) § 60.46b(e)(3) [G]§ 60.48b(b) § 60.48b(c) § 60.48b(d) § 60.48b(e) [G]§ 60.48b(e)(2) § 60.48b(e)(3) § 60.48b(f)	[G]§ 60.48b(b) § 60.48b(c) [G]§ 60.49b(d) [G]§ 60.49b(g) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3) § 60.49b(b) § 60.49b(h) § 60.49b(i) § 60.49b(v) § 60.49b(w)
30-B-05	EU	60Db	PM	40 CFR Part 60, Subpart Db	§ 60.40b(a)	This subpart applies to each steam generating unit constructed, modified, or reconstructed after 6/19/84, and that has a heat input capacity from fuels combusted in the unit > 29 MW (100 MMBtu/hr).	None	[G]§ 60.49b(d) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3)
30-B-05	EU	60Db	PM (Opacity)	40 CFR Part 60, Subpart Db	§ 60.40b(a)	This subpart applies to each steam generating unit constructed, modified, or reconstructed after 6/19/84, and that has a heat input capacity from fuels combusted in the unit > 29 MW (100 MMBtu/hr).	None	[G]§ 60.49b(d) § 60.49b(o)	§ 60.49b(a) § 60.49b(a)(1) § 60.49b(a)(3)
30-B-05	EU	60Ja-1	Hydrogen Sulfide	40 CFR Part 60, Subpart Ja	§ 60.102a(g)(1)(ii) § 60.102a(a) § 60.102a(g) § 60.102a(g)(1) § 60.103a(c) § 60.103a(d) § 60.103a(d)(1)	For each fuel gas combustion device the owner or operator shall not burn in any fuel gas combustion device any fuel gas that contains H ₂ S in excess of 162 ppmv	§ 60.104a(a) § 60.104a(c) [G]§ 60.104a(j) § 60.107a(a) § 60.107a(a)(2) § 60.107a(a)(2)(i) § 60.107a(a)(2)(ii)	§ 60.108a(a) § 60.108a(c) [G]§ 60.108a(c)(6) [G]§ 60.108a(d)	§ 60.108a(a) § 60.108a(b) [G]§ 60.108a(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.103a(d)(5) [G]§ 60.103a(e)	determined hourly on a 3-hour rolling average basis and H ₂ S in excess of 60 ppmv determined daily on a 365 successive calendar day rolling average basis.	§ 60.107a(a)(2)(iii) § 60.107a(a)(2)(iv) § 60.107a(i) § 60.107a(i)(1)(ii)		
30-B-05	EU	60Ja-2	Hydrogen Sulfide	40 CFR Part 60, Subpart Ja	§ 60.102a(g)(1)(ii) § 60.102a(a) § 60.102a(g) § 60.102a(g)(1) § 60.103a(c) § 60.103a(d) § 60.103a(d)(1) § 60.103a(d)(5) [G]§ 60.103a(e) [G]§ 60.107a(b)	For each fuel gas combustion device the owner or operator shall not burn in any fuel gas combustion device any fuel gas that contains H ₂ S in excess of 162 ppmv determined hourly on a 3-hour rolling average basis and H ₂ S in excess of 60 ppmv determined daily on a 365 successive calendar day rolling average basis.	§ 60.104a(a) § 60.104a(c) [G]§ 60.104a(j) § 60.107a(a)(2)(iv) [G]§ 60.107a(a)(3) § 60.107a(a)(4) § 60.107a(i) § 60.107a(i)(1)(ii) § 60.107a(i)(1)(iii)	§ 60.108a(a) § 60.108a(c) [G]§ 60.108a(c)(6) [G]§ 60.108a(d)	§ 60.108a(a) § 60.108a(b) [G]§ 60.108a(d)
30-B-05	EU	63DDDDD	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7500(a)(1)-Table 3.1 § 63.7500(a)(1) § 63.7500(a)(3) § 63.7505(a) § 63.7540(a) [G]§ 63.7540(a)(10) § 63.7540(a)(12) § 63.7540(a)(13)	A new or existing boiler or process heater with a continuous oxygen trim system that maintains an optimum air to fuel ratio must conduct a tune-up of the boiler or process heater every 5 years as specified in § 63.7540.	§ 63.7510(g) § 63.7515(d) § 63.7525(a)(7) § 63.7540(a) [G]§ 63.7540(a)(10)	§ 63.7555(a) § 63.7555(a)(1) § 63.7560(a) § 63.7560(b) § 63.7560(c)	§ 63.7530(e) § 63.7530(f) § 63.7545(a) § 63.7545(b) § 63.7545(c) [G]§ 63.7545(e) § 63.7550(a) [G]§ 63.7550(b) [G]§ 63.7550(c) [G]§ 63.7550(h)
31-H-01	EU	60Ja	§111 Pollutant	40 CFR Part 60, Subpart Ja	§ 60.100a(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 60,	The permit holder shall comply with the applicable requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 60, Subpart Ja	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 60, Subpart Ja

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					Subpart Ja				
31-H-01	EU	63DDDDD	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
38-H-01	EU	60J	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H ₂ S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
38-H-01	EU	60J-low	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1) § 60.105(a)(4)(iv) § 60.105(a)(4)(iv)(D)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H ₂ S) in excess of 230 mg/dscm (0.10 gr/dscf).	[G]§ 60.105(b) § 60.106(a)	[G]§ 60.105(b) § 60.107(e)	[G]§ 60.105(b) § 60.107(f) § 60.107(g)
38-H-01	EU	63DDDDD	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
38-H-02	EU	60J	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H ₂ S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
38-H-02	EU	60J-low	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1) § 60.105(a)(4)(iv) § 60.105(a)(4)(iv)(D)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H ₂ S) in excess of 230 mg/dscm (0.10 gr/dscf).	[G]§ 60.105(b) § 60.106(a)	[G]§ 60.105(b) § 60.107(e)	[G]§ 60.105(b) § 60.107(f) § 60.107(g)
38-H-02	EU	63DDDDD	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
38-V-54	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(b) § 115.121(b) § 115.122(b)(3)	For all persons in Nueces and Victoria Counties, any vent gas streams affected by §115.121(b) of this title must be controlled properly with a control efficiency of at least 90% or to a VOC concentration of no more than 20 ppmv (on a dry basis corrected to 3.0% oxygen for combustion devices).	[G]§ 115.125 § 115.126(2) ** See Periodic Monitoring Summary	§ 115.126 § 115.126(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
38-V-54	EP	63CC	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC
38-V-55	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(b) § 115.121(b) § 115.122(b)(3)	For all persons in Nueces and Victoria Counties, any vent gas streams affected by §115.121(b) of this title must be controlled properly with a control efficiency of at least 90% or to a VOC concentration of no more than 20 ppmv (on a dry basis corrected to 3.0% oxygen for combustion devices).	[G]§ 115.125 § 115.126(2) ** See Periodic Monitoring Summary	§ 115.126 § 115.126(2)	None
38-V-55	EP	63CC	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC
41-H-07	EU	60J	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						(H2S) in excess of 230 mg/dscm (0.10 gr/dscf).			
44-V-01	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(b) § 115.121(b) § 115.122(b)(2)	For all persons in Nueces and Victoria Counties, any vent gas streams affected by §115.121(b) of this title must be controlled properly with a control efficiency of at least 90% or to a VOC concentration of no more than 20 ppmv (on a dry basis corrected to 3.0% oxygen for combustion devices).	[G]§ 115.125 § 115.126(2) ** See Periodic Monitoring Summary	§ 115.126 § 115.126(2)	None
44-V-01	EP	63CCa	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC
46-H-01	EU	60J	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
46-H-01	EU	63DDDDD	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD		requirements of 40 CFR Part 63, Subpart DDDDD	Part 63, Subpart DDDDD	
47-V-02	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(b) § 115.121(b) § 115.122(b)(3)	For all persons in Nueces and Victoria Counties, any vent gas streams affected by §115.121(b) of this title must be controlled properly with a control efficiency of at least 90% or to a VOC concentration of no more than 20 ppmv (on a dry basis corrected to 3.0% oxygen for combustion devices).	[G]§ 115.125 § 115.126(2) ** See Periodic Monitoring Summary	§ 115.126 § 115.126(2)	None
47-V-02	EP	63CC	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC
48-H-01	EU	60J	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H2S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
48-H-01	EU	60J-AMP	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of	§ 60.106(a) ** See Alternative	None	§ 60.107(d) § 60.107(f)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H ₂ S) in excess of 230 mg/dscm (0.10 gr/dscf).	Requirement		§ 60.107(g)
48-V-01	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(b) § 115.121(b) § 115.122(b)(3)	For all persons in Nueces and Victoria Counties, any vent gas streams affected by §115.121(b) of this title must be controlled properly with a control efficiency of at least 90% or to a VOC concentration of no more than 20 ppmv (on a dry basis corrected to 3.0% oxygen for combustion devices).	[G]§ 115.125 § 115.126(2) ** See Periodic Monitoring Summary	§ 115.126 § 115.126(2)	None
48-V-01	EP	63CC	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC
49-H-91	EU	60J	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H ₂ S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
49-H-91	EU	63DDDDD	112(B)	40 CFR Part 63,	§ 63.7505	The permit holder shall	The permit holder	The permit holder shall	The permit holder shall

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
			HAPS	Subpart DDDDD	The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
49-V-01	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(b) § 115.121(b) § 115.122(b)(2)	For all persons in Nueces and Victoria Counties, any vent gas streams affected by §115.121(b) of this title must be controlled properly with a control efficiency of at least 90% or to a VOC concentration of no more than 20 ppmv (on a dry basis corrected to 3.0% oxygen for combustion devices).	[G]§ 115.125 § 115.126(2) ** See Periodic Monitoring Summary	§ 115.126 § 115.126(2)	None
49-V-01	EP	63CC	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC
49CRU	EU	63UUU	112(B) HAPS	40 CFR Part 63, Subpart UUU	§ 63.1560 The permit holder shall comply with the applicable limitation, standard and/or equipment specification	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart UUU	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63,	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart UUU	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart UUU

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					requirements of 40 CFR Part 63, Subpart UUU		Subpart UUU		
52-H-01	EU	60J	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H ₂ S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
52-H-01	EU	63DDDDDD	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
54F-MTBE	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No pump seal, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
54F-MTBE	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No connector may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
54F-MTBE	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No connector, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
54F-MTBE	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(5)	No pressure relief valve in gaseous service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(C) § 115.324(4) § 115.324(5) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
54F-MTBE	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(5)	No pressure relief valve in gaseous service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
54F-MTBE	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No elevated valve may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(D) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
54F-MTBE	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3)	No elevated valve, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.327(5)	calendar days after the leak is found, except as provided in §115.322(2).			
54F-MTBE	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No compressor seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(A) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
54F-MTBE	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3) § 115.327(6)	No compressor seal, as described in § 115.327(3), (5) or (6), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
54F-MTBE	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No process drain may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(C) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
54F-MTBE	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No process drain, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
54F-MTBE	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No valve in liquid service may be allowed to have a VOC leak as defined in	§ 115.324 § 115.324(1) § 115.324(1)(B)	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.322(4)	§101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	§ 115.326(5)	
54F-MTBE	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No valve in liquid service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
54F-MTBE	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.322(5)	No valve (gaseous service) may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
54F-MTBE	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(5)	No valve (gaseous service), as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
54F-MTBE	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.327(1)	Valves of nominal size of 2" (5 cm) or less are exempt, provided allowable emissions from sources affected by this division after controls are applied with exemptions will not exceed by more than 5.0%	None	None	§ 115.327(1)(A) § 115.327(1)(B) § 115.327(1)(C)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						such allowable emissions with no exemptions.			
54F-MTBE	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No pump seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(A) § 115.324(3) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
54F-MTBE	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-2 [G]§ 60.482-9	Comply with the requirements as stated in §60.482-2 for pumps in light-liquid service.	[G]§ 60.482-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d) § 60.593(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
54F-MTBE	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) § 60.482-3(f) § 60.482-3(g)(1) § 60.482-3(g)(2) [G]§ 60.482-3(i) § 60.482-3(j) [G]§ 60.482-9 § 60.593(c)	Comply with the requirements as stated in §60.482-3 for reciprocating compressors that become subject under §60.14 and §60.15.	§ 60.482-3(f) § 60.482-3(g)(1) § 60.482-3(g)(2) [G]§ 60.482-3(i) § 60.482-3(j) § 60.485(a) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
54F-MTBE	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(d)	Comply with the requirements as stated in §60.482-1(d) for equipment in vacuum service.	None	§ 60.486(e) § 60.486(e)(1) § 60.486(e)(5)	None
54F-MTBE	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b)	Comply with the requirements in as stated in §60.482-8 for pressure relief	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 60.482-8 [G]§ 60.482-9	devices in light-liquid service.	[G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	§ 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(e) § 60.592(e)
54F-MTBE	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for flanges or other connectors.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
54F-MTBE	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for valves in heavy-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
54F-MTBE	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) § 60.482-10(e) [G]§ 60.482-10(g) § 60.482-10(h) § 60.482-10(m)	Comply with the requirements in as stated in §60.482-10 for closed-vent systems.	[G]§ 60.482-10(f) § 60.482-10(i) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.482-10(j) [G]§ 60.482-10(k) [G]§ 60.482-10(l) [G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
54F-MTBE	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.18 § 60.482-1(a) § 60.482-1(b) § 60.482-10(d) § 60.482-10(e) § 60.482-10(m)	Comply with the requirements in as stated in §60.482-10 for flares.	§ 60.485(a) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) [G]§ 60.485(g) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
54F-MTBE	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b)	Comply with the requirements in as stated in §60.482-8 for pumps in	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 60.482-8 [G]§ 60.482-9	heavy-liquid service.	[G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	§ 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(e) § 60.592(e)
54F-MTBE	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-7 [G]§ 60.482-9 [G]§ 60.483-1 [G]§ 60.483-2 § 60.592(b)	Comply with the requirements in as stated in §60.482-7 for valves in gas/vapor or light-liquid service.	[G]§ 60.482-7 [G]§ 60.483-1 [G]§ 60.483-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d) § 60.593(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) [G]§ 60.486(g) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(d) § 60.487(e) § 60.592(e)
54F-MTBE	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-6 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-6 for open-ended valves and lines.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
54F-MTBE	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-5 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-5 for sampling connection systems.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
54F-MTBE	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-4 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-4 for pressure relief devices in gas/vapor service.	[G]§ 60.482-4 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(3) [G]§ 60.486(e)(4) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
54F-MTBE	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-3	Comply with the requirements as stated in §60.482-3 for compressors.	[G]§ 60.482-3 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 60.482-9		[G]§ 60.485(d) § 60.485(f) § 60.592(d)	§ 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.592(e)
54F-MTBE	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC
54F-TAME	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.327(1)	Valves of nominal size of 2" (5 cm) or less are exempt, provided allowable emissions from sources affected by this division after controls are applied with exemptions will not exceed by more than 5.0% such allowable emissions with no exemptions.	None	None	§ 115.327(1)(A) § 115.327(1)(B) § 115.327(1)(C)
54F-TAME	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No pump seal, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
54F-TAME	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No pump seal may be allowed to have a VOC leak as defined in §101.1 for	§ 115.324 § 115.324(1) § 115.324(1)(A)	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324(3) § 115.324(4) § 115.324(6) [G]§ 115.325	§ 115.326(5)	
54F-TAME	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(5)	No valve (gaseous service), as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
54F-TAME	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.322(5)	No valve (gaseous service) may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
54F-TAME	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No valve in liquid service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
54F-TAME	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No valve in liquid service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
54F-TAME	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No process drain, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
54F-TAME	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No process drain may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(C) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
54F-TAME	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3) § 115.327(6)	No compressor seal, as described in § 115.327(3), (5) or (6), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
54F-TAME	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No compressor seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(A) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
54F-TAME	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No elevated valve, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						in §115.322(2).			
54F-TAME	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No elevated valve may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(D) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
54F-TAME	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(5)	No pressure relief valve in gaseous service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
54F-TAME	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(5)	No pressure relief valve in gaseous service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(C) § 115.324(4) § 115.324(5) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
54F-TAME	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No connector, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
54F-TAME	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No connector may be allowed to have a VOC leak as defined in §101.1 for	§ 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						more than 15 calendar days after the leak is found, except as provided in §115.322(2).		§ 115.326(5)	
54F-TAME	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(d)	Comply with the requirements as stated in §60.482-1(d) for equipment in vacuum service.	None	§ 60.486(e) § 60.486(e)(1) § 60.486(e)(5)	None
54F-TAME	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-2 [G]§ 60.482-9	Comply with the requirements as stated in §60.482-2 for pumps in light-liquid service.	[G]§ 60.482-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d) § 60.593(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
54F-TAME	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) § 60.482-3(f) § 60.482-3(g)(1) § 60.482-3(g)(2) [G]§ 60.482-3(i) § 60.482-3(j) [G]§ 60.482-9 § 60.593(c)	Comply with the requirements as stated in §60.482-3 for reciprocating compressors that become subject under §60.14 and §60.15.	§ 60.482-3(f) § 60.482-3(g)(1) § 60.482-3(g)(2) [G]§ 60.482-3(i) § 60.482-3(j) [G]§ 60.485(a) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
54F-TAME	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-3 [G]§ 60.482-9	Comply with the requirements as stated in §60.482-3 for compressors.	[G]§ 60.482-3 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
								§ 60.592(e)	
54F-TAME	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-4 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-4 for pressure relief devices in gas/vapor service.	[G]§ 60.482-4 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(3) [G]§ 60.486(e)(4) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
54F-TAME	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-5 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-5 for sampling connection systems.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
54F-TAME	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-6 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-6 for open-ended valves and lines.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
54F-TAME	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-7 [G]§ 60.482-9 [G]§ 60.483-1 [G]§ 60.483-2 § 60.592(b)	Comply with the requirements in as stated in §60.482-7 for valves in gas/vapor or light-liquid service.	[G]§ 60.482-7 [G]§ 60.483-1 [G]§ 60.483-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d) § 60.593(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) [G]§ 60.486(g) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(d) § 60.487(e) § 60.592(e)
54F-TAME	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for pumps in heavy-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
54F-TAME	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.18 § 60.482-1(a) § 60.482-1(b) § 60.482-10(d) § 60.482-10(e) § 60.482-10(m)	Comply with the requirements in as stated in §60.482-10 for flares.	§ 60.485(a) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) [G]§ 60.485(g) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
54F-TAME	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) § 60.482-10(e) [G]§ 60.482-10(g) § 60.482-10(h) § 60.482-10(m)	Comply with the requirements in as stated in §60.482-10 for closed-vent systems.	[G]§ 60.482-10(f) § 60.482-10(i) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.482-10(j) [G]§ 60.482-10(k) [G]§ 60.482-10(l) [G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
54F-TAME	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for valves in heavy-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
54F-TAME	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for flanges or other connectors.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
54F-TAME	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for pressure relief devices in light-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
54F-TAME	EU	63CCVVALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC
70-TK-137	EU	R5112-b	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(b)(1) § 115.112(b)(2) § 115.112(b)(2)(A) § 115.112(b)(2)(B) § 115.112(b)(2)(C) § 115.112(b)(2)(D) § 115.112(b)(2)(E) § 115.114(b)(1)(A)	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	§ 115.114(b)(1)(A) [G]§ 115.117 ** See Periodic Monitoring Summary	§ 115.118(b)(2) § 115.118(b)(4) § 115.118(b)(5)	§ 115.114(b)(1)(B)
70-TK-137	EU	R5112-c	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(b)(1) § 115.112(b)(2) § 115.112(b)(2)(A) § 115.112(b)(2)(B) § 115.112(b)(2)(C) § 115.112(b)(2)(D) § 115.112(b)(2)(E) § 115.114(b)(1)(A)	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	§ 115.114(b)(1)(A) [G]§ 115.117 ** See Periodic Monitoring Summary	§ 115.118(b)(2) § 115.118(b)(4) § 115.118(b)(5)	§ 115.114(b)(1)(B)
70-TK-137	EU	60K-b	VOC	40 CFR Part 60, Subpart K	§ 60.110(c) § 60.110(c)(2)	Facilities under §60.110(a) of this section with a capacity, construction or modification date as given in §60.110(c)(1) or §60.110(c)(2) are subject to the requirements of this section.	§ 60.113(a) § 60.113(b)	§ 60.113(a)	None
70-TK-137	EU	60K-c	VOC	40 CFR Part 60, Subpart K	§ 60.112(a)(1)	Storage vessels holding petroleum liquids with a true vapor pressure of 78 mm	§ 60.113(a) § 60.113(b) ** See Periodic	§ 60.113(a)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						Hg (1.5 psia) or greater but not greater than 570 mm Hg (11.1 psia) shall have a floating roof, a vapor recovery system, or their equivalents.	Monitoring Summary		
70-TK-137	EU	60K-d	VOC	40 CFR Part 60, Subpart K	§ 60.112(a)(1)	Storage vessels holding petroleum liquids with a true vapor pressure of 78 mm Hg (1.5 psia) or greater but not greater than 570 mm Hg (11.1 psia) shall have a floating roof, a vapor recovery system, or their equivalents.	§ 60.113(a) § 60.113(b) ** See Periodic Monitoring Summary	§ 60.113(a)	None
70-TK-137	EU	63CC	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC
70-TK-138	EU	60K-b	VOC	40 CFR Part 60, Subpart K	§ 60.110(c) § 60.110(c)(2)	Facilities under §60.110(a) of this section with a capacity, construction or modification date as given in §60.110(c)(1) or §60.110(c)(2) are subject to the requirements of this section.	§ 60.113(a) § 60.113(b)	§ 60.113(a)	None
70-TK-140	EU	63GGGG G-1	112(B) HAPS	40 CFR Part 63, Subpart GGGGG	§ 63.7886(b)(1)(i) The permit holder shall comply with the applicable	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart GGGGG	The permit holder shall comply with the applicable monitoring and	The permit holder shall comply with the applicable recordkeeping	The permit holder shall comply with the applicable reporting requirements of 40 CFR

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart GGGGG		testing requirements of 40 CFR Part 63, Subpart GGGGG	requirements of 40 CFR Part 63, Subpart GGGGG	Part 63, Subpart GGGGG
73-TK-168	EU	R5112-d	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(b)(1) § 115.112(b)(2) § 115.112(b)(2)(A) § 115.112(b)(2)(B) § 115.112(b)(2)(C) § 115.112(b)(2)(D) § 115.112(b)(2)(E) § 115.114(b)(1)(A)	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	§ 115.114(b)(1)(A) [G]§ 115.117 ** See Periodic Monitoring Summary	§ 115.118(b)(2) § 115.118(b)(4) § 115.118(b)(5)	§ 115.114(b)(1)(B)
73-TK-168	EU	60Kb-e	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)
73-TK-168	EU	63CC-c	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC
73-TK-9	EU	60KA-b	VOC	40 CFR Part 60, Subpart Ka	§ 60.110a(a)	The affected facility is each storage vessel for	§ 60.115a(a) § 60.115a(b)	§ 60.115a(a)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						petroleum liquids that has a storage capacity > 151,416 L (40,000 gal) and for which construction commenced after 5/18/78 and prior to 7/23/84.			
73-TK-9	EU	63CC	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC
83-TK-155	EU	R5112-b	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(b)(1) § 115.112(b)(2) § 115.112(b)(2)(A) § 115.112(b)(2)(B) § 115.112(b)(2)(C) § 115.112(b)(2)(D) § 115.112(b)(2)(E) § 115.112(b)(2)(F) § 115.114(b)(2)(A) § 115.114(b)(4)(A)	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	§ 115.114(b)(2) § 115.114(b)(3) § 115.114(b)(4) § 115.114(b)(4)(A) [G]§ 115.117	§ 115.118(b)(2) § 115.118(b)(4) § 115.118(b)(5)	§ 115.114(b)(2)(B) § 115.114(b)(4)(B)
83-TK-155	EU	R5112-c	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(b)(1) § 115.112(b)(2) § 115.112(b)(2)(A) § 115.112(b)(2)(B) § 115.112(b)(2)(C) § 115.112(b)(2)(D) § 115.112(b)(2)(E) § 115.112(b)(2)(F) § 115.114(b)(2)(A) § 115.114(b)(4)(A)	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	§ 115.114(b)(2) § 115.114(b)(3) § 115.114(b)(4) § 115.114(b)(4)(A) [G]§ 115.117	§ 115.118(b)(2) § 115.118(b)(4) § 115.118(b)(5)	§ 115.114(b)(2)(B) § 115.114(b)(4)(B)
83-TK-155	EU	60KB-b	VOC	40 CFR Part 60,	[G]§ 60.112b(a)(2)	Storage vessels specified in	[G]§ 60.113b(b)(1)	§ 60.115b	§ 60.113b(b)(4)(iii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Subpart Kb		§60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	[G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	[G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)
83-TK-155	EU	60KB-c	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
83-TK-155	EU	60KB-d	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)
83-TK-155	EU	60QQQ	VOC	40 CFR Part 60, Subpart QQQ	§ 60.692-3(d) § 60.692-1(a) § 60.692-6(a) § 60.692-6(b) § 60.692-7(b)	Storage vessels, including slop oil tanks and other auxiliary tanks that are subject to the requirements of 40 CFR subparts K, Ka, or Kb, are not subject to the requirements of 40 CFR §60.692-3.	§ 60.692-3(a)(4) § 60.696(a)	§ 60.697(a) § 60.697(c) [G]§ 60.697(e) § 60.697(f)(1) [G]§ 60.697(f)(2)	§ 60.698(b)(1) § 60.698(e)
83-TK-155	EU	61FF	Benzene	40 CFR Part 61, Subpart FF	§ 61.351(a) [G]§ 60.112b(a)(2) § 61.351(a)(2) § 61.351(b)	As an alternative to the standards for tanks specified in § 61.343, an owner or operator may elect to comply with one of the following §61.351(a)(1)-(3):	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§	§ 60.115b [G]§ 60.115b(b)(3) § 61.356(k)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 61.357(e) § 61.357(f)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6)		
83-TK-162	EU	R5112-b	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(b)(1) § 115.112(b)(2) § 115.112(b)(2)(A) § 115.112(b)(2)(B) § 115.112(b)(2)(C) § 115.112(b)(2)(D) § 115.112(b)(2)(E) § 115.112(b)(2)(F) § 115.114(b)(2)(A) § 115.114(b)(4)(A)	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	§ 115.114(b)(2) § 115.114(b)(3) § 115.114(b)(4) § 115.114(b)(4)(A) [G]§ 115.117	§ 115.118(b)(2) § 115.118(b)(4) § 115.118(b)(5)	§ 115.114(b)(2)(B) § 115.114(b)(4)(B)
83-TK-162	EU	R5112-c	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(b)(1) § 115.112(b)(2) § 115.112(b)(2)(A) § 115.112(b)(2)(B) § 115.112(b)(2)(C) § 115.112(b)(2)(D) § 115.112(b)(2)(E) § 115.112(b)(2)(F) § 115.114(b)(2)(A) § 115.114(b)(4)(A)	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	§ 115.114(b)(2) § 115.114(b)(3) § 115.114(b)(4) § 115.114(b)(4)(A) [G]§ 115.117	§ 115.118(b)(2) § 115.118(b)(4) § 115.118(b)(5)	§ 115.114(b)(2)(B) § 115.114(b)(4)(B)
83-TK-162	EU	60KB-b	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)		
83-TK-162	EU	60KB-c	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)
83-TK-162	EU	60KB-d	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)		
83-TK-162	EU	60QQQ	VOC	40 CFR Part 60, Subpart QQQ	§ 60.692-3(d) § 60.692-1(a) § 60.692-6(a) § 60.692-6(b) § 60.692-7(b)	Storage vessels, including slop oil tanks and other auxiliary tanks that are subject to the requirements of 40 CFR subparts K, Ka, or Kb, are not subject to the requirements of 40 CFR §60.692-3.	§ 60.692-3(a)(4) § 60.696(a)	§ 60.697(a) § 60.697(c) [G]§ 60.697(e) § 60.697(f)(1) [G]§ 60.697(f)(2)	§ 60.698(b)(1) § 60.698(e)
83-TK-162	EU	61FF	Benzene	40 CFR Part 61, Subpart FF	§ 61.351(a) [G]§ 60.112b(a)(2) § 61.351(a)(2) § 61.351(b)	As an alternative to the standards for tanks specified in § 61.343, an owner or operator may elect to comply with one of the following §61.351(a)(1)-(3):	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6)	§ 60.115b [G]§ 60.115b(b)(3) § 61.356(k)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 61.357(e) § 61.357(f)
83-TK-23	EU	R5112-b	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(b)(1) § 115.112(b)(2) § 115.112(b)(2)(A) § 115.112(b)(2)(B) § 115.112(b)(2)(C) § 115.112(b)(2)(D) § 115.112(b)(2)(E) § 115.112(b)(2)(F)	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	§ 115.114(b)(2) § 115.114(b)(3) § 115.114(b)(4) § 115.114(b)(4)(A) [G]§ 115.117	§ 115.118(b)(2) § 115.118(b)(4) § 115.118(b)(5)	§ 115.114(b)(2)(B) § 115.114(b)(4)(B)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.114(b)(2)(A) § 115.114(b)(4)(A)				
83-TK-23	EU	R5112-c	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(b)(1) § 115.112(b)(2) § 115.112(b)(2)(A) § 115.112(b)(2)(B) § 115.112(b)(2)(C) § 115.112(b)(2)(D) § 115.112(b)(2)(E) § 115.112(b)(2)(F) § 115.114(b)(2)(A) § 115.114(b)(4)(A)	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	§ 115.114(b)(2) § 115.114(b)(3) § 115.114(b)(4) § 115.114(b)(4)(A) [G]§ 115.117	§ 115.118(b)(2) § 115.118(b)(4) § 115.118(b)(5)	§ 115.114(b)(2)(B) § 115.114(b)(4)(B)
83-TK-23	EU	60KA-b	VOC	40 CFR Part 60, Subpart Ka	§ 60.110a(a)	The affected facility is each storage vessel for petroleum liquids that has a storage capacity > 151,416 L (40,000 gal) and for which construction commenced after 5/18/78 and prior to 7/23/84.	§ 60.115a(a) § 60.115a(b)	§ 60.115a(a)	None
83-TK-23	EU	60KA-c	VOC	40 CFR Part 60, Subpart Ka	§ 60.112a(a)(1) § 60.112a(a)(1)(i) § 60.112a(a)(1)(i)(A) § 60.112a(a)(1)(i)(C) § 60.112a(a)(1)(i)(D) § 60.112a(a)(1)(ii)(A) § 60.112a(a)(1)(ii)(B) § 60.112a(a)(1)(ii)(C) § 60.112a(a)(1)(ii)(D) § 60.112a(a)(1)(iii) § 60.112a(a)(1)(iv)	Vessels storing petroleum liquids with a TVP > 10.3 kPa (1.5 psia) but < 76.6 kPa (11.1 psia) shall be equipped with an external floating roof and closure device as specified.	§ 60.113a(a)(1) § 60.113a(a)(1)(i) § 60.113a(a)(1)(i)(A) § 60.113a(a)(1)(i)(B) § 60.113a(a)(1)(i)(C) § 60.113a(a)(1)(i)(D) § 60.113a(a)(1)(i)(E) § 60.113a(a)(1)(ii)(A) § 60.113a(a)(1)(ii)(B) § 60.113a(a)(1)(ii)(C)	§ 60.113a(a)(1)(i)(D) § 60.115a(a)	§ 60.113a(a)(1)(i)(E) § 60.113a(a)(1)(iv)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 60.113a(a)(1)(iii) § 60.113a(a)(1)(iv) § 60.115a(a) § 60.115a(b)		
83-TK-23	EU	60KA-d	VOC	40 CFR Part 60, Subpart Ka	§ 60.112a(a)(1) § 60.112a(a)(1)(i) § 60.112a(a)(1)(i)(A) § 60.112a(a)(1)(i)(C) § 60.112a(a)(1)(i)(D) § 60.112a(a)(1)(ii)(A) § 60.112a(a)(1)(ii)(B) § 60.112a(a)(1)(ii)(C) § 60.112a(a)(1)(ii)(D) § 60.112a(a)(1)(iii) § 60.112a(a)(1)(iv)	Vessels storing petroleum liquids with a TVP > 10.3 kPa (1.5 psia) but < 76.6 kPa (11.1 psia) shall be equipped with an external floating roof and closure device as specified.	§ 60.113a(a)(1) § 60.113a(a)(1)(i) § 60.113a(a)(1)(i)(A) § 60.113a(a)(1)(i)(B) § 60.113a(a)(1)(i)(C) § 60.113a(a)(1)(i)(D) § 60.113a(a)(1)(i)(E) § 60.113a(a)(1)(ii)(A) § 60.113a(a)(1)(ii)(B) § 60.113a(a)(1)(ii)(C) § 60.113a(a)(1)(iii) § 60.113a(a)(1)(iv) § 60.115a(a) § 60.115a(b)	§ 60.113a(a)(1)(i)(D) § 60.115a(a)	§ 60.113a(a)(1)(i)(E) § 60.113a(a)(1)(iv)
83-TK-23	EU	60QQQ	VOC	40 CFR Part 60, Subpart QQQ	§ 60.692-3(d) § 60.692-1(a) § 60.692-6(a) § 60.692-6(b) § 60.692-7(b)	Storage vessels, including slop oil tanks and other auxiliary tanks that are subject to the requirements of 40 CFR subparts K, Ka, or Kb, are not subject to the requirements of 40 CFR §60.692-3.	§ 60.692-3(a)(4) § 60.696(a)	§ 60.697(a) § 60.697(c) [G]§ 60.697(e) § 60.697(f)(1) [G]§ 60.697(f)(2)	§ 60.698(b)(1) § 60.698(e)
83-TK-25	EU	R5112-a	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(b)(1) § 115.112(b)(2) § 115.112(b)(2)(A) § 115.112(b)(2)(B)	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the	§ 115.114(b)(2) § 115.114(b)(3) § 115.114(b)(4) § 115.114(b)(4)(A)	§ 115.118(b)(2) § 115.118(b)(4) § 115.118(b)(5)	§ 115.114(b)(2)(B) § 115.114(b)(4)(B)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.112(b)(2)(C) § 115.112(b)(2)(D) § 115.112(b)(2)(E) § 115.112(b)(2)(F) § 115.114(b)(2)(A) § 115.114(b)(4)(A)	appropriate control device specified in Table I(a) or Table II(a).	[G]§ 115.117		
83-TK-25	EU	60KA-b	VOC	40 CFR Part 60, Subpart Ka	§ 60.110a(a)	The affected facility is each storage vessel for petroleum liquids that has a storage capacity > 151,416 L (40,000 gal) and for which construction commenced after 5/18/78 and prior to 7/23/84.	§ 60.115a(a) § 60.115a(b)	§ 60.115a(a)	None
83-TK-25	EU	61FF	Benzene	40 CFR Part 61, Subpart FF	§ 61.351(a) [G]§ 60.112b(a)(2) § 61.351(a)(2) § 61.351(b)	As an alternative to the standards for tanks specified in § 61.343, an owner or operator may elect to comply with one of the following §61.351(a)(1)-(3):	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6)	§ 60.115b [G]§ 60.115b(b)(3) § 61.356(k)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 61.357(e) § 61.357(f)
83-TK-26	EU	R5112-b	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(b)(1) § 115.112(b)(2) § 115.112(b)(2)(A) § 115.112(b)(2)(B) § 115.112(b)(2)(C) § 115.112(b)(2)(D) § 115.112(b)(2)(E) § 115.112(b)(2)(F) § 115.114(b)(2)(A) § 115.114(b)(4)(A)	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	§ 115.114(b)(2) § 115.114(b)(3) § 115.114(b)(4) § 115.114(b)(4)(A) [G]§ 115.117	§ 115.118(b)(2) § 115.118(b)(4) § 115.118(b)(5)	§ 115.114(b)(2)(B) § 115.114(b)(4)(B)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
83-TK-26	EU	R5112-c	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(b)(1) § 115.112(b)(2) § 115.112(b)(2)(A) § 115.112(b)(2)(B) § 115.112(b)(2)(C) § 115.112(b)(2)(D) § 115.112(b)(2)(E) § 115.112(b)(2)(F) § 115.114(b)(2)(A) § 115.114(b)(4)(A)	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	§ 115.114(b)(2) § 115.114(b)(3) § 115.114(b)(4) § 115.114(b)(4)(A) [G]§ 115.117	§ 115.118(b)(2) § 115.118(b)(4) § 115.118(b)(5)	§ 115.114(b)(2)(B) § 115.114(b)(4)(B)
83-TK-26	EU	60KB-b	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)
83-TK-26	EU	60KB-c	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)		
83-TK-26	EU	60KB-d	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)
83-TK-26	EU	63CC	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					specification requirements of 40 CFR Part 63, Subpart CC		CFR Part 63, Subpart CC		
83-TK-26	EU	63CC-b	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC
83-V-97	EU	R5112-b	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(b)(1) § 115.112(b)(2) § 115.112(b)(2)(A) § 115.112(b)(2)(B) § 115.112(b)(2)(C) § 115.112(b)(2)(D) § 115.112(b)(2)(E) § 115.112(b)(2)(F) § 115.114(b)(2)(A) § 115.114(b)(4)(A)	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	§ 115.114(b)(2) § 115.114(b)(3) § 115.114(b)(4) § 115.114(b)(4)(A) [G]§ 115.117	§ 115.118(b)(2) § 115.118(b)(4) § 115.118(b)(5)	§ 115.114(b)(2)(B) § 115.114(b)(4)(B)
83-V-97	EU	R5112-c	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(b)(1) § 115.112(b)(2) § 115.112(b)(2)(A) § 115.112(b)(2)(B) § 115.112(b)(2)(C) § 115.112(b)(2)(D) § 115.112(b)(2)(E) § 115.112(b)(2)(F) § 115.114(b)(2)(A) § 115.114(b)(4)(A)	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	§ 115.114(b)(2) § 115.114(b)(3) § 115.114(b)(4) § 115.114(b)(4)(A) [G]§ 115.117	§ 115.118(b)(2) § 115.118(b)(4) § 115.118(b)(5)	§ 115.114(b)(2)(B) § 115.114(b)(4)(B)
83-V-97	EU	60KB-b	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						(pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	§ 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.116b(b) § 60.116b(c)	§ 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)
83-V-97	EU	60KB-c	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)
83-V-97	EU	60KB-d	VOC	40 CFR Part 60,	[G]§ 60.112b(a)(2)	Storage vessels specified in	[G]§ 60.113b(b)(1)	§ 60.115b	§ 60.113b(b)(4)(iii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Subpart Kb		§60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	[G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	[G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)
83-V-97	EU	60QQQ	VOC	40 CFR Part 60, Subpart QQQ	§ 60.692-3(d) § 60.692-1(a) § 60.692-6(a) § 60.692-6(b) § 60.692-7(b)	Storage vessels, including slop oil tanks and other auxiliary tanks that are subject to the requirements of 40 CFR subparts K, Ka, or Kb, are not subject to the requirements of 40 CFR §60.692-3.	§ 60.692-3(a)(4) § 60.696(a)	§ 60.697(a) § 60.697(c) [G]§ 60.697(e) § 60.697(f)(1) [G]§ 60.697(f)(2)	§ 60.698(b)(1) § 60.698(e)
83-V-97	EU	61FF	Benzene	40 CFR Part 61, Subpart FF	§ 61.351(a) [G]§ 60.112b(a)(2) § 61.351(a)(2) § 61.351(b)	As an alternative to the standards for tanks specified in § 61.343, an owner or operator may elect to comply with one of the following §61.351(a)(1)-(3):	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii)	§ 60.115b [G]§ 60.115b(b)(3) § 61.356(k)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 61.357(e) § 61.357(f)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6)		
83-V-98	EU	R5112-b	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(b)(1) § 115.112(b)(2) § 115.112(b)(2)(A) § 115.112(b)(2)(B) § 115.112(b)(2)(C) § 115.112(b)(2)(D) § 115.112(b)(2)(E) § 115.114(b)(1)(A)	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	§ 115.114(b)(1)(A) [G]§ 115.117 ** See Periodic Monitoring Summary	§ 115.118(b)(2) § 115.118(b)(4) § 115.118(b)(5)	§ 115.114(b)(1)(B)
83-V-98	EU	R5112-c	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(b)(1) § 115.112(b)(2) § 115.112(b)(2)(A) § 115.112(b)(2)(B) § 115.112(b)(2)(C) § 115.112(b)(2)(D) § 115.112(b)(2)(E) § 115.114(b)(1)(A)	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	§ 115.114(b)(1)(A) [G]§ 115.117 ** See Periodic Monitoring Summary	§ 115.118(b)(2) § 115.118(b)(4) § 115.118(b)(5)	§ 115.114(b)(1)(B)
83-V-98	EU	60KB-b	VOC	40 CFR Part 60, Subpart Kb	§ 60.110b(a)	Except for §60.110b(b), this subpart applies to vessels with a capacity greater than or equal to 75 cubic meters (19,800 gal) used to store VOLs for which construction/reconstruction/modification began after 7/23/84.	§ 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(d) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.116b(d)
83-V-98	EU	60KB-c	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(B) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) [G]§ 60.113b(a)(3) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)		§ 60.116b(e)(2)(i)		
83-V-98	EU	60KB-d	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(B) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) [G]§ 60.113b(a)(3) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(4)
83-V-98	EU	61FF	Benzene	40 CFR Part 61, Subpart FF	§ 61.351(a) § 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(B) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii) § 61.351(a)(1) § 61.351(b)	As an alternative to the standards for tanks specified in § 61.343, an owner or operator may elect to comply with one of the following §61.351(a)(1)-(3):	§ 60.113b(a)(1) [G]§ 60.113b(a)(3) § 60.113b(a)(4) § 60.113b(a)(5)	§ 60.115b § 60.115b(a)(2) § 61.356(k)	§ 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(4) § 61.357(e) § 61.357(f)
83-V-98	EU	63CC	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
83P136A-EN	EU	60III-3	CO	40 CFR Part 60, Subpart IIII	§ 60.4205(b) § 60.4202(a)(2) § 60.4206 § 60.4207(b) § 60.4211(c) [G]§ 60.4211(f) § 60.4211(g) § 60.4211(g)(2) § 60.4218 § 89.112(a)	Owners and operators of emergency stationary CI ICE, that are not fire pump engines, with a maximum engine power greater than or equal to 130 KW and less than or equal to 2237 KW and a displacement of less than 10 liters per cylinder and is a 2007 model year and later must comply with a CO emission limit of 3.5 g/KW-hr, as stated in 40 CFR 60.4202(a)(2) and 40 CFR 89.112(a).	§ 60.4209(a) § 60.4211(g)(2) [G]§ 60.4212	§ 60.4211(g)(2) § 60.4214(b)	[G]§ 60.4214(d)
83P136A-EN	EU	60III-3	NMHC and NO _x	40 CFR Part 60, Subpart IIII	§ 60.4205(b) § 60.4202(a)(2) § 60.4206 § 60.4207(b) § 60.4211(c) [G]§ 60.4211(f) § 60.4211(g) § 60.4211(g)(2) § 60.4218 § 89.112(a)	Owners and operators of emergency stationary CI ICE, that are not fire pump engines, with a maximum engine power greater than or equal to 75 KW and less than or equal to 560 KW and a displacement of less than 10 liters per cylinder and is a 2007 model year and later must comply with an NMHC+NO _x emission limit of 4.0 g/KW-hr, as stated in 40 CFR 60.4202(a)(2) and 40 CFR 89.112(a).	§ 60.4209(a) § 60.4211(g)(2) [G]§ 60.4212	§ 60.4211(g)(2) § 60.4214(b)	[G]§ 60.4214(d)
83P136A-EN	EU	60III-3	PM	40 CFR Part 60, Subpart IIII	§ 60.4205(b) § 60.4202(a)(2) § 60.4206 § 60.4207(b) § 60.4211(c) [G]§ 60.4211(f) § 60.4211(g)	Owners and operators of emergency stationary CI ICE, that are not fire pump engines, with a maximum engine power greater than or equal to 130 KW and less than or equal to 2237 KW	§ 60.4209(a) § 60.4211(g)(2) [G]§ 60.4212	§ 60.4211(g)(2) § 60.4214(b)	[G]§ 60.4214(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.4211(g)(2) § 60.4218 § 89.112(a)	and a displacement of less than 10 liters per cylinder and is a 2007 model year and later must comply with a PM emission limit of 0.20 g/KW-hr, as stated in 40 CFR 60.4202(a)(2) and 40 CFR 89.112(a).			
83P136A-EN	EU	60IIII-3	PM (Opacity)	40 CFR Part 60, Subpart IIII	§ 60.4205(b) § 60.4202(a)(2) § 60.4206 § 60.4207(b) § 60.4211(c) [G]§ 60.4211(f) § 60.4211(g) § 60.4211(g)(2) § 60.4218 § 89.113(a)(1) § 89.113(a)(2) § 89.113(a)(3)	Emergency stationary CI ICE, that are not fire pump engines, with displacement < 10 lpc and not constant-speed engines, with max engine power < 2237 KW and a 2007 model year and later or max engine power > 2237 KW and a 2011 model year and later, must comply with following opacity emission limits: 20% during acceleration, 15% during lugging, 50% during peaks in either acceleration or lugging modes as stated in §60.4202(a)(1)-(2), (b)(2) and §89.113(a)(1)-(3) and §1039.105(b)(1)-(3).	§ 60.4209(a) § 60.4211(g)(2) [G]§ 60.4212	§ 60.4211(g)(2) § 60.4214(b)	[G]§ 60.4214(d)
83P136A-EN	EU	63ZZZZ-3	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(c)	Stationary RICE subject to Regulations under 40 CFR Part 60. An affected source that meets any of the criteria in paragraphs (c)(1) through (7) of this section must meet the requirements of this part by meeting the requirements of 40 CFR part 60 subpart IIII, for compression ignition	None	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						engines or 40 CFR part 60 subpart JJJJ, for spark ignition engines as applicable. No further requirements apply for such engines under this part.			
83P136B-EN	EU	60III-3	CO	40 CFR Part 60, Subpart IIII	§ 60.4205(b) § 60.4202(a)(2) § 60.4206 § 60.4207(b) § 60.4211(c) [G]§ 60.4211(f) § 60.4211(g) § 60.4211(g)(2) § 60.4218 § 89.112(a)	Owners and operators of emergency stationary CI ICE, that are not fire pump engines, with a maximum engine power greater than or equal to 130 KW and less than or equal to 2237 KW and a displacement of less than 10 liters per cylinder and is a 2007 model year and later must comply with a CO emission limit of 3.5 g/KW-hr, as stated in 40 CFR 60.4202(a)(2) and 40 CFR 89.112(a).	§ 60.4209(a) § 60.4211(g)(2) [G]§ 60.4212	§ 60.4211(g)(2) § 60.4214(b)	[G]§ 60.4214(d)
83P136B-EN	EU	60III-3	NMHC and NO _x	40 CFR Part 60, Subpart IIII	§ 60.4205(b) § 60.4202(a)(2) § 60.4206 § 60.4207(b) § 60.4211(c) [G]§ 60.4211(f) § 60.4211(g) § 60.4211(g)(2) § 60.4218 § 89.112(a)	Owners and operators of emergency stationary CI ICE, that are not fire pump engines, with a maximum engine power greater than or equal to 75 KW and less than or equal to 560 KW and a displacement of less than 10 liters per cylinder and is a 2007 model year and later must comply with an NMHC+NO _x emission limit of 4.0 g/KW-hr, as stated in 40 CFR 60.4202(a)(2) and 40 CFR 89.112(a).	§ 60.4209(a) § 60.4211(g)(2) [G]§ 60.4212	§ 60.4211(g)(2) § 60.4214(b)	[G]§ 60.4214(d)
83P136B-	EU	60III-3	PM	40 CFR Part 60,	§ 60.4205(b)	Owners and operators of	§ 60.4209(a)	§ 60.4211(g)(2)	[G]§ 60.4214(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
EN				Subpart IIII	§ 60.4202(a)(2) § 60.4206 § 60.4207(b) § 60.4211(c) [G]§ 60.4211(f) § 60.4211(g) § 60.4211(g)(2) § 60.4218 § 89.112(a)	emergency stationary CI ICE, that are not fire pump engines, with a maximum engine power greater than or equal to 130 KW and less than or equal to 2237 KW and a displacement of less than 10 liters per cylinder and is a 2007 model year and later must comply with a PM emission limit of 0.20 g/KW-hr, as stated in 40 CFR 60.4202(a)(2) and 40 CFR 89.112(a).	§ 60.4211(g)(2) [G]§ 60.4212	§ 60.4214(b)	
83P136B-EN	EU	60IIII-3	PM (Opacity)	40 CFR Part 60, Subpart IIII	§ 60.4205(b) § 60.4202(a)(2) § 60.4206 § 60.4207(b) § 60.4211(c) [G]§ 60.4211(f) § 60.4211(g) § 60.4211(g)(2) § 60.4218 § 89.113(a)(1) § 89.113(a)(2) § 89.113(a)(3)	Emergency stationary CI ICE, that are not fire pump engines, with displacement < 10 lpc and not constant-speed engines, with max engine power < 2237 KW and a 2007 model year and later or max engine power > 2237 KW and a 2011 model year and later, must comply with following opacity emission limits: 20% during acceleration, 15% during lugging, 50% during peaks in either acceleration or lugging modes as stated in §60.4202(a)(1)-(2), (b)(2) and §89.113(a)(1)-(3) and §1039.105(b)(1)-(3).	§ 60.4209(a) § 60.4211(g)(2) [G]§ 60.4212	§ 60.4211(g)(2) § 60.4214(b)	[G]§ 60.4214(d)
83P136B-EN	EU	63ZZZZ-3	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(c)	Stationary RICE subject to Regulations under 40 CFR Part 60. An affected source that meets any of the criteria in paragraphs (c)(1)	None	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						through (7) of this section must meet the requirements of this part by meeting the requirements of 40 CFR part 60 subpart IIII, for compression ignition engines or 40 CFR part 60 subpart JJJJ, for spark ignition engines as applicable. No further requirements apply for such engines under this part.			
APISEP	EU	R5131	VOC	30 TAC Chapter 115, Water Separation	§ 115.132(b)(3) § 115.131(b)	VOC water separator compartments must be equipped with a vapor recovery system which satisfies the provisions of §115.131(b) of this title.	[G]§ 115.135(b) § 115.136(b)(3) § 115.136(b)(4) ** See Periodic Monitoring Summary	§ 115.136(b)(3) § 115.136(b)(4)	None
APISEP	EU	60QQQ	VOC	40 CFR Part 60, Subpart QQQ	§ 60.692-3(a) § 60.692-1(a) § 60.692-3(a)(1) § 60.692-3(a)(2) § 60.692-3(a)(3) § 60.692-3(a)(5) § 60.692-3(b) § 60.692-3(e) § 60.692-5(a) § 60.692-5(d) [G]§ 60.692-5(e) § 60.692-6(a) § 60.692-6(b) § 60.692-7(b)	Except as noted, each oil-water separator tank, slop oil tank, storage vessel, or other auxiliary equipment shall be equipped with fixed roof, meeting following specifications:	§ 60.692-3(a)(4) § 60.695(a) § 60.695(a)(1) § 60.696(a)	§ 60.695(a)(1) § 60.697(a) § 60.697(c) § 60.697(d) [G]§ 60.697(e) § 60.697(f)(1) [G]§ 60.697(f)(2) § 60.697(f)(3) § 60.697(f)(3)(i) § 60.697(f)(3)(iii) § 60.697(f)(3)(iv) § 60.697(f)(3)(v) § 60.697(f)(3)(vi) § 60.697(f)(3)(vii) § 60.697(f)(3)(viii)	§ 60.698(b)(1) § 60.698(d) § 60.698(d)(1) § 60.698(e)
APISEP	EU	60FF-a	Benzene	40 CFR Part 61, Subpart FF	§ 61.347(a)(1) § 61.347(a)(1)(i)(A) § 61.347(a)(1)(i)(B) § 61.347(b) § 61.347(c)	Install, operate, and maintain a fixed-roof and closed-vent system that routes all organic vapors vented from the oil-water	§ 61.347(a)(1)(i)(A) § 61.347(b) § 61.349(a)(1)(i) § 61.349(e) § 61.349(f)	§ 61.354(c) § 61.354(c)(1) § 61.356(d) § 61.356(f) § 61.356(f)(1)	§ 61.357(d)(7) § 61.357(d)(7)(iv) § 61.357(d)(7)(iv)(A)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(i)(C) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	separator to a control device.	§ 61.354(c) § 61.354(c)(1) [G]§ 61.355(h)	§ 61.356(f)(2) § 61.356(f)(2)(i) § 61.356(f)(2)(i)(A) § 61.356(g) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(2) § 61.356(j)(3) § 61.356(j)(4)	
BARGEDOC KS	EU	61BB	Benzene	40 CFR Part 61, Subpart BB	§ 61.300(b)	Any affected facility as per § 61.300(a), loading only liquid containing < 70 weight-percent benzene is exempt from this subpart, except for the recordkeeping and reporting in § 61.305(i).	None	[G]§ 61.305(i)	[G]§ 61.305(i)
BARGEDOC KS	EU	63CC	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC
BARGEDOC KS	EU	63Ya	Exempt	40 CFR Part 63, Subpart Y	§ 63.560(a)(2) § 153.282 § 63.560(a)(4)	Existing sources with emissions less than 10 and 25 tons must meet the submerged fill standards of 46 CFR 153.282. This submerged fill requirement does not apply to petroleum refineries.	§ 63.565(l)	§ 63.567(j)(4)	None
BARGEDOC	EU	63Yb	112(B)	40 CFR Part 63,	§ 63.562(b)	Marine tank vessel loading	[G]§ 63.562(b)(6)	[G]§ 63.562(b)(6)	[G]§ 63.562(b)(6)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
KS			HAPS	Subpart Y	[G]§ 63.562(b)(1) § 63.562(b)(2) § 63.562(b)(5) [G]§ 63.562(b)(6) § 63.562(e) § 63.562(e)(1) [G]§ 63.562(e)(2) [G]§ 63.562(e)(3) § 63.562(e)(4) § 63.562(e)(5) § 63.562(e)(6) § 63.562(e)(7) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) [G]§ 63.563(a)(1) § 63.563(a)(2) § 63.563(a)(3)	operations shall apply MACT standards, except for the VMT source.	[G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) § 63.563(b)(10) § 63.563(b)(3) § 63.563(b)(6) § 63.563(b)(6)(i) § 63.563(b)(6)(iii) [G]§ 63.563(c) § 63.564(a)(2) § 63.564(a)(3) § 63.564(a)(4) § 63.564(b)(3) § 63.564(c) [G]§ 63.565(b) § 63.565(l)	§ 63.562(e)(5) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) § 63.564(b)(3) § 63.567(f) [G]§ 63.567(g) § 63.567(j)(1) § 63.567(j)(2) [G]§ 63.567(k)	§ 63.562(e)(7)(ii) § 63.567(b)(5) § 63.567(c) § 63.567(e)(1) [G]§ 63.567(e)(2) § 63.567(e)(3) § 63.567(e)(4) § 63.567(e)(5) § 63.567(e)(6) § 63.567(f) § 63.567(j)(3) § 63.567(m) § 63.567(n)(1) § 63.567(n)(2)
BARGEDOC KS	EU	63Yb	VOC	40 CFR Part 63, Subpart Y	§ 63.562(c) [G]§ 63.562(c)(2) § 63.562(c)(3) § 63.562(c)(4) [G]§ 63.562(c)(6) § 63.562(e) § 63.562(e)(1) [G]§ 63.562(e)(2) [G]§ 63.562(e)(3) § 63.562(e)(4) § 63.562(e)(5) § 63.562(e)(6) § 63.562(e)(7) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) [G]§ 63.563(a)(1) § 63.563(a)(2) § 63.563(a)(3)	RACT standards, except the VMT source.	[G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) § 63.563(b)(3) § 63.563(b)(6) § 63.563(b)(6)(i) § 63.563(b)(6)(iii) [G]§ 63.563(c) § 63.564(a)(2) § 63.564(a)(3) § 63.564(a)(4) § 63.564(b)(3) § 63.564(c) [G]§ 63.565(b) § 63.565(l)	§ 63.562(e)(5) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) § 63.564(b)(3) § 63.567(f) [G]§ 63.567(g) § 63.567(j)(1) [G]§ 63.567(k)	§ 63.562(c)(1) § 63.562(e)(7)(ii) [G]§ 63.567(b)(2) § 63.567(b)(3) [G]§ 63.567(b)(4) § 63.567(c) § 63.567(e)(1) [G]§ 63.567(e)(2) § 63.567(e)(3) § 63.567(e)(4) § 63.567(e)(5) § 63.567(e)(6) § 63.567(f) § 63.567(m) § 63.567(n)(1) § 63.567(n)(2)
BUTAMER	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b)	Comply with the requirements in as stated in §60.482-6 for open-ended	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 60.482-6 [G]§ 60.482-9	valves and lines.	§ 60.485(f) § 60.592(d)	§ 60.486(j) § 60.592(e)	§ 60.487(e) § 60.592(e)
BUTAMER	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-7 [G]§ 60.482-9 [G]§ 60.483-1 [G]§ 60.483-2 § 60.592(b)	Comply with the requirements in as stated in §60.482-7 for valves in gas/vapor or light-liquid service.	[G]§ 60.482-7 [G]§ 60.483-1 [G]§ 60.483-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d) § 60.593(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) [G]§ 60.486(g) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(d) § 60.487(e) § 60.592(e)
BUTAMER	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for pumps in heavy-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
BUTAMER	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.18 § 60.482-1(a) § 60.482-1(b) § 60.482-10(d) § 60.482-10(e) § 60.482-10(m)	Comply with the requirements in as stated in §60.482-10 for flares.	§ 60.485(a) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) [G]§ 60.485(g) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
BUTAMER	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) § 60.482-10(e) [G]§ 60.482-10(g) § 60.482-10(h) § 60.482-10(m)	Comply with the requirements in as stated in §60.482-10 for closed-vent systems.	[G]§ 60.482-10(f) § 60.482-10(i) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.482-10(j) [G]§ 60.482-10(k) [G]§ 60.482-10(l) [G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
BUTAMER	EU	60GGGAL	VOC	40 CFR Part 60,	§ 60.592(a)	Comply with the	[G]§ 60.482-8	[G]§ 60.486(a)	§ 60.487(a)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		L		Subpart GGG	§ 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	requirements in as stated in §60.482-8 for valves in heavy-liquid service.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	[G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
BUTAMER	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for flanges or other connectors.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
BUTAMER	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for pressure relief devices in light-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
BUTAMER	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-5 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-5 for sampling connection systems.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
BUTAMER	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-4 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-4 for pressure relief devices in gas/vapor service.	[G]§ 60.482-4 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(3) [G]§ 60.486(e)(4) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
BUTAMER	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-3	Comply with the requirements as stated in §60.482-3 for compressors.	[G]§ 60.482-3 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 60.482-9		[G]§ 60.485(d) § 60.485(f) § 60.592(d)	§ 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.592(e)
BUTAMER	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) § 60.482-3(f) § 60.482-3(g)(1) § 60.482-3(g)(2) [G]§ 60.482-3(i) § 60.482-3(j) [G]§ 60.482-9 § 60.593(c)	Comply with the requirements as stated in §60.482-3 for reciprocating compressors that become subject under §60.14 and §60.15.	§ 60.482-3(f) § 60.482-3(g)(1) § 60.482-3(g)(2) [G]§ 60.482-3(i) § 60.482-3(j) § 60.485(a) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
BUTAMER	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-2 [G]§ 60.482-9	Comply with the requirements as stated in §60.482-2 for pumps in light-liquid service.	[G]§ 60.482-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d) § 60.593(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
BUTAMER	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(d)	Comply with the requirements as stated in §60.482-1(d) for equipment in vacuum service.	None	§ 60.486(e) § 60.486(e)(1) § 60.486(e)(5)	None
BWS	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No pump seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(A) § 115.324(3) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
BWS	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No pump seal, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
BWS	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.322(5)	No valve (gaseous service) may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
BWS	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No valve in liquid service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
BWS	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No valve in liquid service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
BWS	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No process drain, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						is found, except as provided in §115.322(2).			
BWS	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No process drain may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(C) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
BWS	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3) § 115.327(6)	No compressor seal, as described in § 115.327(3), (5) or (6), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
BWS	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No compressor seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(A) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
BWS	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No elevated valve, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
BWS	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No elevated valve may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days	§ 115.324 § 115.324(1) § 115.324(1)(D) § 115.324(4)	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						after the leak is found, except as provided in §115.322(2).	§ 115.324(6) [G]§ 115.324(7) [G]§ 115.325		
BWS	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(5)	No pressure relief valve in gaseous service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
BWS	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(5)	No pressure relief valve in gaseous service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(C) § 115.324(4) § 115.324(5) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
BWS	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No connector, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
BWS	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No connector may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
BWS	EU	R5322-	VOC	30 TAC Chapter	§ 115.327(1)	Valves of nominal size of 2"	None	None	§ 115.327(1)(A)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		ALL		115, Fugitives Pet Ref B Counties		(5 cm) or less are exempt, provided allowable emissions from sources affected by this division after controls are applied with exemptions will not exceed by more than 5.0% such allowable emissions with no exemptions.			§ 115.327(1)(B) § 115.327(1)(C)
BWS	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(5)	No valve (gaseous service), as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
BWS	EU	60GGGaV Va	VOC	40 CFR Part 60, Subpart GGGa	[G]§ 60.590a(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 60, Subpart GGGa	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 60, Subpart GGGa
BWS	EU	63CCH-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
CD-LOADING	EU	63CC	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC
CD-PIPING	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No pump seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(A) § 115.324(3) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
CD-PIPING	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(5)	No valve (gaseous service), as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
CD-PIPING	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.322(5)	No valve (gaseous service) may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
CD-PIPING	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No valve in liquid service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.327(3) § 115.327(5)	as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).			
CD-PIPING	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No valve in liquid service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
CD-PIPING	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No process drain, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
CD-PIPING	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No process drain may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(C) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
CD-PIPING	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3) § 115.327(6)	No compressor seal, as described in § 115.327(3), (5) or (6), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
CD-PIPING	EU	R5322ALL	VOC	30 TAC Chapter	§ 115.322(1)	No compressor seal may be	§ 115.324	[G]§ 115.326(1)	[G]§ 115.326(1)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				115, Fugitives Pet Ref B Counties	§ 115.322(2) § 115.322(3)	allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324(2) § 115.324(2)(A) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	§ 115.327(4)
CD-PIPING	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No elevated valve, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
CD-PIPING	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No elevated valve may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(D) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
CD-PIPING	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(5)	No pressure relief valve in gaseous service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
CD-PIPING	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(5)	No pressure relief valve in gaseous service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in	§ 115.324 § 115.324(2) § 115.324(2)(C) § 115.324(4) § 115.324(5) § 115.324(6) [G]§ 115.324(7)	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						§115.322(2).	[G]§ 115.325		
CD-PIPING	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No connector, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
CD-PIPING	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No connector may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
CD-PIPING	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.327(1)	Valves of nominal size of 2" (5 cm) or less are exempt, provided allowable emissions from sources affected by this division after controls are applied with exemptions will not exceed by more than 5.0% such allowable emissions with no exemptions.	None	None	§ 115.327(1)(A) § 115.327(1)(B) § 115.327(1)(C)
CD-PIPING	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No pump seal, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
CD-PIPING	EU	63CCVVALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder	The permit holder shall comply with the applicable	The permit holder shall comply with	The permit holder shall comply with the	The permit holder shall comply with the

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	requirements of 40 CFR Part 63, Subpart CC	the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	applicable reporting requirements of 40 CFR Part 63, Subpart CC
DEGREASE -F	EU	R5412	VOC	30 TAC Chapter 115, Degreasing Processes	§ 115.411(5)	In Gregg, Nueces, and Victoria Counties, degreasing operations located on any property that can emit, when uncontrolled, a combined weight of VOC < 550 pounds in any consecutive 24-hour period are exempt from §115.412 of this title.	None	§ 115.416 § 115.416(3)	None
FUELDRM	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.327(1)	Valves of nominal size of 2" (5 cm) or less are exempt, provided allowable emissions from sources affected by this division after controls are applied with exemptions will not exceed by more than 5.0% such allowable emissions with no exemptions.	None	None	§ 115.327(1)(A) § 115.327(1)(B) § 115.327(1)(C)
FUELDRM	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No connector may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
FUELDRM	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet	§ 115.322(1) § 115.322(2)	No pump seal may be allowed to have a VOC leak	§ 115.324 § 115.324(1)	[G]§ 115.326(1) [G]§ 115.326(2)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Ref B Counties	§ 115.322(3)	as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324(1)(A) § 115.324(3) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(3) § 115.326(5)	
FUELDRM	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(5)	No valve (gaseous service), as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
FUELDRM	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.322(5)	No valve (gaseous service) may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
FUELDRM	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No valve in liquid service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
FUELDRM	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No valve in liquid service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
FUELDRM	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No process drain, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
FUELDRM	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No process drain may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(C) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
FUELDRM	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3) § 115.327(6)	No compressor seal, as described in § 115.327(3), (5) or (6), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
FUELDRM	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No compressor seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(A) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
FUELDRM	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No elevated valve, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						in §115.322(2).			
FUELDRM	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No elevated valve may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(D) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
FUELDRM	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(5)	No pressure relief valve in gaseous service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
FUELDRM	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(5)	No pressure relief valve in gaseous service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(C) § 115.324(4) § 115.324(5) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
FUELDRM	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No connector, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
FUELDRM	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No pump seal, as described in § 115.327(3) or (5), may be allowed to have a VOC	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.327(3)	leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).			
GDFUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No connector, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GDFUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No connector may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GDFUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No valve in liquid service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
GDFUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No valve in liquid service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GDFUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.322(5)	No valve (gaseous service) may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
GDFUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(5)	No valve (gaseous service), as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GDFUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No pump seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(A) § 115.324(3) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GDFUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No pump seal, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GDFUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.327(1)	Valves of nominal size of 2" (5 cm) or less are exempt, provided allowable emissions from sources affected by this division after controls are applied	None	None	§ 115.327(1)(A) § 115.327(1)(B) § 115.327(1)(C)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						with exemptions will not exceed by more than 5.0% such allowable emissions with no exemptions.			
GDFUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(5)	No pressure relief valve in gaseous service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(C) § 115.324(4) § 115.324(5) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
GDFUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(5)	No pressure relief valve in gaseous service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GDFUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No elevated valve may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(D) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
GDFUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No elevated valve, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GDFUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No compressor seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(A) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GDFUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3) § 115.327(6)	No compressor seal, as described in § 115.327(3), (5) or (6), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GDFUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No process drain may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(C) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GDFUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No process drain, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GDFUG	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-7 [G]§ 60.482-9 [G]§ 60.483-1 [G]§ 60.483-2	Comply with the requirements in as stated in §60.482-7 for valves in gas/vapor or light-liquid service.	[G]§ 60.482-7 [G]§ 60.483-1 [G]§ 60.483-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(d) § 60.487(e) § 60.592(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.592(b)		[G]§ 60.485(e) § 60.485(f) § 60.592(d) § 60.593(d)	[G]§ 60.486(f) [G]§ 60.486(g) § 60.486(j) § 60.592(e)	
GDFUG	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for pressure relief devices in light-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GDFUG	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.18 § 60.482-1(a) § 60.482-1(b) § 60.482-10(d) § 60.482-10(e) § 60.482-10(m)	Comply with the requirements in as stated in §60.482-10 for flares.	§ 60.485(a) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) [G]§ 60.485(g) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GDFUG	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) § 60.482-10(e) [G]§ 60.482-10(g) § 60.482-10(h) § 60.482-10(m)	Comply with the requirements in as stated in §60.482-10 for closed-vent systems.	[G]§ 60.482-10(f) § 60.482-10(i) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.482-10(j) [G]§ 60.482-10(k) [G]§ 60.482-10(l) [G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GDFUG	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for pumps in heavy-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GDFUG	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(d)	Comply with the requirements as stated in §60.482-1(d) for equipment	None	§ 60.486(e) § 60.486(e)(1) § 60.486(e)(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						in vacuum service.			
GDFUG	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-2 [G]§ 60.482-9	Comply with the requirements as stated in §60.482-2 for pumps in light-liquid service.	[G]§ 60.482-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d) § 60.593(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GDFUG	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) § 60.482-3(f) § 60.482-3(g)(1) § 60.482-3(g)(2) [G]§ 60.482-3(i) § 60.482-3(j) [G]§ 60.482-9 § 60.593(c)	Comply with the requirements as stated in §60.482-3 for reciprocating compressors that become subject under §60.14 and §60.15.	§ 60.482-3(f) § 60.482-3(g)(1) § 60.482-3(g)(2) [G]§ 60.482-3(i) § 60.482-3(j) § 60.485(a) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GDFUG	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-3 [G]§ 60.482-9	Comply with the requirements as stated in §60.482-3 for compressors.	[G]§ 60.482-3 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GDFUG	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-4 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-4 for pressure relief devices in gas/vapor service.	[G]§ 60.482-4 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(3) [G]§ 60.486(e)(4) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 60.592(d)	§ 60.592(e)	
GDFUG	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-5 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-5 for sampling connection systems.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GDFUG	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-6 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-6 for open-ended valves and lines.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GDFUG	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for flanges or other connectors.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GDFUG	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for valves in heavy-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GDFUG	EU	63CCHALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GDFUG	EU	63CCHAL L	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) § 63.162(e) [G]§ 63.162(g) § 63.162(h)	Comply with the specified Subpart H requirements for equipment operated in organic HAP service < 300 hours per year.	[G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(i) § 63.181(j) § 63.648(h) § 63.654(d)(1)(i) § 63.654(d)(5) [G]§ 63.654(e) § 63.654(i)(4)	[G]§ 63.182(a) [G]§ 63.654(e)
GF-1	EU	R1111	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(4)(A)	Visible emissions from a process gas flare shall not be permitted for more than five minutes in any two-hour period, except for upset emissions as provided in §101.222(b).	§ 111.111(a)(4)(A)(i) § 111.111(a)(4)(A)(ii)	§ 111.111(a)(4)(A)(ii)	None
GF-1	CD	60A	Opacity	40 CFR Part 60, Subpart A	§ 60.18(b) § 60.18(c)(1) § 60.18(c)(2) § 60.18(c)(3)(ii) § 60.18(c)(4)(iii) § 60.18(c)(6) § 60.18(e)	Flares shall comply with paragraphs (c)-(f) of § 60.18.	§ 60.18(d) § 60.18(f)(1) § 60.18(f)(2) § 60.18(f)(3) § 60.18(f)(4) § 60.18(f)(5)	None	None
GF-1	EU	60Ja	H2S	40 CFR Part 60, Subpart Ja	§ 60.103a(h) [G]§ 60.103a(b) § 60.103a(c) [G]§ 60.103a(c)(1) [G]§ 60.103a(d) [G]§ 60.103a(e) § 60.103a(f)	Each owner or operator shall not burn in any affected flare any fuel gas that contains H2S in excess of 162 ppmv determined hourly on a 3-hour rolling average basis. The combustion in a flare of process upset gases or fuel gas that is released to the flare as a result of relief valve leakage or other emergency malfunctions is exempt from this limit.	§ 60.104a(a) § 60.104a(c) § 60.104a(j) [G]§ 60.104a(j)(4) [G]§ 60.107a(a)(2) § 60.107a(e) [G]§ 60.107a(e)(1) [G]§ 60.107a(e)(2) § 60.107a(f) [G]§ 60.107a(f)(1)	[G]§ 60.103a(a) [G]§ 60.103a(e)(3) [G]§ 60.107a(a)(2) § 60.107a(e)(1) § 60.107a(e)(2) § 60.107a(f) § 60.107a(f)(1)(iii) § 60.108a(c) § 60.108a(c)(1) [G]§ 60.108a(c)(6) § 60.108a(c)(7) [G]§ 60.108a(d)	[G]§ 60.103a(b) § 60.107a(i) [G]§ 60.107a(i)(2) [G]§ 60.108a(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GF-1	CD	63A	112(B) HAPS	40 CFR Part 63, Subpart A	§ 63.11(b)(4) § 63.11(b)(1) § 63.11(b)(2) § 63.11(b)(3) § 63.11(b)(5) § 63.11(b)(6)(ii) § 63.11(b)(7)(iii)	Flares shall be designed and operated with no visible emissions, except for periods of a total of 5 minutes or less during any 2 consecutive hrs. Test Method 22 in App. A of part 60 of this chapter shall be used.	§ 63.11(b)(4) § 63.11(b)(5) § 63.11(b)(7)(i)	None	None
GRP-49HTR	EU	60J	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H ₂ S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
GRP-49HTR	EU	60J-low	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1) § 60.105(a)(4)(iv) § 60.105(a)(4)(iv)(C)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H ₂ S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.106(a)	§ 60.107(e)	§ 60.107(f) § 60.107(g)
GRP-49HTR	EU	63DDDDD	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
GRP-5GCCVV	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet	§ 115.322(1) § 115.322(2)	No pressure relief valve in gaseous service may be	§ 115.324 § 115.324(2)	[G]§ 115.326(1) [G]§ 115.326(2)	[G]§ 115.324(7) [G]§ 115.326(1)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Ref B Counties	§ 115.322(3) § 115.322(5)	allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324(2)(C) § 115.324(4) § 115.324(5) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(3) § 115.326(5)	§ 115.327(4)
GRP-5GCCVV	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No connector, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-5GCCVV	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No connector may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-5GCCVV	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No process drain, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-5GCCVV	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No process drain may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(C) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-5GCCVV	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3) § 115.327(6)	No compressor seal, as described in § 115.327(3), (5) or (6), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-5GCCVV	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No compressor seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(A) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-5GCCVV	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No elevated valve, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-5GCCVV	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No elevated valve may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(D) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
GRP-5GCCVV	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(5)	No pressure relief valve in gaseous service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						is found, except as provided in §115.322(2).			
GRP-5GCCVV	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.327(1)	Valves of nominal size of 2" (5 cm) or less are exempt, provided allowable emissions from sources affected by this division after controls are applied with exemptions will not exceed by more than 5.0% such allowable emissions with no exemptions.	None	None	§ 115.327(1)(A) § 115.327(1)(B) § 115.327(1)(C)
GRP-5GCCVV	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No pump seal, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-5GCCVV	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No pump seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(A) § 115.324(3) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-5GCCVV	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(5)	No valve (gaseous service), as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-5GCCVV	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.322(5)	No valve (gaseous service) may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
GRP-5GCCVV	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No valve in liquid service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-5GCCVV	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No valve in liquid service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
GRP-5GCCVV	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(d)	Comply with the requirements as stated in §60.482-1(d) for equipment in vacuum service.	None	§ 60.486(e) § 60.486(e)(1) § 60.486(e)(5)	None
GRP-5GCCVV	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-2 [G]§ 60.482-9	Comply with the requirements as stated in §60.482-2 for pumps in light-liquid service.	[G]§ 60.482-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d) § 60.593(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-5GCCVV	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for pressure relief devices in light-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-5GCCVV	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for flanges or other connectors.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-5GCCVV	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for valves in heavy-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-5GCCVV	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) § 60.482-10(e) [G]§ 60.482-10(g) § 60.482-10(h) § 60.482-10(m)	Comply with the requirements in as stated in §60.482-10 for closed-vent systems.	[G]§ 60.482-10(f) § 60.482-10(i) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.482-10(j) [G]§ 60.482-10(k) [G]§ 60.482-10(l) [G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-5GCCVV	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.18 § 60.482-1(a) § 60.482-1(b) § 60.482-10(d) § 60.482-10(e) § 60.482-10(m)	Comply with the requirements in as stated in §60.482-10 for flares.	§ 60.485(a) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) [G]§ 60.485(g) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-5GCCVV	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for pumps in heavy-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-5GCCVV	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-7 [G]§ 60.482-9 [G]§ 60.483-1 [G]§ 60.483-2 § 60.592(b)	Comply with the requirements in as stated in §60.482-7 for valves in gas/vapor or light-liquid service.	[G]§ 60.482-7 [G]§ 60.483-1 [G]§ 60.483-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d) § 60.593(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) [G]§ 60.486(g) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(d) § 60.487(e) § 60.592(e)
GRP-5GCCVV	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-6 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-6 for open-ended valves and lines.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-5GCCVV	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-5 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-5 for sampling connection systems.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-5GCCVV	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) § 60.482-3(f) § 60.482-3(g)(1) § 60.482-3(g)(2) [G]§ 60.482-3(i) § 60.482-3(j) [G]§ 60.482-9	Comply with the requirements as stated in §60.482-3 for reciprocating compressors that become subject under §60.14 and §60.15.	§ 60.482-3(f) § 60.482-3(g)(1) § 60.482-3(g)(2) [G]§ 60.482-3(i) § 60.482-3(j) § 60.485(a) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.593(c)		§ 60.592(d)	§ 60.592(e)	
GRP-5GCCVV	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-3 [G]§ 60.482-9	Comply with the requirements as stated in §60.482-3 for compressors.	[G]§ 60.482-3 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-5GCCVV	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-4 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-4 for pressure relief devices in gas/vapor service.	[G]§ 60.482-4 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(3) [G]§ 60.486(e)(4) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-5GCCVV	EU	63CCVVALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC
GRP-BLR-DB	EU	60J	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H ₂ S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-EPN118	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(b) § 115.121(b) § 115.122(b)(3)	For all persons in Nueces and Victoria Counties, any vent gas streams affected by §115.121(b) of this title must be controlled properly with a control efficiency of at least 90% or to a VOC concentration of no more than 20 ppmv (on a dry basis corrected to 3.0% oxygen for combustion devices).	[G]§ 115.125 § 115.126(2) ** See Periodic Monitoring Summary	§ 115.126 § 115.126(2)	None
GRP-EPN118	EP	R5121a	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(b) § 115.121(b) § 115.122(b)(3)	For all persons in Nueces and Victoria Counties, any vent gas streams affected by §115.121(b) of this title must be controlled properly with a control efficiency of at least 90% or to a VOC concentration of no more than 20 ppmv (on a dry basis corrected to 3.0% oxygen for combustion devices).	[G]§ 115.125 § 115.126(2) ** See Periodic Monitoring Summary	§ 115.126 § 115.126(2)	None
GRP-EPN121	EP	R1151	PM	30 TAC Chapter 111, Nonagricultural Processes	§ 111.151(a) § 111.151(c)	No person may cause, suffer, allow, or permit emissions of particulate matter from any source to exceed the allowable rates specified in Table 1 as follows, except as provided by §111.153 of this title (relating to Emissions Limits for Steam Generators).	** See CAM Summary	None	None
GRP-EPN121	EP	R1111	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(B) § 111.111(a)(1)(E) § 111.111(a)(3)	Visible emissions from any stationary vent shall not exceed an opacity of 20% averaged over a six minute	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						period for any source on which construction was begun after January 31, 1972.	Summary		
GRP-EPN126A	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(b) § 115.121(b) § 115.122(b)(2)	For all persons in Nueces and Victoria Counties, any vent gas streams affected by §115.121(b) of this title must be controlled properly with a control efficiency of at least 90% or to a VOC concentration of no more than 20 ppmv (on a dry basis corrected to 3.0% oxygen for combustion devices).	[G]§ 115.125 § 115.126(2) ** See Periodic Monitoring Summary	§ 115.126 § 115.126(2)	None
GRP-EPN126A	EP	63CC	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC
GRP-EPN126B	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(b) § 115.121(b) § 115.122(b)(2)	For all persons in Nueces and Victoria Counties, any vent gas streams affected by §115.121(b) of this title must be controlled properly with a control efficiency of at least 90% or to a VOC concentration of no more than 20 ppmv (on a dry basis corrected to 3.0% oxygen for combustion devices).	[G]§ 115.125 § 115.126(2) ** See Periodic Monitoring Summary	§ 115.126 § 115.126(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-EPN126B	EP	R5121a	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(b) § 115.121(b) § 115.122(b)(3)	For all persons in Nueces and Victoria Counties, any vent gas streams affected by §115.121(b) of this title must be controlled properly with a control efficiency of at least 90% or to a VOC concentration of no more than 20 ppmv (on a dry basis corrected to 3.0% oxygen for combustion devices).	[G]§ 115.125 § 115.126(2) ** See Periodic Monitoring Summary	§ 115.126 § 115.126(2)	None
GRP-EPN126B	EP	63CCa	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC
GRP-EPN126B	EP	63CCb	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC
GRP-EPN135	EP	R5121	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(b) § 115.121(b) § 115.122(b)(2)	For all persons in Nueces and Victoria Counties, any vent gas streams affected by §115.121(b) of this title must be controlled properly with a control efficiency of at	[G]§ 115.125 § 115.126(2) ** See Periodic Monitoring Summary	§ 115.126 § 115.126(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						least 90% or to a VOC concentration of no more than 20 ppmv (on a dry basis corrected to 3.0% oxygen for combustion devices).			
GRP-EPN135	EP	63CCa	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC
GRP-ERLQA	EU	R5112-b	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(b)(1) § 115.112(b)(2) § 115.112(b)(2)(A) § 115.112(b)(2)(B) § 115.112(b)(2)(C) § 115.112(b)(2)(D) § 115.112(b)(2)(E) § 115.112(b)(2)(F) § 115.114(b)(2)(A) § 115.114(b)(4)(A)	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	§ 115.114(b)(2) § 115.114(b)(3) § 115.114(b)(4) § 115.114(b)(4)(A) [G]§ 115.117	§ 115.118(b)(2) § 115.118(b)(4) § 115.118(b)(5)	§ 115.114(b)(2)(B) § 115.114(b)(4)(B)
GRP-ERLQA	EU	R5112-c	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(b)(1) § 115.112(b)(2) § 115.112(b)(2)(A) § 115.112(b)(2)(B) § 115.112(b)(2)(C) § 115.112(b)(2)(D) § 115.112(b)(2)(E) § 115.112(b)(2)(F) § 115.114(b)(2)(A) § 115.114(b)(4)(A)	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	§ 115.114(b)(2) § 115.114(b)(3) § 115.114(b)(4) § 115.114(b)(4)(A) [G]§ 115.117	§ 115.118(b)(2) § 115.118(b)(4) § 115.118(b)(5)	§ 115.114(b)(2)(B) § 115.114(b)(4)(B)
GRP-	EU	60KB-b	VOC	40 CFR Part 60,	§ 60.110b(a)	Except for §60.110b(b), this	§ 60.116b(a)	§ 60.116b(a)	§ 60.116b(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
ERLQA				Subpart Kb		subpart applies to vessels with a capacity greater than or equal to 75 cubic meters (19,800 gal) used to store VOLs for which construction/reconstruction/modification began after 7/23/84.	§ 60.116b(b) § 60.116b(c) § 60.116b(d) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.116b(b) § 60.116b(c)	
GRP-ERLQA	EU	60KB-c	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)
GRP-ERLQA	EU	60KB-d	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)		
GRP-ERLQA	EU	61FF	Benzene	40 CFR Part 61, Subpart FF	§ 61.351(a) [G]§ 60.112b(a)(2) § 61.351(a)(2) § 61.351(b)	As an alternative to the standards for tanks specified in § 61.343, an owner or operator may elect to comply with one of the following §61.351(a)(1)-(3):	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) [G]§ 60.113b(b)(6)	§ 60.115b [G]§ 60.115b(b)(3) § 61.356(k)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4) § 61.357(e) § 61.357(f)
GRP-ERLQA	EU	63CC	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC
GRP-HTR	EU	60J	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						device any fuel gas that contains hydrogen sulfide (H ₂ S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.106(a) [G]§ 60.106(e)(1)		
GRP-HTR	EU	63DDDDD	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD
GRP-HTRJ	EU	60J	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H ₂ S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(ii) § 60.105(a)(4)(iii) § 60.106(a) [G]§ 60.106(e)(1)	§ 60.105(a)(4) § 60.105(a)(4)(i) § 60.105(a)(4)(iii)	§ 60.105(e)(3)(ii) § 60.107(d) § 60.107(f) § 60.107(g)
GRP-HTRJ	EU	60J-AMP	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H ₂ S) in excess of 230 mg/dscm (0.10 gr/dscf).	§ 60.106(a) ** See Alternative Requirement	None	§ 60.107(d) § 60.107(f) § 60.107(g)
GRP-HTRJ	EU	63DDDDD	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7505 The permit holder shall comply with the applicable limitation, standard and/or equipment specification	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63,	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart DDDDD	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart DDDDD

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					requirements of 40 CFR Part 63, Subpart DDDDD		Subpart DDDDD		
GRP-IRMTBQ	EU	R5112-b	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(b)(1) § 115.112(b)(2) § 115.112(b)(2)(A) § 115.112(b)(2)(B) § 115.112(b)(2)(C) § 115.112(b)(2)(D) § 115.112(b)(2)(E) § 115.114(b)(1)(A)	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	§ 115.114(b)(1)(A) [G]§ 115.117 ** See Periodic Monitoring Summary	§ 115.118(b)(2) § 115.118(b)(4) § 115.118(b)(5)	§ 115.114(b)(1)(B)
GRP-IRMTBQ	EU	R5112-c	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(b)(1) § 115.112(b)(2) § 115.112(b)(2)(A) § 115.112(b)(2)(B) § 115.112(b)(2)(C) § 115.112(b)(2)(D) § 115.112(b)(2)(E) § 115.114(b)(1)(A)	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	§ 115.114(b)(1)(A) [G]§ 115.117 ** See Periodic Monitoring Summary	§ 115.118(b)(2) § 115.118(b)(4) § 115.118(b)(5)	§ 115.114(b)(1)(B)
GRP-IRMTBQ	EU	60KB-b	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)
GRP-IRMTBQ	EU	60KB-c	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)		§ 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)		
GRP-IRMTBQ	EU	60KB-d	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)
GRP-IRMTBQ	EU	61FF	Benzene	40 CFR Part 61, Subpart FF	§ 61.351(a) § 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(A) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii) § 61.351(a)(1) § 61.351(b)	As an alternative to the standards for tanks specified in § 61.343, an owner or operator may elect to comply with one of the following §61.351(a)(1)-(3):	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5)	§ 60.115b § 60.115b(a)(2) § 61.356(k)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3) § 61.357(e) § 61.357(f)
GRP-IRMTBQ	EU	63CC	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63,	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					Subpart CC				
GRP-IRMTBQ	EU	63CC-b	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC
GRP-NNN	EP	60NNNa	VOC/TOC	40 CFR Part 60, Subpart NNN	§ 60.662(a)	Affected facilities shall reduce TOC emissions by 98 weight-percent or to a concentration of 20ppmv, whichever is less stringent. Introduce the stream into the flame zone of a boiler/process heater.	§ 60.663(f)	§ 60.665(b) § 60.665(p)	§ 60.663(f) § 60.665(a) § 60.665(b) § 60.665(k) § 60.665(l) § 60.665(p)
GRP-NNN	EP	60NNNb	VOC/TOC	40 CFR Part 60, Subpart NNN	§ 60.662(b) § 60.18	Each affected facility shall combust the emissions in a flare that meets the requirements of § 60.18.	§ 60.663(b) § 60.663(b)(1) § 60.663(b)(2) § 60.664(a) § 60.664(d) [G]§ 60.664(e)	§ 60.663(b)(2) § 60.665(b) § 60.665(b)(3) § 60.665(d) § 60.665(f)	§ 60.665(a) § 60.665(b) § 60.665(b)(3) § 60.665(k) § 60.665(l) § 60.665(l)(2) § 60.665(l)(4)
GRP-R5-1	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No valve in liquid service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-R5-1	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No valve in liquid service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
GRP-R5-1	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No compressor seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(A) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5-1	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No elevated valve, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5-1	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No elevated valve may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(D) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
GRP-R5-1	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(5)	No pressure relief valve in gaseous service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						in §115.322(2).			
GRP-R5-1	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(5)	No pressure relief valve in gaseous service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(C) § 115.324(4) § 115.324(5) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
GRP-R5-1	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.327(1)	Valves of nominal size of 2" (5 cm) or less are exempt, provided allowable emissions from sources affected by this division after controls are applied with exemptions will not exceed by more than 5.0% such allowable emissions with no exemptions.	None	None	§ 115.327(1)(A) § 115.327(1)(B) § 115.327(1)(C)
GRP-R5-1	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No pump seal, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5-1	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No pump seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(A) § 115.324(3) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5-1	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet	§ 115.322(1) § 115.322(2)	No valve (gaseous service), as described in §	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Ref B Counties	§ 115.322(3) § 115.322(4) § 115.327(5)	115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).			
GRP-R5-1	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.322(5)	No valve (gaseous service) may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
GRP-R5-1	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No connector, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5-1	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No connector may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5-1	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No process drain, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-R5-1	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No process drain may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(C) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5-1	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3) § 115.327(6)	No compressor seal, as described in § 115.327(3), (5) or (6), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5-2	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No connector, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5-2	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(5)	No valve (gaseous service), as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5-2	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No pump seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found,	§ 115.324 § 115.324(1) § 115.324(1)(A) § 115.324(3) § 115.324(4)	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						except as provided in §115.322(2).	§ 115.324(6) [G]§ 115.325		
GRP-R5-2	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No pump seal, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5-2	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.327(1)	Valves of nominal size of 2" (5 cm) or less are exempt, provided allowable emissions from sources affected by this division after controls are applied with exemptions will not exceed by more than 5.0% such allowable emissions with no exemptions.	None	None	§ 115.327(1)(A) § 115.327(1)(B) § 115.327(1)(C)
GRP-R5-2	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(5)	No pressure relief valve in gaseous service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(C) § 115.324(4) § 115.324(5) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
GRP-R5-2	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(5)	No pressure relief valve in gaseous service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-R5-2	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No elevated valve may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(D) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
GRP-R5-2	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No elevated valve, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5-2	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No compressor seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(A) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5-2	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No valve in liquid service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
GRP-R5-2	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No valve in liquid service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						§115.322(2).			
GRP-R5-2	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3) § 115.327(6)	No compressor seal, as described in § 115.327(3), (5) or (6), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5-2	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No process drain may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(C) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5-2	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No process drain, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5-2	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No connector may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5-2	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.322(5)	No valve (gaseous service) may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak	§ 115.324 § 115.324(2) § 115.324(2)(B) § 115.324(4) § 115.324(6)	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						is found, except as provided in §115.322(2).	[G]§ 115.324(7) [G]§ 115.325		
GRP-R5CC	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(5)	No valve (gaseous service), as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5CC	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(5)	No pressure relief valve in gaseous service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5CC	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(5)	No pressure relief valve in gaseous service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(C) § 115.324(4) § 115.324(5) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
GRP-R5CC	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No connector may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5CC	EU	R5322ALL	VOC	30 TAC Chapter	§ 115.322(1)	No process drain, as	[G]§ 115.325	[G]§ 115.326(1)	[G]§ 115.326(1)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				115, Fugitives Pet Ref B Counties	§ 115.322(2) § 115.322(3) § 115.327(3)	described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).		§ 115.326(5)	§ 115.327(4)
GRP-R5CC	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No process drain may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(C) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5CC	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.327(1)	Valves of nominal size of 2" (5 cm) or less are exempt, provided allowable emissions from sources affected by this division after controls are applied with exemptions will not exceed by more than 5.0% such allowable emissions with no exemptions.	None	None	§ 115.327(1)(A) § 115.327(1)(B) § 115.327(1)(C)
GRP-R5CC	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3) § 115.327(6)	No compressor seal, as described in § 115.327(3), (5) or (6), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5CC	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No connector, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						after the leak is found, except as provided in §115.322(2).			
GRP-R5CC	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No pump seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(A) § 115.324(3) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5CC	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No elevated valve may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(D) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
GRP-R5CC	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No elevated valve, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5CC	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.322(5)	No valve (gaseous service) may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
GRP-R5CC	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No compressor seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days	§ 115.324 § 115.324(2) § 115.324(2)(A) § 115.324(4)	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						after the leak is found, except as provided in §115.322(2).	§ 115.324(6) [G]§ 115.325		
GRP-R5CC	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No pump seal, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5CC	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No valve in liquid service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
GRP-R5CC	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No valve in liquid service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5CC	EU	63CCHALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) § 63.162(e) [G]§ 63.162(g) § 63.162(h)	Comply with the specified Subpart H requirements for equipment operated in organic HAP service < 300 hours per year.	[G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(i) § 63.181(j) § 63.648(h) § 63.654(d)(1)(i) § 63.654(d)(5) [G]§ 63.654(e) § 63.654(i)(4)	[G]§ 63.182(a) [G]§ 63.654(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-R5CC	EU	63CCHALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC
GRP-R5CC2	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(5)	No pressure relief valve in gaseous service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5CC2	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(5)	No valve (gaseous service), as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5CC2	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No elevated valve may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(D) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
GRP-R5CC2	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet	§ 115.322(1) § 115.322(2)	No compressor seal may be allowed to have a VOC leak	§ 115.324 § 115.324(2)	[G]§ 115.326(1) [G]§ 115.326(2)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Ref B Counties	§ 115.322(3)	as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324(2)(A) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(3) § 115.326(5)	
GRP-R5CC2	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.322(5)	No valve (gaseous service) may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
GRP-R5CC2	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No elevated valve, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5CC2	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No pump seal, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5CC2	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No connector, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-R5CC2	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3) § 115.327(6)	No compressor seal, as described in § 115.327(3), (5) or (6), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5CC2	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(5)	No pressure relief valve in gaseous service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(C) § 115.324(4) § 115.324(5) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
GRP-R5CC2	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No process drain, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5CC2	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No valve in liquid service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
GRP-R5CC2	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No pump seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in	§ 115.324 § 115.324(1) § 115.324(1)(A) § 115.324(3) § 115.324(4) § 115.324(6)	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						§115.322(2).	[G]§ 115.325		
GRP-R5CC2	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No connector may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5CC2	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No valve in liquid service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5CC2	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.327(1)	Valves of nominal size of 2" (5 cm) or less are exempt, provided allowable emissions from sources affected by this division after controls are applied with exemptions will not exceed by more than 5.0% such allowable emissions with no exemptions.	None	None	§ 115.327(1)(A) § 115.327(1)(B) § 115.327(1)(C)
GRP-R5CC2	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No process drain may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(C) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5CC2	EU	63CCHALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder	The permit holder shall comply with the applicable	The permit holder shall comply with	The permit holder shall comply with the	The permit holder shall comply with the

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	requirements of 40 CFR Part 63, Subpart CC	the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	applicable reporting requirements of 40 CFR Part 63, Subpart CC
GRP-R5CC2	EU	63CCHALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 63.162(a) § 63.162(c) § 63.162(e) [G]§ 63.162(g) § 63.162(h)	Comply with the specified Subpart H requirements for equipment operated in organic HAP service < 300 hours per year.	[G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(i) § 63.181(j) § 63.648(h) § 63.654(d)(1)(i) § 63.654(d)(5) [G]§ 63.654(e) § 63.654(i)(4)	[G]§ 63.182(a) [G]§ 63.654(e)
GRP-R5G	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.322(5)	No valve (gaseous service) may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
GRP-R5G	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No connector, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5G	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No connector may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days	§ 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						after the leak is found, except as provided in §115.322(2).			
GRP-R5G	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No process drain, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5G	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No process drain may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(C) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5G	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3) § 115.327(6)	No compressor seal, as described in § 115.327(3), (5) or (6), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5G	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No valve in liquid service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5G	EU	R5322ALL	VOC	30 TAC Chapter	§ 115.322(1)	No valve in liquid service	§ 115.324	[G]§ 115.326(1)	[G]§ 115.324(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				115, Fugitives Pet Ref B Counties	§ 115.322(2) § 115.322(3) § 115.322(4)	may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324(1) § 115.324(1)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5G	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No compressor seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(A) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5G	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No elevated valve, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5G	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No elevated valve may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(D) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
GRP-R5G	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(5)	No pressure relief valve in gaseous service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-R5G	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(5)	No pressure relief valve in gaseous service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(C) § 115.324(4) § 115.324(5) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
GRP-R5G	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.327(1)	Valves of nominal size of 2" (5 cm) or less are exempt, provided allowable emissions from sources affected by this division after controls are applied with exemptions will not exceed by more than 5.0% such allowable emissions with no exemptions.	None	None	§ 115.327(1)(A) § 115.327(1)(B) § 115.327(1)(C)
GRP-R5G	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No pump seal, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5G	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No pump seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(A) § 115.324(3) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-R5G	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No valve (gaseous service), as described in § 115.327(3) or (5), may be allowed to have a VOC leak	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.327(5)	as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).			
GRP-R5G	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(d)	Comply with the requirements as stated in §60.482-1(d) for equipment in vacuum service.	None	§ 60.486(e) § 60.486(e)(1) § 60.486(e)(5)	None
GRP-R5G	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-2 [G]§ 60.482-9	Comply with the requirements as stated in §60.482-2 for pumps in light-liquid service.	[G]§ 60.482-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d) § 60.593(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-R5G	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for pressure relief devices in light-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-R5G	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for flanges or other connectors.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-R5G	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b)	Comply with the requirements as stated in §60.482-3 for reciprocating	§ 60.482-3(f) § 60.482-3(g)(1) § 60.482-3(g)(2)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.482-3(f) § 60.482-3(g)(1) § 60.482-3(g)(2) [G]§ 60.482-3(i) § 60.482-3(j) [G]§ 60.482-9 § 60.593(c)	compressors that become subject under §60.14 and §60.15.	[G]§ 60.482-3(i) § 60.482-3(j) § 60.485(a) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	§ 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(e) § 60.592(e)
GRP-R5G	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-3 [G]§ 60.482-9	Comply with the requirements as stated in §60.482-3 for compressors.	[G]§ 60.482-3 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-R5G	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-4 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-4 for pressure relief devices in gas/vapor service.	[G]§ 60.482-4 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(3) [G]§ 60.486(e)(4) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-R5G	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-5 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-5 for sampling connection systems.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-R5G	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-6 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-6 for open-ended valves and lines.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-R5G	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a)	Comply with the requirements in as stated in	[G]§ 60.482-7 [G]§ 60.483-1	[G]§ 60.486(a) [G]§ 60.486(b)	§ 60.487(a) [G]§ 60.487(b)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.482-1(b) [G]§ 60.482-7 [G]§ 60.482-9 [G]§ 60.483-1 [G]§ 60.483-2 § 60.592(b)	§60.482-7 for valves in gas/vapor or light-liquid service.	[G]§ 60.483-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d) § 60.593(d)	[G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) [G]§ 60.486(g) § 60.486(j) § 60.592(e)	[G]§ 60.487(c) § 60.487(d) § 60.487(e) § 60.592(e)
GRP-R5G	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for pumps in heavy-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-R5G	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.18 § 60.482-1(a) § 60.482-1(b) § 60.482-10(d) § 60.482-10(e) § 60.482-10(m)	Comply with the requirements in as stated in §60.482-10 for flares.	§ 60.485(a) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) [G]§ 60.485(g) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-R5G	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) § 60.482-10(e) [G]§ 60.482-10(g) § 60.482-10(h) § 60.482-10(m)	Comply with the requirements in as stated in §60.482-10 for closed-vent systems.	[G]§ 60.482-10(f) § 60.482-10(i) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.482-10(j) [G]§ 60.482-10(k) [G]§ 60.482-10(l) [G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-R5G	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for valves in heavy-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 60.592(d)	§ 60.592(e)	
GRP-RRR	EP	60RRRa	VOC/TOC	40 CFR Part 60, Subpart RRR	§ 60.702(a) [G]§ 60.704(b)(5)	For each vent stream, reduce TOC by 98%w or to a TOC concentration of 20 ppmv, on a dry basis corrected to 3% oxygen, whichever is less stringent. If a boiler or process heater is used, introduce vent stream as specified.	§ 60.703(c) § 60.704(a) § 60.704(b) § 60.704(b)(1) § 60.704(b)(2) § 60.704(b)(3) [G]§ 60.704(b)(4)	§ 60.705(b) § 60.705(b)(2)(i) § 60.705(c) § 60.705(c)(4) § 60.705(s)	§ 60.705(a) § 60.705(b) § 60.705(b)(2)(i) § 60.705(c) § 60.705(c)(4) § 60.705(k) § 60.705(l) § 60.705(l)(1) § 60.705(s)
GRP-RRR	EP	60RRRb	VOC/TOC	40 CFR Part 60, Subpart RRR	§ 60.702(a) [G]§ 60.704(b)(5)	For each vent stream, reduce TOC by 98%w or to a TOC concentration of 20 ppmv, on a dry basis corrected to 3% oxygen, whichever is less stringent. If a boiler or process heater is used, introduce vent stream as specified.	§ 60.703(c) § 60.704(a) § 60.704(b) § 60.704(b)(1) § 60.704(b)(2) § 60.704(b)(3) [G]§ 60.704(b)(4)	§ 60.705(b) § 60.705(b)(2)(i) § 60.705(c) § 60.705(c)(4) § 60.705(s)	§ 60.705(a) § 60.705(b) § 60.705(b)(2)(i) § 60.705(c) § 60.705(c)(4) § 60.705(k) § 60.705(l) § 60.705(l)(1) § 60.705(s)
GRP-RRR	EP	60RRRc	VOC/TOC	40 CFR Part 60, Subpart RRR	§ 60.702(b) § 60.18	For each vent stream, combust the emissions in a flare that meets the requirements of §60.18.	§ 60.703(b) § 60.703(b)(1) § 60.704(a) § 60.704(c) [G]§ 60.704(d)	§ 60.705(b) § 60.705(b)(3) § 60.705(e) § 60.705(s)	§ 60.705(a) § 60.705(b) § 60.705(b)(3) § 60.705(k) § 60.705(l) § 60.705(l)(3) § 60.705(s)
GRP-SRU3	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No valve in liquid service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-SRU3	EU	R5322ALL	VOC	30 TAC Chapter	§ 115.322(1)	No compressor seal may be	§ 115.324	[G]§ 115.326(1)	[G]§ 115.326(1)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				115, Fugitives Pet Ref B Counties	§ 115.322(2) § 115.322(3)	allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324(2) § 115.324(2)(A) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	§ 115.327(4)
GRP-SRU3	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No valve in liquid service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
GRP-SRU3	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3) § 115.327(6)	No compressor seal, as described in § 115.327(3), (5) or (6), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-SRU3	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No process drain may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(C) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-SRU3	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No process drain, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-SRU3	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No connector may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-SRU3	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No connector, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-SRU3	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.322(5)	No valve (gaseous service) may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
GRP-SRU3	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(5)	No valve (gaseous service), as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-SRU3	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No pump seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in	§ 115.324 § 115.324(1) § 115.324(1)(A) § 115.324(3) § 115.324(4) § 115.324(6)	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						§115.322(2).	[G]§ 115.325		
GRP-SRU3	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No pump seal, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-SRU3	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.327(1)	Valves of nominal size of 2" (5 cm) or less are exempt, provided allowable emissions from sources affected by this division after controls are applied with exemptions will not exceed by more than 5.0% such allowable emissions with no exemptions.	None	None	§ 115.327(1)(A) § 115.327(1)(B) § 115.327(1)(C)
GRP-SRU3	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(5)	No pressure relief valve in gaseous service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(C) § 115.324(4) § 115.324(5) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
GRP-SRU3	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(5)	No pressure relief valve in gaseous service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-SRU3	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No elevated valve may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(D) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
GRP-SRU3	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No elevated valve, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
GRP-SRU3	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for pressure relief devices in light-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-SRU3	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for flanges or other connectors.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-SRU3	EU	60GGGALL	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for valves in heavy-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-SRU3	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) § 60.482-10(e) [G]§ 60.482-10(g) § 60.482-10(h) § 60.482-10(m)	Comply with the requirements in as stated in §60.482-10 for closed-vent systems.	[G]§ 60.482-10(f) § 60.482-10(i) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.482-10(j) [G]§ 60.482-10(k) [G]§ 60.482-10(l) [G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-SRU3	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.18 § 60.482-1(a) § 60.482-1(b) § 60.482-10(d) § 60.482-10(e) § 60.482-10(m)	Comply with the requirements in as stated in §60.482-10 for flares.	§ 60.485(a) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) [G]§ 60.485(g) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-SRU3	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for pumps in heavy-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-SRU3	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(d)	Comply with the requirements as stated in §60.482-1(d) for equipment in vacuum service.	None	§ 60.486(e) § 60.486(e)(1) § 60.486(e)(5)	None
GRP-SRU3	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-6 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-6 for open-ended valves and lines.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-SRU3	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-5 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-5 for sampling connection systems.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-SRU3	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-4 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-4 for pressure relief devices in gas/vapor service.	[G]§ 60.482-4 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(3) [G]§ 60.486(e)(4) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-SRU3	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-3 [G]§ 60.482-9	Comply with the requirements as stated in §60.482-3 for compressors.	[G]§ 60.482-3 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-SRU3	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) § 60.482-3(f) § 60.482-3(g)(1) § 60.482-3(g)(2) [G]§ 60.482-3(i) § 60.482-3(j) [G]§ 60.482-9 § 60.593(c)	Comply with the requirements as stated in §60.482-3 for reciprocating compressors that become subject under §60.14 and §60.15.	§ 60.482-3(f) § 60.482-3(g)(1) § 60.482-3(g)(2) [G]§ 60.482-3(i) § 60.482-3(j) § 60.485(a) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
GRP-SRU3	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-2 [G]§ 60.482-9	Comply with the requirements as stated in §60.482-2 for pumps in light-liquid service.	[G]§ 60.482-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d) § 60.593(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-SRU3	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-7 [G]§ 60.482-9 [G]§ 60.483-1 [G]§ 60.483-2 § 60.592(b)	Comply with the requirements in as stated in §60.482-7 for valves in gas/vapor or light-liquid service.	[G]§ 60.482-7 [G]§ 60.483-1 [G]§ 60.483-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d) § 60.593(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) [G]§ 60.486(g) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(d) § 60.487(e) § 60.592(e)
GRP-VACJET	EU	R5311a	VOC	30 TAC Chapter 115, Unit Turn & Vac System-Pet Ref	§ 115.311(b)(1) § 115.312(b)(2) § 115.312(b)(2)(C)	No person may be allowed to emit VOC from a steam ejector or mechanical vacuum pump in a petroleum refinery, unless vent stream is burned properly in accordance with §115.312(b)(2) of this title.	[G]§ 115.315(b) ** See Periodic Monitoring Summary	None	None
GRP-VACJET	EU	R5311b	VOC	30 TAC Chapter 115, Unit Turn & Vac System-Pet Ref	§ 115.311(b)(1) § 115.312(b)(2) § 115.312(b)(2)(B)	No person may be allowed to emit VOC from a steam ejector or mechanical vacuum pump in a petroleum refinery, unless vent stream is burned properly in accordance with §115.312(b)(2) of this title.	[G]§ 115.315(b) ** See Periodic Monitoring Summary	None	None
GRPTURNJET	EU	R5311a	VOC	30 TAC Chapter 115, Unit Turn & Vac System-Pet Ref	§ 115.317	In Gregg, Nueces and Victoria Counties, a vacuum-producing system emitting a combined weight of VOCs less than or equal to 100 lbs. in any consecutive 24-hour period is exempt from the requirements of §115.311(b).	None	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
HOC-PP-CT	EU	63CC	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.654(a) § 63.642(b) § 63.642(n) [G]§ 63.654(d) [G]§ 63.654(f)	Except as specified in §63.654(b), the owner or operator of a heat exchange system that meets the criteria in §63.640(c)(8) must comply with the requirements of §63.654(c)-(g).	§ 63.642(d)(1) § 63.642(d)(3) § 63.642(d)(4) § 63.654(c) [G]§ 63.654(c)(1) § 63.654(c)(3) [G]§ 63.654(c)(4) [G]§ 63.654(c)(6) [G]§ 63.654(d) § 63.654(e) [G]§ 63.654(f) [G]§ 63.654(g)	§ 63.642(d)(3) [G]§ 63.654(g) § 63.655(i) § 63.655(i)(5) § 63.655(i)(5)(i) § 63.655(i)(5)(ii) [G]§ 63.655(i)(5)(iii) § 63.655(i)(5)(iv) § 63.655(i)(5)(v) § 63.655(i)(6)	§ 63.642(d)(2) § 63.642(f) [G]§ 63.654(c)(4) § 63.655(f) § 63.655(f)(1)(vi) § 63.655(f)(4) § 63.655(g) § 63.655(g)(14) [G]§ 63.655(g)(9) § 63.655(h) § 63.655(h)(7)
HOCPP-FUG	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(5)	No pressure relief valve in gaseous service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(C) § 115.324(4) § 115.324(5) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
HOCPP-FUG	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(5)	No pressure relief valve in gaseous service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
HOCPP-FUG	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No elevated valve may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(D) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
HOCPP-	EU	R5322-	VOC	30 TAC Chapter	§ 115.322(1)	No elevated valve, as	[G]§ 115.325	[G]§ 115.326(1)	[G]§ 115.326(1)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
FUG		ALL		115, Fugitives Pet Ref B Counties	§ 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).		§ 115.326(5)	§ 115.327(4)
HOCPP-FUG	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No compressor seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(A) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
HOCPP-FUG	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3) § 115.327(6)	No compressor seal, as described in § 115.327(3), (5) or (6), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
HOCPP-FUG	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No process drain may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(C) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
HOCPP-FUG	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No process drain, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
HOCPP-FUG	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No valve in liquid service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
HOCPP-FUG	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No valve in liquid service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
HOCPP-FUG	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.322(5)	No valve (gaseous service) may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
HOCPP-FUG	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(5)	No valve (gaseous service), as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
HOCPP-FUG	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No pump seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found,	§ 115.324 § 115.324(1) § 115.324(1)(A) § 115.324(3) § 115.324(4)	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						except as provided in §115.322(2).	§ 115.324(6) [G]§ 115.325		
HOCPP-FUG	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No pump seal, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
HOCPP-FUG	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.327(1)	Valves of nominal size of 2" (5 cm) or less are exempt, provided allowable emissions from sources affected by this division after controls are applied with exemptions will not exceed by more than 5.0% such allowable emissions with no exemptions.	None	None	§ 115.327(1)(A) § 115.327(1)(B) § 115.327(1)(C)
HOCPP-FUG	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No connector may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
HOCPP-FUG	EU	R5322-ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No connector, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
HOCPP-	EU	60GGGA-	VOC	40 CFR Part 60,	§ 60.593a(g)	Connectors in gas/vapor or	§ 60.482-11a(a)	§ 60.482-11a(b)(3)(v)	§ 60.487a(a)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
FUG		ALL		Subpart GGGa	§ 60.482-11a(b)(2) § 60.482-11a(b)(3) § 60.482-11a(d) [G]§ 60.482-11a(e) [G]§ 60.482-11a(f)(1) § 60.482-11a(f)(2) § 60.482-11a(g) § 60.482-9a(a) § 60.482-9a(b) [G]§ 60.482-9a(c) § 60.482-9a(f) § 60.485a(b) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k) § 60.592a(d) § 60.592a(e)	light liquid service are exempt from the requirements in §60.482-11a, provided the owner or operator complies with §60.482-8a for all connectors, not just those in heavy liquid service.	§ 60.482-11a(b) § 60.482-11a(b)(1) § 60.482-11a(b)(3) § 60.482-11a(b)(3)(i) § 60.482-11a(b)(3)(ii) [G]§ 60.482-11a(b)(3)(iii) § 60.482-11a(b)(3)(iv) § 60.482-11a(c) § 60.482-9a(a) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2) [G]§ 60.485a(d) [G]§ 60.485a(e) § 60.593a(d)	§ 60.485a(b)(2) [G]§ 60.486a(a)(3) [G]§ 60.486a(b) [G]§ 60.486a(c) § 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(8) § 60.486a(e)(9) § 60.486a(f) § 60.486a(f)(1)	§ 60.487a(b) § 60.487a(b)(1) § 60.487a(b)(5) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(i) § 60.487a(c)(2)(vii) § 60.487a(c)(2)(viii) § 60.487a(c)(2)(xi) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)
HOCPP-FUG	EU	60GGGA-ALL	VOC	40 CFR Part 60, Subpart GGGa	§ 60.592a(a) § 60.18 § 60.482-10a(a) § 60.482-10a(d) § 60.482-10a(m) § 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(g) § 60.485a(b) § 60.485a(c) § 60.485a(c)(1) § 60.485a(f) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k) § 60.592a(d) § 60.592a(e)	Comply with the requirements as stated in §60.482-10a for flares.	§ 60.482-10a(e) § 60.482-1a(g) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2) § 60.485a(c)(2) [G]§ 60.485a(d) [G]§ 60.485a(g) § 60.593a(d)	§ 60.482-1a(g) § 60.485a(b)(2) § 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(8)	§ 60.487a(a) § 60.487a(b) § 60.487a(b)(1) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(xi) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)
HOCPP-FUG	EU	60GGGA-ALL	VOC	40 CFR Part 60, Subpart GGGa	§ 60.592a(a) § 60.482-10a(a)	Comply with the requirements as stated in	§ 60.485a(a) [G]§ 60.485a(b)(1)	[G]§ 60.482-10a(l) § 60.485a(b)(2)	§ 60.487a(a) § 60.487a(b)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 60.482-10a(f) [G]§ 60.482-10a(g) § 60.482-10a(h) § 60.482-10a(i) [G]§ 60.482-10a(j) [G]§ 60.482-10a(k) § 60.482-10a(m) § 60.485a(b) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k) § 60.592a(d) § 60.592a(e)	§60.482-10a for closed-vent systems.	§ 60.485a(b)(2) [G]§ 60.485a(d) § 60.593a(d)	[G]§ 60.486a(d) § 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(8)	§ 60.487a(b)(1) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(xi) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)
HOCPP-FUG	EU	60GGGA-ALL	VOC	40 CFR Part 60, Subpart GGa	§ 60.592a(a) § 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(g) [G]§ 60.482-2a(c)(2) [G]§ 60.482-7a(e) § 60.482-8a(a) § 60.482-8a(a)(2) § 60.482-8a(b) [G]§ 60.482-8a(c) § 60.482-8a(d) § 60.482-9a(a) § 60.482-9a(b) § 60.485a(b) § 60.485a(f) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k) § 60.592a(d) § 60.592a(e)	Comply with the requirements as stated in §60.482-8a for pressure relief devices in heavy liquid service.	§ 60.482-1a(g) § 60.482-8a(a)(1) § 60.482-9a(a) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2) [G]§ 60.485a(d) [G]§ 60.485a(e) § 60.593a(d)	§ 60.482-1a(g) § 60.485a(b)(2) [G]§ 60.486a(a)(3) [G]§ 60.486a(b) [G]§ 60.486a(c) § 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(8)	§ 60.487a(a) § 60.487a(b) § 60.487a(b)(1) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(xi) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)
HOCPP-FUG	EU	60GGGA-ALL	VOC	40 CFR Part 60, Subpart GGa	§ 60.592a(a) § 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(g)	Comply with the requirements as stated in §60.482-8a for connectors in heavy liquid service.	§ 60.482-1a(g) § 60.482-8a(a)(1) § 60.482-9a(a) § 60.485a(a)	§ 60.482-1a(g) § 60.485a(b)(2) [G]§ 60.486a(a)(3) [G]§ 60.486a(b)	§ 60.487a(a) § 60.487a(b) § 60.487a(b)(1) § 60.487a(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 60.482-2a(c)(2) [G]§ 60.482-7a(e) § 60.482-8a(a) § 60.482-8a(a)(2) § 60.482-8a(b) [G]§ 60.482-8a(c) § 60.482-8a(d) § 60.482-9a(a) § 60.482-9a(b) [G]§ 60.482-9a(c) § 60.482-9a(f) § 60.485a(b) § 60.485a(f) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k) § 60.592a(d) § 60.592a(e)		[G]§ 60.485a(b)(1) § 60.485a(b)(2) [G]§ 60.485a(d) [G]§ 60.485a(e) § 60.593a(d)	[G]§ 60.486a(c) § 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(8)	§ 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(xi) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)
HOCPP-FUG	EU	60GGGA-ALL	VOC	40 CFR Part 60, Subpart GGGa	§ 60.592a(a) § 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(g) [G]§ 60.482-2a(c)(2) [G]§ 60.482-7a(e) § 60.482-8a(a) § 60.482-8a(a)(2) § 60.482-8a(b) [G]§ 60.482-8a(c) § 60.482-8a(d) § 60.482-9a(a) § 60.482-9a(b) [G]§ 60.482-9a(c) § 60.482-9a(e) § 60.482-9a(f) § 60.485a(b) § 60.485a(f) § 60.486a(a)(1)	Comply with the requirements as stated in §60.482-8a for valves in heavy liquid service.	§ 60.482-1a(g) § 60.482-8a(a)(1) § 60.482-9a(a) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2) [G]§ 60.485a(d) [G]§ 60.485a(e) § 60.593a(d)	§ 60.482-1a(g) § 60.485a(b)(2) [G]§ 60.486a(a)(3) [G]§ 60.486a(b) [G]§ 60.486a(c) § 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(8)	§ 60.487a(a) § 60.487a(b) § 60.487a(b)(1) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(xi) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.486a(a)(2) § 60.486a(k) § 60.592a(d) § 60.592a(e)				
HOCPP-FUG	EU	60GGGA-ALL	VOC	40 CFR Part 60, Subpart GGGa	§ 60.592a(a) § 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(g) § 60.482-7a(a)(1) § 60.482-7a(b) [G]§ 60.482-7a(d) [G]§ 60.482-7a(e) [G]§ 60.482-7a(f) [G]§ 60.482-7a(g) [G]§ 60.482-7a(h) § 60.482-9a(a) § 60.482-9a(b) [G]§ 60.482-9a(c) § 60.482-9a(e) § 60.482-9a(f) § 60.485a(b) § 60.485a(c) § 60.485a(c)(1) § 60.485a(f) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k) § 60.592a(d) § 60.592a(e)	Comply with the requirements as stated in §60.482-7a for valves in gas/vapor or light liquid service.	§ 60.482-1a(f)(1) § 60.482-1a(f)(2) [G]§ 60.482-1a(f)(3) § 60.482-1a(g) § 60.482-7a(a)(1) [G]§ 60.482-7a(a)(2) [G]§ 60.482-7a(c) § 60.482-9a(a) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2) § 60.485a(c)(2) [G]§ 60.485a(d) [G]§ 60.485a(e) § 60.593a(d)	§ 60.482-1a(g) § 60.485a(b)(2) [G]§ 60.486a(a)(3) [G]§ 60.486a(b) [G]§ 60.486a(c) § 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(2) [G]§ 60.486a(e)(4) [G]§ 60.486a(e)(8) § 60.486a(f) § 60.486a(f)(1) § 60.486a(f)(2)	§ 60.487a(a) § 60.487a(b) § 60.487a(b)(1) § 60.487a(b)(2) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(i) § 60.487a(c)(2)(ii) § 60.487a(c)(2)(xi) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)
HOCPP-FUG	EU	60GGGA-ALL	VOC	40 CFR Part 60, Subpart GGGa	§ 60.592a(a) § 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(g) § 60.482-6a(a)(1) § 60.482-6a(a)(2) § 60.482-6a(b) § 60.482-6a(c) § 60.482-6a(d)	Comply with the requirements as stated in §60.482-6a for open-ended valves and lines.	§ 60.482-1a(g) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2) [G]§ 60.485a(d) § 60.593a(d)	§ 60.482-1a(g) § 60.485a(b)(2) § 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(8)	§ 60.487a(a) § 60.487a(b) § 60.487a(b)(1) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(xi) § 60.487a(c)(3) § 60.487a(c)(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.482-6a(e) § 60.485a(b) § 60.485a(f) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k) § 60.592a(d) § 60.592a(e)			§ 60.487a(e)	
HOCPP-FUG	EU	60GGGA-ALL	VOC	40 CFR Part 60, Subpart GGGa	§ 60.593a(f) § 60.482-1a(a) § 60.482-1a(g)	Open-ended valves or lines containing asphalt as defined in (§60.591a are exempt from the requirements of §60.482-6a(a) through (c).	§ 60.482-1a(g) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2) [G]§ 60.485a(d)	§ 60.482-1a(g) § 60.485a(b)(2) § 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(8)	§ 60.487a(a) § 60.487a(b) § 60.487a(b)(1) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(xi) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)
HOCPP-FUG	EU	60GGGA-ALL	VOC	40 CFR Part 60, Subpart GGGa	§ 60.592a(a) § 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(g) § 60.482-5a(a) [G]§ 60.482-5a(b) § 60.482-5a(c) § 60.485a(b) § 60.485a(f) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k) § 60.592a(d) § 60.592a(e)	Comply with the requirements as stated in §60.482-5a for sampling connection systems.	§ 60.482-1a(g) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2) [G]§ 60.485a(d) § 60.593a(d)	§ 60.482-1a(g) § 60.485a(b)(2) § 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(8)	§ 60.487a(a) § 60.487a(b) § 60.487a(b)(1) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(xi) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)
HOCPP-FUG	EU	60GGGA-ALL	VOC	40 CFR Part 60, Subpart GGGa	§ 60.592a(a) § 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(g) [G]§ 60.482-2a(c)(2)	Comply with the requirements as stated in §60.482-8a for pressure relief devices in light liquid service.	§ 60.482-1a(g) § 60.482-8a(a)(1) § 60.482-9a(a) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2)	§ 60.482-1a(g) § 60.485a(b)(2) [G]§ 60.486a(a)(3) [G]§ 60.486a(b) [G]§ 60.486a(c) § 60.486a(e)	§ 60.487a(a) § 60.487a(b) § 60.487a(b)(1) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 60.482-7a(e) § 60.482-8a(a) § 60.482-8a(a)(2) § 60.482-8a(b) [G]§ 60.482-8a(c) § 60.482-8a(d) § 60.482-9a(a) § 60.482-9a(b) § 60.485a(b) § 60.485a(f) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k) § 60.592a(d) § 60.592a(e)		[G]§ 60.485a(d) [G]§ 60.485a(e) § 60.593a(d)	§ 60.486a(e)(1) [G]§ 60.486a(e)(8)	§ 60.487a(c)(2)(xi) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)
HOCPP-FUG	EU	60GGGA-ALL	VOC	40 CFR Part 60, Subpart GGGa	§ 60.592a(a) § 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(g) § 60.482-4a(a) § 60.482-4a(b)(1) § 60.482-4a(b)(2) § 60.482-4a(c) § 60.482-4a(d)(1) § 60.482-4a(d)(2) § 60.482-9a(a) § 60.482-9a(b) § 60.485a(b) § 60.485a(c) § 60.485a(c)(1) § 60.485a(f) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k) § 60.592a(d) § 60.592a(e)	Comply with the requirements as stated in §60.482-4a for pressure relief devices in gas/vapor service.	§ 60.482-1a(g) § 60.482-4a(b)(2) § 60.482-9a(a) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2) § 60.485a(c)(2) [G]§ 60.485a(d) § 60.593a(d)	§ 60.482-1a(g) § 60.485a(b)(2) § 60.486a(e) § 60.486a(e)(1) § 60.486a(e)(10) § 60.486a(e)(3) [G]§ 60.486a(e)(4) [G]§ 60.486a(e)(8)	§ 60.487a(a) § 60.487a(b) § 60.487a(b)(1) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(xi) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)
HOCPP-FUG	EU	60GGGA-ALL	VOC	40 CFR Part 60, Subpart GGGa	§ 60.592a(a) § 60.482-1a(a)	Comply with the requirements as stated in	§ 60.482-1a(g) § 60.482-3a(e)(1)	§ 60.482-1a(g) § 60.485a(b)(2)	§ 60.487a(a) § 60.487a(b)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.482-1a(b) § 60.482-1a(g) § 60.482-3a(a) [G]§ 60.482-3a(b) § 60.482-3a(c) § 60.482-3a(d) § 60.482-3a(e)(2) § 60.482-3a(f) [G]§ 60.482-3a(g) § 60.482-3a(h) [G]§ 60.482-3a(i) § 60.482-3a(j) § 60.482-9a(a) § 60.482-9a(b) § 60.485a(b) § 60.485a(c) § 60.485a(c)(1) § 60.485a(f) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k) § 60.592a(d) § 60.592a(e)	§60.482-3a for compressors.	§ 60.482-9a(a) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2) § 60.485a(c)(2) [G]§ 60.485a(d) § 60.593a(d)	[G]§ 60.486a(a)(3) [G]§ 60.486a(b) [G]§ 60.486a(c) § 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(2) [G]§ 60.486a(e)(4) [G]§ 60.486a(e)(8) [G]§ 60.486a(h)	§ 60.487a(b)(1) § 60.487a(b)(4) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(v) § 60.487a(c)(2)(vi) § 60.487a(c)(2)(xi) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)
HOCPP-FUG	EU	60GGGA-ALL	VOC	40 CFR Part 60, Subpart GGGa	§ 60.592a(a) § 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(g) § 60.482-3a(a) [G]§ 60.482-3a(b) § 60.482-3a(c) § 60.482-3a(d) § 60.482-3a(e)(2) § 60.482-3a(f) [G]§ 60.482-3a(g) § 60.482-3a(h) [G]§ 60.482-3a(i) § 60.482-3a(j) § 60.482-9a(a) § 60.482-9a(b)	Comply with the requirements as stated in §60.482-3a for reciprocating compressors that become subject under §60.14 and §60.15.	§ 60.482-1a(g) § 60.482-3a(e)(1) § 60.482-9a(a) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2) § 60.485a(c)(2) [G]§ 60.485a(d) § 60.593a(d)	§ 60.482-1a(g) § 60.485a(b)(2) [G]§ 60.486a(a)(3) [G]§ 60.486a(b) [G]§ 60.486a(c) § 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(2) [G]§ 60.486a(e)(4) [G]§ 60.486a(e)(8) [G]§ 60.486a(h)	§ 60.487a(a) § 60.487a(b) § 60.487a(b)(1) § 60.487a(b)(4) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(v) § 60.487a(c)(2)(vi) § 60.487a(c)(2)(xi) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.485a(b) § 60.485a(c) § 60.485a(c)(1) § 60.485a(f) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k) § 60.592a(d) § 60.592a(e) § 60.593a(c)				
HOCPP-FUG	EU	60GGGA-ALL	VOC	40 CFR Part 60, Subpart GGGA	§ 60.593a(b)(1)	Compressors in hydrogen service are exempt from the requirements of §60.592a if an owner or operator demonstrates that a compressor is in hydrogen service.	§ 60.593a(b)(2) [G]§ 60.593a(b)(3)	None	None
HOCPP-FUG	EU	60GGGA-ALL	VOC	40 CFR Part 60, Subpart GGGA	§ 60.592a(a) § 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(g) [G]§ 60.482-2a(c)(2) [G]§ 60.482-7a(e) § 60.482-8a(a) § 60.482-8a(a)(2) § 60.482-8a(b) [G]§ 60.482-8a(c) § 60.482-8a(d) § 60.482-9a(a) § 60.482-9a(b) [G]§ 60.482-9a(d) § 60.482-9a(f) § 60.485a(b) § 60.485a(f) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k)	Comply with the requirements as stated in §60.482-8a for pumps in heavy liquid service.	§ 60.482-1a(g) § 60.482-8a(a)(1) § 60.482-9a(a) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2) [G]§ 60.485a(d) [G]§ 60.485a(e) § 60.593a(d)	§ 60.482-1a(g) § 60.485a(b)(2) [G]§ 60.486a(a)(3) [G]§ 60.486a(b) [G]§ 60.486a(c) § 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(8)	§ 60.487a(a) § 60.487a(b) § 60.487a(b)(1) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(xi) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.592a(d) § 60.592a(e)				
HOCPP-FUG	EU	60GGGA-ALL	VOC	40 CFR Part 60, Subpart GGa	§ 60.592a(a) § 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(d) § 60.485a(b) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k) § 60.592a(d) § 60.592a(e)	Comply with the requirements as stated in §60.482-1a(d) for equipment in vacuum service.	[G]§ 60.485a(b)(1) § 60.485a(b)(2)	§ 60.485a(b)(2) § 60.486a(e) § 60.486a(e)(1) § 60.486a(e)(5)	None
HOCPP-FUG	EU	60GGGA-ALL	VOC	40 CFR Part 60, Subpart GGa	§ 60.592a(a) § 60.482-1a(a) § 60.482-1a(b) § 60.482-1a(g) § 60.482-2a(b)(1) § 60.482-2a(b)(2) § 60.482-2a(b)(2)(ii) § 60.482-2a(c)(1) [G]§ 60.482-2a(c)(2) § 60.482-2a(d) [G]§ 60.482-2a(d)(1) § 60.482-2a(d)(2) § 60.482-2a(d)(3) [G]§ 60.482-2a(d)(6) [G]§ 60.482-2a(e) § 60.482-2a(f) [G]§ 60.482-2a(g) § 60.482-2a(h) § 60.482-9a(a) § 60.482-9a(b) [G]§ 60.482-9a(d) § 60.482-9a(f)	Comply with the requirements as stated in §60.482-2a for pumps in light liquid service.	§ 60.482-1a(f)(1) § 60.482-1a(f)(2) [G]§ 60.482-1a(f)(3) § 60.482-1a(g) § 60.482-2a(a)(1) § 60.482-2a(a)(2) § 60.482-2a(b)(2)(i) [G]§ 60.482-2a(d)(4) [G]§ 60.482-2a(d)(5) § 60.482-9a(a) § 60.485a(a) [G]§ 60.485a(b)(1) § 60.485a(b)(2) § 60.485a(c)(2) [G]§ 60.485a(d) [G]§ 60.485a(e) § 60.593a(d)	§ 60.482-1a(g) § 60.485a(b)(2) [G]§ 60.486a(a)(3) [G]§ 60.486a(b) [G]§ 60.486a(c) § 60.486a(e) § 60.486a(e)(1) [G]§ 60.486a(e)(2) [G]§ 60.486a(e)(4) § 60.486a(e)(7) [G]§ 60.486a(e)(8) § 60.486a(f) § 60.486a(f)(1) [G]§ 60.486a(h)	§ 60.487a(a) § 60.487a(b) § 60.487a(b)(1) § 60.487a(b)(3) § 60.487a(c) § 60.487a(c)(1) § 60.487a(c)(2) § 60.487a(c)(2)(iii) § 60.487a(c)(2)(iv) § 60.487a(c)(2)(xi) § 60.487a(c)(3) § 60.487a(c)(4) § 60.487a(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.485a(b) § 60.485a(c) § 60.485a(c)(1) § 60.485a(f) § 60.486a(a)(1) § 60.486a(a)(2) § 60.486a(k) § 60.592a(d) § 60.592a(e)				
HOCPP-FUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	[G]§ 63.648(g) § 63.642(b) § 63.642(n)	Compressors in hydrogen service are exempt from the requirements of §63.648(a) and (c) if an owner or operator demonstrates that a compressor is in hydrogen service. §63.648(g)(1)-(2).	[G]§ 63.648(g)	§ 63.648(h) § 63.655(d)(3) § 63.655(i)	None
HOCPP-FUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(d) § 60.486(k) § 63.642(b) § 63.642(n)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for equipment in vacuum service.	None	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(5) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i) § 63.655(i)(6)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 63.642(f) § 63.655(d)(2)
HOCPP-FUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) § 60.482-1(g) § 60.482-2(b)(1) [G]§ 60.482-2(b)(2) § 60.482-2(c)(1) [G]§ 60.482-2(c)(2) § 60.482-2(d) [G]§ 60.482-2(d)(1) § 60.482-2(d)(2) § 60.482-2(d)(3) [G]§ 60.482-2(d)(4)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pumps in light liquid service complying with §60.482-2.	§ 60.482-1(f)(1) § 60.482-1(f)(2) [G]§ 60.482-1(f)(3) [G]§ 60.482-2(a) [G]§ 60.482-2(b)(2) [G]§ 60.482-2(d)(4) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) [G]§ 63.648(b)	§ 60.482-1(g) [G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) § 60.486(f) [G]§ 60.486(h) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 63.642(f) § 63.655(d)(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 60.482-2(d)(5) [G]§ 60.482-2(d)(6) [G]§ 60.482-2(e) § 60.482-2(f) [G]§ 60.482-2(g) § 60.482-2(h) § 60.482-9(a) § 60.482-9(b) [G]§ 60.482-9(d) § 60.482-9(f) § 60.486(k) § 63.642(b) § 63.642(n) § 63.648(a)(2) § 63.648(f)			§ 63.655(d)(6) § 63.655(i) § 63.655(i)(6)	
HOCPP-FUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) § 60.482-1(g) § 60.482-3(a) [G]§ 60.482-3(b) § 60.482-3(c) § 60.482-3(d) § 60.482-3(e)(1) § 60.482-3(e)(2) § 60.482-3(f) § 60.482-3(g)(1) § 60.482-3(g)(2) § 60.482-3(h) [G]§ 60.482-3(i) § 60.482-3(j) § 60.482-9(a) § 60.482-9(b) § 60.486(k) § 63.642(b) § 63.642(n) § 63.648(a)(2) § 63.648(i)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for compressors complying with §60.482-3.	§ 60.482-3(e)(1) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f)	§ 60.482-1(g) [G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(d)(6) § 63.655(i) § 63.655(i)(6)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 63.642(f) § 63.655(d)(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
HOCPP-FUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) § 60.482-1(g) § 60.482-5(a) [G]§ 60.482-5(b) § 60.482-5(c) § 60.486(k) § 63.642(b) § 63.642(n) § 63.648(a)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for sampling connection systems complying with §60.482-5.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f)	§ 60.482-1(g) [G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i) § 63.655(i)(6)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 63.642(f) § 63.655(d)(2)
HOCPP-FUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) § 60.482-1(g) § 60.482-6(a)(1) § 60.482-6(a)(2) § 60.482-6(b) § 60.482-6(c) § 60.482-6(d) § 60.482-6(e) § 60.486(k) § 63.642(b) § 63.642(n) § 63.648(a)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for open-ended valves or lines complying with §60.482-6.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f)	§ 60.482-1(g) [G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i) § 63.655(i)(6)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 63.642(f) § 63.655(d)(2)
HOCPP-FUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(j)(4)(iv) § 63.642(b) § 63.642(n) § 63.644(a)(2) § 63.670	For each pressure relief device in organic HAP gas or vapor service routed to a control device, both the closed vent system and control device (if applicable) referenced in §63.648(j)(4)(i)-(iii) must meet the requirements of §63.644. When complying with this §63.648(j)(4), all references to 'Group 1 miscellaneous process vent'	§ 63.644(a) § 63.644(e)	§ 63.648(h) § 63.655(i) [G]§ 63.655(i)(3) § 63.655(i)(6)	§ 63.642(f) § 63.655(f) § 63.655(f)(4) § 63.655(g) [G]§ 63.655(g)(10) § 63.655(g)(14) § 63.655(g)(6) § 63.655(h)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						in §63.644 mean 'pressure relief device.'			
HOCPP-FUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) § 60.482-1(g) § 60.482-8(a) § 60.482-8(a)(2) § 60.482-8(b) § 60.482-8(c)(1) § 60.482-8(c)(2) § 60.482-8(d) § 60.482-9(a) § 60.482-9(b) [G]§ 60.482-9(d) § 60.482-9(f) § 60.486(k) § 63.642(b) § 63.642(n) § 63.648(a)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pumps in heavy liquid service complying with §60.482-8.	§ 60.482-8(a)(1) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f)	§ 60.482-1(g) [G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i) § 63.655(i)(6)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 63.642(f) § 63.655(d)(2)
HOCPP-FUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) § 60.482-1(g) § 60.482-8(a) § 60.482-8(a)(2) § 60.482-8(b) § 60.482-8(c)(1) § 60.482-8(c)(2) § 60.482-8(d) § 60.482-9(a) § 60.482-9(b) [G]§ 60.482-9(c) § 60.482-9(e) § 60.482-9(f) § 60.486(k) § 63.642(b) § 63.642(n)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for valves in heavy liquid service complying with §60.482-8.	§ 60.482-8(a)(1) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f)	§ 60.482-1(g) [G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i) § 63.655(i)(6)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 63.642(f) § 63.655(d)(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.648(a)(2)				
HOCPP-FUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) § 60.482-1(g) § 60.482-8(a) § 60.482-8(a)(2) § 60.482-8(b) § 60.482-8(c)(1) § 60.482-8(c)(2) § 60.482-8(d) § 60.482-9(a) § 60.482-9(b) § 60.486(k) § 63.642(b) § 63.642(n) § 63.648(a)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for pressure relief devices in heavy liquid service complying with §60.482-8.	§ 60.482-8(a)(1) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f)	§ 60.482-1(g) [G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i) § 63.655(i)(6)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 63.642(f) § 63.655(d)(2)
HOCPP-FUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) § 60.482-1(g) § 60.482-8(a) § 60.482-8(a)(2) § 60.482-8(b) § 60.482-8(c)(1) § 60.482-8(c)(2) § 60.482-8(d) § 60.482-9(a) § 60.482-9(b) § 60.486(k) § 63.642(b) § 63.642(n) § 63.648(a)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for flanges or other connectors complying with §60.482-8.	§ 60.482-8(a)(1) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f)	§ 60.482-1(g) [G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i) § 63.655(i)(6)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 63.642(f) § 63.655(d)(2)
HOCPP-FUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) § 60.482-1(g) [G]§ 60.482-10(f)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for closed vent (or vapor collection) systems complying with	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f)	§ 60.482-1(g) [G]§ 60.482-10(l) [G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 63.642(f)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 60.482-10(g) § 60.482-10(h) § 60.482-10(i) [G]§ 60.482-10(j) [G]§ 60.482-10(k) § 60.482-10(m) § 60.486(k) § 63.642(b) § 63.642(n) § 63.648(a)(2)	§60.482-10.		§ 60.486(e)(1) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i) § 63.655(i)(6)	§ 63.655(d)(2)
HOCPP-FUG	EU	63CCVV-ALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.648(a) § 60.482-1(a) § 60.482-1(b) § 60.482-1(g) § 60.482-7(b) § 60.482-7(d)(1) § 60.482-7(d)(2) [G]§ 60.482-7(e) [G]§ 60.482-7(f) [G]§ 60.482-7(g) [G]§ 60.482-7(h) § 60.482-9(a) § 60.482-9(b) [G]§ 60.482-9(c) § 60.482-9(e) § 60.482-9(f) § 60.486(k) § 63.642(b) § 63.642(n) § 63.648(a)(2)	Comply with the specified 40 CFR Part 60, Subpart VV requirements for valves in gas/vapor service or in light liquid service complying with §60.482-7.	§ 60.482-1(f)(1) § 60.482-1(f)(2) [G]§ 60.482-1(f)(3) § 60.482-7(a)(1) [G]§ 60.482-7(a)(2) § 60.482-7(c)(1)(i) § 60.482-7(c)(1)(ii) § 60.482-7(c)(2) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) [G]§ 63.648(b)	§ 60.482-1(g) [G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) § 60.486(j) § 63.648(h) § 63.655(d)(1)(i) § 63.655(i) § 63.655(i)(6)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(d) § 60.487(e) § 63.642(f) § 63.655(d)(2)
LPG STORAG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.327(1)	Valves of nominal size of 2" (5 cm) or less are exempt, provided allowable emissions from sources affected by this division after controls are applied with exemptions will not exceed by more than 5.0%	None	None	§ 115.327(1)(A) § 115.327(1)(B) § 115.327(1)(C)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						such allowable emissions with no exemptions.			
LPG STORAG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No connector may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
LPG STORAG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No pump seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(A) § 115.324(3) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
LPG STORAG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(5)	No valve (gaseous service), as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
LPG STORAG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.322(5)	No valve (gaseous service) may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
LPG STORAG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No valve in liquid service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.327(3) § 115.327(5)	as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).			
LPG STORAG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No valve in liquid service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
LPG STORAG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No process drain, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
LPG STORAG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No process drain may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(C) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
LPG STORAG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3) § 115.327(6)	No compressor seal, as described in § 115.327(3), (5) or (6), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
LPG	EU	R5322ALL	VOC	30 TAC Chapter	§ 115.322(1)	No compressor seal may be	§ 115.324	[G]§ 115.326(1)	[G]§ 115.326(1)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
STORAG				115, Fugitives Pet Ref B Counties	§ 115.322(2) § 115.322(3)	allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324(2) § 115.324(2)(A) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	§ 115.327(4)
LPG STORAG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No elevated valve, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
LPG STORAG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No elevated valve may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(D) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
LPG STORAG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(5)	No pressure relief valve in gaseous service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
LPG STORAG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(5)	No pressure relief valve in gaseous service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in	§ 115.324 § 115.324(2) § 115.324(2)(C) § 115.324(4) § 115.324(5) § 115.324(6) [G]§ 115.324(7)	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						§115.322(2).	[G]§ 115.325		
LPG STORAGE	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No connector, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
LPG STORAGE	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No pump seal, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
MEROX	EP	R5121a	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(b) § 115.121(b) § 115.122(b)(3)	For all persons in Nueces and Victoria Counties, any vent gas streams affected by §115.121(b) of this title must be controlled properly with a control efficiency of at least 90% or to a VOC concentration of no more than 20 ppmv (on a dry basis corrected to 3.0% oxygen for combustion devices).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2)	None
MEROX	EP	R5121b	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(b) § 115.121(b) § 115.122(b)(1)	For all persons in Nueces and Victoria Counties, any vent gas streams affected by §115.121(b) of this title must be controlled properly with a control efficiency of at least 90% or to a VOC concentration of no more	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						than 20 ppmv (on a dry basis corrected to 3.0% oxygen for combustion devices).			
MEROX	EP	63CCa	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.643(a)(2) § 63.116(b) § 63.642(b) § 63.642(n) § 63.643(b)	For a Group 1 miscellaneous process vent, reduce emissions of organic HAPs, using a control device, by 98 weight-percent or to a concentration of 20 parts per million by volume, on a dry basis, corrected to 3 percent oxygen, whichever is less stringent. Compliance can be determined by measuring either organic HAPs or TOCs using the procedures in §63.645.	§ 63.644(a) § 63.644(a)(3) § 63.644(d) § 63.644(e) § 63.645(a)	§ 63.655(i) § 63.655(i)(6)	§ 63.642(f) § 63.644(d) § 63.655(f) § 63.655(f)(1)(ii) [G]§ 63.655(f)(3) § 63.655(g) § 63.655(g)(14) § 63.655(h)
MEROX	EP	63CCb	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.643(a)(2) § 63.642(b) § 63.642(n)	For a Group 1 miscellaneous process vent, reduce emissions of organic HAPs, using a control device, by 98 weight-percent or to a concentration of 20 parts per million by volume, on a dry basis, corrected to 3 percent oxygen, whichever is less stringent. Compliance can be determined by measuring either organic HAPs or TOCs using the procedures in §63.645.	§ 63.116(c) § 63.116(c)(1) § 63.116(c)(1)(ii) § 63.116(c)(2) [G]§ 63.116(c)(3) § 63.642(d)(1) § 63.642(d)(3) § 63.642(d)(4) § 63.644(a) § 63.644(a)(1)(i) § 63.644(d) § 63.644(e) § 63.645(a)	§ 63.644(a)(1)(i) § 63.655(i) § 63.655(i)(2) [G]§ 63.655(i)(3) § 63.655(i)(6)	§ 63.642(d)(2) § 63.642(f) § 63.644(d) § 63.655(f) § 63.655(f)(1)(ii) [G]§ 63.655(f)(1)(iii) [G]§ 63.655(f)(2) [G]§ 63.655(f)(3) § 63.655(f)(4) § 63.655(g) § 63.655(g)(14) § 63.655(g)(6) § 63.655(h) [G]§ 63.655(h)(10) [G]§ 63.655(h)(9)
MFL-1	EU	R1111	Opacity	30 TAC Chapter 111, Visible	§ 111.111(a)(4)(A)	Visible emissions from a process gas flare shall not	§ 111.111(a)(4)(A)(i)	§ 111.111(a)(4)(A)(ii)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Emissions		be permitted for more than five minutes in any two-hour period, except for upset emissions as provided in §101.222(b).	§ 111.111(a)(4)(A)(ii)		
MFL-1	CD	60A	Opacity	40 CFR Part 60, Subpart A	§ 60.18(b) § 60.18(c)(1) § 60.18(c)(2) § 60.18(c)(3)(ii) § 60.18(c)(4)(iii) § 60.18(c)(6) § 60.18(e)	Flares shall comply with paragraphs (c)-(f) of § 60.18.	§ 60.18(d) § 60.18(f)(1) § 60.18(f)(2) § 60.18(f)(3) § 60.18(f)(4) § 60.18(f)(5)	None	None
MFL-1	EU	60Ja	H2S	40 CFR Part 60, Subpart Ja	§ 60.103a(h) [G]§ 60.103a(b) § 60.103a(c) [G]§ 60.103a(c)(1) [G]§ 60.103a(d) [G]§ 60.103a(e) § 60.103a(f)	Each owner or operator shall not burn in any affected flare any fuel gas that contains H2S in excess of 162 ppmv determined hourly on a 3-hour rolling average basis. The combustion in a flare of process upset gases or fuel gas that is released to the flare as a result of relief valve leakage or other emergency malfunctions is exempt from this limit.	§ 60.104a(a) § 60.104a(c) § 60.104a(j) [G]§ 60.104a(j)(4) [G]§ 60.107a(a)(2) § 60.107a(e) [G]§ 60.107a(e)(1) [G]§ 60.107a(e)(2) § 60.107a(f) [G]§ 60.107a(f)(1)	[G]§ 60.103a(a) [G]§ 60.103a(e)(3) [G]§ 60.107a(a)(2) § 60.107a(e)(1) § 60.107a(e)(2) § 60.107a(f) § 60.107a(f)(1)(iii) § 60.108a(c) § 60.108a(c)(1) [G]§ 60.108a(c)(6) § 60.108a(c)(7) [G]§ 60.108a(d)	[G]§ 60.103a(b) § 60.107a(i) [G]§ 60.107a(i)(2) [G]§ 60.108a(d)
MFL-1	CD	63A	112(B) HAPS	40 CFR Part 63, Subpart A	§ 63.11(b)(4) § 63.11(b)(1) § 63.11(b)(2) § 63.11(b)(3) § 63.11(b)(5) § 63.11(b)(6)(ii) § 63.11(b)(7)(iii)	Flares shall be designed and operated with no visible emissions, except for periods of a total of 5 minutes or less during any 2 consecutive hrs. Test Method 22 in App. A of part 60 of this chapter shall be used.	§ 63.11(b)(4) § 63.11(b)(5) § 63.11(b)(7)(i)	None	None
MFL-1B	EP	R1111	Opacity	30 TAC Chapter 111, Visible	§ 111.111(a)(4)(A) § 111.111(a)(1)(B)	Visible emissions from an acid gas flare shall not	[G]§ 111.111(a)(1)(F)	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Emissions	§ 111.111(a)(1)(E)	exceed an opacity of 20% averaged over a six minute period for any source on which construction was begun after January 31, 1972.			
MFL-1B	CD	63A	112(B) HAPS	40 CFR Part 63, Subpart A	§ 63.11(b)(4) § 63.11(b)(1) § 63.11(b)(2) § 63.11(b)(3) § 63.11(b)(5) § 63.11(b)(6)(i)(A) § 63.11(b)(6)(i)(B) § 63.11(b)(7)(i)	Flares shall be designed and operated with no visible emissions, except for periods of a total of 5 minutes or less during any 2 consecutive hrs. Test Method 22 in App. A of part 60 of this chapter shall be used.	§ 63.11(b)(4) § 63.11(b)(5) § 63.11(b)(7)(i)	None	None
MTBE FL-2	EU	R1111	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(4)(A)	Visible emissions from a process gas flare shall not be permitted for more than five minutes in any two-hour period, except for upset emissions as provided in §101.222(b).	§ 111.111(a)(4)(A)(i) § 111.111(a)(4)(A)(ii)	§ 111.111(a)(4)(A)(ii)	None
MTBE FL-2	CD	60A	Opacity	40 CFR Part 60, Subpart A	§ 60.18(b) § 60.18(c)(1) § 60.18(c)(2) § 60.18(c)(3)(ii) § 60.18(c)(4)(ii) § 60.18(c)(6) § 60.18(e)	Flares shall comply with paragraphs (c)-(f) of § 60.18.	§ 60.18(d) § 60.18(f)(1) § 60.18(f)(2) § 60.18(f)(3) § 60.18(f)(4)	None	None
MTBE FL-2	EU	60Ja	H2S	40 CFR Part 60, Subpart Ja	§ 60.103a(h) [G]§ 60.103a(b) § 60.103a(c) [G]§ 60.103a(c)(1) [G]§ 60.103a(d) [G]§ 60.103a(e) § 60.103a(f)	Each owner or operator shall not burn in any affected flare any fuel gas that contains H2S in excess of 162 ppmv determined hourly on a 3-hour rolling average basis. The combustion in a flare of	§ 60.104a(a) § 60.104a(c) § 60.104a(j) [G]§ 60.104a(j)(4) [G]§ 60.107a(a)(2) § 60.107a(e) [G]§ 60.107a(e)(1) [G]§ 60.107a(e)(2)	§ 60.103a(a) § 60.103a(a)(1) [G]§ 60.103a(a)(2) § 60.103a(a)(3) [G]§ 60.103a(a)(3)(i) § 60.103a(a)(3)(ii) § 60.103a(a)(3)(iii) § 60.103a(a)(3)(iv)	[G]§ 60.103a(b) § 60.107a(i) [G]§ 60.107a(i)(2) [G]§ 60.108a(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						process upset gases or fuel gas that is released to the flare as a result of relief valve leakage or other emergency malfunctions is exempt from this limit.	§ 60.107a(f) [G]§ 60.107a(f)(1)	§ 60.103a(a)(3)(v) [G]§ 60.103a(a)(4) § 60.103a(a)(5) § 60.103a(a)(6) [G]§ 60.103a(e)(3) [G]§ 60.107a(a)(2) § 60.107a(e)(1) § 60.107a(e)(2) § 60.107a(f) § 60.107a(f)(1)(iii) § 60.108a(c) § 60.108a(c)(1) [G]§ 60.108a(c)(6) § 60.108a(c)(7) [G]§ 60.108a(d)	
MTBE FL-2	CD	63A	112(B) HAPS	40 CFR Part 63, Subpart A	§ 63.11(b)(4) § 63.11(b)(1) § 63.11(b)(2) § 63.11(b)(3) § 63.11(b)(5) § 63.11(b)(6)(ii) § 63.11(b)(7)(iii)	Flares shall be designed and operated with no visible emissions, except for periods of a total of 5 minutes or less during any 2 consecutive hrs. Test Method 22 in App. A of part 60 of this chapter shall be used.	§ 63.11(b)(4) § 63.11(b)(5) § 63.11(b)(7)(i)	None	None
MTBE-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No valve in liquid service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
MTBE-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No connector may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
MTBE-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No connector, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
MTBE-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(5)	No pressure relief valve in gaseous service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(C) § 115.324(4) § 115.324(5) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
MTBE-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(5)	No pressure relief valve in gaseous service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
MTBE-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No elevated valve may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(D) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
MTBE-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3)	No elevated valve, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.327(5)	calendar days after the leak is found, except as provided in §115.322(2).			
MTBE-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No compressor seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(A) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
MTBE-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3) § 115.327(6)	No compressor seal, as described in § 115.327(3), (5) or (6), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
MTBE-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No process drain may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(C) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
MTBE-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No process drain, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
MTBE-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No valve in liquid service, as described in § 115.327(3) or (5), may be	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.322(4) § 115.327(3) § 115.327(5)	allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).			
MTBE-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.322(5)	No valve (gaseous service) may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
MTBE-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(5)	No valve (gaseous service), as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
MTBE-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No pump seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(A) § 115.324(3) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
MTBE-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No pump seal, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
MTBE-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.327(1)	Valves of nominal size of 2" (5 cm) or less are exempt, provided allowable emissions from sources affected by this division after controls are applied with exemptions will not exceed by more than 5.0% such allowable emissions with no exemptions.	None	None	§ 115.327(1)(A) § 115.327(1)(B) § 115.327(1)(C)
MTBE-FUG	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for valves in heavy-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
MTBE-FUG	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for flanges or other connectors.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
MTBE-FUG	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for pressure relief devices in light-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
MTBE-FUG	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-4 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-4 for pressure relief devices in gas/vapor service.	[G]§ 60.482-4 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(3) [G]§ 60.486(e)(4) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 60.592(d)	§ 60.592(e)	
MTBE-FUG	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-8 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-8 for pumps in heavy-liquid service.	[G]§ 60.482-8 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
MTBE-FUG	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-6 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-6 for open-ended valves and lines.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
MTBE-FUG	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) § 60.482-10(e) [G]§ 60.482-10(g) § 60.482-10(h) § 60.482-10(m)	Comply with the requirements in as stated in §60.482-10 for closed-vent systems.	[G]§ 60.482-10(f) § 60.482-10(i) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.482-10(j) [G]§ 60.482-10(k) [G]§ 60.482-10(l) [G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
MTBE-FUG	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-3 [G]§ 60.482-9	Comply with the requirements as stated in §60.482-3 for compressors.	[G]§ 60.482-3 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
MTBE-FUG	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(d)	Comply with the requirements as stated in §60.482-1(d) for equipment in vacuum service.	None	§ 60.486(e) § 60.486(e)(1) § 60.486(e)(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
MTBE-FUG	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-5 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-5 for sampling connection systems.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
MTBE-FUG	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-2 [G]§ 60.482-9	Comply with the requirements as stated in §60.482-2 for pumps in light-liquid service.	[G]§ 60.482-2 § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d) § 60.593(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
MTBE-FUG	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) § 60.482-3(f) § 60.482-3(g)(1) § 60.482-3(g)(2) [G]§ 60.482-3(i) § 60.482-3(j) [G]§ 60.482-9 § 60.593(c)	Comply with the requirements as stated in §60.482-3 for reciprocating compressors that become subject under §60.14 and §60.15.	§ 60.482-3(f) § 60.482-3(g)(1) § 60.482-3(g)(2) [G]§ 60.482-3(i) § 60.482-3(j) § 60.485(a) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
MTBE-FUG	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.18 § 60.482-1(a) § 60.482-1(b) § 60.482-10(d) § 60.482-10(e) § 60.482-10(m)	Comply with the requirements in as stated in §60.482-10 for flares.	§ 60.485(a) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f) [G]§ 60.485(g) § 60.592(d)	[G]§ 60.486(a) [G]§ 60.486(d) § 60.486(e) § 60.486(e)(1) § 60.592(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.592(e)
MTBE-FUG	EU	60GGGAL L	VOC	40 CFR Part 60, Subpart GGG	§ 60.592(a) § 60.482-1(a) § 60.482-1(b) [G]§ 60.482-7 [G]§ 60.482-9	Comply with the requirements in as stated in §60.482-7 for valves in gas/vapor or light-liquid service.	[G]§ 60.482-7 [G]§ 60.483-1 [G]§ 60.483-2 § 60.485(a) [G]§ 60.485(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(d) § 60.487(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 60.483-1 [G]§ 60.483-2 § 60.592(b)		[G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f) § 60.592(d) § 60.593(d)	[G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) [G]§ 60.486(g) § 60.486(j) § 60.592(e)	§ 60.592(e)
MVRUF	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No elevated valve may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(D) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
MVRUF	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.327(1)	Valves of nominal size of 2" (5 cm) or less are exempt, provided allowable emissions from sources affected by this division after controls are applied with exemptions will not exceed by more than 5.0% such allowable emissions with no exemptions.	None	None	§ 115.327(1)(A) § 115.327(1)(B) § 115.327(1)(C)
MVRUF	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No pump seal, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
MVRUF	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No pump seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in	§ 115.324 § 115.324(1) § 115.324(1)(A) § 115.324(3) § 115.324(4) § 115.324(6)	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						§115.322(2).	[G]§ 115.325		
MVRUF	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(5)	No pressure relief valve in gaseous service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
MVRUF	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(5)	No valve (gaseous service), as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
MVRUF	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.322(5)	No valve (gaseous service) may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
MVRUF	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(5)	No pressure relief valve in gaseous service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(C) § 115.324(4) § 115.324(5) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
MVRUF	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet	§ 115.322(1) § 115.322(2)	No valve in liquid service, as described in §	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Ref B Counties	§ 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).			
MVRUF	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No elevated valve, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
MVRUF	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No compressor seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(A) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
MVRUF	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No connector may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
MVRUF	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.327(3) § 115.327(6)	No compressor seal, as described in § 115.327(3), (5) or (6), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
MVRUF	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No process drain may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(C) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
MVRUF	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No connector, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
MVRUF	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No process drain, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
MVRUF	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No valve in liquid service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
MVRUF	EU	63CCVVALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63,	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					requirements of 40 CFR Part 63, Subpart CC		Subpart CC		
OLEFLEX-FU	EU	60VV-ALL	VOC	40 CFR Part 60, Subpart VV	§ 60.482-1(d) § 60.486(k)	Equipment that is in vacuum service is excluded from the requirements of §60.482-2 to §60.482-10, if it is identified as required in §60.486(e)(5).	None	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(5) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
OLEFLEX-FU	EU	60VV-ALL	VOC	40 CFR Part 60, Subpart VV	§ 60.482-2(b)(1) § 60.482-1(a) § 60.482-1(b) § 60.482-1(g) § 60.482-2(a)(2) [G]§ 60.482-2(b)(2) § 60.482-2(c)(1) [G]§ 60.482-2(c)(2) § 60.482-2(d) [G]§ 60.482-2(d)(1) § 60.482-2(d)(2) § 60.482-2(d)(3) [G]§ 60.482-2(d)(4) [G]§ 60.482-2(d)(5) [G]§ 60.482-2(d)(6) [G]§ 60.482-2(e) § 60.482-2(f) [G]§ 60.482-2(g) § 60.482-2(h) § 60.482-9(a) § 60.482-9(b) [G]§ 60.482-9(d) § 60.482-9(f) § 60.486(k)	If an instrument reading of 10,000 ppm or greater is measured for pumps in light liquid service, a leak is detected.	§ 60.482-1(f)(1) § 60.482-1(f)(2) [G]§ 60.482-1(f)(3) § 60.482-2(a)(1) [G]§ 60.482-2(b)(2) [G]§ 60.482-2(d)(4) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f)	§ 60.482-1(g) [G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) [G]§ 60.486(h) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
OLEFLEX-FU	EU	60VV-ALL	VOC	40 CFR Part 60, Subpart VV	§ 60.482-3(a) § 60.482-1(a) § 60.482-1(b) § 60.482-1(g) [G]§ 60.482-3(b)	Each compressor shall be equipped with a seal system that includes a barrier fluid system and that prevents leakage of VOC to the	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f)	§ 60.482-1(g) [G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.482-3(c) § 60.482-3(d) § 60.482-3(e)(1) § 60.482-3(e)(2) § 60.482-3(f) § 60.482-3(g)(1) § 60.482-3(g)(2) § 60.482-3(h) [G]§ 60.482-3(i) § 60.482-3(j) § 60.482-9(a) § 60.482-9(b) § 60.486(k)	atmosphere, except as provided in §60.482-1(c) and paragraphs (h), (i), and (j) of this section.		§ 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(h) § 60.486(j)	
OLEFLEX-FU	EU	60VV-ALL	VOC	40 CFR Part 60, Subpart VV	§ 60.482-4(a) § 60.482-1(a) § 60.482-1(b) § 60.482-1(g) § 60.482-4(b)(1) § 60.482-4(c) § 60.482-4(d)(1) § 60.482-4(d)(2) § 60.482-9(a) § 60.482-9(b) § 60.486(k)	Except during pressure releases, each pressure relief device in gas/vapor service shall be operated with no detectable emissions, as indicated by an instrument reading of less than 500 ppm above background, as determined by the methods specified in § 60.485(c).	§ 60.482-4(b)(2) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) § 60.485(f)	§ 60.482-1(g) [G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(3) [G]§ 60.486(e)(4) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
OLEFLEX-FU	EU	60VV-ALL	VOC	40 CFR Part 60, Subpart VV	§ 60.482-5(a) § 60.482-1(a) § 60.482-1(b) § 60.482-1(g) [G]§ 60.482-5(b) § 60.482-5(c) § 60.486(k)	Each sampling connection system shall be equipped with a closed-purge, closed-loop, or closed-vent system, except as provided in §60.482-1(c) and paragraph (c) of this section.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f)	§ 60.482-1(g) [G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
OLEFLEX-FU	EU	60VV-ALL	VOC	40 CFR Part 60, Subpart VV	[G]§ 60.482-1(e) § 60.486(k)	Equipment that an owner or operator designates as being in VOC service less than 300 hours (hr)/yr is excluded from the requirements of §§ 60.482-2 through 60.482-10 if it is	None	§ 60.486 [G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(6) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						identified as required in §60.486(e)(6) and it meets any of the conditions specified in paragraphs (e)(1) through (3) of this section. §60.482-1(e)(1)-(3)			
OLEFLEX-FU	EU	60VV-ALL	VOC	40 CFR Part 60, Subpart VV	§ 60.482-7(b) § 60.482-1(a) § 60.482-1(b) § 60.482-1(g) § 60.482-7(d)(1) § 60.482-7(d)(2) [G]§ 60.482-7(e) [G]§ 60.482-7(f) [G]§ 60.482-7(g) [G]§ 60.482-7(h) § 60.482-9(a) § 60.482-9(b) [G]§ 60.482-9(c) § 60.482-9(e) § 60.482-9(f) § 60.486(k)	If an instrument reading of 10,000 ppm or greater is measured for valves in gas/vapor service and in light liquid service, a leak is detected.	§ 60.482-1(f)(1) § 60.482-1(f)(2) [G]§ 60.482-1(f)(3) § 60.482-7(a)(1) [G]§ 60.482-7(a)(2) § 60.482-7(c)(1)(i) § 60.482-7(c)(1)(ii) § 60.482-7(c)(2) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f)	§ 60.482-1(g) [G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
OLEFLEX-FU	EU	60VV-ALL	VOC	40 CFR Part 60, Subpart VV	§ 60.482-8(b) § 60.482-1(a) § 60.482-1(b) § 60.482-1(g) § 60.482-8(a) § 60.482-8(a)(2) § 60.482-8(c)(1) § 60.482-8(c)(2) § 60.482-8(d) § 60.482-9(a) § 60.482-9(b) [G]§ 60.482-9(d) § 60.482-9(f) § 60.486(k)	For pumps in heavy liquid service, if an instrument reading of 10,000 ppm or greater is measured, a leak is detected.	§ 60.482-8(a)(1) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f)	§ 60.482-1(g) [G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
OLEFLEX-FU	EU	60VV-ALL	VOC	40 CFR Part 60, Subpart VV	§ 60.482-8(b) § 60.482-1(a)	For valves in heavy liquid service, if an instrument	§ 60.482-8(a)(1) § 60.485(a)	§ 60.482-1(g) [G]§ 60.486(a)	§ 60.487(a) [G]§ 60.487(b)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.482-1(b) § 60.482-1(g) § 60.482-8(a) § 60.482-8(a)(2) § 60.482-8(c)(1) § 60.482-8(c)(2) § 60.482-8(d) § 60.482-9(a) § 60.482-9(b) § 60.482-9(e) § 60.482-9(f) § 60.486(k)	reading of 10,000 ppm or greater is measured, a leak is detected.	[G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f)	[G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j)	[G]§ 60.487(c) § 60.487(e)
OLEFLEX-FU	EU	60VV-ALL	VOC	40 CFR Part 60, Subpart VV	§ 60.482-8(b) § 60.482-1(a) § 60.482-1(b) § 60.482-1(g) § 60.482-8(a) § 60.482-8(a)(2) § 60.482-8(c)(1) § 60.482-8(c)(2) § 60.482-8(d) § 60.482-9(a) § 60.482-9(b) § 60.486(k)	For pressure relief devices in light liquid or in heavy liquid service, if an instrument reading of 10,000 ppm or greater is measured, a leak is detected.	§ 60.482-8(a)(1) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) [G]§ 60.485(e) § 60.485(f)	§ 60.482-1(g) [G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
OLEFLEX-FU	EU	60VV-ALL	VOC	40 CFR Part 60, Subpart VV	§ 60.482-8(b) § 60.482-1(a) § 60.482-1(b) § 60.482-1(g) § 60.482-8(a) § 60.482-8(a)(2) § 60.482-8(c)(1) § 60.482-8(c)(2) § 60.482-8(d) § 60.482-9(a) § 60.482-9(b) § 60.486(k)	For flanges and other connectors, if an instrument reading of 10,000 ppm or greater is measured, a leak is detected.	§ 60.482-8(a)(1) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(d) § 60.485(f)	§ 60.482-1(g) [G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e)
OLEFLEX-FU	EU	60VV-ALL	VOC	40 CFR Part 60, Subpart VV	§ 60.482-6(a)(1) § 60.482-1(a)	Each open-ended valve or line shall be equipped with a	§ 60.485(a) [G]§ 60.485(b)	§ 60.482-1(g) [G]§ 60.486(a)	§ 60.487(a) [G]§ 60.487(b)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.482-1(b) § 60.482-1(g) § 60.482-6(a)(2) § 60.482-6(b) § 60.482-6(c) § 60.482-6(d) § 60.482-6(e) § 60.486(k)	cap, blind flange, plug, or a second valve, except as provided in §60.482-1(c) and paragraphs (d) and (e) of this section.	[G]§ 60.485(d) § 60.485(f)	§ 60.486(e) § 60.486(e)(1) § 60.486(j)	[G]§ 60.487(c) § 60.487(e)
RAIL-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.327(1)	Valves of nominal size of 2" (5 cm) or less are exempt, provided allowable emissions from sources affected by this division after controls are applied with exemptions will not exceed by more than 5.0% such allowable emissions with no exemptions.	None	None	§ 115.327(1)(A) § 115.327(1)(B) § 115.327(1)(C)
RAIL-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No pump seal, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
RAIL-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No connector may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
RAIL-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No pump seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days	§ 115.324 § 115.324(1) § 115.324(1)(A) § 115.324(3)	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						after the leak is found, except as provided in §115.322(2).	§ 115.324(4) § 115.324(6) [G]§ 115.325		
RAIL-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(5)	No valve (gaseous service), as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
RAIL-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.322(5)	No valve (gaseous service) may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
RAIL-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No valve in liquid service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
RAIL-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No valve in liquid service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
RAIL-FUG	EU	R5322ALL	VOC	30 TAC Chapter	§ 115.322(1)	No process drain, as	[G]§ 115.325	[G]§ 115.326(1)	[G]§ 115.326(1)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				115, Fugitives Pet Ref B Counties	§ 115.322(2) § 115.322(3) § 115.327(3)	described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).		§ 115.326(5)	§ 115.327(4)
RAIL-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No process drain may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(C) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
RAIL-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3) § 115.327(6)	No compressor seal, as described in § 115.327(3), (5) or (6), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
RAIL-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No compressor seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(A) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
RAIL-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No elevated valve, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
RAIL-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No elevated valve may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(D) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
RAIL-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(5)	No pressure relief valve in gaseous service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
RAIL-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(5)	No pressure relief valve in gaseous service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(C) § 115.324(4) § 115.324(5) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
RAIL-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No connector, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
RAIL-FUG	EU	63CCALL	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					and/or equipment specification requirements of 40 CFR Part 63, Subpart CC		requirements of 40 CFR Part 63, Subpart CC	Part 63, Subpart CC	
RAILRACK1	EU	R5211	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(b)(3)(A) § 115.212(b)(2) § 115.214(b)(1)(B) § 115.214(b)(1)(D) § 115.214(b)(1)(D)(i)	Plants, excluding gasoline bulk plants, which load <20,000 gallons of VOC into transport vessels per day with a true vapor pressure of 1.5 psia or greater are exempt from this division, except for the specified requirements.	§ 115.214(b)(1)(A) § 115.214(b)(1)(A)(i) § 115.215 § 115.215(4)	§ 115.216 § 115.216(2) § 115.216(3)(B) § 115.216(3)(D)	None
SHIPDOCK S	EU	61BB	Benzene	40 CFR Part 61, Subpart BB	§ 61.300(b)	Any affected facility as per § 61.300(a), loading only liquid containing < 70 weight-percent benzene is exempt from this subpart, except for the recordkeeping and reporting in § 61.305(i).	None	[G]§ 61.305(i)	[G]§ 61.305(i)
SHIPDOCK S	EU	63CC	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC
SHIPDOCK S	EU	63Ya	Exempt	40 CFR Part 63, Subpart Y	§ 63.560(a)(2) § 153.282 § 63.560(a)(4)	Existing sources with emissions less than 10 and 25 tons must meet the submerged fill standards of 46 CFR 153.282. This	§ 63.565(l)	§ 63.567(j)(4)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						submerged fill requirement does not apply to petroleum refineries.			
SHIPDOCK S	EU	63Yb	112(B) HAPS	40 CFR Part 63, Subpart Y	§ 63.562(b) [G]§ 63.562(b)(1) § 63.562(b)(2) § 63.562(b)(5) [G]§ 63.562(b)(6) § 63.562(e) § 63.562(e)(1) [G]§ 63.562(e)(2) [G]§ 63.562(e)(3) § 63.562(e)(4) § 63.562(e)(5) § 63.562(e)(6) § 63.562(e)(7) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) [G]§ 63.563(a)(1) § 63.563(a)(2) § 63.563(a)(3)	Marine tank vessel loading operations shall apply MACT standards, except for the VMT source.	[G]§ 63.562(b)(6) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) § 63.563(b)(10) § 63.563(b)(3) § 63.563(b)(6) § 63.563(b)(6)(i) § 63.563(b)(6)(iii) [G]§ 63.563(c) § 63.564(a)(2) § 63.564(a)(3) § 63.564(a)(4) § 63.564(b)(3) § 63.564(c) [G]§ 63.565(b) § 63.565(l)	[G]§ 63.562(b)(6) § 63.562(e)(5) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) § 63.564(b)(3) § 63.567(f) [G]§ 63.567(g) § 63.567(j)(1) § 63.567(j)(2) [G]§ 63.567(k)	[G]§ 63.562(b)(6) § 63.562(e)(7)(ii) § 63.567(b)(5) § 63.567(c) § 63.567(e)(1) [G]§ 63.567(e)(2) § 63.567(e)(3) § 63.567(e)(4) § 63.567(e)(5) § 63.567(e)(6) § 63.567(f) § 63.567(j)(3) § 63.567(m) § 63.567(n)(1) § 63.567(n)(2)
SHIPDOCK S	EU	63Yb	VOC	40 CFR Part 63, Subpart Y	§ 63.562(c) [G]§ 63.562(c)(2) § 63.562(c)(3) § 63.562(c)(4) [G]§ 63.562(c)(6) § 63.562(e) § 63.562(e)(1) [G]§ 63.562(e)(2) [G]§ 63.562(e)(3) § 63.562(e)(4) § 63.562(e)(5) § 63.562(e)(6) § 63.562(e)(7) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) [G]§ 63.563(a)(1) § 63.563(a)(2)	RACT standards, except the VMT source.	[G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) § 63.563(b)(3) § 63.563(b)(6) § 63.563(b)(6)(i) § 63.563(b)(6)(iii) [G]§ 63.563(c) § 63.564(a)(2) § 63.564(a)(3) § 63.564(a)(4) § 63.564(b)(3) § 63.564(c) [G]§ 63.565(b) § 63.565(l)	§ 63.562(e)(5) [G]§ 63.562(e)(7)(i) § 63.562(e)(7)(ii) § 63.564(b)(3) § 63.567(f) [G]§ 63.567(g) § 63.567(j)(1) [G]§ 63.567(k)	§ 63.562(c)(1) § 63.562(e)(7)(ii) [G]§ 63.567(b)(2) § 63.567(b)(3) [G]§ 63.567(b)(4) § 63.567(c) § 63.567(e)(1) [G]§ 63.567(e)(2) § 63.567(e)(3) § 63.567(e)(4) § 63.567(e)(5) § 63.567(e)(6) § 63.567(f) § 63.567(m) § 63.567(n)(1) § 63.567(n)(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.563(a)(3)				
SRU	EU	REG2	SO ₂	30 TAC Chapter 112, Sulfur Compounds	§ 112.7(a) § 112.7(b)	No person may cause, suffer, allow, or permit emissions of SO ₂ to exceed the emission limits specified for stack effluent flow rates < 4,000 scfm as determined by the specified equation.	§ 112.2(a) ** See CAM Summary	§ 112.2(c)	§ 112.2(b)
SRU	PRO	60J	SO ₂	40 CFR Part 60, Subpart J	§ 60.104(a)(2)(i)	No owner or operator subject to the provisions of this subpart shall discharge or cause the discharge into the atmosphere from any Claus sulfur recovery plant with a reduction control system followed by incineration any gases containing in excess of 250 ppm by volume of SO ₂ at zero percent excess air.	[G]§ 60.105(a)(5) § 60.106(a) [G]§ 60.106(f)	[G]§ 60.105(a)(5)	§ 60.105(e)(4)(i) § 60.107(d) § 60.107(f) § 60.107(g)
SRU	EU	60J-AMP	SO ₂	40 CFR Part 60, Subpart J	§ 60.104(a)(2)(i)	No owner or operator subject to the provisions of this subpart shall discharge or cause the discharge into the atmosphere from any Claus sulfur recovery plant with a reduction control system followed by incineration any gases containing in excess of 250 ppm by volume of SO ₂ at zero percent excess air.	§ 60.106(a) [G]§ 60.106(f) ** See Alternative Requirement	None	§ 60.107(d) § 60.107(f) § 60.107(g)
SRU	EU	63UUU	112(B) HAPS	40 CFR Part 63, Subpart UUU	§ 63.1560 The permit holder shall comply with the applicable	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart UUU	The permit holder shall comply with the applicable monitoring and	The permit holder shall comply with the applicable recordkeeping	The permit holder shall comply with the applicable reporting requirements of 40 CFR

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart UUU		testing requirements of 40 CFR Part 63, Subpart UUU	requirements of 40 CFR Part 63, Subpart UUU	Part 63, Subpart UUU
SRU3	EU	REG2	SO ₂	30 TAC Chapter 112, Sulfur Compounds	§ 112.7(a) § 112.7(b)	No person may cause, suffer, allow, or permit emissions of SO ₂ to exceed the emission limits specified for stack effluent flow rates < 4,000 scfm as determined by the specified equation.	§ 112.2(a) ** See CAM Summary	§ 112.2(c)	§ 112.2(b)
SRU3	PRO	60J	SO ₂	40 CFR Part 60, Subpart J	§ 60.104(a)(2)(i)	No owner or operator subject to the provisions of this subpart shall discharge or cause the discharge into the atmosphere from any Claus sulfur recovery plant with a reduction control system followed by incineration any gases containing in excess of 250 ppm by volume of SO ₂ at zero percent excess air.	[G]§ 60.105(a)(5) § 60.106(a) [G]§ 60.106(f)	[G]§ 60.105(a)(5)	§ 60.105(e)(4)(i) § 60.107(d) § 60.107(f) § 60.107(g)
SRU3	EU	60J-AMP	SO ₂	40 CFR Part 60, Subpart J	§ 60.104(a)(2)(i)	No owner or operator subject to the provisions of this subpart shall discharge or cause the discharge into the atmosphere from any Claus sulfur recovery plant with a reduction control system followed by incineration any gases containing in excess of 250 ppm by volume of SO ₂ at zero percent excess air.	§ 60.106(a) [G]§ 60.106(f) ** See Alternative Requirement	None	§ 60.107(d) § 60.107(f) § 60.107(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
SRU3	EU	63UUU	112(B) HAPS	40 CFR Part 63, Subpart UUU	§ 63.1560 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart UUU	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart UUU	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart UUU	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart UUU	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart UUU
T-RACK	EU	R5211a	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.211(2) § 115.212(b)(3)(A) § 115.212(b)(3)(A)(i) § 115.212(b)(3)(B) [G]§ 115.212(b)(3)(C) § 115.212(b)(3)(E) § 115.212(b)(4)(A) § 115.212(b)(4)(B) § 115.212(b)(4)(C) § 115.214(b)(1)(B) § 115.214(b)(1)(C)	Gasoline terminals, in the covered attainment counties, shall ensure that VOC emissions do not exceed 0.17lb/1,000gal, and until 4/30/00 in Gregg, Nueces, and Victoria Counties 0.67lb/1,000gal.	§ 115.212(b)(3)(B) [G]§ 115.212(b)(3)(C) § 115.212(b)(4)(C) § 115.214(b)(1)(A) § 115.214(b)(1)(A)(i) § 115.214(b)(1)(A)(ii) § 115.214(b)(1)(A)(iii) § 115.214(b)(2) § 115.215 § 115.215(1) § 115.215(10) [G]§ 115.215(2) § 115.215(4) § 115.215(5) § 115.215(6) § 115.215(9) § 115.216(1) § 115.216(1)(A) § 115.216(1)(A)(iv) ** See CAM Summary	§ 115.216 § 115.216(1) § 115.216(1)(A) § 115.216(1)(A)(iv) § 115.216(2) § 115.216(3)(A) § 115.216(3)(A)(i) § 115.216(3)(A)(ii) § 115.216(3)(A)(iii) § 115.216(3)(B) [G]§ 115.216(3)(E)	None
T-RACK	EU	R5211b	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(b)(2) § 115.212(b)(2) § 115.214(b)(1)(B)	Vapor pressure (at land-based operations). All land-based loading and	§ 115.214(b)(1)(A) § 115.214(b)(1)(A)(i)	§ 115.216 § 115.216(2) § 115.216(3)(B)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.214(b)(1)(D) § 115.214(b)(1)(D)(i)	unloading of VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division except as specified.	§ 115.215 § 115.215(4)		
T-RACK	EU	R5211c	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(b)(4) § 115.212(b)(2) § 115.214(b)(1)(B) § 115.214(b)(1)(D) § 115.214(b)(1)(D)(i)	Crude oil, condensate, and liquefied petroleum gas. All loading and unloading of crude oil, condensate, and liquefied petroleum gas is exempt from division, except for the specified requirements.	§ 115.214(b)(1)(A) § 115.214(b)(1)(A)(i)	§ 115.216 § 115.216(3)(A) § 115.216(3)(A)(ii) § 115.216(3)(B)	None
T-RACK	EU	63CC	112(B) HAPS	40 CFR Part 63, Subpart CC	§ 63.640(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart CC	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart CC
TRUCKCOM B	EU	60J	Hydrogen Sulfide	40 CFR Part 60, Subpart J	§ 60.104(a)(1) § 60.105(a)(4)(iv) § 60.105(a)(4)(iv)(D)	No owner or operator subject to the provisions of this subpart shall burn in any fuel gas combustion device any fuel gas that contains hydrogen sulfide (H ₂ S) in excess of 230 mg/dscm (0.10 gr/dscf).	[G]§ 60.105(b) § 60.106(a)	[G]§ 60.105(b) § 60.107(e)	[G]§ 60.105(b) § 60.107(f) § 60.107(g)
WWTP-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.327(1)	Valves of nominal size of 2" (5 cm) or less are exempt, provided allowable emissions from sources affected by this division after controls are applied	None	None	§ 115.327(1)(A) § 115.327(1)(B) § 115.327(1)(C)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						with exemptions will not exceed by more than 5.0% such allowable emissions with no exemptions.			
WWTP-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No pump seal, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
WWTP-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No pump seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(A) § 115.324(3) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
WWTP-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(5)	No valve (gaseous service), as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
WWTP-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.322(5)	No valve (gaseous service) may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
WWTP-FUG	EU	R5322ALL	VOC	30 TAC Chapter	§ 115.322(1)	No valve in liquid service,	[G]§ 115.325	[G]§ 115.326(1)	[G]§ 115.326(1)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				115, Fugitives Pet Ref B Counties	§ 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).		§ 115.326(5)	§ 115.327(4)
WWTP-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No valve in liquid service may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(B) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
WWTP-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No process drain, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
WWTP-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No process drain may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(C) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
WWTP-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3) § 115.327(6)	No compressor seal, as described in § 115.327(3), (5) or (6), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						in §115.322(2).			
WWTP-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No compressor seal may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(2) § 115.324(2)(A) § 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
WWTP-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4) § 115.327(3) § 115.327(5)	No elevated valve, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
WWTP-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(4)	No elevated valve may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324 § 115.324(1) § 115.324(1)(D) § 115.324(4) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)
WWTP-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(5)	No pressure relief valve in gaseous service, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
WWTP-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.322(5)	No pressure relief valve in gaseous service may be allowed to have a VOC leak as defined in §101.1 for	§ 115.324 § 115.324(2) § 115.324(2)(C) § 115.324(4)	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.324(7) [G]§ 115.326(1) § 115.327(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324(5) § 115.324(6) [G]§ 115.324(7) [G]§ 115.325		
WWTP-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3) § 115.327(3)	No connector, as described in § 115.327(3) or (5), may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	[G]§ 115.325	[G]§ 115.326(1) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
WWTP-FUG	EU	R5322ALL	VOC	30 TAC Chapter 115, Fugitives Pet Ref B Counties	§ 115.322(1) § 115.322(2) § 115.322(3)	No connector may be allowed to have a VOC leak as defined in §101.1 for more than 15 calendar days after the leak is found, except as provided in §115.322(2).	§ 115.324(4) § 115.324(6) [G]§ 115.325	[G]§ 115.326(1) [G]§ 115.326(2) [G]§ 115.326(3) § 115.326(5)	[G]§ 115.326(1) § 115.327(4)
WWTP-FUG	CD	61FF-DRAINS	Benzene	40 CFR Part 61, Subpart FF	§ 61.349(a) § 61.349(a)(1)(i) § 61.349(a)(1)(iii) § 61.349(a)(1)(iv) § 61.349(a)(2)(ii) § 61.349(b) § 61.349(e) § 61.349(f) § 61.349(g)	For each closed-vent system and control device used to comply with §§61.343-61.348, properly design, install, operate, and maintain the closed-vent system and control device.	§ 61.349(a)(1)(i) § 61.349(e) § 61.349(f) § 61.354(d) [G]§ 61.355(h) § 61.355(i)(1) § 61.355(i)(2) § 61.355(i)(3)(i) § 61.355(i)(3)(ii) § 61.355(i)(3)(ii)(A) § 61.355(i)(3)(ii)(B) § 61.355(i)(3)(ii)(C) § 61.355(i)(3)(iii) § 61.355(i)(3)(iv) § 61.355(i)(4)	§ 61.355(i)(1) § 61.355(i)(3)(ii)(A) § 61.356(f) § 61.356(f)(1) § 61.356(f)(2)(i)(G) [G]§ 61.356(f)(3) § 61.356(h) § 61.356(j) § 61.356(j)(1) § 61.356(j)(10) § 61.356(j)(2) § 61.356(j)(3)	None

Additional Monitoring Requirements

Compliance Assurance Monitoring Summary	253
Periodic Monitoring Summary	262

CAM Summary

Unit/Group/Process Information	
ID No.: 24-ST-01	
Control Device ID No.: 24-ST-02	Control Device Type: Wet scrubber
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart J	SOP Index No.: 60J
Pollutant: PM	Main Standard: § 60.102(a)(1)
Monitoring Information	
Indicator: Pressure Drop	
Minimum Frequency: four times per hour	
Averaging Period: one hour	
Deviation Limit: Min. flue gas pressure drop across the filtering modules & cyclolabs is 80% of the avg. value recorded from the most recent performance test. The TCEQ will be notified of changes to the deviation limit from the most recent stack test within 60 days.	
<p>CAM Text: Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following:</p> <ul style="list-style-type: none"> ± 1 inch water gauge pressure (± 250 pascals); or ± 2% of span. 	

CAM Summary

Unit/Group/Process Information	
ID No.: 24-ST-01	
Control Device ID No.: 24-ST-02	Control Device Type: Wet scrubber
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart J	SOP Index No.: 60J
Pollutant: PM	Main Standard: § 60.102(a)(1)
Monitoring Information	
Indicator: Liquid Supply Pressure	
Minimum Frequency: four times per hour	
Averaging Period: one hour	
Deviation Limit: Minimum water pressure to filtering modules is 80% of the average value recorded from the most recent performance test. The TCEQ will be notified of changes to the deviation limit from the most recent stack test within 60 days after the stack sample	
<p>CAM Text: Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following:</p> <ul style="list-style-type: none"> ± 5% of span; or ± 5% of design liquid supply pressure. 	

CAM Summary

Unit/Group/Process Information	
ID No.: 24-ST-01	
Control Device ID No.: 24-ST-02	Control Device Type: Wet scrubber
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart J	SOP Index No.: 60J
Pollutant: PM (Opacity)	Main Standard: § 60.102(a)(2)
Monitoring Information	
Indicator: Pressure Drop	
Minimum Frequency: four times per hour	
Averaging Period: one hour	
Deviation Limit: Min. flue gas pressure drop across the filtering modules & cyclolabs is 80% of the avg. value recorded from the most recent performance test. The TCEQ will be notified of changes to the deviation limit from the most recent stack test within 60 days.	
CAM Text: Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following: ± 1 inch water gauge pressure (± 250 pascals); or ± 2% of span.	

CAM Summary

Unit/Group/Process Information	
ID No.: 24-ST-01	
Control Device ID No.: 24-ST-02	Control Device Type: Wet scrubber
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart J	SOP Index No.: 60J
Pollutant: PM (Opacity)	Main Standard: § 60.102(a)(2)
Monitoring Information	
Indicator: Liquid Supply Pressure	
Minimum Frequency: four times per hour	
Averaging Period: one hour	
Deviation Limit: Minimum water pressure to filtering modules is 80% of the average value recorded from the most recent performance test. The TCEQ will be notified of changes to the deviation limit from the most recent stack test within 60 days after the stack sample	
CAM Text: Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following: <ul style="list-style-type: none"> ± 5% of span; or ± 5% of design liquid supply pressure. 	

CAM Summary

Unit/Group/Process Information	
ID No.: GRP-EPN121	
Control Device ID No.: 24-ST-02	Control Device Type: Wet scrubber
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Nonagricultural Processes	SOP Index No.: R1151
Pollutant: PM	Main Standard: § 111.151(a)
Monitoring Information	
Indicator: Pressure Drop	
Minimum Frequency: four times per hour	
Averaging Period: one hour	
Deviation Limit: Minimum flue gas pressure drop across the filtering modules and cyclolabs of 10.08 inches of water.	
<p>CAM Text: Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following:</p> <ul style="list-style-type: none"> ± 1 inch water gauge pressure (± 250 pascals); or ± 2% of span. 	

CAM Summary

Unit/Group/Process Information	
ID No.: GRP-EPN121	
Control Device ID No.: 24-ST-02	Control Device Type: Wet scrubber
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Nonagricultural Processes	SOP Index No.: R1151
Pollutant: PM	Main Standard: § 111.151(a)
Monitoring Information	
Indicator: Liquid Supply Pressure	
Minimum Frequency: four times per hour	
Averaging Period: one hour	
Deviation Limit: Minimum water pressure to filtering modules of 40 psig.	
<p>CAM Text: Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following:</p> <ul style="list-style-type: none"> ± 5% of span; or ± 5% of design liquid supply pressure. 	

CAM Summary

Unit/Group/Process Information	
ID No.: SRU	
Control Device ID No.: SULFTEN	Control Device Type: Sulfur recovery unit with incinerator
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 112, Sulfur Compounds	SOP Index No.: REG2
Pollutant: SO ₂	Main Standard: § 112.7(a)
Monitoring Information	
Indicator: Sulfur Dioxide Concentration	
Minimum Frequency: four times per hour	
Averaging Period: one hour	
Deviation Limit: 2493.1 lbs/hr SO ₂	
<p>CAM Text: Use a continuous emission monitoring system (CEMS) to measure and record sulfur dioxide emissions in the exhaust stream of the control device. The CEMS shall be operated in accordance with the monitoring requirements of 40 CFR § 60.13 and the performance specifications of 40 CFR Part 60, Appendix B. In addition, monitor oxygen or carbon dioxide with a CEMS operated in accordance with above CEMS procedures.</p>	

CAM Summary

Unit/Group/Process Information	
ID No.: SRU3	
Control Device ID No.: SCOT	Control Device Type: Sulfur recovery unit with incinerator
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 112, Sulfur Compounds	SOP Index No.: REG2
Pollutant: SO ₂	Main Standard: § 112.7(a)
Monitoring Information	
Indicator: Sulfur Dioxide Concentration	
Minimum Frequency: four times per hour	
Averaging Period: one hour	
Deviation Limit: 2667.5 lbs/hr SO ₂	
<p>CAM Text: Use a continuous emission monitoring system (CEMS) to measure and record sulfur dioxide emissions in the exhaust stream of the control device. The CEMS shall be operated in accordance with the monitoring requirements of 40 CFR § 60.13 and the performance specifications of 40 CFR Part 60, Appendix B. In addition, monitor oxygen or carbon dioxide with a CEMS operated in accordance with above CEMS procedures.</p>	

CAM Summary

Unit/Group/Process Information	
ID No.: T-RACK	
Control Device ID No.: TRUCKCOMB	Control Device Type: Vapor combustor
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Loading and Unloading of VOC	SOP Index No.: R5211a
Pollutant: VOC	Main Standard: § 115.211(2)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: four times per hour	
Averaging Period: one hour	
Deviation Limit: Minimum combustion temperature is the average value recorded from the most recent performance test. The TCEQ will be notified of the changes to the deviation limit from the most recent stack test within 60 days after the stack sampling is completed	
<p>CAM Text: The monitoring device should be installed in the combustion chamber or immediately downstream of the combustion chamber. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following:</p> <ul style="list-style-type: none"> ± 2% of reading; or ± 2.5 degrees Celsius. 	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: 02-V-12	
Control Device ID No.: MFL-1	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121
Pollutant: VOC	Main Standard: § 115.122(b)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Once per hour	
Averaging Period: N/A	
Deviation Limit: Any monitoring which indicates the lack of a pilot flame shall be considered and reported as a deviation when vent is routed to the flare, MFL-1, for vapor control.	
<p>Periodic Monitoring Text: Measure and record the presence of the pilot flame or maintain records of alarm events and duration of alarm events. The presence of a flare pilot flame shall be monitored using a thermocouple or any other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. The monitoring instrumentation shall be maintained, calibrated and operated in accordance with manufacturer's specifications or other written procedures. Any monitoring data which indicates the lack of a pilot flame shall be considered and reported as a deviation.</p>	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: 38-V-54	
Control Device ID No.: 38-H-01	Control Device Type: Steam generating unit (boiler)/process heater (design heat input is greater than or equal to 44 megawatts)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121
Pollutant: VOC	Main Standard: § 115.122(b)
Monitoring Information	
Indicator: Period of Operation	
Minimum Frequency: N/A	
Averaging Period: N/A	
Deviation Limit: All periods of operation that are not recorded are to be considered and reported as a deviation when vent is routed to the Oleflex Charge Heater, 38-H-01, for vapor control.	
Periodic Monitoring Text: Monitor and record the periods of operation of the steam generating units or process heater. All periods that are not recorded shall be considered and reported as a deviation. The records must be readily available for inspection.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: 38-V-55	
Control Device ID No.: 38-H-02	Control Device Type: Steam generating unit (boiler)/process heater (design heat input is greater than or equal to 44 megawatts)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121
Pollutant: VOC	Main Standard: § 115.122(b)
Monitoring Information	
Indicator: Period of Operation	
Minimum Frequency: N/A	
Averaging Period: N/A	
Deviation Limit: All periods of operation that are not recorded are to be considered and reported as a deviation when vent is routed to the Oleflex Interheater, 38-H-02, for vapor control.	
Periodic Monitoring Text: Monitor and record the periods of operation of the steam generating units or process heater. All periods that are not recorded shall be considered and reported as a deviation. The records must be readily available for inspection.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: 44-V-01	
Control Device ID No.: GF-1	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121
Pollutant: VOC	Main Standard: § 115.122(b)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Once per hour	
Averaging Period: N/A	
Deviation Limit: Any monitoring which indicates the lack of a pilot flame shall be considered and reported as a deviation when vent is routed to the flare, GF-1, for vapor control.	
<p>Periodic Monitoring Text: Measure and record the presence of the pilot flame or maintain records of alarm events and duration of alarm events. The presence of a flare pilot flame shall be monitored using a thermocouple or any other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. The monitoring instrumentation shall be maintained, calibrated and operated in accordance with manufacturer's specifications or other written procedures. Any monitoring data which indicates the lack of a pilot flame shall be considered and reported as a deviation.</p>	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: 47-V-02	
Control Device ID No.: 47-H-01	Control Device Type: Steam generating unit (boiler)/process heater (design heat input is greater than or equal to 44 megawatts)
Control Device ID No.: 47-H-02	Control Device Type: Steam generating unit (boiler)/process heater (design heat input is greater than or equal to 44 megawatts)
Control Device ID No.: 47-H-03	Control Device Type: Steam generating unit (boiler)/process heater (design heat input is greater than or equal to 44 megawatts)
Control Device ID No.: 47-H-04	Control Device Type: Steam generating unit (boiler)/process heater (design heat input is greater than or equal to 44 megawatts)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121
Pollutant: VOC	Main Standard: § 115.122(b)
Monitoring Information	
Indicator: Period of Operation	
Minimum Frequency: N/A	
Averaging Period: N/A	
Deviation Limit: All periods of operation that are not recorded are to be considered and reported as a deviation when vent is routed to the Hydrocracker heaters, 47-H-01, 47-H-02, 47-H-03, & 47-H-04, for vapor control.	
Periodic Monitoring Text: Monitor and record the periods of operation of the steam generating units or process heater. All periods that are not recorded shall be considered and reported as a deviation. The records must be readily available for inspection.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: 48-V-01	
Control Device ID No.: 48-H-01	Control Device Type: Steam generating unit (boiler)/process heater (design heat input is greater than or equal to 44 megawatts)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121
Pollutant: VOC	Main Standard: § 115.122(b)
Monitoring Information	
Indicator: Period of Operation	
Minimum Frequency: N/A	
Averaging Period: N/A	
Deviation Limit: All periods of operation that are not recorded are to be considered and reported as a deviation when vent is routed to the NHT heater, 48-H-01, for vapor control.	
Periodic Monitoring Text: Monitor and record the periods of operation of the steam generating units or process heater. All periods that are not recorded shall be considered and reported as a deviation. The records must be readily available for inspection.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: 49-V-01	
Control Device ID No.: GF-1	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121
Pollutant: VOC	Main Standard: § 115.122(b)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Once per hour	
Averaging Period: N/A	
Deviation Limit: Any monitoring which indicates the lack of a pilot flame shall be considered and reported as a deviation when vent is routed to the flare, GF-1, for vapor control.	
<p>Periodic Monitoring Text: Measure and record the presence of the pilot flame or maintain records of alarm events and duration of alarm events. The presence of a flare pilot flame shall be monitored using a thermocouple or any other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. The monitoring instrumentation shall be maintained, calibrated and operated in accordance with manufacturer's specifications or other written procedures. Any monitoring data which indicates the lack of a pilot flame shall be considered and reported as a deviation.</p>	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: 70-TK-137	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-b
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: N/A	
Deviation Limit: Any monitoring data in which the roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered a deviation.	
Periodic Monitoring Text: Visually inspect and record the inspection of the internal floating roof to ensure: the roof is floating on the surface of the VOC and, liquid has not accumulated on the internal floating roof, the seals are not detached, and there are no holes or tears in the seal fabric. Any monitoring data in which the roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: 70-TK-137	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-c
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: N/A	
Deviation Limit: Any monitoring data in which the roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered a deviation.	
Periodic Monitoring Text: Visually inspect and record the inspection of the internal floating roof to ensure: the roof is floating on the surface of the VOC and, liquid has not accumulated on the internal floating roof, the seals are not detached, and there are no holes or tears in the seal fabric. Any monitoring data in which the roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: 70-TK-137	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart K	SOP Index No.: 60K-c
Pollutant: VOC	Main Standard: § 60.112(a)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: N/A	
<p>Deviation Limit: Any monitoring data in which the roof is not floating on the surface of the VOC, if liquid has accumulated on the IFR, the seals are detached, or if there are holes or tears in the seal fabric shall be considered a deviation.</p> <p>Periodic Monitoring Text: Visually inspect and record the inspection of the internal floating roof to ensure: the roof is floating on the surface of the VOC and, liquid has not accumulated on the internal floating roof, the seals are not detached, and there are no holes or tears in the seal fabric. Any monitoring data in which the roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation.</p>	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: 70-TK-137	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart K	SOP Index No.: 60K-d
Pollutant: VOC	Main Standard: § 60.112(a)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: N/A	
<p>Deviation Limit: Any monitoring data in which the roof is not floating on the surface of the VOC, if liquid has accumulated on the IFR, the seals are detached, or if there are holes or tears in the seal fabric shall be considered a deviation.</p> <p>Periodic Monitoring Text: Visually inspect and record the inspection of the internal floating roof to ensure: the roof is floating on the surface of the VOC and, liquid has not accumulated on the internal floating roof, the seals are not detached, and there are no holes or tears in the seal fabric. Any monitoring data in which the roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation.</p>	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: 73-TK-168	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-d
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: N/A	
Deviation Limit: Any monitoring data in which the roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be reported as a deviation.	
Periodic Monitoring Text: Visually inspect and record the inspection of the internal floating roof to ensure: the roof is floating on the surface of the VOC and, liquid has not accumulated on the internal floating roof, the seals are not detached, and there are no holes or tears in the seal fabric. Any monitoring data in which the roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: 83-V-98	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-b
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: N/A	
Deviation Limit: Any monitoring data in which the roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered a deviation.	
Periodic Monitoring Text: Visually inspect and record the inspection of the internal floating roof to ensure: the roof is floating on the surface of the VOC and, liquid has not accumulated on the internal floating roof, the seals are not detached, and there are no holes or tears in the seal fabric. Any monitoring data in which the roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: 83-V-98	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-c
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: N/A	
<p>Deviation Limit: Any monitoring data in which the roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered a deviation.</p> <p>Periodic Monitoring Text: Visually inspect and record the inspection of the internal floating roof to ensure: the roof is floating on the surface of the VOC and, liquid has not accumulated on the internal floating roof, the seals are not detached, and there are no holes or tears in the seal fabric. Any monitoring data in which the roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation.</p>	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: APISEP	
Control Device ID No.: 124	Control Device Type: Vapor combustor
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Water Separation	SOP Index No.: R5131
Pollutant: VOC	Main Standard: § 115.132(b)(3)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: N/A	
Deviation Limit: Minimum combustor temperature of 1645 F.	
<p>Periodic Monitoring Text: Measure and record the combustion temperature in the combustion chamber or immediately downstream of the combustion chamber. The monitoring instrumentation shall be maintained, calibrated and operated in accordance with manufacturer's specifications or other written procedures. Any monitoring data below the minimum limit shall be considered and reported as a deviation.</p>	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: GRP-EPN118	
Control Device ID No.: 13T01	Control Device Type: Other control device type
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121
Pollutant: VOC	Main Standard: § 115.122(b)
Monitoring Information	
Indicator: Exhaust Gas Temperature	
Minimum Frequency: once per week	
Averaging Period: N/A	
Deviation Limit: Maximum exhaust gas temperature = 121° F	
<p>Periodic Monitoring Text: Measure and record the outlet exhaust gas temperature from the condenser system. The monitoring instrumentation shall be maintained, calibrated and operated in accordance with manufacturer's specifications or other written procedures. Any monitoring data above the maximum limit shall be considered and reported as a deviation.</p>	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: GRP-EPN118	
Control Device ID No.: 13-H-01A	Control Device Type: Steam generating unit (boiler)/process heater (design heat input is greater than or equal to 44 megawatts)
Control Device ID No.: 13-H-01B	Control Device Type: Steam generating unit (boiler)/process heater (design heat input is greater than or equal to 44 megawatts)
Control Device ID No.: 13-H-01C	Control Device Type: Steam generating unit (boiler)/process heater (design heat input is greater than or equal to 44 megawatts)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121a
Pollutant: VOC	Main Standard: § 115.122(b)
Monitoring Information	
Indicator: Period of Operation	
Minimum Frequency: N/A	
Averaging Period: N/A	
Deviation Limit: All periods of operation that are not recorded are to be considered and reported as a deviation when vent is routed to hydrogen reformer heater, 13-H-01A, 13-H-01B, 13-H-01C for vapor control.	
Periodic Monitoring Text: Monitor and record the periods of operation of the steam generating units or process heater. All periods that are not recorded shall be considered and reported as a deviation. The records must be readily available for inspection.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: GRP-EPN121	
Control Device ID No.: 24-ST-02	Control Device Type: Wet scrubber
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111
Pollutant: Opacity	Main Standard: § 111.111(a)(1)(B)
Monitoring Information	
Indicator: Pressure Drop	
Minimum Frequency: once per week	
Averaging Period: N/A	
Deviation Limit: The minimum flue gas pressure drop across the filtering modules and cyclolabs is 80% of the average value recorded from the most recent performance test. Any monitoring data below the minimum limit shall be considered a deviation.	
Periodic Monitoring Text: Measure and record the pressure drop. The monitoring instrumentation shall be calibrated, maintained and operated in accordance with manufacturer's specifications or other written procedures. Any monitoring data below the minimum limit shall be considered and reported as a deviation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: GRP-EPN121	
Control Device ID No.: 24-ST-02	Control Device Type: Wet scrubber
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111
Pollutant: Opacity	Main Standard: § 111.111(a)(1)(B)
Monitoring Information	
Indicator: Liquid Supply Pressure	
Minimum Frequency: once per week	
Averaging Period: N/A	
Deviation Limit: The minimum water pressure to filtering modules is 80% of the average value recorded from the most recent performance test. Any monitoring data below the minimum limit shall be considered a deviation.	
Periodic Monitoring Text: Measure and record the liquid supply pressure. The monitoring instrumentation shall be calibrated, maintained and operated in accordance with manufacturer's specifications or other written procedures. Any monitoring data below the minimum limit shall be considered and reported as a deviation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: GRP-EPN126A	
Control Device ID No.: MFL-1	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121
Pollutant: VOC	Main Standard: § 115.122(b)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Once per hour	
Averaging Period: N/A	
Deviation Limit: Any monitoring which indicates the lack of a pilot flame shall be considered and reported as a deviation when vent is routed to the flare, MFL-1, for vapor control.	
<p>Periodic Monitoring Text: Measure and record the presence of the pilot flame or maintain records of alarm events and duration of alarm events. The presence of a flare pilot flame shall be monitored using a thermocouple or any other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. The monitoring instrumentation shall be maintained, calibrated and operated in accordance with manufacturer's specifications or other written procedures. Any monitoring data which indicates the lack of a pilot flame shall be considered and reported as a deviation.</p>	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: GRP-EPN126B	
Control Device ID No.: MFL-1	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121
Pollutant: VOC	Main Standard: § 115.122(b)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Once per hour	
Averaging Period: N/A	
Deviation Limit: Any monitoring which indicates the lack of a pilot flame shall be considered and reported as a deviation when vent is routed to the flare, MFL-1, for vapor control.	
<p>Periodic Monitoring Text: Measure and record the presence of the pilot flame or maintain records of alarm events and duration of alarm events. The presence of a flare pilot flame shall be monitored using a thermocouple or any other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. The monitoring instrumentation shall be maintained, calibrated and operated in accordance with manufacturer's specifications or other written procedures. Any monitoring data which indicates the lack of a pilot flame shall be considered and reported as a deviation.</p>	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: GRP-EPN126B	
Control Device ID No.: GRP-49HTR	Control Device Type: Steam generating unit (boiler)/process heater (design heat input is greater than or equal to 44 megawatts)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121a
Pollutant: VOC	Main Standard: § 115.122(b)
Monitoring Information	
Indicator: Period of Operation	
Minimum Frequency: N/A	
Averaging Period: N/A	
Deviation Limit: All periods of operation that are not recorded are to be considered and reported as a deviation when vent is routed to the reformer heater, GRP-49HTR, for vapor control.	
Periodic Monitoring Text: Monitor and record the periods of operation of the steam generating units or process heater. All periods that are not recorded shall be considered and reported as a deviation. The records must be readily available for inspection.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: GRP-EPN135	
Control Device ID No.: MFL-1	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121
Pollutant: VOC	Main Standard: § 115.122(b)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Once per hour	
Averaging Period: N/A	
Deviation Limit: Any monitoring which indicates the lack of a pilot flame shall be considered and reported as a deviation when vent is routed to the flare, MFL-1, for vapor control.	
<p>Periodic Monitoring Text: Measure and record the presence of the pilot flame or maintain records of alarm events and duration of alarm events. The presence of a flare pilot flame shall be monitored using a thermocouple or any other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. The monitoring instrumentation shall be maintained, calibrated and operated in accordance with manufacturer's specifications or other written procedures. Any monitoring data which indicates the lack of a pilot flame shall be considered and reported as a deviation.</p>	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: GRP-IRMTBQ	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-b
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: N/A	
Deviation Limit: Any monitoring data in which the roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered a deviation.	
Periodic Monitoring Text: Visually inspect and record the inspection of the internal floating roof to ensure: the roof is floating on the surface of the VOC and, liquid has not accumulated on the internal floating roof, the seals are not detached, and there are no holes or tears in the seal fabric. Any monitoring data in which the roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: GRP-IRMTBQ	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-c
Pollutant: VOC	Main Standard: § 115.112(b)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: N/A	
Deviation Limit: Any monitoring data in which the roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered a deviation.	
Periodic Monitoring Text: Visually inspect and record the inspection of the internal floating roof to ensure: the roof is floating on the surface of the VOC and, liquid has not accumulated on the internal floating roof, the seals are not detached, and there are no holes or tears in the seal fabric. Any monitoring data in which the roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: GRP-VACJET	
Control Device ID No.: 02-H-01	Control Device Type: Other control device type
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Unit Turn & Vac System-Pet Ref	SOP Index No.: R5311a
Pollutant: VOC	Main Standard: § 115.311(b)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: N/A	
Deviation Limit: Minimum Temperature = 1200 F	
Periodic Monitoring Text: Measure and record the combustion temperature in the combustion chamber or immediately downstream of the combustion chamber into which the volatile organic compound is introduced. Any monitoring data below the minimum limit shall be considered and reported as a deviation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: GRP-VACJET	
Control Device ID No.: MFL-1	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Unit Turn & Vac System-Pet Ref	SOP Index No.: R5311b
Pollutant: VOC	Main Standard: § 115.311(b)(1)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Once per hour	
Averaging Period: N/A	
Deviation Limit: Lack of a pilot flame shall be considered and reported as a deviation.	
<p>Periodic Monitoring Text: Measure and record the presence of the pilot flame or maintain records of alarm events and duration of alarm events. The presence of a flare pilot flame shall be monitored using a thermocouple or any other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. The monitoring instrumentation shall be maintained, calibrated and operated in accordance with manufacturer's specifications or other written procedures. Any monitoring data which indicates the lack of a pilot flame shall be considered and reported as a deviation.</p>	

Permit Shield

Permit Shield 290

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit / Group / Process ID No.	Group / Inclusive Units	Regulation	Basis of Determination
13-H-01A	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a solid fossil fuel-fired or liquid fuel-fired heater.
13-H-01B	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a solid fossil fuel-fired or liquid fuel-fired heater.
13-H-01C	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a solid fossil fuel-fired or liquid fuel-fired boiler.
13-H-01C	N/A	40 CFR Part 60, Subpart D	Boiler does not have a heat input of greater than 250 MMBtu/hr.
13-H-01C	N/A	40 CFR Part 60, Subpart Da	Boiler does not have a heat input of greater than 250 MMBtu/hr and is not an electric utility steam generating units.
13-H-01C	N/A	40 CFR Part 60, Subpart Db	Boiler construction began before June 19, 1984.
13-H-01C	N/A	40 CFR Part 60, Subpart Dc	Boiler construction began before June 9, 1989.
16-P-4-EN	N/A	40 CFR Part 60, Subpart IIII	Emergency CI ICE was manufactured prior to 04/01/2006 and is not a fire pump, and not modified or reconstructed after 07/11/2005.
16-P-7-EN	N/A	40 CFR Part 60, Subpart IIII	Emergency CI ICE was manufactured prior to 04/01/2006 and is not a fire pump, and not modified or reconstructed after 07/11/2005.
16-V-11	N/A	30 TAC Chapter 115, Storage of VOCs	Tank capacity less than 1,000 gallons.
16-V-11	N/A	40 CFR Part 60, Subpart Kb	Tank capacity less than 19,800 gallons.
16-V-12	N/A	30 TAC Chapter 115, Storage of VOCs	Tank capacity less than 1,000 gallons.
16-V-12	N/A	40 CFR Part 60, Subpart Kb	Tank capacity less than 19,800 gallons.
16-V-13	N/A	30 TAC Chapter 115, Storage of VOCs	Tank capacity less than 1,000 gallons.

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit / Group / Process ID No.	Group / Inclusive Units	Regulation	Basis of Determination
16-V-13	N/A	40 CFR Part 60, Subpart Kb	Tank capacity less than 19,800 gallons.
16-V-14	N/A	30 TAC Chapter 115, Storage of VOCs	Tank capacity less than 1,000 gallons.
16-V-14	N/A	40 CFR Part 60, Subpart Kb	Tank capacity less than 19,800 gallons.
30-B-02	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a solid fossil fuel-fired or liquid fuel-fired boiler.
30-B-02	N/A	40 CFR Part 60, Subpart D	Boiler does not have a heat input of greater than 250 MMBtu/hr.
30-B-02	N/A	40 CFR Part 60, Subpart Da	Boiler does not have a heat input of greater than 250 MMBtu/hr, and boiler is not electric utility steam generating unit.
30-B-02	N/A	40 CFR Part 60, Subpart Dc	Boiler has a heat input of greater than 100 MMBtu/hr.
30-B-03	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a solid fossil fuel-fired or liquid fuel-fired boiler.
30-B-03	N/A	40 CFR Part 60, Subpart D	Boiler does not have a heat input of greater than 250 MMBtu/hr.
30-B-03	N/A	40 CFR Part 60, Subpart Da	Boiler does not have a heat input of greater than 250 MMBtu/hr, and boiler is not electric utility steam generating unit.
30-B-03	N/A	40 CFR Part 60, Subpart Dc	Boiler has a heat input of greater than 100 MMBtu/hr.
31-H-01	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a solid fossil fuel-fired or liquid fuel-fired heater.
38-H-01	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a solid fossil fuel-fired or liquid fuel-fired heater.

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit / Group / Process ID No.	Group / Inclusive Units	Regulation	Basis of Determination
38-H-02	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a solid fossil fuel-fired or liquid fuel-fired heater.
43-TK-04	N/A	40 CFR Part 63, Subpart CC	Tank does not store HAPs listed in Table 1 of 63 Subpart CC
43-TK-04	N/A	40 CFR Part 63, Subpart G	Not subject because not associated with SOCM1 unit.
46-H-01	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a solid fossil fuel-fired or liquid fuel-fired hot oil heater.
46-H-01	N/A	40 CFR Part 60, Subpart D	Hot oil heater does not have a heat input of greater than 250 MMBtu/hr.
46-H-01	N/A	40 CFR Part 60, Subpart Da	Hot oil heater does not have a heat input of greater than 250 MMBtu/hr and is not an electric utility steam generating unit.
46-H-01	N/A	40 CFR Part 60, Subpart Db	Hot oil heater has a heat input of less than 100 MMBtu/hr.
46-H-01	N/A	40 CFR Part 60, Subpart Dc	Hot oil heater construction began before June 9, 1989.
49-H-91	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a solid fossil fuel-fired or liquid fuel-fired heater.
49-V-14	N/A	30 TAC Chapter 115, Storage of VOCs	When not storing VOC, tank is not subject to regulation. When storing any VOC, a storage tank with storage capacity less than 1,000 gallons is exempt.
49-V-14	N/A	40 CFR Part 60, Subpart Kb	Storage vessel capacity is less than 19,800 gallons.
49-V-14	N/A	40 CFR Part 63, Subpart CC	Tank does not store HAPs listed in Table 1 of 63

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit / Group / Process ID No.	Group / Inclusive Units	Regulation	Basis of Determination
			Subpart CC
49-V-14	N/A	40 CFR Part 63, Subpart G	Not subject because not associated with SOCM unit.
52-H-01	N/A	30 TAC Chapter 112, Sulfur Compounds	Not a solid fossil fuel-fired or liquid fuel-fired heater.
54F-MTBE	N/A	40 CFR Part 60, Subpart VV	Does not produce listed chemical
54F-MTBE	N/A	40 CFR Part 63, Subpart H	Not subject to HON - unit does not produce a listed chemical.
70-TK-138	N/A	40 CFR Part 63, Subpart G	Not subject because not associated with SOCM unit.
70-TK-140	N/A	40 CFR Part 60, Subpart Kb	Storage vessel has a capacity greater than or equal to 75 cubic meters but less than 151 cubic meters with a maximum true vapor pressure less than 2.2 psia.
83-TK-155	N/A	40 CFR Part 63, Subpart CC	Does not process MACT CC Group 1 wastewater streams.
83-TK-155	N/A	40 CFR Part 63, Subpart DD	The facility doesn't process wastes, materials are considered off-spec products to be recycled. The facility does process both in-plant generated and employee household "do-it-yourself" used motor oil that doesn't meet the definition of used oil.
83-TK-155	N/A	40 CFR Part 63, Subpart G	Not subject because not associated with SOCM unit.
83-TK-23	N/A	40 CFR Part 63, Subpart CC	Does not process MACT CC Group 1 wastewater streams.

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit / Group / Process ID No.	Group / Inclusive Units	Regulation	Basis of Determination
83-TK-23	N/A	40 CFR Part 63, Subpart DD	The facility doesn't process wastes, materials are considered off-spec products to be recycled. The facility does process both in-plant generated and employee household "do-it-yourself" used motor oil that doesn't meet the definition of used oil.
83-TK-23	N/A	40 CFR Part 63, Subpart G	Not subject because not associated with SOCM I unit.
83-TK-25	N/A	40 CFR Part 63, Subpart CC	Tank does not store HAPs listed in Table 1 of 63 Subpart CC
83-TK-25	N/A	40 CFR Part 63, Subpart G	Not subject because not associated with SOCM I unit.
83-TK-26	N/A	40 CFR Part 60, Subpart QQQ	A Group 1 wastewater stream managed in a unit subject to both MACT CC and NSPS QQQ is required to comply only with MACT CC.
83-TK-26	N/A	40 CFR Part 63, Subpart G	Not subject because not associated with SOCM I unit.
83-TK-28	N/A	40 CFR Part 63, Subpart CC	Tank does not store HAPs listed in Table 1 of 63 Subpart CC.
83-TK-28	N/A	40 CFR Part 63, Subpart G	Not subject because not associated with SOCM I unit.
83-V-97	N/A	40 CFR Part 63, Subpart CC	Does not process MACT CC Group 1 wastewater streams.
83-V-97	N/A	40 CFR Part 63, Subpart G	Not subject because not associated with SOCM I unit.
APISEP	N/A	40 CFR Part 63, Subpart CC	Does not process MACT CC Group 1

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit / Group / Process ID No.	Group / Inclusive Units	Regulation	Basis of Determination
			wastewater streams.
APISEP	N/A	40 CFR Part 63, Subpart DD	Facility does not process off-site waste. Used oil at crude refineries is exempt under 279.10(g)(3).
APISEP	N/A	40 CFR Part 63, Subpart VV	Facility is not subject to 40 CFR Part 60, 61, 63 subparts which reference this subpart
BARGEDOCKS	N/A	30 TAC Chapter 115, Loading and Unloading of VOC	Marine loading not subject to requirements.
BARGEDOCKS	N/A	40 CFR Part 60, Subpart XX	Does not load tank trucks.
BARGEDOCKS	N/A	40 CFR Part 63, Subpart G	Not a transfer rack by MACT F definition.
BARGEDOCKS	N/A	40 CFR Part 63, Subpart R	Does not load tank trucks
BUTAMER	N/A	30 TAC Chapter 115, Fugitives Pet Ref B Counties	Fugitive unit is not engaged in any of the functions listed in the petroleum refinery definition in 115.10 (34).
FUELDRM	N/A	40 CFR Part 60, Subpart GGG	Not a process unit.
FUELDRM	N/A	40 CFR Part 60, Subpart VV	Does not produce listed chemical.
GRP-49HTR	49-H-01, 49-H-02, 49-H-03, 49-H-04	30 TAC Chapter 112, Sulfur Compounds	Not solid fossil fuel-fired or liquid fuel-fired heaters.
GRP-5GCCVV	11F-HOC, 49-RSU, 49-XFU, 4F, CRU-FUG, CRUDE UNIT, HCU-FUG, HOC-FUG, HRLEU-FUG, LRU, NHT-FUG	40 CFR Part 61, Subpart J	Equipment leaks that are also subject to 40 CFR Part 60 or 61 standards promulgated before 9/4/2007, are required to comply only with the provisions specified in 40 CFR Part 63, Subpart CC.
GRP-CT	ALKY-CT, BUP-CT, CRUDE-CT, HOC-CT	40 CFR Part 63, Subpart Q	Cooling towers do not use chromium-based water treatment chemicals.

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit / Group / Process ID No.	Group / Inclusive Units	Regulation	Basis of Determination
GRP-EPN118	13T01, SMR-CO2-VT	40 CFR Part 63, Subpart CC	By definition, CO2 vents from hydrogen production plants are not subject to vent rules.
GRP-EPN118	13T01, SMR-CO2-VT	40 CFR Part 63, Subpart G	Not subject to HON - unit does not produce a listed chemical.
GRP-EPN121	2202-L, 2203-L, 24-ST-02, SCOT, SULFTEN	30 TAC Chapter 115, Vent Gas Controls	Vent downstream of combustion device.
GRP-EPN121	2202-L, 2203-L, 24-ST-02, SCOT, SULFTEN	40 CFR Part 63, Subpart CC	Vents from Cracking Units and Sulfur Recovery Units are except from MACT CC
GRP-EPN121	2202-L, 2203-L, 24-ST-02, SCOT, SULFTEN	40 CFR Part 63, Subpart G	Process vent is not part of a SOCMI process
GRP-EPN135	01V01, 01V13, 01V16, 24V36	40 CFR Part 63, Subpart G	Does not meet the definition of subject process vents.
GRP-EPN155	49-SCRUB	30 TAC Chapter 115, Vent Gas Controls	Vent downstream of combustion device.
GRP-EPN155	49-SCRUB	40 CFR Part 63, Subpart CC	Vents from catalytic reformer catalyst regeneration are except from MACT CC.
GRP-EPN155	49-SCRUB	40 CFR Part 63, Subpart G	Does not meet the definition of subject process vents.
GRP-EPN168	38-SCRUB	30 TAC Chapter 115, Vent Gas Controls	Vent downstream of combustion device.
GRP-EPN168	38-SCRUB	40 CFR Part 63, Subpart CC	Not part of a petroleum refining process unit.
GRP-EPN168	38-SCRUB	40 CFR Part 63, Subpart G	Does not meet the definition of subject process vents.
GRP-ERLQA	83-V-58, 83-V-59	40 CFR Part 60, Subpart QQQ	A Group 1 wastewater stream managed in a unit subject to both MACT CC and NSPS QQQ is required to comply only with MACT CC.
GRP-ERLQA	83-V-58, 83-V-59	40 CFR Part 63, Subpart G	Not subject because not associated with SOCMI

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit / Group / Process ID No.	Group / Inclusive Units	Regulation	Basis of Determination
			unit.
GRP-FIXAS	43-TK-08, 43-V-10	40 CFR Part 60, Subpart Ka	Tank capacity less than 40,000 gallons.
GRP-FIXAS	43-TK-08, 43-V-10	40 CFR Part 63, Subpart CC	Tank does not store HAPs listed in Table 1 of 63 Subpart CC
GRP-FIXAS	43-TK-08, 43-V-10	40 CFR Part 63, Subpart G	Not subject because not associated with SOCMI unit.
GRP-HTR	01-H-01, 01-H-02, 01-H-03, 02-H-01, 11-H-01, 12-H-01A, 12-H-01B, 12-H-02, 36-H-01, 38-H-03, 49-H-71, 49-H-90	30 TAC Chapter 112, Sulfur Compounds	Not solid fossil fuel-fired or liquid fuel-fired heaters.
GRP-HTRJ	47-H-01, 47-H-02, 47-H-03, 47-H-04, 48-H-01	30 TAC Chapter 112, Sulfur Compounds	Not solid fossil fuel-fired or liquid fuel-fired heaters.
GRP-IRMTBQ	83-TK-159, 83-TK-160	40 CFR Part 60, Subpart QQQ	A Group 1 wastewater stream managed in a unit subject to both MACT CC and NSPS QQQ is required to comply only with MACT CC.
GRP-IRMTBQ	83-TK-159, 83-TK-160	40 CFR Part 63, Subpart G	Not subject because not associated with SOCMI unit.
GRP-R5-1	41F, AMINE-FUG, SMR-FUG, SWS-FUG	40 CFR Part 60, Subpart GGG	Construction before applicability date
GRP-R5-1	41F, AMINE-FUG, SMR-FUG, SWS-FUG	40 CFR Part 60, Subpart VV	Does not produce listed chemical
GRP-R5-1	41F, AMINE-FUG, SMR-FUG, SWS-FUG	40 CFR Part 63, Subpart CC	No HAPS
GRP-R5-2	30B01F, 30B02F, 30B03F, 30B04F	40 CFR Part 60, Subpart GGG	Not a process unit
GRP-R5-2	30B01F, 30B02F, 30B03F, 30B04F	40 CFR Part 60, Subpart VV	Does not produce listed chemical

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit / Group / Process ID No.	Group / Inclusive Units	Regulation	Basis of Determination
GRP-R5-2	30B01F, 30B02F, 30B03F, 30B04F	40 CFR Part 63, Subpart CC	No HAPS
GRP-R5CC	11F-HDS, ALKY-FUG, HDS FUG	40 CFR Part 60, Subpart GGG	Construction before applicability date
GRP-R5CC	11F-HDS, ALKY-FUG, HDS FUG	40 CFR Part 60, Subpart VV	Does not produce listed chemical
GRP-R5CC2	DOCKS-F, GAS BLEND, PIPING FUG, TERMIN 2/2A, TERMINAL 1, TERMINAL 3	40 CFR Part 60, Subpart GGG	Not a process unit
GRP-R5CC2	DOCKS-F, GAS BLEND, PIPING FUG, TERMIN 2/2A, TERMINAL 1, TERMINAL 3	40 CFR Part 60, Subpart VV	Does not produce listed chemical.
GRP-R5G	46F/24F, 47PSA, VACUUMUNIT	40 CFR Part 60, Subpart VV	Does not produce listed chemical
GRP-R5G	46F/24F, 47PSA, VACUUMUNIT	40 CFR Part 63, Subpart CC	No HAPS
GRP-SULJET	43J01, 43J02	30 TAC Chapter 115, Unit Turn & Vac System-Pet Ref	No VOCs in the vent stream.
LPG STORAG	N/A	40 CFR Part 60, Subpart GGG	Not a process unit
LPG STORAG	N/A	40 CFR Part 60, Subpart VV	Does not produce listed chemical
LPG STORAG	N/A	40 CFR Part 63, Subpart CC	No HAPS
MTBE-FUG	N/A	40 CFR Part 60, Subpart VV	Does not produce listed chemical
MTBE-FUG	N/A	40 CFR Part 63, Subpart H	Not subject to HON - unit does not produce a listed chemical.
MVRUF	N/A	40 CFR Part 60, Subpart GGG	Not a process unit.
MVRUF	N/A	40 CFR Part 60, Subpart VV	Does not produce listed chemical.
OLEFLEX-FU	N/A	30 TAC Chapter 115, Fugitives Pet Ref B Counties	Fugitive unit is not engaged in any of the functions listed in the petroleum refinery definition in 115.10 (34).

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit / Group / Process ID No.	Group / Inclusive Units	Regulation	Basis of Determination
OLEFLEX-FU	N/A	40 CFR Part 60, Subpart GGG	Facilities subject to Subpart VV are excluded from Subpart GGG.
OLEFLEX-FU	N/A	40 CFR Part 63, Subpart CC	Not a petroleum refining process unit.
SHIPDOCKS	N/A	30 TAC Chapter 115, Loading and Unloading of VOC	Marine loading not subject to requirements.
SHIPDOCKS	N/A	40 CFR Part 60, Subpart XX	Does not load tank trucks.
SHIPDOCKS	N/A	40 CFR Part 63, Subpart G	Not a transfer rack by MACT F definition.
SHIPDOCKS	N/A	40 CFR Part 63, Subpart R	Does not load tank trucks
SRU	N/A	40 CFR Part 60, Subpart LLL	Not onshore natural gas processing plant.
SRU3	N/A	40 CFR Part 60, Subpart LLL	Not onshore natural gas processing plant.
T-RACK	N/A	40 CFR Part 60, Subpart XX	Group 1 gasoline loading rack subject to MACT CC and NSPS XX is required to comply only with MACT CC.
T-RACK	N/A	40 CFR Part 61, Subpart BB	Truck rack does not load benzene.
T-RACK	N/A	40 CFR Part 63, Subpart G	Not a transfer rack by MACT F definition.
T-RACK	N/A	40 CFR Part 63, Subpart R	Subject to MACT CC - overrides MACT R
T-RACK	N/A	40 CFR Part 63, Subpart Y	Not marine loading
VRU	N/A	30 TAC Chapter 115, Loading and Unloading of VOC	Marine loading not subject to requirements.
VRU	N/A	40 CFR Part 60, Subpart XX	Does not load tank trucks.
VRU	N/A	40 CFR Part 63, Subpart G	Not a transfer rack by MACT F definition
VRU	N/A	40 CFR Part 63, Subpart R	Does not load tank trucks

New Source Review Authorization References

New Source Review Authorization References	301
New Source Review Authorization References by Emission Unit	302

New Source Review Authorization References

The New Source Review authorizations listed in the table below are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Prevention of Significant Deterioration (PSD) Permits	
PSD Permit No.: GHGPSDTX211	Issuance Date: 05/03/2024
PSD Permit No.: PSDTX324M15	Issuance Date: 05/03/2024
Title 30 TAC Chapter 116 Permits, Special Permits, and Other Authorizations (Other Than Permits By Rule, PSD Permits, or NA Permits) for the Application Area.	
Authorization No.: 20740	Issuance Date: 08/10/2016
Authorization No.: 20992	Issuance Date: 08/10/2016
Authorization No.: 38754	Issuance Date: 05/03/2024
Authorization No.: 106965	Issuance Date: 08/14/2017
Authorization No.: 109543	Issuance Date: 04/22/2016
Authorization No.: 135590	Issuance Date: 09/28/2015
Permits By Rule (30 TAC Chapter 106) for the Application Area	
Number: 69	Version No./Date: 05/05/1976
Number: 71	Version No./Date: 05/05/1976
Number: 86	Version No./Date: 09/12/1989
Number: 86	Version No./Date: 09/13/1993
Number: 102	Version No./Date: 05/12/1981
Number: 106.261	Version No./Date: 09/04/2000
Number: 106.261	Version No./Date: 11/01/2003
Number: 106.262	Version No./Date: 11/01/2003
Number: 106.371	Version No./Date: 09/04/2000
Number: 106.472	Version No./Date: 09/04/2000
Number: 106.478	Version No./Date: 03/14/1997
Number: 106.478	Version No./Date: 09/04/2000
Number: 106.511	Version No./Date: 09/04/2000
Number: 106.532	Version No./Date: 03/14/1997
Number: 118	Version No./Date: 09/12/1989
Number: 125	Version No./Date: 09/23/1982

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
01-H-01	CRUDE HEATER	38754, PSDTX324M15
01-H-02	CRD PREFLASH HTR	38754, PSDTX324M15
01-H-03	CRD STAB HEATER	38754, PSDTX324M15
01V01	CRUDE TOWER OVERHEAD ACCUMULATOR	38754, PSDTX324M15
01V13	PREFLASH OVERHEAD ACCUMULATOR	38754, PSDTX324M15
01V16	STABILIZER OVERHEAD ACCUMULATOR	38754, PSDTX324M15
02-H-01	VACUUM HEATER	38754, PSDTX324M15
02-V-12	VACUUM UNIT COOLANT OIL HOLDUP TANK	106.261/11/01/2003
02J01	VACUUM TOWER JET	38754, PSDTX324M15
02J02	VACUUM TOWER JET	38754, PSDTX324M15
02J03	VACUUM TOWER JET	38754, PSDTX324M15
02J04	VACUUM TOWER JET	38754, PSDTX324M15
02J05	VACUUM TOWER JET	38754, PSDTX324M15
02J06	VACUUM TOWER JET	38754, PSDTX324M15
05-CT-109	CRUDE UNIT COOLING TOWER	106965
11-H-01	DESALTER HEATER	38754, PSDTX324M15
11F-HDS	HDS DESALTER UNIT	38754, PSDTX324M15, 106.261/11/01/2003
11F-HOC	HOC DESALTER UNIT	38754, PSDTX324M15
12-H-01A	HDS HTR. A	38754, PSDTX324M15
12-H-01B	HDS HTR. B	38754, PSDTX324M15
12-H-02	HDS PREHEATER	38754, PSDTX324M15

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
13-H-01A	H2 REFORMER HTR	38754, PSDTX324M15
13-H-01B	H2 REFORMER HTR	38754, PSDTX324M15
13-H-01C	H2 REFORMER AUX BOILER	38754, PSDTX324M15
13T01	CONDENSATE STRIPPER	38754, PSDTX324M15
16-P-11-EN	DIESEL ENGINE DRIVER FOR PUMP	38754, PSDTX324M15
16-P-12-EN	DIESEL ENGINE DRIVER FOR PUMP	38754, PSDTX324M15
16-P-13-EN	DIESEL ENGINE DRIVER FOR PUMP	38754, PSDTX324M15
16-P-14-EN	DIESEL ENGINE DRIVER FOR PUMP	38754, PSDTX324M15
16-P-4-EN	DIESEL ENGINE DRIVER FOR PUMP	38754, PSDTX324M15
16-P-7-EN	DIESEL ENGINE DRIVER FOR PUMP	38754, PSDTX324M15
16-V-11	DIESEL STORAGE TANK	38754, PSDTX324M15
16-V-12	DIESEL STORAGE TANK	38754, PSDTX324M15
16-V-13	DIESEL STORAGE TANK	38754, PSDTX324M15
16-V-14	DIESEL STORAGE TANK	38754, PSDTX324M15
17-FUG	CRUDE UNIT FUGITIVES	106965
17-H-1	CRUDE UNIT CHARGE HEATER	106965
20-V-03	LRU STABILIZER O/H VENT	38754, PSDTX324M15
2202-L	LPG OXIDIZER VENT	38754, PSDTX324M15
2203-L	LPG OXIDIZER VENT	38754, PSDTX324M15
24-ST-01	FCCU	38754, PSDTX324M15, GHGPSDTX211
24-ST-02	CAUSTIC SCRUBBER	38754, PSDTX324M15, GHGPSDTX211

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
24V36	WATER DEGASSING DRUM	38754, PSDTX324M15
25-T-03	GAS PLANT ABSORBER TOWER VENT 25-T-03	38754, PSDTX324M15
30-B-02	30-B-02 BOILER	38754, PSDTX324M15
30-B-03	30-B-03 BOILER	20740
30-B-04	30-B-04 BOILER	38754, PSDTX324M15
30-B-05	30-B-05 BOILER	38754, PSDTX324M15, GHGPSDTX211
30B01F	30-B-01 FUGITIVES	38754, PSDTX324M15
30B02F	30-B-02 FUGITIVES	38754, PSDTX324M15
30B03F	30-B-03 FUGITIVES	20740, 38754, PSDTX324M15
30B04F	BOILER 30-B-04 FUGITIVES	38754, PSDTX324M15
31-H-01	ALKY REBOILER	38754, PSDTX324M15
31V05	DEPROPANIZER OVHD	38754, PSDTX324M15
36-H-01	BUTAMER HEATER	38754, PSDTX324M15
36-T-02	BUTAMER STABILIZER VENT 36-T-02	38754, PSDTX324M15
36-V-06	BUTAMER DEISOBUT OVERHEAD ACCUMULATOR 36-V-06	38754, PSDTX324M15
36J01	BUTAMER TURNAROUND VACUUM JET	118/09/12/1989
37-V-03	MTBE BUTENE COLUMN OVERHEAD DRUM 37-V-03	38754, PSDTX324M15
37-V-05	MTBE DEPROPANIZER OVERHEAD DRUM 37-V-05	38754, PSDTX324M15
38-H-01	OLEFLEX CHARGE HEATER	38754, PSDTX324M15
38-H-02	OLEFLEX INTERHEATER	38754, PSDTX324M15
38-H-03	OLEFLEX INTERHEATER	38754, PSDTX324M15

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
38-SCRUB	OLEFLEX SCRUBBER	38754, PSDTX324M15
38-V-23	OLEFLEX PSA FEED COMPRESSOR 38-V-23	38754, PSDTX324M15
38-V-32	OLEFLEX PSA TAIL GAS COMP. SEC. OIL SEP. 38-V-32	38754, PSDTX324M15
38-V-54	OLEFLEX LOCK HOPPER #1	106.261/11/01/2003
38-V-55	OLEFLEX LOCK HOPPER #2	106.261/11/01/2003
38J01	OLEFLEX TURNAROUND VACUUM JET	118/09/12/1989
41-H-07	SRU INCINERATOR	38754, PSDTX324M15
41F	SRU FUGITIVES	38754, PSDTX324M15
43-TK-04	MDEA TANK	102/05/12/1981
43-TK-08	AMINE STORAGE TANK 43TK08	102/05/12/1981
43-V-10	AMINE SLOP TANK 43V10	86/09/12/1989
43J01	SULFUR LOADING VACUUM JET	118/09/12/1989
43J02	SULFUR PIT VACUUM JET	118/09/12/1989
44-V-01	MAIN FUEL GAS DRUM	38754, PSDTX324M15
46-H-01	SULFTEN HEATER	38754, PSDTX324M15
46F/24F	SULFTEN/SEU FUGITIVES	38754, PSDTX324M15
47-H-01	HCU RX-01 47-H-01	38754, PSDTX324M15
47-H-02	HCU RX-02 47-H-02	38754, PSDTX324M15
47-H-03	DEBUTAN. REBOILER 47-H-03	38754, PSDTX324M15
47-H-04	FRACTIONATOR REBOILER 47-H-04	38754, PSDTX324M15
47-V-02	HCU FEED SURGE DRUM	106.261/11/01/2003

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
47J01	HCU TURNAROUND VACUUM JET	118/09/12/1989
47L01PSA	PSA OFF-GAS	38754, PSDTX324M15
47PSA	PSA	38754, PSDTX324M15
48-H-01	NHT HEATER	38754, PSDTX324M15
48-V-01	NHT FEED SURGE DRUM	106.261/11/01/2003
49-H-01	CRU CHARGE HEATER 49-H-01A	38754, PSDTX324M15
49-H-02	CRU CHARGE HEATER 49-H-01B	38754, PSDTX324M15
49-H-03	CRU NO.2 INTERHEATER 49-H-03	38754, PSDTX324M15
49-H-04	CRU NO.3 INTERHEATER 49-H-04	38754, PSDTX324M15
49-H-71	RSU HEATER	38754, PSDTX324M15
49-H-90	C7 SPLITTER REB.	38754, PSDTX324M15
49-H-91	C8 SPLITTER REB.	20992
49-RSU	49-RSU	38754, PSDTX324M15, 106.261/11/01/2003
49-SCRUB	CRU SCRUBBER	38754, PSDTX324M15
49-V-01	NET GAS SEPARATOR DRUM	38754, PSDTX324M15
49-V-14	PERCHLOROETHYLENE DRUM 49V14	38754, PSDTX324M15
49-XFU	49-XFU	38754, PSDTX324M15, 106.261/11/01/2003
49CRU	UNIT 49 CRU	38754, PSDTX324M15, 106.261/11/01/2003
49J01	CRU TURNAROUND VACUUM JET	118/09/12/1989
49V06	FUEL GAS DRUM NO. 1	38754, PSDTX324M15, 106.261/11/01/2003
49V07	FUEL GAS DRUM NO. 2	38754, PSDTX324M15, 106.261/11/01/2003

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
4F	LEU	38754, PSDTX324M15, 106.261/11/01/2003
52-H-01	GD CHARGE HEATER	38754, PSDTX324M15
54-V-42	HOC MTBE DME STRIPPER OVERHEAD DRUM 54-V-42	38754, PSDTX324M15
54F-MTBE	MTBE/TAME FUGITIVES	38754, PSDTX324M15
54F-TAME	TAMU UNIT	38754, PSDTX324M15
70-TK-137	TANK NO. 137	38754, PSDTX324M15
70-TK-138	TANK NO. 138	71/05/05/1976
70-TK-140	TANK NO. 140	106.532/03/14/1997
73-TK-168	TANK 168	106965
73-TK-9	TANK NO. 9	38754, PSDTX324M15
83-TK-155	TANK NO. 155	106.532/03/14/1997
83-TK-159	TANK NO. 159	38754, PSDTX324M15
83-TK-160	TANK NO. 160	38754, PSDTX324M15
83-TK-162	TANK NO. 162	106.532/03/14/1997
83-TK-23	TANK NO. 23	38754, PSDTX324M15
83-TK-25	TANK NO. 25	106.532/03/14/1997
83-TK-26	TANK NO. 26	38754, PSDTX324M15
83-TK-28	CATALYST STORAGE TANK 83TK28	38754, PSDTX324M15
83-V-58	83-V-58-OIL ONLY	38754, PSDTX324M15
83-V-59	83-V-59	38754, PSDTX324M15
83-V-97	83-V-97	38754, PSDTX324M15

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
83-V-98	83-V-98	106.478/03/14/1997
83P136A-EN	DIESEL ENGINE DRIVER FOR PUMP	38754, PSDTX324M15
83P136B-EN	DIESEL ENGINE DRIVER FOR PUMP	38754, PSDTX324M15
ALKY-CT	ALKY COOLING TOWER	38754, PSDTX324M15
ALKY-FUG	ALKY UNIT	38754, PSDTX324M15
AMINE-FUG	AMINE UNIT	38754, PSDTX324M15
APISEP	API SEPARATOR	38754, PSDTX324M15
ATU3FUG	AMINE TREATER NO. 3 FUGITIVES	38754, PSDTX324M15
BARGEDOCKS	BARGEDOCKS	38754, PSDTX324M15
BUP-CT	BUP COOLING TOWER	38754, PSDTX324M15
BUTAMER	BUTAMER UNIT	38754, PSDTX324M15, 106.261/11/01/2003
BWS	BWS FUGITIVES	106965
CD-LOADING	THERMAL OXIDIZER AREA	109543
CD-PIPING	PIPING FUGITIVES	109543
CRU-FUG	CRU	38754, PSDTX324M15
CRUDE UNIT	CU FUGITIVES	38754, PSDTX324M15, 106.261/11/01/2003
CRUDE-CT	CRUDE COOLING TOWER	38754, PSDTX324M15
DEGREASE-F	DEGREASING	125/09/23/1982
DOCKS-F	DOCKS	38754, PSDTX324M15, 106.261/11/01/2003
FUELDRM	FUEL GAS DRUM	38754, PSDTX324M15
GAS BLEND	GAS BLENDING	38754, PSDTX324M15

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
GDFUG	GD FUGITIVES	38754, PSDTX324M15, 106.261/11/01/2003
GF-1	GROUND FLARE	38754, PSDTX324M15
HCU-FUG	HCU	38754, PSDTX324M15, 106.261/11/01/2003
HDS FUG	HDS UNIT	38754, PSDTX324M15, 106.261/11/01/2003
HOC-CT	HOC COOLING TOWER	38754, PSDTX324M15
HOC-FUG	HOC UNIT	38754, PSDTX324M15, 106.261/11/01/2003
HOC-PP-CT	COOLING TOWER-PROPYLENE PROJECT	38754, PSDTX324M15
HOCPP-FUG	HOC PP FUGITIVES	38754, PSDTX324M15, GHGPSDTX211
HRLEU-FUG	HRLEU UNIT	38754, PSDTX324M15, 106.261/11/01/2003
LPG STORAG	LPG STORAGE	38754, PSDTX324M15, 106.261/11/01/2003
LRU	LRU	38754, PSDTX324M15
MEROX	MEROX VENT	38754, PSDTX324M15
MFL-1	MAIN FLARE	38754, PSDTX324M15
MFL-1B	ACID GAS FLARE	38754, PSDTX324M15
MTBE FL-2	MTBE FLARE	38754, PSDTX324M15
MTBE-FUG	MTBE / ISO-OCTENE	38754, PSDTX324M15, 106.261/11/01/2003
MVRUF	VRU FUGITIVES	38754, PSDTX324M15
NHT-FUG	NHT	38754, PSDTX324M15, 106.261/11/01/2003
OLEFLEX-FU	OLEFLEX	38754, PSDTX324M15
PIPING FUG	TRUCK RACK	38754, PSDTX324M15, 106.261/11/01/2003
RAIL-FUG	RAILCAR RACK FUGITIVES	38754, PSDTX324M15

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
RAILRACK1	RAILCAR RACK	38754, PSDTX324M15
SCOT	SCOT INCINERATOR TRAIN 3	38754, PSDTX324M15
SCOTFUG	SCOT UNIT FUGITIVES	38754, PSDTX324M15
SHIPDOCKS	SHIPDOCKS	38754, PSDTX324M15
SMR-CO2-VT	CO2 STRIPPER VENT	38754, PSDTX324M15
SMR-FUG	SMR	38754, PSDTX324M15, 106.261/11/01/2003
SP-1271	HDS TURNAROUND VACUUM JET	118/09/12/1989
SRU	SULFUR RECOVERY UNIT	38754, PSDTX324M15
SRU3	SULFUR RECOVERY UNIT #3	38754, PSDTX324M15
SRU3FUG	SULFUR TRAIN NO. 3 FUGITIVES	38754, PSDTX324M15
SULFTEN	SULFTEN INCINERATOR TRAIN 1 & 2	38754, PSDTX324M15
SWS-FUG	SWS	38754, PSDTX324M15, 106.261/11/01/2003
T-RACK	TRUCK RACK	38754, PSDTX324M15
TERMIN 2/2A	TERMINAL 2/2A FUGITIVES	38754, PSDTX324M15, 106.261/11/01/2003
TERMINAL 1	TERMINAL 1 FUGITIVES	38754, PSDTX324M15, 106.261/11/01/2003
TERMINAL 3	TERMINAL 3 FUGITIVES	38754, PSDTX324M15
TRUCKCOMB	TRUCK LOADING COMBUSTOR	38754, PSDTX324M15
VACUUMUNIT	VACUUM UNIT	38754, PSDTX324M15
VRU	VAPOR RECOVERY UNIT	38754, PSDTX324M15
WWTP-FUG	WWTP FUGITIVES	38754, PSDTX324M15

Schedules

Compliance Schedule	312
----------------------------------	------------

Compliance Schedule

A. Compliance Schedule				
1. Specific Non-Compliance Situation				
Unit/Group/ Process ID. No(s).	SOP Index No.	Pollutant	Applicable Requirement	
			Citation	Text Description
83P136A-EN, 83P136B-EN		VOC, NOX, CO	60.4205(b) & 60.4202(a)(2)	COMPLY WITH THE EMISSION STANDARDS FOR NEW NONROAD CI ENGINE IN §60.4202, FOR ALL POLLUTANTS. CERTIFY TO EMISSION STANDARDS IN (A)(1)-(2). CERTIFY EMISSION STANDARDS IN 89.112 & 89.113 FOR ALL POLLUTANTS IN MODEL YEAR 2007.
2. Compliance Status Assessment Method and Records Location				
Compliance Status Assessment Method			Location of Records/Documentation	
Citation	Text Description			
60.4205(b) & 60.4202(a)(2)	Comply with the emission standards for new nonroad CI engine in §60.4202, for all pollutants. Certify to emission standards in (a)(1)-(2). Certify emission standards in 89.112 & 89.113 for all pollutants in model year 2007.		Environmental Offices	
3. Non-compliance Situation Description				
Two diesel engines used as drivers for two emergency storm water pumps were manufactured as fire water pumps and do not meet the requirements of NSPS IIII.				
4. Corrective Action Plan Description				
Resolve 40 CFR 60 Subpart IIII compliance issues with two diesel engine drivers for two emergency storm water pumps.				
5. List of Activities/Milestones to Implement the Corrective Action Plan				
1	November 2, 2010 letter requesting guidance or a waiver from the U.S. EPA for the engines was re-submitted to EPA via e-mail in 2013. The U.S. EPA has not yet responded to the request.			
2	Continue to submit deviation reports pursuant to 30 TAC Chapter 122 until compliance issues are resolved.			
6. Previously Submitted Compliance Plan(s)		Type of Action		Date Submitted
		N/A		N/A
7. Progress Report Submission Schedule		Semi-annually		


Alternative Requirement

Alternative Requirement.....	314
-------------------------------------	------------



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
REGION 6
1445 ROSS AVENUE, SUITE 1200
DALLAS, TX 75202-2733

AUG 19 1999



Mr. Kirk A. Saffell
Manager, Environmental Engineering
Valero Refining Company - Texas
P.O. Box 9370
Corpus Christi, TX 78469-9370

Re: Approval of Alternative Monitoring for NSPS Subpart J
Valero Refining Company - Texas
Corpus Christi Refinery
TNRCC Account No. NE-0112-G

Dear Mr. Saffell:

By letter dated February 5, 1999, Valero Refining Company - Texas (Valero) requested approval of alternative monitoring to a continuous opacity monitoring system (COMS), which is required by a New Source Performance Standard (NSPS) under Title 40, Code of Federal Regulations (CFR) Part 60, at its petroleum refinery in Corpus Christi, Texas. Valero's petroleum refinery contains a fluid catalytic cracking unit (FCCU) which is subject to NSPS Subpart J - *Standards of Performance for Petroleum Refineries*. A COMS on the FCCU (EPN 121) is required by § 60.105(a)(1) of NSPS Subpart J. The FCCU is equipped with a high efficiency Belco Technologies Corporation (Belco) flue gas scrubber. Moisture in the exhaust of the Belco scrubber would interfere with the operation of a COMS. Therefore, Valero requested that the following alternate monitoring program be approved as recommended to Valero by Belco.

1. Monitor the pressure of the water to the filtering modules and maintain a pressure of at least 45 psig at all times.
2. Monitor the flue gas pressure drop across the filtering modules/cyclolabs and maintain a drop of at least 5" H₂O.

In a letter dated November 12, 1993, by which Valero submitted additional information and comments on draft provisions to Permit No. 8373 and PSD-TX-324M-6 to the Texas Natural Resource Conservation Commission (TNRCC), Valero proposed alternative monitoring to the COMS required by NSPS Subpart J. The TNRCC included the following approval of the alternative monitoring as Special Provision 15 when it revised Permit No. 8373 and PSD-TX-324M-6 on December 13, 1993.

In order to control opacity from the stack of EPN 121, the permittee shall maintain the liquid to the filtering modules at a pressure greater than 45 pounds per square inch and the flue gas pressure drop across the filtering modules and the cyclolabs at no less than five inches of water. Liquid pressure and pressure drop shall be continuously recorded and maintained at the plant site for a period of two years. These records shall be made available for inspection by the Executive Director of the TNRCC or his designated representative.

Special Provision 15 of Permit No. 8373 and PSD-TX-324M-6 became Special Condition 31 of Permit No. 8373 and PSD-TX-324M7, which was issued on May 29, 1997, and remained Special Condition 31 of Permit No. 8373 and PSD-TX-324M8, which was issued on January 27, 1998. Valero has not received approval of this alternative monitoring program from EPA. The authority to approve alternative monitoring under 40 CFR 60.13(i) has been delegated to the EPA Region 6, but has not been delegated to the TNRCC.

Pursuant to 40 CFR 60.13(i), we are approving the following alternative monitoring to the COMS which is required under § 60.105(a)(1) of NSPS Subpart J for the HOC FCCU (EPN 121) at Valero's petroleum refinery in Corpus Christi, Texas.

1. Valero shall continuously monitor and record the pressure of the water to the filtering modules of the Belco scrubber and the flue gas pressure drop across the filtering modules/cyclolabs of the Belco scrubber.
2. Valero shall maintain records of the water pressure and flue gas pressure drop at the plant site for at least two years.
3. Valero shall monitor and record the pressure of the water to the filtering modules of the Belco scrubber and the flue gas pressure drop across the filtering modules/cyclolabs of the Belco scrubber during all performance tests for particulate matter of the Belco scrubber. The arithmetic averages of the three runs shall be used as the baseline average values for the purposes of defining excess emissions. The arithmetic averages of the water pressure and flue gas pressure drop which were determined during a performance test for particulate matter which was conducted prior to the date of approval of this alternative monitoring may be used as the baseline average values for the purposes of defining excess emissions.
4. Valero shall submit reports of excess emissions semiannually to the Texas Natural Resource Conservation Commission. All reports shall be postmarked by the 30th day following the end of each calendar half. Excess emissions are defined as follows.
 - a. Any 6-minute period when the average pressure of the water to the filtering modules of the Belco scrubber is less than 80 percent of the average value recorded during the most recent performance test that demonstrated compliance with the particulate matter standard in § 60.102(a)(1) of NSPS Subpart J.

- b. Any 6-minute period when the flue gas pressure drop across the filtering modules/cyclolabs of the Belco scrubber is less than 80 percent of the average value recorded during the most recent performance test that demonstrated compliance with the particulate matter standard in § 60.102(a)(1) of NSPS Subpart J.

By letter dated July 13, 1999, we notified the TNRCC of our intention to approve this alternative monitoring. The TNRCC did not have any objections to our approving this alternative monitoring, nor any proposed conditions to this alternative monitoring. In our letter to the TNRCC, we proposed that excess emissions be defined as any 6-minute period when the parameter in provision 4.a or 4.b is less than 90 percent of the average value recorded during the most recent performance test for particulate matter. We sent Valero a copy of our letter of July 13, 1999, to the TNRCC. Valero requested that the 90 percent level specified in provisions 4.a and 4.b be changed to 80 percent. Eighty percent will allow Valero sufficient operating flexibility while still ensuring compliance with the standards for opacity and particulate matter in NSPS Subpart J. A limit of 80 percent is more restrictive than the alternative monitoring requirements for NSPS Subpart LL - *Standards of Performance for Metallic Mineral Processing Plants*, NSPS Subpart OOO - *Standards of Performance for Nonmetallic Mineral Processing Plants*, and NSPS Subpart PPP - *Standards of Performance for Wool fiberglass Insulation Manufacturing Plants*. In all of these subparts, excess emissions are defined as periods when the alternative monitoring parameters for a wet gas scrubber are less than 70 percent of the value recorded during the performance test. Valero submitted information from a recent stack test that was conducted on the Belco scrubber on April 13, 1999, by letter dated May 12, 1999, and a fax on May 25, 1999. The average emission rate of particulate matter was 25 percent of the standard of 1.0 lb/1000 lb of coke burnoff in § 60.102(a)(1) of NSPS Subpart J. The testing information is summarized in the following table.


	<i>Run #1</i>	<i>Run #2</i>	<i>Run #3</i>	<i>Average</i>
Particulate Matter (lb/1000 lb coke burnoff)	0.33	0.22	0.19	0.25
Average Filter Differential Pressure (in. of H ₂ O)	9.87	9.63	9.85	9.78
Average Discharge Pressure (psig)	80.8	81.3	81.4	81.2
Minimum 6-min Average Filter Differential Pressure (in. of H ₂ O)	9.80	9.47	9.80	
Minimum 6-min Average Discharge Pressure (psig)	80.7	81.1	81.1	

Eighty percent of the arithmetic averages of the three runs of the water pressure and flue gas pressure drop are more stringent requirements than the minimum pressures for these parameters

of 45 pounds per square inch and five inches of water, respectively, established by the TNRCC in the air permit.

If you have any questions concerning this matter, please contact Mr. George V. Marusak, of my staff, at (214) 665-8366.

Sincerely yours,

A handwritten signature in black ink, appearing to read "John R. Hepola". The signature is fluid and cursive, with the first name "John" being more prominent.

John R. Hepola

Chief

Air/Toxics and Inspection

Coordination Branch

cc: Jeffrey P. Greif, TNRCC
David Bower, TNRCC
Jim Bowman, TNRCC Region 14 - Corpus Christi



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
REGION 6
1445 ROSS AVENUE, SUITE 1200
DALLAS TX 75202-2733



March 21, 2016

Sam D. Sanders
Senior Environmental Engineer
Valero Refining-Texas, LP
Corpus Christi Manufacturing Facility
P.O. Box 9370
Corpus Christi, Texas 78469-9370

Re: Conditional Approval of Alternative Monitoring Plan (AMP) – Revision of Monitoring Plan Process Parameters for NHT Feed Surge Drum (48-V-01) Vent Stream. - New Source Performance Standards (NSPS) 40 Code of Federal Regulations (C.F.R.) Part 60, Subpart J – Valero Corpus Christi Refinery West Plant, Corpus Christi, Texas (Valero West).

Dear Mr. Sanders:

This letter is in response to your request dated November 13, 2015, regarding the revision of monitoring plan process parameters for the NHT Feed Surge Drum (48-V-01) vent stream to be combusted at the NHT Charge heater (48-H-01) under NSPS Subpart J. The Environmental Protection Agency (EPA) evaluated your request based on the process data submitted with the request. EPA conditionally approves your request to revise the monitoring plan process parameters.

Valero has proposed to use concentrations of Total Sulfur in the Combined Feed and the temperature of the contents in the Feed Surge Drum (48-V-01) as a means of monitoring the vent stream that is combusted in the NHT Charge Heater, 48-11-01. Total Sulfur and the temperature of the Feed Surge Drum will be sampled and analyzed in conjunction with the vent stream from 48-V-01 Feed Surge Drum, according to the H₂S monitoring schedule. Revised process parameter limits should not exceed 452 parts per million (ppm) of Total Sulfur in the Combined Feed and a temperature in the Feed Surge Drum of 189 degrees Fahrenheit.

Internet Address (URL) • <http://www.epa.gov/region6>
Recycled/Recyclable • Printed with Vegetable Oil Based Inks on 100% Recycled Paper, Process Chlorine Free

Valero will continue to follow the steps outlined in Appendix D (Alternative Monitoring Plan for NSPS Subpart J Refinery Fuel Gas) of the Valero consent decree (Civil Action No. SA-05-CA-0569) relative to monitoring the NHT Feed Surge Drum vent stream. If refinery operations change such that the sulfur content of the vent stream changes from representations made for this determination, then Valero West must document the change(s) and follow the appropriate steps outlined in 40 C.F.R. § 60.105(b)(3)(i)-(iii).

If you have any questions or concerns about this conditional approval, please contact Prince Nfodzo of my staff at (214) 665-7491 or Nfodzo.prince@epa.gov.

Sincerely,



Steve Thompson

Branch Chief

Air Enforcement Branch

Compliance Assurance & Enforcement Division

Cc: Michael De La Cruz, Texas Commission on Environmental Quality



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
REGION 6
1445 ROSS AVENUE, SUITE 1200
DALLAS TX 75202-2733

NOV 30 2010

CERTIFIED MAIL RETURN REQUEST 7007 1490 0004 0582 0263

Sam D. Sanders,
Senior Environmental Engineer
VALERO REFINING-TEXAS, L.P.
Corpus Christi Manufacturing Facility
P.O. Box 9370
Corpus Christi, Texas 78469-9370



Re: Alternative Monitoring Plans (AMPs) – Valero Refining – Texas, L.P. (Valero)
West Plant, Corpus Christi, Nueces County, Account Number: NE-0112-G,
Regulated Entity Number: RN100214386; Monitoring plan for West Plant,
Hydrocracker Feed Surge Drum, 47-V-02, vent stream to the fuel gas line that is
Combusted at the Hydrocracker Heaters: 47-H-01, 47-H-02, 47-H-03, and
47-H-04, dated November 20, 2007.

Dear Mr. Sanders:

This letter is in response to your AMP request, dated November 20, 2007, as referenced above for your Corpus Christi West Plant. Your request involves control of a vent stream from the Hydrocracker Feed Surge Drum, 47-V-02 that is combusted at the Hydrocracker Heaters: 47-H-01, 47-H-02, 47-H-03, and 47-H-04. Based on the description of your process vent stream, the particular design of the vent gas controls, and H₂S monitoring data, the Environmental Protection Agency is approving your AMP.

According to the diagrams provided in your AMP, there are no crossover points or points where sour gas can be introduced into the fuel gas to the Hydrocracker Heaters 47-H-01, 47-H-02, 47-H-03, and 47-H-04. The sample point for the vent stream from the Hydrocracker Feed Surge Drum (47-V-02) is located at the fuel gas line from the Feed Surge Drum (47-V-02) to the fuel gas line to the Hydrocracker Heaters. H₂S testing of the vent stream was conducted using colorimetric tubes, and results from a 14 day monitoring period indicate an average H₂S concentration of 7.71 ppmv.

Valero has proposed to use concentrations of Total Sulfur in the Combined Feed and the temperature of the contents in the Feed Surge Drum (47-V-02) as a means of monitoring the vent stream that is combusted in the Hydrocracker Heaters. Total Sulfur and the temperature of the Feed Surge Drum would be sampled and analyzed in conjunction with the Vent from 47-V-02 Feed Surge Drum H₂S monitoring schedule. Process parameter limits should not exceed 1.50 wt % maximum of Total Sulfur in the Combined Feed and a temperature in the Feed Surge Drum (47-V-02) not to exceed 190 degrees F.

Valero would follow the seven step process outlined in Appendix D (Alternative Monitoring Plan for NSPS Subpart J Refinery Fuel Gas) of the Valero consent decree (Civil Action No. SA-05-CA-0569) relative to monitoring the Hydrocracker Feed Surge Drum, 48-V-01, vent stream.

If you have any questions or concerns regarding this AMP approval, please do not hesitate to contact either Ms. Cynthia Kaleri of my staff at (214) 665-6772, or Mr. Garry Mokry of my staff at (214) 665-7429.

Sincerely yours,



David F. Garcia
Associate Director
Air/Toxics & Inspection
Coordination Branch

Cc: Robert Lucas (OAQPS)
Maria Malave (OECA)
David Turner (TCEQ, Corpus Christi)
John Sadler (TCEQ, Austin)
Karen Kornell (Office of the Attorney General of the State of Texas)



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

REGION 6
1445 ROSS AVENUE, SUITE 1200
DALLAS, TX 75202-2733

OCT 04 2011



Mr. Sam Sanders
Senior Environmental Engineer
Valero Refining – Texas L.P.
Corpus Christi East Plant
Post Office Box 9370
Corpus Christi, Texas 78469-9370

**RE: New Source Performance Standards (NSPS) 40 CFR 60 Subpart J
Alternative Monitoring Plan (AMP)
Sulfur Loading and Storage Vent Streams
Routed to Tail Gas Incinerator (TGI)
CD No SA-05-CA-0569**

Dear Mr. Sanders:

This letter is in response to your AMP dated November 20, 2007, with additional information from April 30, 2011, and August 24, 2011, concerning sulfur vapor vents from the following:

1. East Plant Sulfur Truck (Unit 141 and SULF-TLDG) and Railcar loading (Unit 141 and SULF-RCLD);
2. East Plant Sulfur Storage Tank (195-TK-038), routed to SRU No. 2 TGI (Unit 195);
3. East Plant Sulfur Drain Header (195-V-037), routed to SRU No. 1 TGI (Unit 195);
4. East Plant Sulfur Drain Header (141-V-021), routed to SRU No. 1 TGI (Unit 141);
5. West Plant Sulfur Truck Loading vent gas stream (Unit 41 and Vent Stream WPSULF-TLD) routed to the Claus Tail Gas Burner (41H07) TGI or alternately to the Claus Tail Gas Burner (41H34) TGI.

In addition to the review of all material submitted by Valero, EPA also evaluated saturated steam tables and partial vapor pressure of sulfur at various temperatures. From the available materials it has been determined that saturated steam at 50 pounds per square inch gauge (psig) pressure, which keeps the sulfur molten for storage and transfer operations at approximately 139°C, does not generate sufficient partial vapor pressure to exceed 250 ppm by volume of sulfur dioxide at 0% oxygen after vapor incineration. Under consideration of this information, EPA approves the alternative monitoring plan as stipulated above such that the temperature of the molten sulfur (139°C) shall not generate sufficient vapors to exceed 250 ppmv of sulfur dioxide at 0% oxygen in the combusted gas.

Recycled/Recyclable • Printed with Vegetable Oil Based Inks on 100% Recycled Paper (40% Postconsumer)

If you have any questions, please contact Mr. Charles Handrich at (214) 665-6553.

Sincerely,

A handwritten signature in black ink, appearing to read "David F. Garcia". The signature is fluid and cursive, with the first name "David" being more prominent.

David F. Garcia
Associate Director
Air/Toxics & Inspection
Coordination Branch

cc: Michael De La Cruz (Texas Commission on Environmental Quality)



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
REGION 6
1445 ROSS AVENUE, SUITE 1200
DALLAS TX 75202-2733

December 19, 2017

Sam Sanders
Staff Environmental Engineer
Valero Refining – Texas, L.P.
Post Office Box 9370
Corpus Christi, TX 78469-9370

Re: Alternative Monitoring Plan (AMP) – New Source Performance Standards (NSPS) for Petroleum Refineries, 40 Code of Federal Regulations (CFR) Part 60, Subpart J) – HOC Liquid Petroleum Gas (LPG) Merox Oxidizer Vent Stream Routed to the Sulfur Recovery Unit (SRU) No. 3 Shell-Claus Off-Gas Treatment (SCOT) Unit Tail Gas Incinerator (TGI) - Valero Corpus Christi, Texas West Refinery

Dear Mr. Sanders:

This letter is in response to your AMP request dated May 20, 2015, and supplemental data provided on May 9, 2017, concerning a fuel gas stream at the Valero Corpus Christi West Refinery that you have identified as inherently low in sulfur content under 40 CFR Part 60 Subpart J (NSPS Subpart J). Upon review of all available information, the Environmental Protection Agency (EPA) believes the HOC LPG Merox Oxidizer vent gas stream will meet the exemption provided at 40 CFR § 60.105(a)(4)(iv)(D), provided certain parametric monitoring provisions are maintained as represented in the AMP. Therefore, EPA conditionally approves your AMP as outlined in the enclosure to this letter.

Valero will not need to meet the continuous monitoring requirements of either 40 Code of Federal Regulations (CFR) § 60.105(a)(3) or § 60.105(a)(4) for the HOC LPG Merox Oxidizer Vent Stream or the SRU No. 3 SCOT TGI under this conditional AMP approval. However, if refinery operations change such that the sulfur content of the off-gas stream changes from representations delineated in the AMP submittals, then Valero must document the change(s) and follow the appropriate steps at 40 CFR § 60.105(b)(3)(i)-(iii). This conditional approval should also be referenced and attached to the facility's new source review (NSR) and Title V permits for federal enforceability. If you have any questions or concerns about this conditional approval, please contact Ms. Diana L. Lundelius of my staff either by email at Lundelius.Diana@epa.gov or by phone at (214) 665-7468.

Sincerely,

Steve Thompson
Chief, Air Enforcement Branch

Enclosure

cc: Michael De La Cruz, Texas Commission on Environmental Quality

ENCLOSURE
New Source Performance Standards (NSPS) Subpart J
Valero Refining - Corpus Christi West Refinery
HOC LPG Merox Oxidizer Vent to Sulfur Recovery Unit (SRU) No. 3 SCOT TGI

Valero Corpus Christi West Refinery submitted an alternative monitoring plan (AMP) request dated May 20, 2015, in order to claim the exemption at 40 CFR § 60.105(a)(4)(iv)(D) for a vent gas stream that is shown to be inherently low in sulfur content prior to combustion. Valero provided supplemental data on May 9, 2017, in accordance with 40 CFR § 60.105(b)(1), to substantiate and explain the conditions that ensure low amounts of sulfur in the fuel gas stream at all times.

Specifically, in the HOC Vapor Recovery Unit (VRU), gasoline is separated from liquefied petroleum gas (LPG) and dry gas. The LPG is treated to remove sulfur and is separated into propane/propylene and butane/butylene mixtures. The LPG Treater uses caustic to remove residual sulfur. The treater generates an off-gas stream that vents from an oxidizer tower (22L03-T1) and is routed to the SRU No.3 Shell-Claus Off-Gas Treatment (SCOT) Unit Tail Gas Incinerator (TGI) for combustion. Therefore, the HOC LPG Merox Oxidizer Vent Stream should contain very low amounts of hydrogen sulfide (H₂S). Constant caustic circulation flow, as well as forced air flow in the LPG Oxidizer Unit, ensures very low H₂S in the vent gas stream. Valero samples the circulated caustic at regular intervals, and tests the samples at the refinery onsite laboratory to determine caustic strength. Valero confirmed the following operating parameter range limits and values associated with the HOC LPG Merox Oxidizer Vent and the SRU No. 3 SCOT TGI:

Parameter	Range Limit or Value
Spent caustic strength – prewash	Not to exceed 50%
Spent caustic strength - treatment/regen/oxidizer	Not to exceed 25%
Caustic sampling frequency	Daily
Caustic change out frequency – prewash	Weekly or at 50% spent caustic
Caustic change out frequency – treatment/regen/oxidizer	At 25% sustained spent caustic
Average minimum caustic circulation flow rate	Above 20,000 pounds per hour
Average minimum air flow volume	150 pounds per hour

In the AMP submittal, Valero provided two weeks (14 samples) of monitoring data for the off-gas vent stream from the HOC LPG Merox Oxidizer Vent going to the SRU No. 3 SCOT TGI. Samples were obtained after the exit from the HOC LPG Merox Oxidizer, prior to mixing with other vent gas streams. Valero conducted H₂S monitoring using length of stain gas detector tubes according to the steps outlined in the exemption application, and the method outlined in Gas Processor Association Standard 2377-86. However, the length of stain H₂S detector tubes used had a range of 2.5 to 60 parts per million (ppm). The gas detector tubes have relative standard deviations of 5-15%, depending on the measured range for each tube type. The gas detector tubes are substantially similar to length of stain detector tubes specified in Gas Processor Association Standard 2377-86, except for the detection range. The two weeks of sample results showed concentrations of H₂S less than 5 parts per million by volume (ppmv) at the monitoring point. The monitoring data were submitted as representative of typical operating conditions affecting H₂S

content in the off-gas vent stream from the HOC LPG Merox Oxidizer that is routed to the SRU No. 3 SCOT TGI.

Valero also furnished process and instrumentation drawings (P&IDs) which showed that there are no other process vent streams that commingle with the HOC LPG Merox Oxidizer Vent, prior to entering the SRU No. 3 SCOT TGI. Furthermore, Valero has indicated that the vent stream is routed to the SRU No. 1 and No. 2 TGI in the event that the SRU No. 3 SCOT TGI is down for scheduled or unscheduled maintenance. Therefore, upon evaluation of all information provided and the specific representations made in the submittals as outlined above, the off-gas vent stream appears to meet the exemption of 40 CFR § 60.105(a)(4)(iv)(D), as long as Valero monitors and controls the relevant process parameters summarized above in order to maintain the exemption status of the HOC LPG Merox Oxidizer Vent Stream.

Appendix A

Acronym List 328

Acronym List

The following abbreviations or acronyms may be used in this permit:

ACFM	actual cubic feet per minute
AMOC	alternate means of control
ARP	Acid Rain Program
ASTM	American Society of Testing and Materials
B/PA	Beaumont/Port Arthur (nonattainment area)
CAM	Compliance Assurance Monitoring
CD	control device
CEMS	continuous emissions monitoring system
CFR	Code of Federal Regulations
COMS	continuous opacity monitoring system
CVS	closed vent system
D/FW	Dallas/Fort Worth (nonattainment area)
EP	emission point
EPA	U.S. Environmental Protection Agency
EU	emission unit
FCAA Amendments	Federal Clean Air Act Amendments
FOP	federal operating permit
gr/100 scf	grains per 100 standard cubic feet
HAP	hazardous air pollutant
H/G/B	Houston/Galveston/Brazoria (nonattainment area)
H ₂ S	hydrogen sulfide
ID No.	identification number
lb/hr	pound(s) per hour
MACT	Maximum Achievable Control Technology (40 CFR Part 63)
MMBtu/hr	Million British thermal units per hour
NA	nonattainment
N/A	not applicable
NADB	National Allowance Data Base
NESHAP	National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61)
NO _x	nitrogen oxides
NSPS	New Source Performance Standard (40 CFR Part 60)
NSR	New Source Review
ORIS	Office of Regulatory Information Systems
Pb	lead
PBR	Permit By Rule
PEMS	predictive emissions monitoring system
PM	particulate matter
ppmv	parts per million by volume
PRO	process unit
PSD	prevention of significant deterioration
psia	pounds per square inch absolute
SIP	state implementation plan
SO ₂	sulfur dioxide
TCEQ	Texas Commission on Environmental Quality
TSP	total suspended particulate
TVP	true vapor pressure
U.S.C.	United States Code
VOC	volatile organic compound

Appendix B

Major NSR Summary Table 330

Major NSR Summary Table

Permit Numbers 38754 and PSDTX324M15					Issuance Date: May 3, 2024		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
MSS Caps	MSS Caps	CO	2,085.19	128.91	51, 52, 53, 54, 55, 56, 57, 60, 61, 62, 68, 75, 76	50, 51, 52, 53, 54, 55, 56, 57, 60, 61, 62, 64, 66, 68, 74, 75, 76	75, 76
		H ₂ S	10.59	0.22			
		NH ₃	4.41	0.17			
		NO _x	356.84	27.19			
		PM	79.52	3.76			
		PM ₁₀	79.52	2.92			
		PM _{2.5}	79.52	2.92			
		SO ₂	996.29	338.89			
		VOC	578.44	70.04			
		Exempt Solvents	1.76	0.60			
1	Heater - Crude Heater (01-H-01)	CO	8.10	20.13	15, 18, 39, 40, 60, 75	15, 39, 40, 60, 74, 75	39, 40, 75
		NH ₃	0.05	0.17			
		NO _x	9.72	19.24			
		PM	1.21	4.00			
		PM ₁₀	1.21	4.00			
		PM _{2.5}	1.21	4.00			

Major NSR Summary Table

Permit Numbers 38754 and PSDTX324M15					Issuance Date: May 3, 2024		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
		SO ₂	2.50	5.71			
		VOC	0.87	2.90			
131	Heater - Crude Preflash (01-H-02)	CO	0.62	2.71	18, 60, 75	60, 69, 74, 75	75
		NH ₃	<0.01	0.02			
		NO _x	1.77	6.29			
		PM	0.13	0.49			
		PM ₁₀	0.13	0.49			
		PM _{2.5}	0.13	0.49			
		SO ₂	0.27	0.64			
		VOC	0.10	0.35			
132	Heater - Crude Stabilizer (01-H-03)	CO	0.17	0.72	18, 60, 75	60, 69, 74, 75	75
		NH ₃	<0.01	<0.01			
		NO _x	0.48	2.06			
		PM	0.04	0.15			
		PM ₁₀	0.04	0.15			
		PM _{2.5}	0.04	0.15			

Major NSR Summary Table

Permit Numbers 38754 and PSDTX324M15					Issuance Date: May 3, 2024		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
		SO ₂	0.07	0.22			
		VOC	0.03	0.11			
74	Vacuum Heater	CO	4.99	16.77	15, 18, 39, 40, 60, 75	15, 39, 40, 60, 74, 75	39, 40, 75
		NH ₃	0.03	0.14			
		NO _x	5.98	26.21			
		PM	0.74	3.26			
		PM ₁₀	0.74	3.26			
		PM _{2.5}	0.74	3.26			
		SO ₂	1.37	4.13			
		VOC	0.54	2.36			
114	Heater - Desalter Heater (11-H-01)	CO	3.54	15.52	15, 18, 19, 39, 40, 60, 75	15, 19, 39, 40, 60, 74, 75	39, 40, 75
		CO	3.54	15.52			
		NH ₃	0.03	0.14			
		NO _x	3.96	17.34			
		PM	0.74	3.23			
		PM ₁₀	0.74	3.23			

Major NSR Summary Table

Permit Numbers 38754 and PSDTX324M15					Issuance Date: May 3, 2024		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
		PM _{2.5}	0.74	3.23			
		SO ₂	1.52	4.60			
		VOC	0.53	2.34			
		H ₂ S	0.02	0.05			
115	HDS Heaters	CO	8.08	32.91	15, 18, 39, 40, 60, 75	15, 39, 40, 60, 74, 75	39, 40, 75
		NH ₃	0.05	0.22			
		NO _x	9.70	42.07			
		PM	1.20	5.22			
		PM ₁₀	1.20	5.22			
		PM _{2.5}	1.20	5.22			
		SO ₂	2.49	7.45			
		VOC	0.87	3.78			
115	HDS Heaters	CO	8.08	32.91	15, 18, 39, 40, 60, 75	15, 39, 40, 60, 74, 75	39, 40, 75
		NH ₃	0.05	0.22			
		NO _x	9.70	42.07			
		PM	1.20	5.22			

Major NSR Summary Table

Permit Numbers 38754 and PSDTX324M15					Issuance Date: May 3, 2024		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
		PM ₁₀	1.20	5.22			
		PM _{2.5}	1.20	5.22			
		SO ₂	2.49	7.45			
		VOC	0.87	3.78			
116	Heater - HDS Pre-Heater (12-H-02)	CO	0.31	1.10	18, 60, 75	60, 74, 75	75
		NH ₃	<0.01	0.02			
		NO _x	2.36	8.28			
		PM	0.15	0.51			
		PM ₁₀	0.15	0.51			
		PM _{2.5}	0.15	0.51			
		SO ₂	0.30	0.73			
		VOC	0.11	0.37			
118	Hydrogen Reformer Heater	CO	58.51	220.73	15, 18, 39, 40, 60, 75	15, 39, 40, 60, 74, 75	39, 40, 75
		NH ₃	0.37	1.52			
		NO _x	70.21	284.40			
		PM	8.72	35.80			

Major NSR Summary Table

Permit Numbers 38754 and PSDTX324M15					Issuance Date: May 3, 2024		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
		PM ₁₀	8.72	35.80			
		PM _{2.5}	8.72	35.80			
		SO ₂	44.53	122.64			
		VOC	9.95	25.91			
153	Heater - HR Boiler (30-B-02)	CO	8.46	28.94	15, 18, 39, 40, 60, 75	15, 39, 40, 60, 74, 75	39, 40, 75
		NH ₃	0.09	0.33			
		NO _x	22.56	82.34			
		PM	2.10	5.51			
		PM ₁₀	2.10	5.51			
		PM _{2.5}	2.10	5.51			
		SO ₂	4.34	10.66			
		VOC	1.52	3.99			
30-B-04	Boiler 30-B-04	CO	19.84	48.14	15, 18, 39, 40, 60, 75,	15, 39, 40, 60, 74, 75	39, 40, 75
		NH ₃	2.41	5.86			
		NO _x	8.25	20.02			
		PM	4.10	9.95			

Major NSR Summary Table

Permit Numbers 38754 and PSDTX324M15					Issuance Date: May 3, 2024		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
		PM ₁₀	4.10	9.95			
		PM _{2.5}	4.10	9.95			
		SO ₂	8.65	14.47			
		VOC	2.97	7.20			
30-B-04MSS	Boiler 30-B-04	CO	198.55	3.57	60	60, 74	
		NO _x	55.00	0.99			
117	Heater - Alky Frac. Reb. (31-H-01)	CO	2.51	8.83	15, 18, 39, 40, 60, 75	15, 39, 40, 60, 74, 75	39, 40, 75
		NH ₃	0.05	0.17			
		NO _x	5.64	19.86			
		PM	1.17	4.11			
		PM ₁₀	1.17	4.11			
		PM _{2.5}	1.17	4.11			
		SO ₂	2.41	5.86			
		VOC	0.85	2.97			
120	Heater - Butamer Heater (36-H-01)	CO	0.27	0.98	18, 60, 75	60, 74, 75	75
		NH ₃	<0.01	0.02			

Major NSR Summary Table

Permit Numbers 38754 and PSDTX324M15					Issuance Date: May 3, 2024		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
		NO _x	2.00	4.30			
		PM	0.12	0.26			
		PM ₁₀	0.12	0.26			
		PM _{2.5}	0.12	0.26			
		SO ₂	0.26	0.41			
		VOC	0.09	0.19			
162	Oleflex Heater	CO	19.45	69.49	15, 18, 39, 40, 60, 75	15, 39, 40, 60, 74, 75	39, 40, 75
		NH ₃	0.12	0.49			
		NO _x	23.34	65.75			
		PM	2.90	11.62			
		PM ₁₀	2.90	11.62			
		PM _{2.5}	2.90	11.62			
		SO ₂	5.99	16.57			
		VOC	2.10	8.41			
119	Heater - Sulften Heater (46-H-01)	CO	0.35	1.49	18, 60, 75	60, 74, 75	75
		NH ₃	0.01	0.03			

Major NSR Summary Table

Permit Numbers 38754 and PSDTX324M15					Issuance Date: May 3, 2024		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
		NO _x	2.62	5.21			
		PM	0.16	0.32			
		PM ₁₀	0.16	0.32			
		PM _{2.5}	0.16	0.32			
		SO ₂	0.34	0.63			
		VOC	0.12	0.24			
150	HCU Heater	CO	6.10	24.38	15, 18, 39, 40, 60, 75	15, 39, 40, 60, 74, 75	39, 40, 75
		NH ₃	0.06	0.26			
		NO _x	12.19	48.76			
		PM	1.51	6.06			
		PM ₁₀	1.51	6.06			
		PM _{2.5}	1.51	6.06			
		SO ₂	3.13	8.63			
		VOC	1.10	4.38			
151	Heater - NHU Heater (48-H-01)	CO	3.05	6.68	18, 60, 75	60, 74, 75	75
		NH ₃	0.01	0.05			

Major NSR Summary Table

Permit Numbers 38754 and PSDTX324M15					Issuance Date: May 3, 2024		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
		NO _x	3.90	17.08			
		PM	0.29	1.27			
		PM ₁₀	0.29	1.27			
		PM _{2.5}	0.29	1.27			
		SO ₂	0.60	1.81			
		VOC	0.21	0.92			
152	CRU Heater	CO	16.85	57.02	15, 18, 39, 40, 60, 75	15, 39, 40, 60, 74, 75	39, 40, 75
		NH ₃	0.18	0.60			
		NO _x	39.31	133.06			
		PM	4.18	14.16			
		PM ₁₀	4.18	14.16			
		PM _{2.5}	4.18	14.16			
		SO ₂	9.80	22.69			
		VOC	3.03	10.25			
172	Heater - RSU Heater (49-H-71)	CO	3.30	12.72	15, 18, 39, 40, 60, 75	15, 39, 40, 60, 74, 75	39, 40, 75
		NH ₃	0.02	0.08			

Major NSR Summary Table

Permit Numbers 38754 and PSDTX324M15					Issuance Date: May 3, 2024		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
		NO _x	3.96	15.26			
		PM	0.49	1.90			
		PM ₁₀	0.49	1.90			
		PM _{2.5}	0.49	1.90			
		SO ₂	1.02	2.70			
		VOC	0.36	1.37			
49-H-90	Heater - C7 Splitter Reb. (49-H-90)	CO	5.32	16.82	15, 18, 39, 40, 60, 75	15, 39, 40, 60, 74, 75	39, 40, 75
		NH ₃	0.03	0.13			
		NO _x	4.25	15.46			
		PM	0.79	3.01			
		PM ₁₀	0.79	3.01			
		PM _{2.5}	0.79	3.01			
		SO ₂	1.64	4.29			
		VOC	0.57	2.18			
195	Heater - GDU Charge Heater (52-H-01)	CO	13.65	34.29	15, 18, 39, 40, 60, 75	15, 39, 40, 60, 74, 75	39, 40, 75
		NH ₃	0.05	0.20			

Major NSR Summary Table

Permit Numbers 38754 and PSDTX324M15					Issuance Date: May 3, 2024		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
		NO _x	5.80	14.69			
		PM	1.23	4.61			
		PM ₁₀	1.23	4.61			
		PM _{2.5}	1.23	4.61			
		SO ₂	2.55	6.57			
		VOC	0.89	3.34			
1F	Crude Unit	VOC	See Subcap	See Subcap			
2F	Vacuum Unit	H ₂ S	See Subcap	See Subcap			
		VOC	See Subcap	See Subcap			
4F	LEU Unit	VOC	See Subcap	See Subcap			
11F	Desalter Unit	VOC	See Subcap	See Subcap			
12F	HDS Unit	H ₂ S	See Subcap	See Subcap			
		VOC	See Subcap	See Subcap			
13F	H ₂ Reformer	VOC	See Subcap	See Subcap			
18F	LEU -2	VOC	See Subcap	See Subcap			
20F	LRU	VOC	See Subcap	See Subcap			

Major NSR Summary Table

Permit Numbers 38754 and PSDTX324M15					Issuance Date: May 3, 2024		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
21/22F	HOC	H ₂ S	See Subcap	See Subcap			
		VOC	See Subcap	See Subcap			
30F	Boiler House	VOC	See Subcap	See Subcap			
07F	#07 BUP Flare	VOC	See Subcap	See Subcap			
31F	Alky Unit	H ₂ S	See Subcap	See Subcap			
		HF	0.52	2.30	34, 43, 75, 77	34, 74, 75, 77	45, 75, 77
		VOC	See Subcap	See Subcap			
36F	Butamer Unit	VOC	See Subcap	See Subcap			
37F	Iso-Octene	VOC	See Subcap	See Subcap			
38F	Oleflex Unit	VOC	See Subcap	See Subcap			
46-24F	SULF-10 Fugitives (5)	H ₂ S	See Subcap	See Subcap			
		VOC	See Subcap	See Subcap			
41F	SRU Unit Fugitives (5)	H ₂ S	See Subcap	See Subcap			
		VOC	See Subcap	See Subcap			
47F	HCU Unit	H ₂ S	See Subcap	See Subcap			
		VOC	See Subcap	See Subcap			

Major NSR Summary Table

Permit Numbers 38754 and PSDTX324M15					Issuance Date: May 3, 2024		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
47PSA	PSA Unit	VOC	See Subcap	See Subcap			
48F	NHT Unit	H ₂ S	See Subcap	See Subcap			
		VOC	See Subcap	See Subcap			
49F	CRU Unit	VOC	See Subcap	See Subcap			
175	XFU/RFU/C7Split Unit	VOC	See Subcap	See Subcap			
52F	GDU Unit	VOC	See Subcap	See Subcap			
DOCKS	DK-Docks	VOC	See Subcap	See Subcap			
08F	#08FLR/Day Tanks	VOC	See Subcap	See Subcap			
LPG STGF	LPG STORAGE	VOC	See Subcap	See Subcap			
MVRUF	MVRU	VOC	See Subcap	See Subcap			
TERM-F	#TM-Terminal	VOC	See Subcap	See Subcap			
TRKRACKFUG	TRUCK RACK (5)	VOC	See Subcap	See Subcap			
83F	Wastewater Treatment Plant	VOC	See Subcap	See Subcap			
54F	Selective Hydrogenation Unit	VOC	See Subcap	See Subcap			
42F	Sour Water Stripper	H ₂ S	See Subcap	See Subcap			

Major NSR Summary Table

Permit Numbers 38754 and PSDTX324M15					Issuance Date: May 3, 2024		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
		VOC	See Subcap	See Subcap			
##F	Selective Hydrogenation Unit (5)	VOC	See Subcap	See Subcap			
##F	LPG Gas Plant (5)	VOC	See Subcap	See Subcap			
##F	Boiler 30-B-05 (5)	VOC	See Subcap	See Subcap			
168	Oleflex CCR	Cl ₂	<0.01	0.04	26, 75, 77	74, 75, 77	75, 77
		H ₂ SO ₄	<0.01	0.01			
		HCl	0.06	0.28			
		SO ₂	0.04	0.19			
69	Tank - 9	VOC	3.10	0.49		74	
122	Cooling Tower - HOC	PM	3.54	13.17	30	30, 74	
		PM ₁₀	3.36	12.52			
		PM _{2.5}	0.53	1.96			
		VOC	5.67	21.09			
123	Cooling Tower - Alky	PM	0.71	2.00	30	30, 74	
		PM ₁₀	0.70	1.98			

Major NSR Summary Table

Permit Numbers 38754 and PSDTX324M15					Issuance Date: May 3, 2024		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
		PM _{2.5}	0.19	0.55			
		VOC	1.26	3.55			
167-CT	Cooling Tower - BUP	PM	4.52	19.26	30	30, 74	
		PM ₁₀	4.30	18.33			
		PM _{2.5}	0.67	2.88			
		VOC	1.47	6.27			
1CT	Cooling Tower - Crude	PM	0.34	1.13	30	30, 74	
		PM ₁₀	0.34	1.11			
		PM _{2.5}	0.06	0.21			
		VOC	0.17	0.55			
16-P-04	Engine - 16-P-04	CO	2.20	0.06	18	74	
		NO _x	8.00	0.21			
		PM	0.73	0.02			
		PM ₁₀	0.73	0.02			
		PM _{2.5}	0.73	0.02			
		SO ₂	0.68	0.02			

Major NSR Summary Table

Permit Numbers 38754 and PSDTX324M15					Issuance Date: May 3, 2024		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
		VOC	0.83	0.02			
16-P-07	Engine - 16-P-07	CO	2.67	0.04	18	74	
		NO _x	9.69	0.15			
		PM	0.88	0.01			
		PM ₁₀	0.88	0.01			
		PM _{2.5}	0.88	0.01			
		SO ₂	0.82	0.01			
		VOC	1.01	0.02			
16-P-11	Engine - 16-P-11	CO	0.80	0.02		74	
		NO _x	3.32	0.09			
		PM	0.11	<0.01			
		PM ₁₀	0.11	<0.01			
		PM _{2.5}	0.11	<0.01			
		SO ₂	0.10	<0.01			
		VOC	0.12	<0.01			
16-P-12	Engine - 16-P-12	CO	0.80	0.02	18	74	

Major NSR Summary Table

Permit Numbers 38754 and PSDTX324M15					Issuance Date: May 3, 2024		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
		NO _x	3.32	0.09			
		PM	0.11	<0.01			
		PM ₁₀	0.11	<0.01			
		PM _{2.5}	0.11	<0.01			
		SO ₂	0.10	<0.01			
		VOC	0.12	<0.01			
16-P-13	Engine - 16-P-13	CO	0.80	0.02	18	74	
		NO _x	3.32	0.09			
		PM	0.11	<0.01			
		PM ₁₀	0.11	<0.01			
		PM _{2.5}	0.11	<0.01			
		SO ₂	0.10	<0.01			
		VOC	0.12	<0.01			
16-P-14	Engine - 16-P-14	CO	0.80	0.02	18	74	
		NO _x	3.32	0.09			
		PM	0.11	<0.01			

Major NSR Summary Table

Permit Numbers 38754 and PSDTX324M15					Issuance Date: May 3, 2024		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
		PM ₁₀	0.11	<0.01			
		PM _{2.5}	0.11	<0.01			
		SO ₂	0.10	<0.01			
		VOC	0.12	<0.01			
126	Main Flare	CO	See Subcap	See Subcap			
		H ₂ S	See Subcap	See Subcap			
		NO _x	See Subcap	See Subcap			
		SO ₂	See Subcap	See Subcap			
		VOC	See Subcap	See Subcap			
158	Ground Flare	CO	See Subcap	See Subcap			
		H ₂ S	See Subcap	See Subcap			
		NO _x	See Subcap	See Subcap			
		SO ₂	See Subcap	See Subcap			
		VOC	See Subcap	See Subcap			
127	BUP Flare	CO	See Subcap	See Subcap			
		H ₂ S	See Subcap	See Subcap			

Major NSR Summary Table

Permit Numbers 38754 and PSDTX324M15					Issuance Date: May 3, 2024		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
		NO _x	See Subcap	See Subcap			
		SO ₂	See Subcap	See Subcap			
		VOC	See Subcap	See Subcap			
135	Acid Gas Flare (pilot only)	CO	See Subcap	See Subcap			
		H ₂ S	See Subcap	See Subcap			
		NO _x	See Subcap	See Subcap			
		SO ₂	See Subcap	See Subcap			
		VOC	See Subcap	See Subcap			
Various	Flares Subcap	CO	113.27	121.03	12, 18, 47, 62, 75, 77	12, 47, 62, 74, 75, 77	47, 75, 77
		H ₂ S	0.04	0.11			
		NO _x	23.04	20.77			
		SO ₂	3.55	10.43			
		VOC	291.17	63.51			
31	Loading - Heavy Oil	VOC	14.96	4.72		74	
SHIP FUG	Loading - Ships Fugitives (5)	VOC	237.46	91.74	10, 31, 33	31, 33, 74	31, 33

Major NSR Summary Table

Permit Numbers 38754 and PSDTX324M15					Issuance Date: May 3, 2024		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
VRU	Loading - MVRU	VOC	61.33	23.13	11, 39, 40, 77	11, 39, 40, 74, 77	39, 40, 77
TRUCKFUG	Loading - Truck Fugitives (5)	VOC	11.86	15.87	6, 31, 33	31, 33, 74	31, 33
TRUCKCOMB	Loading - Truck Combustor	CO	15.28	22.76	5, 18, 39, 75	5, 39, 74, 75	39, 75
		NO _x	7.64	11.38			
		SO ₂	0.02	0.03			
		VOC	8.18	13.61			
		PM	0.23	0.34			
		PM ₁₀	0.23	0.34			
		PM _{2.5}	0.23	0.34			
AE-49601A/B	AE-49601A/B Analyzer Vent	VOC	0.01	0.01		74	
AE-49900A/B	AE-49900A/B Analyzer Vent	VOC	0.01	0.01		74	
AE-49901A/B	AE-49901A/B Analyzer Vent	VOC	0.01	0.01		74	
121 (6)	HOC Belco Scrubber	CO	958.40	1559.15	21, 25, 39, 40, 60, 75, 77	21, 25, 39, 40, 60, 74, 75, 77	39, 40, 75, 77
		HCN	80.47	320.40			

Major NSR Summary Table

Permit Numbers 38754 and PSDTX324M15					Issuance Date: May 3, 2024		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
		H ₂ SO ₄	49.00	199.30			
		NO _x	384.12	473.81			
		PM	140.00	569.40			
		PM ₁₀	140.00	569.40			
		PM _{2.5}	140.00	569.40			
		SO ₂	223.08	437.03			
		VOC	30.42	123.79			
		H ₂ S	<0.01	<0.01			
		NH ₃	4.84	17.88			
121 (6)	SRU Incinerators Cap	CO	220.75	678.85	18, 22, 39, 40, 60, 75, 77	22, 39, 40, 60, 74, 75, 77	23, 39, 40, 75, 77
		H ₂ S	5.82	18.73			
		NO _x	54.64	239.31			
		PM	24.72	98.38			
		PM ₁₀	24.72	98.38			
		PM _{2.5}	24.72	98.38			
		SO ₂	191.32	837.99			

Major NSR Summary Table

Permit Numbers 38754 and PSDTX324M15					Issuance Date: May 3, 2024		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
		VOC	0.96	3.46			
121 (6)	Temporary SRU Stack	CO	10.04	7.23	18, 22, 39, 40, 60, 75, 77	22, 39, 40, 60, 74, 75, 77	23, 39, 40, 75, 77
		H ₂ S	0.047	0.03			
		NO _x	1.233	0.72			
		PM	1.205	0.87			
		PM ₁₀	1.205	0.87			
		PM _{2.5}	1.205	0.87			
		SO ₂	13.816	9.95			
FUG-CAP	Fugitives Subcap (5)	VOC	112.45	492.32	31, 32, 33, 34, 53, 62, 75, 77	31, 32, 33, 34, 53, 62, 74, 75, 77	31, 32, 33, 75, 77
		H ₂ S	0.59	2.58			
		NH ₃	0.01	0.06			
155	CRU CCR	HCl	0.07	0.29	26, 75, 77	27, 74, 75, 77	75, 77
118	SMR Condenser Vent	VOC	3.64	15.94	39, 46	39, 46, 74	39
21 BH	MAGNACAT Unit	PM	0.18	0.60		74	
		PM ₁₀	0.18	0.60			
		PM _{2.5}	0.18	0.60			

Major NSR Summary Table

Permit Numbers 38754 and PSDTX324M15					Issuance Date: May 3, 2024		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
187	Tank 25	H ₂ S	0.02	0.04	28, 76, 79	28, 74, 76, 79	76, 79
		NH ₃	<0.01	<0.01			
		VOC	1.43	5.33			
83-P-136A	Engine 83-P-136A-EN	CO	2.48	0.06	18	74	
		NO _x	7.43	0.19			
		PM	0.38	<0.01			
		PM ₁₀	0.38	<0.01			
		PM _{2.5}	0.38	<0.01			
		SO ₂	0.88	0.02			
		VOC	7.43	0.19			
83-P-136B	Engine 83-P-136B-EN	CO	2.48	0.06	18	74	
		NO _x	7.43	0.19			
		PM	0.38	<0.01			
		PM ₁₀	0.38	<0.01			
		PM _{2.5}	0.38	<0.01			
		SO ₂	0.88	0.02			

Major NSR Summary Table

Permit Numbers 38754 and PSDTX324M15					Issuance Date: May 3, 2024		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
		VOC	7.43	0.19			
WWTP-OWS	WW collection system	VOC	8.62	37.77	35, 36, 75, 76	35, 36, 74, 75, 76	35, 75, 76
83-TK-26	Tank 26	VOC	0.12	0.45	28, 37, 76	28, 37, 74, 76	76
83-TK-159	Tank 159	VOC	0.15	0.39	37, 76	37, 74, 76	76
83-TK-160	Tank 160	VOC	0.15	0.39	37, 76	37, 74, 76	76
83-V-97	Tank 97	VOC	0.18	0.40	28, 37, 76	28, 37, 74, 76	76
83-V-58	Tank 58	VOC	0.11	0.44	37, 76	37, 74, 76	76
83-V-59	Tank 59	VOC	0.11	0.44	37, 76	37, 74, 76	76
83-TK-162	Tank 162	VOC	0.39	1.77	28, 37, 76	28, 37, 74, 76	76
83-TK-155	Tank 155	VOC	0.39	1.77	28, 37, 76	28, 37, 74, 76	76
124	API/DGF Combustor	CO	1.65	7.22	13, 18, 39, 40, 52, 75, 76	13, 39, 40, 74, 75, 76	39, 40, 75, 76
		NO _x	0.45	1.76			
		SO ₂	0.03	0.13			
		VOC	2.94	12.88			
83-TK-23	Equalization Tank	VOC	0.81	3.51	28, 37, 76	28, 37, 74, 76	76
83-TK27	Bio Oxidation Reactor	VOC	0.51	2.22	37, 38	37, 38, 74	

Major NSR Summary Table

Permit Numbers 38754 and PSDTX324M15					Issuance Date: May 3, 2024		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
	Tank						
WWTP-AERB	Aeration Basin	VOC	0.25	1.09	35, 37, 38	35, 37, 38, 74	35
WWTP-CLRF	Clarifier	VOC	<0.01	0.04	35, 37, 75	35, 37, 74, 75	35, 75
WWTP-SLB	Saline Basin	VOC	<0.01	<0.01	35, 37, 75	35, 37, 74, 75	35, 75
01-01	Crude/Vacuum Unit Pump Alley	VOC	<0.01	0.02	76	74, 76	76
01-02	North Side of Vacuum Unit	VOC	<0.01	0.02	76	74, 76	76
01-03	North Side of Vacuum Unit	VOC	<0.01	0.02	76	74, 76	76
01-04	Northwest Side of Vacuum Unit - Main Sump	VOC	<0.01	0.03	76	74, 76	76
03-01	N of Tanks 156/161	VOC	0.02	0.08	76	74, 76	76
98-02	WP MSAT Rail Rack	VOC	0.02	0.08	76	74, 76	76
11-01	Desalter Pump Alley	VOC	<0.01	0.02	76	74, 76	76
41-01	North of 43-TK-08 (Amine Tank)	VOC	<0.01	0.02	76	74, 76	76
41-02	W of 41-V-05 (Acid Gas	VOC	<0.01	0.02	76	74, 76	76

Major NSR Summary Table

Permit Numbers 38754 and PSDTX324M15					Issuance Date: May 3, 2024		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
	K.O. Drum)						
49-01	Northwest of XFU	VOC	<0.01	0.02	76	74, 76	76
49-02	North Side of NHT (Unit 48)	VOC	<0.01	0.02	76	74, 76	76
49-03	NHT (Unit 48) Pump Alley	VOC	<0.01	0.02	76	74, 76	76
50-01	East of Tank 62	VOC	<0.01	0.02	76	74, 76	76
52-01	NW of GDU MCC Room	VOC	<0.01	0.02	76	74, 76	76
70-01	East of Tank 55	VOC	<0.01	0.02	76	74, 76	76
70-02	Northwest of Tank 106	VOC	<0.01	0.02	76	74, 76	76
70-03	West of Tank 94 (S&D Main Sump)	VOC	<0.01	0.03	76	74, 76	76
72-01	East of Tank 111	VOC	<0.01	0.02	76	74, 76	76
73-01	North of Tank 152 (Terminal 2A)	VOC	<0.01	0.02	76	74, 76	76
73-02	Between TK 8 & TK 164 (Terminal 2)	VOC	<0.01	0.02	76	74, 76	76
83-01	WWT (Hydroblast Pad)	VOC	0.02	0.07	76	74, 76	76

Major NSR Summary Table

Permit Numbers 38754 and PSDTX324M15					Issuance Date: May 3, 2024		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
83-02	WWT (Desalter Lift Station)	VOC	0.01	0.05	76	74, 76	76
83-03	WWT (East of KOH Treater)	VOC	0.02	0.07	76	74, 76	76
83-04	WWT (Northeast of Tank 159)	VOC	<0.01	0.02	76	74, 76	76
83-05	WWT (North Lift Station)	VOC	<0.01	0.03	76	74, 76	76
83-06	WWT (North of V-68)	VOC	<0.01	0.02	76	74, 76	76
83-07	WWT (South of V-55)	VOC	<0.01	0.02	76	74, 76	76
83-09	WWT (BSRP)	VOC	<0.01	0.02	76	74, 76	76
83-10	WWT 83-V-99 (Diversion Box)	VOC	0.02	0.07	76	74, 76	76
83-12	WWT 83-V-28 (SE of Catalyst Pad)	VOC	0.02	0.07	76	74, 76	76
V-201	WP MSAT Rail Rack	VOC	0.51	2.23	4, 76	74, 76	76
124a	WP WWT API Combustor Backup	VOC	0.02	0.08	76	74, 76	76
16-V-11	FWP 16-P-11 Diesel Tank	VOC	0.03	<0.01		28, 74	

Major NSR Summary Table

Permit Numbers 38754 and PSDTX324M15					Issuance Date: May 3, 2024		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
16-V-12	FWP 16-P-12 Diesel Tank	VOC	0.03	<0.01		28, 74	
16-V-13	FWP 16-P-13 Diesel Tank	VOC	0.03	<0.01		28, 74	
16-V-14	FWP 16-P-14 Diesel Tank	VOC	0.03	<0.01		28, 74	
FWP-FUG	Firewater Pump Engine Fugitives	VOC	0.06	0.26	31, 32	31, 32, 74	31, 32
30-B-05	Boiler 30-B-05	CO	33.48	70.84	15, 18, 39, 40, 60, 75, 77	15, 39, 40, 60, 74, 75, 77	39, 40, 75, 77
		NH ₃	2.18	8.68			
		NO _x	7.16	30.14			
		PM	3.56	14.16			
		PM ₁₀	3.56	14.16			
		PM _{2.5}	3.56	14.16			
		SO ₂	11.56	38.06			
		H ₂ S	<0.01	<0.01			
		VOC	2.81	11.30			
30-B-05	Boiler 30-B-05 (MSS)	NO _x	71.61	--	60	60, 74	

Major NSR Summary Table

Permit Numbers 38754 and PSDTX324M15					Issuance Date: May 3, 2024		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
HOC-PP-CT	Cooling Tower-Propylene Project	PM	0.78	3.42	30, 77	30, 74, 77	77
		PM ₁₀	0.18	0.81			
		PM _{2.5}	<0.01	0.01			
		VOC	1.09	4.78			
XX-01	HOC PP Gas Plant CAS	VOC	<0.01	0.02	36	36	

- (1) Emission point identification - either specific equipment designation or emission point number from plot plan.
- (2) Specific point source name. For fugitive sources, use area name or fugitive source name.
- (3)
 - Cl₂ - chlorine
 - CO - carbon monoxide
 - HCN - hydrogen cyanide
 - HF - hydrogen fluoride
 - H₂S - hydrogen sulfide
 - H₂SO₄ - sulfuric acid
 - MSS - Maintenance, Startup and Shutdown
 - NH₃ - ammonia
 - NO_x - total oxides of nitrogen
 - PM - total particulate matter, suspended in the atmosphere, including PM₁₀ and PM_{2.5}, as represented
 - PM₁₀ - total particulate matter equal to or less than 10 microns in diameter, including PM_{2.5}, as represented
 - PM_{2.5} - particulate matter equal to or less than 2.5 microns in diameter
 - SO₂ - sulfur dioxide
 - VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1
- (4) Compliance with annual emission limits (tons per year) is based on a 12-month rolling period.
- (5) Emission rate is an estimate and is enforceable through compliance with the applicable special condition(s) and permit application representations.

Major NSR Summary Table

Permit Number GHGPSDTX211					Issuance Date: May 3, 2024		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lb/hr	TPY (4)	Special Condition/Application Information	Special Condition/Application Information	Special Condition/Application Information
121	HOC Belco Scrubber	CO ₂ (5)		2,451,673.00	82	83	
		CH ₄ (5)		72.08			
		N ₂ O (5)		14.42			
		CO ₂ e		2,457,772.00			
Various (FUG-CAP)	Fugitives Subcap	CH ₄ (5)		3.59	82	83	
		CO ₂ e		90.00			
30-B-05	Boiler 30-B-05	CO ₂ (5)		222,364.00	82, 84	83, 84	
		CH ₄ (5)		4.19			
		N ₂ O (5)		0.42			
		CO ₂ e		22,594.00			

(1) Emission point identification - either specific equipment designation or emission point number from plot plan.

(2) Specific point source name. For fugitive sources, use area name or fugitive source name.

(3) CO₂ - carbon dioxide
 N₂O - nitrous oxide
 CH₄ - methane
 CO₂e - carbon dioxide equivalents based on the following Global Warming Potentials (1/2015):
 CO₂ (1), N₂O (298), CH₄(25)

(4) Compliance with annual emission limits (tons per year) is based on a 12-month rolling period. These rates include emissions from maintenance, startup, and shutdown.

(5) Emission rate is given for informational purposes only and does not constitute enforceable limit.



Texas Commission on Environmental Quality Air Quality Permit

A Permit is Hereby Issued To
Valero Refining-Texas, L.P.
Authorizing the Construction and Operation of
Valero Corpus Christi Refinery West Plant
Located at Corpus Christi, Nueces County, Texas
Latitude 27.820555 Longitude -97.488333

Permits: 38754, PSOTX324M15 and GHGPSOTX211

Amendment Date: May 3, 2024

Expiration Date: January 22, 2024


For the Commission

1. **Facilities** covered by this permit shall be constructed and operated as specified in the application for the permit. All representations regarding construction plans and operation procedures contained in the permit application shall be conditions upon which the permit is issued. Variations from these representations shall be unlawful unless the permit holder first makes application to the Texas Commission on Environmental Quality (commission) Executive Director to amend this permit in that regard and such amendment is approved. [Title 30 Texas Administrative Code (TAC) Section 116.116 (30 TAC § 116.116)]¹
2. **Voiding of Permit.** A permit or permit amendment is automatically void if the holder fails to begin construction within 18 months of the date of issuance, discontinues construction for more than 18 months prior to completion, or fails to complete construction within a reasonable time. Upon request, the executive director may grant an 18-month extension. Before the extension is granted the permit may be subject to revision based on best available control technology, lowest achievable emission rate, and netting or offsets as applicable. One additional extension of up to 18 months may be granted if the permit holder demonstrates that emissions from the facility will comply with all rules and regulations of the commission, the intent of the Texas Clean Air Act (TCAA), including protection of the public's health and physical property; and (b)(1) the permit holder is a party to litigation not of the permit holder's initiation regarding the issuance of the permit; or (b)(2) the permit holder has spent, or committed to spend, at least 10 percent of the estimated total cost of the project up to a maximum of \$5 million. A permit holder granted an extension under subsection (b)(1) of this section may receive one subsequent extension if the permit holder meets the conditions of subsection (b)(2) of this section. [30 TAC § 116.120]
3. **Construction Progress.** Start of construction, construction interruptions exceeding 45 days, and completion of construction shall be reported to the appropriate regional office of the commission not later than 15 working days after occurrence of the event. [30 TAC § 116.115(b)(2)(A)]
4. **Start-up Notification.** The appropriate air program regional office shall be notified prior to the commencement of operations of the facilities authorized by the permit in such a manner that a representative of the commission may be present. The permit holder shall provide a separate notification for the commencement of operations for each unit of phased construction, which may involve a series of units commencing operations at different times. Prior to operation of the facilities authorized by the permit, the permit holder shall identify the source or sources of allowances to be utilized for compliance with Chapter 101, Subchapter H, Division 3 of this title (relating to Mass Emissions Cap and Trade Program). [30 TAC § 116.115(b)(2)(B)]
5. **Sampling Requirements.** If sampling is required, the permit holder shall contact the commission's Office of Compliance and Enforcement prior to sampling to obtain the proper data forms and procedures. All sampling and testing procedures must be approved by the executive director and coordinated with the regional representatives of the commission. The permit holder is also responsible for providing sampling facilities and conducting the sampling operations or contracting with an independent sampling consultant. [30 TAC § 116.115(b)(2)(C)]
6. **Equivalency of Methods.** The permit holder must demonstrate or otherwise justify the equivalency of emission control methods, sampling or other emission testing methods, and monitoring methods proposed as alternatives to methods indicated in the conditions of the permit. Alternative methods shall be applied for in writing and must be reviewed and approved by the executive director prior to their use in fulfilling any requirements of the permit. [30 TAC § 116.115(b)(2)(D)]
7. **Recordkeeping.** The permit holder shall maintain a copy of the permit along with records containing the information and data sufficient to demonstrate compliance with the permit, including production records and

operating hours; keep all required records in a file at the plant site. If, however, the facility normally operates unattended, records shall be maintained at the nearest staffed location within Texas specified in the application; make the records available at the request of personnel from the commission or any air pollution control program having jurisdiction in a timely manner; comply with any additional recordkeeping requirements specified in special conditions in the permit; and retain information in the file for at least two years following the date that the information or data is obtained. [30 TAC § 116.115(b)(2)(E)]

8. **Maximum Allowable Emission Rates.** The total emissions of air contaminants from any of the sources of emissions must not exceed the values stated on the table attached to the permit entitled "Emission Sources--Maximum Allowable Emission Rates." [30 TAC § 116.115(b)(2)(F)]¹
9. **Maintenance of Emission Control.** The permitted facilities shall not be operated unless all air pollution emission capture and abatement equipment is maintained in good working order and operating properly during normal facility operations. The permit holder shall provide notification in accordance with 30 TAC §101.201, 101.211, and 101.221 of this title (relating to Emissions Event Reporting and Recordkeeping Requirements; Scheduled Maintenance, Startup, and Shutdown Reporting and Recordkeeping Requirements; and Operational Requirements). [30 TAC § 116.115(b)(2)(G)]
10. **Compliance with Rules.** Acceptance of a permit by an applicant constitutes an acknowledgment and agreement that the permit holder will comply with all rules and orders of the commission issued in conformity with the TCAA and the conditions precedent to the granting of the permit. If more than one state or federal rule or regulation or permit condition is applicable, the most stringent limit or condition shall govern and be the standard by which compliance shall be demonstrated. Acceptance includes consent to the entrance of commission employees and agents into the permitted premises at reasonable times to investigate conditions relating to the emission or concentration of air contaminants, including compliance with the permit. [30 TAC § 116.115(b)(2)(H)]
11. **This permit may not be transferred, assigned, or conveyed by the holder except as provided by rule.** [30 TAC § 116.110(e)]
12. **There may be additional special conditions attached to a permit upon issuance or modification of the permit.** Such conditions in a permit may be more restrictive than the requirements of Title 30 of the Texas Administrative Code. [30 TAC § 116.115(c)]
13. **Emissions from this facility must not cause or contribute to "air pollution" as defined in Texas Health and Safety Code (THSC) §382.003(3) or violate THSC § 382.085.** If the executive director determines that such a condition or violation occurs, the holder shall implement additional abatement measures as necessary to control or prevent the condition or violation.
14. **The permit holder shall comply with all the requirements of this permit.** Emissions that exceed the limits of this permit are not authorized and are violations of this permit.¹

¹ Please be advised that the requirements of this provision of the general conditions may not be applicable to greenhouse gas emissions.

Common Acronyms in Air Permits

°C = Temperature in degrees Celsius	GLC _{max} = maximum (predicted) ground-level concentration
°F = Temperature in degrees Fahrenheit	gpm = gallon per minute
°K = Temperature in degrees Kelvin	gr/1000scf = grain per 1000 standard cubic feet
µg = microgram	gr/dscf = grain per dry standard cubic feet
µg/m ³ = microgram per cubic meter	H ₂ CO = formaldehyde
acfm = actual cubic feet per minute	H ₂ S = hydrogen sulfide
AMOC = alternate means of control	H ₂ SO ₄ = sulfuric acid
AOS = alternative operating scenario	HAP = hazardous air pollutant as listed in § 112(b) of the Federal Clean Air Act or Title 40 Code of Federal Regulations Part 63, Subpart C
AP-42 = Air Pollutant Emission Factors, 5th edition	HC = hydrocarbons
APD = Air Permits Division	HCl = hydrochloric acid, hydrogen chloride
API = American Petroleum Institute	Hg = mercury
APWL = air pollutant watch list	HGB = Houston/Galveston/Brazoria
BPA = Beaumont/ Port Arthur	hp = horsepower
BACT = best available control technology	hr = hour
BAE = baseline actual emissions	IFR = internal floating roof tank
bbl = barrel	in H ₂ O = inches of water
bbl/day = barrel per day	in Hg = inches of mercury
bhp = brake horsepower	IR = infrared
BMP = best management practices	ISC3 = Industrial Source Complex, a dispersion model
Btu = British thermal unit	ISCST3 = Industrial Source Complex Short-Term, a dispersion model
Btu/scf = British thermal unit per standard cubic foot or feet	K = Kelvin; extension of the degree Celsius scaled-down to absolute zero
CAA = Clean Air Act	LACT = lease automatic custody transfer
CAM = compliance-assurance monitoring	LAER = lowest achievable emission rate
CEMS = continuous emissions monitoring systems	lb = pound
cfm = cubic feet (per) minute	lb/day = pound per day
CFR = Code of Federal Regulations	lb/hr = pound per hour
CN = customer ID number	lb/MMBtu = pound per million British thermal units
CNG = compressed natural gas	LDAR = Leak Detection and Repair (Requirements)
CO = carbon monoxide	LNG = liquefied natural gas
COMS = continuous opacity monitoring system	LPG = liquefied petroleum gas
CPMS = continuous parametric monitoring system	LT/D = long ton per day
DFW = Dallas/ Fort Worth (Metrolplex)	m = meter
DE = destruction efficiency	m ³ = cubic meter
DRE = destruction and removal efficiency	m/sec = meters per second
dscf = dry standard cubic foot or feet	MACT = maximum achievable control technology
dscfm = dry standard cubic foot or feet per minute	MAERT = Maximum Allowable Emission Rate Table
ED = (TCEQ) Executive Director	MERA = Modeling and Effects Review Applicability
EF = emissions factor	mg = milligram
EFR = external floating roof tank	mg/g = milligram per gram
EGU = electric generating unit	mL = milliliter
EI = Emissions Inventory	MMBtu = million British thermal units
ELP = El Paso	MMBtu/hr = million British thermal units per hour
EPA = (United States) Environmental Protection Agency	MSDS = material safety data sheet
EPN = emission point number	MSS = maintenance, startup, and shutdown
ESL = effects screening level	MW = megawatt
ESP = electrostatic precipitator	NAAQS = National Ambient Air Quality Standards
FCAA = Federal Clean Air Act	NESHAP = National Emission Standards for Hazardous Air Pollutants
FCCU = fluid catalytic cracking unit	NGL = natural gas liquids
FID = flame ionization detector	NNSR = nonattainment new source review
FIN = facility identification number	NO _x = total oxides of nitrogen
ft = foot or feet	NSPS = New Source Performance Standards
ft/sec = foot or feet per second	
g = gram	
gal/week = gallon per week	
gal/yr = gallon per year	
GLC = ground level concentration	

PAL = plant-wide applicability limit
 PBR = Permit(s) by Rule
 PCP = pollution control project
 PEMS = predictive emission monitoring system
 PID = photo ionization detector
 PM = periodic monitoring
 PM = total particulate matter, suspended in the atmosphere, including PM₁₀ and PM_{2.5}, as represented
 PM_{2.5} = particulate matter equal to or less than 2.5 microns in diameter
 PM₁₀ = total particulate matter equal to or less than 10 microns in diameter, including PM_{2.5}, as represented
 POC = products of combustion
 ppb = parts per billion
 ppm = parts per million
 ppmv = parts per million (by) volume
 psia = pounds (per) square inch, absolute
 psig = pounds (per) square inch, gage
 PTE = potential to emit
 RA = relative accuracy
 RATA = relative accuracy test audit
 RM = reference method
 RVP = Reid vapor pressure
 scf = standard cubic foot or feet
 scfm = standard cubic foot or feet (per) minute
 SCR = selective catalytic reduction
 SIL = significant impact levels
 SNCR = selective non-catalytic reduction
 SO₂ = sulfur dioxide
 SOCMi = synthetic organic chemical manufacturing industry
 SRU = sulfur recovery unit
 TAC = Texas Administrative Code
 TCAA = Texas Clean Air Act
 TCEQ = Texas Commission on Environmental Quality
 TD = Toxicology Division
 TLV = threshold limit value
 TMDL = total maximum daily load
 tpd = tons per day
 tpy = tons per year
 TVP = true vapor pressure
 VOC = volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1
 VRU = vapor recovery unit or system

Special Conditions

Permit Numbers 38754, PSDTX324M15, and GHGPSDTX211

1. This permit authorizes emissions only from those points listed in the attached table entitled "Emission Sources - Maximum Allowable Emission Rates" (MAERT), and the facilities covered by this permit are authorized to emit subject to the emission rate limits on that table and other operating requirements specified in the special conditions.

Throughput Limitations

2. Tank truck loading operations are limited to the following liquids and maximum loading rates:
(12/19)

Chemical	Hourly Rate (gal/hr)
Kerosene	30,000
Diesel	60,000
Gasoline	98,000
Residual Oils	31,920

3. Marine loading shall comply with the following:
 - A. Marine loading with emissions that are controlled with the marine vapor recovery unit (VRU) shall be limited to a maximum of 35,000 bbl/hr. The liquids that are loaded at this rate and controlled with the VRU at this facility are limited to gasoline, natural gasoline, naphtha, cat gasoline, alkylate, and reformat.

The BT concentrate, mixed xylenes, heartcut, and toluene concentrate may also be loaded into marine vessels with emissions controlled by the VRU, at a rate not to exceed 5,000 bbl/hr. Only one of these products may be loaded at a time.
 - B. Marine loading with uncontrolled vapor emissions shall be limited to the following services at the indicated rates:

Liquid	Barge bbl/hr	Ship bbl/hr
Diesel*	8,500	12,500
Kerosene*	5,000	12,500
Gas Oil	6,000	20,000
ATB	6,000	20,000
VTB	6,000	20,000
Slurry	6,000	0
Bunker	6,000	20,000

*Diesel and kerosene shall not be loaded onto ships and barges concurrently.

Loading Controls

4. Operation without visible liquid leaks or spills shall be maintained at all loading or unloading facilities regardless of vapor pressure. This does not apply to momentary dripping associated with

the initial connection or disconnection of fittings. Sustained dripping from fittings during loading or unloading operations is not permitted. Any liquid spill that occurs during loading or unloading activities shall be cleaned up immediately to minimize air emissions.

5. Emissions resulting from the tank truck loading of gasoline shall be routed to the Vapor Combustor (Emission Point No. [EPN] TRUCKCOMB) for final abatement. The volatile organic compounds (VOC) emissions from EPN TRUCKCOMB shall not exceed 10 milligrams per liter of gasoline loaded. The vapor combustor combustion temperature shall be maintained at or above 1400°F (based on a five-minute averaging period) when loading vapors are routed to it. This temperature shall be recorded during loading operations and the records maintained on-site. The vapor combustor operating temperature may be lowered if it has been tested at the lower temperature in accordance with Special Condition (SC) No. 39 to demonstrate compliance with this emission limit. Records associated with this permit condition shall be kept for at least five years. The Vapor Combustion Unit (EPN TRUCKCOMB) shall comply with the following. **(12/19)**
 - A. The vapor combustor shall be operated with no visible emissions and have a constant pilot flame during all times waste gas could be directed to it. The temperature of the combustion chamber shall be continuously monitored when loading vapors are routed to it. The time, date, and duration of any drop of temperature below 1400°F shall be recorded. Each monitoring device shall be accurate to, and shall be calibrated or have a calibration check performed at a frequency in accordance with, the manufacturer's specifications.
 - B. Pilot and make-up fuel for the vapor combustor shall be pipeline-quality, sweet natural gas containing no more than 5 grains of total sulfur per 100 dry standard cubic feet.
 - C. The control device shall not have a bypass. If there is a bypass for the control device, comply with either of the following requirements:
 - (1) Install a flow indicator that records and verifies zero flow at least once every fifteen minutes immediately downstream of each valve that if opened would allow a vent stream to bypass the control device and be emitted, either directly or indirectly, to the atmosphere; or
 - (2) Once a month, inspect the valves, verifying that the position of the valves and the condition of the car seals prevent flow out the bypass.

A bypass does not include authorized analyzer vents, highpoint bleeder vents, low point drains, or rupture discs upstream of pressure relief valves if the pressure between the disc and relief valve is monitored and recorded at least weekly. A deviation shall be reported if the monitoring or inspections indicate bypass of the control device when it is required to be in service.
6. All tank trucks loading gasoline at this facility shall be leak-tight tested a minimum of once a year using the method described in the U.S. Environmental Protection Agency (EPA) regulations in Title 40 Code of Federal Regulations Part 63 (40 CFR Part 63), Subparts A and R, National Emission Standards for Gasoline Distribution Facilities (Bulk Gasoline Terminals and Pipeline Breakout Stations). **(12/19)**
7. All tank truck loading of residual oils, kerosene and diesel shall be conducted using a submerged fill pipe or using a discharge point no higher than 6 in. above the bottom of the cargo tank. **(12/19)**
8. The marine VRU shall limit VOC emissions from EPN VRU to 5 mg/l of liquid loaded.

9. All marine loading emissions of liquids with vapor pressures greater than 0.5 pound per square inch, absolute (psia) must be vented to the VRU.
10. A vacuum of at least one-inch water column shall be established downstream of the dock pressure control valve prior to commencing marine loading. A vacuum shall also be established on the barge or ship being loaded if possible. The vacuum shall be maintained during loading and monitored continually or an alarm activated if the vacuum is not maintained.
11. The VRU VOC concentration as measured by the continuous emission monitor specified in SC No. 40 shall not exceed 7,621 parts per million (ppm) over any one-hour period while the marine loading emissions are being vented. If the reading exceeds this limit, marine loading shall be suspended, the Texas Commission on Environmental Quality (TCEQ) Corpus Christi Regional Office notified, and the cause determined and corrected before loading resumes.

Combustion Controls

12. Flares shall be designed and operated in accordance with the following requirements: **(01/21)**
 - A. The flare system(s) shall be designed such that the combined vent gas, assist air, and/or total steam to each flare meets the 40 CFR § 63.670 specifications for minimum combustion zone net heating value and maximum tip velocity at all times that emissions may be directed to the flare for more than 15 minutes. Flared gas actual exit velocity, vent gas net heating value, and flared gas combustion zone net heating value shall be determined in accordance with 40 CFR §63.670(k), §63.670(l), and §63.670(m) on a 15-minute block average and recorded at least once every 15 minutes.

If the flare actively receives perimeter assist air, it shall be operated to meet the 40 CFR §63.670 specifications for minimum net heating value dilution parameters.
 - B. The flare(s) shall be operated with pilot flame(s) present at all times vent gas may be directed to the flare(s). The pilot flame(s) shall be continuously monitored by a thermocouple, infrared monitor, or ultraviolet monitor. The time, date, and duration of any loss of pilot flame shall be recorded. Each monitoring device shall be accurate to, and shall be calibrated at a frequency in accordance with, the manufacturer's specifications.
 - C. Flares shall be operated with no visible emissions except periods not to exceed a total of five minutes during any two consecutive hours, demonstrated and recorded per the requirements of §63.670(h).
 - D. The permit holder shall install flow monitors that continuously measure, calculate and record the total volumetric vent stream flow rate (including waste gas, purge gas, supplemental gas, and sweep gas), and shall install a monitoring system capable of determining the concentration of individual components in the flare vent gas or the net heating value of the flare vent gas. The flow monitor sensor and analyzer sample points shall be installed in the vent stream such that the total vent stream to the flare is measured and analyzed.

If one or more gas streams that combine to comprise the total flare vent gas flow are monitored separately for net heating value and flow, the 15-minute block average net heating value shall be determined separately for each measurement location and a flow-weighted average of the gas stream net heating values shall be used to determine the 15-minute block average net heating value of the cumulative flare vent gas.

If assist air or assist steam is used, the owner or operator shall install, operate, calibrate, and maintain a monitoring system capable of continuously measuring, calculating, and recording the total volumetric flow rate of assist air and/or assist steam used with the flare.

If pre-mix assist air and/or perimeter assist are used, the owner or operator shall install, operate, calibrate, and maintain a monitoring system capable of separately measuring, calculating, and recording the volumetric flow rate of pre-mix assist air and/or perimeter assist air used with the flare. Continuously monitoring fan speed or power and using fan curves is an acceptable method for continuously monitoring assist air flow rates.

Perimeter assist air includes all air assist except pre-mix assist air. Pre-mix assist air includes any air intentionally entrained in center steam.

Assist air includes pre-mix assist air and perimeter assist air, but does not include the surrounding ambient air.

The monitors shall be calibrated or have a calibration check performed as specified in Table 13 of the appendix to 40 CFR 63, Part CC to meet the following accuracy specifications: the vent flow monitor shall be ± 20 percent of flow rate at velocities ranging from 0.03 to 0.3 meters per second (0.1 to 1 foot per second) ± 5 percent of flow rate at velocities greater than 0.3 meters per second (1 foot per second), all other gas flow monitors shall be ± 5 percent over the normal range of flow measured or 280 liters per minute (10 cubic feet per minute) whichever is greater, temperature monitor shall be ± 1 percent over the normal range of temperature measured, expressed in degrees Celsius (C), or 2.8 degrees C, whichever is greater, and pressure monitor shall be ± 5 percent over the normal operating range or 0.12 kilopascals (0.5 inches of water column), whichever is greater. For purposes of this permit, a calibration check means, at a minimum, using a second device or method to verify that the monitor is accurate as specified in the permit.

Calorimeters shall have an accuracy of at least $\pm 2\%$ of span and be calibrated, installed, operated, and maintained in accordance with manufacturer recommendations and as specified in Table 13 of the appendix to 40 CFR 63, Part CC, to continuously measure and record the net heating value of the vent gas sent to the flare, in British thermal units/standard cubic foot of the gas.

For determination of net heating value by gas chromatograph, the minimum accuracy shall be as specified in Performance Specification 9 of Part 60, appendix B. Composition monitoring instruments shall be calibrated, installed, operated, and maintained in accordance with manufacturer recommendations and as specified in 40 CFR §63.671(e) and Table 13 of 40 CFR Pt. 63, Subpart CC. Individual component properties specified in Table 12 of Subpart CC shall apply to net heating value calculations.

- E. Quality assured (or valid) data must be generated during periods that flare is operating. Loss of valid data due to periods of monitor break down, out-of-control operation (producing inaccurate data), repair, maintenance, or calibration may be exempted provided it does not exceed 5 percent of the time (in minutes) that the flare operated over the previous rolling 12-month period. The measurements missed shall be estimated using engineering judgment and the methods used recorded.
- F. Hourly mass emission rates shall be determined and recorded using the monitoring data collected pursuant to paragraph D of this Special Condition and the emission factors specified in the permit application PI-1 dated March 31, 2011.
- G. The Acid Gas Flare (EPN 135) is not authorized for routine emissions or for planned maintenance, startup, and shutdown (MSS) emissions.

13. The American Petroleum Institute (API) Separator Combustor shall achieve at least 98 percent destruction efficiency. The vapor combustor combustion temperature shall be maintained at or above 1600°F (based on a five-minute averaging period) when the separator is in service. This temperature shall be recorded and the records maintained on-site. The vapor combustor operating temperature may be lowered if it has been tested at the lower temperature in accordance with SC No. 38 to demonstrate compliance with this emission limit. Records associated with this permit condition shall be kept for five years.

A back-up carbon adsorption system (CAS) is a means of control equivalent to the API Separator Combustor for compliance with the preceding paragraph of this special condition. When used as back-up control, the CAS shall meet the following requirements:

- A. The CAS shall consist of 2 carbon canisters in series with adequate carbon supply for the emission control operation.
- B. The CAS shall be sampled downstream on the first can and the concentration recorded at least once every hour of CAS run time to determine breakthrough of the VOC. The sampling frequency may be extended using either of the following methods:
 - (1) The CAS systems equipped with an upstream liquid scrubber may be sampled once every 12 hours of CAS run time to determine breakthrough.
 - (2) Sampling frequency may be extended to up to 30 percent of the minimum potential saturation time for a new can of carbon. The permit holder shall maintain records including the calculations performed to determine the minimum saturation time.
 - (3) The carbon sampling frequency may be extended to longer periods based on previous experience with carbon control of a MSS waste gas stream. The past experience must be with the same VOC, type of facility, and MSS activity. The basis for the sampling frequency shall be recorded. If breakthrough is monitored on the initial sample of the upstream can when the polishing can is put in place, a permit deviation shall be recorded.
- C. The method of VOC sampling and analysis shall be by detector meeting the requirements of SC No. 52. **(02/18)**
- D. Breakthrough is defined as the highest measured VOC or benzene concentration at or exceeding 100 ppmv or 5 ppmv, respectively, above background. When the condition of breakthrough of VOC from the initial saturation canister occurs, the waste gas flow shall be switched to the second canister and a fresh canister shall be placed as the new final polishing canister within twenty-four hours. In lieu of replacing canisters, the flow of waste gas may be discontinued until the canisters are switched. Sufficient new activated carbon canisters shall be available to replace spent carbon canisters such that replacements can be done in the above specified time frame.
- E. Records of CAS monitoring shall include the following:
 - (1) Sample time and date.
 - (2) Monitoring results (ppmv).
 - (3) Canister replacement log.
- F. Single canister systems are allowed if the time the carbon canister is in service is limited to no more than 30 percent of the minimum potential saturation time. The permit holder shall maintain records for these systems, including the calculations performed to determine the

saturation time. The time limit on carbon canister service shall be recorded and the expiration date attached to the carbon can.

- G. Liquid scrubbers may be used upstream of carbon canisters to enhance VOC capture provided such systems are closed systems and the spent absorbing solution is discharged into a closed container, vessel, or system.
14. No visible emissions are allowed from the heaters.
15. The permittee shall operate a continuous hydrogen sulfide (H₂S) monitoring instrument in the fuel feed line header for all fired units with a firing rate greater than 40 MMBtu/hr to continuously monitor a representative sample of fuel gas for H₂S content. The instrument shall be installed and operated according to the specifications set out in 40 CFR § 60.105. These gases shall have a maximum H₂S concentration of 0.054 grain per dry standard cubic foot (dscf) on an hourly average. The Vacuum Unit Heater (EPN 74) may also be fired with vacuum off-gas having a maximum H₂S concentration of 0.10 grain/dscf on an hourly average.
- The following units with a firing rate greater than 40 MMBtu/hr are subject to this condition: EPNs 1, 74, 114, 115, 118, 153, 30-B-04, 117, 162, 150, 152, 172, 49-H-90, and 195.
16. Heater, boiler, and reboiler emissions of ammonia (NH₃), carbon monoxide (CO), hydrogen sulfide (H₂S), nitrogen oxide (NO_x), Particulate matter (PM), PM ≤ 10 microns diameter (PM₁₀), PM ≤ 2.5 microns diameter (PM_{2.5}), and volatile organic compounds (VOC) shall meet the following specifications:

EPN	Facility	NO _x 1-hr block average (lb/MMBtu)	NO _x 3-hr block average (lb/MMBtu)	NO _x daily 365 rolling average (lb/MMBtu)	NO _x Compliance Method
162	38-H-01/02/03	0.06	--	0.060	CEMS
1	Crude Heater	0.06	--	0.060	CEMS
74	Vacuum Unit Heater	0.06	0.060	--	stack test
150	47-H-01/02/03/04	0.06	0.060	--	stack test
152	49-H-01/02/03/04	0.07	--	0.070	CEMS
153	Boiler 30-B-02	--	--	0.080	CEMS
172	RSU Heater	0.06	0.060	--	stack test
49-H-90	C7 Splitter Reboiler	0.04	--	0.040	CEMS
114	Desalter Heater	0.040	0.040	--	stack test
115	12-H-01A/B	0.06	0.060	--	stack test
116	HDS Heavy Oil Preheater	0.12	--	--	
117	Alky Fract Reboiler	0.036	--	0.036	CEMS
118	13-H-01A/B/C	0.06	--	0.060	CEMS
119	Sulften Heater	0.12	--	--	
120	Butamer Heater	0.12	--	--	

EPN	Facility	NO _x 1-hr block average (lb/MMBtu)	NO _x 3-hr block average (lb/MMBtu)	NO _x daily 365 rolling average (lb/MMBtu)	NO _x Compliance Method
195	GD Charge Heater	0.035	--	0.035	CEMS
30-B-04	Boiler 30-B-04	0.015	--	0.015	CEMS
30-B-05	Boiler 30-B-05	0.015	--	0.015	CEMS

EPN	Facility	CO 1-hr block average
162	38-H-01/02/03	0.05 lb/MMBtu
1	Crude Heater	0.05 lb/MMBtu
74	Vacuum Unit Heater	0.05 lb/MMBtu
150	47-H-01/02/03/04	0.03 lb/MMBtu
152	49-H-01/02/03/04	0.03 lb/MMBtu
153	Boiler 30-B-02	--
172	RSU Heater	0.05 lb/MMBtu
49-H-90	C7 Splitter Reboiler	0.05 lb/MMBtu
114	Desalter Heater	0.037 lb/MMBtu
115	12-H-01A/B	0.05 lb/MMBtu
116	HDS Heavy Oil Preheater	0.016 lb/MMBtu
117	Alky Fract Reboiler	0.016 lb/MMBtu
118	13-H-01A/B/C	0.05 lb/MMBtu
119	Sulften Heater	0.016 lb/MMBtu
120	Butamer Heater	0.016 lb/MMBtu
195	GD Charge Heater	100 ppmv (3% O ₂)
30-B-04	Boiler 30-B-04	50 ppmv (3% O ₂)
30-B-05	Boiler 30-B-05	50 ppmv (3% O ₂)

EPN	Facility	VOC lb/MMBtu	PM/PM ₁₀ /PM _{2.5} lb/MMBtu
30-B-04	Boiler 30-B-04	0.0053	0.0075
119	Sulften Heater	0.0053	0.0075
30-B-05	Boiler 30-B-05	0.0053	0.0075

EPN	Facility	H ₂ S in fuel gas lb/MMBtu	NH ₃ lb/MMBtu
30-B-04	Boiler 30-B-04	87 ppmv	10 ppmv
119	Sulften Heater	87 ppmv	10 ppmv
30-B-05	Boiler 30-B-05	87 ppmv	10 ppmv

During reduced-load operations for heaters or boilers equipped with CO CEMS, the emission limitations in the above table for CO shall not apply. Reduced-load operation means the operation of a heater or boiler at a firing rate of no greater than 50% of the maximum rated heat duty of the heater or boiler and not during planned MSS. The time and duration of each of each heater or boiler non-routine operation shall be recorded. Additionally, during each non-routine operation the rates of CO shall be calculated from a boiler or heater's CEMS data to demonstrate that MAERT emission limits are not exceeded. Records shall be maintained at the plant site for a period of five years. **(04/22)**

17. Heaters and boilers are prohibited from burning or combusting fuel oil. For purposes of this paragraph, fuel oil is predominately in the liquid phase at the point of combustion with a sulfur content of greater than 0.05% by weight. **(08/16)**
18. Upon request by the Executive Director of the TCEQ, the EPA, or any local air pollution control program having jurisdiction, the holder of this permit shall provide a sample and/or an analysis of the fuel(s) utilized in these facilities or shall allow air pollution control agency representatives to obtain a sample for analysis.
19. The Desalter Heater (EPN 114) shall comply with the following: **(04/22)**
 - A. The desalter heater shall only be fired with natural gas and fuel gas and the firing rate shall not exceed 99 MMBtu/hr on an annual basis (12-month rolling period) and short-term basis.
 - B. The natural gas and fuel gas shall be sampled every 6 months to determine the net heating value. Test results from the fuel supplier may be used to satisfy this requirement.
 - C. The permit holder shall install and operate a fuel flow meter to measure the gas fuel usage for the desalter heater. The monitored data shall be reduced to an hourly average flow rate at least once every day, using a minimum of four equally-spaced data points from each one-hour period. The monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications or at least annually, whichever is more frequent, and shall be accurate to within 5 percent.
 - D. Quality assured (or valid) data must be generated when the desalter heater is operating. Loss of valid data due to periods of monitor break down, out-of-control operation (producing inaccurate data), repair, maintenance, or calibration may be exempted provided it does not exceed 5 percent of the time (in minutes) that the desalter heater operated over the previous rolling 12 month period. The measurements missed shall be estimated using engineering judgment and the methods used recorded.

Sulfur Recovery Units (SRUs) and HOC Scrubber

20. The coke burn-off non-sulfate particulate matter (PM) emissions may not exceed 0.57 pound per 1,000 pounds of coke burn-off. The HOC scrubber sulfuric acid mist (a subset of total PM) emissions shall not exceed 0.35 pound per 1,000 pounds of coke burn-off.

Total particulate emissions from the HOC shall not exceed one (1) pound per 1,000 pounds of coke burned, measured as a one-hour average over three performance test runs.

The coke burn-off rate shall be calculated using Equation 6 from 40 CFR § 60.104a(d)(4)(iii).

21. The pH of the HOC scrubber circulating caustic solution shall be continually monitored and be maintained at a level between 6.0 and 9.0 by the addition of fresh caustic solution as required. The pH shall be recorded at least hourly, and the records maintained at the plant site for a period of five years. These records shall be made available for inspection by the Executive Director of the TCEQ or his designated representative.
22. The minimum sulfur recovery efficiency for the SRU/Sulften and SRU/Scot shall be 99.8 percent. The sulfur recovery efficiency shall be determined by calculation as follows: **(01/21)**

$$\text{Efficiency} = (\text{S recovered}) * (100) / (\text{S acid gas})$$

Where:

Efficiency = sulfur recovery efficiency, percent

S recovered = (S acid gas - S stack), pounds per hour (lb/hr)

S acid gas = sulfur in acid gas stream, lb/hr

S stack = sulfur in incinerator stack, lb/hr

The sulfur recovery efficiency shall be demonstrated for each calendar day (24-hour period) by a mass balance calculation using data obtained from the incinerator stack sulfur dioxide monitor and sulfur production records. Records and copies of the compliance calculations shall be maintained.

23. Acid gas must be routed to a properly operating SRU train. All SRU trains shall normally be operated when acid gas is being produced to maintain the maximum redundant sulfur capacity. The TCEQ Regional Office shall be notified within 72 hours if any SRU train is not fully operational. The notification shall include a description of the problem, the estimated loss of capacity, actions required to correct the problem, and when the line is expected to be fully operational.

In the event that the Sulften/Scot unit is not operating properly, immediate steps shall be taken to correct the improper operation and shift the acid gas feeds to another fully operational SRU.

24. The Scot tail gas incinerator shall be operated with no less than 3.0 percent oxygen (O₂) in the incinerator stack and at no less than 1500°F incinerator firebox exit temperature. The incinerator shall achieve a minimum H₂S destruction efficiency of 99.9 percent or 5 parts per million by volume (ppmv) (corrected to 3 percent excess O₂) reduced sulfur compound exit concentration. If stack testing indicates that a higher temperature or O₂ concentration is necessary to obtain a minimum H₂S destruction efficiency of 99.9 percent or 5 ppmv (corrected to 3 percent excess O₂) reduced sulfur compound exit concentration, then the temperature and O₂ maintained during the stack test

will become the new minimum operating limits. The O₂ and temperature requirements do not apply when performing a stack test on the incinerator in accordance with SC No. 39. The permit holder may request that the operating limits be relaxed with a permit alteration request should stack testing indicate the required emissions control is obtained at the proposed limits.

25. In order to control opacity from the stack of EPN 121, the permittee shall maintain the liquid to the filtering modules at a pressure greater than 45 pounds per square inch (psi) and the flue gas pressure drop across the filtering modules and the cyclolabs at no less than 5 inches of water. Liquid pressure and pressure drop shall be continuously recorded and maintained at the plant site for a period of five years. These records shall be made available for inspection by the Executive Director of the TCEQ or his designated representative.

The opacity of emissions from the Caustic Scrubber Stack (EPN 121) shall not exceed 20 percent averaged over a six-minute period as determined by a trained observer. Visual emissions observations shall be made quarterly using Method 22. If visual emissions are observed, the permit holder shall measure the visual emissions using Method 9.

Control Requirements

26. The Oleflex and Naphtha Continuous Catalyst Regenerator (CCR) scrubber liquids shall be sampled at least twice daily (once per shift) for caustic inventory. The pH of the scrubbing liquids in the Oleflex CCR caustic scrubber shall be maintained at 8 pH units or greater. The caustic concentration of the Naphtha Reformer CCR shall be maintained greater than 0.41 weight percent sodium hydroxide (measured as total alkalinity). **(11/20)**
27. The caustic absorber circulation rate for the Naphtha CCR shall be a minimum of 368 gpm. The circulation rate shall be recorded at least hourly, and the records maintained at the plant site for a period of five years. These records shall be made available for inspection by the Executive Director of the TCEQ or his designated representative.
28. Storage tanks are subject to the following requirements. The control requirements specified in paragraphs A through D of this condition shall not apply (1) where the VOC has an aggregate partial pressure of less than 0.50 psia at the maximum feed temperature or 95°F, whichever is greater, or (2) to storage tanks smaller than 25,000 gallons.
 - A. An internal floating deck or roof or equivalent control shall be installed in all tanks. The floating roof shall be equipped with one of the following closure devices between the wall of the storage vessel and the edge of the internal floating roof: (1) a liquid-mounted seal, (2) two continuous seals mounted one above the other, or (3) a mechanical shoe seal.
 - B. An open-top tank containing a floating roof (external floating roof tank) which uses double seal or secondary seal technology shall be an approved control alternative to an internal floating roof tank provided the primary seal consists of either a mechanical shoe seal or a liquid-mounted seal and the secondary seal is rim-mounted. A weathershield is not approvable as a secondary seal unless specifically reviewed and determined to be vapor-tight.
 - C. For any tank equipped with a floating roof, the permit holder shall perform the visual inspections and seal gap measurements as specified in 40 CFR § 60.113b, Testing and Procedures (as amended at 54 FR 32973, Aug. 11, 1989), to verify fitting and seal integrity. Records shall be maintained of the dates seals were inspected and seal gap measurements

made, results of inspections and measurements made (including raw data), and actions taken to correct any deficiencies noted.

- D. The floating roof design shall incorporate sufficient flotation to conform to the requirements of API Code 650 dated November 1, 1998, except that an internal floating cover need not be designed to meet rainfall support requirements and the materials of construction may be steel or other materials.
- E. Uninsulated tank exterior surfaces exposed to the sun shall be white or aluminum. Storage tanks must be equipped with permanent submerged fill pipes.
- F. The permit holder shall maintain an emissions record which includes calculated emissions of VOC from all storage tanks during the previous calendar month and the past consecutive 12-month period. The record shall include tank identification number, control method used, tank capacity in barrels, name of the material stored, VOC molecular weight, VOC monthly average temperature in degrees Fahrenheit, VOC vapor pressure at the monthly average material temperature in psia, VOC throughput for the previous month and year-to-date. Records of VOC monthly average temperature are not required to be kept for unheated tanks which receive liquids that are at or below ambient temperatures.

Emissions for tanks shall be calculated using the TCEQ publication titled "Technical Guidance Package for Chemical Sources - Storage Tanks."

- G. Floating roof tanks 23, 26, and 164 shall be equipped with a Pole Sleeve System or equivalent as required by the Storage Tank Emission Reduction Partnership Program (STERPP) Agreement with U.S. EPA, dated May 23, 2001, as listed in Appendix I and Annex A of that agreement. Storage Tank 164 was owned by the Valero Bill Greehey Refinery – West Plant at the time of STERPP Agreement execution and is currently owned by NuStar Energy LP (a non-affiliated company).
29. Non-fugitive emissions from relief valves, safety valves, or rupture discs of gases containing VOC at a concentration of greater than 1 percent are not authorized by this permit unless authorized on the maximum allowable rates table. Any releases directly to atmosphere from relief valves, safety valves, or rupture discs of gases containing VOC at a concentration greater than 1 weight percent are not consistent with good practice for minimizing emissions.
30. All cooling towers except for the Propylene cooling tower (EPN HOC-PP-CT) shall comply with the requirements of paragraphs A-D, and the Propylene cooling tower (EPN HOC-PP-CT) shall comply with the requirements of paragraph E:
- A. The cooling tower water shall be monitored monthly for VOC leakage from heat exchangers in accordance with the requirements of the TCEQ Sampling Procedures Manual, Appendix P (dated January 2003 or a later edition) or another air stripping method approved by the TCEQ Executive Director.
 - B. Cooling water VOC concentrations above 0.08 ppmw indicate faulty equipment. Equipment shall be maintained so as to minimize VOC emissions into the cooling water. Faulty equipment shall be repaired at the earliest opportunity but no later than the next scheduled shutdown of the process unit in which the leak occurs.
 - C. Emissions from the cooling tower are not authorized if the VOC concentration of the water returning to the cooling tower exceeds 0.80 ppmw. The VOC concentrations above 0.80 ppmw are not subject to extensions for delay of repair under this permit condition. The results of the monitoring and maintenance efforts shall be recorded.

- D. Cooling water shall be sampled once a week for total dissolved solids (TDS) and once a day for conductivity. Dissolved solids in the cooling water drift are considered to be emitted as total particulate matter (PM) / PM equal to or less than 10 microns in diameter (PM₁₀) / PM equal to or less than 2.5 microns in diameter (PM_{2.5}). The data shall result from collection of water samples from the cooling tower feed water and represent the water being cooled in the tower. Water samples should be capped upon collection, and transferred to a laboratory area for analysis. The analysis method for TDS shall be EPA Method 160.1, ASTM D5907, and SM 2540 C [SM - 19th edition of Standard Methods for Examination of Water]. The analysis method for Conductivity shall be ASTM D1125-95A and SM2510 B. Use of an alternative method shall be approved by the TCEQ Regional Director prior to its implementation.
- E. The Propylene cooling tower (EPN HOC-PP-CT) shall be operated and monitored in accordance with the following:
- (1) The VOC associated with the Propylene cooling tower (EPN HOC-PP-CT) water shall be monitored monthly with an air stripping system meeting the requirements of the TCEQ Sampling Procedures Manual, Appendix P (dated January 2003 or a later edition) or an approved equivalent sampling method. The results of the monitoring, cooling water flow rate and maintenance activities on the cooling water system shall be recorded. The monitoring results and cooling water hourly mass flow rate shall be used to determine cooling tower hourly VOC emissions. The rolling 12 month cooling water emission rate shall be recorded on a monthly basis and be determined by summing the VOC emissions between VOC monitoring periods over the rolling 12 month period. The emissions between VOC monitoring periods shall be obtained by multiplying the total cooling water mass flow between cooling water monitoring periods by the higher of the two VOC monitored results.
 - (2) Each cooling tower shall be equipped with drift eliminators having manufacturer's design assurance of 0.001% drift or less. Drifts eliminators shall be maintained and inspected at least annually. The permit holder shall maintain records of all inspections and repairs.
 - (3) Total dissolved solids (TDS) shall not exceed 6,000 parts per million by weight (ppmw). Dissolved solids in the cooling water drift are considered to be emitted as PM, PM₁₀, and PM_{2.5} as represented in the permit application calculations.
 - (4) Cooling water shall be sampled at least once per week for TDS.
 - (5) Cooling water sampling shall be representative of the cooling tower feed water and shall be conducted using approved methods.
 - (a) The analysis method for TDS shall be EPA Method 160.1, ASTM D5907, and SM 2540 C [SM - 19th edition of Standard Methods for Examination of Water]. Water samples should be capped upon collection, and transferred to a laboratory area for analysis.
 - (b) Alternate sampling and analysis methods may be used to comply with (5)(a) with written approval from the TCEQ Regional Director. If approved by the TCEQ Regional Director, the permit holder shall submit a permit application to incorporate the alternative sampling and analysis method into the permit within 2 months of the date of written approval.
 - (c) Records of all instrument calibrations and test results and process measurements used for the emission calculations shall be retained.

- (6) Emission rates of PM, PM₁₀ and PM_{2.5} shall be calculated using the measured TDS, the design drift rate and the daily maximum and average actual cooling water circulation rate for the short term and annual average rates. Alternately, the design maximum circulation rate may be used for all calculations. Emission records shall be updated monthly.

Fugitive Emissions Control

31. Piping, Valves, Flanges, Pumps, and Compressors in VOC Service - Intensive Directed Maintenance - 28 VHP

Except as may be provided for in the special conditions of this permit, the following requirements apply to the above-referenced equipment.

- A. These conditions shall not apply (1) where the VOC has an aggregate partial pressure or vapor pressure of less than 0.044 psia at 68°F or (2) the operating pressure is at least 5 kilopascals (0.725 psi) below ambient pressure. Equipment excluded from this condition shall be identified in a list or by one of the methods described below to be made readily available upon request.

The exempted components may be identified by one or more of the following methods:

- (1) piping and instrumentation diagram (PID);
 - (2) a written or electronic database or electronic file;
 - (3) color coding;
 - (4) a form of weatherproof identification; or
 - (5) designation of exempted process unit boundaries.
- B. Construction of new and reworked piping, valves, pump systems, and compressor systems shall conform to applicable American National Standards Institute (ANSI), API, American Society of Mechanical Engineers (ASME), or equivalent codes.
 - C. New and reworked underground process pipelines shall contain no buried valves such that fugitive emission monitoring is rendered impractical. New and reworked buried connectors shall be welded.
 - D. To the extent that good engineering practice will permit, new and reworked valves and piping connections shall be so located to be reasonably accessible for leak-checking during plant operation. Difficult-to-monitor and unsafe-to-monitor valves, as defined by Title 30 Texas Administrative Code Chapter 115 (30 TAC Chapter 115), shall be identified in a list to be made readily available upon request. The difficult-to-monitor and unsafe-to-monitor valves may be identified by one or more of the methods described in subparagraph A above. If an unsafe-to-monitor component is not considered safe to monitor within a calendar year, then it shall be monitored as soon as possible during safe-to-monitor times. A difficult-to-monitor component for which quarterly monitoring is specified may instead be monitored annually.
 - E. New and reworked piping connections shall be welded or flanged. Screwed connections are permissible only on piping smaller than two-inch diameter. Gas or hydraulic testing of the new and reworked piping connections at no less than operating pressure shall be performed prior to returning the components to service or they shall be monitored for leaks using an approved gas analyzer within 15 days of the components being returned to service. Adjustments shall be made as necessary to obtain leak-free performance. Connectors shall

be inspected by visual, audible, and/or olfactory means at least weekly by operating personnel walk-through.

Each open-ended valve or line shall be equipped with an appropriately sized cap, blind flange, plug, or a second valve to seal the line. Except during sampling, both valves shall be closed. If the removal of a component for repair or replacement results in an open ended line or valve, it is exempt from the requirement to install a cap, blind flange, plug, or second valve for 72 hours. If the repair or replacement is not completed within 72 hours, the permit holder must complete either of the following actions within that time period: the line or valve must have a cap, blind flange, plug, or second valve installed; or the permit holder shall verify that there is no leakage from the open-ended line or valve. The open-ended line or valve shall be monitored on a weekly basis in accordance with the applicable permit condition for fugitive emission monitoring, except that a leak is defined as any VOC reading greater than background. Leaks must be repaired within 24 hours or a cap, blind flange, plug, or second valve must be installed on the line or valve. The results of this weekly check and any corrective actions taken shall be recorded.

- F. Accessible valves shall be monitored by leak-checking for fugitive emissions at least quarterly using an approved gas analyzer. Sealless/leakless valves (including, but not limited to, welded bonnet bellows and diaphragm valves) and relief valves equipped with a rupture disc upstream or venting to a control device are not required to be monitored. For valves equipped with rupture discs, a pressure-sensing device shall be installed between the relief valve and rupture disc to monitor disc integrity. All leaking discs shall be replaced at the earliest opportunity but no later than the next process shutdown.

A check of the reading of the pressure-sensing device to verify disc integrity shall be performed weekly and recorded in the unit log or equivalent. Pressure-sensing devices that are continuously monitored with alarms are exempt from recordkeeping requirements specified in this paragraph.

The gas analyzer shall conform to requirements listed in Method 21 of 40 CFR part 60, appendix A. The gas analyzer shall be calibrated with methane. In addition, the response factor of the instrument for a specific VOC of interest shall be determined and meet the requirements of Section 8 of Method 21. If a mixture of VOCs are being monitored, the response factor shall be calculated for the average composition of the process fluid. A calculated average is not required when all of the compounds in the mixture have a response factor less than 10 using methane. If a response factor less than 10 cannot be achieved using methane, then the instrument may be calibrated with one of the VOC to be measured or any other VOC so long as the instrument has a response factor of less than 10 for each of the VOC to be measured.

Replaced components shall be re-monitored within 15 days of being placed back into VOC service.

- G. Except as may be provided for in the special conditions of this permit, all pump and compressor seals shall be monitored with an approved gas analyzer at least quarterly or be equipped with a shaft sealing system that prevents or detects emissions of VOC from the seal. Seal systems designed and operated to prevent emissions or seals equipped with an automatic seal failure detection and alarm system need not be monitored. These seal systems may include (but are not limited to) dual pump seals with barrier fluid at higher pressure than process pressure, seals degassing to vent control systems kept in good working order, or seals equipped with an automatic seal failure detection and alarm system. Submerged pumps or sealless pumps (including, but not limited to, diaphragm, canned, or

magnetic-driven pumps) may be used to satisfy the requirements of this condition and need not be monitored.

- H. Damaged or leaking valves or connectors found to be emitting VOC in excess of 500 ppmv or found by visual inspection to be leaking (e.g., dripping process fluids) shall be tagged and replaced or repaired. Damaged or leaking pump and compressor seals found to be emitting VOC in excess of 2,000 ppmv or found by visual inspection to be leaking (e.g., dripping process fluids) shall be tagged and replaced or repaired. A first attempt to repair the leak must be made within 5 days. Records of the first attempt to repair shall be maintained.
- I. Every reasonable effort shall be made to repair a leaking component, as specified in this paragraph, within 15 days after the leak is found. If the repair of a component would require a unit shutdown that would create more emissions than the repair would eliminate, the repair may be delayed until the next scheduled shutdown. All leaking components which cannot be repaired until a scheduled shutdown shall be identified for such repair by tagging within 15 days of the detection of the leak. A listing of all components that qualify for delay of repair shall be maintained on a delay of repair list. The cumulative daily emissions from all components on the delay of repair list shall be estimated by multiplying by 24 the mass emission rate for each component calculated in accordance with the instructions in 30 TAC 115.782 (c)(1)(B)(i)(II). The calculations of the cumulative daily emissions from all components on the delay of repair list shall be updated within ten days of when the latest leaking component is added to the delay of repair list. When the cumulative daily emission rate of all components on the delay of repair list times the number of days until the next scheduled unit shutdown is equal to or exceeds the total emissions from a unit shutdown as calculated in accordance with 30 TAC 115.782 (c)(1)(B)(i)(I), the TCEQ Regional Manager and any local programs shall be notified and may require early unit shutdown or other appropriate action based on the number and severity of tagged leaks awaiting shutdown. This notification shall be made within 15 days of making this determination.
- J. Records of repairs shall include date of repairs, repair results, justification for delay of repairs, and corrective actions taken for all components. Records of instrument monitoring shall indicate dates and times, test methods, and instrument readings. The instrument monitoring record shall include the time that monitoring took place for no less than 95% of the instrument readings recorded. Records of physical inspections shall be noted in the operator's log or equivalent.
- K. Alternative monitoring frequency schedules of 30 TAC §§ 115.352 through 115.359 or National Emission Standards for Organic Hazardous Air Pollutants, 40 CFR Part 63, Subpart H, may be used in lieu of Items F through G of this condition.

Compliance with the requirements of this condition does not assure compliance with requirements of 30 TAC Chapter 115, an applicable New Source Performance Standards (NSPS), or an applicable National Emission Standard for Hazardous Air Pollutants (NESHAPS) and does not constitute approval of alternative standards for these regulations.

- 32. Pump and compressor seals shall be monitored for fugitive leakage monthly rather than quarterly as specified by SC No. 31. The leak definitions, recordkeeping, and corrective actions of those conditions still apply to these components.
- 33. In addition to the weekly physical inspection required by Item E of SC No. 31, all accessible valve connectors in gas or vapor and light liquid service shall be monitored quarterly with an approved gas analyzer in accordance with Items F through J of SC No. 31.

In lieu of the monitoring frequency specified in the above paragraph, connectors may be monitored on a semiannual basis if the percent of connectors leaking for two consecutive quarterly monitoring periods is less than 0.5 percent.

Connectors may be monitored on an annual basis if the percent of connectors leaking for two consecutive semiannual monitoring periods is less than 0.5 percent.

If the percent of connectors leaking for any semiannual or annual monitoring period is 0.5 percent or greater, the facility shall revert to quarterly monitoring until the facility again qualifies for the alternative monitoring schedules previously outlined in the paragraph.

The percent of connectors leaking used in paragraph B shall be determined using the following formula:

$$(CI + Cs) \times 100/Ct = Cp$$

Where:

- CI = the number of connectors found leaking by the end of the monitoring period, either by Method 21 or sight, sound, and smell.
- Cs = the number of connectors for which repair has been delayed and are listed on the facility shutdown log.
- Ct = the total number of connectors in the facility subject to the monitoring requirements, as of the last day of the monitoring period, not including nonaccessible and unsafe-to-monitor connectors.
- Cp = the percentage of leaking connectors for the monitoring period.

Process Piping, Valves, Pumps, and Compressors in H₂S and Hydrogen Fluoride (HF) Service.

34. This condition shall apply to all process streams with greater than 2 weight percent H₂S and all process streams with greater than 0.5 weight percent HF.
- A. Audio, olfactory, and visual checks for H₂S and HF leaks within the operating area shall be made once a shift. **(04/22)**
 - B. Immediately, but no later than one hour upon detection of a leak, plant personnel shall take the following actions:
 - (1) Isolate the leak.
 - (2) Commence repair or replacement of the leaking component.
 - (3) If immediate repair is not possible, a leak collection or containment system will be used to prevent or minimize the leak or the facility shall be shutdown in an orderly manner until repair or replacement can be made. Containment can include adjustment of bolts, fittings, packing glands, and pump or compressor seals to contain the leak.
- Records shall be maintained of all inspections, leaks noted, repairs, and replacements made. These records shall be maintained at the plant site for a period of five years and shall be made immediately available at the request of TCEQ personnel.

Wastewater Collection and Treatment

35. The wastewater collection and treatment system shall comply with the requirements of this permit and with the requirements for wastewater systems in 40 CFR Part 60, Subparts A and QQQ, except as described in the following sentence. Components for which construction, modification, or reconstruction has not commenced after May 4, 1987, in the process units that follow, shall comply with the requirements of this permit and with the requirements of applicable State regulations, but are exempt from 40 CFR Part 60, Subparts A and QQQ.

Process Unit	
Heavy Oil Cracker	Vacuum Unit
HDS Unit	HF Alky Unit
SMR Unit	Boilerhouse
Crude Unit	SWS/Amine
SRU/Sulften	Tank Farm

36. The wastewater collection systems which are routed to a control device shall comply with the following requirements:
- A. Process wastewater drains shall be equipped with water seals or equivalent. Lift stations (with the exception of the HOC Gas Plant lift station), manholes, junction boxes, any other wastewater collection system components, conveyance, storage, and treatment system to the biological treatment unit shall be equipped with a closed vent system that routes all organic vapors to an API Separator Combustor or a back-up CAS. The HOC Gas Plant lift station shall be routed to the CAS (EPN CAS-HOCPP).
 - B. Water seals shall be checked by visual or physical inspection quarterly for indications of low water levels or other conditions that would reduce the effectiveness of water seal controls. Water seals shall be restored as necessary within 24 hours. Records shall be maintained of these inspections and of corrective actions taken.
 - C. The HOC Gas Plant lift station shall vent through a CAS (EPN CAS-HOCPP) consisting of at least two activated carbon canisters that are connected in series.
 - (1) The CAS shall be sampled every two weeks or at 30 percent of the minimum potential saturation time, whichever is soonest, to determine breakthrough of volatile organic compounds (VOC). The sampling point shall be at the outlet of the initial canister but before the inlet to the second or final polishing canister. Sampling shall be done during routine operation of the lift station when wastewater is being generated by process units.
 - (2) The VOC sampling and analysis shall be performed using an instrument with a flame ionization detector (FID), or a TCEQ-approved alternative detector. The instrument/FID must meet all requirements specified in Section 8.1 of EPA Method 21 (40 CFR 60, Appendix A). Sampling and analysis for VOC breakthrough shall be performed as follows:
 - (a) Immediately prior to performing sampling, the instrument/FID shall be calibrated with zero and span calibration gas mixtures. Zero gas shall be certified to

contain less than 0.1 ppmv total hydrocarbons. Span calibration gas shall be methane at a concentration within ± 10 percent of 5 ppmv, and certified by the manufacturer to be ± 2 percent accurate. Calibration error for the zero and span calibration gas checks must be less than ± 5 percent of the span calibration gas value before sampling may be conducted.

- (b) The sampling point shall be at the outlet of the initial canister but before the inlet to the second or final polishing canister. Sample ports or connections must be designed such that air leakage into the sample port does not occur during sampling.
 - (c) During sampling, data recording shall not begin until after two times the instrument response time. The VOC concentration shall be monitored for at least 5 minutes, recording 1-minute averages, during the maximum flow rate from the lift station.
 - (3) Breakthrough shall be defined as the highest 1 minute average measured VOC concentration at or exceeding 100 ppmv or benzene concentration at or exceeding 5 ppmv. When the condition of breakthrough of VOC from the initial saturation canister occurs, the waste gas flow shall be switched to the second canister and a fresh canister shall be placed as the new final polishing canister within 24 hours. Sufficient new activated carbon canisters shall be maintained at the site to replace spent carbon canisters such that replacements can be done in the above specified time frame.
 - (4) Records of the CAS monitoring maintained at the plant site, shall include (but are not limited to) the following:
 - (a) Sample time and date.
 - (b) Monitoring results (ppmv).
 - (c) Corrective action taken including the time and date of that action.
 - (d) Process operations occurring at the time of sampling.
 - (5) Alternate monitoring or sampling requirements that are equivalent or better may be approved by the TCEQ Regional Manager. Alternate requirements must be approved in writing before they can be used for compliance purposes.
37. The daily wastewater flow into the wastewater treatment plant shall be monitored and recorded. The rolling 12-month wastewater flow shall be totaled on a monthly basis.
38. The minimum mixed liquor total suspended solids (MLSS) concentration in the aeration basins on a daily average basis shall not be less than 2000 mg/L. The MLSS concentration is the arithmetic average of all samples collected during the 24-hour period. The MLSS concentrations shall be monitored and recorded daily using Method 160.2 (Methods for Chemical Analysis of Water and Wastes, EPA-600/4-79-020 or Method 2540D (Standard Methods of the Examination of Water and Wastewater, 18th Edition, American Public Health Association).

Compliance Testing

39. The permit holder shall perform stack sampling and other testing as required to establish the actual pattern and quantities of air contaminants being emitted into the atmosphere from all heaters and boilers with firing rates greater than 40 MMBtu/hr, Scot Tail Gas Incinerator (EPN 121 or 121a),

Sulften Tail Gas Incinerator (EPN 121 or 121a), Caustic Scrubber (EPN 121), Marine Loading VRU (EPN VRU), and Vapor Combustors (EPNs TRUCKCOMB and 124), to demonstrate compliance with the maximum allowable emissions rate table (MAERT). Sampling shall be performed upstream and downstream of the SMR condensate stripper vent condenser to demonstrate compliance with SC No. 46. The permit holder is responsible for providing sampling and testing facilities and conducting the sampling and testing operations at his expense. Sampling shall be conducted in accordance with the appropriate procedures of the TCEQ Sampling Procedures Manual and the U.S. Environmental Protection Agency (EPA) Reference Methods.

Requests to waive testing for any pollutant specified in this condition shall be submitted to the TCEQ Office of Air, Air Permits Division. Test waivers and alternate/equivalent procedure proposals for 40 CFR Part 60 testing which must have EPA approval shall be submitted to the TCEQ Regional Director.

- A. The appropriate TCEQ Regional Office shall be notified not less than 30 days prior to sampling.

The notice shall include:

- (1) Proposed date for pretest meeting.
- (2) Date sampling will occur.
- (3) Name of firm conducting sampling.
- (4) Type of sampling equipment to be used.
- (5) Method or procedure to be used in sampling.
- (6) Description of any proposed deviation from the sampling procedures specified in this permit or TCEQ/EPA sampling procedures.
- (7) Procedure/parameters to be used to determine worst case emissions, such as production rate, to set operating parameters and limits to be monitored during the sampling period.

The purpose of the pretest meeting is to review the necessary sampling and testing procedures, to provide the proper data forms for recording pertinent data, and to review the format procedures for the test reports.

- B. Air contaminants to be tested from sources:

- (1) Air contaminants emitted from the heaters and boilers to be tested for include (but are not limited to) NO_x and CO.
- (2) Air contaminants emitted from the caustic scrubber to be tested for include (but are not limited to) sulfur dioxide (SO₂), NO_x, PM (both front and back-half of the sampling train), sulfuric acid, and CO. Stack testing of the Belco Scrubber (EPN 121) shall be accomplished by temporarily routing the Sulften and Scot Tail gas to EPN 121a.
- (3) Air contaminants emitted from the Sulften and Scot tail gas incinerators to be tested for include (but are not limited to) SO₂, NO_x, CO, PM (both front and back half of the sampling train), and total reduced sulfur.
- (4) Air contaminants emitted from the vapor combustors to be tested for include (but are not limited to) VOC, NO_x, and CO.

- (5) Air contaminants to be tested for the SMR condensate stripper vent condenser include methanol.
- C. Requests for additional time to perform sampling shall be submitted to the TCEQ Corpus Christi Regional Office. Additional time to comply with the applicable requirements of 40 CFR Part 60 and 40 CFR Part 61 requires the EPA approval. Sampling of air contaminants shall occur as follows:
 - (1) Air contaminants monitored with a CEMS as specified under SC No. 40 shall be sampled to support CEMS operation as required by that condition.
 - (2) Sampling of air contaminants not monitored by CEMS under SC No. 40 shall occur as follows:
 - (a) Within 180 days of the issuance of this permit unless the emission point had been sampled within the last 5 years.
 - (b) Each emission point shall be sampled within 60 days of achieving maximum operation, not to exceed 180 days after initial operation, if new burners have been installed or if an operational change has been made allowing emissions to increase more than 10 percent greater than determined by the last stack sample.
 - (c) Each emission point shall be sampled as may be required by the Executive Director of the TCEQ.
- D. The facility shall operate at maximum production rates during stack emission testing. Primary operating parameters that enable determination of production rates shall be monitored and recorded during the stack test. Any additional parameters shall be determined at the pretest meeting and shall be stated in the sampling report. Permit conditions and parameter limits may be waived during stack testing performed under this condition if the proposed condition/parameter range is identified in the test notice specified in paragraph A and accepted by the TCEQ Regional Office. Permit allowable emissions and emission control requirements are not waived and still apply during stack testing periods.

During subsequent operations, if an operating parameter as determined in the previous paragraph is greater than that recorded during the test period, stack sampling shall be performed at the new operating conditions within 120 days. This sampling may be waived by the TCEQ Air Section Manager for the Region.
- E. One copy of the final sampling report shall be forwarded to the TCEQ within 60 days after sampling is completed. Sampling reports shall comply with the attached conditions of Chapter 14 of the TCEQ Sampling Procedures Manual. The reports shall be distributed as follows:

One copy to the TCEQ Corpus Christi Regional Office.

Continuous Determination of Compliance

- 40. The holder of this permit shall install, calibrate, and maintain a CEMS to measure and record the in-stack concentration of VOC from the marine VRU; CO, NO_x, and O₂ from the heaters and boilers with firing rates greater than 100 MMBtu/hr; SO₂ and O₂ from the SRU/Sulften Tail Gas Incinerator (exhausts to EPN 121 or 121a); SO₂ and O₂ from the SRU/Scot Tail Gas Incinerator (exhausts to EPN 121 or 121a), and NO_x, CO, O₂, and SO₂ from the Caustic Scrubber (exhausts to EPN 121). The monitoring system shall meet the following section of Requirements for CEMS. **(02/18)**

Requirements for CEMS

- A. The CEMS shall meet the design and performance specifications, pass the field tests, and meet the installation requirements and the data analysis and reporting requirements specified in the applicable Performance Specification Nos. 1 through 7, 40 CFR Part 60, Appendix B. If there are no applicable performance specifications in 40 CFR Part 60, Appendix B, contact the TCEQ Office of Air, Air Permits Division for requirements to be met.
- B. Section 1 below applies to sources subject to the quality-assurance requirements of 40 CFR Part 60, Appendix F; section 2 applies to all other sources:
- (1) The permit holder shall assure that the CEMS meets the applicable quality-assurance requirements specified in 40 CFR Part 60, Appendix F, Procedure 1. Relative accuracy exceedances, as specified in 40 CFR Part 60, Appendix F, § 5.2.3 and any CEMS downtime shall be reported to the appropriate TCEQ Regional Manager, and necessary corrective action shall be taken. Supplemental stack concentration measurements may be required at the discretion of the appropriate TCEQ Regional Manager.
 - (2) The system shall be zeroed and spanned daily, and corrective action taken when the 24-hour span drift exceeds two times the amounts specified in the applicable Performance Specification Nos. 1 through 9, 40 CFR Part 60, Appendix B, or as specified by the TCEQ if not specified in Appendix B. Zero and span is not required on weekends and plant holidays if instrument technicians are not normally scheduled on those days, unless the monitor is required by a subpart of NSPS or NESHAPS, in which case zero and span shall be done daily without exception.
- Each monitor shall be quality-assured at least quarterly using Cylinder Gas Audits (CGA) in accordance with 40 CFR Part 60, Appendix F, Procedure 1, Section 5.1.2, with the following exception: a relative accuracy test audit (RATA) is not required once every four quarters (i.e., four successive quarterly CGA may be conducted). An equivalent quality-assurance method approved by the TCEQ may also be used. Successive quarterly audits shall occur no closer than two months.
- All CGA exceedances of +15 percent accuracy indicate that the CEMS is out of control.
- C. The monitoring data shall be reduced to hourly average concentrations at least once weekly, using a minimum of four equally-spaced data points from each one-hour period. The individual average concentrations shall be reduced to units of the permit allowable emission rate in pounds/hr at least once every week and cumulative tons per year (TPY) on a 12-month rolling average at least once every month.
- D. All monitoring data and quality-assurance data shall be maintained by the source for a period of five years and shall be made available to the TCEQ Executive Director or his designated representative upon request. The data from the CEMS may, at the discretion of the TCEQ, be used to determine compliance with the conditions of this permit.
- E. All cylinder gas audit exceedances of ± 15 percent accuracy and any CEMS downtime associated with emissions from EPNs 121 and 121a shall be reported to the appropriate TCEQ Regional Director within three days of any downtime, and necessary corrective action shall be taken. If the CEMS downtime for a specific emission point occurs when emissions are not being routed to that stack, that time period shall not be considered reportable CEMS downtime for the purposes of this special condition. Exceedances at other emission points shall be reported in Semiannual Excess Emission Reports. Supplemental stack

concentration measurements may be required at the discretion of the appropriate TCEQ Regional Director.

- F. The appropriate TCEQ Regional Office shall be notified at least 30 days prior to any required RATA in order to provide them the opportunity to observe the testing.
 - G. Quality-assured (or valid) data must be generated when each emitting facility is operating, except during the performance of a daily zero and span check. Loss of valid data due to periods of monitor break down, out-of-control operation (producing inaccurate data), repair, maintenance, or calibration may be exempted, provided that it does not exceed 5 percent of the time (in minutes) that the facility operated over the previous rolling 12-month period. The measurements missed shall be estimated using engineering judgment and the methods used recorded. Options to increase system reliability to an acceptable value, including a redundant CEMS, may be required by the TCEQ Regional Manager.
 - H. This paragraph applies to the NO_x, SO₂, and O₂ CEMS on the Caustic Scrubber (exhausts to EPN 121) and to the heaters and boilers in listed in SC No. 16 with NO_x CEMS. In addition to the requirements of SC No. 40.A-G., the CEMS shall be installed, certified, calibrated, maintained and operated in accordance with the provisions of 40 CFR §60.13 which are applicable only to CEMS (excluding those provisions applicable only to continuous opacity monitoring systems) and Part 60, Appendices A and F, and the applicable performance specification test of 40 CFR Part 60, Appendix B. With respect to 40 CFR Part 60 Appendix F, in lieu of the requirements of 40 CFR Part 60, Appendix F §§5.1.1, 5.1.3 and 5.1.4, the source must conduct either a RAA or a RATA on each CEMS at least once every three (3) years. The source must also conduct CGA each calendar quarter during which a RAA or a RATA is not performed. **(02/18)**
41. Pollutant concentrations at the outlet from the Caustic Scrubber (exhausts to EPN 121) shall not exceed the following values at dry conditions, zero percent O₂:

Pollutant	Maximum Allowable	Averaging Period
SO ₂	50 ppm	1.0 hour
SO ₂	50 ppm	7-day rolling average (04/16)
SO ₂	25 ppm	365-day rolling average (04/16)
CO	500 ppm	1.0 hour
NO _x	150 ppm	1.0 hour

Pollutant concentrations at the outlet from the SCOT Stack (EPN 121a) shall not exceed the following values at dry conditions, zero percent O₂:

Pollutant	Maximum Allowable	Averaging Period
SO ₂	250 ppm	1.0 hour
CO	332 ppm	1.0 hour
NO _x	50 ppm	1.0 hour

42. The continuous monitoring data will be used to determine violations of the limitations in this permit. For purposes of enforcement, the following averaging periods shall be utilized unless otherwise specified in this permit with respect to a specific emission point and pollutant:

Pollutant	Averaging Period
SO ₂	1.0 hour
CO	1.0 hour
H ₂ S	1.0 hour
Opacity	6.0 minutes
NO _x	1.0 hour

HF Control Measures

43. The HF detection paint shall be used on all potential fugitive sources and possible leak sites. Locations with HF detection paint shall be inspected every shift during the audio, visual, and olfactory checks required by SC No. 34. If leaks are detected, corrective action shall be taken immediately as described in SC No. 34. If there is a problem with HF sensitive paint availability, the holder of this permit shall notify the TCEQ Corpus Christi Regional Office and request additional time for painting or request alternate leak detection methods pending availability of the HF sensitive paint.
44. In the event of an HF release which may have the potential for off-site impacts, the holder of this permit shall implement the procedures outlined in the emergency response plans.
45. There shall be no overhead work in the HF process unit where equipment is being lifted over unprotected vessels or lines without first completing a safe work checklist in accordance with Occupational Safety and Health Administration Process Safety Management rules. The safe work checklist shall be used to ensure that every effort is made to minimize the potential for an accident that would result in loss of integrity of HF-containing equipment.

The holder of this permit is required to notify the TCEQ Corpus Christi Regional Office no less than eight hours prior to conducting work over unprotected vessels or lines containing more than 5 percent by weight HF.

Miscellaneous

46. The SMR stripper vent condenser shall collect 98 percent of the methanol in the stripper vent on an hourly averaging period. The stripper exhaust gas temperature shall be maintained below that maintained during the most recent stack sample following the initial stack test.

The condenser exhaust gas temperature shall be continuously monitored and recorded when the stripper is operating. The temperature measurement device shall reduce the temperature readings to an averaging period of six minutes or less and record it at that frequency. The temperature measurement device shall be installed, calibrated, and maintained according to accepted practice and the manufacturer's specifications. The device shall have an accuracy of the greater of ± 0.75 percent of the temperature being measured expressed in degrees Celsius or $\pm 2.5^{\circ}\text{C}$.

47. Flares: BUP Flare, Main Flare and Ground Flare shall be operated in accordance with the New Source Performance Standards for Petroleum Refineries, 40 CFR Part 60 Subpart Ja. **(04/16)**
48. After December 31, 2008 the maximum allowable emission limit of NO_x from the West Plant Heavy Oil Cracker (HOC) (EPN 121) shall not exceed 37 ppmv (dry, zero percent O₂ basis) on a 365-day rolling average and shall not exceed 74 ppmv (dry, zero percent O₂ basis) on a 7-day rolling average. **(04/16)**

Maintenance, Startup, and Shutdown

49. Planned startup and shutdown emissions due to the activities identified in SC No. 50 are authorized from facilities and emission points identified in Attachment 1, Boiler 30-B-03 (EPN: 163) in Permit 20740, the Xylene Splitter Reboiler Heater 49-H-91 (EPN: 49-H-91) in Permit 20992, emission points identified in SC No. 16 in Permit 106965, and emission points identified in SC No. 25 in Permit 109543, provided the facility and emissions are compliant with the routine emission caps and SC No. 60 of this permit. **(02/14)**
50. This permit authorizes the emissions for the planned MSS activities summarized in the MSS Activity Summary (Attachment 4) attached to this permit. This permit also authorizes emissions from the following temporary facilities used to support planned MSS activities at permanent site facilities: frac tanks, containers, vacuum trucks, facilities used for painting or abrasive blasting, portable control devices identified in SC No. 61, and controlled recovery systems. Emissions from temporary facilities are authorized provided the temporary facility (a) does not remain on the plant site for more than 12 consecutive months, (b) is used solely to support planned MSS activities at the permanent site facilities listed in Attachment 1, and (c) does not operate as a replacement for an existing authorized facility.

Attachment 2 identifies the inherently low emitting MSS activities that may be performed at the refinery. Emissions from activities identified in Attachment 2 shall be considered to be equal to the potential to emit represented in the permit application. The estimated emissions from the activities listed in Attachment 2 must be revalidated annually. This revalidation shall consist of the estimated emissions for each type of activity and the basis for that emission estimate.

Routine maintenance activities, as identified in Attachment 3 may be tracked through the work orders or equivalent. Emissions from activities identified in Attachment 3 shall be calculated using the number of work orders or equivalent that month and the emissions associated with that activity identified in the permit application.

The performance of each planned MSS activity not identified in Attachments 2 or 3 and the emissions associated with it shall be recorded and include at least the following information: **(04/22)**

- A. the process unit at which emissions from the MSS activity occurred, including the emission point number and common name of the process unit;
- B. the type of planned MSS activity and the reason for the planned activity;
- C. the common name or the facility identification number, if applicable, of the facilities at which the MSS activity and emissions occurred;
- D. the date and time on which the MSS activity occurred;

- E. the estimated quantity of each air contaminant, or mixture of air contaminants, emitted with the data and methods used to determine it. The emissions shall be estimated using the methods identified in the permit application, consistent with good engineering practice.

All MSS emissions shall be summed monthly and the rolling 12-month emissions shall be updated on a monthly basis. A sum of all hourly MSS emissions shall be kept during all times when MSS activities are occurring to demonstrate that the MAERT hourly MSS Cap is not exceeded.

- 51. Process units and facilities, with the exception of those identified in SC Nos. 54 (related to Floating Roof Tanks), 55 (related to Fixed Roof Tanks), 57 (related to frac or temporary tanks), and activities listed in Attachment 2, shall operate in accordance with the following requirements during MSS.

- A. The process equipment shall be depressurized to a control device or a controlled recovery system prior to venting to atmosphere, degassing, or draining liquid. Equipment that only contains material that is liquid with VOC true vapor pressure (TVP) less than 0.50 psi at the normal process temperature and 95°F may be opened to atmosphere and drained in accordance with paragraph C of this special condition without depressuring or degassing to a control device. The vapor pressure at 95°F may be used if the actual temperature of the liquid is verified to be less than 95°F and the temperature is recorded.
- B. If mixed phase materials must be removed from process equipment, the cleared material shall be routed to a knockout drum or equivalent to allow for managed initial phase separation. If the VOC TVP is greater than 0.50 psi at either the normal process temperature or 95°F, any vents in the system must be routed to a control device or a controlled recovery system. The vapor pressure at 95°F may be used if the actual temperature of the liquid is verified to be less than 95°F and the temperature is recorded. Control must remain in place until degassing has been completed or the system is no longer vented to atmosphere.
- C. All liquids from process equipment shall be removed to the maximum extent practical prior to opening equipment to commence degassing and/or maintenance. Liquids with a VOC partial pressure greater than or equal to 0.044 psia at 68°F shall be drained into a closed vessel or to a controlled oily water system, unless prevented by the physical configuration of the equipment. If it is necessary to drain liquid into an open pan or sump, the liquid shall be covered or transferred to a covered vessel within one hour of being drained. After draining is complete, empty open pans may remain in use for housekeeping reasons to collect incidental drips.
- D. If the VOC TVP is greater than 0.50 psi at the normal process temperature or 95°F, facilities shall be degassed using good engineering practice to ensure air contaminants are removed from the system through the control device or controlled recovery system to the extent allowed by process equipment or storage vessel design. The vapor pressure at 95°F may be used if the actual temperature of the liquid is verified to be less than 95°F and the temperature is recorded.

The following requirements do not apply to fugitive components, pumps, compressors.

- (1) For MSS activities identified in Attachment 3, the following option may be used in lieu of (2) below. The facilities being prepared for maintenance shall not be vented directly to atmosphere, except as necessary to verify an acceptable VOC concentration and establish isolation of the work area, until the VOC concentration has been verified to be less than 10 percent of the lower explosive limit (LEL) per the site safety procedures.

- (2) The locations and/or identifiers where the purge gas or steam enters the process equipment or storage vessel and the exit points for the exhaust gases shall be recorded (PFD's, P&ID's, or Turnaround and Inspection [T&I] plans may be used to demonstrate compliance with the requirement). Documented refinery procedures used to deinventory equipment to a control device for safety purposes (i.e., hot work or vessel entry procedures) that achieve at least the same level of purging may be used in lieu of the above. If the process equipment is purged with a gas, purge gas must have passed through the control device or controlled recovery system for a sufficient period of time in accordance with the applicable site operating procedures before the vent stream may be sampled to verify acceptable VOC concentration prior to uncontrolled venting. The VOC sampling and analysis shall be performed using an instrument meeting the requirements of SC No. 52. The sampling point shall be upstream of the inlet to the control device or controlled recovery system. The sample ports and the collection system must be designed and operated such that there is no air leakage into the sample probe or the collection system downstream of the process equipment or vessel being purged. The facilities shall be degassed to a control device or controlled recovery system until the VOC concentration is less than or equal to 10,000 ppmv or 10 percent of the LEL.
 - (3) Alternatively, the process equipment may filled with a liquid with a VOC vapor pressure less than 0.147 psi while venting to control. If it can be verified that the liquid filled the entire process equipment or vessel, no sampling is necessary. If not, the VOC concentration shall be verified to be less than 10,000 ppmv or 10 percent of the LEL using an instrument meeting the requirements of SC No. 52 while purging to control immediately after draining the liquid from the system. The locations and/or identifiers where the liquid enters the process equipment or storage vessel and the exit points for the exhaust gases shall be recorded (PFDs, P&IDs, or T&I plans may be used to demonstrate compliance with the requirement).
 - E. Equipment containing materials with VOC TVP greater than 0.50 psi may be vented directly to atmosphere if all the following criteria are met:
 - (1) It is not technically practicable to depressurize or degas, as applicable, into the process.
 - (2) There is not an available connection to a plant control system (flare).
 - (3) There is no more than 50 lb of air contaminants to be vented to atmosphere during each shutdown or startup of a piece of equipment, as applicable.

All instances of venting directly to atmosphere per SC No. 51.D must be documented when occurring as part of any MSS activity. The emissions associated with venting without control must be included in the work order, shift logs, or equivalent for those planned MSS activities identified in Attachment 3. **(02/18)**
52. Air contaminant concentration shall be measured using an instrument/detector meeting one set of requirements specified below.
 - A. The VOC concentration shall be measured using an instrument meeting all the requirements specified in EPA Method 21 (40 CFR Part 60, Appendix A) with the following exceptions:
 - (1) The instrument shall be calibrated within 24 hours of use with a calibration gas. The calibration gas used and its concentration, and the vapor to be sampled and its approximate response factor (RF), shall be recorded. If the RF of the VOC (or mixture

of VOCs) to be monitored is greater than 2.0, the VOC concentration shall be determined as follows:

VOC Concentration = Concentration as read from the instrument*RF

- (2) Sampling shall be performed as directed by this permit in lieu of section 8.3 of Method 21. During sampling, data recording shall not begin until after two times the instrument response time. The date and time shall be recorded, and VOC concentration shall be monitored for at least 5 minutes and the greatest VOC concentration recorded. This VOC concentration shall not exceed the specified VOC concentration limit prior to uncontrolled venting.
 - (3) If a TVA-1000 series FID analyzer calibrated with methane is used to determine the VOC concentration, a measured concentration of 34,000 ppmv may be considered equivalent to 10,000 ppmv as VOC.
- B. Colorimetric gas detector tubes may be used to determine air contaminant concentrations if they are used in accordance with the following requirements.
- (1) The air contaminant concentration measured is less than 80 percent of the range of the tube. If the maximum range of the tube is greater than the release concentration defined in (3), the concentration measured is at least 20 percent of the maximum range of the tube.
 - (2) The tube is used in accordance with the manufacturer's guidelines.
 - (3) At least 2 samples taken at least 5 minutes apart must satisfy the following prior to uncontrolled venting:
measured contaminant concentration (ppmv) < release concentration.
Where the release concentration is:
10,000*mole fraction of the total air contaminants present that can be detected by the tube.
The mole fraction may be estimated based on process knowledge. The release concentration and basis for its determination shall be recorded.
Records shall be maintained of the tube type, range, measured concentrations, and time the samples were taken.
- C. Lower explosive limit measured with a lower explosive limit detector.
- (1) The detector shall be calibrated monthly with a certified pentane gas standard at 25 percent of the lower explosive limit (LEL) for pentane. Records of the calibration date/time and calibration result (pass/fail) shall be maintained.
 - (2) A daily functionality test shall be performed on each detector using the same certified gas standard used for calibration. The LEL monitor shall read no lower than 90 percent of the calibration gas certified value. Records, including the date/time and test results, shall be maintained.
 - (3) A certified methane gas standard equivalent to 25 percent of the LEL for pentane may be used for calibration and functionality tests provided that the LEL response is within 95 percent of that for pentane.
- D. For measuring benzene breakthrough on Carbon Adsorption Systems in SC No. 61.A.(4), a portable gas chromatograph using a flame ionization detector or photo ionization detector

may be used. Alternatively a photo-ionization detector equipped with a benzene separation tube consistent with manufacturer requirements may be used. The monitor shall have the sensitivity and specificity to quantify low level benzene concentrations. The monitor device shall be calibrated within 24 hours of use with a certified calibration gas containing ~5 ppm benzene. Records of the calibration date/time and calibration result shall be maintained.

53. If the removal of a component for repair or replacement results in an open ended line or valve, the open ended line is exempt from any New Source Review (NSR) permit condition requirement to install a cap, blind flange, plug, or second valve for 72 hours. If the repair or replacement is not completed within 72 hours, the permit holder must complete either of the following actions within that time period;
- A. a cap, blind flange, plug, or second valve must be installed on the line or valve, or demonstrate that the line, valve, component, etc, has been double blocked from the process; or
 - B. the permit holder shall verify that there is no leakage from the open-ended line or valve. The open-ended line or valve shall be monitored on a weekly basis in accordance with the applicable NSR permit condition for fugitive emission monitoring except that a leak is defined as any VOC reading greater than background. Leaks must be repaired within 24 hours or a cap, blind flange, plug, or second valve must be installed on the line or valve. The results of this weekly check and any corrective actions taken shall be recorded.
54. This permit authorizes emissions from the storage tanks identified in Attachment 1 during planned floating roof landings. Tank floating roofs may only be landed for changes of tank service or tank inspection/maintenance as identified in the permit application, except when the VOC vapors below the floating roof are routed to a control device or a controlled recovery system while the roof is landed. Tank change of service includes landings to accommodate seasonal RVP spec changes and landings to correct off-spec material that cannot be blended into finished product tanks. Tank roof landings include all operations when the tank floating roof is on its supporting legs. These emissions are subject to the maximum allowable emission rates indicated on the MAERT. The following requirements apply to tank roof landings.
- A. The tank liquid level shall be continuously lowered after the tank floating roof initially lands on its supporting legs until the tank has been drained to the maximum extent practicable without entering the tank. Liquid level may be maintained steady for a period of up to two hours if necessary to allow for valve lineups and pump changes necessary to drain the tank. This requirement does not apply where the vapor under a floating roof is routed to control during this process.
 - B. If the VOC TVP of the liquid previously stored in the tank is greater than 0.50 psi at 95°F tank refilling or degassing of the vapor space under the landed floating roof must begin within 24 hours after the tank has been drained. Floating roof tanks with liquid capacities less than 100,000 gallons may be degassed without control if the VOC TVP of the standing liquid in the tank has been reduced to less than 0.02 psia prior to ventilating the tank. Controlled degassing of the vapor space under landed roofs shall be completed as follows:
 - (1) Any gas or vapor removed from the vapor space under the floating roof must be routed to a control device or a controlled recovery system and controlled degassing must be maintained until the VOC concentration is less than 10,000 ppmv or 10 percent of the LEL. The locations and identifiers of vents other than permanent roof fittings and seals, control device or controlled recovery system, and controlled exhaust stream

shall be recorded. There shall be no other gas/vapor flow out of the vapor space under the floating roof when degassing to the control device or controlled recovery system.

- (2) The vapor space under the floating roof shall be vented using good engineering practice to ensure air contaminants are flushed out of the tank through the control device or controlled recovery system to the extent allowed by the storage tank design.
 - (3) A volume equivalent to twice the volume of the vapor space under the floating roof must have passed through the control device or into a controlled recovery system, before the vent stream may be sampled to verify acceptable VOC concentration. The volume measurement shall not include any make-up air introduced into the control device or recovery system. The VOC sampling and analysis shall be performed as specified in SC No. 52.
 - (4) The sampling point shall be upstream of the inlet to the control device or controlled recovery system. The sample ports and the collection system must be designed and operated such that there is no air leakage into the sample probe or the collection system downstream of the process equipment or vessel being purged.
 - (5) If ventilation is to be maintained with emission control, the VOC concentration shall be recorded once an hour.
 - (6) Degassing must be performed every 24 hours unless there is no standing liquid in the tank or the VOC TVP of the remaining liquid in the tank is less than 0.15 psia.
- C. The tank shall not be opened except as necessary to set up for degassing and cleaning, or ventilated without control, until either all standing liquid has been removed from the tank or the liquid in the tank has a VOC TVP less than 0.02 psia. These criteria may be demonstrated in any one of the following ways.
- (1) Low VOC TVP liquid that is soluble with the liquid previously stored may be added to the tank to lower the VOC TVP of the liquid mixture remaining in the tank to less than 0.02 psia. This liquid shall be added during tank degassing if practicable. The estimated volume of liquid remaining in the drained tank and the volume and type of liquid added shall be recorded. The liquid VOC TVP may be estimated based on this information and engineering calculations.
 - (2) If water is added or sprayed into the tank to remove standing VOC, one of the following must be demonstrated:
 - (a) Take a representative sample of the liquid remaining in the tank and verify no visible sheen using the static sheen test from 40 CFR Part 435 Subpart A Appendix 1.
 - (b) Take a representative sample of the liquid remaining in the tank and verify hexane soluble VOC concentration is less than 1000 ppmw using EPA method 1664 (may also use 8260B or 5030 with 8015 from SW-846).
 - (c) Stop ventilation and close the tank for at least 24 hours. When the tank manway is opened after this period, verify VOC concentration is less than 1000 ppmv through the procedure in MSS SC No. 52.
 - (3) No standing liquid verified through visual inspection.
- The permit holder shall maintain records to document the method used to release the tank.

- D. Tanks shall be refilled as rapidly as practicable until the roof is off its legs unless the vapor space is routed to control during refilling except as required by SC No. 69.
 - E. The occurrence of each roof landing and the associated emissions shall be recorded and the rolling 12-month tank roof landing emissions shall be updated on a monthly basis. These records shall include at least the following information:
 - (1) the identification of the tank and emission point number, and any control devices or recovery systems used to reduce emissions;
 - (2) the reason for the tank roof landing;
 - (3) for the purpose of estimating emissions, the date and time of each of the following events:
 - (a) the roof was initially landed,
 - (b) all liquid was pumped from the tank to the extent practical,
 - (c) start and completion of controlled degassing, and total volumetric flow,
 - (d) all standing liquid was removed from the tank or any transfers of low VOC TVP liquid to or from the tank including volumes and vapor pressures to reduce tank liquid VOC TVP to <0.02 psi,
 - (e) if there is liquid in the tank, VOC TVP of liquid, start and completion of uncontrolled degassing, and total volumetric flow,
 - (f) refilling commenced, liquid filling the tank, and the volume necessary to float the roof; and
 - (g) tank roof off supporting legs, floating on liquid;
 - (4) the estimated quantity of each air contaminant, or mixture of air contaminants, emitted between events (c) and (g) with the data and methods used to determine it. The emissions associated with roof landing activities shall be calculated using the methods described in Section 7.1.3.2 of AP-42 "Compilation of Air Pollution Emission Factors, Chapter 7 - Storage of Organic Liquids" dated November 2006 and the permit application.
55. Fixed-roof storage tanks shall not be ventilated without control, until either all standing liquid has been removed from the tank or the liquid in the tank has a VOC TVP less than 0.02 psia. This shall be verified and documented through one of the criteria identified in MSS SC No. 52.C. Storage tanks manways may be opened without emission controls when there is standing liquid with a VOC TVP greater than 0.02 psia as necessary to set up for degassing and cleaning. One manway may be opened to provide access to the tank when necessary to allow access to remove or de-volatilize the remaining liquid. The emission control system shall meet the requirements of SC Nos. 54.B.(1) through 54.B.(5) and records maintained per SC No. 54.E.(3)c through 54.E.(3)e, and 54.E.(4). Low vapor pressure liquid may be added to and removed from the tank as necessary to lower the vapor pressure of the liquid mixture remaining in the tank to less than 0.02 psia.
56. The following requirements apply to vacuum and air mover truck operations at this site:
- A. Vacuum pumps and blowers shall not be operated on trucks containing or vacuuming liquids with VOC TVP greater than 0.50 psi at 95F unless the vacuum/blower exhaust is routed to a control device or a controlled recovery system.

- B. Equip fill line intake with a “duckbill” or equivalent attachment if the hose end cannot be submerged in the liquid being collected.
 - C. A daily record containing the information identified below is required for each vacuum truck in operation at the site each day.
 - (1) Prior to initial use, identify any liquid in the truck. Record the liquid level and document that the VOC TVP is less than 0.50 psi if the vacuum exhaust is not routed to a control device or a controlled recovery system. After each liquid transfer, identify the liquid transferred and document that the VOC TVP is less than 0.50 psi if the vacuum exhaust is not routed to a control device or a controlled recovery system.
 - (2) For each liquid transfer made with the vacuum operating, record the duration of any periods when air may have been entrained with the liquid transfer. The reason for operating in this manner and whether a “duckbill” or equivalent was used shall be recorded. Short, incidental periods, such as those necessary to walk from the truck to the fill line intake, do not need to be documented.
 - (3) If the vacuum truck exhaust is controlled with a control device other than an engine or oxidizer, VOC exhaust concentration upon commencing each transfer, at the end of each transfer, and as required by SC No. 61, measured using an instrument meeting the requirements of MSS SC No. 52.
 - (4) The volume in the vacuum truck at the end of the day, or the volume unloaded, as applicable.
 - D. The permit holder shall determine the vacuum truck emissions each month using the daily vacuum truck records and the calculation methods utilized in the permit application. If records of the volume of liquid transferred for each pick-up are not maintained, the emissions shall be determined using the physical properties of the liquid vacuumed with the greatest potential emissions. Rolling 12 month vacuum truck emissions shall also be determined on a monthly basis.
 - E. If the VOC TVP of all the liquids vacuumed into the truck is less than 0.10 psi, this shall be recorded when the truck is unloaded or leaves the plant site and the emissions may be estimated as the maximum potential to emit for a truck in that service as documented in the permit application. The recordkeeping requirements in SC Nos. 56.A through 56.D do not apply.
57. The following requirements apply to frac, or temporary, tanks and vessels used in support of MSS activities.
- A. Except for labels, logos, etc. not to exceed 15 percent of the tank/vessel total surface area, the exterior surfaces of these tanks/vessels that are exposed to the sun shall be white or aluminum. This requirement does not apply to tanks/vessels that only vent to atmosphere when being filled. This requirement also does not apply to frac tanks which are heated for the purpose of mixing liquids with VOC TVP less than 0.10 psi at 95°F. **(03/16)**
 - B. These tanks/vessels must be covered and equipped with fill pipes that discharge within 6 inches of the tank/vessel bottom.
 - C. These requirements do not apply to vessels storing less than 25 barrels of liquid that are closed such that the vessel does not vent to atmosphere.

- D. The permit holder shall maintain an emissions record which includes calculated emissions of VOC from all frac tanks during the previous calendar month and the past consecutive 12 month period. The record shall include tank identification number, dates put into and removed from service, control method used, tank capacity and volume of liquid stored in gallons, name of the material stored, VOC molecular weight, and VOC TVP at the estimated monthly average material temperature in psia. Filling emissions for tanks shall be calculated using the TCEQ publication titled "Technical Guidance Package for Chemical Sources - Loading Operations" and standing emissions determined using: the TCEQ publication titled "Technical Guidance Package for Chemical Sources Storage Tanks."
- E. If the tank/vessel is used to store liquid with VOC TVP less than 0.10 psi at 95F, records may be limited to the days the tank is in service and the liquid stored. Emissions may be estimated based upon the potential to emit as identified in the permit application.
58. The term "true vapor pressure (TVP)" is used in lieu of the term "partial pressure" in this permit.
59. The MSS activities represented in the permit application may be authorized under permit by rule only if the procedures, emission controls, monitoring, and recordkeeping are the same as those required by this permit.
60. All permanent facilities must comply with all operating requirements, limits, and representations in the permits identified in Attachment 1 during planned startup and shutdown unless alternate requirements and limits are identified in this permit. Alternate requirements for emissions from routine emission points are identified below:
- A. Heaters, boilers, and furnaces are exempt from NO_x and CO operating requirements identified in other special conditions this permit during planned startup and shutdown if the following criteria are satisfied. This exemption does not include NO_x 365-day rolling average limits. **(08/16)**
- (1) The routine maximum allowable emission caps are not exceeded.
 - (2) Except as noted in SC 60 A(4) below the startup period does not exceed 8 hours in duration and the firing rate does not exceed 75 percent of the design firing rate. The time it takes to complete the shutdown does not exceed 4 hours.
 - (3) Control devices are started and operating properly when venting a waste gas stream.
 - (4) Startup times exceeding 8 hours for specific facilities are allowed as identified below: **(04/22)**

Heater, Boiler, or Furnace FIN	EPN	Maximum Hours Allowed for Startup of each FIN
12-H01A and 12-H01B	115A and 115B	48
13-H-01A, 13-H-01B, and 13-H-01C	118	28
31-H-01	117	12
38-H-01, 38-H-02, 38-H-03	162	45
47-H-03 and 47-H-04	150	10
48-H-01	151	12
49-H-01, 49-H-02, 49-H-03, 49-H-04	152	16

Heater, Boiler, or Furnace FIN	EPN	Maximum Hours Allowed for Startup of each FIN
52-H-01	195	24

- B. The limits identified below apply to the operations of the specified facilities during startup and shutdown. All other routine operating limitations apply during planned startup and shutdown.
- (1) The HOC startup period shall not exceed 86 hours and the hourly average CO concentration during this period shall not exceed 1200 ppmvd corrected to zero percent O₂. All HOC emissions during startup are in the MSS emission caps.
 - (2) The sulfur recovery requirements and SRU tail gas incinerator sulfur dioxide concentration limits in SC Nos. 22 and 41 do not apply during SRU startup. Operation in the hot standby mode shall be minimized. The SRU tailgas incinerator shall be operated in accordance with SC No. 24 during this period. A SRU incinerator shall not operate in this mode for more than 72 hours in any rolling 12 month period.
 - (3) Paragraph (2) of this condition does not apply when SRU vent gasses from a TGI are routed through the HOC caustic scrubber prior to being discharged to the atmosphere. This paragraph applies instead. The HOC caustic scrubber shall be monitored with a SO₂ CEMS.
- C. A record shall be maintained indicating that the start and end times for each of the activities identified above occur and documentation that the requirements for each have been satisfied.
61. Control devices required by this permit for emissions from planned MSS activities are limited to those types identified in this condition. Control devices shall be operated with no visible emissions except periods not to exceed a total of five minutes during any two consecutive hours. Each device used must meet all the requirements identified for that type of control device.

Controlled recovery systems identified in this permit shall be directed to an operating refinery process or to a collection system that is vented through a control device meeting the requirements of this permit condition.

- A. Carbon Adsorption System (CAS).
- (1) The CAS shall consist of 2 carbon canisters in series with adequate carbon supply for the emission control operation.
 - (2) The CAS shall be sampled downstream on the first can and the concentration recorded at least once every hour of CAS run time to determine breakthrough of the VOC. The sampling frequency may be extended using either of the following methods:
 - (a) The CAS systems equipped with an upstream liquid scrubber may be sampled once every 12 hours of CAS run time to determine breakthrough.
 - (b) Sampling frequency may be extended to up to 30 percent of the minimum potential saturation time for a new can of carbon. The permit holder shall maintain records including the calculations performed to determine the minimum saturation time.
 - (c) The carbon sampling frequency may be extended to longer periods based on previous experience with carbon control of a MSS waste gas stream. The past experience must be with the same VOC, type of facility, and MSS activity. The

basis for the sampling frequency shall be recorded. If breakthrough is monitored on the initial sample of the upstream can when the polishing can is put in place, a permit deviation shall be recorded.

- (3) The method of VOC sampling and analysis shall be by detector meeting the requirements of SC No. 52.
- (4) Breakthrough is defined as the highest measured VOC or benzene concentration at or exceeding 100 ppmv or 5 ppmv, respectively, above background. When the condition of breakthrough of VOC from the initial saturation canister occurs, the waste gas flow shall be switched to the second canister and a fresh canister shall be placed as the new final polishing canister within twenty-four hours. In lieu of replacing canisters, the flow of waste gas may be discontinued until the canisters are switched. Sufficient new activated carbon canisters shall be available to replace spent carbon canisters such that replacements can be done in the above specified time frame.
- (5) Records of CAS monitoring shall include the following:
 - (a) Sample time and date.
 - (b) Monitoring results (ppmv).
 - (c) Canister replacement log.
- (6) Single canister systems are allowed if the time the carbon canister is in service is limited to no more than 30 percent of the minimum potential saturation time. The permit holder shall maintain records for these systems, including the calculations performed to determine the saturation time. The time limit on carbon canister service shall be recorded and the expiration date attached to the carbon can.
- (7) Liquid scrubbers may be used upstream of carbon canisters to enhance VOC capture provided such systems are closed systems and the spent absorbing solution is discharged into a closed container, vessel, or system.

B. Thermal Oxidizer and Vapor Combustion Units (VCUs) (04/22)

- (1) The thermal oxidizer or VCU six minute average firebox exit temperature shall be maintained at not less than 1400°F and waste gas flows shall be limited to assure at least a 0.5 second residence time in the fire box while waste gas is being fed into the oxidizer.
- (2) The thermal oxidizer or VCU exhaust temperature shall be continuously monitored and recorded when waste gas is directed to the oxidizer or VCU. The temperature measurements shall be made at intervals of six minutes or less and recorded at that frequency. Temperature measurements recorded in continuous strip charts may be used to meet the requirements of this section.

The temperature measurement device shall be installed, calibrated, and maintained according to accepted practice and the manufacturer's specifications. The device shall have an accuracy of the greater of ± 0.75 percent of the temperature being measured expressed in degrees Celsius or $\pm 2.5^{\circ}\text{C}$.

- (3) As an alternative to 61.B.(1) of this condition, the thermal oxidizer or VCU may be tested to confirm a minimum 99 wt percent destruction efficiency. The results of the test will be used to determine the minimum operating temperature and residence time. Stack Test must have been performed within the last 12 months. Stack VOC concentrations and flow rates shall be measured in accordance with applicable United

States Environmental Protection Agency (EPA) Reference Methods. A copy of the test report shall be maintained with the thermal oxidizer or VCU and a summary of the testing results shall be included with the emission calculations.

- (4) As an alternative to 61.B.(1)-(2) of this condition, the thermal oxidizer or VCU may be equipped with continuous VOC monitors (inlet and outlet). The VOC monitors shall be calibrated and maintained according to SC No. 52, except 52.C. In order to demonstrate compliance with this requirement, inlet VOC and outlet VOC concentrations and flows shall be measured at least every 15 minutes and this information used to determine inlet and outlet VOC mass rates on an hourly basis to confirm a minimum of 99 percent destruction efficiency or an exhaust concentration not greater than 20 ppmv.

C. Internal Combustion Engine.

- (1) The internal combustion engine shall have a VOC destruction efficiency of at least 99 percent.
- (2) The engine must have been stack tested with butane to confirm the required destruction efficiency within the past 12 months. VOC shall be measured in accordance with the applicable United States EPA Reference Method during the stack test and the exhaust flow rate may be determined from measured fuel flow rate and measured oxygen concentration. A copy of the stack test report shall be maintained with the engine. There shall also be documentation of acceptable VOC emissions following each occurrence of engine maintenance which may reasonably be expected to increase emissions including oxygen sensor replacement and catalyst cleaning or replacement. Stain tube indicators specifically designed to measure VOC concentration shall be acceptable for this documentation, provided a hot air probe or equivalent device is used to prevent error due to high stack temperature, and three sets of concentration measurements are made and averaged. Portable VOC analyzers meeting the requirements of SC No. 52 are also acceptable for this documentation.
- (3) The engine shall be operated with an oxygen sensor-based air-to-fuel ratio (AFR) controller. Documentation for each AFR controller that the, manufacturer's, or supplier's recommended maintenance has been performed, including replacement of the oxygen sensor as necessary for oxygen sensor-based controllers shall be maintained with the engine. The oxygen sensor shall be replaced at least quarterly in the absence of a specific written recommendation.

D. The plant flare system

- (1) The heating value and velocity requirements in 40 CFR 60.18 shall be satisfied during operations authorized by this permit.
- (2) The flare shall be operated with a flame present at all times and/or have a constant pilot flame. The pilot flame shall be continuously monitored by a thermal couple or an infrared monitor. The time, date, and duration of any loss of pilot flame shall be recorded. Each monitoring device shall be accurate to, and shall be calibrated at a frequency in accordance with, the manufacturer's specifications.
- (3) Each flare shall be equipped with one of the following:
 - (a) Operation and maintenance of a flare gas recovery system.

- (b) A continuous flow monitor and composition analyzer that provides a record of the flare gas flow and composition of either the total VOC or heating value of the flare gas.

The flow monitor and analyzer sample point shall be installed as near as possible to the flare inlet such that the total vent stream to the flare is measured and analyzed. Readings shall be taken at least once every 15 minutes and the average hourly values of the flow and composition shall be recorded each hour. The flow monitors shall be calibrated on an annual basis to meet the following accuracy specifications: the flow monitor must be calibrated to manufacturer's specifications; the temperature monitor must be calibrated to within ± 2.0 percent at absolute temperature; the pressure monitor must be calibrated to within ± 5.0 mmHg.

- i. If VOC monitoring is chosen: Calibration of the analyzer shall follow the procedures and requirements of Section 10.0 of 40 CFR Part 60, Appendix B, Performance Specification 9, as amended through October 17, 2000, (65 FR 61744), except that the multi-point calibration procedure in Section 10.1 of Performance Specification 9 shall be performed at least once every calendar quarter instead of once every month, and the mid-level calibration check procedure in Section 10.2 of Performance Specification 9 shall be performed at least once every calendar week instead of once every 24 hours. The on-line analyzer system must be capable of measuring constituents sufficient to determine the net heating value of the gas combusted in the flare to within 5.0%, or be calibrated with certified standards of the top two constituents affecting net heating value, whichever is more stringent and the ranges of calibration standards may be based on the typical concentrations observed rather than the full potential range of concentrations. The calibration gases used for calibration procedures shall be in accordance with Section 7.1 of Performance Specification 9. Net heating value of the gas combusted in the flare shall be calculated according to the equation given in 40 CFR § 60.18(f)(3) as amended through October 17, 2000, (65 FR 61744).
- ii. If heating value is chosen: The calorimeter shall be calibrated, installed, operated, and maintained, in accordance with manufacturer recommendations, to continuously measure and record the net heating value of the gas sent to the flare, in British thermal units/standard cubic foot of the gas.

E. Single Carbon Adsorption or Scrubber System

A single liquid scrubbing or single carbon canister adsorption system may be used as a sole control device if the requirements below are satisfied.

- (1) The exhaust to atmosphere shall be continuously monitored with a CEM. The VOC concentration shall be recorded at least once every 15 minutes when waste gas is directed to the CAS or scrubber.
- (2) The method of VOC sampling and analysis shall be by detector meeting the requirements of SC No. 52 except 52.C.
- (3) An alarm shall be installed such that an operator is alerted when outlet VOC concentration exceeds 100 ppmv above background. The MSS activity shall be stopped as soon as possible when the VOC concentration exceeds 100 ppmv above

background for more than one minute. The date and time of all alarms and the actions taken shall be recorded.

- F. A closed loop refrigerated vapor recovery system
 - (1) The vapor recovery system shall be installed on the facility to be degassed using good engineering practice to ensure air contaminants are flushed from the facility through the refrigerated vapor condensers and back to the facility being degassed. The vapor recovery system and facility being degassed shall be enclosed except as necessary to insure structural integrity (such as roof vents on a floating roof tank).
 - (2) VOC concentration in vapor being circulated by the system shall be sampled and recorded at least once every 4 hours at the inlet of the condenser unit with an instrument meeting the requirements of SC No. 52.
 - (3) The quantity of liquid recovered from the tank vapors and the tank pressure shall be monitored and recorded each hour. The liquid recovered must increase with each reading and the tank pressure shall not exceed one inch water pressure while the system is operating.
- G. Other control devices approved by the TCEQ through a permit amendment application or a pollution control permit application.

62. The following requirements apply to capture systems for the plant flare system.

- A. Each capture system for the plant flare system shall comply with one of the following:
 - (1) Conduct a once a month visual, audible, and/or olfactory inspection of the capture system to verify there are no leaking components in the capture system; or
 - (2) verify the capture system is leak-free by inspecting in accordance with 40 CFR Part 60, Appendix A, Test Method 21 once a year. Leaks shall be indicated by an instrument reading greater than or equal to 500 ppmv above background.
- B. The control device shall not have a bypass.
- C. If any of the inspections under A of this condition is not satisfactory, the permit holder shall promptly take necessary corrective action. Records shall be maintained documenting the performance and results of the inspections required in this condition.

63. If spray guns are used to apply paint, they shall be airless, high volume low pressure (HVLP), or have the same or higher transfer efficiency as airless or HVLP spray guns.

64. Emissions from all painting activities, except for minor painting identified in Attachment 2 to this permit, at this site must satisfy the criteria below. New compounds may also be added through the use of the procedure below.

- A. Short-term (pounds per hour [lb/hr]) and annual (TPY) emissions shall be determined for each chemical in the paint as documented in the permit application. The calculated emission rate shall not exceed the maximum allowable emissions rate at any emission point.
- B. The Effect Screening Level (ESL) for the material shall be obtained from the current TCEQ ESL list or by written request to the TCEQ Toxicology Division.
- C. The total painting emissions of any compound must satisfy one of the following conditions:

- (1) The total emission rate is less than 0.1 lb/hr and the ESL greater than or equal to $2 \mu\text{g}/\text{m}^3$; or
 - (2) The emission rate of the compound in pounds per hour is less than the ESL for the compound divided by 171.5 ($\text{ER} < \text{ESL}/171.5$).
- D. The permit holder shall maintain records of the information below and the demonstrations in steps A through C above. The following documentation is required for each compound:
 - (1) Chemical name(s), composition, and chemical abstract registry number if available.
 - (2) Material Safety Data Sheet.
 - (3) Maximum concentration of the chemical in weight percent
 - (4) Paint usage and the associated emissions shall be recorded each month and the rolling 12 month total emissions updated.
65. No visible emissions shall leave the property due to painting or abrasive blasting.
66. Black Beauty and Garnet Sand may be used for abrasive blasting. The permit holder may also use blast media that meet the criteria below:
 - A. The media shall not contain asbestos or greater than 1.0 weight percent crystalline silica.
 - B. The weight fraction of any metal in the blast media with a short term ESL less than 50 micrograms per cubic meter as identified in the most recently published TCEQ ESL list shall not exceed the $\text{ESL}_{\text{metal}}/1000$.
 - C. The MSDS for each media used shall be maintained on site.
 - D. Blasting media usage and the associated emissions shall be recorded each month and the rolling 12 month total emissions updated.
67. Planned maintenance activities must be conducted in a manner consistent with good practice for minimizing emissions, including the use of air pollution control equipment, practices and processes. All reasonable and practical efforts to comply with SC Nos. 49 through 66, 68, and 69 must be used when conducting the planned maintenance activity, until the commission determines that the efforts are unreasonable or impractical, or that the activity is an unplanned maintenance activity.
68. Slab cleaning activities are limited to water washing small pieces of process equipment, empty vacuum trucks, and empty portable frac containers. Records shall be maintained of the number of items cleaned each day and the emissions determined each month based on the number of items cleaned as estimated in the permit amendment application, PI-1 dated December 21, 2006. The permit holder may assume that all vacuum trucks and frac tanks used on the site as recorded in SC Nos. 56 and 57 are cleaned in lieu of maintaining cleaning records for those items.
69. The following requirements ensure satisfactory impacts off-site during MSS.
 - A. A maximum of 3 frac or temporary storage tanks or vessels may be filled with naphtha during any one hour period.
 - B. Emissions from refilling tanks with a landed roofs with a liquid with a vapor pressure greater than 0.50 psia shall be routed to a control device meeting the requirements of SC No. 61 unless the tank has been cleaned and degassed.

- C. While filling a tank with a landed roof with a liquid with vapor pressure greater than 0.50 psia without emission control, no other tanks with landed roofs may be degassed or filled with that type of liquid.
- D. If a cleaned and degassed tank with a landed roof has been refilled with a liquid with vapor pressure greater than 0.50 psia without emission control in the past 12 months, emissions from refilling the tank with a landed roof shall be routed to a control device meeting the requirements of SC No. 61 if the liquid has a vapor pressure greater than 0.50 psia.
70. Records shall be maintained in accordance with SC No. 50 for planned MSS on the Air Liquide Large Industries SMR (Permit 34245, RN103120929). Total waste gas directed to the Valero flares during these operations shall not exceed the total identified in the permit amendment application, PI-1 dated September 23, 2014. **(03/16)**
71. The following steps shall take place before the catalyst is removed from the HDS unit for transfer to the catalyst pad. The reactor shall be cooled prior to opening and the catalyst shall be flushed with gas oil followed by hydrogen recycle gas circulation. The catalyst shall then be neutralized with a demineralized water and soda ash solution.
72. Each of the following EPNs may not exceed the hours of MSS operation per calendar year shown in the table. **(03/16)**

Emission Point Number	Hours of MSS operation per calendar year
30-B-04MSS	36
16-P-11	52
16-P-12	52
16-P-13	52
16-P-14	52

Permit References

73. The permit holder shall maintain a copy of the effective permit at the site together with complete copies of all confidential documents that are referenced in the above permit conditions as attachments. The permit and attachments shall be made available to TCEQ personnel at the site upon request.

Emission Cap Compliance Recordkeeping

74. Recordkeeping programs for those facilities authorized by the permit shall be established and maintained such that the ability to demonstrate compliance with all authorized emission caps and individual emission rate limits (short-term and annual) is ensured. Records of all compliance testing, CEMS/PEMS results, and process parameters necessary to demonstrate compliance with the emission rate caps shall be maintained on-site for a period of five years.

Emissions calculations for verifying compliance with the emission caps shall be performed at least once every quarter to demonstrate compliance with the annual rolling average requirement. The

holder of this permit shall maintain all records necessary to demonstrate compliance with the short-term (lb/hr) and annual TPY emissions cap and provide such demonstration of compliance to the TCEQ Corpus Christi Regional Office upon request.

The emissions shall be determined using the following techniques: **(02/18)**

Fugitive	Component counts using the emission factors and method specified in the permit application.
Cooling Towers	Measured strippable VOC concentration as specified in SC No. 30 and the cooling tower circulation rate.
Tanks	As specified in SC No. 28.
Heaters/Boilers	If a CEMS is installed, as specified in SC No. 40. If stack tested per SC No. 39, using the most recent stack test result and recorded firing rate for the period. If no sampling is required, using the emission factor in the permit application and the recorded firing rate for the period.
Loading	Fugitive emissions from loading operations shall be calculated using: (a) AP 42 loading equation listed in Chapter 5.2 and (b) the TCEQ publication titled "Technical Guidance for Chemical Sources Loading Operations." Emissions from control devices shall be determined using the emission factor (in mg/l) determined through testing and the volume loaded. The manufacturer's guaranteed emission factor may be used if the most recent stack testing has verified that factor.
SRU/HOC	If a CEMS is installed, as specified in SC No. 40.
Scrubber	If stack tested per SC No. 38, using the most recent stack test result and recorded operating rate for the period. If no sampling is required, using the emission factor in the flexible permit application and the average value of the appropriate operating parameter for the period.
Diesel Engines	Emissions calculated based on hours of operation and emission factors listed on Table D-1 in the confidential section of the permit amendment application dated November 16, 2004.

These and all other records required by any previous condition of this permit shall be made available to the TCEQ Executive Director or his representative upon request.

Federal Applicability

75. These facilities shall comply with all applicable requirements of the U.S. Environmental Protection Agency (EPA) regulations on Standards of Performance for New Stationary Sources promulgated for the following:
 - A. Petroleum Refineries in 40 CFR Part 60, Subparts A , J, and Ja as follows: **(04/16)**
 - (1) All heaters and boilers – Subpart J, except as noted below;

- (2) Desalter Heater (EPN 114), Heater 31-H-01 (EPN: 117), Boiler 30-B-04 (EPN: 30-04), and Boiler 30-B-05 (EPN 30-B-05) – Subpart Ja
 - (3) HOC – Subpart J
 - (4) HOC – Subpart Ja (upon startup of the HOC Reconfiguration Project (Project 333877))
 - (5) SRU's – Subpart J
 - (6) BUP Flare, Main Flare, and Ground Flare – Subpart Ja
 - B. Petroleum Liquids for Which Construction, Reconstruction, or Modification Commenced After June 11, 1973, and Prior to May 19, 1978, in 40 CFR Part 60, Subparts A and K.
 - C. Petroleum Liquids for Which Construction, Reconstruction, or Modification Commenced After May 18, 1978, and Prior to July 23, 1984, in 40 CFR Part 60, Subparts A and Ka.
 - D. Volatile Organic Liquid Storage Vessels (including Petroleum Liquid Storage Vessels) for Which Construction, Reconstruction, or Modification Commenced after July 23, 1984, in 40 CFR Part 60, Subparts A and Kb.
 - E. Equipment Leaks of VOC in the Synthetic Organic Chemicals Manufacturing Industry (SOCMI) for which Construction, Reconstruction, or Modification Commenced After January 5, 1981, and on or Before November 7, 2006, in 40 CFR Part 60, Subparts A and VV.
 - F. Bulk Gasoline Terminals in 40 CFR Part 60, Subparts A and XX.
 - G. Petroleum Refineries for which Construction, Reconstruction, or Modification Commenced after January 4, 1983, and on or Before November 7, 2006, in 40 CFR Part 60, Subparts A and GGG.
 - H. The VOC Emissions from SOCMI Distillation Operations in 40 CFR Part 60, Subparts A and NNN.
 - I. The VOC Emissions from Petroleum Refinery Wastewater Systems in 40 CFR Part 60, Subparts A and QQQ.
 - J. The VOC Emissions from SOCMI Reactor Processes in 40 CFR Part 60, Subparts A and RRR.
76. These facilities shall comply with all applicable requirements of EPA regulations on National Emission Standards for Hazardous Air Pollutants (NESHAPS) promulgated for the following:
- A. Asbestos in 40 CFR Part 63, Subparts A and M.
 - B. Benzene Waste Operations in 40 CFR Part 63, Subparts A and FF.
77. These facilities shall comply with all applicable requirements of EPA regulations on National Emission Standards for Hazardous Air Pollutants (NESHAPS) for Source Categories promulgated for the following:
- A. Marine Tank Vessel Loading Operations in 40 CFR Part 63, Subparts A and Y.
 - B. Hazardous Air Pollutants from Petroleum Refineries in 40 CFR Part 63, Subparts A and CC.
 - C. Hazardous Air Pollutants for Petroleum Refineries: Catalytic Cracking Units, Catalytic Reforming Units, and Sulfur Recovery Units in 40 CFR Part 63, Subparts A and UUU.

- D. Industrial, Commercial, and Institutional Boilers and Process Heaters in 40 CFR Part 63, Subparts A and DDDDD. **(02/18)**
- E. Hazardous Air Pollutants: Site Remediation in 40 CFR Part 63, Subparts A and GGGGG.

Referenced Permit by Rule Authorizations

78. The following sources and/or activities are authorized under a Permit by Rule (PBR) by Title 30 Texas Administrative Code Chapter 106 (30 TAC Chapter 106). These lists are not intended to be all inclusive and can be altered without modifications to this permit. **(04/22)**

Authorization	Source or Activity
PBR No. 155846	Control of liquid petroleum gas (LPG) unloading with a portable vapor combustion unit.

Sour Water Storage Tanks

79. The sour water storage tanks shall be subject to the following conditions:
- A. The sour water storage tank system shall be maintained by either of the following methods:
 - (1) A minimum sour water retention time of 2.0 days in conjunction with a hydrocarbon detection and flow diversion system designed to prevent hydrocarbon carryover to the SRUs by routing sour waters with unacceptable levels of hydrocarbons to the tanks listed in A of this condition. Retention time shall be calculated and recorded daily using the daily average combined tank volume of all sour water tanks and the daily average combined feed rates to the sour water strippers.
 - (2) A minimum sour water retention time of 3.0 days
 - B. If acid gas flaring takes place that might be traced to hydrocarbon carryover from the sour water system, the operator shall engage a third-party consultant to complete a Root Cause Failure Analysis (RCFA) within 90 days after the acid gas flaring event in question. The Corpus Christi Regional Office shall be supplied with a copy of the RCFA within 10 days of it being completed. If the RCFA determines that the acid gas flaring event can be traced to sour water system hydrocarbon carryover that is partially or totally caused by inadequate retention or hold up times, the holder of this permit shall implement one of the following options within 60 days after completion of the RCFA:
 - (1) The holder of this permit shall submit design information and a proposed implementation schedule to the TCEQ Office of Permitting and Registration for three days of sour water retention and hold up time based on maximum expected feed rates to the sour water strippers, or
 - (2) Design information and implementation schedule of a proposed alternative other than increased sour water retention time.
 - C. For periods of planned maintenance activity for the sour water tank, the sour water stripper surge system shall have a reduced minimum on-line retention time of one and a half days

based on the sour water flow rate into the tanks. Records of these periods and the corresponding maintenance activity must be maintained and made available upon request.

Greenhouse Gas Emissions

80. Permit holders must keep records sufficient to demonstrate compliance with 30 Texas Administrative Code § 116.164. If construction, a physical change or a change in method of operation results in Prevention of Significant Deterioration (PSD) review for criteria pollutants, records shall be sufficient to demonstrate the amount of emissions of GHGs from the source as a result of construction, a physical change or a change in method of operation does not require authorization under 30 TAC §116.164(a). If there is construction, a physical change or change in the method of operation that will result in a net emission increase of 75,000 tpy or more CO_{2e} and PSD review is triggered for criteria pollutants, greenhouse gas emissions are subject to PSD review.
81. Monitoring, quality assurance/quality control requirements, emission calculation methodologies, record keeping, and reporting requirements related to Greenhouse Gas (GHG) emissions shall adhere to the applicable requirements in 40 CFR Part 98 and in this permit.
82. Beginning after the start-up of the new and modified sources associated with the HOC Reconfiguration Project (TCEQ Project 333877), modification and construction, the permittee shall calculate the CO_{2e} emissions on a 12-month rolling basis, based on the procedures and Global Warming Potentials (GWP) contained in Greenhouse Gas Regulations, 40 CFR Part 98, Subpart A, Table A-1. This condition applies to the following EPNs: 121 (HOC contribution only), FUG-CAP (new components added for Project 333877), and 30-B0-05.
83. Records of emissions of GHG, and how they were determined, in compliance with Special Condition Nos. 80, 81, and 82 must be maintained by the holder of this permit in a form suitable for inspection for a period of five years after collection and must be made available upon request to representatives of the TCEQ, EPA, or any local air pollution control program having jurisdiction.
84. Operational and Monitoring requirements for Boiler 30-B-05.
 - A. Boiler 30-B-05 shall be operated with a net thermal efficiency of no less than 78 percent on a 12-month rolling average, excluding periods of maintenance, startup and shutdown. This shall be ensured by using the following good combustion practices: operating the boiler at an optimum air-fuel ratio, limiting the boiler's operating temperature to the extent practicable, and reducing heat loss through the use of insulating materials where feasible.
 - B. Thermal efficiency shall be calculated and recorded at least monthly using equation G-1 from American Petroleum Institute (API) method 560 (4th ed. or later), Annex G using monitoring data collected as required under this permit, other quality-assured data, and engineering judgment.

If the maximum range between twelve or more consecutive monthly efficiency calculations does not exceed 5 percentage points, and each calculation demonstrates compliance with the minimum efficiency requirements of this paragraph, the permit holder may elect to reduce the frequency of performing the calculation to quarterly (skipping up to two monthly calculations); provided, however, that:

Special Conditions

Permit Numbers 38754, PSDTX324M15, and GHGPSDTX211

Page 44

- (1) In case a quarterly efficiency calculation yields an efficiency value outside of the maximum range specified in this previous paragraph, monthly efficiency calculations shall be resumed.
- (2) In case a quarterly efficiency calculation shows non-compliance with the minimum efficiency requirement of this paragraph, the permit holder shall assume that a condition of non-compliance occurred during each month of the previous quarter where a calculation was skipped.

Date: May 3, 2024

Attachment 1

Permit Numbers 38754, PSDTX324M15, and GHGPSDTX211

Permit Emission Points by Type

Category	EPN	Description
Fired Units	1	Crude Heater
	16-P-04	Diesel Pump
	16-P-07	Diesel Pump
	16-P-11	Diesel Pump
	16-P-12	Diesel Pump
	16-P-13	Diesel Pump
	16-P-14	Diesel Pump
	49-H-90	C7 Splitter Reboiler
	74	Vacuum Unit Heater
	83-P-136A	Diesel Pump
	83-P-136B	Diesel Pump
	114	Desalter Heater
	115	HDS Charge Heaters
	116	HDS Heavy Oil Preheater
	117	Alky Fract Reboiler
	118	Hydrogen Reformer Heater
	119	Sulfen Heater
	120	Butamer Heater
	121	HOC (incinerator and scrubber stack)
	121a	SRU Bypass Stack
	124	API Separator Combustor
	131	Crude Preflash Heater
	132	Crude Stabilizer Heater
	150	HCU Heater
	151	NHT Heater
	152	CRU Heaters
	153	Boiler 30-B-02
	162	Oleflex Heaters
	172	RSU Heater

Category	EPN	Description
	30-B-04	Boiler 30-B-04
	30-B-04MSS	Boiler 30-B-04MSS
	195	GD Charge Heater
	900	Crude Charge Heater (Permit No. 106965)
	TRUCKCOMB	Truck Loading Combustor
	30-B-05	Boiler 30-B-05
Flares	126	Main Flare
	127	MTBE Flare
	135	Acid Gas Flare (Pilots Only)
	158	Ground Flare
Tanks	69	Tank No. 9
	83-TK-26	Tank No. 26
	83-TK-155	Tank No. 155
	83-TK-159	Tank No. 159
	83-TK-160	Tank No. 160
	83-TK-162	Tank No. 162
	187	Tank No. 25 (Sour Water Tank)
	902	Tank No. 165 (Permit No. 106965)
Fugitive	1F	Crude Unit
	2F	Vacuum Unit
	4F	LEU
	07F	BUP Flare
	08F	08 FLR/Day Tanks
	11F	Desalter Unit
	12F	HDS Unit
	13F	SMR
	18F	HRLEU Unit
	20F	LRU
	21/22F	HOC Unit
	30F	Boilerhouse

Category	EPN	Description
	31F	HF Alkylation Unit
	36F	Butamer Unit
	37F	MTBE
	38F	Oleflex
	41F	SRU Unit
	42F	SWS
	46-24F	SULF/SEU
	47F	HCU
	47PSAF	PSA
	48F	NHT
	49F	CRU
	52F	Gasoline Desulfurization
	54F	SHU
	83F	WWT
	175	49-RSU/XFU
	201	Railcar Unloading
	DOCKS	Docks
	LPGSTGF	LPG Storage
	MVRUF	MVRU
	TERM-F	Terminals
	TRKRACKFUG	Truck Rack
	903	Crude Unit Fugitives (Permit No. 106965)
	904	Crude Unit BWS Fugitives (Permit No. 106965)
	908	Crude Storage Fugitives (Permit No. 109543)
	##F	Selective Hydrogenation Unit
	##F	LPG Gas Plant
	##F	Boiler 30-B-05
Loading	31	Barge Loading (Heavy Oil)
	SHIP FUG	Ship Dock Fugitives
	TRUCKFUG	Truck Loading

Category	EPN	Description
	VRU	Marine loading VRU
	907	Crude Loading Fugitives (Permit No. 109543)
	909	Crude Loading Vapor Combustor (Permit No. 109543)
Other	1CT	CU/VRU Cooling Tower
	01-01	Crude/Vac Pump Alley
	01-02	North of Vac Unit
	01-03	North of Vac Unit
	50-01	East of Tank 62
	52-01	NW of GDU MCC
	70-01	East of Tank 55
	70-02	NW of Tank 106
	70-03	West of Tank 94
	72-01	East of Tank 111
	73-01	North of Tank 152
	73-01	Between TK 8 & TK 164
	83-01	WWT-Hydroblast Pad
	01-04	NW of Vac Unit
	03-01	North of tanks 156/161
	11-01	Desalter Pump Alley
	21BH	Magnacat Unit
	41-01	North of 43-TK-08
	41-02	West of 41-V-05
	49-01	NW of XFU
	49-02	North of NHT
	49-03	NHT Pump Alley
	83-02	WWT-Desalter Lift
	83-03	WWT-East of KOH Trtr
	83-04	WWT- NE of Tank 159
	83-05	WWT-North Lift

Category	EPN	Description
	83-06	WWT-North of V-68
	83-07	WWT-South of V-55
	83-09	WWT-BSRP
	83-10	WWT-83-V-99
	83-12	WWT-83-V-28
	83-TK-23	Equalization Tank
	83-TK-27	Bio Oxidation Tank
	83-V-58	Tank No. 58
	83-V-59	Tank No. 59
	83-V-97	Tank No. 97
	98-02	WP MSAT Rail Rack
	122	HOC Cooling Tower
	123	ALKY Cooling Tower
	124a	API Sep Back Up
	155	CCU CCR
	901	Crude Unit Cooling Tower (Permit No. 106965)
	168	Oleflex CCR
	AE-49601A/B	Analyzer Vent AE-49601A/B
	167-CT	BUP Cooling Tower
	AE-49900A/B	Analyzer Vent AE-49900A/B
	AE-49901A/B	Analyzer Vent AE-49901A/B
	V-201	WP MSAT Rail Rack
	WWTP-AERB	Aeration Basin
	WWTP-CLRF	Clarifier
	WWTP-OWS	WW Collection System
	WWTP-SLB	Salin Basin
	HOC-PP-CT	Cooling Tower -Propylene Project
	XX-01	HOC PP Gas Plant CAS

Date: May 3, 2024

Attachment 2

Permit Numbers 38754, PSDTX324M15, and GHGPSDTX211

Inherently Low Emitting Activities

Activity	Emissions				
	VOC	NO _x	CO	PM	H ₂ S/SO ₂
Catalyst activation/deactivation	x				
Management of sludge from pits, ponds, sumps, and water conveyances	x				
Aerosol Cans	x				
Calibration of analytical equipment and process instrumentation	x	x	x		x
Carbon canister replacement	x				
Catalyst charging/handling				x	
Instrumentation/analyzer maintenance	x				
Meter proving	x				
Replacement of analyzer filters and screens	x				
Maintenance on water treatment systems (cooling, boiler, potable)	x				
Soap and other aqueous based cleaners	x				
Cleaning sight glasses	x				
Aerosol and miscellaneous chemical usage	x				

Date: January 22, 2016

Attachment 3

Permit Numbers 38754, PSDTX324M15, and GHGPSDTX211

Routine Maintenance Activities

Pump repair/replacement

Fugitive component (valve, pipe, flange) repair/replacement

Compressor repair/replacement

Heat exchanger repair/replacement

Vessel repair/replacement

Date: January 22, 2014

Attachment 4

Permit Numbers 38754, PSDTX324M15, and GHGPSDTX211

MSS Activity Summary

Facilities	Description	Emissions Activity	EPN
all process units and tanks	shutdown/depressurize/drain/startup (includes SRU shutdowns, FCCU startups and Air Liquide MSS activities)	Vent to control	MSS Turnaround (MSS-TA) Routine MSS (MSS-MA)
all process units and tanks	process unit purgegas/drain/startup (except FCCU and SRU)	Vent to atmosphere	MSS-TA Uncontrolled MSS-MA Uncontrolled
Vacuum Trucks	removal and transfer of process and/or waste liquids	Vent to atmosphere	MSS-TA Uncontrolled MSS-MA Uncontrolled
Process units and tanks	Painting	Vent to atmosphere	MSS-TA Uncontrolled MSS-MA Uncontrolled
Process units and tanks	Miscellaneous chemical usage	Vent to atmosphere	MSS-TA Uncontrolled MSS-MA Uncontrolled
FRAC tanks	Temporary storage of process liquids and/or waste liquids	Vent to atmosphere	MSS-TA Uncontrolled MSS-MA Uncontrolled
Cleaning Slab	Washing of portable or mobile MSS or process equipment	vent to atmosphere	MSS-TA Uncontrolled MSS-MA Uncontrolled
Process units and tanks	Abrasive blasting	Vent to atmosphere	MSS-TA Uncontrolled
HDS	Remove spent catalyst, store on pad prior to transfer	Vent to atmosphere	MSS-TA Uncontrolled
Boiler 30-B-04	Startup and shutdown	Vent to atmosphere	30-B-04 MSS
Firewater Pump Engines	Test runs	Vent to atmosphere	16-P-11, 16-P-12, 16-P-13, and 16-P-14

Date: May 3, 2024

Emission Sources - Maximum Allowable Emission Rates

Permit Numbers 38754 and PSDTX324M15

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities, sources, and related activities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

Air Contaminants Data

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
MSS Caps	MSS Caps	CO	2,085.19	128.91
		H ₂ S	10.59	0.22
		NH ₃	4.41	0.17
		NO _x	356.84	27.19
		PM	79.52	3.76
		PM ₁₀	79.52	2.92
		PM _{2.5}	79.52	2.92
		SO ₂	996.29	338.89
		VOC	578.44	70.04
		Exempt Solvents	1.76	0.60
1	Heater - Crude Heater (01-H-01)	CO	8.10	20.13
		NH ₃	0.05	0.17
		NO _x	9.72	19.24
		PM	1.21	4.00
		PM ₁₀	1.21	4.00
		PM _{2.5}	1.21	4.00
		SO ₂	2.50	5.71
		VOC	0.87	2.90
131	Heater - Crude Preflash (01-H-02)	CO	0.62	2.71
		NH ₃	<0.01	0.02
		NO _x	1.77	6.29
		PM	0.13	0.49
		PM ₁₀	0.13	0.49
		PM _{2.5}	0.13	0.49

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
		SO ₂	0.27	0.64
		VOC	0.10	0.35
132	Heater - Crude Stabilizer (01-H-03)	CO	0.17	0.72
		NH ₃	<0.01	<0.01
		NO _x	0.48	2.06
		PM	0.04	0.15
		PM ₁₀	0.04	0.15
		PM _{2.5}	0.04	0.15
		SO ₂	0.07	0.22
		VOC	0.03	0.11
74	Vacuum Heater	CO	4.99	16.77
		NH ₃	0.03	0.14
		NO _x	5.98	26.21
		PM	0.74	3.26
		PM ₁₀	0.74	3.26
		PM _{2.5}	0.74	3.26
		SO ₂	1.37	4.13
		VOC	0.54	2.36
114	Heater - Desalter Heater (11-H-01)	CO	3.54	15.52
		CO	3.54	15.52
		NH ₃	0.03	0.14
		NO _x	3.96	17.34
		PM	0.74	3.23
		PM ₁₀	0.74	3.23
		PM _{2.5}	0.74	3.23
		SO ₂	1.52	4.60
		VOC	0.53	2.34

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
		H ₂ S	0.02	0.05
115	HDS Heaters	CO	8.08	32.91
		NH ₃	0.05	0.22
		NO _x	9.70	42.07
		PM	1.20	5.22
		PM ₁₀	1.20	5.22
		PM _{2.5}	1.20	5.22
		SO ₂	2.49	7.45
		VOC	0.87	3.78
115	HDS Heaters	CO	8.08	32.91
		NH ₃	0.05	0.22
		NO _x	9.70	42.07
		PM	1.20	5.22
		PM ₁₀	1.20	5.22
		PM _{2.5}	1.20	5.22
		SO ₂	2.49	7.45
		VOC	0.87	3.78
116	Heater - HDS Pre-Heater (12-H-02)	CO	0.31	1.10
		NH ₃	<0.01	0.02
		NO _x	2.36	8.28
		PM	0.15	0.51
		PM ₁₀	0.15	0.51
		PM _{2.5}	0.15	0.51
		SO ₂	0.30	0.73
		VOC	0.11	0.37
118	Hydrogen Reformer Heater	CO	58.51	220.73
		NH ₃	0.37	1.52

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
		NO _x	70.21	284.40
		PM	8.72	35.80
		PM ₁₀	8.72	35.80
		PM _{2.5}	8.72	35.80
		SO ₂	44.53	122.64
		VOC	9.95	25.91
153	Heater - HR Boiler (30-B-02)	CO	8.46	28.94
		NH ₃	0.09	0.33
		NO _x	22.56	82.34
		PM	2.10	5.51
		PM ₁₀	2.10	5.51
		PM _{2.5}	2.10	5.51
		SO ₂	4.34	10.66
		VOC	1.52	3.99
30-B-04	Boiler 30-B-04	CO	19.84	48.14
		NH ₃	2.41	5.86
		NO _x	8.25	20.02
		PM	4.10	9.95
		PM ₁₀	4.10	9.95
		PM _{2.5}	4.10	9.95
		SO ₂	8.65	14.47
		VOC	2.97	7.20
30-B-04MSS	Boiler 30-B-04	CO	198.55	3.57
		NO _x	55.00	0.99
117	Heater - Alky Frac. Reb. (31-H-01)	CO	2.51	8.83
		NH ₃	0.05	0.17
		NO _x	5.64	19.86

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
		PM	1.17	4.11
		PM ₁₀	1.17	4.11
		PM _{2.5}	1.17	4.11
		SO ₂	2.41	5.86
		VOC	0.85	2.97
120	Heater - Butamer Heater (36-H-01)	CO	0.27	0.98
		NH ₃	<0.01	0.02
		NO _x	2.00	4.30
		PM	0.12	0.26
		PM ₁₀	0.12	0.26
		PM _{2.5}	0.12	0.26
		SO ₂	0.26	0.41
		VOC	0.09	0.19
162	Oleflex Heater	CO	19.45	69.49
		NH ₃	0.12	0.49
		NO _x	23.34	65.75
		PM	2.90	11.62
		PM ₁₀	2.90	11.62
		PM _{2.5}	2.90	11.62
		SO ₂	5.99	16.57
		VOC	2.10	8.41
119	Heater - Sulften Heater (46-H-01)	CO	0.35	1.49
		NH ₃	0.01	0.03
		NO _x	2.62	5.21
		PM	0.16	0.32
		PM ₁₀	0.16	0.32
		PM _{2.5}	0.16	0.32

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
		SO ₂	0.34	0.63
		VOC	0.12	0.24
150	HCU Heater	CO	6.10	24.38
		NH ₃	0.06	0.26
		NO _x	12.19	48.76
		PM	1.51	6.06
		PM ₁₀	1.51	6.06
		PM _{2.5}	1.51	6.06
		SO ₂	3.13	8.63
		VOC	1.10	4.38
151	Heater - NHU Heater (48-H-01)	CO	3.05	6.68
		NH ₃	0.01	0.05
		NO _x	3.90	17.08
		PM	0.29	1.27
		PM ₁₀	0.29	1.27
		PM _{2.5}	0.29	1.27
		SO ₂	0.60	1.81
		VOC	0.21	0.92
152	CRU Heater	CO	16.85	57.02
		NH ₃	0.18	0.60
		NO _x	39.31	133.06
		PM	4.18	14.16
		PM ₁₀	4.18	14.16
		PM _{2.5}	4.18	14.16
		SO ₂	9.80	22.69
		VOC	3.03	10.25
172	Heater - RSU Heater (49-H-71)	CO	3.30	12.72

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
		NH ₃	0.02	0.08
		NO _x	3.96	15.26
		PM	0.49	1.90
		PM ₁₀	0.49	1.90
		PM _{2.5}	0.49	1.90
		SO ₂	1.02	2.70
		VOC	0.36	1.37
49-H-90	Heater - C7 Splitter Reb. (49-H-90)	CO	5.32	16.82
		NH ₃	0.03	0.13
		NO _x	4.25	15.46
		PM	0.79	3.01
		PM ₁₀	0.79	3.01
		PM _{2.5}	0.79	3.01
		SO ₂	1.64	4.29
		VOC	0.57	2.18
195	Heater - GDU Charge Heater (52-H-01)	CO	13.65	34.29
		NH ₃	0.05	0.20
		NO _x	5.80	14.69
		PM	1.23	4.61
		PM ₁₀	1.23	4.61
		PM _{2.5}	1.23	4.61
		SO ₂	2.55	6.57
		VOC	0.89	3.34
1F	Crude Unit	VOC	See Subcap	See Subcap
2F	Vacuum Unit	H ₂ S	See Subcap	See Subcap
		VOC	See Subcap	See Subcap
4F	LEU Unit	VOC	See Subcap	See Subcap

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
11F	Desalter Unit	VOC	See Subcap	See Subcap
12F	HDS Unit	H ₂ S	See Subcap	See Subcap
		VOC	See Subcap	See Subcap
13F	H ₂ Reformer	VOC	See Subcap	See Subcap
18F	LEU -2	VOC	See Subcap	See Subcap
20F	LRU	VOC	See Subcap	See Subcap
21/22F	HOC	H ₂ S	See Subcap	See Subcap
		VOC	See Subcap	See Subcap
30F	Boiler House	VOC	See Subcap	See Subcap
07F	#07 BUP Flare	VOC	See Subcap	See Subcap
31F	Alky Unit	H ₂ S	See Subcap	See Subcap
		HF	0.52	2.30
		VOC	See Subcap	See Subcap
36F	Butamer Unit	VOC	See Subcap	See Subcap
37F	Iso-Octene	VOC	See Subcap	See Subcap
38F	Oleflex Unit	VOC	See Subcap	See Subcap
46-24F	SULF-10 Fugitives (5)	H ₂ S	See Subcap	See Subcap
		VOC	See Subcap	See Subcap
41F	SRU Unit Fugitives (5)	H ₂ S	See Subcap	See Subcap
		VOC	See Subcap	See Subcap
47F	HCU Unit	H ₂ S	See Subcap	See Subcap
		VOC	See Subcap	See Subcap
47PSA	PSA Unit	VOC	See Subcap	See Subcap
48F	NHT Unit	H ₂ S	See Subcap	See Subcap
		VOC	See Subcap	See Subcap
49F	CRU Unit	VOC	See Subcap	See Subcap
175	XFU/RFU/C7Split Unit	VOC	See Subcap	See Subcap

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
52F	GDU Unit	VOC	See Subcap	See Subcap
DOCKS	DK-Docks	VOC	See Subcap	See Subcap
08F	#08FLR/Day Tanks	VOC	See Subcap	See Subcap
LPG STGF	LPG STORAGE	VOC	See Subcap	See Subcap
MVRUF	MVRU	VOC	See Subcap	See Subcap
TERM-F	#TM-Terminal	VOC	See Subcap	See Subcap
TRKRACKFUG	TRUCK RACK (5)	VOC	See Subcap	See Subcap
83F	Wastewater Treatment Plant	VOC	See Subcap	See Subcap
54F	Selective Hydrogenation Unit	VOC	See Subcap	See Subcap
42F	Sour Water Stripper	H ₂ S	See Subcap	See Subcap
		VOC	See Subcap	See Subcap
##F	Selective Hydrogenation Unit (5)	VOC	See Subcap	See Subcap
##F	LPG Gas Plant (5)	VOC	See Subcap	See Subcap
##F	Boiler 30-B-05 (5)	VOC	See Subcap	See Subcap
168	Oleflex CCR	Cl ₂	<0.01	0.04
		H ₂ SO ₄	<0.01	0.01
		HCl	0.06	0.28
		SO ₂	0.04	0.19
69	Tank - 9	VOC	3.10	0.49
122	Cooling Tower - HOC	PM	3.54	13.17
		PM ₁₀	3.36	12.52
		PM _{2.5}	0.53	1.96
		VOC	5.67	21.09
123	Cooling Tower - Alky	PM	0.71	2.00
		PM ₁₀	0.70	1.98
		PM _{2.5}	0.19	0.55
		VOC	1.26	3.55

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
167-CT	Cooling Tower - BUP	PM	4.52	19.26
		PM ₁₀	4.30	18.33
		PM _{2.5}	0.67	2.88
		VOC	1.47	6.27
1CT	Cooling Tower - Crude	PM	0.34	1.13
		PM ₁₀	0.34	1.11
		PM _{2.5}	0.06	0.21
		VOC	0.17	0.55
16-P-04	Engine - 16-P-04	CO	2.20	0.06
		NO _x	8.00	0.21
		PM	0.73	0.02
		PM ₁₀	0.73	0.02
		PM _{2.5}	0.73	0.02
		SO ₂	0.68	0.02
		VOC	0.83	0.02
16-P-07	Engine - 16-P-07	CO	2.67	0.04
		NO _x	9.69	0.15
		PM	0.88	0.01
		PM ₁₀	0.88	0.01
		PM _{2.5}	0.88	0.01
		SO ₂	0.82	0.01
		VOC	1.01	0.02
16-P-11	Engine - 16-P-11	CO	0.80	0.02
		NO _x	3.32	0.09
		PM	0.11	<0.01
		PM ₁₀	0.11	<0.01
		PM _{2.5}	0.11	<0.01

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
		SO ₂	0.10	<0.01
		VOC	0.12	<0.01
16-P-12	Engine - 16-P-12	CO	0.80	0.02
		NO _x	3.32	0.09
		PM	0.11	<0.01
		PM ₁₀	0.11	<0.01
		PM _{2.5}	0.11	<0.01
		SO ₂	0.10	<0.01
		VOC	0.12	<0.01
16-P-13	Engine - 16-P-13	CO	0.80	0.02
		NO _x	3.32	0.09
		PM	0.11	<0.01
		PM ₁₀	0.11	<0.01
		PM _{2.5}	0.11	<0.01
		SO ₂	0.10	<0.01
		VOC	0.12	<0.01
16-P-14	Engine - 16-P-14	CO	0.80	0.02
		NO _x	3.32	0.09
		PM	0.11	<0.01
		PM ₁₀	0.11	<0.01
		PM _{2.5}	0.11	<0.01
		SO ₂	0.10	<0.01
		VOC	0.12	<0.01
126	Main Flare	CO	See Subcap	See Subcap
		H ₂ S	See Subcap	See Subcap
		NO _x	See Subcap	See Subcap
		SO ₂	See Subcap	See Subcap

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
		VOC	See Subcap	See Subcap
158	Ground Flare	CO	See Subcap	See Subcap
		H ₂ S	See Subcap	See Subcap
		NO _x	See Subcap	See Subcap
		SO ₂	See Subcap	See Subcap
		VOC	See Subcap	See Subcap
127	BUP Flare	CO	See Subcap	See Subcap
		H ₂ S	See Subcap	See Subcap
		NO _x	See Subcap	See Subcap
		SO ₂	See Subcap	See Subcap
		VOC	See Subcap	See Subcap
135	Acid Gas Flare (pilot only)	CO	See Subcap	See Subcap
		H ₂ S	See Subcap	See Subcap
		NO _x	See Subcap	See Subcap
		SO ₂	See Subcap	See Subcap
		VOC	See Subcap	See Subcap
Various	Flares Subcap	CO	113.27	121.03
		H ₂ S	0.04	0.11
		NO _x	23.04	20.77
		SO ₂	3.55	10.43
		VOC	291.17	63.51
31	Loading - Heavy Oil	VOC	14.96	4.72
SHIP FUG	Loading - Ships Fugitives (5)	VOC	237.46	91.74
VRU	Loading - MVRU	VOC	61.33	23.13
TRUCKFUG	Loading - Truck Fugitives (5)	VOC	11.86	15.87
TRUCKCOMB	Loading - Truck Combustor	CO	15.28	22.76
		NO _x	7.64	11.38

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
		SO ₂	0.02	0.03
		VOC	8.18	13.61
		PM	0.23	0.34
		PM ₁₀	0.23	0.34
		PM _{2.5}	0.23	0.34
AE-49601A/B	AE-49601A/B Analyzer Vent	VOC	0.01	0.01
AE-49900A/B	AE-49900A/B Analyzer Vent	VOC	0.01	0.01
AE-49901A/B	AE-49901A/B Analyzer Vent	VOC	0.01	0.01
121 (6)	HOC Belco Scrubber	CO	958.40	1559.15
		HCN	80.47	320.40
		H ₂ SO ₄	49.00	199.30
		NO _x	384.12	473.81
		PM	140.00	569.40
		PM ₁₀	140.00	569.40
		PM _{2.5}	140.00	569.40
		SO ₂	223.08	437.03
		VOC	30.42	123.79
		H ₂ S	<0.01	<0.01
		NH ₃	4.84	17.88
121 (6)	SRU Incinerators Cap	CO	220.75	678.85
		H ₂ S	5.82	18.73
		NO _x	54.64	239.31
		PM	24.72	98.38
		PM ₁₀	24.72	98.38
		PM _{2.5}	24.72	98.38
		SO ₂	191.32	837.99
		VOC	0.96	3.46

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
121 (6)	Temporary SRU Stack	CO	10.04	7.23
		H ₂ S	0.047	0.03
		NO _x	1.233	0.72
		PM	1.205	0.87
		PM ₁₀	1.205	0.87
		PM _{2.5}	1.205	0.87
		SO ₂	13.816	9.95
FUG-CAP	Fugitives Subcap (5)	VOC	112.45	492.32
		H ₂ S	0.59	2.58
		NH ₃	0.01	0.06
155	CRU CCR	HCl	0.07	0.29
118	SMR Condenser Vent	VOC	3.64	15.94
21 BH	MAGNACAT Unit	PM	0.18	0.60
		PM ₁₀	0.18	0.60
		PM _{2.5}	0.18	0.60
187	Tank 25	H ₂ S	0.02	0.04
		NH ₃	<0.01	<0.01
		VOC	1.43	5.33
83-P-136A	Engine 83-P-136A-EN	CO	2.48	0.06
		NO _x	7.43	0.19
		PM	0.38	<0.01
		PM ₁₀	0.38	<0.01
		PM _{2.5}	0.38	<0.01
		SO ₂	0.88	0.02
		VOC	7.43	0.19
83-P-136B	Engine 83-P-136B-EN	CO	2.48	0.06
		NO _x	7.43	0.19

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
		PM	0.38	<0.01
		PM ₁₀	0.38	<0.01
		PM _{2.5}	0.38	<0.01
		SO ₂	0.88	0.02
		VOC	7.43	0.19
WWTP-OWS	WW collection system	VOC	8.62	37.77
83-TK-26	Tank 26	VOC	0.12	0.45
83-TK-159	Tank 159	VOC	0.15	0.39
83-TK-160	Tank 160	VOC	0.15	0.39
83-V-97	Tank 97	VOC	0.18	0.40
83-V-58	Tank 58	VOC	0.11	0.44
83-V-59	Tank 59	VOC	0.11	0.44
83-TK-162	Tank 162	VOC	0.39	1.77
83-TK-155	Tank 155	VOC	0.39	1.77
124	API/DGF Combustor	CO	1.65	7.22
		NO _x	0.45	1.76
		SO ₂	0.03	0.13
		VOC	2.94	12.88
83-TK-23	Equalization Tank	VOC	0.81	3.51
83-TK27	Bio Oxidation Reactor Tank	VOC	0.51	2.22
WWTP-AERB	Aeration Basin	VOC	0.25	1.09
WWTP-CLRF	Clarifier	VOC	<0.01	0.04
WWTP-SLB	Saline Basin	VOC	<0.01	<0.01
01-01	Crude/Vacuum Unit Pump Alley	VOC	<0.01	0.02
01-02	North Side of Vacuum Unit	VOC	<0.01	0.02
01-03	North Side of Vacuum Unit	VOC	<0.01	0.02
01-04	Northwest Side of Vacuum Unit - Main Sump	VOC	<0.01	0.03

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
03-01	N of Tanks 156/161	VOC	0.02	0.08
98-02	WP MSAT Rail Rack	VOC	0.02	0.08
11-01	Desalter Pump Alley	VOC	<0.01	0.02
41-01	North of 43-TK-08 (Amine Tank)	VOC	<0.01	0.02
41-02	W of 41-V-05 (Acid Gas K.O. Drum)	VOC	<0.01	0.02
49-01	Northwest of XFU	VOC	<0.01	0.02
49-02	North Side of NHT (Unit 48)	VOC	<0.01	0.02
49-03	NHT (Unit 48) Pump Alley	VOC	<0.01	0.02
50-01	East of Tank 62	VOC	<0.01	0.02
52-01	NW of GDU MCC Room	VOC	<0.01	0.02
70-01	East of Tank 55	VOC	<0.01	0.02
70-02	Northwest of Tank 106	VOC	<0.01	0.02
70-03	West of Tank 94 (S&D Main Sump)	VOC	<0.01	0.03
72-01	East of Tank 111	VOC	<0.01	0.02
73-01	North of Tank 152 (Terminal 2A)	VOC	<0.01	0.02
73-02	Between TK 8 & TK 164 (Terminal 2)	VOC	<0.01	0.02
83-01	WWT (Hydroblast Pad)	VOC	0.02	0.07
83-02	WWT (Desalter Lift Station)	VOC	0.01	0.05
83-03	WWT (East of KOH Treater)	VOC	0.02	0.07
83-04	WWT (Northeast of Tank 159)	VOC	<0.01	0.02
83-05	WWT (North Lift Station)	VOC	<0.01	0.03
83-06	WWT (North of V-68)	VOC	<0.01	0.02
83-07	WWT (South of V-55)	VOC	<0.01	0.02
83-09	WWT (BSRP)	VOC	<0.01	0.02
83-10	WWT 83-V-99 (Diversion Box)	VOC	0.02	0.07
83-12	WWT 83-V-28 (SE of Catalyst Pad)	VOC	0.02	0.07

Emission Sources - Maximum Allowable Emission Rates

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
V-201	WP MSAT Rail Rack	VOC	0.51	2.23
124a	WP WWT API Combustor Backup	VOC	0.02	0.08
16-V-11	FWP 16-P-11 Diesel Tank	VOC	0.03	<0.01
16-V-12	FWP 16-P-12 Diesel Tank	VOC	0.03	<0.01
16-V-13	FWP 16-P-13 Diesel Tank	VOC	0.03	<0.01
16-V-14	FWP 16-P-14 Diesel Tank	VOC	0.03	<0.01
FWP-FUG	Firewater Pump Engine Fugitives	VOC	0.06	0.26
30-B-05	Boiler 30-B-05	CO	33.48	70.84
		NH ₃	2.18	8.68
		NO _x	7.16	30.14
		PM	3.56	14.16
		PM ₁₀	3.56	14.16
		PM _{2.5}	3.56	14.16
		SO ₂	11.56	38.06
		H ₂ S	<0.01	<0.01
		VOC	2.81	11.30
30-B-05	Boiler 30-B-05 (MSS)	NO _x	71.61	--
HOC-PP-CT	Cooling Tower-Propylene Project	PM	0.78	3.42
		PM ₁₀	0.18	0.81
		PM _{2.5}	<0.01	0.01
		VOC	1.09	4.78
XX-01	HOC PP Gas Plant CAS	VOC	<0.01	0.02

Emission Sources - Maximum Allowable Emission Rates

- (1) Emission point identification - either specific equipment designation or emission point number from plot plan.
- (2) Specific point source name. For fugitive sources, use area name or fugitive source name.
- (3)
 - Cl₂ - chlorine
 - CO - carbon monoxide
 - HCN - hydrogen cyanide
 - HF - hydrogen fluoride
 - H₂S - hydrogen sulfide
 - H₂SO₄ - sulfuric acid
 - MSS - Maintenance, Startup and Shutdown
 - NH₃ - ammonia
 - NO_x - total oxides of nitrogen
 - PM - total particulate matter, suspended in the atmosphere, including PM₁₀ and PM_{2.5}, as represented
 - PM₁₀ - total particulate matter equal to or less than 10 microns in diameter, including PM_{2.5}, as represented
 - PM_{2.5} - particulate matter equal to or less than 2.5 microns in diameter
 - SO₂ - sulfur dioxide
 - VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1
- (4) Compliance with annual emission limits (tons per year) is based on a 12-month rolling period.
- (5) Emission rate is an estimate and is enforceable through compliance with the applicable special condition(s) and permit application representations.

Date: Commission Issued 5/3/2024

Emission Sources - Maximum Allowable Emission Rates

Permit Number GHGPSDTX211

This table lists the maximum allowable emission rates of greenhouse gas (GHG) emissions, as defined in Title 30 Texas Administrative Code § 101.1, for all sources of GHG air contaminants on the applicant's property that are authorized by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities, sources, and related activities. Any proposed increase in emission rates may require an application for a modification of the facilities authorized by this permit.

Air Contaminants Data

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates
			TPY (4)
121	HOC Belco Scrubber	CO ₂ (5)	2,451,673.00
		CH ₄ (5)	72.08
		N ₂ O (5)	14.42
		CO ₂ e	2,457,772.00
Various (FUG-CAP)	Fugitives Subcap	CH ₄ (5)	3.59
		CO ₂ e	90.00
30-B-05	Boiler 30-B-05	CO ₂ (5)	222,364.00
		CH ₄ (5)	4.19
		N ₂ O (5)	0.42
		CO ₂ e	22,594.00

(1) Emission point identification - either specific equipment designation or emission point number from plot plan.

(2) Specific point source name. For fugitive sources, use area name or fugitive source name.

(3) CO₂ - carbon dioxide
N₂O - nitrous oxide
CH₄ - methane
CO₂e - carbon dioxide equivalents based on the following Global Warming Potentials (1/2015):
CO₂ (1), N₂O (298), CH₄(25)

(4) Compliance with annual emission limits (tons per year) is based on a 12-month rolling period. These rates include emissions from maintenance, startup, and shutdown.

(5) Emission rate is given for informational purposes only and does not constitute enforceable limit.

Date: Commission Issued 5/3/2024