

FEDERAL OPERATING PERMIT

A FEDERAL OPERATING PERMIT IS HEREBY ISSUED TO
Lion Elastomers LLC

AUTHORIZING THE OPERATION OF
Port Neches Plant
Synthetic Rubber Manufacturing

LOCATED AT
Jefferson County, Texas
Latitude 29° 59' 15" Longitude 93° 56' 42"
Regulated Entity Number: RN100224799

This permit is issued in accordance with and subject to the Texas Clean Air Act (TCAA), Chapter 382 of the Texas Health and Safety Code and Title 30 Texas Administrative Code Chapter 122 (30 TAC Chapter 122), Federal Operating Permits. Under 30 TAC Chapter 122, this permit constitutes the permit holder's authority to operate the site and emission units listed in this permit. Operations of the site and emission units listed in this permit are subject to all additional rules or amended rules and orders of the Commission pursuant to the TCAA.

This permit does not relieve the permit holder from the responsibility of obtaining New Source Review authorization for new, modified, or existing facilities in accordance with 30 TAC Chapter 116, Control of Air Pollution by Permits for New Construction or Modification.

The site and emission units authorized by this permit shall be operated in accordance with 30 TAC Chapter 122, the general terms and conditions, special terms and conditions, and attachments contained herein.

This permit shall expire five years from the date of issuance. The renewal requirements specified in 30 TAC § 122.241 must be satisfied in order to renew the authorization to operate the site and emission units.

Permit No: O1224 Issuance Date: _____

For the Commission

Table of Contents

Section	Page
General Terms and Conditions	1
Special Terms and Conditions:	1
Emission Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting.....	1
Additional Monitoring Requirements	7
New Source Review Authorization Requirements	7
Compliance Requirements.....	7
Risk Management Plan	9
Protection of Stratospheric Ozone	9
Permit Location	9
Permit Shield (30 TAC § 122.148)	9
Attachments	11
Applicable Requirements Summary.....	12
Additional Monitoring Requirements	151
Permit Shield	157
New Source Review Authorization References	159
Appendix A	171
Acronym List	172

General Terms and Conditions

The permit holder shall comply with all terms and conditions contained in 30 TAC § 122.143 (General Terms and Conditions), 30 TAC § 122.144 (Recordkeeping Terms and Conditions), 30 TAC § 122.145 (Reporting Terms and Conditions), and 30 TAC § 122.146 (Compliance Certification Terms and Conditions).

In accordance with 30 TAC § 122.144(1), records of required monitoring data and support information required by this permit, or any applicable requirement codified in this permit, are required to be maintained for a period of five years from the date of the monitoring report, sample, or application unless a longer data retention period is specified in an applicable requirement. The five year record retention period supersedes any less stringent retention requirement that may be specified in a condition of a permit identified in the New Source Review Authorization attachment.

If the permit holder chooses to demonstrate that this permit is no longer required, a written request to void this permit shall be submitted to the Texas Commission on Environmental Quality (TCEQ) by the Responsible Official in accordance with 30 TAC § 122.161(e). The permit holder shall comply with the permit's requirements, including compliance certification and deviation reporting, until notified by the TCEQ that this permit is voided.

The permit holder shall comply with 30 TAC Chapter 116 by obtaining a New Source Review authorization prior to new construction or modification of emission units located in the area covered by this permit.

All reports required by this permit must include in the submittal a cover letter which identifies the following information: company name, TCEQ regulated entity number, air account number (if assigned), site name, area name (if applicable), and Air Permits Division permit number(s).

Special Terms and Conditions:

Emission Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting

1. Permit holder shall comply with the following requirements:
 - A. Emission units (including groups and processes) in the Applicable Requirements Summary attachment shall meet the limitations, standards, equipment specifications, monitoring, recordkeeping, reporting, testing, and other requirements listed in the Applicable Requirements Summary attachment to assure compliance with the permit.
 - B. The textual description in the column titled "Textual Description" in the Applicable Requirements Summary attachment is not enforceable and is not deemed as a substitute for the actual regulatory language. The Textual Description is provided for information purposes only.
 - C. A citation listed on the Applicable Requirements Summary attachment, which has a notation [G] listed before it, shall include the referenced section and subsection for all commission rules, or paragraphs for all federal and state regulations and all subordinate paragraphs, subparagraphs and clauses, subclauses, and items contained within the referenced citation as applicable requirements.
 - D. When a grouped citation, notated with a [G] in the Applicable Requirements Summary, contains multiple compliance options, the permit holder must keep records of when each compliance option was used.
 - E. Emission units subject to 40 CFR Part 63, Subparts G, H, U, ZZZZ, and DDDDD as identified in the attached Applicable Requirements Summary table are subject to 30 TAC

Chapter 113, Subchapter C, §§ 113.120, 113.130, 113.260, 113.1090, and 113.1130 which incorporates the 40 CFR Part 63 Subpart by reference.

2. The permit holder shall comply with the following sections of 30 TAC Chapter 101 (General Air Quality Rules):
 - A. Title 30 TAC § 101.1 (relating to Definitions), insofar as the terms defined in this section are used to define the terms used in other applicable requirements
 - B. Title 30 TAC § 101.3 (relating to Circumvention)
 - C. Title 30 TAC § 101.8 (relating to Sampling), if such action has been requested by the TCEQ
 - D. Title 30 TAC § 101.9 (relating to Sampling Ports), if such action has been requested by the TCEQ
 - E. Title 30 TAC § 101.10 (relating to Emissions Inventory Requirements)
 - F. Title 30 TAC § 101.201 (relating to Emission Event Reporting and Recordkeeping Requirements)
 - G. Title 30 TAC § 101.211 (relating to Scheduled Maintenance, Start-up, and Shutdown Reporting and Recordkeeping Requirements)
 - H. Title 30 TAC § 101.221 (relating to Operational Requirements)
 - I. Title 30 TAC § 101.222 (relating to Demonstrations)
 - J. Title 30 TAC § 101.223 (relating to Actions to Reduce Excessive Emissions)
3. Permit holder shall comply with the following requirements of 30 TAC Chapter 111:
 - A. Visible emissions from stationary vents with a flow rate of less than 100,000 actual cubic feet per minute and constructed after January 31, 1972 that are not listed in the Applicable Requirements Summary attachment for 30 TAC Chapter 111, Subchapter A, Division 1, shall not exceed 20% opacity averaged over a six-minute period. The permit holder shall comply with the following requirements for stationary vents at the site subject to this standard:
 - (i) Title 30 TAC § 111.111(a)(1)(B) (relating to Requirements for Specified Sources)
 - (ii) Title 30 TAC § 111.111(a)(1)(E)
 - (iii) Title 30 TAC § 111.111(a)(1)(F)(i), (ii), (iii), or (iv)
 - (iv) For emission units with vent emissions subject to 30 TAC § 111.111(a)(1)(B), complying with 30 TAC § 111.111(a)(1)(F)(ii), (iii), or (iv), and capable of producing visible emissions from, but not limited to, particulate matter, acid gases and NO_x, the permit holder shall also comply with the following periodic monitoring requirements for the purpose of annual compliance certification under 30 TAC § 122.146. These periodic monitoring requirements do not apply to vents that are not capable of producing visible emissions such as vents that emit only colorless VOCs; vents from non-fuming liquids; vents that provide passive ventilation, such as plumbing vents; or vent emissions from any other source that

does not obstruct the transmission of light. Vents, as specified in the “Applicable Requirements Summary” attachment, that are subject to the emission limitation of 30 TAC § 111.111(a)(1)(B) are not subject to the following periodic monitoring requirements:

- (1) An observation of stationary vents from emission units in operation shall be conducted at least once during each calendar quarter unless the emission unit is not operating for the entire quarter.
- (2) For stationary vents from a combustion source, if an alternative to the normally fired fuel is fired for a period greater than or equal to 24 consecutive hours, the permit holder shall conduct an observation of the stationary vent for each such period to determine if visible emissions are present. If such period is greater than 3 months, observations shall be conducted once during each quarter. Supplementing the normally fired fuel with natural gas or fuel gas to increase the net heating value to the minimum required value does not constitute creation of an alternative fuel.
- (3) Records of all observations shall be maintained.
- (4) Visible emissions observations of emission units operated during daylight hours shall be conducted no earlier than one hour after sunrise and no later than one hour before sunset. Visible emissions observations of emission units operated only at night must be made with additional lighting and the temporary installation of contrasting backgrounds. Visible emissions observations shall be made during times when the activities described in 30 TAC § 111.111(a)(1)(E) are not taking place. Visible emissions shall be determined with each stationary vent in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 mile, away from each stationary vent during the observation. For outdoor locations, the observer shall select a position where the sun is not directly in the observer's eyes. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. A certified opacity reader is not required for visible emissions observations.
- (5) Compliance Certification:
 - (a) If visible emissions are not present during the observation, the RO may certify that the source is in compliance with the applicable opacity requirement in 30 TAC § 111.111(a)(1) and (a)(1)(B).
 - (b) However, if visible emissions are present during the observation, the permit holder shall either list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(1)(F) as soon as practicable, but no later than 24 hours after observing visible emissions to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is

determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.

- (c) Some vents may be subject to multiple visible emission or monitoring requirements. All credible data must be considered when certifying compliance with this requirement even if the observation or monitoring was performed to demonstrate compliance with a different requirement.

B. For visible emissions from a building, enclosed facility, or other structure; the permit holder shall comply with the following requirements:

- (i) Title 30 TAC § 111.111(a)(7)(A) (relating to Requirements for Specified Sources)
- (ii) Title 30 TAC § 111.111(a)(7)(B)(i) or (ii)
- (iii) For a building containing an air emission source, enclosed facility, or other structure containing or associated with an air emission source subject to 30 TAC § 111.111(a)(7)(A), complying with 30 TAC § 111.111(a)(7)(B)(i) or (ii), and capable of producing visible emissions from, but not limited to, particulate matter, acid gases and NO_x, the permit holder shall also comply with the following periodic monitoring requirements for the purpose of annual compliance certification under 30 TAC § 122.146:
 - (1) An observation of visible emissions from a building containing an air emission source, enclosed facility, or other structure containing or associated with an air emission source which is required to comply with 30 TAC § 111.111(a)(7)(A) shall be conducted at least once during each calendar quarter unless the air emission source or enclosed facility is not operating for the entire quarter.
 - (2) Records of all observations shall be maintained.
 - (3) Visible emissions observations of air emission sources or enclosed facilities operated during daylight hours shall be conducted no earlier than one hour after sunrise and no later than one hour before sunset. Visible emissions observations of air emission sources or enclosed facilities operated only at night must be made with additional lighting and the temporary installation of contrasting backgrounds. Visible emissions shall be determined with each emissions outlet in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 mile, away from each emissions outlet during the observation. For outdoor locations, the observer shall select a position where the sun is not directly in the observer's eyes. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. A certified opacity reader is not required for visible emissions observations.

- (4) Compliance Certification:
 - (a) If visible emissions are not present during the observation, the RO may certify that the source is in compliance with the applicable opacity requirement in 30 TAC § 111.111(a)(7) and (a)(7)(A).
 - (b) However, if visible emissions are present during the observation, the permit holder shall either list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(7)(B) as soon as practicable, but no later than 24 hours after observing visible emissions to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.
- C. Emission limits on nonagricultural processes, except for the steam generators specified in 30 TAC § 111.153, shall comply with the following requirements:
 - (i) Emissions of PM from any source may not exceed the allowable rates as required in 30 TAC § 111.151(a) (relating to Allowable Emissions Limits)
 - (ii) Sources with an effective stack height (h_e) less than the standard effective stack height (H_e), must reduce the allowable emission level by multiplying it by $[h_e/H_e]^2$ as required in 30 TAC § 111.151(b)
 - (iii) Effective stack height shall be calculated by the equation specified in 30 TAC § 111.151(c)
- D. Outdoor burning, as stated in 30 TAC § 111.201, shall not be authorized unless the following requirements are satisfied:
 - (i) Title 30 TAC § 111.205 (relating to Exception for Fire Training)
 - (ii) Title 30 TAC § 111.221 (relating to Responsibility for Consequences of Outdoor Burning)
4. For storage vessels maintaining working pressure as specified in 30 TAC Chapter 115, Subchapter B, Division 1: "Storage of Volatile Organic Compounds," the permit holder shall comply with the requirements of 30 TAC § 115.112(a)(1).
5. Permit holder shall comply with the following 30 TAC Chapter 115, Subchapter C requirements:
 - A. When filling stationary gasoline storage vessels (Stage I) for motor vehicle fuel dispensing facilities, constructed prior to November 15, 1992, with transfers to stationary storage tanks located at a facility which has dispensed no more than 10,000 gallons of gasoline in any calendar month after January 1, 1991, the permit holder shall comply with the following requirements specified in 30 TAC Chapter 115, Subchapter C:

- (i) Title 30 TAC § 115.222(3) (relating to Control Requirements), as it applies to liquid gasoline leaks, visible vapors, or significant odors
 - (ii) Title 30 TAC § 115.222(6) (relating to Control Requirements)
 - (iii) Title 30 TAC § 115.224(1) (relating to Inspection Requirements), as it applies to liquid gasoline leaks, visible vapors, or significant odors
 - (iv) Title 30 TAC § 115.226(2)(B) (relating to Recordkeeping Requirements)
- 6. The permit holder shall comply with the following 30 TAC Chapter 115, Subchapter F requirements (relating to Cutback Asphalt Requirements):
 - A. Title 30 TAC § 115.512(1) (relating to Control Requirements)
 - B. Title 30 TAC § 115.512(2) (relating to Control Requirements)
 - C. Title 30 TAC § 115.515 (relating to Testing Requirements)
- 7. The permit holder shall comply with the following requirements for units subject to any subpart of 40 CFR Part 60, unless otherwise stated in the applicable subpart:
 - A. Title 40 CFR § 60.7 (relating to Notification and Recordkeeping)
 - B. Title 40 CFR § 60.8 (relating to Performance Tests)
 - C. Title 40 CFR § 60.11 (relating to Compliance with Standards and Maintenance Requirements)
 - D. Title 40 CFR § 60.12 (relating to Circumvention)
 - E. Title 40 CFR § 60.13 (relating to Monitoring Requirements)
 - F. Title 40 CFR § 60.14 (relating to Modification)
 - G. Title 40 CFR § 60.15 (relating to Reconstruction)
 - H. Title 40 CFR § 60.19 (relating to General Notification and Reporting Requirements)
- 8. The permit holder shall comply with the requirements of 30 TAC Chapter 113, Subchapter C, § 113.100 for units subject to any subpart of 40 CFR Part 63, unless otherwise stated in the applicable subpart.
- 9. For elastomer product process facilities subject to maintenance wastewater requirements as specified in 40 CFR § 63.501(b), the permit holder shall comply with the requirements of 40 CFR § 63.105(b) - (e) (relating to Maintenance Wastewater Requirements) (Title 30 TAC Chapter 113, Subchapter C, § 113.260 incorporated by reference).
- 10. For the elastomer product process facilities with Group 2 wastewater streams subject to wastewater operations requirements in 40 CFR Part 63, Subpart U, the permit holder shall comply with the requirements of 40 CFR § 63.132(a), (a)(1), (a)(1)(i), and (a)(3) as specified in § 63.501(a) (Title 30 TAC Chapter 113, Subchapter C, § 113.260 incorporated by reference).

Additional Monitoring Requirements

11. The permit holder shall comply with the periodic monitoring requirements as specified in the attached "Periodic Monitoring Summary" upon issuance of the permit. Except for, as applicable, monitoring malfunctions, associated repairs, and required quality assurance or control activities (including, as applicable, calibration checks and required zero and span adjustments), the permit holder shall conduct all monitoring in continuous operation (or shall collect data at all required intervals) at all times that the pollutant-specific emissions unit is operating. The permit holder may elect to collect monitoring data on a more frequent basis and average the data, consistent with the averaging time or minimum frequency specified in the "Periodic Monitoring Summary," for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis. In no event shall data be collected and used in particular instances to avoid reporting deviations. Deviations shall be reported according to 30 TAC § 122.145 (Reporting Terms and Conditions).

New Source Review Authorization Requirements

12. Permit holder shall comply with the requirements of New Source Review authorizations issued or claimed by the permit holder for the permitted area, including permits, permits by rule (including the terms, conditions, monitoring, recordkeeping, and reporting identified in registered PBRs and permits by rule identified in the PBR Supplemental Tables dated October 11, 2023 in the application for project 35095), standard permits, flexible permits, special permits, permits for existing facilities including Voluntary Emissions Reduction Permits and Electric Generating Facility Permits issued under 30 TAC Chapter 116, Subchapter I, or special exemptions referenced in the New Source Review Authorization References attachment. These requirements:
 - A. Are incorporated by reference into this permit as applicable requirements
 - B. Shall be located with this operating permit
 - C. Are not eligible for a permit shield
13. The permit holder shall comply with the general requirements of 30 TAC Chapter 106, Subchapter A or the general requirements, if any, in effect at the time of the claim of any PBR.
14. The permit holder shall maintain records to demonstrate compliance with any emission limitation or standard that is specified in a permit by rule (PBR) or Standard Permit listed in the New Source Review Authorizations attachment. The records shall yield reliable data from the relevant time period that are representative of the emission unit's compliance with the PBR or Standard Permit. These records may include, but are not limited to, production capacity and throughput, hours of operation, safety data sheets (SDS), chemical composition of raw materials, speciation of air contaminant data, engineering calculations, maintenance records, fugitive data, performance tests, capture/control device efficiencies, direct pollutant monitoring (CEMS, COMS, or PEMS), or control device parametric monitoring. These records shall be made readily accessible and available as required by 30 TAC § 122.144. Any monitoring or recordkeeping data indicating noncompliance with the PBR or Standard Permit shall be considered and reported as a deviation according to 30 TAC § 122.145 (Reporting Terms and Conditions).

Compliance Requirements

15. The permit holder shall certify compliance in accordance with 30 TAC § 122.146. The permit holder shall comply with 30 TAC § 122.146 using at a minimum, but not limited to, the continuous or intermittent compliance method data from monitoring, recordkeeping, reporting, or testing required by the permit and any other credible evidence or information. The certification period

may not exceed 12 months and the certification must be submitted within 30 days after the end of the period being certified.

16. Permit holder shall comply with the following 30 TAC Chapter 117 requirements:
 - A. The permit holder shall comply with the compliance schedules and submit written notification to the TCEQ Executive Director as required in 30 TAC Chapter 117, Subchapter H, Division 1:
 - (i) For sources in the Beaumont-Port Arthur Nonattainment area, 30 TAC § 117.9000
 - B. The permit holder shall comply with the Initial Control Plan unit listing requirement in 30 TAC § 117.150(c) and (c)(1).
17. Use of Emission Credits to comply with applicable requirements:
 - A. Unless otherwise prohibited, the permit holder may use emission credits to comply with the following applicable requirements listed elsewhere in this permit:
 - (i) Title 30 TAC Chapter 115
 - (ii) Title 30 TAC Chapter 117
 - (iii) Offsets for Title 30 TAC Chapter 116
 - B. The permit holder shall comply with the following requirements in order to use the emission credits to comply with the applicable requirements:
 - (i) The permit holder must notify the TCEQ according to 30 TAC § 101.306(c)-(d)
 - (ii) The emission credits to be used must meet all the geographic, timeliness, applicable pollutant type, and availability requirements listed in 30 TAC Chapter 101, Subchapter H, Division 1
 - (iii) The executive director has approved the use of the credit according to 30 TAC § 101.306(c)-(d)
 - (iv) The permit holder keeps records of the use of credits towards compliance with the applicable requirements in accordance with 30 TAC § 101.302(g) and 30 TAC Chapter 122
 - (v) Title 30 TAC § 101.305 (relating to Emission Reductions Achieved Outside the United States)
18. Use of Discrete Emission Credits to comply with the applicable requirements:
 - A. Unless otherwise prohibited, the permit holder may use discrete emission credits to comply with the following applicable requirements listed elsewhere in this permit:
 - (i) Title 30 TAC Chapter 115
 - (ii) Title 30 TAC Chapter 117
 - (iii) If applicable, offsets for Title 30 TAC Chapter 116

- (iv) Temporarily exceed state NSR permit allowables
- B. The permit holder shall comply with the following requirements in order to use the credit to comply with the applicable requirements:
 - (i) The permit holder must notify the TCEQ according to 30 TAC § 101.376(d)
 - (ii) The discrete emission credits to be used must meet all the geographic, timeliness, applicable pollutant type, and availability requirements listed in 30 TAC Chapter 101, Subchapter H, Division 4
 - (iii) The executive director has approved the use of the discrete emission credits according to 30 TAC § 101.376(d)(1)(A)
 - (iv) The permit holder keeps records of the use of credits towards compliance with the applicable requirements in accordance with 30 TAC § 101.372(h) and 30 TAC Chapter 122
 - (v) Title 30 TAC § 101.375 (relating to Emission Reductions Achieved Outside the United States)

Risk Management Plan

- 19. For processes subject to 40 CFR Part 68 and specified in 40 CFR § 68.10, the permit holder shall comply with the requirements of the Accidental Release Prevention Provisions in 40 CFR Part 68. The permit holder shall submit to the appropriate agency either a compliance schedule for meeting the requirements of 40 CFR Part 68 by the date provided in 40 CFR § 68.10(a), or as part of the compliance certification submitted under this permit, a certification statement that the source is in compliance with all requirements of 40 CFR Part 68, including the registration and submission of a risk management plan.

Protection of Stratospheric Ozone

- 20. Permit holders at a site subject to Title VI of the FCAA Amendments shall meet the following requirements for protection of stratospheric ozone:
 - A. Any on site servicing, maintenance, and repair on refrigeration and nonmotor vehicle air-conditioning appliances using ozone-depleting refrigerants or non-exempt substitutes shall be conducted in accordance with 40 CFR Part 82, Subpart F. Permit holders shall ensure that repairs on or refrigerant removal from refrigeration and nonmotor vehicle air-conditioning appliances using ozone-depleting refrigerants are performed only by properly certified technicians using certified equipment. Records shall be maintained as required by 40 CFR Part 82, Subpart F.

Permit Location

- 21. The permit holder shall maintain a copy of this permit and records related to requirements listed in this permit on site.

Permit Shield (30 TAC § 122.148)

- 22. A permit shield is granted for the emission units, groups, or processes specified in the attached "Permit Shield." Compliance with the conditions of the permit shall be deemed compliance with the specified potentially applicable requirements or specified potentially applicable state-only requirements listed in the attachment "Permit Shield." Permit shield provisions shall not be

modified by the executive director until notification is provided to the permit holder. No later than 90 days after notification of a change in a determination made by the executive director, the permit holder shall apply for the appropriate permit revision to reflect the new determination. Provisional terms are not eligible for this permit shield. Any term or condition, under a permit shield, shall not be protected by the permit shield if it is replaced by a provisional term or condition or the basis of the term and condition changes.

Attachments

Applicable Requirements Summary

Additional Monitoring Requirements

Permit Shield

New Source Review Authorization References

Applicable Requirements Summary

Unit Summary 13

Applicable Requirements Summary 35

Note: A “none” entry may be noted for some emission sources in this permit’s “Applicable Requirements Summary” under the heading of “Monitoring and Testing Requirements” and/or “Recordkeeping Requirements” and/or “Reporting Requirements.” Such a notation indicates that there are no requirements for the indicated emission source as identified under the respective column heading(s) for the stated portion of the regulation when the emission source is operating under the conditions of the specified SOP Index Number. However, other relevant requirements pursuant to 30 TAC Chapter 122 including Recordkeeping Terms and Conditions (30 TAC § 122.144), Reporting Terms and Conditions (30 TAC § 122.145), and Compliance Certification Terms and Conditions (30 TAC § 122.146) continue to apply.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
39-0016	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
39-0016	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
39-0016	Storage Tanks/Vessels	N/A	Primary	40 CFR Part 63, Subpart U	No changing attributes.
40-0229	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
40-0229	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
40-0229	Storage Tanks/Vessels	N/A	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.
40-0230	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
40-0230	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
40-0230	Storage Tanks/Vessels	N/A	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.
40-0231	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
40-0231	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
40-0231	Storage Tanks/Vessels	N/A	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.
40-0232	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
40-0232	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
40-0232	Storage Tanks/Vessels	N/A	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.
40-0235	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
40-0235	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
40-0235	Storage Tanks/Vessels	N/A	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
AIRCOMP	SRIC Engines	N/A	63ZZZZ	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
AM VENT	Emission Points/Stationary Vents/Process Vents	N/A	Primary	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
BOILER 2	Boilers/Steam Generators/Steam Generating Units	N/A	60Dc-1	40 CFR Part 60, Subpart Dc	No changing attributes.
BOILER 2	Boilers/Steam Generators/Steam Generating Units	N/A	63DDDDDD	40 CFR Part 63, Subpart DDDDDD	No changing attributes.
BOILER 5	Boilers/Steam Generators/Steam Generating Units	N/A	63DDDDDD	40 CFR Part 63, Subpart DDDDDD	No changing attributes.
DOCKFLARE	Flares	N/A	Primary	30 TAC Chapter 111, Visible Emissions	No changing attributes.
EPPU 1	Chemical Manufacturing Process	N/A	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.
F-RFBASIN	Storage Tanks/Vessels	N/A	63U	40 CFR Part 63, Subpart U	No changing attributes.
F-SKIM	Storage Tanks/Vessels	N/A	63U	40 CFR Part 63, Subpart U	No changing attributes.
FWPUMP	SRIC Engines	N/A	63ZZZZ	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
GRP-BOILER	Boilers/Steam Generators/Steam Generating Units	BOILER 1, BOILER 4	63DDDDDD	40 CFR Part 63, Subpart DDDDDD	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
GRP-DRYER	Emission Points/Stationary Vents/Process Vents	S-DRYERA, S- DRYERB, S- DRYERC, S- DRYERD, S- DRYERE, S- DRYERF, S- DRYERG, S- DRYERH, S- DRYERI, S- DRYERJ, SS-12, SS-13, SS-14, SS- 16, SS-20	R1111-1	30 TAC Chapter 111, Visible Emissions	No changing attributes.
GRP-DRYER	Emission Points/Stationary Vents/Process Vents	S-DRYERA, S- DRYERB, S- DRYERC, S- DRYERD, S- DRYERE, S- DRYERF, S- DRYERG, S- DRYERH, S- DRYERI, S- DRYERJ, SS-12, SS-13, SS-14, SS- 16, SS-20	Primary	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
GRP-FUG	Fugitive Emission Units	DOCK FUGT, F- CBLK, F-MAINT BLEND, F-MAINT CARBON, F-MAINT MISC, F-MAINT SHOPS, F-MAINT- MONTF, F-MAINT- REACCA, F-MAINT- REACCB, F-MAINT- REACCC, F-MAINT- REACDA, F-MAINT- REACDB, F-MAINT- RECOVD, F-MAINT- RECV, F-MAINT- RECVCC, F- MONTF, F- REACCA, F- REACCB, F- REACCC, F- REACDA, F- REACDB, F- RECOVCA, F- RECOVCB, F- RECOVCC, F- RECOVDA, F- RECOVDB, F-WWT	R5352-ALL	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
GRP-FUG	Fugitive Emission Units	DOCK FUGT, F- CBLK, F-MAINT BLEND, F-MAINT CARBON, F-MAINT MISC, F-MAINT SHOPS, F-MAINT- MONTF, F-MAINT- REACCA, F-MAINT- REACCB, F-MAINT- REACCC, F-MAINT- REACDA, F-MAINT- REACDB, F-MAINT- RECOVD, F-MAINT- RECV, F-MAINT- RECVCC, F- MONTF, F- REACCA, F- REACCB, F- REACCC, F- REACDA, F- REACDB, F- RECOVCA, F- RECOVCB, F- RECOVCC, F- RECOVDA, F- RECOVDB, F-WWT	63H-ALL	40 CFR Part 63, Subpart H	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
GRP-FUG	Fugitive Emission Units	DOCK FUGT, F-CBLK, F-MAINT BLEND, F-MAINT CARBON, F-MAINT MISC, F-MAINT SHOPS, F-MAINT- MONTF, F-MAINT- REACCA, F-MAINT- REACCB, F-MAINT- REACCC, F-MAINT- REACDA, F-MAINT- REACDB, F-MAINT- RECOVD, F-MAINT- RECV, F-MAINT- RECVCC, F- MONTF, F- REACCA, F- REACCB, F- REACCC, F- REACDA, F- REACDB, F- RECOVCA, F- RECOVCB, F- RECOVCC, F- RECOVDA, F- RECOVDB, F-WWT	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.
GRP-MACTU	Storage Tanks/Vessels	F-7CBASIN, F- 7DBASIN, F-TFLIFT	63U	40 CFR Part 63, Subpart U	No changing attributes.
GRP-PROCVENTS	Emission Points/Stationary Vents/Process Vents	F-PACKC, F- PACKCC, F- PACKD, F- PROCESSC, F- PROCESSCC, F- PROCESSD	Primary	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
GRP-UDRYERS	Chemical Manufacturing Process	S-DRYERA, S- DRYERB, S- DRYERC, S- DRYERD, S- DRYERE, S- DRYERF, S- DRYERG, S- DRYERH, S- DRYERI, S- DRYERJ	63U	40 CFR Part 63, Subpart U	No changing attributes.
GRPAMTNK101-4	Storage Tanks/Vessels	AM ST-101, AM ST- 102, AM ST-103, AM ST-104	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
GRPAMTNK101-4	Storage Tanks/Vessels	AM ST-101, AM ST- 102, AM ST-103, AM ST-104	63G	40 CFR Part 63, Subpart G	No changing attributes.
GRPCATTNK	Storage Tanks/Vessels	T-105, V-101A, V- 101B	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
GRPCATTNK	Storage Tanks/Vessels	T-105, V-101A, V- 101B	63G	40 CFR Part 63, Subpart G	No changing attributes.
GRPDILTKB1-4	Storage Tanks/Vessels	DT-B1, DT-B2, DT- B3, DT-B4	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
GRPDILTKB1-4	Storage Tanks/Vessels	DT-B1, DT-B2, DT- B3, DT-B4	63G	40 CFR Part 63, Subpart G	No changing attributes.
GRPLTXB1-8	Storage Tanks/Vessels	T-LTX-B1, T-LTX- B2, T-LTX-B3, T- LTX-B4, T-LTX-B5, T-LTX-B6, T-LTX- B7, T-LTX-B8	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
GRPLTXB1-8	Storage Tanks/Vessels	T-LTX-B1, T-LTX-B2, T-LTX-B3, T-LTX-B4, T-LTX-B5, T-LTX-B6, T-LTX-B7, T-LTX-B8	63G	40 CFR Part 63, Subpart G	No changing attributes.
GRPLTXB1-8	Storage Tanks/Vessels	T-LTX-B1, T-LTX-B2, T-LTX-B3, T-LTX-B4, T-LTX-B5, T-LTX-B6, T-LTX-B7, T-LTX-B8	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.
GRPMST1-6	Storage Tanks/Vessels	MST-1, MST-2, MST-3, MST-4, MST-5, MST-6	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
GRPMST1-6	Storage Tanks/Vessels	MST-1, MST-2, MST-3, MST-4, MST-5, MST-6	63G	40 CFR Part 63, Subpart G	No changing attributes.
GRPMST1-6	Storage Tanks/Vessels	MST-1, MST-2, MST-3, MST-4, MST-5, MST-6	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.
GRPTK800-1-3	Storage Tanks/Vessels	TANK800, TANK801, TANK803	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
GRPTK800-1-3	Storage Tanks/Vessels	TANK800, TANK801, TANK803	63G	40 CFR Part 63, Subpart G	No changing attributes.
PAM VENT	Emission Points/Stationary Vents/Process Vents	N/A	Primary	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
PAMFUG	Fugitive Emission Units	N/A	R5352-ALL	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	No changing attributes.
PAMFUG	Fugitive Emission Units	N/A	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
PLANTFLARE	Flares	N/A	Primary	30 TAC Chapter 111, Visible Emissions	No changing attributes.
PLANTFLARE	Flares	N/A	Primary	40 CFR Part 60, Subpart A	No changing attributes.
S-7CDVENT	Emission Points/Stationary Vents/Process Vents	N/A	R5121-1	30 TAC Chapter 115, Vent Gas Controls	Control Device ID = SPLANTFLR
S-7CDVENT	Emission Points/Stationary Vents/Process Vents	N/A	R5121-2	30 TAC Chapter 115, Vent Gas Controls	Control Device ID = BACKUPFLARE
S-7CDVENT	Emission Points/Stationary Vents/Process Vents	N/A	Primary	40 CFR Part 63, Subpart U	No changing attributes.
S-BACKUPFLR	Flares	N/A	Primary	30 TAC Chapter 111, Visible Emissions	No changing attributes.
S-BACKUPFLR	Flares	N/A	Primary	40 CFR Part 60, Subpart A	No changing attributes.
S-BACKUPFLR	Flares	N/A	Primary	40 CFR Part 63, Subpart A	No changing attributes.
S-CARBLK	Emission Points/Stationary Vents/Process Vents	N/A	R1111-1	30 TAC Chapter 111, Visible Emissions	No changing attributes.
S-PROCESSCC	Emission Points/Stationary Vents/Process Vents	N/A	R1111-1	30 TAC Chapter 111, Visible Emissions	No changing attributes.
S-SUPERHEAT	Process Heaters/Furnaces	N/A	63DDDDD	40 CFR Part 63, Subpart DDDDD	No changing attributes.
SERVPUMP	SRIC Engines	N/A	63ZZZZ	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
T-AMINE	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-AMINE	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-AMINE	Storage Tanks/Vessels	N/A	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.
T-COAGID1	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
T-COAGID1	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-COAGID2	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-COAGID2	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-COAGID2	Storage Tanks/Vessels	N/A	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.
T-COAGID3	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-COAGID3	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-COAGID4	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-COAGID4	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-COAGID5	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-COAGID5	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-COAGID6	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-COAGID6	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-D/L-OIL1	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-D/L-OIL1	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-D/L-OIL1	Storage Tanks/Vessels	N/A	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.
T-D/L-OIL10	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-D/L-OIL10	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-D/L-OIL10	Storage Tanks/Vessels	N/A	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
T-D/L-OIL3	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-D/L-OIL3	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-D/L-OIL3	Storage Tanks/Vessels	N/A	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.
T-D/L-OIL7	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-D/L-OIL7	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-D/L-OIL7	Storage Tanks/Vessels	N/A	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.
T-D/L-OIL8	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-D/L-OIL8	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-D/L-OIL8	Storage Tanks/Vessels	N/A	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.
T-D/L-OIL9	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-D/L-OIL9	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-D/L-OIL9	Storage Tanks/Vessels	N/A	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.
T-DIESEL1	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-DIESEL1	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-DIESEL2	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-DIESEL2	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-DIESEL3	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-EM/MOD1	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
T-EM/MOD1	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-EM/MOD10	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-EM/MOD10	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-EM/MOD11	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-EM/MOD12	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-EM/MOD13	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-EM/MOD13	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-EM/MOD14	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-EM/MOD14	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-EM/MOD15	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-EM/MOD15	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-EM/MOD17	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-EM/MOD2	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-EM/MOD2	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-EM/MOD3	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-EM/MOD3	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-EM/MOD4	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-EM/MOD4	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
T-EM/MOD5	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-EM/MOD5	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-EM/MOD6	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-EM/MOD6	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-EM/MOD7	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-EM/MOD7	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-EM/MOD7	Storage Tanks/Vessels	N/A	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.
T-EM/MOD8	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-EM/MOD8	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-EM/MOD8	Storage Tanks/Vessels	N/A	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.
T-EM/MOD9	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-EM/MOD9	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-EM/MOD9	Storage Tanks/Vessels	N/A	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.
T-LTX-B16	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-LTX-B16	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-LTX-B16	Storage Tanks/Vessels	N/A	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.
T-LTX-B17	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-LTX-B17	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
T-LTX-B17	Storage Tanks/Vessels	N/A	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.
T-LTX-C11	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-LTX-C11	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-LTX-C11	Storage Tanks/Vessels	N/A	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.
T-LTX-C12	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-LTX-C12	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-LTX-C12	Storage Tanks/Vessels	N/A	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.
T-LTX-C13	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-LTX-C13	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-LTX-C13	Storage Tanks/Vessels	N/A	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.
T-LTX-C14	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-LTX-C14	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-LTX-C14	Storage Tanks/Vessels	N/A	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.
T-LTX-C15	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-LTX-C15	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-LTX-C15	Storage Tanks/Vessels	N/A	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.
T-LTX-C16	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-LTX-C16	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-LTX-C16	Storage Tanks/Vessels	N/A	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
T-LTX-C17	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-LTX-C17	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-LTX-C17	Storage Tanks/Vessels	N/A	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.
T-LTX-C18	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-LTX-C18	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-LTX-C18	Storage Tanks/Vessels	N/A	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.
T-LTX-C19	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-LTX-C19	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-LTX-C19	Storage Tanks/Vessels	N/A	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.
T-LTX-CC41	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-LTX-CC41	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-LTX-CC41	Storage Tanks/Vessels	N/A	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.
T-LTX-CC42	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-LTX-CC42	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-LTX-CC42	Storage Tanks/Vessels	N/A	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.
T-LTX-CC43	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-LTX-CC43	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-LTX-CC43	Storage Tanks/Vessels	N/A	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
T-LTX-CC44	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-LTX-CC44	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-LTX-CC44	Storage Tanks/Vessels	N/A	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.
T-LTX-CC45	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-LTX-CC45	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-LTX-CC45	Storage Tanks/Vessels	N/A	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.
T-LTX-CC46	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-LTX-CC46	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-LTX-CC46	Storage Tanks/Vessels	N/A	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.
T-LTX-CD	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-LTX-CD	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-LTX-CD	Storage Tanks/Vessels	N/A	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.
T-LTX-D1	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-LTX-D1	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-LTX-D1	Storage Tanks/Vessels	N/A	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.
T-LTX-D10	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-LTX-D10	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-LTX-D10	Storage Tanks/Vessels	N/A	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
T-LTX-D11	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-LTX-D11	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-LTX-D11	Storage Tanks/Vessels	N/A	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.
T-LTX-D2	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-LTX-D2	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-LTX-D2	Storage Tanks/Vessels	N/A	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.
T-LTX-D3	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-LTX-D3	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-LTX-D3	Storage Tanks/Vessels	N/A	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.
T-LTX-D4	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-LTX-D4	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-LTX-D4	Storage Tanks/Vessels	N/A	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.
T-LTX-D5	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-LTX-D5	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-LTX-D5	Storage Tanks/Vessels	N/A	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.
T-LTX-D6	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-LTX-D6	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-LTX-D6	Storage Tanks/Vessels	N/A	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
T-LTX-D7	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-LTX-D7	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-LTX-D7	Storage Tanks/Vessels	N/A	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.
T-LTX-D8	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-LTX-D8	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-LTX-D8	Storage Tanks/Vessels	N/A	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.
T-LTX-D9	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-LTX-D9	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-LTX-D9	Storage Tanks/Vessels	N/A	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.
T-MSTY1	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-MSTY1	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-SFLEX1	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-SFLEX1	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-SFLEX1	Storage Tanks/Vessels	N/A	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.
T-SFLEX10	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-SFLEX10	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-SFLEX10	Storage Tanks/Vessels	N/A	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.
T-SFLEX11	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
T-SFLEX11	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-SFLEX11	Storage Tanks/Vessels	N/A	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.
T-SFLEX2	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-SFLEX2	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-SFLEX2	Storage Tanks/Vessels	N/A	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.
T-SFLEX3	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-SFLEX3	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-SFLEX4	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-SFLEX4	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-SFLEX4	Storage Tanks/Vessels	N/A	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.
T-SFLEX5	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-SFLEX5	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-SFLEX6	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-SFLEX6	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-SFLEX7	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-SFLEX7	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-SFLEX8	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-SFLEX8	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
T-SFLEX9	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-SFLEX9	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-SGEL	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-SGEL	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-SGEL	Storage Tanks/Vessels	N/A	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.
T-SLPY1	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-SLPY1	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-SLPY2	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-SLPY2	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-SLPY3	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-SLPY3	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-SLPY4	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-SLPY4	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-SLPY5	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-SLPY5	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-SLPY6	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-SLPY6	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
T-SSTP1	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-SSTP1	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-SSTP1	Storage Tanks/Vessels	N/A	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.
T-SSTP2	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-SSTP2	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-SSTP3	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-SSTP3	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-TALLOIL1	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-TALLOIL1	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-TALLOIL1	Storage Tanks/Vessels	N/A	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.
T-TALLOIL2	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-TALLOIL2	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-TALLOIL2	Storage Tanks/Vessels	N/A	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.
T-TALLOIL3	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-TALLOIL3	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.
T-TALLOIL3	Storage Tanks/Vessels	N/A	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.
T-WGAS	Storage Tanks/Vessels	N/A	Primary	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-WGAS	Storage Tanks/Vessels	N/A	63G	40 CFR Part 63, Subpart G	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
UTILGEN2	SRIC Engines	N/A	63ZZZZ	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
XNBR-FUG	Fugitive Emission Units	B-REACMSS, F- REACB, F-RECOVB	R5352-ALL	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	No changing attributes.
XNBR-FUG	Fugitive Emission Units	B-REACMSS, F- REACB, F-RECOVB	63U-ALL	40 CFR Part 63, Subpart U	No changing attributes.

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
39-0016	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
39-0016	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
39-0016	EU	Primary	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)
40-0229	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
40-0229	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
40-0229	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)
40-0230	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
40-0230	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
40-0230	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)
40-0231	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
40-0231	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
40-0231	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)
40-0232	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
40-0232	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
40-0232	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
40-0235	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
40-0235	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
40-0235	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
AIRCOMP	EU	63ZZZZ	CO	40 CFR Part 63, Subpart ZZZZ	§ 63.6602-Table 2c.4.b § 63.6595(a)(1) § 63.6595(c) § 63.6604(a) § 63.6605(a) § 63.6605(b) § 63.6625(h) § 63.6630(a) § 63.6640(b)	For each existing non-emergency, non-black start CI stationary RICE with a site rating greater than 300 HP and less than or equal to 500 HP, located at a major source, you must reduce CO emissions by 70% or more.	§ 63.6612(a) § 63.6620(a) § 63.6620(a)-Table 4.1.a.i § 63.6620(a)-Table 4.1.a.ii § 63.6620(a)-Table 4.1.a.iii § 63.6620(b) § 63.6620(d) § 63.6620(e)(1) [G]§ 63.6620(e)(2) § 63.6630(a)-Table 5.11.a.i § 63.6635(a) § 63.6635(b) § 63.6640(b)	§ 63.6620(i) § 63.6635(a) § 63.6635(c) § 63.6655(a) § 63.6655(a)(1) § 63.6655(a)(2) § 63.6655(a)(3) § 63.6655(a)(4) § 63.6655(a)(5) § 63.6660(a) § 63.6660(b) § 63.6660(c)	§ 63.6620(i) § 63.6630(c) § 63.6640(b) § 63.6640(e) § 63.6645(a) § 63.6645(g) § 63.6645(h) § 63.6650(a) § 63.6650(a)-Table 7.1.a.i § 63.6650(a)-Table 7.1.b § 63.6650(a)-Table 7.1.c § 63.6650(b) § 63.6650(b)(1) § 63.6650(b)(2) § 63.6650(b)(3) § 63.6650(b)(4) [G]§ 63.6650(c) [G]§ 63.6650(d) § 63.6650(f)
AM VENT	EP	Primary	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(4)(C) [G]§ 115.122(a)(4)	Any reactor process or distillation operation vent gas stream with a flow rate less than 0.388 standard cubic feet per minute or a VOC concentration less than 500 ppmv is exempt from the requirements of §115.121(a)(2)(A) of this title.	[G]§ 115.125 § 115.126(2) § 115.126(3)(D)	§ 115.126 § 115.126(2) § 115.126(3) § 115.126(3)(D)	None
BOILER 2	EU	60Dc-1	PM	40 CFR Part 60, Subpart Dc	§ 60.40c(a)	This subpart applies to each steam generating unit constructed, reconstructed, or modified after 6/9/89 and that has a maximum design heat input capacity of 2.9-29 megawatts (MW).	None	§ 60.48c(g)(1) § 60.48c(g)(2) § 60.48c(g)(3) § 60.48c(i)	[G]§ 60.48c(a)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
BOILER 2	EU	60Dc-1	PM (Opacity)	40 CFR Part 60, Subpart Dc	§ 60.40c(a)	This subpart applies to each steam generating unit constructed, reconstructed, or modified after 6/9/89 and that has a maximum design heat input capacity of 2.9-29 megawatts (MW).	None	§ 60.48c(g)(1) § 60.48c(g)(2) § 60.48c(g)(3) § 60.48c(i)	[G]§ 60.48c(a)
BOILER 2	EU	60Dc-1	SO ₂	40 CFR Part 60, Subpart Dc	§ 60.40c(a)	This subpart applies to each steam generating unit constructed, reconstructed, or modified after 6/9/89 and that has a maximum design heat input capacity of 2.9-29 megawatts (MW).	None	§ 60.48c(g)(1) § 60.48c(g)(2) § 60.48c(g)(3) § 60.48c(i)	[G]§ 60.48c(a)
BOILER 2	EU	63DDDDD	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7500(a)(1)-Table 3.3 § 63.7500(a)(1) § 63.7500(a)(3) § 63.7505(a) § 63.7540(a) § 63.7540(a)(1) [G]§ 63.7540(a)(10) § 63.7540(a)(13)	A new or existing boiler or process heater without a continuous oxygen trim system and with heat input capacity of 10 million Btu per hour or greater must conduct a tune-up of the boiler or process heater annually as specified in § 63.7540. Units in either the Gas 1 or Metal Process Furnace subcategories will conduct this tune-up as a work practice for all regulated emissions.	§ 63.7515(d) [G]§ 63.7521(f) [G]§ 63.7521(g) § 63.7521(h) § 63.7521(i) § 63.7530(g) § 63.7540(a) [G]§ 63.7540(a)(10) [G]§ 63.7540(c)	§ 63.7555(a) § 63.7555(a)(1) § 63.7555(a)(2) § 63.7555(g) § 63.7555(h) § 63.7560(a) § 63.7560(b) § 63.7560(c)	[G]§ 63.7521(g) § 63.7530(e) § 63.7530(f) § 63.7545(a) § 63.7545(b) § 63.7545(c) [G]§ 63.7545(e) [G]§ 63.7545(f) § 63.7550(a) [G]§ 63.7550(b) [G]§ 63.7550(c) [G]§ 63.7550(h)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
BOILER 5	EU	63DDDDD	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7500(a)(1)-Table 3.1 § 63.7500(a)(1) § 63.7500(a)(3) § 63.7505(a) § 63.7540(a) [G]§ 63.7540(a)(10) § 63.7540(a)(12) § 63.7540(a)(13)	A new or existing boiler or process heater with a continuous oxygen trim system that maintains an optimum air to fuel ratio must conduct a tune-up of the boiler or process heater every 5 years as specified in § 63.7540.	§ 63.7515(d) § 63.7525(a)(7) § 63.7540(a) [G]§ 63.7540(a)(10)	§ 63.7555(a) § 63.7555(a)(1) § 63.7560(a) § 63.7560(b) § 63.7560(c)	§ 63.7530(e) § 63.7530(f) § 63.7545(a) § 63.7545(b) § 63.7545(c) [G]§ 63.7545(e) § 63.7550(a) [G]§ 63.7550(b) [G]§ 63.7550(c) [G]§ 63.7550(h)
DOCKFLARE	EU	Primary	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(4)(A)	Visible emissions from a process gas flare shall not be permitted for more than five minutes in any two-hour period. Non-excessive upset events are subject to the provisions under §101.222(b).	§ 111.111(a)(4)(A)(i) § 111.111(a)(4)(A)(ii)	§ 111.111(a)(4)(A)(ii)	None
EPPU 1	PRO	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.480(f)(1)(iv) § 63.480(f)(9) § 63.480(j) § 63.480(j)(1) § 63.480(j)(2) § 63.480(j)(3) § 63.480(j)(4) [G]§ 63.480(j)(4)(i) § 63.480(j)(4)(ii) § 63.506(e)(1)	If the primary product of a process unit is an elastomer product, then that process unit shall be designated as an EPPU.	§ 63.504(a) [G]§ 63.504(a)(1) § 63.504(a)(5) § 63.504(b) § 63.506(h)(1)(i) [G]§ 63.506(h)(1)(ii) § 63.506(h)(1)(iii) § 63.506(h)(1)(iv) [G]§ 63.506(h)(1)(v)	[G]§ 63.506(a) § 63.506(b) § 63.506(b)(1) [G]§ 63.506(b)(1)(i) § 63.506(h) § 63.506(h)(1) § 63.506(h)(1)(i) [G]§ 63.506(h)(1)(ii) § 63.506(h)(1)(iii) [G]§ 63.506(h)(1)(v) [G]§ 63.506(h)(1)(vi) § 63.506(h)(2) § 63.506(h)(2)(ii) § 63.506(h)(2)(iii)	§ 63.480(f)(8) § 63.480(f)(8)(i) § 63.480(f)(9) § 63.480(h)(6) § 63.480(j)(4)(ii) [G]§ 63.481(e) § 63.504(a)(4) § 63.506(b) § 63.506(b)(1) § 63.506(b)(1)(ii) § 63.506(e) [G]§ 63.506(e)(1)(iii) § 63.506(e)(2) [G]§ 63.506(e)(3)(ix) § 63.506(e)(5) [G]§ 63.506(e)(5)(i) § 63.506(e)(5)(ii) § 63.506(e)(5)(ii)(A) § 63.506(e)(5)(ii)(B) § 63.506(e)(5)(ii)(C)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
									§ 63.506(e)(5)(ii)(E) § 63.506(e)(5)(v) § 63.506(e)(5)(vi) § 63.506(e)(5)(viii) § 63.506(e)(5)(x) § 63.506(e)(5)(xii) § 63.506(e)(6) § 63.506(e)(6)(i) § 63.506(e)(6)(ii) § 63.506(e)(6)(iii) § 63.506(e)(6)(iii)(A) § 63.506(e)(6)(iii)(B) § 63.506(e)(6)(iii)(D)(2) [G]§ 63.506(e)(6)(iii)(D)(3) § 63.506(e)(6)(iii)(E) § 63.506(e)(6)(ix) [G]§ 63.506(e)(6)(v) § 63.506(e)(6)(vi) § 63.506(e)(6)(viii) § 63.506(e)(6)(x) [G]§ 63.506(e)(6)(xii) § 63.506(e)(7) § 63.506(e)(7)(iv) [G]§ 63.506(e)(7)(v) § 63.506(e)(8) § 63.506(e)(8)(ii) § 63.506(h) § 63.506(h)(1) § 63.506(h)(2)(i) § 63.506(h)(2)(ii) [G]§ 63.506(i)
F-RFBASIN	EU	63U	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
F-RFBASIN	EU	63U	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.501(a) § 63.133(a)(1) § 63.506(e)(1)	Comply with requirements of §§ 63.132-63.147 for each process wastewater stream, § 63.148 for leak inspection and § 63.149 for equipment subject to § 63.149.	None	None	§ 63.146(b)(2) § 63.146(b)(5) [G]§ 63.506(i)
F-SKIM	EU	63U	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.501(a) § 63.133(a)(1) § 63.506(e)(1)	Comply with requirements of §§ 63.132-63.147 for each process wastewater stream, § 63.148 for leak inspection and § 63.149 for equipment subject to § 63.149.	None	None	§ 63.146(b)(2) § 63.146(b)(5) [G]§ 63.506(i)
F-SKIM	EU	63U	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)
FWPUMP	EU	63ZZZZ	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6602-Table 2c.1 § 63.6595(a)(1) § 63.6605(a) § 63.6605(b) § 63.6625(e) § 63.6625(f) § 63.6625(h) § 63.6625(i) § 63.6640(f)(1) § 63.6640(f)(2) § 63.6640(f)(2)(i) § 63.6640(f)(3)	For each existing emergency stationary CI RICE and black start stationary CI RICE, located at a major source, you must comply with the requirements as specified in Table 2c.1.a-c.	§ 63.6625(i) § 63.6640(a) § 63.6640(a)-Table 6.9.a.i § 63.6640(a)-Table 6.9.a.ii	§ 63.6625(i) § 63.6655(e) § 63.6655(f) § 63.6660(a) § 63.6660(b) § 63.6660(c)	§ 63.6640(e) § 63.6650(f)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-BOILER	EU	63DDDDD	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7500(a)(1)-Table 3.3 § 63.7500(a)(1) § 63.7500(a)(3) § 63.7505(a) § 63.7540(a) § 63.7540(a)(1) [G]§ 63.7540(a)(10) § 63.7540(a)(13)	A new or existing boiler or process heater without a continuous oxygen trim system and with heat input capacity of 10 million Btu per hour or greater must conduct a tune-up of the boiler or process heater annually as specified in § 63.7540. Units in either the Gas 1 or Metal Process Furnace subcategories will conduct this tune-up as a work practice for all regulated emissions.	§ 63.7515(d) [G]§ 63.7521(f) [G]§ 63.7521(g) § 63.7521(h) § 63.7521(i) § 63.7530(g) § 63.7540(a) [G]§ 63.7540(a)(10) [G]§ 63.7540(c)	§ 63.7555(a) § 63.7555(a)(1) § 63.7555(a)(2) § 63.7555(g) § 63.7555(h) § 63.7560(a) § 63.7560(b) § 63.7560(c)	[G]§ 63.7521(g) § 63.7530(e) § 63.7530(f) § 63.7545(a) § 63.7545(b) § 63.7545(c) [G]§ 63.7545(e) [G]§ 63.7545(f) § 63.7550(a) [G]§ 63.7550(b) [G]§ 63.7550(c) [G]§ 63.7550(h)
GRP-DRYER	EP	R1111-1	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(A) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall not exceed an opacity of 30% averaged over a six minute period.	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None
GRP-DRYER	EP	Primary	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(B) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream specified in §115.121(a)(1) of this title with a concentration of VOC less than 612 parts per million by volume (ppmv) is exempt from §115.121(a)(1) of this title.	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(2) § 115.352(9)	Conservation vents or other devices on atmospheric storage tanks that are actuated either by a vacuum or a pressure of no more than 2.5 psig, pressure relief valves equipped with a rupture disk or venting to a control device, components in continuous vacuum service, and valves that are not externally regulated (such as in-line check valves) are exempt from the requirements of this division, except that each pressure relief valve equipped with a rupture disk must comply with §115.352(9) and §115.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
GRP-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(8) § 115.357(9)	No valves contacting a fluid with TVP less than or equal to 0.044 psia (heavy liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(C) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(8) § 115.358(c)(1) [G]§ 115.358(h)	If the owner or operator elects to use the alternative work practice in §115.358, no component shall be allowed to have a VOC leak, detected as defined in §115.358, for more than 15 days after discovery. This includes any leak detected using the alternative work practice on a component that is subject to the requirements of this division but not specifically selected for alternative work practice monitoring.	§ 115.354(1) § 115.354(11) § 115.354(13)(A) § 115.354(13)(B) § 115.354(13)(C) § 115.354(13)(D) § 115.354(13)(E) § 115.354(13)(F) § 115.354(4) § 115.354(5) § 115.354(9) [G]§ 115.355 § 115.358(c)(2) § 115.358(d) [G]§ 115.358(e) § 115.358(f)	§ 115.352(7) § 115.354(13)(D) § 115.354(13)(E) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) [G]§ 115.356(4) § 115.356(5)	[G]§ 115.358(g)
GRP-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	No pump seals contacting a fluid with TVP greater than 0.044 psia (gas/vapor or light liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1) § 115.357(8)	No pump seals contacting a fluid with TVP less than or equal to 0.044 psia (heavy liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None
GRP-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(4) § 115.357(8)	No pump seals that are equipped with a shaft sealing system that prevents or detects emissions of VOCs from the seal shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	No compressor seals contacting a fluid with TVP greater than 0.044 psia (gas/vapor or light liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
GRP-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1) § 115.357(8)	No compressor seals contacting a fluid with TVP less than or equal to 0.044 psia (heavy liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(4) § 115.357(8)	No compressor seals that are equipped with a shaft sealing system that prevents or detects emissions of VOCs from the seal shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None
GRP-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(3) § 115.357(8)	No compressor seals in hydrogen service with and the hydrogen content can be expected to always exceed 50.0% by volume shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(7) § 115.357(8)	No agitators contacting a fluid with TVP greater than 0.044 psia (gas/vapor or light liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
GRP-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(7) § 115.357(1) § 115.357(8)	No agitators contacting a fluid with TVP less than or equal to 0.044 psia (heavy liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	[G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(8) § 115.357(12) § 115.357(8)	No flanges or other connectors contacting a fluid with TVP greater than 0.044 psia (gas/vapor or light liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
GRP-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(8) § 115.357(1) § 115.357(12) § 115.357(8)	No flanges or other connectors contacting a fluid with TVP less than or equal to 0.044 psia (heavy liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8) § 115.357(9)	No valves contacting a fluid with TVP greater than 0.044 psia (gas/vapor or light liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
GRP-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8) § 115.357(9)	No open-ended valves or lines contacting a fluid with TVP greater than 0.044 psia (gas/vapor or light liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
GRP-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(5)	Reciprocating compressors and positive displacement pumps used in natural gas/gasoline processing operations are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(10)	Instrumentation systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet 40 CFR §63.169 (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
GRP-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(11)	Sampling connection systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet the requirements of 40 CFR §63.166(a) and (b) (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
GRP-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(13)	Components/systems that contact a process fluid containing VOC having a true vapor pressure equal to or less than 0.002 psia at 68 degrees Fahrenheit are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(6)	Components at a petroleum refinery or synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process, that contact a process fluid that contains less than 10% VOC by weight are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
GRP-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7) § 115.357(1)	No process drains contacting a fluid with TVP less than or equal to 0.044 psia (heavy liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7)	No process drains contacting a fluid with TVP greater than 0.044 psia (gas/vapor or light liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(5)	None
GRP-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(9) § 115.357(1) § 115.357(8) § 115.357(9)	No pressure relief valves contacting a fluid with TVP less than or equal to 0.044 psia (heavy liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(9) § 115.357(12) § 115.357(8) § 115.357(9)	No pressure relief valves contacting a fluid with TVP greater than 0.044 psia (gas/vapor or light liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
GRP-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(8) § 115.357(9)	No open-ended valves or lines contacting a fluid with TVP less than or equal to 0.044 psia (heavy liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
GRP-FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.164 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Compressors. §63.164(a)-(i)	[G]§ 63.164 [G]§ 63.180(b) [G]§ 63.180(c) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(f)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.166 § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Sampling connection systems. §63.166(a)-(c)	[G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
GRP-FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.165 § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Pressure relief device in gas/vapor service. §63.165(a)-(d)	[G]§ 63.165 [G]§ 63.180(b) [G]§ 63.180(c) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(f)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
GRP-FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.168 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.175	Standards: Valves in gas/vapor service and in light liquid service. §63.168(a)-(j)	[G]§ 63.168 [G]§ 63.175 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
GRP-FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.167 § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.175	Standards: Open-ended valves or lines. §63.167(a)-(e).	[G]§ 63.175 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.163 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.176	Standards: Pumps in light liquid service. §63.163(a)-(j)	[G]§ 63.163 [G]§ 63.176 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(3) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(8)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
GRP-FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.174 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Connectors in gas/vapor service and in light liquid service. §63.174(a)-(j)	[G]§ 63.174 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
GRP-FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.173 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Agitators gas/vapor service and in light liquid service. §63.173(a)-(j).	[G]§ 63.173 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
GRP-FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	§ 63.170 § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Surge control vessels and bottom receivers.	[G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Pressure relief devices in liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
GRP-FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Instrumentation systems. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
GRP-FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Agitators in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
GRP-FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Connectors in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
GRP-FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Valves in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Pumps in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
GRP-FUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	§ 63.162(e) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h)	Equipment that is in organic HAP service less than 300 hours per year is excluded from the requirements of §§63.163 - 63.174 and §63.178 if it is identified as required in §63.181(j).	[G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(i) § 63.181(j)	[G]§ 63.182(a) [G]§ 63.182(b)
GRP-FUG	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.502(a) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.165 [G]§ 63.171 [G]§ 63.481(m) § 63.506(e)(1)	The owner or operator of each affected source, shall comply with the requirements of subpart H for pressure relief devices in gas/vapor service, with exceptions noted in paragraphs (b)-(m) of § 63.502.	[G]§ 63.165 [G]§ 63.180(b) [G]§ 63.180(c) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4) [G]§ 63.502(j)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(f)	§ 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d) § 63.502(f) § 63.502(g) [G]§ 63.506(i)
GRP-FUG	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.502(a) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.168 [G]§ 63.171 [G]§ 63.175 [G]§ 63.481(m) § 63.506(e)(1)	The owner or operator of each affected source, shall comply with the requirements of subpart H for valves in light liquid or gas/vapor service, with exceptions noted in paragraphs (b)-(m) of § 63.502.	[G]§ 63.168 [G]§ 63.175 [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4) [G]§ 63.502(j)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(9)	§ 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) [G]§ 63.182(c)(4) [G]§ 63.182(d) § 63.502(f) § 63.502(g) [G]§ 63.506(i)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-FUG	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.502(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 [G]§ 63.481(m) § 63.502(d) § 63.502(d)(2) § 63.506(e)(1)	The owner or operator of each affected source, shall comply with the requirements of subpart H for pumps in heavy liquid service, with exceptions noted in paragraphs (b)-(m) of § 63.502.	[G]§ 63.169 [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4) [G]§ 63.502(j)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	§ 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d) § 63.502(f) § 63.502(g) [G]§ 63.506(i)
GRP-FUG	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.502(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 [G]§ 63.481(m) § 63.506(e)(1)	The owner or operator of each affected source, shall comply with the requirements of subpart H for valves in heavy liquid service, with exceptions noted in paragraphs (b)-(m) of § 63.502.	[G]§ 63.169 [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4) [G]§ 63.502(j)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	§ 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d) § 63.502(f) § 63.502(g) [G]§ 63.506(i)
GRP-FUG	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.502(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 [G]§ 63.481(m) § 63.506(e)(1)	The owner or operator of each affected source, shall comply with the requirements of subpart H for connectors in heavy liquid service, with exceptions noted in paragraphs (b)-(m) of § 63.502.	[G]§ 63.169 [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4) [G]§ 63.502(j)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	§ 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d) § 63.502(f) § 63.502(g) [G]§ 63.506(i)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-FUG	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.502(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 [G]§ 63.481(m) § 63.506(e)(1)	The owner or operator of each affected source, shall comply with the requirements of subpart H for agitators in heavy liquid service, with exceptions noted in paragraphs (b)-(m) of § 63.502.	[G]§ 63.169 [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4) [G]§ 63.502(j)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	§ 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d) § 63.502(f) § 63.502(g) [G]§ 63.506(i)
GRP-FUG	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.502(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 [G]§ 63.481(m) § 63.506(e)(1)	The owner or operator of each affected source, shall comply with the requirements of subpart H for instrumentation systems, with exceptions noted in paragraphs (b)-(m) of § 63.502.	[G]§ 63.169 [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4) [G]§ 63.502(j)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	§ 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d) § 63.502(f) § 63.502(g) [G]§ 63.506(i)
GRP-FUG	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.502(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 [G]§ 63.481(m) § 63.506(e)(1)	The owner or operator of each affected source, shall comply with the requirements of subpart H for pressure relief devices in liquid service, with exceptions noted in paragraphs (b)-(m) of § 63.502.	[G]§ 63.169 [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4) [G]§ 63.502(j)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	§ 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d) § 63.502(f) § 63.502(g) [G]§ 63.506(i)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-FUG	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.502(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.173 [G]§ 63.481(m) § 63.506(e)(1)	The owner or operator of each affected source, shall comply with the requirements of subpart H for agitators in gas/vapor or light liquid service, with exceptions noted in paragraphs (b)-(m) of § 63.502.	[G]§ 63.173 [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4) [G]§ 63.502(j)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	§ 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d) § 63.502(f) § 63.502(g) [G]§ 63.506(i)
GRP-FUG	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.502(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.174 [G]§ 63.481(m) § 63.506(e)(1)	The owner or operator of each affected source, shall comply with the requirements of subpart H for connectors in gas/vapor or light liquid service, with exceptions noted in paragraphs (b)-(m) of § 63.502.	[G]§ 63.174 [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4) [G]§ 63.502(j)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	§ 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d) § 63.502(f) § 63.502(g) [G]§ 63.506(i)
GRP-FUG	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.502(a) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.166 [G]§ 63.171 [G]§ 63.481(m) § 63.502(i) § 63.506(e)(1)	The owner or operator of each affected source, shall comply with the requirements of subpart H for sampling connection system, with exceptions noted in paragraphs (b)-(m) of § 63.502.	[G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4) [G]§ 63.502(j)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c)	§ 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d) § 63.502(f) § 63.502(g) [G]§ 63.506(i)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-FUG	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.502(a) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.167 [G]§ 63.171 [G]§ 63.175 [G]§ 63.481(m) § 63.506(e)(1)	The owner or operator of each affected source, shall comply with the requirements of subpart H for open-ended valves and lines, with exceptions noted in paragraphs (b)-(m) of § 63.502.	[G]§ 63.175 [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4) [G]§ 63.502(j)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(8) § 63.181(h)(9)	§ 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d) § 63.502(f) § 63.502(g) [G]§ 63.506(i)
GRP-FUG	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.502(a) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.163 [G]§ 63.171 [G]§ 63.176 [G]§ 63.481(m) § 63.502(d) § 63.502(d)(1) § 63.502(d)(3) § 63.506(e)(1)	The owner or operator of each affected source, shall comply with the requirements of subpart H for pumps in light liquid service, with exceptions noted in paragraphs (b)-(m) of § 63.502.	[G]§ 63.163 [G]§ 63.176 [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4) [G]§ 63.502(j)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(3) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(8) § 63.181(h)(9)	§ 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d) § 63.502(f) § 63.502(g) [G]§ 63.506(i)
GRP-FUG	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.502(a) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.164 [G]§ 63.171 [G]§ 63.481(m) § 63.506(e)(1)	The owner or operator of each affected source, shall comply with the requirements of subpart H for compressors, with exceptions noted in paragraphs (b)-(m) of § 63.502.	[G]§ 63.164 [G]§ 63.180(b) [G]§ 63.180(c) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4) [G]§ 63.502(j)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(f)	§ 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d) § 63.502(f) § 63.502(g) [G]§ 63.506(i)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-MACTU	EU	63U	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.501(a) § 63.133(a)(1) § 63.506(e)(1)	Comply with requirements of §§ 63.132-63.147 for each process wastewater stream, § 63.148 for leak inspection and § 63.149 for equipment subject to § 63.149.	None	None	§ 63.146(b)(2) § 63.146(b)(5) [G]§ 63.506(i)
GRP-MACTU	EU	63U	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)
GRP-PROCVENT S	EP	Primary	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(B) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream specified in §115.121(a)(1) of this title with a concentration of VOC less than 612 parts per million by volume (ppmv) is exempt from §115.121(a)(1) of this title.	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRP-UDRYERS	PRO	63U	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.494(a) [G]§ 63.481(m) § 63.494(a)(1)(i) [G]§ 63.494(a)(4) § 63.495(a) § 63.495(g) § 63.495(g)(1) [G]§ 63.495(g)(2) § 63.495(g)(4) § 63.495(g)(5) § 63.498(a)(4) § 63.500(a) § 63.500(a)(1) § 63.500(a)(3) § 63.505(j) § 63.506(e)(1)	The monthly weighted average residual organic HAP content of all grades of elastomer processed, measured as specified, shall not exceed the limits provided in § 63.494(a)(1)-(a)(4).	§ 63.495(b)(2)(ii) § 63.495(b)(4) § 63.495(b)(5) [G]§ 63.495(d)(1) [G]§ 63.495(e) § 63.495(f) § 63.500(c) § 63.500(c)(2) § 63.500(c)(2)(i) § 63.500(c)(2)(ii) § 63.500(c)(2)(iii) [G]§ 63.500(c)(2)(iv) § 63.500(e)(2)(i) § 63.506(d)(1) § 63.506(d)(3) § 63.506(d)(3)(i)	§ 63.495(b)(4) § 63.495(g)(1) [G]§ 63.495(g)(2) § 63.495(g)(3) § 63.495(g)(4) § 63.495(g)(5) § 63.498(a) § 63.498(a)(1) § 63.498(a)(2) § 63.498(a)(3) § 63.498(b) § 63.498(b)(1) § 63.498(b)(1)(i) § 63.498(b)(1)(ii) § 63.498(b)(1)(iii) § 63.498(b)(1)(iii)(A) § 63.498(b)(1)(iv) § 63.498(b)(2) § 63.498(b)(3) § 63.498(e) § 63.500(c)(2)(v) [G]§ 63.500(d) § 63.506(d) § 63.506(d)(2) § 63.506(d)(6) [G]§ 63.506(d)(7) § 63.506(d)(8)	§ 63.495(g)(1) § 63.495(g)(5) [G]§ 63.499(a) § 63.499(f) § 63.500(e) § 63.500(e)(1) § 63.500(e)(2)(ii) § 63.505(j) § 63.506(e)(6)(iii)(D)(4) [G]§ 63.506(i)
GRPAMTNK 101-4	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRPAMTNK 101-4	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
GRPCATTN K	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
GRPCATTN K	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
GRPDILTKB 1-4	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
GRPDILTKB 1-4	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRPLTXB1-8	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
GRPLTXB1-8	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
GRPLTXB1-8	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)
GRPMST1-6	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
GRPMST1-6	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRPMST1-6	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)
GRPTK800-1-3	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
GRPTK800-1-3	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
PAM VENT	EP	Primary	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(B) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream specified in §115.121(a)(1) of this title with a concentration of VOC less than 612 parts per million by volume (ppmv) is exempt from §115.121(a)(1) of this title.	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
PAMFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(5)	Reciprocating compressors and positive displacement pumps used in natural gas/gasoline processing operations are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
PAMFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(10)	Instrumentation systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet 40 CFR §63.169 (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
PAMFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(11)	Sampling connection systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet the requirements of 40 CFR §63.166(a) and (b) (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
PAMFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(13)	Components/systems that contact a process fluid containing VOC having a true vapor pressure equal to or less than 0.002 psia at 68 degrees Fahrenheit are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
PAMFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(6)	Components at a petroleum refinery or synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process, that contact a process fluid that contains less than 10% VOC by weight are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
PAMFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(2) § 115.352(9)	Conservation vents or other devices on atmospheric storage tanks that are actuated either by a vacuum or a pressure of no more than 2.5 psig, pressure relief valves equipped with a rupture disk or venting to a control device, components in continuous vacuum service, and valves that are not externally regulated (such as in-line check valves) are exempt from the requirements of this division, except that each pressure relief valve equipped with a rupture disk must comply with §115.352(9) and §115.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
PAMFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7) § 115.357(1)	No process drains contacting a fluid with TVP less than or equal to 0.044 psia (heavy liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
PAMFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7)	No process drains contacting a fluid with TVP greater than 0.044 psia (gas/vapor or light liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
PAMFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(9) § 115.357(1) § 115.357(8) § 115.357(9)	No pressure relief valves contacting a fluid with TVP less than or equal to 0.044 psia (heavy liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
PAMFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(9) § 115.357(12) § 115.357(8) § 115.357(9)	No pressure relief valves contacting a fluid with TVP greater than 0.044 psia (gas/vapor or light liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
PAMFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(8) § 115.357(9)	No open-ended valves or lines contacting a fluid with TVP less than or equal to 0.044 psia (heavy liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
PAMFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8) § 115.357(9)	No open-ended valves or lines contacting a fluid with TVP greater than 0.044 psia (gas/vapor or light liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
PAMFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8) § 115.357(9)	No valves contacting a fluid with TVP greater than 0.044 psia (gas/vapor or light liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
PAMFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(8) § 115.357(1) § 115.357(12) § 115.357(8)	No flanges or other connectors contacting a fluid with TVP less than or equal to 0.044 psia (heavy liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
PAMFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(8) § 115.357(12) § 115.357(8)	No flanges or other connectors contacting a fluid with TVP greater than 0.044 psia (gas/vapor or light liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
PAMFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(7) § 115.357(1) § 115.357(8)	No agitators contacting a fluid with TVP less than or equal to 0.044 psia (heavy liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	[G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
PAMFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(7) § 115.357(8)	No agitators contacting a fluid with TVP greater than 0.044 psia (gas/vapor or light liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
PAMFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(3) § 115.357(8)	No compressor seals in hydrogen service with and the hydrogen content can be expected to always exceed 50.0% by volume shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
PAMFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(4) § 115.357(8)	No compressor seals that are equipped with a shaft sealing system that prevents or detects emissions of VOCs from the seal shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None
PAMFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1) § 115.357(8)	No compressor seals contacting a fluid with TVP less than or equal to 0.044 psia (heavy liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
PAMFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	No compressor seals contacting a fluid with TVP greater than 0.044 psia (gas/vapor or light liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
PAMFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(4) § 115.357(8)	No pump seals that are equipped with a shaft sealing system that prevents or detects emissions of VOCs from the seal shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
PAMFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1) § 115.357(8)	No pump seals contacting a fluid with TVP less than or equal to 0.044 psia (heavy liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None
PAMFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	No pump seals contacting a fluid with TVP greater than 0.044 psia (gas/vapor or light liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
PAMFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(C) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(8) § 115.358(c)(1) [G]§ 115.358(h)	If the owner or operator elects to use the alternative work practice in §115.358, no component shall be allowed to have a VOC leak, detected as defined in §115.358, for more than 15 days after discovery. This includes any leak detected using the alternative work practice on a component that is subject to the requirements of this division but not specifically selected for alternative work practice monitoring.	§ 115.354(1) § 115.354(11) § 115.354(13)(A) § 115.354(13)(B) § 115.354(13)(C) § 115.354(13)(D) § 115.354(13)(E) § 115.354(13)(F) § 115.354(4) § 115.354(5) § 115.354(9) [G]§ 115.355 § 115.358(c)(2) § 115.358(d) [G]§ 115.358(e) § 115.358(f)	§ 115.352(7) § 115.354(13)(D) § 115.354(13)(E) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) [G]§ 115.356(4) § 115.356(5)	[G]§ 115.358(g)
PAMFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(8) § 115.357(9)	No valves contacting a fluid with TVP less than or equal to 0.044 psia (heavy liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
PAMFUG	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.502(a) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.166 [G]§ 63.171 [G]§ 63.481(m) § 63.502(i) § 63.506(e)(1)	The owner or operator of each affected source, shall comply with the requirements of subpart H for sampling connection system, with exceptions noted in paragraphs (b)-(m) of § 63.502.	[G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4) [G]§ 63.502(j)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c)	§ 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d) § 63.502(f) § 63.502(g) [G]§ 63.506(i)
PAMFUG	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.502(a) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.167 [G]§ 63.171 [G]§ 63.175 [G]§ 63.481(m) § 63.506(e)(1)	The owner or operator of each affected source, shall comply with the requirements of subpart H for open-ended valves and lines, with exceptions noted in paragraphs (b)-(m) of § 63.502.	[G]§ 63.175 [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4) [G]§ 63.502(j)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(8) § 63.181(h)(9)	§ 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d) § 63.502(f) § 63.502(g) [G]§ 63.506(i)
PAMFUG	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.502(a) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.163 [G]§ 63.171 [G]§ 63.176 [G]§ 63.481(m) § 63.502(d) § 63.502(d)(1) § 63.502(d)(3) § 63.506(e)(1)	The owner or operator of each affected source, shall comply with the requirements of subpart H for pumps in light liquid service, with exceptions noted in paragraphs (b)-(m) of § 63.502.	[G]§ 63.163 [G]§ 63.176 [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4) [G]§ 63.502(j)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(3) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(8) § 63.181(h)(9)	§ 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d) § 63.502(f) § 63.502(g) [G]§ 63.506(i)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
PAMFUG	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.502(a) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.164 [G]§ 63.171 [G]§ 63.481(m) § 63.506(e)(1)	The owner or operator of each affected source, shall comply with the requirements of subpart H for compressors, with exceptions noted in paragraphs (b)-(m) of § 63.502.	[G]§ 63.164 [G]§ 63.180(b) [G]§ 63.180(c) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4) [G]§ 63.502(j)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(f)	§ 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d) § 63.502(f) § 63.502(g) [G]§ 63.506(i)
PAMFUG	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.502(a) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.165 [G]§ 63.171 [G]§ 63.481(m) § 63.506(e)(1)	The owner or operator of each affected source, shall comply with the requirements of subpart H for pressure relief devices in gas/vapor service, with exceptions noted in paragraphs (b)-(m) of § 63.502.	[G]§ 63.165 [G]§ 63.180(b) [G]§ 63.180(c) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4) [G]§ 63.502(j)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(f)	§ 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d) § 63.502(f) § 63.502(g) [G]§ 63.506(i)
PAMFUG	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.502(a) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.168 [G]§ 63.171 [G]§ 63.175 [G]§ 63.481(m) § 63.506(e)(1)	The owner or operator of each affected source, shall comply with the requirements of subpart H for valves in light liquid or gas/vapor service, with exceptions noted in paragraphs (b)-(m) of § 63.502.	[G]§ 63.168 [G]§ 63.175 [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4) [G]§ 63.502(j)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(9)	§ 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d) § 63.502(f) § 63.502(g) [G]§ 63.506(i)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
PAMFUG	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.502(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 [G]§ 63.481(m) § 63.502(d) § 63.502(d)(2) § 63.506(e)(1)	The owner or operator of each affected source, shall comply with the requirements of subpart H for pumps in heavy liquid service, with exceptions noted in paragraphs (b)-(m) of § 63.502.	[G]§ 63.169 [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4) [G]§ 63.502(j)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	§ 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d) § 63.502(f) § 63.502(g) [G]§ 63.506(i)
PAMFUG	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.502(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 [G]§ 63.481(m) § 63.506(e)(1)	The owner or operator of each affected source, shall comply with the requirements of subpart H for valves in heavy liquid service, with exceptions noted in paragraphs (b)-(m) of § 63.502.	[G]§ 63.169 [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4) [G]§ 63.502(j)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	§ 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d) § 63.502(f) § 63.502(g) [G]§ 63.506(i)
PAMFUG	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.502(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 [G]§ 63.481(m) § 63.506(e)(1)	The owner or operator of each affected source, shall comply with the requirements of subpart H for connectors in heavy liquid service, with exceptions noted in paragraphs (b)-(m) of § 63.502.	[G]§ 63.169 [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4) [G]§ 63.502(j)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	§ 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d) § 63.502(f) § 63.502(g) [G]§ 63.506(i)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
PAMFUG	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.502(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 [G]§ 63.481(m) § 63.506(e)(1)	The owner or operator of each affected source, shall comply with the requirements of subpart H for agitators in heavy liquid service, with exceptions noted in paragraphs (b)-(m) of § 63.502.	[G]§ 63.169 [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4) [G]§ 63.502(j)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	§ 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d) § 63.502(f) § 63.502(g) [G]§ 63.506(i)
PAMFUG	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.502(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 [G]§ 63.481(m) § 63.506(e)(1)	The owner or operator of each affected source, shall comply with the requirements of subpart H for instrumentation systems, with exceptions noted in paragraphs (b)-(m) of § 63.502.	[G]§ 63.169 [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4) [G]§ 63.502(j)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	§ 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d) § 63.502(f) § 63.502(g) [G]§ 63.506(i)
PAMFUG	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.502(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 [G]§ 63.481(m) § 63.506(e)(1)	The owner or operator of each affected source, shall comply with the requirements of subpart H for pressure relief devices in liquid service, with exceptions noted in paragraphs (b)-(m) of § 63.502.	[G]§ 63.169 [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4) [G]§ 63.502(j)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	§ 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d) § 63.502(f) § 63.502(g) [G]§ 63.506(i)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
PAMFUG	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.502(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.173 [G]§ 63.481(m) § 63.506(e)(1)	The owner or operator of each affected source, shall comply with the requirements of subpart H for agitators in gas/vapor or light liquid service, with exceptions noted in paragraphs (b)-(m) of § 63.502.	[G]§ 63.173 [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4) [G]§ 63.502(j)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	§ 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d) § 63.502(f) § 63.502(g) [G]§ 63.506(i)
PAMFUG	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.502(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.174 [G]§ 63.481(m) § 63.506(e)(1)	The owner or operator of each affected source, shall comply with the requirements of subpart H for connectors in gas/vapor or light liquid service, with exceptions noted in paragraphs (b)-(m) of § 63.502.	[G]§ 63.174 [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4) [G]§ 63.502(j)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	§ 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d) § 63.502(f) § 63.502(g) [G]§ 63.506(i)
PLANTFLARE	EU	Primary	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(4)(A)	Visible emissions from a process gas flare shall not be permitted for more than five minutes in any two-hour period. Non-excessive upset events are subject to the provisions under §101.222(b).	§ 111.111(a)(4)(A)(i) § 111.111(a)(4)(A)(ii)	§ 111.111(a)(4)(A)(ii)	None
PLANTFLARE	CD	Primary	Opacity	40 CFR Part 60, Subpart A	§ 60.18(b) § 60.18(c)(1) § 60.18(c)(2) § 60.18(c)(3)(ii) § 60.18(c)(4)(i) § 60.18(c)(6) § 60.18(e)	Flares shall comply with paragraphs (c)-(f) of § 60.18.	§ 60.18(d) § 60.18(f)(1) § 60.18(f)(2) § 60.18(f)(3) § 60.18(f)(4)	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
S-7CDVENT	EP	R5121-1	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(a)(1) § 115.121(a)(1) § 115.122(a)(1)(B) § 60.18	Vent gas streams affected by §115.121(a)(1) must be controlled properly with a control efficiency of at least 90% or to a volatile organic compound (VOC) concentration of no more than 20 parts per million (ppmv) (on a dry basis corrected to 3.0% oxygen for combustion devices).	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None
S-7CDVENT	EP	R5121-2	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.122(a)(1) § 115.121(a)(1) § 115.122(a)(1)(B) § 60.18	Vent gas streams affected by §115.121(a)(1) must be controlled properly with a control efficiency of at least 90% or to a volatile organic compound (VOC) concentration of no more than 20 parts per million (ppmv) (on a dry basis corrected to 3.0% oxygen for combustion devices).	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2)	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None
S-7CDVENT	PRO	Primary	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.485(a) [G]§ 63.113(a)(1) § 63.113(h) [G]§ 63.481(m) § 63.504(c) § 63.506(e)(1)	For each continuous front-end process vent located at an affected source, the owner or operator shall comply with §§63.113-63.118, except as provided for in § 63.485(b)(-v).	§ 63.11(b)(4) § 63.11(b)(6) § 63.11(b)(7)(i) § 63.11(b)(7)(iii) § 63.11(b)(8) § 63.114(a) § 63.114(a)(2) § 63.114(e) [G]§ 63.115(a) § 63.116(a) § 63.504(c)(1) § 63.504(c)(2) § 63.504(c)(3)	[G]§ 63.117(a)(5) § 63.118(a)(1) § 63.118(a)(2)	§ 63.114(e) [G]§ 63.117(a)(5) § 63.117(f) § 63.118(f)(1) § 63.118(f)(2) § 63.118(f)(3) § 63.118(f)(5) [G]§ 63.485(l) [G]§ 63.506(i)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
S-BACKUPFLR	CD	Primary	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(4)(A)	Visible emissions from a process gas flare shall not be permitted for more than five minutes in any two-hour period. Non-excessive upset events are subject to the provisions under §101.222(b).	§ 111.111(a)(4)(A)(i) § 111.111(a)(4)(A)(ii)	§ 111.111(a)(4)(A)(ii)	None
S-BACKUPFLR	CD	Primary	Opacity	40 CFR Part 60, Subpart A	§ 60.18(b) § 60.18(c)(1) § 60.18(c)(2) § 60.18(c)(3)(ii) § 60.18(c)(5) § 60.18(c)(6) § 60.18(e)	Flares shall comply with paragraphs (c)-(f) of § 60.18.	§ 60.18(d) § 60.18(f)(1) § 60.18(f)(2) § 60.18(f)(3) § 60.18(f)(6)	None	None
S-BACKUPFLR	CD	Primary	Opacity	40 CFR Part 63, Subpart A	§ 63.11(b)(4) § 63.11(b)(1) § 63.11(b)(2) § 63.11(b)(3) § 63.11(b)(5) § 63.11(b)(6)(ii) § 63.11(b)(8)	Flares shall be designed and operated with no visible emissions, except for periods of a total of 5 minutes or less during any 2 consecutive hrs. Test Method 22 in App. A of part 60 of this chapter shall be used.	§ 63.11(b)(4) § 63.11(b)(5)	None	None
S-CARBLK	EP	R1111-1	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(B) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall not exceed an opacity of 20% averaged over a six minute period for any source on which construction was begun after January 31, 1972.	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
S-PROCESS C	EP	R1111-1	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(B) § 111.111(a)(1)(E)	Visible emissions from any stationary vent shall not exceed an opacity of 20% averaged over a six minute period for any source on which construction was begun after January 31, 1972.	[G]§ 111.111(a)(1)(F) ** See Periodic Monitoring Summary	None	None
S-SUPERHEAT	EU	63DDDD	112(B) HAPS	40 CFR Part 63, Subpart DDDDD	§ 63.7500(a)(1)-Table 3.1 § 63.7500(a)(1) § 63.7500(a)(3) § 63.7500(e) § 63.7505(a) § 63.7540(a) [G]§ 63.7540(a)(10) § 63.7540(a)(12) § 63.7540(a)(13)	For a new or existing boiler or process heater with a heat input capacity of less than or equal to 5 million Btu per hour designed to burn gas 1, a tune-up of the boiler or process heater must be conducted every 5 years as specified in § 63.7540.	§ 63.7515(d) [G]§ 63.7521(f) [G]§ 63.7521(g) § 63.7521(h) § 63.7521(i) § 63.7530(g) § 63.7540(a) [G]§ 63.7540(a)(10) [G]§ 63.7540(c)	§ 63.7555(a) § 63.7555(a)(1) § 63.7555(a)(2) § 63.7555(g) § 63.7555(h) § 63.7560(a) § 63.7560(b) § 63.7560(c)	[G]§ 63.7521(g) § 63.7530(e) § 63.7530(f) § 63.7545(a) § 63.7545(b) § 63.7545(c) [G]§ 63.7545(e) [G]§ 63.7545(f) § 63.7550(a) [G]§ 63.7550(b) [G]§ 63.7550(c) [G]§ 63.7550(h)
SERV PUMP	EU	63ZZZZ	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6602-Table 2c.2 § 63.6595(a)(1) § 63.6605(a) § 63.6605(b) § 63.6625(e) § 63.6625(h) § 63.6625(i)	For each existing non-emergency, non-black start stationary CI RICE with a site rating less than 100 HP, located at a major source, you must comply with the requirements as specified in Table 2c.2.a-c.	§ 63.6625(i) § 63.6640(a) § 63.6640(a)-Table 6.9.a.i § 63.6640(a)-Table 6.9.a.ii	§ 63.6625(i) § 63.6655(e) § 63.6660(a) § 63.6660(b) § 63.6660(c)	§ 63.6640(e) § 63.6650(f)
T-AMINE	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T-AMINE	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-AMINE	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)
T-COAGID1	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-COAGID1	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-COAGID2	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T-COAGID2	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-COAGID2	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)
T-COAGID3	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-COAGID3	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-COAGID4	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T-COAG4ID4	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-COAG4ID5	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-COAG4ID5	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-COAG4ID6	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-COAG4ID6	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T-D/L-OIL1	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-D/L-OIL1	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-D/L-OIL1	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)
T-D/L-OIL10	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-D/L-OIL10	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T-D/L-OIL10	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)
T-D/L-OIL3	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-D/L-OIL3	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-D/L-OIL3	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)
T-D/L-OIL7	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T-D/L-OIL7	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-D/L-OIL7	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)
T-D/L-OIL8	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-D/L-OIL8	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-D/L-OIL8	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T-D/L-OIL9	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-D/L-OIL9	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-D/L-OIL9	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)
T-DIESEL1	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-DIESEL1	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T-DIESEL2	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-DIESEL2	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-DIESEL3	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-EM/MOD1	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-EM/MOD1	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T-EM/MOD10	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-EM/MOD10	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-EM/MOD11	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-EM/MOD12	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-EM/MOD13	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T-EM/MOD13	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-EM/MOD14	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-EM/MOD14	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-EM/MOD15	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-EM/MOD15	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T-EM/MOD17	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-EM/MOD2	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-EM/MOD2	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-EM/MOD3	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-EM/MOD3	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T-EM/MOD4	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-EM/MOD4	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-EM/MOD5	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-EM/MOD5	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-EM/MOD6	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T-EM/MOD6	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-EM/MOD7	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-EM/MOD7	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-EM/MOD7	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)
T-EM/MOD8	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T-EM/MOD8	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-EM/MOD8	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)
T-EM/MOD9	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-EM/MOD9	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-EM/MOD9	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T-LTX-B16	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-LTX-B16	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-LTX-B16	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)
T-LTX-B17	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-LTX-B17	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T-LTX-B17	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)
T-LTX-C11	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-LTX-C11	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-LTX-C11	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)
T-LTX-C12	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T-LTX-C12	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-LTX-C12	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)
T-LTX-C13	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-LTX-C13	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-LTX-C13	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T-LTX-C14	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-LTX-C14	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-LTX-C14	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)
T-LTX-C15	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-LTX-C15	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T-LTX-C15	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)
T-LTX-C16	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-LTX-C16	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-LTX-C16	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)
T-LTX-C17	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T-LTX-C17	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-LTX-C17	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)
T-LTX-C18	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-LTX-C18	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-LTX-C18	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T-LTX-C19	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-LTX-C19	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-LTX-C19	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)
T-LTX-CC41	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-LTX-CC41	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T-LTX-CC41	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)
T-LTX-CC42	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-LTX-CC42	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-LTX-CC42	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)
T-LTX-CC43	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T-LTX-CC43	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-LTX-CC43	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)
T-LTX-CC44	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-LTX-CC44	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-LTX-CC44	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T-LTX-CC45	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-LTX-CC45	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-LTX-CC45	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)
T-LTX-CC46	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-LTX-CC46	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T-LTX-CC46	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)
T-LTX-CD	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-LTX-CD	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-LTX-CD	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)
T-LTX-D1	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T-LTX-D1	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-LTX-D1	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)
T-LTX-D10	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-LTX-D10	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-LTX-D10	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T-LTX-D11	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-LTX-D11	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-LTX-D11	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)
T-LTX-D2	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-LTX-D2	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T-LTX-D2	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)
T-LTX-D3	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-LTX-D3	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-LTX-D3	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)
T-LTX-D4	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T-LTX-D4	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-LTX-D4	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)
T-LTX-D5	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-LTX-D5	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-LTX-D5	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T-LTX-D6	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-LTX-D6	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-LTX-D6	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)
T-LTX-D7	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-LTX-D7	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T-LTX-D7	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)
T-LTX-D8	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-LTX-D8	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-LTX-D8	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)
T-LTX-D9	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T-LTX-D9	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-LTX-D9	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)
T-MSTY1	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-MSTY1	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-SFLEX1	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T-SFLEX1	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-SFLEX1	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)
T-SFLEX10	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-SFLEX10	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-SFLEX10	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T-SFLEX11	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-SFLEX11	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-SFLEX11	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)
T-SFLEX2	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-SFLEX2	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T-SFLEX2	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)
T-SFLEX3	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-SFLEX3	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-SFLEX4	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-SFLEX4	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T-SFLEX4	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)
T-SFLEX5	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-SFLEX5	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-SFLEX6	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-SFLEX6	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T-SFLEX7	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-SFLEX7	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-SFLEX8	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-SFLEX8	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-SFLEX9	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T-SFLEX9	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-SGEL	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-SGEL	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-SGEL	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)
T-SLPY1	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T-SLPY1	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-SLPY2	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-SLPY2	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-SLPY3	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-SLPY3	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T-SLPY4	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-SLPY4	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-SLPY5	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-SLPY5	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-SLPY6	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T-SLPY6	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-SSTP1	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-SSTP1	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-SSTP1	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)
T-SSTP2	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T-SSTP2	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-SSTP3	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-SSTP3	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-TALLOIL1	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-TALLOIL1	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T-TALLOIL1	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)
T-TALLOIL2	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
T-TALLOIL2	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-TALLOIL2	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)
T-TALLOIL3	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T-TALLOIL3	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)
T-TALLOIL3	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.484(a) § 63.119(a)(3) [G]§ 63.481(m)	For storage vessels at a source, comply with requirements of §63.119 through §63.123 and §63.148, except as noted in § 63.484(c) through (s).	None	§ 63.123(a)	§ 63.480(g)(6) § 63.506(e)(6)(vii) § 63.506(e)(7)(i) [G]§ 63.506(i)
T-WGAS	EU	Primary	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(a)(1)	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	[G]§ 115.117 ** See Periodic Monitoring Summary	§ 115.118(a)(5) § 115.118(a)(7)	None
T-WGAS	EU	63G	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(a)(3)	Group 2 tanks not using emissions averaging as prescribed by §63.150 shall use record keeping methods in §63.123(a). Not required to comply with §63.119 to §63.123.	None	§ 63.123(a)	§ 63.152(c)(4)(iii)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
UTILGEN2	EU	63ZZZZ	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6602-Table 2c.1 § 63.6595(a)(1) § 63.6605(a) § 63.6605(b) § 63.6625(e) § 63.6625(f) § 63.6625(h) § 63.6625(i) § 63.6640(f)(1) § 63.6640(f)(2) § 63.6640(f)(2)(i) § 63.6640(f)(3)	For each existing emergency stationary CI RICE and black start stationary CI RICE, located at a major source, you must comply with the requirements as specified in Table 2c.1.a-c.	§ 63.6625(i) § 63.6640(a) § 63.6640(a)-Table 6.9.a.i § 63.6640(a)-Table 6.9.a.ii	§ 63.6625(i) § 63.6655(e) § 63.6655(f) § 63.6660(a) § 63.6660(b) § 63.6660(c)	§ 63.6640(e) § 63.6650(f)
XNBR-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(5)	Reciprocating compressors and positive displacement pumps used in natural gas/gasoline processing operations are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
XNBR-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(10)	Instrumentation systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet 40 CFR §63.169 (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
XNBR-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(8) § 115.357(9)	No valves contacting a fluid with TVP less than or equal to 0.044 psia (heavy liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
XNBR-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(C) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(8) § 115.358(c)(1) [G]§ 115.358(h)	If the owner or operator elects to use the alternative work practice in §115.358, no component shall be allowed to have a VOC leak, detected as defined in §115.358, for more than 15 days after discovery. This includes any leak detected using the alternative work practice on a component that is subject to the requirements of this division but not specifically selected for alternative work practice monitoring.	§ 115.354(1) § 115.354(11) § 115.354(13)(A) § 115.354(13)(B) § 115.354(13)(C) § 115.354(13)(D) § 115.354(13)(E) § 115.354(13)(F) § 115.354(4) § 115.354(5) § 115.354(9) [G]§ 115.355 § 115.358(c)(2) § 115.358(d) [G]§ 115.358(e) § 115.358(f)	§ 115.352(7) § 115.354(13)(D) § 115.354(13)(E) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) [G]§ 115.356(4) § 115.356(5)	[G]§ 115.358(g)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
XNBR-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	No pump seals contacting a fluid with TVP greater than 0.044 psia (gas/vapor or light liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
XNBR-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1) § 115.357(8)	No pump seals contacting a fluid with TVP less than or equal to 0.044 psia (heavy liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
XNBR-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(4) § 115.357(8)	No pump seals that are equipped with a shaft sealing system that prevents or detects emissions of VOCs from the seal shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None
XNBR-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	No compressor seals contacting a fluid with TVP greater than 0.044 psia (gas/vapor or light liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
XNBR-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1) § 115.357(8)	No compressor seals contacting a fluid with TVP less than or equal to 0.044 psia (heavy liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
XNBR-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(4) § 115.357(8)	No compressor seals that are equipped with a shaft sealing system that prevents or detects emissions of VOCs from the seal shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
XNBR-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(3) § 115.357(8)	No compressor seals in hydrogen service with and the hydrogen content can be expected to always exceed 50.0% by volume shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None
XNBR-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(7) § 115.357(8)	No agitators contacting a fluid with TVP greater than 0.044 psia (gas/vapor or light liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
XNBR-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(7) § 115.357(1) § 115.357(8)	No agitators contacting a fluid with TVP less than or equal to 0.044 psia (heavy liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	[G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
XNBR-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(8) § 115.357(12) § 115.357(8)	No flanges or other connectors contacting a fluid with TVP greater than 0.044 psia (gas/vapor or light liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
XNBR-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(8) § 115.357(1) § 115.357(12) § 115.357(8)	No flanges or other connectors contacting a fluid with TVP less than or equal to 0.044 psia (heavy liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
XNBR-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(11)	Sampling connection systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet the requirements of 40 CFR §63.166(a) and (b) (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
XNBR-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(13)	Components/systems that contact a process fluid containing VOC having a true vapor pressure equal to or less than 0.002 psia at 68 degrees Fahrenheit are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
XNBR-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(6)	Components at a petroleum refinery or synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process, that contact a process fluid that contains less than 10% VOC by weight are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
XNBR-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(2) § 115.352(9)	Conservation vents or other devices on atmospheric storage tanks that are actuated either by a vacuum or a pressure of no more than 2.5 psig, pressure relief valves equipped with a rupture disk or venting to a control device, components in continuous vacuum service, and valves that are not externally regulated (such as in-line check valves) are exempt from the requirements of this division, except that each pressure relief valve equipped with a rupture disk must comply with §115.352(9) and §115.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
XNBR-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7) § 115.357(1)	No process drains contacting a fluid with TVP less than or equal to 0.044 psia (heavy liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
XNBR-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7)	No process drains contacting a fluid with TVP greater than 0.044 psia (gas/vapor or light liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
XNBR-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(9) § 115.357(1) § 115.357(8) § 115.357(9)	No pressure relief valves contacting a fluid with TVP less than or equal to 0.044 psia (heavy liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
XNBR-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(9) § 115.357(12) § 115.357(8) § 115.357(9)	No pressure relief valves contacting a fluid with TVP greater than 0.044 psia (gas/vapor or light liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
XNBR-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(8) § 115.357(9)	No open-ended valves or lines contacting a fluid with TVP less than or equal to 0.044 psia (heavy liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
XNBR-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8) § 115.357(9)	No open-ended valves or lines contacting a fluid with TVP greater than 0.044 psia (gas/vapor or light liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
XNBR-FUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8) § 115.357(9)	No valves contacting a fluid with TVP greater than 0.044 psia (gas/vapor or light liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
XNBR-FUG	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.502(a) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.164 [G]§ 63.171 [G]§ 63.481(m) § 63.506(e)(1)	The owner or operator of each affected source, shall comply with the requirements of subpart H for compressors, with exceptions noted in paragraphs (b)-(m) of § 63.502.	[G]§ 63.164 [G]§ 63.180(b) [G]§ 63.180(c) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4) [G]§ 63.502(j)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(f)	§ 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d) § 63.502(f) § 63.502(g) [G]§ 63.506(i)
XNBR-FUG	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.502(a) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.163 [G]§ 63.171 [G]§ 63.176 [G]§ 63.481(m) § 63.502(d) § 63.502(d)(1) § 63.502(d)(3) § 63.506(e)(1)	The owner or operator of each affected source, shall comply with the requirements of subpart H for pumps in light liquid service, with exceptions noted in paragraphs (b)-(m) of § 63.502.	[G]§ 63.163 [G]§ 63.176 [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4) [G]§ 63.502(j)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(3) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(8) § 63.181(h)(9)	§ 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d) § 63.502(f) § 63.502(g) [G]§ 63.506(i)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
XNBR-FUG	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.502(a) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.166 [G]§ 63.171 [G]§ 63.481(m) § 63.502(i) § 63.506(e)(1)	The owner or operator of each affected source, shall comply with the requirements of subpart H for sampling connection system, with exceptions noted in paragraphs (b)-(m) of § 63.502.	[G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4) [G]§ 63.502(j)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c)	§ 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d) § 63.502(f) § 63.502(g) [G]§ 63.506(i)
XNBR-FUG	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.502(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.174 [G]§ 63.481(m) § 63.506(e)(1)	The owner or operator of each affected source, shall comply with the requirements of subpart H for connectors in gas/vapor or light liquid service, with exceptions noted in paragraphs (b)-(m) of § 63.502.	[G]§ 63.174 [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4) [G]§ 63.502(j)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	§ 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d) § 63.502(f) § 63.502(g) [G]§ 63.506(i)
XNBR-FUG	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.502(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.173 [G]§ 63.481(m) § 63.506(e)(1)	The owner or operator of each affected source, shall comply with the requirements of subpart H for agitators in gas/vapor or light liquid service, with exceptions noted in paragraphs (b)-(m) of § 63.502.	[G]§ 63.173 [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4) [G]§ 63.502(j)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	§ 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d) § 63.502(f) § 63.502(g) [G]§ 63.506(i)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
XNBR-FUG	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.502(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 [G]§ 63.481(m) § 63.506(e)(1)	The owner or operator of each affected source, shall comply with the requirements of subpart H for pressure relief devices in liquid service, with exceptions noted in paragraphs (b)-(m) of § 63.502.	[G]§ 63.169 [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4) [G]§ 63.502(j)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	§ 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d) § 63.502(f) § 63.502(g) [G]§ 63.506(i)
XNBR-FUG	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.502(a) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.167 [G]§ 63.171 [G]§ 63.175 [G]§ 63.481(m) § 63.506(e)(1)	The owner or operator of each affected source, shall comply with the requirements of subpart H for open-ended valves and lines, with exceptions noted in paragraphs (b)-(m) of § 63.502.	[G]§ 63.175 [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4) [G]§ 63.502(j)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(8) § 63.181(h)(9)	§ 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d) § 63.502(f) § 63.502(g) [G]§ 63.506(i)
XNBR-FUG	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.502(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 [G]§ 63.481(m) § 63.506(e)(1)	The owner or operator of each affected source, shall comply with the requirements of subpart H for agitators in heavy liquid service, with exceptions noted in paragraphs (b)-(m) of § 63.502.	[G]§ 63.169 [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4) [G]§ 63.502(j)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	§ 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d) § 63.502(f) § 63.502(g) [G]§ 63.506(i)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
XNBR-FUG	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.502(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 [G]§ 63.481(m) § 63.506(e)(1)	The owner or operator of each affected source, shall comply with the requirements of subpart H for connectors in heavy liquid service, with exceptions noted in paragraphs (b)-(m) of § 63.502.	[G]§ 63.169 [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4) [G]§ 63.502(j)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	§ 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d) § 63.502(f) § 63.502(g) [G]§ 63.506(i)
XNBR-FUG	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.502(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 [G]§ 63.481(m) § 63.506(e)(1)	The owner or operator of each affected source, shall comply with the requirements of subpart H for valves in heavy liquid service, with exceptions noted in paragraphs (b)-(m) of § 63.502.	[G]§ 63.169 [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4) [G]§ 63.502(j)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	§ 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d) § 63.502(f) § 63.502(g) [G]§ 63.506(i)
XNBR-FUG	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.502(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 [G]§ 63.481(m) § 63.502(d) § 63.502(d)(2) § 63.506(e)(1)	The owner or operator of each affected source, shall comply with the requirements of subpart H for pumps in heavy liquid service, with exceptions noted in paragraphs (b)-(m) of § 63.502.	[G]§ 63.169 [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4) [G]§ 63.502(j)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	§ 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d) § 63.502(f) § 63.502(g) [G]§ 63.506(i)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
XNBR-FUG	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.502(a) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.168 [G]§ 63.171 [G]§ 63.175 [G]§ 63.481(m) § 63.506(e)(1)	The owner or operator of each affected source, shall comply with the requirements of subpart H for valves in light liquid or gas/vapor service, with exceptions noted in paragraphs (b)-(m) of § 63.502.	[G]§ 63.168 [G]§ 63.175 [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4) [G]§ 63.502(j)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(9)	§ 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d) § 63.502(f) § 63.502(g) [G]§ 63.506(i)
XNBR-FUG	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.502(a) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.165 [G]§ 63.171 [G]§ 63.481(m) § 63.506(e)(1)	The owner or operator of each affected source, shall comply with the requirements of subpart H for pressure relief devices in gas/vapor service, with exceptions noted in paragraphs (b)-(m) of § 63.502.	[G]§ 63.165 [G]§ 63.180(b) [G]§ 63.180(c) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4) [G]§ 63.502(j)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(f)	§ 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d) § 63.502(f) § 63.502(g) [G]§ 63.506(i)
XNBR-FUG	EU	63U-ALL	112(B) HAPS	40 CFR Part 63, Subpart U	§ 63.502(a) § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.169 [G]§ 63.171 [G]§ 63.481(m) § 63.506(e)(1)	The owner or operator of each affected source, shall comply with the requirements of subpart H for instrumentation systems, with exceptions noted in paragraphs (b)-(m) of § 63.502.	[G]§ 63.169 [G]§ 63.180(b) § 63.180(d)(1) [G]§ 63.180(d)(2) § 63.180(d)(3) § 63.180(d)(4) [G]§ 63.502(j)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	§ 63.182(a)(2) § 63.182(a)(3) [G]§ 63.182(a)(6) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d) § 63.502(f) § 63.502(g) [G]§ 63.506(i)

Additional Monitoring Requirements

Periodic Monitoring Summary	152
--	------------

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: GRP-DRYER	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-1
Pollutant: Opacity	Main Standard: § 111.111(a)(1)(A)
Monitoring Information	
Indicator: Visible Emissions	
Minimum Frequency: once per quarter	
Averaging Period: N/A	
Deviation Limit: Visible Emissions	
<p>Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor.</p> <p>If visible emissions are observed, the permit holder shall report a deviation. As an alternative, the permit holder may determine the opacity consistent with Test Method 9, as soon as practicable, but no later than 24 hours after observing visible emissions. If a Test Method 9 is performed, the opacity limit is the corresponding opacity limit associated with the particulate matter standard in the underlying applicable requirement. If there is no corresponding opacity limit in the underlying applicable requirement, the maximum opacity will be established using the most recent performance test. If the result of the Test Method 9 is opacity above the corresponding opacity limit (associated with the particulate matter standard in the underlying applicable requirement or as identified as a result of a previous performance test to establish the maximum opacity limit), the permit holder shall report a deviation.</p>	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: S-CARBLK	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-1
Pollutant: Opacity	Main Standard: § 111.111(a)(1)(B)
Monitoring Information	
Indicator: Visible Emissions	
Minimum Frequency: once per calendar quarter	
Averaging Period: N/A	
Deviation Limit: Maximum Opacity = 20%	
<p>Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor.</p> <p>If visible emissions are observed, the permit holder shall report a deviation. As an alternative, the permit holder may determine the opacity consistent with Test Method 9, as soon as practicable, but no later than 24 hours after observing visible emissions. If the result of the Test Method 9 is opacity above the opacity limit in the applicable requirement, the permit holder shall report a deviation.</p>	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: S-PROCESSCC	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-1
Pollutant: Opacity	Main Standard: § 111.111(a)(1)(B)
Monitoring Information	
Indicator: Visible Emissions	
Minimum Frequency: once per calendar quarter	
Averaging Period: N/A	
Deviation Limit: Maximum Opacity = 20%	
<p>Periodic Monitoring Text: Visible emissions observations shall be made and recorded. Note that to properly determine the presence of visible emissions, all sources must be in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 miles, away from the emission source during the observation. The observer shall select a position where the sun is not directly in the observer's eyes. If the observations cannot be conducted due to weather conditions, the date, time, and specific weather conditions shall be recorded. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor.</p> <p>If visible emissions are observed, the permit holder shall report a deviation. As an alternative, the permit holder may determine the opacity consistent with Test Method 9, as soon as practicable, but no later than 24 hours after observing visible emissions. If the result of the Test Method 9 is opacity above the opacity limit in the applicable requirement, the permit holder shall report a deviation.</p>	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: T-WGAS	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: Primary
Pollutant: VOC	Main Standard: § 115.112(a)(1)
Monitoring Information	
Indicator: Record of Tank Construction Specifications	
Minimum Frequency: N/A	
Averaging Period: N/A	
Deviation Limit: Failure to keep tank construction records shall be considered and reported as a deviation.	
<p>Periodic Monitoring Text: Keep a record of tank construction specifications (e.g. engineering drawings) that show a fill pipe that extends from the top of a tank to have a maximum clearance of six inches (15.2 centimeters) from the bottom or, when the tank is loaded from the side, a discharge opening entirely submerged when the pipe used to withdraw liquid from the tank can no longer withdraw liquid in normal operation.</p>	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: T-WGAS	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: Primary
Pollutant: VOC	Main Standard: § 115.112(a)(1)
Monitoring Information	
Indicator: Structural Integrity of the Pipe	
Minimum Frequency: Emptied and degassed	
Averaging Period: N/A	
Deviation Limit: Failure to conduct inspections or to complete any necessary repairs to the fill pipe prior to refilling the storage vessel shall be considered and reported as a deviation.	
<p>Periodic Monitoring Text: Inspect to determine the structural integrity of the fill pipe and record each time the storage vessel is emptied and degassed to ensure that it continues to meet the specifications in the above requirement. If the structural integrity of the fill pipe is in question, repairs shall be made before the storage vessel is refilled. It shall be considered and reported as a deviation if the repairs are not completed prior to refilling the storage vessel.</p>	

Permit Shield

Permit Shield 158

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit / Group / Process ID No.	Group / Inclusive Units	Regulation	Basis of Determination
AM VENT	N/A	40 CFR Part 63, Subpart U	Emission unit is not subject to 40 CFR Part 63, Subpart U as acrylamide is not an elastomer product.
PAM VENT	N/A	40 CFR Part 63, Subpart U	Emission unit is not subject to 40 CFR Part 63, Subpart U as acrylamide is not an elastomer product.
SOUTH-CT	N/A	40 CFR Part 63, Subpart Q	No chromium used in water.

New Source Review Authorization References

New Source Review Authorization References	160
New Source Review Authorization References by Emission Unit	161

New Source Review Authorization References

The New Source Review authorizations listed in the table below are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Title 30 TAC Chapter 116 Permits, Special Permits, and Other Authorizations (Other Than Permits By Rule, PSD Permits, or NA Permits) for the Application Area.	
Authorization No.: 4132A	Issuance Date: 02/29/2024
Authorization No.: 9908	Issuance Date: 06/14/2023
Authorization No.: 74010	Issuance Date: 03/24/2015
Permits By Rule (30 TAC Chapter 106) for the Application Area	
Number: 106.183	Version No./Date: 09/04/2000
Number: 106.261	Version No./Date: 11/01/2003
Number: 106.262	Version No./Date: 11/01/2003
Number: 106.433	Version No./Date: 09/04/2000
Number: 106.452	Version No./Date: 09/04/2000
Number: 106.454	Version No./Date: 11/01/2001
Number: 106.472	Version No./Date: 09/04/2000
Number: 106.478	Version No./Date: 09/04/2000
Number: 106.511	Version No./Date: 09/04/2000
Number: 106.512	Version No./Date: 03/14/1997
Number: 106.512	Version No./Date: 06/13/2001

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization**
39-0016	6D Oil Stg Tank 4	9908
40-0229	C/D Soap Unit Soap Makeup Tank 101	9908
40-0230	C/D Soap Unit Soap Makeup Tank 102	9908
40-0231	C/D Soap Unit Soap Makeup Tank 103	9908
40-0232	C/D Soap Unit Soap Makeup Tank 104	9908
40-0235	C/D Soap Unit Soap Makeup Tank 105	9908
AIRCOMP	Sull Air Compressor	106.512/03/14/1997
AM ST-101	Acrylamide Tank 101	9908
AM ST-102	Acrylamide Tank 102	9908
AM ST-103	Acrylamide Tank 103	9908
AM ST-104	Acrylamide Tank 104	9908
AM VENT	Water Scrubber	9908
B-REACMSS	B Reactor MSS	9908
BOILER 1	56 MMBtu/hr Boiler	74010
BOILER 2	56 MMBtu/hr Boiler	74010
BOILER 4	56 MMBtu/hr Boiler	74010
BOILER 5	145 MMBtu/hr Boiler	74010
DOCK FUGT	River Dock Fugitives	4132A
DOCKFLARE	River Dock Flare	4132A
DT-B1	Dilution Tank B1	9908
DT-B2	Dilution Tank B2	9908

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization**
DT-B3	Dilution Tank B3	9908
DT-B4	Dilution Tank B4	9908
EPPU 1	Polymers and Resins Process	9908
F-7CBASIN	Fugitives (Tank)	9908
F-7DBASIN	Fugitives (Tank)	9908
F-CBLK	Carbon Black Losses	9908
F-MAINT BLEND	Blend Finishing Lab MSS	9908
F-MAINT CARBON	Carbon Black Area MSS	9908
F-MAINT MISC	Miscellaneous MSS	9908
F-MAINT SHOPS	Shops MSS	9908
F-MAINT-MONTF	Monomer Tank Farm MSS	9908
F-MAINT-REACCA	CA Reactor MSS	9908
F-MAINT-REACCB	CB Reactor MSS	9908
F-MAINT-REACCC	CC Reactor MSS	9908
F-MAINT-REACDA	DA Reactor MSS	9908
F-MAINT-REACDB	DB Reactor MSS	9908
F-MAINT-RECOVD	D Recovery MSS	9908
F-MAINT-RECVV	C Recovery MSS	9908
F-MAINT-RECVCC	CC Recovery MSS	9908
F-MONTF	Monomer Tank Farm Fugitives	9908
F-PACKC	Pack Out C Building Losses	9908

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization**
F-PACKCC	Pack Out CC Building Losses	9908
F-PACKD	Pack Out D Building Losses	9908
F-PROCESSC	Process C Fugitives	9908
F-PROCESSCC	Process CC Building Losses	9908
F-PROCESSD	Process D Fugitives	9908
F-REACB	B Reactor Chain Fugitives	9908
F-REACCA	CA Reactor Fugitives	9908
F-REACCB	CB Reactor Fugitives	9908
F-REACCC	CC Reactor Fugitives	9908
F-REACDA	DA Reactor Fugitive Butadiene	9908
F-REACDB	DB Reactor Fugitives	9908
F-RECOVB	Recovery B Fugitives	9908
F-RECOVCA	CA Recovery Fugitives	9908
F-RECOVCB	CB Recovery Fugitives	9908
F-RECOVCC	CC Recovery Fugitives	9908
F-RECOVDA	DA Recovery Fugitives	9908
F-RECOVDB	DB Recovery Fugitives	9908
F-RFBASIN	Rubber Fines Pit Fug Emission	9908
F-SKIM	Skimmer Pit Fug Emissions (Tank)	9908
F-TFLIFT	Lift Fugitives (Tank)	9908
F-WWT	Wastewater System	9908

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization**
FWPUMP	Diesel Firewater Pump	106.511/09/04/2000
MST-1	Modifier/Rosin Soap/Methacrylic Acid Tank 1	9908
MST-2	Modifier/Rosin Soap/Methacrylic Acid Tank 2	9908
MST-3	Modifier/Rosin Soap/Methacrylic Acid Tank 3	9908
MST-4	Modifier/Rosin Soap/Methacrylic Acid Tank 4	9908
MST-5	Modifier/Rosin Soap/Methacrylic Acid Tank 5	9908
MST-6	Modifier/Rosin Soap/Methacrylic Acid Tank 6	9908
PAM VENT	PAM Unit Carbon Adsorption System (CAS)	9908
PAMFUG	PAM Unit Fugitives	9908
PLANTFLARE	Copolymer Flare	9908
S-7CDVENT	Recovery Vent Bypass, Areas C	9908
S-BACKUPFLR	Backup Flare	9908
S-CARBLK	Carbon Black Grinding	9908
S-DRYERA	Process Dryer A Stack	9908
S-DRYERB	Process Dryer B Stack	9908
S-DRYERC	Process Dryer C Stack	9908
S-DRYERD	D Dryer	9908
S-DRYERE	Process Dryer E Stack	9908
S-DRYERF	F Dryer	9908
S-DRYERG	G Dryer	9908
S-DRYERH	H Dryer	9908

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization**
S-DRYER I	Process Dryer I Stack	9908
S-DRYER J	J Dryer	9908
S-PROCESS CC	I-Line Packing Dust	9908
S-SUPERHEAT	Steam Super Heater	9908
SERV PUMP	Service Pump	106.512/06/13/2001
SOUTH-CT	South Cooling Tower	9908, 106.262/11/01/2003 [166610]
SS-12	A Dryer	9908
SS-13	B Dryer	9908
SS-14	C Dryer	9908
SS-16	E Dryer	9908
SS-20	I Dryer	9908
T-105	Caustic Tank	9908
T-AMINE	Amine Coagulant Tank-6C Stg	9908
T-COAG AID1	Coagulation Aid Tank 1-6C, Make Up	9908
T-COAG AID2	Coagulation Aid Tank 2-6C, Supply	9908
T-COAG AID3	Coagulation Aid Tank 3-6CC, 1 Line	9908
T-COAG AID4	Coagulation Aid Tank 4-6D, Stg	9908
T-COAG AID5	Coagulation Aid Tank 5-6CC, 1 Line	9908
T-COAG AID6	Coagulation Aid Tank 6-6C, Supply	9908
T-D/L-OIL1	D/L Oil Tank	9908
T-D/L-OIL10	D/L Oil Tank	9908

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization**
T-D/L-OIL3	D/L Oil Tank	9908
T-D/L-OIL7	D/L Oil Tank	9908
T-D/L-OIL8	D/L Oil Tank	9908
T-D/L-OIL9	D/L Oil Tank	9908
T-DIESEL1	Diesel Tank	9908
T-DIESEL2	Diesel Tank	9908
T-DIESEL3	Diesel Tank	9908
T-EM/MOD1	EM/OX/MODTank	9908
T-EM/MOD10	EM/OX/MODTank	9908
T-EM/MOD11	EM/OX/MODTank	9908
T-EM/MOD12	EM/OX/MODTank	9908
T-EM/MOD13	EM/OX/MODTank	9908
T-EM/MOD14	EM/OX/MODTank	9908
T-EM/MOD15	EM/OX/MODTank	9908
T-EM/MOD17	EM/OX/MODTank	9908
T-EM/MOD2	EM/OX/MODTank	9908
T-EM/MOD3	EM/OX/MODTank	9908
T-EM/MOD4	EM/OX/MODTank	9908
T-EM/MOD5	EM/OX/MODTank	9908
T-EM/MOD6	EM/OX/MODTank	9908
T-EM/MOD7	EM/OX/MODTank	9908

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization**
T-EM/MOD8	EM/OX/MODTank	9908
T-EM/MOD9	EM/OX/MODTank	9908
T-LTX-B1	Latex Tank B1	9908
T-LTX-B16	Latex Tank B16	9908
T-LTX-B17	Latex Tank B17	9908
T-LTX-B2	Latex Tank B2	9908
T-LTX-B3	Latex Tank B3	9908
T-LTX-B4	Latex Tank B4	9908
T-LTX-B5	Latex Tank B5	9908
T-LTX-B6	Latex Tank B6	9908
T-LTX-B7	Latex Tank B7	9908
T-LTX-B8	Latex Tank B8	9908
T-LTX-C11	Latex Tank C11	9908
T-LTX-C12	Latex Tank C12	9908
T-LTX-C13	Latex Tank C13	9908
T-LTX-C14	Latex Tank C14	9908
T-LTX-C15	Latex Tank C15	9908
T-LTX-C16	Latex Tank C16	9908
T-LTX-C17	Latex Tank C17	9908
T-LTX-C18	Latex Tank C18	9908
T-LTX-C19	Latex Tank C19	9908

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization**
T-LTX-CC41	Latex Tank CC41	9908
T-LTX-CC42	Latex Tank CC42	9908
T-LTX-CC43	Latex Tank CC43	9908
T-LTX-CC44	Latex Tank CC44	9908
T-LTX-CC45	Latex Tank CC45	9908
T-LTX-CC46	Latex Tank CC46	9908
T-LTX-CD	Latex C/D Dorr Tank	9908
T-LTX-D1	Latex Tank D1	9908
T-LTX-D10	Latex Tank D10	9908
T-LTX-D11	Latex Tank D11	9908
T-LTX-D2	Latex Tank D2	9908
T-LTX-D3	Latex Tank D3	9908
T-LTX-D4	Latex Tank D4	9908
T-LTX-D5	Latex Tank D5	9908
T-LTX-D6	Latex Tank D6	9908
T-LTX-D7	Latex Tank D7	9908
T-LTX-D8	Latex Tank D8	9908
T-LTX-D9	Latex Tank D9	9908
T-MSTY1	Main Styrene Tank	9908
T-SFLEX1	Staining AO Tank 1 - 9C, Make Up	9908
T-SFLEX10	Staining AO Tank 10 - 6C, Blend, Feed	9908

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization**
T-SFLEX11	Staining AO Tank 11 - 6C, Blend, Feed	9908
T-SFLEX2	Staining AO Tank 2 - 9D, Make Up	9908
T-SFLEX3	Staining AO Tank 3 - 9D, Make Up	9908
T-SFLEX4	Staining AO Tank 4 - 9D, Emulsion Stg	9908
T-SFLEX5	Staining AO Tank 5 - 9D, Make Up	9908
T-SFLEX6	Staining AO Tank 6 - 9D, Make Up	9908
T-SFLEX7	Staining AO Tank 7 - 9D, Make Up	9908
T-SFLEX8	Staining AO Tank 8 - 9D, Stg	9908
T-SFLEX9	Staining AO Tank 9 - 9D, Stg	9908
T-SGEL	Geltrol Tank	9908
T-SLPY1	Nonstaining AO Tank I 9C Make Up	9908
T-SLPY2	Nonstaining AO Tank 3 6CC	9908
T-SLPY3	Nonstaining AO Tank 4 6CC	9908
T-SLPY4	Nonstaining AO Tank 5 6C Blend Feed	9908
T-SLPY5	Nonstaining AO Tank 6 67D Blend Feed	9908
T-SLPY6	Nonstaining AO Tank I 9C Make Up	9908
T-SSTP1	Shortstop Tank 1 8CC, Stg	9908
T-SSTP2	Shortstop Tank 2 9D, Make Up	9908
T-SSTP3	Shortstop Tank 3 9C, Make Up	9908
T-TALLOIL1	Raw Soap Tank 1	9908
T-TALLOIL2	Raw Soap Tank 2	9908

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization**
T-TALLOIL3	Raw Soap Tank 3 PTF	9908
T-WGAS	West Gasoline Tank	9908
TANK800	Tank 800	9908
TANK801	Tank 801	9908
TANK803	Tank 803	9908
UTILGEN2	Utilities - 350 KW Generator	106.511/09/04/2000
V-101A	Catalyst Tank 101A	9908
V-101B	Catalyst Tank 101B	9908

**This column may include Permit by Rule (PBR) numbers and version dates, PBR Registration numbers in brackets, Standard Permit Registration numbers, Minor NSR permit numbers, and Major NSR permit numbers.

Appendix A

Acronym List 172

Acronym List

The following abbreviations or acronyms may be used in this permit:

ACFM	actual cubic feet per minute
AMOC	alternate means of control
ARP	Acid Rain Program
ASTM	American Society of Testing and Materials
B/PA	Beaumont/Port Arthur (nonattainment area)
CAM	Compliance Assurance Monitoring
CD	control device
CEMS	continuous emissions monitoring system
CFR	Code of Federal Regulations
COMS	continuous opacity monitoring system
CVS	closed vent system
D/FW	Dallas/Fort Worth (nonattainment area)
EP	emission point
EPA	U.S. Environmental Protection Agency
EU	emission unit
FCAA Amendments	Federal Clean Air Act Amendments
FOP	federal operating permit
gr/100 scf	grains per 100 standard cubic feet
HAP	hazardous air pollutant
H/G/B	Houston/Galveston/Brazoria (nonattainment area)
H ₂ S	hydrogen sulfide
ID No.	identification number
lb/hr	pound(s) per hour
MACT	Maximum Achievable Control Technology (40 CFR Part 63)
MMBtu/hr	Million British thermal units per hour
NA	nonattainment
N/A	not applicable
NADB	National Allowance Data Base
NESHAP	National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61)
NO _x	nitrogen oxides
NSPS	New Source Performance Standard (40 CFR Part 60)
NSR	New Source Review
ORIS	Office of Regulatory Information Systems
Pb	lead
PBR	Permit By Rule
PEMS	predictive emissions monitoring system
PM	particulate matter
ppmv	parts per million by volume
PRO	process unit
PSD	prevention of significant deterioration
psia	pounds per square inch absolute
SIP	state implementation plan
SO ₂	sulfur dioxide
TCEQ	Texas Commission on Environmental Quality
TSP	total suspended particulate
TVP	true vapor pressure
U.S.C.	United States Code
VOC	volatile organic compound