

FEDERAL OPERATING PERMIT

A FEDERAL OPERATING PERMIT IS HEREBY ISSUED TO
SK Primacor Americas LLC

AUTHORIZING THE OPERATION OF
SK Primacor Americas
Adhesive Polymers Plant
Plastics Material and Resin Manufacturing

LOCATED AT
Brazoria County, Texas
Latitude 28° 59' 58" Longitude 95° 24' 32"
Regulated Entity Number: RN110300126

This permit is issued in accordance with and subject to the Texas Clean Air Act (TCAA), Chapter 382 of the Texas Health and Safety Code and Title 30 Texas Administrative Code Chapter 122 (30 TAC Chapter 122), Federal Operating Permits. Under 30 TAC Chapter 122, this permit constitutes the permit holder's authority to operate the site and emission units listed in this permit. Operations of the site and emission units listed in this permit are subject to all additional rules or amended rules and orders of the Commission pursuant to the TCAA.

This permit does not relieve the permit holder from the responsibility of obtaining New Source Review authorization for new, modified, or existing facilities in accordance with 30 TAC Chapter 116, Control of Air Pollution by Permits for New Construction or Modification.

The site and emission units authorized by this permit shall be operated in accordance with 30 TAC Chapter 122, the general terms and conditions, special terms and conditions, and attachments contained herein.

This permit shall expire five years from the date of issuance. The renewal requirements specified in 30 TAC § 122.241 must be satisfied in order to renew the authorization to operate the site and emission units.

Permit No: 02215 Issuance Date: _____

For the Commission

Table of Contents

| Section | Page |
|---|------|
| General Terms and Conditions | 1 |
| Special Terms and Conditions: | 1 |
| Emission Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting..... | 1 |
| Additional Monitoring Requirements | 7 |
| New Source Review Authorization Requirements | 7 |
| Compliance Requirements..... | 8 |
| Risk Management Plan | 9 |
| Protection of Stratospheric Ozone | 10 |
| Temporary Fuel Shortages (30 TAC § 112.15) | 10 |
| Alternative Requirements..... | 10 |
| Permit Location | 11 |
| Permit Shield (30 TAC § 122.148)..... | 11 |
| Attachments | 12 |
| Applicable Requirements Summary..... | 13 |
| Additional Monitoring Requirements | 84 |
| Permit Shield | 86 |
| New Source Review Authorization References | 93 |
| Alternative Requirement..... | 98 |
| Appendix A..... | 101 |
| Acronym List | 102 |

General Terms and Conditions

The permit holder shall comply with all terms and conditions contained in 30 TAC § 122.143 (General Terms and Conditions), 30 TAC § 122.144 (Recordkeeping Terms and Conditions), 30 TAC § 122.145 (Reporting Terms and Conditions), and 30 TAC § 122.146 (Compliance Certification Terms and Conditions).

In accordance with 30 TAC § 122.144(1), records of required monitoring data and support information required by this permit, or any applicable requirement codified in this permit, are required to be maintained for a period of five years from the date of the monitoring report, sample, or application unless a longer data retention period is specified in an applicable requirement. The five year record retention period supersedes any less stringent retention requirement that may be specified in a condition of a permit identified in the New Source Review Authorization attachment.

If the permit holder chooses to demonstrate that this permit is no longer required, a written request to void this permit shall be submitted to the Texas Commission on Environmental Quality (TCEQ) by the Responsible Official in accordance with 30 TAC § 122.161(e). The permit holder shall comply with the permit's requirements, including compliance certification and deviation reporting, until notified by the TCEQ that this permit is voided.

The permit holder shall comply with 30 TAC Chapter 116 by obtaining a New Source Review authorization prior to new construction or modification of emission units located in the area covered by this permit.

All reports required by this permit must include in the submittal a cover letter which identifies the following information: company name, TCEQ regulated entity number, air account number (if assigned), site name, area name (if applicable), and Air Permits Division permit number(s).

Special Terms and Conditions:

Emission Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting

1. Permit holder shall comply with the following requirements:
 - A. Emission units (including groups and processes) in the Applicable Requirements Summary attachment shall meet the limitations, standards, equipment specifications, monitoring, recordkeeping, reporting, testing, and other requirements listed in the Applicable Requirements Summary attachment to assure compliance with the permit.
 - B. The textual description in the column titled "Textual Description" in the Applicable Requirements Summary attachment is not enforceable and is not deemed as a substitute for the actual regulatory language. The Textual Description is provided for information purposes only.
 - C. A citation listed on the Applicable Requirements Summary attachment, which has a notation [G] listed before it, shall include the referenced section and subsection for all commission rules, or paragraphs for all federal and state regulations and all subordinate paragraphs, subparagraphs and clauses, subclauses, and items contained within the referenced citation as applicable requirements.
 - D. When a grouped citation, notated with a [G] in the Applicable Requirements Summary, contains multiple compliance options, the permit holder must keep records of when each compliance option was used.
 - E. Emission units subject to 40 CFR Part 63, Subpart A or FFFF as identified in the attached Applicable Requirements Summary table are subject to 30 TAC Chapter 113,

Subchapter C, §113.100 or §113.890, respectively, which incorporate the 40 CFR Part 63 Subparts by reference.

- F. For the purpose of generating emission reduction credits through 30 TAC Chapter 101, Subchapter H, Division 1 (Emission Credit Banking and Trading), the permit holder shall comply with the following requirements:
- (i) Title 30 TAC § 101.302 (relating to General Provisions)
 - (ii) Title 30 TAC § 101.303 (relating to Emission Reduction Credit Generation Certification)
 - (iii) Title 30 TAC § 101.304 (relating to Mobile Emission Reduction Credit Generation and Certification)
 - (iv) Title 30 TAC § 101.309 (relating to Emission Credit Banking and Trading)
 - (v) The terms and conditions by which the emission limits are established to generate the reduction credit are applicable requirements of this permit
- G. The permit holder shall comply with the following 30 TAC Chapter 101, Subchapter H, Division 3 (Mass Emission Cap and Trade Program) Requirements:
- (i) Title 30 TAC § 101.352 (relating to General Provisions)
 - (ii) Title 30 TAC § 101.353 (relating to Allocation of Allowances)
 - (iii) Title 30 TAC § 101.354 (relating to Allowance Deductions)
 - (iv) Title 30 TAC § 101.356 (relating to Allowance Banking and Trading)
 - (v) Title 30 TAC § 101.359 (relating to Reporting)
 - (vi) Title 30 TAC § 101.360 (relating to Level of Activity Certification)
 - (vii) The terms and conditions by which the emission limits are established to meet or exceed the cap are applicable requirements of this permit
- H. For the purpose of generating discrete emission reduction credits through 30 TAC Chapter 101, Subchapter H, Division 4 (Discrete Emission Credit Banking and Trading), the permit holder shall comply with the following requirements:
- (i) Title 30 TAC § 101.372 (relating to General Provisions)
 - (ii) Title 30 TAC § 101.373 (relating to Discrete Emission Reduction Credit Generation and Certification)
 - (iii) Title 30 TAC § 101.374 (relating to Mobile Discrete Emission Reduction Credit Generation and Certification)
 - (iv) Title 30 TAC § 101.378 (relating to Discrete Emission Credit Banking and Trading)
 - (v) The terms and conditions by which the emission limits are established to generate the discrete reduction credit are applicable requirements of this permit

- I. The permit holder shall comply with the following 30 TAC Chapter 101, Subchapter H, Division 6 (Highly Reactive Volatile Organic Compound Emissions Cap and Trade Program) requirements:
 - (i) Title 30 TAC § 101.392 (relating to Exemptions)
 - (ii) Title 30 TAC § 101.401 (relating to Level of Activity Certification)
2. The permit holder shall comply with the following sections of 30 TAC Chapter 101 (General Air Quality Rules):
 - A. Title 30 TAC § 101.1 (relating to Definitions), insofar as the terms defined in this section are used to define the terms used in other applicable requirements
 - B. Title 30 TAC § 101.3 (relating to Circumvention)
 - C. Title 30 TAC § 101.8 (relating to Sampling), if such action has been requested by the TCEQ
 - D. Title 30 TAC § 101.9 (relating to Sampling Ports), if such action has been requested by the TCEQ
 - E. Title 30 TAC § 101.10 (relating to Emissions Inventory Requirements)
 - F. Title 30 TAC § 101.201 (relating to Emission Event Reporting and Recordkeeping Requirements)
 - G. Title 30 TAC § 101.211 (relating to Scheduled Maintenance, Start-up, and Shutdown Reporting and Recordkeeping Requirements)
 - H. Title 30 TAC § 101.221 (relating to Operational Requirements)
 - I. Title 30 TAC § 101.222 (relating to Demonstrations)
 - J. Title 30 TAC § 101.223 (relating to Actions to Reduce Excessive Emissions)
3. Permit holder shall comply with the following requirements of 30 TAC Chapter 111:
 - A. Visible emissions from stationary vents with a flow rate of less than 100,000 actual cubic feet per minute and constructed after January 31, 1972 that are not listed in the Applicable Requirements Summary attachment for 30 TAC Chapter 111, Subchapter A, Division 1, shall not exceed 20% opacity averaged over a six-minute period. The permit holder shall comply with the following requirements for stationary vents at the site subject to this standard:
 - (i) Title 30 TAC § 111.111(a)(1)(B) (relating to Requirements for Specified Sources)
 - (ii) Title 30 TAC § 111.111(a)(1)(E)
 - (iii) Title 30 TAC § 111.111(a)(1)(F)(i), (ii), (iii), or (iv)
 - (iv) For emission units with vent emissions subject to 30 TAC § 111.111(a)(1)(B), complying with 30 TAC § 111.111(a)(1)(F)(ii), (iii), or (iv), and capable of producing visible emissions from, but not limited to, particulate matter, acid gases and NO_x, the permit holder shall also comply with the following periodic

monitoring requirements for the purpose of annual compliance certification under 30 TAC § 122.146. These periodic monitoring requirements do not apply to vents that are not capable of producing visible emissions such as vents that emit only colorless VOCs; vents from non-fuming liquids; vents that provide passive ventilation, such as plumbing vents; or vent emissions from any other source that does not obstruct the transmission of light. Vents, as specified in the "Applicable Requirements Summary" attachment, that are subject to the emission limitation of 30 TAC § 111.111(a)(1)(B) are not subject to the following periodic monitoring requirements:

- (1) An observation of stationary vents from emission units in operation shall be conducted at least once during each calendar quarter unless the emission unit is not operating for the entire quarter.
- (2) For stationary vents from a combustion source, if an alternative to the normally fired fuel is fired for a period greater than or equal to 24 consecutive hours, the permit holder shall conduct an observation of the stationary vent for each such period to determine if visible emissions are present. If such period is greater than 3 months, observations shall be conducted once during each quarter. Supplementing the normally fired fuel with natural gas or fuel gas to increase the net heating value to the minimum required value does not constitute creation of an alternative fuel.
- (3) Records of all observations shall be maintained.
- (4) Visible emissions observations of emission units operated during daylight hours shall be conducted no earlier than one hour after sunrise and no later than one hour before sunset. Visible emissions observations of emission units operated only at night must be made with additional lighting and the temporary installation of contrasting backgrounds. Visible emissions observations shall be made during times when the activities described in 30 TAC § 111.111(a)(1)(E) are not taking place. Visible emissions shall be determined with each stationary vent in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 mile, away from each stationary vent during the observation. For outdoor locations, the observer shall select a position where the sun is not directly in the observer's eyes. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. A certified opacity reader is not required for visible emissions observations.
- (5) Compliance Certification:
 - (a) If visible emissions are not present during the observation, the RO may certify that the source is in compliance with the applicable opacity requirement in 30 TAC § 111.111(a)(1) and (a)(1)(B).
 - (b) However, if visible emissions are present during the observation, the permit holder shall either list this occurrence as a deviation on the next deviation report as required under

30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(1)(F) as soon as practicable, but no later than 24 hours after observing visible emissions to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.

- (c) Some vents may be subject to multiple visible emission or monitoring requirements. All credible data must be considered when certifying compliance with this requirement even if the observation or monitoring was performed to demonstrate compliance with a different requirement.
- B. Certification of opacity readers determining opacities under Method 9 (as outlined in 40 CFR Part 60, Appendix A) to comply with opacity monitoring requirements shall be accomplished by completing the Visible Emissions Evaluators Course, or approved agency equivalent, no more than 180 days before the opacity reading.
- C. For emission units with contributions from uncombined water, the permit holder shall comply with the requirements of 30 TAC § 111.111(b).
- D. Emission limits on nonagricultural processes, except for the steam generators specified in 30 TAC § 111.153, shall comply with the following requirements:
 - (i) Emissions of PM from any source may not exceed the allowable rates as required in 30 TAC § 111.151(a) (relating to Allowable Emissions Limits)
 - (ii) Sources with an effective stack height (h_e) less than the standard effective stack height (H_e), must reduce the allowable emission level by multiplying it by $[h_e/H_e]^2$ as required in 30 TAC § 111.151(b)
 - (iii) Effective stack height shall be calculated by the equation specified in 30 TAC § 111.151(c)
- E. Outdoor burning, as stated in 30 TAC § 111.201, shall not be authorized unless the following requirements are satisfied:
 - (i) Title 30 TAC § 111.207 (relating to Exception for Recreation, Ceremony, Cooking, and Warmth)
 - (ii) Title 30 TAC § 111.219 (relating to General Requirements for Allowable Outdoor Burning)
 - (iii) Title 30 TAC § 111.221 (relating to Responsibility for Consequences of Outdoor Burning)
- 4. For storage vessels maintaining working pressure as specified in 30 TAC Chapter 115, Subchapter B, Division 1: Storage of Volatile Organic Compounds, the permit holder shall comply with the requirements of 30 TAC § 115.112(e)(1).

5. The permit holder shall comply with the following requirements of 30 TAC Chapter 115, Subchapter H, Division 1 for pressure relief devices not controlled by a flare:
 - A. Title 30 TAC § 115.725(c)
 - B. Title 30 TAC § 115.725(c)(1), (c)(1)(A) - (C)
 - C. Title 30 TAC § 115.725(c)(2)
 - D. Title 30 TAC § 115.725(c)(3), (c)(3)(A) - (E)
 - E. Title 30 TAC § 115.725(c)(4)
 - F. Title 30 TAC § 115.725(l)
 - G. Title 30 TAC § 115.726(c), (c)(1) - (4)
6. The permit holder shall comply with the requirements of 30 TAC § 115.726(e)(3)(A) for vent streams having no potential to emit HRVOC.
7. The permit holder shall comply with the requirements of 30 TAC § 115.726(e)(3)(A) for vent streams from sources exempt under 30 TAC § 115.727(c)(3).
8. The permit holder shall comply with the following requirements for units subject to any subpart of 40 CFR Part 60, unless otherwise stated in the applicable subpart:
 - A. Title 40 CFR § 60.7 (relating to Notification and Recordkeeping)
 - B. Title 40 CFR § 60.8 (relating to Performance Tests)
 - C. Title 40 CFR § 60.11 (relating to Compliance with Standards and Maintenance Requirements)
 - D. Title 40 CFR § 60.12 (relating to Circumvention)
 - E. Title 40 CFR § 60.13 (relating to Monitoring Requirements)
 - F. Title 40 CFR § 60.14 (relating to Modification)
 - G. Title 40 CFR § 60.15 (relating to Reconstruction)
 - H. Title 40 CFR § 60.19 (relating to General Notification and Reporting Requirements)
9. The permit holder shall comply with the requirements of 30 TAC Chapter 113, Subchapter C, § 113.100 for units subject to any subpart of 40 CFR Part 63, unless otherwise stated in the applicable subpart.
10. For miscellaneous chemical process facilities subject to maintenance wastewater requirements as specified in 40 CFR § 63.2485, Table 7, the permit holder shall comply with the requirements of 40 CFR § 63.105 (relating to Maintenance Wastewater Requirements) (Title 30 TAC Chapter 113, Subchapter C, § 113.890 incorporated by reference).
11. For the transfer of site remediation materials subject to 40 CFR Part 63, Subpart GGGGG off-site to another facility, the permit holder shall comply with the following requirements (Title 30 TAC, Subchapter C, § 113.1160 incorporated by reference):

- A. Title 40 CFR § 63.7936(a), for the transfer of site remediation materials
 - B. Title 40 CFR § 63.7936(b)(1), for transfer to a landfill or land disposal unit
 - C. Title 40 CFR § 63.7936(b)(2), for transfer to a facility subject to 40 CFR Part 63, Subpart DD
 - D. Title 40 CFR § 63.7936(b)(3), (b)(3)(i) - (iv), for transfer to a facility managing the site remediation material according to the requirements of 40 CFR Part 63, Subpart GGGG
 - E. Title 40 CFR § 63.7952(a)(10), for recordkeeping requirements
12. The permit holder shall comply with certified registrations submitted to the TCEQ for purposes of establishing federally enforceable emission limits. A copy of the certified registration shall be maintained with the permit. Records sufficient to demonstrate compliance with the established limits shall be maintained. The certified registration and records demonstrating compliance shall be provided, on request, to representatives of the appropriate TCEQ regional office and any local air pollution control agency having jurisdiction over the site. The permit holder shall submit updated certified registrations when changes at the site require establishment of new emission limits. If changes result in emissions that do not remain below major source thresholds, the permit holder shall submit a revision application to codify the appropriate requirements in the permit.

Additional Monitoring Requirements

13. The permit holder shall comply with the periodic monitoring requirements as specified in the attached "Periodic Monitoring Summary" upon issuance of the permit. Except for, as applicable, monitoring malfunctions, associated repairs, and required quality assurance or control activities (including, as applicable, calibration checks and required zero and span adjustments), the permit holder shall conduct all monitoring in continuous operation (or shall collect data at all required intervals) at all times that the pollutant-specific emissions unit is operating. The permit holder may elect to collect monitoring data on a more frequent basis and average the data, consistent with the averaging time or minimum frequency specified in the "Periodic Monitoring Summary," for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis. In no event shall data be collected and used in particular instances to avoid reporting deviations. Deviations shall be reported according to 30 TAC § 122.145 (Reporting Terms and Conditions).

New Source Review Authorization Requirements

14. Permit holder shall comply with the requirements of New Source Review authorizations issued or claimed by the permit holder for the permitted area, including permits, permits by rule (including the terms, conditions, monitoring, recordkeeping, and reporting identified in registered PBRs and permits by rule identified in the PBR Supplemental Tables dated August 18, 2025 in the application for project 36422), standard permits, flexible permits, special permits, permits for existing facilities including Voluntary Emissions Reduction Permits and Electric Generating Facility Permits issued under 30 TAC Chapter 116, Subchapter I, or special exemptions referenced in the New Source Review Authorization References attachment. These requirements:
- A. Are incorporated by reference into this permit as applicable requirements
 - B. Shall be located with this operating permit
 - C. Are not eligible for a permit shield

15. The permit holder shall comply with the general requirements of 30 TAC Chapter 106, Subchapter A or the general requirements, if any, in effect at the time of the claim of any PBR.
16. The permit holder shall maintain records to demonstrate compliance with any emission limitation or standard that is specified in a permit by rule (PBR) or Standard Permit listed in the New Source Review Authorizations attachment. The records shall yield reliable data from the relevant time period that are representative of the emission unit's compliance with the PBR or Standard Permit. These records may include, but are not limited to, production capacity and throughput, hours of operation, safety data sheets (SDS), chemical composition of raw materials, speciation of air contaminant data, engineering calculations, maintenance records, fugitive data, performance tests, capture/control device efficiencies, direct pollutant monitoring (CEMS, COMS, or PEMS), or control device parametric monitoring. These records shall be made readily accessible and available as required by 30 TAC § 122.144. Any monitoring or recordkeeping data indicating noncompliance with the PBR or Standard Permit shall be considered and reported as a deviation according to 30 TAC § 122.145 (Reporting Terms and Conditions).

Compliance Requirements

17. The permit holder shall certify compliance in accordance with 30 TAC § 122.146. The permit holder shall comply with 30 TAC § 122.146 using at a minimum, but not limited to, the continuous or intermittent compliance method data from monitoring, recordkeeping, reporting, or testing required by the permit and any other credible evidence or information. The certification period may not exceed 12 months and the certification must be submitted within 30 days after the end of the period being certified.
18. Permit holder shall comply with the following 30 TAC Chapter 117 requirements:
 - A. The permit holder shall comply with the compliance schedules and submit written notification to the TCEQ Executive Director as required in 30 TAC Chapter 117, Subchapter H, Division 1:
 - (i) For sources in the Houston-Galveston-Brazoria Nonattainment area, 30 TAC § 117.9020:
 - (1) Title 30 TAC § 117.9020(2)(A), (C), and (D)
 - B. The permit holder shall comply with the Initial Control Plan unit listing requirement in 30 TAC § 117.350(c) and (c)(1).
 - C. The permit holder shall comply with the requirements of 30 TAC § 117.354 for Final Control Plan Procedures for Attainment Demonstration Emission Specifications and 30 TAC § 117.356 for Revision of Final Control Plan.
19. Use of Emission Credits to comply with applicable requirements:
 - A. Unless otherwise prohibited, the permit holder may use emission credits to comply with the following applicable requirements listed elsewhere in this permit:
 - (i) Title 30 TAC Chapter 115
 - (ii) Title 30 TAC Chapter 117
 - (iii) Offsets for Title 30 TAC Chapter 116

- B. The permit holder shall comply with the following requirements in order to use the emission credits to comply with the applicable requirements:
 - (i) The permit holder must notify the TCEQ according to 30 TAC § 101.306(c)-(d)
 - (ii) The emission credits to be used must meet all the geographic, timeliness, applicable pollutant type, and availability requirements listed in 30 TAC Chapter 101, Subchapter H, Division 1
 - (iii) The executive director has approved the use of the credit according to 30 TAC § 101.306(c)-(d)
 - (iv) The permit holder keeps records of the use of credits towards compliance with the applicable requirements in accordance with 30 TAC § 101.302(g) and 30 TAC Chapter 122
 - (v) Title 30 TAC § 101.305 (relating to Emission Reductions Achieved Outside the United States)
20. Use of Discrete Emission Credits to comply with the applicable requirements:
- A. Unless otherwise prohibited, the permit holder may use discrete emission credits to comply with the following applicable requirements listed elsewhere in this permit:
 - (i) Title 30 TAC Chapter 115
 - (ii) Title 30 TAC Chapter 117
 - (iii) If applicable, offsets for Title 30 TAC Chapter 116
 - (iv) Temporarily exceed state NSR permit allowables
 - B. The permit holder shall comply with the following requirements in order to use the credit to comply with the applicable requirements:
 - (i) The permit holder must notify the TCEQ according to 30 TAC § 101.376(d)
 - (ii) The discrete emission credits to be used must meet all the geographic, timeliness, applicable pollutant type, and availability requirements listed in 30 TAC Chapter 101, Subchapter H, Division 4
 - (iii) The executive director has approved the use of the discrete emission credits according to 30 TAC § 101.376(d)(1)(A)
 - (iv) The permit holder keeps records of the use of credits towards compliance with the applicable requirements in accordance with 30 TAC § 101.372(h) and 30 TAC Chapter 122
 - (v) Title 30 TAC § 101.375 (relating to Emission Reductions Achieved Outside the United States)

Risk Management Plan

21. For processes subject to 40 CFR Part 68 and specified in 40 CFR § 68.10, the permit holder shall comply with the requirements of the Accidental Release Prevention Provisions in 40 CFR Part 68.

The permit holder shall submit to the appropriate agency either a compliance schedule for meeting the requirements of 40 CFR Part 68 by the date provided in 40 CFR § 68.10(a), or as part of the compliance certification submitted under this permit, a certification statement that the source is in compliance with all requirements of 40 CFR Part 68, including the registration and submission of a risk management plan.

Protection of Stratospheric Ozone

22. Permit holders at a site subject to Title VI of the FCAA Amendments shall meet the following requirements for protection of stratospheric ozone:
- A. Any on site servicing, maintenance, and repair on refrigeration and nonmotor vehicle air-conditioning appliances using ozone-depleting refrigerants or non-exempt substitutes shall be conducted in accordance with 40 CFR Part 82, Subpart F. Permit holders shall ensure that repairs on or refrigerant removal from refrigeration and nonmotor vehicle air-conditioning appliances using ozone-depleting refrigerants are performed only by properly certified technicians using certified equipment. Records shall be maintained as required by 40 CFR Part 82, Subpart F.
 - B. The permit holder shall comply with 40 CFR Part 82, Subpart A for controlling the production, transformation, destruction, export or import of a controlled (ozone-depleting) substance or product as specified in 40 CFR § 82.1 - § 82.13 and the applicable Part 82 Appendices.
 - C. The permit holder shall comply with 40 CFR Part 82, Subpart A, § 82.13 related to recordkeeping and reporting requirements for the production and consumption of ozone depleting substances.

Temporary Fuel Shortages (30 TAC § 112.15)

23. The permit holder shall comply with the following 30 TAC Chapter 112 requirements:
- A. Title 30 TAC § 112.15 (relating to Temporary Fuel Shortage Plan Filing Requirements)
 - B. Title 30 TAC § 112.16(a), (a)(1), and (a)(2)(B) - (C) (relating to Temporary Fuel Shortage Plan Operating Requirements)
 - C. Title 30 TAC § 112.17 (relating to Temporary Fuel Shortage Plan Notification Procedures)
 - D. Title 30 TAC § 112.18 (relating to Temporary Fuel Shortage Plan Reporting Requirements)

Alternative Requirements

24. The permit holder shall comply with the approved alternative means of control (AMOC); alternative monitoring, recordkeeping, or reporting requirements; or requirements determined to be equivalent to an otherwise applicable requirement contained in the Alternative Requirements attachment of this permit. Units complying with an approved alternative requirement have reference to the approval in the Applicable Requirements summary listing for the unit. The permit holder shall maintain the original documentation, from the TCEQ Executive Director, demonstrating the method or limitation utilized. Documentation shall be maintained and made available in accordance with 30 TAC § 122.144.

Permit Location

25. The permit holder shall maintain a copy of this permit and records related to requirements listed in this permit on site.

Permit Shield (30 TAC § 122.148)

26. A permit shield is granted for the emission units, groups, or processes specified in the attached "Permit Shield." Compliance with the conditions of the permit shall be deemed compliance with the specified potentially applicable requirements or specified potentially applicable state-only requirements listed in the attachment "Permit Shield." Permit shield provisions shall not be modified by the executive director until notification is provided to the permit holder. No later than 90 days after notification of a change in a determination made by the executive director, the permit holder shall apply for the appropriate permit revision to reflect the new determination. Provisional terms are not eligible for this permit shield. Any term or condition, under a permit shield, shall not be protected by the permit shield if it is replaced by a provisional term or condition or the basis of the term and condition changes.

Attachments

Applicable Requirements Summary

Additional Monitoring Requirements

Permit Shield

New Source Review Authorization References

Alternative Requirement

Applicable Requirements Summary

| | |
|---------------------------|-----------|
| Unit Summary | 14 |
|---------------------------|-----------|

| | |
|--|-----------|
| Applicable Requirements Summary | 21 |
|--|-----------|

Note: A “none” entry may be noted for some emission sources in this permit’s “Applicable Requirements Summary” under the heading of “Monitoring and Testing Requirements” and/or “Recordkeeping Requirements” and/or “Reporting Requirements.” Such a notation indicates that there are no requirements for the indicated emission source as identified under the respective column heading(s) for the stated portion of the regulation when the emission source is operating under the conditions of the specified SOP Index Number. However, other relevant requirements pursuant to 30 TAC Chapter 122 including Recordkeeping Terms and Conditions (30 TAC § 122.144), Reporting Terms and Conditions (30 TAC § 122.145), and Compliance Certification Terms and Conditions (30 TAC § 122.146) continue to apply.

Unit Summary

| Unit/Group/ Process ID No. | Unit Type | Group/Inclusive Units | SOP Index No. | Regulation | Requirement Driver |
|-------------------------------|--|--------------------------|---------------|--|-------------------------|
| B77APCF401 | EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS | N/A | R5121-01 | 30 TAC Chapter 115, Vent Gas Controls | No changing attributes. |
| B77APCF402 | EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS | N/A | R5121-01 | 30 TAC Chapter 115, Vent Gas Controls | No changing attributes. |
| B77APCT1 | INDUSTRIAL PROCESS COOLING TOWERS | N/A | R5760-01 | 30 TAC Chapter 115, HRVOC Cooling Towers | No changing attributes. |
| B77APD108 | EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS | N/A | R5121-01 | 30 TAC Chapter 115, Vent Gas Controls | No changing attributes. |
| B77APD109 | EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS | N/A | R5121-01 | 30 TAC Chapter 115, Vent Gas Controls | No changing attributes. |
| B77APFU1 | FUGITIVE EMISSION UNITS | N/A | R5780-ALL | 30 TAC Chapter 115, HRVOC Fugitive Emissions | No changing attributes. |
| B77APFU1 | FUGITIVE EMISSION UNITS | N/A | R5352-ALL | 30 TAC Chapter 115, Pet. Refinery & Petrochemicals | No changing attributes. |
| B77APFU1 | FUGITIVE EMISSION UNITS | N/A | 63FFFF-01 | 40 CFR Part 63, Subpart FFFF | No changing attributes. |
| B77APLR1 | LOADING/UNLOADING OPERATIONS | N/A | R5211-01 | 30 TAC Chapter 115, Loading and Unloading of VOC | No changing attributes. |
| B77APLR133 | LOADING/UNLOADING OPERATIONS | N/A | R5211-01 | 30 TAC Chapter 115, Loading and Unloading of VOC | No changing attributes. |
| B77APLR750 | LOADING/UNLOADING OPERATIONS | N/A | R5211-01 | 30 TAC Chapter 115, Loading and Unloading of VOC | No changing attributes. |

Unit Summary

| Unit/Group/ Process ID No. | Unit Type | Group/Inclusive Units | SOP Index No. | Regulation | Requirement Driver |
|-------------------------------|--|--------------------------|---------------|---|-------------------------|
| B77APPT10 | EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS | N/A | R5121-01 | 30 TAC Chapter 115, Vent Gas Controls | No changing attributes. |
| B77APPT10A | EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS | N/A | R5121-01 | 30 TAC Chapter 115, Vent Gas Controls | No changing attributes. |
| B77APPT11 | EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS | N/A | R5121-01 | 30 TAC Chapter 115, Vent Gas Controls | No changing attributes. |
| B77APPT11A | EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS | N/A | R5121-01 | 30 TAC Chapter 115, Vent Gas Controls | No changing attributes. |
| B77APPT12 | EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS | N/A | R5121-01 | 30 TAC Chapter 115, Vent Gas Controls | No changing attributes. |
| B77APPT12A | EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS | N/A | R5121-01 | 30 TAC Chapter 115, Vent Gas Controls | No changing attributes. |
| B77APPVAV | EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS | N/A | R5720-01 | 30 TAC Chapter 115, HRVOC Vent Gas | No changing attributes. |
| B77APSC07 | SOLVENT DEGREASING MACHINES | N/A | R5412-01 | 30 TAC Chapter 115, Degreasing Processes | No changing attributes. |
| B77APSC07 | CLEANING/DEPAINTING OPERATION | N/A | R5460-01 | 30 TAC Chapter 115, Subchapter E, Division 6 | No changing attributes. |
| B77APSP101 | EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS | N/A | R5720-01 | 30 TAC Chapter 115, HRVOC Vent Gas | No changing attributes. |
| B77APSP101 | EMISSION | N/A | R5121-01 | 30 TAC Chapter 115, Vent | No changing attributes. |

Unit Summary

| Unit/Group/ Process ID No. | Unit Type | Group/Inclusive Units | SOP Index No. | Regulation | Requirement Driver |
|-------------------------------|--|--------------------------|---------------|--|-------------------------|
| | POINTS/STATIONARY VENTS/PROCESS VENTS | | | Gas Controls | |
| B77APSPS1 | VOLATILE ORGANIC COMPOUND WATER SEPARATORS | N/A | R5131-01 | 30 TAC Chapter 115, Water Separation | No changing attributes. |
| B77APSPS2 | VOLATILE ORGANIC COMPOUND WATER SEPARATORS | N/A | R5131-01 | 30 TAC Chapter 115, Water Separation | No changing attributes. |
| B77APSPS3 | VOLATILE ORGANIC COMPOUND WATER SEPARATORS | N/A | R5131-01 | 30 TAC Chapter 115, Water Separation | No changing attributes. |
| B77APST1 | STORAGE TANKS/VESSELS | N/A | R5112-01 | 30 TAC Chapter 115, Storage of VOCs | No changing attributes. |
| B77APST10 | STORAGE TANKS/VESSELS | N/A | R5112-01 | 30 TAC Chapter 115, Storage of VOCs | No changing attributes. |
| B77APST11 | STORAGE TANKS/VESSELS | N/A | R5112-01 | 30 TAC Chapter 115, Storage of VOCs | No changing attributes. |
| B77APST12 | STORAGE TANKS/VESSELS | N/A | R5112-01 | 30 TAC Chapter 115, Storage of VOCs | No changing attributes. |
| B77APST133 | EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS | N/A | R5121-01 | 30 TAC Chapter 115, Vent Gas Controls | No changing attributes. |
| B77APST8 | STORAGE TANKS/VESSELS | N/A | R5112-01 | 30 TAC Chapter 115, Storage of VOCs | No changing attributes. |
| B77APSTT14 | STORAGE TANKS/VESSELS | N/A | R5112-01 | 30 TAC Chapter 115, Storage of VOCs | No changing attributes. |
| B77APSTT15 | STORAGE TANKS/VESSELS | N/A | R5112-01 | 30 TAC Chapter 115, Storage of VOCs | No changing attributes. |

Unit Summary

| Unit/Group/ Process ID No. | Unit Type | Group/Inclusive Units | SOP Index No. | Regulation | Requirement Driver |
|-------------------------------|--|--------------------------|---------------|--|-------------------------|
| B77APV101 | EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS | N/A | R5720-01 | 30 TAC Chapter 115, HRVOC Vent Gas | No changing attributes. |
| B77APV101 | EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS | N/A | R5121-01 | 30 TAC Chapter 115, Vent Gas Controls | No changing attributes. |
| B77APV102 | EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS | N/A | R5720-01 | 30 TAC Chapter 115, HRVOC Vent Gas | No changing attributes. |
| B77APV102 | EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS | N/A | R5121-01 | 30 TAC Chapter 115, Vent Gas Controls | No changing attributes. |
| B77SB101 | EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS | N/A | R5720-01 | 30 TAC Chapter 115, HRVOC Vent Gas | No changing attributes. |
| B77SB101 | EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS | N/A | R5121-01 | 30 TAC Chapter 115, Vent Gas Controls | No changing attributes. |
| B77SB102 | EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS | N/A | R5720-01 | 30 TAC Chapter 115, HRVOC Vent Gas | No changing attributes. |
| B77SB102 | EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS | N/A | R5121-01 | 30 TAC Chapter 115, Vent Gas Controls | No changing attributes. |
| B77SB103 | EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS | N/A | R5720-01 | 30 TAC Chapter 115, HRVOC Vent Gas | No changing attributes. |
| B77SB103 | EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS | N/A | R5121-01 | 30 TAC Chapter 115, Vent Gas Controls | No changing attributes. |

Unit Summary

| Unit/Group/ Process ID No. | Unit Type | Group/Inclusive Units | SOP Index No. | Regulation | Requirement Driver |
|-------------------------------|--|--------------------------|---------------|--|-------------------------|
| B77SB104 | EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS | N/A | R5720-01 | 30 TAC Chapter 115, HRVOC Vent Gas | No changing attributes. |
| B77SB104 | EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS | N/A | R5121-01 | 30 TAC Chapter 115, Vent Gas Controls | No changing attributes. |
| B77SB105 | EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS | N/A | R5720-01 | 30 TAC Chapter 115, HRVOC Vent Gas | No changing attributes. |
| B77SB105 | EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS | N/A | R5121-01 | 30 TAC Chapter 115, Vent Gas Controls | No changing attributes. |
| B77SB106 | EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS | N/A | R5720-01 | 30 TAC Chapter 115, HRVOC Vent Gas | No changing attributes. |
| B77SB106 | EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS | N/A | R5121-01 | 30 TAC Chapter 115, Vent Gas Controls | No changing attributes. |
| B77SB107 | EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS | N/A | R5720-01 | 30 TAC Chapter 115, HRVOC Vent Gas | No changing attributes. |
| B77SB107 | EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS | N/A | R5121-01 | 30 TAC Chapter 115, Vent Gas Controls | No changing attributes. |
| B77SPS102 | VOLATILE ORGANIC COMPOUND WATER SEPARATORS | N/A | R5131-01 | 30 TAC Chapter 115, Water Separation | No changing attributes. |
| B77SPS103 | EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS | N/A | R5121-01 | 30 TAC Chapter 115, Vent Gas Controls | No changing attributes. |

Unit Summary

| Unit/Group/ Process ID No. | Unit Type | Group/Inclusive Units | SOP Index No. | Regulation | Requirement Driver |
|-------------------------------|--|--------------------------|---------------|--|-------------------------|
| B78APF1 | FLARES | N/A | R1111-01 | 30 TAC Chapter 111, Visible Emissions | No changing attributes. |
| B78APF1 | FLARES | N/A | R5720-01 | 30 TAC Chapter 115, HRVOC Vent Gas | No changing attributes. |
| B78APF1 | FLARES | N/A | 60A-01 | 40 CFR Part 60, Subpart A | No changing attributes. |
| B78APF1 | FLARES | N/A | 63A-01 | 40 CFR Part 63, Subpart A | No changing attributes. |
| B78APF1 | EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS | N/A | 63FFFF-01 | 40 CFR Part 63, Subpart FFFF | No changing attributes. |
| B78APFU1 | FUGITIVE EMISSION UNITS | N/A | R5780-ALL | 30 TAC Chapter 115, HRVOC Fugitive Emissions | No changing attributes. |
| B78APFU1 | FUGITIVE EMISSION UNITS | N/A | R5352-ALL | 30 TAC Chapter 115, Pet. Refinery & Petrochemicals | No changing attributes. |
| B78APFU1 | FUGITIVE EMISSION UNITS | N/A | 63FFFF-01 | 40 CFR Part 63, Subpart FFFF | No changing attributes. |
| B78APKO2A | EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS | N/A | R5720-01 | 30 TAC Chapter 115, HRVOC Vent Gas | No changing attributes. |
| B78APKO2A | EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS | N/A | R5121-01 | 30 TAC Chapter 115, Vent Gas Controls | No changing attributes. |
| B78APPTT1 | STORAGE TANKS/VESSELS | N/A | R5112-01 | 30 TAC Chapter 115, Storage of VOCs | No changing attributes. |
| B78APST5 | STORAGE TANKS/VESSELS | N/A | R5112-01 | 30 TAC Chapter 115, Storage of VOCs | No changing attributes. |
| PROAPP | CLEANING/DEPAINTING OPERATION | N/A | R5460-01 | 30 TAC Chapter 115, Subchapter E, Division 6 | No changing attributes. |
| PROAPP | CHEMICAL | N/A | 63FFFF-01 | 40 CFR Part 63, Subpart | No changing attributes. |

Unit Summary

| Unit/Group/ Process ID No. | Unit Type | Group/Inclusive Units | SOP Index No. | Regulation | Requirement Driver |
|-------------------------------|--------------------------|--------------------------|---------------|------------|--------------------|
| | MANUFACTURING PROCESS | | | FFFF | |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|---------------------|--|---|---|--|--|---|
| B77APCF401 | EP | R5121-01 | VOC | 30 TAC Chapter 115, Vent Gas Controls | § 115.127(a)(1) [G]§ 115.122(a)(4) | A vent gas stream from a LDPE plant is exempt from §115.121(a)(1) if less than or equal to 1.1 pounds of ethylene per 1,000 pounds (1.1 kg/1000 kg) of product are emitted from all the specified vent gas streams. | [G]§ 115.125 § 115.126(2) § 115.126(3)(A) | § 115.126 § 115.126(2) § 115.126(3) § 115.126(3)(A) | None |
| B77APCF402 | EP | R5121-01 | VOC | 30 TAC Chapter 115, Vent Gas Controls | § 115.127(a)(1) [G]§ 115.122(a)(4) | A vent gas stream from a LDPE plant is exempt from §115.121(a)(1) if less than or equal to 1.1 pounds of ethylene per 1,000 pounds (1.1 kg/1000 kg) of product are emitted from all the specified vent gas streams. | [G]§ 115.125 § 115.126(2) § 115.126(3)(A) | § 115.126 § 115.126(2) § 115.126(3) § 115.126(3)(A) | None |
| B77APCT1 | EU | R5760-01 | Highly Reactive VOC | 30 TAC Chapter 115, HRVOC Cooling Towers | § 115.767(6) § 115.764(a)(1) § 115.766(i) | All sites that are subject to this division and that are located in the Houston/ Galveston/Brazoria area as defined in § 115.10, excluding Harris County, are exempt from § 115.761(b) and (c)(2), except as provided in § 115.769(a)(3). | § 115.764(a)(1) § 115.764(a)(3) [G]§ 115.764(a)(6) § 115.764(c) | § 115.766(a)(1) § 115.766(a)(2) § 115.766(a)(3) § 115.766(a)(5) § 115.766(a)(6) § 115.766(c) § 115.766(i)(1) | § 115.766(i)(2) |
| B77APD108 | EP | R5121-01 | VOC | 30 TAC Chapter 115, Vent Gas Controls | § 115.127(a)(1) [G]§ 115.122(a)(4) | A vent gas stream from a LDPE plant is exempt from §115.121(a)(1) if less than or equal to 1.1 pounds of ethylene per 1,000 pounds (1.1 kg/1000 kg) of product are emitted from all the specified vent gas streams. | [G]§ 115.125 § 115.126(2) § 115.126(3)(A) | § 115.126 § 115.126(2) § 115.126(3) § 115.126(3)(A) | None |
| B77APD109 | EP | R5121-01 | VOC | 30 TAC Chapter 115, Vent Gas Controls | § 115.127(a)(1) [G]§ 115.122(a)(4) | A vent gas stream from a LDPE plant is exempt from §115.121(a)(1) if less than | [G]§ 115.125 § 115.126(2) § 115.126(3)(A) | § 115.126 § 115.126(2) § 115.126(3) | None |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|---------------------|--|--|--|--|--|---|
| | | | | | | or equal to 1.1 pounds of ethylene per 1,000 pounds (1.1 kg/1000 kg) of product are emitted from all the specified vent gas streams. | | § 115.126(3)(A) | |
| B77APFU1 | EU | R5780-ALL | Highly Reactive VOC | 30 TAC Chapter 115, HRVOC Fugitive Emissions | § 115.781(b)(9) § 115.780(b) [G]§ 115.781(a) § 115.781(g)(3) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) [G]§ 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) [G]§ 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv) § 115.783(4)(A)(i) § 115.783(4)(A)(ii) § 115.783(4)(A)(ii)(I) § 115.783(4)(A)(ii)(II) § 115.783(4)(B) § 115.783(4)(B)(i) § 115.783(4)(B)(ii) | Process drains within a petroleum refinery; synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process; or natural gas/gasoline processing operation in which a highly-reactive volatile organic compound is a raw material, intermediate, final product, or in a waste stream is subject to the requirements of this division. A leak is defined as a screening concentration greater than 500 ppmv above background as methane for all components. | § 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) § 115.781(b) § 115.781(b)(10) § 115.781(b)(3) § 115.781(b)(4) § 115.781(b)(5) § 115.781(b)(6) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(2) § 115.782(d)(2) | § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(5) § 115.781(b)(10) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) [G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g) | [G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) |
| B77APFU1 | EU | R5780-ALL | Highly Reactive VOC | 30 TAC Chapter 115, HRVOC Fugitive Emissions | § 115.781(b)(9) § 115.780(b) [G]§ 115.781(a) § 115.781(g)(3) § 115.782(a) § 115.782(b)(1) | Pressure relief valves (in gaseous service) within a petroleum refinery; synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing | § 115.354(1) § 115.354(10) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) | § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) | [G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.788(c) [G]§ 115.788(d) § 115.788(e) [G]§ 115.788(g) |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|---------------------|--|--|---|--|--|---|
| | | | | | § 115.782(b)(2) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) [G]§ 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) [G]§ 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv) § 115.787(e) § 115.787(f) § 115.787(g) § 115.788(a) § 115.788(a)(1) § 115.788(a)(2) § 115.788(a)(2)(A) § 115.788(a)(2)(B) § 115.788(a)(2)(C) § 115.788(a)(2)(C)(i) § 115.788(a)(2)(C)(ii) § 115.788(a)(2)(C)(iii) § 115.788(a)(2)(D) § 115.788(a)(3) § 115.788(a)(3)(A) § 115.788(a)(3)(B) [G]§ 115.788(g) | process; or natural gas/gasoline processing operation in which a highly-reactive volatile organic compound is a raw material, intermediate, final product, or in a waste stream is subject to the requirements of this division. A leak is defined as a screening concentration greater than 500 ppmv above background as methane for all components. | § 115.354(9) § 115.781(b) § 115.781(b)(10) § 115.781(b)(4) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) § 115.781(b)(8) § 115.781(e) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.782(d)(2) | § 115.356(3)(B) § 115.356(5) § 115.781(b)(10) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) [G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g) [G]§ 115.788(g) | |
| B77APFU1 | EU | R5780-ALL | Highly Reactive VOC | 30 TAC Chapter 115, HRVOC Fugitive Emissions | § 115.781(b)(9) § 115.780(b) [G]§ 115.781(a) § 115.781(g)(3) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) | Valves within a petroleum refinery; synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process; or natural gas/gasoline processing operation which | § 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) § 115.781(b) | § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) | § 115.782(c)(2)(A)(ii) [G]§ 115.786(c) § 115.788(c) [G]§ 115.788(d) § 115.788(e) [G]§ 115.788(g) |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|---------------------|--|---|--|--|--|--|
| | | | | | § 115.782(c)(2) § 115.782(c)(2)(A) § 115.782(c)(2)(A)(i) § 115.782(c)(2)(A)(ii) § 115.782(c)(2)(B) § 115.783(5) § 115.787(f) § 115.787(f)(4) § 115.787(g) § 115.788(a) § 115.788(a)(1) § 115.788(a)(2) § 115.788(a)(2)(A) § 115.788(a)(2)(B) § 115.788(a)(2)(C) § 115.788(a)(2)(C)(i) § 115.788(a)(2)(C)(ii) § 115.788(a)(2)(C)(iii) § 115.788(a)(2)(D) § 115.788(a)(3) § 115.788(a)(3)(A) § 115.788(a)(3)(B) [G]§ 115.788(g) | a highly-reactive volatile organic compound is a raw material, intermediate, final product, or in a waste stream is subject to the requirements of this division. A leak is defined as a screening concentration greater than 500 ppmv above background as methane for all components. | § 115.781(b)(10) § 115.781(b)(4) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.782(d)(2) | § 115.356(5) § 115.781(b)(10) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) § 115.782(c)(2)(A)(ii) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(2) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g) [G]§ 115.788(g) | |
| B77APFU1 | EU | R5780-ALL | Highly Reactive VOC | 30 TAC Chapter 115, HRVOC Fugitive Emissions | § 115.781(b)(9) § 115.780(b) [G]§ 115.781(a) § 115.781(g)(3) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) [G]§ | Flanges or other connectors within a petroleum refinery; synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process; or natural gas/gasoline processing operation in which a highly-reactive volatile organic compound is a raw material, | § 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) § 115.781(b) § 115.781(b)(10) § 115.781(b)(3) § 115.781(b)(4) | § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(5) § 115.781(b)(10) § 115.781(g) § 115.781(g)(1) | [G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.789(1)(B) |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|---------------------|--|--|--|--|--|--|
| | | | | | 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) [G]§ 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv) | intermediate, final product, or in a waste stream is subject to the requirements of this division. A leak is defined as a screening concentration greater than 500 ppmv above background as methane for all components. | § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) § 115.781(f) § 115.781(f)(1) § 115.781(f)(2) § 115.781(f)(3) § 115.781(f)(4) § 115.781(f)(5) § 115.781(f)(6) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.782(d)(2) § 115.789(1)(B) | § 115.781(g)(2) § 115.781(g)(3) [G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g) | |
| B77APFU1 | EU | R5780-ALL | Highly Reactive VOC | 30 TAC Chapter 115, HRVOC Fugitive Emissions | § 115.781(b)(9) § 115.780(b) [G]§ 115.781(a) § 115.781(g)(3) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) [G]§ 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) [G]§ 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv) § 115.782(c)(1)(C)(i) § 115.782(c)(1)(C)(i)(I) § | Compressor seals within a petroleum refinery; synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process; or natural gas/gasoline processing operation in which a highly-reactive volatile organic compound is a raw material, intermediate, final product, or in a waste stream is subject to the requirements of this division. A leak is defined as a screening concentration greater than 500 ppmv above background as methane for all components. | § 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) § 115.781(b) § 115.781(b)(10) § 115.781(b)(4) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) § 115.781(c)(1) § 115.781(c)(2) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.782(d)(2) | § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(5) § 115.781(b)(10) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) [G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g) | [G]§ 115.782(c)(1)(B)(i) § 115.783(3)(C) [G]§ 115.786(c) |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|---------------------|--|--|--|--|--|--|
| | | | | | 115.782(c)(1)(C)(i)(II) § 115.782(c)(1)(C)(i)(III) § 115.782(c)(1)(C)(ii) § 115.783(3) [G]§ 115.783(3)(A) [G]§ 115.783(3)(B) § 115.787(b) | | | | |
| B77APFU1 | EU | R5780-ALL | Highly Reactive VOC | 30 TAC Chapter 115, HRVOC Fugitive Emissions | § 115.781(b)(9) § 115.780(b) [G]§ 115.781(a) § 115.781(g)(3) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) [G]§ 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) [G]§ 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv) § 115.782(c)(1)(C)(i) § 115.782(c)(1)(C)(i)(I) § 115.782(c)(1)(C)(i)(II) § 115.782(c)(1)(C)(i)(| Pump seals within a petroleum refinery; synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process; or natural gas/gasoline processing operation in which a highly-reactive volatile organic compound is a raw material, intermediate, final product, or in a waste stream is subject to the requirements of this division. A leak is defined as a screening concentration greater than 500 ppmv above background as methane for all components. | § 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) § 115.781(b) § 115.781(b)(10) § 115.781(b)(4) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) § 115.781(c)(1) § 115.781(c)(2) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.782(d)(2) | § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(5) § 115.781(b)(10) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) [G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g) | [G]§ 115.782(c)(1)(B)(i) § 115.783(3)(C) [G]§ 115.786(c) |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|---------------------|--|--|---|---|--|--|
| | | | | | III) § 115.782(c)(1)(C)(ii) § 115.783(3) [G]§ 115.783(3)(A) [G]§ 115.783(3)(B) § 115.787(b) § 115.787(b)(1) | | | | |
| B77APFU1 | EU | R5780-ALL | Highly Reactive VOC | 30 TAC Chapter 115, HRVOC Fugitive Emissions | § 115.781(b)(9) § 115.780(b) [G]§ 115.781(a) § 115.781(g)(3) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) [G]§ 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) [G]§ 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv) § 115.782(c)(1)(C)(i) § 115.782(c)(1)(C)(i)(I) § 115.782(c)(1)(C)(i)(II) § 115.782(c)(1)(C)(i)(III) § 115.782(c)(1)(C)(ii) | Agitators within a petroleum refinery; synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process; or natural gas/gasoline processing operation in which a highly-reactive volatile organic compound is a raw material, intermediate, final product, or in a waste stream is subject to the requirements of this division. A leak is defined as a screening concentration greater than 500 ppmv above background as methane for all components. | § 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) § 115.781(b) § 115.781(b)(10) § 115.781(b)(3) § 115.781(b)(4) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) § 115.781(c)(1) § 115.781(c)(2) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.782(d)(2) | § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(5) § 115.781(b)(10) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) [G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g) | [G]§ 115.782(c)(1)(B)(i) § 115.783(3)(C) [G]§ 115.786(c) |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|---------------------|--|--|--|--|---|--|
| | | | | | § 115.783(3) [G]§ 115.783(3)(A) [G]§ 115.783(3)(B) § 115.787(b) | | | | |
| B77APFU1 | EU | R5780-ALL | Highly Reactive VOC | 30 TAC Chapter 115, HRVOC Fugitive Emissions | § 115.781(b)(9) § 115.358(c)(1) [G]§ 115.358(h) § 115.780(b) [G]§ 115.781(a) § 115.781(g)(3) § 115.782(a) § 115.782(b)(2) § 115.782(b)(3) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) [G]§ 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) [G]§ 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv) | Components within the process unit or processes listed in §115.780(a) is subject to the requirements of this division. If the owner of operator elects to use the alternative work practice in §115.358 of this title, a leak is defined as specified in §115.358 of this title, including any leak detected using the alternative work practice on a component that is subject to the requirements of this division but not specifically selected for alternative work practice monitoring. | § 115.354(1) § 115.354(11) § 115.354(13)(A) § 115.354(13)(B) § 115.354(13)(C) § 115.354(13)(D) § 115.354(13)(E) § 115.354(13)(F) § 115.354(4) § 115.354(5) § 115.354(9) § 115.358(c)(2) § 115.358(d) [G]§ 115.358(e) § 115.358(f) § 115.781(b) § 115.781(b)(4) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(h)(1) § 115.781(h)(2) § 115.781(h)(3) § 115.781(h)(4) § 115.781(h)(5) [G]§ 115.781(h)(6) § 115.782(b)(4) § 115.782(d)(1) § 115.788(h)(1) [G]§ 115.788(h)(2) § 115.788(h)(3) | § 115.354(13)(D) § 115.354(13)(E) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(4) § 115.356(5) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) [G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) [G]§ 115.786(f) § 115.786(g) | [G]§ 115.358(g) [G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|---------------------|--|--|--|--|--|--|
| B77APFU1 | EU | R5780-ALL | Highly Reactive VOC | 30 TAC Chapter 115, HRVOC Fugitive Emissions | § 115.781(b)(9) § 115.780(b) [G]§ 115.781(a) § 115.781(g)(3) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(2) § 115.782(c)(2)(A) § 115.782(c)(2)(A)(i) § 115.782(c)(2)(A)(ii) § 115.782(c)(2)(B) § 115.783(5) § 115.787(f) § 115.787(f)(2) § 115.787(f)(3) § 115.787(f)(4) § 115.787(g) § 115.788(a) § 115.788(a)(1) § 115.788(a)(2) § 115.788(a)(2)(A) § 115.788(a)(2)(B) § 115.788(a)(2)(C) § 115.788(a)(2)(C)(i) § 115.788(a)(2)(C)(ii) § 115.788(a)(2)(C)(iii) § 115.788(a)(2)(D) § 115.788(a)(3) § 115.788(a)(3)(A) § 115.788(a)(3)(B) [G]§ 115.788(g) | Open-ended valves or lines within a petroleum refinery; synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process; or natural gas/gasoline processing operation in which a highly-reactive volatile organic compound is a raw material, intermediate, final product, or in a waste stream is subject to the requirements of this division. A leak is defined as a screening concentration greater than 500 ppmv above background as methane for all components. | § 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) § 115.781(b) § 115.781(b)(10) § 115.781(b)(3) § 115.781(b)(4) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) § 115.781(f) § 115.781(f)(1) § 115.781(f)(2) § 115.781(f)(3) § 115.781(f)(4) § 115.781(f)(5) § 115.781(f)(6) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.782(d)(2) § 115.789(1)(B) | § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(5) § 115.781(b)(10) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) § 115.782(c)(2)(A)(ii) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(2) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g) [G]§ 115.788(g) | § 115.782(c)(2)(A)(ii) [G]§ 115.786(c) § 115.788(c) [G]§ 115.788(d) § 115.788(e) [G]§ 115.788(g) § 115.789(1)(B) |
| B77APFU1 | EU | R5780-ALL | Highly Reactive | 30 TAC Chapter 115, HRVOC | § 115.787(a) | Components that contact a process fluid containing less | None | § 115.786(e) § 115.786(g) | None |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|---------------------|--|--|--|---|--|---|
| | | | VOC | Fugitive Emissions | | than 5.0% highly-reactive volatile organic compounds by weight on an annual average basis are exempt from the requirements of this division (relating to Fugitive Emissions), except for 115.786(e) and (g) of this title (relating to Record keeping Requirements). | | | |
| B77APFU1 | EU | R5780-ALL | Highly Reactive VOC | 30 TAC Chapter 115, HRVOC Fugitive Emissions | § 115.781(b)(9) § 115.780(b) [G]§ 115.781(a) § 115.781(g)(3) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) [G]§ 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) [G]§ 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv) | Heat exchanger heads, sight glasses, meters, gauges, sampling connections, bolted manways, hatches, sump covers, junction box vents, and covers and seals on VOC water separators within the process unit or processes listed in §115.780(a) in which a HRVOC is a raw material, intermediate, final product, or in a waste stream is subject to the requirements of this division. A leak is defined as a screening concentration greater than 500 ppmv above background as methane for all components. | § 115.781(b) § 115.781(b)(10) § 115.781(b)(3) § 115.781(b)(4) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) § 115.781(f) § 115.781(f)(1) § 115.781(f)(2) § 115.781(f)(3) § 115.781(f)(4) § 115.781(f)(5) § 115.781(f)(6) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.782(d)(2) § 115.789(1)(B) | § 115.781(b)(10) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) [G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g) | [G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.789(1)(B) |
| B77APFU1 | EU | R5780-ALL | Highly Reactive VOC | 30 TAC Chapter 115, HRVOC Fugitive Emissions | § 115.781(b)(9) § 115.780(b) [G]§ 115.781(a) [G]§ 115.781(d) § 115.781(g)(3) § 115.782(a) § 115.782(b)(1) | Bypass line valves within a petroleum refinery; synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process; or natural gas/gasoline processing | § 115.781(b) § 115.781(b)(10) § 115.781(b)(4) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) [G]§ 115.781(d) | § 115.781(b)(10) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) § 115.782(c)(2)(A)(ii) § 115.786(a)(1) | § 115.782(c)(2)(A)(ii) [G]§ 115.786(c) § 115.788(c) [G]§ 115.788(d) § 115.788(e) [G]§ 115.788(g) |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|---------------------|--|--|---|--|--|--|
| | | | | | § 115.782(b)(2) § 115.782(c)(2) § 115.782(c)(2)(A) § 115.782(c)(2)(A)(i) § 115.782(c)(2)(A)(ii) § 115.782(c)(2)(B) § 115.783(1) § 115.783(1)(A) § 115.783(1)(B) § 115.783(5) § 115.787(f) § 115.787(f)(4) § 115.787(g) § 115.788(a) § 115.788(a)(1) § 115.788(a)(2) § 115.788(a)(2)(A) § 115.788(a)(2)(B) § 115.788(a)(2)(C) § 115.788(a)(2)(C)(i) § 115.788(a)(2)(C)(ii) § 115.788(a)(2)(C)(iii) § 115.788(a)(2)(D) § 115.788(a)(3) § 115.788(a)(3)(A) § 115.788(a)(3)(B) [G]§ 115.788(g) | operation in which a highly-reactive volatile organic compound is a raw material, intermediate, final product, or in a waste stream is subject to the requirements of this division. A leak is defined as a screening concentration greater than 500 ppmv above background as methane for all components. | § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.782(d)(2) § 115.786(a)(1) | § 115.786(a)(2) § 115.786(a)(2)(A) § 115.786(a)(2)(B) § 115.786(b)(1) § 115.786(b)(2) § 115.786(b)(2)(A) § 115.786(b)(2)(B) § 115.786(b)(2)(C) [G]§ 115.786(b)(3) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(2) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g) [G]§ 115.788(g) | |
| B77APFU1 | EU | R5780-ALL | Highly Reactive VOC | 30 TAC Chapter 115, HRVOC Fugitive Emissions | § 115.787(d) § 115.780(b) [G]§ 115.781(a) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(1) | All agitators that are equipped with a shaft sealing system that prevents or detects emissions of VOC from the seal are exempt from the monitoring requirement of | § 115.782(d)(2) | [G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) | [G]§ 115.782(c)(1)(B)(i) § 115.783(3)(C) [G]§ 115.786(c) |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|---------------------|--|---|---|-------------------------------------|---|--|
| | | | | | § 115.782(c)(1)(A) § 115.782(c)(1)(B) [G]§ 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) [G]§ 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv) § 115.782(c)(1)(C)(i) § 115.782(c)(1)(C)(i)(I) § 115.782(c)(1)(C)(i)(II) § 115.782(c)(1)(C)(i)(III) § 115.782(c)(1)(C)(ii) § 115.783(3) [G]§ 115.783(3)(A) [G]§ 115.783(3)(B) § 115.787(b) § 115.787(b)(1) § 115.787(g) | §115.781(b) and (c). Submerged pumps or sealless pumps may be used to satisfy the requirements of this subsection. | | § 115.786(d)(2)(C) § 115.786(e) § 115.786(g) | |
| B77APFU1 | EU | R5780-ALL | Highly Reactive VOC | 30 TAC Chapter 115, HRVOC Fugitive Emissions | § 115.787(d) § 115.780(b) [G]§ 115.781(a) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) [G]§ | All pumps that are equipped with a shaft sealing system that prevents or detects emissions of VOC from the seal are exempt from the monitoring requirement of §115.781(b) and (c). Submerged pumps or sealless pumps may be used to satisfy the | § 115.782(d)(2) | [G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g) | [G]§ 115.782(c)(1)(B)(i) § 115.783(3)(C) [G]§ 115.786(c) |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|---------------------|--|--|--|-------------------------------------|---|--|
| | | | | | 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) [G]§ 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv) § 115.782(c)(1)(C)(i) § 115.782(c)(1)(C)(i)(I) § 115.782(c)(1)(C)(i)(II) § 115.782(c)(1)(C)(i)(III) § 115.782(c)(1)(C)(ii) § 115.783(3) [G]§ 115.783(3)(A) [G]§ 115.783(3)(B) § 115.787(b) § 115.787(b)(1) § 115.787(g) | requirements of this subsection. | | | |
| B77APFU1 | EU | R5780-ALL | Highly Reactive VOC | 30 TAC Chapter 115, HRVOC Fugitive Emissions | § 115.787(d) § 115.780(b) [G]§ 115.781(a) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) [G]§ 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) | All compressors that are equipped with a shaft sealing system that prevents or detects emissions of VOC from the seal are exempt from the monitoring requirement of §115.781(b) and (c). Submerged pumps or sealless pumps may be used to satisfy the requirements of this subsection. | § 115.782(d)(2) | [G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g) | [G]§ 115.782(c)(1)(B)(i) § 115.783(3)(C) [G]§ 115.786(c) |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|-----------|--|---|--|--|---|---|
| | | | | | [G]§ 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv) § 115.782(c)(1)(C)(i) § 115.782(c)(1)(C)(i)(I) § 115.782(c)(1)(C)(i)(II) § 115.782(c)(1)(C)(i)(III) § 115.782(c)(1)(C)(ii) § 115.783(3) [G]§ 115.783(3)(A) [G]§ 115.783(3)(B) § 115.787(b) § 115.787(b)(1) § 115.787(g) | | | | |
| B77APFU1 | EU | R5352-ALL | VOC | 30 TAC Chapter 115, Pet. Refinery & Petrochemicals | § 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1) § 115.357(8) | No compressor seals contacting a fluid with TVP less than or equal to 0.044 psia (heavy liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound. | § 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1) | § 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5) | None |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|-----------|--|---|---|---|--|---|
| B77APFU1 | EU | R5352-ALL | VOC | 30 TAC Chapter 115, Pet. Refinery & Petrochemicals | § 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8) | No compressor seals contacting a fluid with TVP greater than 0.044 psia (gas/vapor or light liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound. | § 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 | § 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5) | None |
| B77APFU1 | EU | R5352-ALL | VOC | 30 TAC Chapter 115, Pet. Refinery & Petrochemicals | § 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(4) § 115.357(8) | No pump seals that are equipped with a shaft sealing system that prevents or detects emissions of VOCs from the seal shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound. | [G]§ 115.355 | § 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5) | None |
| B77APFU1 | EU | R5352-ALL | VOC | 30 TAC Chapter 115, Pet. Refinery & Petrochemicals | § 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) | No pump seals contacting a fluid with TVP less than or equal to 0.044 psia (heavy liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery which | § 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1) | § 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5) | None |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|-----------|--|---|---|---|--|---|
| | | | | | § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1) § 115.357(8) | exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound. | | | |
| B77APFU1 | EU | R5352-ALL | VOC | 30 TAC Chapter 115, Pet. Refinery & Petrochemicals | § 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8) | No pump seals contacting a fluid with TVP greater than 0.044 psia (gas/vapor or light liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound. | § 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 | § 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5) | None |
| B77APFU1 | EU | R5352-ALL | VOC | 30 TAC Chapter 115, Pet. Refinery & Petrochemicals | § 115.352(1)(C) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(8) § 115.358(c)(1) [G]§ 115.358(h) | If the owner or operator elects to use the alternative work practice in §115.358, no component shall be allowed to have a VOC leak, detected as defined in §115.358, for more than 15 days after discovery. This includes any leak detected using the alternative work practice on a component that is subject to the requirements of this division but not specifically selected for alternative work practice | § 115.354(1) § 115.354(11) § 115.354(13)(A) § 115.354(13)(B) § 115.354(13)(C) § 115.354(13)(D) § 115.354(13)(E) § 115.354(13)(F) § 115.354(4) § 115.354(5) § 115.354(9) [G]§ 115.355 § 115.358(c)(2) § 115.358(d) [G]§ 115.358(e) | § 115.352(7) § 115.354(13)(D) § 115.354(13)(E) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) [G]§ 115.356(4) § 115.356(5) | [G]§ 115.358(g) |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|-----------|--|---|--|---|---|---|
| | | | | | | monitoring. | § 115.358(f) | | |
| B77APFU1 | EU | R5352-ALL | VOC | 30 TAC Chapter 115, Pet. Refinery & Petrochemicals | § 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(8) § 115.357(9) | No valves contacting a fluid with TVP less than or equal to 0.044 psia (heavy liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound. | § 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 § 115.357(1) | § 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5) | [G]§ 115.354(7) |
| B77APFU1 | EU | R5352-ALL | VOC | 30 TAC Chapter 115, Pet. Refinery & Petrochemicals | § 115.357(2) § 115.352(9) | Conservation vents or other devices on atmospheric storage tanks that are actuated either by a vacuum or a pressure of no more than 2.5 psig, pressure relief valves (PRVs) equipped with a rupture disk or venting to a control device, components in continuous vacuum service, and valves that are not externally regulated (i.e. in-line check valves) are exempt from the requirements of this division, except that each PRV equipped with a rupture disk must comply with §115.352(9) and §115.356(3)(C). | None | § 115.356 § 115.356(3) [G]§ 115.356(3)(C) | None |
| B77APFU1 | EU | R5352-ALL | VOC | 30 TAC Chapter 115, Pet. Refinery | § 115.352(1)(B) § 115.352(1) | No compressor seals in hydrogen service with a | [G]§ 115.355 | § 115.352(7) § 115.356 | None |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|-----------|--|---|---|-------------------------------------|--|--|
| | | | | & Petrochemicals | § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(3) § 115.357(8) | hydrogen content that can be demonstrated to always exceed 50.0% by volume shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound. | | [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5) | |
| B77APFU1 | EU | R5352-ALL | VOC | 30 TAC Chapter 115, Pet. Refinery & Petrochemicals | § 115.357(5) | Reciprocating compressors and positive displacement pumps used in natural gas/gasoline processing operations are exempt from the requirements of this division except §115.356(3)(C) of this title. | None | § 115.356 § 115.356(3) [G]§ 115.356(3)(C) | None |
| B77APFU1 | EU | R5352-ALL | VOC | 30 TAC Chapter 115, Pet. Refinery & Petrochemicals | § 115.357(10) | Instrumentation systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet 40 CFR §63.169 (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title. | None | § 115.356 § 115.356(3) [G]§ 115.356(3)(C) | None |
| B77APFU1 | EU | R5352-ALL | VOC | 30 TAC Chapter 115, Pet. Refinery & Petrochemicals | § 115.357(11) | Sampling connection systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet the requirements of 40 CFR §63.166(a) and (b) (June 20, 1996) are exempt from the requirements of this | None | § 115.356 § 115.356(3) [G]§ 115.356(3)(C) | None |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|-----------|--|--|--|--|---|---|
| | | | | | | division except §115.356(3)(C) of this title. | | | |
| B77APFU1 | EU | R5352-ALL | VOC | 30 TAC Chapter 115, Pet. Refinery & Petrochemicals | § 115.357(13) | Components/systems that contact a process fluid containing VOC having a true vapor pressure equal to or less than 0.002 psia at 68 degrees Fahrenheit are exempt from the requirements of this division except §115.356(3)(C) of this title. | None | § 115.356 § 115.356(3) [G]§ 115.356(3)(C) | None |
| B77APFU1 | EU | R5352-ALL | VOC | 30 TAC Chapter 115, Pet. Refinery & Petrochemicals | § 115.357(6) | Components at a petroleum refinery or synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process, that contact a process fluid that contains less than 10% VOC by weight are exempt from the requirements of this division except §115.356(3)(C) of this title. | None | § 115.356 § 115.356(3) [G]§ 115.356(3)(C) | None |
| B77APFU1 | EU | R5352-ALL | VOC | 30 TAC Chapter 115, Pet. Refinery & Petrochemicals | § 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7) § 115.357(1) | No process drains contacting a fluid with TVP less than or equal to 0.044 psia (heavy liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound. | § 115.354(1) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1) | § 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5) | None |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|-----------|--|---|--|---|---|---|
| B77APFU1 | EU | R5352-ALL | VOC | 30 TAC Chapter 115, Pet. Refinery & Petrochemicals | § 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7) | No process drains contacting a fluid with TVP greater than 0.044 psia (gas/vapor or light liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound. | § 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 | § 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(5) | None |
| B77APFU1 | EU | R5352-ALL | VOC | 30 TAC Chapter 115, Pet. Refinery & Petrochemicals | § 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(9) § 115.357(1) § 115.357(8) § 115.357(9) | No pressure relief valves contacting a fluid with TVP less than or equal to 0.044 psia (heavy liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound. | § 115.354(1) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 § 115.357(1) | § 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5) | [G]§ 115.354(7) |
| B77APFU1 | EU | R5352-ALL | VOC | 30 TAC Chapter 115, Pet. Refinery & Petrochemicals | § 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(7) | No pressure relief valves contacting a fluid with TVP greater than 0.044 psia (gas/vapor or light liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a | § 115.354(1) § 115.354(10) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) | § 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) | [G]§ 115.354(7) |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|-----------|--|--|--|--|--|---|
| | | | | | § 115.352(9) § 115.357(12) § 115.357(8) § 115.357(9) | screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound. | [G]§ 115.355 | [G]§ 115.356(3)(C) § 115.356(5) | |
| B77APFU1 | EU | R5352-ALL | VOC | 30 TAC Chapter 115, Pet. Refinery & Petrochemicals | § 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(8) § 115.357(9) | No open-ended valves or lines contacting a fluid with TVP less than or equal to 0.044 psia (heavy liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound. | § 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 § 115.357(1) | § 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5) | [G]§ 115.354(7) |
| B77APFU1 | EU | R5352-ALL | VOC | 30 TAC Chapter 115, Pet. Refinery & Petrochemicals | § 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8) § 115.357(9) | No open-ended valves or lines contacting a fluid with TVP greater than 0.044 psia (gas/vapor or light liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound. | § 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 | § 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5) | [G]§ 115.354(7) |
| B77APFU1 | EU | R5352- | VOC | 30 TAC Chapter | § 115.352(1)(A) | No valves contacting a fluid | § 115.354(1) | § 115.352(7) | [G]§ 115.354(7) |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|-----------|--|---|--|--|--|---|
| | | ALL | | 115, Pet. Refinery & Petrochemicals | § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8) § 115.357(9) | with TVP greater than 0.044 psia (gas/vapor or light liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound. | § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 | § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5) | |
| B77APFU1 | EU | R5352-ALL | VOC | 30 TAC Chapter 115, Pet. Refinery & Petrochemicals | § 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(8) § 115.357(1) § 115.357(12) § 115.357(8) | No flanges or other connectors contacting a fluid with TVP less than or equal to 0.044 psia (heavy liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound. | § 115.354(1) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1) | § 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5) | None |
| B77APFU1 | EU | R5352-ALL | VOC | 30 TAC Chapter 115, Pet. Refinery & Petrochemicals | § 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(8) | No flanges or other connectors contacting a fluid with TVP greater than 0.044 psia (gas/vapor or light liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery which | § 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 | § 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) | None |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|-----------|--|--|--|-------------------------------------|---|---|
| | | | | | § 115.357(12) § 115.357(8) | exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound. | | [G]§ 115.356(3)(C) § 115.356(5) | |
| B77APFU1 | EU | R5352-ALL | VOC | 30 TAC Chapter 115, Pet. Refinery & Petrochemicals | § 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(7) § 115.357(1) § 115.357(8) | No agitators contacting a fluid with TVP less than or equal to 0.044 psia (heavy liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound. | [G]§ 115.355 § 115.357(1) | § 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5) | None |
| B77APFU1 | EU | R5352-ALL | VOC | 30 TAC Chapter 115, Pet. Refinery & Petrochemicals | § 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(7) § 115.357(8) | No agitators contacting a fluid with TVP greater than 0.044 psia (gas/vapor or light liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound. | [G]§ 115.355 | § 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5) | None |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|-------------|--|--|---|---|---|---|
| B77APFU1 | EU | R5352-ALL | VOC | 30 TAC Chapter 115, Pet. Refinery & Petrochemicals | § 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(4) § 115.357(8) | No compressor seals that are equipped with a shaft sealing system that prevents or detects emissions of VOCs from the seal shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound. | [G]§ 115.355 | § 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5) | None |
| B77APFU1 | EU | 63FFFF-01 | 112(B) HAPS | 40 CFR Part 63, Subpart FFFF | § 63.2480(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart FFFF | The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart FFFF | The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart FFFF | The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart FFFF | The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart FFFF |
| B77APLR1 | EU | R5211-01 | VOC | 30 TAC Chapter 115, Loading and Unloading of VOC | § 115.213(b) § 115.212(a)(3)(B) § 115.212(a)(3)(E) § 115.213(b)(1) § 115.213(b)(4) [G]§ 115.213(b)(6) § 115.214(a)(1)(B) § 115.214(a)(1)(D) § 115.214(a)(1)(D)(ii) | As an alternative to §115.212(a)(1), loading operations may elect to achieve a 90% overall control of emissions at the account when loading VOC with true vapor pressure greater than 0.5 psia, but less than 11.0 psia, provided that the conditions specified in §115.213(b)(1)-(6) are met. | § 115.212(a)(3)(B) § 115.213(b) § 115.213(b)(1) § 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.215 § 115.215(1) § 115.215(10) [G]§ 115.215(2) § 115.215(4) § 115.215(9) | § 115.213(b)(1) § 115.216 § 115.216(2) § 115.216(3)(A) § 115.216(3)(A)(i) § 115.216(3)(A)(ii) § 115.216(3)(A)(iii) § 115.216(3)(B) | § 115.213(b)(1) § 115.213(b)(2) § 115.213(b)(3) § 115.213(b)(4) |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|-----------|--|---|---|--|---|---|
| B77APLR133 | EU | R5211-01 | VOC | 30 TAC Chapter 115, Loading and Unloading of VOC | § 115.217(a)(1) § 115.212(a)(2) § 115.214(a)(1)(B) § 115.214(a)(1)(D) § 115.214(a)(1)(D)(i) | Vapor pressure (at land-based operations). All land-based loading and unloading of VOC with a true vapor pressure less than 0.5 psia is exempt from the requirements of this division, except as specified. | § 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.215 § 115.215(4) | § 115.216 § 115.216(2) § 115.216(3)(B) | None |
| B77APLR750 | EU | R5211-01 | VOC | 30 TAC Chapter 115, Loading and Unloading of VOC | § 115.217(a)(1) § 115.214(a)(1)(B) § 115.214(a)(1)(D) § 115.214(a)(1)(D)(i) | Vapor pressure (at land-based operations). All land-based loading and unloading of VOC with a true vapor pressure less than 0.5 psia is exempt from the requirements of this division, except as specified. | § 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.215 § 115.215(4) | § 115.216 § 115.216(2) § 115.216(3)(B) | None |
| B77APPT10 | EP | R5121-01 | VOC | 30 TAC Chapter 115, Vent Gas Controls | § 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2) | A vent gas stream having a combined weight of volatile organic compounds (VOC) equal to or less than 100 pounds in any continuous 24-hour period is exempt from §115.121(a)(1) of this title. | [G]§ 115.125 § 115.126(2) | § 115.126 § 115.126(2) § 115.126(4) | None |
| B77APPT10A | EP | R5121-01 | VOC | 30 TAC Chapter 115, Vent Gas Controls | § 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2) | A vent gas stream having a combined weight of volatile organic compounds (VOC) equal to or less than 100 pounds in any continuous 24-hour period is exempt from §115.121(a)(1) of this title. | [G]§ 115.125 § 115.126(2) | § 115.126 § 115.126(2) § 115.126(4) | None |
| B77APPT11 | EP | R5121-01 | VOC | 30 TAC Chapter 115, Vent Gas Controls | § 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2) | A vent gas stream having a combined weight of volatile organic compounds (VOC) | [G]§ 115.125 § 115.126(2) | § 115.126 § 115.126(2) § 115.126(4) | None |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|---------------------|---------------------------------------|---|---|-------------------------------------|---|---|
| | | | | | | equal to or less than 100 pounds in any continuous 24-hour period is exempt from §115.121(a)(1) of this title. | | | |
| B77APPT11 A | EP | R5121-01 | VOC | 30 TAC Chapter 115, Vent Gas Controls | § 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2) | A vent gas stream having a combined weight of volatile organic compounds (VOC) equal to or less than 100 pounds in any continuous 24-hour period is exempt from §115.121(a)(1) of this title. | [G]§ 115.125 § 115.126(2) | § 115.126 § 115.126(2) § 115.126(4) | None |
| B77APPT12 | EP | R5121-01 | VOC | 30 TAC Chapter 115, Vent Gas Controls | § 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2) | A vent gas stream having a combined weight of volatile organic compounds (VOC) equal to or less than 100 pounds in any continuous 24-hour period is exempt from §115.121(a)(1) of this title. | [G]§ 115.125 § 115.126(2) | § 115.126 § 115.126(2) § 115.126(4) | None |
| B77APPT12 A | EP | R5121-01 | VOC | 30 TAC Chapter 115, Vent Gas Controls | § 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2) | A vent gas stream having a combined weight of volatile organic compounds (VOC) equal to or less than 100 pounds in any continuous 24-hour period is exempt from §115.121(a)(1) of this title. | [G]§ 115.125 § 115.126(2) | § 115.126 § 115.126(2) § 115.126(4) | None |
| B77APPVAV | EP | R5720-01 | Highly Reactive VOC | 30 TAC Chapter 115, HRVOC Vent Gas | § 115.727(c)(2) | A vent gas stream that has the potential to emit HRVOCs, but has a concentration less than 100 ppmv at all times or has a maximum potential flow rate equal to or less than 100 dry standard cubic feet per | None | § 115.726(e)(3)(A) § 115.726(j)(2) | None |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|---------------------|--|--|---|---|---|---|
| | | | | | | hour is exempt from this division with the exception of § 115.726(e)(3)(A) of this title. The maximum potential HRVOC emissions for the sum of all vent gas streams claimed under this exemption, must be less for the account specified in § 115.722(a) or (b) of this title than 0.5 tpy. | | | |
| B77APSC07 | EU | R5412-01 | VOC | 30 TAC Chapter 115, Degreasing Processes | § 115.412(1) § 115.411(1) § 115.411(2) [G]§ 115.412(1)(A) § 115.412(1)(C) § 115.412(1)(D) [G]§ 115.412(1)(F) | No person shall own or operate a system utilizing a VOC for the cold solvent cleaning of objects without the controls listed in §115.412(1)(A)-(F), except as exempted in §115.411. | [G]§ 115.415(1) § 115.415(3) ** See Periodic Monitoring Summary | None | None |
| B77APSC07 | PRO | R5460-01 | VOC | 30 TAC Chapter 115, Subchapter E, Division 6 | [G]§ 115.461(d) [G]§ 115.463(c) | The following are exempt from the VOC limits in §115.463(a) of this title (relating to Control Requirements): §115.461(d)(1)-(17) | None | § 115.468(b)(2) § 115.468(b)(5) | None |
| B77APSP10 1 | EP | R5720-01 | Highly Reactive VOC | 30 TAC Chapter 115, HRVOC Vent Gas | § 115.727(c)(2) | A vent gas stream that has the potential to emit HRVOCs, but has a concentration less than 100 ppmv at all times or has a maximum potential flow rate equal to or less than 100 dry standard cubic feet per hour is exempt from this division with the exception of § 115.726(e)(3)(A) of this title. The maximum potential HRVOC emissions for the sum of all vent gas | None | § 115.726(e)(3)(A) § 115.726(j)(2) | None |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|-----------|---------------------------------------|---|---|--|--|---|
| | | | | | | streams claimed under this exemption, must be less for the account specified in § 115.722(a) or (b) of this title than 0.5 tpy. | | | |
| B77APSP101 | EP | R5121-01 | VOC | 30 TAC Chapter 115, Vent Gas Controls | § 115.127(a)(1) [G]§ 115.122(a)(4) | A vent gas stream from a LDPE plant is exempt from §115.121(a)(1) if less than or equal to 1.1 pounds of ethylene per 1,000 pounds (1.1 kg/1000 kg) of product are emitted from all the specified vent gas streams. | [G]§ 115.125 § 115.126(2) § 115.126(3)(A) | § 115.126 § 115.126(2) § 115.126(3) § 115.126(3)(A) | None |
| B77APSPS1 | EU | R5131-01 | VOC | 30 TAC Chapter 115, Water Separation | § 115.137(a)(2) [G]§ 115.132(a)(4) | Any single or multiple compartment VOC water separator which separates materials having a true vapor pressure of VOC < .5 psia obtained from any equipment is exempt from §115.132(a). | [G]§ 115.135(a) § 115.136(a)(1) § 115.136(a)(3) § 115.136(a)(4) | § 115.136(a)(1) § 115.136(a)(3) § 115.136(a)(4) | None |
| B77APSPS2 | EU | R5131-01 | VOC | 30 TAC Chapter 115, Water Separation | § 115.137(a)(2) [G]§ 115.132(a)(4) | Any single or multiple compartment VOC water separator which separates materials having a true vapor pressure of VOC < .5 psia obtained from any equipment is exempt from §115.132(a). | [G]§ 115.135(a) § 115.136(a)(1) § 115.136(a)(3) § 115.136(a)(4) | § 115.136(a)(1) § 115.136(a)(3) § 115.136(a)(4) | None |
| B77APSPS3 | EU | R5131-01 | VOC | 30 TAC Chapter 115, Water Separation | § 115.137(a)(2) [G]§ 115.132(a)(4) | Any single or multiple compartment VOC water separator which separates materials having a true vapor pressure of VOC < .5 psia obtained from any equipment is exempt from §115.132(a). | [G]§ 115.135(a) § 115.136(a)(1) § 115.136(a)(3) § 115.136(a)(4) | § 115.136(a)(1) § 115.136(a)(3) § 115.136(a)(4) | None |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|-----------|---------------------------------------|---|---|-------------------------------------|---|---|
| B77APST1 | EU | R5112-01 | VOC | 30 TAC Chapter 115, Storage of VOCs | § 115.111(a)(1) | Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division. | [G]§ 115.117 | § 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7) | None |
| B77APST10 | EU | R5112-01 | VOC | 30 TAC Chapter 115, Storage of VOCs | § 115.111(a)(1) | Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division. | [G]§ 115.117 | § 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7) | None |
| B77APST11 | EU | R5112-01 | VOC | 30 TAC Chapter 115, Storage of VOCs | § 115.111(a)(1) | Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division. | [G]§ 115.117 | § 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7) | None |
| B77APST12 | EU | R5112-01 | VOC | 30 TAC Chapter 115, Storage of VOCs | § 115.111(a)(1) | Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division. | [G]§ 115.117 | § 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7) | None |
| B77APST13 3 | EP | R5121-01 | VOC | 30 TAC Chapter 115, Vent Gas Controls | § 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2) | A vent gas stream having a combined weight of volatile organic compounds (VOC) equal to or less than 100 pounds in any continuous 24-hour period is exempt from §115.121(a)(1) of this title. | [G]§ 115.125 § 115.126(2) | § 115.126 § 115.126(2) § 115.126(4) | None |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|---------------------|---------------------------------------|---|---|-------------------------------------|---|---|
| B77APST8 | EU | R5112-01 | VOC | 30 TAC Chapter 115, Storage of VOCs | § 115.111(a)(1) | Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division. | [G]§ 115.117 | § 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7) | None |
| B77APSTT14 | EU | R5112-01 | VOC | 30 TAC Chapter 115, Storage of VOCs | § 115.111(a)(1) | Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division. | [G]§ 115.117 | § 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7) | None |
| B77APSTT15 | EU | R5112-01 | VOC | 30 TAC Chapter 115, Storage of VOCs | § 115.111(a)(1) | Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division. | [G]§ 115.117 | § 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7) | None |
| B77APV101 | EP | R5720-01 | Highly Reactive VOC | 30 TAC Chapter 115, HRVOC Vent Gas | § 115.727(c)(2) | A vent gas stream that has the potential to emit HRVOCs, but has a concentration less than 100 ppmv at all times or has a maximum potential flow rate equal to or less than 100 dry standard cubic feet per hour is exempt from this division with the exception of § 115.726(e)(3)(A) of this title. The maximum potential HRVOC emissions for the sum of all vent gas streams claimed under this exemption, must be less for the account specified in | None | § 115.726(e)(3)(A) § 115.726(j)(2) | None |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|---------------------|---------------------------------------|---|---|---|--|---|
| | | | | | | § 115.722(a) or (b) of this title than 0.5 tpy. | | | |
| B77APV101 | EP | R5121-01 | VOC | 30 TAC Chapter 115, Vent Gas Controls | § 115.127(a)(1) [G]§ 115.122(a)(4) | A vent gas stream from a LDPE plant is exempt from §115.121(a)(1) if less than or equal to 1.1 pounds of ethylene per 1,000 pounds (1.1 kg/1000 kg) of product are emitted from all the specified vent gas streams. | [G]§ 115.125 § 115.126(2) § 115.126(3)(A) | § 115.126 § 115.126(2) § 115.126(3) § 115.126(3)(A) | None |
| B77APV102 | EP | R5720-01 | Highly Reactive VOC | 30 TAC Chapter 115, HRVOC Vent Gas | § 115.727(c)(2) | A vent gas stream that has the potential to emit HRVOCs, but has a concentration less than 100 ppmv at all times or has a maximum potential flow rate equal to or less than 100 dry standard cubic feet per hour is exempt from this division with the exception of § 115.726(e)(3)(A) of this title. The maximum potential HRVOC emissions for the sum of all vent gas streams claimed under this exemption, must be less for the account specified in § 115.722(a) or (b) of this title than 0.5 tpy. | None | § 115.726(e)(3)(A) § 115.726(j)(2) | None |
| B77APV102 | EP | R5121-01 | VOC | 30 TAC Chapter 115, Vent Gas Controls | § 115.127(a)(1) [G]§ 115.122(a)(4) | A vent gas stream from a LDPE plant is exempt from §115.121(a)(1) if less than or equal to 1.1 pounds of ethylene per 1,000 pounds (1.1 kg/1000 kg) of product are emitted from all the specified vent gas streams. | [G]§ 115.125 § 115.126(2) § 115.126(3)(A) | § 115.126 § 115.126(2) § 115.126(3) § 115.126(3)(A) | None |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|---------------------|---------------------------------------|---|---|---|--|---|
| B77SB101 | EP | R5720-01 | Highly Reactive VOC | 30 TAC Chapter 115, HRVOC Vent Gas | § 115.727(c)(2) | A vent gas stream that has the potential to emit HRVOCs, but has a concentration less than 100 ppmv at all times or has a maximum potential flow rate equal to or less than 100 dry standard cubic feet per hour is exempt from this division with the exception of § 115.726(e)(3)(A) of this title. The maximum potential HRVOC emissions for the sum of all vent gas streams claimed under this exemption, must be less for the account specified in § 115.722(a) or (b) of this title than 0.5 tpy. | None | § 115.726(e)(3)(A) § 115.726(j)(2) | None |
| B77SB101 | EP | R5121-01 | VOC | 30 TAC Chapter 115, Vent Gas Controls | § 115.127(a)(1) [G]§ 115.122(a)(4) | A vent gas stream from a LDPE plant is exempt from §115.121(a)(1) if less than or equal to 1.1 pounds of ethylene per 1,000 pounds (1.1 kg/1000 kg) of product are emitted from all the specified vent gas streams. | [G]§ 115.125 § 115.126(2) § 115.126(3)(A) | § 115.126 § 115.126(2) § 115.126(3) § 115.126(3)(A) | None |
| B77SB102 | EP | R5720-01 | Highly Reactive VOC | 30 TAC Chapter 115, HRVOC Vent Gas | § 115.727(c)(2) | A vent gas stream that has the potential to emit HRVOCs, but has a concentration less than 100 ppmv at all times or has a maximum potential flow rate equal to or less than 100 dry standard cubic feet per hour is exempt from this division with the exception of § 115.726(e)(3)(A) of this | None | § 115.726(e)(3)(A) § 115.726(j)(2) | None |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|---------------------|---------------------------------------|---|---|---|--|---|
| | | | | | | title. The maximum potential HRVOC emissions for the sum of all vent gas streams claimed under this exemption, must be less for the account specified in § 115.722(a) or (b) of this title than 0.5 tpy. | | | |
| B77SB102 | EP | R5121-01 | VOC | 30 TAC Chapter 115, Vent Gas Controls | § 115.127(a)(1) [G]§ 115.122(a)(4) | A vent gas stream from a LDPE plant is exempt from §115.121(a)(1) if less than or equal to 1.1 pounds of ethylene per 1,000 pounds (1.1 kg/1000 kg) of product are emitted from all the specified vent gas streams. | [G]§ 115.125 § 115.126(2) § 115.126(3)(A) | § 115.126 § 115.126(2) § 115.126(3) § 115.126(3)(A) | None |
| B77SB103 | EP | R5720-01 | Highly Reactive VOC | 30 TAC Chapter 115, HRVOC Vent Gas | § 115.727(c)(2) | A vent gas stream that has the potential to emit HRVOCs, but has a concentration less than 100 ppmv at all times or has a maximum potential flow rate equal to or less than 100 dry standard cubic feet per hour is exempt from this division with the exception of § 115.726(e)(3)(A) of this title. The maximum potential HRVOC emissions for the sum of all vent gas streams claimed under this exemption, must be less for the account specified in § 115.722(a) or (b) of this title than 0.5 tpy. | None | § 115.726(e)(3)(A) § 115.726(j)(2) | None |
| B77SB103 | EP | R5121-01 | VOC | 30 TAC Chapter 115, Vent Gas Controls | § 115.127(a)(1) [G]§ 115.122(a)(4) | A vent gas stream from a LDPE plant is exempt from §115.121(a)(1) if less than | [G]§ 115.125 § 115.126(2) § 115.126(3)(A) | § 115.126 § 115.126(2) § 115.126(3) | None |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|---------------------|---------------------------------------|---|---|---|--|---|
| | | | | | | or equal to 1.1 pounds of ethylene per 1,000 pounds (1.1 kg/1000 kg) of product are emitted from all the specified vent gas streams. | | § 115.126(3)(A) | |
| B77SB104 | EP | R5720-01 | Highly Reactive VOC | 30 TAC Chapter 115, HRVOC Vent Gas | § 115.727(c)(2) | A vent gas stream that has the potential to emit HRVOCs, but has a concentration less than 100 ppmv at all times or has a maximum potential flow rate equal to or less than 100 dry standard cubic feet per hour is exempt from this division with the exception of § 115.726(e)(3)(A) of this title. The maximum potential HRVOC emissions for the sum of all vent gas streams claimed under this exemption, must be less for the account specified in § 115.722(a) or (b) of this title than 0.5 tpy. | None | § 115.726(e)(3)(A) § 115.726(j)(2) | None |
| B77SB104 | EP | R5121-01 | VOC | 30 TAC Chapter 115, Vent Gas Controls | § 115.127(a)(1) [G]§ 115.122(a)(4) | A vent gas stream from a LDPE plant is exempt from §115.121(a)(1) if less than or equal to 1.1 pounds of ethylene per 1,000 pounds (1.1 kg/1000 kg) of product are emitted from all the specified vent gas streams. | [G]§ 115.125 § 115.126(2) § 115.126(3)(A) | § 115.126 § 115.126(2) § 115.126(3) § 115.126(3)(A) | None |
| B77SB105 | EP | R5720-01 | Highly Reactive VOC | 30 TAC Chapter 115, HRVOC Vent Gas | § 115.727(c)(2) | A vent gas stream that has the potential to emit HRVOCs, but has a concentration less than 100 ppmv at all times or has a maximum potential flow rate | None | § 115.726(e)(3)(A) § 115.726(j)(2) | None |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|---------------------|---------------------------------------|---|---|---|--|---|
| | | | | | | equal to or less than 100 dry standard cubic feet per hour is exempt from this division with the exception of § 115.726(e)(3)(A) of this title. The maximum potential HRVOC emissions for the sum of all vent gas streams claimed under this exemption, must be less for the account specified in § 115.722(a) or (b) of this title than 0.5 tpy. | | | |
| B77SB105 | EP | R5121-01 | VOC | 30 TAC Chapter 115, Vent Gas Controls | § 115.127(a)(1) [G]§ 115.122(a)(4) | A vent gas stream from a LDPE plant is exempt from §115.121(a)(1) if less than or equal to 1.1 pounds of ethylene per 1,000 pounds (1.1 kg/1000 kg) of product are emitted from all the specified vent gas streams. | [G]§ 115.125 § 115.126(2) § 115.126(3)(A) | § 115.126 § 115.126(2) § 115.126(3) § 115.126(3)(A) | None |
| B77SB106 | EP | R5720-01 | Highly Reactive VOC | 30 TAC Chapter 115, HRVOC Vent Gas | § 115.727(c)(2) | A vent gas stream that has the potential to emit HRVOCs, but has a concentration less than 100 ppmv at all times or has a maximum potential flow rate equal to or less than 100 dry standard cubic feet per hour is exempt from this division with the exception of § 115.726(e)(3)(A) of this title. The maximum potential HRVOC emissions for the sum of all vent gas streams claimed under this exemption, must be less for the account specified in | None | § 115.726(e)(3)(A) § 115.726(j)(2) | None |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|---------------------|---------------------------------------|---|---|---|--|---|
| | | | | | | § 115.722(a) or (b) of this title than 0.5 tpy. | | | |
| B77SB106 | EP | R5121-01 | VOC | 30 TAC Chapter 115, Vent Gas Controls | § 115.127(a)(1) [G]§ 115.122(a)(4) | A vent gas stream from a LDPE plant is exempt from §115.121(a)(1) if less than or equal to 1.1 pounds of ethylene per 1,000 pounds (1.1 kg/1000 kg) of product are emitted from all the specified vent gas streams. | [G]§ 115.125 § 115.126(2) § 115.126(3)(A) | § 115.126 § 115.126(2) § 115.126(3) § 115.126(3)(A) | None |
| B77SB107 | EP | R5720-01 | Highly Reactive VOC | 30 TAC Chapter 115, HRVOC Vent Gas | § 115.727(c)(2) | A vent gas stream that has the potential to emit HRVOCs, but has a concentration less than 100 ppmv at all times or has a maximum potential flow rate equal to or less than 100 dry standard cubic feet per hour is exempt from this division with the exception of § 115.726(e)(3)(A) of this title. The maximum potential HRVOC emissions for the sum of all vent gas streams claimed under this exemption, must be less for the account specified in § 115.722(a) or (b) of this title than 0.5 tpy. | None | § 115.726(e)(3)(A) § 115.726(j)(2) | None |
| B77SB107 | EP | R5121-01 | VOC | 30 TAC Chapter 115, Vent Gas Controls | § 115.127(a)(1) [G]§ 115.122(a)(4) | A vent gas stream from a LDPE plant is exempt from §115.121(a)(1) if less than or equal to 1.1 pounds of ethylene per 1,000 pounds (1.1 kg/1000 kg) of product are emitted from all the specified vent gas streams. | [G]§ 115.125 § 115.126(2) § 115.126(3)(A) | § 115.126 § 115.126(2) § 115.126(3) § 115.126(3)(A) | None |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|---------------------|---------------------------------------|--|---|--|---|---|
| B77SPS102 | EU | R5131-01 | VOC | 30 TAC Chapter 115, Water Separation | § 115.137(a)(2) [G]§ 115.132(a)(4) | Any single or multiple compartment VOC water separator which separates materials having a true vapor pressure of VOC < .5 psia obtained from any equipment is exempt from §115.132(a). | [G]§ 115.135(a) § 115.136(a)(1) § 115.136(a)(3) § 115.136(a)(4) | § 115.136(a)(1) § 115.136(a)(3) § 115.136(a)(4) | None |
| B77SPS103 | EP | R5121-01 | VOC | 30 TAC Chapter 115, Vent Gas Controls | § 115.122(a)(1) § 115.121(a)(1) § 115.122(a)(1)(B) § 60.18 | Vent gas streams affected by §115.121(a)(1) must be controlled properly with a control efficiency of at least 90% or to a volatile organic compound (VOC) concentration of no more than 20 parts per million (ppmv) (on a dry basis corrected to 3.0% oxygen for combustion devices). | [G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2) | § 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2) | None |
| B78APF1 | EU | R1111-01 | Opacity | 30 TAC Chapter 111, Visible Emissions | § 111.111(a)(4)(A) | Visible emissions from a process gas flare shall not be permitted for more than five minutes in any two-hour period. Non-excessive upset events are subject to the provisions under §101.222(b). | § 111.111(a)(4)(A)(i) § 111.111(a)(4)(A)(ii) | § 111.111(a)(4)(A)(ii) | None |
| B78APF1 | EP | R5720-01 | Highly Reactive VOC | 30 TAC Chapter 115, HRVOC Vent Gas | § 115.722(d) § 115.722(d)(1) § 115.722(d)(2) [G]§ 115.725(d)(1) § 115.725(d)(2) § 115.725(d)(2)(A)(i) [G]§ 115.725(d)(2)(A)(ii) § 115.725(d)(2)(A)(iii) | All flares must continuously meet the requirements of 40 CFR § 60.18(c)(2)-(6) and (d) as amended through October 17, 2000 (65 FR 61744) when vent gas containing HRVOC is being routed to the flare. | [G]§ 115.725(d)(1) § 115.725(d)(2) § 115.725(d)(2)(A)(i) [G]§ 115.725(d)(2)(A)(ii) § 115.725(d)(2)(A)(iii) § 115.725(d)(2)(A)(iv) § 115.725(d)(2)(B) | § 115.726(a)(1) § 115.726(a)(1)(A) § 115.726(d)(1) § 115.726(d)(2) § 115.726(d)(3) § 115.726(d)(4) § 115.726(i) § 115.726(j)(1) § 115.726(j)(2) | § 115.725(n) § 115.726(a)(1)(B) |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|-------------|---------------------------------------|--|--|---|---|---|
| | | | | | § 115.725(d)(2)(A)(iv) § 115.725(d)(2)(B) § 115.725(d)(2)(B)(i) § 115.725(d)(2)(B)(ii) § 115.725(d)(2)(B)(iii) § 115.725(d)(2)(B)(iv) § 115.725(d)(2)(B)(iii) § 115.725(d)(2)(B)(iv) [G]§ 115.725(l) § 115.725(n) | | § 115.725(d)(2)(B)(i) § 115.725(d)(2)(B)(ii) § 115.725(d)(2)(B)(iii) § 115.725(d)(2)(B)(iv) § 115.725(d)(3) § 115.725(d)(4) § 115.725(d)(5) § 115.725(d)(6) § 115.725(d)(7) | | |
| B78APF1 | CD | 60A-01 | Opacity | 40 CFR Part 60, Subpart A | § 60.18(b) § 60.18(c)(1) § 60.18(c)(2) § 60.18(c)(3)(ii) § 60.18(c)(4)(iii) § 60.18(c)(6) § 60.18(e) | Flares shall comply with paragraphs (c)-(f) of § 60.18. | § 60.18(d) § 60.18(f)(1) § 60.18(f)(2) § 60.18(f)(3) § 60.18(f)(4) § 60.18(f)(5) | None | None |
| B78APF1 | CD | 63A-01 | Opacity | 40 CFR Part 63, Subpart A | § 63.11(b)(4) § 63.11(b)(1) § 63.11(b)(2) § 63.11(b)(3) § 63.11(b)(5) § 63.11(b)(6)(ii) § 63.11(b)(7)(iii) | Flares shall be designed and operated with no visible emissions, except for periods of a total of 5 minutes or less during any 2 consecutive hrs. Test Method 22 in App. A of part 60 of this chapter shall be used. | § 63.11(b)(4) § 63.11(b)(5) § 63.11(b)(7)(i) | None | None |
| B78APF1 | EP | 63FFFF-01 | 112(B) HAPS | 40 CFR Part 63, Subpart FFFF | § 63.2455(a)-Table 1.1.a.ii § 63.11(b) § 63.2450(a)(2) § 63.2450(b) [G]§ 63.2450(e)(4) [G]§ 63.2450(e)(5) [G]§ 63.2450(e)(6) § 63.2450(k)(8) | For each Group 1 continuous process vent, the owner or operator must reduce emissions of total organic HAP by venting emissions through a closed vent system to a flare. | [G]§ 63.115(d)(2)(v) § 63.983(b) [G]§ 63.983(b)(1) [G]§ 63.983(b)(2) [G]§ 63.983(b)(3) [G]§ 63.983(c)(1) § 63.983(c)(2) § 63.983(c)(3) § 63.983(d)(1) | § 63.2450(k)(1)(ii) § 63.2450(k)(7) [G]§ 63.2525(m) § 63.2525(n) § 63.983(b) [G]§ 63.983(d)(2) [G]§ 63.998(b)(1) [G]§ 63.998(d)(1) | § 63.2520(d)(3) [G]§ 63.2520(e)(11) § 63.2520(e)(12) [G]§ 63.999(a)(1) § 63.999(b)(5) § 63.999(c)(1) § 63.999(c)(2)(i) § 63.999(c)(6) [G]§ 63.999(d)(1) |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|---------------------|--|--|--|--|---|--|
| | | | | | § 63.2450(u) § 63.2455(a) § 63.2455(b) § 63.2455(b)(1) § 63.2535(m)(1) § 63.2535(m)(2) § 63.983(a)(1) § 63.983(a)(2) § 63.983(d)(1) § 63.983(d)(1)(i) [G]§ 63.983(d)(2) § 63.983(d)(3) | | § 63.983(d)(1)(ii) ** See Alternative Requirement | | [G]§ 63.999(d)(2) |
| B78APFU1 | EU | R5780-ALL | Highly Reactive VOC | 30 TAC Chapter 115, HRVOC Fugitive Emissions | § 115.787(d) § 115.780(b) [G]§ 115.781(a) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) [G]§ 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) [G]§ 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv) § 115.782(c)(1)(C)(i) § 115.782(c)(1)(C)(i)(I) § 115.782(c)(1)(C)(i)(II) § 115.782(c)(1)(C)(i)(| All pumps that are equipped with a shaft sealing system that prevents or detects emissions of VOC from the seal are exempt from the monitoring requirement of §115.781(b) and (c). Submerged pumps or sealless pumps may be used to satisfy the requirements of this subsection. | § 115.782(d)(2) | [G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g) | [G]§ 115.782(c)(1)(B)(i) § 115.783(3)(C) [G]§ 115.786(c) |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|---------------------|--|--|--|-------------------------------------|---|--|
| | | | | | III) § 115.782(c)(1)(C)(ii) § 115.783(3) [G]§ 115.783(3)(A) [G]§ 115.783(3)(B) § 115.787(b) § 115.787(b)(1) § 115.787(g) | | | | |
| B78APFU1 | EU | R5780-ALL | Highly Reactive VOC | 30 TAC Chapter 115, HRVOC Fugitive Emissions | § 115.787(d) § 115.780(b) [G]§ 115.781(a) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) [G]§ 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) [G]§ 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv) § 115.782(c)(1)(C)(i) § 115.782(c)(1)(C)(i)(I) § 115.782(c)(1)(C)(i)(II) § 115.782(c)(1)(C)(i)(III) § 115.782(c)(1)(C)(ii) | All compressors that are equipped with a shaft sealing system that prevents or detects emissions of VOC from the seal are exempt from the monitoring requirement of §115.781(b) and (c). Submerged pumps or sealless pumps may be used to satisfy the requirements of this subsection. | § 115.782(d)(2) | [G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g) | [G]§ 115.782(c)(1)(B)(i) § 115.783(3)(C) [G]§ 115.786(c) |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|---------------------|--|--|--|-------------------------------------|---|--|
| | | | | | § 115.783(3) [G]§ 115.783(3)(A) [G]§ 115.783(3)(B) § 115.787(b) § 115.787(b)(1) § 115.787(g) | | | | |
| B78APFU1 | EU | R5780-ALL | Highly Reactive VOC | 30 TAC Chapter 115, HRVOC Fugitive Emissions | § 115.787(d) § 115.780(b) [G]§ 115.781(a) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) [G]§ 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) [G]§ 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv) § 115.782(c)(1)(C)(i) § 115.782(c)(1)(C)(i)(I) § 115.782(c)(1)(C)(i)(II) § 115.782(c)(1)(C)(i)(III) § 115.782(c)(1)(C)(ii) § 115.783(3) [G]§ 115.783(3)(A) [G]§ 115.783(3)(B) | All agitators that are equipped with a shaft sealing system that prevents or detects emissions of VOC from the seal are exempt from the monitoring requirement of §115.781(b) and (c). Submerged pumps or sealless pumps may be used to satisfy the requirements of this subsection. | § 115.782(d)(2) | [G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g) | [G]§ 115.782(c)(1)(B)(i) § 115.783(3)(C) [G]§ 115.786(c) |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|---------------------|--|--|--|---|--|---|
| | | | | | § 115.787(b) § 115.787(b)(1) § 115.787(g) | | | | |
| B78APFU1 | EU | R5780-ALL | Highly Reactive VOC | 30 TAC Chapter 115, HRVOC Fugitive Emissions | § 115.781(b)(9) § 115.780(b) [G]§ 115.781(a) [G]§ 115.781(d) § 115.781(g)(3) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(2) § 115.782(c)(2)(A) § 115.782(c)(2)(A)(i) § 115.782(c)(2)(A)(ii) § 115.782(c)(2)(B) § 115.783(1) § 115.783(1)(A) § 115.783(1)(B) § 115.783(5) § 115.787(f) § 115.787(f)(4) § 115.787(g) § 115.788(a) § 115.788(a)(1) § 115.788(a)(2) § 115.788(a)(2)(A) § 115.788(a)(2)(B) § 115.788(a)(2)(C) § 115.788(a)(2)(C)(i) § 115.788(a)(2)(C)(ii) § 115.788(a)(2)(C)(iii) § 115.788(a)(2)(D) § 115.788(a)(3) | Bypass line valves within a petroleum refinery; synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process; or natural gas/gasoline processing operation in which a highly-reactive volatile organic compound is a raw material, intermediate, final product, or in a waste stream is subject to the requirements of this division. A leak is defined as a screening concentration greater than 500 ppmv above background as methane for all components. | § 115.781(b) § 115.781(b)(10) § 115.781(b)(4) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) [G]§ 115.781(d) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.782(d)(2) § 115.786(a)(1) | § 115.781(b)(10) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) § 115.782(c)(2)(A)(ii) § 115.786(a)(1) § 115.786(a)(2) § 115.786(a)(2)(A) § 115.786(a)(2)(B) § 115.786(b)(1) § 115.786(b)(2) § 115.786(b)(2)(A) § 115.786(b)(2)(B) § 115.786(b)(2)(C) [G]§ 115.786(b)(3) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(2) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g) [G]§ 115.788(g) | § 115.782(c)(2)(A)(ii) [G]§ 115.786(c) § 115.788(c) [G]§ 115.788(d) § 115.788(e) [G]§ 115.788(g) |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|---------------------|--|--|--|---|--|--|
| | | | | | § 115.788(a)(3)(A) § 115.788(a)(3)(B) [G]§ 115.788(g) | | | | |
| B78APFU1 | EU | R5780-ALL | Highly Reactive VOC | 30 TAC Chapter 115, HRVOC Fugitive Emissions | § 115.781(b)(9) § 115.780(b) [G]§ 115.781(a) § 115.781(g)(3) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) [G]§ 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) [G]§ 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv) | Heat exchanger heads, sight glasses, meters, gauges, sampling connections, bolted manways, hatches, sump covers, junction box vents, and covers and seals on VOC water separators within the process unit or processes listed in §115.780(a) in which a HRVOC is a raw material, intermediate, final product, or in a waste stream is subject to the requirements of this division. A leak is defined as a screening concentration greater than 500 ppmv above background as methane for all components. | § 115.781(b) § 115.781(b)(10) § 115.781(b)(3) § 115.781(b)(4) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) § 115.781(f) § 115.781(f)(1) § 115.781(f)(2) § 115.781(f)(3) § 115.781(f)(4) § 115.781(f)(5) § 115.781(f)(6) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.782(d)(2) § 115.789(1)(B) | § 115.781(b)(10) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) [G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g) | [G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.789(1)(B) |
| B78APFU1 | EU | R5780-ALL | Highly Reactive VOC | 30 TAC Chapter 115, HRVOC Fugitive Emissions | § 115.787(a) | Components that contact a process fluid containing less than 5.0% highly-reactive volatile organic compounds by weight on an annual average basis are exempt from the requirements of this division (relating to Fugitive Emissions), except for 115.786(e) and (g) of this title (relating to Record keeping Requirements). | None | § 115.786(e) § 115.786(g) | None |
| B78APFU1 | EU | R5780-ALL | Highly Reactive | 30 TAC Chapter 115, HRVOC | § 115.781(b)(9) § 115.780(b) | Process drains within a petroleum refinery; synthetic | § 115.354(1) § 115.354(10) | § 115.354(10) § 115.356 | [G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|---------------------|--|---|--|--|--|---|
| | | | VOC | Fugitive Emissions | [G]§ 115.781(a) § 115.781(g)(3) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) [G]§ 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) [G]§ 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv) § 115.783(4)(A)(i) § 115.783(4)(A)(ii) § 115.783(4)(A)(ii)(I) § 115.783(4)(A)(ii)(II) § 115.783(4)(B) § 115.783(4)(B)(i) § 115.783(4)(B)(ii) | organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process; or natural gas/gasoline processing operation in which a highly-reactive volatile organic compound is a raw material, intermediate, final product, or in a waste stream is subject to the requirements of this division. A leak is defined as a screening concentration greater than 500 ppmv above background as methane for all components. | § 115.354(5) § 115.354(6) § 115.354(9) § 115.781(b) § 115.781(b)(10) § 115.781(b)(3) § 115.781(b)(4) § 115.781(b)(5) § 115.781(b)(6) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.782(d)(2) | [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(5) § 115.781(b)(10) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) [G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g) | |
| B78APFU1 | EU | R5780-ALL | Highly Reactive VOC | 30 TAC Chapter 115, HRVOC Fugitive Emissions | § 115.781(b)(9) § 115.780(b) [G]§ 115.781(a) § 115.781(g)(3) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) [G]§ 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) | Pressure relief valves (in gaseous service) within a petroleum refinery; synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process; or natural gas/gasoline processing operation in which a highly-reactive volatile organic compound is a raw material, intermediate, final product, or in a waste stream is subject to the requirements | § 115.354(1) § 115.354(10) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) § 115.354(9) § 115.781(b) § 115.781(b)(10) § 115.781(b)(4) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) § 115.781(b)(8) | § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(5) § 115.781(b)(10) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) [G]§ 115.782(c)(1)(B)(i) | [G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.788(c) [G]§ 115.788(d) § 115.788(e) [G]§ 115.788(g) |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|---------------------|--|--|---|---|--|---|
| | | | | | [G]§ 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv) § 115.787(e) § 115.787(f) § 115.787(g) § 115.788(a) § 115.788(a)(1) § 115.788(a)(2) § 115.788(a)(2)(A) § 115.788(a)(2)(B) § 115.788(a)(2)(C) § 115.788(a)(2)(C)(i) § 115.788(a)(2)(C)(ii) § 115.788(a)(2)(C)(iii) § 115.788(a)(2)(D) § 115.788(a)(3) § 115.788(a)(3)(A) § 115.788(a)(3)(B) [G]§ 115.788(g) | of this division. A leak is defined as a screening concentration greater than 500 ppmv above background as methane for all components. | § 115.781(e) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.782(d)(2) | [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g) [G]§ 115.788(g) | |
| B78APFU1 | EU | R5780-ALL | Highly Reactive VOC | 30 TAC Chapter 115, HRVOC Fugitive Emissions | § 115.781(b)(9) § 115.780(b) [G]§ 115.781(a) § 115.781(g)(3) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(2) § 115.782(c)(2)(A) § 115.782(c)(2)(A)(i) § 115.782(c)(2)(A)(ii) § 115.782(c)(2)(B) § 115.783(5) | Valves within a petroleum refinery; synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process; or natural gas/gasoline processing operation which a highly-reactive volatile organic compound is a raw material, intermediate, final product, or in a waste stream is subject to the requirements of this division. A leak is defined as a screening concentration | § 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) § 115.781(b) § 115.781(b)(10) § 115.781(b)(4) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) | § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(5) § 115.781(b)(10) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) § 115.782(c)(2)(A)(ii) [G]§ 115.786(c) | § 115.782(c)(2)(A)(ii) [G]§ 115.786(c) § 115.788(c) [G]§ 115.788(d) § 115.788(e) [G]§ 115.788(g) |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|---------------------|--|---|---|---|--|--|
| | | | | | § 115.787(f) § 115.787(f)(4) § 115.787(g) § 115.788(a) § 115.788(a)(1) § 115.788(a)(2) § 115.788(a)(2)(A) § 115.788(a)(2)(B) § 115.788(a)(2)(C) § 115.788(a)(2)(C)(i) § 115.788(a)(2)(C)(ii) § 115.788(a)(2)(C)(iii) § 115.788(a)(2)(D) § 115.788(a)(3) § 115.788(a)(3)(A) § 115.788(a)(3)(B) [G]§ 115.788(g) | greater than 500 ppmv above background as methane for all components. | § 115.782(d)(2) | § 115.786(d) § 115.786(d)(2) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g) [G]§ 115.788(g) | |
| B78APFU1 | EU | R5780-ALL | Highly Reactive VOC | 30 TAC Chapter 115, HRVOC Fugitive Emissions | § 115.781(b)(9) § 115.780(b) [G]§ 115.781(a) § 115.781(g)(3) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) [G]§ 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) [G]§ 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv) | Flanges or other connectors within a petroleum refinery; synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process; or natural gas/gasoline processing operation in which a highly-reactive volatile organic compound is a raw material, intermediate, final product, or in a waste stream is subject to the requirements of this division. A leak is defined as a screening concentration greater than 500 ppmv above background as methane for | § 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) § 115.781(b) § 115.781(b)(10) § 115.781(b)(3) § 115.781(b)(4) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) § 115.781(f) § 115.781(f)(1) § 115.781(f)(2) § 115.781(f)(3) § 115.781(f)(4) | § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(5) § 115.781(b)(10) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) [G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) | [G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.789(1)(B) |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|---------------------|--|--|--|--|--|--|
| | | | | | | all components. | § 115.781(f)(5) § 115.781(f)(6) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.782(d)(2) § 115.789(1)(B) | § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g) | |
| B78APFU1 | EU | R5780-ALL | Highly Reactive VOC | 30 TAC Chapter 115, HRVOC Fugitive Emissions | § 115.781(b)(9) § 115.780(b) [G]§ 115.781(a) § 115.781(g)(3) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) [G]§ 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) [G]§ 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv) § 115.782(c)(1)(C)(i) § 115.782(c)(1)(C)(i)(I) § 115.782(c)(1)(C)(i)(II) § 115.782(c)(1)(C)(i)(III) § 115.782(c)(1)(C)(ii) § 115.783(3) | Compressor seals within a petroleum refinery; synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process; or natural gas/gasoline processing operation in which a highly-reactive volatile organic compound is a raw material, intermediate, final product, or in a waste stream is subject to the requirements of this division. A leak is defined as a screening concentration greater than 500 ppmv above background as methane for all components. | § 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) § 115.781(b) § 115.781(b)(10) § 115.781(b)(4) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) § 115.781(c)(1) § 115.781(c)(2) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.782(d)(2) | § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(5) § 115.781(b)(10) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) [G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g) | [G]§ 115.782(c)(1)(B)(i) § 115.783(3)(C) [G]§ 115.786(c) |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|---------------------|--|---|--|--|--|--|
| | | | | | [G]§ 115.783(3)(A) [G]§ 115.783(3)(B) § 115.787(b) | | | | |
| B78APFU1 | EU | R5780-ALL | Highly Reactive VOC | 30 TAC Chapter 115, HRVOC Fugitive Emissions | § 115.781(b)(9) § 115.780(b) [G]§ 115.781(a) § 115.781(g)(3) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) [G]§ 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) [G]§ 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv) § 115.782(c)(1)(C)(i) § 115.782(c)(1)(C)(i)(I) § 115.782(c)(1)(C)(i)(II) § 115.782(c)(1)(C)(i)(III) § 115.782(c)(1)(C)(ii) § 115.783(3) [G]§ 115.783(3)(A) [G]§ 115.783(3)(B) § 115.787(b) § 115.787(b)(1) | Pump seals within a petroleum refinery; synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process; or natural gas/gasoline processing operation in which a highly-reactive volatile organic compound is a raw material, intermediate, final product, or in a waste stream is subject to the requirements of this division. A leak is defined as a screening concentration greater than 500 ppmv above background as methane for all components. | § 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) § 115.781(b) § 115.781(b)(10) § 115.781(b)(4) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) § 115.781(c)(1) § 115.781(c)(2) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.782(d)(2) | § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(5) § 115.781(b)(10) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) [G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g) | [G]§ 115.782(c)(1)(B)(i) § 115.783(3)(C) [G]§ 115.786(c) |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|---------------------|--|--|---|---|--|--|
| B78APFU1 | EU | R5780-ALL | Highly Reactive VOC | 30 TAC Chapter 115, HRVOC Fugitive Emissions | § 115.781(b)(9) § 115.780(b) [G]§ 115.781(a) § 115.781(g)(3) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) [G]§ 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) [G]§ 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv) § 115.782(c)(1)(C)(i) § 115.782(c)(1)(C)(i)(I) § 115.782(c)(1)(C)(i)(II) § 115.782(c)(1)(C)(i)(III) § 115.782(c)(1)(C)(ii) § 115.783(3) [G]§ 115.783(3)(A) [G]§ 115.783(3)(B) § 115.787(b) | Agitators within a petroleum refinery; synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process; or natural gas/gasoline processing operation in which a highly-reactive volatile organic compound is a raw material, intermediate, final product, or in a waste stream is subject to the requirements of this division. A leak is defined as a screening concentration greater than 500 ppmv above background as methane for all components. | § 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) § 115.781(b) § 115.781(b)(10) § 115.781(b)(3) § 115.781(b)(4) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) § 115.781(c)(1) § 115.781(c)(2) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.782(d)(2) | § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(5) § 115.781(b)(10) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) [G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g) | [G]§ 115.782(c)(1)(B)(i) § 115.783(3)(C) [G]§ 115.786(c) |
| B78APFU1 | EU | R5780-ALL | Highly Reactive VOC | 30 TAC Chapter 115, HRVOC Fugitive Emissions | § 115.781(b)(9) § 115.358(c)(1) [G]§ 115.358(h) § 115.780(b) | Components within the process unit or processes listed in §115.780(a) is subject to the requirements | § 115.354(1) § 115.354(11) § 115.354(13)(A) § 115.354(13)(B) | § 115.354(13)(D) § 115.354(13)(E) § 115.356 [G]§ 115.356(1) | [G]§ 115.358(g) [G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|---------------------|--|---|---|---|---|--|
| | | | | | [G]§ 115.781(a) § 115.781(g)(3) § 115.782(a) § 115.782(b)(2) § 115.782(b)(3) § 115.782(c)(1) § 115.782(c)(1)(A) § 115.782(c)(1)(B) [G]§ 115.782(c)(1)(B)(i) § 115.782(c)(1)(B)(ii) [G]§ 115.782(c)(1)(B)(iii) § 115.782(c)(1)(B)(iv) | of this division. If the owner of operator elects to use the alternative work practice in §115.358 of this title, a leak is defined as specified in §115.358 of this title, including any leak detected using the alternative work practice on a component that is subject to the requirements of this division but not specifically selected for alternative work practice monitoring. | § 115.354(13)(C) § 115.354(13)(D) § 115.354(13)(E) § 115.354(13)(F) § 115.354(4) § 115.354(5) § 115.354(9) § 115.358(c)(2) § 115.358(d) [G]§ 115.358(e) § 115.358(f) § 115.781(b) § 115.781(b)(4) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(h)(1) § 115.781(h)(2) § 115.781(h)(3) § 115.781(h)(4) § 115.781(h)(5) [G]§ 115.781(h)(6) § 115.782(b)(4) § 115.782(d)(1) § 115.788(h)(1) [G]§ 115.788(h)(2) § 115.788(h)(3) | [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(4) § 115.356(5) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) [G]§ 115.782(c)(1)(B)(i) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(1) § 115.786(d)(2) § 115.786(d)(2)(A) § 115.786(d)(2)(B) § 115.786(d)(2)(C) § 115.786(e) [G]§ 115.786(f) § 115.786(g) | |
| B78APFU1 | EU | R5780-ALL | Highly Reactive VOC | 30 TAC Chapter 115, HRVOC Fugitive Emissions | § 115.781(b)(9) § 115.780(b) [G]§ 115.781(a) § 115.781(g)(3) § 115.782(a) § 115.782(b)(1) § 115.782(b)(2) § 115.782(c)(2) § 115.782(c)(2)(A) | Open-ended valves or lines within a petroleum refinery; synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process; or natural gas/gasoline processing operation in which a highly-reactive | § 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) § 115.781(b) § 115.781(b)(10) § 115.781(b)(3) | § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(5) § 115.781(b)(10) | § 115.782(c)(2)(A)(ii) [G]§ 115.786(c) § 115.788(c) [G]§ 115.788(d) § 115.788(e) [G]§ 115.788(g) § 115.789(1)(B) |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|-----------|--|--|--|--|--|---|
| | | | | | § 115.782(c)(2)(A)(i) § 115.782(c)(2)(A)(ii) § 115.782(c)(2)(B) § 115.783(5) § 115.787(f) § 115.787(f)(2) § 115.787(f)(3) § 115.787(f)(4) § 115.787(g) § 115.788(a) § 115.788(a)(1) § 115.788(a)(2) § 115.788(a)(2)(A) § 115.788(a)(2)(B) § 115.788(a)(2)(C) § 115.788(a)(2)(C)(i) § 115.788(a)(2)(C)(ii) § 115.788(a)(2)(C)(iii) § 115.788(a)(2)(D) § 115.788(a)(3) § 115.788(a)(3)(A) § 115.788(a)(3)(B) [G]§ 115.788(g) | volatile organic compound is a raw material, intermediate, final product, or in a waste stream is subject to the requirements of this division. A leak is defined as a screening concentration greater than 500 ppmv above background as methane for all components. | § 115.781(b)(4) § 115.781(b)(7) § 115.781(b)(7)(A) § 115.781(b)(7)(B) § 115.781(f) § 115.781(f)(1) § 115.781(f)(2) § 115.781(f)(3) § 115.781(f)(4) § 115.781(f)(5) § 115.781(f)(6) § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.782(d)(2) § 115.789(1)(B) | § 115.781(g) § 115.781(g)(1) § 115.781(g)(2) § 115.781(g)(3) § 115.782(c)(2)(A)(ii) [G]§ 115.786(c) § 115.786(d) § 115.786(d)(2) § 115.786(d)(2)(C) § 115.786(e) § 115.786(g) [G]§ 115.788(g) | |
| B78APFU1 | EU | R5352-ALL | VOC | 30 TAC Chapter 115, Pet. Refinery & Petrochemicals | § 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) | No valves contacting a fluid with TVP less than or equal to 0.044 psia (heavy liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or | § 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 § 115.357(1) | § 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5) | [G]§ 115.354(7) |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|-----------|--|--|--|--|--|---|
| | | | | | § 115.357(8) § 115.357(9) | the dripping or exuding of process fluid based on sight, smell, or sound. | | | |
| B78APFU1 | EU | R5352-ALL | VOC | 30 TAC Chapter 115, Pet. Refinery & Petrochemicals | § 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8) § 115.357(9) | No open-ended valves or lines contacting a fluid with TVP greater than 0.044 psia (gas/vapor or light liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound. | § 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 | § 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5) | [G]§ 115.354(7) |
| B78APFU1 | EU | R5352-ALL | VOC | 30 TAC Chapter 115, Pet. Refinery & Petrochemicals | § 115.357(5) | Reciprocating compressors and positive displacement pumps used in natural gas/gasoline processing operations are exempt from the requirements of this division except §115.356(3)(C) of this title. | None | § 115.356 § 115.356(3) [G]§ 115.356(3)(C) | None |
| B78APFU1 | EU | R5352-ALL | VOC | 30 TAC Chapter 115, Pet. Refinery & Petrochemicals | § 115.357(10) | Instrumentation systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet 40 CFR §63.169 (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title. | None | § 115.356 § 115.356(3) [G]§ 115.356(3)(C) | None |
| B78APFU1 | EU | R5352-ALL | VOC | 30 TAC Chapter 115, Pet. Refinery & Petrochemicals | § 115.357(11) | Sampling connection systems, as defined in 40 CFR §63.161 (January 17, | None | § 115.356 § 115.356(3) [G]§ 115.356(3)(C) | None |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|-----------|--|---|---|-------------------------------------|---|---|
| | | | | | | 1997), that meet the requirements of 40 CFR §63.166(a) and (b) (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title. | | | |
| B78APFU1 | EU | R5352-ALL | VOC | 30 TAC Chapter 115, Pet. Refinery & Petrochemicals | § 115.357(13) | Components/systems that contact a process fluid containing VOC having a true vapor pressure equal to or less than 0.002 psia at 68 degrees Fahrenheit are exempt from the requirements of this division except §115.356(3)(C) of this title. | None | § 115.356 § 115.356(3) [G]§ 115.356(3)(C) | None |
| B78APFU1 | EU | R5352-ALL | VOC | 30 TAC Chapter 115, Pet. Refinery & Petrochemicals | § 115.357(6) | Components at a petroleum refinery or synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process, that contact a process fluid that contains less than 10% VOC by weight are exempt from the requirements of this division except §115.356(3)(C) of this title. | None | § 115.356 § 115.356(3) [G]§ 115.356(3)(C) | None |
| B78APFU1 | EU | R5352-ALL | VOC | 30 TAC Chapter 115, Pet. Refinery & Petrochemicals | § 115.357(2) § 115.352(9) | Conservation vents or other devices on atmospheric storage tanks that are actuated either by a vacuum or a pressure of no more than 2.5 psig, pressure relief valves equipped with a rupture disk or venting to a control device, components in continuous vacuum | None | § 115.356 § 115.356(3) [G]§ 115.356(3)(C) | None |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|-----------|--|--|--|---|---|---|
| | | | | | | service, and valves that are not externally regulated (such as in-line check valves) are exempt from the requirements of this division, except that each pressure relief valve equipped with a rupture disk must comply with §115.352(9) and §115. | | | |
| B78APFU1 | EU | R5352-ALL | VOC | 30 TAC Chapter 115, Pet. Refinery & Petrochemicals | § 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7) § 115.357(1) | No process drains contacting a fluid with TVP less than or equal to 0.044 psia (heavy liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound. | § 115.354(1) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1) | § 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5) | None |
| B78APFU1 | EU | R5352-ALL | VOC | 30 TAC Chapter 115, Pet. Refinery & Petrochemicals | § 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7) | No process drains contacting a fluid with TVP greater than 0.044 psia (gas/vapor or light liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of | § 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 | § 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(5) | None |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|-----------|--|--|--|--|--|---|
| | | | | | | process fluid based on sight, smell, or sound. | | | |
| B78APFU1 | EU | R5352-ALL | VOC | 30 TAC Chapter 115, Pet. Refinery & Petrochemicals | § 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(9) § 115.357(1) § 115.357(8) § 115.357(9) | No pressure relief valves contacting a fluid with TVP less than or equal to 0.044 psia (heavy liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound. | § 115.354(1) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 § 115.357(1) | § 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5) | [G]§ 115.354(7) |
| B78APFU1 | EU | R5352-ALL | VOC | 30 TAC Chapter 115, Pet. Refinery & Petrochemicals | § 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(9) § 115.357(12) § 115.357(8) § 115.357(9) | No pressure relief valves contacting a fluid with TVP greater than 0.044 psia (gas/vapor or light liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound. | § 115.354(1) § 115.354(10) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 | § 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5) | [G]§ 115.354(7) |
| B78APFU1 | EU | R5352-ALL | VOC | 30 TAC Chapter 115, Pet. Refinery & Petrochemicals | § 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) | No open-ended valves or lines contacting a fluid with TVP less than or equal to 0.044 psia (heavy liquid service) shall be allowed to have a VOC leak, for more | § 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) | § 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) | [G]§ 115.354(7) |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|-----------|--|--|---|---|--|---|
| | | | | | § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(8) § 115.357(9) | than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound. | [G]§ 115.355 § 115.357(1) | § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5) | |
| B78APFU1 | EU | R5352-ALL | VOC | 30 TAC Chapter 115, Pet. Refinery & Petrochemicals | § 115.352(1)(C) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(iii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(8) § 115.358(c)(1) [G]§ 115.358(h) | If the owner or operator elects to use the alternative work practice in §115.358, no component shall be allowed to have a VOC leak, detected as defined in §115.358, for more than 15 days after discovery. This includes any leak detected using the alternative work practice on a component that is subject to the requirements of this division but not specifically selected for alternative work practice monitoring. | § 115.354(1) § 115.354(11) § 115.354(13)(A) § 115.354(13)(B) § 115.354(13)(C) § 115.354(13)(D) § 115.354(13)(E) § 115.354(13)(F) § 115.354(4) § 115.354(5) § 115.354(9) [G]§ 115.355 § 115.358(c)(2) § 115.358(d) [G]§ 115.358(e) § 115.358(f) | § 115.352(7) § 115.354(13)(D) § 115.354(13)(E) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) [G]§ 115.356(4) § 115.356(5) | [G]§ 115.358(g) |
| B78APFU1 | EU | R5352-ALL | VOC | 30 TAC Chapter 115, Pet. Refinery & Petrochemicals | § 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8) § 115.357(9) | No valves contacting a fluid with TVP greater than 0.044 psia (gas/vapor or light liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid | § 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 | § 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5) | [G]§ 115.354(7) |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|-----------|--|---|--|--|--|---|
| | | | | | | based on sight, smell, or sound. | | | |
| B78APFU1 | EU | R5352-ALL | VOC | 30 TAC Chapter 115, Pet. Refinery & Petrochemicals | § 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(8) § 115.357(1) § 115.357(12) § 115.357(8) | No flanges or other connectors contacting a fluid with TVP less than or equal to 0.044 psia (heavy liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound. | § 115.354(1) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1) | § 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5) | None |
| B78APFU1 | EU | R5352-ALL | VOC | 30 TAC Chapter 115, Pet. Refinery & Petrochemicals | § 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(8) § 115.357(12) § 115.357(8) | No flanges or other connectors contacting a fluid with TVP greater than 0.044 psia (gas/vapor or light liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound. | § 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 | § 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5) | None |
| B78APFU1 | EU | R5352-ALL | VOC | 30 TAC Chapter 115, Pet. Refinery & Petrochemicals | § 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) | No agitators contacting a fluid with TVP less than or equal to 0.044 psia (heavy liquid service) shall be | [G]§ 115.355 § 115.357(1) | § 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) | None |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|-----------|--|--|--|-------------------------------------|---|---|
| | | | | | § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(7) § 115.357(1) § 115.357(8) | allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound. | | § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5) | |
| B78APFU1 | EU | R5352-ALL | VOC | 30 TAC Chapter 115, Pet. Refinery & Petrochemicals | § 115.352(1)(A) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(7) § 115.357(8) | No agitators contacting a fluid with TVP greater than 0.044 psia (gas/vapor or light liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound. | [G]§ 115.355 | § 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5) | None |
| B78APFU1 | EU | R5352-ALL | VOC | 30 TAC Chapter 115, Pet. Refinery & Petrochemicals | § 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(3) | No compressor seals in hydrogen service with and the hydrogen content can be expected to always exceed 50.0% by volume shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background | [G]§ 115.355 | § 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5) | None |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|-----------|--|--|---|--|---|---|
| | | | | | § 115.357(8) | as methane, or the dripping or exuding of process fluid based on sight, smell, or sound. | | | |
| B78APFU1 | EU | R5352-ALL | VOC | 30 TAC Chapter 115, Pet. Refinery & Petrochemicals | § 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(4) § 115.357(8) | No compressor seals that are equipped with a shaft sealing system that prevents or detects emissions of VOCs from the seal shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound. | [G]§ 115.355 | § 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5) | None |
| B78APFU1 | EU | R5352-ALL | VOC | 30 TAC Chapter 115, Pet. Refinery & Petrochemicals | § 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1) § 115.357(8) | No compressor seals contacting a fluid with TVP less than or equal to 0.044 psia (heavy liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound. | § 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1) | § 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5) | None |
| B78APFU1 | EU | R5352-ALL | VOC | 30 TAC Chapter 115, Pet. Refinery & Petrochemicals | § 115.352(1)(B) § 115.352(1) § 115.352(2) | No compressor seals contacting a fluid with TVP greater than 0.044 psia | § 115.354(1) § 115.354(10) § 115.354(2) | § 115.352(7) § 115.354(10) § 115.356 | None |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|-----------|--|--|---|--|--|---|
| | | | | | § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8) | (gas/vapor or light liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound. | § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 | [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5) | |
| B78APFU1 | EU | R5352-ALL | VOC | 30 TAC Chapter 115, Pet. Refinery & Petrochemicals | § 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(4) § 115.357(8) | No pump seals that are equipped with a shaft sealing system that prevents or detects emissions of VOCs from the seal shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound. | [G]§ 115.355 | § 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5) | None |
| B78APFU1 | EU | R5352-ALL | VOC | 30 TAC Chapter 115, Pet. Refinery & Petrochemicals | § 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) | No pump seals contacting a fluid with TVP less than or equal to 0.044 psia (heavy liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by | § 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1) | § 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5) | None |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|---------------------|--|---|--|--|--|---|
| | | | | | § 115.352(7) § 115.357(1) § 115.357(8) | volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound. | | | |
| B78APFU1 | EU | R5352-ALL | VOC | 30 TAC Chapter 115, Pet. Refinery & Petrochemicals | § 115.352(1)(B) § 115.352(1) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8) | No pump seals contacting a fluid with TVP greater than 0.044 psia (gas/vapor or light liquid service) shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dripping or exuding of process fluid based on sight, smell, or sound. | § 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 | § 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5) | None |
| B78APFU1 | EU | 63FFFF-01 | 112(B) HAPS | 40 CFR Part 63, Subpart FFFF | § 63.2480(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart FFFF | The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart FFFF | The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart FFFF | The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart FFFF | The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart FFFF |
| B78APKO2A | EP | R5720-01 | Highly Reactive VOC | 30 TAC Chapter 115, HRVOC Vent Gas | § 115.727(f) § 115.725(n) | All sites that are subject to this division and that are located in the Houston/Galveston/ Brazoria area as defined in §115.10 of this title (relating to Definitions), excluding Harris County, are exempt | None | § 115.726(i) § 115.726(j)(1) § 115.726(j)(2) | § 115.725(n) |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|-----------|---------------------------------------|---|--|--|---|---|
| | | | | | | from § 115.722(b) and (c)(2) of this title, except as provided in § 115.729(a)(3) of this title (relating to Counties and Compliance Schedules). | | | |
| B78APKO2A | EP | R5121-01 | VOC | 30 TAC Chapter 115, Vent Gas Controls | § 115.122(a)(1) § 115.121(a)(1) § 115.122(a)(1)(B) § 60.18 | Vent gas streams affected by § 115.121(a)(1) must be controlled properly with a control efficiency of at least 90% or to a volatile organic compound (VOC) concentration of no more than 20 parts per million (ppmv) (on a dry basis corrected to 3.0% oxygen for combustion devices). | [G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2) | § 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2) | None |
| B78APPTT1 | EU | R5112-01 | VOC | 30 TAC Chapter 115, Storage of VOCs | § 115.112(e)(1) § 115.112(e)(3) § 115.112(e)(3)(C) § 60.18 | No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate. | § 115.115(a) § 115.115(a)(6) § 115.116(a)(2) [G]§ 115.117 | § 115.118(a)(4) § 115.118(a)(4)(F) § 115.118(a)(5) § 115.118(a)(7) | None |
| B78APST5 | EU | R5112-01 | VOC | 30 TAC Chapter 115, Storage of VOCs | § 115.111(a)(1) | Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than | [G]§ 115.117 | § 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7) | None |

Applicable Requirements Summary

| Unit Group Process ID No. | Unit Group Process Type | SOP Index No. | Pollutant | State Rule or Federal Regulation Name | Emission Limitation, Standard or Equipment Specification Citation | Textual Description (See Special Term and Condition 1.B.) | Monitoring And Testing Requirements | Recordkeeping Requirements (30 TAC § 122.144) | Reporting Requirements (30 TAC § 122.145) |
|---------------------------|-------------------------|---------------|-------------|--|--|--|-------------------------------------|---|---|
| | | | | | | 1.5 psia is exempt from the requirements of this division. | | | |
| PROAPP | PRO | R5460-01 | VOC | 30 TAC Chapter 115, Subchapter E, Division 6 | [G]§ 115.461(d) [G]§ 115.463(c) | The following are exempt from the VOC limits in §115.463(a) of this title (relating to Control Requirements): §115.461(d)(1)-(17) | None | § 115.468(b)(2) § 115.468(b)(5) | None |
| PROAPP | PRO | 63FFFF-01 | 112(B) HAPS | 40 CFR Part 63, Subpart FFFF | § 63.2440(a) § 63.2450(a) § 63.2450(a)(2) [G]§ 63.2450(e)(4) § 63.2450(g)(7) § 63.2450(k)(8) § 63.2450(l) § 63.2450(t) § 63.2450(u) [G]§ 63.2450(v) | This subpart applies to each miscellaneous organic chemical manufacturing affected source. | § 63.2445(d) § 63.2450(g)(6) | § 63.2525 § 63.2525(a) [G]§ 63.2525(b) § 63.2525(c) [G]§ 63.2525(p) | § 63.2435(d) § 63.2445(c) § 63.2450(g)(5) § 63.2450(m) § 63.2450(m)(1) § 63.2450(m)(2) § 63.2515(a) § 63.2515(b)(1) § 63.2515(c) § 63.2520(a) [G]§ 63.2520(b) [G]§ 63.2520(c) [G]§ 63.2520(d) § 63.2520(e) § 63.2520(e)(1) [G]§ 63.2520(e)(10) [G]§ 63.2520(e)(14) § 63.2520(e)(2) § 63.2520(e)(3) § 63.2520(e)(5) § 63.2520(e)(5)(i) [G]§ 63.2520(e)(5)(ii) [G]§ 63.2520(e)(5)(iii) § 63.2520(e)(6) § 63.2520(e)(7) § 63.2520(e)(9) |

Additional Monitoring Requirements

Periodic Monitoring Summary 85

Periodic Monitoring Summary

| Unit/Group/Process Information | |
|---|-----------------------------|
| ID No.: B77APSC07 | |
| Control Device ID No.: N/A | Control Device Type: N/A |
| Applicable Regulatory Requirement | |
| Name: 30 TAC Chapter 115, Degreasing Processes | SOP Index No.: R5412-01 |
| Pollutant: VOC | Main Standard: § 115.412(1) |
| Monitoring Information | |
| Indicator: Visual Inspection | |
| Minimum Frequency: Monthly | |
| Averaging Period: N/A | |
| Deviation Limit: Any monitoring data which indicates that the cold cleaner is not in compliance with the applicable requirements of 30 TAC § 115.412(1)(A) shall be considered and reported as a deviation. | |
| Periodic Monitoring Text: Inspect equipment and record data monthly to ensure compliance with any applicable requirements in § 115.412(1)(A)-(F). Any monitoring data which indicates that the cold cleaner is not in compliance with the applicable requirements of § 115.412(1)(A)-(F) shall be considered and reported as a deviation. | |

Permit Shield

Permit Shield 87

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

| Unit / Group / Process ID No. | Group / Inclusive Units | Regulation | Basis of Determination |
|-------------------------------|-------------------------|--|--|
| B77APD132 | N/A | 30 TAC Chapter 115, Storage of VOCs | Tank capacity is less than 1,000 gallons. |
| B77APD132 | N/A | 40 CFR Part 60, Subpart Kb | Constructed after July 23, 1984 and capacity is less than 19,800 gallons. |
| B77APD132 | N/A | 40 CFR Part 61, Subpart FF | Does not contain or store benzene waste. |
| B77APD132 | N/A | 40 CFR Part 61, Subpart Y | Does not store benzene. |
| B77APPT10 | N/A | 40 CFR Part 63, Subpart FFFF | Uncontrolled HAP emissions are less than 200 lb/yr so does not meet the definition of a batch process vent |
| B77APPT10A | N/A | 40 CFR Part 63, Subpart FFFF | Uncontrolled HAP emissions are less than 200 lb/yr so does not meet the definition of a batch process vent |
| B77APPT11 | N/A | 40 CFR Part 63, Subpart FFFF | Uncontrolled HAP emissions are less than 200 lb/yr so does not meet the definition of a batch process vent |
| B77APPT11A | N/A | 40 CFR Part 63, Subpart FFFF | Uncontrolled HAP emissions are less than 200 lb/yr so does not meet the definition of a batch process vent |
| B77APPT12 | N/A | 40 CFR Part 63, Subpart FFFF | Uncontrolled HAP emissions are less than 200 lb/yr so does not meet the definition of a batch process vent |
| B77APPT12A | N/A | 40 CFR Part 63, Subpart FFFF | Uncontrolled HAP emissions are less than 200 lb/yr so does not meet the definition of a batch process vent |
| B77APRX1 | N/A | 40 CFR Part 60, Subpart RRR | Affected facility does not produce any of the chemicals listed in 60.707. |
| B77APSC01 | N/A | 30 TAC Chapter 115, Degreasing Processes | The remote reservoir cold cleaner uses a |

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

| Unit / Group / Process ID No. | Group / Inclusive Units | Regulation | Basis of Determination |
|-------------------------------|-------------------------|----------------------------|--|
| | | | solvent with a true vapor pressure of less than 0.6 psia at 100°F with a drain area less than 16 in2. Waste solvent is disposed of in enclosed containers. |
| B77APSPS1 | N/A | 40 CFR Part 61, Subpart FF | The separator does not contain benzene hazardous waste from the listed chemical manufacturing plant. |
| B77APSPS2 | N/A | 40 CFR Part 61, Subpart FF | The separator does not contain benzene hazardous waste from the listed chemical manufacturing plant. |
| B77APSPS3 | N/A | 40 CFR Part 61, Subpart FF | The separator does not contain benzene hazardous waste from the listed chemical manufacturing plant. |
| B77APST1 | N/A | 40 CFR Part 60, Subpart Ka | Constructed after May 18, 1978 and prior to July 23, 1984 and storage capacity less than 40,000 gallons. |
| B77APST1 | N/A | 40 CFR Part 61, Subpart FF | The storage tank does not contain benzene hazardous waste from the listed chemical manufacturing plant. |
| B77APST1 | N/A | 40 CFR Part 61, Subpart Y | Does not store benzene |
| B77APST10 | N/A | 40 CFR Part 60, Subpart Ka | Constructed after May 18, 1978 and prior to July 23, 1984 and storage capacity less than 40,000 gallons. |
| B77APST10 | N/A | 40 CFR Part 61, Subpart FF | The storage tank does not contain benzene hazardous waste from the listed chemical manufacturing plant. |
| B77APST10 | N/A | 40 CFR Part 61, Subpart Y | Does not store benzene |

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

| Unit / Group / Process ID No. | Group / Inclusive Units | Regulation | Basis of Determination |
|-------------------------------|-------------------------|-------------------------------------|---|
| B77APST10 | N/A | 40 CFR Part 63, Subpart FFFF | Contains HAP only as impurities so does not meet the definition of a storage tank. |
| B77APST11 | N/A | 40 CFR Part 60, Subpart Ka | Constructed after May 18, 1978 and prior to July 23, 1984 and does not store petroleum liquids. |
| B77APST11 | N/A | 40 CFR Part 61, Subpart FF | The storage tank does not contain benzene hazardous waste from the listed chemical manufacturing plant. |
| B77APST11 | N/A | 40 CFR Part 61, Subpart Y | Does not store benzene |
| B77APST11 | N/A | 40 CFR Part 63, Subpart FFFF | Contains HAP only as impurities so does not meet the definition of a storage tank. |
| B77APST12 | N/A | 40 CFR Part 60, Subpart Ka | Constructed after May 18, 1978 and prior to July 23, 1984 and does not store petroleum liquids. |
| B77APST12 | N/A | 40 CFR Part 61, Subpart FF | The storage tank does not contain benzene hazardous waste from the listed chemical manufacturing plant. |
| B77APST12 | N/A | 40 CFR Part 61, Subpart Y | Does not store benzene |
| B77APST12 | N/A | 40 CFR Part 63, Subpart FFFF | Contains HAP only as impurities so does not meet the definition of a storage tank. |
| B77APST133 | N/A | 40 CFR Part 63, Subpart FFFF | By definition, this vent is not a regulated batch process vent because it contains less than 50 ppm of HAP. |
| B77APST750 | N/A | 30 TAC Chapter 115, Storage of VOCs | Capacity is less than 1,000 gallons |
| B77APST750 | N/A | 40 CFR Part 60, Subpart Kb | Constructed after July 23, 1984 and capacity is less than 1,000 gallons (less than 75 cubic meters) |

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

| Unit / Group / Process ID No. | Group / Inclusive Units | Regulation | Basis of Determination |
|-------------------------------|-------------------------|------------------------------|--|
| B77APST750 | N/A | 40 CFR Part 63, Subpart FFFF | Contains HAP only as impurities so does not meet the definition of a storage tank. |
| B77APST8 | N/A | 40 CFR Part 60, Subpart Ka | Constructed after May 18, 1978 and prior to July 23, 1984 and does not store petroleum liquids. |
| B77APST8 | N/A | 40 CFR Part 61, Subpart FF | The storage tank does not contain benzene hazardous waste from the listed chemical manufacturing plant. |
| B77APST8 | N/A | 40 CFR Part 61, Subpart Y | Does not store benzene |
| B77APSTT14 | N/A | 40 CFR Part 60, Subpart Ka | Constructed after May 18, 1978 and prior to July 23, 1984 and does not store petroleum liquids. |
| B77APSTT14 | N/A | 40 CFR Part 61, Subpart FF | The storage tank does not contain benzene hazardous waste from the listed chemical manufacturing plant. |
| B77APSTT14 | N/A | 40 CFR Part 61, Subpart Y | Does not store benzene |
| B77APSTT15 | N/A | 40 CFR Part 60, Subpart Ka | Constructed after May 18, 1978 and prior to July 23, 1984 and does not store petroleum liquids. |
| B77APSTT15 | N/A | 40 CFR Part 61, Subpart FF | The storage tank does not contain benzene hazardous waste from the listed chemical manufacturing plant. |
| B77APSTT15 | N/A | 40 CFR Part 61, Subpart Y | Does not store benzene |
| B77APV101 | N/A | 40 CFR Part 63, Subpart FFFF | By definition, this vent is not a regulated batch process vent because it contains less than 50 ppm of HAP |
| B77APV102 | N/A | 40 CFR Part 63, Subpart FFFF | By definition, this vent is not a regulated batch process vent because it contains less than 50 ppm of HAP |

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

| Unit / Group / Process ID No. | Group / Inclusive Units | Regulation | Basis of Determination |
|-------------------------------|-------------------------|---|--|
| B77APWW | N/A | 30 TAC Chapter 115, Industrial Wastewater | Wastewater does not meet the definition of affected VOC wastewater streams. |
| B77SB101 | N/A | 40 CFR Part 63, Subpart FFFF | Uncontrolled HAP emissions are less than 200 lb/yr so does not meet the definition of a batch process vent |
| B77SB102 | N/A | 40 CFR Part 63, Subpart FFFF | Uncontrolled HAP emissions are less than 200 lb/yr so does not meet the definition of a batch process vent |
| B77SB103 | N/A | 40 CFR Part 63, Subpart FFFF | Uncontrolled HAP emissions are less than 200 lb/yr so does not meet the definition of a batch process vent |
| B77SB104 | N/A | 40 CFR Part 63, Subpart FFFF | Uncontrolled HAP emissions are less than 200 lb/yr so does not meet the definition of a batch process vent |
| B77SB105 | N/A | 40 CFR Part 63, Subpart FFFF | Uncontrolled HAP emissions are less than 200 lb/yr so does not meet the definition of a batch process vent |
| B77SB106 | N/A | 40 CFR Part 63, Subpart FFFF | Uncontrolled HAP emissions are less than 200 lb/yr so does not meet the definition of a batch process vent |
| B77SB107 | N/A | 40 CFR Part 63, Subpart FFFF | Uncontrolled HAP emissions are less than 200 lb/yr so does not meet the definition of a batch process vent |
| B77SPS102 | N/A | 40 CFR Part 61, Subpart FF | The separator does not contain benzene hazardous waste from the listed chemical manufacturing plant. |
| B78APPTT1 | N/A | 40 CFR Part 60, Subpart Kb | Constructed after July 23, 1984 and capacity is |

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

| Unit / Group / Process ID No. | Group / Inclusive Units | Regulation | Basis of Determination |
|-------------------------------|-------------------------|----------------------------|---|
| | | | less than 19,800 gallons. |
| B78APPTT1 | N/A | 40 CFR Part 61, Subpart FF | Does not contain or store benzene waste. |
| B78APPTT1 | N/A | 40 CFR Part 61, Subpart Y | Does not store benzene |
| B78APST5 | N/A | 40 CFR Part 60, Subpart Ka | Constructed after May 18, 1978 and prior to 23, 1984 and does not store petroleum liquids. |
| B78APST5 | N/A | 40 CFR Part 61, Subpart FF | The storage tank does not contain benzene hazardous waste from the listed chemical manufacturing plant. |
| B78APST5 | N/A | 40 CFR Part 61, Subpart Y | Does not store benzene |

New Source Review Authorization References

| | |
|--|-----------|
| New Source Review Authorization References | 94 |
| New Source Review Authorization References by Emission Unit | 95 |

New Source Review Authorization References

The New Source Review authorizations listed in the table below are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

| Title 30 TAC Chapter 116 Permits, Special Permits, and Other Authorizations (Other Than Permits By Rule, PSD Permits, or NA Permits) for the Application Area. | |
|--|------------------------------|
| Authorization No.: 8567 | Issuance Date: 12/22/2021 |
| Permits By Rule (30 TAC Chapter 106) for the Application Area | |
| Number: 106.124 | Version No./Date: 09/04/2000 |
| Number: 106.261 | Version No./Date: 11/01/2003 |
| Number: 106.262 | Version No./Date: 11/01/2003 |
| Number: 106.263 | Version No./Date: 11/01/2001 |
| Number: 106.371 | Version No./Date: 09/04/2000 |
| Number: 106.454 | Version No./Date: 07/08/1998 |
| Number: 106.473 | Version No./Date: 09/04/2000 |

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

| Unit/Group/Process ID No. | Emission Unit Name/Description | New Source Review Authorization** |
|---------------------------|---------------------------------|--|
| B77APCF401 | KNOCKOUT VENT | 106.261/11/01/2003 [105203] |
| B77APCF402 | KNOCKOUT VENT | 106.261/11/01/2003 [105203] |
| B77APCT1 | CT-1 | 8567, 106.371/09/04/2000 |
| B77APD108 | APP MATERIALS HANDLING VENT 108 | 8567 |
| B77APD109 | APP MATERIALS HANDLING VENT 109 | 8567 |
| B77APD132 | PTZ-EA TOTE | 106.261/11/01/2003 [148427], 106.262/11/01/2003 [148427] |
| B77APFU1 | B-77 PROCESS FUGITIVES | 8567, 106.261/11/01/2003 [105203, 106311, 108295, 148427, 179825], 106.262/11/01/2003 [108295, 148427], 106.263/11/01/2001, 106.473/09/04/2000 |
| B77APLR1 | APP LOADING RACK | 8567 |
| B77APLR133 | KEROSENE LOADING | 8567, 106.473/09/04/2000 |
| B77APLR750 | D-50 WASTE CATALYST LOADING | 8567 |
| B77APPT10 | CATALYST MIX TANK | 8567 |
| B77APPT10A | CATALYST MIX TANK | 8567 |
| B77APPT11 | CATALYST MIX TANK | 8567 |
| B77APPT11A | CATALYST MIX TANK | 8567 |
| B77APPT12 | CATALYST MIX TANK | 8567 |
| B77APPT12A | CATALYST MIX TANK | 8567 |
| B77APPVAV | APP HRVOC ANALYZERS | 106.261/11/01/2003 [179825], 106.262/11/01/2003 [179825] |

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

| Unit/Group/Process ID No. | Emission Unit Name/Description | New Source Review Authorization** |
|---------------------------|--------------------------------------|-----------------------------------|
| B77APRX1 | APP PROCESS | 8567 |
| B77APSC01 | DEGREASER | 106.454/07/08/1998 |
| B77APSC07 | B7700 MAINTENANCE & SOLVENT CLEANING | 8567 |
| B77APSP101 | APP SPIN DRYER VENT 101 | 8567 |
| B77APSPS1 | AP OIL/WATER SEPARATOR SUMP 1 | 8567 |
| B77APSPS2 | AP OIL/WATER SEPARATOR SUMP 2 | 8567 |
| B77APSPS3 | AP OIL/WATER SEPARATOR SUMP 3 | 8567 |
| B77APST1 | KEROSENE STORAGE TANK T-1 | 8567 |
| B77APST10 | AP STORAGE TANK T-10 | 8567 |
| B77APST11 | AP STORAGE TANK T-11 | 8567 |
| B77APST12 | AP STORAGE TANK T-12 | 8567 |
| B77APST133 | KEROSENE PROCESS TANK | 8567 |
| B77APST750 | APP CATALYST AND WASTE OIL DUMPSTER | 8567 |
| B77APST8 | AP STORAGE TANK T-8 | 8567 |
| B77APSTT14 | AP STORAGE TANK T-14 | 8567 |
| B77APSTT15 | AP STORAGE TANK T-15 | 8567 |
| B77APV101 | APP SILO V-101, CHECK HOPPER | 8567 |
| B77APV102 | APP SILO V-102, CHECK HOPPER | 8567 |
| B77APWW | APP POLYETHYLENE WASTE WATER | 8567 |
| B77SB101 | APP SILO SB-101, MAKE HOPPER | 8567 |
| B77SB102 | APP SILO SB-102, MAKE HOPPER | 8567 |

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

| Unit/Group/Process ID No. | Emission Unit Name/Description | New Source Review Authorization** |
|---------------------------|--------------------------------|---|
| B77SB103 | APP SILO SB-103, MAKE HOPPER | 8567 |
| B77SB104 | APP SILO SB-104, MAKE HOPPER | 8567 |
| B77SB105 | APP SILO SB-105, MAKE HOPPER | 8567 |
| B77SB106 | APP SILO SB-106, MAKE HOPPER | 8567 |
| B77SB107 | APP SILO SB-107, MAKE HOPPER | 8567 |
| B77SPS102 | AP SEPARATOR | 8567 |
| B77SPS103 | AP SEPARATOR | 8567 |
| B78APF1 | APP FLARE | 8567, 106.261/11/01/2003 [142435], 106.263/11/01/2001 |
| B78APFU1 | B-78 PROCESS FUGITIVES | 8567, 106.124/09/04/2000 |
| B78APKO2A | APP FLARE KNOCK OUT DRUM D-22 | 8567 |
| B78APPTT1 | ACRYLIC ACID ISOCONTAINER | 106.124/09/04/2000 |
| B78APST5 | AP STORAGE TANK T-5 | 8567, 106.261/11/01/2003 [108295], 106.262/11/01/2003 [108295] |
| PROAPP | APP PROCESS UNIT | 8567 |

**This column may include Permit by Rule (PBR) numbers and version dates, PBR Registration numbers in brackets, Standard Permit Registration numbers, Minor NSR permit numbers, and Major NSR permit numbers.

Alternative Requirement

Alternative Requirement..... 99

Buddy Garcia, *Chairman*
Larry R. Soward, *Commissioner*
Bryan W. Shaw, Ph.D., *Commissioner*
Glenn Shankle, *Executive Director*



TEXAS COMMISSION ON ENVIRONMENTAL QUALITY

Protecting Texas by Reducing and Preventing Pollution

January 23, 2008

Mr. Joel Courtwright
Sr. Environmental Specialist
Dow Chemical Company
2301 N. Brazosport Blvd.
Freeport, TX 77541-3257

Re: Testing Waiver Request for the APP Flare, Texas Commission on Environmental Quality (TCEQ) Permit No. 8567, Emission Point Number (EPN) B78F1, Air Account No. BL-0082-R, RN100225945, CN600356976 Subject to title 40 Code of Federal Regulations Part 63 (40 CFR 63), Subpart FFFF.

Dear Mr. Courtwright:

The purpose of this letter is to respond to your November 5, 2007 request to waive testing the APP Flare, EPN B78F1 based upon 40 CFR 63, Subpart A, 63.7(e)(2)(iv). The flare flow rate and net heating value of the gas combusted are continuously monitored by the instruments noted below:

GE Panametrics ultrasonic flowmeter, Model GM868-1-11-21004-FM-S, Serial # 1693

Siemens Maxum II Gas Chromatograph, Serial # 5060380001

These instruments are installed, operated, and maintained according to the requirements of 30 Texas Administrative Code Chapter 115, §115.725(d), and may demonstrate by other means to the TCEQ that the facility is in compliance with the standard.

40 CFR 60, §60.18(c)(1) and 40 CFR 63, §63.11(b)(4) require flares be designed for smokeless operations. Compliance with the design requirement does not eliminate the need to confirm proper operation, therefore the request to waive Method 22 testing is denied.

Mr. Joel Courtwright
January 23, 2008
Page 2

By copy of this letter we are informing the Environmental Protection Agency, Region 6, of this decision as required by TCEQ's delegation of authority. If you have any questions, please contact me at (512) 239-1676.

Sincerely,

A handwritten signature in cursive script, appearing to read "John R. Smith".

John R. Smith
Air Program Support Section
Field Operations Support Division

JRS/

cc: Mr. David Garcia, 6EN-A, USEPA Region 6, 1445 Ross Avenue, Suite 1200, Dallas,
Texas 75202-2733

Mr. Joel Anderson, Air Section Manager, TCEQ Field Operations Division, Houston
Regional Office

Appendix A

Acronym List 102

Acronym List

The following abbreviations or acronyms may be used in this permit:

| | |
|------------------------|---|
| ACFM | actual cubic feet per minute |
| AMOC | alternate means of control |
| ARP | Acid Rain Program |
| ASTM | American Society of Testing and Materials |
| B/PA | Beaumont/Port Arthur (nonattainment area) |
| CAM | Compliance Assurance Monitoring |
| CD | control device |
| CEMS | continuous emissions monitoring system |
| CFR | Code of Federal Regulations |
| COMS | continuous opacity monitoring system |
| CVS | closed vent system |
| D/FW | Dallas/Fort Worth (nonattainment area) |
| EP | emission point |
| EPA | U.S. Environmental Protection Agency |
| EU | emission unit |
| FCAA Amendments | Federal Clean Air Act Amendments |
| FOP | federal operating permit |
| gr/100 scf | grains per 100 standard cubic feet |
| HAP | hazardous air pollutant |
| H/G/B | Houston/Galveston/Brazoria (nonattainment area) |
| H ₂ S | hydrogen sulfide |
| ID No. | identification number |
| lb/hr | pound(s) per hour |
| MACT | Maximum Achievable Control Technology (40 CFR Part 63) |
| MMBtu/hr | Million British thermal units per hour |
| NA | nonattainment |
| N/A | not applicable |
| NADB | National Allowance Data Base |
| NESHAP | National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) |
| NO _x | nitrogen oxides |
| NSPS | New Source Performance Standard (40 CFR Part 60) |
| NSR | New Source Review |
| ORIS | Office of Regulatory Information Systems |
| Pb | lead |
| PBR | Permit By Rule |
| PEMS | predictive emissions monitoring system |
| PM | particulate matter |
| ppmv | parts per million by volume |
| PRO | process unit |
| PSD | prevention of significant deterioration |
| psia | pounds per square inch absolute |
| SIP | state implementation plan |
| SO ₂ | sulfur dioxide |
| TCEQ | Texas Commission on Environmental Quality |
| TSP | total suspended particulate |
| TVP | true vapor pressure |
| U.S.C. | United States Code |
| VOC | volatile organic compound |