FEDERAL OPERATING PERMIT

A FEDERAL OPERATING PERMIT IS HEREBY ISSUED TO Motiva Enterprises LLC

AUTHORIZING THE OPERATION OF
Port Neches Terminal
Port Terminal
Petroleum Bulk Stations and Terminals

LOCATED AT

Jefferson County, Texas Latitude 29° 59′ 21″ Longitude 93° 56′ 21″ Regulated Entity Number: RN100210103

This permit is issued in accordance with and subject to the Texas Clean Air Act (TCAA), Chapter 382 of the Texas Health and Safety Code and Title 30 Texas Administrative Code Chapter 122 (30 TAC Chapter 122), Federal Operating Permits. Under 30 TAC Chapter 122, this permit constitutes the permit holder's authority to operate the site and emission units listed in this permit. Operations of the site and emission units listed in this permit are subject to all additional rules or amended rules and orders of the Commission pursuant to the TCAA.

This permit does not relieve the permit holder from the responsibility of obtaining New Source Review authorization for new, modified, or existing facilities in accordance with 30 TAC Chapter 116, Control of Air Pollution by Permits for New Construction or Modification.

The site and emission units authorized by this permit shall be operated in accordance with 30 TAC Chapter 122, the general terms and conditions, special terms and conditions, and attachments contained herein.

This permit shall expire five years from the date of issuance. The renewal requirements specified in 30 TAC § 122.241 must be satisfied in order to renew the authorization to operate the site and emission units.

Permit No:	O3277	Issuance Date:	February 1, 2023	
For the Co	mmission			

Table of Contents

Section	Page
General Terms and Conditions	1
Special Terms and Conditions:	1
Emission Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting	1
Additional Monitoring Requirements	
New Source Review Authorization Requirements	6
Compliance Requirements	
Permit Location	
Permit Shield (30 TAC § 122.148)	8
Attachments	
Applicable Requirements Summary	10
Additional Monitoring Requirements	23
Permit Shield	
New Source Review Authorization References	
Appendix A	33
Acronym List	

General Terms and Conditions

The permit holder shall comply with all terms and conditions contained in 30 TAC § 122.143 (General Terms and Conditions), 30 TAC § 122.144 (Recordkeeping Terms and Conditions), 30 TAC § 122.145 (Reporting Terms and Conditions), and 30 TAC § 122.146 (Compliance Certification Terms and Conditions).

In accordance with 30 TAC § 122.144(1), records of required monitoring data and support information required by this permit, or any applicable requirement codified in this permit, are required to be maintained for a period of five years from the date of the monitoring report, sample, or application unless a longer data retention period is specified in an applicable requirement. The five year record retention period supersedes any less stringent retention requirement that may be specified in a condition of a permit identified in the New Source Review Authorization attachment.

If the permit holder chooses to demonstrate that this permit is no longer required, a written request to void this permit shall be submitted to the Texas Commission on Environmental Quality (TCEQ) by the Responsible Official in accordance with 30 TAC § 122.161(e). The permit holder shall comply with the permit's requirements, including compliance certification and deviation reporting, until notified by the TCEQ that this permit is voided.

The permit holder shall comply with 30 TAC Chapter 116 by obtaining a New Source Review authorization prior to new construction or modification of emission units located in the area covered by this permit.

All reports required by this permit must include in the submittal a cover letter which identifies the following information: company name, TCEQ regulated entity number, air account number (if assigned), site name, area name (if applicable), and Air Permits Division permit number(s).

Special Terms and Conditions:

Emission Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting

- 1. Permit holder shall comply with the following requirements:
 - A. Emission units (including groups and processes) in the Applicable Requirements Summary attachment shall meet the limitations, standards, equipment specifications, monitoring, recordkeeping, reporting, testing, and other requirements listed in the Applicable Requirements Summary attachment to assure compliance with the permit.
 - B. The textual description in the column titled "Textual Description" in the Applicable Requirements Summary attachment is not enforceable and is not deemed as a substitute for the actual regulatory language. The Textual Description is provided for information purposes only.
 - C. A citation listed on the Applicable Requirements Summary attachment, which has a notation [G] listed before it, shall include the referenced section and subsection for all commission rules, or paragraphs for all federal and state regulations and all subordinate paragraphs, subparagraphs and clauses, subclauses, and items contained within the referenced citation as applicable requirements.
 - D. When a grouped citation, notated with a [G] in the Applicable Requirements Summary, contains multiple compliance options, the permit holder must keep records of when each compliance option was used.

- E. Emission units subject to 40 CFR Part 63, Subpart ZZZZ as identified in the attached Applicable Requirements Summary table are subject to 30 TAC Chapter 113, Subchapter C, §113.1090 which incorporates the 40 CFR Part 63 Subpart by reference.
- 2. The permit holder shall comply with the following sections of 30 TAC Chapter 101 (General Air Quality Rules):
 - A. Title 30 TAC § 101.1 (relating to Definitions), insofar as the terms defined in this section are used to define the terms used in other applicable requirements
 - B. Title 30 TAC § 101.3 (relating to Circumvention)
 - Title 30 TAC § 101.8 (relating to Sampling), if such action has been requested by the TCEQ
 - D. Title 30 TAC § 101.9 (relating to Sampling Ports), if such action has been requested by the TCEQ
 - E. Title 30 TAC § 101.10 (relating to Emissions Inventory Requirements)
 - F. Title 30 TAC § 101.201 (relating to Emission Event Reporting and Recordkeeping Requirements)
 - G. Title 30 TAC § 101.211 (relating to Scheduled Maintenance, Start-up, and Shutdown Reporting and Recordkeeping Requirements)
 - H. Title 30 TAC § 101.221 (relating to Operational Requirements)
 - I. Title 30 TAC § 101.222 (relating to Demonstrations)
 - J. Title 30 TAC § 101.223 (relating to Actions to Reduce Excessive Emissions)
- 3. Permit holder shall comply with the following requirements of 30 TAC Chapter 111:
 - A. Visible emissions from stationary vents with a flow rate of less than 100,000 actual cubic feet per minute and constructed after January 31, 1972 that are not listed in the Applicable Requirements Summary attachment for 30 TAC Chapter 111, Subchapter A, Division 1, shall not exceed 20% opacity averaged over a six-minute period. The permit holder shall comply with the following requirements for stationary vents at the site subject to this standard:
 - (i) Title 30 TAC § 111.111(a)(1)(B) (relating to Requirements for Specified Sources)
 - (ii) Title 30 TAC § 111.111(a)(1)(E)
 - (iii) Title 30 TAC § 111.111(a)(1)(F)(i), (ii), (iii), or (iv)
 - (iv) For emission units with vent emissions subject to 30 TAC § 111.111(a)(1)(B), complying with 30 TAC § 111.111(a)(1)(F)(ii), (iii), or (iv), and capable of producing visible emissions from, but not limited to, particulate matter, acid gases and NO_x, the permit holder shall also comply with the following periodic monitoring requirements for the purpose of annual compliance certification under 30 TAC § 122.146. These periodic monitoring requirements do not apply to vents that are not capable of producing visible emissions such as vents that emit only colorless VOCs; vents from non-fuming liquids; vents that provide passive

ventilation, such as plumbing vents; or vent emissions from any other source that does not obstruct the transmission of light. Vents, as specified in the "Applicable Requirements Summary" attachment, that are subject to the emission limitation of 30 TAC § 111.111(a)(1)(B) are not subject to the following periodic monitoring requirements:

- (1) An observation of stationary vents from emission units in operation shall be conducted at least once during each calendar quarter unless the emission unit is not operating for the entire quarter.
- (2) For stationary vents from a combustion source, if an alternative to the normally fired fuel is fired for a period greater than or equal to 24 consecutive hours, the permit holder shall conduct an observation of the stationary vent for each such period to determine if visible emissions are present. If such period is greater than 3 months, observations shall be conducted once during each quarter. Supplementing the normally fired fuel with natural gas or fuel gas to increase the net heating value to the minimum required value does not constitute creation of an alternative fuel
- (3) Records of all observations shall be maintained.
- (4) Visible emissions observations of emission units operated during daylight hours shall be conducted no earlier than one hour after sunrise and no later than one hour before sunset. Visible emissions observations of emission units operated only at night must be made with additional lighting and the temporary installation of contrasting backgrounds. Visible emissions observations shall be made during times when the activities described in 30 TAC § 111.111(a)(1)(E) are not taking place. Visible emissions shall be determined with each stationary vent in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 mile, away from each stationary vent during the observation. For outdoor locations, the observer shall select a position where the sun is not directly in the observer's eyes. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. A certified opacity reader is not required for visible emissions observations.
- (5) Compliance Certification:
 - (a) If visible emissions are not present during the observation, the RO may certify that the source is in compliance with the applicable opacity requirement in 30 TAC § 111.111(a)(1) and (a)(1)(B).
 - (b) However, if visible emissions are present during the observation, the permit holder shall either list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(1)(F) as soon as practicable, but no later than 24 hours after observing visible emissions to determine if the source is in compliance with the opacity

requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.

- (c) Some vents may be subject to multiple visible emission or monitoring requirements. All credible data must be considered when certifying compliance with this requirement even if the observation or monitoring was performed to demonstrate compliance with a different requirement.
- B. Emission limits on nonagricultural processes, except for the steam generators specified in 30 TAC § 111.153, shall comply with the following requirements:
 - (i) Emissions of PM from any source may not exceed the allowable rates as required in 30 TAC § 111.151(a) (relating to Allowable Emissions Limits)
 - (ii) Sources with an effective stack height (h_e) less than the standard effective stack height (H_e), must reduce the allowable emission level by multiplying it by [h_e/H_e]² as required in 30 TAC § 111.151(b)
 - (iii) Effective stack height shall be calculated by the equation specified in 30 TAC § 111.151(c)
- 4. The permit holder shall comply with the following requirements of 30 TAC Chapter 115, Subchapter F, Division 3, Degassing of Storage Tanks, Transport Vessels and Marine Vessels:
 - A. For degassing of stationary VOC storage tanks, the permit holder shall comply with the following requirements:
 - (i) Title 30 TAC § 115.541(a) (c) (relating to Emission Specifications)
 - (ii) Title 30 TAC § 115.541(f) (relating to Emission Specifications), for floating roof storage tanks
 - (iii) Title 30 TAC § 115.542(a) and (a)(1), (a)(2), (a)(3) or (a)(4) (relating to Control Requirements). Where the requirements of 30 TAC Chapter 115, Subchapter F contain multiple compliance options, the permit holder shall keep records of when each compliance option was used.
 - (iv) Title 30 TAC § 115.542(b) (d), (relating to Control Requirements)
 - (v) Title 30 TAC § 115.543 (relating to Alternate Control Requirements)
 - (vi) Title 30 TAC § 115.544(a)(1) and (a)(2) (relating to Inspection, Monitoring, and Testing Requirements), for inspections
 - (vii) Title 30 TAC § 115.544(b) (relating to Inspection, Monitoring, and Testing Requirements), for monitoring

- (viii) Title 30 TAC § 115.544(b)(1) and (b)(2) (relating to Inspection, Monitoring, and Testing Requirements), for monitoring of control devices
- (ix) Title 30 TAC § 115.544(b)(2)(A) (J) (relating to Inspection, Monitoring, and Testing Requirements), for monitoring (as appropriate to the control device)
- (x) Title 30 TAC § 115.544(b)(3), (b)(4) and (b)(6) (relating to Inspection, Monitoring, and Testing Requirements), for VOC concentration or lower explosive limit threshold monitoring
- (xi) Title 30 TAC § 115.544(c), and (c)(1) (c)(3) (relating to Inspection, Monitoring, and Testing Requirements), for testing of control devices used to comply with 30 TAC § 115.542(a)(1)
- (xii) Title 30 TAC § 115.545(1) (7), (9) (11) and (13) (relating to Approved Test Methods)
- (xiii) Title 30 TAC § 115.546(a), (a)(1) and (a)(3) (relating to Recordkeeping and Notification Requirements), for recordkeeping
- (xiv) Title 30 TAC § 115.546(a)(2) and (a)(2)(A) (J) (relating to Recordkeeping and Notification Requirements), for recordkeeping (as appropriate to the control device)
- (xv) Title 30 TAC § 115.546(a)(4) (relating to Recordkeeping and Notification Requirements), for recordkeeping of testing of control devices used to comply with 30 TAC § 115.542(a)(1)
- (xvi) Title 30 TAC § 115.547(4) (relating to Exemptions)
- 5. The permit holder shall comply with the following requirements for units subject to any subpart of 40 CFR Part 60, unless otherwise stated in the applicable subpart:
 - A. Title 40 CFR § 60.7 (relating to Notification and Recordkeeping)
 - B. Title 40 CFR § 60.8 (relating to Performance Tests)
 - C. Title 40 CFR § 60.11 (relating to Compliance with Standards and Maintenance Requirements)
 - D. Title 40 CFR § 60.12 (relating to Circumvention)
 - E. Title 40 CFR § 60.13 (relating to Monitoring Requirements)
 - F. Title 40 CFR § 60.14 (relating to Modification)
 - G. Title 40 CFR § 60.15 (relating to Reconstruction)
 - H. Title 40 CFR § 60.19 (relating to General Notification and Reporting Requirements)
- 6. The permit holder shall comply with the requirements of 30 TAC Chapter 113, Subchapter C, § 113.100 for units subject to any subpart of 40 CFR Part 63, unless otherwise stated in the applicable subpart.

7. The permit holder shall comply with certified registrations submitted to the TCEQ for purposes of establishing federally enforceable emission limits. A copy of the certified registration shall be maintained with the permit. Records sufficient to demonstrate compliance with the established limits shall be maintained. The certified registration and records demonstrating compliance shall be provided, on request, to representatives of the appropriate TCEQ regional office and any local air pollution control agency having jurisdiction over the site. The permit holder shall submit updated certified registrations when changes at the site require establishment of new emission limits. If changes result in emissions that do not remain below major source thresholds, the permit holder shall submit a revision application to codify the appropriate requirements in the permit.

Additional Monitoring Requirements

8. The permit holder shall comply with the periodic monitoring requirements as specified in the attached "Periodic Monitoring Summary" upon issuance of the permit. Except for, as applicable, monitoring malfunctions, associated repairs, and required quality assurance or control activities (including, as applicable, calibration checks and required zero and span adjustments), the permit holder shall conduct all monitoring in continuous operation (or shall collect data at all required intervals) at all times that the pollutant-specific emissions unit is operating. The permit holder may elect to collect monitoring data on a more frequent basis and average the data, consistent with the averaging time or minimum frequency specified in the "Periodic Monitoring Summary," for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis. In no event shall data be collected and used in particular instances to avoid reporting deviations. Deviations shall be reported according to 30 TAC § 122.145 (Reporting Terms and Conditions).

New Source Review Authorization Requirements

- 9. Permit holder shall comply with the requirements of New Source Review authorizations issued or claimed by the permit holder for the permitted area, including permits, permits by rule (including the terms, conditions, monitoring, recordkeeping, and reporting identified in registered PBRs and permits by rule identified in the PBR Supplemental Tables dated April 27, 2022 in the application for project 33704), standard permits, flexible permits, special permits, permits for existing facilities including Voluntary Emissions Reduction Permits and Electric Generating Facility Permits issued under 30 TAC Chapter 116, Subchapter I, or special exemptions referenced in the New Source Review Authorization References attachment. These requirements:
 - A. Are incorporated by reference into this permit as applicable requirements
 - B. Shall be located with this operating permit
 - C. Are not eligible for a permit shield
- 10. The permit holder shall comply with the general requirements of 30 TAC Chapter 106, Subchapter A or the general requirements, if any, in effect at the time of the claim of any PBR.
- 11. The permit holder shall maintain records to demonstrate compliance with any emission limitation or standard that is specified in a permit by rule (PBR) or Standard Permit listed in the New Source Review Authorizations attachment. The records shall yield reliable data from the relevant time period that are representative of the emission unit's compliance with the PBR or Standard Permit. These records may include, but are not limited to, production capacity and throughput, hours of operation, safety data sheets (SDS), chemical composition of raw materials, speciation of air contaminant data, engineering calculations, maintenance records, fugitive data, performance tests, capture/control device efficiencies, direct pollutant monitoring (CEMS, COMS, or PEMS), or control device parametric monitoring. These records shall be made readily accessible and

available as required by 30 TAC § 122.144. Any monitoring or recordkeeping data indicating noncompliance with the PBR or Standard Permit shall be considered and reported as a deviation according to 30 TAC § 122.145 (Reporting Terms and Conditions).

Compliance Requirements

- 12. The permit holder shall certify compliance in accordance with 30 TAC § 122.146. The permit holder shall comply with 30 TAC § 122.146 using at a minimum, but not limited to, the continuous or intermittent compliance method data from monitoring, recordkeeping, reporting, or testing required by the permit and any other credible evidence or information. The certification period may not exceed 12 months and the certification must be submitted within 30 days after the end of the period being certified.
- 13. Use of Emission Credits to comply with applicable requirements:
 - A. Unless otherwise prohibited, the permit holder may use emission credits to comply with the following applicable requirements listed elsewhere in this permit:
 - (i) Title 30 TAC Chapter 115
 - (ii) Title 30 TAC Chapter 117
 - (iii) Offsets for Title 30 TAC Chapter 116
 - B. The permit holder shall comply with the following requirements in order to use the emission credits to comply with the applicable requirements:
 - (i) The permit holder must notify the TCEQ according to 30 TAC § 101.306(c)-(d)
 - (ii) The emission credits to be used must meet all the geographic, timeliness, applicable pollutant type, and availability requirements listed in 30 TAC Chapter 101, Subchapter H, Division 1
 - (iii) The executive director has approved the use of the credit according to 30 TAC § 101.306(c)-(d)
 - (iv) The permit holder keeps records of the use of credits towards compliance with the applicable requirements in accordance with 30 TAC § 101.302(g) and 30 TAC Chapter 122
 - (v) Title 30 TAC § 101.305 (relating to Emission Reductions Achieved Outside the United States)
- 14. Use of Discrete Emission Credits to comply with the applicable requirements:
 - A. Unless otherwise prohibited, the permit holder may use discrete emission credits to comply with the following applicable requirements listed elsewhere in this permit:
 - (i) Title 30 TAC Chapter 115
 - (ii) Title 30 TAC Chapter 117
 - (iii) If applicable, offsets for Title 30 TAC Chapter 116
 - (iv) Temporarily exceed state NSR permit allowables

- B. The permit holder shall comply with the following requirements in order to use the credit to comply with the applicable requirements:
 - (i) The permit holder must notify the TCEQ according to 30 TAC § 101.376(d)
 - (ii) The discrete emission credits to be used must meet all the geographic, timeliness, applicable pollutant type, and availability requirements listed in 30 TAC Chapter 101, Subchapter H, Division 4
 - (iii) The executive director has approved the use of the discrete emission credits according to 30 TAC § 101.376(d)(1)(A)
 - (iv) The permit holder keeps records of the use of credits towards compliance with the applicable requirements in accordance with 30 TAC § 101.372(h) and 30 TAC Chapter 122
 - (v) Title 30 TAC § 101.375 (relating to Emission Reductions Achieved Outside the United States)

Permit Location

15. The permit holder shall maintain a copy of this permit and records related to requirements listed in this permit on site.

Permit Shield (30 TAC § 122.148)

16. A permit shield is granted for the emission units, groups, or processes specified in the attached "Permit Shield." Compliance with the conditions of the permit shall be deemed compliance with the specified potentially applicable requirements or specified potentially applicable state-only requirements listed in the attachment "Permit Shield." Permit shield provisions shall not be modified by the executive director until notification is provided to the permit holder. No later than 90 days after notification of a change in a determination made by the executive director, the permit holder shall apply for the appropriate permit revision to reflect the new determination. Provisional terms are not eligible for this permit shield. Any term or condition, under a permit shield, shall not be protected by the permit shield if it is replaced by a provisional term or condition or the basis of the term and condition changes.

Attachments

Applicable Requirements Summary

Additional Monitoring Requirements

Permit Shield

New Source Review Authorization References

Unit Summary	1	1
Applicable Requirements Summary	1	4

Note: A "none" entry may be noted for some emission sources in this permit's "Applicable Requirements Summary" under the heading of "Monitoring and Testing Requirements" and/or "Recordkeeping Requirements" and/or "Reporting Requirements." Such a notation indicates that there are no requirements for the indicated emission source as identified under the respective column heading(s) for the stated portion of the regulation when the emission source is operating under the conditions of the specified SOP Index Number. However, other relevant requirements pursuant to 30 TAC Chapter 122 including Recordkeeping Terms and Conditions (§ 122.144), Reporting Terms and Conditions (§ 122.145), and Compliance Certification Terms and Conditions (§ 122.146) continue to apply.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver	
ENGINE3	SRIC ENGINES	N/A	60IIII-01	40 CFR Part 60, Subpart IIII	No changing attributes.	
ENGINE3	SRIC ENGINES	N/A	63ZZZZ-01	40 CFR Part 63, Subpart ZZZZ	No changing attributes.	
GEN-1	SRIC ENGINES	N/A	60IIII-01	40 CFR Part 60, Subpart IIII	No changing attributes.	
GEN-1	SRIC ENGINES	N/A	63ZZZZ-01	40 CFR Part 63, Subpart ZZZZ	No changing attributes.	
GRPEFR1	STORAGE TANKS/VESSELS	TET00278, TET00279, TST00275	R5112	30 TAC Chapter 115, Storage of VOCs	No changing attributes.	
GRPEFR1	STORAGE TANKS/VESSELS	TET00278, TET00279, TST00275	60K	40 CFR Part 60, Subpart K	No changing attributes.	
GRPEFR2	STORAGE TANKS/VESSELS	340-1, 340-2, 600-1, PNT1, PNT2, PNT3, TDC01834, TDC01835	R5112-01	30 TAC Chapter 115, Storage of VOCs	Product Stored = Crude oil and/or condensate, Storage Capacity = Capacity is greater than 40,000 gallons, True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia	
GRPEFR2	STORAGE TANKS/VESSELS	340-1, 340-2, 600-1, PNT1, PNT2, PNT3, TDC01834, TDC01835	R5112-02	30 TAC Chapter 115, Storage of VOCs	Product Stored = VOC other than crude oil or condensate, Storage Capacity = Capacity is greater than 40,000 gallons, True Vapor Pressure = True vapor pressure is less than 1.0 psia	
GRPEFR2	STORAGE TANKS/VESSELS	340-1, 340-2, 600-1, PNT1, PNT2, PNT3, TDC01834, TDC01835	60KbEFR2-1	40 CFR Part 60, Subpart Kb	Product Stored = Petroleum (other than crude oil) or condensate stored, processed, and/or treated after custody transfer, Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.5 psia but less than 0.75 psia	

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
GRPEFR2	STORAGE TANKS/VESSELS	340-1, 340-2, 600-1, PNT1, PNT2, PNT3, TDC01834, TDC01835	60KbEFR2-2	40 CFR Part 60, Subpart Kb	Product Stored = Petroleum (other than crude oil) or condensate stored, processed, and/or treated after custody transfer, Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia
GRPEFR2	STORAGE TANKS/VESSELS	340-1, 340-2, 600-1, PNT1, PNT2, PNT3, TDC01834, TDC01835	60KbEFR2-3	40 CFR Part 60, Subpart Kb	Product Stored = Crude oil stored, processed, and/or treated after custody transfer, Reid Vapor Pressure = Reid vapor pressure is greater than or equal to 2.0 psia, Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.5 psia but less than 0.75 psia
GRPEFR2	STORAGE TANKS/VESSELS	340-1, 340-2, 600-1, PNT1, PNT2, PNT3, TDC01834, TDC01835	60KbEFR2-4	40 CFR Part 60, Subpart Kb	Product Stored = Crude oil stored, processed, and/or treated after custody transfer, Reid Vapor Pressure = Reid vapor pressure is greater than or equal to 2.0 psia, Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia
GRPEFR2	STORAGE TANKS/VESSELS	340-1, 340-2, 600-1, PNT1, PNT2, PNT3, TDC01834, TDC01835	60KbEFR2-5	40 CFR Part 60, Subpart Kb	Product Stored = Petroleum liquid (other than petroleum or condensate), Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.5 psia but less than 0.75 psia
GRPEFR2	STORAGE TANKS/VESSELS	340-1, 340-2, 600-1, PNT1, PNT2, PNT3,	60KbEFR2-6	40 CFR Part 60, Subpart Kb	Product Stored = Petroleum liquid (other than petroleum or

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
		TDC01834, TDC01835			condensate), Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia
GRPFXR1	STORAGE TANKS/VESSELS	TST00142, TST00143, TST00176	R5112	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
LOUT34030	STORAGE TANKS/VESSELS	N/A	R5112-02	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
LOUT34030	STORAGE TANKS/VESSELS	N/A	60Kb-1	40 CFR Part 60, Subpart Kb	No changing attributes.
TBS00280	STORAGE TANKS/VESSELS	N/A	R5112	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
TBS00280	STORAGE TANKS/VESSELS	N/A	60Kb	40 CFR Part 60, Subpart Kb	No changing attributes.
TT1815	STORAGE TANKS/VESSELS	N/A	R5112-04	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
TT1815	STORAGE TANKS/VESSELS	N/A	60Kb-2	40 CFR Part 60, Subpart Kb	No changing attributes.

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
ENGINE3	EU	60IIII-01	РМ	40 CFR Part 60, Subpart IIII	§ 60.4205(c)-Table 4 § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218	Owners and operators of emergency stationary fire pump CI ICE with a maximum engine power greater than or equal to 130 KW and less than or equal to 560 KW and a displacement of less than 30 liters per cylinder and is a 2009 model year and later must comply with a PM emission limit of 0.20 g/KW-hr, as listed in Table 4 to this subpart.	§ 60.4209(a)	§ 60.4214(b)	[G]§ 60.4214(d)
ENGINE3	EU	63ZZZZ- 01	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(c)	Stationary RICE subject to Regulations under 40 CFR Part 60. An affected source that meets any of the criteria in paragraphs (c)(1) through (7) of this section must meet the requirements of this part by meeting the requirements of 40 CFR part 60 subpart IIII, for compression ignition engines or 40 CFR part 60 subpart JJJJ, for spark ignition engines as applicable. No further requirements apply for such engines under this part.	None	None	None
GEN-1	EU	60IIII-01	со	40 CFR Part 60, Subpart IIII	§ 60.4205(b) § 60.4202(a)(2) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f)	Owners and operators of emergency stationary CI ICE, that are not fire pump engines, with a maximum engine power greater than or equal to 130 KW and less than or equal to 2237 KW	None	None	[G]§ 60.4214(d)

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.4218 § 89.112(a)	and a displacement of less than 10 liters per cylinder and is a 2007 model year and later must comply with a CO emission limit of 3.5 g/KW-hr, as stated in 40 CFR 60.4202(a)(2) and 40 CFR 89.112(a).			
GEN-1	EU	60IIII-01	NMHC and NO _X	40 CFR Part 60, Subpart IIII	§ 60.4205(b) § 60.4202(a)(2) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218 § 89.112(a)	Owners and operators of emergency stationary CI ICE, that are not fire pump engines, with a maximum engine power greater than or equal to 75 KW and less than or equal to 560 KW and a displacement of less than 10 liters per cylinder and is a 2007 model year and later must comply with an NMHC+NOx emission limit of 4.0 g/KW-hr, as stated in 40 CFR 60.4202(a)(2) and 40 CFR 89.112(a).	None	None	[G]§ 60.4214(d)
GEN-1	EU	60IIII-01	PM	40 CFR Part 60, Subpart IIII	§ 60.4205(b) § 60.4202(a)(2) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f) § 60.4218 § 89.112(a)	Owners and operators of emergency stationary CI ICE, that are not fire pump engines, with a maximum engine power greater than or equal to 130 KW and less than or equal to 2237 KW and a displacement of less than 10 liters per cylinder and is a 2007 model year and later must comply with a PM emission limit of 0.20 g/KW-hr, as stated in 40 CFR 60.4202(a)(2) and 40	None	None	[G]§ 60.4214(d)

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						CFR 89.112(a).			
GEN-1	EU	601111-01	PM (Opacity)	40 CFR Part 60, Subpart IIII	§ 60.4205(b) § 60.4202(a)(2) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(f) § 60.4218 § 89.113(a)(1) § 89.113(a)(2) § 89.113(a)(3)	Emergency stationary CI ICE, that are not fire pump engines, with displacement < 10 lpc and not constant-speed engines, with max engine power < 2237 KW and a 2007 model year and later or max engine power > 2237 KW and a 2011 model year and later, must comply with following opacity emission limits: 20% during acceleration, 15% during lugging, 50% during peaks in either acceleration or lugging modes as stated in §60.4202(a)(1)-(2), (b)(2) and §89.113(a)(1)-(3).	None	None	[G]§ 60.4214(d)
GEN-1	EU	63 <i>ZZZZ</i> - 01	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(c)	Stationary RICE subject to Regulations under 40 CFR Part 60. An affected source that meets any of the criteria in paragraphs (c)(1) through (7) of this section must meet the requirements of this part by meeting the requirements of 40 CFR part 60 subpart IIII, for compression ignition engines or 40 CFR part 60 subpart JJJJ, for spark ignition engines as applicable. No further requirements apply for such engines under this part.	None	None	None
GRPEFR1	EU	R5112	VOC	30 TAC Chapter	§ 115.112(a)(1)	Tanks shall not store VOC	§ 115.114(a)(2)	§ 115.118(a)(3)	§ 115.114(a)(2)(B)

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				115, Storage of VOCs	§ 115.112(a)(2) § 115.112(a)(2)(A) § 115.112(a)(2)(B) § 115.112(a)(2)(C) § 115.112(a)(2)(D) § 115.112(a)(2)(E) § 115.112(a)(2)(F) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	§ 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(5) § 115.118(a)(7)	§ 115.114(a)(4)(B) § 115.118(a)(3)
GRPEFR1	EU	60K	voc	40 CFR Part 60, Subpart K	§ 60.112(a)(1)	Storage vessels holding petroleum liquids with a true vapor pressure of 78 mm Hg (1.5 psia) or greater but not greater than 570 mm Hg (11.1 psia) shall have a floating roof, a vapor recovery system, or their equivalents.	** See Periodic Monitoring	§ 60.113(a)	None
GRPEFR2	EU	R5112-01	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(a)(1) § 115.112(a)(2) § 115.112(a)(2)(A) § 115.112(a)(2)(B) § 115.112(a)(2)(C) § 115.112(a)(2)(D) § 115.112(a)(2)(E) § 115.112(a)(2)(F) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)
GRPEFR2	EU	R5112-02	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
GRPEFR2	EU	60KbEFR2 -1	VOC	40 CFR Part 60, Subpart Kb	§ 60.110b(a)	Except for §60.110b(b), this subpart applies to vessels	§ 60.116b(a) § 60.116b(b)	§ 60.116b(a) § 60.116b(b)	§ 60.116b(d)

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						with a capacity greater than or equal to 75 cubic meters (19,813 gal) used to store VOLs for which construction/reconstruction/modification began after 7/23/1984.	§ 60.116b(c) § 60.116b(d) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.116b(c)	
GRPEFR2	EU	60KbEFR2 -2	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(4)(iii) § 60.113b(b)(6) § 60.113b(b)(6)(i) § 60.113b(b)(6)(i) § 60.113b(b)(6)(i) § 60.113b(b)(6)(i) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(c)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)
GRPEFR2	EU	60KbEFR2 -3	VOC	40 CFR Part 60, Subpart Kb	§ 60.110b(a)	Except for §60.110b(b), this subpart applies to vessels with a capacity greater than or equal to 75 cubic meters (19,813 gal) used to store VOLs for which construction/reconstruction/modification began after 7/23/1984.	§ 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(d) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2) § 60.116b(e)(2)(i)	§ 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.116b(d)

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GRPEFR2	EU	60KbEFR2 -4	voc	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6) § 60.113b(b)(6) § 60.113b(b)(6)(i) § 60.113b(b)(6)(ii) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(2) § 60.116b(e)(2) § 60.116b(e)(2) § 60.116b(e)(2)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)
GRPEFR2	EU	60KbEFR2 -5	VOC	40 CFR Part 60, Subpart Kb	§ 60.110b(a)	Except for §60.110b(b), this subpart applies to vessels with a capacity greater than or equal to 75 cubic meters (19,813 gal) used to store VOLs for which construction/reconstruction/modification began after 7/23/1984.	§ 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(d) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2) § 60.116b(e)(2)(i)	§ 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.116b(d)
GRPEFR2	EU	60KbEFR2 -6	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck type) are to meet the specifications of	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4) § 60.113b(b)(4)(i) §	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b § 60.115b(b)(1) [G]§ 60.115b(b)(2)

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						§60.112b(a)(2)(i)-(iii).	60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6) (ii) § 60.113b(b)(6)(ii) § 60.113b(b)(6)(iii) § 60.116b(a) § 60.116b(c) § 60.116b(c) § 60.116b(c) § 60.116b(e) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2) § 60.116b(e)(2) § 60.116b(e)(2) §		§ 60.115b(b)(4)
GRPFXR1	EU	R5112	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
LOUT34030	EU	R5112-02	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(a)(1) § 115.112(a)(2) § 115.112(a)(2)(A) § 115.112(a)(2)(B) § 115.112(a)(2)(C) § 115.112(a)(2)(D) § 115.112(a)(2)(E) § 115.112(a)(2)(F) § 115.114(a)(2)(A) § 115.114(a)(4)(A)	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	§ 115.114(a)(2) § 115.114(a)(3) § 115.114(a)(4) § 115.114(a)(4)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(7)	§ 115.114(a)(2)(B) § 115.114(a)(4)(B) § 115.118(a)(3)
LOUT34030	EU	60Kb-1	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(2)	Storage vessels specified in §60.112b(a) and equipped with an external floating roof (pontoon or double-deck	[G]§ 60.113b(b)(1) [G]§ 60.113b(b)(2) § 60.113b(b)(3) § 60.113b(b)(4)	§ 60.115b [G]§ 60.115b(b)(3) § 60.116b(a) § 60.116b(b)	§ 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6)(ii) § 60.115b

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						type) are to meet the specifications of §60.112b(a)(2)(i)-(iii).	§ 60.113b(b)(4)(i) § 60.113b(b)(4)(i)(A) § 60.113b(b)(4)(i)(B) [G]§ 60.113b(b)(4)(ii) § 60.113b(b)(4)(iii) § 60.113b(b)(5) § 60.113b(b)(6) § 60.113b(b)(6)(ii) § 60.113b(b)(6)(ii) § 60.116b(a) § 60.116b(c) § 60.116b(c) § 60.116b(e) § 60.116b(e) § 60.116b(e)(1)	§ 60.116b(c)	§ 60.115b(b)(1) [G]§ 60.115b(b)(2) § 60.115b(b)(4)
TBS00280	EU	R5112	voc	30 TAC Chapter 115, Storage of VOCs	§ 115.112(a)(1) § 115.112(a)(2) § 115.112(a)(2)(A) § 115.112(a)(2)(B) § 115.112(a)(2)(C) § 115.112(a)(2)(D) § 115.112(a)(2)(E) § 115.114(a)(1)(A)	Tanks shall not store VOC unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(7)	§ 115.114(a)(1)(B)
TBS00280	EU	60Kb	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)
TT1815	EU	R5112-04	VOC	30 TAC Chapter	§ 115.112(a)(1)	Tanks shall not store VOC	§ 115.114(a)(1)	§ 115.118(a)(3)	§ 115.114(a)(1)(B)

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				115, Storage of VOCs	§ 115.112(a)(2) § 115.112(a)(2)(A) § 115.112(a)(2)(B) § 115.112(a)(2)(C) § 115.112(a)(2)(D) § 115.112(a)(2)(E) § 115.114(a)(1)(A)	unless the required pressure is maintained, or they are equipped with the appropriate control device specified in Table I(a) or Table II(a).	§ 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(5) § 115.118(a)(7)	
TT1815	EU	60Kb-2	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(v) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)

Additional Monitoring Requirements	
Periodic Monitoring Summary	24

Periodic Monitoring Summary

Unit/Group/Process Information				
ID No.: GRPEFR1				
Control Device ID No.: N/A	Control Device Type: N/A			
Applicable Regulatory Requirement				
Name: 40 CFR Part 60, Subpart K	SOP Index No.: 60K			
Pollutant: VOC	Main Standard: § 60.112(a)(1)			
Monitoring Information				
Indicator: External Floating Roof				
Minimum Frequency: annually				
Averaging Period: N/A				

Deviation Limit: Roof is not floating on the surface of the VOC or liquid has accumulated on the external floating roof or the seals are detached or there are holes or tears in the seal fabric.

Periodic Monitoring Text: Visually inspect and record the inspection of the external floating roof to ensure: the roof is floating on the surface of the VOC and not on the leg supports, liquid has not accumulated on the external floating roof, the seals are not detached, and there are no holes or tears in the seal fabric. Any monitoring data in which the roof is not floating on the surface of the VOC, if liquid has accumulated on the external floating roof, the seals are detached, or if there are holes or tears in the seal fabric shall be considered and reported as a deviation.

	Permit Shield
Permit Shield	

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit / Group / Process ID No.	Group / Inclusive Units	Regulation	Basis of Determination
FPH3	N/A	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	The site is not a petroleum refinery; a synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process; or a natural gas/gasoline processing operation.
FPH3	N/A	40 CFR Part 63, Subpart CC	The fugitive components are not located at a plant site that is a major source as defined in section 112(a) of the Clean Air Act.
GRPDETK	ENG1DTK, ENG2DTK, ENG3DTK	40 CFR Part 60, Subpart Kb	The tanks have capacities less than 75 cubic meters.
GRPEFR1	TET00278, TET00279, TST00275	40 CFR Part 63, Subpart CC	The tanks are not located at a plant site that is a major source as defined in section 112(a) of the Clean Air Act.
GRPEFR1	TET00278, TET00279, TST00275	40 CFR Part 63, Subpart EEEE	The tanks are not part of an OLD operation that is located at, or is part of, a major source of HAP emissions.
GRPEFR2	340-1, 340-2, 600-1, PNT1, PNT2, PNT3, TDC01834, TDC01835	40 CFR Part 63, Subpart CC	The tank is not located at a plant site that is a major source as defined in section 112(a) of the Clean Air Act.
GRPFXR1	TST00142, TST00143, TST00176	40 CFR Part 60, Subpart K	Constructed on or before 6/11/1973.
GRPFXR1	TST00142, TST00143, TST00176	40 CFR Part 63, Subpart CC	The tanks are not located at a plant site that is a major source as defined in section 112(a) of the Clean Air Act.
GRPFXR1	TST00142, TST00143, TST00176	40 CFR Part 63, Subpart EEEE	The tanks are not part of an OLD operation that is located at, or is part of, a major source of HAP emissions.
GRPMLR	BERTH2, BERTH3	30 TAC Chapter 115, Loading and Unloading of VOC	All marine loading/unloading in ozone nonattainment areas other than HGB are

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit / Group / Process ID No.	Group / Inclusive Units	Regulation	Basis of Determination
			exempt from requirements of this Division.
GRPMLR	BERTH2, BERTH3	40 CFR Part 63, Subpart Y	The true vapor pressure of the product at marine tank vessel loading is less than 1.5 psia at standard conditions.
MVLOAD	N/A	30 TAC Chapter 115, Loading and Unloading of VOC	The loading and unloading operation is considered part of a motor vehicle fuel dispensing facility, as defined in §101.1.
PU2097	N/A	30 TAC Chapter 117, Subchapter B	The site is not a major source of NOx emissions.
PU2097	N/A	40 CFR Part 60, Subpart IIII	The stationary combustion ignition ICE is a fire water pump that was installed prior to July 11, 2005 and has not been modified.
PU2098	N/A	30 TAC Chapter 117, Subchapter B	The site is not a major source of NOx emissions.
PU2098	N/A	40 CFR Part 60, Subpart IIII	The stationary combustion ignition ICE is a fire water pump that was installed prior to July 11, 2005 and has not been modified.
SITELOAD	N/A	30 TAC Chapter 115, Loading and Unloading of VOC	Vacuum truck loading and unloading for maintenance and spill response is the only transport vessel loading and unloading activities conducted in the application area, which does not meet the definition of transport vessel in 115.10(46).
T-DIESEL	N/A	30 TAC Chapter 115, Storage of VOCs	Storage vessel has a capacity of less than 1000 gallons.
T-DIESEL	N/A	40 CFR Part 60, Subpart Kb	Storage vessel has a capacity of less than 75 cubic meters (19,800 gallons).
TBS00280	N/A	40 CFR Part 63, Subpart CC	The tank is not located at a plant site that is a

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit / Group / Process ID No.	Group / Inclusive Units	Regulation	Basis of Determination
			major source as defined in section 112(a) of the Clean Air Act.
TBS00280	N/A	40 CFR Part 63, Subpart EEEE	The tank is not part of an OLD operation that is located at, or is part of, a major source of HAP emissions.
TOTETANKS	N/A	30 TAC Chapter 115, Storage of VOCs	Tank capacity less than 1,000 gallons.
TST01871	N/A	30 TAC Chapter 115, Storage of VOCs	Tank capacity less than 25,000 gallons located at a motor vehicle fuel dispensing facility.
TST01871	N/A	40 CFR Part 60, Subpart Kb	Tank capacity less than 19,800 gallons.
TST01872	N/A	30 TAC Chapter 115, Storage of VOCs	Tank capacity less than 25,000 gallons located at a motor vehicle fuel dispensing facility.
TST01872	N/A	40 CFR Part 60, Subpart Kb	Tank capacity less than 19,800 gallons.

New Source Review Authorization References

New Source Review Authorization References	30
New Source Review Authorization References by Emission Unit	31

New Source Review Authorization References

The New Source Review authorizations listed in the table below are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Title 30 TAC Chapter 116 Permits, Special Permits, and Other Authorizations (Other Than Permits By Rule, PSD Permits, or NA Permits) for the Application Area.				
Authorization No.: 148259	Issuance Date: 10/04/2024			
Permits By Rule (30 TAC Chapter 106) for the	Application Area			
Number: 5	Version No./Date: 08/30/1988			
Number: 14	Version No./Date: 07/20/1992			
Number: 54	Version No./Date: 08/30/1988			
Number: 61	Version No./Date: 09/12/1989			
Number: 86	Version No./Date: 09/12/1989			
Number: 86	Version No./Date: 07/20/1992			
Number: 86	Version No./Date: 05/04/1994			
Number: 106	Version No./Date: 09/12/1989			
Number: 106	Version No./Date: 07/20/1992			
Number: 106.261	Version No./Date: 09/04/2000			
Number: 106.261	Version No./Date: 11/01/2003			
Number: 106.262	Version No./Date: 11/01/2003			
Number: 106.263	Version No./Date: 11/01/2001			
Number: 106.264	Version No./Date: 09/04/2000			
Number: 106.265	Version No./Date: 09/04/2000			
Number: 106.371	Version No./Date: 09/04/2000			
Number: 106.373	Version No./Date: 09/04/2000			
Number: 106.452	Version No./Date: 09/04/2000			
Number: 106.454	Version No./Date: 11/01/2001			
Number: 106.472	Version No./Date: 09/04/2000			
Number: 106.473	Version No./Date: 09/04/2000			
Number: 106.478	Version No./Date: 09/04/2000			
Number: 106.511	Version No./Date: 09/04/2000			

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization**
340-1	TANK 340-1	106.263/11/01/2001, 106.478/09/04/2000
340-2	TANK 340-2	106.263/11/01/2001, 106.478/09/04/2000
600-1	TANK 600-1	106.263/11/01/2001, 106.478/09/04/2000
BERTH2	LOADING BERTH 2	106/07/20/1992
BERTH3	LOADING BERTH 3	106/07/20/1992
ENG1DTK	DIESEL TANK FOR FIREPUMP ENGINE #1	106.472/09/04/2000
ENG2DTK	DIESEL TANK FOR FIREPUMP ENGINE #2	106.472/09/04/2000
ENG3DTK	DIESEL TANK FOR FIREPUMP ENGINE #3	106.472/09/04/2000
ENGINE3	FIREPUMP ENGINE #3	106.511/09/04/2000
FPH3	PUMPHOUSE NO. 3 FUGITIVES	106.261/09/04/2000
GEN-1	EMERGENCY GENERATOR #1	106.511/09/04/2000
LOUT34030	TANK 34030	148259
MVLOAD	MOTOR VEHICLE FUEL LOADING & UNLOADING FACILITIES	14/07/20/1992
PNT1	NEW CRUDE TANK 1	106.478/09/04/2000 [154083]
PNT2	NEW CRUDE TANK 1	106.478/09/04/2000 [154083]
PNT3	NEW CRUDE TANK 1	106.478/09/04/2000 [154083]
PU2097	DIESEL ENGINE	5/08/30/1988
PU2098	DIESEL ENGINE	5/08/30/1988
SITELOAD	SITE LOADING AND UNLOADING	106.472/09/04/2000, 106.473/09/04/2000
T-DIESEL	766 GALLON DIESEL STORAGE TANK	106.472/09/04/2000
TBS00280	INTERNAL FLOATING ROOF TANK	106.478/09/04/2000

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization**
TDC01834	EXTERNAL FLOATING ROOF TANK	86/09/12/1989
TDC01835	EXTERNAL FLOATING ROOF TANK	86/09/12/1989
TET00278	EXTERNAL FLOATING ROOF TANK	86/09/12/1989
TET00279	EXTERNAL FLOATING ROOF TANK	86/09/12/1989
TOTETANKS	MISCELLANEOUS TOTE TANKS	106.472/09/04/2000, 106.473/09/04/2000
TST00142	FIXED ROOF TANK	86/07/20/1992
TST00143	FIXED ROOF TANK	86/05/04/1994
TST00176	FIXED ROOF TANK	86/07/20/1992
TST00275	EXTERNAL FLOATING ROOF TANK	86/07/20/1992
TST01871	FIXED ROOF TANK	14/07/20/1992
TST01872	FIXED ROOF TANK	14/07/20/1992
TT1815	TANK 1815	148259

^{**}This column may include Permit by Rule (PBR) numbers and version dates, PBR Registration numbers in brackets, Standard Permit Registration numbers, Minor NSR permit numbers, and Major NSR permit numbers.

Appendix A	
Acronym List	34

Acronym List

The following abbreviations or acronyms may be used in this permit:

	actual aubia fact per minute
	actual cubic feet per minute
	alternate means of control
	Acid Rain Program
	American Society of Testing and Materials
B/PA	Beaumont/Port Arthur (nonattainment area)
	control device
	continuous opacity monitoring system
CVS	closed vent system
D/FW	
FP	emission point
	U.S. Environmental Protection Agency
	emission unit
EU	ernission unit
	federal operating permit
gr/100 scf	grains per 100 standard cubic feet
HAP	hazardous air pollutant
	hydrogen sulfide
	identification number
	pound(s) per hour
MΔCT	Maximum Achievable Control Technology (40 CFR Part 63)
	Million British thermal units per hour
MMBtu/hr	
MMBtu/hrNA	
MMBtu/hr NA N/A	
MMBtu/hr NA N/A NADB	
MMBtu/hrNAN/ANADBNESHAP	
MMBtu/hrNAN/ANADBNESHAPNOx	
MMBtu/hr	Million British thermal units per hour nonattainment not applicable National Allowance Data Base National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) nitrogen oxides New Source Performance Standard (40 CFR Part 60) New Source Review Office of Regulatory Information Systems lead Permit By Rule Permit By Rule predictive emissions monitoring system particulate matter parts per million by volume process unit process unit prevention of significant deterioration pounds per square inch absolute state implementation plan
MMBtu/hr	Million British thermal units per hour nonattainment not applicable National Allowance Data Base National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) New Source Performance Standard (40 CFR Part 60) New Source Review Office of Regulatory Information Systems lead Permit By Rule Permit By Rule predictive emissions monitoring system particulate matter parts per million by volume process unit process unit prevention of significant deterioration pounds per square inch absolute state implementation plan sulfur dioxide
MMBtu/hr NA N/A N/A NADB NESHAP NOx NSPS NSR ORIS Pb PBR PEMS PEMS PM ppmv PRO PSD psia SIP SO2 TCEQ	Million British thermal units per hour nonattainment not applicable National Allowance Data Base National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) nitrogen oxides New Source Performance Standard (40 CFR Part 60) New Source Review Office of Regulatory Information Systems lead Permit By Rule predictive emissions monitoring system particulate matter parts per million by volume process unit prevention of significant deterioration pounds per square inch absolute state implementation plan sulfur dioxide Texas Commission on Environmental Quality
MMBtu/hr NA N/A N/A NADB NESHAP NOx NSPS NSR ORIS Pb PBR PEMS PM ppmv PRO PSD psia SIP SO2 TCEQ TSP	Million British thermal units per hour nonattainment not applicable National Allowance Data Base National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) nitrogen oxides New Source Performance Standard (40 CFR Part 60) New Source Review Office of Regulatory Information Systems lead Permit By Rule predictive emissions monitoring system particulate matter parts per million by volume process unit prevention of significant deterioration pounds per square inch absolute state implementation plan sulfur dioxide Texas Commission on Environmental Quality total suspended particulate
MMBtu/hr NA N/A N/A NADB NESHAP NOx NSPS NSR ORIS Pb PBR PEMS PBM PPM ppmv PRO PSD psia SIP SO2 TCEQ TSP TVP	Million British thermal units per hour nonattainment not applicable National Allowance Data Base National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) nitrogen oxides New Source Performance Standard (40 CFR Part 60) New Source Review Office of Regulatory Information Systems lead Permit By Rule Permit By Rule predictive emissions monitoring system particulate matter parts per million by volume process unit prevention of significant deterioration pounds per square inch absolute state implementation plan sulfur dioxide Texas Commission on Environmental Quality total suspended particulate true vapor pressure
MMBtu/hr NA N/A N/A NADB NESHAP NO _x NSPS NSR ORIS Pb PBR PEMS PM ppmv PRO PSD psia SIP SO ₂ TCEQ TSP TVP U.S.C.	Million British thermal units per hour nonattainment not applicable National Allowance Data Base National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) nitrogen oxides New Source Performance Standard (40 CFR Part 60) New Source Review Office of Regulatory Information Systems lead Permit By Rule predictive emissions monitoring system particulate matter parts per million by volume process unit provention of significant deterioration punds per square inch absolute state implementation plan sulfur dioxide Texas Commission on Environmental Quality total suspended particulate true vapor pressure United States Code
MMBtu/hr NA N/A N/A NADB NESHAP NO _x NSPS NSR ORIS Pb PBR PEMS PM ppmv PRO PSD psia SIP SO ₂ TCEQ TSP TVP U.S.C.	Million British thermal units per hour nonattainment not applicable National Allowance Data Base National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61) nitrogen oxides New Source Performance Standard (40 CFR Part 60) New Source Review Office of Regulatory Information Systems lead Permit By Rule Permit By Rule predictive emissions monitoring system particulate matter parts per million by volume process unit prevention of significant deterioration pounds per square inch absolute state implementation plan sulfur dioxide Texas Commission on Environmental Quality total suspended particulate true vapor pressure