

FEDERAL OPERATING PERMIT

A FEDERAL OPERATING PERMIT IS HEREBY ISSUED TO
ExxonMobil Pipeline Company LLC

AUTHORIZING THE OPERATION OF
ExxonMobil North Houston Terminal
Petroleum Bulk Stations and Terminals

LOCATED AT
Harris County, Texas
Latitude 29° 53' 11" Longitude 95° 24' 39"
Regulated Entity Number: RN100212745


This permit is issued in accordance with and subject to the Texas Clean Air Act (TCAA), Chapter 382 of the Texas Health and Safety Code and Title 30 Texas Administrative Code Chapter 122 (30 TAC Chapter 122), Federal Operating Permits. Under 30 TAC Chapter 122, this permit constitutes the permit holder's authority to operate the site and emission units listed in this permit. Operations of the site and emission units listed in this permit are subject to all additional rules or amended rules and orders of the Commission pursuant to the TCAA.

This permit does not relieve the permit holder from the responsibility of obtaining New Source Review authorization for new, modified, or existing facilities in accordance with 30 TAC Chapter 116, Control of Air Pollution by Permits for New Construction or Modification.

The site and emission units authorized by this permit shall be operated in accordance with 30 TAC Chapter 122, the general terms and conditions, special terms and conditions, and attachments contained herein.

This permit shall expire five years from the date of issuance. The renewal requirements specified in 30 TAC § 122.241 must be satisfied in order to renew the authorization to operate the site and emission units.

Permit No: 03022 Issuance Date: March 25, 2026



For the Commission

Table of Contents

Section	Page
General Terms and Conditions	1
Special Terms and Conditions:	1
Emission Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting.....	1
Additional Monitoring Requirements	5
New Source Review Authorization Requirements	6
Compliance Requirements.....	6
Protection of Stratospheric Ozone	8
Permit Location	8
Permit Shield (30 TAC § 122.148)	8
Attachments	9
Applicable Requirements Summary.....	10
Additional Monitoring Requirements	27
Permit Shield.....	40
New Source Review Authorization References	43
Appendix A.....	47
Acronym List	48

General Terms and Conditions

The permit holder shall comply with all terms and conditions contained in 30 TAC § 122.143 (General Terms and Conditions), 30 TAC § 122.144 (Recordkeeping Terms and Conditions), 30 TAC § 122.145 (Reporting Terms and Conditions), and 30 TAC § 122.146 (Compliance Certification Terms and Conditions).

In accordance with 30 TAC § 122.144(1), records of required monitoring data and support information required by this permit, or any applicable requirement codified in this permit, are required to be maintained for a period of five years from the date of the monitoring report, sample, or application unless a longer data retention period is specified in an applicable requirement. The five year record retention period supersedes any less stringent retention requirement that may be specified in a condition of a permit identified in the New Source Review Authorization attachment.

If the permit holder chooses to demonstrate that this permit is no longer required, a written request to void this permit shall be submitted to the Texas Commission on Environmental Quality (TCEQ) by the Responsible Official in accordance with 30 TAC § 122.161(e). The permit holder shall comply with the permit's requirements, including compliance certification and deviation reporting, until notified by the TCEQ that this permit is voided.

The permit holder shall comply with 30 TAC Chapter 116 by obtaining a New Source Review authorization prior to new construction or modification of emission units located in the area covered by this permit.

All reports required by this permit must include in the submittal a cover letter which identifies the following information: company name, TCEQ regulated entity number, air account number (if assigned), site name, area name (if applicable), and Air Permits Division permit number(s).

Special Terms and Conditions:

Emission Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting

1. Permit holder shall comply with the following requirements:
 - A. Emission units (including groups and processes) in the Applicable Requirements Summary attachment shall meet the limitations, standards, equipment specifications, monitoring, recordkeeping, reporting, testing, and other requirements listed in the Applicable Requirements Summary attachment to assure compliance with the permit.
 - B. The textual description in the column titled "Textual Description" in the Applicable Requirements Summary attachment is not enforceable and is not deemed as a substitute for the actual regulatory language. The Textual Description is provided for information purposes only.
 - C. A citation listed on the Applicable Requirements Summary attachment, which has a notation [G] listed before it, shall include the referenced section and subsection for all commission rules, or paragraphs for all federal and state regulations and all subordinate paragraphs, subparagraphs and clauses, subclauses, and items contained within the referenced citation as applicable requirements.
 - D. When a grouped citation, notated with a [G] in the Applicable Requirements Summary, contains multiple compliance options, the permit holder must keep records of when each compliance option was used.
 - E. Emission units subject to 40 CFR Part 63, Subpart ZZZZ or BBBB as identified in the attached Applicable Requirements Summary table are subject to 30 TAC Chapter 113,

Subchapter C, § 113.1090 or § 113.1370 which incorporate the 40 CFR Part 63 Subparts by reference.

2. The permit holder shall comply with the following sections of 30 TAC Chapter 101 (General Air Quality Rules):
 - A. Title 30 TAC § 101.1 (relating to Definitions), insofar as the terms defined in this section are used to define the terms used in other applicable requirements
 - B. Title 30 TAC § 101.3 (relating to Circumvention)
 - C. Title 30 TAC § 101.8 (relating to Sampling), if such action has been requested by the TCEQ
 - D. Title 30 TAC § 101.9 (relating to Sampling Ports), if such action has been requested by the TCEQ
 - E. Title 30 TAC § 101.10 (relating to Emissions Inventory Requirements)
 - F. Title 30 TAC § 101.201 (relating to Emission Event Reporting and Recordkeeping Requirements)
 - G. Title 30 TAC § 101.211 (relating to Scheduled Maintenance, Start-up, and Shutdown Reporting and Recordkeeping Requirements)
 - H. Title 30 TAC § 101.221 (relating to Operational Requirements)
 - I. Title 30 TAC § 101.222 (relating to Demonstrations)
 - J. Title 30 TAC § 101.223 (relating to Actions to Reduce Excessive Emissions)
3. Permit holder shall comply with the following requirements of 30 TAC Chapter 111:
 - A. Permit holders for sites that have materials handling, construction, roads, streets, alleys, and parking lots shall comply with the following requirements:
 - (i) Title 30 TAC § 111.143 (relating to Materials Handling)
 - (ii) Title 30 TAC § 111.145 (relating to Construction and Demolition)
 - (iii) Title 30 TAC § 111.147 (relating to Roads, Streets, and Alleys)
 - (iv) Title 30 TAC § 111.149 (relating to Parking Lots)
 - B. Emission limits on nonagricultural processes, except for the steam generators specified in 30 TAC § 111.153, shall comply with the following requirements:
 - (i) Emissions of PM from any source may not exceed the allowable rates as required in 30 TAC § 111.151(a) (relating to Allowable Emissions Limits)
 - (ii) Sources with an effective stack height (h_e) less than the standard effective stack height (H_e), must reduce the allowable emission level by multiplying it by $[h_e/H_e]^2$ as required in 30 TAC § 111.151(b)

- (iii) Effective stack height shall be calculated by the equation specified in 30 TAC § 111.151(c)
4. The permit holder shall comply with the following requirements of 30 TAC Chapter 115, Subchapter F, Division 3, Degassing of Storage Tanks, Transport Vessels and Marine Vessels:
- A. For degassing of stationary VOC storage tanks, the permit holder shall comply with the following requirements:
 - (i) Title 30 TAC § 115.541(a) - (c) (relating to Emission Specifications)
 - (ii) Title 30 TAC § 115.541(f) (relating to Emission Specifications), for floating roof storage tanks
 - (iii) Title 30 TAC § 115.542(a) and (a)(1), (a)(2), (a)(3) or (a)(4) (relating to Control Requirements). Where the requirements of 30 TAC Chapter 115, Subchapter F contain multiple compliance options, the permit holder shall keep records of when each compliance option was used.
 - (iv) Title 30 TAC § 115.542(b) - (d), (relating to Control Requirements)
 - (v) Title 30 TAC § 115.543 (relating to Alternate Control Requirements)
 - (vi) Title 30 TAC § 115.544(a)(1) and (a)(2) (relating to Inspection, Monitoring, and Testing Requirements), for inspections
 - (vii) Title 30 TAC § 115.544(b) (relating to Inspection, Monitoring, and Testing Requirements), for monitoring
 - (viii) Title 30 TAC § 115.544(b)(1) and (b)(2) (relating to Inspection, Monitoring, and Testing Requirements), for monitoring of control devices
 - (ix) Title 30 TAC § 115.544(b)(2)(A) - (J) (relating to Inspection, Monitoring, and Testing Requirements), for monitoring (as appropriate to the control device)
 - (x) Title 30 TAC § 115.544(b)(3), (b)(4) and (b)(6) (relating to Inspection, Monitoring, and Testing Requirements), for VOC concentration or lower explosive limit threshold monitoring
 - (xi) Title 30 TAC § 115.544(c), and (c)(1) - (c)(3) (relating to Inspection, Monitoring, and Testing Requirements), for testing of control devices used to comply with 30 TAC § 115.542(a)(1)
 - (xii) Title 30 TAC § 115.545(1) - (7), (9) - (11) and (13) (relating to Approved Test Methods)
 - (xiii) Title 30 TAC § 115.546(a), (a)(1) and (a)(3) (relating to Recordkeeping and Notification Requirements), for recordkeeping
 - (xiv) Title 30 TAC § 115.546(a)(2) and (a)(2)(A) - (J) (relating to Recordkeeping and Notification Requirements), for recordkeeping (as appropriate to the control device)

- (xv) Title 30 TAC § 115.546(a)(4) (relating to Recordkeeping and Notification Requirements), for recordkeeping of testing of control devices used to comply with 30 TAC § 115.542(a)(1)
 - (xvi) Title 30 TAC § 115.546(b) (relating to Recordkeeping and Notification Requirements), for notification
 - (xvii) Title 30 TAC § 115.547(4) (relating to Exemptions)
5. The permit holder shall comply with the following requirements for units subject to any subpart of 40 CFR Part 60, unless otherwise stated in the applicable subpart:
- A. Title 40 CFR § 60.7 (relating to Notification and Recordkeeping)
 - B. Title 40 CFR § 60.8 (relating to Performance Tests)
 - C. Title 40 CFR § 60.11 (relating to Compliance with Standards and Maintenance Requirements)
 - D. Title 40 CFR § 60.12 (relating to Circumvention)
 - E. Title 40 CFR § 60.13 (relating to Monitoring Requirements)
 - F. Title 40 CFR § 60.14 (relating to Modification)
 - G. Title 40 CFR § 60.15 (relating to Reconstruction)
 - H. Title 40 CFR § 60.19 (relating to General Notification and Reporting Requirements)
6. For the bulk gasoline terminals specified in 40 CFR Part 60, Subpart XX, the permit holder shall comply with the following requirements:
- A. Title 40 CFR § 60.502(e) - (f) (relating to Standard for VOC Emissions from Bulk Gasoline Terminals)
 - B. Title 40 CFR § 60.505(a) - (b), and (d) (relating to Reporting and Recordkeeping)
7. The permit holder shall comply with the requirements of 30 TAC Chapter 113, Subchapter C, § 113.100 for units subject to any subpart of 40 CFR Part 63, unless otherwise stated in the applicable subpart.
8. For each bulk gasoline terminal specified in 40 CFR Part 63, SubpartBBBBB, the permit holder shall comply with the following requirements (Title 30 TAC, Subchapter C, § 113.1370 incorporated by reference):
- A. Title 40 CFR § 60.502(e) - (f), as required by Title 40 CFR § 63.11088(a)
 - B. Title 40 CFR § 63.11085(a), for operation and maintenance of the affected source
 - C. Title 40 CFR § 63.11089(a), for leak inspections at the facility
 - D. Title 40 CFR § 63.11089(b) and (c), for log book maintenance and recordkeeping
 - E. Title 40 CFR § 63.11089(d), for delay of repair

- F. Title 40 CFR § 63.11092(f) and (f)(1), for annual certification of gasoline cargo tanks
- G. Title 40 CFR § 63.11093(a), for Initial Notification
- H. Title 40 CFR § 63.11093(b), for Notification of Compliance Status
- I. Title 40 CFR § 63.11094(d), for recordkeeping
- J. Title 40 CFR § 63.11094(e), for recordkeeping
- K. Title 40 CFR § 63.11094(g), for recordkeeping
- L. Title 40 CFR § 63.11095(a), (a)(3), (b), (b)(5) and (d), for reporting

Additional Monitoring Requirements

9. Unless otherwise specified, the permit holder shall comply with the compliance assurance monitoring requirements as specified in the attached “CAM Summary” upon issuance of the permit. In addition, the permit holder shall comply with the following:
 - A. The permit holder shall comply with the terms and conditions contained in 30 TAC § 122.147 (General Terms and Conditions for Compliance Assurance Monitoring).
 - B. The permit holder shall report, consistent with the averaging time identified in the “CAM Summary,” deviations as defined by the deviation limit in the “CAM Summary.” Any monitoring data above a maximum limit, that is collected in accordance with the requirements specified in 40 CFR § 64.7(c), shall be reported as a deviation. Deviations shall be reported according to 30 TAC § 122.145 (Reporting Terms and Conditions).
 - C. The permit holder may elect to collect monitoring data on a more frequent basis and average the data, consistent with the averaging time or minimum frequency specified in the “CAM Summary,” for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis. In no event shall data be collected and used in particular instances in order to avoid reporting deviations. All monitoring data shall be collected in accordance with the requirements specified in 40 CFR § 64.7(c).
 - D. The permit holder shall operate the monitoring, identified in the attached “CAM Summary,” in accordance with the provisions of 40 CFR § 64.7.
 - E. The permit holder shall comply with the requirements of 40 CFR § 70.6(a)(3)(ii)(A) and 30 TAC § 122.144(1)(A)-(F) for documentation of all required inspections.
10. The permit holder shall comply with the periodic monitoring requirements as specified in the attached “Periodic Monitoring Summary” upon issuance of the permit. Except for, as applicable, monitoring malfunctions, associated repairs, and required quality assurance or control activities (including, as applicable, calibration checks and required zero and span adjustments), the permit holder shall conduct all monitoring in continuous operation (or shall collect data at all required intervals) at all times that the pollutant-specific emissions unit is operating. The permit holder may elect to collect monitoring data on a more frequent basis and average the data, consistent with the averaging time or minimum frequency specified in the “Periodic Monitoring Summary,” for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis. In no event shall data be collected and used in particular

instances to avoid reporting deviations. Deviations shall be reported according to 30 TAC § 122.145 (Reporting Terms and Conditions).

New Source Review Authorization Requirements

11. Permit holder shall comply with the requirements of New Source Review authorizations issued or claimed by the permit holder for the permitted area, including permits, permits by rule (including the terms, conditions, monitoring, recordkeeping, and reporting identified in registered PBRs and permits by rule identified in the PBR Supplemental Tables dated September 11, 2025 in the application for project 37595), standard permits, flexible permits, special permits, permits for existing facilities including Voluntary Emissions Reduction Permits and Electric Generating Facility Permits issued under 30 TAC Chapter 116, Subchapter I, or special exemptions referenced in the New Source Review Authorization References attachment. These requirements:
 - A. Are incorporated by reference into this permit as applicable requirements
 - B. Shall be located with this operating permit
 - C. Are not eligible for a permit shield
12. The permit holder shall comply with the general requirements of 30 TAC Chapter 106, Subchapter A or the general requirements, if any, in effect at the time of the claim of any PBR.
13. The permit holder shall maintain records to demonstrate compliance with any emission limitation or standard that is specified in a permit by rule (PBR) or Standard Permit listed in the New Source Review Authorizations attachment. The records shall yield reliable data from the relevant time period that are representative of the emission unit's compliance with the PBR or Standard Permit. These records may include, but are not limited to, production capacity and throughput, hours of operation, safety data sheets (SDS), chemical composition of raw materials, speciation of air contaminant data, engineering calculations, maintenance records, fugitive data, performance tests, capture/control device efficiencies, direct pollutant monitoring (CEMS, COMS, or PEMS), or control device parametric monitoring. These records shall be made readily accessible and available as required by 30 TAC § 122.144. Any monitoring or recordkeeping data indicating noncompliance with the PBR or Standard Permit shall be considered and reported as a deviation according to 30 TAC § 122.145 (Reporting Terms and Conditions).
14. The permit holder shall comply with the following requirements for Air Quality Standard Permits:
 - A. Registration requirements listed in 30 TAC § 116.611, unless otherwise provided for in an Air Quality Standard Permit
 - B. General Conditions listed in 30 TAC § 116.615, unless otherwise provided for in an Air Quality Standard Permit
 - C. Requirements of the non-rule Air Quality Standard Permit for Pollution Control Projects

Compliance Requirements

15. The permit holder shall certify compliance in accordance with 30 TAC § 122.146. The permit holder shall comply with 30 TAC § 122.146 using at a minimum, but not limited to, the continuous or intermittent compliance method data from monitoring, recordkeeping, reporting, or testing required by the permit and any other credible evidence or information. The certification period may not exceed 12 months and the certification must be submitted within 30 days after the end of the period being certified.

16. Use of Emission Credits to comply with applicable requirements:
- A. Unless otherwise prohibited, the permit holder may use emission credits to comply with the following applicable requirements listed elsewhere in this permit:
 - (i) Title 30 TAC Chapter 115
 - (ii) Title 30 TAC Chapter 117
 - (iii) Offsets for Title 30 TAC Chapter 116
 - B. The permit holder shall comply with the following requirements in order to use the emission credits to comply with the applicable requirements:
 - (i) The permit holder must notify the TCEQ according to 30 TAC § 101.306(c)-(d)
 - (ii) The emission credits to be used must meet all the geographic, timeliness, applicable pollutant type, and availability requirements listed in 30 TAC Chapter 101, Subchapter H, Division 1
 - (iii) The executive director has approved the use of the credit according to 30 TAC § 101.306(c)-(d)
 - (iv) The permit holder keeps records of the use of credits towards compliance with the applicable requirements in accordance with 30 TAC § 101.302(g) and 30 TAC Chapter 122
 - (v) Title 30 TAC § 101.305 (relating to Emission Reductions Achieved Outside the United States)
17. Use of Discrete Emission Credits to comply with the applicable requirements:
- A. Unless otherwise prohibited, the permit holder may use discrete emission credits to comply with the following applicable requirements listed elsewhere in this permit:
 - (i) Title 30 TAC Chapter 115
 - (ii) Title 30 TAC Chapter 117
 - (iii) If applicable, offsets for Title 30 TAC Chapter 116
 - (iv) Temporarily exceed state NSR permit allowables
 - B. The permit holder shall comply with the following requirements in order to use the credit to comply with the applicable requirements:
 - (i) The permit holder must notify the TCEQ according to 30 TAC § 101.376(d)
 - (ii) The discrete emission credits to be used must meet all the geographic, timeliness, applicable pollutant type, and availability requirements listed in 30 TAC Chapter 101, Subchapter H, Division 4
 - (iii) The executive director has approved the use of the discrete emission credits according to 30 TAC § 101.376(d)(1)(A)

- (iv) The permit holder keeps records of the use of credits towards compliance with the applicable requirements in accordance with 30 TAC § 101.372(h) and 30 TAC Chapter 122
- (v) Title 30 TAC § 101.375 (relating to Emission Reductions Achieved Outside the United States)

Protection of Stratospheric Ozone

- 18. Permit holders at a site subject to Title VI of the FCAA Amendments shall meet the following requirements for protection of stratospheric ozone:
 - A. Any on site servicing, maintenance, and repair on refrigeration and nonmotor vehicle air-conditioning appliances using ozone-depleting refrigerants or non-exempt substitutes shall be conducted in accordance with 40 CFR Part 82, Subpart F. Permit holders shall ensure that repairs on or refrigerant removal from refrigeration and nonmotor vehicle air-conditioning appliances using ozone-depleting refrigerants are performed only by properly certified technicians using certified equipment. Records shall be maintained as required by 40 CFR Part 82, Subpart F.

Permit Location

- 19. The permit holder shall maintain a copy of this permit and records related to requirements listed in this permit on site.

Permit Shield (30 TAC § 122.148)

- 20. A permit shield is granted for the emission units, groups, or processes specified in the attached "Permit Shield." Compliance with the conditions of the permit shall be deemed compliance with the specified potentially applicable requirements or specified potentially applicable state-only requirements listed in the attachment "Permit Shield." Permit shield provisions shall not be modified by the executive director until notification is provided to the permit holder. No later than 90 days after notification of a change in a determination made by the executive director, the permit holder shall apply for the appropriate permit revision to reflect the new determination. Provisional terms are not eligible for this permit shield. Any term or condition, under a permit shield, shall not be protected by the permit shield if it is replaced by a provisional term or condition or the basis of the term and condition changes.

Attachments

Applicable Requirements Summary

Additional Monitoring Requirements

Permit Shield

New Source Review Authorization References

Applicable Requirements Summary

Unit Summary	11
Applicable Requirements Summary	14

Note: A “none” entry may be noted for some emission sources in this permit’s “Applicable Requirements Summary” under the heading of “Monitoring and Testing Requirements” and/or “Recordkeeping Requirements” and/or “Reporting Requirements.” Such a notation indicates that there are no requirements for the indicated emission source as identified under the respective column heading(s) for the stated portion of the regulation when the emission source is operating under the conditions of the specified SOP Index Number. However, other relevant requirements pursuant to 30 TAC Chapter 122 including Recordkeeping Terms and Conditions (30 TAC § 122.144), Reporting Terms and Conditions (30 TAC § 122.145), and Compliance Certification Terms and Conditions (30 TAC § 122.146) continue to apply.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
GEN	SRIC ENGINES	N/A	60JJJJ	40 CFR Part 60, Subpart JJJJ	No changing attributes.
GEN	SRIC ENGINES	N/A	63ZZZZ	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
GRP ADD	STORAGE TANKS/VESSELS	T-4011, T-4014, T- 4015, T-4016, T- 4017, T-430	R5112-ADD	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
GRP VENT	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	LR-6401, OWS, SUMP, T-100, T- 4011, T-4012, T- 4014, T-4015, T- 4016, T-4017, T- 430, T-688, T-689, T-690, T-691, T- DRAIN, T-REM	R111-VENT	30 TAC Chapter 111, Visible Emissions	No changing attributes.
LR-6401	LOADING/UNLOADING OPERATIONS	N/A	R5211-VCU	30 TAC Chapter 115, Loading and Unloading of VOC	Chapter 115 Control Device Type = Vapor control system with a vapor combustor that is not considered to be a flare
LR-6401	LOADING/UNLOADING OPERATIONS	N/A	R5211-VRU	30 TAC Chapter 115, Loading and Unloading of VOC	Chapter 115 Control Device Type = Vapor control system with a carbon adsorption system.
LR-6401	LOADING/UNLOADING OPERATIONS	N/A	60XX-VCU	40 CFR Part 60, Subpart XX	Vapor Processing System Type = Continuous combustion vapor processing system.
LR-6401	LOADING/UNLOADING OPERATIONS	N/A	60XX-VRU	40 CFR Part 60, Subpart XX	Vapor Processing System Type = Continuous non-combustion vapor processing system.
LR-6401	LOADING/UNLOADING OPERATIONS	N/A	63BBBBBB-LOAD	40 CFR Part 63, Subpart BBBBBB	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
SUMP	STORAGE TANKS/VESSELS	N/A	R5112-INT	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-100	STORAGE TANKS/VESSELS	N/A	R5112-INT	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-4012	STORAGE TANKS/VESSELS	N/A	R5112-INT	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T-4012	STORAGE TANKS/VESSELS	N/A	63BBBBBB-INT	40 CFR Part 63, Subpart BBBBBB	No changing attributes.
T-688	STORAGE TANKS/VESSELS	N/A	R5112-DSL	30 TAC Chapter 115, Storage of VOCs	True Vapor Pressure = True vapor pressure is less than 1.0 psia
T-688	STORAGE TANKS/VESSELS	N/A	R5112-GAS-IFR	30 TAC Chapter 115, Storage of VOCs	True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia
T-688	STORAGE TANKS/VESSELS	N/A	63BBBBBB- GASTK	40 CFR Part 63, Subpart BBBBBB	No changing attributes.
T-689	STORAGE TANKS/VESSELS	N/A	R5112-DSL	30 TAC Chapter 115, Storage of VOCs	True Vapor Pressure = True vapor pressure is less than 1.0 psia
T-689	STORAGE TANKS/VESSELS	N/A	R5112-GAS-IFR	30 TAC Chapter 115, Storage of VOCs	True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia
T-689	STORAGE TANKS/VESSELS	N/A	63BBBBBB- GASTK	40 CFR Part 63, Subpart BBBBBB	No changing attributes.
T-690	STORAGE TANKS/VESSELS	N/A	R5112-DSL	30 TAC Chapter 115, Storage of VOCs	True Vapor Pressure = True vapor pressure is less than 1.0 psia
T-690	STORAGE TANKS/VESSELS	N/A	R5112-GAS-IFR	30 TAC Chapter 115, Storage of VOCs	True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia
T-690	STORAGE	N/A	63BBBBBB-	40 CFR Part 63, Subpart	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	TANKS/VESSELS		GASTK	BBBBBB	
T-691	STORAGE TANKS/VESSELS	N/A	R5112-DSL	30 TAC Chapter 115, Storage of VOCs	True Vapor Pressure = True vapor pressure is less than 1.0 psia
T-691	STORAGE TANKS/VESSELS	N/A	R5112-GAS-IFR	30 TAC Chapter 115, Storage of VOCs	True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia
T-691	STORAGE TANKS/VESSELS	N/A	60Kb-ETH-IFR	40 CFR Part 60, Subpart Kb	Product Stored = Volatile organic liquid
T-691	STORAGE TANKS/VESSELS	N/A	60Kb-GAS-IFR	40 CFR Part 60, Subpart Kb	Product Stored = Petroleum liquid (other than petroleum or condensate)
T-691	STORAGE TANKS/VESSELS	N/A	63BBBBBB- GASTK	40 CFR Part 63, Subpart BBBBBB	No changing attributes.
T-DRAIN	STORAGE TANKS/VESSELS	N/A	R5112-INT	30 TAC Chapter 115, Storage of VOCs	No changing attributes.

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
GEN	EU	60JJJJ	CO	40 CFR Part 60, Subpart JJJJ	§ 60.4233(e)-Table 1 § 60.4234 § 60.4243(b) § 60.4243(b)(1) [G]§ 60.4243(d) § 60.4243(g)	Owners and operators of stationary emergency SI ICE with a maximum engine power greater than or equal to 130 HP and were manufactured on or after 01/01/2009 must comply with a CO emission limit of 4.0 g/HP-hr, as listed in Table 1 to this subpart.	§ 60.4237(b)	§ 60.4243(a)(1) § 60.4245(a) § 60.4245(a)(1) § 60.4245(a)(2) § 60.4245(a)(3) § 60.4245(b) § 60.4245(j)	[G]§ 60.4245(e) [G]§ 60.4245(g) [G]§ 60.4245(h) [G]§ 60.4245(i)
GEN	EU	60JJJJ	NO _x	40 CFR Part 60, Subpart JJJJ	§ 60.4233(e)-Table 1 § 60.4234 § 60.4243(b) § 60.4243(b)(1) [G]§ 60.4243(d) § 60.4243(g)	Owners and operators of stationary emergency SI ICE with a maximum engine power greater than or equal to 130 HP and were manufactured on or after 01/01/2009 must comply with a NO _x emission limit of 2.0 g/HP-hr, as listed in Table 1 to this subpart.	§ 60.4237(b)	§ 60.4243(a)(1) § 60.4245(a) § 60.4245(a)(1) § 60.4245(a)(2) § 60.4245(a)(3) § 60.4245(b) § 60.4245(j)	[G]§ 60.4245(e) [G]§ 60.4245(g) [G]§ 60.4245(h) [G]§ 60.4245(i)
GEN	EU	60JJJJ	VOC	40 CFR Part 60, Subpart JJJJ	§ 60.4233(e)-Table 1 § 60.4234 § 60.4243(b) § 60.4243(b)(1) [G]§ 60.4243(d) § 60.4243(g)	Owners and operators of stationary emergency SI ICE with a maximum engine power greater than or equal to 130 HP and were manufactured on or after 01/01/2009 must comply with a VOC emission limit of 1.0 g/HP-hr, as listed in Table 1 to this subpart.	§ 60.4237(b)	§ 60.4243(a)(1) § 60.4245(a) § 60.4245(a)(1) § 60.4245(a)(2) § 60.4245(a)(3) § 60.4245(b) § 60.4245(j)	[G]§ 60.4245(e) [G]§ 60.4245(g) [G]§ 60.4245(h) [G]§ 60.4245(i)
GEN	EU	63ZZZZ	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(c)	Stationary RICE subject to Regulations under 40 CFR Part 60. An affected source that meets any of the criteria in paragraphs (c)(1) through (7) of this section must meet the requirements of this part by meeting the	None	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						requirements of 40 CFR part 60 subpart IIII, for compression ignition engines or 40 CFR part 60 subpart JJJJ, for spark ignition engines as applicable. No further requirements apply for such engines under this part.			
GRP ADD	EU	R5112-ADD	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	§ 115.117(8)	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
GRP VENT	EP	R111-VENT	Opacity	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(1)(B)	Visible emissions from any stationary vent shall not exceed an opacity of 20% averaged over a six-minute period for any source on which construction was begun after January 31, 1972. The emissions from this vent originate from colorless VOCs, non-fuming liquids, or other sources that are not capable of obstructing the transmission of light. These vents are not capable of exceeding the opacity standards of 30 TAC Chapter 111 and therefore no monitoring is required to demonstrate compliance.	None	None	None
LR-6401	EU	R5211-VCU	VOC	30 TAC Chapter 115, Loading and	§ 115.211(1) § 115.212(a)(3)(A)	In the Beaumont-Port Arthur, Bexar County,	§ 115.212(a)(3)(B) § 115.212(a)(4)(C)	§ 115.216 § 115.216(1)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Unloading of VOC	§ 115.212(a)(3)(A)(i) § 115.212(a)(3)(B) [G] § 115.212(a)(3)(C) § 115.212(a)(3)(E) § 115.212(a)(4)(A) § 115.212(a)(4)(B) § 115.212(a)(4)(C) § 115.214(a)(1)(B) § 115.214(a)(1)(C)	Dallas-Fort Worth, El Paso, and Houston-Galveston-Brazoria areas, gasoline terminals shall ensure that VOC emissions do not exceed 0.09 pound per 1,000 gallons (10.8 mg/liter) of gasoline loaded into transport vessels.	§ 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.214(a)(1)(A)(ii) § 115.214(a)(1)(A)(iii) § 115.214(a)(2) § 115.215 § 115.215(1) § 115.215(10) [G]§ 115.215(2) § 115.215(4) § 115.215(6) § 115.215(9) § 115.216(1) § 115.216(1)(A) § 115.216(1)(A)(iv) ** See CAM Summary	§ 115.216(1)(A) § 115.216(1)(A)(iv) § 115.216(2) § 115.216(3)(A) § 115.216(3)(A)(i) § 115.216(3)(A)(ii) § 115.216(3)(A)(iii) § 115.216(3)(B) [G]§ 115.216(3)(E)	
LR-6401	EU	R5211-VRU	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.211(1) § 115.212(a)(3)(A) § 115.212(a)(3)(A)(i) § 115.212(a)(3)(B) [G] § 115.212(a)(3)(C) § 115.212(a)(3)(E) § 115.212(a)(4)(A) § 115.212(a)(4)(B) § 115.212(a)(4)(C) § 115.214(a)(1)(B) § 115.214(a)(1)(C)	In the Beaumont-Port Arthur, Bexar County, Dallas-Fort Worth, El Paso, and Houston-Galveston-Brazoria areas, gasoline terminals shall ensure that VOC emissions do not exceed 0.09 pound per 1,000 gallons (10.8 mg/liter) of gasoline loaded into transport vessels.	§ 115.212(a)(3)(B) § 115.212(a)(4)(C) § 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.214(a)(1)(A)(ii) § 115.214(a)(1)(A)(iii) § 115.214(a)(2) § 115.215 § 115.215(1) § 115.215(10) [G]§ 115.215(2) § 115.215(4) § 115.215(6) § 115.215(9) § 115.216(1) § 115.216(1)(A)	§ 115.216 § 115.216(1) § 115.216(1)(A) § 115.216(1)(A)(iii) § 115.216(2) § 115.216(3)(A) § 115.216(3)(A)(i) § 115.216(3)(A)(ii) § 115.216(3)(A)(iii) § 115.216(3)(B) [G]§ 115.216(3)(E)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 115.216(1)(A)(iii) ** See CAM Summary		
LR-6401	EU	60XX-VCU	TOC	40 CFR Part 60, Subpart XX	§ 60.502(a) § 60.502(b) § 60.502(d) § 60.502(g) § 60.502(h) § 60.502(i)	Each bulk gasoline terminal facility shall be equipped with a vapor collection system designed to collect the total organic compounds vapors displaced from tank trucks during product loading.	§ 60.502(j) § 60.503(a) § 60.503(b) § 60.503(c)(1) § 60.503(c)(3) § 60.503(c)(4) § 60.503(c)(5)(i) § 60.503(c)(6) § 60.503(c)(7) § 60.503(d) § 60.503(d)(1) § 60.503(d)(2) ** See CAM Summary	§ 60.502(j) § 60.503(c)(4) § 60.503(d)(2) [G]§ 60.505(c) [G]§ 60.505(e)	[G]§ 60.505(e)
LR-6401	EU	60XX-VRU	TOC	40 CFR Part 60, Subpart XX	§ 60.502(a) § 60.502(b) § 60.502(d) § 60.502(g) § 60.502(h) § 60.502(i)	Each bulk gasoline terminal facility shall be equipped with a vapor collection system designed to collect the total organic compounds vapors displaced from tank trucks during product loading.	§ 60.502(j) § 60.503(a) § 60.503(b) § 60.503(c)(1) § 60.503(c)(3) § 60.503(c)(4) § 60.503(c)(5)(ii) § 60.503(c)(6) § 60.503(c)(7) § 60.503(d) § 60.503(d)(1) § 60.503(d)(2) ** See CAM Summary	§ 60.502(j) § 60.503(c)(4) § 60.503(d)(2) [G]§ 60.505(c) [G]§ 60.505(e)	[G]§ 60.505(e)
LR-6401	EU	63BBBBB B-LOAD	112(B) HAPS	40 CFR Part 63, Subpart BBBBBB	§ 63.11088(a)-Table 2.1.b § 60.502(g) § 60.502(h) § 60.502(i) § 63.11083(a)(2) § 63.11085(a)	If you own or operate a gasoline loading rack(s) at a bulk gasoline terminal with a gasoline throughput (total of all racks) of 250,000 gallons per day, or greater, then you must reduce emissions	§ 60.502(j) § 63.11092(a)(2) § 63.11092(b) § 63.11092(b)(4) § 63.11092(b)(5) § 63.11092(b)(5)(i)	§ 60.502(j) § 63.11081(j) § 63.11094(c) § 63.11094(c)(2) § 63.11094(c)(2)(i) § 63.11094(f)(1) § 63.11094(g)	§ 63.11086(e) § 63.11086(e)(1) § 63.11086(e)(2) § 63.11086(e)(3) § 63.11086(e)(4) § 63.11086(f) § 63.11092(a)(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.11088(a)-Table 2.1.a § 63.11088(a)-Table 2.1.c § 63.11088(a)-Table 2.1.d § 63.11088(b) § 63.11092(d)(2) § 63.11092(d)(3) § 63.422(e) § 63.422(e)(1) § 63.422(e)(2)	of TOC to less than or equal to 80 mg/l of gasoline loaded into gasoline cargo tanks at the loading rack.		§ 63.11094(g)(1) § 63.11094(g)(2)	§ 63.11092(b)(4) § 63.11094(c)(2)(ii) § 63.11095(a) § 63.11095(a)(2) § 63.11095(b) § 63.11095(b)(1) § 63.11095(b)(2) § 63.11095(b)(3) § 63.11095(d)
SUMP	EU	R5112-INT	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.117(8) ** See Periodic Monitoring Summary	§ 115.118(a)(5) § 115.118(a)(7)	None
T-100	EU	R5112-INT	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in	§ 115.117(8) ** See Periodic Monitoring Summary	§ 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.			
T-4012	EU	R5112-INT	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.117(8) ** See Periodic Monitoring Summary	§ 115.118(a)(5) § 115.118(a)(7)	None
T-4012	EU	63BBBBB B-INT	112(B) HAPS	40 CFR Part 63, Subpart BBBBBB	§ 63.11087(a)-Table 1.1 § 63.11083(a)(2) § 63.11085(a)	If you own or operate a gasoline storage tank with a capacity of less than 75 cubic meters (m3), or a capacity of less than 151 cubic meters (m3) and a gasoline throughput of 480 gallons per day or less, then you must equip each gasoline storage tank with a fixed roof that is mounted to the storage tank in a stationary manner, and	None	§ 63.11081(j) § 63.11094(f)(2) § 63.11094(g) § 63.11094(g)(1) § 63.11094(g)(2)	§ 63.11086(e) § 63.11086(e)(1) § 63.11086(e)(2) § 63.11086(e)(3) § 63.11086(e)(4) § 63.11086(f) § 63.11094(f)(2) § 63.11095(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						maintain all openings in a closed position at all times when not in use.			
T-688	EU	R5112-DSL	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	§ 115.117(8)	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
T-688	EU	R5112-GAS-IFR	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(D) § 115.112(e)(2)(F) [G]§ 115.112(e)(2)(I) § 115.114(a)(1)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(1) § 115.114(a)(1)(A) § 115.117(8)	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(1)(B)
T-688	EU	63BBBBB B-GASTK	112(B) HAPS	40 CFR Part 63, Subpart BBBBBB	§ 63.11087(a)-Table 1.2.d § 113.540 § 63.1063(a)(1)(i) § 63.1063(a)(1)(i)(B) § 63.1063(a)(2)(i) § 63.1063(a)(2)(ii) § 63.1063(a)(2)(iii) § 63.1063(a)(2)(iv) § 63.1063(a)(2)(ix)	If you own or operate an internal floating roof gasoline storage tank with a capacity of greater than or equal to 75 m3 (19800 gallons) with a throughput over 480 gallons per day or a capacity equal to or greater than 151 m3 (40000 gallons), you must equip and operate the tank	§ 63.1063(c)(1) [G]§ 63.1063(c)(1)(i) [G]§ 63.1063(d)(1) § 63.1063(d)(2) § 63.11092(e)(1)	§ 63.1063(e)(2) § 63.1065 § 63.1065(a) [G]§ 63.1065(b)(1) § 63.1065(c) § 63.1065(d) § 63.11081(j) § 63.11094(a) § 63.11094(f)(1) § 63.11094(f)(2) § 63.11094(f)(2)(i)	[G]§ 63.1066(a) § 63.1066(b)(1) § 63.1066(b)(2) § 63.1066(b)(4) § 63.11086(e) § 63.11086(e)(1) § 63.11086(e)(2) § 63.11086(e)(3) § 63.11086(e)(4) § 63.11086(f) § 63.11094(f)(2)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.1063(a)(2)(v) § 63.1063(a)(2)(vi) § 63.1063(a)(2)(viii) § 63.1063(a)(2)(viii)(A) § 63.1063(b)(1) § 63.1063(b)(2) § 63.1063(b)(3) § 63.1063(b)(4) § 63.1063(e)(1) § 63.1063(e)(2) § 63.11083(a)(2) § 63.11085(a)	according to the applicable requirements in §63.1063(a)(1) and (b), except for the secondary seal requirements under §63.1063(a)(1)(i)(C) and (D).		§ 63.11094(g) § 63.11094(g)(1) § 63.11094(g)(2)	§ 63.11094(f)(2)(i) § 63.11095(a) § 63.11095(a)(1) § 63.11095(d)
T-689	EU	R5112-DSL	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	§ 115.117(8)	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
T-689	EU	R5112-GAS-IFR	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(D) § 115.112(e)(2)(F) [G]§ 115.112(e)(2)(I) § 115.114(a)(1)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(1) § 115.114(a)(1)(A) § 115.117(8)	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(1)(B)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
T-689	EU	63BBBBB B-GASTK	112(B) HAPS	40 CFR Part 63, Subpart BBBBBB	§ 63.11087(a)-Table 1.2.d § 113.540 § 63.1063(a)(1)(i) § 63.1063(a)(1)(i)(B) § 63.1063(a)(2)(i) § 63.1063(a)(2)(ii) § 63.1063(a)(2)(iii) § 63.1063(a)(2)(iv) § 63.1063(a)(2)(ix) § 63.1063(a)(2)(v) § 63.1063(a)(2)(vi) § 63.1063(a)(2)(viii) § 63.1063(a)(2)(viii)(B) § 63.1063(b)(1) § 63.1063(b)(2) § 63.1063(b)(3) § 63.1063(b)(4) § 63.1063(e)(1) § 63.1063(e)(2) § 63.11083(a)(2) § 63.11085(a)	If you own or operate an internal floating roof gasoline storage tank with a capacity of greater than or equal to 75 m3 (19800 gallons) with a throughput over 480 gallons per day or a capacity equal to or greater than 151 m3 (40000 gallons), you must equip and operate the tank according to the applicable requirements in §63.1063(a)(1) and (b), except for the secondary seal requirements under §63.1063(a)(1)(i)(C) and (D).	§ 63.1063(c)(1) [G]§ 63.1063(c)(1)(i) [G]§ 63.1063(d)(1) § 63.1063(d)(2) § 63.11092(e)(1)	§ 63.1063(e)(2) § 63.1065 § 63.1065(a) [G]§ 63.1065(b)(1) § 63.1065(c) § 63.1065(d) § 63.11081(j) § 63.11094(a) § 63.11094(f)(1) § 63.11094(f)(2) § 63.11094(f)(2)(i) § 63.11094(g) § 63.11094(g)(1) § 63.11094(g)(2)	[G]§ 63.1066(a) § 63.1066(b)(1) § 63.1066(b)(2) § 63.1066(b)(4) § 63.11086(e) § 63.11086(e)(1) § 63.11086(e)(2) § 63.11086(e)(3) § 63.11086(e)(4) § 63.11086(f) § 63.11094(f)(2) § 63.11094(f)(2)(i) § 63.11095(a) § 63.11095(a)(1) § 63.11095(d)
T-690	EU	R5112-DSL	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	§ 115.117(8)	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
T-690	EU	R5112-GAS-IFR	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(D)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all	§ 115.114(a)(1) § 115.114(a)(1)(A) § 115.117(8)	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(1)(B)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.112(e)(2)(F) [G]§ 115.112(e)(2)(I) § 115.114(a)(1)(A)	times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.			
T-690	EU	63BBBBB B-GASTK	112(B) HAPS	40 CFR Part 63, Subpart BBBBBB	§ 63.11087(a)-Table 1.2.d § 113.540 § 63.1063(a)(1)(i) § 63.1063(a)(1)(i)(B) § 63.1063(a)(2)(i) § 63.1063(a)(2)(ii) § 63.1063(a)(2)(iii) § 63.1063(a)(2)(iv) § 63.1063(a)(2)(ix) § 63.1063(a)(2)(v) § 63.1063(a)(2)(vi) § 63.1063(a)(2)(viii) § 63.1063(a)(2)(viii)(A) § 63.1063(b)(1) § 63.1063(b)(2) § 63.1063(b)(3) § 63.1063(b)(4) § 63.1063(e)(1) § 63.1063(e)(2) § 63.11083(a)(2) § 63.11085(a)	If you own or operate an internal floating roof gasoline storage tank with a capacity of greater than or equal to 75 m3 (19800 gallons) with a throughput over 480 gallons per day or a capacity equal to or greater than 151 m3 (40000 gallons), you must equip and operate the tank according to the applicable requirements in §63.1063(a)(1) and (b), except for the secondary seal requirements under §63.1063(a)(1)(i)(C) and (D).	§ 63.1063(c)(1) [G]§ 63.1063(c)(1)(i) [G]§ 63.1063(d)(1) § 63.1063(d)(2) § 63.11092(e)(1)	§ 63.1063(e)(2) § 63.1065 § 63.1065(a) [G]§ 63.1065(b)(1) § 63.1065(c) § 63.1065(d) § 63.11081(j) § 63.11094(a) § 63.11094(f)(1) § 63.11094(f)(2) § 63.11094(f)(2)(i) § 63.11094(g) § 63.11094(g)(1) § 63.11094(g)(2)	[G]§ 63.1066(a) § 63.1066(b)(1) § 63.1066(b)(2) § 63.1066(b)(4) § 63.11086(e) § 63.11086(e)(1) § 63.11086(e)(2) § 63.11086(e)(3) § 63.11086(e)(4) § 63.11086(f) § 63.11094(f)(2) § 63.11094(f)(2)(i) § 63.11095(a) § 63.11095(a)(1) § 63.11095(d)
T-691	EU	R5112-DSL	VOC	30 TAC Chapter 115, Storage of	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank	§ 115.117(8)	§ 115.118(a)(1) § 115.118(a)(5)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				VOCs		storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.		§ 115.118(a)(6)(A) § 115.118(a)(7)	
T-691	EU	R5112-GAS-IFR	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(D) § 115.112(e)(2)(F) [G]§ 115.112(e)(2)(I) § 115.114(a)(1)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(1) § 115.114(a)(1)(A) § 115.117(8)	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(1)(B)
T-691	EU	60Kb-ETH-IFR	VOC	40 CFR Part 60, Subpart Kb	§ 60.110b(e)(5) § 113.540 § 63.1062(a) § 63.1062(a)(1) § 63.1063(a)(1)(i) § 63.1063(a)(1)(i)(B) § 63.1063(a)(2)(i) § 63.1063(a)(2)(ii) § 63.1063(a)(2)(iii) § 63.1063(a)(2)(iv) § 63.1063(a)(2)(ix) § 63.1063(a)(2)(v) § 63.1063(a)(2)(vi) § 63.1063(a)(2)(viii) §	Compliance with 40 CFR part 63, subpart WW, may be chosen to satisfy the requirements of 40 CFR part 60, subpart Kb for IFR storage vessels with a design capacity greater than or equal to 75 m3 but less than 151 m3 containing a VOL with a max true vapor pressure equal to or greater than 27.6 kPa but less than 76.6 kPa.	§ 60.110b(e)(5)(iii) § 60.116b(a) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3) § 63.1063(c)(1) [G]§ 63.1063(c)(1)(i) [G]§ 63.1063(d)(1) § 63.1063(d)(2)	§ 60.110b(e)(5)(iv)(B) § 60.110b(e)(5)(iv)(C) § 60.110b(e)(5)(iv)(D) § 60.110b(e)(5)(iv)(E) § 60.116b(a) § 60.116b(c) § 63.1063(e)(2) § 63.1065 § 63.1065(a) [G]§ 63.1065(b)(1) § 63.1065(c) § 63.1065(d)	§ 60.110b(e)(5)(iv)(A) § 60.110b(e)(5)(iv)(F)(1) § 60.110b(e)(5)(iv)(F)(2) [G]§ 63.1066(a) § 63.1066(b)(1) § 63.1066(b)(2) § 63.1066(b)(4)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					63.1063(a)(2)(viii)(B) § 63.1063(b)(1) § 63.1063(b)(2) § 63.1063(b)(3) § 63.1063(b)(4) § 63.1063(e)(1) § 63.1063(e)(2)				
T-691	EU	60Kb-GAS-IFR	VOC	40 CFR Part 60, Subpart Kb	§ 60.110b(e)(5) § 113.540 § 63.1062(a) § 63.1062(a)(1) § 63.1063(a)(1)(i) § 63.1063(a)(1)(i)(B) § 63.1063(a)(2)(i) § 63.1063(a)(2)(ii) § 63.1063(a)(2)(iii) § 63.1063(a)(2)(iv) § 63.1063(a)(2)(ix) § 63.1063(a)(2)(v) § 63.1063(a)(2)(vi) § 63.1063(a)(2)(viii) § 63.1063(a)(2)(viii)(B) § 63.1063(b)(1) § 63.1063(b)(2) § 63.1063(b)(3) § 63.1063(b)(4) § 63.1063(e)(1) § 63.1063(e)(2)	Compliance with 40 CFR part 63, subpart WW, may be chosen to satisfy the requirements of 40 CFR part 60, subpart Kb for IFR storage vessels with a design capacity greater than or equal to 75 m3 but less than 151 m3 containing a VOL with a max true vapor pressure equal to or greater than 27.6 kPa but less than 76.6 kPa.	§ 60.110b(e)(5)(iii) § 60.116b(a) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2) § 60.116b(e)(2)(i) § 63.1063(c)(1) [G]§ 63.1063(c)(1)(i) [G]§ 63.1063(d)(1) § 63.1063(d)(2)	§ 60.110b(e)(5)(iv)(B) § 60.110b(e)(5)(iv)(C) § 60.110b(e)(5)(iv)(D) § 60.110b(e)(5)(iv)(E) § 60.116b(a) § 60.116b(c) § 63.1063(e)(2) § 63.1065 § 63.1065(a) [G]§ 63.1065(b)(1) § 63.1065(c) § 63.1065(d)	§ 60.110b(e)(5)(iv)(A) § 60.110b(e)(5)(iv)(F)(1) § 60.110b(e)(5)(iv)(F)(2) [G]§ 63.1066(a) § 63.1066(b)(1) § 63.1066(b)(2) § 63.1066(b)(4)
T-691	EU	63BBBBB B-GASTK	112(B) HAPS	40 CFR Part 63, Subpart BBBBBB	§ 63.11087(a)-Table 1.2.d § 113.540 § 63.1063(a)(1)(i) § 63.1063(a)(1)(i)(B)	If you own or operate an internal floating roof gasoline storage tank with a capacity of greater than or equal to 75 m3 (19800 gallons) with a throughput	§ 63.1063(c)(1) [G]§ 63.1063(c)(1)(i) [G]§ 63.1063(d)(1) § 63.1063(d)(2) § 63.11092(e)(1)	§ 63.1063(e)(2) § 63.1065 § 63.1065(a) [G]§ 63.1065(b)(1) § 63.1065(c) § 63.1065(d)	[G]§ 63.1066(a) § 63.1066(b)(1) § 63.1066(b)(2) § 63.1066(b)(4) § 63.11086(e) § 63.11086(e)(1)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.1063(a)(2)(i) § 63.1063(a)(2)(ii) § 63.1063(a)(2)(iii) § 63.1063(a)(2)(iv) § 63.1063(a)(2)(ix) § 63.1063(a)(2)(v) § 63.1063(a)(2)(vi) § 63.1063(a)(2)(viii) § 63.1063(a)(2)(viii)(B) § 63.1063(b)(1) § 63.1063(b)(2) § 63.1063(b)(3) § 63.1063(b)(4) § 63.1063(e)(1) § 63.1063(e)(2) § 63.11083(a)(2) § 63.11085(a)	over 480 gallons per day or a capacity equal to or greater than 151 m3 (40000 gallons), you must equip and operate the tank according to the applicable requirements in §63.1063(a)(1) and (b), except for the secondary seal requirements under §63.1063(a)(1)(i)(C) and (D).		§ 63.11081(j) § 63.11094(a) § 63.11094(f)(1) § 63.11094(f)(2) § 63.11094(f)(2)(i) § 63.11094(g) § 63.11094(g)(1) § 63.11094(g)(2)	§ 63.11086(e)(2) § 63.11086(e)(3) § 63.11086(e)(4) § 63.11086(f) § 63.11094(f)(2) § 63.11094(f)(2)(i) § 63.11095(a) § 63.11095(a)(1) § 63.11095(d)
T-DRAIN	EU	R5112-INT	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.117(8) ** See Periodic Monitoring Summary	§ 115.118(a)(5) § 115.118(a)(7)	None

Additional Monitoring Requirements

Compliance Assurance Monitoring Summary 28

Periodic Monitoring Summary 32

CAM Summary

Unit/Group/Process Information	
ID No.: LR-6401	
Control Device ID No.: VCU	Control Device Type: Vapor combustor
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Loading and Unloading of VOC	SOP Index No.: R5211-VCU
Pollutant: VOC	Main Standard: § 115.211(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: once per day	
Averaging Period: N/A	
Deviation Limit: Less than 300°F when loading is occurring and VCU is temporarily being used as control device instead of VRU.	
<p>CAM Text: The monitoring device should be installed in the combustion chamber or immediately downstream of the combustion chamber. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following:</p> <ul style="list-style-type: none"> ± 2% of reading; or ± 2.5 degrees Celsius. 	

CAM Summary

Unit/Group/Process Information	
ID No.: LR-6401	
Control Device ID No.: VRU	Control Device Type: Carbon adsorption system (regenerative)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Loading and Unloading of VOC	SOP Index No.: R5211-VRU
Pollutant: VOC	Main Standard: § 115.211(1)
Monitoring Information	
Indicator: VOC concentration	
Minimum Frequency: 4 times per hour	
Averaging Period: 6-hour period	
Deviation Limit: Maximum VOC concentration = 8,000 ppm propane	
<p>CAM Text: The VOC concentration of exhaust from the VRU shall be monitored and recorded by a continuous emission monitoring system (CEMS) that is capable of measuring organic compound concentration in the exhaust air stream of the control device.</p> <p>The CEMS shall be operated in accordance with the monitoring requirements of 40 CFR § 60.13 and the Performance Specifications of 40 CFR Part 60, Appendices B and F.</p>	

CAM Summary

Unit/Group/Process Information	
ID No.: LR-6401	
Control Device ID No.: VCU	Control Device Type: Vapor combustor
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart XX	SOP Index No.: 60XX-VCU
Pollutant: TOC	Main Standard: § 60.502(a)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: once per day	
Averaging Period: N/A	
Deviation Limit: Less than 300°F when loading is occurring and VCU is temporarily being used as control device instead of VRU	
<p>CAM Text: The monitoring device should be installed in the combustion chamber or immediately downstream of the combustion chamber. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following:</p> <ul style="list-style-type: none"> ± 2% of reading; or ± 2.5 degrees Celsius. 	

CAM Summary

Unit/Group/Process Information	
ID No.: LR-6401	
Control Device ID No.: VRU	Control Device Type: Carbon adsorption system (regenerative)
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart XX	SOP Index No.: 60XX-VRU
Pollutant: TOC	Main Standard: § 60.502(a)
Monitoring Information	
Indicator: VOC concentration	
Minimum Frequency: 4 times per hour	
Averaging Period: 6-hour period	
Deviation Limit: Maximum VOC concentration = 8,000 ppm propane	
<p>CAM Text: The VOC concentration of exhaust from the VRU shall be monitored and recorded by a continuous emission monitoring system (CEMS) that is capable of measuring organic compound concentration in the exhaust air stream of the control device.</p> <p>The CEMS shall be operated in accordance with the monitoring requirements of 40 CFR § 60.13 and the Performance Specifications of 40 CFR Part 60, Appendices B and F.</p>	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: SUMP	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-INT
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Record of Tank Construction Specifications	
Minimum Frequency: N/A	
Averaging Period: N/A	
Deviation Limit: No record of tank construction specifications.	
Periodic Monitoring Text: Keep a record of tank construction specifications (e.g. engineering drawings) that show a fill pipe that extends from the top of a tank to have a maximum clearance of six inches (15.2 centimeters) from the bottom or, when the tank is loaded from the side, a discharge opening entirely submerged when the pipe used to withdraw liquid from the tank can no longer withdraw liquid in normal operation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: SUMP	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-INT
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Structural Integrity of the Pipe	
Minimum Frequency: Emptied and degassed	
Averaging Period: N/A	
Deviation Limit: Repairs are not completed prior to refilling the storage vessel.	
Periodic Monitoring Text: Inspect to determine the structural integrity of the fill pipe and record each time the storage vessel is emptied and degassed to ensure that it continues to meet the specifications in the above requirement. If the structural integrity of the fill pipe is in question, repairs shall be made before the storage vessel is refilled. It shall be considered and reported as a deviation if the repairs are not completed prior to refilling the storage vessel.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: T-100	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-INT
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Record of Tank Construction Specifications	
Minimum Frequency: N/A	
Averaging Period: N/A	
Deviation Limit: No record of tank construction specifications.	
<p>Periodic Monitoring Text: Keep a record of tank construction specifications (e.g. engineering drawings) that show a fill pipe that extends from the top of a tank to have a maximum clearance of six inches (15.2 centimeters) from the bottom or, when the tank is loaded from the side, a discharge opening entirely submerged when the pipe used to withdraw liquid from the tank can no longer withdraw liquid in normal operation.</p>	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: T-100	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-INT
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Structural Integrity of the Pipe	
Minimum Frequency: Emptied and degassed	
Averaging Period: N/A	
Deviation Limit: Repairs are not completed prior to refilling the storage vessel.	
<p>Periodic Monitoring Text: Inspect to determine the structural integrity of the fill pipe and record each time the storage vessel is emptied and degassed to ensure that it continues to meet the specifications in the above requirement. If the structural integrity of the fill pipe is in question, repairs shall be made before the storage vessel is refilled. It shall be considered and reported as a deviation if the repairs are not completed prior to refilling the storage vessel.</p>	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: T-4012	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-INT
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Record of Tank Construction Specifications	
Minimum Frequency: N/A	
Averaging Period: N/A	
Deviation Limit: No record of tank construction specifications.	
<p>Periodic Monitoring Text: Keep a record of tank construction specifications (e.g. engineering drawings) that show a fill pipe that extends from the top of a tank to have a maximum clearance of six inches (15.2 centimeters) from the bottom or, when the tank is loaded from the side, a discharge opening entirely submerged when the pipe used to withdraw liquid from the tank can no longer withdraw liquid in normal operation.</p>	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: T-4012	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-INT
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Structural Integrity of the Pipe	
Minimum Frequency: Emptied and degassed	
Averaging Period: N/A	
Deviation Limit: Repairs are not completed prior to refilling the storage vessel.	
<p>Periodic Monitoring Text: Inspect to determine the structural integrity of the fill pipe and record each time the storage vessel is emptied and degassed to ensure that it continues to meet the specifications in the above requirement. If the structural integrity of the fill pipe is in question, repairs shall be made before the storage vessel is refilled. It shall be considered and reported as a deviation if the repairs are not completed prior to refilling the storage vessel.</p>	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: T-DRAIN	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-INT
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Record of Tank Construction Specifications	
Minimum Frequency: N/A	
Averaging Period: N/A	
Deviation Limit: No record of tank construction specifications.	
Periodic Monitoring Text: Keep a record of tank construction specifications (e.g. engineering drawings) that show a fill pipe that extends from the top of a tank to have a maximum clearance of six inches (15.2 centimeters) from the bottom or, when the tank is loaded from the side, a discharge opening entirely submerged when the pipe used to withdraw liquid from the tank can no longer withdraw liquid in normal operation.	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: T-DRAIN	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-INT
Pollutant: VOC	Main Standard: § 115.112(e)(1)
Monitoring Information	
Indicator: Structural Integrity of the Pipe	
Minimum Frequency: Emptied and degassed	
Averaging Period: N/A	
Deviation Limit: Repairs are not completed prior to refilling the storage vessel.	
<p>Periodic Monitoring Text: Inspect to determine the structural integrity of the fill pipe and record each time the storage vessel is emptied and degassed to ensure that it continues to meet the specifications in the above requirement. If the structural integrity of the fill pipe is in question, repairs shall be made before the storage vessel is refilled. It shall be considered and reported as a deviation if the repairs are not completed prior to refilling the storage vessel.</p>	

Permit Shield

Permit Shield 41

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit / Group / Process ID No.	Group / Inclusive Units	Regulation	Basis of Determination
GRP ADD	T-4011, T-4014, T-4015, T-4016, T-4017, T-430	40 CFR Part 60, Subpart Kb	Tank capacity is less than 75 cubic meters.
GRP ADD	T-4011, T-4014, T-4015, T-4016, T-4017, T-430	40 CFR Part 63, Subpart BBBB	Tank does not store gasoline.
GRP ADD	T-4011, T-4014, T-4015, T-4016, T-4017, T-430	40 CFR Part 63, Subpart R	Located at facility which is minor for HAP.
LR-6401	N/A	40 CFR Part 63, Subpart R	Located at facility which is minor for HAP.
OWS	N/A	30 TAC Chapter 115, Water Separation	Separator used for spills and storm water only.
OWS	N/A	40 CFR Part 63, Subpart R	Located at facility which is minor for HAP.
OWS	N/A	40 CFR Part 63, Subpart VV	Not required by another applicable standard.
SUMP	N/A	40 CFR Part 60, Subpart Kb	Tank capacity is less than 75 cubic meters.
SUMP	N/A	40 CFR Part 63, Subpart BBBB	Tank is not a gasoline storage tank as defined in 40 CFR 63.11100.
SUMP	N/A	40 CFR Part 63, Subpart R	Located at a facility which is minor for HAP.
T-100	N/A	30 TAC Chapter 115, Industrial Wastewater	Tank is not located at a site which is an affected source category.
T-100	N/A	40 CFR Part 60, Subpart Kb	Tank capacity is less than 75 cubic meters.
T-100	N/A	40 CFR Part 63, Subpart BBBB	Tank does not store gasoline.
T-100	N/A	40 CFR Part 63, Subpart R	Located at facility which is minor for HAP.
T-4012	N/A	40 CFR Part 60, Subpart K	Tank was not constructed, reconstructed, or modified after 06/11/1973.
T-4012	N/A	40 CFR Part 63, Subpart R	Located at facility which is minor for HAP.
T-688	N/A	40 CFR Part 60, Subpart K	Tank was not constructed, reconstructed, or

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit / Group / Process ID No.	Group / Inclusive Units	Regulation	Basis of Determination
			modified after 06/11/1973.
T-688	N/A	40 CFR Part 63, Subpart R	Located at facility which is minor for HAP.
T-689	N/A	40 CFR Part 60, Subpart K	Tank was not constructed, reconstructed, or modified after 06/11/1973.
T-689	N/A	40 CFR Part 63, Subpart R	Located at facility which is minor for HAP.
T-690	N/A	40 CFR Part 60, Subpart K	Tank was not constructed, reconstructed, or modified after 06/11/1973.
T-690	N/A	40 CFR Part 63, Subpart R	Located at facility which is minor for HAP.
T-691	N/A	40 CFR Part 63, Subpart R	Located at facility which is minor for HAP.
T-DRAIN	N/A	40 CFR Part 60, Subpart Kb	Tank capacity is less then 75 cubic meters.
T-DRAIN	N/A	40 CFR Part 63, Subpart BBBB	Tank is not a gasoline storage tank as defined in 40 CFR 63.11100.
T-DRAIN	N/A	40 CFR Part 63, Subpart R	Located at a facility which is minor for HAP.
T-REM	N/A	30 TAC Chapter 115, Storage of VOCs	Tank capacity is less than 1,000 gallons.
T-REM	N/A	40 CFR Part 60, Subpart Kb	Tank capacity is less than 75 cubic meters.
T-REM	N/A	40 CFR Part 63, Subpart BBBB	Tank does not store gasoline.
T-REM	N/A	40 CFR Part 63, Subpart R	Located at facility which is minor for HAP.

New Source Review Authorization References

New Source Review Authorization References 44

New Source Review Authorization References by Emission Unit 45

New Source Review Authorization References

The New Source Review authorizations listed in the table below are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Title 30 TAC Chapter 116 Permits, Special Permits, and Other Authorizations (Other Than Permits By Rule, PSD Permits, or NA Permits) for the Application Area.	
Authorization No.: 18597	Issuance Date: 05/31/2017
Authorization No.: 158337	Issuance Date: 09/24/2019
Authorization No.: 163932	Issuance Date: 02/03/2021
Authorization No.: 164878	Issuance Date: 05/21/2021
Permits By Rule (30 TAC Chapter 106) for the Application Area	
Number: 106.261	Version No./Date: 11/01/2003
Number: 106.262	Version No./Date: 11/01/2003
Number: 106.263	Version No./Date: 11/01/2001
Number: 106.472	Version No./Date: 09/04/2000
Number: 106.473	Version No./Date: 09/04/2000
Number: 106.511	Version No./Date: 09/04/2000
Number: 106.533	Version No./Date: 07/04/2004

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization**
GEN	CUMMINS C80 N6 EMERGENCY GENERATOR	106.511/09/04/2000
LR-6401	TRUCK LOADING RACK	18597, 158337, 106.261/11/01/2003 [164239, 166571]
OWS	OIL WATER SEPARATOR	18597
SUMP	SUMP	106.473/09/04/2000 [158338]
T-100	TANK 100	18597
T-4011	TANK 4011	18597
T-4012	TANK 4012	18597
T-4014	TANK 4014	18597, 106.261/11/01/2003 [160711], 106.262/11/01/2003 [160711]
T-4015	TANK 4015	18597, 106.472/09/04/2000, 106.473/09/04/2000
T-4016	TANK 4016	18597, 106.472/09/04/2000, 106.473/09/04/2000
T-4017	TANK 4017	106.472/09/04/2000
T-430	TANK 430	106.473/09/04/2000
T-688	TANK 688	18597, 106.261/11/01/2003 [158338, 164239, 166571]
T-689	TANK 689	18597, 164878, 106.261/11/01/2003 [164239, 166571]
T-690	TANK 690	18597, 106.261/11/01/2003 [158338, 164239, 166571]
T-691	TANK 691	18597, 163932, 106.261/11/01/2003 [164239]
T-DRAIN	T-DRAIN	18597

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization**
T-REM	REMEDICATION SYSTEM TANK	106.533/07/04/2004

**This column may include Permit by Rule (PBR) numbers and version dates, PBR Registration numbers in brackets, Standard Permit Registration numbers, Minor NSR permit numbers, and Major NSR permit numbers.

Appendix A

Acronym List 48

Acronym List

The following abbreviations or acronyms may be used in this permit:

ACFM	actual cubic feet per minute
AMOC	alternate means of control
ARP	Acid Rain Program
ASTM	American Society of Testing and Materials
B/PA	Beaumont/Port Arthur (nonattainment area)
CAM	Compliance Assurance Monitoring
CD	control device
CEMS	continuous emissions monitoring system
CFR	Code of Federal Regulations
COMS	continuous opacity monitoring system
CVS	closed vent system
D/FW	Dallas/Fort Worth (nonattainment area)
EP	emission point
EPA	U.S. Environmental Protection Agency
EU	emission unit
FCAA Amendments	Federal Clean Air Act Amendments
FOP	federal operating permit
gr/100 scf	grains per 100 standard cubic feet
HAP	hazardous air pollutant
H/G/B	Houston/Galveston/Brazoria (nonattainment area)
H ₂ S	hydrogen sulfide
ID No.	identification number
lb/hr	pound(s) per hour
MACT	Maximum Achievable Control Technology (40 CFR Part 63)
MMBtu/hr	Million British thermal units per hour
NA	nonattainment
N/A	not applicable
NADB	National Allowance Data Base
NESHAP	National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61)
NO _x	nitrogen oxides
NSPS	New Source Performance Standard (40 CFR Part 60)
NSR	New Source Review
ORIS	Office of Regulatory Information Systems
Pb	lead
PBR	Permit By Rule
PEMS	predictive emissions monitoring system
PM	particulate matter
ppmv	parts per million by volume
PRO	process unit
PSD	prevention of significant deterioration
psia	pounds per square inch absolute
RO	Responsible Official
SIP	state implementation plan
SO ₂	sulfur dioxide
TCEQ	Texas Commission on Environmental Quality
TSP	total suspended particulate
TVP	true vapor pressure
U.S.C.	United States Code
VOC	volatile organic compound