

FEDERAL OPERATING PERMIT

A FEDERAL OPERATING PERMIT IS HEREBY ISSUED TO
Kinder Morgan Production Company LLC

AUTHORIZING THE OPERATION OF
Yates Gas Plant
Natural Gas Liquid Extraction

LOCATED AT
Pecos County, Texas
Latitude 30° 53' 4" Longitude 101° 55' 13"
Regulated Entity Number: RN102540093

This permit is issued in accordance with and subject to the Texas Clean Air Act (TCAA), Chapter 382 of the Texas Health and Safety Code and Title 30 Texas Administrative Code Chapter 122 (30 TAC Chapter 122), Federal Operating Permits. Under 30 TAC Chapter 122, this permit constitutes the permit holder's authority to operate the site and emission units listed in this permit. Operations of the site and emission units listed in this permit are subject to all additional rules or amended rules and orders of the Commission pursuant to the TCAA.

This permit does not relieve the permit holder from the responsibility of obtaining New Source Review authorization for new, modified, or existing facilities in accordance with 30 TAC Chapter 116, Control of Air Pollution by Permits for New Construction or Modification.

The site and emission units authorized by this permit shall be operated in accordance with 30 TAC Chapter 122, the general terms and conditions, special terms and conditions, and attachments contained herein.

This permit shall expire five years from the date of issuance. The renewal requirements specified in 30 TAC § 122.241 must be satisfied in order to renew the authorization to operate the site and emission units.

Permit No: O800 Issuance Date: _____

For the Commission

Table of Contents

Section	Page
General Terms and Conditions	1
Special Terms and Conditions:	1
Emission Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting.....	1
Additional Monitoring Requirements	6
New Source Review Authorization Requirements	6
Compliance Requirements.....	7
Protection of Stratospheric Ozone	8
Temporary Fuel Shortages (30 TAC § 112.15)	8
Permit Location	8
Permit Shield (30 TAC § 122.148).....	8
Attachments	9
Applicable Requirements Summary.....	10
Additional Monitoring Requirements	37
Permit Shield.....	42
New Source Review Authorization References	48
Appendix A.....	54
Acronym List	55
Appendix B.....	56

General Terms and Conditions

The permit holder shall comply with all terms and conditions contained in 30 TAC § 122.143 (General Terms and Conditions), 30 TAC § 122.144 (Recordkeeping Terms and Conditions), 30 TAC § 122.145 (Reporting Terms and Conditions), and 30 TAC § 122.146 (Compliance Certification Terms and Conditions).

In accordance with 30 TAC § 122.144(1), records of required monitoring data and support information required by this permit, or any applicable requirement codified in this permit, are required to be maintained for a period of five years from the date of the monitoring report, sample, or application unless a longer data retention period is specified in an applicable requirement. The five year record retention period supersedes any less stringent retention requirement that may be specified in a condition of a permit identified in the New Source Review Authorization attachment.

If the permit holder chooses to demonstrate that this permit is no longer required, a written request to void this permit shall be submitted to the Texas Commission on Environmental Quality (TCEQ) by the Responsible Official in accordance with 30 TAC § 122.161(e). The permit holder shall comply with the permit's requirements, including compliance certification and deviation reporting, until notified by the TCEQ that this permit is voided.

The permit holder shall comply with 30 TAC Chapter 116 by obtaining a New Source Review authorization prior to new construction or modification of emission units located in the area covered by this permit.

All reports required by this permit must include in the submittal a cover letter which identifies the following information: company name, TCEQ regulated entity number, air account number (if assigned), site name, area name (if applicable), and Air Permits Division permit number(s).

Special Terms and Conditions:

Emission Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting

1. Permit holder shall comply with the following requirements:
 - A. Emission units (including groups and processes) in the Applicable Requirements Summary attachment shall meet the limitations, standards, equipment specifications, monitoring, recordkeeping, reporting, testing, and other requirements listed in the Applicable Requirements Summary attachment to assure compliance with the permit.
 - B. The textual description in the column titled "Textual Description" in the Applicable Requirements Summary attachment is not enforceable and is not deemed as a substitute for the actual regulatory language. The Textual Description is provided for information purposes only.
 - C. A citation listed on the Applicable Requirements Summary attachment, which has a notation [G] listed before it, shall include the referenced section and subsection for all commission rules, or paragraphs for all federal and state regulations and all subordinate paragraphs, subparagraphs and clauses, subclauses, and items contained within the referenced citation as applicable requirements.
 - D. When a grouped citation, notated with a [G] in the Applicable Requirements Summary, contains multiple compliance options, the permit holder must keep records of when each compliance option was used.
 - E. Emission units subject to 40 CFR Part 63, Subparts HH, YYYY, or ZZZZ as identified in the attached Applicable Requirements Summary table are subject to 30 TAC Chapter

113, Subchapter C, §§ 113.390, 113.1080, or 113.1090, respectively, which incorporate the 40 CFR Part 63 Subparts by reference.

2. The permit holder shall comply with the following sections of 30 TAC Chapter 101 (General Air Quality Rules):
 - A. Title 30 TAC § 101.1 (relating to Definitions), insofar as the terms defined in this section are used to define the terms used in other applicable requirements
 - B. Title 30 TAC § 101.3 (relating to Circumvention)
 - C. Title 30 TAC § 101.8 (relating to Sampling), if such action has been requested by the TCEQ
 - D. Title 30 TAC § 101.9 (relating to Sampling Ports), if such action has been requested by the TCEQ
 - E. Title 30 TAC § 101.10 (relating to Emissions Inventory Requirements)
 - F. Title 30 TAC § 101.201 (relating to Emission Event Reporting and Recordkeeping Requirements)
 - G. Title 30 TAC § 101.211 (relating to Scheduled Maintenance, Start-up, and Shutdown Reporting and Recordkeeping Requirements)
 - H. Title 30 TAC § 101.221 (relating to Operational Requirements)
 - I. Title 30 TAC § 101.222 (relating to Demonstrations)
 - J. Title 30 TAC § 101.223 (relating to Actions to Reduce Excessive Emissions)
3. Permit holder shall comply with the following requirements of 30 TAC Chapter 111:
 - A. Visible emissions from stationary vents with a flow rate of less than 100,000 actual cubic feet per minute and constructed after January 31, 1972 that are not listed in the Applicable Requirements Summary attachment for 30 TAC Chapter 111, Subchapter A, Division 1, shall not exceed 20% opacity averaged over a six-minute period. The permit holder shall comply with the following requirements for stationary vents at the site subject to this standard:
 - (i) Title 30 TAC § 111.111(a)(1)(B) (relating to Requirements for Specified Sources)
 - (ii) Title 30 TAC § 111.111(a)(1)(E)
 - (iii) Title 30 TAC § 111.111(a)(1)(F)(i), (ii), (iii), or (iv)
 - (iv) For emission units with vent emissions subject to 30 TAC § 111.111(a)(1)(B), complying with 30 TAC § 111.111(a)(1)(F)(ii), (iii), or (iv), and capable of producing visible emissions from, but not limited to, particulate matter, acid gases and NO_x, the permit holder shall also comply with the following periodic monitoring requirements for the purpose of annual compliance certification under 30 TAC § 122.146. These periodic monitoring requirements do not apply to vents that are not capable of producing visible emissions such as vents that emit only colorless VOCs; vents from non-fuming liquids; vents that provide passive ventilation, such as plumbing vents; or vent emissions from any other source that

does not obstruct the transmission of light. Vents, as specified in the “Applicable Requirements Summary” attachment, that are subject to the emission limitation of 30 TAC § 111.111(a)(1)(B) are not subject to the following periodic monitoring requirements:

- (1) An observation of stationary vents from emission units in operation shall be conducted at least once during each calendar quarter unless the emission unit is not operating for the entire quarter.
- (2) For stationary vents from a combustion source, if an alternative to the normally fired fuel is fired for a period greater than or equal to 24 consecutive hours, the permit holder shall conduct an observation of the stationary vent for each such period to determine if visible emissions are present. If such period is greater than 3 months, observations shall be conducted once during each quarter. Supplementing the normally fired fuel with natural gas or fuel gas to increase the net heating value to the minimum required value does not constitute creation of an alternative fuel.
- (3) Records of all observations shall be maintained.
- (4) Visible emissions observations of emission units operated during daylight hours shall be conducted no earlier than one hour after sunrise and no later than one hour before sunset. Visible emissions observations of emission units operated only at night must be made with additional lighting and the temporary installation of contrasting backgrounds. Visible emissions observations shall be made during times when the activities described in 30 TAC § 111.111(a)(1)(E) are not taking place. Visible emissions shall be determined with each stationary vent in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 mile, away from each stationary vent during the observation. For outdoor locations, the observer shall select a position where the sun is not directly in the observer’s eyes. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. A certified opacity reader is not required for visible emissions observations.
- (5) Compliance Certification:
 - (a) If visible emissions are not present during the observation, the RO may certify that the source is in compliance with the applicable opacity requirement in 30 TAC § 111.111(a)(1) and (a)(1)(B).
 - (b) However, if visible emissions are present during the observation, the permit holder shall either list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(1)(F) as soon as practicable, but no later than 24 hours after observing visible emissions to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is

determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.

- (c) Some vents may be subject to multiple visible emission or monitoring requirements. All credible data must be considered when certifying compliance with this requirement even if the observation or monitoring was performed to demonstrate compliance with a different requirement.

B. For visible emissions from a building, enclosed facility, or other structure; the permit holder shall comply with the following requirements:

- (i) Title 30 TAC § 111.111(a)(7)(A) (relating to Requirements for Specified Sources)
- (ii) Title 30 TAC § 111.111(a)(7)(B)(i) or (ii)
- (iii) For a building containing an air emission source, enclosed facility, or other structure containing or associated with an air emission source subject to 30 TAC § 111.111(a)(7)(A), complying with 30 TAC § 111.111(a)(7)(B)(i) or (ii), and capable of producing visible emissions from, but not limited to, particulate matter, acid gases and NO_x, the permit holder shall also comply with the following periodic monitoring requirements for the purpose of annual compliance certification under 30 TAC § 122.146:
 - (1) An observation of visible emissions from a building containing an air emission source, enclosed facility, or other structure containing or associated with an air emission source which is required to comply with 30 TAC § 111.111(a)(7)(A) shall be conducted at least once during each calendar quarter unless the air emission source or enclosed facility is not operating for the entire quarter.
 - (2) Records of all observations shall be maintained.
 - (3) Visible emissions observations of air emission sources or enclosed facilities operated during daylight hours shall be conducted no earlier than one hour after sunrise and no later than one hour before sunset. Visible emissions observations of air emission sources or enclosed facilities operated only at night must be made with additional lighting and the temporary installation of contrasting backgrounds. Visible emissions shall be determined with each emissions outlet in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 mile, away from each emissions outlet during the observation. For outdoor locations, the observer shall select a position where the sun is not directly in the observer's eyes. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. A certified opacity reader is not required for visible emissions observations.

(4) Compliance Certification:

- (a) If visible emissions are not present during the observation, the RO may certify that the source is in compliance with the applicable opacity requirement in 30 TAC § 111.111(a)(7) and (a)(7)(A).
 - (b) However, if visible emissions are present during the observation, the permit holder shall either list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(7)(B) as soon as practicable, but no later than 24 hours after observing visible emissions to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.
- C. Certification of opacity readers determining opacities under Method 9 (as outlined in 40 CFR Part 60, Appendix A) to comply with opacity monitoring requirements shall be accomplished by completing the Visible Emissions Evaluators Course, or approved agency equivalent, no more than 180 days before the opacity reading.
- D. For emission units with contributions from uncombined water, the permit holder shall comply with the requirements of 30 TAC § 111.111(b).
- E. Emission limits on nonagricultural processes, except for the steam generators specified in 30 TAC § 111.153, shall comply with the following requirements:
- (i) Emissions of PM from any source may not exceed the allowable rates as required in 30 TAC § 111.151(a) (relating to Allowable Emissions Limits)
 - (ii) Sources with an effective stack height (h_e) less than the standard effective stack height (H_e), must reduce the allowable emission level by multiplying it by $[h_e/H_e]^2$ as required in 30 TAC § 111.151(b)
 - (iii) Effective stack height shall be calculated by the equation specified in 30 TAC § 111.151(c)
4. The permit holder shall comply with the following requirements for units subject to any subpart of 40 CFR Part 60, unless otherwise stated in the applicable subpart:
- A. Title 40 CFR § 60.7 (relating to Notification and Recordkeeping)
 - B. Title 40 CFR § 60.8 (relating to Performance Tests)
 - C. Title 40 CFR § 60.11 (relating to Compliance with Standards and Maintenance Requirements)
 - D. Title 40 CFR § 60.12 (relating to Circumvention)

- E. Title 40 CFR § 60.13 (relating to Monitoring Requirements)
 - F. Title 40 CFR § 60.14 (relating to Modification)
 - G. Title 40 CFR § 60.15 (relating to Reconstruction)
 - H. Title 40 CFR § 60.19 (relating to General Notification and Reporting Requirements)
5. The permit holder shall comply with the requirements of 30 TAC Chapter 113, Subchapter C, § 113.100 for units subject to any subpart of 40 CFR Part 63, unless otherwise stated in the applicable subpart.
 6. For oil and natural gas production facilities as specified in 40 CFR Part 63, Subpart HH, the permit holder shall comply with the following requirements (Title 30 TAC Chapter 113, Subchapter C, § 113.390 incorporated by reference):
 - A. Title 40 CFR § 63.760(a)(1)(i) - (iii) (relating to Applicability and Designation of Affected Source)
 - B. Title 40 CFR § 63.775(d)(9) (relating to Reporting Requirements)

Additional Monitoring Requirements

7. The permit holder shall comply with the periodic monitoring requirements as specified in the attached “Periodic Monitoring Summary” upon issuance of the permit. Except for, as applicable, monitoring malfunctions, associated repairs, and required quality assurance or control activities (including, as applicable, calibration checks and required zero and span adjustments), the permit holder shall conduct all monitoring in continuous operation (or shall collect data at all required intervals) at all times that the pollutant-specific emissions unit is operating. The permit holder may elect to collect monitoring data on a more frequent basis and average the data, consistent with the averaging time or minimum frequency specified in the “Periodic Monitoring Summary,” for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis. In no event shall data be collected and used in particular instances to avoid reporting deviations. Deviations shall be reported according to 30 TAC § 122.145 (Reporting Terms and Conditions).

New Source Review Authorization Requirements

8. Permit holder shall comply with the requirements of New Source Review authorizations issued or claimed by the permit holder for the permitted area, including permits, permits by rule (including the terms, conditions, monitoring, recordkeeping, and reporting identified in registered PBRs and permits by rule identified in the PBR Supplemental Tables dated January 20, 2026 in the application for project 38564), standard permits, flexible permits, special permits, permits for existing facilities including Voluntary Emissions Reduction Permits and Electric Generating Facility Permits issued under 30 TAC Chapter 116, Subchapter I, or special exemptions referenced in the New Source Review Authorization References attachment. These requirements:
 - A. Are incorporated by reference into this permit as applicable requirements
 - B. Shall be located with this operating permit
 - C. Are not eligible for a permit shield

9. The permit holder shall comply with the general requirements of 30 TAC Chapter 106, Subchapter A or the general requirements, if any, in effect at the time of the claim of any PBR.
10. The permit holder shall maintain records to demonstrate compliance with any emission limitation or standard that is specified in a permit by rule (PBR) or Standard Permit listed in the New Source Review Authorizations attachment. The records shall yield reliable data from the relevant time period that are representative of the emission unit's compliance with the PBR or Standard Permit. These records may include, but are not limited to, production capacity and throughput, hours of operation, safety data sheets (SDS), chemical composition of raw materials, speciation of air contaminant data, engineering calculations, maintenance records, fugitive data, performance tests, capture/control device efficiencies, direct pollutant monitoring (CEMS, COMS, or PEMS), or control device parametric monitoring. These records shall be made readily accessible and available as required by 30 TAC § 122.144. Any monitoring or recordkeeping data indicating noncompliance with the PBR or Standard Permit shall be considered and reported as a deviation according to 30 TAC § 122.145 (Reporting Terms and Conditions).

Compliance Requirements

11. The permit holder shall certify compliance in accordance with 30 TAC § 122.146. The permit holder shall comply with 30 TAC § 122.146 using at a minimum, but not limited to, the continuous or intermittent compliance method data from monitoring, recordkeeping, reporting, or testing required by the permit and any other credible evidence or information. The certification period may not exceed 12 months and the certification must be submitted within 30 days after the end of the period being certified.
12. Use of Discrete Emission Credits to comply with the applicable requirements:
 - A. Unless otherwise prohibited, the permit holder may use discrete emission credits to comply with the following applicable requirements listed elsewhere in this permit:
 - (i) Title 30 TAC Chapter 115
 - (ii) Title 30 TAC Chapter 117
 - (iii) If applicable, offsets for Title 30 TAC Chapter 116
 - (iv) Temporarily exceed state NSR permit allowables
 - B. The permit holder shall comply with the following requirements in order to use the credit to comply with the applicable requirements:
 - (i) The permit holder must notify the TCEQ according to 30 TAC § 101.376(d)
 - (ii) The discrete emission credits to be used must meet all the geographic, timeliness, applicable pollutant type, and availability requirements listed in 30 TAC Chapter 101, Subchapter H, Division 4
 - (iii) The executive director has approved the use of the discrete emission credits according to 30 TAC § 101.376(d)(1)(A)
 - (iv) The permit holder keeps records of the use of credits towards compliance with the applicable requirements in accordance with 30 TAC § 101.372(h) and 30 TAC Chapter 122

- (v) Title 30 TAC § 101.375 (relating to Emission Reductions Achieved Outside the United States)

Protection of Stratospheric Ozone

- 13. Permit holders at a site subject to Title VI of the FCAA Amendments shall meet the following requirements for protection of stratospheric ozone:
 - A. Any on site servicing, maintenance, and repair on refrigeration and nonmotor vehicle air-conditioning appliances using ozone-depleting refrigerants or non-exempt substitutes shall be conducted in accordance with 40 CFR Part 82, Subpart F. Permit holders shall ensure that repairs on or refrigerant removal from refrigeration and nonmotor vehicle air-conditioning appliances using ozone-depleting refrigerants are performed only by properly certified technicians using certified equipment. Records shall be maintained as required by 40 CFR Part 82, Subpart F.
 - B. The permit holder shall comply with 40 CFR Part 82, Subpart H related to Halon Emissions Reduction requirements as specified in 40 CFR § 82.250 - § 82.270 and the applicable Part 82 Appendices.

Temporary Fuel Shortages (30 TAC § 112.15)

- 14. The permit holder shall comply with the following 30 TAC Chapter 112 requirements:
 - A. Title 30 TAC § 112.15 (relating to Temporary Fuel Shortage Plan Filing Requirements)
 - B. Title 30 TAC § 112.16(a), (a)(1), and (a)(2)(B) - (C) (relating to Temporary Fuel Shortage Plan Operating Requirements)
 - C. Title 30 TAC § 112.17 (relating to Temporary Fuel Shortage Plan Notification Procedures)
 - D. Title 30 TAC § 112.18 (relating to Temporary Fuel Shortage Plan Reporting Requirements)

Permit Location

- 15. The permit holder shall maintain a copy of this permit and records related to requirements listed in this permit on site.

Permit Shield (30 TAC § 122.148)

- 16. A permit shield is granted for the emission units, groups, or processes specified in the attached "Permit Shield." Compliance with the conditions of the permit shall be deemed compliance with the specified potentially applicable requirements or specified potentially applicable state-only requirements listed in the attachment "Permit Shield." Permit shield provisions shall not be modified by the executive director until notification is provided to the permit holder. No later than 90 days after notification of a change in a determination made by the executive director, the permit holder shall apply for the appropriate permit revision to reflect the new determination. Provisional terms are not eligible for this permit shield. Any term or condition, under a permit shield, shall not be protected by the permit shield if it is replaced by a provisional term or condition or the basis of the term and condition changes.

Attachments

Applicable Requirements Summary

Additional Monitoring Requirements

Permit Shield

New Source Review Authorization References

Applicable Requirements Summary

Unit Summary 11

Applicable Requirements Summary 13

Note: A “none” entry may be noted for some emission sources in this permit’s “Applicable Requirements Summary” under the heading of “Monitoring and Testing Requirements” and/or “Recordkeeping Requirements” and/or “Reporting Requirements.” Such a notation indicates that there are no requirements for the indicated emission source as identified under the respective column heading(s) for the stated portion of the regulation when the emission source is operating under the conditions of the specified SOP Index Number. However, other relevant requirements pursuant to 30 TAC Chapter 122 including Recordkeeping Terms and Conditions (§ 122.144), Reporting Terms and Conditions (§ 122.145), and Compliance Certification Terms and Conditions (§ 122.146) continue to apply.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
AGB1-FUG	FUGITIVE EMISSION UNITS	N/A	60KKK-002	40 CFR Part 60, Subpart KKK	No changing attributes.
AGB2-FUG	FUGITIVE EMISSION UNITS	N/A	60KKK-002	40 CFR Part 60, Subpart KKK	No changing attributes.
AGB3-FUG	FUGITIVE EMISSION UNITS	N/A	60KKK-002	40 CFR Part 60, Subpart KKK	No changing attributes.
AIR-1	SRIC ENGINES	N/A	60III	40 CFR Part 60, Subpart III	No changing attributes.
AIR-1	SRIC ENGINES	N/A	63ZZZZ	40 CFR Part 63, Subpart ZZZZ	No changing attributes.
COMPFUG2	FUGITIVE EMISSION UNITS	N/A	60KKK-003	40 CFR Part 60, Subpart KKK	No changing attributes.
COMPFUG3	FUGITIVE EMISSION UNITS	N/A	60KKK-002	40 CFR Part 60, Subpart KKK	No changing attributes.
COMPFUG5	FUGITIVE EMISSION UNITS	N/A	60KKK-004	40 CFR Part 60, Subpart KKK	No changing attributes.
D1	STATIONARY TURBINES	N/A	60GG-001	40 CFR Part 60, Subpart GG	No changing attributes.
D2	STATIONARY TURBINES	N/A	60GG-001	40 CFR Part 60, Subpart GG	No changing attributes.
DGA4-FUG	FUGITIVE EMISSION UNITS	N/A	60KKK-005	40 CFR Part 60, Subpart KKK	No changing attributes.
E1-E	STATIONARY TURBINES	N/A	60GG-001	40 CFR Part 60, Subpart GG	No changing attributes.
E1-W	STATIONARY TURBINES	N/A	60GG-001	40 CFR Part 60, Subpart GG	No changing attributes.
FL-2	FLARES	N/A	60A-002	40 CFR Part 60, Subpart A	No changing attributes.
FUG-NGP	FUGITIVE EMISSION UNITS	N/A	60KKK-008	40 CFR Part 60, Subpart KKK	No changing attributes.
FWP	SRIC ENGINES	N/A	60III-01	40 CFR Part 60, Subpart III	No changing attributes.
FWP	SRIC ENGINES	N/A	63ZZZZ-01	40 CFR Part 63, Subpart	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
				ZZZZ	
INLET-FUG	FUGITIVE EMISSION UNITS	N/A	60KKK-006	40 CFR Part 60, Subpart KKK	No changing attributes.
TEGDEHY	GLYCOL DEHYDRATION	N/A	63HH-1	40 CFR Part 63, Subpart HH	No changing attributes.
TREAT-FUG	FUGITIVE EMISSION UNITS	N/A	60KKK-007	40 CFR Part 60, Subpart KKK	No changing attributes.
U1	STATIONARY TURBINES	N/A	60KKKK-2	40 CFR Part 60, Subpart KKKK	No changing attributes.
U1	STATIONARY TURBINES	N/A	63YYYY-2	40 CFR Part 63, Subpart YYYY	No changing attributes.

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
AGB1-FUG	EU	60KKK-002	VOC	40 CFR Part 60, Subpart KKK	§ 60.633(f)	Reciprocating compressors in wet gas service are exempt from the compressor control requirements of §60.482-3.	None	§ 60.486(j) § 60.635(c)	None
AGB1-FUG	EU	60KKK-002	VOC	40 CFR Part 60, Subpart KKK	§ 60.632(a) § 60.482-1(a) § 60.482-1(b) § 60.482-7(b) § 60.482-7(d)(1) § 60.482-7(d)(2) [G]§ 60.482-7(e) [G]§ 60.482-7(f) [G]§ 60.482-7(g) [G]§ 60.482-7(h) § 60.482-9(a) § 60.482-9(b) [G]§ 60.482-9(c) § 60.482-9(e) § 60.482-9(f) § 60.486(k)	Comply with the requirements for valves in gas/vapor service as stated in §60.482-7 and §60.482-1(a), (b) and (d), except as provided in §60.633.	§ 60.482-7(a)(1) [G]§ 60.482-7(a)(2) § 60.482-7(c)(1)(i) § 60.482-7(c)(1)(ii) § 60.482-7(c)(2) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) § 60.485(d)(2) § 60.485(d)(3) § 60.485(f) § 60.632(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.636(b) [G]§ 60.636(c)
AGB1-FUG	EU	60KKK-002	VOC	40 CFR Part 60, Subpart KKK	§ 60.632(a) § 60.482-1(a) § 60.482-1(b) § 60.482-6(a)(1) § 60.482-6(a)(2) § 60.482-6(b) § 60.482-6(c) § 60.482-6(d) § 60.482-6(e) § 60.482-9(a) § 60.482-9(b) [G]§ 60.482-9(c) § 60.482-9(e) § 60.482-9(f) § 60.486(k)	Comply with the requirements for open-ended valves or lines as stated in §60.482-6 and §60.482-1(a), (b) and (d), except as provided in §60.633.	§ 60.485(a) [G]§ 60.485(b) § 60.485(d)(2) § 60.485(d)(3) § 60.485(f) § 60.632(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.636(b) [G]§ 60.636(c)
AGB1-FUG	EU	60KKK-002	VOC	40 CFR Part 60, Subpart KKK	§ 60.632(a) § 60.482-1(a)	Comply with the requirements for connectors	§ 60.482-8(a)(1) § 60.485(a)	[G]§ 60.486(a) [G]§ 60.486(b)	§ 60.487(a) [G]§ 60.487(b)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.482-1(b) § 60.482-8(a) § 60.482-8(a)(2) § 60.482-8(b) § 60.482-8(c)(1) § 60.482-8(c)(2) § 60.482-8(d) § 60.482-9(a) § 60.482-9(b) § 60.486(k)	as stated in §60.482-8, except as provided in §60.633.	[G]§ 60.485(b) § 60.485(d)(2) § 60.485(d)(3) § 60.485(f) § 60.632(d)	[G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j)	[G]§ 60.487(c) § 60.487(e) § 60.636(b) [G]§ 60.636(c)
AGB1-FUG	EU	60KKK-002	VOC	40 CFR Part 60, Subpart KKK	§ 60.632(a) § 60.482-1(a) § 60.482-1(b) § 60.482-4(a) § 60.482-4(b)(1) § 60.482-4(c) § 60.482-4(d)(1) § 60.482-4(d)(2) § 60.482-9(a) § 60.482-9(b) § 60.486(k) [G]§ 60.633(b)(3)	Comply with the requirements for pressure relief devices in gas/vapor service as stated in §60.482-4 and 60.482-1(a), (b) and (d), except as provided in §60.633.	§ 60.482-4(b)(2) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) § 60.485(d)(2) § 60.485(d)(3) § 60.485(f) § 60.632(d) § 60.633(b)(1) § 60.633(b)(2) [G]§ 60.633(b)(3) [G]§ 60.633(b)(4)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(3) [G]§ 60.486(e)(4) § 60.486(j) § 60.633(b)(1) [G]§ 60.633(b)(4) [G]§ 60.635(b)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.636(b) [G]§ 60.636(c)
AGB1-FUG	EU	60KKK-002	VOC	40 CFR Part 60, Subpart KKK	§ 60.632(a) § 60.482-1(a) § 60.482-1(b) § 60.482-2(b)(1) [G]§ 60.482-2(b)(2) § 60.482-2(c)(1) [G]§ 60.482-2(c)(2) § 60.482-2(d) [G]§ 60.482-2(d)(1) § 60.482-2(d)(2) § 60.482-2(d)(3) [G]§ 60.482-2(d)(4) [G]§ 60.482-2(d)(5) [G]§ 60.482-2(d)(6) [G]§ 60.482-2(e) § 60.482-2(f)	Comply with the requirements for pumps in light liquid service as stated in §60.482-2 and §60.482-1(a), (b) and (d), except as provided in §60.633.	[G]§ 60.482-2(a) [G]§ 60.482-2(b)(2) [G]§ 60.482-2(d)(4) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) § 60.485(d)(2) § 60.485(d)(3) [G]§ 60.485(e) § 60.485(f) § 60.632(d) [G]§ 60.633(h)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) [G]§ 60.486(h) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.636(b) [G]§ 60.636(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 60.482-2(g) § 60.482-2(h) § 60.482-9(a) § 60.482-9(b) [G]§ 60.482-9(d) § 60.482-9(f) § 60.486(k)				
AGB2-FUG	EU	60KKK-002	VOC	40 CFR Part 60, Subpart KKK	§ 60.632(a) § 60.482-1(a) § 60.482-1(b) § 60.482-2(b)(1) [G]§ 60.482-2(b)(2) § 60.482-2(c)(1) [G]§ 60.482-2(c)(2) § 60.482-2(d) [G]§ 60.482-2(d)(1) § 60.482-2(d)(2) § 60.482-2(d)(3) [G]§ 60.482-2(d)(4) [G]§ 60.482-2(d)(5) [G]§ 60.482-2(d)(6) [G]§ 60.482-2(e) § 60.482-2(f) [G]§ 60.482-2(g) § 60.482-2(h) § 60.482-9(a) § 60.482-9(b) [G]§ 60.482-9(d) § 60.482-9(f) § 60.486(k)	Comply with the requirements for pumps in light liquid service as stated in §60.482-2 and §60.482-1(a), (b) and (d), except as provided in §60.633.	[G]§ 60.482-2(a) [G]§ 60.482-2(b)(2) [G]§ 60.482-2(d)(4) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) § 60.485(d)(2) § 60.485(d)(3) [G]§ 60.485(e) § 60.485(f) § 60.632(d) [G]§ 60.633(h)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) [G]§ 60.486(h) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.636(b) [G]§ 60.636(c)
AGB2-FUG	EU	60KKK-002	VOC	40 CFR Part 60, Subpart KKK	§ 60.633(f)	Reciprocating compressors in wet gas service are exempt from the compressor control requirements of §60.482-3.	None	§ 60.486(j) § 60.635(c)	None
AGB2-FUG	EU	60KKK-002	VOC	40 CFR Part 60, Subpart KKK	§ 60.632(a) § 60.482-1(a) § 60.482-1(b)	Comply with the requirements for open-ended valves or lines as	§ 60.485(a) [G]§ 60.485(b) § 60.485(d)(2)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.482-6(a)(1) § 60.482-6(a)(2) § 60.482-6(b) § 60.482-6(c) § 60.482-6(d) § 60.482-6(e) § 60.482-9(a) § 60.482-9(b) [G]§ 60.482-9(c) § 60.482-9(e) § 60.482-9(f) § 60.486(k)	stated in §60.482-6 and §60.482-1(a), (b) and (d), except as provided in §60.633.	§ 60.485(d)(3) § 60.485(f) § 60.632(d)	§ 60.486(j)	§ 60.487(e) § 60.636(b) [G]§ 60.636(c)
AGB2-FUG	EU	60KKK-002	VOC	40 CFR Part 60, Subpart KKK	§ 60.632(a) § 60.482-1(a) § 60.482-1(b) § 60.482-7(b) § 60.482-7(d)(1) § 60.482-7(d)(2) [G]§ 60.482-7(e) [G]§ 60.482-7(f) [G]§ 60.482-7(g) [G]§ 60.482-7(h) § 60.482-9(a) § 60.482-9(b) [G]§ 60.482-9(c) § 60.482-9(e) § 60.482-9(f) § 60.486(k)	Comply with the requirements for valves in gas/vapor service as stated in §60.482-7 and §60.482-1(a), (b) and (d), except as provided in §60.633.	§ 60.482-7(a)(1) [G]§ 60.482-7(a)(2) § 60.482-7(c)(1)(i) § 60.482-7(c)(1)(ii) § 60.482-7(c)(2) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) § 60.485(d)(2) § 60.485(d)(3) § 60.485(f) § 60.632(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.636(b) [G]§ 60.636(c)
AGB2-FUG	EU	60KKK-002	VOC	40 CFR Part 60, Subpart KKK	§ 60.632(a) § 60.482-1(a) § 60.482-1(b) § 60.482-8(a) § 60.482-8(a)(2) § 60.482-8(b) § 60.482-8(c)(1) § 60.482-8(c)(2) § 60.482-8(d) § 60.482-9(a)	Comply with the requirements for connectors as stated in §60.482-8, except as provided in §60.633.	§ 60.482-8(a)(1) § 60.485(a) [G]§ 60.485(b) § 60.485(d)(2) § 60.485(d)(3) § 60.485(f) § 60.632(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.636(b) [G]§ 60.636(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.482-9(b) § 60.486(k)				
AGB2-FUG	EU	60KKK-002	VOC	40 CFR Part 60, Subpart KKK	§ 60.632(a) § 60.482-1(a) § 60.482-1(b) § 60.482-4(a) § 60.482-4(b)(1) § 60.482-4(c) § 60.482-4(d)(1) § 60.482-4(d)(2) § 60.482-9(a) § 60.482-9(b) § 60.486(k) [G]§ 60.633(b)(3)	Comply with the requirements for pressure relief devices in gas/vapor service as stated in §60.482-4 and 60.482-1(a), (b) and (d), except as provided in §60.633.	§ 60.482-4(b)(2) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) § 60.485(d)(2) § 60.485(d)(3) § 60.485(f) § 60.632(d) § 60.633(b)(1) § 60.633(b)(2) [G]§ 60.633(b)(3) [G]§ 60.633(b)(4)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(3) [G]§ 60.486(e)(4) § 60.486(j) § 60.633(b)(1) [G]§ 60.633(b)(4) [G]§ 60.635(b)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.636(b) [G]§ 60.636(c)
AGB3-FUG	EU	60KKK-002	VOC	40 CFR Part 60, Subpart KKK	§ 60.633(f)	Reciprocating compressors in wet gas service are exempt from the compressor control requirements of §60.482-3.	None	§ 60.486(j) § 60.635(c)	None
AGB3-FUG	EU	60KKK-002	VOC	40 CFR Part 60, Subpart KKK	§ 60.632(a) § 60.482-1(a) § 60.482-1(b) § 60.482-7(b) § 60.482-7(d)(1) § 60.482-7(d)(2) [G]§ 60.482-7(e) [G]§ 60.482-7(f) [G]§ 60.482-7(g) [G]§ 60.482-7(h) § 60.482-9(a) § 60.482-9(b) [G]§ 60.482-9(c) § 60.482-9(e) § 60.482-9(f) § 60.486(k)	Comply with the requirements for valves in gas/vapor service as stated in §60.482-7 and §60.482-1(a), (b) and (d), except as provided in §60.633.	§ 60.482-7(a)(1) [G]§ 60.482-7(a)(2) § 60.482-7(c)(1)(i) § 60.482-7(c)(1)(ii) § 60.482-7(c)(2) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) § 60.485(d)(2) § 60.485(d)(3) § 60.485(f) § 60.632(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.636(b) [G]§ 60.636(c)
AGB3-FUG	EU	60KKK-002	VOC	40 CFR Part 60, Subpart KKK	§ 60.632(a) § 60.482-1(a)	Comply with the requirements for pressure	§ 60.482-4(b)(2) § 60.485(a)	[G]§ 60.486(a) § 60.486(e)	§ 60.487(a) [G]§ 60.487(b)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.482-1(b) § 60.482-4(a) § 60.482-4(b)(1) § 60.482-4(c) § 60.482-4(d)(1) § 60.482-4(d)(2) § 60.482-9(a) § 60.482-9(b) § 60.486(k) [G]§ 60.633(b)(3)	relief devices in gas/vapor service as stated in §60.482-4 and 60.482-1(a), (b) and (d), except as provided in §60.633.	[G]§ 60.485(b) [G]§ 60.485(c) § 60.485(d)(2) § 60.485(d)(3) § 60.485(f) § 60.632(d) § 60.633(b)(1) § 60.633(b)(2) [G]§ 60.633(b)(3) [G]§ 60.633(b)(4)	§ 60.486(e)(1) § 60.486(e)(3) [G]§ 60.486(e)(4) § 60.486(j) § 60.633(b)(1) [G]§ 60.633(b)(4) [G]§ 60.635(b)	[G]§ 60.487(c) § 60.487(e) § 60.636(b) [G]§ 60.636(c)
AGB3-FUG	EU	60KKK-002	VOC	40 CFR Part 60, Subpart KKK	§ 60.632(a) § 60.482-1(a) § 60.482-1(b) § 60.482-6(a)(1) § 60.482-6(a)(2) § 60.482-6(b) § 60.482-6(c) § 60.482-6(d) § 60.482-6(e) § 60.482-9(a) § 60.482-9(b) [G]§ 60.482-9(c) § 60.482-9(e) § 60.482-9(f) § 60.486(k)	Comply with the requirements for open-ended valves or lines as stated in §60.482-6 and §60.482-1(a), (b) and (d), except as provided in §60.633.	§ 60.485(a) [G]§ 60.485(b) § 60.485(d)(2) § 60.485(d)(3) § 60.485(f) § 60.632(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.636(b) [G]§ 60.636(c)
AGB3-FUG	EU	60KKK-002	VOC	40 CFR Part 60, Subpart KKK	§ 60.632(a) § 60.482-1(a) § 60.482-1(b) § 60.482-8(a) § 60.482-8(a)(2) § 60.482-8(b) § 60.482-8(c)(1) § 60.482-8(c)(2) § 60.482-8(d) § 60.482-9(a) § 60.482-9(b) § 60.486(k)	Comply with the requirements for connectors as stated in §60.482-8, except as provided in §60.633.	§ 60.482-8(a)(1) § 60.485(a) [G]§ 60.485(b) § 60.485(d)(2) § 60.485(d)(3) § 60.485(f) § 60.632(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.636(b) [G]§ 60.636(c)
AGB3-FUG	EU	60KKK-	VOC	40 CFR Part 60,	§ 60.632(a)	Comply with the	[G]§ 60.482-2(a)	[G]§ 60.486(a)	§ 60.487(a)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		002		Subpart KKK	§ 60.482-1(a) § 60.482-1(b) § 60.482-2(b)(1) [G]§ 60.482-2(b)(2) § 60.482-2(c)(1) [G]§ 60.482-2(c)(2) § 60.482-2(d) [G]§ 60.482-2(d)(1) § 60.482-2(d)(2) § 60.482-2(d)(3) [G]§ 60.482-2(d)(4) [G]§ 60.482-2(d)(5) [G]§ 60.482-2(d)(6) [G]§ 60.482-2(e) § 60.482-2(f) [G]§ 60.482-2(g) § 60.482-2(h) § 60.482-9(a) § 60.482-9(b) [G]§ 60.482-9(d) § 60.482-9(f) § 60.486(k)	requirements for pumps in light liquid service as stated in §60.482-2 and §60.482-1(a), (b) and (d), except as provided in §60.633.	[G]§ 60.482-2(b)(2) [G]§ 60.482-2(d)(4) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) § 60.485(d)(2) § 60.485(d)(3) [G]§ 60.485(e) § 60.485(f) § 60.632(d) [G]§ 60.633(h)	[G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) [G]§ 60.486(h) § 60.486(j)	[G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.636(b) [G]§ 60.636(c)
AIR-1	EU	60III	CO	40 CFR Part 60, Subpart III	§ 60.4205(b) § 1039-Appendix I § 60.4202(a)(2) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f)	Owners and operators of emergency stationary CI ICE, that are not fire pump engines, with a maximum engine power greater than or equal to 130 KW and less than or equal to 2237 KW and a displacement of less than 10 liters per cylinder and is a 2007 model year and later must comply with a CO emission limit of 3.5 g/KW-hr, as stated in 40 CFR 60.4202(a)(2) and 40 CFR 1039-Appendix I.	§ 60.4209(a)	§ 60.4214(b)	[G]§ 60.4214(d)
AIR-1	EU	60III	NMHC and	40 CFR Part 60,	§ 60.4205(b)	Owners and operators of	§ 60.4209(a)	§ 60.4214(b)	[G]§ 60.4214(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
			NO _x	Subpart IIII	§ 1039-Appendix I § 60.4202(a)(2) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f)	emergency stationary CI ICE, that are not fire pump engines, with a maximum engine power greater than or equal to 75 KW and less than or equal to 560 KW and a displacement of less than 10 liters per cylinder and is a 2007 model year and later must comply with an NMHC+NO _x emission limit of 4.0 g/KW-hr, as stated in 40 CFR 60.4202(a)(2) and 40 CFR 1039-Appendix I.			
AIR-1	EU	60IIII	PM	40 CFR Part 60, Subpart IIII	§ 60.4205(b) § 1039-Appendix I § 60.4202(a)(2) § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f)	Owners and operators of emergency stationary CI ICE, that are not fire pump engines, with a maximum engine power greater than or equal to 130 KW and less than or equal to 2237 KW and a displacement of less than 10 liters per cylinder and is a 2007 model year and later must comply with a PM emission limit of 0.20 g/KW-hr, as stated in 40 CFR 60.4202(a)(2) and 40 CFR 1039-Appendix I.	§ 60.4209(a)	§ 60.4214(b)	[G]§ 60.4214(d)
AIR-1	EU	63ZZZZ	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(c)	Stationary RICE subject to Regulations under 40 CFR Part 60. An affected source that meets any of the criteria in paragraphs (c)(1) through (7) of this section must meet the requirements of this part by meeting the	None	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						requirements of 40 CFR part 60 subpart IIII, for compression ignition engines or 40 CFR part 60 subpart JJJJ, for spark ignition engines as applicable. No further requirements apply for such engines under this part.			
COMPFUG2	EU	60KKK-003	VOC	40 CFR Part 60, Subpart KKK	§ 60.632(a) § 60.482-1(a) § 60.482-1(b) § 60.482-8(a) § 60.482-8(a)(2) § 60.482-8(b) § 60.482-8(c)(1) § 60.482-8(c)(2) § 60.482-8(d) § 60.482-9(a) § 60.482-9(b) § 60.486(k)	Comply with the requirements for connectors as stated in §60.482-8, except as provided in §60.633.	§ 60.482-8(a)(1) § 60.485(a) [G]§ 60.485(b) § 60.485(d)(2) § 60.485(d)(3) § 60.485(f) § 60.632(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.636(b) [G]§ 60.636(c)
COMPFUG2	EU	60KKK-003	VOC	40 CFR Part 60, Subpart KKK	§ 60.632(a) § 60.482-1(a) § 60.482-1(b) § 60.482-7(b) § 60.482-7(d)(1) § 60.482-7(d)(2) [G]§ 60.482-7(e) [G]§ 60.482-7(f) [G]§ 60.482-7(g) [G]§ 60.482-7(h) § 60.482-9(a) § 60.482-9(b) [G]§ 60.482-9(c) § 60.482-9(e) § 60.482-9(f) § 60.486(k)	Comply with the requirements for valves in gas/vapor service as stated in §60.482-7 and §60.482-1(a), (b) and (d), except as provided in §60.633.	§ 60.482-7(a)(1) [G]§ 60.482-7(a)(2) § 60.482-7(c)(1)(i) § 60.482-7(c)(1)(ii) § 60.482-7(c)(2) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) § 60.485(d)(2) § 60.485(d)(3) § 60.485(f) § 60.632(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.636(b) [G]§ 60.636(c)
COMPFUG2	EU	60KKK-	VOC	40 CFR Part 60,	§ 60.632(a)	Comply with the	§ 60.482-4(b)(2)	[G]§ 60.486(a)	§ 60.487(a)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		003		Subpart KKK	§ 60.482-1(a) § 60.482-1(b) § 60.482-4(a) § 60.482-4(b)(1) § 60.482-4(c) § 60.482-4(d)(1) § 60.482-4(d)(2) § 60.482-9(a) § 60.482-9(b) § 60.486(k) [G]§ 60.633(b)(3)	requirements for pressure relief devices in gas/vapor service as stated in §60.482-4 and 60.482-1(a), (b) and (d), except as provided in §60.633.	§ 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) § 60.485(d)(2) § 60.485(d)(3) § 60.485(f) § 60.632(d) § 60.633(b)(1) § 60.633(b)(2) [G]§ 60.633(b)(3) [G]§ 60.633(b)(4)	§ 60.486(e) § 60.486(e)(1) § 60.486(e)(3) [G]§ 60.486(e)(4) § 60.486(j) § 60.633(b)(1) [G]§ 60.633(b)(4) [G]§ 60.635(b)	[G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.636(b) [G]§ 60.636(c)
COMPFUG2	EU	60KKK-003	VOC	40 CFR Part 60, Subpart KKK	§ 60.633(f)	Reciprocating compressors in wet gas service are exempt from the compressor control requirements of §60.482-3.	None	§ 60.486(j) § 60.635(c)	None
COMPFUG3	EU	60KKK-002	VOC	40 CFR Part 60, Subpart KKK	§ 60.632(a) § 60.482-1(a) § 60.482-1(b) § 60.482-7(b) § 60.482-7(d)(1) § 60.482-7(d)(2) [G]§ 60.482-7(e) [G]§ 60.482-7(f) [G]§ 60.482-7(g) [G]§ 60.482-7(h) § 60.482-9(a) § 60.482-9(b) [G]§ 60.482-9(c) § 60.482-9(e) § 60.482-9(f) § 60.486(k)	Comply with the requirements for valves in gas/vapor service as stated in §60.482-7 and §60.482-1(a), (b) and (d), except as provided in §60.633.	§ 60.482-7(a)(1) [G]§ 60.482-7(a)(2) § 60.482-7(c)(1)(i) § 60.482-7(c)(1)(ii) § 60.482-7(c)(2) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) § 60.485(d)(2) § 60.485(d)(3) § 60.485(f) § 60.632(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.636(b) [G]§ 60.636(c)
COMPFUG3	EU	60KKK-002	VOC	40 CFR Part 60, Subpart KKK	§ 60.632(a) § 60.482-1(a) § 60.482-1(b) § 60.482-6(a)(1) § 60.482-6(a)(2) § 60.482-6(b)	Comply with the requirements for open-ended valves or lines as stated in §60.482-6 and §60.482-1(a), (b) and (d), except as provided in	§ 60.485(a) [G]§ 60.485(b) § 60.485(d)(2) § 60.485(d)(3) § 60.485(f) § 60.632(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.636(b) [G]§ 60.636(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.482-6(c) § 60.482-6(d) § 60.482-6(e) § 60.482-9(a) § 60.482-9(b) [G]§ 60.482-9(c) § 60.482-9(e) § 60.482-9(f) § 60.486(k)	§60.633.			
COMPFUG3	EU	60KKK-002	VOC	40 CFR Part 60, Subpart KKK	§ 60.632(a) § 60.482-1(a) § 60.482-1(b) § 60.482-8(a) § 60.482-8(a)(2) § 60.482-8(b) § 60.482-8(c)(1) § 60.482-8(c)(2) § 60.482-8(d) § 60.482-9(a) § 60.482-9(b) § 60.486(k)	Comply with the requirements for connectors as stated in §60.482-8, except as provided in §60.633.	§ 60.482-8(a)(1) § 60.485(a) [G]§ 60.485(b) § 60.485(d)(2) § 60.485(d)(3) § 60.485(f) § 60.632(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.636(b) [G]§ 60.636(c)
COMPFUG3	EU	60KKK-002	VOC	40 CFR Part 60, Subpart KKK	§ 60.633(f)	Reciprocating compressors in wet gas service are exempt from the compressor control requirements of §60.482-3.	None	§ 60.486(j) § 60.635(c)	None
COMPFUG3	EU	60KKK-002	VOC	40 CFR Part 60, Subpart KKK	§ 60.632(a) § 60.482-1(a) § 60.482-1(b) § 60.482-2(b)(1) [G]§ 60.482-2(b)(2) § 60.482-2(c)(1) [G]§ 60.482-2(c)(2) § 60.482-2(d) [G]§ 60.482-2(d)(1) § 60.482-2(d)(2) § 60.482-2(d)(3) [G]§ 60.482-2(d)(4)	Comply with the requirements for pumps in light liquid service as stated in §60.482-2 and §60.482-1(a), (b) and (d), except as provided in §60.633.	[G]§ 60.482-2(a) [G]§ 60.482-2(b)(2) [G]§ 60.482-2(d)(4) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) § 60.485(d)(2) § 60.485(d)(3) [G]§ 60.485(e) § 60.485(f) § 60.632(d) [G]§ 60.633(h)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) [G]§ 60.486(h) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.636(b) [G]§ 60.636(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 60.482-2(d)(5) [G]§ 60.482-2(d)(6) [G]§ 60.482-2(e) § 60.482-2(f) [G]§ 60.482-2(g) § 60.482-2(h) § 60.482-9(a) § 60.482-9(b) [G]§ 60.482-9(d) § 60.482-9(f) § 60.486(k)				
COMPFUG3	EU	60KKK-002	VOC	40 CFR Part 60, Subpart KKK	§ 60.632(a) § 60.482-1(a) § 60.482-1(b) § 60.482-4(a) § 60.482-4(b)(1) § 60.482-4(c) § 60.482-4(d)(1) § 60.482-4(d)(2) § 60.482-9(a) § 60.482-9(b) § 60.486(k) [G]§ 60.633(b)(3)	Comply with the requirements for pressure relief devices in gas/vapor service as stated in §60.482-4 and 60.482-1(a), (b) and (d), except as provided in §60.633.	§ 60.482-4(b)(2) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) § 60.485(d)(2) § 60.485(d)(3) § 60.485(f) § 60.632(d) § 60.633(b)(1) § 60.633(b)(2) [G]§ 60.633(b)(3) [G]§ 60.633(b)(4)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(3) [G]§ 60.486(e)(4) § 60.486(j) § 60.633(b)(1) [G]§ 60.633(b)(4) [G]§ 60.635(b)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.636(b) [G]§ 60.636(c)
COMPFUG5	EU	60KKK-004	VOC	40 CFR Part 60, Subpart KKK	§ 60.632(a) § 60.482-1(a) § 60.482-1(b) § 60.482-4(a) § 60.482-4(b)(1) § 60.482-4(c) § 60.482-4(d)(1) § 60.482-4(d)(2) § 60.482-9(a) § 60.482-9(b) § 60.486(k) [G]§ 60.633(b)(3)	Comply with the requirements for pressure relief devices in gas/vapor service as stated in §60.482-4 and 60.482-1(a), (b) and (d), except as provided in §60.633.	§ 60.482-4(b)(2) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) § 60.485(d)(2) § 60.485(d)(3) § 60.485(f) § 60.632(d) § 60.633(b)(1) § 60.633(b)(2) [G]§ 60.633(b)(3) [G]§ 60.633(b)(4)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(3) [G]§ 60.486(e)(4) § 60.486(j) § 60.633(b)(1) [G]§ 60.633(b)(4) [G]§ 60.635(b)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.636(b) [G]§ 60.636(c)
COMPFUG5	EU	60KKK-004	VOC	40 CFR Part 60, Subpart KKK	§ 60.632(a) § 60.482-1(a) § 60.482-1(b)	Comply with the requirements for valves in gas/vapor service as stated	§ 60.482-7(a)(1) [G]§ 60.482-7(a)(2) § 60.482-7(c)(1)(i)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.482-7(b) § 60.482-7(d)(1) § 60.482-7(d)(2) [G]§ 60.482-7(e) [G]§ 60.482-7(f) [G]§ 60.482-7(g) [G]§ 60.482-7(h) § 60.482-9(a) § 60.482-9(b) [G]§ 60.482-9(c) § 60.482-9(e) § 60.482-9(f) § 60.486(k)	in §60.482-7 and §60.482-1(a), (b) and (d), except as provided in §60.633.	§ 60.482-7(c)(1)(ii) § 60.482-7(c)(2) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) § 60.485(d)(2) § 60.485(d)(3) § 60.485(f) § 60.632(d)	§ 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) § 60.486(j)	§ 60.487(e) § 60.636(b) [G]§ 60.636(c)
COMPFUG5	EU	60KKK-004	VOC	40 CFR Part 60, Subpart KKK	§ 60.632(a) § 60.482-1(a) § 60.482-1(b) § 60.482-8(a) § 60.482-8(a)(2) § 60.482-8(b) § 60.482-8(c)(1) § 60.482-8(c)(2) § 60.482-8(d) § 60.482-9(a) § 60.482-9(b) § 60.486(k)	Comply with the requirements for connectors as stated in §60.482-8, except as provided in §60.633.	§ 60.482-8(a)(1) § 60.485(a) [G]§ 60.485(b) § 60.485(d)(2) § 60.485(d)(3) § 60.485(f) § 60.632(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.636(b) [G]§ 60.636(c)
D1	EU	60GG-001	NO _x	40 CFR Part 60, Subpart GG	§ 60.332(a)(2) § 60.332(a)(3) § 60.332(k)	No owner or operator shall discharge into the atmosphere from any stationary gas turbine, any gases which contain nitrogen oxides in excess of the amount as determined from the specified equation.	[G]§ 60.335(a) § 60.335(b)(1) § 60.335(b)(2) § 60.335(c)(1) ** See Periodic Monitoring Summary	None	None
D1	EU	60GG-001	SO ₂	40 CFR Part 60, Subpart GG	§ 60.333(b)	No stationary gas turbine shall burn any fuel which contains sulfur in excess of 0.8% by weight.	§ 60.334(h) [G]§ 60.334(h)(3)	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
D2	EU	60GG-001	NO _x	40 CFR Part 60, Subpart GG	§ 60.332(a)(2) § 60.332(a)(3) § 60.332(k)	No owner or operator shall discharge into the atmosphere from any stationary gas turbine, any gases which contain nitrogen oxides in excess of the amount as determined from the specified equation.	[G]§ 60.335(a) § 60.335(b)(1) § 60.335(b)(2) § 60.335(c)(1) ** See Periodic Monitoring Summary	None	None
D2	EU	60GG-001	SO ₂	40 CFR Part 60, Subpart GG	§ 60.333(b)	No stationary gas turbine shall burn any fuel which contains sulfur in excess of 0.8% by weight.	§ 60.334(h) [G]§ 60.334(h)(3)	None	None
DGA4-FUG	EU	60KKK-005	VOC	40 CFR Part 60, Subpart KKK	§ 60.632(a) § 60.482-1(a) § 60.482-1(b) § 60.482-8(a) § 60.482-8(a)(2) § 60.482-8(b) § 60.482-8(c)(1) § 60.482-8(c)(2) § 60.482-8(d) § 60.482-9(a) § 60.482-9(b) § 60.486(k)	Comply with the requirements for connectors as stated in §60.482-8, except as provided in §60.633.	§ 60.482-8(a)(1) § 60.485(a) [G]§ 60.485(b) § 60.485(d)(2) § 60.485(d)(3) § 60.485(f) § 60.632(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.636(b) [G]§ 60.636(c)
DGA4-FUG	EU	60KKK-005	VOC	40 CFR Part 60, Subpart KKK	§ 60.632(a) § 60.482-1(a) § 60.482-1(b) § 60.482-7(b) § 60.482-7(d)(1) § 60.482-7(d)(2) [G]§ 60.482-7(e) [G]§ 60.482-7(f) [G]§ 60.482-7(g) [G]§ 60.482-7(h) § 60.482-9(a) § 60.482-9(b) [G]§ 60.482-9(c) § 60.482-9(e)	Comply with the requirements for valves in gas/vapor service as stated in §60.482-7 and §60.482-1(a), (b) and (d), except as provided in §60.633.	§ 60.482-7(a)(1) [G]§ 60.482-7(a)(2) § 60.482-7(c)(1)(i) § 60.482-7(c)(1)(ii) § 60.482-7(c)(2) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) § 60.485(d)(2) § 60.485(d)(3) § 60.485(f) § 60.632(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.636(b) [G]§ 60.636(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.482-9(f) § 60.486(k)				
DGA4-FUG	EU	60KKK-005	VOC	40 CFR Part 60, Subpart KKK	§ 60.632(a) § 60.482-1(a) § 60.482-1(b) § 60.482-6(a)(1) § 60.482-6(a)(2) § 60.482-6(b) § 60.482-6(c) § 60.482-6(d) § 60.482-6(e) § 60.482-9(a) § 60.482-9(b) [G]§ 60.482-9(c) § 60.482-9(e) § 60.482-9(f) § 60.486(k)	Comply with the requirements for open-ended valves or lines as stated in §60.482-6 and §60.482-1(a), (b) and (d), except as provided in §60.633.	§ 60.485(a) [G]§ 60.485(b) § 60.485(d)(2) § 60.485(d)(3) § 60.485(f) § 60.632(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.636(b) [G]§ 60.636(c)
DGA4-FUG	EU	60KKK-005	VOC	40 CFR Part 60, Subpart KKK	§ 60.632(a) § 60.482-1(a) § 60.482-1(b) § 60.482-4(a) § 60.482-4(b)(1) § 60.482-4(c) § 60.482-4(d)(1) § 60.482-4(d)(2) § 60.482-9(a) § 60.482-9(b) § 60.486(k) [G]§ 60.633(b)(3)	Comply with the requirements for pressure relief devices in gas/vapor service as stated in §60.482-4 and 60.482-1(a), (b) and (d), except as provided in §60.633.	§ 60.482-4(b)(2) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) § 60.485(d)(2) § 60.485(d)(3) § 60.485(f) § 60.632(d) § 60.633(b)(1) § 60.633(b)(2) [G]§ 60.633(b)(3) [G]§ 60.633(b)(4)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(e)(3) [G]§ 60.486(e)(4) § 60.486(j) § 60.633(b)(1) [G]§ 60.633(b)(4) [G]§ 60.635(b)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.636(b) [G]§ 60.636(c)
DGA4-FUG	EU	60KKK-005	VOC	40 CFR Part 60, Subpart KKK	§ 60.632(a) § 60.482-1(a) § 60.482-1(b) § 60.482-8(a) § 60.482-8(a)(2) § 60.482-8(b) § 60.482-8(c)(1) § 60.482-8(c)(2) § 60.482-8(d)	Comply with the requirements for valves in heavy liquid service as stated in §60.482-8, except as provided in §60.633.	§ 60.482-8(a)(1) § 60.485(a) [G]§ 60.485(b) § 60.485(d)(2) § 60.485(d)(3) [G]§ 60.485(e) § 60.485(f) § 60.632(d) [G]§ 60.633(h)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.636(b) [G]§ 60.636(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.482-9(a) § 60.482-9(b) [G]§ 60.482-9(c) § 60.482-9(e) § 60.482-9(f) § 60.486(k)				
DGA4-FUG	EU	60KKK-005	VOC	40 CFR Part 60, Subpart KKK	§ 60.632(a) § 60.482-1(a) § 60.482-1(b) § 60.482-8(a) § 60.482-8(a)(2) § 60.482-8(b) § 60.482-8(c)(1) § 60.482-8(c)(2) § 60.482-8(d) § 60.482-9(a) § 60.482-9(b) [G]§ 60.482-9(d) § 60.482-9(f) § 60.486(k)	Comply with the requirements for pumps in heavy liquid service as stated in §60.482-8, except as provided in §60.633.	§ 60.482-8(a)(1) § 60.485(a) [G]§ 60.485(b) § 60.485(d)(2) § 60.485(d)(3) [G]§ 60.485(e) § 60.485(f) § 60.632(d) [G]§ 60.633(h)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.636(b) [G]§ 60.636(c)
E1-E	EU	60GG-001	NO _x	40 CFR Part 60, Subpart GG	§ 60.332(a)(2) § 60.332(a)(3) § 60.332(k)	No owner or operator shall discharge into the atmosphere from any stationary gas turbine, any gases which contain nitrogen oxides in excess of the amount as determined from the specified equation.	[G]§ 60.335(a) § 60.335(b)(2) § 60.335(b)(3) ** See Periodic Monitoring Summary	None	None
E1-E	EU	60GG-001	SO ₂	40 CFR Part 60, Subpart GG	§ 60.333(b)	No stationary gas turbine shall burn any fuel which contains sulfur in excess of 0.8% by weight.	§ 60.334(h) [G]§ 60.334(h)(3)	None	None
E1-W	EU	60GG-001	NO _x	40 CFR Part 60, Subpart GG	§ 60.332(a)(2) § 60.332(a)(3) § 60.332(k)	No owner or operator shall discharge into the atmosphere from any stationary gas turbine, any gases which contain	[G]§ 60.335(a) § 60.335(b)(2) § 60.335(b)(3) ** See Periodic Monitoring	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						nitrogen oxides in excess of the amount as determined from the specified equation.	Summary		
E1-W	EU	60GG-001	SO ₂	40 CFR Part 60, Subpart GG	§ 60.333(b)	No stationary gas turbine shall burn any fuel which contains sulfur in excess of 0.8% by weight.	§ 60.334(h) [G]§ 60.334(h)(3)	None	None
FL-2	CD	60A-002	Opacity	40 CFR Part 60, Subpart A	§ 60.18(b) § 60.18(c)(1) § 60.18(c)(2) § 60.18(c)(3)(ii) § 60.18(c)(5) § 60.18(c)(6) § 60.18(e)	Flares shall comply with paragraphs (c)-(f) of § 60.18.	§ 60.18(d) § 60.18(f)(1) § 60.18(f)(2) § 60.18(f)(3) § 60.18(f)(6)	None	None
FUG-NGP	EU	60KKK-008	VOC	40 CFR Part 60, Subpart KKK	§ 60.633(f)	Reciprocating compressors in wet gas service are exempt from the compressor control requirements of §60.482-3.	None	§ 60.486(j) § 60.635(c)	None
FUG-NGP	EU	60KKK-008	VOC	40 CFR Part 60, Subpart KKK	§ 60.632(a) § 60.482-1(a) § 60.482-1(b) § 60.482-8(a) § 60.482-8(a)(2) § 60.482-8(b) § 60.482-8(c)(1) § 60.482-8(c)(2) § 60.482-8(d) § 60.482-9(a) § 60.482-9(b) § 60.486(k)	Comply with the requirements for connectors as stated in §60.482-8, except as provided in §60.633.	§ 60.482-8(a)(1) § 60.485(a) [G]§ 60.485(b) § 60.485(d)(2) § 60.485(d)(3) § 60.485(f) § 60.632(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.636(b) [G]§ 60.636(c)
FUG-NGP	EU	60KKK-008	VOC	40 CFR Part 60, Subpart KKK	§ 60.632(a) § 60.482-1(a) § 60.482-1(b) § 60.482-2(b)(1) [G]§ 60.482-2(b)(2)	Comply with the requirements for pumps in light liquid service as stated in §60.482-2 and §60.482-1(a), (b) and (d), except as	[G]§ 60.482-2(a) [G]§ 60.482-2(b)(2) [G]§ 60.482-2(d)(4) § 60.485(a) [G]§ 60.485(b)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.636(b)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.482-2(c)(1) [G]§ 60.482-2(c)(2) § 60.482-2(d) [G]§ 60.482-2(d)(1) § 60.482-2(d)(2) § 60.482-2(d)(3) [G]§ 60.482-2(d)(4) [G]§ 60.482-2(d)(5) [G]§ 60.482-2(d)(6) [G]§ 60.482-2(e) § 60.482-2(f) [G]§ 60.482-2(g) § 60.482-2(h) § 60.482-9(a) § 60.482-9(b) [G]§ 60.482-9(d) § 60.482-9(f) § 60.486(k)	provided in §60.633.	[G]§ 60.485(c) § 60.485(d)(2) § 60.485(d)(3) [G]§ 60.485(e) § 60.485(f) § 60.632(d) [G]§ 60.633(h)	[G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) [G]§ 60.486(h) § 60.486(j)	[G]§ 60.636(c)
FUG-NGP	EU	60KKK-008	VOC	40 CFR Part 60, Subpart KKK	§ 60.632(a) § 60.482-1(a) § 60.482-1(b) § 60.482-6(a)(1) § 60.482-6(a)(2) § 60.482-6(b) § 60.482-6(c) § 60.482-6(d) § 60.482-6(e) § 60.482-9(a) § 60.482-9(b) [G]§ 60.482-9(c) § 60.482-9(e) § 60.482-9(f) § 60.486(k)	Comply with the requirements for open-ended valves or lines as stated in §60.482-6 and §60.482-1(a), (b) and (d), except as provided in §60.633.	§ 60.485(a) [G]§ 60.485(b) § 60.485(d)(2) § 60.485(d)(3) § 60.485(f) § 60.632(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.636(b) [G]§ 60.636(c)
FUG-NGP	EU	60KKK-008	VOC	40 CFR Part 60, Subpart KKK	§ 60.632(a) § 60.482-1(a) § 60.482-1(b) § 60.482-8(a) § 60.482-8(a)(2)	Comply with the requirements for pressure relief devices in light liquid service as stated in §60.482-8, except as	§ 60.482-8(a)(1) § 60.485(a) [G]§ 60.485(b) § 60.485(d)(2) § 60.485(d)(3)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.636(b)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.482-8(b) § 60.482-8(c)(1) § 60.482-8(c)(2) § 60.482-8(d) § 60.482-9(a) § 60.482-9(b) § 60.486(k)	provided in §60.633.	[G]§ 60.485(e) § 60.485(f) § 60.632(d) [G]§ 60.633(h)	§ 60.486(j)	[G]§ 60.636(c)
FUG-NGP	EU	60KKK-008	VOC	40 CFR Part 60, Subpart KKK	§ 60.632(a) § 60.482-1(a) § 60.482-1(b) § 60.482-7(b) § 60.482-7(d)(1) § 60.482-7(d)(2) [G]§ 60.482-7(e) [G]§ 60.482-7(f) [G]§ 60.482-7(g) [G]§ 60.482-7(h) § 60.482-9(a) § 60.482-9(b) [G]§ 60.482-9(c) § 60.482-9(e) § 60.482-9(f) § 60.486(k)	Comply with the requirements for valves in light liquid service as stated in §60.482-7 and §60.482-1(a), (b) and (d), except as provided in §60.633.	§ 60.482-7(a)(1) [G]§ 60.482-7(a)(2) § 60.482-7(c)(1)(i) § 60.482-7(c)(1)(ii) § 60.482-7(c)(2) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) § 60.485(d)(2) § 60.485(d)(3) [G]§ 60.485(e) § 60.485(f) § 60.632(d) [G]§ 60.633(h)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.636(b) [G]§ 60.636(c)
FUG-NGP	EU	60KKK-008	VOC	40 CFR Part 60, Subpart KKK	§ 60.632(a) § 60.482-1(a) § 60.482-1(b) § 60.482-7(b) § 60.482-7(d)(1) § 60.482-7(d)(2) [G]§ 60.482-7(e) [G]§ 60.482-7(f) [G]§ 60.482-7(g) [G]§ 60.482-7(h) § 60.482-9(a) § 60.482-9(b) [G]§ 60.482-9(c) § 60.482-9(e) § 60.482-9(f)	Comply with the requirements for valves in gas/vapor service as stated in §60.482-7 and §60.482-1(a), (b) and (d), except as provided in §60.633.	§ 60.482-7(a)(1) [G]§ 60.482-7(a)(2) § 60.482-7(c)(1)(i) § 60.482-7(c)(1)(ii) § 60.482-7(c)(2) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) § 60.485(d)(2) § 60.485(d)(3) § 60.485(f) § 60.632(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.636(b) [G]§ 60.636(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.486(k)				
FWP	EU	60III-01	NMHC and NO _x	40 CFR Part 60, Subpart IIII	§ 60.4205(c)-Table 4 § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f)	Owners and operators of emergency stationary fire pump CI ICE with a maximum engine power greater than or equal to 130 KW and less than or equal to 560 KW and a displacement of less than 30 liters per cylinder and is a 2009 model year and later must comply with an NMHC+NO _x emission limit of 4.0 g/KW-hr, as listed in Table 4 to this subpart.	None	None	[G]§ 60.4214(d)
FWP	EU	60III-01	PM	40 CFR Part 60, Subpart IIII	§ 60.4205(c)-Table 4 § 60.4206 § 60.4207(b) [G]§ 60.4211(a) § 60.4211(c) [G]§ 60.4211(f)	Owners and operators of emergency stationary fire pump CI ICE with a maximum engine power greater than or equal to 130 KW and less than or equal to 560 KW and a displacement of less than 30 liters per cylinder and is a 2009 model year and later must comply with a PM emission limit of 0.20 g/KW-hr, as listed in Table 4 to this subpart.	None	None	[G]§ 60.4214(d)
FWP	EU	63ZZZZ-01	112(B) HAPS	40 CFR Part 63, Subpart ZZZZ	§ 63.6590(c)	Stationary RICE subject to Regulations under 40 CFR Part 60. An affected source that meets any of the criteria in paragraphs (c)(1) through (7) of this section must meet the requirements of this part by meeting the requirements of 40 CFR	None	None	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						part 60 subpart IIII, for compression ignition engines or 40 CFR part 60 subpart JJJJ, for spark ignition engines as applicable. No further requirements apply for such engines under this part.			
INLET-FUG	EU	60KKK-006	VOC	40 CFR Part 60, Subpart KKK	§ 60.632(a) § 60.482-1(a) § 60.482-1(b) § 60.482-7(b) § 60.482-7(d)(1) § 60.482-7(d)(2) [G]§ 60.482-7(e) [G]§ 60.482-7(f) [G]§ 60.482-7(g) [G]§ 60.482-7(h) § 60.482-9(a) § 60.482-9(b) [G]§ 60.482-9(c) § 60.482-9(e) § 60.482-9(f) § 60.486(k)	Comply with the requirements for valves in light liquid service as stated in §60.482-7 and §60.482-1(a), (b) and (d), except as provided in §60.633.	§ 60.482-7(a)(1) [G]§ 60.482-7(a)(2) § 60.482-7(c)(1)(i) § 60.482-7(c)(1)(ii) § 60.482-7(c)(2) § 60.485(a) [G]§ 60.485(b) [G]§ 60.485(c) § 60.485(d)(2) § 60.485(d)(3) [G]§ 60.485(e) § 60.485(f) § 60.632(d) [G]§ 60.633(h)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) [G]§ 60.486(e)(2) [G]§ 60.486(e)(4) [G]§ 60.486(f) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.636(b) [G]§ 60.636(c)
INLET-FUG	EU	60KKK-006	VOC	40 CFR Part 60, Subpart KKK	§ 60.632(a) § 60.482-1(a) § 60.482-1(b) § 60.482-8(a) § 60.482-8(a)(2) § 60.482-8(b) § 60.482-8(c)(1) § 60.482-8(c)(2) § 60.482-8(d) § 60.482-9(a) § 60.482-9(b) § 60.486(k)	Comply with the requirements for connectors as stated in §60.482-8, except as provided in §60.633.	§ 60.482-8(a)(1) § 60.485(a) [G]§ 60.485(b) § 60.485(d)(2) § 60.485(d)(3) § 60.485(f) § 60.632(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.636(b) [G]§ 60.636(c)
INLET-FUG	EU	60KKK-006	VOC	40 CFR Part 60, Subpart KKK	§ 60.632(a) § 60.482-1(a)	Comply with the requirements for open-	§ 60.485(a) [G]§ 60.485(b)	[G]§ 60.486(a) § 60.486(e)	§ 60.487(a) [G]§ 60.487(b)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 60.482-1(b) § 60.482-6(a)(1) § 60.482-6(a)(2) § 60.482-6(b) § 60.482-6(c) § 60.482-6(d) § 60.482-6(e) § 60.482-9(a) § 60.482-9(b) [G]§ 60.482-9(c) § 60.482-9(e) § 60.482-9(f) § 60.486(k)	ended valves or lines as stated in §60.482-6 and §60.482-1(a), (b) and (d), except as provided in §60.633.	§ 60.485(d)(2) § 60.485(d)(3) § 60.485(f) § 60.632(d)	§ 60.486(e)(1) § 60.486(j)	[G]§ 60.487(c) § 60.487(e) § 60.636(b) [G]§ 60.636(c)
TEGDEHY	EU	63HH-1	112(B) HAPS	40 CFR Part 63, Subpart HH	§ 63.764(e)(1)(ii) § 63.764(a) § 63.764(e)(1) § 63.764(j) § 63.775(c)(8)	The owner or operator of an area source is exempt from the requirements of §63.764(d) when the actual average emissions of benzene from the glycol dehydration unit process vent to the atmosphere < 0.90 megagram/yr, as determined by the procedures specified in §63.772(b)(2) of this subpart.	[G]§ 63.772(b)(2)	§ 63.774(d)(1) § 63.774(d)(1)(ii)	None
TREAT-FUG	EU	60KKK-007	VOC	40 CFR Part 60, Subpart KKK	§ 60.632(a) § 60.482-1(a) § 60.482-1(b) § 60.482-8(a) § 60.482-8(a)(2) § 60.482-8(b) § 60.482-8(c)(1) § 60.482-8(c)(2) § 60.482-8(d) § 60.482-9(a) § 60.482-9(b) § 60.486(k)	Comply with the requirements for connectors as stated in §60.482-8, except as provided in §60.633.	§ 60.482-8(a)(1) § 60.485(a) [G]§ 60.485(b) § 60.485(d)(2) § 60.485(d)(3) § 60.485(f) § 60.632(d)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.636(b) [G]§ 60.636(c)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
TREAT-FUG	EU	60KKK-007	VOC	40 CFR Part 60, Subpart KKK	§ 60.632(a) § 60.482-1(a) § 60.482-1(b) § 60.482-8(a) § 60.482-8(a)(2) § 60.482-8(b) § 60.482-8(c)(1) § 60.482-8(c)(2) § 60.482-8(d) § 60.482-9(a) § 60.482-9(b) [G]§ 60.482-9(c) § 60.482-9(e) § 60.482-9(f) § 60.486(k)	Comply with the requirements for valves in heavy liquid service as stated in §60.482-8, except as provided in §60.633.	§ 60.482-8(a)(1) § 60.485(a) [G]§ 60.485(b) § 60.485(d)(2) § 60.485(d)(3) [G]§ 60.485(e) § 60.485(f) § 60.632(d) [G]§ 60.633(h)	[G]§ 60.486(a) [G]§ 60.486(b) [G]§ 60.486(c) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.636(b) [G]§ 60.636(c)
TREAT-FUG	EU	60KKK-007	VOC	40 CFR Part 60, Subpart KKK	§ 60.632(a) § 60.482-1(a) § 60.482-1(b) § 60.482-6(a)(1) § 60.482-6(a)(2) § 60.482-6(b) § 60.482-6(c) § 60.482-6(d) § 60.482-6(e) § 60.482-9(a) § 60.482-9(b) [G]§ 60.482-9(c) § 60.482-9(e) § 60.482-9(f) § 60.486(k)	Comply with the requirements for open-ended valves or lines as stated in §60.482-6 and §60.482-1(a), (b) and (d), except as provided in §60.633.	§ 60.485(a) [G]§ 60.485(b) § 60.485(d)(2) § 60.485(d)(3) § 60.485(f) § 60.632(d)	[G]§ 60.486(a) § 60.486(e) § 60.486(e)(1) § 60.486(j)	§ 60.487(a) [G]§ 60.487(b) [G]§ 60.487(c) § 60.487(e) § 60.636(b) [G]§ 60.636(c)
U1	EU	60KKKK-2	NO _x	40 CFR Part 60, Subpart KKKK	§ 60.4320(a)-Table 1 § 60.4320(a) § 60.4320(b) § 60.4333(a)	Modified or reconstructed turbine with a heat input at peak load of 50 MMBtu/h or less must meet the nitrogen oxides emission standard of 1,100 ng/J of useful output (8.7 lb/MWh).	§ 60.4340(a) [G]§ 60.4400(a) § 60.4400(b) § 60.4400(b)(1) § 60.4400(b)(4) § 60.4400(b)(6)	None	§ 60.4375(b)
U1	EU	60KKKK-2	SO ₂	40 CFR Part 60,	§ 60.4330(a)(2)	You must not burn in the	§ 60.4365	§ 60.4365(b)	§ 60.4375(a)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				Subpart KKKK	§ 60.4333(a)	subject stationary combustion turbine any fuel which contains total potential sulfur emissions in excess of 26 ng SO ₂ /J (0.060 lb SO ₂ /MMBtu) heat input. If your turbine simultaneously fires multiple fuels, each fuel must meet this requirement.	§ 60.4365(b) § 60.4415(a) § 60.4415(a)(2) § 60.4415(a)(2)(ii)		
U1	EU	63YYYY-2	Formaldehyde	40 CFR Part 63, Subpart YYYY	§ 63.6100-Table 1.1 § 63.6100 § 63.6100-Table 2.2 § 63.6105(a) § 63.6105(c) § 63.6120(e) § 63.6130(a) § 63.6130(a)-Table 4 § 63.6140(a) § 63.6165	For each new or reconstructed stationary combustion turbine described in §63.6100, which is a lean premix gas-fired stationary combustion turbine as defined in this subpart, must limit the concentration of formaldehyde to 91 ppbvd or less at 15% O ₂ .	§ 63.6110(a) § 63.6115 § 63.6120(a) § 63.6120(a)-Table 3.a § 63.6120(a)-Table 3.b § 63.6120(a)-Table 3.c § 63.6120(a)-Table 3.d § 63.6120(b) § 63.6120(c) § 63.6120(d) § 63.6120(e) § 63.6125(b) § 63.6125(e) § 63.6135(a) § 63.6140(a)-Table 5.1 § 63.6140(a)-Table 5.2 § 63.6145(e) § 63.6145(f)	§ 63.6125(e) § 63.6135(b) § 63.6155(a) § 63.6155(a)(1) § 63.6155(a)(2) § 63.6155(a)(5) § 63.6155(a)(6) [G]§ 63.6155(a)(7) § 63.6155(c) § 63.6155(d) § 63.6160(a) § 63.6160(b) § 63.6160(c)	§ 63.6120(e) [G]§ 63.6120(f) § 63.6130(b) § 63.6140(b) § 63.6145(a) § 63.6145(b) § 63.6145(c) § 63.6145(e) § 63.6145(f) § 63.6150(a) § 63.6150(a)(1) § 63.6150(a)(2) § 63.6150(a)(3) [G]§ 63.6150(a)(5) § 63.6150(a)-Table 6.1 § 63.6150(a)-Table 6.3.1 § 63.6150(a)-Table 6.3.2 § 63.6150(a)-Table 6.3.3 [G]§ 63.6150(b) [G]§ 63.6150(d) [G]§ 63.6150(f) § 63.6150(g) [G]§ 63.6150(h) [G]§ 63.6150(i)

Additional Monitoring Requirements

Periodic Monitoring Summary 38

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: D1	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart GG	SOP Index No.: 60GG-001
Pollutant: NO _x	Main Standard: § 60.332(a)(2)
Monitoring Information	
Indicator: NO _x concentration	
Minimum Frequency: monthly	
Averaging Period: N/A	
Deviation Limit: 150 ppmv corrected to 15 % O ₂	
<p>Periodic Monitoring Text: Monitor and record the nitrogen oxide concentration in the exhaust stream using a portable analyzer to monitor nitrogen oxide. The portable analyzer shall be operated in accordance with the Environmental Protection Agency's, Office of Air Quality Planning & Standards, Emission Measurement Center Conditional Test Method - Determination of Oxygen, Carbon Monoxide, and Oxides of Nitrogen from Stationary Sources for Periodic Monitoring (Portable Electrochemical Analyzer Procedure) [CTM-034] (September 8, 1999). NO_x emissions shall be corrected/calculated in units of the underlying applicable emission limitation (grams per horsepower hour, pounds per MMBtu, pounds per hour).</p>	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: D2	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart GG	SOP Index No.: 60GG-001
Pollutant: NO _x	Main Standard: § 60.332(a)(2)
Monitoring Information	
Indicator: NO _x concentration	
Minimum Frequency: monthly	
Averaging Period: N/A	
Deviation Limit: 150 ppmv corrected to 15 % O ₂	
<p>Periodic Monitoring Text: Monitor and record the nitrogen oxide concentration in the exhaust stream using a portable analyzer to monitor nitrogen oxide. The portable analyzer shall be operated in accordance with the Environmental Protection Agency's, Office of Air Quality Planning & Standards, Emission Measurement Center Conditional Test Method - Determination of Oxygen, Carbon Monoxide, and Oxides of Nitrogen from Stationary Sources for Periodic Monitoring (Portable Electrochemical Analyzer Procedure) [CTM-034] (September 8, 1999). NO_x emissions shall be corrected/calculated in units of the underlying applicable emission limitation (grams per horsepower hour, pounds per MMBtu, pounds per hour).</p>	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: E1-E	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart GG	SOP Index No.: 60GG-001
Pollutant: NO _x	Main Standard: § 60.332(a)(2)
Monitoring Information	
Indicator: NO _x concentration	
Minimum Frequency: Monthly	
Averaging Period: N/A	
Deviation Limit: 150 ppmv corrected to 15 % O ₂	
<p>Periodic Monitoring Text: Monitor and record the nitrogen oxide concentration in the exhaust stream using a portable analyzer to monitor nitrogen oxide. The portable analyzer shall be operated in accordance with the Environmental Protection Agency's, Office of Air Quality Planning & Standards, Emission Measurement Center Conditional Test Method - Determination of Oxygen, Carbon Monoxide, and Oxides of Nitrogen from Stationary Sources for Periodic Monitoring (Portable Electrochemical Analyzer Procedure) [CTM-034] (September 8, 1999). NO_x emissions shall be corrected/calculated in units of the underlying applicable emission limitation (grams per horsepower hour, pounds per MMBtu, pounds per hour).</p>	

Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: E1-W	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart GG	SOP Index No.: 60GG-001
Pollutant: NO _x	Main Standard: § 60.332(a)(2)
Monitoring Information	
Indicator: NO _x concentration	
Minimum Frequency: Monthly	
Averaging Period: N/A	
Deviation Limit: 150 ppmv corrected to 15 % O ₂	
<p>Periodic Monitoring Text: Monitor and record the nitrogen oxide concentration in the exhaust stream using a portable analyzer to monitor nitrogen oxide. The portable analyzer shall be operated in accordance with the Environmental Protection Agency's, Office of Air Quality Planning & Standards, Emission Measurement Center Conditional Test Method - Determination of Oxygen, Carbon Monoxide, and Oxides of Nitrogen from Stationary Sources for Periodic Monitoring (Portable Electrochemical Analyzer Procedure) [CTM-034] (September 8, 1999). NO_x emissions shall be corrected/calculated in units of the underlying applicable emission limitation (grams per horsepower hour, pounds per MMBtu, pounds per hour).</p>	

Permit Shield

Permit Shield 43

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit / Group / Process ID No.	Group / Inclusive Units	Regulation	Basis of Determination
AT-1	N/A	40 CFR Part 60, Subpart Kb	Storage capacity is less than 75 cubic meters (19,813 gallons)
AT-2	N/A	40 CFR Part 60, Subpart Kb	Storage capacity is less than 75 cubic meters (19,813 gallons)
C10	N/A	40 CFR Part 60, Subpart JJJJ	Engine was constructed/modified/reconstructed prior to June 12, 2006.
C13	N/A	40 CFR Part 60, Subpart JJJJ	Engine was constructed/modified/reconstructed prior to June 12, 2006.
C14	N/A	40 CFR Part 60, Subpart JJJJ	Engine was constructed/modified/reconstructed prior to June 12, 2006.
C15	N/A	40 CFR Part 60, Subpart JJJJ	Engine was constructed/modified/reconstructed prior to June 12, 2006.
C16	N/A	40 CFR Part 60, Subpart JJJJ	Engine was constructed/modified/reconstructed prior to June 12, 2006.
C19	N/A	40 CFR Part 60, Subpart JJJJ	Engine was constructed/modified/reconstructed prior to June 12, 2006.
C21	N/A	40 CFR Part 60, Subpart JJJJ	Engine was constructed/modified/reconstructed prior to June 12, 2006.
C8	N/A	40 CFR Part 60, Subpart JJJJ	Engine was constructed/modified/reconstructed prior to June 12, 2006.
C9	N/A	40 CFR Part 60, Subpart JJJJ	Engine was constructed/modified/reconstructed prior to June 12, 2006.
COMPFUG1	N/A	40 CFR Part 60, Subpart KKK	Constructed, modified or reconstructed before January 20, 1984
CT-1	N/A	40 CFR Part 60, Subpart Kb	Storage capacity is less than 75 cubic meters

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit / Group / Process ID No.	Group / Inclusive Units	Regulation	Basis of Determination
			(19,813 gallons)
CT-2	N/A	40 CFR Part 60, Subpart Kb	Storage capacity is less than 75 cubic meters (19,813 gallons)
CT-3	N/A	40 CFR Part 60, Subpart Kb	Storage capacity is less than 75 cubic meters (19,813 gallons)
DEG1	N/A	40 CFR Part 63, Subpart T	Does not use any of the chemicals listed in 63.460(a)
DEG2	N/A	40 CFR Part 63, Subpart T	Does not use any of the chemicals listed in 63.460(a)
DGA3-FUG	N/A	40 CFR Part 60, Subpart KKK	Constructed, modified or reconstructed prior to January 20, 1984.
DT-1	N/A	40 CFR Part 60, Subpart Kb	Storage capacity is less than 75 cubic meters (19,813 gallons)
DT-2	N/A	40 CFR Part 60, Subpart Kb	Storage capacity is less than 75 cubic meters (19,813 gallons)
FL-1	N/A	40 CFR Part 60, Subpart A	Flare is not used to control a source subject to a Part 60 or Part 61 subpart.
FL-1	N/A	40 CFR Part 63, Subpart A	Flare is not used to control a source subject to a Part 63 subpart.
FL-2	N/A	40 CFR Part 63, Subpart A	Flare is not used to control a source subject to a Part 63 subpart.
G-4	N/A	40 CFR Part 60, Subpart Kb	Storage capacity is less than 75 cubic meters (19,000 gallons)
G-4	N/A	40 CFR Part 63, Subpart HH	This tank does not meet the definition of a storage vessel with the potential for flash

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit / Group / Process ID No.	Group / Inclusive Units	Regulation	Basis of Determination
			emissions. The GOR, API and throughput of the material stored are less than the thresholds cited under 63.761.
GLY	N/A	40 CFR Part 60, Subpart Kb	Storage capacity is less than 75 cubic meters (19,813 gallons)
LO-1	N/A	40 CFR Part 60, Subpart Kb	Storage capacity is less than 75 cubic meters (19,813 gallons)
LO-2	N/A	40 CFR Part 60, Subpart Kb	Storage capacity is less than 75 cubic meters (19,813 gallons)
LOAD	N/A	30 TAC Chapter 115, Loading and Unloading of VOC	Site is located in an attainment area, but not in a covered attainment county.
MT-1	N/A	40 CFR Part 60, Subpart Kb	Storage capacity is less than 75 cubic meters (19,813 gallons)
MT-2	N/A	40 CFR Part 60, Subpart Kb	Storage capacity is less than 75 cubic meters (19,813 gallons)
MT-3	N/A	40 CFR Part 60, Subpart Kb	Storage capacity is less than 75 cubic meters (19,813 gallons)
MT-4	N/A	40 CFR Part 60, Subpart Kb	Storage capacity is less than 75 cubic meters (19,813 gallons)
MT-5	N/A	40 CFR Part 60, Subpart Kb	Storage capacity is less than 75 cubic meters (19,813 gallons)
MT-6	N/A	40 CFR Part 60, Subpart Kb	Storage capacity is less than 75 cubic meters (19,813 gallons)
PRODGA	N/A	30 TAC Chapter 112, Sulfur Compounds	Process does not include a sulfur recovery unit.
PRODGA	N/A	40 CFR Part 60, Subpart LLL	Acid gas from this process is completely

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit / Group / Process ID No.	Group / Inclusive Units	Regulation	Basis of Determination
			reinjecting into the field and is not released to the atmosphere.
SV-00-301	N/A	40 CFR Part 60, Subpart Kb	Storage capacity is less than 75 cubic meters (19,813 gallons)
SV-00-302	N/A	40 CFR Part 60, Subpart Kb	Storage capacity is less than 75 cubic meters (19,813 gallons)
SV-00-610	N/A	40 CFR Part 60, Subpart Kb	Petroleum (other than crude oil) or condensate stored, processed, and/or treated prior to custody transfer and capacity is less than or equal to 420,000 gallons (1,589,873 liters)
SV-00-610	N/A	40 CFR Part 63, Subpart HH	This tank does not meet the definition of a storage vessel with the potential for flash emissions. The GOR, API and throughput of the material stored are less than the thresholds cited under 63.761.
SV-00-903	N/A	40 CFR Part 60, Subpart Kb	Storage capacity is less than 75 cubic meters (19,813 gallons)
SV-00-905	N/A	40 CFR Part 60, Subpart Kb	Storage capacity is less than 75 cubic meters (19,813 gallons)
SV-02-301	N/A	40 CFR Part 60, Subpart Kb	Storage capacity is less than 75 cubic meters (19,813 gallons)
SV-02-302	N/A	40 CFR Part 60, Subpart Kb	Storage capacity is less than 75 cubic meters (19,813 gallons)
T-1	N/A	40 CFR Part 60, Subpart Kb	Storage capacity is less than 75 cubic meters (19,813 gallons)
T-2	N/A	40 CFR Part 60, Subpart Kb	Storage capacity is less than 75 cubic meters

Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit / Group / Process ID No.	Group / Inclusive Units	Regulation	Basis of Determination
			(19,813 gallons)
T-4	N/A	40 CFR Part 60, Subpart Kb	Storage capacity is less than 75 cubic meters (19,813 gallons)
TK-1	N/A	40 CFR Part 60, Subpart Kb	Storage capacity is less than 75 cubic meters (19,813 gallons)
TK-1	N/A	40 CFR Part 63, Subpart HH	This tank does not meet the definition of a storage vessel with the potential for flash emissions. The GOR, API and throughput of the material stored are less than the thresholds cited under 63.761.
U1	N/A	40 CFR Part 60, Subpart GG	Modified after February 18, 2005, therefore exempt from the requirements of Subpart GG and now subject to KKKK.

New Source Review Authorization References

New Source Review Authorization References 49

New Source Review Authorization References by Emission Unit..... 50

New Source Review Authorization References

The New Source Review authorizations listed in the table below are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Prevention of Significant Deterioration (PSD) Permits	
PSD Permit No.: PSDTX436M2	Issuance Date: 10/29/2021
PSD Permit No.: PSDTX637M1	Issuance Date: 12/12/2022
PSD Permit No.: PSDTX654M2	Issuance Date: 11/14/2018
PSD Permit No.: PSDTX718	Issuance Date: 08/11/2023
Title 30 TAC Chapter 116 Permits, Special Permits, and Other Authorizations (Other Than Permits By Rule, PSD Permits, or NA Permits) for the Application Area.	
Authorization No.: 6689	Issuance Date: 03/06/2024
Authorization No.: 8929	Issuance Date: 10/29/2021
Authorization No.: 9488	Issuance Date: 12/12/2022
Authorization No.: 9608	Issuance Date: 11/14/2018
Authorization No.: 17800	Issuance Date: 08/11/2023
Permits By Rule (30 TAC Chapter 106) for the Application Area	
Number: 6	Version No./Date: 05/05/1976
Number: 80	Version No./Date: 07/20/1992
Number: 106.263	Version No./Date: 11/01/2001
Number: 106.352	Version No./Date: 03/14/1997
Number: 106.352	Version No./Date: 09/04/2000
Number: 106.359	Version No./Date: 09/10/2013
Number: 106.454	Version No./Date: 11/01/2001
Number: 106.472	Version No./Date: 03/14/1997
Number: 106.472	Version No./Date: 09/04/2000
Number: 106.473	Version No./Date: 09/04/2000
Number: 106.478	Version No./Date: 09/04/2000
Number: 106.511	Version No./Date: 09/04/2000
Number: 106.512	Version No./Date: 06/13/2001

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization**
AGB1-FUG	ACID GAS BOOSTER 1 FUGITIVES	106.352/03/14/1997 [41836]
AGB2-FUG	ACID GAS BOOSTER 2 FUGITIVES	106.352/03/14/1997 [41836]
AGB3-FUG	ACID GAS BOOSTER 3 FUGITIVES	106.352/03/14/1997 [41836]
AIR-1	6.6L CATERPILLAR C6.6 ACERT	106.511/09/04/2000
AT-1	ANTIFREEZE TANK	106.478/09/04/2000
AT-2	ANTIFREEZE TANK	106.478/09/04/2000
C10	COMPRESSOR 10P CLARK TLAB-6 2SLB	6689
C13	COMPRESSOR 12P CLARK TLAB-6 2SLB	9488, PSDTX637M1
C14	COMPRESSOR 13P CLARK TLAB-6 2SLB	9488, PSDTX637M1
C15	RAW GAS COMPRESSOR	9608, PSDTX654M2
C16	RAW GAS COMPRESSOR	9608, PSDTX654M2
C19	1665 HP CATERPILLAR 3606 COMPRESSOR	106.512/06/13/2001 [41836]
C21	1665 HP CATERPILLAR 3606 COMPRESSOR	106.512/06/13/2001 [41836]
C8	COMPRESSOR 8P CLARK TLAB-6 2SLB	6/05/05/1976 [10141]
C9	COMPRESSOR 9P CLARK TLAB-6 2SLB	6689
COMPFUG1	COMPRESSOR 8P, 9P, & 10P FUGITIVES	6689, 106.352/09/04/2000 [41836]
COMPFUG2	COMPRESSOR 12-15P FUG; TURBINE 16-18P FUG.	8929, 9488, 9608, 17800, PSDTX436M2, PSDTX637M1, PSDTX654M2, PSDTX718, 106.352/09/04/2000 [41836]
COMPFUG3	COMPRESSOR C19 AND C21 FUGITIVES	106.512/06/13/2001 [41836]
COMPFUG5	FUGITIVES FOR E1-E, E1-W, AND WHB	9608, PSDTX654M2

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization**
CT-1	MISC. CHEMICAL STORAGE TANK	106.472/09/04/2000
CT-2	MISC. CHEMICAL STORAGE TANK	106.472/09/04/2000
CT-3	MISC. CHEMICAL STORAGE TANK	106.472/09/04/2000
D1	36 MMBTU/HR TURBINE 17P	8929, PSDTX436M2
D2	36 MMBTU/HR TURBINE 18P	9608, PSDTX654M2
DEG1	DEGREASER 1	106.454/11/01/2001
DEG2	DEGREASER 2	106.454/11/01/2001
DGA3-FUG	DGA UNIT 3 FUGITIVES	8929, PSDTX436M2
DGA4-FUG	DGA UNIT 4 FUGITIVES	8929, PSDTX436M2
DT-1	DIESEL STORAGE TANK	106.472/09/04/2000
DT-2	DIESEL STORAGE TANK	106.472/09/04/2000
E1-E	36 MMBTU/HR EAST GENERATOR SET	9608, PSDTX654M2
E1-W	36 MMBTU/HR WEST GENERATOR SET	9608, PSDTX654M2
FL-1	WEST FLARE	8929, PSDTX436M2, 106.263/11/01/2001
FL-2	EAST FLARE	80/07/20/1992 [23596], 106.263/11/01/2001
FUG-NGP	NGL PLANT FUGITIVES	9608, PSDTX654M2
FWP	8.9L CUMMINS 359 HP EMERGENCY FIRE-WATER PUMP	106.511/09/04/2000
G-4	PLANT DRAIN TANK	8929, PSDTX436M2, 106.478/09/04/2000
GLY	TEG STORAGE TANK	106.472/09/04/2000
INLET-FUG	INLET LINE FUGITIVES	106.352/03/14/1997 [41836]
LO-1	14P/15P LUBE OIL TANK	106.472/09/04/2000

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization**
LO-2	LUBE OIL TANK	106.472/09/04/2000
LOAD	LOADING	106.472/03/14/1997, 106.472/09/04/2000, 106.478/09/04/2000
MT-1	METHANOL STORAGE TANK	106.473/09/04/2000
MT-2	METHANOL STORAGE TANK	106.473/09/04/2000
MT-3	METHANOL STORAGE TANK	106.473/09/04/2000
MT-4	METHANOL STORAGE TANK	106.473/09/04/2000
MT-5	METHANOL STORAGE TANK	106.473/09/04/2000
MT-6	METHANOL STORAGE TANK	106.473/09/04/2000, 106.478/09/04/2000
PRODGA	PRODGA	9608, PSDTX654M2
SV-00-301	TURBINE LUBE OIL STORAGE TANK	106.472/09/04/2000
SV-00-302	LUBE OIL TANK	106.472/09/04/2000
SV-00-610	SLOP OIL TANK (NORTH)	106.472/09/04/2000
SV-00-903	TURBINE LUBE OIL STORAGE TANK	106.472/09/04/2000
SV-00-905	14P/15P OIL TANK	8929, PSDTX436M2, 106.478/09/04/2000
SV-02-301	PROPANE OIL STORAGE	106.478/09/04/2000
SV-02-302	PROPANE OIL STORAGE	106.478/09/04/2000
T-1	SKIM OIL TANK	8929, PSDTX436M2, 106.478/09/04/2000
T-2	DGA STORAGE TANK	106.472/03/14/1997
T-4	DGA STORAGE TANK	106.472/09/04/2000
TEGDEHY	TEG GLYCOL DEHYDRATOR	9608, PSDTX654M2

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization**
TK-1	SPILL OVER TANK	8929, PSDTX436M2, 106.478/09/04/2000
TREAT-FUG	PRODUCT TREATING FUGITIVES	8929, PSDTX436M2
U1	44 MMBTU/HR TURBINE 16P	17800, PSDTX718

**This column may include Permit by Rule (PBR) numbers and version dates, PBR Registration numbers in brackets, Standard Permit Registration numbers, Minor NSR permit numbers, and Major NSR permit numbers.

Appendix A

Acronym List 55

Acronym List

The following abbreviations or acronyms may be used in this permit:

ACFM	actual cubic feet per minute
AMOC	alternate means of control
ARP	Acid Rain Program
ASTM	American Society of Testing and Materials
B/PA	Beaumont/Port Arthur (nonattainment area)
CAM	Compliance Assurance Monitoring
CD	control device
CEMS	continuous emissions monitoring system
CFR	Code of Federal Regulations
COMS	continuous opacity monitoring system
CVS	closed vent system
D/FW	Dallas/Fort Worth (nonattainment area)
EP	emission point
EPA	U.S. Environmental Protection Agency
EU	emission unit
FCAA Amendments	Federal Clean Air Act Amendments
FOP	federal operating permit
gr/100 scf	grains per 100 standard cubic feet
HAP	hazardous air pollutant
H/G/B	Houston/Galveston/Brazoria (nonattainment area)
H ₂ S	hydrogen sulfide
ID No.	identification number
lb/hr	pound(s) per hour
MACT	Maximum Achievable Control Technology (40 CFR Part 63)
MMBtu/hr	Million British thermal units per hour
NA	nonattainment
N/A	not applicable
NADB	National Allowance Data Base
NESHAP	National Emission Standards for Hazardous Air Pollutants (40 CFR Part 61)
NO _x	nitrogen oxides
NSPS	New Source Performance Standard (40 CFR Part 60)
NSR	New Source Review
ORIS	Office of Regulatory Information Systems
Pb	lead
PBR	Permit By Rule
PEMS	predictive emissions monitoring system
PM	particulate matter
ppmv	parts per million by volume
PRO	process unit
PSD	prevention of significant deterioration
psia	pounds per square inch absolute
RO	Responsible Official
SIP	state implementation plan
SO ₂	sulfur dioxide
TCEQ	Texas Commission on Environmental Quality
TSP	total suspended particulate
TVP	true vapor pressure
U.S.C.	United States Code
VOC	volatile organic compound

Appendix B

Major NSR Summary Table 57

Major NSR Summary Table

Permit Numbers: 8929 and PSDTX436M2					Issuance Date: October 29, 2021		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Special Conditions/ Application Information	Special Conditions/ Application Information	Special Conditions/ Application Information
D'1	Turbine Engine 17P (Solar A Compressor)	NO _x	16.20	71.00	5, 8	5, 8, 9	5
		CO	5.20	22.70			
		VOC	1.00	4.30			
		PM/PM ₁₀ /PM _{2.5}	0.22	0.97			
		SO ₂	0.11	0.50			
		CH ₂ O	0.02	0.10			
FL-1	West Flare (Pilot Gas Only) Emergency Use Only	NO _x	0.05	0.22	2		
		CO	0.44	1.85			
		VOC	0.01	0.01			
		SO ₂	<0.01	<0.01			
FUG-1	Fugitive and Storage Losses, 17P, G-4, T-1, TREATFUG, DGA-3, and DGA-4 (5)	VOC	3.20	13.90	5, 6	5, 6, 9	5
		H ₂ S	1.00	4.50			

- (1) Emission point identification – either specific equipment designation or emission point number from plot plan.
- (2) Specific point source name. For fugitive sources, use area name or fugitive source name.
- (3) VOC – volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1
 HCHO – formaldehyde
 NO_x – total oxides of nitrogen
 SO₂ – sulfur dioxide
 PM₁₀ – particulate matter equal to or less than 10 microns in diameter, including PM_{2.5}
 PM_{2.5} – particulate matter equal to or less than 2.5 microns in diameter
 CO – carbon monoxide
 HAP – hazardous air pollutant as listed in § 112(b) of the Federal Clean Air Act or Title 40 Code of Federal Regulations Part 63, Subpart C
- (4) Compliance with annual emission limits (tons per year) is based on a 12-month rolling period.
- (5) HCHO (formaldehyde) is a HAP and a subspecies of VOC. The VOC emission limits are inclusive of HCHO.

Major NSR Summary Table

Permit Numbers: 9488 and PSDTX637M1					Issuance Date: December 12, 2022		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Special Conditions/ Application Information	Special Conditions/ Application Information	Special Conditions/ Application Information
C-12	2,000-hp Gas-Fired Clark TLAB-6 Compressor Engine 12P	NO _x	22.0	96.5	7, 9	9, 10, 11	
		CO	8.8	38.6			
		VOC	1.72	7.5			
		HCHO (5)	0.789	3.46			
		PM ₁₀	0.69	3.0			
		PM _{2.5}	0.69	3.0			
		SO ₂	0.013	0.06			
C-13	2,000-hp Gas-Fired Clark TLAB-6 Compressor Engine 13P	NO _x	22.0	96.5	7, 9	9, 10, 11	
		CO	8.8	38.6			
		VOC	1.72	7.5			
		HCHO (5)	0.789	3.46			
		PM ₁₀	0.69	3.0			
		PM _{2.5}	0.69	3.0			
		SO ₂	0.013	0.06			

- (1) Emission point identification – either specific equipment designation or emission point number from plot plan.
- (2) Specific point source name. For fugitive sources, use area name or fugitive source name.
- (3) VOC – volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1
HCHO – formaldehyde
NO_x – total oxides of nitrogen
SO₂ – sulfur dioxide
PM₁₀ – particulate matter equal to or less than 10 microns in diameter, including PM_{2.5}
PM_{2.5} – particulate matter equal to or less than 2.5 microns in diameter
CO – carbon monoxide
HAP – hazardous air pollutant as listed in § 112(b) of the Federal Clean Air Act or Title 40 Code of Federal Regulations Part 63, Subpart C
- (4) Compliance with annual emission limits (tons per year) is based on a 12-month rolling period.
- (5) HCHO (formaldehyde) is a HAP and a subspecies of VOC. The VOC emission limits are inclusive of HCHO.

Major NSR Summary Table

Permit Numbers: 9608 and PSDTX654M2					Issuance Date: November 14, 2018		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Special Conditions/ Application Information	Special Conditions/ Application Information	Special Conditions/ Application Information
C15	Ingersoll Rand KVSR 2,600 hp Four Stroke Lean Burn	CO (5)	22.93	100.42	4, 5, 9	5, 9	9
		NOx (5)	28.66	125.53			
		PM/PM ₁₀	0.22	0.97			
		SO ₂	0.02	0.06			
		VOC	2.50	10.95			
C16	Ingersoll Rand KVSR 2,600 hp Four Stroke Lean Burn	CO (5)	22.93	100.42	4, 5, 9	5, 9	9
		NOx (5)	28.66	125.53			
		PM/PM ₁₀	0.22	0.97			
		SO ₂	0.02	0.06			
		VOC	2.50	10.95			
D2	Processed Gas Compressor One 4,100 hp Solar T-4500	CO (5)	3.04	13.31	2, 4, 9	2, 9	2, 9
		NOx (5)	11.86	51.94			
		PM/PM ₁₀	0.25	1.07			
		SO ₂	0.13	0.55			
		VOC	0.08	0.34			
E1	Generator Set 8,200 hp (6) Two 36 MMBtu/hr Solar T-4500s One 19.0 MMBtu/hr WHB	CO (5)	7.64		4, 9	9	9
		NOx (5)	25.58				
		PM/PM ₁₀	0.64				
		SO ₂	0.27				
		VOC	0.26				
E1E	East Generator 4,100 hp (6)	CO (5)	3.04		2, 4	2	2
		NOx (5)	11.86				

Major NSR Summary Table

Permit Numbers: 9608 and PSDTX654M2					Issuance Date: November 14, 2018		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Special Conditions/ Application Information	Special Conditions/ Application Information	Special Conditions/ Application Information
	One 36 MMBtu/hr Solar T-4500	PM/PM ₁₀	0.25				
		SO ₂	0.13				
		VOC	0.08				
E1W	West Generator 4,100 hp (6) One 36 MMBtu/hr Solar T-4500	CO (5)	3.04		2, 4	2	2
		NO _x (5)	11.86				
		PM/PM ₁₀	0.25				
		SO ₂	0.13				
		VOC	0.08				
E1, E1E, and E1W	Annual Emissions (6)	CO (5)		33.47	2, 4	2	2
		NO _x (5)		112.04			
		PM/PM ₁₀		2.76			
		SO ₂		1.15			
		VOC		1.13			
FUG-2	Process Fugitives (4)	H ₂ S	0.05	0.20	3, 8	3, 8	8
		VOC	0.04	0.18			
FUG-NGP	Process Fugitives (4)	H ₂ S	0.31	1.35	8	8	8
		VOC	0.48	2.10			

- (1) Emission point identification – either specific equipment designation or emission point number from plot plan.
- (2) Specific point source name. For fugitive sources, use area name or fugitive source name.
- (3) CO – carbon monoxide
 NO_x – total oxides of nitrogen
 PM₁₀ – particulate matter equal to or less than 10 microns in diameter, including PM_{2.5}
 PM_{2.5} – particulate matter equal to or less than 2.5 microns in diameter
 SO₂ – sulfur dioxide

VOC – volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1

H₂S – hydrogen sulfide

(4) Fugitive emissions are an estimate only and should not be considered as a maximum allowable emission rate.

(5) A PSDTX654M2 pollutant

(6) Emissions from EPN E1 will not occur at the same time as emissions from EPN E1E or E1W.

Major NSR Summary Table

Permit Numbers: 17800 and PSDTX718					Issuance Date: August 11, 2023		
Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates		Monitoring and Testing Requirements	Recordkeeping Requirements	Reporting Requirements
			lbs/hour	TPY (4)	Special Conditions/ Application Information	Special Conditions/ Application Information	Special Conditions/ Application Information
U1	Compressor 16P (Solar 50-5900L Turbine, 5000 hp)	NO _x	29.74	130.26	2, 3, 5, 7, 8, 9, 10	2, 3, 8, 9, 10, 11, 12	2, 3, 9
		CO	6.04	26.46			
		VOC	0.35	1.52			
		SO ₂	0.03	0.14			
		PM ₁₀	0.33	1.43			
		PM _{2.5}	0.33	1.43			
		HAP (HCHO)	0.04	0.15			
FUG-U	Fugitive Emissions (5)	VOC	0.10	0.46	2	2	2
		H ₂ S	0.14	0.62			

- (1) Emission point identification – either specific equipment designation or emission point number from plot plan.
- (2) Specific point source name. For fugitive sources, use area name or fugitive source name.
- (3) VOC – volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1
 NO_x – total oxides of nitrogen
 SO₂ – sulfur dioxide
 PM₁₀ – particulate matter equal to or less than 10 microns in diameter, including PM_{2.5}
 PM_{2.5} – particulate matter equal to or less than 2.5 microns in diameter
 CO – carbon monoxide
 HAP – hazardous air pollutant as listed in § 112(b) of the Federal Clean Air Act or Title 40 Code of Federal Regulations Part 63, Subpart C
 H₂S – hydrogen sulfide
 HCHO – formaldehyde
- (4) Compliance with annual emission limits (tons per year) is based on a 12-month rolling period.
- (5) Emission rate is an estimate and is enforceable through compliance with the applicable special condition(s) and permit application representations.

Texas Commission on Environmental Quality Air Quality Permit

A Permit Is Hereby Issued To
Kinder Morgan Production Company LLC
Authorizing the Continued Operation of
Yates Gas Plant
Located at **Iraan, Pecos County, Texas**
Latitude 30° 53' 7" Longitude -101° 55' 17"

Permit: 8929 and PSDTX436M2

Issuance Date: October 29, 2021

Expiration Date: October 29, 2031



For the Commission

1. **Facilities** covered by this permit shall be constructed and operated as specified in the application for the permit. All representations regarding construction plans and operation procedures contained in the permit application shall be conditions upon which the permit is issued. Variations from these representations shall be unlawful unless the permit holder first makes application to the Texas Commission on Environmental Quality (commission) Executive Director to amend this permit in that regard and such amendment is approved. [Title 30 Texas Administrative Code (TAC) Section 116.116 (30 TAC § 116.116)]¹
2. **Voiding of Permit.** A permit or permit amendment is automatically void if the holder fails to begin construction within 18 months of the date of issuance, discontinues construction for more than 18 months prior to completion, or fails to complete construction within a reasonable time. Upon request, the executive director may grant an 18-month extension. Before the extension is granted the permit may be subject to revision based on best available control technology, lowest achievable emission rate, and netting or offsets as applicable. One additional extension of up to 18 months may be granted if the permit holder demonstrates that emissions from the facility will comply with all rules and regulations of the commission, the intent of the Texas Clean Air Act (TCAA), including protection of the public's health and physical property; and (b)(1) the permit holder is a party to litigation not of the permit holder's initiation regarding the issuance of the permit; or (b)(2) the permit holder has spent, or committed to spend, at least 10 percent of the estimated total cost of the project up to a maximum of \$5 million. A permit holder granted an extension under subsection (b)(1) of this section may receive one subsequent extension if the permit holder meets the conditions of subsection (b)(2) of this section. [30 TAC § 116.120]
3. **Construction Progress.** Start of construction, construction interruptions exceeding 45 days, and completion of construction shall be reported to the appropriate regional office of the commission not later than 15 working days after occurrence of the event. [30 TAC § 116.115(b)(2)(A)]
4. **Start-up Notification.** The appropriate air program regional office shall be notified prior to the commencement of operations of the facilities authorized by the permit in such a manner that a representative of the commission may be present. The permit holder shall provide a separate notification for the commencement of operations for each unit of phased construction, which may involve a series of units commencing operations at different times. Prior to operation of the facilities authorized by the permit, the permit holder shall identify the source or sources of allowances to be utilized for compliance with Chapter 101, Subchapter H, Division 3 of this title (relating to Mass Emissions Cap and Trade Program). [30 TAC § 116.115(b)(2)(B)]
5. **Sampling Requirements.** If sampling is required, the permit holder shall contact the commission's Office of Compliance and Enforcement prior to sampling to obtain the proper data forms and procedures. All sampling and testing procedures must be approved by the executive director and coordinated with the regional representatives of the commission. The permit holder is also responsible for providing sampling facilities and conducting the sampling operations or contracting with an independent sampling consultant. [30 TAC § 116.115(b)(2)(C)]
6. **Equivalency of Methods.** The permit holder must demonstrate or otherwise justify the equivalency of emission control methods, sampling or other emission testing methods, and monitoring methods proposed as alternatives to methods indicated in the conditions of the permit. Alternative methods shall be applied for in writing and must be reviewed and approved by the executive director prior to their use in fulfilling any requirements of the permit. [30 TAC § 116.115(b)(2)(D)]
7. **Recordkeeping.** The permit holder shall maintain a copy of the permit along with records containing the information and data sufficient to demonstrate compliance with the permit, including production records and operating hours;

keep all required records in a file at the plant site. If, however, the facility normally operates unattended, records shall be maintained at the nearest staffed location within Texas specified in the application; make the records available at the request of personnel from the commission or any air pollution control program having jurisdiction in a timely manner; comply with any additional recordkeeping requirements specified in special conditions in the permit; and retain information in the file for at least two years following the date that the information or data is obtained. [30 TAC § 116.115(b)(2)(E)]

8. **Maximum Allowable Emission Rates.** The total emissions of air contaminants from any of the sources of emissions must not exceed the values stated on the table attached to the permit entitled "Emission Sources-- Maximum Allowable Emission Rates." [30 TAC § 116.115(b)(2)(F)]¹
9. **Maintenance of Emission Control.** The permitted facilities shall not be operated unless all air pollution emission capture and abatement equipment is maintained in good working order and operating properly during normal facility operations. The permit holder shall provide notification in accordance with 30 TAC §101.201, 101.211, and 101.221 of this title (relating to Emissions Event Reporting and Recordkeeping Requirements; Scheduled Maintenance, Startup, and Shutdown Reporting and Recordkeeping Requirements; and Operational Requirements). [30 TAC§ 116.115(b)(2)(G)]
10. **Compliance with Rules.** Acceptance of a permit by an applicant constitutes an acknowledgment and agreement that the permit holder will comply with all rules and orders of the commission issued in conformity with the TCAA and the conditions precedent to the granting of the permit. If more than one state or federal rule or regulation or permit condition is applicable, the most stringent limit or condition shall govern and be the standard by which compliance shall be demonstrated. Acceptance includes consent to the entrance of commission employees and agents into the permitted premises at reasonable times to investigate conditions relating to the emission or concentration of air contaminants, including compliance with the permit. [30 TAC § 116.115(b)(2)(H)]
11. **This** permit may not be transferred, assigned, or conveyed by the holder except as provided by rule. [30 TAC § 116.110(e)]
12. **There** may be additional special conditions attached to a permit upon issuance or modification of the permit. Such conditions in a permit may be more restrictive than the requirements of Title 30 of the Texas Administrative Code. [30 TAC § 116.115(c)]
13. **Emissions** from this facility must not cause or contribute to "air pollution" as defined in Texas Health and Safety Code (THSC) §382.003(3) or violate THSC § 382.085. If the executive director determines that such a condition or violation occurs, the holder shall implement additional abatement measures as necessary to control or prevent the condition or violation.
14. **The** permit holder shall comply with all the requirements of this permit. Emissions that exceed the limits of this permit are not authorized and are violations of this permit.¹

¹ Please be advised that the requirements of this provision of the general conditions may not be applicable to greenhouse gas emissions.

15. Common Acronyms in Air Permits

°C = Temperature in degrees Celsius
°F = Temperature in degrees Fahrenheit
°K = Temperature in degrees Kelvin
µg = microgram
µg/m³ = microgram per cubic meter
acfm = actual cubic feet per minute
AMOC = alternate means of control
AOS = alternative operating scenario
AP-42 = Air Pollutant Emission Factors, 5th edition
APD = Air Permits Division
API = American Petroleum Institute
APWL = air pollutant watch list
BPA = Beaumont/ Port Arthur
BACT = best available control technology
BAE = baseline actual emissions
bbl = barrel
bbl/day = barrel per day
bhp = brake horsepower
BMP = best management practices
Btu = British thermal unit
Btu/scf = British thermal unit per standard cubic foot or feet
CAA = Clean Air Act
CAM = compliance-assurance monitoring
CEMS = continuous emissions monitoring systems
cfm = cubic feet (per) minute
CFR = Code of Federal Regulations
CN = customer ID number
CNG = compressed natural gas
CO = carbon monoxide
COMS = continuous opacity monitoring system
CPMS = continuous parametric monitoring system
DFW = Dallas/ Fort Worth (Metroplex)
DE = destruction efficiency
DRE = destruction and removal efficiency
dscf = dry standard cubic foot or feet
dscfm = dry standard cubic foot or feet per minute
ED = (TCEQ) Executive Director
EF = emissions factor
EFR = external floating roof tank
EGU = electric generating unit
EI = Emissions Inventory
ELP = El Paso
EPA = (United States) Environmental Protection Agency
EPN = emission point number
ESL = effects screening level
ESP = electrostatic precipitator
FCAA = Federal Clean Air Act
FCCU = fluid catalytic cracking unit
FID = flame ionization detector
FIN = facility identification number
ft = foot or feet
ft/sec = foot or feet per second
g = gram
gal/wk = gallon per week
gal/yr = gallon per year
GLC = ground level concentration
GLC_{max} = maximum (predicted) ground-level concentration
gpm = gallon per minute
gr/100scf = grain per 100 standard cubic feet
gr/dscf = grain per dry standard cubic feet
H₂CO = formaldehyde
H₂S = hydrogen sulfide
H₂SO₄ = sulfuric acid
HAP = hazardous air pollutant as listed in § 112(b) of the Federal Clean Air Act or Title 40 Code of Federal Regulations Part 63, Subpart C
HC = hydrocarbons
HCl = hydrochloric acid, hydrogen chloride
Hg = mercury
HGB = Houston/Galveston/Brazoria
hp = horsepower
hr = hour
IFR = internal floating roof tank
in H₂O = inches of water
in Hg = inches of mercury
IR = infrared
ISC3 = Industrial Source Complex, a dispersion model
ISCST3 = Industrial Source Complex Short-Term, a dispersion model
K = Kelvin; extension of the degree Celsius scaled-down to absolute zero
LACT = lease automatic custody transfer
LAER = lowest achievable emission rate
lb = pound
hp = horsepower
hr = hour
lb/day = pound per day
lb/hr = pound per hour
lb/MMBtu = pound per million British thermal units
LDAR = Leak Detection and Repair (Requirements)
LNG = liquefied natural gas
LPG = liquefied petroleum gas
LT/D = long ton per day
m = meter
m³ = cubic meter
m/sec = meters per second
MACT = maximum achievable control technology
MAERT = Maximum Allowable Emission Rate Table
MERA = Modeling and Effects Review Applicability
mg = milligram
mg/g = milligram per gram
mL = milliliter
MMBtu = million British thermal units
MMBtu/hr = million British thermal units per hour
MSDS = material safety data sheet
MSS = maintenance, startup, and shutdown
MW = megawatt
NAAQS = National Ambient Air Quality Standards
NESHAP = National Emission Standards for Hazardous Air Pollutants
NGL = natural gas liquids
NNSR = nonattainment new source review
NO_x = total oxides of nitrogen
NSPS = New Source Performance Standards
PAL = plant-wide applicability limit
PBR = Permit(s) by Rule

PCP = pollution control project
PEMS = predictive emission monitoring system
PID = photo ionization detector
PM = periodic monitoring
PM = total particulate matter, suspended in the atmosphere, including PM₁₀ and PM_{2.5}, as represented
PM_{2.5} = particulate matter equal to or less than 2.5 microns in diameter
PM₁₀ = total particulate matter equal to or less than 10 microns in diameter, including PM_{2.5}, as represented
POC = products of combustion
ppb = parts per billion
ppm = parts per million
ppmv = parts per million (by) volume
psia = pounds (per) square inch, absolute
psig = pounds (per) square inch, gage
PTE = potential to emit
RA = relative accuracy
RATA = relative accuracy test audit
RM = reference method
RVP = Reid vapor pressure
scf = standard cubic foot or feet
scfm = standard cubic foot or feet (per) minute
SCR = selective catalytic reduction
SIL = significant impact levels
SNCR = selective non-catalytic reduction
SO₂ = sulfur dioxide
SOCMI = synthetic organic chemical manufacturing industry
SRU = sulfur recovery unit
TAC = Texas Administrative Code
TCAA = Texas Clean Air Act
TCEQ = Texas Commission on Environmental Quality
TD = Toxicology Division
TLV = threshold limit value
TMDL = total maximum daily load
tpd = tons per day
tpy = tons per year
TVP = true vapor pressure
VOC = volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1
VRU = vapor recovery unit or system

Special Conditions

Permit Numbers 8929 and PSDTX436M2

Emission Standards

1. This permit covers only those emissions from those points listed in the attached table entitled A Emission Sources - Maximum Allowable Emission Rates, @ and the facilities covered by this permit are authorized to emit only the air contaminants on that table subject to the emission rates limits and other conditions specified in this permit.
2. The following sources are authorized under Title 30 Texas Administrative Code Chapter 106 (30 TAC Chapter 106):

Permit By Rule	Permit by Rule (PBR) No.
Oil and Gas Handling and Production Facilities	§106.352
Organic and Inorganic Liquid Loading and Unloading	§106.472
Storage Tank and Change of Service	§106.478
Smokeless Gas Flares	Standard Exemption 80 (August 16, 1993) Registration No. 23596

3. With the exception of fugitive emissions, all sources of air contaminants shall be physically marked in a conspicuous location with the emission point numbers (EPNs) and/or the source names as identified on the maximum allowable emission rates table (MAERT).

Operational Parameters

4. Carbon Compound Waste Gas Streams

Non-fugitive emissions from relief valves, safety valves, or rupture discs of gases containing volatile organic compounds (VOCs) at a concentration of greater than one percent are not authorized by this permit. Any releases directly to atmosphere from relief valves, safety valves, or rupture discs of gases containing VOCs at a concentration greater than one weight percent are not consistent with good practice for minimizing emissions, with the exception of those listed below:

Gas Compressor Discharge

Except for those emissions authorized and listed on the MAERT, all emissions from relief valves, safety valves, and rupture discs (including those listed above) must be documented and reported as required by 30 TAC Chapter 101.201 or 101.211.

Federal Applicability

5. These facilities shall comply with applicable requirements of the U.S. Environmental Protection Agency (EPA) regulations in Title 40 of the Code of Federal Regulations, Part 60 (40 CFR Part 60) on Standards of Performance for New Stationary Sources (NSPS) promulgated for:
 - A. Subpart A, Applicable General Conditions.
 - B. Subpart GG, Stationary Gas Turbines.
 - C. Subpart KKK, Equipment Leaks of VOC from Onshore Natural Gas Processing Plants.
6. These facilities shall comply with all applicable requirements of EPA regulations on National Emission Standards for Hazardous Air Pollutants for Source Categories (NESHAP) in 40 CFR Part 63, promulgated for:
 - A. Subpart A, General Provisions.
 - B. Subpart HH, Oil and Gas Production Facilities.
7. If any condition of this permit is more stringent than the regulations so incorporated, then for the purposes of complying with this permit, the permit shall govern and be the standard by which compliance shall be demonstrated.

Continuous Determination of Compliance

8. The holder of this permit shall monitor and record the nitrogen oxides (NO_x) concentration in the exhaust stream of the turbine (EPN D'1) using a portable analyzer on a monthly basis. The portable analyzer shall be operated in accordance with the EPA Office of Air Quality Planning & Standards, Emission Measurement Center Conditional Test Method - Determination of Oxygen, Carbon Monoxide and Oxides of Nitrogen from Stationary Sources For Periodic Monitoring (Portable Electrochemical Analyzer Procedure) [CTM-034] (September 8, 1999). NO_x emissions shall be converted/calculated in units corresponding to the underlying applicable emission limitation (grams per horsepower hour, pounds per MMBtu, pounds per hour, etc.).
 - A. The monitoring data shall be used to demonstrate compliance with the emission limits on the MAERT.
 - B. All monitoring data and quality-assurance data shall be maintained by the source for a period of five years and shall be made available to the TCEQ Executive Director or designated representative upon request. The hourly average data from the analyzer

shall be used to determine compliance with the conditions of this permit. Hourly average concentrations from EPN D'1 shall be summed to tons each month and used to determine compliance with the 12-month rolling annual emission limits of this permit.

Recordkeeping

9. The following information shall be maintained by the holder of this permit in a form suitable for inspection for a period of five years after collection and shall be made immediately available upon request to representatives of the TCEQ, EPA, or any local air pollution control program having jurisdiction:
 - A. Records of the feed rate and sulfur content of gas processed at this facility.
 - B. Records of emissions from relief valves, safety valves, and ruptured discs pursuant to Special Condition No. 4.
 - C. A complete copy of the monitoring reports and records of the performance monitoring completed pursuant to Special Condition No. 8 to demonstrate compliance with this permit.
 - D. Records sufficient document compliance with the applicable requirements of 40 CFR Part 60), Subparts A, GG, and KKK.
 - E. Records sufficient document compliance with the applicable requirements of 40 CFR Part 63), Subparts A and HH.

Dated March 26, 2012

Emission Sources - Maximum Allowable Emission Rates

Permit Numbers 8929 and PSDTX436M2

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities, sources, and related activities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

Air Contaminants Data

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
D'1	Turbine Engine 17P (Solar A Compressor)	NO _x	16.20	71.00
		CO	5.20	22.70
		VOC	1.00	4.30
		PM/PM ₁₀ /PM _{2.5}	0.22	0.97
		SO ₂	0.11	0.50
		CH ₂ O	0.02	0.10
FL-1	West Flare (Pilot Gas Only) Emergency Use Only	NO _x	0.05	0.22
		CO	0.44	1.85
		VOC	0.01	0.01
		SO ₂	<0.01	<0.01
FUG-1	Fugitive and Storage Losses, 17P, G-4, T-1, TREATFUG, DGA-3, and DGA-4 (5)	VOC	3.20	13.90
		H ₂ S	1.00	4.50

- (1) Emission point identification - either specific equipment designation or emission point number from plot plan.
- (2) Specific point source name. For fugitive sources, use area name or fugitive source name.
- (3) VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1
- NO_x - total oxides of nitrogen
- SO₂ - sulfur dioxide
- PM - total particulate matter, suspended in the atmosphere, including PM₁₀ and PM_{2.5}, as represented
- PM₁₀ - total particulate matter equal to or less than 10 microns in diameter, including PM_{2.5}, as represented
- PM_{2.5} - particulate matter equal to or less than 2.5 microns in diameter
- CO - carbon monoxide
- H₂S - hydrogen sulfide
- CH₂O - formaldehyde

Emission Sources - Maximum Allowable Emission Rates

- (4) Compliance with annual emission limits (tons per year) is based on a 12-month rolling period.
- (5) Fugitive emissions are an estimate only and should not be considered as a maximum allowable emission rate.

Date: March 26, 2012

**Texas Commission on Environmental Quality
Air Quality Permit**

A Permit Is Hereby Issued To
Kinder Morgan Production Company, LLC
Authorizing the Continued Operation of
Yates Gas Plant
Located at Iraan, Pecos County, Texas
Latitude 30° 53' 7" Longitude -101° 55' 17"

Permit: 9488 and PSDTX637

Issuance Date: December 12, 2022

Expiration Date: December 12, 2032



For the Commission

1. **Facilities** covered by this permit shall be constructed and operated as specified in the application for the permit. All representations regarding construction plans and operation procedures contained in the permit application shall be conditions upon which the permit is issued. Variations from these representations shall be unlawful unless the permit holder first makes application to the Texas Commission on Environmental Quality (commission) Executive Director to amend this permit in that regard and such amendment is approved. [Title 30 Texas Administrative Code (TAC) Section 116.116 (30 TAC § 116.116)]¹
2. **Voiding of Permit.** A permit or permit amendment is automatically void if the holder fails to begin construction within 18 months of the date of issuance, discontinues construction for more than 18 months prior to completion, or fails to complete construction within a reasonable time. Upon request, the executive director may grant an 18-month extension. Before the extension is granted the permit may be subject to revision based on best available control technology, lowest achievable emission rate, and netting or offsets as applicable. One additional extension of up to 18 months may be granted if the permit holder demonstrates that emissions from the facility will comply with all rules and regulations of the commission, the intent of the Texas Clean Air Act (TCAA), including protection of the public's health and physical property; and (b)(1) the permit holder is a party to litigation not of the permit holder's initiation regarding the issuance of the permit; or (b)(2) the permit holder has spent, or committed to spend, at least 10 percent of the estimated total cost of the project up to a maximum of \$5 million. A permit holder granted an extension under subsection (b)(1) of this section may receive one subsequent extension if the permit holder meets the conditions of subsection (b)(2) of this section. [30 TAC § 116.120]
3. **Construction Progress.** Start of construction, construction interruptions exceeding 45 days, and completion of construction shall be reported to the appropriate regional office of the commission not later than 15 working days after occurrence of the event. [30 TAC § 116.115(b)(2)(A)]
4. **Start-up Notification.** The appropriate air program regional office shall be notified prior to the commencement of operations of the facilities authorized by the permit in such a manner that a representative of the commission may be present. The permit holder shall provide a separate notification for the commencement of operations for each unit of phased construction, which may involve a series of units commencing operations at different times. Prior to operation of the facilities authorized by the permit, the permit holder shall identify the source or sources of allowances to be utilized for compliance with Chapter 101, Subchapter H, Division 3 of this title (relating to Mass Emissions Cap and Trade Program). [30 TAC § 116.115(b)(2)(B)]
5. **Sampling Requirements.** If sampling is required, the permit holder shall contact the commission's Office of Compliance and Enforcement prior to sampling to obtain the proper data forms and procedures. All sampling and testing procedures must be approved by the executive director and coordinated with the regional representatives of the commission. The permit holder is also responsible for providing sampling facilities and conducting the sampling operations or contracting with an independent sampling consultant. [30 TAC § 116.115(b)(2)(C)]
6. **Equivalency of Methods.** The permit holder must demonstrate or otherwise justify the equivalency of emission control methods, sampling or other emission testing methods, and monitoring methods proposed as alternatives to methods indicated in the conditions of the permit. Alternative methods shall be applied for in writing and must be reviewed and approved by the executive director prior to their use in fulfilling any requirements of the permit. [30 TAC § 116.115(b)(2)(D)]
7. **Recordkeeping.** The permit holder shall maintain a copy of the permit along with records containing the information and data sufficient to demonstrate compliance with the permit, including production records and operating hours;

keep all required records in a file at the plant site. If, however, the facility normally operates unattended, records shall be maintained at the nearest staffed location within Texas specified in the application; make the records available at the request of personnel from the commission or any air pollution control program having jurisdiction in a timely manner; comply with any additional recordkeeping requirements specified in special conditions in the permit; and retain information in the file for at least two years following the date that the information or data is obtained. [30 TAC § 116.115(b)(2)(E)]

8. **Maximum Allowable Emission Rates.** The total emissions of air contaminants from any of the sources of emissions must not exceed the values stated on the table attached to the permit entitled "Emission Sources-- Maximum Allowable Emission Rates." [30 TAC § 116.115(b)(2)(F)]¹
9. **Maintenance of Emission Control.** The permitted facilities shall not be operated unless all air pollution emission capture and abatement equipment is maintained in good working order and operating properly during normal facility operations. The permit holder shall provide notification in accordance with 30 TAC §101.201, 101.211, and 101.221 of this title (relating to Emissions Event Reporting and Recordkeeping Requirements; Scheduled Maintenance, Startup, and Shutdown Reporting and Recordkeeping Requirements; and Operational Requirements). [30 TAC§ 116.115(b)(2)(G)]
10. **Compliance with Rules.** Acceptance of a permit by an applicant constitutes an acknowledgment and agreement that the permit holder will comply with all rules and orders of the commission issued in conformity with the TCAA and the conditions precedent to the granting of the permit. If more than one state or federal rule or regulation or permit condition is applicable, the most stringent limit or condition shall govern and be the standard by which compliance shall be demonstrated. Acceptance includes consent to the entrance of commission employees and agents into the permitted premises at reasonable times to investigate conditions relating to the emission or concentration of air contaminants, including compliance with the permit. [30 TAC § 116.115(b)(2)(H)]
11. **This** permit may not be transferred, assigned, or conveyed by the holder except as provided by rule. [30 TAC § 116.110(e)]
12. **There** may be additional special conditions attached to a permit upon issuance or modification of the permit. Such conditions in a permit may be more restrictive than the requirements of Title 30 of the Texas Administrative Code. [30 TAC § 116.115(c)]
13. **Emissions** from this facility must not cause or contribute to "air pollution" as defined in Texas Health and Safety Code (THSC) §382.003(3) or violate THSC § 382.085. If the executive director determines that such a condition or violation occurs, the holder shall implement additional abatement measures as necessary to control or prevent the condition or violation.
14. **The** permit holder shall comply with all the requirements of this permit. Emissions that exceed the limits of this permit are not authorized and are violations of this permit.¹

¹ Please be advised that the requirements of this provision of the general conditions may not be applicable to greenhouse gas emissions.

Common Acronyms in Air Permits

°C = Temperature in degrees Celsius
°F = Temperature in degrees Fahrenheit
°K = Temperature in degrees Kelvin
µg = microgram
µg/m³ = microgram per cubic meter
acfm = actual cubic feet per minute
AMOC = alternate means of control
AOS = alternative operating scenario
AP-42 = Air Pollutant Emission Factors, 5th edition
APD = Air Permits Division
API = American Petroleum Institute
APWL = air pollutant watch list
BPA = Beaumont/ Port Arthur
BACT = best available control technology
BAE = baseline actual emissions
bbl = barrel
bbl/day = barrel per day
bhp = brake horsepower
BMP = best management practices
Btu = British thermal unit
Btu/scf = British thermal unit per standard cubic foot or feet
CAA = Clean Air Act
CAM = compliance-assurance monitoring
CEMS = continuous emissions monitoring systems
cfm = cubic feet (per) minute
CFR = Code of Federal Regulations
CN = customer ID number
CNG = compressed natural gas
CO = carbon monoxide
COMS = continuous opacity monitoring system
CPMS = continuous parametric monitoring system
DFW = Dallas/ Fort Worth (Metroplex)
DE = destruction efficiency
DRE = destruction and removal efficiency
dscf = dry standard cubic foot or feet
dscfm = dry standard cubic foot or feet per minute
ED = (TCEQ) Executive Director
EF = emissions factor
EFR = external floating roof tank
EGU = electric generating unit
EI = Emissions Inventory
ELP = El Paso
EPA = (United States) Environmental Protection Agency
EPN = emission point number
ESL = effects screening level
ESP = electrostatic precipitator
FCAA = Federal Clean Air Act
FCCU = fluid catalytic cracking unit
FID = flame ionization detector
FIN = facility identification number
ft = foot or feet
ft/sec = foot or feet per second
g = gram
gal/wk = gallon per week
gal/yr = gallon per year
GLC = ground level concentration
GLC_{max} = maximum (predicted) ground-level concentration
gpm = gallon per minute
gr/100scf = grain per 100 standard cubic feet
gr/dscf = grain per dry standard cubic feet
H₂CO = formaldehyde
H₂S = hydrogen sulfide
H₂SO₄ = sulfuric acid
HAP = hazardous air pollutant as listed in § 112(b) of the Federal Clean Air Act or Title 40 Code of Federal Regulations Part 63, Subpart C
HC = hydrocarbons
HCl = hydrochloric acid, hydrogen chloride
Hg = mercury
HGB = Houston/Galveston/Brazoria
hp = horsepower
hr = hour
IFR = internal floating roof tank
in H₂O = inches of water
in Hg = inches of mercury
IR = infrared
ISC3 = Industrial Source Complex, a dispersion model
ISCST3 = Industrial Source Complex Short-Term, a dispersion model
K = Kelvin; extension of the degree Celsius scaled-down to absolute zero
LACT = lease automatic custody transfer
LAER = lowest achievable emission rate
lb = pound
hp = horsepower
hr = hour
lb/day = pound per day
lb/hr = pound per hour
lb/MMBtu = pound per million British thermal units
LDAR = Leak Detection and Repair (Requirements)
LNG = liquefied natural gas
LPG = liquefied petroleum gas
LT/D = long ton per day
m = meter
m³ = cubic meter
m/sec = meters per second
MACT = maximum achievable control technology
MAERT = Maximum Allowable Emission Rate Table
MERA = Modeling and Effects Review Applicability
mg = milligram
mg/g = milligram per gram
mL = milliliter
MMBtu = million British thermal units
MMBtu/hr = million British thermal units per hour
MSDS = material safety data sheet
MSS = maintenance, startup, and shutdown
MW = megawatt
NAAQS = National Ambient Air Quality Standards
NESHAP = National Emission Standards for Hazardous Air Pollutants
NGL = natural gas liquids
NNSR = nonattainment new source review
NO_x = total oxides of nitrogen
NSPS = New Source Performance Standards
PAL = plant-wide applicability limit
PBR = Permit(s) by Rule

PCP = pollution control project
PEMS = predictive emission monitoring system
PID = photo ionization detector
PM = periodic monitoring
PM = total particulate matter, suspended in the atmosphere, including PM₁₀ and PM_{2.5}, as represented
PM_{2.5} = particulate matter equal to or less than 2.5 microns in diameter
PM₁₀ = total particulate matter equal to or less than 10 microns in diameter, including PM_{2.5}, as represented
POC = products of combustion
ppb = parts per billion
ppm = parts per million
ppmv = parts per million (by) volume
psia = pounds (per) square inch, absolute
psig = pounds (per) square inch, gage
PTE = potential to emit
RA = relative accuracy
RATA = relative accuracy test audit
RM = reference method
RVP = Reid vapor pressure
scf = standard cubic foot or feet
scfm = standard cubic foot or feet (per) minute
SCR = selective catalytic reduction
SIL = significant impact levels
SNCR = selective non-catalytic reduction
SO₂ = sulfur dioxide
SOCMI = synthetic organic chemical manufacturing industry
SRU = sulfur recovery unit
TAC = Texas Administrative Code
TCAA = Texas Clean Air Act
TCEQ = Texas Commission on Environmental Quality
TD = Toxicology Division
TLV = threshold limit value
TMDL = total maximum daily load
tpd = tons per day
tpy = tons per year
TVP = true vapor pressure
VOC = volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1
VRU = vapor recovery unit or system

Special Conditions

Permit Numbers 9488 and PSDTX637

1. This permit authorizes two natural gas engines and associated operations located at Yates Gas Plant on Gas Plant Road 2 miles south of Iraan, Pecos County.
2. This permit covers only those sources of emissions listed in the attached table entitled "Emission Sources - Maximum Allowable Emission Rates," and those sources are limited to the emission limits and other conditions specified in that attached table. The annual rates are based on any consecutive 12-month period.
3. The following sources are authorized under Title 30 Texas Administrative Code Chapter 106 (30 TAC Chapter 106):

Emission Sources	Permit by Rule (PBR) No.
Oil and Gas Handling and Production Facilities	§106.352
Organic and Inorganic Liquid Loading and Unloading	§106.472
Storage Tank and Change of Service	§106.478
Smokeless Gas Flares	Standard Exemption 80 (August 16, 1993) Registration No. 23596

4. All non-fugitive sources of air contaminants shall be physically marked in a conspicuous location with the emission point numbers (EPNs) and/or the source names as identified on the Maximum Allowable Emission Rates Table (MAERT).

Federal Applicability

5. These facilities shall comply with applicable requirements of the U.S. Environmental Protection Agency (EPA) regulations in Title 40 Code of Federal Regulations Part 60, (40 CFR Part 60) on Standards of Performance for New Stationary Sources promulgated for:
 - A. Applicable General Conditions, Subpart A.
 - B. Standards of Performance for Equipment Leaks of VOC From Onshore Natural Gas Processing Plants for Which Construction, Reconstruction, or Modification Commenced After January 20, 1984, and on or Before August 23, 2011, Subpart KKK.
6. If any condition of this permit is more stringent than the regulations so incorporated, then for the purposes of complying with this permit, the permit shall govern and be the standard by which compliance shall be demonstrated.

Emission Standards and Operating Specifications

7. During normal operations, emissions of nitrogen oxides (NO_x) shall not exceed 5.0 grams per horsepower hour from the two engines of this permit, identified as Emission Point Nos. C 12 and C 13.
8. Fuel use is limited to sweet natural gas containing no more than 0.25 grain total sulfur per 100 dry standard cubic feet.

Compliance Determination

9. Documentation for both engines shall be kept for emissions of NO_x and carbon monoxide (CO), measured biennially in odd numbered years in accordance with the EPA Reference Method 7E or 20 for NO_x and Method 10 for CO. Exhaust flow rate may be determined from measured fuel flow rate and EPA Method 19. California Air Resources Board Method A-100 (adopted June 29, 1983) is an acceptable alternate to EPA test methods. Modifications to these methods will be subject to the prior approval of the Texas Commission on Environmental Quality (TCEQ) Office of Air, Air Permits Division. Emissions shall be measured and recorded in the as-found operating condition; however, compliance determinations shall not be established during start-up, shutdown, or under breakdown conditions. Any such engine shall be sampled no less frequently than biennially (or every 15,000 hours of elapsed run time, as recorded by an elapsed run time meter) and upon request of the TCEQ Executive Director. In lieu of performing stack sampling on a biennial calendar basis, an owner or operator may elect to install and operate an elapsed operating time meter and shall test the engine within 15,000 hours of engine operation after the previous emission test. The owner or operator who elects to test on an operating hour schedule shall submit in writing, to the appropriate TCEQ Regional Office, biennially after initial sampling, documentation of the actual recorded hours of engine operation since the previous emission test, and an estimate of the date of the next required sampling.

Recordkeeping Requirements

10. The following records shall be kept at the plant for the life of the permit. All records required in this permit shall be made available at the request of personnel from the TCEQ, EPA, or any air pollution control agency with jurisdiction.
 - A. A copy of this permit.
 - B. Permit renewal application dated February 1, 2012 and subsequent representations submitted to the TCEQ.
 - C. A complete copy of the testing reports and records of the initial performance testing completed pursuant to Special Condition No. 9 to demonstrate initial compliance.
 - D. Stack sampling results or other air emissions testing that may be conducted on units authorized under this permit after the date of issuance of this permit.

11. The following information shall be maintained by the holder of this permit in a form suitable for inspection for a period of five years after collection and shall be made immediately available upon request to representatives of the TCEQ, EPA, or any local air pollution control program having jurisdiction:
 - A. A complete copy of the monitoring reports of the performance monitoring completed pursuant to Special Condition 9 to demonstrate compliance with this permit.
 - B. Records sufficient to document compliance with the applicable requirements of 40 CFR Part 60, Subparts A and KKK.

Dated: April 10, 2013

Emission Sources - Maximum Allowable Emission Rates

Permit Numbers 9488 and PSDTX637

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities, sources, and related activities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

Air Contaminants Data

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lbs/hour	TPY (4)
C-12	2,000-hp Gas-Fired Clark TLAB-6 Compressor Engine 12P	NO _x	22.0	96.5
		CO	8.8	38.6
		VOC	1.72	7.5
		HCHO (5)	0.789	3.46
		PM ₁₀	0.69	3.0
		PM _{2.5}	0.69	3.0
		SO ₂	0.013	0.06
C-13	2,000-hp Gas-Fired Clark TLAB-6 Compressor Engine 13P	NO _x	22.0	96.5
		CO	8.8	38.6
		VOC	1.72	7.5
		HCHO (5)	0.789	3.46
		PM ₁₀	0.69	3.0
		PM _{2.5}	0.69	3.0
		SO ₂	0.013	0.06

- (1) Emission point identification - either specific equipment designation or emission point number from plot plan.
- (2) Specific point source name. For fugitive sources, use area name or fugitive source name.
- (3) VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1
- HCHO - formaldehyde
- NO_x - total oxides of nitrogen
- SO₂ - sulfur dioxide
- PM₁₀ - total particulate matter equal to or less than 10 microns in diameter, including PM_{2.5}, as represented
- PM_{2.5} - particulate matter equal to or less than 2.5 microns in diameter
- CO - carbon monoxide
- HAP - hazardous air pollutant as listed in § 112(b) of the Federal Clean Air Act or Title 40 Code of Federal Regulations Part 63, Subpart C
- (4) Compliance with annual emission limits (tons per year) is based on a 12 month rolling period.
- (5) HCHO (formaldehyde) is a HAP and a subspecies of VOC. The VOC emission limits are inclusive of HCHO.

Date: April 10, 2013

Emission Sources - Maximum Allowable Emission Rates



Texas Commission on Environmental Quality Air Quality Permit

A Permit Is Hereby Issued To
Kinder Morgan Production Company LLC
Authorizing the Continued Operation of
Yates Gas Plant
Located at Iraan, Pecos County, Texas
Latitude 30° 53' 7" Longitude -101° 55' 17"

Permit: 9608 and PSDTX654M2

Issuance Date: November 14, 2018

Expiration Date: November 14, 2028

For the Commission

- Facilities** covered by this permit shall be constructed and operated as specified in the application for the permit. All representations regarding construction plans and operation procedures contained in the permit application shall be conditions upon which the permit is issued. Variations from these representations shall be unlawful unless the permit holder first makes application to the Texas Commission on Environmental Quality (commission) Executive Director to amend this permit in that regard and such amendment is approved. [Title 30 Texas Administrative Code (TAC) Section 116.116 (30 TAC § 116.116)]¹
- Voiding of Permit.** A permit or permit amendment is automatically void if the holder fails to begin construction within 18 months of the date of issuance, discontinues construction for more than 18 months prior to completion, or fails to complete construction within a reasonable time. Upon request, the executive director may grant an 18-month extension. Before the extension is granted the permit may be subject to revision based on best available control technology, lowest achievable emission rate, and netting or offsets as applicable. One additional extension of up to 18 months may be granted if the permit holder demonstrates that emissions from the facility will comply with all rules and regulations of the commission, the intent of the Texas Clean Air Act (TCAA), including protection of the public's health and physical property; and (b)(1) the permit holder is a party to litigation not of the permit holder's initiation regarding the issuance of the permit; or (b)(2) the permit holder has spent, or committed to spend, at least 10 percent of the estimated total cost of the project up to a maximum of \$5 million. A permit holder granted an extension under subsection (b)(1) of this section may receive one subsequent extension if the permit holder meets the conditions of subsection (b)(2) of this section. [30 TAC § 116.120]
- Construction Progress.** Start of construction, construction interruptions exceeding 45 days, and completion of construction shall be reported to the appropriate regional office of the commission not later than 15 working days after occurrence of the event. [30 TAC § 116.115(b)(2)(A)]
- Start-up Notification.** The appropriate air program regional office shall be notified prior to the commencement of operations of the facilities authorized by the permit in such a manner that a representative of the commission may be present. The permit holder shall provide a separate notification for the commencement of operations for each unit of phased construction, which may involve a series of units commencing operations at different times. Prior to operation of the facilities authorized by the permit, the permit holder shall identify the source or sources of allowances to be utilized for compliance with Chapter 101, Subchapter H, Division 3 of this title (relating to Mass Emissions Cap and Trade Program). [30 TAC § 116.115(b)(2)(B)]
- Sampling Requirements.** If sampling is required, the permit holder shall contact the commission's Office of Compliance and Enforcement prior to sampling to obtain the proper data forms and procedures. All sampling and testing procedures must be approved by the executive director and coordinated with the regional representatives of the commission. The permit holder is also responsible for providing sampling facilities and conducting the sampling operations or contracting with an independent sampling consultant. [30 TAC § 116.115(b)(2)(C)]
- Equivalency of Methods.** The permit holder must demonstrate or otherwise justify the equivalency of emission control methods, sampling or other emission testing methods, and monitoring methods proposed as alternatives to methods indicated in the conditions of the permit. Alternative methods shall be applied for in writing and must be reviewed and approved by the executive director prior to their use in fulfilling any requirements of the permit. [30 TAC § 116.115(b)(2)(D)]
- Recordkeeping.** The permit holder shall maintain a copy of the permit along with records containing the information and data sufficient to demonstrate compliance with the permit, including production records and operating hours;

keep all required records in a file at the plant site. If, however, the facility normally operates unattended, records shall be maintained at the nearest staffed location within Texas specified in the application; make the records available at the request of personnel from the commission or any air pollution control program having jurisdiction in a timely manner; comply with any additional recordkeeping requirements specified in special conditions in the permit; and retain information in the file for at least two years following the date that the information or data is obtained. [30 TAC § 116.115(b)(2)(E)]

8. **Maximum Allowable Emission Rates.** The total emissions of air contaminants from any of the sources of emissions must not exceed the values stated on the table attached to the permit entitled "Emission Sources-- Maximum Allowable Emission Rates." [30 TAC § 116.115(b)(2)(F)]¹
9. **Maintenance of Emission Control.** The permitted facilities shall not be operated unless all air pollution emission capture and abatement equipment is maintained in good working order and operating properly during normal facility operations. The permit holder shall provide notification in accordance with 30 TAC §101.201, 101.211, and 101.221 of this title (relating to Emissions Event Reporting and Recordkeeping Requirements; Scheduled Maintenance, Startup, and Shutdown Reporting and Recordkeeping Requirements; and Operational Requirements). [30 TAC§ 116.115(b)(2)(G)]
10. **Compliance with Rules.** Acceptance of a permit by an applicant constitutes an acknowledgment and agreement that the permit holder will comply with all rules and orders of the commission issued in conformity with the TCAA and the conditions precedent to the granting of the permit. If more than one state or federal rule or regulation or permit condition is applicable, the most stringent limit or condition shall govern and be the standard by which compliance shall be demonstrated. Acceptance includes consent to the entrance of commission employees and agents into the permitted premises at reasonable times to investigate conditions relating to the emission or concentration of air contaminants, including compliance with the permit. [30 TAC § 116.115(b)(2)(H)]
11. **This** permit may not be transferred, assigned, or conveyed by the holder except as provided by rule. [30 TAC § 116.110(e)]
12. **There** may be additional special conditions attached to a permit upon issuance or modification of the permit. Such conditions in a permit may be more restrictive than the requirements of Title 30 of the Texas Administrative Code. [30 TAC § 116.115(c)]
13. **Emissions** from this facility must not cause or contribute to "air pollution" as defined in Texas Health and Safety Code (THSC) §382.003(3) or violate THSC § 382.085. If the executive director determines that such a condition or violation occurs, the holder shall implement additional abatement measures as necessary to control or prevent the condition or violation.
14. **The** permit holder shall comply with all the requirements of this permit. Emissions that exceed the limits of this permit are not authorized and are violations of this permit.¹

¹ Please be advised that the requirements of this provision of the general conditions may not be applicable to greenhouse gas emissions.

SPECIAL CONDITIONS

Permit Numbers 9608 and PSD-TX-654M2

EMISSION LIMITS

1. This permit authorizes emissions only from those points listed in the attached table entitled A Emission Sources - Maximum Allowable Emission Rates and the facilities covered by this permit are authorized to emit subject to the emission rate limits on that table and other operating requirements specified in the special conditions. **PSD**
2. The Turbines identified as Emission Point Nos. (EPNs) D2, E1E, and E1W shall comply with all applicable requirements of the U.S. Environmental Protection Agency regulations in Title 40 Code of Federal Regulations Part 60, Subparts A and GG on Stationary Gas Turbines. (Subpart GG does not apply to the Waste Heat Boiler identified as EPN E1.) **PSD**
3. These facilities authorized in this permit shall comply with all applicable requirements of the U.S. Environmental Protection Agency regulations in Title 40 Code of Federal Regulations Part 63, Subpart HH on Oil and Natural Gas Production Facilities.
4. Emissions of carbon monoxide (CO) shall not exceed 4.0 grams per horsepower hour (g/hp-hr) and emissions of nitrogen oxides (NO_x) shall not exceed 5.0 g/hp-hr during normal operation from Emission Point Nos. C-15, C-16, D2, E1, E1E, and E1W. The sweet gas fired waste heat boiler that vents through EPN E1 is not subject to the requirements of this special condition. **PSD**
5. Combustible or oxygen (O₂) content of the exhaust of the two reciprocating engines designated as EPNs C15 and C16 shall be checked at least once a month and the engine air/fuel ratio adjusted as necessary to ensure the combustibles or O₂ content is adequate to maintain emissions of NO_x of no more than 5.0 g/hr-hr. Monthly monitoring records shall be maintained on a rolling two year basis by the permit holder and made readily available at the request of EPA and/or TCEQ personnel. An automatic air fuel ratio (AFR) controller may be installed in lieu of the manual monitoring and recordkeeping requirements of this special condition. **PSD**
6. Fuel use for each gas fired turbine, gas fired compressor engine and gas fired waste heat boiler is limited to sweet natural gas containing no more than 0.25 grain total sulfur per 100 dry standard cubic feet. The use of any other fuel will require an amendment to this permit. **PSD**
7. The glycol regenerator vent VOC emissions shall be directed for injection into the Yates Field Reservoir under normal operation. Planned maintenance, start-up, and shutdown activities and emissions are not authorized by this special condition.

SPECIAL CONDITIONS

Permit Numbers 9608 and PSD-TX-654M2

Page 2

8. These facilities shall comply with all requirements of the U.S. Environmental Protection Agency regulations on Standards of Performance for New Stationary Sources promulgated for Equipment Leaks of VOC from Onshore Natural Gas Processing Plants in Title 40 Code of Federal Regulations Part 60, Subparts A and KKK.

INITIAL DETERMINATION OF COMPLIANCE

9. A. The holder of this permit shall perform stack sampling and other testing as required to determine the quantity of CO and NO_x being emitted from the compressor engines designated as EPNs C15 or C16 and D2 or E1. Emissions shall be determined by Environmental Protection Agency (EPA) Methods 1, 2, 3, 4, 10, and 20 or any other methods approved by the Executive Director of the TCEQ prior to sampling. Emissions shall be sampled at four points over the normal load range of the engine, including the minimum and maximum of the range. The adjusted NO_x emission level shall be used to determine compliance with the brake specific emission limits of this permit. **PSD**

(Stack sampling was completed in 1986 for each EPN.)

- B. Sampling ports shall consist of two 2 inch diameter or larger schedule 40 couplings or 3-inch long pipe nipples installed in the exhaust system according to EPA Method 1 at a location where the full flow of the engine exhaust sweeps by the sampling point and where sufficient turbulence (no stratification) may be expected to insure a representative sample. A temporary work platform for sampling operations is acceptable if proper safety and accessibility is provided. All other requirements detailed in Chapter 2 of the TCEQ Sampling Procedures Manual pertaining to monorails, ports, loading clearance and power must be met by the temporary facilities. **PSD**
- C. The appropriate TCEQ Regional Office shall be notified as soon as testing is scheduled but not less than 45 days prior to sampling to schedule a pretest meeting. **PSD**

The notice shall include:

- (1) Date for pretest meeting.
- (2) Date sampling will occur.
- (3) Name of firm conducting sampling.
- (4) Type of sampling equipment to be used.
- (5) Method or procedure to be used in sampling.
- (6) Procedure to be used to determine engine horsepower load during sampling period.

SPECIAL CONDITIONS

Permit Numbers 9608 and PSD-TX-654M2

Page 3

A written proposed description of any deviation from sampling procedures specified in permit conditions or the TCEQ or the EPA sampling procedures shall be made available to the TCEQ at or prior to the pretest meeting. The TCEQ Midland Regional Director shall approve or disapprove of any deviation from specified sampling procedures after consultation with the EPA. Requests to waive testing for any pollutant specified in this condition shall be submitted to the TCEQ Air Permits Division. Test waivers and alternate/equivalent procedure proposals for New Source Performance Standards testing which must have the EPA approval shall be submitted to the TCEQ Compliance Support Division in Austin for further review and approval by the EPA. **PSD (1/09)**

- D. Sampling shall occur within 60 days after the facilities achieve maximum production, but not later than 180 days after initial start-up of the facilities and at such other times as may be required by the Executive Director of the TCEQ or the Regional Administrator of the EPA. Additional time to comply with the requirements of 40 CFR Part 60 cannot be granted. **PSD (1/09)**
- E. Copies of the final sampling report shall be forwarded to the TCEQ Regional Office and Air Enforcement Branch, EPA, Dallas within 45 days after sampling is completed. Sampling reports shall comply with the provisions of Chapter 14 of the TCEQ Sampling Procedure Manual. The reports shall be distributed to the nearest TCEQ Regional Office and the EPA Region 6 NSR Permit Section, Dallas, Texas. **PSD (1/09)**

Dated June 8, 2009

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

Permit Numbers 9608 and PSD-TX-654M2

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY**
C15	Ingersoll Rand KVSR 2,600 hp Four Stroke Lean Burn	CO (5)	22.93	100.42
		NO _x (5)	28.66	125.53
		PM/PM ₁₀	0.22	0.97
		SO ₂	0.02	0.06
		VOC	2.50	10.95
C16	Ingersoll Rand KVSR 2,600 hp Four Stroke Lean Burn	CO (5)	22.93	100.42
		NO _x (5)	28.66	125.53
		PM/PM ₁₀	0.22	0.97
		SO ₂	0.02	0.06
		VOC	2.50	10.95
D2	Processed Gas Compressor One 4,100 hp Solar T-4500	CO (5)	3.04	13.31
		NO _x (5)	11.86	51.94
		PM/PM ₁₀	0.25	1.07
		SO ₂	0.13	0.55
		VOC	0.08	0.34
E1	Generator Set 8,200 hp (6) Two 36 MMBtu/hr Solar T-4500s One 19.0 MMBtu/hr WHB	CO (5)	7.64	
		NO _x (5)	25.58	
		PM/PM ₁₀	0.64	
		SO ₂	0.27	
		VOC	0.26	
E1E	East Generator 4,100 hp (6) One 36 MMBtu/hr Solar T-4500	CO (5)	3.04	
		NO _x (5)	11.86	
		PM/PM ₁₀	0.25	
		SO ₂	0.13	
		VOC	0.08	
E1W	West Generator 4,100 hp (6) One 36 MMBtu/hr Solar T-4500	CO (5)	3.04	
		NO _x (5)	11.86	
		PM/PM ₁₀	0.25	
		SO ₂	0.13	
		VOC	0.08	

EMISSION SOURCES - MAXIMUM ALLOWABLE EMISSION RATES

AIR CONTAMINANTS DATA

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates *	
			lb/hr	TPY**
E1, E1E, and E1W	Annual Emissions (6)	CO (5)		33.47
		NO _x (5)		112.04
		PM/PM ₁₀		2.76
		SO ₂		1.15
		VOC		1.13
FUG-2	Process Fugitives (4)	H ₂ S	0.05	0.20
		VOC	0.04	0.18
FUG-NGP	Process Fugitives (4)	H ₂ S	0.31	1.35
		VOC	0.48	2.10

- (1) Emission point identification - either specific equipment designation or emission point number from plot plan.
- (2) Specific point source name. For fugitive sources use area name or fugitive source name.
- (3) CO - carbon monoxide
NO_x - total oxides of nitrogen
PM - particulate matter, suspended in the atmosphere, including PM₁₀
PM₁₀ - particulate matter equal to or less than 10 microns in diameter
SO₂ - sulfur dioxide
VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1
H₂S - hydrogen sulfide
- (4) Fugitive emissions are an estimate only and should not be considered as a maximum allowable emission rate.
- (5) A PSD-TX-654M2 pollutant
- (6) Emissions from EPN E1 will not occur at the same time as emissions from EPN E1E or E1W.

* Emission rates are based on and the facilities are limited by the following maximum operating schedule:

24 Hrs/day 7 Days/week 52 Weeks/year

** Compliance with annual emission limits is based on a rolling 12-month period.

Dated June 8, 2009

Texas Commission on Environmental Quality Air Quality Permit

A Permit Is Hereby Issued To
Kinder Morgan Production Company LLC
Authorizing the Continued Operation of
Yates Gas Plant
Located at Iraan, Pecos County, Texas
Latitude 30.8844 Longitude -101.9202

Permit: 17800 and PSDTX718

Issuance Date: August 11, 2023

Expiration Date: August 11, 2033



For the Commission

1. **Facilities** covered by this permit shall be constructed and operated as specified in the application for the permit. All representations regarding construction plans and operation procedures contained in the permit application shall be conditions upon which the permit is issued. Variations from these representations shall be unlawful unless the permit holder first makes application to the Texas Commission on Environmental Quality (commission) Executive Director to amend this permit in that regard and such amendment is approved. [Title 30 Texas Administrative Code (TAC) Section 116.116 (30 TAC § 116.116)]¹
2. **Voiding of Permit.** A permit or permit amendment is automatically void if the holder fails to begin construction within 18 months of the date of issuance, discontinues construction for more than 18 months prior to completion, or fails to complete construction within a reasonable time. Upon request, the executive director may grant an 18-month extension. Before the extension is granted the permit may be subject to revision based on best available control technology, lowest achievable emission rate, and netting or offsets as applicable. One additional extension of up to 18 months may be granted if the permit holder demonstrates that emissions from the facility will comply with all rules and regulations of the commission, the intent of the Texas Clean Air Act (TCAA), including protection of the public's health and physical property; and (b)(1) the permit holder is a party to litigation not of the permit holder's initiation regarding the issuance of the permit; or (b)(2) the permit holder has spent, or committed to spend, at least 10 percent of the estimated total cost of the project up to a maximum of \$5 million. A permit holder granted an extension under subsection (b)(1) of this section may receive one subsequent extension if the permit holder meets the conditions of subsection (b)(2) of this section. [30 TAC § 116.120]
3. **Construction Progress.** Start of construction, construction interruptions exceeding 45 days, and completion of construction shall be reported to the appropriate regional office of the commission not later than 15 working days after occurrence of the event. [30 TAC § 116.115(b)(2)(A)]
4. **Start-up Notification.** The appropriate air program regional office shall be notified prior to the commencement of operations of the facilities authorized by the permit in such a manner that a representative of the commission may be present. The permit holder shall provide a separate notification for the commencement of operations for each unit of phased construction, which may involve a series of units commencing operations at different times. Prior to operation of the facilities authorized by the permit, the permit holder shall identify the source or sources of allowances to be utilized for compliance with Chapter 101, Subchapter H, Division 3 of this title (relating to Mass Emissions Cap and Trade Program). [30 TAC § 116.115(b)(2)(B)]
5. **Sampling Requirements.** If sampling is required, the permit holder shall contact the commission's Office of Compliance and Enforcement prior to sampling to obtain the proper data forms and procedures. All sampling and testing procedures must be approved by the executive director and coordinated with the regional representatives of the commission. The permit holder is also responsible for providing sampling facilities and conducting the sampling operations or contracting with an independent sampling consultant. [30 TAC § 116.115(b)(2)(C)]
6. **Equivalency of Methods.** The permit holder must demonstrate or otherwise justify the equivalency of emission control methods, sampling or other emission testing methods, and monitoring methods proposed as alternatives to methods indicated in the conditions of the permit. Alternative methods shall be applied for in writing and must be reviewed and approved by the executive director prior to their use in fulfilling any requirements of the permit. [30 TAC § 116.115(b)(2)(D)]
7. **Recordkeeping.** The permit holder shall maintain a copy of the permit along with records containing the information and data sufficient to demonstrate compliance with the permit, including production records and operating hours;

keep all required records in a file at the plant site. If, however, the facility normally operates unattended, records shall be maintained at the nearest staffed location within Texas specified in the application; make the records available at the request of personnel from the commission or any air pollution control program having jurisdiction in a timely manner; comply with any additional recordkeeping requirements specified in special conditions in the permit; and retain information in the file for at least two years following the date that the information or data is obtained. [30 TAC § 116.115(b)(2)(E)]

8. **Maximum Allowable Emission Rates.** The total emissions of air contaminants from any of the sources of emissions must not exceed the values stated on the table attached to the permit entitled "Emission Sources-- Maximum Allowable Emission Rates." [30 TAC § 116.115(b)(2)(F)]¹
9. **Maintenance of Emission Control.** The permitted facilities shall not be operated unless all air pollution emission capture and abatement equipment is maintained in good working order and operating properly during normal facility operations. The permit holder shall provide notification in accordance with 30 TAC §101.201, 101.211, and 101.221 of this title (relating to Emissions Event Reporting and Recordkeeping Requirements; Scheduled Maintenance, Startup, and Shutdown Reporting and Recordkeeping Requirements; and Operational Requirements). [30 TAC§ 116.115(b)(2)(G)]
10. **Compliance with Rules.** Acceptance of a permit by an applicant constitutes an acknowledgment and agreement that the permit holder will comply with all rules and orders of the commission issued in conformity with the TCAA and the conditions precedent to the granting of the permit. If more than one state or federal rule or regulation or permit condition is applicable, the most stringent limit or condition shall govern and be the standard by which compliance shall be demonstrated. Acceptance includes consent to the entrance of commission employees and agents into the permitted premises at reasonable times to investigate conditions relating to the emission or concentration of air contaminants, including compliance with the permit. [30 TAC § 116.115(b)(2)(H)]
11. **This** permit may not be transferred, assigned, or conveyed by the holder except as provided by rule. [30 TAC § 116.110(e)]
12. **There** may be additional special conditions attached to a permit upon issuance or modification of the permit. Such conditions in a permit may be more restrictive than the requirements of Title 30 of the Texas Administrative Code. [30 TAC § 116.115(c)]
13. **Emissions** from this facility must not cause or contribute to "air pollution" as defined in Texas Health and Safety Code (THSC) §382.003(3) or violate THSC § 382.085. If the executive director determines that such a condition or violation occurs, the holder shall implement additional abatement measures as necessary to control or prevent the condition or violation.
14. **The** permit holder shall comply with all the requirements of this permit. Emissions that exceed the limits of this permit are not authorized and are violations of this permit.¹

¹ Please be advised that the requirements of this provision of the general conditions may not be applicable to greenhouse gas emissions.

Common Acronyms in Air Permits

°C = Temperature in degrees Celsius	gpm = gallon per minute
°F = Temperature in degrees Fahrenheit	gr/100scf = grain per 100 standard cubic feet
°K = Temperature in degrees Kelvin	gr/dscf = grain per dry standard cubic feet
µg = microgram	H ₂ CO = formaldehyde
µg/m ³ = microgram per cubic meter	H ₂ S = hydrogen sulfide
acfm = actual cubic feet per minute	H ₂ SO ₄ = sulfuric acid
AMOC = alternate means of control	HAP = hazardous air pollutant as listed in § 112(b) of the Federal Clean Air Act or Title 40 Code of Federal Regulations Part 63, Subpart C
AOS = alternative operating scenario	HC = hydrocarbons
AP-42 = Air Pollutant Emission Factors, 5th edition	HCl = hydrochloric acid, hydrogen chloride
APD = Air Permits Division	Hg = mercury
API = American Petroleum Institute	HGB = Houston/Galveston/Brazoria
APWL = air pollutant watch list	hp = horsepower
BPA = Beaumont/ Port Arthur	hr = hour
BACT = best available control technology	IFR = internal floating roof tank
BAE = baseline actual emissions	in H ₂ O = inches of water
bbl = barrel	in Hg = inches of mercury
bbl/day = barrel per day	IR = infrared
bhp = brake horsepower	ISC3 = Industrial Source Complex, a dispersion model
BMP = best management practices	ISCST3 = Industrial Source Complex Short-Term, a dispersion model
Btu = British thermal unit	K = Kelvin; extension of the degree Celsius scaled-down to absolute zero
Btu/scf = British thermal unit per standard cubic foot or feet	LACT = lease automatic custody transfer
CAA = Clean Air Act	LAER = lowest achievable emission rate
CAM = compliance-assurance monitoring	lb = pound
CEMS = continuous emissions monitoring systems	lb/day = pound per day
cfm = cubic feet (per) minute	lb/hr = pound per hour
CFR = Code of Federal Regulations	lb/MMBtu = pound per million British thermal units
CN = customer ID number	LDAR = Leak Detection and Repair (Requirements)
CNG = compressed natural gas	LNG = liquefied natural gas
CO = carbon monoxide	LPG = liquefied petroleum gas
COMS = continuous opacity monitoring system	LT/D = long ton per day
CPMS = continuous parametric monitoring system	m = meter
DFW = Dallas/ Fort Worth (Metroplex)	m ³ = cubic meter
DE = destruction efficiency	m/sec = meters per second
DRE = destruction and removal efficiency	MACT = maximum achievable control technology
dscf = dry standard cubic foot or feet	MAERT = Maximum Allowable Emission Rate Table
dscfm = dry standard cubic foot or feet per minute	MERA = Modeling and Effects Review Applicability
ED = (TCEQ) Executive Director	mg = milligram
EF = emissions factor	mg/g = milligram per gram
EFR = external floating roof tank	mL = milliliter
EGU = electric generating unit	MMBtu = million British thermal units
EI = Emissions Inventory	MMBtu/hr = million British thermal units per hour
ELP = El Paso	MSDS = material safety data sheet
EPA = (United States) Environmental Protection Agency	MSS = maintenance, startup, and shutdown
EPN = emission point number	MW = megawatt
ESL = effects screening level	NAAQS = National Ambient Air Quality Standards
ESP = electrostatic precipitator	NESHAP = National Emission Standards for Hazardous Air Pollutants
FCAA = Federal Clean Air Act	NGL = natural gas liquids
FCCU = fluid catalytic cracking unit	NNSR = nonattainment new source review
FID = flame ionization detector	NO _x = total oxides of nitrogen
FIN = facility identification number	NSPS = New Source Performance Standards
ft = foot or feet	PAL = plant-wide applicability limit
ft/sec = foot or feet per second	PBR = Permit(s) by Rule
g = gram	PCP = pollution control project
gal/wk = gallon per week	
gal/yr = gallon per year	
GLC = ground level concentration	
GLC _{max} = maximum (predicted) ground-level concentration	

PEMS = predictive emission monitoring system
PID = photo ionization detector
PM = periodic monitoring
PM = total particulate matter, suspended in the atmosphere, including PM₁₀ and PM_{2.5}, as represented
PM_{2.5} = particulate matter equal to or less than 2.5 microns in diameter
PM₁₀ = total particulate matter equal to or less than 10 microns in diameter, including PM_{2.5}, as represented
POC = products of combustion
ppb = parts per billion
ppm = parts per million
ppmv = parts per million (by) volume
psia = pounds (per) square inch, absolute
psig = pounds (per) square inch, gage
PTE = potential to emit
RA = relative accuracy
RATA = relative accuracy test audit
RM = reference method
RVP = Reid vapor pressure
scf = standard cubic foot or feet
scfm = standard cubic foot or feet (per) minute
SCR = selective catalytic reduction
SIL = significant impact levels
SNCR = selective non-catalytic reduction
SO₂ = sulfur dioxide
SOCMI = synthetic organic chemical manufacturing industry
SRU = sulfur recovery unit
TAC = Texas Administrative Code
TCAA = Texas Clean Air Act
TCEQ = Texas Commission on Environmental Quality
TD = Toxicology Division
TLV = threshold limit value
TMDL = total maximum daily load
tpd = tons per day
tpy = tons per year
TVP = true vapor pressure
VOC = volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1
VRU = vapor recovery unit or system

Special Conditions

Permit Numbers 17800 and PSDTX718

1. This permit covers only those sources of emissions listed in the attached table entitled “Emission Sources - Maximum Allowable Emission Rates,” and those sources are limited to the emission limits and other conditions specified in that attached table. Compliance with the annual emission limits and operating schedules is based on a consecutive 12-month period rather than the calendar year.

Federal Applicability

2. The facilities operated under this permit shall comply with all applicable requirements of the U.S. Environmental Protection Agency (EPA) regulations in Title 40 Code of Federal Regulations Part 60 (40 CFR Part 60) on Standards of Performance for New Stationary Sources promulgated for:
 - A. Subpart A: General Provisions;
 - B. Subpart KKK: Equipment Leaks of volatile organic compounds from Onshore Natural Gas Processing Plants; and
 - C. Subpart KKKK: Standards of Performance for Stationary Combustion Turbines.

If any condition of this permit is more stringent than the regulations so incorporated, then for the purposes of complying with this permit, the permit shall govern and be the standard by which compliance shall be demonstrated.

3. These facilities shall comply with applicable requirements of the EPA regulations on National Emission Standards for Hazardous Air Pollutants for Source Categories, 40 CFR Part 63:
 - A. Subpart A: General Provisions.
 - B. Subpart YYYY: National Emission Standard for Hazardous Air Pollutants for Stationary Combustion Turbines.

If any condition of this permit is more stringent than the regulations so incorporated, then for the purposes of complying with this permit, the permit shall govern and be the standard by which compliance shall be demonstrated.

Emission Standards and Operating Specifications

4. This permit authorizes one Solar Centaur 50-5900L natural gas fired combustion turbine, Emission Point Number (EPN) U1, rated at a nominal output of 5000 horsepower.

5. Emission Rates
 - A. The concentration of nitrogen oxides (NO_x) in the stack gases from the turbine shall not exceed 150 parts per million by volume dry (ppmvd) per 40 CFR § 60.4320(a) and Table 1. For determining initial compliance with this provision, measured stack concentrations shall be expressed on a dry basis at 15 percent oxygen (O₂) and shall be determined from a rolling three-hour average as per 60.4400(a).
 - B. Reduced load operation below base load is authorized, provided the maximum NO_x concentrations of this permit condition are not exceeded and provided the maximum pounds per hour (lb/hr) emission rates specified in the attached table entitled "Emission Sources - Maximum Allowable Emission Rates" for Emission Point Number U1 are not exceeded.
6. Fuel used is limited to pipeline quality sweet natural gas containing no more than 0.25 grain hydrogen sulfide per 100 dry standard cubic feet (dscf).
7. Upon request by the Executive Director of the Texas Commission on Environmental Quality (TCEQ) or any air pollution control program having jurisdiction, the holder of this permit shall provide a sample and/or an analysis of the fuel fired in the gas turbine or shall allow air pollution control agency representatives to obtain a sample for analysis.
8. Opacity of particulate matter emissions shall not exceed twenty percent averaged over a six-minute period from EPN U1. This determination shall be made by first observing for visible emissions while the facility is operating. Observations shall be made at least 15 feet and no more than 0.25 mile from the emission point. If visible emissions are observed from the stack, then opacity may be determined by 40 CFR Part 60, Appendix A, Test Method 9. The opacity observation as determined by 40 CFR Part 60, Appendix A, Test Method 9 may be performed by a third party contractor within 48 hours following the visible emissions observation. Contributions from uncombined water shall not be included in determining compliance with this condition. Observations shall be performed and recorded quarterly. If opacity exceeds twenty percent or if visible emissions are observed and no Method 9 measurement is taken, corrective action to eliminate the source of visible emissions shall be taken within 48 hours and documented within one week of first observation.

Initial Determination of Compliance

9. The holder of this permit shall perform stack sampling and other testing as required to establish the actual pattern and quantities of air contaminants being emitted into the atmosphere from EPN U1. Sampling must be conducted in accordance with appropriate procedures of the TCEQ Sampling Procedures Manual and in accordance with the appropriate EPA Reference Methods to be determined during the pretest meeting.

If fuel sampling is used to determine compliance with New Source Performance Standards (NSPS) Subpart KKKK, SO₂ limits shall be based on 100 percent conversion of the sulfur in the fuel to SO₂. Any deviations from those procedures must be approved by the Executive Director of the TCEQ prior to sampling. The TCEQ Executive Director or his designated representative shall be afforded the opportunity to observe all such sampling.

The holder of this permit is responsible for providing sampling and testing facilities and conducting the sampling and testing operation at his expense.

- A. The TCEQ Midland Regional Office shall be contacted as soon as testing is scheduled but not less than 30 days prior to sampling to schedule a pretest meeting.

The notice shall include:

- (1) Date for pretest meeting.
- (2) Date sampling will occur.
- (3) Name of firm conducting sampling.
- (4) Type of sampling equipment to be used.
- (5) Method or procedure to be used in sampling.
- (6) Procedure used to determine turbine loads during and after the sampling period.

The purpose of the pretest meeting is to review the necessary sampling and testing procedures, to provide the proper data forms for recording pertinent data, and to review the format procedures for submitting the test reports. A written proposed description of any deviation from sampling procedures specified in permit conditions or the TCEQ or the EPA sampling procedures shall be made available to the TCEQ prior to the pretest meeting. The TCEQ Midland Regional Director shall approve or disapprove of any deviation from specified sampling procedures. Requests to waive testing for any pollutant specified in this condition shall be submitted to the TCEQ Office of Air, Air Permits Division. Test waivers and alternate or equivalent procedure proposals for NSPS testing which must have EPA approval shall be submitted to the EPA and copied to the TCEQ Regional Director.

- B. Air contaminants and diluents emitted from the turbine to be sampled and analyzed include (but are not limited to) NO_x, O₂, and CO.
- C. The turbine shall be tested at or above 75% of maximum load operations. Each tested turbine load shall be identified in the sampling report. The permit holder shall present at the pretest meeting the manner in which stack sampling will be executed in order to demonstrate compliance with emission standards found in 40 CFR Part 60, Subpart KKKK.

- D. Sampling as required by this condition shall occur within 60 days after achieving the maximum production rate at which each turbine will be operated, but no later than 180 days after initial start-up of each unit. Additional sampling may be required by TCEQ or EPA.
- E. Within 60 days after the completion of the testing and sampling required herein, two copies of the sampling reports shall be distributed as follows:

One copy to the TCEQ Regional Office in Midland.
One copy to the EPA Region 6 Office, Dallas.

Note: Initial determination of compliance stack testing was performed on May 9, 2012 and submitted to TCEQ and the EPA on July 12, 2012 to demonstrate compliance with permit limits and 40 CFR Part 60, Subpart KKKK requirements.

Monitoring / Continuous Determination of Compliance

- 10. The permit holder shall monitor and record the hours of operation of the turbine.

Recordkeeping Requirements and Reporting

- 11. The following records shall be kept at the plant for the life of the permit. All records required in this permit shall be made available at the request of personnel from the TCEQ, EPA, or any air pollution control agency with jurisdiction.
 - A. A copy of this permit.
 - B. Permit renewal application dated December 27, 2012, and subsequent representations submitted to the TCEQ.
 - C. A complete copy of the testing reports and records of the initial performance testing completed to demonstrate initial compliance with permit limits and 40 CFR Part 60, Subpart KKKK requirements.
 - D. Stack sampling results or other air emissions testing that may be conducted on units authorized under this permit after the date of issuance of this permit.
- 12. The following information shall be maintained by the holder of this permit in a form suitable for inspection for a period of five years after collection and shall be made immediately available upon request to representatives of the TCEQ, EPA, or any local air pollution control program having jurisdiction:
 - A. The NO_x, CO, and O₂ diluent gas emissions data to demonstrate compliance with the emissions rates listed in the maximum allowable emission rates table (MAERT) and Special Condition 5.

- B. Records of fuel sampling, if conducted, pursuant to 40 CFR Part 60, Subpart KKKK.
- C. Records of the amount of natural gas fired monthly in the turbine.
- D. Records of visible emissions and opacity observations.

Date November 20, 2013

Emission Sources - Maximum Allowable Emission Rates

Permit Numbers 17800 and PSDTX718

This table lists the maximum allowable emission rates and all sources of air contaminants on the applicant's property covered by this permit. The emission rates shown are those derived from information submitted as part of the application for permit and are the maximum rates allowed for these facilities, sources, and related activities. Any proposed increase in emission rates may require an application for a modification of the facilities covered by this permit.

Air Contaminants Data

Emission Point No. (1)	Source Name (2)	Air Contaminant Name (3)	Emission Rates	
			lb/hour	TPY (4)
U1	Compressor 16P (Solar 50-5900L Turbine, 5000 hp)	NO _x	29.74	130.26
		CO	6.04	26.46
		VOC	0.35	1.52
		SO ₂	0.03	0.14
		PM ₁₀	0.33	1.43
		PM _{2.5}	0.33	1.43
		HAP (HCHO)	0.04	0.15
FUG-U	Fugitives Emissions (5)	VOC	0.10	0.46
		H ₂ S	0.14	0.62

- (1) Emission point identification - either specific equipment designation or emission point number from plot plan.
- (2) Specific point source name. For fugitive sources, use area name or fugitive source name.
- (3) VOC - volatile organic compounds as defined in Title 30 Texas Administrative Code § 101.1
 NO_x - total oxides of nitrogen
 SO₂ - sulfur dioxide
 PM₁₀ - total particulate matter, suspended in the atmosphere, equal to or less than 10 microns in diameter, including PM_{2.5}, as represented
 PM_{2.5} - particulate matter equal to or less than 2.5 microns in diameter
 CO - carbon monoxide
 HAP - hazardous air pollutant as listed in § 112(b) of the Federal Clean Air Act or Title 40 Code of Federal Regulations Part 63, Subpart C
 H₂S - hydrogen sulfide
 HCHO - formaldehyde
- (4) Compliance with annual emission limits (tons per year) is based on a 12 month rolling period.
- (5) Emission rate is an estimate and is enforceable through compliance with the applicable special condition(s) and permit application representations.

Date: November 20, 2013