Trophic Classification of Texas Reservoirs

2018 Texas Integrated Report for Clean Water Act Sections 305(b) and 303(d)

The primary productivity of reservoirs, as indicated by the amount of nutrients (phosphorus and nitrogen) and the extent of algae (suspended, floating, and attached) and rooted aquatic plants, can have a significant effect on water quality. Up to a point, nutrients promote ecosystem production and healthy growth of algae, larger plants, and fish and other aquatic organisms. However, excess nutrients and algae in reservoirs can have a deleterious effect on water quality, and algae can reach nuisance levels that potentially (1) create nuisance aesthetic conditions, (2) cause taste and odor in drinking water sources, (3) contribute to reduced dissolved oxygen as algae decay, and (4) and ultimately reduce the ability of a water body to support healthy, diverse aquatic communities.

Eutrophication refers to an overall condition characterized by an accumulation of nutrients that support relatively elevated growth of algae and other organisms. Eutrophication is primarily influenced by the physical and hydrological characteristics of the water body and can be affected by natural processes and human activities in the surrounding watershed. Human activities can accelerate the eutrophication process by increasing the rate at which nutrients and organic substances enter impoundments and surrounding watersheds. Discharges of treated sewage, agricultural and urban runoff, leaking septic tanks, and erosion of stream banks can increase the flow of nutrients and organic substances into reservoirs. In comparison to natural lakes in northern states, the eutrophication process in southern reservoirs is often enhanced by (1) warm climates with long growing seasons, (2) soils and geologic substrates that create high concentrations of sediment and nutrients in rainfall runoff, and (3) relatively high river inflows on main stem impoundments. As a result, some reservoirs in Texas can be relatively eutrophic even where nutrient loadings due to human activities are not relatively large.

The trophic state of a reservoir refers to its nutritional status that is indicated by measurements of nutrients and algae. Section 314 of the U.S. Clean Water Act (CWA) requires all states to classify lakes and reservoirs according to trophic state. Assessing water body condition based on algae is accomplished by evaluating indicators that reflect nutrient dynamics that drive primary production. Various classification schemes (Table 1-1) or indices have been developed that group reservoirs into discrete quality (trophic) states along a continuum from oligotrophic (poorly nourished) to hypereutrophic (over nourished). The basis for the trophic state index concept is that in many reservoirs the degree of eutrophication may be related to increased nutrient concentrations. Typically, phosphorus is the nutrient of concern and changes in its concentration may trigger a response that influences the amount of algae, as estimated by chlorophyll a (Chl a) in the reservoir. For example, increases in phosphorus can result in higher algal biomass, which in turn decreases water transparency (as measured by a Secchi disk or submarine photometer).

Table 1 - 1. Types of Trophic States in Reservoirs and Lakes

Trophic State	Water Quality Characteristics
Oligotrophic	Clear waters with extreme clarity, low nutrient concentrations, little organic matter or sediment, and minimal biological activity.
Mesotrophic	Waters with moderate nutrient concentrations and, therefore, more biological productivity. Waters may be lightly clouded by organic matter, sediment, suspended solids or algae.
Eutrophic	Waters relatively rich in nutrient concentrations, with high biological productivity. Waters more clouded by organic matter, sediment, suspended solids, and algae.
Hypereutrophic	Murkier, highly productive waters. Dense algae, very high nutrient concentrations.

(Adapted from a variety of descriptions of trophic state characteristics)

Major Texas reservoirs have been evaluated and ranked every two years by the TCEQ using Carlson's Trophic State Index (TSI). Carlson's Index was developed to compare reservoirs using in-reservoir sampling data (Carlson, 1977; Carlson and Simpson, 1996). Secchi disk depths, chlorophyll *a* concentrations, and total phosphorus concentrations are three variables that are highly correlated and considered estimators of algal biomass. The Carlson Index uses regression analysis to relate these three parameters to determine trophic state. The TSI is determined from any of the three computational equations:

TSI (Secchi Disk)	=	$60 - 14.41 \ln(SD)$, where SD is mean Secchi disk depth in meters.
TSI (Chlorophyll a)	=	9.81 ln(Chl <i>a</i>) + 30.6, where Chl <i>a</i> is mean chlorophyll <i>a</i> in μ g/L.
TSI (Total Phosphorus)	=	14.42 ln(TP) + 4.15, where TP is mean total phosphorus in μ g/L.

Although chlorophyll *a* is the most direct measure of algal biomass, the TSI uses Secchi disk depth as the primary indicator. The index was scaled, so that TSI = 0 represents the largest measured Secchi disk depth (64 m) among reservoirs. Each halving of transparency represents an increase of 10 TSI units (Table 1-2). Since the relationships between Secchi disk and chlorophyll *a* was nonlinear a 10-unit TSI (Chl *a*) change does not correspond to a doubling of chlorophyll *a*. Instead, chlorophyll *a* approximately doubles for each 7-unit increase in TSI (Chl *a*).

Table 1 - 2. Carlson's Trophic State Index and Associated Parameters

Trophic State Index	Secchi Disc (m)	Total Phosphorus (µg/L)	Chlorophyll a (µg/L)
0	64	0.75	0.04
10	32	1.5	0.12
20	16	3	0.34
30	8	6	0.94
40	4	12	2.6
50	2	24	6.4
60	1	48	20.0
70	0.5	96	56
80	0.25	192	154
90	0.12	384	427
100	0.062	768	1,183

(Adapted from Carlson, 1977; and Carlson and Simpson, 1996)

Carlson's Index provides a useful tool for assessing a reservoir's condition and evaluating changes over time. For example, the index would provide a quantitative estimate of the degree of improvement for a reservoir in which the TSI (Chl *a*) decreased from 60 to 40 units following implementation of restoration measures. The index provides useful information which explains possible causes of the water body condition. For example, if TSI (TP) > TSI (Chl *a*), phosphorus is probably not the limiting nutrient; TSI (SD) > TSI (Chl *a*) indicates the presence of non-algal turbidity.

Carlson's Index provides a simple model for evaluating condition which provides both advantages and disadvantages. The trophic state is developed on a continuous numeric scale and is useful for approximating the oligotrophic-hypereutrophic nomenclature required by the EPA. Secchi disk depths, total phosphorus, and chlorophyll *a* concentrations are routinely determined at fixed monitoring stations on reservoirs and lakes, so data are readily available for computation of Carlson's Index. The index does not perform well for certain water quality conditions: (1) where transparency is affected by suspended erosional materials rather than phytoplankton, (2) where primary production is controlled by attached algae or aquatic macrophytes rather than phytoplankton, and (3) when phosphorus is not the nutrient limiting phytoplankton growth.

Although the index can be used to classify and rank Texas reservoirs by trophic state, priority ranking for restoration is difficult. Carlson's Index does not replace the need to use attainment determinations. Carlson (1977) points out that trophic state is not equivalent to an index of water quality. Assessment of reservoir water quality depends to a large degree on the assignment of beneficial uses and determinations to evaluate if the uses are being maintained and/or impaired. Texas reservoirs are ranked in Appendix A according to Carlson's TSI for chlorophyll *a* as an average calculated from 10 years of SWQM data (December 1, 2006 - November 30, 2016). In order to maximize comparability among reservoirs, data from the monitoring station nearest the dam, with the most available data, in the main pool of each reservoir were utilized if available. In some cases, multiple stations situated within close proximity of one another were

also used. For many reservoirs, these are the only sites monitored by the TCEQ and Clean Rivers Program. Chlorophyll *a* was given priority as the primary trophic state indicator because it has proven to be most useful for estimating algal biomass in most reservoirs. A minimum of four chlorophyll *a* measurements, two total phosphorus, and two Secchi disk measurements were required for a reservoir to be included in the ranking. Of the 140 reservoirs surveyed, 132 had sufficient data to be included in the ranking. Based on this assessment, the 132 reservoirs show a range of eutrophication, from oligotrophic to hypereutrophic (Table 1 - 3). Rankings are also provided for total phosphorus (TP) and Secchi disk transparency (SD). Comparing TSI indicators between the reservoirs provides indications of the clearest reservoirs (low TSI SD) and identifies reservoirs with low and high total phosphorus concentrations.

Trophic Class	TSI (Chl a) Index Range	Number of Texas Reservoirs
Oligotrophic	0-40	6
Mesotrophic	>40 - 50	22
Eutrophic	>50 - 70	97
Hypereutrophic	>70	7

Table 1 - 3. Number of Texas Reservoirs Assessed in Each Trophic Class

Adapted from Carlson and Simpson (1996)

Reservoirs with the clearest water (highest mean Secchi disk transparency), listed in descending order: International Amistad Reservoir (4.46 m), Canyon Lake (3.80 m), Brandy Branch Reservoir (3.38 m), Lake Alan Henry (3.24 m), and Lake Travis (3.06 m). Reservoirs with the highest turbidity (poorest light transparency, lowest mean Secchi disk transparency), listed in ascending order: Rita Blanca Lake (0.06 m), Cox Lake (0.14 m), Palo Duro Reservoir (0.20 m), Lake Crook (0.24 m), and Lake Kickapoo (0.26 m).

Thirty-two reservoirs share the lowest mean total phosphorus concentration of 0.02 mg/L. Reservoirs with the highest mean total phosphorus concentrations, listed in descending order: Rita Blanca Lake (3.80 mg/L), O. C. Fisher Lake (1.26 mg/L), Lake Tanglewood (1.02 mg/L), Lake Woodlands (0.88 mg/L), and Scarborough Creek Reservoir (0.54 mg/L).

Water Quality Differences in Reservoirs

Carlson's TSI Chl *a* values for 95 reservoirs from the 2008 and 2018 reporting cycles were compared to indicate temporal differences (Appendix A). Differences could not be calculated for 37 reservoirs (28 %), due to the lack of comparable reporting information from 2008. The 2008 period of record was December 1, 1996 - November 30, 2006; for 2018, the period of record was December 1, 2006 - November 30, 2016.

TSI Chl *a* values, which estimate the amount of algal biomass, can indicate water quality improvement when values decrease. There were decreases in TSI Chl *a* values in 14 % of the comparable reservoirs between 2008 and 2018. Reservoirs with largest decrease in mean TSI Chl *a* values, listed in descending order: Lake Alan Henry (-16.08), Canyon Lake (-10.28), Oak Creek Reservoir (-6.56), Medina Lake (-5.98), and Lake Conroe (-5.36). Increases in algal

biomass (increase in TSI Chl *a* values) are indicated in 114 (86 %) of the comparable reservoirs, which may be indicative of natural or cultural eutrophication. Reservoirs with the largest differences for increasing algal content (substantial positive TSI Chl *a* values), listed in descending order: O. C. Fisher Reservoir (+22.50), Wright Patman Lake (+18.14), Lake Meredith (+16.92), Lake Bob Sandlin (+12.66), and White River Lake (+12.18).

It should be noted that a reservoir's trophic rank may differ from that in the last assessment due to improvements in data reporting and analytical capabilities or a change in monitoring station(s) rather than changes in water quality. Many individual values in the SWQMIS water quality database are reported as less than analytical reporting limits (non-detects or censored data). There is no generalized way to determine the true value for an individual result in the range between zero and the reporting limit. For the trophic classification assessment of Texas reservoirs, 50 percent of an analytical reporting limit is computed for censored results. This is done to maximize the amount of data used in this analysis and to indicate the level of monitoring effort. For more information please contact the Surface Water Quality Monitoring Team at swqm@tceq.texas.gov.

Reservoir Control Programs

Texas implements several reservoir pollution control procedures to ensure high-quality water for recreational, aquatic life, domestic, and industrial uses. Surface water quality standards have been adopted for significant reservoirs throughout the state in Title 30, Texas Administrative Code (TAC), Chapter 307 the Texas Surface Water Quality Standards (TSWQS). The TSWQS establish uses for classified segments and unclassified waterbodies, and include numerical criteria to protect those uses. Designated uses are determined by taking into account the reservoir's physical and biological characteristics, natural water quality, and existing uses. Criteria, depending on parameter, are based on background levels or accepted levels for protection of human health and aquatic life. The TCEQ issues permits that include limits designed to protect these uses. Each major reservoir is routinely monitored to assess the overall condition of the water body in comparison to the criteria and determine short- or long-term water quality trends. Reservoirs with non-supported uses are placed on the State of Texas 303(d) List. When a water body is identified as impaired and in need of remedial efforts, in some cases a Total Maximum Daily Load (TMDL) is conducted to determine the assimilative capacity of the segment and to determine discharge treatment levels and nonpoint source loads necessary to meet the criteria. Compliance with wastewater permits is monitored through on-site inspections by TCEQ personnel and through self-reporting procedures. When noncompliance with permits is found, enforcement actions may be required to attain compliance. The uses, criteria, TMDLs, and permits are periodically reviewed and, if necessary, revised.

The TCEQ has several specific rules that prescribe permit limitations for discharges of domestic wastewater into reservoirs. The rules in 30 TAC, Chapter 309 Domestic Wastewater Effluent Limitation and Plant Siting, require discharges located within five river miles upstream of certain reservoirs to achieve a minimum effluent quality for 5-day biological oxygen demand (BOD₅) of 10 mg/L, and total suspended solids (TSS) of 15 mg/L; both expressed as a 30-day average. This rule applies to reservoirs that are subject to on-site/private sewage facility regulation or that may be used as a source for a public drinking water supply. Currently, 95 reservoirs are designated for the public water supply use in Section (§) 307.10, Appendices A and B of the TSWQS. Additional rules under 30 TAC, Chapter 311 Watershed Protection, have been promulgated that

protect specific reservoirs:

Subchapter D: §§311.31-.36.

This rule requires all domestic and industrial permittees in the entire Lake Houston (Segment 1002) watershed to meet effluent limitations equal to or commensurate with 10 mg/L of BOD₅, 15 mg/L of TSS, and 3 mg/L of ammonia-nitrogen (NH3-N); all expressed as a 30-day average. All wastewater effluents disposed of on land shall meet an effluent quality of 20 mg/L of BOD₅ and 20 mg/L of TSS. Domestic facilities must submit a solids management plan. Additionally, all domestic and industrial facilities with gaseous chlorination disinfection systems must have dual feed chlorination systems and must meet a minimum chlorine residual of 1 mg/L and a maximum chlorine residual of 4.0 mg/L.

Subchapter A, B and F: §§311.1-.6, 311.11-.16 and 311.51-.56.

These rules apply to a series of reservoirs on the Colorado River, which are commonly referred to as the Highland Lakes, including Lake Austin (Segment 1403), Lake Travis (Segment 1404), Lake Marble Falls (Segment 1405), Lake LBJ, (Segment 1406), Inks Lake (Segment 1407), and Lake Buchanan (Segment 1408). Water quality areas, those portions of the watersheds within 10 river miles of the reservoirs, were established for each reservoir. New wastewater facilities constructed in these areas will be issued no-discharge permits, meaning that treated wastewater will not be discharged to surface waters. Any existing facility that requires a permit amendment for expansion or is not meeting permit requirements because of sewage overloading will be issued a no-discharge permit. Proposed new or expanded treatment facilities in the watersheds of these reservoirs will be issued no-discharge permits unless the applicant can establish that any alternative proposed wastewater disposal will protect and maintain the existing quality of the reservoirs. Allowable storm water runoff and certain non-storm water discharges that may be authorized by a Texas Pollution Discharge Elimination System (TPDES) or National Pollution Discharge Elimination System (NPDES) permit are also included in these watershed rules.

Subchapter G: §§311.61.-311.67.

This rule applies to Lakes Worth (Segment 0807), Eagle Mountain (Segment 0809), Bridgeport (Segment 0811), Cedar Creek (Segment 0818), Arlington (Segment 0828), Benbrook (Segment 0830), and Richland-Chambers (Segment 0836). With the exception of oxidation pond systems, domestic discharges within the water quality areas of the watersheds of these reservoirs are required to meet advanced treatment limits for BOD₅ of 10 mg/L, and filtration is required to supplement suspended solids removal by January 1, 1993. Section 311.67 specifies effluent limitations to control nutrients from new domestic wastewater facilities discharging to the Benbrook Lake watershed and Benbrook Lake water quality area. Based on location within the watershed and size of discharge, permittees must meet a daily effluent limit for TP of 1.0 mg/L, based on a 30-day average.

Reservoir and Lake Restoration Efforts

Section 314 of the Clean Water Act makes federal grant funds available to states under the Clean Lakes Program. The TCEQ is currently not administering any grant funding under this program. There are several lakes and reservoirs throughout the State where restoration efforts are currently under way to improve water quality. In addition to TMDLs, WPPs and Watershed Characterizations may be developed to protect high-quality waters, to address threatened waters before they become impaired, or to restore water bodies for which TMDLs are not practical. The lakes and reservoirs with ongoing restoration efforts include the following:

Lake O' the Pines – TMDL Implementation Plan E.V. Spence Reservoir – TMDL Implementation Plan Lake Austin – TMDL Implementation Plan Lake Worth – TMDL Implementation Plan Lake Houston – TMDL Implementation Plan Aquilla Reservoir – TMDL Implementation Plan Mountain Creek Lake – TMDL Implementation Plan Lake Como – TMDL Implementation Plan Eake Como – TMDL Implementation Plan Fosdic Lake – TMDL Implementation Plan Echo Lake – TMDL Implementation Plan Lake Arlington/Village Creek – Watershed Protection Plan Lake Granbury – Watershed Protection Plan Lake Lavon – Watershed Protection Plan Joe Pool Lake – Watershed Protection Plan

High and Low pH in Texas Water Bodies

The trophic status of a water body can impact a number of water quality parameters, including pH. Photosynthesis, respiration, and decomposition all contribute to pH fluctuations due to their influences on available carbon dioxide levels in the water column. Elevations in pH are typically highest in mid-afternoon, and lowest just before sunrise. Section 314 of the CWA requires states to include methods and procedures to evaluate and mitigate pH as part of the trophic classification.

Instantaneous and diel pH data collected as part of routine water quality monitoring and special studies are evaluated to determine attainment with site-specific water quality standards for high and low pH as part of the Integrated Report. If impaired, TCEQ considers this information when developing restoration strategies such as TMDLs and Watershed Protection Plans (WPPs), to determine if the pH impairment is related to excessive enrichment.

Low pH in Texas Water Bodies

Data from one reservoir, freshwater stream, and tidal stream (Table 1-4) have indicated low pH (high acidity) in at least one assessment location resulting in the water bodies being included in the Index of Water Quality Impairments. During respiration, dissolved carbon dioxide reacts with water to form carbonic acid, which may lower pH. Most of these water bodies are located in the eastern portion of the state, where natural geologic buffering capacity is limited.

Segment Number	Water Body Name
0510	Lake Cherokee
0511	Cow Bayou Tidal
1407A	Clear Creek

Table 1 - 4. Texas Water Bodies with Low pH

High pH in Texas Water Bodies

Data from twelve reservoirs and two freshwater streams (Table 1-5) have indicated elevated pH (high basicity) in at least one assessment location. A likely cause of elevated pH is consumption of dissolved carbon dioxide by photosynthetic processes. Excessive amounts of photosynthetically active algae and macrophytes can increase consumption of carbon dioxide during the day, increasing pH in the water column. Many of these water bodies are located in the eastern portion of the state, where natural geologic buffering capacity is limited.

Since five new waterbodies were impaired for high pH during the 2018 IR, changes in environmental conditions due to drought have contributed to the increased number of impairments. TCEQ will continue to evaluate the impact of drought on water quality results.

Segment Number	Water Body Name	Trophic Class
0105	Rita Blanca Lake	Hypereutrophic
0302	Wright Patman Lake	Eutrophic
0306	Upper South Sulphur River	Unknown
0307	Jim L. Chapman Lake (formerly Cooper Lake)	Eutrophic
0403	Lake O' the Pines	Eutrophic
0405	Lake Cypress Springs	Eutrophic
0512	Lake Fork Reservoir	Eutrophic
0514	Big Sandy Creek	Unknown
0605	Lake Palestine	Eutrophic
0818	Cedar Creek Reservoir	Eutrophic
0826	Grapevine Lake	Eutrophic
1002	Lake Houston	Eutrophic
1212	Somerville Lake	Eutrophic
1232	Clear Fork Brazos River	Unknown
1252	Lake Limestone	Eutrophic
2203	Petronila Creek Tidal	Unknown

 Table 1 - 5. Texas Water Bodies with High pH

Segment	Station ID	Reservoir	Chl <i>a</i> Rank ª	Chl <i>a</i> Records	Chl <i>a</i> Mean (µg/L)	Chl a TSI	Chl <i>a</i> TSI (2008)	10 Year Change ^c	Secchi Rank	Secchi Records	Secchi Mean (m)	Secchi TSI	TP Rank	TP Records	TP Mean (mg/L) ♭	TP TSI
1805	12597	CANYON LAKE	1	36	1.94	37.06	47.34	-10.28	2	35	3.8	40.74	3	33	0.02	44.7
1904	12825 12826	MEDINA LAKE		15	1.94	37.06	43.04	-5.98	7	23	3.02	44.04	21	18	0.02	50.1
1241B	18414	LAKE ALAN HENRY	3	19	1.94	37.1	53.18	-16.08	4	19	3.24	43.08	110	19	0.08	68.2
2305	13835	INTERNATIONAL AMISTAD RESERVOIR	4	33	1.98	37.34			1	34	4.46	38.48	6	33	0.02	46.2
1909	18407	MEDINA DIVERSION LAKE	5	20	2	37.38			18	20	1.76	51.82	15	20	0.02	48.9
0302G	20813	TP LAKE	6	18	2.36	39			25	26	1.54	53.7	87	19	0.06	62
0611R	17824	LAKE STRIKER	7	34	3.46	42.78	44.6	-1.82	56	38	1.02	59.62	76	34	0.04	59.9
1404	12302	LAKE TRAVIS	8	60	3.54	42.98	42.58	0.4	5	60	3.06	43.86	9	60	0.02	46.7
1216	11894	STILLHOUSE HOLLOW LAKE	9	76	3.66	43.34	44.16	-0.82	8	75	2.56	46.5	51	74	0.04	55.3
0614	10639	LAKE JACKSONVILLE	10	34	3.82	43.74	45.48	-1.74	9	37	2.44	47.2	7	28	0.02	46.3
1234	12005	LAKE CISCO	11	10	3.84	43.8			93	11	0.68	65.56	2	10	0.02	44.1
1604	15377	LAKE TEXANA	12	40	3.88	43.88			130	111	0.3	76.92	124	40	0.18	79.2
1230	11977	LAKE PALO PINTO	13	5	4.56	45.5	49	-3.5	90	5	0.7	65.26	94	5	0.06	63.7
0505E	13703	BRANDY BRANCH RESERVOIR	14	24	5.22	46.8			3	29	3.38	42.46	4	24	0.02	45.1
0610	14906	SAM RAYBURN RESERVOIR	15	40	5.36	47.08	47.66	-0.58	16	42	1.82	51.3	14	37	0.02	48.2
0202Q	16945	PICKENS LAKE	16	14	5.76	47.78			17	15	1.8	51.48	40	15	0.04	53.8
0611Q	15801	LAKE NACOGDOCHES	17	37	5.78	47.82	39	8.82	23	38	1.62	53.06	86	38	0.06	61.7
05061	14422	LAKE HAWKINS	18	34	5.82	47.86			10	35	2.36	47.58	13	30	0.02	47.7
1220	11921	BELTON LAKE	19	45	5.94	48.08	44.08	4	13	47	1.96	50.36	34	44	0.02	52.7
0504	10404	TOLEDO BEND RESERVOIR	20	108	6.02	48.2	46.74	1.46	14	109	1.94	50.4	36	96	0.04	53.2
1249	12111	LAKE GEORGETOWN	21	79	6.08	48.3	39.04	9.26	22	79	1.62	53.02	55	74	0.04	55.9
1233	12002	HUBBARD CREEK RESERVOIR	22	22	6.18	48.46	46.7	1.76	50	24	1.1	58.56	24	19	0.02	51
0840	14039 17834	RAY ROBERTS LAKE		41	6.18	48.46	45.88	2.58	52	24	1.08	58.76	23	38	0.02	50.3
1403	12294	LAKE AUSTIN	24	60	6.36	48.74	45.96	2.78	19	60	1.74	52	10	59	0.02	47.1

Appendix A. Carlson's Trophic State Index (TSI)

Segment	Station ID	Reservoir	Chl <i>a</i> Rank ^a	Chl <i>a</i> Records	Chl <i>a</i> Mean (µg/L)	Chl a TSI	Chl <i>a</i> TSI (2008)	10 Year Change ^c	Secchi Rank	Secchi Records	Secchi Mean (m)	Secchi TSI	TP Rank	TP Records	TP Mean (mg/L) [♭]	TP TSI
1426A	12180	OAK CREEK RESERVOIR	25	20	6.54	49	55.56	-6.56	40	18	1.26	56.72	27	16	0.02	51.6
1433	12511	O. H. IVIE RESERVOIR	26	23	6.86	49.48	46.62	2.86	12	28	2	50.04	28	27	0.02	51.7
0213	10143	LAKE KICKAPOO	27	20	6.88	49.54	43.86	5.68	132	21	0.26	79.86	103	21	0.08	66
0204B	15447	MOSS LAKE	28	17	7.1	49.82	47.1	2.72	45	17	1.2	57.26	38	18	0.04	53.6
0811	10970	BRIDGEPORT RESERVOIR	29	49	7.28	50.06	42.58	7.48	61	49	1	60.08	55	46	0.04	55.9
0228	10188	MACKENZIE RESERVOIR	30	23	7.32	50.12	51.56	-1.44	46	23	1.16	57.76	23	19	0.02	50.3
0203	15440 20545	LAKE TEXOMA	31	80	7.84	50.8			44	51	1.22	57.24	75	80	0.04	59.6
1419	12398	LAKE COLEMAN	32	21	8.04	51.04	43.44	7.6	79	23	0.8	63.24	50	21	0.04	55.1
0605F	17575	LAKE ATHENS	33	37	8.62	51.74	49.5	2.24	15	40	1.92	50.68	9	32	0.02	46.7
1418	12395	LAKE BROWNWOOD	34	16	8.92	52.06	45.34	6.72	59	20	1	59.92	53	18	0.04	55.6
0834	11063	LAKE AMON G. CARTER	35	17	9.16	52.32	45.18	7.14	24	18	1.56	53.5	40	15	0.04	53.8
0208	10137	LAKE CROOK	36	20	9.28	52.44			133	21	0.24	80.54	125	20	0.18	79.3
1231	11979	LAKE GRAHAM	37	24	9.38	52.56	45.92	6.64	83	24	0.78	63.76	64	21	0.04	57.5
0223	10173	GREENBELT LAKE	38	36	9.4	52.58	42.68	9.9	48	36	1.16	57.94	48	38	0.04	55
0408	17059	LAKE BOB SANDLIN	39	32	9.58	52.78	40.12	12.66	20	36	1.66	52.66	12	31	0.02	47.5
0603	10582	B A. STEINHAGEN LAKE	41	38	10.62	53.78	50.7	3.08	116	38	0.42	72.24	100	35	0.06	65
0217	10159	LAKE KEMP	42	27	10.94	54.08	47.88	6.2	39	28	1.26	56.58	32	29	0.02	52.3
1408	12344	LAKE BUCHANAN	43	60	11.2	54.3	50.98	3.32	28	60	1.46	54.5	21	60	0.02	50.1
0612G	21435	LAKE NACONICHE	44	11	11.6	54.64			27	11	1.5	54.24	5	11	0.02	46
1207	11865	POSSUM KINGDOM LAKE	45	115	11.72	54.74	50.34	4.4	11	115	2.04	49.78	42	108	0.04	54.2
1012	11342	LAKE CONROE	47	38	12.14	55.1	60.46	-5.36	69	106	0.9	61.36	97	76	0.06	64.2
0512	10458	LAKE FORK RESERVOIR	48	109	12.38	55.28	55.66	-0.38	30	114	1.44	54.68	45	97	0.04	54.7
0212	10142	LAKE ARROWHEAD	49	30	12.4	55.3	49.92	5.38	102	30	0.56	68.32	122	29	0.16	77.7
1422	12418	LAKE NASWORTHY	50	34	12.54	55.4	54.04	1.36	100	38	0.58	67.92	72	35	0.04	59.3
0613	10637	LAKE TYLER	51	36	12.7	55.54			37	39	1.3	56.3	17	32	0.02	49.6

Segment	Station ID	Reservoir	Chl <i>a</i> Rank ^a	Chl <i>a</i> Records	Chl <i>a</i> Mean (µg/L)	Chl a TSI	Chl <i>a</i> TSI (2008)	10 Year Change ^c	Secchi Rank	Secchi Records	Secchi Mean (m)	Secchi TSI	TP Rank	TP Records	TP Mean (mg/L) ^ь	TP TSI
0613	10638	LAKE TYLER EAST	52	35	12.84	55.64	50.52	5.12	36	39	1.3	56.2	19	32	0.02	49.9
0836	15168	RICHLAND-CHAMBERS RESERVOIR	53	41	12.96	55.72	51.24	4.48	62	38	0.98	60.32	69	40	0.04	58.5
1429	12476	LADY BIRD LAKE (FORMERLY TOWN LAKE)	54	37	13	55.76	48.62	7.14	33	35	1.4	55.22	25	26	0.02	51.2
0303A	16856	BIG CREEK LAKE	55	25	13.04	55.78			125	24	0.34	75.16	111	24	0.08	68.3
0506L	18847	LAKE HOLBROOK	56	22	13.24	55.94			31	25	1.44	54.7	18	23	0.02	49.7
1406	12324	LAKE LYNDON B JOHNSON	57	59	13.32	56	52.16	3.84	34	60	1.38	55.36	43	60	0.04	54.5
0604T	17339	LAKE RATCLIFF	58	27	13.46	56.1			82	24	0.78	63.6	62	26	0.04	57.2
1247	12095	GRANGER LAKE	59	82	13.8	56.36	46.48	9.88	116	81	0.42	72.24	73	77	0.04	59.5
0813	10973	HOUSTON COUNTY LAKE	60	38	14.76	57.02	53.56	3.46	30	39	1.44	54.68	30	32	0.02	52
2454A	12514	COX LAKE	61	34	14.9	57.1	55.22	1.88	135	32	0.14	87.64	129	30	0.26	84.8
2116	13020	CHOKE CANYON RESERVOIR	62	40	15.28	57.34			101	50	0.56	68.3	77	40	0.04	60.4
0307	13855	JIM L. CHAPMAN LAKE (FORMERLY COOPER LAKE)		22	15.28	57.34			96	23	0.64	66.4	108	21	0.08	67.3
0826	11035 16113 17827	GRAPEVINE LAKE	64	40	15.6	57.54			80	27	0.8	63.3	68	36	0.04	57.9
1225	11942	WACO LAKE		39	15.6	57.54	52.38	5.16	78	39	0.82	62.98	57	36	0.04	56.1
1254	12127	AQUILLA RESERVOIR	66	40	15.66	57.58	51.12	6.46	99	37	0.6	67.18	68	36	0.04	57.9
1224	11939	LEON RESERVOIR	67	16	16.04	57.82	50.14	7.68	49	20	1.14	58.02	59	14	0.04	56.4
0817	10981	NAVARRO MILLS LAKE	68	30	16.28	57.98	52.94	5.04	111	29	0.48	70.76	96	25	0.06	64.1
1203	11851	WHITNEY LAKE		34	16.28	57.98	57.46	0.52	35	45	1.32	56.08	27	34	0.02	51.6
1405	12319	MARBLE FALLS LAKE	70	59	16.36	58.02	50.26	7.76	32	59	1.42	54.9	31	59	0.02	52.1
0215	10157	DIVERSION LAKE	71	24	16.56	58.14	52.3	5.84	85	26	0.74	64.16	53	27	0.04	55.6
0401	10283	CADDO LAKE	72	38	16.98	58.38	52.96	5.42	87	139	0.74	64.36	116	32	0.12	73.6
0409D	17478	LAKE GILMER	73	35	17.12	58.46	56.56	1.9	38	36	1.3	56.32	48	27	0.04	55
0816	10980	LAKE WAXAHACHIE	74	30	17.3	58.56	54.16	4.4	103	39	0.56	68.48	58	34	0.04	56.3

Segment	Station ID	Reservoir	Chl <i>a</i> Rank ª	Chl <i>a</i> Records	Chl <i>a</i> Mean (µg/L)	Chl a TSI	Chl <i>a</i> TSI (2008)	10 Year Change ^c	Secchi Rank	Secchi Records	Secchi Mean (m)	Secchi TSI	TP Rank	TP Records	TP Mean (mg/L) ^b	TP TSI
1236	12010	FORT PHANTOM HILL RESERVOIR	75	13	17.56	58.7	56.86	1.84	113	13	0.46	71.36	109	9	0.08	67.4
1407	12336	INKS LAKE	76	59	17.6	58.74	56.5	2.24	42	59	1.24	56.96	29	59	0.02	51.9
2303	13189	INTERNATIONAL FALCON RESERVOIR	77	33	17.72	58.8	52	6.8	47	22	1.16	57.88	93	32	0.06	63.2
0209	16343	PAT MAYSE LAKE	78	38	18.06	58.98			54	38	1.06	59.14	45	34	0.04	54.7
2103	12967	LAKE CORPUS CHRISTI	79	40	18.54	59.24	64.5	-5.26	120	51	0.38	74.06	127	40	0.2	79.8
1411	13863	E. V. SPENCE RESERVOIR	80	16	18.56	59.26	60.94	-1.68	57	15	1.02	59.68	60	16	0.04	56.9
0210	10139	FARMERS CREEK RESERVOIR (ALSO KNOWN AS LAKE NOCONA)	81	28	18.8	59.38	47.48	11.9	70	28	0.88	61.84	70	28	0.04	58.6
0815	10979	BARDWELL RESERVOIR	82	31	18.86	59.4	58.04	1.36	114	37	0.42	72.22	78	33	0.04	60.5
0506H	17062	LAKE GLADEWATER	83	35	18.98	59.48	57.38	2.1	72	41	0.88	61.98	64	33	0.04	57.5
0102	10036	LAKE MEREDITH	84	38	19.18	59.58	42.66	16.92	71	39	0.88	61.9	61	32	0.04	57.1
1228	11974	LAKE PAT CLEBURNE		41	19.16	59.58			98	42	0.62	66.76	84	39	0.06	61.6
0809	10944	EAGLE MOUNTAIN RESERVOIR	86	40	19.3	59.64	61.94	-2.3	61	41	1	60.08	91	42	0.06	63
0830	15151	BENBROOK LAKE	87	46	19.42	59.7	58.24	1.46	75	46	0.86	62.18	82	45	0.06	61.1
1242H	18457	TRADINGHOUSE RESERVOIR	88	39	20.32	60.14	59.32	0.82	77	39	0.84	62.5	55	39	0.04	55.9
1423	12422	TWIN BUTTES RESERVOIR	89	27	20.68	60.32	53.88	6.44	94	29	0.68	65.62	80	26	0.06	60.9
0505F	13601	MARTIN CREEK RESERVOIR	90	29	20.92	60.42			55	33	1.06	59.2	45	27	0.04	54.7
1008F	16482	LAKE WOODLANDS	91	40	20.98	60.46	60.44	0.02	118	117	0.42	72.62	133	40	0.88	102
2312	13267	RED BLUFF RESERVOIR	92	15	21.32	60.62	58.7	1.92	76	20	0.84	62.38	41	13	0.04	54.1
0818	16748 16749	CEDAR CREEK RESERVOIR	93	86	21.56	60.72			73	72	0.86	62	89	87	0.06	62.6
0821	15685	LAKE LAVON	94	11	21.74	60.8			104	15	0.54	68.74	88	15	0.06	62.3
0405	10312	LAKE CYPRESS SPRINGS	95	34	22.14	60.98	52.56	8.42	51	36	1.1	58.72	35	33	0.02	52.9
1413	21614	LAKE J. B. THOMAS	96	16	22.88	61.3	51.04	10.26	108	16	0.5	69.72	102	16	0.06	65.2
1428K	20161	WALTER E. LONG LAKE	97	18	23.06	61.38			41	19	1.24	56.82	66	8	0.04	57.8
0403	10296	LAKE O' THE PINES	98	32	23.2	61.44	53.4	8.04	66	36	0.94	60.9	34	34	0.02	52.7
0820	10998	LAKE RAY HUBBARD	99	43	23.62	61.62	61.02	0.6	74	31	0.86	62.14	65	45	0.04	57.7

Segment	Station ID	Reservoir	Chl <i>a</i> Rank ª	Chl <i>a</i> Records	Chl <i>a</i> Mean (µg/L)	Chl a TSI	Chl <i>a</i> TSI (2008)	10 Year Change ^c	Secchi Rank	Secchi Records	Secchi Mean (m)	Secchi TSI	TP Rank	TP Records	TP Mean (mg/L) [♭]	TP TSI
0803	10899	LAKE LIVINGSTON	100	38	24.26	61.88	57.34	4.54	110	38	0.48	70.46	115	39	0.1	70.6
1205	11860	LAKE GRANBURY	101	120	25.52	62.38			68	122	0.92	61.12	75	115	0.04	59.6
0807	10942	LAKE WORTH	102	39	25.76	62.46	55.76	6.7	92	39	0.68	65.5	91	38	0.06	63
0828	13904	LAKE ARLINGTON	103	43	26.42	62.72			82	42	0.78	63.6	98	43	0.06	64.5
1232D	17941	LAKE DANIEL	104	10	26.76	62.84			129	12	0.32	76.76	117	10	0.12	73.8
0605	16159	LAKE PALESTINE	105	36	26.78	62.86	61.1	1.76	65	39	0.94	60.86	50	29	0.04	55.1
0199A	10005	PALO DURO RESEVOIR		20	26.8	62.86			134	20	0.2	83.04	131	18	0.34	88
1434C	17020	LAKE BASTROP	107	58	27.82	63.22	56.7	6.52	53	58	1.08	58.96	86	57	0.06	61.7
0832	11061	LAKE WEATHERFORD	108	33	28.08	63.32	55.22	8.1	106	34	0.52	69.58	71	32	0.04	58.9
1416B	12179	BRADY CREEK RESERVOIR	109	27	28.7	63.54	58.84	4.7	91	29	0.68	65.4	79	26	0.04	60.6
1002	11204	LAKE HOUSTON	110	40	28.86	63.58	55.58	8	122	35	0.36	74.46	127	44	0.18	79.8
1252	12123	LAKE LIMESTONE	111	55	29.58	63.82			84	58	0.76	64	95	53	0.06	63.8
1237	12021	LAKE SWEETWATER	112	9	31.2	64.36			131	9	0.3	77.34	105	8	0.08	66.5
1240	12027	WHITE RIVER LAKE	113	32	31.92	64.58	52.4	12.18	119	37	0.38	73.68	101	31	0.06	65.1
1402G	17017	CEDAR CREEK RESERVOIR/LAKE FAYETTE	114	59	33.22	64.96	62.48	2.48	63	59	0.96	60.46	106	59	0.08	66.6
1235	12006	LAKE STAMFORD	115	21	33.64	65.1	53.04	12.06	109	22	0.5	70.22	112	19	0.08	68.5
0507	10434	LAKE TAWAKONI	116	105	33.78	65.14	63.88	1.26	64	112	0.96	60.7	81	95	0.06	61
1210	17586	LAKE MEXIA	117	40	35.9	65.72			124	41	0.36	74.8	121	38	0.16	77.4
0302	14097 10213	WRIGHT PATMAN LAKE	118	55	35.94	65.74	47.6	18.14	95	123	0.66	65.96	114	42	0.1	69.6
0827	11038	WHITE ROCK LAKE	119	26	36.74	65.96			105	30	0.52	69.42	99	27	0.06	64.7
0515A	17948	LAKE QUITMAN	120	29	37.42	66.14			88	26	0.74	64.44	107	19	0.08	66.7
0509	10444	MURVAUL LAKE	121	36	37.92	66.26	66.34	-0.08	89	39	0.72	64.72	83	33	0.06	61.3
0803G	16953	LAKE MADISONVILLE	122	12	38.66	66.46			117	11	0.42	72.32	119	12	0.12	74.1
1241C	11529	BUFFALO SPRINGS LAKE	123	20	40.42	66.9	69.9	-3	67	19	0.94	60.96	92	19	0.06	63.1
1222	11935	PROCTOR LAKE	124	20	44.6	67.86	58.36	9.5	107	21	0.52	69.6	118	18	0.12	73.9
1212	11881	SOMERVILLE LAKE	125	34	45.44	68.04	67.26	0.78	97	37	0.64	66.54	104	30	0.08	66.4

Segment	Station ID	Reservoir	Chl <i>a</i> Rank ª	Chl <i>a</i> Records	Chl <i>a</i> Mean (µg/L)	Chl a TSI	Chl <i>a</i> TSI (2008)	10 Year Change ^c	Secchi Rank	Secchi Records	Secchi Mean (m)	Secchi TSI	TP Rank	TP Records	TP Mean (mg/L) ⁵	TP TSI
0202M	21032	LAKE BONHAM (BONHAM CITY LAKE)	126	53	50.28	69.04			121	47	0.36	74.36	113	54	0.08	69
0804J	17951	FAIRFIELD LAKE	127	39	53.06	69.56			86	41	0.74	64.32	120	36	0.16	76.7
1242A	16781	NEW MARLIN CITY LAKE	128	40	56.78	70.22	67.46	2.76	126	39	0.34	75.74	123	36	0.18	78.5
1253A	16247	SPRINGFIELD LAKE	129	39	64.5	71.48	63.84	7.64	127	38	0.32	76.24	128	37	0.2	80.6
0229A	10192	LAKE TANGLEWOOD	130	35	67.38	71.9	63.02	8.88	58	40	1.02	59.76	134	30	1.02	104
1255K	17224	SCARBOROUGH CREEK RESERVOIR	131	16	87.56	74.48			128	16	0.32	76.58	132	16	0.54	94.8
0219	10163	LAKE WICHITA	132	26	98.7	75.64	76.42	-0.78	123	23	0.36	74.58	130	31	0.3	86.5
1425	12429	O. C. FISHER LAKE	133	21	271.86	85.58	63.08	22.5	112	22	0.46	71.12	135	21	1.26	107.1
0105	10060	RITA BLANCA LAKE	134	22	978	98.14	88.04	10.1	136	24	0.06	100.94	136	19	3.8	123

Chl *a* – chlorophyll *a*; TP – total phosphorus

The Carlson's TSI (Chl a), (TP), and (Secchi) were computed for each reservoir by calculating the arithmetic average for the TSI values from each sample date. The effect of these computations is that the ranking of Carlson's TSI (Chl a), (TP), and (Secchi) values may vary slightly from a ranking based on the arithmetic average of chlorophyll a, total phosphorus, and Secchi disk values.

^a Reservoirs are ranked in priority by TSI (Chl *a*). A true rank was used which can result in a tied rank for reservoirs with the same TSI (Chl *a*). Therefore, some ranking assignments are skipped by the computational data model. The rank resumes with subsequent rank value.

 $^{\rm b}$ Total phosphorus concentrations converted from $\mu g/L$ to mg/L.

^c A positive value indicates increased algal content; A negative value indicates increased algal content; missing values indicate a comparison cannot be made due to absence of comparable data.

Citations:

Carlson, R.E. (1977) A trophic state index for lakes. Limnology and Oceanography. 22:2 361-369

Carlson, R.E. and J. Simpson. 1996. A Coordinator's Guide to Volunteer Lake Monitoring Methods. North American Lake Management Society. 96 pp.

This page intentionally left blank