40 CFR Part 60, Subpart Da - Requirements Reference Tables

Subpart Da Standards

- §60.42Da(a) PM requirements for facilities constructed, reconstructed, or modified before or on March 1, 2005.
- §60.42Da(b) PM(Opacity) requirements for facilities not using a CEMS for PM monitoring.
- §60.42Da(c)(1) Gross energy output-based PM requirements for facilities constructed, reconstructed, or modified after February 28, 2005, but before May 4, 2011.
- §60.42Da(c)(2) Heat input-based PM requirements for facilities constructed, reconstructed, or modified after February 28, 2005, but before May 4, 2011.
- §60.42Da(d)(1) Alternate PM requirements for facilities constructed, reconstructed, or modified after February 28, 2005, but before May 4, 2011.
- §60.42Da(e)(1)(i)(A) Gross energy output-based PM requirements for facilities constructed or reconstructed after May 3, 2011.
- §60.42Da(e)(1)(i)(B) Net energy output-based PM requirements for facilities constructed or reconstructed after May 3, 2011.
- §60.43Da(a)(1) SO₂ requirements for facilities constructed, reconstructed, or modified before or on February 28, 2005 that combust solid fuel or solid-derived fuel.
- §60.43Da(a)(2) SO₂ requirements for facilities constructed, reconstructed, or modified before or on February 28, 2005 that combust solid fuel or solid-derived fuel when emissions are less than 260 ng/J (0.60 lb/MMBtu) heat input.
- §60.43Da(a)(3) Gross energy output-based SO₂ requirements for facilities constructed, reconstructed or modified before or on February 28, 2005 that combust solid fuel or solidderived fuel.
- §60.43Da(a)(4) Heat input-based SO₂ requirements for facilities constructed, reconstructed, or modified before or on February 28, 2005 that combust solid fuel or solid-derived fuel.
- §60.43Da(b)(1) SO₂ requirements for facilities constructed, reconstructed, or modified before or on February 28, 2005 that combust liquid or gaseous fuels.
- §60.43Da(b)(2) SO₂ requirements for facilities constructed, reconstructed, or modified before or on February 28, 2005 that combust liquid or gaseous fuels when emissions are less than 86 ng/J (0.20 lb/MMBtu) heat input.
- §60.43Da(c) SO₂ requirements for facilities constructed, reconstructed, or modified before or on February 28, 2005 that combust solid solvent refined coal (SRC–I).
- §60.43Da(d) SO₂ requirements for facilities constructed, reconstructed, or modified before or on February 28, 2005 that combust 100% anthracite or that is classified as a resource recovery unit.
- §60.43Da(h)(1) SO₂ requirements for facilities constructed, reconstructed, or modified before or on February 28, 2005 that combust different fuels simultaneously and emissions greater than 260 ng/J (0.60 lb/MMBtu) heat input.
- §60.43Da(h)(2) SO₂ requirements for facilities constructed, reconstructed, or modified before or on February 28, 2005 that combust different fuels simultaneously and emissions equal to or less than 260 ng/J (0.60 lb/MMBtu) heat input.
- §60.43Da(i)(1)(i) Gross energy output-based SO₂ requirements for facilities constructed after February 28, 2005, but before May 4, 2011.
- §60.43Da(i)(1)(ii) SO₂ percent reduction requirements for facilities constructed after February 28, 2005, but before May 4, 2011.
- §60.43Da(i)(2)(i) Gross energy output-based SO₂ requirements for facilities reconstructed after February 28, 2005, but before May 4, 2011.

- §60.43Da(i)(2)(ii) Heat input-based SO₂ requirements for facilities reconstructed after February 28, 2005, but before May 4, 2011.
- §60.43Da(i)(2)(iii) SO₂ percent reduction requirements for facilities reconstructed after February 28, 2005, but before May 4, 2011.
- §60.43Da(i)(3)(i) Gross energy output-based SO₂ requirements for facilities modified after February 28, 2005, but before May 4, 2011.
- §60.43Da(i)(3)(ii) Heat input-based SO₂ requirements for facilities modified after February 28, 2005, but before May 4, 2011.
- §60.43Da(i)(3)(iii) SO₂ percent reduction requirements for facilities modified after February 28, 2005, but before May 4, 2011.
- §60.43Da(j)(1)(i) Gross energy output-based SO₂ requirements for facilities constructed after February 28, 2005 that burn 75 percent or more (by heat input) coal refuse on a 12-month rolling average basis.
- §60.43Da(j)(1)(ii) SO₂ percent reduction requirements for facilities constructed after February 28, 2005 that burn 75 percent or more (by heat input) coal refuse on a 12-month rolling average basis.
- §60.43Da(j)(2)(i) Gross energy output-based SO₂ requirements for facilities reconstructed after February 28, 2005 that burn 75 percent or more (by heat input) coal refuse on a 12-month rolling average basis.
- §60.43Da(j)(2)(ii) Heat input-based SO₂ requirements for facilities reconstructed after February 28, 2005 that burn 75 percent or more (by heat input) coal refuse on a 12-month rolling average basis.
- §60.43Da(j)(2)(iii) SO₂ percent reduction requirements for facilities reconstructed after February 28, 2005 that burn 75 percent or more (by heat input) coal refuse on a 12-month rolling average basis.
- §60.43Da(j)(3)(i) Gross energy output-based SO₂ requirements for facilities modified after February 28, 2005 that burn 75 percent or more (by heat input) coal refuse on a 12-month rolling average basis.
- §60.43Da(j)(3)(ii) Heat input-based SO₂ requirements for facilities modified after February 28, 2005 that burn 75 percent or more (by heat input) coal refuse on a 12-month rolling average basis.
- §60.43Da(j)(3)(iii) SO₂ percent reduction requirements for facilities modified after February 28, 2005 that burn 75 percent or more (by heat input) coal refuse on a 12-month rolling average basis.
- §60.43Da(I)(1)(i) Gross energy output-based SO₂ requirements for facilities constructed or reconstructed after May 3, 2011.
- §60.43Da(I)(1)(ii) Net energy output-based SO₂ requirements for facilities constructed or reconstructed after May 3, 2011.

- §60.43Da(I)(1)(iii) SO₂ percent reduction requirements for facilities modified after May 3, 2011.
- §60.43Da(I)(2)(i) Gross energy output-based SO₂ requirements for facilities modified after May 3, 2011.
- §60.43Da(I)(2)(ii) SO2 percent reduction requirements for facilities modified after May 3, 2011.
- §60.44Da(a)(1) NOx requirements for facilities based on a 30-boiler operating day rolling average basis for facilities constructed, reconstructed, or modified before July 10, 1997.
- §60.44Da(a)(2) NOx requirements for facilities combusting two or more fuels simultaneously based on a 30-boiler operating day rolling average basis for facilities constructed, reconstructed, or modified before July 10, 1997.
- §60.44Da(d)(1) Gross energy output-based NOx requirements for facilities constructed after July 9, 1997, but before March 1, 2005.
- §60.44Da(d)(2) Heat input-based NOx requirements for facilities reconstructed after July 9, 1997, but before March 1, 2005.
- §60.44Da(e)(1) Gross energy output-based NOx requirements for facilities constructed after February 28, 2005, but before May 4, 2011.
- §60.44Da(e)(2)(i) Gross energy output-based NOx requirements for facilities reconstructed after February 28, 2005, but before May 4, 2011.
- §60.44Da(e)(2)(ii) Heat input-based NOx requirements for facilities reconstructed after February 28, 2005, but before May 4, 2011.
- §60.44Da(e)(3)(i) Gross energy output-based NOx requirements for facilities modified after February 28, 2005, but before May 4, 2011.
- §60.44Da(e)(3)(ii) Heat input-based NOx requirements for facilities modified after February 28, 2005, but before May 4, 2011.
- §60.44Da(f)(1) Gross energy output-based NOx requirements for IGCC facilities constructed, reconstructed or modified after February 28, 2005 but before May 4, 2011 when liquid fuel is less than 50% of the total heat input.
- §60.44Da(f)(2) Gross energy output-based NOx requirements for IGCC facilities constructed, reconstructed or modified after February 28, 2005, but before May 4, 2011, that burn liquid fuel exclusively or in combination with solid-derived fuel such that liquid fuel contributes 50% or more of the total heat input.
- §60.44Da(f)(3) NOx requirements for IGCC facilities constructed, reconstructed or modified after February 28, 2005, but before May 4, 2011, that, during a 30-day rolling average compliance period burn liquid fuel in combination with solid-derived fuel such the liquid fuel contributes 50% or more of the total heat input for only a portion of the clock hours in the 30-day period.
- §60.44Da(g)(1)(i) Gross energy output-based NOx requirements for facilities constructed or reconstructed after May 3, 2011.
- §60.44Da(g)(1)(ii) Net energy output-based NOx requirements for facilities constructed or reconstructed after May 3, 2011.
- §60.44Da(g)(2)(i) Gross energy output-based NOx requirements for facilities constructed or reconstructed after May 3, 2011, that burn 75 percent or more (by heat input) coal refuse on a 12-month rolling average basis.
- §60.44Da(g)(2)(ii) Net energy output-based NOx requirements for facilities constructed or reconstructed after May 3, 2011, that burn 75 percent or more (by heat input) coal refuse on a 12-month rolling average basis.
- §60.44Da(g)(3) Gross energy output-based NOx requirements for facilities modified after May 3, 2011, that burn 75 percent or more (by heat input) coal refuse on a 12-month rolling average basis.
- §60.45Da(b)(1)(i) Gross energy output-based NOx plus CO requirements for facilities constructed or reconstructed after May 3, 2011.

- §60.45Da(b)(1)(ii) Net energy output-based NOx plus CO requirements for facilities constructed or reconstructed after May 3, 2011.
- §60.45Da(b)(2)(i) Gross energy output-based NOx plus CO requirements for facilities constructed or reconstructed after May 3, 2011, that burn 75 percent or more (by heat input) coal refuse on a 12-month rolling average basis.
- §60.45Da(b)(2)(ii) Net energy output-based NOx requirements for facilities constructed or reconstructed after May 3, 2011, that burn 75 percent or more (by heat input) coal refuse on a 12-month rolling average basis.
- §60.45Da(b)(3) Gross energy output-based NOx plus CO requirements for facilities modified after May 3, 2011, that burn 75 percent or more (by heat input) coal refuse on a 12-month rolling average basis.

These relationship entry screens and flowcharts are for use by sources subject to the Texas Federal Operating Permits Program only and are subject to revision.

Last Modified: March 14, 2023