

40 CFR Part 60, Subpart UU - Requirements Reference Tables

Subpart UU Standards

- [§60.472\(a\)\(1\)\(i\)](#) Saturator particulate matter limit of 0.04 kg particulate per Mg asphalt shingle
- [§60.472\(a\)\(1\)\(ii\)](#) Saturator particulate matter limit of 0.4 kg particulate per Mg saturated felt
- [§60.472\(a\)\(2\)](#) Saturator opacity limit of 20 percent
- [§60.472\(b\)\(1\)](#) Blowing still particulate matter limit of 0.67 kg particulate per Mg asphalt
- [§60.472\(b\)\(2\)](#) Blowing still particulate matter limit of 0.71 kg particulate per Mg asphalt
- [§60.472\(b\)\(3\)](#) Blowing still particulate matter limit of 0.60 kg particulate per Mg asphalt
- [§60.472\(b\)\(4\)](#) Blowing still particulate matter limit of 0.64 kg particulate per Mg asphalt
- [§60.472\(b\)\(5\)](#) Blowing still exhaust gases opacity limit of 0 percent
- [§60.472\(c\)](#) Asphalt storage tank opacity limit of 0 percent
- [§60.472\(d\)](#) Mineral handling and storage facility opacity limit of 1 percent
- [§60.474\(g\)](#) Blowing still alternative means to establish an opacity limit

These relationship entry screens and flowcharts are for use by sources subject to the Texas Federal Operating Permits Program only and are subject to revision.

Last Modified: August 13,1997