

## 40 CFR Part 63, Subpart G Section 113 - Requirements Reference Tables

### Subpart G Section 113 Standards

- [§63.110\(d\)\(2\)\(i\)](#) Group 2 process vent with a TRE value < 1 as determined by the procedures in 40 CFR part 60 subpart III, is required to comply with the provisions in paragraphs(d)(2)(i)(A)-(d)(2)(i)(C) of this section.
- [§63.110\(d\)\(2\)\(ii\)](#) Group 2 process vent with a TRE value ≥ 1 as determined by the procedures in 40 CFR part 60 subpart III, is required to comply only with the provisions specified in paragraphs (d)(2)(ii)(A)-(d)(2)(ii)(D) of this section.
- [§63.110\(d\)\(5\)\(i\)](#) Group 2 process vent with a TRE value < 1 as determined by the procedures in 40 CFR part 60 subpart NNN, is required to comply with the provisions in paragraphs(d)(5)(i)(A)-(d)(5)(i)(C) of this section.
- [§63.110\(d\)\(5\)\(ii\)](#) Group 2 process vent with a TRE value ≥ 1 as determined by the procedures in 40 CFR part 60 subpart NNN, is required to comply only with the provisions specified in paragraphs (d)(5)(ii)(A)-(d)(5)(ii)(D) of this section.
- [§63.110\(d\)\(8\)\(i\)](#) Group 2 process vent with a TRE value < 1 as determined by the procedures in 40 CFR part 60 subpart RRR, is required to comply with the provisions in paragraphs(d)(8)(i)(A)-(d)(8)(i)(C) of this section.
- [§63.110\(d\)\(8\)\(ii\)](#) Group 2 process vent with a TRE value ≥ 1 as determined by the procedures in 40 CFR part 60 subpart RRR, is required to comply only with the provisions specified in paragraphs (d)(8)(ii)(A)-(d)(8)(ii)(D) of this section.
- [§63.110\(f\)\(2\)\(i\)](#) Process vent already controlled by a combustion device meeting the requirements of 40 CFR part 61 subpart F shall comply with either the provisions for Group 1 process vents in this subpart or the provisions of 40 CFR part 61 subpart F.
- [§63.113\(a\)\(1\)](#) Reduce emissions of organic HAP using a flare
- [§63.113\(a\)\(2\)](#) Reduce emissions of total organic HAPs by 98 wt.% or to a concentration of 20 ppm by volume
- [§63.113\(d\)](#) Group 2 process with specified criteria shall maintain a TRE index value >1
- [§63.113\(e\)](#) Group 2 process vent with a TRE index > 4.0 shall maintain a TRE index value > 4.0
- [§63.113\(f\)](#) Group 2 process vent with a flow rate < than 0.005 standard m<sup>3</sup>/min shall maintain it
- [§63.113\(g\)](#) Group 2 process vent with a concentration less than 50 ppm by volume shall maintain it

These relationship entry screens and flowcharts are for use by sources subject to the Texas Federal Operating Permits Program only and are subject to revision.

Last Modified: September 26, 2007