40 CFR Part 63, Subpart H - Requirements Reference Tables

Subpart H Standards

- §63.162(e) Exclusion for equipment in organic HAP service less than 300 hours per calendar year.
- <u>§63.163</u> Standards: Pumps in light liquid service.
- §63.164 Standards: Compressors.
- §63.165 Standards: Pressure relief devices in gas/vapor service.
- §63.166 Standards: Sampling connection systems.
- §63.167 Standards: Open-ended valves or lines.
- §63.168 Standards: Valves in gas/vapor service and in light liquid service.
- §63.169 1 Standards: Pumps in heavy liquid service.
- §63.169|2 Standards: Valves in heavy liquid service.
- §63.169 | 3 Standards: Connections in heavy liquid service.
- §63.169 4 Standards: Agitators in heavy liquid service.
- §63.169 | 5 Standards: Instrumentation systems in liquid service.
- §63.169 6 Standards: Pressure relief devices in liquid service.
- §63.170 Standards: Surge control vessels and bottom receivers.
- §63.172(a) Standard for Closed-vent systems and control devices.
- §63.172(b) Standard for Recovery or recapture devices
- §63.172(c) Standard for Enclosed combustion devices.
- §63.172(d) Standard for Flares.
- §63.173 Standards: Agitators in gas/vapor service and in light liquid service.
- §63.174 Standards: Connectors in gas/vapor service and in light liquid service.
- §63.177 Alternative means of emission limitation: General.
- §63.178 Alternative means of emission limitation: Batch processes.
- §63.179 Alternative means of emission limitation: Enclosed-vented process units.

These relationship entry screens and flowcharts are for use by sources subject to the Texas Federal Operating Permits Program only and are subject to revision.

Last modified: February 11, 2004