

## 30 TAC 115/170, Oil and Natural Gas Service in Ozone Nonattainment Areas - Requirements Reference Tables

### 30 TAC 115/170 Standards

- [§115.172\(a\)\(3\)](#) Exemption for storage tanks.
- [§115.172\(a\)\(7\)](#) Exemption for sampling connection systems.
- [§115.172\(a\)\(8\)](#) Exemption for fugitive components at a well site.
- [§115.173\(3\)\(A\)1](#) Requirements for centrifugal compressors controlling VOC emissions by 95%.
- [§115.173\(3\)\(A\)2](#) Requirements for reciprocating compressors controlling VOC emissions by 95%.
- [§115.173\(3\)\(A\)3](#) Requirements for centrifugal compressors maintaining VOC concentration of equal to or less than 275 ppmv.
- [§115.173\(3\)\(A\)4](#) Requirements for reciprocating compressors maintaining VOC concentration of equal to or less than 275 ppmv.
- [§115.173\(3\)\(B\)1](#) Requirements for centrifugal compressors using a flare to control VOC emissions.
- [§115.173\(3\)\(B\)2](#) Requirements for reciprocating compressors using a flare to control VOC emissions.
- [§115.173\(3\)\(C\)1](#) Requirements for centrifugal compressors controlling VOC emissions by routing to a process.
- [§115.173\(3\)\(C\)2](#) Requirements for reciprocating compressors controlling VOC emissions by routing to a process.
- [§115.174\(a\)\(1\)](#) Requirements for pneumatic pump drives at natural gas processing plants.
- [§115.174\(a\)\(2\)](#) Requirements for pneumatic controllers at natural gas processing plants.
- [§115.174\(b\)\(1\)](#) Requirements for pneumatic pumps not located at natural gas processing plant.
- [§115.174\(b\)\(2\)](#) Requirements for pneumatic controllers not located at natural gas processing plant.
- [§115.175\(a\)](#) Requirements for storage vessels.
- [§115.175\(b\)](#) Exemption for storage vessels complying with [§115.112\(e\)](#).
- [§115.176\(a\)](#) Alternate requirements for natural gas processing plants.
- [§115.177\(b\)\(1\)\(A\)1](#) Requirements for VOC leakage from pumps seals in light liquid service at a natural gas processing plant that are used for polymerizing monomer
- [§115.177\(b\)\(1\)\(A\)2](#) Requirements for VOC leakage from pumps seals in light liquid service at a natural gas processing plant that are not used for polymerizing monomer
- [§115.177\(b\)\(1\)\(B\)1](#) Requirements for VOC leakage from valves at a natural gas processing plant.
- [§115.177\(b\)\(1\)\(B\)2](#) Requirements for VOC leakage from flanges at a natural gas processing plant.
- [§115.177\(b\)\(1\)\(B\)3](#) Requirements for VOC leakage from connectors at a natural gas processing plant.
- [§115.177\(b\)\(1\)\(B\)4](#) Requirements for VOC leakage from pressure relief devices at a natural gas processing plant.
- [§115.177\(b\)\(1\)\(B\)5](#) Requirements for VOC leakage from pumps in heavy liquid service at a natural gas processing plant.
- [§115.177\(b\)\(1\)\(B\)6](#) Requirements for VOC leakage from sampling connections at a

- natural gas processing plant.
- [§115.177\(b\)\(1\)\(B\)7](#) Requirements for VOC leakage from process drains at a natural gas processing plant.
- [§115.177\(b\)\(1\)\(C\)](#) Requirements for VOC leakage from compressors at a natural gas processing plant.
- [§115.177\(b\)\(2\)1](#) Requirements for fugitive components at a well site.
- [§115.177\(b\)\(2\)2](#) Requirements for fugitive components a gathering/boosting station.
- [§115.177\(b\)\(11\)1](#) Alternate requirements for fugitive components at a natural gas processing plant.
- [§115.177\(b\)\(11\)2](#) Alternate requirements for fugitive components at a well site or gathering/boosting station.

These relationship entry screens and flowcharts are for use by sources subject to the Texas Federal Operating Permits Program only and are subject to revision.

Last Modified: May 2, 2023