

30 TAC 115/352, Fugitive Emission Control in Petroleum Refining, Natural Gas/Gasoline Processing, and Petrochemical Processes in Ozone Nonattainment Areas - Requirements Reference Tables

30 TAC 115/352 Standards

- [§115.352\(1\)\(A\)|33](#) Requirements for VOC leakage from process drains in heavy liquid service.
- [§115.352\(1\)\(A\)|34](#) Requirements for VOC leakage from pressure relief valves in heavy liquid service).
- [§115.352\(1\)\(A\)|35](#) Requirements for VOC leakage from open-ended valves or lines in heavy liquid service.
- [§115.352\(1\)\(A\)|36](#) Requirements for VOC leakage from valves in heavy liquid service.
- [§115.352\(1\)\(A\)|37](#) Requirements for VOC leakage from flanges or other connectors in heavy liquid service.
- [§115.352\(1\)\(A\)|38](#) Requirements for VOC leakage from agitators in heavy liquid service.
- [§115.352\(1\)\(A\)|39](#) Requirements for VOC leakage from process drains in gas/vapor or light liquid service.
- [§115.352\(1\)\(A\)|40](#) Requirements for VOC leakage from pressure relief valves in gas/vapor or light liquid service.
- [§115.352\(1\)\(A\)|41](#) Requirements for VOC leakage from open-ended valves or lines in gas/vapor or light liquid service.
- [§115.352\(1\)\(A\)|42](#) Requirements for VOC leakage from valves in gas/vapor or light liquid service.
- [§115.352\(1\)\(A\)|43](#) Requirements for VOC leakage from flanges or other connectors in gas/vapor or light liquid service.
- [§115.352\(1\)\(A\)|44](#) Requirements for VOC leakage from agitators in gas/vapor or light liquid service.
- [§115.352\(1\)\(B\)|7](#) Requirements for VOC leakage from compressor seals in heavy liquid service.
- [§115.352\(1\)\(B\)|8](#) Requirements for VOC leakage from pump seals in heavy liquid service.
- [§115.352\(1\)\(B\)|9](#) Requirements for VOC leakage from compressor seals in gas/vapor or light liquid service.
- [§115.352\(1\)\(B\)|10](#) Requirements for VOC leakage from compressors in hydrogen service.
- [§115.352\(1\)\(B\)|11](#) Requirements for VOC leakage from compressors that are equipped with a shaft sealing system.
- [§115.352\(1\)\(B\)|12](#) Requirements for VOC leakage from pump seals in gas/vapor or light liquid service.
- [§115.352\(1\)\(B\)|13](#) Requirements for VOC leakage from pumps that are equipped with a shaft sealing system.
- [§115.352\(1\)\(C\)](#) Requirements for components that utilize the alternative work practices in §115.358.
- [§115.353\(a\)](#) Alternative requirements for VOC leakage from process drains at natural gas processing plants.
- [§115.357\(2\)](#) Exemption for pressure relief valves equipped with a rupture disk.
- [§115.357\(5\)](#) Exemption for reciprocating compressors and positive displacement pumps.
- [§115.357\(6\)|1](#) Exemption for various components at a petroleum refinery or synthetic

organic chemical, polymer, resin or methyl-ter-butyl ether manufacturing process that contact a process fluid that contains less than 10.0% VOC by weight.

- [§115.357\(6\)2](#) Exemption for various components at a natural gas/gasoline processing operation that contact a process fluid that contains less than 1.0% VOC by weight.
- [§115.357\(7\)](#) Exemption for various plant sites covered by a single account number with less than 250 components in VOC service.
- §115.357(10) Exemption for instrumentation systems.
- [§115.357\(11\)](#) Exemption for sampling connection systems.
- [§115.357\(13\)](#) Exemption for components/systems that contact a process fluid containing VOC having a true vapor pressure equal or less than 0.002 psia at 68 degrees Fahrenheit.

These relationship entry screens and flowcharts are for use by sources subject to the Texas Federal Operating Permits Program only and are subject to revision.

Last Modified: June 22, 2021