

June 27, 2023

Franklin Anciano - License & Permit Specialist Edwards Aquifer Protection Program Texas Commission on Environmental Quality

Re: Shops at Hero Way CZP-MOD - Administrative NOD

Dear Franklin Anciano,

The following comments in red are in response to your comments.

#### Edwards Aquifer Applica0on Cover Page (TCEQ-20705)

1. Line 9. Please provide information. Line 9 (Application Fee) information added.

#### Core Data Form (TCEQ-10400)

- 2. Line 23-24. Information provided could not be validated by the U.S. Postal Service. Please provide information on Line 25. Description to physical location provided on Line 25
- 3. Line 39. Please select Edwards Aquifer. Edward's Aquifer selected.

#### **Plan Sheets**

- 4. If the application contains any of the following sheets, please remove them because they are not applicable to our review:
  - Tree List
  - All Wastewater and Water Utility plan sheets (private & public)
  - Fire protection plan
  - Water & Wastewater detail sheets
  - All landscaping sheets.
  - Architect Sheets
  - Street Plan/Signage/Profile drawings.
  - Electrical distribution plan sheets and details.

Any of the above listed sheets have been removed from the submitted Sheet Set.

Sincerely,

Anthony Goode, PE

1



# **SHOPS AT HERO WAY**

1561 HERO WAY
LEANDER, TX 78641
WILLIAMSON COUNTY

# T.C.E.Q. EDWARDS AQUIFER PROTECTION PLAN CZP MODIFICATION

PREPARED FOR

TRANSIT VILLAGE INVESTMENTS LTD

MAY 2023

#### **Texas Commission on Environmental Quality**

# **Edwards Aquifer Application Cover Page**

#### **Our Review of Your Application**

The Edwards Aquifer Program staff conducts an administrative and technical review of all applications. The turnaround time for administrative review can be up to 30 days as outlined in 30 TAC 213.4(e). Generally administrative completeness is determined during the intake meeting or within a few days of receipt. The turnaround time for technical review of an administratively complete Edwards Aquifer application is 90 days as outlined in 30 TAC 213.4(e). Please know that the review and approval time is directly impacted by the quality and completeness of the initial application that is received. In order to conduct a timely review, it is imperative that the information provided in an Edwards Aquifer application include final plans, be accurate, complete, and in compliance with 30 TAC 213.

#### **Administrative Review**

- 1. <u>Edwards Aquifer applications</u> must be deemed administratively complete before a technical review can begin. To be considered administratively complete, the application must contain completed forms and attachments, provide the requested information, and meet all the site plan requirements. The submitted application and plan sheets should be final plans. Please submit one full-size set of plan sheets with the original application, and half-size sets with the additional copies.
  - To ensure that all applicable documents are included in the application, the program has developed tools to guide you and web pages to provide all forms, checklists, and guidance. Please visit the below website for assistance: <a href="http://www.tceq.texas.gov/field/eapp">http://www.tceq.texas.gov/field/eapp</a>.
- 2. This Edwards Aquifer Application Cover Page form (certified by the applicant or agent) must be included in the application and brought to the administrative review meeting.
- 3. Administrative reviews are scheduled with program staff who will conduct the review. Applicants or their authorized agent should call the appropriate regional office, according to the county in which the project is located, to schedule a review. The average meeting time is one hour.
- 4. In the meeting, the application is examined for administrative completeness. Deficiencies will be noted by staff and emailed or faxed to the applicant and authorized agent at the end of the meeting, or shortly after. Administrative deficiencies will cause the application to be deemed incomplete and returned.
  - An appointment should be made to resubmit the application. The application is re-examined to ensure all deficiencies are resolved. The application will only be deemed administratively complete when all administrative deficiencies are addressed.
- 5. If an application is received by mail, courier service, or otherwise submitted without a review meeting, the administrative review will be conducted within 30 days. The applicant and agent will be contacted with the results of the administrative review. If the application is found to be administratively incomplete, it can be retrieved from the regional office or returned by regular mail. If returned by mail, the regional office may require arrangements for return shipping.
- 6. If the geologic assessment was completed before October 1, 2004 and the site contains "possibly sensitive" features, the assessment must be updated in accordance with the *Instructions to Geologists* (TCEQ-0585 Instructions).

#### **Technical Review**

- When an application is deemed administratively complete, the technical review period begins. The regional
  office will distribute copies of the application to the identified affected city, county, and groundwater
  conservation district whose jurisdiction includes the subject site. These entities and the public have 30 days
  to provide comments on the application to the regional office. All comments received are reviewed by TCEQ.
- 2. A site assessment is usually conducted as part of the technical review, to evaluate the geologic assessment and observe existing site conditions. The site must be accessible to our staff. The site boundaries should be

- clearly marked, features identified in the geologic assessment should be flagged, roadways marked and the alignment of the Sewage Collection System and manholes should be staked at the time the application is submitted. If the site is not marked the application may be returned.
- 3. We evaluate the application for technical completeness and contact the applicant and agent via Notice of Deficiency (NOD) to request additional information and identify technical deficiencies. There are two deficiency response periods available to the applicant. There are 14 days to resolve deficiencies noted in the first NOD. If a second NOD is issued, there is an additional 14 days to resolve deficiencies. If the response to the second notice is not received, is incomplete or inadequate, or provides new information that is incomplete or inadequate, the application must be withdrawn or will be denied. Please note that because the technical review is underway, whether the application is withdrawn or denied **the application fee will be forfeited**.
- 4. The program has 90 calendar days to complete the technical review of the application. If the application is technically adequate, such that it complies with the Edwards Aquifer rules, and is protective of the Edwards Aquifer during and after construction, an approval letter will be issued. Construction or other regulated activity may not begin until an approval is issued.

#### **Mid-Review Modifications**

It is important to have final site plans prior to beginning the permitting process with TCEQ to avoid delays.

Occasionally, circumstances arise where you may have significant design and/or site plan changes after your Edwards Aquifer application has been deemed administratively complete by TCEQ. This is considered a "Mid-Review Modification". Mid-Review Modifications may require redistribution of an application that includes the proposed modifications for public comment.

If you are proposing a Mid-Review Modification, two options are available:

- If the technical review has begun your application can be denied/withdrawn, your fees will be forfeited, and the plan will have to be resubmitted.
- TCEQ can continue the technical review of the application as it was submitted, and a modification application can be submitted at a later time.

If the application is denied/withdrawn, the resubmitted application will be subject to the administrative and technical review processes and will be treated as a new application. The application will be redistributed to the affected jurisdictions.

Please contact the regional office if you have questions. If your project is located in Williamson, Travis, or Hays County, contact TCEQ's Austin Regional Office at 512-339-2929. If your project is in Comal, Bexar, Medina, Uvalde, or Kinney County, contact TCEQ's San Antonio Regional Office at 210-490-3096

Please fill out all required fields below and submit with your application.

1. Regulated Entity Name: Shops at Hero Way				2. Regulated Entity No.:					
3. Customer Name: Transit Village Investments LTI					s LTD	<b>4. Customer No.:</b> CN604379081			
5. Project Type: (Please circle/check one)  New  Modification					ı	Extension		Exception	
6. Plan Type: (Please circle/check one)	WPAP	CZP	SCS	UST	AST	EXP	EXT	Technical Clarification	Optional Enhanced Measures
7. Land Use: (Please circle/check one)	Resider	ntial	Non-r	esiden	tial		8. Site (acres): 2.23 acres (site) 11.78 (total project)		
9. Application Fee:	\$650	00	10. P	ermai	nent I	existing Sedimentation/Filtration Basin			
11. SCS (Linear Ft.):	NA		12. A	ST/US	ST (No	(No. Tanks): NA			
13. County:	Willian	nson	14. W	4. Watershed: Brushy Creek					

# **Application Distribution**

Instructions: Use the table below to determine the number of applications required. One original and one copy of the application, plus additional copies (as needed) for each affected incorporated city, county, and groundwater conservation district are required. Linear projects or large projects, which cross into multiple jurisdictions, can require additional copies. Refer to the "Texas Groundwater Conservation Districts within the EAPP Boundaries" map found at:

http://www.tceq.texas.gov/assets/public/compliance/field\_ops/eapp/EAPP%20GWCD%20map.pdf

For more detailed boundaries, please contact the conservation district directly.

Austin Region							
County:	Hays	Travis	Williamson				
Original (1 req.)							
Region (1 req.)	_	_					
County(ies)			<u>X</u>				
Groundwater Conservation District(s)	Edwards Aquifer AuthorityBarton Springs/ Edwards AquiferHays Trinity Plum Creek	Barton Springs/ Edwards Aquifer	NA				
City(ies) Jurisdiction	Pluin Creek AustinBudaDripping SpringsKyleMountain CitySan MarcosWimberleyWoodcreek	AustinBee CavePflugervilleRollingwoodRound RockSunset ValleyWest Lake Hills	AustinCedar ParkFlorenceGeorgetownJerrell X_LeanderLiberty HillPflugervilleRound Rock				

	San Antonio Region							
County:	Bexar	Comal	Kinney	Medina	Uvalde			
Original (1 req.)								
Region (1 req.)								
County(ies)								
Groundwater Conservation District(s)	Edwards Aquifer Authority Trinity-Glen Rose	Edwards Aquifer Authority	Kinney	EAA Medina	EAA Uvalde			
City(ies) Jurisdiction	Castle HillsFair Oaks RanchHelotesHill Country VillageHollywood ParkSan Antonio (SAWS)Shavano Park	Bulverde Fair Oaks Ranch Garden Ridge New Braunfels Schertz	NA	San Antonio ETJ (SAWS)	NA			

I certify that to the best of my knowledge, that the appapplication is hereby submitted to TCEQ for administ	
Anthony Goode	
Print Name of Customer/Authorized Agent	
dalle	6/1/2023
Signature of Customer/Authorized Agent	Date

**FOR TCEQ INTERNAL USE ONLY**						
Date(s)Reviewed: Date Administratively Complete:						
Received From:	Correct	Number of Copies:				
Received By:	Distribu	ntion Date:				
EAPP File Number:	Complex	x:				
Admin. Review(s) (No.):	No. AR	Rounds:				
Delinquent Fees (Y/N):	Review '	Time Spent:				
Lat./Long. Verified:	SOS Cus	stomer Verification:				
Agent Authorization Complete/Notarized (Y/N):	Fee	Payable to TCEQ (Y/N):				
Core Data Form Complete (Y/N):	Check:	Signed (Y/N):				
Core Data Form Incomplete Nos.:		Less than 90 days old (Y/N):				

# Modification of a Previously Approved Contributing Zone Plan

**Texas Commission on Environmental Quality** 

for Regulated Activities on the Edwards Aquifer Recharge Zone and Transition Zone and Relating to 30 TAC 213.4(j), Effective June 1, 1999

To ensure that the application is administratively complete, confirm that all fields in the form are complete, verify that all requested information is provided, consistently reference the same site and contact person in all forms in the application, and ensure forms are signed by the appropriate party.

Note: Including all the information requested in the form and attachments contributes to more streamlined technical reviews.

### Signature

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. This **Modification of a Previously Approved Contributing Zone Plan** is hereby submitted for TCEQ review and executive director approval. The request was prepared by:

Print Name of Customer/Agent: Anthony Goode, PE

Date: 6/1/2023

Signature of Customer/Agent:

## **Project Information**

1.	Current Regulated Entity Name: Transit Village Investments LTD
	Original Regulated Entity Name: LEANDER STATION MULTI FAMILY (WP West Acquisitions LLC)
	Assigned Regulated Entity Number(s) (RN): 110460532 (Permit # 11002153)
	Edwards Aquifer Protection Program ID Number(s):
	The applicant has not changed and the Customer Number (CN) is:
	The applicant or Regulated Entity has changed. A new Core Data Form has been
	provided.

- 2. X Attachment A: Original Approval Letter and Approved Modification Letters. A copy of the original approval letter and copies of any modification approval letters are attached.
- 3. A modification of a previously approved plan is requested for (check all that apply):

Any physical or operational modification of any best management practices or
structure(s), including but not limited to temporary or permanent ponds, dams,
berms, silt fences, and diversionary structures;
Any change in the nature or character of the regulated activity from that which was
originally approved;
A change that would significantly impact the ability to prevent pollution of the
Edwards Aquifer and hydrologically connected surface water; or
X Any development of land previously identified in a contributing zone plan as
undeveloped.

4. X Summary of Proposed Modifications (select plan type being modified). If the approved plan has been modified more than once, copy the appropriate table below, as necessary, and complete the information for each additional modification.

CZP Modification	Approved Project	<b>Proposed Modification</b>
Summary		
Acres	11.78	<u>11.78</u>
Type of Development	<u>Reside</u> ntial	<u>Comm</u> ercial
Number of Residential		NA
Lots		
Impervious Cover (acres)	7.22	8.95
Impervious Cover (%)	61.29	76.91
Permanent BMPs	Sed-Fil Basin	Existing Sed-Fil Basin to be used
Other	NA	NA
AST Modification	Approved Project	<b>Proposed Modification</b>
Summary		
Number of ASTs	NA	NA
Other	NA	NA
UST Modification	Approved Project	<b>Proposed Modification</b>
Summary		
Number of USTs	NA_	NA
Other	NA_	NA

<sup>5.</sup> X Attachment B: Narrative of Proposed Modification. A detailed narrative description of the nature of the proposed modification is attached. It discusses what was approved,

including previous modifications, and how this proposed modification will change the approved plan.

6.	X Attachment C: Current Site Plan of the Approved Project. A current site plan showing
	the existing site development (i.e., current site layout) at the time this application for modification is attached. A site plan detailing the changes proposed in the submitted
	modification is required elsewhere.
	The approved construction has not commenced. The original approval letter and any subsequent modification approval letters are included as Attachment A to document that the approval has not expired.
	X The approved construction has commenced and has been completed. Attachment C illustrates that the site was constructed as approved.
	The approved construction has commenced and has been completed. Attachment C illustrates that the site was <b>not</b> constructed as approved.
	☐ The approved construction has commenced and has <b>not</b> been completed.
	Attachment C illustrates that, thus far, the site was constructed as approved.
	The approved construction has commenced and has <b>not</b> been completed.
	Attachment C illustrates that, thus far, the site was <b>not</b> constructed as approved.
7.	<ul> <li>Acreage has not been added to or removed from the approved plan.</li> <li>Acreage has been added to or removed from the approved plan and is discussed in Attachment B: Narrative of Proposed Modification.</li> </ul>
8.	Submit one (1) original and one (1) copy of the application, plus additional copies as needed for each affected incorporated city, groundwater conservation district, and county in which the project will be located. The TCEQ will distribute the additional copies to these jurisdictions. The copies must be submitted to the appropriate regional office.



# ATTACHMENT A – ORIGINAL APPROVAL LETTER

Jon Niermann, *Chairman*Emily Lindley, *Commissioner*Bobby Janecka, *Commissioner*Toby Baker, *Executive Director* 



### TEXAS COMMISSION ON ENVIRONMENTAL QUALITY

Protecting Texas by Reducing and Preventing Pollution

November 12, 2020

Mr. Bart Barrett WP West Acquisitions LLC 211 E 7<sup>th</sup> St, Ste 620 Austin, Texas 78701

Re: Edwards Aquifer, Williamson County

NAME OF PROJECT: Leander Station Multi Family; Located southeast of Hero Way and Mel Mathis Avenue; Leander, Texas

TYPE OF PLAN: Request for Approval of a Contributing Zone Plan (CZP); 30 Texas Administrative Code (TAC) Chapter 213 Subchapter B Edwards Aquifer

Regulated Entity No. RN110460532; Additional ID No. 11002153

Dear Mr. Barrett:

The Texas Commission on Environmental Quality (TCEQ) has completed its review of the CZP Application for the above-referenced project submitted to the Austin Regional Office by WGI on behalf of WP West Acquisitions LLC on August 12, 2020. Final review of the CZP was completed after additional material was received on November 4, 2020 and November 5, 2020. As presented to the TCEQ, the Temporary and Permanent Best Management Practices (BMPs) were selected and construction plans were prepared by a Texas Licensed Professional Engineer to be in general compliance with the requirements of 30 TAC Chapter 213. These planning materials were sealed, signed and dated by a Texas Licensed Professional Engineer. Therefore, based on the engineer's concurrence of compliance, the planning materials for construction of the proposed project and pollution abatement measures are hereby approved subject to applicable state rules and the conditions in this letter. The applicant or a person affected may file with the chief clerk a motion for reconsideration of the executive director's final action on this Edwards Aquifer Protection Plan. A motion for reconsideration must be filed no later than 23 days after the date of this approval letter. This approval expires two (2) years from the date of this letter unless, prior to the expiration date, more than 10 percent of the construction has commenced on the project or an extension of time has been requested.

#### PROJECT DESCRIPTION

The proposed commercial project will have an area of approximately 11.78 acres. It will include the construction of a multi-family apartment complex consisting of eight buildings with associated parking, drives, utilities, and drainage improvements. The impervious cover will be 7.22 acres (76.09 percent). Project wastewater will be disposed of by conveyance to the existing Leander Water Recycling Center owned by the City of Leander.

Mr. Bart Barrett Page 2 November 12, 2020

#### PERMANENT POLLUTION ABATEMENT MEASURES

To prevent the pollution of stormwater runoff originating on-site or upgradient of the site and potentially flowing across and off the site after construction, one sedimentation/filtration basin, designed using the TCEQ technical guidance document, Complying with the Edwards Aquifer Rules: Technical Guidance on Best Management Practices (2005), will be constructed to treat stormwater runoff. The required total suspended solids (TSS) treatment for this project is 6,284 pounds of TSS generated from the 7.22 acres of impervious cover. The approved measures meet the required 80 percent removal of the increased load in TSS caused by the project.

#### **SPECIAL CONDITIONS**

- I. All permanent pollution abatement measures shall be operational prior to first occupancy of the facilities.
- II. All sediment and/or media removed from the water quality basin during maintenance activities shall be properly disposed of according to 30 TAC 330 or 30 TAC 335, as applicable.

#### STANDARD CONDITIONS

- 1. Pursuant to Chapter 7 Subchapter C of the Texas Water Code, any violations of the requirements in 30 TAC Chapter 213 may result in administrative penalties.
- 2. The holder of the approved Edwards Aquifer protection plan must comply with all provisions of 30 TAC Chapter 213 and all best management practices and measures contained in the approved plan. Additional and separate approvals, permits, registrations and/or authorizations from other TCEQ Programs (i.e., Stormwater, Water Rights, UIC) can be required depending on the specifics of the plan.
- 3. In addition to the rules of the Commission, the applicant may also be required to comply with state and local ordinances and regulations providing for the protection of water quality.

#### Prior to Commencement of Construction:

- 4. All contractors conducting regulated activities at the referenced project location shall be provided a copy of this notice of approval. At least one complete copy of the approved Contributing Zone Plan and this notice of approval shall be maintained at the project location until all regulated activities are completed.
- 5. Any modification to the activities described in the referenced CZP application following the date of approval may require the submittal of a plan to modify this approval, including the payment of appropriate fees and all information necessary for its review and approval prior to initiating construction of the modifications.
- 6. The applicant must provide written notification of intent to commence construction, replacement, or rehabilitation of the referenced project. Notification must be submitted to the Austin Regional Office no later than 48 hours prior to commencement of the regulated activity. Written notification must include the name of the approved plan and file number for the regulated activity, the date on which the regulated activity will commence, and the name of the prime contractor with the name and telephone number of the contact person.
- 7. Temporary erosion and sedimentation (E&S) controls, i.e., silt fences, rock berms, stabilized construction entrances, or other controls described in the approved Storm Water Pollution Prevention Plan (SWPPP) must be installed prior to construction and maintained during construction. Temporary E&S controls may be removed when vegetation is established and the construction area is stabilized. If a water quality pond is proposed, it shall be used as a sedimentation basin during construction. The TCEQ may monitor stormwater discharges

Mr. Bart Barrett Page 3 November 12, 2020

from the site to evaluate the adequacy of temporary E&S control measures. Additional controls may be necessary if excessive solids are being discharged from the site.

#### **During Construction:**

- 8. During the course of regulated activities related to this project, the applicant or his agent shall comply with all applicable provisions of 30 TAC Chapter 213, Edwards Aquifer. The applicant shall remain responsible for the provisions and conditions of this approval until such responsibility is legally transferred to another person or entity.
- 9. If sediment escapes the construction site, the sediment must be removed at a frequency sufficient to minimize offsite impacts to water quality (e.g., fugitive sediment in street being washed into surface streams or sensitive features by the next rain). Sediment must be removed from sediment traps or sedimentation ponds not later than when design capacity has been significantly reduced. Litter, construction debris, and construction chemicals exposed to stormwater shall be prevented from becoming a pollutant source for stormwater discharges (e.g., screening outfalls, picked up daily).
- 10. Intentional discharges of sediment laden water are not allowed. If dewatering becomes necessary, the discharge will be filtered through appropriately selected best management practices. These may include vegetated filter strips, sediment traps, rock berms, silt fence rings, etc.
- 11. The following records shall be maintained and made available to the executive director upon request: the dates when major grading activities occur, the dates when construction activities temporarily or permanently cease on a portion of the site, and the dates when stabilization measures are initiated.
- 12. Stabilization measures shall be initiated as soon as practicable in portions of the site where construction activities have temporarily or permanently ceased, and construction activities will not resume within 21 days. When the initiation of stabilization measures by the 14th day is precluded by weather conditions, stabilization measures shall be initiated as soon as practicable.
- 13. This approval does not authorize the installation of temporary aboveground storage tanks on this project. If the contractor desires to install a temporary aboveground storage tank for use during construction, an application to modify this approval must be submitted and approved prior to installation. The application must include information related to tank location and spill containment. Refer to Standard Condition No. 5, above.

#### **After Completion of Construction:**

- 14. Owners of permanent BMPs and measures must ensure that the BMPs and measures are constructed and function as designed. A Texas Licensed Professional Engineer must certify in writing that the permanent BMPs or measures were constructed as designed. The certification letter must be submitted to the Austin Regional Office within 30 days of site completion.
- 15. The applicant shall be responsible for maintaining the permanent BMPs after construction until such time as the maintenance obligation is either assumed in writing by another entity having ownership or control of the property (such as without limitation, an owner's association, a new property owner or lessee, a district, or municipality) or the ownership of the property is transferred to the entity. Such entity shall then be responsible for maintenance until another entity assumes such obligations in writing or ownership is transferred. A copy of the transfer of responsibility must be filed with the executive director through the Austin Regional Office within 30 days of the transfer. A copy of the transfer form (TCEQ-10263) is enclosed.
- 16. Upon legal transfer of this property, the new owner(s) is required to comply with all terms of the approved Contributing Zone Plan. If the new owner intends to commence any new regulated activity on the site, a new Contributing Zone Plan that specifically addresses the new activity must be submitted to the executive director. Approval of the plan for the new

Mr. Bart Barrett Page 4 November 12, 2020

regulated activity by the executive director is required prior to commencement of the new regulated activity.

- 17. A Contributing Zone Plan approval or extension will expire and no extension will be granted if more than 50 percent of the total construction has not been completed within ten years from the initial approval of a plan. A new Contributing Zone Plan must be submitted to the Austin Regional Office with the appropriate fees for review and approval by the executive director prior to commencing any additional regulated activities.
- 18. At project locations where construction is initiated and abandoned, or not completed, the site shall be returned to a condition such that the aquifer is protected from potential contamination.

This action is taken under authority delegated by the Executive Director of the Texas Commission on Environmental Quality. If you have any questions or require additional information, please contact the Edwards Aquifer Protection Program of the Austin Regional Office at 512-339-2929.

Sincerely,

Robert Sadlier, Section Manager Edwards Aquifer Protection Program

Texas Commission on Environmental Quality

RCS/jv

Enclosures: Change in Responsibility for Maintenance of Permanent BMPs, Form TCEQ-10263

cc: Mr. Bailey Harrington, WGI

# Change in Responsibility for Maintenance on Permanent Best Management Practices and Measures

The applicant is no longer responsible for maintaining the permanent best management practice (BMP) and other measures. The project information and the new entity responsible for maintenance is listed below.

Customer:				<u>.</u>	
Regulated Entity Name	:				
Site Address:					
City, Texas, Zip:					
County:					
Approval Letter Date:			<u></u>		<del></del>
BMPs for the project:					
New Responsible Party	/:				
Name of contact:					
Mailing Address:					
City, State:				Zip:	
Telephone:			FAX:		
Signature of New Resp	onsible Party	– Date			

I acknowledge and understand that I am assuming full responsibility for maintaining all permanent best management practices and measures approved by the TCEQ for the site, until another entity assumes such obligations in writing or ownership is transferred.

If you have questions on how to fill out this form or about the Edwards Aquifer protection program, please contact us at 210/490-3096 for projects located in the San Antonio Region or 512/339-2929 for projects located in the Austin Region.

Individuals are entitled to request and review their personal information that the agency gathers on its forms. They may also have any errors in their information corrected. To review such information, contact us at 512/239-3282.

### **TCEQ Approved CZP and Permanent BMP**

#### **Central Registry**

The Customer Name displayed may be different than the Customer Name associated to the Additional IDs related to the customer. This name may be different due to ownership changes, legal name changes, or other administrative changes.

Detail of: Edwards Aquifer Permit 11002153

For: LEANDER STATION MULTI FAMILY (RN110460532 ...)

SE OF HERO WAY AND MEL MATHIS AVE

Permit Status: ACTIVE

Held by: WP WEST ACQUISITIONS LLC (CN603869256 ...) View 'Issued To' History ...

RESPONSIBLE PARTY Since 07/16/2020 View Compliance History ...

Mailing Address: 211 E 7TH ST STE 620 AUSTIN, TX 78701 -3218

Legal	Description	Start Date	End Date	Туре	Status	Status Date
11002153	EDWARDS AQUIFER	07/16/2020		PERMIT	APPROVED	11/12/2020

Tracking No.	Туре	Value	Start Date	End Date
25373003	APPLICATION RECEIVED	07/16/2020	07/16/2020	11/12/2020

Physical	Description	Start Date	Туре	Status	Status Date
LEANDER STATION MULTI FAMILY		07/16/2020	EDWARDS AQUIFER SITE	SEE LEGAL STATUS	07/16/2020

Tracking No.	Туре	Value	Start Date	End Date
25373027	Project Area	11.78 ACRES	08/12/2020	
25373028	Watershed	BRUSHY CREEK	08/12/2020	
25721739	Permanent BMP Name	SEDIMENTATION/FILTRATION BASIN	08/12/2020	
25721738	WASTEWATER TREATMENT PLANT	LEANDER WRC	08/12/2020	

#### **Central Registry**

The Customer Name displayed may be different than the Customer Name associated to the Additional IDs related to the customer. This name may be different due to ownership changes, legal name changes, or other administrative changes.

Detail of: Edwards Aquifer Permit 11002153

For: LEANDER STATION MULTI FAMILY (RN110460532 ...)

SE OF HERO WAY AND MEL MATHIS AVE

Permit Status: ACTIVE

Held by: WP WEST ACQUISITIONS LLC (CN603869256 ...) View 'Issued To' History ...

RESPONSIBLE PARTY Since 07/16/2020 View Compliance History ...

Mailing Address: 211 E 7TH ST STE 620 AUSTIN, TX 78701 -3218

# PERMANENT BMP NAME - SEDIMENTATION/FILTRATION BASIN - 08/12/2020 - Tracking No. 25721739

Tracking No.	Туре	Value	Start Date	<b>End Date</b>
25721740	Permanent BMP Type	SAND FILTER BASIN	08/12/2020	



#### ATTACHMENT B – NARRATIVE OF PROPOSED MODIFICATION

The previous CZP was approved for a total of 9.12 acres of impervious cover. The existing approved development has 7.22 acres of impervious cover. The assumed impervious cover for the proposed project site in the approved plans was 82,568 sq. ft. or ~1.90 acres. This proposed modification plan adds a total of 1.84 acres of impervious cover, however, of this 1.73 acres of impervious cover contributes to the pond. The proposed site acreage is 2.23 acres total, and 2.00 acres flows to the existing pond. The other 0.23 acres flows offsite and has 0.11 acres of impervious cover.

The existing sedimentation filtration pond was designed for the 9.12 acres of impervious cover and an overall drainage area of 11.78 acres. The addition of this proposed site (2.23 acres) brings the total impervious cover to the pond to 8.95 acres which is below the approved design of the pond.




# ATTACHMENT C - CURRENT SITE PLAN OF THE APPROVED PROJECT

348 MAIN STREET, LEANDER, TX 78641 20-TOD-SD-020

FLOODPLAIN DEVELOPMENT PLANS 20-TOD-FPD-020-007

LEANDER, WILLIAMSON COUNTY, TEXAS 78641



BEING 15.968 ACRES OF LAND, MORE OR LESS, BEING OUT OF AND A PART OF THE TALBOT CHAMBERS SURVEY, ABSTRACT NO. 125, AND THE ELIJAH D. HARMON SURVEY, ABSTRACT NO. 6, IN THE CITY OF LEANDER, WILLIAMSON COUNTY, TEXAS, BEING A PORTION OF THAT CERTAIN CALLED 94.24 ACRE TRACT DESCRIBED AS TRACT NO. 3 IN A SPECIAL WARRANTY DEED TO TRANSIT VILLAGE INVESTMENT, LTD., OF RECORD IN DOCUMENT NO. 2006112794, OFFICIAL PUBLIC RECORDS OF WILLIAMSON COUNTY, TEXAS (O.P.R.W.C.T.)

# 3 Nov 2020 TEXAS REG. NO. F-15085 114304 AUSTIN, TEXAS 78702

I CERTIFY THAT THESE ENGINEERING DOCUMENTS ARE COMPLETE, ACCURATE AND ADEQUATE FOR THE INTENDED PURPOSES, INCLUDING CONSTRUCTION, BUT ARE NOT AUTHORIZED FOR CONSTRUCTION PRIOR TO FORMAL CITY APPROVAL. THE PLAN IS COMPLETE, ACCURATE AND IN COMPLIANCE WITH CHAPTER 25-8 SUBCHAPTER A OF THE LAND DEVELOPMENT CODE.

	SHEET NO.	SHEET TITLE
C-001	1	COVER SHEET
C-002	2	GENERAL NOTES
C-002.1	3	PLAT-1
C-002.2	4	PLAT-2
C-002.3	5	PLAT-3
C-002.4	6	PLAT-4
C100	7	EXISTING CONDITIONS
CD100	8	DEMOLITION PLAN
C200	9	EROSION & SEDIMENTATION CONTROL PLAN
CG100	10	OVERALL GRADING PLAN
CG101	11	ENLARGED GRADING PLAN A
CG102	12	ENLARGED GRADING PLAN B
CG103	13	ENLARGED GRADING PLAN C
CG104	14	ENLARGED GRADING PLAN D
CG201	15	ENLARGED DRAINAGE PLAN A
CG202	16	ENLARGED DRAINAGE PLAN B
CG203	17	ENLARGED DRAINAGE PLAN C
CG204	18	ENLARGED DRAINAGE PLAN D
CG300	19	EXISTING DRAINAGE AREA MAP
CG400	20	PROPOSED DRAINAGE AREA MAP
CG401	21	PROPOSED INLET DRAINAGE AREA MAP
CS100	22	OVERALL SITE AND STRIPING PLAN
CS101	23	ENLARGED SITE PLAN A
CS102	24	ENLARGED SITE PLAN B
CS103	25	ENLARGED SITE PLAN C
CS104	26	ENLARGED SITE PLAN D
CG500	27	ENLARGED POND PLAN
CG501	28	POND DETAILS & CALCULATIONS
CG502	29	GEOMEMBRANE LINER DETAILS
CG503	30	POND PUMP SPECIFICATIONS
CU100	31	OVERALL UTILITY PLAN
CU102	32	ENLARGED UTILITY PLAN A
CU103	33	ENLARGED UTILITY PLAN B
CU104	34	ENLARGED UTILITY PLAN C
CU105	35	ENLARGED UTILITY PLAN D
CT100	36	TRAFFIC CONTROL PLAN
C501	37	CONSTRUCTION DETAILS - 1
C502	38	CONSTRUCTION DETAILS - 2
C503	39	CONSTRUCTION DETAILS - 3
C-504	40	CONSTRUCTION DETAILS - 4
C-505	41	CONSTRUCTION DETAILS - 5
L0.01	42	TREE INVENTORY & LANDSCAPE WORKSHEET
L0.02	43	TREE PRESERVATION PLAN
L0.03	44	PLANTING PLAN
L0.04	45	PLANTING PLAN
L0.05	46	PLANTING PLAN
L0.06	47	PLANTING PLAN
L0.07	48	PLANTING PLAN
L0.08	49	PLANTING PLAN
L0.09	50	PLANTING PLAN
E-1.2	51	SITE PLAN

**CIVIL SHEET INDEX** 

APPROVED BY:	
ROBIN M. GRIFFIN, AICP, PLANNING DIRECTOR	DATE
WAYNE S. WATTS, P.E., CFM, CITY ENGINEER	DATE
MARK TUMMONS, CPRP, DIRECTOR OF PARKS AND RECREATION	DATE
CHIEF JOSHUA DAVIS, FIRE MARSHAL	DATE



LEANDI

20-TOD-SD-020

20-FDP-007

RANSIT VILLAGE INVESTMENTS, LTD 2215 WESTLAKE DRIVE, SUITE 300

WANTMAN GROUP, INC. 2021 E. 5TH STREET, SUITE 200 (512) 669-5560 CONTACT: JORDAN MILLER

SURVEYOR: WANTMAN GROUP, INC 2021 E. 5TH STREET, SUITE 200 AUSTIN, TX 78702 (512) 669-5560

SUBMITTAL DATE:

CONTACT: COLEEN JOHNSON

08/25/2020

S2 - STATION SECTOR; T5 URBAN CENTER ZONE; LEANDER STATION PUD

# LAND USE SUMMARY:

LOT	AREA (AC)	PROPOSED USE	IMPERVIOUS COVER
1	2.00	COMMERCIAL	0 AC
2	13.96	MULTIFAMILY	5.58 AC
TOTAL	15.96	-	5.58 AC

**DEVELOPER** 

WOOD PARTNERS, LLC

HOUSTON, TX 77046 (713) 904-2681

ARCHITECT: DESIGN BALANCE, INC

ROCKWALL, TX 75032 (214) 668-2306

CONTACT: JOHN WOMBLE, AIA

CONTACT: BART BARRETT

8 GREENWAY PLAZA, SUITE 1120

### LOT 2 BUILDING CALCULATIONS:

BUILDING IMPERVIOUS COVER: TOTAL UNITS:

# FLOODPLAIN INFORMATION:

# PORTIONS OF THE TRACT SHOWN HEREON LIE WITHIN;

ZONE "X" (0.2%) AREAS OF 0.2% ANNUAL CHANCE FLOOD; AREAS OF 1 % ANNUAL CHANCE FLOOD WITH AVERAGE DEPTHS OF LESS THAN 1 FOOT OR WITH DRAINAGE AREAS LESS THAN 1 SQUARE MILE; AND AREAS PROTECTED BY LEVEES FROM 1 % ANNUAL CHANCE FLOOD; ZONE "AE" BASE FLOOD ELEVATIONS DETERMINED:

ZONE "AE" REGULATORY FLOODWAY (CHANNEL OF A STREAM PLUS ANY ADJACENT FLOODPLAIN AREAS THAT MUST BE KEPT FREE OF ENCROACHMENT SO THE 1% ANNUAL CHANCE FLOOD CAN BE CARRIED WITHOUT SUBSTANTIAL INCREASES IN FLOOD HEIGHTS;

ALL AS IDENTIFIED BY THE FEDERAL EMERGENCY MANAGEMENT AGENCY, NATIONAL FLOOD INSURANCE PROGRAM, AS SHOWN ON MAP NO. 48491C0455F, MAP REVISED DECEMBER 20, 2019, FOR WILLIAMSON COUNTY, TEXAS AND INCORPORATED AREAS. IF THIS SITE IS NOT WITHIN AN IDENTIFIED SPECIAL FLOOD HAZARD AREA, THIS FLOOD STATEMENT DOES NOT IMPLY THAT THE PROPERTY AND/OR THE STRUCTURES THEREON WILL BE FREE FROM FLOODING OR FLOOD DAMAGE. THIS FLOOD STATEMENT SHALL NOT CREATE LIABILITY ON THE PART OF THE SURVEYOR.

FEMA LOMR FOR THE SITE 19-06-3344P-481536 EFFECTIVE 10/30/2020

19-06-3660P-481536 EFFECTIVE 10/30/2020

CITY OF LEANDER FLOODPLAIN PERMIT: 20-FDP-XXX

# WATERSHED:

THE SITE IS LOCATED WITHIN THE BRUSHY CREEK WATERSHED AND THE EDWARDS AQUIFER CONTRIBUTING ZONE ACCORDING TO TCEQ.

# BENCHMARK:

TBM #10000- N: 10184309.22, E: 3078248.44, ELEV.= 956.82' (SET 5/8" I.R.&C."GPS/TRAV WGI") TBM #10001- N: 10184725.51, E: 3078069.80, ELEV.= 952.84' (SET 5/8" I.R.&C."GPS/TRAV WGI") TBM #10003- N: 10185232.22, E: 3078904.73, ELEV.= 944.31' (SET 5/8" I.R.&C."GPS/TRAV WGI") TBM #10004- N: 10184658.11, E: 3078331.73, ELEV.= 948.40' (SET 5/8" I.R.&C."GPS/TRAV WGI") TBM #10005- N: 10184650.36, E: 3078935.54, ELEV.= 944.45' (SET 5/8" I.R.&C."GPS/TRAV WGI") TBM #12791- N: 10184981.69, E: 3078074.70, ELEV.= 949.13' (SET %" I.R.&C."GPS/TRAV WGI")

- 1. RELEASE OF THIS APPLICATION DOES NOT CONSTITUTE A VERIFICATION OF ALL DATA, INFORMATION AND CALCULATIONS SUPPLIED BY THE APPLICANT. THE ENGINEER OF RECORD IS SOLELY RESPONSIBLE FOR THE COMPLETENESS, ACCURACY AND ADEQUACY OF HIS SUBMITTAL, WHETHER OR NOT THE APPLICATION IS REVIEWED FOR CODE COMPLIANCE BY CITY ENGINEERS.
- 2. BY THE ACT OF SUBMITTING A BID FOR THE PROPOSED CONTRACT, THE BIDDER WARRANTS THAT THE BIDDER, AND ALL SUBCONTRACTORS AND MATERIAL SUPPLIERS HE INTENDS TO USE HAVE CAREFULLY AND THOROUGHLY REVIEWED THE DRAWINGS AND SPECIFICATIONS AND OTHER CONTRACT DOCUMENTS AND HAVE FOUND THEM COMPLETE AND FREE FROM ANY AMBIGUITIES AND SUFFICIENT FOR THE PURPOSE INTENDED. THE BIDDER FURTHER WARRANTS THAT TO THE BEST OF HIS OR HIS SUBCONTRACTORS AND MATERIAL SUPPLIERS KNOWLEDGE ALL MATERIALS AND PRODUCTS SPECIFIED OR INDICATED HEREIN ARE ACCEPTABLE FOR ALL APPLICABLE CODES AND AUTHORITIES.
- 3. THE LOCATION OF ALL EXISTING UTILITIES SHOWN ON THESE PLANS HAS BEEN BASED UPON RECORD INFORMATION AND/OR A FIELD SURVEY, AND MAY NOT MATCH LOCATIONS AS CONSTRUCTED. THE CONTRACTOR SHALL CONTACT THE "ONE CALL" SYSTEM @ 811, OR THE OWNER OF EACH INDIVIDUAL UTILITY, FOR ASSISTANCE IN DETERMINING EXISTING UTILITY LOCATIONS PRIOR TO BEGINNING CONSTRUCTION. CONTRACTOR SHALL FIELD VERIFY LOCATIONS OF UTILITY CROSSING PRIOR TO BEGINNING CONSTRUCTION.
- 4. ALL CONSTRUCTION OPERATIONS SHALL BE ACCOMPLISHED IN ACCORDANCE WITH APPLICABLE REGULATIONS OF THE U.S. OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION. (OSHA STANDARDS MAY BE PURCHASED FROM THE GOVERNMENT PRINTING OFFICE; INFORMATION AND RELATED REFERENCE MATERIALS MAY BE PURCHASED FROM OSHA, WASHINGTON SQUARE BLVD, SUITE 203, 800 DOLOROSA ST, SAN ANTONIO, TEXAS
- 5. CONTRACTOR SHALL RESTORE ALL SIGNS AND PAVEMENT MARKINGS TO EXISTING CONDITIONS FOLLOWING THE COMPLETION OF EACH PHASE OF CONSTRUCTION. CONTRACTORS SHALL REFER TO THE TEXAS MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (TMUTCD) FOR SIGN AND MARKING DIMENSIONS AND COLORS.
- 6. THIS DEVELOPMENT WILL NOT BE GATED.
- 7. PUBLIC IMPROVEMENTS ARE TO BE CONSTRUCTED BY SEPARATE PERMIT (20-TOD-PICP-025 ALTA LEANDER STATION).
- 8. ALL MASONRY REQUIREMENTS WILL ADHERE TO THE CITY OF LEANDER DEVELOPMENT AGREEMENT

REVISION # DESCRIPTION APPROVAL

#### **GENERAL NOTES: REVISED FEBRUARY 25,2020**

- THE CONTRACTOR SHALL VERIFY ALL DEPTHS AND LOCATIONS OF EXISTING UTILITIES PRIOR TO ANY CONSTRUCTION. ANY DISCREPANCIES WITH CONSTRUCTION PLANS FOUND IN THE FIELD SHALL BE BROUGHT IMMEDIATELY TO THE ATTENTION OF THE ENGINEER.
- THE CONTRACTOR SHALL CONTACT THE TEXAS EXCAVATION SYSTEM AT 1-800-344-8377 FOR EXISTING UTILITY LOCATIONS 48 HOURS PRIOR TO THE START OF CONSTRUCTION. THE CONTRACTOR SHALL VERIFY THE LOCATIONS OF ALL UTILITIES THAT ARE TO BE EXTENDED, TIED TO, CROSSED, OR ALTERED; OR SUBJECT TO DAMAGE/INCONVENIENCE BY THE CONSTRUCTION OPERATIONS.
- CONTACT THE CITY OF LEANDER PUBLIC WORKS DEPARTMENT FOR EXISTING WATER, WASTEWATER, STREET LIGHT ELECTRICAL WIRING, AND TRAFFIC SIGNAL WIRING LOCATIONS A MINIMUM OF 48 HOURS PRIOR TO START OF CONSTRUCTION. a. LOCATE REQUESTS MUST INCLUDE A COPY OF YOUR 811 TICKET.

b. REFRESH ALL LOCATES BEFORE 14 DAYS – LOCATE REFRESH REQUESTS MUST INCLUDE A COPY OF YOUR 811 TICKET. TEXAS PIPELINE DAMAGE PREVENTION LAWS REQUIRE THAT A LOCATE REFRESH REQUEST BE SUBMITTED BEFORE 14 DAYS, OR IF LOCATION MARKERS ARE NO LONGER VISIBLE.

c. REPORT ALL DAMAGE TO CITY INFRASTRUCTURE IMMEDIATELY - IF YOU WITNESS OR EXPERIENCE EXCAVATION DAMAGE, PLEASE CONTACT THE CITY OF LEANDER PUBLIC WORKS DEPARTMENT BY PHONE. IF DAMAGE IS WITNESSED OR EXPERIENCED AFTER HOURS, CALL THE CITY OF LEANDER UTILITIES ON-CALL LINE AT THE NUMBER LISTED ABOVE.

- ANY CHANGES OR REVISIONS TO THESE PLANS MUST FIRST BE SUBMITTED TO THE CITY BY THE DESIGN ENGINEER FOR REVIEW AND WRITTEN APPROVAL PRIOR TO CONSTRUCTION OF THE REVISION.
- A TRAFFIC CONTROL PLAN, IN ACCORDANCE WITH THE TEXAS MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES, SHALL BE SUBMITTED TO THE CITY FOR REVIEW AND APPROVAL PRIOR TO ANY PARTIAL OR COMPLETE ROADWAY CLOSURES. TRAFFIC CONTROL PLANS SHALL BE SITE SPECIFIC AND SEALED BY A REGISTERED PROFESSIONAL ENGINEER. LANE CLOSURES ON ARTERIALS AND ANY FULL ROAD CLOSURES REQUIRE MESSAGE BOARDS NOTIFYING THE PUBLIC ONE WEEK PRIOR TO THE CLOSURE.
- NO WORK IS TO BE PERFORMED BETWEEN THE HOURS OF 6:00 P.M. AND 7:00 A.M. THE CITY INSPECTOR RESERVES THE RIGHT TO REOUIRE THE CONTRACTOR TO UNCOVER ALL WORK PERFORMED WITHOUT INSPECTION. FURTHER, THERE IS A NOISE ORDINANCE IN EFFECT FOR CONSTRUCTION ACTIVITY BETWEEN THE HOURS OF 9 PM AND 7 AM. REQUESTS FOR EXCEPTIONS TO THE ORDINANCE MUST BE MADE TO LEANDER CITY COUNCIL.
- CONTACT THE CITY INSPECTOR 4 DAYS PRIOR TO WORK TO SCHEDULE ANY INSPECTIONS ON WEEKENDS OR CITY HOLIDAYS.
- 8. NO STREET LIGHTS OR SIGNS OF ANY KIND ARE TO BE PLACED WITHIN ANY SIDEWALKS.
- 9. NO BLASTING IS ALLOWED.
- 10. ANY EXISTING UTILITIES, PAVEMENT, CURBS, SIDEWALKS, STRUCTURES, TREES, ETC., THAT ARE DAMAGED OR REMOVED SHALL BE REPAIRED OR REPLACED BY THE CONTRACTOR AT NO COST TO THE
- 11. THE CONTRACTOR SHALL GIVE THE CITY OF LEANDER 48 HOURS NOTICE BEFORE BEGINNING EACH PHASE OF CONSTRUCTION. CONTACT ASSIGNED CITY INSPECTOR.
- 12. A PRE-CONSTRUCTION CONFERENCE SHALL BE HELD WITH THE CONTRACTOR, DESIGN ENGINEER/PERMIT APPLICANT AND THE CITY OF LEANDER REPRESENTATIVES PRIOR TO INSTALLATION OF EROSION/SEDIMENTATION CONTROLS AND TREE PROTECTION MEASURES AND PRIOR TO BEGINNING ANY WORK. THE CONTRACTOR SHALL NOTIFY THE CITY OF LEANDER PLANNING DEPARTMENT PLANNING COORDINATOR AT LEAST THREE (3) DAYS PRIOR TO THE MEETING DATE.
- 13. THE CONTRACTOR AND ENGINEER SHALL KEEP ACCURATE RECORDS OF ALL CONSTRUCTION THAT DEVIATES FROM THE PLANS. THE ENGINEER SHALL FURNISH THE CITY OF LEANDER ACCURATE "RECORD DRAWINGS" FOLLOWING THE COMPLETION OF ALL CONSTRUCTION. THESE "RECORD DRAWINGS" SHALL MEET THE SATISFACTION OF THE ENGINEERING DEPARTMENTS PRIOR TO FINAL ACCEPTANCE
- 14. WHEN CONSTRUCTION IS BEING CARRIED OUT WITHIN EASEMENTS, THE CONTRACTOR SHALL CONFINE HIS WORK TO WITHIN THE PERMANENT AND TEMPORARY EASEMENTS. PRIOR TO ACCEPTANCE, THE CONTRACTOR SHALL BE RESPONSIBLE FOR REMOVING ALL TRASH AND DEBRIS WITHIN THE PERMANENT EASEMENTS. CLEANUP SHALL BE TO THE SATISFACTION OF THE ENGINEER.
- 15. CONTRACTOR TO LOCATE, PROTECT, AND MAINTAIN BENCHMARKS, MONUMENTS, CONTROL POINTS AND PROJECT ENGINEERING REFERENCE POINTS. RE-ESTABLISH DISTURBED OR DESTROYED ITEMS BY REGISTERED PROFESSIONAL LAND SURVEYOR IN THE STATE OF TEXAS, AT NO ADDITIONAL COST TO
- 16. THE CONTRACTOR SHALL PROTECT ALL EXISTING FENCES. IN THE EVENT THAT A FENCE MUST BE REMOVED, THE CONTRACTOR SHALL REPLACE SAID FENCE OR PORTION THEREOF WITH THE SAME TYPE OF FENCING TO A QUALITY OF EQUAL OR BETTER THAN THE ORIGINAL FENCE.
- 17. ALL CONSTRUCTION SHALL BE IN ACCORDANCE WITH THE LATEST CITY OF AUSTIN STANDARD SPECIFICATIONS. CITY OF AUSTIN STANDARDS SHALL BE USED UNLESS OTHERWISE NOTED IN DETAILS.
- 18. ALL CONSTRUCTION OPERATIONS SHALL BE ACCOMPLISHED IN ACCORDANCE WITH APPLICABLE REGULATIONS OF THE U.S. OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA). OSHA STANDARDS MAY BE PURCHASED FROM THE GOVERNMENT PRINTING OFFICE; INFORMATION AND RELATED REFERENCE MATERIALS MAY BE PURCHASED FROM OSHA, 1033 LA POSADA DR. SUITE 375, AUSTIN, TEXAS 78752-3832.
- 19. ALL MATERIALS AND CONSTRUCTION PROCEDURES WITHIN THE SCOPE OF THIS CONTRACT WHERE NOT SPECIFICALLY COVERED IN THE PROJECT SPECIFICATIONS SHALL CONFORM TO ALL CITY OF LEANDER DETAILS AND CITY OF AUSTIN STANDARD SPECIFICATIONS.
- 20. PROJECT SPECIFICATIONS TAKE PRECEDENCE OVER PLANS AND SPECIAL CONDITIONS GOVERN OVER TECHNICAL SPECIFICATIONS.
- 21. HOT MIX ASPHALTIC CONCRETE PAVEMENT SHALL BE MINIMUM THICKNESS OF 2 INCHES WITH NO RECYCLED ASPHALT SHINGLES CONTENT. THE PORTLAND CEMENT CONCRETE SHOULD BE AIR ENTRAINED TO RESULT IN A 4 PERCENT +/- 1 PERCENT AIR, SHOULD HAVE A MAXIMUM SLUMP OF 5 INCHES, AND SHOULD HAVE A MINIMUM 28-DAY COMPRESSIVE STRENGTH OF 4,000 PSI. A LIQUID MEMBRANE-FORMING CURING COMPOUND SHOULD BE APPLIED AS SOON AS PRACTICAL AFTER BROOM FINISHING THE CONCRETE SURFACE. THE CURING COMPOUND WILL HELP REDUCE THE LOSS OF WATER FROM THE CONCRETE. THE REDUCTION IN THE RAPID LOSS IN WATER WILL HELP REDUCE SHRINKAGE CRACKING OF THE CONCRETE. WHEN PROOFROLLING THE SUBGRADE, WEAK OR SOFT AREAS IDENTIFIED SHOULD BE REMOVED AND REPLACED WITH SUITABLE, COMPACTED ON-SITE CLAYS, FREE OF ORGANICS, OVERSIZED MATERIALS, AND DEGRADABLE OR DELETERIOUS MATERIALS.
- 22. CONTRACTOR SHALL IMMEDIATELY NOTIFY THE ENGINEER OF ANY QUESTIONS THAT MAY RISE CONCERNING THE INTENT, PLACEMENT, OR LIMITS OF DIMENSIONS OR GRADES NECESSARY FOR THE CONSTRUCTION OF THIS PROJECT.
- 23. CONTRACTOR SHALL BE RESPONSIBLE FOR ACQUIRING ALL PERMITS, TESTS, APPROVALS AND ACCEPTANCES REQUIRED TO COMPLETE CONSTRUCTION OF THIS PROJECT.
- 24. THE CONTRACTOR SHALL BE RESPONSIBLE FOR ALL COORDINATION BETWEEN HIMSELF AND OTHER CONTRACTORS AND UTILITIES IN THE VICINITY OF THE PROJECT. THIS INCLUDES GAS, WATER, WASTEWATER, ELECTRICAL, TELEPHONE, CABLE TV AND STREET DRAINAGE WORK. ONCE THE CONTRACTOR BECOMES AWARE OF A POSSIBLE CONFLICT, IT IS THE CONTRACTOR'S RESPONSIBILITY TO NOTIFY THE ENGINEER WITHIN TWENTY-FOUR (24) HOURS.
- 25. THE CONTRACTOR MUST OBTAIN A CONSTRUCTION WATER METER FOR ALL WATER USED DURING CONSTRUCTION. A COPY OF THIS PERMIT MUST BE CARRIED AT ALL TIMES BY ALL WHO USE WATER.
- 26. CONTRACTOR SHALL BE RESPONSIBLE FOR KEEPING ROADS AND DRIVES ADJACENT TO AND NEAR THE SITE FREE FROM SOIL, SEDIMENT AND DEBRIS. CONTRACTOR WILL NOT REMOVE SOIL, SEDIMENT OR DEBRIS FROM ANY AREA OR VEHICLE BY MEANS OF WATER. ONLY SHOVELING AND SWEEPING WILL BE ALLOWED. CONTRACTOR WILL BE RESPONSIBLE FOR DUST CONTROL FROM THE SITE.
- 27. THE CITY OF LEANDER SHALL NOT BE PETITIONED FOR ACCEPTANCE UNTIL ALL NECESSARY EASEMENT DOCUMENTS HAVE BEEN SIGNED AND RECORDED.
- 28. AN ENGINEER'S CONCURRENCE LETTER AND RECORD DRAWINGS SHALL BE SUBMITTED TO THE ENGINEERING DEPARTMENT PRIOR TO THE ISSUANCE OF CERTIFICATE OF COMPLETION OR SUBDIVISION ACCEPTANCE. THE ENGINEER AND CONTRACTOR SHALL VERIFY THAT ALL FINAL REVISIONS AND CHANGES HAVE BEEN MADE TO THE DIGITAL COPY PRIOR TO CITY SUBMITTAL. RECORD CONSTRUCTION DRAWINGS, INCLUDING ROADWAY AND ALL UTILITIES SHALL BE PROVIDED TO THE CITY IN DIGITAL FORMAT AS AUTOCAD ".DWG" FILES, MICROSTATION ".DGN" FILES OR ESRI ".SHP" FILES ON CD ROM. LINE WEIGHTS, LINE TYPES AND TEXT SIZE SHALL BE SUCH THAT IF HALF-SIZE PRINTS (11"X17") WERE

PRODUCED, THE PLANS WOULD STILL BE LEGIBLE. ALL REQUIRED DIGITAL FILES SHALL CONTAIN A MINIMUM OF TWO CONTROL POINTS REFERENCED TO THE STATE PLANE GRID COORDINATE SYSTEM - TEXAS CENTRAL ZONE (4203), IN US SURVEY FEET AND SHALL INCLUDE ROTATION INFORMATION AND SCALE FACTOR REQUIRED TO REDUCE SURFACE COORDINATES TO GRID COORDINATES IN US SURVEY FEET

29. TREES IN EXISTING ROW SHOULD BE PROTECTED OR NOTED IN THE PLANS TO BE REMOVED.

# CITY OF LEANDER CONTACTS:

ENGINEERING MAIN LINE: 512-528-2766 PLANNING DEPARTMENT: 512-528-2750 PUBLIC WORKS MAIN LINE: 512-259-2640 STORMWATER INSPECTIONS: 512-285-0055 UTILITIES MAIN LINE: 512-259-1142 UTILITIES ON-CALL: 512-690-4760

### **SEQUENCE OF CONSTRUCTION:**

- 1. CONDUCT PRE-CONSTRUCTION MEETING
- 2. INSTALL TEMPORARY EROSION & SEDIMENTATION CONTROLS
- ROUGH OUT POND FOR SEDIMENTATION.
- 4. INSTALL UTILITIES INCLUDING ALL FOR FIRE SUPPRESSIONS.
- BEGIN VERTICAL CONSTRUCTION.

INSTALL FIRE ACCESS LANES.

7. INSTALL FLAT WORK.

8. INSTALL LANDSCAPING.

### **EROSION CONTROL NOTES:**

- 1. THE CONTRACTOR SHALL INSTALL EROSION/SEDIMENTATION CONTROLS AND TREE PROTECTIVE FENCING PRIOR TO ANY WORK (CLEARING, GRUBBING OR EXCAVATION). CONTACT STORMWATER INSPECTOR FOR ON SITE INSPECTION PRIOR TO BEGINNING CONSTRUCTION.
- 2. THE CONTRACTOR IS REQUIRED TO INSPECT THE CONTROLS AND FENCES AT WEEKLY INTERVALS AND AFTER SIGNIFICANT RAINFALL EVENTS TO ENSURE THAT THEY ARE FUNCTIONING PROPERLY THE PERSON(S) RESPONSIBLE FOR MAINTENANCE OF CONTROLS AND FENCES SHALL IMMEDIATELY MAKE ANY NECESSARY REPAIRS TO DAMAGED AREAS. SILT ACCUMULATION AT CONTROLS MUST BE REMOVED WHEN THE DEPTH REACHES SIX (6) INCHES.
- 3. THE TEMPORARY SPOILS DISPOSAL SITE IS TO BE SHOWN IN THE EROSION CONTROL MAP.
- 4. NY ON-SITE SPOILS DISPOSAL SHALL BE REMOVED PRIOR TO ACCEPTANCE UNLESS SPECIFICALLY SHOWN ON THE PLANS. THE DEPTH OF SPOIL SHALL NOT EXCEED 10 FEET IN ANY AREA.
- 5. ALL AREAS DISTURBED OR EXPOSED DURING CONSTRUCTION SHALL BE RESTORED WITH A MINIMUM OF 6 INCHES OF TOPSOIL AND COMPOST BLEND. TOPSOIL ON SINGLE FAMILY LOTS MAY BE INSTALLED WITH HOME CONSTRUCTION. THE TOPSOIL AND COMPOST BLEND SHALL CONSIST OF 75% TOPSOIL AND 25% COMPOST.
- 6. SEEDING FOR REESTABLISHING VEGETATION SHALL COMPLY WITH THE AUSTIN GROW GREEN GUIDE OR WILLIAMSON COUNTY'S PROTOCOL FOR SUSTAINABLE ROADSIDES (SPEC 164--WC001 SEEDING FOR EROSION CONTROL). RESEEDING VARIETIES OF BERMUDA SHALL NOT BE USED.
- 7. STABILIZED CONSTRUCTION ENTRANCE IS REQUIRED AT ALL POINTS WHERE CONSTRUCTION TRAFFIC IS EXITING THE PROJECT ONTO EXISTING PAVEMENT. LINEAR CONSTRUCTION PROJECTS MAY REQUIRE SPECIAL CONSIDERATION. ROADWAYS SHALL REMAIN CLEAR OF SILT AND MUD.
- 8. TEMPORARY STOP SIGNS SHOULD BE INSTALLED AT ALL CONSTRUCTION ENTRANCES WHERE A STOP CONDITION DOES NOT ALREADY EXIST.
- 9. IN THE EVENT OF INCLEMENT WEATHER THAT MAY RESULT IN A FLOODING SITUATION, THE CONTRACTOR SHALL REMOVE INLET PROTECTION MEASURES UNTIL SUCH TIME AS THE WEATHER

# TRENCH SAFETY NOTES:

1. TRENCH SAFETY SYSTEMS TO BE UTILIZED FOR THIS PROJECT ARE DESCRIBED IN ITEM 509S "TRENCH SAFETY SYSTEMS" OF THE CITY OF AUSTIN STANDARD SPECIFICATIONS AND SHALL BE IN ACCORDANCE WITH THE LAWS OF THE STATE OF TEXAS AND THE U.S. OCCUPATION SAFETY AND HEALTH ADMINISTRATION REGULATIONS.

# TEXAS ADMINISTRATIVE CODE:

IN ACCORDANCE WITH TEXAS ADMINISTRATIVE CODE TITLE 30, PART 1, CHAPTER 290, SUBCHAPTER D. RULE 290.44.(e)(4)(B)(iv)(III): WHEN A NEW WATERLINE CROSSES UNDER A WASTEWATER MAIN OR LATERAL, THE WATERLINE SHALL BE CONSTRUCTED OF DUCTILE IRON WITH MECHANICAL OR WELDED JOINTS AS APPROPRIATE. AN ABSOLUTE MINIMUM SEPARATION DISTANCE OF ONE FOOT BETWEEN THE WATERLINE AND THE WASTEWATER MAIN OR LATERAL SHALL BE PROVIDED. BOTH THE WATERLINE AND WASTEWATER MAIN AND/OR LATERAL MUST PASS A PRESSURE AND LEAKAGE TEST AS SPECIFIED IN AWWA C600 STANDARDS.

# REFERENCE SPECIFICATIONS AND CODES:

- 1. OSHA REQUIREMENTS AND LOCAL CODES OR THOSE OF ANY REGULATORY AGENCY OR BODY THAT HAS JURISDICTION SHALL BE STRICTLY ADHERED TO.
- 2. ALL CONSTRUCTION SHALL BE IN ACCORDANCE WITH THE CITY OF AUSTIN STANDARD SPECIFICATIONS, DRAINAGE CRITERIA MANUAL, AND TRANSPORTATION CRITERIA MANUAL AS ADOPTED AND AMENDED BY THE CITY OF LEANDER.
- 3. PRIOR TO ANY CONSTRUCTION, THE CONTRACTOR SHALL APPLY FOR AND SECURE ALL PROPER PERMITS FROM THE APPROPRIATE AUTHORITIES.
- 4. THE ATTENTION OF THE CONTRACTOR IS DIRECTED TO THE CITY OF LEANDER STANDARD SPECIFICATIONS AND TO THE STATE LAW (VERNON'S ANNOTATED TEXAS STATUTES, ARTICLE 1436(C) AND THE NEED FOR EFFECTIVE PRECAUTIONARY MEASURES WHEN OPERATING EQUIPMENT IN THE VICINITY OF ELECTRICAL LINES. IF THE CONTRACTOR CHOOSES TO USE EQUIPMENT WITH THE POTENTIAL OF COMING WITHIN THE DISTANCE PRESCRIBED BY STATUTE, THE CONTRACTOR IS RESPONSIBLE FOR COORDINATION OF THE WORK WITH THE APPROPRIATE ELECTRIC UTILITY COMPANY.

# **WATER & WASTEWATER NOTES:**

- 1. PRESSURE TAPS SHALL BE IN ACCORDANCE WITH CITY OF LEANDER STANDARD SPECIFICATIONS. THE CONTRACTOR SHALL PERFORM ALL EXCAVATION, ETC. AND SHALL FURNISH, INSTALL AND AIR TEST THE SLEEVE AND VALVE. A CITY OF LEANDER INSPECTOR MUST BE PRESENT WHEN THE CONTRACTOR MAKES A TAP, AND/OR ASSOCIATED TESTS. A MINIMUM OF TWO (2) WORKING DAYS NOTICE IS REQUIRED. "SIZE ON SIZE" TAPS WILL NOT BE PERMITTED UNLESS MADE BY THE USE OF AN APPROVED FULL-CIRCLE GASKETED TAPPING SLEEVE. CONCRETE BLOCKING SHALL BE PLACED BEHIND AND UNDER ALL TAP SLEEVES A MINIMUM OF 24 HOURS PRIOR TO THE BRANCH BEING PLACED INTO SERVICE. BLOCKING SHALL BE INSPECTED PRIOR
- 2. FIRE HYDRANTS ON MAINS UNDER CONSTRUCTION SHALL BE SECURELY WRAPPED WITH A BLACK POLY WRAP BAG AND TAPED INTO PLACE. THE POLY WRAP SHALL BE REMOVED WHEN THE MAINS ARE ACCEPTED AND
- 3. CURVILINEAR WASTEWATER DESIGN LAYOUT IS NOT PERMITTED.
- 4. THRUST BLOCKING OR RESTRAINTS SHALL BE IN ACCORDANCE WITH THE CITY OF LEANDER STANDARD SPECIFICATIONS AND REQUIRED AT ALL FITTINGS PER DETAIL OR MANUFACTURER'S RECOMMENDATION. ALL FITTINGS SHALL HAVE BOTH THRUST BLOCKING AND RESTRAINTS.
- 5. MANDREL TESTING WILL BE REQUIRED ON ALL WASTEWATER PIPE. PER TCEQ, THIS TEST MUST BE CONDUCTED AFTER THE FINAL BACKFILL HAS BEEN IN PLACE AT LEAST 30 DAYS.
- 6. ALL NEWLY INSTALLED PIPES AND RELATED PRODUCTS MUST CONFORM TO AMERICAN NATIONAL STANDARDS INSTITUTE/NATIONAL SANITATION FOUNDATION (ANSI/NSF) STANDARD 61 AND MUST BE CERTIFIED BY AND ORGANIZATION ACCREDITED BY ANSI
- 7. IN ADDITION TO NORMAL COMPACTION METHODS DURING DRY WEATHER CONDITIONS, TRENCH AND MANHOLE BACKFILL IN AND/OR ADJACENT TO STREETS, STRUCTURES, DRIVEWAYS, ETC., SHOULD BE FLOODED TO PROVIDE ADDITIONAL CONSOLIDATION OF BACKFILL DURING CONSTRUCTION PERIODS THAT DO NOT EXPERIENCE SIGNIFICANT RAINFALL EVENTS PRIOR TO SUBGRADE PREPARATION, FLEXIBLE BASE PLACEMENT, PAVING OPERATIONS.
- 8. ALL WATER SERVICE, WASTEWATER SERVICE AND VALVE LOCATIONS SHALL BE APPROPRIATELY STAMPED AS

- 9. TOOLS FOR STAMPING THE CURBS SHALL BE PROVIDED BY THE CONTRACTOR. OTHER APPROPRIATE MEANS OF STAMPING SERVICE AND VALVE LOCATIONS SHALL BE PROVIDED IN AREAS WITHOUT CURBS. SUCH MEANS OF STAMPING SHALL BE SPECIFIED BY THE ENGINEER AND ACCEPTED BY THE CITY OF LEANDER
- 10. ALL PLASTIC PIPES FOR USE IN PUBLIC WATER SYSTEMS MUST BEAR THE NATIONAL SANITATION FOUNDATION SEAL OF APPROVAL (NSF-PW) AND HAVE AN ASTM DESIGN PRESSURE RATING OF AT LEAST 200
- 11. NO PIPE OR FITTING WHICH HAS BEEN USED FOR ANY PURPOSE OTHER THAN THE CONVEYANCE OF DRINKING WATER SHALL BE ACCEPTED OR RELOCATED FOR USE IN ANY PUBLIC DRINKING WATER SUPPLY
- 12. TYPICAL DEPTH OF COVER FOR ALL WASTEWATER LINES SHALL BE 48" MINIMUM, WATER LINES SHALL BE 36" MINIMUM UNDER BOTH PAVEMENT AND NATURAL GROUND. STORM SEWER SHALL BE 24" MINIMUM
- 13. THE HYDROSTATIC LEAKAGE RATE SHALL NOT EXCEED THE AMOUNT ALLOWED OR RECOMMENDED BY AWWA FORMULAS.
- 14. ALL WATER MAINS, DISTRIBUTION LINES AND SERVICE LINES SHALL BE INSTALLED IN ENCASEMENT PIPE UNDERNEATH EXISTING STREETS AND OTHER PAVED SURFACES UNLESS APPROVED WITH PLANS.
- 15. ALL MECHANICAL RESTRAINTS SHALL BE INSTALLED IN ACCORDANCE WITH THE MANUFACTURER'S INSTRUCTIONS
- 16. ALL DEAD-END WATER MAINS SHALL HAVE THRUST RESTRAINTS INSTALLED ON THE LAST THREE PIPE-LENGTHS (STANDARD 20' LAYING LENGTH), AT MINIMUM, AND THRUST BLOCKS INSTALLED ON THE PLUG. ADDITIONAL THRUST RESTRAINTS MAY BE REQUIRED BASED UPON THE MANUFACTURER'S RECOMMENDATIONS AND/OR CALCULATIONS BY THE ENGINEER OF RECORD.
- 17. WHERE WATER LINES CROSS WASTEWATER LINES AND THERE IS LESS THAN 9 FEET CLEARANCE BETWEEN LINES, THE WASTEWATER LINE SHALL BE PLACED SO THAT THE WASTEWATER PIPE SECTION IS CENTERED ON THE WATER LINE AND CONSTRUCTED IN ACCORDANCE WITH TCEQ CHAPTERS 217.53(b) AND 290.44(e).
- 18. PIPE MATERIAL FOR WATER MAINS SHALL BE PVC (AWWA C900-16 MIN. 235 PSI PRESSURE RATING). WATER SERVICES (2" OR LESS) SHALL BE POLYETHYLENE TUBING (BLACK, 200PSI, SDR- (9)). DUCTILE IRON PIPE (AWWA C115/C151, MIN. PRESSURE CLASS 250) MAY BE USED FOR WATER MAINS WITH THE EXPRESS APPROVAL OF CITY OF LEANDER ENGINEERING.
- 19. PIPE FOR PRESSURE WASTEWATER MAINS SHALL BE PVC (AWWA C900-16), GREEN AND MARKED FOR SEWER. PIPE MATERIAL FOR GRAVITY WASTEWATER MAINS SHALL BE PVC (ASTM D2241, D3034 MAX. SDR-26 OR PS115 F679) OR FIBERGLASS WITH PIPE STIFFNESS OF 72 PSI PER COA SPL WW-509.
- 20. ALL FIRE HYDRANT LEADS SHALL BE DUCTILE IRON PIPE (AWWA C115/C151 PRESSURE CLASS 350).
- 21. INTERIOR SURFACES OF ALL DUCTILE IRON POTABLE OR RECLAIMED WATER PIPE SHALL BE CEMENT-MORTAR LINED AND SEAL COATED AS REQUIRED BY AWWA C104.
- 22. ALL IRON PIPE AND FITTINGS SHALL BE WRAPPED WITH MINIMUM 8-MIL POLYETHYLENE.
- 23. THE CONTRACTOR SHALL CONTACT THE ENGINEERING DEPARTMENT INSPECTOR AT 528-2700 AT LEAST 48 HOURS PRIOR TO CONNECTING TO THE EXISTING WATER LINES.
- 24. ALL MANHOLES SHALL BE CONCRETE WITH CAST IRON RING AND COVER. TAPPING OF FIBERGLASS MANHOLES SHALL NOT BE ALLOWED.
- 25. EXISTING MANHOLES MODIFIED BY CONSTRUCTION ACTIVITY SHALL BE TESTED FOR LEAKAGE BY VACUUM. ANY EXISTING MANHOLE WHICH FAILS TO PASS THE VACUUM TEST SHALL BE CLOSELY EXAMINED BY THE INSPECTOR AND THE CONTRACTOR TO DETERMINE IF THE MANHOLE CAN BE REPAIRED. THEREAFTER, THE CONTRACTOR SHALL EITHER REPAIR OR REMOVE AND REPLACE THE MANHOLE AS DIRECTED.
- 26. PIPE CONNECTIONS TO EXISTING MANHOLES AND JUNCTION BOXES SHALL BE CONSTRUCTED IN ACCORDANCE WITH CITY OF AUSTIN SPECIFICATION 506.5.F.
- 27. LINE FLUSHING OR ANY ACTIVITY USING A LARGE QUANTITY OF WATER MUST BE COORDINATED WITH THE PUBLIC WORKS DEPARTMENT.
- 28. THE CONTRACTOR, AT HIS EXPENSE, SHALL PERFORM STERILIZATION OF ALL CONSTRUCTED POTABLE WATER LINES AND SHALL PROVIDE ALL EQUIPMENT (INCLUDING TEST GAUGES), SUPPLIES (INCLUDING CONCENTRATED CHLORINE DISINFECTING MATERIAL), AND NECESSARY LABOR REQUIRED FOR THE STERILIZATION PROCEDURE. THE STERILIZATION PROCEDURE SHALL BE MONITORED BY CITY OF LEANDER PERSONNEL. WATER SAMPLES WILL BE COLLECTED BY THE CITY OF LEANDER TO VERIFY EACH TREATED LINE HAS ATTAINED AN INITIAL CHLORINE CONCENTRATION OF 50 PPM. WHERE MEANS OF FLUSHING IS NECESSARY, THE CONTRACTOR, AT HIS EXPENSE, SHALL PROVIDE FLUSHING DEVICES AND REMOVE SAID DEVICES PRIOR TO FINAL ACCEPTANCE BY THE CITY OF LEANDER.
- 29. SAMPLING TAPS SHALL BE BROUGHT UP TO 3 FEET ABOVE GRADE AND SHALL BE EASILY ACCESSIBLE FOR CITY PERSONNEL. AT THE CONTRACTORS' REQUEST, AND IN HIS PRESENCE, SAMPLES FOR BACTERIOLOGICAL TESTING WILL BE COLLECTED BY THE CITY OF LEANDER NOT LESS THAN 24 HOURS AFTER THE TREATED LINE HAS BEEN FLUSHED OF THE CONCENTRATED CHLORINE SOLUTION AND CHARGED WITH WATER APPROVED BY
- 30. TESTING SHALL BE PERFORMED FOR ALL WASTEWATER PIPE INSTALLED AND PRESSURE PIPE HYDROSTATIC TESTING OF ALL WATER LINES CONSTRUCTED. THE OWNER'S CONTRACTOR SHALL PROVIDE ALL EQUIPMENT (INCLUDING PUMPS AND GAUGES), SUPPLIES AND LABOR NECESSARY TO PERFORM THE TESTS. THE CONTRACTOR SHALL NOTIFY THE CITY OF LEANDER ENGINEERING DEPARTMENT NO LESS THAN 48 HOURS PRIOR TO PERFORMING STERILIZATION, QUALITY TESTS, OR PRESSURE TESTS. A CITY OF LEANDER INSPECTOR SHALL BE PRESENT FOR ALL TESTS AND SHALL BE PAID FOR BY THE OWNER/CONTRACTOR. THESE SERVICES ARE PAID FOR AT THE TIME OF CONSTRUCTION PLAN SUBMITTAL.
- 31. THE CONTRACTOR SHALL NOT OPEN OR CLOSE ANY VALVE UNLESS AUTHORIZED BY THE CITY OF LEANDER.
- 32. ALL VALVE BOXES AND COVERS SHALL BE CAST IRON.

- 33. ALL WATER VALVE COVERS ARE TO BE PAINTED BLUE.
- 34. ALL WATER METER BOXES SHALL BE: a. SINGLE, 1" METER AND BELOW DFW37F-12-1CA, OR EQUAL b. DUAL, 1" METERS AND BELOW DFW39F-12-1CA, OR EQUAL c. 1.5" SINGLE METER DFW65C-14-1CA, OR EQUAL d. 2" SINGLE METER DFW1730F-12-1CA, OR EQUAL
- 35. SAND, AS DESCRIBED IN AUSTIN SPECIFICATION ITEM 510 PIPE, SHALL NOT BE USED AS BEDDING FOR WATER AND WASTEWATER LINES. ACCEPTABLE BEDDING MATERIALS ARE PIPE BEDDING STONE, PEA GRAVEL AND IN LIEU OF SAND, A NATURALLY OCCURRING OR MANUFACTURED STONE MATERIAL CONFORMING TO ASTM C33 FOR STONE QUALITY AND MEETING THE FOLLOWING GRADATION SPECIFICATION:

PERCENT RETAINED BY WEIGHT SIEVE SIZE 0-2 3/8"

36. THE CONTRACTOR IS HEREBY NOTIFIED THAT CONNECTING TO, SHUTTING DOWN, OR TERMINATING EXISTING UTILITY LINES MAY HAVE TO OCCUR AT OFF-PEAK HOURS. SUCH HOURS ARE USUALLY OUTSIDE NORMAL WORKING HOURS AND POSSIBLY BETWEEN 12 AM AND 6 AM.

95-100

- 37. ALL WASTEWATER CONSTRUCTION SHALL BE IN ACCORDANCE WITH THE TEXAS COMMISSION ON ENVIRONMENTAL QUALITY (TCEQ) REGULATIONS, 30 TAC CHAPTER 213 AND 30 TAC CHAPTER 217, AS APPLICABLE. WHENEVER TCEQ AND CITY OF LEANDER SPECIFICATION CONFLICT, THE MORE STRINGENT
- 38. MANHOLES SHALL BE COATED PER CITY OF AUSTIN SPL WW-511 (RAVEN 405 OR SPRAYWALL).
- 39. DENSITY TESTING FOR TRENCH BACKFILL LOCATED WITHIN THE LIMITS OF THE PAVED AREA IS TO BE DONE
- 40. ALL GRAVITY WASTEWATER MAINS TO BE TESTED BY CAMERA AND PAID FOR BY THE CONTRACTOR. CAMERA TESTING FOR WASTEWATER LINES IN ROADWAY SHALL OCCUR BEFORE PAVING. CONTRACTOR SHALL PROVIDE THE CITY WITH A DVD COPY OF THE FULL CAMERA INSPECTION.
- IN 12" LIFTS EVERY 500' AND AT LEAST ONCE PER LINE SEGMENT
- 41. RECLAIMED AND RECYCLED WATER LINE SHALL BE CONSTRUCTED OF "PURPLE PIPE." ALL RECLAIMED AND RECYCLED WATER VALVE COVERS SHALL BE SQUARE AND PAINTED PURPLE

# ABBREVIATIONS LEGEND:

FOUND

GUTTER

GROUND

HIGH POINT

INFORMATION

HEIGHT

IRON ROD LATERAL

LINEAR FEET

LOW POINT

MANHOLE MINIMUM

NORTHING

NUMBER

OFFSET

PROPOSED

PAVEMENT

ROCK BERM

REFERENCE

SILT FENCE

SQUARE FEET

STORM DRAIN

TOP OF CURB

TOP OF WALL

UNKNOWN

VERTICAL

WATER LINE

WATER METER

WATER VALVE

WASTEWATER

YEAR

VOLUME

WATER

TREE PROTECTION

TEMPORARY BENCHMARK

TIME OF CONCENTRATION

UNDERGROUND ELECTRIC

UNDERGROUND TELEPHONE

WATER QUALITY TRANSITION ZONE

WATER SURFACE ELEVATION

TELEPHONE

RIGHT

SHEET

SHEETS

STATION

SHT

TW

VERT

VOL

WQTZ

SHTS

SQ. FT.

STM / SD

RADIUS

NTS / N.T.S. NOT TO SCALE

LAND USE PLAN

ON CENTER (& TO &)

OVERHEAD UTILITY

POINT OF BEGINNING

POLYVINYL CHLORIDE

R.O.W. - RIGHT OF WAY

REINFORCED CONCRETE PIPE

RESILIENT SEAT GATE VALVE

TOP OF MANHOLE LID ELEVATION

HORIZONTAL

FIBER OPTIC

FACE OF CURB

FLOOD PLAIN

FINISHED GRATE AT WALL

STORM INLET PROTECTION

LIMITS OF CONSTRUCTION

MECHANICAL, ELECTRICAL & PLUMBING

TANGENT - CURVE INTERSECTION

TANGENT - TANGENT INTERSECTION

CURVE - TANGENT INTERSECTION


POINT OF CURVE INTERSECT

HIGH-DENSITY POLYETHYLENE

BOC

NOTE: SOME ABBREVIATIONS LISTED BELOW ARE NOT USED IN THIS

PLAN SET. APPROXIMATELY APPROX ASPHALT BACK OF CURB VERTICAL TANGENT CURVE INTERSECT ELEVATION **BVCS** VERTICAL TANGENT CURVE INTERSECT STATION CLEAN-OUT COA / C.O.A.CITY OF AUSTIN CONCRETE CWQZ CRITICAL WATER QUALITY ZONE DIAMETER ELECTRIC **FASTING ELEVATION** EOP EDGE OF PAVEMENT ESC **EROSION & SEDIMENTATION CONTROL EXIST EXISTING** FILTER DIKE FF / FFE FINISHED FLOOR ELEVATION FINISHED GRADE FIRE HYDRANT FLOW LINE FORCE MAIN



AND Ш


20-FDP-007


SHEET

2 OF 51 20-TOD-SD-020

G

DATE:
PROJECT:
SCALE:
CHECK/QC:
TECH:
FIELD CREW:
SURVEY DATE:
SHEET: WGINC.COM
21 EAST 5TH STREET, SUITE 200, AUSTIN, TX
Phone No. 512.689.5560 www.wginc.co 3-4 5 6 z<del>O</del> ALTA CITY OF 385 LF 231 LF 520 LF 225 LF 175 LF CIVIL ENGINEER.
WGI ING.
WGI ING.
AUSTRIX, 78702
AUSTRIX, 78702
(512) 669–5560
CONTACT: GEORGE B. HA






SITE DEVELOPMENT PLANS ALTA LEANDER STATION
348 MAIN STREET
LEANDER, WILIAMSON COUNTY, TEXAS 78641


PLAT-1

SHEET C-002.1

3 OF 51 20-TOD-SD-020 20-FDP-007



G




WGINC.COM
EET, SUITE 200 AUSTIN, TEXAS, 78702

DEVELOPMENT PLANS ALTA LEANDER STATION 348 MAIN STREET LEANDER, WILIAMSON COUNTY, TEXAS 78641 SITE

SHEET

C-002.2 4 OF 51

20-TOD-SD-020 20-FDP-007



20-TOD-SD-020

20-FDP-007

WGInc.com
WGInc.com DAY OF DAY OF COMING COMMISSION OF FILED FOR RECORD BY THE COUNTY 1 LEANDER STATION FINAL PLAT LEANDER, WILLIAMSON COUNTY, TEXAS 6DICAL PLY NOTES:

1. THIS SUBDIVISION IS INPALLY CONTANED.
2. OF THE CITY OF LEAVER FOR.
2. OF LEAVER WITH DISTRIBUTION AND WITEVIEW COLLEGE.
3. A BAULDION CERROL IS SEQUENCED FROM THE CITY OF LEAVER PROPERTY.
3. A BAULDION CERROL SEGUENCES AND THE CITY OF LEAVER PROPERTY.
4. MINIMADES FROM SEGUENCES AND THE CITY OF LEAVER PROPERTY.
5. PROPERTY OWNES DEPARTMENT.
6. CONSTRUCTION OF ANY BAULDING OF STEEL WITHOUT BY THE CITY OF LEAVER PROPERTY.
6. MINIMADES FROM SEGUENCES AND THE CITY OF LEAVER PROPERTY.
6. MINIMADE OF THE ASSERDENT SOURCE FROM ACCOUNTY.
7. MINIMAD TO THE ESCREATES SHOWN PEREDY. A TENT OF LEAVER PROPERTY.
6. MINIMAD OF THE ASSERDENT SOURCE FROM A TENT OF LEAVER PROPERTY.
6. MINIMAD OF THE ASSERDENT SOURCE FROM A TENT OF LEAVER PROPERTY.
6. MINIMAD OF THE ASSERDENT SOURCE FROM A TENT OF LEAVER PROPERTY.
6. MINIMAD OF THE ASSERDENT SOURCE FROM A TENT OF LEAVER PROPERTY.
6. MINIMAD OF THE ASSERDENT SOURCE FROM A TENT OF LEAVER PROPERTY.
6. MINIMAD OF THE ASSERDENT SOURCE FROM A TENT OF LEAVER PROPERTY.
6. MINIMAD OF THE ASSERDENT SOURCE FROM A TENT OF LEAVER FROM A TENT OF THE ASSERDENT SOURCE FROM A TENT O AL 7A EFORE ME, THE UNDERSIGNED AUTHORITY, A NOT TATE, ON THIS THE DAY OF TATE, ON THIS THE DAY OF SHOULTY COMPANY, ON BEHALF OF SAID CO, UTHORIZED AGENT WITH AUTHORITY TO SIGN SAI NOVED TO ME ON THE BASIS OF STISSFACTOR! SUBSCIRBED TO THE RORECOING INSTRUMINATION THE PURPOSES AND CASE OF THE PURPOSES

LAST MODIFIED BY: JOHNNIE.GARZA
LAST MODIFIED ON: 11/4/2020 7:49 AM
PLOTTED BY: JOHNUNE GARZA
PLOTTED BY: JOHNUNE GARZA
PLOTTED BY: JOHNUNE GARZA
PLOTTED BY: JOHNUNE GARZA
PLOTTED ON: 11/4/2020 7:33 AM
WITH: \_AUTOCAD PDF (GENERAL DOCUMENTATION), PC3
PLOT STYLE: VI: 0 BRD PRODUCTION STANDARD.CTB

G

WGINCOM EAST 5TH STREET, SUITE 200 AUSTIN, TEXAS, 78702


PLAT-4


SITE DEVELOPMENT PLANS ALTA LEANDER STATION 348 MAIN STREET LEANDER, WILIAMSON COUNTY, TEXAS 78641


SHEET


C-002.4


6 OF 51 20-TOD-SD-020 20-FDP-007






























































## GABION WALL TO BE CONSTRUCTED ACCORDING TO COA SPECIFICATIONS 594S

## GABION BASKET WALL DETAIL NOT TO SCALE

## **GABION BASKET WALL NOTES:**

THIS ITEM SHALL INCLUDE FURNISHING, ASSEMBLING, FILLING, AND TYING ROCK-FILLED WIRE MESH COMPARTMENTED GABIONS AND REVET MATTRESSESS IN ACCORDANCE WITH THE LINES, GRADES, AND DIMENSIONS SHOWN ON THE DRAWINGS OR OTHERWISE ESTABLISHED IN THE FIELD BY THE ENGINEER OR DESIGNATED REPRESENATIVE. 594S.2 MATERIALS

## (1) GABION AND REVET MATTRESS WIRE

GABION WIRE SHALL BE GALVANIZED STEEL, CLASS 3 OR A COATING, SOFT TEMPER CONFORMING TO ASTM A 641, AND SHALL SPECIFICALLY MEET THE REQUIREMENTS GIVEN BELOW FOR GABIONS (12 GUAGE WIRE) AND/OR REVET MATTRESSES (13.5 WIRE GUAGE) AS CALLED OUT IN DRAWINGS. PVC COATING OF WIRE MAY BE FUSEBONDED OR EXTRUDED ONTO THE WIRE. GALVANIZATION OF WELDED WIRE SHALL BE PERFORMED EITHER BEFORE OR AFTER WELDING.

CHARACTERISTIC	GABIONS	REVET MATTRESSES
WIRE GAUGE	12 GAUGE	13.5 GAUGE
MAX. TENSILE STRENGTH (ASTM 641)	70,000 PSI. (483 mPa)	75,000 PSI. (517 mPa)
NOMINAL WIRE DIAMETER	0.106 INCH	0.0866 INCH
(ASTM A 641)	(2.7 mm)	(2.2 mm²)
MINIMUM DIAMETER	0.102 INCH	0.0826 INCH
(ASTM A 641, TABLE 3)	(2.6 mm)	(2.9 mm)
GALVANIZED, ZINC	0.80 OZ/F <sup>2</sup> f	0.70 OZ/FT
(ASTM A 641, TABLE 1)	(245 GR/M <sup>2</sup> )	(215 GR/M )

## (2) GABION MESH

WOVEN MESH SHALL BE OF A UNIFORM NONRAVELING, DOUBLE TWIST HEXAGONAL PATTERN NOMINALLY OF DIMENSIONS 3.25 INCHES BY 4.5 INCHES (83 mm BY 144mm). SELVEDGE WIRE SHALL BE 10 GUAGE (NOMINAL DIAMETER OF 3.4 mm).

(B) WELDED MESH MESH OPENING SHALL BE NOMINALLY 3 INCHES BY 3 INCHES (75 mm BY 75 mm). STRENGTH OF WELDS SHALL BEET THE FOLLOWING REQUIREMENTS WHEN TESTED IN ACCORDANCE WITH SECTION 13.4 OF ASTM, A-974:

TYPE OF STRUCTURE	WIRE SIZE	MINIMUM AVERAGE
	(DIAMETER)	WELD SHEAR STRENGTH
	GUAGE (mm)	ENGLISH UNITS (SI UNITS)
GABIONS	12 (2.7)	475 lbf (2.10 kN)
REVET MATRESS	13.5 (2.2)	292 lbf (1.30 kN)

TWISTED WIRE MESH GABIONS SHALL BE MANUFACTURED IN CONFORMANCE WITH ASTM A-975, WHILE WELDED WIRE MESH GABIONS SHALL BE MANUFACTURED IN CONFORMANCE WITH ASTM A-974.

## (3) REVET MATRESSES

WOVEN MESH SHALL BE OF A UNIFORM NONRAVELING, DOUBLE TWIST HEXAGONAL PATTERN NOMINALLY OF DIMENSIONS 2.5 INCHES BY 3.25 INCHES (64 mm BY 83mm).

SELVEDGE WIRE SHALL BE 12 GUAGE (NOMINAL DIAMETER OF 2.7 mm). (B) WELDED MESH MESH OPENING SHALL BE NOMINALLY 1.5 INCHES BY 3 INCHES (38 mm BY 76 mm). STRENGTH OF WELDS SHALL BEET THE REQUIREMENTS LISTED IN TABLE 2 FOR 13.5 GUAGE (2.2 mm) WIRE WHEN TESTED IN ACCORDANCE WITH SECTION 13.4 OF ASTM, A-974: (C) MANUFACTURING TWISTED WIRE MESH REVET MATRESSES SHALL BE MANUFACTURED IN CONFORMANCE WITH

ASTM A-975, WHILE WELDED WIRE MESH REVET MATRESSES SHALL BE MANUFACTURED IN

## CONFORMANCE WITH ASTM A-974. (4) PVC COATING

SEE CITY OF AUSTIN STANDARD SPECIFICATIONS ITEM NO 594S GABIONS AND

## (5) STONE

(A) GABION BASKET STONES STONE FILL SHALL BE DURABLE AND OF SUITABLE QUALITY TO ENSURE PERMINANENCE IN THE STRUCTURE. THE STONE USED TO FILL THE GABION BASKETS SHALL BE A CLEAN, SOUND, AND DURABLE ROCK MEETING THE FOLLOWING REQUIREMENTS. IT SHALL HAVE A WEARING LOSS LESS THAN 35% WHEN THE STONE IS TESTED WITH THE LOS ANGELES ABRASION MACHINE IN ACCORDANCE WITH ASTM TEST METHOD C535 (TXDOT TEST METHOD TEX-410A). THE LOSS OF MATERIAL EXPERIENCED DURING FIVE CYCLES OF MAGNESIUM SULFATE EXPOSURE CONDUCTED IN ACCORDANCE WITH TXDOT TEST METHOD TEX-411A FOR ROCK RIP RAP SHALL NOT EXCEED 18%. THE STONE SHALL BE WELL GRADED TO PRODUCE A DENSE FILL, ANGULAR IN TEXTURE, WHILE MEETING THE FOLLOWING GRADATION REQUIREMENTS:

	SIEVE SIZE	PERCENT BY WEIGHT (MASS)
	US (SI)	% PASSING EACH INDIVIDUAL SIEVE
[8	8 INCH (200 mm)	100
	4 INCH (100 mm)	0-5
	3 INCH (75 mm)	0

THE MINIMUM UNIT WEIGHT (UNIT MASS) OF A ROCKFILLED GABION SHALL BE 120 pcf [1.92 MEGAGRAMS (mg) PER CUBIC METER]. VERIFICATION OF UNIT WEIGHT (MASS) SHALL BE PERFORMED WHEN ORDERED BY THE ENGINEER. BY CONSTRUCTING A TEST GABION WITH MATERIALS SUPPLIED FOR CONSTRUCTION WITH THE SAME EFFORT AND METHOD INTENDED FOR

## CONNECTIONS

SEE CITY OF AUSTIN STANDARD SPECIFICATIONS ITEM NO 594S GABIONS AND REVET MATTRESSES.

## (7) FASTENER SYSTEM

PRODUCTION GABIONS.

SEE CITY OF AUSTIN STANDARD SPECIFICATIONS ITEM NO 594S GABIONS AND REVET MATTRESSES.

(8) PANEL TO PANEL JOINT STRENGTH

Texas Commission on Environmental Quality TSS Removal Calculations 04-20-2009

Project Name: Leander Station MF Date Prepared: 9/25/2020

Additional information is provided for cells with a red triangle in the upper right corner. Place the cursor over the cell. Text shown in blue indicate location of instructions in the Technical Guidance Manual - RG-348.

Characters shown in red are data entry fields Characters shown in black (Bold) are calculated fields. Changes to these fields will remove the equations used in the spreadsheet

1. The Required Load Reduction for the total project: Calculations from RG-348 Pages 3-27 to 3-30 Page 3-29 Equation 3.3: L<sub>M</sub> = 27.2(A<sub>N</sub> x P)  $L_{\text{M TOTAL PROJECT}}$  = Required TSS removal resulting from the proposed development = 80% of increased load

A<sub>N</sub> = Net increase in impervious area for the project

P = Average annual precipitation, inches Site Data: Determine Required Load Removal Based on the Entire Project Total project area included in plan \* = 11.78 Predevelopment impervious area within the limits of the plan\* = Total post-development impervious area within the limits of the plan = Total post-development impervious cover fraction\* =

L<sub>M TOTAL PROJECT</sub> = 7938 \* The values entered in these fields should be for the total project area.

Number of drainage basins / outfalls areas leaving the plan area =

## 2. Drainage Basin Parameters (This information should be provided for each basin):

Drainage Basin/Outfall Area No. = Total drainage basin/outfall area= 11.78 acres Predevelopment impervious area within drainage basin/outfall areæ 0.00 Post-development impervious area within drainage basin/outfall areæ 9.12 acres Post-development impervious fraction within drainage basin/outfall area 0.77 L<sub>M THIS BASIN</sub> = 7938

## 3. Indicate the proposed BMP Code for this basin.

PERFORATION

 $\leftarrow$  PERFORATIONS TO  $\stackrel{\sim}{-}$ 

BE 3/8" IN SIZE

SPECIFICATION

0.08 (MIN.)

125 (MIN.)

400 (MIN.)

200 (MIN.)

80 (MIN.)

275 (MIN.)

WASHED ROUNDED

RIVER GRAVEL

— SET PERFORATIONS DOWN

Removal efficiency = 89 4. Calculate Maximum TSS Load Removed (L<sub>R</sub>) for this Drainage Basin by the selected BMP Type.

RG-348 Page 3-33 Equation 3.7: L<sub>R</sub> = (BMP efficiency) x P x (A<sub>1</sub> x 34.6 + A<sub>P</sub> x 0.54)

Proposed BMP = Sand Filter

A<sub>C</sub> = Total On-Site drainage area in the BMP catchment area A<sub>i</sub> = Impervious area proposed in the BMP catchment area A<sub>P</sub> = Pervious area remaining in the BMP catchment area L<sub>R</sub> = TSS Load removed from this catchment area by the proposed BMP

A<sub>C</sub> = 11.78 acres A<sub>I</sub> = 9.12 acres A<sub>P</sub> = **2.66** acres L<sub>R</sub> = 9028 lbs

## 5. Calculate Fraction of Annual Runoff to Treat the drainage basin / outfall area

F = 0.88

6. Calculate Capture Volume required by the BMP Type for this drainage basin / outfall area.

Rainfall Depth = 1.50 inches

Post Development Runoff Coefficient = 0.59 On-site Water Quality Volume = 37820 cubic feet

Calculations from RG-348 Pages 3-36 to 3-37

Off-site area draining to BMP = 0.00 acres Off-site Impervious cover draining to BMP = 0.00 Impervious fraction of off-site area = Off-site Runoff Coefficient = 0.00

Storage for Sediment = 7564 Total Capture Volume (required water quality volume(s) x 1.20) = 45384 cubic feet

Off-site Water Quality Volume = 0

The values for BMP Types not selected in cell C45 will show NA. Designed as Required in RG-348 Pages 3-58 to 3-63 9. Filter area for Sand Filters

## 9B. Partial Sedimentation and Filtration System

Water Quality Volume for combined basins = 45384 cubic feet Minimum filter basin area = 3782 square feet

Maximum sedimentation basin area = 15128 square feet For minimum water depth of 2 feet Minimum sedimentation basin area = 945 square feet For maximum water depth of 8 feet

## Sedimentation Basin:

Seamentation	Dasiii.	
Stage (ft msl)*	Area (sf)	Storage (c
939.50	0.00	0.00
940.00	1,270.00	317.50
941.00	2,845.00	2,375.00
942.00	3,415.00	5,505.00
943.00	3,460.00	8,942.50
944.00	3,510.00	12,427.50
944.50	3,555.00	14,193.75

Filtration Basin	:	
Stage (ft msl)*	Area (sf)	Storage (c
939.50	6,275.00	0.00
940.00	6,275.00	3,137.50
941.00	6,275.00	9,412.50
942.00	6,275.00	15,687.50
943.00	6,275.00	21,962.50
944.00	6,275.00	28,237.50

944.50 | 6,275.00 | 31,375.00

## KNOCKOUT CALCUL ATION

KNOCKOUT CALCU	LATION
# of Knockouts	5
Knockout Area (ft²)	9
Head to pass water (ft)	3.5
Max Flow (CFS)	405.4
Can Pass 25-YR Flow?	TRUE
Velocity (fps)	1.8

Head to pass water (ft)	3.5
Max Flow (CFS)	405.4
Can Pass 25-YR Flow?	TRUE
Velocity (fps)	1.8

**POND NOTES:** 

1. WATER QUALITY IS TO BE PROVIDED BY A SEDIMENTATION AND FILTRATION BASIN.

2. CONCRETE WALLS OF THE SPLITTER BOX SHALL BE CONSTRUCTED WITH WATER TIGHT JOINTS. REFERENCE STRUCTURAL PLANS FOR REINFORCING, JOINTS, AND OTHERS DETAILS.

3. THE ENGINEER HAS DESIGNED THE POND WITH A RUBBER LINER TO BE INSTALLED IN BOTH SEDIMENTATION AND FILTRATION BASIN:

## FIRESTONE POND GUARD RUBBER LINER (OR EQUIVALENT) (GEOMEMBRANE LINER)

THIS LINER MUST MEET THE SPECIFICATIONS REQUIRED IN SECTION 1.6.2 OF THE AUSTIN ENVIRONMENTAL CRITERIA MANUAL.

4. TO ACCOMMODATE QA/QC FOR THIS ASPECT OF THE PROJECT, RUBBER GÉOMEMBRANE LINER TO BE INSTALLED IN ACCORDANCE WITH GEOMEMBRANE MANUFACTURER'S DETAILS USING GEOMEMBRANE MANUFACTURER'S RECOMMENDED PRODUCTS. ANY DEVIATION TO THIS PROCESS WILL BE CONSIDERED ON A CASE BY CASE BASIS AND MUST BE SUBMITTED TO THE ENGINEER FOR CONCURRENCE PRIOR TO CONSTRUCTION.

- 5. THE RUBBER LINER WILL BE INSTALLED TO POND WATER QUALITY ELEVATION IN BOTH BASINS.
- 6. WATER QUALITY CONTROLS SHALL BE MAINTAINED BY THE PROPERTY OWNER.

## SEDIMENTATION BASIN MAINTENANCE NOTES:

1. SILT SHOULD BE REMOVED WHEN THE ACCUMULATION EXCEEDS SIX (6) INCHES IN SEDIMENT BASINS WITHOUT SEDIMENT TRAPS. IN BASINS WITH SEDIMENT TRAPS, REMOVAL OF SILT SHALL OCCUR WHEN THE ACCUMULATION EXCEEDS FOUR (4) INCHES IN THE BASINS, AND THE SEDIMENT TRAPS SHALL BE CLEANED WHEN FULL.

- 2. ACCUMULATED PAPER, TRASH AND DEBRIS SHOULD BE REMOVED EVERY SIX (6) MONTHS OR AS NECESSARY.
- 3. VEGETATION WITHIN THE BASIN SHOULD NOT BE ALLOWED TO EXCEED EIGHTEEN (18) INCHES IN HEIGHT AT ANY TIME, EXCEPT FOR THOSE PROVIDED IN THE DESIGN.
- 4. THE BASIN SHOULD BE INSPECTED ANNUALLY AND REPAIRS SHOULD BE MADE IF NECESSARY.
- 5. CORRECTIVE MAINTENANCE IS REQUIRED ANY TIME A SEDIMENTATION BASIN DOES NOT DRAIN THE EQUIVALENT OF THE WATER QUALITY VOLUME WITHIN SIXTY (60) HOURS (I.E. NO STANDING WATER IS ALLOWED).

## FILTRATION BASIN MAINTENENCE NOTES:

- REMOVED EVERY SIX (6) MONTHS OR AS NECESSARY.
- 2. VEGETATION WITHIN THE BASIN SHOULD NOT BE ALLOWED TO EXCEED EIGHTEEN (18) INCHES IN
- 3. CORRECTIVE MAINTENANCE IS REQUIRED ANY TIME DRAW-DOWN DOES NOT OCCUR WITHIN THIRTY-SIX (36) HOURS AFTER THE SEDIMENTATION BASIN HAS
- 4. THE BASIN SHOULD BE INSPECTED ANNUALLY AND

## ACCUMULATED PAPER, TRASH AND DEBRIS SHOULD BE

## HEIGHT AT ANY TIME.

## GEORGE B. HARRINGT 114304

3 Nov 2020

REPAIRS SHOULD BE MADE AS NECESSARY.

# EAND

SHEET

28 OF 51

0.02-0.04 INCH DIAMETER

GEOMEMBRANE ,

PERFORATED 6"

SHD 40 PVC PIPE -

PROPERTY

(PIPING SHALL BE MIN. 6 INCH

DIAMETER, SCH 40 PVC WITH 3/8 INCH

FEET. MINIMUM SLOPE TO BE 1.0%)

PERFORATIONS, SPACED AT A MAX. OF 10

LINER

MATERIAL

UNIT WEIGHT

FILTRATION RATE

PUNCTURE STRENGTH

TENSILE STRENGTH

WATER FLOW RATE

EQUIV. OPENING SIZE

[PER ECM 1.6.5(A)(4)]

MULLEN BURST STRENGTH

SOURCE: CITY OF AUSTIN

ASTM C-33 CONCRETE SAND (TOP OF BED TO BE HORIZONTAL) -

GEOTEXTILE:

10' O.C. AND

TEST METHOD

NONWOVEN GEOTEXTILE FABRIC

ASTM D-751 (MODIFIED)

ASTM D-751

ASTM D-1682

ASTM D-4491

SAND BED WITH TRENCH DESIGN NOTES AND SPECIFICATIONS

2: HIGH FLOW FILTER FABRIC REQUIREMENTS.

US STANDARD SIEVE

THE TOP LAYER SHALL BE TWELVE (12) TO EIGHTEEN (18) INCHES OF 0.02-0.04 INCH

DIAMETER SAND WHICH CORRESPONDS WITH ASTM C-33 CONCRETE SAND (SMALLER SAND

ONE-HALF (0.5) TO ONE AND ONE-HALF (1.5) INCH DIAMETER WASHED, ROUNDED RIVER

OF THE UNDERDRAIN LATERAL PIPES AND GEOTEXTILE FABRIC. THE GEOTEXTILE FABRIC IS NEEDED TO PREVENT THE FILTER MEDIA FROM INFILTRATING INTO THE LATERAL PIPING. THE

GEOTEXTILE FABRIC SPECIFICATIONS ARE SHOWN IN STANDARD SPECIFICATION 620S, TABLE

NOTE: ONLY THE GEOTEXTILE FABRIC SEPARATING SAND AND GRAVEL SHALL BE HIGH FLOW AND FOLLOW SPECS IN THE TABLE ABOVE. GEOTEXTILE FABRIC FOR LINER

PROTECTION SHALL FOLLOW SPECS ON GEOMEMBRANE LINER DETAILS SHEET.

SIZE IS NOT ACCEPTABLE). LATERALS SHALL BE PLACED IN TRENCHES WITH A COVERING OF

GRAVEL WHICH PROVIDES THREE (3) INCHES TO FIVE (5) INCHES OF COVER OVER THE TOP

<5' FROM EDGE GEOTEXTILE FABRIC

OZ/SQ.YD.

IN/SEC

LB.

PSI

LB.

NO.


GPM/SQ.FT.

SAND BED PROFILE (WITH GRAVEL FILTER)

HIGH FLOW GEOTEXTILE FABRIC SPECIFICATIONS

N.T.S.

20-TOD-SD-020 20-FDP-007



1.0 GENERAL NOTES

a. GEOMEMBRANE LINER IS REQUIRED FOR BOTH SEDIMENTATION AND FILTRATION BASIN.

b. WHERE A GEOMEMBRANE LINER IS USED IS SHALL HAVE A MINIMUM THICKNESS OF THIRTY (30) MILS. IT SHALL ALSO HAVE A 3"-4" FUSION WELD AT ALL SEAMS WITHIN THE LINER. ALL WELDS ARE TO BE TESTED FOR ONE MINUTE. IF TEST FAILS, RE-WELD SEAM AND TEST AGAIN.

c. CONCRETE WALL OF THE WATER QUALITY POND SHALL BE CONSTRUCTED WITH WATER TIGHT

d. GEOMEMBRANE LINER TO BE PLACED UP TO A MINIMUM HEIGHT EQUAL TO THE WATER QUALITY

e. THE CONNECTION OF THE GEOMEMBRANE LINER TO THE PVC PIPE WILL BE PER THE

GEOMEMBRANE MANUFACTURER'S STANDARD DESIGN OR RECOMENDATION.

JOINTS. SEE STRUCTURAL PLANS FOR REINFORCING, JOINTS, AND OTHER DETAILS.

2.0 MATERIAL AND INSTALLATION

a. THE GEOMEMBRANE LINER SHALL CONSIST OF EPDM MEETING THE MATERIAL AND MANUFACTURER'S APPLICATIONS AND REQUIREMENTS. THE LINER SHALL HAVE A MINIMUM OF THRITY (30) MILS AND BE ULTRAVIOLET RESISTANT.

b. THE GEOMEMBRANE SHALL BE UNDERLAIN AND OVERLAIN BY A LAYER OF GEOTEXTILE FABRIC TO PROTECT THE LINER FROM PUNCTURE DUE TO ROCKS OR OTHER SUBSTANCES WITHIN THE SOILS. REFERENCE TABLE THIS SHEET FOR PROPERTIES GEOTEXTILE FABRIC TO HAVE.

3.0 PLACEMENT

a. PRIOR TO FABRIC AND LINER PLACEMENT, THE SUBGRADE SHALL BE EXCAVATED AND REMOVED TO THE ELEVATION ESTABLISHED ON THE PLANS. LOOSE SOIL/ROCKS SHALL BE REMOVED FROM THE EXCAVATIONS. IF SOIL, THE SUBGRADE SHALL BE SCARIFIED TO A DEPTH OF SIX (6) INCHES, MOISTURE CONDITIONED, AND RECOMPACTED. IF THE POND IS OVER EXCAVATED, THE OVER EXCAVATED AREAS MAY BE FILLED IN WITH ON-SITE SOILS, COMPACTED SIMILARLY TO THE SUBGRADE SOILS UP TO THE BOTTOM ELEVATION OF THE LINER. IF LIMESTONE, THE SURFACE SHALL REASONABLY CLEANED OF LARGE ROCKS AND OTHER LOOSE MATERIAL. IN LIMESTONE SUBGRADE AREAS, A THIN LAYER (± 1"-2" THICK) OF LEVELING SAND (NO PARTICLES LARGER THAN 3/8") SHALL BE PLACED TO PROTECT THE FABRIC AND LINER FROM PUNCTURE. NO SHARP ROCKS OR OTHER SIMILAR SUBSTANCES SHALL BE PRESENT WITHIN THE TOP ONE (1) INCH OF THE SUBGRADE TO BE COVERED BY LINER.

b. GROUNDWATER CONTROL DURING EXCAVATION AND CONSTRUCTION OF THE LINER IS THE RESPONSIBILITY OF THE CONTRACTOR. GROUNDWATER CONTROL MUST BE PROVIDED SUCH THAT IT RESULTS IN A STABLE AND DRY SUBGRADE THAT IS CONDUCTIVE TO PROPER LINER PLACEMENT. APPROPRIATE MEASURES SUCH AS PERIMETER AND/OR LATERAL INTERCEPTOR TRENCHES, SUMPS, AND PUMPS SHALL BE INSTALLED AND MAINTAINED THROUGHOUT CONSTRUCTION AS NEEDED.

c. THE GEOTEXTILE FABRIC SHALL BE PLACED AT THE TOP OF THE SUBGRADE (BELOW THE LINER) IN ACCORDANCE WITH ALL MANUFACTURER'S SPECIFICATIONS AND REQUIREMENTS.

d. THE GEOMEMBRANE LINER SHALL BE PLACED IN ACCORDANCE WITH ALL MANUFACTURER'S SPECIFICATIONS AND REQUIREMENTS. ALL SEAMS SHALL BE OVERLAPPED AT LEAST FOUR (4) INCHES, PREPARED AND SEALED IN ACCORDANCE WITH MANUFACTURER'S INSTALLATION GUIDELINES. ALL AREAS TO BE SEAMED SHALL BE CLEANED AND FREE OF MOISTURE, DUST, DIRT, AND OTHER FOREIGN MATERIAL.

e. THE GEOMENBRANE LINER SHALL EXTEND AT LEAST SIX (6) INCHES ABOVE THE DESIGN WATER QUALITY ELEVATION.

f. THE GEOMEMBRANE LINER SHALL EXTEND BELOW AND AROUND ALL CONCRETE RAMPS, INFOW/OUTFLOW HEADWALL STRUCTURES, APRONS, WALLS, AND OTHER STRUCTURES WITHIN THE POND INTERIOR. THE GEOMEMBRANE SHALL BE ATTACHED TO SUCH PROTRUSION/STRUCTURES AS OUTLINED IN MANUFACTURER'S INSTALLATION GUIDELINES AND THE ATTACHED DETAILS.

3.1 COMPACTION

a. COMPACT THE SUBGRADE WITH PROPERLY BALLASTED PENETRATING PAD-FOOT COMPACTORS. A MINIMUM OF TWO (2) PASSES SHALL BE REQUIRED REGARDLESS OF WHETHER THE SUBGRADE MEETS DENSITY SPECIFICATIONS. A PASS IS DEFINED AS ONE (1) TRIP ACROSS THE SUBGRADE AND BACK TO THE STARTING POINT BY A SINGLE ROLLER OR ONE (1) TRIP FROM ONE SIDE TO THE OTHER IF THE COMPACTING EQUIPMENT HAS FRONT AND BACK COMPACTING ROLLERS. THIS REQUIREMENT IS TO ALLOW THOUGHROUGH REMOLDING OF SOILS THROUGH KNEADING ACTION. THE SURFACE SHALL BE COMPACTED WITH A SMOOTH-WHEELED VIBRATORY ROLLER TO PROVIDE A SMOOTH FINISH TO THE

b. THE SUBGRADE, IF SOIL, SHALL BE COMPACTED TO AT LEAST 95 PERCENT OF THE MAXIMUM DRY DENSITY DETERMINED BY THE STANDARD PROCTOR TEST, ASTM D 698. IF THE MATERIAL CLASSIFIES AS A (CH) IN ACCORDANCE WITH USCS, THE MOISTURE CONTENT AT THE TIME OF COMPACTION SHALL BE BETWEEN OPTIMUM AND +4 PERCENTAGE POINTS ABOVE OPTIMUM MOISTURE CONTENT. FOR ALL OTHER SOIL MATERIAL, THE MOISTURE CONTENT AT THE TIME OF COMPACTION SHALL BE BETWEEN 3 AND +3 PERCENTAGE POINTS ABOVE THE OPTIMUM MOISTURE CONTENT. MOISTURE/DENSITY CONTROL IS NOT NECESSARY IN EXPOSED LIMESTONE SUBGRADE AREAS.

3.3 QUALITY CONTROL

a. THE INSTALLER AND CONSTRUCTION TESTING FIRM SHALL DOCUMENT ALL GEOMEMBRANE AND FABRIC MATERIALS AND INSTALLATION, INCLUDING AND REPAIRS/PATCHES.

b. ALL NON-DESTRUCTIVE AIR-LANCE TESTING SHALL BE PERFORMED BY INSTALLER AT SEAMS. THE AIR-LANCE TESTING SHALL BE MONITORED AND DOCUMENTED BY THE CONSTRUCTION TESTING FIRM.

c. THE AS-BUILT THICKNESS OF THE PROTECTIVE SOIL COVER SHALL BE DETERMINED BY SURVEY METHODS DETERMINED BY A PROFESSIONAL SURVEYING FIRM, AS REQUIRED IN THE CITY OF AUSTIN ENVIRONMENTAL CRITERIA MANUAL (ECM) SECTION 1.6.2.C.1. PRIOR TO THE PLACEMENT OF ANY SOIL COVER, THE GEOMEMBRANE/FABRIC SURFACE SHALL BE SURVEYED IN A SUFFICIENT MANNER TO ESTABLISH AN ADEQUATE NUMBER OF DATA POINTS ON THE POND BOTTOM AND SIDE SLOPES. UPON COMPLETION OF THE SOIL COVER INSTALLATION, AND PRIOR TO THE INSTALLATION OF SUBSEQUENT ELEMENTS SUCH AS PLANTS, WALLS, RAMPS, ETC., THE TOP OF THE PROTECTIVE SOIL SHALL BE SURVEYED AT THE SAME DATA POINT LOCATIONS TO ENSURE THE SPECIFIED SOIL COVER HAS BEEN ACHIEVED AND THE TOP OF THE SOIL COVER IS AT THE CIVIL ENGINEERS'S SPECIFIED GRADES AND SLOPES, WITHIN A TOLERANCE OF 0 TO +0.2 FEET. AREAS THAT DO NOT MEET THE SPECIFIED THICKNESS GRADES AND SLOPES, SHALL BE CORRECTED AND RE-SURVEYED. THE SURVEYOR SHALL USE EXTREME CAUTION TO NOT DAMAGE THE GEOMEMBRANE LINER WHEN SURVEYING FOR THE PROTECTIVE SOIL COVER.

d. THE SELECTION OF THE DATA POINT LOCATIONS AND THE SUBSEQUENT SURVEYS SHALL BE PERFORMED BY A REGISTERED PROFESSIONAL LICENSED SURVEYOR (RPLS) REGISTERED IN THE STATE OF TEXAS. AT THE END OF POND CONSTRUCTION, THE RPLS SHALL PREPARE AND SEAL A LETTER DOCUMENTING THE SURVEYING SERVICES AND THICKNESS OF THE PROTECTIVE SOIL COVER AS INDICATED IN 6.1(C). THIS LETTER SHALL INCLUDE A DRAWING INDICATING SURVEYING POINT LOCATIONS AND THE ELEVATIONS AT EACH POINT PRIOR TO AND AFTER SOIL COVER PLACEMENT.

3.4 PROTECTION

a. AFTER COMPLETION OF GEOMEMBRANE/GEOTEXTILE FABRIC PLACEMENT, A PROTECTIVE SOIL COVER WITH A MINIMUM THICKNESS OF TWENTY—FOUR (24) INCHES SHALL BE PLACED OVER ALL PORTIONS OF THE LINER SYSTEM TO REDUCE POSSIBLE DAMAGE TO THE LINER FROM CONSTRUCTION ACTIVITIES AND FUTURE MAINTENANCE OPERATIONS, NO CONSTRUCTION OR MAINTENANCE VEHICLES SHALL BE ALLOWED ON/ABOVE THE GEOMEMBRANE LINED AREAS. THIS PROTECTIVE SOIL COVER DOES NOT REQUIRE FIELD AND LABORATORY TESTING; HOWEVER, IT DOES REQUIRE A THICKNESS SURVEY AS DISCUSSED IN 3.3(D). THE PROTECTIVE SOIL COVER SHALL NOT INCLUDE ANY ROCKS LARGER THAN 3/8" IN SIZE. THIS PROTECTIVE SOIL MAT INCLUDE ANY SAND FILTRATION BEDDING AND ANY TOPSOIL USED FOR PLANTINGS. COMPACTION EQUIPMENT SHALL NOT BE USED FOR THE PROTECTIVE SOIL COVER. A PROTECTIVE SOIL COVER IS NOT REQUIRED IN AREAS WHERE A GEOMEMBRANE LINER IS ATTACHED DIRECTLY TO A VERTICAL CONCRETE WALL.

b. NO CONSTRUCTION EQUIPMENT, MAINTENANCE VEHICLES, OR ANY SHARP OBJECTS SHALL BE PLACED ON/OVER THE GEOMEMBRANE LINER AND ITS PROTECTIVE SOIL COVER.

4.1 LINER PERFORATIONS

a. FOR AREAS OF THE GEOMEMBRANE THAT BECOME PUNCTURED, PERFORATED, OR TORN DURING CONSTRUCTION (INCLUDING THOSE AREAS SUBJECTED TO DESTRUCTIVE TESTING), THE AREA SHALL BE REPAIRED AS SPECIFIED BY THE MANUFACTURER IN THE ATTACHED MANUFACTURER'S REPAIR SPECIFICATIONS. THE REPAIR PROCEDURES MAY INCLUDE PATCHING, BUFFING/RE-WELDING, SPOT WELDING/SEAMING, CAPPING, AND/OR TOPPING.

b. PRIOR TO AND DURING REPAIRS, ALL SURFACES SHALL BE CLEAN AND DRY.

c. PATCHES OR CAPS SHALL EXTEND BEYOND THE EDGES OF THE REPAIR.

d. ALL CORNERS OF THE REPAIR SHALL BE ROUNDED.

e. AL REPAIRS SHALL BE MONITORED AND/OR VERIFIED BY THE MANUFACTURE'S REPRESENTATIVE

5.1 SAMPLING AND TESTING

a. FOR SUBGRADE MATERIALS, AT LEAST ONE (1) SAMPLE SHALL BE OBTAINED WITHIN THE EXPOSED SUBGRADE AREAS FOR TESTING OF ATTERBERG LIMITS (ASTM D 4318), GRADATION (ASTM D 422), AND MOSITURE—DENSITY RELATIONSHIP (ASTM D 698). THESE SAMPLES SHALL BE EXCAVATED FROM EXPOSED AREAS IN THE FIELD IN SUFFICIENT QUANTITIES TO PERFORM THE THREE LABORATORY TESTS ITEMIZED ABOVE, PALCED IN SAMPLE CONTAINERS, AND TRANSPORTED TO THE LABORATORY FOR TESTING. THE EXCAVATED SAMPLE AREAS IN THE FIELD SHALL BE BACKFILLED WITH SIMILAR SUBGRADE MATERIAL OR CLAY LINER MATERIAL, MOISTURE, AND COMPACTED.

b. ADDITIONAL SAMPLES SHALL BE OBTAINED AS VARIATIONS IN MATERIAL ARE OBSERVED.

c. IN-PLACE DENSITY AND MOISTURE CONTENT BY NUCLEAR METHODS (ASTM D 2922 AND D 3017) SHALL BE PERFORMED ON ALL SUBGRADE MATERIAL AT A MINIMUM RATE OF ONE (1) TEST PER 5,000 SQUARE-FEET PER LIFT (OR A MINIMUM OF THREE (3) TESTS PER LIFT).

d. AREAS THAT DO NOT MEET MOISTURE OR DENSITY SPECIFICATIONS DURING INITIAL TESTING SHALL BE REWORKED AND RETESTED UNTIL THE MATERIAL MEETS AFOREMENTIONED SPECIFICATIONS.


a. AS MANDATED BY THE CITY OF AUSTIN REQUIREMENTS, THE CONSTRUCTION TESTING FIRM SHALL BE NOTIFIED BY THE GENERAL CONTRACTOR TO BE ON—SITE ON A FULL—TIME BASIS DURING THE POND CONSTRUCTION. THE CONSTRUCTION TESTING FIRM SHALL ISSUE DAILY CONSTRUCTION REPORTS INDICATING THE WORK PERFORMED BY THE CONTRACTOR, THE TYPE OF EQUIPMENT UTILIZED TO PERFORM STATED WORK, THE DUTIES PERFORMED BY THE CONSTRUCTION TESTING FIRM REPRESENTATIVE (FIELD TECHNICIAN), A SUMMARY OF TEST RESULTS (MAY REFERENCE A SEPARATE REPORT), ANY NON—CONFORMING TEST RESULTS OR AREAS IN NEED OF CORRECTIVE ACTION (MAY REFERENCE A SEPARATE REPORT), THE TECHNICIANS NAME, DATE OF REPORT AND, REVIEWER'S SIGNATURE.


b. AFTER LINER CONSTRUCTION IS COMPLETE, A GEOMEMBRANE LINER EVALUATION REPORT (GLER) SHALL BE PREPARED AND SEALED BY CONSTRUCTION TESTING FIRM'S PROFESSIONAL ENGINEER LINCENSED IN THE STATE OF TEXAS. THE GLER LETTER SHALL SUMMARIZE THE TYPES OF TESTS PERFORMED AND WHETHER THE RESULTS WERE IN GENERAL CONFORMANCE WITH THE PROJECT PLANS AND SPECIFICATIONS. AT A MINIMUM, THIS LETTER SHALL DESCRIBE THE SUBGRADE PREPARATION, LINER PLACEMENT, MOISTURE/DENSITY CONTROL, TEST FREQUENCIES AND RESULTS, AND APPROPRIATE TEST LOCATIONS. THIS REPORT SHALL REFER TO OR INCLUDE ATTACHMENTS OF PREVIOUS TESTING REPORTS ISSUED FOR THE LINER.


c. AS IN ITEM 3.3(D), AFTER POND CONSTRUCTION IS COMPLETE, THE RPLS LICENSED IN THE STATE OF TEXAS SHALL PREPARE AND SEAL A LETTER DOCUMENTING THE SURVEYING SERVICES AND THE THICKNESS OF THE GEOMEMBRANE LINER AND PROTECTIVE SOIL COVER. THIS LETTER SHALL INCLUDE A DRAWING INDICATING SURVEY POINT LOCATIONS AND THE ELEVATIONS AT EACH POINT PRIOR TO AND AFTER LINER/COVER PLACEMENT.

d. ANY REQUESTS FOR INFORMATION OR CHANGES TO DESIGN ND/OR CONSTRUCTION ITEMS SHALL BE PREPARED BY THE POND INSTALLATION CONTRACTOR IN THE FORM OF A REQUEST FOR INFORMATION (RFI) AND ISSUED TO THE GENERAL CONTRACTOR, WITH COPIES TO THE DEVELOPER, THE GEOMEMBRANE MANUFACTURER'S AUTHORIZED REPRESENTATIVE, THE CIVIL ENGINEER, THE GEOTECHNICAL ENGINEER, THE CONSTRUCTION TESTING FIRM, AND THE CITY OF AUSTIN.


	GEOTEXTILE FABRIC SPEC	IFICATIONS	
PROPERTY	TEST METHOD	UNIT	SPECIFICATION
MATERIAL	NONWOVEN GEOTEXTILE FABRIC		
UNIT WEIGHT		OZ/SQ.YD.	8
FILTRATION RATE		IN/SEC	0.08 (MIN.)
PUNCTURE STRENGTH	ASTM D-751 (MODIFIED)	LB.	125 (MIN.)
MULLEN BURST STRENGTH	ASTM D-751	PSI	400 (MIN.)
TENSILE STRENGTH	ASTM D-1682	LB.	200 (MIN.)
EQUIV. OPENING SIZE	US STANDARD SIEVE	NO.	80 (MIN.)
SOURCE: CITY OF AUSTIN			











ON COUNTY, TEXAS 78641

E DEVELOPMENT PLANS ALTA LEANDI 348 MAIN STREET LEANDER, WILIAMSON COUNTY, TEXAS

SHEET

29 OF 51

29 OF 51 20-TOD-SD-020

20-FDP-007

F D C B

1 2 X" SUBMERSIBLE PUMP 2 2 X" BASE ELBOWS 3 2 XX' SS STEEL CHAINS
4 1 DUPLEX CONTROL PANEL NEMA 4X (MOUNTED & WIRED BY CONTRACTOR) ACTION 5 4 FLOAT SWITCH
6 1 SS CABLE BRACKET
7 1 XX" DIA x X'-X" DEEP CONCRETE WET WELL
8 1 X" THK FLAT CONCRETE TOP LEAD PUMP TURNS "ON", FS-2 LEAD PUMP "ON"

LAG PUMP TURNS "ON", FS-3 LEAD & LAG PUMPS "ON" HIGH WATER "ALARM" LEVEL, FS-4 HIGH LEVEL ALARM "ON"
HIGH WATER IN DITCH, FS-5 ALL PUMPS "OFF" FALLING LEVEL CYCLE

XXXXX\* HIGH WATER ALARM, FS-4 HIGH LEVEL ALARM "OFF"

XXXXX\* DITCH FLOAT HIGH WATER, FS-5 ALL PUMPS "ON"

XXXXX\* PUMPS "OFF" LEVEL, FS-1 ALL PUMPS "OFF" LAG PUMP

SWITCHES TO LEAD PUMP 13 2 X\* DI 90' ELBOW FL x MJ w/ STAR GR
14 2 SS UPPER GUIDE BRACKETS
15 2 X\* HDL BALL CHECK VALVE
16 2 X\* DIRECT BURY GATE VALVES
17 2 X\* CAST IRON VALVE BOX
18 4 SS GUIDE RAILS
19 2 3\* CONDUIT
20 - REBAR AS REQ'D
21 2 LIFT-OUT ASSEMBLY
22 2 X\* DUCTILE IRON ELBOW (BY OTHERS) 23 1 X" DUCTILE IRON TEE (BY OTHERS)
24 2 24" SQ CONCRETE PAD (BY OTHERS) 25 2 RESILIENT RUBBER BOOT 2 RESILIENT RUBBER BOOT

ALL JOINTS MADE WATER-TIGHT w/ PLASTIC FLEXIBLE GASKET (RAM-NEK)

NAMEPLATE INDICATING:
MFG: PARKUSA

888-611-PARK
WWW.PARK-USA.COM
MODEL: WWXX-NCDX-XXX-XXX-XXX
DATE MANUFACTURED

28 1 REMOTE MOUNT DITCH FLOAT
STORM INLETT PIPING SEAL w/ NON-SHF PUMP Trooper Included SAMOON PLAN VIEW 1 STORM INLET PIPING SEAL W/ NON-SHRINK GROUT (BY OTHERS) NOTE: ALL DASHED PIPING TO BE FURNISHED BY CONTRACTOR NOTE: VERIFY ALL ELEVATIONS PRIOR TO FABRICATION NOTE: VERIFY ALL INLET/OUTLET ORIENTATIONS PRIOR TO MODEL NUMBER: Specifications HIGH WATER "ALARM" LEVEL
"FS-4"
EL= XX.XX' POWER CHARACTERISTICS

43 - 460V/3PH/60Hz
23 - 230V/3PH/60Hz
21 - 230V/1PH/60Hz
PUMP MOTOR SIZE

050 - 5.0 HP
075 - 7.5 HP
100 - 10.0 HP
150 - 15.0 HP
200 - 20.0 HP CONCRETE: PUMP CONFIGURATION
S - SIMPLEX
D - DUPLEX
PUMP DISCHARGE SIZE
3 - 3"
4 - 4"
6 - 6"
8 - 8" Class I/II concrete with design strength of 4500 PSI at 28 days. Unit is of monolithic construction at floor, first stage of wall and baffle with sectional riser to required depth. REINFORCEMENT: Grade 60 reinforced with steel rebar conforming to ASTM A615 on required centers or equal. PUMP HEAD CAPACITY (TDH)

10 - 10' TOTAL DYNAMIC HEAD

20 - 20' TOTAL DYNAMIC HEAD

ETC... ALUMINUM HATCH:

300 PSF rated, 1/4" aluminum skid-resistant floor plate, stainless steel tamperproof bolting & hinges & slamlock. VERIFY INLET ELEVATION FLOW RATE CAPACITY (GPM)
100 - 100 GPM
200 - 200 GPM
ETC...

PROJECT: X FLOW> X" INLET FL EL= XX.XX' @ParkUSA. ALL RIGHTS RESERVED. Pumps shall be centrifugal solids handling type with submersible type motor. Pumps shall have a capacity as follows: CUSTOMER: X LAG PUMP "ON" LEVEL, "FS-3" CEL= XX.XX' 
 PUMP No.
 TYPE
 GPM
 TDH
 RPM
 HP
 ELECTRICAL V
 PH
 Hz

 P-1
 NON CLOG
 X
 X
 X
 X
 X
 X
 X

 P-2
 NON CLOG
 X
 X
 X
 X
 X
 X
 X
 ENGINEER: X ORDER #: X LEAD PUMP "ON" LEVEL

"FS-2"
EL= XX.XX." PROJ #: X DATE: X CONTROLS: Pump controls shall be mounted inside a UL Listed NEMA-4X enclosure and include circuit breakers, alarm circuit fuse, IEC rated motor starter, pump HOA, and alternator relay. Panel shall have a visual alarm beacon. Panel is designed for remote mounting. 888.611.PARK www.park-usa.com PUMP "OFF" LEVEL, "FS-1" \_ EL= XX.XX' PARK Engineering Data
Field excavation and preparation shall be completed prior to delivery of assembly. Use dimensional data as shown. All pipe, valves and fittings of the assembly are approved by one of the following associations: STORM SEWER LIFT STATION SUBMERSIBLE NON-CLOG PUMP STATION **ELEVATION** WWXX-NCDX-XX

> NOTE: EXACT PUMP MODEL TO BE PROVIDED BY MANUFACTURER. SUBMITTAL SHALL BE COORDINATED WITH CIVIL ENGINEER FOR APPROVAL PRIOR TO ANY INSTALLATION.

3 Nov 2020 GEORGE B. HARRINGTO

LEANDER DEVELOPMENT PLANS ALTA 348 MAIN STREET LEANDER, WILIAMSON COUNTY


SPECIFICATIONS


POND

SHEET CG503

30 OF 51

20-TOD-SD-020 20-FDP-007





3 Nov 2020 GEORGE B. HARRINGTO 114304

WGInc.com


DE

LEANDI EVELOPMENT I

C502

38 OF 51

20-TOD-SD-020 20-FDP-007



C503 39 OF 51

3 Nov 2020

**DETAIL** 

CONSTRUCTION

GEORGE B. HARRINGT

LEANDER


EVELOPMENT


114304

20-TOD-SD-020

SHEET

20-FDP-007





## **Contributing Zone Plan Application**

## **Texas Commission on Environmental Quality**

for Regulated Activities on the Contributing Zone to the Edwards Aquifer and Relating to 30 TAC §213.24(1), Effective June 1, 1999

To ensure that the application is administratively complete, confirm that all fields in the form are complete, verify that all requested information is provided, consistently reference the same site and contact person in all forms in the application, and ensure forms are signed by the appropriate party.

Note: Including all the information requested in the form and attachments contributes to more streamlined technical reviews.

## Signature

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. This **Contributing Zone Plan Application** is hereby submitted for TCEQ review and Executive Director approval. The application was prepared by:

Print Name of Customer/Agent: Anthony Goode, PE

Date: <u>6/1/2</u>023

Signature of Customer/Agent:

Regulated Entity Name: \_\_\_\_\_

## **Project Information**

1. County: Williamson

2. Stream Basin: Brushy Creek

3. Groundwater Conservation District (if applicable): NA

4. Customer (Applicant):

Contact Person: Jeff Musgrove

Entity: Transit Village Investments LTD

Mailing Address: 2215 Westlake Drive Ste 300

Email Address: jmusgrove@americanrealty.com

5.	Agent/Representative (If any):	
	Contact Person: Anthony Goode Entity: Goode Faith Engineering Mailing Address: 1620 La Jaita Dr Ste 300 City, State: Cedar Park, TX Telephone: 972-822-1682 Email Address: Anthony@goodefaitheng.com	Zip: <u>78613</u> Fax:
6.	Project Location:	
	<ul> <li>X The project site is located inside the city limits</li> <li>The project site is located outside the city limit jurisdiction) of</li> <li>The project site is not located within any city's</li> </ul>	ts but inside the ETJ (extra-territorial
7.	X The location of the project site is described be provided so that the TCEQ's Regional staff car boundaries for a field investigation.  1621 Hero Way Leander, TX 78641	
8.	X Attachment A - Road Map. A road map show project site is attached. The map clearly show	_
9.	X Attachment B - USGS Quadrangle Map. A cop Quadrangle Map (Scale: 1" = 2000') is attache	•
	<ul><li>X Project site boundaries.</li><li>X USGS Quadrangle Name(s).</li></ul>	
10.	Attachment C - Project Narrative. A detailed project is attached. The project description is contains, at a minimum, the following details:	• • • •
	<ul> <li>X Area of the site</li> <li>X Offsite areas</li> <li>X Impervious cover</li> <li>X Permanent BMP(s)</li> <li>X Proposed site use</li> <li>X Site history</li> <li>X Previous development</li> <li>X Area(s) to be demolished</li> </ul>	
11.	Existing project site conditions are noted below:	
	<ul> <li>Existing commercial site</li> <li>Existing industrial site</li> <li>Existing residential site</li> </ul>	

	<ul> <li>Existing paved and/or unpaved roads</li> <li>Undeveloped (Cleared)</li> <li>Undeveloped (Undisturbed/Not cleared)</li> <li>Other:</li> </ul>
12.	The type of project is:
	Residential: # of Lots: Residential: # of Living Unit Equivalents: X Commercial Industrial Other:
13.	Total project area (size of site): 2.23 Acres
	Total disturbed area: 1.97 Acres
14.	Estimated projected population: NA
15.	The amount and type of impervious cover expected after construction is complete is shown below:

Table 1 - Impervious Cover

Impervious Cover of Proposed Project	Sq. Ft.	Sq. Ft./Acre	Acres
Structures/Rooftops	13423	÷ 43,560 =	0.31
Parking	11683	÷ 43,560 =	0.27
Other paved surfaces	55044	÷ 43,560 =	1.26
Total Impervious Cover	80150	÷ 43,560 =	1.84

Total Impervious Cover  $1.84 \div$  Total Acreage  $2.23 \times 100 = 82.5 \%$  Impervious Cover

16. 🛛	Attachment D - Factors Affecting Surface Water Quality. A detailed description of all
	factors that could affect surface water quality is attached. If applicable, this includes the
	location and description of any discharge associated with industrial activity other than
	construction.

17. Only inert materials as defined by 30 TAC 330.2 will be used as fill material.

## For Road Projects Only

Complete questions 18 - 23 if this application is exclusively for a road project.

X N/A

18. Type of project:
<ul> <li>TXDOT road project.</li> <li>County road or roads built to county specifications.</li> <li>City thoroughfare or roads to be dedicated to a municipality.</li> <li>Street or road providing access to private driveways.</li> </ul>
19. Type of pavement or road surface to be used:
<ul><li>Concrete</li><li>Asphaltic concrete pavement</li><li>Other:</li></ul>
20. Right of Way (R.O.W.):
Length of R.O.W.: feet. Width of R.O.W.: feet. $L \times W = $ $Ft^2 \div 43,560 Ft^2/Acre = acres.$
21. Pavement Area:
Length of pavement area: feet.  Width of pavement area: feet.  L x W = Ft² ÷ 43,560 Ft²/Acre = acres.  Pavement area acres ÷ R.O.W. area acres x 100 = % impervious cover.
22. A rest stop will be included in this project.
A rest stop will not be included in this project.
23. Maintenance and repair of existing roadways that do not require approval from the TCEQ Executive Director. Modifications to existing roadways such as widening roads/adding shoulders totaling more than one-half (1/2) the width of one (1) existing lane require prior approval from the TCEQ.
Stormwater to be generated by the Proposed Project
24. X Attachment E - Volume and Character of Stormwater. A detailed description of the volume (quantity) and character (quality) of the stormwater runoff which is expected to occur from the proposed project is attached. The estimates of stormwater runoff quality and quantity are based on area and type of impervious cover. Include the runof coefficient of the site for both pre-construction and post-construction conditions.
Wastewater to be generated by the Proposed Project
25. Wastewater is to be discharged in the contributing zone. Requirements under 30 TAC §213.6(c) relating to Wastewater Treatment and Disposal Systems have been satisfied.  X N/A

		To	 otal x 1.5 = Gallon
5			
4			
3			
2			
AST Number	Size (Gallons)	Substance to be Stored	Tank Material
Table 2 - Tanks and	Substance Storage	Cubatanaa ta ba	
27. Tanks and substanc			
<u> </u>			
greater than or equal t ⊠N/A	.บ วบบ gailons.		
<b>Gallons</b> Complete questions 27	- 33 if this project includ		-
	oveground Sto	rago Tanks/AS	Tc) > 500
☐ Proposed.			
Existing.			
The sewage collecti	on System (Sewer Lines) on system will convey th Plant. The treatment fac	ne wastewater to the LE	ANDER WASTEWATER
size. The sy	his project/development stem will be designed by nd installed by a licensed	a licensed professional	engineer or registered
will be used licensing au the land is s the requirer	F - Suitability Letter fro to treat and dispose of t thority's (authorized age uitable for the use of pri ments for on-site sewage On-site Sewage Facilities.	the wastewater from thi int) written approval is a vate sewage facilities ar e facilities as specified ur	is site. The appropriate attached. It states that and will meet or exceed
On-Site Sewage	Facility (OSSF/Septic Tai	nk):	
26. Wastewater will be	disposed of by:		

5 of 11

•	stem, the containm umulative storage c		ed to capture one and	d one-half (1 1/2)
for providir		nment are proposed	ent Methods. Alternd. Specifications sho	
29. Inside dimensi	ons and capacity of	containment structu	ure(s):	
Table 3 - Second	dary Containment	t .		
Length (L)(Ft.)	Width(W)(Ft.)	Height (H)(Ft.)	L x W x H = (Ft3)	Gallons
			To	tal: Gallons
Some of the structure.  The piping The piping of the piping of the piping of the contain substance (structure).	e piping to dispense will be aboveground will be underground nment area must be s) being stored. The	ers or equipment wild d constructed of and e proposed containn	side the containment lextend outside the in a material impervenent structure will be ings. A scaled drawi	containment vious to the e constructed of:
	nt structure is attacl		-	
Interna Tanks cl Piping c	· -	=	wall and floor thickno collection of any spi	
storage tan			or collection and rec controlled drainage a	
<u></u>		pillage will be remo	ved from the contain	nment structure

45.	Permanent aboveground storage tank facilities.
	X Permanent aboveground storage tank facilities will not be located on this site.
46.	X Legal boundaries of the site are shown.
Pe	ermanent Best Management Practices (BMPs)
Pra	actices and measures that will be used during and after construction is completed.
47.	X Permanent BMPs and measures must be implemented to control the discharge of pollution from regulated activities after the completion of construction.
	□ N/A
48.	X These practices and measures have been designed, and will be constructed, operated, and maintained to insure that 80% of the incremental increase in the annual mass loading of total suspended solids (TSS) from the site caused by the regulated activity is removed. These quantities have been calculated in accordance with technical guidance prepared or accepted by the executive director.
	<ul> <li>X The TCEQ Technical Guidance Manual (TGM) was used to design permanent BMPs and measures for this site.</li> <li>X A technical guidance other than the TCEQ TGM was used to design permanent BMPs and measures for this site. The complete citation for the technical guidance that was used is: RG-348</li> </ul>
	□ N/A
49.	X Owners must insure that permanent BMPs and measures are constructed and function as designed. A Texas Licensed Professional Engineer must certify in writing that the permanent BMPs or measures were constructed as designed. The certification letter must be submitted to the appropriate regional office within 30 days of site completion.
	□ N/A
50.	Where a site is used for low density single-family residential development and has 20 % or less impervious cover, other permanent BMPs are not required. This exemption from permanent BMPs must be recorded in the county deed records, with a notice that if the percent impervious cover increases above 20% or land use changes, the exemption for the whole site as described in the property boundaries required by 30 TAC §213.4(g) (relating to Application Processing and Approval), may no longer apply and the property owner must notify the appropriate regional office of these changes.
	<ul> <li>The site will be used for low density single-family residential development and has 20% or less impervious cover.</li> <li>The site will be used for low density single-family residential development but has more than 20% impervious cover.</li> <li>X The site will not be used for low density single-family residential development.</li> </ul>

far im red ind the	e executive director may waive the requirement for other permanent BMPs for multi- mily residential developments, schools, or small business sites where 20% or less pervious cover is used at the site. This exemption from permanent BMPs must be corded in the county deed records, with a notice that if the percent impervious cover creases above 20% or land use changes, the exemption for the whole site as described in the property boundaries required by 30 TAC §213.4(g) (relating to Application Processing and Approval), may no longer apply and the property owner must notify the appropriate gional office of these changes.
	<ul> <li>Attachment I - 20% or Less Impervious Cover Waiver. The site will be used for multi-family residential developments, schools, or small business sites and has 20% or less impervious cover. A request to waive the requirements for other permanent BMPs and measures is attached.</li> <li>The site will be used for multi-family residential developments, schools, or small business sites but has more than 20% impervious cover.</li> </ul>
	x The site will not be used for multi-family residential developments, schools, or small business sites.
52. x	Attachment J - BMPs for Upgradient Stormwater.
	<ul> <li>A description of the BMPs and measures that will be used to prevent pollution of surface water, groundwater, or stormwater that originates upgradient from the site and flows across the site is attached.</li> <li>No surface water, groundwater or stormwater originates upgradient from the site and flows across the site, and an explanation is attached.</li> <li>Permanent BMPs or measures are not required to prevent pollution of surface water, groundwater, or stormwater that originates upgradient from the site and flows across the site, and an explanation is attached.</li> </ul>
53. X	Attachment K - BMPs for On-site Stormwater.
	<ul> <li>A description of the BMPs and measures that will be used to prevent pollution of surface water or groundwater that originates on-site or flows off the site, including pollution caused by contaminated stormwater runoff from the site is attached.</li> <li>Permanent BMPs or measures are not required to prevent pollution of surface wate or groundwater that originates on-site or flows off the site, including pollution caused by contaminated stormwater runoff, and an explanation is attached.</li> </ul>
54.	Attachment L - BMPs for Surface Streams. A description of the BMPs and measures that prevent pollutants from entering surface streams is attached.
X	N/A
55. x	Attachment M - Construction Plans. Construction plans and design calculations for the proposed permanent BMPs and measures have been prepared by or under the direct supervision of a Texas Licensed Professional Engineer, and are signed, sealed, and dated. Construction plans for the proposed permanent BMPs and measures are

	attached and include: Design calculations, TCEQ Construction Notes, all proposed structural plans and specifications, and appropriate details.
	N/A
56. X	<b>Attachment N - Inspection, Maintenance, Repair and Retrofit Plan</b> . A site and BMP specific plan for the inspection, maintenance, repair, and, if necessary, retrofit of the permanent BMPs and measures is attached. The plan fulfills all of the following:
	X Prepared and certified by the engineer designing the permanent BMPs and measures
	<ul> <li>X Signed by the owner or responsible party</li> <li>X Outlines specific procedures for documenting inspections, maintenance, repairs, and, if necessary, retrofit.</li> <li>X Contains a discussion of record keeping procedures</li> </ul>
	N/A
57.	<b>Attachment O - Pilot-Scale Field Testing Plan</b> . Pilot studies for BMPs that are not recognized by the Executive Director require prior approval from the TCEQ. A plan for pilot-scale field testing is attached.
Х	N/A
58.	Attachment P - Measures for Minimizing Surface Stream Contamination. A description of the measures that will be used to avoid or minimize surface stream contamination and changes in the way in which water enters a stream as a result of the construction and development is attached. The measures address increased stream flashing, the creation of stronger flows and in-stream velocities, and other in-stream effects caused by the regulated activity, which increase erosion that result in water quality degradation.
х	N/A
•	oonsibility for Maintenance of Permanent BMPs and sures after Construction is Complete.
59.	The applicant is responsible for maintaining the permanent BMPs after construction until such time as the maintenance obligation is either assumed in writing by another entity having ownership or control of the property (such as without limitation, an owner's association, a new property owner or lessee, a district, or municipality) or the ownership of the property is transferred to the entity. Such entity shall then be responsible for maintenance until another entity assumes such obligations in writing or ownership is transferred.
60.	A copy of the transfer of responsibility must be filed with the executive director at the appropriate regional office within 30 days of the transfer if the site is for use as a multiple single-family residential development, a multi-family residential development,


or a non-residential development such as commercial, industrial, institutional, schools, and other sites where regulated activities occur.


## Administrative Information

- 61. X Submit one (1) original and one (1) copy of the application, plus additional copies as needed for each affected incorporated city, groundwater conservation district, and county in which the project will be located. The TCEQ will distribute the additional copies to these jurisdictions.
- 62. X Any modification of this Contributing Zone Plan may require TCEQ review and Executive Director approval prior to construction, and may require submission of a revised application, with appropriate fees.
- 63. X The site description, controls, maintenance, and inspection requirements for the storm water pollution prevention plan (SWPPP) developed under the EPA NPDES general permits for stormwater discharges have been submitted to fulfill paragraphs 30 TAC §213.24(1-5) of the technical report. All requirements of 30 TAC §213.24(1-5) have been met by the SWPPP document.

	The Tem	porary S	Stormwater	Section	(TCEQ-0602	) is	included	with	the	appli	catior
--	---------	----------	------------	---------	------------	------	----------	------	-----	-------	--------

## Attachment A – Road Map





## Attachment B - USGS Quadrangle





## **Attachment C – Project Narrative**

The proposed project is a 2.23-acre commercial development located in the city of Leander, Texas in Williamson County. The project is located at the corner of Hero Way and Main Street. It is in the northwest section of the overall common development. Refer to **Attachment A** for the Location Map.

The project is located in the Brushy Creek watershed and the entire tract is located within the Edwards Aquifer Contributing Zone. It is located within the FEMA FIRM panel 48491C0455F dated 12/20/2019. The project is not in a water quality transition zone, over a karst aquifer, or within an area draining to a karst aquifer or reservoir.

The 2.23-acre site is undeveloped. There are no trees on the site. This lot is a part of the previously approved Alta Leander Station Project. There are no natural slopes in excess of 15% within or near the proposed limits of construction on site. The proposed site currently has a construction trailer and construction materials all of which will be removed prior to construction.

The proposed development consists of one building with approximately 13,400 SF for three small businesses. One of the businesses will be a coffee shop with a drive-thru. The project will also include associated drives, parking, and utilities.

The proposed site has a total of 1.84 acres of impervious cover. The drainage pattern for the 2.23-acre site has 0.23 acres flowing off-site and 2.00 acres contributes to the pond. The 2.00 acres flowing to the pond has 1.73 acres of impervious cover.

The development of the previously approved CZP included a Sedimentation/Infiltration Basin (TCEQ Tracking No. 25721739) which was designed for the entire development including this proposed project site.



## Attachment D - Factors Affecting Surface Water Quality

## **During Construction:**

There will be a slight increase in suspended solids during construction which will be mitigated utilizing BMPs including silt fencing, inlet protection, stabilized construction entrances and the proposed pond for temporary sediment basins. Potential sources of pollutants affecting surface water quality include:

- soil particle migration as a result of erosion from construction activity including the use of spoil piles, clearing and grubbing, excavation and burrow of existing grades, final grading, and installation of utilities and storm water infrastructure.
- soil particle migration resulting from pipe bedding material installation or staging and soil and/or road base placement and storage
- © Construction equipment and vehicle drippings or leaks containing petroleum such as fuel, grease, oil, and hydraulic fluid
- Concrete truck wash out activities
- Materials used during construction (paints, glues, chemicals, pavement striping/markings, gravel) may also affect the surface water quality
- Trash and debris from construction crews, equipment, and supplies can be another pollutant source and will be properly disposed of and effectively managed throughout construction to minimize any potential impact
- Sanitary waste from construction crews could also lead to a potential source of contamination. Propersanitation during construction, including temporary restroom facilities and trash barrels will not be provided.

## Post Construction:

Automobiles utilized by future tenants will generate some pollutants that can affect water quality. Leaks from engines and transmissions may add oil, grease or antifreeze and other automotive related liquids to the storm runoff.

Activities may include the utilization of chemical pesticides and lawn products that may affect the water quality. These products are typically labeled with instructions and warning labels about proper and safe usage by the customers. The owner will provide information through the leasing agreements about the proper use of products to the occupants and their effect on water quality.

Lack of lawn care maintenance can cause soil erosion and impact the quality of stream Water by increasing suspended solids. The owner is, therefore, managing on-going lawn care and maintenance.



## Attachment E - Volume and Character of Stormwater

The total impervious cover calculation for the proposed 2.23-acre site is 1.84 acres. Of this total, 1.73 acres of impervious cover (drainage area of 2.0 acres) is flowing to the existing Sedimentation Filtration Pond to be treated. The remaining 0.23 acres is flowing offsite.

The volume of stormwater runoff to the pond from the proposed 2.0-acre drainage area is 27.3 CFS for the 100-year event. This total to the pond includes 18.9 CFS routed through a 30-inch storm line which collects storm water from proposed drainage areas P2, P3 and P4 and 0.51 acres which flows offsite and to the previously approved Sedimentation Filtration Pond.

Refer to the following table for detailed information on the drainage calculations and the included construction plans for details.

Existing Drainage Calculations										
	Impervious Imp. Cover Q - 2 year Q (10 year) Q (25 year) Q							Q (100 year)		
	Acres	Tc (min)	Cover (%)	(CN=84) (AC)	(CFS)	(CFS)	(CFS)	(CFS)		
(Drainage Area P1)	2.23	5.00	0%	84	8.4	15.8	20.5	28.6		
Proposed Drainage Calculations										
			Impervious	Imp. Cover	Q - 2 year	Q (10 year)	Q (25 year)	Q (100 year)		
	Acres	Tc (min)	Cover (%)	(CN=98) (AC)	(CFS)	(CFS)	(CFS)	(CFS)		
P1	0.62	5.00	82%	0.51	3.2	5.1	6.3	8.4		
P2	0.43	5.00	91%	0.39	2.3	3.6	4.4	5.9		
P3	0.60	5.00	98%	0.59	3.2	5.1	6.2	8.3		
P4	0.35	5.00	69%	0.24	1.7	2.8	3.5	4.7		
P5 (Into street)	0.23	5.00	48%	0.11	1.0	1.8	2.2	3.1		
Proposed Total to 30" SS	1.65	5.00	90%	1.49	8.6	13.7	17.0	22.6		
Site Total (Lot 1 & Parkway)	2.23	5.00	83%	1.84	11.4	18.3	22.7	30.4		
Flow to Pond	2.00	5.00	87%	1.73	10.3	16.5	20.5	27.3		



## ATTACHMENT F - SUITABILITY LETTER FROM AUTHORIZED AGENT

Not Applicable.

No On-Site Sewage Facility is proposed in this project area.



## ATTACHMENT G - ALTERNATIVE SECONDARY CONTAINMENT METHODS

Not Applicable.

No Alternate Secondary Containment Methods are proposed in this project area.




#### ATTACHMENT H - AST CONTAINMENT STRUCTURE DRAWINGS

Not Applicable.

No Alternate Secondary Containment Methods are proposed in this project area.

### ALTA LEANDER STATION PHASE 2 SITE DEVELOPMENT PLAN FLOODPLAIN DEVELOPMENT PLAN LEANDER, TX

## **JUNE 2023** 1561 HERO WAY



PROJECT NUMBER: SD-23-0095

#### CURRENT CITY OF LEANDER PERMITS APPLICABLE:

THIS SITE PLAN DEVELOPMENT AGREEMENT 20-DA-008 ZONING ORDINANCE NO. 21-044-00 T5

ASSOCIATED PROJECTS: 20-FPD-007, 20-TOD-FP-015, 20-TOD-PICP-025, 20-TOD-SD-020

TOTAL IC: 61,395 BUILDING IC PROPOSED: 13,423

FLU CATEGORY: URBAN MIXED-USE AND GREENWAY.

<u>CIVIL ENGINEER / AGENT/LANDSCAPE</u>

GOODE FAITH ENGINEERING, LLC 1620 LA JAITA DR. SUITE 300 CEDAR PARK, TEXAS, 78613 CONTACT: ANTHONY H. GOODE, P.E. P:(972) 822-1682 E: ANTHONY@GOODEFAITHENG.COM

TRANSIT VILLAGE INVESTMENTS LTD. 2215 WESTLAKE DRIVE, SUITE 300 CONTACT: JEFF MUSGROVE

E: JMUGROVE@AMERICANREALTY.CC <u>Surveyor:</u> 4Ward land surveying

P: (512) 554-6282

P.O. BOX 90876

AUSTIN, TEXAS 78709 P: (512) 537.2384

NUMBER	SHEET TITLE
1	COVER
2	GENERAL NOTES
3	FINAL PLAT (1 OF 3)
4	FINAL PLAT (2 OF 3)
5	FINAL PLAT (3 OF 3)
6	EXISTING SITE CONDITIONS AND DEMO PLAN
7	EROSION & SEDIMENT CONTROL PLAN
8	EROSION & SEDMIENT CONTROL NOTES
9	EXISTING DRAINAGE (RECORD DRAWING)
10	DRAINAGE AREA MAP (RECORD DRAWING)
11	PROPOSED DRAINAGE PLAN
12	SITE PLAN
13	ADDRESS PLAN
14	GRADING PLAN
15	UTILITY PLAN
16	LANDSCAPING PLAN
17	ESC DTLS
18	CONSTRUCTION DETAILS (1 OF 5)
19	CONSTRUCTION DETAILS (2 OF 5)
20	CONSTRUCTION DETAILS (3 OF 5)
21	CONSTRUCTION DETAILS (4 OF 5)
22	CONSTRUCTION DETAILS (5 OF 5)
23	MASTER ARCHITECTURAL PLAN

PLAN SUBMITTAL/REVIEW LOG

1ST SUBMITTAL TO CITY	03/28/2023
2ND SUBMITTAL TO CITY	05/16/2023
3RD SUBMITTAL TO CITY	06/27/2023

FILING DATE: 03/28/2023

# **REVISIONS**

1. LEGAL DESCRIPTION: LOT 1, BLOCK "A" ALTA LEANDER STATION

3. CURRENT ZONING IS PUD - T5 (SMARTCODE).

PUBLIC SIDEWALK ALONG MAIN ST.

APPROVED BY:

SERVICES

RECREATION

7. DISTURBED ACREAGE IS 1.96 AC.

**SPECIAL CONSTRUCTION NOTES:** 

2. THIS SITE IS LOCATED WITHIN THE EDWARDS AQUIFER CONTRIBUTING ZONE.

5. GEOTECH REPORT BY RABA KISTNER CONSULTANTS, INC (RKCI) FEB 23, 2023.

ROBIN M. GRIFFIN, AICP, EXECUTIVE DIRECTOR OF DEVELOPMENT

EMILY TRUMAN, P.E., CFM, CITY ENGINEER

CHIEF JOSHUA DAVIS, FIRE MARSHAL

MARK TUMMONS, CRRP, DIRECTOR OF PARKS AND

4. ALL EASEMENT OF RECORD AS INDICATED ON THE MOST RECENT TITLE RUN (DATED **FEB 23, 2023** BY FIRST AMERICAN TITLE COMPANY FOR THIS PROPERTY ARE SHOWN ON THIS SITE PLAN.

6. IMPROVEMENTS TO BE DEDICATED TO THE CITY OF LEANDER IS 10' PUBLIC SIDEWALK ALONG HERO WAY AND 5'

1. CONTRACTOR SHALL CALL "DIG-TESS" SYSTEM (1-800-344-8377) FOR UTILITY LOCATIONS PRIOR TO ANY WORK IN CITY OR COUNTY EASEMENTS OR STREET R.O.W.


OF THE U.S. OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION." (OSHA STANDARDS MAY BE

PURCHASED FROM THE GOVERNMENT PRINTING OFFICE; INFORMATION AND RELATED REFERENCE MATERIALS MAY BE PURCHASED FROM OSHA, 611 EAST 6TH STREET, AUSTIN TEXAS.)

CONTRACTOR SHALL POT HOLE ALL EXISTING UTILITIES AT CONNECTION AND INTERSECTION PRIOR TO UTILITY MATERIALS BEING DELIVERED TO SITE.

FOR SLOPES OR TRENCHES GREATER THAN FIVE FEET IN DEPTH, A NOTE MUST BE ADDED STATING: "ALL CONSTRUCTION OPERATIONS SHALL BE ACCOMPLISHED IN ACCORDANCE WITH APPLICABLE REGULATIONS





CEDAR PARK, TX, 78613

(972) P: 822-1682

SUBMITTED BY: ANTHONY GOODE, P.E. GOODE FAITH ENGINEERING, LLC. TBPE FIRM NO. F-22664

DOES NOT CONSTITUTE A VERIFICATION OF ALL DATA, INFORMATION AND CALCULATIONS SUPPLIED BY THE APPLICANT. THE ENGINEER OF RECORD IS SOLELY RESPONSIBLE FOR THE COMPLETENESS, ACCURACT, AND ADEQUACY OF HIS/HER SUBMITTAL, WHETHER OR NOT THE APPLICATION IS REVIEWED FOR CODE COMPLIANCE BY CITY

ENGINEERS.

06-27-2023 JDL CHECKED BY 23-003.0 ΑG

ANY CHANGES TO THESE NOTES SHOULD BE CLOUDED ON THE PLAN SET.

CITY CONTACTS: ENGINEERING MAIN LINE: 512-528-2766 PLANNING DEPARTMENT: 512-528-2750 PUBLIC WORKS MAIN LINE: 512-259-2640 STORMWATER INSPECTIONS: 512-285-0055 UTILITIES MAIN LINE 512-259-1142 UTILITIES ON-CALL: 512-690-4760 UTILITY LOCATE REQUESTS locates@leandertx.gov

- 1. THE CONTRACTOR SHALL VERIFY ALL DEPTHS AND LOCATIONS OF EXISTING UTILITIES PRIOR TO ANY CONSTRUCTION. ANY DISCREPANCIES WITH CONSTRUCTION PLANS FOUND IN THE FIELD SHALL BE BROUGHT IMMEDIATELY TO THE ATTENTION OF THE ENGINEER.
- 2. THE CONTRACTOR SHALL CONTACT THE TEXAS EXCAVATION SYSTEM AT 1-800-344-8377 FOR EXISTING UTILITY LOCATIONS 48 HOURS PRIOR TO THE START OF CONSTRUCTION. THE CONTRACTOR SHALL VERIFY THE LOCATIONS OF ALL UTILITIES THAT ARE TO BE EXTENDED, TIED TO, CROSSED, OR ALTERED; OR SUBJECT TO DAMAGE/INCONVENIENCE BY THE CONSTRUCTION OPERATIONS.
- 3. CONTACT THE CITY OF LEANDER PUBLIC WORKS DEPARTMENT FOR EXISTING WATER AND WASTEWATER LOCATIONS 48 HOURS PRIOR TO CONSTRUCTION.
- a. LOCATE REQUESTS MUST INCLUDE A COPY OF YOUR 811 TICKET. THE CITY OF LEANDER IS ALLOWED UP TO 48 HOURS TO COMPLY WITH YOUR REQUEST, EXCLUDING WEEKENDS AND DESIGNATED CITY HOLIDAYS.
- b. **REFRESH ALL LOCATES <u>BEFORE</u> 14 DAYS –** LOCATE REFRESH REQUESTS <u>MUST INCLUDE</u> A COPY OF YOUR 811 TICKET. SUBMIT ALL REQUESTS TO LOCATES@LEANDERTX.GOV. TEXAS PIPELINE DAMAGE PREVENTION LAWS REQUIRE THAT A LOCATE REFRESH REQUEST BE SUBMITTED BEFORE 14 DAYS, OR IF LOCATION MARKERS ARE NO LONGER
- REPORT PIPELINE DAMAGE IMMEDIATELY IF YOU WITNESS OR EXPERIENCE PIPELINE EXCAVATION DAMAGE, PLEASE CONTACT THE CITY OF LEANDER BY PHONE AT 512-259-
- 4. ANY CHANGES OR REVISIONS TO THESE PLANS MUST FIRST BE SUBMITTED TO THE CITY BY THE DESIGN ENGINEER FOR REVIEW AND WRITTEN APPROVAL PRIOR TO CONSTRUCTION OF
- 5. A TRAFFIC CONTROL PLAN, IN ACCORDANCE WITH THE TEXAS MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES, SHALL BE SUBMITTED TO THE CITY FOR REVIEW AND APPROVAL PRIOR TO ANY PARTIAL OR COMPLETE ROADWAY CLOSURES. TRAFFIC CONTROL PLANS SHALL BE SITE SPECIFIC AND SEALED BY A REGISTERED PROFESSIONAL ENGINEER. LANE CLOSURES ON ARTERIALS AND ANY FULL ROAD CLOSURES REQUIRE MESSAGE BOARDS NOTIFYING THE PUBLIC ONE WEEK PRIOR TO THE CLOSURE.
- 6. NO WORK IS TO BE PERFORMED BETWEEN THE HOURS OF 9:00 P.M. AND 7:00 A.M. THE CITY INSPECTOR RESERVES THE RIGHT TO REQUIRE THE CONTRACTOR TO UNCOVER ALL WORK PERFORMED WITHOUT INSPECTION FURTHER, THERE IS A NOISE ORDINANCE IN EFFECT FOR CONSTRUCTION ACTIVITY BETWEEN THE HOURS OF 9:00 PM AND 7:00 AM.
- REQUESTS FOR EXCEPTIONS TO THE ORDINANCE MUST BE MADE TO LEANDER CITY COUNCIL. 7. CONTACT THE CITY INSPECTOR 4 DAYS PRIOR TO WORK TO SCHEDULE ANY INSPECTIONS ON WEEKENDS OR CITY HOLIDAYS.
- 8. NO STREET LIGHTS OR SIGNS OF ANY KIND ARE TO BE PLACED WITHIN ANY SIDEWALKS. NO BLASTING IS ALLOWED.
- 10. ANY EXISTING UTILITIES, PAVEMENT, CURBS, SIDEWALKS, STRUCTURES, TREES, ETC., THAT ARE DAMAGED OR REMOVED SHALL BE REPAIRED OR REPLACED BY THE CONTRACTOR AT NO COST TO THE OWNER.
- 11. THE CONTRACTOR SHALL GIVE THE CITY OF LEANDER 48 HOURS NOTICE BEFORE BEGINNING EACH PHASE OF CONSTRUCTION. CONTACT ASSIGNED CITY INSPECTOR.
- 12. A PRE-CONSTRUCTION CONFERENCE SHALL BE HELD WITH THE CONTRACTOR, DESIGN ENGINEER/PERMIT APPLICANT AND THE CITY OF LEANDER REPRESENTATIVES PRIOR TO INSTALLATION OF EROSION/SEDIMENTATION CONTROLS AND TREE PROTECTION MEASURES AND PRIOR TO BEGINNING ANY WORK. THE CONTRACTOR SHALL NOTIFY THE CITY OF LEANDER PLANNING DEPARTMENT PLANNING COORDINATOR AT LEAST THREE (3) DAYS PRIOR TO THE MEETING DATE.
- 13. THE CONTRACTOR AND ENGINEER SHALL KEEP ACCURATE RECORDS OF ALL CONSTRUCTION THAT DEVIATES FROM THE PLANS. THE ENGINEER SHALL FURNISH THE CITY OF LEANDER ACCURATE "RECORD DRAWINGS" FOLLOWING THE COMPLETION OF ALL CONSTRUCTION. THESE "RECORD DRAWINGS" SHALL MEET THE SATISFACTION OF THE ENGINEERING DEPARTMENTS PRIOR TO FINAL ACCEPTANCE
- 14. WHEN CONSTRUCTION IS BEING CARRIED OUT WITHIN EASEMENTS, THE CONTRACTOR SHALL CONFINE HIS WORK TO WITHIN THE PERMANENT AND TEMPORARY EASEMENTS. PRIOR TO ACCEPTANCE, THE CONTRACTOR SHALL BE RESPONSIBLE FOR REMOVING ALL TRASH AND DEBRIS WITHIN THE PERMANENT EASEMENTS. CLEANUP SHALL BE TO THE SATISFACTION OF THE ENGINEER.
- 15. CONTRACTOR TO LOCATE, PROTECT, AND MAINTAIN BENCHMARKS, MONUMENTS, CONTROL POINTS AND PROJECT ENGINEERING REFERENCE POINTS. RE-ESTABLISH DISTURBED OR DESTROYED ITEMS BY REGISTERED PROFESSIONAL LAND SURVEYOR IN THE STATE OF TEXAS, AT NO ADDITIONAL COST TO OWNER.
- 16. THE CONTRACTOR SHALL PROTECT ALL EXISTING FENCES. IN THE EVENT THAT A FENCE MUST BE REMOVED. THE CONTRACTOR SHALL REPLACE SAID FENCE OR PORTION THEREOF WITH THE SAME TYPE OF FENCING TO A QUALITY OF EQUAL OR BETTER THAN THE ORIGINAL
- 17. ALL CONSTRUCTION OPERATIONS SHALL BE ACCOMPLISHED IN ACCORDANCE WITH APPLICABLE REGULATIONS OF THE U.S. OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA). OSHA STANDARDS MAY BE PURCHASED FROM THE GOVERNMENT PRINTING OFFICE: INFORMATION AND RELATED REFERENCE MATERIALS MAY BE PURCHASED FROM OSHA, 1033 LA POSADA DR. SUITE 375, AUSTIN, TEXAS 78752-3832
- 18. ALL MATERIALS AND CONSTRUCTION PROCEDURES WITHIN THE SCOPE OF THIS CONTRACT WHERE NOT SPECIFICALLY COVERED IN THE PROJECT SPECIFICATIONS SHALL CONFORM TO ALL CITY OF LEANDER DETAILS AND CITY OF AUSTIN STANDARD SPECIFICATIONS.
- 19. PROJECT SPECIFICATIONS TAKE PRECEDENCE OVER PLANS AND SPECIAL CONDITIONS GOVERN OVER TECHNICAL SPECIFICATIONS.
- 20. HOT MIX ASPHALTIC CONCRETE PAVEMENT SHALL BE MINIMUM THICKNESS OF 2 INCHES WITH NO RECYCLED ASPHALT SHINGLES CONTENT.
- 21. CONTRACTOR SHALL IMMEDIATELY NOTIFY THE ENGINEER OF ANY QUESTIONS THAT MAY RISE CONCERNING THE INTENT, PLACEMENT, OR LIMITS OF DIMENSIONS OR GRADES NECESSARY FOR THE CONSTRUCTION OF THIS PROJECT.
- 22. CONTRACTOR SHALL BE RESPONSIBLE FOR ACQUIRING ALL PERMITS, TESTS, APPROVALS AND ACCEPTANCES REQUIRED TO COMPLETE CONSTRUCTION OF THIS PROJECT.
- 23. THE CONTRACTOR SHALL BE RESPONSIBLE FOR ALL COORDINATION BETWEEN HIMSELF AND OTHER CONTRACTORS AND UTILITIES IN THE VICINITY OF THE PROJECT. THIS INCLUDES GAS, WATER, WASTEWATER, ELECTRICAL, TELEPHONE, CABLE TV AND STREET DRAINAGE WORK. ONCE THE CONTRACTOR BECOMES AWARE OF A POSSIBLE CONFLICT, IT IS THE CONTRACTOR'S RESPONSIBILITY TO NOTIFY THE ENGINEER WITHIN TWENTY-FOUR (24)
- 24. THE CONTRACTOR MUST OBTAIN A CONSTRUCTION WATER METER FOR ALL WATER USED DURING CONSTRUCTION. A COPY OF THIS PERMIT MUST BE CARRIED AT ALL TIMES BY ALL
- 25. CONTRACTOR SHALL BE RESPONSIBLE FOR KEEPING ROADS AND DRIVES ADJACENT TO AND NEAR THE SITE FREE FROM SOIL, SEDIMENT AND DEBRIS. CONTRACTOR WILL NOT REMOVE

SOIL, SEDIMENT OR DEBRIS FROM ANY AREA OR VEHICLE BY MEANS OF WATER. ONLY SHOVELING AND SWEEPING WILL BE ALLOWED. CONTRACTOR WILL BE RESPONSIBLE FOR DUST CONTROL FROM THE SITE.

- 26. THE CITY OF LEANDER SHALL NOT BE PETITIONED FOR ACCEPTANCE UNTIL ALL NECESSARY EASEMENT DOCUMENTS HAVE BEEN SIGNED AND RECORDED.
- 27. AN ENGINEER'S CONCURRENCE LETTER AND RECORD DRAWINGS SHALL BE SUBMITTED TO THE ENGINEERING DEPARTMENT PRIOR TO THE ISSUANCE OF CERTIFICATE OF COMPLETION OR SUBDIVISION ACCEPTANCE. THE ENGINEER AND CONTRACTOR SHALL VERIFY THAT ALL FINAL REVISIONS AND CHANGES HAVE BEEN MADE TO THE DIGITAL COPY PRIOR TO CITY SUBMITTAL. RECORD CONSTRUCTION DRAWINGS, INCLUDING ROADWAY AND ALL UTILITIES SHALL BE PROVIDED TO THE CITY IN DIGITAL FORMAT AS AUTOCAD ".DWG" FILES, MICROSTATION ".DGN" FILES OR ESRI ".SHP" FILES ON CD ROM. LINE WEIGHTS, LINE TYPES AND TEXT SIZE SHALL BE SUCH THAT IF HALF-SIZE PRINTS (11"X17") WERE PRODUCED, THE PLANS WOULD STILL BE LEGIBLE. ALL REQUIRED DIGITAL FILES SHALL CONTAIN A MINIMUM OF TWO CONTROL POINTS REFERENCED TO THE STATE PLANE GRID COORDINATE SYSTEM -TEXAS CENTRAL ZONE (4203), IN US SURVEY FEET AND SHALL INCLUDE ROTATION
- COORDINATES IN US SURVEY FEET

28. TREES IN EXISTING ROW SHOULD BE PROTECTED OR NOTED IN THE PLANS TO BE REMOVED.

#### CONSTRUCTION SEQUENCING:

- 1. THE CONTRACTOR SHALL ARRANGE AND COORDINATE ACCEPTABLE MEETING TIMES FOR AN ON-SITE PRE-CONSTRUCTION MEETING WITH THE OWNER, PROJECT ENGINEER, RELEVANT CONTRACTORS RELEVANT UTILITY REPRESENTATIVES, AND THE CITY ENGINEER. AT THIS MEETING. THE CITY SHALL VERIFY THAT ALL EROSION AND SEDIMENT CONTROLS AND TREE PROTECTION ARE IN PLACE, THAT CONSTRUCTION DRAWINGS AND THE SWPPP ARE LOCATED ON SITE, AND THAT THE SWPPP PERMITS HAVE BEEN ISSUED. THE CITY MAY THEN ISSUE THE SUBDIVISION IMPROVEMENT PERMIT
- 2. INSTALL EROSION AND SEDIMENT CONTROLS 3. BEGIN CLEARING AND SITE DEMOLITION
- 4 STOCK PILE TOP SOIL 5. COORDINATE ROW PERMITS FOR CONNECTIONS TO PUBLIC MAINS 6. INSTALL UTILITIES, INSTALL FILL, GRADE TO SUBGRADE
- 7. INSTALL TRAFFIC CONTROL FOR PAVEMENT AND UTILITY CONNECTIONS 8. INSTALL PAVEMENT FOR FIRE ACCESS TO BUILDING
- 9. BEGIN BUILDING AND VERTICAL CONSTRUCTION 10 FINISH PAVEMENT 11. INSTALL LANDSCAPE AND IRRIGATION, REVEGITAION, AND
- 12. CLEAN OUT REGIONAL POND 13. REMOVE EROSION AND SEDIMENT CONTROLS
- 2. THE CONTRACTOR IS REQUIRED TO INSPECT THE CONTROLS AND FENCES AT WEEKLY INTERVALS AND AFTER SIGNIFICANT RAINFALL EVENTS TO ENSURE THAT THEY ARE FUNCTIONING PROPERLY. THE PERSON(S) RESPONSIBLE FOR MAINTENANCE OF CONTROLS AND FENCES SHALL
- CONTROLS MUST BE REMOVED WHEN THE DEPTH REACHES SIX (6) INCHES. 3. THE TEMPORARY SPOILS DISPOSAL SITE IS TO BE SHOWN IN THE EROSION CONTROL MAP. 4. ANY ON-SITE SPOILS DISPOSAL SHALL BE REMOVED PRIOR TO ACCEPTANCE UNLESS SPECIFICALLY SHOWN ON THE PLANS. THE DEPTH OF SPOIL SHALL NOT EXCEED 10 FEET IN ANY

IMMEDIATELY MAKE ANY NECESSARY REPAIRS TO DAMAGED AREAS. SILT ACCUMULATION AT

- 5. ALL AREAS DISTURBED OR EXPOSED DURING CONSTRUCTION SHALL BE RESTORED WITH A MINIMUM OF 6 INCHES OF TOPSOIL AND COMPOST BLEND. TOPSOIL ON SINGLE FAMILY LOTS MAY BE INSTALLED WITH HOME CONSTRUCTION. THE TOPSOIL AND COMPOST BLEND SHALL
- CONSIST OF 75% TOPSOIL AND 25% COMPOST. 6. SEEDING FOR REESTABLISHING VEGETATION SHALL COMPLY WITH THE AUSTIN GROW GREEN GUIDE OR WILLIAMSON COUNTY'S PROTOCOL FOR SUSTAINABLE ROADSIDES (SPEC 164--WC001 SEEDING FOR EROSION CONTROL). RESEEDING VARIETIES OF BERMUDA SHALL NOT BE USED.
- 7. STABILIZED CONSTRUCTION ENTRANCE IS REQUIRED AT ALL POINTS WHERE CONSTRUCTION TRAFFIC IS EXITING THE PROJECT ONTO EXISTING PAVEMENT. LINEAR CONSTRUCTION PROJECTS MAY REQUIRE SPECIAL CONSIDERATION. ROADWAYS SHALL REMAIN CLEAR OF SILT AND MUD. 8. TEMPORARY STOP SIGNS SHOULD BE INSTALLED AT ALL CONSTRUCTION ENTRANCES WHERE A 27. LINE FLUSHING OR ANY ACTIVITY USING A LARGE QUANTITY OF WATER MUST BE COORDINATED
- 9. IN THE EVENT OF INCLEMENT WEATHER THAT MAY RESULT IN A FLOODING SITUATION, THE CONTRACTOR SHALL REMOVE INLET PROTECTION MEASURES UNTIL SUCH TIME AS THE WEATHER EVENT HAS PASSED.

#### WATER AND WASTEWATER NOTES

STOP CONDITION DOES NOT ALREADY EXIST.

- 1. PRESSURE TAPS SHALL BE IN ACCORDANCE WITH CITY OF LEANDER STANDARD SPECIFICATIONS. THE CONTRACTOR SHALL PERFORM ALL EXCAVATION, ETC. AND SHALL FURNISH, INSTALL AND AIR TEST THE SLEEVE AND VALVE. A CITY OF LEANDER INSPECTOR MUST BE PRESENT WHEN THE CONTRACTOR MAKES A TAP, AND/OR ASSOCIATED TESTS. A MINIMUM OF TWO (2) WORKING DAYS NOTICE IS REQUIRED. "SIZE ON SIZE" TAPS WILL NOT BE PERMITTED UNLESS MADE BY THE USE OF AN APPROVED FULL-CIRCLE GASKETED TAPPING SLEEVE. CONCRETE BLOCKING SHALL BE PLACED BEHIND AND UNDER ALL TAP SLEEVES A MINIMUM OF 24 HOURS PRIOR TO THE BRANCH BEING PLACED INTO SERVICE. BLOCKING SHALL BE INSPECTED PRIOR TO 30. TESTING SHALL BE PERFORMED FOR ALL WASTEWATER PIPE INSTALLED AND PRESSURE PIPE
- FIRE HYDRANTS ON MAINS UNDER CONSTRUCTION SHALL BE SECURELY WRAPPED WITH A BLACK POLY WRAP BAG AND TAPED INTO PLACE. THE POLY WRAP SHALL BE REMOVED WHEN THE MAINS ARE ACCEPTED AND PLACED INTO SERVICE.
- 3. CURVILINEAR WASTEWATER DESIGN LAYOUT IS NOT PERMITTED.
- 4. THRUST BLOCKING OR RESTRAINTS SHALL BE IN ACCORDANCE WITH THE CITY OF LEANDER STANDARD SPECIFICATIONS AND REQUIRED AT ALL FITTINGS PER DETAIL OR MANUFACTURER'S FOR AT THE TIME OF CONSTRUCTION PLAN SUBMITTAL.
- 5. MANDREL TESTING WILL BE REQUIRED ON ALL WASTEWATER PIPE. PER TCEQ, THIS TEST MUST BE CONDUCTED AFTER THE FINAL BACKFILL HAS BEEN IN PLACE AT LEAST 30 DAYS.
- 6. ALL NEWLY INSTALLED PIPES AND RELATED PRODUCTS MUST CONFORM TO AMERICAN NATIONAL STANDARDS INSTITUTE/NATIONAL SANITATION FOUNDATION (ANSI/NSF) STANDARD 34. ALL WATER METER BOXES SHALL BE: 61 AND MUST BE CERTIFIED BY AND ORGANIZATION ACCREDITED BY ANSI
- 7. DURING PERIODS OF EXTENDED DRY WEATHER, TRENCH BACKFILL MUST BE COMPACTED BY
- FLOODING THE TRENCHES AS DIRECTED BY THE CITY ENGINEER. 8. ALL WATER SERVICE, WASTEWATER SERVICE AND VALVE LOCATIONS SHALL BE APPROPRIATELY

"W" ON TOP OF CURB WATER SERVICE WASTEWATER SERVICE "S" ON TOP OF CURB "V" ON TOP OF CURB

STAMPED AS FOLLOWS:

RECOMMENDED BY AWWA FORMULAS.

- 9. TOOLS FOR STAMPING THE CURBS SHALL BE PROVIDED BY THE CONTRACTOR. OTHER APPROPRIATE MEANS OF STAMPING SERVICE AND VALVE LOCATIONS SHALL BE PROVIDED IN AREAS WITHOUT CURBS. SUCH MEANS OF STAMPING SHALL BE SPECIFIED BY THE ENGINEER AND ACCEPTED BY THE CITY OF LEANDER
- 10. ALL PLASTIC PIPES FOR USE IN PUBLIC WATER SYSTEMS MUST BEAR THE NATIONAL SANITATION FOUNDATION SEAL OF APPROVAL (NSF-PW) AND HAVE AN ASTM DESIGN PRESSURE RATING OF AT LEAST 200 PSI.
- 11. NO PIPE OR FITTING WHICH HAS BEEN USED FOR ANY PURPOSE OTHER THAN THE CONVEYANCE OF DRINKING WATER SHALL BE ACCEPTED OR RELOCATED FOR USE IN ANY PUBLIC DRINKING
- 12. TYPICAL DEPTH OF COVER FOR ALL WASTEWATER LINES SHALL BE 48" MINIMUM, WATER LINES SHALL BE 36" MINIMUM UNDER BOTH PAVEMENT AND NATURAL GROUND. STORM SEWER SHALL BE 24" MINIMUM UNDER NATURAL GROUND
- 13. THE HYDROSTATIC LEAKAGE RATE SHALL NOT EXCEED THE AMOUNT ALLOWED OR
- 14. ALL WATER MAINS, DISTRIBUTION LINES AND SERVICE LINES SHALL BE INSTALLED IN ENCASEMENT PIPE UNDERNEATH EXISTING STREETS AND OTHER PAVED SURFACES UNLESS APPROVED WITH PLANS.
- 15. ALL MECHANICAL RESTRAINTS SHALL BE INSTALLED IN ACCORDANCE WITH THE MANUFACTURER'S INSTRUCTIONS
- 16. ALL DEAD-END WATER MAINS SHALL HAVE THRUST RESTRAINTS INSTALLED ON THE LAST THREE PIPE-LENGTHS (STANDARD 20' LAYING LENGTH), AT MINIMUM, AND THRUST BLOCKS INSTALLED ON THE PLUG. ADDITIONAL THRUST RESTRAINTS MAY BE REQUIRED BASED UPON THE MANUFACTURER'S RECOMMENDATIONS AND/OR CALCULATIONS BY THE ENGINEER OF RECORD.
- 17. WHERE WATER LINES CROSS WASTEWATER LINES AND THERE IS LESS THAN 9 FEET CLEARANCE BETWEEN LINES, THE WASTEWATER LINE SHALL BE PLACED SO THAT THE WASTEWATER PIPE SECTION IS CENTERED ON THE WATER LINE AND CONSTRUCTED IN ACCORDANCE WITH TCEQ
- CHAPTERS 217,53(b) AND 290,44(e). 18. PIPE MATERIAL FOR WATER MAINS SHALL BE PVC (AWWA C900-16 MIN. 235 PSI PRESSURE RATING). WATER SERVICES (2" OR LESS) SHALL BE POLYETHYLENE TUBING (BLACK, 200PSI, SDR-(9)). DUCTILE IRON PIPE (AWWA C115/C151, MIN. PRESSURE CLASS 250) MAY BE USED FOR
- WATER MAINS WITH THE EXPRESS APPROVAL OF CITY OF LEANDER ENGINEERING. 19. PIPE FOR PRESSURE WASTEWATER MAINS SHALL BE PVC (AWWA C900-16), GREEN AND
- MARKED FOR SEWER. PIPE MATERIAL FOR GRAVITY WASTEWATER MAINS SHALL BE PVC (ASTM D2241, D3034 MAX. SDR-26 OR PS115 F679) OR FIBERGLASS WITH PIPE STIFFNESS OF 72 PSI PER COA SPL WW-509.
- 20. ALL FIRE HYDRANT LEADS SHALL BE DUCTILE IRON PIPE (AWWA C115/C151 PRESSURE CLASS
- 21. INTERIOR SURFACES OF ALL DUCTILE IRON POTABLE OR RECLAIMED WATER PIPE SHALL BE CEMENT-MORTAR LINED AND SEAL COATED AS REQUIRED BY AWWA C104.
- 22. ALL IRON PIPE AND FITTINGS SHALL BE WRAPPED WITH MINIMUM 8-MIL POLYETHYLENE. 23. THE CONTRACTOR SHALL CONTACT THE ENGINEERING DEPARTMENT INSPECTOR AT 528-2700
- AT LEAST 48 HOURS PRIOR TO CONNECTING TO THE EXISTING WATER LINES. 24. ALL MANHOLES SHALL BE CONCRETE WITH CAST IRON RING AND COVER. TAPPING OF

FIBERGLASS MANHOLES SHALL NOT BE ALLOWED.

- 25. EXISTING MANHOLES MODIFIED BY CONSTRUCTION ACTIVITY SHALL BE TESTED FOR LEAKAGE BY VACUUM. ANY EXISTING MANHOLE WHICH FAILS TO PASS THE VACUUM TEST SHALL BE CLOSELY EXAMINED BY THE INSPECTOR AND THE CONTRACTOR TO DETERMINE IF THE MANHOLE CAN BE REPAIRED. THEREAFTER, THE CONTRACTOR SHALL EITHER REPAIR OR REMOVE AND REPLACE THE MANHOLE AS DIRECTED.
- 26. PIPE CONNECTIONS TO EXISTING MANHOLES AND JUNCTION BOXES SHALL BE CONSTRUCTED IN ACCORDANCE WITH CITY OF AUSTIN SPECIFICATION 506.5.F.
- WITH THE PUBLIC WORKS DEPARTMENT.
- 28. THE CONTRACTOR, AT HIS EXPENSE, SHALL PERFORM STERILIZATION OF ALL CONSTRUCTED POTABLE WATER LINES AND SHALL PROVIDE ALL EQUIPMENT (INCLUDING TEST GAUGES), SUPPLIES (INCLUDING CONCENTRATED CHLORINE DISINFECTING MATERIAL), AND NECESSARY LABOR REQUIRED FOR THE STERILIZATION PROCEDURE. THE STERILIZATION PROCEDURE SHALL BE MONITORED BY CITY OF LEANDER PERSONNEL. WATER SAMPLES WILL BE COLLECTED BY THE CITY OF LEANDER TO VERIFY FACH TREATED LINE HAS ATTAINED AN INITIAL CHI ORINE CONCENTRATION OF 50 PPM. WHERE MEANS OF FLUSHING IS NECESSARY, THE CONTRACTOR, AT HIS EXPENSE, SHALL PROVIDE FLUSHING DEVICES AND REMOVE SAID DEVICES PRIOR TO FINAL ACCEPTANCE BY THE CITY OF LEANDER.
- 29. SAMPLING TAPS SHALL BE BROUGHT UP TO 3 FEET ABOVE GRADE AND SHALL BE EASILY ACCESSIBLE FOR CITY PERSONNEL. AT THE CONTRACTORS' REQUEST, AND IN HIS PRESENCE, SAMPLES FOR BACTERIOLOGICAL TESTING WILL BE COLLECTED BY THE CITY OF LEANDER NOT LESS THAN 24 HOURS AFTER THE TREATED LINE HAS BEEN FLUSHED OF THE CONCENTRATED CHLORINE SOLUTION AND CHARGED WITH WATER APPROVED BY THE CITY.
- HYDROSTATIC TESTING OF ALL WATER LINES CONSTRUCTED. THE OWNER'S CONTRACTOR SHALL PROVIDE ALL EQUIPMENT (INCLUDING PUMPS AND GAUGES), SUPPLIES AND LABOR NECESSARY TO PERFORM THE TESTS. THE CONTRACTOR SHALL NOTIFY THE CITY OF LEANDER ENGINEERING DEPARTMENT NO LESS THAN 48 HOURS PRIOR TO PERFORMING STERILIZATION, QUALITY TESTS, OR PRESSURE TESTS. A CITY OF LEANDER INSPECTOR SHALL BE PRESENT FOR ALL TESTS AND SHALL BE PAID FOR BY THE OWNER/CONTRACTOR. THESE SERVICES ARE PAID
- RECOMMENDATION. ALL FITTINGS SHALL HAVE BOTH THRUST BLOCKING AND RESTRAINTS.

  31. THE CONTRACTOR SHALL NOT OPEN OR CLOSE ANY VALVE UNLESS AUTHORIZED BY THE CITY OF
  - 32. ALL VALVE BOXES AND COVERS SHALL BE CAST IRON.

  - 33. ALL WATER VALVE COVERS ARE TO BE PAINTED BLUE.
    - a. SINGLE, 1" METER AND BELOW DFW37F-12-1CA, OR EQUAL b. DUAL, 1" METERS AND BELOW DFW39F-12-1CA, OR EQUAL
    - c. 1.5" SINGLE METER DFW65C-14-1CA, OR EQUAL d. 2" SINGLE METER DFW1730F-12-1CA, OR EQUAL
  - 35. SAND, AS DESCRIBED IN AUSTIN SPECIFICATION ITEM 510 PIPE, SHALL NOT BE USED AS BEDDING FOR WATER AND WASTEWATER LINES. ACCEPTABLE BEDDING MATERIALS ARE PIPE BEDDING STONE, PEA GRAVEL AND IN LIEU OF SAND, A NATURALLY OCCURRING OR MANUFACTURED STONE MATERIAL CONFORMING TO ASTM C33 FOR STONE QUALITY AND MEETING THE FOLLOWING GRADATION SPECIFICATION:

SIEVE SIZE	PERCENT	RETAINED	BY	WEIGHT

1/2"	0
3/8"	0-2
#4	40-85
#10	95-100

#### GRADING NOTES

36. THE CONTRACTOR IS HEREBY NOTIFIED THAT CONNECTING TO, SHUTTING DOWN, OR

TERMINATING EXISTING UTILITY LINES MAY HAVE TO OCCUR AT OFF-PEAK HOURS. SUCH

ON ENVIRONMENTAL QUALITY (TCEQ) REGULATIONS, 30 TAC CHAPTER 213 AND 30 TAC

CHAPTER 217, AS APPLICABLE. WHENEVER TCEQ AND CITY OF LEANDER SPECIFICATION

MANHOLES SHALL BE COATED PER CITY OF AUSTIN SPL WW-511 (RAVEN 405 OR SPRAYWALL)

CONTRACTOR. CAMERA TESTING FOR WASTEWATER LINES IN ROADWAY SHALL OCCUR BEFORE

PAVING. CONTRACTOR SHALL PROVIDE THE CITY WITH A DVD COPY OF THE FULL CAMERA

RECLAIMED AND RECYCLED WATER VALVE COVERS SHALL BE SQUARE AND PAINTED PURPLE.

LEANDER HAS NOT REVIEWED THESE PLANS FOR COMPLIANCE WITH THE AMERICANS WITH

DISABILITIES ACT, OR ANY OTHER ACCESSIBILITY LEGISLATION, AND DOES NOT WARRANTY OR

IMPROVEMENTS WERE INSPECTED BY TDLR OR A REGISTERED ACCESSIBLITY SPECIALIST (RAS)

3. CONTRACTOR SHALL PROVIDE QUALITY TESTING FOR ALL INFRASTRUCTURES TO BE ACCEPTED

AND MAINTAINED BY THE CITY OF LEANDER AFTER COMPLETION. THE CONTRACTOR SHALL

NOTIFY THE CITY OF LEANDER ENGINEERING DEPARTMENT AT 528-2700 NO LESS THAN 48

4. BACKFILL BEHIND THE CURB SHALL BE COMPACTED TO OBTAIN A MINIMUM OF 95% MAXIMUM

DENSITY TO WITHIN 6" OF TOP OF CURB. MATERIAL USED SHALL BE PRIMARILY GRANULAR

5. A MINIMUM OF 6" OF TOPSOIL SHALL BE PLACED BETWEEN THE CURB AND RIGHT-OF-WAY AND

CLEAN TOPSOIL FREE FROM ALL CLODS AND SUITABLE FOR SUSTAINING PLANT LIFE

IN ALL DRAINAGE CHANNELS EXCEPT CHANNELS CUT IN STABLE ROCK.

6. DEPTH OF COVER FOR ALL CROSSINGS UNDER PAVEMENT, INCLUDING GAS, ELECTRIC

7. STREET RIGHT-OF-WAY SHALL BE GRADED AT A SLOPE OF 1/2" PER FOOT TOWARD THE CURB

GRADING SCHEME IS MADE TO AND ACCEPTED BY THE CITY OF LEANDER PUBLIC WORKS

9. ALL REINFORCED CONCRETE PIPE SHALL BE MINIMUM CLASS III OF TONGUE AND GROOVE OR

10. THE CONTRACTOR IS TO NOTIFY THE ENGINEERING INSPECTOR 48 HOURS PRIOR TO THE

FOLLOWING TESTING: PROOF ROLLING SUB-GRADE AND EVERY LIFT OF ROADWAY

OF THIS TESTING MUST BE WITNESSED BY A CITY OF LEANDER REPRESENTATIVE.

8. BARRICADES BUILT TO THE CITY OF LEANDER STANDARDS SHALL BE ERECTED ON ALL DEAD-END

STREETS AND AS NECESSARY DURING CONSTRUCTION TO MAINTAIN JOB AND PUBLIC SAFETY.

EMBANKMENT, IN-PLACE DENSITY TESTING OF EVERY BASE COURSE, AND ASPHALT CORES. ALL

11. THE CONTRACTOR MUST PROVIDE A PNEUMATIC TRUCK PER TXDOT SPEC FOR PROOF ROLLING.

STREETS WILL CULMINATE IN A DISTANCE OF 40 FEET FROM INTERSECTING CURB LINE UNLESS

STREETS WILL CULMINATE IN A DISTANCE OF 40 FEET FROM INTERSECTING CURB LINE UNLESS

14. A CURB LAYDOWN IS REQUIRED AT ALL POINTS WHERE THE PROPOSED SIDEWALK INTERSECTS

15. ALL STRIPING, WITH THE EXCEPTION OF STOP BARS, CROSS WALKS, WORDS AND ARROWS, IS TO

BE TYPE II (WATER BASED). STOP BARS, CROSS WALKS, WORDS AND ARROWS REQUIRE TYPE

16. MANHOLE FRAMES, COVERS, VALVES, CLEAN-OUTS, ETC. SHALL BE RAISED TO GRADE PRIOR TO

17. CONTRACTOR SHALL NOTIFY THE LEANDER ENGINEERING DEPARTMENT AT 528-2700 AT LEAST

EASEMENT OR STREET ROW. THE METHOD OF PLACEMENT AND COMPACTION OF BACKFILL IN

48 HOURS PRIOR TO THE INSTALLATION OF ANY DRAINAGE FACILITY WITHIN A DRAINAGE

THE CITY'S ROW MUST BE APPROVED PRIOR TO THE START OF BACKFILL OPERATIONS.

20. THE GEOTECHNICAL ENGINEER SHALL INSPECT THE SUBGRADE FOR COMPLIANCE WITH THE

21. GEOTECHNICAL INVESTIGATION INFORMATION AND PAVEMENT RECOMMENDATIONS WERE

PROVIDED BY RABA KISTNER. PAVEMENT RECOMMENDATIONS ARE AS FOLLOWS:

1. TRENCH SAFETY SYSTEMS TO BE UTILIZED FOR THIS PROJECT ARE DESCRIBED IN ITEM 509S

"TRENCH SAFETY SYSTEMS" OF THE CITY OF AUSTIN STANDARD SPECIFICATIONS AND SHALL BE

IN ACCORDANCE WITH THE LAWS OF THE STATE OF TEXAS AND THE U.S. OCCUPATION SAFETY

9.0 in.

RIGID PAVEMENT

Trurks Type

hedium Duty Thriffic

19. A MINIMUM OF SEVEN DAYS OF CURE TIME IS REQUIRED FOR HMAC PRIOR TO THE

DESIGN ASSUMPTIONS MADE DURING PREPARATION OF THE SOILS REPORT. ANY

ADJUSTMENTS THAT ARE REQUIRED SHALL BE MADE THROUGH REVISIONS OF THE

12. AT INTERSECTIONS WHICH HAVE VALLEY DRAINAGE, THE CROWNS OF THE INTERSECTING

13. AT THE INTERSECTION OF TWO 44' STREETS OR LARGER, THE CROWNS OF THE INTERSECTING

UNLESS OTHERWISE INDICATED. HOWEVER, IN NO CASE SHALL THE WIDTH OF RIGHT-OF-WAY

AT 1/4" PER FOOT SLOPE BE LESS THAN 10 FEET UNLESS A SPECIFIC REQUEST FOR AN ALTERNATE

TELEPHONE, CABLE TV, ETC., SHALL BE A MINIMUM OF 36" BELOW SUBGRADE.

WITH NO ROCKS LARGER THAN 6" IN THE GREATEST DIMENSION. THE REMAINING 6" SHALL BE

41. RECLAIMED AND RECYCLED WATER LINE SHALL BE CONSTRUCTED OF "PURPLE PIPE." ALL

1. ALL SIDEWALKS SHALL COMPLY WITH THE AMERICANS WITH DISABILITIES ACT. THE CITY OF

2. PRIOR TO ACCEPTANCE THE ENGINEER SHALL SUBMIT DOCUMENTATION THAT THE

APPROVE THESE PLANS FOR ANY ACCESSIBILITY STANDARDS.

AND ARE IN COMPLIANCE WITH THE REQUIREMENTS OF THE TABA.

TO BE DONE IN 12" LIFTS EVERY 500' AND AT LEAST ONCE PER LINE SEGMENT

40. ALL GRAVITY WASTEWATER MAINS TO BE TESTED BY CAMERA AND PAID FOR BY THE

CONFLICT, THE MORE STRINGENT SHALL APPLY.

INSPECTION.

STREET AND DRAINAGE NOTES

HOURS PRIOR TO ANY TESTING.

O-RING JOINT DESIGN.

OTHERWISE NOTED.

OTHERWISE NOTED.

THERMOPLASTIC.

CONSTRUCTION PLANS.

den Detr - 00.000 USA

charmolised stalls areas)

TRENCH SAFETY NOTES

FINAL PAVEMENT CONSTRUCTION.

18. A STOP BAR SHALL BE PLACED AT ALL STOP SIGN LOCATIONS.

INTRODUCTION OF PUBLIC VEHICULAR TRAFFIC TO ANY STREETS.

FLEXIBLE PAVEMENT

AND HEALTH ADMINISTRATION REGULATIONS.

HOURS ARE USUALLY OUTSIDE NORMAL WORKING HOURS AND POSSIBLY BETWEEN 12 AM AND

- POSITIVE DRAINAGE SHALL BE MAINTAINED ON ALL SURFACE AREAS WITHIN THE SCOPE OF THIS PROJECT. CONTRACTOR SHOULD TAKE PRECAUTIONS NOT TO ALLOW ANY PONDING OF
- 2. THE CONTRACTOR SHALL CONSTRUCT EARTHEN EMBANKMENTS WITH SLOPES NO STEEPER THAN 3:1 AND COMPACT SOIL TO 95% OF MAXIMUM DENSITY IN ACCORDANCE WITH THE CITY
- OF AUSTIN STANDARD SPECIFICATIONS 3. AREAS OF SOIL DISTURBANCE ARE LIMITED TO GRADING AND IMPROVEMENTS SHOWN. ALL 37. ALL WASTEWATER CONSTRUCTION SHALL BE IN ACCORDANCE WITH THE TEXAS COMMISSION OTHER AREAS WILL NOT BE DISTURBED.

#### BENCHMARK INFO:

#### 39. DENSITY TESTING FOR TRENCH BACKFILL LOCATED WITHIN THE LIMITS OF THE PAVED AREA IS

SQUARE CUT IN CONCRETE ISLAND OF DRIVEWAY ISLAND SOUTHWEST OF SOUTHWEST CORNER OF PROJECT SITE NORTHING - 10184706.158

EASTING - 3078080.988 ELEVATION - 954.62'

#### SQUARE CUT ON TOP OF CURB INLET ON NORTH SIDE OF HERO WAY APPROXIMATELY CENTER OF PROJECT SITE NORTHING - 10185109.224

EASTING - 3078193.756

ELEVATION - 948.8'

GOODE FAITH


CIVIL ENGINEERING AND PLANNING

(972) 822 - 1682


TBPE FIRM REGISTRATION NO. F-2266

DATE 06-27-2023 PROJECT NO. 23-003.0 DESIGNED BY


JDL CHECKED BY ΑG



PLAT DOC NO.



3 of **23** 



## STA TION AL $\alpha r$

	a a		P	- · · · · · · · · · · · · · · · · · · ·	
ACRES OF LAND, MORE OR LESS, BEING OUT OF AND A PART OF THE TALBOT CHAMBERS TRACT NO. 125, AND THE ELUAH D. HARMON SURVEY, ABSTRACT NO. 6, IN THE CITY OF LAMSON COUNTY, TEXAS, BEING A PORTION OF THAT CERTAIN CALLED 94.24 ACRE TRACT STRACT NO. 3 IN A SPECCAL WARRANTY DEED TO TRANSIT WILLDED INVESTMENT, LTD., OF DOCUMENT NO. 2 IN A SPECCAL PUBLIC RECORDS OF WILLAMSON COUNTY, TEXAS SAID 15.97 ACRES OF LAND BEING MORE PARTICULARLY DESCRIBED BY METES AND BOUNDS	a 1/2-inch fron rod found in the southerly right-of-way line of Hero Way (County Road c right-of-way (ROW) dedicated by a ROW Donation Deed to Williamson County, of record in 2.209077324, O.P.R.W.C.T., for the southeasterly corner of said ROW Donation Deed, same westerly line of that certain called 3.1001 acre tract described as Parcel 2A in a Donation nty Deed to Williamson County, of record in Document No. 2009073716, O.P.R.W.C.T., for the corner of the tract described herein;	the easterly line of the tract described herein, with the easterly line of said 94.24 acre 21'37'23' East, at a distance of 16.54 feet possing a 1½-inch iron rod found at the corner of said 3.1001 acre tract described as Parel 2A, same also being an angle point berry right—of-way line of Hero Way (County, Road 259), same also being the northwesterly semainder of that certain 23.402 acre tract described as Tract 2 in a Warranty Deed from ouse and wife, Bonnie R. House to House Medical Center Convalescent Home, Inc. (conveying 50% interest), of record in Volume 1726, Page 941, Deed Records of Williamson County, C.T.), said 23.402 acre tract also described as Tract 2 in a Warranty Deed from Franklin R. Wife, Bonnie R. House to House —Cross and Associates (conveying an undivided 16.667% record in Volume 1726, Page 947, D.R.W.C.T., in all a total distance of 710.89 feet to a oint in the center of Brushy Creek, from which point a 1½-inch iron rod found 21'37'23" East, a distance of 645.47 feet;	the centerline of Brushy Creek, over and across said 94.24 acre tract, the following 1) courses and distances:	distance of 47.8 distance of 25.33 distance of 25.33 distance of 23.34 distance of 11.96 distance of 14.65 distance of 14.92 distance of 19.82 distance of 19.82 distance of 19.83 distance of 19.83 distance of 19.71 distance of 19.73 distance of 19.73 distance of 19.73 distance of 19.73 distance of 19.74 distance of 25.94 distance of 2	ein, the following six (b) courses and distances: 3.16.29° West, at a distance of 40.00 feet passing a 5/8-inch iron rod set with a plastic "WCI 10194451" set for reference, at a distance of 162.87 feet passing a 5/8-inch iron of plastic cap stamped "WCI 10194451" set for reference, in all a total distance sit to a calculated point in rock riprap for the beginning of a curve to the left; feet along the arc of said curve, with a radius of 1079.04 feet, a central angle and whose chord bears, North 1712.33° West, a distance of 148.70 feet to a 5/8-inch with a plastic cap stamped "WCI 10194451";
ACRE TRACT LIANS LIANS S TRA DOCUI	D 2 7 € 2 0	the contract of the contract o	1) t	73.14 73.15 73.15 73.15 73.15 73.15 74.15 74.15 74.15 74.15 75	Fib. 29 WG/ WG/ WG/ O bet to a pet to a feet a and


_	SALVE STATE OF THE	
5	S83°31'40"W	47.85
2	S86°21'53"W	25.25
2	S70*41'03"W	67.30
7	S23°08'19"W	23.30
57	S55°15'45"W	24.49
97	N88-13'55"W	29.16
77	N69°20'43"W	11.96
87	N88°17'49"W	58.86
67	N68°52'36"W	14.65
C.50	N50°45'41"W	20.16
141	N88°48'38"W	14.92
L12	S39°25'14"W	85.61
L13	S62*49'07"W	54.20
2	S81°05'26"W	19.83
L15	N70°25'02"W	21.18
1.16	N79°48'04"W	42.37
112	S82"02'08"W	32.92
1.18		27.12
	THOUGH	1 2
2 2	W 00 90 000	47.08
3	W 82 CL 18N	35.40
2	S55"10"49"W	19.77
122	S65°52'45"W	24.43
123	S81°24'52"W	25.94'
124	S86°12'43"W	29.99
1.25	S75°08'12"W	5.54
927	N82°17'10"W	23.10
127	N42°27"58"W	53.15
1.28	N58*46'05"W	32.52
[28]	N63°08'05"W	51.80
L30	N73-54'12'W	20.56
131	N64°38'35"W	74.30
132	N23°26'48"E	42.48
((L32))	S23°27'21"W	42.47
L33	N68°25'49"E	25.00
(((33))	S68°26'22"W	25.00
134	N21°34'11"W	14.61
135	S68°25'36"W	29.08
136	N82*15'34"E	2.73
137	N86°32'59"E	21.14
138	S72*17'37"E	16.77
L39	N67*46'17"E	8.77
140	N22°12'15"W	727
41	N67*45'04"E	11.52
142	N86°33'12"E	15.50
143	N22°13'43"W	12.77


						,
29.09	N20°23'16.22"W	1.32'41"	1079.04"	29.09	C110	
9.88	S29*37'26.45"W	76-18'01"	8.00	10.65	C109	
11.31	N67*13'48.57"W	89*59*50*	8.00'	12.57	C108	
17.74	N29*18'22.83"W	14"09"19"	72.00	17.79	C107	
14.29	N29*18'22.83"W	14.09.19"	58.00	14.33	C108	
36.35	N49°22'44.80"W	45°52'01"	46.64'	37.34	C105	
8.49	S89*39*11.81*E	13*10'32"	37.00	8.51	C104	
24.63	S49°26'24.03"E	44.20.24"	32.64'	25.26	C103	
17.74	S29*18'22.83"E	14.09.19"	72.00	17.79	C102	


## STA TION LEANDER FINAL PLA ANDER, WILLIAMSON JY


LID., OWNER OF 2.00 ACRES, BEING A PORTION OF A 94.24 ACRE TRACT OFED OF RECORD IN DOCUMENT NO. 2006112794, OF THE OFFICIAL TEXAS DO HEREBY CERTIFY THAT THERE ARE NO LIEN HOLDERS AND USE OF ALL ADDITIONAL ROW, STREATENS, ALLEYS, EASEMENTS, PARKS, AND UBLIC DEDICATION, OF WHEN THE SUBDINIOSAL ROWS HOR FOR TO THE INHABITANTS OF THE SUBDINISON AS SHOWN HEREON TO BE













WAY HERO

AT SHOPS

DATE 06-27-2023

PROJECT NO.

23-003.0

DESIGNED BY JDL


CHECKED BY ΑG


AT (3 OF 3)

GOODE FAITH CIVIL ENGINEERING AND PLANNING (972) 822 - 1682 TBPE FIRM REGISTRATION NO. F-2266

5 of 23

PLAT DOC NO.





7 of 23

POTENTIAL POLLUTANTS

POTENTIAL SOURCES OF STORM WATER POLLUTION FROM THE CONSTRUCTION OF THE PROJECT ARE:

1. DISTURBED SOILS FROM THE CONSTRUCTION SITE

INCREASED SEDIMENT LOADING IN STORM WATER CAN BE ATTRIBUTED TO: A)DIRECT RAINFALL ONTO DISTURBED SOIL AREAS, STOCKPILES, SAND, GRAVEL, AND ROCK AREA WHERE RAIN DISLODGES SOIL PARTICLES; B) EROSION OF DISTURBED SOIL AREAS; C) THE TRANSFER OF SOILS BY EQUIPMENT OR VEHICLE TIRES ONTO DISTURBED AND NON-DISTURBED AREAS WHERE THEY ARE WASHED INTO DRAINAGE DITCHES OR OTHER SIMILAR WATER CONVEYANCE

2. OIL, GREASE, HYDRAULIC FLUIDS, AND FUELS FROM THE OPERATION OF EQUIPMENT ON THE SITE.

THERE IS A POTENTIAL FOR STORM WATER CONTAMINATION IN THE FORM OF OIL, GREASE, HYDRAULIC FLUID, AND FUEL FROM EQUIPMENT AND VEHICLES ON THE SITE, THESE SUBSTANCES ARE TYPICALLY RELEASED TO THE ENVIRONMENT BECAUSE OF EQUIPMENT FAILURE AND DURING MAINTENANCE OPERATIONS.

#### SITE LOCATION MAP

SEE CONSTRUCTION DRAWING PLAN SET PROJECT LOCATION MAP

#### DETAILED SITE MAP

SEE CONSTRUCTION DRAWING PLAN SET SITE MAP

FOR IDENTIFICATION OF RECEIVING WATERS ON OR ADJACENT TO THE SITE REFERENCE DETAILED CONSTRUCTION DRAWING PLAN SET "EXISTING CONDITIONS PLAN".

#### STATE AND LOCAL PLANS

THE SWPPP IS CONSISTENT WITH REQUIREMENTS SPECIFIED IN APPLICABLE STORM WATER, WATER QUALITY, SEDIMENT, AND EROSION SITE PLANS, PERMITS OR SIMILAR ORDINANCES OF LOCAL, STATE, OR FEDERAL OFFICIALS.

THIS PROJECT IS LOCATED IN THE EDWARDS AQUIFER CONRTIBUTING ZONE.

- SEQUENCE OF MAJOR ACTIVITIES INSTALLATION OF TEMPORARY EROSION CONTROLS.
- SITE DEMOLITION AND GRADING. 3. CONSTRUCTION OF FACILITIES.
- 4. SITE RESTORATION.
- 5. ASPHALT REPAIR, SEEDING, RE-VEGATATION, AND SOIL SURFACE PROTECTION.
- 6. REMOVAL OF TEMPORARY EROSION AND SEDIMENTATION CONTROLS.

TEMPORARY AND PERMANENT EROSION CONTROLS

TEMPORARY EROSION AND SEDIMENT CONTROLS WILL CONSIST OF SILT FENCE AND ROCK BERMS ON THE DOWN-GRADIENT PERIMETER OF THE SITE, PRESERVATION OF NATURAL VEGETATION WHERE AVAILABLE AND RECURRING CLEAN UP OF MUD/SOIL TRACKED ONTO

SERVE AS FINAL STABILIZATION AND WILL REDUCE SURFACE EROSION ON AREAS NOT COVERED BY ASPHALT, CONCRETE.

FOR SPECIFIC LOCATION AND SELECTION OF TEMPORARY AND PERMANENT CONTROLS REFER TO EROSION AND SEDIMENTATION CONTROL PLAN WITHIN CONSTRUCTION DRAWING PLAN SET.

#### TEMPORARY STABILIZATION

STABILIZATION MEASURES WILL BE INITIATED IN PORTIONS OF THE PROJECT SITE WHERE CONSTRUCTION ACTIVITIES HAVE TEMPORARLY OR PERMANENTLY CEASED FOR 14 DAYS, BUT IN NO CIRCUMSTANCES MORE THAN 21 DAYS AFTER THE CONSTRUCTION - 100% SHALL PASS THROUGH A 1.5-INCH (38-MM) SCREEN. ACTIVITY IN THAT PORTION OF THE PROJECT SITE HAS TEMPORARILY OR PERMANENTLY CEASED.

#### FINAL STABILIZATION

FINAL STABILIZATION OF SITE WILL CONSIST OF ESTABLISHMENT OF PERMANENT WARM SEASON VEGETATION ON PORTIONS OF THE SITE NOT COVERED BY CONCRETE, OR ASPHALT. ESTABLISHMENT OF PERMANENT VEGETATION SUITABLE FOR TPDES GENERAL PERMIT COMPLIANCE MUST MEASURE 70% AERIAL COVERAGE (COMPARED TO BACKGROUND NATIVE VEGETATION AERIAL COVERAGE PERCENTAGE) WITH NO LARGE BARE AREAS. CONTRACTORS MUST MEET VEGETATIVE REQUIREMENT IDENTIFIED BY THE ENGINEER WITHIN THE CONTRACT SPECIFICATION, OR THE HIGHEST REQUIREMENT.

#### SPOIL/FILL MANAGEMENT

ALL SOIL STOCKPILE, EXCAVATION SPOIL MATERIAL, AND ON-SITE SPOIL DISPOSAL AREAS SHALL BE MANAGED BY THE CONTRACTOR IN A MANNER THAT WILL MINIMIZE OR ATTEMPT TO ELIMINATE THE AMOUNT OF SEDIMENT THAT MAY MAY ENTER RECEIVING WATERS AND SHALL NOT BE LOCATED IN ANY WETLAND, FLOODPLAIN, STREAMBED, DITCH, OR OTHER SIMILAR WATER FEATURE OR

#### OFF-SITE VEHICLE TRACKING

OFF-SITE VEHICLE TRACKING OF SOIL BY VEHICLES AND EQUIPMENT SHALL BE MINIMIZED AND CONTROLLED BY THE CONTRACTOR. SOIL SHALL BE REMOVED FROM SITE ROADWAYS, ENTRANCE, AND ACCESS ROADS AS NECESSARY TO PREVENT SEDIMENT FROM ENTERING RECEIVING WATERS.

DUST WILL BE CONTROLLED BY PERIODIC WETTING WITH WATER TRUCKS DURING DRY PERIODS.

#### DEWATERING AND NON-STORMWATER DISCHARGES

ANY NON-STORMWATER DISCHARGES FROM THE CONSTRUCTION SITE WILL BE CONTROLLED AND MANAGED BY THE CONTRACTOR IN COMPLIANCE WITH ALL TCEQ AND LOCAL WATER QUALITY DISCHARGE REQUIREMNETS, INCLUDING BUT NOT LIMITED TO 30 TAC 307, SURFACE WATER QUALITY STANDARDS FOR THE STATE OF TEXAS.

THE FOLLOWING NON-STORM WATER DISCHARGES FROM CONSTRUCTION ACTIVITIES ARE ACCEPTABLE:

- 1. DISCHARGES FROM FIRE FIGHTING ACTIVITIES
- FIRE HYDRANT FLUSHINGS. 3. VEHICLE, EXTERNAL BUILDING, AND PAVEMENT WASH WATER WHERE DETERGENTS AND SOAPS ARE NOT USED AND WHERE SPILLS OR LEAKS OF TOXIC OR HAZARDOUS MATERIALS HAVE NOT OCCURRED (UNLESS SPILLED MATERIALS HAVE BEEN REMOVED; AND IF LOCAL STATE, OR FEDERAL REGULATIONS ARE APPLICABLE, THE MATERIALS ARE REMOVED ACCORDING TO THOSE REGULATIONS), AND WHERE THE PURPOSE IS TO REMOVE MUD, DIRT, AND DUST.
- 4. WATER USED TO CONTROL DUST. 5. POTABLE WATER SOURCES INCLUDING WATERLINE FLUSHINGS.
- AIR CONDITIONING CONDENSATE.
- 7. UNCONTAMINATED GROUND WATER OR SPRING WATER, INCLUDING FOUNDATION OR FOOTING DRAINS WHERE FLOWS ARE NOT CONTAMINATED WITH INDUSTRIAL MATERIALS SUCH AS SOLVENTS OR OTHER POLLUTANTS.

NON-STORM WATER DISCHARGES WILL, AT A MINIMUM, FLOW THROUGH A SILT FENCE, OR OTHER SUITABLE STRUCTURAL CONTROLS, AND NATURAL VEGETATION (IF AVAILABLE) PRIOR TO LEAVING THE SITE, AS NECESSARY TO MEET COMPLIANCE REQUIREMENTS WITH ALL STATE AND LOCAL WATER QUALITY DISCHARGE REQUIREMENTS, INCLUDING BUT NOT LIMITED TO 30 TAC 307 OR 26 TWC 121, SURFACE WATER QUALITY STANDARDS AND WATER QUALITY CONTROL FRO THE STATE OF TEXAS RESPECTIVELY.

#### INSPECTION AND MAINTENANCE PROCEDURES

THE FOLLOWING PROCEDURES WILL BE USED TO INSPECT AND MAINTAIN EROSION AND SEDIMENT CONTROLS ON THE CONSTRUCTION SITE.

ALL CONTROLS WILL BE INSPECTED BY THE CONTRACTOR AT LEASAT ONCE PER WEEK ON A SPECIFIC DAY OF THE WEEK SELECTED BY THE CONTRACTOR AT BEGINNING OF PROJECT. (I.E. EACH MONDAY).

AN INSPECTION AND MAINTENANCE REPORT (SEE COPY OF 1 IN SWPPP) WILL BE PERFORMED AND DOCUMENTED DURING EACH WEEKLY INSPECTION. EACH INSPECTION REPORT WILL NOTE ANY EROSION AND SEDIMENTATION CONTROL ITEMS IN NEED OF REPAIR SUCH ASS: DETACHED SILT FENCE/ROCK BERMS, AND SEDIMENT BUILD UP DEPTH CAPTURED BY CONTROLS, ETCETERA.

WHERE A REPORT DOES <u>NOT</u> IDENTIFY ANY INCIDENTS OF NON-COMPLIANCE NOR ANY ITEMS REQUIRING MAINTENANCE, THE REPORT MUST CONTAIN A CERTIFICATION BY THE CONTRACTORS' CERTIFYING EXECUTIVE OFFICER THAT THIS FACILITY OR SITE IS IN COMPLIANCE WITH THE SWPPP AND THE TPDES GENERAL PERMIT (SEE RECORDS SECTION ABOVE). IF THE INSPECTION REPORTS IDENTIFY ITEMS OF NON-COMPLIANCE OR ITEMS THAT REQUIRE MAINTENANCE THEN NO NONE IS REQUIRED TO SIGN OR CERTIFY THE INSPECTION REPORTS.

DIVERSION DIKES, BERMS, OR SWALES WILL BE INSPECTED AND ANY BREACHES OR AREAS WHERE SEDIMENT HAS ESCAPED THE SITE WILL BE NOTED AS WELL.

REPORTS WILL BE ADDRESS CONTROLS THAT FAILED TO OPERATE AS DESIGNED OR PROVED INADEQUATE FOR A PARTICULAR LOCATION AND LOCATIONS WHERE ADDITIONAL MEASURES ARE REQUIRED.

WHEN A CONTROL FAILS TO OPERATE AS DESIGNED, PROVES INADEQUATE FOR A PARTICULAR LOCATION, WHERE ADDITIONAL MEASURES ARE REQUIRED, OR A CONTROL BECOMES DAMAGED TO ESSENTIALLY CAUSE MAJOR REPAIR OR REINSTALLATION, THE CONTRACTOR WILL NOTIFY THE ENGINEER AND THE OWNER IMMEDIATELY.

SEDIMENT BASINS WILL BE INSPECTED FOR DEPTH OF SEDIMENT.

QUALIFICATIONS OF THE INSPECTOR THE CONTRACTOR WILL SELECT, AND TRAIN AS NECESSARY, DESIGNATED PERSONNEL RESPONSIBLE FOR THE INSPECTION, REPAIR, SEDIMENT REMOVAL, AND ANY OTHER RELATED MAINTENANCE REQUIRED FOR KEEPING EROSION AND SEDIMENT CONTROLS IN GOOD WORKING ORDER. THE INSPECTION PERSONNEL MUST BE FAMILIAR WITH SWPPP. THE CONTRACTOR SHALL COMPLY WITH THE INSPECTION REQUIREMENTS SPECIFIED. IN THE TPDES PERMIT IN SECTION VI

#### EROSION CONTROL NOTES

- 1. THE CONTRACTOR SHALL INSTALL EROSION/SEDIMENTATION CONTROLS AND TREE/NATURAL AREA PROTECTIVE FENCING PRIOR TO ANY SITE PREPARATION WORK (CLEARING, GRUBBING OR EXCAVATION)
- 2. THE PLACEMENT OF EROSION/SEDIMENTATION CONTROLS SHALL BE IN ACCORDANCE WITH THE ENVIRONMENTAL CRITERIA MANUAL AND THE APPROVED EROSION AND SEDIMENTATION CONTROL PLAN. THE CITY OF CEDAR PARK ESC PLAN SHALL BE CONSULTED AND USED AS THE BASIS FOR A TPDES REQUIRED SWPPP. IF A SWPPP IS REQUIRED, IT SHALL BE AVAILABLE FOR REVIEW BY THE CITY OF CEDAR PARK ENVIRONMENTAL INSPECTOR AT ALL TIMES DURING CONSTRUCTION, INCLUDING AT THE PRE-CONSTRUCTION MEETING. THE CHECKLIST BELOW CONTAINS THE BASIC ELEMENTS THAT SHALL BE REVIEWED FOR PERMIT APPROVAL BY CITY OF CEDAR PARK ENVIRONMENTAL PLAN REVIEWERS AS WELL AS CITY OF CEDAR PARK ENVIRONMENTAL INSPECTORS.
- 3. THE PLACEMENT OF TREE/NATURAL AREA PROTECTIVE FENCING SHALL BE IN ACCORDANCE WITH THE STANDARD NOTES FOR TREE AND NATURAL AREA PROTECTION AND THE APPROVED GRADING/TREE AND NATURAL AREA
- 4. A PRE-CONSTRUCTION CONFERENCE SHALL BE HELD ON-SITE WITH THE CONTRACTOR, DESIGN ENGINEER/PERMIT APPLICANT AND CITY INSPECTOR AFTER INSTALLATION OF THE EROSION/SEDIMENTATION CONTROLS AND TREE/NATURAL AREA PROTECTION MEASURES AND PRIOR TO BEGINNING ANY SITE PREPARATION WORK.
- 5. ANY MAJOR VARIATION IN MATERIALS OR LOCATIONS OF CONTROLS OR FENCES FROM THOSE SHOWN ON THE APPROVED PLANS WILL REQUIRE A REVISION AND MUST BE APPROVED BY THE REVIEWING ENGINEER. ENVIRONMENTAL SPECIALIST OR CITY INSPECTOR AS APPROPRIATE. MINOR CHANGES TO BE MADE AS FIELD REVISIONS TO THE EROSION AND SEDIMENTATION CONTROL PLAN MAY BE REQUIRED BY THE CITY OR ENGINEER INSPECTOR DURING THE COURSE OF CONSTRUCTION TO CORRECT CONTROL INADEQUACIES.
- SIGNIFICANT RAINFALL EVENTS TO INSURE THAT THEY ARE FUNCTIONING PROPERLY. THE PERSON(S) RESPONSIBLE FOR MAINTENANCE OF CONTROLS AND FENCES SHALL IMMEDIATELY MAKE ANY NECESSARY REPAIRS TO DAMAGED AREAS. SILT ACCUMULATION AT CONTROLS MUST BE REMOVED WHEN THE DEPTH REACHES SIX (6) INCHES. 7. PRIOR TO FINAL ACCEPTANCE BY THE CITY, HAUL ROADS AND WATERWAY CROSSINGS CONSTRUCTED FOR TEMPORARY CONTRACTOR ACCESS MUST BE REMOVED, ACCUMULATED SEDIMENT REMOVED FROM THE WATERWAY AND THE AREA RESTORED TO THE ORIGINAL GRADE AND REVEGETATED. ALL LAND CLEARING DEBRIS SHALL BE

6. THE CONTRACTOR IS REQUIRED TO INSPECT THE CONTROLS AND FENCES AT WEEKLY INTERVALS AND AFTER

- DISPOSED OF IN APPROVED SPOIL DISPOSAL SITES. 8. ALL WORK MUST STOP IF A VOID IN THE ROCK SUBSTRATE IS DISCOVERED WHICH IS; ONE SQUARE FOOT IN TOTAL AREA; BLOWS AIR FROM WITHIN THE SUBSTRATE AND/OR CONSISTENTLY RECEIVES WATER DURING ANY RAIN EVENT. AT THIS TIME IT IS THE RESPONSIBILITY OF THE PROJECT MANAGER TO IMMEDIATELY CONTACT A CITY OF LEANDER INSPECTOR FOR FURTHER INVESTIGATION.
- 9. TEMPORARY AND PERMANENT EROSION CONTROL: ALL DISTURBED AREAS SHALL BE RESTORED AS NOTED BELOW. PERMANENT CONTROLS MAY CONSIST OF ROCK BERMS, SWALES, AND RE-VEGATATION. PERMANENT WARM SEASON VEGETATION WILL A. ALL DISTURBED AREAS TO BE REVEGETATED ARE REQUIRED TO PLACE A MINIMUM OF SIX (6) INCHES OF TOPSOIL [SEE STANDARD SPECIFICATION ITEM NO. 601S.3(A)]. DO NOT ADD TOPSOIL WITHIN THE CRITICAL ROOT ZONE OF EXISTING TREES. THE TOPSOIL SHALL BE COMPOSED OF 4 PARTS OF SOIL MIXED WITH 1 PART COMPOST, BY VOLUME. THE COMPOST SHALL MEET THE DEFINITION OF COMPOST AS DEFINED BY TXDOT SPECIFICATION ITEM 161. THE SOIL SHALL BE LOCALLY AVAILABLE NATIVE SOIL THAT MEETS THE FOLLOWING SPECIFICATIONS:
  - SHALL BE FREE OF TRASH, WEEDS, DELETERIOUS MATERIALS, ROCKS, AND DEBRIS.

  - SOIL TO BE A LOAMY MATERIAL THAT MEETS THE REQUIREMENTS OF THE TABLE BELOW IN ACCORDANCE WITH THE USDA TEXTURAL TRIANGLE, SOIL KNOWN LOCALLY AS "RED DEATH" IS NOT AN ALLOWABLE SOIL. TEXTURAL COMPOSITION SHALL MEET THE FOLLOWING CRITERIA:

TEXTURAL CLASS	MINIMUM	MAXIMUM
CLAY	5%	50%
SILT	10%	50%
SAND	15%	67%

- AN OWNER/ENGINEER MAY PROPOSE USE OF ONSITE SALVAGED TOPSOIL WHICH DOES NOT MEET THE SOIL TEXTURE CLASS REQUIRED ABOVE BY PROVIDING A SOIL ANALYSIS AND A WRITTEN STATEMENT FROM A QUALIFIED PROFESSIONAL IN SOILS, LANDSCAPE ARCHITECTURE, OR AGRONOMY INDICATING THE ONSITE TOPSOIL WILL PROVIDE AN EQUIVALENT GROWTH MEDIA AND SPECIFYING WHAT, IF ANY, SOIL AMENDMENTS ARE
- SOIL AMENDMENTS SHALL BE WORKED INTO THE EXISTING ONSITE TOPSOIL WITH A DISC OR TILLER TO CREATE A

TOPSOIL SALVAGED FROM THE EXISTING SITE MAY OFTEN BE USED, BUT IT SHOULD MEET THE SAME STANDARDS AS SET FORTH IN THESE STANDARDS.

THE VEGETATIVE STABILIZATION OF AREAS DISTURBED BY CONSTRUCTION SHALL BE AS FOLLOWS:

#### TEMPORARY VEGETATIVE STABILIZATION:

CRITERIA MANUAL.

- 1. FROM SEPTEMBER 15 TO MARCH 1, SEEDING SHALL BE WITH COOL SEASON COVER CROPS (WHEAT AT 0.5 POUNDS PER 1000 SF, OATS AT 0.5 POUNDS PER 1000 SF, CEREAL RYE GRAIN AT 0.5 POUNDS PER 1000 SF) WITH A TOTAL RATE OF 1.5 POUNDS PER 1000 SF. COOL SEASON COVER CROPS ARE NOT PERMANENT EROSION CONTROL.
- 2. FROM MARCH 2 TO SEPTEMBER 14, SEEDING SHALL BE WITH BUFFALO AT A RATE OF 1 POUNDS PER 1000 SF. A. FERTILIZER SHALL BE WATER SOLUBLE WITH AN ANALYSIS OF 15-15-15 TO BE APPLIED ONCE AT PLANTING AND ONCE
- DURING THE PERIOD OF ESTABLISHMENT AT A RATE OF 1/2 POUND PER 1000 SF. B. HYDROMULCH SHALL COMPLY WITH TABLE1, BELOW.
- C. TEMPORARY EROSION CONTROL SHALL BE ACCEPTABLE WHEN THE GRASS HAS GROWN AT LEAST 1.5 INCHES HIGH WITH 95% COVERAGE, PROVIDED NO BARE SPOTS LARGER THAN 16 SQUARE FEET EXIST. D. WHEN REQUIRED, NATIVE GRASS SEEDING SHALL COMPLY WITH REQUIREMENTS OF THE CITY OF AUSTIN ENVIRONMENTAL

TABLE 1: HYDROMULCHING FOR TEMPORARY VEGETATIVE STABILIZATION

MATERIAL	DESCRIPTION	LONGEVITY	TYPICAL APPLICATIONS	LONGEVITY
100% OR ANY BLEND OF WOOD, CELLULOSE, STRAW, AND/OR COTTON PLANT MATERIAL (EXCEPT NO MULCH SHALL EXCEED 30% PAPER)	70% OR GREATER WOOD/STRAW 30% OR LESS PAPER OR NATURAL FIBERS	0-3 MONTH	MODERATE SLOPES; FROM FLAT TO 3:1	MODERATE SLOPES; FROM FLAT TO 3:1

PERMANENT VEGETATIVE STABILIZATION:

- 1. FROM SEPTEMBER 15 TO MARCH 1, SEEDING IS CONSIDERED TO BE TEMPORARY STABILIZATION ONLY. IF COOL SEASON COVER CROPS EXIST WHERE PERMANENT VEGETATIVE STABILIZATION IS DESIRED, THE GRASSES SHALL BE MOWED TO A HEIGHT OF LESS THAN ONE-HALF ( $\frac{1}{2}$ ) INCH AND THE AREA SHALL BE RE-SEEDED IN ACCORDANCE WITH 2. BELOW.
- 2. FROM MARCH 2 TO SEPTEMBER 14. SEEDING SHALL BE WITH BUFFALO AT A RATE OF 1 POUND PER 1000 SE WITH A PURITY OF 95% WITH 85% GERMINATION. BUFFALO GRASS IS A WARM SEASON GRASS AND IS CONSIDERED PERMANENT EROSION CONTROL.
- A. FERTILIZER SHALL BE A WATER SOLUBLE WITH AN ANALYSIS OF 15-15-15 TO BE APPLIED ONCE AT PLANTING AND ONCE DURING THE PERIOD OF ESTABLISHMENT AT A RATE OF 1/2 POUND PER 1000 SF.
- HYDROMULCH SHALL COMPLY WITH TABLE 2, BELOW. C. THE PLANTED AREA SHALL BE IRRIGATED OR SPRINKLED IN A MANNER THAT WILL NOT ERODE THE TOPSOIL, BUT WILL SUFFICIENTLY SOAK THE SOIL TO A DEPTH OF SIX INCHES. THE IRRIGATION SHALL OCCUR AT DAILY

INTERVALS (MINIMUM) DURING THE FIRST TWO MONTHS. RAINFALL OCCURRENCES OF 1 INCH OR MORE SHALL

POSTPONE THE WATERING SCHEDULE FOR ONE WEEK D. PERMANENT EROSION CONTROL SHALL BE ACCEPTABLE WHEN THE GRASS HAS GROWN AT LEAST 1.5 INCHES HIGH WITH 95% COVERAGE, PROVIDED NO BARE SPOTS LARGER THAN 16 SQUARE FEET EXIST.

	DESCRIPTION	LONGEVITY
BONDED FIBER MATRIX (BFM)	80% ORGANIC DEFIBRATED FIBERS 10% TACKIFER	6 MONTHS
FIBER REINFORCED MATRIX (FRM)	65% ORGANIC DEFIBRATED FIBERS 25% REINFORCING FIBERS OR LESS 10% TACKIFIER	UP TO 12 MONTHS

11. THE CONTRACTOR SHALL NOT DISPOSE OF SURPLUS EXCAVATED MATERIAL FROM THE SITE WITHOUT NOTIFYING THE CITY INSPECTOR AT LEAST 48 HOURS PRIOR WITH THE LOCATION AND A COPY OF THE PERMIT ISSUED TO RECEIVE THE MATERIAL.

GOODE FAITH M: EST. 2021

CIVIL ENGINEERING AND PLANNING (972) 822 - 1682 TBPE FIRM REGISTRATION NO. F-2266


S OSIO


DATE 06-27-2023

PROJECT NO 23-003.0

DESIGNED BY


JDL CHECKED BY







PLAT DOC NO.

8 of 23








10 of **23** 














THAT THE DOWNSLOPE FACE OF THE TRENCH IS FLAT AND PERPENDICULAR TO THE LINE OF FLOW.

3. THE TRENCH MUST BE A MINIMUM OF 150 mm (6 inches) DEEP AND 150 mm (6 inches) WIDE TO ALLOW FOR THE SILT FENCE FABRIC TO BE LAID IN THE GROUND AND BACKFILLED WITH COMPACTED


4. SILT FENCE FABRIC SHOULD BE SECURELY FASTENED TO EACH STEEL OR WOOD SUPPORT POST OR TO WOVEN WIRE, WHICH IS IN TURN ATTACHED TO THE STEEL OR WOOD FENCE POST.


5. INSPECTION SHALL BE MADE WEEKLY OR AFTER EACH RAINFALL EVENT AND REPAIR OR REPLACEMENT SHALL BE MADE PROMPTY AS NEEDED.


6. SILT FENCE SHALL BE REMOVED WHEN THE SITE IS COMPLETELY STABILIZED SO AS NOT TO BLOCK OR IMPEDE STORM FLOW OR DRAINAGE.


7. ACCUMULATED SILT SHALL BE REMOVED WHEN IT REACHES A DEPTH OF 150 mm (6 inches). THE SILT SHALL BE DISPOSED OF ON AN APPROVED SITE AND IN SUCH A MANNER THAT WILL NOT CONTRIBUTE TO ADDITIONAL SILTATION.

CITY OF AUSTIN WATERSHED PROTECTION DEPARTMENT	SILT FENCE	
RECORD COPY SIGNED BY MORGAN BYARS 09/01/2011 ADOPTED	THE ARCHITECT/ENGINEER ASSUMES RESPONSIBILITY FOR APPROPRIATE USE OF THIS STANDARD.	









**GOODE FAITH** 

CIVIL ENGINEERING AND PLANNING (972) 822 - 1682 TBPE FIRM REGISTRATION NO. F-22664

**D** 

64 1S-

RESPONSIBILITY FOR APPROPRIATE USE OF THIS STANDARD.


DATE 06-27-2023 PROJECT NO. 23-003.0 DESIGNED BY JDL CHECKED BY

ΑG



PLAT DOC NO.

17 of **23** 



12. INVERT OF INLET SHALL BE SLOPED 1:20 WITH FILL CONCRETE SHAPED AS "V"

NOTED ON THE PLANS OR PERMITTED IN WRITING BY THE ENGINEER.

6'-0" MIN- WIDTH MAY VARY TO ACCOMMODATE MULTIPLE DUMPSTERS

FIN. GRADE -

TRASH ENCLOSURE GATES TO SWING

180', PROVIDE DROP ROD RECEIVER

AND OPENED POSITIONS.

HOLES IN CONCRETE AT BOTH CLOSED

405 2X2 INLET

4'-9" MIN.CLEAR OPENING

<u>PLAN VIEW</u>

PAINTED TO MATCH BUILDING.

GARBAGE TRUCK

1. CMU'S MUST BE FINISHED WITH STUCCO OR BRICK VENEER

2. GARBAGE DUMPSTERS ARE LOCATED NO CLOSER TO A ROADWAY

BY A WALL (COMPRISED OF MASONRY COMPATIBLE WITH THE

FOR 90 GALLON ROLL OUT CONTAINER STORED OUTSIDE, IT IS

DUMPSTER ENCLOSURE

4. EXTENDED CONCRETE DUMPSTER SECTION IN FRONT WITH 4,000 PSI

REQUIRED TO BE ENCLOSED BY PRIVACY FENCE.

CONCRETE TO BE 8" THICK WITH #4 @ 12" OCEW.

STRUCTURE OR WOODCRETE) AT LEAST AS HIGH AS THE

THAN THE FRONT WALL OF THE PRINCIPAL STRUCTURE LOCATED

CONTAINER. THE OPEN SIDE TO THE DUMPSTER OR OTHER TRASH

RECEPTACLE IS A GATE CONSTRUCTED OF SOLID WOOD OR METAL. THE DUMPSTER IS ORIENTED FOR PICKUP BY A FRONT LOAD

CLOSEST TO THE ROADWAY. GARBAGE DUMPSTERS ARE SCREENED

SCALE: 1/2" = 1'

13. NO SPLICING OF REINFORCING STEEL SHALL BE PERMITTED UNLESS OTHERWISE

<u>SECTION</u>

ACCESS LID, MIN. 750 mm (30") IN LEAST DIMENSION SEE NOTE 5 SIDEWALL (TYP.) (SERVICE SIDE). SEE NOTE 2. WITH 2 SHUT-OFF VALVES AND BACKFLOW PREVENTER SIDEWALL (TYP.)

NOTES:

1. ALL BACKFLOW PREVENTION ASSEMBLIES SHALL HAVE LAB AND FIELD APPROVAL FROM THE UNIVERSITY OF SOUTHERN CALIFORNIA FOUNDATION FOR CROSS CONNECTION CONTROL AND HYDRAULIC RESEARCH.

ALL TEST PORTS SHALL BE DIRECTED UPWARD AND PLUGGED. TEST PORTS ARE LOCATED ON SERVICE SIDE. PLUGS SHALL BE NON-FERROUS. BACKFLOW PREVENTION ASSEMBLIES SHALL BE INSTALLED IN THE UPRIGHT

HORIZONTAL POSITION, UNLESS OTHERWISE APPROVED. BACKFLOW PREVENTION ASSEMBLIES SHALL NOT BE ROTATED ON THEIR AXIS. CLEARANCE SHALL BE AS INDICATED, AND IN THE STANDARD CROSS CONNECTION

ORDINANCES AND UCM. ACCESS OPENING MUST BE LARGE ENOUGH TO REMOVE LARGEST PORTION OF BACKFLOW PREVENTER, BUT NOT LESS THAN 750 mm (30") IN LEAST DIMENSION.

TEST AND MAINTENANCE REPORT SHALL BE RECEIVED BY AUSTIN WATER UTILITY'S SPECIAL SERVICE DIVISION WITHIN 5 DAYS AFTER BEING INSTALLED.

VAULT SHALL NOT BE INSTALLED IN TRAFFIC AREA. VAULT DEPTH MAY NOT EXCEED 1.8m (72"), BOTTOM OF LID TO TOP OF FLOOR.
HAND WHEELS SHALL BE HORIZONTALLY LOCATED WITHIN 300mm (12") OF ACCESS OPENING. FOR ACCESS DOORS SEE SPL WW-614 OR APPROVED EQUAL (H20 LOADING

FOR VAULT SEE SPL WW-298 OR APPROVED EQUAL (H20 LOADING REQUIRED). VAULT PIPE WALL VOIDS SHALL BE SEALED WITH NON-SHRINK GROUT OR SEALANT PER SPL WW-148A OR APPROVED EQUAL.

THE TOP OF THE METER VAULT SHALL BE AT AN ELEVATION SUCH THAT THE SURROUNDING GROUND SLOPES AWAY FROM THE VAULT. ADDITIONAL DRAINAGE CONSIDERATION SUCH AS CONNECTION OF VAULT TO STORM SEWER, LATERAL DRAIN LINES FROM GRAVEL BED OR OTHER MEANS SHALL BE REQUIRED IF CONDITIONS CAUSE WATER TO COLLECT IN VAULT.

- SEE NOTE 6 -TYPICAL STRIPING STRIPING AT BARRIER CURB

1. ALL FIRE LANE STRIPING SHALL COMPLY WITH THE CURRENT INTERNATIONAL FIRE CODE, AS ADOPTED BY THE CITY OF LEANDER, AND CITY OF LEANDER CODE OF ORDINANCES.

2. FIRE LANES SHALL BE CONTINUOUSLY MARKED BY RED TRAFFIC PAINT THAT IS MINIMUM SIX INCHES (6") IN WIDTH TO SHOW THE BOUNDARIES OF THE LANE.

3. "FIRE LANE - TOW AWAY ZONE" SHALL APPEAR IN FOUR INCH (4") TYPE D WHITE BLOCK LETTERS AT TWENTY-FIVE FOOT (25') INTERVALS, OR LESS, ON THE RED BORDER MARKINGS ALONG BOTH SIDES OF THE FIRE LANE.

4. WHERE A 6" BARRIER CURB EXISTS, THE FIRE LANE STRIPING SHALL BE ON BOTH THE VERTICAL FACE OF THE CURB AND TOP OF CURB., "FIRE LANE - TOW AWAY ZONE" SHALL BE MARKED IN 4" WHITE BLOCK LETTERS ON FACE OF CURB ONLY. 5. WHERE A FIRE LANE IS ADJACENT TO PARKING SPACES THE FIRE LANE STRIPING SHALL BE AN 8" RED STRIPE PAINTED ON THE DRIVE SURFACE WITH 4" WHITE LETTERS STATING "FIRE LANE NO PARKING TOW-AWAY ZONE." FIRE LANE STRIPING SHALL EXTEND BEHIND ALL PARKING SPACES.

6. WHERE A FIRE HYDRANT, FIRE DEPARTMENT CONNECTION, OR OTHER FIRE PROTECTION EQUIPMENT IS LOCATED ON A FIRE LANE, THE FIRE LANE SHALL BE A MINIMUM OF TWENTY-SIX FEET (26') IN WIDTH, EXCLUSIVE OF SHOULDERS. THE ARCHITECT/ENGINEER ASSUMES RESPONSIBILITY FOR APPROPRIATE USE OF THIS STANDARD, DRAWING NOT TO SCALE.

EXIST. SEWER PIPE

15" TO 60" DIA

City Of Leander, Texas

DETAIL #501-2

FIRE LANE STRIPING

BARREL SECTION


SHELF AT 1"/FT SLOPE

APPLY CONCRETE BONDER BETWEEN

NEW AND EXISTING CONCRETE

TOP OF CONCRETE

KOR-N-SEAL



SIDE ELEVATION SECTION

CITY OF AUSTIN

GROUT BOTTOM TO ALLOW-FLOW TO OUTLET PIPE

12 6 8 18

12" 3'-0" 32

12" 2'=10" 15

THE ARCHITECT/ENGINEER ASSUMES

RESPONSIBILITY FOR APPROPRIATE USE OF THIS STANDARD.

TOTAL WEIGHT --- 91 LB.


508-11

REINFORCING STEEL SCHEDULE

4 4 12 5 2 14

4 5 12" 2=10" 12

BAR OTY SIZE SPACING LENGTH WEIGHT



TRE MARSHAL


3. SIGNS SHALL BE PERMANENTLY AFFIXED TO A STATIONARY POST AND THE BOTTOM OF THE SIGN ASSEMBLY SHALL BE SIX FEET, SIX INCHES (6'-6") ABOVE FINISHED GRADE. 4. SIGNS SHALL BE SPACED NOT MORE THAN 35' APART.

5. SIGNS MAY BE INSTALLED ON PERMANENT BUILDINGS OR WALLS AS APPROVED BY THE FIRE CODE OFFICIAL. 6. IF THE SIGN IS AT THE END OF A FIRE ZONE, THE SIGN SHALL HAVE A SINGLE-HEADED ARROW POINTING IN THE DIRECTION OF THE ZONE. IF THE SIGN IS AT AN INTERMEDIATE POINT IN THE ZONE, THE SIGN SHALL HAVE A DOUBLE-HEADED ARROW POINTING IN BOTH DIRECTIONS.

7. FIRE LANE SIGNS SHALL BE POSTED ON BOTH SIDES OF FIRE APPARATUS ACCESS ROADS THAT ARE TWENTY FEET (20) TO TWENTY-SIX FEET (26') WIDE.

8. FIRE LANE SIGNS SHALL BE POSTED ON ONE SIDE OF FIRE APPARATUS ACCESS ROADS MORE THAN TWENTY-SIX FEET (26') WIDE AND LESS THAN THIRTY-TWO FEET (32') WIDE. \*THE ARCHITECT/ENGINEER ASSUMES RESPONSIBILITY FOR APPROPRIATE USE OF THIS STANDARD. DRAWING NOT TO SCALE. City Of Leander, Texas DETAIL #501-1

FIRE LANE SIGN ASSEMBLY



CONTINUUS SWELL-SEAL PRE-CAST WATERSTOP-CAULK BARREL SECTION KOR-N-SEAL APPLY CONCRETE SONDER BETWEEN NEW AND PRECAST CONCRETE PLAN VIEW

DOGHOUSE MANHOLE DETAIL

PLAT DOC NO.

21 of **23** 

**GOODE FAITH** CIVIL ENGINEERING AND PLANNING (972) 822 - 1682 TBPE FIRM REGISTRATION NO. F-22664


5

4

DET

S

DATE 06-27-2023 PROJECT NO. 23-003.0 DESIGNED BY JDL CHECKED BY ΑG





#### ATTACHMENT I - 20% OR LESS IMPERVIOUS COVER DECLARATION

Not Applicable.

This project is not multi-family, a school, residential or small business and greater than 20% impervious cover is proposed for the site.



#### ATTACHMENT J – BMPS FOR UPGRADIENT STORMWATER


Not Applicable.

Storm water from off-site is minimal. Any offsite storm water will not be treated through the existing sedimentation filtration pond or the proposed vegetative filter strip.



#### ATTACHMENT K - BMPS FOR ON-SITE STORMWATER

The existing sedimentation filtration pond of the approved plans is located on Lot P2 in the southeast corner. The pond was sized for a drainage area of 11.78 acres with 9.2 acres of impervious cover. Lot P2 (9.55 acres of approved CZP) was allotted 76% or ~7.3 acres of impervious cover. Lot P1 (proposed commercial project site) was allotted 85% or ~1.9 acres of impervious cover. Proposed Lot P1 has 1.73 acres of impervious cover flowing to the existing sedimentation filtration pond.



**Existing Sedimentation Filtration Pond** 

The existing best management practices (BMPs) will treat at least 80% of the increase in total suspended solids (TSS) for the site. The sedimentation filtration pond has been designed in accordance with the TCEQ Technical Guidance Manual (TGM) RG-348.



#### **ATTACHMENT M – CONSTRUCTION PLANS**

SEE ATTACHMENT C-CURRENT SITE PLAN OF THE APPROVED PROJECT OF MODIFICATION OF A PREVIOUSLY APPROVED CONTRIBUTING ZONE PLAN.

SHEETS 15 – 20 OF SITE PLAN OF THE APPROVED PROJECT (PAGES 32-38 OF CZP)

CURRENT CONSTRUCTION PLANS ATTACHED SEPARATELY.



#### ATTACHMENT N - INSPECTION, MAINTENANCE, REPAIR AND RETROFIT PLAN

A Storm Water Pollution Prevention Plan (SWPPP) prepared by Goode Faith Engineering for this project details the maintenance of temporary BMPs during construction. Please refer to this document for specifics regarding the maintenance requirements for the temporary BMPs on this site.

Maintenance of the storm water controls and facilities on this site is required by the Owner and is important for the continuous treatment of storm water treatment of the development. A copy of the previously approved and signed maintenance plan is in the following pages and will continue to serve as the maintenance plan for the sedimentation filtration pond.



#### **Contributing Zone Application (TCEQ-10257)**

#### Attachment N Inspection, Maintenance, Repair, and Retrofit Plan

The owner will be responsible for inspection, maintenance and repair for the proposed sedimentation filtration ponds associated with the Leander Station Multi-Family project.

The City of Leander defers water quality control to the TCEQ's rules. Per the TCEQ's Complying with the Edwards Aquifer Rules, Water quality controls required for commercial and multi-family development shall be maintained by the property owner.

#### Sand Filter Sytems (See Section 3.5.9).

- a. Regular, routine maintenance is essential to effective, long-lasting performance of sand filters. Neglect or failure to service the filters on a regular basis will lead to poor performance and eventual costly repairs. It is recommended that sand filter BMPs be inspected on a quarterly basis and after large storms for the first year of operation. This intensive monitoring is intended to ensure proper operation and provide maintenance personnel with a feel for the operational characteristics of the filter. Subsequent inspections can be limited to semi-annually or more often if deemed necessary (Young et al., 1996). Certain construction and maintenance practices are essential to efficient operation of the filter. The biggest threat to any filtering system is exposure to heavy sediment loads that clog the filter media. Construction within the watershed should be complete prior to exposing the filter to stormwater runoff. All exposed areas should be stabilized to minimize sediment loads. Runoff from any unstabilized construction areas should be treated via a separate sediment system that bypasses the filter media. Another important consideration in constructing the filter bed is to ensure that the top of the media is completely level. The filter design is based on the use of the entire filter media surface area; a sloped filter surface would result in disproportionate use of the filter media.
- b. Inspections. BMP facilities must be inspected at least twice a year (once during or immediately following wet weather) to evaluate facility operation. During each inspection, erosion areas inside and downstream of the BMP must be identified and repaired or revegetated immediately. With each inspection, any damage to the structural elements of the system (pipes, concrete drainage structures, retaining walls, etc.) must be identified and repaired immediately. Cracks, voids and undermining should be patched/filled to prevent additional structural damage. Trees and root systems should be removed to prevent growth in cracks and joints that can cause structural damage.



- c. Sediment Removal. Remove sediment from the inlet structure and sedimentation chamber when sediment buildup reaches a depth of 6 inches or when the proper functioning of inlet and outlet structures is impaired. Sediment should be cleared from the inlet structure at least every year and from the sedimentation basin at least every 5 years.
- d. Media Replacement. Maintenance of the filter media is necessary when the drawdown time exceeds 48 hours. When this occurs, the upper layer of sand should be removed and replaced with new material meeting the original specifications. Any discolored sand should also be removed and replaced. In filters that have been regularly maintained, this should be limited to the top 2 to 3 inches.
- e. Debris and Litter Removal. Debris and litter will accumulate near the sedimentation basin outlet device and should be removed during regular mowing operations and inspections. Particular attention should be paid to floating debris that can eventually clog the control device or riser.
- f. Filter Underdrain. Clean underdrain piping network to remove any sediment buildup as needed to maintain design drawdown time.
- g. Mowing. Grass areas in and around sand filters must be mowed at least twice annually to limit vegetation height to 18 inches. More frequent mowing to maintain aesthetic appeal may be necessary in landscaped areas. Vegetation on the pond embankments should be mowed as appropriate to prevent the establishment of woody vegetation.

Zah	7/7/20
Signature of Customer	Date
Rom 3 Hamp	11/04/20
Signature of Agent	Date

#### STORMWATER POLLUTION PREVENTION PLAN

SHOPS AT HERO WAY

PREPARED FOR: TRANSIT VILLAGE INVESTMENTS LTD

MAY 2023

#### **STORMWATER POLLUTION PREVENTION PLAN**

(T.P.D.E.S.GENERALPERMIT-TXR150000)



#### **SHOPS AT HERO WAY**

SITE OPERATOR	
( Responsible Party)	
COVERAGE AREA	
NOI APPLICATIONDATE	
AUTHORIZATION #	
SITE OPERATOR	
COVERAGE AREA	
NOI APPLICATIONDATE	
AUTHORIZATION #	
SITE OPERATOR	
COVERAGE AREA	
NOI APPLICATIONDATE	
AUTHORIZATION #	

#### **TABLE OF CONTENTS**

- 1. PLAN IMPLEMENTATION CHECKLIST
- 2. STORM WATER POLLUTION PREVENTION PLAN (SWPPP)
- 3. LOCATION MAP Exhibit 1
- 4. SWPPP PLAN Exhibit 2
- 5. PROJECT MILESTONE DATES Exhibit 3
- 6. ON-SITE MATERIALS LIST Exhibit 4
- 7. RESPONSIBLEPARTYFORM-Exhibit5
- 8. INSPECTION REPORT FORM Exhibit 6
- 9. PLAN MODIFICATIONS (IF NECESSARY)
- 10. CONSTRUCTION SITE NOTICES Exhibit 7
- 11. TCEQ NOTICE OF INTENT (NOI) Exhibit 8
- 12. TCEQ NOTICE OF TERMINATION (NOT) Exhibit 9
- 13. TDPES GENERAL PERMIT (TXR150000) Exhibit 10
- 14. WETLAND MAP Exhibit 11

PLAN IMPLEMENTATION CHECKLIST

#### PLAN IMPLEMENTATION CHECKLIST

- 1. Definition of Construction Site Operator "The person(s) having operational control over construction plans and specifications to the extent necessary to meet the requirements and conditions of this general permit or ... the person(s) having day to day operational control of those activities at the construction site which are necessary to ensure compliance with a storm water pollution prevention plan..." (TPDES General Permit (TXR150000), pg. 4)
- 2. All Notices of Intent (NOI), Notices of Termination (NOT), Storm Water Pollution Prevention Plans (SWPPP) reports, certification, or information either submitted to the Director, the operator of a large or medium municipal separate storm sewer system, or that this permit required and maintained by the permittee shall be signed by a responsible corporate officer, by a general partner or proprietor, by a principal executive public officer, or by a ranking elected public official.
- 3. At least two (2) days prior to start of construction, the Construction Site Operator must submit a Storm Water TPDES General Permit Notice of Intent (NOI) TCEQ-20022, pg. 1 of 2 by Certified Mail-Return Receipt Requested to:

Texas Commission on Environmental Quality Stormwater & General Permits Team; MC-228 P.O. Box 13087 Austin, Texas 78711-3087

Note:

TCEQ provides instructions for filling out the Notice of Intent (NOI) ~TCEQ-20022-Instructions. These instructions are included in the Notice of Intent Section of this Booklet.

4. An application fee of \$325.00 payable to Texas Commission on Environmental Quality is to be attached to the second page of the Notice of Intent (NOI) – TCEQ-20022, pg. 2 of 2, and submitted separately by Certified Mail-Return Receipt to:

#### By Regular Mail

Texas Commission on Environmental Quality
Financial Administration Division Cashier's Office, MC-214
P.O. Box 13088
Austin, Texas 78711-3088

By Overnight/Express Mail

Texas Commission on Environmental Quality Financial Administration Division Cashier's Office, MC-214 12100 Park 35 Circle Austin, Texas 78753

5. Submit signed copy of NOI – TCEQ-20022, pg. 1 of 2 by Certified Mail – Return Receipt to:

NPDES Coordinator City of Boerne (MS4) P.O. Box 1677 Boerne, Texas 78006

6. The effective date of provisional coverage starts two days from the date the completed NOI is postmarked for delivery to TCEQ. The provisional coverage is removed when the executive director finds the NOI complete, and the project is assigned an authorization number.

#### TPDES - Storm Water Pollution Prevention Plan

- 7. The responsible party shall post a signed copy of NOI TCEQ-20022, pg. 1 of 2 and the SWPPP booklet in a protective covering at a 24 hour readily accessible location at the main entrance of the construction site.
- 8. The responsible party for the SWPPP as well as any additional site operator must sign the cover sheet within the SWPPP booklet.
- 9. The responsible party must implement the SWPPP prior to beginning of construction activities.
- 10. The responsible party shall use "Responsible Party Form" (Exhibit 5) to designate responsibility for pollution prevention measures.
- 11. The responsible party shall use "Inspection Report Form" to designate responsibility to conduct inspections and fill out Inspection Form.
- 12. The responsible party shall ensure the SWPPP provides adequate best management practices (as defined by this permit), covers appropriate areas under Responsible party's control, and all other operators on the site are notified of modifications to the SWPPP.
- 13. The responsible party shall in a timely fashion, sign and date, the SWPPP booklet with any modifications to design, construction, operation, maintenance, or significant change not previously addressed. Any inspection should be logged into the booklet and any controls found ineffective should be modified and noted on the SWPPP.
- 14. The responsible party should initiate the Notice of Change (NOC) to TCEQ and the MS4 operator within 14 days after discovery if incorrect information was submitted or if relevant facts were not included.
- 15. The responsible party should initiate a Notice of Termination (NOT) TCEQ-20023 to TCEQ and the MS4 operator effective at midnight of the postmarked date when and if:
  - a. Final stabilization had been achieved for areas of responsibility
  - b. Another permitted operator assumes control of the site
  - c. All temporary structural controls have been removed, are scheduled for removal, or are transferred to another permitted operator.
- 16. The responsible party should pay special attention to Parts IV thru VII of the general permit TXR150000, which describe effluent limitations, reporting requirements, retention records, standard permit conditions, and fee structure.
- 17. The Responsible party for the SWPPP shall be aware of <u>all</u> terms and conditions of the TPDES TXR150000 general permit. The information provided in this checklist is for convenience purposes only and does not amend or limit any non-highlighted provision of the general permit. The responsible party should thoroughly read the general permit and be cognizant of their obligations as set forth in the general permit.

STORM WATER POLLUTION PREVENTIONPLAN (SWPPP)

#### **INTRODUCTION**

This Storm Water Pollution Prevention Plan is prepared for TRANSIT VILLAGE INVESTMENTS LTD – SHOPS AT HERO WAY, per the Texas Pollution Discharge Elimination System (TPDES) which implements the federal National Pollutant Discharge Elimination System (NPDES) in the state of Texas.

#### **SITE DESCRIPTION**

Project Name: SHOPS AT HERO WAY

Project Street Address: 1561 HERO WAY LEANDER, TX 78641

Nature of Construction Activity: Site clearing, grading and construction of drives, parking, sewer lines, water lines, storm water inlets and stormwater lines, utilities, and retail/coffee shop building.

#### Potential Pollutant Sources:

- a) Soil erosion due to clearing of site for drainage and pavement
- b) Oil, grease, fuel & hydraulic fluid contamination from construction vehicle drippings
- c) Miscellaneous trash and litter from construction workers and material wrappings
- d) Construction debris
- e) Concrete truck washout
- f) Hydrocarbons from asphalt paving operations

Proposed Construction Start Date: 2023-September-1

Proposed Construction End Date: 2024-December-1

#### Sequence of Major Activities:

- a) Installation of temporary stabilized construction entrance/exit
- b) Installation of erosion and sedimentation controls
- c) Site clearing
- d) Connect to public mains: sanitary sewer and water
- e) Install utilities, install fill, grade to subgrade
- f) Install traffic control for pavement and utility connections
- g) Install pavement for fire access to building
- h) Begin building and vertical construction
- i) Finish pavement and drainage infrastructure installation
- j) Install landscape and irrigation, revegetation, and striping
- k) Clean out regional pond
- *l)* Removal of temporary erosion and sedimentation controls
- m) Site clean up

#### TPDES - Storm Water Pollution Prevention Plan

Total Site Area (Acres): 2.23 acres

Total Site Area to be Disturbed (Acres): +/- 1.97 acrea

Pre-Construction Runoff Coefficient: 84

Post Construction Runoff Coefficient: 94

Soil Types: Doss Silty Clay, moist, 1 to 5 percent slopes, ~ 63% of site Crawford clay 1 to 3 percent slopes, ~ 37% of site

Industrial Activity Discharges: None

Receiving Water: North Brushy Creek

Wetlands: No -

Ref. Exhibit 11 - Wetland Map Overlay

National Register of Historic Places: None

Edwards Aquifer Recharge or Contributing Zone: Yes

Water Pollution Abatement Plan (WPAP): No

- 1) EXHIBIT 1 General Location Map
- 2) EXHIBIT 2
  - a) Site Plan illustrating the SWPPP:
    - i) Drainage patterns
    - ii) Approximate post-grading slopes
    - iii) Areas of soil disturbance
    - iv) Location of all major structural and non-structural controls either planned or in place
    - v) Locations of off-site material, waste, borrow, fill, or equipment storage
    - vi) Surface waters (including wetlands) either adjacent or in close proximity
    - vii) Storm water discharges to a surface water body
  - b) Typical Details:
    - i) Temporary Construction Entrance/Exit
    - ii) Silt Fence
    - iii) Rock Berm
    - iv) Construction Staging Area
    - v) Concrete washout pit

#### **CONTROLS**

The sequence of major work activities on the site will be divided into two phases: preparation and construction. Site preparation consists of installing temporary best management practices (BMPs). Site preparation will consist of clearing, grubbing, demolition, and trenching. This work, which is the initiation of all activity on the project, will disturb the largest amount of soil. Therefore, before any of this work can begin, the site contractor will be responsible for the installation and maintenance of control measures as located and illustrated on Exhibit 2. These measures are designed to prevent eroded soil from leaving the site.

Construction activities include installation of temporary BMPs and clearing. The construction contractor will be responsible for the installation of all control measures as located and illustrated on Exhibit 2. These controls are intended to prevent eroded soil, trash, and construction debris from leaving the site.

It is to be understood that modifications to the Storm Water Pollution Prevention Plan may have to be made in the field to adjust for field conditions and to provide the intended effect. All changes to the plan must be shown on Exhibit 2, dated, and signed by the responsible party.

#### 1) EROSION AND SEDIMENT CONTROLS

#### a) GOALS AND CRITERIA

- i) Erosion and sediment controls are designed to retain sediment on-site to the extent possible.
- ii) All control measures must be properly installed and maintained in accordance with manufacturer's specifications and with project specifications.
- iii) Sediment must be removed from sediment traps and basins when design capacity has been reduced by 50%.
- iv) If sediment escapes the construction site, the off-site accumulations of sediment must be removed at a frequency to minimize further negative effects, and whenever feasible, prior to the next storm event.
- v) Litter, construction debris, and construction chemicals exposed to storm water shall be prevented from becoming a pollutant source for storm water discharges.
- vi) Off-site material storage areas such as construction staging areas, soil stockpiles, and borrow areas used solely by the project are considered part of the project for Storm Water Pollution Prevention Plan purposes.

#### b) STABILIZATION PRACTICES

Stabilization practices may include but are not limited to: establishment of temporary vegetation, establishment of permanent vegetation, mulching, geotextiles, sod stabilization, vegetative buffer strips, protection of existing trees, and other similar measures.

Interim on-site stabilization measures, which are continuous (ongoing), will include the following:

#### TPDES - Storm Water Pollution Prevention Plan

- i) Soil disturbances shall be minimized by exposing only the smallest practical area of land required for the construction activity and for the shortest practical period of time.
- ii) Trenching and associated backfilling for utilities and/or storm drainage piping shall be coordinated to minimize to the extent practical the time the area is disturbed.
- iii) Maximum practical use will be made of natural vegetation including grass, weeds, trees, shrubs, etc. by leaving these materials in place until construction necessitates clearing the minimum practical area for continuance of construction.
- iv) The minimum practical area required for the installation and construction of the utility and streets will be cleared of trees and ground cover.

Permanent on-site stabilization measures, which will be scheduled as detailed below, will include the following:

i) All disturbed soil associated with clearing will be stabilized per applicable project specifications.

Records of project milestone dates are required to be maintained and shall be recorded in Exhibit 3. Project milestones include the following:

- (1) Dates when major grading activities begin and end.
- (2) Dates when construction activities temporarily or permanently cease on all or a portion of the project.
- (3) Dates when stabilization measures are initiated and when stabilization is complete.

#### c) STRUCTURAL CONTROL PRACTICES

On-site structural practices, which are continuous (on-going) until the site is permanently stabilized, may include the following:

- i) Erection of silt fences, rock berms with silt fence, bagged gravel inlet filters, and sandbag controls as located and illustrated on Exhibit 2.
- ii) Installation of concrete truck washout pit as located and illustrated on Exhibit 2.
- iii) Installation of temporary construction entrance/exit as required and a construction staging area as located and illustrated on Exhibit 2.

These storm water pollution control features will slow the velocity of runoff thereby enhancing sedimentation and capture of contaminants that may accumulate in the storm water runoff exiting this construction site. There are no structures to divert storm water and no structures to store storm water on this project.

It is to be understood that modifications to the Storm Water Pollution Prevention Plan may have to be made in the field to adjust for field conditions and to provide the intended effect. All changes to the plan must be shown on Exhibit 2, dated, and signed by the responsible party or described and included in the Plan Modifications section of this Storm Water Pollution Prevention Plan.

#### TPDES - Storm Water Pollution Prevention Plan

#### 2) POST-CONSTRUCTION STORM WATER MANAGEMENT

a) This project does not require any TPDES post-construction storm water pollution controls or velocity dissipation devices.

#### 3) OTHER CONTROLS

Additional on-site practices, which are continuous (on-going) until the site is permanently stabilized, will include the following:

- a) Vehicular traffic leaving the construction site will exit through the temporary construction entrance/exit as located and illustrated on Exhibit 2. When soils have collected on the temporary construction entrance/exit to an extent, which reduces its intended effectiveness, the surface will be cleaned and reestablished for its designed or intended purpose.
- b) Mud/dirt inadvertently tracked off-site and onto public streets shall be removed immediately by hand or mechanical broom sweeping.
- c) Construction and waste materials shall be stored within a designated storage area in the construction equipment staging area as located and illustrated on Exhibit 2. Bulk materials such as sand, topsoil, etc. will be bordered on the down gradient sides with a silt fence as illustrated on Exhibit 2. A list of materials to be stored on-site should be recorded and regularly updated on the "On-Site Material List" provided in Exhibit 4.
- d) An area shall be designated as a construction equipment staging area as located on Exhibit 2. Construction equipment (except large slow-moving equipment) not removed from the site at night shall be stored in the containment area.
- e) Excavation spoils temporarily stored on-site, pending off-site disposal in accordance with applicable regulations, shall be bordered on the down gradient side by a silt fence as illustrated on Exhibit 2 and recorded on the "On-Site Material List" provided in Exhibit 4.
- f) The designated construction equipment staging area shall have a single entrance and will be bordered on the down gradient sides by a silt fence as illustrated on Exhibit 2.
- g) Sediment collected behind the silt fence will be periodically collected and placed as fill material within the property. Contaminated sediments will be disposed off-site in accordance to applicable regulations.
- h) The use of on-site temporary construction fuel storage tanks is limited to tank sizes which can only store unregulated quantities of fuel.
- i) Intentional release of vehicle or equipment fluid onto the ground is prohibited. Tainted soil resulting from accidental spills shall be removed and disposed of offsite in accordance with applicable regulations.
- j) Scheduled construction equipment and vehicle maintenance accomplished on-site shall be done within the construction equipment and vehicle staging area.
- k) A controlled area on-site as located and illustrated on Exhibit 2 shall be designated as a rinse-out pit for concrete trucks. Rinse-out pits shall be surrounded by a berm or hay bales to prevent runoff of contaminated water. The contractor will advise his concrete suppliers of the requirements to utilize the rinse-out pits for the intended purpose.

#### TPDES - Storm Water Pollution Prevention Plan

- Additional rinse-out pits may be added as construction conditions require. The
  contractor will advise his concrete suppliers of the requirements to utilize the
  rinse-out pits for the intended purpose.
- m) Construction waste materials, domestic garbage, etc. shall be periodically collected and disposed of off-site in accordance with applicable regulations.
- n) Trash receptacles will be established at storage locations, in the vicinity of equipment storing and near the construction areas. Receptacles shall be emptied as required and disposed of off-site in accordance with applicable regulations.
- o) Velocity dissipation devices, if necessary, shall be placed at discharge locations and along the length of any outfall channel to provide a non-erosive flow velocity from the structure to a water course so that the natural physical and biological characteristics and functions are maintained and protected.

#### 4) STATE AND LOCAL CONTROLS

The site is not located within the Edwards Aquifer Recharge Zone or Contributing Zone.

The site is not located on Native American Tribal lands.

Except as noted herein, there are no other known applicable state, tribal, or local storm water pollution prevention control requirements for construction projects at this location.

All activities during construction shall comply with state and/or local sanitary sewer, septic system, and waste disposal regulations.

Trees, limbs, leaves, brush, and vegetation from clearing operations shall be burned onsite in accordance with applicable permit requirements or removed from the site and disposed off-site in accordance with applicable regulations. Excavation spoils which will not be reused on this development project shall be disposed off-site at an approved location in accordance with applicable regulations.

#### **MAINTENANCE**

Structural controls shall be inspected as stipulated in this plan. Structural units shall be maintained to perform the function as intended. When a structure deteriorates to a condition so that its performance is compromised, the structure shall be repaired or replaced to full function as specified prior to the next storm event or as necessary.

Particular attention should be paid to the sedimentation areas behind the rock berm outlets, bagged gravel inlet filters, and silt fences. Sedimentation, including construction debris, tree trimming, trash, municipal type garbage, etc. will be removed and the structure restored to its original dimensions when the sediment has accumulated to six inches or more. Contaminated sediment removed from the containment areas (vehicle maintenance, concrete wash out pits, etc.) shall be disposed of off-site in accordance with appropriate regulations.

#### TPDES - Storm Water Pollution Prevention Plan

Exhibit 5 lists the various major components of this pollution prevention plan and identifies the party responsible for its function, maintenance, and inspections.

#### **INSPECTIONS**

Designated and qualified person(s) provided by the permittee shall inspect Pollution Control Measures every fourteen (14) calendar days and within twenty-four (24) hours after a storm event greater than 0.5 inches of rainfall. An inspection report that summarizes the scope of the inspection, date of inspection, major observations, and actions taken as a result of the inspection shall be recorded and maintained as part of Storm water TPDES data for a period of three years after the date of inspection.

As a minimum, the inspector shall observe:

- i) significant disturbed areas for evidence of erosion
- ii) storage areas for evidence of leakage from the exposed stored materials
- iii) structural controls (rock berm, silt fences, etc.) for evidence of failure or excess silting (over six inches deep)
- iv) vehicle exit point for evidence of off-site sediment tracking
- v) vehicle storage areas for signs of leaking equipment or spills
- vi) concrete truck rinse-out pit for signs of potential failure
- vii) general site cleanliness

Deficiencies noted during the inspection will be corrected and documented within seven (7) calendar days following the inspection or before the next anticipated storm event if practicable.

Exhibit 5 lists the various major components of this pollution prevention plan and identifies the party responsible for its function, maintenance, and inspections.

#### NON-STORM WATER DISCHARGES

Storm water discharges from this construction site may be intermittently mixed with non-storm water discharges. The following non-storm water discharges from this site authorized under this general permit include:

- i) discharges from firefighting activities
- ii) fire hydrant flushing
- iii) vehicle, external building, and pavement wash water where detergents and soaps are not used and where spills of toxic or hazardous materials have not occurred
- iv) water used to control dust
- v) potable water sources including waterline line flushing
- vi) air conditioning condensate
- vii) uncontaminated ground water or spring water

The above non-storm water components would exit the site via the storm water drainage paths and would be subject to the same filtering and sedimentation provided by the vegetative drainage channels and structural controls used for storm water runoff. Other non-storm water discharges are not anticipated from the construction of this project.

# **LOCATION MAP**



**SHOPS AT HERO WAY** 

# **PROJECT MILESTONE DATES**

## TPDES – Storm Water Pollution Prevention Plan

PROJECT MILESTONE DATES	
Dates when major site grading activities begin:	
Construction Activity	<u>Date</u>
Dates when construction activities temporarily or permathe project:	anently cease on all or a portion of
Construction Activity	<u>Date</u>
Dates when stabilization measures are initiated:	
Stabilization Activity	<u>Date</u>

# **ON-SITE MATERIALSLIST**

#### TPDES – Storm Water Pollution Prevention Plan

#### **ON-SITE MATERIALS LIST**

List construction and waste materials to be stored on-site. This list is to be kept curred and updated. (Examples: topsoil, gravel, sand, base, excess material to be hauled of demolition or construction waste, bulk chemicals, fuel, lubricants, etc.)	

# **RESPONSIBLE PARTYFORM**

## Responsible PartyForm

Pollu	Responsible party Name and Phone Number	
	Revegetation	
	Erosion/Sedimentation Controls	
	Vehicle Exits	
General	Material Areas	
Gen	Equipment Areas	
	Concrete Rinse	
	Construction Debris	
	Trash Receptacles	
	Site Clearing	
ø	Utility Clearing	
Infrastructure	Site Grading	
štru	Utility Construction	
fras	Drainage Construction	
드	Asphalt Base	
	Asphalt Surface	
	Site Cleanup	

Identify responsible parties and indicate responsible party for each pollution prevention item listed above by marking an X under the Responsible Party Name.

# **INSPECTION REPORT FORM**

## Inspection Report

Pollution Prevention Measure		Inspected	Corrective Action	
			Description	Date Completed
	Inspections			
Silt Fence	Fencing			
T Fe	Sediment Removal			
Si	Torn Fabric			
	Crushed/Collapsed Fencing			
E	Inspections			
Rock Berm	Remove sediment and Debris			
Ä	Repair any loose wire sheathing			
8	Reshaping			
	Replaced			
ed ed rs	Inspections			
Bagged Gravel Inlet Filters	Replaced/Reshaped			
	Silt Removed			
ion	Inspections			
Construction Entrance/Exit	Additional top Dressing			
onst	Repair/Cleanout			
Sediment removed immediately				
Inspector's Name Inspector's Signature				
Name of Owner/Operator			Date	

Note: Inspector is to attach a brief statement of his qualifications to this report.

# **PLAN MODIFICATIONS**

(IF NECESSARY)

# TEXAS COMMISSION ON ENVIRONMENTAL QUALITY TOPES GENERAL PERMIT (TXR150000) CONSTRUCTION SITE NOTICES PART II D.1 & D.2



# **CONSTRUCTION SITE NOTICE**

#### FOR THE

Texas Commission on Environmental Quality (TCEQ) Storm Water Program

#### **TPDES GENERAL PERMIT TXR150000**

The following information is posted in compliance with **Part II.D.1.** of the TCEQ General Permit Number TXR150000 for discharges of storm water runoff from construction sites. Additional information regarding the TCEQ storm water permit program may be found on the internet at:

www.tnrcc.state.tx.us/permitting/waterperm/wwperm/tpdestorm

**Contractor:** 

Contact: Phone:

Contact Name and Phone Number:

		AECA Have Way
	Project Description:	1561 Hero Way
	(Physical address or description of the site's location, estimated start date and projected end date, or date that disturbed soils will be stabilized)	Leander, TX 78641  Estimated Start Date: September 1, 2023  Projected End Date: December 1, 2023
I_coate TI	ertify under penalty of law that I have read and athorization by waiver under Part II.D.1. of Therms of this permit. Construction activities at the PDES general permit for this county, that period and erstand that if construction activities continuately provision of this general permit. A conscharges enter an MS4 system. I am aware the	art II.D.1. the following certification must be completed:  (Typed or Printed Name Person Completing This Certification) I understand the eligibility requirements for claiming an PDES General Permit TXR150000 and agree to comply with the his site shall occur within a time period listed in Appendix A of the od beginning on and ending on  The past this period, all storm water runoff must be authorized under topy of this signed notice is supplied to the operator of the MS4 if there are significant penalties for providing false information or for the possibility of fine and imprisonment for knowing violations.
S	ignature and Title	Date



# **CONSTRUCTION SITE NOTICE**

#### FOR THE

Texas Commission on Environmental Quality (TCEQ) Storm Water Program

#### **TPDES GENERAL PERMIT TXR150000**

The following information is posted in compliance with **Part II.D.2.** of the TCEQ General Permit Number TXR150000 for discharges of storm water runoff from construction sites. Additional information regarding the TCEQ storm water permit program may be found on the internet at:

www.tnrcc.state.tx.us/permitting/waterperm/wwperm/tpdestorm

Contact Name and Phone Number:	Contractor: Contact: Phone:
Project Description:	1561 Hero Way Leander, TX 78641
(Physical address or description of the site's location, estimated start date and projected end date, or date that disturbed soils will be stabilized)	Estimated Start Date: September 1, 2023 Projected End Date: December 1, 2023
Location of Storm Water Pollution Prevention Plan :	
or Construction Sites Authorized Under Pertification must be completed:	art II.D.2. (Obtaining Authorization to Discharge) the following
aw that I have read and understand the eligibility PDES General Permit TXR150000 and agree revention plan has been developed and imple otice is supplied to the operator of the MS4 if	Typed or Printed Name Person Completing This Certification) certify under penalty of ty requirements for claiming an authorization under Part II.D.2. of to comply with the terms of this permit. A storm water pollution mented according to permit requirements. A copy of this signed discharges enter an MS4 system. I am aware there are significant onducting unauthorized discharges, including the possibility of fine
ignature and Title	Date

# NOTICE OF INTENT (NOI) FOR STORMWATER DISCHARGES ASSOCIATED WITH CONSTRUCTION ACTIVITY UNDER TPDES GENERAL PERMIT (TXR150000)



# Notice of Intent (NOI) for an Authorization for Stormwater Discharges Associated with Construction Activity under TPDES General Permit TXR150000

#### IMPORTANT INFORMATION

Please read and use the General Information and Instructions prior to filling out each question in the NOI form.

Use the NOI Checklist to ensure all required information is completed correctly. **Incomplete applications delay approval or result in automatic denial.** 

Once processed your permit authorization can be viewed by entering the following link into your internet http://www2.tceq.texas.gov/wq\_dpa/index.cfm or you can contact TCEQ Stormwater Processing Center at 512-239-3700.

#### **ePERMITS**

Effective September 1, 2018, this paper form must be submitted to TCEQ with a completed electronic reporting waiver form (TCEQ-20754).

To submit an NOI electronically, enter the following web address into your internet browser and follow the instructions: https://www3.tceq.texas.gov/steers/index.cfm

#### APPLICATION FEE AND PAYMENT

The application fee for submitting a paper NOI is \$325. The application fee for electronic submittal of a NOI through the TCEQ ePermits system (STEERS) is \$225.

Payment of the application fee can be submitted by mail or through the TCEQ ePay system. The payment and the NOI must be mailed to separate addresses. To access the TCEQ ePay system enter the following web address into your internet browser: http://www.tceq.texas.gov/epay.

Provide your payment information for verification of payment:

If payment was mailed to TCEQ, provide the following:		
o Check/Money Order Number:		
o Name printed on Check:		
If payment was made via ePay, provide the following:		
o Voucher Number:		
o A copy of the payment voucher is attached to this paper NOI form.		

(This portion of the NOI is not applicable after June 3, 2018)				
Is	Is this NOI for a renewal of an existing authorization? ☐ Yes ☐ No			
If	Yes, provide the authorization number here: TXR15			
NO	OTE: If an authorization number is not provided, a new number will be assigned.			
SE	ECTION 1. OPERATOR (APPLICANT)			
a)	If the applicant is currently a customer with TCEQ, what is the Customer Number (CN) issued to this entity? CN604379081			
	(Refer to Section 1.a) of the Instructions)			
b)	What is the Legal Name of the entity (applicant) applying for this (The legal name must be spelled exactly as filed with the Texas Secretary of State, County, or in the legal document forming the entity.)			
	Transit Village Investments, Ltd.			
C)	What is the contact information for the Operator (Responsible Authority)?			
	Prefix (Mr. Ms. Miss): Mr.			
	First and Last Name: <u>Jeff Musgrove</u> Suffix:			
	Title: Owner Credentials: P.E.			
	Phone Number: 512-554-6282 Fax Number:			
	E-mail: <u>jmusgrove@americanrealty.com</u>			
	Mailing Address: <u>2215 Westlake Dr.</u>			
	City, State, and Zip Code: <u>Austin, TX 78746</u>			
	Mailing Information if outside USA:			
	Territory:			
	Country Code: Postal Code:			
d)	Indicate the type of customer:			
	☐ Individual ☐ Federal Government			
	☐ County Government ☐ County Government			
	☐ General Partnership ☐ State Government			
	☐ Trust ☐ City Government			
	☐ Sole Proprietorship (D.B.A.) ☐ Other Government			
	☐ Corporation ☐ Other:			
	□ Estate			
e)	Is the applicant an independent operator?   ☑ Yes □ No			

	(If a governmental entity, a subsidiary, or part	of a larger corporation, check No.)
f)	Number of Employees. Select the range application	able to your company.
	☑ 0-20	□ 251-500
	□ 21-100	□ 501 or higher
	□ 101-250	
g)	Customer Business Tax and Filing Numbers: <b>R</b> Partnerships. <b>Not Required</b> for Individuals, Go	
	State Franchise Tax ID Number: 32035081069	2
	Federal Tax ID: <u>20-8042936.</u>	
	Texas Secretary of State Charter (filing) Numb	er: Click here to enter text.
	DUNS Number (if known):	
SE	ECTION 2. APPLICATION CONTACT	
Ις	the application contact the same as the applicar	at identified above?
15	☐ Yes, go to Section 3	a racinifica above.
	<ul><li>☑ Yes, go to Section 3</li><li>☑ No, complete this section</li></ul>	
Dr	refix (Mr. Ms. Miss): Mr.	
	irst and Last Name: Anthony Goode Suffix:	
	itle: President Credential: <u>P.E.</u>	HELE WEINER LOSE
	rganization Name: Goode Faith Engineering LLC	
	hone Number: 972-822-1682 Fax Number:	mere an enter text
	-mail: Anthony@goodefaitheng.com	
	Tailing Address: 1620 La Jaita Dr., Ste.300	
	iternal Routing (Mail Code, Etc.):	
	ity, State, and Zip Code: Cedar Park, TX, 78613	
	Iailing information if outside USA:	
	erritory:	
Co	ountry Code: Postal Cod	e: Makharatoantartaxt
SE	ECTION 3. REGULATED ENTITY (RE) INFORMAT	ION ON PROJECT OR SITE
a)	If this is an existing permitted site, what is the issued to this site? RN	Regulated Entity Number(RN)
	(Refer to Section 3.a) of the Instructions)	

b)	Name of project or site (the name known by the community where it's located):  Shops at Hero Way
c)	In your own words, briefly describe the type of construction occurring at the regulated site (residential, industrial, commercial, or other): Commercial: small retail shops
d)	County or Counties (if located in more than one): Williamson County
e)	Latitude: 30.584260 Longitude: -97.848927
f)	Site Address/Location
	If the site has a physical address such as 12100 Park 35 Circle, Austin, TX 78753, complete <i>Section A</i> .
	If the site does not have a physical address, provide a location description in <i>Section B</i> . Example: located on the north side of FM 123, 2 miles west of the intersection of FM 123 and Highway 1.
	Section A:
	Street Number and Name: 1561 Hero Way
	City, State, and Zip Code: Leander, TX 78641
	Section B:
	Location Description:
	City (or city nearest to) where the site is located:
	Zip Code where the site islocated:
SE	CTION 4. GENERAL CHARACTERISTICS
a)	Is the project or site located on Indian CountryLands?
	☐ Yes, do not submit this form. You must obtain authorization through EPA Region 6.
	⊠ No
b)	Is your construction activity associated with a facility that, when completed, would be
	associated with the exploration, development, or production of oil or gas or geothermal resources?
	resources?  Yes. Note: The construction stormwater runoff may be under jurisdiction of the Railroad Commission of Texas and may need to obtain authorization through EPA
c)	resources?  Yes. Note: The construction stormwater runoff may be under jurisdiction of the Railroad Commission of Texas and may need to obtain authorization through EPA Region 6.
	resources?  ☐ Yes. Note: The construction stormwater runoff may be under jurisdiction of the Railroad Commission of Texas and may need to obtain authorization through EPA Region 6.  ☑ No  What is the Primary Standard Industrial Classification (SIC) Code that best describes the
-	resources?  ☐ Yes. Note: The construction stormwater runoff may be under jurisdiction of the Railroad Commission of Texas and may need to obtain authorization through EPA Region 6.  ☑ No  What is the Primary Standard Industrial Classification (SIC) Code that best describes the construction activity being conducted at the site? 154

	⊠ Yes
	☐ No. The total number of acres disturbed, provided in e) above, must be 5 or more. If the total number of acres disturbed is less than 5, do not submit this form. See the requirements in the general permit for small construction sites.
g)	What is the estimated start date of the project?
h)	What is the estimated end date of the project?
1)	Will concrete truck washout be performed at the site?   ✓ Yes  ✓ No
j)	What is the name of the first water body(ies) to receive the stormwater runoff or potential runoff from the site? North Fork Brushy Creek
k)	What is the segment number(s) of the classified water body(ies) that the discharge will eventually reach? <u>1244A North Fork Brushy Creek</u>
l)	Is the discharge into a Municipal Separate Storm Sewer System(MS4)?
	□ Yes ⊠ No
	If Yes, provide the name of the MS4 operator:
	Note: The general permit requires you to send a copy of this NOI form to the MS4 operator.
m)	Is the discharge or potential discharge from the site within the Recharge Zone, Contributing Zone, or Contributing Zone within the Transition Zone of the Edwards Aquifer, as defined in 30 TAC Chapter 213?
	Yes, complete the certification below.
	□ No, go to Section 5
	I certify that the copy of the TCEQ-approved Plan required by the Edwards Aquifer Rule (30 TAC Chapter 213) that is included or referenced in the Stormwater Pollution Prevention Plan will be implemented.
SE	CTION 5. NOI CERTIFICATION
a)	I certify that I have obtained a copy and understand the terms and conditions of the Construction General Permit (TXR150000).
b)	I certify that the full legal name of the entity applying for this permit has been provided and is legally authorized to do business in Texas.
C)	I understand that a Notice of Termination (NOT) must be submitted when this authorization is no longer needed.   ⊠ Yes
d)	I certify that a Stormwater Pollution Prevention Plan has been developed, will be implemented prior to construction and to the best of my knowledge and belief is compliant with any applicable local sediment and erosion control plans, as required in the Construction General Permit (TXR150000).
	Note: For multiple operators who prepare a shared SWP3, the confirmation of an

operator may be limited to its obligations under the SWP3, provided all obligations are

TCEQ-20022 (3/6/2018) Notice of Intent for Construction Stormwater Discharges under TXR150000

confirmed by at least one operator.

# Operator Signatory Name: Anthony Goode, PE Operator Signatory Title: President I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations. I further certify that I am authorized under 30 Texas Administrative Code §305.44 to sign and submit this document and can provide documentation in proof of such authorization upon request.

Signature (use blue ink):\_\_\_\_\_\_\_Date: \_\_\_\_\_

SECTION 6. APPLICANT CERTIFICATION SIGNATURE

#### NOTICE OF INTENT CHECKLIST (TXR150000)

Did you complete everything? Use this checklist to be sure!

Are you ready to mail your form to TCEQ? Go to the General Information Section of the Instructions for mailing addresses.

Confirm each item (or applicable item) in this form is complete. This checklist is for use by the applicant to ensure a complete application is being submitted. **Missing information** may result in denial of coverage under the general permit. (See NOI process description in the General Information and Instructions.)

#### APPLICATION FEE

If paying by check:

- ☐ Check was mailed **separately** to the TCEQs Cashier's Office. (See Instructions for Cashier's address and Application address.)
- ☐ Check number and name on check is provided in this application.

If using ePay:

☐ The voucher number is provided in this application and a copy of the voucher is attached.

#### RENEWAL

☐ If this application is for renewal of an existing authorization, the authorization number is provided.

#### **OPERATOR INFORMATION**

- ☑ Customer Number (CN) issued by TCEQ Central Registry
- ☑ Legal name as filed to do business in Texas. (Call TX SOS 512-463-5555 to verify.)
- Name and title of responsible authority signing the application.
- ☑ Phone number and e-mail address
- ☑ Mailing address is complete & verifiable with USPS. www.usps.com
- ☑ Type of operator (entity type). Is applicant an independent operator?
- Number of employees.
- ☑ For corporations or limited partnerships Tax ID and SOS filing numbers.
- Application contact and address is complete & verifiable with USPS.\_ <a href="http://www.usps.com">http://www.usps.com</a>

#### REGULATED ENTITY (RE) INFORMATION ON PROJECT OR SITE

- ☐ Regulated Entity Number (RN) (if site is already regulated by TCEQ)
- ☑ Site/project name and construction activity description
- □ County
- ☐ Latitude and longitude <a href="http://www.tceq.texas.gov/gis/sqmaview.html">http://www.tceq.texas.gov/gis/sqmaview.html</a>

☐ Site Address/Location. Do not use a rural route or post office box.
GENERAL CHARACTERISTICS
☐ Indian Country Lands —the facility is not on Indian Country Lands.
☐ Construction activity related to facility associated to oil, gas, or geothermal resources
☐ Primary SIC Code that best describes the construction activity being conducted at the site <a href="https://www.osha.gov/oshstats/sicser.html">www.osha.gov/oshstats/sicser.html</a>
☑ Estimated starting and ending dates of the project.
☑ Confirmation of concrete truck washout.
☑ Acres disturbed is provided and qualifies for coverage through a NOI.
☑ Common plan of development or sale.
Receiving water body or water bodies.
☐ Segment number or numbers.

#### **CERTIFICATION**

☑ Edwards Aquifer rule.

☐ MS4 operator.

- ☑ Certification statements have been checked indicating Yes.
- ☑ Signature meets 30 Texas Administrative Code (TAC) §305.44 and is original.

# Instructions for Notice of Intent (NOI) for Stormwater Discharges Associated with Construction Activity under TPDES General Permit (TXR 150000)

#### GENERAL INFORMATION

#### Where to Send the Notice of Intent (NOI):

By Overnight or Express Mail: By Regular Mail:

**TCEQ TCEQ** 

Stormwater Processing Center (MC228) Stormwater Processing Center (MC228)

P.O. Box 13087 12100 Park 35 Circle

Austin, Texas 78711-3087 Austin, TX

#### **Application Fee:**

The application fee of \$325 is required to be paid at the time the NOI is submitted. Failure to submit payment at the time the application is filed will cause delays in acknowledgment or denial of coverage under the general permit. Payment of the fee may be made by check or money order, payable to TCEQ, or through EPAY (electronic payment through the web).

#### **Mailed Payments:**

Use the attached General Permit Payment Submittal Form. The application fee is submitted to a different address than the NOI. Read the General Permit Payment Submittal Form for further instructions, including the address to send the payment.

#### ePAY Electronic Payment: http://www.tceq.texas.gov/epay

When making the payment you must select Water Quality, and then select the fee category "General Permit Construction Storm Water Discharge NOI Application". You must include a copy of the payment voucher with your NOI. Your NOI will not be considered complete without the payment

#### TCEQ Contact List:

Application – status and form questions: 512-239-3700, swpermit@tceq.texas.gov

Technical questions: 512-239-4671, swgp@tceq.texas.gov

**Environmental Law Division:** 512-239-0600 Records Management - obtain copies of forms: 512-239-0900

Reports from databases (as available): 512-239-DATA (3282)

Cashier's office: 512-239-0357 or 512-239-0187

#### **Notice of Intent Process:**

When your NOI is received by the program, the form will be processed as follows:

Administrative Review: Each item on the form will be reviewed for a complete response. In addition, the operator's legal name must be verified with Texas Secretary of State as valid and active (if applicable). The address(es) on the form must be verified with the US Postal service as receiving regular mail delivery. Do not give an overnight/express mailing address.

- Notice of Deficiency: If an item is incomplete or not verifiable as indicated above, a notice of deficiency (NOD) will be mailed to the operator. The operator will have 30 days to respond to the NOD. The response will be reviewed for completeness.
- Acknowledgment of Coverage: An Acknowledgment Certificate will be mailed to the operator. This certificate acknowledges coverage under the general permit.

or

**Denial of Coverage:** If the operator fails to respond to the NOD or the response is inadequate, coverage under the general permit may be denied. If coverage is denied, the operator will be notified.

#### **General Permit (Your Permit)**

For NOIs submitted **electronically** through ePermits, provisional coverage under the general permit begins immediately following confirmation of receipt of the NOI form by the TCEQ.

For **paper** NOIs, provisional coverage under the general permit begins **7 days after a completed NOI is postmarked for delivery** to the TCEQ.

You should have a copy of your general permit when submitting your application. You may view and print your permit for which you are seeking coverage, on the TCEQ web site <a href="http://www.tceq.texas.gov">http://www.tceq.texas.gov</a>. Search using keyword TXR150000.

#### Change in Operator

An authorization under the general permit is not transferable. If the operator of the regulated project or site changes, the present permittee must submit a Notice of Termination and the new operator must submit a Notice of Intent. The NOT and NOI must be submitted no later than 10 days prior to the change in Operator status.

#### TCEQ Central Registry Core Data Form

The Core Data Form has been incorporated into this form. Do not send a Core Data Form to TCEQ. After final acknowledgment of coverage under the general permit, the program will assign a Customer Number and Regulated Entity Number, if one has not already been assigned to this customer or site.

For existing customers and sites, you can find the Customer Number and Regulated Entity Number by entering the following web address into your internet browser: http://www15.tceq.texas.gov/crpub/ or you can contact the TCEQ Stormwater Processing Center at 512-239-3700 for assistance. On the website, you can search by your permit number, the Regulated Entity (RN) number, or the Customer Number (CN). If you do not know these numbers, you can select "Advanced Search" to search by permittee name, site address, etc.

The Customer (Permittee) is responsible for providing consistent information to the TCEQ, and for updating all CN and RN data for all authorizations as changes occur. For this permit, a Notice of Change form must be submitted to the program area.

#### INSTRUCTIONS FOR FILLING OUT THE NOI FORM

Renewal of General Permit. Dischargers holding active authorizations under the expired General Permit are required to submit a NOI to continue coverage. The existing permit number is required. If the permit number is not provided or has been terminated, expired, or denied, a new permit number will be issued.

#### **Section 1. OPERATOR (APPLICANT)**

#### a) Customer Number (CN)

TCEQ's Central Registry will assign each customer a number that begins with CN, followed by nine digits. This is not a permit number, registration number, or license number.

If the applicant is an existing TCEQ customer, the Customer Number is available at the following website: <a href="http://www15.tceq.texas.gov/crpub/">http://www15.tceq.texas.gov/crpub/</a>. If the applicant is not an existing TCEQ customer, leave the space for CN blank.

#### b) Legal Name of Applicant

Provide the current legal name of the applicant. The name must be provided exactly as filed with the Texas Secretary of State (SOS), or on other legal documents forming the entity, as filed in the county. You may contact the SOS at 512-463-5555, for more information related to filing in Texas. If filed in the county, provide a copy of the legal documents showing the legal name.

#### c) Contact Information for the Applicant (Responsible Authority)

Provide information for the person signing the application in the Certification section. This person is also referred to as the Responsible Authority.

Provide a complete mailing address for receiving mail from the TCEQ. The mailing address must be recognized by the US Postal Service. You may verify the address on the following website: https://tools.usps.com/go/ZipLookupAction!input.action.

The phone number should provide contact to the applicant.

The fax number and e-mail address are optional and should correspond to the applicant.

#### d) Type of Customer (Entity Type)

Check only one box that identifies the type of entity. Use the descriptions below to identify the appropriate entity type. Note that the selected entity type also indicates the name that must be provided as an applicant for an authorization.

#### **Individual**

An individual is a customer who has not established a business, but conducts an activity that needs to be regulated by the TCEQ.

#### **Partnership**

A customer that is established as a partnership as defined by the Texas Secretary of State Office (TX SOS). If the customer is a 'General Partnership' or 'Joint Venture' filed in the county (not filed with TX SOS), the legal name of each partner forming the 'General Partnership' or 'Joint Venture' must be provided. Each 'legal entity' must apply as a co-applicant.

#### **Trust or Estate**

A trust and an estate are fiduciary relationships governing the trustee/executor with respect to the trust/estate property.

#### **Sole Proprietorship (DBA)**

A sole proprietorship is a customer that is owned by only one person and has not been incorporated. This business may:

- 1. be under the person's name
- 2. have its own name (doing business as or DBA)
- 3. have any number of employees.

If the customer is a Sole Proprietorship or DBA, the 'legal name' of the individual business 'owner' must be provided. The DBA name is not recognized as the 'legal name' of the entity. The DBA name may be used for the site name (regulated entity).

#### Corporation

A customer that meets all of these conditions:

- 1. is a legally incorporated entity under the laws of any state or country
- 2. is recognized as a corporation by the Texas Secretary of State
- 3. has proper operating authority to operate in Texas

The corporation's 'legal name' as filed with the Texas Secretary of State must be provided as applicant. An 'assumed' name of a corporation is not recognized as the 'legal name' of the entity.

#### Government

Federal, state, county, or city government (as appropriate)

The customer is either an agency of one of these levels of government or the governmental body itself. The government agency's 'legal name' must be provided as the applicant. A department name or other description of the organization is not recognized as the 'legal name'.

#### Other

This may include a utility district, water district, tribal government, college district, council of governments, or river authority. Provide the specific type of government.

#### e) Independent Entity

Check if this customer is a subsidiary, part of a larger company, or is a governmental entity. Otherwise, check Yes.

#### f) Number of Employees

Check one box to show the number of employees for this customer's entire company, at all locations. This is not necessarily the number of employees at the site named in the application.

#### g) Customer Business Tax and Filing Numbers

These are required for Corporations and Limited Partnerships. These are not required for Individuals, Government, and Sole Proprietors.

#### State Franchise Tax ID Number

Corporations and limited liability companies that operate in Texas are issued a franchise tax identification number. If this customer is a corporation or limited liability company, enter the Tax ID number.

#### Federal Tax ID

All businesses, except for some small sole proprietors, individuals, or general partnerships should have a federal taxpayer identification number (TIN). Enter this number here. Use no prefixes, dashes, or hyphens. Sole proprietors, individuals, or general partnerships do not need to provide a federal tax ID.

#### TX SOS Charter (filing) Number

Corporations and Limited Partnerships required to register with the Texas Secretary of State are issued a charter or filing number. You may obtain further information by calling SOS at 512-463-5555.

#### **DUNS Number**

Most businesses have a DUNS (Data Universal Numbering System) number issued by Dun and Bradstreet Corp. If this customer has one, enter it here.

#### Section 2. APPLICATION CONTACT

Provide the name and contact information for the person that TCEQ can contact for additional information regarding this application.

#### Section 3. REGULATED ENTITY (RE) INFORMATION ON PROJECT OR SITE

#### a) Regulated Entity Number (RN)

The RN is issued by TCEQ's Central Registry to sites where an activity is regulated by TCEQ. This is not a permit number, registration number, or license number. Search TCEQ's Central Registry to see if the site has an assigned RN at <a href="http://www15.tceq.texas.gov/crpub/">http://www15.tceq.texas.gov/crpub/</a>. If this regulated entity has not been assigned an RN, leave this space blank.

If the site of your business is part of a larger business site, an RN may already be assigned for the larger site. Use the RN assigned for the larger site.

If the site is found, provide the assigned RN and provide the information for the site to be authorized through this application. The site information for this authorization may vary from the larger site information.

An example is a chemical plant where a unit is owned or operated by a separate corporation that is accessible by the same physical address of your unit or facility. Other examples include industrial parks identified by one common address but different corporations have control of defined areas within the site. In both cases, an RN would be assigned for the physical address location and the permitted sites would be identified separately under the same RN.

#### **b)** Name of the Project or Site

Provide the name of the site or project as known by the public in the area where the site is located. The name you provide on this application will be used in the TCEQ Central Registry as the Regulated Entity name.

#### c) Description of Activity Regulated

In your own words, briefly describe the primary business that you are doing that requires this authorization. Do not repeat the SIC Code description.

#### d) County

Provide the name of the county where the site or project is located. If the site or project is located in more than one county, provide the county names as secondary.

#### e) Latitude and Longitude

Enter the latitude and longitude of the site in degrees, minutes, and seconds or decimal form. For help obtaining the latitude and longitude, go to: http://www.tceq.texas.gov/gis/sqmaview.html.

#### f) Site Address/Location

If a site has an address that includes a street number and street name, enter the complete address for the site in *Section A*. If the physical address is not recognized as a USPS delivery address, you may need to validate the address with your local police (911 service) or through an online map site used to locate a site. Please confirm this to be a complete and valid address. Do not use a rural route or post office box for a site location.

If a site does not have an address that includes a street number and street name, provide a complete written location description in *Section B*. For example: "The site is located on the north side of FM 123, 2 miles west of the intersection of FM 123 and Highway 1."

Provide the city (or nearest city) and zip code of the site location.

#### **Section 4. GENERAL CHARACTERISTICS**

#### a) Indian Country Lands

If your site is located on Indian Country Lands, the TCEQ does not have authority to process your application. You must obtain authorization through EPA Region 6, Dallas. Do not submit this form to TCEQ.

# b) Construction activity associated with facility associated with exploration, development, or production of oil, gas, or geothermal resources

If your activity is associated with oil and gas exploration, development, or production, you may be under jurisdiction of the Railroad Commission of Texas (RRC) and may need to obtain authorization from EPA Region 6.

Construction activities associated with a facility related to oil, gas or geothermal resources may include the construction of a well site; treatment or storage facility; underground hydrocarbon or natural gas storage facility; reclamation plant; gas processing facility; compressor station; terminal facility where crude oil is stored prior to refining and at which refined products are stored solely for use at the facility; a carbon dioxide geologic storage facility; and a gathering, transmission, or distribution

pipeline that will transport crude oil or natural gas, including natural gas liquids, prior to refining of such oil or the use of the natural gas in any manufacturing process or as a residential or industrial fuel.

Where required by federal law, discharges of stormwater associated with construction activities under the RRC's jurisdiction must be authorized by the EPA and the RRC, as applicable. Activities under RRC jurisdiction include construction of a facility that, when completed, would be associated with the exploration, development, or production of oil or gas or geothermal resources, such as a well site; treatment or storage facility; underground hydrocarbon or natural gas storage facility; reclamation plant; gas processing facility; compressor station; terminal facility where crude oil is stored prior to refining and at which refined products are stored solely for use at the facility; a carbon dioxide geologic storage facility under the jurisdiction of the RRC; and a gathering, transmission, or distribution pipeline that will transport crude oil or natural gas, including natural gas liquids, prior to refining of such oil or the use of the natural gas in any manufacturing process or as a residential or industrial fuel. The RRC also has jurisdiction over stormwater from land disturbance associated with a site survey that is conducted prior to construction of a facility that would be regulated by the RRC. Under 33 U.S.C. §1342(1)(2) and §1362(24), EPA cannot require a permit for discharges of stormwater from field activities or operations associated with {oil and gas} exploration, production, processing, or treatment operations, or transmission facilities, including activities necessary to prepare a site for drilling and for the movement and placement of drilling equipment, whether or not such field activities or operations may be considered to be construction activities unless the discharge is contaminated by contact with any overburden, raw material, intermediate product, finished product, byproduct, or waste product located on the site of the facility. Under §3.8 of this title (relating to Water Protection), the RRC prohibits operators from causing or allowing pollution of surface or subsurface water. Operators are encouraged to implement and maintain best management practices (BMPs) to minimize discharges of pollutants, including sediment, in stormwater during construction activities to help ensure protection of surface water quality during stormevents.

For more information about the jurisdictions of the RRC and the TCEQ, read the Memorandum of Understanding (MOU) between the RRC and TCEQ at 16 Texas Administrative Code, Part 1, Chapter 3, Rule 3.30, by entering the following link into an internet browser:

http://texreg.sos.state.tx.us/public/readtac\$ext.TacPage?sl=R&app=9&p\_dir=&p\_rloc=&p\_tloc=&p\_ploc=&pg=1&p\_tac=&ti=16&pt=1&ch=3&rl=30 or contact the TCEQ Stormwater Team at 512-239-4671 for additional information.

#### c) Primary Standard Industrial Classification (SIC) Code

Provide the SIC Code that best describes the construction activity being conducted at this site.

Common SIC Codes related to construction activities include:

- 1521 Construction of Single-Family Homes
- 1522 Construction of Residential Buildings Other than Single Family Homes
- 1541 Construction of Industrial Buildings and Warehouses

1542 - Construction of Non-residential Buildings, other than Industrial Buildings and Warehouses
 1611 - Highway and Street Construction, except Highway Construction
 1622 - Bridge, Tunnel, and Elevated Highway Construction
 1623 - Water, Sewer, Pipeline and Communications, and PowerLine Construction

For help with SIC Codes, enter the following link into your internet browser: <a href="http://www.osha.gov/pls/imis/sicsearch.html">http://www.osha.gov/pls/imis/sicsearch.html</a> or you can contact the TCEQ Small Business and Local Government Assistance Section at 800-447-2827 for assistance.

#### d) Secondary SIC Code

Secondary SIC Code(s) may be provided. Leave this blank if not applicable. For help with SIC Codes, enter the following link into your internet browser: <a href="http://www.osha.gov/pls/imis/sicsearch.html">http://www.osha.gov/pls/imis/sicsearch.html</a> or you can contact the TCEQ Small Business and Environmental Assistance Section at 800-447-2827 for assistance.

#### e) Total Number of Acres Disturbed

Provide the approximate number of acres that the construction site will disturb. Construction activities that disturb less than one acre, unless they are part of a larger common plan that disturbs more than one acre, do not require permit coverage. Construction activities that disturb between one and five acres, unless they are part of a common plan that disturbs more than five acres, do not require submission of an NOI. Therefore, the estimated area of land disturbed should not be less than five, unless the project is part of a larger common plan that disturbs five or more acres. Disturbed means any clearing, grading, excavating, or other similar activities.

If you have any questions about this item, please contact the stormwater technical staff by phone at 512-239-4671 or by email at swgp@tceq.texas.gov.

#### f) Common Plan of Development

Construction activities that disturb less than five acres do not require submission of an NOI unless they are part of a common plan of development or for sale where the area disturbed is five or more acres. Therefore, the estimated area of land disturbed should not be less than five, unless the project is part of a larger common plan that disturbs five or more acres. Disturbed means any clearing, grading, excavating, or other similar activities.

For more information on what a common plan of development is, refer to the definition of "Common Plan of Development" in the section of the general permit or enter the following link into your internet browser:

www.tceq.texas.gov/permitting/stormwater/common plan of development steps.html

For further information, go to the TCEQ stormwater construction webpage enter the following link into your internet browser: <a href="www.tceq.texas.gov/goto/construction">www.tceq.texas.gov/goto/construction</a> and search for "Additional Guidance and Quick". If you have any further questions about the Common Plan of Development you can contact the TCEQ Stormwater Team at 512-239-4671 or the TCEQ Small Business and Environmental Assistance at 800-447-2827.

#### g) Estimated Start Date of the Project

This is the date that any construction activity or construction support activity is initiated at the site. If renewing the permit provide the original start date of when construction activity for this project began.

#### h) Estimated End Date of the Project

This is the date that any construction activity or construction support activity will end and final stabilization will be achieved at the site.

#### i) Will concrete truck washout be performed at the site?

Indicate if you expect that operators of concrete trucks will washout concrete trucks at the construction site.

#### j) Identify the water body(s) receiving stormwater runoff

The stormwater may be discharged directly to a receiving stream or through a MS4 from your site. It eventually reaches a receiving water body such as a local stream or lake, possibly via a drainage ditch. You must provide the name of the water body that receives the discharge from the site (a local stream or lake).

If your site has more than one outfall you need to include the name of the first water body for each outfall, if they are different.

#### k) Identify the segment number(s) of the classified water body(s)

Identify the classified segment number(s) receiving a discharge directly or indirectly. Enter the following link into your internet browser to find the segment number of the classified water body where stormwater will flow from the site:

www.tceq.texas.gov/waterquality/monitoring/viewer.html or by contacting the TCEQ Water Quality Division at (512) 239-4671 for assistance.

You may also find the segment number in TCEQ publication GI-316 by entering the following link into your internet browser: <a href="www.tceq.texas.gov/publications/gi/gi-316">www.tceq.texas.gov/publications/gi/gi-316</a> or by contacting the TCEQ Water Quality Division at (512) 239-4671 for assistance.

If the discharge is into an unclassified receiving water and then crosses state lines prior to entering a classified segment, select the appropriate watershed:

0100 (Canadian River Basin)
0200 (Red River Basin)
0300 (Sulfur River Basin)
0400 (Cypress Creek Basin)
0500 (Sabine River Basin)

Call the Water Quality Assessments section at 512-239-4671 for further assistance.

#### 1) Discharge into MS4 - Identify the MS4 Operator

The discharge may initially be into a municipal separate storm sewer system (MS4). If the stormwater discharge is into an MS4, provide the name of the entity that operates the MS4 where the stormwater discharges. An MS4 operator is often a city, town, county, or utility district, but possibly can be another form of government. Please note that the Construction General Permit requires the Operator to supply the MS4 with a

copy of the NOI submitted to TCEQ. For assistance, you may call the technical staff at 512-239-4671.

#### m) Discharges to the Edwards Aquifer Recharge Zone and Certification

The general permit requires the approved Contributing Zone Plan or Water Pollution Abatement Plan to be included or referenced as a part of the Stormwater Pollution Prevention Plan.

See maps on the TCEQ website to determine if the site is located within the Recharge Zone, Contributing Zone, or Contributing Zone within the Transition Zone of the Edwards Aquifer by entering the following link into an internet browser: <a href="https://www.tceq.texas.gov/field/eapp/viewer.html">www.tceq.texas.gov/field/eapp/viewer.html</a> or by contacting the TCEQ Water Quality Division at 512-239-4671 for assistance.

If the discharge or potential discharge is within the Recharge Zone, Contributing Zone, or Contributing Zone within the Transition Zone of the Edwards Aquifer, a site-specific authorization approved by the Executive Director under the Edwards Aquifer Protection Program (30 TAC Chapter 213) is required before construction can begin.

For questions regarding the Edwards Aquifer Protection Program, contact the appropriate TCEQ Regional Office. For projects in Hays, Travis and Williamson Counties: Austin Regional Office, 12100 Park 35 Circle, Austin, TX 78753, 512-339-2929. For Projects in Bexar, Comal, Kinney, Medina and Uvalde Counties: TCEQ San Antonio Regional Office, 14250 Judson Rd., San Antonio, TX 78233-4480, 210-490-3096.

#### **Section 5. NOI CERTIFICATION**

Note: Failure to indicate Yes to all of the certification items may result in denial of coverage under the general permit.

# a) Certification of Understanding the Terms and Conditions of Construction General Permit (TXR150000)

Provisional coverage under the Construction General Permit (TXR150000) begins 7 days after the completed paper NOI is postmarked for delivery to the TCEQ. Electronic applications submitted through ePermits have immediate provisional coverage. You must obtain a copy and read the Construction General Permit before submitting your application. You may view and print the Construction General Permit for which you are seeking coverage at the TCEQ web site by entering the following link into an internet browser: <a href="www.tceq.texas.gov/goto/construction">www.tceq.texas.gov/goto/construction</a> or you may contact the TCEQ Stormwater processing Center at 512-239-3700 for assistance.

#### b) Certification of Legal Name

The full legal name of the applicant as authorized to do business in Texas is required. The name must be provided exactly as filed with the Texas Secretary of State (SOS), or on other legal documents forming the entity, that is filed in the county where doing business. You may contact the SOS at 512-463 5555, for more information related to filing in Texas.

#### c) Understanding of Notice of Termination

A permittee shall terminate coverage under the Construction General Permit through the submittal of a NOT when the operator of the facility changes, final stabilization has been reached, the discharge becomes authorized under an individual permit, or the construction activity never began at this site.

#### d) Certification of Stormwater Pollution Prevention Plan

The SWP3 identifies the areas and activities that could produce contaminated runoff at your site and then tells how you will ensure that this contamination is mitigated. For example, in describing your mitigation measures, your site's plan might identify the devices that collect and filter stormwater, tell how those devices are to be maintained, and tell how frequently that maintenance is to be carried out. You must develop this plan in accordance with the TCEQ general permit requirements. This plan must be developed and implemented before you complete this NOI. The SWP3 must be available for a TCEQ investigator to review on request.

#### Section 6. APPLICANT CERTIFICATION SIGNATURE

The certification must bear an original signature of a person meeting the signatory requirements specified under 30 Texas Administrative Code (TAC) §305.44.

#### If you are a corporation:

The regulation that controls who may sign an NOI or similar form is 30 Texas Administrative Code §305.44(a)(1) (see below). According to this code provision, any corporate representative may sign an NOI or similar form so long as the authority to sign such a document has been delegated to that person in accordance with corporate procedures. By signing the NOI or similar form, you are certifying that such authority has been delegated to you. The TCEQ may request documentation evidencing such authority.

#### If you are a municipality or other government entity:

The regulation that controls who may sign an NOI or similar form is 30 Texas Administrative Code §305.44(a)(3) (see below). According to this code provision, only a ranking elected official or principal executive officer may sign an NOI or similar form. Persons such as the City Mayor or County Commissioner will be considered ranking elected officials. In order to identify the principal executive officer of your government entity, it may be beneficial to consult your city charter, county or city ordinances, or the Texas statute(s) under which your government entity was formed. An NOI or similar document that is signed by a government official who is not a ranking elected official or principal executive officer does not conform to §305.44(a)(3). The signatory requirement may not be delegated to a government representative other than those identified in the regulation. By signing the NOI or similar form, you are certifying that you are either a ranking elected official or principal executive officer as required by the administrative code. Documentation demonstrating your position as a ranking elected official or principal executive officer may be requested by the TCEQ.

If you have any questions or need additional information concerning the signatory requirements discussed above, please contact the TCEQ's Environmental Law Division at 512-239-0600.

#### 30 Texas Administrative Code

#### §305.44. Signatories to Applications

- (a) All applications shall be signed as follows.
- (1) For a corporation, the application shall be signed by a responsible corporate officer. For purposes of this paragraph, a responsible corporate officer means a president, secretary, treasurer, or vice-president of the corporation in charge of a principal business function, or any other person who performs similar policy or decision-making functions for the

corporation; or the manager of one or more manufacturing, production, or operating facilities employing more than 250 persons or having gross annual sales or expenditures exceeding \$25 million (in second-quarter 1980 dollars), if authority to sign documents has been assigned or delegated to the manager in accordance with corporate procedures. Corporate procedures governing authority to sign permit or post-closure order applications may provide for assignment or delegation to applicable corporate positions rather than to specific individuals.

- (2) For a partnership or sole proprietorship, the application shall be signed by a general partner or the proprietor, respectively.
- (3) For a municipality, state, federal, or other public agency, the application shall be signed by either a principal executive officer or a ranking elected official. For purposes of this paragraph, a principal executive officer of a federal agency includes the chief executive officer of the agency, or a senior executive officer having responsibility for the overall operations of a principal geographic unit of the agency (e.g., regional administrator of the EPA).

#### 30 Texas Administrative Code

#### §305.44. Signatories to Applications

- (a) All applications shall be signed as follows.
- (1) For a corporation, the application shall be signed by a responsible corporate officer. For purposes of this paragraph, a responsible corporate officer means a president, secretary, treasurer, or vice president of the corporation in charge of a principal business function, or any other person who performs similar policy or decision-making functions for the

corporation; or the manager of one or more manufacturing, production, or operating facilities employing more than 250 persons or having gross annual sales or expenditures exceeding \$25 million (in second - quarter 1980 dollars), if authority to sign documents has been assigned or delegated to the manager in accordance with corporate procedures. Corporate procedures governing authority to sign permit or post - closure order applications may provide for assignment or delegation to applicable corporate positions rather than to specific individuals.

- (2) For a partnership or sole proprietorship, the application shall be signed by a general partner or the proprietor, respectively.
- (3) For a municipality, state, federal, or other public agency, the application shall be signed by either a principal executive officer or a ranking elected official. For purposes of this paragraph, a principal executive officer of a federal agency includes the chief executive officer of the agency, or a senior executive officer having responsibility for the overall operations of a principal geographic unit of the agency (e.g., regional administrator of the EPA).

# SHOPS AT HERO WAY

# NOTICE OF TERMINATION (NOT) FOR AUTHORIZATIONS UNDER TPDES GENERAL PERMIT (TXR150000)

Exhibit 9



# Notice of Termination (NOT) for Authorizations under TPDES General Permit TXR150000

#### IMPORTANT INFORMATION:

Please read and use the General Information and Instructions prior to filling out each question in the form.

Effective September 1, 2018, this paper form must be submitted to TCEQ with a completed electronic reporting waiver form (TCEQ - 20754).

ePermits: This form is available on our online permitting system. Sign up for online permitting at: <a href="https://www3.tceq.texas.gov/steers/">https://www3.tceq.texas.gov/steers/</a>

What is the permit number to be terminated?

TXR15	<b>TXRCW</b>	

#### Section 1. OPERATOR (Permittee)

- a) What is the Customer Number (CN) issued to this entity?
  - CN604379081
- b) What is the Legal Name of the current permittee?
  - TRANSIT VILLAGE INVESTMENTS LTD
- c) Provide the contact information for the Operator (Responsible Authority).
  - Prefix (Mr. Ms. or Miss): Mr.
  - First and Last Name: <u>Jeff Musgrove</u> Suffix:
  - Title: Owner Credentials: P.E,
  - Phone Number: <u>512-554-6282</u> Fax Number:
  - Email: jmusgrove@americanrealty.com
  - Mailing Address: 2215 Westlake Drive
  - City, State, and Zip Code: Austin, TX 78746
  - Country Mailing Information, if outside USA:

#### Section 2. APPLICATION CONTACT

This is the person TCEQ will contact if additional information is needed regarding this application.

Is the application contact the same as the permittee identified above?

- $\square$  Yes, go to Section 3.
- No, complete section below

Prefix (Mr. Ms. or Miss): Mr.

First and Last Name: Anthony Goode Suffix:

Title: President Credentials: P.E.

Phone Number: <u>512 - 260 -9100</u> Fax Number:

Email: anthony@goodefaitheng.com

Mailing Address: <u>1620 La Jaita Dr., Ste 300</u> City, State, and Zip Code: <u>Cedar Park, TX 78613</u> Country Mailing Information, if outside USA:

#### Section 3. REGULATED ENTITY (RE) INFORMATION ON PROJECT OR SITE

- a) TCEQ issued RE Reference Number (RN): RN
- b) Name of project or site as known by the local community: Shops at Hero Way
- c) County, or counties if more than 1: Williamson County
- d) Latitude: 30.584260 Longitude: -97.848927
- e) Site Address/Location:

If the site has a physical address such as 12100 Park 35 Circle, Austin, TX 78753, complete Section 3A.

If the site does not have a physical address, provide a location description in Section 3B. Example: located on the north side of FM 123, 2 miles west of the intersection of FM 123 and Highway 1.

#### Section 3A: Physical Address of Project or Site:

Street Number and Name: 1561 Hero Way

City, State, and Zip Code: Leander, TX 78641

#### **Section 3B: Site Location Description:**

#### **Location description:**

City where the site is located or, if not in a city, what is the nearest city: Zip Code where the site is located:

#### Section 4. REASON FOR TERMINATION

Check the reason for termination:

- Final stabilization has been achieved on all portions of the site that are the responsibility of the Operator and all silt fences and other temporary erosion controls have been removed or scheduled for removal as defined in the SWP3.
- Another permitted Operator has assumed control over all areas of the site that have not been finally stabilized, and temporary erosion controls that have been identified in the SWP3 have been transferred to the new Operator.

oxdot The activity never began at this site that is regulated under the general permit.
Section 5. CERTIFICATION
Signatory Name:
Signatory Title:
I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations.
I further certify that I am authorized under 30 Texas Administrative Code §305.44 to sign and submit this document and can provide documentation in proof of such authorization upon request.

Signature (use blue ink): \_\_\_\_\_\_Date: \_\_\_\_\_

The discharge is now authorized under an alternate TPDES permit.

# Instructions for Notice of Termination (NOT) for Authorizations under TPDES General Permit TXR150000

#### **GENERAL INFORMATION**

#### Where to Send the Notice of Termination (NOT):

#### BY REGULAR U.S. MAIL:

Texas Commission on Environmental Quality Stormwater Processing Center (MC -228)

P.O. Box 13087

Austin, Texas 78711 - 3087

#### BY OVERNIGHT/EXPRESS MAIL:

Texas Commission on Environmental Quality Stormwater Processing Center (MC -228)

12100 Park 35 Circle Austin, TX 78753

#### TCEQ Contact List:

Application status and form questions: 512 -239 -3700, <a href="mailto:swpermit@tceq.texas.gov">swpermit@tceq.texas.gov</a>
Technical questions: 512 -239 -4671, <a href="mailto:swgp@tceq.texas.gov">swgp@tceq.texas.gov</a>

Environmental Law Division: 512-239-0600

Records Management - obtain copies of forms: 512-239-0900

Reports from databases (as available): 512-239-DATA (3282)

Cashier's office: 512-239-0357 or 512-239-0187

#### Notice of Termination Process:

A Notice of Termination is effective on the date postmarked for delivery to TCEQ.

When your NOT is received by the program, the form will be processed as follows:

- 1) Administrative Review: The form will be reviewed to confirm the following:
  - the permit number is provided:
  - the permit is active and has been approved;
  - the entity terminating the permit is the current permittee;
  - the site information matches the original permit record; and
  - the form has the required original signature with title and date.
- 2) Notice of Deficiency: If an item is incomplete or not verifiable as indicated above, a phone call will be made to the applicant to clear the deficiency. A letter will not be sent to the permittee if unable to process the form.
- 3) Confirmation of Termination: A Notice of Termination Confirmationletter will be mailed to the operator.

#### Change in Operator:

An authorization under the general permit is not transferable. If the operator of the regulated entity changes, the present permittee must submit a Notice of Termination and the new operator must submit a Notice of Intent. The NOT and NOI must be submitted not later than 10 days prior to the change in Operator status.

#### INSTRUCTIONS FOR FILLING OUT THE FORM

The majority of permit information related to the current operator and regulated entity are available at the following website: <a href="http://www2.tceq.texas.gov/wq\_dpa/index.cfm">http://www2.tceq.texas.gov/wq\_dpa/index.cfm</a>.

#### Section 1. Operator (Current Permittee):

a) Customer Number (CN)

TCEQ's Central Registry assigns each customer a number that begins with CN, followed by nine digits. This is not a permit number, registration number, or license number. The Customer Number, for the current permittee, is available at the following website: http://www2.tceq.texas.gov/wq\_dpa/index.cfm.

b) Legal Name of Operator

The operator must be the same entity as previously submitted on the original Notice of Intent for the permit number provided. The current operator name, as provided on the current authorization, is available at the following website: http://www2.tceq.texas.gov/wq\_dpa/index.cfm.

c) Contact Information for the Operator (Responsible Authority)
 Provide information for person signing the NOT application in the Certification section.
 This person is also referred to as the Responsible Authority.

Provide a complete mailing address for receiving mail from the TCEQ. Update the address if different than previously submitted for the Notice of Intent or Notice of Change. The mailing address must be recognized by the US Postal Service. You may verify the address on the following website: <a href="https://tools.usps.com/go/ZipLookupAction!input.action">https://tools.usps.com/go/ZipLookupAction!input.action</a>.

The phone number should provide contact to the operator.

The fax number and e-mail address are optional and should correspond to the operator.

#### Section 2. Application Contact:

Provide the name, title and contact information of the person that TCEQ can contact for additional information regarding this application.

#### Section 3. Regulated Entity (RE) Information on Project or Site:

a) Regulated Entity Reference Number(RN)

A number issued by TCEQ's Central Registry to sites where an activity regulated by TCEQ. This is not a permit number, registration number, or license number. The Regulated Entity Reference Number is available at the following website: <a href="http://www2.tceq.texas.gov/wq\_dpa/index.cfm">http://www2.tceq.texas.gov/wq\_dpa/index.cfm</a>.

- b) Name of the Project or Site Provide the name of the site as known by the public in the area where the site is located.
- County
  Identify the county or counties in which the regulated entity is located.
- d) Latitude and Longitude

Enter the latitude and longitude of the site in degrees, minutes, and seconds or decimal form. The latitude and longitude as provided on the current authorization is available at the following website: <a href="http://www2.tceq.texas.gov/wq\_dpa/index.cfm">http://www2.tceq.texas.gov/wq\_dpa/index.cfm</a>.

e) Site/Project (RE) Physical Address/Location Information
The physical address/location information, as provided on the current authorization, is available at the following website: http://www2.tceq.texas.gov/wq\_dpa/index.cfm.

- Section 3A. If a site has an address that includes a street number and street name, enter the complete address for the site. If the physical address is not recognized as a USPS delivery address, you may need to validate the address with your local police (911 service) or through an online map site used to locate the site. Please confirm this to be a complete and valid address. Do not use a rural route or post office box for a site location.
- Section 3B. If a site does not have an address that includes a street number and street name, provide a complete written location description. For example: "The site is located on the north side of FM 123, 2 miles west of the intersection of FM 123 and Highway 1."

Provide the city (or nearest city) and Zip Code of the facility location.

#### Section 4. Reason for Termination:

The Notice of Termination form is only for use to terminate the authorization (permit). The Permittee must indicate the specific reason for terminating by checking one of the options. If the reason is not listed then provide an attachment that explains the reason for termination.

Please read your general permit carefully to determine when to terminateyour permit. Permits will not be reactivated after submitting a termination form. The termination is effective on the date postmarked for delivery to TCEQ.

#### Section 5. Certification:

The certification must bear an original signature of a person meeting the signatory requirements specified under 30 Texas Administrative Code §305.44.

#### IF YOU ARE A CORPORATION:

The regulation that controls who may sign an application form is 30 Texas Administrative Code §305.44(a), which is provided below. According to this code provision, any corporate representative may sign an NOI or similar form so long as the authority to sign such a document has been delegated to that person in accordance with corporate procedures. By signing the NOI or similar form, you are certifying that such authority has been delegated to you. The TCEQ may request documentation evidencing such authority.

#### IF YOU ARE A MUNICIPALITY OR OTHER GOVERNMENT ENTITY:

The regulation that controls who may sign an NOI or similar form is 30 Texas Administrative Code §305.44(a), which is provided below. According to this code provision, only a ranking elected official or principal executive officer may sign an NOI or similar form. Persons such as the City Mayor or County Commissioner will be considered ranking elected officials. In order to identify the principal executive officer of your government entity, it may be beneficial to consult your city charter, county or city ordinances, or the Texas statutes under which your government entity was formed. An NOI or similar document that is signed by a government official who is not a ranking elected official or principal executive officer does not conform to §305.44(a) (3). The signatory requirement may not be delegated to a government representative other than those identified in the regulation. By signing the NOI or similar form, you are certifying that you are either a ranking elected official or principal executive officer as required by the administrative code. Documentation demonstrating your position as a ranking elected official or principal executive officer may be requested by the TCEQ.

If you have any questions or need additional information concerning the signatory requirements discussed above, please contact the Texas Commission on Environmental Quality's Environmental Law Division at 512 -239 - 0600.

- (a) All applications shall be signed as follows.
- (1) For a corporation, the application shall be signed by a responsible corporate officer. For purposes of this paragraph, a responsible corporate officer means a president, secretary, treasurer, or vice president of the corporation in charge of a principal business function, or any other person who performs similar policy or decision making functions for the corporation; or the manager of one or more manufacturing, production, or operating facilities employing more than 250 persons or having gross annual sales or expenditures exceeding \$25 million (in second quarter 1980 dollars), if authority to sign documents has been assigned or delegated to the manager in accordance with corporate procedures. Corporate procedures governing authority to sign permit or post closure order applications may provide for assignment or delegation to applicable corporate positions rather than to specific individuals.
- (2) For a partnership or sole proprietorship, the application shall be signed by a general partner or the proprietor, respectively.
- (3) For a municipality, state, federal, or other public agency, the application shall be signed by either a principal executive officer or a ranking elected official. For purposes of this paragraph, a principal executive officer of a federal agency includes the chief executive officer of the agency, or a senior executive officer having responsibility for the overall operations of a principal geographic unit of the agency (e.g., regional administrator of the EPA).

# SHOPS AT HERO WAY

# TEXAS COMMISSION ON ENVIRONMENTAL QUALITY TOPES GENERAL PERMIT (TXR150000)

Exhibit 10



# General Permit to Discharge Under the Texas Pollutant Discharge Elimination System

# Stormwater Discharges Associated with Construction Activities TXR150000

Effective March 5, 2023

## **Texas Commission on Environmental Quality**

P.O. Box 13087, Austin, Texas 78711-3087



#### GENERAL PERMIT TO DISCHARGE UNDER THE

#### TEXAS POLLUTANT DISCHARGE ELIMINATION SYSTEM

under provisions of Section 402 of the Clean Water Act and Chapter 26 of the Texas Water Code

This permit supersedes and replaces TPDES General Permit No. TXR150000, effective March 5, 2018, and amended January 28, 2022

Construction sites that discharge stormwater associated with construction activity located in the state of Texas may discharge to surface water in the state only according to monitoring requirements and other conditions set forth in this general permit, as well as the rules of the Texas Commission on Environmental Quality (TCEQ or Commission), the laws of the State of Texas, and other orders of the Commission of the TCEQ. The issuance of this general permit does not grant to the permittee the right to use private or public property for conveyance of stormwater and certain non-stormwater discharges along the discharge route. This includes property belonging to but not limited to any individual, partnership, corporation or other entity. Neither does this general permit authorize any invasion of personal rights nor any violation of federal, state, or local laws or regulations. It is the responsibility of the permittee to acquire property rights as may be necessary to use the discharge route.

This general permit and the authorization contained herein shall expire at midnight, on March 5, 2028.

EFFECTIVE DATE: March 5, 2023

ISSUED DATE: February 27, 2023

For the Commission

# **SHOPS AT HERO WAY**

## WETLAND MAP



PROJECT LOCATION IN RED

Exhibit 11

#### Agent Authorization Form

For Required Signature
Edwards Aquifer Protection Program
Relating to 30 TAC Chapter 213
Effective June 1, 1999

1	Jeff Musgrove	
	Print Name	
	Vice President	
	Title - Owner/President/Other	
of	Transit Village Investments LTD	,
	Corporation/Partnership/Entity Name	
have authorized	Anthony Goode, PE	
	Print Name of Agent/Engineer	
of	Goode Faith Engineering LLC	
	Print Name of Firm	

to represent and act on the behalf of the above named Corporation, Partnership, or Entity for the purpose of preparing and submitting this plan application to the Texas Commission on Environmental Quality (TCEQ) for the review and approval consideration of regulated activities.

#### I also understand that:

- 1. The applicant is responsible for compliance with 30 Texas Administrative Code Chapter 213 and any condition of the TCEQ's approval letter. The TCEQ is authorized to assess administrative penalties of up to \$10,000 per day per violation.
- For those submitting an application who are not the property owner, but who have the right to control and possess the property, additional authorization is required from the owner.
- Application fees are due and payable at the time the application is submitted. The
  application fee must be sent to the TCEQ cashier or to the appropriate regional office.
  The application will not be considered until the correct fee is received by the
  commission.
- 4. A notarized copy of the Agent Authorization Form must be provided for the person preparing the application, and this form must accompany the completed application.
- 5. No person shall commence any regulated activity on the Edwards Aquifer Recharge Zone, Contributing Zone or Transition Zone until the appropriate application for the activity has been filed with and approved by the Executive Director.

#### SIGNATURE PAGE:

Applicant's Signature	Date June 4 2013
THE STATE OF <u>Texas</u> §	JUDY T. MUSGROVE My Notary ID # 132826398
County of Travis §	Expires December 15, 2024

BEFORE ME, the undersigned authority, on this day personally appeared \_\_\_\_\_\_known to me to be the person whose name is subscribed to the foregoing instrument, and acknowledged to me that (s)he executed same for the purpose and consideration therein expressed.

GIVEN under my hand and seal of office on this 4 day of June 2023.

NOTARY PUBLIC

Typed or Printed Name of Notary

MY COMMISSION EXPIRES: Dec 15, 2024

# **Application Fee Form**

Texas Commission on Environme Name of Proposed Regulated Entit Regulated Entity Location: 1621 Name of Customer: Transit Village Contact Person: Jeff Musgrove Customer Reference Number (if is Regulated Entity Reference Number Austin Regional Office (3373)	ity: <u>Shop</u> s at Hero Way Hero Way Leander, TX e Investments LTD Phon ssued):CN <u>60437</u> 9081		6282	
Hays San Antonio Regional Office (336	Travis		XW	illiamson
Bexar Comal	☐ Medina ☐ Kinney		☐ U\	/alde
Application fees must be paid by c Commission on Environmental Q form must be submitted with you	uality. Your canceled c	heck will serv	e as you	r receipt. This
X Austin Regional Office Mailed to: TCEQ - Cashier	☐ Sa	an Antonio Re vernight Deli	egional O very to: 1	
Revenues Section Mail Code 214 P.O. Box 13088	В	2100 Park 35 uilding A, 3rd ustin, TX 787	Floor	
Austin, TX 78711-3088 Site Location (Check All That App	- WEW	512)239-0357		
Recharge Zone	X Contributing Zone	[	Transi	tion Zone
Type of Plan	n	Size		Fee Due
Water Pollution Abatement Plan, Plan: One Single Family Residentia			Acres	\$
Water Pollution Abatement Plan,				
Plan: Multiple Single Family Reside			Acres	\$
Water Pollution Abatement Plan, Plan: Non-residential	Contributing Zone	11.78	Acres	\$ 6500.00
Sewage Collection System		11.70	L.F.	\$ 6500.00 \$
Lift Stations without sewer lines			Acres	\$
Underground or Aboveground Sto	rage Tank Facility		Tanks	\$
Piping System(s)(only)			Each	\$
Exception			Each	\$
Extension of Time			Each	\$

Signature:

Date: 6/4/23

## **Application Fee Schedule**

**Texas Commission on Environmental Quality** 

Edwards Aquifer Protection Program 30 TAC Chapter 213 (effective 05/01/2008)

Water Pollution Abatement Plans and Modifications

Contributing Zone Plans and Modifications

Project	Project Area in Acres	Fee	
One Single Family Residential Dwelling	< 5	\$650	
Multiple Single Family Residential and Parks	< 5	\$1,500	
	5 < 10	\$3,000	
	10 < 40	\$4,000	
	40 < 100	\$6,500	
of the state of th	100 < 500	\$8,000	
	≥ 500	\$10,000	
Non-residential (Commercial, industrial, institutional,	< 1	\$3,000	
multi-family residential, schools, and other sites	1 < 5	\$4,000	
where regulated activities will occur)	5 < 10	\$5,000	
The second secon	10 < 40	\$6,500	
	40 < 100	\$8,000	
	≥ 100	\$10,000	

Organized Sewage Collection Systems and Modifications

Project	Cost per Linear Foot	Minimum Fee- Maximum Fee	
Sewage Collection Systems	\$0.50	\$650 - \$6,500	

# Underground and Aboveground Storage Tank System Facility Plans and Modifications

Project	Cost per Tank or Piping System	Minimum Fee- Maximum Fee
Underground and Aboveground Storage Tank Facility	\$650	\$650 - \$6,500

**Exception Requests** 

Project	Fee
Exception Request	\$500

**Extension of Time Requests** 

Project	Fee	
Extension of Time Request	\$150	



# **TCEQ Core Data Form**

For detailed instructions on completing this form, please read the Core Data Form Instructions or call 512-239-5175.

## **SECTION I: General Information**

1. Reason for Submission (If other is checked please describe in space provided.)								
New Permit, Registration or Authorization (Core Data F	New Permit, Registration or Authorization (Core Data Form should be submitted with the program application.)							
Renewal (Core Data Form should be submitted with the	e renewal form)	☑ Other						
2. Customer Reference Number (if issued)	3. Regulated Entity Reference Number (if issued)							
CN 604379081	for CN or RN numbers in Central Registry**	RN 11046053						
SECTION II: Customer Infor	mation							

#### SECTION II: Customer Information

4. General Cu	stomer I	nformation	5. Effective D	ate for Cu	ustome	er Info	ormation	Updat	es (mm/dd/	уууу)		5/10/2023
New Custon		U (Verifiable with the Tex	pdate to Customo kas Secretary of S			ptroll		•	egulated Ent nts)	ity Owne	ership	
The Customer	r Name s	ubmitted here may l	be updated aut	omatical	lly base	ed on	what is c	urrent	and active	with th	ne Texas Seci	retary of State
(SOS) or Texas	s Comptr	oller of Public Accou	ints (CPA).									
6. Customer L	egal Nar	ne (If an individual, pri	nt last name first.	: eg: Doe, J	John)			<u>If nev</u>	v Customer,	enter pre	evious Custom	er below:
Transit Village II	nvestmen	ts LTD						WP V	Vest Acquisit	ions LLC		
7. TX SOS/CPA	A Filing N	lumber	8. TX State Ta	<b>IX ID</b> (11 d	ligits)			9. Fe	deral Tax II	D		Number (if
0800746002			32035081069					(9 dig	gits)		applicable)	
								20-8042936				
11. Type of Cu	ustomer:	☐ Corporat	tion				Individ	dual		Partne	rship: 🗌 Gen	eral 🔀 Limited
Government:	City 🗌	County  Federal	Local 🗌 State 🛭	Other			Sole P	roprieto	orship	Otl	her:	
12. Number o	of Employ	/ees						13. I	ndepender	itly Ow	ned and Ope	erated?
□ 0-20    □ 2	1-100		500 🗌 501 ar	nd higher				⊠ Ye	es [	☐ No		
14. Customer	Role (Pro	oposed or Actual) – as i	t relates to the Re	egulated E	ntity list	ted on	this form.	Please	check one of	the follo	owing	
⊠Owner ☐Occupationa	ll Licensee	Operator Responsible Par	_	er & Opera P/BSA App					Other:			
15. Mailing 2215 Westlake Drive Ste 300												
Address:				1								
	City	Austin		State	TX		ZIP	7874	6		ZIP + 4	
16. Country N	/lailing In	formation (if outside	USA)			17.	E-Mail A	ddress	(if applicable	e)		
						jmu	ısgrove@aı	merican	realty.com			
18. Telephone	18. Telephone Number 19. Extension					ode			20. Fax N	umber	(if applicable)	

TCEQ-10400 (11/22) Page 1 of 3

( 512 ) 554-6282	( ) -

## **SECTION III: Regulated Entity Information**

21. General Regulated Entity Information (If 'New Regulated Entity" is selected, a new permit application is also required.)

☐ New Regulated Entity									
The Regulated Entity Name submitted may be updated, in order to meet TCEQ Core Data Standards (removal of organizational endings such as Inc, LP, or LLC).									
22. Regulated Entity Name (Enter name of the site where the regulated action is taking place.)									
Shops at Hero Way									
23. Street Address of the Regulated Entity:	1561 Hero Way								
(No PO Boxes)		T			T	T			
	City	Leander	State	TX	<b>ZIP</b> 78641		1	ZIP + 4	
24. County	Williamson								
		If no Stree	et Address is provid	ded, fields 2	25-28 are re	quired.			
25. Description to	This p	roperty is loc	cated at the so	utheast	corner of	Herc	Wav and	Main Str	eet in
Physical Location:	-	ty of Leander					, ,		
26. Nearest City						State		Nea	rest ZIP Code
Leander						TX		7864	1
Latitude/Longitude are required and may be added/updated to meet TCEQ Core Data Standards. (Geocoding of the Physical Address may be used to supply coordinates where none have been provided or to gain accuracy).									
27. Latitude (N) In Decima	al:	30.584260		28. L	ongitude (V	V) In De	ecimal:	-97.8489	27
Degrees	Minutes		Seconds	Degre	ees		Minutes		Seconds
30		35	3.34		-97		50		56.14
29. Primary SIC Code	30	). Secondary SIC	Code	31. Prima	ry NAICS Co	de	32. Seco	ndary NAI	CS Code
(4 digits)	(4	digits)		(5 or 6 digits) (5 or 6 digits			gits)	ts)	
1524				722515					
33. What is the Primary Business of this entity? (Do not repeat the SIC or NAICS description.)									
small retail shops and coffee shop									
1561 Hero Way									
34. Mailing									
Address:	City	Leander	State	тх	ZIP	7864	1	ZIP + 4	
35. E-Mail Address:	jm	nusgrove@america	nrealty.com						
36. Telephone Number			37. Extension or	Code	38. F	ax Nun	nber (if applicat	ble)	
(512)554-6282									

**39. TCEQ Programs and ID Numbers** Check all Programs and write in the permits/registration numbers that will be affected by the updates submitted on this form. See the Core Data Form instructions for additional guidance.

TCEQ-10400 (11/22) Page 2 of 3

☐ Dam Safety	Districts	X Edwards Aquifer	Emissions Inventory Air	☐ Industrial Hazardous Waste			
Municipal Solid Waste	New Source Review Air	OSSF	Petroleum Storage Tank	□ PWS			
Sludge	Storm Water	☐ Title V Air	Tires	Used Oil			
☐ Voluntary Cleanup	Wastewater	☐ Wastewater Agriculture	☐ Water Rights	Other:			
SECTION IV: Preparer Information							

40. Name:	Anthony Goode		41. Title:	President		
42. Telephone	Number	43. Ext./Code	44. Fax Number	45. E-Mail Address		
(972)822-1682			( ) -	anthony@go	odefaitheng.com	

## **SECTION V: Authorized Signature**

46. By my signature below, I certify, to the best of my knowledge, that the information provided in this form is true and complete, and that I have signature authority to submit this form on behalf of the entity specified in Section II, Field 6 and/or as required for the updates to the ID numbers identified in field 39.

Company:	Goode Faith Engineering, LLC	:			
Name (In Print):	Anthony Goode	Phone:	( 972 ) 822- <b>1682</b>		
Signature:	Chaffel.			Date:	6/1/2023

TCEQ-10400 (11/22) Page 3 of 3