Texas Commission on Environmental Quality

Edwards Aquifer Application Cover Page

Our Review of Your Application

The Edwards Aquifer Program staff conducts an administrative and technical review of all applications. The turnaround time for administrative review can be up to 30 days as outlined in 30 TAC 213.4(e). Generally administrative completeness is determined during the intake meeting or within a few days of receipt. The turnaround time for technical review of an administratively complete Edwards Aquifer application is 90 days as outlined in 30 TAC 213.4(e). Please know that the review and approval time is directly impacted by the quality and completeness of the initial application that is received. In order to conduct a timely review, it is imperative that the information provided in an Edwards Aquifer application include final plans, be accurate, complete, and in compliance with 30 TAC 213.

Administrative Review

- 1. Edwards Aquifer applications must be deemed administratively complete before a technical review can begin. To be considered administratively complete, the application must contain completed forms and attachments, provide the requested information, and meet all the site plan requirements. The submitted application and plan sheets should be final plans. Please submit one full-size set of plan sheets with the original application, and half-size sets with the additional copies.
 - To ensure that all applicable documents are included in the application, the program has developed tools to guide you and web pages to provide all forms, checklists, and guidance. Please visit the below website for assistance: http://www.tceq.texas.gov/field/eapp.
- 2. This Edwards Aquifer Application Cover Page form (certified by the applicant or agent) must be included in the application and brought to the administrative review meeting.
- 3. Administrative reviews are scheduled with program staff who will conduct the review. Applicants or their authorized agent should call the appropriate regional office, according to the county in which the project is located, to schedule a review. The average meeting time is one hour.
- 4. In the meeting, the application is examined for administrative completeness. Deficiencies will be noted by staff and emailed or faxed to the applicant and authorized agent at the end of the meeting, or shortly after. Administrative deficiencies will cause the application to be deemed incomplete and returned.
 - An appointment should be made to resubmit the application. The application is re-examined to ensure all deficiencies are resolved. The application will only be deemed administratively complete when all administrative deficiencies are addressed.
- 5. If an application is received by mail, courier service, or otherwise submitted without a review meeting, the administrative review will be conducted within 30 days. The applicant and agent will be contacted with the results of the administrative review. If the application is found to be administratively incomplete, it can be retrieved from the regional office or returned by regular mail. If returned by mail, the regional office may require arrangements for return shipping.
- 6. If the geologic assessment was completed before October 1, 2004 and the site contains "possibly sensitive" features, the assessment must be updated in accordance with the *Instructions to Geologists* (TCEQ-0585 Instructions).

Technical Review

- 1. When an application is deemed administratively complete, the technical review period begins. The regional office will distribute copies of the application to the identified affected city, county, and groundwater conservation district whose jurisdiction includes the subject site. These entities and the public have 30 days to provide comments on the application to the regional office. All comments received are reviewed by TCEQ.
- 2. A site assessment is usually conducted as part of the technical review, to evaluate the geologic assessment and observe existing site conditions. The site must be accessible to our staff. The site boundaries should be

- clearly marked, features identified in the geologic assessment should be flagged, roadways marked and the alignment of the Sewage Collection System and manholes should be staked at the time the application is submitted. If the site is not marked the application may be returned.
- 3. We evaluate the application for technical completeness and contact the applicant and agent via Notice of Deficiency (NOD) to request additional information and identify technical deficiencies. There are two deficiency response periods available to the applicant. There are 14 days to resolve deficiencies noted in the first NOD. If a second NOD is issued, there is an additional 14 days to resolve deficiencies. If the response to the second notice is not received, is incomplete or inadequate, or provides new information that is incomplete or inadequate, the application must be withdrawn or will be denied. Please note that because the technical review is underway, whether the application is withdrawn or denied **the application fee will be forfeited**.
- 4. The program has 90 calendar days to complete the technical review of the application. If the application is technically adequate, such that it complies with the Edwards Aquifer rules, and is protective of the Edwards Aquifer during and after construction, an approval letter will be issued. Construction or other regulated activity may not begin until an approval is issued.

Mid-Review Modifications

It is important to have final site plans prior to beginning the permitting process with TCEQ to avoid delays.

Occasionally, circumstances arise where you may have significant design and/or site plan changes after your Edwards Aquifer application has been deemed administratively complete by TCEQ. This is considered a "Mid-Review Modification". Mid-Review Modifications may require redistribution of an application that includes the proposed modifications for public comment.

If you are proposing a Mid-Review Modification, two options are available:

- If the technical review has begun your application can be denied/withdrawn, your fees will be forfeited, and the plan will have to be resubmitted.
- TCEQ can continue the technical review of the application as it was submitted, and a modification application can be submitted at a later time.

If the application is denied/withdrawn, the resubmitted application will be subject to the administrative and technical review processes and will be treated as a new application. The application will be redistributed to the affected jurisdictions.

Please contact the regional office if you have questions. If your project is located in Williamson, Travis, or Hays County, contact TCEQ's Austin Regional Office at 512-339-2929. If your project is in Comal, Bexar, Medina, Uvalde, or Kinney County, contact TCEQ's San Antonio Regional Office at 210-490-3096

Please fill out all required fields below and submit with your application.

Regulated Entity Name: Hesters 4 Apartments				2. Re	egulat	ed Entity No.:			
3. Customer Mame.	Hesters Crossing Apts Holdings LLC			4. Customer No.:					
5. Project Type: (Please circle/check one)	New	/	Modif	Modification		Extension		Exception	
6. Plan Type: (Please circle/check one)	WPAP	CZP	SCS	SCS UST AST		EXP	EXT	Technical Clarification	Optional Enhanced Measures
7. Land Use: (Please circle/check one)	Reside	ntial	Non-residential		/	8. Sit	e (acres):	4.056	
9. Application Fee:	\$4,000)	10. P	10. Permanent BMP(s):			s):	Partial sedimenta detention pond	ation/filtration pond, and
11. SCS (Linear Ft.):	N/A		12. AS	12. AST/UST (No. Tanks			ıks):	N/A	
13. County:	William	son	14. Watershed:					Lake Creek	

Application Distribution

Instructions: Use the table below to determine the number of applications required. One original and one copy of the application, plus additional copies (as needed) for each affected incorporated city, county, and groundwater conservation district are required. Linear projects or large projects, which cross into multiple jurisdictions, can require additional copies. Refer to the "Texas Groundwater Conservation Districts within the EAPP Boundaries" map found at:

http://www.tceq.texas.gov/assets/public/compliance/field_ops/eapp/EAPP%2oGWCD%2omap.pdf

For more detailed boundaries, please contact the conservation district directly.

Austin Region				
County:	Hays	Travis	Williamson	
Original (1 req.)		_	<u> </u>	
Region (1 req.)			<u> </u>	
County(ies)			\checkmark	
Groundwater Conservation District(s)	Edwards Aquifer AuthorityBarton Springs/ Edwards AquiferHays TrinityPlum Creek	Barton Springs/ Edwards Aquifer	NA	
City(ies) Jurisdiction	AustinBudaDripping SpringsKyleMountain CitySan MarcosWimberleyWoodcreek	AustinBee CavePflugervilleRollingwoodRound RockSunset ValleyWest Lake Hills	AustinCedar ParkFlorenceGeorgetownJerrellLeanderLiberty HillPflugervilleRound Rock	

	S	an Antonio Region		***************************************	
County:	Bexar	Comal	Kinney	Medina	Uvalde
Original (1 req.)	_	_			
Region (1 req.)		_			
County(ies)					
Groundwater Conservation District(s)	Edwards Aquifer Authority Trinity-Glen Rose	Edwards Aquifer Authority	Kinney	EAA Medina	EAA Uvalde
City(ies) Jurisdiction	Castle HillsFair Oaks RanchHelotesHill Country VillageHollywood ParkSan Antonio (SAWS)Shavano Park	Bulverde Fair Oaks Ranch Garden Ridge New Braunfels Schertz	NA	San Antonio ETJ (SAWS)	NA

I certify that to the best of my knowledge, that the application is complete and accurate. This application is hereby submitted to TCEQ for administrative review and technical review.
application is necessary submitted to 1010 for administrative review and technical review.
A
ANNA HORE
Print Name of Customer/Authorized Agent
1100 Lei Hber 6/8/23
Signature of Customer/Authorized Agent Date
Signature of Customer/Mathorized rigent Date

FOR TCEQ INTERNAL USE ON	LY			
Date(s)Reviewed:		Date Administratively Complete:		
Received From:	ceived From:		Correct Number of Copies:	
Received By:		Distribution Date:		
EAPP File Number:		Complex	•	
Admin. Review(s) (No.):		No. AR R	Rounds:	
Delinquent Fees (Y/N):		Review Time Spent:		
Lat./Long. Verified:		SOS Customer Verification:		
Agent Authorization Complete/Notarized (Y/N):		Fee	Payable to TCEQ (Y	/N):
Core Data Form Complete (Y/N):		Check: Signed (Y/N):		
Core Data Form Incomplete Nos.:	-		Less than 90 days o	ld (Y/N):

General Information Form

Texas Commission on Environmental Quality

For Regulated Activities on the Edwards Aquifer Recharge and Transition Zones and Relating to 30 TAC §213.4(b) & §213.5(b)(2)(A), (B) Effective June 1, 1999

To ensure that the application is administratively complete, confirm that all fields in the form are complete, verify that all requested information is provided, consistently reference the same site and contact person in all forms in the application, and ensure forms are signed by the appropriate party.

Note: Including all the information requested in the form and attachments contributes to more streamlined technical reviews.

Signature

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. This **General Information Form** is hereby submitted for TCEQ review. The application was prepared by:

***	s prepared by:
Pri	nt Name of Customer/Agent: <u>Anna Hoge</u>
Da	te: <u>5/11/2023</u>
Sig	nature of Customer/Agent:
(and defige
PI	roject Information
1.	Regulated Entity Name: <u>Hesters 4</u>
2.	County: Williamson
3.	Stream Basin: Lake Creek Tributary 6
4.	Groundwater Conservation District (If applicable): <u>N/A</u>
5.	Edwards Aquifer Zone:
	Recharge Zone Transition Zone
6.	Plan Type:
	WPAPSCS☐ Modification☐ AST☐ UST☐ Exception Request


7.	Customer (Applicant):	
	Contact Person: <u>Jonathan Marcus</u> Entity: <u>Hesters Crossing Apts Holdings, LLC</u> Mailing Address: <u>155 Schmitt Blvd</u> City, State: <u>Farmingdale, NY</u> Telephone: <u>512-315-3515</u> Email Address: <u>jmarcus@marcusbuild.com</u>	Zip: <u>11735</u> FAX:
8.	Agent/Representative (If any):	
	Contact Person: Anna Hoge, RLA Entity: Consort Inc. Mailing Address: 1609 Shoal Creek Blvd, Ste, 300 City, State: Austin, Texas Telephone: 512-469-0500 Email Address: ahoge@consortinc.com	Zip: <u>78701</u> FAX:
9.	Project Location:	
	 ☐ The project site is located inside the city limits ☐ The project site is located outside the city limit jurisdiction) of ☐ The project site is not located within any city's 	s but inside the ETJ (extra-territorial
10.	The location of the project site is described bel detail and clarity so that the TCEQ's Regional so boundaries for a field investigation.	
	Northwest quadrant of the intersection of Hes Round Rock, Tx.	ters Crossing Rd. and Rawhide Dr. in
11.	Attachment A – Road Map. A road map showing project site is attached. The project location are the map.	_
12.	Attachment B - USGS / Edwards Recharge Zon USGS Quadrangle Map (Scale: 1" = 2000') of th The map(s) clearly show:	
	 ☑ Project site boundaries. ☑ USGS Quadrangle Name(s). ☑ Boundaries of the Recharge Zone (and Trance) ☑ Drainage path from the project site to the keep some continuous project site site site to the keep some continuous project site site site site site site site sit	
13.	The TCEQ must be able to inspect the project sufficient survey staking is provided on the prothe boundaries and alignment of the regulated features noted in the Geologic Assessment.	ject to allow TCEQ regional staff to locate


	urvey staking will be completed by this date:
r	Attachment C – Project Description. Attached at the end of this form is a detailed arrative description of the proposed project. The project description is consistent hroughout the application and contains, at a minimum, the following details:
	Area of the site Offsite areas Impervious cover Permanent BMP(s) Proposed site use Site history Previous development Area(s) to be demolished
15. Exist	ing project site conditions are noted below:
	Existing commercial site Existing industrial site Existing residential site Existing paved and/or unpaved roads Undeveloped (Cleared) Undeveloped (Undisturbed/Uncleared) Other:
Prohi	bited Activities
	am aware that the following activities are prohibited on the Recharge Zone and are no roposed for this project:
(:	1) Waste disposal wells regulated under 30 TAC Chapter 331 of this title (relating to Underground Injection Control);
(2	2) New feedlot/concentrated animal feeding operations, as defined in 30 TAC §213.3;
(3	3) Land disposal of Class I wastes, as defined in 30 TAC §335.1;
(4	4) The use of sewage holding tanks as parts of organized collection systems; and
!)	5) New municipal solid waste landfill facilities required to meet and comply with Type standards which are defined in §330.41(b), (c), and (d) of this title (relating to Types of Municipal Solid Waste Facilities).
(6	 New municipal and industrial wastewater discharges into or adjacent to water in the state that would create additional pollutant loading.
	am aware that the following activities are prohibited on the Transition Zone and are ot proposed for this project:
(:	 Waste disposal wells regulated under 30 TAC Chapter 331 (relating to Underground Injection Control);

- (2) Land disposal of Class I wastes, as defined in 30 TAC §335.1; and
- (3) New municipal solid waste landfill facilities required to meet and comply with Type I standards which are defined in §330.41 (b), (c), and (d) of this title.

Administrative Information

18. The	e fee for the plan(s) is based on:
	For a Water Pollution Abatement Plan or Modification, the total acreage of the site where regulated activities will occur. For an Organized Sewage Collection System Plan or Modification, the total linear footage of all collection system lines. For a UST Facility Plan or Modification or an AST Facility Plan or Modification, the total number of tanks or piping systems. A request for an exception to any substantive portion of the regulations related to the protection of water quality. A request for an extension to a previously approved plan.
19. 🔀	Application fees are due and payable at the time the application is filed. If the correct fee is not submitted, the TCEQ is not required to consider the application until the correct fee is submitted. Both the fee and the Edwards Aquifer Fee Form have been sent to the Commission's:
	 ☐ TCEQ cashier ☐ Austin Regional Office (for projects in Hays, Travis, and Williamson Counties) ☐ San Antonio Regional Office (for projects in Bexar, Comal, Kinney, Medina, and Uvalde Counties)
20. 🔀	Submit one (1) original and one (1) copy of the application, plus additional copies as needed for each affected incorporated city, groundwater conservation district, and county in which the project will be located. The TCEQ will distribute the additional copies to these jurisdictions. The copies must be submitted to the appropriate regional office.
21. 🔀	No person shall commence any regulated activity until the Edwards Aquifer Protection Plan(s) for the activity has been filed with and approved by the Executive Director.





Consort, Inc.

1609 Shoal Creek Blvd., Suite 300
Austin, Texas 78701
(512) 469-0500
T.B.P.E. Firm Registration No. F-859

USGS/EDWARDS RECHARGE ZONE MAP

PRLIGERMLLE WEST, TX

2/14/2023 SCALE: 1"=2000' 2200 RAWHIDE DRIVE ROUND ROCK, TEXAS 78681

ATTACHMENT "C" - PROJECT DESCRIPTION

We are submitting a WPAP for a 4.055-acre site in Round Rock, Texas. The closest cross street is Hesters Crossing to the south of the property and Rawhide Drive to the east of the property. The site is currently undeveloped with evidence of fill being placed on the site previously. The site is within the Recharge and Transition zone of the Edwards Aquifer. Permanent BMPs will be put in place in the form of a sedimentation/filtration pond.

The proposed project includes the construction of a mixed-use/multifamily development with water and wastewater services, driveways, storm sewer, and a water quality treatment pond.

The existing impervious cover is \pm 0.00 acres (\pm 0%) for the 4.055-acre site. The proposed increase in impervious cover within in the site is approximately \pm 115,050 S.F., totaling \pm 2.641 acres or 65.13% for the 4.055 acres site.

The storm water from this project will be treated by an engineered BMP to comply with Texas Commission on Environmental Quality rules.

Proposed Permanent BMPs: The drainage basin will be treated with a sedimentation/filtration pond. The sand filter system with the water being collected by grate inlets and conveyed to the sand filter basin by storm drain lines. The total area going to the sand filter system is 3.24 acres at 81.52% impervious cover.

Geologic Assessment

Texas Commission on Environmental Quality

For Regulated Activities on The Edwards Aquifer Recharge/transition Zones and Relating to 30 TAC §213.5(b)(3), Effective June 1, 1999

To ensure that the application is administratively complete, confirm that all fields in the form are complete, verify that all requested information is provided, consistently reference the same site and contact person in all forms in the application, and ensure forms are signed by the appropriate party.

Note: Including all the information requested in the form and attachments contributes to more streamlined technical reviews.

Signature

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. My signature certifies that I am qualified as a geologist as defined by 30 TAC Chapter 213.

Print Name of Geologist: Russell C Ford	Telephone: <u>512 442-1122</u>
Date: 3/25/22	Fax:
Repression Ferración Consultants, Inc. (Name of Consultants, Inc.) Regulated Exiltres de Consultants, Inc. (Name of Consultants, Inc.) Regulated Exiltres de Consultants, Inc. (Name of Consultants, Inc.)	Company and TBPG or TBPE registration Road Round
Rock, Texas	Toda, Rodria
Project Information	
1. Date(s) Geologic Assessment was performed: 3/	17/22
2. Type of Project:	
WPAP☐ SCS3. Location of Project:	AST UST
Recharge Zone Transition Zone Contributing Zone within the Transition Zone	2

- 4. Attachment A Geologic Assessment Table. Completed Geologic Assessment Table (Form TCEQ-0585-Table) is attached.
- 5. Soil cover on the project site is summarized in the table below and uses the SCS Hydrologic Soil Groups* (Urban Hydrology for Small Watersheds, Technical Release No. 55, Appendix A, Soil Conservation Service, 1986). If there is more than one soil type on the project site, show each soil type on the site Geologic Map or a separate soils map.

Table 1 - Soil Units, Infiltration Characteristics and Thickness

Soil Name	Group*	Thickness(feet)
FaB	D	3-4
FhF2	D	3-4
HedC2	D	3-4
HeiD3	D	3-4

- * Soil Group Definitions (Abbreviated)
 - A. Soils having a high infiltration rate when thoroughly wetted.
 - B. Soils having a moderate infiltration rate when thoroughly wetted.
 - C. Soils having a slow infiltration rate when thoroughly wetted.
 - D. Soils having a very slow infiltration rate when thoroughly wetted.
- 6. Attachment B Stratigraphic Column. A stratigraphic column showing formations, members, and thicknesses is attached. The outcropping unit, if present, should be at the top of the stratigraphic column. Otherwise, the uppermost unit should be at the top of the stratigraphic column.
- 7. Attachment C Site Geology. A narrative description of the site specific geology including any features identified in the Geologic Assessment Table, a discussion of the potential for fluid movement to the Edwards Aquifer, stratigraphy, structure(s), and karst characteristics is attached.
- 8. Attachment D Site Geologic Map(s). The Site Geologic Map must be the same scale as the applicant's Site Plan. The minimum scale is 1": 400'

Applicant's Site Plan Scale: 1" = _'
Site Geologic Map Scale: 1" = 100'

Site Soils Map Scale (if more than 1 soil type): 1" = 100'

9. Method of collecting positional data:

Global Positioning System (GPS) technology.

Other method(s). Please describe method of data collection: _____

10. The project site and boundaries are clearly shown and labeled on the Site Geologic Map.

11. Surface geologic units are shown and labeled on the Site Geologic Map.

12.	Geologic or manmade features were discovered on the project site during the field investigation. They are shown and labeled on the Site Geologic Map and are described in the attached Geologic Assessment Table.
	\boxtimes Geologic or manmade features were not discovered on the project site during the field investigation.
13.	\mathbb{R} . \boxtimes The Recharge Zone boundary is shown and labeled, if appropriate.
14.	All known wells (test holes, water, oil, unplugged, capped and/or abandoned, etc.): If applicable, the information must agree with Item No. 20 of the WPAP Application Section.
	There are (#) wells present on the project site and the locations are shown and labeled. (Check all of the following that apply.) The wells are not in use and have been properly abandoned. The wells are not in use and will be properly abandoned. The wells are in use and comply with 16 TAC Chapter 76.
	\times There are no wells or test holes of any kind known to exist on the project site.

Administrative Information

15. Submit one (1) original and one (1) copy of the application, plus additional copies as needed for each affected incorporated city, groundwater conservation district, and county in which the project will be located. The TCEQ will distribute the additional copies to these jurisdictions. The copies must be submitted to the appropriate regional office.

NO FEATURES OBSERVED Attachment A

GFO	OGIC AS	GEOLOGIC ASSESSMENT TABL	T TN=	ABI F		L	PRO	FCT	JAME: Pr	6	Sed Roi	und Ro	ck Anar	rtments 4	OO Hos	there	rose	ing R	Dad B	PROJECT NAME: Pronosed Round Rock Apartments 400 Hesters Crossing Road Round Rock Tayas
LOCATION	NO.		FEATURE CH		HARACTERISTICS	ISTIC	တ္လ			1					EVA	UAT	S N	PHY	EVALUATION PHYSICAL	SETTING
14	18 *	1C*	2A	28	г		4		5	5A	9	7	8A	8B	6	10		1		12
FEATUREID	LATITUDE	LONGITUDE	FEATURE	POINTS	FORMATION	DIME	DIMENSIONS (FEET)		TREND (DEGREES)	Dom [DENSITY A	APER TURE (FEET)	INFILL	RELATIVE IN FILTRATION RATE	TOTAL	SENSITMITY	<u>}</u>	CATCHM ENTAREA (ACRES)		TOPOGRAPHY
						×	>	Z		10		П				<40	>40	<1.6	21.6	
										H										
* DATU	NAD27																			
2A TYPE	2A TYPE TYPE				2B POINTS		8A IN	8A INFILLING	פט											
O	Cave				30		z	None,	None, exposed bedrock	bedr	²ock									
SC	Solution cavity	ı ity			20		O	Coars	Coarse - cobbles, breakdown, sand, gravel	es, bi	reakdow	m, sand	, gravel							
SF	Solution-en	Solution-enlarged fracture(s)	œ(s)		20		0	Loose	or soft n	o pnu	or soil, o	organics,	leaves	Loose or soft mud or soil, organics, leaves, sticks, dark colors	ark co	lors				
L	Fault				. 20		Щ	Fines,	compac	ted c	lay -rich	sedime	nt, soil	Fines, compacted clay-rich sediment, soil profile, gray or red colors	ıy or re	ed colc	হ			
0	Other natura	Other natural bedrock features	atures		5		>	Veget	Vegetation. Give details in narrative description	e de	tails in r	narrative	descri	ption						
MB	Manmade f	Manmade feature in bedrock	rock		30		БS	Flows	Flowstone, cements, cave deposits	nents	;, cave	deposits								
SW	Swallow hole	Φ			Co.		×	Other	Other materials	,										
SH	Sinkhole			•	A.A.	TEX														
CD	Non-karst c	losed depres	sion	15	٧,٧	/	"⊢" (3) (2)	POGF	L TOGRAPHY											
Z	Zone, clust	Zone, clustered or aligned feature	ed featur		To an article of the second			Hilto	Killtop, Hillside, Drainage, Floodplain, Streambed	e, Dr	ʻainage,	Floodpl	ain, Stre	eambed						
			l have	法		ع ار	100		Lthe Tex	as Ng	atural R	esonrce	Conse	The Texas Natural Resource Conservation Commission's Instructions to Geologists.	mmiss	il s'noi	nstruc	ctions	to Geok	logists. The
			inform	~	0.00	è	iles		documer	ıt anc	disatr.	ue repre	sentatio	document and is a true representation of the conditions observed in the field.	onditio	sqo su	erv ec	in the	field.	
			My sign	igt.	The See of the		auc Fre	ويوز د المائن	a geologist as defined by 30 TAC 213	t as c	defined	by 30 T,	AC 213							
			1		TEST X	RY N	1				ļ			Date						
TNRCC	-0585-Tabl	TNRCC-0585-Table (Rev. 5-1-02)	-02)				D.						υ,	Sheet		ا م				
			3/25	3/25/2022		i }														

ATTACHMENT B

Stratigraphic Column
Proposed Round Rock Apartments
400 Hesters Crossing Road
Round Rock, Texas

HYDROGEOLOGIC SUBDIVISION	FORMATION	THICKNESS (feet)	LITHOLOGY
	Buda	30	Calcareous, fossiliferous hard limestone
Confining Layer	Del Rio Clay	50	Calcareous, fossiliferous clay with pyrite and gypsum



Source: Senger, Collins and Kreitler, 1990



ATTACHMENT C

SITE-SPECIFIC GEOLOGY

The Geologic Assessment (GA) of the Proposed Round Rock Apartments site was conducted by Mr. Russell C. Ford, P.G., of Terracon Consultants, Inc. on March 17, 2022. The site consists of an approximately 4.1-acre tract of undeveloped property located at 400 Hesters Crossing Road in Round Rock, Texas. Exhibit 1 (attached) is a site location map depicting the site in relation to the surrounding area. The areas immediately surrounding the site are a mix of residential and commercial properties. Site elevation ranges from about 810 feet above mean sea level (msl) to about 780 feet msl and slopes to the northwest.


The surficial geologic units present at the site have been identified as the Buda Formation and the Del Rio Formation. Exhibit 2 (attached) is a geologic map of the site. The Buda Formation consists of calcareous, fossiliferous hard limestone that is somewhat glauconitic. The Buda is about 30 feet thick in the area and forms the upper confining unit for the Edwards Aquifer. The Del Rio Formation consists of calcareous, fossiliferous clay that commonly contains pyrite and gypsum. The Del Rio is about 50 feet thick in the area and is part of the upper confining unit for the Edwards Aquifer and is generally characterized as an aquitard. The unit is poorly exposed in slopes below the Buda and produces a distinct break in slope with the overlying Buda. The fossil oyster *Ilymatogyra arietina* is very abundant and are locally known as "rams horns". The site is located within both the recharge zone and the transition zone of the Edwards Aquifer. The recharge zone boundary crosses the site as shown on Exhibit 1. Table 1 (attached) is a stratigraphic column prepared for the site. Exposure of the Buda and del Rio Formations onsite is obscured by the existing vegetation and soil cover. The completed Geologic Assessment form is attached. Table 1 (attached) is a stratigraphic column prepared for the site.


Based on a review of site topography, aerial photographs, and published geologic maps, there are no mapped faults located onsite and no field evidence of onsite faulting was observed. The nearest mapped fault (locally referred to as the Chandler Fault) is located approximately 50 feet west-northwest of the site. The fault is associated with the Balcones fault zone, which is comprised of en echelon, normal, high-angle faults, that are generally down thrown to the southeast and represents the dominant structural trend of the area.


No sensitive geologic features (feature score above 40 points) were observed on the site. Due to the lack of any sensitive recharge features observed on the site and the presence of a relatively impermeable soil cover present, the potential for fluid movement to the Edwards aquifer beneath the site is considered low.



3/25/2022







Water Pollution Abatement Plan Application

Texas Commission on Environmental Quality

for Regulated Activities on the Edwards Aquifer Recharge Zone and Relating to 30 TAC §213.5(b), Effective June 1, 1999

To ensure that the application is administratively complete, confirm that all fields in the form are complete, verify that all requested information is provided, consistently reference the same site and contact person in all forms in the application, and ensure forms are signed by the appropriate party.

Note: Including all the information requested in the form and attachments contributes to more streamlined technical reviews.

Signature

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. This **Water Pollution Abatement Plan Application Form** is hereby submitted for TCEQ review and Executive Director approval. The form was prepared by:

Print Name of Customer/Agent: Anna Hoge
Date: 6 8 23
Signature of Customer/Agent:
Regulated Entity Name: Hesters 4
Regulated Entity Information
1. The type of project is:
 Residential: Number of Lots: ✓ Residential: Number of Living Unit Equivalents: 144 ✓ Commercial Industrial Other:
2. Total site acreage (size of property): 4.176
3. Estimated projected population: 288
4. The amount and type of impervious cover expected after construction are shown below:

Table 1 - Impervious Cover Table

Impervious Cover of Proposed Project	Sq. Ft.	Sq. Ft./Acre	Acres
Structures/Rooftops	72,812	÷ 43,560 =	1.671
Parking	40,995	÷ 43,560 =	0.94
Other paved surfaces		÷ 43,560 =	
Total Impervious Cover	113,807	÷ 43,560 =	2.612

Total Impervious Cover $\frac{2.656}{}$ ÷ Total Acreage $\frac{4.176}{}$ X 100 = $\frac{62.6}{}$ % Impervious Cover

- 5. Attachment A Factors Affecting Surface Water Quality. A detailed description of all factors that could affect surface water and groundwater quality that addresses ultimate land use is attached.
- 6. Only inert materials as defined by 30 TAC §330.2 will be used as fill material.

For Road Projects Only

Complete questions 7 - 12 if this application is exclusively for a road project.

7.	Type of project:
	 TXDOT road project. County road or roads built to county specifications. City thoroughfare or roads to be dedicated to a municipality. Street or road providing access to private driveways.
8.	Type of pavement or road surface to be used:
	Concrete Asphaltic concrete pavement Other:
9.	Length of Right of Way (R.O.W.): feet.
	Width of R.O.W.: feet. $L \times W = Ft^2 \div 43,560 Ft^2/Acre = acres.$
10.	Length of pavement area: feet.
	Width of pavement area: feet. L x W = $Ft^2 \div 43,560 Ft^2/Acre =$ acres. Pavement area acres \div R.O.W. area acres x $100 =$ % impervious cover.
11.	A rest stop will be included in this project.
	A rest stop will not be included in this project.

TCEQ Executive Director. Mod	sting roadways that do not require approval from the ifications to existing roadways such as widening ng more than one-half (1/2) the width of one (1) existing om the TCEQ.
Stormwater to be gene	rated by the Proposed Project
volume (quantity) and charact occur from the proposed projection quality and quantity are based	haracter of Stormwater. A detailed description of the er (quality) of the stormwater runoff which is expected to ect is attached. The estimates of stormwater runoff on the area and type of impervious cover. Include the or both pre-construction and post-construction conditions
Wastewater to be gene	rated by the Proposed Project
14. The character and volume of wast	ewater is shown below:
% Domestic % Industrial % Commingled TOTAL gallons/day	26 <u>9,568</u> Gallons/day Gallons/day Gallons/day
15. Wastewater will be disposed of by	<i>r</i> :
On-Site Sewage Facility (OSSF/	Septic Tank):
will be used to treat and di licensing authority's (authority's (authority's (authority)) the land is suitable for the the requirements for on-sire relating to On-site Sewage Each lot in this project/dev size. The system will be de	Letter from Authorized Agent. An on-site sewage facility spose of the wastewater from this site. The appropriate orized agent) written approval is attached. It states that use of private sewage facilities and will meet or exceed the sewage facilities as specified under 30 TAC Chapter 285 Facilities. elopment is at least one (1) acre (43,560 square feet) in esigned by a licensed professional engineer or registered a licensed installer in compliance with 30 TAC Chapter
Sewage Collection System (Sev	ver Lines):
to an existing SCS.	n the wastewater generating facilities will be connected in the wastewater generating facilities will be connected
The SCS was previously subThe SCS was submitted witThe SCS will be submitted a be installed prior to Execut	h this application. at a later date. The owner is aware that the SCS may not

East Regional WWTP

✓ The sewage collection system will convey the wastewater to the (name) Treatment Plant. The treatment facility is:	
✓ Existing.☐ Proposed.	
16. 🗹 All private service laterals will be inspected as required in 30 TAC §213.5.	
Site Plan Requirements	
Items 17 – 28 must be included on the Site Plan.	
17. $\boxed{\ }$ The Site Plan must have a minimum scale of 1" = 400'.	
Site Plan Scale: $1'' = 30$ '.	
18. 100-year floodplain boundaries:	
 ✓ Some part(s) of the project site is located within the 100-year floodplain. The flo is shown and labeled. ✓ No part of the project site is located within the 100-year floodplain. The 100-year floodplain boundaries are based on the following specific (including damaterial) sources(s): 	·
19. The layout of the development is shown with existing and finished contours at appropriate, but not greater than ten-foot contour intervals. Lots, recreation celbuildings, roads, open space, etc. are shown on the plan.	nters,
The layout of the development is shown with existing contours at appropriate, by greater than ten-foot intervals. Finished topographic contours will not differ from existing topographic configuration and are not shown. Lots, recreation centers, buildings, roads, open space, etc. are shown on the site plan.	
20. All known wells (oil, water, unplugged, capped and/or abandoned, test holes, etc.):	
There are (#) wells present on the project site and the locations are shown labeled. (Check all of the following that apply)	n and
 The wells are not in use and have been properly abandoned. The wells are not in use and will be properly abandoned. The wells are in use and comply with 16 TAC §76. 	
igwedge There are no wells or test holes of any kind known to exist on the project site.	
21. Geologic or manmade features which are on the site:	
 All sensitive geologic or manmade features identified in the Geologic Assessn shown and labeled. No sensitive geologic or manmade features were identified in the Geologic Assessment. 	าent are
Attachment D - Exception to the Required Geologic Assessment. A request justification for an exception to a portion of the Geologic Assessment is attac	

22. 🗸	The drainage patterns and approximate slopes anticipated after major grading activities
23. 🗸	Areas of soil disturbance and areas which will not be disturbed.
24. 🗸	Locations of major structural and nonstructural controls. These are the temporary and permanent best management practices.
25.	Locations where soil stabilization practices are expected to occur.
26. 🗸	Surface waters (including wetlands).
	N/A
27. 🔽	Locations where stormwater discharges to surface water or sensitive features are to occur.
	There will be no discharges to surface water or sensitive features.
28. 🗸	Legal boundaries of the site are shown.
Adm	ninistrative Information
29. 🗸	Submit one (1) original and one (1) copy of the application, plus additional copies as needed for each affected incorporated city, groundwater conservation district, and county in which the project will be located. The TCEQ will distribute the additional copies to these jurisdictions. The copies must be submitted to the appropriate regional office.
30. 🔽	Any modification of this WPAP will require Executive Director approval, prior to construction, and may require submission of a revised application, with appropriate fees

ATTACHMENT "A"

FACTORS AFFECTING WATER QUALITY

Factors that could affect the quality of surface water and ground water are the parking and use of motor vehicles on the site. This includes the emission of certain hydrocarbon based substances as well as the tracking of silt. Also, the maintenance of lawn areas could affect the quality of surface water and ground water through runoff of chemical fertilizers or pesticides.

Texas Commission on Environmental Quality

TSS Removal Calculations 04-20-2009

Project Name: Hesters 4 Date Prepared: 02/08/23. Additional information is provided for cells with a red triangle in the upper right corner. Place the cursor over the cell.

Text shown in blue indicate location of instructions in the Technical Guidance Manual - RG-348.

Characters shown in red are data entry fields. Characters shown in black (Bold) are calculated fields. Changes to these fields will remove the equations used in the spreadsheet.

1. The Required Load Reduction for the total project:

Pages 3-27 to 3-30

Calculations from RG-348

where:

Page 3-29 Equation 3.3: $L_M = 27.2(A_N \times P)$

LM TOTAL PROJECT = Required TSS removal resulting from the proposed development = 80% of increased load

A_N = Net increase in impervious area for the project

P = Average annual precipitation, inches

Site Data: Determine Required Load Removal Based on the Entire Project

inches acres acres County = Williamson Predevelopment impervious area within the limits of the plan * = Total post-development impervious area within the limits of the plan * = Total post-development impervious cover fraction * = П Total project area included in plan *=

lbs. 2363 LM TOTAL PROJECT =

* The values entered in these fields should be for the total project area.

Number of drainage basins / outfalls areas leaving the plan area =

2. Drainage Basin Parameters (This information should be provided for each basin):

	acres	acres	acres		lbs.
~	4.18	0.00	2.71	0.65	2363
Drainage Basin/Outfall Area No. =	Total drainage basin/outfall area =	Predevelopment impervious area within drainage basin/outfall area =	Post-development impervious area within drainage basin/outfall area =	Post-development impervious fraction within drainage basin/outfall area =	L _M THIS BASIN =

3. Indicate the proposed BMP Code for this basin.

percent Proposed BMP = Sand Filter moval efficiency = 89 Removal efficiency =

Aqualogic Cartridge Filter

Contech Storm Filter
Constructed Wetland
Extended Detention
Grassy Swale
Retention / Irrigation
Sand Filter
Stormceptor
Vegetated Filter Strips Bioretention Vortechs Wet Basin Wet Vault

4. Calculate Maximum TSS Load Removed (L_R) for this Drainage Basin by the selected BMP Type.

RG-348 Page 3-33 Equation 3.7: L_R = (BMP efficiency) x P x (A_I x 34.6 + A_P x 0.54)

 $A_{\mbox{\scriptsize c}}$ = Total On-Site drainage area in the BMP catchment area A_{I} = Impervious area proposed in the BMP catchment area A_{P} = Pervious area remaining in the BMP catchment area

where:

 $L_{\rm R}$ = TSS Load removed from this catchment area by the proposed BMP

acres ы н Р_С

acres lbs 4.18 2.71 1.46 2698 A_P =

5. Calculate Fraction of Annual Runoff to Treat the drainage basin / outfall area

lbs. 2363 Desired L_{M THIS BASIN} =

0.88

6. Calculate Capture Volume required by the BMP Type for this drainage basin / outfall area.

Pages 3-34 to 3-36

Calculations from RG-348

inches 1.50 0.46 10451 Rainfall Depth =
Post Development Runoff Coefficient =
On-site Water Quality Volume =

Calculations from RG-348 Pages 3-36 to 3-37

cubic feet

acres	acres			cubic foot
0.00	0.00	0	0.00	c
Off-site area draining to BMP =	Off-site Impervious cover draining to BMP =	Impervious fraction of off-site area =	Off-site Runoff Coefficient =	Off-eite Water Ouglity Volume =

Storage for Sediment = 2090

Total Capture Volume (required water quality volume(s) x 1.20) = 12541 cubic feet

The following sections are used to calculate the required water quality volume(s) for the selected BMP.

The values for BMP Types not selected in celf C45 will show NA.

Designed as Required in RG-348

Pages 3-58 to 3-63

9A. Full Sedimentation and Filtration System

Water Quality Volume for sedimentation basin =

square feet 581 Minimum filter basin area =

cubic feet

12541

Maximum sedimentation basin area = Minimum sedimentation basin area =

square feet For minimum water depth of 2 feet square feet For maximum water depth of 8 feet 5225 1306

9B. Partial Sedimentation and Filtration System

cubic feet 12541 Water Quality Volume for combined basins = square feet 1045 Minimum filter basin area =

square feet For minimum water depth of 2 feet square feet For maximum water depth of 8 feet Maximum sedimentation basin area = Minimum sedimentation basin area =

4180 261

ATTACHMENT "B"

VOLUME AND CHARACTER OF STORMWATER

It is expected that the character of surface water and ground water run-off would be consistent with the development of a multifamily. Constituents would include hydrocarbon based product residues, silt, pesticides, and chemicals resulting from vehicular emissions and landscape maintenance.

The expected volume of run-off was based on the SCS method. This was calculated using curve numbers, which are based on impervious cover and the nature of surfaces over which run-off water flows. These calculations are presented in the HEC-HMS model submitted with this application. The stormwater quality for the site was determined using "Complying with the Edwards Aquifer Rules: Technical Guidance on Best Management Practices". The results from these calculations are presented next page.

ATTACHMENT "C"

SUITABILITY LETTER FROM AUTHORIZED AGENT

There is no OSSF proposed with this project.

ATTACHMENT "D"

EXCEPTION TO THE REQUIRED GEOLOGIC ASSESSMENT

An exception request for the site geologic assessment is not being made.

Temporary Stormwater Section

Texas Commission on Environmental Quality

for Regulated Activities on the Edwards Aquifer Recharge Zone and Relating to 30 TAC §213.5(b)(4)(A), (B), (D)(I) and (G); Effective June 1, 1999

To ensure that the application is administratively complete, confirm that all fields in the form are complete, verify that all requested information is provided, consistently reference the same site and contact person in all forms in the application, and ensure forms are signed by the appropriate party.

Note: Including all the information requested in the form and attachments contributes to more streamlined technical reviews.

Signature

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. This **Temporary Stormwater Section** is hereby submitted for TCEQ review and executive director approval. The application was prepared by:

Print Name of Customer/Agent: <u>Anna</u> Hoge
Date: <u>5/11/</u> 2023
Signature of Customer/Agent:
Mus Du Hose
Regulated Entity Name: Hesters 4

Project Information

Potential Sources of Contamination

Examples: Fuel storage and use, chemical storage and use, use of asphaltic products, construction vehicles tracking onto public roads, and existing solid waste.

1.	Fuels for construction equipment and hazardous substances which will be used during construction:
	The following fuels and/or hazardous substances will be stored on the site:
	These fuels and/or hazardous substances will be stored in:
	Aboveground storage tanks with a cumulative storage capacity of less than 250 gallons will be stored on the site for less than one (1) year.

	 Aboveground storage tanks with a cumulative storage capacity between 250 gallons and 499 gallons will be stored on the site for less than one (1) year. Aboveground storage tanks with a cumulative storage capacity of 500 gallons or more will be stored on the site. An Aboveground Storage Tank Facility Plan application must be submitted to the appropriate regional office of the TCEQ prior to moving the tanks onto the project.
	Fuels and hazardous substances will not be stored on the site.
2.	Attachment A - Spill Response Actions. A site specific description of the measures to be taken to contain any spill of hydrocarbons or hazardous substances is attached.
3.	Temporary aboveground storage tank systems of 250 gallons or more cumulative storage capacity must be located a minimum horizontal distance of 150 feet from any domestic, industrial, irrigation, or public water supply well, or other sensitive feature.
4.	Attachment B - Potential Sources of Contamination. A description of any activities or processes which may be a potential source of contamination affecting surface water quality is attached.
S	equence of Construction
5.	Attachment C - Sequence of Major Activities. A description of the sequence of major activities which will disturb soils for major portions of the site (grubbing, excavation, grading, utilities, and infrastructure installation) is attached.
	 For each activity described, an estimate (in acres) of the total area of the site to be disturbed by each activity is given. For each activity described, include a description of appropriate temporary control measures and the general timing (or sequence) during the construction process that the measures will be implemented.
6.	Name the receiving water(s) at or near the site which will be disturbed or which will receive discharges from disturbed areas of the project: <u>Lake Creek</u>
Te	emporary Best Management Practices (TBMPs)
sta coi	osion control examples: tree protection, interceptor swales, level spreaders, outlet abilization, blankets or matting, mulch, and sod. Sediment control examples: stabilized instruction exit, silt fence, filter dikes, rock berms, buffer strips, sediment traps, and sediment sins. Please refer to the Technical Guidance Manual for guidelines and specifications. All

7. Attachment D – Temporary Best Management Practices and Measures. TBMPs and

measures will prevent pollution of surface water, groundwater, and stormwater. The construction-phase BMPs for erosion and sediment controls have been designed to

retain sediment on site to the extent practicable. The following information is attached:

structural BMPs must be shown on the site plan.

 ✓ A description of how BMPs and measures will prevent pollution of surface water, groundwater or stormwater that originates upgradient from the site and flows across the site. ✓ A description of how BMPs and measures will prevent pollution of surface water or groundwater that originates on-site or flows off site, including pollution caused by contaminated stormwater runoff from the site. ✓ A description of how BMPs and measures will prevent pollutants from entering
surface streams, sensitive features, or the aquifer. A description of how, to the maximum extent practicable, BMPs and measures will maintain flow to naturally-occurring sensitive features identified in either the geologic assessment, TCEQ inspections, or during excavation, blasting, or construction.
The temporary sealing of a naturally-occurring sensitive feature which accepts recharge to the Edwards Aquifer as a temporary pollution abatement measure during active construction should be avoided.
 Attachment E - Request to Temporarily Seal a Feature. A request to temporarily seal a feature is attached. The request includes justification as to why no reasonable and practicable alternative exists for each feature. ✓ There will be no temporary sealing of naturally-occurring sensitive features on the site.
Attachment F - Structural Practices. A description of the structural practices that will be used to divert flows away from exposed soils, to store flows, or to otherwise limit runoff discharge of pollutants from exposed areas of the site is attached. Placement of structural practices in floodplains has been avoided.
Attachment G - Drainage Area Map. A drainage area map supporting the following requirements is attached:
 For areas that will have more than 10 acres within a common drainage area disturbed at one time, a sediment basin will be provided. For areas that will have more than 10 acres within a common drainage area disturbed at one time, a smaller sediment basin and/or sediment trap(s) will be used.
 For areas that will have more than 10 acres within a common drainage area disturbed at one time, a sediment basin or other equivalent controls are not attainable, but other TBMPs and measures will be used in combination to protect down slope and side slope boundaries of the construction area. There are no areas greater than 10 acres within a common drainage area that will be disturbed at one time. A smaller sediment basin and/or sediment trap(s) will be used in combination with other erosion and sediment controls within each disturbed drainage area.

There are no areas greater than 10 acres within a common drainage area that will be disturbed at one time. Erosion and sediment controls other than sediment basins or sediment traps within each disturbed drainage area will be used. 11. Attachment H - Temporary Sediment Pond(s) Plans and Calculations. Temporary sediment pond or basin construction plans and design calculations for a proposed temporary BMP or measure have been prepared by or under the direct supervision of a Texas Licensed Professional Engineer. All construction plans and design information must be signed, sealed, and dated by the Texas Licensed Professional Engineer. Construction plans for the proposed temporary BMPs and measures are attached. ✓ N/A 12. Attachment I - Inspection and Maintenance for BMPs. A plan for the inspection of each temporary BMP(s) and measure(s) and for their timely maintenance, repairs, and, if necessary, retrofit is attached. A description of the documentation procedures, recordkeeping practices, and inspection frequency are included in the plan and are specific to the site and/or BMP. 13. 🖊 All control measures must be properly selected, installed, and maintained in accordance with the manufacturer's specifications and good engineering practices. If periodic inspections by the applicant or the executive director, or other information indicate a control has been used inappropriately, or incorrectly, the applicant must replace or modify the control for site situations. 14. If sediment escapes the construction site, off-site accumulations of sediment must be removed at a frequency sufficient to minimize offsite impacts to water quality (e.g., fugitive sediment in street being washed into surface streams or sensitive features by the next rain). 15. Sediment must be removed from sediment traps or sedimentation ponds not later than when design capacity has been reduced by 50%. A permanent stake will be provided that can indicate when the sediment occupies 50% of the basin volume. 16. Litter, construction debris, and construction chemicals exposed to stormwater shall be prevented from becoming a pollutant source for stormwater discharges (e.g., screening outfalls, picked up daily). Soil Stabilization Practices

Examples: establishment of temporary vegetation, establishment of permanent vegetation, mulching, geotextiles, sod stabilization, vegetative buffer strips, protection of trees, or preservation of mature vegetation.

17. Attachment J - Schedule of Interim and Permanent Soil Stabilization Practices. A schedule of the interim and permanent soil stabilization practices for the site is attached.

- 18. Records must be kept at the site of the dates when major grading activities occur, the dates when construction activities temporarily or permanently cease on a portion of the site, and the dates when stabilization measures are initiated.
- 19. Stabilization practices must be initiated as soon as practicable where construction activities have temporarily or permanently ceased.

Administrative Information

- 20. All structural controls will be inspected and maintained according to the submitted and approved operation and maintenance plan for the project.
- 21. If any geologic or manmade features, such as caves, faults, sinkholes, etc., are discovered, all regulated activities near the feature will be immediately suspended. The appropriate TCEQ Regional Office shall be immediately notified. Regulated activities must cease and not continue until the TCEQ has reviewed and approved the methods proposed to protect the aquifer from any adverse impacts.
- 22. Silt fences, diversion berms, and other temporary erosion and sediment controls will be constructed and maintained as appropriate to prevent pollutants from entering sensitive features discovered during construction.

ATTACHMENT A SPILL RESPONSE ACTIONS

1.4.16 Spill Prevention and Control

The objective of this section is to describe measures to prevent or reduce the discharge of pollutants to drainage systems or watercourses from leaks and spills by reducing the chance for spills, stopping the source of spills, containing and cleaning up spills, properly disposing of spill materials, and training employees. The following steps will help reduce the stormwater impacts of leaks and spills:

Education

- (1) Be aware that different materials pollute in different amounts. Make sure that each employee knows what a "significant spill" is for each material they use, and what is the appropriate response for "significant" and "insignificant" spills. Employees should also be aware of when spill must be reported to the TCEQ. Information available in 30 TAC 327.4 and 40 CFR 302.4.
- (2) Educate employees and subcontractors on potential dangers to humans and the environment from spills and leaks.
- (3) Hold regular meetings to discuss and reinforce appropriate disposal procedures (incorporate into regular safety meetings).
- (4) Establish a continuing education program to indoctrinate new employees.
- (5) Have contractor's superintendent or representative oversee and enforce proper spill prevention and control measures.

General Measures

- (1) To the extent that the work can be accomplished safely, spills of oil, petroleum products, substances listed under 40 CFR parts 110,117, and 302, and sanitary and septic wastes should be contained and cleaned up immediately.
- (2) Store hazardous materials and wastes in covered containers and protect from vandalism.
- (3) Place a stockpile of spill cleanup materials where it will be readily accessible.
- (4) Train employees in spill prevention and cleanup.
- (5) Designate responsible individuals to oversee and enforce control measures.

- (6) Spills should be covered and protected from stormwater runoff during rainfall to the extent that it doesn't compromise cleanup activities.
- (7) Do not bury or wash spills with water.
- (8) Store and dispose of used clean up materials, contaminated materials, and recovered spill material that is no longer suitable for the intended purpose in conformance with the revisions in applicable BMPs.
- (9) Do not allow water used for cleaning and decontamination to enter storm drains or watercourses. Collect and dispose of contaminated water in accordance with applicable regulations.
- (10) Contain water overflow or minor water spillage and do not allow it to discharge into drainage facilities or watercourses.
- (11) Place Material Safety Data Sheets (MSDS), as well as proper storage, cleanup, and spill reporting instructions for hazardous materials stored or used on the project site in an open, conspicuous, and accessible location.
- (12) Keep waste storage areas clean, well-organized, and equipped with ample cleanup supplies as appropriate for the materials being stored. Perimeter controls, containment structures, covers, and liners should be repaired or replaced as needed to maintain proper function.

Cleanup

- (1) Clean up leaks and spills immediately.
- (2) Use a rag for small spills on paved surfaces, a damp mop for general cleanup, and absorbent material for larger spills. If the spilled material is hazardous, then the used cleanup materials are also hazardous and must be disposed of as hazardous waste.
- (3) Never hose down or bury dry material spills. Clean up as much of the material as possible and dispose of properly. See the waste management BMPs in this section for specific information.

Minor Spills

- (1) Minor spills typically involve small quantities of oil, gasoline, paint, etc. which can be controlled by the first responder at the discovery of the spill.
- (2) Use absorbent materials on small spills rather than hosing down or burying the spill.
- (3) Absorbent materials should be promptly removed and disposed of properly.
- (4) Follow the practice below for a minor spill:
- (5) Contain the spread of the spill.
- (6) Recover spilled materials.
- (7) Clean the contaminated area and properly dispose of contaminated materials.

Semi-Significant Spills

Semi-significant spills still can be controlled by the first responder along with the aid of other personnel such as laborers and the foreman, etc. This response may require the cessation of all other activities. Spills should be cleaned up immediately:

- (1) Contain spread of the spill.
- (2) Notify the project foreman immediately.
- (3) If the spill occurs on paved or impermeable surfaces, clean up using "dry" methods absorbent materials, cat litter and/or rags). Contain the spill by encircling with absorbent materials and do not let the spill spread widely.
- (4) If the spill occurs in dirt areas, immediately contain the spill by constructing an earthen dike. Dig up and properly dispose of contaminated soil.
- (5) If the spill occurs during rain, cover spill with tarps or other material to prevent contaminating runoff.

Significant/Hazardous Spills

For significant or hazardous spills that are in reportable quantities:

(1) Notify the TCEQ by telephone as soon as possible and within 24 hours at 512-339-2929 (Austin) or 210-490-3096 (San Antonio) between 8 AM and 5 PM. After hours, contact the Environmental Release Hotline at 1-800-832-8224. It is

the contractor's responsibility to have all emergency phone numbers at the construction site.

ATTACHMENT B POTENTIAL SOURCES OF CONTAMINATION

There are no other potential sources of contamination during the development of this site except soil sediments from erosion, leaking fuel or oil from construction vehicles and human litter. Refer to Attachment A for the spill response actions during construction.

ATTACHMENT C SEQUENCE OF MAJOR ACTIVITIES

- 1. Install temporary erosion control measures and tree protection fencing. Controls shall be in place before the pre-construction meeting.
- 2. The contractor shall give the City of Round Rock 48 hours notice before beginning each phase of construction. Telephone 512-801-4460 (Inspectors)
- 3. Call DIG TESS Texas Excavation Safety System at (800) 344-8377 for utility location.
- 4. Rough-cut and grading of site work. The drainage system shall be protected from erosion and shall be maintained throughout the course of construction until final restoration is achieved.
- 5. Construct utilities under paved areas and above ground structures.
- 6. Install irrigation and landscaping.
- 7. Restore all areas disturbed by construction activities.
- 8. Contractor to coordinate engineer's and landscapes architect's concurrence letters and City's final inspection after receipt of concurrence letters.
- 9. Complete permanent erosion control and site restoration. Remove and dispose of temporary erosion control measures. Restore any areas disturbed during removal of erosion/sedimentation controls.

ATTACHMENT D TEMPORARY BEST MANAGEMENT PRACTICES AND MEASURES

The project construction site will have temporary erosion control measures including silt fence, mulch sock, inlet protection devices, and stabilized construction entrance. The sediment controls will be in place before any construction activity begins and will encompass the project site. Please refer to the Notes Sheet on sheet 2 for the Texas Commission on Environmental Quality Water Pollution Abatement Plan General Construction Notes.

Silt fences or mulch socks will be placed downstream of all areas to be disturbed by construction. The silt fence and mulch sock will remove any sediment particles from the stormwater runoff flowing off the site by causing the runoff to pond and allowing heavier solids to settle out. There are no up-gradient flows across the site. After every rainfall, the sediment controls will be checked for integrity. Obstructions, silt, or pollutant accumulations will be removed and properly disposed of at an approved location. The control will be rehabilitated after the maintenance to a condition which will insure its proper performance for the next rainfall event. There are no known naturally occurring sensitive features on or near the project site that would require additional Temporary Best Management Practices and Measures. Inlet protection devices including filter fabric material will be placed at all storm sewer inlets. All temporary measures will be in place during all construction activities and not removed until construction is finished, and Revegetation is established.

ATTACHMENT E REQUEST TO TEMPORARILY SEAL A FEATURE

We are not requesting to seal any feature.

ATTACHMENT F STRUCTURAL PRACTICES

Silt fencing and	mulch socks	s will be plac	ed on the o	down gradie	nt side of any	exposed
soils in order to	limit the disc	charge of silt	and pollu	tants from ex	xposed areas	of the site.

ATTACHMENT G DRAINAGE AREA MAPS

Please refer to Sheet 29 – Existing Drainage Plan and Sheet 30 – Proposed Drainage Plan for the drainage area maps.

ATTACHMENT H

TEMPORARY SEDIMENT POND(S) PLANS & CALCULATIONS

This site has an area no greater than ten acres within a common drainage area that will be disturbed at one time. Erosion and sediments control other than a sediment pond or trap within disturbed drainage area will be used. All plans are signed by a Texas Licensed Professional Engineer.

ATTACHMENT I INSPECTION AND MAINTENANCE FOR BMP'S

Silt fences and mulch socks must be inspected once per week and after significant rainfall events to check for damage and accumulated silt and debris. Any damaged fence must be replaced immediately, and silt or debris accumulations removed.

Inlet protection control structures require frequent maintenance to prevent clogging. Accumulated silt shall be removed when it reaches a depth of two (2) inches or one-third the height of the inlet throat and disposed of in a manner which will not cause additional siltation.

The stabilized construction entrance shall be maintained in a condition which will prevent tracking or flowing of sediment onto public rights of way. This may require periodic top dressing with additional stone as conditions demand and repair and/or clean out of any measures used to trap sediment. All sediment spilled, dropped, washed, or tracked onto public rights of way must be removed immediately by contractor. When necessary, wheels must be cleaned to remove sediment prior to entrance onto public right of way. When washing is required, it shall be done on an area stabilized with crushed stone which drains into an approved sediment trap or sediment basin. All sediment shall be prevented from entering any storm drain, ditch or watercourse using approved methods.

ATTACHMENT J SCHEDULE OF INTERIM AND PERMANENT SOIL STABILIZATION PRACTICES

As indicated in the construction sequence, silt fence will be in place prior to clearing or grading of any portions of the site. Once construction activities cease permanently, all disturbed areas will be stabilized with permanent seeding and sodding. All seeding shall be in accordance with the Erosion and Sedimentation Control Notes found on Sheet 02 – Note Sheet of the construction plans.

Permanent Stormwater Section

Texas Commission on Environmental Quality

Print Name of Customer/Agent: Anna Hoge

for Regulated Activities on the Edwards Aquifer Recharge Zone and Relating to 30 TAC §213.5(b)(4)(C), (D)(Ii), (E), and (5), Effective June 1, 1999

To ensure that the application is administratively complete, confirm that all fields in the form are complete, verify that all requested information is provided, consistently reference the same site and contact person in all forms in the application, and ensure forms are signed by the appropriate party.

Note: Including all the information requested in the form and attachments contributes to more streamlined technical reviews.

Signature

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. This **Permanent Stormwater Section** is hereby submitted for TCEQ review and executive director approval. The application was prepared by:

Date: <u>(4/8/2-3</u>
Signature of Customer/Agent
and Su Ha
Regulated Entity Name: Hesters 4
Permanent Best Management Practices (BMPs)
Permanent best management practices and measures that will be used during and after construction is completed.
 Permanent BMPs and measures must be implemented to control the discharge of pollution from regulated activities after the completion of construction.
□ N/A
These practices and measures have been designed, and will be constructed, operated, and maintained to insure that 80% of the incremental increase in the annual mass loading of total suspended solids (TSS) from the site caused by the regulated activity is removed. These quantities have been calculated in accordance with technical guidance prepared or accepted by the executive director.
4

	A technical guidance other than the TCEQ TGM was used to design permanent BMPs and measures for this site. The complete citation for the technical guidance that was used is:
	□ N/A
3.	Owners must insure that permanent BMPs and measures are constructed and function as designed. A Texas Licensed Professional Engineer must certify in writing that the permanent BMPs or measures were constructed as designed. The certification letter must be submitted to the appropriate regional office within 30 days of site completion.
	□ N/A
4.	Where a site is used for low density single-family residential development and has 20 % or less impervious cover, other permanent BMPs are not required. This exemption from permanent BMPs must be recorded in the county deed records, with a notice that if the percent impervious cover increases above 20% or land use changes, the exemption for the whole site as described in the property boundaries required by 30 TAC §213.4(g) (relating to Application Processing and Approval), may no longer apply and the property owner must notify the appropriate regional office of these changes.
	 The site will be used for low density single-family residential development and has 20% or less impervious cover. The site will be used for low density single-family residential development but has more than 20% impervious cover. ✓ The site will not be used for low density single-family residential development.
5.	The executive director may waive the requirement for other permanent BMPs for multifamily residential developments, schools, or small business sites where 20% or less impervious cover is used at the site. This exemption from permanent BMPs must be recorded in the county deed records, with a notice that if the percent impervious cover increases above 20% or land use changes, the exemption for the whole site as described in the property boundaries required by 30 TAC §213.4(g) (relating to Application Processing and Approval), may no longer apply and the property owner must notify the appropriate regional office of these changes.
	 Attachment A - 20% or Less Impervious Cover Waiver. The site will be used for multi-family residential developments, schools, or small business sites and has 20% or less impervious cover. A request to waive the requirements for other permanent BMPs and measures is attached. ✓ The site will be used for multi-family residential developments, schools, or small business sites but has more than 20% importances.
	business sites but has more than 20% impervious cover. The site will not be used for multi-family residential developments, schools, or small business sites.
6.	Attachment B - BMPs for Upgradient Stormwater.

	 A description of the BMPs and measures that will be used to prevent pollution of surface water, groundwater, or stormwater that originates upgradient from the site and flows across the site is attached. ✓ No surface water, groundwater or stormwater originates upgradient from the site and flows across the site, and an explanation is attached. ✓ Permanent BMPs or measures are not required to prevent pollution of surface water, groundwater, or stormwater that originates upgradient from the site and flows across the site, and an explanation is attached.
7.	Attachment C - BMPs for On-site Stormwater.
	 ✓ A description of the BMPs and measures that will be used to prevent pollution of surface water or groundwater that originates on-site or flows off the site, including pollution caused by contaminated stormwater runoff from the site is attached. ✓ Permanent BMPs or measures are not required to prevent pollution of surface water or groundwater that originates on-site or flows off the site, including pollution caused by contaminated stormwater runoff, and an explanation is attached.
8.	Attachment D - BMPs for Surface Streams. A description of the BMPs and measures that prevent pollutants from entering surface streams, sensitive features, or the aquifer is attached. Each feature identified in the Geologic Assessment as sensitive has been addressed.
	□ N/A
9.	The applicant understands that to the extent practicable, BMPs and measures must maintain flow to naturally occurring sensitive features identified in either the geologic assessment, executive director review, or during excavation, blasting, or construction.
	 ✓ The permanent sealing of or diversion of flow from a naturally-occurring sensitive feature that accepts recharge to the Edwards Aquifer as a permanent pollution abatement measure has not been proposed. ✓ Attachment E - Request to Seal Features. A request to seal a naturally-occurring sensitive feature, that includes, for each feature, a justification as to why no reasonable and practicable alternative exists, is attached.
10.	Attachment F - Construction Plans. All construction plans and design calculations for the proposed permanent BMP(s) and measures have been prepared by or under the direct supervision of a Texas Licensed Professional Engineer, and are signed, sealed, and dated. The plans are attached and, if applicable include:
	 ✓ Design calculations (TSS removal calculations) ✓ TCEQ construction notes ✓ All geologic features ✓ All proposed structural BMP(s) plans and specifications
	LIN/A

insp	achment G - Inspection, Maintenance, Repair and Retrofit Plan . A plan for the pection, maintenance, repairs, and, if necessary, retrofit of the permanent BMPs and asures is attached. The plan includes all of the following:
	Prepared and certified by the engineer designing the permanent BMPs and measures Signed by the owner or responsible party Procedures for documenting inspections, maintenance, repairs, and, if necessary retrofit
	A discussion of record keeping procedures
N/A	
rece	achment H - Pilot-Scale Field Testing Plan. Pilot studies for BMPs that are not ognized by the Executive Director require prior approval from the TCEQ. A plan for ot-scale field testing is attached.
✓ N/A	A. Company of the com
of t and and crea by t	he measures that will be used to avoid or minimize surface stream contamination. A description dechanges in the way in which water enters a stream as a result of the construction development is attached. The measures address increased stream flashing, the ation of stronger flows and in-stream velocities, and other in-stream effects caused the regulated activity, which increase erosion that results in water quality gradation.
☐ N/A	
Respor	nsibility for Maintenance of Permanent BMP(s)
	ility for maintenance of best management practices and measures after on is complete.
unt ent owi owi resp	e applicant is responsible for maintaining the permanent BMPs after construction il such time as the maintenance obligation is either assumed in writing by another ity having ownership or control of the property (such as without limitation, an ner's association, a new property owner or lessee, a district, or municipality) or the nership of the property is transferred to the entity. Such entity shall then be ponsible for maintenance until another entity assumes such obligations in writing or nership is transferred.
□ N/A	A
app mu or a	copy of the transfer of responsibility must be filed with the executive director at the propriate regional office within 30 days of the transfer if the site is for use as a ltiple single-family residential development, a multi-family residential development, a non-residential development such as commercial, industrial, institutional, schools, a other sites where regulated activities occur.
N/A	

ATTACHMENT "A"

20% or LESS IMPERVIOUS COVER WAIVER

This project is not seeking an impervious cover waiver.

ATTACHMENT B BMP's FOR UPGRADIENT STORMWATER

There is no upgradient stormwater that flows across the site.

ATTACHMENT C BMPs FOR ON-SITE STORMWATER

I. Erosion Control

Disturbed areas will be stabilized to prevent the introduction of sediment to adjacent water bodies during wet weather conditions. **Revegetation**, **Mulch Socks** and **Filter Fabric (Silt) Fence** will be maintained and remain in place until the area has been stabilized.

II. Post Construction Total Suspended Solids Control

After construction has been completed and the site stabilized, total suspended solids (TSS) loadings shall be controlled by the **Partial Sedimentation/Filtration Water Quality Pond**.

III. Sedimentation Control

Prior to project initiation, the project area must be isolated from adjacent water bodies by the use of Filter Fabric (Silt) Fence and Mulch Socks.

ATTACHMENT D BMP's FOR SURFACE STREAMS

The water quality volume from the site will be cleaned by an on-site water quality pond before it enters any surface streams. The water quality pond volume will be released by the filtration basin pipe underdrain system. No runoff from developed areas of the site is released directly to any surface streams.

ATTACHMENT E

REQUEST TO SEAL FEATURES

We are not requesting to seal a feature.

ATTACHMENT F CONSTRUCTION PLANS

Please refer to the construction plans being submitted with this application for design calculations for the existing permanent BMP.

ATTACHMENT G INSPECTION, MAINTENANCE, REPAIR AND RETROFIT PLAN

SEDIMENTATION BASIN

Quarterly:

The level of accumulated silt in the basin shall be checked. If depth of silt exceeds 6 inches, it shall be removed and disposed of at an approved off-site disposal location.

The basin shall be checked for accumulated debris and trash. Excessive trash and debris shall be

removed. All debris and trash shall be removed at least every six months.

Annually:

The basin shall be inspected for structural integrity and repaired if necessary.

After Rainfall:

The basin shall be checked after each rainfall occurrence to ensure that it drains within 48 hours after the storm is over. If it does not drain within this time, corrective maintenance will be accomplished.

FILTRATION BASIN

Quarterly:

The level of accumulated silt shall be checked. If depth of silt/pollutants exceeds ½-inch, it shall be removed and disposed of at an approved off-site disposal location.

The accumulation of pollutants/oils shall be checked. If the pollutants have significantly reduced the designed capacity of the sand filter, the pollutants shall be removed.

The basin shall be checked for accumulated debris and trash. Excessive trash and debris shall be removed. All debris and trash shall be removed at least every six months.

Annually:

The basin shall be inspected for structural integrity and repaired if necessary.

After Rainfall:

The basin shall be checked after each rainfall occurrence to insure that it drains within 48 hours after the sedimentation basin has been emptied. If it does not drain within this time, corrective maintenance will be accomplished.

Following any required maintenance, the surface of the filtration basin shall be raked and leveled to restore the system to its designed condition.

Proper disposal of accumulated silt shall be accomplished following TCEQ and City of Austin guidelines and specifications.

Records of the inspections and cleaning shall be retained by the building management company.

An amended copy of this document will be provided to the Texas Natural Resource Conservation Commission within 30 days of any changes in the following information:

Responsible Party:

Hesters Crossing Apt Holdings LLC

Mailing Address:

155 Schmitt Blvd

City, State, Zip:

Farmingdale, NY 11735

Telephone/Fax:

(512)315-3515

Jonathan Marcus

6/29/23

Date

Signature of Responsible Party

ATTACHMENT H

PILOT-SCALE FIELD TESTING PLAN

Not applicable for this project. The BMP was designed using the "Complying with the Edwards Aquifer Rules: Technical Guidance for BMPs".

ATTACHMENT I MEASURES FOR MINIMIZING SURFACE STREAM CONTAMINATION

Under existing conditions, the site generally sheet drains from east to west into Lake Creek Tributary 6. In the developed condition, the runoff will be collected and flow through water quality and detention ponds.

A partial sedimentation/filtration pond is proposed for the development. The pond is designed using "Complying with the Edwards Aquifer Rules Technical Guidance on Best Management Practices. This pond will remove pollutants generated by the development to a level prescribed by the TCEQ.

To control the rate of runoff discharge from the developed site, a detention pond is being constructed. The detention pond will discharge at rates that are below the existing rates for the 2, 10, 25 and 100-year storms.

To control erosion in the creek due to the detention pond discharge, gabion mattresses and gabion baskets will be installed. They will spread and slow down the discharges from the pond.

All of these measures combined will protect the tributary from erosion and contamination.

Agent Authorization Form

For Required Signature
Edwards Aquifer Protection Program
Relating to 30 TAC Chapter 213
Effective June 1, 1999

I	Jonathan Marcu	S	
		Print Name	
(Owner		
		Title - Owner/President/Other	
of	Hesters Cross	sing Apts Holdings LLC	
01_		Corporation/Partnership/Entity Name	
hav	e authorized	Anna Hoge	
Print Name of Agent/Engineer			
of	Consort Inc.		
		Print Name of Firm	

to represent and act on the behalf of the above named Corporation, Partnership, or Entity for the purpose of preparing and submitting this plan application to the Texas Commission on Environmental Quality (TCEQ) for the review and approval consideration of regulated activities.

I also understand that:

- 1. The applicant is responsible for compliance with 30 Texas Administrative Code Chapter 213 and any condition of the TCEQ's approval letter. The TCEQ is authorized to assess administrative penalties of up to \$10,000 per day per violation.
- For those submitting an application who are not the property owner, but who have the right to control and possess the property, additional authorization is required from the owner.
- 3. Application fees are due and payable at the time the application is submitted. The application fee must be sent to the TCEQ cashier or to the appropriate regional office. The application will not be considered until the correct fee is received by the commission.
- 4. A notarized copy of the Agent Authorization Form must be provided for the person preparing the application, and this form must accompany the completed application.
- 5. No person shall commence any regulated activity on the Edwards Aquifer Recharge Zone, Contributing Zone or Transition Zone until the appropriate application for the activity has been filed with and approved by the Executive Director.

SIGNATURE PAGE:

	6/8/23
Applicant's Signature	Date ' I

THE STATE OF NY \$
County of SIFFOIK \$

BEFORE ME, the undersigned authority, on this day personally appeared <u>Vivril Vivril</u> known to me to be the person whose name is subscribed to the foregoing instrument, and acknowledged to me that (s)he executed same for the purpose and consideration therein expressed.

GIVEN under my hand and seal of office on this \(\frac{\gamma}{\lambda} \) day of \(\frac{\frac{\gamma(\gamma \epsilon)}{\gamma}}{\lambda} \).

MICHELLE ALLOCCA
Notary Public, State of New York
Reg. No. 01BE6216593
Qualified in Suffolk County
Commission Expires February 24, 20, 370

Ninkelli Cllocca NOTARY PUBLIC

Typed or Printed Name of Notary

MY COMMISSION EXPIRES:

Application Fee Form

Texas Commission on Environmental Quality Name of Proposed Regulated Entity: Hesters 4 Regulated Entity Location: 155 Schmitt Blvd., Farmingdale, NY 11735 Name of Customer: Jonathan Marcus Contact Person: Anna Hoge Phone: 512-469-0500				
Customer Reference Number (if issue				
Regulated Entity Reference Number		_		
Austin Regional Office (3373)		_		
Hays	Travis		⊘ wi	illiamson
San Antonio Regional Office (3362)				
Bexar	Medina		□Uv	ralde
Comal	Kinney			
Application fees must be paid by che		or money ord	ler, pavab	le to the Texas
Commission on Environmental Qual				
form must be submitted with your f				
Austin Regional Office		San Antonio R		
Mailed to: TCEQ - Cashier			_	CEQ - Cashier
Revenues Section		J	•	
Revenues Section 12100 Park 35 Circle Mail Code 214 Building A, 3rd Floor				
P.O. Box 13088 Austin, TX 78753				
Austin, TX 78711-3088				
Site Location (Check All That Apply):				
Recharge Zone Contributing Zone Transition Zone				
Tune of Plan		Size		Fee Due
Type of Plan Water Pollution Abatement Plan, Contributing Zone		3126	,	ree bue
Plan: One Single Family Residential D			Acres	\$
Water Pollution Abatement Plan, Cor			7 101 00	<u> </u>
Plan: Multiple Single Family Resident	_		Acres	\$
Water Pollution Abatement Plan, Contributing Zone				
Plan: Non-residential		4.056	Acres	\$ 4,000.00
Sewage Collection System			L.F.	\$
Lift Stations without sewer lines			Acres	\$
Underground or Aboveground Storage Tank Facility			Tanks	\$
Piping System(s)(only)			Each	\$
Exception			Each	\$
Extension of Time		Each	\$	
Signature: Mha Leifia Date: 6/8/23				

Application Fee Schedule

Texas Commission on Environmental Quality

Edwards Aquifer Protection Program 30 TAC Chapter 213 (effective 05/01/2008)

Water Pollution Abatement Plans and Modifications

Contributing Zone Plans and Modifications

contributing zone rians and riodineations	Project Area in	
Project	Acres	Fee
One Single Family Residential Dwelling	< 5	\$650
Multiple Single Family Residential and Parks	< 5	\$1,500
	5 < 10	\$3,000
	10 < 40	\$4,000
	40 < 100	\$6,500
	100 < 500	\$8,000
	≥ 500	\$10,000
Non-residential (Commercial, industrial, institutional,	< 1	\$3,000
multi-family residential, schools, and other sites	1 < 5	\$4,000
where regulated activities will occur)	5 < 10	\$5,000
	10 < 40	\$6,500
	40 < 100	\$8,000
	≥ 100	\$10,000

Organized Sewage Collection Systems and Modifications

Project	Cost per Linear Foot	Minimum Fee- Maximum Fee	
Sewage Collection Systems	\$0.50	\$650 - \$6,500	

Underground and Aboveground Storage Tank System Facility Plans and Modifications

Project	Cost per Tank or Piping System	Minimum Fee- Maximum Fee
Underground and Aboveground Storage Tank Facility	\$650	\$650 - \$6,500

Exception Requests

Project	Fee		
Exception Request	\$500		

Extension of Time Requests

Extension of time Requests	
Project	Fee
Extension of Time Request	\$150



TCEQ Core Data Form

TCEQ Use Only

For detailed instructions regarding completion of this form, please read the Core Data Form Instructions or call 512-239-5175. SECTION I: General Information

0_011011		momado	•								
		•	hecked please		-						
									rogram application	on.)	
Renewal (Core Data Form should be submitted with the renewal form)							Other 3. Regulated Entity Reference Number (if issued)				
2. Customer Reference Number (if issued)			Follow this link to search		h 💳	Regulate	ea Enuly Referen	ice ivumber	(II ISSUEU)		
CN					for CN or RN numbers in Central Registry**			RN			
SECTION	II: Custom	er Informat	ion	- Ce	ntral Re	gistry^	-				
4. General C	Customer Info	ormation	5. Effective D	ate fo	r Custome	r Informa	ition U	pdates (ı	mm/dd/yyyy)		
New Cus		e (Verifiable wi		•	to Custom			troller of	Change in Public Accounts	_	Entity Ownership
The Custo	mer Name	e submitted		е ирс	dated au	tomatic	cally	based	on what is cu		d active with the
6. Customer	Legal Name	(If an individual,	print last name f	irst: e.g	g.: Doe, Joh	n)	<u>If</u>	new Cus	stomer, enter prev	vious Custon	ner below:
Hesters Cro	ssing Apts	Holdings LL	_C								
7. TX SOS/0	PA Filing Nu	ımber	8. TX State T	ax ID	(11 digits)		9	. Federa	I Tax ID (9 digits)	10. DUN	NS Number (if applicable)
013703098	30		320890267	62							
11. Type of 0	Customer:		on	×	Indiv	/idual		Par	tnership: 🔲 Gene	eral Limited	
Government	: City C	ounty 🔲 Federal [State Other		Sole	Proprie	torship		Other:		
12. Number × 0-20	of Employee:	s 101-250	251-500	5	501 and hig	jher		3. Indep ✓ Yes	endently Owned	and Operat	ed?
14. Custome	r Role (Propo	osed or Actual) -	as it relates to th	ne Regi	ulated Entity	listed on	this for	m. Please	e check one of the	following:	
Occupation	onal License	Opera	ator onsible Party			r & Oper ary Clea		oplicant	Other:		
	115 Schm					•					
15. Mailing Address:	15. Mailing Address:										
7.444.000.	City F	armingdale		St	tate N	Y	ZIP	1173	5	ZIP + 4	
16. Country	Mailing Inforr	nation (if outside	USA)		'	17. E	-Mail	Address	(if applicable)		
	, , , ,					cus@	ıs@marcusbuild.com				
18. Telephone Number			19. Extension or Code				20. Fax Number (if applicable)				
(512) 315 - 3515											
SECTION	III: Regula	nted Entity In	nformation								
21. General l	Regulated Er	ntity Information	ı (If `New Regu	lated E	Entity" is se	elected b	elow th	nis form s	should be accom	panied by a	permit application)
			to Regulated E						Entity Information		
_		•	bmitted mag h as Inc, LP,		•	in ord	er to i	meet T	CEQ Agency	Data Sta	ndards (removal
•			f the site where t			n is taking	place.)				
							Engippiakusi			ur estra Dipos Nosalista (Necisional)	
Hesters Cr	ossing Apa	artments Rou	ina Kock								

23. Street Address of the	2200 Rawhide Drive									
Regulated Entity:										
(No PO Boxes)	City Round Rock	State	TX	ZIP	78681	ZIP + 4				
24. County	Williamson									
	Enter Physical L	ocation Description	n if no street	address is	provided.					
25. Description to Physical Location:	The subject property is loc	ated at the North W	Vest quadran	t of the Ra		esters Crossing intersection.				
26. Nearest City Round Rock					State	Nearest ZIP Code 78681				
27. Latitude (N) In Decima	al:		28. Lor	ngitude (W)	Bisconseinol	Telefisefisefisecocon				
Degrees	Minutes	Seconds	Degrees		Minutes	Seconds				
30	29	16	97		40	54				
29. Primary SIC Code (4 digi	its) 30. Secondary SIC	Code (4 digits)	31. Primary (5 or 6 digits)	/ NAICS Co		econdary NAICS Code 6 digits)				
1522	6513		236116		5311					
33. What is the Primary Bus Land Development and	siness of this entity? (Do not Lessor of Commercial	t repeat the SIC or NAIC Real Estate	CS description.)							
0.4 8.4 95	155 Schmitt Blvd									
34. Mailing Address:										
Addicos.	City Farmingdale	State	NY	ZIP	11735	ZIP + 4				
35. E-Mail Address:	jmarcus@marcusbu	ild.com								
36. Telepho		37. Extensi	37. Extension or Code		38. Fax Number (if applicable)					
(512)3	315 - 3515		(
39. TCEQ Programs and ID Num Form instructions for additional guid		in the permits/registration	on numbers that	t will be affect	ed by the updates subm	nitted on this form. See the Core Data				
Dam Safety	Districts		quifer	Emiss	sions Inventory Air	Industrial Hazardous Waste				
Municipal Solid Waste	New Source Review A	ir OSSF		Petroleum Storage Tank		☐ PWS				
Sludge	Storm Water	☐ Title V Air	CONTRACTOR	☐ Tires		Used Oil				
☐ Voluntary Cleanup	☐ Waste Water	Wastewater	r Agriculture	☐ Water Rights		Other:				
OFOTION IV. Drop over			<u> </u>	_						
SECTION IV: Preparer			THE PARTY AND TH	T	SECURE OF THE PROPERTY OF T					
40. Name: Mark T. Burson,				1	Senior Engineer					
42. Telephone Number	43. Ext./Code	44. Fax Numbe	en seekkeneentriseery	45. E-Mail Address						
(512)469-0500				tburson@consortinc.com						
SECTION V: Authoriz 46. By my signature below, I ce to submit this form on behalf of t	ertify, to the best of my knowledg					nd that I have signature authority ed in field 39.				
Company: Consort, Inc.				Job Title:	Sr. Project Manag	er				
Name(In Print): Anna Hoge	7			Phone:	(512)469-500					
Signature:	1160			Date:	6/20/20	2				

TCEQ-10400 (04/15)

THE ENGINEER ASSUMES NO RESPONSIBILITY FOR THE EXISTENCE OR LOCATION OF ANY SURFACE OR SUBSURFACE STRUCTURES. THE CONTRACTOR IS RESPONSIBLE FOR CONTACTING ALL AGENCIES AND/OR OWNERS TO VERIFY THIS INFORMATION. CONTRACTOR SHALL CONTACT THE TEXAS EXCAVATION SAFETY SYSTEM (DIG TESS) AT (800/344-8377) AT LEAST TWO FULL WORKING DAYS BEFORE COMMENCING ANY SUBSURFACE WORK OR ANY OTHER WORK THAT WOULD AFFECT UTILITIES.

THIS PROJECT WILL PROVIDE ON SITE DETENTION TO MEET CITY CODE.

THIS SITE IS LOCATED IN THE EDWARDS AQUIFER RECHARGE ZONE AS WELL AS THE EDWARDS AQUIFER

ALL CONSTRUCTION SHALL BE IN FULL COMPLIANCE WITH ALL LOCAL, STATE AND FEDERAL RULES AND REGULATIONS AND STATUTES; INCLUDING BUT NOT LIMITED TO THE OCCUPATIONAL HEALTH AND SAFETY ADMINISTRATION (OSHA).

APPROVAL OF THESE PLANS BY THE CITY OF ROUND ROCK INDICATES COMPLIANCE WITH APPLICABLE CITY REGULATIONS ONLY. APPROVAL BY OTHER GOVERNMENTAL ENTITIES MAY BE REQUIRED PRIOR TO THE START OF CONSTRUCTION. THE APPLICANT IS RESPONSIBLE FOR DETERMINING WHAT ADDITIONAL APPROVALS MAY BE NECESSARY.

ALL RESPONSIBILITY FOR THE ADEQUACY OF THESE PLANS REMAINS WITH THE ENGINEER WHO PREPARED THEM. IN ACCEPTING THESE PLANS, THE CITY OF ROUND ROCK MUST RELY UPON THE ADEQUACY OF THE WORK OF THE DESIGN ENGINEER.

LEGAL DESCRIPTION: BLOCK A, LOT 1A AMENDING PLAT OF LOT 1, LOT 2, AND LOT 3, BLOCK "A" FOUR POINTS BY SHERATON SUBDIVISION

BENCHMARK:

BM 1: COTTON SPINDLE SET IN THE BACK OF CURB FOR CHAPARRAL CONTROL POINT CH100. SET NEAR THE NORTHEAST CORNER OF SUBJECT.

ELEV.=788.82'

BM 2: TRIANGLE CUT IN THE SIDEWALK ON THE NORTH SIDE OF HESTERS CROSSING +/- 257' SOUTHWEST OF THE INTERSECTION OF HESTERS CROSSING AND RAWHIDE DRIVE.

ELEV.=802.11'

BM 3: 2" CITY OF ROUND ROCK BRASS DISK FOUND IN THE WEST END OF CONCRETE HEADWAL ON THE NORTH SIDE OF HESTERS CROSSING.

ELEV.=795.95'

VERTICAL DATUM: NAVD 88 (GEOID 18)

SITE DEVELOPMENT IMPROVEMENTS FOR

HESTERS 4 APARTMENTS

DEVELOPER: HIGH RUSTLER VENTURES, LLC AUSTIN, TEXAS 78748


OWNER:

K HOTELS & RESORTS LLC 1802 PROSPECT ST HOUSTON, TEXAS 77004

2240 RAWHIDE DRIVE ROUND ROCK, TEXAS 78681

Site Planning, Engineering, & Landscape Architecture





ACCEPTED FOR CONSTRUCTION:

City of Round Rock, Texas, Engineering and Development Services Department Site Plan Development Permit Number Recorded Plat Document Number WPAP Document Number Approval Date

> STATE OF TEXAS COUNTY OF WILLIAMSON



I, Mark T. Burson, o hereby certify that the Public Works and Drainage Improvements described herein have been designed in compliance with the subdivision and building regulation ordinances and stormwater drainage policy adopted by the city of Round Rock, Texas.

Made T. Burson 6/8/2023 DATE

Sheet List Table

Sheet Number	Sheet Title
01	COVER PAGE
02	NOTE SHEET
03	PLAT
04	EXISTING CONDITION PLAN A
05	EXISTING CONDITION PLAN B
06	TREE, PROTECTION AND MITIGATION PLAN
07	EROSION SEDIMENTATION CONTROL A
08	EROSION SEDIMENTATION CONTROL B
09	EROSION SEDIMENTATION CONTROL DETAILS
10	OVERALL SITE PLAN
11	DETAILED SITE PLAN A
12	DETAILED SITE PLAN B
13	FIRE COVERAGE PLAN
14	SITE PLAN DETAILS
15	SITE PLAN DETAILS
16	UTILITY PLAN A
17	UTILITY PLAN B
18	PUBLIC WATER PLAN AND PROFILES
19	PUBLIC WASTEWATER PLAN AND PROFILES
20	UTILITY DETAILS 1
21	UTILITY DETAILS 2
22	STORM SEWER PLAN A
23	STORM SEWER PLAN B
24	RETAINING WALL DESIGN
25	DIMENSION CONTROL PLAN A
26	DIMENSION CONTROL PLAN B
27	GRADING PLAN A
28	GRADING PLAN B
29	EXISTING DRAINAGE PLAN
30	PROPOSED DRAINAGE PLAN
31	STORM WATER DETENTION & WATER QUALITY PLAN
32	GARAGE PLAN L1
33	GARAGE PLAN B1
34	GARAGE PLAN B2
35	ARCHITECTURAL ELEVATIONS N-E
36	ARCHITECTURAL ELEVATIONS S-W
37	LANDSCAPE PLAN A
38	LANDSCAPE PLAN B
39	LANDSCAPE DETAILS 1
40	LIGHTING PLAN

ENGINEER/LANDSCAPE ARCHITECT:

CÓNSORT, INC. 1609 SHOAL CREEK BLVD, SUITE 300 AUSTIN, TEXAS 78701 512-469-0500 Contact: ANNA HOGE

NILES BOLTON ASSOCIATES 3060 PEACHTREE RD NW, STE 600 ATLANTA, GA 30305 404.365.7600 CONTACT: CAREN HAMMETT

IMPERVIOUS COVER TABLE

	TOTAL
TOTAL EXISTING IMPERVIOUS COVER	0 S.F.
TOTAL PROPOSED IMPERVIOUS COVER	115,215 S.F.
% OF TOTAL SITE PROPOSED	65.23 %

SDP2212-0003

GENERAL NOTES:

- 1. ALL CONSTRUCTION SHALL BE IN ACCORDANCE WITH THE CITY OF ROUND ROCK STANDARD SPECIFICATIONS MANUAL.
- 2. ANY EXISTING UTILITIES, PAVEMENT, CURBS, SIDEWALKS, STRUCTURES, TREES, ETC., NOT PLANNED FOR DESTRUCTION OR REMOVAL THAT ARE DAMAGED OR REMOVED SHALL BE REPAIRED OR REPLACED AT HIS EXPENSE.
- THE CONTRACTOR SHALL VERIFY ALL DEPTHS AND LOCATIONS OF EXISTING UTILITIES PRIOR TO ANY CONSTRUCTION. ANY DISCREPANCIES WITH THE CONSTRUCTION PLANS FOUND IN THE FIELD SHALL BE BROUGHT IMMEDIATELY TO THE ATTENTION OF THE ENGINEER WHO SHALL BE RESPONSIBLE FOR REVISING THE PLANS AS APPROPRIATE.
- 4. MANHOLE FRAMES, COVERS, VALVES, CLEANOUTS, ETC. SHALL BE RAISED TO FINISHED GRADE PRIOR TO FINAL PAVING CONSTRUCTION.
- 5. THE CONTRACTOR SHALL GIVE THE CITY OF ROUND ROCK 48 HOURS NOTICE BEFORE BEGINNING EACH PHASE OF CONSTRUCTION. TELEPHONE (512) 801-4460 (INSPECTORS).
- 6. ALL AREAS DISTURBED OR EXPOSED DURING CONSTRUCTION SHALL BE REVEGETATED IN ACCORDANCE WITH THE PLANS AND SPECIFICATIONS. REVEGETATION OF ALL DISTURBED OR EXPOSED AREAS SHALL CONSIST OF SODDING OR SEEDING, AT THE CONTRACTOR'S DISCRETION HOWEVER, THE TYPE OF REVEGETATION MUST EQUAL OR EXCEED THE TYPE OF VEGETATION PRESENT BEFORE CONSTRUCTION.
- PRIOR TO ANY CONSTRUCTION, THE ENGINEER SHALL CONVENE A PRECONSTRUCTION CONFERENCE BETWEEN THE CITY OF ROUND ROCK, HIMSELF, THE CONTRACTOR, OTHER UTILITY COMPANIES, ANY AFFECTED PARTIES AND ANY OTHER ENTITY THE CITY OR ENGINEER MAY
- 8. THE CONTRACTOR AND THE ENGINEER SHALL KEEP ACCURATE RECORDS OF ALL CONSTRUCTION THAT DEVIATES FROM THE PLANS. THE ENGINEER SHALL FURNISH THE CITY OF ROUND ROCK ACCURATE "AS-BUILT" DRAWINGS FOLLOWING COMPLETION OF ALL CONSTRUCTION. THESE "AS-BUILT" DRAWINGS SHALL MEET WITH THE SATISFACTION OF THE ENGINEERING AN DEVELOPMENT SERVICES DEPARTMENT PRIOR TO
- 9. THE ROUND ROCK CITY COUNCIL SHALL NOT BE PETITIONED FOR ACCEPTANCE UNTIL ALL NECESSARY EASEMENT DOCUMENTS HAVE BEEN
- 10. WHEN CONSTRUCTION IS BEING CARRIED OUT WITHIN EASEMENTS, THE CONTRACTOR SHALL CONFINE HIS WORK TO WITHIN THE PERMANENT AND ANY TEMPORARY EASEMENTS. PRIOR TO FINAL ACCEPTANCE, THE CONTRACTOR SHALL BE RESPONSIBLE FOR REMOVING ALL TRASH AND DEBRIS WITHIN THE PERMANENT AND TEMPORARY EASEMENTS. CLEAN-UP SHALL BE TO THE SATISFACTION OF THE CITY ENGINEER.
- 11. PRIOR TO ANY CONSTRUCTION, THE CONTRACTOR SHALL APPLY FOR AND SECURE ALL PROPER PERMITS FROM THE APPROPRIATE
- 12. AVAILABLE BENCHMARKS (CITY OF ROUND ROCK DATUM) THAT MAY BE UTILIZED FOR THE CONSTRUCTION OF THIS PROJECT ARE DESCRIBED AS FOLLOWS: (SEE SHEET 01 - COVER PAGE)

TRENCH SAFETY NOTES:

- 1. IN ACCORDANCE WITH THE LAWS OF THE STATE OF TEXAS AND THE U. S. OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION REGULATIONS, ALL TRENCHES OVER 5 FEET IN DEPTH IN EITHER HARD AND COMPACT OR SOFT AND UNSTABLE SOIL SHALL BE SLOPED, SHORED, SHEETED, BRACED OR OTHERWISE SUPPORTED. FURTHERMORE, ALL TRENCHES LESS THAN 5 FEET IN DEPTH SHALL ALSO BE EFFECTIVELY PROTECTED WHEN HAZARDOUS GROUND MOVEMENT MAY BE EXPECTED. TRENCH SAFETY SYSTEMS TO BE UTILIZED FOR THIS PROJECT WILL BE PROVIDED BY THE CONTRACTOR.
- 2. IN ACCORDANCE WITH THE U. S. OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION REGULATIONS, WHEN PERSONS ARE IN TRENCHES 4-FEET DEEP OR MORE, ADEQUATE MEANS OF EXIT, SUCH AS A LADDER OR STEPS, MUST BE PROVIDED AND LOCATED SO AS TO REQUIRE
- 3. IF TRENCH SAFETY SYSTEM DETAILS WERE NOT PROVIDED IN THE PLANS BECAUSE TRENCHES WERE ANTICIPATED TO BE LESS THAN 5 FEET IN DEPTH AND DURING CONSTRUCTION IT IS FOUND THAT TRENCHES ARE IN FACT 5 FEET OR MORE IN DEPTH OR TRENCHES LESS THAN 5 FEET IN DEPTH ARE IN AN AREA WHERE HAZARDOUS GROUND MOVEMENT IS EXPECTED, ALL CONSTRUCTIONSHALL CEASE, THE TRENCHED AREA SHALL BE BARRICADED AND THE ENGINEER NOTIFIED IMMEDIATELY. CONSTRUCTION SHALL NOT RESUME UNTIL APPROPRIATE TRENCH SAFETY SYSTEM DETAILS, AS DESIGNED BY A PROFESSIONAL ENGINEER, ARE RETAINED AND COPIES SUBMITTED TO THE CITY OF ROUND

- 1. ALL TESTING SHALL BE DONE BY AN INDEPENDENT LABORATORY AT THE OWNER'S EXPENSE. ANY RETESTING SHALL BE PAID FOR BY THE CONTRACTOR. A CITY INSPECTOR SHALL BE PRESENT DURING ALL TESTS. TESTING SHALL BE COORDINATED WITH THE CITY
- BACKFILL BEHIND THE CURB SHALL BE COMPACTED TO OBTAIN A MINIMUM OF 95% MAXIMUM DENSITY TO WITHIN 3" OF TOP OF CURB. MATERIAL USED SHALL BE PRIMARILY GRANULAR WITH NO ROCKS LARGER THAN 6" IN THE GREATEST DIMENSION. THE REMAINING 3" SHALL BE CLEAN TOPSOIL FREE FROM ALL CLODS AND SUITABLE FOR SUSTAINING PLANT LIFE.
- 3. DEPTH OF COVER FOR ALL CROSSINGS UNDER PAVEMENT INCLUDING GAS, ELECTRIC, TELEPHONE, CABLE TV, WATER SERVICES, ETC., SHALL BE A MINIMUM OF 30" BELOW SUBGRADE.
- STREET RIGHTS-OF-WAY SHALL BE GRADED AT A SLOPE OF 1/4" PER FOOT TOWARD THE CURB UNLESS OTHERWISE INDICATED. HOWEVER. IN NO CASE SHALL THE WIDTH OF RIGHT-OF-WAY AT 1/4" PER FOOT SLOPE BE LESS THAN 10 FEET UNLESS A SPECIFIC REQUEST FOR AN ALTERNATE GRADING SCHEME IS MADE TO AND ACCEPTED BY THE CITY OF ROUND ROCK ENGINEERING AND DEVELOPMENT SERVICES DEPARTMENT.
- BARRICADES BUILT TO CITY OF ROUND ROCK STANDARDS SHALL BE CONSTRUCTED ON ALL DEAD-END STREETS AND AS NECESSARY DURING CONSTRUCTION TO MAINTAIN JOB AND PUBLIC SAFETY.
- 6. ALL R.C.P. SHALL BE MINIMUM CLASS III.
- THE SUBGRADE MATERIAL FOR THE STREETS SHOWN HEREIN WAS TESTED BY: N/A AND THE PAVING SECTIONS DESIGNED IN ACCORDANCE WITH THE CURRENT CITY OF ROUND ROCK DESIGN CRITERIA. THE PAVING SECTIONS ARE TO BE CONSTRUCTED AS FOLLOWS: N/A THE GEOTECHNICAL ENGINEER SHALL INSPECT THE SUBGRADE FOR COMPLIANCE WITH THE DESIGN ASSUMPTIONS MADE DURING PRÉPARATION OF THE SOILS REPORT. ANY ADJUSTMENTS THAT ARE REQUIRED SHALL BE MADE THROUGH REVISION OF THE CONSTRUCTION PLANS.
- WHERE PI'S ARE OVER 20, SUBGRADES MUST BE STABILIZED UTILIZING A METHOD ACCEPTABLE TO THE CITY ENGINEER. THE GEOTECHNICAL ENGINEER SHALL RECOMMEND AN APPROPRIATE SUBGRADE STABILIZATION IF SULFATES ARE DETERMINED TO BE

WATER AND WASTEWATER NOTES:

- 1. PIPE MATERIAL FOR WATER MAINS SHALL BE PVC (AWWA C-900, MIN. CLASS 200), OR DUCTILE IRON (AWWA C-100, MIN. CLASS 200). WATER SERVICES (2" OR LESS) SHALL BE POLYETHYLENE TUBING (BLACK, 200 PSI, DR
- 2. PIPE MATERIAL FOR PRESSURE WASTEWATER MAINS SHALL BE PVC (AWWA C-900, MIN. CLASS 150), OR DUCTILE IRON (AWWA C-100, MIN. CLASS 200). PIPE MATERIAL FOR GRAVITY WASTEWATER MAINS SHALL BE PVC (ASTM D2241 OR D3034, MAX. DR-26), DUCTILE IRON (AWWA C-100, MIN. CLASS 200).
- UNLESS OTHERWISE ACCEPTED BY THE CITY ENGINEER, DEPTH OF COVER FOR ALL LINES OUT OF THE PAVEMENT SHALL BE 42" MIN., AND DEPTH OF COVER FOR ALL LINES UNDER PAVEMENT SHALL BE A MIN. OF 30" BELOW
- 4. ALL FIRE HYDRANT LEADS SHALL BE DUCTILE IRON PIPE (AWWA C-100, MIN. CLASS 200).
- 5. ALL IRON PIPE AND FITTINGS SHALL BE WRAPPED WITH MINIMUM 8-MIL POLYETHYLENE AND SEALED WITH DUCT TAPE OR EQUAL ACCEPTED BY THE CITY ENGINEER.
- 6. THE CONTRACTOR SHALL CONTACT THE CITY INSPECTOR AT (512) 218-3241 TO COORDINATE UTILITY TIE-INS AND NOTIFY HIM AT LEAST 48 HOURS PRIOR TO CONNECTING TO EXISTING LINES.
- 7. ALL MANHOLES SHALL BE CONCRETE WITH CAST IRON RING AND COVER. ALL MANHOLES LOCATED OUTSIDE OF THE PAVEMENT SHALL HAVE BOLTED COVERS. TAPPING OF FIBERGLASS MANHOLES SHALL NOT BE ALLOWED.
- 8. THE CONTRACTOR MUST OBTAIN A BULK WATER PERMIT OR PURCHASE AND INSTALL A WATER METER FOR ALL WATER USED DURING CONSTRUCTION. A COPY OF THIS PERMIT MUST BE CARRIED AT ALL TIMES BY ALL WHO USE
- 9. LINE FLUSHING OR ANY ACTIVITY USING A LARGE QUANTITY OF WATER MUST BE SCHEDULED WITH THE CIVIL
- 10. THE CONTRACTOR, AT HIS EXPENSE, SHALL PERFORM STERILIZATION OF ALL POTABLE WATER LINES CONSTRUCTED AND SHALL PROVIDE ALL EQUIPMENT (INCLUDING TEST GAUGES), SUPPLIES (INCLUDING CONCENTRATED CHLORINE DISINFECTING MATERIAL), AND NECESSARY LABOR REQUIRED FOR THE STERILIZATION PROCEDURE. THE STERILIZATION PROCEDURE SHALL BE MONITORED BY CITY OF ROUND ROCK PERSONNEL. WATER SAMPLES WILL BE COLLECTED BY THE CITY OF ROUND ROCK TO VERIFY EACH TREATED LINE HAS ATTAINED AN INITIAL CHLORINE CONCENTRATION OF 50 WHERE MEANS OF FLUSHING IS NECESSARY, THE CONTRACTOR, AT HIS EXPENSE, SHALL PROVIDE FLUSHING DEVICES AND REMOVE SAID DEVICES PRIOR TO FINAL ACCEPTANCE BY THE CITY OF ROUND ROCK.
- 11. SAMPLING TAPS SHALL BE BROUGHT UP TO 3 FEET ABOVE GRADE AND SHALL BE EASILY ACCESSIBLE FOR CITY PERSONNEL, AT THE CONTRACTOR'S REQUEST, AND IN HIS PRESENCE, SAMPLES FOR BACTERIOLOGICAL TESTING WILL BE COLLECTED BY THE CITY OF ROUND ROCK NOT LESS THAN 24 HOURS AFTER THE TREATED LINE HAS BEEN FLUSHED OF THE CONCENTRATED CHLORINE SOLUTION AND CHARGED WITH WATER APPROVED BY THE CITY. THE CONTRACTOR SHALL SUPPLY A CHECK OR MONEY ORDER, PAYABLE TO THE CITY OF ROUND ROCK, TO COVER THE FEE CHARGED FOR TESTING EACH WATER SAMPLE. CITY OF ROUND ROCK FEE AMOUNTS MAY BE OBTAINED BY CALLING THE DEVELOPMENT SERVICES OFFICE AT (512) 218-7043.
- 12. THE CONTRACTOR, AT HIS EXPENSE, SHALL PERFORM QUALITY TESTING FOR ALL WASTEWATER PIPE INSTALLED AND Pressure Pipe Hydrostatic testing of all water lines constructed and shall provide all equipment (INCLUDING PUMPS AND GAUGES), SUPPLIES AND LABOR NECESSARY TO PERFORM THE QUALITY AND PRESSURE TESTING SHALL BE MONITORED BY CITY OF ROUND ROCK PERSONNEL.
- 13. THE CONTRACTOR SHALL COORDINATE TESTING WITH THE CITY OF ROUND ROCK INSPECTOR AND PROVIDE NO LESS THAN 24 HOURS NOTICE PRIOR TO PERFORMING STERILIZATION, QUALITY TESTING OR PRESSURE TESTING.
- 14. THE CONTRACTOR SHALL COORDINATE TESTING WITH THE CITY OF INSPECTOR AND PROVIDE NO LESS THAN 24 HOURS NOTICE PRIOR TO PERFORMING STERILIZATION, QUALITY TESTING OR PRESSURE TESTING.
- 15. THE CONTRACTOR SHALL NOT OPEN OR CLOSE ANY VALVES UNLESS AUTHORIZED BY THE CITY OF ROUND ROCK.
- 16. ALL VALVE BOXES AND COVERS SHALL BE CAST IRON.
- 17. ALL WATER SERVICE, WASTEWATER SERVICE AND VALVE LOCATIONS SHALL BE APPROPRIATELY MARKED AS

WATER SERVICE "W" ON TOP OF CURB

WASTEWATER SERVICE "S" ON TOP OF CURB

VALVE "V" ON FACE OF CURB

- TOOLS FOR MARKING THE CURB SHALL BE PROVIDED BY THE CONTRACTOR. OTHER APPROPRIATE MEANS OF MARKING SERVICE AND VALVE LOCATIONS SHALL BE PROVIDED IN AREAS WITHOUT CURBS. SUCH MEANS OF MARKING SHALL BE AS SPECIFIED BY THE ENGINEER AND ACCEPTED BY THE CITY OF ROUND ROCK.
- 18. CONTACT CITY OF ROUND ROCK DEVELOPMENT SERVICES OFFICE AT (512) 218-7043 FOR ASSISTANCE IN OBTAINING EXISTING WATER AND WASTEWATER LOCATIONS.
- 19. THE CITY OF ROUND ROCK FIRE DEPARTMENT SHALL BE NOTIFIED 48 HOURS PRIOR TO TESTING OF ANY BUILDING SPRINKLER PIPING IN ORDER THAT THE FIRE DEPARTMENT MAY MONITOR SUCH TESTING.
- 20. SAND, AS DESCRIBED IN SPECIFICATION ITEM 510 PIPE, SHALL NOT BE USED AS BEDDING FOR WATER AND WASTEWATER LINES. ACCEPTABLE BEDDING MATERIALS ARE PIPE BEDDING STONE, PEA GRAVEL AND IN LIEU OF SAND, A NATURALLY OCCURRING OR MANUFACTURED STONE MATERIAL CONFORMING TO ASTM C33 FOR STONE QUALITY AND MEETING THE FOLLOWING

GRADATION SPECIFICATION:

SIEVE SIZE PERCENT RETAINED BY WEIGHT

AND POSSIBLY BETWEEN 12 AND 6 A.M.

1/2" 0

3/8" 0-2

40-85

95-100

- 21. THE CONTRACTOR IS HEREBY NOTIFIED THAT CONNECTING TO, SHUTTING DOWN, OR TERMINATING EXISTING UTILITY LINES MAY HAVE TO OCCUR AT OFF-PEAK HOURS. SUCH HOURS ARE USUALLY OUTSIDE NORMAL WORKING HOURS
- 22. ALL WASTEWATER CONSTRUCTION SHALL BE IN ACCORDANCE WITH THE TEXAS COMMISSION ON ENVIRONMENTAL QUALITY (TCEQ) REGULATIONS, 30 TAC CHAPTER 213 AND 217, AS APPLICABLE. WHENEVER TCEQ AND CITY OF ROUND ROCK SPECIFICATIONS CONFLICT, THE MORE STRINGENT SHALL APPLY.

TCEQ WPAP GENERAL CONSTRUCTION NOTES

- A WRITTEN NOTICE OF CONSTRUCTION MUST BE SUBMITTED TO THE TCEQ REGIONAL OFFICE AT LEAST 48 HOURS PRIOR TO THE START OF ANY REGULATED ACTIVITIES. THIS NOTICE MUST INCLUDE:
- THE NAME OF THE APPROVED PROJECT;
- THE ACTIVITY START DATE; AND THE CONTACT INFORMATION OF THE PRIME CONTRACTOR.
- 2. ALL CONTRACTORS CONDUCTING REGULATED ACTIVITIES ASSOCIATED WITH THIS PROJECT MUST BE PROVIDED WITH COMPLETE COPIES OF THE APPROVED WATER POLLUTION ABATEMENT PLAN (WPAP) AND THE TCEQ LETTER INDICATING THE SPECIFIC CONDITIONS OF ITS APPROVAL. DURING THE COURSE OF THESE REGULATED ACTIVITIES, THE CONTRACTORS ARE REQUIRED TO KEEP ON-SITE COPIES OF THE APPROVED PLAN AND APPROVAL LETTER.
- 3. IF ANY SENSITIVE FEATURE(S) (CAVES, SOLUTION CAVITY, SINK HOLE, ETC.) IS DISCOVERED DURING CONSTRUCTION. ALL REGULATED ACTIVITIES NEAR THE SENSITIVE FEATURE MUST BE SUSPENDED IMMEDIATELY. THE APPROPRIATE TCEQ REGIONAL OFFICE MUST BE IMMEDIATELY NOTIFIED OF ANY SENSITIVE FEATURES ENCOUNTERED DURING CONSTRUCTION. CONSTRUCTION ACTIVITIES MAY NOT BE RESUMED UNTIL THE TCEQ HAS REVIEWED AND APPROVED THE APPROPRIATE PROTECTIVE MEASURES IN ORDER TO PROTECT ANY SENSITIVE FEATURE AND THE EDWARDS AQUIFER FROM POTENTIALLY ADVERSE IMPACTS TO
- NO TEMPORARY OR PERMANENT HAZARDOUS SUBSTANCE STORAGE TANK SHALL BE INSTALLED WITHIN 150 FEET OF A WATER SUPPLY SOURCE, DISTRIBUTION SYSTEM, WELL, OR SENSITIVE FEATURE.
- PRIOR TO BEGINNING ANY CONSTRUCTION ACTIVITY, ALL TEMPORARY EROSION AND SEDIMENTATION (E&S) CONTROL MEASURES MUST BE PROPERLY INSTALLED AND MAINTAINED IN ACCORDANCE WITH THE APPROVED PLANS AND MANUFACTURERS SPECIFICATIONS. IF INSPECTIONS INDICATE A CONTROL HAS BEEN USED INAPPROPRIATELY, OR INCORRECTLY, THE APPLICANT MUST REPLACE OR MODIFY THE CONTROL FOR SITE SITUATIONS. THESE CONTROLS MUST REMAIN IN PLACE UNTIL THE DISTURBED AREAS HAVE BEEN PERMANENTLY STABILIZED.
- ANY SEDIMENT THAT ESCAPES THE CONSTRUCTION SITE MUST BE COLLECTED AND PROPERLY DISPOSED OF BEFORE THE NEXT RAIN EVENT TO ENSURE IT IS NOT WASHED INTO SURFACE STREAMS, SENSITIVE FEATURES, ETC.
- 7. SEDIMENT MUST BE REMOVED FROM THE SEDIMENT TRAPS OR SEDIMENTATION BASINS NOT LATER THAN WHEN IT OCCUPIES
- 8. LITTER, CONSTRUCTION DEBRIS, AND CONSTRUCTION CHEMICALS EXPOSED TO STORMWATER SHALL BE PREVENTED FROM BEING DISCHARGED OFFSITE.
- 9. ALL SPOILS (EXCAVATED MATERIAL) GENERATED FROM THE PROJECT SITE MUST BE STORED ON-SITE WITH PROPER E&S CONTROLS. FOR STORAGE OR DISPOSAL OF SPOILS AT ANOTHER SITE ON THE EDWARDS AQUIFER RECHARGE ZONE, THE OWNER OF THE SITE MUST RECEIVE APPROVAL OF A WATER POLLUTION ABATEMENT PLAN FOR THE PLACEMENT OF FILL MATERIAL OR MASS GRADING PRIOR TO THE PLACEMENT OF SPOILS AT THE OTHER SITE.
- 10. IF PORTIONS OF THE SITE WILL HAVE A TEMPORARY OR PERMANENT CEASE IN CONSTRUCTION ACTIVITY LASTING LONGER THAN 14 DAYS, SOIL STABILIZATION IN THOSE AREAS SHALL BE INITIATED AS SOON AS POSSIBLE PRIOR TO THE 14TH DAY OF INACTIVITY. IF ACTIVITY WILL RESUME PRIOR TO THE 21ST DAY, STABILIZATION MEASURES ARE NOT REQUIRED. IF DROUGHT CONDITIONS OR INCLEMENT WEATHER PREVENT ACTION BY THE 14TH DAY, STABILIZATION MEASURES SHALL BE
- 11. THE FOLLOWING RECORDS SHALL BE MAINTAINED AND MADE AVAILABLE TO THE TCEQ UPON REQUEST:

FAX (210) 545-4329

- THE DATES WHEN MAJOR GRADING ACTIVITIES OCCUR; THE DATES WHEN CONSTRUCTION ACTIVITIES TEMPORARILY OR PERMANENTLY CEASE ON A PORTION OF THE SITE; AND
- THE DATES WHEN STABILIZATION MEASURES ARE INITIATED.
- THE HOLDER OF ANY APPROVED EDWARD AQUIFER PROTECTION PLAN MUST NOTIFY THE APPROPRIATE REGIONAL OFFICE IN WRITING AND OBTAIN APPROVAL FROM THE EXECUTIVE DIRECTOR PRIOR TO INITIATING ANY OF THE FOLLOWING:
- ANY PHYSICAL OR OPERATIONAL MODIFICATION OF ANY WATER POLLUTION ABATEMENT STRUCTURE(S), INCLUDING BUT NOT
- LIMITED TO PONDS, DAMS, BERMS, SEWAGE TREATMENT PLANTS, AND DIVERSIONARY STRUCTURES; B. ANY CHANGE IN THE NATURE OR CHARACTER OF THE REGULATED ACTIVITY FROM THAT WHICH WAS ORIGINALLY APPROVED OR
- A CHANGE WHICH WOULD SIGNIFICANTLY IMPACT THE ABILITY OF THE PLAN TO PREVENT POLLUTION OF THE EDWARDS ANY DEVELOPMENT OF LAND PREVIOUSLY IDENTIFIED AS UNDEVELOPED IN THE ORIGINAL WATER POLLUTION ABATEMENT PLAN.

AUSTIN REGIONAL OFFICE 12100 PARK 35 CIRCLE, BUILDING A AUSTIN, TEXAS 78753—1808	FAX (512) 339-3795 SAN ANTONIO REGIONAL OFFICE 14250 JUDSON ROAD SAN ANTONIO, TEXAS 78233-4480
PHONE (512) 339-2929	PHONE (210) 490-3096

TREE REMOVAL

ALLOWABLE REMOVAL— TREE REMOVAL IS APPROVED AS PART OF THE SUBDIVISION AND SITE PLAN PROCESS, OR IN THE CASE OF INDIVIDUAL TREES, THROUGH THE TREE REMOVAL PERMIT PROCESS. THESE THREE PROCESSES ARE DEFINED IN THE ORDINANCE, A TREE REMOVAL PERMIT MUST BE GRANTED, OR A SITE OR SUBDIVISION PLAN WITH A TREE SURVEY AND REPLACEMENT PLAN APPROVED, BEFORE REMOVING A PROTECTED TREE REGARDLESS OF THE CONDITION OF THE TREE.

PROTECTED TREE REMOVAL PERMIT APPLICATION— TREE REMOVAL APPLICATIONS ARE AVAILABLE AT THE CITY OF ROUND ROCK FORESTRY DIVISION. THE FORM IS REQUIRED ONLY WHEN A REQUEST FOR TREE REMOVAL ORIGINATES WITH AN OWNER OF FULLY DEVELOPED LAND, INCLUDING A SINGLE FAMILY HOUSE UNDER CONSTRUCTION. ALL OTHER REQUESTS FOR REMOVAL OF PROTECTED TREES TAKE PLACE DURING THE SUBDIVISION AND SITE DEVELOPMENT PROCESSES AS DEFINED IN THE ORDINANCE.

TREE REPLACEMENT PLAN

REPLACEMENT REQUIREMENTS ARE DEFINED IN THE ORDINANCE, AND ARE LIMITED TO PROTECTED TREES, EXCLUDING MONARCH TREES. IT IS IMPORTANT TO NOTE THAT TREE REPLACEMENTS DURING THE SITE PLAN PROCESS WILL BE ADDRESSED IN BOTH THE TREE PROTECTION AND PRESERVATION ORDINANCE AND THE LANDSCAPE ORDINANCE. WHICHEVER ORDINANCE REQUIRES THE GREATEST NUMBER OF TREE REPLACEMENT INCHES. THAT IS THE ORDINANCE WHICH WILL BE FOLLOWED IN TERMS OF THE NUMBER OF INCHES TO BE REPLACED. THE TREE REQUIREMENTS OF BOTH ORDINANCES WILL NOT BE ADDED UP. SEE SECTION 3.1108 OF THE ORDINANCE FOR THE TYPES OF REPLACEMENTS THAT ARE REQUIRED DEPENDENT ON LOT SIZE AND DEVELOPMENT STATUS.

CONSTRUCTION SUMMARY TABLE

		WATER		CONCRETE VALLEY	SIDEV	
Pipe Size	TYPE	LENGTH (LF)	VOL (GAL)	GUTTERS	Total	LF
4"	Ductile Iron	39.7	1303.3 gal	Total		
6"	Ductile Iron	143.8	210.8 gal	LF	4'	T
8"	Ductile Iron	498.9	23.8 gal		5'	
	<u> </u>		<u>l</u>	HMAC Total	VA	LV
				SY	Size	T
		WASTEWATE	₹		8"	Ι
Pipe Size	TYPE	LENGTH (LF)	VOL (GAL)		6"	
8"	PVC	24	65 gal	CURB & GUTTER	4"	I
				Total		
				LF		L
						_
				WASTEWATER MANHOLES	INI	<u>-E1</u>
				Size Qty	Size	╀
	T STOR	M CEWED	1	41		╀
D: 0:	TYPE	M SEWER LENGTH (LF)	4	4' ² 5'	5' 10'	+
Pipe Size	ITTE	LENGTH (LF)	4	6'	15'	╀
			4	6	15	\perp
	+		1			
			<u> </u>	STORM SEWER MANHOLES	FIRE H	/D
			<u> </u> 	STORM SEWER MANHOLES Size Qty	FIRE HY	γD
						YD
					Total	YD

AMERICANS WITH DISABILITIES ACT

UNDER TITLE II AND TITLE III OF THE AMERICANS WITH DISABILITIES ACT (42 USC 12131) AND THE ARCHITECTURAL BARRIERS ACT, ARE REQUIRED TO INCLUDE ALL SERVICES, OR ACTIVITIES ON THE BASIS OF DISABILITY. THE CITY OF THE ROUND ROCK HAS REVIEWED THIS PLAN FOR COMPLIANCE WITH CITY DEVELOPMENT REGULATIONS ONLY. THE APPLICANT, PROPERTY OWNER, AND OCCUPANT OF THE PREMISES ARE RESPONSIBLE FOR DETERMINING WHETHER THE PLAN COMPLIES WITH ALL OTHER LAWS, REGULATIONS, AND RESTRICTIONS WHICH MAY BE APPLICABLE TO THE PROPERTY AND


TRAFFIC MARKING NOTES:

- 1. ANY METHODS, STREET MARKINGS AND SIGNAGE NECESSARY FOR WARNING MOTORISTS, WARNING PEDESTRIANS OR DIVERTING TRAFFIC DURING CONSTRUCTION SHALL CONFORM TO THE TEXAS MANUAL OF UNIFORM TRAFFIC CONTROL DEVICES FOR STREETS AND HIGHWAYS, LATEST EDITION.
- 2. ALL PAVEMENT MARKINGS, MARKERS, PAINT, TRAFFIC BUTTONS, TRAFFIC CONTROLS AND SIGNS SHALL BE INSTALLED IN ACCORDANCE WITH THE TEXAS DEPARTMENT OF TRANSPORTATION STANDARD SPECIFICATIONS FOR CONSTRUCTION OF HIGHWAYS, STREETS AND BRIDGES AND, THE TEXAS MANUAL OF UNIFORM TRAFFIC CONTROL DEVICES FOR STREETS AND HIGHWAYS, LATEST EDITIONS.

EROSION AND SEDIMENTATION CONTROL NOTES:


- EROSION CONTROL MEASURES, SITE WORK AND RESTORATION WORK SHALL BE IN ACCORDANCE WITH THE CITY OF ROUND ROCK EROSION AND SEDIMENTATION CONTROL ORDINANCE.
- 2. ALL SLOPES SHALL BE SODDED OR SEEDED WITH APPROVED GRASS, GRASS MIXTURES OR GROUND COVER SUITABLE TO THE AREA AND SEASON IN WHICH THEY ARE APPLIED.
- 3. SILT FENCES, ROCK BERMS, SEDIMENTATION BASINS AND SIMILARLY RECOGNIZED TECHNIQUES AND MATERIALS SHALL BE EMPLOYED DURING CONSTRUCTION TO PREVENT POINT SOURCE SEDIMENTATION LOADING OF DOWNSTREAM FACILITIES. SUCH INSTALLATION SHALL BE REGULARLY INSPECTED BY THE CITY OF ROUND ROCK FOR EFFECTIVENESS. ADDITIONAL MEASURES MAY BE REQUIRED IF, IN THE OPINION OF THE CITY ENGINEER, THEY ARE
- 4. ALL TEMPORARY EROSION CONTROL MEASURES SHALL NOT BE REMOVED UNTIL FINAL INSPECTION AND APPROVAL OF THE PROJECT BY THE ENGINEER. IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO MAINTAIN ALL TEMPORARY EROSION CONTROL STRUCTURES AND TO REMOVE EACH STRUCTURE AS APPROVED BY THE ENGINEER.
- 5. ALL MUD, DIRT, ROCKS, DEBRIS, ETC., SPILLED, TRACKED OR OTHERWISE DEPOSITED ON EXISTING PAVED STREETS, DRIVES AND AREAS USED BY THE PUBLIC SHALL BE CLEANED UP IMMEDIATELY.

NO PART OF THIS SITE PLAN MAY BE REPRODUCED OR DISTRIBUTED IN ANY FORM OR BY ANY MEANS, OR STORED IN A DATA BASE OR RETRIEVAL SYSTEM, WITHOUT THE PRIOR



JOB NO.: DRAWN BY: SCALE: 06/08/23 DATE: FILE:

XREF: REV./CORR:



AMENDING PLAT OF LOT 1, LOT 2, AND LOT 3, BLOCK "A" FOUR POINTS BY SHERATON SUBDIVISION

THAT K HOTELS AND RESORTS, LLC, BEING OWNER OF LOTS 1, 2, AND 3, BLOCK "A", FOUR POINTS BY SHERATON SUBDIVISION A SUBDIVISION OF RECORD IN DOCUMENT NO. 2019039270 OF THE OFFICIAL PUBLIC RECORDS OF WILLIAMSON COUNTY, TEXAS, CONVEYED BY DEED OF RECORD DOCUMENT NUMBER 2008027850 OF THE OFFICIAL PUBLIC RECORDS OF WILLIAMSON COUNTY, TEXAS, AND SAID SUBDIVISION HAVING BEEN APPROVED FOR RESUBDIVISION PURSUANT TO THE PUBLIC PUBLIC RECORDS OF WILLIAMSON COUNTY, TEXAS, AND SAID SUBDIVISION HAVING BEEN APPROVED FOR RESUBDIVISION PURSUANT TO THE PUBLIC NOTIFICATION AND HEARING PROVISIONS OF CHAPTER 212.014 OF THE LOCAL GOVERNMENT CODE,

DO HEREBY AMEND 4.118 ACRES IN ACCORDANCE WITH THE MAP OR PLAT ATTACHED HERETO, TO BE KNOWN AS: AMENDING PLAT OF LOT 1, LOT 2, AND LOT 3, BLOCK "A" FOUR POINTS BY SHERATON SUBDIVISION AND DO HEREBY DEDICATE TO THE PUBLIC THE USE OF ALL STREETS AND EASEMENT SHOWN HEREON, SUBJECT TO ANY AND ALL EASEMENTS OR RESTRICTIONS HERETOFORE GRANTED AND NOT RELEASED.

JONATHAN MARCUS K HOTELS AND RESORTS, LLC.

THE STATE OF TEXAS § COUNTY OF WILLIAMSON §

THIS INSTRUMENT WAS ACKNOWLEDGED BEFORE ME ON THE ____DAY OF _____, 2021, BY JONATHAN MARCUS AS AUTHORIZED REPRESENTATIVE OF HESTERS CROSSINGS APTS HOLDINGS, LLC., A DELAWARE LIMITED LIABILITY COMPANY ON BEHALF OF SAID HESTERS CROSSINGS APTS HOLDINGS, LLC.

NOTARY PUBLIC, STATE OF TEXAS PRINTED NAME: MY COMMISSION EXPIRES:

THE STATE OF TEXAS § COUNTY OF WILLIAMSON §

THAT I, BRYAN D. NEWSOME, DO HEREBY CERTIFY THAT I PREPARED THIS PLAT FROM AN ACTUAL AND ACCURATE ON-THE-GROUND SURVEY OF THE LAND AND THAT THE CORNER MONUMENTS SHOWN THEREON WERE PROPERLY PLACED UNDER MY PERSONAL SUPERVISION, IN ACCORDANCE WITH CHAPTER 36, SUBDIVISIONS, CODE OF ORDINANCES, CITY OF

ROUND ROCK, 2010 EDITION AS AMENDED.

Preliminary, this document shall not be recorded for any purpose and shall not be used or viewed or relied upon as a final survey document. (Per "The Board of Professional Land Surveying" Texas Administrative Code, Title 22 - Part 6, Chapter 138, Subchapter B, Rule 138.33)

BRYAN D. NEWSOME. R.P.L.S. DAT'STATE OF TEXAS NO.: 5657
CHAPARRAL PROFESSIONAL LAND SURVEYING. INC.

OWNER'S RESPONSIBILITIES
IN APPROVING THIS PLAT BY THE COMMISSIONERS COURT OF WILLIAMSON COUNTY, TEXAS, IT IS UNDERSTOOD THAT THE BUILDING OF ALL STREETS, ROADS, AND OTHER PUBLIC THOROUGHFARES AND ANY BRIDGES OR CULVERTS NECESSARY TO BE CONSTRUCTED OR PLACED IS THE RESPONSIBILITY OF THE OWNERS OF THE TRACT OF LAND COVERED BY THIS PLAT IN ACCORDANCE WITH THE PLANS AND SPECIFICATIONS PRESCRIBED BY THE COMMISSIONERS COURT OF WILLIAMSON COUNTY, TEXAS. SAID COMMISSIONERS COURT ASSUMES NO OBLIGATION TO BUILD ANY OF THE STREETS, ROADS OR OTHER PUBLIC THOROUGHFARES SHOWN ON THIS PLAT OR OF CONSTRUCTING ANY OF THE BRIDGES OR DRAINAGE IMPROVEMENTS IN CONNECTION THEREWITH. THE COUNTY WILL ASSUME NO RESPONSIBILITY FOR DRAINAGE WAYS OR EASEMENTS IN THE

THE COUNTY ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OF REPRESENTATIONS BY OTHER PARTIES IN THIS PLAT. FLOOD PLAIN DATA, IN PARTICULAR, MAY CHANGE DEPENDING ON SUBSEQUENT DEVELOPMENT. IT IS FURTHER UNDERSTOOD THAT THE OWNERS OF THE TRACT OF LAND COVERED BY THIS PLAT MUST INSTALL AT THEIR OWN EXPENSE ALL TRAFFIC CONTROL DEVICES AND SIGNAGE THAT MAY BE REQUIRED BEFORE THE STREETS IN THE SUBDIVISION HAVE FINALLY BEEN ACCEPTED FOR MAINTENANCE BY THE COUNTY.

THE STATE OF TEXAS § KNOW ALL MEN BY THESE PRESENTS:

COUNTY OF WILLIAMSON §

I, BILL GRAVELL, Jr., COUNTY JUDGE OF WILLIAMSON COUNTY, TEXAS DO HEREBY CERTIFY THAT THIS MAP OR PLAT, A SUBDIVISION, REPLAT OF LOT 9, BLOCK, TERAVISTA COM 24, HAVING BEEN FULLY PRESENTED TO THE COMMISSIONER'S COURT OF WILLIAMSON COUNTY, TEXAS AND BY THE SAID COURT DULY CONSIDERED, WAS ON THIS DAY APPROVED AND SAID PLAT IS AUTHORIZED TO BE REGISTERED AND RECORDED IN THE OFFICIAL PUBLIC RECORDS OF THE COUNTY CLERK OF WILLIAMSON

BILL GAVELL, Jr., COUNTY JUDGE WILLIAMSON COUNTY, TEXAS

THE STATE OF TEXAS §

COUNTY OF WILLIAMSON §

THAT I, NANCY RISTER, CLERK OF THE COUNTY COURT OF SAID COUNTY, DO HEREBY CERTIFY THAT THE FOREGOING INSTRUMENT IN WRITING, WITH ITS CERTIFICATION OF AUTHENTICATION, WAS FILED FOR RECORD IN MY OFFICE ON THE ____DAY OF _______ A.D. 2022 , AT _____O'CLOCK ___M. AND DULY RECORDED ON THE ___ DAY OF ______, A.D. 2022 AT ____O'CLOCK ___M. IN THE PLAT RECORDS OF SAID COUNTY, IN DOCUMENT

WITNESS MY HAND AND SEAL OF THE COUNTY COURT OF SAID COUNTY, AT OFFICE IN GEORGETOWN, TEXAS, THE DATE LAST ABOVE WRITTEN.
NANCY RISTER, CLERK, COUNTY COURT
WILLIAMSON COUNTY, TEXAS

Professional Land Surveying,

C8-XX-XXXXXX

3500 McCall Lane Austin, Texas 78744 512-443-1724 T.B.P.E.L.S. Firm No. 10124500

DRAWN BY: RGH SHEET 02 OF 02

DRAWING NO.: 1900-001-PL

PLOT DATE: 09/23/2022

PLOT SCALE: 1"=100'

NO PART OF THIS SITE PLAN MAY BE REPRODUCED OR DISTRIBUTED IN ANY FORM OR BY ANY MEANS, OR STORED IN A DATA BASE OR RETRIEVAL SYSTEM, WITHOUT THE PRIOR WRITTEN PERMISSION OF CONSORT, INC. 2240

DRAWN BY:


REV./CORR:


06/08/23

SCALE:

DATE:

FILE: XREF:






HIGH RUSTLER VENTURES, LLC 155 SCHMITT BLVD FARMINGDALE, NY, 11735

DRIVE, ROUND ROCK, IX /8(


EXISTING

3600 Bee Cove Road Suite 100 / Austin, IX 78746 / (512) 469-0500 T.B.P.E. Firm Registration No. F-859



JOB NO.: 1587-003 DRAWN BY: SCALE: 1"=20' DATE: 06/08/23 FILE: XREF: REV./CORR:

> 04 of 40



3000 Bee Cove Road Suite 100 / Austin, IX 78746 T.B.P.E. Firm Redistration



JOB NO.: 1587-003 DRAWN BY: 1"=20" SCALE: 06/08/23 DATE: XREF: REV./CORR:

SHEET

• • • • ACCESSIBLE ROUTE

FIRE LANE DESIGNATION

— ∪E — UNDERGROUND ELECTRIC

100.00 EXISTING SPOT ELEVATION

100.00 PROPOSED SPOT ELEVATION


BOP EXISTING CONTOUR BOTTOM OF POND


EXISTING CONTOUR


ALL RESPONSIBILITY FOR THE ADEQUACY OF THESE PLANS REMAINS WITH THE ENGINEER WHO PREPARED


THEM. IN REVIEWING THESE PLANS, THE CITY OF ROUND ROCK MUST RELY UPON THE ADEQUACY OF


THE WORK OF THE DESIGN ENGINEER.

































NO PART OF THIS SITE PLAN MAY BE REPRODUCED OR DISTRIBUTED IN ANY FORM OR BY ANY MEANS, OR STORED IN A DATA BASE OR RETRIEVAL SYSTEM, WITHOUT THE PRIOR WRITTEN PERMISSION OF CONSORT, INC.

1"=30' 06/08/23 SCALE: DATE: FILE: XREF: REV./CORR: SHEET

1587-003

JOB NO.:

DRAWN BY:

66334

78681

SDP2212-0003

4. SOCK MATERIAL WILL BE 100% BIODEGRADABLE, PHOTODEGRADABLE, OR RECYCLABLE SUCH AS BURLAP, TWINE, UV PHOTOBIODEGRADABLE PLASTIC, POLYESTER, OR ANY OTHER ACCEPTABLE RECORD COPY SIGNED BY 08/24/2010 THE ARCHITECT/ENGINEER ASSUMES STANDARD NO.

ADDRESS OF THIS STANDARD. N.T.S. ADOPTED TRIANGULAR SEDIMENT FITER DIKE MULCH SOCK DETAIL Lath and flagging on 3 sides 10 mil plastic lining Section A-A ─ 10 mil plastic lining Actual layout determined in the field. 2. A concrete washout sign shall be installed within 10 m of the Type "Below Grade' temporary concrete washout facility. CONCRETE WASHOUT DETAIL

ANY POWER OPERATED GATES ACROSS FIRE ACCESS ROADS MUST BE PROVIDED WITH A KNOX KEY SWITCH. ALSO, GATES INSTALLED ACROSS FIRE ACCESS ROADS SHALL BE EQUIPPED WITH GATE OPERATORS COMPLYING WITH UL 325 AND ASTM F2200. A MANUAL MEANS OF OPENING THE GATE IN THE EVENT OF POWER LOSS IS REQUIRED.

PAVEMENT PAINT SPECIFICATION:

FIRE LANE PAVEMENT PAINT SHALL BE GLIDDEN #4520 OIL ENAMEL "SAFETY RED" OR EQUAL. TRAFFIC ARROW PAVEMENT PAINT SHALL BE GLIDDEN #22693 OIL ENAMEL "TRAFFIC WHITE" OR EQUAL. TRAFFIC STRIPE PAVEMENT PAINT SHALL
BE GLIDDEN #22693 OIL ENAMEL"TRAFFIC WHITE" OR EQUAL. CROSSWALK PAVEMENT PAINT SHALL BE GLIDDEN #22693 OIL ENAMEL"TRAFFIC WHITE" OR EQUAL.

SCHEMATIC CROSSWALK LAYOUT

NOTE

LIGHTING.

A. SITE LIGHTING DESIGN REQUIREMENTS:

1.FIXTURE (LUMINAIRE). THE LIGHT SOURCE SHALL BE COMPLETELY CONCEALED (RECESSED) WITHIN AN OPAQUE HOUSING AND SHALL NOT BE VISIBLE FROM ANY STREET RIGHT-OF-WAY OR RESIDENTIAL PROPERTY LINE. LIGHT FIXTURES WITHIN GAS STATION CANOPIES SHALL BE FLUSH WITH THE UNDERSIDE OF THE CANOPY.

2.LIGHT SOURCE (LAMP). ONLY INCANDESCENT, FLUORESCENT, COMPACT FLUORESCENT (CFL), LIGHT-EMITTING DIODES (LED), METAL HALIDE, OR COLOR CORRECTED HIGH-PRESSURE SODIUM MAY BE USED. THE SAME TYPE SHALL BE USED FOR THE SAME OR SIMILAR TYPES OF LIGHTING ON ANY ONE SITE THROUGHOUT ANY MASTER PLANNED DEVELOPMENT.

3.MOUNTING. EXCEPT AS REQUIRED BY SUBSECTION (B)(4)C. BELOW, FIXTURES SHALL BE MOUNTED IN SUCH A MANNER THAT THE CONE OF LIGHT DOES NOT EXCEED ONE (1) FOOT CANDLE AT ANY PROPERTY LINE SHARED WITH A NONRESIDENTIAL USE AND TWO (2) FOOT CANDLES AT

ANY PROPERTY LINE ABUTTING A PUBLIC STREET (RIGHT-OF-WAY). 4.ALL SITE AND BUILDING LIGHTING SHALL BE ACCOMPLISHED WITH LIGHT THAT DOES NOT FLASH, BLINK OR PULSE.


5.ATHLETIC FACILITIES ASSOCIATED WITH SCHOOLS, PLACES OF WORSHIP, AND CHARITABLE NONPROFIT ORGANIZATIONS MAY EXCEED THE FIXTURE HEIGHT REQUIREMENT IF THEY IMPLEMENT REASONABLE MEASURES TO LIMIT ADVERSE IMPACTS ON NEIGHBORING PROPERTIES THAT MAY RESULT FROM THE INCREASED FIXTURE HEIGHT.

B. EXCESSIVE ILLUMINATION:

1.INTERFERES WITH USE OR ENJOYMENT. LIGHTING WITHIN ANY LOT THAT UNNECESSARILY ILLUMINATES AND SUBSTANTIALLY INTERFERES WITH THE USE OR ENJOYMENT OF ANY OTHER LOT IS PROHIBITED. LIGHTING UNNECESSARILY ILLUMINATES ANOTHER LOT IF IT CLEARLY EXCEEDS THE REQUIREMENTS OF THIS SECTION, OR IF THE STANDARD COULD REASONABLY BE ACHIEVED IN A MANNER THAT WOULD NOT SUBSTANTIALLY INTERFERE WITH THE USE OR ENJOYMENT OF NEIGHBORING PROPERTIES.

2.GLARES OR IS EXCESSIVE. LIGHTING SHALL NOT BE ORIENTED SO AS TO DIRECT GLARE OR EXCESSIVE ILLUMINATION ONTO STREETS IN A MANNER THAT MAY DISTRICT OR INTERFERE WITH THE VISION OF DRIVERS ON SUCH STREETS.C.COMPATIBILITY WITH RESIDENTIAL PROPERTIES.1.LIGHTING SHALL BE DIRECTED AWAY FROM ANY RESIDENTIAL PROPERTIES.2.THE CONE OF LIGHT SHALL NOT EXCEED 0.5 FOOT CANDLES AT ANY RESIDENTIAL PROPERTY LINE.

3.EXTERIOR SHIELDING OF LIGHT FIXTURES OR OTHER LIGHT MITIGATION MEASURES SHALL BE REQUIRED IF DEEMED NECESSARY BY CITY STAFF DURING THE SITE PLAN REVIEW PROCESS.



NO PART OF THIS SITE PLAN MAY BE REPRODUCED OR DISTRIBUTED IN ANY FORM OR BY ANY MEANS, OR STORED IN A DATA BASE OR RETRIEVAL SYSTEM, WITHOUT THE PRIOR WRITTEN PERMISSION OF CONSORT, INC.



		PROVIDED STRUCTURE			PROVIDED SURFACE				
USE	REQUIRED	STANDARD	TANDEM	HANDICAP	CHARGE	STANDARD	HANDICAP	ON-STREET	TOTAL
1-BEDROOM 239 UNITS @ 1 SP./UNIT	239								
2-BEDROOM 32 UNITS © 2 SP./UNIT	64								
COMMERCIAL RETAIL 5,932 S.F.@ 1 SP./250 S.F.	24								
		292	14*	8	30	19	04	06	
TOTAL	327	344			29			373	

*TANDEM PARKING FOR 2-BEDROOM USE ONLY PER P.U.D.

SITE DATA

	TOTAL
TOTAL CITE ADEA	176,628 S.F.
TOTAL SITE AREA	4.05 A.C.
TOTAL BUILDING COVERAGE	74,451 S.F. 1.71 A.C. 42.2%
PROPOSED USE: MULTIFAMILY RETAIL	276 UNITS 6,061 S.F.
ZONING	PUD
OTAL EXISTING MPERVIOUS COVER	0 S.F. 0%
OTAL PROPOSED	115,215 S.F.
MPERVIOUS COVER	65.23%

		CUR	VE TABLE			
CURVE	RADIUS	DELTA	ARC	BEARING	CHORD	(RECORD CHORD)
C1	440.60'	12*24'38"	95.44	S22°59'58"E	95.25'	(S22°06'41"E 95.25'
C2	15.00'	90°33'07"	23.71'	S15°07'32"W	21.32'	(S15*54'26"E 21.26'
C3	522.22'	21°45'03"	198.25'	S74°20'05"W	197.06	

5' PUBLIC EASEMENT POINT OF ENDING (P.O.E) 15' DRAINAGE & PUBLIC UTILITY EASEMENT

EXCLUSIVE WATER LINES EASEMENT REF. DOC. NO. ______ O.P.R.W.C.T.

- 100-YR FLOOD PLAIN

WATER QUALITY AND DETENTION POND

DRAINAGE EASEMENT (2004058296) AND STORM SEWER EASEMENT

100-YR FLOOD PLAIN

._____

-STORY MIXED USE BUILDING 5- STORIES ABOVE 2-STORIES PARKING BELOW 276 MULTIFAMILY UNITS 6,061 S.F. RETAIL 55'-2" HT.

77309'37'E 293,374'
(N7357'00' 293,93)

EXCLUSIVE WITH REF. 1.50'E WITH RE

<u>ATTENTION</u>

PUBLIC UTILITY EASEMENT PER PLAT

STONE PAVERS REF. DET. 5&6 37

PUBLIC UTILITY EASEMENT PER PLAT

THE ENGINEER ASSUMES NO RESPONSIBILITY FOR THE EXISTENCE OR LOCATION OF ANY SURFACE OR SUBSURFACE STRUCTURES. THE CONTRACTOR IS RESPONSIBLE FOR CONTACTING ALL AGENCIES AND/OR OWNERS TO VERIFY THIS INFORMATION. CONTRACTOR SHALL CONTACT THE TEXAS EXCAVATION SAFETY SYSTEM (DIG TESS) AT (800/344-8377) AT LEAST TWO FULL WORKING DAYS BEFORE COMMENCING ANY SUBSURFÀCE WORK OR ANY OTHER WORK THAT WOULD AFFECT UTILITIES.

ALL CONSTRUCTION MATERIALS AND TECHNIQUES SHALL CONFORM TO CURRENT CITY OF ROUND ROCK STANDARD SPECIFICATIONS.

ALL RESPONSIBILITY FOR THE ADEQUACY OF THESE PLANS REMAINS WITH THE ENGINEER WHO PREPARED THEM. IN REVIEWING THESE PLANS, THE CITY OF ROUND ROCK MUST RELY UPON THE ADEQUACY OF THE WORK OF THE DESIGN ENGINEER.

EXISTING

△ TBM TEMPORARY BENCHMARK

SURVEY MONUMENT

IRON ROD FOUND

COTTON GIN BOLT

EXISTING CONTOUR BOTTOM OF POND

IRON ROD SET

■ ■ ■ LIMITS OF CONSTRUCTION

100.00 Existing spot elevation

100.00 PROPOSED SPOT ELEVATION

N90°00'00"E SURVEY DATA

(N90°00'00"E) RECORD DATA

▲ BM BENCHMARK

PROPERTY LINE

BOP


SCALE IN FEET LEGEND PLAT RECORDS WILLIAMSON O.P.R.W.C.T. OFFICIAL PUBLIC RECORDS WILLIAMSON COUNTY, TEXAS COUNTY, TEXAS PROPOSED CONCRETE WALK SPACE NUMBER 4 1/2 PROPOSED CONCRETE PAVING COMPACT PARKING SPACE PROPOSED ASPHALT PAVING ACCESSIBLE PARKING SPACE TOP OF CURB PROPOSED CONTOUR MORTAR STACK ROCK WALL TOP OF CURB RETAINING WALL BOTTOM OF CURB "X" HT. WOOD FENCE HIGH POINT — w — water line ---- WW ---- WASTE WATER LINE FLOW LINE ----- SD ----- STORM DRAIN LINE TOP OF GRATE DOWN GUY TOP OF WALL PAVEMENT — — — UNDERGROUND UTILITIES CI FANOUT EXISTING TREE REF. DET. REFER DETAIL TO REMAIN REF. ARCH. REFER ARCHITECTURAL PLANS TYP. TYPICAL EXISTING TREE CONC. CONCRETE EXIST.

TO BE REMOVED SILT FENCE -+++++++ Filter Dike TREE PROTECTION FENCE EXIST. SIGN EXIST. LIGHT POLE DOWNSPOUTS → → → HAND RAILS

SHEET TRAFFIC GUARD RAIL FIRE LANE DESIGNATION • • • • ACCESSIBLE ROUTE --- UE --- UNDERGROUND ELECTRIC

SDP2212-0003





1587-003

06/08/23

JOB NO.:

SCALE:


DATE:

FILE:

XREF:

DRAWN BY:

REV./CORR:



66334

DETAILED



JOB NO.: DRAWN BY: 1"=20' 06/08/23 SCALE: DATE: FILE: XREF: REV./CORR:


— ∪E — UNDERGROUND ELECTRIC


EXISTING CONTOUR BOTTOM OF POND


BOP

THEM. IN REVIEWING THESE PLANS, THE CITY OF ROUND ROCK MUST RELY UPON THE ADEQUACY OF

THE WORK OF THE DESIGN ENGINEER.








66334

TAIL

4

JOB NO.: DRAWN BY: N.T.S. 06/08/23 SCALE: DATE: FILE: XREF: REV./CORR:

SHEET




THE WORK OF THE DESIGN ENGINEER.

66334



JOB NO.: DRAWN BY: 1"=20' 06/08/23 SCALE: DATE: FILE: XREF: REV./CORR:





JOB NO.: 1587-003 DRAWN BY: SCALE: 1"=20' DATE: 06/08/23 FILE: XREF: REV./CORR:

MARK T. BURSON 66334



1587-003 JOB NO.: DRAWN BY: 1"=20' 06/08/23 SCALE: DATE: FILE: XREF: REV./CORR:

> Of 40

<u>ATTENTION</u>

ALL CONSTRUCTION MATERIALS AND TECHNIQUES SHALL CONFORM TO CURRENT CITY OF ROUND ROCK STANDARD SPECIFICATIONS.

ALL RESPONSIBILITY FOR THE ADEQUACY OF THESE PLANS REMAINS WITH THE ENGINEER WHO PREPARED THEM. IN REVIEWING THESE PLANS, THE CITY OF ROUND ROCK MUST RELY UPON THE ADEQUACY OF THE WORK OF THE DESIGN ENGINEER.

TRAFFIC GUARD RAIL

• • • • ACCESSIBLE ROUTE

FIRE LANE DESIGNATION

── UE ── UNDERGROUND ELECTRIC

PLAT RECORDS WILLIAMSON O.P.R.W.C.T. OFFICIAL PUBLIC RECORDS

4 17 %

ACCESSIBLE PARKING SPACE 100 PROPOSED CONTOUR
TOP OF CURB MORTAR STACK ROCK WALL

RETAINING WALL

—— WATER LINE

DOWN GUY

SILT FENCE

-+++++++ FILTER DIKE

→ → → HAND RAILS

"X" HT. WOOD FENCE

---- WW ---- WASTE WATER LINE

— SD — STORM DRAIN LINE
— OU — OVERHEAD UTILITIES

— — — UNDERGROUND UTILITIES

EXISTING TREE

EXISTING TREE

TREE PROTECTION FENCE

EXIST. SIGN

DOWNSPOUTS

EXIST. LIGHT POLE

TO BE REMOVED

TO REMAIN

COUNTY, TEXAS

SPACE NUMBER

BOTTOM OF CURB

HIGH POINT

GROUND

FLOW LINE

TOP OF GRATE

TOP OF WALL PAVEMENT

MANHOLE

CI FANOUT

TYPICAL

CONCRETE

EXISTING

△ TBM TEMPORARY BENCHMARK

SURVEY MONUMENT

IRON ROD FOUND

COTTON GIN BOLT

EXISTING CONTOUR BOTTOM OF POND

iron rod set

LIMITS OF CONSTRUCTION

100.00 EXISTING SPOT ELEVATION

100.00 PROPOSED SPOT ELEVATION

N90°00'00"E SURVEY DATA

(N90°00'00"E) RECORD DATA

▲ BM BENCHMARK

PROPERTY LINE

BOP

REFER DETAIL

COMPACT PARKING SPACE


WILLIAMSON COUNTY, TEXAS


PROPOSED CONCRETE WALK

PROPOSED CONCRETE PAVING

PROPOSED ASPHALT PAVING

NOTES: 1. THE CONTRACTOR IS TO LOCATE THE EXISTING UTILITIES AND NOTIFY THE ENGINEER IF THEY ARE NOT LOCATED AS INDICATED ON THIS PLAN.





<u>ATTENTION</u>

THE ENGINEER ASSUMES NO RESPONSIBILITY FOR THE EXISTENCE OR LOCATION OF ANY SURFACE OR SUBSURFACE STRUCTURES. THE CONTRACTOR IS RESPONSIBLE FOR CONTACTING ALL AGENCIES AND/OR OWNERS TO VERIFY THIS INFORMATION. CONTRACTOR SHALL CONTACT THE TEXAS EXCAVATION SAFETY SYSTEM (DIG TESS) AT (800/344-8377) AT LEAST TWO FULL WORKING DAYS BEFORE COMMENCING ANY

ALL RESPONSIBILITY FOR THE ADEQUACY OF THESE PLANS REMAINS WITH THE ENGINEER WHO PREPARED THEM. IN REVIEWING THESE PLANS, THE CITY OF ROUND ROCK MUST RELY UPON THE ADEQUACY OF THE WORK OF THE DESIGN ENGINEER.

P.R.W.C.T.	PLAT RECORDS WILLIAMSON COUNTY, TEXAS	O.P.R.W.C.T.	OFFICIAL PUBLIC RECORDS WILLIAMSON COUNTY, TEXAS
\bigcirc	COUNTY, TEXAS	F	PROPOSED CONCRETE WALK
1	SPACE NUMBER	4 1/4	PROPOSED CONCRETE PAVING
(1) (1)	COMPACT PARKING SPACE		PROPOSED ASPHALT PAVING
(1+)	ACCESSIBLE PARKING SPACE	100	PROPOSED CONTOUR
TC	TOP OF CURB		MORTAR STACK ROCK WALL
BC	BOTTOM OF CURB		RETAINING WALL
HP	HIGH POINT		"X" HT. WOOD FENCE
GRD	GROUND	w	WATER LINE WASTE WATER LINE
FL	FLOW LINE	****	STORM DRAIN LINE
TG	TOP OF GRATE	— SD —	OVERHEAD UTILITIES
TW	TOP OF WALL		DOWN GUY
PVMT	PAVEMENT	<u> </u>	UNDERGROUND UTILITIES
MH	MANHOLE	—	GAS LINE
CO	CLEANOUT	Ŏ	OAS LINE
REF. DET.	REFER DETAIL	#100)	EXISTING TREE
REF. ARCH.			TO REMAIN
TYP.	TYPICAL	<u> </u>	
CONC.	CONCRETE	#100 \	EXISTING TREE
EXIST.	EXISTING	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	TO BE REMOVED
N90'00'00"			SILT FENCE
(N90°00'00")			
♣ BM			FILTER DIKE
△ TBI		-X -X	TREE PROTECTION FENCE
	SURVEY MONUMENT	<u>,</u> ¶	EXIST. SIGN
Ŏ	IRON ROD FOUND IRON ROD SET	→	EXIST. LIGHT POLE
0	COTTON GIN BOLT	O DS	DOWNSPOUTS
	PROPERTY LINE		HAND RAILS
		$\Delta \Delta \Delta$	TRAFFIC GUARD RAIL
<u>100.00</u>			FIRE LANE DESIGNATION
100.00	_		ACCESSIBLE ROUTE
— 100.00	EXISTING CONTOUR	— UE —	UNDERGROUND ELECTRIC
BOP	BOTTOM OF POND	<u> </u>	C. DENOTION DELOTING
БОІ	DOTTOM OF TOTAL		

LEGEND


SUBSURFACE WORK OR ANY OTHER WORK THAT WOULD AFFECT UTILITIES.


ALL CONSTRUCTION MATERIALS AND TECHNIQUES SHALL CONFORM TO CURRENT CITY OF ROUND ROCK STANDARD SPECIFICATIONS.

66334


78681


2240







FIRE HYDRANT ASSEMBLY DETAIL












(10" METER)






EXISTING PAVED SURFACE




WATER METER VAULT SCHEDULE

TAG NO.

DESCRIPTION



GATE VALVE DETAIL





66334


TURES, I BLVD NY, 117

WATER METER ASSEMBLY DETAIL NO PART OF THIS SITE PLAN MAY BE REPRODUCED OR DISTRIBUTED IN ANY FORM OR BY ANY MEANS, OR STORED IN A DATA BASE OR RETRIEVAL SYSTEM, WITHOUT THE PRIOR WRITTEN PERMISSION OF CONSORT, INC.


SDP2212-0003









1/2" LETTERS








FLEXIBLE "SEAL BOOT" RESILIENT CONNECTOR

Copyright (C) 2022,


Consort, Inc.


NO PART OF THIS SITE PLAN MAY BE REPRODUCED OR


DISTRIBUTED IN ANY FORM OR BY ANY MEANS, OR STORED IN A DATA BASE OR RETRIEVAL SYSTEM, WITHOUT THE PRIOR WRITTEN PERMISSION OF CONSORT, INC.




WASTEWATER FLOW PATTERNS FOR INVERT CHANNELS








WASTEWATER LINE BEDDING AND SURFACE REPAIR






66334

N

TAIL

HESTERS IIDE DRIVE





JOB NO.: 1587-003 DRAWN BY: 1"=30' 06/08/23 SCALE: DATE: FILE: XREF: REV./CORR:

SHEET

• • • • ACCESSIBLE ROUTE

— UE — UNDERGROUND ELECTRIC


100.00 EXISTING SPOT ELEVATION

100.00 PROPOSED SPOT ELEVATION


BOP

EXISTING CONTOUR BOTTOM OF POND

ALL RESPONSIBILITY FOR THE ADEQUACY OF THESE PLANS REMAINS WITH THE ENGINEER WHO PREPARED THEM. IN REVIEWING THESE PLANS, THE CITY OF ROUND ROCK MUST RELY UPON THE ADEQUACY OF THE WORK OF THE DESIGN ENGINEER.



SHEET



<u>ATTENTION</u>

THE ENGINEER ASSUMES NO RESPONSIBILITY FOR THE EXISTENCE OR LOCATION OF ANY SURFACE OR SUBSURFACE STRUCTURES. THE CONTRACTOR IS RESPONSIBLE FOR CONTACTING ALL AGENCIES AND/OR OWNERS TO VERIFY THIS INFORMATION. CONTRACTOR SHALL CONTACT THE TEXAS EXCAVATION SAFETY SYSTEM (DIG TESS) AT (800/344-8377) AT LEAST TWO FULL WORKING DAYS BEFORE COMMENCING ANY SUBSURFACE WORK OR ANY OTHER WORK THAT WOULD AFFECT UTILITIES.

ALL CONSTRUCTION MATERIALS AND TECHNIQUES SHALL CONFORM TO CURRENT CITY OF ROUND ROCK STANDARD SPECIFICATIONS.

ALL RESPONSIBILITY FOR THE ADEQUACY OF THESE PLANS REMAINS WITH THE ENGINEER WHO PREPARED THEM. IN REVIEWING THESE PLANS, THE CITY OF ROUND ROCK MUST RELY UPON THE ADEQUACY OF THE WORK OF THE DESIGN ENGINEER.

TRAFFIC GUARD RAIL

• • • • ACCESSIBLE ROUTE

FIRE LANE DESIGNATION

— ∪E — UNDERGROUND ELECTRIC

PLAT RECORDS WILLIAMSON O.P.R.W.C.T. OFFICIAL PUBLIC RECORDS COUNTY, TEXAS WILLIAMSON COUNTY, TEXAS

4 17 %

ACCESSIBLE PARKING SPACE
TOP OF CURB
BOTTOM OF CURB

WORTAR STACK ROCK WALL
RETAINING WALL
RETAINING WALL
RETAINING WALL

PROPOSED CONCRETE WALK

PROPOSED CONCRETE PAVING

PROPOSED ASPHALT PAVING

"X" HT. WOOD FENCE

---- WW ---- WASTE WATER LINE

— SD — STORM DRAIN LINE
— OU — OVERHEAD UTILITIES

— — — UNDERGROUND UTILITIES

EXISTING TREE

EXISTING TREE

TO BE REMOVED

TO REMAIN

TREE PROTECTION FENCE

EXIST. SIGN

DOWNSPOUTS

EXIST. LIGHT POLE

—— WATER LINE

DOWN GUY

----- GAS LINE

SILT FENCE

+ HAND RAILS

COUNTY, TEXAS

SPACE NUMBER

BOTTOM OF CURB

HIGH POINT

GROUND

FLOW LINE

PAVEMENT

MANHOLE

CI FANOUT

TYPICAL

CONCRETE

EXISTING

△ TBM TEMPORARY BENCHMARK

SURVEY MONUMENT

IRON ROD FOUND

COTTON GIN BOLT

EXISTING CONTOUR BOTTOM OF POND

IRON ROD SET

LIMITS OF CONSTRUCTION

100.00 EXISTING SPOT ELEVATION

100.00 PROPOSED SPOT ELEVATION

N90°00'00"E SURVEY DATA

(N90°00'00"E) RECORD DATA

▲ BM BENCHMARK

PROPERTY LINE

BOP

REFER DETAIL

TOP OF GRATE

TOP OF WALL

COMPACT PARKING SPACE

MATCHLINE THIS SHEET 26

NO PART OF THIS SITE PLAN MAY BE REPRODUCED OR DISTRIBUTED IN ANY FORM OR BY ANY MEANS, OR STORED IN A DATA BASE OR RETRIEVAL SYSTEM, WITHOUT THE PRIOR WRITTEN PERMISSION OF CONSORT, INC.

SUBSURFACE STRUCTURES. THE CONTRACTOR IS RESPONSIBLE FOR CONTACTING ALL AGENCIES AND/OR OWNERS TO VERIFY THIS INFORMATION. CONTRACTOR SHALL CONTACT THE TEXAS EXCAVATION SAFETY SYSTEM (DIG TESS) AT (800/344-8377) AT LEAST TWO FULL WORKING DAYS BEFORE COMMENCING ANY SUBSURFACE WORK OR ANY OTHER WORK THAT WOULD AFFECT UTILITIES.

STANDARD SPECIFICATIONS.

ALL RESPONSIBILITY FOR THE ADEQUACY OF THESE PLANS REMAINS WITH THE ENGINEER WHO PREPARED THEM. IN REVIEWING THESE PLANS, THE CITY OF ROUND ROCK MUST RELY UPON THE ADEQUACY OF THE WORK OF THE DESIGN ENGINEER.

DIMENSION CONTROL NOTES

LEGEND

REF. DET.

BOP

SPACE NUMBER

GROUND FLOW LINE TOP OF GRATE TOP OF WALL PAVEMENT

CLEANOUT

N90°00'00"E SURVEY DATA

(N90°00'00"E) RECORD DATA

▲ BM BENCHMARK

PROPERTY LINE

REFER DETAIL

REF. ARCH. REFER ARCHITECTURAL PLANS
TYP. TYPICAL
CONC. CONCRETE
EXIST. EXISTING

△ TBM TEMPORARY BENCHMARK

SURVEY MONUMENT

IRON ROD FOUND

COTTON GIN BOLT

iron rod set


LIMITS OF CONSTRUCTION

100.00 EXISTING SPOT ELEVATION

PROPOSED SPOT ELEVATION
PROPOSED SPOT ELEVATION
EXISTING CONTOUR
BOP
BOTTOM OF POND

COMPACT PARKING SPACE

- 1. ALL DIMENSIONS ARE TAKEN TO FACE OF CURB OR BUILDING UNLESS OTHERWISE
- 2. CONTRACTOR SHALL VERIFY DIMENSIONS AND NOTIFY ENGINEER OF ANY DISCREPANCIES.
- 3. USE DIMENSIONAL INFORMATION GIVEN. DO NOT SCALE DRAWINGS.
- 4. CONTRACTOR SHALL VERIFY EXACT LOCATIONS AND PROTECT ALL EXISTING SITE IMPROVEMENTS AND UTILITIES DURING CONSTRUCTION OPERATIONS.
- 5. ALL WALKWAYS LEADING TO ENTRANCES ARE TO BE CENTERED ON DOORWAYS UNLESS OTHERWISE NOTED.
- 6. CURB RADII ARE 3' UNLESS OTHERWISE NOTED.



SHEET						
JOB NO.: DRAWN BY: SCALE: DATE: FILE: XREF: REV./CORR:	1587-003 1"=20' 06/08/23					

<u>ATTENTION</u>

THE ENGINEER ASSUMES NO RESPONSIBILITY FOR THE EXISTENCE OR LOCATION OF ANY SURFACE OR

ALL CONSTRUCTION MATERIALS AND TECHNIQUES SHALL CONFORM TO CURRENT CITY OF ROUND ROCK

TRAFFIC GUARD RAIL

 • • • • ACCESSIBLE ROUTE --- UE --- UNDERGROUND ELECTRIC

FIRE LANE DESIGNATION

PLAT RECORDS WILLIAMSON
COUNTY, TEXAS

SPACE NUMBER

O.P.R.W.C.T.
OFFICIAL PUBLIC RECORDS
WILLIAMSON COUNTY, TEXAS
PROPOSED CONCRETE WALK

ACCESSIBLE PARKING SPACE
TOP OF CURB
BOTTOM OF CURB
HIGH POINT
GROUND

TOP OF CURB
WATER STACK ROCK WALL
RETAINING WALL
"X" HT. WOOD FENCE
WATER LINE
WATER WATER LINE

PROPOSED CONCRETE PAVING

WW WATER LINE
WASTE WATER LINE
SD STORM DRAIN LINE
OU OVERHEAD UTILITIES
DOWN GUY

----- GAS LINE

SILT FENCE

-+++++++ FILTER DIKE

+ HAND RAILS

— — — UNDERGROUND UTILITIES

EXISTING TREE

TO REMAIN EXISTING TREE TO BE REMOVED


TREE PROTECTION FENCE

EXIST. SIGN


DOWNSPOUTS

EXIST. LIGHT POLE

PROPOSED ASPHALT PAVING



NO PART OF THIS SITE PLAN MAY BE REPRODUCED OR DISTRIBUTED IN ANY FORM OR BY ANY MEANS, OR STORED IN A DATA BASE OR RETRIEVAL SYSTEM, WITHOUT THE PRIOR WRITTEN PERMISSION OF CONSORT, INC.



HIGH RUSTLER VENTURES, LL. 155 SCHMITT BLVD FARMINGDALE, NY, 11735

HIGH RUSTLER W 155 SCHMI FARMINGDAL

AIVE, ROUND ROCK, IX /

3600 Bee Cove Road Suite 100 / Austin, TX 78746 / (512) 469-0500
T.B.P.E. Firm Registration No. F-859

/ NI

NORTH

JOB NO.: 1587-003
DRAWN BY:
SCALE: 1"=20'
DATE: 06/08/23
FILE:
XREF:
REV./CORR:

SHEET
26
of
40

TRAFFIC GUARD RAIL

• • • • ACCESSIBLE ROUTE

FIRE LANE DESIGNATION

--- UE --- UNDERGROUND ELECTRIC

+ HAND RAILS

COTTON GIN BOLT

■ ■ ■ LIMITS OF CONSTRUCTION

100.00 EXISTING SPOT ELEVATION


100.00 PROPOSED SPOT ELEVATION EXISTING CONTOUR BOTTOM OF POND

PROPERTY LINE

ALL CONSTRUCTION MATERIALS AND TECHNIQUES SHALL CONFORM TO CURRENT CITY OF ROUND ROCK

ALL RESPONSIBILITY FOR THE ADEQUACY OF THESE PLANS REMAINS WITH THE ENGINEER WHO PREPARED THEM. IN REVIEWING THESE PLANS, THE CITY OF ROUND ROCK MUST RELY UPON THE ADEQUACY OF THE WORK OF THE DESIGN ENGINEER.


STANDARD SPECIFICATIONS.






JOB NO.: 1587-003 DRAWN BY: 1"=20' 06/08/23 SCALE: DATE: FILE: XREF: REV./CORR:

SHEET



GRADING



JOB NO.: 1587-003 06/08/23






DRAINAGE LEGEND

DIRECTION OF FLOW



SUB AREA



JOB NO.: 1587-003 DRAWN BY: SCALE: 06/08/23 DATE: FILE: XREF: REV./CORR: SHEET

— ∪E — UNDERGROUND ELECTRIC

PROPOSED CONCRETE WALK

PROPOSED CONCRETE PAVING

PROPOSED ASPHALT PAVING

RETAINING WALL

—— WATER LINE

DOWN GUY

----- GAS LINE

SILT FENCE

-+++++++ FILTER DIKE

→ → → HAND RAILS

"X" HT. WOOD FENCE

---- WW ---- WASTE WATER LINE

— SD — STORM DRAIN LINE
— OU — OVERHEAD UTILITIES

— — — UNDERGROUND UTILITIES

EXISTING TREE

EXISTING TREE

TO BE REMOVED

TO REMAIN

TREE PROTECTION FENCE

TRAFFIC GUARD RAIL

• • • • ACCESSIBLE ROUTE

FIRE LANE DESIGNATION

EXIST. SIGN


DOWNSPOUTS

EXIST. LIGHT POLE

(IN FEET) 1 inch = 30 ft.

BOP

THE WORK OF THE DESIGN ENGINEER.



GEOTEXTILE FABRIC

UNDERDRAIN PERFORATED 4"

FILTRATION BASIN AND UNDERDRAIN

ROCK USED TO FILL THE GABION

5"-8" DIAMETER STONE.

MATTRESS AND GABION BASKET SHALL BE

GABION WALL TYPICAL SECTION

PVC PIPE SET PERFORATIONS DOWN

IMPERMEABLE

LAYER

2.05

<u>ATTENTION</u>

STANDARD SPECIFICATIONS.

THE WORK OF THE DESIGN ENGINEER.

GRAVEL LAYER

SCALE = 1":5"

GABION MATTRESS

6'X9'X3' TYPICAL

GABION STACK

3'X3'X3' TYPICAL

| L_{FL= 7/0...} |-FL= 778.57 | W E

4" SCHEDULE 40

PERFORATED PVC @ 1.00%

UNDER SAND BED (TYP.)

└FL= 778.64 ¡′

ı̈́ FL= 778.75 √

FILTRATION BASIN

′ FL= 778.79 → /

ı̃ FL= 778.86 ¬ /

NO PART OF THIS SITE PLAN MAY BE REPRODUCED OR DISTRIBUTED IN ANY FORM OR BY ANY MEANS, OR STORED IN A DATA BASE OR RETRIEVAL SYSTEM, WITHOUT THE PRIOR WRITTEN PERMISSION OF CONSORT, INC.

► FL= 778.92 -√

FL= 778.99 H

└ FL= 778.70 ;

SEDIMENTATION

REF. DET. 7 HEREON

BEGIN 4" SCHEDULE 40

4" DIA. PVC CLEANOUT OUTSIDE

1.0' THICKNESS

PERFORATED PVC

FL= 778.79

OF PONDING AREA

TOP ELEVATION 790

FL= 778.81

6'X33.02' GABION MATTRESS

SPLITTER

∦6'X33.02' GABION MATTRESS∤

1.0' THICKNESS

GABION BASKET

REF. DET. 7 HEREON

<_BASIN___

33.02'

JOB NO.: DRAWN BY: 1"=30' 06/08/23 SCALE: DATE: FILE: XREF: REV./CORR:

TRAFFIC GUARD RAIL

• • • • ACCESSIBLE ROUTE

FIRE LANE DESIGNATION

— ∪E — UNDERGROUND ELECTRIC

PLAT RECORDS WILLIAMSON O.P.R.W.C.T. OFFICIAL PUBLIC RECORDS

4 1/2

ACCESSIBLE PARKING SPACE TOP OF CURB PROPOSED CONTOUR MORTAN STACK ROCK WALL

RETAINING WALL

---- WW ---- WASTE WATER LINE

— SD — STORM DRAIN LINE
— OU — OVERHEAD UTILITIES

— -- UNDERGROUND UTILITIES

EXISTING TREE

EXISTING TREE

TREE PROTECTION FENCE

EXIST. SIGN

DOWNSPOUTS

EXIST. LIGHT POLE

TO BE REMOVED

TO REMAIN

—— WATER LINE

DOWN GUY

——— G—— GAS LINE

SILT FENCE

-+++++++ FILTER DIKE

→ → HAND RAILS

"X" HT. WOOD FENCE

WILLIAMSON COUNTY, TEXAS

PROPOSED CONCRETE WALK

PROPOSED CONCRETE PAVING

PROPOSED ASPHALT PAVING

2.83'

DETENTION POND OUTLET STRUCTURE

LEGEND

REF. DET.

TYP.

CONC. EXIST.

RETAINING WALL

REF. SHT. 24

COUNTY, TEXAS

SPACE NUMBER

TOP OF CURB

HIGH POINT

GROUND

FLOW LINE

TOP OF GRATE

TOP OF WALL

PAVEMENT

CI FANOUT

TYPICAL

CONCRETE

EXISTING

△ TBM TEMPORARY BENCHMARK

SURVEY MONUMENT

IRON ROD FOUND

IRON ROD SET

LIMITS OF CONSTRUCTION

100.00 EXISTING SPOT ELEVATION

100.00 PROPOSED SPOT ELEVATION

COTTON GIN BOLT

EXISTING CONTOUR BOTTOM OF POND

N90°00'00"E SURVEY DATA

(N90°00'00"E) RECORD DATA

▲ BM BENCHMARK

PROPERTY LINE

REFER DETAIL

REF. ARCH. REFER ARCHITECTURAL PLANS

BOTTOM OF CURB

COMPACT PARKING SPACE

781.00

THE ENGINEER ASSUMES NO RESPONSIBILITY FOR THE EXISTENCE OR LOCATION OF ANY SURFACE OR

OWNERS TO VERIFY THIS INFORMATION. CONTRACTOR SHALL CONTACT THE TEXAS EXCAVATION SAFETY

ALL CONSTRUCTION MATERIALS AND TECHNIQUES SHALL CONFORM TO CURRENT CITY OF ROUND ROCK

ALL RESPONSIBILITY FOR THE ADEQUACY OF THESE PLANS REMAINS WITH THE ENGINEER WHO PREPARED

THEM. IN REVIEWING THESE PLANS, THE CITY OF ROUND ROCK MUST RELY UPON THE ADEQUACY OF

SUBSURFACE WORK OR ANY OTHER WORK THAT WOULD AFFECT UTILITIES.

SUBSURFACE STRUCTURES. THE CONTRACTOR IS RESPONSIBLE FOR CONTACTING ALL AGENCIES AND/OR

SYSTEM (DIG TESS) AT (800/344-8377) AT LEAST TWO FULL WORKING DAYS BEFORE COMMENCING ANY