

RECHARGE AND TRANSITION ZONE EXCEPTION REQUEST

FOR

ROUND ROCK CHRISTIAN ACADEMY

800 WESTWOOD DRIVE ROUND ROCK, TEXAS 78681

APPLICANT: ROUND ROCK CHRISTIAN ACADEMY 301-A N. LAKE CREEK ROUND ROCK, TX 78681

SUBMITTED TO: TEXAS COMMISSION ON ENVIRONMENTAL QUALITY REGION 11 OFFICE 12100 PARK 35 CIRCLE, BLDG A. AUSTIN, TEXAS 78753

MAY 2023

HEA#22-025

Our Review of Your Application

The Edwards Aquifer Program staff conducts an administrative and technical review of all applications. The turnaround time for administrative review can be up to 30 days as outlined in 30 TAC 213.4(e). Generally administrative completeness is determined during the intake meeting or within a few days of receipt. The turnaround time for technical review of an administratively complete Edwards Aquifer application is 90 days as outlined in 30 TAC 213.4(e). Please know that the review and approval time is directly impacted by the quality and completeness of the initial application that is received. In order to conduct a timely review, it is imperative that the information provided in an Edwards Aquifer application include final plans, be accurate, complete, and in compliance with <u>30 TAC 213</u>.

Administrative Review

1. <u>Edwards Aquifer applications</u> must be deemed administratively complete before a technical review can begin. To be considered administratively complete, the application must contain completed forms and attachments, provide the requested information, and meet all the site plan requirements. The submitted application and plan sheets should be final plans. Please submit one full-size set of plan sheets with the original application, and half-size sets with the additional copies.

To ensure that all applicable documents are included in the application, the program has developed tools to guide you and web pages to provide all forms, checklists, and guidance. Please visit the below website for assistance: <u>http://www.tceq.texas.gov/field/eapp</u>.

- 2. This Edwards Aquifer Application Cover Page form (certified by the applicant or agent) must be included in the application and brought to the administrative review meeting.
- 3. Administrative reviews are scheduled with program staff who will conduct the review. Applicants or their authorized agent should call the appropriate regional office, according to the county in which the project is located, to schedule a review. The average meeting time is one hour.
- 4. In the meeting, the application is examined for administrative completeness. Deficiencies will be noted by staff and emailed or faxed to the applicant and authorized agent at the end of the meeting, or shortly after. Administrative deficiencies will cause the application to be deemed incomplete and returned.

An appointment should be made to resubmit the application. The application is re-examined to ensure all deficiencies are resolved. The application will only be deemed administratively complete when all administrative deficiencies are addressed.

- 5. If an application is received by mail, courier service, or otherwise submitted without a review meeting, the administrative review will be conducted within 30 days. The applicant and agent will be contacted with the results of the administrative review. If the application is found to be administratively incomplete, it can be retrieved from the regional office or returned by regular mail. If returned by mail, the regional office may require arrangements for return shipping.
- 6. If the geologic assessment was completed before October 1, 2004 and the site contains "possibly sensitive" features, the assessment must be updated in accordance with the *Instructions to Geologists* (TCEQ-0585 Instructions).

Technical Review

1. When an application is deemed administratively complete, the technical review period begins. The regional office will distribute copies of the application to the identified affected city, county, and groundwater conservation district whose jurisdiction includes the subject site. These entities and the public have 30 days to provide comments on the application to the regional office. All comments received are reviewed by TCEQ.

2. A site assessment is usually conducted as part of the technical review, to evaluate the geologic assessment and observe existing site conditions. The site must be accessible to our staff. The site boundaries should be clearly marked, features identified in the geologic assessment should be flagged, roadways marked and the alignment of the Sewage Collection System and manholes should be staked at the time the application is submitted. If the site is not marked the application may be returned.

١

- 3. We evaluate the application for technical completeness and contact the applicant and agent via Notice of Deficiency (NOD) to request additional information and identify technical deficiencies. There are two deficiency response periods available to the applicant. There are 14 days to resolve deficiencies noted in the first NOD. If a second NOD is issued, there is an additional 14 days to resolve deficiencies. If the response to the second notice is not received, is incomplete or inadequate, or provides new information that is incomplete or inadequate, the application must be withdrawn or if not withdrawn the application will be denied and the application fee will be forfeited.
- 4. The program has 90 calendar days to complete the technical review of the application. If the application is technically adequate, such that it complies with the Edwards Aquifer rules, and is protective of the Edwards Aquifer during and after construction, an approval letter will be issued. Construction or other regulated activity may not begin until an approval is issued.

Mid-Review Modifications

It is important to have final site plans prior to beginning the permitting process with TCEQ to avoid delays.

Occasionally, circumstances arise where you may have significant design and/or site plan changes after your Edwards Aquifer application has been deemed administratively complete by TCEQ. This is considered a "Mid-Review Modification". Mid-Review Modifications may require redistribution of an application that includes the proposed modifications for public comment.

If you are proposing a Mid-Review Modification, two options are available to you:

- You can withdraw your application, and your fees will be refunded or credited for a resubmittal.
- TCEQ can continue the technical review of the application as it was submitted, and a modification application can be submitted at a later time.

If the application is withdrawn, the resubmitted application will be subject to the administrative and technical review processes and will be treated as a new application. The application will be redistributed to the effected jurisdictions.

Please contact the regional office if you have questions. If your project is located in Williamson, Travis, or Hays County, contact TCEQ's Austin Regional Office at 512-339-2929. If your project is in Comal, Bexar, Medina, Uvalde, or Kinney County, contact TCEQ's San Antonio Regional Office at 210-490-3096

Please fill out all required fields below and submit with your application.

1. Regulated Entity Name: ROUND ROCK CHRISTIAN ACADEMY					2. Regulated Entity No.: 110717196				
3. Customer Name: ROUND ROCK CHRISTIAN ACADEMY				AN	4. Customer No.: 605631290				
5. Project Type: (Please circle/check onc)	New		Modif	icatior	1	Exter	nsion	Exception XX	
6. Plan Type: (Please circle/check one)	WPAP	CZP	SCS	UST	AST	EXP	EXT	Technical Clarification	Optional Enhanced Measures
7. Land Use: (Please circle/check one)	Reside	ntial	Non-residential X		x	8. Sit	e (acres):	8.733	
9. Application Fee:	\$500.0	0	10. Permanent F			BMP(s):	SED/FIL PONI)
11. SCS (Linear Ft.):			12. A	ST/US	ST (N	o. Tar	ıks):		

13. County:	Williamson	14. Watershed:	LAKE CREEK

Application Distribution

Instructions: Use the table below to determine the number of applications required. One original and one copy of the application, plus additional copies (as needed) for each affected incorporated city, county, and groundwater conservation district are required. Linear projects or large projects, which cross into multiple jurisdictions, can require additional copies. Refer to the "Texas Groundwater Conservation Districts within the EAPP Boundaries" map found at:

http://www.tceq.texas.gov/assets/public/compliance/field_ops/eapp/EAPP%20GWCD%20map.pdf

For more detailed boundaries, please contact the conservation district directly.

Austin Region					
County:	Hays	Travis	Williamson		
Original (1 req.)		_	_X_		
Region (1 req.)	Annual La		_x_		
County(ies)			X		
Groundwater Conservation District(s)	Edwards Aquifer Authority Barton Springs/ Edwards Aquifer Hays Trinity Plum Creek	Barton Springs/ Edwards Aquifer	NA		
City(ies) Jurisdiction	Austin Buda Dripping Springs Kyle Mountain City San Marcos Wimberley Woodcreek	Austin Bee Cave Pflugerville Rollingwood Round Rock Sunset Valley West Lake Hills	Austin Cedar Park Florence Georgetown Jerrell Leander Liberty Hill Pflugerville		

	San Antonio Region						
County:	Bexar	Comal	Kinney	Medina	Uvalde		
Original (1 req.)							
Region (1 req.)							
County(ies)			<u> </u>				
Groundwater Conservation District(s)	Edwards Aquifer Authority Trinity-Glen Rose	Edwards Aquifer Authority	Kinney	EAA Medina	EAA Uvalde		
City(ies) Jurisdiction	Castle Hills Fair Oaks Ranch Helotes Hill Country Village Hollywood Park	Bulverde Fair Oaks Ranch Garden Ridge New Braunfels Schertz	NA	San Antonio ETJ (SAWS)	NA		

San Antonio (SAWS)		
Shavano Park		

I certify that to the best of my knowledge, that the application is complete and accurate. This application is hereby submitted to TCEQ for administrative review and technical review.

TOM ASUQUO

Runt Name of Customer/Authorized Agent

05 15 2023 Date

FOR TCEQ INTERNAL USE ONLY				
Date(s)Reviewed:	Da	ate Adn	ninistratively Complet	e:
Received From:	Co	orrect N	lumber of Copies:	
Received By:	Di	istributi	ion Date:	
EAPP File Number:	Co	Complex:		
Admin. Review(s) (No.):	N	No. AR Rounds:		
Delinquent Fees (Y/N):	Re	Review Time Spent:		
Lat./Long. Verified:	SO	SOS Customer Verification:		
Agent Authorization Complete/Notarized (Y/N):	Fe	Payable to TCEQ (Y/N):		N):
Core Data Form Complete (Y/N):	Cl	Check: Signed (Y/N): Less than 90 days old (Y/N)		
Core Data Form Incomplete Nos.:				d (Y/N):

General Information Form

Texas Commission on Environmental Quality

For Regulated Activities on the Edwards Aquifer Recharge and Transition Zones and Relating to 30 TAC §213.4(b) & §213.5(b)(2)(A), (B) Effective June 1, 1999

To ensure that the application is administratively complete, confirm that all fields in the form are complete, verify that all requested information is provided, consistently reference the same site and contact person in all forms in the application, and ensure forms are signed by the appropriate party.

Note: Including all the information requested in the form and attachments contributes to more streamlined technical reviews.

Signature

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. This **General Information Form** is hereby submitted for TCEQ review. The application was prepared by:

Print Name of Customer/Agent: TOM ASUQUO

Date: 05 15 20 23

Signature of Customer/Agent:

Project Information

- 1. Regulated Entity Name: ROUND ROCK CHRISTIAN ACADEMY
- 2. County: WILLIAMSON
- 3. Stream Basin: LAKE CREEK
- 4. Groundwater Conservation District (If applicable): _____
- 5. Edwards Aquifer Zone:



6. Plan Type:

WPAP
SCS
Modification

	AST			
	UST			
\boxtimes	Exception	Rec	jue	est

TCEQ-0587 (Rev. 02-11-15)

7. Customer (Applicant):

Contact Person: <u>REBECCA BLAUSER</u> Entity: <u>ROUND ROCK CHRISTIAN ACADEMY</u> Mailing Address: <u>3800 WESTWOOD DR</u> City, State: <u>ROUND ROCK, TX</u> Telephone: <u>512.255.4491</u> Email Address: <u>BECKYBLAUSER@RRCA-TX.ORG</u>

Zip: <u>78681</u> FAX: _____

8. Agent/Representative (If any):

Contact Person: <u>TOM ASUQUO</u> Entity: <u>HAGOOD ENGINEERING ASSOCIATES</u> Mailing Address: <u>900 E. MAIN STREE</u> City, State: <u>ROUND ROCK, TX</u> Telephone: <u>512.244.1546</u> Email Address: <u>TOMA@HEAENG.COM</u>

Zip: <u>78664</u> FAX: _____

9. Project Location:

The project site is located inside the city limits of <u>ROUND ROCK</u>.

The project site is located outside the city limits but inside the ETJ (extra-territorial jurisdiction) of _____.

The project site is not located within any city's limits or ETJ.

10. The location of the project site is described below. The description provides sufficient detail and clarity so that the TCEQ's Regional staff can easily locate the project and site boundaries for a field investigation.

This site is a flag lot located behind the Central Baptist Church situated at 301 N. Lake Creek Drive. The lot is situated at the termination of Westwood Drive approximately 168LF from the intersection of Westwood Drive and Bonwood Drive

- 11. Attachment A Road Map. A road map showing directions to and the location of the project site is attached. The project location and site boundaries are clearly shown on the map.
- 12. Attachment B USGS / Edwards Recharge Zone Map. A copy of the official 7 ½ minute USGS Quadrangle Map (Scale: 1" = 2000') of the Edwards Recharge Zone is attached. The map(s) clearly show:

Project site boundaries.

USGS Quadrangle Name(s).

Boundaries of the Recharge Zone (and Transition Zone, if applicable).

Drainage path from the project site to the boundary of the Recharge Zone.

13. The TCEQ must be able to inspect the project site or the application will be returned. Sufficient survey staking is provided on the project to allow TCEQ regional staff to locate the boundaries and alignment of the regulated activities and the geologic or manmade features noted in the Geologic Assessment.

TCEQ-0587 (Rev. 02-11-15)

Survey staking will be completed by this date: <u>Already completed.</u>

- 14. Attachment C Project Description. Attached at the end of this form is a detailed narrative description of the proposed project. The project description is consistent throughout the application and contains, at a minimum, the following details:
 - Area of the site
 - 🔀 Offsite areas
 - Impervious cover
 - Permanent BMP(s)
 - Proposed site use
 - Site history
 - Previous development
 - 🔀 Area(s) to be demolished
- 15. Existing project site conditions are noted below:
 - 🔀 Existing commercial site
 - Existing industrial site
 - Existing residential site
 - Existing paved and/or unpaved roads
 - 🛛 Undeveloped (Cleared)
 - Undeveloped (Undisturbed/Uncleared)
 - Other: _____

Prohibited Activities

- 16. 🔀 I am aware that the following activities are prohibited on the Recharge Zone and are not proposed for this project:
 - (1) Waste disposal wells regulated under 30 TAC Chapter 331 of this title (relating to Underground Injection Control);
 - (2) New feedlot/concentrated animal feeding operations, as defined in 30 TAC §213.3;
 - (3) Land disposal of Class I wastes, as defined in 30 TAC §335.1;
 - (4) The use of sewage holding tanks as parts of organized collection systems; and
 - (5) New municipal solid waste landfill facilities required to meet and comply with Type I standards which are defined in §330.41(b), (c), and (d) of this title (relating to Types of Municipal Solid Waste Facilities).
 - (6) New municipal and industrial wastewater discharges into or adjacent to water in the state that would create additional pollutant loading.
- 17. I am aware that the following activities are prohibited on the Transition Zone and are not proposed for this project:
 - (1) Waste disposal wells regulated under 30 TAC Chapter 331 (relating to Underground Injection Control);

- (2) Land disposal of Class I wastes, as defined in 30 TAC §335.1; and
- (3) New municipal solid waste landfill facilities required to meet and comply with Type I standards which are defined in §330.41 (b), (c), and (d) of this title.

Administrative Information

18. The fee for the plan(s) is based on:

- For a Water Pollution Abatement Plan or Modification, the total acreage of the site where regulated activities will occur.
- For an Organized Sewage Collection System Plan or Modification, the total linear footage of all collection system lines.
- For a UST Facility Plan or Modification or an AST Facility Plan or Modification, the total number of tanks or piping systems.

A request for an exception to any substantive portion of the regulations related to the protection of water quality.

- \boxtimes A request for an extension to a previously approved plan.
- 19. Application fees are due and payable at the time the application is filed. If the correct fee is not submitted, the TCEQ is not required to consider the application until the correct fee is submitted. Both the fee and the Edwards Aquifer Fee Form have been sent to the Commission's:

🔀 TCEQ cashier

Austin Regional Office (for projects in Hays, Travis, and Williamson Counties) San Antonio Regional Office (for projects in Bexar, Comal, Kinney, Medina, and Uvalde Counties)

- 20. Submit one (1) original and one (1) copy of the application, plus additional copies as needed for each affected incorporated city, groundwater conservation district, and county in which the project will be located. The TCEQ will distribute the additional copies to these jurisdictions. The copies must be submitted to the appropriate regional office.
- 21. No person shall commence any regulated activity until the Edwards Aquifer Protection Plan(s) for the activity has been filed with and approved by the Executive Director.

GENERAL INFORMATION Attachments to form TCEQ-0587

ATTACHMENT A - Road Map



GENERAL INFORMATION

Attachments to form TCEQ-0587

ATTACHMENT B - USGS / Edwards Recharge Zone Map

See attached

ATTACHMENT C - Project Description

Please refer to the attached plans for site improvement layout. The site is located within the City of Round Rock's Corporate Limits. This site is also located with the Edwards Aquifer Recharge Zone.

This exception request is for the construction of a 2065-sf classroom addition to the existing building which was included as part of the modification with the EAPP ID number 11001467.

The project site is currently developed with an existing shared partial sedimentation and filtration pond located off site. This permanent BMP was originally permitted under the Round Rock Retirement Residences under the EAPP 1D: 11-05021501. This was further modified under EAPP ID: 11-06060101. This plan was again modified under the EAPP ID number 11001467.

This pond was designed to treat a total of 10 acres with 60% impervious cover (6 acres). The existing Round Rock Retirement Residences currently has a total impervious cover of **2.26 acres**. The fully developed RRCA site (including the classroom) will have a total impervious cover of **3.44 acres**. This bring the total proposed impervious cover acreage to be treated by the pond to **5.70 acres** which is within the allowable limits of the design acreage for the pond.

Edwards Aquifer Viewer Custom Print







Austin Community College, City of Austin, County of Williamson, Texas Parks & Wildlife, Esri, HERE, Garmin, INCREMENT P, Intermap, USGS, METI/

Web AppBuilder for ArcGIS

Austin Community College, City of Austin, County of Williamson, Texas Parks & Wildlife, Esri, HERE, Garmin, INCREMENT P, Intermap, USGS, METI/NASA, EPA, USDA | TCEQ |

GEOLOGIC ASSESSMENT

ROUND ROCK CHRISTIAN ACADEMY 300 CHISHOLM TRAIL ROAD ROUND ROCK, WILLIAMSON COUNTY, TEXAS

February 19, 2019

Prepared for:

9200

Round Rock Christian Academy 301-A North Lake Creek Drive Round Rock, Texas 78681





"Setting the Standard for Service"

February 19, 2019

Ms. Rebecca K. Blauser Round Rock Christian Academy 301-A North Lake Creek Drive Round Rock, Texas 78681

Geologic Assessment for Round Rock Christian Academy, 300 Chisholm Trail Road, Subject: Round Rock, Williamson County, Texas

Dear Ms. Blauser:

We are pleased to provide Round Rock Christian Academy with a Geologic Assessment for the above referenced property. ECS' services were conducted in accordance with the services outlined in ECS Proposal 51-0920 dated and authorized on January 31, 2019.

ECS did not observe recharge features on the site. The lack of features observed on this property do not appear to meet the TCEQ's criteria for sensitive features in the Edwards Aquifer Recharge Zone; and as such, the site should not be subject to protection under applicable regulations.

If there are questions regarding this report, or a need for further information, please contact the undersigned at (512) 837-8005.

Respectfully submitted,

Roger S. Willis, M.S. **Environmental Project Manager**

ing With

Craig Hiatt, M.S. **Environmental Director**

Stephy J. Seog



Stephen Krogh, P.G. Geoscientist

Electronic Seal approved by Daniel Tibbals, P.G. on February 18, 2019

GEOLOGIC ASSESSMENT FOR DEVELOPMENT OVER THE EDWARDS AQUIFER

Round Rock Christian Academy 300 Chisholm Trail Road Round Rock, Williamson County, Texas

TABLE OF CONTENTS

1.0	Introduction	1
2.0	Soil Unit	1
3.0	Regional Geology	2
4.0	Site Geology	3
5.0	Site Hydrology	3
5.1	Surface Water Hydrology	3
6.0	Site Investigation	3
7.0	Summary	4
8.0	References	5

Attachments:

Figures

Figure 1: Subject Property Location

Figure 2: Topographic Map

- Figure 3: Subject Property Map
- Figure 4: Edwards Aquifer Map of the Subject Site
- Figure 5: Soil Survey Map
- Figure 6: Geologic Map

Appendices

Completed Form TCEQ-0585 Stratigraphic Column Narrative Description of Site Specific Geology Photo Documentation

Attachments

Soil Survey

Round Rock Christian Academy Round Rock, Williamson County, Texas ECS Project No. 51:1542 February 18, 2019

1.0 Introduction

The geologic assessment provided here, as part of the applicant's plan, addresses the required items as cited in Title 30 of the Texas Administrative Code (TAC), Part 1, Chapter 213, Subchapter A, Rule 213.5, relating to development over the Edwards Aquifer (Figure 1). This report identifies observed potential pathways for contaminant movement into the underlying Edwards Aquifer as required by the Texas Commission on Environmental Quality (TCEQ).

The subject property consists of a portion of one (1) parcel of land containing approximately 8.8 acres of partially developed land located at 300 Chisholm Trail Road in Round Rock, Williamson County, Texas. *The subject property is located within the Edwards Aquifer Recharge Zone.*

The purpose of this Geologic Assessment is to fulfill the requirements for the applicant's plan for site improvements on the property. This report will describe surficial geologic units and identify the locations and extent of significant features that may impact the underlying Edwards Aquifer recharge zone.

2.0 Soil Units

According to the United States Department of Agriculture (USDA) Soil Survey of Williamson County, Texas, there are two (2) soil units mapped on the site. The soils on site consist of Doss silty clay, moist, 1 to 5 percent slopes (DoC) and Eckrant extremely stony clay, 0 to 3 percent slopes (EeB).

Doss silty clay, moist, 1 to 5 percent slopes (DoC) consists shallow soils formed in residuum weathered from limestone located on the back and side slopes of ridges. Slopes range from 1 to 5 percent. The Hydrologic Soil Group is listed as D, and the soil is well drained. Flooding or ponding is reported as "none." Capacity of the most limiting layer to transmit water (Ksat) is listed as moderately low (0.06 to 0.57 in/hr). The depth to a restrictive layer is reported as 11-20 inches to paralithic bedrock, and the available water storage (in profile) is listed as very low. This soil is listed as "not prime farmland."

Eckrant extremely stony clay, 0 to 3 percent slopes (EeB) consists shallow soils formed in residuum weathered from limestone located on the summit and side slopes of ridges. Slopes range from 0 to 3 percent. The Hydrologic Soil Group is listed as D, and the soil is well drained. Flooding or ponding is

Round Rock Christian Academy Round Rock, Williamson County, Texas ECS Project No. 51:1542 February 18, 2019

reported as "none." Capacity of the most limiting layer to transmit water (Ksat) is listed as moderately low to moderately high (0.06 to 0.57 in/hr). The depth to a restrictive layer is reported to be 10 to 20 inches to lithic bedrock, and the available water storage (in profile) is listed as very low. This soil is listed as not prime farmland."

3.0 Regional Geology

Ranging from east to west, two primary physiographic provinces are present in Williamson County, the Gulf Coastal Plain and the Great Plain. The Gulf Coastal Plain is comprised mainly of Blackland prairie. The Great plain is comprised chiefly of limestone plains, which merges with the Edwards Plateau in the vicinity of the Colorado River.

Groundwater recharge and flow are controlled by faulted Edwards Aquifer and adjacent strata. Water enters the aquifer by means of solution features controlled by faults, fractures and solution conduits. Solution features are created by the dissolution of limestone primarily from rainwater and groundwater. Deformation of the Balcones fault system controls both the large and small scale flow barriers and pathways present in the Edwards Aquifer.

4.0 Site Geology

Geological information pertaining to the area was obtained from the Geologic Atlas of Texas, Austin Sheet, published by University of Texas at Austin, Bureau of Economic Geology (BEG), 1997. The subject property is situated on Edwards Limestone (Ked). BEG describes the formation as gray, calcareous and gypsiferous clay that contains pyrite and marine megafossils. No faulting was observed or mapped on the site. *The subject property is located within the Edwards Aquifer Recharge Zone.*

5.0 Site Hydrology

Based upon interpretation of the United States Geological Survey 7.5 Minute Series topographic quadrangle map, Georgetown, Texas, and the onsite reconnaissance, the estimated regional shallow groundwater flow direction is southeasterly. It should be noted that shallow groundwater flow direction is estimated based on a review of published maps, surface topography, and site reconnaissance. Local

conditions that may influence the subsurface hydrology would be local topography (hills and valleys), geologic anomalies, utilities, and nearby wells or sumps.

5.1 Surface Water Hydrology

The western portion of subject property drains to the west towards N Lake Creek Drive. The eastern portion of the subject property drains towards the southeast towards Lake Creek. Field observations and analysis are supported from the Round Rock, Texas USGS Topographic Quadrangle map. There were no observed groundwater seeps or discharges of any type from bedrock observed on the subject site.

6.0 Site Investigation

The site reconnaissance was performed on February 14, 2019. The site investigation was performed by traversing the subject property in meandering transects, spaced 10 to 15 meters apart. Photographs were taken to document any features observed during the reconnaissance.

The subject property consists of a 8.8-acre partially developed parcel of land. The developed portions of the subject property consists of three (3) temporary buildings, one (1) permanent building, athletic fields consisting of manicured turf areas on the central and northern portions. The southern portion of the subject property is essentially undeveloped. The vegetation consists of manicured turf grass, naturalized grasses, herbs and forbs. Scattered ashe juniper and oak trees are present on the central and southern portions of the subject property.

No potential natural recharge features such as caves, sinkholes, closed depressions, solution cavities, fractured rock outcrops, faults or lineaments were observed on the subject property. Four (4) buildings, as well as one (1) water well were observed on the subject property. The water well is located within a pump house adjacent to the permanent building on the central portion of the subject property. The well system consists of an electric pump and pressure tank. An intact annular seal at the ground surface appears to prevent groundwater infiltration into the well. Evidence of standing water or surface water infiltration was not observed in the vicinity of the well or annular seal. Petroleum products or hazardous materials were not located within the pump house, or in the vicinity of the pump house, at the time of the geologic assessment.

Round Rock Christian Academy Round Rock, Williamson County, Texas ECS Project No. 51:1542 February 18, 2019

7.0 Summary

The subject property consists of one (1) parcel that contains 8.8 acres of partially developed land located at 300 Chisholm Trail Road in Round Rock, Williamson County, Texas. *The subject property is located within the Edwards Aquifer Recharge Zone.*

Karst features were not identified on the site. No caves or cavities were observed on the subject property at the time of the site reconnaissance with the potential for contaminant movement into the Edwards Aquifer. Four (4) buildings and one (1) water well were observed on the subject property.

It appears that the property drains to the west. No improved drainage features were observed on the subject property.

Round Rock Christian Academy Round Rock, Williamson County, Texas ECS Project No. 51:1542 February 18, 2019

8.0 References

- (BEG) The University of Texas at Austin Bureau of Economic Geology, Geologic Map of Texas, Austin Sheet, 1997.
- (USDA) United States Department of Agriculture (USDA) Custom Soil Survey of Williamson County, 2019.

United States Geologic Survey (USGS), Round Rock, Texas Topographic Quadrangle, 2013.

ATTACHMENTS

FIGURES



Figure 1 -- Subject Property Location Map



Round Rock Christian Academy 300 Chisholm Trail Road Round Rock, Texas 78681 ECS Project 51:1542





Figure 2 -- Topographic Map









W X S

Figure 3 -- Subject Property Map Round Rock Christian Academy 300 Chisholm Trail Road Round Rock, Texas 78681

ECS Project 51:1542





W K S

Figure 6 -- Geologic Map Round Rock Christian Academy 300 Chisholm Trail Road Round Rock, Texas 78681 ECS Project 51:1542





w K r

Figure 4 -- Edwards Aquifer Map

Round Rock Christian Academy 300 Chisholm Trail Road Round Rock, TX 78681 ECS Project 51:1542





W K S

Figure 5 -- Soils Map Round Rock Christian Academy 300 Chisholm Trail Road Round Rock, TX 78681 ECS Project 51:1542





Figure 6 -- Geologic Map



Round Rock Christian Academy 300 Chisholm Trail Road Round Rock, Texas 78681 ECS Project 51:1542



APPENDIX

Completed Form TCEQ-0585

Geologic Assessment

Texas Commission on Environmental Quality

For Regulated Activities on The Edwards Aquifer Recharge/transition Zones and Relating to 30 TAC §213.5(b)(3), Effective June 1, 1999

To ensure that the application is administratively complete, confirm that all fields in the form are complete, verify that all requested information is provided, consistently reference the same site and contact person in all forms in the application, and ensure forms are signed by the appropriate party.

Note: Including all the information requested in the form and attachments contributes to more streamlined technical reviews.

Signature

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. My signature certifies that I am qualified as a geologist as defined by 30 TAC Chapter 213.

Print Name of Geologist: <u>Stephen Krogh</u>

Telephone: 512-837-8005

Date: 2/18/2019

Fax: <u>512-837-8221</u>

Representing: <u>ECS Southwest, LLP, PG 3387</u> (Name of Company and TBPG or TBPE registration number)

Signature of Geologist:

Stephen 9. Jeach

Regulated Entity Name: Round Rock Christian Academyt

Project Information

- 1. Date(s) Geologic Assessment was performed: February 13, 2019
- 2. Type of Project:

\times	WPAP
	SCS

AST
UST

3. Location of Project:

\ge	Rec	har	ge	Zon	e
	_			_	

Transition Zone

Contributing Zone within the Transition Zone

- 4. X Attachment A Geologic Assessment Table. Completed Geologic Assessment Table (Form TCEQ-0585-Table) is attached.
- 5. Soil cover on the project site is summarized in the table below and uses the SCS Hydrologic Soil Groups* (Urban Hydrology for Small Watersheds, Technical Release No. 55, Appendix A, Soil Conservation Service, 1986). If there is more than one soil type on the project site, show each soil type on the site Geologic Map or a separate soils map.

Table 1 - Soil Units, InfiltrationCharacteristics and Thickness

Soil Name	Group*	Thickness(feet)
Doss silty clay, moist, 1-5% slopes (DoC)	D	>1
Eckrant extremely stony clay, 0-2% slopes (EeB)	D	<1

Soil Name	Group*	Thickness(feet)						

- * Soil Group Definitions (Abbreviated)
 - A. Soils having a high infiltration rate when thoroughly wetted.
 - B. Soils having a moderate infiltration rate when thoroughly wetted.
 - C. Soils having a slow infiltration rate when thoroughly wetted.
 - D. Soils having a very slow infiltration rate when thoroughly wetted.
- 6. Attachment B Stratigraphic Column. A stratigraphic column showing formations, members, and thicknesses is attached. The outcropping unit, if present, should be at the top of the stratigraphic column. Otherwise, the uppermost unit should be at the top of the stratigraphic column.
- 7. X Attachment C Site Geology. A narrative description of the site specific geology including any features identified in the Geologic Assessment Table, a discussion of the potential for fluid movement to the Edwards Aquifer, stratigraphy, structure(s), and karst characteristics is attached.
- 8. Attachment D Site Geologic Map(s). The Site Geologic Map must be the same scale as the applicant's Site Plan. The minimum scale is 1": 400'

Applicant's Site Plan Scale: 1" = <u>400</u>' Site Geologic Map Scale: 1" = <u>400</u>' Site Soils Map Scale (if more than 1 soil type): 1" = <u>400</u>'

9. Method of collecting positional data:

Global Positioning System (GPS) technology.

Other method(s). Please describe method of data collection:

10. The project site and boundaries are clearly shown and labeled on the Site Geologic Map.

- 11. Surface geologic units are shown and labeled on the Site Geologic Map.
- 12. Geologic or manmade features were discovered on the project site during the field investigation. They are shown and labeled on the Site Geologic Map and are described in the attached Geologic Assessment Table.

Geologic or manmade features were not discovered on the project site during the field investigation.

- 13. \square The Recharge Zone boundary is shown and labeled, if appropriate.
- 14. All known wells (test holes, water, oil, unplugged, capped and/or abandoned, etc.): If applicable, the information must agree with Item No. 20 of the WPAP Application Section.

There are $\underline{1}$ (#) wells present on the project site and the locations are shown and labeled. (Check all of the following that apply.)

] The wells are not in use and have been properly abandoned.

ig The wells are not in use and will be properly abandoned.

] The wells are in use and comply with 16 TAC Chapter 76.

There are no wells or test holes of any kind known to exist on the project site.

Administrative Information

15. Submit one (1) original and one (1) copy of the application, plus additional copies as needed for each affected incorporated city, groundwater conservation district, and county in which the project will be located. The TCEQ will distribute the additional copies to these jurisdictions. The copies must be submitted to the appropriate regional office.

GEOLOGIC ASSESSMENT TABLE PROJECT NAME:																				
LOCATION				FEATURE CHARACTERISTICS									EVALUATION PHYSICAL SET					_ SETTING		
1A	1B *	1C*	2A	2B	3	4		5	5A	6	7	8A	8B	9	9 10		11		12	
FEATURE ID	LATITUDE	LONGITUDE	FEATURE TYPE	POINTS	FORMATION	DIMENSIONS (FEET)		TREND (DEGREES)	DOM	DENSITY (NO/FT)	APERTURE (FEET)	INFILL	RELATIVE INFILTRATION RATE	TOTAL	SENSITIVITY		CATCHMENT AREA (ACRES)		TOPOGRAPHY	
						х	Υ	Z		10						<40	<u>>40</u>	<1.6	<u>>1.6</u>	
Well	30.508933°	-97.691521°	MB	30	KeD	1	1	Unk	0				Х	0	30	Х		Х		Hilltop
-																				
-																				
* DATUM:																				
2A TYPE	0	TYPE		21	BPOINTS	S 8A INFILLING														
	Cave				30	J IN NORE, EXPOSED DEDITOCK														
SC	Solution cavit	у			20	C Coarse - cobbles, breakdown, sand, gravel														
SF	Solution-enlar	ged fracture(s)			20	O Loose or soft mud or soil, organics, leaves, sticks, dark co								olors						
F	Fault				20) F Fines, compacted clay-rich sediment, soil profile, gray or red colors														
0	Other natural	bedrock features			5	V Vegetation. Give details in narrative description														
SW/	Swallow bolo				30	Y Other materials														
SH	Sinkhole				20															
CD	Non-karst clos	sed depression			20															
7	Zone clustere	ed or aligned feat	ires		30		Hill	ton												
CD Z	Non-karst clos Zone, clustere	sed depression ed or aligned feat	ures		5 30	5 12 TOPOGRAPHY 30 Hilltop														

I have read, I understood, and I have followed the Texas Commission on Environmental Quality's Instructions to Geologists. The information presented here complies with that document and is a true representation of the conditions observed in the field. My signature certifies that I am qualified as a geologist as defined by 30 TAC Chapter 213.

Stephy g. Seaf

TCEQ-0585-Table (Rev. 10-01-04)

Date OF TE TE Sheet ___1___ of ___1___ STEPHEN J. KROGH GEOLOGY 3387

2/18/2019

Stratigraphic Column
Stratigraphic Column Proposed Express Car Wash Smyers Lane at FM 620 Round Rock, Williamson County, Texas

Formation	Thickness (ft)	Description
Edwards Formation	100-300	The Edwards Formation consists of
(Ked)		approximately 100 to 300 feet) of
		limestone, dolomitic limestone, and some
		marl. Known to contain karstic solution
		cavities and accounts for most of the
		Edwards Aquifer strata.

Narrative Description of Site Specific Geology

Round Rock Christian Academy Round Rock, Williamson County, Texas ECS Project No. 51:1542 February 19, 2019

NARRATIVE DESCRIPTION OF SITE SPECIFIC GEOLOGY

The property is situated on the Edwards Aquifer Recharge Zone. Ranging from north to south, two primary physiographic provinces are present in Bexar County: the Great Plain and the Gulf Coastal Plain. The Gulf Coastal Plain is comprised mainly of Blackland prairie. The Great Plain is comprised chiefly of limestone plains, which merges with the Edwards Plateau in the vicinity of the Colorado River.

Groundwater recharge and flow are controlled by faulted Edwards Aquifer and adjacent strata. Water enters the aquifer by means of solution features controlled by faults, fractures and solution conduits. Solution features are created by the dissolution of limestone primarily from rainwater and groundwater. Deformation of the Balcones fault system controls both the large and small scale flow barriers and pathways present in the Edwards Aquifer.

Geological information pertaining to the area was obtained from the Geologic Atlas of Texas, Austin Sheet, published by University of Texas at Austin, Bureau of Economic Geology (BEG), 1997. The subject property is situated on the Edwards Limestone (Ked). BEG describes the formation as medium gray to grayish brown, fine to coarse grained, fossiliferous, limestone with abundant chert. Solution zones and collapse breccia are common in the Edwards Limestone. No faulting was observed on the site.

Vegetation on the site consists of manicured turf grass on athletic fields, naturalized grasses, herbs, and forbs, as well as sycamores associated with landscaping and natural stands of scrub live oak and ashe juniper.

No potential natural recharge features such as caves, sinkholes, closed depressions, solution cavities, fractured rock outcrops, faults or lineaments were observed on the subject property. One (1) water well was observed within a pump house on the central portion of the subject property.



Photo Documentation



1 - View of western portion of subject property



2 - View of western portion of subject property near temporary buildings





3 - View of well head and pressure tank



4 - View of temporary buildings





5 - View of southeastern portion of the property



6 - View of permanent building





7 - View of permanent building and well pump house



8 - View of eastern portion of subject property



ATTACHMENTS

Soil Survey



United States Department of Agriculture



Natural Resources Conservation Service A product of the National Cooperative Soil Survey, a joint effort of the United States Department of Agriculture and other Federal agencies, State agencies including the Agricultural Experiment Stations, and local participants

Custom Soil Resource Report for Williamson County, Texas

Round Rock Christian Academy



Preface

Soil surveys contain information that affects land use planning in survey areas. They highlight soil limitations that affect various land uses and provide information about the properties of the soils in the survey areas. Soil surveys are designed for many different users, including farmers, ranchers, foresters, agronomists, urban planners, community officials, engineers, developers, builders, and home buyers. Also, conservationists, teachers, students, and specialists in recreation, waste disposal, and pollution control can use the surveys to help them understand, protect, or enhance the environment.

Various land use regulations of Federal, State, and local governments may impose special restrictions on land use or land treatment. Soil surveys identify soil properties that are used in making various land use or land treatment decisions. The information is intended to help the land users identify and reduce the effects of soil limitations on various land uses. The landowner or user is responsible for identifying and complying with existing laws and regulations.

Although soil survey information can be used for general farm, local, and wider area planning, onsite investigation is needed to supplement this information in some cases. Examples include soil quality assessments (http://www.nrcs.usda.gov/wps/portal/nrcs/main/soils/health/) and certain conservation and engineering applications. For more detailed information, contact your local USDA Service Center (https://offices.sc.egov.usda.gov/locator/app?agency=nrcs) or your NRCS State Soil Scientist (http://www.nrcs.usda.gov/wps/portal/nrcs/detail/soils/contactus/? cid=nrcs142p2_053951).

Great differences in soil properties can occur within short distances. Some soils are seasonally wet or subject to flooding. Some are too unstable to be used as a foundation for buildings or roads. Clayey or wet soils are poorly suited to use as septic tank absorption fields. A high water table makes a soil poorly suited to basements or underground installations.

The National Cooperative Soil Survey is a joint effort of the United States Department of Agriculture and other Federal agencies, State agencies including the Agricultural Experiment Stations, and local agencies. The Natural Resources Conservation Service (NRCS) has leadership for the Federal part of the National Cooperative Soil Survey.

Information about soils is updated periodically. Updated information is available through the NRCS Web Soil Survey, the site for official soil survey information.

The U.S. Department of Agriculture (USDA) prohibits discrimination in all its programs and activities on the basis of race, color, national origin, age, disability, and where applicable, sex, marital status, familial status, parental status, religion, sexual orientation, genetic information, political beliefs, reprisal, or because all or a part of an individual's income is derived from any public assistance program. (Not all prohibited bases apply to all programs.) Persons with disabilities who require

alternative means for communication of program information (Braille, large print, audiotape, etc.) should contact USDA's TARGET Center at (202) 720-2600 (voice and TDD). To file a complaint of discrimination, write to USDA, Director, Office of Civil Rights, 1400 Independence Avenue, S.W., Washington, D.C. 20250-9410 or call (800) 795-3272 (voice) or (202) 720-6382 (TDD). USDA is an equal opportunity provider and employer.

Contents

Preface	2
How Soil Surveys Are Made	5
Soil Map	8
Soil Map	9
Legend	10
Map Unit Legend	11
Map Unit Descriptions	11
Williamson County, Texas	13
DoC-Doss silty clay, moist, 1 to 5 percent slopes	13
EeB—Eckrant extremely stony clay, 0 to 3 percent slopes	15
References	17

How Soil Surveys Are Made

Soil surveys are made to provide information about the soils and miscellaneous areas in a specific area. They include a description of the soils and miscellaneous areas and their location on the landscape and tables that show soil properties and limitations affecting various uses. Soil scientists observed the steepness, length, and shape of the slopes; the general pattern of drainage; the kinds of crops and native plants; and the kinds of bedrock. They observed and described many soil profiles. A soil profile is the sequence of natural layers, or horizons, in a soil. The profile extends from the surface down into the unconsolidated material in which the soil formed or from the surface down to bedrock. The unconsolidated material is devoid of roots and other living organisms and has not been changed by other biological activity.

Currently, soils are mapped according to the boundaries of major land resource areas (MLRAs). MLRAs are geographically associated land resource units that share common characteristics related to physiography, geology, climate, water resources, soils, biological resources, and land uses (USDA, 2006). Soil survey areas typically consist of parts of one or more MLRA.

The soils and miscellaneous areas in a survey area occur in an orderly pattern that is related to the geology, landforms, relief, climate, and natural vegetation of the area. Each kind of soil and miscellaneous area is associated with a particular kind of landform or with a segment of the landform. By observing the soils and miscellaneous areas in the survey area and relating their position to specific segments of the landform, a soil scientist develops a concept, or model, of how they were formed. Thus, during mapping, this model enables the soil scientist to predict with a considerable degree of accuracy the kind of soil or miscellaneous area at a specific location on the landscape.

Commonly, individual soils on the landscape merge into one another as their characteristics gradually change. To construct an accurate soil map, however, soil scientists must determine the boundaries between the soils. They can observe only a limited number of soil profiles. Nevertheless, these observations, supplemented by an understanding of the soil-vegetation-landscape relationship, are sufficient to verify predictions of the kinds of soil in an area and to determine the boundaries.

Soil scientists recorded the characteristics of the soil profiles that they studied. They noted soil color, texture, size and shape of soil aggregates, kind and amount of rock fragments, distribution of plant roots, reaction, and other features that enable them to identify soils. After describing the soils in the survey area and determining their properties, the soil scientists assigned the soils to taxonomic classes (units). Taxonomic classes are concepts. Each taxonomic class has a set of soil characteristics with precisely defined limits. The classes are used as a basis for comparison to classify soils systematically. Soil taxonomy, the system of taxonomic classification used in the United States, is based mainly on the kind and character of soil properties and the arrangement of horizons within the profile. After the soil

scientists classified and named the soils in the survey area, they compared the individual soils with similar soils in the same taxonomic class in other areas so that they could confirm data and assemble additional data based on experience and research.

The objective of soil mapping is not to delineate pure map unit components; the objective is to separate the landscape into landforms or landform segments that have similar use and management requirements. Each map unit is defined by a unique combination of soil components and/or miscellaneous areas in predictable proportions. Some components may be highly contrasting to the other components of the map unit. The presence of minor components in a map unit in no way diminishes the usefulness or accuracy of the data. The delineation of such landforms and landform segments on the map provides sufficient information for the development of resource plans. If intensive use of small areas is planned, onsite investigation is needed to define and locate the soils and miscellaneous areas.

Soil scientists make many field observations in the process of producing a soil map. The frequency of observation is dependent upon several factors, including scale of mapping, intensity of mapping, design of map units, complexity of the landscape, and experience of the soil scientist. Observations are made to test and refine the soil-landscape model and predictions and to verify the classification of the soils at specific locations. Once the soil-landscape model is refined, a significantly smaller number of measurements of individual soil properties are made and recorded. These measurements may include field measurements, such as those for color, depth to bedrock, and texture, and laboratory measurements, such as those for content of sand, silt, clay, salt, and other components. Properties of each soil typically vary from one point to another across the landscape.

Observations for map unit components are aggregated to develop ranges of characteristics for the components. The aggregated values are presented. Direct measurements do not exist for every property presented for every map unit component. Values for some properties are estimated from combinations of other properties.

While a soil survey is in progress, samples of some of the soils in the area generally are collected for laboratory analyses and for engineering tests. Soil scientists interpret the data from these analyses and tests as well as the field-observed characteristics and the soil properties to determine the expected behavior of the soils under different uses. Interpretations for all of the soils are field tested through observation of the soils in different uses and under different levels of management. Some interpretations are modified to fit local conditions, and some new interpretations are developed to meet local needs. Data are assembled from other sources, such as research information, production records, and field experience of specialists. For example, data on crop yields under defined levels of management are assembled from farm records and from field or plot experiments on the same kinds of soil.

Predictions about soil behavior are based not only on soil properties but also on such variables as climate and biological activity. Soil conditions are predictable over long periods of time, but they are not predictable from year to year. For example, soil scientists can predict with a fairly high degree of accuracy that a given soil will have a high water table within certain depths in most years, but they cannot predict that a high water table will always be at a specific level in the soil on a specific date.

After soil scientists located and identified the significant natural bodies of soil in the survey area, they drew the boundaries of these bodies on aerial photographs and

identified each as a specific map unit. Aerial photographs show trees, buildings, fields, roads, and rivers, all of which help in locating boundaries accurately.

Soil Map

The soil map section includes the soil map for the defined area of interest, a list of soil map units on the map and extent of each map unit, and cartographic symbols displayed on the map. Also presented are various metadata about data used to produce the map, and a description of each soil map unit.



	MAP LEGEND			MAP INFORMATION	
Area of Int	Area of Interest (AOI)		Spoil Area	The soil surveys that comprise your AOI were mapped at	
	Area of Interest (AOI)	٥	Stony Spot	1:20,000.	
Soils		0	Very Stony Spot	Warning: Soil Map may not be valid at this scale	
	Soil Map Unit Polygons	\$2	Wet Spot		
~	Soil Map Unit Lines	Δ	Other	Enlargement of maps beyond the scale of mapping can cause	
	Soil Map Unit Points	- S	Special Line Features	line placement. The maps do not show the small areas of	
Special	Point Features	Water Fea	itures	contrasting soils that could have been shown at a more detailed	
9	Borrow Dit	\sim	Streams and Canals	50010.	
	Borrow Pit	Transportation		Please rely on the bar scale on each map sheet for map	
英	Clay Spot	+++	Rails	measurements.	
\diamond	Closed Depression	~	Interstate Highways	Source of Map: Natural Resources Conservation Service	
X	Gravel Pit	~	US Routes	Web Soil Survey URL:	
00	Gravelly Spot	\sim	Major Roads Coordinate System: Web Mercato	Coordinate System: Web Mercator (EPSG:3857)	
0	Landfill	\sim	Local Roads	Maps from the Web Soil Survey are based on the Web Mercator	
Λ.	🙏 Lava Flow		nd	projection, which preserves direction and shape but distorts distance and area. A projection that preserves area, such as the	
علله	Marsh or swamp	Contraction of the local division of the loc	Aerial Photography	Albers equal-area conic projection, should be used if more accurate calculations of distance or area are required.	
衆	Mine or Quarry				
0	Miscellaneous Water			This product is generated from the USDA-NRCS certified data as	
0	Perennial Water			of the version date(s) listed below.	
\sim	Rock Outcrop			Soil Survey Area: Williamson County, Texas	
+	Saline Spot			Survey Area Data: Version 19, Sep 15, 2018	
°.°	Sandy Spot			Soil man units are labeled (as space allows) for man scales	
-	Severely Eroded Spot			1:50,000 or larger.	
۵	Sinkhole			Data(c) agrial images were photographed: Ech 8, 2015 Mar	
à	Slide or Slip			14, 2017	
, second s	Sodic Spot			The education of the base were as which the edition of the	
θų.				compiled and digitized probably differs from the background imagery displayed on these maps. As a result, some minor shifting of map unit boundaries may be evident.	

Map Unit Legend

Map Unit Symbol	Map Unit Name	Acres in AOI	Percent of AOI
DoC	Doss silty clay, moist, 1 to 5 percent slopes	8.8	99.9%
EeB	Eckrant extremely stony clay, 0 to 3 percent slopes	0.0	0.1%
Totals for Area of Interest	•	8.8	100.0%

Map Unit Descriptions

The map units delineated on the detailed soil maps in a soil survey represent the soils or miscellaneous areas in the survey area. The map unit descriptions, along with the maps, can be used to determine the composition and properties of a unit.

A map unit delineation on a soil map represents an area dominated by one or more major kinds of soil or miscellaneous areas. A map unit is identified and named according to the taxonomic classification of the dominant soils. Within a taxonomic class there are precisely defined limits for the properties of the soils. On the landscape, however, the soils are natural phenomena, and they have the characteristic variability of all natural phenomena. Thus, the range of some observed properties may extend beyond the limits defined for a taxonomic class. Areas of soils of a single taxonomic class rarely, if ever, can be mapped without including areas of other taxonomic classes. Consequently, every map unit is made up of the soils or miscellaneous areas for which it is named and some minor components that belong to taxonomic classes other than those of the major soils.

Most minor soils have properties similar to those of the dominant soil or soils in the map unit, and thus they do not affect use and management. These are called noncontrasting, or similar, components. They may or may not be mentioned in a particular map unit description. Other minor components, however, have properties and behavioral characteristics divergent enough to affect use or to require different management. These are called contrasting, or dissimilar, components. They generally are in small areas and could not be mapped separately because of the scale used. Some small areas of strongly contrasting soils or miscellaneous areas are identified by a special symbol on the maps. If included in the database for a given area, the contrasting minor components are identified in the map unit descriptions along with some characteristics of each. A few areas of minor components may not have been observed, and consequently they are not mentioned in the descriptions, especially where the pattern was so complex that it was impractical to make enough observations to identify all the soils and miscellaneous areas on the landscape.

The presence of minor components in a map unit in no way diminishes the usefulness or accuracy of the data. The objective of mapping is not to delineate pure taxonomic classes but rather to separate the landscape into landforms or landform segments that have similar use and management requirements. The delineation of such segments on the map provides sufficient information for the development of resource plans. If intensive use of small areas is planned, however,

onsite investigation is needed to define and locate the soils and miscellaneous areas.

An identifying symbol precedes the map unit name in the map unit descriptions. Each description includes general facts about the unit and gives important soil properties and qualities.

Soils that have profiles that are almost alike make up a *soil series*. Except for differences in texture of the surface layer, all the soils of a series have major horizons that are similar in composition, thickness, and arrangement.

Soils of one series can differ in texture of the surface layer, slope, stoniness, salinity, degree of erosion, and other characteristics that affect their use. On the basis of such differences, a soil series is divided into *soil phases*. Most of the areas shown on the detailed soil maps are phases of soil series. The name of a soil phase commonly indicates a feature that affects use or management. For example, Alpha silt loam, 0 to 2 percent slopes, is a phase of the Alpha series.

Some map units are made up of two or more major soils or miscellaneous areas. These map units are complexes, associations, or undifferentiated groups.

A *complex* consists of two or more soils or miscellaneous areas in such an intricate pattern or in such small areas that they cannot be shown separately on the maps. The pattern and proportion of the soils or miscellaneous areas are somewhat similar in all areas. Alpha-Beta complex, 0 to 6 percent slopes, is an example.

An association is made up of two or more geographically associated soils or miscellaneous areas that are shown as one unit on the maps. Because of present or anticipated uses of the map units in the survey area, it was not considered practical or necessary to map the soils or miscellaneous areas separately. The pattern and relative proportion of the soils or miscellaneous areas are somewhat similar. Alpha-Beta association, 0 to 2 percent slopes, is an example.

An *undifferentiated group* is made up of two or more soils or miscellaneous areas that could be mapped individually but are mapped as one unit because similar interpretations can be made for use and management. The pattern and proportion of the soils or miscellaneous areas in a mapped area are not uniform. An area can be made up of only one of the major soils or miscellaneous areas, or it can be made up of all of them. Alpha and Beta soils, 0 to 2 percent slopes, is an example.

Some surveys include *miscellaneous areas*. Such areas have little or no soil material and support little or no vegetation. Rock outcrop is an example.

Williamson County, Texas

DoC—Doss silty clay, moist, 1 to 5 percent slopes

Map Unit Setting

National map unit symbol: 2s0st Elevation: 630 to 1,840 feet Mean annual precipitation: 30 to 36 inches Mean annual air temperature: 66 to 68 degrees F Frost-free period: 210 to 240 days Farmland classification: Not prime farmland

Map Unit Composition

Doss and similar soils: 85 percent Minor components: 15 percent Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Doss

Setting

Landform: Hillslopes Landform position (two-dimensional): Backslope Landform position (three-dimensional): Side slope Down-slope shape: Convex Across-slope shape: Linear Parent material: Residuum weathered from limestone

Typical profile

A - 0 to 9 inches: silty clay Bk - 9 to 17 inches: silty clay Cr - 17 to 80 inches: bedrock

Properties and qualities

Slope: 1 to 5 percent
Depth to restrictive feature: 11 to 20 inches to paralithic bedrock
Natural drainage class: Well drained
Runoff class: Medium
Capacity of the most limiting layer to transmit water (Ksat): Moderately low to moderately high (0.06 to 0.57 in/hr)
Depth to water table: More than 80 inches
Frequency of flooding: None
Frequency of ponding: None
Calcium carbonate, maximum in profile: 70 percent
Salinity, maximum in profile: Nonsaline to very slightly saline (0.0 to 2.0 mmhos/cm)
Available water storage in profile: Very low (about 2.4 inches)

Interpretive groups

Land capability classification (irrigated): None specified Land capability classification (nonirrigated): 4e Hydrologic Soil Group: D Ecological site: Shallow 29-35" PZ (R081CY574TX) Hydric soil rating: No

Minor Components

Brackett

Percent of map unit: 7 percent Landform: Ridges Landform position (two-dimensional): Shoulder, backslope, footslope Landform position (three-dimensional): Side slope Down-slope shape: Linear Across-slope shape: Convex Ecological site: Steep Adobe 29-35" PZ (R081CY362TX) Hydric soil rating: No

Bolar

Percent of map unit: 5 percent Landform: Ridges Landform position (two-dimensional): Shoulder Landform position (three-dimensional): Side slope Down-slope shape: Convex Across-slope shape: Convex Ecological site: Clay Loam 29-35" PZ (R081CY357TX) Hydric soil rating: No

Purves

Percent of map unit: 1 percent Landform: Plains Landform position (two-dimensional): Backslope Landform position (three-dimensional): Side slope Down-slope shape: Convex Across-slope shape: Linear Ecological site: Shallow 29-35" PZ (R081CY574TX) Hydric soil rating: No

Eckrant

Percent of map unit: 1 percent Landform: Ridges Landform position (two-dimensional): Shoulder Landform position (three-dimensional): Side slope Down-slope shape: Convex Across-slope shape: Convex Ecological site: Low Stony Hill 29-35" PZ (R081CY360TX) Hydric soil rating: No

Denton

Percent of map unit: 1 percent Landform: Plains Landform position (two-dimensional): Backslope Landform position (three-dimensional): Side slope Down-slope shape: Linear Across-slope shape: Linear Ecological site: Clay Loam 29-35" PZ (R081CY357TX) Hydric soil rating: No

EeB—Eckrant extremely stony clay, 0 to 3 percent slopes

Map Unit Setting

National map unit symbol: djpv Elevation: 1,000 to 2,400 feet Mean annual precipitation: 22 to 32 inches Mean annual air temperature: 66 to 70 degrees F Frost-free period: 210 to 240 days Farmland classification: Not prime farmland

Map Unit Composition

Eckrant and similar soils: 100 percent *Estimates are based on observations, descriptions, and transects of the mapunit.*

Description of Eckrant

Setting

Landform: Ridges Landform position (two-dimensional): Summit Landform position (three-dimensional): Side slope Down-slope shape: Convex Across-slope shape: Convex Parent material: Residuum weathered from limestone

Typical profile

H1 - 0 to 4 inches: extremely stony clay H2 - 4 to 11 inches: extremely stony clay H3 - 11 to 16 inches: bedrock

Properties and qualities

Slope: 0 to 3 percent
Depth to restrictive feature: 10 to 20 inches to lithic bedrock
Natural drainage class: Well drained
Capacity of the most limiting layer to transmit water (Ksat): Moderately low to moderately high (0.06 to 0.57 in/hr)
Depth to water table: More than 80 inches
Frequency of flooding: None
Frequency of ponding: None
Calcium carbonate, maximum in profile: 8 percent
Salinity, maximum in profile: Nonsaline to very slightly saline (0.0 to 2.0 mmhos/cm)
Available water storage in profile: Very low (about 0.9 inches)

Interpretive groups

Land capability classification (irrigated): None specified Land capability classification (nonirrigated): 7s Hydrologic Soil Group: D Ecological site: Low Stony Hill 29-35" PZ (R081CY360TX) Hydric soil rating: No Custom Soil Resource Report

References

American Association of State Highway and Transportation Officials (AASHTO). 2004. Standard specifications for transportation materials and methods of sampling and testing. 24th edition.

American Society for Testing and Materials (ASTM). 2005. Standard classification of soils for engineering purposes. ASTM Standard D2487-00.

Cowardin, L.M., V. Carter, F.C. Golet, and E.T. LaRoe. 1979. Classification of wetlands and deep-water habitats of the United States. U.S. Fish and Wildlife Service FWS/OBS-79/31.

Federal Register. July 13, 1994. Changes in hydric soils of the United States.

Federal Register. September 18, 2002. Hydric soils of the United States.

Hurt, G.W., and L.M. Vasilas, editors. Version 6.0, 2006. Field indicators of hydric soils in the United States.

National Research Council. 1995. Wetlands: Characteristics and boundaries.

Soil Survey Division Staff. 1993. Soil survey manual. Soil Conservation Service. U.S. Department of Agriculture Handbook 18. http://www.nrcs.usda.gov/wps/portal/ nrcs/detail/national/soils/?cid=nrcs142p2_054262

Soil Survey Staff. 1999. Soil taxonomy: A basic system of soil classification for making and interpreting soil surveys. 2nd edition. Natural Resources Conservation Service, U.S. Department of Agriculture Handbook 436. http://www.nrcs.usda.gov/wps/portal/nrcs/detail/national/soils/?cid=nrcs142p2_053577

Soil Survey Staff. 2010. Keys to soil taxonomy. 11th edition. U.S. Department of Agriculture, Natural Resources Conservation Service. http://www.nrcs.usda.gov/wps/portal/nrcs/detail/national/soils/?cid=nrcs142p2 053580

Tiner, R.W., Jr. 1985. Wetlands of Delaware. U.S. Fish and Wildlife Service and Delaware Department of Natural Resources and Environmental Control, Wetlands Section.

United States Army Corps of Engineers, Environmental Laboratory. 1987. Corps of Engineers wetlands delineation manual. Waterways Experiment Station Technical Report Y-87-1.

United States Department of Agriculture, Natural Resources Conservation Service. National forestry manual. http://www.nrcs.usda.gov/wps/portal/nrcs/detail/soils/ home/?cid=nrcs142p2 053374

United States Department of Agriculture, Natural Resources Conservation Service. National range and pasture handbook. http://www.nrcs.usda.gov/wps/portal/nrcs/ detail/national/landuse/rangepasture/?cid=stelprdb1043084

United States Department of Agriculture, Natural Resources Conservation Service. National soil survey handbook, title 430-VI. http://www.nrcs.usda.gov/wps/portal/ nrcs/detail/soils/scientists/?cid=nrcs142p2_054242

United States Department of Agriculture, Natural Resources Conservation Service. 2006. Land resource regions and major land resource areas of the United States, the Caribbean, and the Pacific Basin. U.S. Department of Agriculture Handbook 296. http://www.nrcs.usda.gov/wps/portal/nrcs/detail/national/soils/? cid=nrcs142p2_053624

United States Department of Agriculture, Soil Conservation Service. 1961. Land capability classification. U.S. Department of Agriculture Handbook 210. http://www.nrcs.usda.gov/Internet/FSE_DOCUMENTS/nrcs142p2_052290.pdf

Recharge and Transition Zone Exception Request Form

Texas Commission on Environmental Quality 30 TAC §213.9 Effective June 1, 1999

To ensure that the application is administratively complete, confirm that all fields in the form are complete, verify that all requested information is provided, consistently reference the same site and contact person in all forms in the application, and ensure forms are signed by the appropriate party.

Note: Including all the information requested in the form and attachments contributes to more streamlined technical reviews.

Signature

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. This **Recharge and Transition Zone Exception Request Form** is hereby submitted for TCEQ review and executive director approval. The request was prepared by:

Print Name of Customer/Agent: <u>TOM ASUQUO</u> Date: <u>OS IST</u> 2023 Signature of Customer/Agent:

Regulated Entity Name: ROUND ROCK CHRISTIAN ACADEMY

Exception Request

- 1. Attachment A Nature of Exception. A narrative description of the nature of each exception requested is attached. All provisions of 30 TAC §213 Subchapter A for which an exception is being requested have been identified in the description.
- 2. Attachment B Documentation of Equivalent Water Quality Protection. Documentation demonstrating equivalent water quality protection for the Edwards Aquifer is attached.

Administrative Information

- 3. Submit one (1) original and one (1) copy of the application, plus additional copies as needed for each affected incorporated city, groundwater conservation district, and county in which the project will be located. The TCEQ will distribute the additional copies to these jurisdictions. The copies must be submitted to the appropriate regional office.
- 4. The applicant understands that no exception will be granted for a prohibited activity in Chapter 213.
- 5. The applicant understands that prior approval under this section must be obtained from the executive director for the exception to be authorized.

ι

RECHARGE AND TRANSITION ZONE EXCEPTION REQUEST

Attachments to form TCEQ-0628

ATTACHMENT A - NATURE OF EXCEPTION

This exception request is for the construction of a 2065-sf classroom addition to the existing classroom building which was included as part of the modification with the EAPP ID number 11001467. The project site is currently developed with an existing shared partial sedimentation and filtration pond located on site

The aforementioned permanent BMP was originally permitted under the Round Rock Retirement Residences under the EAPP 1D: 11-05021501. A modification was done to this original WPAP to include additional impervious cover and BMP under EAPP ID: 11-06060101. This plan was further modified under the EAPP ID number 11001467 for the construction of 8.73 acres of Round Rock Christian Academy (including two classroom buildings, a gymnasium, and an auditorium with associated driveways, sidewalks, drainage and utility infrastructure). Impervious cover for this proposed development (gymnasium) was accounted for in the previous WPAP Mod. The existing partial sed-fil pond that shall be utilized for this development has an existing water quality volume of 42,984 c.f. The Water Quality volume required to account for all contributing drainage areas for this shared pond is 22,975 c.f. It can be demonstrated that

ATTACHMENT B - EQUIVALENT WATER QUALITY PROTECTION

there is adequate capacity within the said water quality pond.

The existing shared partial sedimentation and filtration pond shall provide water quality for this project. This pond has a water quality volume of **42,984 c.f.** and a required WQ volume of **22,975 c.f.**

Temporary Stormwater Section

Texas Commission on Environmental Quality

for Regulated Activities on the Edwards Aquifer Recharge Zone and Relating to 30 TAC §213.5(b)(4)(A), (B), (D)(I) and (G); Effective June 1, 1999

To ensure that the application is administratively complete, confirm that all fields in the form are complete, verify that all requested information is provided, consistently reference the same site and contact person in all forms in the application, and ensure forms are signed by the appropriate party.

Note: Including all the information requested in the form and attachments contributes to more streamlined technical reviews.

Signature

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. This **Temporary Stormwater Section** is hereby submitted for TCEQ review and executive director approval. The application was prepared by:

Print Name of Customer/Agent: TOM ASUQUO

Date: 05 15 2028

Signature of Customer/Agent:

ellet

Regulated Entity Name: ROUND ROCK CHRISTIAN ACADEMY

Project Information

Potential Sources of Contamination

Examples: Fuel storage and use, chemical storage and use, use of asphaltic products, construction vehicles tracking onto public roads, and existing solid waste.

1. Fuels for construction equipment and hazardous substances which will be used during construction:

The following fuels and/or hazardous substances will be stored on the site: _____

These fuels and/or hazardous substances will be stored in:

Aboveground storage tanks with a cumulative storage capacity of less than 250 gallons will be stored on the site for less than one (1) year.

Aboveground storage tanks with a cumulative storage capacity between 250 gallons and 499 gallons will be stored on the site for less than one (1) year.
 Aboveground storage tanks with a cumulative storage capacity of 500 gallons or more will be stored on the site. An Aboveground Storage Tank Facility Plan application must be submitted to the appropriate regional office of the TCEQ prior to moving the tanks onto the project.

Fuels and hazardous substances will not be stored on the site.

- 2. X Attachment A Spill Response Actions. A site specific description of the measures to be taken to contain any spill of hydrocarbons or hazardous substances is attached.
- 3. X Temporary aboveground storage tank systems of 250 gallons or more cumulative storage capacity must be located a minimum horizontal distance of 150 feet from any domestic, industrial, irrigation, or public water supply well, or other sensitive feature.
- 4. Attachment B Potential Sources of Contamination. A description of any activities or processes which may be a potential source of contamination affecting surface water quality is attached.

Sequence of Construction

5. Attachment C - Sequence of Major Activities. A description of the sequence of major activities which will disturb soils for major portions of the site (grubbing, excavation, grading, utilities, and infrastructure installation) is attached.

For each activity described, an estimate (in acres) of the total area of the site to be disturbed by each activity is given.

For each activity described, include a description of appropriate temporary control measures and the general timing (or sequence) during the construction process that the measures will be implemented.

6. Name the receiving water(s) at or near the site which will be disturbed or which will receive discharges from disturbed areas of the project: <u>N/A</u>

Temporary Best Management Practices (TBMPs)

Erosion control examples: tree protection, interceptor swales, level spreaders, outlet stabilization, blankets or matting, mulch, and sod. Sediment control examples: stabilized construction exit, silt fence, filter dikes, rock berms, buffer strips, sediment traps, and sediment basins. Please refer to the Technical Guidance Manual for guidelines and specifications. All structural BMPs must be shown on the site plan.

7. X Attachment D – Temporary Best Management Practices and Measures. TBMPs and measures will prevent pollution of surface water, groundwater, and stormwater. The construction-phase BMPs for erosion and sediment controls have been designed to retain sediment on site to the extent practicable. The following information is attached:

		 A description of how BMPs and measures will prevent pollution of surface water, groundwater or stormwater that originates upgradient from the site and flows across the site. A description of how BMPs and measures will prevent pollution of surface water or groundwater that originates on-site or flows off site, including pollution caused by
		 contaminated stormwater runoff from the site. A description of how BMPs and measures will prevent pollutants from entering surface streams, sensitive features, or the aquifer. A description of how, to the maximum extent practicable, BMPs and measures will maintain flow to naturally-occurring sensitive features identified in either the geologic assessment, TCEQ inspections, or during excavation, blasting, or construction.
8.	\boxtimes	The temporary sealing of a naturally-occurring sensitive feature which accepts recharge to the Edwards Aquifer as a temporary pollution abatement measure during active construction should be avoided.
		 Attachment E - Request to Temporarily Seal a Feature. A request to temporarily seal a feature is attached. The request includes justification as to why no reasonable and practicable alternative exists for each feature. There will be no temporary sealing of naturally-occurring sensitive features on the site.
9.		Attachment F - Structural Practices. A description of the structural practices that will be used to divert flows away from exposed soils, to store flows, or to otherwise limit runoff discharge of pollutants from exposed areas of the site is attached. Placement of structural practices in floodplains has been avoided.
10.	\boxtimes	Attachment G - Drainage Area Map. A drainage area map supporting the following requirements is attached:
		 For areas that will have more than 10 acres within a common drainage area disturbed at one time, a sediment basin will be provided. For areas that will have more than 10 acres within a common drainage area disturbed at one time, a smaller sediment basin and/or sediment trap(s) will be used.
		 For areas that will have more than 10 acres within a common drainage area disturbed at one time, a sediment basin or other equivalent controls are not attainable, but other TBMPs and measures will be used in combination to protect down slope and side slope boundaries of the construction area. There are no areas greater than 10 acres within a common drainage area that will be
		disturbed at one time. A smaller sediment basin and/or sediment trap(s) will be used in combination with other erosion and sediment controls within each disturbed drainage area.

There are no areas greater than 10 acres within a common drainage area that will be disturbed at one time. Erosion and sediment controls other than sediment basins or sediment traps within each disturbed drainage area will be used.

11. Attachment H - Temporary Sediment Pond(s) Plans and Calculations. Temporary sediment pond or basin construction plans and design calculations for a proposed temporary BMP or measure have been prepared by or under the direct supervision of a Texas Licensed Professional Engineer. All construction plans and design information must be signed, sealed, and dated by the Texas Licensed Professional Engineer. Construction plans for the proposed temporary BMPs and measures are attached.

🛛 N/A

- 12. Attachment I Inspection and Maintenance for BMPs. A plan for the inspection of each temporary BMP(s) and measure(s) and for their timely maintenance, repairs, and, if necessary, retrofit is attached. A description of the documentation procedures, recordkeeping practices, and inspection frequency are included in the plan and are specific to the site and/or BMP.
- 13. All control measures must be properly selected, installed, and maintained in accordance with the manufacturer's specifications and good engineering practices. If periodic inspections by the applicant or the executive director, or other information indicate a control has been used inappropriately, or incorrectly, the applicant must replace or modify the control for site situations.
- 14. If sediment escapes the construction site, off-site accumulations of sediment must be removed at a frequency sufficient to minimize offsite impacts to water quality (e.g., fugitive sediment in street being washed into surface streams or sensitive features by the next rain).
- 15. Sediment must be removed from sediment traps or sedimentation ponds not later than when design capacity has been reduced by 50%. A permanent stake will be provided that can indicate when the sediment occupies 50% of the basin volume.
- 16. Litter, construction debris, and construction chemicals exposed to stormwater shall be prevented from becoming a pollutant source for stormwater discharges (e.g., screening outfalls, picked up daily).

Soil Stabilization Practices

Examples: establishment of temporary vegetation, establishment of permanent vegetation, mulching, geotextiles, sod stabilization, vegetative buffer strips, protection of trees, or preservation of mature vegetation.

17. Attachment J - Schedule of Interim and Permanent Soil Stabilization Practices. A schedule of the interim and permanent soil stabilization practices for the site is attached.
- 18. Records must be kept at the site of the dates when major grading activities occur, the dates when construction activities temporarily or permanently cease on a portion of the site, and the dates when stabilization measures are initiated.
- 19. X Stabilization practices must be initiated as soon as practicable where construction activities have temporarily or permanently ceased.

Administrative Information

- 20. All structural controls will be inspected and maintained according to the submitted and approved operation and maintenance plan for the project.
- 21. X If any geologic or manmade features, such as caves, faults, sinkholes, etc., are discovered, all regulated activities near the feature will be immediately suspended. The appropriate TCEQ Regional Office shall be immediately notified. Regulated activities must cease and not continue until the TCEQ has reviewed and approved the methods proposed to protect the aquifer from any adverse impacts.
- 22. Silt fences, diversion berms, and other temporary erosion and sediment controls will be constructed and maintained as appropriate to prevent pollutants from entering sensitive features discovered during construction.

TEMPORARY STORWATER SECTION

Attachments to form TCEQ-0602

ATTACHMENT A

There are several factors that could affect surface and ground water quality. During construction, fuels and hazardous substances could spill. These spills shall be contained on-site and immediately cleaned up and properly discarded. Any spills or discharges of oil, petroleum products and used oil onto land having a volume greater than as included in <u>https://www.tceq.texas.gov/response/spills/spill_rg.html</u>, shall be reported immediately to TCEQ at (512) 339-2929 or the State Emergency Response Center at 1-800-832-8224. There are no significant factors proposed which could affect surface and ground water quality relating to the permanent use of the facility.

ATTACHMENT B

Potential Sources of Contamination:

- 1. Soil disturbance during construction.
- 2. Hydrocarbon-based fluids from Construction Equipment.
- 3. Landscaping Fertilizer and Pesticides.

ATTACHMENT C

Sequence of major activities for each phase is as follows:

- 1. The installation of Erosion/Sedimentation Controls –0.01 Ac. Disturbed
- 2. Clearing, grubbing, and removal of topsoil from entire site 0.05 Ac. Disturbed
 - Temporary control measures to be used include tree protection fencing, silt fences and filter dykes
- 3. Rough grading and building pad excavation 0.05 Ac. Disturbed
 - Temporary control measures to be used include tree protection fencing, silt fences and inlet protection
- 4. Excavating for utilities 0 Ac. Disturbed
 - Temporary control measures to be used include tree protection fencing, silt fences and inlet protection.
- 5. Finish grading and landscaping 0.05 Ac. Disturbed
 - Temporary control measures to be used include tree protection fencing, silt fences and inlet protection.

ATTACHMENT D

The Temporary Best Management Practices (TBMP) for this project will consist of:

- 1. A stabilized construction entrance.
- 2. Silt fencing around down gradient boundary of site.
- 3. Filter dykes
- 4. Inlet Protection to protect all existing and proposed inlets.
- 5. Concrete washout

All TBMP's will be in place prior to any regulated activities commencing. The stabilized construction entrance will remove excess spoils from construction vehicles leaving the site. The silt fencing will collect silt runoff and debris during construction activities.

TEMPORARY STORWATER SECTION

Attachments to form TCEQ-0602

These controls will be maintained during construction and will remain until after all construction activities are complete and permanent re-vegetation is established.

ATTACHMENT E

There will be no temporary sealing of naturally-occurring sensitive features on the site.

ATTACHMENT F

Due to the limited area of the site, the silt fence will provide control to retain any runoff from the exposed site.

ATTACHMENT G

Refer to the drawings, sheet EDA and PDA.

ATTACHMENT H

N/A

ATTACHMENT I

The contractor is required to inspect all of the erosion and sediment controls and fences at weekly intervals and after significant rainfall events to ensure that they are functioning properly. The person(s) responsible for maintenance of controls and fences shall immediately make any necessary repairs to damaged areas. Silt accumulation at controls must be removed when the depth reaches six (6) inches. Records described in the SWPPP must be retained on site for 5 years beyond the date of the cover letter notifying the facility of coverage under a storm water permit, and shall be made available to the state or federal compliance inspection officer upon request. Additionally, employee training records and waste and recycling receipts or vouchers shall also be maintained.

ATTACHMENT J

Schedule of Interim Soil Stabilization Practices:

- 1. Erosion and sediment control measures including perimeter sediment controls must be in place before vegetation is disturbed and must remain in place and be maintained and repaired.
- 2. Temporary stabilization or covering of soil stockpiles and protection of stockpile located away from construction activity must be maintained
- 3. Should construction activities cease for fifteen (15) days or more on any significant portion of the construction site, temporary stabilization is required for that portion of the site to prevent soil and wind erosion until work resumes on that portion of the site.
- 4. Should all construction activities cease for thirty days or more, the entire site must be temporarily stabilized using vegetation or a heavy mulch layer, temporary seeding or other method.
- 5. Bare soils should be seeded or otherwise stabilized within 14 calendar days after final grading or where construction activity has temporarily ceased for more than 21 days.

TEMPORARY STORWATER SECTION

Attachments to form TCEQ-0602

Schedule of Permanent Soil Stabilization Practices:

- 1. Stabilized any unpaved area that is final grade or remain unpaved for the next two weeks. Permanent stabilization may consist of sodding, seeding, or mulching that must be maintained to prevent erosion from the site until re-vegetation has achieved 70% coverage
- 2. Once construction is complete, remove all the pollution prevention measures that were temporary.

Agent Authorization Form For Required Signature Edwards Aquifer Protection Program Relating to 30 TAC Chapter 213 Effective June 1, 1999 REBECCA BLAUSER Print Name HEAD OF SCHOOL Title - Owner/President/Other of ROUND ROCK CHRISTIAN ACADEMY Corporation/Partnership/Entity Name have authorized TERRY HAGOOD Print Name of Agent/Engineer of HAGOOD ENGINEERING ASSOCIATES, INC. Print Name of Firm

to represent and act on the behalf of the above named Corporation, Partnership, or Entity for the purpose of preparing and submitting this plan application to the Texas Commission on Environmental Quality (TCEQ) for the review and approval consideration of regulated activities.

I also understand that:

- 1. The applicant is responsible for compliance with 30 Texas Administrative Code Chapter 213 and any condition of the TCEQ's approval letter. The TCEQ is authorized to assess administrative penalties of up to \$10,000 per day per violation.
- 2. For those submitting an application who are not the property owner, but who have the right to control and possess the property, additional authorization is required from the owner.
- 3. Application fees are due and payable at the time the application is submitted. The application fee must be sent to the TCEQ cashier or to the appropriate regional office. The application will not be considered until the correct fee is received by the commission.
- 4. A notarized copy of the Agent Authorization Form must be provided for the person preparing the application, and this form must accompany the completed application.
- 5. No person shall commence any regulated activity on the Edwards Aquifer Recharge Zone, Contributing Zone or Transition Zone until the appropriate application for the activity has been filed with and approved by the Executive Director.

,

· · . *

SIGNATURE PAGE:

Date

THE STATE OF TEXAS §

County of WILLIAMSON §

BEFORE ME, the undersigned authority, on this day personally appeared <u>REBECCA BLAUSER</u> known to me to be the person whose name is subscribed to the foregoing instrument, and acknowledged to me that (s)he executed same for the purpose and consideration therein expressed.

GIVEN under my hand and seal of office on this 11 day of May , 2023

Typed br Printed Name of Notar

CYNTHIA J. POTTS My Notary ID # 128052943 Expires November 13, 2025

MY COMMISSION EXPIRES: November 13, 2025



TCEQ Core Data Form



For detailed instructions regarding completion of this form, please read the Core Data Form Instructions or call 512-239-5175.

SECTION I: General Information										
1. Reason for Submission (If other is checked please describe in space provided)										
New Permit, Registration or Authorization (Core Data Form should be submitted with the program application)										
Renewa	Renewal (Core Data Form should be submitted with the renewal form)									
2. Attachmer	nts C	Describe Any Attachments:	(ex. Title V Aj	pplicatio	n, Waste	Transp	orter Applica	ation, etc.)		
<u>⊠</u> Yes		EXCEPTION REQUES	ST							
3. Customer Reference Number (<i>if issued</i>) Follow this link to search for CN or RN numbers in										
CN 605631290 Central Registry** RN 110717196										
SECTION	SECTION II: Customer Information									
5. Effective I	5. Effective Date for Customer Information Updates (mm/dd/yyyy) 2/28/2019									
6. Customer	Role (Propor	sed or Actual) – as it relates to the	Regulated E	<u>Entity</u> list	ed on thi	s form. I	Please chec	k only <u>one</u> of t	he following:	
Owner		Operator	⊠ 0	wner &	Operate	or				
	nal Licensee	e Responsible Party		oluntary	/ Cleanu	ıp Appli	cant	Other:		
7. General C	ustomer Inf	ormation								
New Cust	tomer	Ur	pdate to Cu	stomer	Informat	tion		Change in	Regulated Er	ntity Ownership
Change in	Legal Name	e (Verifiable with the Texas Sec	cretary of St	ate)		() (\boxtimes	No Change)** 	
	nge" and Se	ection i is complete, skip to S	ection III –	Regula	atea En	tity into	ormation.			
8. Type of Ci	ustomer:	Corporation	Individual			Sole Proprietorship- D.B.A				
City Gove	ernment	County Government	Federal Government		nent	State Government				
Other Go	vernment	General Partnership	Limited Partnership			Othe	NON	PROFIT		
9. Customer	Legal Name	e (If an individual, print last name i	first: ex: Doe,	John)	<u>lf ne</u> bek	ew Cust <u>ow</u>	omer, entei	r previous Cu	<u>stomer</u>	End Date:
ROUND I	ROCK CI	HRISTIAN ACADEM	Y							
	800 WE	ST WOOD DR								-
10. Mailing										
Address:	City I	ROUND ROCK	State	ТХ	Z		78681		ZIP+4	
11 Country	Mailing Info	rmation (if outside (184)	1		12 F-N	Iail ∆d	dress <i>lif</i> an	nlicable)	1	
Thoundy	indining into		· · · · ·		l de , bes l l	nun ru	ureee (<i>in up</i> ,	pileubicy		
13. Telephor	13. Telephone Number 14. Extension or Code 15. Fax Number (if applicable)									
(512)25	5-4491						() -		
16. Federal 1	i ax ID (9 digits)) 17. TX State Franchise T	ax ID (11 digi	is} '	18. DUN	IS Num	ber(if applica	b/e) 19. TX	SOS Filing	Number (if applicable)
27-392264 32042999790 801341395										
20. Number of Employees 21. Independently Owned and Operated?										
□ 0-20 🖄 21-100 □ 101-250 □ 251-500 □ 501 and higher										
SECTION	SECTION III: Regulated Entity Information									
22. General I	Regulated E	intity Information (If 'New Reg	gulated Enti	ty" is se	lected b	elow th	is form sho	ould be acco	mpanied by a	a permit application)
L New Reg	New Regulated Entity Update to Regulated Entity Name Dupdate to Regulated Entity Information No Change** (See below)									

**If "NO CHANGE" is checked and Section I is complete, skip to Section IV, Preparer Information.

23. Regulated Entity Name (name of the site where the regulated action is taking place)

ROUND ROCK CHRISTIAN ACADEMY

24. Street Address	800	800 WESTWOOD DRIVE							
of the Regulated									
(No P.O. Boxes)	City	ROUND ROCK	State	TX	ZIP	78681		ZIP + 4	
	301-	A N. LAKE CREE	K DRIVE						
25. Mailing Address:			1	1		1			
	City	ROUND ROCK	State	TX	ZIP	78681		ZIP + 4	
26. E-Mail Address:	BE	CKYBLAUSER@	RRCA-TX	K.ORG		12			
27. Telephone Numbe	r		28. Extensio	on or Code	29.	Fax Numbe	er (if applicable)		
(512) 255-4491					() -			
30. Primary SIC Code	(4 digits)	31. Secondary SIC C	ode (4 digits)	32. Primary (5 or 6 digits)	NAICS	Code	33. Second (5 or 6 digits)	dary NAICS	Code
8299				611110					
34. What is the Primary Business of this entity? (Please do not repeat the SIC or NAICS description.)									
SCHOOL									
Q	uestion	s 34 – 37 address geogr	aphic locatic	on. Please refe	er to the	e instructior	ns for applic	ability.	
25 Decembrishes to	This	site is a flag lot loc	ated behin	d the Centr	al Baj	otist Chur	ch situate	d at 301 1	J. Lake
Physical Location:	Cree	k Drive. The lot is s	situated at	the termina	tion c	of Westwo	ood Drive	approxin	nately

168LF from the intersection of Westwood Drive and Bonwood Drive	
	168LF from the intersection of Westwood Drive and Bonwood Drive

36. Nearest City				County		State			Nea	rest ZIP Code
ROUND ROCK			WILLIAMSON		ТХ			78681		
37. Latitude (N) In Decimal: 30.509026		5	38. Longitude (W) In Decimal:		-97.692354		54	
Degrees	Minutes		Second	S	Degrees		Minutes			Seconds

39. TCEQ Programs and ID Numbers Check all Programs and write in the permits/registration numbers that will be affected by the updates submitted on this form or the updates may not be made. If your Program is not listed, check other and write it in. See the Core Data Form instructions for additional guidance.

Dam Safety	Districts	Edwards Aquifer	Industrial Hazardous Waste	Municipal Solid Waste
		11-05021501;		
		06060601		
New Source Review – Air	OSSF OSSF	Petroleum Storage Tank	PWS	Sludge
Stormwater	Title V – Air	Tires	Used Oil	Utilities
U Voluntary Cleanup	Waste Water	Wastewater Agriculture	Water Rights	Other:

SECTION IV: Preparer Information

40. Name: RAQUEL SAENZ					PROJECT ASSISTANT
42. Telephone Number 4		43. Ext./Code	44. Fax Number	45. E-Mail	Address
(512)244	-1546		() -	RAQUE	LR@HEAENG.CO,

SECTION V: Authorized Signature

46. By my signature below, I certify, to the best of my knowledge, that the information provided in this form is true and complete, and that I have signature authority to submit this form on behalf of the entity specified in Section II, Field 9 and/or as required for the updates to the ID numbers identified in field 39.

(See the Core Data Form instructions for more information on who should sign this form.)

Company:	HAGOOD ENGINEERING ASSOC.	Job Title:	E.I.T		
Name(In Print) :	TOM ASUQUO			Phone:	(512)244-1546
Signature:	Smano			Date:	05 15 2023

Application Fee Form

Texas Commission on Environmental Quality Name of Proposed Regulated Entity: <u>Round Rock Christian Academy</u> Regulated Entity Location: 800 Westwood Drive Round Rock, TX 78681						
Regulated Entity Location: 800 Westwood Drive Round Rock, 1X 78681						
Name of Customer: Round Rock Christian Academy						
Contact Person: <u>Repecca Blauser</u> Phone: <u>512.2</u>	55.4491					
Customer Reference Number (if issued):CN 605631290						
Regulated Entity Reference Number (if issued):RN <u>110/1/196</u>						
Austin Regional Office (3373)	Ç (EL) (영향 12)(전					
Hays Travis	W	illiamson				
San Antonio Regional Office (3362)						
Bexar Medina		/alde				
Application food must be paid by check, contributed shock, or manage order, noveble to the Taylor						
Commission on Environmental Quality Your canceled check will	l sorvo as vou	r receipt This				
form must be submitted with your fee payment. This payment is	s boing subm	itted to:				
	s being subin	itteu to.				
Austin Regional Office	nio Regional C	Office				
Mailed to: TCEQ - Cashier	Delivery to: 1	FCEQ - Cashier				
Revenues Section 12100 Par	Revenues Section 12100 Park 35 Circle					
Mail Code 214 Building A	, 3rd Floor					
P.O. Box 13088 Austin, TX 78753						
P.O. Box 13088 Austin, TX	78753					
P.O. Box 13088Austin, TXAustin, TX 78711-3088(512)239-	(78753 0357					
Austin, TX Austin, TX 78711-3088 (512)239- Site Location (Check All That Apply):	(78753 0357					
P.O. Box 13088 Austin, TX Austin, TX 78711-3088 (512)239- Site Location (Check All That Apply): Recharge Zone Contributing Zone	(78753 0357	tion Zone				
P.O. Box 13088 Austin, TX Austin, TX 78711-3088 (512)239- Site Location (Check All That Apply): Recharge Zone Contributing Zone Type of Plan	(78753 0357	tion Zone Fee Due				
P.O. Box 13088 Austin, TX Austin, TX 78711-3088 (512)239- Site Location (Check All That Apply): Recharge Zone Contributing Zone Type of Plan Water Pollution Abatement Plan, Contributing Zone	(78753 0357	tion Zone Fee Due				
P.O. Box 13088 Austin, TX Austin, TX 78711-3088 (512)239- Site Location (Check All That Apply): Contributing Zone Image: Contribution Abatement Plan, Contributing Zone Image: Contributing Zone Water Pollution Abatement Plan, Contributing Zone Image: Contributing Zone Plan: One Single Family Residential Dwelling Image: Contributing Zone	(78753 0357 Transi <i>Size</i> Acres	tion Zone Fee Due \$				
P.O. Box 13088 Austin, TX Austin, TX 78711-3088 (512)239- Site Location (Check All That Apply): □ Contributing Zone ☑ Recharge Zone □ Contributing Zone Type of Plan Water Pollution Abatement Plan, Contributing Zone Plan: One Single Family Residential Dwelling Water Pollution Abatement Plan, Contributing Zone	(78753 0357 Transi Size Acres	tion Zone Fee Due \$				
P.O. Box 13088 Austin, TX Austin, TX 78711-3088 (512)239- Site Location (Check All That Apply): Contributing Zone Recharge Zone Contributing Zone Water Pollution Abatement Plan, Contributing Zone Plan: One Single Family Residential Dwelling Water Pollution Abatement Plan, Contributing Zone Plan: Multiple Single Family Residential and Parks	(78753 0357 Transi Size Acres Acres	tion Zone Fee Due \$ \$				
P.O. Box 13088 Austin, TX Austin, TX 78711-3088 (512)239- Site Location (Check All That Apply): □ Contributing Zone ☑ Recharge Zone □ Contributing Zone Image: Contributing Zone Water Pollution Abatement Plan, Contributing Zone Plan: One Single Family Residential Dwelling Image: Contributing Zone Water Pollution Abatement Plan, Contributing Zone Plan: Multiple Single Family Residential and Parks Water Pollution Abatement Plan, Contributing Zone Plan: Multiple Single Family Residential and Parks	Transi	tion Zone Fee Due \$ \$				
P.O. Box 13088 Austin, TX Austin, TX 78711-3088 (512)239- Site Location (Check All That Apply): Recharge Zone Contributing Zone Type of Plan Water Pollution Abatement Plan, Contributing Zone Plan: One Single Family Residential Dwelling Water Pollution Abatement Plan, Contributing Zone Plan: Multiple Single Family Residential and Parks Water Pollution Abatement Plan, Contributing Zone Plan: Multiple Single Family Residential and Parks Water Pollution Abatement Plan, Contributing Zone Plan: Non-residential	(78753 0357 Transi Size Acres Acres Acres	tion Zone <i>Fee Due</i> \$ \$				
P.O. Box 13088 Austin, TX Austin, TX 78711-3088 (512)239- Site Location (Check All That Apply): Recharge Zone Contributing Zone Type of Plan Water Pollution Abatement Plan, Contributing Zone Plan: One Single Family Residential Dwelling Water Pollution Abatement Plan, Contributing Zone Plan: Multiple Single Family Residential and Parks Water Pollution Abatement Plan, Contributing Zone Plan: Multiple Single Family Residential and Parks Water Pollution Abatement Plan, Contributing Zone Plan: Multiple Single Family Residential and Parks Water Pollution Abatement Plan, Contributing Zone Plan: Non-residential Sewage Collection System	Transi	tion Zone Fee Due \$ \$ \$ \$				
P.O. Box 13088 Austin, TX Austin, TX 78711-3088 (512)239- Site Location (Check All That Apply): Contributing Zone Recharge Zone Contributing Zone Water Pollution Abatement Plan, Contributing Zone Plan: One Single Family Residential Dwelling Water Pollution Abatement Plan, Contributing Zone Plan: Multiple Single Family Residential and Parks Water Pollution Abatement Plan, Contributing Zone Plan: Multiple Single Family Residential and Parks Water Pollution Abatement Plan, Contributing Zone Plan: Non-residential Sewage Collection System Lift Stations without sewer lines	C 78753 0357 Transi Size Acres Acres Acres L.F. Acres	tion Zone Fee Due \$ \$ \$ \$ \$ \$ \$				
P.O. Box 13088 Austin, TX Austin, TX 78711-3088 (512)239- Site Location (Check All That Apply): (512)239- Recharge Zone Contributing Zone Image: Type of Plan Image: Sone Water Pollution Abatement Plan, Contributing Zone Plan: One Single Family Residential Dwelling Water Pollution Abatement Plan, Contributing Zone Plan: Multiple Single Family Residential and Parks Water Pollution Abatement Plan, Contributing Zone Plan: Multiple Single Family Residential and Parks Water Pollution Abatement Plan, Contributing Zone Plan: Non-residential Sewage Collection System Image: Sone Lift Stations without sewer lines Underground or Aboveground Storage Tank Facility	78753 0357 Transi Size Acres Acres Acres L.F. Acres Tanks	tion Zone Fee Due \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$				
P.O. Box 13088 Austin, TX Austin, TX 78711-3088 (512)239- Site Location (Check All That Apply): (512)239- Recharge Zone Contributing Zone Image: Type of Plan Image: Sone Water Pollution Abatement Plan, Contributing Zone Plan: One Single Family Residential Dwelling Water Pollution Abatement Plan, Contributing Zone Plan: Multiple Single Family Residential and Parks Water Pollution Abatement Plan, Contributing Zone Plan: Multiple Single Family Residential and Parks Water Pollution Abatement Plan, Contributing Zone Plan: Non-residential Sewage Collection System Image: Sone Lift Stations without sewer lines Image: Sone Underground or Aboveground Storage Tank Facility Piping System(s)(only)	78753 0357 Transi Size Acres Acres L.F. Acres L.F. Acres Tanks Each	tion Zone Fee Due \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$				
P.O. Box 13088 Austin, TX Austin, TX 78711-3088 (512)239- Site Location (Check All That Apply): (512)239- Recharge Zone Contributing Zone Image: Type of Plan Image: Sone Water Pollution Abatement Plan, Contributing Zone Plan: One Single Family Residential Dwelling Water Pollution Abatement Plan, Contributing Zone Plan: Multiple Single Family Residential and Parks Water Pollution Abatement Plan, Contributing Zone Plan: Multiple Single Family Residential and Parks Water Pollution Abatement Plan, Contributing Zone Plan: Non-residential Sewage Collection System Image: Sone Lift Stations without sewer lines Underground or Aboveground Storage Tank Facility Piping System(s)(only) Exception	78753 0357 Transi Size Acres Acres L.F. Acres L.F. Acres Tanks Each 1 Each	tion Zone Fee Due \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$				
P.O. Box 13088 Austin, TX Austin, TX 78711-3088 (512)239- Site Location (Check All That Apply): (512)239- Site Location (Check All That Apply): Contributing Zone Recharge Zone Contributing Zone Water Pollution Abatement Plan, Contributing Zone Plan: One Single Family Residential Dwelling Water Pollution Abatement Plan, Contributing Zone Plan: Multiple Single Family Residential and Parks Water Pollution Abatement Plan, Contributing Zone Plan: Nultiple Single Family Residential and Parks Water Pollution Abatement Plan, Contributing Zone Plan: Non-residential Sewage Collection System Lift Stations without sewer lines Underground or Aboveground Storage Tank Facility Piping System(s)(only) Exception Exception Extension of Time Image: State	78753 0357 Transi Size Acres Acres Acres L.F. Acres L.F. Acres Tanks Each 1 Each Each	tion Zone Fee Due \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$				

TCEQ-0574 (Rev. 02-24-15)

Application Fee Schedule

Texas Commission on Environmental Quality

Edwards Aquifer Protection Program 30 TAC Chapter 213 (effective 05/01/2008)

Water Pollution Abatement Plans and Modifications

Contributing Zone Plans and Modifications

Project	Project Area in Acres	Fee
One Single Family Residential Dwelling	< 5	\$650
Multiple Single Family Residential and Parks	< 5	\$1,500
	5 < 10	\$3,000
	10 < 40	\$4,000
	40 < 100	\$6,500
	100 < 500	\$8,000
	≥ 500	\$10,000
Non-residential (Commercial, industrial, institutional,	< 1	\$3,000
multi-family residential, schools, and other sites	1 < 5	\$4,000
where regulated activities will occur)	5 < 10	\$5,000
	10 < 40	\$6,500
	40 < 100	\$8,000
	≥ 100	\$10,000

Organized Sewage Collection Systems and Modifications

	Cost per Linear	Minimum Fee-		
Project	Foot	Maximum Fee		
Sewage Collection Systems	\$0.50	\$650 - \$6,500		

Underground and Aboveground Storage Tank System Facility Plans and Modifications

	Cost per Tank or	Minimum Fee-
Project	Piping System	Maximum Fee
Underground and Aboveground Storage Tank Facility	\$650	\$650 - \$6,500

Exception Requests

Project	Fee
Exception Request	\$500

Extension of Time Requests

Project	Fee
Extension of Time Request	\$150



SITE DEVELOPMENT IMPROVEMENTS SUBMITTED FOR **ROUND ROCK CHRISTIAN ACADEMY ADDITION 800 WESTWOOD DRIVE ROUND ROCK, TEXAS 78665 SDP2205-0006**

BENCHMARKS

TBM #1 - MNS "JPH BENCHMARK" (SEE SP1 NAVD88 (GEOID18) EV = 741.41

TBM #2 - MNS "JPH BENCHMARK" (SEE SP1) ELEV = 747.71

NAVD88 (GEOID18)

LEGAL DESCRIPTION

-OT 1, BLOCK A CENTRAL BAPTIST CHURCH, LOT 1A & 1B, BLOCK "A" SUBDIVISION INST #2016106475

PLAN SUBMITTALS

COMMENTS

1	6/15/2022	ISSUED FOR PRELIMINARY PRICING
2	8/12/2022	ISSUED FOR AGENCY REVIEW
3	11/4/2022	ISSUED FOR PRICING
4	12/12/2022	UPDATE SUBMITTAL TO CITY OF ROUND ROCK
5	12/12/2022	UPDATE SUBMITTAL TO TCEQ
6	1/18/2022	ASAP TO CITY OF ROUND ROCK
7	2/8/2023	ISSUED FOR CONSTRUCTION
8	5/15/2023	UPDATE SUBMITTAL TO TCEQ
9		

OWNER **ROUND ROCK CHRISTIAN ACADEMY**

SURVEYOR JPH LAND SURVEYING INC 1516 E. PALM VALLEY BLVD

NOTES:

NO. DATE

- A PORTION OF THE ABOVE LEGALLY DESCRIBED PROPERTY IS WITHIN THE DESIGNATED .2% ANNUAL CHANCE FLOODPLAIN AREA AS DESIGNATED BY F.E.M.A. FLOOD INSURANCE RATE MAP (FIRM) ON COMMUNITY PANEL NO. 48491C0489F, DATED DECEMBER 19, 2019 FOR THE CITY OF ROUND ROCK, WILLIAMSON COUNTY, TEXAS.
- 2. THIS PROPERTY IS WITHIN THE EDWARDS AQUIFER RECHARGE ZONE.
- 3. SEE SHEET CO0 FOR GENERAL NOTES.
- 4. A PORTION OF THIS TRACT IS ENCROACHED BY THE ULTIMATE 1% ANNUAL CHANCE FLOODPLAIN.

ALL RESPONSIBILITY FOR ENGINEER WHO PREPARE ROUND ROCK MUST RELY ENGINEER.	THE ADEQUACY OF T D THEM. IN ACCEPTIN Y UPON THE ADEQUA	HESE PLANS REMAINS WITH THE NG THESE PLANS, THE CITY OF CY OF THE WORK OF THE DESIGN
STATE OF TEXAS	*	
COUNTY OF WILLIAMSON	★ ★	
I, TERRY R. HAGOOD, DC DRAINAGE IMPROVEMEN COMPLIANCE WITH THE S ORDINANCES AND STOR ROUND ROCK, TEXAS.) HEREBY CERTIFY THA TS DESCRIBED HEREIN SUBDIVISION AND BU M WATER DRAINAGE F	T THE PUBLIC WORKS AND HAVE BEEN DESIGNED IN ILDING REGULATION POLICY ADOPTED BY THE CITY OF
TERRY R. HAGOOD	Im Ritzont	05/15/2023
NONTROLENCE		
ACCEPTED FOR CONSTRUC	TION BY:	
Planning and Developmer City of Round Rock, Texas	nt Services	Date

301-A N. LAKE CREEK DRIVE ROUND ROCK, TEXAS 78681 BECKY BLAUSER (512)796-7386

ARCHITECT **SPENCER-PIERCE ARCHITECTURE** + INTERIORS, INC.

110 N. STONE STREET ROUND ROCK, TEXAS 78664 BO SPENCER, AIA (512) 388-0677

ROUND ROCK, TEXAS 78664 CHRIS HENDERSON, RPLS

ENGINEER HAGOOD ENGINEERING ASSOCIATES, INC.

900 E. MAIN STREET **ROUND ROCK, TEXAS 78664** TERRY R. HAGOOD, P.E. (512) 244-1546

LANDSCAPE ARCHITECT **BLAIR LANDSCAPING**

100 CONGRESS AVE, STE, 2000 AUSTIN, TEXAS 78701 WILL BLAIR, AIA 512-522-8979

	Sha	ot list Table
	JIE	
SHEET NUMBER	SHEET TITLE	SHEET DESCRIPTION
01	CVR	COVER
02	SP	OVERALL SITE PLAN
03	PRK	PARKING PLAN
04	SRV	SURVEY
05	PLAT	PLAT
06	EDA	EXISTING DRAINAGE AREA
07	PDA	DEVELOPED DRAINAGE AREA
08	DA INLETS	INLET DRAINAGE AREA
09	CALC 1	HYDROLOGIC CALCULATIONS
10	CALC 2	WATER QUALITY CALCULATIONS
11	C00	GENERAL NOTES
12	C10A	EROSION AND SEDIMENTATION CONTROL PLAN
13	C10B	EROSION AND SEDIMENTATION CONTROL PLAN
14	C11A	DEMOLITION PLAN
15	C11B	DEMOLITION PLAN
16	C20A	DIMENSION CONTROL PLAN
17	C20B	DIMENSION CONTROL PLAN
18	C30A	PAVING AND STRIPING PLAN
19	C30B	PAVING AND STRIPING PLAN
20	C40A	GRADING PLAN
21	C40B	GRADING PLAN
22	C50A	DRAINAGE PLAN
23	C50B	DRAINAGE PLAN
24	C51	DRAINAGE PROFILE
25	C60A	UTILITY PLAN
26	C60B	UTILITY PLAN
27	C61	UTILITY PROFILE
28	C70	CONSTRUCTION DETAILS
29	C71	EROSION DETAILS
30	C72	UTILITY DETAILS
31	L1	LANDSCAPE PLAN
32	L2	LANDSCAPE CALCULATIONS

SITE PLA	AN PERA	AIT NO.		SDP2205-000)6		
RECORI	DED FIN	IAL PLAT DOC.	NO.	2016106475			
SCS CA	.SE NUA	ABER & DATE		11001468		2019/06/03	
WPAP #	≠ & DAT	E		11001467		2019/06/03	
WPAP E	XCEPTI	ON # & DATE		11003277		2022/12/14	
			IN	NPERVIOUS CO	VER		
STREET,	CURB	and Gutter				N/A	
EX. BUIL						54,397	SF
NEW BL	JILDINC	FOOTPRINT				19,101	SF
EX. PAR	KING, F	RIVATE SIDEWA	ALK			75,126	SF
NEW PA	RKING	, PRIVATE SIDEV	VALK			19,188	SF
EX. TOT	AL					129,523	SF
NEW TO	DTAL					38,289	SF
	area o	f disturbanc	E (LOC)			108,040	SF
				REVISI	ONS		
	NO.	DATE		DESCRIP	TION		APPROVED BY
	1						
	2						
	3						
	5						
		i	900 Bou	E. Main Street		JOB NO:	21-025
			Pho Fax	ne (512) 244-1546 (512) 244-1010		DRAWN BY:	TA
			TBP	v.hea.eng.pro E Registration No. F-127	709	CHECKED BY:	TRH
			JOE	3 NO. 21-025 © 2022	2 HEA, Inc.	P.I.C.:	TRH
		HAGO	OD			FILE NO:	21-025 CVR
		nvineeki nv aa	rv441 23			DATE:	05/15/2023
u diq.						SHEET:	01 OF 32







TRM-1 MNS BENCHMARK" DA 10 741.41' IRM **= = = = =** EX. ASPHALT EX. DRAINAGE FEATURE CARE AND AND AND TANK TO BUILDING EX. PORTABLE BLDG. TEX: PORTABLE BLD Eb Li li d X. PQRTABLE BL X. PORTABLE BLDA _p Lì Lì []] [] **[**] **[**] _____ <u>e</u> EX. DA 2.86 AC. **===**== EX. DUMPSTER ╴╧╧╴╵╴╵╴╵╴┙╴╴╴╴╴╴╴╴╴╴╴╴╴ 100' SHEET FLOW 390' SHALLOW CONCENTRATED FLOW ____. 735 🗸





		0 50 SCALE: 1" = 50'	ALL RESPONSIBILITY FOR THE ADEQUACY OF THESE PLANS REMAINS WITH THE ENGINEER WHO PREPARED THEM. IN REVIEWING THESE PLANS, THE CITY MUST RELY UPON THE ADEQUANCE OF THE WORK OF THE DESIGN ENGINEER.	DATE: 05/15/2023 REV: 1 - ADD BUILDING EXTENSION, REMOVE FIRELANE HAMMERHEAD	DRW. SPai CHK. SPai
		NOTE: 1. REFER TO RRCA PROJECT WITH BREAKDOWN OF EX DA1	BYOE E. Main Street Round Rock, TX 78664 Phone (512) 244-1546 Fax (512) 244-1010 www.heaeng.com TBFE Registration No. F-12709 Import Provided Street Import Provided Street	SITE DEVELOPMENT IMPROVEMENTS ROUND ROCK CHRISTIAN ACADEMY 800 WESTWOOD DRIVE	ROUND ROCK, TEXAS 78681
, [O IRON ROD FOUND/SET □ CONCRETE MONUMENT FOUND/SET △ NAIL FOUND/SET PIPE FOUND ⑤ STORMWATER MANHOLE (DRAWN TO SCALE) ● JUNCTION BOX (DRAWN TO SCALE)	— — — UGT — — — — — — WW — — — — — — FM — — — — — — FOC — — — — — — GAS — — —	EXISTING UNDERGROUND TELEPHONE LINE EXISTING WATER LINE (SIZE VARIES) EXISTING WASTEWATER LINE (SIZE VARIES) EXISTING FORCE MAIN (SIZE VARIES) EXISTING FIBER OPTIC LINE EXISTING GAS LINE (SIZE VARIES) BENCHMARK LOCATION		
× _{EX.WV} × _{EX.ICV} ====================================	GRATE INLET (DRAWN TO SCALE) GRATE INLET (DRAWN TO SCALE) VASTEWATER MANHOLE (DRAWN TO SCALE) VASTEWATER CLEANOUT GAS TEST STATION GAS METER ELECTRIC METER ELECTRIC METER ELECTRIC METER ELECTRIC METER ELECPHONE MANHOLE FIRE HYDRANT GATE VALVE IRRIGATION CONTROL VALVE IRRIGATION CONTROL VALVE IRRIGATION CONTOURS EXISTING CHAIN LINK FENCE EXISTING WOOD FENCE EXISTING WOOD FENCE EXISTING WOOD FENCE EXISTING ASPHALT EXISTING OVERHEAD ELECTRIC LINE EXISTING OVERHEAD TELEPHONE LINE		EXISTING TREE TO REMAIN (SIZE VARIES) EXISTING TREE TO BE REMOVED (SIZE VARIES) MONARCH/HERITAGE TREE (SIZE VARIES) PARKING COUNT PARCEL LINES HANDICAP ACCESS LINES CONCRETE PAVING CONCRETE PAVING CONCRETE SIDEWALK CONCRETE SIDEWALK CONCRETE WASHOUT STABILIZED CONSTRUCTION ENTRANCE SILT FENCE ROCK BERM INLET PROTECTION TREE PROTECTION MULCH SOCK LIMITS OF CONSTRUCTION	Spencer - Pierce Architecture + Interiors, Inc. 110 N. STONE Round Rock, Texas 78664	Phone: (512) 388-0677 Fax: (512) 388-0752 Email: spai@sp-ai.com Web Site: www.sp-ai.com
				Copyright SHEET	

07 of 32 SDP2205-0006



May 15,2023-1:28pm Z:\HEA\HEA Projects Projects 21-000\21-025 Round Rock Christian Acadamy Addition\CAD Files\Civil\SD\21-025 PDA 2.dwg

			DRW. SPai CHK. SPai
		Image: Second	UUD UNIVE , TEXAS 78681
			ROCK
			ND F
		■ ■	vo SOU
Och METER WOUNDINGEROUT REEDERVANES DIGETION OF BIONAL LIGHT POLE WOUNDINGE WOUNDINGE UNIT POLE WECKLINIS UNIT POLE WEI POLECION UNIT POLE WEI POLECION UNIT POLE UNIT POLE UNIT POLE UNIT POLE UNIT POLE		GAS NETS WOWNCHHERKGETHE BUE WARES BECTRE WATE (2) BECTRE WATE (2) WARNE COUNT (2) BERNE WARDE (2)	ц <u>т</u>
INSTRUME INSTRUMENT			
NAME DEFINITION PACE: LINES NULL PROVE PROCESSINGS OWNER MERCE PROVIDER PANING OWNER PANIN PROVIDER PANING OWNER PANIN PROVIDER PANING OWNER PANING PROVIDER PANING INTER FLOOW	NAMEL CHI TALL: PARCE, LINES ULL PARE HC HANDORA ROCESS LINES INE PROVINGE AND CAP ROCESS LINES OBJERT ON CONTROL MADE: CONCRET: SUBWAIK OBJERT ON CONTROL MADE: SUBJERCE OBJERT ON MODE BALE CONCRET: SUBWAIK OBJERT ON MODE BALE SUBJERCE OBJERT ON MODE BALE JULE # SOFETION DISTING MARKED LECTIC LINE JULE # SOFETION DINT PONTOR OF AND LECTIC LINE	North Upting North Upting North Upting North Upting North Upting High Holdson North Upting North Upting North Upting North Upting High Holdson North Upting North Upting North Upting North Upting High Holdson North Upting North Upting North Upting North Upting High Holdson North Upting North Upting North Upting North Upting High Holdson North Upting North Upting North Upting North Upting High Holdson North Upting North Upting North Upting North Upting High Holdson North Upting North Upting North Upting North Upting High Holdson North Upting North Upting North Upting North Upting High Holdson North Upting North Upting North Upting North Upting North Upting High Holdson North Upting North Upting North Upting North Upting North Upting North Upting High Holdson North Upting North Upting North Upting North Upting North Upting North Upting </td <td></td>	
TERTION MARTICLE INEL FORMATI Second Sec	TERMON MARINE CONCRETE FAIRING SERVICE SERVICE SERVICE MERT FORM CONCRETE FAIRING WITE AFTER WITE AFTER WITE AFTER BIRING CONTONE CONCRETE FAIRING WITE AFTER CONCRETE NUMMERS BIRING CONTONE NUM FRACE DESTING OVER WITE FOR DESTING OVER WITE FORCE DESTING OVERFEAD ELEMENT DESTING OVERFEAD ELEMENT DESTING OVERFEAD ELEMENT TOO DESTING OVERFEAD ELEMENT DESTING OVERFEAD ELEMENT TOO NULT FOOM CACLULATION TABLE - TO YE STOOM FOOM NULT FOOM CACLULATION TABLE - TO YE STOOM FOOM NULT FOOM CACLULATION TABLE - TO YE STOOM FOOM NULT FOOM CACLULATION TABLE - TO YE STOOM FOOM FOOM NULT FOOM CACLULATION TABLE - TO YE STOOM FOOM NULT FOOM CACLULATION TABLE - TO YE STOOM FOOM NULT FOOM CACLULATION TABLE - TO YE STOOM FOOM <td>INTERFORMATION INTERFORMATION INTE</td> <td></td>	INTERFORMATION INTERFORMATION INTE	
B CATE VALVE ASM/A1 7 XM/NG REGRETION CONTROL WAVE ASM/A1 7 XM/NG B CONCRETE SDEWARK EXTING CONTOURS CONCRETE SDEWARK EXTING CONTOURS CONCRETE WASHOUT EXTING VERTICE SCALED CONSTRUCTION BUTWAREE EXTING WIN PROCE SCALED CONSTRUCTION BUTWAREE EXTING VERTICE SCALED CONSTRUCTION BUTWAREE EXTING VERTICE TOLE SCALED CONSTRUCTION EXTING VERTICE TOLE UNE NULT PROTECTION A 0.05 0.57 0.4 7.9 0.00 A 0.05 0.57 0.4 7.60 3.33 1.0.3 0	Generalize APHAT PMING INFRACTION CONTOURS INFORMATION CONCRETE SIDEMUK INFINIS CONTOURS INFORMATION CONCRETE SIDEMUK INFINIS CONTOURS INFORMATION CONCRETE SIDEMUK INFINIS CONTOURS INFORMATION STRUCKIN INFINIS CONTOURS INFORMATION STRUCKINS INFINIS CONTOURS INFINIS INFINIS INFINIS CONTOURS INFINIS INFINIS INFINIS CONTOURS INFINIS INFINIS INFINIS CONTRECT INFINIS INFINIS INFINIS CONTRECT LINE INFINIS PROJECTION INFINIS CONTRECT LINE INFINIS PROJECTION INFINIS CONTRECT LINE INFINIS PROJECTION INFINIS CONTRECT LINE INFINIS CONTRECT LINE	B CHI KUVE APPRAIDADE BREAKTION CONTROL KUVE APPRAID KONKOL BREAKTION CONTROL KUVE APPRAID KONKOL BREAKTION CONTROL KUVE CONCRET: SDEWALK BREAKTION CONTROL KUVE STARLED BREAKTON CONTON STARLED BREAKTON CONTROL KUVE WITH PROFE BREAKTON CONTROL KUVE WITH REPORT BREAKTON CONTROL KUVE STARLED BREAKTON CONTROL KUVE STARLED BREAKTON CONTROL KUVE <td></td>	
WAIR METER CONCRETE SUBWAIK BISSING CONTOURS CONCRETE SUBWAIK BISSING CONTOURS CONCRETE WASHOUT BISSING CARENT LWR FENCE CONCRETE WASHOUT BISSING CARENT LWR FENCE STABULED CONSTRUCTION ENTRANCE BISSING CARENT LWR STABULED CONSTRUCTION ENTRANCE BISSING CARENT CLINE SITE FROE BISSING CARENT CLINE SITE FROE BISSING CARENT CLINE INCET FROETCION BISSING CARENT CLINE INCET FROETCION BISSING CARENT CLINE INCET ROTICTION BISSING CARENT CLINE INCET ROTICTION BISSING CARENT CLINE INCET ROTICTION INCET FOOW CALCULATION TABLE - 25 YR. STORM EVENT INCET SOC 05.54 CA 0.1 0.76 0.77 0.5 0.37 1.0.3 0 4 0.1 0.74 0.5 0.57 0.5 1.1.4 0.33 1 0.7 0.7 4 0.1 2.7 0.5 0.57 0.5 1 1 0.1 0.7 0.7 0.7 0.7 0.7	WHER WEIR CONCRETE SDRWUK DERING CONTOURS CONCRETE SDRWUK DERING CWININK RICCE CONCRETE SDRWUK DERING CWOOD PRACE STRELED CONSTRUCTION BITRACE DERING CWOOD PRACE STRELED CONSTRUCTION MILEY FLOW CALCULATION TABLE - 29 YR. STORM EVENT STRELED CONSTRUCTION STRELED CONSTRUCTION STRELED CONSTRUCTION STRELED CONSTRUCTION STRELED CONSTRUCTION STRELED CONSTRUCTION STRELED CONSTRUCTION STRELED CONSTRUCTION STRELED CONSTRUCTION	WATER METER CONCRETE SUBWALK BISTING CONTOURS CONCRETE SUBWALK BISTING CARLINK RENCE CONCRETE WASHOUT BISTING WOOD PIECL CONCRETE WASHOUT BISTING CARLINK RENCE SITELECONTRUCTION BITRANCE BISTING WOOD PIECL SITELECONTRUCTION BISTING WOOD PIECL SITELECONTRUCTION BISTING WOOD PIECL SITELECONTRUCTION BISTING WORK PENCE SITELECONTRUCTION BISTING WORK PENCE SITELECONTRUCTION BISTING WORK PENCE SITELECONTRUCTION BISTING WORK PENCE UNICH SOCK BISTING WORK PENCE UNICH SOCK DISTING WORK PENCE SITELECONT NAME CONSTRUCTION TABLE - 25 YR. STORM EVENT Group of the pence CALCULATION TABLE - 100 YR. STORM EVENT 10.1 CALO LIA LON TABLE - 100 YR. STORM EVENT 10.1	
Image: Control Contro Control Control Control Control Control Control Control Control C		■ UNING CHAN UNK FINCE ■ UNING CHAN UNK FINCE ■ BUSING WAGE FINCE ■ WAGE FINCE ■ BUSING WAGE TIME ■ WAGE FINCE ■ BUSING WAGE FINCE ■ WAGE FINCE ■ BUSING WAGE FINCE ■ WAGE FINCE ■ UNICH SOCK ■ WAGE FINCE ■ UNICH SOCK ■ WAGE FINCE ■ UNICH SOCK ■ WAGE FINCE ■ OLI A LAG OLIS O.ST OLI A TALE FING FINE FINCH	
■ LABING WR: PNCE STABLEDE CONSTRUCTION ENTRANCE ■ BUSING WR: PNCE STABLED CONSTRUCTION ENTRANCE ■ EXSTING WOOD ENCE SULT ENCE ■ EXSTING WOOD ENCE SULT ENCE ■ EXSTING WOOD ENCE SULT ENCE ■ EXSTING WOOD ENCE NEET PROTECTION ■ EXSTING CORENED ELECTRIC UNE PREE PROTECTION ■ EXSTING CORENED ELECTRIC UNE MUCH SOCK ■ EXSTING CORENED ELECTRIC UNE UNITS OF CONSTRUCTION ■ EXSTING CORENED ELECTRIC UNE UNITS OF CONSTRUCTION ■ EXSTING CORENED THEETIC UNE UNITS OF CONSTRUCTION ■ EXSTING CORENED THEETIC UNE UNITS OF CONSTRUCTION ■ EXSTING CORENED THEETIC UNE UNITS OF CONSTRUCTION ■ UNITS OF CONSTRUCTION 10.0 70 4 0.1 3.7 0.5 0.37 0.5 17.0 0 3.33 1 0.3 0.4 4 0.1 3.7 0.5 0.37 0.5 4.7.60 3.33 1 0.3 0.4 4 0.1 4.6 0.5 0.37 0.5 4.7.60 3.33 1 0.3 0.7	Elbino (with PNC) STABLEDE CONSTRUCTION ENTRANCE BUBINO WITH PNCE STABLEDE CONSTRUCTION ENTRANCE BUBINO WOTH PNCE SIT FINCS BUBINO WAT ENCL SIT FINCS BUBINO WATE PNCE SIT FINCS	EDITING WRE PNACE STABILIZED CONSTRUCTION ENTRANCE DESTING WOOD FINCE SUIT FINCE DESTING WOOD FINCE MILET PROTECTION DESTING WOOD FINCE MILET SOF CONSTRUCTION DESTING WOOD FINCE MILET FLOW CALCULATION TABLE - 25 YR. STORM EVENT MILET FLOW CALCULATION TABLE - 25 YR. STORM EVENT (N) (FT) (FT) (FT) (FT) (FT) (CFS) (CFS) (CFS) 4 0.03 2.7 0.5 0.57 0.2 4 7.60 3.33 1 0.3 0.70 0.70 4 0.1 2.6 0.57 0.5 4 7.60 3.33 1 0.3 0.70 0.70 4 0.1 2.6 0.57 0.5 <	
Image: Index LINE SulT FENCE ■ BASEMART LINE BUT FENCE ■ BASEMART LINE INTERPORT CONN ■ BASEMART LINE INTERPORT FROME ■ BASEMART LINE MULCH SOCK BASEMART LINE MULCH SOCK UNITS OF CONSTRUCTION UNITS OF CONSTRUCTION INTERPORT CALCULATION TABLE - 25 YP. STORM EVENT INTERPORT CANA (IN) (FT) (FT) (FT) (FT) I 0.7 0.7 4 0.1 3.7 0.5 0.57 0.4 4 1.0.1 0.7 0.7 4 0.1 7.7 0.5 0.57 0.5 4 7.60 3.33 1 0.7 0 4 0.1 7.4 4 1.40 3.33 1 0.7 0 4	Image: Startex LINE SLT FINCE BASEMENT LINE ROCK BEM BASEMENT LINE ROCK BEM BASEMENT LINE NELT PROTECTION BASEMENT LINE NULCH SOCK BASEMENT LINE NULCH SOCK DIALT FLOW CALCULATION TABLE - 25 YR. STORM EVENT 0 0 (PT) (PT) (PT) FLOW CALCULATION TABLE - 25 YR. STORM EVENT 0 4 0.1 0.70 4 0.1 0.76 4 0.1 2.7 0.5 0.57 0.5 4 1.60 1.07 0.7 0 4 0.1 2.6 0.57 0.5 4 7.60 3.33 1 0.3 0 4 0.1 7.7 0.5 0.57 0.5 4 7.60 3.33 1 0.7 0	Image: Start AC LINE SUT FEVCE SUT FEVCE BASEMENT LINE NOCK BEBM DISTING ASPHALT NOCK BEBM DISTING ASPHALT NOCK BEBM DESTING OVERHEAD ELECTRIC LINE NUCH SOCK DESTING OVERHEAD TELEMONE LINE NUCH SOCK DISTING OVERHEAD TELEMONE LINE NUCH SOCK UNITS OF CONSTRUCTION LINET ROUTCINCIN THE ROW CALCULATION TABLE - 25 YR. STORM EVENT NUCH SOCK 0 Yo 0 Yo 10 YO 11 0.76 10.1 0.77 10.2 0.78 4 0.1 4.0.1 3.7 4.0.5 0.57 0.5 0.57 4 0.1 4.0.1 4.5 0.2 8.9 0.5 0.57 1.4 0.5 1.7 0.5 1.7 0.5 1.7 0.5 1.7 0.5 1.7 0.5	
ENSTING ASPHALT INLET PROTECTION	IDETING ASPHALT INLET PROTECTION BISTING ASPHALT THE PROTECTION DESTING ADVERADAD ELECTRIC LINE THE PROTECTION DESTING OVERHAD ELECTRIC LINE THE PROTECTION DISTING OVERHAD TELEPHONE LINE THE PROTECTION INLET FLOW CALCULATION TABLE - 25 YR. STORM EVENT THE PROTECTION (IN) (FT) (FT) <td>■ DISTING ASPHAU </td> <td></td>	■ DISTING ASPHAU	
→ EXISTING UNDERGROUND ELECTRIC LINE MULCH SOCK → EXISTING OVERHEAD TELEHIONE LINE LIMITS OF CONSTRUCTION INTEG FLOW CALCULATION TABLE - 25 YR. STORM EVENT (IN) (FT) INTO 50 0.57 0.4 4 11.40 3.33 11 0.7 0 4 0.01 3.7 0.5 0.57 0.5 4 7.60 3.33 11 0.3 0 4 0.1 3.7 0.5 0.57 0.5 4 7.60 3.33 11 0.2 0 4 0.1 3.7 0.5 0.57 0.5 4 7.60 3.33 11 0.3 0 4 0.1 3.7 0.5 0.57 0.5 4 7.60 3.33 1 0.3 0 4 0.1 3.7 0.5 0.57 0.5 4 7.60 3.33 1 0.3 0 4 0.1 4.6 0.5 0.57 0.5 4 7.60 3.33 1 0.3 0 4 0.1 3.7 0.5 0.57 0.5 4 7.60 3.33 1 0.3 0 4 0.1 3.7 0.5 0.57 0.5 4 7.60 3.33 1 0.3 0 4 0.1 3.7 0.5 0.57 0.5 4 7.60 3.33 1 0.3 0 4 0.1 4.6 0.5 0.57 0.5 4 7.60 3.33 1 0.3 0 4 0.1 4.6 0.5 0.57 0.5 4 7.60 3.33 1 0.3 0 4 0.1 4.6 0.5 0.57 0.5 4 7.60 3.33 1 0.3 0 4 0.1 4.6 0.5 0.57 0.5 4 7.60 3.33 1 0.7 0 6 0.1 4.6 0.5 0.57 0.5 4 7.60 3.33 1 0.7 0 6 0.1 4.6 0.5 0.57 0.5 4 7.60 3.33 1 0.7 0 6 0.1 4.6 0.5 0.57 0.5 4 7.60 3.33 1 0.7 0 7 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	→ DESTING UNDERGROUND ELECTRIC LINE MUCH SOCK → DUITS OF CONSTRUCTION JUITS OF CONSTRUCTION JUITS OF CONSTRUCTION INTET FLOW CALCULATION TABLE - 25 YR. STORM EVENT JUITS OF CONSTRUCTION AULCH SOCK Auron Much Sock Auron Much Sock 0 Y Y PONDED WIDTH REDUCTION CFN 1/1 0/2	→ DISTING UNDERGROUND ELECTRIC LINE MULCH SOCK → BISTING OVERHEAD TELEPHONE LINE LIMITS OF CONSTRUCTION IMILET FLOW CALCULATION TABLE - 25 YR. STORM EVENT LIMITS OF CONSTRUCTION A 0 0.3 5.9 0.1 0.79 1.0 5 4.0.1 0.7 0 4 0.1 0.76 0.9 5 5.4.3 1.0.2 0 1 0.1 0.7 0 4 0.1 3.7 0.5 0.57 0.4 4 1.40 3.33 1 0.3 0 4 0.1 3.7 0.5 0.57 0.4 4 1.40 3.33 1 0.3 0 4 0.1 7.4 0.5 0.57 0.4 4 1.40 3.33 1 0.3 0 4 0.1 7.4 3.26 5.00 1 1 0.7 0 0 0 0 0 0 0 0 0.5 0.57<	
Lenn by Column (N) INTELET FLOW CALCULATION TABLE - 25 YR. STORM EVENT a Vo Quada (FT)	INITE FLOW CALCULATION TABLE - 25 YR. STORM EVENT Image: Construction Constrution Construction <th< td=""><td>INFORCE CONNECTED INFORCE CONNECTED a View PONDED WIDTH REDUCTION add/a (FT) (FT) (FT) FACTOR add/a (FT) (FT)<td></td></td></th<>	INFORCE CONNECTED INFORCE CONNECTED a View PONDED WIDTH REDUCTION add/a (FT) (FT) (FT) FACTOR add/a (FT) (FT) <td></td>	
Inter FLOW Concentration table Low Concentration La Length Q Qpass Q	Interf Construction Construction <thconstruction< th=""> Construction</thconstruction<>	Interfect Calculation rate Isometric Isometri	di.com
5 0.3 5.9 0.1 0.79 1.0 5 4.94 1.39 1 0.8 0 5 0.3 5.4 0.1 0.76 0.9 5 5.43 1.39 1 0.77 0 4 0.05 2.7 0.5 0.57 0.2 4 22.80 6.67 1 0.1 0 4 0.1 4.6 0.5 0.57 0.4 4 1.40 3.33 1 0.2 0 4 0.1 4.6 0.5 0.57 0.4 4 1.1.40 3.33 1 0.3 0 4 0.1 7.4 0.5 0.57 1.2 4 3.26 5.00 1 1 0 4 0.2 8.9 0.5 0.66 3.2 16 5.03 1.67 1 3.1 0 4 0.2 8.9 0.5 0.66 3.2 1.67 3.33	s 0.3 5.9 0.1 0.76 1.0 5 4.94 1.39 1 0.8 0 4 0.05 2.7 0.5 0.57 0.2 4 22.80 6.67 1 0.1 0.7 0 4 0.11 3.7 0.5 0.57 0.2 4 1.08 0.3 0 4 0.11 3.7 0.5 0.57 0.2 4 1.08 0.3 0 4 0.1 3.7 0.5 0.57 0.2 4 1.08 3.33 1 0.2 0 4 0.1 4.6 0.5 0.57 0.5 4 7.60 3.33 1 0.3 0 4 0.1 7.4 0.5 0.57 1.2 4 3.33 1 0.2 0 4 0.2 3.1 0.5 0.66 3.2 16 5.03 1.67 1 1.1 0 4 0.2 3.1 0.5 0.66 4.7 8 1.70323	5 0.3 5.9 0.1 0.76 0.9 5 4.4 1.39 1 0.8 0 4 0.05 2.7 0.5 0.57 0.2 4 22.80 6.67 1 0.1 0.4 4 0.1 3.7 0.5 0.57 0.2 4 14 3.33 1 0.2 0 4 0.1 3.7 0.5 0.57 0.5 4 7.60 3.33 1 0.3 0 4 0.1 4.6 0.5 0.57 0.5 4 7.60 3.33 1 0.3 0 4 0.1 3.7 0.5 0.57 0.4 4 11.40 3.33 1 0.2 0 4 0.1 6.5 0.57 0.4 4 11.40 3.33 1 0.2 0 4 0.2 3.1 0.5 0.66 4.7 8 1.70323 1.67 1 3.1 0 6 0.1 0.2 8.9 0.5 <td< td=""><td>-ds.www</td></td<>	-ds.www
4 0.1 3.7 0.5 0.57 0.4 4 11.40 3.33 1 0.2 0 4 0.1 4.6 0.5 0.57 0.5 4 7.60 3.33 1 0.3 0 4 0.1 3.7 0.5 0.57 0.5 4 7.60 3.33 1 0.3 0 4 0.1 3.7 0.5 0.57 0.5 4 11.40 3.33 1 0.2 0 4 0.1 7.4 0.5 0.57 1.2 4 3.26 3.33 1 0.7 0 4 0.2 8.9 0.5 0.66 3.2 16 5.03 1.67 1 3.1 0 4 0.2 3.1 0.5 0.66 4.7 8 1.70323 1.67 1 3.1 0 1 0.2 3.3 1 0.7 0.5 0.57 0.2 4 22.80 3.33 1 0.1 0 0 0 0 0 <td>4 0.1 3.7 0.5 0.57 0.4 4 11.40 3.33 1 0.2 0 4 0.1 4.6 0.5 0.57 0.5 4 7.60 3.33 1 0.2 0 4 0.1 3.7 0.5 0.57 0.5 4 7.60 3.33 1 0.3 0 4 0.1 3.7 0.5 0.57 0.4 4 11.40 3.33 1 0.2 0 4 0.1 7.4 0.5 0.57 1.2 4 3.26 3.33 1 0.2 0 6 0.1 6.5 0.5 0.56 0.57 1.8 8 4.56 5.00 1 1 0 4 0.2 3.1 0.5 0.66 4.7 8 1.70323 1.67 1 3.1 0 1 0.5 0.57 0.5 4 7.60 3.33 1 0.3 0 5 0.3 6.3 0.57 0.5</td> <td>4 0.1 3.7 0.5 0.57 0.4 4 11.40 3.33 1 0.2 0 4 0.1 4.6 0.5 0.57 0.5 4 7.60 3.33 1 0.3 0 4 0.1 3.7 0.5 0.57 0.5 4 7.60 3.33 1 0.3 0 4 0.1 3.7 0.5 0.57 0.4 4 11.40 3.33 1 0.2 0 4 0.1 7.4 0.5 0.57 1.2 4 3.26 3.33 1 0.7 0 6 0.1 6.5 0.5 0.57 1.2 4 3.26 5.00 1 1 0 4 0.2 8.9 0.5 0.66 3.2 16 5.03 1.67 1 3.1 0 INLET FLOW CALCULATION TABLE - 100 YR. STORM EVENT (FT) L/La o/Yo Q/Qaq Q Q pass Q pass 6 0.3 7.3 0.1 0.76 <th< td=""><td>eb Site:</td></th<></td>	4 0.1 3.7 0.5 0.57 0.4 4 11.40 3.33 1 0.2 0 4 0.1 4.6 0.5 0.57 0.5 4 7.60 3.33 1 0.2 0 4 0.1 3.7 0.5 0.57 0.5 4 7.60 3.33 1 0.3 0 4 0.1 3.7 0.5 0.57 0.4 4 11.40 3.33 1 0.2 0 4 0.1 7.4 0.5 0.57 1.2 4 3.26 3.33 1 0.2 0 6 0.1 6.5 0.5 0.56 0.57 1.8 8 4.56 5.00 1 1 0 4 0.2 3.1 0.5 0.66 4.7 8 1.70323 1.67 1 3.1 0 1 0.5 0.57 0.5 4 7.60 3.33 1 0.3 0 5 0.3 6.3 0.57 0.5	4 0.1 3.7 0.5 0.57 0.4 4 11.40 3.33 1 0.2 0 4 0.1 4.6 0.5 0.57 0.5 4 7.60 3.33 1 0.3 0 4 0.1 3.7 0.5 0.57 0.5 4 7.60 3.33 1 0.3 0 4 0.1 3.7 0.5 0.57 0.4 4 11.40 3.33 1 0.2 0 4 0.1 7.4 0.5 0.57 1.2 4 3.26 3.33 1 0.7 0 6 0.1 6.5 0.5 0.57 1.2 4 3.26 5.00 1 1 0 4 0.2 8.9 0.5 0.66 3.2 16 5.03 1.67 1 3.1 0 INLET FLOW CALCULATION TABLE - 100 YR. STORM EVENT (FT) L/La o/Yo Q/Qaq Q Q pass Q pass 6 0.3 7.3 0.1 0.76 <th< td=""><td>eb Site:</td></th<>	eb Site:
4 0.1 4.6 0.5 0.57 0.5 4 7.60 3.33 1 0.3 0 4 0.1 3.7 0.5 0.57 0.4 4 11.40 3.33 1 0.2 0 4 0.1 7.4 0.5 0.57 1.2 4 3.26 3.33 1 0.7 0 6 0.1 6.5 0.5 0.57 1.8 8 4.56 5.00 1 1 0 4 0.2 8.9 0.5 0.66 3.2 16 5.03 1.67 1 3.1 0 4 0.2 3.1 0.5 0.66 4.7 8 1.70323 1.67 1 3.1 0 INLET FLOW CALCULATION TABLE - 100 YR. STORM EVENT a Yo PONDED WIDTH REDUCTION La Length L/La a/Yo Q/Qaa (CFS) (cfs) 5 0.3 6.4 0.1 0.76 1.2 5 4.22 1.39 1 1.1 0	4 0.1 4.6 0.5 0.5 4 7.60 3.33 1 0.3 0 4 0.1 3.7 0.5 0.57 1.4 4 11.40 3.33 1 0.2 0 4 0.1 7.4 0.5 0.57 1.2 4 3.26 3.33 1 0.7 0 6 0.1 6.5 0.5 0.57 1.8 8 4.56 5.00 1 1 0 4 0.2 3.1 0.5 0.66 3.2 16 5.03 1.67 1 2.1 0 4 0.2 3.1 0.5 0.66 4.7 8 1.70323 1.67 1 3.1 0 1 1 0.2 3.1 0.79 1.4 5 3.59 1.39 1 1.1 0 5 0.3 6.4 0.1 0.5 0.57 0.5 4 7.60 3.33 1 0.4 0 4 0.1 6.1 0.5 0.57 0.5<	4 0.1 4.6 0.5 0.57 0.5 4 7.60 3.33 1 0.3 0 4 0.1 3.77 0.5 0.57 0.4 4 11.40 3.33 1 0.2 0 4 0.1 7.4 0.5 0.57 1.2 4 3.26 3.33 1 0.7 0 6 0.1 6.5 0.5 0.57 1.8 8 4.56 5.00 1 1 0 4 0.2 8.9 0.5 0.66 3.2 16 5.03 1.67 1 2.1 0 4 0.2 3.1 0.5 0.66 4.7 8 1.70323 1.67 1 3.1 0 6 0.1 5.6 0.57 0.5 4.7 8 1.70323 1.67 1 1.1 0 5 0.3 7.3 0.1 0.79 1.4 5 3.59 1.39 1 1.1 0 6 0.1 5.4 0.5 <t< td=""><td></td></t<>	
A O.1 J.1 J.3 O.37 I.12 A J.20 J.30 I O.1 O.5 O.5 O.57 I.18 8 4.56 J.00 I I O	Image: Non-original condition of the second condite condition of the second condition of the se	A 0.1 1.1 0.3 0.30 1.12 4 0.30 1.12 1 0.5 0.5	uuuu @sp-ai.
4 0.2 3.1 0.5 0.66 4.7 8 1.70323 1.67 1 3.1 0 INLET FLOW CALCULATION TABLE - 100 YR. STORM EVENT a Yo PONDED WIDTH REDUCTION La LENGTH a/Yo Q/Qa Qpass (cfs) (cfs) (cfs) (cfs) (cfs) (cfs) (cfs) U/Yo NOT NOT <td>4 0.2 3.1 0.5 0.66 4.7 8 1.70323 1.67 1 3.1 0 INLET FLOW CALCULATION TABLE - 100 YR. STORM EVENT a Yo PONDED WIDTH REDUCTION La LENGTH L/La a/Yo Q/Qaa Qpass (CFS) (dfs) 5 0.3 7.3 0.1 0.79 1.4 5 3.59 1.39 1 1.1 0 5 0.3 6.4 0.1 0.76 0.2 4 22.80 3.33 1 0.1 0.76 1.2 5 4.22 1.39 1 0.1 0 0 4 0.1 2.7 0.5 0.57 0.2 4 22.80 3.33 1 0.3 0 4 0.1 5.4 0.5 0.57 0.5 4 7.60 3.33 1 0.3 0 4 0.1 4.6 0.5 0.57 0.5 4 7.60 3.33 1 0.3 0 4 0.2 8.9<!--</td--><td>4 0.2 3.1 0.5 0.66 4.7 8 1.70323 1.67 1 3.1 0 INLET FLOW CALCULATION TABLE - 100 YR. STORM EVENT a Yo PONDED WIDTH REDUCTION La LENGTH a//c Q/Qa Q Qposs (cfs) <</td><td>nail: spa</td></td>	4 0.2 3.1 0.5 0.66 4.7 8 1.70323 1.67 1 3.1 0 INLET FLOW CALCULATION TABLE - 100 YR. STORM EVENT a Yo PONDED WIDTH REDUCTION La LENGTH L/La a/Yo Q/Qaa Qpass (CFS) (dfs) 5 0.3 7.3 0.1 0.79 1.4 5 3.59 1.39 1 1.1 0 5 0.3 6.4 0.1 0.76 0.2 4 22.80 3.33 1 0.1 0.76 1.2 5 4.22 1.39 1 0.1 0 0 4 0.1 2.7 0.5 0.57 0.2 4 22.80 3.33 1 0.3 0 4 0.1 5.4 0.5 0.57 0.5 4 7.60 3.33 1 0.3 0 4 0.1 4.6 0.5 0.57 0.5 4 7.60 3.33 1 0.3 0 4 0.2 8.9 </td <td>4 0.2 3.1 0.5 0.66 4.7 8 1.70323 1.67 1 3.1 0 INLET FLOW CALCULATION TABLE - 100 YR. STORM EVENT a Yo PONDED WIDTH REDUCTION La LENGTH a//c Q/Qa Q Qposs (cfs) <</td> <td>nail: spa</td>	4 0.2 3.1 0.5 0.66 4.7 8 1.70323 1.67 1 3.1 0 INLET FLOW CALCULATION TABLE - 100 YR. STORM EVENT a Yo PONDED WIDTH REDUCTION La LENGTH a//c Q/Qa Q Qposs (cfs) <	nail: spa
INLET FLOW CALCULATION TABLE - 100 YR. STORM EVENT a Yo PONDED WIDTH REDUCTION La LENGTH a/Yo Q/Qa Q pass (CFS) (cfs) G D S 0.1 0.79 1.4 5 3.59 1.39 1 1.1 0 5 0.3 7.3 0.1 0.79 1.4 5 3.59 1.39 1 1.1 0 4 0.1 2.7 0.5 0.57 0.2 4 22.80 3.33 1 0.1 0 4 0.1 5.4 0.57 0.57 0.5 4 7.60 3.33 1 0.4 0 4 0.1 5.4 0.57 0.57 4 7.60 3.33 1 0.4 0 4 0.1 6.1 0.5 0.57 0.5 4 7.60 3.33 1 0.3 0 4 0.1 4.6 0.5 0.57 0.5 4 7.60 3.33 1 0.3 0 4 0.2	INLET FLOW CALCULATION TABLE - 100 YR. STORM EVENT a Yo PONDED WIDTH REDUCTION La LENGTH a Q Qpass Qffs Qffs <td>INLET FLOW CALCULATION TABLE - 100 YR. STORM EVENT a Yo PONDED WIDTH REDUCTION La LENGTH Q/Qa Q/Qa Qpass Qfs Qpass Qfs Qpass Qfs Qfs Qpass Qfs Qfs</td> <td>Ē</td>	INLET FLOW CALCULATION TABLE - 100 YR. STORM EVENT a Yo PONDED WIDTH REDUCTION La LENGTH Q/Qa Q/Qa Qpass Qfs Qpass Qfs Qpass Qfs Qfs Qpass Qfs	Ē
INLET FLOW CALCULATION TABLE - 100 YR. STORM EVENT a Yo PONDED WIDTH REDUCTION La LENGTH a/Yo Q/Qaa Qpass (cFS) Qides Qpass (cfs) Qides	INLET FLOW CALCULATION TABLE - 100 YR. STORM EVENT a Yo PONDED WIDTH REDUCTION La LENGTH a/Yo Q/Qa Qpass Qpass Qffs (IN) (FT) (FT) FACTOR Qa/La (FT) (FT) L/La a/Yo Q/Qa (CFS) (cfs) (fs) 5 0.3 7.3 0.1 0.79 1.4 5 3.59 1.39 1 1.1 0 5 0.3 6.4 0.1 0.76 1.2 5 4.22 1.39 1 0.1 0 0 4 0.1 4.6 0.5 0.57 0.2 4 22.80 3.33 1 0.3 0 4 0.1 5.4 0.5 0.57 0.7 4 5.70 3.33 1 0.4 0 4 0.1 6.1 0.5 0.57 0.5 4 7.60 3.33 1 0.3 0 4 0.2 8.9 0.5 0.66 1.5 4 2.64 1.67 <td>INLET FLOW CALCULATION TABLE - 100 YR. STORM EVENT a Yo PONDED WIDTH REDUCTION La LENGTH a Q Q Opass (fs) Opass (fs)</td> <td></td>	INLET FLOW CALCULATION TABLE - 100 YR. STORM EVENT a Yo PONDED WIDTH REDUCTION La LENGTH a Q Q Opass (fs)	
(1.7) (1.7) <th< td=""><td>1.1.1 1.1.1 1.1.1 0 5 0.3 7.3 0.1 0.79 1.4 5 3.59 1.39 1 1.1.1 0 5 0.3 6.4 0.1 0.76 1.2 5 4.22 1.39 1 0.9 0 4 0.1 2.7 0.5 0.57 0.2 4 22.80 3.33 1 0.1 0 4 0.1 5.4 0.5 0.57 0.5 4 7.60 3.33 1 0.3 0 4 0.1 5.4 0.5 0.57 0.7 4 5.70 3.33 1 0.4 0 4 0.1 6.1 0.5 0.57 0.5 4 7.60 3.33 1 0.3 0 4 0.1 4.6 0.5 0.57 0.5 4 7.60 3.33 1 0.3 0 4 0.2 8.9 0.5 0.66 1.5 4 2.64 1.67 1 1 0 <td>(1.1) <th< td=""><td></td></th<></td></td></th<>	1.1.1 1.1.1 1.1.1 0 5 0.3 7.3 0.1 0.79 1.4 5 3.59 1.39 1 1.1.1 0 5 0.3 6.4 0.1 0.76 1.2 5 4.22 1.39 1 0.9 0 4 0.1 2.7 0.5 0.57 0.2 4 22.80 3.33 1 0.1 0 4 0.1 5.4 0.5 0.57 0.5 4 7.60 3.33 1 0.3 0 4 0.1 5.4 0.5 0.57 0.7 4 5.70 3.33 1 0.4 0 4 0.1 6.1 0.5 0.57 0.5 4 7.60 3.33 1 0.3 0 4 0.1 4.6 0.5 0.57 0.5 4 7.60 3.33 1 0.3 0 4 0.2 8.9 0.5 0.66 1.5 4 2.64 1.67 1 1 0 <td>(1.1) <th< td=""><td></td></th<></td>	(1.1) (1.1) <th< td=""><td></td></th<>	
4 0.1 2.7 0.5 0.57 0.2 4 22.80 3.33 1 0.1 0 4 0.1 4.6 0.5 0.57 0.5 4 7.60 3.33 1 0.1 0 4 0.1 5.4 0.5 0.57 0.5 4 7.60 3.33 1 0.3 0 4 0.1 5.4 0.5 0.57 0.7 4 5.70 3.33 1 0.3 0 4 0.1 6.1 0.5 0.57 0.7 4 5.70 3.33 1 0.4 0 4 0.1 6.1 0.5 0.57 0.9 4 4.56 3.33 1 0.3 0 4 0.1 4.6 0.5 0.57 0.5 4 7.60 3.33 1 0.3 0 4 0.2 8.9 0.5 0.66 1.5 4 2.64 1.67 1 1 0 6 0.2 7.9 0.5 0.66 </td <td>4 0.1 2.7 0.5 0.57 0.2 4 22.80 3.33 1 0.1 0 4 0.1 4.6 0.5 0.57 0.5 4 7.60 3.33 1 0.1 0 4 0.1 5.4 0.5 0.57 0.7 4 5.70 3.33 1 0.3 0 4 0.1 6.1 0.5 0.57 0.7 4 5.70 3.33 1 0.4 0 4 0.1 6.1 0.5 0.57 0.9 4 4.56 3.33 1 0.4 0 4 0.1 4.6 0.5 0.57 0.5 4 7.60 3.33 1 0.3 0 4 0.2 8.9 0.5 0.66 1.5 4 2.64 1.67 1 1 0 6 0.2 7.9 0.5 0.66 2.1 8 3.77 2.50 1 1.4 0 4 0.2 0.4 0.5 0.66<!--</td--><td>4 0.1 2.7 0.5 0.57 0.2 4 22.80 3.33 1 0.1 0 4 0.1 4.6 0.5 0.57 0.2 4 7.60 3.33 1 0.1 0 4 0.1 4.6 0.5 0.57 0.7 4 5.70 3.33 1 0.1 0 4 0.1 5.4 0.5 0.57 0.7 4 5.70 3.33 1 0.4 0 4 0.1 6.1 0.5 0.57 0.9 4 4.56 3.33 1 0.4 0 4 0.1 4.6 0.5 0.57 0.5 4 7.60 3.33 1 0.3 0 4 0.2 8.9 0.5 0.66 1.5 4 2.64 1.67 1 1 0 6 0.2 7.9 0.5 0.66 2.1 8 3.77 2.50 1 1.4 0 4 0.2 6.4 0.5 0.66<!--</td--><td>310 388-067 38-0752</td></td></td>	4 0.1 2.7 0.5 0.57 0.2 4 22.80 3.33 1 0.1 0 4 0.1 4.6 0.5 0.57 0.5 4 7.60 3.33 1 0.1 0 4 0.1 5.4 0.5 0.57 0.7 4 5.70 3.33 1 0.3 0 4 0.1 6.1 0.5 0.57 0.7 4 5.70 3.33 1 0.4 0 4 0.1 6.1 0.5 0.57 0.9 4 4.56 3.33 1 0.4 0 4 0.1 4.6 0.5 0.57 0.5 4 7.60 3.33 1 0.3 0 4 0.2 8.9 0.5 0.66 1.5 4 2.64 1.67 1 1 0 6 0.2 7.9 0.5 0.66 2.1 8 3.77 2.50 1 1.4 0 4 0.2 0.4 0.5 0.66 </td <td>4 0.1 2.7 0.5 0.57 0.2 4 22.80 3.33 1 0.1 0 4 0.1 4.6 0.5 0.57 0.2 4 7.60 3.33 1 0.1 0 4 0.1 4.6 0.5 0.57 0.7 4 5.70 3.33 1 0.1 0 4 0.1 5.4 0.5 0.57 0.7 4 5.70 3.33 1 0.4 0 4 0.1 6.1 0.5 0.57 0.9 4 4.56 3.33 1 0.4 0 4 0.1 4.6 0.5 0.57 0.5 4 7.60 3.33 1 0.3 0 4 0.2 8.9 0.5 0.66 1.5 4 2.64 1.67 1 1 0 6 0.2 7.9 0.5 0.66 2.1 8 3.77 2.50 1 1.4 0 4 0.2 6.4 0.5 0.66<!--</td--><td>310 388-067 38-0752</td></td>	4 0.1 2.7 0.5 0.57 0.2 4 22.80 3.33 1 0.1 0 4 0.1 4.6 0.5 0.57 0.2 4 7.60 3.33 1 0.1 0 4 0.1 4.6 0.5 0.57 0.7 4 5.70 3.33 1 0.1 0 4 0.1 5.4 0.5 0.57 0.7 4 5.70 3.33 1 0.4 0 4 0.1 6.1 0.5 0.57 0.9 4 4.56 3.33 1 0.4 0 4 0.1 4.6 0.5 0.57 0.5 4 7.60 3.33 1 0.3 0 4 0.2 8.9 0.5 0.66 1.5 4 2.64 1.67 1 1 0 6 0.2 7.9 0.5 0.66 2.1 8 3.77 2.50 1 1.4 0 4 0.2 6.4 0.5 0.66 </td <td>310 388-067 38-0752</td>	310 388-067 38-0752
$\begin{array}{c c c c c c c c c c c c c c c c c c c $	$\begin{array}{c c c c c c c c c c c c c c c c c c c $	4 0.1 5.4 0.5 0.57 0.7 4 5.70 3.33 1 0.4 0 4 0.1 6.1 0.5 0.57 0.9 4 4.56 3.33 1 0.5 0 4 0.1 4.6 0.5 0.57 0.9 4 4.56 3.33 1 0.5 0 4 0.1 4.6 0.5 0.57 0.5 4 7.60 3.33 1 0.3 0 4 0.2 8.9 0.5 0.66 1.5 4 2.64 1.67 1 1 0 6 0.2 7.9 0.5 0.66 2.1 8 3.77 2.50 1 1.4 0 4 0.2 10.2 0.5 0.66 6.5 8 1.23 1.67 1 2.9 0 4 0.2 6.4 0.5 0.66 6.5 8 1.23 1.67 1 4.3 0	10 11 2ne: (512 :: (512) 38
4 0.1 4.0 0.5 0.5/ 0.5 4 7.60 3.33 1 0.3 0 4 0.2 8.9 0.5 0.66 1.5 4 2.64 1.67 1 1 0 6 0.2 7.9 0.5 0.66 2.1 8 3.77 2.50 1 1.4 0 4 0.2 10.2 0.5 0.66 4.4 16 3.64 1.67 1 2.9 0 4 0.2 6.4 0.5 0.66 6.5 8 1.23 1.67 1 4.3 0	4 0.1 4.0 0.5 0.57 0.5 4 7.60 3.33 1 0.3 0 4 0.2 8.9 0.5 0.66 1.5 4 2.64 1.67 1 1 0 6 0.2 7.9 0.5 0.66 2.1 8 3.77 2.50 1 1.4 0 4 0.2 10.2 0.5 0.66 4.4 16 3.64 1.67 1 2.9 0 4 0.2 6.4 0.5 0.66 6.5 8 1.23 1.67 1 4.3 0	$\begin{array}{c c c c c c c c c c c c c c c c c c c $	- Lax
4 0.2 10.2 0.5 0.66 4.4 16 3.64 1.67 1 2.9 0 4 0.2 6.4 0.5 0.66 6.5 8 1.23 1.67 1 4.3 0	4 0.2 10.2 0.5 0.66 4.4 16 3.64 1.67 1 2.9 0 4 0.2 6.4 0.5 0.66 6.5 8 1.23 1.67 1 2.9 0	4 0.2 10.2 0.5 0.66 4.4 16 3.64 1.67 1 2.9 0 4 0.2 6.4 0.5 0.66 6.5 8 1.23 1.67 1 2.9 0	

08 of 32 SDP2205-0006

SHEET

Segment #1													
Segment #1	TP 55 SCS Lag Times (HYDROLOGIC	SUMMA	ARY for	DA 1A	Elaur Sum					[
Sheet Flow	Segment #2 Shallow Concent	Segment #3 Channelized		Area acres	Tc hours	Cn -	Q2 cfs	Q10 cfs	Q25 cfs	Q50 cfs	Q100 cfs	Segment #1 Sheet Flow	
Mannings "n" _ength (ft)	Unpaved Length (ft)	Mannings "n" Length (ft)	0	0.62	0.0833	79	1.7	2.4	3.6	4	5	Mannings "n" Length (ft)	
Slope (%) 2-yr, 24 hr rainfall	Slope (%)	Slope (%) Velocity (fps)	0 0822	Imporvio		17%						Slope (%) 2-yr, 24 hr rainfall	0.08
	segment total	time of conc.(hrs)	0.0833	SCS La	g Time (.	6 x Tc)=	0.05					USER DEFINED	0.083
		HYDROLOGIC	SUMMA	ARY for	DA 1E	3					1		
Segment #1	TR-55 SCS Lag Time (Segment #2	hours) Segment #3		Area	Тс	Flow Sun Cn	Q2	Q10	Q25	Q50	Q100	Segment #1	
Sheet Flow Mannings "n"	Unpaved	Mannings "n"	0	0.43	hours 0.0833	- 79	1.3	1.8	2.6	2.9	3.5	Sheet Flow Manninas "n"	
Slope (%) 2-vr, 24 hr rainfall	Slope (%)	Slope (%) Velocity (fps)	0					_			-	Length (ft) Slope (%)	
segment total	segment total	segment total time of conc.(hrs)	0.0833 <i>0.083</i>	Impervio SCS Lag	us Cover g Time (.	68% 6 x Tc]=	0.05					2-yr, 24 hr rainfall segment total	0.083
		HYDROLOGIC	SUMMA	RY for	DA 10	7						USER DEFINED	
Segment #1	TR-55 SCS Lag Time (hours)		Area		Flow Sun	nmary	Q10	Q25	Q50	Q100		
Sheet Flow Mannings "n"	Shallow Concent Unpaved	Channelized Mannings "n"	0	acres	hours 0.0833	- 79	cfs 0.1	cfs 0.1	cfs 0.2	cfs 0.2	cfs 0.2	Segment #1 Sheet Flow	
ength (ft) Slope (%)	Length (ft) Slope (%)	Length (ft) Slope (%)	0									Mannings "n" Length (ft)	
2-yr, 24 hr raintall segment total	segment total	Velocity (tps) segment total	0.0833	Impervio	us Cover	0%	0.05					2-yr, 24 hr rainfall segment total	0.083
JSER DEFINED			0.003		g Time (.	o x i cj=	0.05					USER DEFINED	
	TR-55 SCS Lag Time (HYDROLOGIC	SUMM	ARY to	<u>r DA 2</u>	Flow Sun	nmary						
Segment #1 Sheet Flow	Segment #2 Shallow Concent	Segment #3 Channelized		Area acres	Tc hours	Cn -	Q2 cfs	Q10 cfs	Q25 cfs	Q50 cfs	Q100 cfs	Segment #1	
viannings "n" _ength (ft) Slope (%)	Length (ft)	Length (ft)	0	2.96	0.0833	/9	0.3	10.3	16	17.8	22.9	Mannings "n" Length (ft)	
2-yr, 24 hr rainfall segment total	segment total	Velocity (fps) segment total	0.0833	Impervio	us Cover	1%						Slope (%) 2-yr, 24 hr rainfall	
JSER DEFINED		time of conc.(hrs)	0.083	SCS La	g Time (.	6 x Tc)=	0.05					segment total USER DEFINED	0.083
	TR-55 SCS L ~~ Time (HYDROLOGIC	SUMM	ARY fo	r DA 3	Flow S	1mary						
Segment #1 Sheet Flow	Segment #2 Shallow Concent	Segment #3 Channelized		Area acres	Tc hours	Cn -	Q2 cfs	Q10 cfs	Q25 cfs	Q50 cfs	Q100 cfs		
Mannings "n" _ength (ft)	Unpaved Length (ft)	Mannings "n" Length (ft)	0	0.82	0.0833	79	1.7	2.8	4.3	4.8	6.2	Segment #1 Sheet Flow	
Slope (%) 2-yr, 24 hr rainfall	Slope (%)	Slope (%) Velocity (fps)	0	1	6	0.0%						Mannings "n" Length (ft) Slope (%)	
JSER DEFINED	segmeni iolai	time of conc.(hrs)	0.0833	SCS La	g Time (.	6 x Tc]=	0.05					2-yr, 24 hr rainfall segment total	0.08333
		HYDROLOGIC	SUMM	ARY fo	r DA 4							USER DEFINED	
Segment #1	TR-55 SCS Lag Time (Segment #2	hours) Segment #3		Area	Tc	Flow Sun Cn	Q2	Q10	Q25	Q50	Q100		
Mannings "n"	Unpaved	Mannings "n"		0.75	5 0.0833	79	1.1	1.8	2.9	3.2	4.1	Segment #1 Sheet Flow	
enain (II)	Slope (%)	Slope (%)										A A second second line II	
Slope (%) 2-yr, 24 hr rainfall		Velocity (fps)										Length (ft)	
Slope (%) 2-yr, 24 hr rainfall segment total JSER DEFINED	segment total	Velocity (fps) segment total <i>time of conc.(hrs)</i>	0.0833 0.083	Impervio SCS Lag	us Cover g Time (.	0% 6 x TcJ=	0.05	· · · · · · · · · · · · · · · · · · ·				Length (ft) Slope (%) 2-yr, 24 hr rainfall	0.08
Slope (%) 2-yr, 24 hr rainfall segment total JSER DEFINED	segment total	Velocity (fps) segment total time of conc.(hrs) HYDROLOGIC	0.0833 0.083	Impervio SCS La ARY fo	us Cover g Time (. r DA 5	0% 6 x TcJ=	0.05					Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED	0.083
Segment #1	TR-55 SCS Lag Time (Segment #2	Velocity (fps) segment total time of conc.(hrs) HYDROLOGIC hours) Segment #3	0.0833 0.083	Impervio SCS Lag ARY fo Area	us Cover g Time (. r DA 5	0% 6 x TcJ= Flow Sun Cn	0.05	Q10	Q25	Q50	Q100	Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED	0.083
Segment #1 Sheet Flow Mannings "n" ength (ft)	TR-55 SCS Lag Time (Segment #2 Shallow Concent Unpaved Length (ft)	Velocity (fps) segment total time of conc.(hrs) HYDROLOGIC hours) Segment #3 Channelized Mannings "n"	0.0833 0.083 5 SUMM	Impervio SCS Lag ARY for Area acres 0.1	us Cover g Time (. r DA 5 Tc hours 0.0833	0% 6 x TcJ= Flow Sun Cn - 79	0.05	Q10 cfs 0.3	Q25 cfs 0.5	Q50 cfs 0.6	Q100 cfs 0.8	Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED Segment #1 Sheet Flow	0.083
Segment #1 Sheet Flow Annings "n" Length (ft) Sheet flow Mannings "n" Length (ft) Shope (%) 2-yr, 3 hr rainfall	TR-55 SCS Lag Time (Segment #2 Shallow Concent Unpaved Length (ft) Slope (%)	Velocity (fps) segment total <i>time of conc.(hrs)</i> HYDROLOGIC hours) Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps)	0.0833 0.083 550000 550000 550000 550000 550000 550000 550000 550000 550000 550000 55000000	Impervio SCS Lag ARY fo Area acres 0.1	us Cover g Time (. r DA 5 Tc hours 0.0833	0% 6 x TcJ= Flow Sun Cn - 79	0.05	Q10 cfs 0.3	Q25 cfs 0.5	Q50 cfs 0.6	Q100 cfs 0.8	Mannings n Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED Segment #1 Sheet Flow Mannings "n" Length (ft)	0.083
Segment #1 Shope (%) 2-yr, 24 hr rainfall segment total JSER DEFINED Segment #1 Sheet Flow Mannings "n" ength (ft) Shope (%) 2-yr, 3 hr rainfall segment total JSER DEFINED	TR-55 SCS Lag Time (Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total	Velocity (fps) segment total time of conc.(hrs) HYDROLOGIC hours) Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc.(hrs)	0.0833 0.083 5 5 5 5 5 5 7 5 7 7 7 7 7 7 7 7 7 7 7	Impervio SCS Lag ARY fo Area acres 0.1 Impervio SCS Lag	us Cover g Time (. r DA 5 Tc hours 0.0833 us Cover g Time (.	0% 6 x TcJ= Flow Sun Cn - 79 79 0% 6 x TcJ=	0.05	Q10 cfs 0.3	Q25 cfs 0.5	Q50 cfs 0.6	Q100 cfs 0.8	Mannings n Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED Segment #1 Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 24 hr rainfall	0.08
Segment #1 Shope (%) 2-yr, 24 hr rainfall Segment total JSER DEFINED Segment #1 Sheet Flow Mannings "n" .ength (ft) Slope (%) 2-yr, 3 hr rainfall segment total JSER DEFINED	TR-55 SCS Lag Time (Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total	Velocity (fps) segment total <i>time of conc.(hrs)</i> HYDROLOGIC hours) Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(hrs)</i> HYDROLOGIC S	0.0833 0.083 5 SUMM 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	Impervio SCS Lag ARY fo Area acres 0.1 Impervio SCS Lag	us Cover g Time (. r DA 5 Tc hours 0.0833 us Cover g Time (. EX. DA	0% 6 x TcJ= Flow Sun Cn - 79 0% 6 x TcJ= 7	0.05	Q10 cfs 0.3	Q25 cfs 0.5	Q50 cfs 0.6	Q100 cfs 0.8	Mannings n Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED Segment #1 Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED	0.083
Segment #1 Shope (%) 2-yr, 24 hr rainfall Segment total JSER DEFINED Segment #1 Sheet Flow Mannings "n" .ength (ft) Slope (%) 2-yr, 3 hr rainfall Segment total JSER DEFINED Segment #1 Segment #1	TR-55 SCS Lag Time (Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total TR-55 SCS Lag Time (Segment #2	Velocity (fps) segment total <i>time of conc.(hrs)</i> HYDROLOG/C hours) Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(hrs)</i> HYDROLOG/C S hours) Segment #3	0.0833 0.083 5 5 5 5 5 5 5 7 5 7 7 7 7 7 7 7 7 7 7	Impervio SCS Lag ARY fo Area acres 0.1 Impervio SCS Lag RY for L Area	us Cover g Time (. r DA 5 Tc hours 0.0833 us Cover g Time (. EX. DA Tc	0% 6 x TcJ= Flow Sum Cn - 79 0% 6 x TcJ= 7 Flow Sum Cn	0.05	Q10 cfs 0.3	Q25 cfs 0.5	Q50 cfs 0.6	Q100 cfs 0.8	Mannings n Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED Segment #1 Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED	0.083
Segment #1 Sheet Flow Mannings "n" Segment total JSER DEFINED Segment #1 Sheet Flow Mannings "n" Segment total JSER DEFINED Segment #1 Sheet Flow Mannings "n" Segment #1 Sheet Flow Mannings "n"	TR-55 SCS Lag Time (Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total TR-55 SCS Lag Time (Segment #2 Shallow Concent Unpaved	Velocity (fps) segment total <i>time of conc.(hrs)</i> HYDROLOGIC hours) Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(hrs)</i> HYDROLOGIC S hours) Segment #3 Channelized Mannings "n"	0.0833 0.083 0.083 0.083 0.083 0.083 0.083	Impervio SCS Lag ARY for Area acres 0.1 Impervio SCS Lag RY for L Area acres 2.86	us Cover g Time (. r DA 5 Tc hours 0.0833 us Cover g Time (. EX. DA Tc hours 5 0.0833	0% 6 x Tc]= Flow Sun Cn - 79 0% 6 x Tc]= 7 Flow Sun Cn - 79	0.05 mary Q2 cfs 0.2 0.05 0.05	Q10 cfs 0.3 Q10 cfs 12.2	Q25 cfs 0.5 Q25 cfs 17.8	Q50 cfs 0.6 Q50 cfs 19.9	Q100 cfs 0.8 Q100 cfs 23.8	Mannings n Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED Segment #1 Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED Segment #1	0.08
Segment #1 Shope (%) 2-yr, 24 hr rainfall Segment total JSER DEFINED Segment #1 Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 3 hr rainfall Segment total JSER DEFINED Segment #1 Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 4 hr rainfall Slope (%) 2-yr, 4 hr rainfall	TR-55 SCS Lag Time (Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total TR-55 SCS Lag Time (Segment #2 Shallow Concent Unpaved Length (ft) Slope (%)	Velocity (fps) segment total <i>time of conc.(hrs)</i> <i>HYDROLOGIC</i> hours) Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(hrs)</i> <i>HYDROLOGIC S</i> hours) Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps)	0.0833 0.083 5 5 5 5 5 5 5 5 7 7 7 7 7 7 7 7 7 7 7	Impervio SCS Lag ARY fo Area acres 0.1 Impervio SCS Lag RY for L Area acres 2.86	us Cover g Time (. r DA 5 Tc hours 0.0833 us Cover g Time (. EX. DA EX. DA Tc hours 0.0833	0% 6 x TcJ= Flow Sun Cn 79 6 x TcJ= 7 Flow Sun Cn - 79 79	0.05	Q10 cfs 0.3 Q10 cfs 12.2	Q25 cfs 0.5 Q25 cfs 17.8	Q50 cfs 0.6 Q50 cfs 19.9	Q100 cfs 0.8 Q100 cfs 23.8	Mannings n Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED Segment #1 Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED Segment #1 Sheet Flow Mannings "n" Length (ft)	0.083
Segment #1 Sheet Flow Mannings "n" Segment total JSER DEFINED Segment #1 Sheet Flow Mannings "n" Segment total JSER DEFINED Segment #1 Sheet Flow Mannings "n" Segment #1 Sheet Flow Mannings "n" Shee	TR-55 SCS Lag Time (Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total TR-55 SCS Lag Time (Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total	Velocity (fps) segment total <i>time of conc.(hrs)</i> HYDROLOG/C hours) Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(hrs)</i> HYDROLOG/C S hours) Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(hrs)</i>	0.0833 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.0833 0.083 0.0833	Impervio SCS Lag ARY fo Area acres 0.1 Impervio SCS Lag RY for L Area acres 2.86	us Cover g Time (. r DA 5 Tc hours 0.0833 us Cover g Time (. EX. DA Tc hours 5 0.0833 us Cover g Time (.	0% 6 x Tc]= Flow Sun Cn - 79 0% 6 x Tc]= 7 Flow Sun Cn - 79 79 83% 6 x Tc]=	0.05	Q10 cfs 0.3 Q10 cfs 12.2	Q25 cfs 0.5 Q25 cfs 17.8	Q50 cfs 0.6 Q50 cfs 19.9	Q100 cfs 0.8 Q100 cfs 23.8	Mannings n Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED Segment #1 Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED Segment #1 Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 24 hr rainfall	0.083
Segment #1 Sheet Flow Segment total Segment #1 Sheet Flow Mannings "n" Segment total USER DEFINED Solope (%) 2-yr, 3 hr rainfall Segment total USER DEFINED Segment #1 Sheet Flow Mannings "n" Sheet F	TR-55 SCS Lag Time (Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) Segment total TR-55 SCS Lag Time (Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) Slope (%) Segment total	Velocity (fps) segment total fime of conc.(hrs) HYDROLOGIC hours) Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc.(hrs) HYDROLOGIC S hours) Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc.(hrs)	0.0833 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083	Impervio SCS Lag ARY fo Area acres 0.1 Impervio SCS Lag RY for L Area acres 2.86 Impervio SCS Lag	us Cover g Time (. r DA 5 Tc hours 0.0833 us Cover g Time (. EX. DA to cover g Time (. bours to cover g Time (.	0% 6 x TcJ= Flow Sun Cn - 79 6 x TcJ= 7 Flow Sun Cn - 79 79 83% 6 x TcJ= 83%	0.05	Q10 cfs 0.3 Q10 cfs 12.2	Q25 cfs 0.5 Q25 cfs 17.8	Q50 cfs 0.6 Q50 cfs 19.9	Q100 cfs 0.8 Q100 cfs 23.8	Mannings n Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 24 hr rainfall Segment #1 Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED	0.083
Segment #1 Sheet Flow Segment #1 Sheet Flow Mannings "n" Segment total JSER DEFINED Sope (%) 2-yr, 3 hr rainfall JSER DEFINED Segment #1 Sheet Flow Mannings "n" Segment #1	TR-55 SCS Lag Time (Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total TR-55 SCS Lag Time (Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total TR-55 SCS Lag Time (Segment total	Velocity (fps) segment total <i>time of conc.(hrs)</i> HYDROLOGIC hours) Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(hrs)</i> HYDROLOGIC S hours) Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(hrs)</i> HYDROLOGIC S hours)	0.0833 0.083 0.083 0.083 0.083 0.0833 0.083 0.0833 0.0833 0.0833 0.0833	Impervio SCS Lag ARY fo Area acres 0.1 Impervio SCS Lag RY for L Area acres 2.86 Impervio SCS Lag RY for L	us Cover g Time (. r DA 5 Tc hours 0.0833 us Cover g Time (. EX. DA L Tc hours 0.0833 us Cover g Time (. EX. DA	0% 6 x TcJ= Flow Sun Cn - 79 6 x TcJ= 7 Flow Sun Cn - 79 83% 6 x TcJ= 2 Flow Sun Cn	0.05	Q10 cfs 0.3 Q10 cfs 12.2	Q25 cfs 0.5 Q25 cfs 17.8	Q50 cfs 0.6 Q50 cfs 19.9	Q100 cfs 0.8 Q100 cfs 23.8 Q100	Mannings n Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED Segment #1 Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 24 hr rainfall segment #1 Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED	0.083
Annings "n" Segment #1 Segment #1 Sheet Flow Mannings "n" Segment #1 Sheet Flow Mannings "n" Segment #1 Sheet Flow Mannings "n" Segment #1 Sheet Flow Mannings "n" Sheet Flow Mannings "n" Sheet Flow Mannings "n" Segment #1 Sheet Flow Mannings "n" Segment #1 Sheet Flow Mannings "n" Sheet Flow Mannings "n" Sheet Flow Mannings "n" Sheet Flow Mannings "n" Sheet Flow Mannings "n" Sheet Flow Mannings "n"	TR-55 SCS Lag Time (Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total TR-55 SCS Lag Time (Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total TR-55 SCS Lag Time (Segment total	Velocity (fps) segment total <i>time of conc.(hrs)</i> HYDROLOGIC hours) Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(hrs)</i> HYDROLOGIC S hours) Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(hrs)</i> HYDROLOGIC S hours) Segment total <i>time of conc.(hrs)</i> HYDROLOGIC S hours) Segment #3 Channelized	0.0833 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083	Impervio SCS Lag ARY fo Area acres 0.1 Impervio SCS Lag RY for L Area acres 2.86 SCS Lag RY for L Area acres 2.86 Area acres 0.16	us Cover g Time (. r DA 5 Tc hours 0.0833 us Cover g Time (. EX. DA EX. DA us Cover g Time (. bours o 0.0833 us Cover g Time (. bours o 0.0833	0% 6 x TcJ= Flow Sum Cn - 79 6 x TcJ= 7 79 79 79 79 83% 6 x TcJ= 2 Flow Sum Cn Cn Cn 79	0.05 mary Q2 cfs 0.2 0.05 0.05 0.05 0.05 0.05	Q10 cfs 0.3 Q10 cfs 12.2 Q10 cfs 0.5	Q25 cfs 0.5 Q25 cfs 17.8 Q25 cfs 17.8 Q25 cfs 0.8	Q50 cfs 0.6 Q50 cfs 19.9 Q50 cfs 0.9	Q100 cfs 0.8 Q100 cfs 23.8 Q100 cfs 1.2	Mannings n Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED Segment #1 Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED Segment #1 Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED Segment total USER DEFINED	0.083
Segment #1 Sheet Flow Mannings "n" Segment total JSER DEFINED Segment #1 Sheet Flow Mannings "n" Sheet Flow Sheet Flow Sheet Flow Mannings "n" Sheet Flow Sheet Flow Mannings "n" Sheet Flow Sheet Flow Mannings "n" Sheet Flow Mannings "n" Sheet Flow	TR-55 SCS Lag Time (Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) TR-55 SCS Lag Time (Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) Slope (%) TR-55 SCS Lag Time (Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) TR-55 SCS Lag Time (Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) TR-55 SCS Lag Time (Segment #2 Shallow Concent Unpaved Length (ft) Slope (%)	Velocity (fps) segment total <i>time of conc.(hrs)</i> HYDROLOGIC hours) Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(hrs)</i> HYDROLOGIC S hours) Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(hrs)</i> HYDROLOGIC S hours) Segment total <i>time of conc.(hrs)</i> HYDROLOGIC S hours) Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (ft) Slope (%)	0.0833 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083	Impervio SCS Lag ARY fo Area acres 0.1 Impervio SCS Lag RY for L Area acres 2.86 Impervio SCS Lag RY for L Area acres 0.16	us Cover g Time (. r DA 5 Tc hours 0.0833 us Cover g Time (. EX. DA Tc hours 0.0833 us Cover g Time (. EX. DA Tc hours 0.0833	0% 6 x TcJ= Flow Sun Cn - 79 0% 6 x TcJ= 79 79 79 83% 6 x TcJ= 2 Flow Sun Cn - 2 Flow Sun Cn 79 79	0.05 mary Q2 cfs 0.2 0.05 0.05 0.05 0.05	Q10 cfs 0.3 Q10 cfs 12.2 Q10 cfs 0.5	Q25 cfs 0.5 Q25 cfs 17.8 Q25 cfs 17.8	Q50 cfs 0.6 Q50 cfs 19.9 Q50 cfs 0.9	Q100 cfs 0.8 Q100 cfs 23.8 Q100 cfs 1.2	Mannings n Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 24 hr rainfall segment #1 Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED Segment #1 Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 24 hr rainfall segment #1 Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED Segment #1 Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED	0.083
Segment #1 Sheet Flow Mannings "n" Segment total JSER DEFINED Segment #1 Sheet Flow Mannings "n" Segment total JSER DEFINED Segment total JSER DEFINED Segment #1 Sheet Flow Mannings "n" Segment total JSER DEFINED Segment #1 Sheet Flow Mannings "n" Segment total JSER DEFINED Segment #1 Sheet Flow Mannings "n" Segment total SER DEFINED SEGMENT #1 Sheet Flow Mannings "n" Segment total SER DEFINED SEGMENT #1 Sheet Flow Mannings "n" Segment total SER DEFINED SEGMENT #1 Sheet Flow Mannings "n" Segment total SER DEFINED SEGMENT #1 Sheet Flow Mannings "n" Segment total SER DEFINED	TR-55 SCS Lag Time (Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total TR-55 SCS Lag Time (Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) Slope (%) TR-55 SCS Lag Time (Segment total Segment total TR-55 SCS Lag Time (Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) TR-55 SCS Lag Time (Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) Slope (%)	Velocity (fps) segment total <i>time of conc.(hrs)</i> HYDROLOGIC hours) Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(hrs)</i> HYDROLOGIC S hours) Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(hrs)</i> HYDROLOGIC S hours) Segment total time of conc.(hrs) HYDROLOGIC S hours) Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total	0.0833 0.083 0.083 0.083 0.083 0.0833 0.083 0.0833 0.0833 0.0833 0.0833 0.0833 0.0833 0.0833	Impervio SCS Lag ARY fo Area acres 0.1 Impervio SCS Lag RY for L Area acres 2.86 Impervio SCS Lag RY for L Area acres 0.16 Impervio SCS Lag	us Cover g Time (. r DA 5 Tc hours 0.0833 us Cover g Time (. EX. DA EX. DA Solutions 0.0833 us Cover g Time (. EX. DA L Tc hours 0.0833 US Cover g Time (. EX. DA	0% $6 \times TcJ =$ Flow Sun Cn - 79 $6 \times TcJ =$ 7 Flow Sun Cn - 79 6 × TcJ = 2 Flow Sun Cn - 79 83% 6 × TcJ = 2 Flow Sun Cn - 79 0% 6 × TcJ = 0%	0.05	Q10 cfs 0.3 Q10 cfs 12.2 Q10 cfs 0.5	Q25 cfs 0.5 Q25 cfs 17.8 Q25 cfs 17.8 Q25 cfs 0.8	Q50 cfs 0.6 Q50 cfs 19.9 Q50 cfs 0.9	Q100 cfs 0.8 Q100 cfs 23.8 Q100 cfs 1.2	Mannings n Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 24 hr rainfall segment #1 Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED Segment total USER DEFINED Sheet Flow Mannings "n" Length (ft) Sheet Flow Mannings "n" Length (ft) Slope (%) Solope (%) Solope (%)	0.083
Length (II) Slope (%) 2-yr, 24 hr rainfall segment total JSER DEFINED Segment #1 Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 3 hr rainfall segment total JSER DEFINED Segment #1 Sheet Flow Mannings "n" Length (ft) Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total JSER DEFINED Segment #1 Sheet Flow Mannings "n" Length (ft) Sheet Flow<	TR-55 SCS Lag Time (Segment total Unpaved Length (ft) Slope (%) segment total TR-55 SCS Lag Time (Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total TR-55 SCS Lag Time (Segment total Slope (%) Slope (%) segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total	Velocity (fps) segment total time of conc.(hrs) HYDROLOGIC hours) Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc.(hrs) HYDROLOGIC S hours) Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc.(hrs) HYDROLOGIC S hours) Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc.(hrs) Slope (%) Velocity (fps) segment total time of conc.(hrs) <t< td=""><td>0.0833 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083</td><td>Impervio SCS Lag ARY fo Area acres 0.1 Impervio SCS Lag RY for L Area acres 2.86 Impervio SCS Lag RY for L Area acres 0.16 Impervio SCS Lag RY for L Area acres 0.16 CSC Lag RY for L Area acres 0.16 CSC Lag CSC Lag C</td><td>us Cover g Time (. r DA 5 Tc hours 0.0833 us Cover g Time (. EX. DA Tc hours 0.0833 us Cover g Time (. EX. DA Tc hours 0.0833 us Cover g Time (. EX. DA</td><td>0% 6 x TcJ= Flow Sun Cn - 79 6 x TcJ= 7 79 79 83% 6 x TcJ= 2 Flow Sun Cn - 79 83% 6 x TcJ= 2 Flow Sun Cn Cn - 79 6 x TcJ= 79</td><td>0.05</td><td>Q10 cfs 0.3 Q10 cfs 12.2 Q10 cfs 0.5</td><td>Q25 cfs 0.5 Q25 cfs 17.8 Q25 cfs 17.8</td><td>Q50 cfs 0.6 Q50 cfs 19.9 Q50 cfs 0.9</td><td>Q100 cfs 0.8 Q100 cfs 23.8 Q100 cfs 1.2</td><td>Mannings n Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 24 hr rainfall segment #1 Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED Segment #1 Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED Segment #1 Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 24 hr rainfall segment #1 Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total LISER DEFINED</td><td>0.083</td></t<>	0.0833 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083	Impervio SCS Lag ARY fo Area acres 0.1 Impervio SCS Lag RY for L Area acres 2.86 Impervio SCS Lag RY for L Area acres 0.16 Impervio SCS Lag RY for L Area acres 0.16 CSC Lag RY for L Area acres 0.16 CSC Lag CSC Lag C	us Cover g Time (. r DA 5 Tc hours 0.0833 us Cover g Time (. EX. DA Tc hours 0.0833 us Cover g Time (. EX. DA Tc hours 0.0833 us Cover g Time (. EX. DA	0% 6 x TcJ= Flow Sun Cn - 79 6 x TcJ= 7 79 79 83% 6 x TcJ= 2 Flow Sun Cn - 79 83% 6 x TcJ= 2 Flow Sun Cn Cn - 79 6 x TcJ= 79	0.05	Q10 cfs 0.3 Q10 cfs 12.2 Q10 cfs 0.5	Q25 cfs 0.5 Q25 cfs 17.8 Q25 cfs 17.8	Q50 cfs 0.6 Q50 cfs 19.9 Q50 cfs 0.9	Q100 cfs 0.8 Q100 cfs 23.8 Q100 cfs 1.2	Mannings n Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 24 hr rainfall segment #1 Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED Segment #1 Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED Segment #1 Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 24 hr rainfall segment #1 Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total LISER DEFINED	0.083
Segment (I) Slope (%) 2-yr, 24 hr rainfall segment total JSER DEFINED Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 3 hr rainfall segment #1 Slope (%) 2-yr, 3 hr rainfall segment total JSER DEFINED Segment #1 Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 24 hr rainfall segment #1 Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 24 hr rainfall segment #1 Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total JSER DEFINED Slope (%) 2-yr, 24 hr rainfall segment total JSER DEFINED Slope (%) 2-yr, 24 hr rainfall segment total JSER DEFINED	TR-55 SCS Lag Time (Segment total Unpaved Length (ft) Slope (%) Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) Slope (%) Slope (%) Slope (%) Slope (%) Slope (%) Slope (%) Segment total TR-55 SCS Lag Time (Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) Slope (%) Sl	Velocity (fps) segment total <i>time of conc.(hrs)</i> HYDROLOGIC hours) Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(hrs)</i> HYDROLOGIC S hours) Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(hrs)</i> HYDROLOGIC S hours) Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(hrs)</i> HYDROLOGIC SU hours)	0.0833 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083	Impervio SCS Lag ARY fo Area acres 0.1 Impervio SCS Lag RY for L Area acres 2.86 Impervio SCS Lag RY for L Area acres 0.16 SCS Lag C Area acres	us Cover g Time (. r DA 5 TC hours 0.0833 us Cover g Time (. EX. DA TC hours 0.0833 us Cover g Time (. EX. DA TC hours 0.0833 us Cover g Time (. EX. DA	0% 6 x TcJ= Flow Sun Cn - 79 0% 6 x TcJ= 7 79 79 83% 6 x TcJ= 2 Flow Sun Cn - 79 79 83% 6 x TcJ= 79 79 79 6 x TcJ= 79 79 79 6 x TcJ= 79	0.05	Q10 cfs 0.3 Q10 cfs 12.2 Q10 cfs 0.5	Q25 cfs 0.5 Q25 cfs 17.8 Q25 cfs 0.8	Q50 cfs 0.6 Q50 cfs 19.9 Q50 cfs 0.9	Q100 cfs 0.8 Q100 cfs 23.8 Q100 cfs 1.2 0 0 0 0 0 0 0 0 0 0 0 0 0	Kannings n Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 24 hr rainfall segment #1 Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED Segment #1 Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED Segment #1 Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 24 hr rainfall segment #1 Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED	0.083
Segment #1 Sheet Flow Mannings "n" Segment total JSER DEFINED Sore (%) 2-yr, 24 hr rainfall Sheet Flow Mannings "n" Segment total JSER DEFINED Segment total JSER DEFINED Sore (%) 2-yr, 24 hr rainfall Segment total JSER DEFINED Segment #1 Sheet Flow Mannings "n" Segment #1 Sheet Flow	TR-55 SCS Lag Time (Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) Slope (%) Slope (%) Slope (%) Slope (%) Concent Unpaved Length (ft) Slope (%) Slope (%) Slope (%) Slope (%) Concent Unpaved Length (ft) Slope (%) Slope (%) Concent Conc	Velocity (fps) segment total <i>time of conc.(hrs)</i> HYDROLOGIC hours) Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(hrs)</i> HYDROLOGIC S hours) Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(hrs)</i> HYDROLOGIC S hours) Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(hrs)</i> HYDROLOGIC SU hours) Segment #3 Channelized Mannings "n"	0.0833 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083	Impervio SCS Lag ARY fo Area acres 0.1 Impervio SCS Lag RY for L Area acres 2.86 SCS Lag RY for L Area acres 2.86 Impervio SCS Lag Area acres 2.86 SCS Lag Area acres 2.86 SCS Lag Area acres 2.86 SCS Lag	us Cover g Time (. r DA 5 Tc hours 0.0833 us Cover g Time (. EX. DA EX. DA Cover g Time (. EX. DA US Cover g Time (. EX. DA Cover g Time (. Cover g Cover g Cover	0% 6 x TcJ= Flow Sun Cn - 79 6 x TcJ= 7 79 6 x TcJ= 2 Flow Sun Cn - 79 83% 6 x TcJ= 2 Flow Sun Cn - 79 6 x TcJ= 79 0% 6 x TcJ= 79 0% 6 x TcJ= 79 79 79 79 79 79 79 79 79 79 79 79 79	0.05	Q10 cfs 0.3 Q10 cfs 12.2 Q10 cfs 12.2 Q10 cfs 0.5	Q25 cfs 0.5 Q25 cfs 17.8 Q25 cfs 17.8 Q25 cfs 0.8	Q50 cfs 0.6 Q50 cfs 19.9 Q50 cfs 0.9 Q50 cfs 0.9	Q100 cfs 0.8 Q100 cfs 23.8 Q100 cfs 1.2 Q100 cfs 1.2 Q100 cfs 39.3	Annings n Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 24 hr rainfall segment #1 Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED Segment #1 Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINE	0.083
Length (II) Slope (%) 2-yr, 24 hr rainfall segment total JSER DEFINED Segment #1 Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 3 hr rainfall segment total JSER DEFINED Segment #1 Sheet Flow Mannings "n" Length (ft) Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total JSER DEFINED Segment #1 Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total JSER DEFINED Segment total JSER DEFINED Segment #1 Sheet Flow Mannings "n" Length (ft) Slope (%) Z-yr, 24 hr rainfall Segment #1 Sheet Flow Mannings "n"	TR-55 SCS Lag Time (Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total TR-55 SCS Lag Time (Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) Shallow Concent Unpaved Length (ft) Shallow Concent Unpaved Length (ft) Slope (%) segment total TR-55 SCS Lag Time (Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) Shallow Concent Unpaved Length (ft) Slope (%) Segment total Segment total Impoved Length (ft) Slope (%) Segment total Unpaved Length (ft) Shallow Concent Unpaved Length (ft) Shallow Concent Unpaved </td <td>Velocity (fps) segment total time of conc.(hrs) HYDROLOGIC hours) Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc.(hrs) HYDROLOGIC S hours) Segment total time of conc.(hrs) HYDROLOGIC S hours) Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc.(hrs) HYDROLOGIC S hours) Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc.(hrs) HYDROLOGIC SU hours) Segment total time of conc.(hrs) Slope (%) Velocity (fps) <</td> <td>0.0833 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083</td> <td>Impervio SCS Lag ARY fo Area acres 0.1 Impervio SCS Lag RY for L Area acres 2.86 Impervio SCS Lag RY for L Area acres 0.16 Area acres 0.16 Area acres 0.16 Area acres 0.16</td> <td>us Cover g Time (. r DA 5 Tc hours 0.0833 us Cover g Time (. EX. DA EX. DA US Cover g Time (. EX. DA EX. DA US Cover g Time (. Cover g Time</td> <td>0% 6 x TcJ= Flow Sum Cn - 79 6 x TcJ= 7 79 79 79 83% 6 x TcJ= 2 Flow Sum Cn - 79 79 83% 6 x TcJ= 2 Flow Sum Cn Cn - 79 79 0% 6 x TcJ= 79</td> <td>0.05</td> <td>Q10 cfs 0.3 Q10 cfs 12.2 Q10 cfs 0.5 Q10 cfs 0.5</td> <td>Q25 cfs 0.5 Q25 cfs 17.8 Q25 cfs 0.8 Q25 cfs 0.8 Q25 cfs 0.8</td> <td>Q50 cfs 0.6 Q50 cfs 19.9 Q50 cfs 0.9 Q50 cfs 0.9</td> <td>Q100 cfs 0.8 Q100 cfs 23.8 Q100 cfs 1.2 Q100 cfs 39.3</td> <td>Mannings n Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 24 hr rainfall segment #1 Slope (%) 2-yr, 24 hr rainfall segment #1 Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 24 hr rainfall segment #1 Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED Segment #1 Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED Segment #1 Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total</td> <td>0.083</td>	Velocity (fps) segment total time of conc.(hrs) HYDROLOGIC hours) Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc.(hrs) HYDROLOGIC S hours) Segment total time of conc.(hrs) HYDROLOGIC S hours) Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc.(hrs) HYDROLOGIC S hours) Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc.(hrs) HYDROLOGIC SU hours) Segment total time of conc.(hrs) Slope (%) Velocity (fps) <	0.0833 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083 0.083	Impervio SCS Lag ARY fo Area acres 0.1 Impervio SCS Lag RY for L Area acres 2.86 Impervio SCS Lag RY for L Area acres 0.16 Area acres 0.16 Area acres 0.16 Area acres 0.16	us Cover g Time (. r DA 5 Tc hours 0.0833 us Cover g Time (. EX. DA EX. DA US Cover g Time (. EX. DA EX. DA US Cover g Time (. Cover g Time	0% 6 x TcJ= Flow Sum Cn - 79 6 x TcJ= 7 79 79 79 83% 6 x TcJ= 2 Flow Sum Cn - 79 79 83% 6 x TcJ= 2 Flow Sum Cn Cn - 79 79 0% 6 x TcJ= 79	0.05	Q10 cfs 0.3 Q10 cfs 12.2 Q10 cfs 0.5 Q10 cfs 0.5	Q25 cfs 0.5 Q25 cfs 17.8 Q25 cfs 0.8 Q25 cfs 0.8 Q25 cfs 0.8	Q50 cfs 0.6 Q50 cfs 19.9 Q50 cfs 0.9 Q50 cfs 0.9	Q100 cfs 0.8 Q100 cfs 23.8 Q100 cfs 1.2 Q100 cfs 39.3	Mannings n Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 24 hr rainfall segment #1 Slope (%) 2-yr, 24 hr rainfall segment #1 Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 24 hr rainfall segment #1 Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED Segment #1 Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED Segment #1 Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total	0.083
Segment (II) Slope (%) 2-yr, 24 hr rainfall regment total JSER DEFINED Segment #1 Sheet Flow Mannings "n" .ength (ft) Slope (%) 2-yr, 3 hr rainfall segment total JSER DEFINED Segment #1 Shope (%) 2-yr, 3 hr rainfall segment total JSER DEFINED Sheet Flow Mannings "n" ength (ft) Slope (%) 2-yr, 24 hr rainfall segment #1 Sheet Flow Mannings "n" ength (ft) Slope (%) 2-yr, 24 hr rainfall segment #1 Sheet Flow Mannings "n" ength (ft) Slope (%) 2-yr, 24 hr rainfall segment #1 Sheet Flow Mannings "n" ength (ft) Slope (%) 2-yr, 24 hr rainfall segment #1 Sheet Flow	TR-55 SCS Lag Time (Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment #2 Shallow Concent Unpaved Length (ft) Slope (%) Segment total Unpaved Length (ft) Shallow Concent Unpaved Length (ft) Shallow Concent Unpaved Length (ft) Slope (%) segment total Shallow Concent Unpaved Length (ft) Slope (%) Shallow Concent Unpaved Length (ft) Slope (%) Segment total Shallow Concent Unpaved Length (ft) Slope (%) Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) Slope (%) Slope (%) Slope (%) Slope (%) Slope	Velocity (fps) segment total time of conc.(hrs) HYDROLOGIC hours) Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc.(hrs) HYDROLOGIC S hours) Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc.(hrs) Slope (%) Velocity (fps) segment total time of conc.(hrs) hours) Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc.(hrs) HYDROLOGIC SU hours) Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Veloc	0.0833 0.083	Impervio SCS Lag ARY fo Area acres 0.1 SCS Lag RY for L Area acres 2.86 Impervio SCS Lag RY for L Area acres 0.16 SCS Lag C for EX	us Cover g Time (. r DA 5 Tc hours 0.0833 us Cover g Time (. EX. DA EX. DA EX. DA EX. DA Cover g Time (. EX. DA Cover g Time (. Cover g Ti	0% 6 x TcJ= Flow Sun Cn - 79 6 x TcJ= 7 Flow Sun Cn - 79 83% 6 x TcJ= 2 Flow Sun Cn - 79 83% 6 x TcJ= 79 83% 6 x TcJ= 79 79 83% 6 x TcJ= 79 79 83% 6 x TcJ= 79 79 83% 6 x TcJ= 79 83% 6 x TcJ= 79 83% 6 x TcJ= 79 83% 6 x TcJ= 79 83% 6 x TcJ= 79 83% 6 x TcJ= 79 79 83% 6 x TcJ= 79 79 79 79 79 79 79 79 79 79 79 79 79	0.05	Q10 cfs 0.3 Q10 cfs 12.2 Q10 cfs 0.5 0.5 Q10 cfs 19.1	Q25 cfs 0.5 Q25 cfs 17.8 Q25 cfs 0.8 Q25 cfs 0.8	Q50 cfs 0.6 Q50 cfs 19.9 Q50 cfs 0.9 Q50 cfs 31.9	Q100 cfs 0.8 Q100 cfs 23.8 Q100 cfs 1.2 Q100 cfs 39.3	Mannings n Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 24 hr rainfall segment #1 Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED Segment #1 Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED Segment #1 Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 24 hr rainfall segment #1 Sheet Flow Mannings "n" Length (ft) Slope (%) 2-yr, 24 hr rainfall segment total USER DEFINED Segment #1 Sheet Flow Mannings "n" Length (ft) Slope (%)	0.083

	<u>D</u>	EVELOPE	D CO	NDI		<u>s</u>					
	H TR-55 SCS Lag Time (hours	YDROLOGIC	C SUMN	NARY to	or DA i	A Flow Sum	mary				
	Segment #2 Shallow Concent	Segment #3 Channelized	0	Area acres	Tc hours	Cn - 70	Q2 cfs	Q10 cfs 3.8	Q25 cfs	Q50 cfs	Q100 cfs
	Length (ft) Slope (%)	Length (ft) Slope (%)	0	0.72	0.000		2.0	0.0	0.0	0.2	7.0
83	segment total	Velocity (fps) segment total	0	Imperviou	s Cover	63%					
		fime of conc.(h	0.083	SCS Lag	Time (.e	5 x 1c)=	0.0498				
	H TR-55 SCS Lag Time (hours	YDROLOGIC	SUMN	IARY to	or DA I	Flow Sum	mary				
	Segment #2 Shallow Concent	Segment #3 Channelized		Area acres	Tc hours	Cn -	Q2 cfs	Q10 cfs	Q25 cfs	Q50 cfs	Q100 cfs
	Unpaved Length (ft)	Mannings "n" Length (ft)	0	0.35	0.083	79	1.1	1.4	2.1	2.4	2.9
0	Slope (%)	Slope (%) Velocity (fps)	0			(00)					
83	segment total	time of conc.(h	0.083	SCS Lag	Time (68% 6 x TcJ=	0.0498				
	Н	YDROLOGIC	SUMN	1ARY fo	or DA i	'C					
	TR-55 SCS Lag Time (hours Segment #2 Shallow Concent) Segment #3 Chappelized		Area	Tc	Flow Sum Cn	Mary Q2 cfs	Q10	Q25	Q50	Q100
	Unpaved Length (ft)	Mannings "n" Length (ft)	0	0.05	0.083	79	0.1	0.2	0.3	0.3	0.4
	Slope (%)	Slope (%) Velocity (fps)	0								
83	segment total	time of conc.(h	0.083	SCS Lag	Time (0% 5 x TcJ=	0.0498				
	Н	YDROLOGIC	SUMN	1ARY fo	or DA i	D				1	
	TR-55 SCS Lag Time (hours Segment #2	5) Segment #3		Area	Tc	Flow Sum Cn	mary Q2	Q10	Q25	Q50	Q100
	Unpaved Lenath (ft)	Mannings "n" Lenath (ft)	0	0.24	0.083	79	0.7	1	1.5	1.6	2
	Slope (%)	Slope (%) Velocity (fps)	0								
83	segment total	segment total time of conc.(h	0 0.083	Imperviou SCS Lag	s Cover	89% 5 x TcJ=	0.0498				
						0					
	TR-55 SCS Lag Time (hours))	_ <u>50M</u>	MARY	or DA	Z Flow Sum	mary				
	Segment #2 Shallow Concent	Segment #3 Channelized	0	Area acres	hours	- 79	cfs 5.4	Cfs 8.7	Q25 cfs 13.6	cfs	cfs
	Length (ft) Slope (%)	Length (ft) Slope (%)	0								
33	segment total	Velocity (fps) segment total	0	Imperviou	is Cover	1%	0.05				
			0.083		(D)	o x I c =	0.05				
	F TR-55 SCS Lag Time (hours	i)	_ SUM	MARY	for DA	3 Flow Sum	mary				
	Segment #2 Shallow Concent	Segment #3 Channelized	0	Area acres	Tc hours	Cn - 70	Q2 cfs	Q10 cfs 2 3	Q25 cfs	Q50 cfs	Q100 cfs
	Length (ft) Slope (%)	Length (ft) Slope (%)	0	0.07	0.000		1.4	2.0	0.0	0.7	
		Velocity (fps)	0								
83	segment total	segment total	0	Imperviou	s Cover	8%	0.0400				
83	segment total	segment total	0 0.083	Imperviou SCS Lag	Time (8% 5 x TcJ=	0.0498				
83	TR-55 SCS Lag Time (hours	segment total time of conc.(h YDROLOGIC	0 0.083 5 SUMN	Imperviou SCS Lag	ns Cover Time (or DA 4	8% 5 x TcJ= 1A Flow Sum	0.0498	0.12	0	0.00	0
83	H TR-55 SCS Lag Time (hours Segment #2 Shallow Concent	segment total <i>time of conc.(h</i> <i>YDROLOGIC</i>) Segment #3 Channelized Mannings "n"	0 0.083	Imperviou SCS Lag NARY fo Area acres 0.57	or DA 4 Time (Tc hours 0.083	8% 5 x TcJ= 1A Flow Sum Cn - 79	0.0498 mary Q2 cfs 1.2	Q10 cfs 2	Q25 cfs 3.1	Q50 cfs 3.4	Q100 cfs 4.3
83	H TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%)	segment total time of conc.(fr YDROLOGIC) Segment #3 Channelized Mannings "n" Length (ft) Slope (%)	0 0.083 5 SUMA 0 0 0	Imperviou SCS Lag ARY fc Area acres 0.57	Time (.0 Time (.0 Tr DA 4 Tc hours 0.083	8% 5 x TcJ= 79	0.0498 mary Q2 cfs 1.2	Q10 cfs 2	Q25 cfs 3.1	Q50 cfs 3.4	Q100 cfs 4.3
83	H TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total	segment total <i>time of conc.(h</i> <i>YDROLOGIC</i>) Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc (h</i>	0 0.083 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	Imperviou SCS Lag ARY fc Area acres 0.57 Imperviou	Time (.e or DA 4 Tc hours 0.083	8% 5 x Tc)= 7A Flow Sum Cn - 79 79	0.0498 mary Q2 cfs 1.2	Q10 cfs 2	Q25 cfs 3.1	Q50 cfs 3.4	Q100 cfs 4.3
83	H TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total	segment total time of conc.(fr YDROLOGIC) Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc.(fr	0 0.083 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	Imperviou SCS Lag ARY fc Area acres 0.57 Imperviou SCS Lag	Time (Time (Tc hours 0.083	8% 5 x TcJ= 79 0% 5 x TcJ=	0.0498 mary Q2 cfs 1.2 0.0498	Q10 cfs 2	Q25 cfs 3.1	Q50 cfs 3.4	Q100 cfs 4.3
83	H TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total H TR-55 SCS Lag Time (hours	segment total <i>time of conc.(h</i> <i>YDROLOGIC</i>) Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>YDROLOGIC</i>)	0 0.083 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	Imperviou SCS Lag ARY fc Area acres 0.57 Imperviou SCS Lag	Trime (.e or DA 4 Tc hours 0.083	8% $5 \times Tc) =$ $7A$ Flow Sum Cn - 79 0% $5 \times Tc) =$ $7B$ Flow Sum	0.0498 mary Q2 cfs 1.2 0.0498	Q10 cfs 2	Q25 cfs 3.1	Q50 cfs 3.4	Q100 cfs 4.3
83	H TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total H TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Unpaved	segment total time of conc.(fr YDROLOGIC) Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc.(fr YDROLOGIC) Segment #3 Channelized Mannings "n"	0 0.083 5 SUMM 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	Imperviou SCS Lag ARAY fo Area acres 0.57 Imperviou SCS Lag ARAY fo Area acres 0.26	Time (.e or DA 2 Tc hours 0.083 0.083 0.083 0.083	8% 5 x Tc)= 7A Flow Sum Cn 5 x Tc)= 79 5 x Tc)= 79 Flow Sum Cn - 79	0.0498 mary Q2 cfs 1.2 0.0498 0.0498 mary Q2 cfs 0.6	Q10 cfs 2 Q10 cfs 1	Q25 cfs 3.1 Q25 cfs 1.5	Q50 cfs 3.4 Q50 cfs 1.6	Q100 cfs 4.3 Q100 cfs 2
83	H TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total H TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%)	segment total time of conc.(h YDROLOGIC Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc.(h YDROLOGIC Segment #3 Channelized Mannings "n" Length (ft) Slope (%)	0 0.083 5 SUMM 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	Imperviou SCS Lag ARAY fo Area acres 0.57 Imperviou SCS Lag AARY fo Area acres 0.26	Trime (.e or DA 4 To hours 0.083 0.083 0.083 0.083	8% 5 x Tc)= 7A Flow Sum Cn 5 x Tc)= 79 Flow Sum Cn - 79 79	0.0498 mary Q2 cfs 1.2 0.0498 mary Q2 cfs 0.6	Q10 cfs 2 Q10 cfs 1	Q25 cfs 3.1 Q25 cfs 1.5	Q50 cfs 3.4 Q50 cfs 1.6	Q100 cfs 4.3 Q100 cfs 2
83	segment total H TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total H TR-55 SCS Lag Time (hours Segment total H TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total segment total	segment total time of conc.(fr YDROLOGIC Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc.(fr YDROLOGIC Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc.	0 0.083 5 SUMM 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	Imperviou SCS Lag ARAY fo Area acres 0.57 Imperviou SCS Lag ARAY fo Area acres 0.26	Is Cover Time (or DA 4 Tc hours 0.083 Is Cover Time (hours 0.083 0.083 0.083	8% 5 x Tc) = 7A Flow Sum Cn - 79 6 x Tc) = 79 Flow Sum Cn - 79 79	0.0498 mary Q2 cfs 1.2 0.0498 mary Q2 cfs 0.6	Q10 cfs 2 2 Q10 cfs 1	Q25 cfs 3.1 Q25 cfs 1.5	Q50 cfs 3.4 Q50 cfs 1.6	Q100 cfs 4.3 Q100 cfs 2
83	segment total H TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total H TR-55 SCS Lag Time (hours Segment total H TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total	segment total time of conc.(h YDROLOGIC Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc.(h YDROLOGIC Solution YDROLOGIC Solution Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc.(h (h) Slope (%) Velocity (fps) segment total time of conc.(h (h) Slope (%) Velocity (fps) segment total time of conc.(h (h) Slope (%) Velocity (fps) Segment total Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) Segment total time of conc.(h) (h) (h) Slope (h) Velocity (fps) Segment total (h) (h) Slope (h) (h) (h) Slope (h) (h) (h) (h) (h) (h) (h) (h)	0 0.083 0.083 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	Imperviou SCS Lag ARY fc Area acres 0.57 Imperviou SCS Lag Area acres 0.26 Imperviou SCS Lag	Trime (Time (Trime (Trime (Trime (Trime (Trime (Trime (Trime (Trime (8% $5 \times Tc) =$ A Flow Sum Cn - 79 0% $5 \times Tc) =$ B Flow Sum Cn - 79 5% $5 \times Tc) =$ 5%	0.0498 mary Q2 cfs 1.2 0.0498 mary Q2 cfs 0.6 0.0498	Q10 cfs 2 Q10 cfs 1	Q25 cfs 3.1 Q25 cfs 1.5	Q50 cfs 3.4 Q50 cfs 1.6	Q100 cfs 4.3 Q100 cfs 2
83	segment total H TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total H TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total	segment total time of conc.(h YDROLOGIC Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc.(h YDROLOGIC Sogment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc.(h (YDROLOGIC Sogment total time of conc.(h (YDROLOGIC) Sogment total time of conc.(h (YDROLOGIC) Sogment total time of conc.(h (YDROLOGIC) Sogment #2	0 0.083 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	Imperviou SCS Lag ARAY fo Area acres 0.57 Imperviou SCS Lag Area acres 0.26	Is Cover Time (or DA 2 Tc hours 0.083 IS Cover Time (hours 0.083 IS Cover Tc hours 0.083 IS Cover Tc hours 0.083 IS Cover Tc hours 0.083 IS Cover Tr hours 0.083 IS Cover Tc hours 0.083 IS Cover Tc Tc hours 0.083 IS Cover Tc Time (Tc Time (Tc Time (8% $5 \times Tc] =$ A Flow Sum Cn - 79 0% $5 \times Tc] =$ AB Flow Sum Cn - 79 5% $5 \times TcJ =$ 5% Flow Sum	0.0498 mary Q2 cfs 1.2 0.0498 mary Q2 cfs 0.6 0.6 0.0498	Q10 cfs 2 Q10 cfs 1	Q25 cfs 3.1 Q25 cfs 1.5	Q50 cfs 3.4 Q50 cfs 1.6	Q100 cfs 4.3 Q100 cfs 2
833	segment total H TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total H TR-55 SCS Lag Time (hours Segment total Unpaved Length (ft) Slope (%) segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total Fre-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total Fre-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved	segment total time of conc.(h YDROLOGIC) Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc.(h YDROLOGIC) Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc.(h (h) Slope (%) Velocity (fps) segment total time of conc.(h (h) Slope (%) Velocity (fps) segment total time of conc.(h (h) Segment #3 Channelized Mannings "n"	0 0.083 0.083 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	Imperviou SCS Lag ARY fo Area acres 0.57 Imperviou SCS Lag Area acres 0.26 MARY fo SCS Lag MARY fo SCS Lag	Is Cover Time (.e or DA 2 Tc hours 0.083 Is Cover Time (.e or DA 2 Tc hours 0.083 Is Cover Tr for DA 2 Tc hours 0.083 Is Cover Tc hours 0.083	8% 5 x Tc) = 7A Flow Sum Cn - 79 6 x Tc) = 79 5% 5 x Tc) = 5% 5 x Tc) = 5% 5 x Tc) = 5% 5 x Tc) = 79	0.0498 mary Q2 cfs 1.2 0.0498 mary Q2 cfs 0.6 0.0498 0.0498	Q10 cfs 2 2 Q10 cfs 1 1 Q10 cfs 0.3	Q25 cfs 3.1 Q25 cfs 1.5 Q25 cfs 0.4	Q50 cfs 3.4 Q50 cfs 1.6 Q50 cfs 0.5	Q100 cfs 4.3 Q100 cfs 2 Q100 cfs 0.6
333	segment total H TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total H TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) Shallow Concent Unpaved Length (ft) Slope (%) segment total FR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) Shallow Concent Unpaved Length (ft) Slope (%)	segment total time of conc.(h YDROLOG/C Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc.(h YDROLOG/C Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc.(h YDROLOG/C Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Segment #3 Channelized Mannings "n" Length (ft) Slope (%)	0 0.083 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	Imperviou SCS Lag ARY fc Area acres 0.57 Imperviou SCS Lag Area acres 0.26 Imperviou SCS Lag MARY f Area acres 0.26	Is Cover Time (or DA 4 Tc hours 0.083 IS Cover Time (or DA 4 Tc hours 0.083 IS Cover Tc hours 0.083 IS Cover Tc IS Cover IS Cover Tc hours 0.083 IS Cover IS Cover	8% $5 \times Tc] =$ A Flow Sum Cn - 79 0% $5 \times Tc] =$ AB Flow Sum Cn - 79 5% $5 \times Tc] =$ 5% Flow Sum Cn - 79 5% $5 \times Tc] =$ 5 Flow Sum Cn - 79 5%	0.0498 mary Q2 cfs 1.2 0.0498 mary Q2 cfs 0.6 0.0498 0.0498 0.0498	Q10 cfs 2 2 Q10 cfs 1 2 0.3	Q25 cfs 3.1 Q25 cfs 1.5 Q25 cfs 0.4	Q50 cfs 3.4 Q50 cfs 1.6 Q50 cfs 0.5	Q100 cfs 4.3 Q100 cfs 2 Q100 cfs 0.6
333	segment total H TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total H TR-55 SCS Lag Time (hours Segment total H TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total F TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) Shallow Concent Unpaved Length (ft) Slope (%) Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total	segment total <i>time of conc.(fr.</i> <i>YDROLOGIC</i>) Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(fr.</i> <i>YDROLOGIC</i>)	0 0.083 C SUMM 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	Imperviou SCS Lag Area acres 0.57 Imperviou SCS Lag Area acres 0.26 MARY fc SCS Lag MARY f	Is Cover Time (pr DA 4 Tc hours 0.083 Is Cover Time (pr DA 4 Tc hours 0.083 Is Cover Tc hours 0.083 Is Cover Time (8% 5 x Tc) = 7 Flow Sum Cn - 79 0% 5 x Tc) = 7 79 5% 5 x Tc) = 5 Flow Sum Cn - 79 5% 5 x Tc) = 5 Flow Sum Cn - 79 0% 6 x Tc) = 5% 6 x Tc) = 5% 6 x Tc) = 0% 6 x Tc) = 0% 0% 6 x Tc) = 0% 0% 6 x Tc) = 0% 0% 0% 0% 0% 0% 0% 0% 0% 0%	0.0498 mary Q2 cfs 1.2 0.0498 mary Q2 cfs 0.6 0.0498 mary Q2 cfs 0.6 0.0498 mary Q2 cfs 0.2 0.0498	Q10 cfs 2 2 Q10 cfs 1 1 Q10 cfs 0.3	Q25 cfs 3.1 Q25 cfs 1.5 Cfs 1.5 Cfs 0.4	Q50 cfs 3.4 Q50 cfs 1.6 Q50 cfs 0.5	Q100 cfs 4.3 Q100 cfs 2 Q100 cfs 0.6
333	segment total H TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total H TR-55 SCS Lag Time (hours Segment total H TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total FR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total Segment total	segment total time of conc.(h YDROLOGIC Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc.(h YDROLOGIC Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc.(h YDROLOGIC Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc.(h Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc.(h Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc.(h Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc.(h COROLOGIC	0 0.083 C SUMM 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	Imperviou SCS Lag ARY fc Area acres 0.57 Imperviou SCS Lag MARY fc Area acres 0.26 Imperviou SCS Lag MARY f Area acres 0.26 Imperviou SCS Lag	IS Cover Time (Dr DA 4 Tc hours 0.083 DS Cover Time (DO DA 4 Tc hours 0.083 DS Cover Time (For DA Tc hours 0.083 DS Cover Time (Tc hours 0.083 DS Cover Time (8% $5 \times Tc] =$ A Flow Sum Cn - 79 0% $5 \times Tc] =$ $Flow Sum Cn - 79 5% 5 \times Tc] = 5 Flow Sum Cn - 79 5% 5 \times Tc] = 6 \times Tc] = 6 \times Tc] = 6 \times Tc] = 6 \times Tc] = 79$	0.0498 mary Q2 cfs 1.2 0.0498 mary Q2 cfs 0.6 0.0498 mary Q2 cfs 0.6 0.0498	Q10 cfs 2 2 Q10 cfs 1 Q10 cfs 0.3	Q25 cfs 3.1 Q25 cfs 1.5 Q25 cfs 0.4	Q50 cfs 3.4 Q50 cfs 1.6 Q50 cfs 0.5	Q100 cfs 4.3 Q100 cfs 2 Q100 cfs 0.6
833	segment total H TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total H TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total Impaved Length (ft) Slope (%) segment total Impaved Length (ft) Slope (%) Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total H Shallow Concent Unpaved Length (ft) Slope (%) segment total HY TR-55 SCS Lag Time (hours Segment total HY	segment total <i>time of conc.(h</i> <i>YDROLOGIC</i> Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>YDROLOGIC</i> Sogment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>YDROLOGIC</i> Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>YDROLOGIC</i> Sogment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>DROLOGIC</i> Sogment #2	0 0.083 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	Imperviou SCS Lag ARY fo Area acres 0.57 Imperviou SCS Lag AARY fo Area acres 0.26 Imperviou SCS Lag MARY fo Area acres 0.08 Imperviou SCS Lag ARY for Area	Is Cover Time (or DA 4 Tc hours 0.083 Is Cover Time (or DA 4 Tc hours 0.083 Is Cover Trime (for DA Tc hours 0.083 Is Cover Trime (for DA Tc hours 0.083 Is Cover Trime (for DA Tc hours 0.083 Is Cover Trime (Tc hours 0.083 Is Cover Tc hours 0.083 Is Cover Trime (8% $5 \times Tc] =$ A Flow Sum Cn - 79 0% $5 \times Tc] =$ AB Flow Sum Cn - 79 5% $5 \times Tc] =$ 5 Flow Sum Cn - 79 5% $5 \times Tc] =$ 5 Flow Sum Cn - 79 0% $5 \times Tc] =$ $4 7$ Flow Sum Cn - 79 0% $5 \times Tc] =$ $4 7$ Flow Sum Cn - 79 0% $5 \times Tc] =$ $79 \times Tc] =$	0.0498 mary Q2 cfs 1.2 0.0498 mary Q2 cfs 0.6 0.6 0.0498 mary Q2 cfs 0.2 0.0498 0.0498	Q10 cfs 2 Q10 cfs 1 Q10 cfs 0.3	Q25 cfs 3.1 Q25 cfs 1.5 Cfs 0.4	Q50 cfs 3.4 Q50 cfs 1.6 Q50 cfs 0.5	Q100 cfs 4.3 Q100 cfs 2 2 Q100 cfs 0.6
833	segment total H TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total H TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total HY TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved	segment total time of conc.(h YDROLOGIC Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc.(h YDROLOGIC Solution YDROLOGIC Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc.(h YDROLOGIC Solution Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc.(h DROLOGIC Solution Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc.(h DROLOGIC Solution Segment #3 Channelized Mannings "n"	0 0.083 0.083 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	Imperviou SCS Lag ARY fo Area acres 0.57 Imperviou SCS Lag MARY fo Area acres 0.26 Imperviou SCS Lag MARY fo Area acres 0.08 Imperviou SCS Lag ARY fo Area acres 0.26 Imperviou SCS Lag	IS Cover Time (Dr DA 2 Tc hours 0.083 IS Cover Time (Dr DA 2 Tc hours 0.083 IS Cover Tc hours 0.083 IS Cover Tc hours 0.083 IS Cover Tre (DA 2 Tc hours 0.083 IS Cover Tre (DA 2 IS Cover Tre (DA 2 IS Cover Tc hours 0.083 IS Cover IS Cov	8% $5 \times Tc) =$ A Flow Sum Cn - 79 0% $5 \times Tc) =$ $Flow Sum Cn - 79 5\% 5 \times Tc) = 5 Flow Sum Cn - 79 5\% 5 \times Tc) = 6 \times Tc) = 6 \times Tc) = 79 0\% 5 \times Tc) = 79 0\% 79 79 79 79 79 79 79 79$	0.0498 mary Q2 cfs 1.2 0.0498 mary Q2 cfs 0.6 0.0498 mary Q2 cfs 0.6 0.0498 0.0498 0.0498 0.0498 0.0498	Q10 cfs 2 Q10 cfs 1 Q10 cfs 0.3 Q10 cfs 0.3 Q10 cfs 12.2	Q25 cfs 3.1 Q25 cfs 1.5 Q25 cfs 0.4 Q25 cfs 0.4	Q50 cfs 3.4 Q50 cfs 1.6 Q50 cfs 0.5 Q50 cfs 0.5	Q100 cfs 4.3 Q100 cfs 2 Q100 cfs 0.6 Q100 cfs 2.3.8
833	segment total H TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total H TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total F TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total HY TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment #2 Shallow Concent Unpaved Length (ft) Slope (%) Slope (%) Slope (%) <td>segment total time of conc.(h YDROLOG/C Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc.(h DROLOG/C Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment #3 Channelized Mannings "n" Length (ft) Slope (%)</td> <td>0 0.083 C SUMM 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0</td> <td>Imperviou SCS Lag ARY fo Area acres 0.57 Imperviou SCS Lag Area acres 0.26 Imperviou SCS Lag MARY fo Area acres 0.26 Imperviou SCS Lag Area acres 0.26</td> <td>IS Cover Time (Dr DA 2 Tc hours 0.083 DS Cover Time (DS Cover Tc hours 0.083 DS Cover Tc hours 0.083 DS Cover Time (Tc hours 0.083 DS Cover Time (Tc hours 0.083 DS Cover Time (Tc hours 0.083 DS Cover Tc hours 0.083 DS Cover Tc DS Cover Tc hours 0.083 DS Cover Tc hours 0.083 DS Cover Tc hours 0.083 DS Cover Tc hours 0.083 DS Cover Tc hours 0.083 DS Cover Tc DS Cover Tc hours 0.083 DS Cover Tc hours 0.083 DS Cover Tc hours 0.083 DS Cover TC DS Cover Tc hours 0.083 DS Cover TC NO DS COVER TC NO TC NO DS COVER TC NO TC NO TC NO DS COVER TC NO TC NO TC NO TC NO TC TC NO TC TC TC NO TC TC TC TC TC TC TC TC TC TC</td> <td>8% $5 \times Tc) =$ A Flow Sum Cn - 79 0% $5 \times Tc) =$ AB Flow Sum Cn - 79 5% $5 \times Tc) =$ 5 Flow Sum Cn - 79 5% $5 \times Tc) =$ $4 T$ Flow Sum Cn - 79 0% $5 \times Tc) =$ 79</td> <td>0.0498 mary Q2 cfs 1.2 0.0498 0.0498 mary Q2 cfs 0.6 0.0498 mary Q2 cfs 0.6 0.0498 mary Q2 cfs 0.2 0.2 0.2 0.2 0.2 0.2 0.2 0.2</td> <td>Q10 cfs 2 2 0 2 0 2 0 2 0 2 0 2 0 2 0 2 0 2 0</td> <td>Q25 cfs 3.1 Q25 cfs 1.5 Cfs 0.4 Q25 cfs 0.4</td> <td>Q50 cfs 3.4 Q50 cfs 1.6 Q50 cfs 0.5 Q50 cfs 0.5</td> <td>Q100 cfs 4.3 Q100 cfs 2 Q100 cfs 0.6 Q100 cfs 0.6</td>	segment total time of conc.(h YDROLOG/C Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc.(h DROLOG/C Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment #3 Channelized Mannings "n" Length (ft) Slope (%)	0 0.083 C SUMM 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	Imperviou SCS Lag ARY fo Area acres 0.57 Imperviou SCS Lag Area acres 0.26 Imperviou SCS Lag MARY fo Area acres 0.26 Imperviou SCS Lag Area acres 0.26	IS Cover Time (Dr DA 2 Tc hours 0.083 DS Cover Time (DS Cover Tc hours 0.083 DS Cover Tc hours 0.083 DS Cover Time (Tc hours 0.083 DS Cover Time (Tc hours 0.083 DS Cover Time (Tc hours 0.083 DS Cover Tc hours 0.083 DS Cover Tc DS Cover Tc hours 0.083 DS Cover Tc hours 0.083 DS Cover Tc hours 0.083 DS Cover Tc hours 0.083 DS Cover Tc hours 0.083 DS Cover Tc DS Cover Tc hours 0.083 DS Cover Tc hours 0.083 DS Cover Tc hours 0.083 DS Cover TC DS Cover Tc hours 0.083 DS Cover TC NO DS COVER TC NO TC NO DS COVER TC NO TC NO TC NO DS COVER TC NO TC NO TC NO TC NO TC TC NO TC TC TC NO TC TC TC TC TC TC TC TC TC TC	8% $5 \times Tc) =$ A Flow Sum Cn - 79 0% $5 \times Tc) =$ AB Flow Sum Cn - 79 5% $5 \times Tc) =$ 5 Flow Sum Cn - 79 5% $5 \times Tc) =$ $4 T$ Flow Sum Cn - 79 0% $5 \times Tc) =$ 79	0.0498 mary Q2 cfs 1.2 0.0498 0.0498 mary Q2 cfs 0.6 0.0498 mary Q2 cfs 0.6 0.0498 mary Q2 cfs 0.2 0.2 0.2 0.2 0.2 0.2 0.2 0.2	Q10 cfs 2 2 0 2 0 2 0 2 0 2 0 2 0 2 0 2 0 2 0	Q25 cfs 3.1 Q25 cfs 1.5 Cfs 0.4 Q25 cfs 0.4	Q50 cfs 3.4 Q50 cfs 1.6 Q50 cfs 0.5 Q50 cfs 0.5	Q100 cfs 4.3 Q100 cfs 2 Q100 cfs 0.6 Q100 cfs 0.6
333	segment total H TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total FR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total Unpaved Length (ft) Slope (%) segment total Unpaved Length (ft) Slope (%) segment total H TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total HY TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) Segment total HY TR-55 SCS Lag Time (hours Segment total Slope (%) <td>segment total <i>time of conc.(h</i> <i>YDROLOGIC</i>) Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>YDROLOGIC</i>) Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>YDROLOGIC</i>) Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>Sope</i> (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>DROLOGIC</i>) Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>DROLOGIC</i>) Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>DROLOGIC</i>)</td> <td>0 0.083 C SUMM 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0</td> <td>Imperviou SCS Lag ARY fo Area acres 0.57 Imperviou SCS Lag ARY fo MARY fo SCS Lag MARY fo Area acres 0.26 MARY fo Area acres 2.86</td> <td>Is Cover Time (pr DA 2 Tc hours 0.083 Is Cover Time (pr DA 2 Tc hours 0.083 Is Cover Trime (for DA Tc hours 0.083 Is Cover Time (for DA Tc hours 0.083 Is Cover Tc hours 0.083 Is Cover Tc</td> <td>8% 5 x Tc) = 7 Flow Sum Cn - 79 0% 5 x Tc) = 7 79 5% 5 x Tc) = 5 Flow Sum Cn - 79 5% 5 x Tc) = 79 0% 5 x Tc) = 4 7 1 Flow Sum Cn - 79 0% 5 x Tc) = 7 0% 5 x Tc) = 7 8 8 8 8 8 8 8 8 8 8 8 8 8</td> <td>0.0498 mary Q2 cfs 1.2 0.0498 mary Q2 cfs 0.0498 mary Q2 cfs 0.6 0.0498 mary Q2 cfs 0.6 0.0498 mary Q2 cfs 0.2 0.0498 mary Q2 cfs 0.2 0.0498 mary Q2 cfs 0.2 0.0498</td> <td>Q10 cfs 2 Q10 cfs 1 Q10 cfs 0.3 Q10 cfs 12.2</td> <td>Q25 cfs 3.1 Q25 cfs 1.5 Q25 cfs 0.4 Q25 cfs 0.4</td> <td>Q50 cfs 3.4 Q50 cfs 1.6 Q50 cfs 0.5 Q50 cfs 0.5 Q50 cfs 19.9</td> <td>Q100 cfs 4.3 Q100 cfs 2 Q100 cfs 0.6 Q100 cfs 2.3.8</td>	segment total <i>time of conc.(h</i> <i>YDROLOGIC</i>) Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>YDROLOGIC</i>) Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>YDROLOGIC</i>) Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>Sope</i> (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>DROLOGIC</i>) Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>DROLOGIC</i>) Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>DROLOGIC</i>)	0 0.083 C SUMM 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	Imperviou SCS Lag ARY fo Area acres 0.57 Imperviou SCS Lag ARY fo MARY fo SCS Lag MARY fo Area acres 0.26 MARY fo Area acres 2.86	Is Cover Time (pr DA 2 Tc hours 0.083 Is Cover Time (pr DA 2 Tc hours 0.083 Is Cover Trime (for DA Tc hours 0.083 Is Cover Time (for DA Tc hours 0.083 Is Cover Tc hours 0.083 Is Cover Tc	8% 5 x Tc) = 7 Flow Sum Cn - 79 0% 5 x Tc) = 7 79 5% 5 x Tc) = 5 Flow Sum Cn - 79 5% 5 x Tc) = 79 0% 5 x Tc) = 4 7 1 Flow Sum Cn - 79 0% 5 x Tc) = 7 0% 5 x Tc) = 7 8 8 8 8 8 8 8 8 8 8 8 8 8	0.0498 mary Q2 cfs 1.2 0.0498 mary Q2 cfs 0.0498 mary Q2 cfs 0.6 0.0498 mary Q2 cfs 0.6 0.0498 mary Q2 cfs 0.2 0.0498 mary Q2 cfs 0.2 0.0498 mary Q2 cfs 0.2 0.0498	Q10 cfs 2 Q10 cfs 1 Q10 cfs 0.3 Q10 cfs 12.2	Q25 cfs 3.1 Q25 cfs 1.5 Q25 cfs 0.4 Q25 cfs 0.4	Q50 cfs 3.4 Q50 cfs 1.6 Q50 cfs 0.5 Q50 cfs 0.5 Q50 cfs 19.9	Q100 cfs 4.3 Q100 cfs 2 Q100 cfs 0.6 Q100 cfs 2.3.8
333	segment total H TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total M TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total FR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total M TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total MY TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) <td>segment total time of conc.(h YDROLOG/C Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc.(h YDROLOG/C Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc.(h YDROLOG/C Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc.(h DROLOG/C Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc.(h DROLOG/C Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc.(h DROLOG/C</td> <td>0 0.083 C SUMM 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0</td> <td>Imperviou SCS Lag ARY fo Area acres 0.57 Imperviou SCS Lag MARY fo Imperviou SCS Lag MARY fo Area acres 0.26 Imperviou SCS Lag ARY fo Area acres 0.26 Imperviou SCS Lag ARY fo Area acres 0.26 Imperviou SCS Lag</td> <td>IS Cover Time (Dr DA 2 Tc hours 0.083 IS Cover Time (Dr DA 2 Tc hours 0.083 IS Cover Trime (For DA Tc hours 0.083 IS Cover Time (Tc hours 0.083 IS Cover Trime (Tc hours 0.083 IS Cover Tc hours 0.083 IS Cover Tc hours 0.083 IS Cover Tc IS Cove</td> <td>8% $5 \times Tc] =$ A Flow Sum Cn - 79 - 79 - 79 - 79 - 79 - 5% 5 \times Tc] = - 5 Flow Sum Cn 79 - 5% 5 \times Tc] = - 4 Flow Sum Cn 79 - 5% 5 \times Tc] = - 4 Flow Sum Cn 79</td> <td>0.0498 mary Q2 cfs 1.2 0.0498 0.0498 mary Q2 cfs 0.6 0.0498 mary Q2 cfs 0.6 0.0498 mary Q2 cfs 0.2 0.0498 mary Q2 cfs 0.2 0.0498 mary Q2 cfs 0.2 0.0498 0.0</td> <td>Q10 cfs 2 Q10 cfs 1 Q10 cfs 0.3 Q10 cfs 0.3</td> <td>Q25 cfs 3.1 Q25 cfs 1.5 Cfs 0.4 Q25 cfs 0.4 Q25 cfs 0.4</td> <td>Q50 cfs 3.4 Q50 cfs 1.6 Q50 cfs 0.5 Q50 cfs 0.5 Q50 cfs 0.5</td> <td>Q100 cfs 4.3 Q100 cfs 2 Q100 cfs 0.6 Q100 cfs 0.6</td>	segment total time of conc.(h YDROLOG/C Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc.(h YDROLOG/C Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc.(h YDROLOG/C Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc.(h DROLOG/C Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc.(h DROLOG/C Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc.(h DROLOG/C	0 0.083 C SUMM 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	Imperviou SCS Lag ARY fo Area acres 0.57 Imperviou SCS Lag MARY fo Imperviou SCS Lag MARY fo Area acres 0.26 Imperviou SCS Lag ARY fo Area acres 0.26 Imperviou SCS Lag ARY fo Area acres 0.26 Imperviou SCS Lag	IS Cover Time (Dr DA 2 Tc hours 0.083 IS Cover Time (Dr DA 2 Tc hours 0.083 IS Cover Trime (For DA Tc hours 0.083 IS Cover Time (Tc hours 0.083 IS Cover Trime (Tc hours 0.083 IS Cover Tc hours 0.083 IS Cover Tc hours 0.083 IS Cover Tc IS Cove	8% $5 \times Tc] =$ A Flow Sum Cn - 79 - 79 - 79 - 79 - 79 - 5% 5 \times Tc] = - 5 Flow Sum Cn 79 - 5% 5 \times Tc] = - 4 Flow Sum Cn 79 - 5% 5 \times Tc] = - 4 Flow Sum Cn 79	0.0498 mary Q2 cfs 1.2 0.0498 0.0498 mary Q2 cfs 0.6 0.0498 mary Q2 cfs 0.6 0.0498 mary Q2 cfs 0.2 0.0498 mary Q2 cfs 0.2 0.0498 mary Q2 cfs 0.2 0.0498 0.0	Q10 cfs 2 Q10 cfs 1 Q10 cfs 0.3 Q10 cfs 0.3	Q25 cfs 3.1 Q25 cfs 1.5 Cfs 0.4 Q25 cfs 0.4 Q25 cfs 0.4	Q50 cfs 3.4 Q50 cfs 1.6 Q50 cfs 0.5 Q50 cfs 0.5 Q50 cfs 0.5	Q100 cfs 4.3 Q100 cfs 2 Q100 cfs 0.6 Q100 cfs 0.6
333	segment total H TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total Unpaved Length (ft) Slope (%) segment total Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total	segment total <i>time of conc.(h</i> <i>YDROLOGIC</i> Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>DROLOGIC</i> Solope (%) Velocity (fps) segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>DROLOGIC</i> <i>Concelled</i> <i>Concelled</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Chanelized</i> <i>Channelized</i>	0 0.083 5 5 5 5 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	Imperviou SCS Lag ARY fo Area acres 0.57 Imperviou SCS Lag ARY fo Imperviou SCS Lag MARY fo Area acres 0.26 Imperviou SCS Lag ARY fo Area acres 0.26 Imperviou SCS Lag ARY fo Area acres 0.26 Area	s Cover Time (pr DA 2 Tc hours 0.083 s Cover Time (pr DA 2 for DA 2 for DA 2 Tc hours 0.083 s Cover Tc hours 0.083 s Cover Tc Tc hours 0.083 s Cover Tc Tc hours 0.083 s Cover Tc Tc hours 0.083 s Cover Tc Tc hours 0.083 s Cover Tc Tc hours 0.083 s Cover Tc Tc hours b Cover Tc Tc hours c Cover Tc Tc b Cover Tc Tc tr Tc tr tr tr tr tr tr tr tr tr tr	8% $5 \times Tc) =$ A Flow Sum Cn - 79 0% $5 \times Tc) =$ AB Flow Sum Cn - 79 5% $5 \times Tc) =$ 5 Flow Sum Cn - 79 5% $5 \times Tc) =$ 5 Flow Sum Cn - 79 0% $5 \times Tc) =$ $4 7$ Flow Sum Cn - 79 0% $5 \times Tc) =$ $4 7$ Flow Sum Cn - 79 0% $5 \times Tc) =$ $4 7$ Flow Sum Cn - 79 0% $5 \times Tc) =$ $4 7$ Flow Sum Cn - 79 0% $5 \times Tc) =$ $4 7$ Flow Sum Cn - 79 0% $5 \times Tc) =$ $4 7$ Flow Sum Cn - 79 0% $5 \times Tc) =$ $4 7$ Flow Sum Cn - 79 0% $5 \times Tc) =$ $4 7$ Flow Sum Cn - 79 0% $5 \times Tc) =$ $4 7$ Flow Sum Cn - 79 0% $5 \times Tc) =$ $5 \times Tc) =$ $4 7$ Flow Sum Cn - 79 0% $5 \times Tc) =$ $4 7$ Flow Sum Cn - 79 0% $5 \times Tc) =$ $4 7$ Flow Sum Cn - 79 0% $5 \times Tc) =$ $4 7$ Flow Sum Cn - 79 0% $5 \times Tc) =$ $4 7$ Flow Sum Cn - 79 0% $5 \times Tc) =$ $5 \times Tc) =$ $5 \times Tc) =$ $7 \times Tc$ $7 \times Tc) =$ $7 \times Tc$ $7 \times Tc) =$ $7 \times Tc$ $7 \times Tc$ $7 \times Tc$	0.0498 mary Q2 cfs 1.2 0.0498 mary Q2 cfs 0.6 0.6 0.0498 mary Q2 cfs 0.2 0.0498 mary Q2 cfs 0.2 0.0498 0.0498	Q10 cfs 2 Q10 cfs 1 Q10 cfs 0.3 Q10 cfs 0.3 Q10 cfs 12.2	Q25 cfs 3.1 Q25 cfs 1.5 Cfs 0.4 Q25 cfs 0.4 Q25 cfs 0.4	Q50 cfs 3.4 Q50 cfs 1.6 Q50 cfs 0.5 0.5 0.5	Q100 cfs 4.3 Q100 cfs 2 Q100 cfs 0.6 Q100 cfs 0.6
	segment total H TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total H TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total Unpaved Length (ft) Slope (%) segment total Unpaved Length (ft) Slope (%) segment total HY TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total HY TR-55 SCS Lag Time (hours Segment total Slope (%) segment total HY	segment total <i>time of conc.(h</i> <i>YDROLOGIC</i> Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>YDROLOGIC</i> Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>YDROLOGIC</i> Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>DROLOGIC</i> Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>DROLOGIC</i> <i>S</i> Segment #3 Channelized Mannings "n" <i>Segment</i> #3 <i>Channelized</i> <i>Manninge</i> "n" <i>Segment</i> #3 <i>Segment</i> #3	0 0.083 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	Imperviou SCS Lag ARY fo Area acres 0.57 Imperviou SCS Lag ARY fo Area acres 0.26 MARY fo Area acres 0.26 MARY fo Area acres 2.86 ARY fo Area acres 2.86 ARY fo Area acres	s Cover Time (pr DA 2 Tc hours 0.083 s Cover Time (pr DA 2 for DA 2	8% $5 \times Tc) =$ A Flow Sum Cn - 79 0% $5 \times Tc) =$ AB Flow Sum Cn - 79 5% $5 \times Tc) =$ 5 Flow Sum Cn - 79 5% $5 \times Tc) =$ $4 7$ Flow Sum Cn - 79 0% $5 \times Tc) =$ $4 7$ Flow Sum Cn - 79 0% $5 \times Tc) =$ $4 7$ Flow Sum Cn - 79 0% $5 \times Tc) =$ $4 7$ Flow Sum Cn - 79 0% $5 \times Tc) =$ $4 7$ Flow Sum Cn - 79 0% $5 \times Tc) =$ $4 7$ Flow Sum Cn - 79 0% $5 \times Tc) =$ $4 7$ Flow Sum Cn - 79 0% $5 \times Tc) =$ $4 7$ Flow Sum Cn - 79 0% $5 \times Tc) =$ $4 7$ Flow Sum Cn - 79 0% $5 \times Tc) =$ $4 7$ Flow Sum Cn - 79 0% $5 \times Tc) =$ $4 7$ Flow Sum Cn - 79 0% $5 \times Tc) =$ 79	0.0498 mary Q2 cfs 1.2 0.0498 mary Q2 cfs 0.6 0.0498 0.0498 0.0498 0.0498 0.0498 0.0498 0.0498 0.0498 0.0498 0.0498 0.0498 0.0498 0.0498 0.0498 0.0498	Q10 cfs 2 Q10 cfs 1 Q10 cfs 0.3 Q10 cfs 12.2 Q10 cfs 0.3	Q25 cfs 3.1 Q25 cfs 1.5 Q25 cfs 0.4 Q25 cfs 0.4	Q50 cfs 3.4 Q50 cfs 1.6 Q50 cfs 0.5 0.5 0.5 0.5 0.5	Q100 cfs 4.3 Q100 cfs 2 Q100 cfs 0.6 Q100 cfs 23.8 Q100 cfs 1.2
	segment total H TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total M TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total M TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total MY TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total MY TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft)	segment total time of conc. (h YDROLOGIC Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc. (h YDROLOGIC Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc. (h YDROLOGIC Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc. (h DROLOGIC Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc. (h DROLOGIC Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc. (h DROLOGIC Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc. (h DROLOGIC	0 0.083 C SUMM 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	Imperviou SCS Lag ARY fo Area acres 0.57 Imperviou SCS Lag ARY fo Area acres 0.26 Imperviou SCS Lag MARY fo Area acres 0.26 Imperviou SCS Lag ARY fo Area acres 0.26 Imperviou SCS Lag ARY fo Area acres 0.36 Imperviou SCS Lag ARY fo Area acres 0.36 Imperviou SCS Lag ARY fo Area acres 0.36 Imperviou SCS Lag ARY fo Area acres 0.36 Imperviou SCS Lag ARY fo Area acres 0.36 Imperviou SCS Lag	IS Cover Time (Dr DA 2 Tc hours 0.083 IS Cover Time (Dr DA 2 Tc hours 0.083 IS Cover Tc hours 0.083 IS Cover Trime (A Tc hours 0.083 IS Cover Tc hours 0.083 IS Cover Tc hours 0.0833 IS Cover TC IS Cover TC IS Cover IS Cover I	8% $5 \times Tc) =$ A Flow Sum Cn - 79 0% $5 \times Tc) =$ AB Flow Sum Cn - 79 5% $5 \times Tc) =$ 5 Flow Sum Cn - 79 0% $5 \times Tc) =$ 4 2 Flow Sum Cn - 79 0% $5 \times Tc) =$ 4 2 Flow Sum Cn - 79 0% $5 \times Tc) =$ 4 2 Flow Sum Cn - 79 0% $5 \times Tc) =$ 79 0% $5 \times Tc) =$ 79 0% $5 \times Tc) =$ 4 2 Flow Sum Cn - 79 0% $5 \times Tc) =$ 79 0% $5 \times Tc) =$ 79	0.0498 mary Q2 cfs 1.2 0.0498 0.	Q10 cfs 2 Q10 cfs 1 Q10 cfs 0.3 Q10 cfs 0.3 Q10 cfs 0.3	Q25 cfs 3.1 Q25 cfs 1.5 Cfs 1.5 Q25 cfs 0.4 Q25 cfs 0.4	Q50 cfs 3.4 Q50 cfs 1.6 Q50 cfs 0.5 Q50 cfs 0.5 Q50 cfs 0.5	Q100 cfs 4.3 Q100 cfs 2 Q100 cfs 0.6 Q100 cfs 0.6 Q100 cfs 1.2
	segment total H TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total M TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) Segment total Unpaved Length (ft) Slope (%) segment total M TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total M TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total MY TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) <td>segment total <i>time of conc.(h</i> <i>YDROLOGIC</i> Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>YDROLOGIC</i> Sogment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>YDROLOGIC</i> Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>DROLOGIC</i> Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>DROLOGIC</i> <i>S</i> <i>Segment #3</i> <i>Channelized</i> Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>Segment #3</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelize</i></td> <td>0 0.083 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5</td> <td>Imperviou SCS Lag Area acres 0.57 Imperviou SCS Lag ARY for Area acres 0.26 MARY for Area acres 0.26 MARY for Area acres 0.08 MARY for Area acres 0.08 MARY for Area acres 0.08 MARY for Area acres 0.08</td> <td>s Cover Time (pr DA 2 Tc hours 0.083 s Cover Time (pr DA 2 nor DA 2 for DA 2 Tc hours 0.083 s Cover Tc hours 0.083 s Cover Tc bo bo bo bo bo bo bo bo bo bo</td> <td>8% $5 \times Tc) =$ A Flow Sum Cn - 79 0% $5 \times Tc) =$ AB Flow Sum Cn - 79 5% $5 \times Tc) =$ 5 Flow Sum Cn - 79 5% $5 \times Tc) =$ $4 7$ Flow Sum Cn - 79 0% $5 \times Tc) =$ $4 7$ Flow Sum Cn - 79 0% $5 \times Tc) =$ $4 7$ Flow Sum Cn - 79 0% $5 \times Tc) =$ $6 \times Tc) =$ 79 0% $5 \times Tc) =$ 79 0% $5 \times Tc) =$ 79 0% $5 \times Tc) =$ 79 0% $5 \times Tc) =$ 79 0% $5 \times Tc) =$ 79 0% 79 0%</td> <td>0.0498 mary Q2 cfs 1.2 0.0498 0.0498 mary Q2 cfs 0.6 0.0498 mary Q2 cfs 0.2 0.0498 mary Q2 cfs 0.2 0.0498</td> <td>Q10 cfs 2 Q10 cfs 1 Q10 cfs 0.3 Q10 cfs 12.2 Q10 cfs 0.3</td> <td>Q25 cfs 3.1 Q25 cfs 1.5 Q25 cfs 0.4 Q25 cfs 0.4 Q25 cfs 0.4</td> <td>Q50 cfs 3.4 Q50 cfs 1.6 Q50 cfs 0.5 0.5 Q50 cfs 19.9 Q50 cfs 0.5</td> <td>Q100 cfs 4.3 Q100 cfs 2 Q100 cfs 0.6 Q100 cfs 1.2</td>	segment total <i>time of conc.(h</i> <i>YDROLOGIC</i> Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>YDROLOGIC</i> Sogment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>YDROLOGIC</i> Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>DROLOGIC</i> Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>DROLOGIC</i> <i>S</i> <i>Segment #3</i> <i>Channelized</i> Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>Segment #3</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelize</i>	0 0.083 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	Imperviou SCS Lag Area acres 0.57 Imperviou SCS Lag ARY for Area acres 0.26 MARY for Area acres 0.26 MARY for Area acres 0.08 MARY for Area acres 0.08 MARY for Area acres 0.08 MARY for Area acres 0.08	s Cover Time (pr DA 2 Tc hours 0.083 s Cover Time (pr DA 2 nor DA 2 for DA 2 Tc hours 0.083 s Cover Tc hours 0.083 s Cover Tc bo bo bo bo bo bo bo bo bo bo	8% $5 \times Tc) =$ A Flow Sum Cn - 79 0% $5 \times Tc) =$ AB Flow Sum Cn - 79 5% $5 \times Tc) =$ 5 Flow Sum Cn - 79 5% $5 \times Tc) =$ $4 7$ Flow Sum Cn - 79 0% $5 \times Tc) =$ $4 7$ Flow Sum Cn - 79 0% $5 \times Tc) =$ $4 7$ Flow Sum Cn - 79 0% $5 \times Tc) =$ $6 \times Tc) =$ 79 0% $5 \times Tc) =$ 79 0%	0.0498 mary Q2 cfs 1.2 0.0498 0.0498 mary Q2 cfs 0.6 0.0498 mary Q2 cfs 0.2 0.0498 mary Q2 cfs 0.2 0.0498	Q10 cfs 2 Q10 cfs 1 Q10 cfs 0.3 Q10 cfs 12.2 Q10 cfs 0.3	Q25 cfs 3.1 Q25 cfs 1.5 Q25 cfs 0.4 Q25 cfs 0.4 Q25 cfs 0.4	Q50 cfs 3.4 Q50 cfs 1.6 Q50 cfs 0.5 0.5 Q50 cfs 19.9 Q50 cfs 0.5	Q100 cfs 4.3 Q100 cfs 2 Q100 cfs 0.6 Q100 cfs 1.2
	segment total H TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total M TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total M TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total MY TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total MY TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft)	segment total <i>time of conc.(h</i> <i>YDROLOG/C</i> Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>YDROLOG/C</i> Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>YDROLOG/C</i> Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>DROLOG/C</i> Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>DROLOG/C</i> <i>Segment #3</i> <i>Channelized</i> Mannings "n" <i>Length (ft)</i> Slope (%) <i>Velocity (fps)</i> <i>segment total</i> <i>time of conc.(h</i> <i>DROLOG/C</i> <i>Segment #3</i> <i>Channelized</i> <i>Mannings "n"</i> <i>Length (ft)</i> <i>Slope (%)</i> <i>Velocity (fps)</i> <i>segment total</i> <i>time of conc.(h</i> <i>DROLOG/C</i> <i>Segment #3</i> <i>Channelized</i> <i>Segment fotal</i> <i>time of conc.(h</i> <i>Sope (%)</i> <i>Segment fotal</i> <i>time of conc.(h</i> <i>Segment fotal</i> <i>time of conc.(h)</i> <i>Segment fotal</i> <i>time of conc.(h)</i> <i>Segment fotal</i> <i>Segment fotal</i> <i>Segme</i>	0 0.083 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	Imperviou SCS Lag ARY fo Area acres 0.57 Imperviou SCS Lag ARY fo Area acres 0.26 Imperviou SCS Lag MARY fo Area acres 0.26 Imperviou SCS Lag ARY fo Area acres 0.36 Imperviou SCS Lag	s Cover Time (pr DA 2 Tc hours 0.083 s Cover Time (pr DA 2 for DA 2	8% $5 \times Tc) =$ A Flow Sum Cn - 79 0% $5 \times Tc) =$ A Flow Sum Cn - 79 5% $5 \times Tc) =$ 5 Flow Sum Cn - 79 5% $5 \times Tc) =$ 4 Flow Sum Cn - 79 0% $5 \times Tc) =$ 4 Flow Sum Cn - 79 0% $5 \times Tc) =$ 4 79 0% $5 \times Tc) =$ 4 79 0% $5 \times Tc) =$ 4 79 0% $5 \times Tc) =$ 79 0% $5 \times Tc) =$ 4 79 0% $5 \times Tc) =$ 4 79 0% $5 \times Tc) =$ 79 0% 70 79 0% 70 70 70 70 70 70 70 70	0.0498 mary Q2 cfs 1.2 0.0498	Q10 cfs 2 Q10 cfs 1 Q10 cfs 0.3 Q10 cfs 0.3 Q10 cfs 0.3 Q10 cfs 0.3	Q25 cfs 3.1 Q25 cfs 1.5 Q25 cfs 0.4 Q25 cfs 0.4 Q25 cfs 0.4	Q50 cfs 3.4 Q50 cfs 1.6 Q50 cfs 0.5 Q50 cfs 0.5 Q50 cfs 0.5 Q50 cfs 0.5	Q100 cfs 4.3 Q100 cfs 2 Q100 cfs 0.6 Q100 cfs 1.2 Q100 cfs 1.2
	segment total H TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total FR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total FR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total Segment #2 Shallow Concent Unpaved Length (ft)<	segment total time of conc. (h YDROLOGIC Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc. (h YDROLOGIC Some for total time of conc. (h Slope (%) Velocity (fps) segment total time of conc. (h Slope (%) Velocity (fps) segment total time of conc. (h Slope (%) Velocity (fps) segment total time of conc. (h DROLOGIC Some for total time of conc. (h Slope (%) Velocity (fps) segment total time of conc. (h Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc. (h DROLOGIC Some for total time of conc. (h Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc. (h Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total time of conc. (h COCOGIC Some for total time for total tim	0 0.083 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	Imperviou SCS Lag ARY fo Area acres 0.57 Imperviou SCS Lag ARY fo Imperviou SCS Lag MARY fo Imperviou SCS Lag MARY fo Area acres 0.26 Imperviou SCS Lag ARY fo Area acres 0.08 Imperviou SCS Lag ARY fo Area acres 0.08 Imperviou SCS Lag ARY fo Area acres 0.08	s Cover Time (pr DA 2 Tc hours 0.083 s Cover Time (pr DA 2 for DA 2 for DA 2 Tc hours 0.083 s Cover Tc hours 0.083 s Cover Tc hours 0.0833 s Cover Tc bours S Cover Tc bours S Cover Tc bours S Cover Tc S Cover Tc S Cover S	8% $5 \times Tc) =$ A Flow Sum Cn - 79 0% $5 \times Tc) =$ AB Flow Sum Cn - 79 5% $5 \times Tc) =$ 5 Flow Sum Cn - 79 5% $5 \times Tc) =$ $4 1$ Flow Sum Cn - 79 0% $5 \times Tc) =$ $4 2$ Flow Sum Cn - 79 0% $5 \times Tc) =$ $4 2$ Flow Sum Cn - 79 0% $5 \times Tc) =$ $6 \times Tc) =$ 79 0% $5 \times Tc) =$ 79	0.0498 mary Q2 cfs 1.2 0.0498 0.0498 mary Q2 cfs 0.6 0.0498 0.055 0.05 0.055 0	Q10 cfs 2 Q10 cfs 1 Q10 cfs 0.3 Q10 cfs 0.3 Q10 cfs 0.3 Q10 cfs 0.3	Q25 cfs 3.1 Q25 cfs 1.5 Cfs 1.5 Q25 cfs 0.4 Q25 cfs 0.4 Q25 cfs 0.4	Q50 cfs 3.4 Q50 cfs 1.6 Q50 cfs 0.5 0.5 0.5	Q100 cfs 4.3 Q100 cfs 2 Q100 cfs 0.6 Q100 cfs 1.2 Q100 cfs 1.2
	segment total H TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total M TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) Segment total HY TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total HY TR-55 SCS Lag Time (hours Segment #2	segment total <i>time of conc.(h</i> <i>YDROLOGIC</i> Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>YDROLOGIC</i> Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>YDROLOGIC</i> Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>DROLOGIC</i> Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>DROLOGIC</i> Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>ROLOGIC</i> Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>ROLOGIC</i> Stal Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>ROLOGIC</i> Stal <i>Channelized</i> Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>ROLOGIC</i> Stal <i>Channelized</i> Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>ROLOGIC</i> Stal <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channelized</i> <i>Channe</i>	0 0.083 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	Imperviou SCS Lag Area acres 0.57 Imperviou SCS Lag ARY for Area acres 0.26 MARY for SCS Lag MARY for Area acres 0.08 MARY for Area acres 0.08 MARY for Area acres 0.08 MARY for SCS Lag ARY for Area acres 0.16 Area acres	s Cover Time (pr DA 2 Tc hours 0.083 s Cover Trome (pr DA 2 for DA 2	8% $5 \times Tc) =$ A Flow Sum Cn - 79 0% $5 \times Tc) =$ A Flow Sum Cn - 79 5% $5 \times Tc) =$ 5% Flow Sum Cn - 79 5% $5 \times Tc) =$ $6 \times Tc) =$ $6 \times Tc) =$ 79 0% $5 \times Tc) =$ 79	0.0498 mary Q2 cfs 1.2 0.0498 mary Q2 cfs 0.6 0.0498 mary Q2 cfs 0.2 0.0498 mary Q2 cfs 0.2 0.0498 mary Q2 cfs 0.2 0.0498 mary Q2 cfs 0.2 0.0498 mary Q2 cfs 0.05 mary Q2 cfs 0.05 mary Mar	Q10 cfs 2 Q10 cfs 1 Q10 cfs 0.3 Q10 cfs 0.3 Q10 cfs 0.3 Q10 cfs 0.3 Q10 cfs 0.3	Q25 cfs 3.1 Q25 cfs 1.5 Q25 cfs 0.4 Q25 cfs 0.4 Q25 cfs 0.4 Q25 cfs 0.4 Q25 cfs 0.4	Q50 cfs 3.4 Q50 cfs 1.6 Q50 cfs 0.5 0.5 0.5 0.5 0.5 0.5	Q100 cfs 4.3 Q100 cfs 2 Q100 cfs 0.6 Q100 cfs 1.2 Q100 cfs 1.2
	segment total H TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total M TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total M TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total MY TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total MY TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft)	segment total <i>time of conc.(h</i> <i>YDROLOG/C</i> Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>YDROLOG/C</i> Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>YDROLOG/C</i> Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>DROLOG/C</i> Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>DROLOG/C</i> Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>DROLOG/C</i> Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>ROLOG/C</i> Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>ROLOG/C</i> Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>ROLOG/C</i> Segment #3 Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment fotal <i>time of conc.(h</i> <i>ROLOG/C</i> <i>S</i> <i>Segment #3</i> <i>Channelized</i> <i>ROLOG/C</i> <i>S</i> <i>Segment #3</i> <i>Segment #3</i> <i>Segme</i>	0 0.083 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	Imperviou SCS Lag ARY fo Area acres 0.57 Imperviou SCS Lag ARY fo Area acres 0.26 Imperviou SCS Lag MARY fo Area acres 0.08 Imperviou SCS Lag ARY fo Area acres 0.08 Imperviou SCS Lag ARY fo Area acres 0.16 Area acres 0.16	IS Cover Time (Dr DA 2 Tc hours 0.083 IS Cover Time (Dr DA 2 Tc hours 0.083 IS Cover Trime (Cor DA Tc hours 0.083 IS Cover Time (Cor DA Tc hours 0.083 IS Cover Trime (Cor DA IS Cover IS Cover	8% $5 \times Tc) =$ A Flow Sum Cn - 79 AB Flow Sum Cn - 79 5% $5 \times Tc) =$ 5% Flow Sum Cn - 79 5% $5 \times Tc) =$ $4 7$ Flow Sum Cn - 79 0% $5 \times Tc) =$ $4 2$ Flow Sum Cn - 79 0% $5 \times Tc) =$ $6 \times Tc) =$ 79 0% $5 \times Tc) =$ 79 0% 79 79 0% 79 79 79 79 79	0.0498 mary Q2 cfs 1.2 0.0498 0.049 0.0498 0.049 0.0498 0.049 0.0498 0.049 0.0498 0.049 0.04	Q10 cfs 2 2 Q10 cfs 1 Q10 cfs 1 Q10 cfs 0.3 Q10 cfs 0.5 Q10 cfs 0.5 Q10 cfs 0.5 Q10 cfs 0.5 Q10 cfs 0.5 Q10 cfs 0.5 Q10 cfs 0.5 Q10 cfs 0.5 Q10 cfs 0.5 Q10 cfs 0.5 Q10 cfs Q10	Q25 cfs 3.1 Q25 cfs 1.5 Q25 cfs 0.4 Q25 cfs 0.4 Q25 cfs 0.4 Q25 cfs 0.4 Q25 cfs 0.4 Q25 cfs 0.4 Q25 cfs 0.4	Q50 cfs 3.4 Q50 cfs 1.6 Q50 cfs 0.5 0.5 Q50 cfs 0.5 Q50 cfs 0.5 Q50 cfs 0.5 Q50 cfs 0.5 Q50 cfs Q50 cfs Q50 cfs Q50 cfs Q50 cfs Q50 Q50 cfs Q50 cfs Q50 cfs Q50 Cfs Cfs Cfs Cfs Cfs Cfs Cfs Cfs Cfs Cfs	Q100 cfs 4.3 Q100 cfs 2 Q100 cfs 2 Q100 cfs 0.6 Q100 cfs 1.2 Q100 cfs 1.2 Q100 cfs 39.3
	segment total H TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total TR-55 SCS Lag Time (hours Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) Segment total Unpaved Length (ft) Slope (%) segment total Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total Segment #2 Shallow Concent Unpaved Length (ft) Slope (%) segment total	segment total <i>time of conc.(h</i> <i>YDROLOGIC</i> <i>Segment #3</i> Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>YDROLOGIC</i> <i>Segment #3</i> Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>YDROLOGIC</i> <i>Segment #3</i> Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>DROLOGIC</i> <i>Segment #3</i> Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>DROLOGIC</i> <i>Segment #3</i> Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>CROLOGIC</i> <i>Segment #3</i> Channelized Mannings "n" Length (ft) Slope (%) Velocity (fps) segment total <i>time of conc.(h</i> <i>ROLOGIC</i> <i>Segment #3</i> <i>Channelized</i> <i>Channelized</i> <i>Segment #3</i> <i>Channelized</i> <i>Segment #3</i> <i>Segment #3</i> <i>Segment #3</i> <i>Segment #3</i> <i>Segment #3</i> <i>Segment </i>	0 0.083 5 5 5 5 5 0 0 0 0 0 0 0 0 0 0 0 0 0 0	Imperviou SCS Lag Area acres 0.57 Imperviou SCS Lag Area acres 0.26 Area acres 0.26 Imperviou SCS Lag MARY for Area acres 0.08 Imperviou SCS Lag ARY for Area acres 0.08 Imperviou SCS Lag ARY for Area acres 0.16 Imperviou SCS Lag ARY for Area acres 2.86	IS Cover Time (.4 Tre (.4 Tc hours 0.083 IS Cover Trime (.4 IS Cover Trime (.4 I	8% $5 \times Tc) =$ A Flow Sum Cn - 79 0% $5 \times Tc) =$ A Flow Sum Cn - 79 5% $5 \times Tc) =$ 5% $5 \times Tc) =$ 5% $5 \times Tc) =$ 79 0% $5 \times Tc) =$ 79 0%	0.0498 mary Q2 cfs 1.2 0.0498 0.049 0.0498 0.0498 0.049 0.049 0.0498 0.049	Q10 cfs 2 Q10 cfs 1 Q10 cfs 0.3 Q10 cfs 12.2 Q10 cfs 12.2 Q10 cfs 12.2	Q25 cfs 3.1 Q25 cfs 1.5 Q25 cfs 0.4 Q25 cfs 0.4 Q25 cfs 0.4 Q25 cfs 0.4	Q50 cfs 3.4 Q50 cfs 1.6 Q50 cfs 0.5 0.5 Q50 cfs 19.9 Q50 cfs 19.9	Q100 cfs 4.3 Q100 cfs 2 Q100 cfs 2 Q100 cfs 2.3.8 Q100 cfs 1.2 Q100 cfs 39.3

		Detention P	ond Depth	v. Storage v	. Outflow for	MOD. J	-вох	
		Accumulated			Accumulated			
	Depth	Depth	Area	Volume	Volume		Outflow	
Elevation	(ft.)	(ft.)	(sf.)	(cf.)	(cf.)	allow.rel	(cfs.)	Remarks
731.5	0	0	25.00	0.00	0.00			
732	0.5	0.5	25.00	12.50	12.50			
733	1	1.5	25.00	25.00	37.50		10.30	2 YR.
733.4	0.4	1.9	25.00	10.00	47.50		14.60	10 YR.
734	0.6	2.5	25.00	15.00	62.50			
734.2	0.2	2.7	25.00	5.00	67.50		19.90	25 YR.
734.5	0.3	3	25.00	7.50	75.00		21.20	50 YR.
735	0.5	3.5	25.00	12.50	87.50			
735.6	0.6	4.1	25.00	15.00	102.50		26.70	100 YR.
736	0.4	4.5	25.00	10.00	112.50			
737	1	5.5	25.00	25.00	137.50			
738	1	6.5	25.00	25.00	162.50			
739	1	7.5	25.00	25.00	187.50			
740	1	8.5	25.00	25.00	212.50			
741	1	9.5	25.00	25.00	237.50			

	D	etention Po	nd Depth v	. Storage v.	Outflow for M	NOD. J-	BOX 2	
		Accumulated			Accumulated			
	Depth	Depth	Area	Volume	Volume		Outflow	
Elevation	(ft.)	(ft.)	(sf.)	(cf.)	(cf.)	allow.rel	(cfs.)	Remarks
731.46	0	0	25.00	0.00	0.00			
732	0.54	0.54	25.00	13.50	13.50			
733	1	1.54	25.00	25.00	38.50			
733.6	0.6	2.14	25.00	15.00	53.50		8.80	2 YR.
734	0.4	2.54	25.00	10.00	63.50			
734.2	0.2	2.74	25.00	5.00	68.50		13.30	10 YR.
734.6	0.4	3.14	25.00	10.00	78.50		17.2	25 YR.
704.0	0.4	0.14	25.00	10.00	70.50		17.7	50 YR.
735	0.4	3.54	25.00	10.00	88.50			
735.1	0.1	3.64	25.00	2.50	91.00		23.30	100 YR.
736	0.9	4.54	25.00	22.50	113.50			
737	1	5.54	25.00	25.00	138.50			
738	1	6.54	25.00	25.00	163.50			
739	1	7.54	25.00	25.00	188.50			
740	1	8.54	25.00	25.00	213.50			
741	1	9.54	25.00	25.00	238.50			

LL RESPONSIBILITY FOR THE ADEQUACY OF THESE PLANS REMAINS WITH THE ENGINEER WHO PREPARED THEM. IN REVIEWING THESE LANS, THE CITY MUST RELY UPON THE ADEQUANCE OF THE WORK OF THE DESIGN ENGINEER.	E: 05/15/202 [°]			I. SPai CHK. SPe
<image/> <text><text><text></text></text></text>	SITE DEVELOPMENT IMPROVEMENTS	ROUND ROCK CHRISTIAN ACADEMY	800 WESTWOOD DRIVE	ROUND ROCK, TEXAS 78681
	- Pierce	ure + Interiors, Inc.	Round Rock, Texas 78664	Email: spai@sp-ai.com Web Site: www.sp-ai.com
	Spencer - Pierce	Architecture + Interiors, Inc.	110 N. STONE Round Rock, Texas 78664	Phone: (512) 388-0677 Fax: (512) 388-0752 Email: spai@sp-ai.com Web Site: www.sp-ai.com
	Spencer - Pierce	Architecture + Interiors, Inc.	110 N. STONE Round Rock, Texas 78664	Phone: (512) 388-0677 Fax: (512) 388-0752 Email: spai@sp-ai.com Web Site: www.sp-ai.com

Texas Co	mmission on Environmental Quality							
TSS Remo	val Calculations 04-20-2009			Project Name:	RRRR			
				Date Prepared:	12/2/2022			_
<u>1. The Requir</u>	ed Load Reduction for the total project:	Calculations fr	om RG-348		Pages 3-27 to 3-3	30		
	Page 3-29 Equation 3.3: L_{M} =	27.2(A _N x P)						
where	LM TOTAL PROJECT =	Required TSS	removal resu	Ilting from the propose	d development = 8	30% of in	creased loa	d
	A _N =	Net increase in	n impervious	area for the project				
Site Data	: Determine Required Load Removal Based on the Entire Projection County =	ct Williamson	•					
	Total project area included in plan * = Predevelopment impervious area within the limits of the plan * =	4.91	acres acres					_
Total p	ost-development impervious area within the limits of the plan* =	2.26	acres					
	P =	32	inches					
	L _{M TOTAL PROJECT} =	1967	lbs.					
* The values	entered in these fields should be for the total project area	a.						
Nu	mber of drainage basins / outfalls areas leaving the plan area =	1						
2. Drainage B	asin Parameters (This information should be provided for	<u>each basin):</u>						-
	Drainage Basin/Outfall Area No. =	1	•					
	Total drainage basin/gutfall area -	10.00	acres					_
Pred	evelopment impervious area within drainage basin/outfall area =	0.13	acres					_
Post-deve	evelopment impervious area within drainage basin/outiali area = elopment impervious fraction within drainage basin/outfall area =	0.57	acres					
	L _M this basin =	4848	lbs.					_
3. Indicate the	e proposed BMP Code for this basin.							
	Proposed BMP =	Sand Filter						
4. Calculate N	Removal emciency = Maximum TSS Load Removed (L _R) for this Drainage Basin	by the select	ed BMP Typ	<u>e.</u>				
	RG-348 Page 3-33 Equation 3.7: L _R =	BMP efficience	y) x P x (A ₁ :	x 34.6 + A _P x 0.54)				-
whore		Total On Site	drain ago aros	in the PMD establish	nt aroa			
where		Impervious are	a proposed in	n the BMP catchment	area		-	-
	A _P =	Pervious area	remaining in	the BMP catchment a	rea			
	L_R =	ISS Load rem	ioved from thi	is catchment area by t	ne proposed BIVIF			
	A _C =	10.00	acres					
	A _P =	4.30	acres				-	-
	L _R =	5683	lbs					
5. Calculate F	raction of Annual Runoff to Treat the drainage basin / ou	tfall area						
	Desired L _{M THIS BASIN} =	4848	lbs.					
	F =	0.85	•					-
6. Calculate 0	Capture Volume required by the BMP Type for this drainad	ne basin / outf	all area.	Calculations from RG	-348	Pages 3	-34 to 3-36	
	Rainfall Depth =	1.32	inches					
	On-site Water Quality Volume =	19146	cubic feet					
		Calculations fr	om RG-348	Pages 3-36 to 3-37				
	Off-site area draining to BMP = Off-site Impervious cover draining to BMP =	0.00	acres acres					_
	Impervious fraction of off-site area = Off-site Runoff Coefficient =	0 00						
	Off-site Water Quality Volume =	0	cubic feet					
	Storage for Sediment =	3829						
Total Ca 9. Filter area	apture Volume (required water quality volume(s) x 1.20) = for Sand Filters	22975 Designed as F	cubic feet Required in R	G-348	Pages 3-58 to 3-	63		
	9A. Full Sedimentation and Filtration System							_
	Water Quality Volume for sedimentation basin =	22975	cubic feet					-
	Minimum filter basin area -	1064	square feet					-
	Maximum codimentation basis area -	0572	square feet	For minimum wet	r denth of 2 feet			
	Minimum sedimentation basin area =	2393	square feet	For maximum wate	r depth of 2 feet r depth of 8 feet	¢		_
								-
	9B. Partial Sedimentation and Filtration System							_
	Water Quality Volume for combined basins =	22975	cubic feet					-
	Minimum filter basin area =	1915	square feet					_
	Maximum sedimentation basin area =	7658	square feet	For minimum water	r depth of 2 feet			-
		413	Square ICCl	. or maximum wate		-		-

SS Removal Calculations of 4-20-2009 The Required Lass Resonant terms total preset: The Resonant terms total preset: The Resonant terms te	Fexas Cor	nmission on Environmental Quality						
The second of a construction for the load property of a construction of the property o	rss Remov	al Calculations 04-20-2009			Project Name: Date Prepared:	RRCA 12/2/2022		
	The Pequire	d Load Reduction for the total project:	Calculations fr	om PC-348		Dages 3.27 to 3	30	
Pipe 3-28 Equation 3.3 Let 272.0x, 7.0 uncer Let mode interpret	. The Require					Fages 5-27 10 5-	50	
Interest Line mature (b) Projection of the project devices and the project devices of the projection of the projection of the projectio		Page 3-29 Equation 3.3: L_M =	27.2(A _N x P)					
A_1 End inclusion A_2 End inclusion Interpretation on the page: Bite Data Determine Required Load Removal Based on the Exitive Paget A sharpe status Page status status	where:		Required TSS	removal resu	Iting from the propose	d development = 8	30% of in	creased loa
P = Accord and precision of the the provided on provide set on the first of the provide set on the provide set on the provide set on th	intere.	A _N =	Net increase in	n impervious	area for the project			
Site Data. Determine Required Load Removal faces on the Entity Fuel Internet Total project area notation in parts - 10.2 areas - 10.2 a		P =	Average annua	al precipitation	n, inches			
Control Register Register Control R	Site Data:	Determine Required Load Removal Record on the Entire Drain	ot					
Total project area within the funct of page 1 0.13 order Total post-development improvant own file builts of the data of the total page 1 0.14 order Star paid development improvant own file builts of the data order 0.14 order 0.14 Star paid development improvant own file builts of the data page 1 0.14 0.14 0.14 The values endered in these fields doubt de tor the total page 1 0.14 0.14 0.14 The values endered in these fields doubt de tor the total page 1 0.14 0.14 0.14 Databage Basic/Duffall Area fields 0.10 order 0.14 0.14 Production repressons area within the initial page 1 0.10 order 0.14 0.14 Production repressons area within the initial page 1 0.10 order 0.15 order Production repressons area within the initial page 1 0.10 order 0.15 order Production repressons area within the initial page 1 0.10 order 0.16 order Initial transmost in total the initial transmost initial transmost in total transmost in the initial transmost initial transmost initial transmost initial transmost initial transmost init	Sile Dala.	County =	Williamson					
Teledecognet improves and with he limits of the part is the sector of the part of the sector o		Total project area included in plan * =	8.73	acres				
Non-overlage State Just disargement important core lice to a state Just disargement interaction and core lice to a state Just disargement interaction and core lice to a state Just disargement interaction and core lice to a state Just disargement interaction and core lice to a state Just disargement interaction and the state Just disargement interaction and Justate Just disargement interaction and Filtration Statement and Ju	F	Predevelopment impervious area within the limits of the plan * =	0.13	acres				
Image: Second	rotarpe	Total post-development impervious cover fraction * =	0.39	acres				
He rous maked 2881 Its. Its. The values entered in these fields should be for the total project area. 1 Its. Its. Number of damage basis / outbills eroses leaving the plan area 1 Its. Its. Its. Databage Basis / outbills eroses leaving during basis/outbill area 1.00 onces Its. Its. Declarge Basis / outbills eroses basis/outbill area 0.00 onces Its. Its. Its. Post-development imperiods area within damage basis/outbill area 0.00 onces Its. Its. Its. Indicate the proposed BMP Code for this basis. Proposed BMP Code for this basis. Its. Its. Its. Its. Catolate Maximum T38 Load Removed Luke to this Rainane Basis Areb. Its. Its. Its. Its. Its. Catolate Maximum T38 Load Removed Luke to this Rainane Basis Areb. Its.		P =	32	inches				
The values entend in these failed shall be for the total project area. Number of desinge basins / outsils areas leaving the plan area in in the second in these failed shall be provided for each basins in the second in the second in desings basins of the second in the second in desings basins of the second in the second in desings basins of the second interest in the second interest interest in the second interest interest in the second interest interest interest in the second interest								
Number of duringe basiss / outfalls areas leaving the plan area = 1 Darinage Basis / outfalls areas leaving the plan area = 1 Darinage Basis / outfalls areas leaving the plan area = 1 Darinage Basis / outfalls areas leaving the plan area = 1 Darinage Basis / outfalls areas leaving the plan area = 1 Darinage Basis / outfall area = 0.03 Protecleapment imperices area within dranage basis / outfall area = 0.13 Protecleapment imperices area within dranage basis / outfall area = 0.13 Protecleapment imperices area within dranage basis / outfall area = 0.13 Protecleapment imperices area within dranage basis / outfall area = 0.13 Protecleapment imperices area within dranage basis / outfall area = 0.13 Indicate the proposed BMP Code for this basis. Proto decisioned III for this Basis. Proto decisioned III for this Basis. Proto decisioned III for this Basis / III for the selected BMP True. RIS-546 Page 5:35 Equation 37: Leaving Basis / Add III for the selected BMP True. RIS-546 Page 5:35 Equation 37: Leaving Basis / Add III for the selected BMP True. RIS-546 Page 5:35 Equation 37: Leaving Basis / Add III for the selected BMP True. RIS-546 Page 5:35 Equation 37: Leaving Basis / Add III for the selected BMP True. RIS-546 Page 5:35 Equation 37: Leaving Basis / Add III for the selected BMP True. RIS-546 Page 5:35 Equation 37: Leaving Basis / Add III for the selected BMP to the maximum differ BMP exist ment area A = Protors area protopoid III to EMP exist ment area A = Protors area protopoid III to EMP exist ment area A = Protors area protopoid III to EMP exist ment area A = Protors area protopoid III to EMP exist ment area A = Protors area protopoid III to EMP exist ment area A = Protors area protopoid III to EMP exist ment area A = Protors area protopoid III to EMP exist ment area A = Protors area protopoid IIII to EMP exist ment area A = Protors area protopoid III to EMP exist ment area A = Protors area protopoid III to EMP exist ment area A = Protors area protopoid IIII to EMP exist ment area A = Protors area protopoid III	The velue of		2881	IDS.				
Number of drainage basins / cutilsis areas leaving the plan area = 1 1 Decinate Basin Parameters (This information should be provided for each basin): 1 1 Total drainage basins/offil area = 10.00 orea = Packedecynett importus sets with drainage basins/offil area = 5.70 orea = Pack devecynett importus sets with drainage basins/offil area = 5.70 orea = Pack devecynett importus sets with drainage basins/offil area = 5.70 orea = Pack devecynett importus sets with drainage basins/offil area = 5.70 orea = Pack devecynett importus sets with area = 5.70 orea = Pack devecynett importus sets with area = 5.70 orea = Pack devecynett importus sets with area = 6.70 orea = Calculate Maximum T3S Load Removed La for Bits Basin La Hass effect BMP Type. BMP effortune xet A Calculate Maximum T3S Load Removed La for Bits Information area = A = Information area = Information area = La = Stat Information area = A = Information area = Information area = Calculate Reaction of Annual Runoff to Tract the dealanage babin / outful area. Calculates tran RG-34	The values of	entered in these fields should be for the total project area						
Decinage Basin Parameters (This information should be provided for each basin): 1 1 Datange Basin Oxfall Area Ro. 1 1 Preservationment mometors area within datange basin oxfall area 0.00 cores Preservationment mometors area within datange basin oxfall area 0.00 cores Post-devolution imports area within datange basin oxfall area 0.01 cores Post-devolution imports area within datange basin oxfall area 0.02 cores Post-devolution imports area within datange basin oxfall area 0.02 cores Post-devolution imports area within datange basin oxfall area 0.02 cores Removed BMP Code for bits basin Processed BMP Code for bits basin area state of the selected BMP Type. Removed BMP Code for bits basin area state of the selected BMP Type. area state of the BMP codehenet area A = brockow area proceed BMP Code for BMS basin area state of the BMP codehenet area A = brockow area proceed BMP codehenet area A = brockow area proceed BMP Code for BMP Type to this datage basin of outfall area basin basin area basin for the selected BMP Type to the selected BMP to tothereat area A = brockow area proceed BMP coth	Nur	hber of drainage basins / outfalls areas leaving the plan area =	1					
Detainage Bain Parameters (This Information should be provide for each bain): Image Bain Parameters (This Information should be provide for each bain): Image Bain Parameters (This Information should be provide for each bain): Productionent importious area within dramage basin/offill area = 0.00 0.03 acros 1 <td< td=""><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></td<>								
Definition of Annual Runoff to Treat the drainage basin/ Cuttini area A series Prot-development impervious area within drainage basin/ Cuttini area 0.00 arres Prot-development impervious area within drainage basin/ Cuttini area 0.00 arres Prot-development impervious area within drainage basin/ Cuttini area 0.00 arres Prot-development impervious area within drainage Basin/ Cuttini area 0.00 arres Prot-development impervious area within drainage Basin/ Cuttini area 0.00 arres Prot-development impervious frontinis Calainae Basin Calculate Maximum T85 Load Removed La Ior this Danianae Basin but hus subcated BMP Type. Removed frontinis Calainae Basin Cuttinia area A set for the development area A set for the development area A set for the development area A set for the development area A set for the development area A set for the development area A set for the development area A set for the development area A set for the dev								
Drainage Basin/Outbill Area No. 1 Total drainage basin/Outbill area 0.00 acros Prodeexignent impervious rection with drainage basin/Outbill area 0.00 acros 0.00 acros Paid-devicement impervious rection with drainage basin/Outbill area 0.00 acros 0.00 acros Paid-devicement impervious rection with drainage basin/Outbill area 0.00 acros 0.00 acros Indicate the proposed BMP Code for this basin. Peroposed BMP = Sand Filter 80 percent 6449 bs. Indicate the proposed BMP = Sand Filter 80 percent 6449 bs. 6449 bs. Indicate the proposed BMP = Sand Filter 80 percent 6449 bs. 6449 bs. Indicate the proposed BMP = Sand Filter 80 percent 6449 bs. 6449 bs. 6449 bs. 655 6449 bs. 655 6449 bs. 655 6449 bs. 6450 6450 6450 6450 6450 6450 6450 6450 6450 6450	. Drainage Ba	asin Parameters (This information should be provided for	each basin):					
Calculate Note: Construction Prode-decoment impervious area within damage basin control area = 0.13 erres = 0.13 Prode-decoment impervious area within damage basin control area = 0.13 erres = 0.13 Prode-decoment impervious area within damage basin control area = 0.13 erres = 0.13 Indicates the proposed BMP Code for this basin. Prode-decoment impervious area within damage basin but the selected BMP Type. Calculate Maximum TBS Load Removed L_1 for this Datagea Basin but the selected BMP Type. Sand Filter Recover and the proposed BMP Code for this basin. Prode-deciment impervious erea proposed Int the SMP colchment area A = profess area remaining in the SMP colchment area A = profess area remaining in the SMP colchment area A = 0.00 where A = 0.00 erres = 0.00 A = 0.00 erres = 0.00 erres = 0.00 A = 0.00 erres = 0.00 erres = 0.00 A = 0.00 erres = 0.00 erres = 0.00 A = 0.00 erres = 0.00 erres = 0.00 A = 0.00 erres = 0.00 erres = 0.00 A = 0.00 erres = 0.00 erres = 0.00 A = 0.00 erres = 0.00 erres = 0.00 A = 0.00 erres = 0.00 erres = 0.00 <		Drainage Basin/Outfall Area No. =	1					
Total dominange basin/outil area 0.00 acres Prodi development imprevolas mete within dominang basin/outil area 0.71 acres Prodi development imprevolas mete within dominang basin/outil area 0.77 acres Prodi development imprevolas mete within dominang basin/outil area 0.77 acres Indicate the processor BMP Code for this basin. Promoval Technicanes 680 Prodi development imprevolas meter Workson Basin the Second Piller 680 procett Calculate Maximum TBS Load Removed Linfor this Datames Basin the basin Basin the Basic BBP Code moved and Linform this Calculate Maximum TBS Load Removed Linform this Calculate Basin the Basic Basin the Basic Basin the Basic BBP code moved and Linform this Calculate Basin the Basic Basin the Basic Basin the Basic BBP code moved and Linform tarea A		Stanlage Bachteradul Alou No						
Production of Annual Runoff to Treat the drainage basin voltage and the BMP Catchered runa and the BMP	Drode	Total drainage basin/outfall area =	10.00	acres				
Desidelegnment imperdues faction within drainage basin/outbil area 0.57 Lig recorded BMP Code for this basin. Proposed BMP Code for this basin. Proposed BMP Code for this basin. Proposed BMP Code for this basin. Calculate Maximum TSS Lead Removed (La) for his Domaine Basin but	Post-de	evelopment impervious area within drainage basin/outfall area =	5.70	acres				
Let mis zeam 4848 Ds. Indicate the proposed BMP Code for this bain. Remotel efficery > - 80 porcent Calculate Maximum TSS Load Removed (La) for this Damage Basin to the Balecket BMP Type. RC3486 Page 335 Equation 3.7. La (BMP efficiency) P X (A x 34.6 + A, x 0.54) where A ₂ = Total Ch-Site drainage area in the BMP Catchment area A ₂ = Pay (BMP efficiency) P X (A x 34.6 + A, x 0.54) where A ₂ = Total Ch-Site drainage area in the BMP catchment area A ₂ = Pay (BMP efficiency) P X (A x 34.6 + A, x 0.54) where A ₂ = Total Ch-Site drainage area in the BMP catchment area A ₂ = Pay (BMP efficiency) P X (A x 34.6 + A, x 0.54) Lin = Stoad temoord from this catchment area A ₂ = Total Ch-Site drainage basin / outfull area A ₂ = Stoad temoord from this catchment area A ₂ = Calculate Fraction of Annual Runoff to Treat the drainage basin / outfull area Desired La res Basin B484 Ds. F = 0.85 Calculations from RG-349 Pages 3-34 to 3.36 Calculate Capture Volume required by the BMP Type for this drainage basin / outfull area Of-site Water Caulity Volume for a cas Of-site Imperiods case of dia teras Of-site Imperiods case of dia tera Of-site Imperiods case of di	Post-devel	opment impervious fraction within drainage basin/outfall area =	0.57					
Indicate the proposed BMP Code for this basin. Proposed BMP Code for this basin. Proposed BMP Code for this Definition of the proposed BMP Code for this Definition of the Sector Sector Code (SMP Type, Calculate Maximum TSS Load Removed (La) for this Drainage Basin by the selected BMP Type, RC-348 Page 3-33 Equation 3.7: La * (BMP efficiency) x P x (A x 34.6 + A x 0.54) where: A = Total Co-Side dimension and Filter Sector Sector Code (SMP Code) (SMP efficiency) x P x (A x 34.6 + A x 0.54) Calculate Maximum TSS Load Removed (La) for this Drainage Basin the BMP efficiency is P x (A x 34.6 + A x 0.54) where: A = Total Code (SMP Code) (SMP efficiency) x P x (A x 34.6 + A x 0.54) Calculate Coduce (SMP Code) (SMP efficiency) x P x (A x 34.6 + A x 0.54) (SMP efficiency) x P x (A x 0.64) (SMP efficiency) x P x (A x 0.64) (SMP ef		L _M this basin =	4848	lbs.				
Proposed BMP = Sand Filer percent Calculate Maximum TSS Load Removed (La) for this formande Bash to the selected BMP Tryp.	. Indicate the	proposed BMP Code for this basin.						
Proposed BWP = Sand Filter - Toreat Calculate Maximum TSS Load Removed (La) for this Drinage Basin by the selected BMP Type. RG-348 Page 3-33 Equation 37: L _R = (BMP efficiency) x P x (h; x 34.6 + A; x 0.51) where: A _c = Total Ch-Site drainage masin the BMP catchment area A _c = Total Ch-Site drainage masin the BMP catchment area A _c = Total Ch-Site drainage masin the BMP catchment area A _c = Total Ch-Site drainage masin the BMP catchment area A _c = Total Ch-Site drainage masin the BMP catchment area A _c = Total Ch-Site drainage masin the Catchment area A _c = 10.00 acres A _c = 10.00 acres A _c = 5583 bits Calculate Fraction of Annual Rumoff to Treat the drainage basin / outfall area Calculations from RG-348 Pages 3:34 to 3:36 Calculate Capture Volume required by the BMP Type for this drainage basin / outfall area Calculations from RG-348 Pages 3:34 to 3:36 Calculation for MGC-348 Pages 3:34 to 3:37 Off-site area draining to BMP = 0.00 acres Off-site area draining to BMP = Tope for this drainage basin / outfall area Calculations from RG-348 Pages 3:34 to 3:36 Calculation for MGC-348 Pages 3:36 to 3:37 Off-site area draining to BMP = 0.00 acres Off-site area draining to BM								
Calculate Maximum TSS Load Removed (L ₄) for this Drainage Basin to the selected BMP Type. R0-348 Page 3-33 Equation 3.7: L ₄ = (BMP efficiency) x P x (A _x x 34.6 + A _x x 0.54) where: A _x = Total On-Site drainage area in the BMP catchment area A _x = Total On-Site drainage area in the BMP catchment area A _x = Total On-Site drainage area in the BMP catchment area A _x = Total On-Site drainage area in the BMP catchment area A _x = Total On-Site drainage area in the BMP catchment area A _x = Total On-Site drainage area in the BMP catchment area A _x = Total On-Site drainage basin / outfall area A _x = Total On-Site drainage basin / outfall area A _x = Total On-Site drainage basin / outfall area A _x = Total On-Site drainage basin / outfall area Calculate Fraction of Annual Runoff to Treat the drainage basin / outfall area Calculations from RG 348 Desired L _x miss total 4848 Reinall Deph 1.32 Reinall Deph 1.32 Reinall Deph 1.32 On-Site Water Coulty Volume = 0.00 Off-Site area draining to BMP = 0.00 acces		Removal efficiency =	Sand Filter 89	percent				
RG-348 Page 3-33 Equation 3.7. L _n = (BMP efficiency) x P x (A, 34.8 + A ₀ x 0.54) where: A = Total Cn-Site drainage area in the BMP catchment area A = Inpervious area proposed in the BMP catchment area A = Provious area proposed in the BMP catchment area A = Provious area proposed in the BMP catchment area A = Provious area proposed in the BMP catchment area A = C 10.00 acres A = S 10.00 acres A = S 3.00 acres A = S 5683 Ibs Catculate Fraction of Annual Runoff to Treat the drainage basin / outfall area Catculators from RG-348 Pages 3-34 to 3-36 Catculate Capture Volume regulared by the BMP Type for this drainage basin / outfall area Catculations from RG-348 Pages 3-36 to 3-37 Catculate Capture Volume regulared by the BMP Type for this drainage basin / outfall area Catculations from RG-348 Pages 3-36 to 3-37 Off-site area draining to BMP = On-site Water Caulity Volume = OR-site Runoff Coefficient = OR-Site area draining to BMP = OR-Site area draining t	. Calculate M	aximum TSS Load Removed (L _R) for this Drainage Basin	by the selecte	ed BMP Type	<u>e.</u>			
Minimum Side Page 3-33 Equation 3.7. Lip = (BMP electrone); P x (R, X 36 + A x 0.04) where: A = Total On-Site drainage area in the BMP catchment area A = Derivous area remaining in the EMP catchment area A = Pervisus area remaining in the EMP catchment area A = S.70 acres Calculate Capture Volume reguined by the BMP Type for this drahage basin / outfail area. Calculations from RG-348								
where: A _c = Total On-Site drainage area in the BMP catchment area A = Impervious area proposed in the BMP catchment area A = Pervious area remaining in the BMP catchment area A = 10.00 A = 1		RG-348 Page 3-33 Equation 3.7: $L_R =$	(BMP efficienc	;y) x P x (A _l)	(34.6 + A _P x 0.54)			
A = Impervious area proposed in the BMP actohment area A ₁ = Total Continuent area A ₂ = Pervious area proposed from this actohment area L ₄ = TSS Load removed from this actohment area by the proposed BMP A ₂ = 10.00 acres A ₂ = 5883 total acres A ₄ = 5583 total acres L ₄ = 5683 total acres L ₄ = 5683 total acres L ₄ = 6000 total acres Desired L ₄ (mis sustant) 4848 Desired L ₄ (mis sustant) total acres Calculate Capture Volume required by the BMP Type for this drainage basin / outfull area, Calculations from RG-348 Post Development Rundf Coefficient = 0.00 0.00 Off-site market cousity Volume = 0.00 acres Off-site market cousity Volume = 0.00 acres Off-site market cousity Volume = 0.00 acres Off-site market cousity volume (s) x 1.209 22975	where:	A _C =	Total On-Site	drainage area	in the BMP catchme	nt area		
Are = Pervous area remaining in the BMP catchment area Lin = TSS Load removed from this catchment area by the proposed BMP Are = 10.00 acres Lin = 1000 acres Lin = 1000 acres Lin = 1000 acres Calculate Fraction of Annual Runoff to Treat the drainage basin / outfall area 100 Desired Lin mis stand 100 F = 0.85 0.85 Calculate Capture Volume required by the BMP Type for this drainage basin / outfall area. Calculations from RC-348 Post Development Runoff Coefficient = 0.40 1.32 Off-site improvidus for of off-site strone of one cres Off-site improvidus from of off-site strone of off-site strone of off-site strone of off-site strone of one cres Off-site improvidus from of off-site strone of off-site strone of one cres Off-site improvidus from of off-site strone off-site strone off-site strone off-site strone off-site strone off-site st		A _i =	Impervious are	a proposed in	n the BMP catchment	area		
Lip TSS. Load removed from this catchment area by the proposed BMP A; = 10.00 scres A; = 57.0 scres A; = 4.30 acres Lip 5683 bs Calculate Fraction of Annual Runoff to Treat the drainage basin / outfall area 4848 bs. Calculate Capture Yolume required by the BMP Type for this drainage basin / outfall area. Calculations from RG-346 Pages 3-34 to 3-36 Calculate Capture Yolume required by the BMP Type for this drainage basin / outfall area. Calculations from RG-346 Pages 3-34 to 3-36 Calculate Capture Yolume required by the BMP Type for this drainage basin / outfall area. Calculations from RG-346 Pages 3-34 to 3-36 Calculate Raming Deptine 1.32 inches 0.40 19146 cubic feet Off-site area draining to BMP 0.00 acres 0.00 acres 0.00 acres Off-site Read chaining to BMP 0.00 acres 0.00 acres<		A _P =	Pervious area	remaining in	the BMP catchment a	rea		
Ac 10.00 acres Ac 5.70 acres Ac 4.30 acres Lx 5683 lbs Calculate Fraction of Annual Runoff to Treat the drainage basin / outfall area Ibs Desired L _{AL THES RAME} 4848 lbs Calculate Capture Volume required by the BMP Type for this drainage basin / outfall area. Calculations from RG-348 Pages 3-34 to 3-36 Calculate Capture Volume required by the BMP Type for this drainage basin / outfall area. Calculations from RG-348 Pages 3-34 to 3-36 Calculate Capture Volume required by the BMP Type for this drainage basin / outfall area. Calculations from RG-348 Pages 3-34 to 3-36 Calculate Capture Volume required by the BMP Type for BMP = 10.00 acres 0.00 acres Off-site Runof Coefficient = 0.00 0.00 acres 0.00 acres Off-site Runof Coefficient = 0.00 0.00 cubic feet 0.00 acres 0.00 Off-site Runof Coefficient = 0.00 0.00 cubic feet 0.00 acres 0.00 Off-site Runof Coefficient = 0.00 0.00 cubic feet 0.00 acres 0.00 Off-site Runof Coefficient = 0.00		L _R =	TSS Load rem	oved from this	s catchment area by t	he proposed BMF)	
A 5.00 acres A 5.00 acres A 5.683 bs Calculate Fraction of Annual Runoff to Treat the drainage basin / outfall area bs Desired L _{d1 (HIS MAXIN} 4848 Desired L _{d1 (HIS MAXIN} 4848 Calculate Capture Volume required by the BMP Type for this drainage basin / outfall area. Calculations from RG-348 Pages 3-34 to 3-36 Calculate Capture Volume required by the BMP Type for this drainage basin / outfall area. Calculations from RG-348 Pages 3-34 to 3-36 Calculate Capture Volume required by the BMP Type for this drainage basin / outfall area. Calculations from RG-348 Pages 3-34 to 3-36 Calculate Capture Volume required by the BMP Type for this drainage basin / outfall area. Calculations from RG-348 Pages 3-36 to 3-37 Calculate Capture Volume required water Quality Volume in Destriet Runoff Coefficient = 0.00 acres 0.00 Off-site Runoff Coefficient = 0.00 acres 0.00 acres Off-site Runoff Coefficient = 0.00 acres 0.00 acres Off-site Runoff Coefficient = 0.00 acres 0.00 acres Off-site Runoff Coefficient = 0.00 cubic feet		A	40.00	aaraa				
Are Are acres Ln 5683 Ibs Calculate Fraction of Annual Runoff to Treat the drainage basin / outfall area Desired Latmise basin / outfall area Desired Latmise basin 4848 Desired Latmise basin 6848 F = 0.85 Calculate Capture Volume required by the BMP Type for this drainage basin / outfall area Calculations from R0-348 Post Development Runoff Coefficient = 0.40 On-site Water Quality Volume = 0.00 Off-site area draining to BMP = 0.00 Off-site mendiation of distice area 0.00 Off-site mendiation of distice area 0.00 Off-site Runoff Coefficient =		A. =	5 70	acres				
Lin = 5683 lbs Calculate Fraction of Annual Runoff to Treat the drainage basin / outfall area 4848 lbs. Desired L _{M THE BAGN} = 4848 lbs. F = 0.85 Calculate Capture Volume required by the BMP Type for this drainage basin / outfall area. Calculations from RG-348 Pages 3-34 to 3-36 Rainfail Depth = 1.32 inches 0.40 1146 cubic feet Post Development Runoff Coefficient = 0.40 cubic feet 0.40 calculations from RG-348 Pages 3-36 to 3-37 Off-site area draining to BMP = 0.00 acres 0.00 acres 0.00 acres Off-site imperious faction of off-site area 0 0.00 acres 0.00 acres Off-site moder Quilty Volume = 0 cubic feet 22975 cubic feet 5328 Total Capture Volume (required water quality volume(s) x 1.20) Designed as Required in RG-348 Pages 3-58 to 3-63 644 Storage for Sediment = 3829 cubic feet 3297 cubic feet 64 Filter area for Sand Filters Designed as Required in RG-348 Pages 3-58 to 3-63 64 square feet<		A _P =	4.30	acres				
Calculate Fraction of Annual Runoff to Treat the drainage basin / outfall area Desired L _{at THIS BASIN} = 4848 lbs. F = 0.85 Calculate Capture Volume required by the BMP Type for this drainage basin / outfall area Post Development Runoff Coefficient = On-site Water Quality Volume = 1.32 Off-site area draining to BMP = Off-site area for Same filtration System Water Quality Volume for combined basins = Z2975 cubic feet Minimum sedmentation basin area = Z2975 cubic feet Minimum water depth of 2 feet Square feet Minimum sedmentation basin area = Z2975 cubic feet Minimum sedme		L _R =	5683	lbs				
Calculate Fraction of Annual Runoff to Treat the drainage basin / outfall area Desired L _{M THSD BASIN} = 4848 bs. F = 0.85 Calculate Capture Volume required by the BMP Type for this drainage basin / outfall area. Calculations from RG-348 Pages 3-34 to 3-36 Calculate Capture Volume required by the BMP Type for this drainage basin / outfall area. Calculations from RG-348 Pages 3-34 to 3-36 Calculate Capture Volume required by the BMP Type for this drainage basin / outfall area. Calculations from RG-348 Pages 3-34 to 3-36 Calculations from RG-348 Pages 3-36 to 3-37 Off-site area draining to BMP = 0.40 Calculations from RG-348 Pages 3-36 to 3-37 Off-site impervious cover draining to BMP = 0.40 Calculations from RG-348 Pages 3-36 to 3-37 Off-site impervious faction of off-site area = 0.00 Off-site impervious faction of off-site area = 0.00 Catculations from RG-348 Pages 3-36 to 3-37 Total Capture Volume (required water quality volume (s) x 1.20 = 22975 Cubic feet Filler area for Sand Filters PA. Full Sedimentation and Filtration System Water Quality Volume for sedimentation basin area = 2383 Square feet Minimum sedimentation basin area = 22975 Subic feet Water Quality Volume for combined basins = 22975 Cubic feet Storage for Sediment = 2383 Square feet Minimum sedimentation basin area = 2383 Square feet Water Quality Volume for combined basins = 22975 Cubic feet Water Quality Volume for combined basin area = 22975 Cubic feet Minimum sedimentation basin area = 22975 Cubic feet Storage feet Storage feet Minimum sedimentation basin area = 22975 Cubic feet Minimum sedimentation basin area = 22975 Cubic feet Storage feet Minimum filter basin area = 22975 Cubic feet Minimum sedimentation basin area = 22975 Cubic feet Minimum sedimentation basin area = 22975 Cubic feet Minimum sedimentation basin area = 22975 Cubic feet Minimum filter basin area								
Calculate Fraction of Annual Runoff to Treat the drainage basin / outfall area Desired Latters basin / outfall area Desired Latters basin 4848 lbs. F = 0.85 Calculate Capture Volume required by the BMP Type for this drainage basin / outfall area. Calculations from RG-348 Pages 3-34 to 3-36 Calculate Capture Volume required by the BMP Type for this drainage basin / outfall area. Calculations from RG-348 Pages 3-34 to 3-36 Calculate Capture Volume required by the BMP Type for this drainage basin / outfall area. Calculations from RG-348 Pages 3-36 to 3-37 Colf-site Imperious cover draining to BMP = 0.40 0.40 0.40 0.40 Off-site Imperious cover draining to BMP = 0.00 acres 0 0.40 Off-site Imperious cover draining to BMP = 0.00 acres 0 0 Off-site Imperious cover draining to BMP = 0.00 acres 0 0 Off-site Imperious cover draining to BMP = 0.00 acres 0 0 0 Off-site Imperious cover draining to BMP = 0.00 acres 0 0 0 0 0 0 0 0 0 0 0 0 0								
Desired L _{M THIS BASIN} = 4848 bs. Image: Construction of the second seco	. Calculate Fi	raction of Annual Runoff to Treat the drainage basin / out	tfall area					
Desired Littinis MANN F = 0.85 Calculate Capture Volume required by the BMP Type for this drainage basin / outfall area. Calculations from RG-348 Pages 3-34 to 3-36 Calculate Capture Volume required by the BMP Type for this drainage basin / outfall area. Calculations from RG-348 Pages 3-34 to 3-36 Rainfall Depth = 1.32 inches		Desired I –	4040	llha				
F = 0.85 Calculate Capture Volume required by the BMP Type for this drainage basin / outfall area. Calculations from RG-348 Pages 3-34 to 3-36 Rainfall Depth = 1.32 inches 0.40 19146 cubic feet Post Development Runoff Coefficient = 0.40 19146 cubic feet 19146 Off-site area draining to BMP = 0.00 acres 19146 19146 Off-site moder/ous cover draining to BMP = 0.00 acres 19146 19146 Off-site moder/ous factor of off-site area 0 0.00 acres 19146 Off-site moder/ous factor of off-site area 0.00 acres 19146 19146 Off-site moder/ous factor of off-site area 0.00 acres 19146 19146 Off-site moder/ous factor of off-site area 0.00 acres 19146 19146 Off-site Water Quality Volume = 0.00 acres 1004 acres 1004 Off-site Water Quality Volume(s) x 1.20 22975 cubic feet 1014 1014 1014 1014 Water Quality Volume for sedimentation basin area = 2973 square feet 1064		Desired L _{M THIS BASIN} =	4848	IDS.				
Calculate Capture Volume required by the BMP Type for this drainage basin / outfall area. Calculations from RG-348 Pages 3-34 to 3-36 Rainfall Depth = 1.32 inches inches inches Post Development Runoff Coefficient = 0.40 cubic feet inches On-site Water Quality Volume = 19146 cubic feet inches Off-site area draining to BMP = 0.00 acres inches Off-site impervious cover draining to BMP = 0.00 acres inches Off-site moder draining to BMP = 0.00 acres inches Off-site moder draining to BMP = 0.00 acres inches Off-site Runoff Coefficient = 0.00 acres inches Off-site Water Quality Volume = 0 cubic feet inches Storage for Sediment = 3829 22975 cubic feet Filter area for Sand Filters Designed as Required in RG-348 Pages 3-58 to 3-63 9A. Full Sedimentation and Filtration System 22975 cubic feet inches Maximum sedimentation basin area = 2573 square feet inches 9B. Partial Sedimentation and Filtration System in		F =	0.85					
Calculate Capture Volume required by the BMP type for this drainage basin / outrail area, Calculations from RG-348 Pages 3-36 to 3-36 Rainfall Depth = 0.32 inches 0.40 Post Development Runoff Coefficient = 0.40 19146 cubic feet Off-site area draining to BMP = 0.40 acres 0.40 Off-site area draining to BMP = 0.00 acres 0.00 Off-site Impervious cover draining to BMP = 0.00 acres 0 Off-site Runoff Coefficient = 0 0.00 acres 0 Off-site Runoff Coefficient = 0.00 acres 0 0 Off-site Runoff Coefficient = 0.00 acres 0 0 Off-site Runoff Coefficient = 0.00 cubic feet 0 0 Storage for Sediment = 3829 22975 cubic feet 0 Eller area for Sand Filters Designed as Required in RG-348 Pages 3-58 to 3-63 0 9A. Full Sedimentation and Filtration System 22975 cubic feet 0 0 Maximum sedimentation basin area = 9573 square feet 577 maximum water depth of 2 feet 0					Online from DO	0.10	Design	04.4- 0.00
Rainfall Depth = 1.32 inches 1.32 Post Development Runoff Coefficient = 0.40 cubic feet 19146 On-site Water Quality Volume = 19146 cubic feet 19146 Off-site area draining to BMP = 0.00 acres 19146 Off-site impervious cover draining to BMP = 0.00 acres 19146 Off-site impervious cover draining to BMP = 0.00 acres 19146 Off-site impervious cover draining to BMP = 0.00 acres 19146 Off-site impervious cover draining to BMP = 0.00 acres 19146 Off-site impervious faction of Off-site are = 0 acres 19146 Off-site water Quality Volume = 0.00 cubic feet 1000 Off-site Water Quality Volume (s) x 1.20) = 22975 cubic feet 1001 Filter area for Sand Filters Designed as Required in RG-348 Pages 3-58 to 3-63 1014 Water Quality Volume for sedimentation basin area = 1064 square feet Square feet 1014 Maximum sedimentation basin area = 2393 square feet For maximum water depth of 8 feet 1014 <t< td=""><td>. Calculate C</td><td>apture Volume required by the BMP Type for this drainag</td><td>je basin / outh</td><td>all area.</td><td>Calculations from RG</td><td>-348</td><td>Pages 3</td><td>-34 to 3-36</td></t<>	. Calculate C	apture Volume required by the BMP Type for this drainag	je basin / outh	all area.	Calculations from RG	-348	Pages 3	-34 to 3-36
Rainfall Depth = 1.32 inches Post Development Rundf Coefficient = 0.40 cubic feet On-site Water Quality Volume = 19146 cubic feet Off-site area draining to BMP = 0.00 acres Off-site area draining to BMP = 0.00 acres Off-site impervious cover draining to BMP = 0.00 acres Off-site area draining to BMP = 0.00 acres Off-site area draining to BMP = 0.00 acres Off-site moervious cover draining to BMP = 0.00 acres Off-site Runoff Coefficient = 0 0 Off-site Runoff Coefficient = 0.00 acres Off-site Water Quality Volume = 0 cubic feet Storage for Sediment = 3829 22975 Filter area for Sand Filters Designed as Required in RG-348 Pages 3-58 to 3-63 9A. Full Sedimentation and Filtration System 22975 cubic feet Maximum sedimentation basin area = 9573 square feet For maximum water depth of 2 feet 9B. Partial Sedimentation and Filtration System 2333 square feet For maximum water depth of 8 feet Water								
On-site Water Quality Volume = 19146 cubic feet On-site Water Quality Volume = 19146 cubic feet Calculations from RG-348 Pages 3-36 to 3-37 Off-site impervious cover draining to BMP = 0.00 acres Off-site impervious faction of off-site area = 0 0.00 Off-site Runoff Coefficient = 0.00 acres Storage for Sediment = 3829 cubic feet Filter area for Sand Filters Designed as Required in RG-348 Pages 3-58 to 3-63 Water Quality Volume for sedimentation basin = 22975 cubic feet Minimum filter basin area = 9573 square feet Square feet For maximum water depth of 2 feet Storage feet For maximum water depth of 8 feet Storage feet Minimum filter basin are		Rainfall Depth = Post Development Runoff Coefficient =	1.32	Inches				
Off-site area draining to BMP = 0.00 acres acres acres Off-site impervicus cover draining to BMP = 0.00 acres acres acres Off-site impervicus fraction of off-site area = 0 0.00 acres acres Off-site Runoff Coefficient = 0 0.00 acres acres acres Off-site Runoff Coefficient = 0 0 cubic feet acres acres Storage for Sediment = 3829 22975 cubic feet acres acres Filter area for Sand Filters Designed as Required in RG-348 Pages 3-58 to 3-63 acres acres Water Quality Volume for sedimentation basin = 22975 cubic feet acres acres <t< td=""><td></td><td>On-site Water Quality Volume =</td><td>19146</td><td>cubic feet</td><td></td><td></td><td></td><td></td></t<>		On-site Water Quality Volume =	19146	cubic feet				
Calculations from RG-348 Pages 3-36 to 3-37 Off-site area draining to BMP = 0.00 acres Off-site Impervious fraction of off-site area = 0 acres Off-site Impervious fraction of off-site area = 0 acres Off-site Runoff Coefficient = 0.00 acres Off-site Water Quality Volume = 0 cubic feet Storage for Sediment = 3829 cubic feet Total Capture Volume (required water quality volume(s) x 1.20) = 22975 cubic feet Pilter area for Sand Filters Designed as Required in RG-348 Pages 3-58 to 3-63 Water Quality Volume for sedimentation basin = 22975 cubic feet								
Off-site area draining to BMP = 0.00 acres acres Off-site Impervious cover draining to BMP = 0.00 acres acres Impervious fraction of off-site area = 0 acres acres Off-site Runoff Coefficient = 0.00 acres acres Off-site Runoff Coefficient = 0.00 cubic feet acres Off-site Water Quality Volume = 0 cubic feet acres Storage for Sediment = 3829 22975 cubic feet Total Capture Volume (required water quality volume(s) x 1.20) = 22975 cubic feet acres Pilter area for Sand Filters Designed as Required in RG-348 Pages 3-58 to 3-63 acres Water Quality Volume for sedimentation basin = 22975 cubic feet acres Minimum filter basin area = 1064 square feet acres acres Maximum sedimentation basin area = 9573 square feet acres acres acres 9B. Partial Sedimentation and Filtration System acres 22975 cubic feet acres acres Water Quality Volume for combined basins = 22975 cubic feet <			Calculations fr	om RG-348	Pages 3-36 to 3-37			
Off-site area draining to BMP = 0.00 acres Off-site Impervious cover draining to BMP = 0.00 acres Impervious fraction of off-site area = 0 acres Off-site Runoff Coefficient = 0 cubic feet Off-site Water Quality Volume = 0 cubic feet Off-site Runoff Coefficient = 0 cubic feet Off-site Water Quality Volume(s) x 1.20) = 22975 cubic feet Filter area for Sand Filters Designed as Required in RG-348 Pages 3-58 to 3-63 9A. Full Sedimentation and Filtration System 22975 cubic feet 1 Water Quality Volume for sedimentation basin area = 1064 square feet 1 Maximum sedimentation basin area = 9573 square feet 1 1 9B. Partial Sedimentation and Filtration System 2393 square feet 1 1 Water Quality Volume for combined basins = 22975 cubic feet 1 1 9B. Partial Sedimentation and Filtration System 1 1 1 1 1 Water Quality Volume for combined basins = 22975 cubic feet 1 1 1								
Impervious fraction of off-site area = 0 Off-site Runoff Coefficient = 0.00 Off-site Water Quality Volume = 0 Cubic feet 0 Storage for Sediment = 3829 Storage for Sediment = 3829 Total Capture Volume (required water quality volume(s) x 1.20) = 22975 Filter area for Sand Filters Designed as Required in RG-348 Pages 3-58 to 3-63 Pages 3-58 to 3-63 9A. Full Sedimentation and Filtration System 22975 Water Quality Volume for sedimentation basin = 22975 Cubic feet 1064 Square feet 1064 Maximum sedimentation basin area = 9573 square feet For minimum water depth of 2 feet Water Quality Volume for combined basins area = 2393 9B. Partial Sedimentation and Filtration System 1064 Water Quality Volume for combined basins = 22975 Water Quality V		Off-site area draining to BMP = Off-site Impervious cover draining to BMP =	0.00	acres				
Off-site Runoff Coefficient = 0.00 oubic feet Off-site Water Quality Volume = 0 cubic feet Storage for Sediment = 3829 1 1 Total Capture Volume (required water quality volume(s) x 1.20) = 22975 cubic feet 1 Filter area for Sand Filters Designed as Required in RG-348 Pages 3-58 to 3-63 1 9A. Full Sedimentation and Filtration System 1 1 1 1 Water Quality Volume for sedimentation basin area = 1064 square feet 1 1 Maximum sedimentation basin area = 9573 square feet 1 1 1 9B. Partial Sedimentation and Filtration System 1 1 1 1 1 1 Water Quality Volume for combined basins area = 2393 square feet For minimum water depth of 2 feet 1 1 Water Quality Volume for combined basins = 22975 cubic feet 1 1 1 Water Quality Volume for combined basins = 2393 square feet For maximum water depth of 8 feet 1 1 Water Quality Volume for combined basins = 22975 cubic feet <t< td=""><td></td><td>Impervious fraction of off-site area =</td><td>0</td><td></td><td></td><td></td><td></td><td></td></t<>		Impervious fraction of off-site area =	0					
Storage for Sediment = 3829 a a a Total Capture Volume (required water quality volume(s) x 1.20) = 22975 cubic feet a a Filter area for Sand Filters Designed as Required in RG-348 Pages 3-58 to 3-63 a a 9A. Full Sedimentation and Filtration System Designed as Required in RG-348 Pages 3-58 to 3-63 a Water Quality Volume for sedimentation basin = 22975 cubic feet a a Maximum sedimentation basin area = 1064 square feet a a Maximum sedimentation basin area = 9573 square feet a a 9B. Partial Sedimentation and Filtration System a a a a Water Quality Volume for combined basins = 22975 cubic feet a a 9B. Partial Sedimentation and Filtration System a a a a a Water Quality Volume for combined basins = 22975 cubic feet a a a 9B. Partial Sedimentation and Filtration System a a a a a a Water Quality Volume for combined basins =		Off-site Runoff Coefficient =	0.00	cubic feet				
Storage for Sediment = 3829 and the sediment at t		Cir-site Water Quality Voume =	U					
Total Capture Volume (required water quality volume(s) x 1.20) = 22975 cubic feet Pages 3-58 to 3-63 Filter area for Sand Filters Designed as Required in RG-348 Pages 3-58 to 3-63 9A. Full Sedimentation and Filtration System Cubic feet Cubic feet Water Quality Volume for sedimentation basin = 22975 cubic feet Cubic feet Minimum filter basin area = 1064 square feet For minimum water depth of 2 feet Maximum sedimentation basin area = 2393 square feet For maximum water depth of 8 feet 9B. Partial Sedimentation and Filtration System Cubic feet Cubic feet Cubic feet Water Quality Volume for combined basins = 22975 cubic feet Cubic feet Water Quality Volume for combined basins = 22975 cubic feet Cubic feet Minimum filter basin area = 1915 Square feet Cubic feet		Storage for Sediment =	3829					
Filter area for Sand Filters Designed as Required in RG-348 Pages 3-58 to 3-63 9A. Full Sedimentation and Filtration System	Total Ca	pture Volume (required water quality volume(s) x 1.20) =	22975	cubic feet	2.248	Deres 0.50 (~~	
9A. Full Sedimentation and Filtration System Image: Syste	Filter area f	or Sand Filters	Designed as F	kequired in R	J-340	Pages 3-58 to 3-	03	
Water Quality Volume for sedimentation basin = 22975 cubic feet		9A. Full Sedimentation and Filtration System						
White is search and y volume is search and any volume is search any volume is any volume is any volume is search any vol		Water Quality Volume for sedimentation basin -	22075	cubic feet				
Minimum filter basin area = 1064 square feet Image: Square feet <td></td> <td>water squarty vourne to southolitation pasifi =</td> <td>22313</td> <td></td> <td></td> <td></td> <td></td> <td></td>		water squarty vourne to southolitation pasifi =	22313					
Maximum sedimentation basin area = 9573 square feet For minimum water depth of 2 feet Minimum sedimentation basin area = 2393 square feet For maximum water depth of 8 feet 9B. Partial Sedimentation and Filtration System Image: Complex System Image: Complex System Image: Complex System Water Quality Volume for combined basins = 22975 cubic feet Image: Complex System Minimum filter basin area = 1915 Square feet Square feet		Minimum filter basin area =	1064	square feet				
Minimum sedimentation basin area = 2393 square feet For maximum water depth of 8 feet 9B. Partial Sedimentation and Filtration System		Maximum sedimentation basin area =	9573	square feet	For minimum wate	r depth of 2 feet		
9B. Partial Sedimentation and Filtration System Image: Complexity of the set of the se		Minimum sedimentation basin area =	2393	square feet	For maximum wate	er depth of 8 feet		
9B. Partial Sedimentation and Filtration System Image: Comparison of the system Image: Comparison of the system Water Quality Volume for combined basins = 22975 cubic feet Minimum filter basin area = 1915 square feet								
Water Quality Volume for combined basins = 22975 cubic feet		9B. Partial Sedimentation and Filtration System						
Water Quality Volume for combined basins = 22975 cubic feet Minimum filter basin area = 1915 square feet								
Minimum filter basin area = 1915								
		Water Quality Volume for combined basins =	22975	cubic feet				

Maximum sedimentation basin area =7658square feetFor minimum water depth of 2 feetMinimum sedimentation basin area =479square feetFor maximum water depth of 8 feet

ВМР АССС	UNTING	TABLE	
Contributing Projects	Lm (lbs.)	WQV Required (cf)	WQV Provided (cf)
Round Rock Christian Academy	2881	22075	44214
Round Rock Retirement Residences	1967	ZZATJ	44214

	Depth Vs Storage Sedimentation Pond									
	Remarks	Accumul.	Volume	Area	Accumul	Depth	Elevation			
		Volume			Depth					
		0	0	0	0	0	728.25			
		2456.25	2456.3	6550	0.75	0.75	729			
		9006.25	6550	6550	1.75	1	730			
	> WQ Vol.	15556	6550	6550	2.75	1	731			
		22106.3	6550	6550	3.75	1	732			
		28656.3	6550	6550	4.75	1	733			
Sed/Fil		n Pond	Filtratio	Storage	epth Vs	D				
			10111111111 Mai		Accumul					
Combined	Remarks	Accumul.	Volume	Area	•	Depth	Elevation			
Volume		Volume			Depth					
(0	0	2593	0	0	728			
7642.2		5186	5186	2593	1	1	729			
16785.23		7779	2593	2593	2	1	730			
25928.25	> WQ Vol.	10372	2593	2593	3	1	731			
35071.23		12965	2593	2593	4	1	732			
and the second sec										

ALL RESPONSIBILITY FOR THE ADEQUACY OF THESE PLANS REMAINS WITH THE ENGINEER WHO PREARED THEM. IN REVIEWING THESE PLANS, THE CITY MUST REVIEWING THESE OF THE DESIGN ENGINEER.	DATE: 05/15/2023 RFV·			DRW. SPai CHK. SPe
<text><text><text></text></text></text>	SITE DEVELOPMENT IMPROVEMENTS	ROUND ROCK CHRISTIAN ACADEMY	800 WESTWOOD DRIVE	ROUND ROCK, TEXAS 78681
	Pierce	Jre + Interiors, Inc.	Round Rock, Texas 78664	Email: spai@sp-ai.com Web Site: www.sp-ai.com
	Spencer -	Architectu	110 N. STONE	Phone: (512) 388-0677 Fax: (512) 388-0752
		opyright SHF	ET	
	C	10 o SDP220	C f 32 05-000	2

GENERAL NOTES:

- 1. ALL CONSTRUCTION SHALL BE IN ACCORDANCE WITH THE CITY OF ROUND ROCK STANDARD SPECIFICATIONS MANUAL
- 2. ANY EXISTING UTILITIES, PAVEMENT, CURBS, SIDEWALKS, STRUCTURES, TREES, ETC., NOT PLANNED FOR DEMOLITION OR REMOVAL THAT ARE DAMAGED OR REMOVED SHALL BE REPAIRED OR REPLACED AT CONTRACTOR'S EXPENSE.
- 3. THE CONTRACTOR SHALL VERIFY ALL DEPTHS AND LOCATIONS OF EXISTING UTILITIES PRIOR TO ANY CONSTRUCTION. ANY DISCREPANCIES WITH THE CONSTRUCTION PLANS FOUND IN THE FIELD SHALL BE BROUGHT IMMEDIATELY TO THE ATTENTION OF THE ENGINEER WHO SHALL BE REPONSIBLE FOR REVISING THE PLANS AS APPROPRIATE.
- 4. MANHOLE FRAMES, COVERS, VALVES, CLEANOUTS, ETC. SHALL BE RAISED TO FINISHED GRADE PRIOR TO FINAL PAVING CONSTRUCTION.
- 5. THE CONTRACTOR SHALL GIVE THE CITY OF ROUND ROCK 48 HOURS NOTICE BEFORE BEGINNING EACH PHASE OF CONSTRUCTION. TELEPHONE (512)-218-5428 (PLANNING AND DEVELOPMENT SERVICES).
- ALL AREAS DISTURBED OR EXPOSED DURING CONSTRUCTION SHALL BE REVEGETATED IN ACCORDANCE WITH THE PLANS AND SPECIFICATIONS AS WELL AS THE STANDARD SPECIFICATIONS MANUAL SERIES 600. REVEGETATION OF ALL DISTURBED OR EXPOSED AREAS SHALL CONSIST OF SODDING OR SEEDING, AT THE CONTRACTOR'S OPTION. HOWEVER, THE TYPE OF REVEGETATION MUST EQUAL OR EXCEED THE TYPE OF VEGETATION PRESENT BEFORE CONSTRUCTION UNLESS.
- 7. PRIOR TO ANY CONSTRUCTION, THE ENGINEER SHALL CONVENE A PRECONSTRUCTION CONFERENCE BETWEEN THE CITY OF ROUND ROCK, HIMSELF, THE CONTRACTOR, OTHER UTILITY COMPANIES, ANY AFFECTED PARTIES AND ANY OTHER ENTITY THE CITY OR ENGINEER MAY REQUIRE.
- 8. THE CONTRACTOR AND THE ENGINEER SHALL KEEP ACCURATE RECORDS OF ALL CONSTRUCTION THAT DEVIATES FROM THE PLANS. ANY DEVIATIONS SHALL BE INCORPORATED INTO A REVISION AND APPROVED BY PLANNING AND DEVELOPMENT SERVICES. THE ENGINEER SHALL FURNISH THE CITY OF ROUND ROCK ACCURATE "AS-BUILT" RECORD DRAWINGS FOLLOWING COMPLETION OF ALL CONSTRUCTION. THESE "AS-BUILT" RECORD DRAWINGS SHALL MEET WITH THE SATISFACTION OF THE PLANNING AND DEVELOPMENT SERVICES DEPARTMENT PRIOR TO FINAL ACCEPTANCE.
- 9. THE ROUND ROCK CITY COUNCIL SHALL NOT BE PETITIONED FOR ACCEPTANCE UNTIL ALL NECESSARY EASEMENT DOCUMENTS HAVE BEEN SIGNED AND RECORDED.
- 10. WHEN CONSTRUCTION IS BEING CARRIED OUT WITHIN EASEMENTS, THE CONTRACTOR SHALL CONFINE HIS WORK TO WITHIN THE PERMANENT AND ANY TEMPORARY EASEMENTS. PRIOR TO FINAL ACCEPTANCE, THE CONTRACTOR SHALL BE RESPONSIBLE FOR REMOVING ALL TRASH AND DEBRIS WITHIN THE PERMANENT AND TEMPORARY EASEMENTS. CLEAN-UP SHALL BE TO THE SATISFACTION OF THE PLANNING AND DEVELOPMENT SERVICES INSPECTOR.
- 11. PRIOR TO ANY CONSTRUCTION, THE CONTRACTOR SHALL APPLY FOR AND SECURE ALL PROPER PERMITS FROM THE APPROPRIATE AUTHORITIES.
- 12. AVAILABLE BENCHMARKS THAT MAY BE UTILIZED FOR THE CONSTRUCTION OF THIS PROJECT ARE DESCRIBED AS FOLLOWS:

TBM #1 - MNS "JPH BENCHMARK" (SEE SP1) NAVD'88 (GEOID 18) ELEV = 741.41

TBM #2 - MNS "JPH BENCHMARK" (SEE SP1) ELEV = 747.71NAVD'88 (GEOID 18)

TRENCH SAFETY NOTES:

- IN ACCORDANCE WITH THE LAWS OF THE STATE OF TEXAS AND THE U. S. OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION REGULATIONS, ALL TRENCHES OVER 5 FEET IN DEPTH IN EITHER HARD AND COMPACT OR SOFT AND unstable soil shall be sloped, shored, sheeted, braced or otherwise supported. Furthermore, all trenches LESS THAN 5 FEET IN DEPTH SHALL ALSO BE EFFECTIVELY PROTECTED WHEN HAZARDOUS GROUND MOVEMENT MAY BE EXPECTED. A SITE SPECIFIC TRENCH SAFETY SYSTEM, ACCEPTED BY PLANNING AND DEVELOPMENT SERVICES, SHALL BE UTILIZED BY THIS PRODUCT.
- 2. IN ACCORDANCE WITH THE U. S. OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION REGULATIONS, WHEN PERSONS ARE IN TRENCHES 4 FEET DEEP OR MORE, ADEQUATE MEANS OF EXIT, SUCH AS A LADDER OR STEPS, MUST BE PROVIDED AND LOCATED SO AS TO REQUIRE NO MORE THAN 25 FEET OF LATERAL TRAVEL.
- 3. IF TRENCH SAFETY SYSTEM DETAILS WERE NOT PROVIDED IN THE PLANS BECAUSE TRENCHES WERE ANTICIPATED TO BE LESS THAN 5 FEET IN DEPTH AND DURING CONSTRUCTION IT IS FOUND THAT TRENCHES ARE IN FACT 5 FEET OR MORE IN DEPTH OR TRENCHES LESS THAN 5 FEET IN DEPTH ARE IN AN AREA WHERE HAZARDOUS GROUND MOVEMENT IS EXPECTED, ALL CONSTRUCTION SHALL CEASE, THE TRENCHED AREA SHALL BE BARRICADED AND THE ENGINEER NOTIFIED IMMEDIATELY. CONSTRUCTION SHALL NOT RESUME UNTIL APPROPRIATE TRENCH SAFETY SYSTEM DETAILS, AS DESIGNED BY A PROFESSIONAL ENGINEER, ARE RETAINED AND COPIES SUBMITTED TO THE CITY OF ROUND ROCK.

STREET AND DRAINAGE NOTES

- ALL TESTING SHALL BE DONE BY AN INDEPENDENT LABORATORY AT THE OWNER'S EXPENSE. ANY RETESTING SHALL BE PAID FOR BY THE CONTRACTOR. A CITY INSPECTOR SHALL BE PRESENT DURING ALL TESTS. TESTING SHALL BE COORDINATED WITH THE CITY INSPECTOR AND HE SHALL BE GIVEN A MINIMUM OF 24 HOURS NOTICE PRIOR TO ANY TESTING.
- 2. BACKFILL BEHIND THE CURB SHALL BE COMPACTED TO OBTAIN A MINIMUM OF 95% MAXIMUM DENSITY TO WITHIN 3" OF TOP OF CURB. MATERIAL USED SHALL BE PRIMARILY GRANULAR WITH NO ROCKS LARGER THAN 6" IN THE GREATEST DIMENSION. THE REMAINING 3" SHALL BE CLEAN TOPSOIL FREE FROM ALL CLODS AND SUITABLE FOR SUSTAINING PLANT LIFE.
- 3. DEPTH OF COVER FOR ALL CROSSINGS UNDER PAVEMENT INCLUDING GAS, ELECTRIC, TELEPHONE, CABLE TV, WATER SERVICES, ETC., SHALL BE A MINIMUM OF 30" BELOW SUBGRADE.
- 4. STREET RIGHTS-OF-WAY SHALL BE GRADED AT A SLOPE OF 1/4" PER FOOT TOWARD THE CURB UNLESS OTHERWISE INDICATED. HOWEVER, IN NO CASE SHALL THE WIDTH OF RIGHT-OF-WAY AT 1/4" PER FOOT SLOPE BE LESS THAN 10 FEET UNLESS A SPECIFIC REQUEST FOR AN ALTERNATE GRADING SCHEME IS MADE TO AND ACCEPTED BY THE CITY OF ROUND ROCK PLANNING AND DEVELOPMENT SERVICES DEPARTMENT.
- 5. BARRICADES BUILT TO CITY OF ROUND ROCK STANDARDS SHALL BE CONSTRUCTED ON ALL DEAD-END STREETS AND AS NECESSARY DURING CONSTRUCTION TO MAINTAIN JOB AND PUBLIC SAFETY.
- 6. ALL R.C.P. SHALL BE MINIMUM CLASS III.
- 7. THE SUBGRADE MATERIAL FOR THE STREETS SHOWN HEREIN WAS TESTED BY: ALLIANCE ENGINEERING GROUP, INC. IN A REPORT DATED 12/27/2022, AND THE PAVING SECTIONS DESIGNED IN ACCORDANCE WITH THE CURRENT CITY OF ROUND ROCK DESIGN CRITERIA. THE PAVING SECTIONS ARE TO BE CONSTRUCTED AS FOLLOWS: SEE DETAIL 02/C70

THE GEOTECHNICAL ENGINEER SHALL INSPECT THE SUBGRADE FOR COMPLIANCE WITH THE DESIGN ASSUMPTIONS MADE DURING PREPARATION OF THE SOILS REPORT. ANY ADJUSTMENTS THAT ARE REQUIRED SHALL BE MADE THROUGH REVISION OF THE CONSTRUCTION PLANS.

8. WHERE PI'S ARE OVER 20, SUBGRADES MUST BE STABILIZED UTILIZING A METHOD ACCEPTABLE TO THE CITY ENGINEER. THE GEOTECHNICAL ENGINEER SHALL RECOMMEND AN APPROPRIATE SUBGRADE STABILIZATION IF SULFATES ARE DETERMINED TO BE PRESENT.

CITY OF ROUND ROCK GENERAL CONSTRUCTION NOTES

WATER AND WASTEWATER NOTES:

- PIPE MATERIAL AND ACCESSORIES SHALL BE OF NEW MATERIALS ONLY. WATER MAINS SHALL BE DUCTILE IRON (AWWA C-110, C104, AND ANSI/AWWA C-153/A21.53-84, MIN PRESSURE CLASS 200) OR PVC (AWWA C-900/C905, ASTM F477 AND D3139, MIN PRESSURE CLASS 200) OR HDPE (AWWA C-906, ASTM F714, NSF 61 AND PE 3408 BY ASTM 3350) WITH A MINIMUM 11 DIMENSION RATIO AND (DR) DUCTILE IRON PIPE SIZE (DIPS). SERVICE PIPING SHALL BE COPPER SEAMLESS TYPE K OR POLYETHYLENE (BLACK, 200 PSI, DR 9) AS ACCEPTED BY THE CITY.
- PIPE MATERIAL FOR PRESSURE WASTEWATER MAINS SHALL BE SDR 26 HIGHER PRESSURE RATED (150+PSI) OR DUCTILE IRON (AWWA C-100, MIN. CLASS 200). PIPE MATERIAL FOR GRAVITY WASTEWATER MAINS SHALL BE PVC (ASTM D2241 OR D3034, MAX. DR-26), DUCTILE IRON (AWWA C-100, MIN. CLASS 200).
- 3. UNLESS OTHERWISE DIRECTED BY THE CITY ENGINEER, DEPTH OF COVER FOR ALL LINES OUT OF THE PAVEMENT SHALL BE
- 4. ALL FIRE HYDRANT LEADS SHALL BE DUCTILE IRON PIPE (AWWA C-100, MIN. CLASS 200).
- 5. ALL IRON PIPE AND FITTINGS SHALL BE WRAPPED WITH MINIMUM 8-MIL POLYETHYLENE AND SEALED WITH DUCT TAPE OR EQUAL ACCEPTED BY THE CITY ENGINEER.
- 6. THE CONTRACTOR SHALL CONTACT THE CITY OF ROUND ROCK CIVIL INSPECTOR TO COORDINATE UTILITY TIE-INS AND NOTIFY HIM AT LEAST 48 HOURS PRIOR TO CONNECTING TO EXISTING LINES.
- ALL MANHOLES SHALL BE CONCRETE WITH CAST IRON RING AND COVER. ALL MANHOLES LOCATED OUTSIDE OF THE PAVEMENT SHALL HAVE BOLTED COVERS. TAPPING OF FIBERGLASS MANHOLES SHALL NOT BE ALLOWED.
- THE CONTRACTOR MUST OBTAIN A BULK WATER PERMIT OR PURCHASE AND INSTALL A WATER METER FOR ALL WATER USED 8
- 9. LINE FLUSHING OR ANY ACTIVITY USING A LARGE QUANTITY OF WATER MUST BE SCHEDULED WITH THE CITY OF ROUND ROCK CIVIL INSPECTOR.
- 10. THE CONTRACTOR, AT HIS EXPENSE, SHALL PERFORM STERILIZATION OF ALL POTABLE WATER LINES CONSTRUCTED AND SHALL PROVIDE ALL EQUIPMENT (INCLUDING TEST GAUGES), SUPPLIES (INCLUDING CONCENTRATED CHLORINE DISINFECTING MATERIAL), AND NECESSARY LABOR REQUIRED FOR THE STERILIZATION PROCEDURE. THE STERILIZATION PROCEDURE SHALL BE MONITORED BY CITY OF ROUND ROCK PERSONNEL. WATER SAMPLES WILL BE COLLECTED BY THE CITY OF ROUND ROCK TO VERIFY EACH TREATED LINE HAS ATTAINED AN INITIAL CHLORINE CONCENTRATION OF 50 PPM. WHERE MEANS OF FLUSHING IS NECESSARY, THE CONTRACTOR, AT HIS EXPENSE, SHALL PROVIDE FLUSHING DEVICES AND REMOVE SAID DEVICES PRIOR TO FINAL ACCEPTANCE BY THE CITY OF ROUND ROCK.
- SAMPLING TAPS SHALL BE BROUGHT UP TO 3 FEET ABOVE GRADE AND SHALL BE EASILY ACCESSIBLE FOR CITY PERSONNEL AT THE CONTRACTOR'S REQUEST, AND IN HIS PRESENCE, SAMPLES FOR BACTERIOLOGICAL TESTING WILL BE COLLECTED BY THE CITY OF ROUND ROCK NOT LESS THAN 24 HOURS AFTER THE TREATED LINE HAS BEEN FLUSHED OF THE CONCENTRATED CHLORINE SOLUTION AND CHARGED WITH WATER APPROVED BY THE CITY. THE CONTRACTOR SHALL SUPPLY A CHECK OR MONEY ORDER, PAYABLE TO THE CITY OF ROUND ROCK, TO COVER THE FEE CHARGED FOR TESTING EACH WATER SAMPLE. CITY OF ROUND ROCK FEE AMOUNTS MAY BE OBTAINED BY CALLING THE CITY OF ROUND ROCK CIVIL INSPECTOR.
- 12. THE CONTRACTOR, AT HIS EXPENSE, SHALL PERFORM QUALITY TESTING FOR ALL WASTEWATER PIPE INSTALLED AND PRESSURE PIPE HYDROSTATIC TESTING OF ALL WATER LINES CONSTRUCTED AND SHALL PROVIDE ALL EQUIPMENT (INCLUDING PUMPS AND GAUGES), SUPPLIES AND LABOR NECESSARY TO PERFORM THE TESTS. QUALITY AND PRESSURE TESTING SHALL BE MONITORED BY CITY OF ROUND ROCK PERSONNEL
- 13. THE CONTRACTOR SHALL COORDINATE TESTING WITH THE CITY OF ROUND ROCK INSPECTOR AND PROVIDE NO LESS
- 14. THE CONTRACTOR SHALL NOT OPEN OR CLOSE ANY VALVES UNLESS AUTHORIZED BY THE CITY OF ROUND ROCK.
- 15. ALL VALVE BOXES AND COVERS SHALL BE CAST IRON.
- 16. ALL WATER SERVICE, WASTEWATER SERVICE AND VALVE LOCATIONS SHALL BE APPROPRIATELY MARKED THROUGH CHISELING AND PAINTING AS FOLLOWS:

WATER SERVICE	"W" ON TOP OF CURB
WASTEWATER SERVICE	"S" ON TOP OF CURB
CURB VALVE	"V" ON FACE OF CURB

TOOLS FOR MARKING THE CURB SHALL BE PROVIDED BY THE CONTRACTOR. OTHER APPROPRIATE MEANS OF MARKING SERVICE AND VALVE LOCATIONS SHALL BE PROVIDED IN AREAS WITHOUT CURBS. SUCH MEANS OF MARKING SHALL BE AS SPECIFIED BY THE ENGINEER AND ACCEPTED BY THE CITY OF ROUND ROCK.

- 17. CONTACT THE CITY OF ROUND ROCK PLANNING AND DEVELOPMENT SERVICES DEPARTMENT AT (512) 218-5428 FOR ASSISTANCE IN OBTAINING EXISTING WATER AND WASTEWATER LOCATIONS.
- 18. THE CITY OF ROUND ROCK FIRE DEPARTMENT SHALL BE NOTIFIED 48 HOURS PRIOR TO TESTING OF ANY BUILDING SPRINKLER PIPING IN ORDER THAT THE FIRE DEPARTMENT MAY MONITOR SUCH TESTING.
- 19. SAND, AS DESCRIBED IN SPECIFICATION ITEM 510 PIPE, SHALL NOT BE USED AS BEDDING FOR WATER AND WASTEWATER LINES. ACCEPTABLE BEDDING MATERIALS ARE PIPE BEDDING STONE, PEA GRAVEL AND IN LIEU OF SAND, A NATURALLY OCCURRING OR MANUFACTURED STONE MATERIAL CONFORMING TO ASTM C33 FOR STONE QUALITY AND MEETING THE FOLLOWING GRADATION SPECIFICATION. SIEVE SIZ

IZE PERCENT	RETAINED BY WEIGHT
1/2"	0
3/8"	0-2
#4	40-85
#10	95-100

- 20. THE CONTRACTOR IS HEREBY NOTIFIED THAT CONNECTING TO, SHUTTING DOWN, OR TERMINATING EXISTING UTILITY LINES, MAY HAVE TO OCCUR AT OFF-PEAK HOURS. SUCH HOURS ARE USUALLY OUTSIDE NORMAL WORKING HOURS AND POSSIBLY BETWEEN 12 A.M. AND 6 A.M. ANY WATER SHUTDOWN OR TIE-IN MUST BE SCHEDULED TEN (10) DAYS IN ADVANCE.
- 21. ALL WASTEWATER CONSTRUCTION SHALL BE IN ACCORDANCE WITH THE TEXAS COMMISSION ON ENVIRONMENTAL QUALITY (TCEQ) REGULATIONS, 30 TAC CHAPTER 213 AND 317 OR 217, AS APPLICABLE. WHENEVER TCEQ AND CITY OF ROUND ROCK SPECIFICATIONS CONFLICT, THE MORE STRINGENT SHALL APPLY.

TRAFFIC MARKING NOTES

- ANY METHODS, STREET MARKINGS AND SIGNAGE NECESSARY FOR WARNING MOTORISTS, WARNING PEDESTRIANS OR DIVERTING TRAFFIC DURING CONSTRUCTION SHALL CONFORM TO THE TEXAS MANUAL OF UNIFORM TRAFFIC CONTROL DEVICES FOR STREETS AND HIGHWAYS, LATEST EDITION.
- 2. ALL PAVEMENT MARKINGS, MARKERS, PAINT, TRAFFIC BUTTONS, TRAFFIC CONTROLS AND SIGNS SHALL BE INSTALLED IN ACCORDANCE WITH THE TEXAS DEPARTMENT OF TRANSPORTATION STANDARD SPECIFICATIONS FOR CONSTRUCTION OF HIGHWAYS, STREETS AND BRIDGES AND, THE TEXAS MANUAL OF UNIFORM TRAFFIC CONTROL DEVICES FOR STREETS AND HIGHWAYS, LATEST EDITIONS.

EROSION AND SEDIMENTATION CONTROL NOTES: EROSION CONTROL MEASURES, SITE WORK AND RESTORATION WORK SHALL BE IN ACCORDANCE WITH THE CITY OF ROUND ROCK EROSION AND SEDIMENTATION CONTROL ORDINANCE.

- 2. ALL SLOPES SHALL BE SODDED OR SEEDED WITH APPROVED GRASS, GRASS MIXTURES OR GROUND COVER SUITABLE TO THE AREA AND SEASON IN WHICH THEY ARE APPLIED.
- 3. SILT FENCES, ROCK BERMS, SEDIMENTATION BASINS AND SIMILARLY RECOGNIZED TECHNIQUES AND MATERIALS SHALL BE EMPLOYED DURING CONSTRUCTION TO PREVENT POINT SOURCE SEDIMENTATION LOADING OF DOWNSTREAM FACILITIES. SUCH INSTALLATION SHALL BE REGULARLY INSPECTED BY THE CITY OF ROUND ROCK FOR EFFECTIVENESS. ADDITIONAL MEASURES MAY BE REQUIRED IF, IN THE OPINION OF THE CITY ENGINEER, THEY ARE WARRANTED.
- ALL TEMPORARY EROSION CONTROL MEASURES SHALL NOT BE REMOVED UNTIL FINAL INSPECTION AND APPROVAL OF THE PROJECT BY THE ENGINEER. IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO MAINTAIN ALL TEMPORARY EROSION CONTROL STRUCTURES AND TO REMOVE EACH STRUCTURE AS APPROVED BY THE ENGINEER.
- AND AREAS USED BY THE PUBLIC SHALL BE CLEANED UP IMMEDIATELY.
- 6. ONCE REVEGETATION REQUIREMENTS HAVE BEEN MET, ALL TEMPORARY SEDIMENT CONTROLS (E.G. SILT FENCE, ROCK BERMS, INLET PROTECTION, ETC.) SHALL BE REMOVED FROM THE SITE AND DISPOSED, ANY DISTURBED AREAS SHALL BE CLEANSED OF DIRT AND DEBRIS AND PROPERLY RAKED AND GRADED.

42" MINIMUM AND DEPTH OF COVER FOR ALL LINES UNDER PAVEMENT SHALL BE A MINIMUM OF 30" BELOW SUBGRADE.

DURING CONSTRUCTION. A COPY OF THIS PERMIT MUST BE CARRIED AT ALL TIMES BY ALL WHO USE WATER.

THAN 24 HOURS NOTICE PRIOR TO PERFORMING STERILIZATION, QUALITY TESTING OR PRESSURE TESTING.

5. ALL MUD, DIRT, ROCKS, DEBRIS, ETC., SPILLED, TRACKED OR OTHERWISE DEPOSITED ON EXISTING PAVED STREETS, DRIVES

TREE PROTECTION NOTES:

- ALL TREES NOT LOCATED WITHIN THE LIMITS OF CONSTRUCTION AND OUTSIDE OF DISTURBED AREAS SHALL BE PRESERVED. THE CONTRACTOR IS RESPONSIBLE FOR PROTECTING ALL TREES TO BE PRESERVED FROM HIS ACTIVITIES.
- ALL TREES SHOWN TO BE RETAINED WITHIN THE LIMITS OF CONSTRUCTION ON THE PLANS, SHALL BE PROTECTED DURING CONSTRUCTION WITH FENCING. SEE: TREE PROTECTION TREE WELLS (EC-06), TREE PROTECTION TREE LOCATION (EC-07) AND TREE PROTECTION FENCE-CHAIN LINK (EC-08).
- TREE PROTECTION FENCES SHALL BE ERECTED ACCORDING TO CITY STANDARDS FOR TREE PROTECTION, INCLUDING TYPES OF FENCING AND SIGNAGE
- TREE PROTECTION FENCES SHALL BE INSTALLED PRIOR TO THE COMMENCEMENT OF ANY SITE PREPARATION WORK (CLEARING, GRUBBING, OR GRADING) AND SHALL BE MAINTAINED THROUGHOUT ALL PHASES OF THE CONSTRUCTION PROJECT.
- 5. EROSION AND SEDIMENTATION CONTROL BARRIERS SHALL BE INSTALLED OR MAINTAINED IN A MANNER WHICH DOES NOT RESULT IN SOIL BUILD-UP WITHIN TREE DRIPLINES.
- FENCES SHALL COMPLETELY SURROUND THE TREE OR CLUSTERS OF TREES, LOCATED AT THE OUTERMOST LIMITS OF THE TREE BRANCHES (DRIPLINE) OR CRITICAL ROOT ZONE (CRZ), WHICHEVER IS GREATER; AND SHALL BE MAINTAINED THROUGHOUT THE CONSTRUCTION PROJECT IN ORDER TO PREVENT THE FOLLOWING:
- 6.1. SOIL COMPACTION IN CRZ AREA RESULTING FROM VEHICULAR TRAFFIC OR STORAGE OF EQUIPMENT OR MATERIAL. CRZ DISTURBANCES DUE TO GRADE CHANGES OR TRENCHING NOT REVIEWED AND UTHORIZED BY THE FORESTRY MANAGER. 6.2. 6.3. WOUNDS TO EXPOSED ROOTS, TRUNK, OR LIMBS BY MECHANICAL EQUIPMENT OTHER ACTIVITIES DETRIMENTAL TO TREES SUCH AS CHEMICAL STORAGE, CONCRETE TRUCK CLEANING, AND FIRES. 6.4.
- EXCEPTIONS TO INSTALLING TREE FENCES AT THE TREE DRIPLINES OR CRZ, WHICHEVER IS GREATER, MAY BE PERMITTED IN THE FOLLOWING CASES:
- 7.1. WHERE THERE IS TO BE AN APPROVED GRADE CHANGE, IMPERMEABLE PAVING SURFACE, OR TREE WELL 7.2. HERE PERMEABLE PAVING IS TO BE INSTALLED, ERECT THE FENCE AT THE OUTER LIMITS OF THE PERMEABLE PAVING AREA.
- 7.3. HERE TREES ARE CLOSE TO PROPOSED BUILDINGS, ERECT THE FENCE NO CLOSER THAN 6 FEET TO THE BUILDING. 7.4. HERE THERE ARE SEVERE SPACE CONSTRAINTS DUE TO TRACT SIZE, OR OTHER SPECIAL REQUIREMENTS, CONTACT THE FORESTRY MANAGER TO DISCUSS ALTERNATIVES.
- HERE ANY OF THE ABOVE EXCEPTIONS RESULT IN A FENCE THAT IS CLOSER THAN 5 FEET TO A TREE TRUNK, THE TRUNK SHALL BE PROTECTED BY STRAPPED-ON PLANKING TO A HEIGHT OF 8 FEET (OR TO THE LIMITS OF LOWER BRANCHING) IN ADDITION TO THE REDUCED FENCING PROVIDED.
- WHERE ANY OF THE ABOVE EXCEPTIONS RESULT IN AREAS OF UNPROTECTED ROOT ZONES UNDER THE DRIPLINE OR CRZ, WHICHEVER IS GREATER, THOSE AREAS SHOULD BE COVERED WITH 4 INCHES OF ORGANIC MULCH TO MINIMIZE SOIL COMPACTION.
- 10. ALL GRADING WITHIN CRZ AREAS SHALL BE DONE BY HAND OR WITH SMALL EQUIPMENT TO MINIMIZE ROOT DAMAGE. PRIOR TO GRADING, RELOCATE PROTECTIVE FENCING TO 2 FEET BEHIND THE GRADE CHANGE AREA.
- ANY ROOTS EXPOSED BY CONSTRUCTION ACTIVITY SHALL BE PRUNED FLUSH WITH THE SOIL AND BACKFILLED WITH GOOD QUALITY TOP SOIL WITHIN TWO DAYS. IF EXPOSED ROOT AREAS CANNOT BE BACKFILLED WITHIN 2 DAYS, AN ORGANIC MATERIAL WHICH REDUCES SOIL TEMPERATURE AND MINIMIZES WATER LOSS DUE TO EVAPORATION SHALL BE PLACED TO COVER THE ROOTS UNTIL BACKFILL CAN OCCUR.
- 12. PRIOR TO EXCAVATION OR GRADE CUTTING WITHIN TREE DRIPLINES, A CLEAN CUT SHALL BE MADE WITH A ROCK SAW OR SIMILAR EQUIPMENT, IN A LOCATION AND TO A DEPTH APPROVED BY THE FORESTRY MANAGER, TO MINIMIZE DAMAGE TO REMAINING roots.
- 13. TREES MOST HEAVILY IMPACTED BY CONSTRUCTION ACTIVITIES WILL BE WATERED DEEPLY ONCE A WEEK DURING PERIODS OF HOT, DRY WEATHER. TREE CROWNS ARE TO BE SPRAYED WITH WATER PERIODICALLY TO REDUCE DUST ACCUMULATION ON LEAVES.
- 14. WHEN INSTALLING CONCRETE ADJACENT TO THE ROOT ZONE OF A TREE, A PLASTIC VAPOR BARRIER SHALL BE PLACED BEHIND THE CONCRETE TO PROHIBIT LEACHING OF LIME INTO THE CRZ.
- 15. ANY TRENCHING REQUIRED FOR THE INSTALLATION OF LANDSCAPE IRRIGATION SHALL BE PLACED AS FAR FROM EXISTING TREE TRUNKS AS POSSIBLE
- 16. NO LANDSCAPE TOPSOIL DRESSING GREATER THAN FOUR (4) INCHES SHALL BE PERMITTED WITHIN THE DRIPLINE OR CRZ OF TREES, WHICHEVER IS GREATER. NO TOPSOIL IS PERMITTED ON ROOT FLARES OF ANY TREE.
- 17. PRUNING TO PROVIDE CLEARANCE FOR STRUCTURES, VEHICULAR TRAFFIC, AND CONSTRUCTION EQUIPMENT SHALL TAKE PLACE BEFORE CONSTRUCTION BEGINS. ALL PRUNING MUST BE DONE ACCORDING TO CITY STANDARDS AND AS OUTLINED IN LITERATURE PROVIDED BY THE INTERNATIONAL SOCIETY OF ARBORICULTURE (ISA PRUNING TECHNIQUES).
- 18. ALL OAK TREE CUTS, INTENTIONAL OR UNINTENTIONAL, SHALL BE SEALED WITH AN APPROVED PRUNING SEALER IMMEDIATELY (WITHIN 10 MINUTES). TREE PAINT MUST BE KEPT ON SITE AT ALL TIMES.
- 12. 19. THE FORESTRY MANAGER HAS THE AUTHORITY TO REQUIRE ADDITIONAL TREE PROTECTION BEFORE OR DURING CONSTRUCTION. 20. TREES APPROVED FOR REMOVAL SHALL BE REMOVED IN A MANNER WHICH DOES NOT IMPACT TREES TO BE PRESERVED. REFER TO THE CITY OF ROUND ROUND ROCK TREE TECHNICAL MANUAL FOR APPROPRIATE REMOVAL METHODS.
- 21. PRIOR TO CONSTRUCTION, ALL LOWER TREE LIMBS OVER ROADWAYS MUST BE PRUNED TO A HEIGHT OF 14 FEET USING THE TECHNIQUES DESCRIBED IN THE CITY OF ROUND ROCK TREE TECHNICAL MANUAL.
- 22. DEVIATIONS FROM THE ABOVE REQUIREMENTS AND NEGLIGENT DAMAGE TO TREES MAY BE CONSIDERED AS ORDINANCE VIOLATIONS.

TCEQ WPAP NOTES

- (REV. 7/1 TEXAS COMMISSION ON EN WATER POLLUTION GENERAL CONSTRU
- A WRITTEN NOTICE OF CONSTRUCTION MU OFFICE AT LEAST 48 HOURS PRIOR TO THE S NOTICE MUST INCLUDE:
- THE NAME OF THE APPROVED PROJEC THE ACTIVITY START DATE; AND THE CONTACT INFORMATION OF THE
- ALL CONTRACTORS CONDUCTING REGULA MUST BE PROVIDED WITH COMPLETE COPIES ABATEMENT PLAN (WPAP) AND THE TCEQ LE OF ITS APPROVAL. DURING THE COURSE OF CONTRACTORS ARE REQUIRED TO KEEP ON-APPROVAL LETTER.
- IF ANY SENSITIVE FEATURE(S) (CAVES, SOLUT DURING CONSTRUCTION, ALL REGULATED SUSPENDED IMMEDIATELY. THE APPROPRIAT IMMEDIATELY NOTIFIED OF ANY SENSITIVE F CONSTRUCTION. CONSTRUCTION ACTIVITIE REVIEWED AND APPROVED THE APPROPRIATE ANY SENSITIVE FEATURE AND THE EDWARDS TO WATER QUALITY.
- NO TEMPORARY OR PERMANENT HAZARDOL INSTALLED WITHIN 150 FEET OF A WATER SU SENSITIVE FEATURE.
- PRIOR TO BEGINNING ANY CONSTRUCTION SEDIMENTATION (E&S) CONTROL MEASURES MAINTAINED IN ACCORDANCE WITH THE AF SPECIFICATIONS. IF INSPECTIONS INDICATE OR INCORRECTLY, THE APPLICANT MUST RE SITUATIONS. THESE CONTROLS MUST REMA BEEN PERMANENTLY STABILIZED.
- ANY SEDIMENT THAT ESCAPES THE CONSTRU SURFACE STREAMS, SENSITIVE FEATURES, ETC.

SEDIMENT MUST BE REMOVED FROM THE SEDIMENT TRAPS OR SEDIMENTATION BASINS NOT LATER THAN TCEQ-0592 WHEN IT OCCUPIES 50% OF THE BASIN'S DESIGN CAPACITY.

LITTER, CONSTRUCTION DEBRIS, AND CONSTRUCTION CHEMICALS EXPOSED TO STORMWATER SHALL BE PREVENTED FROM BEING DISCHARGED OFFSITE.

ALL SPOILS (EXCAVATED MATERIAL) GENERATED FROM THE PROJECT SITE MUST BE STORED ON-SITE WITH PROPER E&S CONTROLS. FOR STORAGE OR DISPOSAL OF SPOILS AT ANOTHER SITE ON THE EDWARDS AQUIFER RECHARGE ZONE, THE OWNER OF THE SITE MUST RECEIVE APPROVAL OF A WATER POLLUTION ABATEMENT PLAN FOR THE PLACEMENT OF FILL MATERIAL OR MASS GRADING PRIOR TO THE PLACEMENT OF SPOILS AT THE OTHER SITE.

IF PORTIONS OF THE SITE WILL HAVE A TEMPORARY OR PERMANENT CEASE IN CONSTRUCTION ACTIVITY LASTING LONGER THAN 14 DAYS, SOIL STABILIZATION IN THOSE AREAS SHALL BE INITIATED AS SOON AS POSSIBLE PRIOR TO THE 14TH DAY OF INACTIVITY. IF ACTIVITY WILL RESUME PRIOR TO THE 21ST DAY, STABILIZATION MEASURES ARE NOT REQUIRED. IF DROUGHT CONDITIONS OR INCLEMENT WEATHER PREVENT ACTION BY THE 14TH DAY, STABILIZATION MEASURES SHALL BE INITIATED AS SOON AS POSSIBLE

THE FOLLOWING RECORDS SHALL BE MAINTAINED AND MADE AVAILABLE TO THE TCEQ UPON REQUEST:

- THE DATES WHEN MAJOR GRADING ACTIVITIES OCCUR;
- ON A PORTION OF THE SITE; AND THE DATES WHEN STABILIZATION MEASURES ARE INITIATED.

THE HOLDER OF ANY APPROVED EDWARD AQUIFER PROTECTION PLAN MUST NOTIFY THE APPROPRIATE REGIONAL OFFICE IN WRITING AND OBTAIN APPROVAL FROM THE EXECUTIVE DIRECTOR PRIOR TO INITIATING ANY OF THE FOLLOWING:

- SEWAGE TREATMENT PLANTS, AND DIVERSIONARY STRUCTURES; B. ANY CHANGE IN THE NATURE OR CHARACTER OF THE REGULATED ACTIVITY FROM THAT
- ORIGINAL WATER POLLUTION ABATEMENT PLAN.

AUSTIN REGIONAL OFFICE SAN ANTONIO REGIONAL OFFICE 2100 PARK 35 CIRCLE, BLDG. A 14250 JUDSON ROAD SAN ANTONIO, TEXAS 78233-4480 AUSTIN, TEXAS 78753 PHONE (512) 339-2929 PHONE (210) 490-3096 FAX (512) 339-3795 FAX (210) 545-4329

- SEQUENCE OF CONSTRUCTION:
- A. INSTALL EROSION CONTROLS AS INDICATED ON APPROVED SITE PLAN.
- B. INSTALL TREE PROTECTION AS NOTED ON APPROVED SITE PLAN.
- C. SCHEDULE PRE CONSTRUCTION MEETING WITH THE CITY OF ROUND ROCK INSPECTION DEPT., CONTRACTOR, UTILITY CONTRACTOR, AND ENGINEER. 218-6607.
- D. EVALUATION OF TEMPORARY EROSION CONTROL INSTALLATION. REVIEW CONSTRUCTION SCHEDULE AND THE EROSION CONTROL PLAN.
- INSTALL TEMPORARY SEDIMENTATION PONDS AND ROUGH GRADE SITE. INSPECT AND MAINTAIN ALL CONTROLS AS PER GENERAL NOTES. G. CONSTRUCT SITE UTILITIES.
- H. MID-CONSTRUCTION ON-SITE MEETING TO COORDINATE CHANGES IN CONSTRUCTION SCHEDULE AND EVALUATE EFFECTIVENESS OF EROSION CONTROL PLAN (CITY INSPECTOR, PROJECT ENGINEER, GENERAL CONTRACTOR).
- I. CONSTRUCT PAVING, PARKING AND BUILDINGS.
- J. COMPLETE CONSTRUCTION AND INSTALL LANDSCAPING.
- K. PROVIDE AS-BUILTS TO ENGINEER.
- REVEGETATE DISTURBED AREAS OR COMPLETE A DEVELOPERS CONTRACT FOR THE RE-VEGETATION ALONG WITH THE ENGINEERS CONCURRENCE LETTER.
- M. PROJECT ENGINEER INSPECTS JOB AND WRITES CONCURRENCE LETTER TO THE CITY, FINAL INSPECTION IS SCHEDULED UPON RECEIPT OF THE LETTER
- N. RECEIVE CITY CLEARANCE FOR OCCUPANCY.
- O. REMOVE TEMPORARY EROSION/SEDIMENTATION CONTROLS.

	VA SIZE TOTAL 6 1	ALVES BRAND AMERICAN DARLING WASTEWATER	CURB / TOTAL		GUTTER LF WASTEWA ⁻	TER MAN	INL SIZE 5' 10' 15'	ETS QTY 0 0 0 SIDEV	VAL	TOTAL 1	FIRE F	AM AM RM SEV	NTS BRAND ERICAN DARLING VER MANHOLES		encer - Piel chitecture - L STONE
PIPE SIZE	TYPE	LENGTH (LF)	VOL (GAL)	Γ	SIZE	Q	TY	TOTAL		LF	S	ZE	QTY		
					4'		0	4'				4'	0		\mathcal{N} \mathcal{I} Ξ
					<u> 5' </u>		0	5'				5' 6' 7'	0 0 0		
		WATER													Comuniable
FIFE SIZE	TYPE	LENGTH (LF)	VOL (GAL)											╞	Copyright
0'-2	BLACK POLY	15.4000													SHEET
0'-6	" DI	16.4000													600
5-0	C900	97.1600													CUU
															11 of 32 SDP2205-0006

		V
PIPE SIZE	TYPE	LENG
0'-2"	BLACK POLY	
0'-6"	DI	
0'-8"	C900	

- - E. BEGIN SITE CLEARING.

5/15) IVIRONMENTAL QUALITY ABATEMENT PLAN UCTION NOTES	
JST BE SUBMITTED TO THE TCEQ REGIONAL TART OF ANY REGULATED ACTIVITIES. THIS	(S)
Т;	[0]
PRIME CONTRACTOR.	0110 H+H 0110
TED ACTIVITIES ASSOCIATED WITH THIS PROJECT S OF THE APPROVED WATER POLLUTION TTER INDICATING THE SPECIFIC CONDITIONS THESE REGULATED ACTIVITIES, THE -SITE COPIES OF THE APPROVED PLAN AND	(<u>(</u>)) ° <i>ex. co</i> © G
ION CAVITY, SINK HOLE, ETC.) IS DISCOVERED ACTIVITIES NEAR THE SENSITIVE FEATURE MUST BE E TCEQ REGIONAL OFFICE MUST BE EATURES ENCOUNTERED DURING ES MAY NOT BE RESUMED UNTIL THE TCEQ HAS E PROTECTIVE MEASURES IN ORDER TO PROTECT AQUIFER FROM POTENTIALLY ADVERSE IMPACTS	
JS SUBSTANCE STORAGE TANK SHALL BE IPPLY SOURCE, DISTRIBUTION SYSTEM, WELL, OR	∞ _{EX. WV} ⊗ _{EX. ICV}
ACTIVITY, ALL TEMPORARY EROSION AND MUST BE PROPERLY INSTALLED AND PROVED PLANS AND MANUFACTURERS A CONTROL HAS BEEN USED INAPPROPRIATELY, PLACE OR MODIFY THE CONTROL FOR SITE IN IN PLACE UNTIL THE DISTURBED AREAS HAVE	
UCTION SITE MUST BE COLLECTED AND	— — — 0

PROPERLY DISPOSED OF BEFORE THE NEXT RAIN EVENT TO ENSURE IT IS NOT WASHED INTO

THE DATES WHEN CONSTRUCTION ACTIVITIES TEMPORARILY OR PERMANENTLY CEASE

A. ANY PHYSICAL OR OPERATIONAL MODIFICATION OF ANY WATER POLLUTION ABATEMENT STRUCTURE(S), INCLUDING BUT NOT LIMITED TO PONDS, DAMS, BERMS,

WHICH WAS ORIGINALLY APPROVED OR A CHANGE WHICH WOULD SIGNIFICANTLY IMPACT THE ABILITY OF THE PLAN TO PREVENT POLLUTION OF THE EDWARDS AQUIFER; C. ANY DEVELOPMENT OF LAND PREVIOUSLY IDENTIFIED AS UNDEVELOPED IN THE

LEGEND IRON ROD FOUND/SET 0 CONCRETE MONUMENT FOUND/SET NAIL FOUND/SET Δ PIPE FOUND STORMWATER MANHOLE (DRAWN TO SCALE) (S)

<u>í</u>

JUNCTION BOX (DRAWN TO SCALE) GRATE INLET (DRAWN TO SCALE)

WASTEWATER MANHOLE (DRAWN TO SCALE) WASTEWATER CLEANOUT GAS TEST STATION GAS METER ELECTRIC METER LIGHT POLE SIGNAL LIGHT POLE UTILITY POLE TELEPHONE MANHOLE FIRE HYDRANT GATE VALVE IRRIGATION CONTROL VALVE WATER METER





SUMMARY TABLES



May 15,2023-1:29pm Z:\HEA\HEA Projects\Projects 21-000\21-025 Round Rock Christian Acadamy Addition\CAD Files\Civil\SD\21-025 C10.dv







13 of 32 SDP2205-0006

TEMPORARY ESC LEGEND

. . . CONCRETE WASHOUT **— TP** — TREE PROTECTION —— MS——— MULCH SOCK

NOTES:

- 1. CONTRACTOR TO ENSURE AT ALL TIMES, CONSTRUCTION TRAFFIC SHALL ENTER AND EXIT THROUGH A STABILIZED CONSTRUCTION ENTRANCE.
- 2. ALL DIRT, MUD, ROCKS, DEBRIS, ETC. SPILLED, TRACKED, OR OTHERWISE DEPOSITED ON ANY EXISTING PAVED STREETS, DRIVES AND AREAS USED BY THE PUBLIC SHALL BE CLEANED UP IMMEDIATELY.
- 3. CONTRACTOR TO IMPLEMENT TRAFFIC CONTROL MEASURES AS REQUIRED WHEN NECESSARY.
- 4. EROSION CONTROLS SHALL BE IN PLACE PRIOR TO ANY DEMOLITION.
- 5. THE CONTRACTOR SHALL CONSTRUCT AN ALL WEATHER SURFACE ACCESS DRIVE PRIOR TO GOING VERTICAL WITH THE BUILDING STRUCTURE. DIRT WORK AND FOUNDATION WORK MAY BE DONE PRIOR TO THE CONSTRUCTION OF THIS REQUIREMENT. ALL WEATHER SURFACE IS DEFINED AS ASPHALT, CONCRETE OR CHIP SEAL OVER AN ENGINEERED COMPACTED BASE.
- 6. ALL DISTURBED AREAS SHALL BE REVEGETATED AND ESTABLISHED PER CITY OF ROUND ROCK AND TCEQ REQUIREMENTS PRIOR TO ISSUANCE OF CERTIFICATE OF OCCUPANCY.
- DURING CONSTRUCTION, ADDITIONAL EROSION CONTROL MEASURES MAY BE REQUIRED BY THE SITE INSPECTOR.



	ALL RESPONSIBILITY FOR THE ADEQUACY OF THESE PLANS REMAINS WITH THE ENCINEER WHO PREPARED THEM. IN REVIEWING THESE PLANS, THE CITY MUST RELY UPON THE ADEQUANCE OF THE WORK OF THE DESIGN ENGINEER.	DATE: 05/15/2023 RFV:			DRW. SPai CHK. SPai
EGENDE RON ROD FOUNDAST CONCRETE MONUMENT FOUNDAST NAL FOUNDAST REF FOUND STORMATTER MANHOLE (DRAWN TO SCALE) GATE INLET (DRAWN TO SCALE) GATE INLET MASTEWATER (LANOUT GATE FAUNE IELETIKO (METER LIGHT POLE BISTING CONTOURS ENSTING CONT	<text><text><text><text><text><text><text><text><text></text></text></text></text></text></text></text></text></text>	SITE DEVELOPMENT IMPROVEMENTS	ROUND ROCK CHRISTIAN ACADEMY	800 WESTWOOD DRIVE	ROUND ROCK, TEXAS 78681
Auch Pole Signal Light Pole UTILITY Pole REGATION CONTROL VALVE WATER METER EXISTING CONTOURS EXISTING CONTOURS EXISTING COALUNE EXISTING COALUNE EXISTING COALUNE EXISTING WOOD FENCE SETBACK LINE EXISTING WOOD FENCE SETBACK LINE EXISTING WOOD FENCE EXISTING WOOD FENCE EXISTING GAVEREAD ELECTRIC LINE EXISTING OVERHEAD ELECTRIC LINE EXISTING OVERHEAD TELEPHONE LINE EXISTING OVERHEAD TELEPHONE LINE EXISTING OVERHEAD TELEPHONE LINE EXISTING GAS LINE (SIZE VARES) EXISTING GASE INE (SIZE VARES) EXISTING GASE LINE (SIZE VARES) EXISTING COULDER EXISTING COULDE	EGEND IRON ROD FOUND/SET CONCRETE MONUMENT FOUND/SET NAIL FOUND/SET PIPE FOUND STORMWATER MANHOLE (DRAWN TO SCALE) JUNCTION BOX (DRAWN TO SCALE) GRATE INLET (DRAWN TO SCALE) WASTEWATER MANHOLE (DRAWN TO SCALE) WASTEWATER MANHOLE (DRAWN TO SCALE) WASTEWATER CLEANOUT GAS TEST STATION GAS METER ELECTRIC METER				
PAVEMENT TO BE DEMOLISHED CURB & GUTTER TO BE DEMOLISHED PLACE PRIOR TO DEMOLITION. BUILDING FOOTPRINT SHALL BE	SIGNAL LIGHT POLE UTILITY POLE TELEPHONE MANHOLE FIRE HYDRANT GATE VALVE IRRIGATION CONTROL VALVE WATER METER EXISTING CONTOURS EXISTING CHAIN LINK FENCE EXISTING WIRE FENCE EXISTING WOOD FENCE SETBACK LINE EASEMENT LINE EXISTING OVERHEAD ELECTRIC LINE EXISTING OVERHEAD ELECTRIC LINE EXISTING OVERHEAD ELECTRIC LINE EXISTING OVERHEAD TELEPHONE LINE EXISTING OVERHEAD TELEPHONE LINE EXISTING WATER LINE (SIZE VARIES) EXISTING WASTEWATER LINE (SIZE VARIES) EXISTING FIBER OPTIC LINE EXISTING FIBER OPTIC LINE	ncer - Pierce	nitecture + Interiors, Inc.	rone Round Rock, Texas 78664	18-0677 152 Email: spai@sp-ai.com Web Site: www.sp-ai.com
	PAVEMENT TO BE DEMOLISHED CURB & GUTTER TO BE DEMOLISHED PLACE PRIOR TO DEMOLITION. BUILDING FOOTPRINT SHALL BE	Sper	Arch	110 N. ST	Phone: (512) 38. Fax: (512) 388-07

15 of 32

SDP2205-0006

	0 20 $40SCALE: 1" = 20'$	ALL RESPONSIBILITY FOR THE ADEQUACY OF THESE PLANS REMAINS WITH THE ENGINEER WHO PREPARED THEM. IN REVIEWING THESE PLANS, THE CITY MUST RELY UPON THE ADEQUANCE OF THE WORK OF THE DESIGN ENGINEER.	DATE: 05/15/2023 REV: A - ADD BUILDING EXTENSION, REMOVE FIRELANE HAMMERHEAD	DRW. SPai CHK. SPai
LOT 1 RECKA VAT OF LOT 1. BLOCK A ROUND ROCK RETREMENT RESIDENCE UNST. # 2005064681 O.R.W.C.T. LODGING (RETIREMENT HOME FACILITY)	C IRON ROD FOUND/SET C CONCRETE MONUMENT FOUND/SET A NAIL FOUND/SET IPPE FOUND STORMWATER MANHOLE (DRAWN TO SCALE) IDI GRATE INLET (DRAWN TO SCALE) IDI VASTEWATER MANHOLE (DRAWN TO SCALE) IDI VASTEWATER MANHOLE (DRAWN TO SCALE) IDI VASTEWATER MANHOLE (DRAWN TO SCALE) IDI VASTEWATER CLEANOUT GATE VALVE VASTEWATER IDI ONTOOLS VASTEWATER IDI ONTROL VALVE VASTEWATER	<text><text><text></text></text></text>	SITE DEVELOPMENT IMPROVEMENTS ROUND ROCK CHRISTIAN ACADEMY 800 WESTWOOD DRIVE	ROUND ROCK, TEXAS 78681
-	7 PARKING COUNT PARCEL LINES HANDICAP ACCESS LINES CONCRETE PAVING ASPHALT PAVING CONCRETE SIDEWALK			
TWALL CZO SBSB	NOTES: 1. FIRELANE STRIPING TO BE 6" WIDE RI PARKING" IN 4" TALL WHITE LETTERS. MORE THAN 30 FEET APART. STRIPIN WHEN PRESENT AND PAINTED FLAT (NOT. 2. ALL DIMENSIONS ARE TO THE FACE (WHERE APPLICABLE), UNLESS OTHEF 3. FIRELANES SHALL BE SURFACED SO A CAPABILITIES BEFORE ANY COMBUS' SITE. 4. ALL WEATHER SURFACE ROADS OF C SUPPORT 80,000 LBS. AND SITE HYD COMBUSTIBLE MATERIAL ON SITE. 20	ED PAINT WITH "FIRE LANE-NO WORDING MAY NOT BE SPACED G TO BE PAINTED ON FACE OF CURB ON PARKING SURFACE WHEN IT IS OF CURB, OR CENTER OF STRIPING RWISE NOTED. AS TO PROVIDE ALL-WEATHER DRIVING TIBLE MATERIALS ARE ALLOWED ON CONCRETE OR ASPHALT ABLE TO RANTS IN-SERVICE BEFORE ANY 015 IFC D102.	Provide the set of the	Phone: (512) 388-0677 Fax: (512) 388-0752 Email: spai@sp-ai.com Web Site: www.sp-ai.com

DATE: 05/15/2023 REV:			DRW. SPai CHK. SPai
SITE DEVELOPMENT IMPROVEMENTS	ROUND ROCK CHRISTIAN ACADEMY	800 WESTWOOD DRIVE	ROUND ROCK, TEXAS 78681
Spencer - Pierce	Architecture + Interiors, Inc.	110 N. STONE Round Rock, Texas 78664	Phone: (512) 388-0677 Fax: (512) 388-0752 Email: spai@sp-ai.com Web Site: www.sp-ai.com
	SITE DEVELOPMENT IMPROVEMENTS Rev. 05/15/2023	SITE DEVELOPMENT IMPROVEMENTS ME: 04/15/2023 Architecture + Interiors, Inc. ROUND ROCK CHRISTIAN ACADEMY	Site DEVELOPMENT IMPROVEMENTS MATE: 05/15/2023 Stencer - Pierce Not November 1 Architecture + Interiors, Inc. ROUND ROCK CHRISTIAN ACADEMY 110 N. STONE Revi Revi 800 WESTWOOD DRIVE

SDP2205-0006

LEGEND

•	0	IRON ROD FOUND/SET
		CONCRETE MONUMENT FOUND/SET
	Δ	NAIL FOUND/SET
۲		PIPE FOUND
(Ŝ)	S	STORMWATER MANHOLE (DRAWN TO SCALE
C		JUNCTION BOX (DRAWN TO SCALE)
田田田田		GRATE INLET (DRAWN TO SCALE)
$(\mathbf{\hat{o}})$	٢	WASTEWATER MANHOLE (DRAWN TO SCALE
° _{EX.} CO	o	WASTEWATER CLEANOUT
۵		GAS TEST STATION
G		GAS METER
E		ELECTRIC METER
Ø	ЭШ	LIGHT POLE
Ø		SIGNAL LIGHT POLE
Ø		UTILITY POLE
0		TELEPHONE MANHOLE
− ¶ <i>EX. FH</i>	-	FIRE HYDRANT
$\otimes_{_{\it EX.WV}}$	8	GATE VALVE
⊗ _{EX. ICV}	_	IRRIGATION CONTROL VALVE
<u> </u>		WATER METER
99		
		- EXISTING CHAIN LINK FENCE
- — —×-		- EXISTING WIRE FENCE
		- EXISTING WOOD FENCE
SB-		- SETBACK LINE
	1	
	#	
\		EXISTING UNDERGROUND TELEPHONE LINE
		- EXISTING WATER LINE (SIZE VARIES)
— — FM		- EXISTING FORCE MAIN (SIZE VARIES)
1 141		- EXISTING FIBER OPTIC LINE
		- EXISTING GAS LINE (SIZE VARIES)
Tu		BENCHMARK LOCATION
		existing tree to remain (size varies)
$\left(\begin{array}{c} \cdot \end{array} \right)$	\sum	EXISTING TREE TO BE REMOVED (SIZE VARIES)
AN V	n de la companya de l	MONARCH/HERITAGE TREE (SIZE VARIES)
(7))	PARKING COUNT
		- PARCEL LINES
		 HANDICAP ACCESS LINES
		CONCRETE PAVING
		ASPHALT PAVING
		CONCRETE SIDEWALK

E ADEQUACY OF THESE PLANS REMAINS PREPARED THEM. IN REVIEWING THESE UPON THE ADEQUANCE OF THE WORK DESIGN ENGINEER.	DATE: 05/15/2023 RFV·			DRW. SPai CHK. SPai	f spaces and elements of the
ACCOUNT ACTION A	SITE DEVELOPMENT IMPROVEMENTS	ROUND ROCK CHRISTIAN ACADEMY	800 WESTWOOD DRIVE	ROUND ROCK, TEXAS 78681	known as Architectural Vorks Copyright protection Act of 1990. The Protection includes but is not limited to the overall form as well as the arrangement and composition a
G ESTED. S. DR-26. BLE, AND					as amended December 1990 and k
I' OR ABOVE DVAL OF MATION HE YY. N LINE OUTSIDE 150 PSI; ROSSING. N LINE OUTSIDE ON THE OR GER, AND OSSING.	r - Pierce	cture + Interiors, Inc.	Round Rock, Texas 78664	Email: spai@sp-ai.com Web Site: www.sp-ai.com	irchitectural Work' under section JUZ of the copyright act, 1/ U.S.D
OCKED.	Spence	Architec	110 N. STONE	Phone: (512) 388-0677 Fax: (512) 388-0752	to copyright protection as an A
		opyright SHE			: Ihese plans are copyrighted and are subject i
		26 o SDP220	•f 32 05-000	06	Jpyright Notice






ALL RESPONSIBILITY FOR THE ADEQUACY OF THESE PLANS REMAINS WITH THE ENGINEER WHO PREPARED THEM. IN REVIEWING THESE PLANS, THE CITY MUST RELY UPON THE ADEQUANCE OF THE WORK OF THE DESIGN ENGINEER.	TE: 05/15/2023 v·	:		W. SPai CHK. SPai
<image/> <text><text><text><text><text><text><text></text></text></text></text></text></text></text>	SITE DEVELOPMENT IMPROVEMENTS	ROUND ROCK CHRISTIAN ACADEMY	800 WESTWOOD DRIVE	ROUND ROCK, TEXAS 78681
	- Pierce	Ure + Interiors, Inc.	Round Rock, Texas 78664	Email: spai@sp-ai.com Web Site: www.sp-ai.com
	Spencer	/ Architect	110 N. STONE	Phone: (512) 388-0677 Fax: (512) 388-0752
		opyright	ET	
		27 o SDP220	f 32	06







05/15/2023			iPai CHK. SP
DATE: REV:			DRW. S
SITE DEVELOPMENT IMPROVEMENTS	ROUND ROCK CHRISTIAN ACADEMY	800 WESTWOOD DRIVE	ROUND ROCK, TEXAS 78681
- Pierce	Ture + Interiors, Inc.	Round Rock, Texas 78664	Email: spai@sp-ai.com Web Site: www.sp-ai.com
Spencer	Architect	110 N. STONE	Phone: (512) 388-0677 Fax: (512) 388-0752
Copyright SHEET			
	SITE DEVELOPMENT IMPROVEMENTS BATE: 05/15/2023	Round Reviews Revi	SITE DEVELOPMENT IMPROVEMENTS Spencer - Pierce Architecture + Interiors, Inc. IION.STONE Round Rock, Texas 78664 Round Rock, T

<u>ہ</u> ھ