

Ranger Excavating, LP

Water Pollution Abatement Plan (WPAP)

Rattlesnake Ranch Quarry

8880 Old 195, Florence, Texas 76527

Williamson County

Submitted to: TCEQ Region 11, Austin

Prepared By:




Boerne, Texas

830-249-8284

Date: December 2023

Project No. 11260-005

-BGB-



Signature: Nicolas E. Mercado

Nicolas E. Mercado, PE – License No. 144228

TX PE Firm No. 4524

Date: 12/19/2023

Water Pollution Abatement Plan Checklist

- **Edwards Aquifer Application Cover Page (TCEQ-20705)**
- **General Information Form (TCEQ-0587)**
 - Attachment A - Road Map
 - Attachment B - USGS / Edwards Recharge Zone Map
 - Attachment C - Project Description
- **Geologic Assessment Form (TCEQ-0585)**
 - Attachment A - Geologic Assessment Table (TCEQ-0585-Table)
 - Attachment B - Stratigraphic Column
 - Attachment C - Site Geology
 - Attachment D - Site Geologic Map(s)
- **Water Pollution Abatement Plan Application Form (TCEQ-0584)**
 - Attachment A - Factors Affecting Surface Water Quality
 - Attachment B - Volume and Character of Stormwater
 - Attachment C - Suitability Letter from Authorized Agent (if OSSF is proposed)
 - Attachment D - Exception to the Required Geologic Assessment (if requested)
 - Site Plan
- **Temporary Stormwater Section (TCEQ-0602)**
 - Attachment A - Spill Response Actions
 - Attachment B - Potential Sources of Contamination
 - Attachment C - Sequence of Major Activities
 - Attachment D - Temporary Best Management Practices and Measures
 - Attachment E - Request to Temporarily Seal a Feature (if requested)
 - Attachment F - Structural Practices
 - Attachment G - Drainage Area Map
 - Attachment H - Temporary Sediment Pond(s) Plans and Calculations
 - Attachment I - Inspection and Maintenance for BMPs
 - Attachment J - Schedule of Interim and Permanent Soil Stabilization Practices
- **Permanent Stormwater Section (TCEQ-0600)**
 - Attachment A - 20% or Less Impervious Cover Waiver (if requested for multi-family, school, or small business site)
 - Attachment B - BMPs for Upgradient Stormwater
 - Attachment C - BMPs for On-site Stormwater
 - Attachment D - BMPs for Surface Streams
 - Attachment E - Request to Seal Features (if sealing a feature)
 - Attachment F - Construction Plans
 - Attachment G - Inspection, Maintenance, Repair and Retrofit Plan
 - Attachment H - Pilot-Scale Field Testing Plan (if proposed)
 - Attachment I - Measures for Minimizing Surface Stream Contamination

- **Agent Authorization Form (TCEQ-0599), if application submitted by agent**
- **Application Fee Form (TCEQ-0574)**
- **Check Payable to the “Texas Commission on Environmental Quality”**
- **Core Data Form (TCEQ-10400)**

Texas Commission on Environmental Quality

Edwards Aquifer Application Cover Page

Our Review of Your Application

The Edwards Aquifer Program staff conducts an administrative and technical review of all applications. The turnaround time for administrative review can be up to 30 days as outlined in 30 TAC 213.4(e). Generally administrative completeness is determined during the intake meeting or within a few days of receipt. The turnaround time for technical review of an administratively complete Edwards Aquifer application is 90 days as outlined in 30 TAC 213.4(e). Please know that the review and approval time is directly impacted by the quality and completeness of the initial application that is received. In order to conduct a timely review, it is imperative that the information provided in an Edwards Aquifer application include final plans, be accurate, complete, and in compliance with [30 TAC 213](#).

Administrative Review

1. [Edwards Aquifer applications](#) must be deemed administratively complete before a technical review can begin. To be considered administratively complete, the application must contain completed forms and attachments, provide the requested information, and meet all the site plan requirements. The submitted application and plan sheets should be final plans. Please submit one full-size set of plan sheets with the original application, and half-size sets with the additional copies.

To ensure that all applicable documents are included in the application, the program has developed tools to guide you and web pages to provide all forms, checklists, and guidance. Please visit the below website for assistance: <http://www.tceq.texas.gov/field/eapp>.

2. This Edwards Aquifer Application Cover Page form (certified by the applicant or agent) must be included in the application and brought to the administrative review meeting.
3. Administrative reviews are scheduled with program staff who will conduct the review. Applicants or their authorized agent should call the appropriate regional office, according to the county in which the project is located, to schedule a review. The average meeting time is one hour.
4. In the meeting, the application is examined for administrative completeness. Deficiencies will be noted by staff and emailed or faxed to the applicant and authorized agent at the end of the meeting, or shortly after. Administrative deficiencies will cause the application to be deemed incomplete and returned.

An appointment should be made to resubmit the application. The application is re-examined to ensure all deficiencies are resolved. The application will only be deemed administratively complete when all administrative deficiencies are addressed.

5. If an application is received by mail, courier service, or otherwise submitted without a review meeting, the administrative review will be conducted within 30 days. The applicant and agent will be contacted with the results of the administrative review. If the application is found to be administratively incomplete, it can be retrieved from the regional office or returned by regular mail. If returned by mail, the regional office may require arrangements for return shipping.
6. If the geologic assessment was completed before October 1, 2004 and the site contains “possibly sensitive” features, the assessment must be updated in accordance with the *Instructions to Geologists* (TCEQ-0585 Instructions).

Technical Review

1. When an application is deemed administratively complete, the technical review period begins. The regional office will distribute copies of the application to the identified affected city, county, and groundwater conservation district whose jurisdiction includes the subject site. These entities and the public have 30 days to provide comments on the application to the regional office. All comments received are reviewed by TCEQ.
2. A site assessment is usually conducted as part of the technical review, to evaluate the geologic assessment and observe existing site conditions. The site must be accessible to our staff. The site boundaries should be

clearly marked, features identified in the geologic assessment should be flagged, roadways marked and the alignment of the Sewage Collection System and manholes should be staked at the time the application is submitted. If the site is not marked the application may be returned.

3. We evaluate the application for technical completeness and contact the applicant and agent via Notice of Deficiency (NOD) to request additional information and identify technical deficiencies. There are two deficiency response periods available to the applicant. There are 14 days to resolve deficiencies noted in the first NOD. If a second NOD is issued, there is an additional 14 days to resolve deficiencies. If the response to the second notice is not received, is incomplete or inadequate, or provides new information that is incomplete or inadequate, the application must be withdrawn or will be denied. Please note that because the technical review is underway, whether the application is withdrawn or denied **the application fee will be forfeited**.
4. The program has 90 calendar days to complete the technical review of the application. If the application is technically adequate, such that it complies with the Edwards Aquifer rules, and is protective of the Edwards Aquifer during and after construction, an approval letter will be issued. Construction or other regulated activity may not begin until an approval is issued.

Mid-Review Modifications

It is important to have final site plans prior to beginning the permitting process with TCEQ to avoid delays.

Occasionally, circumstances arise where you may have significant design and/or site plan changes after your Edwards Aquifer application has been deemed administratively complete by TCEQ. This is considered a “Mid-Review Modification”. Mid-Review Modifications may require redistribution of an application that includes the proposed modifications for public comment.

If you are proposing a Mid-Review Modification, two options are available:

- If the technical review has begun your application can be denied/withdrawn, your fees will be forfeited, and the plan will have to be resubmitted.
- TCEQ can continue the technical review of the application as it was submitted, and a modification application can be submitted at a later time.

If the application is denied/withdrawn, the resubmitted application will be subject to the administrative and technical review processes and will be treated as a new application. The application will be redistributed to the affected jurisdictions.

Please contact the regional office if you have questions. If your project is located in Williamson, Travis, or Hays County, contact TCEQ’s Austin Regional Office at 512-339-2929. If your project is in Comal, Bexar, Medina, Uvalde, or Kinney County, contact TCEQ’s San Antonio Regional Office at 210-490-3096

Please fill out all required fields below and submit with your application.

1. Regulated Entity Name: Rattlesnake Ranch Quarry					2. Regulated Entity No.: NEW				
3. Customer Name: Ranger Excavation, LP					4. Customer No.: 602783037				
5. Project Type: (Please circle/check one)	<input checked="" type="radio"/> New	<input type="radio"/> Modification			<input type="radio"/> Extension		<input type="radio"/> Exception		
6. Plan Type: (Please circle/check one)	<input checked="" type="radio"/> WPAP	<input type="radio"/> CZP	<input type="radio"/> SCS	<input type="radio"/> UST	<input type="radio"/> AST	<input type="radio"/> EX P	<input type="radio"/> EXT	Technical Clarification	Optional Enhanced Measures
7. Land Use: (Please circle/check one)	<input type="radio"/> Residential		<input checked="" type="radio"/> Non-residential			8. Site (acres):		163	
9. Application Fee:	\$10,000		10. Permanent BMP(s):			Earthen Berms, Vegetative Buffers			
11. SCS (Linear Ft.):	N/A		12. AST/UST (No. Tanks):			N/A			
13. County:	Williamson		14. Watershed:			Berry Creek			

Application Distribution

Instructions: Use the table below to determine the number of applications required. One original and one copy of the application, plus additional copies (as needed) for each affected incorporated city, county, and groundwater conservation district are required. Linear projects or large projects, which cross into multiple jurisdictions, can require additional copies. Refer to the “Texas Groundwater Conservation Districts within the EAPP Boundaries” map found at:

http://www.tceq.texas.gov/assets/public/compliance/field_ops/eapp/EAPP%20GWCD%20map.pdf

For more detailed boundaries, please contact the conservation district directly.

Austin Region			
County:	Hays	Travis	Williamson
Original (1 req.)	—	—	<u>X</u>
Region (1 req.)	—	—	<u>X</u>
County(ies)	—	—	<u>X</u>
Groundwater Conservation District(s)	<u>—</u> Edwards Aquifer Authority <u>—</u> Barton Springs/ Edwards Aquifer <u>—</u> Hays Trinity <u>—</u> Plum Creek	<u>—</u> Barton Springs/ Edwards Aquifer	NA
City(ies) Jurisdiction	<u>—</u> Austin <u>—</u> Buda <u>—</u> Dripping Springs <u>—</u> Kyle <u>—</u> Mountain City <u>—</u> San Marcos <u>—</u> Wimberley <u>—</u> Woodcreek	<u>—</u> Austin <u>—</u> Bee Cave <u>—</u> Pflugerville <u>—</u> Rollingwood <u>—</u> Round Rock <u>—</u> Sunset Valley <u>—</u> West Lake Hills	<u>—</u> Austin <u>—</u> Cedar Park <u>—</u> Florence <u>X</u> Georgetown <u>—</u> Jerrell <u>—</u> Leander <u>—</u> Liberty Hill <u>—</u> Pflugerville <u>—</u> Round Rock

San Antonio Region					
County:	Bexar	Comal	Kinney	Medina	Uvalde
Original (1 req.)	—	—	—	—	—
Region (1 req.)	—	—	—	—	—
County(ies)	—	—	—	—	—
Groundwater Conservation District(s)	<u>—</u> Edwards Aquifer Authority <u>—</u> Trinity-Glen Rose	<u>—</u> Edwards Aquifer Authority	<u>—</u> Kinney	<u>—</u> EAA <u>—</u> Medina	<u>—</u> EAA <u>—</u> Uvalde
City(ies) Jurisdiction	<u>—</u> Castle Hills <u>—</u> Fair Oaks Ranch <u>—</u> Helotes <u>—</u> Hill Country Village <u>—</u> Hollywood Park <u>—</u> San Antonio (SAWS) <u>—</u> Shavano Park	<u>—</u> Bulverde <u>—</u> Fair Oaks Ranch <u>—</u> Garden Ridge <u>—</u> New Braunfels <u>—</u> Schertz	NA	<u>—</u> San Antonio ETJ (SAWS)	NA

I certify that to the best of my knowledge, that the application is complete and accurate. This application is hereby submitted to TCEQ for administrative review and technical review.	
Nicolas E. Mercado, PE – License No. 144228	
Print Name of Customer/Authorized Agent	
<i>Nicolas E. Mercado</i>	12/19/2023
Signature of Customer/Authorized Agent	Date

FOR TCEQ INTERNAL USE ONLY			
Date(s) Reviewed:		Date Administratively Complete:	
Received From:		Correct Number of Copies:	
Received By:		Distribution Date:	
EAPP File Number:		Complex:	
Admin. Review(s) (No.):		No. AR Rounds:	
Delinquent Fees (Y/N):		Review Time Spent:	
Lat./Long. Verified:		SOS Customer Verification:	
Agent Authorization Complete/Notarized (Y/N):		Fee Check:	Payable to TCEQ (Y/N):
Core Data Form Complete (Y/N):			Signed (Y/N):
Core Data Form Incomplete Nos.:			Less than 90 days old (Y/N):

General Information Form

Texas Commission on Environmental Quality

For Regulated Activities on the Edwards Aquifer Recharge and Transition Zones and Relating to 30 TAC §213.4(b) & §213.5(b)(2)(A), (B) Effective June 1, 1999

To ensure that the application is administratively complete, confirm that all fields in the form are complete, verify that all requested information is provided, consistently reference the same site and contact person in all forms in the application, and ensure forms are signed by the appropriate party.

Note: Including all the information requested in the form and attachments contributes to more streamlined technical reviews.

Section 1.01 Signature

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. This **General Information Form** is hereby submitted for TCEQ review. The application was prepared by:


Print Name of Customer/Agent: Nicolas E. Mercado

Texas License No. 144228 | Firm No. 4524

Date: 12/19/2023

Signature of Customer/Agent:

Nicolas E. Mercado



Section 1.02 Project Information

1. Regulated Entity Name: Rattlesnake Ranch Quarry
2. County: Williamson County
3. Stream Basin: Berry Creek
4. Groundwater Conservation District (If applicable): N/A

5. Edwards Aquifer Zone:

- ☒ Recharge Zone
☒ Contributing Zone

☐ Transition Zone

6. Plan Type:

- ☒ WPAP
☐ SCS
☐ Modification

- ☐ AST
☐ UST
☐ Exception Request

7. Customer (Applicant):

Contact Person: Hamilton McRae

Entity: Ranger Excavating, LP.

Mailing Address: 5222 Thunder Creek Rd, Suite B1

City, State: Austin, TX

Zip: 78759

Telephone: 512-331-5551

FAX: 512-343-9618

Email Address: hamilton.mcrae@austingeologic.com

8. Agent/Representative (If any):

Contact Person: Nicolas Mercado, PE

Entity: Westward Environmental, Inc.

Mailing Address: PO Box 2205

City, State: Boerne, TX

Zip: 78006

Telephone: 830-249-8284

FAX: 830-249-0221

Email Address: nmercado@westwardenv.com

9. Project Location:

- ☐ The project site is located inside the city limits of ____.
- ☒ The project site is located outside the city limits but inside the ETJ (extra-territorial jurisdiction) of Georgetown.
- ☐ The project site is not located within any city's limits or ETJ.

10. ☒ The location of the project site is described below. The description provides sufficient detail and clarity so that the TCEQ's Regional staff can easily locate the project and site boundaries for a field investigation.

8880 Old 195, Florence, TX 76527. Located east of SH 195 and Old 195 (Rattlesnake Rd)

11. ☒ **Attachment A – Road Map.** A road map showing directions to and the location of the project site is attached. The project location and site boundaries are clearly shown on the map.
12. ☒ **Attachment B - USGS / Edwards Recharge Zone Map.** A copy of the official 7 ½ minute USGS Quadrangle Map (Scale: 1" = 2000') of the Edwards Recharge Zone is attached. The map(s) clearly show:
- ☒ Project site boundaries.
 - ☒ USGS Quadrangle Name(s).
 - ☒ Boundaries of the Recharge Zone (and Transition Zone, if applicable).
 - ☒ Drainage path from the project site to the boundary of the Recharge Zone.
13. ☒ **The TCEQ must be able to inspect the project site or the application will be returned.** Sufficient survey staking is provided on the project to allow TCEQ regional staff to locate

the boundaries and alignment of the regulated activities and the geologic or manmade features noted in the Geologic Assessment.

☒ Survey staking will be completed by this date: 10/23/2023

14. ☒ **Attachment C – Project Description.** Attached at the end of this form is a detailed narrative description of the proposed project. The project description is consistent throughout the application and contains, at a minimum, the following details:

- ☒ Area of the site
- ☒ Offsite areas
- ☒ Impervious cover
- ☒ Permanent BMP(s)
- ☒ Proposed site use
- ☒ Site history
- ☒ Previous development
- ☒ Area(s) to be demolished

15. Existing project site conditions are noted below:

- ☐ Existing commercial site
- ☐ Existing industrial site
- ☒ Existing residential site
- ☒ Existing paved and/or unpaved roads
- ☒ Undeveloped (Cleared)
- ☒ Undeveloped (Undisturbed/Uncleared)
- ☐ Other: _____

Section 1.03 Prohibited Activities

16. ☒ I am aware that the following activities are prohibited on the Recharge Zone and are not proposed for this project:

- (1) Waste disposal wells regulated under 30 TAC Chapter 331 of this title (relating to Underground Injection Control);
- (2) New feedlot/concentrated animal feeding operations, as defined in 30 TAC §213.3;
- (3) Land disposal of Class I wastes, as defined in 30 TAC §335.1;
- (4) The use of sewage holding tanks as parts of organized collection systems; and
- (5) New municipal solid waste landfill facilities required to meet and comply with Type I standards which are defined in §330.41(b), (c), and (d) of this title (relating to Types of Municipal Solid Waste Facilities).
- (6) New municipal and industrial wastewater discharges into or adjacent to water in the state that would create additional pollutant loading.

17. ☒ I am aware that the following activities are prohibited on the Transition Zone and are not proposed for this project:

- (1) Waste disposal wells regulated under 30 TAC Chapter 331 (relating to Underground Injection Control);
- (2) Land disposal of Class I wastes, as defined in 30 TAC §335.1; and
- (3) New municipal solid waste landfill facilities required to meet and comply with Type I standards which are defined in §330.41 (b), (c), and (d) of this title.

Section 1.04 Administrative Information

18. The fee for the plan(s) is based on:

- ☒ For a Water Pollution Abatement Plan or Modification, the total acreage of the site where regulated activities will occur.
- ☐ For an Organized Sewage Collection System Plan or Modification, the total linear footage of all collection system lines.
- ☐ For a UST Facility Plan or Modification or an AST Facility Plan or Modification, the total number of tanks or piping systems.
- ☐ A request for an exception to any substantive portion of the regulations related to the protection of water quality.
- ☐ A request for an extension to a previously approved plan.

19. ☒ Application fees are due and payable at the time the application is filed. If the correct fee is not submitted, the TCEQ is not required to consider the application until the correct fee is submitted. Both the fee and the Edwards Aquifer Fee Form have been sent to the Commission's:

- ☒ TCEQ cashier
- ☐ Austin Regional Office (for projects in Hays, Travis, and Williamson Counties)
- ☐ San Antonio Regional Office (for projects in Bexar, Comal, Kinney, Medina, and Uvalde Counties)

20. ☒ Submit one (1) original and one (1) copy of the application, plus additional copies as needed for each affected incorporated city, groundwater conservation district, and county in which the project will be located. The TCEQ will distribute the additional copies to these jurisdictions. The copies must be submitted to the appropriate regional office.



21. ☒ No person shall commence any regulated activity until the Edwards Aquifer Protection Plan(s) for the activity has been filed with and approved by the Executive Director.

1. WRITING CONSTRUCTION NOTIFICATION MUST BE SUBMITTED TO THE TCEQ REGIONAL OFFICE AT LEAST 48 HOURS PRIOR TO THE START OF ANY REGULATED ACTIVITIES. THIS NOTICE MUST INCLUDE:
 - THE NAME OF THE APPROVED PROJECT;
 - THE ACTIVITY START DATE; AND
 - THE CONTACT INFORMATION OF THE PRIME CONTRACTOR
2. ALL CONTRACTORS CONDUCTING REGULATED ACTIVITIES ASSOCIATED WITH THIS PROJECT MUST BE PROVIDED WITH COMPLETE COPIES OF THE APPROVED CONSTRUCTION ABATEMENT PLAN (CWAP) AND THE TCEQ LETTER INDICATING THE SPECIFIC CONDITIONS OF ITS APPROVAL. DURING THE COURSE OF THESE REGULATED ACTIVITIES, THE CONTRACTORS ARE REQUIRED TO KEEP ON-SITE COPIES OF THE APPROVED PLAN AND APPROVAL LETTER.
3. IF ANY SENSITIVE FEATURE(S) (CAVES, SOLUTION, CAVITY, SINK HOLE, ETC.) IS DISCOVERED DURING CONSTRUCTION, ALL WORKERS OF THE PROJECT MUST IMMEDIATELY STOP ALL ACTIVITIES IMMEDIATELY. THE APPROPRIATE TCEQ REGIONAL OFFICE MUST BE IMMEDIATELY NOTIFIED OF ANY SENSITIVE FEATURES ENCOUNTERED DURING CONSTRUCTION. CONSTRUCTION ACTIVITIES MAY NOT BE RESUMED UNTIL THE TCEQ HAS REVIEWED AND APPROVED THE APPROPRIATE PROTECTIVE MEASURES IN ORDER TO PROTECT ANY SENSITIVE FEATURE AND THE EDWARDS AQUIFER FROM POTENTIALLY ADVERSE IMPACTS TO WATER QUALITY.
4. NO TEMPORARY OR PERMANENT HAZARDOUS SUBSTANCE STORAGE TANK SYSTEM SHALL BE INSTALLED WITHIN 150 FEET OF A WATER SUPPLY SOURCE, DISTRIBUTION SYSTEM, WELL, OR SENSITIVE FEATURE.
5. PRIOR TO BEGINNING ANY CONSTRUCTION ACTIVITY, ALL TEMPORARY EROSION AND SEDIMENTATION (E&S) CONTROL MEASURES MUST BE PROPERLY INSTALLED, AND MAINTAINED IN ACCORDANCE WITH THE APPROVED PLANS AND THE TCEQ REGIONAL OFFICE'S SUPERVISORY COMMENTS. INSPECTIONS INDICATE A CONTROL HAS BEEN USED INAPPROPRIATELY, OR INCORRECTLY, THE APPLICANT MUST REPLACE OR MODIFY THE CONTROL FOR SITE SITUATIONS. THESE CONTROLS MUST REMAIN IN PLACE UNTIL DISTURBED AREAS HAVE BEEN PERMANENTLY STABILIZED.
6. ANY SEDIMENT THAT ESCAPES THE CONSTRUCTION SITE MUST BE COLLECTED AND PROPERLY DISPOSED OF BEFORE THE NEXT RAINFALL EVENT. SEDIMENT THAT IS NOT WASHED INTO SURFACE STREAMS, SENSITIVE FEATURES, ETC.
7. SEDIMENT MUST BE REMOVED FROM THE SEDIMENT TRAPS OR SEDIMENTATION BASINS NOT LATER THAN WHEN IT OCCUPIES 50% OF THE BASIN'S DESIGN CAPACITY.
8. LITTER, CONSTRUCTION DEBRIS, AND CONSTRUCTION CHEMICALS EXPOSED TO STORMWATER MUST BE PREVENTED FROM BEING DISCHARGED OFFSITE.
9. ALL SPOILS (EXCAVATED MATERIAL) GENERATED FROM THE PROJECT SITE MUST BE STORED ON-SITE WITH PROPER E&S CONTROLS. FOR STORAGE OR DISPOSAL OF SPOILS AT ANOTHER SITE ON THE EDWARDS AQUIFER RECHARGE ZONE, THE APPLICANT MUST OBTAIN A PERMIT FROM THE TCEQ REGIONAL OFFICE. SPOILS ARE NOT TO BE USED FOR THE PLACEMENT OF FILL MATERIAL OR MASS GRADING PRIOR TO THE PLACEMENT OF SPOILS AT THE OTHER SITE.
10. IF PORTIONS OF THE SITE WILL HAVE A TEMPORARY OR PERMANENT CEASE IN CONSTRUCTION ACTIVITY LASTING LONGER THAN 14 DAYS, SOIL STABILIZATION IN THOSE AREAS SHALL BE INITIATED AS SOON AS POSSIBLE PRIOR TO THE 14TH DAY AFTER THE PORTION OF THE SITE HAS CEASED CONSTRUCTION. IF WEATHER PREVENT ACTION BY THE 14TH DAY, STABILIZATION MEASURES SHALL BE INITIATED AS SOON AS POSSIBLE.
11. THE FOLLOWING RECORDS SHALL BE MAINTAINED AND MADE AVAILABLE TO THE TCEQ UPON REQUEST:
 - THE DATES WHEN MAJOR GRADING ACTIVITIES OCCURRED;
 - THE DATES WHEN CONSTRUCTION ACTIVITIES TEMPORARILY OR PERMANENTLY CEASED ON A PORTION OF THE SITE; AND
 - THE DATES WHEN STABILIZATION MEASURES WERE INITIATED.
12. THE HOLDER OF ANY APPROVED EDWARDS AQUIFER PROTECTION PLAN MUST NOTIFY THE APPROPRIATE REGIONAL OFFICE IN WRITING AND OBTAIN APPROVAL FROM THE EXECUTIVE DIRECTOR PRIOR TO INITIATING ANY OF THE FOLLOWING:
 - A. ANY PHYSICAL OR OPERATIONAL MODIFICATION OF ANY WATER POLLUTION ABATEMENT STRUCTURE(S), INCLUDING BUT NOT LIMITED TO POND, DAMS, BERMS, SEWAGE TREATMENT PLANTS, AND DIVERSIONARY STRUCTURES;
 - B. ANY CHANGE IN THE NATURE OR CHARACTER OF THE REGULATED ACTIVITY FROM THAT WHICH WAS ORIGINALLY APPROVED; OR
 - C. ANY DEVELOPMENT OF LAND PREVIOUSLY IDENTIFIED AS UNDEVELOPED IN THE ORIGINAL WATER POLLUTION ABATEMENT PLAN.

BMP CONSTRUCTION NOTES

- GENERAL NOTES

- THE CONTRACTOR SHALL BE RESPONSIBLE AT ALL TIMES THROUGHOUT THE DURATION OF CONSTRUCTION FOR THE PROTECTION OF EXISTING AND NEWLY INSTALLED FACILITIES FROM DAMAGE OR DISRUPTION OF SERVICE. THE CONTRACTOR SHALL BE RESPONSIBLE FOR TAKING SUCH MEASURES AS NECESSARY TO PROTECT THE HEALTH, SAFETY, AND WELFARE OF THOSE PERSONS HAVING ACCESS TO THE WORK SITE.
2. FACILITIES PROPOSED HEREIN SHALL BE CONSTRUCTED IN ACCORDANCE WITH THE APPROVED PLANS, DEVIATIONS FROM THE APPROVED PLANS SHALL BE APPROVED IN ADVANCE BY THE ENGINEER OF RECORD.
3. UPON COMPLETION OF CONSTRUCTION AND PRIOR TO FINAL ACCEPTANCE OF THE WORK, A FINAL INSPECTION SHALL VERIFY PROPER ADHERENCE TO ALL FACETS OF THE PLANS AND SPECIFICATIONS.
4. AS-BUILT DRAWINGS SHALL BE PREPARED BY A REGISTERED LAND SURVEYOR, REGISTERED IN THE STATE OF TEXAS, AND SUBMITTED BY THE CONTRACTOR TO THE ENGINEER OF RECORD. CONTRACTOR TO PROVIDE RECORD INFORMATION WHICH LOCATES ALL UNDERGROUND UTILITIES, SITE GRADING AND CLEARANCE TO WATER MAIN FROM OTHER UTILITIES HORIZONTALLY AND VERTICALLY.
5. CONTRACTOR SHALL NOTIFY TEXAS811 ONE CALL SYSTEM (1-800-344-8377) 48 HOURS IN ADVANCE OF CONSTRUCTION.
6. ALL EXISTING, DEBRIS, CONCRETE OR OTHER UNSUITABLE MATERIAL SHALL BE LEGALLY DISPOSED OF OFF-SITE IN AN APPROPRIATE AREA AT THE CONTRACTOR'S EXPENSE.
7. CONTRACTOR SHALL UTILIZE CONSTRUCTION METHODS AND DEVICES, SUCH AS TURBIDITY SCREENS, SEDIMENTATION BASINS, ETC., TO PREVENT EROSION AND SILTATION OF ADJACENT AREAS AND LOCAL WATER QUALITY STANDARDS.
8. ALL CONSTRUCTION SHALL BE DONE IN A SAFE MANNER, SPECIFICALLY, THE RULES AND REGULATIONS OF THE TEXAS DEPARTMENT OF TRANSPORTATION SHALL BE STRICTLY OBSERVED.
9. MINIMUM COVER SHALL BE 3.0 FEET FOR ALL PIPES, (TYPICAL) UNLESS OTHERWISE NOTED ON DRAWINGS.
10. ALL OPEN TRENCHES AND HOLES ADJACENT TO ROADWAY OR WALKWAYS SHALL BE PROPERLY MARKED AND PROTECTED WITH FLOODING SHALL BE PREPARED BY A REGISTERED LAND SURVEYOR, REGISTERED IN THE STATE OF TEXAS, AND SUBMITTED BY THE CONTRACTOR TO THE ENGINEER OF RECORD.
11. CONTRACTOR SHALL MONITOR AND PROHIBIT THE DEFACTING OF FRESHLY PLACED CONCRETE SURFACES, ANY CONCRETE SURFACES DEFACTED SHALL BE REPLACED AT NO ADDITIONAL COST TO THE OWNER.
12. CLEARING AND GRUBBING SHALL INCLUDE REMOVAL OF ALL VEGETATION AS REQUIRED TO CONSTRUCT THE REQUIRED IMPROVEMENTS.
13. PROJECT SITE SAFETY:
- 13.1. THE ENGINEER/OWNER OR THEIR EMPLOYEES HAVE NO AUTHORITY TO EXERCISE ANY CONTROL OVER THE CONTRACTOR OR ANY SUB-CONTRACTOR OR ANY OTHER ENTITY OR THEIR EMPLOYEES IN CONNECTION WITH THEIR WORK OR ANY JOBSITE HEALTH OR SAFETY PRECAUTIONS.
- 13.2. THE CONTRACTOR IS SOLELY RESPONSIBLE FOR JOBSITE SAFETY, AND WARRANTS THAT THIS INTENT IS DEVOLVED FROM THE AGREEMENT TO THE CONTRACTOR.
- 13.3. ALL EXISTING OVERHEAD AND UNDERGROUND UTILITIES SHOWN ON THESE DRAWINGS OR ENCOUNTERED THROUGH THE PROGRESSION OF WORK AT THIS PROJECT SITE ARE ASSUMED TO BE LIVE. CONTRACTOR SHALL BE RESPONSIBLE FOR ALL SAFETY PRECAUTIONS WHEN WORKING AROUND EXISTING OVERHEAD OR UNDERGROUND UTILITIES.
14. ALL CONCRETE SHALL DEVELOP A MINIMUM OF 4000 p.s.i. COMPRESSIVE STRENGTH AT 28 DAYS, UNLESS OTHERWISE STATED.
15. THE SEQUENCE OF CONSTRUCTION SHALL BE SUCH THAT ALL UNDERGROUND INSTALLATION OF ANY KIND THAT WILL COME UNDER THE PAVEMENT OR WITHIN 10 FEET OF ITS EDGES SHALL BE INSTALLED PRIOR TO THE CONSTRUCTION OF THE PAVEMENT.
16. TRENCHES SHALL BE DRY WHEN PIPES ARE INSTALLED. PIPES PLACED BELOW THE WATER TABLE SHALL BE BEDDED ON PEA GRAVEL AND WELL POINT SYSTEMS SHALL BE USED. ALL DOWATERING PERMITS ARE THE RESPONSIBILITY OF THE CONTRACTOR.
17. ALL REQUESTS FOR SHOP DRAWINGS SHALL BE SUBMITTED FOR APPROVAL PRIOR TO CONSTRUCTION. ALL REQUESTS FOR MATERIAL SUBSTITUTIONS MUST BE APPROVED PRIOR TO DELIVERY TO THE SITE. SHOP DRAWINGS SHALL BE SUBMITTED FOR ALL MANUFACTURED ITEMS.
18. ALL TRENCHES IN THE FINISHED GRADE SHALL BE REINFORCED WITH REBAR FROM THE BOTTOM OF THE SUB GRADE.
19. ALL CONSTRUCTION SHALL BE IN ACCORDANCE WITH THE STDS OF ICEO
20. CONTRACTOR SHALL PERFORM ALL WORK NECESSARY TO LOCATE, EXCAVATE AND PREPARE FOR CONNECTIONS TO THE EXISTING SYSTEMS AS SHOWN ON THE DRAWINGS.
21. IF SOIL IS FOUND SHOWN, IT SHALL BE PLACED 2" BELOW THE EDGES OF PAVEMENT TO ALLOW WATER TO DRAIN.
22. COURTS COURTS ARE PRE DEVELOPMENT CONCEPTS
23. COMPACTION NOTES:
- 23.1. PLACE FILL AREAS WHERE WATER WILL BE IMPOUNDED:
- 23.1. PLACE FILL IN LIFTS NO MORE THAN 12" DEEP AT NEAR OPT. MOISTURE CONTENT.
- 23.2. COMPACT TO AT LEAST 95% RC (ASTM D698)
- 23.3. COMPACT TO SLOPE OF FACE
- FOR ON GRADE BERMS AND OTHER MISC. FILL
- 23.4. PLACE CLEAN FILL IN 12" LIFTS
- 23.5. COMPACT WITH ON-SITE HEAVY EQUIPMENT
24. ALL CONCRETE SURFACES TO BE BROOM FINISH
25. DRAINAGE STRUCTURES TO MEET MIN. 1'x0.5' SPECIFICATIONS FOR CONSTRUCTION AND PLACEMENT OF TYPE 3 DROP INLET
26. CONTRACTOR SHALL NOTIFY ALL EXISTING CONDITIONS AND GRADING PRIOR TO CONSTRUCTION. ENGINEER OF RECORD SHALL BE VERIFIED ANY DISCREPANCIES PRIOR TO CONSTRUCTION.
27. ALL RIP RAP SHALL BE COURSE GRADED ROCK AND SHALL BE SIZED IN ACCORDANCE WITH THE FOLLOWING TABLE
- | SLOPE | RIp RAP SIZE |
|------------|--------------|
| 0.5%-1% | 4" ROCK |
| 1.1% TO 2% | 6" ROCK |
| 2.1% TO 4% | 8" ROCK |
| 4.1% TO 5% | 8"-12" ROCK |
28. MIN THICKNESS OF RIPRAP TO BE 1.5 TIMES THE STONE DIAMETER UNO
29. GEOTEXTILE FABRIC (FILTER FABRIC) SHALL BE A NON-WOVEN POLYPROPYLENE FABRIC DESIGNED SPECIFICALLY FOR USE AS A SOIL FILTRATION MEDIA w/ APPROX. WEIGHT 6.02/OZ/YO 2, A MULLEN BURST RATING OF 10 TO 12 AND AN EQUIVALENT OPENING SIZE (ES0) GREATER THAN #50 SIEVE. TENCATE MIRRIU-N-SERIES OF APPROVED QUALITY
30. BASIN LINERS SHALL COMPLY W/ R-348 FOR COMPACTED CLAY LINERS
31. ALL DISTURBED AREAS TO BE SEEDED AND MULCHED FOR SLOPE STABILIZATION. SEED TO BE BERMUODA GRASS
32. ALL CONCRETE SLABS TO HAVE #5 BARS EACH WAY AT 12" c/c IN CENTER OF SLAB UNO.



VICINITY ROAD MAP
SCALE : 1" = 2,000'

SHEET INDEX


1. C1 - COVER PAGE
2. C2 - INTERIM CONDITIONS PLAN
3. C3 - FINAL CONDITIONS PLAN

IMAGE: N/A	
ISSUE DATE:	12/01/2023
DRAWN BY:	BGB
CHECKED BY:	NEM
SCALE: 1" =	2,000'
JOB NO.:	11260-005

SHEET NO.:



C1

OF C3



[illegible]

Rick E. Merino
12/19/2023

COVER PAGE
WPAP APPLICATION
RANGER EXCAVATING, LP
8880 OLD 195, FLORENCE, TX 76527



LEGEND

- PROPERTY LINE
 FLOW PATH
 EDWARDS ZONE BOUNDARY
 FLOW ARROW

NOTE:

USGS TOPO 7.5-MINUTE MAP
FOR FLORENCE, TEXAS AND
COBBS CAVERN, TEXAS

SHEET NO.:

01

OF 01

IMAGE:
USGS Topo 7.5-Minute Maps

ISSUE DATE:12/1/2023

DRAWN BY:BGB

CHECKED BY:NEM

SCALE: 1" =2,000'

JOB NO.:11260-005

USGS TOPO & EDWARDS AQUIFER

RATTLESNAKE RANCH QUARRY – WPAP

RANGER EXCAVATING, LP


FLORENCE, WILLIAMSON COUNTY, TX

REV.

DESCRIPTION

BY

DATE



WESTWARD

Environmental. Engineering. Natural Resources.

P.O. Box 2205 Boerne, Texas 78006

(830) 249-8284 Fax: (830) 249-0221

TBPE REG. NO.: F-4524

TBPG REG. NO.: 50112

**Ranger Excavating, LP
Rattlesnake Ranch Quarry**

General Information Form Attachment A

Road Map

Please see attached the Vicinity Map on the Cover Page (Sheet C1)

General Information Form Attachment B

USGS / Edwards Recharge Zone Map

Please see attached USGS / Edwards Recharge Zone Map.

**General Information Form (TCEQ-0587)
Attachment C**

Project Description

This Water Pollution Abatement Plan (WPAP) has been prepared on behalf of Ranger Excavating, LP, for the proposed Rattlesnake Ranch Quarry (Site). This approximately 163-acre site, located in Williamson County, Florence, Texas, is to be developed for a new limestone quarrying operation. The site is located over the Edwards Aquifer with the east portion over the Recharge Zone and the west portion over the Contributing Zone.

The majority of the 163-acre site is largely undeveloped, with the exception of a residence structure, unpaved ranch roads, well sites, and various agricultural storage buildings. The site will require clearing and grubbing before mining begins. The quarry pit will start construction within an initial 10-acre area and continually expand as mining progresses. The land that is not actively being mined will be utilized for ongoing ranching and agricultural activities. The Site may be entered at the main entrance through a gravel road off Old 195 on the West side of the property. A new entrance road has been proposed further north off Old 195 (see the Proposed Conditions Plan Sheet). Ranger proposes to construct/install a new office and maintenance shop after the initial mining phase has commenced. The only impervious cover expected from this project are the improved operation roads and the future office and maintenance shop with their pertaining parking areas. Given the amount of impervious cover will change as the quarry pit expands, and the majority of expected impervious cover will be from the operation road, the maximum estimated area for said cover is about 3.23 acres (or 19.9%), during the Interim Phase. When the final pit limits have been reached and a new scale and office are constructed, the impervious cover (not contained within the pit) is estimated to be 1.50 acres. All new impervious covers not contained within the pit, including the roads and new office, will be treated by a natural vegetated filter strip.

It is not expected that any significant amount of groundwater will be encountered in the quarry excavation. A 25-foot buffer between the pit floor and the groundwater level will be maintained. There were no monitor wells located on or near the site that had recent data, therefore, the wet-weather high-water elevation for State well no. 5827305 was selected from Table 1 of RG-500. The elevation is given as 690 ft-amsl, so with a 25-ft buffer, the proposed pit bottom is set at 715

Ranger Excavating, LP
Rattlesnake Ranch Quarry

ft amsl. Other structures and activities that will occur onsite include rock crushing, stockpile areas, screens, conveyors, truck scales, scale house, maintenance shop and an office.

Earthen berms shall be utilized as temporary best management practices (BMPs) to control and redirect stormwater runoff from disturbed areas. All berms shall be constructed and maintained to at least meet the height of the tallest vehicle axle onsite. As mining progresses, all the berms will expand to contain the current mining activities. Runoff from all impervious cover will be fully contained within the earthen berms and/or quarry pits, with the exception of the portion of the main entry/exit drive which extends outside of the bermed area. This portion of the driveway will be treated by natural vegetative filter strips. See the attached Interim Conditions plan sheet. As quarry operations expand, areas greater than 10-acres of common drainage may be disturbed at a time, however these areas will be contained within temporary earthen berms, which will expand with the operation up to the Final Earthen Berm (as shown on the Final Conditions Map), and all run-off from these areas will remain contained on-site, ultimately draining to the pit.

Temporary natural existing vegetation will be maintained in a 25-foot buffer from the stream centerline or the floodplain along each side of the unnamed tributary of Berry Creek. This buffer will be maintained with the exception of the two on-grade crossings (one existing and one proposed) shown on the Final Conditions site plan. These crossings will be paved & swept periodically to control TSS. Appropriate permits will be obtained from the Williamson County floodplain administrator and/or the US Army Corps of Engineers, if needed, before any work is performed in the mapped floodplain.

Fueling of mobile equipment and portable screen occurs over compacted base material via mobile refueler.

Existing ranch roads will continue to be used for access around the site. Upon termination of quarrying activities, stormwater that is in the quarry pit will not discharge to the surface; stormwater will be retained in the pit.

Trash generated on-site will be disposed of in a dumpster and handled by a licensed waste service provider. One private septic system is located at the current residential structure.

A geologic assessment (GA) of the site was completed on October 24 and 25, 2023. This GA covered the entire 163-acre tract under the supervision of John J. Sackrider, PG. Twelve (12) features were identified during the GA. Of the twelve (12) features identified, none of the features were classified as sensitive features. Two water wells were discovered in the same well house near the existing residence. One of the wells appeared to be operational and the other was not plumbed into anything. During the desktop review, no public information was available for either well. The well not in use is proposed to be properly abandoned. The other well will be verified to be in compliance and when no longer in use will be properly abandoned as well. A copy of the original geologic assessment is included with this application.

RANGER EXCAVATING, LP

GEOLOGIC ASSESSMENT

RATTLESNAKE RANCH QUARRY
8880 OLD 195
FLORENCE, TEXAS 76527
WILLIAMSON COUNTY

Submitted to: TCEQ Region 11, Austin

Prepared By:




Boerne, Texas

830-249-8284

Date: December 2023

Project No. 11260-005

-JG-



Signature: _____

John J. Sackrider, P.G. - License No. 12654

TX PG Firm No. 50112

Date: 12/15/2023

Article I. Geologic Assessment

Texas Commission on Environmental Quality

For Regulated Activities on The Edwards Aquifer Recharge/transition Zones and Relating to 30 TAC §213.5(b)(3), Effective June 1, 1999

To ensure that the application is administratively complete, confirm that all fields in the form are complete, verify that all requested information is provided, consistently reference the same site and contact person in all forms in the application, and ensure forms are signed by the appropriate party.

Note: Including all the information requested in the form and attachments contributes to more streamlined technical reviews.

Section 1.01 Signature

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. My signature certifies that I am qualified as a geologist as defined by 30 TAC Chapter 213.

Print Name of Geologist:

Telephone: 830-249-8284

John J. Sackrider, P.G. #12654



Fax: 830-249-0221

Date: 12/15/2023

Representing: Westward Environmental, Inc., TBPGE Registered Geoscience Firm 50012

(Name of Company and TBPGE or TBPE registration number)

Signature of Geologist:



Regulated Entity Name: Rattlesnake Ranch Quarry

Section 1.02 Project Information

1. Date(s) Geologic Assessment was performed: October 23-24, 2023

2. Type of Project:

☒ WPAP
☐ SCS

☒ AST
☐ UST

3. Location of Project:

☒ Recharge Zone
☐ Transition Zone
☒ Contributing Zone within the Transition Zone

4. ☒ **Attachment A - Geologic Assessment Table.** Completed Geologic Assessment Table (Form TCEQ-0585-Table) is attached.
5. ☒ Soil cover on the project site is summarized in the table below and uses the SCS Hydrologic Soil Groups* (Urban Hydrology for Small Watersheds, Technical Release No. 55, Appendix A, Soil Conservation Service, 1986). If there is more than one soil type on the project site, show each soil type on the site Geologic Map or a separate soils map.

Article II. Table 1 - Soil Units, Infiltration Characteristics and Thickness

Soil Name	Group*	Thickness(feet)
BkE	D	< 2
DnB	D	< 5
EeB	D	< 2
ErE	D	< 2
FaB	D	< 5
GsB	D	< 4

** Soil Group Definitions (Abbreviated)*

- A. *Soils having a high infiltration rate when thoroughly wetted.*
- B. *Soils having a moderate infiltration rate when thoroughly wetted.*
- C. *Soils having a slow infiltration rate when thoroughly wetted.*
- D. *Soils having a very slow infiltration rate when thoroughly wetted.*

6. ☒ **Attachment B – Stratigraphic Column.** A stratigraphic column showing formations, members, and thicknesses is attached. The outcropping unit, if present, should be at the top of the stratigraphic column. Otherwise, the uppermost unit should be at the top of the stratigraphic column.
7. ☒ **Attachment C – Site Geology.** A narrative description of the site specific geology including any features identified in the Geologic Assessment Table, a discussion of the potential for fluid movement to the Edwards Aquifer, stratigraphy, structure(s), and karst characteristics is attached.
8. ☒ **Attachment D – Site Geologic Map(s).** The Site Geologic Map must be the same scale as the applicant's Site Plan. The minimum scale is 1": 400'
 Applicant's Site Plan Scale: 1" = 200'
 Site Geologic Map Scale: 1" = 200'
 Site Soils Map Scale (if more than 1 soil type): 1" = 200'
9. Method of collecting positional data:
 - ☒ Global Positioning System (GPS) technology.
 - ☐ Other method(s). Please describe method of data collection: _____

10. ☒ The project site and boundaries are clearly shown and labeled on the Site Geologic Map.
11. ☒ Surface geologic units are shown and labeled on the Site Geologic Map.
12. ☒ Geologic or manmade features were discovered on the project site during the field investigation. They are shown and labeled on the Site Geologic Map and are described in the attached Geologic Assessment Table.
- ☐ Geologic or manmade features were not discovered on the project site during the field investigation.
13. ☒ The Recharge Zone boundary is shown and labeled, if appropriate.
14. All known wells (test holes, water, oil, unplugged, capped and/or abandoned, etc.): If applicable, the information must agree with Item No. 20 of the WPAP Application Section.
- ☒ There are 2 (#) wells present on the project site and the locations are shown and labeled. (Check all of the following that apply.)
- ☐ The wells are not in use and have been properly abandoned.
- ☒ The wells are not in use and will be properly abandoned.
- ☒ The well is in use and comply with 16 TAC Chapter 76.
- ☐ There are no wells or test holes of any kind known to exist on the project site.

Section 2.01 Administrative Information

15. ☒ Submit one (1) original and one (1) copy of the application, plus additional copies as needed for each affected incorporated city, groundwater conservation district, and county in which the project will be located. The TCEQ will distribute the additional copies to these jurisdictions. The copies must be submitted to the appropriate regional office.

Attachment A

Geologic Assessment Table (Form TCEQ-0585)

GEOLOGIC ASSESSMENT TABLE						PROJECT NAME: RATTLESNAKE RANCH QUARRY													
LOCATION			FEATURE CHARACTERISTICS											EVALUATION			PHYSICAL SETTING		
1A	1B *	1C*	2A	2B	3	4			5	5A	6	7	8A	8B	9	10		11	12
FEATURE ID	LATITUDE	LONGITUDE	FEATURE TYPE	POINTS	FORMATION	DIMENSIONS (FEET)			TREND (DEGREES)	DOW	DENSITY (NO/FT)	APERTURE (FEET)	INFILL	RELATIVE INFILTRATION RATE	TOTAL	SENSITIVITY		CATCHMENT AREA (ACRES)	TOPOGRAPHY
						X	Y	Z		10					10	<40	≥40	<1.6	≥1.6
S-1	30.746638	-97.758441	CD	5	Kkv	55	30	1	N/A				V	5	10	X		X	Hillside
S-2	30.786350	-97.759031	CD	5	Kkv	180	135	8	N/A				V, O	5	10	X		X	Hillside
S-3	30.785440	-97.759709	CD	5	Kkv	10	20	0.5	N/A				V, O	5	10	X		X	Hillside
S-4	30.785968	-97.759790	CD	5	Kkv	30	15	1	N/A				V, O	5	10	X		X	Floodplain/Drainage
S-5	30.788736	-97.759534	CD	5	Kkv	60	40	2	N/A				V, O	5	10	X		X	Hillside
S-6	30.790083	-97.757300	CD	5	Kkv	60	10	2	N/A				V, X	5	10	X		X	Hillside
S-7	30.788039	-97.757140	MB	30	Kc	0.33		Unknown	None				X	5	35	X		X	Hillside
S-8	30.788438	-97.756784	MB	30	Kc	10		25+	None				X	5	35	X		X	Hillside
S-9	30.789164	-97.754101	SC	20	Ked	0.75	0.5	3	10				O	5	25	X		X	Hillside
S-10	30.790141	-97.754061	SC	20	Ked	0.5	0.33	3	55				O	5	25	X		X	Hillside
S-11	30.786838	-97.762148	CD	20	Kkv	165	150	10	None				O	5	25	X		X	Hillside
S-12	30.788039	-97.757140	MB	30	Kc	0.33		Unknown	None				X	5	35	X		X	Hillside


* DATUM: NAD 83

2A TYPE	TYPE	2B POINTS
C	Cave	30
SC	Solution cavity	20
SF	Solution-enlarged fracture(s)	20
F	Fault	20
O	Other natural bedrock features	5
MB	Manmade feature in bedrock	30
SW	Swallow hole	30
SH	Sinkhole	20
CD	Non-karst closed depression	5
Z	Zone, clustered or aligned features	30


8A INFILLING	
N	None, exposed bedrock
C	Coarse - cobbles, breakdown, sand, gravel
O	Loose or soft mud or soil, organics, leaves, sticks, dark colors
F	Fines, compacted clay-rich sediment, soil profile, gray or red colors
V	Vegetation. Give details in narrative description
FS	Flowstone, cements, cave deposits
X	Other materials

12 TOPOGRAPHY
Cliff, Hilltop, Hillside, Drainage, Floodplain, Streambed

I have read, I understood, and I have followed the Texas Commission on Environmental Quality's Instructions to Geologists. The information presented here complies with that document and is a true representation of the conditions observed in the field. My signature certifies that I am qualified as a geologist as defined by 30 TAC Chapter 213.




Date 12/15/2023



Attachment B

Stratigraphic Column

Generalized Stratigraphic Column



Adapted from *Hydrology of the Northern Segment of the Edwards Aquifer, Austin region* (Senger, 1990).

Attachment C

Site Geology (Geologic Narrative)

Geologic Narrative

1.0 PURPOSE

Westward Environmental, Inc. (WESTWARD) was retained by Ranger Excavating, LP, Inc. (Client) to prepare a Geologic Assessment (GA) on a ~163-acre tract (Site). This GA was prepared as a required attachment to a Water Pollution Abatement Plan (WPAP) for the Site as required by the Texas Commission of Environmental Quality (TCEQ).

2.0 REGULATORY GUIDANCE

Title 30, Chapter 213 of the Texas Administrative Code

This report was prepared in accordance with *Instructions for Geologists for Geologic Assessments on the Edwards Aquifer Recharge/Transition Zones (TCEQ-0585 (Rev. 10-01-04))* and will be reviewed pursuant to Title 30, Chapter 213 of the Texas Administrative Code.

3.0 PROJECT LOCATION

The Site is located between the cities of Florence and Georgetown, where Highway 195 intersects with Old 195 in Williamson County, Texas. The address is listed as 8880 Old 195, Florence, Texas 76527. The Site lies within the northern portion of the City of Georgetown's Extra-Territorial Jurisdiction (ETJ).

The western part of the Site is located over the Edwards Aquifer Contributing Zone (EACZ) and the eastern part of the Site is located over the Edwards Aquifer Recharge Zone (EARZ).

4.0 METHODOLOGY

As part of the GA, WESTWARD performed a desktop review of selected published information. WESTWARD also conducted a field investigation in accordance with *TCEQ-0585 (Rev. 10-01-04)*.

4.1 Desktop Review

WESTWARD conducted a review of aerial imagery, the University of Texas Bureau of Economic Geology (BEG) Geologic Atlas of Texas (GAT) Austin Sheet, applicable U.S. Geological Survey (USGS) Topographic quadrangle(s) and geospatial dataset(s), the Texas Natural Resources Information System (TNRIS), the Texas Water Development Board's Water Data Interactive Groundwater Data Viewer (TWDB Viewer), the Railroad Commission of Texas (RRC), and the U.S. Department of Agriculture (USDA) National Resource Conservation Service (NRCS) Web Soil Survey prior to the field investigation.

4.2 Field Investigation

A field investigation was performed at the Site by WESTWARD staff under the direction of John J. Sackrider, P.G. (TBPG Lic. No. 12654) on October 23 & 24, 2023. Field transects of the Site were walked in accordance with *TCEQ-0585 (rev. 10-01-04)*.

5.0 DESKTOP REVIEW

The desktop review was utilized for preliminary planning of the field investigation. The accuracy of the desktop review was limited by the accessibility, scale, and age of the data available.

5.1 Published Surface Geology

A review of published geologic maps revealed three (3) geologic units mapped at the Site. They include the Cretaceous-aged Keys Valley Marl (Kkv), the Comanche Peak Limestone (Kc), and the Edwards Limestone (Ked).

5.2 Published Structure

The Site is located within the Balcones Fault Zone (BFZ). The desktop review revealed that there are no faults going through the Site. However, there is one published fault that is mapped approximately 50 ft. outside of the western Site boundary trending southwest to northeast at approximately 18°. There is another fault trending southwest to northeast at approximately 46° less than a mile southeast of the Site. The fault that lies just outside of the boundary is the only fault visible within the mapped extents and is shown on the Site Geologic Map (Attachment D).

The average of these two neighboring faults was calculated to establish the dominant fault trend range at this Site, which for the purpose of this assessment, is approximated to be between 17° and 47°.

5.3 Karst Features

The desktop review did not reveal karst features within the Site.

5.4 Non-karst & Manmade Features

The desktop review of aerial imagery revealed two large ponds at the Site that are classified as non-karst closed depressions. A review of the TWDB Viewer did not reveal any onsite groundwater wells at the Site.

5.5 Soils

Six (6) soil units were identified on the Site through the NRCS Web Soil Survey. They are detailed below as well as included on the Geologic Assessment Form TCEQ-0585 (Rev. 02-11-15). A Site Soils Map is included in Attachment D.

Published Soil Unit Descriptions			
<i>Soil Name</i>	<i>Group</i>	<i>Thickness (Feet)</i>	<i>Description</i>
Brackett gravelly clay (BkE), 3 to 12 percent slopes	D	< 2	6 to 20 inches to paralithic bedrock, well drained, moderately low to high (0.06 to 1.98 in/hr) Ksat capacity
Denton silty clay (DnB), 1 to 3 percent slopes	D	< 5	22 to 60 inches to lithic bedrock, well drained, moderately low to moderately high (0.06 to 0.20 in/hr) Ksat capacity
Eckrant stony clay (EeB), 0 to 3 percent slopes	D	< 2	4 to 20 inches to lithic bedrock, well drained, moderately low to moderately high (0.06 to 0.57 in/hr) Ksat capacity
Eckrant-Rock outcrop association (ErE), 1 to 10 percent slopes	D	< 2	4 to 20 inches to lithic bedrock, well drained, moderately low to moderately high (0.06 to 0.57 in/hr) Ksat capacity
Fairlie clay (FaB), 1 to 2 percent slopes	D	< 5	40 to 60 inches to paralithic bedrock, moderately well drained, very low to moderately low (0.00 to 0.06 in/hr) Ksat capacity
Georgetown stony clay loam (GsB), 1 to 3 percent slopes	D	< 4	24 to 40 inches to lithic bedrock, well drained, very low to moderately low (0.00 to 0.06 in/hr) Ksat capacity

6.0 FIELD INVESTIGATION

The field investigation was performed on October 24 & 25, 2023 by WESTWARD staff under the direction of John J. Sackrider, P.G. to verify the presence or absence of recharge features identified in the desktop review and to identify recharge features not found during the desktop review. Field reconnaissance was performed in accordance with the *TCEQ-0585-Instructions (Rev. 10-1-04)*.

6.1 Surface Geology

The mapped geologic units, Kkv, Kc, Ked, were all observed at the Site in places where bedrock was exposed and by the presence of scattered rock at the surface. Observations at the Site indicate that the actual formation contacts varied slightly from the contacts shown on the published maps. Contact lines were redrawn based on outcrop points where a geologic unit was observed and followed using topography lines. An updated Site Geology Map based on the field observations made during this field investigation is included in Appendix D.

6.2 Structure

Evidence of faults was not observed during the field investigation.

6.3 Karst Features

Two (2) solution cavities were identified and recorded during the field investigation. Neither of these features are rated sensitive.

6.4 Non-karst & Manmade Features

Seven (7) non-karst closed depressions and three (3) manmade features in bedrock were identified and recorded during the field investigation. Two (2) of the three (3) manmade features in bedrock are wells. None of these features are rated sensitive.

6.5 Feature Descriptions

S-1 (CD)

Not Sensitive

Feature S-1 is a non-karst closed depression located along the entry road on the southwestern part of the Site. The feature measures approximately 55 ft. x 30 ft. x 1 ft. and the floor was heavily vegetated at the time of the field investigation. The catchment area of the feature is less than 1.6 acres, and the interpreted probability of rapid infiltration is low. This feature is rated not sensitive.

S-2 (CD)

Not Sensitive

Feature S-2 is a large non-karst closed depression on the southwestern part of the Site. The feature measures approximately 180 ft. x 135 ft. x 8 ft. and the floor consists of vegetated dark soil. Mud cracks were observed at the time of the field investigation. The catchment area of the feature is greater than 1.6 acres but due to the vegetated fine-grained soil floor, the interpreted probability of rapid infiltration is low. This feature is rated not sensitive.

S-3 (CD)

Not Sensitive

Feature S-3 is a non-karst closed depression near the southern Site boundary. The feature measures approximately 10 ft. x 20 ft. x 0.5 ft. and the floor consists of vegetated dark soil. The catchment area is less than 1.6 acres, and the interpreted probability of rapid infiltration is low. This feature is rated not sensitive.

S-4 (CD)

Not Sensitive

Feature S-4 is a non-karst closed depression located along the road and within the floodplain on the southwestern part of the Site. The feature measures approximately 30 ft. x 15 ft. x 1 ft. and the floor consist of vegetated dark soil. The catchment area is greater than 1.6 acres, but due to the vegetated fine-grained soil floor, the interpreted probability of rapid infiltration is low. This feature is rated not sensitive.

S-5 (CD)

Not Sensitive

Feature S-5 is a non-karst closed depression located in the terraced area on the western part of the Site. The feature measures approximately 60 ft. x 40 ft. x 2 ft. and is floored with dark soil and short growth vegetation. The catchment area is less than 1.6 acres, and the interpreted probability of rapid infiltration is low. This feature is rated not sensitive.

S-6 (CD)

Not Sensitive

Feature S-6 is a non-karst closed depression located on the northcentral part of the Site near the tree line separating the densely vegetated portion from the open field. The feature

measures approximately 60 ft. x 10 ft. x 2 ft. and is floored with vegetation and covered with tall trees. The feature was filled with trash at the time of the field investigation. The catchment area is less than 1.6 acres and the interpreted probability of rapid infiltration is low. This feature is rated not sensitive.

S-7 (MB-W)

Not Sensitive

Feature S-7 is a water well classified as a manmade feature in bedrock located near the main house in the central part of the Site. The well is inside a well house floored with a concrete slab. The casing is a minimum of 0.33 ft. in diameter and is suspected to be made of steel. This could not be confirmed at the time of the field investigation as it is covered by a steel plate that is flush with the concrete slab. The depth is unknown as there was no public information available pertaining to this well during the desktop review. The catchment area is less than 1.6 acres, and the interpreted probability of rapid infiltration is low. This feature is rated not sensitive.

S-8 (MB)

Not Sensitive

Feature S-8 is a cistern which is classified as a manmade feature in bedrock located next to the main house in the central part of the Site. The feature measures approximately 10 ft. wide in diameter with an unknown depth estimated to be at least 25 ft. It was holding water at the time of the field investigation. The feature is lined with concrete on the inside and the opening extends approximately 1.5 ft. above the ground surface with mortared stone sides and a wooden cap which serves as a cover for the opening of the feature. The catchment area is less than 1.6 acres, and the interpreted probability of rapid infiltration is low. This feature is rated not sensitive.

S-9 (SC)

Not Sensitive

Feature S-9 appears to be a solution cavity located on the southcentral part of the Site. It is possible that the bedrock observed consists of float rock, but the feature is included here to be conservative. The feature measures approximately 0.75 ft. x 0.5 ft. x 3 ft. and has an approximate trend of 10°. It was infilled with dark soil at the time of the field investigation. The catchment area is less than 1.6 acres, and the interpreted probability of rapid infiltration is low. This feature is rated not sensitive.

S-10 (SC)

Not Sensitive

Feature S-10 is a solution cavity located on the heavily vegetated central part of the Site. The feature measures approximately 0.5 ft. x 0.33 ft. x 3 ft. and has an approximate trend of 55°. It was infilled with dark soil and organic debris at the time of the field investigation. The catchment area for this feature is less than 1.6 acres and the interpreted probability of rapid infiltration is low. This feature is rated not sensitive.

S-11 (CD)

Not Sensitive


Feature S-11 is a large non-karst closed depression located on the western part of the Site near Rattlesnake Rd. The feature measures approximately 165 ft. x 150 ft. x 10 ft. The floor consists of dark soil which was moist at the time of the field investigation and appeared to have been holding water recently so although the catchment area for this feature is greater than 1.6 acres, the interpreted probability of rapid infiltration is low. The feature is rated not sensitive.

S-12 (MB-W)

Not Sensitive

Feature S-12 is a water well classified as a manmade feature in bedrock. It is located next to S-7 inside the well house. The casing is estimated to measure approximately 0.33 ft. in diameter and is made of steel. The depth is unknown as there was no public information available pertaining to this well during the desktop review. This well appeared to not be in use as the pipe extending from it was not connected to anything. It is likely that S-7 is a replacement well for S-12. The catchment area is less than 1.6 acres, and the interpreted probability of rapid infiltration is low. This feature is rated not sensitive.

SELECT PHOTOGRAPHS



S-2: Closed depression on the southwestern part of the Site.



S-5: Closed depression in the terraced field on the western part of the Site.



S-6: Closed depression filled with trash on the northcentral part of the Site.



Well house containing features S-7 and S-12.



Groundwater wells S-7 (left) and S-12 (right).



S

S-8: Cistern located by the main house on the central part of the Site.



S-8: Note the water line inside the cistern.



S-9: Solution cavity located on the southcentral part of the Site.



S-10: Solution cavity located on the heavily vegetated central part of the Site.



S-11: Closed depression located on the western part of the Site by Rattlesnake Rd.

Attachment D

Site Geologic Map **Site Soils Map**





IMAGE: ESRI WORLD IMAGERY	
ISSUE DATE:	12/7/2023
DRAWN BY:	CPT
CHECKED BY:	JJS
SCALE: 1" =	200'
JOB NO.:	11260-005











SHEET NO.:	
01	
OF 02	

**WESTWARD**
Environmental Engineering, Natural Resources,
P.O. Box 2205, Boerne, Texas 78006
(830) 249-8284 Fax: (830) 249-0221
TBPE REG. NO.: F-4524
TBPG REG. NO.: 50112

REV	DESCRIPTION	BY	DATE


12/15/2023

SITE GEOLOGIC MAP
RATTLESNAKE RANCH QUARRY
RANGER EXCAVATING, LP
FLORENCE, WILLIAMSON COUNTY, TX 76527

LEGEND
 Approximate Property Boundary
 GA Features
 Edwards Aquifer Recharge Zone
 FEMA Floodplain (NFHL*)
Published & Observed Geology
 Ked - Edwards Limestone
 Kc - Comanche Peak
 Kkv - Keys Valley Marl
 Published Fault







IMAGE: ESRI WORLD IMAGERY	
ISSUE DATE:	11/21/2023
DRAWN BY:	CPT
CHECKED BY:	JS
SCALE: 1" =	200'
JOB NO.:	11260-005

SHEET NO.:	
02	
OF 02	


**WESTWARD**
Environmental Engineering, Natural Resources,
P.O. Box 2205, Boerne, Texas 78006
(830) 249-8284 Fax: (830) 249-0221
TBPB REG. NO.: F-4524
TBPB REG. NO.: 50112


REV	DESCRIPTION	BY	DATE




SITE SOILS MAP
RATTLESNAKE RANCH QUARRY
RANGER EXCAVATING, LP
FLORENCE, WILLIAMSON COUNTY, TX 78132


LEGEND


 Approximate Property Boundary


 GA Features


Published Soil Units


 Brackett Gravelly Clay (BkE)



 Denton Silty Clay (DnB)

 Eckrant Stony Clay (EeB)

 Eckrant-Rock Outcrop Association (ErE)

 Fairlie Clay (FaB)

 Georgetown Stony Clay Loam (GsB)

Water Pollution Abatement Plan Application

Texas Commission on Environmental Quality

for Regulated Activities on the Edwards Aquifer Recharge Zone and Relating to 30 TAC §213.5(b), Effective June 1, 1999

To ensure that the application is administratively complete, confirm that all fields in the form are complete, verify that all requested information is provided, consistently reference the same site and contact person in all forms in the application, and ensure forms are signed by the appropriate party.

Note: Including all the information requested in the form and attachments contributes to more streamlined technical reviews.

Section 1.01 Signature

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. This **Water Pollution Abatement Plan Application Form** is hereby submitted for TCEQ review and Executive Director approval. The form was prepared by:

Print Name of Customer/Agent: Nicolas E. Mercado

Texas License No. 144228 | Firm No. 4524

Date: 12/19/2023

Signature of Customer/Agent:



Regulated Entity Name: Rattlesnake Ranch Quarry

Section 1.02 Regulated Entity Information

1. The type of project is:

- ☐ Residential: Number of Lots: _____
- ☐ Residential: Number of Living Unit Equivalents: _____
- ☐ Commercial
- ☒ Industrial
- ☐ Other: _____

2. Total site acreage (size of property): 163 Acres

3. Estimated projected population: 20

4. The amount and type of impervious cover expected after construction are shown below:

Article II. Table 1 - Impervious Cover Table

Impervious Cover of Proposed Project	Sq. Ft.	Sq. Ft./Acre	Acres
Structures/Rooftops		÷ 43,560 =	
Parking		÷ 43,560 =	
Other paved surfaces	141,065	÷ 43,560 =	3.24
Total Impervious Cover	141,065	÷ 43,560 =	3.24

Total Impervious Cover 3.24 ÷ Total Acreage 163.0 X 100 = 19.9% Impervious Cover

5. ☒ **Attachment A - Factors Affecting Surface Water Quality.** A detailed description of all factors that could affect surface water and groundwater quality that addresses ultimate land use is attached.
6. ☒ Only inert materials as defined by 30 TAC §330.2 will be used as fill material.

Section 2.01 For Road Projects Only

(a) Complete questions 7 - 12 if this application is exclusively for a road project.

7. Type of project:

- ☐ TXDOT road project.
☐ County road or roads built to county specifications.
☐ City thoroughfare or roads to be dedicated to a municipality.
☐ Street or road providing access to private driveways.

8. Type of pavement or road surface to be used:

- ☐ Concrete
☐ Asphaltic concrete pavement
☐ Other: _____

9. Length of Right of Way (R.O.W.): _____ feet.

Width of R.O.W.: _____ feet.

L x W = _____ Ft² ÷ 43,560 Ft²/Acre = _____ acres.

10. Length of pavement area: _____ feet.

Width of pavement area: _____ feet.

L x W = _____ Ft² ÷ 43,560 Ft²/Acre = _____ acres.

Pavement area _____ acres ÷ R.O.W. area _____ acres x 100 = _____% impervious cover.

11. ☐ A rest stop will be included in this project.

- ☐ A rest stop will not be included in this project.
12. ☐ Maintenance and repair of existing roadways that do not require approval from the TCEQ Executive Director. Modifications to existing roadways such as widening roads/adding shoulders totaling more than one-half (1/2) the width of one (1) existing lane require prior approval from the TCEQ.

Section 2.02 Stormwater to be generated by the Proposed Project

13. ☒ **Attachment B - Volume and Character of Stormwater.** A detailed description of the volume (quantity) and character (quality) of the stormwater runoff which is expected to occur from the proposed project is attached. The estimates of stormwater runoff quality and quantity are based on the area and type of impervious cover. Include the runoff coefficient of the site for both pre-construction and post-construction conditions.

Section 2.03 Wastewater to be generated by the Proposed Project

14. The character and volume of wastewater is shown below:

<u>100</u> % Domestic	<u>46</u> Gallons/day
<u> </u> % Industrial	<u> </u> Gallons/day
<u> </u> % Commingled	<u> </u> Gallons/day

TOTAL gallons/day 46 Gallons/day

15. Wastewater will be disposed of by:

☒ On-Site Sewage Facility (OSSF/Septic Tank):

☐ **Attachment C - Suitability Letter from Authorized Agent.** An on-site sewage facility will be used to treat and dispose of the wastewater from this site. The appropriate licensing authority's (authorized agent) written approval is attached. It states that the land is suitable for the use of private sewage facilities and will meet or exceed the requirements for on-site sewage facilities as specified under 30 TAC Chapter 285 relating to On-site Sewage Facilities.

☒ Each lot in this project/development is at least one (1) acre (43,560 square feet) in size. The system will be designed by a licensed professional engineer or registered sanitarian and installed by a licensed installer in compliance with 30 TAC Chapter 285.

☐ Sewage Collection System (Sewer Lines):

☐ Private service laterals from the wastewater generating facilities will be connected to an existing SCS.

☐ Private service laterals from the wastewater generating facilities will be connected to a proposed SCS.

☐ The SCS was previously submitted on ____.

- ☐ The SCS was submitted with this application.
- ☐ The SCS will be submitted at a later date. The owner is aware that the SCS may not be installed prior to Executive Director approval.
- ☐ The sewage collection system will convey the wastewater to the _____ (name) Treatment Plant. The treatment facility is:
- ☐ Existing.
- ☐ Proposed.
16. ☐ All private service laterals will be inspected as required in 30 TAC §213.5.

Section 2.04 Site Plan Requirements

(a) Items 17 – 28 must be included on the Site Plan.

17. ☒ The Site Plan must have a minimum scale of 1" = 400'.
- Site Plan Scale: 1" = 200'.
18. 100-year floodplain boundaries:
- ☒ Some part(s) of the project site is located within the 100-year floodplain. The floodplain is shown and labeled.
- ☐ No part of the project site is located within the 100-year floodplain.
- The 100-year floodplain boundaries are based on the following specific (including date of material) sources(s): FEMA FIRM PANELS 48491C0100E eff. 9/26/2008 & 48491C0125F eff. 12/20/2019
19. ☒ The layout of the development is shown with existing and finished contours at appropriate, but not greater than ten-foot contour intervals. Lots, recreation centers, buildings, roads, open space, etc. are shown on the plan.
- ☐ The layout of the development is shown with existing contours at appropriate, but not greater than ten-foot intervals. Finished topographic contours will not differ from the existing topographic configuration and are not shown. Lots, recreation centers, buildings, roads, open space, etc. are shown on the site plan.
20. All known wells (oil, water, unplugged, capped and/or abandoned, test holes, etc.):
- ☒ There are 2 (#) wells present on the project site and the locations are shown and labeled. (Check all of the following that apply)
- ☐ The wells are not in use and have been properly abandoned.
- ☒ The wells are not in use and will be properly abandoned.
- ☒ The wells are in use and comply with 16 TAC §76.
- ☐ There are no wells or test holes of any kind known to exist on the project site.
21. Geologic or manmade features which are on the site:
- ☐ All sensitive geologic or manmade features identified in the Geologic Assessment are shown and labeled.

- ☒ No sensitive geologic or manmade features were identified in the Geologic Assessment.
- ☐ **Attachment D - Exception to the Required Geologic Assessment.** A request and justification for an exception to a portion of the Geologic Assessment is attached.
22. ☒ The drainage patterns and approximate slopes anticipated after major grading activities.
23. ☒ Areas of soil disturbance and areas which will not be disturbed.
24. ☒ Locations of major structural and nonstructural controls. These are the temporary and permanent best management practices.
25. ☒ Locations where soil stabilization practices are expected to occur.
26. ☒ Surface waters (including wetlands).
- ☐ N/A
27. ☒ Locations where stormwater discharges to surface water or sensitive features are to occur.
- ☐ There will be no discharges to surface water or sensitive features.
28. ☒ Legal boundaries of the site are shown.

Section 2.05 Administrative Information

29. ☒ Submit one (1) original and one (1) copy of the application, plus additional copies as needed for each affected incorporated city, groundwater conservation district, and county in which the project will be located. The TCEQ will distribute the additional copies to these jurisdictions. The copies must be submitted to the appropriate regional office.
30. ☒ Any modification of this WPAP will require Executive Director approval, prior to construction, and may require submission of a revised application, with appropriate fees.

**Ranger Excavating, LP
Rattlesnake Ranch Quarry
WPAP Form (TCEQ-0584)
Attachment A**

Factors Affecting Water Quality

The major factor that could potentially affect water quality is sediment in stormwater runoff after the clearing of vegetation. Other factors include fuels and lubricants from vehicles and equipment and trash/debris items.

Compacted earthen berms located downgradient of the disturbed area(s) are proposed to capture sediment and control the flow of stormwater. Upgradient berms prevent run-on to disturbed areas of the site. Any spills or leaks will be cleaned up immediately and will be disposed of properly. A trash receptacle will be placed on-site for use by employees and visitors.

**WPAP Form (TCEQ-0584)
Attachment B**

Volume and Character of Stormwater

The area of the site, as shown on the Proposed Conditions WPAP Site Plan, is approximately 163-acres.



The stormwater from this disturbed area will carry an increased level of total suspended solids (TSS); however, stormwater from this area will be retained in the pit.

Temporary BMPs (rock/earthen berms, vegetative filter strips, silt fence, etc.) will be used to control stormwater until Final Earthen Berms are complete.

Due to the use of Temporary BMPs during construction, the character of stormwater runoff which is expected to occur from the proposed project will be essentially the same as prior to the site. As quarrying activities continue, the volume of stormwater runoff from the site will be reduced because the quarry pit will ultimately retain the anticipated on-site and upgradient stormwater runoff. The runoff coefficient for the impervious areas is 0.9 and the runoff coefficient for predevelopment is 0.03 per TCEQ guidance.

**WPAP Form (TCEQ-0584)
Attachment C**

There is an existing OSSF on-site associated with the existing residence. Records relating to land suitability for this system were unavailable from Williamson County. No new OSSF is proposed.



- LEGEND**
- PROPERTY LINE
 - - - EXISTING CONTOUR
 - - - PROPOSED CONTOUR
 - - - LINEAR WATER BODIES
 - - - FLOW ARROW
 - - - 100-YR FLOODPLAIN
 - ASPHALT AREA
 - BASE AREA
 - WATER BODY AREA
 - GRASS/VEGETATED BUFFER AREA

EXISTING CONTOURS NOTE:
A TOPOGRAPHIC SURVEY WAS PROVIDED TO BY A THIRD PARTY ON DECEMBER 5, 2023 AND IS USED FOR THE NATURAL EXISTING CONTOURS OF THIS DRAWING. THE SIGNING ENGINEER OF THIS DRAWING BEARS NO RESPONSIBILITY OF THE PROVIDED SURVEY. CONTRACTOR MUST VERIFY EXISTING GRADES IN THE FIELD PRIOR TO COMMENCING GRADE WORK.

IMAGE:	N/A
ISSUE DATE:	12/19/2023
DRAWN BY:	NEM
CHECKED BY:	VH
SCALE:	1" = 200'
JOB NO.:	11260-005

SHEET NO.:	C2
OF C3	

WESTWARD
Environmental Engineering, Natural Resources,
P.O. Box 2205 Boerne, Texas 78006
(830) 249-8284 Fax: (830) 249-0221
TBPB REG. NO.: F-4524
TBPB REG. NO.: 50112

REV.	DESCRIPTION	BY	DATE



INTERIM CONDITIONS
RATTLESNAKE RANCH QUARRY
RANGER EXCAVATING, LP
8880 OLD 195, FLORENCE, TX 76527

Temporary Stormwater Section

Texas Commission on Environmental Quality

for Regulated Activities on the Edwards Aquifer Recharge Zone and Relating to 30 TAC §213.5(b)(4)(A), (B), (D)(I) and (G); Effective June 1, 1999

To ensure that the application is administratively complete, confirm that all fields in the form are complete, verify that all requested information is provided, consistently reference the same site and contact person in all forms in the application, and ensure forms are signed by the appropriate party.

Note: Including all the information requested in the form and attachments contributes to more streamlined technical reviews.

Section 1.01 Signature


To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. This **Temporary Stormwater Section** is hereby submitted for TCEQ review and executive director approval. The application was prepared by:

Print Name of Customer/Agent: Nicolas E. Mercado

Texas License No. 144228 | Firm No. 4524

Date: 12/19/2023

Signature of Customer/Agent:



Regulated Entity Name: Rattlesnake Ranch Quarry

Section 1.02 Project Information

Section 1.03 Potential Sources of Contamination

Examples: Fuel storage and use, chemical storage and use, use of asphaltic products, construction vehicles tracking onto public roads, and existing solid waste.

1. Fuels for construction equipment and hazardous substances which will be used during construction:

☒ The following fuels and/or hazardous substances will be stored on the site: On & Off-road Diesel

These fuels and/or hazardous substances will be stored in:

- ☐ Aboveground storage tanks with a cumulative storage capacity of less than 250 gallons will be stored on the site for less than one (1) year.

- ☐ Aboveground storage tanks with a cumulative storage capacity between 250 gallons and 499 gallons will be stored on the site for less than one (1) year.
- ☒ Aboveground storage tanks with a cumulative storage capacity of 500 gallons or more will be stored on the site. An Aboveground Storage Tank Facility Plan application must be submitted to the appropriate regional office of the TCEQ prior to moving the tanks onto the project.
- ☐ Fuels and hazardous substances will not be stored on the site.
- 2. ☒ **Attachment A - Spill Response Actions.** A site specific description of the measures to be taken to contain any spill of hydrocarbons or hazardous substances is attached.
- 3. ☒ Temporary aboveground storage tank systems of 250 gallons or more cumulative storage capacity must be located a minimum horizontal distance of 150 feet from any domestic, industrial, irrigation, or public water supply well, or other sensitive feature.
- 4. ☒ **Attachment B - Potential Sources of Contamination.** A description of any activities or processes which may be a potential source of contamination affecting surface water quality is attached.

Section 1.04 Sequence of Construction

- 5. ☒ **Attachment C - Sequence of Major Activities.** A description of the sequence of major activities which will disturb soils for major portions of the site (grubbing, excavation, grading, utilities, and infrastructure installation) is attached.
 - ☒ For each activity described, an estimate (in acres) of the total area of the site to be disturbed by each activity is given.
 - ☒ For each activity described, include a description of appropriate temporary control measures and the general timing (or sequence) during the construction process that the measures will be implemented.
- 6. ☒ Name the receiving water(s) at or near the site which will be disturbed or which will receive discharges from disturbed areas of the project: Unnamed Tributary of Berry Creek

Section 1.05 Temporary Best Management Practices (TBMPs)

Erosion control examples: tree protection, interceptor swales, level spreaders, outlet stabilization, blankets or matting, mulch, and sod. Sediment control examples: stabilized construction exit, silt fence, filter dikes, rock berms, buffer strips, sediment traps, and sediment basins. Please refer to the Technical Guidance Manual for guidelines and specifications. All structural BMPs must be shown on the site plan.

- 7. ☒ **Attachment D – Temporary Best Management Practices and Measures.** TBMPs and measures will prevent pollution of surface water, groundwater, and stormwater. The construction-phase BMPs for erosion and sediment controls have been designed to retain sediment on site to the extent practicable. The following information is attached:

- ☒ A description of how BMPs and measures will prevent pollution of surface water, groundwater or stormwater that originates upgradient from the site and flows across the site.
 - ☒ A description of how BMPs and measures will prevent pollution of surface water or groundwater that originates on-site or flows off site, including pollution caused by contaminated stormwater runoff from the site.
 - ☒ A description of how BMPs and measures will prevent pollutants from entering surface streams, sensitive features, or the aquifer.
 - ☒ A description of how, to the maximum extent practicable, BMPs and measures will maintain flow to naturally-occurring sensitive features identified in either the geologic assessment, TCEQ inspections, or during excavation, blasting, or construction.
8. ☒ The temporary sealing of a naturally-occurring sensitive feature which accepts recharge to the Edwards Aquifer as a temporary pollution abatement measure during active construction should be avoided.
- ☐ **Attachment E - Request to Temporarily Seal a Feature.** A request to temporarily seal a feature is attached. The request includes justification as to why no reasonable and practicable alternative exists for each feature.
- ☒ There will be no temporary sealing of naturally-occurring sensitive features on the site.
9. ☒ **Attachment F - Structural Practices.** A description of the structural practices that will be used to divert flows away from exposed soils, to store flows, or to otherwise limit runoff discharge of pollutants from exposed areas of the site is attached. Placement of structural practices in floodplains has been avoided.
10. ☒ **Attachment G - Drainage Area Map.** A drainage area map supporting the following requirements is attached:
- ☐ For areas that will have more than 10 acres within a common drainage area disturbed at one time, a sediment basin will be provided.
 - ☐ For areas that will have more than 10 acres within a common drainage area disturbed at one time, a smaller sediment basin and/or sediment trap(s) will be used.
 - ☐ For areas that will have more than 10 acres within a common drainage area disturbed at one time, a sediment basin or other equivalent controls are not attainable, but other TBMPs and measures will be used in combination to protect down slope and side slope boundaries of the construction area.
 - ☐ There are no areas greater than 10 acres within a common drainage area that will be disturbed at one time. A smaller sediment basin and/or sediment trap(s) will be used in combination with other erosion and sediment controls within each disturbed drainage area.

- ☒ There are no areas greater than 10 acres within a common drainage area that will be disturbed at one time. Erosion and sediment controls other than sediment basins or sediment traps within each disturbed drainage area will be used.
11. ☐ **Attachment H - Temporary Sediment Pond(s) Plans and Calculations.** Temporary sediment pond or basin construction plans and design calculations for a proposed temporary BMP or measure have been prepared by or under the direct supervision of a Texas Licensed Professional Engineer. All construction plans and design information must be signed, sealed, and dated by the Texas Licensed Professional Engineer. Construction plans for the proposed temporary BMPs and measures are attached.
- ☒ N/A
12. ☒ **Attachment I - Inspection and Maintenance for BMPs.** A plan for the inspection of each temporary BMP(s) and measure(s) and for their timely maintenance, repairs, and, if necessary, retrofit is attached. A description of the documentation procedures, recordkeeping practices, and inspection frequency are included in the plan and are specific to the site and/or BMP.
13. ☒ All control measures must be properly selected, installed, and maintained in accordance with the manufacturer's specifications and good engineering practices. If periodic inspections by the applicant or the executive director, or other information indicate a control has been used inappropriately, or incorrectly, the applicant must replace or modify the control for site situations.
14. ☒ If sediment escapes the construction site, off-site accumulations of sediment must be removed at a frequency sufficient to minimize offsite impacts to water quality (e.g., fugitive sediment in street being washed into surface streams or sensitive features by the next rain).
15. ☒ Sediment must be removed from sediment traps or sedimentation ponds not later than when design capacity has been reduced by 50%. A permanent stake will be provided that can indicate when the sediment occupies 50% of the basin volume.
16. ☒ Litter, construction debris, and construction chemicals exposed to stormwater shall be prevented from becoming a pollutant source for stormwater discharges (e.g., screening outfalls, picked up daily).

Section 1.06 Soil Stabilization Practices

Examples: establishment of temporary vegetation, establishment of permanent vegetation, mulching, geotextiles, sod stabilization, vegetative buffer strips, protection of trees, or preservation of mature vegetation.

17. ☒ **Attachment J - Schedule of Interim and Permanent Soil Stabilization Practices.** A schedule of the interim and permanent soil stabilization practices for the site is attached.

18. ☒ Records must be kept at the site of the dates when major grading activities occur, the dates when construction activities temporarily or permanently cease on a portion of the site, and the dates when stabilization measures are initiated.
19. ☒ Stabilization practices must be initiated as soon as practicable where construction activities have temporarily or permanently ceased.

Section 1.07 Administrative Information

20. ☒ All structural controls will be inspected and maintained according to the submitted and approved operation and maintenance plan for the project.
21. ☒ If any geologic or manmade features, such as caves, faults, sinkholes, etc., are discovered, all regulated activities near the feature will be immediately suspended. The appropriate TCEQ Regional Office shall be immediately notified. Regulated activities must cease and not continue until the TCEQ has reviewed and approved the methods proposed to protect the aquifer from any adverse impacts.
22. ☒ Silt fences, diversion berms, and other temporary erosion and sediment controls will be constructed and maintained as appropriate to prevent pollutants from entering sensitive features discovered during construction.

Ranger Excavating, LP
Rattlesnake Ranch Quarry
Temporary Stormwater Section (TCEQ-0602)
Attachment A

Spill Response Actions

Education

- (1) Be aware that different materials pollute in different amounts. Make sure that each employee knows what a “significant spill” is for each material they use, and what is the appropriate response for “significant” and “insignificant” spills. Employees should also be aware of when spill must be reported to the TCEQ.
- (2) Educate employees and subcontractors on potential dangers to humans and the environment from spills and leaks.
- (3) Hold regular meetings to discuss and reinforce appropriate disposal procedures (incorporate into regular safety meetings).
- (4) Establish a continuing education program to indoctrinate new employees.
- (5) Have contractor’s superintendent or representative oversee and enforce proper spill prevention and control measures.

General Measures

- (1) To the extent that the work can be accomplished safely, spills of oil, petroleum products, substances listed under 40 CFR parts 110,117, and 302, and sanitary and septic wastes should be contained and cleaned up immediately.
- (2) Store hazardous materials and wastes in covered containers and protect from vandalism.
- (3) Place a stockpile of spill cleanup materials where it will be readily accessible.
- (4) Train employees in spill prevention and cleanup.
- (5) Designate responsible individuals to oversee and enforce control measures.
- (6) Spills should be covered and protected from stormwater run on during rainfall to the extent that it doesn’t compromise cleanup activities.
- (7) Do not bury or wash spills with water.

Ranger Excavating, LP Rattlesnake Ranch Quarry

(8) Store and dispose of used clean up materials, contaminated materials, and recovered spill material that is no longer suitable for the intended purpose in conformance with the provisions in applicable BMPs.

(9) Do not allow water used for cleaning and decontamination to enter storm drains or watercourses. Collect and dispose of contaminated water in accordance with applicable regulations.

(10) Contain water overflow or minor water spillage and do not allow it to discharge into drainage facilities or watercourses.

(11) Place Safety Data Sheets (SDS), as well as proper storage, cleanup, and spill reporting instructions for hazardous materials stored or used on the project site in an open, conspicuous, and accessible location.

(12) Keep waste storage areas clean, well-organized, and equipped with ample cleanup supplies as appropriate for the materials being stored. Perimeter controls, containment structures, covers, and liners should be repaired or replaced as needed to maintain proper function.

Cleanup

(1) Clean up leaks and spills immediately.

(2) Use a rag for small spills on paved surfaces, a damp mop for general cleanup, and absorbent material for larger spills. If the spilled material is hazardous, then the used cleanup materials are also hazardous and must be disposed of as hazardous waste.

(3) Never hose down or bury dry material spills. Clean up as much of the material as possible and dispose of properly. See the waste management BMPs in this section for specific information.

(4) Never hose down or bury dry material spills. Clean up as much of the material as possible and dispose of properly. See the waste management BMPs in this section for specific information.

Minor Spills

(1) Minor spills typically involve small quantities of oil, gasoline, paint, etc. which can be controlled by the first responder at the discovery of the spill.

(2) Use absorbent materials on small spills rather than hosing down or burying the spill.

(3) Absorbent materials should be promptly removed and disposed of properly.

(4) Follow the practice below for a minor spill:

**Ranger Excavating, LP
Rattlesnake Ranch Quarry**

- (5) Contain the spread of the spill.
- (6) Recover spilled materials.
- (7) Clean the contaminated area and properly dispose of contaminated materials.

Semi-Significant Spills

Semi-significant spills still can be controlled by the first responder along with the aid of other personnel such as laborers and the foreman, etc. This response may require the cessation of all other activities.

Spills should be cleaned up immediately:

- (1) Contain spread of the spill.
- (2) Notify the project foreman as soon as possible.
- (3) If the spill occurs on paved or impermeable surfaces, clean up using "dry" methods (absorbent materials, cat litter and/or rags). Contain the spill by encircling with absorbent materials and do not let the spill spread widely.
- (4) If the spill occurs in dirt areas, as soon as possible contain the spill by constructing an earthen dike. Dig up and properly dispose of contaminated soil.
- (5) If the spill occurs during rain, cover spill with tarps or other material to prevent contaminating runoff.

Significant/Hazardous Spills

For significant or hazardous spills that are in reportable quantities:

- (1) Notify the TCEQ by telephone as soon as possible and within 24 hours at 512-339-2929 (Austin) or 210-490-3096 (San Antonio) between 8 AM and 5 PM. After hours, contact the Environmental Release Hotline at 1-800-832-8224. It is the contractor's responsibility to have all emergency phone numbers at the construction site.
- (2) For spills of federal reportable quantities, in conformance with the requirements in 40 CFR parts 110, 119, and 302, the contractor should notify the National Response Center at (800) 424-8802.
- (3) Notification should first be made by telephone and followed up with a written report.

**Ranger Excavating, LP
Rattlesnake Ranch Quarry**

(4) The services of a spills contractor or a Haz-Mat team should be obtained as soon as possible. Construction personnel should not attempt to clean up until the appropriate and qualified staffs have arrived at the job site.

(5) Other agencies which may need to be consulted include, but are not limited to, the City Police Department, County Sheriff Office, Fire Departments, etc.

In the event of a reportable spill, the following Emergency Response Agencies can be contacted for assistance. Always inform your supervisor of a reportable spill as soon as possible. Follow company policy when responding to an emergency.

State Emergency Response Commission	(512) 463-7727
National Response Center	(800) 424-8802
US EPA Region 6, Dallas, 24-hr Number	(866) 372-7745
National Weather Service	(281) 337-5074
TCEQ 24-hr	(800) 832-8224
TCEQ Region 11	(512) 339-2929

Vehicle and Equipment Maintenance

(1) If maintenance must occur on-site, use a designated area and a secondary containment, located away from drainage courses, to prevent the run-on of stormwater and the runoff of spills.

(2) Regularly inspect on-site vehicles and equipment for leaks and repair in a timely manner.

(3) Check incoming vehicles and equipment (including delivery trucks, and employee and subcontractor vehicles) for leaking oil and fluids. Do not allow leaking vehicles or equipment on-site.

(4) Always use secondary containment, such as a drain pan or drop cloth, to catch spills or leaks when removing or changing fluids.

(5) Place drip pans or absorbent materials under paving equipment when not in use.

(6) Use absorbent materials on small spills rather than hosing down or burying the spill. Remove the absorbent materials promptly and dispose of properly.

(7) Promptly transfer used fluids to the proper waste or recycling drums. Don't leave full drip pans or other open containers lying around.

(8) Oil filters disposed of in trashcans or dumpsters can leak oil and pollute stormwater. Place the oil filter in a funnel over a waste oil-recycling drum to drain excess oil before disposal. Oil filters can also be recycled. Ask the oil supplier or recycler about recycling oil filters.

**Ranger Excavating, LP
Rattlesnake Ranch Quarry**

(9) Store cracked batteries in a non-leaking secondary container. Do this with all cracked batteries even if you think all the acid has drained out. If you drop a battery, treat it as if it is cracked. Put it into the containment area until you are sure it is not leaking.

Vehicle and Equipment Fueling

(1) If fueling must occur on site, use designated areas, located away from drainage courses, to prevent the run-on of stormwater and the runoff of spills.

(2) Discourage “topping off” of fuel tanks.

(3) Always use secondary containment, such as a drain pan, when fueling to catch spills/ leaks.

(4) Equipment fueling will take place on a compacted base pad. Any base material that becomes contaminated with hydrocarbons will be removed from the site and disposed of properly. Fuel will be brought to the equipment by a fueling truck filling up on an aboveground storage tank concrete containment located in the southern portion of the property.

**Ranger Excavating, LP
Rattlesnake Ranch Quarry**

DETAILED TELEPHONE SPILL REPORT FORM

Date of Incident: _____

Location of Incident: _____

Description of material spilled: _____

Quantity of material spilled: _____

Cause of spill: _____

Authorities notified: _____

Remediation/clean-up action: _____

Corrective measures taken for prevention of reoccurrence: _____

Signature: _____

Notes: _____

Emergency Number for the National Response Center 1-800-424-8802

**Ranger Excavating, LP
Rattlesnake Ranch Quarry**

Portable Toilet BMPs:

Portable toilets and/or sewage pump-out tanks will be used on-site and will be handled in accordance with the following guidelines:

- A licensed waste collector should service all the toilets/tanks. **The following tasks will be performed by the portable toilet supplier:**
 - Empty portable toilets/tanks before transporting them.
 - Securely fasten the toilets/tanks to the transport truck.
 - Use hand trucks, dollies, and power tailgates whenever possible.
 - Suppliers should carry bleach for disinfection in the event of a spill or leak.
 - Inspect the toilets frequently for leaks and have the units serviced and sanitized at time intervals that will maintain sanitary conditions of each toilet.
 - Pump-out tanks should be checked periodically for leaks. (Methods may include, but are not limited to: visual inspection, water level monitoring, pump-out volume comparisons, etc.)
- Locate portable toilets at least 20 feet from the nearest storm-drain inlet or sensitive-feature buffer area
- A berm will be constructed around all portable toilet facilities.
- Prepare a level ground surface with clear access to the toilets.
- Secure all portable toilets to prevent tipping by accident, weather, or vandalism.

Sewage pump-out tanks may be associated with modular or trailer-style buildings (i.e. – plant office, scale house, etc.). These tanks operate with the same nature and character as the portable toilets: they temporarily hold sewage from modular building restrooms and will be serviced by the same contractor, in the same way, as portable toilets. These tanks may be partially or fully buried but are still considered temporary/portable as they are intended to be repositioned on site over time to meet operational needs, and therefore do not constitute an OSSF or holding tank as defined by 30 TAC 285, nor any other type of organized sewage collection system.

**Temporary Stormwater Section (TCEQ-0602)
Attachment B**

Potential Sources of Contamination

Potential sources of contamination in the project area are the soil, fuels and lubricants from vehicles and equipment, and trash/debris items.

**Temporary Stormwater Section (TCEQ-0602)
Attachment C**

Sequence of Major Activities

Perimeter earthen berms will be established as shown on the Interim Conditions site plan. Clearing and grubbing will continue for the mining progression in 10-acre or less area increments. The cleared topsoil may be used to construct earthen berms surrounding the cleared area. Berms must be constructed to the height of the highest machine's axle height which will be approximately 2-4 feet high. The earthen berms surrounding the quarry will expand as the quarry expands to the Final Earthen Berm.

**Ranger Excavating, LP
Rattlesnake Ranch Quarry**

Once mining has commenced for the initial pit, Ranger proposes to construct a new entry road near the Northwestern corner of the property off Old 195. This proposed road will connect from Old 195 and transect East to the proposed office building, maintenance shop, and truck scale as shown in the Final Conditions plan sheet.

**Temporary Stormwater Section (TCEQ-0602)
Attachment D**

Temporary Best Management Practices (TBMPs)

7.a. TBMPs and measures will prevent pollution of surface water, groundwater and stormwater that originates upgradient from the site and flows across the site.

As the incremental quarry area is cleared and topsoil is removed, earthen berms will be constructed. Upgradient berms will direct stormwater runoff around disturbed areas of the site.

As the size of the quarry expands, the earthen berms will expand throughout the life of the project, up to the buffer zones to provide additional controls as mining progresses. Temporary natural existing vegetation will be maintained in a 25-foot buffer along the FEMA 100-year floodplain of the tributaries from Berry Creek. This buffer will be maintained until and unless appropriate permits can be obtained from Williamson County, FEMA and/or USACE to allow construction in the area. In addition, a natural vegetated buffer with a minimum width of 50 feet will be maintained between the Final Earthen Berm and the property line. This natural vegetated buffer will serve as a final buffer for stormwater runoff leaving the active portion of the site.

7.b. TBMPs and measures will prevent pollution of surface water, groundwater and stormwater that originates on-site or flows off site, including pollution caused by contaminated stormwater runoff from the site.

As the incremental quarry area is cleared and topsoil is removed, earthen berms will be constructed. Upgradient berms will direct stormwater runoff around disturbed areas of the site.

Natural existing vegetation will be maintained in a 25-foot buffer along the FEMA 100-year floodplain of the tributary from Berry Creek. This buffer will be maintained until and unless appropriate permits can be obtained from Williamson County, FEMA and/or USACE to allow construction in the area. In addition, a natural vegetated buffer with a minimum width of 50 feet will be maintained between the Final Earthen Berm and the property line. This natural vegetated buffer will serve as a final buffer for stormwater runoff leaving the active portion of the site.

7.c. TBMPs and measures will prevent pollution of surface streams, sensitive features, and the aquifer.

As the size of the quarry expands, the earthen berms will expand throughout the life of the project. Earthen berms and vegetated areas will be constructed/maintained as shown on the attached Interim and Final Conditions plan sheets to prevent pollutants from entering surface streams, sensitive features and the aquifer.

**Ranger Excavating, LP
Rattlesnake Ranch Quarry**

Temporary natural existing vegetation will be maintained in a 25-foot buffer on both sides from the centerline of the unnamed tributary of Berry Creek. This buffer will be maintained until construction begins in the area. In addition, a natural vegetated buffer with a minimum width of 50-feet will be maintained between the Final Earthen Berm and the property line. This natural vegetated buffer will serve as a final buffer for stormwater runoff leaving the active portion of the site. No sensitive features were identified on-site.

7.d. To the maximum extent practicable TBMPs and measures will maintain flow to naturally occurring sensitive features identified in the geologic assessment, TCEQ inspections, or during excavation, blasting, or construction.

A geologic assessment has been completed for the proposed ~163-acre site and is included with this application. None of the karst features on site were identified as sensitive. All identified features will eventually be removed through mining.

Ranger Excavating, LP will provide initial feature recognition training to mining staff within 90 days of approval of this WPAP application. Initial feature recognition training will also be provided to applicable new employees (site supervisors and quarry operators) within 90 days of hire. Refresher training will be provided to quarry operators as needed. All training will be conducted by the Site Supervisor or his designee using a training program prepared by a PG.

The site supervisor or his designee will maintain records of when features are identified by mining staff. These records will include the date the feature was identified, the general location of the feature, a general description of the feature, and what action was taken regarding the potential feature. These records will be maintained for five years and will be made available to the TCEQ upon request.

Any possibly sensitive geologic feature discovered by mining staff will be handled in the following manner: Sediment that can be easily removed from the area adjacent to the feature without disturbing the feature will be removed. Then a rock berm will be placed around the feature to control and filter any potential flow into the feature. After placement of the rock berm, the active work area of the quarry will be moved to another portion of the pit where the feature cannot be impacted by the continuing quarry operations. A Professional Geologist will be called to the site to assess and rate the feature. If the feature is determined to be sensitive in accordance with TAC 213 rules, the TCEQ will be notified and an appropriate method for addressing the feature will be formulated and submitted for TCEQ approval. Work will not resume in the area of the feature until the TCEQ approved method for addressing the feature has been carried out.

**Ranger Excavating, LP
Rattlesnake Ranch Quarry
Temporary Stormwater Section (TCEQ-0602)
Attachment E**

Request to Temporarily Seal a Feature

The Temporary Stormwater attachment E is not applicable for this project.

**Temporary Stormwater Section (TCEQ-0602)
Attachment F**

Structural Practices

Structural practices such as compacted earthen berms, rock berms and natural vegetation areas will be utilized as necessary to control stormwater from Site during mine related activities and continued operations at the Site after all mining related activities are complete. The compacted earthen berms will be used to contain and limit runoff discharge of pollutants from exposed areas of the Site as well as to divert flows away from exposed (disturbed) soils.

**Temporary Stormwater Section (TCEQ-0602)
Attachment G**

Drainage Area Map

Please see Interim Conditions Plan Sheet.

**Temporary Stormwater Section (TCEQ-0602)
Attachment H**

The Temporary Stormwater attachment H is not applicable for this project.

**Ranger Excavating, LP
Rattlesnake Ranch Quarry**

**Temporary Stormwater Section (TCEQ-0602)
Attachment I**

Inspection and Maintenance for BMPs

The compacted earthen berms should be inspected quarterly. All rock berms and silt fences should be inspected weekly. Written documentation of these inspections should be kept during construction at the project site (see following example Inspection Form). Any erosion of earthen berms or rock berms should be backfilled and compacted as soon as possible. If a berm is no longer able to properly filter the sediment from the stormwater due to contamination from silt, it should be replaced. Any trash in the vegetated buffers should be removed and eroded areas should be reseeded. Silt fencing should be repaired or replaced when damaged and sediment should be removed when buildup reaches 6 inches.

The site will be authorized to discharge stormwater under the TPDES General Permit No. TXR050000 for industrial activities. Requirements of the general permit include maintaining a SWP3 which includes inspections of stormwater best management practices and sampling of stormwater that is discharged from the site. Trash and construction debris should not become a potential pollutant source for stormwater discharge and should be removed daily. Should any vegetative areas be eroded, they must be reseeded.

It is not anticipated that dewatering of the pit will be required. However, if necessary, mine dewatering will be accomplished according to the TCEQ stormwater regulations noted in the TPDES General Permit No. TXR050000 under Sector J for Mineral Mining and Processing Facilities.

		Quarterly		Weekly and After Rainfall			
		Vegetated Buffers	Earthen Berms	Silt Fence			
Date	Inspector Signature	Trash	Vegetative Cover/Erosion	Erosion of Earthen Berm	Damage	Sediment Build-up	Additional Comments

If the answer to any of the above questions is "yes", perform maintenance/repair/replacement as described below or in accordance with TCEQ Technical Guidance on BMPs.

Earthen Berm

- * Erosion of earthen berm - fill eroded areas and compact

Natural Vegetated Buffers

- * Remove trash if present
- * Reseed eroded areas to reestablish vegetation

Silt Fence

- * Repair any torn fabric, crushed/collapsed sections, etc.
- * Remove sediment when buildup reaches 6 inches

**Ranger Excavating, LP
Rattlesnake Ranch Quarry**

**Temporary Stormwater Section (TCEQ-0602)
Attachment J**

Schedule of Soil Stabilization Practices

Areas Outside the Pit:

Cleared areas and interim earthen berms may be disturbed for more than 14 days without stabilization because it is not practical to be continually stabilizing small areas prior to their excavation and stabilizing the earthen berms that are frequently relocated. The purpose of soil stabilization is to control erosion and prevent pollutants from entering surface waters, streams, and the aquifer through sensitive recharge features. Areas outside of the pit that are disturbed for quarrying are often drilled and blasted within 90 days. It is not feasible or appropriate to try to stabilize these areas with vegetation because 1) the topsoil has been removed and vegetation will not readily grow; 2) these areas will soon be excavated and; 3) other structural BMPs will be used to protect stormwater runoff quality from these areas in a manner consistent with customary and acceptable mining practices.

Because the soils and overburden in these cleared areas have been removed and placed in an earthen berm adjacent to the cleared areas, erosion of these areas is mitigated. The earthen berms upgradient of the cleared areas divert upgradient stormwater away from cleared areas and earthen berms and/or sediment basins downgradient of cleared areas will treat and/or retain stormwater runoff from the cleared area. The proposed BMPs provide adequate protection for the area outside of the pit.

Material stockpiles will be located within the quarry pit and earthen berms.

For the case when the quarry operations have been completed (permanently ceased) all stormwater will be retained in the pit. The Final Earthen Berm outside the pit will be stabilized with native grasses. The undisturbed vegetated buffers shown on the Final Conditions plan sheet will remain undisturbed so no additional stabilization practices will be needed.

Areas Inside the Pit:

Areas inside the pit do not need to be stabilized; the requirement for soil stabilization exists in order to control erosion and prevent pollutants from entering surface waters, streams and the aquifer through sensitive recharge features. The disturbed soils in or upgradient of the quarry pit will be retained in the pit thereby eliminating the need for soil stabilization in the pit to prevent pollutants from entering surface waters or streams. The BMP discussed in the WPAP Temporary Stormwater Section Attachment D (7.d.) will mitigate infiltration of stormwater into the quarry floor. In addition, it is not practical to stabilize areas of the pit with vegetation because often times areas of the pit will not be active for some period of time, then be reactivated. Therefore, since the disturbed areas will be located in the pit no soil stabilization is expected to be necessary at the completion of the project.

Permanent Stormwater Section

Texas Commission on Environmental Quality

for Regulated Activities on the Edwards Aquifer Recharge Zone and Relating to 30 TAC §213.5(b)(4)(C), (D)(li), (E), and (5), Effective June 1, 1999

To ensure that the application is administratively complete, confirm that all fields in the form are complete, verify that all requested information is provided, consistently reference the same site and contact person in all forms in the application, and ensure forms are signed by the appropriate party.

Note: Including all the information requested in the form and attachments contributes to more streamlined technical reviews.

Signature

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. This **Permanent Stormwater Section** is hereby submitted for TCEQ review and executive director approval. The application was prepared by:


Print Name of Customer/Agent: Nicolas E. Mercado

Texas License No. 144228 | Firm No. 4524

Date: 12/19/2023

Signature of Customer/Agent

Nicolas E. Mercado



Regulated Entity Name: Rattlesnake Ranch Quarry

Permanent Best Management Practices (BMPs)

Permanent best management practices and measures that will be used during and after construction is completed.

1. ☒ Permanent BMPs and measures must be implemented to control the discharge of pollution from regulated activities after the completion of construction.
☐ N/A
2. ☒ These practices and measures have been designed, and will be constructed, operated, and maintained to insure that 80% of the incremental increase in the annual mass loading of total suspended solids (TSS) from the site caused by the regulated activity is removed. These quantities have been calculated in accordance with technical guidance prepared or accepted by the executive director.

- ☒ The TCEQ Technical Guidance Manual (TGM) was used to design permanent BMPs and measures for this site.
- ☐ A technical guidance other than the TCEQ TGM was used to design permanent BMPs and measures for this site. The complete citation for the technical guidance that was used is: _____
- ☐ N/A
3. ☒ Owners must insure that permanent BMPs and measures are constructed and function as designed. A Texas Licensed Professional Engineer must certify in writing that the permanent BMPs or measures were constructed as designed. The certification letter must be submitted to the appropriate regional office within 30 days of site completion.
- ☐ N/A
4. Where a site is used for low density single-family residential development and has 20 % or less impervious cover, other permanent BMPs are not required. This exemption from permanent BMPs must be recorded in the county deed records, with a notice that if the percent impervious cover increases above 20% or land use changes, the exemption for the whole site as described in the property boundaries required by 30 TAC §213.4(g) (relating to Application Processing and Approval), may no longer apply and the property owner must notify the appropriate regional office of these changes.
- ☐ The site will be used for low density single-family residential development and has 20% or less impervious cover.
- ☐ The site will be used for low density single-family residential development but has more than 20% impervious cover.
- ☒ The site will not be used for low density single-family residential development.
5. The executive director may waive the requirement for other permanent BMPs for multi-family residential developments, schools, or small business sites where 20% or less impervious cover is used at the site. This exemption from permanent BMPs must be recorded in the county deed records, with a notice that if the percent impervious cover increases above 20% or land use changes, the exemption for the whole site as described in the property boundaries required by 30 TAC §213.4(g) (relating to Application Processing and Approval), may no longer apply and the property owner must notify the appropriate regional office of these changes.
- ☐ **Attachment A - 20% or Less Impervious Cover Waiver.** The site will be used for multi-family residential developments, schools, or small business sites and has 20% or less impervious cover. A request to waive the requirements for other permanent BMPs and measures is attached.
- ☐ The site will be used for multi-family residential developments, schools, or small business sites but has more than 20% impervious cover.
- ☒ The site will not be used for multi-family residential developments, schools, or small business sites.
6. ☒ **Attachment B - BMPs for Upgradient Stormwater.**

- ☒ A description of the BMPs and measures that will be used to prevent pollution of surface water, groundwater, or stormwater that originates upgradient from the site and flows across the site is attached.
 - ☐ No surface water, groundwater or stormwater originates upgradient from the site and flows across the site, and an explanation is attached.
 - ☐ Permanent BMPs or measures are not required to prevent pollution of surface water, groundwater, or stormwater that originates upgradient from the site and flows across the site, and an explanation is attached.
7. ☒ **Attachment C - BMPs for On-site Stormwater.**
- ☒ A description of the BMPs and measures that will be used to prevent pollution of surface water or groundwater that originates on-site or flows off the site, including pollution caused by contaminated stormwater runoff from the site is attached.
 - ☐ Permanent BMPs or measures are not required to prevent pollution of surface water or groundwater that originates on-site or flows off the site, including pollution caused by contaminated stormwater runoff, and an explanation is attached.
8. ☒ **Attachment D - BMPs for Surface Streams.** A description of the BMPs and measures that prevent pollutants from entering surface streams, sensitive features, or the aquifer is attached. Each feature identified in the Geologic Assessment as sensitive has been addressed.
- ☐ N/A
9. ☒ The applicant understands that to the extent practicable, BMPs and measures must maintain flow to naturally occurring sensitive features identified in either the geologic assessment, executive director review, or during excavation, blasting, or construction.
- ☒ The permanent sealing of or diversion of flow from a naturally-occurring sensitive feature that accepts recharge to the Edwards Aquifer as a permanent pollution abatement measure has not been proposed.
 - ☐ **Attachment E - Request to Seal Features.** A request to seal a naturally-occurring sensitive feature, that includes, for each feature, a justification as to why no reasonable and practicable alternative exists, is attached.
10. ☒ **Attachment F - Construction Plans.** All construction plans and design calculations for the proposed permanent BMP(s) and measures have been prepared by or under the direct supervision of a Texas Licensed Professional Engineer, and are signed, sealed, and dated. The plans are attached and, if applicable include:
- ☒ Design calculations (TSS removal calculations)
 - ☒ TCEQ construction notes
 - ☒ All geologic features
 - ☒ All proposed structural BMP(s) plans and specifications
- ☐ N/A

11. ☒ **Attachment G - Inspection, Maintenance, Repair and Retrofit Plan.** A plan for the inspection, maintenance, repairs, and, if necessary, retrofit of the permanent BMPs and measures is attached. The plan includes all of the following:
- ☒ Prepared and certified by the engineer designing the permanent BMPs and measures
 - ☒ Signed by the owner or responsible party
 - ☒ Procedures for documenting inspections, maintenance, repairs, and, if necessary retrofit
 - ☒ A discussion of record keeping procedures
- ☐ N/A
12. ☐ **Attachment H - Pilot-Scale Field Testing Plan.** Pilot studies for BMPs that are not recognized by the Executive Director require prior approval from the TCEQ. A plan for pilot-scale field testing is attached.
- ☒ N/A
13. ☒ **Attachment I - Measures for Minimizing Surface Stream Contamination.** A description of the measures that will be used to avoid or minimize surface stream contamination and changes in the way in which water enters a stream as a result of the construction and development is attached. The measures address increased stream flashing, the creation of stronger flows and in-stream velocities, and other in-stream effects caused by the regulated activity, which increase erosion that results in water quality degradation.
- ☐ N/A

Responsibility for Maintenance of Permanent BMP(s)

Responsibility for maintenance of best management practices and measures after construction is complete.

14. ☒ The applicant is responsible for maintaining the permanent BMPs after construction until such time as the maintenance obligation is either assumed in writing by another entity having ownership or control of the property (such as without limitation, an owner's association, a new property owner or lessee, a district, or municipality) or the ownership of the property is transferred to the entity. Such entity shall then be responsible for maintenance until another entity assumes such obligations in writing or ownership is transferred.
- ☐ N/A
15. ☒ A copy of the transfer of responsibility must be filed with the executive director at the appropriate regional office within 30 days of the transfer if the site is for use as a multiple single-family residential development, a multi-family residential development, or a non-residential development such as commercial, industrial, institutional, schools, and other sites where regulated activities occur.
- ☐ N/A

**Ranger Excavating, LP
Rattlesnake Ranch Quarry**

Permanent Stormwater Section (TCEQ-0600)

Attachment B

BMPs for Upgradient Stormwater

A description of the BMPs and measures that will be used to prevent pollution of surface water, groundwater or stormwater that originates upgradient from the site and flows across the site:

The temporary earthen berms that are constructed as clearing occurs will expand as the size of the quarry expands. The earthen berms will expand throughout the life of the project to the Final Earthen Berm shown on the Proposed Conditions Map. The Final Earthen Berm will be vegetated with native grasses to stabilize soils.

Permanent stormwater controls are those that are to remain in place after construction has been completed. At the time construction is completed at the subject site, the vegetated Final Earth Berm and the 50-foot vegetated buffer that surround most of the site, along portions the property boundary adjacent to non-mining uses.

Permanent Stormwater Section (TCEQ-0600)

Attachment C

BMPs for On-site Stormwater

A description of the BMPs and measures that will be used to prevent pollution of surface water, sensitive features or the aquifer or groundwater that originates on-site or flows off the site, including pollution caused by contaminated stormwater runoff from the site:

Pollution of surface water, groundwater or stormwater that originates on-site or flows off-site during the life of the quarry will be mitigated by the use of temporary earthen berms vegetated areas, and the pit which will be constructed as shown on the Proposed Conditions Map.

Permanent stormwater controls are those that are to remain in place after construction has been completed. At the time construction is completed at the subject site, the vegetated Final Earth Berm and the 50-foot vegetated buffer that surround most of the site, along portions the property boundary adjacent to non-mining uses.

**Ranger Excavating, LP
Rattlesnake Ranch Quarry**

**Permanent Stormwater Section (TCEQ-0600)
Attachment D**

BMPs for Surface Streams

A description of the BMPs and measures that prevent pollutants from entering surface streams, sensitive features or the aquifer:

During the life of the quarry, temporary earthen berms will be constructed to prevent pollutants from entering surface streams and the aquifer. The earthen berms that surround future disturbed areas will expand to protect the unnamed tributary of Berry Creek as mining activities approach. Natural existing vegetation will be maintained in a 25-foot buffer along each side of the centerline or the FEMA 100-year floodplain (as applicable) of the tributary. This buffer will be maintained until/unless appropriate permits can be obtained from Williamson County, FEMA and/or USACE to allow construction in these areas. In addition, a natural vegetated buffer with a minimum width of 50 feet will be maintained between the Final Earthen Berm and the property line. This natural vegetated buffer will serve as a final buffer for stormwater runoff leaving the active portion of the site.

Permanent stormwater controls are those that are to remain in place after construction has been completed. At the time construction is completed at the subject site, on-site stormwater will be treated by quarry pits or sediment ponds.

Any additional possible sensitive geologic feature discovered by construction staff will need to be evaluated by a Professional Geoscientist and if determined to be sensitive, will be reported to TCEQ. An appropriate method for addressing the feature will be formulated by a Professional Geoscientist or a Professional Engineer and upon approval by TCEQ, the method to protect or seal the feature will be implemented. Work will not resume in the area of the feature until the TCEQ approved method for addressing the feature has been carried out.

**Permanent Stormwater Section (TCEQ-0600)
Attachment F**

Construction Plans

See Interim and Final Conditions Site Plans Sheets

Ranger Excavating, LP
Rattlesnake Ranch Quarry
Permanent Stormwater Section (TCEQ-0600)
Attachment G

Inspection, Maintenance, Repair and Retrofit Plan

Final Earthen Berms should be inspected quarterly until stabilized with vegetation. Written documentation of these inspections should be kept during the course of construction at the project site. Significant erosion of berms should be backfilled and compacted as soon as possible.

Vegetated buffers should be inspected at least twice annually, until the Final Earthen Berm has been vegetated, for erosion or damage to vegetation. Written documentation of these inspections should be kept during the course of construction at the project site. Bare spots and areas of erosion identified during inspections must be replanted. Trash and debris items should be removed.

**Ranger Excavating, LP
Rattlesnake Ranch Quarry**

Inspection, Maintenance, Repair and Retrofit Plan

I, Hamilton L M'Rae, have read and understand the Inspection, Maintenance, Repair and Retrofit (IMRR) Plan contained in this Water Pollution Abatement Plan (WPAP).

I understand the specific Permanent Best Management Practices (PBMPs) and associated inspection and maintenance schedule which are outlined in this IMRR Plan. Ranger Excavating, LP will implement these inspections and perform maintenance as required to meet the intent of the IMRR Plan.

Name and signature of responsible party for maintenance of permanent BMPs

Print Name: Hamilton L M'Rae
Ranger Excavating, LP

Signature HL M'Rae


Date: 12/01/2023

Name and signature of Engineer

Print Name: Nicolas E. Mercado
Westward Environmental, Inc.

Signature Nicolas E Mercado

Date: 12/19/2023



**Ranger Excavating, LP
Rattlesnake Ranch Quarry**

**Permanent Stormwater Section (TCEQ-0600)
Attachment H**

The Permanent Stormwater attachment H is not applicable for this project.

**Permanent Stormwater Section (TCEQ-0600)
Attachment I**

Measures for Minimizing Surface Stream Contamination

To avoid surface stream contamination, natural existing vegetation will be maintained in a 25-foot buffer on both sides of the centerline or the FEMA 100-year floodplain (as applicable) the of the unnamed tributary of Berry Creek. This natural vegetated buffer will serve as a final buffer for stormwater runoff leaving the active portion of the site. Any disturbance to the buffer will be reestablished to its vegetated state within 14 days of completed construction.



TCEQ Use Only

TCEQ Core Data Form

For detailed instructions regarding completion of this form, please read the Core Data Form Instructions or call 512-239-5175.

SECTION I: General Information

1. Reason for Submission (If other is checked please describe in space provided.)		
<input checked="" type="checkbox"/> New Permit, Registration or Authorization (Core Data Form should be submitted with the program application.)		
<input type="checkbox"/> Renewal (Core Data Form should be submitted with the renewal form)		<input type="checkbox"/> Other
2. Customer Reference Number (if issued)	Follow this link to search for CN or RN numbers in Central Registry**	3. Regulated Entity Reference Number (if issued)
CN 602783037		RN NEW

SECTION II: Customer Information

4. General Customer Information		5. Effective Date for Customer Information Updates (mm/dd/yyyy)			
<input type="checkbox"/> New Customer		<input type="checkbox"/> Update to Customer Information		<input type="checkbox"/> Change in Regulated Entity Ownership	
<input type="checkbox"/> Change in Legal Name (Verifiable with the Texas Secretary of State or Texas Comptroller of Public Accounts)					
The Customer Name submitted here may be updated automatically based on what is current and active with the Texas Secretary of State (SOS) or Texas Comptroller of Public Accounts (CPA).					
6. Customer Legal Name (If an individual, print last name first: eg: Doe, John)				If new Customer, enter previous Customer below:	
Ranger Excavating, LP					
7. TX SOS/CPA Filing Number		8. TX State Tax ID (11 digits)		9. Federal Tax ID (9 digits)	
0800280937		13310779817			
10. DUNS Number (if applicable)					
11. Type of Customer:		<input checked="" type="checkbox"/> Corporation		<input type="checkbox"/> Individual	
Government: <input type="checkbox"/> City <input type="checkbox"/> County <input type="checkbox"/> Federal <input type="checkbox"/> State <input type="checkbox"/> Other		<input type="checkbox"/> Sole Proprietorship		Partnership: <input type="checkbox"/> General <input type="checkbox"/> Limited	
12. Number of Employees		<input type="checkbox"/> 0-20 <input checked="" type="checkbox"/> 21-100 <input type="checkbox"/> 101-250 <input type="checkbox"/> 251-500 <input type="checkbox"/> 501 and higher		13. Independently Owned and Operated?	
				<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	
14. Customer Role (Proposed or Actual) – as it relates to the Regulated Entity listed on this form. Please check one of the following					
<input type="checkbox"/> Owner		<input type="checkbox"/> Operator		<input checked="" type="checkbox"/> Owner & Operator	
<input type="checkbox"/> Occupational Licensee		<input type="checkbox"/> Responsible Party		<input type="checkbox"/> Voluntary Cleanup Applicant <input type="checkbox"/> Other:	
15. Mailing Address:		5222 Thunder Creek Rd			
		Suite B-1			
City		Austin		State	TX
ZIP		78759		ZIP + 4	4037
16. Country Mailing Information (if outside USA)				17. E-Mail Address (if applicable)	
				hamilton.mcrae@austingeologic.com	
18. Telephone Number		19. Extension or Code		20. Fax Number (if applicable)	
512-331-5551				512-343-9618	

SECTION III: Regulated Entity Information

21. General Regulated Entity Information (If 'New Regulated Entity' is selected below this form should be accompanied by a permit application)		
<input checked="" type="checkbox"/> New Regulated Entity <input type="checkbox"/> Update to Regulated Entity Name <input type="checkbox"/> Update to Regulated Entity Information		
The Regulated Entity Name submitted may be updated in order to meet TCEQ Agency Data Standards (removal of organizational endings such as Inc, LP, or LLC).		
22. Regulated Entity Name (Enter name of the site where the regulated action is taking place.)		
Rattlesnake Ranch Quarry		

23. Street Address of the Regulated Entity: (No PO Boxes)							
	City		State		ZIP		ZIP + 4
24. County	Williamson County						

Enter Physical Location Description if no street address is provided.

25. Description to Physical Location:	Located East of Highway 195 and SE on Old 195 (Rattlesnake Rd)																				
26. Nearest City	Florence				State	TX		Nearest ZIP Code	76527												
27. Latitude (N) In Decimal:	Degrees			Minutes			Seconds			28. Longitude (W) In Decimal:	Degrees			Minutes			Seconds				
	30			47			4.35				-97			45			41.88				
29. Primary SIC Code (4 digits)	1422			30. Secondary SIC Code (4 digits)						31. Primary NAICS Code (5 or 6 digits)						32. Secondary NAICS Code (5 or 6 digits)					
33. What is the Primary Business of this entity? (Do not repeat the SIC or NAICS description.)																					
Contracting																					
34. Mailing Address:		8880 Old 195																			
		City	Florence		State	TX		ZIP	76527		ZIP + 4										
35. E-Mail Address:		hamilton.mcrae@austingecologic.com																			
36. Telephone Number				37. Extension or Code				38. Fax Number (if applicable)													

39. TCEQ Programs and ID Numbers Check all Programs and write in the permits/registration numbers that will be affected by the updates submitted on this form. See the Core Data Form instructions for additional guidance.


<input type="checkbox"/> Dam Safety	<input type="checkbox"/> Districts	<input type="checkbox"/> Edwards Aquifer	<input type="checkbox"/> Emissions Inventory Air	<input type="checkbox"/> Industrial Hazardous Waste
<input type="checkbox"/> Municipal Solid Waste	<input type="checkbox"/> New Source Review Air	<input type="checkbox"/> OSSF	<input type="checkbox"/> Petroleum Storage Tank	<input type="checkbox"/> PWS
<input type="checkbox"/> Sludge	<input type="checkbox"/> Storm Water	<input type="checkbox"/> Title V Air	<input type="checkbox"/> Tires	<input type="checkbox"/> Used Oil
<input type="checkbox"/> Voluntary Cleanup	<input type="checkbox"/> Waste Water	<input type="checkbox"/> Wastewater Agriculture	<input type="checkbox"/> Water Rights	<input type="checkbox"/> Other:

SECTION IV: Preparer Information

40. Name:	Bobbi Bondarenko			41. Title:	Staff Engineer		
42. Telephone Number	43. Ext./Code	44. Fax Number	45. E-Mail Address				
(830) 249-8284		() -	bbondarenko@westwardenv.com				

SECTION V: Authorized Signature

46. By my signature below, I certify, to the best of my knowledge, that the information provided in this form is true and complete, and that I have signature authority to submit this form on behalf of the entity specified in Section II, Field 6 and/or as required for the updates to the ID numbers identified in field 39.

Company:	Ranger Excavating, LP		Job Title:	Engineer	
Name (In Print):	Hamilton McRae, PE			Phone:	512-372-0734
Signature:				Date:	10/05/2023

Agent Authorization Form
For Required Signature
Edwards Aquifer Protection Program
Relating to 30 TAC Chapter 213
Effective June 1, 1999

I _____ Hamilton McRae, PE _____
Print Name

_____ Engineer _____
Title - Owner/President/Other

of _____ Ranger Excavating, LP _____
Corporation/Partnership/Entity Name

have authorized _____ Curt G. Campbell, PE; Doug Millsaps, PE; Vance Houy, PE;
Gary D. Nicholls, PE; Andrea Kidd, PE; and Nicolas Mercado, PE, Chelsy L. Houy, PE
Print Name of Agent/Engineer

of _____ Westward Environmental, Inc _____
Print Name of Firm

to represent and act on the behalf of the above named Corporation, Partnership, or Entity for the purpose of preparing and submitting this plan application to the Texas Commission on Environmental Quality (TCEQ) for the review and approval consideration of regulated activities.

I also understand that:

1. The applicant is responsible for compliance with 30 Texas Administrative Code Chapter 213 and any condition of the TCEQ's approval letter. The TCEQ is authorized to assess administrative penalties of up to \$10,000 per day per violation.
2. For those submitting an application who are not the property owner, but who have the right to control and possess the property, additional authorization is required from the owner.
3. Application fees are due and payable at the time the application is submitted. The application fee must be sent to the TCEQ cashier or to the appropriate regional office. The application will not be considered until the correct fee is received by the commission.
4. A notarized copy of the Agent Authorization Form must be provided for the person preparing the application, and this form must accompany the completed application.
5. No person shall commence any regulated activity on the Edwards Aquifer Recharge Zone, Contributing Zone or Transition Zone until the appropriate application for the activity has been filed with and approved by the Executive Director.

SIGNATURE PAGE:

Applicant's Signature

10/03/2023
Date

THE STATE OF Tx §

County of TRAVIS §

BEFORE ME, the undersigned authority, on this day personally appeared Hamilton McRae known to me to be the person whose name is subscribed to the foregoing instrument, and acknowledged to me that (s)he executed same for the purpose and consideration therein expressed.

GIVEN under my hand and seal of office on this 3rd day of Oct, 2023




NOTARY PUBLIC
Veronica Lopez
Typed or Printed Name of Notary

MY COMMISSION EXPIRES: 02-11-2027

Application Fee Form

Texas Commission on Environmental Quality

Name of Proposed Regulated Entity: Rattlesnake Ranch Quarry

Regulated Entity Location: Florence, Williamson County, TX

Name of Customer: Ranger Excavation, LP

Contact Person: Hamilton McRae

Phone: 512-372-0734

Customer Reference Number (if issued): CN 602783037

Regulated Entity Reference Number (if issued): RN NEW

Austin Regional Office (3373)

☐ Hays

☐ Travis

☒ Williamson

San Antonio Regional Office (3362)

☐ Bexar

☐ Medina

☐ Uvalde

☐ Comal

☐ Kinney

Application fees must be paid by check, certified check, or money order, payable to the **Texas Commission on Environmental Quality**. Your canceled check will serve as your receipt. **This form must be submitted with your fee payment.** This payment is being submitted to:

☐ Austin Regional Office

☐ San Antonio Regional Office

☐ Mailed to: TCEQ - Cashier

☒ Overnight Delivery to: TCEQ - Cashier

Revenues Section

Mail Code 214

P.O. Box 13088

Austin, TX 78711-3088

12100 Park 35 Circle

Building A, 3rd Floor

Austin, TX 78753

(512)239-0357

Site Location (Check All That Apply):

☒ Recharge Zone

☒ Contributing Zone

☐ Transition Zone

Type of Plan	Size	Fee Due
Water Pollution Abatement Plan, Contributing Zone Plan: One Single Family Residential Dwelling	Acres	
Water Pollution Abatement Plan, Contributing Zone Plan: Multiple Single Family Residential and Parks	Acres	\$
Water Pollution Abatement Plan, Contributing Zone Plan: Non-residential	162 Acres	\$10,000
Sewage Collection System	L.F.	\$
Lift Stations without sewer lines	Acres	\$
Underground or Aboveground Storage Tank Facility	Tanks	\$
Piping System(s)(only)	Each	\$
Exception	Each	\$
Extension of Time	Each	\$

Signature: 

Date: 10/03/2023

Application Fee Schedule

Texas Commission on Environmental Quality

Edwards Aquifer Protection Program 30 TAC Chapter 213 (effective 05/01/2008)

Water Pollution Abatement Plans and Modifications

Contributing Zone Plans and Modifications

<i>Project</i>	<i>Project Area in Acres</i>	<i>Fee</i>
One Single Family Residential Dwelling	< 5	\$650
Multiple Single Family Residential and Parks	< 5	\$1,500
	5 < 10	\$3,000
	10 < 40	\$4,000
	40 < 100	\$6,500
	100 < 500	\$8,000
	≥ 500	\$10,000
Non-residential (Commercial, industrial, institutional, multi-family residential, schools, and other sites where regulated activities will occur)	< 1	\$3,000
	1 < 5	\$4,000
	5 < 10	\$5,000
	10 < 40	\$6,500
	40 < 100	\$8,000
	≥ 100	\$10,000

Organized Sewage Collection Systems and Modifications

<i>Project</i>	<i>Cost per Linear Foot</i>	<i>Minimum Fee- Maximum Fee</i>
Sewage Collection Systems	\$0.50	\$650 - \$6,500

Underground and Aboveground Storage Tank System Facility Plans and Modifications

<i>Project</i>	<i>Cost per Tank or Piping System</i>	<i>Minimum Fee- Maximum Fee</i>
Underground and Aboveground Storage Tank Facility	\$650	\$650 - \$6,500

Exception Requests

<i>Project</i>	<i>Fee</i>
Exception Request	\$500

Extension of Time Requests

<i>Project</i>	<i>Fee</i>
Extension of Time Request	\$150