

Texas Commission on Environmental Quality

Edwards Aquifer Application Cover Page

Our Review of Your Application

The Edwards Aquifer Program staff conducts an administrative and technical review of all applications. The turnaround time for administrative review can be up to 30 days as outlined in 30 TAC 213.4(e). Generally administrative completeness is determined during the intake meeting or within a few days of receipt. The turnaround time for technical review of an administratively complete Edwards Aquifer application is 90 days as outlined in 30 TAC 213.4(e). Please know that the review and approval time is directly impacted by the quality and completeness of the initial application that is received. In order to conduct a timely review, it is imperative that the information provided in an Edwards Aquifer application include final plans, be accurate, complete, and in compliance with [30 TAC 213](#).

Administrative Review

1. [Edwards Aquifer applications](#) must be deemed administratively complete before a technical review can begin. To be considered administratively complete, the application must contain completed forms and attachments, provide the requested information, and meet all the site plan requirements. The submitted application and plan sheets should be final plans. Please submit one full-size set of plan sheets with the original application, and half-size sets with the additional copies.

To ensure that all applicable documents are included in the application, the program has developed tools to guide you and web pages to provide all forms, checklists, and guidance. Please visit the below website for assistance: <http://www.tceq.texas.gov/field/eapp>.

2. This Edwards Aquifer Application Cover Page form (certified by the applicant or agent) must be included in the application and brought to the administrative review meeting.
3. Administrative reviews are scheduled with program staff who will conduct the review. Applicants or their authorized agent should call the appropriate regional office, according to the county in which the project is located, to schedule a review. The average meeting time is one hour.
4. In the meeting, the application is examined for administrative completeness. Deficiencies will be noted by staff and emailed or faxed to the applicant and authorized agent at the end of the meeting, or shortly after. Administrative deficiencies will cause the application to be deemed incomplete and returned.

An appointment should be made to resubmit the application. The application is re-examined to ensure all deficiencies are resolved. The application will only be deemed administratively complete when all administrative deficiencies are addressed.

5. If an application is received by mail, courier service, or otherwise submitted without a review meeting, the administrative review will be conducted within 30 days. The applicant and agent will be contacted with the results of the administrative review. If the application is found to be administratively incomplete, it can be retrieved from the regional office or returned by regular mail. If returned by mail, the regional office may require arrangements for return shipping.
6. If the geologic assessment was completed before October 1, 2004 and the site contains “possibly sensitive” features, the assessment must be updated in accordance with the *Instructions to Geologists* (TCEQ-0585 Instructions).

Technical Review

1. When an application is deemed administratively complete, the technical review period begins. The regional office will distribute copies of the application to the identified affected city, county, and groundwater conservation district whose jurisdiction includes the subject site. These entities and the public have 30 days to provide comments on the application to the regional office. All comments received are reviewed by TCEQ.
2. A site assessment is usually conducted as part of the technical review, to evaluate the geologic assessment and observe existing site conditions. The site must be accessible to our staff. The site boundaries should be

clearly marked, features identified in the geologic assessment should be flagged, roadways marked and the alignment of the Sewage Collection System and manholes should be staked at the time the application is submitted. If the site is not marked the application may be returned.

3. We evaluate the application for technical completeness and contact the applicant and agent via Notice of Deficiency (NOD) to request additional information and identify technical deficiencies. There are two deficiency response periods available to the applicant. There are 14 days to resolve deficiencies noted in the first NOD. If a second NOD is issued, there is an additional 14 days to resolve deficiencies. If the response to the second notice is not received, is incomplete or inadequate, or provides new information that is incomplete or inadequate, the application must be withdrawn or will be denied. Please note that because the technical review is underway, whether the application is withdrawn or denied **the application fee will be forfeited.**
4. The program has 90 calendar days to complete the technical review of the application. If the application is technically adequate, such that it complies with the Edwards Aquifer rules, and is protective of the Edwards Aquifer during and after construction, an approval letter will be issued. Construction or other regulated activity may not begin until an approval is issued.

Mid-Review Modifications

It is important to have final site plans prior to beginning the permitting process with TCEQ to avoid delays.

Occasionally, circumstances arise where you may have significant design and/or site plan changes after your Edwards Aquifer application has been deemed administratively complete by TCEQ. This is considered a “Mid-Review Modification”. Mid-Review Modifications may require redistribution of an application that includes the proposed modifications for public comment.

If you are proposing a Mid-Review Modification, two options are available:

- If the technical review has begun your application can be denied/withdrawn, your fees will be forfeited, and the plan will have to be resubmitted.
- TCEQ can continue the technical review of the application as it was submitted, and a modification application can be submitted at a later time.

If the application is denied/withdrawn, the resubmitted application will be subject to the administrative and technical review processes and will be treated as a new application. The application will be redistributed to the affected jurisdictions.

Please contact the regional office if you have questions. If your project is located in Williamson, Travis, or Hays County, contact TCEQ’s Austin Regional Office at 512-339-2929. If your project is in Comal, Bexar, Medina, Uvalde, or Kinney County, contact TCEQ’s San Antonio Regional Office at 210-490-3096

Please fill out all required fields below and submit with your application.

1. Regulated Entity Name: Dripping Springs ISD New Elementary School No. 6				2. Regulated Entity No.:					
3. Customer Name: Dripping Springs ISD				4. Customer No.: CN 601259435					
5. Project Type: (Please circle/check one)	<input checked="" type="radio"/> New	<input type="radio"/> Modification		<input type="radio"/> Extension		<input type="radio"/> Exception			
6. Plan Type: (Please circle/check one)	<input type="radio"/> WPAP	<input checked="" type="radio"/> CZP	<input type="radio"/> SCS	<input type="radio"/> UST	<input type="radio"/> AST	<input type="radio"/> EXP	<input type="radio"/> EXT	<input type="radio"/> Technical Clarification	<input checked="" type="radio"/> Optional Enhanced Measures
7. Land Use: (Please circle/check one)	<input type="radio"/> Residential		<input type="radio"/> Non-residential			8. Site (acres):		64.52	
9. Application Fee:	\$8,000		10. Permanent BMP(s):			Batch Detention and Vegetated Filter Strips			
11. SCS (Linear Ft.):			12. AST/UST (No. Tanks):						
13. County:	Hays		14. Watershed:			Little Barton Creek			

Application Distribution

Instructions: Use the table below to determine the number of applications required. One original and one copy of the application, plus additional copies (as needed) for each affected incorporated city, county, and groundwater conservation district are required. Linear projects or large projects, which cross into multiple jurisdictions, can require additional copies. Refer to the “Texas Groundwater Conservation Districts within the EAPP Boundaries” map found at:

http://www.tceq.texas.gov/assets/public/compliance/field_ops/eapp/EAPP%20GWCD%20map.pdf

For more detailed boundaries, please contact the conservation district directly.

Austin Region			
County:	Hays	Travis	Williamson
Original (1 req.)	<u> </u> X <u> </u>	—	—
Region (1 req.)	<u> </u> X <u> </u>	—	—
County(ies)	X <u> </u>	—	—
Groundwater Conservation District(s)	<u> </u> Edwards Aquifer Authority <u> </u> Barton Springs/ Edwards Aquifer <u> </u> Hays Trinity <u> </u> Plum Creek	<u> </u> Barton Springs/ Edwards Aquifer	NA
City(ies) Jurisdiction	<u> </u> Austin <u> </u> Buda <u> </u> X Dripping Springs <u> </u> Kyle <u> </u> Mountain City <u> </u> San Marcos <u> </u> Wimberley <u> </u> Woodcreek	<u> </u> Austin <u> </u> Bee Cave <u> </u> Pflugerville <u> </u> Rollingwood <u> </u> Round Rock <u> </u> Sunset Valley <u> </u> West Lake Hills	<u> </u> Austin <u> </u> Cedar Park <u> </u> Florence <u> </u> Georgetown <u> </u> Jerrell <u> </u> Leander <u> </u> Liberty Hill <u> </u> Pflugerville <u> </u> Round Rock

San Antonio Region					
County:	Bexar	Comal	Kinney	Medina	Uvalde
Original (1 req.)	—	—	—	—	—
Region (1 req.)	—	—	—	—	—
County(ies)	—	—	—	—	—
Groundwater Conservation District(s)	<u> </u> Edwards Aquifer Authority <u> </u> Trinity-Glen Rose	<u> </u> Edwards Aquifer Authority	<u> </u> Kinney	<u> </u> EAA <u> </u> Medina	<u> </u> EAA <u> </u> Uvalde
City(ies) Jurisdiction	<u> </u> Castle Hills <u> </u> Fair Oaks Ranch <u> </u> Helotes <u> </u> Hill Country Village <u> </u> Hollywood Park <u> </u> San Antonio (SAWS) <u> </u> Shavano Park	<u> </u> Bulverde <u> </u> Fair Oaks Ranch <u> </u> Garden Ridge <u> </u> New Braunfels <u> </u> Schertz	NA	<u> </u> San Antonio ETJ (SAWS)	NA

I certify that to the best of my knowledge, that the application is complete and accurate. This application is hereby submitted to TCEQ for administrative review and technical review.

Elias Haddad

Print Name of Customer/Authorized Agent

9/12/2023

Signature of Customer/Authorized Agent

Date

****FOR TCEQ INTERNAL USE ONLY****

Date(s) Reviewed:		Date Administratively Complete:	
Received From:		Correct Number of Copies:	
Received By:		Distribution Date:	
EAPP File Number:		Complex:	
Admin. Review(s) (No.):		No. AR Rounds:	
Delinquent Fees (Y/N):		Review Time Spent:	
Lat./Long. Verified:		SOS Customer Verification:	
Agent Authorization Complete/Notarized (Y/N):		Fee Check:	Payable to TCEQ (Y/N):
Core Data Form Complete (Y/N):			Signed (Y/N):
Core Data Form Incomplete Nos.:			Less than 90 days old (Y/N):

Contributing Zone Plan Application

Texas Commission on Environmental Quality

for Regulated Activities on the Contributing Zone to the Edwards Aquifer and Relating to 30 TAC §213.24(1), Effective June 1, 1999

To ensure that the application is administratively complete, confirm that all fields in the form are complete, verify that all requested information is provided, consistently reference the same site and contact person in all forms in the application, and ensure forms are signed by the appropriate party.

Note: Including all the information requested in the form and attachments contributes to more streamlined technical reviews.

Signature

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. This **Contributing Zone Plan Application** is hereby submitted for TCEQ review and Executive Director approval. The application was prepared by:

Print Name of Customer/Agent: Elias Haddad

Date: 9/15/2023

Signature of Customer/Agent:



Regulated Entity Name: Dripping Springs ISD New Elementary School No. 6

Project Information

1. County: Hays
2. Stream Basin: Little Barton Creek
3. Groundwater Conservation District (if applicable): N/A
4. Customer (Applicant):

Contact Person: Clint Pruett

Entity: Dripping Springs ISD

Mailing Address: 510 W. Mercer St.

City, State: Dripping Springs, TX

Telephone: 512-858-3032

Email Address: clint.pruett@dsisdtx.us

Zip: 78620

Fax: _____

5. Agent/Representative (If any):

Contact Person: Elias Haddad

Entity: Walker Partners

Mailing Address: 6504 Bridge Point

City, State: Austin, TX

Zip: 78730

Telephone: 512 382.0021

Fax: _____

Email Address: ehaddad@walkerpartners.com

6. Project Location:

- The project site is located inside the city limits of _____.
- The project site is located outside the city limits but inside the ETJ (extra-territorial jurisdiction) of Dripping Springs.
- The project site is not located within any city's limits or ETJ.

7. The location of the project site is described below. Sufficient detail and clarity has been provided so that the TCEQ's Regional staff can easily locate the project and site boundaries for a field investigation.

West of Headwaters Subdivision, Access through Headwaters Boulevard off Route 290, and Mira Vista Drive.

8. **Attachment A - Road Map.** A road map showing directions to and the location of the project site is attached. The map clearly shows the boundary of the project site.
9. **Attachment B - USGS Quadrangle Map.** A copy of the official 7 ½ minute USGS Quadrangle Map (Scale: 1" = 2000') is attached. The map(s) clearly show:
- Project site boundaries.
 - USGS Quadrangle Name(s).
10. **Attachment C - Project Narrative.** A detailed narrative description of the proposed project is attached. The project description is consistent throughout the application and contains, at a minimum, the following details:
- Area of the site
 - Offsite areas
 - Impervious cover
 - Permanent BMP(s)
 - Proposed site use
 - Site history
 - Previous development
 - Area(s) to be demolished

11. Existing project site conditions are noted below:

- Existing commercial site
- Existing industrial site

- Existing residential site
- Existing paved and/or unpaved roads
- Undeveloped (Cleared)
- Undeveloped (Undisturbed/Not cleared)
- Other: _____

12. The type of project is:

- Residential: # of Lots: _____
- Residential: # of Living Unit Equivalents: _____
- Commercial
- Industrial
- Other: School

13. Total project area (size of site): 64.52 Acres

Total disturbed area: 17.5 Acres

14. Estimated projected population: 850 Students

15. The amount and type of impervious cover expected after construction is complete is shown below:

Table 1 - Impervious Cover

<i>Impervious Cover of Proposed Project</i>	<i>Sq. Ft.</i>	<i>Sq. Ft./Acre</i>	<i>Acres</i>
Structures/Rooftops	95,830	÷ 43,560 =	2.2
Parking	291,850	÷ 43,560 =	6.7
Other paved surfaces	100,200	÷ 43,560 =	2.3
Total Impervious Cover	487,880	÷ 43,560 =	11.2

Total Impervious Cover 11.2 ÷ Total Acreage 64.52 X 100 = 17.4% Impervious Cover

16. **Attachment D - Factors Affecting Surface Water Quality.** A detailed description of all factors that could affect surface water quality is attached. If applicable, this includes the location and description of any discharge associated with industrial activity other than construction.

17. Only inert materials as defined by 30 TAC 330.2 will be used as fill material.

For Road Projects Only

Complete questions 18 - 23 if this application is exclusively for a road project.

N/A

18. Type of project:

- TXDOT road project.
- County road or roads built to county specifications.
- City thoroughfare or roads to be dedicated to a municipality.
- Street or road providing access to private driveways.

19. Type of pavement or road surface to be used:

- Concrete
- Asphaltic concrete pavement
- Other: _____

20. Right of Way (R.O.W.):

Length of R.O.W.: _____ feet.

Width of R.O.W.: _____ feet.

$L \times W = \text{_____ Ft}^2 \div 43,560 \text{ Ft}^2/\text{Acre} = \text{_____ acres.}$

21. Pavement Area:

Length of pavement area: _____ feet.

Width of pavement area: _____ feet.

$L \times W = \text{_____ Ft}^2 \div 43,560 \text{ Ft}^2/\text{Acre} = \text{_____ acres.}$

Pavement area _____ acres \div R.O.W. area _____ acres $\times 100 = \text{_____ \%}$ impervious cover.

22. A rest stop will be included in this project.

A rest stop will not be included in this project.

23. Maintenance and repair of existing roadways that do not require approval from the TCEQ Executive Director. Modifications to existing roadways such as widening roads/adding shoulders totaling more than one-half (1/2) the width of one (1) existing lane require prior approval from the TCEQ.

Stormwater to be generated by the Proposed Project

24. **Attachment E - Volume and Character of Stormwater.** A detailed description of the volume (quantity) and character (quality) of the stormwater runoff which is expected to occur from the proposed project is attached. The estimates of stormwater runoff quality and quantity are based on area and type of impervious cover. Include the runoff coefficient of the site for both pre-construction and post-construction conditions.

Wastewater to be generated by the Proposed Project

25. Wastewater is to be discharged in the contributing zone. Requirements under 30 TAC §213.6(c) relating to Wastewater Treatment and Disposal Systems have been satisfied.

N/A

26. Wastewater will be disposed of by:

On-Site Sewage Facility (OSSF/Septic Tank):

Attachment F - Suitability Letter from Authorized Agent. An on-site sewage facility will be used to treat and dispose of the wastewater from this site. The appropriate licensing authority's (authorized agent) written approval is attached. It states that the land is suitable for the use of private sewage facilities and will meet or exceed the requirements for on-site sewage facilities as specified under 30 TAC Chapter 285 relating to On-site Sewage Facilities.

Each lot in this project/development is at least one (1) acre (43,560 square feet) in size. The system will be designed by a licensed professional engineer or registered sanitarian and installed by a licensed installer in compliance with 30 TAC Chapter 285.

Sewage Collection System (Sewer Lines):

The sewage collection system will convey the wastewater to the Headwaters MUD (name) Treatment Plant. The treatment facility is:

Existing.

Proposed.

N/A

Permanent Aboveground Storage Tanks(ASTs) ≥ 500 Gallons

Complete questions 27 - 33 if this project includes the installation of AST(s) with volume(s) greater than or equal to 500 gallons.

N/A

27. Tanks and substance stored:

Table 2 - Tanks and Substance Storage

<i>AST Number</i>	<i>Size (Gallons)</i>	<i>Substance to be Stored</i>	<i>Tank Material</i>
1			
2			
3			
4			
5			

Total x 1.5 = _____ Gallons

28. The AST will be placed within a containment structure that is sized to capture one and one-half (1 1/2) times the storage capacity of the system. For facilities with more than

one tank system, the containment structure is sized to capture one and one-half (1 1/2) times the cumulative storage capacity of all systems.

- Attachment G - Alternative Secondary Containment Methods.** Alternative methods for providing secondary containment are proposed. Specifications showing equivalent protection for the Edwards Aquifer are attached.

29. Inside dimensions and capacity of containment structure(s):

Table 3 - Secondary Containment

<i>Length (L)(Ft.)</i>	<i>Width(W)(Ft.)</i>	<i>Height (H)(Ft.)</i>	<i>L x W x H = (Ft3)</i>	<i>Gallons</i>

Total: _____ Gallons

30. Piping:

- All piping, hoses, and dispensers will be located inside the containment structure.
- Some of the piping to dispensers or equipment will extend outside the containment structure.
- The piping will be aboveground
- The piping will be underground

31. The containment area must be constructed of and in a material impervious to the substance(s) being stored. The proposed containment structure will be constructed of: _____.

32. **Attachment H - AST Containment Structure Drawings.** A scaled drawing of the containment structure is attached that shows the following:

- Interior dimensions (length, width, depth and wall and floor thickness).
- Internal drainage to a point convenient for the collection of any spillage.
- Tanks clearly labeled
- Piping clearly labeled
- Dispenser clearly labeled

33. Any spills must be directed to a point convenient for collection and recovery. Spills from storage tank facilities must be removed from the controlled drainage area for disposal within 24 hours of the spill.

- In the event of a spill, any spillage will be removed from the containment structure within 24 hours of the spill and disposed of properly.

- In the event of a spill, any spillage will be drained from the containment structure through a drain and valve within 24 hours of the spill and disposed of properly. The drain and valve system are shown in detail on the scaled drawing.

Site Plan Requirements

Items 34 - 46 must be included on the Site Plan.

34. The Site Plan must have a minimum scale of 1" = 400'.
Site Plan Scale: 1" = 60'.
35. 100-year floodplain boundaries:
- Some part(s) of the project site is located within the 100-year floodplain. The floodplain is shown and labeled.
- No part of the project site is located within the 100-year floodplain.
The 100-year floodplain boundaries are based on the following specific (including date of material) sources(s): _____.
36. The layout of the development is shown with existing and finished contours at appropriate, but not greater than ten-foot contour intervals. Lots, recreation centers, buildings, roads, etc. are shown on the site plan.
- The layout of the development is shown with existing contours at appropriate, but not greater than ten-foot contour intervals. Finished topographic contours will not differ from the existing topographic configuration and are not shown. Lots, recreation centers, buildings, roads, etc. are shown on the site plan.
37. A drainage plan showing all paths of drainage from the site to surface streams.
38. The drainage patterns and approximate slopes anticipated after major grading activities.
39. Areas of soil disturbance and areas which will not be disturbed.
40. Locations of major structural and nonstructural controls. These are the temporary and permanent best management practices.
41. Locations where soil stabilization practices are expected to occur.
42. Surface waters (including wetlands).
 N/A
43. Locations where stormwater discharges to surface water.
 There will be no discharges to surface water.
44. Temporary aboveground storage tank facilities.
 Temporary aboveground storage tank facilities will not be located on this site.

45. Permanent aboveground storage tank facilities.
 Permanent aboveground storage tank facilities will not be located on this site.
46. Legal boundaries of the site are shown.

Permanent Best Management Practices (BMPs)

Practices and measures that will be used during and after construction is completed.

47. Permanent BMPs and measures must be implemented to control the discharge of pollution from regulated activities after the completion of construction.
 N/A
48. These practices and measures have been designed, and will be constructed, operated, and maintained to insure that 80% of the incremental increase in the annual mass loading of total suspended solids (TSS) from the site caused by the regulated activity is removed. These quantities have been calculated in accordance with technical guidance prepared or accepted by the executive director.
 The TCEQ Technical Guidance Manual (TGM) was used to design permanent BMPs and measures for this site.
 A technical guidance other than the TCEQ TGM was used to design permanent BMPs and measures for this site. The complete citation for the technical guidance that was used is: _____.
 N/A
49. Owners must insure that permanent BMPs and measures are constructed and function as designed. A Texas Licensed Professional Engineer must certify in writing that the permanent BMPs or measures were constructed as designed. The certification letter must be submitted to the appropriate regional office within 30 days of site completion.
 N/A
50. Where a site is used for low density single-family residential development and has 20 % or less impervious cover, other permanent BMPs are not required. This exemption from permanent BMPs must be recorded in the county deed records, with a notice that if the percent impervious cover increases above 20% or land use changes, the exemption for the whole site as described in the property boundaries required by 30 TAC §213.4(g) (relating to Application Processing and Approval), may no longer apply and the property owner must notify the appropriate regional office of these changes.
 The site will be used for low density single-family residential development and has 20% or less impervious cover.
 The site will be used for low density single-family residential development but has more than 20% impervious cover.
 The site will not be used for low density single-family residential development.

51. The executive director may waive the requirement for other permanent BMPs for multi-family residential developments, schools, or small business sites where 20% or less impervious cover is used at the site. This exemption from permanent BMPs must be recorded in the county deed records, with a notice that if the percent impervious cover increases above 20% or land use changes, the exemption for the whole site as described in the property boundaries required by 30 TAC §213.4(g) (relating to Application Processing and Approval), may no longer apply and the property owner must notify the appropriate regional office of these changes.

- Attachment I - 20% or Less Impervious Cover Waiver.** The site will be used for multi-family residential developments, schools, or small business sites and has 20% or less impervious cover. A request to waive the requirements for other permanent BMPs and measures is attached.
- The site will be used for multi-family residential developments, schools, or small business sites but has more than 20% impervious cover.
- The site will not be used for multi-family residential developments, schools, or small business sites.

52. **Attachment J - BMPs for Upgradient Stormwater.**

- A description of the BMPs and measures that will be used to prevent pollution of surface water, groundwater, or stormwater that originates upgradient from the site and flows across the site is attached.
- No surface water, groundwater or stormwater originates upgradient from the site and flows across the site, and an explanation is attached.
- Permanent BMPs or measures are not required to prevent pollution of surface water, groundwater, or stormwater that originates upgradient from the site and flows across the site, and an explanation is attached.

53. **Attachment K - BMPs for On-site Stormwater.**

- A description of the BMPs and measures that will be used to prevent pollution of surface water or groundwater that originates on-site or flows off the site, including pollution caused by contaminated stormwater runoff from the site is attached.
- Permanent BMPs or measures are not required to prevent pollution of surface water or groundwater that originates on-site or flows off the site, including pollution caused by contaminated stormwater runoff, and an explanation is attached.

54. **Attachment L - BMPs for Surface Streams.** A description of the BMPs and measures that prevent pollutants from entering surface streams is attached.

N/A

55. **Attachment M - Construction Plans.** Construction plans and design calculations for the proposed permanent BMPs and measures have been prepared by or under the direct supervision of a Texas Licensed Professional Engineer, and are signed, sealed, and dated. Construction plans for the proposed permanent BMPs and measures are

attached and include: Design calculations, TCEQ Construction Notes, all proposed structural plans and specifications, and appropriate details.

N/A

56. **Attachment N - Inspection, Maintenance, Repair and Retrofit Plan.** A site and BMP specific plan for the inspection, maintenance, repair, and, if necessary, retrofit of the permanent BMPs and measures is attached. The plan fulfills all of the following:

- Prepared and certified by the engineer designing the permanent BMPs and measures
- Signed by the owner or responsible party
- Outlines specific procedures for documenting inspections, maintenance, repairs, and, if necessary, retrofit.
- Contains a discussion of record keeping procedures

N/A

57. **Attachment O - Pilot-Scale Field Testing Plan.** Pilot studies for BMPs that are not recognized by the Executive Director require prior approval from the TCEQ. A plan for pilot-scale field testing is attached.

N/A

58. **Attachment P - Measures for Minimizing Surface Stream Contamination.** A description of the measures that will be used to avoid or minimize surface stream contamination and changes in the way in which water enters a stream as a result of the construction and development is attached. The measures address increased stream flashing, the creation of stronger flows and in-stream velocities, and other in-stream effects caused by the regulated activity, which increase erosion that result in water quality degradation.

N/A

Responsibility for Maintenance of Permanent BMPs and Measures after Construction is Complete.

59. The applicant is responsible for maintaining the permanent BMPs after construction until such time as the maintenance obligation is either assumed in writing by another entity having ownership or control of the property (such as without limitation, an owner's association, a new property owner or lessee, a district, or municipality) or the ownership of the property is transferred to the entity. Such entity shall then be responsible for maintenance until another entity assumes such obligations in writing or ownership is transferred.
60. A copy of the transfer of responsibility must be filed with the executive director at the appropriate regional office within 30 days of the transfer if the site is for use as a multiple single-family residential development, a multi-family residential development,

or a non-residential development such as commercial, industrial, institutional, schools, and other sites where regulated activities occur.


Administrative Information

61. Submit one (1) original and one (1) copy of the application, plus additional copies as needed for each affected incorporated city, groundwater conservation district, and county in which the project will be located. The TCEQ will distribute the additional copies to these jurisdictions.
62. Any modification of this Contributing Zone Plan may require TCEQ review and Executive Director approval prior to construction, and may require submission of a revised application, with appropriate fees.
63. The site description, controls, maintenance, and inspection requirements for the storm water pollution prevention plan (SWPPP) developed under the EPA NPDES general permits for stormwater discharges have been submitted to fulfill paragraphs 30 TAC §213.24(1-5) of the technical report. All requirements of 30 TAC §213.24(1-5) have been met by the SWPPP document.
 The Temporary Stormwater Section (TCEQ-0602) is included with the application.

GENERAL INFORMATION FORM - ATTACHMENT A


A road map (Not to scale) showing directions to the location of the project site.

PROJECT SITE



GENERAL INFORMATION FORM - ATTACHMENT B

USGS Quad Num: 30098B1
USGS Quad Name: DRIPPING SPRINGS



ATTACHMENT C – Project Narrative

The subject property consists of 64.52 acres located north of Route 12 in Dripping Springs, Texas, west of the Headwaters Subdivision.

The project site is currently undeveloped and has natural existing vegetation with sloping terrain.

There is no existing impervious cover. Proposed impervious cover is 489,550 sf (11.25 ac).

The proposed improvements with this Contributing Zone Permit (CZP) application includes the main elementary school building, associated drives and parking lots, and all associated water, wastewater, and drainage improvements. In addition, water quality controls and detention infrastructure will be constructed to treat the storm water.

The master plan for the site includes the potential construction of a future Middle School, football field with running track, a practice field, tennis courts, and related parking and infrastructure. These improvements are not included with this application.

In accordance with the West Travis County Public Utility Agency Water and Sewer Service and Development Policies, this project is required to adopt one of the alternative water quality measures required as specified in the “Memorandum of Understanding” between LCRA and the USFWS. The alternative water quality measures to be employed on this project are designed to comply with the TCEQ “Optional Enhanced Measures for Protection of Water Quality in the Edwards Aquifer” (RG-348 Appendix A and Appendix B).

In accordance with the “Optional Enhanced Measures”, a Geologic Assessment was performed to identify any sensitive features, and stream buffers were established based on drainage areas contributing flow to the streams. No sensitive features were located in the Geologic Assessment. See copy of report attached.

The water quality pond will serve as a temporary sediment basin during construction. The capture volume of 108,000 cf was calculated in accordance with RG-348 Appendix A (see Pond Plan and Pond Details sheets in the plans). Permanent BMP’s will be sized based off the required TSS removal methodology as outlined in the “Optional Enhanced Measures”. Finally, to protect area stream morphology, the project will limit the peak rate of runoff for the 2-yr, 24-hour storm to 50% of the undeveloped rate for that event and will limit the 10-yr, 24-hour storm peak runoff rate to the undeveloped rate for the same storm conditions (see table on Pond Drainage Area Map sheet in the plans).

Water Quality Controls

The required amount of TSS removal is based on the methodology in RG-348 Appendix A which requires the removal of 80% of the annual TSS load in the runoff from the site without regard for the level of impervious cover. Based on the Project Area of 64.52 acres and the impervious cover of 11.25 acres, the required amount of TSS Load removal (L_M) is 10,087 lbs.

A batch detention pond and vegetative filter strips are proposed as Best Management Practices (BMPs) for the project.

Drainage Area 'PR1' (13.5 ac with 9.4 ac impervious) drains to the pond which has the potential to remove 9,885 lbs of TSS.

Drainage Areas 'PR2' and 'PR3' (51.1 ac with 1.8 acres of impervious) flow over the entrance drives and through the vegetative filter strips which have the potential to remove 2,483 lbs of TSS.

The total removal (L_R) by these BMPs is 12,368 lbs of TSS.

In accordance with the requirement to protect stream morphology portion of the Enhanced Measures, the peak stormwater release rates for the 2-yr 24-hr developed condition event must be limited to 50% of the release rates for the same event under undeveloped conditions. HEC-HMS 4.11 was used to model the hydrology of the site.

Drainage

Drainage/grading improvements proposed throughout the project will convey runoff to the water quality treatment measures.

Water

Domestic water service and fire flow will be supplied by the Headwaters MUD who purchases water from the West Travis County Public Utility Agency (WTCPUA)

Wastewater

Wastewater from the proposed facility will be collected via gravity by 6" PVC service line and conveyed to a proposed grinder pump/lift station. The effluent (about 16 GPMs) will be pumped through a 3" PVC force main to the existing wastewater system in the Headwaters Subdivision.

Geologic Assessment

Texas Commission on Environmental Quality

For Regulated Activities on The Edwards Aquifer Recharge/transition Zones and Relating to 30 TAC §213.5(b)(3), Effective June 1, 1999

To ensure that the application is administratively complete, confirm that all fields in the form are complete, verify that all requested information is provided, consistently reference the same site and contact person in all forms in the application, and ensure forms are signed by the appropriate party.

Note: Including all the information requested in the form and attachments contributes to more streamlined technical reviews.

Signature

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. My signature certifies that I am qualified as a geologist as defined by 30 TAC Chapter 213.

Print Name of Geologist: Russell Ford, P.G

Telephone: 512 442-1122

Date: 11/8/22

Fax: 512-442-1181

Representing: Terracon Consultants, Inc. / TBPG 50058 (Name of Company and TBPG or TBPE registration number)

Signature of Geologist:

Regulated Entity Name: Headwaters School Tract, Red Bud Road and Headwaters Boulevard, Dripping Springs, Texas

Project Information

1. Date(s) Geologic Assessment was performed: 11/1/22 and 11/2/22

2. Type of Project:

WPAP

AST

SCS

UST

3. Location of Project:

Recharge Zone

Transition Zone

Contributing Zone within the Transition Zone

4. Attachment A - Geologic Assessment Table. Completed Geologic Assessment Table (Form TCEQ-0585-Table) is attached.
5. Soil cover on the project site is summarized in the table below and uses the SCS Hydrologic Soil Groups* (Urban Hydrology for Small Watersheds, Technical Release No. 55, Appendix A, Soil Conservation Service, 1986). If there is more than one soil type on the project site, show each soil type on the site Geologic Map or a separate soils map.

Table 1 - Soil Units, Infiltration Characteristics and Thickness

Soil Name	Group*	Thickness(feet)
RcD	C	2
BtG	C	1.5
DoC	D	2
SuB	C	2.5

* Soil Group Definitions (Abbreviated)

- A. Soils having a high infiltration rate when thoroughly wetted.
- B. Soils having a moderate infiltration rate when thoroughly wetted.
- C. Soils having a slow infiltration rate when thoroughly wetted.
- D. Soils having a very slow infiltration rate when thoroughly wetted.

6. Attachment B – Stratigraphic Column. A stratigraphic column showing formations, members, and thicknesses is attached. The outcropping unit, if present, should be at the top of the stratigraphic column. Otherwise, the uppermost unit should be at the top of the stratigraphic column.
7. Attachment C – Site Geology. A narrative description of the site specific geology including any features identified in the Geologic Assessment Table, a discussion of the potential for fluid movement to the Edwards Aquifer, stratigraphy, structure(s), and karst characteristics is attached.
8. Attachment D – Site Geologic Map(s). The Site Geologic Map must be the same scale as the applicant's Site Plan. The minimum scale is 1" : 400'
 Applicant's Site Plan Scale: 1" = '
 Site Geologic Map Scale: 1" = 500'
 Site Soils Map Scale (if more than 1 soil type): 1" = 500'
9. Method of collecting positional data:
 - Global Positioning System (GPS) technology.
 - Other method(s). Please describe method of data collection: _____
10. The project site and boundaries are clearly shown and labeled on the Site Geologic Map.
11. Surface geologic units are shown and labeled on the Site Geologic Map.

12. Geologic or manmade features were discovered on the project site during the field investigation. They are shown and labeled on the Site Geologic Map and are described in the attached Geologic Assessment Table.
- Geologic or manmade features were not discovered on the project site during the field investigation.
13. The Recharge Zone boundary is shown and labeled, if appropriate.
14. All known wells (test holes, water, oil, unplugged, capped and/or abandoned, etc.): If applicable, the information must agree with Item No. 20 of the WPAP Application Section.
- There are _____ (#) wells present on the project site and the locations are shown and labeled. (Check all of the following that apply.)
- The wells are not in use and have been properly abandoned.
- The wells are not in use and will be properly abandoned.
- The wells are in use and comply with 16 TAC Chapter 76.
- There are no wells or test holes of any kind known to exist on the project site.

Administrative Information

15. Submit one (1) original and one (1) copy of the application, plus additional copies as needed for each affected incorporated city, groundwater conservation district, and county in which the project will be located. The TCEQ will distribute the additional copies to these jurisdictions. The copies must be submitted to the appropriate regional office.

ATTACHMENT A

NO FEATURES

GEOLOGIC ASSESSMENT TABLE										PROJECT NAME: Headwaters School Tract, Red Bud Road and Headwaters Boulevard, Dripping Springs, Texas									
LOCATION			FEATURE CHARACTERISTICS										EVALUATION		PHYSICAL SETTING				
1A	1B *	1C'	2A	2B	3	4			5	5A	6	7	8A	8B	9	10	11		12
FEATURE ID	LATITUDE	LONGITUDE	FEATURE TYPE	POINTS	FORMATION	DIMENSIONS (FEET)			TREND (DEGREES)	DOM	DENSITY (NO/FT)	APERTURE (FEET)	INFILL	RELATIVE INFILTRATION RATE	TOTAL	SENSITIVITY	CATCHMENT AREA (ACRES)	TOPOGRAPHY	
						X	Y	Z		10						<40	≥40	<1.6	≥1.6

* DATUM: NAD27

2A TYPE	TYPE	2B POINTS
C	Cave	30
SC	Solution cavity	20
SF	Solution-enlarged fracture(s)	20
F	Fault	20
O	Other natural bedrock features	5
MB	Manmade feature in bedrock	30
SW	Swallow hole	30
SH	Sinkhole	20
CD	Non-karst closed depression	5
Z	Zone, clustered or aligned features	30

8A INFILLING	
N	None, exposed bedrock
C	Coarse - cobbles, breakdown, sand, gravel
O	Loose or soft mud or soil, organics, leaves, sticks, dark colors
F	Fines, compacted clay-rich sediment, soil profile, gray or red colors
V	Vegetation. Give details in narrative description
FS	Flowstone, cements, cave deposits
X	Other materials

12 TOPOGRAPHY
Cliff, Hilltop, Hillside, Drainage, Floodplain, Streambed

I have read, I understood, and I have followed the Texas Natural Resource Conservation Commission's Instructions to Geologists. The information presented here complies with that document and is a true representation of the conditions observed in the field.

My signature certifies that I am qualified as a geologist as defined by 30 TAC 213

Date _____

Attachment B
Stratigraphic Column
Headwaters School Tract
Red Bud Road and Headwaters Boulevard
Dripping Springs, Texas

HYDROGEOLOGIC SUBDIVISION	FORMATION	THICKNESS (feet)	LITHOLOGY
Lower confining unit	Glen Rose Limestone	380	Dolomitic limestone interbedded with marl in alternating resistant and recessive beds

Source: Geologic Atlas of Texas, Llano Sheet




ATTACHMENT C SITE-SPECIFIC GEOLOGY

The Geologic Assessment (GA) of the Headwaters School Tract was performed by Mr. Russell C. Ford, P.G., of Terracon on November 1 and 2, 2022. The site consists of approximately 64.51 acres of naturally vegetated, undeveloped land located just west of the intersection of Red Bud Road and Headwaters Boulevard in Dripping Springs, Texas. The site consists of undeveloped, ranch property. Exhibit 1 (attached) is a site location map depicting the site in relation to the surrounding area. The site is vegetated with mostly native grasses and areas with scattered to dense hardwoods, mostly Ashe Juniper and Live Oak. The areas immediately surrounding the site are a combination of undeveloped and residential properties. Two drainages cross the site and drainage is offsite to the north. The site is characterized as sloping to the north with site elevation ranging from about 1180 feet above mean sea level (msl) to about 1080 feet msl.

The Geologic Site Map is provided as Exhibit 2. The site is located outside of the recharge zone of the Edwards aquifer. The surficial geologic unit present at the site has been identified as the Glen Rose Formation. The Glen Rose Formation forms the lower confining unit to the Edwards aquifer and consists of a yellowish-tan, thinly bedded limestone and marl. The upper member of the Glen Rose consists of shale and marl alternating with thin beds of limestone and dolomite. This alternating bedding of limestone and marl forms the typical stair-step topography observed in outcrops in the area and on the site. Thicknesses of about 350 to 400 feet are present in the area. Table 1 (attached) is a stratigraphic column prepared for the site. The upper 100 feet is typically heavily weathered and contains abundant porous, soft dolomite and burrowed limestone resulting in gentle slopes and many springs. The dolomitic portions of the upper member contain water and make up part of the upper Trinity aquifer. The completed Geologic Assessment form is attached.

Surface exposure onsite of the Glen Rose is generally obscured by the presence of soil cover and vegetation. Several small, fractured outcrops of Glen Rose limestone was also observed exposed within the drainages crossing the site. No active seeps or springs were observed onsite. No caves, sinkholes, or significant solution cavities were observed on the site. No evidence of any faulting was observed on the site and none is shown on any of the available published geologic maps of the area. Additionally, a review of aerial photographs did not reveal any lineations, which typically indicate the presence of faulting. The closest mapped fault is located approximately 8 miles southwest of the site. The fault trends toward the northeast and is associated with the Balcones fault zone, which is comprised of en echelon, normal, high-angle faults, that are generally down thrown to the southeast and represents the dominant structural trend of the area.

No sensitive geologic features, as defined in the TCEQ's instructions to geologists, were observed on the site. Since the site is not located within the recharge zone of the Edwards Aquifer, there is no potential for any recharge to the Edwards Aquifer beneath the site.



Legend
 Project Boundary

Sources: TNRS, USGS topoView, Service Layer Credits: Sources: Esri, HERE, DeLorme, USGS, Intermap, INCREMENT P, NRCan, Esri Japan, METI, Esri China (Hong Kong), Esri Korea, Esri (Thailand), MapmyIndia, NGCC, © OpenStreetMap contributors, and the GIS User Community


Project Mngr:	CG
Drawn By:	Terracon
Checked By:	CG
Approved By:	AS

Project No.	96227862
Scale:	AS SHOWN
File No.:	96227862
Date:	11/3/22

Terracon
 Consulting Engineers & Scientists
 5307 INDUSTRIAL OAKS BLVD. - #160 AUSTIN, TX 78735
 PH. (512) 442-1122 FAX. (512) 442-1181

1986 USGS Topographic Map: Dripping Springs
 Headwaters School Tract
 Red Bud Road
 Dripping Springs, Hays County, Texas

EXHIBIT
 1



Legend
 Project Boundary

Sources: TNRS, USGS topoView, Service Layer Credits: Sources: Esri, HERE, DeLorme, USGS, Intermap, INCREMENT P, NRCan, Esri Japan, METI, Esri China (Hong Kong), Esri Korea, Esri (Thailand), MapmyIndia, NGCC, © OpenStreetMap contributors, and the GIS User Community


Project Mngr:	CG
Drawn By:	Terracon
Checked By:	CG
Approved By:	AS

Project No.	96227862
Scale:	AS SHOWN
File No.:	96227862
Date:	11/3/22

Terracon
 Consulting Engineers & Scientists
 5307 INDUSTRIAL OAKS BLVD. - #160 AUSTIN, TX 78735
 PH. (512) 442-1122 FAX. (512) 442-1181

Site Geologic Map
 Headwaters School Tract
 Red Bud Road
 Dripping Springs, Hays County, Texas

EXHIBIT
 2



Legend

Project Boundary

Web Soil Survey

Sources: TNRS, USGS topoView, Service Layer Credits: Sources: Esri, HERE, DeLorme, USGS, Intermap, INCREMENT P, NRCan, Esri Japan, METI, Esri China (Hong Kong), Esri Korea, Esri (Thailand), MapmyIndia, NGCC, © OpenStreetMap contributors, and the GIS User Community

Project Mngr:	CG
Drawn By:	Terracon
Checked By:	CG
Approved By:	AS

Project No.	96227862
Scale:	AS SHOWN
File No.:	96227862
Date:	11/3/22

Terracon
 Consulting Engineers & Scientists
 5307 INDUSTRIAL OAKS BLVD. - #160 AUSTIN, TX 78735
 PH. (512) 442-1122 FAX. (512) 442-1181

USDA Web Soil Survey
 Headwaters School Tract
 Red Bud Road
 Dripping Springs, Hays County, Texas

EXHIBIT
 3

ATTACHMENT D - Factors Affecting Surface Water Quality

Factors affecting water quality include oils, grease, and other substances typically associated with driving areas. Runoff will be treated as required by the TCEQ Environmental Regulations.

ATTACHMENT E - Volume and Character of Stormwater

The expected character of water generated from the project site includes a mixture of water with oil, grease, and other substances generally associated with paved drives.

This 64.52 ac site has an existing 25-year flow of 432.1 cfs and no impervious cover. After construction, the site will have a 25-year flow of 414.8 cfs and 11.25 ac of impervious cover.

ATTACHMENT J – BMPs for Up Gradient Stormwater

Off-site up gradient stormwater generally consists of sheet flow from the adjacent properties and intermittent flow in the existing drainageways flowing across the tract.

The existing drainageway are protected by stream buffers.

Any flows intercepted onsite will be directed to the onsite controls prior to release to the drainageways.

ATTACHMENT K – BMPs for On-Site Stormwater

Permanent measures to capture and treat the required volumes of storm water runoff associated with the proposed school consist of a batch detention pond and vegetated filter strips designed in accordance with TCEQ's requirements including the Optional Enhanced Measures in RG-348 Appendix A.

ATTACHMENT L – BMPs for Surface Streams

As previously described, all site developed flows will be routed to the onsite BMPs prior to discharge into the existing intermittent drainageways on site. In accordance with the enhanced measures requirement, the peak 2-year release rate is less than 50% of the peak existing 2-year release rate. This helps to minimize streambank erosion of downstream surface streams.

ATTACHMENT M – Construction Plans

Construction plans are included with this application.

ATTACHMENT N:

Inspection, Maintenance, Repair and Retrofit Plan

PROJECT NAME: Dripping Springs Elementary School No. 6

Batch Detention Pond:

Inspections. Inspections should be conducted a minimum of twice a year. One inspection should take place during wet weather to determine if the basin is meeting the target detention time of 12 hours and a drawdown time of no more than 48 hours. The remaining inspections should occur between storm events so that manual operation of the valve and controller can be verified. The level sensor in the basin should be inspected and any debris or sediment in the area should be removed. The outlet structure and the trash screen should be inspected for signs of clogging. Debris and sediment should be removed from the orifice and outlet(s) as described below. Debris obstructing the valve should be removed. During each inspection, erosion areas inside and downstream of this BMP should be identified and repaired/revegetated immediately.

Mowing: The basin, basin side-slopes, and embankment of the basin must be mowed to prevent woody growth and control weeds. A mulching mower should be used, or the grass clippings should be caught and removed. Mowing should take place at least twice a year, or more frequently if vegetation exceeds 18 inches in height. More frequent mowing to maintain aesthetic appeal may be necessary in landscaped areas.

Litter and Debris Removal: Litter and debris removal should take place at least twice a year, as part of the periodic mowing operations and inspections. Debris and litter should be removed from the surface of the basin. Particular attention should be paid to floatable debris around the outlet structure. The outlet should be checked for possible clogging or obstructions and any debris removed.

Erosion Control: The basin side slopes and embankment all may periodically suffer from slumping and erosion. To correct these problems, corrective action, such as regarding and revegetation, may be necessary. Correction of erosion control should take place whenever required based on the periodic inspections.

Nuisance Control: Standing water or soggy conditions may occur in the basin. Some standing water may occur after a storm event since the valve may close with 2 to 3 inches of water in the basin. Some flow into the basin may also occur between storms due to spring flow and residential water use that enters the storm sewer system. Twice a year, the facility should be evaluated in terms of nuisance control (insects, weeds, odors, algae, etc.).

Structural Repairs and Replacement: With each inspection, any damage to structural elements of the basin (pipes, concrete drainage structures, retaining walls, etc.) should be identified and repaired immediately. An example of this type of repair can include patching of cracked concrete, sealing of voids, removal of revegetation from cracks and joints. The various inlet/outlet structures in a basin will eventually deteriorate and must be replaced.

Sediment Removal: A properly designed batch detention basin will accumulate quantities of sediment over time. The accumulated sediment can detract from the appearance of the facility and reduce the pollutant removal performance of the facility. The sediment also tends to accumulate near the outlet structure and can interfere with the level sensor operation. Sediment shall be removed from the basin at least every 5 years, when sediment depth exceeds 6 inches, when the sediment interferes with the level sensor or when the basin does not drain within 48 hours. Care should be taken not to compromise the basin lining during maintenance.

Logic Controller. The Logic Controller should be inspected as part of the twice-yearly investigations. Verify that the external indicators (active, cycle in progress) are operating properly by turning the controller off and on, and by initiating a cycle by triggering the level sensor in the basin. The valve should be manually opened and closed using the open/close switch to verify valve operation and to assist in inspecting the valve for debris. The solar panel should be inspected and any dust or debris on the panel should be carefully removed. The controller and all other circuitry and wiring should be inspected for signs of corrosion, damage from insects, water leaks, or other damage. At the end of the inspection, the controller should be reset.

Vegetated Filter Strips:

Once a vegetated area is well established, little additional maintenance is generally necessary. The key to establishing a viable vegetated feature is the care and maintenance it receives in the first few months after it is planted. Once established, all vegetated BMPs require some basic maintenance to insure the health of the plants including:

Seasonal Mowing and Lawn Care: If the filter strip is made up of turf grass, it should be mowed as needed to limit vegetation height to 18 inches, using a mulching mower (or removal of clippings). If native grasses are used, the filter may require less frequent mowing, but a minimum of twice annually. Grass clippings and brush debris should not be deposited on vegetated filter strip areas. Regular mowing should also include weed control practices, however herbicide use should be kept to a minimum (Urbonas et al., 1992). Healthy grass can be maintained without using fertilizers because runoff usually contains sufficient nutrients. Irrigation of the site can help assure a dense and healthy vegetative cover.

Inspection: Inspect filter strips at least twice annually for erosion or damage to vegetation; however, additional inspection after periods of heavy runoff is most desirable. The strip should be checked for uniformity of grass cover, debris and litter, and areas of sediment accumulation. More frequent inspections of the grass cover during the first few years after establishment will help to determine if any problems are developing, and to plan for long-term restorative maintenance needs. Bare spots and areas of erosion identified during semi-annual inspections must be replanted and restored to meet specifications. Construction of a level spreader device may be necessary to reestablish shallow overland flow.

Debris and Litter Removal: Trash tends to accumulate in vegetated areas, particularly along highways. Any filter strip structures (i.e. level spreaders) should be kept free of obstructions to reduce floatables being flushed downstream, and for aesthetic reasons. The need for this practice is determined through periodic inspection, but should be performed no less than 4 times per year.

Sediment Removal: Sediment removal is not normally required in filter strips, since the vegetation normally grows through it and binds it to the soil. However, sediment may accumulate along the upstream boundary of the strip preventing uniform overland flow. Excess sediment should be removed by hand or with flat-bottomed shovels.

Grass Reseeding and Mulching: A healthy dense grass should be maintained on the filter strip. If areas are eroded, they should be filled, compacted, and reseeded so that the final grade is level. Grass damaged during the sediment removal process should be promptly replaced using the same seed mix used during filter strip establishment. If possible, flow should be diverted from the damaged areas until the grass is firmly established. Bare spots and areas of erosion identified during semi-annual inspections must be replanted and restored to meet specifications. Corrective maintenance, such as weeding or replanting should be done more frequently in the first two to three years after installation to ensure stabilization. Dense vegetation may require irrigation immediately after planting, and during particularly dry periods, particularly as the vegetation is initially established.

Responsible Party: Clint Pruett
(Name Printed)

Entity: DRIPPING SPRINGS ISD

Mailing Address: 510 W. MERCER STREET

City, State: DRIPPING SPRINGS, TX Zip Code: 78620

Telephone: 512-858-3013



Signature of Responsible Party

12-19-2023
Date

ATTACHMENT P – Measures for Minimizing Surface Stream Contamination

In order to avoid or minimize surface stream contamination, storm water runoff from the site will be routed through the proposed water quality pond and vegetated filter strips prior to any discharge to the existing intermittent drainageways on site. The improvements are not expected to change the way water enters surface streams.

Temporary Stormwater Section

Texas Commission on Environmental Quality

for Regulated Activities on the Edwards Aquifer Recharge Zone and Relating to 30 TAC §213.5(b)(4)(A), (B), (D)(I) and (G); Effective June 1, 1999

To ensure that the application is administratively complete, confirm that all fields in the form are complete, verify that all requested information is provided, consistently reference the same site and contact person in all forms in the application, and ensure forms are signed by the appropriate party.

Note: Including all the information requested in the form and attachments contributes to more streamlined technical reviews.

Signature

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. This **Temporary Stormwater Section** is hereby submitted for TCEQ review and executive director approval. The application was prepared by:

Print Name of Customer/Agent: Elias Haddad, P.E

Date: 9/13/2023

Signature of Customer/Agent:



Regulated Entity Name: Drippins Springs ISD New Elementary School No. 6

Project Information

Potential Sources of Contamination

Examples: Fuel storage and use, chemical storage and use, use of asphaltic products, construction vehicles tracking onto public roads, and existing solid waste.

1. Fuels for construction equipment and hazardous substances which will be used during construction:

The following fuels and/or hazardous substances will be stored on the site: N/A

These fuels and/or hazardous substances will be stored in:

- Aboveground storage tanks with a cumulative storage capacity of less than 250 gallons will be stored on the site for less than one (1) year.

- Aboveground storage tanks with a cumulative storage capacity between 250 gallons and 499 gallons will be stored on the site for less than one (1) year.
- Aboveground storage tanks with a cumulative storage capacity of 500 gallons or more will be stored on the site. An Aboveground Storage Tank Facility Plan application must be submitted to the appropriate regional office of the TCEQ prior to moving the tanks onto the project.
- Fuels and hazardous substances will not be stored on the site.
- 2. **Attachment A - Spill Response Actions.** A site specific description of the measures to be taken to contain any spill of hydrocarbons or hazardous substances is attached.
- 3. Temporary aboveground storage tank systems of 250 gallons or more cumulative storage capacity must be located a minimum horizontal distance of 150 feet from any domestic, industrial, irrigation, or public water supply well, or other sensitive feature.
- 4. **Attachment B - Potential Sources of Contamination.** A description of any activities or processes which may be a potential source of contamination affecting surface water quality is attached.

Sequence of Construction

- 5. **Attachment C - Sequence of Major Activities.** A description of the sequence of major activities which will disturb soils for major portions of the site (grubbing, excavation, grading, utilities, and infrastructure installation) is attached.
 - For each activity described, an estimate (in acres) of the total area of the site to be disturbed by each activity is given.
 - For each activity described, include a description of appropriate temporary control measures and the general timing (or sequence) during the construction process that the measures will be implemented.
- 6. Name the receiving water(s) at or near the site which will be disturbed or which will receive discharges from disturbed areas of the project: Small Barton Creek

Temporary Best Management Practices (TBMPs)

Erosion control examples: tree protection, interceptor swales, level spreaders, outlet stabilization, blankets or matting, mulch, and sod. Sediment control examples: stabilized construction exit, silt fence, filter dikes, rock berms, buffer strips, sediment traps, and sediment basins. Please refer to the Technical Guidance Manual for guidelines and specifications. All structural BMPs must be shown on the site plan.

- 7. **Attachment D – Temporary Best Management Practices and Measures.** TBMPs and measures will prevent pollution of surface water, groundwater, and stormwater. The construction-phase BMPs for erosion and sediment controls have been designed to retain sediment on site to the extent practicable. The following information is attached:

- A description of how BMPs and measures will prevent pollution of surface water, groundwater or stormwater that originates upgradient from the site and flows across the site.
 - A description of how BMPs and measures will prevent pollution of surface water or groundwater that originates on-site or flows off site, including pollution caused by contaminated stormwater runoff from the site.
 - A description of how BMPs and measures will prevent pollutants from entering surface streams, sensitive features, or the aquifer.
 - A description of how, to the maximum extent practicable, BMPs and measures will maintain flow to naturally-occurring sensitive features identified in either the geologic assessment, TCEQ inspections, or during excavation, blasting, or construction.
8. The temporary sealing of a naturally-occurring sensitive feature which accepts recharge to the Edwards Aquifer as a temporary pollution abatement measure during active construction should be avoided.
- Attachment E - Request to Temporarily Seal a Feature.** A request to temporarily seal a feature is attached. The request includes justification as to why no reasonable and practicable alternative exists for each feature.
 - There will be no temporary sealing of naturally-occurring sensitive features on the site.
9. **Attachment F - Structural Practices.** A description of the structural practices that will be used to divert flows away from exposed soils, to store flows, or to otherwise limit runoff discharge of pollutants from exposed areas of the site is attached. Placement of structural practices in floodplains has been avoided.
10. **Attachment G - Drainage Area Map.** A drainage area map supporting the following requirements is attached:
- For areas that will have more than 10 acres within a common drainage area disturbed at one time, a sediment basin will be provided.
 - For areas that will have more than 10 acres within a common drainage area disturbed at one time, a smaller sediment basin and/or sediment trap(s) will be used.
 - For areas that will have more than 10 acres within a common drainage area disturbed at one time, a sediment basin or other equivalent controls are not attainable, but other TBMPs and measures will be used in combination to protect down slope and side slope boundaries of the construction area.
 - There are no areas greater than 10 acres within a common drainage area that will be disturbed at one time. A smaller sediment basin and/or sediment trap(s) will be used in combination with other erosion and sediment controls within each disturbed drainage area.

- There are no areas greater than 10 acres within a common drainage area that will be disturbed at one time. Erosion and sediment controls other than sediment basins or sediment traps within each disturbed drainage area will be used.
11. **Attachment H - Temporary Sediment Pond(s) Plans and Calculations.** Temporary sediment pond or basin construction plans and design calculations for a proposed temporary BMP or measure have been prepared by or under the direct supervision of a Texas Licensed Professional Engineer. All construction plans and design information must be signed, sealed, and dated by the Texas Licensed Professional Engineer. Construction plans for the proposed temporary BMPs and measures are attached.
- N/A
12. **Attachment I - Inspection and Maintenance for BMPs.** A plan for the inspection of each temporary BMP(s) and measure(s) and for their timely maintenance, repairs, and, if necessary, retrofit is attached. A description of the documentation procedures, recordkeeping practices, and inspection frequency are included in the plan and are specific to the site and/or BMP.
13. All control measures must be properly selected, installed, and maintained in accordance with the manufacturer's specifications and good engineering practices. If periodic inspections by the applicant or the executive director, or other information indicate a control has been used inappropriately, or incorrectly, the applicant must replace or modify the control for site situations.
14. If sediment escapes the construction site, off-site accumulations of sediment must be removed at a frequency sufficient to minimize offsite impacts to water quality (e.g., fugitive sediment in street being washed into surface streams or sensitive features by the next rain).
15. Sediment must be removed from sediment traps or sedimentation ponds not later than when design capacity has been reduced by 50%. A permanent stake will be provided that can indicate when the sediment occupies 50% of the basin volume.
16. Litter, construction debris, and construction chemicals exposed to stormwater shall be prevented from becoming a pollutant source for stormwater discharges (e.g., screening outfalls, picked up daily).

Soil Stabilization Practices

Examples: establishment of temporary vegetation, establishment of permanent vegetation, mulching, geotextiles, sod stabilization, vegetative buffer strips, protection of trees, or preservation of mature vegetation.

17. **Attachment J - Schedule of Interim and Permanent Soil Stabilization Practices.** A schedule of the interim and permanent soil stabilization practices for the site is attached.

18. Records must be kept at the site of the dates when major grading activities occur, the dates when construction activities temporarily or permanently cease on a portion of the site, and the dates when stabilization measures are initiated.
19. Stabilization practices must be initiated as soon as practicable where construction activities have temporarily or permanently ceased.

Administrative Information

20. All structural controls will be inspected and maintained according to the submitted and approved operation and maintenance plan for the project.
21. If any geologic or manmade features, such as caves, faults, sinkholes, etc., are discovered, all regulated activities near the feature will be immediately suspended. The appropriate TCEQ Regional Office shall be immediately notified. Regulated activities must cease and not continue until the TCEQ has reviewed and approved the methods proposed to protect the aquifer from any adverse impacts.
22. Silt fences, diversion berms, and other temporary erosion and sediment controls will be constructed and maintained as appropriate to prevent pollutants from entering sensitive features discovered during construction.

ATTACHMENT A

CONTRACTOR IS RESPONSIBLE FOR ADEQUATE CLEANUP OF ANY SPILLS DURING CONSTRUCTION.

CONTRACTOR SHALL HAVE PERSONNEL ONSITE WHO ARE KNOWLEDGEABLE AND TRAINED TO PERFORM THE SPILL RESPONSE ACTIONS.

SMALL SPILL RESPONSE

BELOW ARE GENERAL STEPS AND MATERIALS TO BE USED FOR CLEANUP.

- 1) IDENTIFYING THE SUBSTANCE & DETERMINING THE RISK BASED ON THE MATERIAL SAFETY DATA SHEETS
- 2) ISOLATING THE AREA OF THE SPILL
- 3) PROTECTING PERSONNEL AND CLEANUP PERSONNEL (Personal Protective Equipment as necessary, goggles, gloves)
- 4) STOPPING THE SPILL AT THE SOURCE
- 5) CONTAINING THE SPILL: Utilizing the correct sorbents to dam or divert the spill for clean up.
- 6) CLEANING UP THE SPILL: Utilizing the proper containers, bags, shovels and other tools, sawdust, sorbent pads, socks, and pillows as needed.

SPILL RESPONSE ACTIONS

Responsibility for adequate cleanup of any chemical spills during construction will be placed on the contractor. The contractor will notify TCEQ of any chemical spills as required at (512) 339-2929.

Reportable quantities as defined by 30 TAC Chapter 327 are as follows:

(a) Hazardous substances. The reportable quantities for hazardous substances shall be:

- (1) for spills or discharges onto land--the quantity designated as the Final Reportable Quantity (RQ) in Table 302.4 in 40 CFR §302.4; or

(2) for spills or discharges into waters in the state--the quantity designated as the Final RQ in Table 302.4 in 40 CFR §302.4, except where the Final RQ is greater than 100 pounds in which case the RQ shall be 100 pounds.

(b) Oil, petroleum product, and used oil.

(1) The RQ for crude oil and oil other than that defined as petroleum product or used oil shall be:

(A) for spills or discharges onto land--210 gallons (five barrels); or

(B) for spills or discharges directly into water in the state--quantity sufficient to create a sheen.

(2) The RQ for petroleum product and used oil shall be:

(A) except as noted in subparagraph (B) of this paragraph, for spills or discharges onto land--25 gallons;

(B) for spills or discharges to land from PST exempted facilities--210 gallons (five barrels); or

(C) for spills or discharges directly into water in the state--quantity sufficient to create a sheen.

(c) Industrial solid waste or other substances. The RQ for spills or discharges into water in the state shall be 100 pounds.

ATTACHMENT B – POTENTIAL SOURCES OF CONTAMINATION

Some potential sources of contamination are as follows: construction vehicles tracking onto public roads, existing solid waste, and other vehicle contaminants (i.e., fuel, oil, lubricants, etc.). Refer to Attachment A for Spill Response Actions.

ATTACHMENT C – SEQUENCE OF MAJOR ACTIVITIES

1. Install Erosion controls.
2. Start excavation of temporary sediment pond (1 acre).
3. Start rough grading of access roads and site (17.5 acres).
4. Start underground utility installation (within disturbed 17.5 acres).
5. Start construction of building, drives, and parking lot (within disturbed 17.5 acres).
6. Finalize construction of pond and vegetated filter strips (within disturbed 17.5 acres).
7. Restore disturbed areas, place top soil, install permanent vegetation (entire disturbed areas outside building and pavement improvements).

ATTACHMENT D – TEMPORARY BEST MANAGEMENT PRACTICES AND MEASURES

The disturbed areas will drain to one of the existing drainageways on site.

Stabilized construction entrance/exit, concrete clean out area, silt fence, rock berm and inlet protection will be installed to protect these drainageways. During construction, these BMPs are to be inspected weekly and after any rainfall.

These TBMPs will provide temporary runoff detention, velocity reduction, and settlement of sediment.

Silt fence and rock berms will prevent pollutants from entering existing surface streams.

There are no naturally-occurring sensitive features identified onsite.

ATTACHMENT F – STRUCTURAL PRACTICES

Structural practices consist of the use of silt fence, rock berms, and inlet protection as previously described.

ATTACHMENT G – DRAINAGE AREA MAP

Drainage area map showing the proposed work is included.

ATTACHMENT H – TEMPORARY SEDIMENT POND(S) PLANS AND CALCULATIONS

The water quality pond will be used as a temporary sediment basin during construction. Per RG-348A, the capture volume for Hays County is 8,000 cf/ac which equates to 108,000 cf for the pond drainage area of 13.5 ac (PR 1). See the enclosed Pond Plan and Pond Details sheets for additional information.

ATTACHMENT I INSPECTION AND MAINTENANCE FOR BMPs

The contractor is required to inspect the controls and fences at weekly intervals and after significant rainfall events to ensure that they are functioning properly. Inspections are to be documented in an inspection report which will document maintenance activities, sediment removal and modifications to the sediment and erosion controls. The person(s) responsible for maintenance of controls and fences shall immediately make the necessary repairs to any damaged areas. Silt accumulation at controls must be removed when the depth reaches six inches.

Silt Fence:

- (1) Inspect all fencing weekly, and after any rainfall.
- (2) Remove sediment when buildup reaches 6 inches.
- (3) Replace any torn fabric or install a second line of fencing parallel to the torn section.
- (4) Replace or repair any sections crushed or collapsed in the course of construction activity. If a section of fence is obstructing vehicular access, consider relocating it to a spot where it will provide equal protection, but will not obstruct vehicles. A triangular filter dike may be preferable to a silt fence at common vehicle access points.
- (5) When construction is complete, the sediment should be disposed of in a manner that will not cause additional siltation and the prior location of the silt fence should be revegetated. The fence itself should be disposed of in an approved landfill.

Rock Berm:

- (1) Inspection should be made weekly and after each rainfall by the responsible party. For installations in streambeds, additional daily inspections should be made.
- (2) Remove sediment and other debris when buildup reaches 6 inches and dispose of the accumulated silt in an approved manner that will not cause any additional siltation.
- (3) Repair any loose wire sheathing.
- (4) The berm should be reshaped as needed during inspection.
- (5) The berm should be replaced when the structure ceases to function as intended due to silt accumulation among the rocks, washout, construction traffic damage, etc.
- (6) The rock berm should be left in place until all upstream areas are stabilized and accumulated silt removed.

Stabilized Construction Entrance/Exit:

- (1) The entrance should be maintained in a condition, which will prevent tracking or flowing of sediment onto public rights-of-way. This may require periodic top dressing with additional stone as conditions demand and repair and/or cleanout of any measures used to trap sediment.
- (2) All sediment spilled, dropped, washed or tracked onto public rights-of-way should be removed immediately by contractor.

- (3) When necessary, wheels should be cleaned to remove sediment prior to entrance onto public right-of-way.
- (4) When washing is required, it should be done on an area stabilized with crushed stone that drains into an approved sediment trap or sediment basin.
- (5) All sediment should be prevented from entering any storm drain, ditch or water course by using approved methods.

Sediment Basins

- (1) Inspection should be made weekly and after each rainfall. Check the embankment, spillways, and outlet for erosion damage, and inspect the embankment for piping and settlement. Repair should be made promptly as needed by the contractor.
- (2) Trash and other debris should be removed after each rainfall to prevent clogging of the outlet structure.
- (3) Accumulated silt should be removed and the basin should be re-graded to its original dimensions at such point that the capacity of the impoundment has been reduced to 75% of its original storage capacity.
- (4) The removed sediment should be stockpiled or redistributed in areas that are protected from erosion.

Concrete Clean Out Areas

When temporary concrete washout facilities are no longer required for the work, the hardened concrete should be removed and disposed of. Materials used to construct temporary concrete washout facilities should be removed from the site of the work and disposed of. Holes, depressions or other ground disturbance caused by the removal of the temporary concrete washout facilities should be backfilled and repaired.

ATTACHMENT J – SCHEDULE OF INTERIM AND PERMANENT SOIL STABILIZATION PRACTICES

1. From September 15 to March 1, seeding shall be with cool season cover crops (wheat at 0.5 pounds per 1000 sf, oats at 0.5 pounds per 1000 sf, cereal rye grain at 0.5 pounds per 1000 sf) with a total rate of 1.5 pounds per 1000 sf. Cool season cover crops are not permanent erosion control.

2. From March 2 to September 14, seeding shall be with hulled bermuda at a rate of 1 pounds per 1000 sf.
 - a. Fertilizer shall be water soluble with an analysis of 15-15-15 to be applied once at planting and once during the period of establishment at a rate of 1/2 pound per 1000 sf.

 - b. Hydromulch shall comply with table below.

 - c. Temporary erosion control shall be acceptable when the grass has grown at least 1 1/2 inches high with 95% coverage, provided no bare spots larger than 16 square feet exist.

 - d. When required, native grass seeding shall comply with requirements of the City of Austin Environmental Criteria Manual (as adopted by the City of Dripping Springs).

Material	Description	Longevity	Typical Applications	Application Rate
100% or any blend of wood, cellulose, straw, and/or cotton plant material (except no mulch shall exceed 30% paper).	71% or greater woods/straw 30% or less paper or natural fibers.	0-3 months	Moderate slopes; from flat to 3:1.	1500 to 2000 lbs per acre.

If portions of the site will have a temporary or permanent cease in construction activity lasting longer than 14 days, soil stabilization in those areas shall be initiated as soon as possible prior to the 14th day of inactivity. If activity will resume prior to the 21st day, stabilization measures are not required. If drought conditions or inclement weather prevent action by the 14th day, stabilization measures shall be initiated as soon as possible.

ATTACHMENT D – NOTICE OF INTENT (NOI)

The NOI will be submitted by the contractor prior to start of construction.

SIGNATURE PAGE:

Clint Pruett
Applicant's Signature

7-25-2023
Date

THE STATE OF Texas §

County of Hays §


BEFORE ME, the undersigned authority, on this day personally appeared Clint Pruett known to me to be the person whose name is subscribed to the foregoing instrument, and acknowledged to me that (s)he executed same for the purpose and consideration therein expressed.

GIVEN under my hand and seal of office on this 25 day of July, 2023

Jennifer Eileen Martinez
NOTARY PUBLIC

Jennifer Eileen Martinez
Typed or Printed Name of Notary

MY COMMISSION EXPIRES: Dec 14, 2026



Application Fee Form

Texas Commission on Environmental Quality

Name of Proposed Regulated Entity: Dripping Springs ISD New Elementary School No. 6

Regulated Entity Location: West of Headwaters Subdivision, Dripping Springs.

Name of Customer: Dripping Springs ISD

Contact Person: Clint Pruett

Phone: 512-858-3032

Customer Reference Number (if issued): CN CN 601259435

Regulated Entity Reference Number (if issued): RN _____

Austin Regional Office (3373)

Hays

Travis

Williamson

San Antonio Regional Office (3362)

Bexar

Medina

Uvalde

Comal

Kinney

Application fees must be paid by check, certified check, or money order, payable to the **Texas Commission on Environmental Quality**. Your canceled check will serve as your receipt. **This form must be submitted with your fee payment.** This payment is being submitted to:

Austin Regional Office

San Antonio Regional Office

Mailed to: TCEQ - Cashier

Overnight Delivery to: TCEQ - Cashier

Revenues Section

Mail Code 214

P.O. Box 13088

Austin, TX 78711-3088

12100 Park 35 Circle

Building A, 3rd Floor

Austin, TX 78753

(512)239-0357

Site Location (Check All That Apply):

Recharge Zone

Contributing Zone

Transition Zone

<i>Type of Plan</i>	<i>Size</i>	<i>Fee Due</i>
Water Pollution Abatement Plan, Contributing Zone Plan: One Single Family Residential Dwelling	Acres	\$
Water Pollution Abatement Plan, Contributing Zone Plan: Multiple Single Family Residential and Parks	Acres	\$
Water Pollution Abatement Plan, Contributing Zone Plan: Non-residential	64.52 Acres	\$ 8,000
Sewage Collection System	L.F.	\$
Lift Stations without sewer lines	Acres	\$
Underground or Aboveground Storage Tank Facility	Tanks	\$
Piping System(s)(only)	Each	\$
Exception	Each	\$
Extension of Time	Each	\$

Signature: _____ 

Date: 9/15/2023

Application Fee Schedule

Texas Commission on Environmental Quality

Edwards Aquifer Protection Program 30 TAC Chapter 213 (effective 05/01/2008)

Water Pollution Abatement Plans and Modifications

Contributing Zone Plans and Modifications

<i>Project</i>	<i>Project Area in Acres</i>	<i>Fee</i>
One Single Family Residential Dwelling	< 5	\$650
Multiple Single Family Residential and Parks	< 5	\$1,500
	5 < 10	\$3,000
	10 < 40	\$4,000
	40 < 100	\$6,500
	100 < 500	\$8,000
	≥ 500	\$10,000
Non-residential (Commercial, industrial, institutional, multi-family residential, schools, and other sites where regulated activities will occur)	< 1	\$3,000
	1 < 5	\$4,000
	5 < 10	\$5,000
	10 < 40	\$6,500
	40 < 100	\$8,000
	≥ 100	\$10,000

Organized Sewage Collection Systems and Modifications

<i>Project</i>	<i>Cost per Linear Foot</i>	<i>Minimum Fee- Maximum Fee</i>
Sewage Collection Systems	\$0.50	\$650 - \$6,500

Underground and Aboveground Storage Tank System Facility Plans and Modifications

<i>Project</i>	<i>Cost per Tank or Piping System</i>	<i>Minimum Fee- Maximum Fee</i>
Underground and Aboveground Storage Tank Facility	\$650	\$650 - \$6,500

Exception Requests

<i>Project</i>	<i>Fee</i>
Exception Request	\$500

Extension of Time Requests

<i>Project</i>	<i>Fee</i>
Extension of Time Request	\$150



TCEQ Core Data Form

For detailed instructions on completing this form, please read the Core Data Form Instructions or call 512-239-5175.

SECTION I: General Information

1. Reason for Submission (If other is checked please describe in space provided.)		
<input checked="" type="checkbox"/> New Permit, Registration or Authorization (Core Data Form should be submitted with the program application.)		
<input type="checkbox"/> Renewal (Core Data Form should be submitted with the renewal form)	<input type="checkbox"/> Other	
2. Customer Reference Number (if issued)	Follow this link to search for CN or RN numbers in Central Registry**	3. Regulated Entity Reference Number (if issued)
CN 601259435		RN

SECTION II: Customer Information

4. General Customer Information		5. Effective Date for Customer Information Updates (mm/dd/yyyy)	
<input type="checkbox"/> New Customer <input type="checkbox"/> Update to Customer Information <input type="checkbox"/> Change in Regulated Entity Ownership <input type="checkbox"/> Change in Legal Name (Verifiable with the Texas Secretary of State or Texas Comptroller of Public Accounts)			
<i>The Customer Name submitted here may be updated automatically based on what is current and active with the Texas Secretary of State (SOS) or Texas Comptroller of Public Accounts (CPA).</i>			
6. Customer Legal Name (If an individual, print last name first: eg: Doe, John)		<i>If new Customer, enter previous Customer below:</i>	
Dripping Springs ISD			
7. TX SOS/CPA Filing Number	8. TX State Tax ID (11 digits)	9. Federal Tax ID (9 digits) 74-600309	10. DUNS Number (if applicable)
11. Type of Customer:	<input type="checkbox"/> Corporation	<input type="checkbox"/> Individual	Partnership: <input type="checkbox"/> General <input type="checkbox"/> Limited
Government: <input type="checkbox"/> City <input type="checkbox"/> County <input type="checkbox"/> Federal <input type="checkbox"/> Local <input type="checkbox"/> State <input checked="" type="checkbox"/> Other	<input type="checkbox"/> Sole Proprietorship	<input type="checkbox"/> Other:	
12. Number of Employees		13. Independently Owned and Operated?	
<input type="checkbox"/> 0-20 <input type="checkbox"/> 21-100 <input type="checkbox"/> 101-250 <input type="checkbox"/> 251-500 <input checked="" type="checkbox"/> 501 and higher		<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	
14. Customer Role (Proposed or Actual) – as it relates to the Regulated Entity listed on this form. Please check one of the following			
<input type="checkbox"/> Owner <input type="checkbox"/> Operator <input checked="" type="checkbox"/> Owner & Operator <input type="checkbox"/> Other: <input type="checkbox"/> Occupational Licensee <input type="checkbox"/> Responsible Party <input type="checkbox"/> VCP/BSA Applicant			
15. Mailing Address:			
PO Box 479 410 W. Mercer St			
City	Dripping Springs	State	TX
ZIP	78620	ZIP + 4	
16. Country Mailing Information (if outside USA)		17. E-Mail Address (if applicable)	
18. Telephone Number	19. Extension or Code	20. Fax Number (if applicable)	

SECTION III: Regulated Entity Information

21. General Regulated Entity Information <i>(If 'New Regulated Entity' is selected, a new permit application is also required.)</i>							
<input checked="" type="checkbox"/> New Regulated Entity <input type="checkbox"/> Update to Regulated Entity Name <input type="checkbox"/> Update to Regulated Entity Information							
<i>The Regulated Entity Name submitted may be updated, in order to meet TCEQ Core Data Standards (removal of organizational endings such as Inc, LP, or LLC).</i>							
22. Regulated Entity Name <i>(Enter name of the site where the regulated action is taking place.)</i>							
Dripping Springs ISD Elementary School No. 6							
23. Street Address of the Regulated Entity: <i>(No PO Boxes)</i>							
City	Dripping Springs	State	TX	ZIP	78620	ZIP + 4	
24. County	Hays						

If no Street Address is provided, fields 25-28 are required.

25. Description to Physical Location:		West of Headwaters subdivision, taking access from Mira Vista Drive					
26. Nearest City				State		Nearest ZIP Code	
Dripping Springs				TX		78620	
<i>Latitude/Longitude are required and may be added/updated to meet TCEQ Core Data Standards. (Geocoding of the Physical Address may be used to supply coordinates where none have been provided or to gain accuracy).</i>							
27. Latitude (N) In Decimal:			28. Longitude (W) In Decimal:				
Degrees	Minutes	Seconds	Degrees	Minutes	Seconds		
30	12	32.	98	3	31.		
29. Primary SIC Code (4 digits)		30. Secondary SIC Code (4 digits)		31. Primary NAICS Code (5 or 6 digits)		32. Secondary NAICS Code (5 or 6 digits)	
8211				611110			
33. What is the Primary Business of this entity? <i>(Do not repeat the SIC or NAICS description.)</i>							
K-8 Educational Institution							
34. Mailing Address:		N/A					
City		State		ZIP		ZIP + 4	
35. E-Mail Address:							
36. Telephone Number			37. Extension or Code			38. Fax Number <i>(if applicable)</i>	
() -						() -	

39. TCEQ Programs and ID Numbers Check all Programs and write in the permits/registration numbers that will be affected by the updates submitted on this form. See the Core Data Form instructions for additional guidance.

<input type="checkbox"/> Dam Safety	<input type="checkbox"/> Districts	<input checked="" type="checkbox"/> Edwards Aquifer	<input type="checkbox"/> Emissions Inventory Air	<input type="checkbox"/> Industrial Hazardous Waste
<input type="checkbox"/> Municipal Solid Waste	<input type="checkbox"/> New Source Review Air	<input type="checkbox"/> OSSF	<input type="checkbox"/> Petroleum Storage Tank	<input type="checkbox"/> PWS
<input type="checkbox"/> Sludge	<input type="checkbox"/> Storm Water	<input type="checkbox"/> Title V Air	<input type="checkbox"/> Tires	<input type="checkbox"/> Used Oil
<input type="checkbox"/> Voluntary Cleanup	<input type="checkbox"/> Wastewater	<input type="checkbox"/> Wastewater Agriculture	<input type="checkbox"/> Water Rights	<input type="checkbox"/> Other:



SECTION IV: Preparer Information

40. Name:	Elias Haddad, PE	41. Title:	Client Manager
42. Telephone Number	43. Ext./Code	44. Fax Number	45. E-Mail Address
(512) 382-0021		() -	ehaddad@walkerpartners.com

SECTION V: Authorized Signature

46. By my signature below, I certify, to the best of my knowledge, that the information provided in this form is true and complete, and that I have signature authority to submit this form on behalf of the entity specified in Section II, Field 6 and/or as required for the updates to the ID numbers identified in field 39.

Company:	Walker Partners	Job Title:	Client Manager
Name (In Print):	Elias Haddad	Phone:	(512) 382- 0021
Signature:		Date:	8/23/2023



HEC-HMS HYDROLOGIC SUMMARY							
DRAINAGE AREA	AREA (AC)	CN	IMPERVIOUS (%)	LAG TIME (MIN)	Q2 (CFS)	Q25 (CFS)	Q100 (CFS)
EX 1	19.1	80	0.0	5.6	55.3	107.4	202.2
EX 2	45.5	80	0.0	8.4	115.1	225.3	426.2
EX OUT	>	>	>	>	166.1	323.2	432.1
PR 1	13.5	80	70.0	3.0	65.6	106.2	133.5
POND (Q OUT)	>	>	>	>	17.0	46.4	71.2
PR 2	14.6	80	3.5	6.5	41.4	80.1	106.4
PR 3	36.5	80	3.5	8.4	94.4	182.5	242.5
OEM (SEE NOTE 4)	13.5	80	0.0	6.8	36.7		
PR OUT	>	>	>	>	149.8	303.7	414.8

NOTES:
 1) EX OUT = EX 1 + EX 2
 2) PR OUT = POND + PR 2 + PR 3
 3) PR OUT < EX OUT
 4) OEM = PR1 (UNDEV) - COMPLIANCE W/ TCEQ RG-348, APP A, SEC 5 (Q2 EXITTING POND < 50% UNDEV) [17.0 CFS < 18.35 CFS]




Tc Calculations (SCS Unit Hydrograph Model)

AREA No.	Sheet Flow				Shallow Concentrated Flow				Open Channel Flow				Total Tc (minimum 5 min)		T lag							
	L (ft)	n	s (ft/ft)	P ₂ (in)	t _{sheet} min	L (ft)	Surface s (ft/ft)	V (fps)	t _{shallow} min	L (ft)	n	s (ft/ft)	R (ft)	V (fps)		t _{channel} min	min	hrs				
EX 1	100	0.15	0.0500	4.06	6.03	165	Unpaved 0.0700	4.27	0.64	0	Unpaved 0.0100	1.61	0.00	1600	0.03	0.0400	1.00	9.93	2.68	9.36	0.16	5.6
EX 2	100	0.15	0.0750	4.06	5.13	520	Unpaved 0.1100	5.35	1.62	0	Unpaved 0.0100	1.61	0.00	2550	0.03	0.0140	1.00	5.88	7.23	13.98	0.23	8.4
PR 1	0	0.15	0.0200	4.06	0.00	0	Unpaved 0.0100	1.61	0.00	0	Unpaved 0.0100	1.61	0.00	0	0.15	0.0100	1.00	0.99	0.00	5.00	0.08	3.0
PR 2	100	0.15	0.0200	4.06	8.70	233	Unpaved 0.1350	5.93	0.66	0	Unpaved 0.0100	1.61	0.00	847	0.03	0.0400	1.00	9.93	1.42	10.77	0.18	6.5
PR 3	100	0.15	0.0750	4.06	5.13	520	Unpaved 0.1100	5.35	1.62	0	Unpaved 0.0100	1.61	0.00	2550	0.03	0.0140	1.00	5.88	7.23	13.98	0.23	8.4
OEM	100	0.15	0.0600	4.06	5.61	1070	Unpaved 0.0380	3.15	5.67	0	Unpaved 0.0100	1.61	0.00	0	0.03	0.0140	1.00	5.88	0.00	11.28	0.19	6.8

!!! CAUTION !!!
 EXISTING OVERHEAD UTILITIES IN VICINITY
 CONTRACTOR SHALL EXERCISE EXTREME CAUTION
 WHEN WORKING NEAR ELECTRIC FACILITIES.


!!! WARNING !!!
 THE ENGINEER ASSUMES NO RESPONSIBILITY FOR THE ACCURACY
 OF THE LOCATION OF UNDERGROUND UTILITIES. THE CONTRACTOR
 SHALL BE RESPONSIBLE FOR LOCATION AND AVOIDING ALL
 EXISTING UTILITIES BY CALLING THE "ONE CALL" LOCATOR SERVICE
 AT (800) 344-8377 AT LEAST 48 HOURS PRIOR TO CONSTRUCTION.

"RELEASE OF THIS APPLICATION DOES NOT CONSTITUTE A
 VERIFICATION OF ALL DATA, INFORMATION AND CALCULATIONS
 SUPPLIED BY THE APPLICANT. THE ENGINEER OF RECORD IS SOLELY
 RESPONSIBLE FOR THE COMPLETENESS, ACCURACY AND ADEQUACY
 OF HIS/HER SUBMITTAL. WHETHER OR NOT THE APPLICATION IS
 REVIEWED FOR CODE COMPLIANCE BY CITY ENGINEERS"



HEC-HMS HYDROLOGIC SUMMARY								
DRAINAGE AREA	AREA (AC)	CN	IMPERVIOUS (%)	LAG TIME (MIN)	Q2 (CFS)	Q10 (CFS)	Q25 (CFS)	Q100 (CFS)
EX 1	19.1	80	0.0	5.6	55.3	107.4	142.8	202.2
EX 2	45.5	80	0.0	8.4	115.1	225.3	300.5	426.2
EX OUT	>	>	>	>	166.1	323.2	432.1	614.2
PR 1	13.5	80	70.0	3.0	65.6	106.2	133.5	179.5
POND (Q. OUT)	>	>	>	>	17.0	46.4	71.2	113.1
PR 2	14.6	80	3.5	6.5	41.4	80.1	106.4	150.5
PR 3	36.5	80	3.5	8.4	94.4	182.5	242.5	342.9
OEM (SEE NOTE 4)	13.5	80	0.0	6.8	36.7			
PR OUT	>	>	>	>	149.8	303.7	414.8	598.4

NOTES:
 1) EX OUT = EX 1 + EX 2
 2) PR OUT = POND + PR 2 + PR 3
 3) PR OUT < EX OUT
 4) OEM = PR1 (UNDEV) - COMPLIANCE W/ TCEQ RG-348, APP A, SEC 5 (Q2 EXITING POND < 50% UNDEV) | [17.0 CFS < 18.35 CFS]





Tc Calculations (SCS Unit Hydrograph Model)

AREA No.	Sheet Flow					Shallow Concentrated Flow					Shallow Concentrated Flow					Open Channel Flow					Total Tc (minimum 5 min)		T lag	
	L (ft)	n	s (ft/ft)	P2 (in)	t _{sheet} min	L (ft)	Surface	s (ft/ft)	V (fps)	t _{shallow} min	L (ft)	Surface	s (ft/ft)	V (fps)	t _{shallow} min	L (ft)	n	s (ft/ft)	R	V (fps)	t _{channel} min	min		hrs
EX 1	100	0.15	0.0500	4.06	6.03	165	Unpaved	0.0700	4.27	0.64	0	Unpaved	0.0100	1.61	0.00	1600	0.03	0.0400	1.00	9.93	2.68	9.36	0.16	5.6
EX 2	100	0.15	0.0750	4.06	5.13	520	Unpaved	0.1100	5.35	1.62	0	Unpaved	0.0100	1.61	0.00	2550	0.03	0.0140	1.00	5.88	7.23	13.98	0.23	8.4
PR 1	0	0.15	0.0200	4.06	0.00	0	Unpaved	0.0100	1.61	0.00	0	0.15	0.0100	1.00	0.99	0.00	5.00	0.08	3.0					3.0
PR 2	100	0.15	0.0200	4.06	8.70	233	Unpaved	0.1350	5.93	0.66	0	Unpaved	0.0100	1.61	0.00	847	0.03	0.0400	1.00	9.93	1.42	10.77	0.18	6.5
PR 3	100	0.15	0.0750	4.06	5.13	520	Unpaved	0.1100	5.35	1.62	0	Unpaved	0.0100	1.61	0.00	2550	0.03	0.0140	1.00	5.88	7.23	13.98	0.23	8.4
OEM	100	0.15	0.0600	4.06	5.61	1070	Unpaved	0.0380	3.15	5.67	0	Unpaved	0.0100	1.61	0.00	0	0.03	0.0140	1.00	5.88	0.00	11.28	0.19	6.8

!!! CAUTION !!!
 EXISTING OVERHEAD UTILITIES IN VICINITY OF THE LOCATION OF UNDERGROUND UTILITIES. THE CONTRACTOR SHALL BE RESPONSIBLE FOR LOCATION AND AVOIDING ALL EXISTING UTILITIES BY CALLING THE "ONE CALL" LOCATOR SERVICE AT (800) 344-8377 AT LEAST 48 HOURS PRIOR TO CONSTRUCTION.

!!! WARNING !!!
 THE ENGINEER ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OF THE LOCATION OF UNDERGROUND UTILITIES. THE CONTRACTOR SHALL BE RESPONSIBLE FOR LOCATION AND AVOIDING ALL EXISTING UTILITIES BY CALLING THE "ONE CALL" LOCATOR SERVICE AT (800) 344-8377 AT LEAST 48 HOURS PRIOR TO CONSTRUCTION.

RELEASE OF THIS APPLICATION DOES NOT CONSTITUTE A VERIFICATION OF ALL DATA, INFORMATION AND CALCULATIONS SUPPLIED BY THE APPLICANT. THE ENGINEER OF RECORD IS SOLELY RESPONSIBLE FOR THE COMPLETENESS, ACCURACY AND ADEQUACY OF HIS/HER SUBMITTAL. WHETHER OR NOT THE APPLICATION IS REVIEWED FOR CODE COMPLIANCE BY CITY ENGINEERS.



LEGEND	
	PROPOSED CURB & GUTTER (SEE PLAN FOR WIDTHS)
	PROPOSED CONCRETE SIDEWALK (SEE PLAN FOR WIDTHS)
	L.O.C. LIMITS OF CONSTRUCTION
	SILTY FENCE
	TREE PROTECTION
	S.C.E. TEMPORARY STABILIZED CONSTRUCTION ENTRANCE
	S.C.S. TEMPORARY SPILLS AND CONSTRUCTION STORAGE
	ROCK BERM
	PROPOSED CONTOURS
	FIRE HYDRANTS
	WATER VALVE
	MANHOLE (STORM)
	MANHOLE (WW)
	INLET
	EXISTING FIRE HYDRANTS
	EXISTING WATER VALVE
	EXISTING MANHOLE (STORM)
	EXISTING MANHOLE (WW)
	EXISTING INLET
	WATER
	WASTEWATER
	STORM SEWER
	PROPERTY LINE (ADJACENT)
	EXISTING EASEMENT
	EXISTING TREE (TO REMAIN)
	EXISTING TREE (REMOVAL)
	50' STREAM BUFFERS
	100' STREAM BUFFERS
	200' STREAM BUFFERS
	400' STREAM BUFFERS
SEE ALL NOTES SHEETS FOR ADDITIONAL REQUIREMENTS	

!!! CAUTION !!!
EXISTING OVERHEAD UTILITIES IN VICINITY OF THE LOCATION OF UNDERGROUND UTILITIES. THE CONTRACTOR SHALL EXERCISE EXTREME CAUTION WHEN WORKING NEAR ELECTRIC FACILITIES.


!!! WARNING !!!
THE ENGINEER ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OF THE LOCATION OF UNDERGROUND UTILITIES. THE CONTRACTOR SHALL BE RESPONSIBLE FOR LOCATION AND AVOIDING ALL EXISTING UTILITIES BY CALLING THE "ONE CALL" LOCATOR SERVICE AT (800) 344-8377 AT LEAST 48 HOURS PRIOR TO CONSTRUCTION.

RELEASE OF THIS APPLICATION DOES NOT CONSTITUTE A VERIFICATION OF ALL DATA, INFORMATION AND CALCULATIONS SUPPLIED BY THE APPLICANT. THE ENGINEER OF RECORD IS SOLELY RESPONSIBLE FOR THE COMPLETENESS, ACCURACY AND ADEQUACY OF HIS/HER SUBMITTAL, WHETHER OR NOT THE APPLICATION IS REVIEWED FOR CODE COMPLIANCE BY CITY ENGINEERS.



PROJECT NO.	499401
DATE	05/24/23
AUTHOR	CHECKED BY:
REVISIONS	
Date	Description





LEGEND	
	PROPOSED CURB & GUTTER (SCALE OF DRAWING NOT TO SCALE)
	PROPOSED CONCRETE SIDEWALK (SEE PLAN FOR WIDTHS)
	L.O.C. LIMITS OF CONSTRUCTION
	SILT FENCE
	TREE PROTECTION
	S.C.E. (TEMPORARY STABILIZED CONSTRUCTION ENTRANCE)
	S.C.S. (TEMPORARY SPOILS AND CONSTRUCTION STORAGE)
	ROCK BERM
	PROPOSED CONTOURS
PROPOSED UTILITIES:	
	FIRE HYDRANTS
	WATER VALVE
	MANHOLE (STORM)
	MANHOLE (WW)
	INLET
EXISTING UTILITIES:	
	FIRE HYDRANTS
	WATER VALVE
	MANHOLE (STORM)
	MANHOLE (WW)
	INLET
	WATER
	WASTEWATER
	STORM SEWER
PROPERTY LINE	
	PROPERTY LINE (ADJACENT)
	EXISTING EASEMENT
	EXISTING TREE (TO REMAIN)
	EXISTING TREE (REMOVAL)
	50' STREAM BUFFERS
	100' STREAM BUFFERS
	200' STREAM BUFFERS
	400' STREAM BUFFERS
SEE ALL NOTES SHEETS FOR ADDITIONAL REQUIREMENTS	

!!! CAUTION !!!
EXISTING OVERHEAD UTILITIES IN VICINITY OF THE LOCATION OF UNDERGROUND UTILITIES. THE CONTRACTOR SHALL EXERCISE EXTREME CAUTION WHEN WORKING NEAR ELECTRIC FACILITIES.








!!! WARNING !!!
THE ENGINEER ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OF THE LOCATION OF UNDERGROUND UTILITIES. THE CONTRACTOR SHALL BE RESPONSIBLE FOR LOCATION AND AVOIDING ALL EXISTING UTILITIES BY CALLING THE "ONE CALL" LOCATOR SERVICE AT (800) 344-8377 AT LEAST 48 HOURS PRIOR TO CONSTRUCTION.

RELEASE OF THIS APPLICATION DOES NOT CONSTITUTE A VERIFICATION OF ALL DATA, INFORMATION AND CALCULATIONS SUPPLIED BY THE APPLICANT. THE ENGINEER OF RECORD IS SOLELY RESPONSIBLE FOR THE COMPLETENESS, ACCURACY AND ADEQUACY OF HIS/HER SUBMITTAL. WHETHER OR NOT THE APPLICATION IS REVIEWED FOR CODE COMPLIANCE BY CITY ENGINEERS.



PROJECT NO.	499401
DATE	05/24/23
AUTHOR	CHECKED BY:
REVISIONS	
Date	Description





LEGEND	
[Symbol]	PROPOSED CURB & GUTTER (SCALE OF OTHERS NOT SHOWN)
[Symbol]	PROPOSED CONCRETE SIDEWALK (SEE PLAN FOR WIDTHS)
[Symbol]	L.O.C. (LIMITS OF CONSTRUCTION)
[Symbol]	SILT FENCE TREE PROTECTION
[Symbol]	S.C.E. (TEMPORARY STABILIZED CONSTRUCTION ENTRANCE)
[Symbol]	S.C.S. (TEMPORARY SPILLS AND CONSTRUCTION STORAGE)
[Symbol]	ROCK BERM
[Symbol]	PROPOSED CONTOURS
[Symbol]	PROPOSED UTILITIES:
[Symbol]	FIRE HYDRANTS
[Symbol]	WATER VALVE
[Symbol]	MANHOLE (STORM)
[Symbol]	MANHOLE (WW)
[Symbol]	INLET
[Symbol]	EXISTING UTILITIES:
[Symbol]	FIRE HYDRANTS
[Symbol]	WATER VALVE
[Symbol]	MANHOLE (STORM)
[Symbol]	MANHOLE (WW)
[Symbol]	INLET
[Symbol]	PROPERTY LINE (ADJACENT)
[Symbol]	EXISTING EASEMENT
[Symbol]	EXISTING TREE (TO REMAIN)
[Symbol]	EXISTING TREE (REMOVAL)
[Symbol]	50' STREAM BUFFERS
[Symbol]	100' STREAM BUFFERS
[Symbol]	200' STREAM BUFFERS
[Symbol]	400' STREAM BUFFERS
SEE ALL NOTES SHEETS FOR ADDITIONAL REQUIREMENTS	

!!! CAUTION !!!
EXISTING OVERHEAD UTILITIES IN VICINITY CONTRACTOR SHALL EXERCISE EXTREME CAUTION WHEN WORKING NEAR ELECTRIC FACILITIES.

!!! WARNING !!!
THE ENGINEER ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OF THE LOCATION OF UNDERGROUND UTILITIES. THE CONTRACTOR SHALL BE RESPONSIBLE FOR LOCATION AND AVOIDING ALL EXISTING UTILITIES BY CALLING THE "ONE CALL" LOCATOR SERVICE AT (800) 344-8377 AT LEAST 48 HOURS PRIOR TO CONSTRUCTION.

RELEASE OF THIS APPLICATION DOES NOT CONSTITUTE A VERIFICATION OF ALL DATA, INFORMATION AND CALCULATIONS SUPPLIED BY THE APPLICANT. THE ENGINEER OF RECORD IS SOLELY RESPONSIBLE FOR THE COMPLETENESS, ACCURACY AND ADEQUACY OF HIS/HER SUBMITTAL, WHETHER OR NOT THE APPLICATION IS REVIEWED FOR CODE COMPLIANCE BY CITY ENGINEERS.

pfluger
office: 512.379.4040 | fax: 512.379.4289
209 E. Riverside Drive Austin, Texas 78704
pflugerarchitects.com

DSISD ES #6 - HEADWATERS SITE
HEADWATERS AT BARTON CREEK SUBDIVISION
DRIPPING SPRINGS ETI, TX
HAYS COUNTY

DRIPPING SPRINGS INDEPENDENT SCHOOL DISTRICT
3100 SPORTSPLEX DRIVE
DRIPPING SPRINGS, TX 78620

STATE OF TEXAS
SEAN FRIEND
99671
LICENSED PROFESSIONAL ENGINEER
December 19, 2023


PROJECT NO. 499401
DATE 05/24/23
AUTHOR CHECKED BY
REVISIONS
Date Description

EROSION & SEDIMENTATION CONTROL PLAN - SECTION 3
C7.3

Texas 811
Know what's below. Call before you dig.

Walker Partners
engineers | surveyors
T.B.P.E. Registration No. 8053

TREE LIST		TREE LIST		TREE LIST		TREE LIST		TREE LIST		TREE LIST		TREE LIST		TREE LIST			
TAG #	Description	TAG #	Description	TAG #	Description	TAG #	Description	TAG #	Description	TAG #	Description	TAG #	Description	TAG #	Description		
5001	20" LIVE OAK (M) [13/13]	5071	19" LIVE OAK (M) [11/8]	5142	9" LIVE OAK	5212	9" LIVE OAK	5285	16" LIVE OAK	5355	8" LIVE OAK	5425	12" LIVE OAK	5495	8" LIVE OAK	5665	9" LIVE OAK
5002	13" LIVE OAK	5072	8" LIVE OAK	5143	18" LIVE OAK (M) [13/9]	5213	17" LIVE OAK	5286	15" LIVE OAK	5356	8" LIVE OAK	5426	19" LIVE OAK (M) [10/9]	5496	16" LIVE OAK (M) [8/8]	5666	19" LIVE OAK (M) [10/9]
5003	10" LIVE OAK	5073	8" LIVE OAK	5144	22" LIVE OAK (M) [12/11/8]	5214	21" LIVE OAK	5287	11" LIVE OAK	5357	8" LIVE OAK	5427	11" LIVE OAK	5497	12" LIVE OAK	5667	9" LIVE OAK
5004	8" LIVE OAK	5074	49" LIVE OAK (M) [14/13/13/9]	5145	9" LIVE OAK	5215	21" LIVE OAK (M) [11/10]	5288	9" LIVE OAK	5358	25" LIVE OAK (M) [11/14]	5428	15" LIVE OAK	5498	8" LIVE OAK	5668	11" LIVE OAK
5005	10" LIVE OAK	5075	8" LIVE OAK	5146	34" LIVE OAK (M) [17/17]	5216	9" LIVE OAK	5289	20" LIVE OAK (M) [10/10]	5359	14" LIVE OAK	5429	11" LIVE OAK	5499	11" LIVE OAK	5669	9" LIVE OAK
5006	9" LIVE OAK	5076	10" LIVE OAK	5147	8" LIVE OAK	5217	14" LIVE OAK	5290	29" LIVE OAK (M) [10/4/15]	5360	13" LIVE OAK	5430	8" LIVE OAK	5500	10" LIVE OAK	5670	9" LIVE OAK
5007	10" LIVE OAK	5077	8" LIVE OAK	5148	17" LIVE OAK	5221	8" LIVE OAK	5291	8" LIVE OAK	5361	9" LIVE OAK	5431	18" LIVE OAK (M) [10/8]	5601	10" LIVE OAK	5671	9" LIVE OAK
5008	9" LIVE OAK	5078	17" LIVE OAK	5149	17" LIVE OAK	5222	8" LIVE OAK	5292	31" LIVE OAK (M) [9/11/11]	5362	11" LIVE OAK	5432	9" LIVE OAK	5602	9" LIVE OAK	5672	13" LIVE OAK
5009	18" LIVE OAK (M) [12/11]	5079	14" LIVE OAK	5150	33" LIVE OAK (M) [11/9/7/6]	5223	12" LIVE OAK	5293	10" LIVE OAK	5363	19" LIVE OAK (M) [10/9]	5433	9" LIVE OAK	5603	15" LIVE OAK	5673	11" LIVE OAK
5010	23" LIVE OAK (M) [16/14]	5080	8" LIVE OAK	5151	9" LIVE OAK	5224	8" LIVE OAK	5294	14" LIVE OAK	5364	17" LIVE OAK (M) [9/8]	5434	17" LIVE OAK (M) [9/8]	5604	10" LIVE OAK	5674	27" LIVE OAK (M) [17/10]
5011	17" LIVE OAK	5081	8" LIVE OAK	5152	8" LIVE OAK	5225	10" LIVE OAK	5295	11" LIVE OAK	5365	12" LIVE OAK	5435	15" LIVE OAK	5605	15" LIVE OAK	5675	19" LIVE OAK (M) [10/9]
5012	8" LIVE OAK	5082	10" LIVE OAK	5153	12" LIVE OAK	5226	16" LIVE OAK	5296	11" LIVE OAK	5366	9" LIVE OAK	5436	13" LIVE OAK	5606	11" LIVE OAK	5676	16" LIVE OAK (M) [8/8]
5013	8" LIVE OAK	5083	12" LIVE OAK	5154	10" LIVE OAK	5227	29" LIVE OAK	5297	10" LIVE OAK	5367	8" LIVE OAK	5437	12" LIVE OAK	5607	9" LIVE OAK	5677	9" LIVE OAK
5014	11" LIVE OAK (M) [8/6]	5084	16" LIVE OAK	5155	9" LIVE OAK	5228	8" LIVE OAK	5298	20" LIVE OAK (M) [11/9]	5368	14" LIVE OAK	5438	9" LIVE OAK	5608	9" LIVE OAK	5678	8" LIVE OAK
5015	11" LIVE OAK (M) [8/4]	5085	12" LIVE OAK	5156	19" LIVE OAK (M) [8/6/5]	5229	16" LIVE OAK	5299	10" LIVE OAK	5369	8" LIVE OAK	5439	9" LIVE OAK	5609	8" LIVE OAK	5679	8" LIVE OAK
5016	10" LIVE OAK	5086	16" LIVE OAK	5157	9" LIVE OAK	5230	10" LIVE OAK	5300	9" LIVE OAK	5370	9" LIVE OAK	5440	9" LIVE OAK	5610	8" LIVE OAK	5680	10" LIVE OAK
5017	8" LIVE OAK	5087	8" LIVE OAK	5158	9" LIVE OAK	5231	10" LIVE OAK	5301	17" LIVE OAK (M) [8/9]	5371	10" LIVE OAK	5441	9" LIVE OAK	5611	8" LIVE OAK	5681	13" LIVE OAK
5018	8" LIVE OAK	5088	9" LIVE OAK	5159	8" LIVE OAK	5232	11" LIVE OAK	5302	19" LIVE OAK (M) [9/10]	5372	9" LIVE OAK	5442	11" LIVE OAK	5612	13" LIVE OAK	5682	14" LIVE OAK
5019	13" LIVE OAK (M) [9/8]	5089	8" LIVE OAK	5160	10" LIVE OAK	5233	8" LIVE OAK	5303	8" LIVE OAK	5373	9" LIVE OAK	5443	13" LIVE OAK	5613	26" LIVE OAK (M) [13/13]	5683	18" LIVE OAK
5020	11" LIVE OAK	5090	20" LIVE OAK (M) [10/10]	5161	9" LIVE OAK	5234	17" LIVE OAK (M) [9/8]	5304	9" LIVE OAK	5374	8" LIVE OAK	5444	14" LIVE OAK	5614	21" LIVE OAK	5684	29" LIVE OAK (M) [16/13]
5021	12" LIVE OAK	5091	8" LIVE OAK	5162	8" LIVE OAK	5235	8" LIVE OAK	5305	13" LIVE OAK	5375	8" LIVE OAK	5445	12" LIVE OAK	5615	10" LIVE OAK	5685	13" LIVE OAK
5022	13" LIVE OAK (M) [9/8]	5092	20" LIVE OAK	5163	19" LIVE OAK (M) [12/7]	5236	13" LIVE OAK	5306	9" LIVE OAK	5376	8" LIVE OAK	5446	11" POST OAK	5616	10" LIVE OAK	5686	13" LIVE OAK
5023	8" LIVE OAK	5093	22" LIVE OAK	5164	14" POST OAK	5237	11" LIVE OAK	5307	11" LIVE OAK	5377	8" LIVE OAK	5447	8" LIVE OAK	5617	9" LIVE OAK	5687	14" LIVE OAK
5024	16" LIVE OAK	5094	8" LIVE OAK	5165	9" POST OAK	5238	12" LIVE OAK	5308	8" LIVE OAK	5378	11" LIVE OAK	5448	9" LIVE OAK	5618	8" LIVE OAK	5688	8" LIVE OAK
5025	10" LIVE OAK (M) [8/4]	5095	15" LIVE OAK	5166	15" LIVE OAK	5239	14" LIVE OAK	5309	8" LIVE OAK	5379	8" LIVE OAK	5449	8" LIVE OAK	5619	14" LIVE OAK	5689	8" LIVE OAK
5026	8" LIVE OAK	5096	9" LIVE OAK	5167	15" LIVE OAK	5240	19" LIVE OAK	5310	9" LIVE OAK	5380	15" LIVE OAK	5450	8" LIVE OAK	5620	16" LIVE OAK (M) [9/8]	5690	13" LIVE OAK
5027	17" LIVE OAK (M) [10/7/6]	5097	14" LIVE OAK	5168	9" LIVE OAK	5241	20" LIVE OAK (M) [9/11]	5311	8" LIVE OAK	5381	10" LIVE OAK	5451	9" LIVE OAK	5621	18" LIVE OAK	5691	15" LIVE OAK
5028	9" CEDAR ELM	5098	8" LIVE OAK	5169	11" LIVE OAK	5242	22" LIVE OAK	5312	9" LIVE OAK	5382	11" LIVE OAK	5452	8" LIVE OAK	5622	12" LIVE OAK	5692	9" LIVE OAK
5029	13" LIVE OAK (M) [9/7]	5099	8" LIVE OAK	5170	12" LIVE OAK	5243	16" LIVE OAK (M) [8/8]	5313	9" LIVE OAK	5383	12" LIVE OAK	5453	15" LIVE OAK	5623	8" LIVE OAK	5693	41" LIVE OAK (M) [15/14/12]
5030	12" LIVE OAK (M) [8/7]	5100	21" LIVE OAK (M) [11/10]	5171	14" LIVE OAK	5244	10" LIVE OAK	5314	11" LIVE OAK	5384	[8/9] LIVE OAK (M)	5454	8" LIVE OAK	5624	8" LIVE OAK	5694	10" LIVE OAK
5031	11" LIVE OAK	5101	8" LIVE OAK	5172	16" LIVE OAK	5245	14" LIVE OAK	5315	16" LIVE OAK (M) [8/8]	5385	10" LIVE OAK	5455	8" LIVE OAK	5625	13" LIVE OAK	5695	10" LIVE OAK
5032	8" LIVE OAK	5102	10" LIVE OAK	5173	8" LIVE OAK	5246	11" LIVE OAK	5316	10" LIVE OAK	5386	16" LIVE OAK (M) [8/8]	5456	8" LIVE OAK	5626	10" LIVE OAK	5696	15" LIVE OAK
5033	8" LIVE OAK	5103	10" LIVE OAK	5174	16" POST OAK	5247	23" LIVE OAK	5317	9" SPANISH OAK	5387	8" LIVE OAK	5457	9" LIVE OAK	5627	12" LIVE OAK	5697	12" LIVE OAK
5034	9" LIVE OAK	5104	16" LIVE OAK (M) [12/8]	5175	10" LIVE OAK	5248	16" LIVE OAK	5318	30" LIVE OAK (M) [12/9/9]	5388	14" LIVE OAK	5458	8" LIVE OAK	5628	11" LIVE OAK	5698	14" LIVE OAK
5035	8" LIVE OAK	5105	17" LIVE OAK (M) [12/8]	5176	9" LIVE OAK	5249	17" LIVE OAK	5319	18" LIVE OAK (M) [8/10]	5389	8" LIVE OAK	5459	13" LIVE OAK	5629	9" LIVE OAK	5699	9" LIVE OAK
5036	9" LIVE OAK	5106	24" LIVE OAK (M) [17/14]	5177	8" LIVE OAK	5250	15" LIVE OAK	5320	12" LIVE OAK	5390	25" LIVE OAK (M) [9/9]	5460	8" LIVE OAK	5630	11" LIVE OAK	5700	11" LIVE OAK
5037	12" LIVE OAK	5107	8" LIVE OAK	5178	13" LIVE OAK	5251	11" LIVE OAK	5321	8" LIVE OAK	5391	8" LIVE OAK	5461	9" LIVE OAK	5631	19" LIVE OAK (M) [10/9]	5701	19" LIVE OAK (M) [9/10]
5038	11" LIVE OAK	5108	8" LIVE OAK	5179	13" LIVE OAK	5252	8" LIVE OAK	5322	8" LIVE OAK	5392	18" LIVE OAK (M) [8/10]	5462	10" LIVE OAK	5632	10" LIVE OAK	5702	10" LIVE OAK
5039	17" LIVE OAK (M) [12/10]	5109	9" LIVE OAK	5180	30" LIVE OAK (M) [18/12]	5253	8" LIVE OAK	5323	8" LIVE OAK	5393	9" LIVE OAK	5463	17" LIVE OAK (M) [9/8]	5633	9" LIVE OAK	5703	9" LIVE OAK
5040	10" LIVE OAK	5110	9" LIVE OAK	5181	8" LIVE OAK	5254	12" LIVE OAK	5324	8" LIVE OAK	5394	10" LIVE OAK	5464	21" LIVE OAK	5634	27" LIVE OAK (M) [9]	5704	8" LIVE OAK
5041	9" LIVE OAK	5111	12" LIVE OAK	5182	20" LIVE OAK (M) [11/9]	5255	8" LIVE OAK	5325	12" LIVE OAK	5395	10" LIVE OAK	5465	13" LIVE OAK	5635	8" LIVE OAK	5705	10" LIVE OAK
5042	9" LIVE OAK	5112	10" LIVE OAK	5183	18" LIVE OAK (M) [10/8]	5256	20" LIVE OAK	5326	11" LIVE OAK	5396	11" LIVE OAK	5466	9" LIVE OAK	5636	9" LIVE OAK	5706	9" LIVE OAK
5043	8" LIVE OAK	5113	8" LIVE OAK	5184	8" LIVE OAK	5257	17" LIVE OAK	5327	26" LIVE OAK (M) [8/9/9]	5397	10" LIVE OAK	5467	8" LIVE OAK	5637	8" LIVE OAK	5707	9" LIVE OAK
5044	28" LIVE OAK	5114	11" LIVE OAK	5185	8" LIVE OAK	5258	11" LIVE OAK	5328	11" LIVE OAK	5398	9" LIVE OAK	5468	25" LIVE OAK (M) [15/10]	5638	12" LIVE OAK	5708	8" LIVE OAK
5045	32" LIVE OAK (M) [23/17]	5115	13" LIVE OAK	5186	8" LIVE OAK	5259	11" LIVE OAK	5329	11" LIVE OAK	5399	8" LIVE OAK	5469	21" LIVE OAK (M) [10/11]	5639	8" LIVE OAK	5709	8" LIVE OAK
5046	11" LIVE OAK	5116	8" LIVE OAK	5187	8" LIVE OAK	5260	11" LIVE OAK	5330	41" LIVE OAK (M) [11/11/10/9]	5400	30" LIVE OAK (M) [8/10/12]	5470	14" LIVE OAK	5640	8" LIVE OAK	5710	8" LIVE OAK
5047	8" LIVE OAK	5117	8" LIVE OAK	5188	11" LIVE OAK	5261	9" LIVE OAK	5331	13" LIVE OAK	5401	14" LIVE OAK	5471	9" LIVE OAK	5641	10" LIVE OAK	5711	8" LIVE OAK
5048	8" LIVE OAK	5118	8" LIVE OAK	5189	8" LIVE OAK	5262	8" LIVE OAK	5332	28" LIVE OAK (M) [14/14]	5402	14" LIVE OAK	5472	18" LIVE OAK	5642	31" LIVE OAK (M) [12/10/9]	5712	11" LIVE OAK
5049	10" LIVE OAK	5119	12" LIVE OAK	5190	8" LIVE OAK	5263	10" LIVE OAK	5333	9" LIVE OAK	5403	8" LIVE OAK	5473	16" LIVE OAK	5643	40" LIVE OAK (M) [15/9/8]	5713	11" LIVE OAK
5050	9" LIVE OAK	5120	10" LIVE OAK	5191	14" LIVE OAK	5264	8" LIVE OAK	5334	8" LIVE OAK	5404	10" LIVE OAK	5474	11" LIVE OAK	5644	10" LIVE OAK	5714	9" LIVE OAK
5051	10" LIVE OAK	5121	10" LIVE OAK	5192	8" LIVE OAK	5265	9" LIVE OAK	5335	24" LIVE OAK [8/8/8]	5405	10" LIVE OAK	5475	13" LIVE OAK	5645	24" LIVE OAK (M) [12/12]	5715	21" LIVE OAK (M) [9/12]
5052	8" LIVE OAK	5122	13" LIVE OAK	5193	9" LIVE OAK	5266	11" LIVE OAK	5336	9" LIVE OAK	5406	8" LIVE OAK	5476	8" LIVE OAK	5646	9" LIVE OAK	5716	10" LIVE OAK
5053	11" LIVE OAK	5123	11" LIVE OAK	5194	9" LIVE OAK	5267	15" LIVE OAK	5337	10" LIVE OAK	5407	13" LIVE OAK	5477	8" LIVE OAK	5647	9" LIVE OAK	5717	18" SPANISH OAK (M) [9/10]
5054	8" LIVE OAK	5124	11" LIVE OAK	5195	8" LIVE OAK	5268	16" LIVE OAK (M) [8/8]	5338	15" LIVE OAK	5408	9" LIVE OAK	5478	10" LIVE OAK	5648	9" LIVE OAK	5718	10" SPANISH OAK
5055	9" LIVE OAK	5125	9" LIVE OAK	5196	8" LIVE OAK	5269	9" LIVE OAK	5339	10" LIVE OAK	5409	20" LIVE OAK (M) [10/10]	5479	14" LIVE OAK	5649	9" LIVE OAK	5719	21" SPANISH OAK (M) [9/12]
5056	10" LIVE OAK	5126	10" LIVE OAK	5197	18" LIVE OAK	5270	9" LIVE OAK	5340	8" LIVE OAK	5410	16" LIVE OAK (M) [8/8]	5480	10" LIVE OAK	5650	9" LIVE OAK	5720	8" LIVE OAK
5057	35" LIVE OAK (M) [19/16]	5127	9" LIVE OAK	5198	13" LIVE OAK	5271	9" LIVE OAK	5341	8" LIVE OAK	5411	12" LIVE OAK	5481	12" LIVE OAK	5651	9" LIVE OAK	5721	21" LIVE OAK (M) [9/12]
5058	12" LIVE OAK	5128	9" LIVE OAK	5199	14" LIVE OAK	5272	18" LIVE OAK (M) [10/8]	5342	18" LIVE OAK	5412	9" LIVE OAK	5482	8" LIVE OAK	5652	10" LIVE OAK	5722	21" LIVE OAK
5059	21" LIVE OAK (M) [11/10]	5129	9" LIVE OAK	5200	10" LIVE OAK	5273	9" LIVE OAK	5343	9" LIVE OAK	5413	9" LIVE OAK	5483	9" LIVE OAK	5653	9" LIVE OAK	5723	8" LIVE OAK
5060	10" LIVE OAK	5130	8" LIVE OAK	5201	14" LIVE OAK	5274	11" LIVE OAK	5344	9" LIVE OAK	5414	9" LIVE OAK	5484	9" LIVE OAK	5654	9" LIVE OAK	5724	9" LIVE OAK
5061	9" LIVE OAK	5131	12" LIVE OAK	5202	8" LIVE OAK	5275	8" LIVE OAK	5345	15" LIVE OAK	5415	11" LIVE OAK	5485	10" LIVE OAK	5655	12" LIVE OAK	5725	11" LIVE OAK
5062	12" LIVE OAK	5132	20" LIVE OAK (M) [13/7]	5203	15" LIVE OAK	5276	8" LIVE OAK	5346	9" LIVE OAK	5416	20" LIVE OAK (M) [11/9]	5486	8" LIVE OAK	5656	13" LIVE OAK	5726	13" LIVE OAK
5063	23" LIVE OAK (M) [13/11/8]	5133	8" LIVE OAK	5204	13" LIVE OAK	5277	35" LIVE OAK (M) [12/12/11]	5347	9" LIVE OAK	5417	10" LIVE OAK	5487</					



LEGEND	
.....	PROPOSED ACCESSIBLE ROUTE
---	PROPOSED CURB & GUTTER (REFER TO OTHER NOTED PLANS)
---	PROPOSED CONCRETE SIDEWALK (SEE PLAN FOR WIDTH)
---	PROPOSED CONCRETE AREAS
---	PROPOSED CONCRETE AREAS
---	BUILDING OVERHEAD HATCH
---	L.O.C. (LIMITS OF CONSTRUCTION)
---	PROPOSED FIRE LANE (REFER TO PLAN FOR STRIPING NOTES)
PROPOSED UTILITIES:	
FW	FIRE HYDRANTS
W	WATER VALVE
WS	MANHOLE (STORM)
WWS	MANHOLE (WW)
IN	INLET
W	WATER
WW	WASTEWATER
SS	STORM SEWER
EXISTING UTILITIES:	
FW	FIRE HYDRANTS
W	WATER VALVE
WS	MANHOLE (STORM)
WWS	MANHOLE (WW)
IN	INLET
W	WATER
WW	WASTEWATER
SS	STORM SEWER
PROPERTY LINE (ADJACENT)	
---	EXISTING EASEMENT
---	EXISTING TREE (TO REMAIN)
---	50' STREAM BUFFERS
---	100' STREAM BUFFERS
---	200' STREAM BUFFERS
---	400' STREAM BUFFERS

SEE ALL NOTES SHEETS FOR ADDITIONAL REQUIREMENTS



PROJECT NO.	499401
DATE	05/24/23
AUTHOR	CHECKED BY
REVISIONS	
Date	Description



!!! CAUTION !!!
 EXISTING OVERHEAD UTILITIES IN VICINITY
 CONTRACTOR SHALL EXERCISE EXTREME CAUTION
 WHEN WORKING NEAR ELECTRIC FACILITIES.

!!! WARNING !!!
 THE ENGINEER ASSUMES NO RESPONSIBILITY FOR THE ACCURACY
 OF THE LOCATION OF UNDERGROUND UTILITIES. THE CONTRACTOR
 SHALL BE RESPONSIBLE FOR LOCATION AND AVOIDING ALL
 EXISTING UTILITIES BY CALLING THE "ONE CALL" LOCATOR SERVICE
 AT (800) 344-8377 AT LEAST 48 HOURS PRIOR TO CONSTRUCTION.

"RELEASE OF THIS APPLICATION DOES NOT CONSTITUTE A
 VERIFICATION OF ALL DATA, INFORMATION AND CALCULATIONS
 SUPPLIED BY THE APPLICANT. THE ENGINEER OF RECORD IS SOLELY
 RESPONSIBLE FOR THE COMPLETENESS, ACCURACY AND ADEQUACY
 OF HIS/HER SUBMITTAL, WHETHER OR NOT THE APPLICATION IS
 REVIEWED FOR CODE COMPLIANCE BY CITY ENGINEERS"



Drawing Path: E:\690401_Drawings_Production Drawings_Production Drawings\SH SITE.dwg Plotted By: Brian Green Date: 12/13/2023 8:27:32 AM Layout: OVERALL SITE PLAN Page Size: ARCH full bleed E1 (30.00 x 42.00 inches) ###



LEGEND	
	PROPOSED CURB & GUTTER (BASED ON THE NOTES PLAN)
	PROPOSED CONCRETE SIDEWALK (SEE PLAN FOR NOTES)
	PROPOSED CONCRETE AREAS (TO BE CONSTRUCTED WITH LOTS)
	PROPOSED CONCRETE AREAS (TO BE CONSTRUCTED WITH STREETS)
	L.O.C. LIMITS OF CONSTRUCTION
	PROPOSED CONTOURS
	PROPOSED SPOT GRADES
	EXISTING SPOT GRADES
	FIRE HYDRANTS
	WATER VALVE
	MANHOLE (STORM)
	MANHOLE (WW)
	INLET
	WATER
	WASTEWATER
	STORM SEWER
	PROPERTY LINE
	PROPERTY LINE (ADJACENT)
	EXISTING EASEMENT
	EXISTING TREE (TO REMAIN)
	50' STREAM BUFFERS
	100' STREAM BUFFERS
	200' STREAM BUFFERS
	400' STREAM BUFFERS

SEE ALL NOTES SHEETS FOR ADDITIONAL REQUIREMENTS

!!! CAUTION !!!
 EXISTING OVERHEAD UTILITIES IN VICINITY OF THE LOCATION OF UNDERGROUND UTILITIES. THE CONTRACTOR SHALL EXERCISE EXTREME CAUTION WHEN WORKING NEAR ELECTRIC FACILITIES.

!!! WARNING !!!
 THE ENGINEER ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OF THE LOCATION OF UNDERGROUND UTILITIES. THE CONTRACTOR SHALL BE RESPONSIBLE FOR LOCATION AND AVOIDING ALL EXISTING UTILITIES BY CALLING THE "ONE CALL" LOCATOR SERVICE AT (800) 344-8377 AT LEAST 48 HOURS PRIOR TO CONSTRUCTION.



RELEASE OF THIS APPLICATION DOES NOT CONSTITUTE A VERIFICATION OF ALL DATA, INFORMATION AND CALCULATIONS SUPPLIED BY THE APPLICANT. THE ENGINEER OF RECORD IS SOLELY RESPONSIBLE FOR THE COMPLETENESS, ACCURACY AND ADEQUACY OF HIS/HER SUBMITTAL. WHETHER OR NOT THE APPLICATION IS REVIEWED FOR CODE COMPLIANCE BY CITY ENGINEERS.



PROJECT NO.	499401
DATE	05/24/23
AUTHOR	CHECKED BY:
REVISIONS	
Date	Description



Drawing Path: E:\499401\Drawings\Production Drawings\Production Drawings\STORM SEWER PLAN.dwg Plotted by: Brian Green Date: 12/13/2023 8:27:43 AM Layout: STORM SEWER PLAN Page Size: ARCH full bleed E1 (20.00 x 42.00 inches), ##



LEGEND

- PROPOSED CONTOURS
- PROPOSED SPOT GRADES
- EXISTING CONTOURS - MAJOR
- EXISTING CONTOURS - MINOR
- PROPOSED FLOW DIRECTION
- L.O.C. (LIMITS OF CONSTRUCTION)
- GATE & FENCE (REF. LANDSCAPE FOR POND)
- EXISTING TREES
- PROPERTY LINE (ADJACENT)
- EXISTING EASEMENT
- EXISTING TREE (TO REMAIN)
- 50' STREAM BUFFERS
- 100' STREAM BUFFERS
- 200' STREAM BUFFERS
- 400' STREAM BUFFERS

SEE ALL NOTES SHEETS FOR ADDITIONAL REQUIREMENTS

DETENTION POND STAGE/STORAGE/DISCHARGE


STAGE	STORAGE (AC-FT)	DISCHARGE (CFS)	NOTE
1097.30	0.00	0.0	WQV
1100.47	1.57	17.0	2YR
1101.67	2.23	46.4	10 YR
1102.33	2.60	71.2	25 YR
1103.27	3.12	113.1	100 YR

POND TO BE USED AS SEDIMENTATION BASIN DURING CONSTRUCTION:
 > CAPTURE VOL = 8,000 CF/AC X 13.5 AC (PR 1) = 108,000 CF
 > STAGE = 1100.4


HEC-HMS HYDROLOGIC SUMMARY

DRAINAGE AREA	AREA (AC)	CN	IMPERVIOUS (%)	LAG TIME (MIN)	Q2 (CFS)	Q10 (CFS)	Q25 (CFS)	Q100 (CFS)
EX 1	19.1	80	0.0	5.6	55.3	107.4	142.8	202.2
EX 2	45.5	80	0.0	8.4	115.1	225.3	300.5	426.2
EX OUT	>	>	>	>	166.1	323.2	432.1	614.2
PR 1	13.5	80	70.0	3.0	65.6	106.2	133.5	179.5
POND (Q OUT)	>	>	>	>	17.0	46.4	71.2	113.1
PR 2	14.6	80	3.5	6.5	41.4	80.1	106.4	150.5
PR 3	36.5	80	3.5	8.4	94.4	182.5	242.5	342.9
OEM (SEE NOTE 4)	13.5	80	0.0	6.8	36.7			
PR OUT	>	>	>	>	149.8	303.7	414.8	598.4


- NOTES:
 1) EX OUT = EX 1 + EX 2
 2) PR OUT = POND + PR 2 + PR 3
 3) PR OUT < EX OUT
 4) OEM = PR1 (UNDEV) - COMPLIANCE W/ TCEQ RG-348, APP A, SEC 5 (Q2 EXITING POND < 50% UNDEV | 17.0 CFS < 18.35 CFS)




POND OUTFALL SECTION A-A
NTS



POND OUTFALL (WEST)
NTS



POND OUTFALL (EAST)
NTS



CONCRETE SWALE
NTS

!!! CAUTION !!!
EXISTING OVERHEAD UTILITIES IN VICINITY CONTRACTOR SHALL EXERCISE EXTREME CAUTION WHEN WORKING NEAR ELECTRIC FACILITIES.

!!! WARNING !!!
THE ENGINEER ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OF THE LOCATION OF UNDERGROUND UTILITIES. THE CONTRACTOR SHALL BE RESPONSIBLE FOR LOCATION AND AVOIDING ALL EXISTING UTILITIES BY CALLING THE "ONE CALL" LOCATOR SERVICE AT (800) 344-8377 AT LEAST 48 HOURS PRIOR TO CONSTRUCTION.

RELEASE OF THIS APPLICATION DOES NOT CONSTITUTE A VERIFICATION OF ALL DATA, INFORMATION AND CALCULATIONS SUPPLIED BY THE APPLICANT. THE ENGINEER OF RECORD IS SOLELY RESPONSIBLE FOR THE COMPLETENESS, ACCURACY AND ADEQUACY OF HIS/HER SUBMITTAL, WHETHER OR NOT THE APPLICATION IS REVIEWED FOR CODE COMPLIANCE BY CITY ENGINEERS.



PROJECT NO. 499401
 DATE 05/24/23
 AUTHORIZED BY: [Signature]
 CHECKED BY: [Signature]
 REVISIONS: [Table]
 Date Description

stabilization in those areas shall be initiated as soon as possible prior to the 14th day of inactivity. If activity will resume prior to the 21st day, stabilization measures are not required. If drought conditions or inclement weather prevent action by the 14th day, stabilization measures shall be initiated as soon as possible.

- The following records should be maintained and made available to the TCEQ upon request:
 - the dates when major grading activities occur;
 - the dates when construction activities temporarily or permanently cease on a portion of the site; and
 - the dates when stabilization measures are initiated.
- The holder of any approved CZP must notify the appropriate regional office in writing and obtain approval from the executive director prior to initiating any of the following:
 - any physical or operational modification of any best management practices (BMPs) or structure(s), including but not limited to temporary or permanent ponds, dams, berms, silt fences, and diversionary structures;
 - any change in the nature or character of the regulated activity from that which was originally approved;
 - any change that would significantly impact the ability to prevent pollution of the Edwards Aquifer; or
 - any development of land previously identified as undeveloped in the approved contributing zone plan.

Austin Regional Office 12100 Park 35 Circle, Building A Austin, Texas 78753-1808 Phone (512) 339-2929 Fax (512) 339-3795	San Antonio Regional Office 14250 Judson Road San Antonio, Texas 78233-4480 Phone (210) 490-3096 Fax (210) 545-4329
--	---

THESE GENERAL CONSTRUCTION NOTES MUST BE INCLUDED ON THE CONSTRUCTION PLANS PROVIDED TO THE CONTRACTOR AND ALL SUBCONTRACTORS.

**Texas Commission on Environmental Quality
Contributing Zone Plan
General Construction Notes**

Edwards Aquifer Protection Program Construction Notes – Legal Disclaimer

The following listed "construction notes" are intended to be advisory in nature only and do not constitute an approval or conditional approval by the Executive Director (ED), nor do they constitute a comprehensive listing of rules or conditions to be followed during construction. Further actions may be required to achieve compliance with TCEQ regulations found in Title 30, Texas Administrative Code (TAC), Chapters 213 and 217, as well as local ordinances and regulations providing for the protection of water quality. Additionally, nothing contained in the following listed "construction notes" restricts the powers of the ED, the commission or any other governmental entity to prevent, correct, or curtail activities that result or may result in pollution of the Edwards Aquifer or hydrologically connected surface waters. The holder of any Edwards Aquifer Protection Plan containing "construction notes" is still responsible for compliance with Title 30, TAC, Chapters 213 or any other applicable TCEQ regulation, as well as all conditions of an Edwards Aquifer Protection Plan through all phases of plan implementation. Failure to comply with any condition of the ED's approval, whether or not in contradiction of any "construction notes," is a violation of TCEQ regulations and any violation is subject to administrative rules, orders, and penalties as provided under Title 30, TAC § 213.10 (relating to Enforcement). Such violations may also be subject to civil penalties and injunction. The following listed "construction notes" in no way represent an approved exception by the ED to any part of Title 30 TAC, Chapters 213 and 217, or any other TCEQ applicable regulation.

- A written notice of construction must be submitted to the TCEQ regional office at least 48 hours prior to the start of any ground disturbance or construction activities. This notice must include:
 - the name of the approved project;
 - the activity start date; and
 - the contact information of the prime contractor.
- All contractors conducting regulated activities associated with this project should be provided with complete copies of the approved Contributing Zone Plan (CZP) and the TCEQ letter indicating the specific conditions of its approval. During the course of these regulated activities, the contractor(s) should keep copies of the approved plan and approval letter on-site.
- No hazardous substance storage tank shall be installed within 150 feet of a water supply source, distribution system, well, or sensitive feature.
- Prior to beginning any construction activity, all temporary erosion and sedimentation (E&S) control measures must be properly installed and maintained in accordance with the manufacturers specifications. If inspections indicate a control has been used inappropriately, or incorrectly, the applicant must replace or modify the control for site situations. These controls must remain in place until the disturbed areas have been permanently stabilized.
- Any sediment that escapes the construction site must be collected and properly disposed of before the next rain event to ensure it is not washed into surface streams, sensitive features, etc.
- Sediment must be removed from the sediment traps or sedimentation basins when it occupies 50% of the basin's design capacity.
- Litter, construction debris, and construction chemicals exposed to stormwater shall be prevented from being discharged offsite.
- All excavated material that will be stored on-site must have proper E&S controls.
- If portions of the site will have a cease in construction activity lasting longer than 14 days, soil

Texas Commission on Environmental Quality

TSS Removal Calculations 04-20-2009

Project Name: **DSISD ES 6**
Date Prepared:

1. The Required Load Reduction for the total project:

Calculations from RG-348

Site Data: Determine Required Load Reduction Based on the Entire Project

County =	Hays	acres
Total project area included in plan =	13.50	acres
Predevelopment impervious area within the limits of the plan =	0.00	acres
Total post-development impervious area within the limits of the plan =	9.45	acres
Total post-development impervious cover fraction =	0.70	
P =	33	inches

L_M TOTAL PROJECT = **8482** lbs.
Number of drainage basins / outfalls areas leaving the plan area = **1**

2. Drainage Basin Parameters (This information should be provided for each basin):

Drainage Basin/Outfall Area No. =	1
Total drainage basin/outfall area =	13.50 acres
Predevelopment impervious area within drainage basin/outfall area =	0.00 acres
Post-development impervious area within drainage basin/outfall area =	9.45 acres
Post-development impervious fraction within drainage basin/outfall area =	0.70
L _M THIS BASIN =	8482 lbs.

3. Indicate the proposed BMP Code for this basin.

Proposed BMP = **Sand Filter** BATCH DETENTION
Removal efficiency = **91** percent

4. Calculate Maximum TSS Load Removed (L_R) for this Drainage Basin by the selected BMP Type.

RG-348 Page 3-33 Equation 3.7: L_R = (BMP efficiency) x P x (A_i x 34.6 + A_p x 0.54)

where:

A_i = Total On-Site drainage area in the BMP catchment area
A_p = Impervious area proposed in the BMP catchment area
A_r = Pervious area remaining in the BMP catchment area
L_R = TSS Load removed from this catchment area by the proposed BMP

A_i = **13.50** acres
A_p = **9.45** acres
A_r = **4.05** acres
L_R = **9885** lbs

5. Calculate Fraction of Annual Runoff to Treat the drainage basin / outfall area




Desired L_M THIS BASIN = **8482** lbs.
F = **0.86**

6. Calculate Capture Volume required by the BMP Type for this drainage basin / outfall area.

Calculations from RG-348

Rainfall Depth =	1.38	inches
Post Development Runoff Coefficient =	0.51	
On-site Water Quality Volume =	34196	cubic feet
Off-site area draining to BMP =	0.00	acres
Off-site Impervious cover draining to BMP =	0.00	acres
Impervious fraction of off-site area =	0	
Off-site Runoff Coefficient =	0	
Off-site Water Quality Volume =	0	cubic feet



Storage for Sediment = **6839**
Total Capture Volume (required water quality volume(s) x 1.20) = **41035** cubic feet



!!! CAUTION !!!
EXISTING OVERHEAD UTILITIES IN VICINITY OF THE LOCATION OF UNDERGROUND UTILITIES. THE CONTRACTOR SHALL BE RESPONSIBLE FOR LOCATION AND AVOIDING ALL EXISTING UTILITIES BY CALLING THE "ONE CALL" LOCATOR SERVICE AT (800) 344-8377 AT LEAST 48 HOURS PRIOR TO CONSTRUCTION.

!!! WARNING !!!
THE ENGINEER ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OF THE LOCATION OF UNDERGROUND UTILITIES. THE CONTRACTOR SHALL BE RESPONSIBLE FOR LOCATION AND AVOIDING ALL EXISTING UTILITIES BY CALLING THE "ONE CALL" LOCATOR SERVICE AT (800) 344-8377 AT LEAST 48 HOURS PRIOR TO CONSTRUCTION.

RELEASE OF THIS APPLICATION DOES NOT CONSTITUTE A VERIFICATION OF ALL DATA, INFORMATION AND CALCULATIONS SUPPLIED BY THE APPLICANT. THE ENGINEER OF RECORD IS SOLELY RESPONSIBLE FOR THE COMPLETENESS, ACCURACY AND ADEQUACY OF HIS/HER SUBMITTAL, WHETHER OR NOT THE APPLICATION IS REVIEWED FOR CODE COMPLIANCE BY CITY ENGINEERS.



LEGEND

	PROPOSED CONTOURS
	PROPOSED SPOT GRADES
	EXISTING CONTOURS - MAJOR
	EXISTING CONTOURS - MINOR
	PROPOSED FLOW DIRECTION
	L.O.C. (LIMITS OF CONSTRUCTION)
	GATE & FENCE (REF. LANDSCAPE FOR FENCE)
	EXISTING TREES
	PROPERTY LINE (ADJACENT)
	EXISTING EASEMENT
	EXISTING TREE (TO REMAIN)
	50' STREAM BUFFERS
	100' STREAM BUFFERS
	200' STREAM BUFFERS
	400' STREAM BUFFERS

SEE ALL NOTES SHEETS FOR ADDITIONAL REQUIREMENTS

- ENGINEERED VEGETATIVE FILTER STRIPS:**
1. MAX SLOPE = 20%
 2. MIN WIDTH = 15'
 3. MIN VEGETATED COVER = 80%
 4. TOP EDGE OF FILTER STRIP ALONG THE PAVEMENT / RIBBON CURB TO BE INSTALLED SUCH THAT RUNOFF TRAVELS THROUGH THE FILTER STRIP AND NOT ALONG THE TOP EDGE.
 5. FILTER STRIPS TO BE VEGETATED AFTER OTHER PORTIONS OF THE PROJECT ARE COMPLETED.

!!! CAUTION !!!
EXISTING OVERHEAD UTILITIES IN VICINITY CONTRACTOR SHALL EXERCISE EXTREME CAUTION WHEN WORKING NEAR ELECTRIC FACILITIES.

!!! WARNING !!!
THE ENGINEER ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OF THE LOCATION OF UNDERGROUND UTILITIES. THE CONTRACTOR SHALL BE RESPONSIBLE FOR LOCATION AND AVOIDING ALL EXISTING UTILITIES BY CALLING THE "ONE CALL" LOCATOR SERVICE AT (800) 344-8377 AT LEAST 48 HOURS PRIOR TO CONSTRUCTION.

RELEASE OF THIS APPLICATION DOES NOT CONSTITUTE A VERIFICATION OF ALL DATA, INFORMATION AND CALCULATIONS SUPPLIED BY THE APPLICANT. THE ENGINEER OF RECORD IS SOLELY RESPONSIBLE FOR THE COMPLETENESS, ACCURACY AND ADEQUACY OF HIS/HER SUBMITTAL. WHETHER OR NOT THE APPLICATION IS REVIEWED FOR CODE COMPLIANCE BY CITY ENGINEERS.



PROJECT NO.	499401
DATE	05/24/23
AUTHOR	CHECKED BY
REVISIONS	
Date	Description

