

ATX PICKLEPLEX
TCEQ CONTRIBUTING ZONE PLAN

Prepared for:

PicklePlex Holdings, LLC
3725 Copper Ridge Ct.
Austin, TX 78734

Prepared by:

Gray Engineering, Inc.
8834 Capital of Texas Highway, Suite 140
Austin, Texas 78759
TBPE Firm #2946

JUL 2024

**Edwards Aquifer Application Cover Page
(TCEQ-20705)**

Texas Commission on Environmental Quality

Edwards Aquifer Application Cover Page

Our Review of Your Application

The Edwards Aquifer Program staff conducts an administrative and technical review of all applications. The turnaround time for administrative review can be up to 30 days as outlined in 30 TAC 213.4(e). Generally administrative completeness is determined during the intake meeting or within a few days of receipt. The turnaround time for technical review of an administratively complete Edwards Aquifer application is 90 days as outlined in 30 TAC 213.4(e). Please know that the review and approval time is directly impacted by the quality and completeness of the initial application that is received. In order to conduct a timely review, it is imperative that the information provided in an Edwards Aquifer application include final plans, be accurate, complete, and in compliance with [30 TAC 213](#).

Administrative Review

1. [Edwards Aquifer applications](#) must be deemed administratively complete before a technical review can begin. To be considered administratively complete, the application must contain completed forms and attachments, provide the requested information, and meet all the site plan requirements. The submitted application and plan sheets should be final plans. Please submit one full-size set of plan sheets with the original application, and half-size sets with the additional copies.

To ensure that all applicable documents are included in the application, the program has developed tools to guide you and web pages to provide all forms, checklists, and guidance. Please visit the below website for assistance: <http://www.tceq.texas.gov/field/eapp>.

2. This Edwards Aquifer Application Cover Page form (certified by the applicant or agent) must be included in the application and brought to the administrative review meeting.
3. Administrative reviews are scheduled with program staff who will conduct the review. Applicants or their authorized agent should call the appropriate regional office, according to the county in which the project is located, to schedule a review. The average meeting time is one hour.
4. In the meeting, the application is examined for administrative completeness. Deficiencies will be noted by staff and emailed or faxed to the applicant and authorized agent at the end of the meeting, or shortly after. Administrative deficiencies will cause the application to be deemed incomplete and returned.

An appointment should be made to resubmit the application. The application is re-examined to ensure all deficiencies are resolved. The application will only be deemed administratively complete when all administrative deficiencies are addressed.

5. If an application is received by mail, courier service, or otherwise submitted without a review meeting, the administrative review will be conducted within 30 days. The applicant and agent will be contacted with the results of the administrative review. If the application is found to be administratively incomplete, it can be retrieved from the regional office or returned by regular mail. If returned by mail, the regional office may require arrangements for return shipping.
6. If the geologic assessment was completed before October 1, 2004 and the site contains “possibly sensitive” features, the assessment must be updated in accordance with the *Instructions to Geologists* (TCEQ-0585 Instructions).

Technical Review

1. When an application is deemed administratively complete, the technical review period begins. The regional office will distribute copies of the application to the identified affected city, county, and groundwater conservation district whose jurisdiction includes the subject site. These entities and the public have 30 days to provide comments on the application to the regional office. All comments received are reviewed by TCEQ.
2. A site assessment is usually conducted as part of the technical review, to evaluate the geologic assessment and observe existing site conditions. The site must be accessible to our staff. The site boundaries should be

clearly marked, features identified in the geologic assessment should be flagged, roadways marked and the alignment of the Sewage Collection System and manholes should be staked at the time the application is submitted. If the site is not marked the application may be returned.

3. We evaluate the application for technical completeness and contact the applicant and agent via Notice of Deficiency (NOD) to request additional information and identify technical deficiencies. There are two deficiency response periods available to the applicant. There are 14 days to resolve deficiencies noted in the first NOD. If a second NOD is issued, there is an additional 14 days to resolve deficiencies. If the response to the second notice is not received, is incomplete or inadequate, or provides new information that is incomplete or inadequate, the application must be withdrawn or will be denied. Please note that because the technical review is underway, whether the application is withdrawn or denied **the application fee will be forfeited**.
4. The program has 90 calendar days to complete the technical review of the application. If the application is technically adequate, such that it complies with the Edwards Aquifer rules, and is protective of the Edwards Aquifer during and after construction, an approval letter will be issued. Construction or other regulated activity may not begin until an approval is issued.

Mid-Review Modifications

It is important to have final site plans prior to beginning the permitting process with TCEQ to avoid delays.

Occasionally, circumstances arise where you may have significant design and/or site plan changes after your Edwards Aquifer application has been deemed administratively complete by TCEQ. This is considered a “Mid-Review Modification”. Mid-Review Modifications may require redistribution of an application that includes the proposed modifications for public comment.

If you are proposing a Mid-Review Modification, two options are available:

- If the technical review has begun your application can be denied/withdrawn, your fees will be forfeited, and the plan will have to be resubmitted.
- TCEQ can continue the technical review of the application as it was submitted, and a modification application can be submitted at a later time.

If the application is denied/withdrawn, the resubmitted application will be subject to the administrative and technical review processes and will be treated as a new application. The application will be redistributed to the affected jurisdictions.

Please contact the regional office if you have questions. If your project is located in Williamson, Travis, or Hays County, contact TCEQ’s Austin Regional Office at 512-339-2929. If your project is in Comal, Bexar, Medina, Uvalde, or Kinney County, contact TCEQ’s San Antonio Regional Office at 210-490-3096

Please fill out all required fields below and submit with your application.

1. Regulated Entity Name: ATX Pickleplex					2. Regulated Entity No.: N/A				
3. Customer Name: Pickleplex Properties LLC					4. Customer No.: N/A				
5. Project Type: (Please circle/check one)	<input checked="" type="radio"/> New	Modification			Extension		Exception		
6. Plan Type: (Please circle/check one)	WPAP	<input checked="" type="radio"/> CZP	SCS	UST	AST	EXP	EXT	Technical Clarification	Optional Enhanced Measures
7. Land Use: (Please circle/check one)	Residential		<input checked="" type="radio"/> Non-residential			8. Site (acres):		3.47 acres	
9. Application Fee:	\$4,650		10. Permanent BMP(s):			Yes			
11. SCS (Linear Ft.):			12. AST/UST (No. Tanks):			N/A			
13. County:	Williamson		14. Watershed:			Brushy Creek			

Application Distribution

Instructions: Use the table below to determine the number of applications required. One original and one copy of the application, plus additional copies (as needed) for each affected incorporated city, county, and groundwater conservation district are required. Linear projects or large projects, which cross into multiple jurisdictions, can require additional copies. Refer to the “Texas Groundwater Conservation Districts within the EAPP Boundaries” map found at:

http://www.tceq.texas.gov/assets/public/compliance/field_ops/eapp/EAPP%20GWCD%20map.pdf

For more detailed boundaries, please contact the conservation district directly.

Austin Region			
County:	Hays	Travis	Williamson
Original (1 req.)	—	—	<u>X</u>
Region (1 req.)	—	—	<u>X</u>
County(ies)	—	—	<u>X</u>
Groundwater Conservation District(s)	<input type="checkbox"/> Edwards Aquifer Authority <input type="checkbox"/> Barton Springs/ Edwards Aquifer <input type="checkbox"/> Hays Trinity <input type="checkbox"/> Plum Creek	<input type="checkbox"/> Barton Springs/ Edwards Aquifer	NA
City(ies) Jurisdiction	<input type="checkbox"/> Austin <input type="checkbox"/> Buda <input type="checkbox"/> Dripping Springs <input type="checkbox"/> Kyle <input type="checkbox"/> Mountain City <input type="checkbox"/> San Marcos <input type="checkbox"/> Wimberley <input type="checkbox"/> Woodcreek	<input type="checkbox"/> Austin <input type="checkbox"/> Bee Cave <input type="checkbox"/> Pflugerville <input type="checkbox"/> Rollingwood <input type="checkbox"/> Round Rock <input type="checkbox"/> Sunset Valley <input type="checkbox"/> West Lake Hills	<input type="checkbox"/> Austin <input checked="" type="checkbox"/> Cedar Park <input type="checkbox"/> Florence <input type="checkbox"/> Georgetown <input type="checkbox"/> Jerrell <input type="checkbox"/> Leander <input type="checkbox"/> Liberty Hill <input type="checkbox"/> Pflugerville <input type="checkbox"/> Round Rock

San Antonio Region					
County:	Bexar	Comal	Kinney	Medina	Uvalde
Original (1 req.)	—	—	—	—	—
Region (1 req.)	—	—	—	—	—
County(ies)	—	—	—	—	—
Groundwater Conservation District(s)	<input type="checkbox"/> Edwards Aquifer Authority <input type="checkbox"/> Trinity-Glen Rose	<input type="checkbox"/> Edwards Aquifer Authority	<input type="checkbox"/> Kinney	<input type="checkbox"/> EAA <input type="checkbox"/> Medina	<input type="checkbox"/> EAA <input type="checkbox"/> Uvalde
City(ies) Jurisdiction	<input type="checkbox"/> Castle Hills <input type="checkbox"/> Fair Oaks Ranch <input type="checkbox"/> Helotes <input type="checkbox"/> Hill Country Village <input type="checkbox"/> Hollywood Park <input type="checkbox"/> San Antonio (SAWS) <input type="checkbox"/> Shavano Park	<input type="checkbox"/> Bulverde <input type="checkbox"/> Fair Oaks Ranch <input type="checkbox"/> Garden Ridge <input type="checkbox"/> New Braunfels <input type="checkbox"/> Schertz	NA	<input type="checkbox"/> San Antonio ETJ (SAWS)	NA

I certify that to the best of my knowledge, that the application is complete and accurate. This application is hereby submitted to TCEQ for administrative review and technical review.

Steven Minor, P.E.

Print Name of Customer/Authorized Agent



8/19/24

Signature of Customer/Authorized Agent

Date

****FOR TCEQ INTERNAL USE ONLY****

Date(s) Reviewed:		Date Administratively Complete:	
Received From:		Correct Number of Copies:	
Received By:		Distribution Date:	
EAPP File Number:		Complex:	
Admin. Review(s) (No.):		No. AR Rounds:	
Delinquent Fees (Y/N):		Review Time Spent:	
Lat./Long. Verified:		SOS Customer Verification:	
Agent Authorization Complete/Notarized (Y/N):		Fee Check:	Payable to TCEQ (Y/N):
Core Data Form Complete (Y/N):			Signed (Y/N):
Core Data Form Incomplete Nos.:			Less than 90 days old (Y/N):

**Contributing Zone Plan Application
(TCEQ-10257)**

Contributing Zone Plan Application

Texas Commission on Environmental Quality

for Regulated Activities on the Contributing Zone to the Edwards Aquifer and Relating to 30 TAC §213.24(1), Effective June 1, 1999

To ensure that the application is administratively complete, confirm that all fields in the form are complete, verify that all requested information is provided, consistently reference the same site and contact person in all forms in the application, and ensure forms are signed by the appropriate party.

Note: Including all the information requested in the form and attachments contributes to more streamlined technical reviews.

Signature

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. This **Contributing Zone Plan Application** is hereby submitted for TCEQ review and Executive Director approval. The application was prepared by:

Print Name of Customer/Agent: Steven Minor, P.E

Date: 8/19/2024

Signature of Customer/Agent:



Regulated Entity Name: ATX Pickleplex

Project Information

1. County: Williamson
2. Stream Basin: Brushy Creek
3. Groundwater Conservation District (if applicable): N/A
4. Customer (Applicant):

Contact Person: Bill Parodi

Entity: PicklePlex Holdings LLC

Mailing Address: 3725 Copper Ridge Ct.

City, State: Austin, TX

Telephone: 512-348-0011

Email Address: billparodi2@gmail.com

Zip: 78734

Fax: N/A

5. Agent/Representative (If any):

Contact Person: Steven Minor, P.E.

Entity: Gray Engineering, Inc.

Mailing Address: 8834 N. Capital of Texas Highway, Suite 140

City, State: Austin, TX

Zip: 78759

Telephone: 512-452-0371

Fax: 512-454-9933

Email Address: sminor@grayengineeringinc.com

6. Project Location:

- The project site is located inside the city limits of Cedar Park.
- The project site is located outside the city limits but inside the ETJ (extra-territorial jurisdiction) of _____.
- The project site is not located within any city's limits or ETJ.

7. The location of the project site is described below. Sufficient detail and clarity has been provided so that the TCEQ's Regional staff can easily locate the project and site boundaries for a field investigation.

Address is 501 Cypress Creek Road, Cedar Park, TX 78613. The site is located in Cedar Park. Approximately .4 miles west from the intersection of Highway 183 and Cypress Creek Road. As well as .3 miles east from the intersection of Cluck Creek Trail and Cypress Creek Road.

8. **Attachment A - Road Map.** A road map showing directions to and the location of the project site is attached. The map clearly shows the boundary of the project site.
9. **Attachment B - USGS Quadrangle Map.** A copy of the official 7 ½ minute USGS Quadrangle Map (Scale: 1" = 2000') is attached. The map(s) clearly show:
- Project site boundaries.
 - USGS Quadrangle Name(s).
10. **Attachment C - Project Narrative.** A detailed narrative description of the proposed project is attached. The project description is consistent throughout the application and contains, at a minimum, the following details:
- Area of the site
 - Offsite areas
 - Impervious cover
 - Permanent BMP(s)
 - Proposed site use
 - Site history
 - Previous development
 - Area(s) to be demolished

11. Existing project site conditions are noted below:

- Existing commercial site
- Existing industrial site
- Existing residential site
- Existing paved and/or unpaved roads
- Undeveloped (Cleared)
- Undeveloped (Undisturbed/Not cleared)
- Other: _____

12. The type of project is:

- Residential: # of Lots: _____
- Residential: # of Living Unit Equivalents: _____
- Commercial
- Industrial
- Other: _____

13. Total project area (size of site): 3.47 Acres

Total disturbed area: 3.47 Acres

14. Estimated projected population: N/A

15. The amount and type of impervious cover expected after construction is complete is shown below:

Table 1 - Impervious Cover

<i>Impervious Cover of Proposed Project</i>	<i>Sq. Ft.</i>	<i>Sq. Ft./Acre</i>	<i>Acres</i>
Structures/Rooftops	43,545	÷ 43,560 =	1.00
Parking	57,290	÷ 43,560 =	1.31
Other paved surfaces	7,339	÷ 43,560 =	.17
Total Impervious Cover	108,174	÷ 43,560 =	2.48

Total Impervious Cover 2.48 ÷ Total Acreage 3.47 X 100 = 71.5% Impervious Cover

- 16. **Attachment D - Factors Affecting Surface Water Quality.** A detailed description of all factors that could affect surface water quality is attached. If applicable, this includes the location and description of any discharge associated with industrial activity other than construction.
- 17. Only inert materials as defined by 30 TAC 330.2 will be used as fill material.

For Road Projects Only

Complete questions 18 - 23 if this application is exclusively for a road project.

N/A

18. Type of project:

- TXDOT road project.
- County road or roads built to county specifications.
- City thoroughfare or roads to be dedicated to a municipality.
- Street or road providing access to private driveways.

19. Type of pavement or road surface to be used:

- Concrete
- Asphaltic concrete pavement
- Other: _____

20. Right of Way (R.O.W.):

Length of R.O.W.: _____ feet.

Width of R.O.W.: _____ feet.

$L \times W = \text{_____ Ft}^2 \div 43,560 \text{ Ft}^2/\text{Acre} = \text{_____ acres.}$

21. Pavement Area:

Length of pavement area: _____ feet.

Width of pavement area: _____ feet.

$L \times W = \text{_____ Ft}^2 \div 43,560 \text{ Ft}^2/\text{Acre} = \text{_____ acres.}$

Pavement area _____ acres \div R.O.W. area _____ acres $\times 100 = \text{_____}\%$ impervious cover.

22. A rest stop will be included in this project.

A rest stop will not be included in this project.

23. Maintenance and repair of existing roadways that do not require approval from the TCEQ Executive Director. Modifications to existing roadways such as widening roads/adding shoulders totaling more than one-half (1/2) the width of one (1) existing lane require prior approval from the TCEQ.

Stormwater to be generated by the Proposed Project

24. **Attachment E - Volume and Character of Stormwater.** A detailed description of the volume (quantity) and character (quality) of the stormwater runoff which is expected to occur from the proposed project is attached. The estimates of stormwater runoff quality and quantity are based on area and type of impervious cover. Include the runoff coefficient of the site for both pre-construction and post-construction conditions.

Wastewater to be generated by the Proposed Project

25. Wastewater is to be discharged in the contributing zone. Requirements under 30 TAC §213.6(c) relating to Wastewater Treatment and Disposal Systems have been satisfied.

N/A

26. Wastewater will be disposed of by:

On-Site Sewage Facility (OSSF/Septic Tank):

Attachment F - Suitability Letter from Authorized Agent. An on-site sewage facility will be used to treat and dispose of the wastewater from this site. The appropriate licensing authority's (authorized agent) written approval is attached. It states that the land is suitable for the use of private sewage facilities and will meet or exceed the requirements for on-site sewage facilities as specified under 30 TAC Chapter 285 relating to On-site Sewage Facilities.

Each lot in this project/development is at least one (1) acre (43,560 square feet) in size. The system will be designed by a licensed professional engineer or registered sanitarian and installed by a licensed installer in compliance with 30 TAC Chapter 285.

Sewage Collection System (Sewer Lines):

The sewage collection system will convey the wastewater to the Cedar Park Wastewater (name) Treatment Plant. The treatment facility is:

Existing.

Proposed.

N/A

Permanent Aboveground Storage Tanks(ASTs) ≥ 500 Gallons

Complete questions 27 - 33 if this project includes the installation of AST(s) with volume(s) greater than or equal to 500 gallons.

N/A

27. Tanks and substance stored:

Table 2 - Tanks and Substance Storage

<i>AST Number</i>	<i>Size (Gallons)</i>	<i>Substance to be Stored</i>	<i>Tank Material</i>
1			
2			
3			

<i>AST Number</i>	<i>Size (Gallons)</i>	<i>Substance to be Stored</i>	<i>Tank Material</i>
4			
5			

Total x 1.5 = _____ Gallons

28. The AST will be placed within a containment structure that is sized to capture one and one-half (1 1/2) times the storage capacity of the system. For facilities with more than one tank system, the containment structure is sized to capture one and one-half (1 1/2) times the cumulative storage capacity of all systems.

Attachment G - Alternative Secondary Containment Methods. Alternative methods for providing secondary containment are proposed. Specifications showing equivalent protection for the Edwards Aquifer are attached.

29. Inside dimensions and capacity of containment structure(s):

Table 3 - Secondary Containment

<i>Length (L)(Ft.)</i>	<i>Width(W)(Ft.)</i>	<i>Height (H)(Ft.)</i>	<i>L x W x H = (Ft3)</i>	<i>Gallons</i>

Total: _____ Gallons

30. Piping:

- All piping, hoses, and dispensers will be located inside the containment structure.
- Some of the piping to dispensers or equipment will extend outside the containment structure.
- The piping will be aboveground
- The piping will be underground

31. The containment area must be constructed of and in a material impervious to the substance(s) being stored. The proposed containment structure will be constructed of: _____.

32. **Attachment H - AST Containment Structure Drawings.** A scaled drawing of the containment structure is attached that shows the following:

- Interior dimensions (length, width, depth and wall and floor thickness).
- Internal drainage to a point convenient for the collection of any spillage.
- Tanks clearly labeled
- Piping clearly labeled

- Dispenser clearly labeled
33. Any spills must be directed to a point convenient for collection and recovery. Spills from storage tank facilities must be removed from the controlled drainage area for disposal within 24 hours of the spill.
- In the event of a spill, any spillage will be removed from the containment structure within 24 hours of the spill and disposed of properly.
- In the event of a spill, any spillage will be drained from the containment structure through a drain and valve within 24 hours of the spill and disposed of properly. The drain and valve system are shown in detail on the scaled drawing.

Site Plan Requirements

Items 34 - 46 must be included on the Site Plan.

34. The Site Plan must have a minimum scale of 1" = 400'.
Site Plan Scale: 1" = 30'.
35. 100-year floodplain boundaries:
- Some part(s) of the project site is located within the 100-year floodplain. The floodplain is shown and labeled.
- No part of the project site is located within the 100-year floodplain.
The 100-year floodplain boundaries are based on the following specific (including date of material) sources(s): FEMA Flood Map Service Eff. 12/20/2019.
36. The layout of the development is shown with existing and finished contours at appropriate, but not greater than ten-foot contour intervals. Lots, recreation centers, buildings, roads, etc. are shown on the site plan.
- The layout of the development is shown with existing contours at appropriate, but not greater than ten-foot contour intervals. Finished topographic contours will not differ from the existing topographic configuration and are not shown. Lots, recreation centers, buildings, roads, etc. are shown on the site plan.
37. A drainage plan showing all paths of drainage from the site to surface streams.
38. The drainage patterns and approximate slopes anticipated after major grading activities.
39. Areas of soil disturbance and areas which will not be disturbed.
40. Locations of major structural and nonstructural controls. These are the temporary and permanent best management practices.
41. Locations where soil stabilization practices are expected to occur.
42. Surface waters (including wetlands).
 N/A

43. Locations where stormwater discharges to surface water.
 There will be no discharges to surface water.
44. Temporary aboveground storage tank facilities.
 Temporary aboveground storage tank facilities will not be located on this site.
45. Permanent aboveground storage tank facilities.
 Permanent aboveground storage tank facilities will not be located on this site.
46. Legal boundaries of the site are shown.

Permanent Best Management Practices (BMPs)

Practices and measures that will be used during and after construction is completed.

47. Permanent BMPs and measures must be implemented to control the discharge of pollution from regulated activities after the completion of construction.
 N/A
48. These practices and measures have been designed, and will be constructed, operated, and maintained to insure that 80% of the incremental increase in the annual mass loading of total suspended solids (TSS) from the site caused by the regulated activity is removed. These quantities have been calculated in accordance with technical guidance prepared or accepted by the executive director.
 The TCEQ Technical Guidance Manual (TGM) was used to design permanent BMPs and measures for this site.
 A technical guidance other than the TCEQ TGM was used to design permanent BMPs and measures for this site. The complete citation for the technical guidance that was used is: _____.
 N/A
49. Owners must insure that permanent BMPs and measures are constructed and function as designed. A Texas Licensed Professional Engineer must certify in writing that the permanent BMPs or measures were constructed as designed. The certification letter must be submitted to the appropriate regional office within 30 days of site completion.
 N/A
50. Where a site is used for low density single-family residential development and has 20 % or less impervious cover, other permanent BMPs are not required. This exemption from permanent BMPs must be recorded in the county deed records, with a notice that if the percent impervious cover increases above 20% or land use changes, the exemption for the whole site as described in the property boundaries required by 30 TAC §213.4(g) (relating to Application Processing and Approval), may no longer apply and the property owner must notify the appropriate regional office of these changes.

- The site will be used for low density single-family residential development and has 20% or less impervious cover.
- The site will be used for low density single-family residential development but has more than 20% impervious cover.
- The site will not be used for low density single-family residential development.

51. The executive director may waive the requirement for other permanent BMPs for multi-family residential developments, schools, or small business sites where 20% or less impervious cover is used at the site. This exemption from permanent BMPs must be recorded in the county deed records, with a notice that if the percent impervious cover increases above 20% or land use changes, the exemption for the whole site as described in the property boundaries required by 30 TAC §213.4(g) (relating to Application Processing and Approval), may no longer apply and the property owner must notify the appropriate regional office of these changes.

- Attachment I - 20% or Less Impervious Cover Waiver.** The site will be used for multi-family residential developments, schools, or small business sites and has 20% or less impervious cover. A request to waive the requirements for other permanent BMPs and measures is attached.
- The site will be used for multi-family residential developments, schools, or small business sites but has more than 20% impervious cover.
- The site will not be used for multi-family residential developments, schools, or small business sites.

52. **Attachment J - BMPs for Upgradient Stormwater.**

- A description of the BMPs and measures that will be used to prevent pollution of surface water, groundwater, or stormwater that originates upgradient from the site and flows across the site is attached.
- No surface water, groundwater or stormwater originates upgradient from the site and flows across the site, and an explanation is attached.
- Permanent BMPs or measures are not required to prevent pollution of surface water, groundwater, or stormwater that originates upgradient from the site and flows across the site, and an explanation is attached.

53. **Attachment K - BMPs for On-site Stormwater.**

- A description of the BMPs and measures that will be used to prevent pollution of surface water or groundwater that originates on-site or flows off the site, including pollution caused by contaminated stormwater runoff from the site is attached.
- Permanent BMPs or measures are not required to prevent pollution of surface water or groundwater that originates on-site or flows off the site, including pollution caused by contaminated stormwater runoff, and an explanation is attached.

54. **Attachment L - BMPs for Surface Streams.** A description of the BMPs and measures that prevent pollutants from entering surface streams is attached.

N/A

55. **Attachment M - Construction Plans.** Construction plans and design calculations for the proposed permanent BMPs and measures have been prepared by or under the direct supervision of a Texas Licensed Professional Engineer, and are signed, sealed, and dated. Construction plans for the proposed permanent BMPs and measures are attached and include: Design calculations, TCEQ Construction Notes, all proposed structural plans and specifications, and appropriate details.

N/A

56. **Attachment N - Inspection, Maintenance, Repair and Retrofit Plan.** A site and BMP specific plan for the inspection, maintenance, repair, and, if necessary, retrofit of the permanent BMPs and measures is attached. The plan fulfills all of the following:

Prepared and certified by the engineer designing the permanent BMPs and measures

Signed by the owner or responsible party

Outlines specific procedures for documenting inspections, maintenance, repairs, and, if necessary, retrofit.

Contains a discussion of record keeping procedures

N/A

57. **Attachment O - Pilot-Scale Field Testing Plan.** Pilot studies for BMPs that are not recognized by the Executive Director require prior approval from the TCEQ. A plan for pilot-scale field testing is attached.

N/A

58. **Attachment P - Measures for Minimizing Surface Stream Contamination.** A description of the measures that will be used to avoid or minimize surface stream contamination and changes in the way in which water enters a stream as a result of the construction and development is attached. The measures address increased stream flashing, the creation of stronger flows and in-stream velocities, and other in-stream effects caused by the regulated activity, which increase erosion that result in water quality degradation.

N/A

Responsibility for Maintenance of Permanent BMPs and Measures after Construction is Complete.

59. The applicant is responsible for maintaining the permanent BMPs after construction until such time as the maintenance obligation is either assumed in writing by another entity having ownership or control of the property (such as without limitation, an owner's association, a new property owner or lessee, a district, or municipality) or the ownership of the property is transferred to the entity. Such entity shall then be


responsible for maintenance until another entity assumes such obligations in writing or ownership is transferred.

60. A copy of the transfer of responsibility must be filed with the executive director at the appropriate regional office within 30 days of the transfer if the site is for use as a multiple single-family residential development, a multi-family residential development, or a non-residential development such as commercial, industrial, institutional, schools, and other sites where regulated activities occur.


Administrative Information

61. Submit one (1) original and one (1) copy of the application, plus additional copies as needed for each affected incorporated city, groundwater conservation district, and county in which the project will be located. The TCEQ will distribute the additional copies to these jurisdictions.
62. Any modification of this Contributing Zone Plan may require TCEQ review and Executive Director approval prior to construction, and may require submission of a revised application, with appropriate fees.
63. The site description, controls, maintenance, and inspection requirements for the storm water pollution prevention plan (SWPPP) developed under the EPA NPDES general permits for stormwater discharges have been submitted to fulfill paragraphs 30 TAC §213.24(1-5) of the technical report. All requirements of 30 TAC §213.24(1-5) have been met by the SWPPP document.
- The Temporary Stormwater Section (TCEQ-0602) is included with the application.

ATTACHMENT A - ROAD MAP



LOCATION MAP
1"=2 MILES



PHASE MAP
1"=2000'


PROJECT SITE



Produced by the United States Geological Survey

North American Datum of 1983 (NAD83)
World Geodetic System of 1984 (WGS84). Projection and
1 000-meter grid/Universal Transverse Mercator, Zone 14R.
This map is not a legal document. Boundaries may be
generalized for this map scale. Private lands within government
reservations may not be shown. Obtain permission before
entering private lands.

Imagery	N.A.I.P., September 2016 - November 2016
Roads	U.S. Census Bureau, 2015 - 2019
Names	G.N.S., 1979 - 2022
Hydrography	National Hydrography Dataset, 2002 - 2020
Contours	National Elevation Dataset, 2019
Boundaries	Multiple sources; see metadata file 2019 - 2021
Wetlands	FWS National Wetlands Inventory, Not Available



QUADRANGLE LOCATION

1	2	3
4	5	6
7	8	

ADJOINING QUADRANGLES

- 1 Nameless
- 2 Leander
- 3 Round Rock
- 4 Mansfield Dam
- 5 Pflugerville West
- 6 Bee Cave
- 7 Austin West
- 8 Austin East

ROAD CLASSIFICATION	
	Expressway
	Secondary Hwy
	Ramp
	Interstate Route
	US Route
	State Route
	Local Connector
	Local Road
	4WD



Attachment C

Project Narrative

ATX Pickleplex is a 3.47 Acre proposed Commercial development located in Williamson County. It is located between US Hwy 183 and Anderson Mill Rd, just south of Cluck Creek. The proposed development will consist of 1 building with two different finish floor sections to house an indoor pickleball facility and appurtenances. The proposed total impervious cover within the site is approximately 71.5% percent including buildings, streets, and other paved surfaces.

During construction, Temporary Best Management Practices (BMPs) will include the use of a temporary stabilized construction entrance/exit, silt fencing, rock berms, and a staging area/spoil site (see construction plans, Attachment M, Erosion and Sedimentation Control Sheet) Location and type of temporary BMPs have been selected to control erosion and sedimentation in accordance with RG-348 - Complying with the Edwards Aquifer Rules Technical Guidance on Best Management Practices. The permanent BMP proposed for this site will be a Batch Detention Pond and Engineered vegetated filter strips.

The proposed batch detention pond will have a water quality depth of 2.28 feet at a volume of 11,892 cubic feet of storage. The required storage volume for the proposed development is 11,892 cubic feet. The batch detention pond will follow the requirements of the RG-348. Additionally Engineered vegetative filter strips will be utilized to remove the remainder of the TSS load required for the site. The filter strips follow the requirements of the RG-348.

The site is currently undeveloped, except for an existing neighbor drive, gravel access road and some existing utilities. The gravel access road is to be removed as needed. The existing utilities will remain as is. Existing trees will be removed as needed for this project.

In the existing condition this site accepts minimal offsite flows from ROW of Cypress Creek Road, along the southern border of the site. The site is designed to keep flow patterns as close as possible to existing conditions, thus the site will continue to accept these offsite flows in the proposed condition.

Attachment D

Factors Affecting Surface Water Quality

The water quality may be affected during construction by rainfall runoff carrying sediment, vehicle oils, waxes, paint, concrete curing compounds, trash and any other customary construction site pollutants from the open construction area. During construction, Temporary Best Management Practices (BMPs) will include the use of a temporary stabilized construction entrance/exit, silt fencing, rock berms, and a staging area/spoil site (see construction plans, Attachment M, Erosion and Sedimentation Control Sheet). Location and type of temporary BMPs have been selected to control erosion and sedimentation in accordance with RG-348 - Complying with the Edwards Aquifer Rules Technical Guidance on Best Management Practices.

After construction, runoff from the impervious cover areas carrying sediment, vehicle oils, waxes, herbicides, pesticides, and any other normal pollutants attributed to Commercial sites may affect the water quality.

Attachment E

Volume and Character of Stormwater

The proposed site is designed to maintain existing flow patterns. Stormwater from this site currently drains directly into Cluck Creek Tributary and will continue to do so. The impervious cover for the developed project is contained in the following table.

Total Impervious Area	2.48 ac
Structures/Roof	1.00 ac
Parking/Pavement	1.31 ac
Other Paved	0.17 ac
Impervious Cover %	71.5%

See construction plan set (Attachment M) for individual drainage areas and runoff coefficients for pre-developed and post-developed flows. The expected flow was calculated using Atlas 14 method. HEC-HMS was the program used for drainage modeling calculations. Time of concentration, and flow for each drainage can also be found in Attachment M.

It is expected that the character of surface water and ground water run-off would be consistent with Commercial development. Runoff from the impervious cover areas may include sediment, vehicle oils, waxes, herbicides, pesticides, and any other normal pollutants attributed to commercial sites.

The site will utilize a batch detention pond and filter strips to capture the TSS created from the proposed development as well as the increase in runoff from the additional impervious cover.

ATTACHMENT J

BMPs FOR UP-GRADIENT STORMWATER

In the existing condition this site accepts offsite flows from the edge of the ROW from Cypress Creek Road, along the southern border of the site. These flows bypass the site and do not flow across the site or to any permanent BMPs. Flows have not been altered to keep flow patterns as close as possible to existing conditions.

ATTACHMENT K

BMPs FOR ONSITE STORMWATER

During construction, Temporary Best Management Practices (BMPs) will include the use of a temporary stabilized construction entrance/exit, silt fencing, rock berms, and a staging area/spoil site (see construction plans, Attachment M, Erosion and Sedimentation Control Sheet) Location and type of temporary BMPs have been selected to control erosion and sedimentation in accordance with RG-348 - Complying with the Edwards Aquifer Rules Technical Guidance on Best Management Practices.

This site will be used for commercial development and will have approximately 71.5% impervious cover. In the contributing zone, permanent BMPs will consist of one (1) batch detention pond and an Engineered vegetative filter strip both designed in accordance with TCEQ's Technical Guidance Manual (TGM) RG-348.

Batch detention basins capture and temporarily detain the water quality volume from a storm event, for a period of 12-48 hours, using an automated controller and valve. The batch detention outfall details and logic controls can be found on the Proposed Pond Plan and Pond Details sheets.

ATTACHMENT L

BMPs FOR SURFACE STREAMS

No streams run through this site. Portions of the existing drainage flow into Cluck Creek Tributary at the north end of the site.

For protection of these surface streams, during construction, Temporary Best Management Practices (BMPs) will include the use of a temporary stabilized construction entrance/exit, silt fencing, rock berms, and a staging area/spoil site (see construction plans, Attachment M, Erosion and Sedimentation Control Sheet) Location and type of temporary BMPs have been selected to control erosion and sedimentation in accordance with RG-348 - Complying with the Edwards Aquifer Rules Technical Guidance on Best Management Practices.

ATTACHMENT N

INSPECTION, MAINTENANCE, REPAIR AND RETROFIT PLAN

Batch Detention Basins

Inspections

Inspections should take place a minimum of twice a year. One inspection should take place during wet weather to determine if the basin is meeting the target detention time of 12 hours and a drawdown time of no more than 48 hours. The remaining inspections should occur between storm events so that manual operation of the valve and controller can be verified. The level sensor in the basin should be inspected and any debris or sediment in the area should be removed. The outlet structure and the trash screen should be inspected for signs of clogging. Debris and sediment should be removed from the orifice and outlet(s) as described in previous sections. Debris obstructing the valve should be removed. During each inspection, erosion areas inside and downstream of this BMP should be identified and repaired/revegetated immediately.

Mowing

The basin, basin side-slopes, and embankment of the basin must be mowed to prevent woody growth and control weeds. A mulching mower should be used, or the grass clippings should be caught and removed. Mowing should take place at least twice a year, or more frequently if vegetation exceeds 18 inches in height. More frequent mowing to maintain aesthetic appeal may be necessary in landscaped areas.

Litter and Debris Removal

Litter and debris removal should take place at least twice a year, as part of the periodic mowing operations and inspections. Debris and litter should be removed from the surface of the basin. Particular attention should be paid to floatable debris around the outlet structure. The outlet should be checked for possible clogging or obstructions and any debris removed.

Erosion control

The basin side slopes and embankment all may periodically suffer from slumping and erosion. To correct these problems, corrective action, such as regrading and revegetation, may be necessary. Correction of erosion control should take place whenever required based on the periodic inspections.

Nuisance Control

Standing water or soggy conditions may occur in the basin. Some standing water may occur after a storm event since the valve may close with 2 to 3 inches of water in the basin. Some flow into the basin may also occur between storms due to spring flow and residential water use that enters the storm sewer system. Twice a year, the facility should be evaluated in terms of nuisance control (insects, weeds, odors, algae, etc.).

Structural Repairs and Replacement

With each inspection, any damage to structural elements of the basin (pipes, concrete drainage structures, retaining walls, etc.) should be identified and repaired immediately. An example of this type of repair can include patching of cracked concrete, sealing of voids, removal of vegetation from cracks and joints. The various inlet/outlet structures in a basin will eventually deteriorate and must be replaced.

Sediment Removal

A properly designed batch detention basin will accumulate quantities of sediment over time. The accumulated sediment can detract from the appearance of the facility and reduce the pollutant removal performance of the facility. The sediment also tends to accumulate near the outlet structure and can interfere with the level sensor operation. Sediment shall be removed from the basin at least every 5 years, when sediment depth exceeds 6 inches, when the sediment interferes with the level sensor or when the basin does not drain within 48 hours. Care should be taken not to compromise the basin lining during maintenance.

Logic Controller

The Logic Controller should be inspected as part of the twice yearly investigations. Verify that the external indicators (active, cycle in progress) are operating properly by turning the controller off and on, and by initiating a cycle by triggering the level sensor in the basin. The valve should be manually opened and closed using the open/close switch to verify valve operation and to assist in inspecting the valve for debris. The solar panel should be inspected and any dust or debris on the panel should be carefully removed. The controller and all other circuitry and wiring should be inspected for signs of corrosion, damage from insects, water leaks, or other damage. At the end of the inspection, the controller should be reset.

Vegetative Filter Strips

Pest Management

An Integrated Pest Management (IPM) Plan should be developed for vegetated areas. This plan should specify how problem insects and weeds will be controlled with minimal or no use of insecticides and herbicides.

Seasonal Mowing and Lawn Care

If the filter strip is made up of turf grass, it should be mowed as needed to limit vegetation height to 18 inches, using a mulching mower (or removal of clippings). If native grasses are used, the filter may require less frequent mowing, but a minimum of twice annually. Grass clippings and brush debris should not be deposited on vegetated filter strip areas. Regular mowing should also include weed control practices, however herbicide use should be kept to a minimum (Urbonas et al., 1992). Healthy grass can be maintained without using fertilizers because runoff usually contains sufficient nutrients. Irrigation of the site can help assure a dense and healthy vegetative cover.

Inspection

Inspect filter strips at least twice annually for erosion or damage to vegetation; however,

additional inspection after periods of heavy runoff is most desirable. The strip should be checked for uniformity of grass cover, debris and litter, and areas of sediment accumulation. More frequent inspections of the grass cover during the first few years after establishment will help to determine if any problems are developing, and to plan for long-term restorative maintenance needs. Bare spots and areas of erosion identified during semi-annual inspections must be replanted and restored to meet specifications. Construction of a level spreader device may be necessary to reestablish shallow overland flow.

Debris and Litter Removal

Trash tends to accumulate in vegetated areas, particularly along highways. Any filter strip structures (i.e. level spreaders) should be kept free of obstructions to reduce floatables being flushed downstream, and for aesthetic reasons. The need for this practice is determined through periodic inspection, but should be performed no less than 4 times per year.

Sediment Removal

Sediment removal is not normally required in filter strips, since the vegetation normally grows through it and binds it to the soil. However, sediment may accumulate along the upstream boundary of the strip preventing uniform overland flow. Excess sediment should be removed by hand or with flat-bottomed shovels.

Grass Reseeding and Mulching

A healthy dense grass should be maintained on the filter strip. If areas are eroded, they should be filled, compacted, and reseeded so that the final grade is level. Grass damaged during the sediment removal process should be promptly replaced using the same seed mix used during filter strip establishment. If possible, flow should be diverted from the damaged areas until the grass is firmly established. Bare spots and areas of erosion identified during semi-annual inspections must be replanted and restored to meet specifications. Corrective maintenance, such as weeding or replanting should be done more frequently in the first two to three years after installation to ensure stabilization. Dense vegetation may require irrigation immediately after planting, and during particularly dry periods, particularly as the vegetation is initially established.

The owner is responsible for operation and maintenance of the detention/water quality pond after the improvements have been constructed and accepted. All inspections, maintenance and repair will be documented, and accurate records of maintenance and repair work shall be kept by the owner.

I, Steven Minor, P.E., authorized representative for Bill Parodi, the owner of the water quality pond tracts and engineered vegetative filter strip, have read these procedures and am aware that these items need to be taken care of in order to keep the water quality ponds and engineered vegetative filter strip functioning properly.



Signature

8/19/2024

Date

Attachment P

Measures for Minimizing Surface Stream Contamination

Portions of the site drain into Cluck Creek Tributary.

For protection of these surface streams, during construction, Temporary Best Management Practices (BMPs) will include the use of a temporary stabilized construction entrance/exit, silt fencing, rock berms, and a staging area/spoil site (see construction plans, Attachment M, Erosion and Sedimentation Control Sheet) Location and type of temporary BMPs have been selected to control erosion and sedimentation in accordance with RG-348 - Complying with the Edwards Aquifer Rules Technical Guidance on Best Management Practices. Once all site grading activities have been completed all disturbed areas will be hydro mulched and seeded to revegetate all exposed soil areas. All controls will remain in place until the revegetated areas have become permanently stabilized.

This site will be used for commercial development and will have approximately 71.5% impervious cover. Batch pond device and engineered vegetative filter strips will be put in place for permanent BMPs.

Temporary Stormwater Section
(TCEQ-0602)

Temporary Stormwater Section

Texas Commission on Environmental Quality

for Regulated Activities on the Edwards Aquifer Recharge Zone and Relating to 30 TAC §213.5(b)(4)(A), (B), (D)(I) and (G); Effective June 1, 1999

To ensure that the application is administratively complete, confirm that all fields in the form are complete, verify that all requested information is provided, consistently reference the same site and contact person in all forms in the application, and ensure forms are signed by the appropriate party.

Note: Including all the information requested in the form and attachments contributes to more streamlined technical reviews.

Signature

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. This **Temporary Stormwater Section** is hereby submitted for TCEQ review and executive director approval. The application was prepared by:

Print Name of Customer/Agent: Steven Minor, P.E

Date: 8/19/2024

Signature of Customer/Agent:



Regulated Entity Name: ATX Pickleplex

Project Information

Potential Sources of Contamination

Examples: Fuel storage and use, chemical storage and use, use of asphaltic products, construction vehicles tracking onto public roads, and existing solid waste.

1. Fuels for construction equipment and hazardous substances which will be used during construction:

The following fuels and/or hazardous substances will be stored on the site: _____

These fuels and/or hazardous substances will be stored in:

- Aboveground storage tanks with a cumulative storage capacity of less than 250 gallons will be stored on the site for less than one (1) year.

- Aboveground storage tanks with a cumulative storage capacity between 250 gallons and 499 gallons will be stored on the site for less than one (1) year.
- Aboveground storage tanks with a cumulative storage capacity of 500 gallons or more will be stored on the site. An Aboveground Storage Tank Facility Plan application must be submitted to the appropriate regional office of the TCEQ prior to moving the tanks onto the project.
- Fuels and hazardous substances will not be stored on the site.
- 2. **Attachment A - Spill Response Actions.** A site specific description of the measures to be taken to contain any spill of hydrocarbons or hazardous substances is attached.
- 3. Temporary aboveground storage tank systems of 250 gallons or more cumulative storage capacity must be located a minimum horizontal distance of 150 feet from any domestic, industrial, irrigation, or public water supply well, or other sensitive feature.
- 4. **Attachment B - Potential Sources of Contamination.** A description of any activities or processes which may be a potential source of contamination affecting surface water quality is attached.

Sequence of Construction

- 5. **Attachment C - Sequence of Major Activities.** A description of the sequence of major activities which will disturb soils for major portions of the site (grubbing, excavation, grading, utilities, and infrastructure installation) is attached.
 - For each activity described, an estimate (in acres) of the total area of the site to be disturbed by each activity is given.
 - For each activity described, include a description of appropriate temporary control measures and the general timing (or sequence) during the construction process that the measures will be implemented.
- 6. Name the receiving water(s) at or near the site which will be disturbed or which will receive discharges from disturbed areas of the project: Cluck Creek Tributary

Temporary Best Management Practices (TBMPs)

Erosion control examples: tree protection, interceptor swales, level spreaders, outlet stabilization, blankets or matting, mulch, and sod. Sediment control examples: stabilized construction exit, silt fence, filter dikes, rock berms, buffer strips, sediment traps, and sediment basins. Please refer to the Technical Guidance Manual for guidelines and specifications. All structural BMPs must be shown on the site plan.

- 7. **Attachment D – Temporary Best Management Practices and Measures.** TBMPs and measures will prevent pollution of surface water, groundwater, and stormwater. The construction-phase BMPs for erosion and sediment controls have been designed to retain sediment on site to the extent practicable. The following information is attached:

- A description of how BMPs and measures will prevent pollution of surface water, groundwater or stormwater that originates upgradient from the site and flows across the site.
 - A description of how BMPs and measures will prevent pollution of surface water or groundwater that originates on-site or flows off site, including pollution caused by contaminated stormwater runoff from the site.
 - A description of how BMPs and measures will prevent pollutants from entering surface streams, sensitive features, or the aquifer.
 - A description of how, to the maximum extent practicable, BMPs and measures will maintain flow to naturally-occurring sensitive features identified in either the geologic assessment, TCEQ inspections, or during excavation, blasting, or construction.
8. The temporary sealing of a naturally-occurring sensitive feature which accepts recharge to the Edwards Aquifer as a temporary pollution abatement measure during active construction should be avoided.
- Attachment E - Request to Temporarily Seal a Feature.** A request to temporarily seal a feature is attached. The request includes justification as to why no reasonable and practicable alternative exists for each feature.
 - There will be no temporary sealing of naturally-occurring sensitive features on the site.
9. **Attachment F - Structural Practices.** A description of the structural practices that will be used to divert flows away from exposed soils, to store flows, or to otherwise limit runoff discharge of pollutants from exposed areas of the site is attached. Placement of structural practices in floodplains has been avoided.
10. **Attachment G - Drainage Area Map.** A drainage area map supporting the following requirements is attached:
- For areas that will have more than 10 acres within a common drainage area disturbed at one time, a sediment basin will be provided.
 - For areas that will have more than 10 acres within a common drainage area disturbed at one time, a smaller sediment basin and/or sediment trap(s) will be used.
 - For areas that will have more than 10 acres within a common drainage area disturbed at one time, a sediment basin or other equivalent controls are not attainable, but other TBMPs and measures will be used in combination to protect down slope and side slope boundaries of the construction area.
 - There are no areas greater than 10 acres within a common drainage area that will be disturbed at one time. A smaller sediment basin and/or sediment trap(s) will be used in combination with other erosion and sediment controls within each disturbed drainage area.

- There are no areas greater than 10 acres within a common drainage area that will be disturbed at one time. Erosion and sediment controls other than sediment basins or sediment traps within each disturbed drainage area will be used.
11. **Attachment H - Temporary Sediment Pond(s) Plans and Calculations.** Temporary sediment pond or basin construction plans and design calculations for a proposed temporary BMP or measure have been prepared by or under the direct supervision of a Texas Licensed Professional Engineer. All construction plans and design information must be signed, sealed, and dated by the Texas Licensed Professional Engineer. Construction plans for the proposed temporary BMPs and measures are attached.
- N/A
12. **Attachment I - Inspection and Maintenance for BMPs.** A plan for the inspection of each temporary BMP(s) and measure(s) and for their timely maintenance, repairs, and, if necessary, retrofit is attached. A description of the documentation procedures, recordkeeping practices, and inspection frequency are included in the plan and are specific to the site and/or BMP.
13. All control measures must be properly selected, installed, and maintained in accordance with the manufacturer's specifications and good engineering practices. If periodic inspections by the applicant or the executive director, or other information indicate a control has been used inappropriately, or incorrectly, the applicant must replace or modify the control for site situations.
14. If sediment escapes the construction site, off-site accumulations of sediment must be removed at a frequency sufficient to minimize offsite impacts to water quality (e.g., fugitive sediment in street being washed into surface streams or sensitive features by the next rain).
15. Sediment must be removed from sediment traps or sedimentation ponds not later than when design capacity has been reduced by 50%. A permanent stake will be provided that can indicate when the sediment occupies 50% of the basin volume.
16. Litter, construction debris, and construction chemicals exposed to stormwater shall be prevented from becoming a pollutant source for stormwater discharges (e.g., screening outfalls, picked up daily).

Soil Stabilization Practices

Examples: establishment of temporary vegetation, establishment of permanent vegetation, mulching, geotextiles, sod stabilization, vegetative buffer strips, protection of trees, or preservation of mature vegetation.

17. **Attachment J - Schedule of Interim and Permanent Soil Stabilization Practices.** A schedule of the interim and permanent soil stabilization practices for the site is attached.

18. Records must be kept at the site of the dates when major grading activities occur, the dates when construction activities temporarily or permanently cease on a portion of the site, and the dates when stabilization measures are initiated.
19. Stabilization practices must be initiated as soon as practicable where construction activities have temporarily or permanently ceased.

Administrative Information

20. All structural controls will be inspected and maintained according to the submitted and approved operation and maintenance plan for the project.
21. If any geologic or manmade features, such as caves, faults, sinkholes, etc., are discovered, all regulated activities near the feature will be immediately suspended. The appropriate TCEQ Regional Office shall be immediately notified. Regulated activities must cease and not continue until the TCEQ has reviewed and approved the methods proposed to protect the aquifer from any adverse impacts.
22. Silt fences, diversion berms, and other temporary erosion and sediment controls will be constructed and maintained as appropriate to prevent pollutants from entering sensitive features discovered during construction.

Attachment A

Spill Response Actions

In the event of an accidental leak or spill:

First, the spill must be contained, and the area staked off and/or rock and earth berms constructed as required, to prevent further contamination. Then, any spill of reportable quantity, as shown at the end of this attachment, should be reported to the TCEQ as soon as possible (no later than 24 hours from the occurrence) to one of the following:

1. The Region 11 Office, 512-339-2929
2. The TCEQ toll free number, 1-800-832-8224
3. The TCEQ 24-hour location, 512-463-7727 or 512-239-2507

The information to be reported should include: the reporter's name, address and telephone number, the date, time and location of the spill, an identification of what substance or substances have been spilled and the approximate amount, the approximate duration of the spill, the name of the surface water or description of the waters of the state that are affected by the spill, the sources of the spill, an approximate description of the extent of water pollution or impacts to the environment that the spill may have, a description of any environmentally sensitive areas or natural resources at risk, a description of any and all actions being taken to contain the spill, any anticipated health risks, any other governmental representatives and local authorities that are responding to the spill, and any other pertinent information regarding the spill.

All site personnel should also be made aware of the manufacturer's recommended methods for spill cleanup and the location of the information and supplies. Materials and equipment necessary for spill clean-up will be kept onsite in an accessible location. All spills will be cleaned up upon discovery and any spill of hydrocarbons or hazardous substances greater than 25 gallons will require notification of the Fire Departments Hazardous Materials team as well as the TCEQ.

After the spill has been contained and cleaned up, site personnel should make any necessary follow-up reports with the TCEQ.

The reportable quantities are:

Reportable Quantities (RQ's) According to the Spill Rule (copied from TNRCC Reg. Guidance. RG-285)

Type of spill	Site of Spill	
	On Land	In Water
Hazardous Substance		
If CERCLA RQ = 1-100 lb	CERCLA RQ	CERCLA RQ
If CERCLA RQ > 100 lb	CERCLA RQ	100 lb
Crude Oil		
Used Oil or petroleum product		
At a PST exempt facility*	210 gal	Enough to form a sheen
All others	25 gal	Enough to form a sheen
Oil other than crude oil, used oil or petroleum product		
Other Substances		
Industrial solid waste		
	No RQ	100 lb
	No RQ	100 lb

Note: This table applies only to the reporting of spills and discharges according to the spill rule, 30 TAC §§327.1-327.5. To find values of CERCLA RQs for hazardous substances, please refer to 40 CFR Table 302.4

* The term "PST exempt facility" refers to facilities that are exempt from the Aboveground Storage Tank Program. Petrochemical plants, petroleum refineries, and electricity generation, transmission, and distribution facilities are some examples of PST exempt facilities.

CERCLA refers to the Comprehensive Emergency Response, Compensation and Liability Act

Attachment B

Potential Sources of Contamination

Potential sources of contamination include fueling of construction vehicles, gasoline, diesel, and hydraulic fluid from construction equipment, asphalt products, construction materials, tracking mud onto the roadway, trash and debris, short-term storage and use of fertilizers for use in establishing vegetation paint, concrete, and gypsum from sheet rock. All materials shall be hauled in a manner consistent with the manufacturer's recommendations. Disposal of waste material shall be in conformance with Local Laws. Contractor will provide receipts from landfill as verification of proper disposal of waste material. The contractor will not be allowed to dispose of any waste material on-site. All activities will be conducted in a manner to minimize the potential for impact to the environment.

Attachment C

Sequence of Major Activities

The estimated total area to be disturbed during construction is shown in the plan set on the "Erosion and Sedimentation Control Plan" as the limits of construction, which is approximately 3.68 acres. Stormwater deposits to make it to Cluck Creek. The sequence of construction is as follows:

- 1) Call Department of Public works and Transportation, Development engineer construction department, and the environmental and construction services department 48 hours prior to beginning any work. Call the One Call center for utility locations.
- 2) Temporary erosion and sedimentation controls are to be installed as indicated on the approved site plan or construction plan and in accordance with the Erosion Sedimentation Control Plan (ESC). Install tree protection and initiate tree mitigation measures prior to any clearing, grading, excavating, etc.
- 3) Hold pre-construction conference with contractor, design-engineer/permit applicant
- 4) Begin construction of project as follows:
 - a) Demolition of existing facilities (0.15 acres)
 - b) Place materials (2.14 acres)
 - c) Excavate (1.05 acres)
 - d) Install all utilities (0.5 acres)
 - e) Inspect temporary erosion controls on a regular basis and adjust the controls and/or remove any sediment buildup.
 - f) Complete all rough grading, underground utilities, and ensure that all underground utility crossings are completed. (3.47 acres)
 - g) Lay final pavement and install all pavement markings & signs according to plans (3.47 acres)
 - h) Complete all necessary final grading and dress up of areas disturbed during construction. (3.47 acres)
 - i) Ensure areas are revegetated and stabilized (3.47 acres)
 - j) Remove and dispose of temporary erosion control devices.
- 5) Hold post-construction conference on site with the contractor, design engineer, owner's representative, and the county's inspector.
- 6) Provide as-built mark-up drawings to the engineer

Attachment D

Temporary Best Management Practices and Measures

Silt fencing will be used during the periods of construction near the perimeter of the disturbed area to intercept sediment while allowing water to percolate through, prevent excessive sediment build up, and prevent sediment from escaping around edges of silt fence. This silt fence will remain in place until the disturbed area is permanently stabilized. Temporary berms will be used in place of silt fence in areas of greater discharge.

A stabilized pad of crushed stone will be placed at the points where traffic will be entering and leaving the construction site to eliminate the tracking or flowing of sediment onto public rights-of-way. The entrance may require periodic top dressing with additional sediment. All sediment spoiled, dropped, washed or tracked onto public right-of-way must be removed immediately by the contractor.

Concrete washout areas will be placed to prevent or reduce the discharge of pollutants to stormwater from concrete waste. Concrete washout areas shall be at least 50 feet from sensitive features, storm drains, open ditches, or water bodies. Onsite concrete wastes will be washed into the temporary washout areas where the concrete can set, be broken up, and be disposed of properly.

Dust control can prevent blowing and movement of dust from exposed soil surfaces, reduce on-site and off-site damage, health hazards and improve traffic safety. Dust control will be implemented at the site during all phases of construction.

Site preparation, which is the initiation of all activity on the project, will disturb the largest amount of soil. Therefore, before any of the work can begin within a phase, the clearing and grading contractor will be responsible for the installation of all on-site control measures within that phase. The methodology for pollution prevention of on-site stormwater will include: (1) erection of silt fences along the downgradient boundary of construction activities for temporary erosion and sedimentation controls, (2) installation of stabilized construction entrance/exit(s), as necessary to reduce the dispersion of sediment from the site

BMP measures utilized in this plan are intended to allow stormwater to continue downstream after passing through the BMPs. This will allow stormwater runoff to continue downgradient to features that may exist downstream of the BMP.

Post construction of improvements and prior to project acceptance, the limits of disturbance shall be revegetated.

Attachment E
Request to Temporarily Seal a Feature

N/A

Attachment F

Structural Practices

The following structural measures will be put in place prior to the installation of site preparation activities.

- Erection of silt fences along the downgradient boundary of construction activities and rock berms for secondary protection.
- Installation of stabilized construction entrance/exit(s) as necessary

Attachment G

Drainage Area Map

An exhibit has been included that depicts the existing site topography as well as the proposed erosion and sedimentation control locations. Please refer to the “Overall Drainage Area Map” Sheets of the attached construction plan set for the Drainage Area Map.

Attachment H
Temporary Sediment Pond Plans and Calculations

N/A

Attachment I

Inspection and Maintenance for BMPs

Best Management Practices installed during construction will be maintained in accordance with the recommendations found in the TCEQ Technical Guidance Manual. The following maintenance procedures shall be followed until permanent stabilization occurs.

Silt Fence

- a. Inspect weekly or after each rainfall event and repair or replacement shall be made promptly as needed.
- b. Silt fence shall be removed when the site is completely stabilized so as to not block or impede storm flow or drainage.
- c. Accumulated silt shall be removed when it reaches a depth of 6 inches. The silt shall be disposed of on an approved site and in such a manner that will not contribute to additional siltation.

Rock Berm

- a. Inspect weekly or after each rain and the stone and/or fabric core-woven sheathing shall be replaced when the structure ceases to function as intended due to silt accumulation among the rocks, washout, construction traffic damage, etc. event and repair or replacement shall be made promptly as needed.
- b. When silt reaches a depth equal to one-third the height of the berm or 6", whichever is less, the silt shall be disposed of on an approved site and in such a manner that will not contribute to additional siltation.
- c. Accumulated silt shall be removed when it reaches a depth of 6 inches. The silt shall be disposed of on an approved site and in such a manner that will not contribute to additional siltation.
- d. Severe service rock berms shall be inspected daily. Silt shall be removed when it reaches a depth of 6"
- e. Rock berms shall be removed when the site is completely stabilized so as to not block or impede storm flow or drainage.

Stabilized Construction Entrance

- a. The entrance shall be maintained in a condition that will prevent tracking or flowing of sediment onto public roadway. This may require periodic top dressing with additional stone as conditions demand, as well as repair and clean out of any devices used to trap sediment.
- b. Entrance must be properly graded to incorporate a drain swale or a similar measure to prevent runoff from leaving the construction site.

Concrete Washout

- a. Incorporate requirements for concrete waste management into material supplier and subcontractor agreements.
- b. Avoid mixing excess amounts of fresh concrete.
- c. Perform washout of concrete trucks in designated areas only.
- d. Do not wash out concrete trucks into storm drains, open ditches, streets, or streams.
- e. Do not allow excess concrete to be dumped onsite, except in designated areas

Attachment J

Schedule of Interim and Permanent Soil Stabilization Practices

The following is a schedule of interim and permanent soil stabilization practices:

- Prior to site disturbance
Install all temporary erosion and sedimentation control features.
- During construction
Maintain all temporary erosion and sedimentation control structures. Inspect all temporary erosion and sedimentation control structures on a weekly and/or daily basis and after all rain events.
- After completion of construction
Install all permanent erosion and sedimentation controls.
- After completion of permanent controls
Remove all temporary erosion and sedimentation control features.

Interim on-site stabilization measures, which are continuous, will include minimizing soil disturbance by exposing the smallest practical area of land required for the shortest period of time and maximizing use of natural vegetation. As soon as practical, all disturbed soil will be stabilized as per project specifications in accordance with TCEQ's Technical Guidance Manual (TGM). Mulching, netting, erosion blankets and seeding are acceptable.

Once all site grading activities have been completed all disturbed areas will be hydro mulched and seeded to revegetate all exposed soil areas. All controls will remain in place until the revegetated areas have become permanently stabilized.

Should construction activities be interrupted for a period of at least 4 weeks of non-activity, Contractor shall revegetate all disturbed areas as required for permanent revegetation. Contractor shall keep all temporary BMPs in place until the disturbed areas become permanently stabilized.

**Copy of Notice of Intent
(NOI)**



Notice of Intent (NOI) for an Authorization for Stormwater Discharges Associated with Construction Activity under TPDES General Permit TXR150000

IMPORTANT INFORMATION

Please read and use the General Information and Instructions prior to filling out each question in the NOI form.

Use the NOI Checklist to ensure all required information is completed correctly.

Incomplete applications delay approval or result in automatic denial.

Once processed your permit authorization can be viewed by entering the following link into your internet browser: http://www2.tceq.texas.gov/wq_dpa/index.cfm or you can contact TCEQ Stormwater Processing Center at 512-239-3700.

ePERMITS

Effective September 1, 2018, this paper form must be submitted to TCEQ with a completed electronic reporting waiver form (TCEQ-20754).

To submit an NOI electronically, enter the following web address into your internet browser and follow the instructions: <https://www3.tceq.texas.gov/steers/index.cfm>

APPLICATION FEE AND PAYMENT

The application fee for submitting a paper NOI is \$325. The application fee for electronic submittal of a NOI through the TCEQ ePermits system (STEERS) is \$225.

Payment of the application fee can be submitted by mail or through the TCEQ ePay system. The payment and the NOI must be mailed to separate addresses. To access the TCEQ ePay system enter the following web address into your internet browser: <http://www.tceq.texas.gov/epay>.

Provide your payment information for verification of payment:

- If payment was mailed to TCEQ, provide the following:
 - Check/Money Order Number: [REDACTED]
 - Name printed on Check: [REDACTED]
- If payment was made via ePay, provide the following:
 - Voucher Number: [REDACTED]
 - A copy of the payment voucher is attached to this paper NOI form.

RENEWAL (This portion of the NOI is not applicable after June 3, 2018)

Is this NOI for a renewal of an existing authorization? Yes No

If Yes, provide the authorization number here: TXR15 [REDACTED]

NOTE: If an authorization number is not provided, a new number will be assigned.

SECTION 1. OPERATOR (APPLICANT)

a) If the applicant is currently a customer with TCEQ, what is the Customer Number (CN) issued to this entity? CN TO BE ISSUED WITH CZP APPLICATION

(Refer to Section 1.a) of the Instructions)

b) What is the Legal Name of the entity (applicant) applying for this permit? (The legal name must be spelled exactly as filed with the Texas Secretary of State, County, or in the legal document forming the entity.)

PicklePlex Holdings LLC

c) What is the contact information for the Operator (Responsible Authority)?

Prefix (Mr. Ms. Miss): Mr.

First and Last Name: Bill Parodi Suffix: N/A

Title: Owner Credentials: N/A

Phone Number: 512-348-0011 Fax Number: N/A

E-mail: billparodi2@gmail.com

Mailing Address: 3725 Copper Ridge Ct.

City, State, and Zip Code: Austin, TX 78734

Mailing Information if outside USA:

Territory: [REDACTED]

Country Code: [REDACTED] Postal Code: [REDACTED]

d) Indicate the type of customer:

- | | |
|---|---|
| <input type="checkbox"/> Individual | <input type="checkbox"/> Federal Government |
| <input type="checkbox"/> Limited Partnership | <input type="checkbox"/> County Government |
| <input type="checkbox"/> General Partnership | <input type="checkbox"/> State Government |
| <input type="checkbox"/> Trust | <input type="checkbox"/> City Government |
| <input type="checkbox"/> Sole Proprietorship (D.B.A.) | <input type="checkbox"/> Other Government |
| <input checked="" type="checkbox"/> Corporation | <input type="checkbox"/> Other: |
| <input type="checkbox"/> Estate | |

e) Is the applicant an independent operator? Yes No

(If a governmental entity, a subsidiary, or part of a larger corporation, check No.)

f) Number of Employees. Select the range applicable to your company.

0-20

251-500

21-100

501 or higher

101-250

g) Customer Business Tax and Filing Numbers: (**Required** for Corporations and Limited Partnerships. **Not Required** for Individuals, Government, or Sole Proprietors.)

State Franchise Tax ID Number: 32091137870

Federal Tax ID: 93-2983000

Texas Secretary of State Charter (filing) Number: 0805189776

DUNS Number (if known): N/A

SECTION 2. APPLICATION CONTACT

Is the application contact the same as the applicant identified above?

Yes, go to Section 3

No, complete this section

Prefix (Mr. Ms. Miss): Mr.

First and Last Name: Steven Minor Suffix: P.E.

Title: Principal Credential: N/A

Organization Name: Gray Engineering

Phone Number: 512-452-0371 Fax Number: N/A

E-mail: sminor@grayengineeringinc.com

Mailing Address: 8834 N. Capital of Texas Highway, Suite 140

Internal Routing (Mail Code, Etc.): N/A

City, State, and Zip Code: Austin, TX 78759

Mailing information if outside USA:

Territory:

Country Code:

Postal Code:

SECTION 3. REGULATED ENTITY (RE) INFORMATION ON PROJECT OR SITE

a) If this is an existing permitted site, what is the Regulated Entity Number (RN) issued to this site? RN TO BE ISSUED WITH CZP APPLICATION

(Refer to Section 3.a) of the Instructions)

- b) Name of project or site (the name known by the community where it's located): ATX Pickleplex
- c) In your own words, briefly describe the type of construction occurring at the regulated site (residential, industrial, commercial, or other): Indoor Recreation Commercial Development
- d) County or Counties (if located in more than one): Williamson
- e) Latitude: 30.497120820905412, Longitude: -97.82209834047435
- f) Site Address/Location

If the site has a physical address such as 12100 Park 35 Circle, Austin, TX 78753, complete *Section A*.

If the site does not have a physical address, provide a location description in *Section B*. Example: located on the north side of FM 123, 2 miles west of the intersection of FM 123 and Highway 1.

Section A:

Street Number and Name: 501 Cypress Creek Road

City, State, and Zip Code: Cedar Park, TX 78613

Section B:

Location Description:

City (or city nearest to) where the site is located:

Zip Code where the site is located:

SECTION 4. GENERAL CHARACTERISTICS

- a) Is the project or site located on Indian Country Lands?
 - Yes, do not submit this form. You must obtain authorization through EPA Region 6.
 - No
- b) Is your construction activity associated with a facility that, when completed, would be associated with the exploration, development, or production of oil or gas or geothermal resources?
 - Yes. Note: The construction stormwater runoff may be under jurisdiction of the Railroad Commission of Texas and may need to obtain authorization through EPA Region 6.
 - No
- c) What is the Primary Standard Industrial Classification (SIC) Code that best describes the construction activity being conducted at the site? 1542
- d) What is the Secondary SIC Code(s), if applicable? 7999
- e) What is the total number of acres to be disturbed? 3.47
- f) Is the project part of a larger common plan of development or sale?

Yes

No. The total number of acres disturbed, provided in e) above, must be 5 or more. If the total number of acres disturbed is less than 5, do not submit this form. See the requirements in the general permit for small construction sites.

g) What is the estimated start date of the project? June 2024

h) What is the estimated end date of the project? Nov 2024

i) Will concrete truck washout be performed at the site? Yes No

j) What is the name of the first water body(ies) to receive the stormwater runoff or potential runoff from the site? Cluck Creek Tributary

k) What is the segment number(s) of the classified water body(ies) that the discharge will eventually reach? 1244D

l) Is the discharge into a Municipal Separate Storm Sewer System (MS4)?

Yes No

If Yes, provide the name of the MS4 operator:

Note: The general permit requires you to send a copy of this NOI form to the MS4 operator.

m) Is the discharge or potential discharge from the site within the Recharge Zone, Contributing Zone, or Contributing Zone within the Transition Zone of the Edwards Aquifer, as defined in 30 TAC Chapter 213?

Yes, complete the certification below.

No, go to Section 5

I certify that the copy of the TCEQ-approved Plan required by the Edwards Aquifer Rule (30 TAC Chapter 213) that is included or referenced in the Stormwater Pollution Prevention Plan will be implemented. Yes

SECTION 5. NOI CERTIFICATION

a) I certify that I have obtained a copy and understand the terms and conditions of the Construction General Permit (TXR150000). Yes

b) I certify that the full legal name of the entity applying for this permit has been provided and is legally authorized to do business in Texas. Yes

c) I understand that a Notice of Termination (NOT) must be submitted when this authorization is no longer needed. Yes

d) I certify that a Stormwater Pollution Prevention Plan has been developed, will be implemented prior to construction and to the best of my knowledge and belief is compliant with any applicable local sediment and erosion control plans, as required in the Construction General Permit (TXR150000). Yes

Note: For multiple operators who prepare a shared SWP3, the confirmation of an operator may be limited to its obligations under the SWP3, provided all obligations are confirmed by at least one operator.

SECTION 6. APPLICANT CERTIFICATION SIGNATURE

Operator Signatory Name: Steven Minor, P.E.

Operator Signatory Title: Principal

I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations.

I further certify that I am authorized under 30 Texas Administrative Code §305.44 to sign and submit this document, and can provide documentation in proof of such authorization upon request.

Signature (use blue ink):  Date: 8/19/2024

NOTICE OF INTENT CHECKLIST (TXR150000)

Did you complete everything? Use this checklist to be sure!

Are you ready to mail your form to TCEQ? Go to the General Information Section of the Instructions for mailing addresses.

Confirm each item (or applicable item) in this form is complete. This checklist is for use by the applicant to ensure a complete application is being submitted. **Missing information may result in denial of coverage under the general permit.** (See NOI process description in the General Information and Instructions.)

APPLICATION FEE

If paying by check:

- Check was mailed **separately** to the TCEQs Cashier's Office. (See Instructions for Cashier's address and Application address.)
- Check number and name on check is provided in this application.

If using ePay:

- The voucher number is provided in this application and a copy of the voucher is attached.

RENEWAL

- If this application is for renewal of an existing authorization, the authorization number is provided.

OPERATOR INFORMATION

- Customer Number (CN) issued by TCEQ Central Registry
- Legal name as filed to do business in Texas. (Call TX SOS 512-463-5555 to verify.)
- Name and title of responsible authority signing the application.
- Phone number and e-mail address
- Mailing address is complete & verifiable with USPS. www.usps.com
- Type of operator (entity type). Is applicant an independent operator?
- Number of employees.
- For corporations or limited partnerships - Tax ID and SOS filing numbers.
- Application contact and address is complete & verifiable with USPS. <http://www.usps.com>

REGULATED ENTITY (RE) INFORMATION ON PROJECT OR SITE

- Regulated Entity Number (RN) (if site is already regulated by TCEQ)
- Site/project name and construction activity description
- County
- Latitude and longitude <http://www.tceq.texas.gov/gis/sqmaview.html>

- Site Address/Location. Do not use a rural route or post office box.

GENERAL CHARACTERISTICS

- Indian Country Lands -the facility is not on Indian Country Lands.
- Construction activity related to facility associated to oil, gas, or geothermal resources
- Primary SIC Code that best describes the construction activity being conducted at the site.
www.osha.gov/oshstats/sicser.html
- Estimated starting and ending dates of the project.
- Confirmation of concrete truck washout.
- Acres disturbed is provided and qualifies for coverage through a NOI.
- Common plan of development or sale.
- Receiving water body or water bodies.
- Segment number or numbers.
- MS4 operator.
- Edwards Aquifer rule.

CERTIFICATION

- Certification statements have been checked indicating Yes.
- Signature meets 30 Texas Administrative Code (TAC) §305.44 and is original.

Instructions for Notice of Intent (NOI) for Stormwater Discharges Associated with Construction Activity under TPDES General Permit (TXR150000)

GENERAL INFORMATION

Where to Send the Notice of Intent (NOI):

By Regular Mail:

TCEQ

Stormwater Processing Center (MC228)

P.O. Box 13087

Austin, Texas 78711-3087

By Overnight or Express Mail:

TCEQ

Stormwater Processing Center (MC228)

12100 Park 35 Circle

Austin, TX

Application Fee:

The application fee of \$325 is required to be paid at the time the NOI is submitted. Failure to submit payment at the time the application is filed will cause delays in acknowledgment or denial of coverage under the general permit. Payment of the fee may be made by check or money order, payable to TCEQ, or through EPAY (electronic payment through the web).

Mailed Payments:

Use the attached General Permit Payment Submittal Form. The application fee is submitted to a different address than the NOI. Read the General Permit Payment Submittal Form for further instructions, including the address to send the payment.

ePAY Electronic Payment: <http://www.tceq.texas.gov/epay>

When making the payment you must select Water Quality, and then select the fee category "General Permit Construction Storm Water Discharge NOI Application". You must include a copy of the payment voucher with your NOI. Your NOI will not be considered complete without the payment voucher.

TCEQ Contact List:

Application – status and form questions:

512-239-3700, swpermit@tceq.texas.gov

Technical questions:

512-239-4671, swgp@tceq.texas.gov

Environmental Law Division:

512-239-0600

Records Management - obtain copies of forms:

512-239-0900

Reports from databases (as available):

512-239-DATA (3282)

Cashier's office:

512-239-0357 or 512-239-0187

Notice of Intent Process:

When your NOI is received by the program, the form will be processed as follows:

- **Administrative Review:** Each item on the form will be reviewed for a complete response. In addition, the operator's legal name must be verified with Texas Secretary of State as valid and active (if applicable). The address(es) on the form must be verified with the US Postal service as receiving regular mail delivery. Do not give an overnight/express mailing address.

- **Notice of Deficiency:** If an item is incomplete or not verifiable as indicated above, a notice of deficiency (NOD) will be mailed to the operator. The operator will have 30 days to respond to the NOD. The response will be reviewed for completeness.
- **Acknowledgment of Coverage:** An Acknowledgment Certificate will be mailed to the operator. This certificate acknowledges coverage under the general permit.

or

Denial of Coverage: If the operator fails to respond to the NOD or the response is inadequate, coverage under the general permit may be denied. If coverage is denied, the operator will be notified.

General Permit (Your Permit)

For NOIs submitted **electronically** through ePermits, provisional coverage under the general permit begins immediately following confirmation of receipt of the NOI form by the TCEQ.

For **paper** NOIs, provisional coverage under the general permit begins **7 days after a completed NOI is postmarked for delivery** to the TCEQ.

You should have a copy of your general permit when submitting your application. You may view and print your permit for which you are seeking coverage, on the TCEQ web site <http://www.tceq.texas.gov>. Search using keyword TXR150000.

Change in Operator

An authorization under the general permit is not transferable. If the operator of the regulated project or site changes, the present permittee must submit a Notice of Termination and the new operator must submit a Notice of Intent. The NOT and NOI must be submitted no later than 10 days prior to the change in Operator status.

TCEQ Central Registry Core Data Form

The Core Data Form has been incorporated into this form. Do not send a Core Data Form to TCEQ. After final acknowledgment of coverage under the general permit, the program will assign a Customer Number and Regulated Entity Number, if one has not already been assigned to this customer or site.

For existing customers and sites, you can find the Customer Number and Regulated Entity Number by entering the following web address into your internet browser: <http://www15.tceq.texas.gov/crpub/> or you can contact the TCEQ Stormwater Processing Center at 512-239-3700 for assistance. On the website, you can search by your permit number, the Regulated Entity (RN) number, or the Customer Number (CN). If you do not know these numbers, you can select “Advanced Search” to search by permittee name, site address, etc.

The Customer (Permittee) is responsible for providing consistent information to the TCEQ, and for updating all CN and RN data for all authorizations as changes occur. For this permit, a Notice of Change form must be submitted to the program area.

INSTRUCTIONS FOR FILLING OUT THE NOI FORM

Renewal of General Permit. Dischargers holding active authorizations under the expired General Permit are required to submit a NOI to continue coverage. The existing permit number is required. If the permit number is not provided or has been terminated, expired, or denied, a new permit number will be issued.

Section 1. OPERATOR (APPLICANT)

a) Customer Number (CN)

TCEQ's Central Registry will assign each customer a number that begins with CN, followed by nine digits. **This is not a permit number, registration number, or license number.**

If the applicant is an existing TCEQ customer, the Customer Number is available at the following website: <http://www15.tceq.texas.gov/crpub/>. If the applicant is not an existing TCEQ customer, leave the space for CN blank.

b) Legal Name of Applicant

Provide the current legal name of the applicant. The name must be provided exactly as filed with the Texas Secretary of State (SOS), or on other legal documents forming the entity, as filed in the county. You may contact the SOS at 512-463-5555, for more information related to filing in Texas. If filed in the county, provide a copy of the legal documents showing the legal name.

c) Contact Information for the Applicant (Responsible Authority)

Provide information for the person signing the application in the Certification section. This person is also referred to as the Responsible Authority.

Provide a complete mailing address for receiving mail from the TCEQ. The mailing address must be recognized by the US Postal Service. You may verify the address on the following website: <https://tools.usps.com/go/ZipLookupAction!input.action>.

The phone number should provide contact to the applicant.

The fax number and e-mail address are optional and should correspond to the applicant.

d) Type of Customer (Entity Type)

Check only one box that identifies the type of entity. Use the descriptions below to identify the appropriate entity type. Note that the selected entity type also indicates the name that must be provided as an applicant for an authorization.

Individual

An individual is a customer who has not established a business, but conducts an activity that needs to be regulated by the TCEQ.

Partnership

A customer that is established as a partnership as defined by the Texas Secretary of State Office (TX SOS). If the customer is a 'General Partnership' or 'Joint Venture' filed in the county (not filed with TX SOS), the legal name of each partner forming the 'General Partnership' or 'Joint Venture' must be provided. Each 'legal entity' must apply as a co-applicant.

Trust or Estate

A trust and an estate are fiduciary relationships governing the trustee/executor with respect to the trust/estate property.

Sole Proprietorship (DBA)

A sole proprietorship is a customer that is owned by only one person and has not been incorporated. This business may:

1. be under the person's name
2. have its own name (doing business as or DBA)
3. have any number of employees.

If the customer is a Sole Proprietorship or DBA, the 'legal name' of the individual business 'owner' must be provided. The DBA name is not recognized as the 'legal name' of the entity. The DBA name may be used for the site name (regulated entity).

Corporation

A customer that meets all of these conditions:

1. is a legally incorporated entity under the laws of any state or country
2. is recognized as a corporation by the Texas Secretary of State
3. has proper operating authority to operate in Texas

The corporation's 'legal name' as filed with the Texas Secretary of State must be provided as applicant. An 'assumed' name of a corporation is not recognized as the 'legal name' of the entity.

Government

Federal, state, county, or city government (as appropriate)

The customer is either an agency of one of these levels of government or the governmental body itself. The government agency's 'legal name' must be provided as the applicant. A department name or other description of the organization is not recognized as the 'legal name'.

Other

This may include a utility district, water district, tribal government, college district, council of governments, or river authority. Provide the specific type of government.

e) Independent Entity

Check No if this customer is a subsidiary, part of a larger company, or is a governmental entity. Otherwise, check Yes.

f) Number of Employees

Check one box to show the number of employees for this customer's entire company, at all locations. This is not necessarily the number of employees at the site named in the application.

g) Customer Business Tax and Filing Numbers

These are required for Corporations and Limited Partnerships. These are not required for Individuals, Government, and Sole Proprietors.

State Franchise Tax ID Number

Corporations and limited liability companies that operate in Texas are issued a franchise tax identification number. If this customer is a corporation or limited liability company, enter the Tax ID number.

Federal Tax ID

All businesses, except for some small sole proprietors, individuals, or general partnerships should have a federal taxpayer identification number (TIN). Enter this number here. Use no prefixes, dashes, or hyphens. Sole proprietors, individuals, or general partnerships do not need to provide a federal tax ID.

TX SOS Charter (filing) Number

Corporations and Limited Partnerships required to register with the Texas Secretary of State are issued a charter or filing number. You may obtain further information by calling SOS at 512-463-5555.

DUNS Number

Most businesses have a DUNS (Data Universal Numbering System) number issued by Dun and Bradstreet Corp. If this customer has one, enter it here.

Section 2. APPLICATION CONTACT

Provide the name and contact information for the person that TCEQ can contact for additional information regarding this application.

Section 3. REGULATED ENTITY (RE) INFORMATION ON PROJECT OR SITE

a) Regulated Entity Number (RN)

The RN is issued by TCEQ's Central Registry to sites where an activity is regulated by TCEQ. This is not a permit number, registration number, or license number. Search TCEQ's Central Registry to see if the site has an assigned RN at <http://www15.tceq.texas.gov/crpub/>. If this regulated entity has not been assigned an RN, leave this space blank.

If the site of your business is part of a larger business site, an RN may already be assigned for the larger site. Use the RN assigned for the larger site.

If the site is found, provide the assigned RN and provide the information for the site to be authorized through this application. The site information for this authorization may vary from the larger site information.

An example is a chemical plant where a unit is owned or operated by a separate corporation that is accessible by the same physical address of your unit or facility. Other examples include industrial parks identified by one common address but different corporations have control of defined areas within the site. In both cases, an RN would be assigned for the physical address location and the permitted sites would be identified separately under the same RN.

b) Name of the Project or Site

Provide the name of the site or project as known by the public in the area where the site is located. The name you provide on this application will be used in the TCEQ Central Registry as the Regulated Entity name.

c) Description of Activity Regulated

In your own words, briefly describe the primary business that you are doing that requires this authorization. Do not repeat the SIC Code description.

d) County

Provide the name of the county where the site or project is located. If the site or project is located in more than one county, provide the county names as secondary.

e) Latitude and Longitude

Enter the latitude and longitude of the site in degrees, minutes, and seconds or decimal form. For help obtaining the latitude and longitude, go to:

<http://www.tceq.texas.gov/gis/sqmaview.html>.

f) Site Address/Location

If a site has an address that includes a street number and street name, enter the complete address for the site in *Section A*. If the physical address is not recognized as a USPS delivery address, you may need to validate the address with your local police (911 service) or through an online map site used to locate a site. Please confirm this to be a complete and valid address. Do not use a rural route or post office box for a site location.

If a site does not have an address that includes a street number and street name, provide a complete written location description in *Section B*. For example: "The site is located on the north side of FM 123, 2 miles west of the intersection of FM 123 and Highway 1."

Provide the city (or nearest city) and zip code of the site location.

Section 4. GENERAL CHARACTERISTICS

a) Indian Country Lands

If your site is located on Indian Country Lands, the TCEQ does not have authority to process your application. You must obtain authorization through EPA Region 6, Dallas. Do not submit this form to TCEQ.

b) Construction activity associated with facility associated with exploration, development, or production of oil, gas, or geothermal resources

If your activity is associated with oil and gas exploration, development, or production, you may be under jurisdiction of the Railroad Commission of Texas (RRC) and may need to obtain authorization from EPA Region 6.

Construction activities associated with a facility related to oil, gas or geothermal resources may include the construction of a well site; treatment or storage facility; underground hydrocarbon or natural gas storage facility; reclamation plant; gas processing facility; compressor station; terminal facility where crude oil is stored prior to refining and at which refined products are stored solely for use at the facility; a carbon dioxide geologic storage facility; and a gathering, transmission, or distribution

pipeline that will transport crude oil or natural gas, including natural gas liquids, prior to refining of such oil or the use of the natural gas in any manufacturing process or as a residential or industrial fuel.

Where required by federal law, discharges of stormwater associated with construction activities under the RRC's jurisdiction must be authorized by the EPA and the RRC, as applicable. Activities under RRC jurisdiction include construction of a facility that, when completed, would be associated with the exploration, development, or production of oil or gas or geothermal resources, such as a well site; treatment or storage facility; underground hydrocarbon or natural gas storage facility; reclamation plant; gas processing facility; compressor station; terminal facility where crude oil is stored prior to refining and at which refined products are stored solely for use at the facility; a carbon dioxide geologic storage facility under the jurisdiction of the RRC; and a gathering, transmission, or distribution pipeline that will transport crude oil or natural gas, including natural gas liquids, prior to refining of such oil or the use of the natural gas in any manufacturing process or as a residential or industrial fuel. The RRC also has jurisdiction over stormwater from land disturbance associated with a site survey that is conducted prior to construction of a facility that would be regulated by the RRC. Under 33 U.S.C. §1342(l)(2) and §1362(24), EPA cannot require a permit for discharges of stormwater from field activities or operations associated with {oil and gas} exploration, production, processing, or treatment operations, or transmission facilities, including activities necessary to prepare a site for drilling and for the movement and placement of drilling equipment, whether or not such field activities or operations may be considered to be construction activities unless the discharge is contaminated by contact with any overburden, raw material, intermediate product, finished product, byproduct, or waste product located on the site of the facility. Under §3.8 of this title (relating to Water Protection), the RRC prohibits operators from causing or allowing pollution of surface or subsurface water. Operators are encouraged to implement and maintain best management practices (BMPs) to minimize discharges of pollutants, including sediment, in stormwater during construction activities to help ensure protection of surface water quality during storm events.

For more information about the jurisdictions of the RRC and the TCEQ, read the Memorandum of Understanding (MOU) between the RRC and TCEQ at 16 Texas Administrative Code, Part 1, Chapter 3, Rule 3.30, by entering the following link into an internet browser:

[http://texreg.sos.state.tx.us/public/readtac\\$ext.TacPage?sl=R&app=9&p_dir=&p_rloc=&p_tloc=&p_ploc=&pg=1&p_tac=&ti=16&pt=1&ch=3&rl=30](http://texreg.sos.state.tx.us/public/readtac$ext.TacPage?sl=R&app=9&p_dir=&p_rloc=&p_tloc=&p_ploc=&pg=1&p_tac=&ti=16&pt=1&ch=3&rl=30) or contact the TCEQ Stormwater Team at 512-239-4671 for additional information.

c) Primary Standard Industrial Classification (SIC) Code

Provide the SIC Code that best describes the construction activity being conducted at this site.

Common SIC Codes related to construction activities include:

- 1521 - Construction of Single Family Homes
- 1522 - Construction of Residential Buildings Other than Single Family Homes
- 1541 - Construction of Industrial Buildings and Warehouses

- 1542 - Construction of Non-residential Buildings, other than Industrial Buildings and Warehouses
- 1611 - Highway and Street Construction, except Highway Construction
- 1622 - Bridge, Tunnel, and Elevated Highway Construction
- 1623 - Water, Sewer, Pipeline and Communications, and Power Line Construction

For help with SIC Codes, enter the following link into your internet browser: <http://www.osha.gov/pls/imis/sicsearch.html> or you can contact the TCEQ Small Business and Local Government Assistance Section at 800-447-2827 for assistance.

d) Secondary SIC Code

Secondary SIC Code(s) may be provided. Leave this blank if not applicable. For help with SIC Codes, enter the following link into your internet browser: <http://www.osha.gov/pls/imis/sicsearch.html> or you can contact the TCEQ Small Business and Environmental Assistance Section at 800-447-2827 for assistance.

e) Total Number of Acres Disturbed

Provide the approximate number of acres that the construction site will disturb. Construction activities that disturb less than one acre, unless they are part of a larger common plan that disturbs more than one acre, do not require permit coverage. Construction activities that disturb between one and five acres, unless they are part of a common plan that disturbs more than five acres, do not require submission of an NOI. Therefore, the estimated area of land disturbed should not be less than five, unless the project is part of a larger common plan that disturbs five or more acres. Disturbed means any clearing, grading, excavating, or other similar activities.

If you have any questions about this item, please contact the stormwater technical staff by phone at 512-239-4671 or by email at swgp@tceq.texas.gov.

f) Common Plan of Development

Construction activities that disturb less than five acres do not require submission of an NOI unless they are part of a common plan of development or for sale where the area disturbed is five or more acres. Therefore, the estimated area of land disturbed should not be less than five, unless the project is part of a larger common plan that disturbs five or more acres. Disturbed means any clearing, grading, excavating, or other similar activities.

For more information on what a common plan of development is, refer to the definition of “Common Plan of Development” in the Definitions section of the general permit or enter the following link into your internet browser:

www.tceq.texas.gov/permitting/stormwater/common_plan_of_development_steps.html

For further information, go to the TCEQ stormwater construction webpage enter the following link into your internet browser: www.tceq.texas.gov/goto/construction and search for “Additional Guidance and Quick Links”. If you have any further questions about the Common Plan of Development you can contact the TCEQ Stormwater Team at 512-239-4671 or the TCEQ Small Business and Environmental Assistance at 800-447-2827.

g) Estimated Start Date of the Project

This is the date that any construction activity or construction support activity is initiated at the site. If renewing the permit provide the original start date of when construction activity for this project began.

h) Estimated End Date of the Project

This is the date that any construction activity or construction support activity will end and final stabilization will be achieved at the site.

i) Will concrete truck washout be performed at the site?

Indicate if you expect that operators of concrete trucks will washout concrete trucks at the construction site.

j) Identify the water body(s) receiving stormwater runoff

The stormwater may be discharged directly to a receiving stream or through a MS4 from your site. It eventually reaches a receiving water body such as a local stream or lake, possibly via a drainage ditch. You must provide the name of the water body that receives the discharge from the site (a local stream or lake).

If your site has more than one outfall you need to include the name of the first water body for each outfall, if they are different.

k) Identify the segment number(s) of the classified water body(s)

Identify the classified segment number(s) receiving a discharge directly or indirectly. Enter the following link into your internet browser to find the segment number of the classified water body where stormwater will flow from the site:

www.tceq.texas.gov/waterquality/monitoring/viewer.html or by contacting the TCEQ Water Quality Division at (512) 239-4671 for assistance.

You may also find the segment number in TCEQ publication GI-316 by entering the following link into your internet browser: www.tceq.texas.gov/publications/gi/gi-316 or by contacting the TCEQ Water Quality Division at (512) 239-4671 for assistance.

If the discharge is into an unclassified receiving water and then crosses state lines prior to entering a classified segment, select the appropriate watershed:

- 0100 (Canadian River Basin)
- 0200 (Red River Basin)
- 0300 (Sulfur River Basin)
- 0400 (Cypress Creek Basin)
- 0500 (Sabine River Basin)

Call the Water Quality Assessments section at 512-239-4671 for further assistance.

l) Discharge into MS4 – Identify the MS4 Operator

The discharge may initially be into a municipal separate storm sewer system (MS4). If the stormwater discharge is into an MS4, provide the name of the entity that operates the MS4 where the stormwater discharges. An MS4 operator is often a city, town, county, or utility district, but possibly can be another form of government. Please note that the Construction General Permit requires the Operator to supply the MS4 with a

copy of the NOI submitted to TCEQ. For assistance, you may call the technical staff at 512-239-4671.

m) Discharges to the Edwards Aquifer Recharge Zone and Certification

The general permit requires the approved Contributing Zone Plan or Water Pollution Abatement Plan to be included or referenced as a part of the Stormwater Pollution Prevention Plan.

See maps on the TCEQ website to determine if the site is located within the Recharge Zone, Contributing Zone, or Contributing Zone within the Transition Zone of the Edwards Aquifer by entering the following link into an internet browser: www.tceq.texas.gov/field/eapp/viewer.html or by contacting the TCEQ Water Quality Division at 512-239-4671 for assistance.

If the discharge or potential discharge is within the Recharge Zone, Contributing Zone, or Contributing Zone within the Transition Zone of the Edwards Aquifer, a site-specific authorization approved by the Executive Director under the Edwards Aquifer Protection Program (30 TAC Chapter 213) is required before construction can begin.

For questions regarding the Edwards Aquifer Protection Program, contact the appropriate TCEQ Regional Office. For projects in Hays, Travis and Williamson Counties: Austin Regional Office, 12100 Park 35 Circle, Austin, TX 78753, 512-339-2929. For Projects in Bexar, Comal, Kinney, Medina and Uvalde Counties: TCEQ San Antonio Regional Office, 14250 Judson Rd., San Antonio, TX 78233-4480, 210-490-3096.

Section 5. NOI CERTIFICATION

Note: Failure to indicate Yes to all of the certification items may result in denial of coverage under the general permit.

a) Certification of Understanding the Terms and Conditions of Construction General Permit (TXR150000)

Provisional coverage under the Construction General Permit (TXR150000) begins 7 days after the completed paper NOI is postmarked for delivery to the TCEQ. Electronic applications submitted through ePermits have immediate provisional coverage. You must obtain a copy and read the Construction General Permit before submitting your application. You may view and print the Construction General Permit for which you are seeking coverage at the TCEQ web site by entering the following link into an internet browser: www.tceq.texas.gov/goto/construction or you may contact the TCEQ Stormwater processing Center at 512-239-3700 for assistance.

b) Certification of Legal Name

The full legal name of the applicant as authorized to do business in Texas is required. The name must be provided exactly as filed with the Texas Secretary of State (SOS), or on other legal documents forming the entity, that is filed in the county where doing business. You may contact the SOS at 512-463 5555, for more information related to filing in Texas.

c) Understanding of Notice of Termination

A permittee shall terminate coverage under the Construction General Permit through the submittal of a NOT when the operator of the facility changes, final stabilization has

been reached, the discharge becomes authorized under an individual permit, or the construction activity never began at this site.

d) Certification of Stormwater Pollution Prevention Plan

The SWP3 identifies the areas and activities that could produce contaminated runoff at your site and then tells how you will ensure that this contamination is mitigated. For example, in describing your mitigation measures, your site's plan might identify the devices that collect and filter stormwater, tell how those devices are to be maintained, and tell how frequently that maintenance is to be carried out. You must develop this plan in accordance with the TCEQ general permit requirements. This plan must be developed and implemented before you complete this NOI. The SWP3 must be available for a TCEQ investigator to review on request.

Section 6. APPLICANT CERTIFICATION SIGNATURE

The certification must bear an original signature of a person meeting the signatory requirements specified under 30 Texas Administrative Code (TAC) §305.44.

If you are a corporation:

The regulation that controls who may sign an NOI or similar form is 30 Texas Administrative Code §305.44(a)(1) (see below). According to this code provision, any corporate representative may sign an NOI or similar form so long as the authority to sign such a document has been delegated to that person in accordance with corporate procedures. By signing the NOI or similar form, you are certifying that such authority has been delegated to you. The TCEQ may request documentation evidencing such authority.

If you are a municipality or other government entity:

The regulation that controls who may sign an NOI or similar form is 30 Texas Administrative Code §305.44(a)(3) (see below). According to this code provision, only a ranking elected official or principal executive officer may sign an NOI or similar form. Persons such as the City Mayor or County Commissioner will be considered ranking elected officials. In order to identify the principal executive officer of your government entity, it may be beneficial to consult your city charter, county or city ordinances, or the Texas statute(s) under which your government entity was formed. An NOI or similar document that is signed by a government official who is not a ranking elected official or principal executive officer does not conform to §305.44(a)(3). The signatory requirement may not be delegated to a government representative other than those identified in the regulation. By signing the NOI or similar form, you are certifying that you are either a ranking elected official or principal executive officer as required by the administrative code. Documentation demonstrating your position as a ranking elected official or principal executive officer may be requested by the TCEQ.

If you have any questions or need additional information concerning the signatory requirements discussed above, please contact the TCEQ's Environmental Law Division at 512-239-0600.

30 Texas Administrative Code

§305.44. Signatories to Applications

(a) All applications shall be signed as follows.

(1) For a corporation, the application shall be signed by a responsible corporate officer. For purposes of this paragraph, a responsible corporate officer means a president, secretary, treasurer, or vice-president of the corporation in charge of a principal business function, or any other person who performs similar policy or decision-making functions for the

corporation; or the manager of one or more manufacturing, production, or operating facilities employing more than 250 persons or having gross annual sales or expenditures exceeding \$25 million (in second-quarter 1980 dollars), if authority to sign documents has been assigned or delegated to the manager in accordance with corporate procedures. Corporate procedures governing authority to sign permit or post-closure order applications may provide for assignment or delegation to applicable corporate positions rather than to specific individuals.

(2) For a partnership or sole proprietorship, the application shall be signed by a general partner or the proprietor, respectively.

(3) For a municipality, state, federal, or other public agency, the application shall be signed by either a principal executive officer or a ranking elected official. For purposes of this paragraph, a principal executive officer of a federal agency includes the chief executive officer of the agency, or a senior executive officer having responsibility for the overall operations of a principal geographic unit of the agency (e.g., regional administrator of the EPA).

Texas Commission on Environmental Quality General Permit Payment Submittal Form

Use this form to submit your Application Fee only if you are mailing your payment.

Instructions:

- Complete items 1 through 5 below:
- Staple your check in the space provided at the bottom of this document.
- *Do not mail this form with your NOI form.*
- *Do not mail this form to the same address as your NOI.*

Mail this form and your check to either of the following:

By Regular U.S. Mail

Texas Commission on Environmental Quality
Financial Administration Division
Cashier's Office, MC-214
P.O. Box 13088
Austin, TX 78711-3088

By Overnight or Express Mail

Texas Commission on Environmental Quality
Financial Administration Division
Cashier's Office, MC-214
12100 Park 35 Circle
Austin, TX 78753

Fee Code: GPA General Permit: TXR150000

1. Check or Money Order No:
2. Amount of Check/Money Order:
3. Date of Check or Money Order:
4. Name on Check or Money Order:
5. NOI Information:

If the check is for more than one NOI, list each Project or Site (RE) Name and Physical Address exactly as provided on the NOI. **Do not submit a copy of the NOI with this form, as it could cause duplicate permit application entries!**

If there is not enough space on the form to list all of the projects or sites the authorization will cover, then attach a list of the additional sites.

Project/Site (RE) Name:

Project/Site (RE) Physical Address:

Staple the check or money order to this form in this space.

Agent Authorization Form
(TCEQ-0599)

Agent Authorization Form
For Required Signature
Edwards Aquifer Protection Program
Relating to 30 TAC Chapter 213
Effective June 1, 1999

I _____ Bill Parodi _____,
Print Name
_____ Owner _____,
Title - Owner/President/Other
of _____ PicklePlex Holdings LLC _____,
Corporation/Partnership/Entity Name
have authorized _____ Steven Minor, P.E. _____
Print Name of Agent/Engineer
of _____ Gray Engineering, Inc. _____
Print Name of Firm

to represent and act on the behalf of the above named Corporation, Partnership, or Entity for the purpose of preparing and submitting this plan application to the Texas Commission on Environmental Quality (TCEQ) for the review and approval consideration of regulated activities.

I also understand that:

1. The applicant is responsible for compliance with 30 Texas Administrative Code Chapter 213 and any condition of the TCEQ's approval letter. The TCEQ is authorized to assess administrative penalties of up to \$10,000 per day per violation.
2. For those submitting an application who are not the property owner, but who have the right to control and possess the property, additional authorization is required from the owner.
3. Application fees are due and payable at the time the application is submitted. The application fee must be sent to the TCEQ cashier or to the appropriate regional office. The application will not be considered until the correct fee is received by the commission.
4. A notarized copy of the Agent Authorization Form must be provided for the person preparing the application, and this form must accompany the completed application.
5. No person shall commence any regulated activity on the Edwards Aquifer Recharge Zone, Contributing Zone or Transition Zone until the appropriate application for the activity has been filed with and approved by the Executive Director.

SIGNATURE PAGE:

William Parodi Jr.
Applicant's Signature


8-19-24
Date

THE STATE OF Texas §

County of Travis §

BEFORE ME, the undersigned authority, on this day personally appeared William Parodi Jr. known to me to be the person whose name is subscribed to the foregoing instrument, and acknowledged to me that (s)he executed same for the purpose and consideration therein expressed.

GIVEN under my hand and seal of office on this 19 day of 08, 2024



Charu Yadav
NOTARY PUBLIC
CHARU YADAV
Typed or Printed Name of Notary

MY COMMISSION EXPIRES: Feb/28/2028

Application Fee Form
(TCEQ-0574)

Application Fee Form

Texas Commission on Environmental Quality

Name of Proposed Regulated Entity: ATX PICKLEPLEX

Regulated Entity Location: 501 Cypress Creek Road, Cedar Park, TX 78613

Name of Customer: PicklePlex Holdings LLC

Contact Person: Steven Minor, P.E.

Phone: 512-452-0371

Customer Reference Number (if issued): CN N/A

Regulated Entity Reference Number (if issued): RN N/A

Austin Regional Office (3373)

Hays

Travis

Williamson

San Antonio Regional Office (3362)

Bexar

Medina

Uvalde

Comal

Kinney

Application fees must be paid by check, certified check, or money order, payable to the **Texas Commission on Environmental Quality**. Your canceled check will serve as your receipt. **This form must be submitted with your fee payment.** This payment is being submitted to:

Austin Regional Office

San Antonio Regional Office

Mailed to: TCEQ - Cashier

Overnight Delivery to: TCEQ - Cashier

Revenues Section

12100 Park 35 Circle

Mail Code 214

Building A, 3rd Floor

P.O. Box 13088

Austin, TX 78753

Austin, TX 78711-3088

(512)239-0357

Site Location (Check All That Apply):

Recharge Zone

Contributing Zone

Transition Zone

<i>Type of Plan</i>	<i>Size</i>	<i>Fee Due</i>
Water Pollution Abatement Plan, Contributing Zone Plan: One Single Family Residential Dwelling	Acres	\$
Water Pollution Abatement Plan, Contributing Zone Plan: Multiple Single Family Residential and Parks	Acres	\$
Water Pollution Abatement Plan, Contributing Zone Plan: Non-residential	3.47 Acres	\$ 4,000
Sewage Collection System	L.F.	\$
Lift Stations without sewer lines	Acres	\$
Underground or Aboveground Storage Tank Facility	Tanks	\$
Piping System(s)(only)	Each	\$
Exception	Each	\$
Extension of Time	Each	\$

Signature: 

Date: 8/19/2024

Application Fee Schedule

Texas Commission on Environmental Quality

Edwards Aquifer Protection Program 30 TAC Chapter 213 (effective 05/01/2008)

Water Pollution Abatement Plans and Modifications

Contributing Zone Plans and Modifications

<i>Project</i>	<i>Project Area in Acres</i>	<i>Fee</i>
One Single Family Residential Dwelling	< 5	\$650
Multiple Single Family Residential and Parks	< 5	\$1,500
	5 < 10	\$3,000
	10 < 40	\$4,000
	40 < 100	\$6,500
	100 < 500	\$8,000
	≥ 500	\$10,000
Non-residential (Commercial, industrial, institutional, multi-family residential, schools, and other sites where regulated activities will occur)	< 1	\$3,000
	1 < 5	\$4,000
	5 < 10	\$5,000
	10 < 40	\$6,500
	40 < 100	\$8,000
	≥ 100	\$10,000

Organized Sewage Collection Systems and Modifications

<i>Project</i>	<i>Cost per Linear Foot</i>	<i>Minimum Fee- Maximum Fee</i>
Sewage Collection Systems	\$0.50	\$650 - \$6,500

Underground and Aboveground Storage Tank System Facility Plans and Modifications

<i>Project</i>	<i>Cost per Tank or Piping System</i>	<i>Minimum Fee- Maximum Fee</i>
Underground and Aboveground Storage Tank Facility	\$650	\$650 - \$6,500

Exception Requests

<i>Project</i>	<i>Fee</i>
Exception Request	\$500

Extension of Time Requests

<i>Project</i>	<i>Fee</i>
Extension of Time Request	\$150

Core Data Form
(TCEQ-10400)



TCEQ Core Data Form

For detailed instructions on completing this form, please read the Core Data Form Instructions or call 512-239-5175.

SECTION I: General Information

1. Reason for Submission (If other is checked please describe in space provided.)		
<input checked="" type="checkbox"/> New Permit, Registration or Authorization (Core Data Form should be submitted with the program application.)		
<input type="checkbox"/> Renewal (Core Data Form should be submitted with the renewal form)	<input type="checkbox"/> Other	
2. Customer Reference Number (if issued)	Follow this link to search for CN or RN numbers in Central Registry**	3. Regulated Entity Reference Number (if issued)
CN		RN

SECTION II: Customer Information

4. General Customer Information		5. Effective Date for Customer Information Updates (mm/dd/yyyy)	
<input checked="" type="checkbox"/> New Customer <input type="checkbox"/> Update to Customer Information <input type="checkbox"/> Change in Regulated Entity Ownership <input type="checkbox"/> Change in Legal Name (Verifiable with the Texas Secretary of State or Texas Comptroller of Public Accounts)			
<i>The Customer Name submitted here may be updated automatically based on what is current and active with the Texas Secretary of State (SOS) or Texas Comptroller of Public Accounts (CPA).</i>			
6. Customer Legal Name (If an individual, print last name first: eg: Doe, John)		<i>If new Customer, enter previous Customer below:</i>	
PicklePlex Holdings LLC			
7. TX SOS/CPA Filing Number	8. TX State Tax ID (11 digits)	9. Federal Tax ID (9 digits)	10. DUNS Number (if applicable)
0805189776	32091137870	93-2983000	
11. Type of Customer:	<input checked="" type="checkbox"/> Corporation	<input type="checkbox"/> Individual	Partnership: <input type="checkbox"/> General <input type="checkbox"/> Limited
Government: <input type="checkbox"/> City <input type="checkbox"/> County <input type="checkbox"/> Federal <input type="checkbox"/> Local <input type="checkbox"/> State <input type="checkbox"/> Other	<input type="checkbox"/> Sole Proprietorship	<input type="checkbox"/> Other:	
12. Number of Employees		13. Independently Owned and Operated?	
<input type="checkbox"/> 0-20 <input checked="" type="checkbox"/> 21-100 <input type="checkbox"/> 101-250 <input type="checkbox"/> 251-500 <input type="checkbox"/> 501 and higher		<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	
14. Customer Role (Proposed or Actual) – as it relates to the Regulated Entity listed on this form. Please check one of the following			
<input checked="" type="checkbox"/> Owner <input type="checkbox"/> Operator <input type="checkbox"/> Owner & Operator <input type="checkbox"/> Other: <input type="checkbox"/> Occupational Licensee <input type="checkbox"/> Responsible Party <input type="checkbox"/> VCP/BSA Applicant			
15. Mailing Address:	3725 Copper Ridge Ct.		
	City	Austin	State TX
	ZIP	78734	ZIP + 4
16. Country Mailing Information (if outside USA)		17. E-Mail Address (if applicable)	
		billparodi2@gmail.com	

18. Telephone Number	19. Extension or Code	20. Fax Number (if applicable)
(512) 348-0011		() -

SECTION III: Regulated Entity Information

21. General Regulated Entity Information (If 'New Regulated Entity' is selected, a new permit application is also required.)							
<input checked="" type="checkbox"/> New Regulated Entity <input type="checkbox"/> Update to Regulated Entity Name <input type="checkbox"/> Update to Regulated Entity Information							
<i>The Regulated Entity Name submitted may be updated, in order to meet TCEQ Core Data Standards (removal of organizational endings such as Inc, LP, or LLC).</i>							
22. Regulated Entity Name (Enter name of the site where the regulated action is taking place.)							
ATX Pickleplex							
23. Street Address of the Regulated Entity: (No PO Boxes)	501 Cypress Creek Road						
	City	Cedar Park	State	TX	ZIP	78613	ZIP + 4
24. County	Williamson						

If no Street Address is provided, fields 25-28 are required.

25. Description to Physical Location:							
26. Nearest City					State	Nearest ZIP Code	
<i>Latitude/Longitude are required and may be added/updated to meet TCEQ Core Data Standards. (Geocoding of the Physical Address may be used to supply coordinates where none have been provided or to gain accuracy).</i>							
27. Latitude (N) In Decimal:	30.497017			28. Longitude (W) In Decimal:	-97.822086		
Degrees	Minutes	Seconds	Degrees	Minutes	Seconds		
29. Primary SIC Code (4 digits)	30. Secondary SIC Code (4 digits)	31. Primary NAICS Code (5 or 6 digits)	32. Secondary NAICS Code (5 or 6 digits)				
1542	7999	713990					
33. What is the Primary Business of this entity? (Do not repeat the SIC or NAICS description.)							
Indoor pickleball facility							
34. Mailing Address:	3725 Copper Ridge Ct.						
	City	Austin	State	TX	ZIP	78734	ZIP + 4
35. E-Mail Address:	billparodi2@gmail.com						
36. Telephone Number	37. Extension or Code	38. Fax Number (if applicable)					
(512) 348-0011		() -					

39. TCEQ Programs and ID Numbers Check all Programs and write in the permits/registration numbers that will be affected by the updates submitted on this form. See the Core Data Form instructions for additional guidance.

<input type="checkbox"/> Dam Safety	<input type="checkbox"/> Districts	<input type="checkbox"/> Edwards Aquifer	<input type="checkbox"/> Emissions Inventory Air	<input type="checkbox"/> Industrial Hazardous Waste
<input type="checkbox"/> Municipal Solid Waste	<input type="checkbox"/> New Source Review Air	<input type="checkbox"/> OSSF	<input type="checkbox"/> Petroleum Storage Tank	<input type="checkbox"/> PWS
<input type="checkbox"/> Sludge	<input type="checkbox"/> Storm Water	<input type="checkbox"/> Title V Air	<input type="checkbox"/> Tires	<input type="checkbox"/> Used Oil
<input type="checkbox"/> Voluntary Cleanup	<input type="checkbox"/> Wastewater	<input type="checkbox"/> Wastewater Agriculture	<input type="checkbox"/> Water Rights	<input type="checkbox"/> Other:

SECTION IV: Preparer Information

40. Name:	Lucas Lahaug	41. Title:	E.I.T.
42. Telephone Number	43. Ext./Code	44. Fax Number	45. E-Mail Address
(512) 452-0371		() -	llahaug@grayengineeringinc.com

SECTION V: Authorized Signature

46. By my signature below, I certify, to the best of my knowledge, that the information provided in this form is true and complete, and that I have signature authority to submit this form on behalf of the entity specified in Section II, Field 6 and/or as required for the updates to the ID numbers identified in field 39.

Company:	Gray Engineering, Inc.	Job Title:	Principal
Name (In Print):	Steven Minor, P.E	Phone:	(512) 452- 0371
Signature:		Date:	8/19/2024

SUBMITTED BY:

Sameer Saini

07/31/2024

SAMEER SAINI, P.E.
GRAY ENGINEERING, INC.
8834 N. CAPITAL OF TEXAS HWY.
SUITE 140
AUSTIN, TEXAS 78759
(512) 452-0371
TBPELS FIRM #2946

NOTICE:
ALTERATION OF A SEALED DRAWING WITHOUT PROPER NOTIFICATION TO THE RESPONSIBLE ENGINEER IS A VIOLATION OF THE TEXAS ENGINEERING PRACTICE ACT.

ACCEPTED FOR CONSTRUCTION:

PLANNING
CITY OF CEDAR PARK, TEXAS

ENGINEERING SERVICES
CITY OF CEDAR PARK, TEXAS

INDUSTRIAL PRETREATMENT
CITY OF CEDAR PARK, TEXAS

FIRE PREVENTION
CITY OF CEDAR PARK, TEXAS

LANDSCAPE PLANNER
CITY OF CEDAR PARK, TEXAS

ADDRESSING
CITY OF CEDAR PARK, TEXAS

SITE INFORMATION
THE FOLLOWING INFORMATION SHOULD BE COMPLETED AND PLACED ON THE COVER SHEET:
OWNER: PICKLEPLEX PROPERTIES LLC, ADDRESS: 3725 COPPER RIDGE CT, AUSTIN, TX 78734
PHONE: N/A CELL: (512) 348-0011 ACREAGE: 3.47 TOTAL IMPERVIOUS COVER: 2.48
LEGAL DESCRIPTION: BEING ALL OF 3.47 ACRES SHORT FORM FINAL PLAT OF BUTTERCUP CREEK INDUSTRIAL PARK, RESUBDIVISION OF LOT 5 AS RECORDED IN CAB. T, SLIDE 87 OF THE PLAT RECORDS OF WILLIAMSON COUNTY, TEXAS.
ADDRESS: 501 CYPRESS CREEK RD, CEDAR PARK, TX 78613
LAND USE SUMMARY: (SQUARE FOOTAGE OF BUILDINGS) FOR EACH LAND USE AND NUMBER OF UNITS IF MULTIFAMILY:
(1) INDOOR RECREATIONAL BUILDING, 3 LEVELS, 48,500 GSF
ZONING: LOCAL BUSINESS (LB) DATE: FEBRUARY 22, 2024
PERSON PREPARING PLAN: SAMEER SAINI, P.E. COMPANY: GRAY ENGINEERING INC. TBPELS FIRM #2946
ADDRESS: 8834 N. CAPITAL OF TEXAS HWY., SUITE 140 AUSTIN, TEXAS 78759
PHONE: (512) 452-0371 CELL: (571) 420-2285
ENGINEER: SAMEER SAINI, P.E. COMPANY: GRAY ENGINEERING INC. TBPELS FIRM #2946
ADDRESS: 8834 N. CAPITAL OF TEXAS HWY., SUITE 140 AUSTIN, TEXAS 78759
PHONE: (512) 452-0371 CELL: (571) 420-2285

SITE DEVELOPMENT PERMIT NUMBER: 2024-10-SD
CZP APPROVAL ID NUMBER: SUBMITTED, PENDING APPROVAL
TABS REGISTRATION NUMBER: 2024013754

PROJECT DESCRIPTION:
THIS DEVELOPMENT PROPOSES IMPROVEMENTS TO BUILD AN INDOOR PICKLEBALL COURT BUILDING TOTALING 48,500 GSF WITH A RESTAURANT/BAR AREA AND ASSOCIATED PARKING, DRIVE AISLES, ON-SITE UTILITIES, AND A STORMWATER MANAGEMENT DETENTION POND.


BENCHMARKS:
CEDAR PARK GPS MONUMENT 9 TBM "A" TBM "B" TBM "C"
NORTHING (Y): 10152522.83 NORTHING (Y): 10153240.30 NORTHING (Y): 10153368.92 NORTHING (Y): 10153194.16
EASTING (X): 30875222.77 EASTING (X): 3087706.70 EASTING (X): 3087442.46 EASTING (X): 3087442.46
MEASURED ELEVATION: 928.36 ELEVATION: 920.87 ELEVATION: 917.69 ELEVATION: 922.31
PUBLISHED ELEVATION: 928.55
DELTA: 0.19'
BEARING AND DISTANCE BETWEEN "CEDAR PARK GPS MONUMENT 9" AND "TBM C" = N68° 08' 38"E , 1803.33'

LEGAL DESCRIPTION:
BEING ALL OF 3.47 ACRES SHORT FORM FINAL PLAT OF BUTTERCUP CREEK INDUSTRIAL PARK, RESUBDIVISION OF LOT 5 AS RECORDED IN CAB. T, SLIDE 87 OF THE PLAT RECORDS OF WILLIAMSON COUNTY, TEXAS.

UTILITY PROVIDERS:
WATER: CITY OF CEDAR PARK
WASTEWATER: CITY OF CEDAR PARK
ELECTRICITY: PEDERNALES ELECTRIC COOPERATIVE, INC.
GAS: ATMOS ENERGY

- NOTES:
- ALL RESPONSIBILITY FOR THE ACCURACY OF THESE PLANS REMAINS WITH THE ENGINEER WHO PREPARED THEM. IN REVIEWING THESE PLANS, THE CITY OF CEDAR PARK MUST RELY ON THE ADEQUACY OF THE WORK OF THE DESIGN ENGINEER.
 - NO PORTION OF THIS PROJECT IS LOCATED IN THE 1% ANNUAL CHANCE FLOODPLAIN AS SHOWN ON FEMA FIRM NO. 48491C0605F, DATED DECEMBER 20, 2019.
 - THIS SITE IS LOCATED IN THE EDWARDS AQUIFER CONTRIBUTING ZONE AS DEFINED BY TCEQ.
 - THIS SUBDIVISION IS NOT SUBJECT TO THE LAKE TRAVIS NON-POINT SOURCE POLLUTION CONTROL ORDINANCE OF THE CEDAR PARK CITY CODE.
 - RELEASE OF THIS APPLICATION DOES NOT CONSTITUTE A VERIFICATION OF ALL DATA, INFORMATION AND CALCULATIONS SUPPLIED BY THE APPLICANT. THE ENGINEER OF RECORD IS SOLELY RESPONSIBLE FOR THE COMPLETENESS, ACCURACY AND ADEQUACY OF HIS/HER SUBMITTAL, WHETHER OR NOT THE APPLICATION IS REVIEWED FOR CODE COMPLIANCE BY CITY ENGINEERS.
 - THESE CONSTRUCTION PLANS WERE PREPARED, SEALED, SIGNED, AND DATED BY A TEXAS LICENSED PROFESSIONAL ENGINEER. THEREFORE, BASED ON THE ENGINEER'S CONCURRENCE OF COMPLIANCE, THE CONSTRUCTION PLANS FOR THE CONSTRUCTION OF THE PROPOSED PROJECT ARE HEREBY APPROVED SUBJECT TO THE STANDARD CONSTRUCTION SPECIFICATIONS AND DETAILS MANUAL AND ALL OTHER APPLICABLE CITY, STATE, AND FEDERAL REGULATIONS AND CODES.
 - ASSIGNED CITY ADDRESS NUMBERS SHALL BE PERMANENTLY AFFIXED TO ALL STRUCTURES IN SUCH POSITIONS AS TO BE PLAINLY VISIBLE AND LEGIBLE FROM THE STREET. THE FOLLOWING ADDRESS HAS BEEN ASSIGNED TO THE BUTTERCUP CREEK INDUSTRIAL PARK, RESUBDIVISION OF LOT 5, 501 CYPRESS CREEK RD, CEDAR PARK, TX 78613
 - THIS PROJECT IS ZONED AS LOCAL BUSINESS-LB
 - A SITE DEVELOPMENT PERMIT SHALL EXPIRE TWO (2) YEARS FROM THE DATE SUCH PERMIT WAS APPROVED IF NO PROGRESS HAS BEEN MADE TOWARDS COMPLETION OF THE PROJECT, PURSUANT TO SECTION 245.005 OF THE TEXAS LOCAL GOVERNMENT CODE, AS AMENDED, (SEC. 14.03.009 (A)).
 - ANY PROJECT, AS DEFINED UNDER CHAPTER 245 OF THE TEXAS LOCAL GOVERNMENT CODE, AS AMENDED, SHALL EXPIRE ON THE FIFTH ANNIVERSARY OF THE DATE THE FIRST PERMIT APPLICATION WAS FILED FOR THE PROJECT, PURSUANT TO SECTION 245.005 OF THE TEXAS LOCAL GOVERNMENT CODE, AS AMENDED, (SEC. 14.03.009 (B)).

CONSTRUCTION PLANS FOR ATX PICKLEPLEX SITE PLAN 501 CYPRESS CREEK RD, CEDAR PARK, TX 78613 DEC. 2023




LOCATION MAP
1"= 600'

ENGINEER:
GRAY ENGINEERING INC.
SAMEER SAINI, P.E.
8834 N. CAPITAL OF TEXAS HWY.,
SUITE 140
AUSTIN, TEXAS 78759
(512) 452-0371
FAX (512) 454-9933
EMAIL: SSAINI@GRAYENGINEERINGINC.COM
TBPELS FIRM #2946

ARCHITECT:
STUDIO ELES
STEPHANIE GUARIGLIA, AIA
4926 SPICEWOOD SPRINGS ROAD
SUITE 101
AUSTIN, TX 78759
(512) 750-8988
EMAIL: SGUARIGLIA@STUDIOELES.COM

LANDSCAPE ARCHITECT:
VERDI
LAUREN RENZ
11707 LOCHRIDGE DR.
SUITE 101
AUSTIN, TX 78758
(512) 413-9366
EMAIL: LRENZ@VERDIAUSTIN.COM



8834 N. Capital of Texas Hwy.
Austin, Texas 78759
Suite 140
(512)452-0371
FAX(512)454-9933
TBPELS FIRM #2946

SHEET LIST TABLE

Sheet Number	Sheet Title
1	COVER SHEET
2	GENERAL NOTES
3	FINAL PLAT (1 OF 2)
4	FINAL PLAT (2 OF 2)
5	EXISTING CONDITIONS & DEMOLITION PLAN
6	SITE PLAN
7	PROPOSED GRADING PLAN
8	EXISTING DRAINAGE AREA
9	PROPOSED DRAINAGE PLAN
10	OVERALL WATER DISTRIBUTION PLAN
11	OVERALL WASTEWATER PLAN
12	OVERALL STORM SEWER PLAN
13	PROPOSED POND PLAN (1 OF 2)
14	PROPOSED POND PLAN (2 OF 2)
15	POND ROUTINGS AND CALCULATIONS
16	VEGETATED FILTER STRIPS PLAN
17	EROSION AND SEDIMENTATION CONTROL PLAN
18	PAVEMENT TYPE THICKNESS PLAN
19	GRADING PLAN
20	STREET CROSS SECTIONS
21	ROADWAY IMPROVEMENTS
22	STORM SEWER LINE A PLAN AND PROFILE
23	TRAFFIC CONTROL DETAIL
24	FIRE ACCESS PLAN
25	SITE DETAILS (1 OF 3)
26	SITE DETAILS (2 OF 3)
27	SITE DETAILS (3 OF 3)
28	EROSION AND SEDIMENTATION CONTROL DETAILS
29	WATER DETAILS
30	WASTEWATER DETAILS
31	LANDSCAPE PLAN
32	LANDSCAPE PLAN NOTES
33	TREE PRESERVATION PLAN
34	ARCHITECTURAL ELEVATION PLAN (1 OF 2)
35	ARCHITECTURAL ELEVATION PLAN (2 OF 2)
36	POND RETAINING WALLS NOTES AND DETAIL
37	PHOTOMETRIC SITE PLAN
38	PHOTOMETRIC DETAILS

REVISION NO.	DESCRIPTION	DATE MADE	SHEET NO.	MADE BY	NET CHANGE IMP. COVER (SQ FT.)



NO.	DATE	REVISION DESCRIPTION

ATX PICKLEPLEX
SITE PLAN

COVER SHEET

PROJECT NO: 1711-11671
DESIGNED BY: LL
DRAWN BY: JM
CHECKED BY: SS

NOTICE:
ALTERATION OF A SEALED DRAWING WITHOUT PROPER NOTIFICATION TO THE RESPONSIBLE ENGINEER IS A VIOLATION OF THE TEXAS ENGINEERING PRACTICE ACT.



H:\PROJECTS\1711 - STUDIO ELES\11671 ATX PICKLEPLEX SITE PLAN\CAD\SHEETS\11671-COVER SHEET.DWG DATE: 7/30/2024 8:02:37 PM BY: LLAHAUJ

CONSTRUCTION NOTES FOR SUBDIVISIONS AND SITE PLANS

CONSTRUCTION NOTES FOR SUBDIVISIONS & SITE PLANS CITY OF CEDAR PARK REVISED APRIL 2, 2024

GENERAL NOTES:

- 1. GENERAL CONTRACTOR SHALL CALL FOR ALL UTILITY LOCATES PRIOR TO ANY CONSTRUCTION. CONTRACTOR SHALL DELINEATE AREAS OF EXCAVATION USING WHITE PAINT (WHITE LINING) IN ACCORDANCE WITH 16 TAC 18.13. WATER & WASTEWATER OWNED BY THE CITY OF CEDAR PARK CAN BE LOCATED BY CALLING TEXAS 811 AT 1-800-832-8343. ONLY UTILITY LOCATES FOR UTILITY LOCATES BY THE CITY OF CEDAR PARK ARE TO BE USED.
2. ALL CONSTRUCTION SHALL BE IN ACCORDANCE WITH THE LATEST CITY OF AUSTIN STANDARD SPECIFICATIONS. CITY OF AUSTIN STANDARDS SHALL BE USED UNLESS OTHERWISE NOTED.
3. DESIGN PROCEDURES SHALL BE IN GENERAL COMPLIANCE WITH THE CITY OF AUSTIN DRAINAGE CRITERIA MANUAL. ALL VARIANCES TO THE MANUAL ARE LISTED BELOW.
4. BENCHMARKS SHOULD BE TIED TO THE CITY OF CEDAR PARK BENCHMARKS AND BE CORRECTLY 'GEOREFERENCED' TO STATE PLANE COORDINATES. A LIST OF THE CITY'S BENCHMARKS CAN BE FOUND AT: HTTP://WWW.CEDARPARKTexas.GOV/INDEX.ASP?XPAGE=793.
5. PRIOR TO ISSUANCE OF A CERTIFICATE OF OCCUPANCY FOR A SITE DEVELOPMENT PERMIT, THE RIGHT OF WAY BETWEEN THE PROPERTY LINE AND EDGE OF PAVEMENT / BACK OF CURB SHALL BE REVEGETATED ACCORDING TO COA SPECIFICATION 602S AND 606S. PRIOR TO CITY ACCEPTANCE OF SUBDIVISION IMPROVEMENTS ALL GRADED AND DISTURBED AREAS SHALL BE RE-VEGETATED IN ACCORDANCE WITH THE CITY OF AUSTIN SPECIFICATION ITEM #604 NATIVE SEEDING UNLESS NON-NATIVE IS SPECIFICALLY APPROVED.
6. THE CONTRACTOR SHALL PROVIDE THE CITY OF CEDAR PARK COPIES OF ALL TEST RESULTS PRIOR TO ACCEPTANCE OF SUBDIVISION IMPROVEMENTS.
7. CITY, OWNER, ENGINEER, CONTRACTOR, REPRESENTATIVES OF ALL UTILITY COMPANIES, AND A REPRESENTATIVE FROM THE TESTING LAB SHALL ATTEND PRE-CONSTRUCTION CONFERENCE PRIOR TO START OF CONSTRUCTION. THE CONTRACTOR SHALL SCHEDULE THE MEETING WITH THE CITY OF CEDAR PARK ENGINEERING DEPARTMENT A MINIMUM OF 48 HOURS PRIOR TO THE MEETING (512-401-5000). FINAL CONSTRUCTION PLANS SHALL BE DELIVERED TO ENGINEERING A MINIMUM OF SEVEN BUSINESS DAYS PRIOR TO REQUESTING A PRE-CONSTRUCTION MEETING.
8. EXCESS SOIL SHALL BE REMOVED AT THE CONTRACTOR'S EXPENSE. NOTIFY THE CITY OF CEDAR PARK IF THE DISPOSAL SITE IS INSIDE THE CITY'S JURISDICTIONAL BOUNDARIES.
9. BURNING IS PROHIBITED.
10. ANY CHANGES OR REVISIONS TO THESE PLANS MUST FIRST BE SUBMITTED TO THE CITY BY THE DESIGN ENGINEER FOR REVIEW AND WRITTEN APPROVAL PRIOR TO CONSTRUCTION OF THE REVISION. ALL CHANGES AND REVISIONS MADE TO THE DESIGN OR UTILITIES OR IMPACTS UTILITIES SHALL USE REVISION CLOUDS TO HIGHLIGHT ALL REVISIONS OR CHANGES WITH EACH SUBMITTAL. REVISION TRIANGLES SHALL BE USED TO MARK REVISIONS. ALL CLOUDS AND TRIANGLE MARKERS FROM PREVIOUS REVISIONS MAY BE REMOVED. REVISION INFORMATION SHALL BE UPDATED IN THE APPROPRIATE AREAS OF THE TITLE BLOCK.
11. MINIMUM SETBACK REQUIREMENTS FOR EXISTING AND NEWLY PLANTED TREES FROM THE EDGE OF PAVEMENT TO CONFORM TO THE REQUIREMENTS AS SHOWN IN TABLE 6-1 OF THE CITY OF AUSTIN'S TRANSPORTATION CRITERIA MANUAL.
12. THE CONTRACTOR WILL REIMBURSE THE CITY FOR ALL COST INCURRED AS A RESULT OF ANY DAMAGE TO ANY CITY UTILITY OR ANY INFRASTRUCTURE WITHIN THE RIGHT-OF-WAY BY THE CONTRACTOR, REGARDLESS OF THESE PLANS. AN ENGINEER'S SIGNATURE AND SEAL IS REQUIRED FOR ALL RECORD DRAWINGS. ALL RECORD DRAWINGS SHALL BE SUBMITTED TO THE ENGINEERING DEPARTMENT PRIOR TO THE ISSUANCE OF CERTIFICATE OF OCCUPANCY OR SUBDIVISION ACCEPTANCE. THE ENGINEER AND CONTRACTOR SHALL VERIFY THAT ALL FINAL REVISIONS AND CHANGES HAVE BEEN MADE TO RECORD DRAWINGS PRIOR TO CITY SUBMITTAL. RECORD CONSTRUCTION DRAWINGS, INCLUDING ROADWAY AND ALL UTILITIES, SHALL BE PROVIDED TO THE CITY IN AUTOCAD *.DWG FILES AND *.PDF FORMAT IN A CD OR DVD. LINE WEIGHTS, LINE TYPES AND TEXT SIZE SHALL BE SUCH THAT IF HALF-SIZE PRINTS (11" X 17") WERE PRODUCED, THE PLANS WOULD STILL BE LEGIBLE. ALL REQUIRED DIGITAL FILES SHALL CONTAIN A MINIMUM OF TWO (2) CONTROL POINTS REFERENCED TO THE STATE PLANE GRID COORDINATE SYSTEM - TEXAS CENTRAL ZONE (4203), IN US FEET AND SHALL INCLUDE ROTATION INFORMATION AND SCALE FACTOR REQUIRED TO REPROJECT COORDINATES TO GRID COORDINATES IN US FEET.
13. THE CITY OF CEDAR PARK HAS NOT REVIEWED THESE PLANS FOR COMPLIANCE WITH THE AMERICANS WITH DISABILITIES ACT. IT IS THE RESPONSIBILITY OF THE OWNER TO PROVIDE COMPLIANCE WITH ALL LEGISLATION RELATED TO ACCESSIBILITY WITHIN THE LIMITS OF CONSTRUCTION SHOWN IN THESE PLANS. ALL RESPONSIBILITY FOR THE ADEQUACY OF THESE PLANS REMAINS WITH THE ENGINEER WHO PREPARED THEM. IN REVIEWING THESE PLANS, THE CITY OF CEDAR PARK MUST RELY ON THE ADEQUACY OF THE WORK OF THE DESIGN ENGINEER.
14. NO BLASTING IS ALLOWED ON THIS PROJECT.
15. A TRAFFIC CONTROL PLAN, IN ACCORDANCE WITH THE TEXAS MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES, SHALL BE SUBMITTED TO THE CITY FOR REVIEW AND APPROVAL PRIOR TO ANY PARTIAL OR COMPLETE ROADWAY CLOSURES. TRAFFIC CONTROL PLANS SHALL BE SITE SPECIFIC AND SEAL BY A REGISTERED PROFESSIONAL ENGINEER.
16. THE CONTRACTOR SHALL KEEP THE SITE CLEAN AND MAINTAINED AT ALL TIMES, TO THE SATISFACTION OF THE CITY. THE SUBDIVISION WILL NOT BE ACCEPTED (OR CERTIFICATE OF OCCUPANCY ISSUED) UNTIL THE SITE HAS BEEN CLEANED TO THE SATISFACTION OF THE CITY.
17. SIGNS ARE NOT PERMITTED IN PUBLIC UTILITY EASEMENTS, SET BACKS OR DRAINAGE EASEMENTS.
18. IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO INSPECT TEMPORARY EROSION CONTROLS ON A DAILY BASIS. ADJUST THE CONTROLS AND/OR REMOVE ANY SEDIMENT BUILDUP AS NECESSARY. A STOP WORK ORDER AND/OR FINE MAY BE IMPOSED IF THE EROSION CONTROLS ARE NOT MAINTAINED.
19. A FINAL CERTIFICATE OF OCCUPANCY WILL NOT BE ISSUED ON COMMERCIAL SITES UNTIL ALL DISTURBED AREAS HAVE BEEN RE-VEGETATED. SUBSTANTIAL GRASS COVER, AS DETERMINED BY ENGINEERING DEPARTMENT, MUST BE ACHIEVED PRIOR TO THE ISSUANCE OF A FINAL CERTIFICATE OF OCCUPANCY. ALL EROSION CONTROLS MUST REMAIN IN PLACE UNTIL ALL DISTURBED AREAS HAVE BEEN RE-VEGETATED TO THE SATISFACTION OF THE CITY OF CEDAR PARK ENGINEERING DEPARTMENT. PRIOR TO ISSUANCE OF A CERTIFICATE OF OCCUPANCY FOR A SITE DEVELOPMENT PERMIT, THE RIGHT OF WAY BETWEEN THE PROPERTY LINE AND EDGE OF PAVEMENT / BACK OF CURB SHALL BE REVEGETATED ACCORDING TO COA SPECIFICATION 602S AND 606S. CONTRACTOR SHALL BE RESPONSIBLE FOR KEEPING GRADES ADJUSTED TO AND NEAR THE SITE FREE FROM SOIL, SEDIMENT AND DEBRIS. CONTRACTOR WILL NOT REMOVE SOIL, SEDIMENT OR DEBRIS FROM ANY AREA OR VEHICLE BY MEANS OF WATER, UNLIT SHOVELING AND SWEEPING WILL BE ALLOWED. CONTRACTOR WILL BE RESPONSIBLE FOR DUST CONTROL FROM THE SITE. FAILURE TO COMPLY WITH THIS REQUIREMENT MAY RESULT IN A STOP WORK ORDER OR A FINE.
20. ALL WET UTILITIES SHALL BE INSTALLED AND ALL DENSITIES MUST HAVE PASSED INSPECTION(S) PRIOR TO THE INSTALLATION OF DRY UTILITIES.
21. A MINIMUM OF SEVEN DAYS OF CURE TIME IS REQUIRED FOR HMAc PRIOR TO THE INTRODUCTION OF VEHICULAR TRAFFIC TO ANY STREETS.
22. PRIOR TO ANY APPROVAL, THE ENGINEER SHALL SUBMIT TO THE ENGINEERING DEPARTMENT DOCUMENTATION OF SUBDIVISION/SITE REGISTRATION WITH THE TEXAS DEPARTMENT OF LICENSING AND REGULATIONS (TDLR) AND PROVIDE DOCUMENTATION OF REVIEW AND COMPLIANCE OF THE SUBDIVISION/SITE CONSTRUCTION PLANS WITH TEXAS ARCHITECTURAL BARRIERS ACT (TABA).
23. PRIOR TO SUBDIVISION/SITE ACCEPTANCE, THE ENGINEER/DEVELOPER/OWNER SHALL SUBMIT TO THE ENGINEERING DEPARTMENT DOCUMENTATION THAT THE SUBDIVISION/SITE WAS INSPECTED BY TDLR OR A REGISTERED ACCESSIBILITY SPECIALIST (RAS) AND THE SUBDIVISION/SITE IS IN COMPLIANCE WITH THE REQUIREMENTS OF THE TABA.
24. ALL CONSTRUCTION AND CONSTRUCTION RELATED ACTIVITIES SHALL BE PERFORMED MONDAY THRU FRIDAY FROM 7:00 A.M. TO 6:00 P.M. EXCEPT FOR THE FOLLOWING: CONSTRUCTED FEET (100') OF A DWELLING OR DWELLING UNIT SHALL BE PERFORMED BETWEEN THE HOURS OF 8:00 A.M. AND 6:00 P.M. OTHERWISE ALL CONSTRUCTION AND CONSTRUCTION RELATED ACTIVITIES SHALL CONFORM TO CITY OF CEDAR PARK CODE OF ORDINANCES, SPECIFICALLY ARTICLE 8.08.
25. APPROVAL FOR CONSTRUCTION ACTIVITIES PERMITTED ON HOLIDAYS, AND/OR SATURDAYS, OUTSIDE OF MONDAY THRU FRIDAY 8 AM TO 6 PM, OR IN EXCESS OF 8 HOURS PER DAY SHALL BE OBTAINED IN WRITING 48 HOURS IN ADVANCE, AND INSPECTION FEES AT 1.5 TIMES THE HOURLY INSPECTION RATE SHALL BE BILLED DIRECTLY TO THE CONTRACTOR. THERE SHALL BE NO CONSTRUCTION OR CONSTRUCTION RELATED ACTIVITIES PERFORMED ON SUNDAY. THE CITY RESERVES THE RIGHT TO REQUIRE THE CONTRACTOR TO UNCOVER ALL WORK PERFORMED WITHOUT CITY INSPECTION.
26. ALL POLES TO BE APPROVED BY CITY AND PEC, NO CONDUIT SHALL BE INSTALLED DOWN LOT LINES / BETWEEN BASIS. ALL CONDUIT SHALL BE LOCATED IN THE PUBLIC ROW OR IN AN EASEMENT ADJACENT TO AND PARALLEL TO THE PUBLIC ROW.
27. DRY UTILITIES SHALL BE INSTALLED AFTER SUBGRADE IS CUT AND BEFORE FIRST COURSE BASE. NO TRENCHING OF COMPACTED BASE. IF NECESSARY DRY UTILITIES INSTALLED AFTER FIRST COURSE BASE SHALL BE BORED ACROSS THE FULL WIDTH OF THE ROW.
28. NO PONDING OF WATER SHALL BE ALLOWED TO COLLECT ON OR NEAR THE INTERSECTION OF PRIVATE DRIVEWAYS(S) AND A PUBLIC STREET. RECONSTRUCTION OF THE DRIVEWAY APPROACH SHALL BE AT THE CONTRACTOR'S EXPENSE.
29. ALL DRIVEWAY APPROACHES SHALL HAVE A UNIFORM TWO PERCENT SLOPE WITHIN THE ROW UNLESS APPROVED IN WRITING BY THE ENGINEERING DEPARTMENT.
30. CONTRACTORS ON SITE SHALL HAVE AN APPROVED SET OF PLANS AT ALL TIMES. FAILURE TO HAVE AN APPROVED SET MAY RESULT IN A STOP WORK ORDER.
31. CONTRACTOR TO CLEAR FIVE FEET BEYOND ALL RIGHT OF WAY TO PREVENT VULNER VEGETATIVE GROWTH INTO THE SIDEWALK AREAS.
32. THERE SHALL BE NO WATER OR WASTEWATER APPURTENANCES, INCLUDING BUT NOT LIMITED TO, VALVES, FITTINGS, METERS, CLEAN-OUTS, MANHOLES, OR VAULTS IN ANY DRIVEWAY, SIDEWALK, TRAFFIC OR PEDESTRIAN AREA.
33. SIDEWALKS SHALL NOT USE CURB INLETS AS A PARTIAL WALKING SURFACE. SIDEWALKS SHALL NOT USE TRAFFIC CONTROL BOXES, METER OR CHECK VALVE VAULTS, COMMUNICATION VAULTS, OR OTHER BURIED OR PARTIALLY BURIED INFRASTRUCTURE AS A VEHICULAR OR PEDESTRIAN SURFACE.
34. STREET NOTES:
35. NO TRENCHING OF COMPACTED BASE WILL BE ALLOWED. A PENALTY AND/OR FINE MAY BE IMPOSED TO THE GENERAL CONTRACTOR IF TRENCHING OF COMPACTED BASE OCCURS WITHOUT CITY APPROVAL, REGARDLESS OF WHO PERFORMED THE TRENCHING.
36. ALL SIDEWALKS SHALL COMPLY WITH THE AMERICANS WITH DISABILITIES ACT. THE CITY OF CEDAR PARK HAS NOT REVIEWED THESE PLANS FOR COMPLIANCE WITH THE AMERICANS WITH DISABILITIES ACT, OR ANY OTHER ACCESSIBILITY LEGISLATION, AND DOES NOT WARRANT OR APPROVE THESE PLANS FOR ANY ACCESSIBILITY STANDARDS.
37. STREET BARRICADES SHALL BE INSTALLED ON ALL DEAD END STREETS AND AS NECESSARY DURING CONSTRUCTION TO MAINTAIN JOB SAFETY.
38. ANY DAMAGE CAUSED TO EXISTING PAVEMENT, CURBS, SIDEWALKS, RAMPS, ETC., SHALL BE REPAIRED BY THE CONTRACTOR TO THE SATISFACTION OF THE CITY PRIOR TO ACCEPTANCE OF THE SUBDIVISION.
39. AT INTERSECTIONS, WHICH HAVE VALLEY DRAINAGE, THE CROWN TO THE INTERSECTING STREET WILL BE CULMINATED AT A DISTANCE OF 40 FT. FROM THE INTERSECTING CURB LINE UNLESS OTHERWISE NOTED.
40. THE SUBGRADE MATERIAL WAS TESTED BY (MLA GEOTECHNICAL, 2804 LONGHORN BOULEVARD AUSTIN, TX 78758 PHONE: (512) 873-8899) ON (3/30/2024) ON (3/30/2024) THE PAVEMENT SECTIONS WERE DESIGNED ACCORDINGLY. THE PAVEMENT SECTIONS ARE TO BE CONSTRUCTED AS FOLLOWS:

Table 1: Recommended Pavement Section Thickness, Inches

Table with 5 columns: Expected Traffic, Average Daily Truck Traffic, Flexible Pavement (HMAC, CLB, JRPPC), Rigid Pavement (CLB). Rows include Passenger Vehicles and Heavy Duty Trucks*.

Notes:

- Abbreviations: HMAc - Hot Mixed Asphalt Concrete, CLB - Crushed Limestone Base, JRPPC - Jointed, Reinforced Portland Cement Concrete
• *Heavy-duty truck parking, loading, unloading, and turning areas should use the rigid pavement option.
• The pavement thicknesses above, once complete, will be capable of supporting a total vehicle live load of 80,000 pounds and meets the HS-20 (16 kips per wheel) load carrying capacity required.
• Average Daily Truck Traffic excludes pickup and panel trucks.
• Inadequate drainage of the pavement system will accelerate pavement distress and result in increased maintenance costs. Adequate drainage should be provided for the pavement system. Adequate drainage consists of a curb and gutter or a shoulder and bar ditch system.

- 7. DENSITY TESTING OF COMPACTED SUBGRADE MATERIAL, FIRST COURSE AND SECOND COURSE COMPACTED BASE SHALL BE MADE AT 500 FOOT INTERVALS.
8. ALL DENSITY TESTING IS THE RESPONSIBILITY OF THE OWNER OR CONTRACTOR AND SHALL BE WITNESSED BY THE CITY OF CEDAR PARK'S PROJECT REPRESENTATIVE. THE CONTRACTOR IS TO NOTIFY THE CITY 48 HOURS PRIOR TO SCHEDULED DENSITY TESTING.
9. TRAFFIC CONTROL SIGNS AND PAVEMENT MARKINGS SHALL BE IN ACCORDANCE WITH THE TEXAS MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES AND INSTALLED AS DIRECTED BY THE CITY OF CEDAR PARK PRIOR TO CITY ACCEPTANCE OF THE SUBDIVISION.
10. SLOPE OF NATURAL GROUND ADJACENT TO THE RIGHT-OF-WAY SHALL NOT EXCEED 3:1. IF A 3:1 SLOPE IS NOT POSSIBLE, A RETAINING WALL OR SOME OTHER FORM OF SLOPE PROTECTION APPROVED BY THE CITY SHALL BE PLACED IN AN EASEMENT ACCEPTABLE TO THE CITY.
11. THE CITY, ENGINEER, CONTRACTOR, AND A REPRESENTATIVE FROM THE ASPHALT TESTING LAB SHALL ATTEND A PRE-PAVING CONFERENCE PRIOR TO THE START OF HMAc PAVING. THE CONTRACTOR SHALL GIVE THE CITY A MINIMUM OF 48 HOURS NOTICE PRIOR TO THIS MEETING (512-401-5000).
12. THE CONTRACTOR OR OWNER IS RESPONSIBLE FOR CONDUCTING TESTS ON ASPHALT PAVEMENT IN ACCORDANCE WITH THE REQUIREMENTS SET FORTH IN THE CITY OF AUSTIN STANDARD SPECIFICATION NO. 340 ANY RE-TESTING OF THE ASPHALT PAVEMENT SHALL BE CONDUCTED UNDER THE SUPERVISION OF THE ENGINEER AND THE CITY OF CEDAR PARK. RE-TESTING OF THE ASPHALT PAVEMENT SHALL BE LIMITED TO ONE RETEST PER PROJECT.
13. ALL PAVEMENT MARKINGS AND SIGNAGE SHALL COMPLY WITH MUTCD STANDARDS. STREET NAME LETTER SIZING SHALL BE IN ACCORDANCE WITH MUTCD/BLACK/22-2 PAVEMENT MARKINGS SHALL BE THERMOPLASTIC UNLESS OTHERWISE NOTED.
14. ALL STREET NAME SIGNS SHALL BE HIGH INTENSITY RETRO GRADE. NO FENCING OR WALL IS ALLOWED TO BE CONSTRUCTED SO THAT IT OBSTRUCTS THE SIGHT LINES OF DRIVERS FROM AN INTERSECTING PUBLIC ROADWAY OR FROM AN INTERSECTING PRIVATE DRIVEWAY. SIGHT LINES ARE TO BE MAINTAINED AS DESCRIBED IN CITY CODE SECTION 14.05.007. INSTALLING A FENCE OR WALL WHICH DOES NOT COMPLY WITH THE CITY'S SIGHT DISTANCE REQUIREMENTS OR FENCING REGULATIONS IS A VIOLATION OF THE CITY'S ORDINANCE AND MAY BE PUNISHABLE PURSUANT TO SECTION 1.01.009 OF CITY CODE.
15. TEMPORARY ROCK CRUSHING OPERATIONS ARE NOT ALLOWED. ALL SOURCES FOR FLEXIBLE BASE MATERIAL ARE REQUIRED TO BE APPROVED BY THE CITY. PRIOR TO BASE PLACEMENT ALL CURRENT TRIAXIAL TEST REPORTS FOR THE PROPOSED STOCKPILES ARE TO BE SUBMITTED TO THE CITY'S PROJECT REPRESENTATIVE FOR REVIEW AND APPROVAL.
16. UTILITY SERVICE BOXES OR OTHER UTILITY FACILITIES SHALL NOT BE INSTALLED WITHIN AREAS DETERMINED TO BE REQUIRED SIGHT LINES OF TWO INTERSECTING PUBLIC STREETS OR WITHIN SIGHT LINES OF A PRIVATE DRIVEWAY. SIGHT LINES ARE TO BE MAINTAINED COMPLIANT WITH TABLE 1-1 OF THE AUSTIN TRANSPORTATION CRITERIA MANUAL. UTILITIES DETERMINED BY THE DIRECTOR OF ENGINEERING TO BE PLACED WITHIN REQUIRED SIGHT LINES MAY BE REQUIRED TO BE RELOCATED AT THE EXPENSE OF THE CONTRACTOR PRIOR TO THE CITY ISSUING A CERTIFICATE OF OCCUPANCY OR PRIOR TO THE CITY'S ACCEPTANCE OF THE PROJECT IMPROVEMENTS.
17. ALL LANE CLOSURES SHALL OCCUR ONLY BETWEEN THE HOURS OF 9 AM AND 4 PM. ANY NIGHT TIME LANE CLOSURES REQUIRE APPROVAL BY THE DIRECTOR OF ENGINEERING AND SHALL OCCUR BETWEEN THE HOURS OF 8 PM AND 6 AM. LANE CLOSURES OBSERVED BY CITY DURING THE PEAK HOURS OF 6 AM TO 9 AM, OR 4 PM TO 8 PM WILL BE SUBJECT TO FINE PER CHAPTER 1 OF CITY ORDINANCE, AND/OR SUBSEQUENT ISSUANCE OF WORK STOPPAGE.
18. IMPROVEMENTS TO EXISTING RECONSTRUCTION OF AN EXISTING TYPE II DRIVEWAY SHALL BE DONE IN A MANNER WHICH RETAINS OPERATIONS OF NOT LESS THAN HALF OF THE DRIVEWAY AT ALL TIMES. FULL CLOSURE OF SUCH DRIVEWAY CAN BE CONSIDERED WITH WRITTEN AUTHORIZATION RETAINED BY THE CONTRACTOR FROM THE PROPERTY OWNER(S) OR ACCESS EASEMENT RIGHT HOLDER(S) OF THE DRIVEWAY ALLOWING FULL CLOSURE OF THE DRIVEWAY.
19. TREES MUST NOT BE OVERKROPPED WITHIN 10' VERTICALLY OF A SIDEWALK, OR 18' VERTICALLY OF A ROADWAY OR DRIVEWAY.

WASTEWATER NOTES:

- 1. REFER TO THE CITY OF CEDAR PARK PUBLIC WORKS UTILITY POLICY AND SPECIFICATIONS MANUAL.
2. MANHOLE FRAMES AND COVERS AND WATER VALVE BOXES SHALL BE RAISED TO FINISHED PAVEMENT GRADE AT THE OWNER'S EXPENSE BY THE CONTRACTOR WITH CITY APPROVAL. ALL UTILITY ADJUSTMENTS SHALL BE COMPLETED PRIOR TO FINAL PAVING CONSTRUCTION.
3. THE LOCATION OF ANY EXISTING UTILITY LINES SHOWN ON THESE PLANS MAY NOT BE ACCURATE. ANY DAMAGE TO EXISTING UTILITY LINES, BOTH KNOWN AND UNKNOWN, SHALL BE REPAIRED AT THE EXPENSE OF THE CONTRACTOR. THE CONTRACTOR SHALL LOCATE ALL UTILITIES PRIOR TO BIDDING THE PROJECT.
4. ALL IRON PIPE AND FITTINGS SHALL BE WRAPPED WITH AT LEAST 8 MIL. POLYETHYLENE WRAP.
5. ALL WATER MAINS, WASTEWATER MAINS AND SERVICE LINES SHALL MEET CITY OF AUSTIN MINIMUM COVER SPECIFICATIONS. ALL STREETS ARE TO BE CUT TO SUBGRADE PRIOR TO INSTALLATION OF WATER MAINS OR CUTS WILL BE ISSUED BY THE ENGINEER.
6. WHERE 48-INCHES OF COVER BELOW SUBGRADE CANNOT BE ACHIEVED FOR WASTEWATER SERVICE LINES ALTERNATE MATERIALS MAY BE USED. A MINIMUM OF 36-INCHES OF COVER BELOW SUBGRADE SHALL BE ACHIEVED. ANY WASTEWATER SERVICE LINE WITH COVER BETWEEN 36-INCH AND 48- INCHES SHALL BE SDR-26 PVC PRESSURE PIPE.
7. GASKETED PVC SEWER MAIN FITTINGS SHALL BE USED TO CONNECT SDR-35 PVC TO SDR-26 PVC PRESSURE PIPE OR C-900.
8. PIPE MATERIALS TO BE USED FOR CONSTRUCTION OF UTILITY LINES: WASTEWATER- 6" PVC-SDR-26 FORCE MAIN- N/A (NOTE: IF USING PVC, SDR-26 IS REQUIRED. SDR-35 WW IS NOT ALLOWED. FORCEMAINS SHALL BE EPOXY LINED DUCTILE IRON)
9. ALL SANITARY SEWERS, EXCLUDING SERVICE LINES, SHALL BE MANHOLE TESTED PER TCEQ (TEXAS COMMISSION ON ENVIRONMENTAL QUALITY) CRITERIA. A MANHOLE TEST WILL NOT BE PERFORMED UNTIL BACKFILL HAS BEEN IN PLACE FOR A MINIMUM OF 30 DAYS.
10. ALL WASTEWATER LINES 10" AND LARGER SHALL BE VIDEO INSPECTED IN ACCORDANCE WITH CITY OF CEDAR PARK PUBLIC AND STANDARD SPECIFICATIONS. VIDEO INSPECTION SHALL BE PERFORMED IN ACCORDANCE WITH E REQUIREMENTS FOR VIDEO INSPECTION OF WASTEWATER LINES AT THE CONTRACTOR'S EXPENSE. NO SEPARATE PAY UNLESS NOTED ON THE BID FORM.
11. ALL SANITARY SEWERS, INCLUDING SERVICE LINES, SHALL BE AIR TESTED PER CITY OF AUSTIN STANDARD SPECIFICATIONS.
12. DENSITY TESTING OF COMPACTED BACKFILL SHALL BE MADE AT A RATE OF ONE TEST PER TWO FOOT LIFTS PER 500 FEET OF INSTALLED PIPE.
13. CITY SHALL BE GIVEN 48 HOURS NOTICE PRIOR TO ALL TESTING OF WATER AND WASTEWATER LINES. CITY INSPECTION IS REQUIRED FOR ALL TESTING OF WATER AND WASTEWATER LINES.
14. WHERE A WATER OR WASTEWATER LINE CROSSES ABOVE (OR BELOW) A STORM SEWER STRUCTURE AND THE BOTTOM (OR TOP) OF THE PIPE IS WITHIN 18 INCHES OF THE TOP (OR BOTTOM) OF THE UTILITY STRUCTURE, THE PIPE SHALL BE ENCASED WITH CONCRETE FOR A DISTANCE OF AT LEAST 1 FT. ON EITHER SIDE OF THE DITCH LINE OF THE UTILITY STRUCTURE OR THE STORM SEWER. CONCRETE ENCASEMENT WILL NOT BE REQUIRED FOR DUCTILE IRON (THICKNESS CLASS 50), AWWA C-900 (SDR- 18) 150 PSI RATED PVC IN SIZES TO 12 INCHES OR AWWA C-905 (SDR- 25) 165 PSI RATED PVC IN SIZES LARGER THAN 12 INCHES. CONCRETE ENCASEMENT SHALL CONFORM TO C.O.A. STANDARD DETAIL 505-1.
15. THE ALLOWABLE (MAXIMUM) ADJUSTMENT FOR A MANHOLE SHALL BE 12" (INCHES) OR LESS.
16. WHERE A SEWER LINE CROSSES A WATER LINE, THE SEWER LINE SHALL BE ONE 20 FT. JOINT OF 150 PSI RATED PVC CENTERED ON CROSSING.
17. ALL MANHOLE AND INLET COVERS SHALL READ 'CITY OF CEDAR PARK'.
18. CONTRACTOR TO NOTIFY, AND OBTAIN APPROVAL FROM, THE CITY OF CEDAR PARK 48 HOURS PRIOR TO CONNECTING TO EXISTING CITY UTILITIES.

- 19. ALL PIPE BEDDING MATERIAL SHALL CONFORM TO CITY OF AUSTIN STANDARD SPECIFICATIONS. UNLESS OTHERWISE SPECIFIED BY THE CONTRACTOR, CONCRETE IS TO BE CLASS "A" (5 SACK, 3000 PSI - 28-DAYS), AND ALL REINFORCING STEEL TO BE ASTM A615 60.
20. ALL WASTEWATER MANHOLES TO BE COATED WITH ORGANIC MATERIALS AND PROCEDURES LISTED IN CITY OF AUSTIN QUALIFIED PRODUCTS LIST NO. WW-511 (WW-511A AND WW-511B ARE NOT ALLOWED UNLESS MANHOLES ARE BEING STRUCTUREALLY REINFORCED WITH APPROVAL BY PUBLIC WORKS). ALL MANHOLES WILL BE PRE-COATED OR COATED AFTER TESTING.
21. POLYBRID COATINGS ON WASTEWATER MANHOLES WILL NOT BE ALLOWED. ANY OTHER PRODUCT APPEARING ON THE COA SPL WW-511 IS ACCEPTABLE.
22. ALL PENETRATIONS OF EXISTING WASTEWATER MANHOLES ARE REQUIRED TO BE RE-COATED IN ACCORDANCE WITH THE SPECIFICATIONS LISTED IN NOTE 20.
23. ALL MANHOLES WILL BE VACUUM TESTED ONLY.
24. TRACER TAPE AND MARKING TAPE SHALL BE INSTALLED ON ALL WATER AND WASTEWATER MAINS IN ACCORDANCE WITH CITY OF AUSTIN STANDARDS, REGARDLESS OF THE TYPE OF PIPE.
26. ALL PRESSURE RESTRAINT AND CONCRETE THRUST BLOCKING AT ALL VALVES, BENDS, TEES, PLUGS, AND OTHER FITTINGS.

WATER NOTES:

- 1. REFER TO THE CITY OF CEDAR PARK PUBLIC WORKS UTILITY POLICY AND SPECIFICATIONS MANUAL.
2. THE TOP OF VALVE STEMS SHALL BE AT LEAST 18" AND NO MORE THAN 36" BELOW FINISHED GRADE. VALVE STEM RISERS SHALL BE WELDED ON EACH END TO THE CITY'S SATISFACTION.
3. FIRE HYDRANT LEADS TO BE DUCTILE IRON, CLASS 350, AND INSTALLED PER CITY OF AUSTIN STANDARD SPECIFICATIONS AND DETAIL.
4. PRIOR TO INSTALLATION OF FIRE HYDRANTS, THE ENGINEER WILL PROVIDE THE CONTRACTOR ONE (1) CUT FROM A HUB PIN, ESTABLISHING THE ELEVATION OF THE BURY LINE.
5. THE ENGINEER SHALL PROVIDE CUTS FOR ALL WATER LINES AT ALL STORM SEWER CROSSINGS TO THE CITY OF CEDAR PARK.
6. PIPE MATERIALS TO BE USED FOR CONSTRUCTION OF UTILITY LINES:
• FIRE LINE - C900 DR-14 PVC AND FOR THE LARGER WATER LINES.
• DOMESTIC AND IRRIGATION SERVICE LINES - POLYETHYLENE COPPER PIPE AND FITTINGS ARE NOT PERMITTED WITHIN THE RIGHT-OF-WAY. MINIMUM DR-14 12" DIA AND SMALLER, MINIMUM CLASS 250 DI LARGER THAN 12" DIA.
7. APPROVED 5 1/2" FIRE HYDRANTS:
• AMERICAN FLOW CONTROL, 884B
• MUELLER COMPANY, SUPER CENTURION 250
• CLOW MEDALLION HYDRANT
- REQUIREMENTS FOR PRIVATE FIRE HYDRANTS (BEHIND DOUBLE CHECK BACKFLOW PREVENTION ASSEMBLY) MUST BE IN ACCORDANCE WITH THE CITY OF AUSTIN SPECIFICATIONS.
• ALL FIRE HYDRANTS MUST MEET CITY OF CEDAR PARK THREAD SPECIFICATIONS (NATIONAL THREAD)
• BLUE REFLECTOR MARKERS SHALL BE LOCATED ON THE CENTERLINE OF THE PAVEMENT ACROSS FROM ALL FIRE HYDRANTS. PAVEMENT MARKERS AT INTERSECTIONS SHALL BE FOUR-SIDED.
8. SHOULD A TAPPING SADDLE BE APPROVED BY PUBLIC WORKS, THE SADDLE SHALL BE SMITH-BLAIR 862 STAINLESS STEEL TAPPING SADDLE. REQUESTS FOR ALTERNATE PROVIDERS SHALL BE MADE TO THE CITY OF CEDAR PARK PUBLIC WORKS. NO TAP EXCEEDING 2" IN DIAMETER WILL BE APPROVED.
9. ALL WATER LINES, INCLUDING SERVICE LINES, SHALL BE PRESSURE AND LEAK TESTED PER CITY OF AUSTIN STANDARD SPECIFICATIONS AND DETAIL. THE CITY OF CEDAR PARK PUBLIC WORKS, ALL TESTING IS TO BE THE RESPONSIBILITY OF THE CONTRACTOR, AND THE CONTRACTOR MAY BE REQUIRED TO RE-TEST LINES IF THE TESTING IS NOT WITNESSED BY THE CITY. CONTRACTOR MUST NOTIFY THE CITY OF CEDAR PARK 48 HOURS PRIOR TO ANY TESTING. INITIAL WATER LINE DISINFECTION MUST MEET A CHLORINE RESIDUAL OF 50PPM AND A MINIMUM RESIDUAL OF 10PPM AFTER A 24 HOUR DETENTION PERIOD. SECTIONS THAT ARE 20 - 30 FEET CAN USE GRANULAR CLOROX FOR DISINFECTION, BUT ANYTHING BEYOND THAT MUST BE LIQUID DISINFECTION TO EVENLY CLEAN THE PIPE.
10. ALL WATER LINES SHALL BE STERILIZED AND BACTERIOLOGICALLY TESTED IN ACCORDANCE WITH CITY OF AUSTIN STANDARDS. THE CONTRACTOR IS RESPONSIBLE FOR STERILIZATION AND THE CITY OF CEDAR PARK IS RESPONSIBLE FOR TESTING. THE CONTRACTOR SHALL SUBMIT A LETTER TO THE CITY OF CEDAR PARK REQUESTING A CONTRACTOR SPECIALIZED IN DISINFECTION FOR LARGE DIAMETER LINES OR CRITICAL INFRASTRUCTURE, SUBSIDIARY TO PIPE INSTALLATION.
11. DENSITY TESTING OF COMPACTED BACKFILL SHALL BE MADE AT A RATE OF ONE TEST PER TWO FOOT LIFTS PER 500 FEET OF INSTALLED PIPE.
12. CONTRACTOR TO OBTAIN A WATER METER FROM THE CITY OF CEDAR PARK FOR ANY WATER THAT MAY BE REQUIRED DURING CONSTRUCTION. (512-401-5000)
13. ALL WATER METER BOXES SHALL BE FORD GULF METER BOX WITH LOCKING LID.
• SINGLE G-148-233
• DUAL G-148-243
• 1" METER YL111 - 444
• 1 1/2" - 2" METER 1730-R (LID) & 1730-12 (BOX)/ACCEPTABLE BOXES FOR THIS SIZE OF METER
14. MANHOLE FRAMES AND COVERS AND WATER VALVE BOXES SHALL BE RAISED TO FINISHED PAVEMENT GRADE, WHEN IN PUBLIC STREETS, AT THE OWNER'S EXPENSE BY THE CONTRACTOR WITH CITY INSPECTION. ALL UTILITY ADJUSTMENTS SHALL BE COMPLETED PRIOR TO FINAL PAVING CONSTRUCTION.
15. THE LOCATION OF ANY EXISTING UTILITY LINES SHOWN ON THESE PLANS IS THE BEST AVAILABLE AND MAY NOT BE ACCURATE. ANY DAMAGE TO EXISTING UTILITY LINES, BOTH KNOWN AND UNKNOWN, SHALL BE REPAIRED AT THE EXPENSE OF THE CONTRACTOR.
16. ALL IRON PIPE AND FITTINGS SHALL BE WRAPPED WITH AT LEAST 8 MIL. POLYETHYLENE WRAP.
17. ALL WATER MAINS, WASTEWATER MAINS AND SERVICE LINES SHALL MEET CITY OF AUSTIN SPECIFICATIONS FOR MINIMUM COVER REQUIREMENTS. ALL STREETS ARE TO BE CUT TO SUBGRADE PRIOR TO INSTALLATION OF WATER MAINS OR CUTS WILL BE ISSUED BY THE ENGINEER.
18. CITY TO BE GIVEN 48 HOURS NOTICE PRIOR TO ALL TESTING OF WATER AND WASTEWATER LINES. CITY INSPECTION IS REQUIRED FOR ALL TESTING OF WATER AND WASTEWATER LINES.
19. WHERE A WATER OR WASTEWATER LINE CROSSES ABOVE (OR BELOW) A STORM SEWER STRUCTURE AND THE BOTTOM (OR TOP) OF THE PIPE IS WITHIN 18 INCHES OF THE TOP (OR BOTTOM) OF THE UTILITY STRUCTURE, THE PIPE SHALL BE ENCASED WITH CONCRETE FOR A DISTANCE OF AT LEAST 1 FT. ON EITHER SIDE OF THE DITCH LINE OF THE UTILITY STRUCTURE OR THE STORM SEWER. CONCRETE ENCASEMENT WILL NOT BE REQUIRED FOR DUCTILE IRON (THICKNESS CLASS 50), AWWA C-900 (SDR- 18) 150 PSI RATED PVC IN SIZES TO 12 INCHES OR AWWA C-905 (SDR- 25) 165 PSI RATED PVC IN SIZES LARGER THAN 12 INCHES. CONCRETE ENCASEMENT SHALL CONFORM TO C.O.A. STANDARD DETAIL 505-1.
20. CONTRACTOR TO NOTIFY THE CITY OF CEDAR PARK 48 HOURS PRIOR TO CONNECTING TO EXISTING UTILITIES.
21. ALL PIPE BEDDING MATERIAL SHALL CONFORM TO CITY OF AUSTIN STANDARD SPECIFICATIONS.
22. TRACER TAPE SHALL BE INSTALLED ON ALL WATER AND WASTEWATER MAINS REGARDLESS OF THE TYPE OF PIPE OR DEPTH OF PIPE INSTALLED.
23. UNLESS OTHERWISE SPECIFIED BY THE ENGINEER ALL CONCRETE IS TO BE CLASS "A" (5 SACK, 3000 PSI - 28-DAYS), AND ALL REINFORCING STEEL TO BE ASTM A615 60.
24. THE CITY CONSIDERS PROTECTION OF ITS WATER SYSTEM PARAMOUNT TO CONSTRUCTION ACTIVITIES. CITY PERSONNEL WILL OPERATE AND MAINTAIN THE CONTRACTOR TO OPERATE. ALL WATER VALVES THAT WILL PASS THROUGH THE CITY'S POTABLE WATER, THE CONTRACTOR MAY NOT OPERATE ANY WATER VALVE, EXISTING OR PROPOSED, THAT WILL ALLOW WATER FROM THE CITY'S WATER SYSTEM TO FLOW TO A PROPOSED OR EXISTING WATER SYSTEM WITHOUT THE EXPRESS CONSENT OF THE CITY. NOTIFY THE CITY TWO BUSINESS DAYS IN ADVANCE OF ANY REFER TO THE CITY OF CEDAR PARK WATER VALVE. THE GENERAL CONTRACTOR MAY BE FINED \$500 OR MORE, INCLUDING ADDITIONAL THEFT OF WATER FINE, IF A WATER VALVE IS OPERATED IN AN UNAUTHORIZED MANNER, REGARDLESS OF WHO OPERATED THE VALVE.
25. ALL WATER VALVES OVER 24" IN SIZE SHALL HAVE A BY-PASS LINE AND VALVE INSTALLED. BY-PASS VALVES AND LINES ARE SUBSIDIARY TO THE COST OF THE VALVE UNLESS SPECIFICALLY IDENTIFIED ON THE BID FORM.
26. ALL WATER VALVES, INCLUDING THOSE OVER 12" IN SIZE, SHALL BE GATE VALVES.
27. A DOUBLE CHECK BACKFLOW DEVICE IN A VAULT SHALL BE INSTALLED AT THE PROPERTY LINE ON ALL PRIVATE FIRE LINES. A DETECTOR WATER METER WILL BE INSTALLED ON THIS BACKFLOW DEVICE, AND IT MUST BE A SENSUS SRII 3/4" METER WITH AMI READOUT CAPABILITY. THE CITY WILL PROVIDE THIS METER. PLEASE REFERENCE THE CITY OF CEDAR PARK DOUBLE CHECK BACKFLOW PREVENTION ASSEMBLY DETAIL.
28. ALL POTABLE WATER SYSTEM COMPONENTS INSTALLED AFTER JANUARY 4, 2014, SHALL BE "LEAD FREE" ACCORDING TO THE UNITED STATES SAFE DRINKING WATER ACT. THE ONLY COMPONENTS EXEMPT FROM THIS REQUIREMENT ARE FIRE HYDRANTS. COMPONENTS THAT ARE NOT CLEARLY IDENTIFIED BY THE MANUFACTURER AS MEETING THIS REQUIREMENT BY MARKING OR ON THE PRODUCT PACKAGING, OR BY PRE-APPROVED SUBMITTAL, WILL BE REJECTED FOR USE. A NSF CERTIFICATION WILL BE ADEQUATE IF THE CERTIFICATION HAS NOT EXPIRED AS OF JANUARY 4, 2014 AND REMAINS UNEXPIRED AT THE TIME OF CONSTRUCTION.
29. ALL PRESSURE PIPE SHALL HAVE MECHANICAL RESTRAINT AND CONCRETE THRUST BLOCKING AT ALL VALVES, BENDS, TEES, PLUGS, AND OTHER FITTINGS.

STORM SEWER NOTES:

- 1. MANHOLE FRAMES AND COVERS AND WATER VALVE BOXES SHALL BE RAISED TO FINISHED PAVEMENT GRADE AT THE OWNER'S EXPENSE BY THE CONTRACTOR WITH CITY INSPECTION. ALL UTILITY ADJUSTMENTS SHALL BE COMPLETED PRIOR TO FINAL PAVING CONSTRUCTION. CONTRACTOR SHALL BACKFILL AROUND MANHOLES AND JUNCTION BOXES WITH CLASS A CONCRETE.
2. ALL MANHOLE LIDS SHALL BE 32" OR LARGER, UNLESS EXPRESSLY APPROVED IN WRITING BY THE ENGINEERING DEPARTMENT.
3. THE LOCATION OF ANY EXISTING UTILITY LINES SHOWN ON THESE PLANS IS THE BEST AVAILABLE AND MAY NOT BE ACCURATE. ANY DAMAGE TO EXISTING UTILITY LINES, BOTH KNOWN AND UNKNOWN, SHALL BE REPAIRED AT THE EXPENSE OF THE CONTRACTOR.
4. PIPE MATERIALS TO BE USED FOR CONSTRUCTION OF UTILITY LINES: UNLESS OTHERWISE SPECIFIED BY THE ENGINEER, ALL STORM SEWER RCP SHALL BE CLASS III CORRUGATED METAL PIPE IS NOT PERMITTED.
5. ALL MANHOLE AND INLET COVERS SHALL READ 'CITY OF CEDAR PARK'.
6. CONTRACTOR TO NOTIFY THE CITY OF CEDAR PARK 48 HOURS PRIOR TO CONNECTING TO EXISTING UTILITIES.
7. ALL PIPE BEDDING MATERIAL SHALL CONFORM TO CITY OF AUSTIN STANDARD SPECIFICATIONS.
8. UNLESS OTHERWISE SPECIFIED BY THE ENGINEER ALL CONCRETE IS TO BE CLASS "A" (5 SACK, 3000 PSI - 28-DAYS), AND ALL REINFORCING STEEL TO BE ASTM A615 60.
9. CONTRACTOR TO INSTALL AND MAINTAIN GEO-TEXTILE FABRIC BARRIER (INLET PROTECTION) AROUND STORM SEWER LEADS AND INLETS TO PREVENT SILT AND OTHER MATERIAL FROM ENTERING THE STORM SEWER COLLECTION SYSTEM.
10. INSTALL CONCRETE SAFETY END TREATMENTS TO ALL CULVERTS AND ENDS OF DRAINAGE PIPE.
11. ALL CURB INLETS SHALL HAVE AN ALMETEK 4" DISC "NO DUMPING DRAINS TO WATERWAY" MARKER.

THE FOLLOWING SEQUENCE OF CONSTRUCTION SHALL BE USED FOR ALL DEVELOPMENT. THE APPLICANT IS ENCOURAGED TO

PROVIDE ANY ADDITIONAL DETAILS APPROPRIATE FOR THE PARTICULAR DEVELOPMENT.

- 1. TEMPORARY EROSION AND SEDIMENTATION CONTROLS ARE TO BE INSTALLED AS INDICATED ON THE APPROVED SITE PLAN OR SUBDIVISION CONSTRUCTION PLAN AND IN ACCORDANCE WITH THE EROSION SEDIMENTATION CONTROL PLAN (ESc) AND STORMWATER POLLUTION PREVENTION PLAN (SWPPP) THAT IS REQUIRED TO BE POSTED ON THE SITE. INSTALL TREE PROTECTION AND INITIATE TREE MITIGATION MEASURES.
2. THE GENERAL CONTRACTOR MUST CONTACT THE CITY INSPECTOR AT 512-401-5000, 72 HOURS PRIOR TO THE SCHEDULED DATE OF THE REQUIRED ON-SITE PRECONSTRUCTION MEETING.
3. THE GENERAL CONTRACTOR WILL FOLLOW THE EROSION SEDIMENTATION CONTROL PLAN (ESc) AND STORM WATER POLLUTION PREVENTION PLAN (SWPPP) POSTED ON THE SITE. TEMPORARY EROSION AND SEDIMENTATION CONTROLS WILL BE REVISED, IF NEEDED, TO COMPLY WITH CITY INSPECTORS' DIRECTIVES, AND REVISED CONSTRUCTION SCHEDULE RELATIVE TO THE WATER QUALITY PLAN REQUIREMENTS AND THE EROSION PLAN.
4. ROUGH GRADE THE POND(S) AT 100% PROPOSED CAPACITY. EITHER THE PERMANENT OUTLET STRUCTURE OR A TEMPORARY OUTLET MUST BE CONSTRUCTED PRIOR TO DEVELOPMENT OF EMBANKMENT OR EXCAVATION THAT LEADS TO PONDING CONDITIONS. THE OUTLET SYSTEM MUST CONSIST OF A SUMP PIT OUTLET AND AN EMERGENCY SPILLWAY MEETING THE REQUIREMENTS OF THE CITY OF AUSTIN DRAINAGE CRITERIA MANUAL, AS REQUIRED. THE OUTLET SYSTEM SHALL BE PROTECTED FROM EROSION AND SHALL BE MAINTAINED THROUGHOUT THE COURSE OF CONSTRUCTION UNTIL INSTALLATION OF THE PERMANENT WATER QUALITY POND(S).
5. TEMPORARY EROSION AND SEDIMENTATION CONTROLS WILL BE INSPECTED AND MAINTAINED IN ACCORDANCE WITH THE EROSION SEDIMENTATION CONTROL PLAN (ESc) AND STORM WATER POLLUTION PREVENTION PLAN (SWPPP) POSTED ON THE SITE.
6. BEGIN SITE CLEARING/CONSTRUCTION (OR DEMOLITION) ACTIVITIES.
7. UNDERGROUND UTILITIES WILL BE INSTALLED, INCLUDING FIRE HYDRANTS.
8. 8PIRE DEPARTMENT ACCESS WILL BE INSTALLED WHERE REQUIRED BY APPROVED SITE PLAN.
9. VERTICAL CONSTRUCTION MAY OCCUR AFTER THE PRE-VEGETATION INSPECTION HAS BEEN CLEARED BY THE FIRE MARSHAL.
10. PERMANENT WATER QUALITY PONDS OR CONTROLS WILL BE CLEANED OUT AND FILTER MEDIA WILL BE INSTALLED PRIOR TO CONCURRENTLY WITH REVEGETATION OF SITE.
11. COMPLETE CONSTRUCTION AND START REVEGETATION OF THE SITE AND INSTALLATION OF LANDSCAPING.
12. UPON COMPLETION OF THE SITE CONSTRUCTION AND REVEGETATION OF A PROJECT SITE, THE DESIGN ENGINEER SHALL SUBMIT AN ENGINEER'S LETTER OF CONCURRENCE BEARING THE ENGINEER'S SEAL, SIGNATURE, AND DATE TO THE CITY INDICATING THAT CONSTRUCTION, INCLUDING REVEGETATION, IS COMPLETE AND IN SUBSTANTIAL CONFORMANCE WITH THE APPROVED PLANS. AFTER RECEIVING THIS LETTER, A FINAL INSPECTION WILL BE SCHEDULED BY THE CITY INSPECTOR.
13. UPON COMPLETION OF LANDSCAPE INSTALLATION OF A PROJECT SITE, THE LANDSCAPE ARCHITECT SHALL SUBMIT A LETTER OF CONCURRENCE TO THE CITY INDICATING THAT THE REQUIRED LANDSCAPING IS COMPLETE AND IN SUBSTANTIAL CONFORMANCE WITH THE APPROVED PLANS. AFTER RECEIVING THIS LETTER, A FINAL INSPECTION WILL BE SCHEDULED BY THE CITY INSPECTOR.
14. AFTER A FINAL INSPECTION HAS BEEN CONDUCTED BY THE CITY INSPECTOR AND WITH APPROVAL FROM THE CITY INSPECTOR, REMOVE THE TEMPORARY EROSION AND SEDIMENTATION CONTROLS AND COMPLETE ANY NECESSARY FINAL REVEGETATION RESULTING FROM REMOVAL OF THE CONTROLS. CONDUCT ANY MAINTENANCE AND REHABILITATION OF THE WATER QUALITY PONDS OR CONTROLS.

TEXAS COMMISSION ON ENVIRONMENTAL QUALITY

GENERAL CONSTRUCTION NOTES

EDWARDS AQUIFER PROTECTION PROGRAM CONSTRUCTION NOTES - LEGAL DISCLAIMER
THE FOLLOWING LISTED "CONSTRUCTION NOTES" ARE INTENDED TO BE ADVISORY IN NATURE ONLY AND DO NOT CONSTITUTE AN APPROVAL OR CONDITIONAL APPROVAL BY THE EXECUTIVE DIRECTOR (ED), NOR DO THEY CONSTITUTE A COMPREHENSIVE LISTING OF RULES OR CONDITIONS TO BE FOLLOWED DURING CONSTRUCTION. FURTHER ACTIONS MAY BE REQUIRED TO ACHIEVE COMPLIANCE WITH TCEQ REGULATIONS FOUND IN TITLE 30, TEXAS ADMINISTRATIVE CODE (TAC), CHAPTERS 213 AND 217, AS WELL AS LOCAL ORDINANCES AND REGULATIONS PROVIDING FOR THE PROTECTION OF WATER QUALITY. ADDITIONALLY, NOTHING CONTAINED IN THE FOLLOWING LISTED "CONSTRUCTION NOTES" RESTRICTS THE POWERS OF THE ED, THE COMMISSION OR ANY OTHER GOVERNMENTAL ENTITY TO PREVENT, CORRECT, OR CURTAIL ACTIVITIES THAT RESULT OR MAY RESULT IN POLLUTION OF THE EDWARDS AQUIFER OR HYDROLOGICALLY CONNECTED SURFACE WATERS. THE HOLDER OF ANY EDWARDS AQUIFER PROTECTION PLAN CONTAINING "CONSTRUCTION NOTES" IS STILL RESPONSIBLE FOR COMPLIANCE WITH TITLE 30, TAC, CHAPTERS 213 OR ANY OTHER APPLICABLE TCEQ REGULATION, AS WELL AS ALL CONDITIONS OF AN EDWARDS AQUIFER PROTECTION PLAN THROUGH ALL PHASES OF PLAN IMPLEMENTATION. FAILURE TO COMPLY WITH ANY CONDITION OF THE ED'S APPROVAL, WHETHER OR NOT IN CONTRADICTION OF ANY "CONSTRUCTION NOTES," IS A VIOLATION OF TCEQ REGULATIONS AND ANY VIOLATION IS SUBJECT TO ADMINISTRATIVE RULES, ORDERS, AND PENALTIES AS PROVIDED UNDER TITLE 30, TAC 213.0 (RELATING TO ENFORCEMENT), WHICH VIOLATIONS MAY ALSO BE SUBJECT TO OTHER PENALTIES AND SANCTIONS UNDER THE FOLLOWING LISTED "CONSTRUCTION NOTES" IN NO WAY REPRESENT AN APPROVED EXCEPTION BY THE ED TO ANY PART OF TITLE 30 TAC, CHAPTERS 213 AND 217, OR ANY OTHER TCEQ APPLICABLE REGULATION.

- 1. A WRITTEN NOTICE OF CONSTRUCTION MUST BE SUBMITTED TO THE TCEQ REGIONAL OFFICE AT LEAST 48 HOURS PRIOR TO THE START OF ANY GROUND DISTURBANCE OR CONSTRUCTION ACTIVITIES. THIS NOTICE MUST INCLUDE:
- THE NAME OF THE APPROVED PROJECT;
- THE ACTIVITY START DATE; AND
- THE CONTACT INFORMATION OF THE PRIME CONTRACTOR.
2. ALL CONTRACTORS CONDUCTING REGULATED ACTIVITIES ASSOCIATED WITH THIS PROJECT SHOULD BE PROVIDED WITH COMPLETE COPIES OF THE APPROVED CONTRIBUTING ZONE PLAN (CZP) AND THE TCEQ LETTER INDICATING THE SPECIFIC CONDITIONS OF ITS APPROVAL. DURING THE COURSE OF THESE REGULATED ACTIVITIES, THE CONTRACTOR(S) SHOULD KEEP COPIES OF THE APPROVED PLAN AND APPROVAL LETTER ON-SITE.
3. NO HAZARDOUS SUBSTANCE STORAGE TANK SHALL BE INSTALLED WITHIN 150 FEET OF A WATER SUPPLY SOURCE, DISTRIBUTION SYSTEM, WELL, OR SENSITIVE FEATURE.
4. PRIOR TO BEGINNING ANY CONSTRUCTION ACTIVITY, ALL TEMPORARY EROSION AND SEDIMENTATION (E&S) CONTROL MEASURES MUST BE PROPERLY INSTALLED AND MAINTAINED IN ACCORDANCE WITH THE MANUFACTURERS SPECIFICATIONS. IF INSPECTIONS AND SUBSTANTIAL CONFORMANCE WITH THE APPROVED PLANS IS NOT MAINTAINED, THE APPLICANT MUST REPLACE OR MODIFY THE CONTROL FOR SITE SITUATIONS. THESE CONTROLS MUST REMAIN IN PLACE UNTIL THE DISTURBED AREAS HAVE BEEN PERMANENTLY STABILIZED.
5. ANY SEDIMENT THAT ESCAPES THE CONSTRUCTION SITE MUST BE COLLECTED AND PROPERLY DISPOSED OF BEFORE THE NEXT RAIN EVENT TO ENSURE IT IS NOT WASHED INTO SURFACE STREAMS, SENSITIVE FEATURES, ETC.
6. SEDIMENT MUST BE REMOVED FROM THE SEDIMENT TRAPS OR SEDIMENTATION BASINS WHEN IT OCCUPIES 50% OF THE BASIN'S DESIGN CAPACITY.
7. LITTER, CONSTRUCTION DEBRIS, AND CONSTRUCTION CHEMICALS EXPOSED TO STORMWATER SHALL BE PREVENTED FROM BEING DISCHARGED OFF-SITE.
8. ALL EXCAVATED MATERIAL THAT WILL BE STORED ON-SITE MUST HAVE PROPER E&S CONTROLS.
9. IF PORTIONS OF THE SITE WILL HAVE A CEASE IN CONSTRUCTION ACTIVITY LASTING LONGER THAN 14 DAYS, SOIL TCEQ-0592A (REV. JULY 15, 2015) PAGE 2 OF 2 STABILIZATION IN THOSE AREAS SHALL BE INITIATED AS SOON AS POSSIBLE PRIOR TO THE 14TH DAY OF INACTIVITY. IF ACTIVITY WILL RESUME PRIOR TO THE 21ST DAY, STABILIZATION MEASURES ARE NOT REQUIRED. IF DROUGHT CONDITIONS PREVENT WEATHER PREVENT ACTION BY THE 14TH DAY, STABILIZATION MEASURES SHALL BE INITIATED AS SOON AS POSSIBLE.
10. THE FOLLOWING RECORDS SHOULD BE MAINTAINED AND MADE AVAILABLE TO THE TCEQ UPON REQUEST:
- THE DATES WHEN MAJOR GRADING ACTIVITIES OCCUR.
- THE DATES WHEN CONSTRUCTION ACTIVITIES TEMPORARILY OR PERMANENTLY CEASE ON A PORTION OF THE SITE; AND
- THE DATES WHEN STABILIZATION MEASURES ARE INITIATED.
11. THE HOLDER OF ANY APPROVED CZP MUST NOTIFY THE APPROPRIATE REGIONAL OFFICE IN WRITING AND OBTAIN APPROVAL FROM THE EXECUTIVE DIRECTOR PRIOR TO INITIATING ANY OF THE FOLLOWING:
A. ANY PHYSICAL OR OPERATIONAL MODIFICATION OF ANY BEST MANAGEMENT PRACTICES (BMPs) OR STRUCTURE(S), INCLUDING BUT NOT LIMITED TO TEMPORARY OR PERMANENT PONDS, DAMS, BERMS, SILT FENCES, AND DIVERSIONARY STRUCTURES;
B. ANY CHANGE IN THE NATURE OR CHARACTER OF THE REGULATED ACTIVITY FROM THAT WHICH WAS ORIGINALLY APPROVED;
C. ANY CHANGE THAT WOULD SIGNIFICANTLY IMPACT THE POTENTIAL TO PREVENT POLLUTION OF THE EDWARDS AQUIFER; OR
D. ANY DEVELOPMENT OF LAND PREVIOUSLY IDENTIFIED AS UNDEVELOPED IN THE APPROVED CONTRIBUTING ZONE PLAN.

AUSTIN REGIONAL OFFICE
12100 PARK 35 CIRCLE, BUILDING A
AUSTIN, TEXAS 78755-1898
PHONE (512) 339-2929
FAX (512) 339-3795



Cabinet T Slide 87

Doc# 2000063914


SHORT FORM FINAL PLAT OF BUTTERCUP CREEK INDUSTRIAL PARK, RESUBDIVISION OF LOT 5

A PORTION OF LOT FIVE (5), BUTTERCUP CREEK INDUSTRIAL PARK, A SUBDIVISION IN WILLIAMSON COUNTY, TEXAS, AS RECORDED IN CABINET E, SLIDES 333, OF THE WILLIAMSON COUNTY PLAT RECORDS, SAVE AND EXCEPT THAT TRACT DESCRIBED AS 2.26 ACRES IN VOLUME 1846, PAGE 354 OF THE OFFICIAL RECORDS WILLIAMSON COUNTY.

OWNER: C.P. 3.475 PARTNERSHIP
1717 WEST 6TH STREET
SUITE 295
AUSTIN, TEXAS 78703
(512) 259-9000
(512) 259-9400 (FAX)

TOTAL ACREAGE: 3.47 ACRES
NO. OF LOTS: 1
AREA OF SMALLEST LOT: 3.47 ACRES
PROPOSED USE: COMMERCIAL

SURVEY & ABSTRACT NO.: RICHARD DUTY SURVEY, A-183
SUBJECT TO:
(1) RESTRICTIVE COVENANTS - E/333, 1155/893, 1155/917
(2) BLANKET ESMT PEDERNALES ELECTRIC CO-OP, INC. - 1521/666
(3) PIPE LINE ESMT ENSEARCH CORP. - 845/167



PERIMETER FIELD NOTES

ALL THAT CERTAIN TRACT OR PARCEL OF LAND SITUATED IN WILLIAMSON COUNTY, TEXAS, OUT OF THE RICHARD DUTY SURVEY, ABSTRACT NO. 183 AND ALSO KNOWN AS BUTTERCUP CREEK INDUSTRIAL PARK LOT 5, A SUBDIVISION RECORDED IN CABINET E, SLIDES 333-334, SAVE AND EXCEPT THAT TRACT DESCRIBED AS 2.26 ACRES IN A SUBSTITUTE TRUSTEE'S DEED, DATED DECEMBER 5, 1989 AND RECORDED IN VOLUME 1846, PAGE 354, OFFICIAL RECORDS WILLIAMSON COUNTY AND FURTHER DESCRIBED BY METES AND BOUNDS:

BEGINNING AT AN IRON PIN FOUND IN THE NORTH MARGIN OF CYPRESS CREEK ROAD AND ALSO KNOWN AS COUNTY ROAD 182, FOR THE SOUTHEAST CORNER OF SAID BUTTERCUP CREEK INDUSTRIAL PARK LOT 5 AND THIS TRACT, THE SOUTHEAST CORNER OF SAID RICHARD DUTY SURVEY BEARS APPROXIMATELY S 23°45' E 5170 FEET;

THENCE: WITH THE NORTH MARGIN OF SAID CYPRESS CREEK ROAD AND THE SOUTH LINE OF SAID BUTTERCUP CREEK INDUSTRIAL PARK LOT 5, 104.64 FEET ALONG A CURVE TO THE RIGHT (D= 5°13'19", R= 1148.11 FEET, LC BEARS S 60°40'04" W 104.60 FEET) TO A 1/2" IRON PIN FOUND AND S 63°17'23" W 110.46 FEET TO A COTTON SPINDLE FOUND FOR THE SOUTHWEST CORNER OF THIS TRACT;


THENCE: ACROSS SAID BUTTERCUP CREEK INDUSTRIAL PARK LOT 5, N 27°27'54" W 217.91 FEET TO AN IRON PIN FOUND AND N 47°23'58" W 250.93 FEET TO AN IRON PIN FOUND IN THE NORTH LINE OF BUTTERCUP CREEK INDUSTRIAL PARK LOT 5 FOR THE NORTHWEST CORNER OF THIS TRACT;

THENCE: N 41°37'35" E 420.47 FEET WITH THE NORTH LINE OF SAID BUTTERCUP CREEK INDUSTRIAL PARK LOT 5 TO A 1/2" IRON PIN FOUND FOR THE NORTHEAST CORNER OF THIS TRACT;

THENCE: S 18°45'11" E 608.94 FEET WITH THE EAST LINE OF SAID BUTTERCUP CREEK INDUSTRIAL PARK LOT 5 TO THE POINT OF BEGINNING AND CONTAINING 3.47 ACRES OF LAND.

BEARINGS CITED HEREON ARE BASED ON THE WEST LINE OF BUTTERCUP CREEK INDUSTRIAL PARK LOT 5, AS RECORDED IN CABINET E, SLIDES 333-334.

1. THIS TRACT IS NOT LOCATED WITHIN THE EDWARDS AQUIFER RECHARGE ZONE.
2. WATER SERVICE AND WASTE WATER SERVICE PROVIDED BY THE CITY OF CEDAR PARK.
3. NO LOT IN THIS SUBDIVISION IS ENCLOSED BY ANY SPECIAL FLOOD HAZARD AREA INUNDATED BY 100 YEAR FLOOD AS IDENTIFIED BY THE U. S. FEDERAL EMERGENCY MANAGEMENT AGENCY BOUNDARY MAPS, (FLOOD INSURANCE RATE MAP), COMMUNITY-PANEL NUMBERS 48491C0306 C AND 48491C0308 C, EFFECTIVE DATES, SEPTEMBER 27, 1991.
4. A TEN (10) FOOT P.U.E. IS HEREBY DEDICATED ADJACENT TO ALL STREET R.O.W. ON ALL LOTS. A FIVE (5) FOOT P.U.E. IS HEREBY DEDICATED ALONG EACH SIDE LOT LINE FROM THE FRONT PROPERTY LINE TO THE FRONT BUILDING LINE. A SEVEN AND ONE HALF (7.5) FOOT P.U.E. IS HEREBY DEDICATED ADJACENT TO ALL REAR LOT LINES.
5. SETBACKS NOT SHOWN ON LOTS SHALL CONFORM TO THE CITY OF CEDAR PARK ZONING ORDINANCE.
6. OBSTRUCTIONS ARE PROHIBITED FROM DRAINAGE EASEMENTS.
7. SIDEWALKS SHALL BE INSTALLED ON THE SUBDIVISION SIDE OF CYPRESS CREEK ROAD. THOSE SIDEWALKS NOT ABUTTING A RESIDENTIAL, COMMERCIAL OR INDUSTRIAL LOT SHALL BE INSTALLED WHEN THE ADJOINING STREET IS CONSTRUCTED.
8. PRIOR TO CONSTRUCTION OF ANY IMPROVEMENTS ON LOTS IN THIS SUBDIVISION, BUILDING PERMITS WILL BE OBTAINED FROM THE CITY OF CEDAR PARK.
9. THIS TRACT IS CURRENTLY ZONED "B-2" BY THE CITY OF CEDAR PARK.
10. THIS SUBDIVISION SHALL COMPLY WITH THE CORRIDOR OVERLAY ORDINANCE OF THE CITY OF CEDAR PARK.
11. THIS PLAT DOES NOT REMOVE ANY COVENANTS OR RESTRICTIONS.
12. THIS SUBDIVISION WILL BE IN FULL COMPLIANCE WITH THE LANDSCAPE AND TREE ORNANCE OF THE CITY OF CEDAR PARK, TEXAS.
13. FIFTY PERCENT OF ALL TREES SUBMITTED IN THIS SUBDIVISION ARE REQUIRED TO BE RETAINED.
14. CONSTRUCTION PLANS AND SPECIFICATIONS FOR ALL SUBDIVISION IMPROVEMENTS SHALL BE REVIEWED AND APPROVED BY THE CITY OF CEDAR PARK PRIOR TO ANY CONSTRUCTION WITHIN THE SUBDIVISION.



SCALE: 1" = 100'

LEGEND:
 ● IRON PIN FOUND
 ○ 1/2" IRON PIN SET
 - - - ELECTRIC LINES

JOB NO: 9520-P
SHEET: 1 OF 2
PREPARED BY: [Signature]
DATE:

BUTTERCUP CREEK INDUSTRIAL PARK, RESUBDIVISION OF LOT 5
A PORTION OF LOT FIVE (5), BUTTERCUP CREEK INDUSTRIAL PARK, A SUBDIVISION IN WILLIAMSON COUNTY, TEXAS, AS RECORDED IN CABINET E, SLIDES 333, OF THE WILLIAMSON COUNTY PLAT RECORDS, SAVE AND EXCEPT THAT TRACT DESCRIBED AS 2.26 ACRES IN VOLUME 1846, PAGE 354 OF THE OFFICIAL RECORDS WILLIAMSON COUNTY.

CASTLEBERRY SURVEYING, INC.
203 SOUTH H-55, SUITE 101C
GEORGETOWN, TEXAS 78628
TELEPHONE: (512) 869-0850 FAX: (512) 930-8388

8834 N. Capital of Texas Hwy.
Suite 140
Austin, Texas 78759
(512) 452-0371
FAX: (512) 454-9933
TBP/ELS FIRM #2946

GRAY ENGINEERING

NO.	BY	DATE	REVISION DESCRIPTION

ATX PICKLEPLEX
SITE PLAN

FINAL PLAT (1 OF 2)

PROJECT NO: 1711-11671
DESIGNED BY: LL
DRAWN BY: JM
CHECKED BY: SS

NOTICE:
ALTERATION OF A SEALED DRAWING WITHOUT PROPER NOTIFICATION TO THE RESPONSIBLE ENGINEER IS A VIOLATION OF THE TEXAS ENGINEERING PRACTICE ACT.

STATE OF TEXAS
Sameer Saini
146542
LICENSED PROFESSIONAL ENGINEER

H:\PROJECTS\1711 - STUDIO ELES11671 ATX PICKLEPLEX SITE PLAN\CAD\SHETS\1671-FINAL PLAT.DWG DATE: 7/30/2024 8:02:49 PM BY: J.MARTINEZ

H:\PROJECTS\1711 - STUDIO ELES11671 ATX PICKLEPLEX SITE PLAN\CAD\SHEETS\1671-EXISTING CONDITIONS & DEMOLITION PLAN.DWG DATE: 7/30/2024 8:02:57 PM BY: JMARTINEZ



SCALE: 1"=30'
GRAPHIC SCALE IN FEET
0 15 30 45 60

LEGEND	
	PROPERTY BOUNDARY
	EXISTING CONTOUR
	EXISTING EASEMENT LINE
	EXISTING EDGE OF PAVEMENT
	EXISTING FIRE HYDRANT
	EXISTING OVERHEAD ELECTRIC
	EXISTING WASTEWATER LINE
	EXISTING WASTEWATER LINE
	EXISTING TREES
	EXISTING FENCE LINE
	EXISTING SIDEWALK TO BE REMOVED
	EXISTING CONCRETE DRIVE TO BE REMOVED
	EXISTING ASPHALT TO BE REMOVED
	EXISTING GRAVEL ROAD TO BE REMOVED

NOTES:
1. ALL UNDERGROUND UTILITIES SHOULD BE LOCATED PRIOR TO CONSTRUCTION.

8834 N. Capital of Texas Hwy.
Suite 140
Austin, Texas 78759
(512)452-0371
FAX(512)454-9933
TBPELS FIRM #2946

GRAY
ENGINEERING

NO.	BY	DATE	REVISION DESCRIPTION

ATX PICKLEPLEX
SITE PLAN


EXISTING CONDITIONS
& DEMOLITION PLAN

PROJECT NO: 1711-11671
DESIGNED BY: LL
DRAWN BY: JM
CHECKED BY: SS

NOTICE:
ALTERATION OF A SEALED DRAWING WITHOUT PROPER NOTIFICATION TO THE RESPONSIBLE ENGINEER IS A VIOLATION OF THE TEXAS ENGINEERING PRACTICE ACT.



H:\PROJECTS\1711 - STUDIO ELES11671 ATX PICKLEPLEX SITE PLAN\CAD\1711-PROPOSED GRADING PLAN.DWG DATE: 7/30/2024 8:03:11 PM BY: JMARTINEZ



SCALE: 1"=30'
GRAPHIC SCALE IN FEET
0 15 30 45 60

LEGEND	
	FIRE LINE STRIPING
	PROPERTY BOUNDARY
	EXISTING TREE
	EXISTING EASEMENT LINE
	EXISTING SIDEWALK
	EXISTING CURB AND GUTTER
	EXISTING WATER LINE
	EXISTING WASTEWATER LINE
	PROPOSED FIRE HYDRANT ASSEMBLY
	EXISTING FIRE HYDRANT ASSEMBLY
	PROPOSED GATE VALVE
	EXISTING WASTEWATER MANHOLE
	PAVEMENT STRIPING
	PROPOSED AREA INLET
X 0.00 HP	HIGH POINT
X 0.00 LP	LOW POINT
X 0.00 TP	TOP OF PAVEMENT
X 0.00 TW	TOP OF WALL
X 0.00 BW	BOTTOM OF WALL
X 0.00 FL	FLOW LINE
X 0.00 GB	GRADE BREAK
X 0.00 TG	TOP OF GRADE
X 0.00 RC	RIBBON CURB
X 0.00 EG	EXISTING GRADE

NOTES:
1. TG SPOT ELEVATIONS INSIDE OF POND IDENTIFY PROPOSED GRADING STARTING AT EXISTING GROUND

8834 N. Capital of Texas Hwy.
Suite 140
Austin, Texas 78759
(512)452-0371
FAX(512)454-9933
TBPELS FIRM #2946

GRAY
ENGINEERING

NO.	BY	DATE	REVISION DESCRIPTION

ATX PICKLEPLEX
SITE PLAN

PROPOSED GRADING
PLAN

PROJECT NO: 1711-11671
DESIGNED BY: LL
DRAWN BY: JM
CHECKED BY: SS

NOTICE:
ALTERATION OF A SEALED DRAWING WITHOUT PROPER NOTIFICATION TO THE RESPONSIBLE ENGINEER IS A VIOLATION OF THE TEXAS ENGINEERING PRACTICE ACT.



H:\PROJECTS\1711 - STUDIO ELES11671 ATX PICKLEPLEX SITE PLAN\CAD\SHEETS\11671-EXISTING DRAINAGE AREA.MXD DWG DATE: 7/30/2024 5:03:18 PM BY: JMARTINEZ



DRAINAGE LEGEND

- DA X-XX
X.XX
AC. DRAINAGE AREA
- DRAINAGE AREA BOUNDARY
- ➔ DIRECTION OF DRAINAGE FLOW
- XXX--- EXISTING MINOR CONTOUR
- XXX--- EXISTING MAJOR CONTOUR

NOTES:

- THE FLOW OFF THE SITE HAS NOT BEEN INCREASED FROM EXISTING CONDITIONS
- NO FLOODPLAIN IS LOCATED ON THIS PROPERTY

SUMMARY OF DRAINAGE FLOWS (DETAILED)

Point of Analysis	Existing Contributing Drainage Areas	Existing Runoff Values
POA 1	EX-1 OFFSITE-1	Q_{2yr} (cfs) = 7.36 Q_{10yr} (cfs) = 16.76 Q_{25yr} (cfs) = 22.64 Q_{100yr} (cfs) = 32.36
POA 2	EX-2	Q_{2yr} (cfs) = 1.30 Q_{10yr} (cfs) = 3.03 Q_{25yr} (cfs) = 4.12 Q_{100yr} (cfs) = 5.92
POA 3	EX-3	Q_{2yr} (cfs) = 1.02 Q_{10yr} (cfs) = 2.23 Q_{25yr} (cfs) = 2.97 Q_{100yr} (cfs) = 4.21

PEAK FLOW TABLE

POINT OF ANALYSIS	Drainage Area	Area (Acre)	Impervious (%)	Pervious (%)	Time of Concentration (min.)	2 Year				10 Year				25 Year				100 Year			
						Q (ft ³ /s)															
POA 1	EX-1	2.61	2%	98%	11.10	5.88	13.68	18.52	26.52												
POA 2	EX-2	0.51	0%	100%	7.12	1.30	3.03	4.12	5.92												
POA 3	EX-3	0.37	16%	84%	8.28	1.02	2.23	2.97	4.21												
POA 1	OFFSITE-1	0.54	24%	76%	7.91	1.59	3.34	4.42	6.22												
	Total	4.03	6.22%	93.78%																	

Drainage Area	Existing																Time of Concentration (min.)	
	Sheet Flow					Sheet Flow					Shallow Concentrated Flow							
	Surface Type	n	Length (ft)	Slope (%)	Tt (min.)	Surface Type	n	Length (ft)	Slope (%)	Tt (min.)	Unpaved		Paved		Total			
EX-1	Grass (Short-grass prairie)	0.15	81	4.0%	6.03	Gravel	0.03	19	2.9%	0.51	602	1.9%	4.56	56	5.1%	0.26	4.56	11.10
EX-2	Grass (Short-grass prairie)	0.15	100	4.4%	6.87												0.26	7.12
EX-3	Grass (Short-grass prairie)	0.15	61	4.5%	4.61	Gravel	0.03	39	0.2%	2.53	182	3.7%	0.98	61	1.1%	0.15	1.13	8.28
OFFSITE-1	Grass (Short-grass prairie)	0.15	36	2.1%	4.13	Gravel	0.03	64	2.2%	1.52	321	2.2%	2.26				2.26	7.91

8834 N. Capital of Texas Hwy.
Suite 140
Austin, Texas 78759
(512)452-0371
FAX (512)454-9933
TBPELS FIRM #2946

GRAY ENGINEERING

NO.	BY	DATE	REVISION DESCRIPTION

**ATX PICKLEPLEX
SITE PLAN**


**EXISTING DRAINAGE
AREA**

PROJECT NO: 1711-11671
DESIGNED BY: LL
DRAWN BY: JM
CHECKED BY: SS

NOTICE:
ALTERATION OF A SEALED DRAWING WITHOUT PROPER NOTIFICATION TO THE RESPONSIBLE ENGINEER IS A VIOLATION OF THE TEXAS ENGINEERING PRACTICE ACT.




H:\PROJECTS\1711 - STUDIO ELES11671 ATX PICKLEPLEX SITE PLAN\CAD\SHETS\1671-OVERALL WATER DISTRIBUTION PLAN.DWG DATE: 7/30/2024 5:03:34 PM BY: JMARTINEZ




BUTTERCUP CREEK INDUSTRIAL PARK, LOT 5 CAB. E, SLIDES 333-334 P.R.W.C.T.
 CALLED 2.26 ACRES 505 CYPRESS CREEK, LLC DDC. NO. 2022107109 D.P.R.W.C.T.

LOT 1, BLOCK A DENUCCI SUBDIVISION CAB. V, SLIDES 91-92 P.R.W.C.T.
 CYPRESS CREEK WEST GROUP, L.P. DDC. NO. 2006001859 D.P.R.W.C.T.



LEGEND	
	PROPERTY BOUNDARY
	EASEMENT LINE
	DRIVE CENTERLINE
	PROPOSED WATER LINE
	PROPOSED FIRE HYDRANT
	PROPOSED GATE VALVE
	PROPOSED PLUG
	FIRE DEPARTMENT CONNECTION
	PROPOSED WASTEWATER LINE
	PROPOSED WASTEWATER MANHOLE
	PROPOSED STORM SEWER LINE
	EXISTING WATER LINE
	EXISTING FIRE HYDRANT
	EXISTING GATE VALVE
	EXISTING PLUG
	EXISTING WASTEWATER LINE
	EXISTING WASTEWATER MANHOLE
	EXISTING STORM SEWER LINE

NOTES:
 1. ALL FIRE WATER LINES ARE REQUIRED TO HAVE AT LEAST 30\"/>



8834 N. Capital of Texas Hwy. Suite 140 Austin, Texas 78759 (512)452-0371 FAX(512)454-9933 TBP&LS FIRM #2946



NO.	DATE	REVISION DESCRIPTION



ATX PICKLEPLEX SITE PLAN

OVERALL WATER DISTRIBUTION PLAN

PROJECT NO: 1711-11671
 DESIGNED BY: LL
 DRAWN BY: JM
 CHECKED BY: SS

NOTICE:
 ALTERATION OF A SEALED DRAWING WITHOUT PROPER NOTIFICATION TO THE RESPONSIBLE ENGINEER IS A VIOLATION OF THE TEXAS ENGINEERING PRACTICE ACT.








LEGEND	
	PROPERTY BOUNDARY
	EXISTING CONTOUR
	PROPOSED CONTOUR
	EASEMENT LINE
	DRIVE CENTERLINE
	PROPOSED WASTEWATER LINE
	PROPOSED WASTEWATER MANHOLE
	PROPOSED PLUG
	WATER LINE CROSSING PROTECTION
	EXISTING WASTEWATER LINE
	EXISTING WASTEWATER MANHOLE
	PROPOSED WATER LINE
	EXISTING WATER LINE
	FIRE HYDRANT
	GATE VALVE
	PROPOSED STORM SEWER LINE
	INSPECTION PORTAL

- NOTES:**
1. AN "INSPECTION PORTAL" IS A SINGLE RISER "TWO-WAY" CLEANOUT, NOT A DOUBLE CLEANOUT (WHICH HAS TWO RISERS).
 2. THE INSPECTION PORTAL NEEDS TO BE AT LEAST FIVE FEET OFF OF THE BUILDING, NOT ON A CHANGE IN DIRECTION OF THE SEWER LINE, AND NOT ON THE EDGE OF A CURB, SIDEWALK OR OTHER HARDSCAPE.
 3. AN INSPECTION PORTAL LOCATED IN A TRAFFIC AREA WILL NEED TO HAVE AN APPROPRIATE TRAFFIC BEARING CAST IRON LID COVERING THE PVC THREADED CAP.

WWL-A

WWL-B

WWL-EX



NO.	BY	DATE	REVISION DESCRIPTION



ATX PICKLEPLEX
SITE PLAN

OVERALL
WASTEWATER PLAN

PROJECT NO: 1711-11671
DESIGNED BY: LL
DRAWN BY: JM
CHECKED BY: SS

NOTICE:
ALTERATION OF A SEALED
DRAWING WITHOUT PROPER
NOTIFICATION TO THE
RESPONSIBLE ENGINEER IS A
VIOLATION OF THE TEXAS
ENGINEERING PRACTICE ACT.





- NOTES (TCEQ RG348):
1. THE FILTER STRIP SHOULD EXTEND ALONG THE ENTIRE LENGTH OF THE CONTRIBUTING AREA AND THE SLOPE SHOULD NOT EXCEED 20%. THE MINIMUM DIMENSION OF THE FILTER STRIP (IN THE DIRECTION OF FLOW) SHOULD BE NO LESS THAN 15 FEET. THE MAXIMUM WIDTH (IN THE DIRECTION OF FLOW) OF THE CONTRIBUTING IMPERVIOUS AREA SHOULD NOT EXCEED 72 FEET. FOR ROADWAYS WITH A VEGETATED STRIP ALONG BOTH SIDES THE TOTAL WIDTH OF THE ROADWAY SHOULD NOT EXCEED 144 FEET (I.E., 72 FEET DRAINING TO EACH SIDE).
 2. THE MINIMUM VEGETATED COVER FOR ENGINEERED STRIPS IS 80%.
 3. THE AREA CONTRIBUTING RUNOFF TO A FILTER STRIP SHOULD BE RELATIVELY FLAT SO THAT THE RUNOFF IS DISTRIBUTED EVENLY TO THE VEGETATED AREA WITHOUT THE USE OF A LEVEL SPREADER.
 4. THE AREA TO BE USED FOR THE STRIP SHOULD BE FREE OF GULLIES OR RILLS THAT CAN CONCENTRATE OVERLAND FLOW (SCHUELER, 1987).
 5. THE TOP EDGE OF THE FILTER STRIP ALONG THE PAVEMENT WILL BE DESIGNED TO AVOID THE SITUATION WHERE RUNOFF WOULD TRAVEL ALONG THE TOP OF THE FILTER STRIP, RATHER THAN THROUGH IT.
 6. TOP EDGE OF THE FILTER STRIP SHOULD BE LEVEL, OTHERWISE RUNOFF WILL TEND TO FORM A CHANNEL IN THE LOW SPOT. A LEVEL SPREADER SHOULD NOT BE USED TO DISTRIBUTE RUNOFF TO AN ENGINEERED FILTER STRIP.
 7. FILTER STRIPS SHOULD BE LANDSCAPED AFTER OTHER PORTIONS OF THE PROJECT ARE COMPLETED.

8834 N. Capital of Texas Hwy.
Suite 140
Austin, Texas 78759
(512)452-0371
FAX(512)454-9933
TBPELS FIRM #2946

NO.	BY	DATE	REVISION DESCRIPTION

ATX PICKLEPLEX
SITE PLAN

PROPOSED POND
PLAN (1 OF 2)


PROJECT NO: 1711-11671
DESIGNED BY: LL
DRAWN BY: JM
CHECKED BY: SS

NOTICE:
ALTERATION OF A SEALED
DRAWING WITHOUT PROPER
NOTIFICATION TO THE
RESPONSIBLE ENGINEER IS A
VIOLATION OF THE TEXAS
ENGINEERING PRACTICE ACT.



Texas Commission on Environmental Quality	
TSS Removal Calculations 04-20-2009	Project Name: ATX Pickleplex Date Prepared: 7/23/2024
Additional information is provided for cells with a red triangle in the upper right corner. Place the cursor over the cell. Text shown in blue indicate location of instructions in the Technical Guidance Manual - RG-348. Characters shown in red are data entry fields. Characters shown in black (Bold) are calculated fields. Changes to these fields will remove the equations used in the spreadsheet.	
1. The Required Load Reduction for the total project:	Calculations from RG-348 Pages 3-27 to 3-30
Page 3-29 Equation 3.3: $L_M = 27.2(A_{IN} \times P)$	
where:	L_M TOTAL PROJECT = Required TSS removal resulting from the proposed development = 80% of increased A_{IN} = Net increase in impervious area for the project P = Average annual precipitation, inches
Site Data: Determine Required Load Removal Based on the Entire Project	
County =	Williamson
Total project area included in plan =	3.47 acres
Predevelopment impervious area within the limits of the plan =	0.00 acres
Total post-development impervious area within the limits of the plan =	2.48 acres
Total post-development impervious cover fraction =	0.71
P =	32 inches
L_M TOTAL PROJECT =	2159 lbs.
* The values entered in these fields should be for the total project area.	
Number of drainage basins / outfalls areas leaving the plan area =	2
2. Drainage Basin Parameters (This information should be provided for each basin):	
Drainage Basin/Outfall Area No. =	2
Total drainage basin/outfall area =	0.51 acres
Predevelopment impervious area within drainage basin/outfall area =	0.00 acres
Post-development impervious area within drainage basin/outfall area =	0.33 acres
Post-development impervious fraction within drainage basin/outfall area =	0.65
L_M THIS BASIN =	287 lbs.
3. Indicate the proposed BMP Code for this basin.	
Proposed BMP =	Vegetated Filter Strips
Removal efficiency =	85 percent

4. Calculate Maximum TSS Load Removed (L_R) for this Drainage Basin by the selected BMP Type.	
RG-348 Page 3-33 Equation 3.7: $L_R = (BMP \text{ efficiency}) \times P \times (A_I \times 34.6 + A_P \times 0.54)$	
where:	A_C = Total On-Site drainage area in the BMP catchment area A_I = Impervious area proposed in the BMP catchment area A_P = Pervious area remaining in the BMP catchment area L_R = TSS Load removed from this catchment area by the proposed BMP
A_C =	0.51 acres
A_I =	0.33 acres
A_P =	0.18 acres
L_R =	313 lbs.
5. Calculate Fraction of Annual Runoff to Treat the drainage basin / outfall area	
Desired L_M THIS BASIN =	307 lbs.
F =	0.98



ENGINEERED VEGETATED FILTER STRIP DETAIL (TYP.)
N.T.S.


H:\PROJECTS\1711 - STUDIO ELES11671 ATX PICKLEPLEX SITE PLAN\CADD\SHEETS\1671-PROPOSED POND PLAN\DWG DATE: 7/30/2024 8:04:01 PM BY: JMARTINEZ



TREE LIST

TREE SUMMARY		
DIAMETER INCHES		
TOTAL	PRESERVED	REMOVED
557	221	336

TREE NO.	COMMON NAME	SCIENTIFIC NAME	CAL. IN.	ACTION
10707	CEDAR ELM	Ulmus crassifolia	10	PRESERVE
10708	CEDAR ELM	Ulmus crassifolia	10	PRESERVE
10712	CEDAR ELM	Ulmus crassifolia	15	PRESERVE
10713	CEDAR ELM	Ulmus crassifolia	8	PRESERVE
10714	CEDAR ELM	Ulmus crassifolia	10	PRESERVE
10715	CEDAR ELM	Ulmus crassifolia	8	REMOVE
10717	CEDAR ELM	Ulmus crassifolia	12	PRESERVE
10718	CEDAR ELM	Ulmus crassifolia	9	PRESERVE
10719	CEDAR ELM	Ulmus crassifolia	10	PRESERVE
10720	CEDAR ELM	Ulmus crassifolia	8	PRESERVE
10721	LIME OAK	Quercus virginiana	15	PRESERVE
10723	LIME OAK	Quercus virginiana	9	PRESERVE
10724	CEDAR ELM	Ulmus crassifolia	9	REMOVE
10725	CEDAR ELM	Ulmus crassifolia	13	REMOVE
10726	CEDAR ELM	Ulmus crassifolia	8	REMOVE
10729	CEDAR ELM	Ulmus crassifolia	13	REMOVE
10730	CEDAR ELM	Ulmus crassifolia	10	REMOVE
10731	CEDAR ELM	Ulmus crassifolia	10	REMOVE
10732	CEDAR ELM	Ulmus crassifolia	9	REMOVE
10733	CEDAR ELM	Ulmus crassifolia	9	REMOVE
10734	CEDAR ELM	Ulmus crassifolia	9	REMOVE
10736	CEDAR ELM	Ulmus crassifolia	9	REMOVE
10738	CEDAR ELM	Ulmus crassifolia	12	PRESERVE
10739	CEDAR ELM	Ulmus crassifolia	8	PRESERVE
10740	CEDAR ELM	Ulmus crassifolia	8	REMOVE
10741	CEDAR ELM	Ulmus crassifolia	11	REMOVE
10743	CEDAR ELM	Ulmus crassifolia	10	REMOVE
417	CEDAR ELM	Ulmus crassifolia	7	REMOVE
418	CEDAR ELM	Ulmus crassifolia	9	REMOVE
419	CEDAR ELM	Ulmus crassifolia	7	REMOVE
420	CEDAR ELM	Ulmus crassifolia	8	REMOVE
421	CEDAR ELM	Ulmus crassifolia	7	REMOVE
422	CEDAR ELM	Ulmus crassifolia	7	REMOVE
423	CEDAR ELM	Ulmus crassifolia	8	PRESERVE
425	CEDAR ELM	Ulmus crassifolia	6	PRESERVE
427	CEDAR ELM	Ulmus crassifolia	7	PRESERVE
431	CEDAR ELM	Ulmus crassifolia	7	REMOVE



LEGEND	
	PROPERTY BOUNDARY
	EXISTING CONTOUR
	PROPOSED CONTOUR
	EASEMENT LINE
	LDC LIMITS OF CONSTRUCTION
	SF SILT FENCE
	LOC-SF LIMITS OF CONSTRUCTION & SILT FENCE
	STABILIZED CONSTRUCTION ENTRANCE
	PROPOSED CURB INLET PROTECTION
	EXISTING CURB INLET PROTECTION
	TEMPORARY ROCK BERM
	CONTRACTOR STAGING AREA
	CONCRETE WASHOUT PIT
	PROPOSED STORM SEWER LINE
	PROPOSED GRATE INLET
	EXISTING STORM SEWER LINE
	PROPOSED CURB INLET
	SILT FENCE J-HOOKS
	EXISTING TREE TO REMAIN
	EXISTING TREE TO REMOVE

- NOTES:**
- ALL DISTURBED AREAS SHALL BE RE-VEGETATED TO MEET THE REQUIREMENTS OF THE CITY OF CEDAR PARK'S ORDINANCES.
 - TOTAL DISTURBED AREA: 3.69 ACRES
 - ADDITIONAL EROSION CONTROL MEASURES MAY BE REQUIRED BY INSPECTOR AT TIME OF CONSTRUCTION.
 - CONTRACTOR SHALL PROVIDE THE FOLLOWING PRIOR TO SCHEDULING THE PRECONSTRUCTION MEETING: NOTICE OF INTENT APPROVED BY TCEQ TO THE CITY'S MSA COORDINATOR (DENNIS NEILSON), UPLOAD TCEQ NOI TO MGO, AND POST ON SITE WITH CGP AND SWPPP.
 - ANY DIRT, MUD, ROCKS, DEBRIS, ETC. THAT IS SPILLED, TRACKED, OR OTHERWISE DEPOSITED ON ANY EXISTING PAVED STREETS SHALL BE CLEANED IMMEDIATELY BY THE CONTRACTOR, AT THE CONTRACTOR'S EXPENSE.
 - STORM INLET SEDIMENT TRAPS PLACED IN PROPOSED INLETS ARE TO BE REMOVED AND REPLACED W/ TRI-DIKES AFTER ALL IMPROVEMENTS HAVE BEEN COMPLETED PRIOR TO THE SUBDIVISION ACCEPTANCE.
 - EXISTING EROSION CONTROLS TO BE MAINTAINED AND REMAIN THROUGHOUT CONSTRUCTION UNTIL VEGETATION ESTABLISHED TO A MINIMUM OF 70% OF DISTURBED CONTRIBUTING DRAINAGE AREA.
 - ALL HAUL OFF/SPOILS TAKEN OFFSITE WILL BE TAKEN TO A LOCATION THAT IS PROPERLY PERMITTED TO ACCEPT FILL. DOCUMENTATION OF SAID SITE'S PERMIT INFORMATION WILL NEED TO BE COLLECTED AND ADDED TO THE SW3P RECORD AT THAT TIME.
 - ON SITE SPOILS STAGED MORE THAN 24 HOURS SHALL BE NOTED ON THE SW3P AND PLACED ON LEVEL GROUND WITH APPROPRIATE EROSION CONTROL. AT A MINIMUM, SILT FENCE WILL BE REQUIRED ON THE DOWN GRADIENT SIDE AND WITH 20 FT. PERPENDICULAR ON BOTH ENDS.
 - TEMPORARY ROCK BERM IS TO BE REMOVED PRIOR TO FINAL INSPECTION.

8834 N. Capital of Texas Hwy.
Suite 140
Austin, Texas 78759
(512)452-0371
FAX(512)454-9933
TBPELS FIRM #2946

NO.	BY	DATE	REVISION DESCRIPTION

**ATX PICKLEPLEX
SITE PLAN**



**EROSION AND SEDIMENTATION
CONTROL PLAN**

PROJECT NO: 1711-11671
DESIGNED BY: LL
DRAWN BY: JM
CHECKED BY: SS

NOTICE:
ALTERATION OF A SEALED DRAWING WITHOUT PROPER NOTIFICATION TO THE RESPONSIBLE ENGINEER IS A VIOLATION OF THE TEXAS ENGINEERING PRACTICE ACT.



H:\PROJECTS\1711 - STUDIO ELEV\11671.66 DECELERATION PLAN APPLICATION\CAD\SHS11671.66-EROSION AND SEDIMENTATION CONTROL PLAN.DWG DATE: 7/30/2024 8:04:18 PM BY: JMARTINEZ



LEGEND	
---	PROPERTY BOUNDARY
- - - -	EXISTING CONTOUR
— 950 —	PROPOSED CONTOUR
- - - -	EASEMENT LINE
[Hatched Pattern]	HEAVY DUTY TRUCK PAVEMENT SECTION
[Diagonal Line Pattern]	PASSENGER VEHICLES PAVEMENT SECTION

Table 1: Recommended Pavement Section Thickness, Inches

Expected Traffic	Average Daily Truck Traffic	Flexible Pavement		Rigid Pavement	
		HMAC	CLB	JRPCC	CLB
Passenger Vehicles	1	2	10	6	-
Heavy Duty Trucks*	Up to 10	2	12	6	-

- Notes:**
- Abbreviations: HMAC - Hot Mixed Asphalt Concrete, CLB - Crushed Limestone Base, JRPCC - Jointed, Reinforced Portland Cement Concrete
 - *Heavy-duty truck parking, loading, unloading, and turning areas should use the rigid pavement option.
 - The pavement thicknesses above, once complete, will be capable of supporting a total vehicle live load of 80,000 pounds and meets the HS-20 (16 kips per wheel) load carrying capacity required.
 - Average Daily Truck Traffic excludes pickup and panel trucks.
 - Inadequate drainage of the pavement system will accelerate pavement distress and result in increased maintenance costs. Adequate drainage should be provided for the pavement system. Adequate drainage consists of a curb and gutter or a shoulder and bar ditch system.
 - These pavement thickness designs are intended to transfer the load from the anticipated traffic conditions. Deep seated soil swelling or settlement of fill materials may cause long wave surface roughness. The recommendations above are intended to reduce maintenance costs and increase the serviceable lifespan of the pavement system.

8834 N. Capital of Texas Hwy.
Suite 140
Austin, Texas 78759
(512)452-0371
FAX (512)454-9933
TBPBLS FIRM #2906

NO.	BY	DATE	REVISION DESCRIPTION

ATX PICKLEPLEX
DECELERATION LANE PLAN



PAVEMENT TYPE
THICKNESS PLAN

PROJECT NO: 1711-11671.66
DESIGNED BY: LL
DRAWN BY: JM
CHECKED BY: SS

NOTICE:
ALTERATION OF A SEALED
DRAWING WITHOUT PROPER
NOTIFICATION TO THE
RESPONSIBLE ENGINEER IS A
VIOLATION OF THE TEXAS
ENGINEERING PRACTICE ACT.



H:\PROJECTS\1711 - STUDIO ELEVS\11671.66 DECELERATION PLAN APPLICATION\CAD\SHETS\11671.66-GRADING PLAN.DWG DATE: 7/30/2024 8:04:25 PM BY: JMARTINEZ



LEGEND	
	PROPERTY BOUNDARY
	EXISTING CONTOUR
	PROPOSED CONTOUR
	EASEMENT LINE
	DRIVE CENTERLINE
	FLOW ARROW
	PROPOSED SIDEWALK
	EXISTING GROUND ELEVATION
	FINISHED FLOOR ELEVATION
	TOP OF PAVEMENT ELEVATION
	TOP OF GRADE ELEVATION
	BOTTOM OF WALL ELEVATION
	TOP OF WALL ELEVATION
	DRIVE CENTERLINE ELEVATION
	HIGH POINT ELEVATION
	LOW POINT ELEVATION
	FLOW LINE

NOTES:
 1. CONTRACTOR TO TRANSITION SLOPES OF CURB SECTIONS USING SMOOTH VERTICAL CURVES, AS NECESSARY.

8834 N. Capital of Texas Hwy.
 Suite 140
 Austin, Texas 78759
 (512) 452-0371
 FAX (512) 454-9833
 TBPELS FIRM #2946

GRAY
 ENGINEERING

NO.	BY	DATE	REVISION DESCRIPTION

ATX PICKLEPLEX
 DECELERATION LANE PLAN

GENERAL NOTES

PROJECT NO: 1711-11671.66
 DESIGNED BY: LL
 DRAWN BY: JM
 CHECKED BY: SS

NOTICE:
 ALTERATION OF A SEALED DRAWING WITHOUT PROPER NOTIFICATION TO THE RESPONSIBLE ENGINEER IS A VIOLATION OF THE TEXAS ENGINEERING PRACTICE ACT.




NO.	BY	DATE	REVISION DESCRIPTION

ATX PICKLEPLEX
 DECELERATION LANE PLAN


GENERAL NOTES

PROJECT NO: 1711-11671.66
 DESIGNED BY: LL
 DRAWN BY: JM
 CHECKED BY: SS

NOTICE:
 ALTERATION OF A SEALED
 DRAWING WITHOUT PROPER
 NOTIFICATION TO THE
 RESPONSIBLE ENGINEER IS A
 VIOLATION OF THE TEXAS
 ENGINEERING PRACTICE ACT.





CYPRESS CREEK ROAD
 EXISTING CROSS SECTION
 N.T.S.




CYPRESS CREEK ROAD
 PROPOSED DECELERATION LANE SECTION
 N.T.S.

NOTES:
 CONTRACTOR SHALL MATCH EXISTING BASE AND HMAC THICKNESSES
 AND TYPES IF DIFFERENT IN THE FIELD THAN IN THESE PLANS.



LEGEND	
	PROPERTY BOUNDARY
	EXISTING CONTOUR
	PROPOSED CONTOUR
	EASEMENT LINE
	PROPOSED STORM SEWER LINE
	PROPOSED CURB INLET
	PROPOSED STORM SEWER MANHOLE
	PROPOSED STORM SEWER HEADWALL
	PROPOSED WASTEWATER LINE
	PROPOSED WASTEWATER MANHOLE
	EXISTING WASTEWATER LINE
	EXISTING WASTEWATER MANHOLE
	PROPOSED WATER LINE
	EXISTING WATER LINE
	FIRE HYDRANT
	GATE VALVE

SDL-A



NO.	BY	DATE	REVISION DESCRIPTION

ATX PICKLEPLEX
DECELERATION LANE PLAN

#####



PROJECT NO: 1711-11671.66
DESIGNED BY: LL
DRAWN BY: JM
CHECKED BY: SS

NOTICE:
ALTERATION OF A SEALED
DRAWING WITHOUT PROPER
NOTIFICATION TO THE
RESPONSIBLE ENGINEER IS A
VIOLATION OF THE TEXAS
ENGINEERING PRACTICE ACT.



DISCLAIMER: The use of this standard is governed by the "Texas Engineering Practice Act". No warranty of any kind is made by TxDOT for any purpose whatsoever. TxDOT assumes no responsibility for the conversion of this standard to other formats or for incorrect results or damages resulting from its use.

DATE: FILE:



LEGEND

	Type 3 Barricade		Channelizing Devices
	Heavy Work Vehicle		Truck Mounted Attenuator (TMA)
	Trailer Mounted Flashing Arrow Board		Portable Changeable Message Sign (PCMS)
	Sign		Traffic Flow
	Flag		Flagger

Posted Speed *	Formula	Minimum Desirable Taper Lengths **			Suggested Maximum Spacing of Channelizing Devices		Minimum Sign Spacing "x" Distance	Suggested Longitudinal Buffer Space "B"	Stopping Sight Distance
		10' Offset	11' Offset	12' Offset	On a Taper	On a Tangent			
30	L = WS / 60	150'	165'	180'	30'	60'	120'	90'	200'
35		205'	225'	245'	35'	70'	160'	120'	250'
40		265'	295'	320'	40'	80'	240'	155'	305'
45	L = WS	450'	495'	540'	45'	90'	320'	195'	360'
50		500'	550'	600'	50'	100'	400'	240'	425'
55		550'	605'	660'	55'	110'	500'	295'	495'
60		600'	660'	720'	60'	120'	600'	350'	570'
65		650'	715'	780'	65'	130'	700'	410'	645'
70	700'	770'	840'	70'	140'	800'	475'	730'	
75	750'	825'	900'	75'	150'	900'	540'	820'	

* Conventional Roads Only
** Taper lengths have been rounded off.
L=Length of Taper(FT) W=Width of Offset(FT) S=Posted Speed(MPH)

TYPICAL USAGE

MOBILE	SHORT DURATION	SHORT TERM STATIONARY	INTERMEDIATE TERM STATIONARY	LONG TERM STATIONARY

- GENERAL NOTES
- Flags attached to signs where shown, are REQUIRED.
 - All traffic control devices illustrated are REQUIRED, except those denoted with the triangle symbol may be omitted when stated elsewhere in the plans, or for routine maintenance work, when approved by the Engineer.
 - The CW3-4 "BE PREPARED TO STOP" sign may be installed after the CW20-4 "ONE LANE ROAD XXX FT" sign, but proper sign spacing shall be maintained.
 - Flaggers should use two-way radios or other methods of communication to control traffic.
 - Length of work space should be based on the ability of flaggers to communicate.
 - A Shadow Vehicle with a TMA should be used anytime it can be positioned 30 to 100 feet in advance of the area of crew exposure without adversely affecting the performance or quality of the work. If workers are no longer present but road or work conditions require the traffic control to remain in place, Type 3 Barricades or other channelizing devices may be substituted for the Shadow Vehicle and TMA.
 - Additional Shadow Vehicles with TMAs may be positioned off the paved surface, next to those shown in order to protect a wider work space.
 - All lane closures shall occur only between the hours of 9 am and 4 pm. Any night time lane closures require approval by the director of engineering and shall occur between the hours of 8 pm and 6 am. Lane closures observed by city during the peak hours of 6 am to 9 am, or 4 pm to 8 pm will be subject to fine per chapter 1 of city ordinance, and/or subsequent issuance of work stoppage.
- TCP (2-2a)
- The R1-2 "YIELD" sign traffic control may be used on projects with approaches that have adequate sight distance. For projects in urban areas, work space should be no longer than one half city block. In rural areas, roadways with less than 2000 ADT, work space should be no longer than 400 feet.
 - The R1-2aP "YIELD TO ONCOMING TRAFFIC" sign shall be placed on a support at a 7 foot minimum mounting height.
- TCP (2-2b)
- Channelizing devices on the center line may be omitted when a pilot car is leading traffic and approved by the Engineer.
 - If the work space is located near a horizontal or vertical curve, the buffer distances should be increased in order to maintain stopping sight distance to the flagger and a queue of stopped vehicles. (See table above).
 - Flaggers should use 24" STOP/SLOW paddles to control traffic. Flags should be limited to emergency situations.

Texas Department of Transportation
Traffic Operations Division Standard

TRAFFIC CONTROL PLAN
ONE-LANE TWO-WAY
TRAFFIC CONTROL

TCP(2-2)-18

FILE: tcp2-2-18.dgn	DN:	CK:	DW:	CK:
©TxDOT December 1985	CONT	SECT	JOB	HIGHWAY
REVISIONS		DIST	COUNTY	SHEET NO.
8-95 3-03				
1-97 2-12				
4-98 2-18				
162				

8834 N. Capital of Texas Hwy. Suite 140 Austin, Texas 78759 (512)452-0371 FAX(512)454-9833 TBP&L FIRM #2946

GRAY ENGINEERING

ATX PICKLEPLEX DECELERATION LANE PLAN

STANDARD DETAILS

PROJECT NO: 1711-11671.66

DESIGNED BY: LL

DRAWN BY: JM

CHECKED BY: SS


NOTICE: ALTERATION OF A SEALED DRAWING WITHOUT PROPER NOTIFICATION TO THE RESPONSIBLE ENGINEER IS A VIOLATION OF THE TEXAS ENGINEERING PRACTICE ACT.

STATE OF TEXAS
Sameer Saini
146542
LICENSED PROFESSIONAL ENGINEER

07/31/2024 SHEET 23 OF #



H:\PROJECTS\1711 - STUDIO ELES11671-ATX PICKLEPLEX SITE PLAN\CAD SHEETS\11671-FIRE ACCESS PLAN.DWG DATE: 7/30/2024 6:04:56 PM BY: JMARTINEZ

- Emergency Responder Radio Coverage (ERCC) is a critical component of all site development and building construction and must be contemplated early in the development process. ERCC is required for all new and existing buildings.
 - Testing for ERCC is the responsibility of the building owner or representative.
 - Testing must be in compliance with 2021 IFC Section 510.
 - Testing is required for:
 - Buildings with any sub-grade floor, including parking.
 - Any building over 50,000 square feet.
 - Any building more than 3 stories above grade plane.
 - Any multi-story tilt wall building.
 - Any building where loss of signal strength becomes evident.
 - Exception: 1- and 2-family dwellings and townhomes.
 - Testing must be completed after the building has the interior walls, exterior walls, elevator shafts, stair shafts, and roof completed, and remediation, if necessary, must be complete prior to issuance of a Certificate of Occupancy.
 - Remediation must be in compliance with 2021 IFC Section 510.
 - Exception: Plans may state that testing and remediation will be in accordance with 2021 IFC Section 510, however a combination of the two codes will not be allowed. Testing and remediation must both be in accordance with the same standard.
- Fire Apparatus Access Roads (Fire Lanes)
 - Must comply with 2021 International Fire Code (IFC) Chapter 5 and Appendices B through L.1 and N, and City of Cedar Park Code of Ordinances Section 5.01 (fire code amendments).
 - Must be constructed of asphalt or concrete to support an imposed vehicle load of 90,000 pounds.
 - Grass pavers and other alternative materials are not allowed.
 - Must provide access to within 150 feet of all portions of the exterior of the building.
 - Access allowance is extended to 175 feet for a fully-sprinkled building.
 - Must have an unobstructed width of not less than 20 feet, except that at least 26 feet shall be required where hydrants are required along the fire lane or dead-end distances reach 500 feet or greater, or where required by other departments for mobility purposes.
 - Must have a minimum inside turning radius of 25 feet, and a minimum outside turning radius of 50 feet.
 - The minimum radii must be carried throughout the turning movement, from and to all required fire lanes. Example: a fire lane that turns 180-degrees must have a median depth of at least 50 feet.
 - Must not have a dead-end of more than 150 feet without an approved turn-around at the dead-end.
 - Drawings for approved turn-arounds may be found in the 2021 IFC, Appendix D as amended.
 - Must be 26 feet wide if the dead end is 500 feet or longer.
 - Must have enlarged radii, per illustration.
 - 150-500-foot dead end requires 96-foot diameter cul-de-sac, 120-foot hammerhead, or the alternative to the hammerhead.
 - 501-750-foot dead end requires 96-foot diameter cul-de-sac
 - 751-1000-foot dead end requires 108-foot diameter cul-de-sac
 - Dead-ends over 1000 feet not allowed.
 - Shall not exceed a grade of more than 10% along any section of fire lane.
 - Shall not exceed an algebraic difference of more than 8% along the angles of approach and departure, measured on a rolling 50-stretch of fire lane. This includes transitions across sidewalks and cross-connecting streets, drives, and fire lanes.
 - Must be marked with red traffic paint or dye along both sides of the fire lane in a continuous stripe a minimum of 4 inches wide.
 - Stripe must use the curb face where available, and must continue along the pavement where no curb face is present.
 - Must stencil FIRE LANE TOW AWAY ZONE in white letters a minimum of 3 inches high, no further than 35 feet between stencils. Place on curb face where available.
- Fire Lanes During Construction
 - All fire lanes shown on the Fire Protection sheet must be in place prior to the onset of vertical construction, and prior to the delivery of any combustible materials to the site.
 - Compacted base may be used as fire apparatus access road during construction if approved by the Fire Prevention Division.
 - Permission must be granted in writing.
 - A compaction report shall be submitted by a third-party group prior to vertical construction and at any time throughout the construction process when deemed necessary by the Fire Prevention Division. Report must show 100% of optimal density throughout the fire lane, measured every 50 feet.
 - Failure to maintain compacted base may result in a halt in construction until access is restored according to these standards.
 - Even with compacted base, ALL CONCRETE DRIVEWAY APPROACHES MUST BE INSTALLED.
 - Temporary fire lanes must still be identified as fire lanes – method to be approved by the Fire Prevention Division.
 - Fire lanes must be maintained throughout the construction process, and must be kept clear at all time. Blocking the fire lane with construction equipment or materials is not permitted.
- Fire Protection During Construction
 - In addition to the fire lane, all fire hydrants need to be installed, tested, and functional prior to the onset of vertical construction, and prior to the delivery of combustible materials.
 - No burning of materials on site allowed.
 - No smoking allowed inside any building under construction, nor within 10 feet of combustible construction. Site supervisor shall designate smoking areas away from the building under construction.
 - Site and building shall be kept free of debris and waste materials.
 - Standpipe for fire protection, if required, shall be installed before a building under construction reaches 40 feet in height, and shall be extended per floor up to one floor below the highest progressed floor.
 - Buildings shall not be occupied, nor shall any combustible items not related to the construction process be brought into the building prior to acceptance of all required fire protection systems.
 - All construction vehicles and those driven by the contractors and their sub-contractors shall be maintained on the lot that is under construction.
 - Buildings under construction shall have portable fire extinguishers:
 - At each stairway on all floor levels.
 - In every storage and construction shed.
 - Anywhere a special hazard exists, such as flammable liquid storage or use.
- Fire Hydrants
 - Fire hydrants shall be installed in accordance with 2021 IFC Chapter 5 and Appendices B and C, including all footnotes in Table C102.1.
 - Any hydrant used to serve the fire flow for a building must be within 400 feet of the building, and must be positioned along a fire lane.
 - Hydrants shall be installed at least 3 feet from back of curb on the fire lane, but not more than 6 feet.
 - Hydrants shall be installed such that the center of the 5" cap measures at least 18 inches from finished grade, but not more than 24 inches.
 - Hydrants are required within 100 feet of a fire department connection or standpipe system, measured as the hose would lay along the fire lane. This hydrant shall not substitute for the hydrant(s) required by section 507.5.1.
 - The 5" cap must face the fire lane.
- Approved Fire Apparatus Turn-arounds
 - Drawings for approved turn-arounds may be found in the 2021 IFC, Appendix D as amended.
 - 150-500-foot dead end requires 96-foot diameter cul-de-sac, 120-foot hammerhead, or the alternative to the hammerhead.
 - 501-750-foot dead end requires 96-foot diameter cul-de-sac
 - 751-1000-foot dead end requires 108-foot diameter cul-de-sac
 - Dead-ends over 1000 feet not allowed.



- NOTE:
- APPLICABLE CODE FOLLOWS 2021 IFC WITH LOCAL AMENDMENTS
 - "FIRE LANE TOW-AWAY ZONE" SHALL APPEAR IN FOUR INCH WHITE LETTERS AT THIRTY FIVE FT INTERVALS ON THE RED BORDER MARKINGS ALONG BOTH SIDES OF FIRE LANES. CURB FACING SHALL BE USED WHEN AVAILABLE. FIRE LANE STRIPING SHALL BE CONTINUOUS THROUGHOUT THE DESIGNATED FIRE LANE AND SHALL LAY DOWN ALONG BACKSIDE OF HEAD IN PARKING SPACES.

** THE CURB FACE MUST BE USED WHEN PRESENT; LAY DOWN STRIPING IS ONLY APPROPRIATE WHEN NO CURB EXISTS.



LEGEND	
	PROPERTY BOUNDARY
	EASEMENT LINE
	DRIVE CENTERLINE
	PROPOSED WATER LINE
	PROPOSED FIRE HYDRANT
	PROPOSED GATE VALVE
	PROPOSED PLUG
	FIRE DEPARTMENT CONNECTION
	PROPOSED WASTEWATER LINE
	PROPOSED WASTEWATER MANHOLE
	PROPOSED STORM SEWER LINE
	EXISTING WATER LINE
	EXISTING FIRE HYDRANT
	EXISTING GATE VALVE
	EXISTING PLUG
	EXISTING WASTEWATER LINE
	EXISTING WASTEWATER MANHOLE
	EXISTING STORM SEWER LINE

8834 N. Capital of Texas Hwy.
Suite 140
Austin, Texas 78759
(512)452-0371
FAX:(512)454-9933
TBPELS FIRM #2946

NO.	BY	DATE	REVISION DESCRIPTION



ATX PICKLEPLEX
SITE PLAN

FIRE ACCESS PLAN

PROJECT NO: 1711-11671
DESIGNED BY: LL
DRAWN BY: JM
CHECKED BY: SS

NOTICE:
ALTERATION OF A SEALED DRAWING WITHOUT PROPER NOTIFICATION TO THE RESPONSIBLE ENGINEER IS A VIOLATION OF THE TEXAS ENGINEERING PRACTICE ACT.





NO.	BY	DATE	REVISION DESCRIPTION

ATX PICKLEPLEX
SITE PLAN











SITE DETAILS (3 OF 3)

PROJECT NO: 1711-11671
DESIGNED BY: LL
DRAWN BY: JM
CHECKED BY: SS

NOTICE:
ALTERATION OF A SEALED DRAWING WITHOUT PROPER NOTIFICATION TO THE RESPONSIBLE ENGINEER IS A VIOLATION OF THE TEXAS ENGINEERING PRACTICE ACT.



H:\PROJECTS\1711 - STUDIO ELES11671 ATX PICKLEPLEX SITE PLAN\CAD\SHEDS\11671-EROSION AND SEDIMENTATION CONTROL DETAILS.DWG DATE: 7/30/2024 8:05:11 PM BY: JMARTINEZ



8834 N. Capital of Texas Hwy.
Suite 140
Austin, Texas 78759
(512) 452-0371
FAX: (512) 454-9933
TBPELS FIRM #2946

GRAY ENGINEERING

NO.	BY	DATE	REVISION DESCRIPTION

ATX PICKLEPLEX SITE PLAN

EROSION AND SEDIMENTATION CONTROL DETAILS

PROJECT NO: 1711-11671

DESIGNED BY: LL

DRAWN BY: JM

CHECKED BY: SS

NOTICE: ALTERATION OF A SEALED DRAWING WITHOUT PROPER NOTIFICATION TO THE RESPONSIBLE ENGINEER IS A VIOLATION OF THE TEXAS ENGINEERING PRACTICE ACT.

STATE OF TEXAS
Samuel Sain
146542
LICENSED PROFESSIONAL ENGINEER

07/31/2024

