



SPOONTS RANCH SUBDIVISION CONTRIBUTING ZONE PLAN

Submitted to:

**Texas Commission on Environmental Quality
Region 11 Field Office (Austin)
12100 Park 35 Circle, Bldg. A, Rm 179
Austin TX 78753**

Submitted by / Agent:

**Eli Engineering, PLLC
700 Theresa Cove
Cedar Park, TX 78613
Office: (512) 658-8095
Attn: Gary Eli Jones, P.E.**

Owner / Applicant:

**Bette Gene Spoonsts Estate
700 Theresa Cove
Cedar Park, TX 78613
Voice: 512-422-1972
Attn: Ms. Bonny Spoonsts Jones**



A handwritten signature in black ink, appearing to read "Gary Eli Jones".

1/13/2025

Texas Commission on Environmental Quality

Edwards Aquifer Application Cover Page

Our Review of Your Application

The Edwards Aquifer Program staff conducts an administrative and technical review of all applications. The turnaround time for administrative review can be up to 30 days as outlined in 30 TAC 213.4(e). Generally administrative completeness is determined during the intake meeting or within a few days of receipt. The turnaround time for technical review of an administratively complete Edwards Aquifer application is 90 days as outlined in 30 TAC 213.4(e). Please know that the review and approval time is directly impacted by the quality and completeness of the initial application that is received. In order to conduct a timely review, it is imperative that the information provided in an Edwards Aquifer application include final plans, be accurate, complete, and in compliance with [30 TAC 213](#).

Administrative Review

1. [Edwards Aquifer applications](#) must be deemed administratively complete before a technical review can begin. To be considered administratively complete, the application must contain completed forms and attachments, provide the requested information, and meet all the site plan requirements. The submitted application and plan sheets should be final plans. Please submit one full-size set of plan sheets with the original application, and half-size sets with the additional copies.

To ensure that all applicable documents are included in the application, the program has developed tools to guide you and web pages to provide all forms, checklists, and guidance. Please visit the below website for assistance: <http://www.tceq.texas.gov/field/eapp>.

2. This Edwards Aquifer Application Cover Page form (certified by the applicant or agent) must be included in the application and brought to the administrative review meeting.
3. Administrative reviews are scheduled with program staff who will conduct the review. Applicants or their authorized agent should call the appropriate regional office, according to the county in which the project is located, to schedule a review. The average meeting time is one hour.
4. In the meeting, the application is examined for administrative completeness. Deficiencies will be noted by staff and emailed or faxed to the applicant and authorized agent at the end of the meeting, or shortly after. Administrative deficiencies will cause the application to be deemed incomplete and returned.

An appointment should be made to resubmit the application. The application is re-examined to ensure all deficiencies are resolved. The application will only be deemed administratively complete when all administrative deficiencies are addressed.

5. If an application is received by mail, courier service, or otherwise submitted without a review meeting, the administrative review will be conducted within 30 days. The applicant and agent will be contacted with the results of the administrative review. If the application is found to be administratively incomplete, it can be retrieved from the regional office or returned by regular mail. If returned by mail, the regional office may require arrangements for return shipping.
6. If the geologic assessment was completed before October 1, 2004 and the site contains "possibly sensitive" features, the assessment must be updated in accordance with the *Instructions to Geologists* (TCEQ-0585 Instructions).

Technical Review

1. When an application is deemed administratively complete, the technical review period begins. The regional office will distribute copies of the application to the identified affected city, county, and groundwater conservation district whose jurisdiction includes the subject site. These entities and the public have 30 days to provide comments on the application to the regional office. All comments received are reviewed by TCEQ.
2. A site assessment is usually conducted as part of the technical review, to evaluate the geologic assessment and observe existing site conditions. The site must be accessible to our staff. The site boundaries should be

clearly marked, features identified in the geologic assessment should be flagged, roadways marked and the alignment of the Sewage Collection System and manholes should be staked at the time the application is submitted. If the site is not marked the application may be returned.

3. We evaluate the application for technical completeness and contact the applicant and agent via Notice of Deficiency (NOD) to request additional information and identify technical deficiencies. There are two deficiency response periods available to the applicant. There are 14 days to resolve deficiencies noted in the first NOD. If a second NOD is issued, there is an additional 14 days to resolve deficiencies. If the response to the second notice is not received, is incomplete or inadequate, or provides new information that is incomplete or inadequate, the application must be withdrawn or will be denied. Please note that because the technical review is underway, whether the application is withdrawn or denied the application fee will be forfeited.
4. The program has 90 calendar days to complete the technical review of the application. If the application is technically adequate, such that it complies with the Edwards Aquifer rules, and is protective of the Edwards Aquifer during and after construction, an approval letter will be issued. Construction or other regulated activity may not begin until an approval is issued.

Mid-Review Modifications

It is important to have final site plans prior to beginning the permitting process with TCEQ to avoid delays.

Occasionally, circumstances arise where you may have significant design and/or site plan changes after your Edwards Aquifer application has been deemed administratively complete by TCEQ. This is considered a "Mid-Review Modification". Mid-Review Modifications may require redistribution of an application that includes the proposed modifications for public comment.

If you are proposing a Mid-Review Modification, two options are available:

- If the technical review has begun your application can be denied/withdrawn, your fees will be forfeited, and the plan will have to be resubmitted.
- TCEQ can continue the technical review of the application as it was submitted, and a modification application can be submitted at a later time.

If the application is denied/withdrawn, the resubmitted application will be subject to the administrative and technical review processes and will be treated as a new application. The application will be redistributed to the affected jurisdictions.

Please contact the regional office if you have questions. If your project is located in Williamson, Travis, or Hays County, contact TCEQ's Austin Regional Office at 512-339-2929. If your project is in Comal, Bexar, Medina, Uvalde, or Kinney County, contact TCEQ's San Antonio Regional Office at 210-490-3096

Please fill out all required fields below and submit with your application.

1. Regulated Entity Name: Spoons Ranch				2. Regulated Entity No.:			
3. Customer Name: Bette Gene Spoons Estate				4. Customer No.:			
5. Project Type: (Please circle/check one)	<input checked="" type="radio"/> New	Modification		Extension		Exception	
6. Plan Type: (Please circle/check one)	WPAP	<input checked="" type="radio"/> CZP	SCS	UST	AST	EXP	EXT
7. Land Use: (Please circle/check one)	<input checked="" type="radio"/> Residential	Non-residential			8. Site (acres):		25.82 Ac
9. Application Fee:	\$4,000	10. Permanent BMP(s):			<20% Impervious Cover		
11. SCS (Linear Ft.):	N/A	12. AST/UST (No. Tanks):			N/A		
13. County:	Williamson	14. Watersheds:			North Fork San Gabriel		

Application Distribution

Instructions: Use the table below to determine the number of applications required. One original and one copy of the application, plus additional copies (as needed) for each affected incorporated city, county, and groundwater conservation district are required. Linear projects or large projects, which cross into multiple jurisdictions, can require additional copies. Refer to the "Texas Groundwater Conservation Districts within the EAPP Boundaries" map found at:

http://www.tceq.texas.gov/assets/public/compliance/field_ops/eapp/EAPP%20GWCD%20map.pdf

For more detailed boundaries, please contact the conservation district directly.

Austin Region			
County:	Hays	Travis	Williamson
Original (1 req.)	—	—	—
Region (1 req.)	—	—	—
County(ies)	—	—	—
Groundwater Conservation District(s)	<input type="checkbox"/> Edwards Aquifer Authority <input type="checkbox"/> Barton Springs/ Edwards Aquifer <input type="checkbox"/> Hays Trinity <input type="checkbox"/> Plum Creek	<input type="checkbox"/> Barton Springs/ Edwards Aquifer	NA
City(ies) Jurisdiction	<input type="checkbox"/> Austin <input type="checkbox"/> Buda <input type="checkbox"/> Dripping Springs <input type="checkbox"/> Kyle <input type="checkbox"/> Mountain City <input type="checkbox"/> San Marcos <input type="checkbox"/> Wimberley <input type="checkbox"/> Woodcreek	<input type="checkbox"/> Austin <input type="checkbox"/> Bee Cave <input type="checkbox"/> Pflugerville <input type="checkbox"/> Rollingwood <input type="checkbox"/> Round Rock <input type="checkbox"/> Sunset Valley <input type="checkbox"/> West Lake Hills	<input type="checkbox"/> Austin <input type="checkbox"/> Cedar Park <input type="checkbox"/> Florence <input type="checkbox"/> Georgetown <input type="checkbox"/> Jerrell <input type="checkbox"/> Leander <input type="checkbox"/> Liberty Hill <input type="checkbox"/> Pflugerville <input type="checkbox"/> Round Rock

San Antonio Region					
County:	Bexar	Comal	Kinney	Medina	Uvalde
Original (1 req.)	—	—	—	—	—
Region (1 req.)	—	—	—	—	—
County(ies)	—	—	—	—	—
Groundwater Conservation District(s)	<input type="checkbox"/> Edwards Aquifer Authority <input type="checkbox"/> Trinity-Glen Rose	<input type="checkbox"/> Edwards Aquifer Authority	<input type="checkbox"/> Kinney	<input type="checkbox"/> EAA <input type="checkbox"/> Medina	<input type="checkbox"/> EAA <input type="checkbox"/> Uvalde
City(ies) Jurisdiction	<input type="checkbox"/> Castle Hills <input type="checkbox"/> Fair Oaks Ranch <input type="checkbox"/> Helotes <input type="checkbox"/> Hill Country Village <input type="checkbox"/> Hollywood Park <input type="checkbox"/> San Antonio (SAWS) <input type="checkbox"/> Shavano Park	<input type="checkbox"/> Bulverde <input type="checkbox"/> Fair Oaks Ranch <input type="checkbox"/> Garden Ridge <input type="checkbox"/> New Braunfels <input type="checkbox"/> Schertz	NA	<input type="checkbox"/> San Antonio ETJ (SAWS)	NA

I certify that to the best of my knowledge, that the application is complete and accurate. This application is hereby submitted to TCEQ for administrative review and technical review.

Gary Eli Jones, P.E.

Print Name of Customer/Authorized Agent

Gary Eli Jones

11/29/2024

Signature of Customer/Authorized Agent

Date

****FOR TCEQ INTERNAL USE ONLY****

Date(s) Reviewed:		Date Administratively Complete:	
Received From:		Correct Number of Copies:	
Received By:		Distribution Date:	
EAPP File Number:		Complex:	
Admin. Review(s) (No.):		No. AR Rounds:	
Delinquent Fees (Y/N):		Review Time Spent:	
Lat./Long. Verified:		SOS Customer Verification:	
Agent Authorization Complete/Notarized (Y/N):		Fee Check:	Payable to TCEQ (Y/N):
Core Data Form Complete (Y/N):			Signed (Y/N):
Core Data Form Incomplete Nos.:			Less than 90 days old (Y/N):

Contributing Zone Plan Application

Texas Commission on Environmental Quality

for Regulated Activities on the Contributing Zone to the Edwards Aquifer and Relating to 30 TAC §213.24(1), Effective June 1, 1999

To ensure that the application is administratively complete, confirm that all fields in the form are complete, verify that all requested information is provided, consistently reference the same site and contact person in all forms in the application, and ensure forms are signed by the appropriate party.

Note: Including all the information requested in the form and attachments contributes to more streamlined technical reviews.

Signature

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. This Contributing Zone Plan Application is hereby submitted for TCEQ review and Executive Director approval. The application was prepared by:

Print Name of Customer/Agent: Gary Eli Jones, P.E.

Date: 11/29/2024

Signature of Customer/Agent:

Gary Eli Jones

Regulated Entity Name: Spoons Ranch

Project Information

1. County: Williamson
2. Stream Basin: N San Gabriel
3. Groundwater Conservation District (if applicable): N/A
4. Customer (Applicant):

Contact Person: Bonny Spoons Jones

Entity: Bette Gene Spoons Estate

Mailing Address: 700 Theresa Cove

City, State: Cedar Park, TX

Telephone: 512-422-1972

Email Address: jonesfamily.austin@gmail.com

Zip: 788613

Fax: N/A

5. Agent/Representative (If any):

Contact Person: Gary Eli Jones, P.E.

Entity: Eli Engineering, PLLC

Mailing Address: 700 Theresa Cove

City, State: Cedar Park, TX

Telephone: 512-658-8095

Email Address: gejtexas@gmail.com

Zip: 78613

Fax: N/A

6. Project Location:

- ☐ The project site is located inside the city limits of _____.
- ☐ The project site is located outside the city limits but inside the ETJ (extra-territorial jurisdiction) of _____.
- ☐ The project site is not located within any city's limits or ETJ.

7. ☒ The location of the project site is described below. Sufficient detail and clarity has been provided so that the TCEQ's Regional staff can easily locate the project and site boundaries for a field investigation.

496 Spoons Lane, Liberty Hill, TX 78642

8. ☒ Attachment A - Road Map. A road map showing directions to and the location of the project site is attached. The map clearly shows the boundary of the project site.

9. ☒ Attachment B - USGS Quadrangle Map. A copy of the official 7 ½ minute USGS Quadrangle Map (Scale: 1" = 2000") is attached. The map(s) clearly show:

- ☒ Project site boundaries.
- ☒ USGS Quadrangle Name(s).

10. ☒ Attachment C - Project Narrative. A detailed narrative description of the proposed project is attached. The project description is consistent throughout the application and contains, at a minimum, the following details:

- ☒ Area of the site
- ☒ Offsite areas
- ☒ Impervious cover
- ☒ Permanent BMP(s)
- ☒ Proposed site use
- ☒ Site history
- ☒ Previous development
- ☒ Area(s) to be demolished

11. Existing project site conditions are noted below:

- ☐ Existing commercial site
- ☐ Existing industrial site
- ☒ Existing residential site

- ☒ Existing paved and/or unpaved roads
- ☒ Undeveloped (Cleared)
- ☐ Undeveloped (Undisturbed/Not cleared)
- ☐ Other: _____

12. The type of project is:

- ☒ Residential: # of Lots: 11
- ☐ Residential: # of Living Unit Equivalents: _____
- ☐ Commercial
- ☐ Industrial
- ☐ Other: _____

13. Total project area (size of site): 25.82 Acres

Total disturbed area: 3.03 Acres

14. Estimated projected population: 11 Single Family homes

15. The amount and type of impervious cover expected after construction is complete is shown below:

Table 1 - Impervious Cover

<i>Impervious Cover of Proposed Project</i>	<i>Sq. Ft.</i>	<i>Sq. Ft./Acre</i>	<i>Acres</i>
Structures/Rooftops	77,000	÷ 43,560 =	1.77
Parking		÷ 43,560 =	
Other paved surfaces	44,720	÷ 43,560 =	1.03
Total Impervious Cover	121,720	÷ 43,560 =	2.80

Total Impervious Cover 2.80 ÷ Total Acreage 25.82 X 100 = 10.8% Impervious Cover

16. ☒ Attachment D - Factors Affecting Surface Water Quality. A detailed description of all factors that could affect surface water quality is attached. If applicable, this includes the location and description of any discharge associated with industrial activity other than construction.

17. ☒ Only inert materials as defined by 30 TAC 330.2 will be used as fill material.

For Road Projects Only

Complete questions 18 - 23 if this application is exclusively for a road project.

☒ N/A

18. Type of project:

- ☐ TXDOT road project.
- ☒ County road or roads built to county specifications.
- ☐ City thoroughfare or roads to be dedicated to a municipality.
- ☐ Street or road providing access to private driveways.

19. Type of pavement or road surface to be used:

- ☐ Concrete
- ☒ Asphaltic concrete pavement
- ☐ Other: _____

20. Right of Way (R.O.W.):

Length of R.O.W.: 1217 feet.

Width of R.O.W.: 60 feet.

$L \times W = 73,020 \text{ Ft}^2 \div 43,560 \text{ Ft}^2/\text{Acre} = 1.68$ acres.

21. Pavement Area:

Length of pavement area: 1217 feet.

Width of pavement area: 23 feet.

$L \times W = 27,991 \text{ Ft}^2 \div 43,560 \text{ Ft}^2/\text{Acre} = 0.64$ acres.

Pavement area 27,991 acres \div R.O.W. area 73,020 acres $\times 100 = 38\%$ impervious cover.

22. ☐ A rest stop will be included in this project.
- ☐ A rest stop will not be included in this project.
23. ☐ Maintenance and repair of existing roadways that do not require approval from the TCEQ Executive Director. Modifications to existing roadways such as widening roads/adding shoulders totaling more than one-half (1/2) the width of one (1) existing lane require prior approval from the TCEQ.

Stormwater to be generated by the Proposed Project

24. ☒ Attachment E - Volume and Character of Stormwater. A detailed description of the volume (quantity) and character (quality) of the stormwater runoff which is expected to occur from the proposed project is attached. The estimates of stormwater runoff quality and quantity are based on area and type of impervious cover. Include the runoff coefficient of the site for both pre-construction and post-construction conditions.

Wastewater to be generated by the Proposed Project

25. ☐ Wastewater is to be discharged in the contributing zone. Requirements under 30 TAC §213.6(c) relating to Wastewater Treatment and Disposal Systems have been satisfied.
- ☒ N/A

26. Wastewater will be disposed of by:

☒ On-Site Sewage Facility (OSSF/Septic Tank):

☒ Attachment F - Suitability Letter from Authorized Agent. An on-site sewage facility will be used to treat and dispose of the wastewater from this site. The appropriate licensing authority's (authorized agent) written approval is attached. It states that the land is suitable for the use of private sewage facilities and will meet or exceed the requirements for on-site sewage facilities as specified under 30 TAC Chapter 285 relating to On-site Sewage Facilities.

☒ Each lot in this project/development is at least one (1) acre (43,560 square feet) in size. The system will be designed by a licensed professional engineer or registered sanitarian and installed by a licensed installer in compliance with 30 TAC Chapter 285.

☐ Sewage Collection System (Sewer Lines):

The sewage collection system will convey the wastewater to the _____ (name) Treatment Plant. The treatment facility is:

☐ Existing.

☐ Proposed.

☐ N/A

Permanent Aboveground Storage Tanks (ASTs) \geq 500 Gallons

Complete questions 27 - 33 if this project includes the installation of AST(s) with volume(s) greater than or equal to 500 gallons.

☒ N/A

27. Tanks and substance stored:

Table 2 - Tanks and Substance Storage

<i>AST Number</i>	<i>Size (Gallons)</i>	<i>Substance to be Stored</i>	<i>Tank Material</i>
1			
2			
3			
4			
5			

Total x 1.5 = _____ Gallons

28. ☐ The AST will be placed within a containment structure that is sized to capture one and one-half (1 1/2) times the storage capacity of the system. For facilities with more than

one tank system, the containment structure is sized to capture one and one-half (1 1/2) times the cumulative storage capacity of all systems.

- ☐ Attachment G - Alternative Secondary Containment Methods. Alternative methods for providing secondary containment are proposed. Specifications showing equivalent protection for the Edwards Aquifer are attached.

29. Inside dimensions and capacity of containment structure(s):

Table 3 - Secondary Containment

<i>Length (L)(Ft.)</i>	<i>Width(W)(Ft.)</i>	<i>Height (H)(Ft.)</i>	<i>L x W x H = (Ft3)</i>	<i>Gallons</i>

Total: _____ Gallons

30. Piping:

- ☐ All piping, hoses, and dispensers will be located inside the containment structure.
- ☐ Some of the piping to dispensers or equipment will extend outside the containment structure.
- ☐ The piping will be aboveground
- ☐ The piping will be underground

31. ☐ The containment area must be constructed of and in a material impervious to the substance(s) being stored. The proposed containment structure will be constructed of: _____.

32. ☐ Attachment H - AST Containment Structure Drawings. A scaled drawing of the containment structure is attached that shows the following:

- ☐ Interior dimensions (length, width, depth and wall and floor thickness).
- ☐ Internal drainage to a point convenient for the collection of any spillage.
- ☐ Tanks clearly labeled
- ☐ Piping clearly labeled
- ☐ Dispenser clearly labeled

33. ☐ Any spills must be directed to a point convenient for collection and recovery. Spills from storage tank facilities must be removed from the controlled drainage area for disposal within 24 hours of the spill.

- ☐ In the event of a spill, any spillage will be removed from the containment structure within 24 hours of the spill and disposed of properly.

- ☐ In the event of a spill, any spillage will be drained from the containment structure through a drain and valve within 24 hours of the spill and disposed of properly. The drain and valve system are shown in detail on the scaled drawing.

Site Plan Requirements

Items 34 - 46 must be included on the Site Plan.

34. ☒ The Site Plan must have a minimum scale of 1" = 400'.
Site Plan Scale: 1" = 50'.
35. 100-year floodplain boundaries:
- ☐ Some part(s) of the project site is located within the 100-year floodplain. The floodplain is shown and labeled.
- ☒ No part of the project site is located within the 100-year floodplain.
The 100-year floodplain boundaries are based on the following specific (including date of material) sources(s): FEMA FIRM Map / Map Service Center / 48491C0240F Eff. 12/20/2019.
36. ☒ The layout of the development is shown with existing and finished contours at appropriate, but not greater than ten-foot contour intervals. Lots, recreation centers, buildings, roads, etc. are shown on the site plan.
- ☐ The layout of the development is shown with existing contours at appropriate, but not greater than ten-foot contour intervals. Finished topographic contours will not differ from the existing topographic configuration and are not shown. Lots, recreation centers, buildings, roads, etc. are shown on the site plan.
37. ☒ A drainage plan showing all paths of drainage from the site to surface streams.
38. ☒ The drainage patterns and approximate slopes anticipated after major grading activities.
39. ☒ Areas of soil disturbance and areas which will not be disturbed.
40. ☒ Locations of major structural and nonstructural controls. These are the temporary and permanent best management practices.
41. ☒ Locations where soil stabilization practices are expected to occur.
42. ☐ Surface waters (including wetlands).
☒ N/A
43. ☐ Locations where stormwater discharges to surface water.
☒ There will be no discharges to surface water.
44. ☐ Temporary aboveground storage tank facilities.
☒ Temporary aboveground storage tank facilities will not be located on this site.

45. ☐ Permanent aboveground storage tank facilities.
☒ Permanent aboveground storage tank facilities will not be located on this site.
46. ☒ Legal boundaries of the site are shown.

Permanent Best Management Practices (BMPs)

Practices and measures that will be used during and after construction is completed.

47. ☒ Permanent BMPs and measures must be implemented to control the discharge of pollution from regulated activities after the completion of construction.
☐ N/A
48. ☒ These practices and measures have been designed, and will be constructed, operated, and maintained to insure that 80% of the incremental increase in the annual mass loading of total suspended solids (TSS) from the site caused by the regulated activity is removed. These quantities have been calculated in accordance with technical guidance prepared or accepted by the executive director.
☒ The TCEQ Technical Guidance Manual (TGM) was used to design permanent BMPs and measures for this site.
☐ A technical guidance other than the TCEQ TGM was used to design permanent BMPs and measures for this site. The complete citation for the technical guidance that was used is: _____.
☐ N/A
49. ☒ Owners must insure that permanent BMPs and measures are constructed and function as designed. A Texas Licensed Professional Engineer must certify in writing that the permanent BMPs or measures were constructed as designed. The certification letter must be submitted to the appropriate regional office within 30 days of site completion.
☐ N/A
50. Where a site is used for low density single-family residential development and has 20 % or less impervious cover, other permanent BMPs are not required. This exemption from permanent BMPs must be recorded in the county deed records, with a notice that if the percent impervious cover increases above 20% or land use changes, the exemption for the whole site as described in the property boundaries required by 30 TAC §213.4(g) (relating to Application Processing and Approval), may no longer apply and the property owner must notify the appropriate regional office of these changes.
☒ The site will be used for low density single-family residential development and has 20% or less impervious cover.
☐ The site will be used for low density single-family residential development but has more than 20% impervious cover.
☐ The site will not be used for low density single-family residential development.

51. The executive director may waive the requirement for other permanent BMPs for multi-family residential developments, schools, or small business sites where 20% or less impervious cover is used at the site. This exemption from permanent BMPs must be recorded in the county deed records, with a notice that if the percent impervious cover increases above 20% or land use changes, the exemption for the whole site as described in the property boundaries required by 30 TAC §213.4(g) (relating to Application Processing and Approval), may no longer apply and the property owner must notify the appropriate regional office of these changes.
- ☐ Attachment I - 20% or Less Impervious Cover Waiver. The site will be used for multi-family residential developments, schools, or small business sites and has 20% or less impervious cover. A request to waive the requirements for other permanent BMPs and measures is attached.
 - ☐ The site will be used for multi-family residential developments, schools, or small business sites but has more than 20% impervious cover.
 - ☒ The site will not be used for multi-family residential developments, schools, or small business sites.
52. ☒ Attachment J - BMPs for Upgradient Stormwater.
- ☐ A description of the BMPs and measures that will be used to prevent pollution of surface water, groundwater, or stormwater that originates upgradient from the site and flows across the site is attached.
 - ☐ No surface water, groundwater or stormwater originates upgradient from the site and flows across the site, and an explanation is attached.
 - ☒ Permanent BMPs or measures are not required to prevent pollution of surface water, groundwater, or stormwater that originates upgradient from the site and flows across the site, and an explanation is attached.
53. ☒ Attachment K - BMPs for On-site Stormwater.
- ☐ A description of the BMPs and measures that will be used to prevent pollution of surface water or groundwater that originates on-site or flows off the site, including pollution caused by contaminated stormwater runoff from the site is attached.
 - ☒ Permanent BMPs or measures are not required to prevent pollution of surface water or groundwater that originates on-site or flows off the site, including pollution caused by contaminated stormwater runoff, and an explanation is attached.
54. ☐ Attachment L - BMPs for Surface Streams. A description of the BMPs and measures that prevent pollutants from entering surface streams is attached.
- ☒ N/A
55. ☒ Attachment M - Construction Plans. Construction plans and design calculations for the proposed permanent BMPs and measures have been prepared by or under the direct supervision of a Texas Licensed Professional Engineer, and are signed, sealed, and dated. Construction plans for the proposed permanent BMPs and measures are

attached and include: Design calculations, TCEQ Construction Notes, all proposed structural plans and specifications, and appropriate details.

☐ N/A

56. ☒ Attachment N - Inspection, Maintenance, Repair and Retrofit Plan. A site and BMP specific plan for the inspection, maintenance, repair, and, if necessary, retrofit of the permanent BMPs and measures is attached. The plan fulfills all of the following:

- ☒ Prepared and certified by the engineer designing the permanent BMPs and measures
- ☒ Signed by the owner or responsible party
- ☒ Outlines specific procedures for documenting inspections, maintenance, repairs, and, if necessary, retrofit.
- ☒ Contains a discussion of record keeping procedures

☐ N/A

57. ☐ Attachment O - Pilot-Scale Field Testing Plan. Pilot studies for BMPs that are not recognized by the Executive Director require prior approval from the TCEQ. A plan for pilot-scale field testing is attached.

☒ N/A

58. ☒ Attachment P - Measures for Minimizing Surface Stream Contamination. A description of the measures that will be used to avoid or minimize surface stream contamination and changes in the way in which water enters a stream as a result of the construction and development is attached. The measures address increased stream flashing, the creation of stronger flows and in-stream velocities, and other in-stream effects caused by the regulated activity, which increase erosion that result in water quality degradation.

☐ N/A

Responsibility for Maintenance of Permanent BMPs and Measures after Construction is Complete.

59. ☒ The applicant is responsible for maintaining the permanent BMPs after construction until such time as the maintenance obligation is either assumed in writing by another entity having ownership or control of the property (such as without limitation, an owner's association, a new property owner or lessee, a district, or municipality) or the ownership of the property is transferred to the entity. Such entity shall then be responsible for maintenance until another entity assumes such obligations in writing or ownership is transferred.
60. ☒ A copy of the transfer of responsibility must be filed with the executive director at the appropriate regional office within 30 days of the transfer if the site is for use as a multiple single-family residential development, a multi-family residential development,

or a non-residential development such as commercial, industrial, institutional, schools, and other sites where regulated activities occur.

Administrative Information

- 61. ☒ Submit one (1) original and one (1) copy of the application, plus additional copies as needed for each affected incorporated city, groundwater conservation district, and county in which the project will be located. The TCEQ will distribute the additional copies to these jurisdictions.
- 62. ☒ Any modification of this Contributing Zone Plan may require TCEQ review and Executive Director approval prior to construction, and may require submission of a revised application, with appropriate fees.
- 63. ☐ The site description, controls, maintenance, and inspection requirements for the storm water pollution prevention plan (SWPPP) developed under the EPA NPDES general permits for stormwater discharges have been submitted to fulfill paragraphs 30 TAC §213.24(1-5) of the technical report. All requirements of 30 TAC §213.24(1-5) have been met by the SWPPP document.
- ☒ The Temporary Stormwater Section (TCEQ-0602) is included with the application.




gejflexas@gmail.com

TBPELS FIRM No. 17877




ELI ENGINEERING, PLLC.
700 THERESA COVE, CEDAR PARK, TX 78613
512-658-8095



ATTACHMENT – A
ROAD MAP

SPOONTS RANCH

SHEET
1
OF 1



LIBERTY HILL (2013)
USGS QUAD MAP


0 1000 2000
SCALE: 1"=2000'

ATTACHMENT - B
USGS QUAD MAP

SPOONTS
RANCH

SHEET
1 OF 1





Firm # 17877

November 28, 2024

Texas Commission on Environmental Quality
Region 11 Field Office (Austin)
2800 S. IH 35, Suite 100
Austin, Texas 78704

**Re: Rio Ranch Subdivision
Contributing Zone Permit
Attachment C-Project Narrative**

To Whom It May Concern:

The application for the Contributing Zone Permit for this project located on County Road 282 outside the City limits of Liberty Hill, TX consists of 11 single family lots on a minimum of two (2) acres per lot. The property currently has one single family home on it that will be maintained. There is an existing gravel road that provides access to this property as well as neighbors next to the property. There is 25.82 acres on the property with a total of 10.8% impervious cover proposed summarized as follows:

<u>Description</u>	<u>Lots</u>	<u>Area (Ac)</u>
Single Family Lots (2 Ac Min)	11	25.82

Impervious cover for the entire project is summarized in the chart below.

<u>IMPERVIOUS COVER CALCULATIONS:</u>	
PROPOSED ROAD:	44,720 SF = 1.03 AC
PROPOSED LOTS:	11 x 7000 SF/LOT = 77,000 SF = 1.77 AC
TOTAL PROPERTY:	25.82 AC
TOTAL PROPOSED IC:	2.80 AC (10.8%)

RESIDENTIAL IC BASED ON TCEQ RG-348, TABLE 3-2

As a result of the proposed impervious cover being less than 20%, there are no permanent BMP's proposed for the project. In accordance with Williamson County Floodplain regulations, the site does not include detention due to all lots being 2 acres or larger. The project proposes to utilize sheet flow for as much of the project as possible. The road will have ribbon curb to provide a smooth transition from asphalt to natural ground. The single family lots will be served by well and septic per Williamson County. Construction plans for the proposed development that detail the proposed regulated activity are included with this submittal.

If you have any questions or need further assistance, please call me at 512-658-8095.

Sincerely,

A handwritten signature in dark ink, appearing to read "Gary Eli Jones", with a long horizontal flourish extending to the right.

Gary Eli Jones, P.E.
Authorized Agent



Firm # 17877

December 5, 2024

Texas Commission on Environmental Quality
Region 11 Field Office (Austin)
2800 S. IH 35, Suite 100
Austin, Texas 78704

**Re: Spoonts Ranch Subdivision
 Contributing Zone Permit
 Attachment D-Factors Affecting Surface Water Quality**


To Whom It May Concern:

The Spoonts Property is a rural property that will include two acre lots that will maintain sheet flow across the property. The proposed road that provides access to the property will be predominately built at existing elevations with ribbon curb to maintain the predominate drainage patterns that exist on the property. The low density development will be less than 20% impervious cover and 2 acre lots to which qualifies as a BMP. Temporary erosion control will be utilized during construction to minimize affects to the surface water quality.

If you have any questions or need further assistance, please call me at 512-658-8095.

Sincerely,

Gary Eli Jones, P.E.
Authorized Agent



Firm # 17877

December 5, 2024

Texas Commission on Environmental Quality
Region 11 Field Office (Austin)
2800 S. IH 35, Suite 100
Austin, Texas 78704

**Re: Spoonts Ranch Subdivision
Contributing Zone Permit
Attachment E-Volume and Character of Stormwater**

To Whom It May Concern:

The proposed development will maintain sheet flow for the proposed 11 two acre lots. Per TCEQ regulations the low density development will maintain practically the existing conditions and existing drainage patterns.

If you have any questions or need further assistance, please contact me at 512-658-8095.

Gary Eli Jones, P.E.
Authorized Agent

Williamson County - County Engineer's Office

3151 SE Inner Loop, Suite B
Georgetown, TX 78626
Telephone (512) 943-3330
Fax (512) 943-3335



Date: Wednesday, December 18, 2024

Bonny Jones
Bette Gene Foster Spoonts Estate
700 THERESA CV
Cedar Park, TX
78613
Jonesfamily.Austin@gmail.com

Permit Number OSSF-2024-511
Job Address: 496 SPOONTS LN, LIBERTY HILL, TX 78642

Bonny Jones,

The review for your project located at 496 SPOONTS LN, LIBERTY HILL, TX 78642 is complete. Additional information is needed for the items listed below. Comments from this review follow.

The following comments have been provided by Paul Walter. Should you have any questions or require additional information regarding any of these comments, please contact Paul Walter by telephone at (512) 943-3625 or by email at paul.walter@wilco.org.

1) OSSF Comments Approved

Please see the attached Ready for Signature comments-checklist for the OSSF review only. You can also view it in the portal.

Additional questions may be generated upon further review.

Should you have questions regarding specific comments, please contact the staff member referenced under the section in which the comment occurs. Should you have questions or require additional information regarding the plan review process itself, please feel free to contact the front counter at (512) 943-3330

If the comments provided indicate that a plan revision is required, please upload the revised plans through the online customer portal at www.mygovernmentonline.org in PDF format.

We appreciate your prompt attention to these matters.

Sincerely,

Paul Walter, OS0008032



Firm # 17877

December 5, 2024

Texas Commission on Environmental Quality
Region 11 Field Office (Austin)
2800 S. IH 35, Suite 100
Austin, Texas 78704


**Re: Spoonts Ranch Subdivision
Contributing Zone Permit
Attachment J-BMPs for Upgradient Stormwater**

To Whom It May Concern:

The drainage areas upstream of the developed areas will remain in their natural state.

If you have any questions or need further assistance, please contact me at 512-658-8095.

Gary Eli Jones, P.E.
Authorized Agent



Firm # 17877

December 5, 2024

Texas Commission on Environmental Quality
Region 11 Field Office (Austin)
2800 S. IH 35, Suite 100
Austin, Texas 78704

**Re: Spoonts Ranch Subdivision
Contributing Zone Permit
Attachment K-BMPs for On-site Stormwater**


To Whom It May Concern:

The proposed BMP for project is maintaining less than 20% impervious cover for the single family development. The proposed impervious cover for the subdivision is 2.8 acres on 25.82 acres or 10.8%.

If you have any questions or need further assistance, please contact me at 512-658-8095.

12/5/2024

Gary Eli Jones, P.E.
Authorized Agent



Firm # 17877

December 5, 2024

Texas Commission on Environmental Quality
Region 11 Field Office (Austin)
2800 S. IH 35, Suite 100
Austin, Texas 78704

**Re: Spoonts Ranch Subdivision
 Contributing Zone Permit
 Attachment M-Construction Plans**

To Whom It May Concern:

Construction plans and design calculations for the proposed subdivision have been prepared by or under the direct supervision of a Texas Licensed Professional Engineer, and are signed, sealed, and dated. Construction plans for the proposed subdivision are attached and include: TCEQ Construction Notes, all proposed structural plans and specifications, and appropriate details.

If you have any questions or need further assistance, please contact me at 512-658-8095.

Gary Eli Jones, P.E.
Authorized Agent

COUNTY ROAD 282
WILLIAMSON COUNTY, TEXAS

OUT OF THE JOHN P. KIMBALL SURVEY, ABSTRACT NO. 372, IN WILLIAMSON COUNTY, TEXAS, AND BEING A PORTION OF THE FOLLOWING TRACTS: THAT CERTAIN 23.22 ACRE TRACT CONVEYED TO TOM AND WIFE BETTE SPOONTS, BY DEED OF RECORD IN VOLUME 793, PAGE 740, OF THE DEED RECORDS OF WILLIAMSON COUNTY, TEXAS, AND THAT CERTAIN 16.00 ACRE TRACT CONVEYED TO TOM L. SPOONTS, BY DEED OF RECORD IN DOCUMENT NUMBER 1997058910, OF THE OFFICIAL PUBLIC RECORDS OF WILLIAMSON COUNTY, TEXAS.

Feb 02, 2025

GARY ELI JONES, P.E.

I, GARY ELI JONES, P.E. DO HEREBY CERTIFY THAT TO THE BEST OF MY KNOWLEDGE, THE PUBLIC WORKS AND DRAINAGE IMPROVEMENTS DESCRIBED HEREIN HAVE BEEN DESIGNED IN COMPLIANCE WITH THE SUBDIVISION AND BUILDING REGULATION ORDINANCES AND STORMWATER DRAINAGE POLICY ADOPTED BY THE CITY OF LIBERTY HILL & WILLIAMSON COUNTY, TEXAS

<p><u>ENGINEER AND AGENT</u> ELI ENGINEERING, P.L.L.C. 700 THERESA COVE CEDAR PARK, TEXAS 78613 CONTACT: GARY ELI JONES, P.E. 512-918-0819 F:512-532-0560 gelj@elias.com</p>	<p><u>WATER</u></p> <p>PRIVATE WELL PER LOT</p>
<p><u>OWNER</u></p> <p>BETTE SPOONTS ESTATE 700 THERESA COVE CEDAR PARK, TEXAS 78613 512-918-0819 jonesfamily.austin@gmail.com</p>	<p><u>WASTEWATER</u></p> <p>PRIVATE ON-SITE SEWAGE FACILITY PER LOT</p>
<p><u>SURVEYOR</u></p> <p>MANHARD CONSULTING 6448 EAST HWY 290, SUITE B-105 AUSTIN, TEXAS 78723 CONTACT: ABRAM C. DASHNER, R.P.L.S. 512-244-3395 adashner@manhard.com</p>	<p><u>TELEPHONE</u></p> <p>AT&T 208 SOUTH ACKARD STREET DALLAS, TEXAS 75202 889-333-6651 CONTACT: _____</p>
<p><u>ELECTRIC</u></p> <p>PEDERNALES ELECTRIC COOPERATIVE 10625 WEST STATE HWY 29 LIBERTY HILL, TEXAS 78642 512-778-5470</p>	<p><u>GAS SERVICE</u></p> <p>PRIVATE PROPANE SERVICE PER LOT</p>
<p><u>FIRE DEPARTMENT</u></p> <p>WILLIAMSON COUNTY E.S.D. #4 301 LOOP 332 LIBERTY HILL, TEXAS 78642 512-515-5165</p>	

* ESTIMATED FROM SERVICE AREA MAPS; THE CONTRACTOR IS ENTIRELY RESPONSIBLE FOR PROPER UTILITY NOTIFICATION OF CONSTRUCTION ACTIVITIES AND CALLING FOR "LOCATES" OF EXISTING UTILITIES WITH EACH ACTUAL UTILITY COMPANY; REGARDLESS OF WHAT IS SHOWN ON THIS SHEET OR IN THESE PLANS. NOT ALL UTILITIES PARTICIPATE IN THE TEXAS EXCAVATION SAFETY SYSTEM. CONTRACTOR TO DO HIS OWN SUB-SURFACE UTILITY RESEARCH PRIOR TO ANY CONSTRUCTION ACTIVITY

[illegible]

SCALE: 1"=2000'

GENERAL SITE NOTES:

- ALL RESPONSIBILITY FOR THE ADEQUACY OF THESE PLANS REMAINS WITH THE ENGINEER WHO PREPARED THEM. IN ACCEPTING THESE PLANS, THE CITY MUST RELY UPON THE ADEQUACY OF THE WORK OF THE DESIGN ENGINEER.

- IN THE EVENT THE CONTRACTOR OR SURVEYOR OBTAINS A DIGITAL COPY OF THE CAD FILES THAT REPRESENT THESE IMPROVEMENTS, ELI ENGINEERING AND ITS ASSOCIATES TAKE NO RESPONSIBILITY FOR THE LOCATION OF THESE IMPROVEMENTS IN ANY COORDINATE SYSTEM. DIGITAL FILES USED TO PRODUCE THESE PLANS WERE PARTIALLY CREATED BY PARTIES OTHER THAN ELI ENGINEERING AND ARE NOT INTENDED FOR USE IN CONSTRUCTION STAKING. VERTICAL AND HORIZONTAL DATA SHALL BE INDEPENDENTLY VERIFIED BY CONTRACTOR'S R.P.L.S.

- ELI ENGINEERING HAS ENDEAVORED TO DESIGN THESE PLANS COMPLIANT WITH ADA/TDLR AND OTHER ACCESSIBILITY REQUIREMENTS. HOWEVER, THE CONTRACTOR SHALL NOT BE RELIEVED OF ANY RESPONSIBILITY FOR CONSTRUCTING THESE IMPROVEMENTS COMPLIANT WITH ALL APPLICABLE ACCESSIBILITY STANDARDS. IF THE CONTRACTOR NOTICES ANY DISCREPANCIES BETWEEN THESE PLANS AND ACCESSIBILITY LAWS/RULES, HE IS TO STOP WORK IN THE AREA OF CONFLICT AND NOTIFY ELI IMMEDIATELY FOR A RESOLUTION AND/OR REVISION TO THESE PLANS. ELI SHALL NOT BE HELD RESPONSIBLE FOR CONSTRUCTING THIS SITE COMPLIANT WITH ACCESSIBILITY LAWS/RULES REGARDLESS OF WHAT IS SHOWN IN THESE PLANS.

1. COVER SHEET
2. GENERAL NOTES (1 OF 2)
3. GENERAL NOTES (2 OF 2)
4. PRELIMINARY PLAT
5. EXISTING CONDITIONS PLAN
6. EROSION AND SEDIMENTATION CONTROL PLAN
7. SPOONTS LANE PLAN AND PROFILE - STA 0+00 TO END
8. SPOONTS LANE ENTRY PLAN
9. EXISTING DRAINAGE AREA MAP
10. CONSTRUCTION DETAILS
11. CONSTRUCTION DETAILS

REVIEWED FOR COMPLIANCE WITH COUNTY REQUIREMENTS (WCSR 2021B):

WILLIAMSON COUNTY, TEXAS

DATE _____

NOTE:

THE CONTRACTOR SHALL OBTAIN A "NOTICE OF PROPOSED INSTALLATION OF UTILITY LINE" PERMIT FROM WILLIAMSON COUNTY FOR ANY WORK PERFORMED IN THE EXISTING COUNTY RIGHT-OF-WAY (DRIVEWAY APRON, WATER MAIN TIE-IN, ETC.). THIS PERMIT APPLICATION WILL REQUIRE A LICENSE FROM A CREWED AND EQUIPPED TRUCK, A TRAFFIC CONTROL WITHIN THE RIGHT-OF-WAY INCLUDING PAVEMENT REPAIR (IF NEEDED), A PERFORMANCE BOND, CONSTRUCTION PLANS AND, IF NECESSARY, A TRAFFIC CONTROL PLAN, AN INSPECTION FEE, AND A PRE-CONSTRUCTION MEETING MAY ALSO BE REQUIRED, DEPENDING ON THE SCOPE OF WORK. THE PERMIT WILL BE REVIEWED AND APPROVED BY THE WILLIAMSON COUNTY ENGINEER, AND MUST ALSO BE APPROVED BY THE WILLIAMSON COUNTY COMMISSIONERS COURT IF ANY ROAD CLOSURE IS INVOLVED.



THIS AREA IS RESERVED FOR FUTURE CITY APPROVAL STAMP

[illegible]

Feb 02, 2025

gejtexas@gmail.com



ELI ENGINEERING, PLLC.
7700 THERESA COVE, CEDAR PARK, TX 78613
512-658-8095

COUNTY OF WILLIAMSON TEXAS

SPOONTS RANCH
A PUBLIC SUBDIVISION

COVER SHEET

DRAWING SCALE:	HORIZ. = VERT. =
SURVEYED:	
FILE NAME:	
DATE:	
DRAWN:	GEJ/JTC
DESIGNED:	EEL

SHEE

1


OF

11

PROJECT No. / PERMIT#:

C:\Users\Valued Customer\Dropbox\Eli Engineering\2-Working Folder\SPOONTS RANCH\00.04-Sheets\Eli_SPOONTS_COVER.dwg Feb 02, 25 7:27 am

C:\Users\jason\Documents (Personal)\Eli Engineering\2-Working Folder\SPONTS RANCH\00-04-Subdiv\ELL SPOONTS_EX COND.dwg Jan 13, 25 1:12 pm



BENCHMARKS:

- TBM #1:**
1/2" IRON ROD FOUND ALONG SOUTH BOUNDARY OF 16.00 ACRE TOM SPOONTS REMAINDER TRACT, AND ALONG NORTH BOUNDARY OF LEON & SALLY DERRICK TRACT, 280.50' EAST OF COUNTY ROAD 282 R.O.W.
N=10203804.43
E=3049541.83
ELEV=1120.87'
- TBM #2:**
1/2" IRON ROD FOUND ALONG SOUTH BOUNDARY OF 16.00 ACRE TOM SPOONTS REMAINDER TRACT, AND AT NORTHEAST CORNER OF LEON & SALLY DERRICK TRACT, 430.96' EAST OF COUNTY ROAD 282 R.O.W.
N=10203808.71
E=3049721.75
ELEV=1118.89'
- TBM #3:**
1/2" IRON ROD FOUND AT SOUTHEAST CORNER OF MARTY HICKS TRACT, AND THE SOUTHWEST CORNER OF LUKE AND KRISTIN SPOONTS TRACT.
N=10204077.69
E=30505854.98
ELEV=1116.45'

NOTES:

- 1) NO PORTION OF THIS PROJECT LIES WITHIN ZONE "A" AND IS NOT WITHIN THE 0.2% ANNUAL CHANCE FLOODPLAIN AS IDENTIFIED WITHIN FEMA F.I.R.M. PANEL # 48491C0240F & # 48491C0245F, PREPARED FOR WILLIAMSON COUNTY ON DECEMBER 20, 2019.
- 2) THIS PROJECT LIES WITHIN THE EDWARDS AQUIFER CONTRIBUTING ZONE. THIS PROJECT DOES NOT LIE WITHIN THE EDWARDS AQUIFER RECHARGE ZONE.

28.820 ACRES:
OUT OF THE JOHN P. KIMBALL SURVEY, ABSTRACT NO. 372, IN WILLIAMSON COUNTY, TEXAS, AND BEING A PORTION OF THE FOLLOWING TRACTS: THAT CERTAIN 23.22 ACRE TRACT CONVEYED TO TOM AND WIFE BETTE SPOONTS, BY DEED OF RECORD IN VOLUME 793, PAGE 740, OF THE DEED RECORDS OF WILLIAMSON COUNTY, TEXAS, AND THAT CERTAIN 16.00 ACRE TRACT CONVEYED TO TOM L. SPOONTS, BY DEED OF RECORD IN DOCUMENT NUMBER 1997058910, OF THE OFFICIAL PUBLIC RECORDS OF WILLIAMSON COUNTY, TEXAS.

EXISTING BOUNDARY LINE TABLE		
NUMBER	BEARING	DISTANCE
L104	N36°54'30"E	199.68'
L105	S53°05'30"E	126.58'
L106	N58°23'46"W	27.53'
L107	N23°21'23"E	154.09'
L108	N76°42'19"E	128.23'
L109	N04°49'07"W	39.86'
L110	N83°02'39"E	204.44'

EXISTING BOUNDARY CURVE TABLE					
Curve	Length	Radius	Delta	Chd Direction	Chd Length
C1	232.28	780.00	17°03'45"	N64°23'18"W	231.42

LEGEND	
	EXISTING BOUNDARY LINE
	EXISTING EASEMENT
	EXISTING CONTOURS
	EXISTING CITY E.T.J. LINE
	EXISTING FLOW DIRECTION

PROJECT / PERMIT # : _____

BY : _____

REVISION : _____

DATE : _____

NO. : _____

ELI ENGINEERING

GARY ELI JONES
79198
REGISTERED PROFESSIONAL ENGINEER
Jan 13, 2025

ELI ENGINEERING, PLLC.
700 THERESA COVE, CEDAR PARK, TX 78613
312-665-8865

COUNTY OF WILLIAMSON TEXAS

SPOONTS RANCH
A PUBLIC SUBDIVISION
EXISTING CONDITIONS PLAN

HORIZ = _____
VERT = _____

DRAWING SCALE: _____

SURVEYED: _____

FILE NAME: _____

DATE: _____


DRAWN: _____

DESIGNED: _____

SHEET
5
OF
11

THIS AREA IS RESERVED FOR FUTURE CITY APPROVAL STAMP

C:\Users\jason\Documents (Personal)\ELI Engineering\2-Working Folder\Spoons Ranch\ELI_Spoons_EROSION.dwg Jan 13, 25 1:08 pm



NOTES:

1. NO EXISTING TREES ARE TO BE REMOVED FOR THIS PROJECT.
2. SEE SHEET 10 FOR EROSION AND SEDIMENTATION CONTROL DETAILS.



EROSION LEGEND	
LIMITS OF CONSTRUCTION	LOC LOC LOC
LIMITS OF CONSTRUCTION & SILT FENCE	LOC/SF
SILT FENCE	SF SF SF
STAGING AREA	
STABILIZED CONSTRUCTION ENTRANCE	
CONCRETE WASHOUT	
EXISTING FLOW DIRECTION	

LEGEND	
	PROPOSED PROPERTY LINE
	EXISTING BOUNDARY LINE
	PROPOSED SETBACK LINE
	PROPOSED EASEMENT
	EXISTING EASEMENT
	EXISTING CONTOURS
	EXISTING CITY E.T.J. LINE

PROJECT / PERMIT # : _____		BY _____
REVISION _____		DATE _____
NO. _____		DATE _____
GARY ELI JONES REGISTERED PROFESSIONAL ENGINEER Jan 13, 2025		
ELI ENGINEERING, PLLC. 700 THERESA COVE, CEDAR PARK, TX 78613 312-665-8865		
COUNTY OF WILLIAMSON, TEXAS		
SPOONS RANCH A PUBLIC SUBDIVISION		
EROSION AND SEDIMENTATION CONTROL PLAN		
DRAWING SCALE: _____	HORIZ. = _____	VERT. = _____
SURVEYED: _____	FILE NAME: _____	DATE: _____
DRAWN: _____	GE/J/JTC	DESIGNED: _____
SHEET 6 OF 11		

THIS AREA IS RESERVED FOR FUTURE CITY APPROVAL STAMP

C:\Users\jlewis\Documents (Personal)\ELI Engineering\2-Working Folder\Spoonts Ranch\00-04-Spoonts\ELI_SPOONTS_PLAN AND PROFILE.dwg Jan 13, 2015 12:58 pm



- NOTE:
1. PROPOSED SPOONTS LANE IS CLASSIFIED AS LOCAL ROAD RURAL PER WCSR B3.4.
 2. THE SPEED LIMIT FOR PROPOSED SPOONTS LANE IS 25 MPH.



ELI ENGINEERING

ELI ENGINEERING, PLLC.
700 THERESA COVE, CEDAR PARK, TX 78613
312-666-8065

geli@eliee.com

TBPELS FIRM No. 17877

COUNTY OF WILLIAMSON TEXAS

SPOONTS RANCH
A PUBLIC SUBDIVISION
SPOONTS LANE DRIVEWAY PLAN

DRAWING SCALE:	HORIZ. = NTS
SURVEYED:	VERT. = 1:1
FILE NAME:	
DATE:	
DRAWN:	GE./JTC
DESIGNED:	EE

SHEET


8

OF

11

THIS AREA IS RESERVED FOR FUTURE CITY APPROVAL STAMP

C:\Users\jason\Documents (Personal)\ELI Engineering\2-Working Folder\Spoons Ranch\ELI_Spoons_EX_DAL.dwg Jan 13, 2025 1:04 pm



Rainfall Intensity-Duration-Frequency Coefficients for Texas
Based on "National Oceanic and Atmospheric Administration's (NOAA) Atlas 14
Precipitation-Frequency Atlas of the United States, Volume 11 Version 2.0: Texas" (Perica et al. 2018)

Parameter Selection
1. **Select Units**
English
2. **Select Methodology**
Annual Maximum Series (AMS)
3. **Select County**
WILLIAMSON
4. **Select County Zone**
San Gabriel River
5. **Select Time of Concentration (t_c)**
10 Minute

Coefficient	Design Annual Exceedance Probability (Design Annual Recurrence Interval)						
	50% (2-year)	20% (5-year)	10% (10-year)	4% (25-year)	2% (50-year)	1% (100-year)	0.2% (500-year)
e	0.8119	0.8046	0.8016	0.7994	0.7991	0.7992	0.7991
b	54.2839	72.4906	87.6084	109.8397	128.9278	150.9468	213.8342
d (min)	11.4257	12.0761	12.7018	13.7038	14.6108	15.8200	19.6722
Intensity (inches/hour)	4.51	6.01	7.17	8.74	9.97	11.23	14.24

Note: Williamson County has 4 rainfall zones. Williamson County uses customized IDF zones derived by the county. Since Williamson County county has more than 1 rainfall zone, consider using the accompanying Google Earth file to accurately locate a project.

SPOONTS RANCH							
Rational Method Runoff Calculations							
AREA	ACREAGE	CONCENTRATION	TIME OF INTENSITY		RUNOFF COEFFICIENT	Q 2	Q 10
	(ac.)	(min.)	2 YR	10 YR	2 YR	10 YR	
			(in/hr)	(in/hr)			(cfs)
EX 1	0.65	10.00	4.51	7.17	0.29	0.35	0.85
							1.63

DRAINAGE LEGEND

EXISTING FLOW DIRECTION

EXISTING DRAINAGE AREA

EXISTING DRAINAGE AREA LABEL

- DRAINAGE NOTES:**
- PROPOSED DEVELOPMENT QUALIFIES FOR A DETENTION EXEMPTION BASED WILLIAMSON COUNTY SUBDIVISION REGULATION 811.13, PLATS WITH ALL LOTS OF TWO ACRES OR MORE, AND LESS THAN 20% OF IMPERVIOUS COVER PER LOT.
 - THE PROPOSED ROAD WILL BE CONSTRUCTED WITH A CROSS-SLOPE TO MAINTAIN SHEET FLOW ACROSS THE PROPERTY AT APPROXIMATE EXISTING GRADE EXCEPT FOR THE ENTRY CUT.
 - LANDSCAPING AND GRASS ON THE DOWNSLOPE EDGE OF ROAD IS REQUIRED TO BE 1.5" BELOW TOP OF RIBBON CURB.

IMPERVIOUS COVER CALCULATIONS:	
PROPOSED ROAD:	44,720 SF = 1.03 AC
PROPOSED LOTS:	11 x 7000 SF/LOT = 77,000 SF = 1.77 AC
TOTAL PROPERTY:	25.82 AC
TOTAL PROPOSED IC:	2.80 AC (10.8%)
RESIDENTIAL IC BASED ON TCEQ RG-348, TABLE 3-2	

LEGEND	
	PROPOSED PROPERTY LINE
	EXISTING BOUNDARY LINE
	PROPOSED SETBACK LINE
	PROPOSED EASEMENT
	EXISTING EASEMENT
	EXISTING CONTOURS
	EXISTING CITY E.T.J. LINE

PROJECT / PERMIT # : _____

BY : _____

REVISION : _____

DATE : _____

NO. : _____

Jan 13, 2025

ELI ENGINEERING, PLLC.
700 THERESA COVE, CEDAR PARK, TX 78613
312-665-8865

COUNTY OF WILLIAMSON TEXAS

SPOONTS RANCH
A PUBLIC SUBDIVISION
EXISTING DRAINAGE AREA MAP

DRAWING SCALE: _____

HORIZ. = _____

VERT. = _____

SURVEYED: _____

FILE NAME: _____

DATE: _____

DRAWN: GEL/JTC

DESIGNED: EE







SHEET


9

OF

11

PROJECT No. / PERMIT# : _____





Firm # 17877

December 5, 2024

Texas Commission on Environmental Quality
Region 11 Field Office (Austin)
2800 S. IH 35, Suite 100
Austin, Texas 78704

**Re: Spoonts Ranch Subdivision
Contributing Zone Plan Permit
Attachment N-Inspection, Maintenance, Repair and Retrofit Plan**

To Whom It May Concern:

A plan for the inspection, maintenance, repair, and if necessary, retrofit of the subdivision is attached. It includes procedures for documenting inspections, maintenance, repairs, and if necessary, retrofits as well as record keeping procedures. The plan has been prepared and certified by the engineer that designed the subdivision. The owner or responsible party has signed the plan.

If you have any questions or need further assistance, please contact me at 512-658-8095.

Gary Eli Jones, P.E.
Authorized Agent



Firm # 17877

December 5, 2024

Ms. Bonny Spoonts Jones
Executor of Bette Gene Spoonts Estate
700 Theresa Cove
Cedar Park, TX 78613

**Re: Spoonts Ranch Subdivision
Contributing Zone Plan
Attachment N – CZP - Operation & Maintenance Plan for BMP**

To Ms. Jones:

TCEQ requires the property owner to keep operation, maintenance, and inspections records of the BMP features including the grassy swale and vegetative buffers. There is no formal BMP structure proposed for this project, however, the maintenance guidelines provided herein will help maintain the natural benefits of the property.

General Guidelines:

- Accessibility: You should maintain accessibility to the BMP at all times. Equipment and personnel required to maintain and inspect the BMP should not be obstructed under reasonable conditions.
- Material Disposal: Stormwater pollutants include a variety of substances that can be deposited in the project. Federal and state laws and regulations may apply to the disposal of substances removed from the project. In order to dispose of substances removed from the project you must 1) characterize the waste 2) classify the waste based on character 3) properly dispose the waste according to current state (30TAC 330 or 335) and federal rules (40 CFR Subchapter C or D). The sediment must be determined inert for on-site disposal.

At a minimum, you should keep written records indicating the following:

Subject	Frequency
Pest management	Develop an integrated pest management plan for vegetated areas. Specify how problem weeds and insects will be controlled with minimal or no use of insecticides and herbicides.
Inspect swales & filters	Twice per year, once after a major rainfall event.
Inspect outlet structures	Twice per year, once after a major rainfall event.
Mow and maintain area	As needed such that grass is less than 18" tall or twice per year.
Remove sediment	Remove sediment that reaches 3 inches in depth over any spot or covers vegetation. Replace eroded areas with compacted fill and re-seed as necessary to maintain

Grassy Swales

Maintenance for grassy swales is minimal and is largely aimed at keeping the grass cover dense and vigorous. Maintenance practices and schedules should be developed and included as part of the original plans to alleviate maintenance problems in the future. Recommended practices include (modified from Young et al., 1996):

- *Pest Management.* An Integrated Pest Management (IPM) Plan should be developed for vegetated areas. This plan should specify how problem insects and weeds will be controlled with minimal or no use of insecticides and herbicides.
- *Seasonal Mowing and Lawn Care.* Lawn mowing should be performed routinely, as needed, throughout the growing season. Grass height should not exceed 18 inches. Grass cuttings should be collected and disposed of offsite, or a mulching mower can be used. Regular mowing should also include weed control practices; however, herbicide use should be kept to a minimum (Urbonas et al., 1992). Healthy grass can be maintained without using fertilizers because runoff usually contains sufficient nutrients.
- *Inspection.* Inspect swales at least twice annually for erosion or damage to vegetation; however, additional inspection after periods of heavy runoff is most desirable. The swale should be checked for uniformity of grass cover, debris and litter, and areas of sediment accumulation. More frequent inspections of the grass cover during the first few years after establishment will help to determine if any problems are developing, and to plan for long-term restorative maintenance needs. Bare spots and areas of erosion identified during semi-annual inspections should be replanted and restored to meet specifications. Construction of a level spreader device may be necessary to reestablish shallow overland flow.
- *Debris and Litter Removal.* Trash tends to accumulate in swale areas, particularly along highways. Any swale structures (i.e. check dams) should be kept free of obstructions to reduce floatables being flushed downstream, and for aesthetic reasons. The need for this practice is determined through periodic inspection, but should be performed no less than two times per year (Urbonas et al., 1992).
- *Sediment Removal.* Sediment accumulating near culverts and in channels needs to be removed when they build up to 3 inches at any spot, or cover vegetation. Excess sediment should be removed by hand or with flat-bottomed shovels. If areas are eroded, they should be filled, compacted, and reseeded so that the final grade is level with the bottom of the swale. Sediment removal should be performed periodically, as determined through inspection.
- *Grass Reseeding and Mulching.* A healthy dense grass should be maintained in the channel and side slopes. Grass damaged during the sediment removal process should be promptly replaced using the same seed mix used during swale establishment. If possible, flow should be diverted from the damaged areas until the grass is firmly established.
- *Public Education.* Private homeowners are often responsible for roadside swale maintenance. Unfortunately, overzealous lawn care on the part of homeowners can present some problems. For example, mowing the swale too close to the ground, or excessive application of fertilizer and pesticides will all be detrimental to the performance of the swale. Pet waste can also be a problem in swales, and should be removed to avoid contamination from fecal coliform and other waste-associated bacteria. The delegation of maintenance responsibilities to individual landowners is a cost benefit to the locality. However, localities should provide an active educational program to encourage the recommended practices.

Vegetative Filter Strips

Once a vegetated area is well established, little additional maintenance is generally necessary. The key to establishing a viable vegetated feature is the care and maintenance it receives in the first few months after it is planted. Once established, all vegetated BMPs require some basic maintenance to insure the health of the plants including:

- *Pest Management.* An Integrated Pest Management (IPM) Plan should be developed for vegetated areas. This plan should specify how problem insects and weeds will be controlled with minimal or no use of insecticides and herbicides.
- *Seasonal Mowing and Lawn Care.* If the filter strip is made up of turf grass, it should be mowed as needed to limit vegetation height to 18 inches, using a mulching mower (or removal of clippings). If native grasses are used, the filter may require less frequent mowing, but a minimum of twice annually. Grass clippings and brush debris should not be deposited on vegetated filter strip areas. Regular mowing should also include weed control practices, however herbicide use should be kept to a minimum (Urbonas et al., 1992). Healthy grass can be maintained without using fertilizers because runoff usually contains sufficient nutrients. Irrigation of the site can help assure a dense and healthy vegetative cover.
- *Inspection.* Inspect filter strips at least twice annually for erosion or damage to vegetation; however, additional inspection after periods of heavy runoff is most desirable. The strip should be checked for uniformity of grass cover, debris and litter, and areas of sediment accumulation. More frequent inspections of the grass cover during the first few years after establishment will help to determine if any problems are developing, and to plan for long-term restorative maintenance needs. Bare spots and areas of erosion identified during semi-annual inspections must be replanted and restored to meet specifications. Construction of a level spreader device may be necessary to reestablish shallow overland flow.
- *Debris and Litter Removal.* Trash tends to accumulate in vegetated areas, particularly along highways. Any filter strip structures (i.e. level spreaders) should be kept free of obstructions to reduce floatables being flushed downstream, and for aesthetic reasons. The need for this practice is determined through periodic inspection, but should be performed no less than 4 times per year.
- *Sediment Removal.* Sediment removal is not normally required in filter strips, since the vegetation normally grows through it and binds it to the soil. However, sediment may accumulate along the upstream boundary of the strip preventing uniform overland flow. Excess sediment should be removed by hand or with flat-bottomed shovels.
- *Grass Reseeding and Mulching.* A healthy dense grass should be maintained on the filter strip. If areas are eroded, they should be filled, compacted, and reseeded so that the final grade is level. Grass damaged during the sediment removal process should be promptly replaced using the same seed mix used during filter strip establishment. If possible, flow should be diverted from the damaged areas until the grass is firmly established. Bare spots and areas of erosion identified during semi-annual inspections must be replanted and restored to meet specifications. Corrective maintenance, such as weeding or replanting should be done more frequently in the first two to three years after installation to ensure stabilization. Dense vegetation may require irrigation immediately after planting, and during particularly dry periods, particularly as the vegetation is initially established.


All maintenance and repairs made to the BMP should be documented along with the inspection report.

Sincerely,


Concurrence & Acceptance:



Gary Eli Jones, P.E.



Bonny Spooner Jones



Firm # 17877

December 5, 2024

Texas Commission on Environmental Quality
Region 11 Field Office (Austin)
2800 S. IH 35, Suite 100
Austin, Texas 78704

**Re: Spoonts Ranch Subdivision
Contributing Zone Permit
Attachment P-Measures for Minimizing Surface Stream Contamination**

To Whom It May Concern:

The permanent BMP that is proposed is single family development with less than 20% impervious cover which in itself will minimize surface stream contamination. The measures are shown in the construction drawings and include temporary E&S controls.

If you have any questions or need further assistance, please contact me at 512-658-8095.

Gary Eli Jones, P.E.
Authorized Agent

Temporary Stormwater Section

Texas Commission on Environmental Quality

for Regulated Activities on the Edwards Aquifer Recharge Zone and Relating to 30 TAC
§213.5(b)(4)(A), (B), (D)(I) and (G); Effective June 1, 1999

To ensure that the application is administratively complete, confirm that all fields in the form are complete, verify that all requested information is provided, consistently reference the same site and contact person in all forms in the application, and ensure forms are signed by the appropriate party.

Note: Including all the information requested in the form and attachments contributes to more streamlined technical reviews.


Signature

To the best of my knowledge, the responses to this form accurately reflect all information requested concerning the proposed regulated activities and methods to protect the Edwards Aquifer. This Temporary Stormwater Section is hereby submitted for TCEQ review and executive director approval. The application was prepared by:

Print Name of Customer/Agent: Gary Eli Jones, P.E.

Date: 1/13/2025

Signature of Customer/Agent:



Regulated Entity Name: Spoons Ranch

Project Information

Potential Sources of Contamination

Examples: Fuel storage and use, chemical storage and use, use of asphaltic products, construction vehicles tracking onto public roads, and existing solid waste.

1. Fuels for construction equipment and hazardous substances which will be used during construction:

☐ The following fuels and/or hazardous substances will be stored on the site: _____

These fuels and/or hazardous substances will be stored in:

- ☐ Aboveground storage tanks with a cumulative storage capacity of less than 250 gallons will be stored on the site for less than one (1) year.

- ☐ Aboveground storage tanks with a cumulative storage capacity between 250 gallons and 499 gallons will be stored on the site for less than one (1) year.
- ☐ Aboveground storage tanks with a cumulative storage capacity of 500 gallons or more will be stored on the site. An Aboveground Storage Tank Facility Plan application must be submitted to the appropriate regional office of the TCEQ prior to moving the tanks onto the project.
- ☒ Fuels and hazardous substances will not be stored on the site.
- 2. ☒ Attachment A - Spill Response Actions. A site specific description of the measures to be taken to contain any spill of hydrocarbons or hazardous substances is attached.
- 3. ☐ Temporary aboveground storage tank systems of 250 gallons or more cumulative storage capacity must be located a minimum horizontal distance of 150 feet from any domestic, industrial, irrigation, or public water supply well, or other sensitive feature.
- 4. ☒ Attachment B - Potential Sources of Contamination. A description of any activities or processes which may be a potential source of contamination affecting surface water quality is attached.

Sequence of Construction

- 5. ☒ Attachment C - Sequence of Major Activities. A description of the sequence of major activities which will disturb soils for major portions of the site (grubbing, excavation, grading, utilities, and infrastructure installation) is attached.
 - ☒ For each activity described, an estimate (in acres) of the total area of the site to be disturbed by each activity is given.
 - ☒ For each activity described, include a description of appropriate temporary control measures and the general timing (or sequence) during the construction process that the measures will be implemented.
- 6. ☒ Name the receiving water(s) at or near the site which will be disturbed or which will receive discharges from disturbed areas of the project: S Fork San Gabriel

Temporary Best Management Practices (TBMPs)

Erosion control examples: tree protection, interceptor swales, level spreaders, outlet stabilization, blankets or matting, mulch, and sod. Sediment control examples: stabilized construction exit, silt fence, filter dikes, rock berms, buffer strips, sediment traps, and sediment basins. Please refer to the Technical Guidance Manual for guidelines and specifications. All structural BMPs must be shown on the site plan.

- 7. ☒ Attachment D – Temporary Best Management Practices and Measures. TBMPs and measures will prevent pollution of surface water, groundwater, and stormwater. The construction-phase BMPs for erosion and sediment controls have been designed to retain sediment on site to the extent practicable. The following information is attached:

- ☒ A description of how BMPs and measures will prevent pollution of surface water, groundwater or stormwater that originates upgradient from the site and flows across the site.
 - ☒ A description of how BMPs and measures will prevent pollution of surface water or groundwater that originates on-site or flows off site, including pollution caused by contaminated stormwater runoff from the site.
 - ☒ A description of how BMPs and measures will prevent pollutants from entering surface streams, sensitive features, or the aquifer.
 - ☒ A description of how, to the maximum extent practicable, BMPs and measures will maintain flow to naturally-occurring sensitive features identified in either the geologic assessment, TCEQ inspections, or during excavation, blasting, or construction.
8. ☒ The temporary sealing of a naturally-occurring sensitive feature which accepts recharge to the Edwards Aquifer as a temporary pollution abatement measure during active construction should be avoided.
- ☐ Attachment E - Request to Temporarily Seal a Feature. A request to temporarily seal a feature is attached. The request includes justification as to why no reasonable and practicable alternative exists for each feature.
 - ☒ There will be no temporary sealing of naturally-occurring sensitive features on the site.
9. ☒ Attachment F - Structural Practices. A description of the structural practices that will be used to divert flows away from exposed soils, to store flows, or to otherwise limit runoff discharge of pollutants from exposed areas of the site is attached. Placement of structural practices in floodplains has been avoided.
10. ☒ Attachment G - Drainage Area Map. A drainage area map supporting the following requirements is attached:
- ☐ For areas that will have more than 10 acres within a common drainage area disturbed at one time, a sediment basin will be provided.
 - ☐ For areas that will have more than 10 acres within a common drainage area disturbed at one time, a smaller sediment basin and/or sediment trap(s) will be used.
 - ☐ For areas that will have more than 10 acres within a common drainage area disturbed at one time, a sediment basin or other equivalent controls are not attainable, but other TBMPs and measures will be used in combination to protect down slope and side slope boundaries of the construction area.
 - ☐ There are no areas greater than 10 acres within a common drainage area that will be disturbed at one time. A smaller sediment basin and/or sediment trap(s) will be used in combination with other erosion and sediment controls within each disturbed drainage area.

- ☒ There are no areas greater than 10 acres within a common drainage area that will be disturbed at one time. Erosion and sediment controls other than sediment basins or sediment traps within each disturbed drainage area will be used.
11. ☐ Attachment H - Temporary Sediment Pond(s) Plans and Calculations. Temporary sediment pond or basin construction plans and design calculations for a proposed temporary BMP or measure have been prepared by or under the direct supervision of a Texas Licensed Professional Engineer. All construction plans and design information must be signed, sealed, and dated by the Texas Licensed Professional Engineer. Construction plans for the proposed temporary BMPs and measures are attached.
- ☒ N/A
12. ☒ Attachment I - Inspection and Maintenance for BMPs. A plan for the inspection of each temporary BMP(s) and measure(s) and for their timely maintenance, repairs, and, if necessary, retrofit is attached. A description of the documentation procedures, recordkeeping practices, and inspection frequency are included in the plan and are specific to the site and/or BMP.
13. ☒ All control measures must be properly selected, installed, and maintained in accordance with the manufacturer's specifications and good engineering practices. If periodic inspections by the applicant or the executive director, or other information indicate a control has been used inappropriately, or incorrectly, the applicant must replace or modify the control for site situations.
14. ☒ If sediment escapes the construction site, off-site accumulations of sediment must be removed at a frequency sufficient to minimize offsite impacts to water quality (e.g., fugitive sediment in street being washed into surface streams or sensitive features by the next rain).
15. ☒ Sediment must be removed from sediment traps or sedimentation ponds not later than when design capacity has been reduced by 50%. A permanent stake will be provided that can indicate when the sediment occupies 50% of the basin volume.
16. ☒ Litter, construction debris, and construction chemicals exposed to stormwater shall be prevented from becoming a pollutant source for stormwater discharges (e.g., screening outfalls, picked up daily).

Soil Stabilization Practices

Examples: establishment of temporary vegetation, establishment of permanent vegetation, mulching, geotextiles, sod stabilization, vegetative buffer strips, protection of trees, or preservation of mature vegetation.

17. ☒ Attachment J - Schedule of Interim and Permanent Soil Stabilization Practices. A schedule of the interim and permanent soil stabilization practices for the site is attached.

18. ☒ Records must be kept at the site of the dates when major grading activities occur, the dates when construction activities temporarily or permanently cease on a portion of the site, and the dates when stabilization measures are initiated.
19. ☒ Stabilization practices must be initiated as soon as practicable where construction activities have temporarily or permanently ceased.

Administrative Information

20. ☒ All structural controls will be inspected and maintained according to the submitted and approved operation and maintenance plan for the project.
21. ☒ If any geologic or manmade features, such as caves, faults, sinkholes, etc., are discovered, all regulated activities near the feature will be immediately suspended. The appropriate TCEQ Regional Office shall be immediately notified. Regulated activities must cease and not continue until the TCEQ has reviewed and approved the methods proposed to protect the aquifer from any adverse impacts.
22. ☒ Silt fences, diversion berms, and other temporary erosion and sediment controls will be constructed and maintained as appropriate to prevent pollutants from entering sensitive features discovered during construction.

ATTACHMENT “A”

Spill Response Actions

Occurrences contributing to a spill may occur during scheduled maintenance of construction equipment. There are no special potential sources of contamination with this site other than normal construction activities for site and building construction. Temporary BMPs including silt fence, rock berms, settling basin, and concrete washout will be on site prior to construction and monitored per SWPPP. Caution is to be exercised to prevent any existing ground surfaces, or new ground surfaces to become contaminated. Once the refueling staging area is no longer needed, the area is to be returned to its original condition, or better. Concrete curing compound and fuel leakage shall be contained downstream of the pond outlet structure. Contractor shall follow the steps below in preventing and responding to spills as outlined in TCEQ publication RG-348, *Technical Guidance on Best Management Practices* (Revised July 2005).

Spill Prevention and Control:

The objective of this section is to describe measures to prevent or reduce the discharge of pollutants to drainage systems or watercourses from leaks and spills by reducing the chance for spills, stopping the source of spills, containing and cleaning up spills, properly disposing of spill materials, and training employees.

The following steps will help reduce the stormwater impacts of leaks and spills:

Education

- (1) Be aware that different materials pollute in different amounts. Make sure that each employee knows what a “significant spill” is for each material they use, and what is the appropriate response for “significant” and “insignificant” spills. Employees should also be aware of when spill must be reported to the TCEQ. Information available in 30 TAC 327.4 and 40 CFR 302.4.
- (2) Educate employees and subcontractors on potential dangers to humans and the environment from spills and leaks.
- (3) Hold regular meetings to discuss and reinforce appropriate disposal procedures (incorporate into regular safety meetings).
- (4) Establish a continuing education program to indoctrinate new employees.
- (5) Have contractor’s superintendent or representative oversee and enforce proper spill prevention and control measures.

General Measures

- (1) To the extent that the work can be accomplished safely, spills of oil, petroleum products, substances listed under 40 CFR parts 110, 117, and 302, and sanitary and septic wastes should be contained and cleaned up immediately.
- (2) Store hazardous materials and wastes in covered containers and protect from vandalism.
- (3) Place a stockpile of spill cleanup materials where it will be readily accessible.
- (4) Train employees in spill prevention and cleanup.
- (5) Designate responsible individuals to oversee and enforce control measures.

(6) Spills should be covered and protected from stormwater runoff during rainfall to the extent that it doesn't compromise clean up activities.

(7) Do not bury or wash spills with water.

1-118

(8) Store and dispose of used clean up materials, contaminated materials, and recovered spill material that is no longer suitable for the intended purpose in conformance with the provisions in applicable BMPs.

(9) Do not allow water used for cleaning and decontamination to enter storm drains or watercourses. Collect and dispose of contaminated water in accordance with applicable regulations.

(10) Contain water overflow or minor water spillage and do not allow it to discharge into drainage facilities or watercourses.

(11) Place Material Safety Data Sheets (MSDS), as well as proper storage, cleanup, and spill reporting instructions for hazardous materials stored or used on the project site in an open, conspicuous, and accessible location.

(12) Keep waste storage areas clean, well organized, and equipped with ample cleanup supplies as appropriate for the materials being stored. Perimeter controls, containment structures, covers, and liners should be repaired or replaced as needed to maintain proper function.

Cleanup

(1) Clean up leaks and spills immediately.

(2) Use a rag for small spills on paved surfaces, a damp mop for general cleanup, and absorbent material for larger spills. If the spilled material is hazardous, then the used cleanup materials are also hazardous and must be disposed of as hazardous waste.

(3) Never hose down or bury dry material spills. Clean up as much of the material as possible and dispose of properly. See the waste management BMPs in this section for specific information.

Minor Spills

(1) Minor spills typically involve small quantities of oil, gasoline, paint, etc. which can be controlled by the first responder at the discovery of the spill.

(2) Use absorbent materials on small spills rather than hosing down or burying the spill.

(3) Absorbent materials should be promptly removed and disposed of properly.

(4) Follow the practice below for a minor spill:

(5) Contain the spread of the spill.

(6) Recover spilled materials.

(7) Clean the contaminated area and properly dispose of contaminated materials.

1-119

Semi-Significant Spills

Semi-significant spills still can be controlled by the first responder along with the aid of other personnel such as laborers and the foreman, etc. This response may require the cessation of all other activities.

Spills should be cleaned up immediately:

- (1) Contain spread of the spill.
- (2) Notify the project foreman immediately.
- (3) If the spill occurs on paved or impermeable surfaces, clean up using "dry" methods (absorbent materials, cat litter and/or rags). Contain the spill by encircling with absorbent materials and do not let the spill spread widely.
- (4) If the spill occurs in dirt areas, immediately contain the spill by constructing an earthen dike. Dig up and properly dispose of contaminated soil.
- (5) If the spill occurs during rain, cover spill with tarps or other material to prevent contaminating runoff.

Significant/Hazardous Spills

For significant or hazardous spills that are in reportable quantities:

- (1) Notify the TCEQ by telephone as soon as possible and within 24 hours at 512-339-2929 (Austin) or 210-490-3096 (San Antonio) between 8 AM and 5 PM. After hours, contact the Environmental Release Hotline at 1-800-832-8224. It is the contractor's responsibility to have all emergency phone numbers at the construction site.
 - (2) For spills of federal reportable quantities, in conformance with the requirements in 40 CFR parts 110, 119, and 302, the contractor should notify the National Response Center at (800) 424-8802.
 - (3) Notification should first be made by telephone and followed up with a written report.
 - (4) The services of a spills contractor or a Haz-Mat team should be obtained immediately. Construction personnel should not attempt to clean up until the appropriate and qualified staffs have arrived at the job site.
 - (5) Other agencies which may need to be consulted include, but are not limited to, the City Police Department, County Sheriff Office, Fire Departments, etc.
- More information on spill rules and appropriate responses is available on the TCEQ website at: <https://www.tceq.texas.gov/response/spills>.

Vehicle and Equipment Maintenance

- (1) If maintenance must occur onsite, use a designated area and a secondary containment, located away from drainage courses, to prevent the runoff of stormwater and the runoff of spills.
- (2) Regularly inspect onsite vehicles and equipment for leaks and repair immediately.
- (3) Check incoming vehicles and equipment (including delivery trucks, and employee and subcontractor vehicles) for leaking oil and fluids. Do not allow leaking vehicles or equipment onsite.
- (4) Always use secondary containment, such as a drain pan or drop cloth, to catch spills or leaks when removing or changing fluids.
- (5) Place drip pans or absorbent materials under paving equipment when not in use.
- (6) Use absorbent materials on small spills rather than hosing down or burying the spill. Remove the absorbent materials promptly and dispose of properly.
- (7) Promptly transfer used fluids to the proper waste or recycling drums. Don't leave full drip pans or other open containers lying around.
- (8) Oil filters disposed of in trashcans or dumpsters can leak oil and pollute

stormwater. Place the oil filter in a funnel over a waste oil-recycling drum to drain excess oil before disposal. Oil filters can also be recycled. Ask the oil supplier or recycler about recycling oil filters.

(9) Store cracked batteries in a non-leaking secondary container. Do this with all cracked batteries even if you think all the acid has drained out. If you drop a battery, treat it as if it is cracked. Put it into the containment area until you are sure it is not leaking.

Vehicle and Equipment Fueling

(1) If fueling must occur on site, use designated areas, located away from drainage courses, to prevent the runoff of stormwater and the runoff of spills.

(2) Discourage “topping off” of fuel tanks.

(3) Always use secondary containment, such as a drain pan, when fueling to catch spills/ leaks.

Concrete Washout Areas

The purpose of concrete washout areas is to prevent or reduce the discharge of pollutants to stormwater from concrete waste by conducting washout offsite, performing onsite washout in a designated area, and training employees and subcontractors.

The following steps will help reduce stormwater pollution from concrete wastes:

- Incorporate requirements for concrete waste management into material supplier and subcontractor agreements.
- Avoid mixing excess amounts of fresh concrete.
- Perform washout of concrete trucks in designated areas only.
- Do not wash out concrete trucks into storm drains, open ditches, streets, or streams.
- Do not allow excess concrete to be dumped onsite, except in designated areas.

For onsite washout:

- Locate washout area at least 50 feet from sensitive features, storm drains, open ditches, or water bodies. Do not allow runoff from this area by constructing a temporary pit or bermed area large enough for liquid and solid waste.
- Wash out wastes into the temporary pit where the concrete can set, be broken up, and then disposed properly.

Below grade concrete washout facilities are typical. These consist of a lined excavation sufficiently large to hold expected volume of washout material. Above grade facilities are used if excavation is not practical. Temporary concrete washout facility (type above grade) should be constructed as shown on the details at the end of this section, with sufficient quantity and volume to contain all liquid and concrete waste generated by washout operations. Plastic lining material should be a minimum of 10 mil in polyethylene sheeting and should be free of holes, tears, or other defects that compromise the impermeability of the material.

When temporary concrete washout facilities are no longer required for the work, the hardened concrete should be removed and disposed of. Materials used to construct temporary concrete washout facilities should be removed from the site of the work and disposed of. Holes, depressions or other ground disturbance caused by the removal of the temporary concrete washout facilities should be backfilled and repaired.




Figure: Schematics of Concrete Washout Areas

REPORTABLE QUANTITIES (RQ)

Refer to: (https://www.tceq.texas.gov/response/spills/spill_rq.html)

Kind of spill	Where discharged	Reportable quantity	Rule, statute, or responsible agency
Hazardous substance	onto land	"Final RQ" in Table 302.4 in 40 CFR 302.4 (PDF)	30 TAC 327 ↗
	into water	"Final RQ" or 100 lbs, whichever is less	
Any oil	coastal waters	as required by the Texas General Land Office	Texas General Land Office ↗
Crude oil, oil that is neither a petroleum product nor used oil	onto land	210 gallons (five barrels)	30 TAC 327 ↗
	directly into water	enough to create a sheen	
Petroleum product, used oil	onto land, from an exempt PST facility	210 gallons (five barrels)	30 TAC 327 ↗
	onto land, or onto land from a non-exempt PST facility	25 gallons	
	directly into water	enough to create a sheen	
Associated with the exploration, development and production of oil, gas, or geothermal resources	under the jurisdiction of the Railroad Commission of Texas	as required by the Railroad Commission of Texas	Railroad Commission of Texas ↗
Industrial solid waste or other substances	into water	100 lbs	30 TAC 327 ↗
From petroleum storage tanks, underground or aboveground	into water	enough to create a sheen on water	30 TAC 334 ↗ , 75-81
From petroleum storage tanks, underground or aboveground	onto land	25 gallons or equal to the RQ under 40 CFR 302 ↗	30 TAC 327 ↗
Other substances that may be useful or valuable and are not ordinarily considered to be waste, but will cause pollution if discharged into water in the state	into water	100 lbs	30 TAC 327 ↗

ATTACHMENT “B”

Potential Sources of Contamination

Occurrences contributing to a spill may occur during scheduled maintenance of construction equipment. There are no special potential sources of contamination with this site other than normal construction activities for site and building construction. Temporary BMPs including construction entrance, silt fence and concrete washout will be on site prior to construction and monitored per SWPPP. Caution is to be exercised to prevent any existing ground surfaces, or new ground surfaces to become contaminated. Once the refueling staging area is no longer needed, the area is to be returned to its original condition, or better. Concrete curing compound and fuel leakage shall be contained downstream of the pond outlet structure. Contractor shall follow the steps below in preventing and responding to spills as outlined in TCEQ publication RG-348, *Technical Guidance on Best Management Practices* (Revised July 2005).

ATTACHMENT "C"

Sequence of Major Activities

<u>Description</u>	<u>Area (acres)</u>
1. Install all erosion control	2.80
2. Conduct pre-construction conference	N/A
3. Establish subgrade on site	1.03
4. Process and compact subgrade to final grades	1.03
5. Install paving	1.03
6. Re-vegetate all disturbed areas	1.12
7. Grading of Lots and home construction (Lot Grading will be done with Home Construction)	1.77
8. Remove temporary erosion control subsequent to establishment of vegetation	2.80

ATTACHMENT “D”

Temporary Best Management Practices

Silt fence will be installed to intercept storm water runoff originating within the project, prior to discharge to existing drainage conveyances. Existing drainage patterns and sheet flow will be maintained for this low density residential project.

A stabilized construction entrance will be installed off of CR 282 to minimize construction vehicles transporting sediment onto neighboring roadways. This site contains no surface streams.

There will be a concrete washout on site for concrete trucks and a temporary staging & storage area to utilize during construction.

ATTACHMENT “F”

Structural Practices

Since this project will be using ribbon curb and maintaining sheet flow, there are no structural practices required. All unpaved areas will be re-vegetated according to TCEQ Specifications for re-vegetation of disturbed areas.

ATTACHMENT “G”

Drainage Area Map

Included in the attached Set of Construction Plans. There are no areas greater than 10 acres that will be disturbed at one time. Per Williamson County Drainage criteria, there is no pond required for this subdivision based on a minimum two (2) acre lots and less than 20% impervious cover. The Drainage Area Map showing the existing conditions is included in the Construction Plan Set.

ATTACHMENT “I”

Inspection & Maintenance for Temporary BMPs

SUMMARY OF EROSION AND SEDIMENT CONTROL MAINTENANCE/INSPECTION PROCEDURES

Silt Fence Inspection and Maintenance Guidelines:

- (1) Inspect all fencing weekly, and after any rainfall.
- (2) Remove sediment when buildup reaches 6 inches.
- (3) Replace any torn fabric or install a second line of fencing parallel to the torn section.
- (4) Replace or repair any sections crushed or collapsed in the course of construction activity. If a section of fence is obstructing vehicular access, consider relocating it to a spot where it will provide equal protection, but will not obstruct vehicles. A triangular filter dike may be preferable to a silt fence at common vehicle access points.
- (5) When construction is complete, the sediment should be disposed of in a manner that will not cause additional siltation and the prior location of the silt fence should be revegetated. The fence itself should be disposed of in an approved landfill.

Temporary Construction Entrance/Exit Inspection and Maintenance Guidelines:

- (1) The entrance should be maintained in a condition, which will prevent tracking or flowing of sediment onto public rights-of-way. This may require periodic top dressing with additional stone as conditions demand and repair and/or cleanout of any measures used to trap sediment.
 - (2) All sediment spilled, dropped, washed or tracked onto public rights-of-way should be removed immediately by contractor.
 - (3) When necessary, wheels should be cleaned to remove sediment prior to entrance onto public right-of-way.
 - (4) When washing is required, it should be done on an area stabilized with crushed stone that drains into an approved sediment trap or sediment basin.
 - (5) All sediment should be prevented from entering any storm drain, ditch or water course by using approved methods.
- Temporary and permanent seeding and planting will be inspected for bare spots, washouts, and healthy growth.
 - A maintenance inspection report will be made after each inspection. A copy of the report forms to be used are included in this WPAP.
 - The site job superintendent will select the individuals who will be responsible for inspections, maintenance and repair activities, and filling out the inspection and maintenance reports.
 - Personnel selected for inspection and maintenance responsibilities will receive training from the site job superintendent. They will be trained in all the inspection and maintenance practices necessary for keeping the erosion and sediment controls used onsite in good working order.

FINAL STABILIZATION/TERMINATION CHECKLIST

1. All soil disturbing activities are complete
2. Temporary erosion and sediment control measures have been removed or will be removed at an appropriate time.
3. All areas of the construction site not otherwise covered by a permanent pavement or structure have been stabilized with a uniform perennial vegetative cover with a density of 70% or equivalent measures have been employed.

**CONTRIBUTING ZONE (CZP)
INSPECTION AND MAINTENANCE REPORT FORM**

STABILIZATION MEASURES

INSPECTOR: _____ DATE: _____

QUALIFICATIONS OF INSPECTOR:

DAYS SINCE LAST RAINFALL: _____ AMOUNT OF LAST RAINFALL: _____

AREA	DATE SINCE LAST RAINFALL	DATE OF NEXT DISTURBANCE	STABILIZED? (YES/NO)	STABILIZED WITH	CONDITION

STABILIZATION REQUIRED:

TO BE PERFORMED BY: _____ ON OR BEFORE: _____

**CONTRIBUTING ZONE (CZP)
INSPECTION AND MAINTENANCE REPORT FORM**

SILT FENCE

INSPECTOR: _____ DATE: _____

QUALIFICATIONS OF INSPECTOR:

DAYS SINCE LAST RAINFALL: _____ AMOUNT OF LAST RAINFALL: _____

IS THE BOTTOM OF THE FABRIC STILL BURIED? _____

IS THE FABRIC TORN OR SAGGING? _____

ARE THE POSTS TIPPED OVER? _____

HOW DEEP IS THE SEDIMENT? _____

MAINTENANCE REQUIRED FOR SILT FENCE: _____

TO BE PERFORMED BY: _____ ON OR BEFORE: _____

**CONTRIBUTING ZONE (CZP)
INSPECTION AND MAINTENANCE REPORT FORM**

STABILIZED CONSTRUCTION EXIT

INSPECTOR: _____ DATE: _____

QUALIFICATIONS OF INSPECTOR:

DAYS SINCE LAST RAINFALL: _____ AMOUNT OF LAST RAINFALL: _____

DOES MUCH SEDIMENT GET TRACKED ON TO ROAD? _____

IS THE GRAVEL CLEAN OR FILLED WITH SEDIMENT? _____

DOES ALL TRAFFIC USE THE STABILIZED EXIT TO LEAVE THE JOB SITE? _____

IS THE CULVERT BENEATH THE EXIT WORKING? _____

MAINTENANCE REQUIRED FOR STABILIZED CONSTRUCTION EXIT: _____

TO BE PERFORMED BY: _____ ON OR BEFORE: _____

ATTACHMENT “J”

Schedule of Interim and Permanent Soil Stabilization Practices

All areas within the project limits that are disturbed during construction will be revegetated and restabilized immediately following construction activities. Stabilization measures shall be initiated as soon as practicable in portions of the site where construction activities have temporarily or permanently ceased, but in no case more than 14 days after the construction activity in that portion of the site has temporarily or permanently ceased. Where the initiation of stabilization measures by the 14th day after construction activity temporary or permanently cease is precluded by weather conditions, stabilization measures shall be initiated as soon as practicable. Where construction activity on a portion of the site is temporarily ceased, and earth disturbing activities will be resumed within 21 days, temporary stabilization measures do not have to be initiated on that portion of site. In areas experiencing droughts where the initiation of stabilization measures by the 14th day after construction activity has temporarily or permanently ceased is precluded by seasonal arid conditions, stabilization measures shall be initiated as soon as practicable.

Agent Authorization Form
For Required Signature
Edwards Aquifer Protection Program
Relating to 30 TAC Chapter 213
Effective June 1, 1999

I _____ Bonny Spoonts Jones _____
Print Name

_____ Executrix _____
Title - Owner/President/Other

of _____ Bette Gene Spoonts Estate _____
Corporation/Partnership/Entity Name

have authorized _____ Gary Eli Jones, P.E. _____
Print Name of Agent/Engineer

of _____ Eli Engineering, PLLC _____
Print Name of Firm

to represent and act on the behalf of the above named Corporation, Partnership, or Entity for the purpose of preparing and submitting this plan application to the Texas Commission on Environmental Quality (TCEQ) for the review and approval consideration of regulated activities.

I also understand that:

1. The applicant is responsible for compliance with 30 Texas Administrative Code Chapter 213 and any condition of the TCEQ's approval letter. The TCEQ is authorized to assess administrative penalties of up to \$10,000 per day per violation.
2. For those submitting an application who are not the property owner, but who have the right to control and possess the property, additional authorization is required from the owner.
3. Application fees are due and payable at the time the application is submitted. The application fee must be sent to the TCEQ cashier or to the appropriate regional office. The application will not be considered until the correct fee is received by the commission.
4. A notarized copy of the Agent Authorization Form must be provided for the person preparing the application, and this form must accompany the completed application.
5. No person shall commence any regulated activity on the Edwards Aquifer Recharge Zone, Contributing Zone or Transition Zone until the appropriate application for the activity has been filed with and approved by the Executive Director.

SIGNATURE PAGE:


Applicant's Signature


1/13/25
Date

THE STATE OF TEXAS §

County of WILLIAMSON §

BEFORE ME, the undersigned authority, on this day personally appeared Bonny Spoonts Jones, known to me to be the person whose name is subscribed to the foregoing instrument, and acknowledged to me that (s)he executed same for the purpose and consideration therein expressed.

GIVEN under my hand and seal of office on this 13th day of January, 2025



Kaur
NOTARY PUBLIC
Navpreet Kaur
Typed or Printed Name of Notary

MY COMMISSION EXPIRES: Aug 1, 2028

Application Fee Form

Texas Commission on Environmental Quality

Name of Proposed Regulated Entity: Spoons Ranch

Regulated Entity Location: 700 Theresa Cove

Name of Customer: Bette Gene Spoons Estate

Contact Person: Bonny Spoons Jones

Phone: 512-422-1972

Customer Reference Number (if issued):CN _____

Regulated Entity Reference Number (if issued):RN _____

Austin Regional Office (3373)

☐ Hays

☐ Travis

☒ Williamson

San Antonio Regional Office (3362)

☐ Bexar

☐ Medina

☐ Uvalde

☐ Comal

☐ Kinney

Application fees must be paid by check, certified check, or money order, payable to the Texas Commission on Environmental Quality. Your canceled check will serve as your receipt. This form must be submitted with your fee payment. This payment is being submitted to:

☒ Austin Regional Office

☐ San Antonio Regional Office

☐ Mailed to: TCEQ - Cashier

☐ Overnight Delivery to: TCEQ - Cashier

Revenues Section

Mail Code 214

P.O. Box 13088

Austin, TX 78711-3088

12100 Park 35 Circle

Building A, 3rd Floor

Austin, TX 78753

(512)239-0357

Site Location (Check All That Apply):

☐ Recharge Zone

☒ Contributing Zone

☐ Transition Zone

<i>Type of Plan</i>	<i>Size</i>	<i>Fee Due</i>
Water Pollution Abatement Plan, Contributing Zone Plan: One Single Family Residential Dwelling	Acres	\$
Water Pollution Abatement Plan, Contributing Zone Plan: Multiple Single Family Residential and Parks	25.82 Acres	\$ 4000
Water Pollution Abatement Plan, Contributing Zone Plan: Non-residential	Acres	\$
Sewage Collection System	L.F.	\$
Lift Stations without sewer lines	Acres	\$
Underground or Aboveground Storage Tank Facility	Tanks	\$
Piping System(s)(only)	Each	\$
Exception	Each	\$
Extension of Time	Each	\$

Signature: Gary Eli Jones

Date: 11/29/2024

Application Fee Schedule

Texas Commission on Environmental Quality

Edwards Aquifer Protection Program 30 TAC Chapter 213 (effective 05/01/2008)

Water Pollution Abatement Plans and Modifications

Contributing Zone Plans and Modifications

<i>Project</i>	<i>Project Area in Acres</i>	<i>Fee</i>
One Single Family Residential Dwelling	< 5	\$650
Multiple Single Family Residential and Parks	< 5	\$1,500
	5 < 10	\$3,000
	10 < 40	\$4,000
	40 < 100	\$6,500
	100 < 500	\$8,000
	≥ 500	\$10,000
Non-residential (Commercial, industrial, institutional, multi-family residential, schools, and other sites where regulated activities will occur)	< 1	\$3,000
	1 < 5	\$4,000
	5 < 10	\$5,000
	10 < 40	\$6,500
	40 < 100	\$8,000
	≥ 100	\$10,000

Organized Sewage Collection Systems and Modifications

<i>Project</i>	<i>Cost per Linear Foot</i>	<i>Minimum Fee- Maximum Fee</i>
Sewage Collection Systems	\$0.50	\$650 - \$6,500

Underground and Aboveground Storage Tank System Facility Plans and Modifications

<i>Project</i>	<i>Cost per Tank or Piping System</i>	<i>Minimum Fee- Maximum Fee</i>
Underground and Aboveground Storage Tank Facility	\$650	\$650 - \$6,500

Exception Requests

<i>Project</i>	<i>Fee</i>
Exception Request	\$500

Extension of Time Requests

<i>Project</i>	<i>Fee</i>
Extension of Time Request	\$150



TCEQ Use Only

TCEQ Core Data Form

For detailed instructions regarding completion of this form, please read the Core Data Form Instructions or call 512-239-5175.

SECTION I: General Information

1. Reason for Submission <i>(If other is checked please describe in space provided.)</i>		
<input checked="" type="checkbox"/> New Permit, Registration or Authorization <i>(Core Data Form should be submitted with the program application.)</i>		
<input type="checkbox"/> Renewal <i>(Core Data Form should be submitted with the renewal form)</i>	<input type="checkbox"/> Other	
2. Customer Reference Number <i>(if issued)</i>	Follow this link to search for CN or RN numbers in Central Registry**	3. Regulated Entity Reference Number <i>(if issued)</i>
CN		RN

SECTION II: Customer Information

4. General Customer Information		5. Effective Date for Customer Information Updates (mm/dd/yyyy)		05/21/2021	
<input checked="" type="checkbox"/> New Customer <input type="checkbox"/> Update to Customer Information <input type="checkbox"/> Change in Regulated Entity Ownership					
<input type="checkbox"/> Change in Legal Name (Verifiable with the Texas Secretary of State or Texas Comptroller of Public Accounts)					
<i>The Customer Name submitted here may be updated automatically based on what is current and active with the Texas Secretary of State (SOS) or Texas Comptroller of Public Accounts (CPA).</i>					
6. Customer Legal Name <i>(If an individual, print last name first: eg: Doe, John)</i>				<i>If new Customer, enter previous Customer below:</i>	
Bette Gene Spoons Estate					
7. TX SOS/CPA Filing Number		8. TX State Tax ID (11 digits)		9. Federal Tax ID (9 digits)	
				85-6433319	
10. DUNS Number <i>(if applicable)</i>					
11. Type of Customer:		<input checked="" type="checkbox"/> Corporation		<input type="checkbox"/> Individual	
				Partnership: <input type="checkbox"/> General <input type="checkbox"/> Limited	
Government: <input type="checkbox"/> City <input type="checkbox"/> County <input type="checkbox"/> Federal <input type="checkbox"/> State <input type="checkbox"/> Other		<input type="checkbox"/> Sole Proprietorship		<input type="checkbox"/> Other:	
12. Number of Employees		<input checked="" type="checkbox"/> 0-20 <input type="checkbox"/> 21-100 <input type="checkbox"/> 101-250 <input type="checkbox"/> 251-500 <input type="checkbox"/> 501 and higher		13. Independently Owned and Operated?	
				<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	
14. Customer Role (Proposed or Actual) – as it relates to the Regulated Entity listed on this form. Please check one of the following:					
<input checked="" type="checkbox"/> Owner <input type="checkbox"/> Operator <input type="checkbox"/> Owner & Operator					
<input type="checkbox"/> Occupational Licensee <input type="checkbox"/> Responsible Party <input type="checkbox"/> Voluntary Cleanup Applicant <input type="checkbox"/> Other:					
15. Mailing Address:					
700 Theresa Cove					
City		Cedar Park		State	TX
ZIP		78613		ZIP + 4	
16. Country Mailing Information <i>(if outside USA)</i>				17. E-Mail Address <i>(if applicable)</i>	
				Jonesfamily.Austin@gmail.com	
18. Telephone Number		19. Extension or Code		20. Fax Number <i>(if applicable)</i>	
(512) 422-1972				() -	

SECTION III: Regulated Entity Information

21. General Regulated Entity Information <i>(If 'New Regulated Entity' is selected below this form should be accompanied by a permit application)</i>	
<input checked="" type="checkbox"/> New Regulated Entity <input type="checkbox"/> Update to Regulated Entity Name <input type="checkbox"/> Update to Regulated Entity Information	
<i>The Regulated Entity Name submitted may be updated in order to meet TCEQ Agency Data Standards (removal of organizational endings such as Inc, LP, or LLC.)</i>	
22. Regulated Entity Name <i>(Enter name of the site where the regulated action is taking place.)</i>	
SPOONTS RANCH SUBDIVISION	

23. Street Address of the Regulated Entity: <i>(No PO Boxes)</i>	496 Spoons Lane							
	City	Liberty Hill	State	TX	ZIP	78642	ZIP + 4	
24. County	Williamson							
Enter Physical Location Description if no street address is provided.								
25. Description to Physical Location:	Located ~1800 ft NE of CR 283 on CR 282							
26. Nearest City	Liberty Hill				State	TX	Nearest ZIP Code 78642	
27. Latitude (N) In Decimal:	30.634572		28. Longitude (W) In Decimal:	-97.940934				
Degrees	Minutes	Seconds	Degrees	Minutes	Seconds			
30	38	4.4592	97	56	27.3624			
29. Primary SIC Code (4 digits)	30. Secondary SIC Code (4 digits)		31. Primary NAICS Code (5 or 6 digits)		32. Secondary NAICS Code (5 or 6 digits)			
1521			236115					
33. What is the Primary Business of this entity? <i>(Do not repeat the SIC or NAICS description.)</i>								
Single Family Residential								
34. Mailing Address:	700 Theresa Cove							
	City	Cedar Park	State	TX	ZIP	78613	ZIP + 4	
35. E-Mail Address:	mallik246@gmail.com							
36. Telephone Number		37. Extension or Code		38. Fax Number <i>(if applicable)</i>				
(512) 422-1972				() -				

39. TCEQ Programs and ID Numbers Check all Programs and write in the permits/registration numbers that will be affected by the updates submitted on this form. See the Core Data Form instructions for additional guidance.


<input type="checkbox"/> Dam Safety	<input type="checkbox"/> Districts	<input type="checkbox"/> Edwards Aquifer	<input type="checkbox"/> Emissions Inventory Air	<input type="checkbox"/> Industrial Hazardous Waste
<input type="checkbox"/> Municipal Solid Waste	<input type="checkbox"/> New Source Review Air	<input type="checkbox"/> OSSF	<input type="checkbox"/> Petroleum Storage Tank	<input type="checkbox"/> PWS
<input type="checkbox"/> Sludge	<input type="checkbox"/> Storm Water	<input type="checkbox"/> Title V Air	<input type="checkbox"/> Tires	<input type="checkbox"/> Used Oil
<input type="checkbox"/> Voluntary Cleanup	<input type="checkbox"/> Waste Water	<input type="checkbox"/> Wastewater Agriculture	<input type="checkbox"/> Water Rights	<input type="checkbox"/> Other:

SECTION IV: Preparer Information

40. Name:	Gary Eli Jones	41. Title:	Design Engineer
42. Telephone Number	43. Ext./Code	44. Fax Number	45. E-Mail Address
(512) 658-8095		() -	gejtexas@gmail.com

SECTION V: Authorized Signature

46. By my signature below, I certify, to the best of my knowledge, that the information provided in this form is true and complete, and that I have signature authority to submit this form on behalf of the entity specified in Section II, Field 6 and/or as required for the updates to the ID numbers identified in field 39.

Company:	Eli Engineering, PLLC	Job Title:	Design Engineer
Name <i>(In Print)</i> :	Gary Eli Jones	Phone:	(512) 658-8095
Signature:		Date:	1/10/2022